ADVANCED DURABILITY FOR DURABILITY F







Featured: LP® SmartSide® Cedar Texture Lap, Soffit, Cedar Shake, Trim & Fascia





ExpertFinish[®] TRIM & SIDING

IP SmartSide[®]

Product Guide & Specifications



ABOUT LP® SMARTSIDE® TRIM & SIDING

Durability	03
Workability	05
Sustainability	07
Beauty	09

PRODUCTS

ExpertFinish [®]	13
Lap Siding	17
Nickel Gap Siding	18
Shakes	19
Soffit	20
Panel & Vertical Siding	21
Trim & Fascia	22
Accessories	23
Primed LP SmartSide	25
Primed Products	28

APPLICATIONS

New Home	31
Remodel	32
Outdoor Building Solutions	33
Multifamily	34

SPECIFICATIONS

ExpertFinish Trim & Siding	37
Cedar Texture Lap Siding	71
Lap Siding Coverage Chart	72
Brushed Smooth Lap Siding	73
Lap Siding Coverage Chart	74
Nickel Gap Siding	75
Pebbled Stucco Panel Siding	76
Cedar Texture Shakes	77
Shakes Coverage Chart	78
Cedar Texture Panel Siding	79
Brushed Smooth Panel Siding	81
Panel Siding Coverage Chart	82
Cedar Texture Trim	83
Brushed Smooth Trim	84
Cedar Texture Soffit	85
Brushed Smooth Soffit	86
Cedar Texture Vented Soffit	87
Brushed Smooth Vented Soffit	88
Vertical Siding	89
Vertical Siding Coverage Chart	90
Accessories	91

29 35

ROURBANGE

With over 20 years of successful performance, it's easy to see why the LP® SmartSide® brand is one of the fastest-growing brands for trim & siding products in the United States.


A PIONEER OF CHANGE

LP has redefined traditional building materials with treated engineered wood products that are designed to offer game-changing durability, beauty and workability. LP is a building industry leader in a category that's shaping the way homes, outdoor building structures and light commercial properties are being built.

See the innovation that goes into making LP SmartSide products at YouTube.com/LPSmartSide.



BECAUSE STRENGTH IS MAKE OR BREAK



A NATURAL DEFENSE AGAINST NATURE

Featured: LP[®] SmartSide[®] ExpertFinish[®] Panel Siding & Trim in Tundra G

All LP® SmartSide® products are treated to the core through our proprietary LP® SmartGuard® manufacturing process. With a carefully formulated mix of resins, waxes and zinc borate, the SmartGuard process adds strength and helps LP SmartSide products offer protection against hail damage and moisture intrusion as well as resistance to termites and fungal decay.

See more about how LP SmartSide products are made at YouTube.com/LPSmartSide

OUTSTANDING IMPACT RESISTANCE

In a study commissioned by LP, researchers determined that LP® SmartSide[®] cedar lap siding resists impact better than vinyl and fiber cement siding, which means that it can stand up better against everything from everyday bumps to storm debris.

And because of LP SmartSide siding's durability, it doesn't break easily and results in less waste.

HAIL AND WIND RESISTANCE

Results of third-party testing commissioned by LP Building Solutions demonstrate that LP SmartSide cedar texture lap siding resists hail damage better than fiber cement and vinyl. In fact, the LP SmartSide warranty covers impacts from hail up to 1.75 inches in diameter. LP SmartSide lap siding is also designed to withstand tough storms with wind gusts of up to 200 miles per hour. Refer to ESR-1301 or PR-N124.



FOUR COMPONENTS OF PROTECTION

LP's proprietary SmartGuard manufacturing process helps ensure that every LP SmartSide Trim & Siding product is treated with an advanced formula of adhesive resins, waterresistant waxes and zinc borate, after which a water-resistant, resin-saturated overlay is bonded to the product. The result: four components of protection against water damage, termites and fungal decay.



BACKED BY STRONG WARRANTIES

LP has your back with an industry-leading transferable prorated limited warranty for LP SmartSide products: a 50-year limited warranty for the substrate and 100% labor and material in the first 5 years. LP® SmartSide® ExpertFinish® Trim & Siding products include an additional 15-year limited warranty for the finish.

RESISTANCE TO FUNGAL DECAY AND TERMITES

Since 1996, LP SmartSide siding has undergone brutal testing in Hilo, Hawaii. An average temperature of more than 70 degrees, high levels of humidity, and almost 170 inches of annual rainfall make Hilo's climate the perfect breeding ground for termites, moisture and fungal decay. Yet our Exterior Exposure Program continues to validate that LP SmartSide siding performs over time.



ENGINEERED FOR FASTER & EASIER INSTALLATIONS

LP® SmartSide® products help you build with greater efficiency on the jobsite. From longer lengths to advanced durability, the math is simple—using LP SmartSide products can help boost your bottom line so you can install siding on more homes in less time.

Featured: LP® SmartSide® ExpertFinish® Panel Siding, Lap Siding & Trim

PUTTING LP® SMARTSIDE® PRODUCTS TO THE TEST

With RSMeans, a trusted third-party construction data company, we tested the productivity of LP SmartSide products and LP[®] SmartSide[®] ExpertFinish[®] products against comparable fiber cement products to find out which helps you install faster and reduce build cycles.

THE RESULTS

Primed LP SmartSide Products vs. Fiber Cement

- LP SmartSide lap installs faster
- LP SmartSide trim installs faster



LP SmartSide ExpertFinish vs. Prefinished Fiber Cement

- LP SmartSide ExpertFinish lap installs faster
- LP SmartSide ExpertFinish trim installs faster

THE LP SMARTSIDE DIFFERENCE



ed: LP[®] SmartSide[®] Panel Siding & Trim

Lighter Weights: LP SmartSide Lap Siding is 45% lighter weight per square foot than fiber cement.

See more about how LP SmartSide products stack up to the competition at LPCorp.com/Proven-Productivity

THE BOTTOM LINE

With lighter weights per square foot, longer lengths and advanced durability, LP SmartSide trim & lap siding installs faster than fiber cement trim & lap siding.





Longer Lengths:

LP SmartSide Lap Siding's 16foot lengths may lead to fewer seams and cuts compared to fiber cement's 12-foot lengths.

SIDING FOR FOR A MORE SUSTAINABLE WORLD

LP[®] SmartSide[®] Trim & Siding products are must-have materials to help builders qualify for sustainable building programs. In fact, the LP SmartSide full product portfolio represents one of the only carbon-negative siding options on the market, making it a great solution for clients who desire sustainable products with minimal impact on our environment.



Featured: LP[®] SmartSide[®] ExpertFinish[®] Panel Siding & Trim in Aby

Featured: LP® SmartSide® ExpertFinish® Panel Siding & Trim in Abyss Black

We're not just building for the future; we're helping to protect it by using Sustainable Forestry Initiative[®] (SFI) certified forest management and fiber sourcing systems to help ensure that our wood comes from well-managed forests.

INHERENTLY SUSTAINABLE

The LP[®] SmartSide[®] manufacturing process begins with wood, a renewable resource, grown and gathered responsibly under strict SFI standards. We utilize 99% of all wood fiber that enters our manufacturing facilities either in our products or as an alternative renewable energy source to offset fossil fuel consumption.



A DURABLE CARBON-NEGATIVE SIDING OPTION

The amount of carbon dioxide emitted from raw material sourcing, manufacturing, shipping, and average end-of-life of LP SmartSide is less than the amount stored over its lifetime, qualifying it as carbon negative. In fact, LP SmartSide Trim & Siding produces 54% less greenhouse gas emissions during manufacturing as compared to fiber cement-based siding products.



Learn more about LP's sustainability story at LPCorp.com/Sustainability

A BEAUTIFUL SOLUTION FROM THE INSIDE OUT

BOOST CURB APPEAL WITH TIMELESS DESIGNS

Siding plays a big role in a home's curb appeal and overall aesthetic. That's why LP® SmartSide® Trim & Siding is designed to make almost any home's design vision come to life—and longer lasting. With its variety of textures, styles and ExpertFinish® colors, LP SmartSide products elevate almost any structure—from traditional homes to modern masterpieces. Its versatility also offers endless options for designs that stand out, making it a siding of choice for over 20 years for homeowners who want distinctive beauty and amazing quality.



GIVE YOUR VISION THE FINISHING TOUCH

Choose your style. Choose your color. Get the look you want—that's the beauty of working with LP[®] SmartSide[®] engineered wood siding products. Available in prefinished and primed options, LP SmartSide Trim & Siding offers the versatility you need to achieve stunning results with ease.

WHICH PRODUCT COLLECTION FITS YOUR NEEDS?

LP SmartSide products are available in prefinished ExpertFinish® colors and primed. A variety of prefinished colors helps you see almost instant color—only a few touch-ups are required after installation. With primed products, you can paint siding any color you choose. Explore each option in the following pages.



See how LP SmartSide products can look on your home with the new Home Visualizer tool, available at LPCorp.com/Home-Visualizer



LP SmartSide

LP® SMARTSIDE® EXPERTFINISH® TRIM & SIDING

The advanced durability you expect from LP® SmartSide® Trim & Siding comes in color. With a variety of versatile prefinished colors, there's a color that'll complement your project-no matter your style. Start visualizing how you could bring color to your design today!



sacrificing beauty.

- attractive look







TAKE ADVANTAGE OF STRONG PREFINISHED OPTIONS

LP[®] SmartSide[®] ExpertFinish[®] Trim & Siding offers more design options than ever. This factory-finished siding with uniform color provides durability without

• Installs easier with the ExpertFinish proprietary lap joint, which eliminates the need for seam caulking, joint molds or pan flashing at butt joints • Backed by an industry-leading 5/15/50-year prorated limited warranty: 5-year labor and materials, 15-year finish, and 50-year substrate · May allow for time and labor savings for the installer and builder • Uniform color application in a controlled environment helps ensure a more

Which color is best for your build? Explore our collection of 16 versatile prefinished colors available in brushed smooth and cedar texture.

All colors shown are representative and may not be an exact match.

See the complete list of colors and product availability on pages 37-70.



DISCOVER COUNTLESS DESIGN OPPORTUNITIES

LP[®] SmartSide[®] ExpertFinish[®] Trim & Siding can take your design vision to the next level with several exclusive products designed to add style and a clean finish to your home. Siding and trim in colors that pop can make your home stand out, while additional details create a polished look that is longer lasting.

- Pair multiple colors of trim, siding and more for a cohesive look
- Match your home's style to traditional colors for it—or try something new
- Achieve a modern look that still stands the test of time
- Choose from a variety of options for black or brown roofs



Scan to use the new Home Vizualizer tool for your next project and discover color exclusively at LPCorp.com/ExpertFinish



HOLDS UP. STANDS OUT.

LAP SIDING

Create the look you want with a versatile selection of LP[®] SmartSide[®] ExpertFinish[®] products. Engineered to help stand up to many weather conditions, LP SmartSide Lap Siding is a natural, durable choice for structures in most regions. Plus, It's a great companion cladding for structures partially finished in stucco, stone or brick.

A MODERN PROFILE WITH DESIGN FLEXIBILITY

NICKEL GAP SIDING

LP[®] SmartSide[®] Nickel Gap Siding offers a modern profile using SmartGuard[®] technology. Nickel Gap features locking flanges with a fastener groove that hides nails. This also allows for the siding to be stacked and tapped into place, creating a gap between the boards about the size of a nickel.



LP SMARTSIDE EXPERTFINISH CEDAR TEXTURE LAP JOINT SIDING Shown in ExpertFinish color Snowscape White



LP SMARTSIDE EXPERTFINISH BRUSHED SMOOTH LAP JOINT SIDING Shown in ExpertFinish color Garden Sage



LP SMARTSIDE EXPERTFINISH CEDAR TEXTURE NICKEL GAP SIDING

Shown in ExpertFinish color Snowscape White

17

PRODUCTS: NICKEL GAP SIDING



LP SMARTSIDE EXPERTFINISH BRUSHED SMOOTH NICKEL GAP SIDING

Shown in ExpertFinish color Garden Sage



A BEAUTIFUL ACCENT FOR ANY DESIGN

SHAKES

19

When you use LP® SmartSide® ExpertFinish® Cedar Texture Shakes on your projects, people will notice your attention to detail. The beautiful aesthetic can be used for accents, gables or siding walls and will take curb appeal to the next level. It's a must-have product for when you want your craftsmanship to stand out on most any home or shed.



CEDAR TEXTURE SHAKES

Shown in ExpertFinish color Snowscape White

THE BEAUTY IS IN THE DETAILS

SOFFIT

When you use LP® SmartSide® ExpertFinish® Soffit on your projects, people will notice your attention to detail. You'll get the same woodgrain or brushed smooth look that matches other LP SmartSide ExpertFinish products in a soffit that's pre-cut to the width you need. Vented soffits are also available with precisely cut vents.





LP SMARTSIDE **EXPERTFINISH CEDAR TEXTURE** SOFFIT

Shown in ExpertFinish color Snowscape White



DURABLE FROM TOP TO BOTTOM

PANEL & VERTICAL SIDING

Tough to the core, LP[®] SmartSide[®] ExpertFinish[®] Panel & Vertical Siding are treated engineered wood products that boast great durability, stability and consistency. They're easy to recommend for multifamily, shed and residential applications that require a premium look and the toughness to help combat many weather conditions. Plus, they can help you re-create the charming appearance of board and batten while providing the added protection of the LP® SmartGuard® process.



THE FINISHING TOUCH TO MAKE THE NEIGHBORS JEALOUS

TRIM & FASCIA

LP® SmartSide® ExpertFinish® Trim & Fascia are the finishing touch that's the first to get noticed. With deep cedar-grain texture and brushed smooth options as well as a variety of widths and thicknesses, you can add custom design accents that take curb appeal to the next level. LP SmartSide ExpertFinish Trim is a must-have product for when you want your craftsmanship to stand out on any home or shed.



LP SMARTSIDE EXPERTFINISH **CEDAR TEXTURE TRIM**

Shown in ExpertFinish color Snowscape White

Available in select colors. Refer to specifications section for details.



LP SMARTSIDE EXPERTFINISH **BRUSHED SMOOTH TRIM**

Shown in ExpertFinish color Garden Sage



INSTALL WITH EASE AND LOOK GOOD DOING IT

OUTSIDE CORNERS, J-BLOCKS & MINI-SPLITS

Finish any structure's exterior with style and the same durability you trust with these efficient accessories, available in brushed smooth and cedar texture. Outside Corners allow you to skip creating corners on the jobsite while J-Blocks and Mini-Splits help you easily mount light fixtures, faucets and other outdoor fixtures.



OUTSIDE CORNER CEDAR TEXTURE Shown in ExpertFinish color Snowscape White



J-BLOCK CEDAR TEXTURE Shown in ExpertFinish color Snowscape White



J-BLOCK BRUSHED SMOOTH Shown in ExpertFinish color Garden Sage **MINI-SPLIT**

CEDAR TEXTURE Shown in ExpertFinish color Snowscape White



MINI-SPLIT BRUSHED SMOOTH

Shown in ExpertFinish color Garden Sage

Available in select colors. Refer to specifications section for details.

23

OUTSIDE CORNER

BRUSHED SMOOTH

Shown in ExpertFinish color Garden Sage



a

PRIMED AND READY TO MATCH YOUR STYLE

The complete LP[®] SmartSide[®] Trim & Siding product collection is available primed and ready to paint any color so you can enjoy the flexibility you need to create almost any home style. Explore the collection and options on the following pages.







SHOW YOUR TRUE COLORS

For even more aesthetic options, primed LP SmartSide products serve as a great option. These products arrive ready to be painted any color so you and your clients can create the look you want. They're also backed by the durability you expect from engineered wood technology. All LP SmartSide products are available in the primed option.





LAP SIDING

Easier-to-maintain traditional siding, available in cedar texture

NICKEL GAP SIDING

hides nails



PANEL & VERTICAL SIDING

Siding that can be used to create the classic board and batten style, among other looks



J-BLOCK

Offers a way to easily and attractively mount light fixtures, water faucets and more





MINI-SPLIT

Install exterior features with ease; can be separated for specific mount styles



Offers a modern profile with locking flanges and a fastener groove that



SHAKES

Accent piece with staggered or straight edges and shiplap ends for a detailed finish



TRIM & FASCIA

curb appeal to any home's look, available in brushed smooth and



Ventilation that completes a clean exterior look and serves as a finishing touch



OUTSIDE CORNER

Primed one-piece corners eliminate the need to build corners on the jobsite and help prevent water intrusion

MARETHEFICSUUM

LP® SmartSide® Trim & Siding products add style and durability to new homes and other applications, such as remodels and multifamily structures. They come in a variety of ExpertFinish® colors designed to enhance any project. Use LP SmartSide products on their own or to complement other claddings, such as brick or stone. With products and colors this versatile, the possibilities are virtually endless, no matter the project.





A FRESH START DESIGNED TO LAST

NEW HOME

Every homeowner wants a custom look that they can take pride in. They want a style that helps differentiate their new home from the one next door. LP® SmartSide® products give builders and architects the ability to design a signature look with a wow-factor that leaves a lasting impression.

POPULAR CHOICES FOR NEW HOMES:

- LP[®] SmartSide[®] Lap Siding
- LP[®] SmartSide[®] Nickel Gap Siding
- LP[®] SmartSide[®] Cedar Texture Shakes
- LP[®] SmartSide[®] Trim & Fascia
- LP[®] SmartSide[®] Soffit
- LP[®] SmartSide[®] Vertical Siding
- LP[®] SmartSide[®] Panel Siding (for Board & Batten Style)

OUT WITH THE OLD, IN WITH THE NEW

REMODEL

LP[®] SmartSide[®] products can help give any home new life with their beautiful selection of styles and profiles. They easily transform homes from boring to bold with brushed smooth and cedar texture options. When you start using LP SmartSide products, it's easy to see why homeowners love them and professional remodelers love to work with them.

LPCorp.com/NewHome

POPULAR CHOICES FOR REMODELING:

- LP[®] SmartSide[®] Lap Siding
- LP[®] SmartSide[®] Cedar Texture Shakes
- LP[®] SmartSide[®] Trim & Fascia
- LP[®] SmartSide[®] Soffit
- LP[®] SmartSide[®] Vertical Siding
- LP[®] SmartSide[®] Panel Siding (for Board & Batten Style)
- LP[®] SmartSide[®] ExpertFinish[®] Trim & Siding



DURABILITY FOR THE GREAT OUTDOORS

OUTDOOR BUILDING SOLUTIONS®

LP® Outdoor Building Solutions® engineered wood products feature innovations that help offer more value to customers. With innovations like SilverTech® panel for a brighter and cooler interior and SmartFinish® overlay for a tough, attractive appearance, LP Outdoor Building Solutions products give you quality you can see inside and out.

POPULAR CHOICES FOR OUTDOOR BUILDINGS:

- LP[®] SmartSide[®] Panel Siding
- LP[®] SmartSide[®] Panel Siding with SilverTech
- LP[®] SmartSide[®] Panel Siding with SmartFinish
- LP[®] SmartSide[®] Lap Siding
- LP[®] ProStruct[®] Flooring with SmartFinish
- LP[®] ProStruct[®] Roof Sheathing with SilverTech
- LP[®] SmartSide[®] Trim & Fascia
- LP[®] SmartSide[®] ExpertFinish[®] Trim & Siding

MORE OPTIONS FOR MORE FAMILIES

MULTIFAMILY

Designed to combine style and durability, LP[®] SmartSide[®] Trim & Siding products are a great fit for multifamily developments. They are compatible with a wide range of styles, claddings and colors, offering flexibility and versatility in both function and design. Because engineered wood is built to be longer lasting, multifamily structures using LP SmartSide products help stand the test of time.

LPCorp.com/Shed

POPULAR CHOICES FOR MULTIFAMILY:

- LP[®] SmartSide[®] Panel Siding
- LP[®] SmartSide[®] Lap Siding
- LP[®] SmartSide[®] Vertical Siding
- LP[®] SmartSide[®] Trim & Fascia
- LP[®] SmartSide[®] Soffit
- LP[®] SmartSide[®] ExpertFinish[®] Trim & Siding

TAKEA LOOK INSIDE

LP® SmartSide® products come in different lengths, widths, textures, ExpertFinish® colors and profiles, so there's an ideal product for virtually any set of needs. Each option has its own unique combination of advantages. Find all those details and product specifications here, including ExpertFinish color availability for each product.



EXPERTFINISH® PRODUCTS


COLOR	38 Series 6″ or 8″ Lap	Nickel Gap Siding 8″	190 Series 3″ Trim	440 Series 4″, 6″, 8″, 10″ or 12″ Trim	540 Series 4 ″, 6 ″, 8 ″, 10 ″ or 12 ″ Trim	38 Series 12″ or 16″ Closed Soffit	38 Series 12″ or 16″ Vented Soffit	38 Series 24" Closed Soffit	38 Series 24" Vented Soffit	38 Series 12 ″ x 48 ″ Shakes	38 Series 16″ x 16″ Vertical Siding	38 Series 4' x 8' Panel	38 Series 4' x 10' Panel	540 Series 4″ x 16′ Outside Corner	540 Series 6″ x 16° Outside Corner	540 Series 7.25″ x 7.25″ J-Block	540 Series 7.25 ″ x 6.75 ″ Mini Split
Snowscape White	•*	•*	•*	●*	•*	•*	•*	●*	•*	٠	•*	●*	•	●*	•*	•*	•*
Sand Dunes	•*	•*	●*	●*	●*			●*	●*	٠	●*	●*	٠	●*		•*	•*
Desert Stone	•*	•*	●*	●*	•*					•	•*	•*	•	●*		•*	•*
Quarry Gray	•*	● *	●*	•*	•*			●*	•*	٠	•*	●*	٠	•*		•*	•*
Prairie Clay	•*	•*	●*	●*	•*					•	•*	•*	•	●*		•*	•*
Terra Brown	•*	●*	●*	•*	•*					٠	•*	●*	٠	•*		●*	● 米
Harvest Honey	•*	•*	•*	●*	•*					٠	•*	●*	٠	●*		•*	•*
Timberland Suede	•*	•*	•*	●*	•*					٠	•*	•*	٠	•*		●*	● *
Garden Sage	•*	•*	•*	•*	•*					٠	•*	•*	٠	•*		●*	•*
Redwood Red	•*	•*	•*	●*	●*					٠	●*	●*	٠	●*		●*	•*
Tundra Gray	•*	•*	●*	●*	•*					٠	•*	●*	٠	●*		●*	•*
Summit Blue	•*	•*	●*	●*	●*					٠	●*	●*	٠	●*		•*	•*
Rapids Blue	•*	•*	●*	●*	●*					٠	•*	●*	٠	●*		•*	•*
Cavern Steel	•*	•*	●*	●*	●*					٠	●*	●*	٠	●*		●*	•*
Midnight Shadow	•*	•*	•*	•*	•*					٠	•*	•*	٠	•*		•*	•*
Abyss Black	•*	●*	•*	●*	●*			●*	●*	٠	•*	●*	٠	●*	●*	•*	•*

All colors shown are representative and may not be an exact match. • Available in Cedar Texture * Available in Brushed Smooth

SNOWSCAPE WHITE CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41715	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42271	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46558	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46468	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	42324	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	42328	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46396	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46412	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46428	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	42312	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	42316	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46316	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46332	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46348	3 PSF
38 Series Cut-To-Width 12″ x 16′ Closed Soffit	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	46434	-
38 Series Cut-To-Width 12" x 16' Vented Soffit †	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	43433	-
38 Series Cut-To-Width 16″ x 16′ Closed Soffit	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	46436	-
38 Series Cut-To-Width 16" x 16' Vented Soffit †	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	46435	-
38 Series Cut-To-Width 24" x 16' Closed Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46536	-
38 Series Cut-To-Width 24" x 16' Vented Soffit $^{\scriptscriptstyle \dagger}$	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46540	-
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46524	2 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	41730	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47097	2 PSF
38 Series 4' \times 10' NGSE Dual Use Siding and Soffit Panel	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47082	2 PSF
E40 Series Outside Corres	16 ft. (192 in.)(4.9 m)	3.625 in. (92.3 mm)	0.970 in. (24.6 mm)	47149	-
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	5.625 in. (142.8 mm)	0.970 in. (24.6 mm)	47185	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43399	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43416	-
Touch-Up Kits	-	-	-	42043	-

38 SERIES EXPERTFINISH LAP



* Same specs for all 16 colors on pages 39-70.

**Lap joint profile is exclusive to LP® SmartSide® ExpertFinish® Lap Siding. Third-party prefinished siding will not include this feature.

‡ LP offers vented soffits in both 5 square inches and 10 square inches of ventilation per linear foot for primed.

SNOWSCAPE WHITE BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45683	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45667	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46574	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45779	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45795	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45811	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45827	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45843	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45859	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45699	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45715	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45731	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45747	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45763	3 PSF
38 Series Cut-To-Width 12" x 16' Closed Soffit	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	46541	-
38 Series Cut-To-Width 12″ x 16′ Vented Soffit	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	47030	-
38 Series Cut-To-Width 16″ x 16′ Closed Soffit	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	46542	-
38 Series Cut-To-Width 16″ x 16′ Vented Soffit	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	47031	-
38 Series Cut-To-Width 24″ x 16′ Closed Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46546	-
38 Series Cut-To-Width 24" x 16' Vented Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	47035	-
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45877	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45893	2 PSF
540 Spring Outside Osmer	16 ft. (192 in.)(4.9 m)	3.625 in. (92.3 mm)	0.970 in. (24.6 mm)	47117	-
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	5.625 in. (142.8 mm)	0.970 in. (24.6 mm)	47181	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45925	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45953	-
Touch-Up Kits				42043	

SAND DUNES CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41841	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42272	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46557	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46267	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46363	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46379	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46395	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46411	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46427	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46283	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46299	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46315	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46331	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46347	3 PSF
38 Series 24" x 16' Closed Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46535	-
38 Series 24" x 16' Vented Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46539	-
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46522	2 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47098	2 PSF
38 Series 4′ x 10′ NGSE Dual Use Siding and Soffit Panel	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47083	2 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	41820	1.5 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47153	-
7.25" x 7.25" J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43401	-
7.25" x 6.75" Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43417	-
Touch Up Kits	-	-	-	42055	-

SAND DUNES BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45682	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45666	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46573	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45778	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45794	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45810	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45826	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45842	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45858	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45698	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45714	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45730	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45746	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45762	3 PSF
38 Series 24" x 16' Closed Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46545	-
38 Series 24" x 16' Vented Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	47034	-
38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45892	2 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45876	1.5 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47121	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45923	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45951	-
Touch Up Kits	-	-	-	42055	-

DESERT STONE CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41842	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42274	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46549	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46248	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46355	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46371	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46387	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46403	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46419	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46275	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46291	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46307	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46323	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46339	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	43152	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47099	2 PSF
38 Series 4´ x 10´ NGSE Dual Use Siding and Soffit Panel	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47084	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	43355	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47155	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43402	-
7.25" x 6.75" Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43418	-
Touch-Up Kits	-	-	-	42049	-

DESERT STONE BRUSHED SMOOTH

38 Series Lap 16 ft. (192 in.)(4.9 m) 7.84 in. (199 mm) 0.354 in. (9 mm) 45658 1.5 F Nickel Gap Siding 16 ft. (192 in.)(4.9 m) 7.88 in. (200 mm) 0.495 in. (12.6 mm) 45656 1.5 F 190 Series Trim 16 ft. (192 in.)(4.9 m) 2.50 in. (64 mm) 0.578 in. (14.7 mm) 45676 2.F 440 Series Trim 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.675 in. (17.1 mm) 45876 2.F 440 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.675 in. (17.1 mm) 45882 2.F 440 Series Trim 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.675 in. (17.1 mm) 45818 2.F 450 2 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.675 in. (17.1 mm) 45818 2.F 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45509 3.F 540 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45738 3.F 540 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45738 3.F <th>DESCRIPTION</th> <th>LENGTH</th> <th>ACTUAL WIDTH</th> <th>THICKNESS</th> <th>PID NUMBER</th> <th>WEIGHT</th>	DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
Ibit Ibit <th< td=""><td></td><td>16 ft. (192 in.)(4.9 m)</td><td>5.84 in. (148 mm)</td><td>0.354 in. (9 mm)</td><td>45674</td><td>1.5 PSF</td></th<>		16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45674	1.5 PSF
190 Series Trim 16 ft. (192 in.)(4.9 m) 2.50 in. (64 mm) 0.578 in. (14.7 mm) 45770 2 P 440 Series Trim 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.675 in. (17.1 mm) 45802 2 P 440 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.675 in. (17.1 mm) 45802 2 P 440 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.675 in. (17.1 mm) 45818 2 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.675 in. (17.1 mm) 45834 2 P 16 ft. (192 in.)(4.9 m) 3.50 in. (234 mm) 0.675 in. (17.1 mm) 45830 2 P 16 ft. (192 in.)(4.9 m) 3.50 in. (234 mm) 0.675 in. (17.1 mm) 45830 2 P 16 ft. (192 in.)(4.9 m) 3.50 in. (140 mm) 0.970 in. (24.6 mm) 45690 3 P 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 <	38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45658	1.5 PSF
440 Series Trim 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.675 in. (17.1 mm) 45786 2 P 440 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.675 in. (17.1 mm) 45802 2 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.675 in. (17.1 mm) 45818 2 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.675 in. (17.1 mm) 45834 2 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.675 in. (17.1 mm) 45834 2 P 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.675 in. (17.1 mm) 45800 2 P 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.675 in. (17.1 mm) 45800 2 P 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.970 in. (24.6 mm) 45690 3 P 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45766 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45768 P	Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46565	1.5 PSF
440 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.675 in. (17.1 mm) 45802 2 P4 440 Series Trim 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.675 in. (17.1 mm) 45818 2 P4 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.675 in. (17.1 mm) 45834 2 P4 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.675 in. (17.1 mm) 45834 2 P4 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.675 in. (17.1 mm) 45830 2 P4 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.675 in. (17.1 mm) 45850 2 P4 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.970 in. (24.6 mm) 45690 3 P4 540 Series Trim 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45738 3 P4 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45738 3 P4 38 Series Vertical Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1216 mm) 0.354 in. (9 mm) 45886 15 F 38 Series Vertical Siding and Soffift Panel	190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45770	2 PSF
440 Series Trim 16 ft. (192 in)(4.9 m) 7.21 in. (183 mm) 0.675 in. (17.1 mm) 45818 2 P4 16 ft. (192 in)(4.9 m) 9.21 in. (234 mm) 0.675 in. (17.1 mm) 45834 2 P4 16 ft. (192 in)(4.9 m) 11.21 in. (285 mm) 0.675 in. (17.1 mm) 45830 2 P4 16 ft. (192 in)(4.9 m) 11.21 in. (285 mm) 0.675 in. (17.1 mm) 45800 2 P4 16 ft. (192 in)(4.9 m) 3.50 in. (89 mm) 0.970 in. (24.6 mm) 45690 3 P4 540 Series Trim 16 ft. (192 in)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45706 3 P4 16 ft. (192 in)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45738 3 P4 16 ft. (192 in)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45744 3 P4 16 ft. (192 in)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45764 3 P4 18 Series Vertical Siding 16 ft. (192 in)(4.9 m) 15.94 in. (405 mm) 0.970 in. (24.6 mm) 45868 15 F4 18 Series Vertical Siding and Softift Paei 16 ft. (192 in)(4.9 m) 3.625 in. (92 mm) 0.354 in. (9 mm) 45864 2 P4 19 Series Vertical Siding C		16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45786	2 PSF
16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.675 in. (17.1 mm) 45834 2 P 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.675 in. (17.1 mm) 45850 2 P 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.970 in. (24.6 mm) 45690 3 P 540 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45706 3 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45706 3 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (285 mm) 0.970 in. (24.6 mm) 45738 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 15.94 in. (405 mm) 0.354 in. (9 mm) 45868 1.5 F 38 Series Vertical Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1216 mm) 0.354 in. (9 mm) 45868 1.5 F 38 Series Vertical Siding and Soffit Panel 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 45868 1.5 F		16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45802	2 PSF
16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.675 in. (17.1 mm) 45850 2 P 16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.970 in. (24.6 mm) 45690 3 P 540 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45706 3 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45708 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45738 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45784 3 P 38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 15.94 in. (405 mm) 0.354 in. (9 mm) 45884 2 P 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 47.88 9 7.25 '' x 7.25 '' J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45.907 -	440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45818	2 PSF
16 ft. (192 in.)(4.9 m) 3.50 in. (89 mm) 0.970 in. (24.6 mm) 45690 3 P 540 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45706 3 P 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45722 3 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45754 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45868 1.5 F 38 Series Vertical Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1 216 mm) 0.354 in. (9 mm) 45868 2 P 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 45808 2 P 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 47123 - 7.25" x 7.25" J-Block 7.2		16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45834	2 PSF
540 Series Trim 16 ft. (192 in.)(4.9 m) 5.50 in. (140 mm) 0.970 in. (24.6 mm) 45706 3 P 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45722 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45754 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 15.94 in. (405 mm) 0.970 in. (24.6 mm) 45768 15 P 38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1 216 mm) 0.354 in. (9 mm) 45884 2 P 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 45907 - 7.25 '' x 7.25'' J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45938 - 7.25 '' x 6.75'' Mini-Split 7.25 in. (184 mm) 6.75 in. (171 mm) 0.970 in. (24.6 mm) 45938 -		16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45850	2 PSF
540 Series Trim 16 ft. (192 in.)(4.9 m) 7.21 in. (183 mm) 0.970 in. (24.6 mm) 45722 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45754 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45868 1.5 F 38 Series Vertical Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1 216 mm) 0.354 in. (9 mm) 45884 2 P 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 45907 - 7.25 ''x 7.25'' J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45907 - 7.25 ''x 6.75'' Mini-Split 7.25 in. (184 mm) 6.75 in. (171 mm) 0.970 in. (24.6 mm) 45938 -		16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45690	3 PSF
16 ft. (192 in.)(4.9 m) 9.21 in. (234 mm) 0.970 in. (24.6 mm) 45738 3 P 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45754 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45754 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 15.94 in. (405 mm) 0.354 in. (9 mm) 45868 1.5 F 38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1 216 mm) 0.354 in. (9 mm) 45884 2 P 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 45907 - 7.25" x 7.25" J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45938 -		16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45706	3 PSF
16 ft. (192 in.)(4.9 m) 11.21 in. (285 mm) 0.970 in. (24.6 mm) 45754 3 P 38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 15.94 in. (405 mm) 0.354 in. (9 mm) 45868 1.5 F 38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1 216 mm) 0.354 in. (9 mm) 45884 2 P 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 47123 - 7.25" x 7.25" J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45907 - 7.25" x 6.75" Mini-Split 7.25 in. (184 mm) 6.75 in. (171 mm) 0.970 in. (24.6 mm) 45938 -	540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45722	3 PSF
38 Series Vertical Siding 16 ft. (192 in.)(4.9 m) 15.94 in. (405 mm) 0.354 in. (9 mm) 45868 1.5 F 38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1 216 mm) 0.354 in. (9 mm) 45884 2 P 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 47.23 - 7.25 '' x 7.25'' J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45907 - 7.25 '' x 6.75'' Mini-Split 7.25 in. (184 mm) 6.75 in. (171 mm) 0.970 in. (24.6 mm) 45938 -		16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45738	3 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel 8 ft. (96 in.)(2.4 m) 47.88 in. (1 216 mm) 0.354 in. (9 mm) 45884 2 PS 540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 47123 - 7.25" x 7.25" J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45907 - 7.25" x 6.75" Mini-Split 7.25 in. (184 mm) 6.75 in. (171 mm) 0.970 in. (24.6 mm) 45938 -		16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45754	3 PSF
540 Series Outside Corner 16 ft. (192 in.)(4.9 m) 3.625 in. (92 mm) 0.970 in. (24.6 mm) 47123 - 7.25" x 7.25" J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45907 - 7.25" x 6.75" Mini-Split 7.25 in. (184 mm) 6.75 in. (171 mm) 0.970 in. (24.6 mm) 45938 -	38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45868	1.5 PSF
7.25" x 7.25" J-Block 7.25 in. (184 mm) 7.25 in. (184 mm) 0.970 in. (24.6 mm) 45907 - 7.25" x 6.75" Mini-Split 7.25 in. (184 mm) 6.75 in. (171 mm) 0.970 in. (24.6 mm) 45938 -	38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45884	2 PSF
7.25" x 6.75" Mini-Split 7.25 in. (184 mm) 6.75 in. (171 mm) 0.970 in. (24.6 mm) 45938 -	540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47123	-
	7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45907	-
	7.25" x 6.75" Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45938	-
Touch-Up Kits 42049 -	Touch-Up Kits	-	-	-	42049	-

QUARRY GRAY CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
00.0	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41837	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42288	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46554	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46264	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46360	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46376	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46392	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46408	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46424	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46280	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46296	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46312	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46328	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46344	3 PSF
38 Series 24" x 16' Closed Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46534	
38 Series 24" x 16' Vented Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46538	
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	41819	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47100	2 PSF
38 Series 4´ x 10´ NGSE Dual Use Siding and Soffit Panel	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47085	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46516	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47157	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43412	-
7.25" x 6.75" Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43428	-
Touch-Up Kits	-	-	-	42052	-

QUARRY GRAY BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45679	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45663	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46570	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45775	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45791	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45807	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45823	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45839	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45855	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45695	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45711	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45727	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45743	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45759	3 PSF
38 Series 24" x 16' Closed Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46544	
38 Series 24" x 16' Vented Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	47033	
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45961	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45889	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47125	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45917	-
7.25" x 6.75" Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45974	-
Touch-Up Kits	-	-	-	42052	-

PRAIRIE CLAY CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41834	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42278	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46553	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46263	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46359	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46375	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46391	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46407	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46423	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46279	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46295	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46311	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46327	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46343	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	43194	1.5 PSF
38 Series 4' \times 8' NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47101	2 PSF
38 Series 4' $x10'$ NGSE Dual Use Siding and Soffit Panel	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47086	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46514	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47159	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43404	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43420	-
Touch-Up Kits	-	-	-	42051	-

PRAIRIE CLAY BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45678	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45662	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46569	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45774	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45790	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45806	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45822	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45838	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45854	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45694	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45710	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45726	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45742	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45758	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45872	1.5 PSF
38 Series 4´ x 8´ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45888	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47127	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45915	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45945	-
Touch-Up Kits	-	-	-	42051	-

TERRA BROWN CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41845	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42277	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46560	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46270	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46366	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46382	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46398	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46414	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46430	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46286	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46302	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46318	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46334	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46350	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	46528	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47102	2 PSF
38 Series 4´ x 10´ NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47087	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46528	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47161	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43403	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43432	-
Touch-Up Kits	-	-	-	42046	-

TERRA BROWN BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45685	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45669	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46576	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45781	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45797	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45813	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45829	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45845	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45861	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45701	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45717	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45733	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45749	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45765	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45964	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45968	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47129	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45929	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45980	-
Touch-Up Kits	-	-	-	42046	-

HARVEST HONEY CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45327	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45284	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46551	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46261	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46357	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46373	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46389	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46405	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46421	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46277	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46293	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46309	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46325	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46341	3 PSF
	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45381	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47103	2 PSF
38 Series 4' x 10' NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47088	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	48.56 in. (1 234 mm)	0.354 in. (9 mm)	46510	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47163	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45436	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45438	-
Touch-Up Kits	-	-	-	45405	-

HARVEST HONEY BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45676	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45660	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46567	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45772	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45788	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45804	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45820	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45836	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45852	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45692	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45708	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45724	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45740	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45756	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45870	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45886	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47131	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45911	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45942	-
Touch-Up Kits	-	-	-	45405	-

TIMBERLAND SUEDE CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41843	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42269	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46561	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46271	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46367	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46383	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46399	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46415	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46431	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46287	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46303	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46319	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46335	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46351	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	43291	1.5 PSF
38 Series 4 $$ x 8 $$ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47104	2 PSF
38 Series 4' x 10' NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47089	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46530	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47165	-
7.25 [~] x 7.25 [~] J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43405	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43421	-
Touch-Up Kits	-	-	-	42058	-

TIMBERLAND SUEDE BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45686	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45670	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46577	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45782	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45798	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45814	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45830	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45846	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45862	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45702	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45718	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45734	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45750	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45766	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45880	1.5 PSF
38 Series 4 $$ x 8 $$ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45896	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47133	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45931	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45957	-
Touch-Up Kits	-	-	-	42058	-

GARDEN SAGE CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45328	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45325	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46550	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46249	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46356	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46372	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46388	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46404	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46420	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46276	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46292	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46308	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46324	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46340	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45382	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47105	2 PSF
38 Series 4' x 10' NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (8 mm)	47090	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (8 mm)	46508	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47167	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45437	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45402	-
Touch-Up Kits	-	-	-	45441	-

GARDEN SAGE BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45675	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45659	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46566	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45771	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45787	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45803	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45819	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45835	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45851	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45691	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45707	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45723	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45739	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45755	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45869	1.5 PSF
38 Series 4´ x 8´ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45885	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47135	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45909	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45940	-
Touch-Up Kits	-	-	-	45441	-

REDWOOD RED CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41840	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42293	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46556	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46266	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46362	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46378	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46394	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46410	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46426	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46282	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46288	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46314	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46330	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46346	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	43232	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47106	2 PSF
38 Series 4´ x 10´ NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47091	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46520	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47169	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43408	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43424	-
Touch-Up Kits	-	-	-	42054	-

REDWOOD RED BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45681	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45665	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46572	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45777	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45793	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45809	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45825	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45841	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45857	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45697	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45713	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45729	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45745	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45761	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45875	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45891	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47137	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45921	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45949	-
Touch-Up Kits	-	-	-	42054	-

TUNDRA GRAY CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41846	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42300	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46562	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46272	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46368	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46384	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46400	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46416	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46432	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46288	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46304	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46320	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46336	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46352	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	43312	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47107	2 PSF
38 Series 4' x 10' NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47092	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46532	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47171	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43413	-
7.25" x 6.75" Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43429	-
Touch-Up Kits	-	-	-	42059	-

TUNDRA GRAY BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45687	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45671	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46578	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45783	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45799	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45815	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45831	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45847	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45863	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45703	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45719	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45735	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45751	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45767	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45965	1.5 PSF
38 Series 4´ x 8´ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45897	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47139	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45933	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45982	-
Touch-Up Kits	-	-	-	42059	-

SUMMIT BLUE CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
2020 · · · ·	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41844	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42273	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46559	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46269	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46365	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46381	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46397	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46413	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46429	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46285	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46301	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46317	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46333	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46349	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	43341	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47108	2 PSF
38 Series 4´ x 10´ NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47093	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46526	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47173	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43410	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43426	-
Touch-Up Kits	-	-	-	42057	-

SUMMIT BLUE BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45684	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45668	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46575	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45780	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45796	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45812	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45828	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45844	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45860	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45700	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45716	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45732	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45748	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45764	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45963	1.5 PSF
38 Series 4´ x 8´ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45967	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47141	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45927	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45978	-
Touch-Up Kits	-	-	-	42057	-

RAPIDS BLUE CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41839	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42287	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46555	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46265	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46461	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46377	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46397	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46409	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46425	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46281	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46297	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46313	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46329	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46345	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	43337	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47109	2 PSF
38 Series 4' \times 10' NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47094	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46518	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47175	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43411	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43427	-
Touch-Up Kits	-	-	-	42053	-

RAPIDS BLUE BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45680	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45664	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46571	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45776	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45792	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45808	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45824	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45840	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45856	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45696	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45712	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45728	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45744	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45760	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45962	1.5 PSF
38 Series 4´ x 8´ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45966	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47143	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45919	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45976	-
Touch-Up Kits	-	-	-	42053	-

CAVERN STEEL CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41835	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42301	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46548	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46247	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46354	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46370	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46387	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46402	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46418	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46274	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46290	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46306	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46322	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46338	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	43133	1.5 PSF
38 Series 4 $\stackrel{\prime}{}$ x 8 $\stackrel{\prime}{}$ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47110	2 PSF
38 Series 4´ x 10´ NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47095	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46504	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47177	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43414	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43430	-
Touch-Up Kits	-	-	-	42048	-

CAVERN STEEL BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45673	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45657	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46564	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45769	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45785	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45801	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45817	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45833	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45849	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45689	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45705	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45721	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45737	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45753	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45959	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45883	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47145	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45905	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45970	-
Touch-Up Kits	-	-	-	42048	-

MIDNIGHT SHADOW CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45329	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45326	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46552	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46262	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46358	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46374	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46390	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46406	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46422	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46478	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46294	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46310	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46326	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46342	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45383	1.5 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47111	2 PSF
38 Series 4' x 10' NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47096	2 PSF
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46512	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47179	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45399	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45440	-
Touch-Up Kits	-	-	-	45442	-

MIDNIGHT SHADOW BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45677	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45661	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46568	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45773	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45789	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45805	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45821	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45837	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45853	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45693	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45709	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45725	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45741	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45757	3 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45960	1.5 PSF
38 Series 4´ x 8´ NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45887	2 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47147	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45913	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45972	-
Touch-Up Kits	-	-	-	45442	-

ABYSS BLACK CEDAR TEXTURE

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	41774	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	42279	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46547	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	46246	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	42327	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46369	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46385	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46401	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46417	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	46273	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	46273	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	46305	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	46321	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	46337	3 PSF
38 Series 24" x 16' Closed Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46533	-
38 Series 24" x 16' Vented Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46537	-
38 Series Shakes	4 ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	46502	2 PSF
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47112	2 PSF
38 Series 4' x 10' NGSE Dual Use Siding and Soffit	10 ft. (119.81 in.)(3043 mm)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	47081	2 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	41775	1.5 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47151	-
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	5.625 in. (143 mm)	0.970 in. (24.6 mm)	47187	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	43435	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43431	-
Touch-Up Kits	-	-	-	42045	-

ABYSS BLACK BRUSHED SMOOTH

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45672	1.5 PSF
38 Series Lap	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45656	1.5 PSF
Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in. (200 mm)	0.495 in. (12.6 mm)	46563	1.5 PSF
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	45768	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	45784	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	45800	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	45816	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	45832	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	45848	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45688	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45704	3 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45720	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45736	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45752	3 PSF
38 Series 24" x 16' Closed Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	45643	-
38 Series 24" x 16' Vented Soffit	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	47032	-
38 Series 4' x 8' NGSE Dual Use Siding and Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	45882	2 PSF
38 Series Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45866	1.5 PSF
540 Series Outside Corner	16 ft. (192 in.)(4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47119	-
540 Series Outside Comer	16 ft. (192 in.)(4.9 m)	5.625 in. (143 mm)	0.970 in. (24.6 mm)	47183	-
7.25″ x 7.25″ J-Block	7.25 in. (184 mm)	7.25 in. (184 mm)	0.970 in. (24.6 mm)	45903	-
7.25″ x 6.75″ Mini-Split	7.25 in. (184 mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	45935	-
Touch-Up Kits	-	-	-	42045	-

Specifications: LP[®] SmartSide[®] Lap Siding Coverage

Lap Siding 16' Length	Revea	ıl (size)	
Area (sq. ft.)	4-7/8″ (6″)	6-7/8″ (8″)	10-7/8″ (12″)
100	16 pcs.	11 pcs.	7 pcs.
200	31 pcs.	22 pcs.	14 pcs.
300	47 pcs.	33 pcs.	21 pcs.
400	62 pcs.	44 pcs.	28 pcs.
500	77 pcs.	55 pcs.	35 pcs.
600	93 pcs.	66 pcs.	42 pcs.
700	108 pcs.	77 pcs.	49 pcs.
800	124 pcs.	88 pcs.	56 pcs.
900	139 pcs.	99 pcs.	63 pcs.
1000	154 pcs.	110 pcs.	69 pcs.
1500	231 pcs.	164 pcs.	104 pcs.
2000	308 pcs.	219 pcs.	138 pcs.
2500	385 pcs.	273 pcs.	173 pcs.
3000	462 pcs.	328 pcs.	207 pcs.
3500	539 pcs.	382 pcs.	242 pcs.
4000	616 pcs.	437 pcs.	276 pcs.
4500	693 pcs.	491 pcs.	311 pcs.
5000	770 pcs.	546 pcs.	345 pcs.

CEDAR TEXTURE LAP SIDING

THE BOLD LOOK OF CEDAR WITHOUT MANY OF THE WORRIES


- One of the most durable lap siding options on the market today
- Available in lengths up to 16' to help speed installation
- May create fewer seams than traditional 12' siding
- Primed for exceptional paint adhesion
- APA-certified lap siding
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay



Cedar Texture

38 SERIES CEDAR TEXTURE LAP





DESCRIPT	TION LENG	TH ACTUAL WIE	THICKNESS	PID NUMBER	WEIGHT
38 Series	Lap 16 ft. (192 i	n.)(4.9 m) 5.84 in. (148	mm) 0.354 in. (9 mm)	25796	1.5 PSF
	16 ft. (192 i	n.)(4.9 m) 7.84 in. (199	mm) 0.354 in. (9 mm)	25797	1.5 PSF
	16 ft. (192 i	n.)(4.9 m) 11.84 in. (301	mm) 0.354 in. (9 mm)	25799	1.5 PSF
76 Series	Lap 16 ft. (192 i	n.)(4.9 m) 7.84 in. (199	mm) 0.418 in. (10.6 mm	n) 25786	1.5 PSF
	16 ft. (192 i	n.)(4.9 m) 11.84 in. (301	mm) 0.418 in. (10.6 mm	n) 25787	1.5 PSF

BRUSHED SMOOTH TEXTURE PROVIDES A MODERN LOOK

• One of the most durable lap siding options on the market today

Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay

Available in lengths up to 16' to help speed installation May create fewer seams than traditional 12' siding

Specifications: LP[®] SmartSide[®] Lap Siding Coverage

BRUSHED SMOOTH LAP SIDING





Brushed Smooth

Lap Siding 16´ Length	Reveal (size)		
Area (sq. ft.)	4-7/8″ (6″)	6-7/8″ (8″)	10-7/8″ (12″)
100	16 pcs.	11 pcs.	7 pcs.
200	31 pcs.	22 pcs.	14 pcs.
300	47 pcs.	33 pcs.	21 pcs.
400	62 pcs.	44 pcs.	28 pcs.
500	77 pcs.	55 pcs.	35 pcs.
600	93 pcs.	66 pcs.	42 pcs.
700	108 pcs.	77 pcs.	49 pcs.
800	124 pcs.	88 pcs.	56 pcs.
900	139 pcs.	99 pcs.	63 pcs.
1000	154 pcs.	110 pcs.	69 pcs.
1500	231 pcs.	164 pcs.	104 pcs.
2000	308 pcs.	219 pcs.	138 pcs.
2500	385 pcs.	273 pcs.	173 pcs.
3000	462 pcs.	328 pcs.	207 pcs.
3500	539 pcs.	382 pcs.	242 pcs.
4000	616 pcs.	437 pcs.	276 pcs.
4500	693 pcs.	491 pcs.	311 pcs.
5000	770 pcs.	546 pcs.	345 pcs.

38 SERIES BRUSHED SMOOTH LAP

THAT STILL REMAINS TIMELESS

APA-certified lap siding

Primed for exceptional paint adhesion



DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series Lap	16 ft. (192 in.)(4.9 m)	5.84 in. (148 mm)	0.354 in. (9 mm)	45989	1.5 PSF
	16 ft. (192 in.)(4.9 m)	7.84 in. (199 mm)	0.354 in. (9 mm)	45990	1.5 PSF
	16 ft. (192 in.)(4.9 m)	11.84 in. (301 mm)	0.354 in. (9 mm)	45991	1.5 PSF

NICKEL GAP SIDING

A MODERN PROFILE WITH DESIGN FLEXIBILITY

- Features include a nominal 1/2" thickness and 7" reveal
- Can be installed vertically or horizontally
- Install with LP SmartFlashTM Metal Pan Flashing accessory (100 pieces/box; only available in primed) or comparable alternative to support a complete system
- Backed by an industry-leading 5/50-year limited warranty

CEDAR TEXTURE NICKEL GAP





SmartFlash Metal Flashing

PEBBLED STUCCO PANEL SIDING

DESIGNED FOR EASIER USE IN METAL FRAME TRIM SYSTEMS

- Elevate your design with a stucco like texture using LP[®] SmartSide[®] Pebbled Stucco panels
- Advanced Durability for Longer Lasting Beauty[®]
- Primed for exceptional paint adhesion
- Backed by an industry-leading 5/50-year limited warranty
- Available in 4' x 8', 4' x 9' and 4' x 10' panels with either Square or Shiplap edge design to meet your installation requirements
 - o Square Edge suitable for use in metal frame trim systems applications

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series NGSE Pebbled Stucco Siding	10 ft. (120 in.) (3.04 m)	47.88 in. (1 216 mm)	0.354 in. (8.9 mm)	46050	1.5 PSF
	9 ft. (108 in.) (2.74 m)	47.88 in. (1 216 mm)	0.354 in. (8.9 mm)	46051	1.5 PSF
	8 ft. (96 in.) (2.43 m)	47.88 in. (1 216 mm)	0.354 in. (8.9 mm)	46669	1.5 PSF
38 Series NGSL Pebbled Stucco Siding	10 ft. (120 in.) (3.04 m)	48.56 in. (1 234 mm)	0.354 in. (8.9 mm)	46052	1.5 PSF
	9 ft. (108 in.) (2.74 m)	48.56 in. (1 234 mm)	0.354 in. (8.9 mm)	46053	1.5 PSF
	8 ft. (96 in.) (2.43 m)	48.56 in. (1 234 mm)	0.354 in. (8.9 mm)	46668	1.5 PSF

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
LP SmartSide Nickel Gap Siding	16 ft. (192 in.)(4.9 m)	7.88 in (200 mm)	0.495 in. (12.6 mm)	45545	1.5 PSF
LP SmartFlash Metal Flashing	10 in. (254 mm)	4 in. (101.6 mm)	0.024 in. (0.61 mm)	46180	9.4LBS/100PC BOX

Specifications: LP[®] SmartSide[®] Nickel Gap Siding Coverage

Nickel Gap 16' Length	Reveal (size)
Area (sq. ft.)	6-7/8″ (7″)
100	11 pcs.
200	22 pcs.
300	33 pcs.
400	44 pcs.
500	55 pcs.
600	66 pcs.
700	77 pcs.
800	88 pcs.
900	99 pcs.
1000	110 pcs.
1500	164 pcs.
2000	219 pcs.
2500	273 pcs.
3000	328 pcs.
3500	382 pcs.
4000	437 pcs.
4500	491 pcs.
5000	546 pcs.

bled Stucco






CEDAR TEXTURE SHAKES

THE LUXURIOUS APPEAL OF CEDAR

- The look of traditional cedar with more durability for easier maintenance over time
- Staggered edges offer a lively, textured effect
- Can be used as a decorative accent or on the entire structure
- Shiplap ends for a clean appearance
- Reversible staggered or straight edge offers exceptional design versatility
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay

38 SERIES CEDAR TEXTURE SHAKES Full View





Staggered



Straight

Specifications: LP® SmartSide® Cedar Texture Shakes Coverage

Cedar Texture Shakes 4' Length	R	eveal (size)
Area (sq. ft.)	7″ (12″)	10″ (12″)
100	44 pcs.	31 pcs.
200	88 pcs.	61 pcs.
300	131 pcs.	92 pcs.
400	175 pcs.	122 pcs.
500	219 pcs.	152 pcs.
600	262 pcs.	183 pcs.
700	306 pcs.	213 pcs.
800	350 pcs.	244 pcs.
900	393 pcs.	274 pcs.
1000	437 pcs.	304 pcs.
1500	655 pcs.	456 pcs.
2000	873 pcs.	608 pcs.
2500	1091 pcs.	760 pcs.
3000	1310 pcs.	912 pcs.
3500	1528 pcs.	1064 pcs.
4000	1746 pcs.	1216 pcs.
4500	1964 pcs.	1368 pcs.
5000	2182 pcs.	1519 pcs.

Disclaimer: The above chart does not account for waste factors. Remember to include your expected jobsite waste. It is up to the purchaser to determine the appropriate waste factor to add to the material estimate. LP takes no responsibility for estimates, including overages or shortages of material based on the above coverage chart.

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series Cedar Texture Shakes	4ft. (48.63 in.)(1.2 m)	11.625 in. (295 mm)	0.354 in. (9 mm)	42092	1.5 PSF

Specifications: LP[®] SmartSide[®] Cedar Texture Panel Siding

CEDAR TEXTURE PANEL SIDING

DURABLE FROM TOP TO BOTTOM

- Shiplap edges with alignment bead for easier installation
- Primed for exceptional paint adhesion
- Lighter per square foot than comparable fiber cement panel
- Strong enough to be nailed directly to stud, making additional sheathing unnecessary in many applications
- Helps to eliminate need for additional bracing on load-bearing walls
- Excellent exterior for homes in areas of high winds
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay




Cedar Texture Panel


GROOVE DETAIL




38 SERIES CEDAR TEXTURE PANEL 8" O.C.



76 SERIES CEDAR TEXTURE PANEL 4" & 8" O.C.



190 SERIES CEDAR TEXTURE PANEL 8" O.C.




38 SERIES CEDAR TEXTURE – NO GROOVE DUAL USE SIDING AND SOFFIT PANEL



38 SERIES CEDAR TEXTURE PANEL - NO GROOVE



76 SERIES CEDAR TEXTURE PANEL - NO GROOVE



DESCRIPTION	LENGTH	GROOVE	GROOVE WIDTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series Cedar Texture Panel 8″ o.c.	6 ft. (72 in.)(1.8 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.354 in. (9 mm)	27805	1.5 PSF
	7 ft. (84 in.)(2.1 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.354 in. (9 mm)	27806	1.5 PSF
	8 ft. (96 in.)(2.4 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.354 in. (9 mm)	25840	1.5 PSF
	9 ft. (108 in.)(2.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.354 in. (9 mm)	25843	1.5 PSF
	10 ft. (120 in.)(3.0 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.354 in. (9 mm)	25844	1.5 PSF
	12 ft. (144 in.)(3.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.354 in. (9 mm)	25845	1.5 PSF
38 Series Cedar Texture Panel No Groove Shiplap Edge**	8 ft. (96 in.)(2.4 m)	No Groove	N/A	48.56 in. (1 234 mm)	0.354 in. (9 mm)	25855 *	1.5 PSF
	9 ft. (108 in.)(2.7 m)	No Groove	N/A	48.56 in. (1 234 mm)	0.354 in. (9 mm)	29189 *	1.5 PSF
	10 ft. (120 in.)(3.0 m)	No Groove	N/A	48.56 in. (1 234 mm)	0.354 in. (9 mm)	25825 *	1.5 PSF
38 Series Cedar Texture NGSE Dual Use Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	No Groove	N/A	47.88 in. (1 216 mm)	0.354 in. (9 mm)	41044	1.5 PSF
76 Series Cedar Texture Panel 4" and 8" o.c.	8 ft. (96 in.)(2.4 m)	4 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.418 in. (10.6 mm)	25831	1.5 PSF
	9 ft. (108 in.)(2.7 m)	4 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.418 in. (10.6 mm)	25832 *	1.5 PSF
	8 ft. (96 in.)(2.4 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm	0.418 in. (10.6 mm)	25848	1.5 PSF
	9 ft. (108 in.)(2.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.418 in. (10.6 mm)	25850	1.5 PSF
	10 ft. (120 in.)(3.0 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.418 in. (10.6 mm)	25851	1.5 PSF
76 Series Cedar Texture Panel No Groove Shiplap Edge**	8 ft. (96 in.)(2.4 m)	No Groove	N/A	48.56 in. (1 234 mm)	0.418 in. (10.6 mm)	25856	1.5 PSF
	9 ft. (108 in.)(2.7 m)	No Groove	N/A	48.56 in. (1 234 mm)	0.418 in. (10.6 mm)	25857	1.5 PSF
	10 ft. (120 in.)(3.0 m)	No Groove	N/A	48.56 in. (1 234 mm)	0.418 in. (10.6 mm)	25858	1.5 PSF
190 Series Cedar Texture 8″ o.c.	8 ft. (96 in.)(2.4 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.578 in. (14.7 mm)	25852	2 PSF
	9 ft. (108 in.)(2.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.578 in. (14.7 mm)	25853 *	2 PSF
	10 ft. (120 in.)(3.0 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (1 234 mm)	0.578 in. (14.7 mm)	25854 *	2 PSF

Rated for Structural Use by APA

*Special order item. Requires minimum quantity and extended lead times. **Coordinates with LP SmartSide Trim for board and batten applications.

Specifications: LP® SmartSide® Panel Siding Coverage

BRUSHED SMOOTH PANEL SIDING

DURABILITY NEVER LOOKED SO GOOD

- Primed for exceptional paint adhesion
- Lighter per square foot than comparable fiber cement panel
- Strong enough to be nailed directly to stud, making additional sheathing unnecessary in many applications
- Helps to eliminate need for additional bracing on load-bearing walls
- Excellent exterior for homes in areas of high winds
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay

Brushed Smooth Panel

Panel Siding		Si	ze	
Area (sq. ft.)	4´x 8´	4´x 9´	4´x 10´	4′x 12′
100	4 pcs.	3 pcs.	3 pcs.	3 pcs.
200	7 pcs.	6 pcs.	5 pcs.	5 pcs.
300	10 pcs.	9 pcs.	8 pcs.	7 pcs.
400	13 pcs.	12 pcs.	10 pcs.	9 pcs.
500	16 pcs.	14 pcs.	13 pcs.	11 pcs.
600	19 pcs.	17 pcs.	15 pcs.	13 pcs.
700	22 pcs.	20 pcs.	18 pcs.	15 pcs.
800	25 pcs.	23 pcs.	20 pcs.	17 pcs.
900	29 pcs.	25 pcs.	23 pcs.	19 pcs.
1000	32 pcs.	28 pcs.	25 pcs.	21 pcs.
1500	47 pcs.	42 pcs.	38 pcs.	32 pcs.
2000	63 pcs.	56 pcs.	50 pcs.	42 pcs.
2500	79 pcs.	70 pcs.	63 pcs.	53 pcs.
3000	94 pcs.	84 pcs.	75 pcs.	63 pcs.
3500	110 pcs.	98 pcs.	88 pcs.	73 pcs.
4000	125 pcs.	112 pcs.	100 pcs.	84 pcs.
4500	141 pcs.	125 pcs.	113 pcs.	94 pcs.
5000	157 pcs.	139 pcs.	125 pcs.	105 pcs.

38 SERIES BRUSHED SMOOTH PANEL - SQUARE EDGE



Specifications: LP[®] SmartSide[®] Brushed Smooth Panel Siding

DESCRIPTION	LENGTH	GROOVE	GROOVE WIDTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series Brushed Smooth No Groove Square Edge	8 ft. (96 in.)(2.4 m)	No Groove	N/A	47.88 in. (405 mm)	0.354 in. (9 mm)	46008	-

Rated for Structural Use by APA

*Special order item. Requires minimum quantity and extended lead times. **Coordinates with LP SmartSide Trim for board and batten applications.

Specifications: LP® SmartSide® Trim

CEDAR TEXTURE TRIM

THE CLASSIC APPEARANCE OF CEDAR

- Use for corners, window and door trims
- Narrow widths for more design flexibility
- Primed for exceptional paint adhesion
- 16' length can result in faster installation and fewer seams
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay





190 SERIES CEDAR TEXTURE TRIM





440 SERIES CEDAR TEXTURE TRIM 0.675 in. (17.1 mm 🖛 1.5 in., 2.5 in., 3.5 in., 5.5 in., 7.21 in., 9.21 in. or 11.21 in. ►

(38 mm, 64 mm, 89 mm, 140 mm, 183 mm, 234 mm or 285 mm



DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
190 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.578 in. (14.7 mm)	28448	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.578 in. (14.7 mm)	28450	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.578 in. (14.7 mm)	28452	2 PSF
440 Series Trim	16 ft. (192 in.)(4.9 m)	1.50 in. (38 mm)	0.675 in. (17.1 mm)	25877	2 PSF
	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.675 in. (17.1 mm)	25878	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	25880	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	25882	2 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	25883	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	25884	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	25885	2 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	1.50 in. (38 mm)	0.970 in. (24.6 mm)	25886 *	3 PSF
	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.970 in. (24.6 mm)	25887 *	3 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	25888	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	25890	3 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	25891	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	25892	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	25893	3 PSF
440 Series Ploughed Fascia	16 ft. (192 in.)(4.9 m)	5.47 in. (140 mm)	0.62 in. (17.1 mm)	27240 *	2 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.62 in. (17.1 mm)	27819 *	2 PSF

*Special order item. Requires minimum quantity and extended lead times.

Specifications: LP® SmartSide® Trim

BRUSHED SMOOTH TRIM

SMOOTH APPEARANCE, ADVANCED DURABILITY OF ENGINEERED WOOD

- Helps protect against moisture intrusion, impacts from hail, and damage from freeze/thaw cycles
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay
- 16' length can result in faster installation and fewer seams
- Primed for exceptional paint adhesion
- Backed by an industry-leading 5/50-year limited warranty



540 SERIES BRUSHED SMOOTH TRIM



DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
440 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.675 in. (17.1 mm)	45999	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.675 in. (17.1 mm)	46000	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.675 in. (17.1 mm)	46001	2 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.675 in. (17.1 mm)	46002	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.675 in. (17.1 mm)	46003	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.675 in. (17.1 mm)	46004	2 PSF
	16 ft. (192 in.)(4.9 m)	1.50 (38 mm)	0.675 in. (17.1 mm)	46012	2 PSF
540 Series Trim	16 ft. (192 in.)(4.9 m)	2.50 in. (64 mm)	0.970 in. (24.6 mm)	46010	3 PSF
	16 ft. (192 in.)(4.9 m)	1.50 (38 mm)	0.970 in. (24.6 mm)	46011	3 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (89 mm)	0.970 in. (24.6 mm)	45992	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (140 mm)	0.970 in. (24.6 mm)	45993	3 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	45995	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (234 mm)	0.970 in. (24.6 mm)	45997	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (285 mm)	0.970 in. (24.6 mm)	45998	3 PSF









Brushed Smooth Trim



CEDAR TEXTURE SOFFIT

THE FINISHING TOUCH

- Cut-to-width can help to eliminate time spent cutting full sheets down to size
- 38 Series engineered for closed soffit applications
- 76 Series and 190 Series are ideal for use as the starter course for roofs with exposed eaves
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay





Cedar Texture

CUT-TO-WIDTH


Specifications: LP® SmartSide® Soffit

BRUSHED SMOOTH SOFFIT


THE FINAL DETAIL TO MAXIMIZE CURB APPEAL

- Cut-to-width can help to eliminate time spent cutting full sheets down to size
- 38 Series engineered for closed soffit applications
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay

38 SERIES 4' x 8' CEDAR TEXTURE SOFFIT



76 SERIES 4' x 8' CEDAR TEXTURE SOFFIT



76 SERIES CEDAR TEXTURE SOFFIT -

11.94 in., 15.94 in. or 23.94 in. (303 mm, 405 mm or 608 mm)

38 SERIES CEDAR TEXTURE SOFFIT -



38 SERIES BRUSHED SMOOTH SOFFIT -**CUT-TO-WIDTH**



DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series Brushed Smooth Soffit - Cut-to-Width	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	46005	-
	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	46006	-
	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46009	-

190 SERIES 4' x 8' CEDAR TEXTURE SOFFIT



DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series 4´x 8´ Cedar Texture Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	25813	-
38 Series Cedar Texture Siding and Soffit Panel	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.354 in. (9 mm)	41044	-
76 Series 4' x 8' Cedar Texture Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.418 in. (10.6 mm)	25814	-
190 Series 4' x 8' Cedar Texture Soffit	8 ft. (96 in.)(2.4 m)	47.88 in. (1 216 mm)	0.578 in. (14.7 mm)	25816 *	-
38 Series Cedar Texture Soffit – Cut-to-Width	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	25805	-
	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	25806	-
	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	25807	-

*Special order item. Requires minimum quantity and extended lead times. | Metric units are rounded.







Brushed Smooth

CEDAR TEXTURE VENTED SOFFIT

ENGINEERED TO CUT OUT PROBLEMS

- Precisely cut vents offer 5 and 10 square inches of ventilation per linear foot, providing more options to meet code requirements while adding architectural beauty
- Promotes continuous airflow
- 1/8" vents to help keep hornets and most bees out
- Eliminates time spent ripping full sheets
- Treated with the SmartGuard[®] process for superior protection and resistance against many weather conditions, fungal decay and termites



Cedar Texture




BRUSHED SMOOTH VENTED SOFFIT

TIMELESS DESIGN MEETS EVERYDAY FUNCTIONALITY


- Precisely cut vents offer 10 square inches of ventilation per linear foot, providing more options to meet code requirements while adding architectural beauty
- Promotes continuous airflow
- 1/8" vents to help keep hornets and bees out
- Eliminates time spent ripping full sheets
- Treated with the SmartGuard[®] process for superior protection and resistance against many weather conditions, fungal decay and termites

38 SERIES VENTED BRUSHED SMOOTH SOFFIT - CUT-TO-WIDTH



DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series 10 sq. in. Vented Brushed Smooth Soffit - Cut-to-Width	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	46964	-
	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	46043	-
	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	46044	-

38 SERIES VENTED CEDAR TEXTURE SOFFIT - CUT-TO-WIDTH



DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series 5 sq. in. Vented Cedar Texture Soffit – Cut-to-Width	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	45450	-
	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	45451	-
38 Series 10 sq. in. Vented Cedar Texture Soffit – Cut-to-Width	16 ft. (192 in.)(4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	25822	-
	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	25823	-
	16 ft. (192 in.)(4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	25824	-




Brushed Smooth

Specifications: LP[®] SmartSide[®] Vertical Siding

VERTICAL SIDING

CREATE THE STYLISH APPEARANCE OF BOARD AND BATTEN

- 16' lengths can eliminate horizontal joints
- Coordinates with LP SmartSide Trim
- Primed for exceptional paint adhesion
- Not rated for structural use
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay
- Sheathing-only attachment



DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series Cedar Texture Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	40503	1.5 PSF
DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER	WEIGHT
38 Series Brushed Smooth Vertical Siding	16 ft. (192 in.)(4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	46007	-



Brushed Smooth

Specifications: LP[®] SmartSide[®] Vertical Siding Coverage

Vertical Siding	Reveal (size)
Area (sq. ft.)	15-15/16″ (16″)
100	5 pcs.
200	10 pcs.
300	15 pcs.
400	19 pcs.
500	24 pcs.
600	29 pcs.
700	33 pcs.
800	38 pcs.
900	43 pcs.
1000	48 pcs.
1500	71 pcs.
2000	95 pcs.
2500	118 pcs.
3000	142 pcs.
3500	165 pcs.
4000	189 pcs.
4500	212 pcs.
5000	236 pcs.

Specifications: LP® SmartSide® Accessories

J-BLOCKS

A COHESIVE LOOK FOR HOME EXTERIORS

- Allows for easier installation
- Primed for exceptional paint adhesion
- Available in cedar texture
- Used to easily and attractively mount light fixtures, water faucets and more
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay
- Backed by a 5/10-year limited warranty





Cedar Texture

Specifications:	LP®	SmartSide [®]	Acc
------------------------	-----	-------------------------------	-----

OUTSIDE CORNERS

TAKE CURB APPEAL TO THE NEXT LEVEL

- One-piece corners eliminate the need to build corners on the jobsite
- Faster and easier installation
- Designed to help prevent water intrusion
- Primed for exceptional paint adhesion

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER
Cedar Texture 7.25″ x 7.25″ J-Block	7.21 in. (183 mm)	7.21 in. (183 mm)	0.970 in. (24.6 mm)	43509

MINI-SPLITS

EASIER INSTALLATION FOR EXTERIOR FEATURES

- Easier installation
- Primed for exceptional paint adhesion
- Available in cedar texture
- Used to easily and attractively mount light fixtures, water faucets and more
- Treated with the SmartGuard[®] process for superior protection against many weather conditions and resistance to termites and fungal decay
- Backed by a 5/10-year limited warranty





Cedar Texture

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER
540 Series Cedar Texture	16 ft. (192 in.) (4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47113
Outside Corners	16 ft. (192 in.) (4.9 m)	5.625 in. (143 mm)	0.970 in. (24.6 mm)	47114
540 Series Brushed Smooth	16 ft. (192 in.) (4.9 m)	3.625 in. (92 mm)	0.970 in. (24.6 mm)	47193
Outside Corners	16 ft. (192 in.) (4.9 m)	5.625 in. (143 mm)	0.970 in. (24.6 mm)	47192

DESCRIPTION	LENGTH	ACTUAL WIDTH	THICKNESS	PID NUMBER
Cedar Texture 7.25″ x 6.75″ Mini Split	7.21 in. (183mm)	6.75 in. (171 mm)	0.970 in. (24.6 mm)	43510

essories





Brushed Smooth

NOTES

NOTES

•	
•	
•	
•	



BUILD BETTER WITH LP BUILDING SOLUTIONS

Building a Better World[™]

LP's mission is to provide an innovative and sustainable portfolio of high-quality products that help our customers build beautiful, durable homes and structures. With a united spirit of discovery, LP is forging ahead with innovative ideas to create new products that make a difference in the world.

LP WeatherLogic® Air & Water Barrier

LP WeatherLogic Air & Water Barrier provides moisture management technology for a better build. To protect against air and water for years to come, LP WeatherLogic Air & Water Barrier helps create a tight building envelope, installs easily, and keeps the jobsite clean.

LP® TechShield® Radiant Barrier

The original, #1 brand of radiant barrier, LP TechShield Radiant Barrier may reduce monthly cooling costs by blocking up to 97% of the radiant heat in the panel from emitting into a home's attic, lowering attic temperatures by up to 30° F.

LP Legacy[®] Premium Sub-Flooring

LP Legacy Premium Sub-Flooring uses Gorilla Glue Technology[®] for one of the strongest, stiffest sub-floors. The resin in Gorilla Glue Technology binds wood fibers at the molecular level for premium performance.

LP® FlameBlock® Fire-Rated Sheathing

LP FlameBlock Fire-Rated Sheathing has structural design values equal to OSB sheathing of the same performance category. Evaluated by ICC-ES, Intertek and UL, it combines flame-spread and burn-through resistance in a single panel.

LP NovaCore® Thermal Insulated Sheathing

LP NovaCore Thermal Insulated Sheathing combines OSB structural sheathing and Owens Corning[®] FOAMULAR[®] NGX[®] 250 Extruded Polystyrene (XPS) insulation for faster installation to protect against cold and heat.

LP® TopNotch® 350 Durable Sub-Flooring

LP TopNotch 350 Durable Sub-Flooring is designed for exceptional stability to create a strong, smooth foundation for a variety of finished flooring. We back LP TopNotch 350 Sub-Flooring with a 200-day "no-sand" warranty and a 50-year transferable limited warranty.

LP[®] ArchForm[™] Concrete Edge Form

LP ArchForm Concrete Edge Form is an engineered wood product designed for use in flatwork concrete forming applications, such as residential landscaping, patios, walkways, pool decks and more. It is flexible enough for curving to fit the contours of formed concrete projects and is backed by LP's industry-leading technology, service and support.





For more information, visit LPCorp.com/SmartSide

WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood.

© 2025 Louisiana-Pacific Corporation. All rights reserved. Sustainable Forestry Initiative, SFI and associated logo are registered trademarks of Sustainable Forestry Initiative, Inc. APA is a registered trademark of The Engineered Wood Association. Gorilla Glue Technology is a registered trademark of Gorilla Glue, Inc. Owens Corning, Foamular and NGX are registered trademarks of Owens Corning Intellectual Capital, LLC. All other trademarks are owned by Louisiana-Pacific Corporation. Specifications subject to change without notice. LPZB0946 2/25