

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Page: 1 of 10

1. Product and company identification

Product identifier

Trade name: SL=P070-B - Urethane Bonding Kit Part B

Relevant identified uses of the substance or mixture and uses advised against

General use: Adhesive, Component B, for orthopedic procedures.
For use in industrial installations and professional treatment only.

Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care
Street/POB-No.: 3820 W. Great Lakes Drive
Postal Code, city: Salt Lake City, UT 84120
USA
WWW: www.ottobockus.com
Telephone: +1 (801) 956-2400
Telefax: +1 (801) 956-2401
Department responsible for information: Quality Department,
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),
Email: USRegulatory@ottobock.com

Additional information: Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency phone number

CHEMTREC, Telephone: +1 (800) 424-9300
Transport:
CONSULTANK Lutz Harder GmbH (Contract QUALI003)
Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2. Hazards identification

Emergency overview

Appearance: Physical state at 68 °F and 101.3 kPa: liquid
Odor: No data available
Classification: Acute Toxicity - oral - Category 4. Eye Irritation - Category 2A. Sensitization - skin - Category 1. Specific Target Organ Toxicity (Repeated Exposure) - Category 2.
Aquatic toxicity - chronic - Category 2.

Hazard symbols:



Signal word:

Warning

**SL=P070-B - Urethane Bonding Kit
Part B**

Material number SL=P070-B

Revision date: 1/10/2025
Version: 16.1
Replaces version: 16.0
Language: en-US
Date of print: 9/2/2025

Page: 2 of 10

Hazard statements: Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure.
Toxic to aquatic life with long lasting effects.

Precautionary statements: Do not breathe mist/vapors/spray.
Wash hands and face thoroughly after handling.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
Collect spillage.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200).

Hazards not otherwise classified

Special danger of slipping by leaking/spilling product.
Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Polyol/Aromatic diamine blend

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 25322-69-4	Polypropylene glycol	72 - 73 %	Acute Toxicity - oral - Category 4.
CAS 68479-98-1	Diethylmethylbenzenediamine	17 - 18 %	Acute Toxicity - oral - Category 4. Acute Toxicity - dermal - Category 4. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Repeated Exposure) - Category 2. Aquatic toxicity - acute - Category 1. Aquatic toxicity - chronic - Category 1.
CAS 3147-75-9	2-(2H-Benzotriazol-2-yl)-4-(1,1,3,3-tetramethylbutyl)phenol	2 - 3 %	not classified
CAS 41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	1 - 2 %	Sensitization - skin - Category 1. Aquatic toxicity - acute - Category 1. Aquatic toxicity - chronic - Category 1.
CAS 82919-37-7	Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1 - 2 %	Sensitization - skin - Category 1. Aquatic toxicity - acute - Category 1. Aquatic toxicity - chronic - Category 1.

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Page: 3 of 10

4. First aid measures

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
In case of inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Do not give milk or alcoholic beverages. Seek medical attention.

Most important symptoms/effects, acute and delayed

May cause damage to organs through prolonged or repeated exposure. Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye irritation.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:	> 201.2 °F
Auto-ignition temperature:	No data available
Suitable extinguishing media:	Extinguishing is to be in accordance with the surrounding fire.
Extinguishing media which must not be used for safety reasons:	Full water jet

Specific hazards arising from the chemical

Combustible. Fires in the immediate vicinity may cause the development of dangerous vapors.
In case of fire may be liberated: Carbon dioxide, carbon monoxide, nitrogen oxides (NOx).

Protective equipment and precautions for firefighters:	Wear a self-contained breathing apparatus and chemical protective clothing.
--	---

Additional information:	Use fine water spray to cool endangered containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow water used to extinguish fire to enter drains, ground or waterways. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.
-------------------------	---

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Page: 4 of 10

6. Accidental release measures

Personal precautions:	Do not breathe mist/vapors/spray. Avoid contact with the substance. If possible, eliminate leakage. Provide adequate ventilation. Wear appropriate protective equipment. Keep unprotected people away. Take off contaminated clothing and wash it before reuse.
Environmental precautions:	Do not allow to enter into ground-water, surface water or drains. If necessary, notify appropriate authorities.
Methods for clean-up:	Soak up with absorbent materials such as sand, siliceus earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance. Collect in closed containers for disposal.
Additional information:	Special danger of slipping by leaking/spilling product.

7. Handling and storage

Handling

Advices on safe handling:	Provide adequate ventilation, and local exhaust as needed. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.
---------------------------	--

Storage

Requirements for storerooms and containers:	Keep container tightly closed and in a well-ventilated place. Keep container dry. Keep only in the original container. Protect from heat and direct sunlight. Store containers in upright position.
Hints on joint storage:	Keep away from food, drink and animal feedingstuffs.

8. Exposure controls / personal protection

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.
See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection:	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
Skin protection:	Wear suitable protective clothing. Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Page: 5 of 10

Respiratory protection: When vapors form: Use filter type A (= against vapors of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

General hygiene considerations:
Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing.
Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Have eye wash bottle or eye rinse ready at work place.

Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Physical state at 68 °F and 101.3 kPa: liquid
Odor:	No data available
Odor threshold:	No data available
pH:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	> 201.2 °F
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	at 77 °F: 1.0209 g/mL
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Viscosity, kinematic:	at 104 °F: > 21 mm²/s

10. Stability and reactivity

Reactivity:	Refer to subsection "Possibility of hazardous reactions".
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	No hazardous reaction when handled and stored according to provisions.
Conditions to avoid:	Protect from heat and direct sunlight. Protect from moisture contamination.

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Page: 6 of 10

Incompatible materials: No data available

Hazardous decomposition products:

Ammonia

Thermal decomposition: No data available

11. Toxicological information

Toxicological tests

Toxicological effects: Acute toxicity (oral): Acute Toxicity - oral - Category 4 = Harmful if swallowed.
ATEmix (calculated): 554.37 mg/kg
Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): > 5,000 mg/kg
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Based on available data, the classification criteria are not met.
May cause irritation
Serious eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Sensitization - skin - Category 1 = May cause an allergic skin reaction.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Lack of data.
Specific target organ toxicity (repeated exposure): Specific Target Organ Toxicity (Repeated Exposure) -
Category 2 = May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard: Lack of data.

Symptoms

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

12. Ecological information

Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

Mobility in soil

No data available

Persistence and degradability

Further details: No data available

Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains.

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Page: 7 of 10

13. Disposal considerations

Product

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

Package

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself.
Non-contaminated packages may be recycled.

14. Transport information

UN number

ADR/RID, IMDG, IATA-DGR:

UN 3082

UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

UN 3082,
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Diethylmethylbenzenediamine

Transport hazard class(es)

ADR/RID:

Class 9, Code: M6

IMDG:

Class 9, Subrisk -

IATA-DGR:

Class 9

Packing group


ADR/RID, IMDG, IATA-DGR:

III

Environmental hazards

Marine pollutant:

yes



Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SAFETY DATA SHEET

according to 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: 1/10/2025
Version: 16.1
Replaces version: 16.0
Language: en-US
Date of print: 9/2/2025

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Page: 8 of 10

USA: Department of Transportation (DOT)

Identification number: UN3082
Proper shipping name: UN 3082,
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. Diethylmethylbenzenediamine
Hazard class or Division: 9
Packing Group: III
Labels: 9
Symbols: G
Special Provisions: 8, 146, 173, 335, 441, IB3, T4, TP1, TP29
Packaging – Exceptions: 155
Packaging – Non-bulk: 203
Packaging – Bulk: 241
Quantity limitations – Passenger aircraft / rail: No limit
Quantity limitations – Cargo only: No limit
Vessel stowage – Location: A



Sea transport (IMDG)

UN number: UN 3082
Proper shipping name: UN 3082,
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Diethylmethylbenzenediamine
Class or division, Subsidiary risk: Class 9, Subrisk -
Packing Group: III
EmS: F-A, S-F
Special Provisions: 274 335 375 969
Limited quantities: 5 L
Excepted quantities: E1
Package - Instructions: P001, LP01
Package - Provisions: PP1
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP1, TP29
Stowage and handling: Category A.
Properties and observations: -
Marine pollutant: yes
Segregation group: none

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Page: 9 of 10

Air transport (IATA)

UN/ID number:	UN 3082
Proper shipping name::	UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Diethylmethylbenzenediamine
Class or division, Subsidiary risk:	Class 9
Packing Group:	III
Hazard label:	Miscellaneous & Environmentally hazardous
Excepted Quantity Code:	E1
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft:	Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
Cargo Aircraft only:	Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
Special Provisions:	A97 A158 A197 A215
Emergency Response Guide-Code (ERG):	9L

15. Regulatory information

National regulations - U.S. Federal Regulations

Polypropylene glycol:	TSCA Inventory: listed
Diethylmethylbenzenediamine:	TSCA Inventory: listed
2-(2H-Benzotriazol-2-yl)-4-(1,1,3,3-tetramethylbutyl)phenol:	TSCA Inventory: listed
Glycerol-Propylene oxide-polymer:	TSCA Inventory: listed
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate:	TSCA Inventory: listed
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:	TSCA Inventory: listed

National regulations - U.S. State Regulations

2-(2H-Benzotriazol-2-yl)-4-(1,1,3,3-tetramethylbutyl)phenol:	EPCRA · Section 302 (extremely hazardous substances): Substance is not listed. · Section 313 (Specific toxic chemical listings): Substance is not listed. CAA 112(r) Regulated Chemicals For Accidental Release Prevention: Substance is not listed.
--	--

16. Other information

Text for labeling:	Contains 72 - 73 % Polypropylene glycol, 17 - 18 % Diethylmethylbenzenediamine, 2 - 3 % 2-(2H-Benzotriazol-2-yl)-4-(1,1,3,3-tetramethylbutyl)phenol, 1 - 2 % Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, 1 - 2 % Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.
--------------------	--

SL=P070-B - Urethane Bonding Kit Part B

Material number SL=P070-B

Revision date: 1/10/2025
Version: 16.1
Replaces version: 16.0
Language: en-US
Date of print: 9/2/2025

Page: 10 of 10

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 2 (Moderate) - Chronic effects

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
X		

Abbreviations and acronyms:

Acute Toxicity: Acute toxicity
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aquatic toxicity - acute: Hazardous to the aquatic environment - acute
Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
ATEmix: Acute Toxicity Estimate of mixture
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
Eye Irritation: Eye irritation
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
MFSU: Manufacture, formulation, supply and use
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
Sensitization - skin: Skin sensitisation
STOT RE: Specific target organ toxicity - repeated exposure
SVHC: Substance of very high concern
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative

Reason of change: Changes in section 14: IMDG 2025

Date of first version: 11/3/2001

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.