



# SAFETY DATA SHEET

according to HCS 2024 (29 CFR 1910.1200)

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Revision date: 11/28/2025  
Version: 11.2  
Replaces version: 11.1  
Language: en-US  
Date of print: 5/29/2026

Page: 1 of 15

### 1. Identification

#### Product identifier

Trade name: 636K40 - Repositionable Spray Adhesive

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Adhesive-Aerosol for orthopedic procedures.  
Reserved for industrial and professional use.

#### Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care  
Street/POB-No.: 3820 W. Great Lakes Drive  
Zip code, city: Salt Lake City, UT 84120  
USA  
WWW: www.ottobockus.com  
Telephone: +1 (801) 956-2400  
Telefax: +1 (801) 956-2401  
Department responsible for information: Quality Department,  
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),  
Email: USRegulatory@ottobock.com  
Additional information: Corporate headquarters:  
Ottobock SE & Co. KGaA  
Max-Näder-Straße 15  
Duderstadt  
Germany

#### Emergency telephone number

CHEMTREC, Telephone: +1 (800) 424-9300  
Transport:  
CONSULTANK Lutz Harder GmbH (Contract QUALI003)  
Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

### 2. Hazard identification

#### Classification of the substance or mixture

Flammable Aerosol - Category 1	Extremely flammable aerosol.
Compressed Gas	Contains gas under pressure; may explode if heated.
Skin Irritation - Category 2	Causes skin irritation.
Eye Irritation - Category 2A	Causes serious eye irritation.
Specific Target Organ Toxicity (Single Exposure) - Category 3	May cause drowsiness or dizziness.
Aquatic toxicity - chronic - Category 3	Harmful to aquatic life with long lasting effects.

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 2 of 15

### Label elements

Symbols:



Signal word:

**Danger**

Hazard statements:

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Harmful to aquatic life with long lasting effects.

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Avoid breathing spray.  
Wear protective gloves/protective clothing/eye protection.  
Call a POISON CENTER/doctor if you feel unwell.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may lead to a narcotic effect.

## 3. Composition/information on ingredients

### Mixtures

Chemical characterization: Blend of active ingredients with propellant.  
Contains acrylate polymer (5-10%) and non volatile content (1-5%)

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 3 of 15

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 67-64-1	Acetone	25 - 35 %	Flammable Liquid - Category 2. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 64742-49-0	Hydrocarbons, C6, isoalkanes, < 5% n-hexane	7 - 13 %	Flammable Liquid - Category 2. Skin Irritation - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	7 - 13 %	Flammable Liquid - Category 2. Skin Irritation - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 109-66-0	n-Pentane	1 - 5 %	Flammable Liquid - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 78-78-4	i-Pentane	0.5 - 1.5 %	Flammable Liquid - Category 1. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 106-97-8	n-Butane, pure	10 - 20 %	Flammable Gas - Category 1. Liquefied Gas.
CAS 74-98-6	Propane	10 - 20 %	Flammable Gas - Category 1. Liquefied Gas.
CAS 75-28-5	Isobutane	5 - 10 %	Flammable Gas - Category 1. Liquefied Gas.

The actual concentration or concentration range is withheld as a trade secret.

## 4. First aid measures

General information:	In case of accident or if you feel unwell, seek medical advice immediately.
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. If the casualty has difficulty breathing, call a doctor immediately.
Following skin contact:	Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with soap and plenty of water. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Seek the attention of an ophthalmologist immediately.
After swallowing:	Do not induce vomiting. Rinse mouth and seek medical attention immediately.

### Most important symptoms/effects, acute and delayed

In case of inhalation: Cough, sneeze, shortage of breath, hoarseness, sore throat.  
After resorption: nausea, drowsiness, headache, agitation, fatigue, dizziness, unconsciousness. Reaction time and coordination may be impaired.  
In case of high vapor concentrations: Causes damage to heart if inhaled. Attention Fatal.  
Symptoms: cardiac arrhythmias, Thoracic oppression.  
After contact with skin:  
Upon direct contact with skin may cause itching and redness. Other symptoms: oedema (swelling).  
Repeated exposure may cause skin dryness or cracking.  
After eye contact:  
redness, swelling of the conjunctive tissues, pain, Risk of corneal clouding.  
vision impairment

### Information to physician

Do not give adrenaline or other stimulants. (Except in case of absolute necessity.)  
No specific antidote known. Treatment methods and measures are determined by the physician's judgement in consultation with the patient.

## 5. Fire-fighting measures

### Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

Extinguishing is to be in accordance with the surrounding fire.

Extinguishing media which must not be used for safety reasons:

Full water jet

### Specific hazards arising from the chemical

Extremely flammable aerosol. Pressurised container: May burst if heated.  
Vapors may proceed on the ground over great distances and cause fire and backflashes.  
In case of fire may be liberated: hydrocarbons, Carbon monoxide and carbon dioxide.

### Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus.

Additional information:

Heating causes rise in pressure with risk of bursting.  
Use fine water spray to cool endangered containers.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.  
Provide for good room ventilation, suctioning/venting.  
Do not breathe vapor/aerosol. Avoid contact with the substance.  
Keep unprotected people away. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

Environmental precautions:

Do not allow to enter soil, sewage, water bodies, lower level rooms or pits.

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 5 of 15

### Methods and material for containment and cleaning up

Methods for clean-up: Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Final cleaning.

Additional information: Special danger of slipping by leaking/spilling product.

## 7. Handling and storage

### Precautions for safe handling

Advices on safe handling: Use only in well-ventilated areas. Do not breathe vapor/aerosol. Avoid contact with skin, eyes, and clothing. When using do not eat, drink or smoke. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.

Precautions against fire and explosion:

Air combined with vapors may form potentially explosive mixtures that are heavier than air. Keep away from sources of ignition - No smoking. Use only non-sparking tools. Protect from direct exposure to sunlight and temperatures exceeding 122 °F. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Take precautionary measures against static discharges. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects.

### Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place. Keep container dry. Keep only in the original container. Protect from heat and direct sunlight. Store containers in upright position. Electrical equipment must be explosion protected according to standards. (DIN VDE 0165)

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids.

keep away from Oxidizing agents (e.g. chlorine, Chromic acid).

Keep away from food, drink and animal feedingstuffs.

Further details:

Heating causes rise in pressure with risk of bursting.

### 8. Exposure controls/personal protection

#### Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
67-64-1	Acetone	USA: ACGIH: STEL	500 ppm
		USA: ACGIH: TWA	250 ppm
		USA: IDLH: TWA	2,500 ppm
		USA: NIOSH: TWA	590 mg/m <sup>3</sup> ; 250 ppm
		USA: OSHA: TWA	2,400 mg/m <sup>3</sup> ; 1,000 ppm
109-66-0	n-Pentane	USA: ACGIH: TWA	2,950 mg/m <sup>3</sup> ; 1,000 ppm
		USA: IDLH: TWA	1,500 ppm [10% LEL]
		USA: NIOSH: Ceiling	1,800 mg/m <sup>3</sup> ; 610 ppm
		USA: NIOSH: TWA	350 mg/m <sup>3</sup> ; 120 ppm
		USA: OSHA: TWA	2,950 mg/m <sup>3</sup> ; 1,000 ppm
78-78-4	i-Pentane	USA: ACGIH: TWA	2,950 mg/m <sup>3</sup> ; 1,000 ppm
		USA: OSHA: TWA	2,950 mg/m <sup>3</sup> ; 1,000 ppm
106-97-8	n-Butane, pure	USA: ACGIH: TWA	1,000 ppm
		USA: IDLH: TWA	1,600 ppm [>10% LEL]
		USA: NIOSH: TWA	1,900 mg/m <sup>3</sup> ; 800 ppm
74-98-6	Propane	USA: IDLH: TWA	2,100 ppm [10% LEL]
		USA: NIOSH: TWA	1,800 mg/m <sup>3</sup> ; 1,000 ppm
		USA: OSHA: TWA	1,800 mg/m <sup>3</sup> ; 1,000 ppm
75-28-5	Isobutane	USA: ACGIH: TWA	1,000 ppm
		USA: NIOSH: TWA	1,900 mg/m <sup>3</sup> ; 800 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
67-64-1	Acetone	USA: ACGIH-BEI, urine	25 mg/L	acetone	end of exposure or end of shift

#### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Personal protection equipment (PPE)

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. Wear half-mask respirator with combination filter for organic vapors and particles.

Hand protection: Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Glove material: Fluororubber (Viton) - Breakthrough time: > 480 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Body protection: Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 7 of 15

### General hygiene considerations:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools.  
Protect from direct exposure to sunlight and temperatures exceeding 122 °F. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.  
Avoid contact with skin, eyes, and clothing. When using do not eat, drink or smoke. Do not breathe vapor/aerosol. Wash hands before breaks and after work.  
Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.

### Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state at 68 °F and 101.3 kPa	liquid
	Form: Aerosol
Color:	colorless
Odor:	sweet
Odor threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	No data available
Explosion limits:	No data available
Flash point/flash point range:	<= -50.8 °F
Evaporation rate:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Viscosity:	No data available
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	No data available
Vapor pressure:	No data available
Density:	0.71 g/mL (active agent)
Vapor density:	No data available
Particle characteristics:	Not applicable

### Additional information

Additional information: No data available

## 10. Stability and reactivity

Reactivity: Extremely flammable aerosol.  
Air combined with vapors may form potentially explosive mixtures that are heavier than air.  
Vapors may proceed on the ground over great distances and cause fire and backflashes.

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 8 of 15

Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Pressurised container: May burst if heated.
Conditions to avoid:	Do not heat spray cans over 122 °F. Do not force spray can open. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Keep away from sources of ignition - No smoking.
Incompatible materials:	No data available
Hazardous decomposition products:	No hazardous decomposition products when regulations for storage and handling are observed.

## 11. Toxicological information

### Information on toxicological effects

Toxicological effects:	<p>The statements are derived from the properties of the single components. No toxicological data is available for the product as such.</p> <p>Acute toxicity (oral): Based on available data, the classification criteria are not met. ATEmix (calculated): 2,000 mg/kg &lt;= ATE &lt; 5,000 mg/kg</p> <p>Acute toxicity (dermal): Based on available data, the classification criteria are not met. ATEmix (calculated): 2,000 mg/kg &lt;= ATE &lt; 5,000 mg/kg</p> <p>Acute toxicity (inhalative): Based on available data, the classification criteria are not met. ATEmix (calculated): 20 - 50 mg/L</p> <p>Skin corrosion/irritation: Skin Irritation - Category 2 = Causes skin irritation.</p> <p>Serious eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.</p> <p>Sensitisation to the respiratory tract: Lack of data.</p> <p>Skin sensitisation: Lack of data.</p> <p>Germ cell mutagenicity/Genotoxicity: Lack of data.</p> <p>Carcinogenicity: Lack of data.</p> <p>Reproductive toxicity: Lack of data.</p> <p>Effects on or via lactation: Lack of data.</p> <p>Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) - Category 3 = May cause drowsiness or dizziness.</p> <p>Specific target organ toxicity (repeated exposure): Lack of data.</p> <p>Aspiration hazard: Lack of data.</p>
------------------------	---



## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 9 of 15

### Other information:

#### Information about Acetone:

LD50 Rat, oral: 5,800 mg/kg  
LD50 Rabbit, dermal: > 15,688 mg/kg  
LC50 Rat, inhalative (vapor): 76 mg/L/4h

#### Information about Hydrocarbons, C6, isoalkanes, < 5% n-hexane:

LD50 Rat, oral: > 16,750 mg/kg  
LD50 Rabbit, dermal: > 3,350 mg/kg  
LC50 Rat, inhalative (vapor): > 259 mg/L/4h

#### Information about Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

LD50 Rat, oral: > 5,840 mg/kg  
LD50 Rabbit, dermal: > 2,920 mg/kg  
LC50 Rat, inhalative (vapor): > 23.3 mg/L/4h

#### Information about acrylate polymer:

LD50 oral (estimated): > 2,000 mg/kg  
LD50 dermal (estimated): > 5,000 mg/kg

#### Information about non volatile content:

LD50 oral: > 34,000 mg/kg  
LD50 dermal (estimated): > 5,000 mg/kg

#### Information about Pentane:

LD50 Rat, oral: > 2,000 mg/kg  
LD50 Rabbit, dermal: 3,000 mg/kg  
LC50 Rat, inhalative (vapor): > 18 mg/L/4h

#### Information about 2-Methylbutane:

LD50 Rat, oral: > 2,000 mg/kg  
LD50 Rabbit, dermal: 3,000 mg/kg  
LC50 Rat, inhalative (vapor): > 18 mg/L/4h

#### Information about Butane:

LC50 Rat, inhalative (gas): 277,000 ppm

#### Information about Propane:

LC50 Rat, inhalative (gas): > 200,000 ppm

#### Information about Isobutane:

LC50 Rat, inhalative (gas): 276,000 ppm

## Symptoms

In case of inhalation: Cough, sneeze, shortage of breath, hoarseness, sore throat.

After resorption: nausea, drowsiness, headache, agitation, fatigue, dizziness, unconsciousness. Reaction time and coordination may be impaired.

In case of high vapor concentrations: Causes damage to heart if inhaled. Attention Fatal.

Symptoms: cardiac arrhythmias, Thoracic oppression.

After contact with skin:

Upon direct contact with skin may cause itching and redness. Other symptoms: oedema (swelling).

Repeated exposure may cause skin dryness or cracking.

After eye contact:

redness, swelling of the conjunctive tissues, pain, Risk of corneal clouding.  
vision impairment

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 10 of 15

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

Information about Hydrocarbons, C6, isoalkanes, < 5% n-hexane:

Fish toxicity:

LL50 Oncorhynchus mykiss: 18.27 mg/L/96h (QSAR)

NOELR Oncorhynchus mykiss: 4.089 mg/L/28d (QSAR)

Daphnia toxicity:

EL50 Daphnia magna (Big water flea): 31.9 mg/L/48h (QSAR)

NOELR Daphnia magna (Big water flea): 7.138 mg/L/21d (QSAR)

Algae toxicity:

EL50 Pseudokirchneriella subcapitata (green algae): 13.56 mg/L/72h (QSAR)

NOELR Pseudokirchneriella subcapitata (green algae): 3.034 mg/L/72h (QSAR)

Information about Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Fish toxicity:

LL50 Oncorhynchus mykiss: > 13.4 mg/L/96h (OECD 203)

NOELR Oncorhynchus mykiss: 1.534 mg/L/28d (QSAR)

Daphnia toxicity:

EL50 Daphnia magna (Big water flea): 3 mg/L/48h (OECD 202)

NOELR Daphnia magna (Big water flea): 1 mg/L/21d (OECD 211)

Algae toxicity:

EL50 Pseudokirchneriella subcapitata (green algae): 10-30 mg/L/72h (OECD 201)

NOELR Pseudokirchneriella subcapitata (green algae): 6.3 mg/L/72h (OECD 201)

### Persistence and degradability

Further details: No data available

### Bioaccumulative potential

Partition coefficient: n-octanol/water:  
No data available

### Mobility in soil

No data available

### Other adverse effects

General information: Special benzine:  
Danger to drinking water when soaking into the soil or waters.  
Do not allow to penetrate into soil, waterbodies or drains.

## 13. Disposal considerations

### Waste treatment methods

#### Product

Recommendation: Do not open with force or incinerate, even when empty.  
Dispose of as hazardous waste. Dispose of waste according to applicable legislation.

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 11 of 15

### Package

Recommendation: Empty carefully and completely, if possible.  
Dispose of waste according to applicable legislation.

## 14. Transport information

### UN number

DOT: UN1950  
IMDG, IATA-DGR: UN 1950

### UN proper shipping name

DOT, IMDG: UN 1950, AEROSOLS  
IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

### Transport hazard class(es)

DOT: 2.1  
IMDG: Class 2.1, Subrisk -  
IATA-DGR: Class 2.1



### Packing group

DOT, IATA-DGR: not applicable  
IMDG: -

### Environmental hazards

Marine pollutant: no

### Transport in bulk according to IMO instruments

No data available

### Special precautions for user

#### USA: Department of Transportation (DOT)

Labels: 2.1  
Special Provisions: N82  
Packaging – Exceptions: 306  
Packaging – Non-bulk: None  
Packaging – Bulk: None  
Quantity limitations – Passenger aircraft / rail: 75 kg  
Quantity limitations – Cargo only: 150 kg  
Vessel stowage – Location: A  
Vessel stowage – Other: 25, 87, 126, 157



# SAFETY DATA SHEET

according to HCS 2024 (29 CFR 1910.1200)

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Revision date: 11/28/2025  
Version: 11.2  
Replaces version: 11.1  
Language: en-US  
Date of print: 5/29/2026

Page: 12 of 15

### Sea transport (IMDG)

EmS: F-D, S-U  
Special Provisions: 63 190 277 327 344 381 959  
Limited quantities: 1000 mL  
Excepted quantities: E0  
Package - Instructions: P207, LP200  
Package - Provisions: PP87, L2  
IBC - Instructions: -  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: -  
Tank instructions - Provisions: -  
Stowage and handling: SW1 SW22  
Segregation: SG69  
Properties and observations: -  
Marine pollutant: no  
Segregation group: none

### Air transport (IATA)

Proper shipping name: UN 1950, AEROSOLS, FLAMMABLE  
Hazard label: Flamm. gas  
Excepted Quantity Code: E0  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg  
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg  
Special Provisions: A145 A167 A802  
Emergency Response Guide-Code (ERG): 10L

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 13 of 15

### 15. Regulatory information

#### National regulations - U.S. Federal Regulations

Acetone:	TSCA Inventory: listed Clean Air Act: CAA SOCM Chemical: yes Other Environmental Laws: CERCLA: RQ 5000 lbs. RCRA Groundwater Monitoring: listed NIOSH Recommendations: Occupational Health Guideline: 0004*
n-Pentane:	TSCA Inventory: listed Clean Air Act: CAA Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = g NIOSH Recommendations: Occupational Health Guideline: 0486
i-Pentane:	TSCA Inventory: listed Clean Air Act: CAA Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = g
n-Butane, pure:	TSCA Inventory: listed Clean Air Act: CAA Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0068*
Propane:	TSCA Inventory: listed Clean Air Act: CAA Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0524
Isobutane:	TSCA Inventory: listed Clean Air Act: CAA Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0350*

#### National regulations - U.S. State Regulations

Acetone:	New York Right-To-Know: listed
----------	--------------------------------

#### Further regulations, limitations and legal requirements

No data available

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 14 of 15

### 16. Other information

**Text for labeling:** Contains 25 - 35 % Acetone, 7 - 13 % Hydrocarbons, C6, isoalkanes, < 5% n-hexane, 7 - 13 % Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, 1 - 5 % n-Pentane, 0.5 - 1.5 % i-Pentane, 10 - 20 % n-Butane, pure, 10 - 20 % Propane, 5 - 10 % Isobutane.  
38 percent of the mixture consists of ingredient(s) of unknown acute toxicity (oral).  
3 percent of the mixture consists of components of unknown hazards to the aquatic environment.

**Revision date:** 11/28/2025

**Date of first version:** 1/6/2021

**Reason of change:** General revision: Safety Data Sheet according to HCS 2024 (29 CFR 1910.1200)

**Hazard rating systems:**



**NFPA Hazard Rating:**

Health: 2 (Moderate)

Fire: 4 (Severe)

Reactivity: 0 (Minimal)

**HMIS Version III Rating:**

Health: 2 (Moderate)

Flammability: 4 (Severe)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	0
	X

**Abbreviations and acronyms:**

Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic  
AS/NZS: Australian Standards/New Zealand Standards  
Aspiration Toxicity: Aspiration toxicity  
ATEmix: Acute Toxicity Estimate of mixture  
CAS: Chemical Abstracts Service  
CFR: Code of Federal Regulations  
CLP: Classification, Labelling and Packaging  
DMEL: Derived minimal effect level  
DNEL: Derived no-effect level  
DOT: Department of Transportation's Safety Regulations (USA)  
EC: European Community  
EL50: Effective loading rate 50%  
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods  
EN: European Standard  
EQ: Excepted quantities  
Eye Irritation: Eye irritation  
Flammable Gas: Flammable gases  
Flammable Liquid: Flammable liquid  
IATA: International Air Transport Association  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
IMDG Code: International Maritime Dangerous Goods Code  
IMO: International Maritime Organization  
LC50: Median lethal concentration  
LD50: Lethal dose 50%  
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
OECD: Organisation for Economic Co-operation and Development  
OEL: Occupational Exposure Limit Value  
OSHA: Occupational Safety and Health Administration  
PBT: Persistent, bioaccumulative and toxic  
PNEC: Predicted no-effect concentration  
QSAR: Quantitative Structure-Activity Relationship  
Skin Irritation: Skin irritation  
STOT SE: Specific target organ toxicity - single exposure  
TLV: Threshold Limit Value  
TRGS: Technical Rules for Hazardous Substances  
UN: United Nations  
vPvB: Very persistent and very bioaccumulative  
WEL: Workplace Exposure Limit



# SAFETY DATA SHEET

according to HCS 2024 (29 CFR 1910.1200)

## 636K40 - Repositionable Spray Adhesive

Material number 636K40

Revision date: 11/28/2025  
Version: 11.2  
Replaces version: 11.1  
Language: en-US  
Date of print: 5/29/2026

Page: 15 of 15

### Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.