



SAFETY DATA SHEET

according to HCS 2024 (29 CFR 1910.1200)

636W1 - OTTO BOCK Universal Adhesive

Material number 636W 1

Revision date: 12/17/2025
Version: 16.4
Replaces version: 16.3
Language: en-US
Date of print: 5/29/2026

Page: 1 of 15

1. Identification

Product identifier

Trade name: 636W1 - OTTO BOCK Universal Adhesive

Relevant identified uses of the substance or mixture and uses advised against

General use: Adhesive for orthopedic procedures.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care
Street/POB-No.: 3820 W. Great Lakes Drive
Zip code, city: Salt Lake City, UT 84120
USA
WWW: www.ottobockus.com
Telephone: +1 (801) 956-2400
Telefax: +1 (801) 956-2401
Department responsible for information: Quality Department,
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),
Email: USRegulatory@ottobock.com
Additional information: Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency telephone number

CHEMTREC, Telephone: +1 (800) 424-9300
Transport:
CONSULTANK Lutz Harder GmbH (Contract QUALI003)
Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2. Hazard identification

Classification of the substance or mixture

Flammable Liquid - Category 2	Highly flammable liquid and vapor.
Eye Irritation - Category 2	Causes serious eye irritation.
Reproductive toxicant - Category 2	Suspected of damaging the unborn child.
Specific Target Organ Toxicity (Single Exposure) - Category 3	May cause drowsiness or dizziness.
Specific Target Organ Toxicity (Repeated Exposure) - Category 2	May cause damage to organs through prolonged or repeated exposure.

636W1 - OTTO BOCK Universal Adhesive

Material number 636W 1

Page: 2 of 15

Label elements

Symbols:



Signal word:

Danger

Hazard statements:

Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

Obtain special instructions before use.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe vapors.
Wash hands and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a POISON CENTER/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use ... to extinguish.

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Dispose of contents/container to hazardous or special waste collection point.

Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.
Special danger of slipping by leaking/spilling product. the product is skin resorptive

3. Composition/information on ingredients

Mixtures

Chemical characterization: Cellulose in organic solvents.

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 67-64-1	Acetone	35 - 40 %	Flammable Liquid - Category 2. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 141-78-6	Ethyl acetate	20 - 25 %	Flammable Liquid - Category 2. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 108-88-3	Toluene	10 - 15 %	Flammable Liquid - Category 2. Skin Irritation - Category 2. Reproductive toxicant - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Specific Target Organ Toxicity (Repeated Exposure) - Category 2. Aspiration Toxicity - Category 1.
CAS 67-63-0	Isopropyl alcohol	5 - 10 %	Flammable Liquid - Category 2. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 123-86-4	n-Butyl acetate	1 - 5 %	Flammable Liquid - Category 3. Specific Target Organ Toxicity (Single Exposure) - Category 3.
CAS 108-94-1	Cyclohexanone	< 1 %	Flammable Liquid - Category 3. Acute Toxicity - inhalative - Category 4.

The actual concentration or concentration range is withheld as a trade secret.

4. First aid measures

General information:	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). First aider: Pay attention to self-protection!
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. In case of irregular breathing or respiratory arrest provide artificial respiration. Seek medical attention. If victim is at risk of losing consciousness, position and transport on their side.
Following skin contact:	After contact with skin, wash immediately with soap and plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Immediately get medical attention.

Most important symptoms/effects, acute and delayed

May cause drowsiness or dizziness. Causes serious eye irritation.

Information to physician

Combat acidosis. Monitor alkali reserves.
Monitor breathing. If breathing becomes irregular or ceases, apply rescue breathing or artificial respiration immediately, where required supply oxygen.
Attention: several hours latency period.
Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

Water spray jet, Sand, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Strong water jet Full water jet

Specific hazards arising from the chemical

Highly flammable liquid and vapor.
Air combined with vapors may form potentially explosive mixtures that are heavier than air. Vapors may proceed on the ground over great distances and cause fire and backflashes.
In case of fire may be liberated: carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Use fine water spray to cool endangered containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapors. Avoid contact with the substance.
Eliminate all ignition sources if safe to do so. If possible, eliminate leakage. Provide adequate ventilation.
Wear appropriate protective equipment. Keep unprotected people away.
Take off contaminated clothing and wash it before reuse. Cordon off downwind area at risk and warn inhabitants.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.
If necessary, notify appropriate authorities.

Methods and material for containment and cleaning up

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).
Beware of reignition. Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.
Special danger of slipping by leaking/spilling product.

7. Handling and storage

Precautions for safe handling

Advices on safe handling: Obtain special instructions before use. Provide adequate ventilation, and local exhaust as needed. Avoid breathing vapors. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
Guarantee sufficient ventilation during and after use, in order to prevent vapor accumulation.
When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.
Use only explosion-protected equipment/instruments. Do not weld.
In partially filled containers explosive mixtures may form.

Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place. Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.
Keep away from acids and oxidizing agents.
On contact with barium hydroxide, sodium hydroxide and many other alkaline materials condensation may occur. Attacks many plastics and rubbers.

636W1 - OTTO BOCK Universal Adhesive

Material number 636W 1

Page: 6 of 15

8. Exposure controls/personal protection

Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
67-64-1	Acetone	USA: ACGIH: STEL	500 ppm
		USA: ACGIH: TWA	250 ppm
		USA: IDLH: TWA	2,500 ppm
		USA: NIOSH: TWA	590 mg/m ³ ; 250 ppm
		USA: OSHA: TWA	2,400 mg/m ³ ; 1,000 ppm
141-78-6	Ethyl acetate	USA: ACGIH: TWA	1,440 mg/m ³ ; 400 ppm
		USA: IDLH: TWA	2,000 ppm [10% LEL]
		USA: NIOSH: TWA	1,400 mg/m ³ ; 400 ppm
		USA: OSHA: TWA	1,400 mg/m ³ ; 400 ppm
108-88-3	Toluene	USA: ACGIH: TWA	20 ppm
		USA: IDLH: TWA	500 ppm
		USA: NIOSH: STEL	560 mg/m ³ ; 150 ppm
		USA: NIOSH: TWA	375 mg/m ³ ; 100 ppm
		USA: OSHA: Ceiling	500 ppm
		USA: OSHA: STEL	300 ppm
		USA: OSHA: TWA	200 ppm
67-63-0	Isopropyl alcohol	USA: ACGIH: STEL	984 mg/m ³ ; 400 ppm
		USA: ACGIH: TWA	492 mg/m ³ ; 200 ppm
		USA: IDLH: TWA	2,000 ppm [10% LEL]
		USA: NIOSH: STEL	1,225 mg/m ³ ; 500 ppm
		USA: NIOSH: TWA	980 mg/m ³ ; 400 ppm
		USA: OSHA: TWA	980 mg/m ³ ; 400 ppm
123-86-4	n-Butyl acetate	USA: ACGIH: STEL	150 ppm
		USA: ACGIH: TWA	50 ppm
		USA: IDLH: TWA	1,700 ppm
		USA: NIOSH: STEL	950 mg/m ³ ; 200 ppm
		USA: NIOSH: TWA	710 mg/m ³ ; 150 ppm
108-94-1	Cyclohexanone	USA: OSHA: TWA	710 mg/m ³ ; 150 ppm
		USA: ACGIH: TWA	50 mg/m ³ ; 20 ppm
			(may be absorbed through the skin)
		USA: IDLH: TWA	700 ppm
		USA: NIOSH: TWA	100 mg/m ³ ; 25 ppm
			(may be absorbed through the skin)
		USA: OSHA: TWA	200 mg/m ³ ; 50 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
67-64-1	Acetone	USA: ACGIH-BEI, urine	25 mg/L	acetone	end of exposure or end of shift
108-88-3	Toluene	USA: ACGIH-BEI, blood	0.02 mg/L	Toluene in blood	Prior to last shift of workweek
		USA: ACGIH-BEI, urine	0.03 mg/L	Toluene in urine	end of exposure or end of shift
		USA: ACGIH-BEI, urine	0.3 mg/g creatinine	o-Cresol in urine	end of exposure or end of shift
67-63-0	Isopropyl alcohol	USA: ACGIH-BEI, urine	40 mg/L	Acetone in urine	end of shift at end of work week
108-94-1	Cyclohexanone	USA: ACGIH-BEI, urine	8 mg/L	Cyclohexanol	end of exposure or end of shift
		USA: ACGIH-BEI, urine	80 mg/L	1,2-Cyclohexaned iol	end of shift at end of work week

Appropriate engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

Personal protection equipment (PPE)

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. Use filter type A (= against vapors of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.

Hand protection: Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Glove material: Nitrile rubber - Layer thickness 0,1 mm. Breakthrough time: > 480 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Body protection: Flame retardant, antistatic and chemical resistant protective clothing.

General hygiene considerations: Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapors. Do not get in eyes, on skin, or on clothing. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink. Wash hands thoroughly after handling. When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state at 68 °F and 101.3 kPa	liquid
Color:	colorless clear
Odor:	Solvent-like
Odor threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	132.89 °F
Flammability:	Highly flammable liquid and vapor.
Explosion limits:	LEL (Lower Explosion Limit): 1.10 Vol-% UEL (Upper Explosive Limit): 13.00 Vol-%
Flash point/flash point range:	1.4 °F
Evaporation rate:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Dynamic viscosity:	at 68 °F: 7,000 mPa*s
Water solubility:	at 68 °F: immiscible
Partition coefficient: n-octanol/water:	-0.23 log P(o/w) (Acetone) Based on the n-octanol/water partition coefficient accumulation in organisms is not expected. 2.73 log P(o/w) (Toluene) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected. 0.68 log P(o/w) (ethyl acetate) Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.
Vapor pressure:	at 68 °F: 70 hPa at 122 °F: (Acetone) 800 hPa
Density:	at 68 °F: 1.01 g/mL
Vapor density:	No data available
Particle characteristics:	Not applicable

Additional information

Explosive properties:	Vapors may form explosive mixtures with air.
Ignition temperature:	779 °F

10. Stability and reactivity

Reactivity:	Highly flammable liquid and vapor. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Heating will lead to pressure increase: danger of bursting and explosion.

Conditions to avoid: Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

Incompatible materials: Attacks many plastics and rubbers.
On contact with barium hydroxide, sodium hydroxide and many other alkaline materials condensation may occur.
Keep away from acids and oxidizing agents.

Hazardous decomposition products: No hazardous decomposition products when regulations for storage and handling are observed.

11. Toxicological information

Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Lack of data.

Serious eye damage/irritation: Eye Irritation - Category 2 = Causes serious eye irritation.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Reproductive toxicant - Category 2 = Suspected of damaging the unborn child.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) - Category 3 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Specific Target Organ Toxicity (Repeated Exposure) - Category 2 = May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: Based on available data, the classification criteria are not met.

636W1 - OTTO BOCK Universal Adhesive

Material number 636W 1

Page: 10 of 15

Other information:

Information about Acetone:
LD50 Rat, oral: 5,800 mg/kg
LD50 Rabbit, dermal: > 7,426 mg/kg
LC50 Rat, inhalative, vapor: 76 mg/L/4h

Information about Ethyl acetate:
LD50 Rabbit, oral: > 4,934 mg/kg
LD50 Rabbit, dermal: > 20,000 mg/kg

Information about Toluene:
LD50 Rat, oral: > 5,000 mg/kg
LD50 Rabbit, dermal: > 5,000 mg/kg
LC50 Rat, inhalative, vapor: 30 mg/L/4h

Symptoms

Symptoms: Headache, dizziness, fatigue, muscle weakness, numbing effect and, in exceptional cases, unconsciousness. Danger of metabolic acidosis.

In case of inhalation: Vapors may cause drowsiness and dizziness.

In case of ingestion:
The absorption of even very small amounts of this product through the stomach may lead to health problems. Symptoms: Gastric and intestinal problems.

After contact with skin: Repeated exposure may cause skin dryness or cracking.
The product can be absorbed through skin.

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

12. Ecological information

Ecotoxicity

Aquatic toxicity:

Information about Acetone:
Fish toxicity: LC50 Pimephales promelas (fathead minnow) 8120 mg/L/96h (OCED 203)
Daphnia toxicity: EC50 Daphnia pulex (water flea) 8800 mg/L/48h
NOEC Daphnia magna (Big water flea) 2212 mg/L/28d
Bacterial toxicity: effects on activated sludge: EC50 61150 mg/L/0.5h

Information about Ethyl acetate:
Fish toxicity: LC50 Pimephales promelas (fathead minnow) 134 mg/L/96h
NOEC Pimephales promelas (fathead minnow) < 9,65 mg/L/32d
Daphnia toxicity: NOEC Daphnia magna (Big water flea) 2,4 mg/L/21d

Persistence and degradability

Further details: No data available

Bioaccumulative potential

Partition coefficient: n-octanol/water:

-0.23 log P(o/w) (Acetone)
Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

2.73 log P(o/w) (Toluene)
Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.

0.68 log P(o/w) (ethyl acetate)
Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

Mobility in soil

No data available

Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

13. Disposal considerations

Waste treatment methods

Product

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

Package

Recommendation: Dispose of waste according to applicable legislation.

14. Transport information

UN number

DOT: UN1133
IMDG, IATA-DGR: UN 1133

UN proper shipping name

DOT, IMDG, IATA-DGR: UN 1133, ADHESIVES

Transport hazard class(es)

DOT: 3
IMDG: Class 3, Subrisk -
IATA-DGR: Class 3



Packing group

DOT, IMDG, IATA-DGR: III

Environmental hazards

Marine pollutant: no

Transport in bulk according to IMO instruments

No data available

636W1 - OTTO BOCK Universal Adhesive

Material number 636W 1

Page: 12 of 15

Special precautions for user

USA: Department of Transportation (DOT)

Labels: 3
Special Provisions: B1, B52, IB3, T2, TP1
Packaging – Exceptions: 150
Packaging – Non-bulk: 173
Packaging – Bulk: 242
Quantity limitations – Passenger aircraft / rail: 60 L
Quantity limitations – Cargo only: 220 L
Vessel stowage – Location: A
Vessel stowage – Other:

Sea transport (IMDG)

EmS: F-E, S-D
Special Provisions: 223 955
Limited quantities: 5 L
Excepted quantities: E1
Package - Instructions: P001, LP01
Package - Provisions: PP1
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T2
Tank instructions - Provisions: TP1
Stowage and handling: Category A.
Properties and observations: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.
Marine pollutant: no
Segregation group: none

Air transport (IATA)

Proper shipping name: UN 1133, ADHESIVES
Hazard label: Flamm. liquid
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special Provisions: A3
Emergency Response Guide-Code (ERG): 3L

636W1 - OTTO BOCK Universal Adhesive

Material number 636W 1

Page: 13 of 15

15. Regulatory information

National regulations - U.S. Federal Regulations

Acetone:	<p>TSCA Inventory: listed</p> <p>Clean Air Act:</p> <p>CAA SOCM Chemical: yes</p> <p>Other Environmental Laws:</p> <p>CERCLA: RQ 5000 lbs.</p> <p>RCRA Groundwater Monitoring: listed</p> <p>NIOSH Recommendations:</p> <p>Occupational Health Guideline: 0004*</p>
Ethyl acetate:	<p>TSCA Inventory: listed</p> <p>Other Environmental Laws:</p> <p>CERCLA: RQ 5000 lbs.</p> <p>NIOSH Recommendations:</p> <p>Occupational Health Guideline: 0260</p>
Toluene:	<p>TSCA Inventory: listed</p> <p>Carcinogen Status: IARC Rating: Group 3</p> <p>OSHA Carcinogen: not listed</p> <p>NTP Rating: not listed</p> <p>Clean Air Act:</p> <p>CAA Hazardous Air Pollutants: yes</p> <p>CAA SOCM Chemical: yes</p> <p>Clean Water Act:</p> <p>CWA Hazardous Substances: Category C; RQ 1000.0 lbs</p> <p>CWA Priority Pollutants: listed</p> <p>Other Environmental Laws:</p> <p>CERCLA: RQ 1000 lbs.</p> <p>RCRA Hazardous Wastes: Waste Code U220</p> <p>RCRA Groundwater Monitoring: listed</p> <p>SARA Title III, Section 313, Toxic Release: NPFAS; De Minimis <=1.0 %;</p> <p>Thresholds 25000/10000 lbs</p> <p>NIOSH Recommendations:</p> <p>Occupational Health Guideline: 0619</p>
Isopropyl alcohol:	<p>TSCA Inventory: listed</p> <p>Carcinogen Status: IARC Rating: Group 3</p> <p>OSHA Carcinogen: not listed</p> <p>NTP Rating: not listed</p> <p>Other Environmental Laws:</p> <p>SARA Title III, Section 313, Toxic Release: NPFAS; De Minimis <=1.0 %;</p> <p>Thresholds 25000/10000 lbs</p> <p>NIOSH Recommendations:</p> <p>Occupational Health Guideline: 0359</p>

636W1 - OTTO BOCK Universal Adhesive

Material number 636W 1

Page: 14 of 15

n-Butyl acetate:	<p>TSCA Inventory: listed</p> <p>Clean Water Act:</p> <p>CWA Hazardous Substances: Category D; RQ 5000.0 lbs</p> <p>Other Environmental Laws:</p> <p>CERCLA: RQ 5000 lbs.</p> <p>NIOSH Recommendations:</p> <p>Occupational Health Guideline: 0072</p>
Cyclohexanone:	<p>TSCA Inventory: listed</p> <p>Carcinogen Status: IARC Rating: Group 3</p> <p>OSHA Carcinogen: not listed</p> <p>NTP Rating: not listed</p> <p>Clean Air Act:</p> <p>CAA SOCM Chemical: yes</p> <p>Other Environmental Laws:</p> <p>CERCLA: RQ 5000 lbs.</p> <p>NIOSH Recommendations:</p> <p>Occupational Health Guideline: 0166</p>

National regulations - U.S. State Regulations

Acetone:	New York Right-To-Know: listed
Ethyl acetate:	New York Right-To-Know: listed
Toluene:	<p>California Proposition 65:</p> <p>developmental</p> <p>New York Right-To-Know: listed</p>
n-Butyl acetate:	New York Right-To-Know: listed
Cyclohexanone:	New York Right-To-Know: listed

Further regulations, limitations and legal requirements

No data available

16. Other information

Text for labeling:	Contains 35 - 40 % Acetone, 20 - 25 % Ethyl acetate, 10 - 15 % Toluene, 5 - 10 % Isopropyl alcohol, 1 - 5 % n-Butyl acetate, < 1 % Cyclohexanone.
Revision date:	12/17/2025
Date of first version:	10/30/1994
Reason of change:	<p>General revision: Safety Data Sheet according to Hazardous Products Regulations (HPR) 2022</p> <p>General revision: Safety Data Sheet according to HCS 2024 (29 CFR 1910.1200)</p>

Hazard rating systems:



NFPA Hazard Rating:

Health: 3 (Serious)
Fire: 3 (Serious)
Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 3 (Serious) - Chronic effects
Flammability: 3 (Serious)
Physical Hazard: 0 (Minimal)
Personal Protection: X = Consult your supervisor

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0
X		

Abbreviations and acronyms:

Acute Toxicity: Acute toxicity
AS/NZS: Australian Standards/New Zealand Standards
Aspiration Toxicity: Aspiration toxicity
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
DOT: Department of Transportation's Safety Regulations (USA)
EC: European Community
EC50: Effective Concentration 50%
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
Eye Irritation: Eye irritation
Flammable Liquid: Flammable liquid
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LD50: Lethal dose 50%
LEL: Lower Explosion Limit
log P(o/w): Partition coefficient: octanol/water
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
NOEC: No Observed Effect Concentration
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
Reproductive toxicant: Reproductive toxicity
Skin Irritation: Skin irritation
STOT RE: Specific target organ toxicity - repeated exposure
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.