

1. Identification

Product identifier

Trade name: 757B16 - BiOM T2 Battery

Relevant identified uses of the substance or mixture and uses advised against

General use: Lithium-ion battery for orthopedic procedures
For commercial user only.

Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care
Street/POB-No.: 3820 W. Great Lakes Drive
Zip code, city: Salt Lake City, UT 84120
USA
WWW: www.ottobockus.com
Telephone: +1 (801) 956-2400
Telefax: +1 (801) 956-2401
Department responsible for information:
Quality Department,
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),
Email: USRegulatory@ottobock.com

Additional information: Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency telephone number

CHEMTREC, Telephone: +1 (800) 424-9300
Transport:
CONSULTANK Lutz Harder GmbH (Contract QUALI003)
Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2. Hazard identification

Classification of the substance or mixture

Article not subject to hazard labelling or classification.

Label elements

not applicable

Other hazards

The battery is hermetically sealed. Cell may explode

danger of releasing ingredients, mentioned in section 3, by damaging the battery

- with strong mechanical action,
- in case of heating and/or Fire,
- with influence of water,
- short circuit.

Hazard statements:

Limited evidence of a carcinogenic effect. May cause sensitization by skin contact.

Electrolyte:

Flammable. Vapors irritate eyes, mucous membranes and respiratory system. Vapors may cause drowsiness and dizziness.

After contact with water: Formation of Hydrogen fluoride. Causes severe skin burns and eye damage. Toxic if swallowed.

3. Composition/information on ingredients

Mixtures

Chemical characterization: Lithium-ion battery - Article, Cell.

The chemical materials are stored in a hermetically sealed metal case.

Contains: Metal oxide (20% - 50%), Carbon (15% - 35%), Aluminium (3% - 12%), Copper (3% - 12%), Polyvinylidene fluoride (< 8%)

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS -	electrolyte	10 - 20 %	Flammable Liquid - Category 3.
CAS 7439-93-2	Lithium	< 1.5 %	Water-reactive - Category 1. Skin Corrosion - Category 1B.

The actual concentration or concentration range is withheld as a trade secret.

4. First aid measures

General information: In case of damaged battery cases: Release of dangerous ingredients possible.

In case of inhalation: In case of damaged battery cases / In case of exposure to hazardous ingredients: Provide fresh air. Keep victim at rest in half upright position. Seek medical attention.

Following skin contact: In case of damaged battery cases / In case of exposure to hazardous ingredients: Wash with plenty of water.

Take off immediately all contaminated clothing. Seek medical attention.

After eye contact: In case of damaged battery cases / In case of exposure to hazardous ingredients: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Afterwards, consult an ophthalmologist immediately.

After swallowing: In case of damaged battery cases / In case of exposure to hazardous ingredients: Drink large quantities of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Immediately get medical attention.

Most important symptoms/effects, acute and delayed

With correct and proper handling/application, no cases health hazards are known.

In case of damaged battery cases:

May cause sensitization by skin contact.

Irritation. Vapors may cause drowsiness and dizziness.

Information to physician

Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

sand, Extinguishing agent on the basis of sodium chloride, sodium hydrogen carbonate, limestone, or with metal extinguishing powder.

Extinguishing media which must not be used for safety reasons:

Water.

Specific hazards arising from the chemical

In case of heating > 266 °F: Cell may explode.

Hazardous vapors may form during fires.

In case of fire may be liberated: hydrogen fluoride, hydrogen, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Remove product from area of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid damage to the battery casing. In case of damaged battery cases: Avoid exposure. Eliminate all ignition sources if safe to do so. Provide fresh air. Avoid contact with skin and eyes.

Wear suitable gloves. Do not inhale vapors or dust particles. Keep unprotected people away.

Environmental precautions:

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

Methods for clean-up:

Take up mechanically. Dispose of waste according to applicable legislation. Avoid generation of dust.

Electrolyte: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal. Final cleaning.

7. Handling and storage

Precautions for safe handling

Advices on safe handling: Provide fresh air. Avoid contact with skin and eyes.
Wear suitable gloves. Do not inhale vapors or dust particles.
Avoid damage to the battery casing. In case of damaged battery cases: Avoid exposure.

Precautions against fire and explosion:
Avoid short circuit. Avoid damage to the battery casing.
In case of damaged battery cases: Remove all sources of ignition.

Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:
Provide adequate ventilation. Store in a dry place.
Protect from: humidity, heat, UV-radiation/sunlight
Store only in corrosive resistant containers.

Hints on joint storage: Keep away from: Acids, bases.
Further details: In case of damaged battery cases: Keep away from water.

8. Exposure controls/personal protection

Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
7440-44-0	Carbon	USA: ACGIH: TWA	10 mg/m ³ (Dust limit value, inhalable fraction)
		USA: ACGIH: TWA	3 mg/m ³ (Dust limit value, respirable fraction)
		USA: OSHA: TWA	15 mg/m ³ (inhalable fraction)
		USA: OSHA: TWA	5 mg/m ³ (respirable fraction)
7429-90-5	Aluminium	USA: ACGIH: TWA	1 mg/m ³
		USA: NIOSH: Ceiling	5 mg/m ³ (inhalable fraction)
		USA: NIOSH: TWA	10 mg/m ³ (inhalable fraction)
		USA: NIOSH: TWA	5 mg/m ³ (inhalable fraction)
		USA: OSHA: TWA	15 mg/m ³ (inhalable fraction)
		USA: OSHA: TWA	5 mg/m ³ (respirable fraction)
7440-50-8	Copper	USA: ACGIH: TWA	0.2 mg/m ³ (Smoke)
		USA: ACGIH: TWA	1 mg/m ³ (Dusts and mist calculated as Cu)
		USA: IDLH: TWA	100 Cu/m ³ (dust and mist)
		USA: IDLH: TWA	100 Cu/m ³ (Smoke)
		USA: NIOSH: TWA	1 mg/m ³
		USA: OSHA: TWA	0.1 mg/m ³ (Smoke; calculated as Cu)
		USA: OSHA: TWA	1 mg/m ³ (Dusts and mist calculated as Cu)

Additional information: The chemical materials are stored in a sealed battery case.

Appropriate engineering controls

In case of damaged battery cases: Provide adequate ventilation.

In case of development of vapors or dust:

The use of local exhaust ventilation is recommended.

Personal protection equipment (PPE)

Respiratory protection: In case of damaged battery cases:
Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection: In case of damaged battery cases:
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.
Glove material: rubber - breakthrough time >480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: In case of damaged battery cases:
Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

General hygiene considerations:
In case of damaged battery cases:
Do not inhale vapors or dust particles.
Avoid contact with skin and eyes.
Keep away from sources of ignition - No smoking.
Wash hands before breaks and after work.

Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state at 68 °F and 101.3 kPa	Form: solid
Color:	No data available
Odor:	odorless
Odor threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	No data available
Explosion limits:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Viscosity:	No data available
Water solubility:	immiscible
Partition coefficient: n-octanol/water:	No data available

Vapor pressure: No data available
 Density: No data available
 Vapor density: No data available
 Particle characteristics: Not applicable

Additional information

Additional information: No data available

10. Stability and reactivity

Reactivity: No data available

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions:

Fire hazard in case of technical defects.

In case of damaged battery cases:

Electrolyte: Flammable. After contact with water: formation of Hydrogen fluoride.

Conditions to avoid:

> 266 °F: Cell may explode.

Protect from: humidity, heat, UV-radiation/sunlight

Avoid short circuit. Avoid damage to the battery casing.

In case of damaged battery cases:

Protect from: water. Keep away from sources of ignition - No smoking.

Incompatible materials:

Acids, bases.

In case of damaged battery cases: Keep away from water.

Hazardous decomposition products:

In case of fire may be liberated: hydrogen fluoride, hydrogen, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on toxicological effects

Toxicological effects:

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Lack of data.

Serious eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information: In case of damaged battery cases:
Limited evidence of a carcinogenic effect. May cause sensitization by skin contact.
Electrolyte, organic:
Vapors irritate eyes, mucous membranes and respiratory system.
Vapors may cause drowsiness and dizziness.

12. Ecological information

Ecotoxicity

Further details: in case of damaged battery cases:
ingredient(s): bioaccumulation possible.

Persistence and degradability

Further details: Product is not biodegradable.

Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

Mobility in soil

No data available

Other adverse effects

General information: Discharge into the environment must be avoided.

13. Disposal considerations

Waste treatment methods

Product

Recommendation: Dispose of waste according to applicable legislation.

Package

Recommendation: Dispose of waste according to applicable legislation.
Packing can be recycled or disposed of.

14. Transport information

UN number

DOT: UN3480
IMDG, IATA-DGR: UN 3480

UN proper shipping name

DOT, IMDG, IATA-DGR: UN 3480, LITHIUM ION BATTERIES

Transport hazard class(es)

DOT: 9
 IMDG: Class 9, Subrisk -
 IATA-DGR: Class 9



Packing group

DOT, IATA-DGR: not applicable
 IMDG: -

Environmental hazards

Marine pollutant: no

Transport in bulk according to IMO instruments

No data available

Special precautions for user

USA: Department of Transportation (DOT)

Labels: 9
 Special Provisions: 388, 422, A54, A100
 Packaging – Exceptions: 185
 Packaging – Non-bulk: 185
 Packaging – Bulk: 185
 Quantity limitations – Passenger aircraft / rail: Forbidden
 Quantity limitations – Cargo only: 35 kg
 Vessel stowage – Location: A
 Vessel stowage – Other: 156

Sea transport (IMDG)

EmS: F-A, S-I
 Special Provisions: 188 230 310 348 376 377 384 387
 Limited quantities: 0
 Excepted quantities: E0
 Package - Instructions: P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
 Package - Provisions: -
 IBC - Instructions: -
 IBC - Provisions: -
 Tank instructions - IMO: -
 Tank instructions - UN: -
 Tank instructions - Provisions: -
 Stowage and handling: Category A. SW19
 Properties and observations: Electrical batteries containing lithium ion may react (e.g., flame, heat, emission of toxic, corrosive or flammable gases or vapours) or disassemble due to damage, defects or short circuit.
 Marine pollutant: no
 Segregation group: none

Air transport (IATA)

Proper shipping name: UN 3480, LITHIUM ION BATTERIES
Hazard label: Lithium batt or Sodium-ion batt
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Forbidden
Passenger and Cargo Aircraft: Forbidden
Cargo Aircraft only: Pack.Instr. See 965 - Max. Net Qty/Pkg. See 965
Special Provisions: A88 A99 A154 A183 A201 A213 A331 A334 A802
Emergency Response Guide-Code (ERG): 12FZ

Further information

In compliance with Special provision IATA 965

15. Regulatory information

National regulations - U.S. Federal Regulations

This product is an article as defined by TSCA regulations, and is exempt from TSCA inventory listing requirements.

National regulations - U.S. State Regulations

Copper: New York Right-To-Know: listed

Further regulations, limitations and legal requirements

No data available

16. Other information

Revision date: 1/1/2026
Date of first version: 5/30/2016
Reason of change: Changes in section 14: IATA-DGR 2026
Hazard rating systems:



NFPA Hazard Rating:
Health: 1 (Slight)
Fire: 1 (Slight)
Reactivity: 0 (Minimal)

HMIS Version III Rating:
Health: 1 (Slight)
Flammability: 1 (Slight)
Physical Hazard: 0 (Minimal)
Personal Protection: X = Consult your supervisor
in case of damaged battery cases: NFPA/HMIS: F2

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Abbreviations and acronyms:

AS/NZS: Australian Standards/New Zealand Standards
 CAS: Chemical Abstracts Service
 CFR: Code of Federal Regulations
 CLP: Classification, Labelling and Packaging
 DMEL: Derived minimal effect level
 DNEL: Derived no-effect level
 DOT: Department of Transportation's Safety Regulations (USA)
 EC: European Community
 EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
 EN: European Standard
 EQ: Excepted quantities
 Flammable Liquid: Flammable liquid
 IATA: International Air Transport Association
 IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
 IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IMDG Code: International Maritime Dangerous Goods Code
 IMO: International Maritime Organization
 MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
 OEL: Occupational Exposure Limit Value
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, bioaccumulative and toxic
 PNEC: Predicted no-effect concentration
 Skin Corrosion: Skin corrosion
 TLV: Threshold Limit Value
 TRGS: Technical Rules for Hazardous Substances
 TSCA: Toxic Substance Control Act
 UN: United Nations
 UV: Ultraviolet
 vPvB: Very persistent and very bioaccumulative
 Water-reactive: Water-reactive
 WEL: Workplace Exposure Limit

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.