

1. Product and company identification

Product identifier

Trade name: 617H21 - ORTHOCRYL Sealing Resin

This safety data sheet pertains to the following products:

617H21=0.900 E = Orthocryl-Siegelharz

617H21=2.300 E = Orthocryl-Siegelharz

617H21=25 E = Orthocryl-Siegelharz

617H21=25 P = Orthocryl Siegelharz, Kunststoffkanister

617H21=4.600 E = Orthocryl-Siegelharz

Recommended use and restrictions on use

General use: Lamination Resin for orthopedic procedures
Reserved for industrial and professional use.

Initial supplier identifier

Company name: Otto Bock HealthCare Canada Ltd.

Street/POB-No.: 5470 Harvester Road

Postal Code, city: Burlington, ON L7L 5N5, CA
Canada

WWW: www.ottobock.ca

E-mail: info.canada@ottobock.com

Telephone: (800) 665-3327

Telefax: (800) 463-3659

Department responsible for information:

Mark Agro, Telephone: (800) 665-3327 (9 am - 5 pm)

Additional information:

Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency phone number

COLLECT, Telephone: (613) 996-6666

Transport:

CONSULTANK Lutz Harder GmbH (Contract QUALI003)

Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2. Hazards identification

Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid

Color: Colorless

Odor: Ester-like

Classification: Flammable Liquid 2. Skin Irritation 2. Sensitization - skin 1.
Specific Target Organ Toxicity (Single Exposure) 3.

Hazard symbols:



Signal word:

Danger

Hazard statements:

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.

Call a POISON CENTER/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS in Canada.

Hazards not otherwise classified

Due to reducing substances and heavy metal ions polymerization with heat generation may occur. Take precautionary measures against static discharge.

Potentially explosive mixtures may form if adequate ventilation is not provided. Higher doses may lead to a narcotic effect.

Special danger of slipping by leaking/spilling product.

see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Solution of acrylic polymers in methylmethacrylate, containing softener. (MMA)

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 80-62-6	Methyl methacrylate	50 - 70 %	Flammable Liquid 2. Skin Irritation 2. Sensitization - skin 1. Specific Target Organ Toxicity (Single Exposure) 3.
CAS 109-16-0	2,2'-Ethylenedioxydiethyl dimethacrylate	< 10 %	Sensitization - skin 1.
CAS 38668-48-3	1,1'-(p-Tolylimino) dipropan-2-ol	< 1 %	Acute Toxicity 2 (oral). Eye Irritation 2A. Aquatic toxicity - acute 3. Aquatic toxicity - chronic 3.
CAS 123-81-9	Ethylene di(S-thioacetate)	< 0.25 %	Acute Toxicity 4 (oral). Acute Toxicity 4 (dermal). Acute Toxicity 4 (inhalative). Eye Irritation 2A. Sensitization - skin 1. Specific Target Organ Toxicity (Single Exposure) 3.
CAS 26523-78-4	Tris(nonylphenyl) phosphite	< 0.25 %	Sensitization - skin 1. Aquatic toxicity - acute 1. Aquatic toxicity - chronic 1.
CAS 141-32-2	n-Butyl acrylate	< 0.25 %	Flammable Liquid 3. Acute Toxicity 4 (inhalative). Skin Irritation 2. Eye Irritation 2A. Sensitization - skin 1. Specific Target Organ Toxicity (Single Exposure) 3. Aquatic toxicity - chronic 3.

4. First aid measures

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical attention.
Following skin contact:	After contact with skin, wash immediately with soap and plenty of water. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Do not induce vomiting. Immediately get medical attention.

Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.
 In case of inhalation: mucous membrane irritation, Cough and shortage of breath.
 In case of prolonged exposure: Headache, drowsiness.

Information to physician

Monitor breathing. Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:	10 °C (Methyl acrylate)
Auto-ignition temperature:	No data available

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide

Extinguishing media which must not be used for safety reasons:

Full water jet

Specific hazards arising from the chemical

Highly flammable liquid and vapor. Concentrated vapors are heavier than air. Explosive mixtures with air may even form at room temperature.

In case of fire may be liberated: Organic materials, sulphur oxides, carbon monoxide and carbon dioxide.

Special protective equipment and precautions for fire-fighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Cool endangered containers with water spray and, if possible, remove from danger zone. Do not allow fire water to penetrate into surface or ground water.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

6. Accidental release measures

Personal precautions:

Eliminate all ignition sources if safe to do so. Plug leak if safely possible. Provide adequate ventilation.

Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

Avoid breathing mist/vapors/spray. When vapors form, use respiratory protection. Avoid contact with skin and eyes.

Keep unprotected people away.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.

Danger of explosion!

In case of release, notify competent authorities.

Methods for clean-up:

Smaller amounts: Soak up with absorbent materials such as sand, siliceous earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance. In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

Special danger of slipping by leaking/spilling product.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed.

Provide room air exhaust at ground level. Concentrated vapors are heavier than air.

Avoid breathing mist/vapors/spray. Avoid contact with skin and eyes. Wear appropriate protective equipment.

Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

Work place should be equipped with a shower and an eye rinsing apparatus.

Wash hands before breaks and after work.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

Air combined with vapors may form potentially explosive mixtures that are heavier than air. Vapors may proceed on the ground over great distances and cause fire and backflashes.

Use only explosion-proof equipment.

Storage

Requirements for storerooms and containers:

Keep only in the original container at temperature not exceeding 25 °C.

Keep container tightly closed. Protect from light.

Because oxygen (air) is necessary to stabilize product, fill container only to 90% of capacity.

Store containers in upright position.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.

Do not store together with organic peroxides, ammonia or persulphates.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
80-62-6	Methyl methacrylate	Canada: OEL 15 min	410 mg/m ³ ; 100 ppm
		Canada: OEL 8 hour	205 mg/m ³ ; 50 ppm
		Canada: OEL STEL	100 ppm
		Canada: OEL TWA	50 ppm
		Canada: VECD	100 ppm
		Canada: VEMP	50 ppm
		USA: ACGIH: STEL	410 mg/m ³ ; 100 ppm
		USA: ACGIH: TWA	205 mg/m ³ ; 50 ppm
		USA: IDLH: TWA	1,000 ppm
		USA: NIOSH: TWA	410 mg/m ³ ; 100 ppm
		USA: OSHA: TWA	410 mg/m ³ ; 100 ppm
141-32-2	n-Butyl acrylate	Canada: OEL 8 hour	10 mg/m ³ ; 2 ppm
		Canada: OEL TWA	2 ppm
		Canada: VEMP	2 ppm
		USA: ACGIH: TWA	11 mg/m ³ ; 2 ppm
		USA: IDLH: TWA	113 ppm
		USA: NIOSH: TWA	55 mg/m ³ ; 10 ppm

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection:	<p>Wear suitable protective clothing. handling larger quantities: Face mask, chemical-resistant boots and apron</p> <p>Protective gloves according to OSHA Standard - 29 CFR: 1910.138.</p> <p>Glove material: butyl caoutchouc (butyl rubber) - Layer thickness: 0.7 mm</p> <p>Breakthrough time approx. 60 min</p> <p>Observe glove manufacturer's instructions concerning penetrability and breakthrough time.</p>
Respiratory protection:	<p>Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.</p> <p>Use filter type A (= against vapors of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.</p>
General hygiene considerations:	<p>Avoid breathing mist/vapors/spray.</p> <p>Avoid contact with skin and eyes.</p> <p>Wash hands before breaks and after work.</p> <p>Separate storage of work clothes.</p> <p>Keep away from sources of ignition - No smoking.</p> <p>Take off contaminated clothing and wash it before reuse.</p> <p>When using do not eat or drink.</p> <p>Work place should be equipped with a shower and an eye rinsing apparatus.</p>

Environmental exposure controls

Do not allow to penetrate into soil, waterbodies or drains.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	<p>Physical state at 20 °C and 101.3 kPa: liquid</p> <p>Color: Colorless</p>
Odor:	Ester-like
Odor threshold:	No data available
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	approx. 100 °C (1013 hPa)
Flash point/flash point range:	10 °C (Methyl acrylate)
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	<p>LEL (Lower Explosion Limit) at 10 °C: 2.10 Vol-% (Methyl methacrylate)</p> <p>UEL (Upper Explosive Limit): 12.50 Vol-% (Methyl methacrylate)</p>
Vapor pressure:	<p>at 20 °C: approx. 40 hPa</p> <p>at 50 °C: 159 hPa</p>
Vapor density:	at 20 °C: >= 1
Density:	at 20 °C: approx. 1 g/mL
Water solubility:	at 20 °C: 16 g/L

Partition coefficient: n-octanol/water:	<p>1.38 log K(o/w) (Methyl methacrylate) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected. (OECD 107) 2.1 log K(o/w) (1,1'-(p-Tolylimino)dipropen-2-ol) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected. at 2 °C: (OECD 117) 1.46 log K(o/w) (Ethylene di(S-thioacetate)) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected. at 20 °C: (OECD 117) 2.3 log K(o/w) (2,2'-Ethylenedioxydiethyl dimethacrylate) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected. at 25 °C: 2.38 log K(o/w) (n-Butyl acrylate) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.</p>
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Viscosity, dynamic:	at 20 °C: approx. 320 mPa*s
Explosive properties:	Explosive mixtures with air may even form at room temperature.
Ignition temperature:	430 °C (Methyl acrylate)

10. Stability and reactivity

Reactivity:	<p>Highly flammable liquid and vapor. Concentrated vapors are heavier than air. Explosive mixtures with air may even form at room temperature.</p>
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	<p>Product is normally delivered in a stable state. However, if shelf life and/or recommended storage temperature are exceeded to a large degree, product may polymerize and generate heat. Due to reducing substances, peroxides and heavy metal ions, polymerization with heat generation may occur. Heating will lead to pressure increase: Danger of bursting and explosion.</p>
Conditions to avoid:	<p>Keep away from heat sources, sparks and open flames. Protect from light.</p>
Incompatible materials:	Amines, sulphur compounds, alkali compounds, reducing agent, oxidizing agents, peroxides
Hazardous decomposition products:	No decomposition when used properly.
Thermal decomposition:	No data available

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.

Serious eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) 3 = May cause respiratory irritation.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information: Information about Methyl methacrylate:

LD50 Rat, oral: > 5,000 mg/kg

LD50 Rabbit, dermal: > 5,000 mg/kg

LC50 Rat, inhalative: 29.8 mg/L/4h

For carcinogenic effects:

IARC Rating: Group 3

OSHA Carcinogen: not listed

NTP Rating: not listed

Information about 2,2'-Ethylenedioxydiethyl dimethacrylate:

LD50 Rat, oral: > 5,000 mg/kg

LD50 Mouse (male), dermal: > 2,000 mg/kg

Information about N,N-Bis-(2-hydroxypropyl)-p-toluidine:

LD50 Rat, oral: 25 mg/kg

LD50 Rat, dermal: > 2,000 mg/kg

Information about Ethylene di(S-thioacetate):

LD50 Rat (male), oral: 303 mg/kg

LC0 Rabbit, dermal: 200 mg/kg

LC0 Rat, inhalative: 1.5 mg/L

LC0 Rat, inhalative (dust, mist, smoke): 11 mg/L

Information about Tris(nonylphenyl)phosphite:

LD50 Rat, oral: > 16,200 mg/kg

LD50 Rabbit, dermal: > 2,000 mg/kg

Information about n-Butyl acrylate:

LD50 Rat, oral: 3,150 mg/kg

LD50 Rabbit (male), dermal: > 2,000 mg/kg

LC50 Rat, inhalative (dust, mist, smoke): 10.3 mg/L/4h

Symptoms

In case of prolonged exposure: Headache, drowsiness

In case of inhalation: Mucous membrane irritation, cough and shortage of breath.

In case of ingestion:

Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract. Can damage your health.

After eye contact: May cause irritations.

12. Ecological information

Ecotoxicity

Aquatic toxicity:

Information about Methyl methacrylate:

Fish toxicity:

LC50 Oncorhynchus mykiss: > 79 mg/L/96h (OECD 203)

NOEC Danio rerio (zebrafish): 9.4 mg/L/32d (OECD 210)

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): 69 mg/L/48h (OECD 202)

NOEC Daphnia magna (Big water flea): 37 mg/L/21d (OECD 202)

Algae toxicity:

EC50 Selenastrum capricornutum: > 100 mg/L/72h (OECD 201)

NOEC Selenastrum capricornutum: > 100 mg/L/72h (OECD 201)

Information about 2,2'-Ethylenedioxydiethyl dimethacrylate:

Fish toxicity:

LC50 Danio rerio (zebrafish): 16.4 mg/L/96h (OECD 203)

Daphnia toxicity:

NOEC Daphnia magna (Big water flea): 32 mg/L/21d (OECD 211)

Algae toxicity:

EC50 Pseudokirchneriella subcapitata (green algae): > 100 mg/L/72h (OECD 201)

NOEC Pseudokirchneriella subcapitata (green algae): 18.6 mg/L/72h (OECD 201)

Information about N,N-Bis-(2-hydroxypropyl)-p-toluidine:

Fish toxicity:

LC50 Danio rerio (zebrafish): 17 mg/L/96h

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): 28.8 mg/L/48h (OECD 202)

Algae toxicity:

EC50 Desmodesmus subspicatus (green algae): 245 mg/L/72h (OECD 201)

Bacterial toxicity:

EC10: > 1,995 mg/L/30 min (OECD 209)

Information about Ethylene di(S-thioacetate):

Fish toxicity:

LC50 Leuciscus idus: 4.85 mg/L/48h (DIN 38412 Teil 15)

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): 11 mg/L/48h

Algae toxicity:

EC50 Desmodesmus subspicatus (green algae): > 100 mg/L/72h (OECD 201)

Information about Tris(nonylphenyl)phosphite:

Fish toxicity:

LC50 Oncorhynchus mykiss: > 100 mg/L/96h (OECD 203)

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): 0.3 mg/L/48h (OECD 202)

NOEC Daphnia magna (Big water flea): > 0.1 mg/L/21d (OECD 211)

Algae toxicity:

NOEC Raphidocelis subcapitata: 100 mg/L/72h (OECD 201)

Bacterial toxicity:

NOEC: 15.4 mg/L (OECD 301D)

Information about n-Butyl acrylate:

Fish toxicity:

LC50 Oncorhynchus mykiss: > 5.2 mg/L/96h (OECD 203)

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): 8.2 mg/L/48h (OECD 202)

NOEC Daphnia magna (Big water flea): 0.136 mg/L/21d (OECD 211)

Algae toxicity:

EC50 Selenastrum capricornutum: 2.65 mg/L/72h (OECD 201)

Bacterial toxicity:

EC0 activated sludge: > 150 mg/L/3d

Mobility in soil

No data available

Persistence and degradability

Further details:

Information about Methyl methacrylate: Product is readily biodegradable. (OECD 301 C, 14d: 94%)

Information about 2,2'-Ethylenedioxydiethyl dimethacrylate:

Biodegradability: 85 %/28 d. Product is readily biodegradable.

Information about 1,1'-(p-Tolylimino)dipropyl-2-ol:

Biodegradability: 39 %/28 d (OECD 301B). Not biodegradable.

Information about Ethylene di(S-thioacetate):

Biodegradability: 65,9 %/28 d (OECD 301D). Product is readily biodegradable.

Information about Tris(nonylphenyl)phosphite:

Biodegradability: < 4% %/28 d (OECD 301D)

Information about n-Butyl acrylate:

Biodegradability: 60 %/28 d (Literature). Product is readily biodegradable.

Biodegradability: > 80 %/28 d (ISO 14593). Product is readily biodegradable.

Additional ecological information

Volatile organic compounds (VOC):

67 % by weight / 670 g/L

General information:

Do not allow to penetrate into soil, waterbodies or drains.

13. Disposal considerations

Product

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

Package

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself.

Non-contaminated packages may be recycled.

Handle empty containers with care. Incineration may cause explosion.

14. Transport information

UN number

ADR/RID, IMDG, IATA-DGR:

UN 1866

UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

UN 1866, RESIN SOLUTION

Transport hazard class(es)

ADR/RID:

Class 3, Code: F1

IMDG:

Class 3, Subrisk -

IATA-DGR:

Class 3



Packing group

ADR/RID, IMDG, IATA-DGR:

II

Environmental hazards

Marine pollutant:

no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

USA: Department of Transportation (DOT)

Identification number:

UN1866

Proper shipping name:

UN 1866, RESIN SOLUTION

Hazard class or Division:

3

Packing Group:

II

Labels:

3

Special Provisions:

149, B52, IB2, T4, TP1, TP8

Packaging – Exceptions:

150

Packaging – Non-bulk:

173

Packaging – Bulk:

242

Quantity limitations – Passenger aircraft / rail:

5 L

Quantity limitations – Cargo only:

60 L

Vessel stowage – Location:

B



Canada: Transportation of Dangerous Goods (TDG)

UN Number:

UN1866

Shipping name:

UN 1866, resin solution

TDG class:

3

Packing group:

II

Explosive limit and limited quantity index:

5 L

Passenger carrying road or rail index:

5 L

Sea transport (IMDG)

UN number: UN 1866
 Proper shipping name: UN 1866, RESIN SOLUTION
 Class or division, Subsidiary risk: Class 3, Subrisk -
 Packing Group: II
 EmS: F-E, S-E
 Special Provisions: -
 Limited quantities: 5 L
 Excepted quantities: E2
 Package - Instructions: P001
 Package - Provisions: PP1
 IBC - Instructions: IBC02
 IBC - Provisions: -
 Tank instructions - IMO: -
 Tank instructions - UN: T4
 Tank instructions - Provisions: TP1, TP8
 Stowage and handling: Category B.
 Properties and observations: Miscibility with water depends upon the composition.
 Marine pollutant: no
 Segregation group: none
 Remarks: For packages < = 30 litres: PG III (IMDG 2.3.2.2)

Air transport (IATA)

UN/ID number: UN 1866
 Proper shipping name: UN 1866, RESIN SOLUTION
 Class or division, Subsidiary risk: Class 3
 Packing Group: II
 Hazard label: Flamm. liquid
 Excepted Quantity Code: E2
 Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y341 - Max. Net Qty/Pkg. 1 L
 Passenger and Cargo Aircraft: Pack.Instr. 353 - Max. Net Qty/Pkg. 5 L
 Cargo Aircraft only: Pack.Instr. 364 - Max. Net Qty/Pkg. 60 L
 Special Provisions: A3
 Emergency Response Guide-Code (ERG): 3L
 Remarks: For packages < = 30 litres: PG III (IATA 3.3.3.1)

15. Regulatory information

National regulations - Canada

Product: DSL: All ingredients are listed or exempt from listing.
 Methyl methacrylate: DSL: listed
 2,2'-Ethylenedioxydiethyl dimethacrylate: DSL: listed
 1,1'-(p-Tolylimino)dipropen-2-ol: DSL: listed
 Ethylene di(S-thioacetate): DSL: listed
 Tris(nonylphenyl)phosphite: DSL: listed
 n-Butyl acrylate: DSL: listed

National regulations - U.S. Federal Regulations

Product: TSCA: All ingredients are listed or exempt from listing.

Methyl methacrylate: Carcinogen Status:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

Clean Air Act:
CAA Hazardous Air Pollutants: yes
CAA SOCM Chemical: yes

Clean Water Act:
CWA Hazardous Substances: RQ 1000 lbs.

Other Environmental Laws:
CERCLA: RQ 1000 lbs.
RCRA Hazardous Wastes: Code U162
RCRA Groundwater Monitoring: Methods 8015, 8240 / PQL 2, 5
SARA Title III - Section 313, Toxic Release: Conc. 1.0% / Threshold Standard

NIOSH Recommendations:
Occupational Health Guideline: 0426

National regulations - U.S. State Regulations

Methyl methacrylate:	<p>Delaware Air Quality Management List: DRQ: 1000 - RQ State: Federal Regulations Apply</p> <p>Idaho Air Pollutant List: Title 585; AAC: 20,5 - EL: 27,3 - OEL: 410 - Title 586: -</p> <p>Massachusetts Haz. Substance Codes: 2,4,5,6 F8 F9</p> <p>Main: HAP - 2000</p> <p>Minnesota Haz. Substance: Codes: AO - Ratings: 3.79 - Status: Air Pollutant. Title III. TRI.</p> <p>New Jersey RTK Hazardous Substance: DOT: 1247 - Sub No.: 1277</p> <p>New York List of Hazardous Substances: RQ-Air: 1000 - RQ-Land: 1</p> <p>No Note Associated with this chemical</p> <p>Pennsylvania Haz. Substance Code: E</p> <p>Washington Air Contaminant: TWA: 100 ppm = 410 mg</p>
Ethylene di(S-thioacetate):	<p>Massachusetts Haz. Substance codes: 6</p> <p>Pennsylvania Haz. Substance code: -</p>
n-Butyl acrylate:	<p>Delaware Air Quality Management List: DRQ: 100</p> <p>RQ State: State requirement differs from Federal</p> <p>Idaho Air Pollutant List: Title 585 -- AAC: 2.75 -- EL: 3.67 -- WEL: 55</p> <p>Title 586 -</p> <p>Massachusetts Haz. Substance codes: 4,5,6 F9</p> <p>Minnesota Haz. Substance: Codes: A -- Ratings: - -- Status: Title III. TRI.</p> <p>New Jersey RTK Hazardous Substance: DOT: 2348 - Sub No.: 0278 - TPQ: -</p> <p>Pennsylvania Haz. Substance code: E</p> <p>Washington Air Contaminant: TWA: 10 ppm / 55 mg</p>

National regulations - EC member states

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3,40

16. Other information

Text for labeling:

Contains 50 - 70 % Methyl methacrylate, < 10 % 2,2'-Ethylenedioxydiethyl dimethacrylate, < 1 % 1,1'-(p-Tolylimino)dipropen-2-ol, < 0.25 % Ethylene di(S-thioacetate), < 0.25 % Tris(nonylphenyl)phosphite, < 0.25 % n-Butyl acrylate.

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)

Fire: 3 (Serious)

Reactivity: 1 (Slight)

HMIS Version III Rating:

Health: 2 (Moderate)

Flammability: 3 (Serious)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	1
	X

Abbreviations and acronyms:

Acute Toxicity: Acute toxicity
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 Aquatic toxicity - acute: Hazardous to the aquatic environment - acute
 Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic
 AS/NZS: Australian Standards/New Zealand Standards
 BCF: Bioconcentration Factor
 CAS: Chemical Abstracts Service
 CFR: Code of Federal Regulations
 CLP: Classification, Labelling and Packaging
 DMEL: Derived minimal effect level
 DNEL: Derived no-effect level
 EC: Effective Concentration
 EC: European Community
 EC50: Effective Concentration 50%
 EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
 EN: European Standard
 EQ: Excepted quantities
 Eye Irritation: Eye irritation
 Flammable Liquid: Flammable liquid
 IATA: International Air Transport Association
 IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
 IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IMDG Code: International Maritime Dangerous Goods Code
 IMO: International Maritime Organization
 LC0: Lethal concentration 0%
 LC50: Median lethal concentration
 LD50: Lethal dose 50%
 LEL: Lower Explosion Limit
 MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
 MFSU: Manufacture, formulation, supply and use
 NOEC: No Observed Effect Concentration
 OECD: Organisation for Economic Co-operation and Development
 OEL: Occupational Exposure Limit Value
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, bioaccumulative and toxic
 PNEC: Predicted no-effect concentration
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
 Sensitization - skin: Skin sensitisation
 Skin Irritation: Skin irritation
 STOT SE: Specific target organ toxicity - single exposure
 SVHC: Substance of very high concern
 TLV: Threshold Limit Value
 TRGS: Technical Rules for Hazardous Substances
 UN: United Nations
 vPvB: Very persistent and very bioaccumulative
 WEL: Workplace Exposure Limit
 WHMIS: Workplace Hazardous Materials Information System

Reason of change: Changes in section 8: Occupational exposure limit values

Date of first version: 4/9/1998

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.