

1 Identification

Product identifier

Trade name: 617PG5 - OrthoEpoX Hardener GreenLine

Recommended use and restrictions on use

General use: For orthopedic procedures, for producing molds.

Initial supplier identifier

Company name: Otto Bock HealthCare Canada Ltd.

Street/POB-No.: 5470 Harvester Road

Postal code, city: Burlington, ON L7L 5N5, CA
Canada

WWW: www.ottobock.ca

Email: info.canada@ottobock.com

Telephone: (800) 665-3327

Telefax: (800) 463-3659

Department responsible for information:

Mark Agro, Telephone: (800) 665-3327 (9 am - 5 pm)

Additional information:

Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency telephone number

COLLECT, Telephone: (613) 996-6666

Transport:

CONSULTANK Lutz Harder GmbH (Contract QUALI003)

Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2 Hazard identification

Classification

Acute Toxicity 4 (oral)

Harmful if swallowed.

Skin Corrosion 1B

Causes severe skin burns and eye damage.

Eye Damage 1

Causes serious eye damage.

Sensitization - skin 1

May cause an allergic skin reaction.

Aquatic toxicity - chronic 2

Toxic to aquatic life with long lasting effects.

Information elements

Symbols:



Signal word:

Danger

Hazard statements: Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.

Precautionary statements: Do not breathe mist/vapours/spray.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.

Other hazards known to the supplier with respect to the product

Special danger of slipping by leaking/spilling product.

3 Composition/Information on ingredients

Mixture

Hazardous ingredients:

CAS No.	Designation	Content	Classification
CAS 39423-51-3	Trimethylolpropane poly(oxypropylene) triamine	25 - 50 %	Acute Toxicity 4 (oral). Acute Toxicity 4 (dermal). Eye Damage 1. Aquatic toxicity - chronic 2.
CAS 2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine	25 - 50 %	Acute Toxicity 4 (oral). Skin Corrosion 1B. Eye Damage 1. Sensitization - skin 1. Aquatic toxicity - chronic 3.
CAS 90-72-2	2,4,6-Tris (dimethylaminomethyl) phenol	2.5 - 10 %	Skin Corrosion 1C. Sensitization - skin 1.
CAS 71074-89-0	Bis[(dimethylamino) methyl]phenol	< 2.5 %	Skin Corrosion 1C. Eye Damage 1.
CAS 112-24-3	Triethylentetramine	< 2.5 %	Acute Toxicity 4 (dermal). Skin Corrosion 1B. Sensitization - skin 1. Aquatic toxicity - chronic 3.

The actual concentration or concentration range is withheld as a trade secret.

4 First-aid measures

Description of necessary first-aid measures

General information: First aider: Pay attention to self-protection!
If medical advice is needed, have product container or label at hand.
Take off immediately all contaminated clothing and wash it before reuse.

In case of inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.
In case of swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. In case of vomiting, position victim on their side. Keep airway open. Immediately get medical attention.
In case of skin contact:	Immediately clean with water and soap followed by thorough rinsing. Immediately get medical attention.
In case of eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Seek the attention of an ophthalmologist immediately.

Most important symptoms and effects, whether acute or delayed

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful if swallowed.

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

5 Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water spray jet, foam, extinguishing powder, carbon dioxide

Unsuitable extinguishing media:

Full water jet

Specific hazards arising from the product

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: Carbon black, Carbon monoxide and carbon dioxide

Special protective equipment and precautions for fire-fighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Heating will lead to pressure increase: danger of bursting and explosion. Keep containers cool with water spray.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. If possible, eliminate leakage.

Do not breathe mist/vapours/spray. Avoid contact with the substance.

Wear appropriate protective equipment. Take off immediately all contaminated clothing and wash it before reuse. Keep unprotected people away.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains. If necessary, notify appropriate authorities.

Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Never return spills in original containers for re-use.

Carefully neutralize with acid. Final cleaning. Do not use any organic solvents.

Additional information: Special danger of slipping by leaking/spilling product.

7 Handling and storage

Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place. When handling large quantities, supply emergency spray.

Precautions against fire and explosion:
Keep away from heat.
When handling larger quantities, take precautionary measures against electrostatic charging.
Keep away from sources of ignition - No smoking.

Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:
Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position.

Hints on joint storage: Keep away from food, drink and animal feedingstuffs.
Do not store together with: Strong oxidizing agents

8 Exposure controls/Personal protection

Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
112-24-3	Triethylenetetramine	Canada: Ontario, OEL TWA	3 mg/m ³ ; 0.5 ppm (may be absorbed through the skin)

Appropriate engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Individual protection measures, such as personal protective equipment

Respiratory protection:	In case of inadequate ventilation wear respiratory protection. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. Recommendation: Use filter type A (= against vapours of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.
Hand protection:	Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Glove material: Natural latex, PVC (polyvinyl chloride) Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
Body protection:	Wear suitable protective clothing.
General hygiene considerations:	Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place. When handling large quantities, supply emergency spray.

Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

9 Physical and chemical properties

Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	No data available
Odour:	No data available
Odour threshold:	No data available
Melting point and freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower and upper explosion limit or lower and upper flammability limit:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	strongly alkaline
Water solubility:	insoluble
Partition coefficient — n-octanol/water:	No data available
Vapour pressure:	No data available
Density and/or relative density	>= 1 g/mL
Vapour density:	No data available
Particle characteristics:	Not applicable

Additional information

Additional information: No data available

10 Stability and reactivity

Reactivity: Refer to subsection "Possibility of hazardous reactions".

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions:
No hazardous reaction when handled and stored according to provisions.

Conditions to avoid: Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

Incompatible materials: No data available

Hazardous decomposition products:
No hazardous decomposition products when regulations for storage and handling are observed.

11 Toxicological information

Information on the likely routes of exposure

No data available

Health hazard information

Acute toxicity (oral): Acute Toxicity 4 (oral) = Harmful if swallowed.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Skin Corrosion 1B = Causes severe skin burns and eye damage.

Serious eye damage/irritation: Eye Damage 1 = Causes serious eye damage.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information: Information about Trimethylolpropane poly(oxypropylene)triamine:
LD50 Rat, oral: 550 mg/kg
LD50 Rat, dermal: > 1,000 mg/kg
Information about 3-Aminomethyl-3,5,5-trimethylcyclohexylamine:
LD50 Rat, oral: 1,030 mg/kg
Information about Bis[(dimethylamino)methyl]phenol:
LD50 Rat, oral: 2,169 mg/kg

Symptoms

In case of ingestion:
Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract. Burns.
After contact with skin: Irritation, redness, burns.
After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

12 Ecological information

Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.
Information about Trimethylolpropane poly(oxypropylene)triamine:
Fish toxicity:
LC50: > 100 mg/L/96h (OECD 203)
Daphnia toxicity:
EC50 DaphniaSp.: 13 mg/L/48h (OECD 202)
Algae toxicity:
EC50 growth rate: 4.4 mg/L/72h
NOEC: 1 mg/L/72h

Persistence and degradability

Further details: No data available

Bioaccumulative potential

Partition coefficient — n-octanol/water:
No data available

Mobility in soil

No data available

Other adverse effects

General information: Do not allow to penetrate into soil, waterbodies or drains.

13 Disposal considerations

Waste treatment methods

Product

Recommendation: Do not dispose of with household waste.
Special waste. Incinerate according to applicable local, state and federal regulations.

Package

Recommendation: Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.
Non-contaminated packages may be recycled.

14 Transport information

UN number

TDG: UN2735
IMDG, IATA-DGR: UN 2735

UN proper shipping name

TDG, IMDG, IATA-DGR: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S.
(Trimethylolpropane poly(oxypropylene)triamine)

Transport hazard class

TDG: 8
IMDG: Class 8, Subrisk -
IATA-DGR: Class 8

Packing group

TDG, IMDG, IATA-DGR: II

Environmental hazards

Marine pollutant: yes



Special precautions in connection with transport or conveyance either within or outside the premises

Canada: Transportation of Dangerous Goods (TDG)

Special Provisions: 16
Explosive limit and limited quantity index: 1 L
Passenger carrying road or rail index: 1 L

Sea transport (IMDG)

EmS:	F-A, S-B
Special Provisions:	274
Limited quantities:	1 L
Excepted quantities:	E2
Package - Instructions:	P001
Package - Provisions:	-
IBC - Instructions:	IBC02
IBC - Provisions:	-
Tank instructions - IMO:	-
Tank instructions - UN:	T11
Tank instructions - Provisions:	TP1, TP27
Stowage and handling:	Category A.
Segregation:	SG35
Properties and observations:	Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. React violently with acids. Cause burns to skin, eyes and mucous membranes.
Marine pollutant:	yes
Segregation group:	18

Air transport (IATA)

Proper shipping name:	UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (Trimethylolpropane poly(oxypropylene)triamine)
Hazard label:	Corrosive
Excepted Quantity Code:	E2
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y840 - Max. Net Qty/Pkg. 0.5 L
Passenger and Cargo Aircraft:	Pack.Instr. 851 - Max. Net Qty/Pkg. 1 L
Cargo Aircraft only:	Pack.Instr. 855 - Max. Net Qty/Pkg. 30 L
Special Provisions:	A3 A803
Emergency Response Guide-Code (ERG):	8L

15 Regulatory information

National regulations - Canada

Trimethylolpropane poly(oxypropylene)triamine:	DSL: listed
3-Aminomethyl-3,5,5-trimethylcyclohexylamine:	DSL: listed
2,4,6-Tris(dimethylaminomethyl)phenol:	DSL: listed
Triethyltetramine:	DSL: listed

Further regulations, limitations and legal requirements

No data available

16 Other information

Text for labelling:	Contains: Trimethylolpropane poly(oxypropylene)triamine 3-Aminomethyl-3,5,5-trimethylcyclohexylamine 2,4,6-Tris(dimethylaminomethyl)phenol Bis[(dimethylamino)methyl]phenol Triethyltetramine
Revision date:	17/12/2025
Date of first version:	15/2/2022
Reason of change:	General revision: Safety Data Sheet according to Hazardous Products Regulations (HPR) 2022
Abbreviations and acronyms:	<p>Acute Toxicity: Acute toxicity Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic AS/NZS: Australian Standards/New Zealand Standards Bw: Body weight CAS: Chemical Abstracts Service CFR: Code of Federal Regulations CLP: Classification, Labelling and Packaging DMEL: Derived minimal effect level DNEL: Derived no-effect level DSL: Domestic Substances List EC: European Community EC50: Effective Concentration 50% EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods EN: European Standard EQ: Excepted quantities Eye Damage: Eye damage IATA: International Air Transport Association IATA-DGR: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IMDG Code: International Maritime Dangerous Goods Code IMO: International Maritime Organization LC50: Median lethal concentration LD50: Lethal dose 50% MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships MFSU: Manufacture, formulation, supply and use NOEC: No Observed Effect Concentration OECD: Organisation for Economic Co-operation and Development OSHA: Occupational Safety and Health Administration PBT: Persistent, bioaccumulative and toxic PNEC: Predicted no-effect concentration PVC: Polyvinyl chloride Sensitization - skin: Skin sensitisation Skin Corrosion: Skin corrosion TDG: Transportation of Dangerous Goods Regulation in Canada TRGS: Technical Rules for Hazardous Substances UN: United Nations vPvB: Very persistent and very bioaccumulative</p>

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.