

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 1 of 9

1 Identification

Product identifier

Trade name: 617Z5 - Pigment Paste, yellow, for resins

Recommended use and restrictions on use

General use: Pigment paste for lamination resin for orthopedic procedures
For commercial user only

Initial supplier identifier

Company name: Otto Bock HealthCare Canada Ltd.

Street/POB-No.: 5470 Harvester Road

Postal code, city: Burlington, ON L7L 5N5, CA
Canada

WWW: www.ottobock.ca

Email: info.canada@ottobock.com

Telephone: (800) 665-3327

Telefax: (800) 463-3659

Department responsible for information:

Mark Agro, Telephone: (800) 665-3327 (9 am - 5 pm)

Additional information:

Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency telephone number

COLLECT, Telephone: (613) 996-6666

Transport:

CONSULTANK Lutz Harder GmbH (Contract QUALI003)

Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2 Hazard identification

Classification

Skin Irritation 2

Causes skin irritation.

Eye Irritation 2A

Causes serious eye irritation.

Sensitization - skin 1

May cause an allergic skin reaction.

Aquatic toxicity - chronic 2

Toxic to aquatic life with long lasting effects.

Information elements

Symbols:



Signal word:

Warning

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 2 of 9

Hazard statements:

- Causes skin irritation.
- May cause an allergic skin reaction.
- Causes serious eye irritation.
- Toxic to aquatic life with long lasting effects.

Precautionary statements:

- Avoid breathing mist/vapours/spray.
- Wash hands and face thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective gloves/protective clothing/eye protection.
- IF ON SKIN: Wash with plenty of water/soap.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Specific treatment (see 'First aid' on this label).
- If skin irritation occurs: Get medical advice/attention.
- If skin irritation or rash occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Take off contaminated clothing and wash it before reuse.
- Collect spillage.
- Dispose of contents/container to hazardous or special waste collection point.

Other hazards known to the supplier with respect to the product

Special danger of slipping by leaking/spilling product.

3 Composition/Information on ingredients

Mixture

Chemical name: Mixture of binders and pigments.

Hazardous ingredients:

CAS No.	Designation	Content	Classification
CAS 25068-38-6	Reaction product: Bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight ≤ 700)	25 - 50 %	Skin Irritation 2. Eye Irritation 2A. Sensitization - skin 1. Aquatic toxicity - chronic 2.

The actual concentration or concentration range is withheld as a trade secret.

4 First-aid measures

Description of necessary first-aid measures

General information: In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation: Provide fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration. When in doubt or if symptoms are observed, get medical advice.

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 3 of 9

In case of swallowing:	Have victim repeatedly drink large amounts of water with activated charcoal. Never give anything by mouth to an unconscious person. Do not induce vomiting. In case of breathing difficulties administer oxygen. Seek medical attention.
In case of skin contact:	Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with soap and plenty of water. Do not use solvents or thinners. In case of skin reactions, consult a physician.
In case of eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.

Most important symptoms and effects, whether acute or delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

5 Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Alcohol resistant foam, carbon dioxide, extinguishing powder, water spray jet

Unsuitable extinguishing media:

Strong water jet

Specific hazards arising from the product

Exposure to fire produces thick, black smoke that is hazardous to health.
Hazardous decomposition byproducts may form with exposure to high temperatures.
E.g.: Hydrogen chloride, Carbon monoxide, carbon dioxide and fume.
Inhaling hazardous decomposing products can cause serious health damage.

Special protective equipment and precautions for fire-fighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Use fine water spray to cool endangered containers.
Do not allow water used to extinguish fire to enter drains, ground or waterways. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear appropriate protective equipment. Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash it before reuse. Keep unprotected people away. Avoid the formation of aerosol/vapours. Avoid breathing dust/fume/gas/mist/vapours/spray.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.
If necessary, notify appropriate authorities.

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 4 of 9

Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Thoroughly clean surrounding area. Clean using cleansing agents. Do not use solvents.

Additional information: Special danger of slipping by leaking/spilling product.

7 Handling and storage

Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.
Avoid the formation of aerosol/vapours. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear appropriate protective equipment. Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash it before reuse.
Do not empty containers with pressure - no pressure vessel!
Handle and open container with care.
Have eye wash bottle or eye rinse ready at work place. Wash hands before breaks and after work.

Precautions against fire and explosion: Keep away from heat sources, sparks and open flames. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers: Store only in original, tightly closed containers at room temperature.
Store containers in upright position. storage temperature: 15 - 30 °C.
Protect against heat /sun rays.

Hints on joint storage: Keep away from strongly acidic and alkaline materials as well as oxidizers.
Keep away from food, drink and animal feedingstuffs.

8 Exposure controls/Personal protection

Control parameters

Appropriate engineering controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

Respiratory protection: In case of warming: development of gas/vapour possible:
Use filter type A (= against vapours of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 5 of 9

Hand protection:	Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Glove material: Nitrile rubber (0.4 mm) Chloroprene rubber (0.5 mm) Butyl caoutchouc (butyl rubber) (0.7 mm) Breakthrough time: > 480 min Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
Body protection:	Wear suitable protective clothing and shoes.
General hygiene considerations:	When using do not eat, drink or smoke. Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash it before reuse. Do not use any organic solvents. Wash hands before breaks and after work. Have eye wash bottle or eye rinse ready at work place.

Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

9 Physical and chemical properties

Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	Form: pasty yellow
Odour:	weak
Odour threshold:	No data available
Melting point and freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower and upper explosion limit or lower and upper flammability limit:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Water solubility:	miscible
Partition coefficient — n-octanol/water:	No data available
Vapour pressure:	No data available
Density and/or relative density	at 20 °C: 1.63 g/cm ³
Vapour density:	No data available
Particle characteristics:	Not applicable

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 6 of 9

Additional information

Additional information: No data available

10 Stability and reactivity

Reactivity: Refer to subsection "Possibility of hazardous reactions".

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions: Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

Conditions to avoid: Take precautionary measures against static discharges.
Protect against heat /sun rays.

Incompatible materials: Avoid contact with strong acids, strong bases and strong oxidizing agents.

Hazardous decomposition products: Hazardous decomposition products such as carbon dioxide, carbon monoxide, fumes, nitrogen oxides may develop with exposure to high temperatures.

11 Toxicological information

Information on the likely routes of exposure

No data available

Health hazard information

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.

Serious eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 7 of 9

Symptoms

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

12 Ecological information

Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

Persistence and degradability

Further details: No data available

Bioaccumulative potential

Partition coefficient — n-octanol/water:
No data available

Mobility in soil

No data available

Other adverse effects

General information: Do not allow to penetrate into soil, waterbodies or drains.

13 Disposal considerations

Waste treatment methods

Product

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.
Do not dispose of with household waste.

Package

Recommendation: Waste key number:
150104 metallic packaging
150102 Plastic packaging
Dispose of waste according to applicable legislation.

14 Transport information

UN number

TDG: UN3082
IMDG, IATA-DGR: UN 3082

UN proper shipping name

TDG, IMDG, IATA-DGR: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Bisphenol A epoxy resin)

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 8 of 9

Transport hazard class

TDG: 9
IMDG: Class 9, Subrisk -
IATA-DGR: Class 9



Packing group

TDG, IMDG, IATA-DGR: III



Environmental hazards

Marine pollutant: yes

Special precautions in connection with transport or conveyance either within or outside the premises

Canada: Transportation of Dangerous Goods (TDG)

Special Provisions: 16, 99
Explosive limit and limited quantity index: 5 L
Marine pollutant: P

Sea transport (IMDG)

EmS: F-A, S-F
Special Provisions: 274 335 375 969
Limited quantities: 5 L
Excepted quantities: E1
Package - Instructions: P001, LP01
Package - Provisions: PP1
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP1, TP29
Stowage and handling: Category A.
Properties and observations: -
Marine pollutant: yes
Segregation group: none

Air transport (IATA)

Proper shipping name: UN 3082,
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Bisphenol A epoxy resin)
Hazard label: Miscellaneous & Environmentally hazardous
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
Cargo Aircraft only: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
Special Provisions: A97 A158 A197 A215
Emergency Response Guide-Code (ERG): 9L

617Z5 - Pigment Paste, yellow, for resins

Material number 617Z 5

Page: 9 of 9

15 Regulatory information

National regulations - Canada

Reaction product: Bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight \leq 700): DSL: listed

Further regulations, limitations and legal requirements

No data available

16 Other information

Text for labelling: Contains Reaction product: Bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight \leq 700).

Revision date: 1/1/2026

Date of first version: 6/10/1994

Reason of change: Changes in section 14: IATA-DGR 2026

Abbreviations and acronyms:

Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
DSL: Domestic Substances List
EC: European Community
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
Eye Irritation: Eye irritation
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
Sensitization - skin: Skin sensitisation
Skin Irritation: Skin irritation
TDG: Transportation of Dangerous Goods Regulation in Canada
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.