

## 1. Identification

### Product identifier

Trade name: 13/625/757 - Lithium-ion battery

This safety data sheet pertains to the following products:

13E210 - Power Pack für DynamicArm  
625B11 - Lithium-Ion Akkupack für Kniegelenk  
757B35=3 - MyoEnergy Integral  
757VAB1 - VASI Li-Ion Batterie

### Relevant identified uses of the substance or mixture and uses advised against

General use: Lithium-ion battery for orthopedic procedures  
For commercial user only.

### Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care  
Street/POB-No.: 3820 W. Great Lakes Drive  
Zip code, city: Salt Lake City, UT 84120  
USA  
WWW: [www.ottobockus.com](http://www.ottobockus.com)  
Telephone: +1 (801) 956-2400  
Telefax: +1 (801) 956-2401  
Department responsible for information:  
Quality Department,  
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),  
Email: [USRegulatory@ottobock.com](mailto:USRegulatory@ottobock.com)  
Additional information: Corporate headquarters:  
Ottobock SE & Co. KGaA  
Max-Näder-Straße 15  
Duderstadt  
Germany

### Emergency telephone number

CHEMTREC, Telephone: +1 (800) 424-9300  
Transport:  
CONSULTANK Lutz Harder GmbH (Contract QUALI003)  
Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

## 2. Hazard identification

### Classification of the substance or mixture

Article not subject to hazard labelling or classification.

### Label elements

not applicable

### Other hazards

The battery is hermetically sealed.

danger of releasing ingredients, mentioned in section 3, by damaging the battery

- with strong mechanical action,
- in case of heating and/or Fire,
- with influence of water,
- short circuit.

Hazard statements:

Limited evidence of a carcinogenic effect. May cause sensitization by skin contact.

Electrolyte, organic:

Flammable. Vapors irritate eyes, mucous membranes and respiratory system. Vapors may cause drowsiness and dizziness.

After contact with water: formation of Hydrogen fluoride (Fatal in contact with skin. Fatal if swallowed. Fatal if inhaled. Causes severe skin burns and eye damage.).

## 3. Composition/information on ingredients

### Mixtures

Chemical characterization: Lithium-ion battery - Article.

The chemical materials are stored in a hermetically sealed metal case.

Contains Aluminium (10 - 40%), Graphite (10 - 20%), Carbon (10 - 20%), Copper (5 - 15%).

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 12190-79-3	Cobalt lithium dioxide	20 - 40 %	Respiratory Sensitizer - Category 1. Sensitization - skin - Category 1. Carcinogenicity - Category 2.
CAS -	Electrolyte, organic	5 - 20 %	Flammable Liquid - Category 3.

The actual concentration or concentration range is withheld as a trade secret.

## 4. First aid measures

General information: In case of damaged battery cases: Release of dangerous ingredients possible.

In case of heating: Generates dangerous gases or fumes in contact with.

In case of inhalation: In case of damaged battery cases:

Provide fresh air. Keep victim at rest in half upright position. Seek medical attention.

Following skin contact: In case of damaged battery cases / In case of exposure to hazardous ingredients:

Clean with plenty of water. If possible, also wash with polyethylene glycol 400.

Take off immediately all contaminated clothing and wash it before reuse. Seek medical treatment in case of troubles.

After eye contact: In case of damaged battery cases / In case of exposure to hazardous ingredients:

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Afterwards, consult an ophthalmologist immediately.

After swallowing: Induce vomiting when the affected person is not unconscious.  
In case of damaged battery cases / In case of exposure to hazardous ingredients:  
Drink large quantities of water.  
Do not induce vomiting. Risk of perforation in case of vomiting!  
Immediately get medical attention. Do not try to neutralize.

### Most important symptoms/effects, acute and delayed

No hazardous reaction when handled and stored according to provisions.  
In case of damaged battery cases / In case of exposure to hazardous ingredients:  
May cause an allergic skin reaction. Irritation. May cause drowsiness or dizziness.

### Information to physician

Treat symptomatically.

## 5. Fire-fighting measures

### Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

Dry chemical powder, Extinguishing agent on the basis of sodium chloride, sodium hydrogen carbonate, limestone, or with metal extinguishing powder.

Extinguishing media which must not be used for safety reasons:

Water, foam.

### Specific hazards arising from the chemical

In case of fire may be liberated: hydrogen fluoride, carbon monoxide and carbon dioxide.

### Protective equipment and precautions for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

In case of damaged battery cases:  
Remove all sources of ignition.  
Provide fresh air. Avoid contact with skin and eyes.  
Wear suitable gloves. Take off immediately all contaminated clothing and wash it before reuse.  
In case of development of vapors or dust:  
Do not inhale vapors or dust particles.

Environmental precautions:

Discharge into the environment must be avoided.

### Methods and material for containment and cleaning up

Methods for clean-up:

Take up mechanically. Dispose of waste according to applicable legislation.  
Electrolyte, organic: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal. Final cleaning.

## 7. Handling and storage

### Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.

Avoid damage to the battery casing.

In case of damaged battery cases: Avoid exposure.

Precautions against fire and explosion:

Avoid short circuit. Avoid damage to the battery casing.

In case of damaged battery cases: Remove all sources of ignition.

### Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Provide adequate ventilation. Store in a dry place.

Protect from: humidity, heat, UV-radiation/sunlight.

Storage temperature: -68 °F up to 95 °F.

Air humidity: 45% up to 85%.

Hints on joint storage:

Do not store together with strong acids, strong oxidizing agents.

## 8. Exposure controls/personal protection

### Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
7429-90-5	Aluminium	USA: ACGIH: TWA	1 mg/m <sup>3</sup>
		USA: NIOSH: Ceiling	5 mg/m <sup>3</sup> (inhalable fraction)
		USA: NIOSH: TWA	10 mg/m <sup>3</sup> (inhalable fraction)
		USA: NIOSH: TWA	5 mg/m <sup>3</sup> (inhalable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> (inhalable fraction)
		USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)
7782-42-5	Graphite	USA: ACGIH: TWA	2 mg/m <sup>3</sup> (respirable fraction)
		USA: IDLH: TWA	1,250 mg/m <sup>3</sup>
		USA: NIOSH: TWA	2.5 mg/m <sup>3</sup> (respirable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> (total dust)
		USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)
7440-44-0	Carbon	USA: ACGIH: TWA	10 mg/m <sup>3</sup>
			(Dust limit value, inhalable fraction)
		USA: ACGIH: TWA	3 mg/m <sup>3</sup>
			(Dust limit value, respirable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> (inhalable fraction)
7440-50-8	Copper	USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)
		USA: ACGIH: TWA	0.2 mg/m <sup>3</sup> (Smoke)
		USA: ACGIH: TWA	1 mg/m <sup>3</sup>
			(Dusts and mist calculated as Cu)
		USA: IDLH: TWA	100 Cu/m <sup>3</sup> (dust and mist)
		USA: IDLH: TWA	100 Cu/m <sup>3</sup> (Smoke)
		USA: NIOSH: TWA	1 mg/m <sup>3</sup>
		USA: OSHA: TWA	0.1 mg/m <sup>3</sup> (Smoke; calculated as Cu)
		USA: OSHA: TWA	1 mg/m <sup>3</sup>
			(Dusts and mist calculated as Cu)

Additional information: The chemical materials are stored in a sealed battery case.

### Appropriate engineering controls

In case of damaged battery cases: Provide adequate ventilation.  
In case of development of vapors or dust:  
The use of local exhaust ventilation is recommended.

### Personal protection equipment (PPE)

**Respiratory protection:** In case of damaged battery cases:  
Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.  
Half mask with particle filter P according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.  
If necessary: When vapors form combination filter Use filter type A, B, K according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.

**Hand protection:** In case of damaged battery cases:  
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.  
Glove material: rubber - breakthrough time >480 min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

**Eye protection:** In case of damaged battery cases:  
Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

**General hygiene considerations:**  
In case of damaged battery cases:  
Do not inhale vapors or dust particles.  
Avoid contact with skin and eyes.  
Keep away from sources of ignition - No smoking.  
Wash hands before breaks and after work.

### Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state at 68 °F and 101.3 kPa	Form: solid
Color:	No data available
Odor:	odorless
Odor threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	No data available
Explosion limits:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Viscosity:	No data available

Solubility: No data available  
Partition coefficient: n-octanol/water: No data available  
Vapor pressure: No data available  
Density: No data available  
Vapor density: No data available  
Particle characteristics: Not applicable

### Additional information

Additional information: No data available

## 10. Stability and reactivity

Reactivity: No data available

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions:

Fire hazard in case of technical defects.  
In case of damaged battery cases:  
Electrolyte, organic: Flammable.  
After contact with water: formation of Hydrogen fluoride.

Conditions to avoid:

> 212 °F: Generation of heat. Ignition.  
Protect from: humidity, water, marine water, heat, UV-radiation/sunlight  
Avoid short circuit. Avoid damage to the battery casing.  
In case of damaged battery cases:  
Keep away from sources of ignition - No smoking. Protect from: water.

Incompatible materials:

Keep away from strong acids and strong oxidizing agents.  
In case of damaged battery cases:  
Electrolyte, organic: Keep away from water.

Hazardous decomposition products:

In case of fire may be liberated: hydrogen fluoride, carbon monoxide and carbon dioxide.

## 11. Toxicological information

### Information on toxicological effects

Toxicological effects:	<p>Acute toxicity (oral): Lack of data.</p> <p>Acute toxicity (dermal): Lack of data.</p> <p>Acute toxicity (inhalative): Lack of data.</p> <p>Skin corrosion/irritation: Lack of data.</p> <p>Serious eye damage/irritation: Lack of data.</p> <p>Sensitisation to the respiratory tract: Lack of data.</p> <p>Skin sensitisation: Lack of data.</p> <p>Germ cell mutagenicity/Genotoxicity: Lack of data.</p> <p>Carcinogenicity: Lack of data.</p> <p>Reproductive toxicity: Lack of data.</p> <p>Effects on or via lactation: Lack of data.</p> <p>Specific target organ toxicity (single exposure): Lack of data.</p> <p>Specific target organ toxicity (repeated exposure): Lack of data.</p> <p>Aspiration hazard: Lack of data.</p>
Other information:	<p>In case of damaged battery cases:</p> <p>cobalt lithium dioxide:</p> <p>Limited evidence of a carcinogenic effect. May cause sensitization by skin contact. (Cobalt: LDLo Guinea pig oral 20 mg/kg)</p> <p>Electrolyte, organic:</p> <p>Vapors irritate eyes, mucous membranes and respiratory system.</p> <p>Vapors may cause drowsiness and dizziness.</p> <p>After contact with water: formation of Hydrogen fluoride (Fatal in contact with skin. Fatal if swallowed. Fatal if inhaled. Causes severe skin burns and eye damage.).</p>

## 12. Ecological information

### Ecotoxicity

Further details: No data available

### Persistence and degradability

Further details: Product is not biodegradable.

### Bioaccumulative potential

Partition coefficient: n-octanol/water:  
No data available

### Mobility in soil

No data available

### Other adverse effects

General information: Discharge into the environment must be avoided.

## 13. Disposal considerations

### Waste treatment methods

#### Product

Recommendation: Dispose of waste according to applicable legislation.

#### Package

Recommendation: Dispose of waste according to applicable legislation.  
Packing can be recycled or disposed of.

## 14. Transport information

### UN number

DOT: UN3480

IMDG, IATA-DGR: UN 3480

### UN proper shipping name

DOT, IMDG, IATA-DGR: UN 3480, LITHIUM ION BATTERIES

### Transport hazard class(es)

DOT: 9

IMDG: Class 9, Subrisk -

IATA-DGR: Class 9



### Packing group

DOT, IATA-DGR: not applicable

IMDG: -

### Environmental hazards

Marine pollutant: no

### Transport in bulk according to IMO instruments

No data available

### Special precautions for user

#### USA: Department of Transportation (DOT)

Labels: 9

Special Provisions: 388, 422, A54, A100

Packaging – Exceptions: 185

Packaging – Non-bulk: 185

Packaging – Bulk: 185

Quantity limitations – Passenger aircraft / rail:

Forbidden

Quantity limitations – Cargo only: 35 kg

Vessel stowage – Location: A

Vessel stowage – Other: 156



### Sea transport (IMDG)

EmS:	F-A, S-I
Special Provisions:	188 230 310 348 376 377 384 387
Limited quantities:	0
Excepted quantities:	E0
Package - Instructions:	P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
Package - Provisions:	-
IBC - Instructions:	-
IBC - Provisions:	-
Tank instructions - IMO:	-
Tank instructions - UN:	-
Tank instructions - Provisions:	-
Stowage and handling:	Category A. SW19
Properties and observations:	Electrical batteries containing lithium ion may react (e.g., flame, heat, emission of toxic, corrosive or flammable gases or vapours) or disassemble due to damage, defects or short circuit.
Marine pollutant:	no
Segregation group:	none

### Air transport (IATA)

Proper shipping name:	UN 3480, LITHIUM ION BATTERIES
Hazard label:	Lithium batt or Sodium-ion batt
Excepted Quantity Code:	E0
Passenger and Cargo Aircraft: Ltd.Qty.:	Forbidden
Passenger and Cargo Aircraft:	Forbidden
Cargo Aircraft only:	Pack.Instr. See 965 - Max. Net Qty/Pkg. See 965
Special Provisions:	A88 A99 A154 A183 A201 A213 A331 A334 A802
Emergency Response Guide-Code (ERG):	12FZ

## 15. Regulatory information

### National regulations - U.S. Federal Regulations

This product is an article as defined by TSCA regulations, and is exempt from TSCA inventory listing requirements.

### National regulations - U.S. State Regulations

Copper: New York Right-To-Know: listed

### Further regulations, limitations and legal requirements

No data available

## 16. Other information

Revision date:	1/1/2026
Date of first version:	10/26/2010
Reason of change:	Changes in section 14: IATA-DGR 2026

Hazard rating systems:



**NFPA Hazard Rating:**

Health: 0 (Minimal)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

**HMIS Version III Rating:**

Health: 0 (Minimal)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

in case of damaged battery cases: NFPA/HMIS: F2

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Abbreviations and acronyms:

AS/NZS: Australian Standards/New Zealand Standards  
 Carcinogenicity: Carcinogenicity  
 CAS: Chemical Abstracts Service  
 CFR: Code of Federal Regulations  
 CLP: Classification, Labelling and Packaging  
 DMEL: Derived minimal effect level  
 DNEL: Derived no-effect level  
 DOT: Department of Transportation's Safety Regulations (USA)  
 EC: European Community  
 EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods  
 EN: European Standard  
 EQ: Excepted quantities  
 Flammable Liquid: Flammable liquid  
 IATA: International Air Transport Association  
 IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
 IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
 IMDG Code: International Maritime Dangerous Goods Code  
 IMO: International Maritime Organization  
 MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
 OEL: Occupational Exposure Limit Value  
 OSHA: Occupational Safety and Health Administration  
 PBT: Persistent, bioaccumulative and toxic  
 PNEC: Predicted no-effect concentration  
 Respiratory Sensitizer: Sensitisation to the respiratory tract  
 Sensitization - skin: Skin sensitisation  
 TLV: Threshold Limit Value  
 TRGS: Technical Rules for Hazardous Substances  
 TSCA: Toxic Substance Control Act  
 UN: United Nations  
 UV: Ultraviolet  
 vPvB: Very persistent and very bioaccumulative  
 WEL: Workplace Exposure Limit

**Department issuing data sheet**

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.