

1. Identification

Product identifier

Trade name: 616T11X - ThermoLyn supra

This safety data sheet pertains to the following products:

Article No. 616T111 - ThermoLyn supra soft plus Silikon

Article No. 616T112 - ThermoLyn supra flexible

Article No. 616T113 - ThermoLyn supra flexible

Relevant identified uses of the substance or mixture and uses advised against

General use: Article for orthopedic procedures.

Processing at Processing temperature and Forming temperature
(refer to section 9: Physical and chemical properties)

Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care

Street/POB-No.: 3820 W. Great Lakes Drive

Zip code, city: Salt Lake City, UT 84120
USA

WWW: www.ottobockus.com

Telephone: +1 (801) 956-2400

Telefax: +1 (801) 956-2401

Department responsible for information:

Quality Department,

Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),

Email: USRegulatory@ottobock.com

Additional information: Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency telephone number

CHEMTREC, Telephone: +1 (800) 424-9300

2. Hazard identification

Classification of the substance or mixture

Article not subject to hazard labelling or classification.

Label elements

not applicable

Other hazards

Processing by heating can produce vapors. Processing, e.g. by cutting, sawing or grinding, can produce particles and dust. For risks which have to be observed thereby, see section 7: Handling, section 8: Exposure controls / personal protection and section 11: Toxicology.

In case of heating: risk of burns.
 Danger of cutaneous absorption.
 dust/vapors: mild irritant

3. Composition/information on ingredients

Substances

Chemical characterization: copolymer based on Ethylene and Vinyl acetate (EVA) and Silicone (616T111), pigments (inorganic).

4. First aid measures

General information: For mechanical processing: dust formation.
 Processing by heating can produce vapors.

In case of inhalation: Dusts/vapors:
 Provide fresh air. Seek medical treatment in case of troubles.

Following skin contact: Remove residues with water. Seek medical treatment in case of troubles.
 If burned by hot product, quench immediately with cold tap water.
 Do not peel solidified product off the skin. Immediately get medical attention.

After eye contact: Dusts/vapors:
 Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.
 In case of troubles or persistent symptoms, consult an ophthalmologist.

Most important symptoms/effects, acute and delayed

In case of heating: risk of burns.
 Danger of cutaneous absorption.
 dust/vapors: mild irritant

Information to physician

Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:
 Water spray jet, foam, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:
 Full water jet,

Specific hazards arising from the chemical

Harmful and/or toxic vapors may be produced in the event of thermal decomposition.
In case of fire may be liberated: acetic acid-vapors, nitrogen oxides (NOx), Vinyl acetate, alcohol, aldehydes, Silicone, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Suitable protective clothing. Keep unprotected people away.
In case of development of vapors or dust:
Provide fresh air. Do not inhale vapors or dust particles. Wear protective equipment.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

Methods and material for containment and cleaning up

Methods for clean-up: Take up mechanically, placing in appropriate containers for disposal.

7. Handling and storage

Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.

Processing: Make sure that the processing machines are well equipped with suction and ventilation systems.

If necessary: With the formation of dust, use a dust mask.

In case of development of vapors or dust:

Provide fresh air. Do not inhale vapors or dust particles. Wear protective equipment.

Precautions against fire and explosion:

Avoid open flames.

Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep only in the original container.

Keep container tightly closed and dry. Protect from moisture contamination.

Protect from direct sunlight.

storage temperature: 50 - 86 °F

Hints on joint storage:

Avoid contact with acids and bases .

8. Exposure controls/personal protection

Control parameters

Occupational exposure limit values:

Type	Limit value
USA: ACGIH: TWA	10 mg/m ³ (Dust limit value, inhalable fraction)
USA: ACGIH: TWA	3 mg/m ³ (Dust limit value, respirable fraction)
USA: OSHA: TWA	15 mg/m ³ (Dust limit value, total dust)
USA: OSHA: TWA	5 mg/m ³ (Dust limit value, respirable fraction)

Appropriate engineering controls

Provide for constant fresh air supply during and after processing.

Personal protection equipment (PPE)

Respiratory protection:	When vapors form: Use combination filter type A, B, E according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2. For mechanical processing: Half mask with particle filter P according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.
Hand protection:	protective gloves according to OSHA Standard - 29 CFR: 1910.138 If necessary: Protective gloves against thermic risks. For machine processing: Protective gloves against mechanical risks. OSHA Standard - 29 CFR: 1910.138 Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
Body protection:	Suitable protective clothing.
General hygiene considerations:	When using do not eat, drink or smoke. Avoid generation of dust. Wash hands before breaks and after work. The following shall be existing in the immediate working surrounding: emergency shower installed.

Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state at 68 °F and 101.3 kPa	Form: solid, plate
Color:	varying, depends on coloring
Odor:	acidic
Odor threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	No data available

Explosion limits:	No data available
Flash point/flash point range:	> 500 °F
Evaporation rate:	No data available
Auto-ignition temperature:	not self-igniting
Decomposition temperature:	> 200 °C
pH:	No data available
Viscosity:	No data available
Solubility:	chloroform: soluble
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	No data available
Vapor pressure:	No data available
Density:	at 68 °F: 0.95 g/cm ³
Vapor density:	No data available
Particle characteristics:	Not applicable

Additional information

Explosive properties:	Product is not explosive.
Additional information:	softening range: 176 - 194 °F Processing temperature, Recommendation: 302 °F

10. Stability and reactivity

Reactivity:	refer to section 10.3
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	No dangerous reactions are known.
Conditions to avoid:	Protect from moisture contamination. Keep away from heat. Protect from direct sunlight. Processing: Avoid temperatures exceeding 302 °F.
Incompatible materials:	Avoid contact with acids and bases .
Hazardous decomposition products:	If heated to decomposition product may emit: Monomer(s). In case of fire may be liberated: acetic acid-vapors, nitrogen oxides (NOx), Vinyl acetate, alcohol, aldehydes, Silicone, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on toxicological effects

Toxicological effects: Acute toxicity (oral): Based on available data, the classification criteria are not met. LD50 Rat, oral: 2920 mg/kg
Acute toxicity (dermal): Based on available data, the classification criteria are not met. LD50 Rat, dermal: 2335 mg/kg
Acute toxicity (inhalative): Based on available data, the classification criteria are not met. LD50 Rat, inhalative: 4000 ppm
Skin corrosion/irritation: Lack of data.
Serious eye damage/irritation: Lack of data.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Lack of data.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Lack of data.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: Vinyl acetate:
skin: mild irritant. Causes serious eye irritation.

Symptoms

In case of heating: risk of burns.
In case of inhalation: dust/vapors: mild irritant
After contact with skin: Danger of cutaneous absorption.
After eye contact: dust/vapors: mild irritant

12. Ecological information

Ecotoxicity

Further details: No data available

Persistence and degradability

Further details: Product is not biodegradable.

Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

Mobility in soil

No data available

Other adverse effects

General information: Do not allow to penetrate into soil, waterbodies or drains.

13. Disposal considerations

Waste treatment methods

Product

Recommendation: Incinerate according to applicable local, state and federal regulations.

Package

Recommendation: Dispose of waste according to applicable legislation.
Non-contaminated packages may be recycled.

14. Transport information

UN number

DOT, IMDG, IATA-DGR: not applicable

UN proper shipping name

DOT, IMDG, IATA-DGR: Not restricted

Transport hazard class(es)

DOT, IMDG, IATA-DGR: not applicable

Packing group

DOT, IMDG, IATA-DGR: not applicable

Environmental hazards

Marine pollutant: no

Transport in bulk according to IMO instruments

No data available

Special precautions for user

USA: Department of Transportation (DOT)

Proper shipping name: Not restricted

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: no

Air transport (IATA)

Proper shipping name: Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

National regulations - U.S. Federal Regulations

This product is an article as defined by TSCA regulations, and is exempt from TSCA inventory listing requirements.

National regulations - U.S. State Regulations

No data available

Further regulations, limitations and legal requirements

No data available

16. Other information

Revision date: 12/17/2025

Date of first version: 5/14/2013

Reason of change: General revision: Safety Data Sheet according to Hazardous Products Regulations (HPR) 2022

General revision: Safety Data Sheet according to HCS 2024 (29 CFR 1910.1200)

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Abbreviations and acronyms:

AS/NZS: Australian Standards/New Zealand Standards

CAS: Chemical Abstracts Service

CFR: Code of Federal Regulations

CLP: Classification, Labelling and Packaging

DMEL: Derived minimal effect level

DNEL: Derived no-effect level

DOT: Department of Transportation's Safety Regulations (USA)

EC: European Community

EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods

EN: European Standard

EQ: Excepted quantities

IATA: International Air Transport Association

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OSHA: Occupational Safety and Health Administration

PBT: Persistent, bioaccumulative and toxic

PNEC: Predicted no-effect concentration

TRGS: Technical Rules for Hazardous Substances

TSCA: Toxic Substance Control Act

vPvB: Very persistent and very bioaccumulative

Literature:

At processing: See information supplied by the manufacturer.



SAFETY DATA SHEET

according to HCS 2024 (29 CFR 1910.1200)

616T11X - ThermoLyn supra

Material number 616T11X

Revision date: 12/17/2025

Version: 5.4

Replaces version: 5.3

Language: en-US

Date of print: 5/29/2026

Page: 9 of 9

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.