

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 1 of 14

1. Identification

Product identifier

Trade name: 617H500 - Orthovinyl Lamination Resin

Relevant identified uses of the substance or mixture and uses advised against

General use: Production of plastics
For orthopedic procedures.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care
Street/POB-No.: 3820 W. Great Lakes Drive
Zip code, city: Salt Lake City, UT 84120
USA
WWW: www.ottobockus.com
Telephone: +1 (801) 956-2400
Telefax: +1 (801) 956-2401
Department responsible for information: Quality Department,
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),
Email: USRegulatory@ottobock.com
Additional information: Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency telephone number

CHEMTREC, Telephone: +1 (800) 424-9300
Transport:
CONSULTANK Lutz Harder GmbH (Contract QUALI003)
Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2. Hazard identification

Classification of the substance or mixture

Flammable Liquid - Category 3	Flammable liquid and vapor.
Acute Toxicity - inhalative - Category 4	Harmful if inhaled.
Skin Irritation - Category 2	Causes skin irritation.
Eye Irritation - Category 2A	Causes serious eye irritation.
Reproductive toxicant - Category 2	Suspected of damaging the unborn child.
Specific Target Organ Toxicity (Single Exposure) - Category 3	May cause respiratory irritation.
Specific Target Organ Toxicity (Repeated Exposure) - Category 1	Causes damage to organs through prolonged or repeated exposure.
Aquatic toxicity - chronic - Category 3	Harmful to aquatic life with long lasting effects.

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page:

2 of 14

Label elements

Symbols:



Signal word:

Danger

Hazard statements:

Flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.
May cause respiratory irritation.
Suspected of damaging the unborn child.
Causes damage to organs through prolonged or repeated exposure.
Harmful to aquatic life with long lasting effects.

Precautionary statements:

Obtain special instructions before use.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not breathe fume/gas/mist/vapors/spray.
Wear protective gloves/protective clothing/eye protection/face protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Store in a well-ventilated place. Keep cool.

Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.
Special danger of slipping by leaking/spilling product.

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 3 of 14

3. Composition/information on ingredients

Mixtures

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 100-42-5	Styrene	25 - 30 %	Flammable Liquid - Category 3. Acute Toxicity - inhalative - Category 4. Skin Irritation - Category 2. Eye Irritation - Category 2A. Reproductive toxicant - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Specific Target Organ Toxicity (Repeated Exposure) - Category 1. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 3.
CAS 64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	2.5 - 10 %	Flammable Liquid - Category 3. Specific Target Organ Toxicity (Single Exposure) - Category 3. Specific Target Organ Toxicity (Repeated Exposure) - Category 1. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 79-41-4	Methacrylic acid	< 3 %	Acute Toxicity - oral - Category 4. Acute Toxicity - dermal - Category 4. Skin Corrosion - Category 1A.
CAS 91-66-7	N,N-Diethylaniline	< 1 %	Acute Toxicity - oral - Category 3. Acute Toxicity - dermal - Category 3. Acute Toxicity - inhalative - Category 3. Specific Target Organ Toxicity (Repeated Exposure) - Category 2. Aquatic toxicity - chronic - Category 2.
CAS 123-31-9	Hydroquinone	< 0.1 %	Acute Toxicity - oral - Category 4. Eye Damage - Category 1. Sensitization - skin - Category 1. Germ cell mutagenicity - Category 2. Carcinogenicity - Category 2. Aquatic toxicity - acute - Category 1 (M-factor = 10).

The actual concentration or concentration range is withheld as a trade secret.

4. First aid measures

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
In case of inhalation:	Move victim to fresh air. In case of breathing difficulties administer oxygen. In case of irregular breathing or respiratory arrest provide artificial respiration. Seek medical attention.
Following skin contact:	Wash affected skin with generous amount of water. Immediately get medical attention.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 4 of 14

After swallowing: Do not induce vomiting. Danger of aspiration! Immediately get medical attention. Aspiration of this product into the lungs during vomiting, may cause serious injury or death. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed

Harmful if inhaled.
Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation.
Causes damage to organs through prolonged or repeated exposure.

Information to physician

When swallowed and vomited immediately, aspiration into the lungs may occur resulting in chemical pneumonia or suffocation.
Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

Alcohol resistant foam, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

Specific hazards arising from the chemical

Flammable liquid and vapor.
Air combined with vapors may form potentially explosive mixtures that are heavier than air. Vapors may proceed on the ground over great distances and cause fire and backflashes.
In case of fire may be liberated: nitrogen oxides (NO_x), Carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Heating will lead to pressure increase: danger of bursting and explosion. Keep containers cool with water spray.
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Do not allow fire water to penetrate into surface or ground water.
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Do not breathe mist/vapors/spray. Eliminate all ignition sources if safe to do so. If possible, eliminate leakage. Provide adequate ventilation.
Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.
Cordon off downwind area at risk and warn inhabitants.

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 5 of 14

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.
If necessary, notify appropriate authorities.

Methods and material for containment and cleaning up

Methods for clean-up: Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).
Beware of reignition. Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.
Special danger of slipping by leaking/spilling product.

7. Handling and storage

Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Avoid breathing vapors. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
Guarantee sufficient ventilation during and after use, in order to prevent vapor accumulation.
When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharge.
Use only explosion-protected equipment/instruments. Do not weld.
In partially filled containers explosive mixtures may form.

Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
100-42-5	Styrene	USA: ACGIH: STEL	20 ppm
		USA: ACGIH: TWA	10 ppm
		USA: IDLH: TWA	700 ppm
		USA: NIOSH: STEL	425 mg/m ³ ; 100 ppm
		USA: NIOSH: TWA	215 mg/m ³ ; 50 ppm
		USA: OSHA: Ceiling	200 ppm
		USA: OSHA: TWA	100 ppm
79-41-4	Methacrylic acid	USA: ACGIH: TWA	70 mg/m ³ ; 20 ppm
		USA: NIOSH: TWA	70 mg/m ³ ; 20 ppm
			(may be absorbed through the skin)
123-31-9	Hydroquinone	USA: ACGIH: TWA	1 mg/m ³
		USA: IDLH: TWA	50 mg/m ³
		USA: NIOSH: Ceiling	2 mg/m ³
		USA: OSHA: TWA	2 mg/m ³

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
100-42-5	Styrene	USA:	150 mg/g	Mandelic acid +	end of exposure or
		ACGIH-BEI,	creatinine	Phenylglyoxylic acid	end of shift
		urine			
		USA:	20 µg/L	Styrene in urine	end of exposure or
		ACGIH-BEI,			end of shift
		urine			

Appropriate engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

Personal protection equipment (PPE)

Respiratory protection:	Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. Use filter type A (= against vapors of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2. Use respiratory protection whenever ventilation is inadequate.
Hand protection:	Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Glove material: butyl caoutchouc (butyl rubber) - Layer thickness: 0.7 mm Breakthrough time: 30 min Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
Body protection:	Flame retardant, antistatic and chemical resistant protective clothing.

General hygiene considerations:

Take off contaminated clothing and wash it before reuse.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Avoid breathing vapors. Do not get in eyes, on skin, or on clothing.
Contaminated work clothing should not be allowed out of the workplace.
When using do not eat or drink.
Wash hands thoroughly after handling.
When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state at 68 °F and 101.3 kPa	liquid
Color:	yellow
Odor:	characteristic
Odor threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	No data available
Explosion limits:	No data available
Flash point/flash point range:	91.4 °F (ISO 3679-B)
Evaporation rate:	No data available
Auto-ignition temperature:	914 °F
Decomposition temperature:	No data available
pH:	No data available
Dynamic viscosity:	at 104 °F: 260 mPa*s
Viscosity, kinematic:	at 73.4 °F: > 61 s (ISO 2431, 6 mm) at 104 °F: 247.15 mm²/s
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Vapor pressure:	No data available
Density:	at 68 °F: 1.061 g/mL at 104 °F: 1.052 g/mL
Vapor density:	No data available
Particle characteristics:	Not applicable

10. Stability and reactivity

Reactivity:	Flammable liquid and vapor. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 8 of 14

Possibility of hazardous reactions:

Heating will lead to pressure increase: danger of bursting and explosion.

Conditions to avoid:

Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

Incompatible materials:

Peroxides.

Hazardous decomposition products:

No decomposition when used properly.

11. Toxicological information

Information on toxicological effects

Toxicological effects:

The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

ATEmix calculated: ATEmix => 10,000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

ATEmix calculated: ATEmix => 10,000 mg/kg

Acute toxicity (inhalative): Acute Toxicity - inhalative - Category 4 = Harmful if inhaled.

ATEmix calculated:

ATEmix vapors: 37.56 mg/L

ATEmix dust/mist: 4.83

Skin corrosion/irritation: Skin Irritation - Category 2 = Causes skin irritation.

Serious eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Reproductive toxicant -

Category 2 = Suspected of damaging the unborn child.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) - Category 3 = May cause respiratory irritation.

Specific target organ toxicity (repeated exposure): Specific Target Organ Toxicity (Repeated Exposure) -

Category 1 = Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard: Based on available data, the classification criteria are not met.

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 9 of 14

Other information: Information about Styrene:
LD50 Rat, oral: > 5,000 mg/kg
LD50 Rat, dermal: > 5,000 mg/kg
LD50 Rat, inhalative (vapors): 11.8 mg/L/4h
Information about Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):
LD50 Rat, oral: > 2,000 mg/kg
LD50 Rabbit, dermal: > 2,000 mg/kg
LD50 Rat, inhalative: > 5 mg/L/4h
Chronic toxicity - Carcinogenic effect:
ACGIH, EPA, IARC, OSHA, and NTP carcinogen lists have been checked for selected similar materials or those components.
Styrene:
IARC Rating: Group 2B
OSHA Carcinogen: not listed
NTP Rating: listed

Symptoms

In case of inhalation: headache, Nausea, dizziness
In case of ingestion:
Danger of aspiration! Aspiration of this product into the lungs during vomiting, may cause serious injury or death.

12. Ecological information

Ecotoxicity

Aquatic toxicity: Information about Styrene:
Fish toxicity: LC50 > 0.1 - 10 mg/L
Daphnia toxicity: EC50 > 0.1 - 10 mg/L
Algae toxicity: EC50 > 0.1 - 10 mg/L

Persistence and degradability

Further details: Information about Styrene: readily biodegradable

Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

Mobility in soil

No data available

Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.
Spilled quantities may penetrate into soil and lead to a contamination of ground water.

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 10 of 14

13. Disposal considerations**Waste treatment methods****Product**

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.
Do not dispose of with household waste.
Do not empty into drains.

Package

Recommendation: Dispose of waste according to applicable legislation.
Non-contaminated packages may be recycled.

14. Transport information**UN number**

DOT: UN1866
IMDG, IATA-DGR: UN 1866

UN proper shipping name

DOT, IMDG, IATA-DGR: UN 1866, RESIN SOLUTION

Transport hazard class(es)

DOT: 3
IMDG: Class 3, Subrisk -
IATA-DGR: Class 3

**Packing group**

DOT, IMDG, IATA-DGR: III

Environmental hazards

Marine pollutant: no

Transport in bulk according to IMO instruments

No data available

Special precautions for user**USA: Department of Transportation (DOT)**

Labels: 3
Special Provisions: B1, B52, IB3, T2, TP1
Packaging – Exceptions: 150
Packaging – Non-bulk: 173
Packaging – Bulk: 242
Quantity limitations – Passenger aircraft / rail: 60 L
Quantity limitations – Cargo only: 220 L
Vessel stowage – Location: A



SAFETY DATA SHEET

according to HCS 2024 (29 CFR 1910.1200)

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Revision date: 11/28/2025
Version: 6.3
Replaces version: 6.2
Language: en-US
Date of print: 5/29/2026

Page: 11 of 14

Sea transport (IMDG)

EmS: F-E, S-E
Special Provisions: 223 955
Limited quantities: 5 L
Excepted quantities: E1
Package - Instructions: P001, LP01
Package - Provisions: PP1
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T2
Tank instructions - Provisions: TP1
Stowage and handling: Category A.
Properties and observations: Miscibility with water depends upon the composition.
Marine pollutant: no
Segregation group: none
Remarks: Transport in containers with max. 30 litres contents are not subject to the regulations of IMDG according to No 2.3.2.5.

Air transport (IATA)

Proper shipping name: UN 1866, RESIN SOLUTION
Hazard label: Flamm. liquid
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special Provisions: A3
Emergency Response Guide-Code (ERG): 3L

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 12 of 14

15. Regulatory information

National regulations - U.S. Federal Regulations

Styrene:

TSCA Inventory: listed
Carcinogen Status: IARC Rating: Group 2A
OSHA Carcinogen: not listed
NTP Rating: listed
Clean Air Act:
CAA Hazardous Air Pollutants: yes
CAA SOCM Chemical: yes
Clean Water Act:
CWA Hazardous Substances: Category C; RQ 1000.0 lbs
Other Environmental Laws:
CERCLA: RQ 1000 lbs.
RCRA Groundwater Monitoring: listed
SARA Title III, Section 313, Toxic Release: NPFAS; De Minimis
≤0.1 %; Thresholds 25000/10000 lbs
NIOSH Recommendations:
Occupational Health Guideline: 0571

Hydrocarbons, C9-C12, n-alkanes,
isoalkanes, cyclics, aromatics
(2-25%):

TSCA Inventory: listed; UVCB

Methacrylic acid:

TSCA Inventory: listed
Clean Air Act:
CAA SOCM Chemical: yes
NIOSH Recommendations:
Occupational Health Guideline: 0386*

N,N-Diethylaniline:

TSCA Inventory: listed
Other Environmental Laws:
CERCLA: RQ 1000 lbs.

Hydroquinone:

TSCA Inventory: listed
Carcinogen Status: IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
Clean Air Act:
CAA Hazardous Air Pollutants: yes
CAA SOCM Chemical: yes
Other Environmental Laws:
CERCLA: RQ 100 lbs.
SARA Title III, Section 302, EHS: Note f; TPQ 500/10000 lbs; RQ
100.0 lbs
SARA Title III, Section 313, Toxic Release: NPFAS; De Minimis
≤1.0 %; Thresholds 25000/10000 lbs
NIOSH Recommendations:
Occupational Health Guideline: 0338

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 13 of 14

National regulations - U.S. State Regulations

Product:	<p>Delaware Air Quality Management List: DRQ: 1000 - RQ State: Federal Regulations Apply Idaho Air Pollutant List: Title 585 -- AAC: 1 -- EL: 6.67 -- WEL: - Title 586 - Maine Hazardous Air Pollutants: Me 2005: HAP - Hap Rpt: 2000 Massachusetts Haz. Substance codes: 1,2,4,5,6,9 *E*C* F7 F8 Michigan Critical Material: Note: 2 - CMR#: 27 - Parameter#: 00100-42-5 - Annual Usage Parameter: 100 Minnesota Haz. Substance: Codes: ANO -- Ratings: 9.63 -- Status: Air Pollutant. Carcinogen. Title III. TRI. New Jersey RTK Hazardous Substance: DOT 2055 - Sub No.: 1748 - TPQ: - New York List of Hazardous Substances: RQ -- Air: 1000 - RQ -- Land: 1 - Note: No Note Associated with this chemical. Pennsylvania Haz. Substance code: E Washington Air Contaminant: TWA: 50 ppm / 215 mg -- STEL: 100 ppm / 425 mg</p>
Styrene:	<p>California Proposition 65: cancer New York Right-To-Know: listed</p>
N,N-Diethylaniline:	New York Right-To-Know: listed
Hydroquinone:	New York Right-To-Know: listed

Further regulations, limitations and legal requirements

No data available

16. Other information

Text for labeling: Contains 25 - 30 % Styrene, 2.5 - 10 % Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 3 % Methacrylic acid, < 1 % N,N-Diethylaniline, < 0.1 % Hydroquinone.

Revision date: 11/28/2025

Date of first version: 7/7/2020

Reason of change: General revision: Safety Data Sheet according to HCS 2024 (29 CFR 1910.1200)

Hazard rating systems: NFPA Hazard Rating:



Health: 3 (Serious)

Fire: 3 (Serious)

Reactivity: 1 (Slight)

HMIS Version III Rating:

Health: 3 (Serious) - Chronic effects

Flammability: 3 (Serious)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		1
X		

Abbreviations and acronyms:

Acute Toxicity: Acute toxicity

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

Aquatic toxicity - acute: Hazardous to the aquatic environment - acute

617H500 - Orthovinyl Lamination Resin

Material number 617H500

Page: 14 of 14

Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
Aspiration Toxicity: Aspiration toxicity
ATEmix: Acute Toxicity Estimate of mixture
Carcinogenicity: Carcinogenicity
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
DOT: Department of Transportation's Safety Regulations (USA)
EC: European Community
EC50: Effective Concentration 50%
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
Eye Damage: Eye damage
Eye Irritation: Eye irritation
Flammable Liquid: Flammable liquid
Germ cell mutagenicity: Mutagenicity
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LD50: Lethal dose 50%
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
M-factor: Multiplication factor
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
Reproductive toxicant: Reproductive toxicity
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
Sensitization - skin: Skin sensitisation
Skin Corrosion: Skin corrosion
Skin Irritation: Skin irritation
STOT RE: Specific target organ toxicity - repeated exposure
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.