

## 1. Identification

### Product identifier

Trade name: 617H5 - Orthopox Epoxy Resin

### Relevant identified uses of the substance or mixture and uses advised against

General use: For orthopedic procedures, for producing molds.

### Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care

Street/POB-No.: 3820 W. Great Lakes Drive

Zip code, city: Salt Lake City, UT 84120  
USA

WWW: [www.ottobockus.com](http://www.ottobockus.com)

Telephone: +1 (801) 956-2400

Telefax: +1 (801) 956-2401

Department responsible for information:

Quality Department,

Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),

Email: [USRegulatory@ottobock.com](mailto:USRegulatory@ottobock.com)

Additional information:

Corporate headquarters:

Ottobock SE & Co. KGaA

Max-Näder-Straße 15

Duderstadt

Germany

### Emergency telephone number

CHEMTREC, Telephone: +1 (800) 424-9300

Transport:

CONSULTANK Lutz Harder GmbH (Contract QUALI003)

Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

## 2. Hazard identification

### Classification of the substance or mixture

Skin Irritation - Category 2

Causes skin irritation.

Eye Irritation - Category 2A

Causes serious eye irritation.

Sensitization - skin - Category 1

May cause an allergic skin reaction.

Reproductive toxicant - Category 1B

May damage fertility.

Aquatic toxicity - chronic - Category 2

Toxic to aquatic life with long lasting effects.

### Label elements

Symbols:



Signal word:

**Danger**

Hazard statements: Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May damage fertility.  
Toxic to aquatic life with long lasting effects.

Precautionary statements: Obtain special instructions before use.  
Avoid breathing mist/vapors/spray.  
Wash hands and face thoroughly after handling.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection.  
  
IF exposed or concerned: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
Collect spillage.

### Other hazards

Special danger of slipping by leaking/spilling product.

## 3. Composition/information on ingredients

### Mixtures

Chemical characterization: Bisphenol A epoxy resin-composition

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 1675-54-3	Bis-[4-(2,3-Epoxypropoxy)phenyl]propane	25 - 50 %	Skin Irritation - Category 2. Eye Irritation - Category 2. Sensitization - skin - Category 1. Aquatic toxicity - chronic - Category 2.
CAS -	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane	25 - 50 %	Skin Irritation - Category 2. Sensitization - skin - Category 1A. Aquatic toxicity - chronic - Category 2.
CAS 2425-79-8	1,4-Bis(2,3-epoxypropoxy)butane	10 - 25 %	Acute Toxicity - oral - Category 4. Acute Toxicity - dermal - Category 4. Acute Toxicity - inhalative - Category 4. Skin Irritation - Category 2. Eye Irritation - Category 2. Sensitization - skin - Category 1. Reproductive toxicant - Category 1B. Aquatic toxicity - chronic - Category 3.

The actual concentration or concentration range is withheld as a trade secret.

### 4. First aid measures

General information:	First aider: Pay attention to self-protection! If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
In case of inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist. If unconscious place in recovery position and seek medical advice.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. In case of vomiting, position victim on their side. Keep airway open. Immediately get medical attention.

### Most important symptoms/effects, acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

### Information to physician

Treat symptomatically.  
For specialist advice physicians should contact the Poisons Information Service.

### 5. Fire-fighting measures

#### Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

Water spray jet, carbon dioxide (CO<sub>2</sub>), alcohol resistant foam, dry chemical powder.

Extinguishing media which must not be used for safety reasons:

Full water jet

#### Specific hazards arising from the chemical

May form dangerous gases and vapors in case of fire.  
Furthermore, there may develop: Halogenated compounds, Carbon monoxide and carbon dioxide.

#### Protective equipment and precautions for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Heating will lead to pressure increase: danger of bursting and explosion. Keep containers cool with water spray.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid exposure. Do not breathe mist/vapors/spray. Avoid contact with the substance.  
If possible, eliminate leakage. Provide adequate ventilation.  
Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.

#### Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

### Methods and material for containment and cleaning up

Methods for clean-up: Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Never return spills in original containers for re-use.

Additional information: Special danger of slipping by leaking/spilling product.

## 7. Handling and storage

### Precautions for safe handling

Advices on safe handling: Obtain special instructions before use.  
Provide adequate ventilation, and local exhaust as needed. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.  
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse.  
Work place should be equipped with a shower and an eye rinsing apparatus.

#### Precautions against fire and explosion:

Keep away from heat.  
When handling larger quantities, take precautionary measures against electrostatic charging.  
Keep away from sources of ignition - No smoking.

### Conditions for safe storage, including any incompatibilities

#### Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.  
Keep container dry. Keep only in the original container.  
Protect from heat and direct sunlight.  
Store containers in upright position.

#### Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.  
Do not store together with: Strong oxidizing agents

## 8. Exposure controls/personal protection

### Appropriate engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

### Personal protection equipment (PPE)

Respiratory protection:	In case of inadequate ventilation wear respiratory protection. The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. Recommendation: Use filter type A (= against vapors of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.
Hand protection:	Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Glove material: butyl caoutchouc (butyl rubber) Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
Body protection:	Wear suitable protective clothing.
General hygiene considerations:	Obtain special instructions before use. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Work place should be equipped with a shower and an eye rinsing apparatus.

People who suffer from skins problems, asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this mixture.

### Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state at 68 °F and 101.3 kPa	liquid
Color:	Colorless-light yellow
Odor:	No data available
Odor threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	No data available
Explosion limits:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Viscosity:	No data available
Solubility:	No data available

Partition coefficient: n-octanol/water:

2.64 - 3.78 log P(o/w) (Bis-[4-(2,3-Epoxypropoxy)phenyl]propane)

Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.

-0.269 - 0.15 log P(o/w) (1,4-Bis(2,3-epoxypropoxy)butane)

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

3.3 log P(o/w) (Reaction mass of

2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and

2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and

2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane)

Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.

Vapor pressure:

No data available

Density:

No data available

Vapor density:

No data available

Particle characteristics:

Not applicable

### Additional information

Additional information:

No data available

## 10. Stability and reactivity

Reactivity:

Refer to subsection "Possibility of hazardous reactions".

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

No dangerous reactions are known.

Conditions to avoid:

Keep away from heat sources, sparks and open flames.

Protect from direct sunlight.

Incompatible materials:

Strong oxidizing agents.

Hazardous decomposition products:

No decomposition when used properly.

## 11. Toxicological information

### Information on toxicological effects

**Toxicological effects:** The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.  
ATEmix: > 5,000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.  
ATEmix: > 5,000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.  
ATEmix, vapors: > 50 mg/L

Skin corrosion/irritation: Skin Irritation - Category 2 = Causes skin irritation.

Serious eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Sensitization - skin - Category 1 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Reproductive toxicant - Category 1B = May damage fertility.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

**Other information:** Information about Bis-[4-(2,3-Epoxypropoxy)phenyl]propane (CAS No. 1675-54-3):  
LD50 Rat, oral: > 15,000 mg/kg  
LD50 Rabbit, dermal: > 23,000 mg/kg

Information about Reaction mass of  
2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and  
2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and  
2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane (List number 701-263-0):  
LD50 Rat, oral: > 5,000 mg/kg (OECD 401, no mortality occurred)  
LD50 Rat, dermal: > 2,000 mg/kg (OECD 402, no mortality occurred)

Information about 1,4-Bis(2,3-epoxypropoxy)butane (CAS No. 2425-79-8):  
LD50 Rat, oral: 1.163 mg/kg (OECD 401)  
LD50 Rat, dermal: > 2,150 mg/kg (OECD 402, no mortality occurred)  
LD50 Rabbit, dermal: 1,130 mg/kg  
ATE inhalative, vapors: 11 mg/L

### Symptoms

After sensitization even concentrations below the exposure limit values may cause asthma.

Other symptoms: Reduced fetal weight, weight increase, increase in skeletal deformities

In case of ingestion:  
Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.

After contact with skin: Irritation, redness

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

Information about Bis-[4-(2,3-Epoxypropoxi)phenyl]propane (CAS No. 1675-54-3):

Fish toxicity:

LC50 Oncorhynchus mykiss: 2.0 mg/L/96h (geometric mean concentration)

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): 1.8 mg/L/48h (geometric mean concentration)

NOEC Daphnia magna (Big water flea): 0.3 mg/L/21d (OECD 211)

Algae toxicity:

EC50 Scenedesmus capricornutum, growth rate: > 11 mg/L/72h (maximum achievable concentration)

NOEC Scenedesmus capricornutum, growth rate: 4.2 mg/L/72h

Information about Reaction mass of

2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and

2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and

2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane (List number 701-263-0):

Fish toxicity:

LC50: 2.54 mg/L/96h

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): 2.55 mg/L/48h

NOEC Daphnia magna (Big water flea): 0.3 mg/L/21d (OECD 211)

Algae toxicity:

EC50 Selenastrum capricornutum (green algae), growth rate: 1.8 mg/L/72h

### Persistence and degradability

Further details:

Product is not readily biodegradable.

### Bioaccumulative potential

Partition coefficient: n-octanol/water:

2.64 - 3.78 log P(o/w) (Bis-[4-(2,3-Epoxypropoxi)phenyl]propane)

Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.

-0.269 - 0.15 log P(o/w) (1,4-Bis(2,3-epoxypropoxy)butane)

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

3.3 log P(o/w) (Reaction mass of

2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and

2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and

2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane)

Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.

### Mobility in soil

No data available

### Other adverse effects

AOX reference:

The product contains organically bound halogen. Thus it may add to the AOX value.

General information:

Do not allow to enter into ground-water, surface water or drains.



## 13. Disposal considerations

### Waste treatment methods

#### Product

Recommendation: Do not dispose of with household waste.  
Special waste. Incinerate according to applicable local, state and federal regulations.

#### Package

Recommendation: Dispose of waste according to applicable legislation.  
Handle contaminated packages in the same way as the substance itself.  
Non-contaminated packages may be recycled.

## 14. Transport information

### UN number

DOT: UN3082  
IMDG, IATA-DGR: UN 3082

### UN proper shipping name

DOT, IMDG, IATA-DGR: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Bisphenol-A epoxy resin (average molecular weight  $\leq 700$ )  
Bisphenol-F-epichlorohydrin resin (molecular weight  $\leq 700$ ))

### Transport hazard class(es)

DOT: 9  
IMDG: Class 9, Subrisk -  
IATA-DGR: Class 9



### Packing group

DOT, IMDG, IATA-DGR: III

### Environmental hazards

Marine pollutant: yes

### Transport in bulk according to IMO instruments

No data available

### Special precautions for user

#### USA: Department of Transportation (DOT)

Labels: 9  
Symbols: G  
Special Provisions: 8, 146, 173, 335, 441, IB3, T4, TP1, TP29  
Packaging – Exceptions: 155  
Packaging – Non-bulk: 203  
Packaging – Bulk: 241  
Quantity limitations – Passenger aircraft / rail: No limit  
Quantity limitations – Cargo only: No limit  
Vessel stowage – Location: A

### Sea transport (IMDG)

EmS: F-A, S-F  
 Special Provisions: 274 335 375 969  
 Limited quantities: 5 L  
 Excepted quantities: E1  
 Package - Instructions: P001, LP01  
 Package - Provisions: PP1  
 IBC - Instructions: IBC03  
 IBC - Provisions: -  
 Tank instructions - IMO: -  
 Tank instructions - UN: T4  
 Tank instructions - Provisions: TP1, TP29  
 Stowage and handling: Category A.  
 Properties and observations: -  
 Marine pollutant: yes  
 Segregation group: none

### Air transport (IATA)

Proper shipping name: UN 3082,  
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
 (Bisphenol-A epoxy resin (average molecular weight  $\leq 700$ )  
 Bisphenol-F-epichlorohydrin resin (molecular weight  $\leq 700$ ))  
 Hazard label: Miscellaneous & Environmentally hazardous  
 Excepted Quantity Code: E1  
 Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G  
 Passenger and Cargo Aircraft: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L  
 Cargo Aircraft only: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L  
 Special Provisions: A97 A158 A197 A215  
 Emergency Response Guide-Code (ERG): 9L

### Further information

Make sure that persons transporting the product know what to do in case of an accident or leakage.

## 15. Regulatory information

### National regulations - U.S. Federal Regulations

Bis-[4-(2,3-Epoxypropoxy)phenyl]propane: TSCA Inventory: listed  
 Carcinogen Status:  
 IARC Rating: Group 3  
 OSHA Carcinogen: not listed  
 NTP Rating: not listed  
 1,4-Bis(2,3-epoxypropoxy)butane: TSCA Inventory: listed

### National regulations - U.S. State Regulations

No data available

### Further regulations, limitations and legal requirements

No data available

## 16. Other information

Text for labeling: Contains 25 - 50 % Bis-[4-(2,3-Epoxypropoxy)phenyl]propane, 25 - 50 % Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane, 10 - 25 % 1,4-Bis(2,3-epoxypropoxy)butane.  
Restricted to professional users.

Revision date: 1/1/2026

Date of first version: 1/17/2018

Reason of change: Changes in section 14: IATA-DGR 2026

Classification procedure: Physical hazards: on basis of test data  
Health hazards, environmental hazards: calculation method

Hazard rating systems: NFPA Hazard Rating:



Health: 1 (Slight)  
Fire: 1 (Slight)  
Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)  
Flammability: 1 (Slight)  
Physical Hazard: 0 (Minimal)  
Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Abbreviations and acronyms:

Acute Toxicity: Acute toxicity  
AOX: Adsorbable Organic Halogens  
Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic  
AS/NZS: Australian Standards/New Zealand Standards  
ATE: Acute toxicity estimate  
ATEmix: Acute Toxicity Estimate of mixture  
CAS: Chemical Abstracts Service  
CFR: Code of Federal Regulations  
CLP: Classification, Labelling and Packaging  
DMEL: Derived minimal effect level  
DNEL: Derived no-effect level  
DOT: Department of Transportation's Safety Regulations (USA)  
EC: European Community  
EC50: Effective Concentration 50%  
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods  
EN: European Standard  
EQ: Excepted quantities  
Eye Irritation: Eye irritation  
IATA: International Air Transport Association  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
IMDG Code: International Maritime Dangerous Goods Code  
IMO: International Maritime Organization  
LC50: Median lethal concentration  
LD50: Lethal dose 50%  
log P(o/w): Partition coefficient: octanol/water  
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
MFSU: Manufacture, formulation, supply and use  
NOEC: No Observed Effect Concentration  
OECD: Organisation for Economic Co-operation and Development  
OSHA: Occupational Safety and Health Administration  
PBT: Persistent, bioaccumulative and toxic  
PNEC: Predicted no-effect concentration  
Reproductive toxicant: Reproductive toxicity  
Sensitization - skin: Skin sensitisation  
Skin Irritation: Skin irritation  
TRGS: Technical Rules for Hazardous Substances  
UN: United Nations  
vPvB: Very persistent and very bioaccumulative



# SAFETY DATA SHEET

according to HCS 2024 (29 CFR 1910.1200)

## 617H5 - Orthopox Epoxy Resin

Material number 617H 5

Revision date: 1/1/2026

Version: 5.2

Replaces version: 5.1

Language: en-US

Date of print: 5/29/2026

Page: 12 of 12

### Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.