

## 1. Identification

### Product identifier

Trade name: 617Z9 - Pigment Paste, black

### Relevant identified uses of the substance or mixture and uses advised against

General use: Pigment paste for lamination resin, for orthopedic procedures  
For commercial user only

### Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care  
Street/POB-No.: 3820 W. Great Lakes Drive  
Zip code, city: Salt Lake City, UT 84120  
USA

WWW: [www.ottobockus.com](http://www.ottobockus.com)

Telephone: +1 (801) 956-2400

Telefax: +1 (801) 956-2401

Department responsible for information:

Quality Department,  
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),  
Email: [USRegulatory@ottobock.com](mailto:USRegulatory@ottobock.com)

Additional information: Corporate headquarters:  
Ottobock SE & Co. KGaA  
Max-Näder-Straße 15  
Duderstadt  
Germany

### Emergency telephone number

**CHEMTREC, Telephone: +1 (800) 424-9300**

**Transport:**

**CONSULTANK Lutz Harder GmbH (Contract QUALI003)**

**Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)**

## 2. Hazard identification

### Classification of the substance or mixture

Skin Irritation - Category 2	Causes skin irritation.
Eye Irritation - Category 2A	Causes serious eye irritation.
Sensitization - skin - Category 1	May cause an allergic skin reaction.
Aquatic toxicity - chronic - Category 2	Toxic to aquatic life with long lasting effects.

### Label elements

Symbols:



Signal word:

**Warning**

Hazard statements:

- Causes skin irritation.
- May cause an allergic skin reaction.
- Causes serious eye irritation.
- Toxic to aquatic life with long lasting effects.

Precautionary statements:

- Avoid breathing mist/vapors/spray.
- Wash hands and face thoroughly after handling.
- Avoid release to the environment.
- Wear protective gloves/protective clothing/eye protection.
- Take off contaminated clothing and wash it before reuse.
- Collect spillage.

### Other hazards

Special danger of slipping by leaking/spilling product.

## 3. Composition/information on ingredients

### Mixtures

Chemical characterization: A mixture of binder and pigments

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 25068-38-6	Reaction product: Bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight ≤ 700)	25 - 50 %	Skin Irritation - Category 2. Eye Irritation - Category 2A. Sensitization - skin - Category 1. Aquatic toxicity - chronic - Category 2.

The actual concentration or concentration range is withheld as a trade secret.

## 4. First aid measures

General information: In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation: Provide fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration. When in doubt or if symptoms are observed, get medical advice.

Following skin contact: After contact with skin, wash immediately with soap and plenty of water. Do not use solvents or thinners. In case of skin reactions, consult a physician. Take off contaminated clothing and wash it before reuse.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.

After swallowing: Have victim repeatedly drink large amounts of water with activated charcoal. Never give anything by mouth to an unconscious person. Do not induce vomiting. In case of vomiting, position victim on their side. In case of breathing difficulties administer oxygen. Seek medical attention.

### Most important symptoms/effects, acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

### Information to physician

Treat symptomatically.

## 5. Fire-fighting measures

### Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

Alcohol resistant foam, carbon dioxide, dry chemical powder, water spray jet

Extinguishing media which must not be used for safety reasons:

strong water jet

### Specific hazards arising from the chemical

Exposure to fire produces thick, black smoke that is hazardous to health.

Hazardous decomposition byproducts may form with exposure to high temperatures.

E.g.: Hydrogen chloride, Carbon monoxide, carbon dioxide and fume.

Inhaling hazardous decomposing products can cause serious health damage.

### Protective equipment and precautions for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Use fine water spray to cool endangered containers.

Do not allow water used to extinguish fire to enter drains, ground or waterways. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear appropriate protective equipment. Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash it before reuse. Keep unprotected people away. Avoid the formation of aerosol/vapors. Avoid breathing dust/fume/gas/mist/vapors/spray.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.

If necessary, notify appropriate authorities.

### Methods and material for containment and cleaning up

Methods for clean-up:

Take up mechanically, placing in appropriate containers for disposal. Clean using cleansing agents. Do not use solvents.

## 7. Handling and storage

### Precautions for safe handling

Advices on safe handling: Make sure there is sufficient air exchange and / or that working rooms are air suctioned. Avoid the formation of aerosol/vapors. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear appropriate protective equipment. Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash it before reuse. Do not empty containers with pressure - no pressure vessel! Handle and open container with care. Do not breathe vapors. Do not empty containers with pressure - no pressure vessel! Handle and open container with care. Avoid contact with the substance. Have eye wash bottle or eye rinse ready at work place.

Precautions against fire and explosion:

Keep away from heat sources, sparks and open flames. Take precautionary measures against static discharges.

### Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Store only in original, tightly closed containers at room temperature.  
Store containers in upright position. storage temperature: 59 - 86 °F.  
Protect against heat /sun rays.

Hints on joint storage:

Keep away from strongly acidic and alkaline materials as well as oxidizers.  
Keep away from food, drink and animal feedingstuffs.

## 8. Exposure controls/personal protection

### Appropriate engineering controls

Provide adequate ventilation.

### Personal protection equipment (PPE)

Respiratory protection:

In case of warming:  
When vapors form: Use filter type A (= against vapors of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.  
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

Hand protection:

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.  
Glove material:  
Nitrile rubber (0.4 mm)  
Chloroprene rubber (0.5 mm)  
Butyl caoutchouc (butyl rubber) (0.7 mm)  
Breakthrough time: >480 min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection:

Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Body protection:

Wear suitable protective clothing and shoes.

### General hygiene considerations:

When using do not eat, drink or smoke.  
Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash it before reuse.  
Do not use any organic solvents. Wash hands before breaks and after work.  
Have eye wash bottle or eye rinse ready at work place.

### Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state at 68 °F and 101.3 kPa	liquid
Color:	Form: viscous black
Odor:	weak
Odor threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	No data available
Explosion limits:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Viscosity:	No data available
Water solubility:	miscible
Partition coefficient: n-octanol/water:	No data available
Vapor pressure:	No data available
Density:	at 68 °F: 1.78 g/cm <sup>3</sup>
Vapor density:	No data available
Particle characteristics:	Not applicable

### Additional information

Additional information:	No data available
-------------------------	-------------------

## 10. Stability and reactivity

Reactivity:	Refer to subsection "Possibility of hazardous reactions".
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

Conditions to avoid: Take precautionary measures against static discharges.  
Protect against heat /sun rays.

Incompatible materials: Avoid contact with strong acids, strong bases and strong oxidizing agents.

Hazardous decomposition products:  
Hazardous decomposition products such as carbon dioxide, carbon monoxide, fumes, nitrogen oxides may develop with exposure to high temperatures.

## 11. Toxicological information

### Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Skin Irritation - Category 2 = Causes skin irritation.

Serious eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Sensitization - skin - Category 1 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

### Symptoms

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

### Persistence and degradability

Further details: No data available

### Bioaccumulative potential

Partition coefficient: n-octanol/water:  
No data available

## Mobility in soil

No data available

## Other adverse effects

General information: Do not allow to penetrate into soil, waterbodies or drains.

# 13. Disposal considerations

## Waste treatment methods

### Product

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.  
Do not dispose of with household waste.

### Package

Recommendation: Waste key number:  
150104 metallic packaging  
150102 Plastic packaging  
Dispose of waste according to applicable legislation.

# 14. Transport information

## UN number

DOT: UN3082  
IMDG, IATA-DGR: UN 3082

## UN proper shipping name

DOT, IMDG, IATA-DGR: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Bisphenol A epoxy resin)

## Transport hazard class(es)

DOT: 9  
IMDG: Class 9, Subrisk -  
IATA-DGR: Class 9

## Packing group


DOT, IMDG, IATA-DGR: III

## Environmental hazards

Marine pollutant: yes

## Transport in bulk according to IMO instruments

No data available



### Special precautions for user

#### USA: Department of Transportation (DOT)

Labels:	9
Symbols:	G
Special Provisions:	8, 146, 173, 335, 441, IB3, T4, TP1, TP29
Packaging – Exceptions:	155
Packaging – Non-bulk:	203
Packaging – Bulk:	241
Quantity limitations – Passenger aircraft / rail:	No limit
Quantity limitations – Cargo only:	No limit
Vessel stowage – Location:	A

#### Sea transport (IMDG)

EmS:	F-A, S-F
Special Provisions:	274 335 375 969
Limited quantities:	5 L
Excepted quantities:	E1
Package - Instructions:	P001, LP01
Package - Provisions:	PP1
IBC - Instructions:	IBC03
IBC - Provisions:	-
Tank instructions - IMO:	-
Tank instructions - UN:	T4
Tank instructions - Provisions:	TP1, TP29
Stowage and handling:	Category A.
Properties and observations:	-
Marine pollutant:	yes
Segregation group:	none

#### Air transport (IATA)

Proper shipping name:	UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin)
Hazard label:	Miscellaneous & Environmentally hazardous
Excepted Quantity Code:	E1
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft:	Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
Cargo Aircraft only:	Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
Special Provisions:	A97 A158 A197 A215
Emergency Response Guide-Code (ERG):	9L

## 15. Regulatory information

### National regulations - U.S. Federal Regulations

Reaction product: Bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight  $\leq 700$ ):

TSCA Inventory: listed

### National regulations - U.S. State Regulations

California Prop 65 List: None



## Further regulations, limitations and legal requirements

No data available

## 16. Other information

Text for labeling: Contains 25 - 50 % Reaction product: Bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight  $\leq 700$ ).

Contains Reaction product: Bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight  $\leq 700$ ).

Revision date: 1/1/2026

Date of first version: 10/6/1994

Reason of change: Changes in section 14: IATA-DGR 2026

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Abbreviations and acronyms:

Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic

AS/NZS: Australian Standards/New Zealand Standards

CAS: Chemical Abstracts Service

CFR: Code of Federal Regulations

CLP: Classification, Labelling and Packaging

DMEL: Derived minimal effect level

DNEL: Derived no-effect level

DOT: Department of Transportation's Safety Regulations (USA)

EC: European Community

EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods

EN: European Standard

EQ: Excepted quantities

Eye Irritation: Eye irritation

IATA: International Air Transport Association

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OSHA: Occupational Safety and Health Administration

PBT: Persistent, bioaccumulative and toxic

PNEC: Predicted no-effect concentration

Sensitization - skin: Skin sensitisation

Skin Irritation: Skin irritation

TRGS: Technical Rules for Hazardous Substances

UN: United Nations

vPvB: Very persistent and very bioaccumulative

## Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.