



MasterCoat® ULTRA

Build your success on solid ground



Part of

MASTER®
>>BUILDERS
SOLUTIONS

Group

MasterCoat®
ULTRA

Coming from a rich heritage of innovation

Starting the venture and becoming a leading construction chemicals supplier

Strategic realignment and building a unified global identity

Becoming a standalone construction chemicals company

1909 - 2006

Founding of Master Builders Inc.

Acquisition by Sandoz

Acquisition by SKW

Merger of Degussa-Hüls and SKW Trostberg

Acquisition by BASF



degussa.



2010 - 2013

Repositioning and reshaping

Launch of MasterBuilders Solutions brand



2020 - 2021

Carve-out from BASF

MBCC group becomes standalone leader in construction chemicals and admixtures

Direct sales in ~ 150 countries

Acquisition of 4 bolt-ons

MBCC GROUP

Main historical innovations

2001 - 2009

2010 - 2026

Robustness



MasterLife®

Solutions for enhanced durability

MasterSuna®

Clay blocking polymer for difficult sands

Rheology/Workability



MasterEase®

Admixture for low-viscosity engineering concrete

Acceleration



High performance

A leading standalone construction chemicals company

2023

Master Builders Solutions becomes a Cinven Portfolio Company and a standalone leader in admixtures

CINVEN

2024

Acquisition of Adril Traders S.L.

Launch of MB Trading & MBT CC

Joint venture with MBT Tech



2025

Launch of Construction Systems

Acquisition of Rapidmix Group

Acquisition of Brexton Dominicana, S.A.S.



2026

Acquisition of Arkaz Al Sharq Building Materials



MasterSphere®

Superabsorbent polymers for reliable freeze-thaw resistance

MasterCO₂re™

reduces the complexity of low-clinker concrete mixes

MasterFlux®

Specialized grouts for the wind industry

MasterCoat®

High performance polymer flooring

MasterCoat ULTRA – Build your success on solid ground



MasterCoat[®] ULTRA

The Ultimate Industrial Flooring Solution

MasterCoat ULTRA is a range of high-performance polyurethane concrete flooring systems developed for the most demanding environments. In addition to its widespread use in the food and beverage industry, it is designed to deliver optimum performance across a wide range of sectors where high chemical and mechanical resistance, together with hygienic and easy-to-clean surfaces, are required.





Food & Beverage

Hygienic, safe and built for production.



Chemical Industry

Resistant to aggressive chemicals and harsh operating conditions.



Pharma & Healthcare

Clean, controlled environments for critical operations.



ATEX & ESD protection

Safe, static-controlled solutions for hazardous and sensitive areas.



Warehouses & Logistics

Durable, efficient floors for heavy traffic and demanding operations.



MasterCoat® ULTRA provides long-term performance in environments subjected to extreme thermal shock and thermal cycling – withstanding temperatures from -45°C to $+125^{\circ}\text{C}$, depending on the system specification. It is also available in anti-static versions for industries where explosion protection or the control of static discharges are required. By combining rapid installation windows with proven durability, it offers building owners a safe, hygienic and cost-effective solution for any industrial application.



MasterCoat[®] ULTRA

Key Benefits at a Glance

MasterCoat ULTRA is a range of polyurethane concrete flooring materials.

The range is suitable for installation and use in food and beverage production, processing and packaging facilities, as well as in environments subject to thermal shock, cycling and varying degrees of chemical exposure, where it offers a wide range of performance benefits for end users and building owners compared with other flooring materials.



Why choose **MasterCoat® ULTRA?**



Free from phthalates and any other LBC Red List Chemicals



Conductive and dissipative systems for EPA environments



Independently verified food-safe contact surfaces (HACCP International)



Moisture-proof packaging



Bfl-s1 fire classification for limited flame spread and low smoke production



System-based components for optimal inventory control



Engineered to withstand extreme thermal shocks and cycling



12 months shelf life for most components



Excellent resistance to a wide range of harsh chemicals



Satin-finish topcoat for improved cleanability in anti-slip systems



Different systems with applications ranging from 2 mm to 12 mm



Vibrant pigment packs in easy-to-mix sachets



Suitable for steam cleaning, depending on the system specification

High performance polyurethane concrete flooring solutions, engineered for every environment.



MasterCoat
ULTRA SL
smooth, low
thickness system

Low thickness, smooth finish system for general industrial and lightly trafficked areas.

- 2–3 mm thickness
- Smooth finish
- Fast curing
- Easy to clean
- Ideal for refurbishment or overlay

TEXTURE	THICKNESS
Smooth	2 – 3 mm

TYPICAL INDUSTRIES

- Warehouses & Logistics
- Distribution Centres
- General Manufacturing
- Retail & Commercial



MasterCoat
ULTRA MF
smooth system

Medium duty, smooth finish system for a wide range of industrial environments.

- 3–6 mm thickness
- Smooth finish
- Good chemical resistance
- Hygienic and easy to clean
- Reliable performance in wet and dry areas

TEXTURE	THICKNESS
Smooth	3 – 6 mm

TYPICAL INDUSTRIES

- Pharmaceutical
- Healthcare & Labs
- Food Processing (dry areas)
- Manufacturing



MasterCoat
ULTRA MFAS
anti-static system

Anti-static, smooth finish system for areas requiring electrostatic control.

- 3–4 mm thickness
- Smooth finish
- Electrostatic dissipative
- Suitable for ESD areas
- Safe for electronics and sensitive environments

TEXTURE	THICKNESS
Smooth	3 – 4 mm

TYPICAL INDUSTRIES

- ATEX / ESD Areas
- Electronics & Semiconductor
- Data Centres
- Aerospace & Defence



MasterCoat
ULTRA DP
heavy duty,
slip resistant system

Heavy duty, textured system with superior chemical and thermal resistance.

- 4–9 mm thickness
- Textured, slip resistant surface
- Excellent chemical and thermal resistance
- High impact and abrasion resistance
- Long term performance in demanding conditions

TEXTURE	THICKNESS
Textured	4 – 9 mm

TYPICAL INDUSTRIES

- Food & Beverage Processing
- Breweries & Distilleries
- Dairies
- Commercial Kitchens



MasterCoat
ULTRA RT
rapid turnaround,
textured system


Rapid curing, textured system designed for fast track projects and high chemical exposure.

- 6–12 mm thickness
- Textured, slip resistant surface
- Fast curing
- Moisture tolerant
- Ideal for shutdowns and rapid projects

TEXTURE	THICKNESS
Textured	6 – 12 mm

TYPICAL INDUSTRIES

- Chemical Processing
- Petrochemical
- Pulp & Paper
- Water & Wastewater



MasterCoat
ULTRA COVE
coved skirting system

Hygienic coved skirting system for seamless transition from floor to wall.

- Coved finish
- Seamless transition floor to wall
- Easy to clean and hygienic
- High chemical resistance
- Compatible with all MasterCoat systems

TEXTURE	THICKNESS
Smooth	4 – 9 mm

TYPICAL INDUSTRIES

- Food & Beverage
- Pharmaceutical
- Healthcare
- Laboratories



Not only
new floors,
but also refurbishment

MasterCoat[®] ULTRA BCR

**Renew your flooring. Maintain its performance.
Like new, in the shortest possible time.**

MasterCoat ULTRA BCR - **B**ase **C**oat **R**efurbishment - is a low-build surface renewal system designed to restore the appearance, texture and original performance of existing **MasterCoat ULTRA** flooring systems.

WHERE AND WHY IS IT USED?



MasterCoat® ULTRA BCR provides a fast and cost-effective solution for refurbishing existing MasterCoat ULTRA flooring, restoring or modifying its original appearance and slip-resistant texture while maintaining MasterCoat ULTRA performance, without the need to replace the entire floor.



Enhances appearance



Increases resistance to wear and abrasion



Extends the service life of the floor



Minimizes disruption to operations

WHY CHOOSE MasterCoat ULTRA BCR?



Fast and efficient

Fast application and rapid return to service.



Maintains performance

Restores the mechanical and thermal resistance of the original flooring system.



Cost-effective solution

Low material consumption and reduced overall cost compared to full replacement.



Sustainable

Reduced waste generation and lower environmental impact.



Like-new finish

Improves appearance, cleanliness and safety of the flooring.



FAST RENEWAL.
PERFORMANCE LIKE DAY ONE.

SYSTEM COMPOSITION

1. EXISTING FLOORING

Existing MasterCoat ULTRA flooring

Mechanical preparation:
shot blasting, diamond grinding, etc.
(Anchor points only at joints and drains, if necessary)

2. REINFORCEMENT LAYER

MasterCoat ULTRA BCR
(2,5 kg/m²)


3. SILICA SAND BROADCAST

Silica Sand
(4 – 5 kg/m² approx.)

4. TOPCOAT

MasterCoat ULTRA DP Topcoat
(0,6 – 0,8 kg/m²)

4. _____
3. _____
2. _____
1. _____



Hygiene and Food Safety

The LBC Red List ensuring our spaces free from harmful materials.

For almost two decades, the International Living Future Institute has been developing the Living Building Challenge (LBC) Red List.

The goal is to ensure the buildings that we work, live and socialise in are safe and free from materials that would be harmful to us and the world around us.

One of the fundamental directives of the LBC is that a truly restorative culture errs on the side of caution and that we simply must remove the following materials from the built environment.

MasterCoat® ULTRA – Free from harmful materials

Common Red List materials for flooring products are antimicrobials (marked with health claims), phthalates such as orthophthalates and volatile organic compounds (VOCs). **MasterCoat® ULTRA** is free from any of those materials.

HACCP food safety management

Hazard Analysis and Critical Control Points (HACCP) is the most internationally recognised food safety management system.

It is a preventive risk assessment tool that takes a careful look at food safety hazards and provides guidelines to guarantee that the facility, its equipment, staff and working processes never constitute a health or hygiene hazard.

All the different MasterCoat ULTRA systems are HACCP International certified, bringing peace of mind to all users that the high-performance polyurethane concrete systems installed in their facilities meet stringent food safety criteria.



MasterCoat[®] ULTRA

Chemical Resistance

Built for demanding industrial environments.

MasterCoat ULTRA polyurethane concrete systems are engineered to withstand the chemical exposure conditions typically found in industrial and hygienic environments.



FOOD & BEVERAGE INDUSTRY



RESISTANT TO:

- Organic acids (e.g. lactic, acetic, citric)
- Sugars and food ingredients
- Fats, oils and animal/vegetable by-products
- Aggressive cleaning and disinfecting agents
- Hot water and steam washdown procedures

BUILT FOR FOOD PROCESSING
ENVIRONMENTS.



CHEMICAL INDUSTRY



DESIGNED TO RESIST:

- Acids (inorganic & organic)
- Alkalis and caustic solutions
- Solvents and aromatic hydrocarbons
- Fuels, lubricants and oils
- Industrial and process chemicals

ENGINEERED FOR SEVERE
CHEMICAL EXPOSURE.



PHARMACEUTICAL INDUSTRY



SUITABLE FOR ENVIRONMENTS
REQUIRING:

- Hygienic, seamless and easy-to-clean surfaces
- Resistance to cleaning and disinfecting agents
- Chemical durability for production processes
- Minimal contamination risk
- Easy decontamination and maintenance

HYGIENIC PERFORMANCE FOR
CONTROLLED ENVIRONMENTS.



LOGISTICS & INDUSTRIAL



EXCELLENT RESISTANCE TO:

- Oils, greases and mineral lubricants
- Cleaning products and detergents
- Heavy traffic and mechanical wear
- Impact and abrasion
- Industrial operational conditions

DURABILITY FOR DAILY
INDUSTRIAL OPERATION.



IMPORTANT NOTE

Chemical resistance performance depends on the chemical type, concentration, temperature, exposure time and housekeeping conditions. This information is intended as a general guide.

Please contact Master Builders Solutions for project-specific recommendations.



SEAMLESS
SOLUTIONS



PROVEN
PERFORMANCE



BUILT
TO LAST




SUSTAINABLE
BY DESIGN

Quick Guide – System Selection

1. RECEIVING/COVERED DOCK:
DRY **MasterCoat ULTRA MF**

2. PROCESSING AREA:
WET **MasterCoat ULTRA DP**
WET **MasterCoat ULTRA RT**
DRY **MasterCoat ULTRA MF**
ATEX/ESD Areas: **MasterCoat ULTRA MF AS**

3. PACKAGING AREA:
DRY **MasterCoat ULTRA MF**
WET **MasterCoat ULTRA DP**



4. FREEZING/COLD STORAGE AREA:
MasterCoat ULTRA DP
MasterCoat ULTRA RT

5. SHIPPING AREA:
DRY **MasterCoat ULTRA MF**
WET **MasterCoat ULTRA DP**
WET **MasterCoat ULTRA RT**



MasterCoat® ULTRA PU Concrete Systems

Technical performance & selection guide

High-performance polyurethane concrete flooring systems engineered for hygiene, durability and demanding environments.

SYSTEM COMPARISON & SELECTION

SYSTEM	THICKNESS*	TYPICAL SERVICE ENVIRONMENT	SERVICE TEMP RANGE
MasterCoat ULTRA SL	2.0 – 3.0 mm	Dry process areas, laboratories, light food prep	 +5°C  +65°C
MasterCoat ULTRA MF	3.0 – 6.0 mm	Medium to heavy-duty food production, dry/wet areas, dairies, beverage processing	 -25°C  +100°C
MasterCoat ULTRA MFAS	3.0 – 4.0 mm	Electronics, pharma, explosive-risk dry process areas, conductive hygienic environments	 -15°C  +70°C
MasterCoat ULTRA DP	4.0 – 9.0 mm	Medium to heavy-duty processing, wet processing, breweries, washdown zones	 -40°C  +120°C
MasterCoat ULTRA RT	6.0 – 12.0 mm	Aggressive washdown, steam-clean, cook lines, abattoirs, severe thermal shock environments	 -45°C  +125°C

*Thickness depends on the mechanical, chemical and thermal requirements




LABORATORIES



FOOD &
BEVERAGE



WET PROCESSING



HEAVY DUTY
AREAS

	THERMAL SHOCK CAPABILITY	SLIP RESISTANCE (INDICATIVE**)	PRIMER / SCRATCH COAT
	Limited	Smooth (approx. R10)	Scratch coat recommended
	Moderate to Very High	Smooth (approx. R10)	Scratch coat recommended
	Moderate to High	Smooth conductive (approx. R10)	Scratch coat recommended
	High to Very High	Defined Profile / Slip Resistant (approx. R11–R13)	Optional
	Very High to Extreme	Heavy Textured / Trowelled (approx. R11–R12)	Optional

** Indicative slip resistance classifications only. Final slip resistance performance will depend on aggregate selection, broadcast density, topcoat application, and the installed surface profile.

Application methodology



SELF-SMOOTHING

Used for smooth finishes in dry and low-slip requirement areas.



BROADCAST DEFINED-PROFILE

Provides slip resistance (R11–R13) via sand or aggregate broadcast.



HEAVY-DUTY TROWEL APPLIED

High-build, textured finishes for extreme thermal shock and aggressive environments.

MasterCoat® ULTRA Systems

Consumption Guide

SYSTEM	PRIMER / SCRATCH COAT	BODYCOAT
MasterCoat ULTRA SL	MasterCoat ULTRA SL (unpigmented): 1.8 kg/m ²	MasterCoat ULTRA SL 2 mm: 1.8 kg/m ² 3 mm: 3.6 kg/m ²
MasterCoat ULTRA MF	MasterCoat ULTRA MF (unpigmented): 1.9 kg/m ²	MasterCoat ULTRA MF 3 mm: 3.8 kg/m ² 4 mm: 5.7 kg/m ² 6 mm: 9.5 kg/m ²
MasterCoat ULTRA MF AS	MasterCoat ULTRA MF (unpigmented): 1.9 kg/m ² + Copper tape + Conductive Primer	MasterCoat ULTRA MF AS 3 mm: 3.8 kg/m ² 4 mm: 5.7 kg/m ²
MasterCoat ULTRA DP	MasterCoat ULTRA Primer 0.5 kg/m ² (Optional)	MasterCoat ULTRA MF (as Basecoat) 4 mm: 5.7 kg/m ² 6 mm: 7.6 kg/m ² 9 mm: 13.3 kg/m ² Broadcast: 3.5 kg/m ² TopCoat: 0.6–0.8 kg/m ²
MasterCoat ULTRA RT	MasterCoat ULTRA Primer 0.5 kg/m ² (Optional)	MasterCoat ULTRA RT 6 mm: 12 kg/m ² 9 mm: 18 kg/m ² 12 mm: 24 kg/m ²



EXTREME TEMPERATURE RESISTANCE

-45°C to +125°C



HIGH CHEMICAL & THERMAL RESISTANCE

Built for aggressive
environments



SLIP-RESISTANT OPTIONS

R10 to R13
profiles available



HYGIENIC & EASY TO CLEAN

Seamless,
impervious and hygienic



FAST INSTALLATION & CURE


Minimise downtime
and disruption



SYSTEMS FOR EVERY APPLICATION

From light-duty
to extreme performance


Colours



Dark Grey



Mid Grey



Light Grey




Yellow



Blue




Red



Green

Anti-slip texture



Global Reach, Continuous Innovation

Evolving Product Research

Through dedicated R&D facilities worldwide, we continually refine our formulations to anticipate industry changes. We adapt to new regulatory compliance frameworks, environmental guidelines, and shifting performance demands.

Next-Generation Solutions

By constantly integrating innovative, cutting edge technologies - from advanced microbial barriers to resilient polymers - MasterCoat® ULTRA remains at the forefront of the global commercial flooring market.

Choosing the Best Solution

Our experts will work with the contractors to specify the best solution according to the specific requirements. We believe in the power of lasting performance and continuous evolution, ensuring your industrial footprint is supported by enduring quality and forward-thinking engineering.

Master Builders Solutions® for the Construction Industry

MasterAir®

Complete solutions for air entrained concrete

MasterCast®

Solutions for the manufactured concrete product industry

MasterCem®

Solutions for cement manufacture

MasterCrete®

Solutions for concrete repair and protection
Solutions for tile fixing and wall systems

MasterCoat®

Solutions for industrial and commercial floors

MasterCO2re®

Solutions for low-clinker concrete

MasterEase®

Low viscosity for high performance concrete

MasterFiber®

Comprehensive solutions for fiber reinforced concrete

MasterFill®

Solutions for concrete injection

MasterFinish®

Solutions for formwork treatment and surface improvement

MasterFlux®

Solutions for precision grouting

MasterGlenium®

Solutions for high performance concrete

MasterJoint®

Solutions for waterproofing and sealing

MasterKure®

Solutions for concrete curing

MasterLife®

Solutions for enhanced durability

MasterRheobuild®

Solutions for high strength concrete

MasterRoc®

Solutions for underground construction

MasterPozzolit®

Solutions for water-reduced concrete

MasterSet®

Solutions for set control

MasterShield®

Solutions for concrete protection

MasterStrength®

Solutions for concrete strengthening

MasterCoat® ULTRA Engineered for the most demanding environments

info.master-builders-solutions.com/mastercoat



Master Builders Solutions Deutschland GmbH

Glücksteinallee 43-45
68163 Mannheim Germany

MBT Teknik Yapı Kimyasalları Sanayi ve Tic. A.Ş. İstanbul Merkez

Eyüp Sultan Mah. Sekmen Cad. HAYY 1000A
No:26 K:5 D:8, 34885
Sancaktepe, İstanbul, Türkiye

Fabrika

Ferizli OSB Mah. 10. Cad. No:2/1 54150 Ferizli, Sakarya

constructionchemicalsinfo@masterbuilders.com

www.master-builders-solutions.com

0 (216) 561 35 45

info@mbt-tech.tr

www.mbt-tech.tr

www.master-builders-solutions.com/tr-tr

The data contained in this publication are based on our current knowledge and experience. They do not constitute the agreed contractual quality of the product and, in view of the many factors that may affect processing and application of our products, do not relieve processors from carrying out their own investigations and tests. The agreed contractual quality of the product at the time of transfer of risk is based solely on the data in the specification data sheet. Any descriptions, drawings, photographs, data, proportions, weights, etc. given in this publication may change without prior information. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed (09/2026).

® registered trademark of Master Builders Solutions in many countries of the world

