

LinuxQMISDK  
SLQS04.00.00

Generated by Doxygen 1.8.6

Tue Jul 12 2016 10:59:49



# Contents

<b>1</b>	<b>Welcome to the Sierra Wireless Linux QMI SDK API Reference Guide</b>	<b>1</b>
1.1	Important Notice . . . . .	1
1.2	Limitation of Liability . . . . .	1
1.3	Patents . . . . .	1
1.4	Copyright . . . . .	2
1.5	Trademarks . . . . .	2
1.6	Contact Information . . . . .	2
<b>2</b>	<b>Module Index</b>	<b>3</b>
2.1	Modules . . . . .	3
<b>3</b>	<b>Namespace Index</b>	<b>5</b>
3.1	Namespace List . . . . .	5
<b>4</b>	<b>Data Structure Index</b>	<b>7</b>
4.1	Data Structures . . . . .	7
<b>5</b>	<b>File Index</b>	<b>27</b>
5.1	File List . . . . .	27
<b>6</b>	<b>Module Documentation</b>	<b>31</b>
6.1	Device Connectivity Service (DCS) . . . . .	31
6.1.1	Detailed Description . . . . .	31
6.2	Wireless Data Service (WDS) . . . . .	32
6.2.1	Detailed Description . . . . .	32
6.3	Device Management Service (DMS) . . . . .	33
6.3.1	Detailed Description . . . . .	33
6.4	Network Access Service (NAS) . . . . .	34
6.4.1	Detailed Description . . . . .	34
6.5	CallBack registration (CBK) . . . . .	35
6.5.1	Detailed Description . . . . .	35
6.6	Short Message Service (SMS) . . . . .	36
6.6.1	Detailed Description . . . . .	36

6.7	Position Determination Service (PDS)	37
6.7.1	Detailed Description	37
6.8	Card Application Toolkit (CAT)	38
6.8.1	Detailed Description	38
6.9	Remote Management Service (RMS)	39
6.9.1	Detailed Description	39
6.10	Firmware Management Service (FMS)	40
6.10.1	Detailed Description	40
6.11	Open Mobile Alliance Service (OMA)	41
6.11.1	Detailed Description	41
6.12	Specific Absorption Rate (SAR)	42
6.12.1	Detailed Description	42
6.13	SWI Open Mobile Alliance Service (SWIOMA)	43
6.13.1	Detailed Description	43
6.14	Voice Service (VOICE)	44
6.14.1	Detailed Description	44
6.15	Non-service specific APIs (SWI)	45
6.15.1	Detailed Description	45
6.16	User Identity Module Service (UIM)	46
6.16.1	Detailed Description	46
6.17	Audio Service (AUDIO)	47
6.17.1	Detailed Description	47
6.18	Quality of Service (QOS)	48
6.18.1	Detailed Description	48
6.19	IMS Service (IMS)	49
6.19.1	Detailed Description	49
6.20	SWI Audio Service(SWIAUDIO)	50
6.20.1	Detailed Description	50
6.21	Location Service(LOC)	51
6.21.1	Detailed Description	51
6.22	Thermal Mitigation Device(TMD)	52
6.22.1	Detailed Description	52
<b>7</b>	<b>Namespace Documentation</b>	<b>53</b>
7.1	Tables Namespace Reference	53
7.1.1	Detailed Description	53
<b>8</b>	<b>Data Structure Documentation</b>	<b>55</b>
8.1	_getIndicationRegResp Struct Reference	55
8.1.1	Detailed Description	55
8.1.2	Field Documentation	56

8.1.2.1	pRegCallStatInfoEvt	56
8.1.2.2	pRegTransLayerInfoEvt	56
8.1.2.3	pRegTransNWRegInfoEvt	56
8.2	_GetProfileSettingIn Struct Reference	56
8.2.1	Detailed Description	56
8.2.2	Field Documentation	57
8.2.2.1	ProfileID	57
8.2.2.2	ProfileType	57
8.3	_GetProfileSettingOut Struct Reference	57
8.3.1	Detailed Description	57
8.3.2	Field Documentation	57
8.3.2.1	curProfile	57
8.3.2.2	pExtErrCode	57
8.4	_getResetInfoNotification Struct Reference	57
8.4.1	Detailed Description	58
8.4.2	Field Documentation	59
8.4.2.1	source	59
8.4.2.2	type	59
8.5	_getTransLayerInfoResp Struct Reference	59
8.5.1	Detailed Description	59
8.5.2	Field Documentation	60
8.5.2.1	pRegInd	60
8.5.2.2	pTransLayerInfo	60
8.6	_getTransNWRegInfoResp Struct Reference	60
8.6.1	Detailed Description	60
8.6.2	Field Documentation	61
8.6.2.1	pRegStatus	61
8.7	_MitigationDevInfo Struct Reference	61
8.7.1	Detailed Description	61
8.7.2	Field Documentation	61
8.7.2.1	deviceId	61
8.7.2.2	deviceIdLen	61
8.8	_modemTempNotification Struct Reference	61
8.8.1	Detailed Description	61
8.8.2	Field Documentation	62
8.8.2.1	ModemTemperature	62
8.8.2.2	ModemTempState	62
8.9	_packetSrvStatus Struct Reference	62
8.9.1	Detailed Description	62
8.9.2	Field Documentation	64

8.9.2.1	bearerID	64
8.9.2.2	connStatus	64
8.9.2.3	ipFamily	64
8.9.2.4	pQmiInterfaceInfo	64
8.9.2.5	reconfigReqd	64
8.9.2.6	sessionEndReason	64
8.9.2.7	techName	64
8.9.2.8	verboseSessnEndReason	64
8.9.2.9	verboseSessnEndReasonType	64
8.10	_qaQmi3GPP2BroadcastCfgInfo Struct Reference	64
8.10.1	Detailed Description	64
8.10.2	Field Documentation	65
8.10.2.1	activated_ind	65
8.10.2.2	CDMABroadcastConfig	65
8.10.2.3	num_instances	65
8.11	_qaQmi3GPPBroadcastCfgInfo Struct Reference	65
8.11.1	Detailed Description	65
8.11.2	Field Documentation	66
8.11.2.1	activated_ind	66
8.11.2.2	broadcastConfig	66
8.11.2.3	num_instances	66
8.12	_setIndicationRegReq Struct Reference	66
8.12.1	Detailed Description	66
8.12.2	Field Documentation	67
8.12.2.1	pRegCallStatInfoEvt	67
8.12.2.2	pRegTransLayerInfoEvt	67
8.12.2.3	pRegTransNWRegInfoEvt	67
8.13	_slqs3GPPConfigItem Struct Reference	67
8.13.1	Detailed Description	67
8.13.2	Field Documentation	69
8.13.2.1	LTEAttachProfileListLen	69
8.13.2.2	p3gppRelease	69
8.13.2.3	pDefaultPDNEnabled	69
8.13.2.4	pLTEAttachProfile	69
8.13.2.5	pLTEAttachProfileList	69
8.13.2.6	pProfileList	69
8.14	_SlqsNas3GppNetworkRAT_ Struct Reference	69
8.14.1	Detailed Description	69
8.14.2	Field Documentation	70
8.14.2.1	MCC	70

8.14.2.2	MNC	70
8.14.2.3	RAT	70
8.15	_slqsNetworkScanInfo Struct Reference	70
8.15.1	Detailed Description	70
8.15.2	Field Documentation	71
8.15.2.1	pNetworkInfo	71
8.15.2.2	pNetworkInfoInstances	71
8.15.2.3	pPCSDigitInfo	71
8.15.2.4	pPCSDigitInstances	71
8.15.2.5	pRATInfo	71
8.15.2.6	pRATInstances	71
8.15.2.7	pScanResult	71
8.16	_SLQSOMADMSessionInfo Struct Reference	72
8.16.1	Detailed Description	72
8.16.2	Field Documentation	74
8.16.2.1	pDate	74
8.16.2.2	pDateLength	74
8.16.2.3	pPkgDescLength	74
8.16.2.4	pPkgDescription	74
8.16.2.5	pPkgName	74
8.16.2.6	pPkgNameLength	74
8.16.2.7	pRetryCount	74
8.16.2.8	pSessionState	74
8.16.2.9	pSessionType	74
8.16.2.10	pSeverity	74
8.16.2.11	pSource	74
8.16.2.12	pSourceLength	74
8.16.2.13	pStatus	74
8.16.2.14	pTime	75
8.16.2.15	pTimeLength	75
8.16.2.16	pUpdateCompleteStatus	75
8.17	_SLQSOMADMSettings Struct Reference	75
8.17.1	Detailed Description	75
8.17.2	Field Documentation	76
8.17.2.1	pAutosdm	76
8.17.2.2	pFOTAdownload	76
8.17.2.3	pFOTAUpdate	76
8.17.2.4	pFwAutoCheck	76
8.17.2.5	pOMADMEEnabled	76
8.18	_SLQSOMADMSettingsReqParams Struct Reference	76

8.18.1 Detailed Description . . . . .	77
8.18.2 Field Documentation . . . . .	77
8.18.2.1 FOTAdownload . . . . .	77
8.18.2.2 FOTAUpdate . . . . .	77
8.18.2.3 pAutosdm . . . . .	77
8.19 _SLQSOMADMSettingsReqParams3 Struct Reference . . . . .	77
8.19.1 Detailed Description . . . . .	78
8.19.2 Field Documentation . . . . .	78
8.19.2.1 FOTAdownload . . . . .	78
8.19.2.2 FOTAUpdate . . . . .	78
8.19.2.3 pAutosdm . . . . .	78
8.19.2.4 pFwAutoCheck . . . . .	78
8.20 _SLQSSwiGetHostDevInfoParams Struct Reference . . . . .	78
8.20.1 Detailed Description . . . . .	79
8.20.2 Field Documentation . . . . .	79
8.20.2.1 bManSize . . . . .	79
8.20.2.2 bModelSize . . . . .	80
8.20.2.3 bPlasmaIDSize . . . . .	80
8.20.2.4 bSWVerSize . . . . .	80
8.20.2.5 pManString . . . . .	80
8.20.2.6 pModelString . . . . .	80
8.20.2.7 pPlasmaIDString . . . . .	80
8.20.2.8 pSWVerString . . . . .	80
8.21 _SLQSSwiGetOSInfoParams Struct Reference . . . . .	80
8.21.1 Detailed Description . . . . .	80
8.21.2 Field Documentation . . . . .	80
8.21.2.1 bNameSize . . . . .	80
8.21.2.2 bVersionSize . . . . .	80
8.21.2.3 pNameString . . . . .	80
8.21.2.4 pVersionString . . . . .	81
8.22 _SLQSSwiGetSerialNoExtParams Struct Reference . . . . .	81
8.22.1 Detailed Description . . . . .	81
8.22.2 Field Documentation . . . . .	81
8.22.2.1 meidLength . . . . .	81
8.22.2.2 pMeidString . . . . .	81
8.23 _SLQSSwiSetHostDevInfoParams Struct Reference . . . . .	81
8.23.1 Detailed Description . . . . .	81
8.23.2 Field Documentation . . . . .	82
8.23.2.1 bManSize . . . . .	82
8.23.2.2 bModelSize . . . . .	82



8.23.2.3	bPlasmaIDSize . . . . .	82
8.23.2.4	bSWVerSize . . . . .	82
8.23.2.5	pManString . . . . .	82
8.23.2.6	pModelString . . . . .	82
8.23.2.7	pPlasmaIDString . . . . .	82
8.23.2.8	pSWVerString . . . . .	82
8.24	_SLQSSwiSetOSInfoParams Struct Reference . . . . .	82
8.24.1	Detailed Description . . . . .	83
8.24.2	Field Documentation . . . . .	83
8.24.2.1	bNameSize . . . . .	83
8.24.2.2	bVersionSize . . . . .	83
8.24.2.3	pNameString . . . . .	83
8.24.2.4	pVersionString . . . . .	83
8.25	_sysSelectPrefInfo Struct Reference . . . . .	83
8.25.1	Detailed Description . . . . .	84
8.25.2	Field Documentation . . . . .	87
8.25.2.1	pBandPref . . . . .	87
8.25.2.2	pEmerMode . . . . .	87
8.25.2.3	pGWAcqOrderPref . . . . .	87
8.25.2.4	pLTEBandPref . . . . .	87
8.25.2.5	pModePref . . . . .	87
8.25.2.6	pNetSelPref . . . . .	87
8.25.2.7	pPRLPref . . . . .	88
8.25.2.8	pRoamPref . . . . .	88
8.25.2.9	pSrvDomainPref . . . . .	88
8.26	_sysSelectPrefParams Struct Reference . . . . .	88
8.26.1	Detailed Description . . . . .	88
8.26.2	Field Documentation . . . . .	93
8.26.2.1	pAcqOrderPref . . . . .	93
8.26.2.2	pBandPref . . . . .	93
8.26.2.3	pChgDuration . . . . .	93
8.26.2.4	pCSGID . . . . .	93
8.26.2.5	pEmerMode . . . . .	93
8.26.2.6	pGWAcqOrderPref . . . . .	93
8.26.2.7	pLTEBandPref . . . . .	93
8.26.2.8	pMNCIncPCSDigStat . . . . .	93
8.26.2.9	pModePref . . . . .	93
8.26.2.10	pNetSelPref . . . . .	93
8.26.2.11	pPRLPref . . . . .	93
8.26.2.12	pRAT . . . . .	93

8.26.2.13 pRoamPref . . . . .	93
8.26.2.14 pSrvDomainPref . . . . .	93
8.26.2.15 pSrvRegRestriction . . . . .	93
8.26.2.16 pTdsdmaBandPref . . . . .	93
8.27 _transLayerinfo Struct Reference . . . . .	93
8.27.1 Detailed Description . . . . .	94
8.27.2 Field Documentation . . . . .	94
8.27.2.1 TransCap . . . . .	94
8.27.2.2 TransType . . . . .	94
8.28 _transLayerInfoNotification Struct Reference . . . . .	94
8.28.1 Detailed Description . . . . .	94
8.28.2 Field Documentation . . . . .	95
8.28.2.1 pTransLayerInfo . . . . .	95
8.28.2.2 regInd . . . . .	95
8.29 _transNWRegInfoNotification Struct Reference . . . . .	95
8.29.1 Detailed Description . . . . .	95
8.29.2 Field Documentation . . . . .	96
8.29.2.1 NWRegStat . . . . .	96
8.30 accelAcceptReady_s Struct Reference . . . . .	96
8.30.1 Detailed Description . . . . .	96
8.30.2 Field Documentation . . . . .	96
8.30.2.1 batchPerSec . . . . .	96
8.30.2.2 injectEnable . . . . .	96
8.30.2.3 samplesPerBatch . . . . .	96
8.31 accelTempAcceptReady_s Struct Reference . . . . .	96
8.31.1 Detailed Description . . . . .	97
8.31.2 Field Documentation . . . . .	97
8.31.2.1 batchPerSec . . . . .	97
8.31.2.2 injectEnable . . . . .	97
8.31.2.3 samplesPerBatch . . . . .	97
8.32 acqOrderPref Struct Reference . . . . .	97
8.32.1 Detailed Description . . . . .	97
8.32.2 Field Documentation . . . . .	98
8.32.2.1 acqOrdeLen . . . . .	98
8.32.2.2 pAcqOrder . . . . .	98
8.33 ActPilotPNElement Struct Reference . . . . .	98
8.33.1 Detailed Description . . . . .	98
8.33.2 Field Documentation . . . . .	98
8.33.2.1 ActSetPilotPN . . . . .	98
8.33.2.2 ActSetPilotPNStrength . . . . .	98

8.34 AddCDMASysInfo Struct Reference . . . . .	98
8.34.1 Detailed Description . . . . .	99
8.34.2 Field Documentation . . . . .	99
8.34.2.1 geoSysIdx . . . . .	99
8.34.2.2 regPrd . . . . .	99
8.35 AddSysInfo Struct Reference . . . . .	99
8.35.1 Detailed Description . . . . .	99
8.35.2 Field Documentation . . . . .	100
8.35.2.1 cellBroadcastCap . . . . .	100
8.35.2.2 geoSysIdx . . . . .	100
8.36 airTimer Struct Reference . . . . .	100
8.36.1 Detailed Description . . . . .	100
8.36.2 Field Documentation . . . . .	100
8.36.2.1 airTimerValue . . . . .	100
8.36.2.2 namID . . . . .	100
8.37 allCallsAlphaIDInfo Struct Reference . . . . .	101
8.37.1 Detailed Description . . . . .	101
8.37.2 Field Documentation . . . . .	101
8.37.2.1 AlphaIDInfo . . . . .	101
8.37.2.2 callID . . . . .	101
8.38 allCallsDiagInfo Struct Reference . . . . .	101
8.38.1 Detailed Description . . . . .	101
8.38.2 Field Documentation . . . . .	101
8.38.2.1 callID . . . . .	101
8.38.2.2 DiagInfo . . . . .	101
8.39 allCallsUUSInfo Struct Reference . . . . .	102
8.39.1 Detailed Description . . . . .	102
8.39.2 Field Documentation . . . . .	102
8.39.2.1 callID . . . . .	102
8.39.2.2 uusInfo . . . . .	102
8.40 alphaIDInfo Struct Reference . . . . .	102
8.40.1 Detailed Description . . . . .	102
8.40.2 Field Documentation . . . . .	103
8.40.2.1 alphaDcs . . . . .	103
8.40.2.2 alphaLen . . . . .	103
8.40.2.3 alphaText . . . . .	103
8.41 altitudeSrcInfo Struct Reference . . . . .	103
8.41.1 Detailed Description . . . . .	103
8.41.2 Field Documentation . . . . .	104
8.41.2.1 coverage . . . . .	104

8.41.2.2	linkage	104
8.41.2.3	source	104
8.42	appStats Struct Reference	104
8.42.1	Detailed Description	105
8.42.2	Field Documentation	108
8.42.2.1	aidLength	108
8.42.2.2	aidVal	108
8.42.2.3	appState	108
8.42.2.4	appType	108
8.42.2.5	persoFeature	108
8.42.2.6	persoRetries	108
8.42.2.7	persoState	108
8.42.2.8	persoUnblockRetries	108
8.42.2.9	pin1Retries	108
8.42.2.10	pin1State	108
8.42.2.11	pin2Retries	108
8.42.2.12	pin2State	108
8.42.2.13	puk1Retries	108
8.42.2.14	puk2Retries	108
8.42.2.15	univPin	108
8.43	appStatus Struct Reference	108
8.43.1	Detailed Description	109
8.43.2	Field Documentation	112
8.43.2.1	aidLength	112
8.43.2.2	aidVal	112
8.43.2.3	appState	112
8.43.2.4	appType	112
8.43.2.5	persoFeature	112
8.43.2.6	persoRetries	112
8.43.2.7	persoState	112
8.43.2.8	persoUnblockRetries	112
8.43.2.9	pin1Retries	112
8.43.2.10	pin1State	112
8.43.2.11	pin2Retries	112
8.43.2.12	pin2State	112
8.43.2.13	puk1Retries	112
8.43.2.14	puk2Retries	112
8.43.2.15	univPin	112
8.44	arrAlertingPattern Struct Reference	112
8.44.1	Detailed Description	112

8.44.2	Field Documentation	113
8.44.2.1	alertingPattern	113
8.44.2.2	callID	113
8.44.2.3	numInstances	113
8.45	arrAlertingType Struct Reference	113
8.45.1	Detailed Description	113
8.45.2	Field Documentation	114
8.45.2.1	AlertingType	114
8.45.2.2	callID	114
8.45.2.3	numInstances	114
8.46	arrAlphaID Struct Reference	114
8.46.1	Detailed Description	114
8.46.2	Field Documentation	114
8.46.2.1	allCallsAlphaIDInfoArr	114
8.46.2.2	numInstances	114
8.47	arrCalledPartyNum Struct Reference	114
8.47.1	Detailed Description	115
8.47.2	Field Documentation	115
8.47.2.1	CalledPartyNum	115
8.47.2.2	numInstances	115
8.48	arrCallEndReason Struct Reference	115
8.48.1	Detailed Description	115
8.48.2	Field Documentation	116
8.48.2.1	callEndReason	116
8.48.2.2	callID	116
8.48.2.3	numInstances	116
8.49	arrCallInfo Struct Reference	116
8.49.1	Detailed Description	116
8.49.2	Field Documentation	116
8.49.2.1	getAllCallInfo	116
8.49.2.2	numInstances	116
8.50	arrConnectPartyNum Struct Reference	116
8.50.1	Detailed Description	117
8.50.2	Field Documentation	117
8.50.2.1	ConnectedPartyNum	117
8.50.2.2	numInstances	117
8.51	arrDiagInfo Struct Reference	117
8.51.1	Detailed Description	117
8.51.2	Field Documentation	117
8.51.2.1	DiagInfo	117

8.51.2.2	numInstances	118
8.52	arrRedirPartyNum Struct Reference	118
8.52.1	Detailed Description	118
8.52.2	Field Documentation	118
8.52.2.1	numInstances	118
8.52.2.2	RedirPartyNum	118
8.53	arrRemotePartyName Struct Reference	118
8.53.1	Detailed Description	118
8.53.2	Field Documentation	119
8.53.2.1	GetAllCallRmtPtyName	119
8.53.2.2	numInstances	119
8.54	arrRemotePartyNum Struct Reference	119
8.54.1	Detailed Description	119
8.54.2	Field Documentation	119
8.54.2.1	numInstances	119
8.54.2.2	RmtPtyNum	119
8.55	arrSvcOption Struct Reference	119
8.55.1	Detailed Description	120
8.55.2	Field Documentation	120
8.55.2.1	callID	120
8.55.2.2	numInstances	120
8.55.2.3	srvOption	120
8.56	arrUUSInfo Struct Reference	120
8.56.1	Detailed Description	120
8.56.2	Field Documentation	121
8.56.2.1	AllCallsUUSInfo	121
8.56.2.2	numInstances	121
8.57	authenticateResult Struct Reference	121
8.57.1	Detailed Description	121
8.57.2	Field Documentation	121
8.57.2.1	content	121
8.57.2.2	contentLen	121
8.58	authenticationData Struct Reference	121
8.58.1	Detailed Description	121
8.58.2	Field Documentation	123
8.58.2.1	context	123
8.58.2.2	data	123
8.58.2.3	dataLen	123
8.59	BandCapabilityResp Struct Reference	123
8.59.1	Detailed Description	123

8.59.2	Field Documentation	125
8.59.2.1	bandCapability	125
8.59.2.2	pLteBandCapability	125
8.59.2.3	pTdsBandCapability	125
8.60	BdsSV Struct Reference	125
8.60.1	Detailed Description	125
8.60.2	Field Documentation	125
8.60.2.1	id	125
8.60.2.2	mask	126
8.61	BdsSVInfo Struct Reference	126
8.61.1	Detailed Description	126
8.61.2	Field Documentation	126
8.61.2.1	len	126
8.61.2.2	pSV	126
8.62	BroadcastConfig Struct Reference	126
8.62.1	Detailed Description	126
8.62.2	Field Documentation	127
8.62.2.1	fromServiceId	127
8.62.2.2	selected	127
8.62.2.3	toServiceId	127
8.63	burstDTMFInfo Struct Reference	127
8.63.1	Detailed Description	127
8.63.2	Field Documentation	128
8.63.2.1	digitCnt	128
8.63.2.2	pCallID	128
8.63.2.3	pDigitBuff	128
8.64	CallBarringSysInfo Struct Reference	128
8.64.1	Detailed Description	128
8.64.2	Field Documentation	129
8.64.2.1	csBarStatus	129
8.64.2.2	psBarStatus	129
8.65	callBarStatus Struct Reference	129
8.65.1	Detailed Description	129
8.65.2	Field Documentation	130
8.65.2.1	csBarStatus	130
8.65.2.2	psBarStatus	130
8.66	calledPartyInfo Struct Reference	130
8.66.1	Detailed Description	130
8.66.2	Field Documentation	132
8.66.2.1	number	132

8.66.2.2	numLen	132
8.66.2.3	numPlan	132
8.66.2.4	numType	132
8.66.2.5	PI	132
8.66.2.6	SI	132
8.67	calledPartySubAdd Struct Reference	132
8.67.1	Detailed Description	132
8.67.2	Field Documentation	133
8.67.2.1	extBit	133
8.67.2.2	oddEvenInd	133
8.67.2.3	subAddr	133
8.67.2.4	subAddrLen	133
8.67.2.5	subAddrType	133
8.68	callerIDInfo Struct Reference	133
8.68.1	Detailed Description	133
8.68.2	Field Documentation	134
8.68.2.1	callerID	134
8.68.2.2	callerIDLen	134
8.68.2.3	PI	134
8.69	callFwdTypeAndPlan Struct Reference	134
8.69.1	Detailed Description	134
8.69.2	Field Documentation	135
8.69.2.1	numberPlan	135
8.69.2.2	numberType	135
8.70	callFWExtInfo Struct Reference	135
8.70.1	Detailed Description	135
8.70.2	Field Documentation	137
8.70.2.1	noReplyTimer	137
8.70.2.2	number	137
8.70.2.3	numLen	137
8.70.2.4	numPlan	137
8.70.2.5	numType	137
8.70.2.6	PI	137
8.70.2.7	SI	137
8.70.2.8	SvcClass	137
8.70.2.9	SvcStatus	137
8.71	callFWInfo Struct Reference	137
8.71.1	Detailed Description	138
8.71.2	Field Documentation	138
8.71.2.1	noReplyTimer	138



8.71.2.2	number	138
8.71.2.3	numLen	138
8.71.2.4	SvcClass	138
8.71.2.5	SvcStatus	138
8.72	callInfo Struct Reference	138
8.72.1	Detailed Description	139
8.72.2	Field Documentation	140
8.72.2.1	callID	140
8.72.2.2	callState	140
8.72.2.3	callType	140
8.72.2.4	direction	140
8.72.2.5	mode	140
8.73	callingPartyInfo Struct Reference	140
8.73.1	Detailed Description	141
8.73.2	Field Documentation	142
8.73.2.1	number	142
8.73.2.2	numLen	142
8.73.2.3	numPlan	142
8.73.2.4	numType	142
8.73.2.5	PI	142
8.73.2.6	SI	142
8.74	cardResult Struct Reference	142
8.74.1	Detailed Description	142
8.74.2	Field Documentation	143
8.74.2.1	sw1	143
8.74.2.2	sw2	143
8.75	cardStatus Struct Reference	143
8.75.1	Detailed Description	143
8.75.2	Field Documentation	144
8.75.2.1	index1xPri	144
8.75.2.2	index1xSec	144
8.75.2.3	indexGwPri	144
8.75.2.4	indexGwSec	144
8.75.2.5	numSlot	144
8.75.2.6	SlotInfo	144
8.76	CarrierImage_t Struct Reference	144
8.76.1	Detailed Description	145
8.76.2	Field Documentation	146
8.76.2.1	m_FwBuildId	146
8.76.2.2	m_FwImageld	146

8.76.2.3	m_nCarrierId	146
8.76.2.4	m_nFolderId	146
8.76.2.5	m_nStorage	146
8.76.2.6	m_PriBuildId	146
8.76.2.7	m_PrImageld	146
8.77	CatAlPhalIdentifierTlv Struct Reference	146
8.77.1	Detailed Description	147
8.77.2	Field Documentation	147
8.77.2.1	AlphaID	147
8.77.2.2	AlphaIDLength	147
8.77.2.3	ReferenceID	147
8.78	CatCommonEventTlv Struct Reference	147
8.78.1	Field Documentation	147
8.78.1.1	CatEvent	147
8.78.1.2	EventID	147
8.78.1.3	EventLength	147
8.78.1.4	TlvPresent	147
8.79	CatEndProactiveSessionTlv Struct Reference	147
8.79.1	Detailed Description	147
8.79.2	Field Documentation	148
8.79.2.1	EndProactiveSession	148
8.80	CATEventDataTlv Struct Reference	148
8.80.1	Field Documentation	148
8.80.1.1	eventMask	148
8.80.1.2	pErrorMask	148
8.81	CatEventIDDDataTlv Struct Reference	148
8.81.1	Detailed Description	148
8.81.2	Field Documentation	148
8.81.2.1	Data	148
8.81.2.2	DataLength	148
8.81.2.3	ReferenceID	148
8.82	CatEventListTlv Struct Reference	148
8.82.1	Detailed Description	149
8.82.2	Field Documentation	149
8.82.2.1	SetupEventList	149
8.83	CatRefreshTlv Struct Reference	149
8.83.1	Detailed Description	149
8.83.2	Field Documentation	149
8.83.2.1	RefreshMode	149
8.83.2.2	RefreshStage	149

8.84	ccSUPSType Struct Reference	149
8.84.1	Detailed Description	150
8.84.2	Field Documentation	150
8.84.2.1	reason	150
8.84.2.2	svcType	150
8.85	CDMABroadcastConfig Struct Reference	150
8.85.1	Detailed Description	150
8.85.2	Field Documentation	151
8.85.2.1	language	151
8.85.2.2	selected	151
8.85.2.3	serviceCategory	151
8.86	CDMAChannel Struct Reference	151
8.86.1	Detailed Description	151
8.86.2	Field Documentation	152
8.86.2.1	priChA	152
8.86.2.2	priChB	152
8.86.2.3	secChA	152
8.86.2.4	secChB	152
8.87	CDMAECIOThresh Struct Reference	152
8.87.1	Detailed Description	152
8.87.2	Field Documentation	153
8.87.2.1	CDMAECIOThreshListLen	153
8.87.2.2	pCDMAECIOThreshList	153
8.88	CDMAInfo Struct Reference	153
8.88.1	Detailed Description	153
8.88.2	Field Documentation	154
8.88.2.1	baseId	154
8.88.2.2	baseLat	154
8.88.2.3	baseLong	154
8.88.2.4	nid	154
8.88.2.5	refpn	154
8.88.2.6	sid	154
8.89	cdmaMsgDecodingParams Struct Reference	154
8.89.1	Detailed Description	155
8.89.2	Field Documentation	156
8.89.2.1	absoluteValidity	156
8.89.2.2	mcTimeStamp	156
8.89.2.3	messageLength	156
8.89.2.4	pAlertPriority	156
8.89.2.5	pCallbkAddr	157

8.89.2.6	<a href="#">pCallbkAddrLength</a>	157
8.89.2.7	<a href="#">pDisplayMode</a>	157
8.89.2.8	<a href="#">pLanguage</a>	157
8.89.2.9	<a href="#">pMessage</a>	157
8.89.2.10	<a href="#">pMessageID</a>	157
8.89.2.11	<a href="#">pPriority</a>	157
8.89.2.12	<a href="#">pPrivacy</a>	157
8.89.2.13	<a href="#">pReadAcknowledgementReq</a>	157
8.89.2.14	<a href="#">pRelativeValidity</a>	157
8.89.2.15	<a href="#">pSenderAddr</a>	157
8.89.2.16	<a href="#">pSenderAddrLength</a>	157
8.89.2.17	<a href="#">pTextMsg</a>	157
8.89.2.18	<a href="#">pTextMsgLength</a>	157
8.89.2.19	<a href="#">pUserAcknowledgementReq</a>	157
8.90	<a href="#">cdmaMsgEncodingParams Struct Reference</a>	157
8.90.1	<a href="#">Detailed Description</a>	157
8.90.2	<a href="#">Field Documentation</a>	158
8.90.2.1	<a href="#">messageld</a>	159
8.90.2.2	<a href="#">pCallbackAddr</a>	159
8.90.2.3	<a href="#">pDestAddr</a>	159
8.90.2.4	<a href="#">pEncodingAlphabet</a>	159
8.90.2.5	<a href="#">pMessage</a>	159
8.90.2.6	<a href="#">pMessageSize</a>	159
8.90.2.7	<a href="#">pPriority</a>	159
8.90.2.8	<a href="#">pRelValidity</a>	159
8.90.2.9	<a href="#">pTextMsg</a>	159
8.90.2.10	<a href="#">textMsgLength</a>	159
8.91	<a href="#">CDMARSSIThresh Struct Reference</a>	159
8.91.1	<a href="#">Detailed Description</a>	159
8.91.2	<a href="#">Field Documentation</a>	159
8.91.2.1	<a href="#">CDMARSSIThreshListLen</a>	159
8.91.2.2	<a href="#">pCDMARSSIThreshList</a>	159
8.92	<a href="#">CDMASSInfo Struct Reference</a>	159
8.92.1	<a href="#">Detailed Description</a>	160
8.92.2	<a href="#">Field Documentation</a>	160
8.92.2.1	<a href="#">ecio</a>	160
8.92.2.2	<a href="#">rssi</a>	160
8.93	<a href="#">cdmaSSInfo Struct Reference</a>	160
8.93.1	<a href="#">Detailed Description</a>	160
8.93.2	<a href="#">Field Documentation</a>	160

8.93.2.1	ecio	160
8.93.2.2	rsi	160
8.94	CDMASysInfo Struct Reference	160
8.94.1	Detailed Description	161
8.94.2	Field Documentation	164
8.94.2.1	baseId	164
8.94.2.2	baseLat	164
8.94.2.3	baseLong	164
8.94.2.4	bsInfoValid	164
8.94.2.5	bsPRev	164
8.94.2.6	bsPRevValid	164
8.94.2.7	ccsSupported	164
8.94.2.8	ccsSupportedValid	164
8.94.2.9	cdmaSysIdValid	164
8.94.2.10	isSysPrIMatch	164
8.94.2.11	isSysPrIMatchValid	164
8.94.2.12	MCC	164
8.94.2.13	MNC	164
8.94.2.14	networkID	164
8.94.2.15	networkIdValid	164
8.94.2.16	packetZone	164
8.94.2.17	packetZoneValid	164
8.94.2.18	pRevInUse	164
8.94.2.19	pRevInUseValid	164
8.94.2.20	sysInfoCDMA	164
8.94.2.21	systemID	164
8.95	CDMASysInfoExt Struct Reference	164
8.95.1	Detailed Description	164
8.95.2	Field Documentation	165
8.95.2.1	imsi_11_12	165
8.95.2.2	MCC	165
8.96	CellIDb Struct Reference	165
8.96.1	Detailed Description	165
8.96.2	Field Documentation	165
8.96.2.1	mask	165
8.97	cellParams Struct Reference	166
8.97.1	Detailed Description	166
8.97.2	Field Documentation	166
8.97.2.1	pci	166
8.97.2.2	rsrp	166

8.97.2.3	rsrq	166
8.97.2.4	rssi	166
8.97.2.5	srxlev	166
8.98	changeUIMPIN Struct Reference	167
8.98.1	Detailed Description	167
8.98.2	Field Documentation	167
8.98.2.1	oldPINLen	167
8.98.2.2	oldPINVal	167
8.98.2.3	pinID	167
8.98.2.4	pinLen	167
8.98.2.5	pinVal	167
8.99	ChannelRate Struct Reference	168
8.99.1	Detailed Description	168
8.99.2	Field Documentation	168
8.99.2.1	CurrChanRxRate	168
8.99.2.2	CurrChanTxRate	168
8.99.2.3	MaxChanRxRate	168
8.99.2.4	MaxChanTxRate	168
8.100	channelRate Struct Reference	168
8.100.1	Detailed Description	168
8.100.2	Field Documentation	169
8.100.2.1	CurrChanRxRate	169
8.100.2.2	CurrChanTxRate	169
8.101	CLIPResp Struct Reference	169
8.101.1	Detailed Description	169
8.101.2	Field Documentation	169
8.101.2.1	ActiveStatus	169
8.101.2.2	ProvisionStatus	170
8.102	CLIRResp Struct Reference	170
8.102.1	Detailed Description	170
8.102.2	Field Documentation	170
8.102.2.1	ActiveStatus	170
8.102.2.2	ProvisionStatus	170
8.103	CIkInfo Struct Reference	170
8.103.1	Detailed Description	171
8.103.2	Field Documentation	172
8.103.2.1	mask	173
8.104	CNAPResp Struct Reference	173
8.104.1	Detailed Description	173
8.104.2	Field Documentation	173

8.104.2.1	ActiveStatus	173
8.104.2.2	ProvisionStatus	173
8.105	COLPResp Struct Reference	173
8.105.1	Detailed Description	173
8.105.2	Field Documentation	174
8.105.2.1	ActiveStatus	174
8.105.2.2	ProvisionStatus	174
8.106	COLRResp Struct Reference	174
8.106.1	Detailed Description	174
8.106.2	Field Documentation	175
8.106.2.1	ActiveStatus	175
8.106.2.2	ProvisionStatus	175
8.107	CommInfo Struct Reference	175
8.107.1	Detailed Description	175
8.107.2	Field Documentation	177
8.107.2.1	imsRegState	177
8.107.2.2	modemMode	177
8.107.2.3	psState	177
8.107.2.4	systemMode	177
8.107.2.5	temperature	177
8.108	ConnectionStatus Struct Reference	177
8.108.1	Detailed Description	177
8.108.2	Field Documentation	178
8.108.2.1	MDMCallDuration	178
8.108.2.2	MDMConnStatus	178
8.109	connectionStatus Struct Reference	178
8.109.1	Detailed Description	178
8.109.2	Field Documentation	178
8.109.2.1	MDMCallDuration	178
8.109.2.2	MDMConnStatus	178
8.110	connectNumInfo Struct Reference	178
8.110.1	Detailed Description	179
8.110.2	Field Documentation	181
8.110.2.1	callerID	181
8.110.2.2	callerIDLen	181
8.110.2.3	numPlan	181
8.110.2.4	numPresInd	181
8.110.2.5	numType	181
8.110.2.6	screeningInd	181
8.111	CrashInfo Struct Reference	181

8.111.1 Detailed Description	181
8.111.2 Field Documentation	182
8.111.2.1 crashData	182
8.111.2.2 crashId	182
8.111.2.3 crashStrLen	182
8.111.2.4 gcDumpStrLen	182
8.111.2.5 numCrashes	182
8.111.2.6 pCrashString	182
8.111.2.7 pGCDumpString	182
8.112 CrashInfoParams Struct Reference	182
8.112.1 Detailed Description	182
8.112.2 Field Documentation	183
8.112.2.1 pCrashInfo	183
8.112.2.2 pDevCrashStatus	183
8.113 CreateProfileIn Struct Reference	183
8.113.1 Detailed Description	183
8.113.2 Field Documentation	183
8.113.2.1 curProfile	183
8.113.2.2 pProfileID	184
8.113.2.3 pProfileType	184
8.114 CreateProfileOut Struct Reference	184
8.114.1 Detailed Description	184
8.114.2 Field Documentation	184
8.114.2.1 pExtErrorCode	184
8.114.2.2 pProfileIndex	184
8.114.2.3 pProfileType	184
8.115 CSGID Struct Reference	184
8.115.1 Detailed Description	184
8.115.2 Field Documentation	185
8.115.2.1 id	185
8.115.2.2 mcc	185
8.115.2.3 mnc	185
8.115.2.4 mncPcsDigits	185
8.115.2.5 rat	185
8.116 CUGInfo Struct Reference	185
8.116.1 Detailed Description	185
8.116.2 Field Documentation	186
8.116.2.1 CUGIndex	186
8.116.2.2 SuppOA	186
8.116.2.3 SuppPrefCUG	186



8.117curAMRConfig Struct Reference	186
8.117.1 Detailed Description	186
8.117.2 Field Documentation	187
8.117.2.1 gsmAmrStat	187
8.117.2.2 wcdmaAmrStat	187
8.118CurrDataSysStat Struct Reference	187
8.118.1 Detailed Description	187
8.118.2 Field Documentation	188
8.118.2.1 pCurrNetworkInfo	188
8.118.2.2 pNetworkInfoLen	188
8.118.2.3 pPrefNetwork	188
8.119currentCatEvent Union Reference	188
8.119.1 Detailed Description	188
8.119.2 Field Documentation	189
8.119.2.1 CatAlphaldtfr	189
8.119.2.2 CatEndPS	189
8.119.2.3 CatEventLst	189
8.119.2.4 CatEvIDData	189
8.119.2.5 CatRefresh	189
8.120CurrentImglList Struct Reference	189
8.120.1 Detailed Description	189
8.120.2 Field Documentation	189
8.120.2.1 carrier	189
8.120.2.2 fwvers	190
8.120.2.3 numEntries	190
8.120.2.4 pCurrImglInfo	190
8.120.2.5 pkgver	190
8.120.2.6 priver	190
8.121currentPLMN Struct Reference	190
8.121.1 Detailed Description	190
8.121.2 Field Documentation	190
8.121.2.1 MCC	191
8.121.2.2 MNC	191
8.121.2.3 netDescr	191
8.121.2.4 netDescrLength	191
8.122CurrImageInfo Struct Reference	191
8.122.1 Detailed Description	191
8.122.2 Field Documentation	191
8.122.2.1 buildID	191
8.122.2.2 buildIDLen	191

8.122.2.3 imageType . . . . .	191
8.122.2.4 uniqueID . . . . .	191
8.123CurrNetworkInfo Struct Reference . . . . .	192
8.123.1 Detailed Description . . . . .	192
8.123.2 Field Documentation . . . . .	194
8.123.2.1 NetworkType . . . . .	194
8.123.2.2 RATMask . . . . .	194
8.123.2.3 SOMask . . . . .	194
8.124currNetworkInfo Struct Reference . . . . .	194
8.124.1 Detailed Description . . . . .	194
8.124.2 Field Documentation . . . . .	194
8.124.2.1 NetworkType . . . . .	194
8.124.2.2 RATMask . . . . .	194
8.124.2.3 SOMask . . . . .	194
8.125custFeaturesInfo Struct Reference . . . . .	194
8.125.1 Detailed Description . . . . .	194
8.125.2 Field Documentation . . . . .	197
8.125.2.1 GpsEnable . . . . .	197
8.125.2.2 pDHCPRelayEnabled . . . . .	197
8.125.2.3 pDisableIMSI . . . . .	197
8.125.2.4 pGPSLPM . . . . .	197
8.125.2.5 pGPSSel . . . . .	197
8.125.2.6 pIPFamSupport . . . . .	197
8.125.2.7 plsVoiceEnabled . . . . .	197
8.125.2.8 pRMAutoConnect . . . . .	197
8.125.2.9 pSMSSupport . . . . .	197
8.126custFeaturesSetting Struct Reference . . . . .	197
8.126.1 Detailed Description . . . . .	198
8.126.2 Field Documentation . . . . .	199
8.126.2.1 pDHCPRelayEnabled . . . . .	199
8.126.2.2 pGPSEnable . . . . .	199
8.126.2.3 pGPSLPM . . . . .	199
8.126.2.4 pGPSSel . . . . .	199
8.126.2.5 plsVoiceEnabled . . . . .	199
8.127custSettingInfo Struct Reference . . . . .	199
8.127.1 Detailed Description . . . . .	200
8.127.2 Field Documentation . . . . .	200
8.127.2.1 cust_attr . . . . .	200
8.127.2.2 cust_id . . . . .	200
8.127.2.3 cust_value . . . . .	200

8.127.2.4 id_length . . . . .	200
8.127.2.5 value_length . . . . .	200
8.128custSettingList Struct Reference . . . . .	200
8.128.1 Detailed Description . . . . .	201
8.128.2 Field Documentation . . . . .	202
8.128.2.1 custSetting . . . . .	202
8.128.2.2 list_type . . . . .	202
8.128.2.3 num_instances . . . . .	202
8.129dataBearers Struct Reference . . . . .	202
8.129.1 Detailed Description . . . . .	202
8.129.2 Field Documentation . . . . .	203
8.129.2.1 dataBearerMask . . . . .	203
8.129.2.2 pCurDataBearerTechnology . . . . .	203
8.129.2.3 pLastCallDataBearerTechnology . . . . .	203
8.130DataBearerTech Struct Reference . . . . .	203
8.130.1 Detailed Description . . . . .	203
8.130.2 Field Documentation . . . . .	205
8.130.2.1 ratValue . . . . .	205
8.130.2.2 soMask . . . . .	205
8.130.2.3 techType . . . . .	205
8.131DataBearerTechExt Struct Reference . . . . .	205
8.131.1 Detailed Description . . . . .	205
8.131.2 Field Documentation . . . . .	205
8.131.2.1 pBearerTech . . . . .	205
8.131.2.2 pLastBearerTech . . . . .	205
8.132dataBearerTechnology Struct Reference . . . . .	205
8.132.1 Detailed Description . . . . .	205
8.132.2 Field Documentation . . . . .	207
8.132.2.1 currentNetwork . . . . .	207
8.132.2.2 ratMask . . . . .	207
8.132.2.3 soMask . . . . .	207
8.133dataRate Struct Reference . . . . .	207
8.133.1 Detailed Description . . . . .	207
8.133.2 Field Documentation . . . . .	207
8.133.2.1 dataRateMax . . . . .	207
8.133.2.2 guaranteedRate . . . . .	207
8.134dataSrvCapabilities Struct Reference . . . . .	207
8.134.1 Detailed Description . . . . .	208
8.134.2 Field Documentation . . . . .	208
8.134.2.1 dataCapabilities . . . . .	208

8.134.2.2 dataCapabilitiesLen . . . . .	208
8.135DataStatusDetail Struct Reference . . . . .	208
8.135.1 Detailed Description . . . . .	208
8.135.2 Field Documentation . . . . .	210
8.135.2.1 IPAddress . . . . .	210
8.135.2.2 LastErrCode . . . . .	210
8.136DataULongLongTlv Struct Reference . . . . .	210
8.136.1 Field Documentation . . . . .	210
8.136.1.1 TlvPresent . . . . .	210
8.136.1.2 ullData . . . . .	210
8.137DataULongTlv Struct Reference . . . . .	210
8.137.1 Field Documentation . . . . .	210
8.137.1.1 TlvPresent . . . . .	210
8.137.1.2 ulData . . . . .	210
8.138DcsUsbPortNames Struct Reference . . . . .	210
8.138.1 Field Documentation . . . . .	210
8.138.1.1 AtCmdPort . . . . .	210
8.138.1.2 DmPort . . . . .	210
8.138.1.3 NmeaPort . . . . .	210
8.139delAssistDataStatus Struct Reference . . . . .	210
8.139.1 Detailed Description . . . . .	211
8.139.2 Field Documentation . . . . .	211
8.139.2.1 status . . . . .	211
8.140depersonalizationInformation Struct Reference . . . . .	211
8.140.1 Detailed Description . . . . .	212
8.140.2 Field Documentation . . . . .	213
8.140.2.1 ckLen . . . . .	213
8.140.2.2 ckVal . . . . .	213
8.140.2.3 feature . . . . .	213
8.140.2.4 operation . . . . .	213
8.141detailSvcInfo Struct Reference . . . . .	213
8.141.1 Detailed Description . . . . .	214
8.141.2 Field Documentation . . . . .	215
8.141.2.1 hdrHybrid . . . . .	215
8.141.2.2 hdrSrvStatus . . . . .	215
8.141.2.3 isSysForbidden . . . . .	215
8.141.2.4 srvCapability . . . . .	215
8.141.2.5 srvStatus . . . . .	215
8.142DeviceConfigDetail Struct Reference . . . . .	215
8.142.1 Detailed Description . . . . .	215

8.142.2 Field Documentation . . . . .	216
8.142.2.1 Chipset . . . . .	216
8.142.2.2 HWVersion . . . . .	216
8.142.2.3 QLIC . . . . .	216
8.142.2.4 Technology . . . . .	216
8.143DHCPOption Struct Reference . . . . .	216
8.143.1 Detailed Description . . . . .	217
8.143.2 Field Documentation . . . . .	217
8.143.2.1 optCode . . . . .	217
8.143.2.2 optValLen . . . . .	217
8.143.2.3 pOptVal . . . . .	217
8.144DHCPOptionList Struct Reference . . . . .	217
8.144.1 Detailed Description . . . . .	217
8.144.2 Field Documentation . . . . .	218
8.144.2.1 numOpt . . . . .	218
8.144.2.2 pOptions . . . . .	218
8.145diagInfo Struct Reference . . . . .	218
8.145.1 Detailed Description . . . . .	218
8.145.2 Field Documentation . . . . .	218
8.145.2.1 diagInfoLen . . . . .	218
8.145.2.2 diagnosticInfo . . . . .	218
8.146dirNum Struct Reference . . . . .	218
8.146.1 Detailed Description . . . . .	219
8.146.2 Field Documentation . . . . .	219
8.146.2.1 dirNum . . . . .	219
8.146.2.2 dirNumLen . . . . .	219
8.147dms_ActivationStatusTlv Struct Reference . . . . .	219
8.147.1 Detailed Description . . . . .	219
8.147.2 Field Documentation . . . . .	220
8.147.2.1 activationStatus . . . . .	220
8.147.2.2 TlvPresent . . . . .	220
8.148dms_OperatingModeTlv Struct Reference . . . . .	220
8.148.1 Detailed Description . . . . .	220
8.148.2 Field Documentation . . . . .	221
8.148.2.1 operatingMode . . . . .	221
8.148.2.2 TlvPresent . . . . .	221
8.149dmsCurrentPRLInfo Struct Reference . . . . .	221
8.149.1 Detailed Description . . . . .	221
8.149.2 Field Documentation . . . . .	221
8.149.2.1 pPRLPreference . . . . .	221

8.149.2.2 pPRLVersion . . . . .	221
8.150DMScustSettingInfo Struct Reference . . . . .	221
8.150.1 Detailed Description . . . . .	221
8.150.2 Field Documentation . . . . .	222
8.150.2.1 cust_attr . . . . .	222
8.150.2.2 cust_id . . . . .	222
8.150.2.3 cust_value . . . . .	222
8.150.2.4 id_length . . . . .	222
8.150.2.5 value_length . . . . .	222
8.151DMScustSettingList Struct Reference . . . . .	222
8.151.1 Detailed Description . . . . .	222
8.151.2 Field Documentation . . . . .	223
8.151.2.1 custSetting . . . . .	223
8.151.2.2 list_type . . . . .	223
8.151.2.3 num_instances . . . . .	223
8.152DMSgetCustomFeatureV2 Struct Reference . . . . .	223
8.152.1 Detailed Description . . . . .	223
8.152.2 Field Documentation . . . . .	223
8.152.2.1 pCustSettingInfo . . . . .	223
8.152.2.2 pCustSettingList . . . . .	223
8.152.2.3 pGetCustomInput . . . . .	223
8.153DMSgetCustomInput Struct Reference . . . . .	224
8.153.1 Detailed Description . . . . .	224
8.153.2 Field Documentation . . . . .	224
8.153.2.1 cust_id . . . . .	224
8.153.2.2 list_type . . . . .	224
8.154dmsIndicationRegisterReq Struct Reference . . . . .	224
8.154.1 Detailed Description . . . . .	224
8.154.2 Field Documentation . . . . .	224
8.154.2.1 pSwiGetResetInd . . . . .	225
8.155dmsSwiGetResetInfo Struct Reference . . . . .	225
8.155.1 Detailed Description . . . . .	225
8.155.2 Field Documentation . . . . .	225
8.155.2.1 source . . . . .	225
8.155.2.2 type . . . . .	225
8.156Domain Struct Reference . . . . .	225
8.156.1 Detailed Description . . . . .	226
8.156.2 Field Documentation . . . . .	226
8.156.2.1 domainLen . . . . .	226
8.156.2.2 domainName . . . . .	226

8.157DomainNameList Struct Reference . . . . .	226
8.157.1 Detailed Description . . . . .	226
8.157.2 Field Documentation . . . . .	226
8.157.2.1 domain . . . . .	226
8.157.2.2 numInstances . . . . .	226
8.158DRCPParams Struct Reference . . . . .	226
8.158.1 Detailed Description . . . . .	227
8.158.2 Field Documentation . . . . .	228
8.158.2.1 DRCCover . . . . .	228
8.158.2.2 DRCValue . . . . .	228
8.159DTMFInfo Struct Reference . . . . .	228
8.159.1 Detailed Description . . . . .	228
8.159.2 Field Documentation . . . . .	229
8.159.2.1 callID . . . . .	229
8.159.2.2 digitBuff . . . . .	229
8.159.2.3 digitCnt . . . . .	229
8.159.2.4 DTMFEvent . . . . .	229
8.160DTMFLengths Struct Reference . . . . .	229
8.160.1 Detailed Description . . . . .	229
8.160.2 Field Documentation . . . . .	229
8.160.2.1 DTMFInterdigitInterval . . . . .	229
8.160.2.2 DTMFPulseWidth . . . . .	229
8.161DUNCallInfoInd Struct Reference . . . . .	229
8.161.1 Field Documentation . . . . .	230
8.161.1.1 CallEndReason . . . . .	230
8.161.1.2 ChannelRate . . . . .	230
8.161.1.3 DataBearerTech . . . . .	230
8.161.1.4 DormancyStatus . . . . .	230
8.161.1.5 MdmConnStatus . . . . .	230
8.161.1.6 RXOKBytesCount . . . . .	230
8.161.1.7 TXOKBytesCount . . . . .	230
8.162dunchannelRate Struct Reference . . . . .	230
8.162.1 Detailed Description . . . . .	230
8.162.2 Field Documentation . . . . .	230
8.162.2.1 CurrChanRxRate . . . . .	230
8.162.2.2 CurrChanTxRate . . . . .	230
8.162.2.3 MaxChanRxRate . . . . .	230
8.162.2.4 MaxChanTxRate . . . . .	231
8.163ecioListElement Struct Reference . . . . .	231
8.163.1 Detailed Description . . . . .	231

8.163.2 Field Documentation . . . . .	231
8.163.2.1 ecio . . . . .	231
8.163.2.2 radiolf . . . . .	231
8.164ECIOTresh Struct Reference . . . . .	231
8.164.1 Detailed Description . . . . .	231
8.164.2 Field Documentation . . . . .	232
8.164.2.1 ECIOThresListLen . . . . .	232
8.164.2.2 pECIOThresList . . . . .	232
8.165ECTNum Struct Reference . . . . .	232
8.165.1 Detailed Description . . . . .	232
8.165.2 Field Documentation . . . . .	233
8.165.2.1 ECTCallState . . . . .	233
8.165.2.2 number . . . . .	233
8.165.2.3 presentationInd . . . . .	233
8.166encryptedPIN1 Struct Reference . . . . .	233
8.166.1 Detailed Description . . . . .	233
8.166.2 Field Documentation . . . . .	234
8.166.2.1 pin1Len . . . . .	234
8.166.2.2 pin1Val . . . . .	234
8.167ERFileparams Struct Reference . . . . .	234
8.167.1 Detailed Description . . . . .	234
8.167.2 Field Documentation . . . . .	234
8.167.2.1 pFile . . . . .	234
8.167.2.2 pFileSize . . . . .	234
8.168errorRateListElement Struct Reference . . . . .	234
8.168.1 Detailed Description . . . . .	234
8.168.2 Field Documentation . . . . .	236
8.168.2.1 errorRate . . . . .	236
8.168.2.2 radiolf . . . . .	236
8.169eTWSPLMNInfoTlv Struct Reference . . . . .	236
8.169.1 Detailed Description . . . . .	236
8.169.2 Field Documentation . . . . .	236
8.169.2.1 ETWSPLMNInfo . . . . .	236
8.169.2.2 TlvPresent . . . . .	236
8.170extDispRecInfo Struct Reference . . . . .	236
8.170.1 Detailed Description . . . . .	237
8.170.2 Field Documentation . . . . .	237
8.170.2.1 dispType . . . . .	237
8.170.2.2 extDispInfo . . . . .	237
8.170.2.3 extDispInfoLen . . . . .	237



8.171 FactorySequenceNumber Struct Reference . . . . .	237
8.171.1 Detailed Description . . . . .	237
8.171.2 Field Documentation . . . . .	237
8.171.2.1 FSNumber . . . . .	237
8.172 fileAttributes Struct Reference . . . . .	237
8.172.1 Detailed Description . . . . .	238
8.172.2 Field Documentation . . . . .	241
8.172.2.1 fileID . . . . .	241
8.172.2.2 fileSize . . . . .	241
8.172.2.3 fileType . . . . .	241
8.172.2.4 rawLen . . . . .	241
8.172.2.5 rawValue . . . . .	241
8.172.2.6 recordCount . . . . .	241
8.172.2.7 recordSize . . . . .	241
8.172.2.8 secActivate . . . . .	241
8.172.2.9 secActivateMask . . . . .	241
8.172.2.10 secDeactivate . . . . .	241
8.172.2.11 secDeactivateMask . . . . .	241
8.172.2.12 secIncrease . . . . .	241
8.172.2.13 secIncreaseMask . . . . .	242
8.172.2.14 secRead . . . . .	242
8.172.2.15 secReadMask . . . . .	242
8.172.2.16 secWrite . . . . .	242
8.172.2.17 secWriteMask . . . . .	242
8.173 fileInfo Struct Reference . . . . .	242
8.173.1 Detailed Description . . . . .	242
8.173.2 Field Documentation . . . . .	242
8.173.2.1 fileID . . . . .	242
8.173.2.2 path . . . . .	242
8.173.2.3 pathLen . . . . .	242
8.174 FirmwareUpdatStat Struct Reference . . . . .	242
8.174.1 Detailed Description . . . . .	243
8.174.2 Field Documentation . . . . .	244
8.174.2.1 plmgType . . . . .	244
8.174.2.2 pLogString . . . . .	244
8.174.2.3 pLogStringLen . . . . .	244
8.174.2.4 pRefData . . . . .	244
8.174.2.5 pRefString . . . . .	244
8.174.2.6 pRefStringLen . . . . .	244
8.174.2.7 ResCode . . . . .	244

8.175FMSImageElement Struct Reference . . . . .	244
8.175.1 Detailed Description . . . . .	244
8.175.2 Field Documentation . . . . .	245
8.175.2.1 buildId . . . . .	245
8.175.2.2 buildIdLength . . . . .	245
8.175.2.3 imageId . . . . .	245
8.175.2.4 imageType . . . . .	245
8.176FMSImageIdElement Struct Reference . . . . .	245
8.176.1 Detailed Description . . . . .	245
8.176.2 Field Documentation . . . . .	246
8.176.2.1 buildID . . . . .	246
8.176.2.2 buildIDLength . . . . .	246
8.176.2.3 failureCount . . . . .	246
8.176.2.4 imageID . . . . .	246
8.176.2.5 storageIndex . . . . .	246
8.177FMSImageIDEntries Struct Reference . . . . .	246
8.177.1 Detailed Description . . . . .	246
8.177.2 Field Documentation . . . . .	247
8.177.2.1 executingImage . . . . .	247
8.177.2.2 imageIDElement . . . . .	247
8.177.2.3 imageIDSize . . . . .	247
8.177.2.4 imageType . . . . .	247
8.177.2.5 maxImages . . . . .	247
8.178FMSImageList Struct Reference . . . . .	247
8.178.1 Detailed Description . . . . .	247
8.178.2 Field Documentation . . . . .	247
8.178.2.1 imageIDEntries . . . . .	247
8.178.2.2 listSize . . . . .	247
8.179FMSPrefImageList Struct Reference . . . . .	248
8.179.1 Detailed Description . . . . .	248
8.179.2 Field Documentation . . . . .	248
8.179.2.1 listEntries . . . . .	248
8.179.2.2 listSize . . . . .	248
8.180fwinfo_s Struct Reference . . . . .	248
8.180.1 Detailed Description . . . . .	248
8.180.2 Field Documentation . . . . .	249
8.180.2.1 Carrier . . . . .	249
8.180.2.2 FirmwareID . . . . .	249
8.180.2.3 GPSCapability . . . . .	249
8.180.2.4 Region . . . . .	249

8.180.2.5 Technology	249
8.181 GERANInfo Struct Reference	249
8.181.1 Detailed Description	249
8.181.2 Field Documentation	251
8.181.2.1 arfcn	251
8.181.2.2 bsic	251
8.181.2.3 cellID	251
8.181.2.4 insNmrCellInfo	251
8.181.2.5 lac	251
8.181.2.6 nmrlnst	251
8.181.2.7 plmn	251
8.181.2.8 rxLev	251
8.181.2.9 timingAdvance	251
8.182 geranInstInfo Struct Reference	251
8.182.1 Detailed Description	251
8.182.2 Field Documentation	252
8.182.2.1 geranArfcn	252
8.182.2.2 geranBsicBcc	252
8.182.2.3 geranBsicNcc	252
8.182.2.4 geranRssi	252
8.183 getAllCallInformation Struct Reference	252
8.183.1 Detailed Description	252
8.183.2 Field Documentation	253
8.183.2.1 ALS	253
8.183.2.2 Callinfo	253
8.183.2.3 isEmpty	253
8.184 getAllCallRmtPtyName Struct Reference	253
8.184.1 Detailed Description	253
8.184.2 Field Documentation	253
8.184.2.1 callID	253
8.184.2.2 RemotePartyName	253
8.185 getAllCallRmtPtyNum Struct Reference	253
8.185.1 Detailed Description	253
8.185.2 Field Documentation	254
8.185.2.1 callID	254
8.185.2.2 RemotePartyNum	254
8.186 GetAudioPathConfigReq Struct Reference	254
8.186.1 Detailed Description	254
8.186.2 Field Documentation	254
8.186.2.1 Item	255

8.186.2.2 Profile . . . . .	255
8.187GetAudioPathConfigResp Struct Reference . . . . .	255
8.187.1 Detailed Description . . . . .	255
8.187.2 Field Documentation . . . . .	256
8.187.2.1 pCodecSTGain . . . . .	256
8.187.2.2 pDTMFTXGain . . . . .	256
8.187.2.3 pECMode . . . . .	256
8.187.2.4 pMICGainSelect . . . . .	256
8.187.2.5 pNSEnable . . . . .	257
8.187.2.6 pRXAGCList . . . . .	257
8.187.2.7 pRXAVCAGCSwitch . . . . .	257
8.187.2.8 pRXAVCList . . . . .	257
8.187.2.9 pRXPCMIIRFitr . . . . .	257
8.187.2.10pTXAGCList . . . . .	257
8.187.2.11pTXAVCSwitch . . . . .	257
8.187.2.12pTXGain . . . . .	257
8.187.2.13pTXPCMIIRFitr . . . . .	257
8.188GetAudioProfileReq Struct Reference . . . . .	257
8.188.1 Detailed Description . . . . .	257
8.188.2 Field Documentation . . . . .	257
8.188.2.1 Generator . . . . .	257
8.189GetAudioProfileResp Struct Reference . . . . .	257
8.189.1 Detailed Description . . . . .	258
8.189.2 Field Documentation . . . . .	259
8.189.2.1 EarMute . . . . .	259
8.189.2.2 MicMute . . . . .	259
8.189.2.3 Profile . . . . .	259
8.189.2.4 Volume . . . . .	259
8.190GetAudioVoTLBConfigReq Struct Reference . . . . .	259
8.190.1 Detailed Description . . . . .	260
8.190.2 Field Documentation . . . . .	260
8.190.2.1 Generator . . . . .	260
8.190.2.2 Item . . . . .	260
8.190.2.3 Profile . . . . .	260
8.190.2.4 Volume . . . . .	260
8.191GetAudioVoTLBConfigResp Struct Reference . . . . .	260
8.191.1 Detailed Description . . . . .	260
8.191.2 Field Documentation . . . . .	261
8.191.2.1 ResCode . . . . .	261
8.192getCallFWExtInfo Struct Reference . . . . .	261

8.192.1 Detailed Description	261
8.192.2 Field Documentation	261
8.192.2.1 CallFWExtInfo	261
8.192.2.2 numInstances	261
8.193getCallFWInfo Struct Reference	261
8.193.1 Detailed Description	261
8.193.2 Field Documentation	262
8.193.2.1 CallFWInfo	262
8.193.2.2 numInstances	262
8.194getCustomFeatureV2 Struct Reference	262
8.194.1 Detailed Description	262
8.194.2 Field Documentation	262
8.194.2.1 pCustSettingInfo	262
8.194.2.2 pCustSettingList	263
8.194.2.3 pGetCustomInput	263
8.195getCustomInput Struct Reference	263
8.195.1 Detailed Description	263
8.195.2 Field Documentation	263
8.195.2.1 cust_id	263
8.195.2.2 list_type	263
8.196getDUNCallInfoReq Struct Reference	263
8.196.1 Detailed Description	263
8.196.2 Field Documentation	264
8.196.2.1 Mask	265
8.196.2.2 pReportChannelRate	265
8.196.2.3 pReportConnStatus	265
8.196.2.4 pReportDataBearerTech	265
8.196.2.5 pReportDormStatus	265
8.196.2.6 pTransferStatInd	265
8.197getDUNCallInfoResp Struct Reference	265
8.197.1 Detailed Description	265
8.197.2 Field Documentation	268
8.197.2.1 pCallEndReason	268
8.197.2.2 pChannelRate	268
8.197.2.3 pConnectionStatus	268
8.197.2.4 pDataBearerTech	268
8.197.2.5 pDormancyStatus	268
8.197.2.6 pLastCallDataBearerTech	268
8.197.2.7 pLastCallRXOKBytesCnt	268
8.197.2.8 pLastCallTXOKBytesCnt	268

8.197.2.9 pMdmCallDurationActive . . . . .	268
8.197.2.10pRXOKBytesCount . . . . .	268
8.197.2.11pTXOKBytesCount . . . . .	268
8.198getDyingGaspCfg Struct Reference . . . . .	268
8.198.1 Detailed Description . . . . .	268
8.198.2 Field Documentation . . . . .	268
8.198.2.1 pDestSMSContent . . . . .	268
8.198.2.2 pDestSMSNum . . . . .	268
8.199getDyingGaspStatistics Struct Reference . . . . .	269
8.199.1 Detailed Description . . . . .	269
8.199.2 Field Documentation . . . . .	269
8.199.2.1 pSMSAttemptedFlag . . . . .	269
8.199.2.2 pTimeStamp . . . . .	269
8.200GetErrRateResp Struct Reference . . . . .	269
8.200.1 Detailed Description . . . . .	269
8.200.2 Field Documentation . . . . .	270
8.200.2.1 pCDMAFrameErrRate . . . . .	270
8.200.2.2 pGSMBER . . . . .	270
8.200.2.3 pHDRPackErrRate . . . . .	270
8.200.2.4 pWCDMABER . . . . .	270
8.201GetHRPDStatsResp Struct Reference . . . . .	270
8.201.1 Detailed Description . . . . .	270
8.201.2 Field Documentation . . . . .	271
8.201.2.1 pDRCPParams . . . . .	271
8.201.2.2 pPilotSetData . . . . .	271
8.201.2.3 pUATI . . . . .	271
8.202GetIMSSMSConfigParams Struct Reference . . . . .	271
8.202.1 Detailed Description . . . . .	271
8.202.2 Field Documentation . . . . .	272
8.202.2.1 pPhoneCtxtURI . . . . .	272
8.202.2.2 pPhoneCtxtURILen . . . . .	272
8.202.2.3 pSettingResp . . . . .	272
8.202.2.4 pSMSFormat . . . . .	272
8.202.2.5 pSMSOverIPNwInd . . . . .	272
8.203GetIMSUserConfigParams Struct Reference . . . . .	272
8.203.1 Detailed Description . . . . .	272
8.203.2 Field Documentation . . . . .	273
8.203.2.1 pIMSDomain . . . . .	273
8.203.2.2 pIMSDomainLen . . . . .	273
8.203.2.3 pSettingResp . . . . .	273

8.204GetIMSVoIPConfigResp Struct Reference	273
8.204.1 Detailed Description	273
8.204.2 Field Documentation	275
8.204.2.1 pAmrMode	275
8.204.2.2 pAmrOctetAligned	275
8.204.2.3 pAmrWbEnable	275
8.204.2.4 pAmrWBMode	275
8.204.2.5 pAmrWBOctetAligned	275
8.204.2.6 pMinSessionExpiryTimer	275
8.204.2.7 pRingBackTimer	275
8.204.2.8 pRingingTimer	275
8.204.2.9 pRTPRTCPInactTimer	275
8.204.2.10pScrAmrEnable	275
8.204.2.11pScrAmrWbEnable	275
8.204.2.12pSessionExpiryTimer	275
8.204.2.13pSettingResp	275
8.205GetInstIDResp Struct Reference	275
8.205.1 Field Documentation	275
8.205.1.1 pInstanceID	275
8.205.1.2 pIPFamily	275
8.206GetM2MAudioProfileReq Struct Reference	275
8.206.1 Detailed Description	275
8.206.2 Field Documentation	276
8.206.2.1 pGenerator	276
8.207GetM2MAudioProfileResp Struct Reference	276
8.207.1 Detailed Description	276
8.207.2 Field Documentation	277
8.207.2.1 CwtMute	277
8.207.2.2 EarMute	277
8.207.2.3 Generator	277
8.207.2.4 MicMute	277
8.207.2.5 Profile	277
8.207.2.6 Volume	277
8.208GetM2MAudioVolumeReq Struct Reference	277
8.208.1 Detailed Description	277
8.208.2 Field Documentation	278
8.208.2.1 Generator	278
8.208.2.2 Profile	278
8.209GetM2MAudioVolumeResp Struct Reference	278
8.209.1 Detailed Description	278

8.209.2 Field Documentation . . . . .	278
8.209.2.1 Level . . . . .	278
8.210GetM2MAVMuteReq Struct Reference . . . . .	278
8.210.1 Detailed Description . . . . .	278
8.210.2 Field Documentation . . . . .	279
8.210.2.1 Profile . . . . .	279
8.211GetM2MAVMuteResp Struct Reference . . . . .	279
8.211.1 Detailed Description . . . . .	279
8.211.2 Field Documentation . . . . .	279
8.211.2.1 CwtMute . . . . .	279
8.211.2.2 EarMute . . . . .	279
8.211.2.3 MicMute . . . . .	279
8.212GetM2MSpkrGainReq Struct Reference . . . . .	280
8.212.1 Detailed Description . . . . .	280
8.212.2 Field Documentation . . . . .	280
8.212.2.1 Profile . . . . .	280
8.213GetM2MSpkrGainResp Struct Reference . . . . .	280
8.213.1 Detailed Description . . . . .	280
8.213.2 Field Documentation . . . . .	280
8.213.2.1 Value . . . . .	280
8.214getMsgWaitingInfo Struct Reference . . . . .	280
8.214.1 Detailed Description . . . . .	281
8.214.2 Field Documentation . . . . .	282
8.214.2.1 msgWaitInfo . . . . .	282
8.214.2.2 numInstances . . . . .	282
8.215GetNetworkTimeResp Struct Reference . . . . .	282
8.215.1 Detailed Description . . . . .	282
8.215.2 Field Documentation . . . . .	282
8.215.2.1 p3GPP2TimeInfo . . . . .	282
8.215.2.2 p3GPPTimeInfo . . . . .	282
8.216GetRegMgrConfigParams Struct Reference . . . . .	282
8.216.1 Detailed Description . . . . .	283
8.216.2 Field Documentation . . . . .	283
8.216.2.1 pIMSTestMode . . . . .	283
8.216.2.2 pPCSCFPort . . . . .	283
8.216.2.3 pPriCSCFPortName . . . . .	283
8.216.2.4 pPriCSCFPortNameLen . . . . .	283
8.216.2.5 pSettingResp . . . . .	283
8.217GetSessionIDResp Struct Reference . . . . .	283
8.217.1 Field Documentation . . . . .	283



8.217.1.1 pSessionIDv4 . . . . .	283
8.217.1.2 pSessionIDv6 . . . . .	284
8.218GetSIPConfigResp Struct Reference . . . . .	284
8.218.1 Detailed Description . . . . .	284
8.218.2 Field Documentation . . . . .	284
8.218.2.1 pSettingResp . . . . .	285
8.218.2.2 pSigCompEnabled . . . . .	285
8.218.2.3 pSIPLocalPort . . . . .	285
8.218.2.4 pSubscribeTimer . . . . .	285
8.218.2.5 pTimerSIPReg . . . . .	285
8.218.2.6 pTimerT1 . . . . .	285
8.218.2.7 pTimerT2 . . . . .	285
8.218.2.8 pTimerTf . . . . .	285
8.219GnssData Struct Reference . . . . .	285
8.219.1 Detailed Description . . . . .	285
8.219.2 Field Documentation . . . . .	287
8.219.2.1 mask . . . . .	287
8.220gnssSvInfoNotification Struct Reference . . . . .	287
8.220.1 Detailed Description . . . . .	287
8.220.2 Field Documentation . . . . .	287
8.220.2.1 bAltitudeAssumed . . . . .	287
8.220.2.2 pSatelliteInfo . . . . .	287
8.221GPRSQoS Struct Reference . . . . .	287
8.221.1 Detailed Description . . . . .	287
8.221.2 Field Documentation . . . . .	288
8.221.2.1 delayClass . . . . .	288
8.221.2.2 meanThroughputClass . . . . .	288
8.221.2.3 peakThroughputClass . . . . .	288
8.221.2.4 precedenceClass . . . . .	288
8.221.2.5 reliabilityClass . . . . .	288
8.222GPRSRequestedQoS Struct Reference . . . . .	288
8.222.1 Detailed Description . . . . .	288
8.222.2 Field Documentation . . . . .	289
8.222.2.1 delayClass . . . . .	289
8.222.2.2 meanThroughputClass . . . . .	289
8.222.2.3 peakThroughputClass . . . . .	289
8.222.2.4 precedenceClass . . . . .	289
8.222.2.5 reliabilityClass . . . . .	289
8.223GPSSStateInfo Struct Reference . . . . .	289
8.223.1 Detailed Description . . . . .	290

8.223.2 Field Documentation . . . . .	292
8.223.2.1 Altitude . . . . .	292
8.223.2.2 EngineState . . . . .	293
8.223.2.3 glo_almanac_sv_msk . . . . .	293
8.223.2.4 glo_ephemeris_sv_msk . . . . .	293
8.223.2.5 glo_health_sv_msk . . . . .	293
8.223.2.6 glo_visible_sv_msk . . . . .	293
8.223.2.7 gps_almanac_sv_msk . . . . .	293
8.223.2.8 gps_ephemeris_sv_msk . . . . .	293
8.223.2.9 gps_health_sv_msk . . . . .	293
8.223.2.10gps_visible_sv_msk . . . . .	293
8.223.2.11HorizontalUncertainty . . . . .	293
8.223.2.12iono_valid . . . . .	293
8.223.2.13Latitude . . . . .	293
8.223.2.14Longitude . . . . .	293
8.223.2.15sbas_almanac_sv_msk . . . . .	293
8.223.2.16sbas_ephemeris_sv_msk . . . . .	293
8.223.2.17sbas_health_sv_msk . . . . .	293
8.223.2.18sbas_visible_sv_msk . . . . .	293
8.223.2.19Time_uncert_ms . . . . .	293
8.223.2.20TimeStmp_gps_week . . . . .	293
8.223.2.21TimeStmp_tow_ms . . . . .	293
8.223.2.22ValidMask . . . . .	293
8.223.2.23VerticalUncertainty . . . . .	293
8.223.2.24xtra_start_gps_minutes . . . . .	293
8.223.2.25xtra_start_gps_week . . . . .	293
8.223.2.26xtra_valid_duration_hours . . . . .	293
8.224gpsTime_s Struct Reference . . . . .	293
8.224.1 Detailed Description . . . . .	294
8.224.2 Field Documentation . . . . .	294
8.224.2.1 gpsTimeOfWeekMs . . . . .	294
8.224.2.2 gpsWeek . . . . .	294
8.225gsmCellInfo Struct Reference . . . . .	294
8.225.1 Detailed Description . . . . .	294
8.225.2 Field Documentation . . . . .	295
8.225.2.1 arfcn . . . . .	295
8.225.2.2 band1900 . . . . .	295
8.225.2.3 bsicld . . . . .	295
8.225.2.4 cellldValid . . . . .	295
8.225.2.5 rssi . . . . .	295

8.225.2.6 srxlev . . . . .	295
8.226GSMRSSIThresh Struct Reference . . . . .	295
8.226.1 Detailed Description . . . . .	295
8.226.2 Field Documentation . . . . .	296
8.226.2.1 GSMRSSIThreshListLen . . . . .	296
8.226.2.2 pGSMRSSIThreshList . . . . .	296
8.227GSMSrvStatusInfo Struct Reference . . . . .	296
8.227.1 Detailed Description . . . . .	296
8.227.2 Field Documentation . . . . .	297
8.227.2.1 isPrefDataPath . . . . .	297
8.227.2.2 srvStatus . . . . .	297
8.227.2.3 trueSrvStatus . . . . .	297
8.228GSMSysInfo Struct Reference . . . . .	297
8.228.1 Detailed Description . . . . .	297
8.228.2 Field Documentation . . . . .	300
8.228.2.1 cellId . . . . .	300
8.228.2.2 cellIdValid . . . . .	300
8.228.2.3 dtmSupp . . . . .	300
8.228.2.4 dtmSuppValid . . . . .	300
8.228.2.5 egprsSupp . . . . .	300
8.228.2.6 egprsSuppValid . . . . .	300
8.228.2.7 lac . . . . .	300
8.228.2.8 lacValid . . . . .	300
8.228.2.9 MCC . . . . .	300
8.228.2.10MNC . . . . .	300
8.228.2.11networkIdValid . . . . .	300
8.228.2.12regRejectInfoValid . . . . .	300
8.228.2.13rejCause . . . . .	300
8.228.2.14rejectSrvDomain . . . . .	300
8.228.2.15sysInfoGSM . . . . .	300
8.229gyroAcceptReady_s Struct Reference . . . . .	300
8.229.1 Detailed Description . . . . .	300
8.229.2 Field Documentation . . . . .	301
8.229.2.1 batchPerSec . . . . .	301
8.229.2.2 injectEnable . . . . .	301
8.229.2.3 samplesPerBatch . . . . .	301
8.230gyroTempAcceptReady_s Struct Reference . . . . .	301
8.230.1 Detailed Description . . . . .	301
8.230.2 Field Documentation . . . . .	302
8.230.2.1 batchPerSec . . . . .	302

8.230.2.2 injectEnable . . . . .	302
8.230.2.3 samplesPerBatch . . . . .	302
8.231 HDRECIOThresh Struct Reference . . . . .	302
8.231.1 Detailed Description . . . . .	302
8.231.2 Field Documentation . . . . .	303
8.231.2.1 HDRECIOThreshListLen . . . . .	303
8.231.2.2 pHRECIOThreshList . . . . .	303
8.232 HDRIOTThresh Struct Reference . . . . .	303
8.232.1 Detailed Description . . . . .	303
8.232.2 Field Documentation . . . . .	303
8.232.2.1 HDRIOTThreshListLen . . . . .	303
8.232.2.2 pHDRIOThreshList . . . . .	303
8.233 HDRPersonalityInd Struct Reference . . . . .	303
8.233.1 Field Documentation . . . . .	303
8.233.1.1 pCurrentPersonality . . . . .	303
8.233.1.2 pPersonalityListLength . . . . .	303
8.233.1.3 pProtocolSubtypeElement . . . . .	303
8.234 HDRPersonalityResp Struct Reference . . . . .	304
8.234.1 Detailed Description . . . . .	304
8.234.2 Field Documentation . . . . .	304
8.234.2.1 pCurrentPersonality . . . . .	304
8.234.2.2 pPersonalityListLength . . . . .	304
8.234.2.3 pProtocolSubtypeElement . . . . .	304
8.235 HDRProtSubtypResp Struct Reference . . . . .	304
8.235.1 Detailed Description . . . . .	304
8.235.2 Field Documentation . . . . .	305
8.235.2.1 pAppSubType . . . . .	305
8.235.2.2 pCurrentPrsnlty . . . . .	305
8.235.2.3 pPersonalityListLength . . . . .	305
8.235.2.4 pProtoSubTypElmnt . . . . .	305
8.236 HDRRSSIThresh Struct Reference . . . . .	305
8.236.1 Detailed Description . . . . .	305
8.236.2 Field Documentation . . . . .	305
8.236.2.1 HDRRSSIThreshListLen . . . . .	305
8.236.2.2 pHDRRSSIThreshList . . . . .	305
8.237 HDRSINRThresh Struct Reference . . . . .	306
8.237.1 Detailed Description . . . . .	306
8.237.2 Field Documentation . . . . .	306
8.237.2.1 HDRSINRThresListLen . . . . .	306
8.237.2.2 pHDRSINRThresList . . . . .	306

8.238HDRSINRThreshold Struct Reference	306
8.238.1 Detailed Description	306
8.238.2 Field Documentation	307
8.238.2.1 HDRSINRThreshListLen	307
8.238.2.2 pHDRSINRThreshList	307
8.239HDRSSInfo Struct Reference	307
8.239.1 Detailed Description	307
8.239.2 Field Documentation	308
8.239.2.1 ecio	308
8.239.2.2 io	308
8.239.2.3 rssi	308
8.239.2.4 sinr	308
8.240hdrSSInfo Struct Reference	308
8.240.1 Detailed Description	308
8.240.2 Field Documentation	309
8.240.2.1 ecio	309
8.240.2.2 io	309
8.240.2.3 rssi	309
8.240.2.4 sinr	309
8.241HDRSysInfo Struct Reference	309
8.241.1 Detailed Description	309
8.241.2 Field Documentation	311
8.241.2.1 hdrActiveProt	311
8.241.2.2 hdrActiveProtValid	311
8.241.2.3 hdrPersonality	311
8.241.2.4 hdrPersonalityValid	311
8.241.2.5 is856SysId	311
8.241.2.6 is856SysIdValid	311
8.241.2.7 isSysPrIMatch	311
8.241.2.8 isSysPrIMatchValid	311
8.241.2.9 sysInfoHDR	311
8.242homeSIDNID Struct Reference	311
8.242.1 Detailed Description	311
8.242.2 Field Documentation	312
8.242.2.1 numInstances	312
8.242.2.2 SidNid	312
8.243hotSwapStatus Struct Reference	312
8.243.1 Detailed Description	312
8.243.2 Field Documentation	312
8.243.2.1 hotSwap	312

8.243.2.2 hotSwapLength . . . . .	312
8.244image_info_t Struct Reference . . . . .	313
8.244.1 Field Documentation . . . . .	313
8.244.1.1 buildID . . . . .	313
8.244.1.2 buildIDLen . . . . .	313
8.244.1.3 imageType . . . . .	313
8.244.1.4 uniqueID . . . . .	313
8.245ImageElement Struct Reference . . . . .	313
8.245.1 Detailed Description . . . . .	313
8.245.2 Field Documentation . . . . .	313
8.245.2.1 buildId . . . . .	313
8.245.2.2 buildIdLength . . . . .	314
8.245.2.3 imageId . . . . .	314
8.245.2.4 imageType . . . . .	314
8.246ImageIdElement Struct Reference . . . . .	314
8.246.1 Detailed Description . . . . .	314
8.246.2 Field Documentation . . . . .	314
8.246.2.1 buildID . . . . .	314
8.246.2.2 buildIDLength . . . . .	314
8.246.2.3 failureCount . . . . .	314
8.246.2.4 imageID . . . . .	314
8.246.2.5 storageIndex . . . . .	314
8.247ImageIDEntries Struct Reference . . . . .	315
8.247.1 Detailed Description . . . . .	315
8.247.2 Field Documentation . . . . .	315
8.247.2.1 executingImage . . . . .	315
8.247.2.2 imageIDElement . . . . .	315
8.247.2.3 imageIDSize . . . . .	315
8.247.2.4 imageType . . . . .	315
8.247.2.5 maxImages . . . . .	315
8.248ImageList Struct Reference . . . . .	315
8.248.1 Detailed Description . . . . .	316
8.248.2 Field Documentation . . . . .	316
8.248.2.1 imageIDEntries . . . . .	316
8.248.2.2 listSize . . . . .	316
8.249IMSAIndRegisterInfo Struct Reference . . . . .	316
8.249.1 Detailed Description . . . . .	316
8.249.2 Field Documentation . . . . .	317
8.249.2.1 pPdpStatusConfig . . . . .	317
8.249.2.2 pRatHandoverStatusConfig . . . . .	317

8.249.2.3 pRegStatusConfig . . . . .	317
8.249.2.4 pServiceStatusConfig . . . . .	317
8.250imsaPdpStatusInfo Struct Reference . . . . .	317
8.250.1 Detailed Description . . . . .	318
8.250.2 Field Documentation . . . . .	318
8.250.2.1 connetionState . . . . .	318
8.250.2.2 pFailErrorCode . . . . .	318
8.251imsaRatStatusInfo Struct Reference . . . . .	318
8.251.1 Detailed Description . . . . .	318
8.251.2 Field Documentation . . . . .	319
8.251.2.1 pErrorCodeStr . . . . .	319
8.251.2.2 pRATStatus . . . . .	319
8.251.2.3 pSrcRAT . . . . .	319
8.251.2.4 pTgtRAT . . . . .	319
8.252IMSARegistrationStatus Struct Reference . . . . .	319
8.252.1 Detailed Description . . . . .	319
8.252.2 Field Documentation . . . . .	320
8.252.2.1 plmsRegErrCode . . . . .	320
8.252.2.2 plmsRegStatus . . . . .	320
8.252.2.3 pNewlmsRegStatus . . . . .	320
8.253imsaRegStatusInfo Struct Reference . . . . .	320
8.253.1 Detailed Description . . . . .	320
8.253.2 Field Documentation . . . . .	321
8.253.2.1 pbIMSRegistered . . . . .	321
8.253.2.2 plmsRegStatus . . . . .	321
8.253.2.3 pRegStatusErrorCode . . . . .	321
8.254IMSAServiceStatus Struct Reference . . . . .	321
8.254.1 Detailed Description . . . . .	321
8.254.2 Field Documentation . . . . .	323
8.254.2.1 pSmsServiceRat . . . . .	323
8.254.2.2 pSmsServiceStatus . . . . .	323
8.254.2.3 pUtServiceRat . . . . .	323
8.254.2.4 pUtServiceStatus . . . . .	323
8.254.2.5 pVoipServiceRat . . . . .	323
8.254.2.6 pVoipServiceStatus . . . . .	323
8.254.2.7 pVsServiceRat . . . . .	323
8.254.2.8 pVsServiceStatus . . . . .	323
8.254.2.9 pVtServiceRat . . . . .	324
8.254.2.10pVtServiceStatus . . . . .	324
8.255IMSASupportedFieldsResp Struct Reference . . . . .	324

8.255.1 Detailed Description . . . . .	324
8.255.2 Field Documentation . . . . .	324
8.255.2.1 pIndFieldsList . . . . .	324
8.255.2.2 pReqFieldsList . . . . .	324
8.255.2.3 pRespFieldsList . . . . .	324
8.256IMSASupportedMsgInfo Struct Reference . . . . .	324
8.256.1 Detailed Description . . . . .	324
8.256.2 Field Documentation . . . . .	325
8.256.2.1 pSupportedMsgList . . . . .	325
8.257imsaSvcStatusInfo Struct Reference . . . . .	325
8.257.1 Detailed Description . . . . .	325
8.257.2 Field Documentation . . . . .	325
8.257.2.1 pSMSSvcRAT . . . . .	325
8.257.2.2 pSMSSvcStatus . . . . .	325
8.257.2.3 pUTSvcRAT . . . . .	325
8.257.2.4 pUTSvcStatus . . . . .	325
8.257.2.5 pVOIPSvcRAT . . . . .	326
8.257.2.6 pVOIPSvcStatus . . . . .	326
8.257.2.7 pVTSvcRAT . . . . .	326
8.257.2.8 pVTSvcStatus . . . . .	326
8.258imsCfgIndRegisterInfo Struct Reference . . . . .	326
8.258.1 Detailed Description . . . . .	326
8.258.2 Field Documentation . . . . .	327
8.258.2.1 pRegMgrConfigEvents . . . . .	327
8.258.2.2 pSIPConfigEvents . . . . .	327
8.258.2.3 pSMSConfigEvents . . . . .	327
8.258.2.4 pUserConfigEvents . . . . .	327
8.258.2.5 pVoIPConfigEvents . . . . .	327
8.259imsRegMgrConfigInfo Struct Reference . . . . .	327
8.259.1 Detailed Description . . . . .	328
8.259.2 Field Documentation . . . . .	329
8.259.2.1 pCSCFPortName . . . . .	329
8.259.2.2 pIMSTestMode . . . . .	329
8.259.2.3 pPriCSCFPort . . . . .	329
8.260imsSIPConfigInfo Struct Reference . . . . .	329
8.260.1 Detailed Description . . . . .	329
8.260.2 Field Documentation . . . . .	330
8.260.2.1 pSigCompEnabled . . . . .	330
8.260.2.2 pSIPLocalPort . . . . .	330
8.260.2.3 pSubscribeTimer . . . . .	330



8.260.2.4 pTimerSIPReg . . . . .	330
8.260.2.5 pTimerT1 . . . . .	330
8.260.2.6 pTimerT2 . . . . .	330
8.260.2.7 pTimerTf . . . . .	330
8.261imsSMSConfigInfo Struct Reference . . . . .	330
8.261.1 Detailed Description . . . . .	330
8.261.2 Field Documentation . . . . .	331
8.261.2.1 pPhoneCtxtURI . . . . .	331
8.261.2.2 pSMSFormat . . . . .	331
8.261.2.3 pSMSOverIPNwInd . . . . .	331
8.262imsUserConfigInfo Struct Reference . . . . .	331
8.262.1 Detailed Description . . . . .	331
8.262.2 Field Documentation . . . . .	331
8.262.2.1 pIMSDomain . . . . .	331
8.263imsVoIPConfigInfo Struct Reference . . . . .	331
8.263.1 Detailed Description . . . . .	332
8.263.2 Field Documentation . . . . .	334
8.263.2.1 pAmrMode . . . . .	334
8.263.2.2 pAmrOctetAligned . . . . .	334
8.263.2.3 pAmrWbEnable . . . . .	334
8.263.2.4 pAmrWBMode . . . . .	334
8.263.2.5 pAmrWBOctetAligned . . . . .	334
8.263.2.6 pMinSessionExpiryTimer . . . . .	334
8.263.2.7 pRingBackTimer . . . . .	334
8.263.2.8 pRingingTimer . . . . .	334
8.263.2.9 pRTPRTCPInactTimer . . . . .	334
8.263.2.10pScrAmrEnable . . . . .	334
8.263.2.11pScrAmrWbEnable . . . . .	334
8.263.2.12pSessionExpiryTimer . . . . .	334
8.264IndFieldsList Struct Reference . . . . .	334
8.264.1 Detailed Description . . . . .	334
8.264.2 Field Documentation . . . . .	335
8.264.2.1 indicationFields . . . . .	335
8.264.2.2 indicationFieldsLen . . . . .	335
8.265infoInterFreq Struct Reference . . . . .	335
8.265.1 Detailed Description . . . . .	335
8.265.2 Field Documentation . . . . .	336
8.265.2.1 cell_resel_priority . . . . .	336
8.265.2.2 cellInterFreqParams . . . . .	336
8.265.2.3 cells_len . . . . .	336

8.265.2.4 earfcn . . . . .	336
8.265.2.5 threshXHigh . . . . .	336
8.265.2.6 threshXLow . . . . .	336
8.266IOThresh Struct Reference . . . . .	336
8.266.1 Detailed Description . . . . .	336
8.266.2 Field Documentation . . . . .	337
8.266.2.1 IOThresListLen . . . . .	337
8.266.2.2 pIOThresList . . . . .	337
8.267IPv4Addr Struct Reference . . . . .	337
8.267.1 Detailed Description . . . . .	337
8.267.2 Field Documentation . . . . .	337
8.267.2.1 addr . . . . .	337
8.267.2.2 subnetMask . . . . .	337
8.268IPv6Addr Struct Reference . . . . .	337
8.268.1 Detailed Description . . . . .	338
8.268.2 Field Documentation . . . . .	339
8.268.2.1 addr . . . . .	339
8.268.2.2 prefixLen . . . . .	339
8.269IPv6AddressInfo Struct Reference . . . . .	339
8.269.1 Detailed Description . . . . .	339
8.269.2 Field Documentation . . . . .	339
8.269.2.1 IPAddressV6 . . . . .	339
8.269.2.2 IPV6PrefixLen . . . . .	339
8.270ipv6AddressInfo Struct Reference . . . . .	339
8.270.1 Detailed Description . . . . .	339
8.270.2 Field Documentation . . . . .	340
8.270.2.1 IPAddressV6 . . . . .	340
8.270.2.2 IPV6PrefixLen . . . . .	340
8.271IPv6GWAddressInfo Struct Reference . . . . .	340
8.271.1 Detailed Description . . . . .	340
8.271.2 Field Documentation . . . . .	340
8.271.2.1 gwAddressV6 . . . . .	340
8.271.2.2 gwV6PrefixLen . . . . .	340
8.272IPv6TrafCls Struct Reference . . . . .	340
8.272.1 Detailed Description . . . . .	340
8.272.2 Field Documentation . . . . .	341
8.272.2.1 mask . . . . .	341
8.272.2.2 val . . . . .	341
8.273LibPackGPRSRequestedQoS Struct Reference . . . . .	341
8.273.1 Detailed Description . . . . .	341

8.273.2 Field Documentation	342
8.273.2.1 delayClass	342
8.273.2.2 meanThroughputClass	342
8.273.2.3 peakThroughputClass	342
8.273.2.4 precedenceClass	342
8.273.2.5 reliabilityClass	342
8.274 LibpackProfile3GPP Struct Reference	342
8.274.1 Detailed Description	343
8.274.2 Field Documentation	348
8.274.2.1 pAddrAllocPref	348
8.274.2.2 pAPNClass	348
8.274.2.3 pAPNDisabledFlag	348
8.274.2.4 pAPNName	348
8.274.2.5 pAPNnameSize	348
8.274.2.6 pAuthenticationPref	348
8.274.2.7 pGPRSMinimumQoS	348
8.274.2.8 pGPRSRequestedQos	348
8.274.2.9 plmCnFlag	348
8.274.2.10 pIPv4AddrPref	348
8.274.2.11 pIPv6AddPref	348
8.274.2.12 pPassword	348
8.274.2.13 pPasswordSize	348
8.274.2.14 pPcscfAddrUsingDhcp	348
8.274.2.15 pPcscfAddrUsingPCO	348
8.274.2.16 pPDNInactivTimeout	348
8.274.2.17 pPdpAccessConFlag	348
8.274.2.18 pPdpContext	349
8.274.2.19 pPdpDataCompType	349
8.274.2.20 pPdpHdrCompType	349
8.274.2.21 pPDType	349
8.274.2.22 pPriDNSIPv4AddPref	349
8.274.2.23 pPriDNSIPv6addpref	349
8.274.2.24 pPrimaryID	349
8.274.2.25 pProfileName	349
8.274.2.26 pProfileNameSize	349
8.274.2.27 pQosClassID	349
8.274.2.28 pSecDNSIPv4AddPref	349
8.274.2.29 pSecDNSIPv6addpref	349
8.274.2.30 pSecondaryFlag	349
8.274.2.31 pTFTID1Params	349

8.274.2.32	pTFTID2Params	349
8.274.2.33	pUMTSMinQoS	349
8.274.2.34	pUMTSMinQoSSigInd	349
8.274.2.35	pUMTSReqQoS	349
8.274.2.36	pUMTSReqQoSSigInd	349
8.274.2.37	pUsername	349
8.274.2.38	pUsernameSize	349
8.275	LibpackProfile3GPP2 Struct Reference	349
8.275.1	Detailed Description	350
8.275.2	Field Documentation	354
8.275.2.1	pAllowLinger	354
8.275.2.2	pAPNClass3GPP2	354
8.275.2.3	pAPNEnabled3GPP2	354
8.275.2.4	pApnString	354
8.275.2.5	pApnStringSize	354
8.275.2.6	pAppPriority	354
8.275.2.7	pAppType	354
8.275.2.8	pAuthPassword	354
8.275.2.9	pAuthPasswordSize	354
8.275.2.10	pAuthProtocol	354
8.275.2.11	pAuthRetryCount	354
8.275.2.12	pAuthTimeout	355
8.275.2.13	pDataMode	355
8.275.2.14	pDataRate	355
8.275.2.15	pIpcpAckTimeout	355
8.275.2.16	pIpcpCreqRetryCount	355
8.275.2.17	pIsPcscfAddressNedded	355
8.275.2.18	pLcpAckTimeout	355
8.275.2.19	pLcpCreqRetryCount	355
8.275.2.20	pNegoDnsSrvrPref	355
8.275.2.21	pPDNInactivTimeout3GPP2	355
8.275.2.22	pPdnType	355
8.275.2.23	pPppSessCloseTimer1x	355
8.275.2.24	pPppSessCloseTimerDO	355
8.275.2.25	pPrimaryV4DnsAddress	355
8.275.2.26	pPriV6DnsAddress	355
8.275.2.27	pRATType	355
8.275.2.28	pSecondaryV4DnsAddress	355
8.275.2.29	pSecV6DnsAddress	355
8.275.2.30	pUserId	355

8.275.2.31p	UserIdSize	355
8.276	LibPackprofile_3GPP Struct Reference	355
8.276.1	Detailed Description	356
8.276.2	Field Documentation	361
8.276.2.1	pAddrAllocPref	361
8.276.2.2	pAPNClass	361
8.276.2.3	pAPNDisabledFlag	361
8.276.2.4	pAPNName	361
8.276.2.5	pAPNnameSize	361
8.276.2.6	pAuthenticationPref	361
8.276.2.7	pGPRSMinimumQoS	361
8.276.2.8	pGPRSRequestedQos	361
8.276.2.9	plmCnFlag	361
8.276.2.10	pIPv4AddrPref	361
8.276.2.11	pIPv6AddPref	361
8.276.2.12	pPassword	361
8.276.2.13	pPasswordSize	361
8.276.2.14	pPcscfAddrUsingDhcp	361
8.276.2.15	pPcscfAddrUsingPCO	361
8.276.2.16	pPDNInactivTimeout	361
8.276.2.17	pPdpAccessConFlag	361
8.276.2.18	pPdpContext	362
8.276.2.19	pPdpDataCompType	362
8.276.2.20	pPdpHdrCompType	362
8.276.2.21	pPDType	362
8.276.2.22	pPriDNSIPv4AddPref	362
8.276.2.23	pPriDNSIPv6addpref	362
8.276.2.24	pPrimaryID	362
8.276.2.25	pProfilename	362
8.276.2.26	pProfilenameSize	362
8.276.2.27	pQosClassID	362
8.276.2.28	pSecDNSIPv4AddPref	362
8.276.2.29	pSecDNSIPv6addpref	362
8.276.2.30	pSecondaryFlag	362
8.276.2.31	pTFTID1Params	362
8.276.2.32	pTFTID2Params	362
8.276.2.33	pUMTSMinQoS	362
8.276.2.34	pUMTSMinQoSSigInd	362
8.276.2.35	pUMTSReqQoS	362
8.276.2.36	pUMTSReqQoSSigInd	362

8.276.2.37pUsername . . . . .	362
8.276.2.38pUsernameSize . . . . .	362
8.277LibPackprofile_3GPP2 Struct Reference . . . . .	362
8.277.1 Detailed Description . . . . .	363
8.277.2 Field Documentation . . . . .	367
8.277.2.1 pAllowLinger . . . . .	367
8.277.2.2 pAPNClass3GPP2 . . . . .	367
8.277.2.3 pAPNEnabled3GPP2 . . . . .	367
8.277.2.4 pApnString . . . . .	367
8.277.2.5 pApnStringSize . . . . .	367
8.277.2.6 pAppPriority . . . . .	367
8.277.2.7 pAppType . . . . .	367
8.277.2.8 pAuthPassword . . . . .	367
8.277.2.9 pAuthPassword_tSize . . . . .	367
8.277.2.10pAuthProtocol . . . . .	367
8.277.2.11pAuthRetryCount . . . . .	367
8.277.2.12pAuthTimeout . . . . .	368
8.277.2.13pDataMode . . . . .	368
8.277.2.14pDataRate . . . . .	368
8.277.2.15pIpcpAckTimeout . . . . .	368
8.277.2.16pIpcpCreqRetryCount . . . . .	368
8.277.2.17pIsPcscfAddressNedded . . . . .	368
8.277.2.18pLcpAckTimeout . . . . .	368
8.277.2.19pLcpCreqRetryCount . . . . .	368
8.277.2.20pNegoDnsSrvrPref . . . . .	368
8.277.2.21pPDNInactivTimeout3GPP2 . . . . .	368
8.277.2.22pPdnType . . . . .	368
8.277.2.23pPppSessCloseTimer1x . . . . .	368
8.277.2.24pPppSessCloseTimerDO . . . . .	368
8.277.2.25pPrimaryV4DnsAddress . . . . .	368
8.277.2.26pPriV6DnsAddress . . . . .	368
8.277.2.27pRATType . . . . .	368
8.277.2.28pSecondaryV4DnsAddress . . . . .	368
8.277.2.29pSecV6DnsAddress . . . . .	368
8.277.2.30pUserId . . . . .	368
8.277.2.31pUserIdSize . . . . .	368
8.278LibPackQosClassID Struct Reference . . . . .	368
8.278.1 Detailed Description . . . . .	368
8.278.2 Field Documentation . . . . .	369
8.278.2.1 gDIBitRate . . . . .	369

8.278.2.2 gUIBitRate . . . . .	369
8.278.2.3 maxDIBitRate . . . . .	369
8.278.2.4 maxUIBitRate . . . . .	369
8.278.2.5 QCI . . . . .	369
8.279LibPackTFTIDParams Struct Reference . . . . .	369
8.279.1 Detailed Description . . . . .	369
8.279.2 Field Documentation . . . . .	371
8.279.2.1 destPortRangeEnd . . . . .	371
8.279.2.2 destPortRangeStart . . . . .	371
8.279.2.3 eValid . . . . .	371
8.279.2.4 filterId . . . . .	371
8.279.2.5 flowLabel . . . . .	371
8.279.2.6 IPSECSPi . . . . .	371
8.279.2.7 ipVersion . . . . .	371
8.279.2.8 nextHeader . . . . .	371
8.279.2.9 pSourceIP . . . . .	371
8.279.2.10sourceIPMask . . . . .	371
8.279.2.11srcPortRangeEnd . . . . .	371
8.279.2.12srcPortRangeStart . . . . .	371
8.279.2.13osMask . . . . .	371
8.280LibPackUMTSQoS Struct Reference . . . . .	371
8.280.1 Detailed Description . . . . .	371
8.280.2 Field Documentation . . . . .	374
8.280.2.1 deliveryErrSDU . . . . .	374
8.280.2.2 grntDownlinkBitrate . . . . .	374
8.280.2.3 grntUplinkBitrate . . . . .	374
8.280.2.4 maxDownlinkBitrate . . . . .	374
8.280.2.5 maxSDUSize . . . . .	374
8.280.2.6 maxUplinkBitrate . . . . .	374
8.280.2.7 qosDeliveryOrder . . . . .	374
8.280.2.8 resBerRatio . . . . .	374
8.280.2.9 sduErrorRatio . . . . .	374
8.280.2.10trafficClass . . . . .	374
8.280.2.11trafficPriority . . . . .	374
8.280.2.12transferDelay . . . . .	374
8.281LibPackUMTSReqQoSsigInd Struct Reference . . . . .	374
8.281.1 Detailed Description . . . . .	374
8.281.2 Field Documentation . . . . .	375
8.281.2.1 SigInd . . . . .	375
8.281.2.2 UMTSReqQoS . . . . .	375

8.282lineCtrlInfo Struct Reference	375
8.282.1 Detailed Description	375
8.282.2 Field Documentation	375
8.282.2.1 polarityIncluded	375
8.282.2.2 pwrDenialTime	375
8.282.2.3 revPolarity	375
8.282.2.4 toggleMode	376
8.283loc_BdsSV Struct Reference	376
8.283.1 Detailed Description	376
8.283.2 Field Documentation	376
8.283.2.1 id	376
8.283.2.2 mask	376
8.284loc_BdsSVInfo Struct Reference	376
8.284.1 Detailed Description	376
8.284.2 Field Documentation	377
8.284.2.1 len	377
8.284.2.2 pSV	377
8.285loc_CellDb Struct Reference	377
8.285.1 Detailed Description	377
8.285.2 Field Documentation	377
8.285.2.1 mask	377
8.286loc_ClkInfo Struct Reference	378
8.286.1 Detailed Description	378
8.286.2 Field Documentation	379
8.286.2.1 mask	380
8.287loc_GnssData Struct Reference	380
8.287.1 Detailed Description	380
8.287.2 Field Documentation	382
8.287.2.1 mask	382
8.288loc_gpsTime Struct Reference	382
8.288.1 Detailed Description	382
8.288.2 Field Documentation	382
8.288.2.1 gpsTimeOfWeekMs	382
8.288.2.2 gpsWeek	382
8.289loc_LocApplicationInfo Struct Reference	382
8.289.1 Detailed Description	382
8.289.2 Field Documentation	383
8.289.2.1 appNameLength	383
8.289.2.2 appProviderLength	383
8.289.2.3 appVersionLength	383



8.289.2.4 appVersionValid . . . . .	383
8.289.2.5 pAppName . . . . .	383
8.289.2.6 pAppProvider . . . . .	383
8.289.2.7 pAppVersion . . . . .	383
8.290loc_precisionDilution Struct Reference . . . . .	383
8.290.1 Detailed Description . . . . .	384
8.290.2 Field Documentation . . . . .	384
8.290.2.1 HDOP . . . . .	384
8.290.2.2 PDOP . . . . .	384
8.290.2.3 VDOP . . . . .	384
8.291loc_sensorDataUsage Struct Reference . . . . .	384
8.291.1 Detailed Description . . . . .	384
8.291.2 Field Documentation . . . . .	385
8.291.2.1 aidingIndicatorMask . . . . .	385
8.291.2.2 usageMask . . . . .	385
8.292loc_SV Struct Reference . . . . .	385
8.292.1 Detailed Description . . . . .	385
8.292.2 Field Documentation . . . . .	386
8.292.2.1 id . . . . .	386
8.292.2.2 mask . . . . .	386
8.292.2.3 system . . . . .	386
8.293loc_SVInfo Struct Reference . . . . .	386
8.293.1 Detailed Description . . . . .	386
8.293.2 Field Documentation . . . . .	387
8.293.2.1 len . . . . .	387
8.293.2.2 pSV . . . . .	387
8.294loc_svUsedforFix Struct Reference . . . . .	387
8.294.1 Detailed Description . . . . .	387
8.294.2 Field Documentation . . . . .	387
8.294.2.1 gnssSvUsedList . . . . .	387
8.294.2.2 gnssSvUsedList_len . . . . .	387
8.295LocApplicationInfo Struct Reference . . . . .	387
8.295.1 Detailed Description . . . . .	388
8.295.2 Field Documentation . . . . .	388
8.295.2.1 appNameLength . . . . .	388
8.295.2.2 appProviderLength . . . . .	388
8.295.2.3 appVersionLength . . . . .	388
8.295.2.4 appVersionValid . . . . .	388
8.295.2.5 pAppName . . . . .	388
8.295.2.6 pAppProvider . . . . .	389

8.295.2.7 pAppVersion . . . . .	389
8.296LocDelAssDataReq Struct Reference . . . . .	389
8.296.1 Detailed Description . . . . .	389
8.296.2 Field Documentation . . . . .	389
8.296.2.1 pBdsSVInfo . . . . .	389
8.296.2.2 pCellDb . . . . .	389
8.296.2.3 pClkInfo . . . . .	389
8.296.2.4 pGnssData . . . . .	389
8.296.2.5 pSVInfo . . . . .	390
8.297LOCEventRegisterReqResp Struct Reference . . . . .	390
8.297.1 Detailed Description . . . . .	390
8.297.2 Field Documentation . . . . .	392
8.297.2.1 eventRegister . . . . .	392
8.298LOCExtPowerStateReqResp Struct Reference . . . . .	392
8.298.1 Detailed Description . . . . .	392
8.298.2 Field Documentation . . . . .	392
8.298.2.1 extPowerState . . . . .	392
8.299LocInjectPositionReq Struct Reference . . . . .	392
8.299.1 Detailed Description . . . . .	393
8.299.2 Field Documentation . . . . .	397
8.299.2.1 pAltitudeSrcInfo . . . . .	397
8.299.2.2 pAltitudeWrtEllipsoid . . . . .	397
8.299.2.3 pAltitudeWrtMeanSeaLevel . . . . .	397
8.299.2.4 pHorConfidence . . . . .	397
8.299.2.5 pHorReliability . . . . .	397
8.299.2.6 pHorUncCircular . . . . .	397
8.299.2.7 pLatitude . . . . .	397
8.299.2.8 pLongitude . . . . .	397
8.299.2.9 pPositionSrc . . . . .	397
8.299.2.10pRawHorConfidence . . . . .	397
8.299.2.11pRawHorUncCircular . . . . .	397
8.299.2.12pTimestampAge . . . . .	397
8.299.2.13pTimestampUtc . . . . .	397
8.299.2.14pVertConfidence . . . . .	397
8.299.2.15pVertReliability . . . . .	397
8.299.2.16pVertUnc . . . . .	398
8.300LocInjectSensorDataReq Struct Reference . . . . .	398
8.300.1 Detailed Description . . . . .	398
8.300.2 Field Documentation . . . . .	399
8.300.2.1 pAcceleroData . . . . .	399

8.300.2.2 pAcceleroTempData . . . . .	399
8.300.2.3 pAcceleroTimeSrc . . . . .	399
8.300.2.4 pGyroData . . . . .	399
8.300.2.5 pGyroTempData . . . . .	399
8.300.2.6 pGyroTimeSrc . . . . .	399
8.300.2.7 pOpaqueIdentifier . . . . .	399
8.301 LocSetCradleMountReq Struct Reference . . . . .	399
8.301.1 Detailed Description . . . . .	399
8.301.2 Field Documentation . . . . .	400
8.301.2.1 pConfidence . . . . .	400
8.301.2.2 state . . . . .	400
8.302 LOCStartReq Struct Reference . . . . .	400
8.302.1 Detailed Description . . . . .	400
8.302.2 Field Documentation . . . . .	402
8.302.2.1 pApplicationInfo . . . . .	402
8.302.2.2 pConfigAltitudeAssumed . . . . .	402
8.302.2.3 pHorizontalAccuracyLvl . . . . .	402
8.302.2.4 pIntermediateReportState . . . . .	402
8.302.2.5 pMinIntervalTime . . . . .	402
8.302.2.6 pRecurrenceType . . . . .	402
8.302.2.7 SessionId . . . . .	402
8.303 LOCStopReq Struct Reference . . . . .	402
8.303.1 Detailed Description . . . . .	402
8.303.2 Field Documentation . . . . .	402
8.303.2.1 sessionId . . . . .	402
8.304 LteCQIParm Struct Reference . . . . .	402
8.304.1 Detailed Description . . . . .	403
8.304.2 Field Documentation . . . . .	403
8.304.2.1 CQIValueCW0 . . . . .	403
8.304.2.2 CQIValueCW1 . . . . .	403
8.304.2.3 ValidityCW0 . . . . .	403
8.304.2.4 ValidityCW1 . . . . .	403
8.305 lteEARFCN Struct Reference . . . . .	403
8.305.1 Detailed Description . . . . .	404
8.305.2 Field Documentation . . . . .	404
8.305.2.1 earfcn0 . . . . .	404
8.305.2.2 earfcn1 . . . . .	404
8.305.2.3 status . . . . .	404
8.306 lteGsmCellInfo Struct Reference . . . . .	404
8.306.1 Detailed Description . . . . .	404

8.306.2 Field Documentation . . . . .	405
8.306.2.1 cellReselPriority . . . . .	405
8.306.2.2 cells_len . . . . .	405
8.306.2.3 GsmCellInfo . . . . .	405
8.306.2.4 nccPermitted . . . . .	405
8.306.2.5 threshGsmHigh . . . . .	405
8.306.2.6 threshGsmLow . . . . .	405
8.307LTEInfo Struct Reference . . . . .	405
8.307.1 Detailed Description . . . . .	406
8.307.2 Field Documentation . . . . .	408
8.307.2.1 band . . . . .	408
8.307.2.2 bandwidth . . . . .	408
8.307.2.3 emmConnState . . . . .	408
8.307.2.4 emmState . . . . .	408
8.307.2.5 emmSubState . . . . .	408
8.307.2.6 RXChan . . . . .	408
8.307.2.7 TXChan . . . . .	408
8.308LTEInfoInterfreq Struct Reference . . . . .	408
8.308.1 Detailed Description . . . . .	408
8.308.2 Field Documentation . . . . .	409
8.308.2.1 freqsLen . . . . .	409
8.308.2.2 InfoInterfreq . . . . .	409
8.308.2.3 ueInIdle . . . . .	409
8.309LTEInfoIntrafreq Struct Reference . . . . .	409
8.309.1 Detailed Description . . . . .	409
8.309.2 Field Documentation . . . . .	411
8.309.2.1 CellParams . . . . .	411
8.309.2.2 cellReselPriority . . . . .	411
8.309.2.3 cellsLen . . . . .	411
8.309.2.4 earfcn . . . . .	411
8.309.2.5 globalCellId . . . . .	411
8.309.2.6 plmn . . . . .	411
8.309.2.7 servingCellId . . . . .	411
8.309.2.8 sIntraSearch . . . . .	411
8.309.2.9 sNonIntraSearch . . . . .	411
8.309.2.10tac . . . . .	411
8.309.2.11threshServingLow . . . . .	411
8.309.2.12ueInIdle . . . . .	411
8.310LTEInfoNeighboringGSM Struct Reference . . . . .	412
8.310.1 Detailed Description . . . . .	412

8.310.2 Field Documentation	412
8.310.2.1 freqsLen	412
8.310.2.2 LteGsmCellInfo	412
8.310.2.3 ueInIdle	412
8.311 LTEInfoNeighboringWCDMA Struct Reference	412
8.311.1 Detailed Description	412
8.311.2 Field Documentation	413
8.311.2.1 freqsLen	413
8.311.2.2 LTEWCDMACellInfo	413
8.311.2.3 ueInIdle	413
8.312 LteNasReleaseInfo_s Struct Reference	413
8.312.1 Detailed Description	413
8.312.2 Field Documentation	413
8.312.2.1 nas_major	413
8.312.2.2 nas_minor	413
8.312.2.3 nas_release	414
8.313 ItePCI Struct Reference	414
8.313.1 Detailed Description	414
8.313.2 Field Documentation	414
8.313.2.1 earfcn	414
8.313.2.2 pci	414
8.313.2.3 status	414
8.314 IteRsrpInformation Struct Reference	414
8.314.1 Detailed Description	414
8.314.2 Field Documentation	415
8.314.2.1 rsrplevel	415
8.315 LTERSRPThresh Struct Reference	415
8.315.1 Detailed Description	415
8.315.2 Field Documentation	415
8.315.2.1 LTERSRPThreshListLen	415
8.315.2.2 pLTERSRPThreshList	415
8.316 LTERSRQThresh Struct Reference	415
8.316.1 Detailed Description	415
8.316.2 Field Documentation	416
8.316.2.1 LTERSRQThreshListLen	416
8.316.2.2 pLTERSRQThreshList	416
8.317 LTERSSIThresh Struct Reference	416
8.317.1 Detailed Description	416
8.317.2 Field Documentation	416
8.317.2.1 LTERSSIThreshListLen	416

8.317.2.2 pLTERSSIThreshList . . . . .	416
8.318LTESigRptCfg Struct Reference . . . . .	416
8.318.1 Detailed Description . . . . .	417
8.318.2 Field Documentation . . . . .	418
8.318.2.1 avgPeriod . . . . .	418
8.318.2.2 rptRate . . . . .	418
8.319LTESigRptConfig Struct Reference . . . . .	418
8.319.1 Detailed Description . . . . .	418
8.319.2 Field Documentation . . . . .	419
8.319.2.1 avgPeriod . . . . .	419
8.319.2.2 rptRate . . . . .	419
8.320IteSnrinformation Struct Reference . . . . .	419
8.320.1 Detailed Description . . . . .	419
8.320.2 Field Documentation . . . . .	420
8.320.2.1 snrlevel . . . . .	420
8.321LTESNRThresh Struct Reference . . . . .	420
8.321.1 Detailed Description . . . . .	420
8.321.2 Field Documentation . . . . .	420
8.321.2.1 LTESNRThresListLen . . . . .	420
8.321.2.2 pLTESNRThresList . . . . .	420
8.322LTESNRThreshold Struct Reference . . . . .	420
8.322.1 Detailed Description . . . . .	421
8.322.2 Field Documentation . . . . .	421
8.322.2.1 LTESNRThreshListLen . . . . .	421
8.322.2.2 pLTESNRThreshList . . . . .	421
8.323LTESInfo Struct Reference . . . . .	421
8.323.1 Detailed Description . . . . .	421
8.323.2 Field Documentation . . . . .	422
8.323.2.1 rsrp . . . . .	422
8.323.2.2 rsrq . . . . .	422
8.323.2.3 rssi . . . . .	422
8.323.2.4 snr . . . . .	422
8.324IteSSInfo Struct Reference . . . . .	422
8.324.1 Detailed Description . . . . .	422
8.324.2 Field Documentation . . . . .	423
8.324.2.1 rsrp . . . . .	423
8.324.2.2 rsrq . . . . .	423
8.324.2.3 rssi . . . . .	423
8.324.2.4 snr . . . . .	423
8.325LTESysInfo Struct Reference . . . . .	423

8.325.1 Detailed Description . . . . .	423
8.325.2 Field Documentation . . . . .	425
8.325.2.1 cellId . . . . .	425
8.325.2.2 cellIdValid . . . . .	425
8.325.2.3 lac . . . . .	425
8.325.2.4 lacValid . . . . .	425
8.325.2.5 MCC . . . . .	425
8.325.2.6 MNC . . . . .	425
8.325.2.7 networkIdValid . . . . .	425
8.325.2.8 regRejectInfoValid . . . . .	425
8.325.2.9 rejCause . . . . .	425
8.325.2.10 rejectSrvDomain . . . . .	425
8.325.2.11 sysInfoLTE . . . . .	425
8.325.2.12 tac . . . . .	425
8.325.2.13 tacValid . . . . .	425
8.326 lteWcdmaCellInfo Struct Reference . . . . .	425
8.326.1 Detailed Description . . . . .	425
8.326.2 Field Documentation . . . . .	426
8.326.2.1 cellReselPriority . . . . .	426
8.326.2.2 cellsLen . . . . .	426
8.326.2.3 threshXhigh . . . . .	426
8.326.2.4 threshXlow . . . . .	426
8.326.2.5 uarfcn . . . . .	426
8.326.2.6 WCDMACellInfo . . . . .	426
8.327 messageModeTlv Struct Reference . . . . .	426
8.327.1 Detailed Description . . . . .	426
8.327.2 Field Documentation . . . . .	427
8.327.2.1 MessageModeInfo . . . . .	427
8.327.2.2 TlvPresent . . . . .	427
8.328 messageWaitingInfoContent Struct Reference . . . . .	427
8.328.1 Detailed Description . . . . .	427
8.328.2 Field Documentation . . . . .	427
8.328.2.1 activeInd . . . . .	428
8.328.2.2 msgCount . . . . .	428
8.328.2.3 msgType . . . . .	428
8.329 minBasedIMSI Struct Reference . . . . .	428
8.329.1 Detailed Description . . . . .	428
8.329.2 Field Documentation . . . . .	428
8.329.2.1 imsiM1112 . . . . .	428
8.329.2.2 imsiMS1 . . . . .	428

8.329.2.3 imsiMS2 . . . . .	428
8.329.2.4 mccM . . . . .	428
8.330mitigationDevList Struct Reference . . . . .	428
8.330.1 Detailed Description . . . . .	429
8.330.2 Field Documentation . . . . .	429
8.330.2.1 maxMitigationLevel . . . . .	429
8.330.2.2 mitigationDevId . . . . .	429
8.330.2.3 mitigationDevIdLen . . . . .	429
8.331MNRInfo Struct Reference . . . . .	429
8.331.1 Detailed Description . . . . .	429
8.331.2 Field Documentation . . . . .	430
8.331.2.1 mcc . . . . .	430
8.331.2.2 mnc . . . . .	430
8.331.2.3 rat . . . . .	430
8.332ModifyProfileIn Struct Reference . . . . .	430
8.332.1 Detailed Description . . . . .	430
8.332.2 Field Documentation . . . . .	431
8.332.2.1 curProfile . . . . .	431
8.332.2.2 pProfileID . . . . .	431
8.332.2.3 pProfileType . . . . .	431
8.333ModifyProfileOut Struct Reference . . . . .	431
8.333.1 Detailed Description . . . . .	431
8.333.2 Field Documentation . . . . .	431
8.333.2.1 pExtErrorCode . . . . .	432
8.334msgWaitingInfo Struct Reference . . . . .	432
8.334.1 Detailed Description . . . . .	432
8.334.2 Field Documentation . . . . .	432
8.334.2.1 msgWaitInfo . . . . .	432
8.334.2.2 numInstances . . . . .	432
8.335namName Struct Reference . . . . .	432
8.335.1 Detailed Description . . . . .	432
8.335.2 Field Documentation . . . . .	433
8.335.2.1 namName . . . . .	433
8.335.2.2 namNameLen . . . . .	433
8.336nas_acqOrderPref Struct Reference . . . . .	433
8.336.1 Detailed Description . . . . .	433
8.336.2 Field Documentation . . . . .	433
8.336.2.1 acqOrdeLen . . . . .	433
8.336.2.2 pAcqOrder . . . . .	433
8.337nas_AddCDMASysInfo Struct Reference . . . . .	433



8.337.1 Detailed Description . . . . .	433
8.337.2 Field Documentation . . . . .	434
8.337.2.1 geoSysIdx . . . . .	434
8.337.2.2 regPrd . . . . .	434
8.338nas_AddSysInfo Struct Reference . . . . .	434
8.338.1 Detailed Description . . . . .	434
8.338.2 Field Documentation . . . . .	434
8.338.2.1 cellBroadcastCap . . . . .	434
8.338.2.2 geoSysIdx . . . . .	435
8.339nas_CallBarringSysInfo Struct Reference . . . . .	435
8.339.1 Detailed Description . . . . .	435
8.339.2 Field Documentation . . . . .	435
8.339.2.1 csBarStatus . . . . .	435
8.339.2.2 psBarStatus . . . . .	435
8.340nas_callBarStatus Struct Reference . . . . .	435
8.340.1 Detailed Description . . . . .	436
8.340.2 Field Documentation . . . . .	436
8.340.2.1 csBarStatus . . . . .	436
8.340.2.2 psBarStatus . . . . .	436
8.341nas_CDMAECIOThresh Struct Reference . . . . .	436
8.341.1 Detailed Description . . . . .	436
8.341.2 Field Documentation . . . . .	437
8.341.2.1 CDMAECIOThreshListLen . . . . .	437
8.341.2.2 pCDMAECIOThreshList . . . . .	437
8.342nas_CDMAInfo Struct Reference . . . . .	437
8.342.1 Detailed Description . . . . .	437
8.342.2 Field Documentation . . . . .	438
8.342.2.1 baseId . . . . .	438
8.342.2.2 baseLat . . . . .	438
8.342.2.3 baseLong . . . . .	438
8.342.2.4 nid . . . . .	438
8.342.2.5 refpn . . . . .	438
8.342.2.6 sid . . . . .	438
8.343nas_CDMARSSIThresh Struct Reference . . . . .	438
8.343.1 Detailed Description . . . . .	438
8.343.2 Field Documentation . . . . .	439
8.343.2.1 CDMARSSIThreshListLen . . . . .	439
8.343.2.2 pCDMARSSIThreshList . . . . .	439
8.344nas_CDMASysInfo Struct Reference . . . . .	439
8.344.1 Detailed Description . . . . .	439

8.344.2 Field Documentation	442
8.344.2.1 baseId	442
8.344.2.2 baseLat	442
8.344.2.3 baseLong	442
8.344.2.4 bsInfoValid	442
8.344.2.5 bsPRev	442
8.344.2.6 bsPRevValid	442
8.344.2.7 ccsSupported	442
8.344.2.8 ccsSupportedValid	443
8.344.2.9 cdmaSysIdValid	443
8.344.2.10 isSysPrIMatch	443
8.344.2.11 isSysPrIMatchValid	443
8.344.2.12 MCC	443
8.344.2.13 MNC	443
8.344.2.14 networkID	443
8.344.2.15 networkIdValid	443
8.344.2.16 packetZone	443
8.344.2.17 packetZoneValid	443
8.344.2.18 pRevInUse	443
8.344.2.19 pRevInUseValid	443
8.344.2.20 sysInfoCDMA	443
8.344.2.21 systemID	443
8.345 nas_CDMASysInfoExt Struct Reference	443
8.345.1 Detailed Description	443
8.345.2 Field Documentation	443
8.345.2.1 imsi_11_12	443
8.345.2.2 MCC	444
8.346 nas_cellParams Struct Reference	444
8.346.1 Detailed Description	444
8.346.2 Field Documentation	444
8.346.2.1 pci	444
8.346.2.2 rsrp	444
8.346.2.3 rsrq	444
8.346.2.4 rssi	444
8.346.2.5 srxlev	445
8.347 nas_CommInfo Struct Reference	445
8.347.1 Detailed Description	445
8.347.2 Field Documentation	446
8.347.2.1 imsRegState	446
8.347.2.2 modemMode	446

8.347.2.3 psState . . . . .	446
8.347.2.4 systemMode . . . . .	446
8.347.2.5 temperature . . . . .	446
8.348nas_CSGID Struct Reference . . . . .	446
8.348.1 Detailed Description . . . . .	447
8.348.2 Field Documentation . . . . .	447
8.348.2.1 id . . . . .	447
8.348.2.2 mcc . . . . .	447
8.348.2.3 mnc . . . . .	447
8.348.2.4 mncPcsDigits . . . . .	447
8.348.2.5 rat . . . . .	447
8.349nas_currentPLMN Struct Reference . . . . .	447
8.349.1 Detailed Description . . . . .	448
8.349.2 Field Documentation . . . . .	448
8.349.2.1 MCC . . . . .	448
8.349.2.2 MNC . . . . .	448
8.349.2.3 netDescr . . . . .	448
8.349.2.4 netDescrLength . . . . .	448
8.350nas_dataSrvCapabilities Struct Reference . . . . .	448
8.350.1 Detailed Description . . . . .	449
8.350.2 Field Documentation . . . . .	449
8.350.2.1 dataCapabilities . . . . .	449
8.350.2.2 dataCapabilitiesLen . . . . .	449
8.351nas_detailSvcInfo Struct Reference . . . . .	449
8.351.1 Detailed Description . . . . .	450
8.351.2 Field Documentation . . . . .	451
8.351.2.1 hdrHybrid . . . . .	451
8.351.2.2 hdrSrvStatus . . . . .	451
8.351.2.3 isSysForbidden . . . . .	451
8.351.2.4 srvCapability . . . . .	451
8.351.2.5 srvStatus . . . . .	451
8.352nas_ecioListElement Struct Reference . . . . .	451
8.352.1 Detailed Description . . . . .	451
8.352.2 Field Documentation . . . . .	452
8.352.2.1 ecio . . . . .	452
8.352.2.2 radiolf . . . . .	452
8.353nas_errorRateListElement Struct Reference . . . . .	452
8.353.1 Detailed Description . . . . .	452
8.353.2 Field Documentation . . . . .	453
8.353.2.1 errorRate . . . . .	453

8.353.2.2 radiolf . . . . .	453
8.354nas_GERANInfo Struct Reference . . . . .	453
8.354.1 Detailed Description . . . . .	454
8.354.2 Field Documentation . . . . .	455
8.354.2.1 arfcn . . . . .	455
8.354.2.2 bsic . . . . .	455
8.354.2.3 cellID . . . . .	455
8.354.2.4 insNmrCellInfo . . . . .	455
8.354.2.5 lac . . . . .	455
8.354.2.6 nmrlnst . . . . .	455
8.354.2.7 plmn . . . . .	455
8.354.2.8 rxLev . . . . .	455
8.354.2.9 timingAdvance . . . . .	455
8.355nas_geranInstInfo Struct Reference . . . . .	455
8.355.1 Detailed Description . . . . .	456
8.355.2 Field Documentation . . . . .	456
8.355.2.1 geranArfcn . . . . .	456
8.355.2.2 geranBsicBcc . . . . .	456
8.355.2.3 geranBsicNcc . . . . .	456
8.355.2.4 geranRssi . . . . .	456
8.356nas_gsmCellInfo Struct Reference . . . . .	456
8.356.1 Detailed Description . . . . .	456
8.356.2 Field Documentation . . . . .	457
8.356.2.1 arfcn . . . . .	457
8.356.2.2 band1900 . . . . .	457
8.356.2.3 bsicld . . . . .	457
8.356.2.4 cellIdValid . . . . .	457
8.356.2.5 rssi . . . . .	457
8.356.2.6 srxlev . . . . .	457
8.357nas_GSMRSSIthresh Struct Reference . . . . .	457
8.357.1 Detailed Description . . . . .	458
8.357.2 Field Documentation . . . . .	458
8.357.2.1 GSMRSSIthreshListLen . . . . .	458
8.357.2.2 pGSMRSSIthreshList . . . . .	458
8.358nas_GSMSrvStatusInfo Struct Reference . . . . .	458
8.358.1 Detailed Description . . . . .	458
8.358.2 Field Documentation . . . . .	459
8.358.2.1 isPrefDataPath . . . . .	459
8.358.2.2 srvStatus . . . . .	459
8.358.2.3 trueSrvStatus . . . . .	459

8.359nas_GSMSysInfo Struct Reference	459
8.359.1 Detailed Description	459
8.359.2 Field Documentation	462
8.359.2.1 cellId	462
8.359.2.2 cellIdValid	462
8.359.2.3 dtmSupp	462
8.359.2.4 dtmSuppValid	462
8.359.2.5 egprsSupp	462
8.359.2.6 egprsSuppValid	462
8.359.2.7 lac	462
8.359.2.8 lacValid	462
8.359.2.9 MCC	462
8.359.2.10MNC	462
8.359.2.11networkIdValid	462
8.359.2.12regRejectInfoValid	462
8.359.2.13rejCause	462
8.359.2.14rejectSrvDomain	462
8.359.2.15sysInfoGSM	462
8.360nas_HDRECIOThresh Struct Reference	462
8.360.1 Detailed Description	462
8.360.2 Field Documentation	463
8.360.2.1 HDRECIOThreshListLen	463
8.360.2.2 pHDRECIOThreshList	463
8.361nas_HDRIOTThresh Struct Reference	463
8.361.1 Detailed Description	463
8.361.2 Field Documentation	463
8.361.2.1 HDRIOTThreshListLen	463
8.361.2.2 pHDRIOTThreshList	463
8.362nas_HDRRSSIThresh Struct Reference	463
8.362.1 Detailed Description	464
8.362.2 Field Documentation	464
8.362.2.1 HDRRSSIThreshListLen	464
8.362.2.2 pHDRRSSIThreshList	464
8.363nas_HDRSINRThreshold Struct Reference	464
8.363.1 Detailed Description	464
8.363.2 Field Documentation	465
8.363.2.1 HDRSINRThreshListLen	465
8.363.2.2 pHDRSINRThreshList	465
8.364nas_HDRSysInfo Struct Reference	465
8.364.1 Detailed Description	465

8.364.2 Field Documentation	467
8.364.2.1 hdrActiveProt	467
8.364.2.2 hdrActiveProtValid	467
8.364.2.3 hdrPersonality	467
8.364.2.4 hdrPersonalityValid	467
8.364.2.5 is856SysId	467
8.364.2.6 is856SysIdValid	467
8.364.2.7 isSysPrIMatch	467
8.364.2.8 isSysPrIMatchValid	467
8.364.2.9 sysInfoHDR	467
8.365nas_infoInterFreq Struct Reference	468
8.365.1 Detailed Description	468
8.365.2 Field Documentation	468
8.365.2.1 cell_resel_priority	468
8.365.2.2 cellInterFreqParams	469
8.365.2.3 cells_len	469
8.365.2.4 earfcn	469
8.365.2.5 threshXHigh	469
8.365.2.6 threshXLow	469
8.366nas_lteGsmCellInfo Struct Reference	469
8.366.1 Detailed Description	469
8.366.2 Field Documentation	470
8.366.2.1 cellReselPriority	470
8.366.2.2 cells_len	470
8.366.2.3 GsmCellInfo	470
8.366.2.4 nccPermitted	470
8.366.2.5 threshGsmHigh	470
8.366.2.6 threshGsmLow	470
8.367nas_LTEInfo Struct Reference	470
8.367.1 Detailed Description	470
8.367.2 Field Documentation	472
8.367.2.1 band	472
8.367.2.2 bandwidth	472
8.367.2.3 emmConnState	472
8.367.2.4 emmState	473
8.367.2.5 emmSubState	473
8.367.2.6 RXChan	473
8.367.2.7 TXChan	473
8.368nas_LTEInfoInterfreq Struct Reference	473
8.368.1 Detailed Description	473

8.368.2 Field Documentation	473
8.368.2.1 freqsLen	473
8.368.2.2 InfoInterfreq	473
8.368.2.3 ueInIdle	473
8.369nas_LTEInfoIntrafreq Struct Reference	473
8.369.1 Detailed Description	474
8.369.2 Field Documentation	475
8.369.2.1 CellParams	475
8.369.2.2 cellReselPriority	475
8.369.2.3 cellsLen	475
8.369.2.4 earfcn	476
8.369.2.5 globalCellId	476
8.369.2.6 plmn	476
8.369.2.7 servingCellId	476
8.369.2.8 sIntraSearch	476
8.369.2.9 sNonIntraSearch	476
8.369.2.10tac	476
8.369.2.11threshServingLow	476
8.369.2.12ueInIdle	476
8.370nas_LTEInfoNeighboringGSM Struct Reference	476
8.370.1 Detailed Description	476
8.370.2 Field Documentation	476
8.370.2.1 freqsLen	476
8.370.2.2 LteGsmCellInfo	476
8.370.2.3 ueInIdle	476
8.371nas_LTEInfoNeighboringWCDMA Struct Reference	477
8.371.1 Detailed Description	477
8.371.2 Field Documentation	477
8.371.2.1 freqsLen	477
8.371.2.2 LTEWCDMACellInfo	477
8.371.2.3 ueInIdle	477
8.372nas_LteRsrpInformation Struct Reference	477
8.372.1 Detailed Description	477
8.372.2 Field Documentation	478
8.372.2.1 rsrpLevel	478
8.373nas_LTERSRPThresh Struct Reference	478
8.373.1 Detailed Description	478
8.373.2 Field Documentation	478
8.373.2.1 LTERSRPThreshListLen	478
8.373.2.2 pLTERSRPThreshList	478

8.374nas_LTERSRQThresh Struct Reference . . . . .	478
8.374.1 Detailed Description . . . . .	478
8.374.2 Field Documentation . . . . .	479
8.374.2.1 LTERSRQThreshListLen . . . . .	479
8.374.2.2 pLTERSRQThreshList . . . . .	479
8.375nas_LTERSSIThresh Struct Reference . . . . .	479
8.375.1 Detailed Description . . . . .	479
8.375.2 Field Documentation . . . . .	479
8.375.2.1 LTERSSIThreshListLen . . . . .	479
8.375.2.2 pLTERSSIThreshList . . . . .	479
8.376nas_LTESigRptConfig Struct Reference . . . . .	479
8.376.1 Detailed Description . . . . .	480
8.376.2 Field Documentation . . . . .	481
8.376.2.1 avgPeriod . . . . .	481
8.376.2.2 rptRate . . . . .	481
8.377nas_lteSnrinformation Struct Reference . . . . .	481
8.377.1 Detailed Description . . . . .	481
8.377.2 Field Documentation . . . . .	481
8.377.2.1 snrlevel . . . . .	481
8.378nas_LTESNRThreshold Struct Reference . . . . .	481
8.378.1 Detailed Description . . . . .	481
8.378.2 Field Documentation . . . . .	482
8.378.2.1 LTESNRThreshListLen . . . . .	482
8.378.2.2 pLTESNRThreshList . . . . .	482
8.379nas_LTESysInfo Struct Reference . . . . .	482
8.379.1 Detailed Description . . . . .	482
8.379.2 Field Documentation . . . . .	484
8.379.2.1 cellId . . . . .	484
8.379.2.2 cellIdValid . . . . .	484
8.379.2.3 lac . . . . .	484
8.379.2.4 lacValid . . . . .	484
8.379.2.5 MCC . . . . .	484
8.379.2.6 MNC . . . . .	484
8.379.2.7 networkIdValid . . . . .	484
8.379.2.8 regRejectInfoValid . . . . .	484
8.379.2.9 rejCause . . . . .	484
8.379.2.10rejectSrvDomain . . . . .	484
8.379.2.11sysInfoLTE . . . . .	484
8.379.2.12ac . . . . .	485
8.379.2.13acValid . . . . .	485



8.380nas_lteWcdmaCellInfo Struct Reference	485
8.380.1 Detailed Description	485
8.380.2 Field Documentation	486
8.380.2.1 cellReselPriority	486
8.380.2.2 cellsLen	486
8.380.2.3 threshXhigh	486
8.380.2.4 threshXlow	486
8.380.2.5 uarfcn	486
8.380.2.6 WCDMACellInfo	486
8.381nas_MNRInfo Struct Reference	486
8.381.1 Detailed Description	486
8.381.2 Field Documentation	487
8.381.2.1 mcc	487
8.381.2.2 mnc	487
8.381.2.3 rat	487
8.382nas_netSelectionPref Struct Reference	487
8.382.1 Detailed Description	487
8.382.2 Field Documentation	487
8.382.2.1 mcc	487
8.382.2.2 mnc	487
8.382.2.3 netReg	487
8.383nas_nmrCellInfo Struct Reference	487
8.383.1 Detailed Description	488
8.383.2 Field Documentation	489
8.383.2.1 nmrArfcn	489
8.383.2.2 nmrBsic	489
8.383.2.3 nmrCellID	489
8.383.2.4 nmrLac	490
8.383.2.5 nmrPlmn	490
8.383.2.6 nmrRxLev	490
8.384nas_qaQmi3Gpp2TimeZone Struct Reference	490
8.384.1 Detailed Description	490
8.384.2 Field Documentation	490
8.384.2.1 daylightSavings	490
8.384.2.2 leapSeconds	490
8.384.2.3 localTimeOffset	490
8.385nas_QmiNas3GppNetworkInfo Struct Reference	490
8.385.1 Detailed Description	491
8.385.2 Field Documentation	491
8.385.2.1 Description	491

8.385.2.2 Forbidden . . . . .	491
8.385.2.3 InUse . . . . .	491
8.385.2.4 MCC . . . . .	491
8.385.2.5 MNC . . . . .	491
8.385.2.6 Preferred . . . . .	491
8.385.2.7 Roaming . . . . .	491
8.386nas_QmiNas3GppNetworkRAT Struct Reference . . . . .	491
8.386.1 Detailed Description . . . . .	491
8.386.2 Field Documentation . . . . .	492
8.386.2.1 MCC . . . . .	492
8.386.2.2 MNC . . . . .	492
8.386.2.3 RAT . . . . .	492
8.387nas_QmisNasPcsDigit Struct Reference . . . . .	492
8.387.1 Detailed Description . . . . .	492
8.387.2 Field Documentation . . . . .	493
8.387.2.1 includes_pcs_digit . . . . .	493
8.387.2.2 MCC . . . . .	493
8.387.2.3 MNC . . . . .	493
8.388nas_RejectReasonTlv Struct Reference . . . . .	493
8.388.1 Detailed Description . . . . .	493
8.388.2 Field Documentation . . . . .	493
8.388.2.1 rejectCause . . . . .	493
8.388.2.2 serviceDomain . . . . .	493
8.388.2.3 TlvPresent . . . . .	493
8.389nas_RFInfoTlv Struct Reference . . . . .	493
8.389.1 Detailed Description . . . . .	493
8.389.2 Field Documentation . . . . .	494
8.389.2.1 activeBandClass . . . . .	494
8.389.2.2 activeChannel . . . . .	494
8.389.2.3 radiolInterface . . . . .	494
8.389.2.4 radiolInterfaceSize . . . . .	494
8.389.2.5 TlvPresent . . . . .	494
8.390nas_roamIndList Struct Reference . . . . .	494
8.390.1 Detailed Description . . . . .	494
8.390.2 Field Documentation . . . . .	495
8.390.2.1 numInstances . . . . .	495
8.390.2.2 radiolInterface . . . . .	495
8.390.2.3 roamIndicator . . . . .	495
8.391nas_rsrqInformation Struct Reference . . . . .	495
8.391.1 Detailed Description . . . . .	495

8.391.2 Field Documentation . . . . .	495
8.391.2.1 radiolf . . . . .	495
8.391.2.2 rsrq . . . . .	495
8.392nas_rxSignalStrengthListElement Struct Reference . . . . .	495
8.392.1 Detailed Description . . . . .	495
8.392.2 Field Documentation . . . . .	496
8.392.2.1 radiolf . . . . .	496
8.392.2.2 rxSignalStrength . . . . .	496
8.393nas_servSystem Struct Reference . . . . .	496
8.393.1 Detailed Description . . . . .	496
8.393.2 Field Documentation . . . . .	498
8.393.2.1 csAttachState . . . . .	498
8.393.2.2 numRadioInterfaces . . . . .	498
8.393.2.3 psAttachState . . . . .	498
8.393.2.4 radiolInterface . . . . .	498
8.393.2.5 regState . . . . .	498
8.393.2.6 selNetwork . . . . .	498
8.394nas_SignalStrengthTlv Struct Reference . . . . .	498
8.394.1 Detailed Description . . . . .	498
8.394.2 Field Documentation . . . . .	499
8.394.2.1 radiolInterface . . . . .	499
8.394.2.2 signalStrength . . . . .	499
8.394.2.3 TlvPresent . . . . .	499
8.395nas_SLQSSignalStrengthsIndReq Struct Reference . . . . .	499
8.395.1 Detailed Description . . . . .	499
8.395.2 Field Documentation . . . . .	499
8.395.2.1 ecioDelta . . . . .	499
8.395.2.2 ecioThresholdList . . . . .	499
8.395.2.3 ecioThresholdListLen . . . . .	499
8.395.2.4 ioDelta . . . . .	499
8.395.2.5 lteRsrpDelta . . . . .	500
8.395.2.6 lteSnrDelta . . . . .	500
8.395.2.7 rsrqDelta . . . . .	500
8.395.2.8 rxSignalStrengthDelta . . . . .	500
8.395.2.9 sinrDelta . . . . .	500
8.395.2.10sinrThresholdList . . . . .	500
8.395.2.11sinrThresholdListLen . . . . .	500
8.396nas_SLQSSignalStrengthsInformation Struct Reference . . . . .	500
8.396.1 Detailed Description . . . . .	500
8.396.2 Field Documentation . . . . .	500

8.396.2.1	eciInfo	500
8.396.2.2	errorRateInfo	500
8.396.2.3	io	500
8.396.2.4	lteRsrpInfo	500
8.396.2.5	lteSnrInfo	500
8.396.2.6	rsrqInfo	500
8.396.2.7	rxSignalStrengthInfo	501
8.396.2.8	sinr	501
8.397	nas_SLQSSignalStrengthsTlv Struct Reference	501
8.397.1	Detailed Description	501
8.397.2	Field Documentation	501
8.397.2.1	sSLQSSignalStrengthsInfo	501
8.397.2.2	TlvPresent	501
8.398	nas_SrvStatusInfo Struct Reference	501
8.398.1	Detailed Description	501
8.398.2	Field Documentation	502
8.398.2.1	isPrefDataPath	502
8.398.2.2	srvStatus	502
8.399	nas_sysInfoCommon Struct Reference	502
8.399.1	Detailed Description	502
8.399.2	Field Documentation	505
8.399.2.1	isSysForbidden	505
8.399.2.2	isSysForbiddenValid	505
8.399.2.3	roamStatus	505
8.399.2.4	roamStatusValid	505
8.399.2.5	srvCapability	505
8.399.2.6	srvCapabilityValid	505
8.399.2.7	srvDomain	505
8.399.2.8	srvDomainValid	505
8.400	nas_TDSCDMAECIOThresh Struct Reference	505
8.400.1	Detailed Description	505
8.400.2	Field Documentation	506
8.400.2.1	pTDSCDMAECIOThreshList	506
8.400.2.2	TDSCDMAECIOThreshListLen	506
8.401	nas_TDSCDMARSCPThresh Struct Reference	506
8.401.1	Detailed Description	506
8.401.2	Field Documentation	506
8.401.2.1	pTDSCDMARSCPThreshList	506
8.401.2.2	TDSCDMARSCPThreshListLen	506
8.402	nas_TDSCDMARSSIThresh Struct Reference	506

8.402.1 Detailed Description	506
8.402.2 Field Documentation	507
8.402.2.1 pTDSCDMARSSIThreshList	507
8.402.2.2 TDSCDMARSSIThreshListLen	507
8.403nas_TDSCDMASINRThresh Struct Reference	507
8.403.1 Detailed Description	507
8.403.2 Field Documentation	507
8.403.2.1 pTDSCDMASINRThreshList	507
8.403.2.2 TDSCDMASINRThreshListLen	507
8.404nas_timeInfo Struct Reference	507
8.404.1 Detailed Description	508
8.404.2 Field Documentation	509
8.404.2.1 day	509
8.404.2.2 dayLtSavingAdj	509
8.404.2.3 dayOfWeek	509
8.404.2.4 hour	509
8.404.2.5 minute	509
8.404.2.6 month	509
8.404.2.7 radiolInterface	509
8.404.2.8 second	509
8.404.2.9 timeZone	509
8.404.2.10TlvPresent	509
8.404.2.11year	509
8.405nas_UMTSInfo Struct Reference	509
8.405.1 Detailed Description	510
8.405.2 Field Documentation	511
8.405.2.1 cellID	511
8.405.2.2 ecio	511
8.405.2.3 geranInst	511
8.405.2.4 GeranInstInfo	511
8.405.2.5 lac	511
8.405.2.6 plmn	511
8.405.2.7 psc	511
8.405.2.8 rscp	511
8.405.2.9 uarfcn	511
8.405.2.10umtsInst	511
8.405.2.11UMTSInstInfo	511
8.406nas_UMTSinstInfo Struct Reference	511
8.406.1 Detailed Description	512
8.406.2 Field Documentation	512

8.406.2.1 umtsEcio . . . . .	512
8.406.2.2 umtsPsc . . . . .	512
8.406.2.3 umtsRscp . . . . .	512
8.406.2.4 umtsUarfcn . . . . .	512
8.407nas_umtsLTENbrCell Struct Reference . . . . .	512
8.407.1 Detailed Description . . . . .	512
8.407.2 Field Documentation . . . . .	513
8.407.2.1 cellsTDD . . . . .	513
8.407.2.2 earfcn . . . . .	513
8.407.2.3 pci . . . . .	513
8.407.2.4 rsrp . . . . .	513
8.407.2.5 rsrq . . . . .	513
8.407.2.6 srxlev . . . . .	513
8.408nas_UniversalTime Struct Reference . . . . .	513
8.408.1 Detailed Description . . . . .	514
8.408.2 Field Documentation . . . . .	515
8.408.2.1 day . . . . .	515
8.408.2.2 dayOfWeek . . . . .	515
8.408.2.3 hour . . . . .	515
8.408.2.4 minute . . . . .	515
8.408.2.5 month . . . . .	515
8.408.2.6 second . . . . .	515
8.408.2.7 year . . . . .	515
8.409nas_wcdmaCellInfo Struct Reference . . . . .	516
8.409.1 Detailed Description . . . . .	516
8.409.2 Field Documentation . . . . .	516
8.409.2.1 cpich_ecno . . . . .	516
8.409.2.2 cpich_rscp . . . . .	516
8.409.2.3 psc . . . . .	516
8.409.2.4 srxlev . . . . .	516
8.410nas_WCDMAECIOThresh Struct Reference . . . . .	516
8.410.1 Detailed Description . . . . .	517
8.410.2 Field Documentation . . . . .	517
8.410.2.1 pWCDMAECIOThreshList . . . . .	517
8.410.2.2 WCDMAECIOThreshListLen . . . . .	517
8.411nas_WCDMAInfoLTENeighborCell Struct Reference . . . . .	517
8.411.1 Detailed Description . . . . .	517
8.411.2 Field Documentation . . . . .	518
8.411.2.1 UMTSLTENbrCell . . . . .	518
8.411.2.2 umtsLTENbrCellLen . . . . .	518

8.411.2.3 wcdmaRRCState . . . . .	518
8.412nas_WCDMARSSIThresh Struct Reference . . . . .	518
8.412.1 Detailed Description . . . . .	518
8.412.2 Field Documentation . . . . .	519
8.412.2.1 pWCDMARSSIThreshList . . . . .	519
8.412.2.2 WCDMARSSIThreshListLen . . . . .	519
8.413nas_WCDMASysInfo Struct Reference . . . . .	519
8.413.1 Detailed Description . . . . .	519
8.413.2 Field Documentation . . . . .	522
8.413.2.1 cellId . . . . .	522
8.413.2.2 cellIdValid . . . . .	522
8.413.2.3 hsCallStatus . . . . .	522
8.413.2.4 hsCallStatusValid . . . . .	522
8.413.2.5 hsInd . . . . .	522
8.413.2.6 hsIndValid . . . . .	522
8.413.2.7 lac . . . . .	523
8.413.2.8 lacValid . . . . .	523
8.413.2.9 MCC . . . . .	523
8.413.2.10MNC . . . . .	523
8.413.2.11networkIdValid . . . . .	523
8.413.2.12psc . . . . .	523
8.413.2.13pscValid . . . . .	523
8.413.2.14regRejectInfoValid . . . . .	523
8.413.2.15rejCause . . . . .	523
8.413.2.16rejectSrvDomain . . . . .	523
8.413.2.17sysInfoWCDMA . . . . .	523
8.414NASBandPreferenceTlv Struct Reference . . . . .	523
8.414.1 Field Documentation . . . . .	523
8.414.1.1 band_pref . . . . .	523
8.414.1.2 TlvPresent . . . . .	523
8.415nasCellLocationInfoResp Struct Reference . . . . .	523
8.415.1 Detailed Description . . . . .	523
8.415.2 Field Documentation . . . . .	524
8.415.2.1 pCDMAInfo . . . . .	524
8.415.2.2 pGERANInfo . . . . .	524
8.415.2.3 pLTEInfoInterfreq . . . . .	524
8.415.2.4 pLTEInfoIntrafreq . . . . .	524
8.415.2.5 pLTEInfoNeighboringGSM . . . . .	524
8.415.2.6 pLTEInfoNeighboringWCDMA . . . . .	524
8.415.2.7 pUMTSCellID . . . . .	524

8.415.2.8 pUMTSInfo . . . . .	524
8.415.2.9 pWCDMAInfoLTENeighborCell . . . . .	524
8.416NASEmergencyModeTlv Struct Reference . . . . .	525
8.416.1 Field Documentation . . . . .	525
8.416.1.1 EmerMode . . . . .	525
8.416.1.2 TlvPresent . . . . .	525
8.417nasGet3GPP2SubscriptionInfoReq Struct Reference . . . . .	525
8.417.1 Detailed Description . . . . .	525
8.417.2 Field Documentation . . . . .	525
8.417.2.1 namID . . . . .	525
8.418nasGet3GPP2SubscriptionInfoResp Struct Reference . . . . .	525
8.418.1 Detailed Description . . . . .	525
8.418.2 Field Documentation . . . . .	526
8.418.2.1 pCDMAChannel . . . . .	526
8.418.2.2 pDirNum . . . . .	526
8.418.2.3 pHomeSIDNID . . . . .	526
8.418.2.4 pMinBasedIMSI . . . . .	526
8.418.2.5 pNAMNameInfo . . . . .	526
8.418.2.6 pTrueIMSI . . . . .	526
8.419nasGetHDRColorCodeResp Struct Reference . . . . .	526
8.419.1 Detailed Description . . . . .	526
8.419.2 Field Documentation . . . . .	527
8.419.2.1 pColorCode . . . . .	527
8.420nasGetLTECphyCa Struct Reference . . . . .	527
8.420.1 Field Documentation . . . . .	527
8.420.1.1 sPhyCaAggPcellInfo . . . . .	527
8.420.1.2 sPhyCaAggScellIDIBw . . . . .	527
8.420.1.3 sPhyCaAggScellIndex . . . . .	527
8.420.1.4 sPhyCaAggScellIndType . . . . .	527
8.420.1.5 sPhyCaAggScellInfo . . . . .	527
8.421NasGetLTECphyCaInfo Struct Reference . . . . .	527
8.421.1 Field Documentation . . . . .	527
8.421.1.1 PhyCaAggPcellInfo . . . . .	527
8.421.1.2 PhyCaAggScellIDIBw . . . . .	527
8.421.1.3 PhyCaAggScellIndex . . . . .	528
8.421.1.4 PhyCaAggScellIndType . . . . .	528
8.421.1.5 PhyCaAggScellInfo . . . . .	528
8.422nasGetLTECphyCaResp Struct Reference . . . . .	528
8.422.1 Field Documentation . . . . .	528
8.422.1.1 pPhyCaAggPcellInfo . . . . .	528



8.422.1.2 pPhyCaAggScellIDIBw . . . . .	528
8.422.1.3 pPhyCaAggScellIndex . . . . .	528
8.422.1.4 pPhyCaAggScellIndType . . . . .	528
8.422.1.5 pPhyCaAggScellInfo . . . . .	528
8.423nasGetSigInfoResp Struct Reference . . . . .	528
8.423.1 Detailed Description . . . . .	528
8.423.2 Field Documentation . . . . .	529
8.423.2.1 pCDMASSInfo . . . . .	529
8.423.2.2 pGSMSSInfo . . . . .	529
8.423.2.3 pHDRSSInfo . . . . .	529
8.423.2.4 pLTESSInfo . . . . .	529
8.423.2.5 pTDSCDMASigInfoExt . . . . .	529
8.423.2.6 pTDSCDMASigInfoRscp . . . . .	529
8.423.2.7 pWCDMASSInfo . . . . .	529
8.424nasGetSysInfoResp Struct Reference . . . . .	529
8.424.1 Detailed Description . . . . .	530
8.424.2 Field Documentation . . . . .	531
8.424.2.1 pAddCDMASysInfo . . . . .	531
8.424.2.2 pAddGSMSysInfo . . . . .	532
8.424.2.3 pAddHDRSysInfo . . . . .	532
8.424.2.4 pAddLTESysInfo . . . . .	532
8.424.2.5 pAddWCDMASysInfo . . . . .	532
8.424.2.6 pCDMASrvStatusInfo . . . . .	532
8.424.2.7 pCDMASysInfo . . . . .	532
8.424.2.8 pGSMCallBarringSysInfo . . . . .	532
8.424.2.9 pGSMCipherDomainSysInfo . . . . .	532
8.424.2.10pGSMStatusInfo . . . . .	532
8.424.2.11pGSMStatusInfo . . . . .	532
8.424.2.12pHDRSrvStatusInfo . . . . .	532
8.424.2.13pHDRSysInfo . . . . .	532
8.424.2.14pLTESrvStatusInfo . . . . .	532
8.424.2.15pLTESysInfo . . . . .	532
8.424.2.16pLTEVoiceSupportSysInfo . . . . .	532
8.424.2.17pWCDMACallBarringSysInfo . . . . .	532
8.424.2.18pWCDMACipherDomainSysInfo . . . . .	532
8.424.2.19pWCDMASrvStatusInfo . . . . .	532
8.424.2.20pWCDMASysInfo . . . . .	532
8.425nasGetTxRxInfoReq Struct Reference . . . . .	532
8.425.1 Detailed Description . . . . .	532
8.425.2 Field Documentation . . . . .	533

8.425.2.1 radio_if . . . . .	533
8.426nasGetTxRxInfoResp Struct Reference . . . . .	533
8.426.1 Detailed Description . . . . .	533
8.426.2 Field Documentation . . . . .	533
8.426.2.1 pRXChain0Info . . . . .	533
8.426.2.2 pRXChain1Info . . . . .	533
8.426.2.3 pTXInfo . . . . .	533
8.427NASGWAcqOrderPrefTlv Struct Reference . . . . .	534
8.427.1 Field Documentation . . . . .	534
8.427.1.1 GWAcqOrderPref . . . . .	534
8.427.1.2 TlvPresent . . . . .	534
8.428nasIndicationRegisterReq Struct Reference . . . . .	534
8.428.1 Detailed Description . . . . .	534
8.428.2 Field Documentation . . . . .	537
8.428.2.1 pDDTMInd . . . . .	537
8.428.2.2 pDualStandByPrefInd . . . . .	537
8.428.2.3 pErrorRateInd . . . . .	537
8.428.2.4 pHDRNewUATIAssInd . . . . .	537
8.428.2.5 pHDRSessionCloseInd . . . . .	537
8.428.2.6 pLTECphyCa . . . . .	537
8.428.2.7 pManagedRoamingInd . . . . .	537
8.428.2.8 pNetworkTimeInd . . . . .	537
8.428.2.9 pServingSystemInd . . . . .	537
8.428.2.10pSignalStrengthInd . . . . .	537
8.428.2.11pSubscriptionInfoInd . . . . .	537
8.428.2.12pSysInfoInd . . . . .	537
8.428.2.13pSystemSelectionInd . . . . .	537
8.429nasInitNetworkReg Struct Reference . . . . .	537
8.429.1 Detailed Description . . . . .	537
8.429.2 Field Documentation . . . . .	538
8.429.2.1 pChangeDuration . . . . .	538
8.429.2.2 pMncPcsDigitStatus . . . . .	538
8.429.2.3 pMNRInfo . . . . .	538
8.429.2.4 regAction . . . . .	538
8.430NASLTEBandPreferenceTlv Struct Reference . . . . .	538
8.430.1 Field Documentation . . . . .	538
8.430.1.1 LTEBandPref . . . . .	538
8.430.1.2 TlvPresent . . . . .	538
8.431NASLteNasReleaseInfoTlv Struct Reference . . . . .	539
8.431.1 Field Documentation . . . . .	539

8.431.1.1 nas_major	539
8.431.1.2 nas_minor	539
8.431.1.3 nas_release	539
8.431.1.4 TlvPresent	539
8.432NASModePreferenceTlv Struct Reference	539
8.432.1 Field Documentation	539
8.432.1.1 ModePref	539
8.432.1.2 TlvPresent	539
8.433NASNetSelPreferenceTlv Struct Reference	539
8.433.1 Field Documentation	539
8.433.1.1 NetSelPref	539
8.433.1.2 TlvPresent	539
8.434nasNetworkTime Struct Reference	539
8.434.1 Detailed Description	540
8.434.2 Field Documentation	540
8.434.2.1 pDayltSavAdj	540
8.434.2.2 pRadioInterface	540
8.434.2.3 pTimeZone	540
8.434.2.4 universalTime	540
8.435nasOperatorNameResp Struct Reference	540
8.435.1 Detailed Description	541
8.435.2 Field Documentation	541
8.435.2.1 pNITZInformation	541
8.435.2.2 pOperatorNameString	541
8.435.2.3 pOperatorPLMNList	541
8.435.2.4 pPLMNNetworkName	541
8.435.2.5 pSrcvProviderName	541
8.436NASOTAMessageTlv Struct Reference	541
8.436.1 Field Documentation	542
8.436.1.1 data_buf	542
8.436.1.2 data_len	542
8.436.1.3 message_type	542
8.436.1.4 TlvPresent	542
8.437NASPhyCaAggPcellInfo Struct Reference	542
8.437.1 Detailed Description	542
8.437.2 Field Documentation	543
8.437.2.1 dl_bw_value	543
8.437.2.2 freq	543
8.437.2.3 iLTEbandValue	543
8.437.2.4 pci	543

8.437.2.5 TlvPresent . . . . .	543
8.438NASPhyCaAggScellIDBw Struct Reference . . . . .	543
8.438.1 Detailed Description . . . . .	543
8.438.2 Field Documentation . . . . .	543
8.438.2.1 dl_bw_value . . . . .	543
8.438.2.2 TlvPresent . . . . .	543
8.439NASPhyCaAggScellIndex Struct Reference . . . . .	543
8.439.1 Detailed Description . . . . .	543
8.439.2 Field Documentation . . . . .	544
8.439.2.1 scell_idx . . . . .	544
8.439.2.2 TlvPresent . . . . .	544
8.440NASPhyCaAggScellIndType Struct Reference . . . . .	544
8.440.1 Detailed Description . . . . .	544
8.440.2 Field Documentation . . . . .	544
8.440.2.1 freq . . . . .	544
8.440.2.2 pci . . . . .	545
8.440.2.3 scell_state . . . . .	545
8.440.2.4 TlvPresent . . . . .	545
8.441NASPhyCaAggScellInfo Struct Reference . . . . .	545
8.441.1 Detailed Description . . . . .	545
8.441.2 Field Documentation . . . . .	545
8.441.2.1 dl_bw_value . . . . .	546
8.441.2.2 freq . . . . .	546
8.441.2.3 iLTEbandValue . . . . .	546
8.441.2.4 pci . . . . .	546
8.441.2.5 scell_state . . . . .	546
8.441.2.6 TlvPresent . . . . .	546
8.442nasPLMNNameReq Struct Reference . . . . .	546
8.442.1 Detailed Description . . . . .	546
8.442.2 Field Documentation . . . . .	546
8.442.2.1 mcc . . . . .	546
8.442.2.2 mnc . . . . .	547
8.442.2.3 pMncPcsStatus . . . . .	547
8.443nasPLMNNameResp Struct Reference . . . . .	547
8.443.1 Detailed Description . . . . .	547
8.443.2 Field Documentation . . . . .	549
8.443.2.1 longName . . . . .	549
8.443.2.2 longNameCI . . . . .	549
8.443.2.3 longNameEn . . . . .	549
8.443.2.4 longNameLen . . . . .	549

8.443.2.5 longNameSB . . . . .	549
8.443.2.6 shortName . . . . .	549
8.443.2.7 shortNameCI . . . . .	549
8.443.2.8 shortNameEn . . . . .	549
8.443.2.9 shortNameLen . . . . .	549
8.443.2.10shortNameSB . . . . .	549
8.443.2.11spn . . . . .	549
8.443.2.12spnEncoding . . . . .	549
8.443.2.13spnLength . . . . .	549
8.444NASPRLPreferenceTlv Struct Reference . . . . .	549
8.444.1 Field Documentation . . . . .	549
8.444.1.1 PRLPref . . . . .	549
8.444.1.2 TlvPresent . . . . .	549
8.445NASQmiCbkNasSwiOTAMessageInd Struct Reference . . . . .	549
8.445.1 Field Documentation . . . . .	550
8.445.1.1 nasRelInfoTlv . . . . .	550
8.445.1.2 otaMsgTlv . . . . .	550
8.445.1.3 timeTlv . . . . .	550
8.446NASQmiCbkNasSystemSelPrefInd Struct Reference . . . . .	550
8.446.1 Field Documentation . . . . .	550
8.446.1.1 BPTlv . . . . .	550
8.446.1.2 EMTlv . . . . .	550
8.446.1.3 GWAOPTlv . . . . .	550
8.446.1.4 LBPTlv . . . . .	550
8.446.1.5 MPTlv . . . . .	550
8.446.1.6 NSPTlv . . . . .	550
8.446.1.7 PRLPTlv . . . . .	550
8.446.1.8 RPTlv . . . . .	550
8.446.1.9 SDPTlv . . . . .	550
8.447NASRoamPreferenceTlv Struct Reference . . . . .	550
8.447.1 Field Documentation . . . . .	550
8.447.1.1 RoamPref . . . . .	550
8.447.1.2 TlvPresent . . . . .	551
8.448NASServDomainPrefTlv Struct Reference . . . . .	551
8.448.1 Field Documentation . . . . .	551
8.448.1.1 SrvDomainPref . . . . .	551
8.448.1.2 TlvPresent . . . . .	551
8.449NASServingSystemInfo Struct Reference . . . . .	551
8.449.1 Detailed Description . . . . .	551
8.449.2 Field Documentation . . . . .	552

8.449.2.1 csAttachState . . . . .	552
8.449.2.2 hdrPersonality . . . . .	552
8.449.2.3 psAttachState . . . . .	552
8.449.2.4 radiolInterfaceList . . . . .	552
8.449.2.5 radiolInterfaceNo . . . . .	553
8.449.2.6 registrationState . . . . .	553
8.449.2.7 selectedNetwork . . . . .	553
8.450nasSigInfo Struct Reference . . . . .	553
8.450.1 Detailed Description . . . . .	553
8.450.2 Field Documentation . . . . .	553
8.450.2.1 pCDMASigInfo . . . . .	553
8.450.2.2 pGSMSigInfo . . . . .	554
8.450.2.3 pHDRSigInfo . . . . .	554
8.450.2.4 pLTESigInfo . . . . .	554
8.450.2.5 pRscp . . . . .	554
8.450.2.6 pTDSCDMASigInfoExt . . . . .	554
8.450.2.7 pWCDMASigInfo . . . . .	554
8.451nasSwiGetChannelLockResp Struct Reference . . . . .	554
8.451.1 Detailed Description . . . . .	554
8.451.2 Field Documentation . . . . .	554
8.451.2.1 pLteEARFCN . . . . .	554
8.451.2.2 pLtePCI . . . . .	554
8.451.2.3 pWcdmaUARFCN . . . . .	554
8.452NasSwiIndReg Struct Reference . . . . .	554
8.452.1 Detailed Description . . . . .	555
8.452.2 Field Documentation . . . . .	555
8.452.2.1 gsmUmtsDI . . . . .	555
8.452.2.2 gsmUmtsUI . . . . .	555
8.452.2.3 lteEmmDI . . . . .	555
8.452.2.4 lteEmmUI . . . . .	555
8.452.2.5 lteEsmDI . . . . .	556
8.452.2.6 lteEsmUI . . . . .	556
8.452.2.7 pRankIndicatorInd . . . . .	556
8.453nasSwiSetChannelLockReq Struct Reference . . . . .	556
8.453.1 Detailed Description . . . . .	556
8.453.2 Field Documentation . . . . .	556
8.453.2.1 pLteEARFCN . . . . .	556
8.453.2.2 pLtePCI . . . . .	556
8.453.2.3 pWcdmaUARFCN . . . . .	556
8.454nasSysInfo Struct Reference . . . . .	556

8.454.1 Detailed Description . . . . .	557
8.454.2 Field Documentation . . . . .	559
8.454.2.1 pAddCDMASysInfo . . . . .	559
8.454.2.2 pAddGSMSysInfo . . . . .	559
8.454.2.3 pAddHDRSysInfo . . . . .	559
8.454.2.4 pAddLTESysInfo . . . . .	559
8.454.2.5 pAddWCDMASysInfo . . . . .	559
8.454.2.6 pCDMASrvStatusInfo . . . . .	559
8.454.2.7 pCDMASysInfo . . . . .	559
8.454.2.8 pGSMCallBarringSysInfo . . . . .	559
8.454.2.9 pGSMCipherDomainSysInfo . . . . .	559
8.454.2.10pGSMSrvStatusInfo . . . . .	559
8.454.2.11pGSMSysInfo . . . . .	559
8.454.2.12pHDRSrvStatusInfo . . . . .	559
8.454.2.13pHDRSysInfo . . . . .	559
8.454.2.14pLTESrvStatusInfo . . . . .	559
8.454.2.15pLTESysInfo . . . . .	559
8.454.2.16pLTEVoiceSupportSysInfo . . . . .	559
8.454.2.17pSysInfoNoChange . . . . .	559
8.454.2.18pWCDMACallBarringSysInfo . . . . .	559
8.454.2.19pWCDMACipherDomainSysInfo . . . . .	559
8.454.2.20pWCDMASrvStatusInfo . . . . .	559
8.454.2.21pWCDMASysInfo . . . . .	559
8.455NASTimeInfoTlv Struct Reference . . . . .	559
8.455.1 Field Documentation . . . . .	559
8.455.1.1 time . . . . .	559
8.455.1.2 TlvPresent . . . . .	560
8.456netSelectionPref Struct Reference . . . . .	560
8.456.1 Detailed Description . . . . .	560
8.456.2 Field Documentation . . . . .	560
8.456.2.1 mcc . . . . .	560
8.456.2.2 mnc . . . . .	560
8.456.2.3 netReg . . . . .	560
8.457NetStats Struct Reference . . . . .	560
8.457.1 Detailed Description . . . . .	561
8.457.2 Field Documentation . . . . .	561
8.457.2.1 rx_bytes . . . . .	561
8.457.2.2 rx_errors . . . . .	561
8.457.2.3 rx_overflows . . . . .	561
8.457.2.4 rx_packets . . . . .	561

8.457.2.5 tx_bytes . . . . .	561
8.457.2.6 tx_errors . . . . .	561
8.457.2.7 tx_overflows . . . . .	561
8.457.2.8 tx_packets . . . . .	561
8.458NetworkDebugResp Struct Reference . . . . .	561
8.458.1 Detailed Description . . . . .	562
8.458.2 Field Documentation . . . . .	562
8.458.2.1 pDataStatusDetail . . . . .	562
8.458.2.2 pDeviceConfigDetail . . . . .	562
8.458.2.3 pNetworkStat1x . . . . .	562
8.458.2.4 pNetworkStatEVDO . . . . .	562
8.458.2.5 pObjectVer . . . . .	562
8.459NetworkStat1x Struct Reference . . . . .	562
8.459.1 Detailed Description . . . . .	563
8.459.2 Field Documentation . . . . .	565
8.459.2.1 ActSetCnt . . . . .	565
8.459.2.2 NeighborSetCnt . . . . .	565
8.459.2.3 pActPilotPNElements . . . . .	565
8.459.2.4 pNeighborSetPilotPN . . . . .	565
8.459.2.5 RX_EC_IO . . . . .	565
8.459.2.6 RX_PWR . . . . .	565
8.459.2.7 SO . . . . .	565
8.459.2.8 State . . . . .	565
8.459.2.9 TX_PWR . . . . .	565
8.460NetworkStatEVDO Struct Reference . . . . .	565
8.460.1 Detailed Description . . . . .	565
8.460.2 Field Documentation . . . . .	567
8.460.2.1 MACIndex . . . . .	567
8.460.2.2 PER . . . . .	567
8.460.2.3 PilotEnergy . . . . .	567
8.460.2.4 pSectorID . . . . .	567
8.460.2.5 RX_PWR . . . . .	567
8.460.2.6 SectorIDLen . . . . .	567
8.460.2.7 SNR . . . . .	567
8.460.2.8 State . . . . .	567
8.461newMTMessageTlv Struct Reference . . . . .	567
8.461.1 Detailed Description . . . . .	567
8.461.2 Field Documentation . . . . .	568
8.461.2.1 MTMessageInfo . . . . .	568
8.461.2.2 TlvPresent . . . . .	568



8.462newPwdData Struct Reference . . . . .	568
8.462.1 Detailed Description . . . . .	568
8.462.2 Field Documentation . . . . .	568
8.462.2.1 newPwd . . . . .	568
8.462.2.2 newPwdAgain . . . . .	568
8.463nmrCellInfo Struct Reference . . . . .	568
8.463.1 Detailed Description . . . . .	569
8.463.2 Field Documentation . . . . .	570
8.463.2.1 nmrArfcn . . . . .	570
8.463.2.2 nmrBsic . . . . .	570
8.463.2.3 nmrCellID . . . . .	570
8.463.2.4 nmrLac . . . . .	571
8.463.2.5 nmrPlmn . . . . .	571
8.463.2.6 nmrRxLev . . . . .	571
8.464NSSAudioCtrl Struct Reference . . . . .	571
8.464.1 Detailed Description . . . . .	571
8.464.2 Field Documentation . . . . .	571
8.464.2.1 downLink . . . . .	571
8.464.2.2 upLink . . . . .	571
8.465NWProfile Struct Reference . . . . .	571
8.465.1 Detailed Description . . . . .	571
8.465.2 Field Documentation . . . . .	572
8.465.2.1 pProfSz . . . . .	572
8.465.2.2 pProfValues . . . . .	572
8.465.2.3 tech . . . . .	572
8.466omaDmConfigTlv Struct Reference . . . . .	572
8.466.1 Detailed Description . . . . .	572
8.466.2 Field Documentation . . . . .	572
8.466.2.1 alertmsg . . . . .	572
8.466.2.2 alertmsglength . . . . .	573
8.466.2.3 state . . . . .	573
8.466.2.4 userInputReq . . . . .	573
8.466.2.5 userInputTimeout . . . . .	573
8.467omaDmConfigTlvExt Struct Reference . . . . .	573
8.467.1 Detailed Description . . . . .	573
8.467.2 Field Documentation . . . . .	575
8.467.2.1 alertmsg . . . . .	575
8.467.2.2 alertmsglength . . . . .	575
8.467.2.3 state . . . . .	575
8.467.2.4 userInputReq . . . . .	575

8.467.2.5 userInputTimeout . . . . .	575
8.468omaDmFotaTlv Struct Reference . . . . .	575
8.468.1 Detailed Description . . . . .	575
8.468.2 Field Documentation . . . . .	577
8.468.2.1 description . . . . .	577
8.468.2.2 descriptionlength . . . . .	577
8.468.2.3 fwdloadsize . . . . .	577
8.468.2.4 fwloadComplete . . . . .	577
8.468.2.5 namelength . . . . .	577
8.468.2.6 package_name . . . . .	577
8.468.2.7 sessionType . . . . .	577
8.468.2.8 severity . . . . .	577
8.468.2.9 state . . . . .	577
8.468.2.10updateCompleteStatus . . . . .	577
8.468.2.11userInputReq . . . . .	577
8.468.2.12userInputTimeout . . . . .	577
8.468.2.13version . . . . .	577
8.468.2.14versionlength . . . . .	577
8.469omaDmFotaTlvExt Struct Reference . . . . .	577
8.469.1 Detailed Description . . . . .	578
8.469.2 Field Documentation . . . . .	579
8.469.2.1 description . . . . .	579
8.469.2.2 descriptionlength . . . . .	579
8.469.2.3 fumoResultCode . . . . .	579
8.469.2.4 namelength . . . . .	579
8.469.2.5 package_name . . . . .	579
8.469.2.6 packageSize . . . . .	579
8.469.2.7 receivedBytes . . . . .	579
8.469.2.8 reserved . . . . .	580
8.469.2.9 state . . . . .	580
8.469.2.10userInputTimeout . . . . .	580
8.469.2.11version . . . . .	580
8.469.2.12versionlength . . . . .	580
8.470omaDmNotificationsTlv Struct Reference . . . . .	580
8.470.1 Field Documentation . . . . .	580
8.470.1.1 notification . . . . .	580
8.470.1.2 sessionStatus . . . . .	580
8.471operatorNameString Struct Reference . . . . .	580
8.471.1 Detailed Description . . . . .	580
8.471.2 Field Documentation . . . . .	580

8.471.2.1 PLMNName . . . . .	580
8.472OperatorPLMNData Struct Reference . . . . .	580
8.472.1 Detailed Description . . . . .	581
8.472.2 Field Documentation . . . . .	581
8.472.2.1 lac1 . . . . .	581
8.472.2.2 lac2 . . . . .	581
8.472.2.3 mcc . . . . .	581
8.472.2.4 mnc . . . . .	581
8.472.2.5 PLMNRecID . . . . .	581
8.473operatorPLMNList Struct Reference . . . . .	581
8.473.1 Detailed Description . . . . .	581
8.473.2 Field Documentation . . . . .	582
8.473.2.1 numInstance . . . . .	582
8.473.2.2 PLMNData . . . . .	582
8.474pack_dms_GetCustFeaturesV2_t Struct Reference . . . . .	582
8.474.1 Detailed Description . . . . .	582
8.474.2 Field Documentation . . . . .	582
8.474.2.1 cust_id . . . . .	582
8.474.2.2 list_type . . . . .	582
8.474.2.3 Tlvresult . . . . .	582
8.475pack_dms_SetCrashAction_t Struct Reference . . . . .	582
8.475.1 Detailed Description . . . . .	583
8.475.2 Field Documentation . . . . .	583
8.475.2.1 crashAction . . . . .	583
8.476pack_dms_SetCustFeature_t Struct Reference . . . . .	583
8.476.1 Field Documentation . . . . .	583
8.476.1.1 DHCPRelayEnabled . . . . .	583
8.476.1.2 DisableIMSI . . . . .	583
8.476.1.3 GpsEnable . . . . .	583
8.476.1.4 GPSLPM . . . . .	583
8.476.1.5 GPSSel . . . . .	583
8.476.1.6 IPFamSupport . . . . .	583
8.476.1.7 IsVoiceEnabled . . . . .	583
8.476.1.8 RMAutoConnect . . . . .	584
8.476.1.9 SMSSupport . . . . .	584
8.477pack_dms_SetCustFeaturesV2_t Struct Reference . . . . .	584
8.477.1 Detailed Description . . . . .	584
8.477.2 Field Documentation . . . . .	584
8.477.2.1 cust_id . . . . .	584
8.477.2.2 cust_value . . . . .	584

8.477.2.3 Tlvresult . . . . .	584
8.477.2.4 value_length . . . . .	584
8.478pack_dms_SetEventReport_t Struct Reference . . . . .	584
8.478.1 Field Documentation . . . . .	584
8.478.1.1 mode . . . . .	584
8.479pack_dms_SetPower_t Struct Reference . . . . .	585
8.479.1 Field Documentation . . . . .	585
8.479.1.1 mode . . . . .	585
8.479.1.2 Tlvresult . . . . .	585
8.480pack_dms_SetUSBComp_t Struct Reference . . . . .	585
8.480.1 Field Documentation . . . . .	585
8.480.1.1 Tlvresult . . . . .	585
8.480.1.2 USBComp . . . . .	585
8.481pack_dms_SLQSDmsSwiIndicationRegister_t Struct Reference . . . . .	585
8.481.1 Detailed Description . . . . .	585
8.481.2 Field Documentation . . . . .	585
8.481.2.1 resetInfoInd . . . . .	585
8.482pack_dms_SLQSSwiSetDyingGaspCfg_t Struct Reference . . . . .	585
8.482.1 Detailed Description . . . . .	586
8.482.2 Field Documentation . . . . .	586
8.482.2.1 pDestSMSContent . . . . .	586
8.482.2.2 pDestSMSNum . . . . .	586
8.483pack_dms_UIMGetICCID_t Struct Reference . . . . .	586
8.483.1 Detailed Description . . . . .	586
8.483.2 Field Documentation . . . . .	586
8.483.2.1 Tlvresult . . . . .	586
8.484pack_fms_GetImagesPreference_t Struct Reference . . . . .	586
8.484.1 Detailed Description . . . . .	587
8.484.2 Field Documentation . . . . .	588
8.484.2.1 Tlvresult . . . . .	588
8.485pack_fms_GetStoredImages_t Struct Reference . . . . .	588
8.485.1 Detailed Description . . . . .	588
8.485.2 Field Documentation . . . . .	588
8.485.2.1 Tlvresult . . . . .	588
8.486pack_fms_SetImagesPreference_t Struct Reference . . . . .	588
8.486.1 Detailed Description . . . . .	588
8.486.2 Field Documentation . . . . .	589
8.486.2.1 bForceDownload . . . . .	589
8.486.2.2 imageListSize . . . . .	589
8.486.2.3 modemindex . . . . .	589

8.486.2.4 pImageList . . . . .	589
8.486.2.5 Tlvresult . . . . .	589
8.487pack_loc_Delete_Assist_Data_t Struct Reference . . . . .	589
8.487.1 Detailed Description . . . . .	589
8.487.2 Field Documentation . . . . .	590
8.487.2.1 pBdsSVInfo . . . . .	590
8.487.2.2 pCellDb . . . . .	590
8.487.2.3 pClkInfo . . . . .	590
8.487.2.4 pGnssData . . . . .	590
8.487.2.5 pSVInfo . . . . .	590
8.487.2.6 Tlvresult . . . . .	590
8.488pack_loc_EventRegister_t Struct Reference . . . . .	590
8.488.1 Detailed Description . . . . .	590
8.488.2 Field Documentation . . . . .	592
8.488.2.1 eventRegister . . . . .	592
8.488.2.2 Tlvresult . . . . .	592
8.489pack_loc_SetExtPowerState_t Struct Reference . . . . .	592
8.489.1 Detailed Description . . . . .	592
8.489.2 Field Documentation . . . . .	592
8.489.2.1 extPowerState . . . . .	592
8.489.2.2 Tlvresult . . . . .	592
8.490pack_loc_SetOperationMode_t Struct Reference . . . . .	592
8.490.1 Detailed Description . . . . .	593
8.490.2 Field Documentation . . . . .	593
8.490.2.1 mode . . . . .	593
8.490.2.2 Tlvresult . . . . .	593
8.491pack_loc_Start_t Struct Reference . . . . .	593
8.491.1 Detailed Description . . . . .	593
8.491.2 Field Documentation . . . . .	595
8.491.2.1 pApplicationInfo . . . . .	595
8.491.2.2 pConfigAltitudeAssumed . . . . .	595
8.491.2.3 pHorizontalAccuracyLvl . . . . .	595
8.491.2.4 pIntermediateReportState . . . . .	595
8.491.2.5 pMinIntervalTime . . . . .	595
8.491.2.6 pRecurrenceType . . . . .	595
8.491.2.7 SessionId . . . . .	595
8.491.2.8 Tlvresult . . . . .	595
8.492pack_loc_Stop_t Struct Reference . . . . .	595
8.492.1 Detailed Description . . . . .	595
8.492.2 Field Documentation . . . . .	595

8.492.2.1 SessionId . . . . .	595
8.492.2.2 Tlvresult . . . . .	595
8.493pack_nas_SetACCOLC_t Struct Reference . . . . .	595
8.493.1 Detailed Description . . . . .	596
8.493.2 Field Documentation . . . . .	597
8.493.2.1 accolc . . . . .	597
8.493.2.2 spc . . . . .	597
8.494pack_nas_SetNetworkPreference_t Struct Reference . . . . .	597
8.494.1 Detailed Description . . . . .	597
8.494.2 Field Documentation . . . . .	598
8.494.2.1 Duration . . . . .	598
8.494.2.2 TechnologyPref . . . . .	598
8.494.2.3 Tlvresult . . . . .	598
8.495pack_nas_SLQSGetPLMNName_t Struct Reference . . . . .	598
8.495.1 Detailed Description . . . . .	598
8.495.2 Field Documentation . . . . .	599
8.495.2.1 mcc . . . . .	599
8.495.2.2 mnc . . . . .	599
8.495.2.3 pMncPcsStatus . . . . .	599
8.496pack_nas_SLQSIInitiateNetworkRegistration_t Struct Reference . . . . .	599
8.496.1 Detailed Description . . . . .	599
8.496.2 Field Documentation . . . . .	600
8.496.2.1 pChangeDuration . . . . .	600
8.496.2.2 pMncPcsDigitStatus . . . . .	600
8.496.2.3 pMNRInfo . . . . .	600
8.496.2.4 regAction . . . . .	600
8.497pack_nas_SLQSNasConfigSigInfo2_t Struct Reference . . . . .	600
8.497.1 Detailed Description . . . . .	602
8.497.2 Field Documentation . . . . .	604
8.497.2.1 pCDMAECIODelta . . . . .	604
8.497.2.2 pCDMAECIOThresh . . . . .	604
8.497.2.3 pCDMARSSIDelta . . . . .	604
8.497.2.4 pCDMARSSIThresh . . . . .	604
8.497.2.5 pGSMRSSIDelta . . . . .	604
8.497.2.6 pGSMRSSIThresh . . . . .	604
8.497.2.7 pHDRECIODelta . . . . .	604
8.497.2.8 pHDRECIOTresh . . . . .	604
8.497.2.9 pHDRIODelta . . . . .	605
8.497.2.10pHDIOTresh . . . . .	605
8.497.2.11pHDRRSSIDelta . . . . .	605

8.497.2.12	pHDRRSSIthresh . . . . .	605
8.497.2.13	pHDRSINRDelta . . . . .	605
8.497.2.14	pHDRSINRThresh . . . . .	605
8.497.2.15	pLTERSRPDelta . . . . .	605
8.497.2.16	pLTERSRPThresh . . . . .	605
8.497.2.17	pLTERSRQDelta . . . . .	605
8.497.2.18	pLTERSRQThresh . . . . .	605
8.497.2.19	pLTERSSIDelta . . . . .	605
8.497.2.20	pLTERSSIthresh . . . . .	605
8.497.2.21	pLTESigRptConfig . . . . .	605
8.497.2.22	pLTESNRDelta . . . . .	605
8.497.2.23	pLTESNRThresh . . . . .	605
8.497.2.24	pTDSCDMAECIODelta . . . . .	605
8.497.2.25	pTDSCDMAECIOThresh . . . . .	605
8.497.2.26	pTDSCDMARSCPDelta . . . . .	605
8.497.2.27	pTDSCDMARSCPThresh . . . . .	605
8.497.2.28	pTDSCDMARSSIDelta . . . . .	605
8.497.2.29	pTDSCDMARSSIthresh . . . . .	605
8.497.2.30	pTDSCMASINRDelta . . . . .	605
8.497.2.31	pTDSCMASINRThresh . . . . .	605
8.497.2.32	pWCDMAECIODelta . . . . .	605
8.497.2.33	pWCDMAECIOThresh . . . . .	605
8.497.2.34	pWCDMARSSIDelta . . . . .	605
8.497.2.35	pWCDMARSSIthresh . . . . .	605
8.498	pack_nas_SLQSNasIndicationRegisterExt_t Struct Reference . . . . .	605
8.498.1	Detailed Description . . . . .	606
8.498.2	Field Documentation . . . . .	608
8.498.2.1	pDDTMInd . . . . .	608
8.498.2.2	pDualStandByPrefInd . . . . .	608
8.498.2.3	pErrorRateInd . . . . .	608
8.498.2.4	pHDRNewUATIAssInd . . . . .	608
8.498.2.5	pHDRSessionCloseInd . . . . .	609
8.498.2.6	pLTECphyCa . . . . .	609
8.498.2.7	pManagedRoamingInd . . . . .	609
8.498.2.8	pNetworkTimeInd . . . . .	609
8.498.2.9	pServingSystemInd . . . . .	609
8.498.2.10	pSignalStrengthInd . . . . .	609
8.498.2.11	pSubscriptionInfoInd . . . . .	609
8.498.2.12	pSysInfoInd . . . . .	609
8.498.2.13	pSystemSelectionInd . . . . .	609

8.499	<a href="#">pack_nas_SLQSNasSwiOTAMessageCallback_t Struct Reference</a>	609
8.499.1	Detailed Description	609
8.499.2	Field Documentation	610
8.499.2.1	<a href="#">gsmUmtsDI</a>	610
8.499.2.2	<a href="#">gsmUmtsUI</a>	610
8.499.2.3	<a href="#">lteEmmDI</a>	610
8.499.2.4	<a href="#">lteEmmUI</a>	610
8.499.2.5	<a href="#">lteEsmDI</a>	610
8.499.2.6	<a href="#">lteEsmUI</a>	610
8.499.2.7	<a href="#">pRankIndicatorInd</a>	610
8.500	<a href="#">pack_nas_SLQSSetSignalStrengthsCallback_t Struct Reference</a>	610
8.500.1	Detailed Description	611
8.500.2	Field Documentation	611
8.500.2.1	<a href="#">bEnable</a>	611
8.500.2.2	<a href="#">pSigIndReq</a>	611
8.501	<a href="#">pack_nas_SLQSSetSysSelectionPref_t Struct Reference</a>	611
8.501.1	Detailed Description	611
8.501.2	Field Documentation	614
8.501.2.1	<a href="#">pAcqOrderPref</a>	614
8.501.2.2	<a href="#">pBandPref</a>	614
8.501.2.3	<a href="#">pChgDuration</a>	615
8.501.2.4	<a href="#">pCSGID</a>	615
8.501.2.5	<a href="#">pEmerMode</a>	615
8.501.2.6	<a href="#">pGWAcqOrderPref</a>	615
8.501.2.7	<a href="#">pLTEBandPref</a>	615
8.501.2.8	<a href="#">pMNCIncPCSDigStat</a>	615
8.501.2.9	<a href="#">pModePref</a>	615
8.501.2.10	<a href="#">pNetSelPref</a>	615
8.501.2.11	<a href="#">pPRLPref</a>	615
8.501.2.12	<a href="#">pRAT</a>	615
8.501.2.13	<a href="#">pRoamPref</a>	615
8.501.2.14	<a href="#">pSrvDomainPref</a>	615
8.501.2.15	<a href="#">pSrvRegRestriction</a>	615
8.501.2.16	<a href="#">pTdsdmaBandPref</a>	615
8.502	<a href="#">pack_qmi_t Struct Reference</a>	615
8.502.1	Detailed Description	615
8.502.2	Field Documentation	615
8.502.2.1	<a href="#">msgid</a>	615
8.502.2.2	<a href="#">svc</a>	615
8.502.2.3	<a href="#">timeout</a>	616



8.502.2.4 xid . . . . .	616
8.503pack_qos_SLQSQosSwiReadApnExtraParams_t Struct Reference . . . . .	616
8.503.1 Detailed Description . . . . .	616
8.503.2 Field Documentation . . . . .	616
8.503.2.1 apnId . . . . .	616
8.504pack_qos_SLQSQosSwiReadDataStats_t Struct Reference . . . . .	616
8.504.1 Detailed Description . . . . .	616
8.504.2 Field Documentation . . . . .	616
8.504.2.1 apnId . . . . .	616
8.505pack_qos_SLQSSetQosEventCallback_t Struct Reference . . . . .	616
8.505.1 Detailed Description . . . . .	617
8.505.2 Field Documentation . . . . .	618
8.505.2.1 enable . . . . .	618
8.506pack_sms_SendSMS_t Struct Reference . . . . .	618
8.506.1 Detailed Description . . . . .	618
8.506.2 Field Documentation . . . . .	618
8.506.2.1 messageFormat . . . . .	618
8.506.2.2 messageSize . . . . .	618
8.506.2.3 pLinktimer . . . . .	618
8.506.2.4 pMessage . . . . .	618
8.507pack_sms_SetNewSMSCallback_t Struct Reference . . . . .	619
8.507.1 Detailed Description . . . . .	619
8.507.2 Field Documentation . . . . .	619
8.507.2.1 status . . . . .	619
8.508pack_sms_SLQSDeleteSMS_t Struct Reference . . . . .	619
8.508.1 Detailed Description . . . . .	620
8.508.2 Field Documentation . . . . .	620
8.508.2.1 pMessageIndex . . . . .	620
8.508.2.2 pMessageMode . . . . .	620
8.508.2.3 pMessageTag . . . . .	620
8.508.2.4 storageType . . . . .	620
8.509pack_sms_SLQSGetSMS_t Struct Reference . . . . .	620
8.509.1 Detailed Description . . . . .	620
8.509.2 Field Documentation . . . . .	621
8.509.2.1 messageIndex . . . . .	621
8.509.2.2 pMessageMode . . . . .	621
8.509.2.3 storageType . . . . .	621
8.510pack_sms_SLQSGetSMSList_t Struct Reference . . . . .	621
8.510.1 Detailed Description . . . . .	621
8.510.2 Field Documentation . . . . .	622

8.510.2.1 pMessageMode . . . . .	622
8.510.2.2 pRequestedTag . . . . .	622
8.510.2.3 storageType . . . . .	622
8.511 pack_sms_SLQSMModifySMSStatus_t Struct Reference . . . . .	622
8.511.1 Detailed Description . . . . .	623
8.511.2 Field Documentation . . . . .	623
8.511.2.1 messageIndex . . . . .	623
8.511.2.2 messageTag . . . . .	623
8.511.2.3 pMessageMode . . . . .	623
8.511.2.4 storageType . . . . .	623
8.512 pack_swilloc_SwiLocSetAutoStart_t Struct Reference . . . . .	623
8.512.1 Detailed Description . . . . .	623
8.512.2 Field Documentation . . . . .	625
8.512.2.1 fix_rate . . . . .	625
8.512.2.2 fix_type . . . . .	625
8.512.2.3 function . . . . .	625
8.512.2.4 max_dist . . . . .	625
8.512.2.5 max_time . . . . .	625
8.512.2.6 set_fix_rate . . . . .	625
8.512.2.7 set_fix_type . . . . .	625
8.512.2.8 set_function . . . . .	625
8.512.2.9 set_max_dist . . . . .	625
8.512.2.10 set_max_time . . . . .	625
8.513 pack_swioima_SLQSOMADMCancelSession_t Struct Reference . . . . .	625
8.513.1 Detailed Description . . . . .	625
8.513.2 Field Documentation . . . . .	625
8.513.2.1 sessionType . . . . .	625
8.514 pack_swioima_SLQSOMADMGetSessionInfo_t Struct Reference . . . . .	625
8.514.1 Detailed Description . . . . .	626
8.514.2 Field Documentation . . . . .	626
8.514.2.1 SessionType . . . . .	626
8.515 pack_swioima_SLQSOMADMSendSelection_t Struct Reference . . . . .	626
8.515.1 Detailed Description . . . . .	626
8.515.2 Field Documentation . . . . .	627
8.515.2.1 pDeferTime . . . . .	627
8.515.2.2 pRejectReason . . . . .	627
8.515.2.3 selection . . . . .	627
8.516 pack_swioima_SLQSOMADMSetSettings_t Struct Reference . . . . .	627
8.516.1 Detailed Description . . . . .	627
8.516.2 Field Documentation . . . . .	628

8.516.2.1 FOTAdownload . . . . .	628
8.516.2.2 FOTAUpdate . . . . .	628
8.516.2.3 pAutosdm . . . . .	628
8.516.2.4 pFwAutoCheck . . . . .	628
8.517pack_swima_SLQSOMADMStartSession_t Struct Reference . . . . .	628
8.517.1 Detailed Description . . . . .	628
8.517.2 Field Documentation . . . . .	628
8.517.2.1 sessionType . . . . .	628
8.518pack_uim_ChangePin_t Struct Reference . . . . .	628
8.518.1 Detailed Description . . . . .	629
8.518.2 Field Documentation . . . . .	629
8.518.2.1 changePIN . . . . .	629
8.518.2.2 EncryptedPIN1 . . . . .	629
8.518.2.3 pIndicationToken . . . . .	629
8.518.2.4 pKeyReferenceID . . . . .	629
8.518.2.5 sessionInfo . . . . .	629
8.518.2.6 Tlvresult . . . . .	629
8.519pack_uim_ReadTransparent_t Struct Reference . . . . .	629
8.519.1 Detailed Description . . . . .	630
8.519.2 Field Documentation . . . . .	630
8.519.2.1 fileIndex . . . . .	630
8.519.2.2 pEncryptData . . . . .	630
8.519.2.3 pIndicationToken . . . . .	630
8.519.2.4 readTransparent . . . . .	630
8.519.2.5 sessionInfo . . . . .	631
8.519.2.6 Tlvresult . . . . .	631
8.520pack_uim_SetPinProtection_t Struct Reference . . . . .	631
8.520.1 Detailed Description . . . . .	631
8.520.2 Field Documentation . . . . .	631
8.520.2.1 EncryptedPIN1 . . . . .	631
8.520.2.2 pIndicationToken . . . . .	632
8.520.2.3 pinProtection . . . . .	632
8.520.2.4 pKeyReferenceID . . . . .	632
8.520.2.5 sessionInfo . . . . .	632
8.520.2.6 Tlvresult . . . . .	632
8.521pack_uim_SLQSUIEventRegister_t Struct Reference . . . . .	632
8.521.1 Detailed Description . . . . .	632
8.521.2 Field Documentation . . . . .	632
8.521.2.1 eventMask . . . . .	632
8.522pack_uim_SLQSUIMSwitchSlot_t Struct Reference . . . . .	632

8.522.1 Detailed Description . . . . .	632
8.522.2 Field Documentation . . . . .	633
8.522.2.1 bLogicalSlot . . . . .	633
8.522.2.2 ulPhysicalSlot . . . . .	633
8.523pack_uim_UnblockPin_t Struct Reference . . . . .	633
8.523.1 Detailed Description . . . . .	633
8.523.2 Field Documentation . . . . .	634
8.523.2.1 EncryptedPIN1 . . . . .	634
8.523.2.2 pIndicationToken . . . . .	634
8.523.2.3 pinProtection . . . . .	634
8.523.2.4 pKeyReferenceID . . . . .	634
8.523.2.5 sessionInfo . . . . .	634
8.523.2.6 Tlvresult . . . . .	634
8.524pack_uim_VerifyPin_t Struct Reference . . . . .	634
8.524.1 Detailed Description . . . . .	635
8.524.2 Field Documentation . . . . .	636
8.524.2.1 pEncryptedPIN1 . . . . .	636
8.524.2.2 pIndicationToken . . . . .	636
8.524.2.3 pKeyReferenceID . . . . .	636
8.524.2.4 sessionInfo . . . . .	636
8.524.2.5 Tlvresult . . . . .	636
8.524.2.6 verifyPIN . . . . .	636
8.525pack_wds_GetDefaultProfile_t Struct Reference . . . . .	636
8.525.1 Detailed Description . . . . .	637
8.525.2 Field Documentation . . . . .	637
8.525.2.1 profiletype . . . . .	637
8.526pack_wds_GetDefaultProfileNum_t Struct Reference . . . . .	637
8.526.1 Detailed Description . . . . .	637
8.526.2 Field Documentation . . . . .	637
8.526.2.1 family . . . . .	637
8.526.2.2 type . . . . .	637
8.527pack_wds_GetDormancyState_t Struct Reference . . . . .	637
8.528pack_wds_GetLastMobileIPError_t Struct Reference . . . . .	637
8.529pack_wds_GetMobileIP_t Struct Reference . . . . .	637
8.530pack_wds_GetMobileIPProfile_t Struct Reference . . . . .	637
8.530.1 Detailed Description . . . . .	638
8.530.2 Field Documentation . . . . .	639
8.530.2.1 index . . . . .	639
8.531pack_wds_GetPacketStatus_t Struct Reference . . . . .	639
8.531.1 Detailed Description . . . . .	639

8.531.2 Field Documentation	639
8.531.2.1 statmask	639
8.532pack_wds_GetSessionDuration_t Struct Reference	639
8.533pack_wds_RMSetTransferStatistics_t Struct Reference	639
8.533.1 Detailed Description	639
8.533.2 Field Documentation	639
8.533.2.1 RmTrasnferStaticsReq	639
8.534pack_wds_SetDefaultProfile_t Struct Reference	639
8.534.1 Detailed Description	640
8.534.2 Field Documentation	640
8.534.2.1 authentication	640
8.534.2.2 ipAddress	640
8.534.2.3 pApnname	640
8.534.2.4 pdpType	640
8.534.2.5 pName	640
8.534.2.6 pPassword	640
8.534.2.7 primaryDNS	640
8.534.2.8 profileType	640
8.534.2.9 pUsername	640
8.534.2.10secondaryDNS	640
8.535pack_wds_SetDefaultProfileNum_t Struct Reference	640
8.535.1 Field Documentation	641
8.535.1.1 family	641
8.535.1.2 index	641
8.535.1.3 type	641
8.536pack_wds_SetMobileIPProfile_t Struct Reference	641
8.536.1 Detailed Description	641
8.536.2 Field Documentation	641
8.536.2.1 index	641
8.536.2.2 pAAASPI	641
8.536.2.3 pAddress	641
8.536.2.4 pEnabled	641
8.536.2.5 pHASPI	641
8.536.2.6 pMNAAA	642
8.536.2.7 pMNHA	642
8.536.2.8 pNAI	642
8.536.2.9 pPrimaryHA	642
8.536.2.10pRevTunneling	642
8.536.2.11pSecondaryHA	642
8.536.2.12spc	642

8.537	<a href="#">pack_wds_SLQSCreateProfile_t Struct Reference</a>	642
8.537.1	Detailed Description	642
8.537.2	Field Documentation	642
8.537.2.1	pCurProfile	642
8.537.2.2	pProfileId	643
8.537.2.3	pProfileType	643
8.538	<a href="#">pack_wds_SLQSDeleteProfile_t Struct Reference</a>	643
8.538.1	Detailed Description	643
8.538.2	Field Documentation	643
8.538.2.1	profileIndex	643
8.538.2.2	profileType	643
8.539	<a href="#">pack_wds_SLQSGetCurrDataSystemStat_t Struct Reference</a>	643
8.540	<a href="#">pack_wds_SLQSGetDataBearerTechnology_t Struct Reference</a>	643
8.541	<a href="#">pack_wds_SLQSGetDUNCallInfo_t Struct Reference</a>	643
8.541.1	Detailed Description	643
8.541.2	Field Documentation	644
8.541.2.1	Mask	644
8.541.2.2	pReportChannelRate	644
8.541.2.3	pReportConnStatus	644
8.541.2.4	pReportDataBearerTech	644
8.541.2.5	pReportDormStatus	644
8.541.2.6	pTransferStatInd	644
8.542	<a href="#">pack_wds_SLQSGetProfileSettings_t Struct Reference</a>	644
8.542.1	Detailed Description	644
8.542.2	Field Documentation	645
8.542.2.1	ProfileId	645
8.542.2.2	ProfileType	645
8.543	<a href="#">pack_wds_SLQSGetRuntimeSettings_t Struct Reference</a>	645
8.543.1	Detailed Description	646
8.543.2	Field Documentation	646
8.543.2.1	pReqSettings	646
8.544	<a href="#">pack_wds_SLQSModifyProfile_t Struct Reference</a>	646
8.544.1	Detailed Description	647
8.544.2	Field Documentation	648
8.544.2.1	curProfile	648
8.544.2.2	pProfileId	648
8.544.2.3	pProfileType	648
8.545	<a href="#">pack_wds_SLQSSet3GPPConfigItem_t Struct Reference</a>	648
8.545.1	Detailed Description	649
8.545.2	Field Documentation	649

8.545.2.1 _3gppRelease . . . . .	649
8.545.2.2 defaultPDNEnabled . . . . .	649
8.545.2.3 LTEAttachProfileList . . . . .	649
8.545.2.4 LTEAttachProfileListLen . . . . .	649
8.545.2.5 profileList . . . . .	649
8.546pack_wds_SLQSSetIPFamilyPreference_t Struct Reference . . . . .	649
8.546.1 Detailed Description . . . . .	650
8.546.2 Field Documentation . . . . .	651
8.546.2.1 IPFamilyPreference . . . . .	651
8.547pack_wds_SLQSSetWdsEventCallback_t Struct Reference . . . . .	651
8.547.1 Detailed Description . . . . .	651
8.547.2 Field Documentation . . . . .	651
8.547.2.1 currentDataBearer . . . . .	651
8.547.2.2 dataBearer . . . . .	651
8.547.2.3 dataSystemStatus . . . . .	651
8.547.2.4 dormancyStatus . . . . .	651
8.547.2.5 interval . . . . .	651
8.547.2.6 mobileIP . . . . .	651
8.547.2.7 transferStats . . . . .	651
8.548pack_wds_SLQSSetDHCPv4ClientConfig_t Struct Reference . . . . .	652
8.548.1 Detailed Description . . . . .	652
8.548.2 Field Documentation . . . . .	652
8.548.2.1 pProfileId . . . . .	652
8.549pack_wds_SLQSStartDataSession_t Struct Reference . . . . .	652
8.549.1 Detailed Description . . . . .	652
8.549.2 Field Documentation . . . . .	653
8.549.2.1 pAuth . . . . .	653
8.549.2.2 pPass . . . . .	653
8.549.2.3 pprofileid3gpp . . . . .	653
8.549.2.4 pprofileid3gpp2 . . . . .	653
8.549.2.5 pTech . . . . .	653
8.549.2.6 pUser . . . . .	653
8.550pack_wds_SLQSStopDataSession_t Struct Reference . . . . .	653
8.550.1 Detailed Description . . . . .	653
8.550.2 Field Documentation . . . . .	654
8.550.2.1 psid . . . . .	654
8.551pack_wds_SLQSWdsSwiPDPRuntimeSettings_t Struct Reference . . . . .	654
8.551.1 Detailed Description . . . . .	654
8.551.2 Field Documentation . . . . .	654
8.551.2.1 contextId . . . . .	654

8.551.2.2 contextType . . . . .	654
8.552PackCreateProfileOut Struct Reference . . . . .	654
8.552.1 Field Documentation . . . . .	654
8.552.1.1 ExtErrorCode . . . . .	654
8.552.1.2 ProfileIndex . . . . .	654
8.552.1.3 ProfileType . . . . .	654
8.553packgetDyingGaspCfg Struct Reference . . . . .	654
8.553.1 Detailed Description . . . . .	654
8.553.2 Field Documentation . . . . .	655
8.553.2.1 pDestSMSContent . . . . .	655
8.553.2.2 pDestSMSNum . . . . .	655
8.554packgetDyingGaspStatistics Struct Reference . . . . .	655
8.554.1 Detailed Description . . . . .	655
8.554.2 Field Documentation . . . . .	655
8.554.2.1 pSMSAttemptedFlag . . . . .	655
8.554.2.2 pTimeStamp . . . . .	655
8.555PCMparams Struct Reference . . . . .	655
8.555.1 Detailed Description . . . . .	656
8.555.2 Field Documentation . . . . .	657
8.555.2.1 iFaceTab . . . . .	657
8.555.2.2 iFaceTabLen . . . . .	657
8.556PCSCFFQDNAddress Struct Reference . . . . .	657
8.556.1 Detailed Description . . . . .	657
8.556.2 Field Documentation . . . . .	657
8.556.2.1 fqdnAddr . . . . .	657
8.556.2.2 fqdnLen . . . . .	657
8.557PCSCFFQDNAddressList Struct Reference . . . . .	657
8.557.1 Detailed Description . . . . .	658
8.557.2 Field Documentation . . . . .	659
8.557.2.1 numInstances . . . . .	659
8.557.2.2 pcsfQDNAddress . . . . .	659
8.558PCSCFIPv4ServerAddressList Struct Reference . . . . .	659
8.558.1 Detailed Description . . . . .	659
8.558.2 Field Documentation . . . . .	659
8.558.2.1 numInstances . . . . .	659
8.558.2.2 pscsfIPv4Addr . . . . .	659
8.559PDSPositionData Struct Reference . . . . .	659
8.559.1 Detailed Description . . . . .	660
8.559.2 Field Documentation . . . . .	661
8.559.2.1 pAltitudeWrtEllipsoid . . . . .	661



8.559.2.2 pAltitudeWrtSealevel . . . . .	661
8.559.2.3 pHorizontalConfidence . . . . .	661
8.559.2.4 pHorizontalUncCircular . . . . .	661
8.559.2.5 pLatitude . . . . .	661
8.559.2.6 pLongitude . . . . .	661
8.559.2.7 pPositionSource . . . . .	661
8.559.2.8 pTimeStamp . . . . .	661
8.559.2.9 pTimeType . . . . .	661
8.559.2.10pVerticalConfidence . . . . .	661
8.559.2.11pVerticalUnc . . . . .	661
8.560PDSPosMethodStateReq Struct Reference . . . . .	661
8.560.1 Detailed Description . . . . .	662
8.560.2 Field Documentation . . . . .	662
8.560.2.1 pWifiState . . . . .	662
8.560.2.2 pXtraDataState . . . . .	662
8.560.2.3 pXtraTimeState . . . . .	662
8.561peerNumberInfo Struct Reference . . . . .	662
8.561.1 Detailed Description . . . . .	663
8.561.2 Field Documentation . . . . .	664
8.561.2.1 callID . . . . .	664
8.561.2.2 number . . . . .	664
8.561.2.3 numLen . . . . .	664
8.561.2.4 numPI . . . . .	664
8.561.2.5 numPlan . . . . .	664
8.561.2.6 numSI . . . . .	664
8.561.2.7 numType . . . . .	664
8.562personalizationStatus Struct Reference . . . . .	664
8.562.1 Detailed Description . . . . .	664
8.562.2 Field Documentation . . . . .	665
8.562.2.1 feature . . . . .	665
8.562.2.2 numFeatures . . . . .	665
8.562.2.3 unblockLeft . . . . .	665
8.562.2.4 verifyLeft . . . . .	665
8.563PhyCaAggPcellInfo Struct Reference . . . . .	665
8.563.1 Detailed Description . . . . .	666
8.563.2 Field Documentation . . . . .	667
8.563.2.1 dl_bw_value . . . . .	667
8.563.2.2 freq . . . . .	667
8.563.2.3 iLTEbandValue . . . . .	667
8.563.2.4 pci . . . . .	667

8.563.2.5 TlvPresent . . . . .	667
8.564PhyCaAggScellIDIBw Struct Reference . . . . .	667
8.564.1 Detailed Description . . . . .	667
8.564.2 Field Documentation . . . . .	668
8.564.2.1 dl_bw_value . . . . .	668
8.564.2.2 TlvPresent . . . . .	668
8.565PhyCaAggScellIndex Struct Reference . . . . .	668
8.565.1 Detailed Description . . . . .	668
8.565.2 Field Documentation . . . . .	668
8.565.2.1 scell_idx . . . . .	668
8.565.2.2 TlvPresent . . . . .	668
8.566PhyCaAggScellIndType Struct Reference . . . . .	668
8.566.1 Detailed Description . . . . .	668
8.566.2 Field Documentation . . . . .	669
8.566.2.1 freq . . . . .	669
8.566.2.2 pci . . . . .	669
8.566.2.3 scell_state . . . . .	669
8.566.2.4 TlvPresent . . . . .	669
8.567PhyCaAggScellInfo Struct Reference . . . . .	669
8.567.1 Detailed Description . . . . .	669
8.567.2 Field Documentation . . . . .	671
8.567.2.1 dl_bw_value . . . . .	671
8.567.2.2 freq . . . . .	671
8.567.2.3 iLTEbandValue . . . . .	671
8.567.2.4 pci . . . . .	671
8.567.2.5 scell_state . . . . .	671
8.567.2.6 TlvPresent . . . . .	671
8.568PilotSetData Struct Reference . . . . .	671
8.568.1 Detailed Description . . . . .	671
8.568.2 Field Documentation . . . . .	672
8.568.2.1 NumPilots . . . . .	672
8.568.2.2 pPilotSetInfo . . . . .	672
8.569PilotSetParams Struct Reference . . . . .	672
8.569.1 Detailed Description . . . . .	672
8.569.2 Field Documentation . . . . .	672
8.569.2.1 PilotPN . . . . .	672
8.569.2.2 PilotStrength . . . . .	672
8.569.2.3 PilotType . . . . .	672
8.570pktErrRate Struct Reference . . . . .	672
8.570.1 Detailed Description . . . . .	673

8.570.2 Field Documentation . . . . .	673
8.570.2.1 exponent . . . . .	673
8.570.2.2 multiplier . . . . .	673
8.571 PLMNNetworkName Struct Reference . . . . .	673
8.571.1 Detailed Description . . . . .	673
8.571.2 Field Documentation . . . . .	673
8.571.2.1 numInstance . . . . .	673
8.571.2.2 PLMNNetName . . . . .	673
8.572 PLMNNetworkNameData Struct Reference . . . . .	673
8.572.1 Detailed Description . . . . .	674
8.572.2 Field Documentation . . . . .	675
8.572.2.1 codingScheme . . . . .	675
8.572.2.2 countryInitials . . . . .	675
8.572.2.3 longName . . . . .	675
8.572.2.4 longNameLen . . . . .	675
8.572.2.5 longNameSpareBits . . . . .	675
8.572.2.6 shortName . . . . .	675
8.572.2.7 shortNameLen . . . . .	675
8.572.2.8 shortNameSpareBits . . . . .	675
8.573 Port Struct Reference . . . . .	675
8.573.1 Detailed Description . . . . .	676
8.573.2 Field Documentation . . . . .	676
8.573.2.1 port . . . . .	676
8.573.2.2 range . . . . .	676
8.574 precisionDilution_s Struct Reference . . . . .	676
8.574.1 Detailed Description . . . . .	676
8.574.2 Field Documentation . . . . .	677
8.574.2.1 HDOP . . . . .	677
8.574.2.2 PDOP . . . . .	677
8.574.2.3 VDOP . . . . .	677
8.575 PrefImageList Struct Reference . . . . .	677
8.575.1 Detailed Description . . . . .	677
8.575.2 Field Documentation . . . . .	677
8.575.2.1 listEntries . . . . .	677
8.575.2.2 listSize . . . . .	677
8.576 prefVoiceSO Struct Reference . . . . .	677
8.576.1 Detailed Description . . . . .	677
8.576.2 Field Documentation . . . . .	679
8.576.2.1 evrcCapability . . . . .	679
8.576.2.2 homeOrigVoiceSO . . . . .	679

8.576.2.3 homePageVoiceSO . . . . .	679
8.576.2.4 namID . . . . .	679
8.576.2.5 roamOrigVoiceSO . . . . .	680
8.577 Profile3GPP Struct Reference . . . . .	680
8.577.1 Detailed Description . . . . .	680
8.577.2 Field Documentation . . . . .	685
8.577.2.1 pAddrAllocPref . . . . .	685
8.577.2.2 pAPNClass . . . . .	685
8.577.2.3 pAPNDisabledFlag . . . . .	685
8.577.2.4 pAPNName . . . . .	685
8.577.2.5 pAPNnameSize . . . . .	685
8.577.2.6 pAuthenticationPref . . . . .	685
8.577.2.7 pGPRSMinimumQoS . . . . .	685
8.577.2.8 pGPRSRequestedQoS . . . . .	685
8.577.2.9 plmCnFlag . . . . .	685
8.577.2.10 pIPv4AddrPref . . . . .	685
8.577.2.11 pIPv6AddPref . . . . .	685
8.577.2.12 pPassword . . . . .	685
8.577.2.13 pPasswordSize . . . . .	685
8.577.2.14 pPcscfAddrUsingDhcp . . . . .	685
8.577.2.15 pPcscfAddrUsingPCO . . . . .	685
8.577.2.16 pPDNInactivTimeout . . . . .	685
8.577.2.17 pPdpAccessConFlag . . . . .	685
8.577.2.18 pPdpContext . . . . .	686
8.577.2.19 pPdpDataCompType . . . . .	686
8.577.2.20 pPdpHdrCompType . . . . .	686
8.577.2.21 pPDType . . . . .	686
8.577.2.22 pPriDNSIPv4AddPref . . . . .	686
8.577.2.23 pPriDNSIPv6addpref . . . . .	686
8.577.2.24 pPrimaryID . . . . .	686
8.577.2.25 pProfilename . . . . .	686
8.577.2.26 pProfilenameSize . . . . .	686
8.577.2.27 pQoSClassID . . . . .	686
8.577.2.28 pSecDNSIPv4AddPref . . . . .	686
8.577.2.29 pSecDNSIPv6addpref . . . . .	686
8.577.2.30 pSecondaryFlag . . . . .	686
8.577.2.31 pTFTID1Params . . . . .	686
8.577.2.32 pTFTID2Params . . . . .	686
8.577.2.33 pUMTSMinQoS . . . . .	686
8.577.2.34 pUMTSMinQoSSigInd . . . . .	686

8.577.2.35	pUMTSReqQoS	686
8.577.2.36	pUMTSReqQoSSigInd	686
8.577.2.37	pUsername	686
8.577.2.38	pUsernameSize	686
8.578	Profile3GPP2 Struct Reference	686
8.578.1	Detailed Description	687
8.578.2	Field Documentation	691
8.578.2.1	pAllowLinger	691
8.578.2.2	pAPNClass3GPP2	691
8.578.2.3	pAPNEnabled3GPP2	691
8.578.2.4	pApnString	691
8.578.2.5	pApnStringSize	691
8.578.2.6	pAppPriority	691
8.578.2.7	pAppType	691
8.578.2.8	pAuthPassword	691
8.578.2.9	pAuthPasswordSize	691
8.578.2.10	pAuthProtocol	691
8.578.2.11	pAuthRetryCount	691
8.578.2.12	pAuthTimeout	692
8.578.2.13	pDataMode	692
8.578.2.14	pDataRate	692
8.578.2.15	pIpcpAckTimeout	692
8.578.2.16	pIpcpCreqRetryCount	692
8.578.2.17	pIsPcscfAddressNedded	692
8.578.2.18	pLcpAckTimeout	692
8.578.2.19	pLcpCreqRetryCount	692
8.578.2.20	pNegoDnsSrvrPref	692
8.578.2.21	pPDNInactivTimeout3GPP2	692
8.578.2.22	pPdnType	692
8.578.2.23	pPppSessCloseTimer1x	692
8.578.2.24	pPppSessCloseTimerDO	692
8.578.2.25	pPrimaryV4DnsAddress	692
8.578.2.26	pPriV6DnsAddress	692
8.578.2.27	pRATType	692
8.578.2.28	pSecondaryV4DnsAddress	692
8.578.2.29	pSecV6DnsAddress	692
8.578.2.30	pUserId	692
8.578.2.31	pUserIdSize	692
8.579	ProfileIdentifier Struct Reference	692
8.579.1	Detailed Description	692

8.579.2 Field Documentation . . . . .	693
8.579.2.1 profileIndex . . . . .	693
8.579.2.2 profileType . . . . .	693
8.580 protocolSubtypeElement Struct Reference . . . . .	693
8.580.1 Detailed Description . . . . .	693
8.580.2 Field Documentation . . . . .	694
8.580.2.1 AccessMac . . . . .	694
8.580.2.2 AuthProt . . . . .	694
8.580.2.3 ControlMac . . . . .	694
8.580.2.4 EncryptProt . . . . .	694
8.580.2.5 ForwardMac . . . . .	694
8.580.2.6 IdleState . . . . .	694
8.580.2.7 KeyExchange . . . . .	694
8.580.2.8 MultDisc . . . . .	694
8.580.2.9 PhysicalLayer . . . . .	694
8.580.2.10 ReverseMac . . . . .	694
8.580.2.11 SecProt . . . . .	694
8.580.2.12 VirtStream . . . . .	695
8.581 PSDetachReq Struct Reference . . . . .	695
8.581.1 Detailed Description . . . . .	695
8.581.2 Field Documentation . . . . .	695
8.581.2.1 pDetachAction . . . . .	695
8.582 qaQmi3Gpp2TimeZone Struct Reference . . . . .	695
8.582.1 Detailed Description . . . . .	695
8.582.2 Field Documentation . . . . .	696
8.582.2.1 daylightSavings . . . . .	696
8.582.2.2 leapSeconds . . . . .	696
8.582.2.3 localTimeOffset . . . . .	696
8.583 qaQmiInterfaceInfo Struct Reference . . . . .	696
8.583.1 Detailed Description . . . . .	696
8.583.2 Field Documentation . . . . .	696
8.583.2.1 qaQmiinstanceid . . . . .	696
8.583.2.2 qaQmisvctype . . . . .	696
8.583.2.3 v4sessionId . . . . .	696
8.583.2.4 v6sessionId . . . . .	696
8.584 qaQmiServingSystemParam Struct Reference . . . . .	696
8.584.1 Detailed Description . . . . .	697
8.584.2 Field Documentation . . . . .	700
8.584.2.1 BasestationID . . . . .	700
8.584.2.2 BasestationLatitude . . . . .	700

8.584.2.3 BasestationLongitude . . . . .	700
8.584.2.4 CallBarStatus . . . . .	700
8.584.2.5 CDMA_P_Rev . . . . .	700
8.584.2.6 CDMASystemInfoExt . . . . .	700
8.584.2.7 CellID . . . . .	700
8.584.2.8 concSvcInfo . . . . .	700
8.584.2.9 CurrentPLMN . . . . .	700
8.584.2.10DataSrvCapabilities . . . . .	700
8.584.2.11defaultRoamInd . . . . .	700
8.584.2.12DetailedSvcInfo . . . . .	700
8.584.2.13DTMInd . . . . .	700
8.584.2.14Gpp2TimeZone . . . . .	700
8.584.2.15GppNetworkDSTAdjustment . . . . .	700
8.584.2.16GppTimeZone . . . . .	700
8.584.2.17hdrPersonality . . . . .	700
8.584.2.18Lac . . . . .	701
8.584.2.19NetworkID . . . . .	701
8.584.2.20PRLInd . . . . .	701
8.584.2.21roamIndicatorVal . . . . .	701
8.584.2.22RoamingIndicatorList . . . . .	701
8.584.2.23ServingSystem . . . . .	701
8.584.2.24SystemID . . . . .	701
8.584.2.25trackAreaCode . . . . .	701
8.585QmiCbKCatEventStatusReportInd Struct Reference . . . . .	701
8.585.1 Field Documentation . . . . .	701
8.585.1.1 CCETiv . . . . .	701
8.585.1.2 event_Index . . . . .	701
8.586QmiCbKLocCradleMountInd Struct Reference . . . . .	701
8.586.1 Detailed Description . . . . .	701
8.586.2 Field Documentation . . . . .	702
8.586.2.1 cradleMountConfigStatus . . . . .	702
8.587QmiCbKLocEngineStateInd Struct Reference . . . . .	702
8.587.1 Detailed Description . . . . .	702
8.587.2 Field Documentation . . . . .	702
8.587.2.1 engineState . . . . .	702
8.588QmiCbKLocEventTimeSyncInd Struct Reference . . . . .	703
8.588.1 Detailed Description . . . . .	703
8.588.2 Field Documentation . . . . .	703
8.588.2.1 timeSyncRefCounter . . . . .	703
8.589QmiCbKLocInjectPositionInd Struct Reference . . . . .	703

8.589.1 Detailed Description . . . . .	703
8.589.2 Field Documentation . . . . .	704
8.589.2.1 status . . . . .	704
8.590QmiCbkLocInjectSensorDataInd Struct Reference . . . . .	704
8.590.1 Detailed Description . . . . .	704
8.590.2 Field Documentation . . . . .	705
8.590.2.1 injectSensorDataStatus . . . . .	705
8.590.2.2 pAccelSamplesAccepted . . . . .	705
8.590.2.3 pAccelTempSamplesAccepted . . . . .	705
8.590.2.4 pGyroSamplesAccepted . . . . .	706
8.590.2.5 pGyroTempSamplesAccepted . . . . .	706
8.590.2.6 pOpaqueIdentifier . . . . .	706
8.591QmiCbkLocInjectTimeInd Struct Reference . . . . .	706
8.591.1 Detailed Description . . . . .	706
8.591.2 Field Documentation . . . . .	706
8.591.2.1 injectTimeSyncStatus . . . . .	706
8.592QmiCbkLocInjectUTCTimeInd Struct Reference . . . . .	706
8.592.1 Detailed Description . . . . .	706
8.592.2 Field Documentation . . . . .	707
8.592.2.1 status . . . . .	707
8.593QmiCbkLocPositionReportInd Struct Reference . . . . .	707
8.593.1 Detailed Description . . . . .	708
8.593.2 Field Documentation . . . . .	712
8.593.2.1 pAltitudeAssumed . . . . .	712
8.593.2.2 pAltitudeWrtEllipsoid . . . . .	712
8.593.2.3 pAltitudeWrtMeanSeaLevel . . . . .	712
8.593.2.4 pFixId . . . . .	712
8.593.2.5 pGpsTime . . . . .	712
8.593.2.6 pHeading . . . . .	712
8.593.2.7 pHeadingUnc . . . . .	712
8.593.2.8 pHorConfidence . . . . .	712
8.593.2.9 pHorReliability . . . . .	712
8.593.2.10pHorUncCircular . . . . .	712
8.593.2.11pHorUncEllipseOrientAzimuth . . . . .	712
8.593.2.12pHorUncEllipseSemiMajor . . . . .	712
8.593.2.13pHorUncEllipseSemiMinor . . . . .	712
8.593.2.14pLatitude . . . . .	712
8.593.2.15pLeapSeconds . . . . .	712
8.593.2.16pLongitude . . . . .	712
8.593.2.17pMagneticDeviation . . . . .	712



8.593.2.18pPrecisionDilution . . . . .	713
8.593.2.19pSensorDataUsage . . . . .	713
8.593.2.20pSpeedHorizontal . . . . .	713
8.593.2.21pSpeedUnc . . . . .	713
8.593.2.22pSpeedVertical . . . . .	713
8.593.2.23pSvUsedforFix . . . . .	713
8.593.2.24pTechnologyMask . . . . .	713
8.593.2.25pTimeSrc . . . . .	713
8.593.2.26pTimestampUtc . . . . .	713
8.593.2.27pTimeUnc . . . . .	713
8.593.2.28pVertConfidence . . . . .	713
8.593.2.29pVertReliability . . . . .	713
8.593.2.30pVertUnc . . . . .	713
8.593.2.31sessionId . . . . .	713
8.593.2.32sessionStatus . . . . .	713
8.594QmiCbkLocSensorStreamingInd Struct Reference . . . . .	713
8.594.1 Detailed Description . . . . .	713
8.594.2 Field Documentation . . . . .	714
8.594.2.1 pAccelAcceptReady . . . . .	714
8.594.2.2 pAccelTempAcceptReady . . . . .	714
8.594.2.3 pGyroAcceptReady . . . . .	714
8.594.2.4 pGyroTempAcceptReady . . . . .	714
8.595QmiCbkLocSetExtPowerConfigInd Struct Reference . . . . .	714
8.595.1 Detailed Description . . . . .	714
8.595.2 Field Documentation . . . . .	714
8.595.2.1 status . . . . .	715
8.596QmiCbkNasLTECphyCaInfo Struct Reference . . . . .	715
8.596.1 Detailed Description . . . . .	715
8.596.2 Field Documentation . . . . .	715
8.596.2.1 sPhyCaAggPcellInfo . . . . .	715
8.596.2.2 sPhyCaAggScellIDBw . . . . .	715
8.596.2.3 sPhyCaAggScellIndex . . . . .	715
8.596.2.4 sPhyCaAggScellIndType . . . . .	715
8.596.2.5 sPhyCaAggScellInfo . . . . .	715
8.597QmiCbkSwiOmaDmEventStatusReportInd Struct Reference . . . . .	715
8.597.1 Field Documentation . . . . .	716
8.597.1.1 SITlv . . . . .	716
8.598QmiCbkSwiOmaDmEventStatusReportIndExt Struct Reference . . . . .	716
8.598.1 Field Documentation . . . . .	716
8.598.1.1 SITlv . . . . .	716

8.599QmiCbktmdMitiLvlRptInd Struct Reference	716
8.599.1 Detailed Description	716
8.599.2 Field Documentation	716
8.599.2.1 currentMitigationLvl	716
8.599.2.2 MitigationDevInfo	716
8.600QmiCbkWdsStatisticsIndState Struct Reference	716
8.600.1 Detailed Description	717
8.600.2 Field Documentation	718
8.600.2.1 RxDropConutTlv	718
8.600.2.2 RxOkByteCountTlv	718
8.600.2.3 RxOkConutTlv	718
8.600.2.4 TxDropConutTlv	718
8.600.2.5 TxOkByteCountTlv	718
8.600.2.6 TxOkConutTlv	718
8.601qmifwinfo_s Struct Reference	718
8.601.1 Detailed Description	718
8.601.2 Field Documentation	719
8.601.2.1 dev	719
8.601.2.2 g	719
8.601.2.3 s	719
8.602QmiNas3GppNetworkInfo Struct Reference	719
8.602.1 Detailed Description	719
8.602.2 Field Documentation	720
8.602.2.1 pDescription	720
8.602.2.2 pForbidden	720
8.602.2.3 plnUse	720
8.602.2.4 pMCC	720
8.602.2.5 pMNC	721
8.602.2.6 pPreferred	721
8.602.2.7 pRoaming	721
8.603QmiNasGetRFBandInfoResp Struct Reference	721
8.603.1 Field Documentation	721
8.603.1.1 plnInstancesSize	721
8.603.1.2 pRFBandInfoElements	721
8.603.1.3 results	721
8.604QmiNasPerformNetworkScanResp Struct Reference	721
8.604.1 Field Documentation	721
8.604.1.1 plnInstances	721
8.604.1.2 plnInstanceSize	721
8.604.1.3 results	721

8.605qmiSmsMessageList Struct Reference	721
8.605.1 Detailed Description	721
8.605.2 Field Documentation	722
8.605.2.1 messageIndex	722
8.605.2.2 messageTag	722
8.606qmiWSDDataBearerTechnology Struct Reference	722
8.606.1 Detailed Description	722
8.606.2 Field Documentation	722
8.606.2.1 currentNetwork	722
8.606.2.2 ratMask	722
8.606.2.3 soMask	722
8.607QmiWdsIpAddressInfo Struct Reference	722
8.607.1 Detailed Description	722
8.607.2 Field Documentation	723
8.607.2.1 pIPAddressV4	723
8.607.2.2 pIPAddressV6	723
8.607.2.3 pIPv6prefixlen	723
8.608qmiWdsRunTimeSettings Struct Reference	723
8.608.1 Detailed Description	724
8.608.2 Field Documentation	726
8.608.2.1 pAPNName	726
8.608.2.2 pAuthentication	726
8.608.2.3 pDomainList	726
8.608.2.4 pGPRSGrantedQoS	726
8.608.2.5 pGWAddressV4	726
8.608.2.6 pIMCNflag	726
8.608.2.7 pIPAddressV4	726
8.608.2.8 pIPFamilyPreference	726
8.608.2.9 pIPv6AddrInfo	727
8.608.2.10pIPv6GWAddrInfo	727
8.608.2.11pMtu	727
8.608.2.12pPCSCFAddrPCO	727
8.608.2.13pPCSCFFQDNAddrList	727
8.608.2.14pPDPTType	727
8.608.2.15pPrimaryDNSV4	727
8.608.2.16pPrimaryDNSV6	727
8.608.2.17pProfileID	727
8.608.2.18pProfileName	727
8.608.2.19pSecondaryDNSV4	727
8.608.2.20pSecondaryDNSV6	727

8.608.2.21pServerAddrList . . . . .	727
8.608.2.22pSubnetMaskV4 . . . . .	727
8.608.2.23pTechnology . . . . .	727
8.608.2.24pUMTSGrantedQoS . . . . .	727
8.608.2.25pUsername . . . . .	727
8.609QosClassID Struct Reference . . . . .	727
8.609.1 Detailed Description . . . . .	727
8.609.2 Field Documentation . . . . .	728
8.609.2.1 gDIBitRate . . . . .	728
8.609.2.2 gUIBitRate . . . . .	728
8.609.2.3 maxDIBitRate . . . . .	728
8.609.2.4 maxUIBitRate . . . . .	728
8.609.2.5 QCI . . . . .	728
8.610QosEventInfo Struct Reference . . . . .	728
8.610.1 Detailed Description . . . . .	728
8.610.2 Field Documentation . . . . .	730
8.610.2.1 pDataBearer . . . . .	730
8.610.2.2 pPacketsCountRX . . . . .	730
8.610.2.3 pPacketsCountTX . . . . .	730
8.610.2.4 pTotalBytesRX . . . . .	730
8.610.2.5 pTotalBytesTX . . . . .	730
8.611QosFlowInfo Struct Reference . . . . .	730
8.611.1 Detailed Description . . . . .	730
8.611.2 Field Documentation . . . . .	731
8.611.2.1 pBearerID . . . . .	731
8.611.2.2 pQFlowState . . . . .	731
8.611.2.3 pRxQFilter . . . . .	731
8.611.2.4 pRxQFlowGranted . . . . .	731
8.611.2.5 pTxQFilter . . . . .	731
8.611.2.6 pTxQFlowGranted . . . . .	731
8.612QosFlowInfoState Struct Reference . . . . .	731
8.612.1 Detailed Description . . . . .	731
8.612.2 Field Documentation . . . . .	732
8.612.2.1 id . . . . .	732
8.612.2.2 isNewFlow . . . . .	732
8.612.2.3 state . . . . .	732
8.613QosMap Struct Reference . . . . .	732
8.613.1 Detailed Description . . . . .	732
8.613.2 Field Documentation . . . . .	733
8.613.2.1 dscp . . . . .	733

8.613.2.2 qos_id . . . . .	733
8.613.2.3 state . . . . .	733
8.614RankIndicatorInd Struct Reference . . . . .	733
8.614.1 Field Documentation . . . . .	733
8.614.1.1 Count1 . . . . .	733
8.614.1.2 Count2 . . . . .	733
8.615readResult Struct Reference . . . . .	733
8.615.1 Detailed Description . . . . .	733
8.615.2 Field Documentation . . . . .	733
8.615.2.1 content . . . . .	733
8.615.2.2 contentLen . . . . .	733
8.616readTransparentInfo Struct Reference . . . . .	733
8.616.1 Detailed Description . . . . .	734
8.616.2 Field Documentation . . . . .	734
8.616.2.1 length . . . . .	734
8.616.2.2 offset . . . . .	734
8.617redirNumInfo Struct Reference . . . . .	734
8.617.1 Detailed Description . . . . .	734
8.617.2 Field Documentation . . . . .	736
8.617.2.1 number . . . . .	736
8.617.2.2 numLen . . . . .	736
8.617.2.3 numPlan . . . . .	736
8.617.2.4 numType . . . . .	736
8.617.2.5 PI . . . . .	736
8.617.2.6 reason . . . . .	736
8.617.2.7 SI . . . . .	736
8.618registerRefresh Struct Reference . . . . .	736
8.618.1 Detailed Description . . . . .	736
8.618.2 Field Documentation . . . . .	737
8.618.2.1 arrfileInfo . . . . .	737
8.618.2.2 numFiles . . . . .	737
8.618.2.3 registerFlag . . . . .	737
8.618.2.4 voteForInit . . . . .	737
8.619remainingRetries Struct Reference . . . . .	737
8.619.1 Detailed Description . . . . .	737
8.619.2 Field Documentation . . . . .	738
8.619.2.1 unblockLeft . . . . .	738
8.619.2.2 verifyLeft . . . . .	738
8.620remotePartyName Struct Reference . . . . .	738
8.620.1 Detailed Description . . . . .	738

8.620.2 Field Documentation . . . . .	739
8.620.2.1 callerName . . . . .	739
8.620.2.2 codingScheme . . . . .	739
8.620.2.3 nameLen . . . . .	739
8.620.2.4 namePI . . . . .	739
8.621 remotePartyNum Struct Reference . . . . .	739
8.621.1 Detailed Description . . . . .	739
8.621.2 Field Documentation . . . . .	740
8.621.2.1 numLen . . . . .	740
8.621.2.2 presentationInd . . . . .	740
8.621.2.3 remPartyNumber . . . . .	740
8.622 ReqFieldsList Struct Reference . . . . .	740
8.622.1 Detailed Description . . . . .	740
8.622.2 Field Documentation . . . . .	741
8.622.2.1 requestFields . . . . .	741
8.622.2.2 requestFieldsLen . . . . .	741
8.623 RespFieldsList Struct Reference . . . . .	741
8.623.1 Detailed Description . . . . .	741
8.623.2 Field Documentation . . . . .	741
8.623.2.1 responseFields . . . . .	741
8.623.2.2 responseFieldsLen . . . . .	741
8.624 RFBandInfoElements Struct Reference . . . . .	741
8.624.1 Detailed Description . . . . .	741
8.624.2 Field Documentation . . . . .	742
8.624.2.1 activeBandClass . . . . .	742
8.624.2.2 activeBandClass . . . . .	742
8.624.2.3 activeChannel . . . . .	742
8.624.2.4 activeChannel . . . . .	742
8.624.2.5 radiolInterface . . . . .	742
8.624.2.6 radiolInterface . . . . .	742
8.625 rmTrasferStaticsReq Struct Reference . . . . .	742
8.625.1 Detailed Description . . . . .	742
8.625.2 Field Documentation . . . . .	742
8.625.2.1 bResetStatistics . . . . .	742
8.625.2.2 ulMask . . . . .	742
8.626 roamIndList Struct Reference . . . . .	743
8.626.1 Detailed Description . . . . .	743
8.626.2 Field Documentation . . . . .	743
8.626.2.1 numInstances . . . . .	743
8.626.2.2 radiolInterface . . . . .	743

8.626.2.3 roamIndicator . . . . .	743
8.627RoamingInfo Struct Reference . . . . .	743
8.627.1 Field Documentation . . . . .	744
8.627.1.1 roaming_ind . . . . .	744
8.627.1.2 TlvPresent . . . . .	744
8.628roamTimer Struct Reference . . . . .	744
8.628.1 Detailed Description . . . . .	744
8.628.2 Field Documentation . . . . .	744
8.628.2.1 namID . . . . .	744
8.628.2.2 roamTimerValue . . . . .	744
8.629RSRPThresh Struct Reference . . . . .	744
8.629.1 Detailed Description . . . . .	745
8.629.2 Field Documentation . . . . .	746
8.629.2.1 pRSRPThresList . . . . .	746
8.629.2.2 RSRPThresListLen . . . . .	746
8.630rsrqInformation Struct Reference . . . . .	746
8.630.1 Detailed Description . . . . .	746
8.630.2 Field Documentation . . . . .	746
8.630.2.1 radiolf . . . . .	746
8.630.2.2 rsrq . . . . .	747
8.631RSRQThresh Struct Reference . . . . .	747
8.631.1 Detailed Description . . . . .	747
8.631.2 Field Documentation . . . . .	747
8.631.2.1 pRSRQThresList . . . . .	747
8.631.2.2 RSRQThresListLen . . . . .	747
8.632RSSIThresh Struct Reference . . . . .	747
8.632.1 Detailed Description . . . . .	747
8.632.2 Field Documentation . . . . .	748
8.632.2.1 pRSSIThresList . . . . .	748
8.632.2.2 RSSIThresListLen . . . . .	748
8.633RXAGCList Struct Reference . . . . .	748
8.633.1 Detailed Description . . . . .	748
8.633.2 Field Documentation . . . . .	749
8.633.2.1 pRXAIG . . . . .	749
8.633.2.2 pRXComprSlope . . . . .	749
8.633.2.3 pRXComprThres . . . . .	749
8.633.2.4 pRXExpSlope . . . . .	749
8.633.2.5 pRXExpThres . . . . .	749
8.633.2.6 pRXStaticGain . . . . .	749
8.634RXAVCList Struct Reference . . . . .	749

8.634.1 Detailed Description	749
8.634.2 Field Documentation	749
8.634.2.1 pAVRXAVCHearoom	749
8.634.2.2 pAVRXAVCSens	750
8.635rxInfo Struct Reference	750
8.635.1 Detailed Description	750
8.635.2 Field Documentation	750
8.635.2.1 ecio	750
8.635.2.2 isRadioTuned	751
8.635.2.3 phase	751
8.635.2.4 rscp	751
8.635.2.5 rsrp	751
8.635.2.6 rxPower	751
8.636RXPCMIIRFitr Struct Reference	751
8.636.1 Detailed Description	751
8.636.2 Field Documentation	753
8.636.2.1 pFlag	753
8.636.2.2 pStage0Val	753
8.636.2.3 pStage1Val	753
8.636.2.4 pStage2Val	753
8.636.2.5 pStage3Val	753
8.636.2.6 pStage4Val	753
8.636.2.7 pStageCnt	753
8.637rxSignalStrengthListElement Struct Reference	753
8.637.1 Detailed Description	753
8.637.2 Field Documentation	754
8.637.2.1 radiolf	754
8.637.2.2 rxSignalStrength	754
8.638sApnExtraParams Struct Reference	754
8.638.1 Detailed Description	754
8.638.2 Field Documentation	755
8.638.2.1 ambr_dl	755
8.638.2.2 ambr_dl_ext	755
8.638.2.3 ambr_dl_ext2	755
8.638.2.4 ambr_ul	755
8.638.2.5 ambr_ul_ext	755
8.638.2.6 ambr_ul_ext2	755
8.638.2.7 apnId	755
8.639satelliteInfo Struct Reference	755
8.639.1 Detailed Description	755



8.639.2 Field Documentation	758
8.639.2.1 azimuth	758
8.639.2.2 elevation	758
8.639.2.3 gnssSvId	758
8.639.2.4 healthStatus	758
8.639.2.5 snr	758
8.639.2.6 svInfoMask	758
8.639.2.7 svListLen	758
8.639.2.8 svStatus	758
8.639.2.9 system	758
8.639.2.10 validMask	758
8.640 sensorData Struct Reference	758
8.640.1 Detailed Description	758
8.640.2 Field Documentation	759
8.640.2.1 flags	759
8.640.2.2 sensorDataLen	759
8.640.2.3 timeOfFirstSample	759
8.640.2.4 timeOffset	760
8.640.2.5 xAxis	760
8.640.2.6 yAxis	760
8.640.2.7 zAxis	760
8.641 sensorDataUsage_s Struct Reference	760
8.641.1 Detailed Description	760
8.641.2 Field Documentation	760
8.641.2.1 aidingIndicatorMask	760
8.641.2.2 usageMask	760
8.642 serialNumbersInfo Struct Reference	760
8.642.1 Detailed Description	761
8.642.2 Field Documentation	761
8.642.2.1 esnSize	761
8.642.2.2 imeiSize	761
8.642.2.3 imeiSvnSize	762
8.642.2.4 meidSize	762
8.642.2.5 pESNString	762
8.642.2.6 pIMEIString	762
8.642.2.7 plmeiSvnString	762
8.642.2.8 pMEIDString	762
8.643 serviceProviderName Struct Reference	762
8.643.1 Detailed Description	762
8.643.2 Field Documentation	762

8.643.2.1 displayCondition . . . . .	762
8.643.2.2 spn . . . . .	762
8.643.2.3 spnLength . . . . .	762
8.644ServingSystemInfo Struct Reference . . . . .	762
8.644.1 Detailed Description . . . . .	763
8.644.2 Field Documentation . . . . .	764
8.644.2.1 csAttachState . . . . .	764
8.644.2.2 hdrPersonality . . . . .	764
8.644.2.3 psAttachState . . . . .	764
8.644.2.4 radiolInterfaceList . . . . .	764
8.644.2.5 radiolInterfaceNo . . . . .	764
8.644.2.6 registrationState . . . . .	764
8.644.2.7 selectedNetwork . . . . .	764
8.645servSystem Struct Reference . . . . .	764
8.645.1 Detailed Description . . . . .	764
8.645.2 Field Documentation . . . . .	766
8.645.2.1 csAttachState . . . . .	766
8.645.2.2 numRadiolInterfaces . . . . .	766
8.645.2.3 psAttachState . . . . .	766
8.645.2.4 radiolInterface . . . . .	766
8.645.2.5 regState . . . . .	766
8.645.2.6 selNetwork . . . . .	766
8.646sessionInfo Union Reference . . . . .	766
8.646.1 Detailed Description . . . . .	766
8.646.2 Field Documentation . . . . .	766
8.646.2.1 omaDmConfig . . . . .	766
8.646.2.2 omaDmFota . . . . .	767
8.646.2.3 omaDmNotifications . . . . .	767
8.647sessionInfoExt Union Reference . . . . .	767
8.647.1 Detailed Description . . . . .	767
8.647.2 Field Documentation . . . . .	767
8.647.2.1 omaDmConfig . . . . .	767
8.647.2.2 omaDmFota . . . . .	767
8.648sessionInfoTlv Struct Reference . . . . .	767
8.648.1 Detailed Description . . . . .	767
8.648.2 Field Documentation . . . . .	767
8.648.2.1 sessionInfo . . . . .	767
8.648.2.2 sessionType . . . . .	767
8.648.2.3 TlvPresent . . . . .	767
8.649sessionInfoTlvExt Struct Reference . . . . .	767

8.649.1 Detailed Description . . . . .	768
8.649.2 Field Documentation . . . . .	768
8.649.2.1 sessionInfo . . . . .	768
8.649.2.2 sessionType . . . . .	768
8.649.2.3 TlvPresent . . . . .	768
8.650SetAudioPathConfigReq Struct Reference . . . . .	768
8.650.1 Detailed Description . . . . .	768
8.650.2 Field Documentation . . . . .	770
8.650.2.1 pCodecSTGain . . . . .	770
8.650.2.2 pDTMFTXGain . . . . .	770
8.650.2.3 pECMode . . . . .	770
8.650.2.4 pNSEnable . . . . .	770
8.650.2.5 Profile . . . . .	770
8.650.2.6 pRXAGCList . . . . .	770
8.650.2.7 pRXAVCAGCSwitch . . . . .	770
8.650.2.8 pRXAVCList . . . . .	770
8.650.2.9 pRXPCMIIRFitr . . . . .	770
8.650.2.10pTXAGCList . . . . .	770
8.650.2.11pTXAVCSwitch . . . . .	770
8.650.2.12pTXGain . . . . .	770
8.650.2.13pTXPCMIIRFitr . . . . .	770
8.651SetAudioProfileReq Struct Reference . . . . .	770
8.651.1 Detailed Description . . . . .	770
8.651.2 Field Documentation . . . . .	771
8.651.2.1 EarMute . . . . .	771
8.651.2.2 Generator . . . . .	771
8.651.2.3 MicMute . . . . .	771
8.651.2.4 Profile . . . . .	772
8.651.2.5 Volume . . . . .	772
8.652SetAudioVolTLBConfigReq Struct Reference . . . . .	772
8.652.1 Detailed Description . . . . .	772
8.652.2 Field Documentation . . . . .	773
8.652.2.1 Generator . . . . .	773
8.652.2.2 Item . . . . .	773
8.652.2.3 Profile . . . . .	773
8.652.2.4 Volume . . . . .	773
8.652.2.5 VolValue . . . . .	773
8.653SetAudioVolTLBConfigResp Struct Reference . . . . .	773
8.653.1 Detailed Description . . . . .	773
8.653.2 Field Documentation . . . . .	773

8.653.2.1 ResCode . . . . .	773
8.654setCustomSettingV2 Struct Reference . . . . .	773
8.654.1 Detailed Description . . . . .	773
8.654.2 Field Documentation . . . . .	774
8.654.2.1 cust_id . . . . .	774
8.654.2.2 cust_value . . . . .	774
8.654.2.3 value_length . . . . .	774
8.655setDyingGaspCfg Struct Reference . . . . .	774
8.655.1 Detailed Description . . . . .	774
8.655.2 Field Documentation . . . . .	774
8.655.2.1 pDestSMSContent . . . . .	774
8.655.2.2 pDestSMSNum . . . . .	774
8.656SetIMSSMSConfigReq Struct Reference . . . . .	774
8.656.1 Detailed Description . . . . .	775
8.656.2 Field Documentation . . . . .	775
8.656.2.1 pPhoneCtxtURI . . . . .	775
8.656.2.2 pPhoneCtxtURILen . . . . .	775
8.656.2.3 pSMSFormat . . . . .	775
8.656.2.4 pSMSOverIPNwInd . . . . .	775
8.657SetIMSSMSConfigResp Struct Reference . . . . .	775
8.657.1 Detailed Description . . . . .	775
8.657.2 Field Documentation . . . . .	776
8.657.2.1 pSettingResp . . . . .	776
8.658SetIMSUserConfigReq Struct Reference . . . . .	776
8.658.1 Detailed Description . . . . .	776
8.658.2 Field Documentation . . . . .	776
8.658.2.1 pIMSDomain . . . . .	776
8.658.2.2 pIMSDomainLen . . . . .	776
8.659SetIMSUserConfigResp Struct Reference . . . . .	776
8.659.1 Detailed Description . . . . .	776
8.659.2 Field Documentation . . . . .	777
8.659.2.1 pSettingResp . . . . .	777
8.660SetIMSVoIPConfigReq Struct Reference . . . . .	777
8.660.1 Detailed Description . . . . .	777
8.660.2 Field Documentation . . . . .	779
8.660.2.1 pAmrMode . . . . .	779
8.660.2.2 pAmrOctetAligned . . . . .	779
8.660.2.3 pAmrWbEnable . . . . .	779
8.660.2.4 pAmrWBMode . . . . .	779
8.660.2.5 pAmrWBOctetAligned . . . . .	779

8.660.2.6 pMinSessionExpiryTimer . . . . .	779
8.660.2.7 pRingBackTimer . . . . .	779
8.660.2.8 pRingingTimer . . . . .	779
8.660.2.9 pRTPRTCPInactTimer . . . . .	779
8.660.2.10pScrAmrEnable . . . . .	779
8.660.2.11pScrAmrWbEnable . . . . .	779
8.660.2.12pSessionExpiryTimer . . . . .	780
8.661 SetIMSVoIPConfigResp Struct Reference . . . . .	780
8.661.1 Detailed Description . . . . .	780
8.661.2 Field Documentation . . . . .	780
8.661.2.1 pSettingResp . . . . .	780
8.662 SetM2MAudioAVCFGReq Struct Reference . . . . .	780
8.662.1 Detailed Description . . . . .	780
8.662.2 Field Documentation . . . . .	781
8.662.2.1 Device . . . . .	781
8.662.2.2 PIFACEId . . . . .	781
8.662.2.3 pPCMPParams . . . . .	781
8.662.2.4 Profile . . . . .	781
8.663 SetM2MAudioLPBKReq Struct Reference . . . . .	781
8.663.1 Detailed Description . . . . .	781
8.663.2 Field Documentation . . . . .	781
8.663.2.1 Enable . . . . .	781
8.664 SetM2MAudioProfileReq Struct Reference . . . . .	781
8.664.1 Detailed Description . . . . .	782
8.664.2 Field Documentation . . . . .	782
8.664.2.1 pCwtMute . . . . .	782
8.664.2.2 pEarMute . . . . .	782
8.664.2.3 pGenerator . . . . .	782
8.664.2.4 pMicMute . . . . .	783
8.664.2.5 Profile . . . . .	783
8.664.2.6 pVolume . . . . .	783
8.665 SetM2MAudioVolumeReq Struct Reference . . . . .	783
8.665.1 Detailed Description . . . . .	783
8.665.2 Field Documentation . . . . .	783
8.665.2.1 Generator . . . . .	783
8.665.2.2 Level . . . . .	783
8.665.2.3 Profile . . . . .	783
8.666 SetM2MAVMuteReq Struct Reference . . . . .	783
8.666.1 Detailed Description . . . . .	784
8.666.2 Field Documentation . . . . .	784

8.666.2.1 EarMute . . . . .	784
8.666.2.2 MicMute . . . . .	784
8.666.2.3 pCwtMute . . . . .	784
8.666.2.4 Profile . . . . .	784
8.667SetM2MSprkGainReq Struct Reference . . . . .	784
8.667.1 Detailed Description . . . . .	784
8.667.2 Field Documentation . . . . .	785
8.667.2.1 Profile . . . . .	785
8.667.2.2 Value . . . . .	785
8.668setPINProtection Struct Reference . . . . .	785
8.668.1 Detailed Description . . . . .	785
8.668.2 Field Documentation . . . . .	786
8.668.2.1 pinID . . . . .	786
8.668.2.2 pinLength . . . . .	786
8.668.2.3 pinOperation . . . . .	786
8.668.2.4 pinValue . . . . .	786
8.669SetRegMgrConfigReq Struct Reference . . . . .	786
8.669.1 Detailed Description . . . . .	786
8.669.2 Field Documentation . . . . .	787
8.669.2.1 pCSCFPortName . . . . .	787
8.669.2.2 pCSCFPortNameLen . . . . .	787
8.669.2.3 pIMSTestMode . . . . .	787
8.669.2.4 pPriCSCFPort . . . . .	787
8.670SetRegMgrConfigResp Struct Reference . . . . .	787
8.670.1 Detailed Description . . . . .	787
8.670.2 Field Documentation . . . . .	787
8.670.2.1 pSettingResp . . . . .	787
8.671setSignalStrengthInfo Struct Reference . . . . .	788
8.671.1 Detailed Description . . . . .	788
8.671.2 Field Documentation . . . . .	792
8.671.2.1 pCDMAECIODelta . . . . .	792
8.671.2.2 pCDMAECIOThresh . . . . .	792
8.671.2.3 pCDMARSSIDelta . . . . .	792
8.671.2.4 pCDMARSSIThresh . . . . .	792
8.671.2.5 pGSMRSSIDelta . . . . .	792
8.671.2.6 pGSMRSSIThresh . . . . .	792
8.671.2.7 pHDRECIODelta . . . . .	792
8.671.2.8 pHDRECIOTresh . . . . .	792
8.671.2.9 pHDRIODelta . . . . .	792
8.671.2.10pHDRIOThresh . . . . .	792

8.671.2.11pHRRSSIDelta . . . . .	792
8.671.2.12pHRRSSIThresh . . . . .	792
8.671.2.13pHDRSINRDelta . . . . .	792
8.671.2.14pHDRSINRThresh . . . . .	792
8.671.2.15pLTERSRPDelta . . . . .	792
8.671.2.16pLTERSRPThresh . . . . .	792
8.671.2.17pLTERSQRDelta . . . . .	792
8.671.2.18pLTERSQRThresh . . . . .	792
8.671.2.19pLTERSSIDelta . . . . .	792
8.671.2.20pLTERSSIThresh . . . . .	792
8.671.2.21pLTESigRptConfig . . . . .	792
8.671.2.22pLTESNRDelta . . . . .	792
8.671.2.23pLTESNRThresh . . . . .	792
8.671.2.24pTDSCDMAECIODelta . . . . .	792
8.671.2.25pTDSCDMAECIOThresh . . . . .	792
8.671.2.26pTDSCDMARSCPDelta . . . . .	792
8.671.2.27pTDSCDMARSCPThresh . . . . .	792
8.671.2.28pTDSCDMARSSIDelta . . . . .	793
8.671.2.29pTDSCDMARSSIThresh . . . . .	793
8.671.2.30pTDSCDMASINRDelta . . . . .	793
8.671.2.31pTDSCDMASINRThresh . . . . .	793
8.671.2.32pWCDMAECIODelta . . . . .	793
8.671.2.33pWCDMAECIOThresh . . . . .	793
8.671.2.34pWCDMARSSIDelta . . . . .	793
8.671.2.35pWCDMARSSIThresh . . . . .	793
8.672SetSIPConfigReq Struct Reference . . . . .	793
8.672.1 Detailed Description . . . . .	793
8.672.2 Field Documentation . . . . .	794
8.672.2.1 pSigCompEnabled . . . . .	794
8.672.2.2 pSIPLocalPort . . . . .	794
8.672.2.3 pSubscribeTimer . . . . .	794
8.672.2.4 pTimerSIPReg . . . . .	794
8.672.2.5 pTimerT1 . . . . .	794
8.672.2.6 pTimerT2 . . . . .	794
8.672.2.7 pTimerTf . . . . .	794
8.673SetSIPConfigResp Struct Reference . . . . .	794
8.673.1 Detailed Description . . . . .	794
8.673.2 Field Documentation . . . . .	794
8.673.2.1 pSettingResp . . . . .	794
8.674sGetDeviceSeriesResult Struct Reference . . . . .	794

8.674.1 Detailed Description . . . . .	795
8.674.2 Field Documentation . . . . .	795
8.674.2.1 eDevice . . . . .	795
8.674.2.2 uResult . . . . .	795
8.675sidNid Struct Reference . . . . .	795
8.675.1 Detailed Description . . . . .	795
8.675.2 Field Documentation . . . . .	795
8.675.2.1 nid . . . . .	795
8.675.2.2 sid . . . . .	795
8.676sigInfo Struct Reference . . . . .	795
8.676.1 Detailed Description . . . . .	796
8.676.2 Field Documentation . . . . .	797
8.676.2.1 pECIOThresh . . . . .	797
8.676.2.2 pHDRSINRThresh . . . . .	797
8.676.2.3 pIOThresh . . . . .	797
8.676.2.4 pLTESigRptCfg . . . . .	797
8.676.2.5 pLTESNRThresh . . . . .	797
8.676.2.6 pRSRPThresh . . . . .	797
8.676.2.7 pRSRQThresh . . . . .	797
8.676.2.8 pRSSIThresh . . . . .	797
8.676.2.9 pTDSCDMASINRCONFTresh . . . . .	797
8.677signalInfo Struct Reference . . . . .	797
8.677.1 Detailed Description . . . . .	797
8.677.2 Field Documentation . . . . .	797
8.677.2.1 alertPitch . . . . .	798
8.677.2.2 signal . . . . .	798
8.677.2.3 signalType . . . . .	798
8.678SignalStrengthDataType Struct Reference . . . . .	798
8.678.1 Field Documentation . . . . .	798
8.678.1.1 thresholds . . . . .	798
8.678.1.2 thresholdsSize . . . . .	798
8.679slot_t Struct Reference . . . . .	798
8.679.1 Detailed Description . . . . .	798
8.679.2 Field Documentation . . . . .	799
8.679.2.1 bICCID . . . . .	799
8.679.2.2 bICCIDLength . . . . .	799
8.679.2.3 bLogicalSlot . . . . .	799
8.679.2.4 uPhyCardStatus . . . . .	799
8.679.2.5 uPhySlotStatus . . . . .	799
8.680slotInf Struct Reference . . . . .	799



8.680.1 Detailed Description . . . . .	799
8.680.2 Field Documentation . . . . .	801
8.680.2.1 AppStatus . . . . .	801
8.680.2.2 cardState . . . . .	801
8.680.2.3 errorState . . . . .	801
8.680.2.4 numApp . . . . .	801
8.680.2.5 upinRetries . . . . .	801
8.680.2.6 upinState . . . . .	801
8.680.2.7 upukRetries . . . . .	801
8.681 slotInfo Struct Reference . . . . .	801
8.681.1 Detailed Description . . . . .	801
8.681.2 Field Documentation . . . . .	803
8.681.2.1 AppStatus . . . . .	803
8.681.2.2 cardState . . . . .	803
8.681.2.3 errorState . . . . .	803
8.681.2.4 numApp . . . . .	803
8.681.2.5 upinRetries . . . . .	803
8.681.2.6 upinState . . . . .	803
8.681.2.7 upukRetries . . . . .	803
8.682 slots_t Struct Reference . . . . .	803
8.682.1 Field Documentation . . . . .	803
8.682.1.1 uimSlotStatus . . . . .	803
8.683 slqsautoconnect Struct Reference . . . . .	803
8.683.1 Detailed Description . . . . .	803
8.683.2 Field Documentation . . . . .	804
8.683.2.1 acroamsetting . . . . .	804
8.683.2.2 acsetting . . . . .	804
8.683.2.3 action . . . . .	804
8.684 SLQSDDeleteProfileParams Struct Reference . . . . .	804
8.684.1 Detailed Description . . . . .	804
8.684.2 Field Documentation . . . . .	805
8.684.2.1 profileIndex . . . . .	805
8.684.2.2 profileType . . . . .	805
8.685 slqsfwinfo_s Struct Reference . . . . .	805
8.685.1 Detailed Description . . . . .	805
8.685.2 Field Documentation . . . . .	806
8.685.2.1 appversion_str . . . . .	806
8.685.2.2 bootversion_str . . . . .	806
8.685.2.3 carrier_str . . . . .	806
8.685.2.4 cur_carr_name . . . . .	806

8.685.2.5 cur_carr_rev . . . . .	806
8.685.2.6 modelid_str . . . . .	806
8.685.2.7 packageid_str . . . . .	806
8.685.2.8 priversion_str . . . . .	806
8.685.2.9 sku_str . . . . .	806
8.686SlqsNas3GppNetworkInfo Struct Reference . . . . .	806
8.686.1 Detailed Description . . . . .	806
8.686.2 Field Documentation . . . . .	807
8.686.2.1 Description . . . . .	807
8.686.2.2 Forbidden . . . . .	807
8.686.2.3 InUse . . . . .	807
8.686.2.4 MCC . . . . .	808
8.686.2.5 MNC . . . . .	808
8.686.2.6 Preferred . . . . .	808
8.686.2.7 Roaming . . . . .	808
8.687SlqsNasPcsDigit Struct Reference . . . . .	808
8.687.1 Detailed Description . . . . .	808
8.687.2 Field Documentation . . . . .	808
8.687.2.1 includes_pcs_digit . . . . .	808
8.687.2.2 MCC . . . . .	808
8.687.2.3 MNC . . . . .	808
8.688slqssendasyncsmsparams_s Struct Reference . . . . .	808
8.688.1 Detailed Description . . . . .	809
8.688.2 Field Documentation . . . . .	810
8.688.2.1 messageFormat . . . . .	810
8.688.2.2 messageSize . . . . .	810
8.688.2.3 pFollowOnDC . . . . .	810
8.688.2.4 pForceOnDC . . . . .	811
8.688.2.5 pLinktimer . . . . .	811
8.688.2.6 pMessage . . . . .	811
8.688.2.7 pRetryMessage . . . . .	811
8.688.2.8 pRetryMessageld . . . . .	811
8.688.2.9 pServiceOption . . . . .	811
8.688.2.10pSmsOnlms . . . . .	811
8.688.2.11pUserData . . . . .	811
8.689slqssendsmsparams_s Struct Reference . . . . .	811
8.689.1 Detailed Description . . . . .	811
8.689.2 Field Documentation . . . . .	812
8.689.2.1 messageFailureCode . . . . .	812
8.689.2.2 messageFormat . . . . .	812

8.689.2.3 messageID . . . . .	812
8.689.2.4 messageSize . . . . .	812
8.689.2.5 pLinktimer . . . . .	812
8.689.2.6 pMessage . . . . .	812
8.689.2.7 pSmsOnlms . . . . .	812
8.690slqsSessionStateInfo Struct Reference . . . . .	812
8.690.1 Detailed Description . . . . .	812
8.690.2 Field Documentation . . . . .	813
8.690.2.1 pQmiInterfaceInfo . . . . .	813
8.690.2.2 reconfiguration_required . . . . .	813
8.690.2.3 sessionEndReason . . . . .	813
8.690.2.4 state . . . . .	813
8.691slqsSignalStrengthInfo Struct Reference . . . . .	813
8.691.1 Detailed Description . . . . .	814
8.691.2 Field Documentation . . . . .	816
8.691.2.1 ecioList . . . . .	816
8.691.2.2 ecioListLen . . . . .	816
8.691.2.3 errorRateList . . . . .	816
8.691.2.4 errorRateListLen . . . . .	817
8.691.2.5 lo . . . . .	817
8.691.2.6 ltersrp . . . . .	817
8.691.2.7 ltesnr . . . . .	817
8.691.2.8 rsrqInfo . . . . .	817
8.691.2.9 rxSignalStrengthList . . . . .	817
8.691.2.10rxSignalStrengthListLen . . . . .	817
8.691.2.11signalStrengthReqMask . . . . .	817
8.691.2.12sinr . . . . .	817
8.692SLQSSignalStrengthsIndReq Struct Reference . . . . .	817
8.692.1 Detailed Description . . . . .	817
8.692.2 Field Documentation . . . . .	818
8.692.2.1 ecioDelta . . . . .	818
8.692.2.2 ecioThresholdList . . . . .	819
8.692.2.3 ecioThresholdListLen . . . . .	819
8.692.2.4 ioDelta . . . . .	819
8.692.2.5 lteRsrpDelta . . . . .	819
8.692.2.6 lteSnrDelta . . . . .	819
8.692.2.7 rsrqDelta . . . . .	819
8.692.2.8 rxSignalStrengthDelta . . . . .	819
8.692.2.9 sinrDelta . . . . .	819
8.692.2.10sinrThresholdList . . . . .	819

8.692.2.1 <code>lsnrThresholdListLen</code> . . . . .	819
8.693 <code>SLQSSignalStrengthsInformation</code> Struct Reference . . . . .	819
8.693.1 Detailed Description . . . . .	819
8.693.2 Field Documentation . . . . .	820
8.693.2.1 <code>eciInfo</code> . . . . .	820
8.693.2.2 <code>errorRateInfo</code> . . . . .	820
8.693.2.3 <code>io</code> . . . . .	820
8.693.2.4 <code>lteRsrpInfo</code> . . . . .	820
8.693.2.5 <code>lteSnrInfo</code> . . . . .	820
8.693.2.6 <code>rsrqInfo</code> . . . . .	820
8.693.2.7 <code>rxSignalStrengthInfo</code> . . . . .	820
8.693.2.8 <code>sinr</code> . . . . .	821
8.694 <code>slqsWdsEventInfo</code> Struct Reference . . . . .	821
8.694.1 Detailed Description . . . . .	821
8.694.2 Field Documentation . . . . .	823
8.694.2.1 <code>pDataBearer</code> . . . . .	823
8.694.2.2 <code>pDormancyStatus</code> . . . . .	823
8.694.2.3 <code>pPacketsCountRX</code> . . . . .	823
8.694.2.4 <code>pPacketsCountTX</code> . . . . .	823
8.694.2.5 <code>pQmiInterfaceInfo</code> . . . . .	823
8.694.2.6 <code>pTotalBytesRX</code> . . . . .	823
8.694.2.7 <code>pTotalBytesTX</code> . . . . .	823
8.695 <code>SMSAsyncRawSend_s</code> Struct Reference . . . . .	823
8.695.1 Detailed Description . . . . .	823
8.695.2 Field Documentation . . . . .	825
8.695.2.1 <code>alphaIDLen</code> . . . . .	825
8.695.2.2 <code>causeCode</code> . . . . .	825
8.695.2.3 <code>errorClass</code> . . . . .	825
8.695.2.4 <code>messageID</code> . . . . .	825
8.695.2.5 <code>msgDelFailureCause</code> . . . . .	825
8.695.2.6 <code>msgDelFailureType</code> . . . . .	825
8.695.2.7 <code>pAlphaID</code> . . . . .	825
8.695.2.8 <code>RPCause</code> . . . . .	825
8.695.2.9 <code>sendStatus</code> . . . . .	825
8.695.2.10 <code>TPCause</code> . . . . .	825
8.695.2.11 <code>userData</code> . . . . .	825
8.696 <code>sMSCAddress</code> Struct Reference . . . . .	825
8.696.1 Detailed Description . . . . .	825
8.696.2 Field Documentation . . . . .	826
8.696.2.1 <code>data</code> . . . . .	826

8.696.2.2 length	826
8.697SMSCAddress Struct Reference	826
8.697.1 Detailed Description	826
8.697.2 Field Documentation	826
8.697.2.1 data	826
8.697.2.2 length	826
8.698sMSCAddressTlv Struct Reference	826
8.698.1 Detailed Description	827
8.698.2 Field Documentation	827
8.698.2.1 SMSCInfo	827
8.698.2.2 TlvPresent	827
8.699sMSEtwsMessage Struct Reference	827
8.699.1 Detailed Description	827
8.699.2 Field Documentation	827
8.699.2.1 data	827
8.699.2.2 length	827
8.699.2.3 notificationType	827
8.700SMSEtwsMessage Struct Reference	827
8.700.1 Detailed Description	828
8.700.2 Field Documentation	828
8.700.2.1 data	828
8.700.2.2 length	828
8.700.2.3 notificationType	828
8.701sMSEtwsMessageTlv Struct Reference	828
8.701.1 Detailed Description	828
8.701.2 Field Documentation	828
8.701.2.1 EtwsMessageInfo	829
8.701.2.2 TlvPresent	829
8.702sMSEtwsPlmn Struct Reference	829
8.702.1 Detailed Description	829
8.702.2 Field Documentation	829
8.702.2.1 mobileCountryCode	829
8.702.2.2 mobileNetworkCode	829
8.703SMSEtwsPlmn Struct Reference	829
8.703.1 Detailed Description	829
8.703.2 Field Documentation	830
8.703.2.1 mobileCountryCode	830
8.703.2.2 mobileNetworkCode	830
8.704SMSEventInfo_s Struct Reference	830
8.704.1 Detailed Description	830

8.704.2 Field Documentation . . . . .	831
8.704.2.1 pEtwSMessageInfo . . . . .	831
8.704.2.2 pEtwSPlmnInfo . . . . .	831
8.704.2.3 pMessageModeInfo . . . . .	831
8.704.2.4 pMTMessageInfo . . . . .	831
8.704.2.5 pSMSCAddressInfo . . . . .	831
8.704.2.6 pSMSOnIMSInfo . . . . .	831
8.704.2.7 pTransferRouteMTMessageInfo . . . . .	831
8.704.2.8 smsEventType . . . . .	831
8.705smsMaxStorageSizeReq Struct Reference . . . . .	831
8.705.1 Detailed Description . . . . .	831
8.705.2 Field Documentation . . . . .	832
8.705.2.1 pMessageMode . . . . .	832
8.705.2.2 storageType . . . . .	832
8.706smsMaxStorageSizeResp Struct Reference . . . . .	832
8.706.1 Detailed Description . . . . .	832
8.706.2 Field Documentation . . . . .	832
8.706.2.1 freeSlots . . . . .	832
8.706.2.2 maxStorageSize . . . . .	832
8.707SMSMemoryInfo Struct Reference . . . . .	832
8.707.1 Detailed Description . . . . .	833
8.707.2 Field Documentation . . . . .	834
8.707.2.1 messageMode . . . . .	834
8.707.2.2 storageType . . . . .	834
8.708sMSMessageMode Struct Reference . . . . .	834
8.708.1 Detailed Description . . . . .	834
8.708.2 Field Documentation . . . . .	834
8.708.2.1 messageMode . . . . .	834
8.709SMSMessageMode Struct Reference . . . . .	834
8.709.1 Detailed Description . . . . .	834
8.709.2 Field Documentation . . . . .	834
8.709.2.1 messageMode . . . . .	835
8.710smsMsgprotocolResp Struct Reference . . . . .	835
8.710.1 Detailed Description . . . . .	835
8.710.2 Field Documentation . . . . .	835
8.710.2.1 msgProtocol . . . . .	835
8.711sMSMTMessage Struct Reference . . . . .	835
8.711.1 Detailed Description . . . . .	835
8.711.2 Field Documentation . . . . .	835
8.711.2.1 messageIndex . . . . .	835

8.711.2.2 storageType . . . . .	835
8.712SMSMTMessage Struct Reference . . . . .	835
8.712.1 Detailed Description . . . . .	836
8.712.2 Field Documentation . . . . .	836
8.712.2.1 messageIndex . . . . .	836
8.712.2.2 storageType . . . . .	836
8.713sMSOnIMS Struct Reference . . . . .	836
8.713.1 Detailed Description . . . . .	836
8.713.2 Field Documentation . . . . .	836
8.713.2.1 smsOnIMS . . . . .	836
8.714SMSOnIMS Struct Reference . . . . .	836
8.714.1 Detailed Description . . . . .	836
8.714.2 Field Documentation . . . . .	837
8.714.2.1 smsOnIMS . . . . .	837
8.715sMSOnIMSTlv Struct Reference . . . . .	837
8.715.1 Detailed Description . . . . .	837
8.715.2 Field Documentation . . . . .	837
8.715.2.1 IMSInfo . . . . .	837
8.715.2.2 TlvPresent . . . . .	837
8.716smsRouteEntry Struct Reference . . . . .	837
8.716.1 Detailed Description . . . . .	837
8.716.2 Field Documentation . . . . .	839
8.716.2.1 messageClass . . . . .	839
8.716.2.2 messageType . . . . .	839
8.716.2.3 receiptAction . . . . .	839
8.716.2.4 routeStorage . . . . .	839
8.717smsSetRoutesReq Struct Reference . . . . .	839
8.717.1 Detailed Description . . . . .	839
8.717.2 Field Documentation . . . . .	839
8.717.2.1 numOfRoutes . . . . .	839
8.717.2.2 pTransferStatusReport . . . . .	839
8.717.2.3 routeList . . . . .	839
8.718sMSTransferRouteMTMessage Struct Reference . . . . .	839
8.718.1 Detailed Description . . . . .	840
8.718.2 Field Documentation . . . . .	840
8.718.2.1 ackIndicator . . . . .	840
8.718.2.2 data . . . . .	840
8.718.2.3 format . . . . .	840
8.718.2.4 length . . . . .	840
8.718.2.5 transactionID . . . . .	840

8.719SMSTransferRouteMTMessage Struct Reference	840
8.719.1 Detailed Description	840
8.719.2 Field Documentation	841
8.719.2.1 ackIndicator	841
8.719.2.2 data	841
8.719.2.3 format	841
8.719.2.4 length	841
8.719.2.5 transactionID	841
8.720sQosFlowStat Struct Reference	841
8.720.1 Detailed Description	841
8.720.2 Field Documentation	842
8.720.2.1 bearerId	842
8.720.2.2 tx_bytes	842
8.720.2.3 tx_bytes_drp	842
8.720.2.4 tx_pkt	842
8.720.2.5 tx_pkt_drp	842
8.721sQosStat Struct Reference	842
8.721.1 Detailed Description	842
8.721.2 Field Documentation	843
8.721.2.1 apnId	843
8.721.2.2 numQosFlow	843
8.721.2.3 qosFlow	843
8.721.2.4 total_rx_bytes	843
8.721.2.5 total_rx_pkt	843
8.721.2.6 total_tx_bytes	843
8.721.2.7 total_tx_bytes_drp	843
8.721.2.8 total_tx_pkt	843
8.721.2.9 total_tx_pkt_drp	843
8.722SrvStatusInfo Struct Reference	844
8.722.1 Detailed Description	844
8.722.2 Field Documentation	844
8.722.2.1 isPrefDataPath	844
8.722.2.2 srvStatus	844
8.723ssdatasession_params Struct Reference	844
8.723.1 Detailed Description	845
8.723.2 Field Documentation	846
8.723.2.1 action	846
8.723.2.2 failureReason	847
8.723.2.3 failureReasonv4	847
8.723.2.4 failureReasonv6	847



8.723.2.5 instanceId	847
8.723.2.6 ipfamily	847
8.723.2.7 pAuthentication	847
8.723.2.8 pPassword	847
8.723.2.9 pProfileId3GPP	847
8.723.2.10pProfileId3GPP2	847
8.723.2.11pTechnology	847
8.723.2.12pUsername	847
8.723.2.13cv4	847
8.723.2.14cv6	847
8.723.2.15sessionId	847
8.723.2.16v4sessionId	847
8.723.2.17v6sessionId	847
8.723.2.18verbFailReason	847
8.723.2.19verbFailReasonType	847
8.724SupportedMsgList Struct Reference	847
8.724.1 Detailed Description	847
8.724.2 Field Documentation	848
8.724.2.1 supportedMsgLen	848
8.724.2.2 supportedMsgs	848
8.725SUPSInfo Struct Reference	848
8.725.1 Detailed Description	848
8.725.2 Field Documentation	848
8.725.2.1 isModByCC	849
8.725.2.2 svcType	849
8.726SV Struct Reference	849
8.726.1 Detailed Description	849
8.726.2 Field Documentation	849
8.726.2.1 id	849
8.726.2.2 mask	850
8.726.2.3 system	850
8.727SVInfo Struct Reference	850
8.727.1 Detailed Description	850
8.727.2 Field Documentation	850
8.727.2.1 len	850
8.727.2.2 pSV	850
8.728svUsedforFix_s Struct Reference	850
8.728.1 Detailed Description	850
8.728.2 Field Documentation	851
8.728.2.1 gnssSvUsedList	851

8.728.2.2 gnssSvUsedList_len . . . . .	851
8.729SWI_STRUCT_CarrierImage Struct Reference . . . . .	851
8.729.1 Detailed Description . . . . .	851
8.729.2 Field Documentation . . . . .	852
8.729.2.1 m_FwBuildId . . . . .	852
8.729.2.2 m_FwImageld . . . . .	852
8.729.2.3 m_nCarrierId . . . . .	852
8.729.2.4 m_nFolderId . . . . .	852
8.729.2.5 m_nStorage . . . . .	852
8.729.2.6 m_PriBuildId . . . . .	852
8.729.2.7 m_PriImageld . . . . .	852
8.730SwiLocGetAutoStartResp Struct Reference . . . . .	852
8.730.1 Detailed Description . . . . .	853
8.730.2 Field Documentation . . . . .	855
8.730.2.1 fix_rate . . . . .	855
8.730.2.2 fix_rate_reported . . . . .	855
8.730.2.3 fix_type . . . . .	855
8.730.2.4 fix_type_reported . . . . .	855
8.730.2.5 function . . . . .	855
8.730.2.6 function_reported . . . . .	855
8.730.2.7 max_dist . . . . .	855
8.730.2.8 max_dist_reported . . . . .	855
8.730.2.9 max_time . . . . .	855
8.730.2.10max_time_reported . . . . .	855
8.731SwiLocSetAutoStartReq Struct Reference . . . . .	855
8.731.1 Detailed Description . . . . .	855
8.731.2 Field Documentation . . . . .	857
8.731.2.1 fix_rate . . . . .	857
8.731.2.2 fix_type . . . . .	857
8.731.2.3 function . . . . .	857
8.731.2.4 max_dist . . . . .	857
8.731.2.5 max_time . . . . .	857
8.731.2.6 set_fix_rate . . . . .	857
8.731.2.7 set_fix_type . . . . .	857
8.731.2.8 set_function . . . . .	857
8.731.2.9 set_max_dist . . . . .	857
8.731.2.10set_max_time . . . . .	857
8.732swiModemStatusResp Struct Reference . . . . .	857
8.732.1 Detailed Description . . . . .	857
8.732.2 Field Documentation . . . . .	857

8.732.2.1 commonInfo . . . . .	857
8.732.2.2 pLTEInfo . . . . .	858
8.733SwtOTAMsg_s Struct Reference . . . . .	858
8.733.1 Detailed Description . . . . .	858
8.733.2 Field Documentation . . . . .	858
8.733.2.1 data . . . . .	858
8.733.2.2 data_len . . . . .	858
8.733.2.3 pLteNasRelInfo . . . . .	858
8.733.2.4 pTime . . . . .	859
8.733.2.5 type . . . . .	859
8.734swiPDPRuntimeSettingsReq Struct Reference . . . . .	859
8.734.1 Detailed Description . . . . .	859
8.734.2 Field Documentation . . . . .	859
8.734.2.1 contextId . . . . .	859
8.734.2.2 contextType . . . . .	859
8.735swiPDPRuntimeSettingsResp Struct Reference . . . . .	859
8.735.1 Detailed Description . . . . .	860
8.735.2 Field Documentation . . . . .	861
8.735.2.1 pAPNName . . . . .	861
8.735.2.2 pBearerId . . . . .	861
8.735.2.3 pContextId . . . . .	861
8.735.2.4 pIPv4Address . . . . .	861
8.735.2.5 pIPv4GWAddress . . . . .	861
8.735.2.6 pIPv6Address . . . . .	862
8.735.2.7 pIPv6GWAddress . . . . .	862
8.735.2.8 pPrDNSIPv4Address . . . . .	862
8.735.2.9 pPrDNSIPv6Address . . . . .	862
8.735.2.10pPrPCSCFIPv4Address . . . . .	862
8.735.2.11pPrPCSCFIPv6Address . . . . .	862
8.735.2.12pSeDNSIPv4Address . . . . .	862
8.735.2.13pSeDNSIPv6Address . . . . .	862
8.735.2.14pSePCSCFIPv4Address . . . . .	862
8.735.2.15pSePCSCFIPv6Address . . . . .	862
8.736swiQosFilter Struct Reference . . . . .	862
8.736.1 Detailed Description . . . . .	862
8.736.2 Field Documentation . . . . .	864
8.736.2.1 index . . . . .	864
8.736.2.2 pEspSpi . . . . .	864
8.736.2.3 pId . . . . .	864
8.736.2.4 pIPv4DstAddr . . . . .	864

8.736.2.5 pIPv4SrcAddr . . . . .	864
8.736.2.6 pIPv6DstAddr . . . . .	864
8.736.2.7 pIPv6Label . . . . .	864
8.736.2.8 pIPv6SrcAddr . . . . .	864
8.736.2.9 pIPv6TrafCls . . . . .	864
8.736.2.10pNxtHdrProto . . . . .	864
8.736.2.11pPrecedence . . . . .	864
8.736.2.12pTCPDstPort . . . . .	864
8.736.2.13pTCPSrcPort . . . . .	864
8.736.2.14pTos . . . . .	864
8.736.2.15pTranDstPort . . . . .	864
8.736.2.16pTranSrcPort . . . . .	864
8.736.2.17pUDPDstPort . . . . .	864
8.736.2.18pUDPSrcPort . . . . .	864
8.736.2.19version . . . . .	864
8.737swiQosFlow Struct Reference . . . . .	864
8.737.1 Detailed Description . . . . .	865
8.737.2 Field Documentation . . . . .	867
8.737.2.1 index . . . . .	867
8.737.2.2 p3GPP2Pri . . . . .	867
8.737.2.3 p3GPPImCn . . . . .	867
8.737.2.4 p3GPPResResidualBER . . . . .	867
8.737.2.5 p3GPPSigInd . . . . .	867
8.737.2.6 p3GPPTraHdlPri . . . . .	867
8.737.2.7 pDataRate . . . . .	868
8.737.2.8 pJitter . . . . .	868
8.737.2.9 pLatency . . . . .	868
8.737.2.10pLteQci . . . . .	868
8.737.2.11pMaxAllowedPktSz . . . . .	868
8.737.2.12pMinPolicedPktSz . . . . .	868
8.737.2.13pPktErrRate . . . . .	868
8.737.2.14pProfileId3GPP2 . . . . .	868
8.737.2.15pTokenBucket . . . . .	868
8.737.2.16pTrafficClass . . . . .	868
8.738swiQosGranted Struct Reference . . . . .	868
8.738.1 Detailed Description . . . . .	868
8.738.2 Field Documentation . . . . .	868
8.738.2.1 pRxFlow . . . . .	868
8.738.2.2 pTxFlow . . . . .	868
8.739swiQosIds Struct Reference . . . . .	868

8.739.1 Detailed Description . . . . .	868
8.739.2 Field Documentation . . . . .	869
8.739.2.1 plds . . . . .	869
8.739.2.2 sz . . . . .	869
8.740swiQosModifyReq Struct Reference . . . . .	869
8.740.1 Detailed Description . . . . .	869
8.740.2 Field Documentation . . . . .	869
8.740.2.1 id . . . . .	869
8.740.2.2 pRxFilter . . . . .	869
8.740.2.3 pRxFlow . . . . .	869
8.740.2.4 pTxFilter . . . . .	869
8.740.2.5 pTxFlow . . . . .	869
8.741swiQosReq Struct Reference . . . . .	869
8.741.1 Detailed Description . . . . .	870
8.741.2 Field Documentation . . . . .	870
8.741.2.1 index . . . . .	870
8.741.2.2 pRxFilter . . . . .	870
8.741.2.3 pRxFlow . . . . .	870
8.741.2.4 pTxFilter . . . . .	870
8.741.2.5 pTxFlow . . . . .	870
8.742swiRMTrasferStaticsReq Struct Reference . . . . .	870
8.742.1 Detailed Description . . . . .	870
8.742.2 Field Documentation . . . . .	871
8.742.2.1 bResetStatistics . . . . .	871
8.742.2.2 ulMask . . . . .	871
8.743sysInfoCommon Struct Reference . . . . .	871
8.743.1 Detailed Description . . . . .	871
8.743.2 Field Documentation . . . . .	873
8.743.2.1 isSysForbidden . . . . .	873
8.743.2.2 isSysForbiddenValid . . . . .	873
8.743.2.3 roamStatus . . . . .	873
8.743.2.4 roamStatusValid . . . . .	873
8.743.2.5 srvCapability . . . . .	874
8.743.2.6 srvCapabilityValid . . . . .	874
8.743.2.7 srvDomain . . . . .	874
8.743.2.8 srvDomainValid . . . . .	874
8.744TDSCDMAECIOThresh Struct Reference . . . . .	874
8.744.1 Detailed Description . . . . .	874
8.744.2 Field Documentation . . . . .	874
8.744.2.1 pTDSCDMAECIOThreshList . . . . .	874

8.744.2.2 TDSCDMAECIOThreshListLen . . . . .	874
8.745TDSCDMARSCPThresh Struct Reference . . . . .	874
8.745.1 Detailed Description . . . . .	874
8.745.2 Field Documentation . . . . .	875
8.745.2.1 pTDSCDMARSCPThreshList . . . . .	875
8.745.2.2 TDSCDMARSCPThreshListLen . . . . .	875
8.746TDSCDMARSSIThresh Struct Reference . . . . .	875
8.746.1 Detailed Description . . . . .	875
8.746.2 Field Documentation . . . . .	875
8.746.2.1 pTDSCDMARSSIThreshList . . . . .	875
8.746.2.2 TDSCDMARSSIThreshListLen . . . . .	875
8.747TDSCDMASigInfoExt Struct Reference . . . . .	875
8.747.1 Detailed Description . . . . .	876
8.747.2 Field Documentation . . . . .	876
8.747.2.1 ecio . . . . .	876
8.747.2.2 rscp . . . . .	876
8.747.2.3 rssi . . . . .	876
8.747.2.4 sinr . . . . .	876
8.748tdscdmaSigInfoExt Struct Reference . . . . .	876
8.748.1 Detailed Description . . . . .	876
8.748.2 Field Documentation . . . . .	876
8.748.2.1 ecio . . . . .	877
8.748.2.2 rscp . . . . .	877
8.748.2.3 rssi . . . . .	877
8.748.2.4 sinr . . . . .	877
8.749TDSCDMASINRCONFThresh Struct Reference . . . . .	877
8.749.1 Detailed Description . . . . .	877
8.749.2 Field Documentation . . . . .	877
8.749.2.1 pTDSCDMASINRCONFThreshList . . . . .	877
8.749.2.2 TDSCDMASINRCONFThreshListLen . . . . .	877
8.750TDSCDMASINRThresh Struct Reference . . . . .	877
8.750.1 Detailed Description . . . . .	877
8.750.2 Field Documentation . . . . .	878
8.750.2.1 pTDSCDMASINRThreshList . . . . .	878
8.750.2.2 TDSCDMASINRThreshListLen . . . . .	878
8.751temperatureData Struct Reference . . . . .	878
8.751.1 Detailed Description . . . . .	878
8.751.2 Field Documentation . . . . .	879
8.751.2.1 temperature . . . . .	879
8.751.2.2 temperatureDataLen . . . . .	879

8.751.2.3 timeOfFirstSample . . . . .	879
8.751.2.4 timeOffset . . . . .	879
8.751.2.5 timeSource . . . . .	879
8.752TFTIDParams Struct Reference . . . . .	879
8.752.1 Detailed Description . . . . .	880
8.752.2 Field Documentation . . . . .	881
8.752.2.1 destPortRangeEnd . . . . .	881
8.752.2.2 destPortRangeStart . . . . .	881
8.752.2.3 eValid . . . . .	881
8.752.2.4 filterId . . . . .	881
8.752.2.5 flowLabel . . . . .	881
8.752.2.6 IPSECSPi . . . . .	881
8.752.2.7 ipVersion . . . . .	881
8.752.2.8 nextHeader . . . . .	881
8.752.2.9 pSourceIP . . . . .	881
8.752.2.10sourceIPMask . . . . .	881
8.752.2.11srcPortRangeEnd . . . . .	881
8.752.2.12srcPortRangeStart . . . . .	881
8.752.2.13osMask . . . . .	881
8.753timeInfo Struct Reference . . . . .	881
8.753.1 Detailed Description . . . . .	882
8.753.2 Field Documentation . . . . .	883
8.753.2.1 day . . . . .	883
8.753.2.2 dayLtSavingAdj . . . . .	883
8.753.2.3 dayOfWeek . . . . .	883
8.753.2.4 hour . . . . .	883
8.753.2.5 minute . . . . .	883
8.753.2.6 month . . . . .	883
8.753.2.7 radioInterface . . . . .	883
8.753.2.8 second . . . . .	883
8.753.2.9 timeZone . . . . .	883
8.753.2.10TlvPresent . . . . .	883
8.753.2.11year . . . . .	883
8.754TmdDeRegNotMitigationLvlReq Struct Reference . . . . .	883
8.754.1 Detailed Description . . . . .	884
8.754.2 Field Documentation . . . . .	884
8.754.2.1 mitigationDevID . . . . .	884
8.754.2.2 mitigationDevIDLen . . . . .	884
8.755TmdGetMitigationDevListResp Struct Reference . . . . .	884
8.755.1 Detailed Description . . . . .	884

8.755.2 Field Documentation . . . . .	884
8.755.2.1 pMitigationDevList . . . . .	884
8.755.2.2 pMitigationDevListLen . . . . .	884
8.756TmdGetMitigationLvlReq Struct Reference . . . . .	885
8.756.1 Detailed Description . . . . .	885
8.756.2 Field Documentation . . . . .	885
8.756.2.1 mitigationDevID . . . . .	885
8.756.2.2 mitigationDevIDLen . . . . .	885
8.757TmdGetMitigationLvlResp Struct Reference . . . . .	885
8.757.1 Detailed Description . . . . .	885
8.757.2 Field Documentation . . . . .	886
8.757.2.1 pCurrentmitigationLvl . . . . .	886
8.757.2.2 pReqMitigationLvl . . . . .	886
8.758TmdMitigationLvlIndReq Struct Reference . . . . .	886
8.758.1 Detailed Description . . . . .	886
8.758.2 Field Documentation . . . . .	886
8.758.2.1 mitigationDevID . . . . .	886
8.758.2.2 mitigationDevIDLen . . . . .	886
8.759TmdRegNotMitigationLvlReq Struct Reference . . . . .	886
8.759.1 Detailed Description . . . . .	886
8.759.2 Field Documentation . . . . .	887
8.759.2.1 mitigationDevID . . . . .	887
8.759.2.2 mitigationDevIDLen . . . . .	887
8.760tokenBucket Struct Reference . . . . .	887
8.760.1 Detailed Description . . . . .	887
8.760.2 Field Documentation . . . . .	887
8.760.2.1 bucketSz . . . . .	887
8.760.2.2 peakRate . . . . .	887
8.760.2.3 tokenRate . . . . .	887
8.761Tos Struct Reference . . . . .	887
8.761.1 Detailed Description . . . . .	888
8.761.2 Field Documentation . . . . .	889
8.761.2.1 mask . . . . .	889
8.761.2.2 val . . . . .	889
8.762transferRouteMessageTlv Struct Reference . . . . .	889
8.762.1 Detailed Description . . . . .	889
8.762.2 Field Documentation . . . . .	889
8.762.2.1 TlvPresent . . . . .	889
8.762.2.2 TransferRouteMTMessageInfo . . . . .	889
8.763transferStatInd Struct Reference . . . . .	889



8.763.1 Detailed Description . . . . .	890
8.763.2 Field Documentation . . . . .	891
8.763.2.1 StatsMask . . . . .	891
8.763.2.2 StatsPeriod . . . . .	891
8.764TransferStatInd Struct Reference . . . . .	891
8.764.1 Detailed Description . . . . .	891
8.764.2 Field Documentation . . . . .	891
8.764.2.1 StatsMask . . . . .	891
8.764.2.2 StatsPeriod . . . . .	891
8.765TransferStatsDataType Struct Reference . . . . .	891
8.765.1 Field Documentation . . . . .	892
8.765.1.1 interval . . . . .	892
8.766TrStatInd Struct Reference . . . . .	892
8.766.1 Detailed Description . . . . .	892
8.766.2 Field Documentation . . . . .	892
8.766.2.1 statsMask . . . . .	892
8.766.2.2 statsPeriod . . . . .	892
8.767trueIMSI Struct Reference . . . . .	892
8.767.1 Detailed Description . . . . .	893
8.767.2 Field Documentation . . . . .	893
8.767.2.1 imsiT1112 . . . . .	893
8.767.2.2 imsiTaddrNum . . . . .	893
8.767.2.3 imsiTS1 . . . . .	893
8.767.2.4 imsiTS2 . . . . .	893
8.767.2.5 mccT . . . . .	893
8.768TXAGCList Struct Reference . . . . .	893
8.768.1 Detailed Description . . . . .	894
8.768.2 Field Documentation . . . . .	894
8.768.2.1 pTXAIG . . . . .	894
8.768.2.2 pTXComprSlope . . . . .	894
8.768.2.3 pTXComprThres . . . . .	894
8.768.2.4 pTXExpSlope . . . . .	894
8.768.2.5 pTXExpThres . . . . .	894
8.768.2.6 pTXStaticGain . . . . .	894
8.769txInfo Struct Reference . . . . .	894
8.769.1 Detailed Description . . . . .	894
8.769.2 Field Documentation . . . . .	895
8.769.2.1 isInTraffic . . . . .	895
8.769.2.2 txPower . . . . .	895
8.770TXPCMIIRFtr Struct Reference . . . . .	895

8.770.1 Detailed Description . . . . .	895
8.770.2 Field Documentation . . . . .	897
8.770.2.1 pFlag . . . . .	897
8.770.2.2 pStage0Val . . . . .	897
8.770.2.3 pStage1Val . . . . .	897
8.770.2.4 pStage2Val . . . . .	897
8.770.2.5 pStage3Val . . . . .	897
8.770.2.6 pStage4Val . . . . .	897
8.770.2.7 pStageCnt . . . . .	897
8.771 uim_appStatus Struct Reference . . . . .	897
8.771.1 Detailed Description . . . . .	897
8.771.2 Field Documentation . . . . .	900
8.771.2.1 aidLength . . . . .	900
8.771.2.2 aidVal . . . . .	900
8.771.2.3 appState . . . . .	900
8.771.2.4 appType . . . . .	900
8.771.2.5 persoFeature . . . . .	900
8.771.2.6 persoRetries . . . . .	900
8.771.2.7 persoState . . . . .	900
8.771.2.8 persoUnblockRetries . . . . .	900
8.771.2.9 pin1Retries . . . . .	900
8.771.2.10 pin1State . . . . .	900
8.771.2.11 pin2Retries . . . . .	900
8.771.2.12 pin2State . . . . .	900
8.771.2.13 puk1Retries . . . . .	900
8.771.2.14 puk2Retries . . . . .	901
8.771.2.15 univPin . . . . .	901
8.772 uim_cardResult Struct Reference . . . . .	901
8.772.1 Detailed Description . . . . .	901
8.772.2 Field Documentation . . . . .	901
8.772.2.1 sw1 . . . . .	901
8.772.2.2 sw2 . . . . .	901
8.773 uim_cardStatus Struct Reference . . . . .	901
8.773.1 Detailed Description . . . . .	901
8.773.2 Field Documentation . . . . .	902
8.773.2.1 index1xPri . . . . .	902
8.773.2.2 index1xSec . . . . .	902
8.773.2.3 indexGwPri . . . . .	902
8.773.2.4 indexGwSec . . . . .	902
8.773.2.5 numSlot . . . . .	902

8.773.2.6 SlotInfo . . . . .	903
8.774uim_changeUIMPIN Struct Reference . . . . .	903
8.774.1 Detailed Description . . . . .	903
8.774.2 Field Documentation . . . . .	903
8.774.2.1 oldPINLen . . . . .	903
8.774.2.2 oldPINVal . . . . .	903
8.774.2.3 pinID . . . . .	903
8.774.2.4 pinLen . . . . .	903
8.774.2.5 pinVal . . . . .	904
8.775uim_encryptedPIN1 Struct Reference . . . . .	904
8.775.1 Detailed Description . . . . .	904
8.775.2 Field Documentation . . . . .	904
8.775.2.1 pin1Len . . . . .	904
8.775.2.2 pin1Val . . . . .	904
8.776uim_fileInfo Struct Reference . . . . .	904
8.776.1 Detailed Description . . . . .	904
8.776.2 Field Documentation . . . . .	905
8.776.2.1 fileID . . . . .	905
8.776.2.2 path . . . . .	905
8.776.2.3 pathLen . . . . .	905
8.777uim_hotSwapStatus Struct Reference . . . . .	905
8.777.1 Detailed Description . . . . .	905
8.777.2 Field Documentation . . . . .	905
8.777.2.1 hotSwap . . . . .	905
8.777.2.2 hotSwapLength . . . . .	905
8.778uim_readResult Struct Reference . . . . .	906
8.778.1 Detailed Description . . . . .	906
8.778.2 Field Documentation . . . . .	906
8.778.2.1 content . . . . .	906
8.778.2.2 contentLen . . . . .	906
8.779uim_readTransparentInfo Struct Reference . . . . .	906
8.779.1 Detailed Description . . . . .	906
8.779.2 Field Documentation . . . . .	906
8.779.2.1 length . . . . .	906
8.779.2.2 offset . . . . .	907
8.780uim_remainingRetries Struct Reference . . . . .	907
8.780.1 Detailed Description . . . . .	907
8.780.2 Field Documentation . . . . .	907
8.780.2.1 unblockLeft . . . . .	907
8.780.2.2 verifyLeft . . . . .	907

8.781uim_sessionInformation Struct Reference . . . . .	907
8.781.1 Detailed Description . . . . .	907
8.781.2 Field Documentation . . . . .	908
8.781.2.1 aid . . . . .	908
8.781.2.2 aidLength . . . . .	908
8.781.2.3 sessionType . . . . .	908
8.782uim_setPINProtection Struct Reference . . . . .	908
8.782.1 Detailed Description . . . . .	908
8.782.2 Field Documentation . . . . .	909
8.782.2.1 pinID . . . . .	909
8.782.2.2 pinLength . . . . .	909
8.782.2.3 pinOperation . . . . .	909
8.782.2.4 pinValue . . . . .	909
8.783uim_slotInfo Struct Reference . . . . .	909
8.783.1 Detailed Description . . . . .	909
8.783.2 Field Documentation . . . . .	911
8.783.2.1 AppStatus . . . . .	911
8.783.2.2 cardState . . . . .	911
8.783.2.3 errorState . . . . .	911
8.783.2.4 numApp . . . . .	911
8.783.2.5 upinRetries . . . . .	911
8.783.2.6 upinState . . . . .	911
8.783.2.7 upukRetries . . . . .	911
8.784uim_UIMSessionInformation Struct Reference . . . . .	911
8.784.1 Detailed Description . . . . .	911
8.784.2 Field Documentation . . . . .	912
8.784.2.1 aid . . . . .	912
8.784.2.2 aidLength . . . . .	912
8.784.2.3 sessionType . . . . .	912
8.785uim_unblockUIMPIN Struct Reference . . . . .	912
8.785.1 Detailed Description . . . . .	912
8.785.2 Field Documentation . . . . .	913
8.785.2.1 newPINLen . . . . .	913
8.785.2.2 newPINVal . . . . .	913
8.785.2.3 pinID . . . . .	913
8.785.2.4 pukLen . . . . .	913
8.785.2.5 pukVal . . . . .	913
8.786uim_verifyUIMPIN Struct Reference . . . . .	913
8.786.1 Detailed Description . . . . .	913
8.786.2 Field Documentation . . . . .	914

8.786.2.1 pinID . . . . .	914
8.786.2.2 pinLen . . . . .	914
8.786.2.3 pinVal . . . . .	914
8.787UIMAuthenticateReq Struct Reference . . . . .	914
8.787.1 Detailed Description . . . . .	914
8.787.2 Field Documentation . . . . .	914
8.787.2.1 authData . . . . .	914
8.787.2.2 pIndicationToken . . . . .	914
8.787.2.3 sessionInfo . . . . .	915
8.788UIMAuthenticateResp Struct Reference . . . . .	915
8.788.1 Detailed Description . . . . .	915
8.788.2 Field Documentation . . . . .	915
8.788.2.1 pAuthenticateResult . . . . .	915
8.788.2.2 pCardResult . . . . .	915
8.788.2.3 pIndicationToken . . . . .	915
8.789UIMChangePinReq Struct Reference . . . . .	915
8.789.1 Detailed Description . . . . .	915
8.789.2 Field Documentation . . . . .	916
8.789.2.1 changePIN . . . . .	916
8.789.2.2 pIndicationToken . . . . .	916
8.789.2.3 pKeyReferenceID . . . . .	916
8.789.2.4 sessionInfo . . . . .	916
8.790UIMDepersonalizationReq Struct Reference . . . . .	916
8.790.1 Detailed Description . . . . .	916
8.790.2 Field Documentation . . . . .	916
8.790.2.1 depersonilisationInfo . . . . .	917
8.791UIMDepersonalizationResp Struct Reference . . . . .	917
8.791.1 Detailed Description . . . . .	917
8.791.2 Field Documentation . . . . .	917
8.791.2.1 pRemainingRetries . . . . .	917
8.792UIMEventRegisterReqResp Struct Reference . . . . .	917
8.792.1 Detailed Description . . . . .	917
8.792.2 Field Documentation . . . . .	917
8.792.2.1 eventMask . . . . .	917
8.793UIMGetCardStatusResp Struct Reference . . . . .	918
8.793.1 Detailed Description . . . . .	918
8.793.2 Field Documentation . . . . .	918
8.793.2.1 pCardStatus . . . . .	918
8.793.2.2 pHotSwapStatus . . . . .	918
8.794UIMGetConfigurationReq Struct Reference . . . . .	918

8.794.1 Detailed Description . . . . .	918
8.794.2 Field Documentation . . . . .	919
8.794.2.1 pConfigurationMask . . . . .	919
8.795UIMGetConfigurationResp Struct Reference . . . . .	919
8.795.1 Detailed Description . . . . .	919
8.795.2 Field Documentation . . . . .	920
8.795.2.1 pAutoSelection . . . . .	920
8.795.2.2 pHaltSubscription . . . . .	920
8.795.2.3 pPersonalizationStatus . . . . .	920
8.796UIMGetFileAttributesReq Struct Reference . . . . .	920
8.796.1 Detailed Description . . . . .	920
8.796.2 Field Documentation . . . . .	920
8.796.2.1 fileIndex . . . . .	920
8.796.2.2 pIndicationToken . . . . .	920
8.796.2.3 sessionInfo . . . . .	920
8.797UIMGetFileAttributesResp Struct Reference . . . . .	920
8.797.1 Detailed Description . . . . .	921
8.797.2 Field Documentation . . . . .	921
8.797.2.1 pCardResult . . . . .	921
8.797.2.2 pFileAttributes . . . . .	921
8.797.2.3 pIndicationToken . . . . .	921
8.798UIMGetSlotsStatusResp Struct Reference . . . . .	921
8.798.1 Detailed Description . . . . .	921
8.798.2 Field Documentation . . . . .	922
8.798.2.1 pNumberOfPhySlot . . . . .	922
8.798.2.2 pUimSlotsStatus . . . . .	922
8.799UIMPinResp Struct Reference . . . . .	922
8.799.1 Detailed Description . . . . .	922
8.799.2 Field Documentation . . . . .	922
8.799.2.1 pEncryptedPIN1 . . . . .	922
8.799.2.2 pIndicationToken . . . . .	922
8.799.2.3 pRemainingRetries . . . . .	923
8.800UIMPowerDownReq Struct Reference . . . . .	923
8.800.1 Detailed Description . . . . .	923
8.800.2 Field Documentation . . . . .	923
8.800.2.1 slot . . . . .	923
8.801UIMPowerUpReq Struct Reference . . . . .	923
8.801.1 Detailed Description . . . . .	923
8.801.2 Field Documentation . . . . .	924
8.801.2.1 plgnoreHotSwapSwitch . . . . .	924

8.801.2.2 slot . . . . .	924
8.802UIMReadTransparentReq Struct Reference . . . . .	924
8.802.1 Detailed Description . . . . .	924
8.802.2 Field Documentation . . . . .	924
8.802.2.1 fileIndex . . . . .	924
8.802.2.2 pEncryptData . . . . .	924
8.802.2.3 pIndicationToken . . . . .	924
8.802.2.4 readTransparent . . . . .	925
8.802.2.5 sessionInfo . . . . .	925
8.803UIMReadTransparentResp Struct Reference . . . . .	925
8.803.1 Detailed Description . . . . .	925
8.803.2 Field Documentation . . . . .	925
8.803.2.1 pCardResult . . . . .	925
8.803.2.2 pEncryptedData . . . . .	925
8.803.2.3 pIndicationToken . . . . .	925
8.803.2.4 pReadResult . . . . .	925
8.804UIMRefreshCompleteReq Struct Reference . . . . .	925
8.804.1 Detailed Description . . . . .	926
8.804.2 Field Documentation . . . . .	926
8.804.2.1 refreshComplete . . . . .	926
8.804.2.2 sessionInfo . . . . .	926
8.805UIMRefreshEvent Struct Reference . . . . .	926
8.805.1 Detailed Description . . . . .	926
8.805.2 Field Documentation . . . . .	928
8.805.2.1 aid . . . . .	928
8.805.2.2 aidLength . . . . .	928
8.805.2.3 arrfileInfo . . . . .	928
8.805.2.4 mode . . . . .	928
8.805.2.5 numOfFiles . . . . .	928
8.805.2.6 sessionType . . . . .	928
8.805.2.7 stage . . . . .	928
8.806UIMRefreshGetLastEventReq Struct Reference . . . . .	928
8.806.1 Detailed Description . . . . .	928
8.806.2 Field Documentation . . . . .	929
8.806.2.1 sessionInfo . . . . .	929
8.807UIMRefreshGetLastEventResp Struct Reference . . . . .	929
8.807.1 Detailed Description . . . . .	929
8.807.2 Field Documentation . . . . .	929
8.807.2.1 pRefreshEvent . . . . .	929
8.808UIMRefreshOKReq Struct Reference . . . . .	929

8.808.1 Detailed Description . . . . .	929
8.808.2 Field Documentation . . . . .	929
8.808.2.1 OKtoRefresh . . . . .	929
8.808.2.2 sessionInfo . . . . .	930
8.809UIMRefreshRegisterReq Struct Reference . . . . .	930
8.809.1 Detailed Description . . . . .	930
8.809.2 Field Documentation . . . . .	930
8.809.2.1 regRefresh . . . . .	930
8.809.2.2 sessionInfo . . . . .	930
8.810UIMSessionInformation Struct Reference . . . . .	930
8.810.1 Detailed Description . . . . .	930
8.810.2 Field Documentation . . . . .	931
8.810.2.1 aid . . . . .	931
8.810.2.2 aidLength . . . . .	931
8.810.2.3 sessionType . . . . .	931
8.811UIMSetPinProtectionReq Struct Reference . . . . .	931
8.811.1 Detailed Description . . . . .	931
8.811.2 Field Documentation . . . . .	932
8.811.2.1 pIndicationToken . . . . .	932
8.811.2.2 pinProtection . . . . .	932
8.811.2.3 pKeyReferenceID . . . . .	932
8.811.2.4 sessionInfo . . . . .	932
8.812UIMSlotsStatus Struct Reference . . . . .	932
8.812.1 Detailed Description . . . . .	932
8.812.2 Field Documentation . . . . .	933
8.812.2.1 uimSlotStatus . . . . .	933
8.813UIMSlotStatus Struct Reference . . . . .	933
8.813.1 Detailed Description . . . . .	933
8.813.2 Field Documentation . . . . .	934
8.813.2.1 bICCID . . . . .	934
8.813.2.2 bICCIDLength . . . . .	934
8.813.2.3 bLogicalSlot . . . . .	934
8.813.2.4 uPhyCardStatus . . . . .	934
8.813.2.5 uPhySlotStatus . . . . .	934
8.814UIMSlotStatusChangeInfo Struct Reference . . . . .	934
8.814.1 Detailed Description . . . . .	934
8.814.2 Field Documentation . . . . .	934
8.814.2.1 bNumberOfPhySlots . . . . .	934
8.814.2.2 slotsstatusChange . . . . .	934
8.815UIMStatusChangeInfo Struct Reference . . . . .	934



8.815.1 Detailed Description . . . . .	935
8.815.2 Field Documentation . . . . .	936
8.815.2.1 statusChange . . . . .	936
8.816UIMSwitchSlotReq Struct Reference . . . . .	936
8.816.1 Detailed Description . . . . .	936
8.816.2 Field Documentation . . . . .	936
8.816.2.1 bLogicalSlot . . . . .	936
8.816.2.2 ulPhysicalSlot . . . . .	936
8.817UIMUnblockPinReq Struct Reference . . . . .	936
8.817.1 Detailed Description . . . . .	937
8.817.2 Field Documentation . . . . .	937
8.817.2.1 pIndicationToken . . . . .	937
8.817.2.2 pKeyReferenceID . . . . .	937
8.817.2.3 sessionInfo . . . . .	937
8.817.2.4 unblockPIN . . . . .	937
8.818UIMVerifyPinReq Struct Reference . . . . .	937
8.818.1 Detailed Description . . . . .	938
8.818.2 Field Documentation . . . . .	938
8.818.2.1 pEncryptedPIN1 . . . . .	938
8.818.2.2 pIndicationToken . . . . .	938
8.818.2.3 pKeyReferenceID . . . . .	938
8.818.2.4 sessionInfo . . . . .	938
8.818.2.5 verifyPIN . . . . .	938
8.819UMTSInfo Struct Reference . . . . .	938
8.819.1 Detailed Description . . . . .	939
8.819.2 Field Documentation . . . . .	940
8.819.2.1 cellID . . . . .	940
8.819.2.2 ecio . . . . .	940
8.819.2.3 geranInst . . . . .	940
8.819.2.4 GeranInstInfo . . . . .	940
8.819.2.5 lac . . . . .	940
8.819.2.6 plmn . . . . .	940
8.819.2.7 psc . . . . .	940
8.819.2.8 rscp . . . . .	940
8.819.2.9 uarfcn . . . . .	940
8.819.2.10umtsInst . . . . .	940
8.819.2.11UMTSInstInfo . . . . .	940
8.820UMTSInstInfo Struct Reference . . . . .	940
8.820.1 Detailed Description . . . . .	941
8.820.2 Field Documentation . . . . .	941

8.820.2.1 umtsEcio . . . . .	941
8.820.2.2 umtsPsc . . . . .	941
8.820.2.3 umtsRscp . . . . .	941
8.820.2.4 umtsUarfcn . . . . .	941
8.821 umtsLTENbrCell Struct Reference . . . . .	941
8.821.1 Detailed Description . . . . .	941
8.821.2 Field Documentation . . . . .	942
8.821.2.1 cellIsTDD . . . . .	942
8.821.2.2 earfcn . . . . .	942
8.821.2.3 pci . . . . .	942
8.821.2.4 rsrp . . . . .	942
8.821.2.5 rsrq . . . . .	942
8.821.2.6 srxlev . . . . .	942
8.822 UMTSMinQoS Struct Reference . . . . .	942
8.822.1 Detailed Description . . . . .	943
8.822.2 Field Documentation . . . . .	945
8.822.2.1 deliveryErrSDU . . . . .	945
8.822.2.2 grntDownlinkBitrate . . . . .	945
8.822.2.3 grntUplinkBitrate . . . . .	945
8.822.2.4 maxDownlinkBitrate . . . . .	945
8.822.2.5 maxSDUSize . . . . .	945
8.822.2.6 maxUplinkBitrate . . . . .	945
8.822.2.7 qosDeliveryOrder . . . . .	945
8.822.2.8 resBerRatio . . . . .	945
8.822.2.9 sduErrorRatio . . . . .	945
8.822.2.10 trafficClass . . . . .	945
8.822.2.11 trafficPriority . . . . .	945
8.822.2.12 transferDelay . . . . .	945
8.823 UMTSQoS Struct Reference . . . . .	946
8.823.1 Detailed Description . . . . .	946
8.823.2 Field Documentation . . . . .	949
8.823.2.1 deliveryErrSDU . . . . .	949
8.823.2.2 grntDownlinkBitrate . . . . .	949
8.823.2.3 grntUplinkBitrate . . . . .	949
8.823.2.4 maxDownlinkBitrate . . . . .	949
8.823.2.5 maxSDUSize . . . . .	949
8.823.2.6 maxUplinkBitrate . . . . .	949
8.823.2.7 qosDeliveryOrder . . . . .	949
8.823.2.8 resBerRatio . . . . .	949
8.823.2.9 sduErrorRatio . . . . .	949

8.823.2.10trafficClass . . . . .	949
8.823.2.11trafficPriority . . . . .	949
8.823.2.12transferDelay . . . . .	949
8.824UMTSReqQoSsigInd Struct Reference . . . . .	949
8.824.1 Detailed Description . . . . .	949
8.824.2 Field Documentation . . . . .	950
8.824.2.1 SigInd . . . . .	950
8.824.2.2 UMTSReqQoS . . . . .	950
8.825unlockUIMPIN Struct Reference . . . . .	950
8.825.1 Detailed Description . . . . .	950
8.825.2 Field Documentation . . . . .	951
8.825.2.1 newPINLen . . . . .	951
8.825.2.2 newPINVal . . . . .	951
8.825.2.3 pinID . . . . .	951
8.825.2.4 pukLen . . . . .	951
8.825.2.5 pukVal . . . . .	951
8.826UniversalTime Struct Reference . . . . .	951
8.826.1 Detailed Description . . . . .	951
8.826.2 Field Documentation . . . . .	952
8.826.2.1 day . . . . .	952
8.826.2.2 dayOfWeek . . . . .	952
8.826.2.3 hour . . . . .	952
8.826.2.4 minute . . . . .	952
8.826.2.5 month . . . . .	952
8.826.2.6 second . . . . .	952
8.826.2.7 year . . . . .	952
8.827unpack_dms_GetActivationState_t Struct Reference . . . . .	952
8.827.1 Detailed Description . . . . .	952
8.827.2 Field Documentation . . . . .	953
8.827.2.1 state . . . . .	953
8.828unpack_dms_GetBandCapability_t Struct Reference . . . . .	953
8.828.1 Field Documentation . . . . .	953
8.828.1.1 BandCapability . . . . .	953
8.828.1.2 Tlvresult . . . . .	953
8.829unpack_dms_GetCrashAction_t Struct Reference . . . . .	953
8.829.1 Field Documentation . . . . .	953
8.829.1.1 DevCrashState . . . . .	953
8.829.1.2 Tlvresult . . . . .	953
8.830unpack_dms_GetCustFeature_t Struct Reference . . . . .	953
8.830.1 Field Documentation . . . . .	954

8.830.1.1 DHCPRelayEnabled . . . . .	954
8.830.1.2 DisableIMSI . . . . .	954
8.830.1.3 GpsEnable . . . . .	954
8.830.1.4 GPSPMP . . . . .	954
8.830.1.5 GPSSel . . . . .	954
8.830.1.6 IPFamSupport . . . . .	954
8.830.1.7 IsVoiceEnabled . . . . .	954
8.830.1.8 RMAutoConnect . . . . .	954
8.830.1.9 SMSSupport . . . . .	954
8.830.1.10Tlvresult . . . . .	954
8.831unpack_dms_GetCustFeaturesV2_t Struct Reference . . . . .	954
8.831.1 Detailed Description . . . . .	954
8.831.2 Field Documentation . . . . .	955
8.831.2.1 GetCustomFeatureV2 . . . . .	955
8.831.2.2 Tlvresult . . . . .	955
8.832unpack_dms_GetDeviceCap_t Struct Reference . . . . .	955
8.832.1 Field Documentation . . . . .	955
8.832.1.1 DataServiceCapability . . . . .	955
8.832.1.2 MaxRXChannelRate . . . . .	955
8.832.1.3 MaxTXChannelRate . . . . .	955
8.832.1.4 Radiofaces . . . . .	955
8.832.1.5 RadiofacesSize . . . . .	955
8.832.1.6 SimCapability . . . . .	955
8.832.1.7 Tlvresult . . . . .	955
8.833unpack_dms_GetDeviceCapabilities_t Struct Reference . . . . .	955
8.833.1 Detailed Description . . . . .	956
8.833.2 Field Documentation . . . . .	956
8.833.2.1 dataServiceCaCapability . . . . .	956
8.833.2.2 maxRxChannelRate . . . . .	956
8.833.2.3 maxTxChannelRate . . . . .	956
8.833.2.4 Radiofaces . . . . .	956
8.833.2.5 radiofacesSize . . . . .	956
8.833.2.6 simCapability . . . . .	956
8.834unpack_dms_GetDeviceHardwareRev_t Struct Reference . . . . .	956
8.834.1 Field Documentation . . . . .	956
8.834.1.1 String . . . . .	956
8.834.1.2 stringSize . . . . .	956
8.834.1.3 Tlvresult . . . . .	956
8.835unpack_dms_GetDeviceMfr_t Struct Reference . . . . .	956
8.835.1 Field Documentation . . . . .	957

8.835.1.1 String . . . . .	957
8.835.1.2 stringSize . . . . .	957
8.835.1.3 Tlvresult . . . . .	957
8.836unpack_dms_GetDeviceSerialNumbers_t Struct Reference . . . . .	957
8.836.1 Field Documentation . . . . .	957
8.836.1.1 esnSize . . . . .	957
8.836.1.2 ESNString . . . . .	957
8.836.1.3 imeiSize . . . . .	957
8.836.1.4 IMEIString . . . . .	957
8.836.1.5 imeiSvnSize . . . . .	957
8.836.1.6 lmeiSvnString . . . . .	957
8.836.1.7 meidSize . . . . .	957
8.836.1.8 MEIDString . . . . .	957
8.836.1.9 Tlvresult . . . . .	957
8.837unpack_dms_GetFirmwareInfo_t Struct Reference . . . . .	957
8.837.1 Detailed Description . . . . .	958
8.837.2 Field Documentation . . . . .	958
8.837.2.1 appversion_str . . . . .	958
8.837.2.2 bootversion_str . . . . .	958
8.837.2.3 carrier_str . . . . .	958
8.837.2.4 cur_carr_name . . . . .	958
8.837.2.5 cur_carr_rev . . . . .	958
8.837.2.6 modelid_str . . . . .	958
8.837.2.7 packageid_str . . . . .	958
8.837.2.8 priversion_str . . . . .	958
8.837.2.9 sku_str . . . . .	958
8.837.2.10Tlvresult . . . . .	958
8.838unpack_dms_GetFirmwareRevision_t Struct Reference . . . . .	958
8.838.1 Field Documentation . . . . .	959
8.838.1.1 amssSize . . . . .	959
8.838.1.2 AMSSString . . . . .	959
8.838.1.3 PRIString . . . . .	959
8.838.1.4 Tlvresult . . . . .	959
8.839unpack_dms_GetFirmwareRevisions_t Struct Reference . . . . .	959
8.839.1 Detailed Description . . . . .	959
8.839.2 Field Documentation . . . . .	959
8.839.2.1 amssSize . . . . .	959
8.839.2.2 AMSSString . . . . .	959
8.839.2.3 bootSize . . . . .	959
8.839.2.4 BootString . . . . .	959

8.839.2.5 priSize . . . . .	959
8.839.2.6 PRIString . . . . .	959
8.839.2.7 Tlvresult . . . . .	959
8.840unpack_dms_GetFSN_t Struct Reference . . . . .	959
8.840.1 Field Documentation . . . . .	960
8.840.1.1 String . . . . .	960
8.840.1.2 Tlvresult . . . . .	960
8.841unpack_dms_GetHardwareRevision_t Struct Reference . . . . .	960
8.841.1 Detailed Description . . . . .	960
8.841.2 Field Documentation . . . . .	960
8.841.2.1 hwVer . . . . .	960
8.842unpack_dms_GetIMSI_t Struct Reference . . . . .	960
8.842.1 Field Documentation . . . . .	960
8.842.1.1 imsi . . . . .	960
8.842.1.2 Tlvresult . . . . .	960
8.843unpack_dms_GetModelID_t Struct Reference . . . . .	960
8.843.1 Detailed Description . . . . .	960
8.843.2 Field Documentation . . . . .	961
8.843.2.1 modelid . . . . .	961
8.843.2.2 Tlvresult . . . . .	961
8.844unpack_dms_GetNetworkTime_t Struct Reference . . . . .	961
8.844.1 Detailed Description . . . . .	961
8.844.2 Field Documentation . . . . .	961
8.844.2.1 source . . . . .	961
8.844.2.2 timestamp . . . . .	961
8.844.2.3 Tlvresult . . . . .	961
8.845unpack_dms_GetPower_t Struct Reference . . . . .	961
8.845.1 Detailed Description . . . . .	962
8.845.2 Field Documentation . . . . .	962
8.845.2.1 HardwareControlledMode . . . . .	962
8.845.2.2 OfflineReason . . . . .	962
8.845.2.3 OperationMode . . . . .	962
8.845.2.4 Tlvresult . . . . .	962
8.846unpack_dms_GetPRLVersion_t Struct Reference . . . . .	962
8.846.1 Field Documentation . . . . .	962
8.846.1.1 Tlvresult . . . . .	962
8.846.1.2 u16PRLVersion . . . . .	962
8.846.1.3 u8PRLPreference . . . . .	962
8.847unpack_dms_GetSerialNumbers_t Struct Reference . . . . .	962
8.847.1 Detailed Description . . . . .	962

8.847.2 Field Documentation . . . . .	963
8.847.2.1 esn . . . . .	963
8.847.2.2 imei_no . . . . .	963
8.847.2.3 imeisv_svn . . . . .	963
8.847.2.4 meid . . . . .	963
8.848unpack_dms_GetUSBComp_t Struct Reference . . . . .	963
8.848.1 Field Documentation . . . . .	963
8.848.1.1 NumSupUSBComps . . . . .	963
8.848.1.2 SupUSBComps . . . . .	963
8.848.1.3 Tlvresult . . . . .	963
8.848.1.4 USBComp . . . . .	963
8.849unpack_dms_GetVoiceNumber_t Struct Reference . . . . .	963
8.849.1 Field Documentation . . . . .	963
8.849.1.1 MIN . . . . .	963
8.849.1.2 minSize . . . . .	963
8.849.1.3 Tlvresult . . . . .	963
8.849.1.4 VoiceNumber . . . . .	964
8.849.1.5 voiceNumberSize . . . . .	964
8.850unpack_dms_SetCrashAction_t Struct Reference . . . . .	964
8.850.1 Detailed Description . . . . .	964
8.850.2 Field Documentation . . . . .	964
8.850.2.1 notused . . . . .	964
8.851unpack_dms_SetCustFeature_t Struct Reference . . . . .	964
8.851.1 Field Documentation . . . . .	964
8.851.1.1 Tlvresult . . . . .	964
8.852unpack_dms_SetCustFeaturesV2_t Struct Reference . . . . .	964
8.852.1 Detailed Description . . . . .	964
8.852.2 Field Documentation . . . . .	964
8.852.2.1 Tlvresult . . . . .	964
8.853unpack_dms_SetEventReport_ind_t Struct Reference . . . . .	964
8.853.1 Detailed Description . . . . .	965
8.853.2 Field Documentation . . . . .	965
8.853.2.1 ActivationStatusTlv . . . . .	965
8.853.2.2 OperatingModeTlv . . . . .	965
8.853.2.3 Tlvresult . . . . .	965
8.854unpack_dms_SetEventReport_t Struct Reference . . . . .	965
8.854.1 Field Documentation . . . . .	965
8.854.1.1 Tlvresult . . . . .	965
8.855unpack_dms_SetFirmwarePreference_t Struct Reference . . . . .	965
8.855.1 Field Documentation . . . . .	965

8.855.1.1 Tlvresult . . . . .	965
8.856unpack_dms_SetPower_t Struct Reference . . . . .	966
8.856.1 Field Documentation . . . . .	966
8.856.1.1 Tlvresult . . . . .	966
8.857unpack_dms_SetUSBComp_t Struct Reference . . . . .	966
8.857.1 Field Documentation . . . . .	966
8.857.1.1 Tlvresult . . . . .	966
8.858unpack_dms_SLQSDmsSwiGetResetInfo_Ind_t Struct Reference . . . . .	966
8.858.1 Detailed Description . . . . .	966
8.858.2 Field Documentation . . . . .	967
8.858.2.1 source . . . . .	967
8.858.2.2 Tlvresult . . . . .	967
8.858.2.3 type . . . . .	967
8.859unpack_dms_SLQSDmsSwiGetResetInfo_t Struct Reference . . . . .	967
8.859.1 Detailed Description . . . . .	967
8.859.2 Field Documentation . . . . .	968
8.859.2.1 source . . . . .	968
8.859.2.2 Tlvresult . . . . .	968
8.859.2.3 type . . . . .	968
8.860unpack_dms_SLQSDmsSwiIndicationRegister_t Struct Reference . . . . .	968
8.860.1 Detailed Description . . . . .	968
8.860.2 Field Documentation . . . . .	969
8.860.2.1 Tlvresult . . . . .	969
8.861unpack_dms_SLQSGetBandCapability_t Struct Reference . . . . .	969
8.861.1 Detailed Description . . . . .	969
8.861.2 Field Documentation . . . . .	971
8.861.2.1 bandCapability . . . . .	971
8.861.2.2 is_LteBandCapability_Available . . . . .	971
8.861.2.3 is_TdsBandCapability_Available . . . . .	971
8.861.2.4 LteBandCapability . . . . .	971
8.861.2.5 TdsBandCapability . . . . .	971
8.862unpack_dms_SLQSSwiClearDyingGaspStatistics_t Struct Reference . . . . .	971
8.862.1 Detailed Description . . . . .	971
8.862.2 Field Documentation . . . . .	971
8.862.2.1 Tlvresult . . . . .	971
8.863unpack_dms_SLQSSwiGetDyingGaspCfg_t Struct Reference . . . . .	971
8.863.1 Detailed Description . . . . .	972
8.863.2 Field Documentation . . . . .	973
8.863.2.1 pGetDyingGaspCfg . . . . .	973
8.863.2.2 Tlvresult . . . . .	973



8.864unpack_dms_SLQSSwiGetDyingGaspStatistics_t Struct Reference	973
8.864.1 Detailed Description	973
8.864.2 Field Documentation	973
8.864.2.1 pGetDyingGaspStatistics	973
8.864.2.2 Tlvresult	973
8.865unpack_dms_SLQSSwiGetFirmwareCurr_t Struct Reference	973
8.865.1 Detailed Description	973
8.865.2 Field Documentation	974
8.865.2.1 carrier	974
8.865.2.2 fwvers	974
8.865.2.3 numEntries	974
8.865.2.4 pCurrImgInfo	974
8.865.2.5 pkgver	974
8.865.2.6 priver	974
8.866unpack_dms_SLQSSwiGetFwUpdateStatus_t Struct Reference	974
8.866.1 Detailed Description	974
8.866.2 Field Documentation	976
8.866.2.1 imgType	976
8.866.2.2 logString	976
8.866.2.3 refData	976
8.866.2.4 refString	976
8.866.2.5 ResCode	976
8.866.2.6 Tlvresult	976
8.867unpack_dms_SLQSSwiSetDyingGaspCfg_t Struct Reference	976
8.867.1 Detailed Description	976
8.867.2 Field Documentation	976
8.867.2.1 Tlvresult	976
8.868unpack_dms_UIMGetICCID_t Struct Reference	976
8.868.1 Detailed Description	976
8.868.2 Field Documentation	977
8.868.2.1 String	977
8.868.2.2 stringSize	977
8.868.2.3 Tlvresult	977
8.869unpack_fms_GetImagesPreference_t Struct Reference	977
8.869.1 Detailed Description	977
8.869.2 Field Documentation	977
8.869.2.1 ImageListSize	977
8.869.2.2 pImageList	977
8.869.2.3 Tlvresult	978
8.870unpack_fms_GetStoredImages_t Struct Reference	978

8.870.1 Detailed Description . . . . .	978
8.870.2 Field Documentation . . . . .	978
8.870.2.1 imageList . . . . .	978
8.870.2.2 imagelistSize . . . . .	978
8.870.2.3 Tlvresult . . . . .	978
8.871unpack_fms_SetImagesPreference_t Struct Reference . . . . .	978
8.871.1 Detailed Description . . . . .	978
8.871.2 Field Documentation . . . . .	979
8.871.2.1 ImageTypes . . . . .	979
8.871.2.2 ImageTypesSize . . . . .	979
8.871.2.3 Tlvresult . . . . .	979
8.872unpack_loc_Delete_Assist_Data_t Struct Reference . . . . .	979
8.872.1 Detailed Description . . . . .	979
8.872.2 Field Documentation . . . . .	979
8.872.2.1 Tlvresult . . . . .	979
8.873unpack_loc_EngineState_Ind_t Struct Reference . . . . .	979
8.873.1 Detailed Description . . . . .	979
8.873.2 Field Documentation . . . . .	980
8.873.2.1 engineState . . . . .	980
8.873.2.2 Tlvresult . . . . .	980
8.874unpack_loc_EventRegister_t Struct Reference . . . . .	980
8.874.1 Detailed Description . . . . .	980
8.874.2 Field Documentation . . . . .	980
8.874.2.1 Tlvresult . . . . .	980
8.875unpack_loc_PositionRpt_Ind_t Struct Reference . . . . .	980
8.875.1 Detailed Description . . . . .	981
8.875.2 Field Documentation . . . . .	986
8.875.2.1 pAltitudeAssumed . . . . .	986
8.875.2.2 pAltitudeWrtEllipsoid . . . . .	986
8.875.2.3 pAltitudeWrtMeanSeaLevel . . . . .	986
8.875.2.4 pFixId . . . . .	986
8.875.2.5 pGpsTime . . . . .	986
8.875.2.6 pHeading . . . . .	986
8.875.2.7 pHeadingUnc . . . . .	986
8.875.2.8 pHorConfidence . . . . .	986
8.875.2.9 pHorReliability . . . . .	986
8.875.2.10pHorUncCircular . . . . .	986
8.875.2.11pHorUncEllipseOrientAzimuth . . . . .	986
8.875.2.12pHorUncEllipseSemiMajor . . . . .	986
8.875.2.13pHorUncEllipseSemiMinor . . . . .	986

8.875.2.14pLatitude . . . . .	986
8.875.2.15pLeapSeconds . . . . .	986
8.875.2.16pLongitude . . . . .	986
8.875.2.17pMagneticDeviation . . . . .	986
8.875.2.18pPrecisionDilution . . . . .	987
8.875.2.19pSensorDataUsage . . . . .	987
8.875.2.20pSpeedHorizontal . . . . .	987
8.875.2.21pSpeedUnc . . . . .	987
8.875.2.22pSpeedVertical . . . . .	987
8.875.2.23pSvUsedforFix . . . . .	987
8.875.2.24pTechnologyMask . . . . .	987
8.875.2.25pTimeSrc . . . . .	987
8.875.2.26pTimestampUtc . . . . .	987
8.875.2.27pTimeUnc . . . . .	987
8.875.2.28pVertConfidence . . . . .	987
8.875.2.29pVertReliability . . . . .	987
8.875.2.30pVertUnc . . . . .	987
8.875.2.31sessionId . . . . .	987
8.875.2.32sessionStatus . . . . .	987
8.875.2.33Tlvresult . . . . .	987
8.876unpack_loc_SetExtPowerConfig_Ind_t Struct Reference . . . . .	987
8.876.1 Detailed Description . . . . .	987
8.876.2 Field Documentation . . . . .	988
8.876.2.1 status . . . . .	988
8.876.2.2 Tlvresult . . . . .	988
8.877unpack_loc_SetExtPowerState_t Struct Reference . . . . .	988
8.877.1 Detailed Description . . . . .	988
8.877.2 Field Documentation . . . . .	988
8.877.2.1 Tlvresult . . . . .	988
8.878unpack_loc_SetOperationMode_t Struct Reference . . . . .	989
8.878.1 Detailed Description . . . . .	989
8.878.2 Field Documentation . . . . .	989
8.878.2.1 Tlvresult . . . . .	989
8.879unpack_loc_Start_t Struct Reference . . . . .	989
8.879.1 Detailed Description . . . . .	989
8.879.2 Field Documentation . . . . .	989
8.879.2.1 Tlvresult . . . . .	989
8.880unpack_loc_Stop_t Struct Reference . . . . .	989
8.880.1 Detailed Description . . . . .	989
8.880.2 Field Documentation . . . . .	990

8.880.2.1 Tlvresult . . . . .	990
8.881unpack_nas_GetCDMANetworkParameters_t Struct Reference . . . . .	990
8.881.1 Detailed Description . . . . .	990
8.881.2 Field Documentation . . . . .	990
8.881.2.1 Application . . . . .	990
8.881.2.2 Broadcast . . . . .	990
8.881.2.3 CustomSCP . . . . .	990
8.881.2.4 ForceRev0 . . . . .	990
8.881.2.5 Protocol . . . . .	990
8.881.2.6 RegForeignNID . . . . .	991
8.881.2.7 RegForeignSID . . . . .	991
8.881.2.8 RegHomeSID . . . . .	991
8.881.2.9 Roaming . . . . .	991
8.881.2.10SCI . . . . .	991
8.881.2.11SCM . . . . .	991
8.882unpack_nas_GetHomeNetwork_t Struct Reference . . . . .	991
8.882.1 Detailed Description . . . . .	991
8.882.2 Field Documentation . . . . .	991
8.882.2.1 mcc . . . . .	991
8.882.2.2 mnc . . . . .	991
8.882.2.3 name . . . . .	991
8.882.2.4 nid . . . . .	991
8.882.2.5 sid . . . . .	991
8.883unpack_nas_GetNetworkPreference_t Struct Reference . . . . .	991
8.883.1 Detailed Description . . . . .	992
8.883.2 Field Documentation . . . . .	993
8.883.2.1 ActiveTechPref . . . . .	993
8.883.2.2 Duration . . . . .	993
8.883.2.3 PersistentTechPref . . . . .	993
8.883.2.4 Tlvresult . . . . .	993
8.884unpack_nas_GetRFInfo_t Struct Reference . . . . .	993
8.884.1 Detailed Description . . . . .	994
8.884.2 Field Documentation . . . . .	994
8.884.2.1 instancesSize . . . . .	994
8.884.2.2 RFBandInfoElements . . . . .	994
8.885unpack_nas_GetServingNetwork_t Struct Reference . . . . .	994
8.885.1 Detailed Description . . . . .	994
8.885.2 Field Documentation . . . . .	995
8.885.2.1 CSDomain . . . . .	995
8.885.2.2 DataCaps . . . . .	995

8.885.2.3 DataCapsLen . . . . .	995
8.885.2.4 MCC . . . . .	995
8.885.2.5 MNC . . . . .	995
8.885.2.6 Name . . . . .	995
8.885.2.7 nameSize . . . . .	995
8.885.2.8 PSDomain . . . . .	995
8.885.2.9 Radiolfaces . . . . .	995
8.885.2.10RadiolfacesSize . . . . .	995
8.885.2.11RAN . . . . .	995
8.885.2.12RegistrationState . . . . .	995
8.885.2.13Roaming . . . . .	995
8.886unpack_nas_GetServingNetworkCapabilities_t Struct Reference . . . . .	995
8.886.1 Detailed Description . . . . .	995
8.886.2 Field Documentation . . . . .	995
8.886.2.1 DataCaps . . . . .	995
8.886.2.2 DataCapsLen . . . . .	996
8.887unpack_nas_GetSignalStrengths_t Struct Reference . . . . .	996
8.887.1 Detailed Description . . . . .	996
8.887.2 Field Documentation . . . . .	996
8.887.2.1 len . . . . .	996
8.887.2.2 radio . . . . .	996
8.887.2.3 rssi . . . . .	996
8.888unpack_nas_PerformNetworkScan_t Struct Reference . . . . .	996
8.888.1 Detailed Description . . . . .	996
8.888.2 Field Documentation . . . . .	996
8.888.2.1 p3GppNetworkInfoInstances . . . . .	996
8.888.2.2 p3GppNetworkInstanceSize . . . . .	996
8.888.2.3 pPCSIInstance . . . . .	997
8.888.2.4 pPCSIInstanceSize . . . . .	997
8.888.2.5 pRATINstance . . . . .	997
8.888.2.6 pRATInstanceSize . . . . .	997
8.888.2.7 pScanResult . . . . .	997
8.889unpack_nas_SetDataCapabilitiesCallback_ind_t Struct Reference . . . . .	997
8.889.1 Detailed Description . . . . .	997
8.889.2 Field Documentation . . . . .	997
8.889.2.1 dataCaps . . . . .	997
8.889.2.2 dataCapsSize . . . . .	997
8.890unpack_nas_SetEventReportInd_t Struct Reference . . . . .	997
8.890.1 Detailed Description . . . . .	997
8.890.2 Field Documentation . . . . .	997

8.890.2.1 RFTlv . . . . .	997
8.890.2.2 RRTlv . . . . .	998
8.890.2.3 SLQSSSTlv . . . . .	998
8.890.2.4 SSTlv . . . . .	998
8.891unpack_nas_SetNetworkPreference_t Struct Reference . . . . .	998
8.891.1 Detailed Description . . . . .	998
8.891.2 Field Documentation . . . . .	999
8.891.2.1 Tlvresult . . . . .	999
8.892unpack_nas_SetRoamingIndicatorCallback_ind_t Struct Reference . . . . .	999
8.892.1 Detailed Description . . . . .	999
8.892.2 Field Documentation . . . . .	999
8.892.2.1 roaming . . . . .	999
8.893unpack_nas_SetServingSystemCallback_ind_t Struct Reference . . . . .	999
8.893.1 Detailed Description . . . . .	1000
8.893.2 Field Documentation . . . . .	1000
8.893.2.1 SSInfo . . . . .	1000
8.893.2.2 Tlvresult . . . . .	1000
8.894unpack_nas_SlqsGetLTECphyCAInfo_t Struct Reference . . . . .	1000
8.894.1 Detailed Description . . . . .	1000
8.894.2 Field Documentation . . . . .	1000
8.894.2.1 LTECphyCAInfo . . . . .	1000
8.894.2.2 Tlvresult . . . . .	1000
8.895unpack_nas_SLQSGetNetworkTime_t Struct Reference . . . . .	1000
8.895.1 Detailed Description . . . . .	1001
8.895.2 Field Documentation . . . . .	1001
8.895.2.1 p3GPP2TimeInfo . . . . .	1001
8.895.2.2 p3GPPTIMEInfo . . . . .	1001
8.896unpack_nas_SLQSGetPLMNName_t Struct Reference . . . . .	1001
8.896.1 Field Documentation . . . . .	1001
8.896.1.1 longName . . . . .	1001
8.896.1.2 longNameCI . . . . .	1001
8.896.1.3 longNameEn . . . . .	1001
8.896.1.4 longNameLen . . . . .	1001
8.896.1.5 longNameSB . . . . .	1002
8.896.1.6 shortName . . . . .	1002
8.896.1.7 shortNameCI . . . . .	1002
8.896.1.8 shortNameEn . . . . .	1002
8.896.1.9 shortNameLen . . . . .	1002
8.896.1.10shortNameSB . . . . .	1002
8.896.1.11spn . . . . .	1002

8.896.1.12	spnEncoding	1002
8.896.1.13	spnLength	1002
8.897	unpack_nas_SLQSGetServingSystem_t Struct Reference	1002
8.897.1	Detailed Description	1002
8.897.2	Field Documentation	1003
8.897.2.1	BasestationID	1003
8.897.2.2	BasestationLatitude	1003
8.897.2.3	BasestationLongitude	1003
8.897.2.4	CallBarStatus	1003
8.897.2.5	CDMA_P_Rev	1003
8.897.2.6	CDMASystemInfoExt	1003
8.897.2.7	CellID	1003
8.897.2.8	ConcSvcInfo	1003
8.897.2.9	CurrentPLMN	1003
8.897.2.10	DataSrvCapabilities	1004
8.897.2.11	DefaultRoamInd	1004
8.897.2.12	DetailedSvcInfo	1004
8.897.2.13	DTMInd	1004
8.897.2.14	Gpp2TimeZone	1004
8.897.2.15	GppNetworkDSTAdjustment	1004
8.897.2.16	GppTimeZone	1004
8.897.2.17	HdrPersonality	1004
8.897.2.18	Lac	1004
8.897.2.19	NetworkID	1004
8.897.2.20	PRLInd	1004
8.897.2.21	RoamIndicatorVal	1004
8.897.2.22	RoamingIndicatorList	1004
8.897.2.23	ServingSystem	1004
8.897.2.24	SystemID	1004
8.897.2.25	TrackAreaCode	1004
8.898	unpack_nas_SLQSGetSignalStrength_t Struct Reference	1004
8.898.1	Detailed Description	1004
8.898.2	Field Documentation	1005
8.898.2.1	ecioList	1005
8.898.2.2	ecioListLen	1005
8.898.2.3	errorRateList	1005
8.898.2.4	errorRateListLen	1005
8.898.2.5	lo	1005
8.898.2.6	ltsrpr	1005
8.898.2.7	ltsnr	1005

8.898.2.8 rsrqInfo . . . . .	1005
8.898.2.9 rxSignalStrengthList . . . . .	1005
8.898.2.10 rxSignalStrengthListLen . . . . .	1005
8.898.2.11 signalStrengthReqMask . . . . .	1005
8.898.2.12 sinr . . . . .	1005
8.899unpack_nas_SLQSGetSysInfo_t Struct Reference . . . . .	1005
8.899.1 Detailed Description . . . . .	1007
8.899.2 Field Documentation . . . . .	1008
8.899.2.1 pAddCDMASysInfo . . . . .	1008
8.899.2.2 pAddGSMSysInfo . . . . .	1008
8.899.2.3 pAddHDRSysInfo . . . . .	1008
8.899.2.4 pAddLTESysInfo . . . . .	1008
8.899.2.5 pAddWCDMASysInfo . . . . .	1008
8.899.2.6 pCDMASrvStatusInfo . . . . .	1008
8.899.2.7 pCDMASysInfo . . . . .	1008
8.899.2.8 pGSMCallBarringSysInfo . . . . .	1008
8.899.2.9 pGSMCipherDomainSysInfo . . . . .	1008
8.899.2.10 pGSMsSrvStatusInfo . . . . .	1008
8.899.2.11 pGSMSysInfo . . . . .	1009
8.899.2.12 pHDRSrvStatusInfo . . . . .	1009
8.899.2.13 pHDRSysInfo . . . . .	1009
8.899.2.14 pLTESrvStatusInfo . . . . .	1009
8.899.2.15 pLTESysInfo . . . . .	1009
8.899.2.16 pLTEVoiceSupportSysInfo . . . . .	1009
8.899.2.17 pWCDMACallBarringSysInfo . . . . .	1009
8.899.2.18 pWCDMACipherDomainSysInfo . . . . .	1009
8.899.2.19 pWCDMASrvStatusInfo . . . . .	1009
8.899.2.20 pWCDMASysInfo . . . . .	1009
8.900unpack_nas_SLQSGetSysSelectionPref_t Struct Reference . . . . .	1009
8.900.1 Detailed Description . . . . .	1009
8.900.2 Field Documentation . . . . .	1012
8.900.2.1 pBandPref . . . . .	1012
8.900.2.2 pEmerMode . . . . .	1012
8.900.2.3 pGWAcqOrderPref . . . . .	1012
8.900.2.4 pLTEBandPref . . . . .	1012
8.900.2.5 pModePref . . . . .	1012
8.900.2.6 pNetSelPref . . . . .	1012
8.900.2.7 pPRLPref . . . . .	1012
8.900.2.8 pRoamPref . . . . .	1012
8.900.2.9 pSrvDomainPref . . . . .	1012



8.901unpack_nas_SLQSNasGetCellLocationInfo_t Struct Reference . . . . .	1012
8.901.1 Detailed Description . . . . .	1012
8.901.2 Field Documentation . . . . .	1013
8.901.2.1 pCDMAInfo . . . . .	1013
8.901.2.2 pGERANInfo . . . . .	1013
8.901.2.3 pLTEInfoInterfreq . . . . .	1013
8.901.2.4 pLTEInfoIntrafreq . . . . .	1013
8.901.2.5 pLTEInfoNeighboringGSM . . . . .	1013
8.901.2.6 pLTEInfoNeighboringWCDMA . . . . .	1013
8.901.2.7 pUMTSCellID . . . . .	1013
8.901.2.8 pUMTSInfo . . . . .	1013
8.901.2.9 pWCDMAInfoLTENeighborCell . . . . .	1013
8.902unpack_nas_SLQSNasGetSigInfo_t Struct Reference . . . . .	1014
8.902.1 Detailed Description . . . . .	1014
8.902.2 Field Documentation . . . . .	1014
8.902.2.1 CDMASigInfo . . . . .	1014
8.902.2.2 GSMSSInfo . . . . .	1014
8.902.2.3 HDRSSInfo . . . . .	1014
8.902.2.4 LTESigInfo . . . . .	1014
8.902.2.5 WCDMASSInfo . . . . .	1014
8.903unpack_nas_SLQSNasNetworkTimeCallBack_ind_t Struct Reference . . . . .	1014
8.903.1 Detailed Description . . . . .	1014
8.903.2 Field Documentation . . . . .	1015
8.903.2.1 pDayltSavAdj . . . . .	1015
8.903.2.2 pRadioInterface . . . . .	1015
8.903.2.3 pTimeZone . . . . .	1015
8.903.2.4 universalTime . . . . .	1015
8.904unpack_nas_SLQSNasSigInfoCallback_t Struct Reference . . . . .	1015
8.904.1 Detailed Description . . . . .	1016
8.904.2 Field Documentation . . . . .	1017
8.904.2.1 pCDMASigInfo . . . . .	1017
8.904.2.2 pGSMSSigInfo . . . . .	1017
8.904.2.3 pHDRSigInfo . . . . .	1017
8.904.2.4 pLTESigInfo . . . . .	1017
8.904.2.5 pRscp . . . . .	1017
8.904.2.6 pTDSCDMASigInfoExt . . . . .	1017
8.904.2.7 pWCDMASigInfo . . . . .	1017
8.905unpack_nas_SLQSNasSwiModemStatus_t Struct Reference . . . . .	1017
8.905.1 Detailed Description . . . . .	1017
8.905.2 Field Documentation . . . . .	1017

8.905.2.1 commonInfo . . . . .	1017
8.905.2.2 pLTEInfo . . . . .	1017
8.906unpack_nas_SLQSNasSwiOTAMessageCallback_ind_t Struct Reference . . . . .	1018
8.906.1 Detailed Description . . . . .	1018
8.906.2 Field Documentation . . . . .	1018
8.906.2.1 Info . . . . .	1018
8.906.2.2 Tlvresult . . . . .	1018
8.907unpack_nas_SLQSSetSysSelectionPrefCallBack_ind_t Struct Reference . . . . .	1018
8.907.1 Detailed Description . . . . .	1018
8.907.2 Field Documentation . . . . .	1018
8.907.2.1 Info . . . . .	1018
8.907.2.2 Tlvresult . . . . .	1019
8.908unpack_nas_SLQSSwiGetLteCQI_t Struct Reference . . . . .	1019
8.908.1 Detailed Description . . . . .	1019
8.908.2 Field Documentation . . . . .	1019
8.908.2.1 CQIValueCW0 . . . . .	1019
8.908.2.2 CQIValueCW1 . . . . .	1019
8.908.2.3 ValidityCW0 . . . . .	1019
8.908.2.4 ValidityCW1 . . . . .	1019
8.909unpack_nas_SLQSSysInfoCallback_t Struct Reference . . . . .	1019
8.909.1 Detailed Description . . . . .	1020
8.909.2 Field Documentation . . . . .	1022
8.909.2.1 pAddCDMASysInfo . . . . .	1022
8.909.2.2 pAddGSMSysInfo . . . . .	1022
8.909.2.3 pAddHDRSysInfo . . . . .	1022
8.909.2.4 pAddLTESysInfo . . . . .	1022
8.909.2.5 pAddWCDMASysInfo . . . . .	1022
8.909.2.6 pCDMASrvStatusInfo . . . . .	1022
8.909.2.7 pCDMASysInfo . . . . .	1022
8.909.2.8 pGSMCalBarringSysInfo . . . . .	1022
8.909.2.9 pGSMCipherDomainSysInfo . . . . .	1022
8.909.2.10pGSMSrvStatusInfo . . . . .	1022
8.909.2.11pGSMSysInfo . . . . .	1022
8.909.2.12pHDRSrvStatusInfo . . . . .	1022
8.909.2.13pHDRSysInfo . . . . .	1022
8.909.2.14pLTESrvStatusInfo . . . . .	1022
8.909.2.15pLTESysInfo . . . . .	1022
8.909.2.16pLTEVoiceSupportSysInfo . . . . .	1022
8.909.2.17pSysInfoNoChange . . . . .	1022
8.909.2.18pWCDMACalBarringSysInfo . . . . .	1022

8.909.2.1pWCDMACipherDomainSysInfo . . . . .	1022
8.909.2.2pWCDMASrvStatusInfo . . . . .	1022
8.909.2.21pWCDMASysInfo . . . . .	1022
8.910unpack_omaDmConfigTlv_t Struct Reference . . . . .	1022
8.910.1 Detailed Description . . . . .	1023
8.910.2 Field Documentation . . . . .	1024
8.910.2.1 alertmsg . . . . .	1024
8.910.2.2 alertmsglength . . . . .	1024
8.910.2.3 state . . . . .	1024
8.910.2.4 userInputReq . . . . .	1024
8.910.2.5 userInputTimeout . . . . .	1024
8.911unpack_omaDmFotaTlv_t Struct Reference . . . . .	1024
8.911.1 Detailed Description . . . . .	1025
8.911.2 Field Documentation . . . . .	1026
8.911.2.1 description . . . . .	1026
8.911.2.2 descriptionlength . . . . .	1026
8.911.2.3 fwdloadsize . . . . .	1026
8.911.2.4 fwloadComplete . . . . .	1026
8.911.2.5 namelength . . . . .	1026
8.911.2.6 package_name . . . . .	1026
8.911.2.7 sessionType . . . . .	1026
8.911.2.8 severity . . . . .	1026
8.911.2.9 state . . . . .	1026
8.911.2.10updateCompleteStatus . . . . .	1026
8.911.2.11userInputReq . . . . .	1026
8.911.2.12userInputTimeout . . . . .	1026
8.911.2.13version . . . . .	1026
8.911.2.14versionlength . . . . .	1026
8.912unpack_omaDmNotificationsTlv_t Struct Reference . . . . .	1026
8.912.1 Field Documentation . . . . .	1027
8.912.1.1 notification . . . . .	1027
8.912.1.2 sessionStatus . . . . .	1027
8.913unpack_qmi_t Struct Reference . . . . .	1027
8.913.1 Detailed Description . . . . .	1027
8.913.2 Field Documentation . . . . .	1027
8.913.2.1 msgid . . . . .	1027
8.913.2.2 type . . . . .	1027
8.913.2.3 xid . . . . .	1027
8.914unpack_qos_dataRate_t Struct Reference . . . . .	1027
8.914.1 Detailed Description . . . . .	1027

8.914.2 Field Documentation . . . . .	1028
8.914.2.1 dataRateMax . . . . .	1028
8.914.2.2 guaranteedRate . . . . .	1028
8.915unpack_qos_IPv4Addr_t Struct Reference . . . . .	1028
8.915.1 Detailed Description . . . . .	1028
8.915.2 Field Documentation . . . . .	1028
8.915.2.1 addr . . . . .	1028
8.915.2.2 subnetMask . . . . .	1028
8.916unpack_qos_IPv6Addr_t Struct Reference . . . . .	1028
8.916.1 Detailed Description . . . . .	1028
8.916.2 Field Documentation . . . . .	1029
8.916.2.1 addr . . . . .	1029
8.916.2.2 prefixLen . . . . .	1029
8.917unpack_qos_IPv6TrafCls_t Struct Reference . . . . .	1029
8.917.1 Detailed Description . . . . .	1029
8.917.2 Field Documentation . . . . .	1029
8.917.2.1 mask . . . . .	1029
8.917.2.2 val . . . . .	1029
8.918unpack_qos_pktErrRate_t Struct Reference . . . . .	1029
8.918.1 Detailed Description . . . . .	1029
8.918.2 Field Documentation . . . . .	1030
8.918.2.1 exponent . . . . .	1030
8.918.2.2 multiplier . . . . .	1030
8.919unpack_qos_Port_t Struct Reference . . . . .	1030
8.919.1 Detailed Description . . . . .	1030
8.919.2 Field Documentation . . . . .	1030
8.919.2.1 port . . . . .	1030
8.919.2.2 range . . . . .	1030
8.920unpack_qos_QosFlowInfo_t Struct Reference . . . . .	1030
8.920.1 Detailed Description . . . . .	1030
8.920.2 Field Documentation . . . . .	1032
8.920.2.1 BearerID . . . . .	1032
8.920.2.2 is_RxQFlowGranted_Available . . . . .	1032
8.920.2.3 is_TxQFlowGranted_Available . . . . .	1032
8.920.2.4 NumRxFilters . . . . .	1032
8.920.2.5 NumTxFilters . . . . .	1032
8.920.2.6 QFlowState . . . . .	1032
8.920.2.7 RxQFilter . . . . .	1032
8.920.2.8 RxQFlowGranted . . . . .	1032
8.920.2.9 TxQFilter . . . . .	1032

8.920.2.10TxQFlowGranted . . . . .	1032
8.921unpack_qos_QosFlowInfoState_t Struct Reference . . . . .	1032
8.921.1 Detailed Description . . . . .	1032
8.921.2 Field Documentation . . . . .	1033
8.921.2.1 id . . . . .	1033
8.921.2.2 isNewFlow . . . . .	1033
8.921.2.3 state . . . . .	1033
8.922unpack_qos_SLQSQosGetNetworkStatus_t Struct Reference . . . . .	1033
8.922.1 Detailed Description . . . . .	1033
8.922.2 Field Documentation . . . . .	1033
8.922.2.1 NWQoSStatus . . . . .	1033
8.923unpack_qos_SLQSQosSwiReadApnExtraParams_t Struct Reference . . . . .	1033
8.923.1 Detailed Description . . . . .	1033
8.923.2 Field Documentation . . . . .	1034
8.923.2.1 ambr_dl . . . . .	1034
8.923.2.2 ambr_dl_ext . . . . .	1034
8.923.2.3 ambr_dl_ext2 . . . . .	1034
8.923.2.4 ambr_ul . . . . .	1034
8.923.2.5 ambr_ul_ext . . . . .	1034
8.923.2.6 ambr_ul_ext2 . . . . .	1034
8.923.2.7 apnId . . . . .	1034
8.924unpack_qos_SLQSQosSwiReadDataStats_t Struct Reference . . . . .	1034
8.924.1 Detailed Description . . . . .	1035
8.924.2 Field Documentation . . . . .	1035
8.924.2.1 apnId . . . . .	1036
8.924.2.2 numQosFlow . . . . .	1036
8.924.2.3 qosFlow . . . . .	1036
8.924.2.4 total_rx_bytes . . . . .	1036
8.924.2.5 total_rx_pkt . . . . .	1036
8.924.2.6 total_tx_bytes . . . . .	1036
8.924.2.7 total_tx_bytes_drp . . . . .	1036
8.924.2.8 total_tx_pkt . . . . .	1036
8.924.2.9 total_tx_pkt_drp . . . . .	1036
8.925unpack_qos_SLQSSetQosEventCallback_ind_t Struct Reference . . . . .	1036
8.925.1 Detailed Description . . . . .	1036
8.925.2 Field Documentation . . . . .	1036
8.925.2.1 NumFlows . . . . .	1036
8.925.2.2 QosFlowInfo . . . . .	1036
8.926unpack_qos_SLQSSetQosNWStatusCallback_ind_t Struct Reference . . . . .	1036
8.926.1 Detailed Description . . . . .	1037

8.926.2 Field Documentation . . . . .	1038
8.926.2.1 status . . . . .	1038
8.927unpack_qos_SLQSSetQosPriEventCallback_ind_t Struct Reference . . . . .	1038
8.927.1 Detailed Description . . . . .	1038
8.927.2 Field Documentation . . . . .	1038
8.927.2.1 event . . . . .	1038
8.928unpack_qos_SLQSSetQosStatusCallback_ind_t Struct Reference . . . . .	1038
8.928.1 Detailed Description . . . . .	1038
8.928.2 Field Documentation . . . . .	1040
8.928.2.1 event . . . . .	1040
8.928.2.2 id . . . . .	1040
8.928.2.3 reason . . . . .	1040
8.928.2.4 status . . . . .	1040
8.929unpack_qos_swiQosFilter_t Struct Reference . . . . .	1040
8.929.1 Detailed Description . . . . .	1040
8.929.2 Field Documentation . . . . .	1042
8.929.2.1 EspSpi . . . . .	1042
8.929.2.2 Id . . . . .	1042
8.929.2.3 index . . . . .	1042
8.929.2.4 IPv4DstAddr . . . . .	1042
8.929.2.5 IPv4SrcAddr . . . . .	1042
8.929.2.6 IPv4Tos . . . . .	1042
8.929.2.7 IPv6DstAddr . . . . .	1042
8.929.2.8 IPv6Label . . . . .	1042
8.929.2.9 IPv6SrcAddr . . . . .	1042
8.929.2.10IPv6TrafCls . . . . .	1042
8.929.2.11is_EspSpi_Available . . . . .	1042
8.929.2.12s_Id_Available . . . . .	1042
8.929.2.13s_IPv4DstAddr_Available . . . . .	1043
8.929.2.14s_IPv4SrcAddr_Available . . . . .	1043
8.929.2.15s_IPv4Tos_Available . . . . .	1043
8.929.2.16s_IPv6DstAddr_Available . . . . .	1043
8.929.2.17s_IPv6Label_Available . . . . .	1043
8.929.2.18s_IPv6SrcAddr_Available . . . . .	1043
8.929.2.19s_IPv6TrafCls_Available . . . . .	1043
8.929.2.20s_NxtHdrProto_Available . . . . .	1043
8.929.2.21is_Precedence_Available . . . . .	1043
8.929.2.22s_TCPDstPort_Available . . . . .	1043
8.929.2.23s_TCPSrcPort_Available . . . . .	1043
8.929.2.24s_TranDstPort_Available . . . . .	1043

8.929.2.25s_TransrcPort_Available . . . . .	1043
8.929.2.26s_UDPdstPort_Available . . . . .	1043
8.929.2.27s_UDPSrcPort_Available . . . . .	1043
8.929.2.28NxtHdrProto . . . . .	1043
8.929.2.29Precedence . . . . .	1043
8.929.2.30TCPDstPort . . . . .	1043
8.929.2.31TCPSrcPort . . . . .	1043
8.929.2.32TranDstPort . . . . .	1043
8.929.2.33TranSrcPort . . . . .	1043
8.929.2.34UDPdstPort . . . . .	1043
8.929.2.35UDPSrcPort . . . . .	1043
8.929.2.36version . . . . .	1043
8.930unpack_qos_swiQosFlow_t Struct Reference . . . . .	1043
8.930.1 Detailed Description . . . . .	1044
8.930.2 Field Documentation . . . . .	1047
8.930.2.1 DataRate . . . . .	1047
8.930.2.2 index . . . . .	1047
8.930.2.3 is_DataRate_Available . . . . .	1047
8.930.2.4 is_Jitter_Available . . . . .	1047
8.930.2.5 is_Latency_Available . . . . .	1047
8.930.2.6 is_LteQci_Available . . . . .	1047
8.930.2.7 is_MaxAllowedPktSz_Available . . . . .	1047
8.930.2.8 is_MinPolicedPktSz_Available . . . . .	1047
8.930.2.9 is_PktErrRate_Available . . . . .	1047
8.930.2.10s_ProfileId3GPP2_Available . . . . .	1047
8.930.2.11is_TokenBucket_Available . . . . .	1047
8.930.2.12s_TrafficClass_Available . . . . .	1047
8.930.2.13s_val_3GPP2Pri_Available . . . . .	1047
8.930.2.14s_val_3GPPImCn_Available . . . . .	1047
8.930.2.15s_val_3GPPResResidualBER_Available . . . . .	1047
8.930.2.16s_val_3GPPSigInd_Available . . . . .	1047
8.930.2.17s_val_3GPPTraHdlPri_Available . . . . .	1048
8.930.2.18Jitter . . . . .	1048
8.930.2.19Latency . . . . .	1048
8.930.2.20LteQci . . . . .	1048
8.930.2.21MaxAllowedPktSz . . . . .	1048
8.930.2.22MinPolicedPktSz . . . . .	1048
8.930.2.23PktErrRate . . . . .	1048
8.930.2.24ProfileId3GPP2 . . . . .	1048
8.930.2.25TokenBucket . . . . .	1048

8.930.2.26TrafficClass . . . . .	1048
8.930.2.27val_3GPP2Pri . . . . .	1048
8.930.2.28val_3GPPImCn . . . . .	1048
8.930.2.29val_3GPPResResidualBER . . . . .	1048
8.930.2.30val_3GPPSigInd . . . . .	1048
8.930.2.31val_3GPPTraHdlPri . . . . .	1048
8.931unpack_qos_tokenBucket_t Struct Reference . . . . .	1048
8.931.1 Detailed Description . . . . .	1048
8.931.2 Field Documentation . . . . .	1048
8.931.2.1 bucketSz . . . . .	1048
8.931.2.2 peakRate . . . . .	1049
8.931.2.3 tokenRate . . . . .	1049
8.932unpack_qos_Tos_t Struct Reference . . . . .	1049
8.932.1 Detailed Description . . . . .	1049
8.932.2 Field Documentation . . . . .	1049
8.932.2.1 mask . . . . .	1049
8.932.2.2 val . . . . .	1049
8.933unpack_QosFlowStat_t Struct Reference . . . . .	1049
8.933.1 Detailed Description . . . . .	1049
8.933.2 Field Documentation . . . . .	1050
8.933.2.1 bearerId . . . . .	1050
8.933.2.2 tx_bytes . . . . .	1050
8.933.2.3 tx_bytes_drp . . . . .	1050
8.933.2.4 tx_pkt . . . . .	1050
8.933.2.5 tx_pkt_drp . . . . .	1050
8.934unpack_sms_SendSMS_t Struct Reference . . . . .	1050
8.934.1 Detailed Description . . . . .	1050
8.934.2 Field Documentation . . . . .	1050
8.934.2.1 messageFailureCode . . . . .	1050
8.934.2.2 messageId . . . . .	1051
8.935unpack_sms_SetNewSMSCallback_ind_t Struct Reference . . . . .	1051
8.935.1 Detailed Description . . . . .	1051
8.935.2 Field Documentation . . . . .	1052
8.935.2.1 ETWSPLMNTlv . . . . .	1052
8.935.2.2 ETWSTlv . . . . .	1052
8.935.2.3 IMSTlv . . . . .	1052
8.935.2.4 MMTlv . . . . .	1052
8.935.2.5 NewMMTlv . . . . .	1052
8.935.2.6 SMSCTlv . . . . .	1052
8.935.2.7 TRMessageTlv . . . . .	1052



8.936unpack_sms_SetNewSMSCallback_t Struct Reference	1052
8.937unpack_sms_SLQSDeleteSMS_t Struct Reference	1052
8.938unpack_sms_SLQSGetSMS_t Struct Reference	1052
8.938.1 Detailed Description	1053
8.938.2 Field Documentation	1053
8.938.2.1 message	1053
8.938.2.2 messageFormat	1053
8.938.2.3 messageSize	1053
8.938.2.4 messageTag	1053
8.939unpack_sms_SLQSGetSMSList_t Struct Reference	1053
8.939.1 Detailed Description	1053
8.939.2 Field Documentation	1054
8.939.2.1 messageList	1054
8.939.2.2 messageListSize	1054
8.940unpack_sms_SLQSModifySMSStatus_t Struct Reference	1054
8.941unpack_sms_SLQSWmsMemoryFullCallBack_ind_t Struct Reference	1054
8.941.1 Detailed Description	1054
8.941.2 Field Documentation	1054
8.941.2.1 messageMode	1054
8.941.2.2 storageType	1054
8.942unpack_swiloc_SwiLocGetAutoStart_t Struct Reference	1054
8.942.1 Detailed Description	1055
8.942.2 Field Documentation	1056
8.942.2.1 fix_rate	1056
8.942.2.2 fix_rate_reported	1056
8.942.2.3 fix_type	1056
8.942.2.4 fix_type_reported	1056
8.942.2.5 function	1056
8.942.2.6 function_reported	1056
8.942.2.7 max_dist	1056
8.942.2.8 max_dist_reported	1056
8.942.2.9 max_time	1056
8.942.2.10max_time_reported	1056
8.943unpack_swioma_SLQSOMADMAAlertCallback_ind_t Struct Reference	1056
8.943.1 Detailed Description	1057
8.943.2 Field Documentation	1057
8.943.2.1 eventType	1057
8.943.2.2 SessionInfoConfig	1057
8.943.2.3 SessionInfoFota	1057
8.943.2.4 SessionInfoNotification	1057

8.944unpack_swioma_SLQSOMADMGetSessionInfo_t Struct Reference . . . . .	1057
8.944.1 Detailed Description . . . . .	1058
8.944.2 Field Documentation . . . . .	1059
8.944.2.1 Date . . . . .	1060
8.944.2.2 DateLength . . . . .	1060
8.944.2.3 PkgDescLength . . . . .	1060
8.944.2.4 PkgDescription . . . . .	1060
8.944.2.5 PkgName . . . . .	1060
8.944.2.6 PkgNameLength . . . . .	1060
8.944.2.7 RetryCount . . . . .	1060
8.944.2.8 SessionState . . . . .	1060
8.944.2.9 SessionType . . . . .	1060
8.944.2.10Severity . . . . .	1060
8.944.2.11Source . . . . .	1060
8.944.2.12SourceLength . . . . .	1060
8.944.2.13Status . . . . .	1060
8.944.2.14Time . . . . .	1060
8.944.2.15TimeLength . . . . .	1060
8.944.2.16UpdateCompleteStatus . . . . .	1060
8.945unpack_swioma_SLQSOMADMGetSettings_t Struct Reference . . . . .	1060
8.945.1 Detailed Description . . . . .	1060
8.945.2 Field Documentation . . . . .	1062
8.945.2.1 Autosdm . . . . .	1062
8.945.2.2 FOTAdownload . . . . .	1062
8.945.2.3 FOTAUpdate . . . . .	1062
8.945.2.4 FwAutoCheck . . . . .	1062
8.945.2.5 OMADMEEnabled . . . . .	1062
8.946unpack_swioma_SLQSOMADMStartSession_t Struct Reference . . . . .	1062
8.946.1 Detailed Description . . . . .	1062
8.946.2 Field Documentation . . . . .	1062
8.946.2.1 FwAvailability . . . . .	1062
8.947unpack_uim_ChangePin_t Struct Reference . . . . .	1062
8.947.1 Detailed Description . . . . .	1063
8.947.2 Field Documentation . . . . .	1063
8.947.2.1 pEncryptedPIN1 . . . . .	1063
8.947.2.2 pIndicationToken . . . . .	1063
8.947.2.3 pRemainingRetries . . . . .	1063
8.947.2.4 Tlvresult . . . . .	1063
8.948unpack_uim_GetCardStatus_t Struct Reference . . . . .	1063
8.948.1 Detailed Description . . . . .	1063

8.948.2 Field Documentation	1064
8.948.2.1 pCardStatus	1064
8.948.2.2 pHotSwapStatus	1064
8.948.2.3 Tlvresult	1064
8.949unpack_uim_ReadTransparent_t Struct Reference	1064
8.949.1 Detailed Description	1064
8.949.2 Field Documentation	1065
8.949.2.1 pCardResult	1065
8.949.2.2 pEncryptedData	1065
8.949.2.3 pIndicationToken	1065
8.949.2.4 pReadResult	1065
8.949.2.5 Tlvresult	1065
8.950unpack_uim_SetPinProtection_t Struct Reference	1065
8.950.1 Detailed Description	1065
8.950.2 Field Documentation	1066
8.950.2.1 pEncryptedPIN1	1066
8.950.2.2 pIndicationToken	1066
8.950.2.3 pRemainingRetries	1066
8.950.2.4 Tlvresult	1066
8.951unpack_uim_SetUimSlotStatusChangeCallback_ind_t Struct Reference	1066
8.951.1 Detailed Description	1066
8.951.2 Field Documentation	1066
8.951.2.1 bNumberOfPhySlots	1066
8.951.2.2 slotsstatusChange	1066
8.952unpack_uim_SLQSUIMEventRegister_t Struct Reference	1066
8.952.1 Detailed Description	1066
8.952.2 Field Documentation	1067
8.952.2.1 eventMask	1067
8.953unpack_uim_SLQSUIMGetSlotsStatus_t Struct Reference	1067
8.953.1 Detailed Description	1067
8.953.2 Field Documentation	1067
8.953.2.1 pNumberOfPhySlot	1067
8.953.2.2 pUimSlotsStatus	1067
8.954unpack_uim_SLQSUIMSetStatusChangeCallBack_ind_t Struct Reference	1067
8.954.1 Detailed Description	1067
8.954.2 Field Documentation	1068
8.954.2.1 pCardStatus	1068
8.955unpack_uim_UnblockPin_t Struct Reference	1068
8.955.1 Detailed Description	1068
8.955.2 Field Documentation	1068

8.955.2.1 pEncryptedPIN1 . . . . .	1068
8.955.2.2 pIndicationToken . . . . .	1068
8.955.2.3 pRemainingRetries . . . . .	1068
8.955.2.4 Tlvresult . . . . .	1068
8.956unpack_uim_VerifyPin_t Struct Reference . . . . .	1068
8.956.1 Detailed Description . . . . .	1069
8.956.2 Field Documentation . . . . .	1070
8.956.2.1 pEncryptedPIN1 . . . . .	1070
8.956.2.2 pIndicationToken . . . . .	1070
8.956.2.3 pRemainingRetries . . . . .	1070
8.956.2.4 Tlvresult . . . . .	1070
8.957unpack_wds_GetConnectionRate_t Struct Reference . . . . .	1070
8.957.1 Detailed Description . . . . .	1070
8.957.2 Field Documentation . . . . .	1071
8.957.2.1 currentChannelRXRate . . . . .	1071
8.957.2.2 currentChannelTXRate . . . . .	1071
8.957.2.3 maxChannelRXRate . . . . .	1071
8.957.2.4 maxChannelTXRate . . . . .	1071
8.958unpack_wds_GetDefaultProfile_t Struct Reference . . . . .	1071
8.958.1 Detailed Description . . . . .	1071
8.958.2 Field Documentation . . . . .	1071
8.958.2.1 apnname . . . . .	1071
8.958.2.2 apnsize . . . . .	1071
8.958.2.3 auth . . . . .	1072
8.958.2.4 ipaddr . . . . .	1072
8.958.2.5 ipaddrv6 . . . . .	1072
8.958.2.6 name . . . . .	1072
8.958.2.7 namesize . . . . .	1072
8.958.2.8 pdptype . . . . .	1072
8.958.2.9 pridns . . . . .	1072
8.958.2.10pridnsv6 . . . . .	1072
8.958.2.11secdns . . . . .	1072
8.958.2.12secdnsv6 . . . . .	1072
8.958.2.13username . . . . .	1072
8.958.2.14usersize . . . . .	1072
8.959unpack_wds_GetDefaultProfileNum_t Struct Reference . . . . .	1072
8.959.1 Detailed Description . . . . .	1072
8.959.2 Field Documentation . . . . .	1072
8.959.2.1 index . . . . .	1072
8.960unpack_wds_GetDormancyState_t Struct Reference . . . . .	1072

8.960.1 Detailed Description	1072
8.960.2 Field Documentation	1073
8.960.2.1 dormancyState	1073
8.961unpack_wds_GetLastMobileIPError_t Struct Reference	1073
8.961.1 Detailed Description	1073
8.961.2 Field Documentation	1073
8.961.2.1 error	1073
8.962unpack_wds_GetMobileIP_t Struct Reference	1073
8.962.1 Detailed Description	1073
8.962.2 Field Documentation	1073
8.962.2.1 mipMode	1073
8.963unpack_wds_GetMobileIPProfile_t Struct Reference	1073
8.963.1 Detailed Description	1074
8.963.2 Field Documentation	1074
8.963.2.1 AAASPI	1074
8.963.2.2 AAASState	1074
8.963.2.3 address	1074
8.963.2.4 enabled	1074
8.963.2.5 HASPI	1074
8.963.2.6 HASState	1074
8.963.2.7 NAI	1074
8.963.2.8 naiSize	1074
8.963.2.9 primaryHA	1074
8.963.2.10revTunneling	1074
8.963.2.11secondaryHA	1074
8.964unpack_wds_GetPacketStatus_t Struct Reference	1074
8.964.1 Detailed Description	1075
8.964.2 Field Documentation	1075
8.964.2.1 rXDroppedCount	1075
8.964.2.2 rXOkBytesCount	1075
8.964.2.3 rXOKBytesLastCall	1075
8.964.2.4 rXPacketErrors	1075
8.964.2.5 rXPacketOverflows	1075
8.964.2.6 rXPacketSuccesses	1075
8.964.2.7 tXDroppedCount	1075
8.964.2.8 tXOkBytesCount	1075
8.964.2.9 tXOKBytesLastCall	1075
8.964.2.10XPacketErrors	1075
8.964.2.11tXPacketOverflows	1075
8.964.2.12XPacketSuccesses	1076

8.965unpack_wds_GetSessionDuration_t Struct Reference . . . . .	1076
8.965.1 Detailed Description . . . . .	1076
8.965.2 Field Documentation . . . . .	1076
8.965.2.1 callDuration . . . . .	1076
8.966unpack_wds_GetSessionState_t Struct Reference . . . . .	1076
8.966.1 Detailed Description . . . . .	1076
8.966.2 Field Documentation . . . . .	1076
8.966.2.1 connectionStatus . . . . .	1076
8.967unpack_wds_RMSetTransferStatistics_t Struct Reference . . . . .	1076
8.968unpack_wds_SetMobileIPProfile_t Struct Reference . . . . .	1076
8.969unpack_wds_SLQSCreateProfile_t Struct Reference . . . . .	1076
8.969.1 Detailed Description . . . . .	1076
8.969.2 Field Documentation . . . . .	1077
8.969.2.1 pCreateProfileOut . . . . .	1077
8.969.2.2 pProfileID . . . . .	1077
8.969.2.3 Tlvresult . . . . .	1077
8.970unpack_wds_SLQSDeleteProfile_t Struct Reference . . . . .	1077
8.970.1 Detailed Description . . . . .	1077
8.970.2 Field Documentation . . . . .	1077
8.970.2.1 extendedErrorCode . . . . .	1077
8.971unpack_wds_SLQSGet3GPPConfigItem_t Struct Reference . . . . .	1077
8.971.1 Detailed Description . . . . .	1078
8.971.2 Field Documentation . . . . .	1078
8.971.2.1 _3gppRelease . . . . .	1078
8.971.2.2 defaultPDNEnabled . . . . .	1078
8.971.2.3 LTEAttachProfileList . . . . .	1078
8.971.2.4 LTEAttachProfileListLen . . . . .	1078
8.971.2.5 profileList . . . . .	1078
8.972unpack_wds_SLQSGetCurrDataSystemStat_t Struct Reference . . . . .	1079
8.972.1 Detailed Description . . . . .	1079
8.972.2 Field Documentation . . . . .	1079
8.972.2.1 currNetworkInfo . . . . .	1079
8.972.2.2 networkInfoLen . . . . .	1079
8.972.2.3 prefNetwork . . . . .	1079
8.973unpack_wds_SLQSGetDataBearerTechnology_t Struct Reference . . . . .	1079
8.973.1 Detailed Description . . . . .	1079
8.973.2 Field Documentation . . . . .	1079
8.973.2.1 curDataBearerTechnology . . . . .	1079
8.973.2.2 dataBearerMask . . . . .	1079
8.973.2.3 lastCallDataBearerTechnology . . . . .	1079

8.974unpack_wds_SLQSGetDUNCallInfo_t Struct Reference	1080
8.974.1 Detailed Description	1080
8.974.2 Field Documentation	1080
8.974.2.1 callEndReason	1080
8.974.2.2 channelRate	1080
8.974.2.3 connectionStatus	1080
8.974.2.4 dataBearerTech	1080
8.974.2.5 dormancyStatus	1080
8.974.2.6 lastCallDataBearerTech	1080
8.974.2.7 lastCallRXOKBytesCnt	1080
8.974.2.8 lastCallTXOKBytesCnt	1080
8.974.2.9 mdmCallDurationActive	1081
8.974.2.10rxOKBytesCount	1081
8.974.2.11txOKBytesCount	1081
8.975unpack_wds_SLQSGetProfileSettings_t Struct Reference	1081
8.975.1 Field Documentation	1081
8.975.1.1 pProfileSettings	1081
8.975.1.2 ProfileType	1081
8.975.1.3 Tlvresult	1081
8.976unpack_wds_SLQSGetRuntimeSettings_t Struct Reference	1081
8.976.1 Detailed Description	1081
8.976.2 Field Documentation	1082
8.976.2.1 APNName	1082
8.976.2.2 Authentication	1082
8.976.2.3 DomainList	1082
8.976.2.4 GPRSGrantedQoS	1082
8.976.2.5 GWAddressV4	1082
8.976.2.6 IMCNflag	1082
8.976.2.7 IPFamilyPreference	1082
8.976.2.8 IPv4	1082
8.976.2.9 IPV6AddrInfo	1082
8.976.2.10IPV6GWAddrInfo	1082
8.976.2.11Mtu	1082
8.976.2.12PCSCFAddrPCO	1083
8.976.2.13PCSCFFQDNAddrList	1083
8.976.2.14PDPTtype	1083
8.976.2.15PrimaryDNSV4	1083
8.976.2.16PrimaryDNSV6	1083
8.976.2.17ProfileID	1083
8.976.2.18ProfileName	1083

8.976.2.19SecondaryDNSV4 . . . . .	1083
8.976.2.20SecondaryDNSV6 . . . . .	1083
8.976.2.21ServerAddrList . . . . .	1083
8.976.2.22SubnetMaskV4 . . . . .	1083
8.976.2.23Technology . . . . .	1083
8.976.2.24UMTSGrantedQoS . . . . .	1083
8.976.2.25Username . . . . .	1083
8.977unpack_wds_SLQSMModifyProfile_t Struct Reference . . . . .	1083
8.977.1 Detailed Description . . . . .	1083
8.977.2 Field Documentation . . . . .	1083
8.977.2.1 pExtErrorCode . . . . .	1083
8.978unpack_wds_SLQSSetIPFamilyPreference_t Struct Reference . . . . .	1083
8.978.1 Detailed Description . . . . .	1083
8.978.2 Field Documentation . . . . .	1084
8.978.2.1 Tlvresult . . . . .	1084
8.979unpack_wds_SLQSSetPacketSrvStatusCallback_t Struct Reference . . . . .	1084
8.979.1 Detailed Description . . . . .	1084
8.979.2 Field Documentation . . . . .	1084
8.979.2.1 bearerID . . . . .	1084
8.979.2.2 conn_status . . . . .	1084
8.979.2.3 ipFamily . . . . .	1084
8.979.2.4 reconfigReqd . . . . .	1084
8.979.2.5 sessionEndReason . . . . .	1084
8.979.2.6 techName . . . . .	1085
8.979.2.7 verboseSessnEndReason . . . . .	1085
8.979.2.8 verboseSessnEndReasonType . . . . .	1085
8.980unpack_wds_SLQSSetWdsEventCallback_ind_t Struct Reference . . . . .	1085
8.980.1 Detailed Description . . . . .	1085
8.980.2 Field Documentation . . . . .	1086
8.980.2.1 currDBTechAvail . . . . .	1086
8.980.2.2 currNWInfo . . . . .	1086
8.980.2.3 dataSysStatAvail . . . . .	1086
8.980.2.4 dBTechAvail . . . . .	1086
8.980.2.5 dBTechnology . . . . .	1086
8.980.2.6 dormancyStatAvail . . . . .	1086
8.980.2.7 dormancyStatus . . . . .	1086
8.980.2.8 mipstatAvail . . . . .	1086
8.980.2.9 mipStatus . . . . .	1086
8.980.2.10netInfoLen . . . . .	1086
8.980.2.11prefNetwork . . . . .	1086



8.980.2.12ratMask . . . . .	1086
8.980.2.13rx_bytes . . . . .	1086
8.980.2.14rx_pkts . . . . .	1086
8.980.2.15soMask . . . . .	1086
8.980.2.16x_bytes . . . . .	1086
8.980.2.17x_pkts . . . . .	1086
8.980.2.18xferStatAvail . . . . .	1086
8.981unpack_wds_SLQSSGetDHCPv4ClientConfig_t Struct Reference . . . . .	1086
8.981.1 Detailed Description . . . . .	1086
8.981.2 Field Documentation . . . . .	1087
8.981.2.1 pHwConfig . . . . .	1087
8.981.2.2 pRequestOptionList . . . . .	1087
8.982unpack_wds_SLQSSStartDataSession_t Struct Reference . . . . .	1087
8.982.1 Detailed Description . . . . .	1087
8.982.2 Field Documentation . . . . .	1087
8.982.2.1 pFailureReason . . . . .	1087
8.982.2.2 psid . . . . .	1087
8.982.2.3 pVerboseFailReasonType . . . . .	1087
8.982.2.4 pVerboseFailureReason . . . . .	1087
8.983unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t Struct Reference . . . . .	1087
8.983.1 Detailed Description . . . . .	1088
8.983.2 Field Documentation . . . . .	1088
8.983.2.1 apnName . . . . .	1088
8.983.2.2 bearerId . . . . .	1088
8.983.2.3 contextId . . . . .	1088
8.983.2.4 ipv4Address . . . . .	1088
8.983.2.5 ipv4GWAddress . . . . .	1088
8.983.2.6 ipv6Address . . . . .	1089
8.983.2.7 ipv6GWAddress . . . . .	1089
8.983.2.8 prDNSIPv4Address . . . . .	1089
8.983.2.9 prDNSIPv6Address . . . . .	1089
8.983.2.10prPCSCFIPv4Address . . . . .	1089
8.983.2.11prPCSCFIPv6Address . . . . .	1089
8.983.2.12seDNSIPv4Address . . . . .	1089
8.983.2.13seDNSIPv6Address . . . . .	1089
8.983.2.14sePCSCFIPv4Address . . . . .	1089
8.983.2.15sePCSCFIPv6Address . . . . .	1089
8.984UnPackGetProfileSettingOut Struct Reference . . . . .	1089
8.984.1 Field Documentation . . . . .	1089
8.984.1.1 curProfile . . . . .	1089

8.984.1.2 pExtErrCode . . . . .	1089
8.985unpackWdsProfileParam Union Reference . . . . .	1089
8.985.1 Field Documentation . . . . .	1089
8.985.1.1 SlqsProfile3GPP . . . . .	1089
8.985.1.2 SlqsProfile3GPP2 . . . . .	1089
8.986USBCompConfig Struct Reference . . . . .	1089
8.986.1 Detailed Description . . . . .	1090
8.986.2 Field Documentation . . . . .	1091
8.986.2.1 pUSBComp . . . . .	1091
8.987USBCompParams Struct Reference . . . . .	1091
8.987.1 Detailed Description . . . . .	1091
8.987.2 Field Documentation . . . . .	1093
8.987.2.1 pNumSupUSBComps . . . . .	1093
8.987.2.2 pSupUSBComps . . . . .	1093
8.987.2.3 pUSBComp . . . . .	1093
8.988USSDNoWaitIndicationInfo Struct Reference . . . . .	1093
8.988.1 Detailed Description . . . . .	1094
8.988.2 Field Documentation . . . . .	1094
8.988.2.1 pAlphaIdentifier . . . . .	1094
8.988.2.2 pError . . . . .	1094
8.988.2.3 pFailureCause . . . . .	1094
8.988.2.4 pUSSDData . . . . .	1094
8.989USSDRespFNetwork Struct Reference . . . . .	1094
8.989.1 Detailed Description . . . . .	1094
8.989.2 Field Documentation . . . . .	1094
8.989.2.1 pRespData . . . . .	1095
8.989.2.2 pTypeCode . . . . .	1095
8.990USSInfo Struct Reference . . . . .	1095
8.990.1 Detailed Description . . . . .	1095
8.990.2 Field Documentation . . . . .	1095
8.990.2.1 ussData . . . . .	1095
8.990.2.2 ussDCS . . . . .	1095
8.990.2.3 ussLen . . . . .	1095
8.991USSResp Struct Reference . . . . .	1095
8.991.1 Field Documentation . . . . .	1096
8.991.1.1 pAlphaIDInfo . . . . .	1096
8.991.1.2 pCallId . . . . .	1096
8.991.1.3 pCcResultType . . . . .	1096
8.991.1.4 pCCSuppsType . . . . .	1096
8.991.1.5 pfailureCause . . . . .	1096

8.991.1.6 pUSSDInfo . . . . .	1096
8.992UUSInfo Struct Reference . . . . .	1096
8.992.1 Detailed Description . . . . .	1096
8.992.2 Field Documentation . . . . .	1097
8.992.2.1 UUSDData . . . . .	1097
8.992.2.2 UUSDatalen . . . . .	1097
8.992.2.3 UUSDcs . . . . .	1097
8.992.2.4 UUSType . . . . .	1097
8.993verifyUIMPIN Struct Reference . . . . .	1097
8.993.1 Detailed Description . . . . .	1098
8.993.2 Field Documentation . . . . .	1098
8.993.2.1 pinID . . . . .	1098
8.993.2.2 pinLen . . . . .	1098
8.993.2.3 pinVal . . . . .	1098
8.994voiceALSSelectLineInfo Struct Reference . . . . .	1098
8.994.1 Detailed Description . . . . .	1098
8.994.2 Field Documentation . . . . .	1099
8.994.2.1 lineValue . . . . .	1099
8.995voiceALSSetLineSwitchInfo Struct Reference . . . . .	1099
8.995.1 Detailed Description . . . . .	1099
8.995.2 Field Documentation . . . . .	1099
8.995.2.1 switchOption . . . . .	1099
8.996voiceAnswerCall Struct Reference . . . . .	1099
8.996.1 Detailed Description . . . . .	1099
8.996.2 Field Documentation . . . . .	1100
8.996.2.1 pCallId . . . . .	1100
8.997voiceBindSubscriptionInfo Struct Reference . . . . .	1100
8.997.1 Detailed Description . . . . .	1100
8.997.2 Field Documentation . . . . .	1100
8.997.2.1 subsType . . . . .	1100
8.998voiceBurstDTMFInfo Struct Reference . . . . .	1100
8.998.1 Detailed Description . . . . .	1100
8.998.2 Field Documentation . . . . .	1101
8.998.2.1 BurstDTMFInfo . . . . .	1101
8.998.2.2 pBurstDTMFLengths . . . . .	1101
8.999voiceCallInfoReq Struct Reference . . . . .	1101
8.999.1 Detailed Description . . . . .	1101
8.999.2 Field Documentation . . . . .	1101
8.999.2.1 callID . . . . .	1101
8.1000voiceCallInfoResp Struct Reference . . . . .	1101

8.1000.1Detailed Description . . . . .	1102
8.1000.2Field Documentation . . . . .	1104
8.1000.2.1pAlertingPattern . . . . .	1104
8.1000.2.2pAlertType . . . . .	1104
8.1000.2.3pAlphaIDInfo . . . . .	1104
8.1000.2.4pCallInfo . . . . .	1104
8.1000.2.5pConnectNumInfo . . . . .	1104
8.1000.2.6pDiagInfo . . . . .	1105
8.1000.2.7pOTASPStatus . . . . .	1105
8.1000.2.8pRemotePartyName . . . . .	1105
8.1000.2.9pRemotePartyNum . . . . .	1105
8.1000.2.10pSrvOpt . . . . .	1105
8.1000.2.11pUUSInfo . . . . .	1105
8.1000.2.12pVoicePrivacy . . . . .	1105
8.1000VoiceCallRequestParams Struct Reference . . . . .	1105
8.1001.1Detailed Description . . . . .	1105
8.1001.2Field Documentation . . . . .	1107
8.1001.2.1callNumber . . . . .	1107
8.1001.2.2pCallPartySubAdd . . . . .	1107
8.1001.2.3pCallType . . . . .	1107
8.1001.2.4pCLIRType . . . . .	1107
8.1001.2.5pCUGInfo . . . . .	1107
8.1001.2.6pEmergencyCategory . . . . .	1107
8.1001.2.7pSvcType . . . . .	1107
8.1001.2.8pUUSInfo . . . . .	1107
8.1001VoiceCallResponseParams Struct Reference . . . . .	1107
8.1002.1Detailed Description . . . . .	1107
8.1002.2Field Documentation . . . . .	1108
8.1002.2.1pAlphaIDInfo . . . . .	1108
8.1002.2.2pCallID . . . . .	1108
8.1002.2.3pCCResultType . . . . .	1108
8.1002.2.4pCCSUPSType . . . . .	1108
8.1002VoiceContDTMFInfo Struct Reference . . . . .	1108
8.1003.1Detailed Description . . . . .	1108
8.1003.2Field Documentation . . . . .	1109
8.1003.2.1DTMFdigit . . . . .	1109
8.1003.2.2pCallID . . . . .	1109
8.1003VoiceDTMFEventInfo Struct Reference . . . . .	1109
8.1004.1Detailed Description . . . . .	1109
8.1004.2Field Documentation . . . . .	1110

8.1004.2.1DTMFInformation . . . . .	1110
8.1004.2.2pOffLength . . . . .	1110
8.1004.2.3pOnLength . . . . .	1110
8.1005VoiceFlashInfo Struct Reference . . . . .	1110
8.1005.1Detailed Description . . . . .	1110
8.1005.2Field Documentation . . . . .	1111
8.1005.2.1pCallID . . . . .	1111
8.1005.2.2pFlashPayLd . . . . .	1111
8.1005.2.3pFlashType . . . . .	1111
8.1006VoiceGetAllCallInfo Struct Reference . . . . .	1111
8.1006.1Detailed Description . . . . .	1111
8.1006.2Field Documentation . . . . .	1113
8.1006.2.1pArrAlertingPattern . . . . .	1113
8.1006.2.2pArrAlertingType . . . . .	1113
8.1006.2.3pArrAlphaID . . . . .	1113
8.1006.2.4pArrCalledPartyNum . . . . .	1113
8.1006.2.5pArrCallEndReason . . . . .	1113
8.1006.2.6pArrCallInfo . . . . .	1113
8.1006.2.7pArrConnectPartyNum . . . . .	1113
8.1006.2.8pArrDiagInfo . . . . .	1113
8.1006.2.9pArrRedirPartyNum . . . . .	1113
8.1006.2.10pArrRemotePartyName . . . . .	1113
8.1006.2.11pArrRemotePartyNum . . . . .	1114
8.1006.2.12pArrSvcOption . . . . .	1114
8.1006.2.13pArrUUSInfo . . . . .	1114
8.1006.2.14pOTASPStatus . . . . .	1114
8.1006.2.15pVoicePrivacy . . . . .	1114
8.1007VoiceGetCallBarringReq Struct Reference . . . . .	1114
8.1007.1Detailed Description . . . . .	1114
8.1007.2Field Documentation . . . . .	1115
8.1007.2.1pSvcClass . . . . .	1115
8.1007.2.2reason . . . . .	1115
8.1008VoiceGetCallBarringResp Struct Reference . . . . .	1115
8.1008.1Detailed Description . . . . .	1115
8.1008.2Field Documentation . . . . .	1116
8.1008.2.1pAlphaIDInfo . . . . .	1116
8.1008.2.2pCallID . . . . .	1116
8.1008.2.3pCCResType . . . . .	1116
8.1008.2.4pCCSUPSType . . . . .	1116
8.1008.2.5pFailCause . . . . .	1116

8.1008.2.6pSvcClass . . . . .	1116
8.1009oiceGetCallFWReq Struct Reference . . . . .	1116
8.1009.1Detailed Description . . . . .	1117
8.1009.2Field Documentation . . . . .	1118
8.1009.2.1pSvcClass . . . . .	1118
8.1009.2.2Reason . . . . .	1118
8.1010oiceGetCallFWResp Struct Reference . . . . .	1118
8.1010.1Detailed Description . . . . .	1118
8.1010.2Field Documentation . . . . .	1119
8.1010.2.1pAlphaIDInfo . . . . .	1119
8.1010.2.2pCallID . . . . .	1120
8.1010.2.3pCCResType . . . . .	1120
8.1010.2.4pCCSUPSType . . . . .	1120
8.1010.2.5pFailCause . . . . .	1120
8.1010.2.6pGetCallFWExtInfo . . . . .	1120
8.1010.2.7pGetCallFWInfo . . . . .	1120
8.1011oiceGetCallWaitInfo Struct Reference . . . . .	1120
8.1011.1Detailed Description . . . . .	1120
8.1011.2Field Documentation . . . . .	1121
8.1011.2.1pAlphaIDInfo . . . . .	1121
8.1011.2.2pCallID . . . . .	1121
8.1011.2.3pCCResType . . . . .	1121
8.1011.2.4pCCSUPSType . . . . .	1121
8.1011.2.5pFailCause . . . . .	1121
8.1011.2.6pSvcClass . . . . .	1121
8.1012oiceGetCLIPResp Struct Reference . . . . .	1121
8.1012.1Detailed Description . . . . .	1122
8.1012.2Field Documentation . . . . .	1123
8.1012.2.1pAlphaIDInfo . . . . .	1123
8.1012.2.2pCallID . . . . .	1123
8.1012.2.3pCCResType . . . . .	1123
8.1012.2.4pCCSUPSType . . . . .	1124
8.1012.2.5pCLIPResp . . . . .	1124
8.1012.2.6pFailCause . . . . .	1124
8.1013oiceGetCLIRResp Struct Reference . . . . .	1124
8.1013.1Detailed Description . . . . .	1124
8.1013.2Field Documentation . . . . .	1125
8.1013.2.1pAlphaIDInfo . . . . .	1125
8.1013.2.2pCallID . . . . .	1125
8.1013.2.3pCCResType . . . . .	1125

8.1013.2.4pCCSUPSType . . . . .	1125
8.1013.2.5pCLIRResp . . . . .	1125
8.1013.2.6pFailCause . . . . .	1125
8.1014oiceGetCNAPResp Struct Reference . . . . .	1125
8.1014.1Detailed Description . . . . .	1125
8.1014.2Field Documentation . . . . .	1126
8.1014.2.1pAlphaIDInfo . . . . .	1126
8.1014.2.2pCallID . . . . .	1126
8.1014.2.3pCCResType . . . . .	1126
8.1014.2.4pCCSUPSType . . . . .	1127
8.1014.2.5pCNAPResp . . . . .	1127
8.1014.2.6pFailCause . . . . .	1127
8.1015oiceGetCOLPResp Struct Reference . . . . .	1127
8.1015.1Detailed Description . . . . .	1127
8.1015.2Field Documentation . . . . .	1128
8.1015.2.1pAlphaIDInfo . . . . .	1128
8.1015.2.2pCallID . . . . .	1128
8.1015.2.3pCCResType . . . . .	1128
8.1015.2.4pCCSUPSType . . . . .	1128
8.1015.2.5pCOLPResp . . . . .	1128
8.1015.2.6pFailCause . . . . .	1128
8.1016oiceGetCOLRResp Struct Reference . . . . .	1128
8.1016.1Detailed Description . . . . .	1128
8.1016.2Field Documentation . . . . .	1129
8.1016.2.1pAlphaIDInfo . . . . .	1129
8.1016.2.2pCallID . . . . .	1129
8.1016.2.3pCCResType . . . . .	1129
8.1016.2.4pCCSUPSType . . . . .	1130
8.1016.2.5pCOLRResp . . . . .	1130
8.1016.2.6pFailCause . . . . .	1130
8.1017oiceGetConfigReq Struct Reference . . . . .	1130
8.1017.1Detailed Description . . . . .	1130
8.1017.2Field Documentation . . . . .	1131
8.1017.2.1pAirTimer . . . . .	1131
8.1017.2.2pAMRStatus . . . . .	1131
8.1017.2.3pAutoAnswer . . . . .	1131
8.1017.2.4pNamID . . . . .	1131
8.1017.2.5pPrefVoicePrivacy . . . . .	1131
8.1017.2.6pPrefVoiceSO . . . . .	1131
8.1017.2.7pRoamTimer . . . . .	1131

8.1017.2.8pTTYMode . . . . .	1132
8.1017.2.9pVoiceDomainPref . . . . .	1132
8.1018VoiceGetConfigResp Struct Reference . . . . .	1132
8.1018.1Detailed Description . . . . .	1132
8.1018.2Field Documentation . . . . .	1133
8.1018.2.1pAirTimerCnt . . . . .	1133
8.1018.2.2pAutoAnswerStat . . . . .	1134
8.1018.2.3pCurAMRConfig . . . . .	1134
8.1018.2.4pCurPrefVoiceSO . . . . .	1134
8.1018.2.5pCurrTTYMode . . . . .	1134
8.1018.2.6pCurVoiceDomainPref . . . . .	1134
8.1018.2.7pCurVoicePrivacyPref . . . . .	1134
8.1018.2.8pRoamTimerCnt . . . . .	1134
8.1019VoiceIndicationRegisterInfo Struct Reference . . . . .	1134
8.1019.1Detailed Description . . . . .	1134
8.1019.2Field Documentation . . . . .	1135
8.1019.2.1pRegDTMFEvents . . . . .	1135
8.1019.2.2pRegVoicePrivacyEvents . . . . .	1135
8.1019.2.3pSuppsNotifEvents . . . . .	1135
8.1020VoiceInfoRec Struct Reference . . . . .	1135
8.1020.1Detailed Description . . . . .	1135
8.1020.2Field Documentation . . . . .	1137
8.1020.2.1callID . . . . .	1137
8.1020.2.2pCalledPartyInfo . . . . .	1137
8.1020.2.3pCallerIDInfo . . . . .	1137
8.1020.2.4pCallerNameInfo . . . . .	1137
8.1020.2.5pCallingPartyInfo . . . . .	1137
8.1020.2.6pCallWaitInd . . . . .	1137
8.1020.2.7pCLIRCause . . . . .	1137
8.1020.2.8pConnectNumInfo . . . . .	1137
8.1020.2.9pDisplInfo . . . . .	1137
8.1020.2.10ExtDisplInfo . . . . .	1137
8.1020.2.11ExtDispRecInfo . . . . .	1137
8.1020.2.12LineCtrlInfo . . . . .	1137
8.1020.2.13pNSSAudioCtrl . . . . .	1137
8.1020.2.14pNSSRelease . . . . .	1137
8.1020.2.15pRedirNumInfo . . . . .	1137
8.1020.2.16pSignalInfo . . . . .	1137
8.1021VoiceManageCallsReq Struct Reference . . . . .	1137
8.1021.1Detailed Description . . . . .	1138



8.1021.2Field Documentation . . . . .	1139
8.1021.2.1pCallID . . . . .	1139
8.1021.2.2SUPType . . . . .	1139
8.1022VoiceManageCallsResp Struct Reference . . . . .	1139
8.1022.1Detailed Description . . . . .	1139
8.1022.2Field Documentation . . . . .	1139
8.1022.2.1pFailCause . . . . .	1139
8.1023VoiceOrigUSSDNoWaitInfo Struct Reference . . . . .	1139
8.1023.1Detailed Description . . . . .	1139
8.1023.2Field Documentation . . . . .	1140
8.1023.2.1USSInformation . . . . .	1140
8.1024VoiceOTASPStatusInfo Struct Reference . . . . .	1140
8.1024.1Detailed Description . . . . .	1140
8.1024.2Field Documentation . . . . .	1141
8.1024.2.1callID . . . . .	1141
8.1024.2.2OTASPStatus . . . . .	1141
8.1025VoicePrivacyInfo Struct Reference . . . . .	1141
8.1025.1Detailed Description . . . . .	1141
8.1025.2Field Documentation . . . . .	1141
8.1025.2.1callID . . . . .	1141
8.1025.2.2voicePrivacy . . . . .	1141
8.1026VoiceSetAllCallStatusCbkJInfo Struct Reference . . . . .	1141
8.1026.1Detailed Description . . . . .	1142
8.1026.2Field Documentation . . . . .	1143
8.1026.2.1arrCallInfomation . . . . .	1143
8.1026.2.2pArrAlertingPattern . . . . .	1143
8.1026.2.3pArrAlertingType . . . . .	1143
8.1026.2.4pArrAlphaID . . . . .	1143
8.1026.2.5pArrCalledPartyNum . . . . .	1143
8.1026.2.6pArrCallEndReason . . . . .	1144
8.1026.2.7pArrConnectPartyNum . . . . .	1144
8.1026.2.8pArrDiagInfo . . . . .	1144
8.1026.2.9pArrRedirPartyNum . . . . .	1144
8.1026.2.10pArrRemotePartyName . . . . .	1144
8.1026.2.11pArrRemotePartyNum . . . . .	1144
8.1026.2.12pArrSvcOption . . . . .	1144
8.1027VoiceSetCallBarringPwdInfo Struct Reference . . . . .	1144
8.1027.1Detailed Description . . . . .	1144
8.1027.2Field Documentation . . . . .	1145
8.1027.2.1newPasswd . . . . .	1145

8.1027.2.2newPasswdAgain . . . . .	1145
8.1027.2.3oldPasswd . . . . .	1145
8.1027.2.4Reason . . . . .	1145
8.1028VoiceSetCallBarringPwdResp Struct Reference . . . . .	1145
8.1028.1Detailed Description . . . . .	1145
8.1028.2Field Documentation . . . . .	1146
8.1028.2.1pAlphaIDInfo . . . . .	1146
8.1028.2.2pCallID . . . . .	1146
8.1028.2.3pCCRResType . . . . .	1146
8.1028.2.4pCCSUPSType . . . . .	1146
8.1028.2.5pFailCause . . . . .	1146
8.1029VoiceSetConfigReq Struct Reference . . . . .	1146
8.1029.1Detailed Description . . . . .	1147
8.1029.2Field Documentation . . . . .	1148
8.1029.2.1pAirTimerConfig . . . . .	1148
8.1029.2.2pAutoAnswer . . . . .	1148
8.1029.2.3pPrefVoiceDomain . . . . .	1148
8.1029.2.4pPrefVoiceSO . . . . .	1148
8.1029.2.5pRoamTimerConfig . . . . .	1148
8.1029.2.6pTTYMode . . . . .	1148
8.1030VoiceSetConfigResp Struct Reference . . . . .	1148
8.1030.1Detailed Description . . . . .	1148
8.1030.2Field Documentation . . . . .	1150
8.1030.2.1pAirTimerStatus . . . . .	1150
8.1030.2.2pAutoAnsStatus . . . . .	1150
8.1030.2.3pPrefVoiceSOStatus . . . . .	1150
8.1030.2.4pRoamTimerStatus . . . . .	1150
8.1030.2.5pTTYConfigStatus . . . . .	1150
8.1030.2.6pVoiceDomainPrefStatus . . . . .	1150
8.1031VoiceSetPrefPrivacy Struct Reference . . . . .	1150
8.1031.1Detailed Description . . . . .	1150
8.1031.2Field Documentation . . . . .	1151
8.1031.2.1privacyPref . . . . .	1151
8.1032VoiceSetSUPSServiceReq Struct Reference . . . . .	1151
8.1032.1Detailed Description . . . . .	1151
8.1032.2Field Documentation . . . . .	1153
8.1032.2.1pCallBarringPasswd . . . . .	1153
8.1032.2.2pCallForwardingNumber . . . . .	1153
8.1032.2.3pCallFwdTypeAndPlan . . . . .	1153
8.1032.2.4pServiceClass . . . . .	1153

8.1032.2.5pTimerVal . . . . .	1153
8.1032.2.6reason . . . . .	1153
8.1032.2.7voiceSvc . . . . .	1153
8.1033voiceSetSUPSServiceResp Struct Reference . . . . .	1153
8.1033.1Detailed Description . . . . .	1154
8.1033.2Field Documentation . . . . .	1154
8.1033.2.1pAlphaIDInfo . . . . .	1154
8.1033.2.2pCallID . . . . .	1154
8.1033.2.3pCCResultType . . . . .	1154
8.1033.2.4pCCSUPSType . . . . .	1154
8.1033.2.5pFailCause . . . . .	1154
8.1034voiceStopContDTMFInfo Struct Reference . . . . .	1155
8.1034.1Detailed Description . . . . .	1155
8.1034.2Field Documentation . . . . .	1155
8.1034.2.1callID . . . . .	1155
8.1035voiceSUPSInfo Struct Reference . . . . .	1155
8.1035.1Detailed Description . . . . .	1155
8.1035.2Field Documentation . . . . .	1157
8.1035.2.1pAlphaIDInfo . . . . .	1157
8.1035.2.2pCallBarPasswd . . . . .	1157
8.1035.2.3pCallFwdInfo . . . . .	1157
8.1035.2.4pCallFWNum . . . . .	1157
8.1035.2.5pCallFWTimerVal . . . . .	1157
8.1035.2.6pCallID . . . . .	1157
8.1035.2.7pCLIPstatus . . . . .	1157
8.1035.2.8pCLIRstatus . . . . .	1157
8.1035.2.9pCNAPstatus . . . . .	1157
8.1035.2.10pCOLPstatus . . . . .	1157
8.1035.2.11pCOLRstatus . . . . .	1157
8.1035.2.12pDataSrc . . . . .	1157
8.1035.2.13pFailCause . . . . .	1158
8.1035.2.14pNewPwdData . . . . .	1158
8.1035.2.15pReason . . . . .	1158
8.1035.2.16pSvcClass . . . . .	1158
8.1035.2.17pUSSInfo . . . . .	1158
8.1035.2.18pSUPSInformation . . . . .	1158
8.1036voiceSUPSNotification Struct Reference . . . . .	1158
8.1036.1Detailed Description . . . . .	1158
8.1036.2Field Documentation . . . . .	1160
8.1036.2.1callID . . . . .	1160

8.1036.2.2	notifType	1160
8.1036.2.3	CUGIndex	1160
8.1036.2.4	PECTNum	1160
8.1037	WcdmaCellInfo Struct Reference	1160
8.1037.1	Detailed Description	1160
8.1037.2	Field Documentation	1161
8.1037.2.1	cpich_ecno	1161
8.1037.2.2	cpich_rscp	1161
8.1037.2.3	psc	1161
8.1037.2.4	srxlev	1161
8.1038	WCDMAECIOThresh Struct Reference	1161
8.1038.1	Detailed Description	1161
8.1038.2	Field Documentation	1161
8.1038.2.1	WCDMAECIOThreshList	1161
8.1038.2.2	WCDMAECIOThreshListLen	1161
8.1039	WCDMAInfoLTENNeighborCell Struct Reference	1161
8.1039.1	Detailed Description	1162
8.1039.2	Field Documentation	1162
8.1039.2.1	UMTSLTENbrCell	1162
8.1039.2.2	umtsLTENbrCellLen	1162
8.1039.2.3	wcdmaRRCState	1162
8.1040	WcdmaLongMsgDecodingParams Struct Reference	1162
8.1040.1	Detailed Description	1163
8.1040.2	Field Documentation	1164
8.1040.2.1	Date	1164
8.1040.2.2	IsUDHPresent	1164
8.1040.2.3	Message	1164
8.1040.2.4	PartNum	1164
8.1040.2.5	ReferenceNum	1164
8.1040.2.6	ScAddr	1164
8.1040.2.7	ScAddrLength	1164
8.1040.2.8	SenderAddr	1164
8.1040.2.9	SenderAddrLength	1164
8.1040.2.10	TextMsg	1164
8.1040.2.11	TextMsgLength	1164
8.1040.2.12	TotalNum	1164
8.1040.2.13	Time	1164
8.1041	WcdmaMsgDecodingParams Struct Reference	1164
8.1041.1	Detailed Description	1164
8.1041.2	Field Documentation	1165

8.1041.2.1Date	1165
8.1041.2.2pMessage	1165
8.1041.2.3pScAddr	1165
8.1041.2.4pScAddrLength	1165
8.1041.2.5pSenderAddr	1165
8.1041.2.6pSenderAddrLength	1165
8.1041.2.7pTextMsg	1166
8.1041.2.8pTextMsgLength	1166
8.1041.2.9Time	1166
8.1042cdmaMsgEncodingParams Struct Reference	1166
8.1042.1Detailed Description	1166
8.1042.2Field Documentation	1166
8.1042.2.1alphabet	1166
8.1042.2.2messageSize	1166
8.1042.2.3pDestAddr	1166
8.1042.2.4pPDUMessage	1166
8.1042.2.5pTextMsg	1167
8.1043WCDMARSSIThresh Struct Reference	1167
8.1043.1Detailed Description	1167
8.1043.2Field Documentation	1167
8.1043.2.1pWCDMARSSIThreshList	1167
8.1043.2.2WCDMARSSIThreshListLen	1167
8.1044WCDMASysInfo Struct Reference	1167
8.1044.1Detailed Description	1168
8.1044.2Field Documentation	1171
8.1044.2.1cellId	1171
8.1044.2.2cellIdValid	1171
8.1044.2.3hsCallStatus	1171
8.1044.2.4hsCallStatusValid	1171
8.1044.2.5hsInd	1171
8.1044.2.6hsIndValid	1171
8.1044.2.7lac	1172
8.1044.2.8lacValid	1172
8.1044.2.9MCC	1172
8.1044.2.10MNC	1172
8.1044.2.11networkIdValid	1172
8.1044.2.12sc	1172
8.1044.2.13scValid	1172
8.1044.2.14regRejectInfoValid	1172
8.1044.2.15jCause	1172

8.1044.2.1	ObjectSrvDomain	1172
8.1044.2.1	SysInfoWCDMA	1172
8.1045	wcdmaUARFCN Struct Reference	1172
8.1045.1	Detailed Description	1172
8.1045.2	Field Documentation	1172
8.1045.2.1	status	1172
8.1045.2.2	uarfcn	1172
8.1046	wds_currNetworkInfo Struct Reference	1172
8.1046.1	Detailed Description	1173
8.1046.2	Field Documentation	1175
8.1046.2.1	NetworkType	1175
8.1046.2.2	RATMask	1175
8.1046.2.3	SOMask	1175
8.1047	wds_Domain Struct Reference	1175
8.1047.1	Detailed Description	1175
8.1047.2	Field Documentation	1175
8.1047.2.1	domainLen	1175
8.1047.2.2	domainName	1175
8.1048	wds_DomainNameList Struct Reference	1175
8.1048.1	Detailed Description	1175
8.1048.2	Field Documentation	1176
8.1048.2.1	domain	1176
8.1048.2.2	numInstances	1176
8.1049	wds_GPRSQoS Struct Reference	1176
8.1049.1	Detailed Description	1176
8.1049.2	Field Documentation	1176
8.1049.2.1	delayClass	1176
8.1049.2.2	meanThroughputClass	1176
8.1049.2.3	peakThroughputClass	1177
8.1049.2.4	precedenceClass	1177
8.1049.2.5	reliabilityClass	1177
8.1050	wds_IPV6AddressInfo Struct Reference	1177
8.1050.1	Detailed Description	1177
8.1050.2	Field Documentation	1177
8.1050.2.1	IPAddressV6	1177
8.1050.2.2	IPV6PrefixLen	1177
8.1051	wds_IPV6GWAddressInfo Struct Reference	1177
8.1051.1	Detailed Description	1177
8.1051.2	Field Documentation	1178
8.1051.2.1	gwAddressV6	1178

8.1051.2.2gwV6PrefixLen . . . . .	1178
8.1052nds_PCSCFFQDNAddress Struct Reference . . . . .	1178
8.1052.1Detailed Description . . . . .	1178
8.1052.2Field Documentation . . . . .	1178
8.1052.2.1fqdnAddr . . . . .	1178
8.1052.2.2fqdnLen . . . . .	1178
8.1053nds_PCSCFFQDNAddressList Struct Reference . . . . .	1178
8.1053.1Detailed Description . . . . .	1179
8.1053.2Field Documentation . . . . .	1180
8.1053.2.1numInstances . . . . .	1180
8.1053.2.2pcsfFQDNAddress . . . . .	1180
8.1054nds_PCSCFIPv4ServerAddressList Struct Reference . . . . .	1180
8.1054.1Detailed Description . . . . .	1180
8.1054.2Field Documentation . . . . .	1180
8.1054.2.1numInstances . . . . .	1180
8.1054.2.2pcsfIPv4Addr . . . . .	1180
8.1055nds_ProfileIdentifier Struct Reference . . . . .	1180
8.1055.1Detailed Description . . . . .	1180
8.1055.2Field Documentation . . . . .	1181
8.1055.2.1profileIndex . . . . .	1181
8.1055.2.2profileType . . . . .	1181
8.1056nds_profileInfo Union Reference . . . . .	1181
8.1056.1Detailed Description . . . . .	1181
8.1056.2Field Documentation . . . . .	1181
8.1056.2.1SIqsProfile3GPP . . . . .	1181
8.1056.2.2SIqsProfile3GPP2 . . . . .	1181
8.1057nds_UMTSMinQoS Struct Reference . . . . .	1181
8.1057.1Detailed Description . . . . .	1182
8.1057.2Field Documentation . . . . .	1185
8.1057.2.1deliveryErrSDU . . . . .	1185
8.1057.2.2grntDownlinkBitrate . . . . .	1185
8.1057.2.3grntUplinkBitrate . . . . .	1185
8.1057.2.4maxDownlinkBitrate . . . . .	1185
8.1057.2.5maxSDUSize . . . . .	1185
8.1057.2.6maxUplinkBitrate . . . . .	1185
8.1057.2.7qosDeliveryOrder . . . . .	1185
8.1057.2.8resBerRatio . . . . .	1185
8.1057.2.9sduErrorRatio . . . . .	1185
8.1057.2.10trafficClass . . . . .	1185
8.1057.2.11trafficPriority . . . . .	1185

8.1057.2.12TransferDelay . . . . .	1185
8.1058WdsByteTotals Struct Reference . . . . .	1185
8.1058.1Detailed Description . . . . .	1185
8.1058.2Field Documentation . . . . .	1186
8.1058.2.1ByteTotalsElmntsV4 . . . . .	1186
8.1058.2.2ByteTotalsElmntsV6 . . . . .	1186
8.1058.2.3pV4sessionId . . . . .	1186
8.1058.2.4pV6sessionId . . . . .	1186
8.1059WdsByteTotalsElmnts Struct Reference . . . . .	1186
8.1059.1Detailed Description . . . . .	1186
8.1059.2Field Documentation . . . . .	1186
8.1059.2.1pRXTotalBytes . . . . .	1187
8.1059.2.2pTXTotalBytes . . . . .	1187
8.1060WdsClientLeaseChange Struct Reference . . . . .	1187
8.1060.1Detailed Description . . . . .	1187
8.1060.2Field Documentation . . . . .	1187
8.1060.2.1pEnableNotification . . . . .	1187
8.1061WdsConnectionRate Struct Reference . . . . .	1187
8.1061.1Detailed Description . . . . .	1187
8.1061.2Field Documentation . . . . .	1188
8.1061.2.1ConnRateElmntsV4 . . . . .	1188
8.1061.2.2ConnRateElmntsV6 . . . . .	1188
8.1061.2.3pV4sessionId . . . . .	1188
8.1061.2.4pV6sessionId . . . . .	1188
8.1062WdsConnectionRateElmnts Struct Reference . . . . .	1188
8.1062.1Detailed Description . . . . .	1188
8.1062.2Field Documentation . . . . .	1189
8.1062.2.1pCurrentChannelRXRate . . . . .	1189
8.1062.2.2pCurrentChannelTXRate . . . . .	1189
8.1062.2.3pMaxChannelRXRate . . . . .	1189
8.1062.2.4pMaxChannelTXRate . . . . .	1189
8.1063WdsDHCPv4ClientLeaseInd Struct Reference . . . . .	1189
8.1063.1Detailed Description . . . . .	1189
8.1063.2Field Documentation . . . . .	1190
8.1063.2.1pIPv4Addr . . . . .	1190
8.1063.2.2pLeaseState . . . . .	1190
8.1063.2.3pOptList . . . . .	1190
8.1063.2.4pProfileId . . . . .	1190
8.1064WdsDHCPv4Config Struct Reference . . . . .	1190
8.1064.1Detailed Description . . . . .	1190



8.1064.2 Field Documentation	1190
8.1064.2.1 pHwConfig	1190
8.1064.2.2 pProfileId	1190
8.1064.2.3 pRequestOptionList	1190
8.1065 wdsDhcpv4HwConfig Struct Reference	1191
8.1065.1 Detailed Description	1191
8.1065.2 Field Documentation	1191
8.1065.2.1 chaddr	1191
8.1065.2.2 chaddrLen	1191
8.1065.2.3 hwType	1191
8.1066 wdsDHCPv4HWConfig Struct Reference	1191
8.1066.1 Detailed Description	1191
8.1066.2 Field Documentation	1192
8.1066.2.1 chaddr	1192
8.1066.2.2 chaddrLen	1192
8.1066.2.3 hwType	1192
8.1067 wdsDHCPv4Option Struct Reference	1192
8.1067.1 Detailed Description	1192
8.1067.2 Field Documentation	1192
8.1067.2.1 optCode	1192
8.1067.2.2 optVal	1192
8.1067.2.3 optValLen	1192
8.1068 wdsDhcpv4Option Struct Reference	1192
8.1068.1 Detailed Description	1193
8.1068.2 Field Documentation	1193
8.1068.2.1 optCode	1193
8.1068.2.2 optVal	1193
8.1068.2.3 optValLen	1193
8.1069 wdsDhcpv4OptionList Struct Reference	1193
8.1069.1 Detailed Description	1193
8.1069.2 Field Documentation	1193
8.1069.2.1 numOpt	1193
8.1069.2.2 pOptList	1193
8.1070 wdsDHCPv4OptionList Struct Reference	1193
8.1070.1 Detailed Description	1194
8.1070.2 Field Documentation	1194
8.1070.2.1 numOpt	1194
8.1070.2.2 pOptList	1194
8.1071 wdsDhcpv4ProfileId Struct Reference	1194
8.1071.1 Detailed Description	1194

8.1071.2Field Documentation . . . . .	1194
8.1071.2.1profileId . . . . .	1194
8.1071.2.2profileType . . . . .	1194
8.1072VdsDHCPv4ProfileId Struct Reference . . . . .	1195
8.1072.1Detailed Description . . . . .	1195
8.1072.2Field Documentation . . . . .	1195
8.1072.2.1profileId . . . . .	1195
8.1072.2.2profileType . . . . .	1195
8.1073WDSGetLoopbackData Struct Reference . . . . .	1195
8.1073.1Detailed Description . . . . .	1195
8.1073.2Field Documentation . . . . .	1196
8.1073.2.1ByteLoopbackMode . . . . .	1196
8.1073.2.2ByteLoopbackMultiplier . . . . .	1196
8.1074WdsIpAddressInfoReq Struct Reference . . . . .	1196
8.1074.1Field Documentation . . . . .	1196
8.1074.1.1ip . . . . .	1196
8.1074.1.2pv4sessionId . . . . .	1196
8.1074.1.3pv6sessionId . . . . .	1196
8.1075VdsPktStatisticsElmnts Struct Reference . . . . .	1196
8.1075.1Detailed Description . . . . .	1197
8.1075.2Field Documentation . . . . .	1198
8.1075.2.1pRXDroppedCount . . . . .	1198
8.1075.2.2pRXOkBytesCount . . . . .	1198
8.1075.2.3pRXOKBytesLastCall . . . . .	1198
8.1075.2.4pRXPacketErrors . . . . .	1198
8.1075.2.5pRXPacketOverflows . . . . .	1199
8.1075.2.6pRXPacketSuccesses . . . . .	1199
8.1075.2.7pTXDroppedCount . . . . .	1199
8.1075.2.8pTXOkBytesCount . . . . .	1199
8.1075.2.9pTXOKBytesLastCall . . . . .	1199
8.1075.2.10pTXPacketErrors . . . . .	1199
8.1075.2.11pTXPacketOverflows . . . . .	1199
8.1075.2.12pTXPacketSuccesses . . . . .	1199
8.1076VdsPktStatisticsReq Struct Reference . . . . .	1199
8.1076.1Detailed Description . . . . .	1199
8.1076.2Field Documentation . . . . .	1199
8.1076.2.1pStatMask . . . . .	1199
8.1077VdsPktStatisticsResp Struct Reference . . . . .	1199
8.1077.1Detailed Description . . . . .	1199
8.1077.2Field Documentation . . . . .	1200

8.1077.2.1PktStatElmntsV4 . . . . .	1200
8.1077.2.2PktStatElmntsV6 . . . . .	1200
8.1077.2.3pV4sessionId . . . . .	1200
8.1077.2.4pV6sessionId . . . . .	1200
8.1078WdsProfileParam Union Reference . . . . .	1200
8.1078.1Detailed Description . . . . .	1200
8.1078.2Field Documentation . . . . .	1200
8.1078.2.1SlqsProfile3GPP . . . . .	1200
8.1078.2.2SlqsProfile3GPP2 . . . . .	1200
8.1079WdsRunTimeSettings Struct Reference . . . . .	1200
8.1079.1Detailed Description . . . . .	1201
8.1079.2Field Documentation . . . . .	1201
8.1079.2.1rts . . . . .	1201
8.1079.2.2v4sessionId . . . . .	1201
8.1079.2.3v6sessionId . . . . .	1201
8.1080WdsSetEventReportReq Struct Reference . . . . .	1201
8.1080.1Detailed Description . . . . .	1202
8.1080.2Field Documentation . . . . .	1204
8.1080.2.1pCurrChannelRateInd . . . . .	1204
8.1080.2.2pCurrDataBearerTechInd . . . . .	1204
8.1080.2.3pCurrPrefDataSysInd . . . . .	1204
8.1080.2.4pDataBearerTechInd . . . . .	1204
8.1080.2.5pDataCallStatusChangeInd . . . . .	1204
8.1080.2.6pDataSystemStatusChangeInd . . . . .	1204
8.1080.2.7pDormancyStatusInd . . . . .	1204
8.1080.2.8pEVDOPageMonPerChangeInd . . . . .	1204
8.1080.2.9pMIPStatusInd . . . . .	1204
8.1080.2.10pTransferStatInd . . . . .	1204
8.1081WDSSetLoopbackData Struct Reference . . . . .	1204
8.1081.1Detailed Description . . . . .	1205
8.1081.2Field Documentation . . . . .	1206
8.1081.2.1pLoopbackMode . . . . .	1206
8.1081.2.2pLoopbackMultiplier . . . . .	1206
8.1082WDSSWICurrentChannelRates Struct Reference . . . . .	1206
8.1082.1Detailed Description . . . . .	1206
8.1082.2Field Documentation . . . . .	1206
8.1082.2.1current_channel_rx_rate . . . . .	1206
8.1082.2.2current_channel_tx_rate . . . . .	1206
8.1082.2.3max_channel_rx_rate . . . . .	1207
8.1082.2.4max_channel_tx_rate . . . . .	1207

<b>9</b>	<b>File Documentation</b>	<b>1209</b>
9.1	apdoxypages.c File Reference	1209
9.1.1	Detailed Description	1209
9.2	common.h File Reference	1209
9.2.1	Macro Definition Documentation	1211
9.2.1.1	DEAULT_LOC_TIMEOUT_IN_SEC	1211
9.2.1.2	MINREQBKLEN	1211
9.2.1.3	MSGID_AND_LEN	1211
9.2.1.4	MSGID_DONT_CARE	1211
9.2.1.5	SDK_VALIDATE_INPUT_PACK_PARAM	1211
9.2.1.6	SDU_HDR_LEN	1211
9.2.1.7	UNUSEDPARAM	1211
9.2.2	Typedef Documentation	1211
9.2.2.1	logger	1211
9.2.3	Enumeration Type Documentation	1211
9.2.3.1	eLOG_LEVEL	1211
9.2.3.2	eQMI_SVC	1211
9.2.3.3	eTimeout	1212
9.2.3.4	msgtype	1212
9.2.4	Function Documentation	1212
9.2.4.1	fill_pack_ctx	1212
9.2.4.2	fill_sdu_hdr	1212
9.2.4.3	get_version	1212
9.2.4.4	helper_get_resp_ctx	1212
9.2.4.5	helper_get_xid	1213
9.2.4.6	helper_set_log_func	1213
9.2.4.7	helper_set_log_lvl	1213
9.2.4.8	libpack_GetVersion	1213
9.2.4.9	libpack_log	1213
9.2.4.10	unpack_result_code_only	1213
9.2.5	Variable Documentation	1213
9.2.5.1	glog	1213
9.2.5.2	gloglvl	1213
9.3	dms.h File Reference	1213
9.3.1	Macro Definition Documentation	1217
9.3.1.1	DMS_IMGDETAILS_LEN	1217
9.3.1.2	DMS_MAX_CUST_ID_LEN	1217
9.3.1.3	DMS_MAX_CUST_VALUE_LEN	1218
9.3.1.4	DMS_MAX_FWUPDATE_LOG_STR_SZ	1218
9.3.1.5	DMS_MAX_FWUPDATE_REF_STR_SZ	1218

9.3.1.6	DMS_PM_FACTORY	1218
9.3.1.7	DMS_PM_LOW	1218
9.3.1.8	DMS_PM_OFFLINE	1218
9.3.1.9	DMS_PM_ONLINE	1218
9.3.1.10	DMS_PM_PERSISTENT_LOW	1218
9.3.1.11	DMS_PM_RESET	1218
9.3.1.12	DMS_PM_SHUT_DOWN	1218
9.3.1.13	DMS_SET_REPORT_DISABLE	1218
9.3.1.14	DMS_SET_REPORT_ENABLE	1218
9.3.1.15	DMS_SLQSFWINFO_APPVERSION_SZ	1218
9.3.1.16	DMS_SLQSFWINFO_BOOTVERSION_SZ	1218
9.3.1.17	DMS_SLQSFWINFO_CARRIER_SZ	1218
9.3.1.18	DMS_SLQSFWINFO_CUR_CARR_NAME	1218
9.3.1.19	DMS_SLQSFWINFO_CUR_CARR_REV	1218
9.3.1.20	DMS_SLQSFWINFO_MODELID_SZ	1218
9.3.1.21	DMS_SLQSFWINFO_PACKAGEID_SZ	1218
9.3.1.22	DMS_SLQSFWINFO_PRIVERSION_SZ	1218
9.3.1.23	DMS_SLQSFWINFO_SKU_SZ	1218
9.3.1.24	DMS_SWI_SET_IND_DISABLE	1218
9.3.1.25	DMS_SWI_SET_IND_ENABLE	1218
9.3.1.26	DMS_UINT8_MAX_STRING_SZ	1218
9.3.1.27	MAX_BUILD_ID_LEN	1218
9.3.1.28	SLQS_MAX_DYING_GASP_CFG_SMS_CONTENT_LENGTH	1218
9.3.1.29	SLQS_MAX_DYING_GASP_CFG_SMS_NUMBER_LENGTH	1218
9.3.1.30	UNIQUE_ID_LEN	1218
9.3.2	Function Documentation	1219
9.3.2.1	pack_dms_GetActivationState	1219
9.3.2.2	pack_dms_GetBandCapability	1219
9.3.2.3	pack_dms_GetCrashAction	1219
9.3.2.4	pack_dms_GetCustFeature	1220
9.3.2.5	pack_dms_GetCustFeaturesV2	1221
9.3.2.6	pack_dms_GetDeviceCap	1221
9.3.2.7	pack_dms_GetDeviceCapabilities	1221
9.3.2.8	pack_dms_GetDeviceHardwareRev	1221
9.3.2.9	pack_dms_GetDeviceMfr	1222
9.3.2.10	pack_dms_GetDeviceSerialNumbers	1222
9.3.2.11	pack_dms_GetFirmwareInfo	1222
9.3.2.12	pack_dms_GetFirmwareRevision	1223
9.3.2.13	pack_dms_GetFirmwareRevisions	1223
9.3.2.14	pack_dms_GetFSN	1223

9.3.2.15	<a href="#">pack_dms_GetHardwareRevision</a>	1224
9.3.2.16	<a href="#">pack_dms_GetIMSI</a>	1224
9.3.2.17	<a href="#">pack_dms_GetModelID</a>	1224
9.3.2.18	<a href="#">pack_dms_GetNetworkTime</a>	1225
9.3.2.19	<a href="#">pack_dms_GetPower</a>	1225
9.3.2.20	<a href="#">pack_dms_GetPRLVersion</a>	1225
9.3.2.21	<a href="#">pack_dms_GetSerialNumbers</a>	1226
9.3.2.22	<a href="#">pack_dms_GetUSBComp</a>	1226
9.3.2.23	<a href="#">pack_dms_GetVoiceNumber</a>	1226
9.3.2.24	<a href="#">pack_dms_SetCrashAction</a>	1227
9.3.2.25	<a href="#">pack_dms_SetCustFeature</a>	1227
9.3.2.26	<a href="#">pack_dms_SetCustFeaturesV2</a>	1228
9.3.2.27	<a href="#">pack_dms_SetEventReport</a>	1228
9.3.2.28	<a href="#">pack_dms_SetFirmwarePreference</a>	1228
9.3.2.29	<a href="#">pack_dms_SetPower</a>	1229
9.3.2.30	<a href="#">pack_dms_SetUSBComp</a>	1229
9.3.2.31	<a href="#">pack_dms_SLQSDmsSwiGetResetInfo</a>	1229
9.3.2.32	<a href="#">pack_dms_SLQSDmsSwiIndicationRegister</a>	1230
9.3.2.33	<a href="#">pack_dms_SLQSGetBandCapability</a>	1230
9.3.2.34	<a href="#">pack_dms_SLQSSwiClearDyingGaspStatistics</a>	1230
9.3.2.35	<a href="#">pack_dms_SLQSSwiGetDyingGaspCfg</a>	1231
9.3.2.36	<a href="#">pack_dms_SLQSSwiGetDyingGaspStatistics</a>	1231
9.3.2.37	<a href="#">pack_dms_SLQSSwiGetFirmwareCurr</a>	1231
9.3.2.38	<a href="#">pack_dms_SLQSSwiGetFwUpdateStatus</a>	1232
9.3.2.39	<a href="#">pack_dms_SLQSSwiSetDyingGaspCfg</a>	1232
9.3.2.40	<a href="#">pack_dms_UIMGetICCID</a>	1232
9.3.2.41	<a href="#">unpack_dms_GetActivationState</a>	1233
9.3.2.42	<a href="#">unpack_dms_GetBandCapability</a>	1233
9.3.2.43	<a href="#">unpack_dms_GetCrashAction</a>	1233
9.3.2.44	<a href="#">unpack_dms_GetCustFeature</a>	1234
9.3.2.45	<a href="#">unpack_dms_GetCustFeaturesV2</a>	1234
9.3.2.46	<a href="#">unpack_dms_GetDeviceCap</a>	1234
9.3.2.47	<a href="#">unpack_dms_GetDeviceCapabilities</a>	1234
9.3.2.48	<a href="#">unpack_dms_GetDeviceHardwareRev</a>	1235
9.3.2.49	<a href="#">unpack_dms_GetDeviceMfr</a>	1235
9.3.2.50	<a href="#">unpack_dms_GetDeviceSerialNumbers</a>	1235
9.3.2.51	<a href="#">unpack_dms_GetFirmwareInfo</a>	1236
9.3.2.52	<a href="#">unpack_dms_GetFirmwareRevision</a>	1236
9.3.2.53	<a href="#">unpack_dms_GetFirmwareRevisions</a>	1236
9.3.2.54	<a href="#">unpack_dms_GetFSN</a>	1237

9.3.2.55	<a href="#">unpack_dms_GetHardwareRevision</a>	1237
9.3.2.56	<a href="#">unpack_dms_GetIMSI</a>	1237
9.3.2.57	<a href="#">unpack_dms_GetModelID</a>	1238
9.3.2.58	<a href="#">unpack_dms_GetNetworkTime</a>	1238
9.3.2.59	<a href="#">unpack_dms_GetPower</a>	1238
9.3.2.60	<a href="#">unpack_dms_GetPRLVersion</a>	1239
9.3.2.61	<a href="#">unpack_dms_GetSerialNumbers</a>	1239
9.3.2.62	<a href="#">unpack_dms_GetUSBComp</a>	1239
9.3.2.63	<a href="#">unpack_dms_GetVoiceNumber</a>	1240
9.3.2.64	<a href="#">unpack_dms_SetCrashAction</a>	1240
9.3.2.65	<a href="#">unpack_dms_SetCustFeature</a>	1240
9.3.2.66	<a href="#">unpack_dms_SetCustFeaturesV2</a>	1241
9.3.2.67	<a href="#">unpack_dms_SetEventReport</a>	1241
9.3.2.68	<a href="#">unpack_dms_SetEventReport_ind</a>	1241
9.3.2.69	<a href="#">unpack_dms_SetFirmwarePreference</a>	1242
9.3.2.70	<a href="#">unpack_dms_SetPower</a>	1242
9.3.2.71	<a href="#">unpack_dms_SetUSBComp</a>	1242
9.3.2.72	<a href="#">unpack_dms_SLQSDmsSwiGetResetInfo</a>	1243
9.3.2.73	<a href="#">unpack_dms_SLQSDmsSwiGetResetInfo_Ind</a>	1243
9.3.2.74	<a href="#">unpack_dms_SLQSDmsSwiIndicationRegister</a>	1243
9.3.2.75	<a href="#">unpack_dms_SLQSGetBandCapability</a>	1244
9.3.2.76	<a href="#">unpack_dms_SLQSSwiClearDyingGaspStatistics</a>	1244
9.3.2.77	<a href="#">unpack_dms_SLQSSwiGetDyingGaspCfg</a>	1244
9.3.2.78	<a href="#">unpack_dms_SLQSSwiGetDyingGaspStatistics</a>	1245
9.3.2.79	<a href="#">unpack_dms_SLQSSwiGetFirmwareCurr</a>	1245
9.3.2.80	<a href="#">unpack_dms_SLQSSwiGetFwUpdateStatus</a>	1245
9.3.2.81	<a href="#">unpack_dms_SLQSSwiSetDyingGaspCfg</a>	1246
9.3.2.82	<a href="#">unpack_dms_UIMGetICCID</a>	1246
9.4	<a href="#">fms.h File Reference</a>	1246
9.4.1	<a href="#">Macro Definition Documentation</a>	1247
9.4.1.1	<a href="#">FMS_FW_PRI_BUILD_MATCH_LEN</a>	1247
9.4.1.2	<a href="#">FMS_GOB_I_LISTENTRIES_MAX</a>	1247
9.4.1.3	<a href="#">FMS_GOB_I_MBN_BUILD_ID_STR_LEN</a>	1247
9.4.1.4	<a href="#">FMS_GOB_I_MBN_IMG_ID_STR_LEN</a>	1247
9.4.1.5	<a href="#">FMS_IMAGE_ID_BUILD_ID_LEN</a>	1247
9.4.1.6	<a href="#">FMS_IMAGE_ID_IMG_ID_LEN</a>	1248
9.4.1.7	<a href="#">FMS_IMAGE_ID_MAX_ENTRIES</a>	1248
9.4.1.8	<a href="#">FMS_IMAGE_ID_PRI_IMGTYPE</a>	1248
9.4.1.9	<a href="#">FMS_MAX_IMAGE_ID_ELEMENT</a>	1248
9.4.1.10	<a href="#">FMS_MAX_IMAGE_PREFERENCE_IMAGE_SIZE</a>	1248

9.4.2	Function Documentation	1248
9.4.2.1	GetValidFwPriCombinations	1248
9.4.2.2	pack_fms_GetImagesPreference	1248
9.4.2.3	pack_fms_GetStoredImages	1249
9.4.2.4	pack_fms_SetImagesPreference	1249
9.4.2.5	unpack_fms_GetImagesPreference	1249
9.4.2.6	unpack_fms_GetStoredImages	1249
9.4.2.7	unpack_fms_SetImagesPreference	1249
9.5	loc.h File Reference	1250
9.5.1	Macro Definition Documentation	1252
9.5.1.1	LOC_UINT8_MAX_STRING_SZ	1252
9.5.1.2	LOCEVENTMASKBATCHFULLNOTIFICATION	1252
9.5.1.3	LOCEVENTMASKENGINESTATE	1252
9.5.1.4	LOCEVENTMASKFIXSESSIONSTATE	1252
9.5.1.5	LOCEVENTMASKGEOFENCEBATCHBREACHNOTIFICATION	1252
9.5.1.6	LOCEVENTMASKGEOFENCEBREACHNOTIFICATION	1252
9.5.1.7	LOCEVENTMASKGEOFENCEGENALERT	1252
9.5.1.8	LOCEVENTMASKGNSSMEASUREMENTREPORT	1252
9.5.1.9	LOCEVENTMASKGNSSSVINFO	1252
9.5.1.10	LOCEVENTMASKINJECTPOSITIONREQ	1252
9.5.1.11	LOCEVENTMASKINJECTPREDICTEDORBITSREQ	1252
9.5.1.12	LOCEVENTMASKINJECTTIMERREQ	1253
9.5.1.13	LOCEVENTMASKINJECTWIFIAPDATAREQ	1253
9.5.1.14	LOCEVENTMASKINVALIDVALUE	1253
9.5.1.15	LOCEVENTMASKLIVEBATCHEDPOSITIONREPORT	1253
9.5.1.16	LOCEVENTMASKLOCATIONSERVERCONNECTIONREQ	1253
9.5.1.17	LOCEVENTMASKMOTIONDATACONTROL	1253
9.5.1.18	LOCEVENTMASKNIGEOFENCENOTIFICATION	1253
9.5.1.19	LOCEVENTMASKNINOTIFYVERIFYREQ	1253
9.5.1.20	LOCEVENTMASKNMEA	1253
9.5.1.21	LOCEVENTMASKPEDOMETERCONTROL	1253
9.5.1.22	LOCEVENTMASKPOSITIONREPORT	1253
9.5.1.23	LOCEVENTMASKSENSORSTREAMINGREADYSTATUS	1254
9.5.1.24	LOCEVENTMASKSETSPISTREAMINGREPORT	1254
9.5.1.25	LOCEVENTMASKTIMESYNCREQ	1254
9.5.1.26	LOCEVENTMASKVEHICLEDATAREADYSTATUS	1254
9.5.1.27	LOCEVENTMASKWIFIREQ	1254
9.5.2	Enumeration Type Documentation	1254
9.5.2.1	anonymous enum	1254
9.5.3	Function Documentation	1254



9.5.3.1	<a href="#">pack_loc_DeleteAssistData</a>	1254
9.5.3.2	<a href="#">pack_loc_EventRegister</a>	1255
9.5.3.3	<a href="#">pack_loc_SetExtPowerState</a>	1255
9.5.3.4	<a href="#">pack_loc_SetOperationMode</a>	1255
9.5.3.5	<a href="#">pack_loc_Start</a>	1255
9.5.3.6	<a href="#">pack_loc_Stop</a>	1256
9.5.3.7	<a href="#">unpack_loc_DeleteAssistData</a>	1256
9.5.3.8	<a href="#">unpack_loc_EngineState_Ind</a>	1256
9.5.3.9	<a href="#">unpack_loc_EventRegister</a>	1257
9.5.3.10	<a href="#">unpack_loc_PositionRpt_Ind</a>	1257
9.5.3.11	<a href="#">unpack_loc_SetExtPowerConfig_Ind</a>	1257
9.5.3.12	<a href="#">unpack_loc_SetExtPowerState</a>	1258
9.5.3.13	<a href="#">unpack_loc_SetOperationMode</a>	1258
9.5.3.14	<a href="#">unpack_loc_Start</a>	1258
9.5.3.15	<a href="#">unpack_loc_Stop</a>	1259
9.6	<a href="#">nas.h File Reference</a>	1259
9.6.1	<a href="#">Macro Definition Documentation</a>	1264
9.6.1.1	<a href="#">NAS_MAX_DESCRIPTION_LENGTH</a>	1264
9.6.1.2	<a href="#">NAS_MAX_NUM_NETWORKS</a>	1264
9.6.1.3	<a href="#">NAS_OTA_MESSAGE_MAX_BUF_SIZE</a>	1264
9.6.1.4	<a href="#">NAS_PLMN_LENGTH</a>	1264
9.6.1.5	<a href="#">NAS_SERVING_SYSTEM_INFO_MAX_RADIO_INTERFACE_LIST</a>	1264
9.6.2	<a href="#">Enumeration Type Documentation</a>	1265
9.6.2.1	<a href="#">LIBPACK_NAS_LTE_CPHY_CA_BW_NRB</a>	1265
9.6.2.2	<a href="#">LIBPACK_NAS_LTE_CPHY_SCELL_STATE</a>	1265
9.6.3	<a href="#">Function Documentation</a>	1265
9.6.3.1	<a href="#">pack_nas_GetACCOLC</a>	1265
9.6.3.2	<a href="#">pack_nas_GetANAAAAAuthenticationStatus</a>	1265
9.6.3.3	<a href="#">pack_nas_GetCDMANetworkParameters</a>	1265
9.6.3.4	<a href="#">pack_nas_GetHomeNetwork</a>	1266
9.6.3.5	<a href="#">pack_nas_GetNetworkPreference</a>	1266
9.6.3.6	<a href="#">pack_nas_GetRFInfo</a>	1266
9.6.3.7	<a href="#">pack_nas_GetServingNetwork</a>	1267
9.6.3.8	<a href="#">pack_nas_GetServingNetworkCapabilities</a>	1268
9.6.3.9	<a href="#">pack_nas_GetSignalStrengths</a>	1268
9.6.3.10	<a href="#">pack_nas_PerformNetworkScan</a>	1268
9.6.3.11	<a href="#">pack_nas_SetACCOLC</a>	1269
9.6.3.12	<a href="#">pack_nas_SetLURejectCallback</a>	1269
9.6.3.13	<a href="#">pack_nas_SetNetworkPreference</a>	1269
9.6.3.14	<a href="#">pack_nas_SetRFInfoCallback</a>	1270

9.6.3.15	<a href="#">pack_nas_SlqsGetLTECphyCAInfo</a>	1270
9.6.3.16	<a href="#">pack_nas_SLQSGetNetworkTime</a>	1270
9.6.3.17	<a href="#">pack_nas_SLQSGetPLMNName</a>	1270
9.6.3.18	<a href="#">pack_nas_SLQSGetServingSystem</a>	1271
9.6.3.19	<a href="#">pack_nas_SLQSGetSignalStrength</a>	1271
9.6.3.20	<a href="#">pack_nas_SLQSGetSysInfo</a>	1271
9.6.3.21	<a href="#">pack_nas_SLQSGetSysSelectionPref</a>	1272
9.6.3.22	<a href="#">pack_nas_SLQSInitiateNetworkRegistration</a>	1272
9.6.3.23	<a href="#">pack_nas_SLQSNasConfigSigInfo2</a>	1272
9.6.3.24	<a href="#">pack_nas_SLQSNasGetCellLocationInfo</a>	1273
9.6.3.25	<a href="#">pack_nas_SLQSNasGetSigInfo</a>	1273
9.6.3.26	<a href="#">pack_nas_SLQSNasIndicationRegisterExt</a>	1273
9.6.3.27	<a href="#">pack_nas_SLQSNasSwiModemStatus</a>	1274
9.6.3.28	<a href="#">pack_nas_SLQSNasSwiOTAMessageCallback</a>	1274
9.6.3.29	<a href="#">pack_nas_SLQSSetBandPreference</a>	1274
9.6.3.30	<a href="#">pack_nas_SLQSSetSignalStrengthsCallback</a>	1275
9.6.3.31	<a href="#">pack_nas_SLQSSetSysSelectionPref</a>	1275
9.6.3.32	<a href="#">pack_nas_SLQSSwiGetLteCQI</a>	1275
9.6.3.33	<a href="#">unpack_nas_GetACCOLC</a>	1276
9.6.3.34	<a href="#">unpack_nas_GetANAAAAAuthenticationStatus</a>	1276
9.6.3.35	<a href="#">unpack_nas_GetCDMANetworkParameters</a>	1276
9.6.3.36	<a href="#">unpack_nas_GetHomeNetwork</a>	1277
9.6.3.37	<a href="#">unpack_nas_GetNetworkPreference</a>	1277
9.6.3.38	<a href="#">unpack_nas_GetRFInfo</a>	1277
9.6.3.39	<a href="#">unpack_nas_GetServingNetwork</a>	1277
9.6.3.40	<a href="#">unpack_nas_GetServingNetworkCapabilities</a>	1278
9.6.3.41	<a href="#">unpack_nas_GetSignalStrengths</a>	1278
9.6.3.42	<a href="#">unpack_nas_PerformNetworkScan</a>	1278
9.6.3.43	<a href="#">unpack_nas_SetACCOLC</a>	1279
9.6.3.44	<a href="#">unpack_nas_SetDataCapabilitiesCallback_ind</a>	1279
9.6.3.45	<a href="#">unpack_nas_SetEventReportInd</a>	1279
9.6.3.46	<a href="#">unpack_nas_SetLURejectCallback</a>	1279
9.6.3.47	<a href="#">unpack_nas_SetNetworkPreference</a>	1280
9.6.3.48	<a href="#">unpack_nas_SetRFInfoCallback</a>	1280
9.6.3.49	<a href="#">unpack_nas_SetRoamingIndicatorCallback_ind</a>	1280
9.6.3.50	<a href="#">unpack_nas_SetServingSystemCallback_ind</a>	1280
9.6.3.51	<a href="#">unpack_nas_SlqsGetLTECphyCAInfo</a>	1280
9.6.3.52	<a href="#">unpack_nas_SLQSGetNetworkTime</a>	1280
9.6.3.53	<a href="#">unpack_nas_SLQSGetPLMNName</a>	1281
9.6.3.54	<a href="#">unpack_nas_SLQSGetServingSystem</a>	1281

9.6.3.55	<a href="#">unpack_nas_SLQSGetSignalStrength</a>	1281
9.6.3.56	<a href="#">unpack_nas_SLQSGetSysInfo</a>	1282
9.6.3.57	<a href="#">unpack_nas_SLQSGetSysSelectionPref</a>	1282
9.6.3.58	<a href="#">unpack_nas_SLQSInitiateNetworkRegistration</a>	1282
9.6.3.59	<a href="#">unpack_nas_SLQSNasConfigSigInfo2</a>	1283
9.6.3.60	<a href="#">unpack_nas_SLQSNasGetCellLocationInfo</a>	1283
9.6.3.61	<a href="#">unpack_nas_SLQSNasGetSigInfo</a>	1283
9.6.3.62	<a href="#">unpack_nas_SLQSNasIndicationRegisterExt</a>	1284
9.6.3.63	<a href="#">unpack_nas_SLQSNasNetworkTimeCallBack_ind</a>	1284
9.6.3.64	<a href="#">unpack_nas_SLQSNasSigInfoCallback</a>	1284
9.6.3.65	<a href="#">unpack_nas_SLQSNasSwtModemStatus</a>	1285
9.6.3.66	<a href="#">unpack_nas_SLQSNasSwtOTAMessageCallback</a>	1285
9.6.3.67	<a href="#">unpack_nas_SLQSNasSwtOTAMessageCallback_ind</a>	1285
9.6.3.68	<a href="#">unpack_nas_SLQSNasSysInfoCallback</a>	1286
9.6.3.69	<a href="#">unpack_nas_SLQSSetBandPreference</a>	1286
9.6.3.70	<a href="#">unpack_nas_SLQSSetSignalStrengthsCallback</a>	1286
9.6.3.71	<a href="#">unpack_nas_SLQSSetSysSelectionPref</a>	1286
9.6.3.72	<a href="#">unpack_nas_SLQSSetSysSelectionPrefCallBack_ind</a>	1287
9.6.3.73	<a href="#">unpack_nas_SLQSSwtGetLteCQI</a>	1287
9.7	<a href="#">qaCbkCatEventReportInd.h File Reference</a>	1287
9.7.1	<a href="#">Macro Definition Documentation</a>	1288
9.7.1.1	<a href="#">QMI_CAN_COMMON_EVENT_TLV_NUMBER</a>	1288
9.7.1.2	<a href="#">QMI_MAX_CAT_EVENT_DATA_LENGTH</a>	1288
9.7.2	<a href="#">Enumeration Type Documentation</a>	1288
9.7.2.1	<a href="#">eQMI_CAT_EVENT_REPORT_IND_TLV</a>	1288
9.7.2.2	<a href="#">eQMI_CAT_EVENT_REPORT_IND_TLV_LENGTH</a>	1289
9.7.3	<a href="#">Function Documentation</a>	1289
9.7.3.1	<a href="#">UpkQmiCbkCatEventReportInd</a>	1289
9.8	<a href="#">qaCbkSwtOmaDmEventReportInd.h File Reference</a>	1289
9.8.1	<a href="#">Macro Definition Documentation</a>	1290
9.8.1.1	<a href="#">QMI_SWIOMA_DM_CONFIG</a>	1290
9.8.1.2	<a href="#">QMI_SWIOMA_DM_FOTA</a>	1290
9.8.1.3	<a href="#">QMI_SWIOMA_DM_NOT</a>	1290
9.8.2	<a href="#">Enumeration Type Documentation</a>	1290
9.8.2.1	<a href="#">eQMI_SWIOMA_DM_EVENT_REPORT_IND</a>	1290
9.8.3	<a href="#">Function Documentation</a>	1290
9.8.3.1	<a href="#">UpkQmiCbkSwtOmaDmEventReportInd</a>	1290
9.8.3.2	<a href="#">UpkQmiCbkSwtOmaDmEventReportIndExt</a>	1290
9.9	<a href="#">qaGobiApiAudio.h File Reference</a>	1290
9.9.1	<a href="#">Detailed Description</a>	1291

9.9.2	Function Documentation	1291
9.9.2.1	SLQSGetAudioPathConfig	1291
9.9.2.2	SLQSGetAudioProfile	1291
9.9.2.3	SLQSGetAudioVoTLBConfig	1292
9.9.2.4	SLQSSetAudioPathConfig	1292
9.9.2.5	SLQSSetAudioProfile	1293
9.9.2.6	SLQSSetAudioVoTLBConfig	1293
9.10	qaGobiApiCat.h File Reference	1294
9.10.1	Detailed Description	1294
9.10.2	Function Documentation	1294
9.10.2.1	CATSendEnvelopeCommand	1294
9.10.2.2	CATSendTerminalResponse	1295
9.11	qaGobiApiCbK.h File Reference	1296
9.11.1	Detailed Description	1303
9.11.2	Macro Definition Documentation	1303
9.11.2.1	CBK_DISABLE_EVENT	1303
9.11.2.2	CBK_ENABLE_EVENT	1303
9.11.2.3	CBK_NOCHANGE	1303
9.11.2.4	DEREGISTER_EVENT	1303
9.11.2.5	DEREGISTER_SRV	1303
9.11.2.6	DHCP_MAX_NUM_OPTIONS	1303
9.11.2.7	DHCP_OPTION_DATA_BUF_SIZE	1303
9.11.2.8	EVENT_MASK_CARD	1303
9.11.2.9	EVENT_MASK_DEREGISTER_ALL	1304
9.11.2.10	EVENT_MASK_PHY_SLOT_STATUS	1304
9.11.2.11	FIRST_INSTANCE	1304
9.11.2.12	INVALID_INSTACNE	1304
9.11.2.13	IPV4	1304
9.11.2.14	IPV4V6	1304
9.11.2.15	IPV6	1304
9.11.2.16	LOC_EVENT_MASK_ENG_STATE	1304
9.11.2.17	LOC_EVENT_MASK_GNSS_SV_INFO	1304
9.11.2.18	LOC_EVENT_MASK_INJECT_TIME	1304
9.11.2.19	LOC_EVENT_MASK_SENSOR_STREAM	1304
9.11.2.20	LOC_EVENT_MASK_TIME_SYNC	1304
9.11.2.21	LOC_EVENT_POSITION_REPORT	1304
9.11.2.22	MAX_MITIGATION_DEV_ID_LEN	1304
9.11.2.23	MAX_NO_OF_APPLICATIONS	1304
9.11.2.24	MAX_NO_OF_CALLS	1304
9.11.2.25	MAX_NO_OF_FILES	1304

9.11.2.26 MAX_NO_OF_SLOTS . . . . .	1304
9.11.2.27 MAX_NO_OF_UUSINFO . . . . .	1304
9.11.2.28 MAX_PATH_LENGTH . . . . .	1304
9.11.2.29 MAX_RADIO_INTERFACE_LIST . . . . .	1304
9.11.2.30 MAXUSSDLENGTH . . . . .	1304
9.11.2.31 NAS_SRV . . . . .	1304
9.11.2.32 NUM_OF_SET . . . . .	1304
9.11.2.33 PDS_SRV . . . . .	1304
9.11.2.34 QMI_ETWS_MAX_PAYLOAD_LENGTH . . . . .	1304
9.11.2.35 QMI_MAX_VOICE_NUMBER_LENGTH . . . . .	1304
9.11.2.36 QMI_WMS_MAX_PAYLOAD_LENGTH . . . . .	1304
9.11.2.37 REGISTER_EVENT . . . . .	1305
9.11.2.38 REGISTER_SRV . . . . .	1305
9.11.2.39 SECOND_INSTANCE . . . . .	1305
9.11.2.40 SIGSTRENGTH_THRESHOLD_ARR_SZ . . . . .	1305
9.11.2.41 THIRD_INSTANCE . . . . .	1305
9.11.2.42 USSD_DCS_8BIT . . . . .	1305
9.11.2.43 USSD_DCS_ASCII . . . . .	1305
9.11.2.44 USSD_DCS_UCS2 . . . . .	1305
9.11.2.45 VOICE_SRV . . . . .	1305
9.11.2.46 WDS_SRV . . . . .	1305
9.11.3 Typedef Documentation . . . . .	1305
9.11.3.1 accelAcceptReady . . . . .	1305
9.11.3.2 accelTempAcceptReady . . . . .	1305
9.11.3.3 eDevState . . . . .	1306
9.11.3.4 eSMSEventType . . . . .	1306
9.11.3.5 gpsTime . . . . .	1306
9.11.3.6 gyroAcceptReady . . . . .	1307
9.11.3.7 gyroTempAcceptReady . . . . .	1308
9.11.3.8 LteNasReleaseInfo . . . . .	1308
9.11.3.9 modemTempNotification . . . . .	1309
9.11.3.10 packetSrvStatus . . . . .	1309
9.11.3.11 precisionDilution . . . . .	1311
9.11.3.12 ResetInfoNotification . . . . .	1312
9.11.3.13 sensorDataUsage . . . . .	1313
9.11.3.14 sessionInformation . . . . .	1313
9.11.3.15 sessionInformationExt . . . . .	1313
9.11.3.16 SMSAsyncRawSend . . . . .	1313
9.11.3.17 SMSCAddressInfo . . . . .	1315
9.11.3.18 SMSEtwsMessageInfo . . . . .	1315

9.11.3.19 SMSEtwPlmnInfo . . . . .	1315
9.11.3.20 SMSEventInfo . . . . .	1316
9.11.3.21 SMSMessageModelInfo . . . . .	1317
9.11.3.22 SMSMTMessageInfo . . . . .	1317
9.11.3.23 SMSOnIMSInfo . . . . .	1318
9.11.3.24 SMSTransferRouteMTMessageInfo . . . . .	1318
9.11.3.25 svUsedforFix . . . . .	1318
9.11.3.26 SwiOTAMsg . . . . .	1319
9.11.3.27 tFNActivationStatus . . . . .	1319
9.11.3.28 tFNAllCallStatus . . . . .	1320
9.11.3.29 tFNASwiLTECphyCallInfo . . . . .	1320
9.11.3.30 tFNASwiOTAMsg . . . . .	1320
9.11.3.31 tFNAsyncRawSend . . . . .	1321
9.11.3.32 tFNBandPreference . . . . .	1322
9.11.3.33 tFNCATEvent . . . . .	1324
9.11.3.34 tFNCbkUimSlotStatusChangeInd . . . . .	1324
9.11.3.35 tFNDataCapabilities . . . . .	1324
9.11.3.36 tFNDataSysStatus . . . . .	1325
9.11.3.37 tFNDelAssistData . . . . .	1325
9.11.3.38 tFNDeviceStateChange . . . . .	1325
9.11.3.39 tFNDHCPv4ClientLeaseStatus . . . . .	1326
9.11.3.40 tFNDTMFEvent . . . . .	1326
9.11.3.41 tFNDUNCallInfo . . . . .	1326
9.11.3.42 tFNEventPosition . . . . .	1326
9.11.3.43 tFNFwDIdCompletion . . . . .	1326
9.11.3.44 tFNGnssSvInfo . . . . .	1327
9.11.3.45 tFNHDRPersonality . . . . .	1327
9.11.3.46 tFNImsaPdpStatus . . . . .	1327
9.11.3.47 tFNImsaRatStatus . . . . .	1328
9.11.3.48 tFNImsaRegStatus . . . . .	1328
9.11.3.49 tFNImsaSvcStatus . . . . .	1328
9.11.3.50 tFNImRegMgrConfig . . . . .	1328
9.11.3.51 tFNImSIPConfig . . . . .	1328
9.11.3.52 tFNImSMSConfig . . . . .	1329
9.11.3.53 tFNImUserConfig . . . . .	1329
9.11.3.54 tFNImVoIPConfig . . . . .	1329
9.11.3.55 tFNInfoRec . . . . .	1329
9.11.3.56 tFNInjectPosition . . . . .	1329
9.11.3.57 tFNInjectSensorData . . . . .	1330
9.11.3.58 tFNInjectTimeStatus . . . . .	1330

9.11.3.59 tFNInjectUTCTime . . . . .	1330
9.11.3.60 tFNLURreject . . . . .	1330
9.11.3.61 tFNMemoryFull . . . . .	1332
9.11.3.62 tFNMessageWaiting . . . . .	1332
9.11.3.63 tFNMitiLvlRpt . . . . .	1332
9.11.3.64 tFNMobileIPStatus . . . . .	1332
9.11.3.65 tFNModemTemplInfo . . . . .	1332
9.11.3.66 tFNNet . . . . .	1333
9.11.3.67 tFNNetworkTime . . . . .	1334
9.11.3.68 tFNNewGPS . . . . .	1334
9.11.3.69 tFNNewNMEA . . . . .	1335
9.11.3.70 tFNNewRMTransferStatistics . . . . .	1335
9.11.3.71 tFNNewSMS . . . . .	1336
9.11.3.72 tFNOMADMState . . . . .	1336
9.11.3.73 tFNOpMode . . . . .	1337
9.11.3.74 tFNOTASPStatus . . . . .	1337
9.11.3.75 tFNPacketSrvState . . . . .	1338
9.11.3.76 tFNPDSState . . . . .	1339
9.11.3.77 tFNPower . . . . .	1339
9.11.3.78 tFNPrivacyChange . . . . .	1339
9.11.3.79 tFNQosNWStatus . . . . .	1340
9.11.3.80 tFNQosPriEvent . . . . .	1340
9.11.3.81 tFNQosStatus . . . . .	1340
9.11.3.82 tFNRankIndicator . . . . .	1341
9.11.3.83 tFNResetInfo . . . . .	1341
9.11.3.84 tFNRfInfo . . . . .	1342
9.11.3.85 tFNRoamingIndicator . . . . .	1342
9.11.3.86 tFNSDKTerminated . . . . .	1342
9.11.3.87 tFNSensorStreaming . . . . .	1343
9.11.3.88 tFNServingSystem . . . . .	1343
9.11.3.89 tFNSetCradleMount . . . . .	1343
9.11.3.90 tFNSetEngineState . . . . .	1343
9.11.3.91 tFNSetEventTimeSync . . . . .	1343
9.11.3.92 tFNSetExtPowerConfig . . . . .	1343
9.11.3.93 tFNSigInfo . . . . .	1343
9.11.3.94 tFNSignalStrength . . . . .	1343
9.11.3.95 tFNLSQSOMADMAAlert . . . . .	1343
9.11.3.96 tFNLSQSQOSEvent . . . . .	1344
9.11.3.97 tFNLSQSSessionState . . . . .	1344
9.11.3.98 tFNLSQSSignalStrengths . . . . .	1344

9.11.3.99	tFNSLQSWDSEvent	1344
9.11.3.100	tFNSMSEvents	1345
9.11.3.101	tFNSUPSInfo	1345
9.11.3.102	tFNSUPSNotification	1345
9.11.3.103	tFNSysInfo	1345
9.11.3.104	tFNSysSelectionPref	1345
9.11.3.105	tFNtransLayerInfo	1346
9.11.3.106	tFNtransNWRegInfo	1346
9.11.3.107	tFNUIMRefresh	1346
9.11.3.108	tFNUIMStatusChangeInfo	1346
9.11.3.109	tFNUSSDNotification	1347
9.11.3.110	tFNUSSDNoWaitIndication	1348
9.11.3.111	tFNUSSDRelease	1348
9.11.3.112	ttransLayerNotification	1348
9.11.3.113	ttransNWRegInfoNotification	1348
9.11.4	Enumeration Type Documentation	1349
9.11.4.1	device_state_enum	1349
9.11.4.2	eQaQMIService	1349
9.11.4.3	SMSEventType	1349
9.11.5	Function Documentation	1350
9.11.5.1	iSetCATEventCallback	1350
9.11.5.2	iSetSignalStrengthCallback	1350
9.11.5.3	iSLQSSetDUNCallInfoCallback	1350
9.11.5.4	iSLQSSetSignalStrengthsCallback	1350
9.11.5.5	iSLQSSetWdsFirstInstEventCallback	1350
9.11.5.6	iSLQSSetWdsSecondInstEventCallback	1350
9.11.5.7	iSLQSSetWdsThirdInstEventCallback	1350
9.11.5.8	iSLQSSetWdsXferStatsFirstInstCallback	1350
9.11.5.9	iSLQSSetWdsXferStatsSecondInstCallback	1350
9.11.5.10	SetActivationStatusCallback	1350
9.11.5.11	SetCATEventCallback	1350
9.11.5.12	SetDataCapabilitiesCallback	1352
9.11.5.13	SetDeviceStateChangeCbK	1352
9.11.5.14	SetFwDIdCompletionCbK	1353
9.11.5.15	SetGPSCallback	1353
9.11.5.16	SetLocCradleMountCallback	1353
9.11.5.17	SetLocDeleteAssistDataCallback	1354
9.11.5.18	SetLocEngineStateCallback	1355
9.11.5.19	SetLocEventPositionCallback	1355
9.11.5.20	SetLocEventTimeSyncCallback	1355



9.11.5.21 SetLocGnssSvInfoCallback . . . . .	1355
9.11.5.22 SetLocInjectSensorDataCallback . . . . .	1356
9.11.5.23 SetLocInjectTimeCallback . . . . .	1356
9.11.5.24 SetLocOpModeCallback . . . . .	1356
9.11.5.25 SetLocSensorStreamingCallback . . . . .	1357
9.11.5.26 SetLocSetExtPowerConfigCallback . . . . .	1357
9.11.5.27 SetLURejectCallback . . . . .	1357
9.11.5.28 SetMobileIPStatusCallback . . . . .	1358
9.11.5.29 SetNasLTECphyCalndCallback . . . . .	1358
9.11.5.30 SetNetChangeCbK . . . . .	1358
9.11.5.31 SetNewSMSCallback . . . . .	1359
9.11.5.32 SetNMEACallback . . . . .	1359
9.11.5.33 SetOMADMStateCallback . . . . .	1360
9.11.5.34 SetPDSSStateCallback . . . . .	1360
9.11.5.35 SetPowerCallback . . . . .	1360
9.11.5.36 SetRankIndicatorCallback . . . . .	1361
9.11.5.37 SetRFInfoCallback . . . . .	1361
9.11.5.38 SetRMTransferStatisticsCallback . . . . .	1361
9.11.5.39 SetRoamingIndicatorCallback . . . . .	1362
9.11.5.40 SetSignalStrengthCallback . . . . .	1362
9.11.5.41 SetSLQSOMADMAAlertCallback . . . . .	1363
9.11.5.42 SetSLQSOMADMAAlertCallbackExt . . . . .	1363
9.11.5.43 SetUimSlotStatusChangeCallback . . . . .	1363
9.11.5.44 SetUSSDNotificationCallback . . . . .	1364
9.11.5.45 SetUSSDNoWaitIndicationCallback . . . . .	1364
9.11.5.46 SetUSSDReleaseCallback . . . . .	1364
9.11.5.47 SLQSNasNetworkTimeCallBack . . . . .	1365
9.11.5.48 SLQSNasSigInfo2CallBack . . . . .	1365
9.11.5.49 SLQSNasSigInfoCallBack . . . . .	1366
9.11.5.50 SLQSNasSwiOTAMessageCallback . . . . .	1366
9.11.5.51 SLQSNasSysInfoCallBack . . . . .	1367
9.11.5.52 SLQSSetBandPreferenceCbK . . . . .	1367
9.11.5.53 SLQSSetDataSystemStatusCallback . . . . .	1368
9.11.5.54 SLQSSetDHCPv4ClientLeaseStatusCallback . . . . .	1369
9.11.5.55 SLQSSetDUNCallInfoCallback . . . . .	1369
9.11.5.56 SLQSSetIMSAPdpStatusCallback . . . . .	1370
9.11.5.57 SLQSSetIMSARatStatusCallback . . . . .	1370
9.11.5.58 SLQSSetIMSARegStatusCallback . . . . .	1370
9.11.5.59 SLQSSetIMSASvcStatusCallback . . . . .	1371
9.11.5.60 SLQSSetIMSSMSConfigCallback . . . . .	1371

9.11.5.61 SLQSSetIMSUserConfigCallback . . . . .	1372
9.11.5.62 SLQSSetIMSVoIPConfigCallback . . . . .	1372
9.11.5.63 SLQSSetLocInjectPositionCallback . . . . .	1372
9.11.5.64 SLQSSetLocInjectUTCTimeCallback . . . . .	1373
9.11.5.65 SLQSSetModemTempCallback . . . . .	1373
9.11.5.66 SLQSSetPacketSrvStatusCallback . . . . .	1373
9.11.5.67 SLQSSetQosEventCallback . . . . .	1374
9.11.5.68 SLQSSetQosNWStatusCallback . . . . .	1374
9.11.5.69 SLQSSetQosPriEventCallback . . . . .	1375
9.11.5.70 SLQSSetQosStatusCallback . . . . .	1376
9.11.5.71 SLQSSetRegMgrConfigCallback . . . . .	1376
9.11.5.72 SLQSSetSDKTerminatedCallback . . . . .	1377
9.11.5.73 SLQSSetServingSystemCallback . . . . .	1377
9.11.5.74 SLQSSetSessionStateCallback . . . . .	1378
9.11.5.75 SLQSSetSignalStrengthsCallback . . . . .	1378
9.11.5.76 SLQSSetSIPConfigCallback . . . . .	1379
9.11.5.77 SLQSSetSMSEventCallback . . . . .	1380
9.11.5.78 SLQSSetSwiGetResetInfoCallback . . . . .	1380
9.11.5.79 SLQSSetSwiHDRPersCallback . . . . .	1380
9.11.5.80 SLQSSetSysSelectionPrefCallBack . . . . .	1381
9.11.5.81 SLQSSetTransLayerInfoCallback . . . . .	1381
9.11.5.82 SLQSSetTransNWRegInfoCallback . . . . .	1382
9.11.5.83 SLQSSetWdsEventCallback . . . . .	1383
9.11.5.84 SLQSSetWdsTransferStatisticCallback . . . . .	1384
9.11.5.85 SLQSTmdMitigationLvlRptCallback . . . . .	1384
9.11.5.86 SLQSUIMSetRefreshCallBack . . . . .	1385
9.11.5.87 SLQSUIMSetStatusChangeCallBack . . . . .	1385
9.11.5.88 SLQSVoiceInfoRecCallback . . . . .	1385
9.11.5.89 SLQSVoiceSetAllCallStatusCallBack . . . . .	1386
9.11.5.90 SLQSVoiceSetDTMFEventCallBack . . . . .	1386
9.11.5.91 SLQSVoiceSetOTASPStatusCallBack . . . . .	1387
9.11.5.92 SLQSVoiceSetPrivacyChangeCallBack . . . . .	1387
9.11.5.93 SLQSVoiceSetSUPSCallBack . . . . .	1388
9.11.5.94 SLQSVoiceSetSUPSNotificationCallback . . . . .	1389
9.11.5.95 SLQSWmsAsyncRawSendCallBack . . . . .	1389
9.11.5.96 SLQSWmsMemoryFullCallBack . . . . .	1390
9.11.5.97 SLQSWmsMessageWaitingCallBack . . . . .	1390
9.12 qaGobiApiDcs.h File Reference . . . . .	1391
9.12.1 Detailed Description . . . . .	1391
9.12.2 Macro Definition Documentation . . . . .	1391

9.12.2.1	LEN	1391
9.12.2.2	PORTNAM_LEN	1391
9.12.3	Function Documentation	1392
9.12.3.1	QCWWAN2kConnect	1392
9.12.3.2	QCWWAN2kEnumerateDevices	1393
9.12.3.3	QCWWAN2kGetConnectedDeviceID	1393
9.12.3.4	QCWWANConnect	1394
9.12.3.5	QCWWANDisconnect	1394
9.12.3.6	QCWWANEnumerateDevices	1394
9.12.3.7	SetSDKImagePath	1395
9.12.3.8	SLQSGetDeviceMode	1395
9.12.3.9	SLQSGetNetStatistic	1396
9.12.3.10	SLQSGetUsbPortNames	1396
9.12.3.11	SLQSKillSDKProcess	1396
9.12.3.12	SLQSQosClearMap	1397
9.12.3.13	SLQSQosDumpMap	1397
9.12.3.14	SLQSQosEditMap	1398
9.12.3.15	SLQSQosMap	1398
9.12.3.16	SLQSQosReadMap	1398
9.12.3.17	SLQSQosUnmap	1399
9.12.3.18	SLQSSetLoggingMask	1399
9.12.3.19	SLQSStart	1399
9.12.3.20	SLQSStart_AVAgent	1400
9.12.3.21	SLQSStartSrv	1400
9.13	qaGobiApiDms.h File Reference	1401
9.13.1	Detailed Description	1404
9.13.2	Macro Definition Documentation	1404
9.13.2.1	IMGDETAILS_LEN	1404
9.13.2.2	MAX_BUILD_ID_LEN	1404
9.13.2.3	MAX_CUST_ID_LEN	1404
9.13.2.4	MAX_CUST_VALUE_LEN	1404
9.13.2.5	MAX_DYING_GASP_CFG_SMS_CONTENT_LENGTH	1404
9.13.2.6	MAX_DYING_GASP_CFG_SMS_NUMBER_LENGTH	1404
9.13.2.7	MAX_FSN_LENGTH	1404
9.13.2.8	UNIQUE_ID_LEN	1404
9.13.3	Typedef Documentation	1404
9.13.3.1	custFeaturesInfo	1404
9.13.3.2	custFeaturesSetting	1406
9.13.3.3	dmsCurrentPRLInfo	1408
9.13.3.4	ERIFileparams	1408

9.13.3.5	<a href="#">serialNumbersInfo</a>	1408
9.13.3.6	<a href="#">SLQSSwiGetHostDevInfoParams</a>	1409
9.13.3.7	<a href="#">SLQSSwiGetOSInfoParams</a>	1410
9.13.3.8	<a href="#">SLQSSwiGetSerialNoExtParams</a>	1410
9.13.3.9	<a href="#">SLQSSwiSetHostDevInfoParams</a>	1411
9.13.3.10	<a href="#">SLQSSwiSetOSInfoParams</a>	1411
9.13.4	<a href="#">Function Documentation</a>	1412
9.13.4.1	<a href="#">ActivateAutomatic</a>	1412
9.13.4.2	<a href="#">GetActivationState</a>	1412
9.13.4.3	<a href="#">GetDeviceCapabilities</a>	1413
9.13.4.4	<a href="#">GetFirmwareRevision</a>	1414
9.13.4.5	<a href="#">GetFirmwareRevisions</a>	1415
9.13.4.6	<a href="#">GetHardwareRevision</a>	1416
9.13.4.7	<a href="#">GetIMSI</a>	1417
9.13.4.8	<a href="#">GetManufacturer</a>	1417
9.13.4.9	<a href="#">GetModelID</a>	1418
9.13.4.10	<a href="#">GetNetworkTime</a>	1418
9.13.4.11	<a href="#">GetOfflineReason</a>	1419
9.13.4.12	<a href="#">GetPower</a>	1420
9.13.4.13	<a href="#">GetPRLVersion</a>	1420
9.13.4.14	<a href="#">GetSerialNumbers</a>	1421
9.13.4.15	<a href="#">GetVoiceNumber</a>	1422
9.13.4.16	<a href="#">ResetToFactoryDefaults</a>	1422
9.13.4.17	<a href="#">SetPower</a>	1423
9.13.4.18	<a href="#">SLQSDmsSwiGetResetInfo</a>	1423
9.13.4.19	<a href="#">SLQSDmsSwiIndicationRegister</a>	1423
9.13.4.20	<a href="#">SLQSGetBandCapabilities</a>	1424
9.13.4.21	<a href="#">SLQSGetBandCapability</a>	1424
9.13.4.22	<a href="#">SLQSGetCurrentPRLInfo</a>	1426
9.13.4.23	<a href="#">SLQSGetCustFeatures</a>	1426
9.13.4.24	<a href="#">SLQSGetCustFeaturesV2</a>	1427
9.13.4.25	<a href="#">SLQSGetERIFile</a>	1427
9.13.4.26	<a href="#">SLQSGetSerialNumbers</a>	1427
9.13.4.27	<a href="#">SLQSSetCustFeatures</a>	1428
9.13.4.28	<a href="#">SLQSSetCustFeaturesV2</a>	1428
9.13.4.29	<a href="#">SLQSSwiClearDyingGaspStatistics</a>	1429
9.13.4.30	<a href="#">SLQSSwiGetCrashAction</a>	1429
9.13.4.31	<a href="#">SLQSSwiGetCrashInfo</a>	1429
9.13.4.32	<a href="#">SLQSSwiGetDyingGaspCfg</a>	1430
9.13.4.33	<a href="#">SLQSSwiGetDyingGaspStatistics</a>	1430

9.13.4.34 SLQSSwiGetFirmwareCurr	1430
9.13.4.35 SLQSSwiGetFSN	1431
9.13.4.36 SLQSSwiGetFwUpdateStatus	1431
9.13.4.37 SLQSSwiGetHostDevInfo	1431
9.13.4.38 SLQSSwiGetOSInfo	1432
9.13.4.39 SLQSSwiGetSerialNoExt	1432
9.13.4.40 SLQSSwiGetUSBComp	1433
9.13.4.41 SLQSSwiSetCrashAction	1433
9.13.4.42 SLQSSwiSetDyingGaspCfg	1434
9.13.4.43 SLQSSwiSetHostDevInfo	1434
9.13.4.44 SLQSSwiSetOSInfo	1434
9.13.4.45 SLQSSwiSetUSBComp	1435
9.13.4.46 SLQSUIMGetState	1435
9.13.4.47 UIMChangePIN	1436
9.13.4.48 UIMGetControlKeyStatus	1437
9.13.4.49 UIMGetICCID	1438
9.13.4.50 UIMGetPINStatus	1439
9.13.4.51 UIMSetControlKeyProtection	1440
9.13.4.52 UIMSetPINProtection	1441
9.13.4.53 UIMUnblockControlKey	1442
9.13.4.54 UIMUnblockPIN	1443
9.13.4.55 UIMVerifyPIN	1444
9.13.4.56 ValidateSPC	1445
9.14 qaGobiApiFms.h File Reference	1446
9.14.1 Detailed Description	1448
9.14.2 Macro Definition Documentation	1448
9.14.2.1 BUILD_ID_LEN	1448
9.14.2.2 DEVICE_OFFLINE	1448
9.14.2.3 DEVICE_RESET	1448
9.14.2.4 DEVICE_SHUTDOWN	1448
9.14.2.5 FIRMWARE_UPDATE_FAIL	1448
9.14.2.6 FIRMWARE_UPDATE_SUCCESS	1449
9.14.2.7 FIRMWARE_UPGRADE_SUCCESS	1449
9.14.2.8 GOBI_LISTENTRIES_MAX	1449
9.14.2.9 GOBI_MBN_BUILD_ID_STR_LEN	1449
9.14.2.10 GOBI_MBN_IMG_ID_STR_LEN	1449
9.14.2.11 GOBI_SET_IMG_PREF_RSPLEN	1449
9.14.2.12 IMG_ID_LEN	1449
9.14.2.13 PRI_UPDATE_FAIL	1449
9.14.2.14 SLQSFWINFO_APPVERSION_SZ	1449

9.14.2.15	SLQSFWINFO_BOOTVERSION_SZ	1449
9.14.2.16	SLQSFWINFO_CARRIER_SZ	1449
9.14.2.17	SLQSFWINFO_CUR_CARR_NAME	1449
9.14.2.18	SLQSFWINFO_CUR_CARR_REV	1449
9.14.2.19	SLQSFWINFO_MODELID_SZ	1449
9.14.2.20	SLQSFWINFO_PACKAGEID_SZ	1449
9.14.2.21	SLQSFWINFO_PRIVERSION_SZ	1449
9.14.2.22	SLQSFWINFO_SKU_SZ	1449
9.14.3	Enumeration Type Documentation	1449
9.14.3.1	eGobiDeviceSeries	1449
9.14.3.2	eGobiImageCarrier	1449
9.14.3.3	eGobiImageGPS	1451
9.14.3.4	eGobiImageRegion	1451
9.14.3.5	eGobiImageTech	1451
9.14.4	Function Documentation	1451
9.14.4.1	DeleteStoredImage	1451
9.14.4.2	eGetDeviceSeries	1452
9.14.4.3	GetImagesPreference	1452
9.14.4.4	GetImageStore	1452
9.14.4.5	GetStoredImages	1453
9.14.4.6	SetImagesPreference	1453
9.14.4.7	SLQSDownloadFirmwareToSlot	1454
9.14.4.8	SLQSGetBootVersionNumber	1455
9.14.4.9	SLQSGetFirmwareInfo	1456
9.14.4.10	SLQSGetImageInfo	1456
9.14.4.11	SLQSGetImageInfo_9x15	1457
9.14.4.12	SLQSGetImageInfoMC77xx	1457
9.14.4.13	SLQSGetImageInfoMC83xx	1458
9.14.4.14	SLQSGetValidFwPriCombinations	1458
9.14.4.15	SLQSIspkgFormatRequired	1459
9.14.4.16	SLQSSwiGetAllCarrierImages	1459
9.14.4.17	SLQSUgradeFirmware9x15	1460
9.14.4.18	upgrade_mc77xx_fw	1461
9.14.4.19	UpgradeFirmware2k	1461
9.15	qaGobiApilms.h File Reference	1461
9.15.1	Detailed Description	1462
9.15.2	Function Documentation	1462
9.15.2.1	SLQSGetIMSSMSConfig	1462
9.15.2.2	SLQSGetIMSUserConfig	1463
9.15.2.3	SLQSGetIMSVoIPConfig	1463

9.15.2.4	SLQSGetRegMgrConfig	1463
9.15.2.5	SLQSGetSIPConfig	1464
9.15.2.6	SLQSImsConfigIndicationRegister	1464
9.15.2.7	SLQSSetIMSSMSConfig	1465
9.15.2.8	SLQSSetIMSUserConfig	1465
9.15.2.9	SLQSSetIMSVoIPConfig	1466
9.15.2.10	SLQSSetRegMgrConfig	1466
9.15.2.11	SLQSSetSIPConfig	1467
9.16	qaGobiApilmsa.h File Reference	1467
9.16.1	Detailed Description	1468
9.16.2	Function Documentation	1468
9.16.2.1	SLQSGetIMSARegStatus	1468
9.16.2.2	SLQSGetIMSAServiceStatus	1468
9.16.2.3	SLQSGetIMSASupportedFields	1469
9.16.2.4	SLQSGetIMSASupportedMsg	1469
9.16.2.5	SLQSRegisterIMSIndication	1470
9.17	qaGobiApiLoc.h File Reference	1470
9.17.1	Detailed Description	1471
9.17.2	Macro Definition Documentation	1472
9.17.2.1	MAX_SENSOR_DATA_LEN	1472
9.17.2.2	MAX_TEMP_DATA_LEN	1472
9.17.3	Function Documentation	1472
9.17.3.1	SLQSLOCDeAssData	1472
9.17.3.2	SLQSLOCEventRegister	1472
9.17.3.3	SLQSLOCInjectPosition	1472
9.17.3.4	SLQSLOCInjectSensorData	1473
9.17.3.5	SLQSLOCInjectUTCTime	1473
9.17.3.6	SLQSLOCSetCradleMountConfig	1474
9.17.3.7	SLQSLOCSetExtPowerState	1474
9.17.3.8	SLQSLOCSetOpMode	1474
9.17.3.9	SLQSLOCStart	1475
9.17.3.10	SLQSLOCStop	1475
9.17.3.11	SwiLocGetAutoStart	1476
9.17.3.12	SwiLocSetAutoStart	1476
9.18	qaGobiApiNas.h File Reference	1477
9.18.1	Detailed Description	1482
9.18.2	Macro Definition Documentation	1482
9.18.2.1	IMSI_M_S1_LENGTH	1482
9.18.2.2	IMSI_M_S2_LENGTH	1482
9.18.2.3	MAX_DATA_SRV_CAPABILITIES	1482

9.18.2.4	MAX_DESCRIPTION_LENGTH	1482
9.18.2.5	MAX_PILOT_SETS	1482
9.18.2.6	MAX_SERV_SYSTEM_RADIO_INTERFACES	1482
9.18.2.7	NAM_NAME_LENGTH	1482
9.18.2.8	NAS_SIG_INFO_MAX_TDSCDMA_THRESHOLDS_LIST_SIZE	1482
9.18.2.9	NAS_SIG_INFO_MIN_dB_FLOAT_VALUE	1482
9.18.2.10	NAS_SIG_INFO_MIN_dBm_FLOAT_VALUE	1482
9.18.2.11	PLMN_LENGTH	1482
9.18.2.12	SLQS_SS_INFO_LIST_MAX_ELEMENTS	1482
9.18.2.13	SLQS_SYSTEM_ID_SIZE	1482
9.18.2.14	UATISIZE	1482
9.18.3	Typedef Documentation	1482
9.18.3.1	SlqsNas3GppNetworkRAT	1482
9.18.3.2	slqsNetworkScanInfo	1483
9.18.3.3	sysSelectPrefInfo	1484
9.18.3.4	sysSelectPrefParams	1487
9.18.4	Enumeration Type Documentation	1492
9.18.4.1	_NAMS_RADIO_IF_TECHNOLOGY_	1492
9.18.4.2	eSYS_SRV_DOMAIN	1492
9.18.4.3	NAS_LTE_CPHY_CA_BW_NRB	1492
9.18.4.4	NAS_LTE_CPHY_SCELL_STATE	1493
9.18.5	Function Documentation	1493
9.18.5.1	GetACCOLC	1493
9.18.5.2	GetANAAAAAuthenticationStatus	1493
9.18.5.3	GetCDMANetworkParameters	1494
9.18.5.4	GetHomeNetwork	1496
9.18.5.5	GetHomeNetwork3GPP2	1497
9.18.5.6	GetNetworkPreference	1498
9.18.5.7	GetRFInfo	1499
9.18.5.8	GetServingNetwork	1500
9.18.5.9	GetServingNetworkCapabilities	1502
9.18.5.10	GetSignalStrengths	1503
9.18.5.11	InitiateDomainAttach	1503
9.18.5.12	InitiateNetworkRegistration	1504
9.18.5.13	PerformNetworkScan	1505
9.18.5.14	SetACCOLC	1505
9.18.5.15	SetCDMANetworkParameters	1506
9.18.5.16	SetNetworkPreference	1508
9.18.5.17	SLQSConfigSigInfo	1508
9.18.5.18	SLQSGetErrorRate	1509



9.18.5.19 SLQSGetNetworkTime . . . . .	1509
9.18.5.20 SLQSGetOperatorNameData . . . . .	1510
9.18.5.21 SLQSGetPLMNName . . . . .	1510
9.18.5.22 SLQSGetServingSystem . . . . .	1511
9.18.5.23 SLQSGetSignalStrength . . . . .	1511
9.18.5.24 SLQSGetSysSelectionPref . . . . .	1511
9.18.5.25 SLQSIInitiateNetworkRegistration . . . . .	1512
9.18.5.26 SLQSNasConfigSigInfo2 . . . . .	1512
9.18.5.27 SLQSNasGet3GPP2Subscription . . . . .	1513
9.18.5.28 SLQSNasGetCellLocationInfo . . . . .	1513
9.18.5.29 SLQSNasGetHDRColorCode . . . . .	1514
9.18.5.30 SLQSNASGetLTECPHYCaInfo . . . . .	1514
9.18.5.31 SLQSNasGetSigInfo . . . . .	1514
9.18.5.32 SLQSNasGetSysInfo . . . . .	1515
9.18.5.33 SLQSNasGetTxRxInfo . . . . .	1515
9.18.5.34 SLQSNasIndicationRegister . . . . .	1516
9.18.5.35 SLQSNasIndicationRegisterExt . . . . .	1517
9.18.5.36 SLQSNasIndicationRegisterLTCphyCa . . . . .	1518
9.18.5.37 SLQSNASSwiGetChannelLock . . . . .	1518
9.18.5.38 SLQSNasSwiIndicationRegister . . . . .	1519
9.18.5.39 SLQSNasSwiModemStatus . . . . .	1519
9.18.5.40 SLQSNASSwiSetChannelLock . . . . .	1519
9.18.5.41 SLQSPerformNetworkScan . . . . .	1520
9.18.5.42 SLQSSetBandPreference . . . . .	1520
9.18.5.43 SLQSSetSysSelectionPref . . . . .	1522
9.18.5.44 SLQSSwiGetHDRPersonality . . . . .	1522
9.18.5.45 SLQSSwiGetHDRProtSubtype . . . . .	1522
9.18.5.46 SLQSSwiGetHRPDStats . . . . .	1523
9.18.5.47 SLQSSwiGetLteCQI . . . . .	1523
9.18.5.48 SLQSSwiNetworkDebug . . . . .	1524
9.18.5.49 SLQSSwiPSDetach . . . . .	1524
9.19 qaGobiApiOadm.h File Reference . . . . .	1524
9.19.1 Detailed Description . . . . .	1525
9.19.2 Function Documentation . . . . .	1525
9.19.2.1 OMADMCancelSession . . . . .	1525
9.19.2.2 OMADMGetPendingNIA . . . . .	1525
9.19.2.3 OMADMGetSessionInfo . . . . .	1526
9.19.2.4 OMADMStartSession . . . . .	1527
9.20 qaGobiApiPds.h File Reference . . . . .	1528
9.20.1 Detailed Description . . . . .	1529

9.20.2	Macro Definition Documentation	1529
9.20.2.1	DEFAULTBYTEVALUE	1529
9.20.2.2	DEFAULTLONGVALUE	1529
9.20.2.3	DEFAULTWORDVALUE	1529
9.20.3	Enumeration Type Documentation	1529
9.20.3.1	anonymous enum	1529
9.20.4	Function Documentation	1529
9.20.4.1	ForceXTRADownload	1529
9.20.4.2	GetPDSDetails	1530
9.20.4.3	GetPDSSState	1530
9.20.4.4	GetPortAutomaticTracking	1531
9.20.4.5	GetServiceAutomaticTracking	1532
9.20.4.6	GetXTRAAutomaticDownload	1533
9.20.4.7	GetXTRANetwork	1533
9.20.4.8	GetXTRAValidity	1534
9.20.4.9	PDSInjectTimeReference	1534
9.20.4.10	ResetPDSDData	1535
9.20.4.11	SetPDSDetails	1536
9.20.4.12	SetPDSSState	1537
9.20.4.13	SetPortAutomaticTracking	1537
9.20.4.14	SetServiceAutomaticTracking	1538
9.20.4.15	SetXTRAAutomaticDownload	1538
9.20.4.16	SetXTRANetwork	1539
9.20.4.17	SLQSGetAGPSConfig	1539
9.20.4.18	SLQSGetGPSSStateInfo	1540
9.20.4.19	SLQSPDSDeterminePosition	1541
9.20.4.20	SLQSPDSInjectAbsoluteTimeReference	1541
9.20.4.21	SLQSPDSInjectPositionData	1541
9.20.4.22	SLQSSetAGPSConfig	1542
9.20.4.23	SLQSSetPositionMethodState	1543
9.20.4.24	StartPDSTrackingSessionExt	1544
9.20.4.25	StopPDSTrackingSession	1545
9.21	qaGobiApiQos.h File Reference	1545
9.21.1	Detailed Description	1546
9.21.2	Macro Definition Documentation	1546
9.21.2.1	MAX_QOS_FILTER_TLV	1546
9.21.2.2	MAX_QOS_SPEC_PER_APN	1546
9.21.3	Function Documentation	1546
9.21.3.1	SLQSQosGetFlowStatus	1546
9.21.3.2	SLQSQosGetGranted	1547

9.21.3.3	SLQSQosGetNetworkStatus	1547
9.21.3.4	SLQSQosGetNWProf	1548
9.21.3.5	SLQSQosModify	1548
9.21.3.6	SLQSQosRel	1549
9.21.3.7	SLQSQosReq	1549
9.21.3.8	SLQSQosReset	1550
9.21.3.9	SLQSQosResume	1550
9.21.3.10	SLQSQosSuspend	1551
9.21.3.11	SLQSQosSwiReadApnExtraParams	1551
9.21.3.12	SLQSQosSwiReadDataStats	1552
9.22	qaGobiApiRms.h File Reference	1552
9.22.1	Detailed Description	1552
9.22.2	Function Documentation	1552
9.22.2.1	GetSMSWake	1552
9.22.2.2	SetSMSWake	1553
9.23	qaGobiApiSar.h File Reference	1554
9.23.1	Detailed Description	1554
9.23.2	Enumeration Type Documentation	1554
9.23.2.1	eQMISARRFState	1554
9.23.3	Function Documentation	1555
9.23.3.1	SLQSGetRfSarState	1555
9.23.3.2	SLQSSetRfSarState	1555
9.24	qaGobiApiSms.h File Reference	1556
9.24.1	Detailed Description	1558
9.24.2	Macro Definition Documentation	1558
9.24.2.1	ABSOLUTE_VALIDITY	1558
9.24.2.2	CONFIG_LEN	1558
9.24.2.3	MAX_SMS_ROUTES	1558
9.24.2.4	NUM_OF_SET	1558
9.24.2.5	TIME_DATE_BUF	1558
9.24.2.6	TIME_STAMP_BUF	1558
9.24.3	Typedef Documentation	1558
9.24.3.1	getIndicationRegResp	1558
9.24.3.2	getTransLayerInfoResp	1559
9.24.3.3	getTransNWRegInfoResp	1560
9.24.3.4	qaQmi3GPP2BroadcastCfgInfo	1560
9.24.3.5	qaQmi3GPPBroadcastCfgInfo	1561
9.24.3.6	setIndicationRegReq	1561
9.24.3.7	transLayerInfo	1562
9.24.4	Function Documentation	1563

9.24.4.1	GetSMSCAddress	1563
9.24.4.2	SaveSMS	1563
9.24.4.3	SendSMS	1564
9.24.4.4	SetSMSCAddress	1565
9.24.4.5	SLQSCDMADecodeMTTextMsg	1566
9.24.4.6	SLQSCDMAEncodeMOTextMsg	1566
9.24.4.7	SLQSDeleteSMS	1567
9.24.4.8	SLQSGetIndicationRegister	1568
9.24.4.9	SLQSGetMessageWaiting	1569
9.24.4.10	SLQSGetSMS	1569
9.24.4.11	SLQSGetSmsBroadcastConfig	1570
9.24.4.12	SLQSGetSMSList	1571
9.24.4.13	SLQSGetTransLayerInfo	1572
9.24.4.14	SLQSGetTransNWRegInfo	1572
9.24.4.15	SLQSModifySMSStatus	1573
9.24.4.16	SLQSSendAsyncSMS	1574
9.24.4.17	SLQSSendLongSMS	1574
9.24.4.18	SLQSSendSMS	1575
9.24.4.19	SLQSSetIndicationRegister	1576
9.24.4.20	SLQSSetSmsBroadcastActivation	1576
9.24.4.21	SLQSSetSmsBroadcastConfig	1577
9.24.4.22	SLQSSetSmsStorage	1578
9.24.4.23	SLQSSmsGetMaxStorageSize	1578
9.24.4.24	SLQSSmsGetMessageProtocol	1579
9.24.4.25	SLQSSmsSetRoutes	1579
9.24.4.26	SLQSSwiGetSMSStorage	1580
9.24.4.27	SLQSWCDMADecodeLongTextMsg	1581
9.24.4.28	SLQSWCDMADecodeMTTextMsg	1581
9.24.4.29	SLQSWCDMAEncodeMOTextMsg	1582
9.25	qaGobiApiSwi.h File Reference	1582
9.25.1	Detailed Description	1583
9.25.2	Function Documentation	1583
9.25.2.1	SLQSGetPidof	1583
9.25.2.2	SLQSGetSdkVersion	1583
9.25.2.3	SLQSSendRawQMI	1583
9.26	qaGobiApiSwiAudio.h File Reference	1583
9.26.1	Detailed Description	1584
9.26.2	Macro Definition Documentation	1584
9.26.2.1	MAX_LEN_IFACE_TABLE	1584
9.26.3	Function Documentation	1584

9.26.3.1	SLQSGetM2MAudioProfile	1584
9.26.3.2	SLQSGetM2MAudioVolume	1585
9.26.3.3	SLQSGetM2MAVMute	1585
9.26.3.4	SLQSGetM2MSpkrGain	1586
9.26.3.5	SLQSSetM2MAudioAVCFG	1586
9.26.3.6	SLQSSetM2MAudioLPBK	1587
9.26.3.7	SLQSSetM2MAudioNVDef	1587
9.26.3.8	SLQSSetM2MAudioProfile	1587
9.26.3.9	SLQSSetM2MAudioVolume	1588
9.26.3.10	SLQSSetM2MAVMute	1588
9.26.3.11	SLQSSetM2MSpkrGain	1589
9.27	qaGobiApiSwiOmadms.h File Reference	1589
9.27.1	Detailed Description	1590
9.27.2	Typedef Documentation	1590
9.27.2.1	SLQSOMADMSessionInfo	1590
9.27.2.2	SLQSOMADMSettings	1592
9.27.2.3	SLQSOMADMSettingsReqParams	1593
9.27.2.4	SLQSOMADMSettingsReqParams3	1594
9.27.3	Function Documentation	1595
9.27.3.1	SLQSOMADMCancelSession	1595
9.27.3.2	SLQSOMADMGetSessionInfo	1595
9.27.3.3	SLQSOMADMGetSettings	1596
9.27.3.4	SLQSOMADMGetSettings2	1597
9.27.3.5	SLQSOMADMSendSelection	1597
9.27.3.6	SLQSOMADMSendSelection2	1598
9.27.3.7	SLQSOMADMSetSettings	1598
9.27.3.8	SLQSOMADMSetSettings2	1599
9.27.3.9	SLQSOMADMSetSettings3	1599
9.27.3.10	SLQSOMADMStartSession	1600
9.27.3.11	SLQSOMADMStartSession2	1600
9.28	qaGobiApiTableBandClasses.h File Reference	1601
9.28.1	Detailed Description	1601
9.28.2	Band Classes (Value - Description)	1601
9.28.2.1	LTE Bands	1603
9.29	qaGobiApiTableCallControlReturnReasons.h File Reference	1604
9.29.1	Detailed Description	1604
9.29.2	Call Control Result Reasons (Value - Name - Description)	1604
9.30	qaGobiApiTableCallEndReasons.h File Reference	1605
9.30.1	Detailed Description	1605
9.30.2	Call end reason codes (Code - Reason)	1605

9.30.2.1	Technology-agnostic call end reasons	1605
9.30.2.2	EVDO CDMA 1xEV-DO	1605
9.30.2.3	WCDMA/GSM call end reasons	1606
9.30.2.4	EVDO CDMA 1xEV-DO	1608
9.30.2.5	call end reason type	1609
9.30.2.6	Mobile IP call end reasons (Type=1)	1609
9.30.2.7	Internal call end reasons (Type=2)	1611
9.30.2.8	Call Manager defined call end reasons (Type=3)	1612
9.30.2.9	3GPP specification defined call end reasons (Type=6)	1617
9.30.2.10	PPP call end reasons (Type=7)	1619
9.30.2.11	EHRPD call end reasons (Type=8)	1619
9.30.2.12	IPv6 call end reasons (Type=9)	1620
9.31	qaGobiApiTableCarrierCodes.h File Reference	1620
9.31.1	Detailed Description	1620
9.31.2	Carrier Codes (Number - Carrier)	1620
9.32	qaGobiApiTableCodingScheme.h File Reference	1622
9.32.1	Detailed Description	1622
9.32.2	Call Control Result Reasons (Value - Name - Description)	1622
9.32.2.1	Use of bits 3..0	1622
9.32.3	Coding Group Bits 7..4(0001)	1623
9.32.3.1	use of bits 3..0	1623
9.32.4	Coding Group Bits 7..4(0010)	1623
9.32.4.1	use of bits 3..0	1623
9.32.5	Coding Group Bits 7..4(0011)	1623
9.32.5.1	use of bits 3..0	1623
9.32.6	Coding Group Bits 7..4(01xx)	1624
9.32.6.1	use of bits 3..0	1624
9.32.7	Coding Group Bits 7..4(1001)	1624
9.32.7.1	Reserved coding groups	1624
9.32.8	Coding Group Bits 7..4(1010..1101)	1624
9.32.8.1	Reserved coding groups	1624
9.32.9	Coding Group Bits 7..4(1110)	1624
9.32.9.1	Defined by the WAP Forum	1624
9.32.10	Coding Group Bits 7..4 (1111)	1624
9.32.10.1	Data coding / message handling	1625
9.32.11	Macro Definition Documentation	1625
9.32.11.1	__GOBI_API_CODING_SCHEME_H__	1625
9.33	qaGobiApiTableGpsCapabilityCodes.h File Reference	1625
9.33.1	Detailed Description	1625
9.33.2	GPS capability (Value - Capability)	1625

9.34	qaGobiApiTablePowerModes.h File Reference	1625
9.34.1	Detailed Description	1625
9.34.2	Power Modes (Value - Description)	1626
9.35	qaGobiApiTableRadioInterfaces.h File Reference	1626
9.35.1	Detailed Description	1626
9.35.2	Radio interface	1626
9.35.2.1	Technology (Value - Radio Interface Technology)	1626
9.36	qaGobiApiTableRegionCodes.h File Reference	1626
9.36.1	Detailed Description	1627
9.36.2	Region Codes (Code - Region)	1627
9.37	qaGobiApiTableServiceOptions.h File Reference	1627
9.37.1	Detailed Description	1627
9.37.2	Service Option codes (Code - Reason)	1627
9.37.2.1	Description	1627
9.38	qaGobiApiTableSupServiceInfoClasses.h File Reference	1629
9.38.1	Detailed Description	1629
9.38.2	Supplementary Service Information Classes (Value - Service Class)	1630
9.39	qaGobiApiTableSwiAudio.h File Reference	1630
9.39.1	Detailed Description	1630
9.39.2	ACDB Device (Device ID - description)	1630
9.39.3	Physical Interface (Device ID - description - Interface parameters)	1630
9.40	qaGobiApiTableSwiOMADMUpdateCompleteStatus.h File Reference	1630
9.40.1	Detailed Description	1631
9.40.2	OMA DM Update Complete Status (Update Complete Status - Meaning - Usage)	1631
9.41	qaGobiApiTableVoiceCallEndReasons.h File Reference	1632
9.41.1	Detailed Description	1632
9.41.2	Voice Call and supplementary services end reason codes (Code - Reason)	1632
9.41.2.1	General	1632
9.41.2.2	service Errors	1634
9.41.2.3	control cause values	1635
9.41.2.4	reject causes	1636
9.41.2.5	reject causes	1637
9.41.2.6	reject causes	1637
9.41.2.7	stratum reject causes	1637
9.41.2.8	reject causes	1638
9.41.2.9	IP end reasons	1638
9.42	qaGobiApiTmd.h File Reference	1638
9.42.1	Detailed Description	1639
9.42.2	Macro Definition Documentation	1639
9.42.2.1	MAX_MITIGATION_DEV_ID_LEN	1639

9.42.2.2	MAX_MITIGATION_DEV_LIST_LEN	1639
9.42.3	Function Documentation	1639
9.42.3.1	SLQSTmdDeRegNotMitigationLvl	1639
9.42.3.2	SLQSTmdGetMitigationDevList	1639
9.42.3.3	SLQSTmdGetMitigationLvl	1640
9.42.3.4	SLQSTmdRegNotMitigationLvl	1640
9.43	qaGobiApiUim.h File Reference	1640
9.43.1	Detailed Description	1642
9.43.2	Macro Definition Documentation	1643
9.43.2.1	MAX_ACTIVE_PERS_FEATURES	1643
9.43.2.2	MAX_CONTENT_LENGTH	1643
9.43.2.3	MAX_DESCRIPTION_LENGTH	1643
9.43.2.4	MAX_ICCID_LENGTH	1643
9.43.2.5	MAX_NO_OF_APPLICATIONS	1643
9.43.2.6	MAX_NO_OF_SLOTS	1643
9.43.2.7	MAX_PATH_LENGTH	1643
9.43.2.8	MAX_PUK_LENGTH	1643
9.43.2.9	MAX_SLOTS_STATUS	1643
9.43.3	Function Documentation	1643
9.43.3.1	SLQSUIMAuthenticate	1643
9.43.3.2	SLQSUIMChangePin	1643
9.43.3.3	SLQSUIMDepersonalization	1644
9.43.3.4	SLQSUIMEventRegister	1645
9.43.3.5	SLQSUIMGetCardStatus	1646
9.43.3.6	SLQSUIMGetConfiguration	1646
9.43.3.7	SLQSUIMGetFileAttributes	1647
9.43.3.8	SLQSUIMGetSlotsStatus	1647
9.43.3.9	SLQSUIMPowerDown	1648
9.43.3.10	SLQSUIMPowerUp	1648
9.43.3.11	SLQSUIMReadTransparent	1649
9.43.3.12	SLQSUIMRefreshComplete	1649
9.43.3.13	SLQSUIMRefreshGetLastEvent	1650
9.43.3.14	SLQSUIMRefreshOK	1650
9.43.3.15	SLQSUIMRefreshRegister	1651
9.43.3.16	SLQSUIMReset	1651
9.43.3.17	SLQSUIMSetPinProtection	1652
9.43.3.18	SLQSUIMSwitchSlot	1652
9.43.3.19	SLQSUIMUnblockPin	1653
9.43.3.20	SLQSUIMVerifyPin	1653
9.44	qaGobiApiVoice.h File Reference	1654



9.44.1	Detailed Description	1657
9.44.2	Macro Definition Documentation	1657
9.44.2.1	MAX_CALL_NO_LEN	1657
9.44.2.2	MAX_DESCRIPTION_LENGTH	1657
9.44.2.3	MAX_NO_OF_CALLS	1657
9.44.2.4	MAXUSSDLENGTH	1657
9.44.2.5	PASSWORD_LENGTH	1657
9.44.3	Enumeration Type Documentation	1657
9.44.3.1	serviceClassInformation	1657
9.44.4	Function Documentation	1658
9.44.4.1	AnswerUSSD	1658
9.44.4.2	CancelUSSD	1658
9.44.4.3	OriginateUSSD	1658
9.44.4.4	SLQSOrginateUSSD	1659
9.44.4.5	SLQSVoiceALSSelectLine	1659
9.44.4.6	SLQSVoiceALSSetLineSwitching	1660
9.44.4.7	SLQSVoiceAnswerCall	1660
9.44.4.8	SLQSVoiceBindSubscription	1661
9.44.4.9	SLQSVoiceBurstDTMF	1661
9.44.4.10	SLQSVoiceDialCall	1662
9.44.4.11	SLQSVoiceEndCall	1663
9.44.4.12	SLQSVoiceGetAllCallInfo	1664
9.44.4.13	SLQSVoiceGetCallBarring	1664
9.44.4.14	SLQSVoiceGetCallForwardingStatus	1665
9.44.4.15	SLQSVoiceGetCallInfo	1666
9.44.4.16	SLQSVoiceGetCallWaiting	1666
9.44.4.17	SLQSVoiceGetCLIP	1667
9.44.4.18	SLQSVoiceGetCLIR	1667
9.44.4.19	SLQSVoiceGetCNAP	1668
9.44.4.20	SLQSVoiceGetCOLP	1668
9.44.4.21	SLQSVoiceGetCOLR	1669
9.44.4.22	SLQSVoiceGetConfig	1670
9.44.4.23	SLQSVoiceIndicationRegister	1671
9.44.4.24	SLQSVoiceManageCalls	1672
9.44.4.25	SLQSVoiceOrigUSSDNoWait	1672
9.44.4.26	SLQSVoiceSendFlash	1673
9.44.4.27	SLQSVoiceSetCallBarringPassword	1674
9.44.4.28	SLQSVoiceSetConfig	1675
9.44.4.29	SLQSVoiceSetPreferredPrivacy	1676
9.44.4.30	SLQSVoiceSetSUPSService	1677

9.44.4.31	SLQSVoiceStartContDTMF	1678
9.44.4.32	SLQSVoiceStopContDTMF	1679
9.45	qaGobiApiWds.h File Reference	1680
9.45.1	Detailed Description	1684
9.45.2	Macro Definition Documentation	1684
9.45.2.1	IPV6_ADDRESS_ARRAY_SIZE	1684
9.45.3	Typedef Documentation	1684
9.45.3.1	GetProfileSettingIn	1684
9.45.3.2	GetProfileSettingOut	1684
9.45.3.3	QmiProfileInfo	1684
9.45.3.4	QmiWDSDataBearers	1685
9.45.3.5	QmiWDSDataBearerTechnology	1686
9.45.3.6	slqs3GPPConfigItem	1688
9.45.4	Enumeration Type Documentation	1689
9.45.4.1	qmiDataBearerMasks	1689
9.45.5	Function Documentation	1689
9.45.5.1	GetAutoconnect	1689
9.45.5.2	GetByteTotals	1690
9.45.5.3	GetConnectionRate	1690
9.45.5.4	GetDataBearerTechnology	1691
9.45.5.5	GetDefaultProfile	1692
9.45.5.6	GetDefaultProfileLTE	1694
9.45.5.7	GetDefaultProfileNum	1696
9.45.5.8	GetDormancyState	1697
9.45.5.9	GetIPAddressLTE	1697
9.45.5.10	GetLastMobileIPError	1698
9.45.5.11	GetMobileIP	1698
9.45.5.12	GetMobileIPProfile	1699
9.45.5.13	GetPacketStatistics	1700
9.45.5.14	GetPacketStatus	1701
9.45.5.15	GetSessionDuration	1702
9.45.5.16	GetSessionState	1702
9.45.5.17	iGetByteTotals	1703
9.45.5.18	iGetConnectionRate	1703
9.45.5.19	iGetPacketStatistics	1703
9.45.5.20	iSLQSMISetIPFamilyPreference	1703
9.45.5.21	RMSetTransferStatistics	1703
9.45.5.22	SetActiveMobileIPProfile	1704
9.45.5.23	SetAutoconnect	1705
9.45.5.24	SetDefaultProfile	1705

9.45.5.25 SetDefaultProfileLTE . . . . .	1707
9.45.5.26 SetDefaultProfileLTEV2 . . . . .	1709
9.45.5.27 SetDefaultProfileNum . . . . .	1711
9.45.5.28 SetMobileIP . . . . .	1711
9.45.5.29 SetMobileIPParameters . . . . .	1712
9.45.5.30 SetMobileIPProfile . . . . .	1713
9.45.5.31 SLQSAutoConnect . . . . .	1714
9.45.5.32 SLQSCreateProfile . . . . .	1715
9.45.5.33 SLQSDeleteProfile . . . . .	1715
9.45.5.34 SLQSGet3GPPConfigItem . . . . .	1716
9.45.5.35 SLQSGetByteTotals . . . . .	1716
9.45.5.36 SLQSGetConnectionRate . . . . .	1717
9.45.5.37 SLQSGetCurrDataSystemStat . . . . .	1717
9.45.5.38 SLQSGetCurrentChannelRate . . . . .	1718
9.45.5.39 SLQSGetDataBearerTechnology . . . . .	1719
9.45.5.40 SLQSGetDataBearerTechnologyExt . . . . .	1719
9.45.5.41 SLQSGetDUNCallInfo . . . . .	1720
9.45.5.42 SLQSGetPacketStatistics . . . . .	1720
9.45.5.43 SLQSGetProfile . . . . .	1721
9.45.5.44 SLQSGetProfileSettings . . . . .	1723
9.45.5.45 SLQSGetRuntimeSettings . . . . .	1723
9.45.5.46 SLQSGetSessionState . . . . .	1724
9.45.5.47 SLQSModifyProfile . . . . .	1724
9.45.5.48 SLQSResetPacketStatics . . . . .	1725
9.45.5.49 SLQSSet3GPPConfigItem . . . . .	1725
9.45.5.50 SLQSSetProfile . . . . .	1726
9.45.5.51 SLQSSetDHCPv4ClientConfig . . . . .	1728
9.45.5.52 SLQSSetLoopback . . . . .	1728
9.45.5.53 SLQSSetDHCPv4ClientConfig . . . . .	1729
9.45.5.54 SLQSSetLoopback . . . . .	1729
9.45.5.55 SLQSStartStopDataSession . . . . .	1729
9.45.5.56 SLQSWdsGoActive . . . . .	1730
9.45.5.57 SLQSWdsGoDormant . . . . .	1730
9.45.5.58 SLQSWdsSetEventReport . . . . .	1731
9.45.5.59 SLQSWdsSwiPDPRuntimeSettings . . . . .	1731
9.45.5.60 WDS_IsGobiDevice . . . . .	1732
9.46 qaNasGetRFBandInfo.h File Reference . . . . .	1732
9.46.1 Enumeration Type Documentation . . . . .	1732
9.46.1.1 eQMI_NAS_GET_RF_INFO_RESP . . . . .	1732
9.46.2 Function Documentation . . . . .	1732

9.46.2.1	PkQmiNasGetRFBandInfo . . . . .	1732
9.46.2.2	UpkQmiNasGetRFBandInfo . . . . .	1732
9.47	qaNasPerformNetworkScan.h File Reference . . . . .	1732
9.47.1	Macro Definition Documentation . . . . .	1733
9.47.1.1	FORBIDDEN_INDEX . . . . .	1733
9.47.1.2	INDEX_ZERO . . . . .	1733
9.47.1.3	MAX_DESCRIPTION_LENGTH . . . . .	1733
9.47.1.4	PREFERRED_INDEX . . . . .	1733
9.47.1.5	QMI_NAS_MAX_INSTANCES . . . . .	1733
9.47.1.6	QMI_NAS_NETSTATUS_MASK . . . . .	1733
9.47.1.7	ROAMING_INDEX . . . . .	1733
9.47.2	Enumeration Type Documentation . . . . .	1733
9.47.2.1	eQMI_NAS_PERFORM_NETWORK_SCAN_RESP . . . . .	1733
9.47.3	Function Documentation . . . . .	1733
9.47.3.1	PkQmiNasPerformNetworkScan . . . . .	1733
9.47.3.2	UpkQmiNasPerformNetworkScan . . . . .	1733
9.48	qmerrno.h File Reference . . . . .	1733
9.48.1	Enumeration Type Documentation . . . . .	1735
9.48.1.1	eQCWWANError . . . . .	1735
9.48.1.2	qm_wds_ds_profile_extended_err_codes . . . . .	1740
9.49	qos.h File Reference . . . . .	1740
9.49.1	Macro Definition Documentation . . . . .	1742
9.49.1.1	LIBPACK_MAX_QOS_FILTERS . . . . .	1742
9.49.1.2	LIBPACK_MAX_QOS_FLOW_PER_APN_STATS . . . . .	1742
9.49.1.3	LIBPACK_MAX_QOS_FLOWS . . . . .	1742
9.49.2	Function Documentation . . . . .	1742
9.49.2.1	pack_qos_SLQSQosGetNetworkStatus . . . . .	1742
9.49.2.2	pack_qos_SLQSQosSwiReadApnExtraParams . . . . .	1742
9.49.2.3	pack_qos_SLQSQosSwiReadDataStats . . . . .	1743
9.49.2.4	pack_qos_SLQSSetQosEventCallback . . . . .	1744
9.49.2.5	unpack_qos_SLQSQosGetNetworkStatus . . . . .	1745
9.49.2.6	unpack_qos_SLQSQosSwiReadApnExtraParams . . . . .	1746
9.49.2.7	unpack_qos_SLQSQosSwiReadDataStats . . . . .	1746
9.49.2.8	unpack_qos_SLQSSetQosEventCallback . . . . .	1747
9.49.2.9	unpack_qos_SLQSSetQosEventCallback_ind . . . . .	1747
9.49.2.10	unpack_qos_SLQSSetQosNWStatusCallback_ind . . . . .	1748
9.49.2.11	unpack_qos_SLQSSetQosPriEventCallback_ind . . . . .	1749
9.49.2.12	unpack_qos_SLQSSetQosStatusCallback_ind . . . . .	1750
9.50	sms.h File Reference . . . . .	1751
9.50.1	Macro Definition Documentation . . . . .	1752

9.50.1.1	MAX_CDMA_ENC_MO_TXT_MSG_SIZE	1752
9.50.1.2	MAX_MS_TRANSFER_ROUTE_MSG	1752
9.50.1.3	MAX_MSC_ADDRESS_SIZE	1752
9.50.1.4	MAX_MSE_TWS_MSG	1753
9.50.1.5	MAX_SMS_LIST_SIZE	1753
9.50.1.6	MAX_SMS_MESSAGE_SIZE	1753
9.50.2	Typedef Documentation	1753
9.50.2.1	sMSCAddressInfo	1753
9.50.2.2	sMSEtwsMessageInfo	1753
9.50.2.3	sMSEtwsPlmnInfo	1753
9.50.2.4	sMSMessageModelInfo	1753
9.50.2.5	sMSMTMessageInfo	1754
9.50.2.6	sMSOnIMSInfo	1754
9.50.2.7	sMSTransferRouteMTMessageInfo	1754
9.50.3	Enumeration Type Documentation	1754
9.50.3.1	eqmiCbKSetStatus	1754
9.50.4	Function Documentation	1754
9.50.4.1	pack_sms_SendSMS	1755
9.50.4.2	pack_sms_SetNewSMSCallback	1756
9.50.4.3	pack_sms_SLQSDDeleteSMS	1756
9.50.4.4	pack_sms_SLQSGetSMS	1756
9.50.4.5	pack_sms_SLQSGetSMSList	1757
9.50.4.6	pack_sms_SLQSModifySMSStatus	1757
9.50.4.7	unpack_sms_SendSMS	1757
9.50.4.8	unpack_sms_SetNewSMSCallback	1758
9.50.4.9	unpack_sms_SetNewSMSCallback_ind	1758
9.50.4.10	unpack_sms_SLQSDDeleteSMS	1758
9.50.4.11	unpack_sms_SLQSGetSMS	1759
9.50.4.12	unpack_sms_SLQSGetSMSList	1759
9.50.4.13	unpack_sms_SLQSModifySMSStatus	1759
9.50.4.14	unpack_sms_SLQSWmsMemoryFullCallBack_ind	1760
9.51	SwiDataTypes.h File Reference	1760
9.51.1	Detailed Description	1761
9.51.2	Macro Definition Documentation	1761
9.51.2.1	QMI_NO_LTE_FW_SUPPORT	1761
9.51.2.2	QMI_TLV_PLACEHOLDER	1761
9.51.2.3	SWI_API	1761
9.51.2.4	UNUSEDPARAM	1761
9.51.3	Typedef Documentation	1761
9.51.3.1	BOOL	1761

9.51.3.2	BYTE	1761
9.51.3.3	CHAR	1761
9.51.3.4	FLOAT	1761
9.51.3.5	INT32	1761
9.51.3.6	INT8	1761
9.51.3.7	LPCSTR	1761
9.51.3.8	SHORT	1761
9.51.3.9	ULONG	1761
9.51.3.10	ULONGLONG	1761
9.51.3.11	USHORT	1761
9.51.3.12	WORD	1761
9.52	swiloc.h File Reference	1761
9.52.1	Function Documentation	1762
9.52.1.1	pack_swiloc_SwiLocGetAutoStart	1762
9.52.1.2	pack_swiloc_SwiLocSetAutoStart	1762
9.52.1.3	unpack_swiloc_SwiLocGetAutoStart	1762
9.52.1.4	unpack_swiloc_SwiLocSetAutoStart	1763
9.53	swioma.h File Reference	1763
9.53.1	Macro Definition Documentation	1764
9.53.1.1	LIBPACK_MAX_SWIOMA_STR_LEN	1764
9.53.2	Function Documentation	1764
9.53.2.1	pack_swioma_SLQSOMADMAAlertCallback	1764
9.53.2.2	pack_swioma_SLQSOMADMCancelSession	1765
9.53.2.3	pack_swioma_SLQSOMADMGetSessionInfo	1765
9.53.2.4	pack_swioma_SLQSOMADMGetSettings	1766
9.53.2.5	pack_swioma_SLQSOMADMSendSelection	1767
9.53.2.6	pack_swioma_SLQSOMADMSetSettings	1767
9.53.2.7	pack_swioma_SLQSOMADMStartSession	1768
9.53.2.8	unpack_swioma_SLQSOMADMAAlertCallback	1769
9.53.2.9	unpack_swioma_SLQSOMADMAAlertCallback_ind	1769
9.53.2.10	unpack_swioma_SLQSOMADMCancelSession	1770
9.53.2.11	unpack_swioma_SLQSOMADMGetSessionInfo	1770
9.53.2.12	unpack_swioma_SLQSOMADMGetSettings	1771
9.53.2.13	unpack_swioma_SLQSOMADMSendSelection	1771
9.53.2.14	unpack_swioma_SLQSOMADMSetSettings	1772
9.53.2.15	unpack_swioma_SLQSOMADMStartSession	1772
9.54	SWIWWANCMAPI.h File Reference	1773
9.55	uim.h File Reference	1773
9.55.1	Macro Definition Documentation	1774
9.55.1.1	MAX_DESCRIPTION_LENGTH	1774

9.55.1.2	MAX_ICCID_LENGTH . . . . .	1774
9.55.1.3	MAX_NO_OF_APPLICATIONS . . . . .	1774
9.55.1.4	MAX_NO_OF_SLOTS . . . . .	1774
9.55.1.5	MAX_SLOTS_STATUS . . . . .	1774
9.55.1.6	UIM_MAX_DESCRIPTION_LENGTH . . . . .	1774
9.55.1.7	UIM_MAX_NO_OF_APPLICATIONS . . . . .	1774
9.55.1.8	UIM_MAX_NO_OF_SLOTS . . . . .	1774
9.55.1.9	UIM_UINT8_MAX_STRING_SZ . . . . .	1774
9.55.2	Function Documentation . . . . .	1775
9.55.2.1	pack_uim_ChangePin . . . . .	1775
9.55.2.2	pack_uim_GetCardStatus . . . . .	1775
9.55.2.3	pack_uim_ReadTransparent . . . . .	1775
9.55.2.4	pack_uim_SetPinProtection . . . . .	1776
9.55.2.5	pack_uim_SLQSUIEventRegister . . . . .	1776
9.55.2.6	pack_uim_SLQSUIGetSlotsStatus . . . . .	1776
9.55.2.7	pack_uim_SLQSUISSwitchSlot . . . . .	1777
9.55.2.8	pack_uim_UnblockPin . . . . .	1778
9.55.2.9	pack_uim_VerifyPin . . . . .	1778
9.55.2.10	unpack_uim_ChangePin . . . . .	1778
9.55.2.11	unpack_uim_GetCardStatus . . . . .	1779
9.55.2.12	unpack_uim_ReadTransparent . . . . .	1779
9.55.2.13	unpack_uim_SetPinProtection . . . . .	1779
9.55.2.14	unpack_uim_SetUimSlotStatusChangeCallback_ind . . . . .	1780
9.55.2.15	unpack_uim_SLQSUIEventRegister . . . . .	1780
9.55.2.16	unpack_uim_SLQSUIGetSlotsStatus . . . . .	1780
9.55.2.17	unpack_uim_SLQSUISetStatusChangeCallBack_ind . . . . .	1781
9.55.2.18	unpack_uim_SLQSUISSwitchSlot . . . . .	1781
9.55.2.19	unpack_uim_UnblockPin . . . . .	1781
9.55.2.20	unpack_uim_VerifyPin . . . . .	1782
9.56	wds.h File Reference . . . . .	1782
9.56.1	Macro Definition Documentation . . . . .	1786
9.56.1.1	IPV6_ADDRESS_ARRAY_SIZE . . . . .	1786
9.56.1.2	MAX_WDS_3GPP_CONF_LTE_ATTACH_PROFILE_LIST_SIZE . . . . .	1786
9.56.1.3	PACK_WDS_IPV4 . . . . .	1786
9.56.1.4	PACK_WDS_IPV6 . . . . .	1786
9.56.2	Typedef Documentation . . . . .	1786
9.56.2.1	UnpackQmiProfileInfo . . . . .	1786
9.56.3	Function Documentation . . . . .	1786
9.56.3.1	pack_wds_GetConnectionRate . . . . .	1786
9.56.3.2	pack_wds_GetDefaultProfile . . . . .	1787

9.56.3.3	pack_wds_GetDefaultProfileNum	1787
9.56.3.4	pack_wds_GetDormancyState	1788
9.56.3.5	pack_wds_GetLastMobileIPError	1789
9.56.3.6	pack_wds_GetMobileIP	1789
9.56.3.7	pack_wds_GetMobileIPProfile	1790
9.56.3.8	pack_wds_GetPacketStatus	1790
9.56.3.9	pack_wds_GetSessionDuration	1790
9.56.3.10	pack_wds_GetSessionState	1791
9.56.3.11	pack_wds_RMSetTransferStatistics	1791
9.56.3.12	pack_wds_SetDefaultProfile	1792
9.56.3.13	pack_wds_SetDefaultProfileNum	1793
9.56.3.14	pack_wds_SetMobileIPProfile	1793
9.56.3.15	pack_wds_SLQSCreateProfile	1794
9.56.3.16	pack_wds_SLQSDeleteProfile	1794
9.56.3.17	pack_wds_SLQSGet3GPPConfigItem	1794
9.56.3.18	pack_wds_SLQSGetCurrDataSystemStat	1795
9.56.3.19	pack_wds_SLQSGetDataBearerTechnology	1795
9.56.3.20	pack_wds_SLQSGetDUNCallInfo	1796
9.56.3.21	pack_wds_SLQSGetProfileSettings	1796
9.56.3.22	pack_wds_SLQSGetRuntimeSettings	1796
9.56.3.23	pack_wds_SLQSModifyProfile	1797
9.56.3.24	pack_wds_SLQSSet3GPPConfigItem	1797
9.56.3.25	pack_wds_SLQSSetIPFamilyPreference	1798
9.56.3.26	pack_wds_SLQSSetWdsEventCallback	1798
9.56.3.27	pack_wds_SLQSSetDHCPv4ClientConfig	1798
9.56.3.28	pack_wds_SLQSStartDataSession	1799
9.56.3.29	pack_wds_SLQSStopDataSession	1799
9.56.3.30	pack_wds_SLQSWdsSwiPDPRuntimeSettings	1800
9.56.3.31	unpack_wds_GetConnectionRate	1800
9.56.3.32	unpack_wds_GetDefaultProfile	1800
9.56.3.33	unpack_wds_GetDefaultProfileNum	1801
9.56.3.34	unpack_wds_GetDormancyState	1801
9.56.3.35	unpack_wds_GetLastMobileIPError	1801
9.56.3.36	unpack_wds_GetMobileIP	1802
9.56.3.37	unpack_wds_GetMobileIPProfile	1802
9.56.3.38	unpack_wds_GetPacketStatus	1802
9.56.3.39	unpack_wds_GetSessionDuration	1803
9.56.3.40	unpack_wds_GetSessionState	1803
9.56.3.41	unpack_wds_RMSetTransferStatistics	1803
9.56.3.42	unpack_wds_SetDefaultProfile	1804



9.56.3.43 unpack_wds_SetDefaultProfileNum . . . . .	1804
9.56.3.44 unpack_wds_SetMobileIPProfile . . . . .	1804
9.56.3.45 unpack_wds_SLQSCreateProfile . . . . .	1805
9.56.3.46 unpack_wds_SLQSDeleteProfile . . . . .	1805
9.56.3.47 unpack_wds_SLQSGet3GPPConfigItem . . . . .	1805
9.56.3.48 unpack_wds_SLQSGetCurrDataSystemStat . . . . .	1806
9.56.3.49 unpack_wds_SLQSGetDataBearerTechnology . . . . .	1806
9.56.3.50 unpack_wds_SLQSGetDUNCallInfo . . . . .	1806
9.56.3.51 unpack_wds_SLQSGetProfileSettings . . . . .	1807
9.56.3.52 unpack_wds_SLQSGetRuntimeSettings . . . . .	1807
9.56.3.53 unpack_wds_SLQSModifyProfile . . . . .	1807
9.56.3.54 unpack_wds_SLQSSet3GPPConfigItem . . . . .	1808
9.56.3.55 unpack_wds_SLQSSetIPFamilyPreference . . . . .	1808
9.56.3.56 unpack_wds_SLQSSetPacketSrvStatusCallback . . . . .	1808
9.56.3.57 unpack_wds_SLQSSetWdsEventCallback . . . . .	1809
9.56.3.58 unpack_wds_SLQSSetWdsEventCallback_ind . . . . .	1809
9.56.3.59 unpack_wds_SLQSSetDHCPv4ClientConfig . . . . .	1809
9.56.3.60 unpack_wds_SLQSStartDataSession . . . . .	1810
9.56.3.61 unpack_wds_SLQSStopDataSession . . . . .	1811
9.56.3.62 unpack_wds_SLQSWdsSwiPDPRuntimeSettings . . . . .	1811



# Chapter 1

## Welcome to the Sierra Wireless Linux QMI SDK API Reference Guide

This API reference guide contains information about all the modules, in the Sierra Wireless Linux QMI SDK (SLQS). Use the tabs at the top of the page to navigate the reference guide.

- Modules tab – lists all the service modules and provides a link to the API header file in each module.
- References tab – links to reference material.

### 1.1 Important Notice

Due to the nature of wireless communications, transmission and reception of data can never be guaranteed. Data may be delayed, corrupted (i.e., have errors) or be totally lost. Although significant delays or losses of data are rare when wireless devices such as the Sierra Wireless modem are used in a normal manner with a well-constructed network, the Sierra Wireless modem should not be used in situations where failure to transmit or receive data could result in damage of any kind to the user or any other party, including but not limited to personal injury, death, or loss of property. Sierra Wireless accepts no responsibility for damages of any kind resulting from delays or errors in data transmitted or received using the Sierra Wireless modem, or for failure of the Sierra Wireless modem to transmit or receive such data.

### 1.2 Limitation of Liability

The information in this manual is subject to change without notice and does not represent a commitment on the part of Sierra Wireless. SIERRA WIRELESS AND ITS AFFILIATES SPECIFICALLY DISCLAIM LIABILITY FOR ANY AND ALL DIRECT, INDIRECT, SPECIAL, GENERAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES INCLUDING, BUT NOT LIMITED TO, LOSS OF PROFITS OR REVENUE OR ANTICIPATED PROFITS OR REVENUE ARISING OUT OF THE USE OR INABILITY TO USE ANY SIERRA WIRELESS PRODUCT, EVEN IF SIERRA WIRELESS AND/OR ITS AFFILIATES HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR THEY ARE FORESEEABLE OR FOR CLAIMS BY ANY THIRD PARTY.

Notwithstanding the foregoing, in no event shall Sierra Wireless and/or its affiliates aggregate liability arising under or in connection with the Sierra Wireless product, regardless of the number of events, occurrences, or claims giving rise to liability, be in excess of the price paid by the purchaser for the Sierra Wireless product.

### 1.3 Patents

**Patents** This product may contain technology developed by or for Sierra Wireless Inc. This product includes technology licensed from QUALCOMM® 3G. This product is manufactured or sold by Sierra Wireless Inc. or its affiliates

under one or more patents licensed from InterDigital Group.

## 1.4 Copyright

© 2011-2015 Sierra Wireless. All rights reserved.

## 1.5 Trademarks

AirCard® and Heart of the Wireless Machine® are registered trademarks of Sierra Wireless. Watcher® is a trademark of Sierra Wireless, registered in the European Community. Sierra Wireless, the Sierra Wireless logo, the red wave design, and the red-tipped antenna are trademarks of Sierra Wireless. Windows® is a registered trademark of Microsoft Corporation. QUALCOMM® is a registered trademark of QUALCOMM Incorporated. Used under license. Linux is a registered trademark of Linus Torvalds. Other trademarks are the property of the respective owners.

## 1.6 Contact Information

If you have any questions about the Sierra Wireless Linux SDK, contact your Sierra Wireless account manager.

Consult our website for up-to-date product descriptions, documentation, application notes, firmware upgrades, troubleshooting tips, and press releases: <http://www.sierrawireless.com>.

## Chapter 2

# Module Index

### 2.1 Modules

Here is a list of all modules:

Device Connectivity Service (DCS) . . . . .	31
Wireless Data Service (WDS) . . . . .	32
Device Management Service (DMS) . . . . .	33
Network Access Service (NAS) . . . . .	34
CallBack registration (CBK) . . . . .	35
Short Message Service (SMS) . . . . .	36
Position Determination Service (PDS) . . . . .	37
Card Application Toolkit (CAT) . . . . .	38
Remote Management Service (RMS) . . . . .	39
Firmware Management Service (FMS) . . . . .	40
Open Mobile Alliance Service (OMA) . . . . .	41
Specific Absorption Rate (SAR) . . . . .	42
SWI Open Mobile Alliance Service (SWIOMA) . . . . .	43
Voice Service (VOICE) . . . . .	44
Non-service specific APIs (SWI) . . . . .	45
User Identity Module Service (UIM) . . . . .	46
Audio Service (AUDIO) . . . . .	47
Quality of Service (QOS) . . . . .	48
IMS Service (IMS) . . . . .	49
SWI Audio Service(SWIAUDIO) . . . . .	50
Location Service(LOC) . . . . .	51
Thermal Mitigation Device(TMD) . . . . .	52



## Chapter 3

# Namespace Index

### 3.1 Namespace List

Here is a list of all namespaces with brief descriptions:

<a href="#">Tables</a> . . . . .	53
----------------------------------	----





## Chapter 4

# Data Structure Index

### 4.1 Data Structures

Here are the data structures with brief descriptions:

<a href="#">_getIndicationRegResp</a>	55
<a href="#">_GetProfileSettingIn</a>	56
<a href="#">_GetProfileSettingOut</a>	57
<a href="#">_getResetInfoNotification</a>	57
<a href="#">_getTransLayerInfoResp</a>	59
<a href="#">_getTransNWRegInfoResp</a>	60
<a href="#">_MitigationDevInfo</a>	61
<a href="#">_modemTempNotification</a>	61
<a href="#">_packetSrvStatus</a>	62
<a href="#">_qaQmi3GPP2BroadcastCfgInfo</a>	64
<a href="#">_qaQmi3GPPBroadcastCfgInfo</a>	65
<a href="#">_setIndicationRegReq</a>	66
<a href="#">_slqs3GPPConfigItem</a>	67
<a href="#">_SlqsNas3GppNetworkRAT_</a>	69
<a href="#">_slqsNetworkScanInfo</a>	70
<a href="#">_SLQSOMADMSessionInfo</a>	72
<a href="#">_SLQSOMADMSettings</a>	75
<a href="#">_SLQSOMADMSettingsReqParams</a>	76
<a href="#">_SLQSOMADMSettingsReqParams3</a>	77
<a href="#">_SLQSSwiGetHostDevInfoParams</a>	78
<a href="#">_SLQSSwiGetOSInfoParams</a>	80
<a href="#">_SLQSSwiGetSerialNoExtParams</a>	81
<a href="#">_SLQSSwiSetHostDevInfoParams</a>	81
<a href="#">_SLQSSwiSetOSInfoParams</a>	82
<a href="#">_sysSelectPrefInfo</a>	83
<a href="#">_sysSelectPrefParams</a>	88
<a href="#">_transLayerinfo</a>	93
<a href="#">_transLayerInfoNotification</a>	94
<a href="#">_transNWRegInfoNotification</a>	95
<a href="#">accelAcceptReady_s</a>	96
<a href="#">accelTempAcceptReady_s</a>	96
<a href="#">acqOrderPref</a>	97
<a href="#">ActPilotPNElement</a>	98
<a href="#">AddCDMASysInfo</a>	98
<a href="#">AddSysInfo</a>	99
<a href="#">airTimer</a>	100
<a href="#">allCallsAlphaIDInfo</a>	101
<a href="#">allCallsDiagInfo</a>	101

<a href="#">allCallsUUSInfo</a>	102
<a href="#">alphaIDInfo</a>	102
<a href="#">altitudeSrcInfo</a>	103
<a href="#">appStats</a>	104
<a href="#">appStatus</a>	108
<a href="#">arrAlertingPattern</a>	112
<a href="#">arrAlertingType</a>	113
<a href="#">arrAlphaID</a>	114
<a href="#">arrCalledPartyNum</a>	114
<a href="#">arrCallEndReason</a>	115
<a href="#">arrCallInfo</a>	116
<a href="#">arrConnectPartyNum</a>	116
<a href="#">arrDiagInfo</a>	117
<a href="#">arrRedirPartyNum</a>	118
<a href="#">arrRemotePartyName</a>	118
<a href="#">arrRemotePartyNum</a>	119
<a href="#">arrSvcOption</a>	119
<a href="#">arrUUSInfo</a>	120
<a href="#">authenticateResult</a>	121
<a href="#">authenticationData</a>	121
<a href="#">BandCapabilityResp</a>	123
<a href="#">BdsSV</a>	125
<a href="#">BdsSVInfo</a>	126
<a href="#">BroadcastConfig</a>	126
<a href="#">burstDTMFInfo</a>	127
<a href="#">CallBarringSysInfo</a>	128
<a href="#">callBarStatus</a>	129
<a href="#">calledPartyInfo</a>	130
<a href="#">calledPartySubAdd</a>	132
<a href="#">callerIDInfo</a>	133
<a href="#">callFwdTypeAndPlan</a>	134
<a href="#">callFWExtInfo</a>	135
<a href="#">callFWInfo</a>	137
<a href="#">callInfo</a>	138
<a href="#">callingPartyInfo</a>	140
<a href="#">cardResult</a>	142
<a href="#">cardStatus</a>	143
<a href="#">CarrierImage_t</a>	144
<a href="#">CatAIPhalIdentifierTlv</a>	146
<a href="#">CatCommonEventTlv</a>	147
<a href="#">CatEndProactiveSessionTlv</a>	147
<a href="#">CATEventDataType</a>	148
<a href="#">CatEventIDDDataTlv</a>	148
<a href="#">CatEventListTlv</a>	148
<a href="#">CatRefreshTlv</a>	149
<a href="#">ccSUPSType</a>	149
<a href="#">CDMABroadcastConfig</a>	150
<a href="#">CDMAChannel</a>	151
<a href="#">CDMAECIOThresh</a>	152
<a href="#">CDMAInfo</a>	153
<a href="#">cdmaMsgDecodingParams</a>	154
<a href="#">cdmaMsgEncodingParams</a>	157
<a href="#">CDMARSSIThresh</a>	159
<a href="#">CDMASSInfo</a>	159
<a href="#">cdmaSSInfo</a>	160
<a href="#">CDMASysInfo</a>	160
<a href="#">CDMASysInfoExt</a>	164
<a href="#">CellDb</a>	165

cellParams	166
changeUIMPIN	167
ChannelRate	168
channelRate	168
CLIPResp	169
CLIRResp	170
ClkInfo	170
CNAPResp	173
COLPResp	173
COLRResp	174
CommInfo	175
ConnectionStatus	177
connectionStatus	178
connectNumInfo	178
CrashInfo	181
CrashInfoParams	182
CreateProfileIn	183
CreateProfileOut	184
CSGID	184
CUGInfo	185
curAMRConfig	186
CurrDataSysStat	187
currentCatEvent	188
CurrentImgList	189
currentPLMN	190
CurrImageInfo	191
CurrNetworkInfo	192
currNetworkInfo	194
custFeaturesInfo	194
custFeaturesSetting	197
custSettingInfo	199
custSettingList	200
dataBearers	202
DataBearerTech	203
DataBearerTechExt	205
dataBearerTechnology	205
dataRate	207
dataSrvCapabilities	207
DataStatusDetail	208
DataULongLongTlv	210
DataULongTlv	210
DcsUsbPortNames	210
delAssistDataStatus	210
depersonalizationInformation	211
detailSvcInfo	213
DeviceConfigDetail	215
DHCPOption	216
DHCPOptionList	217
diagInfo	218
dirNum	218
dms_ActivationStatusTlv	219
dms_OperatingModeTlv	220
dmsCurrentPRLInfo	221
DMScustSettingInfo	221
DMScustSettingList	222
DMSgetCustomFeatureV2	223
DMSgetCustomInput	224
dmsIndicationRegisterReq	224

dmsSwiGetResetInfo	225
Domain	225
DomainNameList	226
DRCParams	226
DTMFInfo	228
DTMFLengths	229
DUNCallInfoInd	229
dunchannelRate	230
ecioListElement	231
ECIOThresh	231
ECTNum	232
encryptedPIN1	233
ERIFileparams	234
errorRateListElement	234
eTWSPLMNInfoTlv	236
extDispRecInfo	236
FactorySequenceNumber	237
fileAttributes	237
fileInfo	242
FirmwareUpdatStat	242
FMSImageElement	244
FMSImageIdElement	245
FMSImageIdEntries	246
FMSImageList	247
FMSPrefImageList	248
fwinfo_s	248
GERANInfo	249
geranInstInfo	251
getAllCallInformation	252
getAllCallRmtPtyName	253
getAllCallRmtPtyNum	253
GetAudioPathConfigReq	254
GetAudioPathConfigResp	255
GetAudioProfileReq	257
GetAudioProfileResp	257
GetAudioVolTLBConfigReq	259
GetAudioVolTLBConfigResp	260
getCallFWExtInfo	261
getCallFWInfo	261
getCustomFeatureV2	262
getCustomInput	263
getDUNCallInfoReq	263
getDUNCallInfoResp	265
getDyingGaspCfg	268
getDyingGaspStatistics	269
GetErrRateResp	269
GetHRPDStatsResp	270
GetIMSSMSConfigParams	271
GetIMSUserConfigParams	272
GetIMSVoIPConfigResp	273
GetInstIDResp	275
GetM2MAudioProfileReq	275
GetM2MAudioProfileResp	276
GetM2MAudioVolumeReq	277
GetM2MAudioVolumeResp	278
GetM2MAVMuteReq	278
GetM2MAVMuteResp	279
GetM2MSpkrGainReq	280

GetM2MSpkrGainResp	280
getMsgWaitingInfo	280
GetNetworkTimeResp	282
GetRegMgrConfigParams	282
GetSessionIDResp	283
GetSIPConfigResp	284
GnssData	285
gnssSvInfoNotification	287
GPRSQoS	287
GPRSRequestedQoS	288
GPSSStateInfo	289
gpsTime_s	293
gsmCellInfo	294
GSMRSSIThresh	295
GSMSrvStatusInfo	296
GSMSysInfo	297
gyroAcceptReady_s	300
gyroTempAcceptReady_s	301
HDRECIOThresh	302
HDRIOThresh	303
HDRPersonalityInd	303
HDRPersonalityResp	304
HDRProtSubtypResp	304
HDRRSSIThresh	305
HDRSINRThresh	306
HDRSINRThreshold	306
HDRSSInfo	307
hdrSSInfo	308
HDRSysInfo	309
homeSIDNID	311
hotSwapStatus	312
image_info_t	313
ImageElement	313
ImageIdElement	314
ImageIDEntries	315
ImageList	315
IMSAIndRegisterInfo	316
imsaPdpStatusInfo	317
imsaRatStatusInfo	318
IMSARegistrationStatus	319
imsaRegStatusInfo	320
IMSAServiceStatus	321
IMSASupportedFieldsResp	324
IMSASupportedMsgInfo	324
imsaSvcStatusInfo	325
imsCfgIndRegisterInfo	326
imsRegMgrConfigInfo	327
imsSIPConfigInfo	329
imsSMSConfigInfo	330
imsUserConfigInfo	331
imsVoIPConfigInfo	331
IndFieldsList	334
infoInterFreq	335
IOThresh	336
IPv4Addr	337
IPv6Addr	337
IPV6AddressInfo	339
ipv6AddressInfo	339

IPV6GWAddressInfo	340
IPv6TrafCls	340
LibPackGPRSRequestedQoS	341
LibpackProfile3GPP	342
LibpackProfile3GPP2	349
LibPackprofile_3GPP	355
LibPackprofile_3GPP2	362
LibPackQoSClassID	368
LibPackTFTIDParams	369
LibPackUMTSQoS	371
LibPackUMTSReqQoSSigInd	374
lineCtrlInfo	375
loc_BdsSV	376
loc_BdsSVInfo	376
loc_CellDb	377
loc_ClkInfo	378
loc_GnssData	380
loc_gpsTime	382
loc_LocApplicationInfo	382
loc_precisionDilution	383
loc_sensorDataUsage	384
loc_SV	385
loc_SVInfo	386
loc_svUsedforFix	387
LocApplicationInfo	387
LocDelAssDataReq	389
LOCEventRegisterReqResp	390
LOCExtPowerStateReqResp	392
LocInjectPositionReq	392
LocInjectSensorDataReq	398
LocSetCradleMountReq	399
LOCStartReq	400
LOCStopReq	402
LteCQIParm	402
LteEARFCN	403
LteGsmCellInfo	404
LTEInfo	405
LTEInfoInterfreq	408
LTEInfoIntrafreq	409
LTEInfoNeighboringGSM	412
LTEInfoNeighboringWCDMA	412
LteNasReleaseInfo_s	413
LtePCI	414
LteRsrpinformation	414
LTERSRPThresh	415
LTERSRQThresh	415
LTERSSIThresh	416
LTESigRptCfg	416
LTESigRptConfig	418
LteSnrinformation	419
LTESNRThresh	420
LTESNRThreshold	420
LTESSInfo	421
LteSSInfo	422
LTESysInfo	423
LteWcdmaCellInfo	425
messageModeTlv	426
messageWaitingInfoContent	427

minBasedIMSI	428
mitigationDevList	428
MNRInfo	429
ModifyProfileIn	430
ModifyProfileOut	431
msgWaitingInfo	432
namName	432
nas_acqOrderPref	433
nas_AddCDMASysInfo	433
nas_AddSysInfo	434
nas_CallBarringSysInfo	435
nas_callBarStatus	435
nas_CDMAECIOThresh	436
nas_CDMAInfo	437
nas_CDMA RSSI Thresh	438
nas_CDMASysInfo	439
nas_CDMASysInfoExt	443
nas_cellParams	444
nas_CommInfo	445
nas_CSGID	446
nas_currentPLMN	447
nas_dataSrvCapabilities	448
nas_detailSvcInfo	449
nas_ecioListElement	451
nas_errorRateListElement	452
nas_GERANInfo	453
nas_geranInstInfo	455
nas_gsmCellInfo	456
nas_GSMRSSI Thresh	457
nas_GSMSrvStatusInfo	458
nas_GSMSysInfo	459
nas_HDRECIOTresh	462
nas_HDRIOThresh	463
nas_HDRRSSI Thresh	463
nas_HDRSINRThreshold	464
nas_HDRSysInfo	465
nas_infoInterFreq	468
nas_lteGsmCellInfo	469
nas_LTEInfo	470
nas_LTEInfoInterfreq	473
nas_LTEInfoIntrafreq	473
nas_LTEInfoNeighboringGSM	476
nas_LTEInfoNeighboringWCDMA	477
nas_lteRsrpInformation	477
nas_LTERS RP Thresh	478
nas_LTERS RQ Thresh	478
nas_LTERSSI Thresh	479
nas_LTESigRptConfig	479
nas_lteSnrinformation	481
nas_LTESNRThreshold	481
nas_LTESysInfo	482
nas_lteWcdmaCellInfo	485
nas_MNRInfo	486
nas_netSelectionPref	487
nas_nmrCellInfo	487
nas_qaQmi3Gpp2TimeZone	490
nas_QmiNas3GppNetworkInfo	490
nas_QmiNas3GppNetworkRAT	491

<a href="#">nas_QmisNasPcsDigit</a>	492
<a href="#">nas_RejectReasonTlv</a>	493
<a href="#">nas_RFInfoTlv</a>	493
<a href="#">nas_roamIndList</a>	494
<a href="#">nas_rsrqInformation</a>	495
<a href="#">nas_rxSignalStrengthListElement</a>	495
<a href="#">nas_servSystem</a>	496
<a href="#">nas_SignalStrengthTlv</a>	498
<a href="#">nas_SLQSSignalStrengthsIndReq</a>	499
<a href="#">nas_SLQSSignalStrengthsInformation</a>	500
<a href="#">nas_SLQSSignalStrengthsTlv</a>	501
<a href="#">nas_SrvStatusInfo</a>	501
<a href="#">nas_sysInfoCommon</a>	502
<a href="#">nas_TDSCDMAECIOThresh</a>	505
<a href="#">nas_TDSCDMARSCPTthresh</a>	506
<a href="#">nas_TDSCDMARSSIThresh</a>	506
<a href="#">nas_TDSCDMASINRThresh</a>	507
<a href="#">nas_timeInfo</a>	507
<a href="#">nas_UMTSInfo</a>	509
<a href="#">nas_UMTSinstInfo</a>	511
<a href="#">nas_umtsLTENbrCell</a>	512
<a href="#">nas_UniversalTime</a>	513
<a href="#">nas_wcdmaCellInfo</a>	516
<a href="#">nas_WCDMAECIOThresh</a>	516
<a href="#">nas_WCDMAInfoLTENeighborCell</a>	517
<a href="#">nas_WCDMARSSIThresh</a>	518
<a href="#">nas_WCDMASysInfo</a>	519
<a href="#">NASBandPreferenceTlv</a>	523
<a href="#">nasCellLocationInfoResp</a>	523
<a href="#">NASEmergencyModeTlv</a>	525
<a href="#">nasGet3GPP2SubscriptionInfoReq</a>	525
<a href="#">nasGet3GPP2SubscriptionInfoResp</a>	525
<a href="#">nasGetHDRColorCodeResp</a>	526
<a href="#">nasGetLTECphyCa</a>	527
<a href="#">NasGetLTECphyCaInfo</a>	527
<a href="#">nasGetLTECphyCaResp</a>	528
<a href="#">nasGetSigInfoResp</a>	528
<a href="#">nasGetSysInfoResp</a>	529
<a href="#">nasGetTxRxInfoReq</a>	532
<a href="#">nasGetTxRxInfoResp</a>	533
<a href="#">NASGWAcqOrderPrefTlv</a>	534
<a href="#">nasIndicationRegisterReq</a>	534
<a href="#">nasInitNetworkReg</a>	537
<a href="#">NASLTEBandPreferenceTlv</a>	538
<a href="#">NASLteNasReleaseInfoTlv</a>	539
<a href="#">NASModePreferenceTlv</a>	539
<a href="#">NASNetSelPreferenceTlv</a>	539
<a href="#">nasNetworkTime</a>	539
<a href="#">nasOperatorNameResp</a>	540
<a href="#">NASOTAMessageTlv</a>	541
<a href="#">NASPhyCaAggPcellInfo</a>	542
<a href="#">NASPhyCaAggScellIDBw</a>	543
<a href="#">NASPhyCaAggScellIndex</a>	543
<a href="#">NASPhyCaAggScellIndType</a>	544
<a href="#">NASPhyCaAggScellInfo</a>	545
<a href="#">nasPLMNNameReq</a>	546
<a href="#">nasPLMNNameResp</a>	547
<a href="#">NASPRLPreferenceTlv</a>	549



NASQmiCbkNasSwiOTAMessageInd	549
NASQmiCbkNasSystemSelPrefInd	550
NASRoamPreferenceTlv	550
NASServDomainPrefTlv	551
NASServingSystemInfo	551
nasSigInfo	553
nasSwiGetChannelLockResp	554
NasSwiIndReg	554
nasSwiSetChannelLockReq	556
nasSysInfo	556
NASTimeInfoTlv	559
netSelectionPref	560
NetStats	560
NetworkDebugResp	561
NetworkStat1x	562
NetworkStatEVDO	565
newMTMessageTlv	567
newPwdData	568
nmrCellInfo	568
NSSAudioCtrl	571
NWProfile	571
omaDmConfigTlv	572
omaDmConfigTlvExt	573
omaDmFotaTlv	575
omaDmFotaTlvExt	577
omaDmNotificationsTlv	580
operatorNameString	580
OperatorPLMNData	580
operatorPLMNList	581
pack_dms_GetCustFeaturesV2_t	582
pack_dms_SetCrashAction_t	582
pack_dms_SetCustFeature_t	583
pack_dms_SetCustFeaturesV2_t	584
pack_dms_SetEventReport_t	584
pack_dms_SetPower_t	585
pack_dms_SetUSBComp_t	585
pack_dms_SLQSDmsSwiIndicationRegister_t	585
pack_dms_SLQSSwiSetDyingGaspCfg_t	585
pack_dms_UIMGetICCID_t	586
pack_fms_GetImagesPreference_t	586
pack_fms_GetStoredImages_t	588
pack_fms_SetImagesPreference_t	588
pack_loc_Delete_Assist_Data_t	589
pack_loc_EventRegister_t	590
pack_loc_SetExtPowerState_t	592
pack_loc_SetOperationMode_t	592
pack_loc_Start_t	593
pack_loc_Stop_t	595
pack_nas_SetACCOLC_t	595
pack_nas_SetNetworkPreference_t	597
pack_nas_SLQSGetPLMNName_t	598
pack_nas_SLQSInitiateNetworkRegistration_t	599
pack_nas_SLQSNasConfigSigInfo2_t	600
pack_nas_SLQSNasIndicationRegisterExt_t	605
pack_nas_SLQSNasSwiOTAMessageCallback_t	609
pack_nas_SLQSSetSignalStrengthsCallback_t	610
pack_nas_SLQSSetSysSelectionPref_t	611
pack_qmi_t	615

<a href="#">pack_qos_SLQSQosSwiReadApnExtraParams_t</a>	616
<a href="#">pack_qos_SLQSQosSwiReadDataStats_t</a>	616
<a href="#">pack_qos_SLQSSetQosEventCallback_t</a>	616
<a href="#">pack_sms_SendSMS_t</a>	618
<a href="#">pack_sms_SetNewSMSCallback_t</a>	619
<a href="#">pack_sms_SLQSDeleteSMS_t</a>	619
<a href="#">pack_sms_SLQSGetSMS_t</a>	620
<a href="#">pack_sms_SLQSGetSMSList_t</a>	621
<a href="#">pack_sms_SLQSModifySMSStatus_t</a>	622
<a href="#">pack_swiloc_SwiLocSetAutoStart_t</a>	623
<a href="#">pack_swima_SLQSOMADMCancelSession_t</a>	625
<a href="#">pack_swima_SLQSOMADMGetSessionInfo_t</a>	625
<a href="#">pack_swima_SLQSOMADMSelectSendSelection_t</a>	626
<a href="#">pack_swima_SLQSOMADMSetSettings_t</a>	627
<a href="#">pack_swima_SLQSOMADMStartSession_t</a>	628
<a href="#">pack_uim_ChangePin_t</a>	628
<a href="#">pack_uim_ReadTransparent_t</a>	629
<a href="#">pack_uim_SetPinProtection_t</a>	631
<a href="#">pack_uim_SLQSUIEventRegister_t</a>	632
<a href="#">pack_uim_SLQSUIMSwitchSlot_t</a>	632
<a href="#">pack_uim_UnblockPin_t</a>	633
<a href="#">pack_uim_VerifyPin_t</a>	634
<a href="#">pack_wds_GetDefaultProfile_t</a>	636
<a href="#">pack_wds_GetDefaultProfileNum_t</a>	637
<a href="#">pack_wds_GetDormancyState_t</a>	637
<a href="#">pack_wds_GetLastMobileIPError_t</a>	637
<a href="#">pack_wds_GetMobileIP_t</a>	637
<a href="#">pack_wds_GetMobileIPProfile_t</a>	637
<a href="#">pack_wds_GetPacketStatus_t</a>	639
<a href="#">pack_wds_GetSessionDuration_t</a>	639
<a href="#">pack_wds_RMSetTransferStatistics_t</a>	639
<a href="#">pack_wds_SetDefaultProfile_t</a>	639
<a href="#">pack_wds_SetDefaultProfileNum_t</a>	640
<a href="#">pack_wds_SetMobileIPProfile_t</a>	641
<a href="#">pack_wds_SLQSCreateProfile_t</a>	642
<a href="#">pack_wds_SLQSDeleteProfile_t</a>	643
<a href="#">pack_wds_SLQSGetCurrDataSystemStat_t</a>	643
<a href="#">pack_wds_SLQSGetDataBearerTechnology_t</a>	643
<a href="#">pack_wds_SLQSGetDUNCallInfo_t</a>	643
<a href="#">pack_wds_SLQSGetProfileSettings_t</a>	644
<a href="#">pack_wds_SLQSGetRuntimeSettings_t</a>	645
<a href="#">pack_wds_SLQSModifyProfile_t</a>	646
<a href="#">pack_wds_SLQSSet3GPPConfigItem_t</a>	648
<a href="#">pack_wds_SLQSSetIPFamilyPreference_t</a>	649
<a href="#">pack_wds_SLQSSetWdsEventCallback_t</a>	651
<a href="#">pack_wds_SLQSSetDHCPv4ClientConfig_t</a>	652
<a href="#">pack_wds_SLQSStartDataSession_t</a>	652
<a href="#">pack_wds_SLQSStopDataSession_t</a>	653
<a href="#">pack_wds_SLQSWdsSwiPDPRuntimeSettings_t</a>	654
<a href="#">PackCreateProfileOut</a>	654
<a href="#">packgetDyingGaspCfg</a>	654
<a href="#">packgetDyingGaspStatistics</a>	655
<a href="#">PCMparams</a>	655
<a href="#">PCSCFFQDNAddress</a>	657
<a href="#">PCSCFFQDNAddressList</a>	657
<a href="#">PCSCFIPv4ServerAddressList</a>	659
<a href="#">PDSPositionData</a>	659
<a href="#">PDSPosMethodStateReq</a>	661

peerNumberInfo	662
personalizationStatus	664
PhyCaAggPcellInfo	665
PhyCaAggScellIDBw	667
PhyCaAggScellIndex	668
PhyCaAggScellIndType	668
PhyCaAggScellInfo	669
PilotSetData	671
PilotSetParams	672
pktErrRate	672
PLMNNetworkName	673
PLMNNetworkNameData	673
Port	675
precisionDilution_s	676
PrefImageList	677
prefVoiceSO	677
Profile3GPP	680
Profile3GPP2	686
ProfileIdentifier	692
protocolSubtypeElement	693
PSDetachReq	695
qaQmi3Gpp2TimeZone	695
qaQmiInterfaceInfo	696
qaQmiServingSystemParam	696
QmiCbkCatEventStatusReportInd	701
QmiCbkLocCradleMountInd	701
QmiCbkLocEngineStateInd	702
QmiCbkLocEventTimeSyncInd	703
QmiCbkLocInjectPositionInd	703
QmiCbkLocInjectSensorDataInd	704
QmiCbkLocInjectTimeInd	706
QmiCbkLocInjectUTCTimeInd	706
QmiCbkLocPositionReportInd	707
QmiCbkLocSensorStreamingInd	713
QmiCbkLocSetExtPowerConfigInd	714
QmiCbkNasLTECphyCalInfo	715
QmiCbkSwiOmaDmEventStatusReportInd	715
QmiCbkSwiOmaDmEventStatusReportIndExt	716
QmiCbkTmdMitiLvlRptInd	716
QmiCbkWdsStatisticsIndState	716
qmifwinfo_s	718
QmiNas3GppNetworkInfo	719
QmiNasGetRFBandInfoResp	721
QmiNasPerformNetworkScanResp	721
qmiSmsMessageList	721
qmiWDSDataBearerTechnology	722
QmiWdsIpAddressInfo	722
qmiWdsRunTimeSettings	723
QosClassID	727
QosEventInfo	728
QosFlowInfo	730
QosFlowInfoState	731
QosMap	732
RankIndicatorInd	733
readResult	733
readTransparentInfo	733
redirNumInfo	734
registerRefresh	736

remainingRetries	737
remotePartyName	738
remotePartyNum	739
ReqFieldsList	740
RespFieldsList	741
RFBandInfoElements	741
rmTrasferStaticsReq	742
roamIndList	743
RoamingInfo	743
roamTimer	744
RSRPThresh	744
rsrqInformation	746
RSRQThresh	747
RSSIThresh	747
RXAGCList	748
RXAVCList	749
rxInfo	750
RXPCMIIRFtr	751
rxSignalStrengthListElement	753
sApnExtraParams	754
satelliteInfo	755
sensorData	758
sensorDataUsage_s	760
serialNumbersInfo	760
serviceProviderName	762
ServingSystemInfo	762
servSystem	764
sessionInfo	766
sessionInfoExt	767
sessionInfoTlv	767
sessionInfoTlvExt	767
SetAudioPathConfigReq	768
SetAudioProfileReq	770
SetAudioVoTLBConfigReq	772
SetAudioVoTLBConfigResp	773
setCustomSettingV2	773
setDyingGaspCfg	774
SetIMSSMSCConfigReq	774
SetIMSSMSCConfigResp	775
SetIMSUserConfigReq	776
SetIMSUserConfigResp	776
SetIMSVoIPConfigReq	777
SetIMSVoIPConfigResp	780
SetM2MAudioAVCFGReq	780
SetM2MAudioLPBKReq	781
SetM2MAudioProfileReq	781
SetM2MAudioVolumeReq	783
SetM2MAVMuteReq	783
SetM2MSprkGainReq	784
setPINProtection	785
SetRegMgrConfigReq	786
SetRegMgrConfigResp	787
setSignalStrengthInfo	788
SetSIPConfigReq	793
SetSIPConfigResp	794
sGetDeviceSeriesResult	794
sidNid	795
sigInfo	795

signalInfo	797
SignalStrengthDataType	798
slot_t	798
slotInf	799
slotInfo	801
slots_t	803
slqsautoconnect	803
SLQSDDeleteProfileParams	804
slqsfwinfo_s	805
SlqNas3GppNetworkInfo	806
SlqNasPcsDigit	808
slqssendasyncsmsparams_s	808
slqssendsmsparams_s	811
slqsSessionStateInfo	812
slqsSignalStrengthInfo	813
SLQSSignalStrengthsIndReq	817
SLQSSignalStrengthsInformation	819
slqsWdsEventInfo	821
SMSAsyncRawSend_s	823
sMSCAddress	825
SMSCAddress	826
sMSCAddressTlv	826
sMSEtwsMessage	827
SMSEtwsMessage	827
sMSEtwsMessageTlv	828
sMSEtwsPlmn	829
SMSEtwsPlmn	829
SMSEventInfo_s	830
smsMaxStorageSizeReq	831
smsMaxStorageSizeResp	832
SMSMemoryInfo	832
sMSMessageMode	834
SMSMessageMode	834
smsMsgprotocolResp	835
sMSMTMessage	835
SMSMTMessage	835
sMSOnIMS	836
SMSOnIMS	836
sMSOnIMSTlv	837
smsRouteEntry	837
smsSetRoutesReq	839
sMSTransferRouteMTMessage	839
SMSTransferRouteMTMessage	840
sQosFlowStat	841
sQosStat	842
SrvStatusInfo	844
ssdatasession_params	844
SupportedMsgList	847
SUPSInfo	848
SV	849
SVInfo	850
svUsedforFix_s	850
SWI_STRUCT_CarrierImage	851
SwiLocGetAutoStartResp	852
SwiLocSetAutoStartReq	855
swiModemStatusResp	857
SwiOTAMsg_s	858
swiPDPRuntimeSettingsReq	859

swiPDPRuntimeSettingsResp	859
swiQosFilter	862
swiQosFlow	864
swiQosGranted	868
swiQosIds	868
swiQosModifyReq	869
swiQosReq	869
swiRMTrasnferStaticsReq	870
sysInfoCommon	871
TDSCDMAECIOThresh	874
TDSCDMARSCPThresh	874
TDSCDMARSSIThresh	875
TDSCDMASigInfoExt	875
tdscdmaSigInfoExt	876
TDSCDMASINRCONFTThresh	877
TDSCDMASINRThresh	877
tempratureData	878
TFTIDParams	879
timeInfo	881
TmdDeRegNotMitigationLvlReq	883
TmdGetMitigationDevListResp	884
TmdGetMitigationLvlReq	885
TmdGetMitigationLvlResp	885
TmdMitigationLvlIndReq	886
TmdRegNotMitigationLvlReq	886
tokenBucket	887
Tos	887
transferRouteMessageTlv	889
transferStatInd	889
TransferStatInd	891
TransferStatsDataType	891
TrStatInd	892
trueIMSI	892
TXAGCList	893
txInfo	894
TXPCMIIRFtr	895
uim_appStatus	897
uim_cardResult	901
uim_cardStatus	901
uim_changeUIMPIN	903
uim_encryptedPIN1	904
uim_fileInfo	904
uim_hotSwapStatus	905
uim_readResult	906
uim_readTransparentInfo	906
uim_remainingRetries	907
uim_sessionInformation	907
uim_setPINProtection	908
uim_slotInfo	909
uim_UIMSessionInformation	911
uim_unblockUIMPIN	912
uim_verifyUIMPIN	913
UIMAuthenticateReq	914
UIMAuthenticateResp	915
UIMChangePinReq	915
UIMDepersonalizationReq	916
UIMDepersonalizationResp	917
UIMEventRegisterReqResp	917

UIMGetCardStatusResp	918
UIMGetConfigurationReq	918
UIMGetConfigurationResp	919
UIMGetFileAttributesReq	920
UIMGetFileAttributesResp	920
UIMGetSlotsStatusResp	921
UIMPinResp	922
UIMPowerDownReq	923
UIMPowerUpReq	923
UIMReadTransparentReq	924
UIMReadTransparentResp	925
UIMRefreshCompleteReq	925
UIMRefreshEvent	926
UIMRefreshGetLastEventReq	928
UIMRefreshGetLastEventResp	929
UIMRefreshOKReq	929
UIMRefreshRegisterReq	930
UIMSessionInformation	930
UIMSetPinProtectionReq	931
UIMSlotsStatus	932
UIMSlotStatus	933
UIMSlotStatusChangeInfo	934
UIMStatusChangeInfo	934
UIMSwitchSlotReq	936
UIMUnblockPinReq	936
UIMVerifyPinReq	937
UMTSInfo	938
UMTSinstInfo	940
umtsLTENbrCell	941
UMTSMinQoS	942
UMTSQoS	946
UMTSReqQoSsigInd	949
unblockUIMPIN	950
UniversalTime	951
unpack_dms_GetActivationState_t	952
unpack_dms_GetBandCapability_t	953
unpack_dms_GetCrashAction_t	953
unpack_dms_GetCustFeature_t	953
unpack_dms_GetCustFeaturesV2_t	954
unpack_dms_GetDeviceCap_t	955
unpack_dms_GetDeviceCapabilities_t	955
unpack_dms_GetDeviceHardwareRev_t	956
unpack_dms_GetDeviceMfr_t	956
unpack_dms_GetDeviceSerialNumbers_t	957
unpack_dms_GetFirmwareInfo_t	957
unpack_dms_GetFirmwareRevision_t	958
unpack_dms_GetFirmwareRevisions_t	959
unpack_dms_GetFSN_t	959
unpack_dms_GetHardwareRevision_t	960
unpack_dms_GetIMSI_t	960
unpack_dms_GetModelID_t	960
unpack_dms_GetNetworkTime_t	961
unpack_dms_GetPower_t	961
unpack_dms_GetPRLVersion_t	962
unpack_dms_GetSerialNumbers_t	962
unpack_dms_GetUSBComp_t	963
unpack_dms_GetVoiceNumber_t	963
unpack_dms_SetCrashAction_t	964

<a href="#">unpack_dms_SetCustFeature_t</a>	964
<a href="#">unpack_dms_SetCustFeaturesV2_t</a>	964
<a href="#">unpack_dms_SetEventReport_ind_t</a>	964
<a href="#">unpack_dms_SetEventReport_t</a>	965
<a href="#">unpack_dms_SetFirmwarePreference_t</a>	965
<a href="#">unpack_dms_SetPower_t</a>	966
<a href="#">unpack_dms_SetUSBComp_t</a>	966
<a href="#">unpack_dms_SLQSDmsSwiGetResetInfo_Ind_t</a>	966
<a href="#">unpack_dms_SLQSDmsSwiGetResetInfo_t</a>	967
<a href="#">unpack_dms_SLQSDmsSwiIndicationRegister_t</a>	968
<a href="#">unpack_dms_SLQSGetBandCapability_t</a>	969
<a href="#">unpack_dms_SLQSSwiClearDyingGaspStatistics_t</a>	971
<a href="#">unpack_dms_SLQSSwiGetDyingGaspCfg_t</a>	971
<a href="#">unpack_dms_SLQSSwiGetDyingGaspStatistics_t</a>	973
<a href="#">unpack_dms_SLQSSwiGetFirmwareCurr_t</a>	973
<a href="#">unpack_dms_SLQSSwiGetFwUpdateStatus_t</a>	974
<a href="#">unpack_dms_SLQSSwiSetDyingGaspCfg_t</a>	976
<a href="#">unpack_dms_UIMGetICCID_t</a>	976
<a href="#">unpack_fms_GetImagesPreference_t</a>	977
<a href="#">unpack_fms_GetStoredImages_t</a>	978
<a href="#">unpack_fms_SetImagesPreference_t</a>	978
<a href="#">unpack_loc_Delete_Assist_Data_t</a>	979
<a href="#">unpack_loc_EngineState_Ind_t</a>	979
<a href="#">unpack_loc_EventRegister_t</a>	980
<a href="#">unpack_loc_PositionRpt_Ind_t</a>	980
<a href="#">unpack_loc_SetExtPowerConfig_Ind_t</a>	987
<a href="#">unpack_loc_SetExtPowerState_t</a>	988
<a href="#">unpack_loc_SetOperationMode_t</a>	989
<a href="#">unpack_loc_Start_t</a>	989
<a href="#">unpack_loc_Stop_t</a>	989
<a href="#">unpack_nas_GetCDMANetworkParameters_t</a>	990
<a href="#">unpack_nas_GetHomeNetwork_t</a>	991
<a href="#">unpack_nas_GetNetworkPreference_t</a>	991
<a href="#">unpack_nas_GetRFInfo_t</a>	993
<a href="#">unpack_nas_GetServingNetwork_t</a>	994
<a href="#">unpack_nas_GetServingNetworkCapabilities_t</a>	995
<a href="#">unpack_nas_GetSignalStrengths_t</a>	996
<a href="#">unpack_nas_PerformNetworkScan_t</a>	996
<a href="#">unpack_nas_SetDataCapabilitiesCallback_ind_t</a>	997
<a href="#">unpack_nas_SetEventReportInd_t</a>	997
<a href="#">unpack_nas_SetNetworkPreference_t</a>	998
<a href="#">unpack_nas_SetRoamingIndicatorCallback_ind_t</a>	999
<a href="#">unpack_nas_SetServingSystemCallback_ind_t</a>	999
<a href="#">unpack_nas_SlqsGetLTECphyCAInfo_t</a>	1000
<a href="#">unpack_nas_SLQSGetNetworkTime_t</a>	1000
<a href="#">unpack_nas_SLQSGetPLMNName_t</a>	1001
<a href="#">unpack_nas_SLQSGetServingSystem_t</a>	1002
<a href="#">unpack_nas_SLQSGetSignalStrength_t</a>	1004
<a href="#">unpack_nas_SLQSGetSysInfo_t</a>	1005
<a href="#">unpack_nas_SLQSGetSysSelectionPref_t</a>	1009
<a href="#">unpack_nas_SLQSNasGetCellLocationInfo_t</a>	1012
<a href="#">unpack_nas_SLQSNasGetSigInfo_t</a>	1014
<a href="#">unpack_nas_SLQSNasNetworkTimeCallBack_ind_t</a>	1014
<a href="#">unpack_nas_SLQSNasSigInfoCallback_t</a>	1015
<a href="#">unpack_nas_SLQSNasSwiModemStatus_t</a>	1017
<a href="#">unpack_nas_SLQSNasSwiOTAMessageCallback_ind_t</a>	1018
<a href="#">unpack_nas_SLQSSetSysSelectionPrefCallBack_ind_t</a>	1018
<a href="#">unpack_nas_SLQSSwiGetLteCQI_t</a>	1019



unpack_nas_SLQSSysInfoCallback_t	1019
unpack_omaDmConfigTlv_t	1022
unpack_omaDmFotaTlv_t	1024
unpack_omaDmNotificationsTlv_t	1026
unpack_qmi_t	1027
unpack_qos_dataRate_t	1027
unpack_qos_IPv4Addr_t	1028
unpack_qos_IPv6Addr_t	1028
unpack_qos_IPv6TrafCls_t	1029
unpack_qos_pktErrRate_t	1029
unpack_qos_Port_t	1030
unpack_qos_QosFlowInfo_t	1030
unpack_qos_QosFlowInfoState_t	1032
unpack_qos_SLQSQosGetNetworkStatus_t	1033
unpack_qos_SLQSQosSwiReadApnExtraParams_t	1033
unpack_qos_SLQSQosSwiReadDataStats_t	1034
unpack_qos_SLQSSetQosEventCallback_ind_t	1036
unpack_qos_SLQSSetQosNWStatusCallback_ind_t	1036
unpack_qos_SLQSSetQosPriEventCallback_ind_t	1038
unpack_qos_SLQSSetQosStatusCallback_ind_t	1038
unpack_qos_swiQosFilter_t	1040
unpack_qos_swiQosFlow_t	1043
unpack_qos_tokenBucket_t	1048
unpack_qos_Tos_t	1049
unpack_QosFlowStat_t	1049
unpack_sms_SendSMS_t	1050
unpack_sms_SetNewSMSCallback_ind_t	1051
unpack_sms_SetNewSMSCallback_t	1052
unpack_sms_SLQSDeleteSMS_t	1052
unpack_sms_SLQSGetSMS_t	1052
unpack_sms_SLQSGetSMSList_t	1053
unpack_sms_SLQSModifySMSStatus_t	1054
unpack_sms_SLQSWmsMemoryFullCallBack_ind_t	1054
unpack_swiloc_SwiLocGetAutoStart_t	1054
unpack_swioma_SLQSOMADMAAlertCallback_ind_t	1056
unpack_swioma_SLQSOMADMGetSessionInfo_t	1057
unpack_swioma_SLQSOMADMGetSettings_t	1060
unpack_swioma_SLQSOMADMStartSession_t	1062
unpack_uim_ChangePin_t	1062
unpack_uim_GetCardStatus_t	1063
unpack_uim_ReadTransparent_t	1064
unpack_uim_SetPinProtection_t	1065
unpack_uim_SetUimSlotStatusChangeCallback_ind_t	1066
unpack_uim_SLQSUIMEventRegister_t	1066
unpack_uim_SLQSUIMGetSlotsStatus_t	1067
unpack_uim_SLQSUIMSetStatusChangeCallBack_ind_t	1067
unpack_uim_UnblockPin_t	1068
unpack_uim_VerifyPin_t	1068
unpack_wds_GetConnectionRate_t	1070
unpack_wds_GetDefaultProfile_t	1071
unpack_wds_GetDefaultProfileNum_t	1072
unpack_wds_GetDormancyState_t	1072
unpack_wds_GetLastMobileIPError_t	1073
unpack_wds_GetMobileIP_t	1073
unpack_wds_GetMobileIPProfile_t	1073
unpack_wds_GetPacketStatus_t	1074
unpack_wds_GetSessionDuration_t	1076
unpack_wds_GetSessionState_t	1076

unpack_wds_RMSetTransferStatistics_t	1076
unpack_wds_SetMobileIPProfile_t	1076
unpack_wds_SLQSCreateProfile_t	1076
unpack_wds_SLQSDeleteProfile_t	1077
unpack_wds_SLQSGet3GPPConfigItem_t	1077
unpack_wds_SLQSGetCurrDataSystemStat_t	1079
unpack_wds_SLQSGetDataBearerTechnology_t	1079
unpack_wds_SLQSGetDUNCallInfo_t	1080
unpack_wds_SLQSGetProfileSettings_t	1081
unpack_wds_SLQSGetRuntimeSettings_t	1081
unpack_wds_SLQSModifyProfile_t	1083
unpack_wds_SLQSSetIPFamilyPreference_t	1083
unpack_wds_SLQSSetPacketSrvStatusCallback_t	1084
unpack_wds_SLQSSetWdsEventCallback_ind_t	1085
unpack_wds_SLQSSetDHCPv4ClientConfig_t	1086
unpack_wds_SLQSStartDataSession_t	1087
unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t	1087
UnPackGetProfileSettingOut	1089
unpackWdsProfileParam	1089
USBCompConfig	1089
USBCompParams	1091
USSDNoWaitIndicationInfo	1093
USSDRespFNetwork	1094
USSInfo	1095
USSResp	1095
UUSInfo	1096
verifyUIMPIN	1097
voiceALSSelectLineInfo	1098
voiceALSSetLineSwitchInfo	1099
voiceAnswerCall	1099
voiceBindSubscriptionInfo	1100
voiceBurstDTMFInfo	1100
voiceCallInfoReq	1101
voiceCallInfoResp	1101
voiceCallRequestParams	1105
voiceCallResponseParams	1107
voiceContDTMFInfo	1108
voiceDTMFEventInfo	1109
voiceFlashInfo	1110
voiceGetAllCallInfo	1111
voiceGetCallBarringReq	1114
voiceGetCallBarringResp	1115
voiceGetCallFWReq	1116
voiceGetCallFWResp	1118
voiceGetCallWaitInfo	1120
voiceGetCLIPResp	1121
voiceGetCLIRResp	1124
voiceGetCNAPResp	1125
voiceGetCOLPResp	1127
voiceGetCOLRResp	1128
voiceGetConfigReq	1130
voiceGetConfigResp	1132
voiceIndicationRegisterInfo	1134
voiceInfoRec	1135
voiceManageCallsReq	1137
voiceManageCallsResp	1139
voiceOrigUSSDNoWaitInfo	1139
voiceOTASPStatusInfo	1140

voicePrivacyInfo	1141
voiceSetAllCallStatusCbInfo	1141
voiceSetCallBarringPwdInfo	1144
voiceSetCallBarringPwdResp	1145
voiceSetConfigReq	1146
voiceSetConfigResp	1148
voiceSetPrefPrivacy	1150
voiceSetSUPSServiceReq	1151
voiceSetSUPSServiceResp	1153
voiceStopContDTMFInfo	1155
voiceSUPSInfo	1155
voiceSUPSNotification	1158
wcdmaCellInfo	1160
WCDMAECIOTresh	1161
WCDMAInfoLTENeighborCell	1161
wcdmaLongMsgDecodingParams	1162
wcdmaMsgDecodingParams	1164
wcdmaMsgEncodingParams	1166
WCDMARSSITresh	1167
WCDMASysInfo	1167
wcdmaUARFCN	1172
wds_currNetworkInfo	1172
wds_Domain	1175
wds_DomainNameList	1175
wds_GPRSQoS	1176
wds_IPV6AddressInfo	1177
wds_IPV6GWAddressInfo	1177
wds_PCSCFFQDNAddress	1178
wds_PCSCFFQDNAddressList	1178
wds_PCSCFIPv4ServerAddressList	1180
wds_ProfileIdentifier	1180
wds_profileInfo	1181
wds_UMTSMinQoS	1181
WdsByteTotals	1185
WdsByteTotalsElmnts	1186
WdsClientLeaseChange	1187
WdsConnectionRate	1187
WdsConnectionRateElmnts	1188
WdsDHCPv4ClientLeaseInd	1189
WdsDHCPv4Config	1190
wdsDhcpv4HwConfig	1191
WdsDHCPv4HWConfig	1191
WdsDHCPv4Option	1192
wdsDhcpv4Option	1192
wdsDhcpv4OptionList	1193
WdsDHCPv4OptionList	1193
wdsDhcpv4ProfileId	1194
WdsDHCPv4ProfileId	1195
WDSGetLoopbackData	1195
WdsIpAddressInfoReq	1196
WdsPktStatisticsElmnts	1196
WdsPktStatisticsReq	1199
WdsPktStatisticsResp	1199
WdsProfileParam	1200
WdsRunTimeSettings	1200
wdsSetEventReportReq	1201
WDSSetLoopbackData	1204
WDSSWICurrentChannelRates	1206



## Chapter 5

# File Index

### 5.1 File List

Here is a list of all files with brief descriptions:

<a href="#">apdoxypages.c</a>	Contains the module declaration for the Doxygen output. Also contains the content of the main page and related pages . . . . .	1209
<a href="#">common.h</a>		1209
<a href="#">dms.h</a>		1213
<a href="#">fms.h</a>		1246
<a href="#">loc.h</a>		1250
<a href="#">nas.h</a>		1259
<a href="#">qaCbkCatEventReportInd.h</a>		1287
<a href="#">qaCbkSwiOmaDmEventReportInd.h</a>		1289
<a href="#">qaGobiApiAudio.h</a>	Audio Service API function prototypes . . . . .	1290
<a href="#">qaGobiApiCat.h</a>	Card Application Toolkit API function headers . . . . .	1294
<a href="#">qaGobiApiCbk.h</a>	Callback Service API function prototypes . . . . .	1296
<a href="#">qaGobiApiDcs.h</a>	Device Connectivity Service API function prototypes . . . . .	1391
<a href="#">qaGobiApiDms.h</a>	Device Management Service API function prototypes . . . . .	1401
<a href="#">qaGobiApiFms.h</a>	Firmware Management Service API function prototypes . . . . .	1446
<a href="#">qaGobiApiIms.h</a>	IMS Service API function prototypes . . . . .	1461
<a href="#">qaGobiApiImsa.h</a>	IMSA Service API function prototypes . . . . .	1467
<a href="#">qaGobiApiLoc.h</a>	Location API function prototypes . . . . .	1470
<a href="#">qaGobiApiNas.h</a>	Network Access Service API function prototypes . . . . .	1477
<a href="#">qaGobiApiOmadm.h</a>	Open Mobile Alliance Device Management Service API function prototypes . . . . .	1524
<a href="#">qaGobiApiPds.h</a>	Position Determination Service API function prototypes . . . . .	1528
<a href="#">qaGobiApiQos.h</a>	Quality of Service API function prototypes . . . . .	1545
<a href="#">qaGobiApiRms.h</a>	Remote Management Service API function prototypes . . . . .	1552

<a href="#">qaGobiApiSar.h</a>	
Specific Absorption Rate API function prototypes	1554
<a href="#">qaGobiApiSms.h</a>	
Short Message Service API function prototypes	1556
<a href="#">qaGobiApiSwi.h</a>	
SWI API function prototypes	1582
<a href="#">qaGobiApiSwiAudio.h</a>	
M2M Audio Service API function prototypes	1583
<a href="#">qaGobiApiSwiOmadms.h</a>	
SWI Open Mobile Alliance Device Management Service API function prototypes	
QMI Service revision 1.6	1589
<a href="#">qaGobiApiTableBandClasses.h</a>	
Network Access Service API Band Classes table	1601
<a href="#">qaGobiApiTableCallControlReturnReasons.h</a>	
Call Control Return Reasons table	1604
<a href="#">qaGobiApiTableCallEndReasons.h</a>	
Wireless Data Service Call End Reasons	1605
<a href="#">qaGobiApiTableCarrierCodes.h</a>	
Carrier Codes table	1620
<a href="#">qaGobiApiTableCodingScheme.h</a>	
Data Coding Scheme	1622
<a href="#">qaGobiApiTableGpsCapabilityCodes.h</a>	
Position Determination Service API GPS Capability Codes	1625
<a href="#">qaGobiApiTablePowerModes.h</a>	
Device Management Service API Power Modes table	1625
<a href="#">qaGobiApiTableRadioInterfaces.h</a>	
Network Access Service API Radio Interfaces table	1626
<a href="#">qaGobiApiTableRegionCodes.h</a>	
Region Codes table	1626
<a href="#">qaGobiApiTableServiceOptions.h</a>	
Voice Service Options	1627
<a href="#">qaGobiApiTableSupServiceInfoClasses.h</a>	
Voice Supplementary Service Information Classes	1629
<a href="#">qaGobiApiTableSwiAudio.h</a>	
Swi Audio related tables	1630
<a href="#">qaGobiApiTableSwiOMADMUpdateCompleteStatus.h</a>	
Update Complete Status table	1630
<a href="#">qaGobiApiTableVoiceCallEndReasons.h</a>	
Voice Service Call and supplementary services end reasons	1632
<a href="#">qaGobiApiTmd.h</a>	
Thermal Mitigation Device API function prototypes	1638
<a href="#">qaGobiApiUim.h</a>	
Uim Service API function prototypes	1640
<a href="#">qaGobiApiVoice.h</a>	
Voice Service API function prototypes	1654
<a href="#">qaGobiApiWds.h</a>	
Wireless Data Service API function prototypes	1680
<a href="#">qaNasGetRFBandInfo.h</a>	1732
<a href="#">qaNasPerformNetworkScan.h</a>	1732
<a href="#">qmerrno.h</a>	1733
<a href="#">qos.h</a>	1740
<a href="#">sms.h</a>	1751
<a href="#">SwiDataTypes.h</a>	
SWI data types	1760
<a href="#">swiloc.h</a>	1761
<a href="#">swioma.h</a>	1763
<a href="#">SWIWWANCMAPI.h</a>	1773
<a href="#">uim.h</a>	1773

<a href="#">wds.h</a>	1782
-----------------------	------





## Chapter 6

# Module Documentation

### 6.1 Device Connectivity Service (DCS)

#### Files

- file [qaGobiApiDcs.h](#)  
*Device Connectivity Service API function prototypes.*

#### 6.1.1 Detailed Description

## 6.2 Wireless Data Service (WDS)

### Files

- file [qaGobiApiTableCallEndReasons.h](#)  
*Wireless Data Service Call End Reasons.*
- file [qaGobiApiTableCarrierCodes.h](#)  
*Carrier Codes table.*
- file [qaGobiApiTableRegionCodes.h](#)  
*Region Codes table.*
- file [qaGobiApiWds.h](#)  
*Wireless Data Service API function prototypes.*

### 6.2.1 Detailed Description

## 6.3 Device Management Service (DMS)

### Files

- file [qaGobiApiTablePowerModes.h](#)  
*Device Management Service API Power Modes table.*
- file [qaGobiApiDms.h](#)  
*Device Management Service API function prototypes.*

### 6.3.1 Detailed Description

## 6.4 Network Access Service (NAS)

### Files

- file [qaGobiApiTableRadioInterfaces.h](#)  
*Network Access Service API Radio Interfaces table.*
- file [qaGobiApiTableBandClasses.h](#)  
*Network Access Service API Band Classes table.*
- file [qaGobiApiNas.h](#)  
*Network Access Service API function prototypes.*

### 6.4.1 Detailed Description

## 6.5 CallBack registration (CBK)

### Files

- file [qaGobiApiCbK.h](#)  
*Callback Service API function prototypes.*

### 6.5.1 Detailed Description

## 6.6 Short Message Service (SMS)

### Files

- file [qaGobiApiSms.h](#)  
*Short Message Service API function prototypes.*

### 6.6.1 Detailed Description

## 6.7 Position Determination Service (PDS)

### Files

- file [qaGobiApiTableGpsCapabilityCodes.h](#)  
*Position Determination Service API GPS Capability Codes.*
- file [qaGobiApiPds.h](#)  
*Position Determination Service API function prototypes.*

### 6.7.1 Detailed Description

## 6.8 Card Application Toolkit (CAT)

### Files

- file [qaGobiApiCat.h](#)  
*Card Application Toolkit API function headers.*

### 6.8.1 Detailed Description



## 6.9 Remote Management Service (RMS)

### Files

- file [qaGobiApiRms.h](#)  
*Remote Management Service API function prototypes.*

### 6.9.1 Detailed Description

## 6.10 Firmware Management Service (FMS)

### Files

- file [qaGobiApiFms.h](#)  
*Firmware Management Service API function prototypes.*

### 6.10.1 Detailed Description

## 6.11 Open Mobile Alliance Service (OMA)

### Files

- file [qaGobiApiOmadm.h](#)

*Open Mobile Alliance Device Management Service API function prototypes.*

### 6.11.1 Detailed Description

## 6.12 Specific Absorption Rate (SAR)

### Files

- file [qaGobiApiSar.h](#)  
*Specific Absorption Rate API function prototypes.*

### 6.12.1 Detailed Description

## 6.13 SWI Open Mobile Alliance Service (SWIOMA)

### Files

- file [qaGobiApiTableSwiOMADMUpdateCompleteStatus.h](#)  
*Update Complete Status table.*
- file [qaGobiApiSwiOmadms.h](#)  
*SWI Open Mobile Alliance Device Management Service API function prototypes SWI OMA-DM QMI Service revision 1.6.*

### 6.13.1 Detailed Description

## 6.14 Voice Service (VOICE)

### Files

- file [qaGobiApiTableServiceOptions.h](#)  
*Voice Service Options.*
- file [qaGobiApiTableVoiceCallEndReasons.h](#)  
*Voice Service Call and supplementary services end reasons.*
- file [qaGobiApiTableCodingScheme.h](#)  
*Data Coding Scheme.*
- file [qaGobiApiTableCallControlReturnReasons.h](#)  
*Call Control Return Reasons table.*
- file [qaGobiApiTableSupServiceInfoClasses.h](#)  
*Voice Supplementary Service Information Classes.*
- file [qaGobiApiVoice.h](#)  
*Voice Service API function prototypes.*

### 6.14.1 Detailed Description

## 6.15 Non-service specific APIs (SWI)

### Files

- file [qaGobiApiSwi.h](#)  
*SWI API function prototypes.*

### 6.15.1 Detailed Description

## 6.16 User Identity Module Service (UIM)

### Files

- file [qaGobiApiUim.h](#)  
*Uim Service API function prototypes.*

### 6.16.1 Detailed Description



## 6.17 Audio Service (AUDIO)

### Files

- file [qaGobiApiAudio.h](#)  
*Audio Service API function prototypes.*

### 6.17.1 Detailed Description

## 6.18 Quality of Service (QOS)

### Files

- file [qaGobiApiQos.h](#)  
*Quality of Service API function prototypes.*

### 6.18.1 Detailed Description

## 6.19 IMS Service (IMS)

### Files

- file [qaGobiApilms.h](#)  
*IMS Service API function prototypes.*
- file [qaGobiApilmsa.h](#)  
*IMSA Service API function prototypes.*

### 6.19.1 Detailed Description

## 6.20 SWI Audio Service(SWIAUDIO)

### Files

- file [qaGobiApiTableSwiAudio.h](#)  
*Swi Audio related tables.*
- file [qaGobiApiSwiAudio.h](#)  
*M2M Audio Service API function prototypes.*

### 6.20.1 Detailed Description

## 6.21 Location Service(LOC)

### Files

- file [qaGobiApiLoc.h](#)  
*Location API function prototypes.*

### 6.21.1 Detailed Description

## 6.22 Thermal Mitigation Device(TMD)

### Files

- file [qaGobiApiTmd.h](#)  
*Thermal Mitigation Device API function prototypes.*

### 6.22.1 Detailed Description

## Chapter 7

# Namespace Documentation

### 7.1 Tables Namespace Reference

#### 7.1.1 Detailed Description

[Tables](#) referenced in the API function headers:

- Table 1 - Call End Reason Codes The reason a call (either in process or connected) was ended. [qaGobiApiTableCallEndReasons.h](#)
- Table 2 - Carrier codes List of carrier identification codes. [qaGobiApiTableCarrierCodes.h](#)
- Table 3 - Region codes List of region identification codes. [qaGobiApiTableRegionCodes.h](#)
- Table 4 - GPS capability codes List of GPS capability codes. [qaGobiApiTableGpsCapabilityCodes.h](#)
- Table 5 - Radio Interfaces List of radio interface technologies. [qaGobiApiTableRadioInterfaces.h](#)
- Table 6 - Band classes List of band classes. [qaGobiApiTableBandClasses.h](#)
- Table 7 - Power modes List of operating modes. [qaGobiApiTablePowerModes.h](#)
- Table 8 - Service Options List of Service Options. [qaGobiApiTableServiceOptions.h](#)
- Table 9 - Voice Call End Reason List of Voice Call End Reason. [qaGobiApiTableVoiceCallEndReasons.h](#)
- Table 10 - Data Coding Scheme List of Data Coding Scheme. [qaGobiApiTableCodingScheme.h](#)
- Table 11 - Call Control Return Reasons List of Voice Call Control Return Reasons. [qaGobiApiTableCallControlReturnReasons.h](#)
- Table 12 - Supplementary Service Information Classes List of Voice Supplementary Service Information Classes. [qaGobiApiTableSupServiceInfoClasses.h](#)
- Table 13 - Audio Calibration Data Base(ACDB) Device List of ACDB devices. [qaGobiApiTableSwiAudio.h](#)
- Table 14 - PIFACE List of physical interfaces. [qaGobiApiTableSwiAudio.h](#)





## Chapter 8

# Data Structure Documentation

### 8.1 `_getIndicationRegResp` Struct Reference

#### Data Fields

- [BYTE](#) \* [pRegTransLayerInfoEvt](#)
- [BYTE](#) \* [pRegTransNWRegInfoEvt](#)
- [BYTE](#) \* [pRegCallStatInfoEvt](#)

#### 8.1.1 Detailed Description

This structure contains Get Indication Register Response parameters

##### Parameters

<i>pRegTrans-LayerInfoEvt</i>	- <ul style="list-style-type: none"><li>• Optional 1 BYTE parameter indicating registration status of transport layer information events</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - Disabled</li><li>– 0x01 - Enabled</li></ul></li><li>• function <a href="#">SLQSGetIndicationRegister()</a> returns a default value 0xFF if this parameter is allocated memory in the structure and no response is received from the device.</li></ul>
-------------------------------	--

<i>pRegTransNW-RegInfoEvt</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating registration status of transport network registration information events</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> <li>function <a href="#">SLQSGetIndicationRegister()</a> returns a default value 0xFF if this parameter is allocated memory in the structure and no response is received from the device.</li> </ul>
<i>pRegCallStat-InfoEvt</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating registration status of call status information events</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> <li>function <a href="#">SLQSGetIndicationRegister()</a> returns a default value 0xFF if this parameter is allocated memory in the structure and no response is received from the device.</li> </ul>

## 8.1.2 Field Documentation

8.1.2.1 BYTE\* [\\_getIndicationRegResp::pRegCallStatInfoEvt](#)

8.1.2.2 BYTE\* [\\_getIndicationRegResp::pRegTransLayerInfoEvt](#)

8.1.2.3 BYTE\* [\\_getIndicationRegResp::pRegTransNWRegInfoEvt](#)

## 8.2 [\\_GetProfileSettingIn](#) Struct Reference

### Data Fields

- [BYTE ProfileType](#)
- [BYTE ProfileID](#)

### 8.2.1 Detailed Description

This structure contains the input parameters for [SLQSGetProfileSettings](#)

#### Parameters

<i>ProfileType</i>	<ul style="list-style-type: none"> <li>Identifies the technology type of the profile <ul style="list-style-type: none"> <li>0x00 - 3GPP</li> <li>0x01 - 3GPP2</li> </ul> </li> </ul>
--------------------	--

<i>ProfileID</i>	<ul style="list-style-type: none"> <li>index identifying the profile</li> </ul>
------------------	---

### 8.2.2 Field Documentation

8.2.2.1 **BYTE** \_GetProfileSettingIn::ProfileID

8.2.2.2 **BYTE** \_GetProfileSettingIn::ProfileType

## 8.3 \_GetProfileSettingOut Struct Reference

### Data Fields

- [QmiProfileInfo curProfile](#)
- WORD** \* [pExtErrCode](#)

### 8.3.1 Detailed Description

This structure contains the profile settings retrieved by the API SLQSGetProfileSettings

#### Parameters

<i>curProfile</i>	<ul style="list-style-type: none"> <li>Structure containing details of the profile</li> <li>See <a href="#">QmiProfileInfo</a> for more details</li> </ul>
<i>pExtErrCode</i>	<ul style="list-style-type: none"> <li>pointer to a 2 byte extended error code</li> <li>Error code will only will be present if error code eQCWWAN_ERR_QMI_EXTENDED-INTERNAL is returned by device.</li> <li>See <a href="#">qm_wds_ds_profile_extended_err_codes</a> enum in <a href="#">qmerrno.h</a> for received error description.</li> </ul>

### 8.3.2 Field Documentation

8.3.2.1 **QmiProfileInfo** \_GetProfileSettingOut::curProfile

8.3.2.2 **WORD**\* \_GetProfileSettingOut::pExtErrCode

## 8.4 \_getResetInfoNotification Struct Reference

### Data Fields

- BYTE** type
- BYTE** source

#### 8.4.1 Detailed Description

Contains the parameters passed for SLQSSetSwiGetResetInfoCallback by the device.

## Parameters

<i>type</i>	<ul style="list-style-type: none"> <li>• type of reset or power down, possible values listed below: <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - warm</li> <li>– 2 - hard</li> <li>– 3 - crash</li> <li>– 4 - power down</li> </ul> </li> </ul>
<i>source</i>	<ul style="list-style-type: none"> <li>• entity which initiated the reset or power down, possible values listed below: <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - user requested</li> <li>– 2 - hardware switch</li> <li>– 3 - temperature critical</li> <li>– 4 - voltage critical</li> <li>– 5 - configuration update</li> <li>– 6 - LWM2M</li> <li>– 7 - OMA-DM</li> <li>– 8 - FOTA</li> </ul> </li> </ul>

## Note

None

## 8.4.2 Field Documentation

8.4.2.1 `BYTE _getResetInfoNotification::source`8.4.2.2 `BYTE _getResetInfoNotification::type`

## 8.5 \_getTransLayerInfoResp Struct Reference

## Data Fields

- `BYTE * pRegInd`
- `transLayerInfo * pTransLayerInfo`

## 8.5.1 Detailed Description

This structure contains Get Transport Layer Info Response parameters

## Parameters

<i>pRegInd</i>	- <ul style="list-style-type: none"> <li>Optional parameter indicating if transport layer is registered</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Transport layer is not registered</li> <li>0x01 - Transport layer is registered</li> </ul> </li> <li>function <a href="#">SLQSGetTransLayerInfo()</a> returns a default value 0xFF if no response is received from the device.</li> </ul>
<i>pTransLayerInfo</i>	<ul style="list-style-type: none"> <li>Pointer to structure of transLayerInfo. <ul style="list-style-type: none"> <li>Optional parameter</li> <li>See <a href="#">transLayerInfo</a> for more information</li> </ul> </li> <li>function <a href="#">SLQSGetTransLayerInfo()</a> returns a default value 0xFF for parameter values if no response is received from the device.</li> </ul>

## 8.5.2 Field Documentation

## 8.5.2.1 BYTE\* \_getTransLayerInfoResp::pRegInd

## 8.5.2.2 transLayerInfo\* \_getTransLayerInfoResp::pTransLayerInfo

## 8.6 \_getTransNWRegInfoResp Struct Reference

## Data Fields

- [BYTE](#) \* [pRegStatus](#)

## 8.6.1 Detailed Description

This structure contains transport network registration info parameter

## Parameters

<i>pRegStatus</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating transport layer network registration status</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - No service</li> <li>0x01 - In progress</li> <li>0x02 - Failed</li> <li>0x03 - Limited Service</li> <li>0x04 - Full Service</li> </ul> </li> <li>function <a href="#">SLQSGetTransNWRegInfo()</a> returns a default value 0xFF if no response is received from the device.</li> </ul>
-------------------	---

## 8.6.2 Field Documentation

### 8.6.2.1 BYTE\* \_getTransNWRegInfoResp::pRegStatus

## 8.7 \_MitigationDevInfo Struct Reference

### Data Fields

- [BYTE devicelLen](#)
- [CHAR deviceID \[255\]](#)

### 8.7.1 Detailed Description

This structure contains mitigation Level Indication request parameters

#### Parameters

<i>devicelLen</i>	<ul style="list-style-type: none"><li>• Number of sets of the following elements<ul style="list-style-type: none"><li>– deviceID</li></ul></li></ul>
<i>deviceID</i>	<ul style="list-style-type: none"><li>• Mitigation device ID</li></ul>

## 8.7.2 Field Documentation

### 8.7.2.1 CHAR \_MitigationDevInfo::deviceID[255]

### 8.7.2.2 BYTE \_MitigationDevInfo::devicelLen

## 8.8 \_modemTempNotification Struct Reference

### Data Fields

- [BYTE ModemTempState](#)
- [WORD ModemTemperature](#)

### 8.8.1 Detailed Description

Contains the parameters passed for SLQSSetModemTempCallback by the device.

## Parameters

<i>ModemTemp-State</i>	<ul style="list-style-type: none"> <li>• provides the temperature state of the modem</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - normal</li> <li>– 2 - high(warning)</li> <li>– 3 - high(critical)</li> <li>– 4 - low(critical)</li> </ul> </li> </ul>
<i>Modem-Temperature</i>	<ul style="list-style-type: none"> <li>• provides the temperature of the modem</li> </ul>

## Note

None

## 8.8.2 Field Documentation

## 8.8.2.1 WORD \_modemTempNotification::ModemTemperature

## 8.8.2.2 BYTE \_modemTempNotification::ModemTempState

## 8.9 \_packetSrvStatus Struct Reference

## Data Fields

- [qaQmiInterfaceInfo](#) \* [pQmiInterfaceInfo](#)
- [BYTE](#) connStatus
- [BYTE](#) reconfigReqd
- [WORD](#) sessionEndReason
- [WORD](#) verboseSessnEndReasonType
- [WORD](#) verboseSessnEndReason
- [BYTE](#) ipFamily
- [WORD](#) techName
- [BYTE](#) bearerID

## 8.9.1 Detailed Description

Contains the parameters passed for SLQSSetPacketSrvStatusCallback by the device.

## Parameters

<i>pQmiInterface-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaQmiInterfaceInfo</a> for more information</li> </ul>
---------------------------	---



<i>connStatus</i>	<ul style="list-style-type: none"> <li>• Current Link Status <ul style="list-style-type: none"> <li>– 1 - Disconnected</li> <li>– 2 - Connected</li> <li>– 3 - Suspended</li> <li>– 4 - Authenticating</li> </ul> </li> </ul>
<i>reconfigReqd</i>	<ul style="list-style-type: none"> <li>• Indicates if the network interface on the host needs to be reconfigured <ul style="list-style-type: none"> <li>– 0 - No need to reconfigure</li> <li>– 1 - Reconfiguration required</li> </ul> </li> </ul>
<i>sessionEnd-Reason</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason, 0xFFFF means invalid value</li> </ul>
<i>verboseSessn-EndReasonType</i>	<ul style="list-style-type: none"> <li>• Call End Reason Type <ul style="list-style-type: none"> <li>– 0 - Unspecified</li> <li>– 1 - Mobile IP</li> <li>– 2 - Internal</li> <li>– 3 - Call Manager defined</li> <li>– 6 - 3GPP Specification defined</li> <li>– 7 - PPP</li> <li>– 8 - EHRPD</li> <li>– 9 - IPv6</li> <li>– 0xFFFF - invalid value</li> </ul> </li> </ul>
<i>verboseSessn-EndReason</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for verbose Call End Reason. The values depend on verboseSessnEndReasonType parameter 0xFFFF means invalid value</li> </ul>
<i>ipFamily</i>	<ul style="list-style-type: none"> <li>• IP Family of the packet data connection <ul style="list-style-type: none"> <li>– 4 - IPv4</li> <li>– 6 - IPv6</li> <li>– 0xFF - invalid value</li> </ul> </li> </ul>

<i>techName</i>	<ul style="list-style-type: none"> <li>Technology name of the packet data connection. <ul style="list-style-type: none"> <li>32767 - CDMA</li> <li>32764 - UMTS</li> <li>30592 - EPC</li> <li>30590 - EMBMS</li> <li>30584 - Modem Link Local</li> <li>0xFFFF - invalid value EPC is a logical interface to support LTE/eHRPD handoff. Modem Link is an interface for transferring data between entities on the AP and modem.</li> </ul> </li> </ul>
<i>bearerID</i>	<ul style="list-style-type: none"> <li>Bearer ID (3GPP) or RLP ID (3GPP2) of the packet data connection 0xFF means invalid value</li> </ul>

#### Note

Any parameter not returned by the device is returned as its maximum unsigned value by the callback.

## 8.9.2 Field Documentation

8.9.2.1 **BYTE** \_packetSrvStatus::bearerID

8.9.2.2 **BYTE** \_packetSrvStatus::connStatus

8.9.2.3 **BYTE** \_packetSrvStatus::ipFamily

8.9.2.4 **qaQmiInterfaceInfo\*** \_packetSrvStatus::pQmiInterfaceInfo

8.9.2.5 **BYTE** \_packetSrvStatus::reconfigReqd

8.9.2.6 **WORD** \_packetSrvStatus::sessionEndReason

8.9.2.7 **WORD** \_packetSrvStatus::techName

8.9.2.8 **WORD** \_packetSrvStatus::verboseSessnEndReason

8.9.2.9 **WORD** \_packetSrvStatus::verboseSessnEndReasonType

## 8.10 \_qaQmi3GPP2BroadcastCfgInfo Struct Reference

### Data Fields

- [BYTE](#) activated\_ind
- [WORD](#) num\_instances
- struct [CDMABroadcastConfig](#) CDMABroadcastConfig [0x05]

### 8.10.1 Detailed Description

This structure contains the 3GPP2 Broadcast Configuration Information parameters

## Parameters

<i>activated_ind</i>	<ul style="list-style-type: none"> <li>Broadcast SMS <ul style="list-style-type: none"> <li>0x00 - Deactivated</li> <li>0x01 - Activated</li> </ul> </li> </ul>
<i>num_instances</i>	<ul style="list-style-type: none"> <li>Number of sets (N) of parameters Following each set describes one entry in the broadcast configuration table. <ul style="list-style-type: none"> <li>serviceCategory</li> <li>language</li> <li>selected</li> </ul> </li> </ul>
<i>broadcastConfig</i>	<ul style="list-style-type: none"> <li>A <a href="#">CDMABroadcastConfig</a> structure array.</li> <li>Further defined by the structure <a href="#">CDMABroadcastConfig</a></li> </ul>

## 8.10.2 Field Documentation

8.10.2.1 BYTE \_qaQmi3GPP2BroadcastCfgInfo::activated\_ind

8.10.2.2 struct CDMABroadcastConfig \_qaQmi3GPP2BroadcastCfgInfo::CDMABroadcastConfig[0x05]

8.10.2.3 WORD \_qaQmi3GPP2BroadcastCfgInfo::num\_instances

## 8.11 \_qaQmi3GPPBroadcastCfgInfo Struct Reference

## Data Fields

- BYTE [activated\\_ind](#)
- WORD [num\\_instances](#)
- struct [BroadcastConfig](#) [broadcastConfig](#) [0x05]

## 8.11.1 Detailed Description

This structure contains the 3GPP Broadcast Configuration Information parameters

## Parameters

<i>activated_ind</i>	<ul style="list-style-type: none"> <li>Broadcast SMS <ul style="list-style-type: none"> <li>0x00 - Deactivated</li> <li>0x01 - Activated</li> </ul> </li> </ul>
----------------------	---

<i>num_instances</i>	<ul style="list-style-type: none"> <li>• Number of sets (N) of parameters Following each set describes one entry in the broadcast configuration table. <ul style="list-style-type: none"> <li>– fromServiceId</li> <li>– toServiceId</li> <li>– selected</li> </ul> </li> </ul>
<i>broadcastConfig</i>	<ul style="list-style-type: none"> <li>• A <a href="#">BroadcastConfig</a> structure array.</li> <li>• Further defined by the structure <a href="#">BroadcastConfig</a></li> </ul>

## 8.11.2 Field Documentation

8.11.2.1 **BYTE** \_qaQmi3GPPBroadcastCfgInfo::activated\_ind

8.11.2.2 **struct BroadcastConfig** \_qaQmi3GPPBroadcastCfgInfo::broadcastConfig[0x05]

8.11.2.3 **WORD** \_qaQmi3GPPBroadcastCfgInfo::num\_instances

## 8.12 \_setIndicationRegReq Struct Reference

### Data Fields

- **BYTE** \* [pRegTransLayerInfoEvt](#)
- **BYTE** \* [pRegTransNWRegInfoEvt](#)
- **BYTE** \* [pRegCallStatInfoEvt](#)

### 8.12.1 Detailed Description

This structure contains Indication Register request parameters

#### Parameters

<i>pRegTransLayerInfoEvt</i>	<p>-</p> <ul style="list-style-type: none"> <li>• Optional 1 BYTE parameter indicating registration status of transport layer information events</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> <li>– NULL - No change - specifying NULL indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>
------------------------------	---

<i>pRegTransNW-RegInfoEvt</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating registration status of transport network registration information events</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> <li>NULL - No change - specifying NULL indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>
<i>pRegCallStat-InfoEvt</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating registration status of call status information events</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> <li>NULL - No change - specifying NULL indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>

## 8.12.2 Field Documentation

8.12.2.1 **BYTE\*** `_setIndicationRegReq::pRegCallStatInfoEvt`

8.12.2.2 **BYTE\*** `_setIndicationRegReq::pRegTransLayerInfoEvt`

8.12.2.3 **BYTE\*** `_setIndicationRegReq::pRegTransNWRegInfoEvt`

## 8.13 \_slqs3GPPConfigItem Struct Reference

### Data Fields

- WORD** \* `pLTEAttachProfile`
- WORD** \* `pProfileList`
- BYTE** \* `pDefaultPDNEnabled`
- BYTE** \* `p3gppRelease`
- WORD** `LTEAttachProfileListLen`
- WORD** \* `pLTEAttachProfileList`

### 8.13.1 Detailed Description

This structure contains the 3gpp Configuration Item information.

## Parameters

<i>pLTEAttach-Profile</i>	<ul style="list-style-type: none"> <li>• LTE Attach Profile <ul style="list-style-type: none"> <li>– points to a single WORD Value indicating the attached LTE Profile</li> <li>– Optional parameter with possible values 1-16 (EM/MC73xx or earlier)</li> <li>– Optional parameter with possible values 1-24 (EM/MC74xx onwards)</li> <li>– function <a href="#">SLQSGet3GPPConfigItem()</a> returns a default value 255 if no LTE Attach Profile is configured</li> </ul> </li> <li>• This setting is deprecated on MC/EM74xx</li> </ul>
<i>pProfileList</i>	<ul style="list-style-type: none"> <li>• Profile List <ul style="list-style-type: none"> <li>– an array of 4 profile configurations</li> <li>– Each element points to a single WORD value indicating profile</li> <li>– Optional parameter with possible values <ul style="list-style-type: none"> <li>* 1 - 16 (MC/EM73xx and before)</li> <li>* 1 - 24 (MC/EM74xx and onwards)</li> </ul> </li> <li>– function <a href="#">SLQSGet3GPPConfigItem()</a> returns a default value 255 if no 3gpp configuration is present</li> </ul> </li> </ul>
<i>pDefaultPDN-Enabled</i>	<ul style="list-style-type: none"> <li>• Always Connect Default PDN <ul style="list-style-type: none"> <li>– A single BYTE value indicating the status of Always connect default PDN <ul style="list-style-type: none"> <li>* 0 - disabled</li> <li>* 1 - enabled</li> </ul> </li> <li>– Optional parameter</li> <li>– function <a href="#">SLQSGet3GPPConfigItem()</a> returns a default value 255 if no 3gpp configuration is present</li> </ul> </li> </ul>
<i>p3gppRelease</i>	<ul style="list-style-type: none"> <li>• 3gpp release <ul style="list-style-type: none"> <li>– A single BYTE value indicating the 3gpp release <ul style="list-style-type: none"> <li>* 0 - Release 99</li> <li>* 1 - Release 5</li> <li>* 2 - Release 6</li> <li>* 3 - Release 7</li> <li>* 4 - Release 8</li> </ul> </li> <li>– Optional parameter</li> <li>– function <a href="#">SLQSGet3GPPConfigItem()</a> returns a default value 255 if no 3gpp configuration is present</li> </ul> </li> </ul>

<i>pLTEAttach-ProfileList</i>	<ul style="list-style-type: none"> <li>• pointer to WORD array indicating LTE Attach Profile List <ul style="list-style-type: none"> <li>– Optional parameter</li> <li>– possible values: 1-24</li> <li>– This setting is only supported for MC/EM74xx onwards</li> <li>– The new equivalent option for "pLTEAttachProfile" on 74xx modems is "pLTE-AttachProfileList". Please provide attach profiles in order of decreasing priority in this list.</li> </ul> </li> </ul>
<i>LTEAttach-ProfileListLen</i>	<ul style="list-style-type: none"> <li>• Number of element in pLTEAttachProfileList <ul style="list-style-type: none"> <li>– valid range: 0-2 <ul style="list-style-type: none"> <li>* This setting is only supported for MC/EM74xx onwards</li> </ul> </li> </ul> </li> </ul>

### 8.13.2 Field Documentation

8.13.2.1 **WORD** \_slqs3GPPConfigItem::LTEAttachProfileListLen

8.13.2.2 **BYTE\*** \_slqs3GPPConfigItem::p3gppRelease

8.13.2.3 **BYTE\*** \_slqs3GPPConfigItem::pDefaultPDNEnabled

8.13.2.4 **WORD\*** \_slqs3GPPConfigItem::pLTEAttachProfile

8.13.2.5 **WORD\*** \_slqs3GPPConfigItem::pLTEAttachProfileList

8.13.2.6 **WORD\*** \_slqs3GPPConfigItem::pProfileList

## 8.14 \_SlqsNas3GppNetworkRAT\_ Struct Reference

### Data Fields

- [WORD MCC](#)
- [WORD MNC](#)
- [BYTE RAT](#)

### 8.14.1 Detailed Description

Contain the 3GPP radio access technology information.

#### Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
------------	---

<i>MNC</i>	<ul style="list-style-type: none"> <li>• Mobile Network Code</li> </ul>
<i>RAT</i>	<ul style="list-style-type: none"> <li>• Radio Access Technology <ul style="list-style-type: none"> <li>– 0x04 - GERAN</li> <li>– 0x05 - UMTS</li> <li>– 0x08 - LTE</li> <li>– 0x09 - TD-SCDMA</li> </ul> </li> </ul>

## 8.14.2 Field Documentation

8.14.2.1 **WORD** \_SlqsNas3GppNetworkRAT\_::MCC

8.14.2.2 **WORD** \_SlqsNas3GppNetworkRAT\_::MNC

8.14.2.3 **BYTE** \_SlqsNas3GppNetworkRAT\_::RAT

## 8.15 \_slqsNetworkScanInfo Struct Reference

### Data Fields

- **BYTE** \* pNetworkInfoInstances
- struct SlqsNas3GppNetworkInfo \* pNetworkInfo
- **BYTE** \* pRATInstances
- SlqsNas3GppNetworkRAT \* pRATInfo
- **BYTE** \* pPCSDigitInstances
- struct SlqsNasPcsDigit \* pPCSDigitInfo
- **ULONG** \* pScanResult

### 8.15.1 Detailed Description

Contain the network scan information.

#### Parameters

<i>pNetworkInfo-Instances[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Upon input, maximum number of elements that the network info instance array can contain.</li> <li>• Upon successful output, the actual number of elements in the network info instance array.</li> </ul>
---------------------------------------	---



<i>pNetworkInfo</i> [O-UT]	<ul style="list-style-type: none"> <li>• Network info instance array <ul style="list-style-type: none"> <li>– See <a href="#">SlqsNas3GppNetworkInfo</a> for more information</li> </ul> </li> </ul>
<i>pRATInstances</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Upon input, maximum number of elements that the RAT info instance array can contain.</li> <li>• Upon successful output, the actual number of elements in the RAT info instance array.</li> </ul>
<i>pRATInfo</i> [OUT]	<ul style="list-style-type: none"> <li>• RAT info instance array <ul style="list-style-type: none"> <li>– See <a href="#">SlqsNas3GppNetworkRAT</a> for more information</li> </ul> </li> </ul>
<i>pPCSDigitInstances</i> [IN/O-UT]	<ul style="list-style-type: none"> <li>• Upon input, maximum number of elements that the PCS Digit info instance array can contain.</li> <li>• Upon successful output, the actual number of elements in the PCS Digit info instance array.</li> </ul>
<i>pPCSDigitInfo</i> [OUT]	<ul style="list-style-type: none"> <li>• PCS Digit info instance array <ul style="list-style-type: none"> <li>– See <a href="#">SlqsNasPcsDigit</a> for more information</li> </ul> </li> </ul>
<i>pScanResult</i> [O-UT]	<ul style="list-style-type: none"> <li>• status of network scan</li> <li>• 0x00 - scan successful</li> <li>• 0x01 - scan was aborted</li> <li>• 0x02 - scan did not complete due to a radio link failure recovery in progress</li> </ul>

## 8.15.2 Field Documentation

8.15.2.1 **struct SlqsNas3GppNetworkInfo\*** \_slqsNetworkScanInfo::pNetworkInfo

8.15.2.2 **BYTE\*** \_slqsNetworkScanInfo::pNetworkInfoInstances

8.15.2.3 **struct SlqsNasPcsDigit\*** \_slqsNetworkScanInfo::pPCSDigitInfo

8.15.2.4 **BYTE\*** \_slqsNetworkScanInfo::pPCSDigitInstances

8.15.2.5 **SlqsNas3GppNetworkRAT\*** \_slqsNetworkScanInfo::pRATInfo

8.15.2.6 **BYTE\*** \_slqsNetworkScanInfo::pRATInstances

8.15.2.7 **ULONG\*** \_slqsNetworkScanInfo::pScanResult

## 8.16 \_SLQSOMADMSessionInfo Struct Reference

### Data Fields

- [BYTE](#) \* [pStatus](#)
- [WORD](#) \* [pUpdateCompleteStatus](#)
- [BYTE](#) \* [pSeverity](#)
- [WORD](#) \* [pSourceLength](#)
- [BYTE](#) \* [pSource](#)
- [WORD](#) \* [pPkgNameLength](#)
- [BYTE](#) \* [pPkgName](#)
- [WORD](#) \* [pPkgDescLength](#)
- [BYTE](#) \* [pPkgDescription](#)
- [WORD](#) \* [pDateLength](#)
- [BYTE](#) \* [pDate](#)
- [WORD](#) \* [pTimeLength](#)
- [BYTE](#) \* [pTime](#)
- [BYTE](#) \* [pSessionType](#)
- [BYTE](#) \* [pSessionState](#)
- [WORD](#) \* [pRetryCount](#)

### 8.16.1 Detailed Description

Structure containing the OMA DM Session Info returned by the device. Also used as input parameter to specify the size of variable parameters. (ref. notes)

#### Parameters

<i>pStatus</i>	<ul style="list-style-type: none"><li>• 1 Byte parameter indicating status(optional)<ul style="list-style-type: none"><li>– 0x01 - No Firmware available</li><li>– 0x02 - Query Firmware Download</li><li>– 0x03 - Firmware Downloading</li><li>– 0x04 - Firmware Downloaded</li><li>– 0x05 - Query Firmware Update</li><li>– 0x06 - Firmware Updating</li><li>– 0x07 - Firmware Updated</li></ul></li></ul>
----------------	--

<i>pUpdate-CompleteStatus</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Update Complete Status(optional) <ul style="list-style-type: none"> <li>– See <a href="#">qaGobiApiTableSwiOMADMUpdateCompleteStatus.h</a> Update Complete Status</li> </ul> </li> </ul>
<i>pSeverity</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating severity(optional) <ul style="list-style-type: none"> <li>– 0x01 - Mandatory</li> <li>– 0x02 - Optional</li> </ul> </li> </ul>
<i>pSourceLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Vendor Name String in Bytes.(optional)</li> </ul>
<i>pSource</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Vendor Name in ASCII(optional)</li> </ul>
<i>pPkgName-Length</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Name String in Bytes.(optional)</li> </ul>
<i>pPkgName</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Name in ASCII(optional)</li> </ul>
<i>pPkgDesc-Length</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Description String in Bytes.(optional)</li> </ul>
<i>pPkgDescription</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Description in ASCII(optional)</li> </ul>
<i>pDateLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Description String in Bytes.(optional)</li> </ul>
<i>pDate</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Description in ASCII</li> </ul>
<i>pTimeLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Time String in Bytes.(optional)</li> </ul>
<i>pTime</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Time String in ASCII(optional)</li> </ul>
<i>pSessionType</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter reflects the last session started for Sprint(optional) <ul style="list-style-type: none"> <li>– 0x00 - No session since boot</li> <li>– 0x01 - Sprint CI-DC Session</li> <li>– 0x02 - Sprint CI-PRL Session</li> <li>– 0x03 - Sprint CI-FUMO Session</li> <li>– 0x04 - Sprint HFA-DC Session</li> <li>– 0x05 - Sprint HFA-PRL Session</li> <li>– 0x06 - Sprint HFA-FUMO Session</li> <li>– 0x07 - Sprint NI Session</li> </ul> </li> </ul>

<i>pSessionState</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating session state(optional) <ul style="list-style-type: none"> <li>– 0x01 - idle</li> <li>– 0x02 - active</li> <li>– 0x03 - pending</li> </ul> </li> </ul>
<i>pRetryCount</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating retries left count(optional) <ul style="list-style-type: none"> <li>– valid values 0 to 6</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

As input parameter the members pSourceLength, pPkgNameLength pPkgDescLength, pDateLength, pTimeLength have to be specified. These should contain the initialized size of pSource, pPkgName, pPkgDescription, pDate, pTime respectively.

**8.16.2 Field Documentation**

8.16.2.1 **BYTE\*** \_SLQSOMADMSessionInfo::pDate

8.16.2.2 **WORD\*** \_SLQSOMADMSessionInfo::pDateLength

8.16.2.3 **WORD\*** \_SLQSOMADMSessionInfo::pPkgDescLength

8.16.2.4 **BYTE\*** \_SLQSOMADMSessionInfo::pPkgDescription

8.16.2.5 **BYTE\*** \_SLQSOMADMSessionInfo::pPkgName

8.16.2.6 **WORD\*** \_SLQSOMADMSessionInfo::pPkgNameLength

8.16.2.7 **WORD\*** \_SLQSOMADMSessionInfo::pRetryCount

8.16.2.8 **BYTE\*** \_SLQSOMADMSessionInfo::pSessionState

8.16.2.9 **BYTE\*** \_SLQSOMADMSessionInfo::pSessionType

8.16.2.10 **BYTE\*** \_SLQSOMADMSessionInfo::pSeverity

8.16.2.11 **BYTE\*** \_SLQSOMADMSessionInfo::pSource

8.16.2.12 **WORD\*** \_SLQSOMADMSessionInfo::pSourceLength

8.16.2.13 **BYTE\*** \_SLQSOMADMSessionInfo::pStatus

8.16.2.14 BYTE\* \_SLQSOMADMSessionInfo::pTime

8.16.2.15 WORD\* \_SLQSOMADMSessionInfo::pTimeLength

8.16.2.16 WORD\* \_SLQSOMADMSessionInfo::pUpdateCompleteStatus

## 8.17 \_SLQSOMADMSettings Struct Reference

### Data Fields

- ULONG \* pOMADMEEnabled
- BYTE \* pFOTAdownload
- BYTE \* pFOTAUpdate
- BYTE \* pAutosdm
- BYTE \* pFwAutoCheck

### 8.17.1 Detailed Description

Structure containing the OMA DM settings retrieved from the device

#### Parameters

<i>pOMADM-Enabled[OUT]</i>	<ul style="list-style-type: none"> <li>• 4 byte parameter indicating OMADM service enabled             <ul style="list-style-type: none"> <li>– 0x00000001 - Client-initiated device configuration</li> <li>– 0x00000002 - Network-initiated device configuration</li> <li>– 0x00000010 - Client-initiated FUMO</li> <li>– 0x00000020 - Network-initiated FUMO</li> </ul> </li> <li>• function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFFFFFFFF in case this parameter is not returned by the modem.</li> </ul>
<i>pFOTAdownload[OUT]</i>	<ul style="list-style-type: none"> <li>• 1 Byte parameter indicating support for FOTA Automatic download             <ul style="list-style-type: none"> <li>– 0x00 - Host permission required before downloading</li> <li>– 0x01 - Automatically start downloading, no host permission required</li> <li>– 0x02 - Automatically start downloading, while not roaming</li> <li>– 0x03 - Automatically reject download</li> <li>– 0x04 - Automatically reject download with “Enterprise Reject Policy”</li> </ul> </li> <li>• function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>

<i>pFOTAUpdate[OUT]</i>	<ul style="list-style-type: none"> <li>1 byte parameter indicating FOTA Automatic update <ul style="list-style-type: none"> <li>0x00 - User permission required before updating firmware</li> <li>0x01 - No user permission required before updating firmware</li> <li>0x02 - User permission required, auto update on power up</li> </ul> </li> <li>function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>
<i>pAutosdm[OUT]</i>	<ul style="list-style-type: none"> <li>1 byte parameter indicating OMA Automatic UI Alert Response <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled Accept</li> <li>0x02 - Enabled Reject</li> </ul> </li> <li>function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>
<i>pFwAutoCheck[OUT]</i>	<ul style="list-style-type: none"> <li>Optional 1 byte parameter indicating OMA Automatic Check for Firmware Update on Power-Up Response <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> <li>function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 8.17.2 Field Documentation

8.17.2.1 **BYTE\*** \_SLQSOMADMSettings::pAutosdm

8.17.2.2 **BYTE\*** \_SLQSOMADMSettings::pFOTAdownload

8.17.2.3 **BYTE\*** \_SLQSOMADMSettings::pFOTAUpdate

8.17.2.4 **BYTE\*** \_SLQSOMADMSettings::pFwAutoCheck

8.17.2.5 **ULONG\*** \_SLQSOMADMSettings::pOMADMEabled

## 8.18 \_SLQSOMADMSettingsReqParams Struct Reference

#### Data Fields

- [BYTE](#) FOTAdownload

- [BYTE FOTAUpdate](#)
- [BYTE \\* pAutosdm](#)

### 8.18.1 Detailed Description

Structure containing the OMA DM settings to be set on the device

#### Parameters

<i>FOTAdownload</i>	<ul style="list-style-type: none"> <li>• 1 Byte parameter indicating support for FOTA Automatic download <ul style="list-style-type: none"> <li>– 0x00 - Firmware auto download FALSE</li> <li>– 0x01 - Firmware auto download TRUE</li> </ul> </li> </ul>
<i>FOTAUpdate</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating FOTA Automatic update <ul style="list-style-type: none"> <li>– 0x00 - Firmware auto update FALSE</li> <li>– 0x01 - Firmware auto update TRUE</li> </ul> </li> </ul>
<i>pAutosdm[IN]</i>	<ul style="list-style-type: none"> <li>• Optional 1 byte parameter indicating OMA Automatic UI Alert Response <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled Accept</li> <li>– 0x02 - Enabled Reject</li> </ul> </li> </ul>

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 8.18.2 Field Documentation

8.18.2.1 [BYTE \\_SLQSOMADMSettingsReqParams::FOTAdownload](#)

8.18.2.2 [BYTE \\_SLQSOMADMSettingsReqParams::FOTAUpdate](#)

8.18.2.3 [BYTE\\* \\_SLQSOMADMSettingsReqParams::pAutosdm](#)

## 8.19 \_SLQSOMADMSettingsReqParams3 Struct Reference

#### Data Fields

- [BYTE FOTAdownload](#)
- [BYTE FOTAUpdate](#)
- [BYTE \\* pAutosdm](#)
- [BYTE \\* pFwAutoCheck](#)

### 8.19.1 Detailed Description

Structure containing the OMA DM settings to be set on the device

#### Parameters

<i>FOTAdownload</i>	<ul style="list-style-type: none"> <li>• 1 Byte parameter indicating support for FOTA Automatic download <ul style="list-style-type: none"> <li>– 0x00 - Firmware auto download FALSE</li> <li>– 0x01 - Firmware auto download TRUE</li> </ul> </li> </ul>
<i>FOTAUpdate</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating FOTA Automatic update <ul style="list-style-type: none"> <li>– 0x00 - Firmware auto update FALSE</li> <li>– 0x01 - Firmware auto update TRUE</li> </ul> </li> </ul>
<i>pAutosdm[IN]</i>	<ul style="list-style-type: none"> <li>• Optional 1 byte parameter indicating OMA Automatic UI Alert Response <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled Accept</li> <li>– 0x02 - Enabled Reject</li> </ul> </li> </ul>
<i>pFwAutoCheck[IN]</i>	<ul style="list-style-type: none"> <li>• Optional 1 byte parameter indicating OMA Automatic Check for Firmware Update on Power-Up Response <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> </ul> </li> </ul>

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 8.19.2 Field Documentation

8.19.2.1 **BYTE** \_SLQSOMADMSettingsReqParams3::FOTAdownload

8.19.2.2 **BYTE** \_SLQSOMADMSettingsReqParams3::FOTAUpdate

8.19.2.3 **BYTE\*** \_SLQSOMADMSettingsReqParams3::pAutosdm

8.19.2.4 **BYTE\*** \_SLQSOMADMSettingsReqParams3::pFwAutoCheck

## 8.20 \_SLQSSwiGetHostDevInfoParams Struct Reference



## Data Fields

- [BYTE bManSize](#)
- [CHAR \\* pManString](#)
- [BYTE bModelSize](#)
- [CHAR \\* pModelString](#)
- [BYTE bSWVerSize](#)
- [CHAR \\* pSWVerString](#)
- [BYTE bPlasmaIDSize](#)
- [CHAR \\* pPlasmaIDString](#)

### 8.20.1 Detailed Description

This structure is used to Get Host Device Information

#### Parameters

<i>bManSize</i> [IN/O- UT]	<ul style="list-style-type: none"> <li>• Host Device Manufacturer String Size</li> </ul>
<i>pManString</i> [OU- T]	<ul style="list-style-type: none"> <li>• Host Device Manufacturer Name(Optional parameter)</li> <li>• Null terminated ASCII String</li> </ul>
<i>bModelSize</i> [IN/- OUT]	<ul style="list-style-type: none"> <li>• Host Device Model String Size</li> </ul>
<i>pModelString</i> [O- UT]	<ul style="list-style-type: none"> <li>• Host Device Model String(Optional parameter)</li> <li>• Null terminated ASCII string.</li> </ul>
<i>bSWVerSize</i> [IN/- OUT]	<ul style="list-style-type: none"> <li>• Host Device Software Version String Size</li> </ul>
<i>pSWVerString</i> [- OUT]	<ul style="list-style-type: none"> <li>• Host Device Software Version String(Optional parameter)</li> <li>• Null terminated ASCII string</li> </ul>
<i>bPlasmaIDSize</i> [- IN/OUT]	<ul style="list-style-type: none"> <li>• Host Device Plasma ID String Size</li> </ul>
<i>pPlasmaID- String</i> [OUT]	<ul style="list-style-type: none"> <li>• Host Device Plasma ID String(Optional parameter)</li> <li>• Null terminated alphanumeric ASCII String.</li> </ul>

### 8.20.2 Field Documentation

#### 8.20.2.1 BYTE \_SLQSSwiGetHostDevInfoParams::bManSize

8.20.2.2 **BYTE** \_SLQSSwiGetHostDevInfoParams::bModelSize

8.20.2.3 **BYTE** \_SLQSSwiGetHostDevInfoParams::bPlasmaIDSize

8.20.2.4 **BYTE** \_SLQSSwiGetHostDevInfoParams::bSWVerSize

8.20.2.5 **CHAR\*** \_SLQSSwiGetHostDevInfoParams::pManString

8.20.2.6 **CHAR\*** \_SLQSSwiGetHostDevInfoParams::pModelString

8.20.2.7 **CHAR\*** \_SLQSSwiGetHostDevInfoParams::pPlasmaIDString

8.20.2.8 **CHAR\*** \_SLQSSwiGetHostDevInfoParams::pSWVerString

## 8.21 \_SLQSSwiGetOSInfoParams Struct Reference

### Data Fields

- [BYTE bNameSize](#)
- [CHAR \\* pNameString](#)
- [BYTE bVersionSize](#)
- [CHAR \\* pVersionString](#)

### 8.21.1 Detailed Description

This structure is used to Get OS Information

#### Parameters

<i>bNameSize</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>• Size of Operating System Name</li> </ul>
<i>pNameString</i> [OUT]	<ul style="list-style-type: none"> <li>• Operating System Name(Optional parameter)</li> <li>• Null terminated ASCII string</li> </ul>
<i>bVersionSize</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>• Operating System Version Size</li> </ul>
<i>pVersionString</i> [OUT]	<ul style="list-style-type: none"> <li>• Operating System Version String(Optional parameter)</li> <li>• Null terminated ASCII string.</li> </ul>

### 8.21.2 Field Documentation

8.21.2.1 **BYTE** \_SLQSSwiGetOSInfoParams::bNameSize

8.21.2.2 **BYTE** \_SLQSSwiGetOSInfoParams::bVersionSize

8.21.2.3 **CHAR\*** \_SLQSSwiGetOSInfoParams::pNameString

## 8.21.2.4 CHAR\* \_SLQSSwiGetOSInfoParams::pVersionString

## 8.22 \_SLQSSwiGetSerialNoExtParams Struct Reference

## Data Fields

- [BYTE meidLength](#)
- [CHAR \\* pMeidString](#)

## 8.22.1 Detailed Description

This structure is used to store MEID Information

## Parameters

<i>meidLength</i> [OU- T]	<ul style="list-style-type: none"> <li>• String length of the of MEID received</li> </ul>
<i>pMeidString</i> [OU- T]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to receive String containing the Mobile Equipment Identifier(MEID) of the device.</li> </ul>

## 8.22.2 Field Documentation

## 8.22.2.1 BYTE \_SLQSSwiGetSerialNoExtParams::meidLength

## 8.22.2.2 CHAR\* \_SLQSSwiGetSerialNoExtParams::pMeidString

## 8.23 \_SLQSSwiSetHostDevInfoParams Struct Reference

## Data Fields

- [BYTE bManSize](#)
- [CHAR \\* pManString](#)
- [BYTE bModelSize](#)
- [CHAR \\* pModelString](#)
- [BYTE bSWVerSize](#)
- [CHAR \\* pSWVerString](#)
- [BYTE bPlasmaIDSize](#)
- [CHAR \\* pPlasmaIDString](#)

## 8.23.1 Detailed Description

This structure is used to Set Host Device Information

## Parameters

<i>bManSize[IN]</i>	<ul style="list-style-type: none"> <li>• Host Device Manufacturer String Size</li> </ul>
<i>pManString[IN]</i>	<ul style="list-style-type: none"> <li>• Host Device Manufacturer Name(Optional parameter)</li> <li>• Null terminated ASCII String</li> </ul>
<i>bModelSize[IN]</i>	<ul style="list-style-type: none"> <li>• Host Device Model String Size</li> </ul>
<i>pModelString[IN]</i>	<ul style="list-style-type: none"> <li>• Host Device Model String(Optional parameter)</li> <li>• Null terminated ASCII string.</li> </ul>
<i>bSWVerSize[IN]</i>	<ul style="list-style-type: none"> <li>• Host Device Software Version String Size</li> </ul>
<i>pSWVerString[IN]</i>	<ul style="list-style-type: none"> <li>• Host Device Software Version String(Optional parameter)</li> <li>• Null terminated ASCII string</li> </ul>
<i>bPlasmaIDSize[IN]</i>	<ul style="list-style-type: none"> <li>• Host Device Plasma ID String Size</li> </ul>
<i>pPlasmaIDString[IN]</i>	<ul style="list-style-type: none"> <li>• Host Device Plasma ID String(Optional parameter)</li> <li>• Null terminated alphanumeric ASCII String.</li> </ul>

## 8.23.2 Field Documentation

8.23.2.1 **BYTE** \_SLQSSwiSetHostDevInfoParams::bManSize

8.23.2.2 **BYTE** \_SLQSSwiSetHostDevInfoParams::bModelSize

8.23.2.3 **BYTE** \_SLQSSwiSetHostDevInfoParams::bPlasmaIDSize

8.23.2.4 **BYTE** \_SLQSSwiSetHostDevInfoParams::bSWVerSize

8.23.2.5 **CHAR\*** \_SLQSSwiSetHostDevInfoParams::pManString

8.23.2.6 **CHAR\*** \_SLQSSwiSetHostDevInfoParams::pModelString

8.23.2.7 **CHAR\*** \_SLQSSwiSetHostDevInfoParams::pPlasmaIDString

8.23.2.8 **CHAR\*** \_SLQSSwiSetHostDevInfoParams::pSWVerString

## 8.24 \_SLQSSwiSetOSInfoParams Struct Reference

## Data Fields

- [BYTE bNameSize](#)
- [CHAR \\* pNameString](#)
- [BYTE bVersionSize](#)
- [CHAR \\* pVersionString](#)

## 8.24.1 Detailed Description

This structure is used to Set OS Information

## Parameters

<i>bNameSize</i> [IN]	<ul style="list-style-type: none"> <li>• Size of Operating System Name</li> </ul>
<i>pNameString</i> [IN]	<ul style="list-style-type: none"> <li>• Operating System Name(Optional parameter)</li> <li>• Null terminated ASCII string</li> </ul>
<i>bVersionSize</i> [IN]	<ul style="list-style-type: none"> <li>• Operating System Version Size</li> </ul>
<i>pVersionString</i> [I- N]	<ul style="list-style-type: none"> <li>• Operating System Version String(Optional parameter)</li> <li>• Null terminated ASCII string.</li> </ul>

## 8.24.2 Field Documentation

8.24.2.1 [BYTE \\_SLQSSwiSetOSInfoParams::bNameSize](#)

8.24.2.2 [BYTE \\_SLQSSwiSetOSInfoParams::bVersionSize](#)

8.24.2.3 [CHAR\\* \\_SLQSSwiSetOSInfoParams::pNameString](#)

8.24.2.4 [CHAR\\* \\_SLQSSwiSetOSInfoParams::pVersionString](#)

## 8.25 \_sysSelectPrefInfo Struct Reference

## Data Fields

- [BYTE \\* pEmerMode](#)
- [WORD \\* pModePref](#)
- [ULONGLONG \\* pBandPref](#)
- [WORD \\* pPRLPref](#)
- [WORD \\* pRoamPref](#)
- [ULONGLONG \\* pLTEBandPref](#)
- [BYTE \\* pNetSelPref](#)
- [ULONG \\* pSrvDomainPref](#)
- [ULONG \\* pGWAcqOrderPref](#)

### 8.25.1 Detailed Description

Structure for storing the current preferred system selection settings for the device.

## Parameters

<i>pEmerMode</i>	<ul style="list-style-type: none"> <li>Optional parameter specifying the emergency Mode</li> <li>Values: <ul style="list-style-type: none"> <li>0 - OFF (normal)</li> <li>1 - ON (Emergency)</li> </ul> </li> <li>function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FF if no value is returned by the device.</li> </ul>
<i>pModePref</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Bit Mask indicating the radio technology mode preference</li> <li>Bit values: <ul style="list-style-type: none"> <li>Bit 0 - cdma2000 1x</li> <li>Bit 1 - cdma2000 HRPD(1xEV-DO)</li> <li>Bit 2 - GSM</li> <li>Bit 3 - UMTS</li> <li>Bit 4 - LTE</li> </ul> </li> <li>function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FF if no value is returned by the device.</li> </ul>
<i>pBandPref</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Bit mask representing the band preference</li> <li>Bit values: <ul style="list-style-type: none"> <li>Bit 0 - Band Class 0, A-System</li> <li>Bit 1 - Band Class 0, B-System, Band Class 0 AB, GSM 850 Band</li> <li>Bit 2 - Band Class 1, all blocks</li> <li>Bit 3 - Band Class 2 place holder</li> <li>Bit 4 - Band Class 3, A-System</li> <li>Bit 5 - Band Class 4, all blocks</li> <li>Bit 6 - Band Class 5, all blocks</li> <li>Bit 7 - GSM_DCS_1800 band</li> <li>Bit 8 - GSM Extended GSM (E-GSM) 900 band</li> <li>Bit 9 - GSM Primary GSM (P-GSM) 900 band</li> <li>Bit 10 - Band Class 6</li> <li>Bit 11 - Band Class 7</li> <li>Bit 12 - Band Class 8</li> <li>Bit 13 - Band Class 9</li> <li>Bit 14 - Band Class 10</li> <li>Bit 15 - Band Class 11</li> <li>Bit 16 - GSM 450 band</li> <li>Bit 17 - GSM 480 band</li> <li>Bit 18 - GSM 750 band</li> <li>Bit 19 - GSM 850 band</li> <li>Bit 20 - GSM Railways GSM 900 Band</li> <li>Bit 21 - GSM PCS 1900 band</li> </ul> </li> </ul>

<i>pRoamPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating the roaming Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - Acquire only systems for which the roaming indicator is off</li> <li>– 0x02 - Acquire a system as long as its roaming indicator is not off</li> <li>– 0x03 - Acquire only systems for which the roaming indicator is off or solid on, i.e. not flashing; CDMA only</li> <li>– 0xFF - Acquire systems, regardless of their roaming indicator</li> </ul> </li> <li>• function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFF if no value is returned by the device.</li> </ul>
<i>pLTEBandPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit mask representing the LTE band preference</li> <li>• Bit Values <ul style="list-style-type: none"> <li>– Bit 0 - E-UTRA Operating Band 1</li> <li>– Bit 1 - E-UTRA Operating Band 2</li> <li>– Bit 2 - E-UTRA Operating Band 3</li> <li>– Bit 3 - E-UTRA Operating Band 4</li> <li>– Bit 4 - E-UTRA Operating Band 5</li> <li>– Bit 5 - E-UTRA Operating Band 6</li> <li>– Bit 6 - E-UTRA Operating Band 7</li> <li>– Bit 7 - E-UTRA Operating Band 8</li> <li>– Bit 8 - E-UTRA Operating Band 9</li> <li>– Bit 9 - E-UTRA Operating Band 10</li> <li>– Bit 10 - E-UTRA Operating Band 11</li> <li>– Bit 11 - E-UTRA Operating Band 12</li> <li>– Bit 12 - E-UTRA Operating Band 13</li> <li>– Bit 13 - E-UTRA Operating Band 14</li> <li>– Bit 16 - E-UTRA Operating Band 17</li> <li>– Bit 17 - E-UTRA Operating Band 18</li> <li>– Bit 18 - E-UTRA Operating Band 19</li> <li>– Bit 19 - E-UTRA Operating Band 20</li> <li>– Bit 20 - E-UTRA Operating Band 21</li> <li>– Bit 32 - E-UTRA Operating Band 33</li> <li>– Bit 33 - E-UTRA Operating Band 34</li> <li>– Bit 34 - E-UTRA Operating Band 35</li> <li>– Bit 35 - E-UTRA Operating Band 36</li> <li>– Bit 36 - E-UTRA Operating Band 37</li> <li>– Bit 37 - E-UTRA Operating Band 38</li> <li>– Bit 38 - E-UTRA Operating Band 39</li> <li>– Bit 39 - E-UTRA Operating Band 40</li> <li>– All other bits are reserved</li> </ul> </li> <li>• function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFFFFFFFFFFFFFF if no value is returned by the device.</li> </ul>
	<p>Generated on Tue Jul 12 2016 10:59:49 for LinuxQMSDK by Doxygen</p>



<i>pNetSelPref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating network selection preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Automatic network selection</li> <li>0x01 - Manual network selection</li> </ul> </li> <li>function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FF if no value is returned by the device.</li> </ul>
<i>pSrvDomainPref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Service domain preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Circuit switched only</li> <li>0x01 - Packet switched only</li> <li>0x02 - Circuit switched and packet switched</li> <li>0x03 - Packet switched attach</li> <li>0x04 - Packet switched detach</li> </ul> </li> <li>function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFFFFFF if no value is returned by the device.</li> </ul>
<i>pGWAcqOrder-Pref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating GSM/WCDMA Acquisition order Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Automatic</li> <li>0x01 - GSM then WCDMA</li> <li>0x02 - WCDMA then GSM</li> </ul> </li> <li>function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFFFFFF if no value is returned by the device.</li> </ul>

## Note

None

## 8.25.2 Field Documentation

8.25.2.1 ULONGLONG\* \_sysSelectPrefInfo::pBandPref

8.25.2.2 BYTE\* \_sysSelectPrefInfo::pEmerMode

8.25.2.3 ULONG\* \_sysSelectPrefInfo::pGWAcqOrderPref

8.25.2.4 ULONGLONG\* \_sysSelectPrefInfo::pLTEBandPref

8.25.2.5 WORD\* \_sysSelectPrefInfo::pModePref

8.25.2.6 BYTE\* \_sysSelectPrefInfo::pNetSelPref

8.25.2.7 **WORD**\* \_sysSelectPrefInfo::pPRLPref

8.25.2.8 **WORD**\* \_sysSelectPrefInfo::pRoamPref

8.25.2.9 **ULONG**\* \_sysSelectPrefInfo::pSrvDomainPref

## 8.26 \_sysSelectPrefParams Struct Reference

### Data Fields

- **BYTE**\* pEmerMode
- **WORD**\* pModePref
- **ULONGLONG**\* pBandPref
- **WORD**\* pPRLPref
- **WORD**\* pRoamPref
- **ULONGLONG**\* pLTEBandPref
- **struct netSelectionPref**\* pNetSelPref
- **BYTE**\* pChgDuration
- **BYTE**\* pMNCIncPCSDigStat
- **ULONG**\* pSrvDomainPref
- **ULONG**\* pGWAcqOrderPref
- **ULONGLONG**\* pTdsdmaBandPref
- **struct acqOrderPref**\* pAcqOrderPref
- **ULONG**\* pSrvRegRestriction
- **struct CSGID**\* pCSGID
- **BYTE**\* pRAT

### 8.26.1 Detailed Description

Contain the system selection preferences.

## Parameters

<i>pEmerMode</i>	<ul style="list-style-type: none"> <li>Optional parameter specifying the emergency Mode</li> <li>Values: <ul style="list-style-type: none"> <li>0 - OFF (normal)</li> <li>1 - ON (Emergency)</li> </ul> </li> </ul>
<i>pModePref</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Bit Mask indicating the radio technology mode preference</li> <li>Bit values: <ul style="list-style-type: none"> <li>Bit 0 - cdma2000 1x</li> <li>Bit 1 - cdma2000 HRPD(1xEV-DO)</li> <li>Bit 2 - GSM</li> <li>Bit 3 - UMTS</li> <li>Bit 4 - LTE</li> </ul> </li> </ul>
<i>pBandPref</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Bit mask representing the band preference</li> <li>Bit values: <ul style="list-style-type: none"> <li>Bit 0 - Band Class 0, A-System</li> <li>Bit 1 - Band Class 0, B-System, Band Class 0 AB, GSM 850 Band</li> <li>Bit 2 - Band Class 1, all blocks</li> <li>Bit 3 - Band Class 2 place holder</li> <li>Bit 4 - Band Class 3, A-System</li> <li>Bit 5 - Band Class 4, all blocks</li> <li>Bit 6 - Band Class 5, all blocks</li> <li>Bit 7 - GSM_DCS_1800 band</li> <li>Bit 8 - GSM Extended GSM (E-GSM) 900 band</li> <li>Bit 9 - GSM Primary GSM (P-GSM) 900 band</li> <li>Bit 10 - Band Class 6</li> <li>Bit 11 - Band Class 7</li> <li>Bit 12 - Band Class 8</li> <li>Bit 13 - Band Class 9</li> <li>Bit 14 - Band Class 10</li> <li>Bit 15 - Band Class 11</li> <li>Bit 16 - GSM 450 band</li> <li>Bit 17 - GSM 480 band</li> <li>Bit 18 - GSM 750 band</li> <li>Bit 19 - GSM 850 band</li> <li>Bit 20 - GSM Railways GSM 900 Band</li> <li>Bit 21 - GSM PCS 1900 band</li> <li>Bit 22 - WCDMA Europe, Japan, and China IMT 2100 band</li> <li>Bit 23 - WCDMA U.S. PCS 1900 band</li> <li>Bit 24 - WCDMA Europe and China DCS 1800 band</li> </ul> </li> </ul>

<i>pPRLPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating the CDMA PRL Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x0001 - Acquire available system only on the A side</li> <li>– 0x0002 - Acquire available system only on the B side</li> <li>– 0x3FFF - Acquire any available systems</li> </ul> </li> </ul>
<i>pRoamPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating the roaming Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - Acquire only systems for which the roaming indicator is off</li> <li>– 0x02 - Acquire a system as long as its roaming indicator is not off</li> <li>– 0x03 - Acquire only systems for which the roaming indicator is off or solid on, i.e. not flashing; CDMA only</li> <li>– 0xFF - Acquire systems, regardless of their roaming indicator</li> </ul> </li> </ul>
<i>pLTEBandPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit mask representing the LTE band preference</li> <li>• Bit Values <ul style="list-style-type: none"> <li>– Bit 0 - E-UTRA Operating Band 1</li> <li>– Bit 1 - E-UTRA Operating Band 2</li> <li>– Bit 2 - E-UTRA Operating Band 3</li> <li>– Bit 3 - E-UTRA Operating Band 4</li> <li>– Bit 4 - E-UTRA Operating Band 5</li> <li>– Bit 5 - E-UTRA Operating Band 6</li> <li>– Bit 6 - E-UTRA Operating Band 7</li> <li>– Bit 7 - E-UTRA Operating Band 8</li> <li>– Bit 8 - E-UTRA Operating Band 9</li> <li>– Bit 9 - E-UTRA Operating Band 10</li> <li>– Bit 10 - E-UTRA Operating Band 11</li> <li>– Bit 11 - E-UTRA Operating Band 12</li> <li>– Bit 12 - E-UTRA Operating Band 13</li> <li>– Bit 13 - E-UTRA Operating Band 14</li> <li>– Bit 16 - E-UTRA Operating Band 17</li> <li>– Bit 17 - E-UTRA Operating Band 18</li> <li>– Bit 18 - E-UTRA Operating Band 19</li> <li>– Bit 19 - E-UTRA Operating Band 20</li> <li>– Bit 20 - E-UTRA Operating Band 21</li> <li>– Bit 32 - E-UTRA Operating Band 33</li> <li>– Bit 33 - E-UTRA Operating Band 34</li> <li>– Bit 34 - E-UTRA Operating Band 35</li> <li>– Bit 35 - E-UTRA Operating Band 36</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– Bit 36 - E-UTRA Operating Band 37</li> <li>– Bit 37 - E-UTRA Operating Band 38</li> <li>– Bit 38 - E-UTRA Operating Band 39</li> <li>– Bit 39 - E-UTRA Operating Band 40</li> </ul>

<i>pNetSelPref</i>	<p>- <a href="#">netSelectionPref</a></p> <ul style="list-style-type: none"> <li>• Optional parameter for specifying Network Selection Preference</li> <li>• Modem selects networks based on this parameter(if present).</li> <li>• Either of pNetSelPref or pCSGID can be set.</li> <li>• see <a href="#">netSelectionPref</a> for more information</li> </ul>
<i>pChgDuration</i>	<ul style="list-style-type: none"> <li>• Optional parameter specifying the duration of the change</li> <li>• At least one system selection setting to be set if pChgDuration is populated.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Power cycle - Remains active until the next device power cycle</li> <li>– 0x01 - Permanent - Remains active through power cycles until changed by client</li> <li>– Device will use "0x01 - permanent" as default if this parameter is omitted</li> </ul> </li> </ul>
<i>pMNCIncPCS-DigStat</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating if MNC includes PCS digit</li> <li>• pNetSelPref is expected if MNC includes PCS digit is set to 1.</li> <li>• Values: <ul style="list-style-type: none"> <li>– TRUE - MNC is a 3 digit value; e.g., a reported value of 90 corresponds to an MNC value of 090</li> <li>– FALSE - MNC is a 2-digit value; e.g., a reported value of 90 corresponds to an MNC value of 90</li> </ul> </li> </ul>
<i>pSrvDomainPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating Service domain preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Circuit switched only</li> <li>– 0x01 - Packet switched only</li> <li>– 0x02 - Circuit switched and packet switched</li> <li>– 0x03 - Packet switched attach</li> <li>– 0x04 - Packet switched detach</li> </ul> </li> </ul>

<i>pGWAcqOrder-Pref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating GSM/WCDMA Acquisition order Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Automatic</li> <li>0x01 - GSM then WCDMA</li> <li>0x02 - WCDMA then GSM</li> </ul> </li> </ul>
<i>pTdsdmaBand-Pref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating bitmask representing the TD-SCDMA band preference to be set.</li> <li>Values: <ul style="list-style-type: none"> <li>0x01 - TD-SCDMA Band A</li> <li>0x02 - TD-SCDMA Band B</li> <li>0x04 - TD-SCDMA Band C</li> <li>0x08 - TD-SCDMA Band D</li> <li>0x10 - TD-SCDMA Band E</li> <li>0x20 - TD-SCDMA Band F</li> <li>All other bits are reserved</li> </ul> </li> </ul>
<i>pAcqOrderPref</i>	<ul style="list-style-type: none"> <li>- <a href="#">acqOrderPref</a></li> <li>Optional parameter for specifying Acquisition Order Preference</li> <li>see <a href="#">acqOrderPref</a> for more information</li> </ul>
<i>pSrvReg-Restriction</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Network Selection Registration Restriction Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Device follows the normal registration process</li> <li>0x01 - Device camps on the network according to its provisioning, but does not register</li> <li>0x02 - Device selects the network for limited service</li> <li>All other values are reserved.</li> </ul> </li> </ul>

<i>pCSGID</i>	- <a href="#">CSGID</a> <ul style="list-style-type: none"> <li>• Optional parameter for specifying CSG ID</li> <li>• Either of pNetSelPref or pCSGID can be set.</li> <li>• see <a href="#">CSGID</a> for more information</li> </ul>
<i>pRAT</i>	<ul style="list-style-type: none"> <li>• Optional parameter Radio Access Technology order Preference</li> <li>• Values:             <ul style="list-style-type: none"> <li>– 0x04 - GSM</li> <li>– 0x05 - UMTS</li> <li>– 0x08 - LTE</li> <li>– 0x09 - TDSCDMA</li> </ul> </li> </ul>

## 8.26.2 Field Documentation

8.26.2.1 `struct acqOrderPref* _sysSelectPrefParams::pAcqOrderPref`

8.26.2.2 `ULONGLONG* _sysSelectPrefParams::pBandPref`

8.26.2.3 `BYTE* _sysSelectPrefParams::pChgDuration`

8.26.2.4 `struct CSGID* _sysSelectPrefParams::pCSGID`

8.26.2.5 `BYTE* _sysSelectPrefParams::pEmerMode`

8.26.2.6 `ULONG* _sysSelectPrefParams::pGWAcqOrderPref`

8.26.2.7 `ULONGLONG* _sysSelectPrefParams::pLTEBandPref`

8.26.2.8 `BYTE* _sysSelectPrefParams::pMNCIncPCSDigStat`

8.26.2.9 `WORD* _sysSelectPrefParams::pModePref`

8.26.2.10 `struct netSelectionPref* _sysSelectPrefParams::pNetSelPref`

8.26.2.11 `WORD* _sysSelectPrefParams::pPRLPref`

8.26.2.12 `BYTE* _sysSelectPrefParams::pRAT`

8.26.2.13 `WORD* _sysSelectPrefParams::pRoamPref`

8.26.2.14 `ULONG* _sysSelectPrefParams::pSrvDomainPref`

8.26.2.15 `ULONG* _sysSelectPrefParams::pSrvRegRestriction`

8.26.2.16 `ULONGLONG* _sysSelectPrefParams::pTdsdmaBandPref`

## 8.27 \_transLayerinfo Struct Reference

## Data Fields

- [BYTE TransType](#)
- [BYTE TransCap](#)

### 8.27.1 Detailed Description

This structure contains Transport Layer Information

#### Parameters

<i>TransType</i>	<ul style="list-style-type: none"> <li>• Transport Type <ul style="list-style-type: none"> <li>– 0x00 - IMS</li> </ul> </li> </ul>
<i>TransCap</i>	<ul style="list-style-type: none"> <li>• Transport Capability</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - CDMA</li> <li>– 0x01 - GW</li> </ul> </li> </ul>

### 8.27.2 Field Documentation

#### 8.27.2.1 `BYTE _transLayerinfo::TransCap`

#### 8.27.2.2 `BYTE _transLayerinfo::TransType`

## 8.28 `_transLayerInfoNotification` Struct Reference

## Data Fields

- [BYTE regInd](#)
- [transLayerInfo \\* pTransLayerInfo](#)

### 8.28.1 Detailed Description

Contains the parameters passed for `SLQSSetTransLayerInfoCallback` by the device.



## Parameters

<i>regInd</i>	<ul style="list-style-type: none"> <li>Indicates whether the transport layer is registered or not</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Transport layer is not registered</li> <li>0x01 - Transport layer is registered</li> </ul> </li> </ul>
<i>pTransLayerInfo</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>See <a href="#">transLayerInfo</a> for more information</li> </ul>

## Note

None

## 8.28.2 Field Documentation

8.28.2.1 [transLayerInfo\\*](#) \_transLayerInfoNotification::pTransLayerInfo8.28.2.2 [BYTE](#) \_transLayerInfoNotification::regInd

## 8.29 \_transNWRegInfoNotification Struct Reference

## Data Fields

- [BYTE](#) NWRegStat

## 8.29.1 Detailed Description

Contains the parameters passed for SLQSSetTransNWRegInfoCallback by the device.

## Parameters

<i>NWRegStat</i>	<ul style="list-style-type: none"> <li>provides the transport network registration information</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - No Service</li> <li>0x01 - In Progress</li> <li>0x02 - Failed</li> <li>0x03 - Limited Service</li> <li>0x04 - Full Service</li> </ul> </li> </ul>
------------------	---

## Note

None

## 8.29.2 Field Documentation

### 8.29.2.1 BYTE \_transNWRegInfoNotification::NWRegStat

## 8.30 accelAcceptReady\_s Struct Reference

### Data Fields

- [BYTE injectEnable](#)
- [WORD samplesPerBatch](#)
- [WORD batchPerSec](#)

### 8.30.1 Detailed Description

This structure contains Accelerometer Accept Ready Info

#### Parameters

<i>injectEnable</i>	<ul style="list-style-type: none"> <li>• GNSS location engine is ready to accept data from sensor.</li> <li>• Values</li> <li>• 0x01 - Ready to accept sensor data</li> <li>• 0x00 - Not ready to accept sensor data</li> </ul>
<i>samplesPerBatch</i>	<ul style="list-style-type: none"> <li>• number of samples per batch the GNSS location engine is to receive.</li> <li>• <math>\text{samplingFrequency} = \text{samplesPerBatch} * \text{batchesPerSecond}</math></li> <li>• samplesPerBatch must be a nonzero positive value.</li> </ul>
<i>batchPerSec</i>	<ul style="list-style-type: none"> <li>• LTE NAS version minor</li> <li>• Number of sensor-data batches the GNSS location engine is to receive per second.</li> <li>• BatchesPerSecond must be a nonzero positive value.</li> </ul>

## 8.30.2 Field Documentation

### 8.30.2.1 WORD accelAcceptReady\_s::batchPerSec

### 8.30.2.2 BYTE accelAcceptReady\_s::injectEnable

### 8.30.2.3 WORD accelAcceptReady\_s::samplesPerBatch

## 8.31 accelTempAcceptReady\_s Struct Reference

### Data Fields

- [BYTE injectEnable](#)
- [WORD samplesPerBatch](#)

- [WORD batchPerSec](#)

### 8.31.1 Detailed Description

This structure contains Accelerometer Temperature Accept Ready Info

#### Parameters

<i>injectEnable</i>	<ul style="list-style-type: none"> <li>• GNSS location engine is ready to accept data from sensor.</li> <li>• Values</li> <li>• 0x01 - Ready to accept sensor data</li> <li>• 0x00 - Not ready to accept sensor data</li> </ul>
<i>samplesPerBatch</i>	<ul style="list-style-type: none"> <li>• number of samples per batch the GNSS location engine is to receive.</li> <li>• <math>\text{samplingFrequency} = \text{samplesPerBatch} * \text{batchesPerSecond}</math></li> <li>• samplesPerBatch must be a nonzero positive value.</li> </ul>
<i>batchPerSec</i>	<ul style="list-style-type: none"> <li>• LTE NAS version minor</li> <li>• Number of sensor-data batches the GNSS location engine is to receive per second.</li> <li>• BatchesPerSecond must be a nonzero positive value.</li> </ul>

### 8.31.2 Field Documentation

8.31.2.1 **WORD** accelTempAcceptReady\_s::batchPerSec

8.31.2.2 **BYTE** accelTempAcceptReady\_s::injectEnable

8.31.2.3 **WORD** accelTempAcceptReady\_s::samplesPerBatch

## 8.32 acqOrderPref Struct Reference

#### Data Fields

- [BYTE acqOrdeLen](#)
- [BYTE \\* pAcqOrder](#)

### 8.32.1 Detailed Description

Contain the Acquisition Order Preference.

#### Parameters

<i>acqOrdeLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements.</li> </ul>
<i>pAcqOrder</i>	<ul style="list-style-type: none"> <li>• Acquisition order preference to be set. Values: <ul style="list-style-type: none"> <li>– 0x01 - NAS_RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - NAS_RADIO_IF_CDMA_1xEVDO - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x04 - NAS_RADIO_IF_GSM - GSM</li> <li>– 0x05 - NAS_RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - NAS_RADIO_IF_LTE - LTE</li> <li>– 0x09 - NAS_RADIO_IF_TDSCDMA - TD-SCDMA</li> </ul> </li> </ul>

### 8.32.2 Field Documentation

8.32.2.1 **BYTE** acqOrderPref::acqOrdeLen

8.32.2.2 **BYTE\*** acqOrderPref::pAcqOrder

## 8.33 ActPilotPNElement Struct Reference

### Data Fields

- [WORD ActSetPilotPN](#)
- [BYTE ActSetPilotPNStrength](#)

### 8.33.1 Detailed Description

This structure describes Active Pilot PN elements

#### Parameters

<i>ActSetPilotPN</i>	<ul style="list-style-type: none"> <li>• Active Pilot PN</li> </ul>
<i>ActSetPilotPN- Strength</i>	<ul style="list-style-type: none"> <li>• Active Pilot PN strength</li> </ul>

### 8.33.2 Field Documentation

8.33.2.1 **WORD** ActPilotPNElement::ActSetPilotPN

8.33.2.2 **BYTE** ActPilotPNElement::ActSetPilotPNStrength

## 8.34 AddCDMASysInfo Struct Reference

## Data Fields

- [WORD geoSysIdx](#)
- [WORD regPrd](#)

### 8.34.1 Detailed Description

Structure for storing the Additional CDMA System Information.

#### Parameters

<i>geoSysIdx</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>regPrd</i>	<ul style="list-style-type: none"> <li>• Registration period after the CDMA system is acquired.</li> <li>• When the CDMA registration period is not valid, 0xFFFF is used.</li> </ul>

### 8.34.2 Field Documentation

8.34.2.1 [WORD AddCDMASysInfo::geoSysIdx](#)

8.34.2.2 [WORD AddCDMASysInfo::regPrd](#)

## 8.35 AddSysInfo Struct Reference

## Data Fields

- [WORD geoSysIdx](#)
- [ULONG cellBroadcastCap](#)

### 8.35.1 Detailed Description

Structure for storing the Additional GSM and WCDMA System Information.

#### Parameters

<i>geoSysIdx</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
------------------	--

<i>cellBroadcastCap</i>	<ul style="list-style-type: none"> <li>• Cell broadcast capability of the serving system.</li> <li>• When the CDMA registration period is not valid, 0xFFFF is used. <ul style="list-style-type: none"> <li>– NAS_CELL_BROADCAST_CAP_UNKNOWN - Cell broadcast support is unknown</li> <li>– NAS_CELL_BROADCAST_CAP_OFF - Cell broadcast is not supported</li> <li>– NAS_CELL_BROADCAST_CAP_ON - Cell broadcast is supported</li> </ul> </li> </ul>
-------------------------	--

## 8.35.2 Field Documentation

8.35.2.1 **ULONG** AddSysInfo::cellBroadcastCap

8.35.2.2 **WORD** AddSysInfo::geoSysIdx

## 8.36 airTimer Struct Reference

### Data Fields

- [BYTE](#) *namID*
- [ULONG](#) *airTimerValue*

### 8.36.1 Detailed Description

This structure contains information about the Air Timer.

#### Parameters

<i>namID</i>	<ul style="list-style-type: none"> <li>• Index of the NAM(Number Assignment Module) to be configured.</li> <li>• Range 0 to 3.</li> <li>• Some modems support only 1 or 2 NAMs.</li> <li>• 0xFF,if not available.</li> </ul>
<i>airTimerValue</i>	<ul style="list-style-type: none"> <li>• Time in minutes.</li> <li>• Cumulative air time is slammed.</li> <li>• 0xFFFFFFFF,if not available.</li> </ul>

## 8.36.2 Field Documentation

8.36.2.1 **ULONG** airTimer::airTimerValue

8.36.2.2 **BYTE** airTimer::namID

## 8.37 allCallsAlphaIDInfo Struct Reference

### Data Fields

- [BYTE callID](#)
- [alphaIDInfo AlphaIDInfo](#)

### 8.37.1 Detailed Description

This structure contains information for Alpha Identifier for All Calls

#### Parameters

<i>callID</i>	<ul style="list-style-type: none"><li>• Unique call identifier for the call.</li></ul>
<i>AlphaIDInfo</i>	<ul style="list-style-type: none"><li>• See <a href="#">alphaIDInfo</a> for more information.</li></ul>

### 8.37.2 Field Documentation

8.37.2.1 [alphaIDInfo](#) allCallsAlphaIDInfo::AlphaIDInfo

8.37.2.2 [BYTE](#) allCallsAlphaIDInfo::callID

## 8.38 allCallsDiagInfo Struct Reference

### Data Fields

- [BYTE callID](#)
- [diagInfo DiagInfo](#)

### 8.38.1 Detailed Description

This structure contains Diagnostic Information for All Calls

#### Parameters

<i>callID</i>	<ul style="list-style-type: none"><li>• Unique call identifier for the call.</li></ul>
<i>DiagInfo</i>	<ul style="list-style-type: none"><li>• See <a href="#">diagInfo</a> for more information.</li></ul>

### 8.38.2 Field Documentation

8.38.2.1 [BYTE](#) allCallsDiagInfo::callID

8.38.2.2 [diagInfo](#) allCallsDiagInfo::DiagInfo

## 8.39 allCallsUUSInfo Struct Reference

### Data Fields

- [BYTE callID](#)
- [UUSInfo uusInfo](#)

### 8.39.1 Detailed Description

This structure contains information for User to User Signaling Service for All Calls.

#### Parameters

<i>callID</i>	<ul style="list-style-type: none"><li>• Unique call identifier for the call.</li></ul>
<i>uusInfo</i>	<ul style="list-style-type: none"><li>• See <a href="#">UUSInfo</a> for more information.</li></ul>

### 8.39.2 Field Documentation

#### 8.39.2.1 BYTE allCallsUUSInfo::callID

#### 8.39.2.2 UUSInfo allCallsUUSInfo::uusInfo

## 8.40 alphaIDInfo Struct Reference

### Data Fields

- [BYTE alphaDcs](#)
- [BYTE alphaLen](#)
- [BYTE alphaText](#) [255]

### 8.40.1 Detailed Description

This structure contains information about the Alpha Identifier.

#### Parameters

<i>alphaDcs</i>	<ul style="list-style-type: none"><li>• Alpha coding scheme<ul style="list-style-type: none"><li>– 0x01 - GSM Default_Char</li><li>– 0x02 - UCS2</li><li>– 0xFF - Not Available</li></ul></li></ul>
-----------------	---



<i>alphaLen</i>	<ul style="list-style-type: none"><li>• Number of sets of the following elements:<ul style="list-style-type: none"><li>– pAlpha_text</li></ul></li><li>• If zero(0) then no further information exists.</li></ul>
<i>alphaText</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"><li>• Data encoded as per the alpha_dcs</li></ul>

## 8.40.2 Field Documentation

8.40.2.1 BYTE alphaIDInfo::alphaDcs

8.40.2.2 BYTE alphaIDInfo::alphaLen

8.40.2.3 BYTE alphaIDInfo::alphaText[255]

## 8.41 altitudeSrcInfo Struct Reference

### Data Fields

- [ULONG source](#)
- [ULONG linkage](#)
- [ULONG coverage](#)

### 8.41.1 Detailed Description

This structure specifies information regarding the altitude source

## Parameters

<i>source</i>	<ul style="list-style-type: none"> <li>• Specifies the source of the altitude</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 0 - Source is unknown</li> <li>– 1 - GPS is the source</li> <li>– 2 - Cell ID provided the source</li> <li>– 3 - Source is enhanced cell ID</li> <li>– 4 - Wi-Fi is the source</li> <li>– 5 - Terrestrial source</li> <li>– 6 - Hybrid terrestrial source</li> <li>– 7 - Altitude database is the source</li> <li>– 8 - Barometric altimeter is the source</li> <li>– 9 - Other sources</li> </ul> </li> </ul>
<i>linkage</i>	<ul style="list-style-type: none"> <li>• Specifies the dependency between the horizontal and altitude position components</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 0 - Not specified</li> <li>– 1 - Fully interdependent</li> <li>– 2 - Depends on latitude and longitude</li> <li>– 3 - Fully independent</li> </ul> </li> </ul>
<i>coverage</i>	<ul style="list-style-type: none"> <li>• Specifies the region of uncertainty.</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 0 - Not specified</li> <li>– 1 - Altitude uncertainty is valid at the injected horizontal position coordinates only</li> <li>– 2 - Altitude uncertainty applies to the position of the device regardless of horizontal position</li> </ul> </li> </ul>

### 8.41.2 Field Documentation

8.41.2.1 **ULONG** altitudeSrcInfo::coverage

8.41.2.2 **ULONG** altitudeSrcInfo::linkage

8.41.2.3 **ULONG** altitudeSrcInfo::source

## 8.42 appStats Struct Reference

### Data Fields

- uint8\_t [appType](#)
- uint8\_t [appState](#)
- uint8\_t [persoState](#)
- uint8\_t [persoFeature](#)
- uint8\_t [persoRetries](#)
- uint8\_t [persoUnblockRetries](#)
- uint8\_t [aidLength](#)
- uint8\_t [aidVal](#) [255]
- uint8\_t [univPin](#)
- uint8\_t [pin1State](#)
- uint8\_t [pin1Retries](#)
- uint8\_t [puk1Retries](#)
- uint8\_t [pin2State](#)
- uint8\_t [pin2Retries](#)
- uint8\_t [puk2Retries](#)

### 8.42.1 Detailed Description

This structure contains Application Status Information loaded on the card.

#### Parameters

<i>appType</i>	<ul style="list-style-type: none"><li>• Indicates the type of the application.<ul style="list-style-type: none"><li>– 0 - Unknown</li><li>– 1 - SIM card</li><li>– 2 - USIM application</li><li>– 3 - RUIM card</li><li>– 4 - CSIM application</li><li>– 5 - ISIM application</li></ul></li><li>• Other values are reserved for the future and are to be handled as "Unknown".</li></ul>
----------------	--

<i>appState</i>	<ul style="list-style-type: none"> <li>• Indicates the state of the application. <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - Detected</li> <li>– 2 - PIN1 or UPIN is required</li> <li>– 3 - PUK1 or PUK for UPIN is required</li> <li>– 4 - Personalization state must be checked</li> <li>– 5 - PIN1 is blocked</li> <li>– 6 - Illegal</li> <li>– 7 - Ready</li> </ul> </li> </ul>
<i>persoState</i>	<ul style="list-style-type: none"> <li>• Indicates the state of the personalization for the application. <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - Personalization operation is in progress</li> <li>– 2 - Ready</li> <li>– 3 - Personalization code is required</li> <li>– 4 - PUK for personalization code is required</li> <li>– 5 - Permanently blocked</li> </ul> </li> </ul>
<i>persoFeature</i>	<ul style="list-style-type: none"> <li>• Indicates the personalization feature.</li> <li>• This applies only when a personalization code is required to deactivate or unblock personalization. <ul style="list-style-type: none"> <li>– 0 - GW network personalization</li> <li>– 1 - GW network subset personalization</li> <li>– 2 - GW service provider personalization</li> <li>– 3 - GW corporate personalization</li> <li>– 4 - GW UIM personalization</li> <li>– 5 - 1X network type 1 personalization</li> <li>– 6 - 1X network type 2 personalization</li> <li>– 7 - 1X HRPD personalization</li> <li>– 8 - 1X service provider personalization</li> <li>– 9 - 1X corporate personalization</li> <li>– 10 - 1X RUIM personalization</li> <li>– 11 - Unknown</li> </ul> </li> </ul>

<i>persoRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to disable the personalization.</li> </ul>
<i>persoUnblock-Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock the personalization.</li> </ul>
<i>aidLength</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements. i.e. aidVal</li> <li>If zero(0) then no aidVal information exists.</li> </ul>
<i>aidVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>Application identifier value.</li> </ul>
<i>univPin</i>	<ul style="list-style-type: none"> <li>Indicates whether UPIN replaces PIN1. <ul style="list-style-type: none"> <li>0 - PIN1 is used</li> <li>1 - UPIN replaces PIN1</li> </ul> </li> </ul>
<i>pin1State</i>	<ul style="list-style-type: none"> <li>Indicates the state of PIN1. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> </ul> </li> </ul>
<i>pin1Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify PIN1.</li> </ul>
<i>puk1Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock PIN1.</li> </ul>
<i>pin2State</i>	<ul style="list-style-type: none"> <li>Indicates the state of PIN2. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> </ul> </li> </ul>

<i>pin2Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify PIN2.</li> </ul>
<i>puk2Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock PIN2.</li> </ul>

## 8.42.2 Field Documentation

8.42.2.1 `uint8_t appStats::aidLength`

8.42.2.2 `uint8_t appStats::aidVal[255]`

8.42.2.3 `uint8_t appStats::appState`

8.42.2.4 `uint8_t appStats::appType`

8.42.2.5 `uint8_t appStats::persoFeature`

8.42.2.6 `uint8_t appStats::persoRetries`

8.42.2.7 `uint8_t appStats::persoState`

8.42.2.8 `uint8_t appStats::persoUnblockRetries`

8.42.2.9 `uint8_t appStats::pin1Retries`

8.42.2.10 `uint8_t appStats::pin1State`

8.42.2.11 `uint8_t appStats::pin2Retries`

8.42.2.12 `uint8_t appStats::pin2State`

8.42.2.13 `uint8_t appStats::puk1Retries`

8.42.2.14 `uint8_t appStats::puk2Retries`

8.42.2.15 `uint8_t appStats::univPin`

## 8.43 appStatus Struct Reference

### Data Fields

- [BYTE appType](#)
- [BYTE appState](#)
- [BYTE persoState](#)
- [BYTE persoFeature](#)
- [BYTE persoRetries](#)
- [BYTE persoUnblockRetries](#)
- [BYTE aidLength](#)
- [BYTE aidVal \[255\]](#)
- [BYTE univPin](#)
- [BYTE pin1State](#)
- [BYTE pin1Retries](#)

- [BYTE puk1Retries](#)
- [BYTE pin2State](#)
- [BYTE pin2Retries](#)
- [BYTE puk2Retries](#)

### 8.43.1 Detailed Description

This structure contains Application Status Information loaded on the card.

#### Parameters

<i>appType</i>	<ul style="list-style-type: none"><li>• Indicates the type of the application.<ul style="list-style-type: none"><li>– 0 - Unknown</li><li>– 1 - SIM card</li><li>– 2 - USIM application</li><li>– 3 - RUIM card</li><li>– 4 - CSIM application</li><li>– 5 - ISIM application</li></ul></li><li>• Other values are reserved for the future and are to be handled as "Unknown".</li></ul>
<i>appState</i>	<ul style="list-style-type: none"><li>• Indicates the state of the application.<ul style="list-style-type: none"><li>– 0 - Unknown</li><li>– 1 - Detected</li><li>– 2 - PIN1 or UPIN is required</li><li>– 3 - PUK1 or PUK for UPIN is required</li><li>– 4 - Personalization state must be checked</li><li>– 5 - PIN1 is blocked</li><li>– 6 - Illegal</li><li>– 7 - Ready</li></ul></li></ul>

<i>persoState</i>	<ul style="list-style-type: none"><li>• Indicates the state of the personalization for the application.<ul style="list-style-type: none"><li>– 0 - Unknown</li><li>– 1 - Personalization operation is in progress</li><li>– 2 - Ready</li><li>– 3 - Personalization code is required</li><li>– 4 - PUK for personalization code is required</li><li>– 5 - Permanently blocked</li></ul></li></ul>
<i>persoFeature</i>	<ul style="list-style-type: none"><li>• Indicates the personalization feature.</li><li>• This applies only when a personalization code is required to deactivate or unblock personalization.<ul style="list-style-type: none"><li>– 0 - GW network personalization</li><li>– 1 - GW network subset personalization</li><li>– 2 - GW service provider personalization</li><li>– 3 - GW corporate personalization</li><li>– 4 - GW UIM personalization</li><li>– 5 - 1X network type 1 personalization</li><li>– 6 - 1X network type 2 personalization</li><li>– 7 - 1X HRPD personalization</li><li>– 8 - 1X service provider personalization</li><li>– 9 - 1X corporate personalization</li><li>– 10 - 1X RUIM personalization</li><li>– 11 - Unknown</li></ul></li></ul>



<i>persoRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to disable the personalization.</li> </ul>
<i>persoUnblock-Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock the personalization.</li> </ul>
<i>aidLength</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements. i.e. aidVal</li> <li>If zero(0) then no aidVal information exists.</li> </ul>
<i>aidVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>Application identifier value.</li> </ul>
<i>univPin</i>	<ul style="list-style-type: none"> <li>Indicates whether UPIN replaces PIN1. <ul style="list-style-type: none"> <li>0 - PIN1 is used</li> <li>1 - UPIN replaces PIN1</li> </ul> </li> </ul>
<i>pin1State</i>	<ul style="list-style-type: none"> <li>Indicates the state of PIN1. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> </ul> </li> </ul>
<i>pin1Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify PIN1.</li> </ul>
<i>puk1Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock PIN1.</li> </ul>
<i>pin2State</i>	<ul style="list-style-type: none"> <li>Indicates the state of PIN2. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> </ul> </li> </ul>

<i>pin2Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify PIN2.</li> </ul>
<i>puk2Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock PIN2.</li> </ul>

### 8.43.2 Field Documentation

8.43.2.1 **BYTE** appStatus::aidLength

8.43.2.2 **BYTE** appStatus::aidVal[255]

8.43.2.3 **BYTE** appStatus::appState

8.43.2.4 **BYTE** appStatus::appType

8.43.2.5 **BYTE** appStatus::persoFeature

8.43.2.6 **BYTE** appStatus::persoRetries

8.43.2.7 **BYTE** appStatus::persoState

8.43.2.8 **BYTE** appStatus::persoUnblockRetries

8.43.2.9 **BYTE** appStatus::pin1Retries

8.43.2.10 **BYTE** appStatus::pin1State

8.43.2.11 **BYTE** appStatus::pin2Retries

8.43.2.12 **BYTE** appStatus::pin2State

8.43.2.13 **BYTE** appStatus::puk1Retries

8.43.2.14 **BYTE** appStatus::puk2Retries

8.43.2.15 **BYTE** appStatus::univPin

## 8.44 arrAlertingPattern Struct Reference

### Data Fields

- [BYTE](#) numInstances
- [BYTE](#) callID [20]
- [ULONG](#) alertingPattern [20]

### 8.44.1 Detailed Description

This structure contains an array of Alerting Pattern.

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of callID, alertingPattern that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>callID</i> [MAX_NO_OF_CALLS]	<ul style="list-style-type: none"> <li>• Array of Unique call identifier for the call.</li> </ul>
<i>alertingPattern</i> [MAX_NO_OF_CALLS]	<ul style="list-style-type: none"> <li>• Array of Alerting pattern. <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_ALERTING_PATTERN_1 - Pattern 1</li> <li>– 0x01 - QMI_VOICE_ALERTING_PATTERN_2 - Pattern 2</li> <li>– 0x02 - QMI_VOICE_ALERTING_PATTERN_3 - Pattern 3</li> <li>– 0x04 - QMI_VOICE_ALERTING_PATTERN_5 - Pattern 5</li> <li>– 0x05 - QMI_VOICE_ALERTING_PATTERN_6 - Pattern 6</li> <li>– 0x06 - QMI_VOICE_ALERTING_PATTERN_7 - Pattern 7</li> <li>– 0x07 - QMI_VOICE_ALERTING_PATTERN_8 - Pattern 8</li> <li>– 0x08 - QMI_VOICE_ALERTING_PATTERN_9 - Pattern 9</li> </ul> </li> </ul>

## 8.44.2 Field Documentation

8.44.2.1 **ULONG** arrAlertingPattern::alertingPattern[20]8.44.2.2 **BYTE** arrAlertingPattern::callID[20]8.44.2.3 **BYTE** arrAlertingPattern::numInstances

## 8.45 arrAlertingType Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [BYTE callID](#) [20]
- [BYTE AlertingType](#) [20]

## 8.45.1 Detailed Description

This structure contains an array of Alerting Type.

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of callID, AlertingType that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
---------------------	---

<i>callID</i> [ <i>MAX_NO_OF_CALLS</i> ]	<ul style="list-style-type: none"> <li>• Array of Unique call identifier for the call.</li> </ul>
<i>AlertingType</i> [ <i>MAX_NO_OF_CALLS</i> ]	<ul style="list-style-type: none"> <li>• Array of Alerting type. <ul style="list-style-type: none"> <li>– 0x00 - ALERTING_LOCAL - Local</li> <li>– 0x01 - ALERTING_REMOTE - Remote</li> </ul> </li> </ul>

## 8.45.2 Field Documentation

8.45.2.1 **BYTE** `arrAlertingType::AlertingType`[20]

8.45.2.2 **BYTE** `arrAlertingType::callID`[20]

8.45.2.3 **BYTE** `arrAlertingType::numInstances`

## 8.46 arrAlphaID Struct Reference

### Data Fields

- [BYTE](#) `numInstances`
- [allCallsAlphaIDInfo](#) `allCallsAlphaIDInfoArr` [20]

### 8.46.1 Detailed Description

This structure contains an array of Alpha ID Info

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of <a href="#">allCallsAlphaIDInfo</a> that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>allCallsAlphaIDInfo</i> [ <i>MAX_NO_OF_CALLS</i> ]	<ul style="list-style-type: none"> <li>• Array of <a href="#">allCallsAlphaIDInfo</a>.</li> <li>• See <a href="#">allCallsAlphaIDInfo</a> for more information.</li> </ul>

## 8.46.2 Field Documentation

8.46.2.1 **allCallsAlphaIDInfo** `arrAlphaID::allCallsAlphaIDInfoArr`[20]

8.46.2.2 **BYTE** `arrAlphaID::numInstances`

## 8.47 arrCalledPartyNum Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [peerNumberInfo CalledPartyNum](#) [20]

### 8.47.1 Detailed Description

This structure contains an array of Called Party Numbers consisting of information of all the numbers which have been called from the device.

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of calledPartyNum that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>CalledParty-Num[MAX_NO_OF_CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of CalledPartyNum.</li> <li>• See <a href="#">peerNumberInfo</a> for more information.</li> </ul>

### 8.47.2 Field Documentation

8.47.2.1 [peerNumberInfo arrCalledPartyNum::CalledPartyNum](#)[20]

8.47.2.2 [BYTE arrCalledPartyNum::numInstances](#)

## 8.48 arrCallEndReason Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [BYTE callID](#) [20]
- [WORD callEndReason](#) [20]

### 8.48.1 Detailed Description

This structure contains an array of Call End Reasons.

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of callID, callEndReason that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
---------------------	--

<i>callID</i> [ <i>MAX_NO_OF_CALLS</i> ]	<ul style="list-style-type: none"> <li>• Array of Unique call identifier for the call.</li> </ul>
<i>callEndReason</i> [ <i>MAX_NO_OF_CALLS</i> ]	<ul style="list-style-type: none"> <li>• Array of Call End Reason .</li> <li>• See Table9 <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for a list of valid voice-related call end reasons</li> </ul>

## 8.48.2 Field Documentation

8.48.2.1 **WORD** arrCallEndReason::callEndReason[20]

8.48.2.2 **BYTE** arrCallEndReason::callID[20]

8.48.2.3 **BYTE** arrCallEndReason::numInstances

## 8.49 arrCallInfo Struct Reference

### Data Fields

- [BYTE](#) numInstances
- [getAllCallInformation](#) [getAllCallInfo](#) [20]

### 8.49.1 Detailed Description

This structure contains an array of Call Info

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of <a href="#">getAllCallInfo</a> that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>getAllCallInfo</i> [ <i>MAX_NO_OF_CALLS</i> ]	<ul style="list-style-type: none"> <li>• Array of CallInfo.</li> <li>• See <a href="#">getAllCallInfo</a> for more information.</li> </ul>

## 8.49.2 Field Documentation

8.49.2.1 **getAllCallInformation** arrCallInfo::getAllCallInfo[20]

8.49.2.2 **BYTE** arrCallInfo::numInstances

## 8.50 arrConnectPartyNum Struct Reference

### Data Fields

- [BYTE](#) numInstances

- [peerNumberInfo ConnectedPartyNum](#) [20]

### 8.50.1 Detailed Description

This structure contains an array of Connected Party Numbers consisting of information regarding all the devices connected.

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of ConnectedPartyNum that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>ConnectedParty-Num[MAX_NO_OF_CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of ConnectedPartyNum.</li> <li>• See <a href="#">peerNumberInfo</a> for more information.</li> </ul>

### 8.50.2 Field Documentation

8.50.2.1 **peerNumberInfo** arrConnectPartyNum::ConnectedPartyNum[20]

8.50.2.2 **BYTE** arrConnectPartyNum::numInstances

## 8.51 arrDiagInfo Struct Reference

### Data Fields

- **BYTE** numInstances
- [allCallsDiagInfo DiagInfo](#) [20]

### 8.51.1 Detailed Description

This structure contains an array of Diagnostic Information.

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of DiagInfo that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>DiagInfo[MAX_NO_OF_CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of DiagInfo.</li> <li>• See <a href="#">allCallsDiagInfo</a> for more information.</li> </ul>

### 8.51.2 Field Documentation

8.51.2.1 **allCallsDiagInfo** arrDiagInfo::DiagInfo[20]

## 8.51.2.2 BYTE arrDiagInfo::numInstances

## 8.52 arrRedirPartyNum Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [peerNumberInfo RedirPartyNum](#) [20]

## 8.52.1 Detailed Description

This structure contains an array of Redirecting Party Numbers consisting of information of all the numbers which have been redirected from the device.

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of redirPartyNum that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>RedirPartyNum[ MAX_NO_OF_ CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of RedirPartyNum.</li> <li>• See <a href="#">peerNumberInfo</a> for more information.</li> </ul>

## 8.52.2 Field Documentation

## 8.52.2.1 BYTE arrRedirPartyNum::numInstances

## 8.52.2.2 peerNumberInfo arrRedirPartyNum::RedirPartyNum[20]

## 8.53 arrRemotePartyName Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [getAllCallRmtPtyName GetAllCallRmtPtyName](#) [20]

## 8.53.1 Detailed Description

This structure contains an array of Remote Party Names

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of <a href="#">remotePartyName</a> that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
---------------------	--



<i>GetAllCallRmtPtyName</i> [MAX_NO_OF_CALLS]	<ul style="list-style-type: none"> <li>• Array of <a href="#">remotePartyName</a>.</li> <li>• See <a href="#">getAllCallRmtPtyName</a> for more information.</li> </ul>
---	---

### 8.53.2 Field Documentation

8.53.2.1 `getAllCallRmtPtyName` `arrRemotePartyName::GetAllCallRmtPtyName`[20]

8.53.2.2 `BYTE` `arrRemotePartyName::numInstances`

## 8.54 arrRemotePartyNum Struct Reference

### Data Fields

- `BYTE` `numInstances`
- `getAllCallRmtPtyNum` `RmtPtyNum` [20]

### 8.54.1 Detailed Description

This structure contains an array of Remote Party Numbers

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of <a href="#">remotePartyNum</a> that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>RmtPtyNum</i> [MAX_NO_OF_CALLS]	<ul style="list-style-type: none"> <li>• Array of <a href="#">remotePartyNum</a>.</li> <li>• See <a href="#">getAllCallRmtPtyNum</a> for more information.</li> </ul>

### 8.54.2 Field Documentation

8.54.2.1 `BYTE` `arrRemotePartyNum::numInstances`

8.54.2.2 `getAllCallRmtPtyNum` `arrRemotePartyNum::RmtPtyNum`[20]

## 8.55 arrSvcOption Struct Reference

### Data Fields

- `BYTE` `numInstances`
- `BYTE` `callID` [20]
- `WORD` `srvOption` [20]

### 8.55.1 Detailed Description

This structure contains array an of Servicing option.

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of callID, srvOption that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>callID[MAX_NO_OF_CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of Unique call identifier for the call.</li> </ul>
<i>srvOption[MAX_NO_OF_CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of Service option.</li> <li>• See Table9 <a href="#">qaGobiApiTableServiceOptions.h</a> for standard service option number assignments.</li> </ul>

## 8.55.2 Field Documentation

8.55.2.1 BYTE arrSvcOption::callID[20]

8.55.2.2 BYTE arrSvcOption::numInstances

8.55.2.3 WORD arrSvcOption::srvOption[20]

## 8.56 arrUUSInfo Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [allCallsUUSInfo AllCallsUUSInfo](#) [20]

## 8.56.1 Detailed Description

This structure contains an array of User to User Signaling Service Information

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of <a href="#">allCallsUUSInfo</a> that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>AllCallsUUS-Info[MAX_NO_OF_CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of <a href="#">allCallsUUSInfo</a>.</li> <li>• See <a href="#">allCallsUUSInfo</a> for more information.</li> </ul>

## 8.56.2 Field Documentation

8.56.2.1 `allCallsUUSInfo arrUUSInfo::AllCallsUUSInfo[20]`

8.56.2.2 `BYTE arrUUSInfo::numInstances`

## 8.57 authenticateResult Struct Reference

### Data Fields

- [WORD contentLen](#)
- [BYTE content](#) [1024]

### 8.57.1 Detailed Description

This structure contains the information about the authenticate result.

#### Parameters

<i>contentLen</i>	<ul style="list-style-type: none"><li>• Length of the following elements i.e. content.</li></ul>
<i>content</i> [ <i>MAX_CONTENT_LENGTH</i> ]	<ul style="list-style-type: none"><li>• Authenticate data.</li><li>• This value is a sequence of bytes returned from the card.</li></ul>

## 8.57.2 Field Documentation

8.57.2.1 `BYTE authenticateResult::content[1024]`

8.57.2.2 `WORD authenticateResult::contentLen`

## 8.58 authenticationData Struct Reference

### Data Fields

- [BYTE context](#)
- [WORD dataLen](#)
- [BYTE data](#) [1024]

### 8.58.1 Detailed Description

This structure contains the Session Information.

## Parameters

<i>context</i>	<ul style="list-style-type: none"> <li>• Authenticate context. <ul style="list-style-type: none"> <li>– 0 - Runs the GSM algorithm (valid only on a 2GSIM card)</li> <li>– 1 - Runs the CAVE algorithm (valid only on a RUIM card)</li> <li>– 2 - GSM security context (valid only on a USIM application)</li> <li>– 3 - 3G security context (valid only on a USIM application)</li> <li>– 4 - VGCS/VBS security context (valid only on a USIM application)</li> <li>– 5 - GBA security context, Bootstrapping mode (valid only on a USIM or ISIM application)</li> <li>– 6 - GBA security context, NAF Derivation mode (valid only on a USIM or ISIM application)</li> <li>– 7 - MBMS security context, MSK Update mode (valid only on a USIM application)</li> <li>– 8 - MBMS security context, MTK Generation mode (valid only on a USIM application)</li> <li>– 9 - MBMS security context, MSK Deletion mode (valid only on a USIM application)</li> <li>– 10 - MBMS security context, MUK Deletion mode (valid only on a USIM application)</li> <li>– 11 - IMS AKA security context (valid only on a USIM application)</li> <li>– 12 - HTTP-digest security context (valid only on an ISIM application)</li> <li>– 13 - Compute IP authentication, CHAP (valid only on RUIM or CSIM)</li> <li>– 14 - Compute IP authentication, MN-HA authenticator (valid only on RUIM or CSIM)</li> <li>– 15 - Compute IP authentication, MIP-RRQ hash (valid only on RUIM or CSIM)</li> <li>– 16 - Compute IP authentication, MN-AAA authenticator (valid only on RUIM or CSIM)</li> <li>– 17 - Compute IP authentication, HRPD access authenticator (valid only on RUIM or CSIM)</li> </ul> </li> <li>• Other values are possible and reserved for future use.</li> </ul>
----------------	--

<i>dataLen</i>	<ul style="list-style-type: none"><li>Length of the following elements i.e. data.</li></ul>
<i>data[<small>MAX_DES- CRIPTION_LE- NGTH</small>]</i>	<ul style="list-style-type: none"><li>Authenticate Data.</li></ul>

## 8.58.2 Field Documentation

8.58.2.1 **BYTE** authenticationData::context

8.58.2.2 **BYTE** authenticationData::data[1024]

8.58.2.3 **WORD** authenticationData::dataLen

## 8.59 BandCapabilityResp Struct Reference

### Data Fields

- [ULONGLONG bandCapability](#)
- [ULONGLONG \\* pLteBandCapability](#)
- [ULONGLONG \\* pTdsBandCapability](#)

### 8.59.1 Detailed Description

This structure contains the TLV required to Get Band Capability.

## Parameters

<i>bandCapability[OUT]</i>	<p>Bitmask of bands supported by the device</p> <ul style="list-style-type: none"> <li>• Bit 0 - Band class 0, A-system</li> <li>• Bit 1 - Band class 0, B-system</li> <li>• Bit 2 - Band class 1, all blocks</li> <li>• Bit 3 - Band class 2</li> <li>• Bit 4 - Band class 3, A-system</li> <li>• Bit 5 - Band class 4, all blocks</li> <li>• Bit 6 - Band class 5, all blocks</li> <li>• Bit 7 - GSM DCS band (1800)</li> <li>• Bit 8 - GSM Extended GSM (E-GSM) band (900)</li> <li>• Bit 9 - GSM Primary GSM (P-GSM) band (900)</li> <li>• Bit 10 - Band class 6</li> <li>• Bit 11 - Band class 7</li> <li>• Bit 12 - Band class 8</li> <li>• Bit 13 - Band class 9</li> <li>• Bit 14 - Band class 10</li> <li>• Bit 15 - Band class 11</li> <li>• Bit 16 - GSM 450 band</li> <li>• Bit 17 - GSM 480 band</li> <li>• Bit 18 - GSM 750 band</li> <li>• Bit 19 - GSM 850 band</li> <li>• Bit 20 - GSM railways GSM band (900)</li> <li>• Bit 21 - GSM PCS band (1900)</li> <li>• Bit 22 - WCDMA (Europe, Japan, and China) 2100 band</li> <li>• Bit 23 - WCDMA US PCS 1900 band</li> <li>• Bit 24 - WCDMA (Europe and China) DCS 1800 band</li> <li>• Bit 25 - WCDMA US 1700 band</li> <li>• Bit 26 - WCDMA US 850 band</li> <li>• Bit 27 - WCDMA Japan 800 band</li> <li>• Bit 28 - Band class 12</li> <li>• Bit 29 - Band class 14</li> <li>• Bit 30 - Reserved</li> <li>• Bit 31 - Band class 15</li> <li>• Bits 32 through 47 - Reserved</li> <li>• Bit 48 - WCDMA Europe 2600 band</li> </ul>
	<ul style="list-style-type: none"> <li>• Bit 49 - WCDMA Europe and Japan 900 band</li> <li>• Bit 50 - WCDMA Japan 1700 band</li> <li>• Bits 51 through 55 - Reserved</li> </ul>

<i>OUT</i>	<p>pTdsBandCapability[OUT] Bitmask of TDS bands supported by the device.</p> <ul style="list-style-type: none"> <li>• Bit 0 - TDS Band A 1900 to 1920 MHz, 2010 to 2020 MHz</li> <li>• Bit 1 - TDS Band B 1850 to 1910 MHz, 1930 to 1990 MHz</li> <li>• Bit 2 - TDS Band C 1910 to 1930 MHz</li> <li>• Bit 3 - TDS Band D 2570 to 2620 MHz</li> <li>• Bit 4 - TDS Band E 2300 to 2400 MHz</li> <li>• Bit 5 - TDS Band F 1880 to 1920 MHz</li> </ul>
------------	---

## 8.59.2 Field Documentation

8.59.2.1 **ULONGLONG** BandCapabilityResp::bandCapability

8.59.2.2 **ULONGLONG\*** BandCapabilityResp::pLteBandCapability

8.59.2.3 **ULONGLONG\*** BandCapabilityResp::pTdsBandCapability

## 8.60 BdsSV Struct Reference

### Data Fields

- [WORD](#) id
- [BYTE](#) mask

### 8.60.1 Detailed Description

This structure contains the BDS [SV](#) Info

#### Parameters

<i>id</i>	<ul style="list-style-type: none"> <li>• <a href="#">SV</a> ID of the satellite whose data is to be deleted. <ul style="list-style-type: none"> <li>– Range for BDS: 201 to 237</li> </ul> </li> </ul>
<i>mask</i>	<ul style="list-style-type: none"> <li>• Indicates if the ephemeris or almanac for a satellite is to be deleted</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– QMI_LOC_MASK_DELETE_EPHEMERIS (0x01) - Delete ephemeris for the satellite</li> <li>– QMI_LOC_MASK_DELETE_ALMANAC (0x02) - Delete almanac for the satellite</li> </ul> </li> </ul>

## 8.60.2 Field Documentation

8.60.2.1 **WORD** BdsSV::id

## 8.60.2.2 BYTE BdsSV::mask

## 8.61 BdsSVInfo Struct Reference

## Data Fields

- [BYTE len](#)
- [BdsSV \\* pSV](#)

## 8.61.1 Detailed Description

This structure contains the number of sets of the BDS SVN Info

## Parameters

<i>len</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements: <ul style="list-style-type: none"> <li>– gnssSvId</li> <li>– deleteSvInfoMask</li> </ul> </li> </ul>
<i>pSV</i>	<ul style="list-style-type: none"> <li>• Pointer to struct <a href="#">BdsSV</a>. See <a href="#">BdsSV</a> for more information</li> </ul>

## 8.61.2 Field Documentation

## 8.61.2.1 BYTE BdsSVInfo::len

## 8.61.2.2 BdsSV\* BdsSVInfo::pSV

## 8.62 BroadcastConfig Struct Reference

## Data Fields

- [WORD fromServiceId](#)
- [WORD toServiceId](#)
- [BYTE selected](#)

## 8.62.1 Detailed Description

This structure contains [BroadcastConfig](#) parameters

## Parameters

<i>fromServiceId</i>	<ul style="list-style-type: none"> <li>• Starting point of range of CBM message identifiers</li> </ul>
----------------------	--



<i>toServiceId</i>	<ul style="list-style-type: none"> <li>Ending point of range of CBM message identifiers</li> </ul>
<i>selected</i>	<ul style="list-style-type: none"> <li>Range of CBM message identifiers indicated by from_service_id and to_service_id <ul style="list-style-type: none"> <li>0x00 – Not selected</li> <li>0x01 – Selected</li> </ul> </li> </ul>

## 8.62.2 Field Documentation

8.62.2.1 WORD BroadcastConfig::fromServiceId

8.62.2.2 BYTE BroadcastConfig::selected

8.62.2.3 WORD BroadcastConfig::toServiceId

## 8.63 burstDTMFInfo Struct Reference

### Data Fields

- [BYTE](#) \* pCallID
- [BYTE](#) digitCnt
- [BYTE](#) pDigitBuff [255]

### 8.63.1 Detailed Description

This structure contains Voice Burst DTMF Information

#### Parameters

<i>pCallID[IN/OUT]</i>	<ul style="list-style-type: none"> <li>Call ID associated with call on which the DTMF information has to be sent. A burst DTMF request is sent to the current active/alerting call when pCallId is set to 0xFF.</li> <li>This is IN/OUT parameter, value passed by user will be packed in request and value received from the device would be returned to the user.</li> <li>If the call ID value received is 0, no value has been returned by the device</li> </ul>
------------------------	--

<i>digitCnt</i>	<ul style="list-style-type: none"> <li>Length of DTMF digit buffer which follows</li> </ul>
<i>pDigitBuff[MAX- _DESCRIPTIO- N_LENGTH]</i>	<ul style="list-style-type: none"> <li>DTMF digit buffer in ASCII, NULL terminated</li> </ul>

### 8.63.2 Field Documentation

8.63.2.1 **BYTE** burstDTMFInfo::digitCnt

8.63.2.2 **BYTE\*** burstDTMFInfo::pCallID

8.63.2.3 **BYTE** burstDTMFInfo::pDigitBuff[255]

## 8.64 CallBarringSysInfo Struct Reference

### Data Fields

- [ULONG csBarStatus](#)
- [ULONG psBarStatus](#)

### 8.64.1 Detailed Description

Structure for storing the GSM and WCDMA Call Barring System Information.

#### Parameters

<i>csBarStatus</i>	<ul style="list-style-type: none"> <li>Call barring status for circuit-switched calls. <ul style="list-style-type: none"> <li>NAS_CELL_ACCESS_NORMAL_ONLY - Cell access is allowed for normal calls only</li> <li>NAS_CELL_ACCESS_EMERGENCY_ONLY - Cell access is allowed for emergency calls only</li> <li>NAS_CELL_ACCESS_NO_CALLS - Cell access is not allowed for any call type</li> <li>NAS_CELL_ACCESS_ALL_CALLS - Cell access is allowed for all call types</li> <li>NAS_CELL_ACCESS_UNKNOWN - Cell access type is unknown</li> </ul> </li> </ul>
--------------------	--

<i>psBarStatus</i>	<ul style="list-style-type: none"> <li>• Call barring status for packet-switched calls. <ul style="list-style-type: none"> <li>– NAS_CELL_ACCESS_NORMAL_ONLY - Cell access is allowed for normal calls only</li> <li>– NAS_CELL_ACCESS_EMERGENCY_ONLY - Cell access is allowed for emergency calls only</li> <li>– NAS_CELL_ACCESS_NO_CALLS - Cell access is not allowed for any call type</li> <li>– NAS_CELL_ACCESS_ALL_CALLS - Cell access is allowed for all call types</li> <li>– NAS_CELL_ACCESS_UNKNOWN - Cell access type is unknown</li> </ul> </li> </ul>
--------------------	---

## 8.64.2 Field Documentation

8.64.2.1 **ULONG** CallBarringSysInfo::csBarStatus

8.64.2.2 **ULONG** CallBarringSysInfo::psBarStatus

## 8.65 callBarStatus Struct Reference

### Data Fields

- [ULONG csBarStatus](#)
- [ULONG psBarStatus](#)

### 8.65.1 Detailed Description

This structure contains Call Barring Status.

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>csBarStatus</i>	<ul style="list-style-type: none"> <li>• Call Barring Status for circuit-switched calls.</li> <li>• Values: <ul style="list-style-type: none"> <li>• NAS_CELL_ACCESS_NORMAL_ONLY - Cell access is allowed for normal calls only</li> <li>• NAS_CELL_ACCESS_EMERGENCY_ONLY - Cell access is allowed for emergency calls only</li> <li>• NAS_CELL_ACCESS_NO_CALLS - Cell access is not allowed for any call type</li> <li>• NAS_CELL_ACCESS_ALL_CALLS - Cell access is allowed for all call types</li> <li>• NAS_CELL_ACCESS_UNKNOWN - Cell access type is unknown</li> </ul> </li> </ul>
--------------------	---

<i>psBarStatus</i>	<ul style="list-style-type: none"> <li>• Call Barring Status for packet-switched calls.</li> <li>• Values: <ul style="list-style-type: none"> <li>– NAS_CELL_ACCESS_NORMAL_ONLY - Cell access is allowed for normal calls only</li> <li>– NAS_CELL_ACCESS_EMERGENCY_ONLY - Cell access is allowed for emergency calls only</li> <li>– NAS_CELL_ACCESS_NO_CALLS - Cell access is not allowed for any call type</li> <li>– NAS_CELL_ACCESS_ALL_CALLS - Cell access is allowed for all call types</li> <li>– NAS_CELL_ACCESS_UNKNOWN - Cell access type is unknown</li> </ul> </li> </ul>
--------------------	--

## 8.65.2 Field Documentation

8.65.2.1 **ULONG** callBarStatus::csBarStatus

8.65.2.2 **ULONG** callBarStatus::psBarStatus

## 8.66 calledPartyInfo Struct Reference

### Data Fields

- [BYTE PI](#)
- [BYTE SI](#)
- [BYTE numType](#)
- [BYTE numPlan](#)
- [BYTE numLen](#)
- [BYTE number](#) [255]

### 8.66.1 Detailed Description

This structure contains Called party Number Information

#### Parameters

<i>PI</i>	<ul style="list-style-type: none"> <li>• Presentation indicator; refer to [S1, Table 2.7.4.4-1] for valid values.</li> </ul>
<i>SI</i>	<ul style="list-style-type: none"> <li>• Number of sets of following elements <ul style="list-style-type: none"> <li>– Caller Id</li> </ul> </li> </ul>

<i>SI</i>	<ul style="list-style-type: none"> <li>• Number screening indicator.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_SI_USER_PROVIDED_NOT_SCREENED - Provided user is not screened</li> <li>– 0x01 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_PASSED - Provided user passed verification</li> <li>– 0x02 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_FAILED - Provided user failed verification</li> <li>– 0x03 - QMI_VOICE_SI_NETWORK_PROVIDED - Provided network</li> </ul> </li> </ul>
<i>numType</i>	<ul style="list-style-type: none"> <li>• Number type.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_TYPE_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_TYPE_INTERNATIONAL - International</li> <li>– 0x02 - QMI_VOICE_NUM_TYPE_NATIONAL - National</li> <li>– 0x03 - QMI_VOICE_NUM_TYPE_NETWORK_SPECIFIC - Network-specific</li> <li>– 0x04 - QMI_VOICE_NUM_TYPE_SUBSCRIBER - Subscriber</li> <li>– 0x05 - QMI_VOICE_NUM_TYPE_RESERVED - Reserved</li> <li>– 0x06 - QMI_VOICE_NUM_TYPE_ABBREVIATED - Abbreviated</li> <li>– 0x07 - QMI_VOICE_NUM_TYPE_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>
<i>numPlan</i>	<ul style="list-style-type: none"> <li>• Number plan.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_PLAN_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_PLAN_ISDN - ISDN</li> <li>– 0x03 - QMI_VOICE_NUM_PLAN_DATA - Data</li> <li>– 0x04 - QMI_VOICE_NUM_PLAN_TELEX - Telex</li> <li>– 0x08 - QMI_VOICE_NUM_PLAN_NATIONAL - National</li> <li>– 0x09 - QMI_VOICE_NUM_PLAN_PRIVATE - Private</li> <li>– 0x0B - QMI_VOICE_NUM_PLAN_RESERVED_CTS - Reserved cordless telephony system</li> <li>– 0x0F - QMI_VOICE_NUM_PLAN_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>

<i>numLen</i>	<ul style="list-style-type: none"> <li>Provides the length of number which follow.</li> </ul>
<i>number[255]</i>	<ul style="list-style-type: none"> <li>number of numLen length, NULL terminated.</li> </ul>

## 8.66.2 Field Documentation

8.66.2.1 **BYTE** calledPartyInfo::number[255]

8.66.2.2 **BYTE** calledPartyInfo::numLen

8.66.2.3 **BYTE** calledPartyInfo::numPlan

8.66.2.4 **BYTE** calledPartyInfo::numType

8.66.2.5 **BYTE** calledPartyInfo::PI

8.66.2.6 **BYTE** calledPartyInfo::SI

## 8.67 calledPartySubAdd Struct Reference

### Data Fields

- [BYTE](#) extBit
- [BYTE](#) subAddrType
- [BYTE](#) oddEvenInd
- [BYTE](#) subAddrLen
- [BYTE](#) subAddr [255]

### 8.67.1 Detailed Description

This structure contains information about the Called Sub Party Addresses.

#### Parameters

<i>extBit</i>	<ul style="list-style-type: none"> <li>Extension bit.</li> </ul>
<i>subAddrType</i>	<ul style="list-style-type: none"> <li>Subaddress type. <ul style="list-style-type: none"> <li>0x00 - NSAP</li> <li>0x01 - USER</li> </ul> </li> </ul>

<i>oddEvenInd</i>	<ul style="list-style-type: none"> <li>• Even/odd indicator. <ul style="list-style-type: none"> <li>– 0x00 - Even number of address signals</li> <li>– 0x01 - Odd number of address signals</li> </ul> </li> </ul>
<i>subAddrLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements: <ul style="list-style-type: none"> <li>– SubAddress</li> </ul> </li> </ul>
<i>subAddr</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>• Array of the SubAddress in BCD number format.</li> </ul>

## 8.67.2 Field Documentation

8.67.2.1 **BYTE** calledPartySubAdd::extBit

8.67.2.2 **BYTE** calledPartySubAdd::oddEvenInd

8.67.2.3 **BYTE** calledPartySubAdd::subAddr[255]

8.67.2.4 **BYTE** calledPartySubAdd::subAddrLen

8.67.2.5 **BYTE** calledPartySubAdd::subAddrType

## 8.68 callerIDInfo Struct Reference

### Data Fields

- [BYTE PI](#)
- [BYTE callerIDLen](#)
- [BYTE callerID](#) [255]

### 8.68.1 Detailed Description

This structure contains Caller ID Information

#### Parameters

<i>PI</i>	<ul style="list-style-type: none"> <li>• Presentation indicator; refer to [S1, Table 2.7.4.4-1] for valid values.</li> </ul>
<i>callerIDLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of following elements <ul style="list-style-type: none"> <li>– Caller Id</li> </ul> </li> </ul>

<i>pCallerID</i>	<ul style="list-style-type: none"> <li>• Caller ID in ASCII string.</li> </ul>
------------------	--

## 8.68.2 Field Documentation

8.68.2.1 **BYTE** callerIDInfo::callerID[255]

8.68.2.2 **BYTE** callerIDInfo::callerIDLen

8.68.2.3 **BYTE** callerIDInfo::PI

## 8.69 callFwdTypeAndPlan Struct Reference

### Data Fields

- [BYTE](#) numberType
- [BYTE](#) numberPlan

### 8.69.1 Detailed Description

This structure contains Supplementary Service request parameters related to different features and their activation, deactivation, registration and erasure (applicable only for 3GPP)

#### Parameters

<i>numberType</i>	<ul style="list-style-type: none"> <li>• Call forwarding number type <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_TYPE_UNKNOWN Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_TYPE_INTERNATIONAL International</li> <li>– 0x02 - QMI_VOICE_NUM_TYPE_NATIONAL National</li> <li>– 0x03 - QMI_VOICE_NUM_TYPE_NETWORK_SPECIFIC Network-specific</li> <li>– 0x04 - QMI_VOICE_NUM_TYPE_SUBSCRIBER Subscriber</li> <li>– 0x05 - QMI_VOICE_NUM_TYPE_RESERVED Reserved</li> <li>– 0x06 - QMI_VOICE_NUM_TYPE_ABBREVIATED Abbreviated</li> <li>– 0x07 - QMI_VOICE_NUM_TYPE_RESERVED_EXTENSION Reserved extension</li> </ul> </li> </ul>
-------------------	---



<i>numberPlan</i>	<ul style="list-style-type: none"> <li>• Call forwarding number plan <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_PLAN_UNKNOWN Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_PLAN_ISDN ISDN</li> <li>– 0x03 - QMI_VOICE_NUM_PLAN_DATA Data</li> <li>– 0x04 - QMI_VOICE_NUM_PLAN_TELEX Telex</li> <li>– 0x08 - QMI_VOICE_NUM_PLAN_NATIONAL National</li> <li>– 0x09 - QMI_VOICE_NUM_PLAN_PRIVATE Private</li> <li>– 0x0B - QMI_VOICE_NUM_PLAN_RESERVED_CTS Reserved cordless telephony system</li> <li>– 0x0F - QMI_VOICE_NUM_PLAN_RESERVED_EXTENSION Reserved extension</li> </ul> </li> </ul>
-------------------	---

## 8.69.2 Field Documentation

8.69.2.1 **BYTE** callFwdTypeAndPlan::numberPlan

8.69.2.2 **BYTE** callFwdTypeAndPlan::numberType

## 8.70 callFWExtInfo Struct Reference

### Data Fields

- [BYTE SvcStatus](#)
- [BYTE SvcClass](#)
- [BYTE noReplyTimer](#)
- [BYTE PI](#)
- [BYTE SI](#)
- [BYTE numType](#)
- [BYTE numPlan](#)
- [BYTE numLen](#)
- [BYTE number](#) [255]

### 8.70.1 Detailed Description

This structure contains information for Get Call Forwarding Extended Information.

#### Parameters

<i>SvcStatus</i>	<ul style="list-style-type: none"> <li>• Service status. Values: <ul style="list-style-type: none"> <li>– 0x00 - SERVICE_STATUS_INACTIVE - Inactive</li> <li>– 0x01 - SERVICE_STATUS_ACTIVE - Active</li> </ul> </li> </ul>
------------------	---

<i>SvcClass</i>	<ul style="list-style-type: none"> <li>• Service Class is a combination (sum) of information class constants</li> <li>• See <a href="#">qaGobiApiTableSupServiceInfoClasses.h</a> for service classes.</li> </ul>
<i>noReplyTimer</i>	<ul style="list-style-type: none"> <li>• No reply timer value in seconds</li> <li>• A value of 0 indicates that no_reply_timer is ignored.</li> </ul>
<i>PI</i>	<ul style="list-style-type: none"> <li>• Presentation indicator; refer to [S1, Table 2.7.4.4-1] for valid values.</li> </ul>
<i>SI</i>	<ul style="list-style-type: none"> <li>• Number screening indicator.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_SI_USER_PROVIDED_NOT_SCREENED - Provided user is not screened</li> <li>– 0x01 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_PASSED - Provided user passed verification</li> <li>– 0x02 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_FAILED - Provided user failed verification</li> <li>– 0x03 - QMI_VOICE_SI_NETWORK_PROVIDED - Provided network</li> </ul> </li> </ul>
<i>numType</i>	<ul style="list-style-type: none"> <li>• Number type.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_TYPE_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_TYPE_INTERNATIONAL - International</li> <li>– 0x02 - QMI_VOICE_NUM_TYPE_NATIONAL - National</li> <li>– 0x03 - QMI_VOICE_NUM_TYPE_NETWORK_SPECIFIC - Network-specific</li> <li>– 0x04 - QMI_VOICE_NUM_TYPE_SUBSCRIBER - Subscriber</li> <li>– 0x05 - QMI_VOICE_NUM_TYPE_RESERVED - Reserved</li> <li>– 0x06 - QMI_VOICE_NUM_TYPE_ABBREVIATED - Abbreviated</li> <li>– 0x07 - QMI_VOICE_NUM_TYPE_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>

<i>numPlan</i>	<ul style="list-style-type: none"> <li>• Number plan.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_PLAN_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_PLAN_ISDN - ISDN</li> <li>– 0x03 - QMI_VOICE_NUM_PLAN_DATA - Data</li> <li>– 0x04 - QMI_VOICE_NUM_PLAN_TELEX - Telex</li> <li>– 0x08 - QMI_VOICE_NUM_PLAN_NATIONAL - National</li> <li>– 0x09 - QMI_VOICE_NUM_PLAN_PRIVATE - Private</li> <li>– 0x0B - QMI_VOICE_NUM_PLAN_RESERVED_CTS - Reserved cordless telephony system</li> <li>– 0x0F - QMI_VOICE_NUM_PLAN_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>
<i>numLen</i>	<ul style="list-style-type: none"> <li>• Provides the length of number which follow.</li> </ul>
<i>number[255]</i>	<ul style="list-style-type: none"> <li>• number of numLen length, NULL terminated.</li> </ul>

## 8.70.2 Field Documentation

8.70.2.1 **BYTE** callFWExtInfo::noReplyTimer

8.70.2.2 **BYTE** callFWExtInfo::number[255]

8.70.2.3 **BYTE** callFWExtInfo::numLen

8.70.2.4 **BYTE** callFWExtInfo::numPlan

8.70.2.5 **BYTE** callFWExtInfo::numType

8.70.2.6 **BYTE** callFWExtInfo::PI

8.70.2.7 **BYTE** callFWExtInfo::SI

8.70.2.8 **BYTE** callFWExtInfo::SvcClass

8.70.2.9 **BYTE** callFWExtInfo::SvcStatus

## 8.71 callFWInfo Struct Reference

### Data Fields

- [BYTE SvcStatus](#)
- [BYTE SvcClass](#)
- [BYTE numLen](#)
- [BYTE number \[255\]](#)
- [BYTE noReplyTimer](#)

### 8.71.1 Detailed Description

This structure contains information for Get Call Forwarding Information.

#### Parameters

<i>SvcStatus</i>	<ul style="list-style-type: none"> <li>Service status. Values: <ul style="list-style-type: none"> <li>0x00 - SERVICE_STATUS_INACTIVE - Inactive</li> <li>0x01 - SERVICE_STATUS_ACTIVE - Active</li> </ul> </li> </ul>
<i>SvcClass</i>	<ul style="list-style-type: none"> <li>Service Class is a combination (sum) of information class constants</li> <li>See <a href="#">qaGobiApiTableSupServiceInfoClasses.h</a> for service classes.</li> </ul>
<i>numLen</i>	<ul style="list-style-type: none"> <li>Provides the length of number which follow.</li> </ul>
<i>number[255]</i>	<ul style="list-style-type: none"> <li>number of numLen length, NULL terminated.</li> </ul>
<i>noReplyTimer</i>	<ul style="list-style-type: none"> <li>No reply timer value in seconds</li> <li>A value of 0 indicates that noReplyTimer is ignored.</li> </ul>

### 8.71.2 Field Documentation

8.71.2.1 **BYTE** callFWInfo::noReplyTimer

8.71.2.2 **BYTE** callFWInfo::number[255]

8.71.2.3 **BYTE** callFWInfo::numLen

8.71.2.4 **BYTE** callFWInfo::SvcClass

8.71.2.5 **BYTE** callFWInfo::SvcStatus

## 8.72 callInfo Struct Reference

#### Data Fields

- [BYTE](#) callID
- [BYTE](#) callState
- [BYTE](#) callType
- [BYTE](#) direction
- [BYTE](#) mode

### 8.72.1 Detailed Description

This structure contains Information about call state changes. For example, when an incoming call is received, this structure is populated and indicate the incoming call information. When this incoming call is answered, the call status changes from INCOMING to CONVERSATION, which means a change in the call information and this structure is populated again with the changes and notified to/retrived by the user.

#### Parameters

<i>callID</i>	<ul style="list-style-type: none"><li>• Call identifier for the call queried for information.</li><li>• If zero(0) then invalid.</li></ul>
<i>callState</i>	<ul style="list-style-type: none"><li>• Call state.<ul style="list-style-type: none"><li>– 0x01 - CALL_STATE_ORIGINATION - Origination</li><li>– 0x02 - CALL_STATE_INCOMING - Incoming</li><li>– 0x03 - CALL_STATE_CONVERSATION - Conversation</li><li>– 0x04 - CALL_STATE_CC_IN_PROGRESS - Call is originating but waiting for call control to complete</li><li>– 0x05 - CALL_STATE_ALERTING - Alerting</li><li>– 0x06 - CALL_STATE_HOLD - Hold</li><li>– 0x07 - CALL_STATE_WAITING - Waiting</li><li>– 0x08 - CALL_STATE_DISCONNECTING - Disconnecting</li><li>– 0x09 - CALL_STATE_END - End</li><li>– 0x0A - CALL_STATE_SETUP - MT call is in Setup state in 3GPP</li><li>– 0xFF - Not Available</li></ul></li></ul>

<i>callType</i>	<ul style="list-style-type: none"> <li>• Call type. <ul style="list-style-type: none"> <li>– 0x00 - CALL_TYPE_VOICE - Voice</li> <li>– 0x02 - CALL_TYPE_VOICE_IP - Voice over IP</li> <li>– 0x06 - CALL_TYPE_OTAPA - OTAPA</li> <li>– 0x07 - CALL_TYPE_STD_OTASP - Standard OTASP</li> <li>– 0x08 - CALL_TYPE_NON_STD_OTASP - Nonstandard OTASP</li> <li>– 0x09 - CALL_TYPE_EMERGENCY - Emergency</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>direction</i>	<ul style="list-style-type: none"> <li>• Direction. <ul style="list-style-type: none"> <li>– 0x01 - CALL_DIRECTION_MO - MO call</li> <li>– 0x02 - CALL_DIRECTION_MT - MT call</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>mode</i>	<ul style="list-style-type: none"> <li>• Mode.</li> <li>• If the mode field is "0x01 - CDMA", the optional Service Option, Voice Privacy, and OTASP Status (only for OTASP calls) TLVs are included in the response. <ul style="list-style-type: none"> <li>– 0x01 - CALL_MODE_CDMA - CDMA</li> <li>– 0x02 - CALL_MODE_GSM - GSM</li> <li>– 0x03 - CALL_MODE_UMTS - UMTS</li> <li>– 0x04 - CALL_MODE_LTE - LTE</li> <li>– 0x05 - CALL_MODE_TDS - TD-SCDMA</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

## 8.72.2 Field Documentation

### 8.72.2.1 BYTE callInfo::callID

### 8.72.2.2 BYTE callInfo::callState

### 8.72.2.3 BYTE callInfo::callType

### 8.72.2.4 BYTE callInfo::direction

### 8.72.2.5 BYTE callInfo::mode

## 8.73 callingPartyInfo Struct Reference

### Data Fields

- [BYTE PI](#)
- [BYTE SI](#)

- [BYTE numType](#)
- [BYTE numPlan](#)
- [BYTE numLen](#)
- [BYTE number](#) [255]

### 8.73.1 Detailed Description

This structure contains Calling party Number Information

#### Parameters

<i>PI</i>	<ul style="list-style-type: none"> <li>• Presentation indicator; refer to [S1, Table 2.7.4.4-1] for valid values.</li> </ul>
<i>SI</i>	<ul style="list-style-type: none"> <li>• Number of sets of following elements <ul style="list-style-type: none"> <li>– Caller Id</li> </ul> </li> </ul>
<i>SI</i>	<ul style="list-style-type: none"> <li>• Number screening indicator.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_SI_USER_PROVIDED_NOT_SCREENED - Provided user is not screened</li> <li>– 0x01 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_PASSED - Provided user passed verification</li> <li>– 0x02 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_FAILED - Provided user failed verification</li> <li>– 0x03 - QMI_VOICE_SI_NETWORK_PROVIDED - Provided network</li> </ul> </li> </ul>
<i>numType</i>	<ul style="list-style-type: none"> <li>• Number type.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_TYPE_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_TYPE_INTERNATIONAL - International</li> <li>– 0x02 - QMI_VOICE_NUM_TYPE_NATIONAL - National</li> <li>– 0x03 - QMI_VOICE_NUM_TYPE_NETWORK_SPECIFIC - Network-specific</li> <li>– 0x04 - QMI_VOICE_NUM_TYPE_SUBSCRIBER - Subscriber</li> <li>– 0x05 - QMI_VOICE_NUM_TYPE_RESERVED - Reserved</li> <li>– 0x06 - QMI_VOICE_NUM_TYPE_ABBREVIATED - Abbreviated</li> <li>– 0x07 - QMI_VOICE_NUM_TYPE_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>

<i>numPlan</i>	<ul style="list-style-type: none"> <li>• Number plan.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_PLAN_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_PLAN_ISDN - ISDN</li> <li>– 0x03 - QMI_VOICE_NUM_PLAN_DATA - Data</li> <li>– 0x04 - QMI_VOICE_NUM_PLAN_TELEX - Telex</li> <li>– 0x08 - QMI_VOICE_NUM_PLAN_NATIONAL - National</li> <li>– 0x09 - QMI_VOICE_NUM_PLAN_PRIVATE - Private</li> <li>– 0x0B - QMI_VOICE_NUM_PLAN_RESERVED_CTS - Reserved cordless telephony system</li> <li>– 0x0F - QMI_VOICE_NUM_PLAN_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>
<i>numLen</i>	<ul style="list-style-type: none"> <li>• Provides the length of number which follow.</li> </ul>
<i>number[255]</i>	<ul style="list-style-type: none"> <li>• number of numLen length, NULL terminated.</li> </ul>

## 8.73.2 Field Documentation

8.73.2.1 **BYTE** callingPartyInfo::number[255]

8.73.2.2 **BYTE** callingPartyInfo::numLen

8.73.2.3 **BYTE** callingPartyInfo::numPlan

8.73.2.4 **BYTE** callingPartyInfo::numType

8.73.2.5 **BYTE** callingPartyInfo::PI

8.73.2.6 **BYTE** callingPartyInfo::SI

## 8.74 cardResult Struct Reference

### Data Fields

- [BYTE sw1](#)
- [BYTE sw2](#)

### 8.74.1 Detailed Description

This structure contains the information about the card result.



## Parameters

<i>sw1</i>	<ul style="list-style-type: none"> <li>• SW1 received from the card.</li> </ul>
<i>sw2</i>	<ul style="list-style-type: none"> <li>• SW2 received from the card.</li> </ul>

## 8.74.2 Field Documentation

## 8.74.2.1 BYTE cardResult::sw1

## 8.74.2.2 BYTE cardResult::sw2

## 8.75 cardStatus Struct Reference

## Data Fields

- [WORD indexGwPri](#)
- [WORD index1xPri](#)
- [WORD indexGwSec](#)
- [WORD index1xSec](#)
- [BYTE numSlot](#)
- [slotInfo SlotInfo](#) [5]

## 8.75.1 Detailed Description

This structure contains Card Status Information.

## Parameters

<i>indexGwPri</i>	<ul style="list-style-type: none"> <li>• Index of the primary GW provisioning application.</li> <li>• The most significant byte indicates the slot (starting from 0), while the least significant byte indicates the application for that slot (starting from 0).</li> <li>• The value 0xFFFF identifies when the session does not exist.</li> </ul>
<i>index1xPri</i>	<ul style="list-style-type: none"> <li>• Index of the primary 1X provisioning application.</li> <li>• The most significant byte indicates the slot (starting from 0), while the least significant byte indicates the application for that slot (starting from 0).</li> <li>• The value 0xFFFF identifies when the session does not exist.</li> </ul>

<i>indexGwSec</i>	<ul style="list-style-type: none"> <li>• Index of the secondary GW provisioning application.</li> <li>• The most significant byte indicates the slot (starting from 0), while the least significant byte indicates the application for that slot (starting from 0).</li> <li>• The value 0xFFFF identifies when the session does not exist.</li> </ul>
<i>index1xSec</i>	<ul style="list-style-type: none"> <li>• Index of the secondary GW provisioning application.</li> <li>• The most significant byte indicates the slot (starting from 0), while the least significant byte indicates the application for that slot (starting from 0).</li> <li>• The value 0xFFFF identifies when the session does not exist.</li> </ul>
<i>numSlot</i>	<ul style="list-style-type: none"> <li>• Indicates the number of slots available on the device.</li> <li>• The following block is repeated for each slot. i.e. cardState</li> <li>• If zero(0) then no cardState information exists.</li> </ul>
<i>SlotInfo[MAX_N-O_OF_SLOTS]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">slotInfo</a> for more information.</li> </ul>

## 8.75.2 Field Documentation

8.75.2.1 **WORD** cardStatus::index1xPri

8.75.2.2 **WORD** cardStatus::index1xSec

8.75.2.3 **WORD** cardStatus::indexGwPri

8.75.2.4 **WORD** cardStatus::indexGwSec

8.75.2.5 **BYTE** cardStatus::numSlot

8.75.2.6 **slotInfo** cardStatus::SlotInfo[5]

## 8.76 CarrierImage\_t Struct Reference

### Data Fields

- uint32\_t [m\\_nCarrierId](#)
- uint32\_t [m\\_nFolderId](#)
- uint32\_t [m\\_nStorage](#)
- uint8\_t [m\\_FwImageId](#) [16]
- uint8\_t [m\\_FwBuildId](#) [32]
- uint8\_t [m\\_PriImageId](#) [16]
- uint8\_t [m\\_PriBuildId](#) [32]

### 8.76.1 Detailed Description

This structure contains the Carrier Image parameters.

## Parameters

<i>m_nCarrierId</i>	<ul style="list-style-type: none"> <li>• Unique numeric carrier ID indicating the carrier that the following images belong to</li> </ul>
<i>m_nFolderId</i>	<ul style="list-style-type: none"> <li>• Unique numeric folder ID indicating the folder where the images should reside on the host storage.</li> </ul>
<i>m_nStorage</i>	<ul style="list-style-type: none"> <li>• Information of storage type</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Device</li> <li>– 1 - Host</li> </ul> </li> </ul>
<i>m_FwImageId</i>	<ul style="list-style-type: none"> <li>• Firmware image ID</li> </ul>
<i>m_FwBuildId</i>	<ul style="list-style-type: none"> <li>• Firmware build ID</li> </ul>
<i>m_PriImageId</i>	<ul style="list-style-type: none"> <li>• PRI image ID</li> </ul>
<i>m_PriBuildId</i>	<ul style="list-style-type: none"> <li>• PRI build ID</li> </ul>

## 8.76.2 Field Documentation

8.76.2.1 `uint8_t CarrierImage_t::m_FwBuildId[32]`8.76.2.2 `uint8_t CarrierImage_t::m_FwImageId[16]`8.76.2.3 `uint32_t CarrierImage_t::m_nCarrierId`8.76.2.4 `uint32_t CarrierImage_t::m_nFolderId`8.76.2.5 `uint32_t CarrierImage_t::m_nStorage`8.76.2.6 `uint8_t CarrierImage_t::m_PriBuildId[32]`8.76.2.7 `uint8_t CarrierImage_t::m_PriImageId[16]`

## 8.77 CatAIPhalIdentifierTlv Struct Reference

## Data Fields

- [BYTE ReferenceID](#)
- [USHORT AlphaIDLength](#)
- [BYTE AlphaID \[255\]](#)

### 8.77.1 Detailed Description

structure used to store all Alpha Identifier parameters.

Parameters

<i>ReferenceID</i>	- proactive command type that included the alpha identifier – 0x01; sends SMS proactive command
<i>AlphaIDLength</i>	- length of AlphaID ( in bytes )
<i>AlphaID</i>	- alpha identifier, encoded as in ETSI TS 102 223 [Section 8.2]

### 8.77.2 Field Documentation

8.77.2.1 **BYTE** CatAlPhalIdentifierTlv::AlphaID[255]

8.77.2.2 **USHORT** CatAlPhalIdentifierTlv::AlphaIDLength

8.77.2.3 **BYTE** CatAlPhalIdentifierTlv::ReferenceID

## 8.78 CatCommonEventTlv Struct Reference

Data Fields

- [BYTE](#) TlvPresent
- [BYTE](#) EventID
- [WORD](#) EventLength
- union [currentCatEvent](#) [CatEvent](#)

### 8.78.1 Field Documentation

8.78.1.1 union [currentCatEvent](#) CatCommonEventTlv::CatEvent

8.78.1.2 **BYTE** CatCommonEventTlv::EventID

8.78.1.3 **WORD** CatCommonEventTlv::EventLength

8.78.1.4 **BYTE** CatCommonEventTlv::TlvPresent

## 8.79 CatEndProactiveSessionTlv Struct Reference

Data Fields

- [BYTE](#) EndProactiveSession

### 8.79.1 Detailed Description

structure used to store End Proactive Session event parameters.

Parameters

---

<i>EndProactiveSession</i>	- The proactive session end type values are: <ul style="list-style-type: none"> <li>• 0x01 – End proactive session command type received from the card</li> <li>• 0x02 – End proactive session internal to ME</li> </ul>
----------------------------	--

## 8.79.2 Field Documentation

### 8.79.2.1 BYTE CatEndProactiveSessionTlv::EndProactiveSession

## 8.80 CATEventDataType Struct Reference

### Data Fields

- [ULONG eventMask](#)
- [ULONG \\* pErrorMask](#)

## 8.80.1 Field Documentation

### 8.80.1.1 ULONG CATEventDataType::eventMask

### 8.80.1.2 ULONG\* CATEventDataType::pErrorMask

## 8.81 CatEventIDDataTlv Struct Reference

### Data Fields

- [ULONG ReferenceID](#)
- [USHORT DataLength](#)
- [BYTE Data](#) [255]

## 8.81.1 Detailed Description

structure used to store all Common CAT Event parameters.

### Parameters

<i>ReferenceID</i>	- proactive command reference ID.
<i>DataLength</i>	- length of pData ( in Bytes )
<i>Data</i>	- command specific to the CAT event ID, encoded as in ETSI TS 102 223 [Section 6.6.X]

## 8.81.2 Field Documentation

### 8.81.2.1 BYTE CatEventIDDataTlv::Data[255]

### 8.81.2.2 USHORT CatEventIDDataTlv::DataLength

### 8.81.2.3 ULONG CatEventIDDataTlv::ReferenceID

## 8.82 CatEventListTlv Struct Reference

## Data Fields

- [ULONG SetupEventList](#)

### 8.82.1 Detailed Description

structure used to store all Event List parameters.

#### Parameters

<i>SetupEventList</i>	- Setup event list bit mask <ul style="list-style-type: none"> <li>• 0x00000001 – User Activity Notify</li> <li>• 0x00000002 – Idle Screen Available</li> <li>• 0x00000004 – Lang Selection Notify Each set bit indicates the availability of the corresponding event in Setup Event list proactive command; all unlisted bits are reserved for future use and will be ignored</li> </ul>
-----------------------	---

### 8.82.2 Field Documentation

#### 8.82.2.1 ULONG CatEventListTlv::SetupEventList

## 8.83 CatRefreshTlv Struct Reference

## Data Fields

- [USHORT RefreshMode](#)
- [BYTE RefreshStage](#)

### 8.83.1 Detailed Description

structure used to store all Refresh Event parameters.

#### Parameters

<i>RefreshMode</i>	- The Refresh Event as in ETSI TS 102 223 [Section 8.6]
<i>RefreshStage</i>	- Stage of a refresh procedure <ul style="list-style-type: none"> <li>• 0x01 – Refresh start</li> <li>• 0x02 – Refresh success</li> <li>• 0x03 – Refresh failed</li> </ul>

### 8.83.2 Field Documentation

#### 8.83.2.1 USHORT CatRefreshTlv::RefreshMode

#### 8.83.2.2 BYTE CatRefreshTlv::RefreshStage

## 8.84 ccSUPSType Struct Reference

## Data Fields

- [BYTE svcType](#)
- [BYTE reason](#)

### 8.84.1 Detailed Description

This structure contains information about the Call Control Supplementary Service Types

#### Parameters

<i>svcType</i>	<ul style="list-style-type: none"> <li>• Service type. <ul style="list-style-type: none"> <li>– 0x01 - VOICE_CC_SUPS_RESULT_SERVICE_TYPE_ACTIVATE - Activate</li> <li>– 0x02 - VOICE_CC_SUPS_RESULT_SERVICE_TYPE_DEACTIVATE - Deactivate</li> <li>– 0x03 - VOICE_CC_SUPS_RESULT_SERVICE_TYPE_REGISTER - Register</li> <li>– 0x04 - VOICE_CC_SUPS_RESULT_SERVICE_TYPE_ERASE - Erase</li> <li>– 0x05 - VOICE_CC_SUPS_RESULT_SERVICE_TYPE_INTERROGATE - Interrogate</li> <li>– 0x06 - VOICE_CC_SUPS_RESULT_SERVICE_TYPE_REGISTER_PASSWORD - Register password</li> <li>– 0x07 - VOICE_CC_SUPS_RESULT_SERVICE_TYPE_USSD - USSD</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>reason</i>	<ul style="list-style-type: none"> <li>• Call control supplementary service result reason</li> <li>• Values: <ul style="list-style-type: none"> <li>– See <a href="#">qaGobiApiTableCallControlReturnReasons.h</a> for return reasons.</li> </ul> </li> </ul>

### 8.84.2 Field Documentation

#### 8.84.2.1 `BYTE ccSUPSType::reason`

#### 8.84.2.2 `BYTE ccSUPSType::svcType`

## 8.85 CDMABroadcastConfig Struct Reference

## Data Fields

- [WORD serviceCategory](#)
- [WORD language](#)
- [BYTE selected](#)

### 8.85.1 Detailed Description

This structure contains [CDMABroadcastConfig](#) parameters



## Parameters

<i>serviceCategory</i>	<ul style="list-style-type: none"> <li>• Service category</li> </ul>
<i>language</i>	<ul style="list-style-type: none"> <li>• Language</li> </ul>
<i>selected</i>	<ul style="list-style-type: none"> <li>• Specified service_category and language <ul style="list-style-type: none"> <li>– 0x00 – Not selected</li> <li>– 0x01 – Selected</li> </ul> </li> </ul>

## 8.85.2 Field Documentation

8.85.2.1 WORD CDMABroadcastConfig::language

8.85.2.2 BYTE CDMABroadcastConfig::selected

8.85.2.3 WORD CDMABroadcastConfig::serviceCategory

## 8.86 CDMAChannel Struct Reference

## Data Fields

- [WORD priChA](#)
- [WORD priChB](#)
- [WORD secChA](#)
- [WORD secChB](#)

## 8.86.1 Detailed Description

This structure contains the parameters for CDMA Channel Information

## Parameters

<i>priChA</i>	<ul style="list-style-type: none"> <li>• A Channel number for the primary carrier. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>priChB</i>	<ul style="list-style-type: none"> <li>• B Channel number for the primary carrier. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>

<i>secChA</i>	<ul style="list-style-type: none"> <li>• A Channel number for the secondary carrier. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>secChB</i>	<ul style="list-style-type: none"> <li>• B Channel number for the secondary carrier. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>

## 8.86.2 Field Documentation

8.86.2.1 WORD CDMAChannel::priChA

8.86.2.2 WORD CDMAChannel::priChB

8.86.2.3 WORD CDMAChannel::secChA

8.86.2.4 WORD CDMAChannel::secChB

## 8.87 CDMAECIOThresh Struct Reference

### Data Fields

- [BYTE CDMAECIOThreshListLen](#)
- [WORD \\* pCDMAECIOThreshList](#)

### 8.87.1 Detailed Description

This structure contains CDMA ECIO threshold related parameters.

#### Parameters

<i>CDMAECIO- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the CDMA ECIO threshold list parameter to follow</li> </ul>
<i>pCDMAECIO- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of ECIO thresholds (in units of 0.1 dB)</li> <li>• Maximum of 32 values. Range for ECIO values: -31.5 to 0 (in dB)</li> </ul>

## 8.87.2 Field Documentation

8.87.2.1 BYTE CDMAECIOThresh::CDMAECIOThreshListLen

8.87.2.2 WORD\* CDMAECIOThresh::pCDMAECIOThreshList

## 8.88 CDMAInfo Struct Reference

## Data Fields

- [WORD sid](#)
- [WORD nid](#)
- [WORD baseld](#)
- [WORD refpn](#)
- [ULONG baseLat](#)
- [ULONG baseLong](#)

## 8.88.1 Detailed Description

This structure contains information about the CDMA Network.

## Parameters

<i>sid</i>	<ul style="list-style-type: none"> <li>• System ID. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>nid</i>	<ul style="list-style-type: none"> <li>• Network ID. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>baseld</i>	<ul style="list-style-type: none"> <li>• Base station ID. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>refpn</i>	<ul style="list-style-type: none"> <li>• Reference PN. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>baseLat</i>	<ul style="list-style-type: none"> <li>• Latitude of the current base station in units of 0.25 sec. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>baseLong</i>	<ul style="list-style-type: none"> <li>• Longitude of the current base station in units of 0.25 sec. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>

## 8.88.2 Field Documentation

## 8.88.2.1 WORD CDMAInfo::baseld

## 8.88.2.2 ULONG CDMAInfo::baseLat

8.88.2.3 **ULONG** CDMAInfo::baseLong

8.88.2.4 **WORD** CDMAInfo::nid

8.88.2.5 **WORD** CDMAInfo::refpn

8.88.2.6 **WORD** CDMAInfo::sid

## 8.89 cdmaMsgDecodingParams Struct Reference

### Data Fields

- [ULONG](#) [messageLength](#)
- [BYTE](#) \* [pMessage](#)
- [ULONG](#) \* [pMessageID](#)
- [BYTE](#) \* [pSenderAddrLength](#)
- [CHAR](#) \* [pSenderAddr](#)
- [BYTE](#) \* [pTextMsgLength](#)
- [WORD](#) \* [pTextMsg](#)
- [BYTE](#) \* [pPriority](#)
- [BYTE](#) \* [pPrivacy](#)
- [BYTE](#) \* [pLanguage](#)
- [BYTE](#) [mcTimeStamp](#) [0x08]
- [BYTE](#) [absoluteValidity](#) [0x08]
- [BYTE](#) \* [pRelativeValidity](#)
- [BYTE](#) \* [pDisplayMode](#)
- [BOOL](#) \* [pUserAcknowledgementReq](#)
- [BOOL](#) \* [pReadAcknowledgementReq](#)
- [BYTE](#) \* [pAlertPriority](#)
- [BYTE](#) \* [pCallbkAddrLength](#)
- [CHAR](#) \* [pCallbkAddr](#)

### 8.89.1 Detailed Description

Structure contains parameters which need to be decoded from message

#### Parameters

<i>messageLength</i> [IN]	<ul style="list-style-type: none"> <li>Length of the message to be decoded in bytes</li> </ul>
<i>pMessage</i> [IN]	<ul style="list-style-type: none"> <li>Message read off the device via GetSMS</li> </ul>
<i>pSenderAddrLength</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Upon input, indicates the maximum number of ASCII characters (including NULL termination) that the pSenderAddr buffer can accommodate. Note that a length of 14 is reasonable. Upon successful output, returns the length of originating address string (including the NULL termination)</li> </ul>

<i>pSenderAddr[OUT]</i>	<ul style="list-style-type: none"> <li>Returns NULL-terminated ASCII String containing the originating address. International number will be prepended with a '+' character</li> </ul>
<i>pTextMsgLength[IN/OUT]</i>	<ul style="list-style-type: none"> <li>Upon input, specifies the number of UCS2 characters the given text message buffer can accommodate. Upon successful output, returns the number of UCS2 characters returns in the given text messagebuffer(including NULL-terminator)</li> </ul>
<i>pTextMsg[OUT]</i>	<ul style="list-style-type: none"> <li>Returns the text message as NULL-terminated UCS2 string</li> </ul>
<i>pPriority[OUT]</i>	(optional parameter) <ul style="list-style-type: none"> <li>Returns the priority setting of the message 0x00 - normal 0x01 - interactive 0x02 - urgent 0x03 - emergency 0xFF - unavailable setting</li> </ul>
<i>pPrivacy[OUT](optional)</i>	parameter) <ul style="list-style-type: none"> <li>Returns the privacy setting of the message 0x00 - not restricted 0x01 - restricted 0x02 - confidential 0x03 - secret 0xFF - unavailable setting</li> </ul>
<i>pLanguage[OUT]</i>	(optional parameter ) <ul style="list-style-type: none"> <li>Returns the language setting of the message 0x00 - unspecified 0x01 - english 0x02 - french 0x03 - spanish 0x04 - japanese 0x05 - korean 0x06 - chinese 0x07 - hebrew 0xFF - unavailable setting</li> </ul>
<i>mcTimeStamp[8][OUT]</i>	(optional parameter) <ul style="list-style-type: none"> <li>Returns the message center timestamp which takes the form: YYMMDDHHMMSS-TZ where YY - year MM - month DD - day HH - hour MM - minute SS - second TZ - timezone All values are in decimal. Timezone is in relation to GMT, one unit is equal to 15 minutes and MSB indicates a negative value. If this information is unavailable for message then this field will be filled with 0xFF</li> </ul>
<i>absoluteValidity[8][OUT]</i>	(optional parameter) <ul style="list-style-type: none"> <li>Returns the absolute validity period setting for this message. This field takes the same form as mcTimeStamp</li> </ul>
<i>pRelativeValidity[OUT]</i>	(optional parameter) <ul style="list-style-type: none"> <li>Returns the relative validity period. Values have the following meanings: 0 to 143: validity period =(value + 1)* 5 minutes 144 to 167: validity period =12 hours+(value - 143)*30 minutes 168 to 196: validity period = (value - 166) * 1 day 197 to 244: validity period = (value - 192) * 1 week 245: validity period = indefinite 246: validity period = immediate 247: validity period = valid until mobile becomes inactive 248: validity period = valid until registration area changes 249 to 254: reserved 255: unavailable information</li> </ul>
<i>pDisplayMode[OUT]</i>	(optional parameter) <ul style="list-style-type: none"> <li>Returns the display mode parameter 0x00 - immediate display 0x01 - mobile default setting 0x02 - user invoked 0x03 - reserved 0xFF - unavailable parameter</li> </ul>
<i>pUserAcknowledgementReq[OUT]</i>	(optional parameter) <ul style="list-style-type: none"> <li>Returns the user (manual) acknowledgment request parameter TRUE - means the user is requested to manually acknowledge the delivery of the message. FALSE - means no such user acknowledgement is requested</li> </ul>
Generated on Tue Jul 12 2016 10:59:49 for LinuxQMISDK by Doxygen	
<i>pReadAcknowledgementReq[OUT]</i>	(optional parameter) <ul style="list-style-type: none"> <li>Returns the read acknowledgement request parameter TRUE - means acknowledgment of the message being viewed is requested. FALSE - means no such read ac-</li> </ul>

## 8.89.2 Field Documentation

- 8.89.2.1 **BYTE** cdmaMsgDecodingParams::absoluteValidity[0x08]
- 8.89.2.2 **BYTE** cdmaMsgDecodingParams::mcTimeStamp[0x08]
- 8.89.2.3 **ULONG** cdmaMsgDecodingParams::messageLength
- 8.89.2.4 **BYTE\*** cdmaMsgDecodingParams::pAlertPriority
- 8.89.2.5 **CHAR\*** cdmaMsgDecodingParams::pCallbkAddr
- 8.89.2.6 **BYTE\*** cdmaMsgDecodingParams::pCallbkAddrLength
- 8.89.2.7 **BYTE\*** cdmaMsgDecodingParams::pDisplayMode
- 8.89.2.8 **BYTE\*** cdmaMsgDecodingParams::pLanguage
- 8.89.2.9 **BYTE\*** cdmaMsgDecodingParams::pMessage
- 8.89.2.10 **ULONG\*** cdmaMsgDecodingParams::pMessageID
- 8.89.2.11 **BYTE\*** cdmaMsgDecodingParams::pPriority
- 8.89.2.12 **BYTE\*** cdmaMsgDecodingParams::pPrivacy
- 8.89.2.13 **BOOL\*** cdmaMsgDecodingParams::pReadAcknowledgementReq
- 8.89.2.14 **BYTE\*** cdmaMsgDecodingParams::pRelativeValidity
- 8.89.2.15 **CHAR\*** cdmaMsgDecodingParams::pSenderAddr
- 8.89.2.16 **BYTE\*** cdmaMsgDecodingParams::pSenderAddrLength
- 8.89.2.17 **WORD\*** cdmaMsgDecodingParams::pTextMsg
- 8.89.2.18 **BYTE\*** cdmaMsgDecodingParams::pTextMsgLength
- 8.89.2.19 **BOOL\*** cdmaMsgDecodingParams::pUserAcknowledgementReq

## 8.90 cdmaMsgEncodingParams Struct Reference

### Data Fields

- **BYTE \*** pMessageSize
- **BYTE \*** pMessage
- **BYTE** messageld
- **CHAR \*** pDestAddr
- **CHAR \*** pCallbackAddr
- **ULONG** textMsgLength
- **WORD \*** pTextMsg
- **BYTE \*** pPriority
- **BYTE \*** pEncodingAlphabet
- **BYTE \*** pRelValidity

### 8.90.1 Detailed Description

Structure contains parameters for message to be encoded

## Parameters

<i>pMessageSize</i> [I- N/OUT]	<ul style="list-style-type: none"> <li>Upon input, specifies the total number of bytes that the given pMessage buffer can hold (a buffer of length 240 is recommended). Upon successful output, specifies the length of the constructed message placed in the pMessage buffer (in bytes)</li> </ul>
<i>pMessage</i> [OUT]	- The constructed raw message
<i>messageId</i> [IN]	<ul style="list-style-type: none"> <li>The message reference number for this message. This value should be incremented for every message the host application sends</li> </ul>
<i>pDestAddr</i> [IN]	<ul style="list-style-type: none"> <li>Gives NULL-terminated ASCII String containing a destination address. International number will be prepended with a '+' character</li> </ul>
<i>pCallbackAddr</i> [I- N]	<ul style="list-style-type: none"> <li>Gives NULL-terminated ASCII String containing a callback address. International number will be prepended with a '+' character</li> </ul>
<i>textMsgLength</i> [I- N]	<ul style="list-style-type: none"> <li>Number of UCS2 characters in the text message(excluding NULL)</li> </ul>
<i>pTextMsg</i> [IN]	<ul style="list-style-type: none"> <li>Text message to be encoded</li> </ul>
<i>pPriority</i> [I- N](optional	<p>parameter)</p> <ul style="list-style-type: none"> <li>Gives the priority of the outgoing message: 0 - normal (default if NULL pointer is given) 1 - interactive 2 - urgent 3 - emergency 64 - 64 is decoded value for URGENT VZAM Support interactive. 128 - 128 is decoded value for URGENT VZAM Support urgent. 192 - 128 is decoded value for URGENT VZAM Support emergency.</li> </ul>
<i>pEncoding- Alphabet</i> [IN/OU- T](optional	<p>parameter)</p> <ul style="list-style-type: none"> <li>Upon input, specifies the alphabet the text message should be encoded in 0 - 8bit ASCII (not supported at this time) 1 - IS91EP (not supported at this time) 2 - 7bit ASCII (default if NULL pointer is given) 3 - IA5 (not supported at this time) 4 - unicode (not supported at this time) 5 - shift JIS (not supported at this time) 6 - korean (not supported at this time) 7 - latin hebrew (not supported at this time) 8 - latin (not supported at this time) 9 - GSM 7 bit default Upon successful output, specifies the alphabet used to encode the message.</li> </ul>



<i>pRelValidity</i> [1-N](optional)	parameter) <ul style="list-style-type: none"> <li>• Gives the relative validity period of the outgoing message 0 - Set Relative validity to 11 1 - Set Relative validity to 71 2 - Set Relative validity to 167 3 - Set Relative validity to 169 4 - Set Relative validity to 171 Values have the following meanings: 0 to 143: validity period = (value + 1)* 5 minutes 144 to 167: validity period = 12 hours + (value - 143)*30 minutes 168 to 196: validity period = (value - 166) * 1 day 197 to 244: validity period = (value - 192) * 1 week 245: validity period = indefinite</li> </ul>
-------------------------------------	--

Currently only encoding of 7bit ASCII messages is supported.

## 8.90.2 Field Documentation

8.90.2.1 **BYTE** cdmaMsgEncodingParams::messageld

8.90.2.2 **CHAR\*** cdmaMsgEncodingParams::pCallbackAddr

8.90.2.3 **CHAR\*** cdmaMsgEncodingParams::pDestAddr

8.90.2.4 **BYTE\*** cdmaMsgEncodingParams::pEncodingAlphabet

8.90.2.5 **BYTE\*** cdmaMsgEncodingParams::pMessage

8.90.2.6 **BYTE\*** cdmaMsgEncodingParams::pMessageSize

8.90.2.7 **BYTE\*** cdmaMsgEncodingParams::pPriority

8.90.2.8 **BYTE\*** cdmaMsgEncodingParams::pRelValidity

8.90.2.9 **WORD\*** cdmaMsgEncodingParams::pTextMsg

8.90.2.10 **ULONG** cdmaMsgEncodingParams::textMsgLength

## 8.91 CDMARSSIThresh Struct Reference

### Data Fields

- [BYTE](#) CDMARSSIThreshListLen
- [WORD \\*](#) [pCDMARSSIThreshList](#)

### 8.91.1 Detailed Description

This structure contains CDMA RSSI threshold related parameters.

#### Parameters

<i>CDMARSSI-ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the CDMARSSI threshold list parameter to follow</li> </ul>
<i>pCDMARSSI-ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>• maximum of 32 values.</li> <li>• Range for RSSI values:-105 to -21 (in dBm).</li> </ul>

## 8.91.2 Field Documentation

8.91.2.1 **BYTE** CDMARSSIThresh::CDMARSSIThreshListLen

8.91.2.2 **WORD\*** CDMARSSIThresh::pCDMARSSIThreshList

## 8.92 CDMASSInfo Struct Reference

### Data Fields

- [INT8](#) [rssi](#)
- [SHORT](#) [ecio](#)

### 8.92.1 Detailed Description

This structure contains the parameters for CDMA/WCDMA Signal Strength Information

#### Parameters

<i>rssi</i>	<ul style="list-style-type: none"> <li>• RSSI in dBm (signed value).</li> <li>• A value of -125 dBm or lower is used to indicate No Signal.</li> </ul>
<i>ecio</i>	<ul style="list-style-type: none"> <li>• ECIO value representing negative 0.5 dBm increments, i.e., 2 means -1 dBm (14 means -7 dBm, 63 means -31.5 dBm).</li> </ul>

## 8.92.2 Field Documentation

8.92.2.1 **SHORT** CDMASSInfo::ecio

8.92.2.2 **INT8** CDMASSInfo::rssi

## 8.93 cdmaSSInfo Struct Reference

### Data Fields

- [int8\\_t](#) [rssi](#)
- [int16\\_t](#) [ecio](#)

### 8.93.1 Detailed Description

#### Parameters

<i>rssi</i>	RSSI in dBm.
<i>ecio</i>	ECIO value representing negative 0.5 dBm increment

## 8.93.2 Field Documentation

8.93.2.1 **int16\_t** cdmaSSInfo::ecio

8.93.2.2 `int8_t cdmaSSInfo::rsi`

## 8.94 CDMA SysInfo Struct Reference

### Data Fields

- [sysInfoCommon](#) [sysInfoCDMA](#)
- [BYTE](#) [isSysPrlMatchValid](#)
- [BYTE](#) [isSysPrlMatch](#)
- [BYTE](#) [pRevInUseValid](#)
- [BYTE](#) [pRevInUse](#)
- [BYTE](#) [bsPRevValid](#)
- [BYTE](#) [bsPRev](#)
- [BYTE](#) [ccsSupportedValid](#)
- [BYTE](#) [ccsSupported](#)
- [BYTE](#) [cdmaSysIdValid](#)
- [WORD](#) [systemID](#)
- [WORD](#) [networkID](#)
- [BYTE](#) [bsInfoValid](#)
- [WORD](#) [baseId](#)
- [ULONG](#) [baseLat](#)
- [ULONG](#) [baseLong](#)
- [BYTE](#) [packetZoneValid](#)
- [WORD](#) [packetZone](#)
- [BYTE](#) [networkIdValid](#)
- [BYTE](#) [MCC](#) [3]
- [BYTE](#) [MNC](#) [3]

### 8.94.1 Detailed Description

Structure for storing the CDMA System Information.

#### Parameters

<i>sysInfoCDMA</i>	<ul style="list-style-type: none"><li>• See <a href="#">sysInfoCommon</a> for more information.</li></ul>
<i>isSysPrlMatch-Valid</i>	<ul style="list-style-type: none"><li>• Indicates whether the system PRL match is valid.<ul style="list-style-type: none"><li>– 0x00 - Invalid</li><li>– 0x01 - Valid</li><li>– 0xFF - Not Available</li></ul></li></ul>

<i>isSysPrIMatch</i>	<ul style="list-style-type: none"> <li>Indicates whether the system is in a PRL.</li> <li>Only applies to CDMA/HDR. <ul style="list-style-type: none"> <li>0x00 - System is not in a PRL</li> <li>0x01 - System is in a PRL</li> <li>0xFF - Not Available</li> </ul> </li> <li>If the system is not in a PRL, roam_status carries the value from the default roaming indicator in the PRL.</li> <li>If the system is in a PRL, roam_status is set to the value based on the standard specification.</li> </ul>
<i>pRevInUseValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the P_Rev in use is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>pRevInUse</i>	<ul style="list-style-type: none"> <li>The lesser of the base station P_Rev and mobile P_Rev</li> <li>Only applicable for CDMA. <ul style="list-style-type: none"> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>bsPRevValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the base station P_Rev is valid <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>bsPRev</i>	<ul style="list-style-type: none"> <li>Base station P_Rev.</li> <li>Only applicable for CDMA. <ul style="list-style-type: none"> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>ccsSupported-Valid</i>	<ul style="list-style-type: none"> <li>Indicates whether the supported concurrent service is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

<i>ccsSupported</i>	<ul style="list-style-type: none"> <li>• Whether concurrent service is supported.</li> <li>• Only applicable for CDMA. <ul style="list-style-type: none"> <li>– 0x00 - Not supported</li> <li>– 0x01 - Supported</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>cdmaSysIdValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the CDMA system ID is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>systemID</i>	<ul style="list-style-type: none"> <li>• System ID. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>networkID</i>	<ul style="list-style-type: none"> <li>• Network ID. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>bsInfoValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the base station information is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>baseLat</i>	<ul style="list-style-type: none"> <li>• Base station latitude in units of 0.25 sec.</li> <li>• Expressed as a two's complement signed number with positive numbers signifying North latitudes. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>baseLong</i>	<ul style="list-style-type: none"> <li>• Base station longitude in units of 0.25 sec.</li> <li>• Expressed as a two's complement signed number with positive numbers signifying East latitudes. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>

<i>packetZoneValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the packet zone is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>packetZone</i>	<ul style="list-style-type: none"> <li>Packet zone (8-bit). <ul style="list-style-type: none"> <li>0xFFFF indicates no packet zone.</li> </ul> </li> <li>Only applicable for CDMA.</li> </ul>
<i>networkIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the network ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>MCC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Country Code.</li> <li>MCC digits in ASCII characters</li> <li>MCC wildcard value is returned as {'3', 0xFF, 0xFF}.</li> </ul>
<i>MNC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Network Code.</li> <li>MNC digits in ASCII characters</li> <li>An unused byte is set to 0xFF.</li> <li>MNC wildcard value is returned as {'7', 0xFF, 0xFF}.</li> </ul>

## 8.94.2 Field Documentation

8.94.2.1 WORD CDMA SysInfo::baseId

8.94.2.2 ULONG CDMA SysInfo::baseLat

8.94.2.3 ULONG CDMA SysInfo::baseLong

8.94.2.4 BYTE CDMA SysInfo::bsInfoValid

8.94.2.5 BYTE CDMA SysInfo::bsPRev

8.94.2.6 BYTE CDMA SysInfo::bsPRevValid

8.94.2.7 BYTE CDMA SysInfo::ccsSupported

- 8.94.2.8 **BYTE** CDMA SysInfo::ccsSupportedValid
- 8.94.2.9 **BYTE** CDMA SysInfo::cdmaSysIdValid
- 8.94.2.10 **BYTE** CDMA SysInfo::isSysPrIMatch
- 8.94.2.11 **BYTE** CDMA SysInfo::isSysPrIMatchValid
- 8.94.2.12 **BYTE** CDMA SysInfo::MCC[3]
- 8.94.2.13 **BYTE** CDMA SysInfo::MNC[3]
- 8.94.2.14 **WORD** CDMA SysInfo::networkID
- 8.94.2.15 **BYTE** CDMA SysInfo::networkIdValid
- 8.94.2.16 **WORD** CDMA SysInfo::packetZone
- 8.94.2.17 **BYTE** CDMA SysInfo::packetZoneValid
- 8.94.2.18 **BYTE** CDMA SysInfo::pRevInUse
- 8.94.2.19 **BYTE** CDMA SysInfo::pRevInUseValid
- 8.94.2.20 **sysInfoCommon** CDMA SysInfo::sysInfoCDMA
- 8.94.2.21 **WORD** CDMA SysInfo::systemID

## 8.95 CDMA SysInfoExt Struct Reference

### Data Fields

- [WORD MCC](#)
- [BYTE imsi\\_11\\_12](#)

### 8.95.1 Detailed Description

This structure contains CDMA system information extension

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
<i>imsi_11_12</i>	<ul style="list-style-type: none"> <li>• IMSI_11_12</li> </ul>

### 8.95.2 Field Documentation

- 8.95.2.1 **BYTE** CDMA SysInfoExt::imsi\_11\_12

## 8.95.2.2 WORD CDMA SysInfoExt::MCC

## 8.96 CellDb Struct Reference

## Data Fields

- [ULONG mask](#)

## 8.96.1 Detailed Description

This structure contains the cell database

## Parameters

<i>mask</i>	<ul style="list-style-type: none"> <li>• Mask for the cell database assistance data that is to be deleted</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– 0x00000001 - DELETE_CELLDB_POS</li> <li>– 0x00000002 - DELETE_CELLDB_LATEST_GPS_POS</li> <li>– 0x00000004 - DELETE_CELLDB_OTA_POS</li> <li>– 0x00000008 - DELETE_CELLDB_EXT_REF_POS</li> <li>– 0x00000010 - DELETE_CELLDB_TIMETAG</li> <li>– 0x00000020 - DELETE_CELLDB_CELLID</li> <li>– 0x00000040 - DELETE_CELLDB_CACHED_CELLID</li> <li>– 0x00000080 - DELETE_CELLDB_LAST_SRV_CELL</li> <li>– 0x00000100 - DELETE_CELLDB_CUR_SRV_CELL</li> <li>– 0x00000200 - DELETE_CELLDB_NEIGHBOR_INFO</li> </ul> </li> </ul>
-------------	--

## 8.96.2 Field Documentation

## 8.96.2.1 ULONG CellDb::mask

## 8.97 cellParams Struct Reference

## Data Fields

- [WORD pci](#)
- [SHORT rsrq](#)
- [SHORT rsrp](#)
- [SHORT rssi](#)
- [SHORT srxlev](#)

## 8.97.1 Detailed Description

This structure contains information about the Cell parameters.



## Parameters

<i>pci</i>	<ul style="list-style-type: none"> <li>Physical cell ID.</li> <li>Range: 0 to 503.</li> </ul>
<i>rsrq</i>	<ul style="list-style-type: none"> <li>Current RSRQ in 1/10 dB as measured by L1.</li> <li>Range: -20.0 dB to -3.0 dB.</li> </ul>
<i>rsrp</i>	<ul style="list-style-type: none"> <li>Current RSRP in 1/10 dBm as measured by L1.</li> <li>Range: -140.0 dBm to -44.0 dBm.</li> </ul>
<i>rssI</i>	<ul style="list-style-type: none"> <li>Current RSSI in 1/10 dBm as measured by L1.</li> <li>Range: -120.0 dBm to 0.</li> </ul>
<i>srxlev</i>	<ul style="list-style-type: none"> <li>Cell selection Rx level (Srxlev) value.</li> <li>Range: -128 to 128.</li> <li>This field is only valid when ue_in_idle is TRUE.</li> </ul>

## 8.97.2 Field Documentation

8.97.2.1 WORD cellParams::pci

8.97.2.2 SHORT cellParams::rsrp

8.97.2.3 SHORT cellParams::rsrq

8.97.2.4 SHORT cellParams::rssI

8.97.2.5 SHORT cellParams::srxlev

## 8.98 changeUIMPIN Struct Reference

## Data Fields

- BYTE pinID
- BYTE oldPINLen
- BYTE oldPINVal [255]
- BYTE pinLen
- BYTE pinVal [255]

## 8.98.1 Detailed Description

This structure contains the information about the pin parameters that need to be verified.

## Parameters

<i>pinID</i>	<ul style="list-style-type: none"> <li>Indicates the PIN ID to be changed. <ul style="list-style-type: none"> <li>1 - PIN1 (also called PIN)</li> <li>2 - PIN2</li> <li>3 - Universal PIN</li> <li>4 - Hidden key</li> </ul> </li> </ul>
<i>oldPINLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. old pin value.</li> </ul>
<i>oldPINVal</i> [MAX_DESCRIPTOR_LENGTH]	<ul style="list-style-type: none"> <li>Old PIN value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>
<i>pinLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. new pin value.</li> </ul>
<i>pinVal</i> [MAX_DESCRIPTOR_LENGTH]	<ul style="list-style-type: none"> <li>New PIN value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

## 8.98.2 Field Documentation

8.98.2.1 BYTE changeUIMPIN::oldPINLen

8.98.2.2 BYTE changeUIMPIN::oldPINVal[255]

8.98.2.3 BYTE changeUIMPIN::pinID

8.98.2.4 BYTE changeUIMPIN::pinLen

8.98.2.5 BYTE changeUIMPIN::pinVal[255]

## 8.99 ChannelRate Struct Reference

## Data Fields

- [ULONG CurrChanTxRate](#)
- [ULONG CurrChanRxRate](#)
- [ULONG MaxChanTxRate](#)
- [ULONG MaxChanRxRate](#)

## 8.99.1 Detailed Description

This structure contains Channel Rate

## Parameters

<i>CurrChanTxRate</i>	<ul style="list-style-type: none"> <li>Instantaneous channel Tx rate in bits per second</li> </ul>
<i>CurrChanRxRate</i>	<ul style="list-style-type: none"> <li>Instantaneous channel Rx rate in bits per second</li> </ul>
<i>MaxChanTxRate</i>	<ul style="list-style-type: none"> <li>maximum Tx rate that can be assigned to the device by the serving system in bits per second</li> </ul>
<i>MaxChanRxRate</i>	<ul style="list-style-type: none"> <li>maximum Rx rate that can be assigned to the device by the serving system in bits per second</li> </ul>

## 8.99.2 Field Documentation

8.99.2.1 **ULONG** ChannelRate::CurrChanRxRate8.99.2.2 **ULONG** ChannelRate::CurrChanTxRate8.99.2.3 **ULONG** ChannelRate::MaxChanRxRate8.99.2.4 **ULONG** ChannelRate::MaxChanTxRate

## 8.100 channelRate Struct Reference

## Data Fields

- [ULONG CurrChanTxRate](#)
- [ULONG CurrChanRxRate](#)

## 8.100.1 Detailed Description

This structure contains Channel Rate

## Parameters

<i>CurrChanTxRate</i>	<ul style="list-style-type: none"> <li>Max channel Tx rate in bits per second</li> </ul>
<i>CurrChanRxRate</i>	<ul style="list-style-type: none"> <li>Max channel Rx rate in bits per second</li> </ul>

## 8.100.2 Field Documentation

8.100.2.1 **ULONG** channelRate::CurrChanRxRate8.100.2.2 **ULONG** channelRate::CurrChanTxRate

## 8.101 CLIPResp Struct Reference

### Data Fields

- [BYTE ActiveStatus](#)
- [BYTE ProvisionStatus](#)

### 8.101.1 Detailed Description

This structure contains information about the Calling Line Identification Presentation (CLIP) supplementary service responses.

#### Parameters

<i>ActiveStatus</i>	<ul style="list-style-type: none"> <li>• Active status.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - ACTIVE_STATUS_INACTIVE - Inactive</li> <li>– 0x01 - ACTIVE_STATUS_ACTIVE - Active</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>ProvisionStatus</i>	<ul style="list-style-type: none"> <li>• Provisioned status.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - PROVISION_STATUS_NOT_PROVISIONED - Not provisioned</li> <li>– 0x01 - PROVISION_STATUS_PROVISIONED - Provisioned</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

### 8.101.2 Field Documentation

#### 8.101.2.1 BYTE CLIPResp::ActiveStatus

#### 8.101.2.2 BYTE CLIPResp::ProvisionStatus

## 8.102 CLIRResp Struct Reference

### Data Fields

- [BYTE ActiveStatus](#)
- [BYTE ProvisionStatus](#)

### 8.102.1 Detailed Description

This structure contains information about the Calling Line Identification Restriction (CLIR) supplementary service responses.

## Parameters

<i>ActiveStatus</i>	<ul style="list-style-type: none"> <li>• Active status.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - ACTIVE_STATUS_INACTIVE - Inactive</li> <li>– 0x01 - ACTIVE_STATUS_ACTIVE - Active</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>ProvisionStatus</i>	<ul style="list-style-type: none"> <li>• Provisioned status.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - PROVISION_STATUS_NOT_PROVISIONED - Not provisioned</li> <li>– 0x01 - PROVISION_STATUS_PROVISIONED_PERMANENT - Permanently provisioned</li> <li>– 0x02 - PROVISION_STATUS_PRESENTATION_RESTRICTED - Restricted presentation</li> <li>– 0x03 - PROVISION_STATUS_PRESENTATION_ALLOWED - Allowed presentation</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

## 8.102.2 Field Documentation

8.102.2.1 BYTE CLIRResp::ActiveStatus

8.102.2.2 BYTE CLIRResp::ProvisionStatus

## 8.103 ClkInfo Struct Reference

## Data Fields

- [ULONG mask](#)

## 8.103.1 Detailed Description

This structure contains the clock Info

## Parameters

<i>mask</i>	<ul style="list-style-type: none"> <li>• Mask for the clock information assistance data that is to be deleted</li> <li>• Valid bitmasks: <ul style="list-style-type: none"> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_TIME_EST (0x00000001) - Mask to delete time estimate from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_FREQ_EST (0x00000002) - Mask to delete frequency estimate from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_WEEK_NUMBER (0x00000004) - Mask to delete week number from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_RTC_TIME (0x00000008) - Mask to delete RTC time from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_TIME_TRANSFER (0x00000010) - Mask to delete time transfer from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GPSTIME_EST (0x00000020) - Mask to delete GPS time estimate from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GLOTIME_EST (0x00000040) - Mask to delete GLONASS time estimate from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GLODAY_NUMBER (0x00000080) - Mask to delete GLONASS day number from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GLO4YEAR_NUMBER (0x00000100) - Mask to delete GLONASS four year number from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GLO_RF_GRP_DELAY (0x00000200) - Mask to delete GLONASS RF GRP delay from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_DISABLE_TT (0x00000400) - Mask to delete disable TT from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GG_LEAPSEC (0x00000800) - Mask to delete a BDS time estimate from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GG_GGTB (0x00001000) - Mask to delete a BDS time estimate from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_BDSTIME_EST (0x00002000) - Mask to delete a BDS time estimate from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GB_GBTB (0x00004000) - Mask to delete Glonass-to-BDS time bias-related information from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_BG_BGTB (0x00008000) - Mask to delete BDS-to-GLONASS time bias-related information from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_BDSWEEK_NUMBER (0x00010000) - Mask to delete the BDS week number from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_BDS_RF_GRP_DELAY (0x00020000) - Mask to delete the BDS RF GRP delay from the clock information</li> </ul> </li> </ul>
-------------	--

## 8.103.2 Field Documentation

8.103.2.1 ULONG CkInfo::mask

## 8.104 CNAPResp Struct Reference

### Data Fields

- [BYTE ActiveStatus](#)
- [BYTE ProvisionStatus](#)

### 8.104.1 Detailed Description

This structure contains information about the Calling Name Presentation (CNAP) supplementary service responses.

#### Parameters

<i>ActiveStatus</i>	<ul style="list-style-type: none"><li>• Active status.</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - ACTIVE_STATUS_INACTIVE - Inactive</li><li>– 0x01 - ACTIVE_STATUS_ACTIVE - Active</li><li>– 0xFF - Not Available</li></ul></li></ul>
<i>ProvisionStatus</i>	<ul style="list-style-type: none"><li>• Provisioned status.</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - PROVISION_STATUS_NOT_PROVISIONED - Not provisioned</li><li>– 0x01 - PROVISION_STATUS_PROVISIONED - Provisioned</li><li>– 0xFF - Not Available</li></ul></li></ul>

### 8.104.2 Field Documentation

8.104.2.1 BYTE CNAPResp::ActiveStatus

8.104.2.2 BYTE CNAPResp::ProvisionStatus

## 8.105 COLPResp Struct Reference

### Data Fields

- [BYTE ActiveStatus](#)
- [BYTE ProvisionStatus](#)

### 8.105.1 Detailed Description

This structure contains information about the Connected Line Identification Presentation (COLP) supplementary service responses.

## Parameters

<i>ActiveStatus</i>	<ul style="list-style-type: none"> <li>• Active status.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - ACTIVE_STATUS_INACTIVE - Inactive</li> <li>– 0x01 - ACTIVE_STATUS_ACTIVE - Active</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>ProvisionStatus</i>	<ul style="list-style-type: none"> <li>• Provisioned status.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - PROVISION_STATUS_NOT_PROVISIONED - Not provisioned</li> <li>– 0x01 - PROVISION_STATUS_PROVISIONED - Provisioned</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

## 8.105.2 Field Documentation

## 8.105.2.1 BYTE COLPResp::ActiveStatus

## 8.105.2.2 BYTE COLPResp::ProvisionStatus

## 8.106 COLRResp Struct Reference

## Data Fields

- [BYTE ActiveStatus](#)
- [BYTE ProvisionStatus](#)

## 8.106.1 Detailed Description

This structure contains information about the Connected Line Identification Restriction (COLR) supplementary service responses.

## Parameters

<i>ActiveStatus</i>	<ul style="list-style-type: none"> <li>• Active status.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - ACTIVE_STATUS_INACTIVE - Inactive</li> <li>– 0x01 - ACTIVE_STATUS_ACTIVE - Active</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
---------------------	---



<i>ProvisionStatus</i>	<ul style="list-style-type: none"><li>• Provisioned status.</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - PROVISION_STATUS_NOT_PROVISIONED - Not provisioned</li><li>– 0x01 - PROVISION_STATUS_PROVISIONED - Provisioned</li><li>– 0xFF - Not Available</li></ul></li></ul>
------------------------	---

## 8.106.2 Field Documentation

### 8.106.2.1 BYTE COLRResp::ActiveStatus

### 8.106.2.2 BYTE COLRResp::ProvisionStatus

## 8.107 CommInfo Struct Reference

### Data Fields

- [BYTE temperature](#)
- [BYTE modemMode](#)
- [BYTE systemMode](#)
- [BYTE imsRegState](#)
- [BYTE psState](#)

### 8.107.1 Detailed Description

Structure for storing the common information for the device.

## Parameters

<i>temperature</i>	<ul style="list-style-type: none"> <li>• Temperature. <ul style="list-style-type: none"> <li>– 8-bit signed integer</li> <li>– 0xFF - Not Available.</li> </ul> </li> </ul>
<i>modemMode</i>	<ul style="list-style-type: none"> <li>• Modem Operating Mode. <ul style="list-style-type: none"> <li>– 0x00 - POWERING OFF</li> <li>– 0x01 - FACTORY TEST</li> <li>– 0x02 - OFFLINE</li> <li>– 0x03 - OFFLINE_AMPS</li> <li>– 0x04 - OFFLINE_CDMA</li> <li>– 0x05 - ONLINE</li> <li>– 0x06 - LOW POWER MODE</li> <li>– 0x07 - RESETTING</li> <li>– 0x08 - NETWORK TEST</li> <li>– 0x09 - OFFLINE REQUEST</li> <li>– 0x0A - PSEUDO ONLINE</li> <li>– 0x0B - RESETTING MODEM</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>systemMode</i>	<ul style="list-style-type: none"> <li>• System Acquisition Mode. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - AMPS</li> <li>– 0x02 - CDMA</li> <li>– 0x03 - GSM</li> <li>– 0x04 - HDR</li> <li>– 0x05 - WCDMA</li> <li>– 0x06 - GPS</li> <li>– 0x08 - WLAN</li> <li>– 0x09 - LTE</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>

<i>imsRegState</i>	<ul style="list-style-type: none"><li>• IMS Registration State.<ul style="list-style-type: none"><li>– 0x00 - NO SRV</li><li>– 0x01 - IN PROG</li><li>– 0x02 - FAILED</li><li>– 0x03 - LIMITED</li><li>– 0x04 - FULL SRV</li><li>– 0xFF - Unknown</li></ul></li></ul>
<i>psState</i>	<ul style="list-style-type: none"><li>• PS Attach State.<ul style="list-style-type: none"><li>– 0x00 - Attached</li><li>– 0x01 - Detached</li><li>– 0xFF - Unknown</li></ul></li></ul>

## 8.107.2 Field Documentation

8.107.2.1 **BYTE** CommInfo::imsRegState

8.107.2.2 **BYTE** CommInfo::modemMode

8.107.2.3 **BYTE** CommInfo::psState

8.107.2.4 **BYTE** CommInfo::systemMode

8.107.2.5 **BYTE** CommInfo::temperature

## 8.108 ConnectionStatus Struct Reference

### Data Fields

- [BYTE MDMConnStatus](#)
- [ULONGLONG MDMDuration](#)

### 8.108.1 Detailed Description

This structure contains modem connection status

## Parameters

<i>MDMConn-Status</i>	<ul style="list-style-type: none"> <li>Current link status <ul style="list-style-type: none"> <li>0x01 - DISCONNECTED</li> <li>0x02 - CONNECTED</li> </ul> </li> </ul>
<i>MDMCall-Duration</i>	<ul style="list-style-type: none"> <li>Call duration in milliseconds.</li> <li>If the modem connection status is connected, this represent the duration of the current DUN call.</li> <li>If the modem connection status is disconnected, this represents the duration of the last DUN call since the device was powered up (zero, if no call has been made or if the last call was not DUN).</li> </ul>

## 8.108.2 Field Documentation

## 8.108.2.1 ULONGLONG ConnectionStatus::MDMCallDuration

## 8.108.2.2 BYTE ConnectionStatus::MDMConnStatus

## 8.109 connectionStatus Struct Reference

## Data Fields

- uint8\_t [MDMConnStatus](#)
- uint64\_t [MDMCallDuration](#)

## 8.109.1 Detailed Description

## Parameters

<i>MDMConn-Status</i>	Current link status 1-Disconnected 2-Connected
<i>MDMCall-Duration</i>	Call duration in milliseconds

## 8.109.2 Field Documentation

## 8.109.2.1 uint64\_t connectionStatus::MDMCallDuration

## 8.109.2.2 uint8\_t connectionStatus::MDMConnStatus

## 8.110 connectNumInfo Struct Reference

## Data Fields

- BYTE [numPresInd](#)
- BYTE [screeningInd](#)

- [BYTE numType](#)
- [BYTE numPlan](#)
- [BYTE callerIDLen](#)
- [BYTE callerID \[81\]](#)

### 8.110.1 Detailed Description

This structure contains information about the numbers connected to a device. It contains information such as number type, eg International or Local.

## Parameters

<i>numPresInd</i>	<ul style="list-style-type: none"> <li>• Presentation indicator <ul style="list-style-type: none"> <li>– 0x00 - PRESENTATION_ALLOWED - Allowed presentation</li> <li>– 0x01 - PRESENTATION_RESTRICTED - Restricted presentation</li> <li>– 0x02 - PRESENTATION_NUM_UNAVAILABLE - Unavailable presentation</li> <li>– 0x04 - PRESENTATION_PAYPHONE - Payphone presentation (GSM/UMTS specific)</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>screeningInd</i>	<ul style="list-style-type: none"> <li>• Screening indicator. <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_SI_USER_PROVIDED_NOT_SCREENED - Provided user is not screened</li> <li>– 0x01 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_PASSED - Provided user passed verification</li> <li>– 0x02 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_FAILED - Provided user failed verification</li> <li>– 0x03 - QMI_VOICE_SI_NETWORK_PROVIDED - Provided network</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>numType</i>	<ul style="list-style-type: none"> <li>• Number type. <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_TYPE_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_TYPE_INTERNATIONAL - International</li> <li>– 0x02 - QMI_VOICE_NUM_TYPE_NATIONAL - National</li> <li>– 0x03 - QMI_VOICE_NUM_TYPE_NETWORK_SPECIFIC - Network-specific</li> <li>– 0x04 - QMI_VOICE_NUM_TYPE_SUBSCRIBER - Subscriber</li> <li>– 0x05 - QMI_VOICE_NUM_TYPE_RESERVED - Reserved</li> <li>– 0x06 - QMI_VOICE_NUM_TYPE_ABBREVIATED - Abbreviated</li> <li>– 0x07 - QMI_VOICE_NUM_TYPE_RESERVED_EXTENSION - Reserved extension</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>numPlan</i>	<ul style="list-style-type: none"> <li>• Number plan. <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_PLAN_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_PLAN_ISDN - ISDN</li> <li>– 0x03 - QMI_VOICE_NUM_PLAN_DATA - Data</li> <li>– 0x04 - QMI_VOICE_NUM_PLAN_TELEX - Telex</li> <li>– 0x08 - QMI_VOICE_NUM_PLAN_NATIONAL - National</li> <li>– 0x09 - QMI_VOICE_NUM_PLAN_PRIVATE - Private</li> <li>– 0x0B - QMI_VOICE_NUM_PLAN_RESERVED_CTS - Reserved cordless telephony system</li> <li>– 0x0F - QMI_VOICE_NUM_PLAN_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> <p>Generated on Tue Jul 12 2016 10:59:49 for LinuxQMI SDK by Doxygen</p>

<i>callerIDLen</i>	<ul style="list-style-type: none"> <li>Provides the length of caller ID which follow.</li> <li>If zero(0) then no further information exists.</li> </ul>
<i>callerID[MAX_C-ALL_NO_LEN]</i>	<ul style="list-style-type: none"> <li>callerID of numLen length, NULL terminated.</li> </ul>

## 8.110.2 Field Documentation

8.110.2.1 **BYTE** connectNumInfo::callerID[81]

8.110.2.2 **BYTE** connectNumInfo::callerIDLen

8.110.2.3 **BYTE** connectNumInfo::numPlan

8.110.2.4 **BYTE** connectNumInfo::numPresInd

8.110.2.5 **BYTE** connectNumInfo::numType

8.110.2.6 **BYTE** connectNumInfo::screeningInd

## 8.111 CrashInfo Struct Reference

### Data Fields

- [WORD numCrashes](#)
- [ULONG crashId](#)
- [ULONG crashData](#)
- [WORD crashStrLen](#)
- [CHAR \\* pCrashString](#)
- [WORD gcDumpStrLen](#)
- [CHAR \\* pGCDumpString](#)

### 8.111.1 Detailed Description

This structure is used to store Crash Information

#### Parameters

<i>numCrashes[OUT]</i>	<ul style="list-style-type: none"> <li>Number of instances of the remaining fields</li> </ul>
<i>crashId[OUT]</i>	<ul style="list-style-type: none"> <li>Random crash id assigned at crash</li> </ul>
<i>crashData[OUT]</i>	<ul style="list-style-type: none"> <li>Crash Data</li> </ul>

<i>crashStrLen</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>Length of the pCrashString field returned by API</li> </ul>
<i>pCrashString</i> [OUT]	<ul style="list-style-type: none"> <li>Pointer to store crash string</li> </ul>
<i>gcDumpStrLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Length of the pGCDumpString field returned by API</li> </ul>
<i>pGCDumpString</i> [OUT]	<ul style="list-style-type: none"> <li>gcdump string for the crash</li> </ul>

### 8.111.2 Field Documentation

8.111.2.1 **ULONG** CrashInfo::crashData

8.111.2.2 **ULONG** CrashInfo::crashId

8.111.2.3 **WORD** CrashInfo::crashStrLen

8.111.2.4 **WORD** CrashInfo::gcDumpStrLen

8.111.2.5 **WORD** CrashInfo::numCrashes

8.111.2.6 **CHAR\*** CrashInfo::pCrashString

8.111.2.7 **CHAR\*** CrashInfo::pGCDumpString

## 8.112 CrashInfoParams Struct Reference

### Data Fields

- BYTE** \* [pDevCrashStatus](#)
- CrashInfo** \* [pCrashInfo](#)

### 8.112.1 Detailed Description

This structure is used to store Crash Information

#### Parameters

<i>pDevCrashStatus</i> [OUT]	<ul style="list-style-type: none"> <li>Device Crash Status</li> <li>0 - no crash</li> <li>1 - crash has occurred</li> </ul>
------------------------------	---



<i>pCrashInfo</i> [OUT]	<ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">CrashInfo</a> (Optional parameter)</li> <li>• See <a href="#">CrashInfo</a> for more information</li> </ul>
-------------------------	---

### 8.112.2 Field Documentation

8.112.2.1 [CrashInfo](#)\* [CrashInfoParams::pCrashInfo](#)

8.112.2.2 [BYTE](#)\* [CrashInfoParams::pDevCrashStatus](#)

## 8.113 CreateProfileIn Struct Reference

### Data Fields

- [BYTE](#) \* [pProfileID](#)
- [BYTE](#) \* [pProfileType](#)
- [QmiProfileInfo](#) [curProfile](#)

### 8.113.1 Detailed Description

This structure contains the input parameters for [SLQSCreateProfile](#)

#### Parameters

<i>ProfileID</i>	<ul style="list-style-type: none"> <li>• 1 to 16 for 3GPP profile (EM/MC73xx or earlier)</li> <li>• 1 to 24 for 3GPP profile (EM/MC74xx onwards)</li> <li>• 101 to 106 for 3GPP2 profile</li> </ul>
<i>ProfileType</i>	<ul style="list-style-type: none"> <li>• Identifies the technology type of the profile <ul style="list-style-type: none"> <li>– 0x00 - 3GPP</li> <li>– 0x01 - 3GPP2</li> <li>– NULL is not allowed</li> </ul> </li> </ul>
<i>curProfile</i>	<ul style="list-style-type: none"> <li>• union of <a href="#">Profile3GPP</a> and <a href="#">Profile3GPP2</a></li> </ul>

#### Note

- If profileID is NULL, 3GPP profile will be created and index will be assigned based on availability in device.
- If profileID is not NULL depending on pProfileType 3GPP/3GPP2 relevant profile will be created

### 8.113.2 Field Documentation

8.113.2.1 [QmiProfileInfo](#) [CreateProfileIn::curProfile](#)

8.113.2.2 **BYTE\*** CreateProfileIn::pProfileID

8.113.2.3 **BYTE\*** CreateProfileIn::pProfileType

## 8.114 CreateProfileOut Struct Reference

### Data Fields

- [BYTE \\*](#) pProfileType
- [BYTE \\*](#) pProfileIndex
- [USHORT \\*](#) pExtErrorCode

### 8.114.1 Detailed Description

structure contains out parameter Information

#### Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>• Identifies the type of profile 0x00 = 3GPP 0x01 = 3GPP2</li> </ul>
<i>profileIndex</i>	<ul style="list-style-type: none"> <li>• Index identifying the profile that was created</li> </ul>
<i>pExtErrorCode</i>	<ul style="list-style-type: none"> <li>• The extended error code received from DS Profile subsystem</li> </ul>

### 8.114.2 Field Documentation

8.114.2.1 **USHORT\*** CreateProfileOut::pExtErrorCode

8.114.2.2 **BYTE\*** CreateProfileOut::pProfileIndex

8.114.2.3 **BYTE\*** CreateProfileOut::pProfileType

## 8.115 CSGID Struct Reference

### Data Fields

- [WORD](#) mcc
- [WORD](#) mnc
- [BYTE](#) mncPcsDigits
- [ULONG](#) id
- [BYTE](#) rat

### 8.115.1 Detailed Description

Contain the [CSGID](#).

## Parameters

<i>mcc</i>	<ul style="list-style-type: none"> <li>MCC value. Range 0 to 999</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>MNC value. Range 0 to 999</li> </ul>
<i>mncPcsDigits</i>	<ul style="list-style-type: none"> <li>TRUE - MNC is a three-digit value; e.g., a reported value of 90 corresponds to an MNC value of 090</li> <li>FALSE - MNC is a two-digit value; e.g., a reported value of 90 corresponds to an MNC value of 90</li> </ul>
<i>id</i>	<ul style="list-style-type: none"> <li>Closed subscriber group identifier.</li> </ul>
<i>rat</i>	<ul style="list-style-type: none"> <li>Radio interface technology of the CSG network. Values: <ul style="list-style-type: none"> <li>0x04 - RADIO_IF_GSM - GSM</li> <li>0x05 - RADIO_IF_UMTS - UMTS</li> <li>0x08 - RADIO_IF_LTE - LTE</li> <li>0x09 - RADIO_IF_TDSCDMA - TDS</li> </ul> </li> </ul>

## 8.115.2 Field Documentation

8.115.2.1 ULONG CSGID::id

8.115.2.2 WORD CSGID::mcc

8.115.2.3 WORD CSGID::mnc

8.115.2.4 BYTE CSGID::mncPcsDigits

8.115.2.5 BYTE CSGID::rat

## 8.116 CUGInfo Struct Reference

## Data Fields

- [WORD CUGIndex](#)
- [BYTE SuppPrefCUG](#)
- [BYTE SuppOA](#)

## 8.116.1 Detailed Description

This structure contains Closed User Group Information

## Parameters

<i>CUGIndex</i>	<ul style="list-style-type: none"> <li>• Range 0x00... 0x7FFF</li> </ul>
<i>SuppPrefCUG</i>	<ul style="list-style-type: none"> <li>• Suppress preferential CUG <ul style="list-style-type: none"> <li>– 0x00 - FALSE</li> <li>– 0x01 - TRUE</li> </ul> </li> </ul>
<i>SuppOA</i>	<ul style="list-style-type: none"> <li>• Suppress OA subscription option <ul style="list-style-type: none"> <li>– 0x00 - FALSE</li> <li>– 0x01 - TRUE</li> </ul> </li> </ul>

## 8.116.2 Field Documentation

## 8.116.2.1 WORD CUGInfo::CUGIndex

## 8.116.2.2 BYTE CUGInfo::SuppOA

## 8.116.2.3 BYTE CUGInfo::SuppPrefCUG

## 8.117 curAMRConfig Struct Reference

## Data Fields

- [BYTE gsmAmrStat](#)
- [BYTE wcdmaAmrStat](#)

## 8.117.1 Detailed Description

This structure contains the Current Adaptive Multi Rate Configuration Information.

## Parameters

<i>gsmAmrStat</i>	<ul style="list-style-type: none"> <li>• GSM AMR Status <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
-------------------	---

<i>wcdmaAmrStat</i>	<ul style="list-style-type: none"> <li>• WCDMA AMR Status</li> <li>• One or a combination of the following bitmask values: <ul style="list-style-type: none"> <li>– Bit 0 - AMR codec advertised is not supported</li> <li>– Bit 1 - Controls WCDMA AMR wideband</li> <li>– Bit 2 - Controls GSM half rate AMR</li> <li>– Bit 3 - Controls GSM AMR wideband</li> <li>– Bit 4 - Controls GSM AMR narrowband</li> </ul> </li> <li>• 0xFF, if not available</li> </ul>
---------------------	---

## 8.117.2 Field Documentation

8.117.2.1 **BYTE** curAMRConfig::gsmAmrStat

8.117.2.2 **BYTE** curAMRConfig::wcdmaAmrStat

## 8.118 CurrDataSysStat Struct Reference

### Data Fields

- [BYTE \\* pPrefNetwork](#)
- [BYTE \\* pNetworkInfoLen](#)
- [CurrNetworkInfo \\* pCurrNetworkInfo](#)

### 8.118.1 Detailed Description

Data System Status

Parameters

<i>pPrefNetwork</i>	[OUT] <ul style="list-style-type: none"> <li>• Preferred Network</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - 3GPP</li> <li>– 1 - 3GPP2</li> </ul> </li> </ul>
---------------------	---

<i>pNetworkInfoLen</i>	[IN/OUT] <ul style="list-style-type: none"> <li>• As input parameter size assigned to next parameter i.e. network information</li> <li>• As output the actual number of network information elements returned by the device</li> </ul>
<i>pCurrNetwork-Info</i>	[OUT] <ul style="list-style-type: none"> <li>• Network information</li> <li>• See <a href="#">CurrNetworkInfo</a> for more details</li> </ul>

### 8.118.2 Field Documentation

8.118.2.1 **CurrNetworkInfo\*** CurrDataSysStat::pCurrNetworkInfo

8.118.2.2 **BYTE\*** CurrDataSysStat::pNetworkInfoLen

8.118.2.3 **BYTE\*** CurrDataSysStat::pPrefNetwork

## 8.119 currentCatEvent Union Reference

### Data Fields

- struct [CatEventIDDataTlv](#) CatEvIDData
- struct [CatAlPhalIdentifierTlv](#) CatAlPhaldtfr
- struct [CatEventListTlv](#) CatEventLst
- struct [CatRefreshTlv](#) CatRefresh
- struct [CatEndProactiveSessionTlv](#) CatEndPS

### 8.119.1 Detailed Description

Union used to represent the current CAT Event Data. Choose the structure based on the EventID received.

- Use [CatEventIDDataTlv](#) if the Event ID is any of the below.
  - 16
  - 17
  - 18
  - 19
  - 20
  - 23
  - 24
- Use [CatAlPhalIdentifierTlv](#) if the Event ID is 21
- Use [CatEventListTlv](#) if the Event ID is 22
- Use [CatRefreshTlv](#) if the Event ID is 25
- Use [CatEndProactiveSessionTlv](#) if the Event ID is 26

### 8.119.2 Field Documentation

8.119.2.1 struct CatAlPhalIdentifierTlv currentCatEvent::CatAlphaldtfr

8.119.2.2 struct CatEndProactiveSessionTlv currentCatEvent::CatEndPS

8.119.2.3 struct CatEventListTlv currentCatEvent::CatEventLst

8.119.2.4 struct CatEventIDDDataTlv currentCatEvent::CatEvIDDData

8.119.2.5 struct CatRefreshTlv currentCatEvent::CatRefresh

## 8.120 CurrentImgList Struct Reference

### Data Fields

- [BYTE numEntries](#)
- [CurrImgInfo](#) \* [pCurrImgInfo](#)
- [CHAR priver](#) [16]
- [CHAR pkgver](#) [16]
- [CHAR fwvers](#) [16]
- [CHAR carrier](#) [16]

### 8.120.1 Detailed Description

This structure is used to store image list

#### Parameters

<i>numEntries</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>• Number of entries in the image list to follow</li> <li>• The size of the list <a href="#">pCurrImgInfo</a> must be specified when calling the API</li> </ul>
<i>pCurrImgInfo</i> [OUT]	<ul style="list-style-type: none"> <li>• Currently Active Image List</li> </ul>
<i>priver</i> [OUT]	<ul style="list-style-type: none"> <li>• PRI version of the currently running firmware</li> </ul>
<i>pkgver</i> [OUT]	<ul style="list-style-type: none"> <li>• Package version of the currently running firmware</li> </ul>
<i>fwvers</i> [OUT]	<ul style="list-style-type: none"> <li>• firmware version of the currently running firmware</li> </ul>
<i>carrier</i> [OUT]	<ul style="list-style-type: none"> <li>• Carrier string of the currently running firmware</li> </ul>

### 8.120.2 Field Documentation

8.120.2.1 [CHAR](#) [CurrentImgList::carrier](#)[16]

8.120.2.2 CHAR CurrentImgList::fwvers[16]

8.120.2.3 BYTE CurrentImgList::numEntries

8.120.2.4 CurrImageInfo\* CurrentImgList::pCurrImgInfo

8.120.2.5 CHAR CurrentImgList::pkgver[16]

8.120.2.6 CHAR CurrentImgList::priver[16]

## 8.121 currentPLMN Struct Reference

### Data Fields

- [WORD MCC](#)
- [WORD MNC](#)
- [BYTE netDescrLength](#)
- [BYTE netDescr](#) [255]

### 8.121.1 Detailed Description

This structure contains the current PLMN parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• mobile country code               <ul style="list-style-type: none"> <li>– A 16 bit representation of MCC</li> <li>– Range 0 to 999</li> </ul> </li> </ul>
<i>MNC</i>	<ul style="list-style-type: none"> <li>• mobile network code               <ul style="list-style-type: none"> <li>– A 16 bit representation of MNC</li> <li>– Range 0 to 999</li> </ul> </li> </ul>
<i>netDescrLength</i>	<ul style="list-style-type: none"> <li>• Length of Network description field</li> <li>• Defaults to zero</li> </ul>
<i>netDescr</i>	<ul style="list-style-type: none"> <li>• Network Description               <ul style="list-style-type: none"> <li>– optional string containing network name or description</li> </ul> </li> </ul>

### 8.121.2 Field Documentation



8.121.2.1 WORD currentPLMN::MCC

8.121.2.2 WORD currentPLMN::MNC

8.121.2.3 BYTE currentPLMN::netDescr[255]

8.121.2.4 BYTE currentPLMN::netDescrLength

## 8.122 CurrImageInfo Struct Reference

### Data Fields

- [BYTE imageType](#)
- [BYTE uniqueID \[16\]](#)
- [BYTE buildIDLen](#)
- [BYTE buildID \[255\]](#)

### 8.122.1 Detailed Description

This structure is used to store image information

#### Parameters

<i>imageType[OUT]</i>	<ul style="list-style-type: none"> <li>• Image Type</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - FW</li> <li>– 1 - configuration</li> </ul> </li> </ul>
<i>uniqueID[OUT]</i>	<ul style="list-style-type: none"> <li>• Image Unique Identifier ( ASCII characters )</li> </ul>
<i>buildIDLen[OUT]</i>	<ul style="list-style-type: none"> <li>• Length of build ID string to follow</li> <li>• If set to zero, build ID string will be blank</li> </ul>
<i>buildID[OUT]</i>	<ul style="list-style-type: none"> <li>• String containing image information( ASCII characters )</li> <li>• Maximum length of this string is 255 chars</li> </ul>

### 8.122.2 Field Documentation

8.122.2.1 BYTE CurrImageInfo::buildID[255]

8.122.2.2 BYTE CurrImageInfo::buildIDLen

8.122.2.3 BYTE CurrImageInfo::imageType

8.122.2.4 BYTE CurrImageInfo::uniqueID[16]

## 8.123 CurrNetworkInfo Struct Reference

### Data Fields

- [BYTE NetworkType](#)
- [ULONG RATMask](#)
- [ULONG SOMask](#)

### 8.123.1 Detailed Description

Network information structure

## Parameters

<i>NetworkType</i>	<ul style="list-style-type: none"> <li>Values: <ul style="list-style-type: none"> <li>0 - 3GPP</li> <li>1 - 3GPP2</li> </ul> </li> </ul>
<i>RATMask</i>	<ul style="list-style-type: none"> <li>Radio Access Technology (RAT) mask to indicate the type of technology.</li> <li>Values: <ul style="list-style-type: none"> <li>0 - Don't Care</li> <li>0x8000 - NULL Bearer</li> </ul> </li> <li>CDMA RAT mask values: <ul style="list-style-type: none"> <li>0x01 - CDMA_1x</li> <li>0x02 - EVDO_REV0</li> <li>0x04 - EVDO_REVA</li> <li>0x08 - EVDO_REVB</li> <li>0x10 - EHRPD</li> <li>0x20 - FMC</li> </ul> </li> <li>UMTS RAT mask values: <ul style="list-style-type: none"> <li>0x01 - WCDMA</li> <li>0x02 - GPRS</li> <li>0x04 - HSDPA</li> <li>0x08 - HSUPA</li> <li>0x10 - EDGE</li> <li>0x20 - LTE</li> <li>0x40 - HSDPA+</li> <li>0x80 - DC_HSDPA+</li> <li>0x100 - 64_QAM</li> <li>0x200 - TDSCDMA</li> </ul> </li> </ul>
<i>SOMask</i>	<ul style="list-style-type: none"> <li>Service Option (SO) mask to indicate the service option or type of application.</li> <li>Values: <ul style="list-style-type: none"> <li>0 - Don't Care</li> </ul> </li> <li>CDMA 1x SO mask values: <ul style="list-style-type: none"> <li>0x01 - CDMA_1X_IS95</li> <li>0x02 - CDMA_1X_IS2000</li> <li>0x04 - CDMA_1X_IS2000_REL_A</li> </ul> </li> <li>CDMA EV-DO Rev 0 SO mask values: <ul style="list-style-type: none"> <li>0x01 - DPA</li> </ul> </li> <li>CDMA EV-DO Rev A SO mask values: <ul style="list-style-type: none"> <li>0x01 - DPA</li> <li>0x02 - MFPA</li> <li>0x04 - EMPA</li> <li>0x08 - EMPA_EHRPD</li> </ul> </li> </ul>

### 8.123.2 Field Documentation

8.123.2.1 **BYTE** CurrNetworkInfo::NetworkType

8.123.2.2 **ULONG** CurrNetworkInfo::RATMask

8.123.2.3 **ULONG** CurrNetworkInfo::SOMask

## 8.124 currNetworkInfo Struct Reference

### Data Fields

- uint8\_t [NetworkType](#)
- uint32\_t [RATMask](#)
- uint32\_t [SOMask](#)

### 8.124.1 Detailed Description

#### Parameters

<i>NetworkType</i>	network type 0-3GPP 1-3GPP2
<i>RATMask</i>	Radio access technology mask to indicate technology.
<i>SOMask</i>	Service Option mask to indicate the service option.

### 8.124.2 Field Documentation

8.124.2.1 **uint8\_t** currNetworkInfo::NetworkType

8.124.2.2 **uint32\_t** currNetworkInfo::RATMask

8.124.2.3 **uint32\_t** currNetworkInfo::SOMask

## 8.125 custFeaturesInfo Struct Reference

### Data Fields

- **ULONG** GpsEnable
- **BYTE** \* pDisableIMSI
- **WORD** \* pIPFamSupport
- **BYTE** \* pRMAutoConnect
- **BYTE** \* pGPSSel
- **BYTE** \* pSMSSupport
- **BYTE** \* plsVoiceEnabled
- **BYTE** \* pDHCPRelayEnabled
- **BYTE** \* pGPSLPM

### 8.125.1 Detailed Description

This structure contains current settings of custom features

## Parameters

<i>GpsEnable</i> [OUT]	<ul style="list-style-type: none"> <li>describes if GPS is enabled or disabled</li> <li>values: <ul style="list-style-type: none"> <li>0x00 - GPS is disabled</li> <li>0x01 - GPS is enabled</li> </ul> </li> <li>function <a href="#">SLQSGetCustFeatures()</a> returns a default value FFFFFFFF if no value is returned by the modem</li> </ul>
<i>pDisableIMSI</i> [OUT]	<ul style="list-style-type: none"> <li>optional 1 byte parameter</li> <li>describes if IMSI display is enabled or disabled</li> <li>values: <ul style="list-style-type: none"> <li>0x00 - Allow display of IMSI</li> <li>0x01 - Do not display IMSI</li> </ul> </li> <li>function <a href="#">SLQSGetCustFeatures()</a> returns a default value FF if no value is returned by the modem</li> </ul>
<i>pIPFamSupport</i> [OUT]	<ul style="list-style-type: none"> <li>optional 2 byte BitMask</li> <li>bitmask representing the IP families supported</li> <li>values: <ul style="list-style-type: none"> <li>0x01 - IPv4</li> <li>0x02 - IPv6</li> <li>0x04 - IPv4v6</li> </ul> </li> <li>function <a href="#">SLQSGetCustFeatures()</a> returns a default value FFFF if no value is returned by the modem</li> </ul>

<i>pRMAuto-Connect[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• QMI Mode RM Net Auto Connect Support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Not Supported</li> <li>– 0x01 - Supported</li> </ul> </li> <li>• function <a href="#">SLQSGetCustFeatures()</a> returns a default value FF if no value is returned by the modem</li> </ul>
<i>pGPSSel[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• GPS Antenna Select</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Dedicated GPS <a href="#">Port</a></li> <li>– 0x01 - GPS Rx over AUX <a href="#">Port</a></li> <li>– 0x02 - GPS Rx over dedicated GPS port with no bias voltage applied</li> </ul> </li> <li>• function <a href="#">SLQSGetCustFeatures()</a> returns a default value FF if no value is returned by the modem</li> </ul>
<i>pSMSSupport[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• SMS support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Not supported</li> <li>– 0x01 - supported</li> </ul> </li> <li>• Used to determine whether or not to hide SMS from user</li> <li>• function <a href="#">SLQSGetCustFeatures()</a> returns a default value FF if no value is returned by the modem. In this case assume, SMS is supported.</li> </ul>

<i>pIsVoice-Enabled[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• Voice support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Enable voice on both AT and QMI interface (default)</li> <li>– 0x01 - Reserved</li> <li>– 0x02 - Disable voice on both AT and QMI interface</li> </ul> </li> </ul>
<i>pDHCPRelay-Enabled[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• DHCP Relay support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Disable DHCP relay</li> <li>– 0x01 - Enable DHCP relay</li> </ul> </li> </ul>
<i>pGPSLPM[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• GPSLPM support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Enable GPS in Low Power Mode</li> <li>– 0x01 - Disable GPS in Low Power Mode</li> </ul> </li> </ul>

## 8.125.2 Field Documentation

8.125.2.1 **ULONG** custFeaturesInfo::GpsEnable

8.125.2.2 **BYTE\*** custFeaturesInfo::pDHCPRelayEnabled

8.125.2.3 **BYTE\*** custFeaturesInfo::pDisableIMSI

8.125.2.4 **BYTE\*** custFeaturesInfo::pGPSLPM

8.125.2.5 **BYTE\*** custFeaturesInfo::pGPSSel

8.125.2.6 **WORD\*** custFeaturesInfo::pIPFamSupport

8.125.2.7 **BYTE\*** custFeaturesInfo::pIsVoiceEnabled

8.125.2.8 **BYTE\*** custFeaturesInfo::pRMAutoConnect

8.125.2.9 **BYTE\*** custFeaturesInfo::pSMSSupport

## 8.126 custFeaturesSetting Struct Reference

## Data Fields

- `BYTE * pGPSSel`
- `ULONG * pGPSEnable`
- `BYTE * pIsVoiceEnabled`
- `BYTE * pDHCPRelayEnabled`
- `BYTE * pGPSLPM`

### 8.126.1 Detailed Description

This structure contains settings to be used for custom features

#### Parameters

<i>pGPSSel</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• GPS Antenna Select</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Dedicated GPS <a href="#">Port</a></li> <li>– 0x01 - GPS Rx over AUX <a href="#">Port</a></li> <li>– 0x02 - GPS Rx over dedicated GPS port with no bias voltage applied</li> </ul> </li> </ul>
<i>pGPSEnable</i>	<ul style="list-style-type: none"> <li>• optional 4 byte parameter</li> <li>• GPS Enable/Disable</li> <li>• values: The value of 7 least significant bits: <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - MT &amp; MO enabled</li> <li>– 2 - MO enabled</li> <li>– 3 - MT enabled</li> <li>– 4 - MT &amp; MO enabled if GPS_DISABLE pin is not asserted</li> <li>– 5 - MO GPS enabled if GPS_DISABLE pin is not asserted</li> <li>– 6 - MT GPS enabled if GPS_DISABLE pin is not asserted</li> </ul> </li> </ul>



## Note

Only MC7750 3.5.x firmware supports above 0x04, 0x05 and 0x06 settings. To disable GLONASS, set the most significant bit - 0x80. This setting is only applicable if GPS is not Disabled.

## Parameters

<i>plsVoiceEnabled</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• voice enabled/disabled</li> <li>• values: <ul style="list-style-type: none"> <li>– 0 - Enable voice on both AT and QMI interface (default)</li> <li>– 1 - Reserved</li> <li>– 2 - Disable voice on both AT and QMI interface</li> </ul> </li> </ul>
<i>pDHCPRelay-Enabled</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• DHCPRELAYENABLE support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0 - Disable DHCP relay</li> <li>– 1 - Enable DHCP relay</li> </ul> </li> </ul>
<i>pGPSLPM</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• GPSLPM support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0 - Enable GPS in Low Power Mode</li> <li>– 1 - Disable GPS in Low Power Mode</li> </ul> </li> </ul>

## 8.126.2 Field Documentation

8.126.2.1 **BYTE\*** custFeaturesSetting::pDHCPRelayEnabled

8.126.2.2 **ULONG\*** custFeaturesSetting::pGPSEnable

8.126.2.3 **BYTE\*** custFeaturesSetting::pGPSLPM

8.126.2.4 **BYTE\*** custFeaturesSetting::pGPSSel

8.126.2.5 **BYTE\*** custFeaturesSetting::plsVoiceEnabled

## 8.127 custSettingInfo Struct Reference

## Data Fields

- [WORD id\\_length](#)

- [CHAR cust\\_id](#) [64+1]
- [WORD value\\_length](#)
- [BYTE cust\\_value](#) [8+1]
- [WORD cust\\_attr](#)

### 8.127.1 Detailed Description

This structure contains information about Customization Setting. This TLV is only applicable for 9x30 modules so far

#### Parameters

<i>id_length</i>	<ul style="list-style-type: none"> <li>• length of cust_id field</li> </ul>
<i>cust_id</i>	<ul style="list-style-type: none"> <li>• Customization ID (Maximum 64 bytes)</li> </ul>
<i>value_length</i>	<ul style="list-style-type: none"> <li>• length of cust_value field</li> </ul>
<i>cust_value</i>	<ul style="list-style-type: none"> <li>• Customization Setting Value (Maximum 8 bytes)</li> </ul>
<i>cust_attr</i>	<ul style="list-style-type: none"> <li>• Customization Setting attribute through QMI             <ul style="list-style-type: none"> <li>– bit 0: Values:                 <ul style="list-style-type: none"> <li>* 0 - read only</li> <li>* 1 - read/write</li> </ul> </li> </ul> </li> </ul>

### 8.127.2 Field Documentation

8.127.2.1 **WORD** custSettingInfo::cust\_attr

8.127.2.2 **CHAR** custSettingInfo::cust\_id[64+1]

8.127.2.3 **BYTE** custSettingInfo::cust\_value[8+1]

8.127.2.4 **WORD** custSettingInfo::id\_length

8.127.2.5 **WORD** custSettingInfo::value\_length

## 8.128 custSettingList Struct Reference

#### Data Fields

- [BYTE list\\_type](#)
- [WORD num\\_instances](#)
- [custSettingInfo custSetting](#) [256]

### 8.128.1 Detailed Description

This structure contains the fields of TLV Customization Setting List. This TLV is only applicable for 9x30 modules so far

## Parameters

<i>list_type</i>	<ul style="list-style-type: none"> <li>list type requested</li> </ul>
<i>num_instances</i>	<ul style="list-style-type: none"> <li>number of instances of customization setting</li> </ul>
<i>custSetting</i>	<ul style="list-style-type: none"> <li>See <a href="#">custSettingInfo</a> for more information</li> </ul>

## 8.128.2 Field Documentation

8.128.2.1 **custSettingInfo** *custSettingList::custSetting*[256]8.128.2.2 **BYTE** *custSettingList::list\_type*8.128.2.3 **WORD** *custSettingList::num\_instances*

## 8.129 dataBearers Struct Reference

## Data Fields

- [BYTE](#) *dataBearerMask*
- [QmiWDSDataBearerTechnology](#) \* *pCurDataBearerTechnology*
- [QmiWDSDataBearerTechnology](#) \* *pLastCallDataBearerTechnology*

## 8.129.1 Detailed Description

Structure to hold the data bearer technology values

## Parameters

<i>dataBearerMask</i> [OUT]	<ul style="list-style-type: none"> <li>This bit mask indicates if data bearer information for the current and/or last call has been received from the device. If a bit is set, then the information is available in the corresponding structure i.e. the one provided by the caller. Refer to <a href="#">qmiDataBearerMasks</a> for bit-mask positions.</li> </ul>
<i>pCurDataBearerTechnology</i> [OUT]	<ul style="list-style-type: none"> <li>current data bearer technology value. <ul style="list-style-type: none"> <li>– NULL if the parameter is not required</li> </ul> </li> </ul>
<i>pLastCallDataBearerTechnology</i> [OUT]	<ul style="list-style-type: none"> <li>last call data bearer technology value. <ul style="list-style-type: none"> <li>– NULL if the parameter is not required</li> </ul> </li> </ul>

## 8.129.2 Field Documentation

8.129.2.1 **BYTE** dataBearers::dataBearerMask

8.129.2.2 **QmiWSDDataBearerTechnology\*** dataBearers::pCurDataBearerTechnology

8.129.2.3 **QmiWSDDataBearerTechnology\*** dataBearers::pLastCallDataBearerTechnology

## 8.130 DataBearerTech Struct Reference

### Data Fields

- [ULONG](#) techType
- [ULONG](#) ratValue
- [ULONGLONG](#) soMask

### 8.130.1 Detailed Description

Network information structure

#### Parameters

<i>TechType</i>	<ul style="list-style-type: none"> <li>• Technology type</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - WDS_BEARER_TECH_NETWORK_3GPP - 3GPP</li> <li>– 1 - WDS_BEARER_TECH_NETWORK_3GPP2 - 3GPP2</li> </ul> </li> </ul>
<i>ratValue</i>	<ul style="list-style-type: none"> <li>• Radio Access Technology (RAT) value</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - WDS_BEARER_TECH_RAT_EX_NULL_BEARER - NULL bearer</li> <li>– 0x01 - WDS_BEARER_TECH_RAT_EX_3GPP_WCDMA - 3GPP WCDMA</li> <li>– 0x02 - WDS_BEARER_TECH_RAT_EX_3GPP_GERAN - 3GPP GERAN</li> <li>– 0x03 - WDS_BEARER_TECH_RAT_EX_3GPP_LTE - 3GPP LTE</li> <li>– 0x04 - WDS_BEARER_TECH_RAT_EX_3GPP_TDSCDMA - 3GPP TDSCDMA</li> <li>– 0x05 - WDS_BEARER_TECH_RAT_EX_3GPP_WLAN - 3GPP WLAN</li> <li>– 0x64 - WDS_BEARER_TECH_RAT_EX_3GPP_MAX - 3GPP maximum</li> <li>– 0x65 - WDS_BEARER_TECH_RAT_EX_3GPP2_1X - 3GPP2 1X</li> <li>– 0x66 - WDS_BEARER_TECH_RAT_EX_3GPP2_HRPD - 3GPP2 HRPD</li> <li>– 0x67 - WDS_BEARER_TECH_RAT_EX_3GPP2_EHRPD - 3GPP2 EHRPD</li> <li>– 0x68 - WDS_BEARER_TECH_RAT_EX_3GPP2_WLAN - 3GPP2 WLAN</li> <li>– 0xC8 - WDS_BEARER_TECH_RAT_EX_3GPP2_MAX - 3GPP2 maximum</li> </ul> </li> </ul>

<i>SOMask</i>	<ul style="list-style-type: none"> <li>• Service Option (SO) mask to indicate the service option or type of application. An SO mask value of zero indicates that this field is ignored.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - SO mask unspecified</li> </ul> </li> <li>• 3GPP SO mask: <ul style="list-style-type: none"> <li>– 0x01 - WCDMA</li> <li>– 0x02 - HSDPA</li> <li>– 0x04 - HSUPA</li> <li>– 0x08 - HSDPAPLUS</li> <li>– 0x10 - DC HSDPAPLUS</li> <li>– 0x20 - 64 QAM</li> <li>– 0x40 - HSPA</li> <li>– 0x80 - GPRS</li> <li>– 0x100 - EDGE</li> <li>– 0x200 - GSM</li> <li>– 0x400 - S2B</li> <li>– 0x800 - LTE limited service</li> <li>– 0x1000 - LTE FDD</li> <li>– 0x2000 - LTE TDD</li> </ul> </li> <li>• 3GPP2 SO mask: <ul style="list-style-type: none"> <li>– 0x01000000 - 1X IS95</li> <li>– 0x02000000 - 1X IS2000</li> <li>– 0x04000000 - 1X IS2000 REL A</li> <li>– 0x08000000 - HDR REV0 DPA</li> <li>– 0x10000000 - HDR REVA DPA</li> <li>– 0x20000000 - HDR REVB DPA</li> <li>– 0x40000000 - HDR REVA MPA</li> <li>– 0x80000000 - HDR REVB MPA</li> <li>– 0x100000000 - HDR REVA EMPA</li> <li>– 0x200000000 - HDR REVB EMPA</li> <li>– 0x400000000 - HDR REVB MMPA</li> <li>– 0x800000000 - HDR EVDO FMC</li> </ul> </li> </ul>
---------------	---

## 8.130.2 Field Documentation

### 8.130.2.1 ULONG DataBearerTech::ratValue

### 8.130.2.2 ULONGLONG DataBearerTech::soMask

### 8.130.2.3 ULONG DataBearerTech::techType

## 8.131 DataBearerTechExt Struct Reference

### Data Fields

- [DataBearerTech](#) \* [pBearerTech](#)
- [DataBearerTech](#) \* [pLastBearerTech](#)

### 8.131.1 Detailed Description

Data Bearer Technology Ext

#### Parameters

<i>pBearerTech</i>	[OUT] <ul style="list-style-type: none"><li>• See <a href="#">DataBearerTech</a> for more information</li></ul>
<i>pLastBearerTech</i>	[OUT] <ul style="list-style-type: none"><li>• See <a href="#">DataBearerTech</a> for more information</li></ul>

### 8.131.2 Field Documentation

8.131.2.1 [DataBearerTech](#)\* [DataBearerTechExt::pBearerTech](#)

8.131.2.2 [DataBearerTech](#)\* [DataBearerTechExt::pLastBearerTech](#)

## 8.132 dataBearerTechnology Struct Reference

### Data Fields

- [BYTE](#) [currentNetwork](#)
- [ULONG](#) [ratMask](#)
- [ULONG](#) [soMask](#)

### 8.132.1 Detailed Description

Structure to hold the current data bearer technology values

#### Parameters

<i>pCurrent-Network</i> [OUT]	<ul style="list-style-type: none"><li>• current selected network<ul style="list-style-type: none"><li>– 0 - UNKNOWN</li><li>– 1 - 3GPP2</li><li>– 2 - 3GPP</li></ul></li></ul>
-------------------------------	--

<i>pRatMask[OUT]</i>	<ul style="list-style-type: none"> <li>• Radio Access Technology (RAT) mask to indicate the type of technology (RAT mask value of zero indicates that this field is ignored) <ul style="list-style-type: none"> <li>– 0x8000 - NULL Bearer</li> <li>– 0x0000 - DO_NOT_CARE CDMA RAT mask</li> <li>– 0x01 - CDMA_1X</li> <li>– 0x02 - EVDO_REV0</li> <li>– 0x04 - EVDO_REVA UMTS RAT mask</li> <li>– 0x01 - WCDMA</li> <li>– 0x02 - GPRS</li> <li>– 0x04 - HSDPA</li> <li>– 0x08 - HSUPA</li> <li>– 0x10 - EDGE</li> <li>– 0x20 - LTE</li> <li>– 0x40 - HSDPA+</li> <li>– 0x80 - DC_HSDPA+</li> </ul> </li> </ul>
<i>pSoMask[OUT]</i>	<ul style="list-style-type: none"> <li>• Service Option (SO) mask to indicate the SO or type of application (SO mask value of zero indicates that this field is ignored) <ul style="list-style-type: none"> <li>– 0x00 - DO_NOT_CARE CDMA 1X SO mask</li> <li>– 0x01 - CDMA_1X_IS95</li> <li>– 0x02 - CDMA_1X_IS2000</li> <li>– 0x04 - CDMA_1X_IS2000_REL_A CDMA EV-DO Rev A SO mask</li> <li>– 0x01 - EVDO_REVA_DPA</li> <li>– 0x02 - EVDO_REVA_MFPA</li> <li>– 0x04 - EVDO_REVA_EMPA</li> <li>– 0x08 - EVDO_REVA_EMPA_EHRPD</li> </ul> </li> </ul>

### 8.132.2 Field Documentation

8.132.2.1 **BYTE** `dataBearerTechnology::currentNetwork`

8.132.2.2 **ULONG** `dataBearerTechnology::ratMask`

8.132.2.3 **ULONG** `dataBearerTechnology::soMask`

## 8.133 dataRate Struct Reference

### Data Fields

- [ULONG dataRateMax](#)
- [ULONG guaranteedRate](#)



### 8.133.1 Detailed Description

This structure contains the IP flow data rate min max

## Parameters

<i>dataRateMax</i>	Maximum required data rate (bits per second)
<i>guaranteedRate</i>	Minimum guaranteed data rate (bits per second)

## 8.133.2 Field Documentation

8.133.2.1 **ULONG** dataRate::dataRateMax8.133.2.2 **ULONG** dataRate::guaranteedRate

## 8.134 dataSrvCapabilities Struct Reference

## Data Fields

- [BYTE](#) dataCapabilitiesLen
- [BYTE](#) dataCapabilities [0x20]

## 8.134.1 Detailed Description

This structure contains the data services capability

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>dataCapabilitiesLen</i>	<ul style="list-style-type: none"> <li>• Length of data capabilities list</li> <li>• Defaults to zero</li> </ul>
<i>dataCapabilities</i>	<ul style="list-style-type: none"> <li>• List of data capabilities</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - GPRS</li> <li>– 0x02 - EDGE</li> <li>– 0x03 - HSDPA</li> <li>– 0x04 - HSUPA</li> <li>– 0x05 - WCDMA</li> <li>– 0x06 - CDMA</li> <li>– 0x07 - EV-DO Rev0</li> <li>– 0x08 - EV-DO RevA</li> <li>– 0x09 - GSM</li> <li>– 0x0A - EV-DO Rev B</li> <li>– 0x0B - LTE</li> <li>– 0x0C - HSDPA+</li> <li>– 0x0D - DC-HSDPA+</li> </ul> </li> </ul>

### 8.134.2 Field Documentation

8.134.2.1 **BYTE** dataSrvCapabilities::dataCapabilities[0x20]

8.134.2.2 **BYTE** dataSrvCapabilities::dataCapabilitiesLen

## 8.135 DataStatusDetail Struct Reference

### Data Fields

- [ULONG IPAddress](#)
- [BYTE LastErrCode](#)

### 8.135.1 Detailed Description

This structure contains Data Status Details

## Parameters

<i>IPAddress</i>	<ul style="list-style-type: none"> <li>• IP Address</li> <li>• 0xABCDEFGH - AB.CD.EF.GH</li> <li>• Example: <ul style="list-style-type: none"> <li>– 0x12345678 - 18.52.86.120</li> <li>0x12=18 0x34=52 0x56=86 0x78=120</li> </ul> </li> <li>• 0xFFFFFFFF - NA</li> </ul>
<i>LastErrCode</i>	<ul style="list-style-type: none"> <li>• MIP Error code <ul style="list-style-type: none"> <li>– 0x00 - MIP_RRP_CODE_SUCCESS</li> <li>– 0x01 - MIP_RRP_CODE_SUCCESS_NO_SIM_BINDINGS</li> <li>– 0x40 - MIP_RRP_CODE_FAILURE_FA_REASON_UNSPECIFIED</li> <li>– 0x41 - MIP_RRP_CODE_FAILURE_FA_ADMIN_PROHIBITED</li> <li>– 0x42 - MIP_RRP_CODE_FAILURE_FA_INSUFFICIENT_RESOURCES</li> <li>– 0x43 - MIP_RRP_CODE_FAILURE_FA_MOBILE_NODE_FAILED_AUTH</li> <li>– 0x44 - MIP_RRP_CODE_FAILURE_FA_HA_FAILED_AUTH</li> <li>– 0x45 - MIP_RRP_CODE_FAILURE_FA_REQUESTED_LIFETIME_TOO_LONG</li> <li>– 0x46 - MIP_RRP_CODE_FAILURE_FA_MALFORMED_REQUEST</li> <li>– 0x47 - MIP_RRP_CODE_FAILURE_FA_MALFORMED_REPLY</li> <li>– 0x48 - MIP_RRP_CODE_FAILURE_FA_ENCAPSULATION_UNAVAILABLE</li> <li>– 0x49 - MIP_RRP_CODE_FAILURE_FA_VJHC_UNAVAILABLE</li> <li>– 0x4A - MIP_RRP_CODE_FAILURE_FA_CANT_REV_TUN</li> <li>– 0x4B - MIP_RRP_CODE_FAILURE_FA_MUST_REV_TUN</li> <li>– 0x4C - MIP_RRP_CODE_FAILURE_FA_BAD_TTL</li> <li>– 0x4D - MIP_RRP_CODE_FAILURE_INVALID_COA</li> <li>– 0x4F - MIP_RRP_CODE_FAILURE_FA_DELIVERY_STYLE_NOT_SUPPORTED</li> <li>– 0x59 - MIP_RRP_CODE_FAILURE_FA_VS_REASON</li> <li>– 0x61 - MIP_RRP_CODE_FAILURE_MISSING_NAI</li> <li>– 0x62 - MIP_RRP_CODE_FAILURE_MISSING_HA_ADDR</li> <li>– 0x63 - MIP_RRP_CODE_FAILURE_MISSING_HOMEADDR</li> <li>– 0x68 - MIP_RRP_CODE_FAILURE_UNKNOWN_CHALLENGE</li> <li>– 0x69 - MIP_RRP_CODE_FAILURE_MISSING_CHALLENGE</li> <li>– 0x6A - MIP_RRP_CODE_FAILURE_STALE_CHALLENGE</li> <li>– 0x6B - MIP_RRP_CODE_FAILURE_MISSING_MN_FA</li> <li>– 0x80 - MIP_RRP_CODE_FAILURE_HA_REASON_UNSPECIFIED</li> <li>– 0x81 - MIP_RRP_CODE_FAILURE_HA_ADMIN_PROHIBITED</li> <li>– 0x82 - MIP_RRP_CODE_FAILURE_HA_INSUFFICIENT_RESOURCES</li> <li>– 0x83 - MIP_RRP_CODE_FAILURE_HA_MOBILE_NODE_FAILED_AUTH</li> <li>– 0x84 - MIP_RRP_CODE_FAILURE_HA_FA_FAILED_AUTH</li> <li>– 0x85 - MIP_RRP_CODE_FAILURE_HA_REG_ID_MISMATCH</li> <li>– 0x86 - MIP_RRP_CODE_FAILURE_HA_MALFORMED_REQUEST</li> <li>– 0x88 - MIP_RRP_CODE_FAILURE_UNKNOWN_HA</li> <li>– 0x89 - MIP_RRP_CODE_FAILURE_HA_CANT_REV_TUN</li> <li>– 0x8A - MIP_RRP_CODE_FAILURE_HA_MUST_REV_TUN</li> <li>– 0x8B - MIP_RRP_CODE_FAILURE_HA_ENCAPSULATION_UNAVAILABLE</li> </ul> </li> </ul>

### 8.135.2 Field Documentation

8.135.2.1 **ULONG** DataStatusDetail::IPAddress

8.135.2.2 **BYTE** DataStatusDetail::LastErrCode

## 8.136 DataUlongLongTlv Struct Reference

### Data Fields

- [BYTE](#) TlvPresent
- [ULONGLONG](#) ullData

### 8.136.1 Field Documentation

8.136.1.1 **BYTE** DataUlongLongTlv::TlvPresent

8.136.1.2 **ULONGLONG** DataUlongLongTlv::ullData

## 8.137 DataUlongTlv Struct Reference

### Data Fields

- [BYTE](#) TlvPresent
- [ULONG](#) ulData

### 8.137.1 Field Documentation

8.137.1.1 **BYTE** DataUlongTlv::TlvPresent

8.137.1.2 **ULONG** DataUlongTlv::ulData

## 8.138 DcsUsbPortNames Struct Reference

### Data Fields

- [CHAR](#) AtCmdPort [32]
- [CHAR](#) NmeaPort [32]
- [CHAR](#) DmPort [32]

### 8.138.1 Field Documentation

8.138.1.1 **CHAR** DcsUsbPortNames::AtCmdPort[32]

8.138.1.2 **CHAR** DcsUsbPortNames::DmPort[32]

8.138.1.3 **CHAR** DcsUsbPortNames::NmeaPort[32]

## 8.139 delAssistDataStatus Struct Reference

## Data Fields

- [ULONG status](#)

### 8.139.1 Detailed Description

Contain the parameters passed for SetLocDeleteAssistDataCallback by the device.

#### Parameters

<i>status</i>	<ul style="list-style-type: none"> <li>• Status of the Delete Assist Data request</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– eQMI_LOC_SUCCESS (0) - Request was completed successfully</li> <li>– eQMI_LOC_GENERAL_FAILURE (1) - Request failed because of a general failure</li> <li>– eQMI_LOC_UNSUPPORTED (2) - Request failed because it is not supported</li> <li>– eQMI_LOC_INVALID_PARAMETER (3) - Request failed because it contained invalid parameters</li> <li>– eQMI_LOC_ENGINE_BUSY (4) - Request failed because the engine is busy</li> <li>– eQMI_LOC_PHONE_OFFLINE (5) - Request failed because the phone is offline</li> <li>– eQMI_LOC_TIMEOUT (6) - Request failed because it timed out</li> <li>– eQMI_LOC_CONFIG_NOT_SUPPORTED (7) - Request failed because an undefined configuration was requested</li> <li>– eQMI_LOC_INSUFFICIENT_MEMORY (8) - Request failed because the engine could not allocate sufficient memory for the request</li> <li>– eQMI_LOC_MAX_GEOFENCE_PROGRAMMED (9) - Request failed because the maximum number of Geofences are already programmed</li> <li>– eQMI_LOC_XTRA_VERSION_CHECK_FAILURE (10) - Location service failed because of an XTRA version-based file format check failure</li> </ul> </li> </ul>
---------------	---

#### Note

None

### 8.139.2 Field Documentation

#### 8.139.2.1 ULONG delAssistDataStatus::status

## 8.140 depersonalizationInformation Struct Reference

## Data Fields

- [BYTE feature](#)
- [BYTE operation](#)
- [BYTE ckLen](#)
- [BYTE ckVal](#) [255]

### 8.140.1 Detailed Description

This structure contains the Depersonalization Information.

## Parameters

<i>feature</i>	<ul style="list-style-type: none"> <li>Indicates the personalization feature to de-activate or unblock. <ul style="list-style-type: none"> <li>0 - GW network personalization</li> <li>1 - GW network subset personalization</li> <li>2 - GW service provider personalization</li> <li>3 - GW corporate personalization</li> <li>4 - GW UIM personalization</li> <li>5 - 1X network type 1 personalization</li> <li>6 - 1X network type 2 personalization</li> <li>7 - 1X HRPD personalization</li> <li>8 - 1X service provider personalization</li> <li>9 - 1X corporate personalization</li> <li>10 - 1X RUIM personalization</li> </ul> </li> </ul>
<i>operation</i>	<ul style="list-style-type: none"> <li>Indicates the operation to perform. <ul style="list-style-type: none"> <li>0 - Deactivate personalization.</li> <li>1 - Unblock personalization.</li> </ul> </li> </ul>
<i>ckLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. control key value.</li> </ul>
<i>ckVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>Control key value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

## 8.140.2 Field Documentation

8.140.2.1 BYTE depersonalizationInformation::ckLen

8.140.2.2 BYTE depersonalizationInformation::ckVal[255]

8.140.2.3 BYTE depersonalizationInformation::feature

8.140.2.4 BYTE depersonalizationInformation::operation

## 8.141 detailSvcInfo Struct Reference

## Data Fields

- BYTE [srvStatus](#)
- BYTE [srvCapability](#)
- BYTE [hdrSrvStatus](#)
- BYTE [hdrHybrid](#)
- BYTE [isSysForbidden](#)



### 8.141.1 Detailed Description

This structure contains Detailed Service information

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>srvStatus</i>	<ul style="list-style-type: none"> <li>• Service status</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service available</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - MS in power save or deep sleep</li> </ul> </li> </ul>
<i>srvCapability</i>	<ul style="list-style-type: none"> <li>• System's service capability</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - No Service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> <li>– 0x04 - MS found the right system but not yet registered/attached</li> </ul> </li> </ul>
<i>hdrSrvStatus</i>	<ul style="list-style-type: none"> <li>• HDR service status</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service available</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - MS in power save or deep sleep</li> </ul> </li> </ul>

<i>hdrHybrid</i>	<ul style="list-style-type: none"> <li>• HDR hybrid information</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - System is not hybrid</li> <li>– 0x01 - System is hybrid</li> </ul> </li> </ul>
<i>isSysForbidden</i>	<ul style="list-style-type: none"> <li>• Forbidden system information</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - System is not a forbidden system</li> <li>– 0x01 - System is a forbidden system</li> </ul> </li> </ul>

## 8.141.2 Field Documentation

8.141.2.1 **BYTE** detailSvcInfo::hdrHybrid

8.141.2.2 **BYTE** detailSvcInfo::hdrSrvStatus

8.141.2.3 **BYTE** detailSvcInfo::isSysForbidden

8.141.2.4 **BYTE** detailSvcInfo::srvCapability

8.141.2.5 **BYTE** detailSvcInfo::srvStatus

## 8.142 DeviceConfigDetail Struct Reference

### Data Fields

- [BYTE Technology](#)
- [BYTE QLIC](#)
- [BYTE Chipset](#)
- [BYTE HWVersion](#)

### 8.142.1 Detailed Description

This structure contains Device Configuration Details

## Parameters

<i>Technology</i>	<ul style="list-style-type: none"> <li>• Current technology in use <ul style="list-style-type: none"> <li>– 0x00 - 1x RTT</li> <li>– 0x01 - EVDO Rev 0</li> <li>– 0x02 - EVDO Rev A</li> <li>– 0xFF - NA</li> </ul> </li> </ul>
<i>QLIC</i>	<ul style="list-style-type: none"> <li>• Quasi Linear Interference Cancellation <ul style="list-style-type: none"> <li>– 0x00 - Not supported</li> <li>– 0x01 - Supported</li> </ul> </li> </ul>
<i>Chipset</i>	<ul style="list-style-type: none"> <li>• Qualcomm platform <ul style="list-style-type: none"> <li>– 0x4E - MDM6200</li> <li>– 0x4F - MDM6600</li> <li>– 0xFF - NA</li> </ul> </li> </ul>
<i>HWVersion</i>	<ul style="list-style-type: none"> <li>• Hardware version <ul style="list-style-type: none"> <li>– 0x00 - BSHWREV0</li> <li>– 0x01 - BSHWREV1</li> <li>– 0x02 - BSHWREV2</li> <li>– 0x03 - BSHWREV3</li> <li>– 0x04 - BSHWREVMAX</li> <li>– 0xFF - BSHWREVUNKNOWN</li> </ul> </li> </ul>

## 8.142.2 Field Documentation

8.142.2.1 BYTE DeviceConfigDetail::Chipset

8.142.2.2 BYTE DeviceConfigDetail::HWVersion

8.142.2.3 BYTE DeviceConfigDetail::QLIC

8.142.2.4 BYTE DeviceConfigDetail::Technology

## 8.143 DHCPOption Struct Reference

## Data Fields

- [BYTE optCode](#)
- [BYTE optValLen](#)

- [BYTE \\* pOptVal](#)

### 8.143.1 Detailed Description

This structure contains DHCPv4 lease option values

#### Parameters

<i>optCode</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– Option code</li> </ul> </li> </ul>
<i>optValLen</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– Option value length</li> </ul> </li> </ul>
<i>pOptValue</i>	<ul style="list-style-type: none"> <li>• Val <ul style="list-style-type: none"> <li>– Option value</li> </ul> </li> </ul>

### 8.143.2 Field Documentation

8.143.2.1 [BYTE DHCPOption::optCode](#)

8.143.2.2 [BYTE DHCPOption::optValLen](#)

8.143.2.3 [BYTE\\* DHCPOption::pOptVal](#)

## 8.144 DHCPOptionList Struct Reference

### Data Fields

- [BYTE numOpt](#)
- [DHCPOption \\* pOptions](#)

### 8.144.1 Detailed Description

This structure contains DHCPv4 lease option list

#### Parameters

<i>optListSize</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– Size of Option List</li> </ul> </li> </ul>
--------------------	---

<i>pOptions</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– Options</li> </ul> </li> </ul>
-----------------	---

### 8.144.2 Field Documentation

8.144.2.1 **BYTE** DHCPOptionList::numOpt

8.144.2.2 **DHCPOption\*** DHCPOptionList::pOptions

## 8.145 diagInfo Struct Reference

### Data Fields

- [BYTE diagInfoLen](#)
- [BYTE diagnosticInfo](#) [255]

### 8.145.1 Detailed Description

This structure contains Diagnostic Information

#### Parameters

<i>diagInfoLen</i>	<ul style="list-style-type: none"> <li>• Provides the length of information which follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>diagnosticInfo[M-AX_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"> <li>• Diagnostic information.</li> </ul>

### 8.145.2 Field Documentation

8.145.2.1 **BYTE** diagInfo::diagInfoLen

8.145.2.2 **BYTE** diagInfo::diagnosticInfo[255]

## 8.146 dirNum Struct Reference

### Data Fields

- [BYTE dirNumLen](#)
- [BYTE dirNum](#) [255]

### 8.146.1 Detailed Description

This structure contains the parameters for Directory Number Information

## Parameters

<i>dirNumLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements: <ul style="list-style-type: none"> <li>– <i>dir_num</i></li> </ul> </li> <li>• If zero(0), then no information follows.</li> </ul>
<i>dirNum</i>	<ul style="list-style-type: none"> <li>• Directory number in ASCII characters.</li> </ul>

## 8.146.2 Field Documentation

8.146.2.1 BYTE *dirNum::dirNum*[255]8.146.2.2 BYTE *dirNum::dirNumLen*

## 8.147 dms\_ActivationStatusTlv Struct Reference

## Data Fields

- uint16\_t [TlvPresent](#)
- uint32\_t [activationStatus](#)

## 8.147.1 Detailed Description

Activation Status Tlv

## Parameters

<i>activationStatus</i>	<ul style="list-style-type: none"> <li>• Service Activation Code <ul style="list-style-type: none"> <li>– 0 - Service not activated</li> <li>– 1 - Service activated</li> <li>– 2 - Activation connecting</li> <li>– 3 - Activation connected</li> <li>– 4 - OTASP security authenticated</li> <li>– 5 - OTASP NAM downloaded</li> <li>– 6 - OTASP MDN downloaded</li> <li>– 7 - OTASP IMSI downloaded</li> <li>– 8 - OTASP PRL downloaded</li> <li>– 9 - OTASP SPC downloaded</li> <li>– 10 - OTASP settings committed</li> </ul> </li> </ul>
-------------------------	--

## 8.147.2 Field Documentation

8.147.2.1 uint32\_t *dms\_ActivationStatusTlv::activationStatus*

8.147.2.2 uint16\_t dms\_ActivationStatusTlv::TlvPresent

## 8.148 dms\_OperatingModeTlv Struct Reference

### Data Fields

- uint16\_t [TlvPresent](#)
- uint32\_t [operatingMode](#)

### 8.148.1 Detailed Description

Operating Mode Tlv

Parameters

<i>operatingMode</i>	<ul style="list-style-type: none"><li>• 0 - Online</li><li>• 1 - Low power</li><li>• 2 - Factory test mode</li><li>• 3 - Offline</li><li>• 4 - Resetting</li><li>• 5 - Shutting down</li><li>• 6 - Persistent low power</li><li>• 7 - Mode-only low power</li></ul>
----------------------	---

### 8.148.2 Field Documentation

8.148.2.1 uint32\_t dms\_OperatingModeTlv::operatingMode

8.148.2.2 uint16\_t dms\_OperatingModeTlv::TlvPresent

## 8.149 dmsCurrentPRLInfo Struct Reference

### Data Fields

- WORD \* [pPRLVersion](#)
- BYTE \* [pPRLPreference](#)

### 8.149.1 Detailed Description

This structure contains GetCurrentPRLInfo response parameter

## Parameters

<i>pPRLVersion</i> [O-UT]	- Optional <ul style="list-style-type: none"> <li>• PRL version of device.</li> </ul>
<i>pPRLPreference</i>	[OUT]- Optional <ul style="list-style-type: none"> <li>• PRL Preference             <ul style="list-style-type: none"> <li>– 0 - Unset</li> <li>– 1 - Set</li> </ul> </li> </ul>

## 8.149.2 Field Documentation

8.149.2.1 **BYTE\*** dmsCurrentPRLInfo::pPRLPreference8.149.2.2 **WORD\*** dmsCurrentPRLInfo::pPRLVersion

## 8.150 DMScustSettingInfo Struct Reference

## Data Fields

- uint16\_t [id\\_length](#)
- uint8\_t [cust\\_id](#) [64+1]
- uint16\_t [value\\_length](#)
- uint8\_t [cust\\_value](#) [8+1]
- uint16\_t [cust\\_attr](#)

## 8.150.1 Detailed Description

This structure contains information about Customization Setting. This TLV is only applicable for 9x30 modules so far



## Parameters

<i>id_length</i>	<ul style="list-style-type: none"> <li>length of cust_id field</li> </ul>
<i>cust_id</i>	<ul style="list-style-type: none"> <li>Customization ID (Maximum 64 bytes)</li> </ul>
<i>value_length</i>	<ul style="list-style-type: none"> <li>length of cust_value field</li> </ul>
<i>cust_value</i>	<ul style="list-style-type: none"> <li>Customization Setting Value (Maximum 8 bytes)</li> </ul>
<i>cust_attr</i>	<ul style="list-style-type: none"> <li>Customization Setting attribute through QMI <ul style="list-style-type: none"> <li>bit 0: Values: <ul style="list-style-type: none"> <li>* 0 - read only</li> <li>* 1 - read/write</li> </ul> </li> </ul> </li> </ul>

## 8.150.2 Field Documentation

8.150.2.1 uint16\_t DMScustSettingInfo::cust\_attr

8.150.2.2 uint8\_t DMScustSettingInfo::cust\_id[64+1]

8.150.2.3 uint8\_t DMScustSettingInfo::cust\_value[8+1]

8.150.2.4 uint16\_t DMScustSettingInfo::id\_length

8.150.2.5 uint16\_t DMScustSettingInfo::value\_length

## 8.151 DMScustSettingList Struct Reference

## Data Fields

- uint8\_t [list\\_type](#)
- uint16\_t [num\\_instances](#)
- [DMScustSettingInfo](#) [custSetting](#) [255+1]

## 8.151.1 Detailed Description

This structure contains the fields of TLV Customization Setting List. This TLV is only applicable for 9x30 modules so far

## Parameters

<i>list_type</i>	<ul style="list-style-type: none"> <li>list type requested</li> </ul>
<i>num_instances</i>	<ul style="list-style-type: none"> <li>number of instances of customization setting</li> </ul>
<i>custSetting</i>	<ul style="list-style-type: none"> <li>See <a href="#">custSettingInfo</a> for more information</li> </ul>

### 8.151.2 Field Documentation

8.151.2.1 **DMScustSettingInfo** DMScustSettingList::custSetting[255+1]

8.151.2.2 **uint8\_t** DMScustSettingList::list\_type

8.151.2.3 **uint16\_t** DMScustSettingList::num\_instances

## 8.152 DMSgetCustomFeatureV2 Struct Reference

### Data Fields

- [DMSgetCustomInput](#) \* [pGetCustomInput](#)
- [DMScustSettingInfo](#) \* [pCustSettingInfo](#)
- [DMScustSettingList](#) \* [pCustSettingList](#)

### 8.152.1 Detailed Description

This struture contains the TLV required to get the Customization Info and customization list.

#### Parameters

<i>IN]</i>	<p><a href="#">pGetCustomInput</a></p> <ul style="list-style-type: none"> <li>See <a href="#">getCustomInput</a> for more information</li> </ul>
<i>OUT]</i>	<p><a href="#">pCustSettingInfo</a></p> <ul style="list-style-type: none"> <li>See <a href="#">custSettingInfo</a> for more information</li> </ul>
<i>OUT]</i>	<p><a href="#">pCustSettingList</a></p> <ul style="list-style-type: none"> <li>See <a href="#">custSettingList</a> for more information</li> </ul>

### 8.152.2 Field Documentation

8.152.2.1 **DMScustSettingInfo\*** DMSgetCustomFeatureV2::pCustSettingInfo

8.152.2.2 **DMScustSettingList\*** DMSgetCustomFeatureV2::pCustSettingList

8.152.2.3 **DMSgetCustomInput\*** DMSgetCustomFeatureV2::pGetCustomInput

## 8.153 DMSgetCustomInput Struct Reference

### Data Fields

- uint8\_t [cust\\_id](#) [64+1]
- uint8\_t [list\\_type](#)

#### 8.153.1 Detailed Description

This structure contains which customization id or the list type want to retrieve from modem. This TLV is only applicable for 9x30 modules so far

##### Parameters

<i>cust_id</i>	<ul style="list-style-type: none"> <li>• Customization ID (Maximum 64 bytes)</li> </ul>
<i>list_type</i>	<ul style="list-style-type: none"> <li>• list type requested</li> </ul>

#### 8.153.2 Field Documentation

8.153.2.1 uint8\_t DMSgetCustomInput::cust\_id[64+1]

8.153.2.2 uint8\_t DMSgetCustomInput::list\_type

## 8.154 dmsIndicationRegisterReq Struct Reference

### Data Fields

- [BYTE](#) \* [pSwiGetResetInd](#)

#### 8.154.1 Detailed Description

This structure contains the SLQSDmsSwiIndicationRegister request parameters.

##### Parameters

<i>/N/</i>	<p>pGetResetInd [Optional]</p> <ul style="list-style-type: none"> <li>• Get Reset Info indication registration. The following callbacks would not be invoked if the indication is disabled. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
------------	---

##### Note

'NULL' value confirms that the indication value is not sent.

#### 8.154.2 Field Documentation

8.154.2.1 **BYTE\*** dmsIndicationRegisterReq::pSwiGetResetInd

## 8.155 dmsSwiGetResetInfo Struct Reference

### Data Fields

- [BYTE type](#)
- [BYTE source](#)

### 8.155.1 Detailed Description

This structure contains the TLV required to Get Reset Info.

#### Parameters

<i>OUT]</i>	type[OUT] <ul style="list-style-type: none"> <li>• type of reset or power down, possible values listed below:               <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - warm</li> <li>– 2 - hard</li> <li>– 3 - crash</li> <li>– 4 - power down</li> </ul> </li> </ul>
<i>OUT]</i>	source[OUT] <ul style="list-style-type: none"> <li>• entity which initiated the reset or power down, possible values listed below:               <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - user requested</li> <li>– 2 - hardware switch</li> <li>– 3 - temperature critical</li> <li>– 4 - voltage critical</li> <li>– 5 - configuration update</li> <li>– 6 - LWM2M</li> <li>– 7 - OMA-DM</li> <li>– 8 - FOTA</li> </ul> </li> </ul>

### 8.155.2 Field Documentation

8.155.2.1 **BYTE** dmsSwiGetResetInfo::source

8.155.2.2 **BYTE** dmsSwiGetResetInfo::type

## 8.156 Domain Struct Reference

### Data Fields

- [WORD domainLen](#)
- [CHAR domainName](#) [256]

### 8.156.1 Detailed Description

This structure contains the DomainName Information

Parameters

<i>domainLen</i>	<ul style="list-style-type: none"> <li>length of the received <a href="#">Domain</a> name</li> </ul>
<i>domainName</i>	<ul style="list-style-type: none"> <li><a href="#">Domain</a> name(Max 256 characters)</li> </ul>

### 8.156.2 Field Documentation

8.156.2.1 WORD Domain::domainLen

8.156.2.2 CHAR Domain::domainName[256]

## 8.157 DomainNameList Struct Reference

Data Fields

- [BYTE](#) numInstances
- struct [Domain](#) domain [10]

### 8.157.1 Detailed Description

This structure contains the [DomainNameList](#) Information

Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>Number of <a href="#">Domain</a> name received</li> </ul>
<i>domain</i>	<ul style="list-style-type: none"> <li><a href="#">Domain</a> name information(Max 10 Domain names)</li> </ul>

### 8.157.2 Field Documentation

8.157.2.1 struct Domain DomainNameList::domain[10]

8.157.2.2 BYTE DomainNameList::numInstances

## 8.158 DRCPParams Struct Reference

Data Fields

- [BYTE](#) DRCValue
- [BYTE](#) DRCCover

### 8.158.1 Detailed Description

This structure contains Data Rate Channel parameters

## Parameters

<i>DRCValue</i>	<ul style="list-style-type: none"><li>• Current Data Rate Channel</li></ul>
<i>DRCCover</i>	<ul style="list-style-type: none"><li>• Current Data Rate Channel cover</li></ul>

## 8.158.2 Field Documentation

## 8.158.2.1 BYTE DRCPParams::DRCCover

## 8.158.2.2 BYTE DRCPParams::DRCValue

## 8.159 DTMFInfo Struct Reference

## Data Fields

- [BYTE callID](#)
- [BYTE DTMFEvent](#)
- [BYTE digitCnt](#)
- [BYTE digitBuff](#) [255]

## 8.159.1 Detailed Description

This structure contains information about the DTMF (Dual Tone Multi-Frequency).

## Parameters

<i>callID</i>	<ul style="list-style-type: none"><li>• Call identifier for the current call.</li></ul>
<i>DTMFEvent</i>	<ul style="list-style-type: none"><li>• DTMF event<ul style="list-style-type: none"><li>– 0x00 - DTMF_EVENT_REV_BURST - Sends a CDMA-burst DTMF</li><li>– 0x01 - DTMF_EVENT_REV_START_CONT - Starts a continuous DTMF tone</li><li>– 0x03 - DTMF_EVENT_REV_STOP_CONT - Stops a continuous DTMF tone</li><li>– 0x05 - DTMF_EVENT_FWD_BURST - Received a CDMA-burst DTMF message</li><li>– 0x06 - DTMF_EVENT_FWD_START_CONT - Received a start-continuous DTMF tone order</li><li>– 0x07 - DTMF_EVENT_FWD_STOP_CONT - Received a stop-continuous DTMF tone order</li></ul></li></ul>

<i>digitCnt</i>	<ul style="list-style-type: none"> <li>• Number of set of following element i.e. digitBuff.</li> </ul>
<i>digitBuff[MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• DTMF digit buffer in ASCII string which is NULL terminated</li> </ul>

## 8.159.2 Field Documentation

### 8.159.2.1 BYTE DTMFInfo::callID

### 8.159.2.2 BYTE DTMFInfo::digitBuff[255]

### 8.159.2.3 BYTE DTMFInfo::digitCnt

### 8.159.2.4 BYTE DTMFInfo::DTMFEvent

## 8.160 DTMFLengths Struct Reference

### Data Fields

- [BYTE DTMFPulseWidth](#)
- [BYTE DTMFInterdigitInterval](#)

### 8.160.1 Detailed Description

This structure contains Voice Burst DTMF pulse length information

#### Parameters

<i>DTMFPulse-Width</i>	<ul style="list-style-type: none"> <li>• DTMF pulse width. Values: <ul style="list-style-type: none"> <li>– 0x00 - DTMF_ONLENGTH_95MS - 95 ms</li> <li>– 0x01 - DTMF_ONLENGTH_150MS - 150 ms</li> <li>– 0x02 - DTMF_ONLENGTH_200MS - 200 ms</li> <li>– 0x03 - DTMF_ONLENGTH_250MS - 250 ms</li> <li>– 0x04 - DTMF_ONLENGTH_300MS - 300 ms</li> <li>– 0x05 - DTMF_ONLENGTH_350MS - 350 ms</li> <li>– 0x06 - DTMF_ONLENGTH_SMS SMS Tx special pulse width</li> </ul> </li> </ul>
<i>DTMFInterdigit-Interval</i>	<ul style="list-style-type: none"> <li>• DTMF interdigit interval Values: <ul style="list-style-type: none"> <li>– 0x00 - DTMF_OFFLENGTH_60MS - 60 ms</li> <li>– 0x01 - DTMF_OFFLENGTH_100MS - 100 ms</li> <li>– 0x02 - DTMF_OFFLENGTH_150MS - 150 ms</li> <li>– 0x03 - DTMF_OFFLENGTH_200MS - 200 ms</li> </ul> </li> </ul>



### 8.160.2 Field Documentation

8.160.2.1 `BYTE DTMFLengths::DTMFInterdigitInterval`

8.160.2.2 `BYTE DTMFLengths::DTMFPulseWidth`

## 8.161 DUNCallInfoInd Struct Reference

### Data Fields

- [BYTE MdmConnStatus](#)
- [WORD CallEndReason](#)
- [ULONGLONG TXOKBytesCount](#)
- [ULONGLONG RXOKBytesCount](#)
- [BYTE DormancyStatus](#)
- [BYTE DataBearerTech](#)
- [channelRate ChannelRate](#)

### 8.161.1 Field Documentation

8.161.1.1 `WORD DUNCallInfoInd::CallEndReason`

8.161.1.2 `channelRate DUNCallInfoInd::ChannelRate`

8.161.1.3 `BYTE DUNCallInfoInd::DataBearerTech`

8.161.1.4 `BYTE DUNCallInfoInd::DormancyStatus`

8.161.1.5 `BYTE DUNCallInfoInd::MdmConnStatus`

8.161.1.6 `ULONGLONG DUNCallInfoInd::RXOKBytesCount`

8.161.1.7 `ULONGLONG DUNCallInfoInd::TXOKBytesCount`

## 8.162 dunchannelRate Struct Reference

### Data Fields

- `uint32_t` [CurrChanTxRate](#)
- `uint32_t` [CurrChanRxRate](#)
- `uint32_t` [MaxChanTxRate](#)
- `uint32_t` [MaxChanRxRate](#)

### 8.162.1 Detailed Description

#### Parameters

<i>CurrChanTxRate</i>	instantaneous channel Tx rate in bits per second
<i>CurrChanRxRate</i>	instantaneous channel Rx rate in bits per second
<i>MaxChanTxRate</i>	maximum Tx rate that can be assigned to the device
<i>MaxChanRxRate</i>	maximum Rx rate that can be assigned to the device

### 8.162.2 Field Documentation

8.162.2.1 `uint32_t dunchannelRate::CurrChanRxRate`

8.162.2.2 `uint32_t dunchannelRate::CurrChanTxRate`

8.162.2.3 `uint32_t dunchannelRate::MaxChanRxRate`

8.162.2.4 `uint32_t dunchannelRate::MaxChanTxRate`

## 8.163 ecioListElement Struct Reference

### Data Fields

- [SHORT](#) `ecio`
- [BYTE](#) `radiolf`

### 8.163.1 Detailed Description

This structure contains the ECIO Information

#### Parameters

<i>ecio</i>	<ul style="list-style-type: none"> <li>• ECIO value in dBm</li> </ul>
<i>radiolf</i>	<ul style="list-style-type: none"> <li>• Radio interface technology of the signal being measured             <ul style="list-style-type: none"> <li>– 0x00 - RADIO_IF_NO_SVC - None (no service)</li> <li>– 0x01 - RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - RADIO_IF_CDMA_1XEVD0 - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 - RADIO_IF_AMPS - AMPS</li> <li>– 0x04 - RADIO_IF_GSM - GSM</li> <li>– 0x05 - RADIO_IF_UMTS - UMTS</li> </ul> </li> </ul>

### 8.163.2 Field Documentation

8.163.2.1 `SHORT ecioListElement::ecio`

8.163.2.2 `BYTE ecioListElement::radiolf`

## 8.164 ECIOThresh Struct Reference

### Data Fields

- [BYTE](#) `ECIOThresListLen`
- [SHORT](#) \* `pECIOThresList`

### 8.164.1 Detailed Description

This structure contains ECIO threshold related parameters.

## Parameters

<i>ECIOThresListLen</i>	<ul style="list-style-type: none"> <li>Length of the ECIO threshold list parameter to follow</li> </ul>
<i>pECIOThresList</i>	<ul style="list-style-type: none"> <li>Sequence of thresholds delimiting ECIO event reporting bands</li> <li>Every time a new ECIO value crosses a threshold value, an event report indication message with the new ECIO value is sent to the requesting control point. For this field <ul style="list-style-type: none"> <li>Each ECIO threshold value is a signed 2 byte value</li> <li>Each ECIO threshold value increments in negative 0.5 dB, e.g., an ECIO threshold value of 2 means -1dB</li> <li>Maximum number of threshold values is 16</li> <li>At least one value must be specified</li> <li>Threshold values specified above are used for all RATs</li> </ul> </li> </ul>

## 8.164.2 Field Documentation

8.164.2.1 BYTE ECIOThresh::ECIOThresListLen

8.164.2.2 SHORT\* ECIOThresh::pECIOThresList

## 8.165 ECTNum Struct Reference

## Data Fields

- BYTE ECTCallState
- BYTE presentationInd
- BYTE number [81]

## 8.165.1 Detailed Description

Contains the parameters passed for Explicit Communication Transfer by the device.

## Parameters

<i>ECTCallState</i>	<ul style="list-style-type: none"> <li>ECT call state: <ul style="list-style-type: none"> <li>0x00 - ECT_CALL_STATE_NONE - None</li> <li>0x01 - ECT_CALL_STATE_ALERTING - Alerting</li> <li>0x02 - ECT_CALL_STATE_ACTIVE - Active</li> </ul> </li> </ul>
---------------------	--

<i>presentationInd</i>	<ul style="list-style-type: none"> <li>• Presentation indicator <ul style="list-style-type: none"> <li>– 0x00 - presentationAllowedAddress</li> <li>– 0x01 - presentationRestricted</li> <li>– 0x02 - numberNotAvailable</li> <li>– 0x04 - presentationRestrictedAddress</li> </ul> </li> </ul>
<i>number</i>	<ul style="list-style-type: none"> <li>• Number in ASCII characters terminated by NULL</li> </ul>

## 8.165.2 Field Documentation

8.165.2.1 **BYTE** ECTNum::ECTCallState

8.165.2.2 **BYTE** ECTNum::number[81]

8.165.2.3 **BYTE** ECTNum::presentationInd

## 8.166 encryptedPIN1 Struct Reference

### Data Fields

- [BYTE](#) pin1Len
- [BYTE](#) pin1Val [255]

## 8.166.1 Detailed Description

This structure contains the encrypted PIN1 Information.

### Parameters

<i>pin1Len</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements ie encrypted PIN1 value.</li> <li>• If zero(0), no information follows.</li> </ul>
<i>pin1Val</i>	<ul style="list-style-type: none"> <li>• Encrypted PIN1 value.</li> </ul>

### Note

This value is returned only when PIN1 is enabled successfully and the feature is supported.

## 8.166.2 Field Documentation

8.166.2.1 **BYTE** encryptedPIN1::pin1Len

8.166.2.2 **BYTE** encryptedPIN1::pin1Val[255]

## 8.167 ERIFileparams Struct Reference

### Data Fields

- [WORD](#) \* [pFileSize](#)
- [BYTE](#) \* [pFile](#)

### 8.167.1 Detailed Description

This structure contains Extended Roaming Indicator(ERI) file parameters

#### Parameters

<i>pFileSize</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Upon input, the maximum number of bytes that file contents array can contain.</li> <li>• Upon successful output, actual number of bytes written to file contents array</li> </ul>
<i>pFile</i> [OUT]	<ul style="list-style-type: none"> <li>• ERI data read from persistent storage( Max size is 1024 )</li> </ul>

### 8.167.2 Field Documentation

8.167.2.1 [BYTE](#)\* [ERIFileparams::pFile](#)

8.167.2.2 [WORD](#)\* [ERIFileparams::pFileSize](#)

## 8.168 errorRateListElement Struct Reference

### Data Fields

- [USHORT](#) [errorRate](#)
- [BYTE](#) [radiolf](#)

### 8.168.1 Detailed Description

This structure contains the Error Rate Information

## Parameters

<i>errorRate</i>	<ul style="list-style-type: none"> <li>• Error rate value corresponds to the RAT that is currently registered. <ul style="list-style-type: none"> <li>– For CDMA, the error rate reported is Frame Error Rate: <ul style="list-style-type: none"> <li>* Valid error rate values between 1 and 10000 are returned to indicate percentage, e.g., a value of 300 means the error rate is 3%</li> <li>* A value of 0xFFFF indicates that the error rate is unknown or unavailable</li> </ul> </li> <li>– For HDR, the error rate reported is Packet Error Rate: <ul style="list-style-type: none"> <li>* Valid error rate values between 1 and 10000 are returned to indicate percentage, e.g., a value of 300 means the error rate is 3%</li> <li>* A value of 0xFFFF indicates that the error rate is unknown or unavailable</li> </ul> </li> <li>– For GSM, the error rate reported is Bit Error Rate: <ul style="list-style-type: none"> <li>* Valid values are 0, 100, 200, 300, 400, 500, 600, and 700 The reported value divided by 100 gives the error rate as an RxQual value, e.g., a value of 300 represents an RxQual value of 3.</li> <li>* A value of 25500 indicates No Data</li> </ul> </li> <li>– For WCDMA, the error rate reported is Block Error Rate (BLER): <ul style="list-style-type: none"> <li>* Valid values are 1 to 10000</li> <li>* The reported value divided by 100 provides the error rate in percentages, e.g., a value of 300 represents a BLER of 3%.</li> <li>* A value of 0 indicates No Data</li> </ul> </li> </ul> </li> </ul>
<i>radioIf</i>	<ul style="list-style-type: none"> <li>• Radio interface technology of the signal being measured <ul style="list-style-type: none"> <li>– 0x00 - RADIO_IF_NO_SVC - None (no service)</li> <li>– 0x01 - RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - RADIO_IF_CDMA_1xEVDO - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 - RADIO_IF_AMPS - AMPS</li> <li>– 0x04 - RADIO_IF_GSM - GSM</li> <li>– 0x05 - RADIO_IF_UMTS - UMTS</li> </ul> </li> </ul>

## 8.168.2 Field Documentation

8.168.2.1 **USHORT** `errorRateListElement::errorRate`

8.168.2.2 **BYTE** `errorRateListElement::radioIlf`

## 8.169 eTWSPLMNInfoTlv Struct Reference

### Data Fields

- `uint8_t` [TlvPresent](#)
- `sMSEtwsPlmnInfo` [ETWSPLMNInfo](#)

### 8.169.1 Detailed Description

#### Parameters

<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Boolean indicating the presence of the TLV in the QMI response</li> </ul>
<i>ETWSPLMNInfo</i>	<ul style="list-style-type: none"> <li>• ETWS PLMN Information</li> <li>• See <a href="#">sMSEtwsPlmnInfo</a> for more information</li> </ul>

## 8.169.2 Field Documentation

8.169.2.1 `sMSEtwsPlmnInfo` `eTWSPLMNInfoTlv::ETWSPLMNInfo`

8.169.2.2 `uint8_t` `eTWSPLMNInfoTlv::TlvPresent`

## 8.170 extDispRecInfo Struct Reference

### Data Fields

- `BYTE` `dispType`
- `BYTE` `extDispInfoLen`
- `BYTE` `extDispInfo` [255]

### 8.170.1 Detailed Description

This structure contains Line Control Information



## Parameters

<i>dispType</i>	<ul style="list-style-type: none"> <li>Values are per [S1, Table 3.7.5.16-1].</li> </ul>
<i>extDispInfoLen</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements: <ul style="list-style-type: none"> <li>ext_display_info</li> </ul> </li> </ul>
<i>extDispInfo</i>	<ul style="list-style-type: none"> <li>Extended display information buffer containing the display record; refer to [S1, Section 3.7.5.16] for the format information of the buffer contents.</li> </ul>

## 8.170.2 Field Documentation

8.170.2.1 BYTE extDispRecInfo::dispType

8.170.2.2 BYTE extDispRecInfo::extDispInfo[255]

8.170.2.3 BYTE extDispRecInfo::extDispInfoLen

## 8.171 FactorySequenceNumber Struct Reference

## Data Fields

- BYTE FSNumber [255]

## 8.171.1 Detailed Description

This structure used to store Factory Sequence Number parameter

## Parameters

<i>FSNumber[OUT]</i>	<ul style="list-style-type: none"> <li>Facorty Sequence Number</li> <li>Maximum Length is 255 Bytes</li> </ul>
----------------------	--

## 8.171.2 Field Documentation

8.171.2.1 BYTE FactorySequenceNumber::FSNumber[255]

## 8.172 fileAttributes Struct Reference

## Data Fields

- WORD fileSize
- WORD fileID
- BYTE fileType

- WORD recordSize
- WORD recordCount
- BYTE secRead
- WORD secReadMask
- BYTE secWrite
- WORD secWriteMask
- BYTE secIncrease
- WORD secIncreaseMask
- BYTE secDeactivate
- WORD secDeactivateMask
- BYTE secActivate
- WORD secActivateMask
- WORD rawLen
- BYTE rawValue [255]

### 8.172.1 Detailed Description

This structure contains the information about the File Attributes.

## Parameters

<i>fileSize</i>	<ul style="list-style-type: none"><li>• Indicates the size of the file.</li></ul>
<i>fileID</i>	<ul style="list-style-type: none"><li>• Indicates the ID of the file.</li></ul>
<i>fileType</i>	<ul style="list-style-type: none"><li>• Indicates the type of the file.<ul style="list-style-type: none"><li>– 0 - Transparent</li><li>– 1 - Cyclic</li><li>– 2 - Linear fixed</li><li>– 3 - Dedicated file</li><li>– 4 - Master file</li></ul></li></ul>
<i>recordSize</i>	<ul style="list-style-type: none"><li>• Indicates the size of the records.</li><li>• Only for cyclic and linear fixed files</li></ul>
<i>recordCount</i>	<ul style="list-style-type: none"><li>• Indicates the total no. of the records.</li><li>• Only for linear fixed files</li></ul>
<i>secRead</i>	<ul style="list-style-type: none"><li>• Read security attributes.<ul style="list-style-type: none"><li>– 0 - Always</li><li>– 1 - Never</li><li>– 2 - AND condition</li><li>– 3 - OR condition</li><li>– 4 - Single condition</li></ul></li></ul>
<i>secReadMask</i>	<ul style="list-style-type: none"><li>• Mask with read security attributes.</li><li>• This field is valid only when required by security attributes.<ul style="list-style-type: none"><li>– Bit 0 - PIN1</li><li>– Bit 1 - PIN2</li><li>– Bit 2 - UPIN</li><li>– Bit 3 - ADM</li></ul></li></ul>

<i>secWrite</i>	<ul style="list-style-type: none"> <li>• Write security attributes. <ul style="list-style-type: none"> <li>– 0 - Always</li> <li>– 1 - Never</li> <li>– 2 - AND condition</li> <li>– 3 - OR condition</li> <li>– 4 - Single condition</li> </ul> </li> </ul>
<i>secWriteMask</i>	<ul style="list-style-type: none"> <li>• Mask with write security attributes.</li> <li>• This field is valid only when required by security attributes. <ul style="list-style-type: none"> <li>– Bit 0 - PIN1</li> <li>– Bit 1 - PIN2</li> <li>– Bit 2 - UPIN</li> <li>– Bit 3 - ADM</li> </ul> </li> </ul>
<i>secIncrease</i>	<ul style="list-style-type: none"> <li>• Increase security attributes. <ul style="list-style-type: none"> <li>– 0 - Always</li> <li>– 1 - Never</li> <li>– 2 - AND condition</li> <li>– 3 - OR condition</li> <li>– 4 - Single condition</li> </ul> </li> </ul>
<i>secIncrease-Mask</i>	<ul style="list-style-type: none"> <li>• Mask with increase security attributes.</li> <li>• This field is valid only when required by security attributes. <ul style="list-style-type: none"> <li>– Bit 0 - PIN1</li> <li>– Bit 1 - PIN2</li> <li>– Bit 2 - UPIN</li> <li>– Bit 3 - ADM</li> </ul> </li> </ul>

<i>secDeactivate</i>	<ul style="list-style-type: none"><li>• Deactivate security attributes.<ul style="list-style-type: none"><li>– 0 - Always</li><li>– 1 - Never</li><li>– 2 - AND condition</li><li>– 3 - OR condition</li><li>– 4 - Single condition</li></ul></li></ul>
<i>secDeactivateMask</i>	<ul style="list-style-type: none"><li>• Mask with deactivate security attributes.</li><li>• This field is valid only when required by security attributes.<ul style="list-style-type: none"><li>– Bit 0 - PIN1</li><li>– Bit 1 - PIN2</li><li>– Bit 2 - UPIN</li><li>– Bit 3 - ADM</li></ul></li></ul>
<i>secActivate</i>	<ul style="list-style-type: none"><li>• Activate security attributes.<ul style="list-style-type: none"><li>– 0 - Always</li><li>– 1 - Never</li><li>– 2 - AND condition</li><li>– 3 - OR condition</li><li>– 4 - Single condition</li></ul></li></ul>
<i>secActivateMask</i>	<ul style="list-style-type: none"><li>• Mask with activate security attributes.</li><li>• This field is valid only when required by security attributes.<ul style="list-style-type: none"><li>– Bit 0 - PIN1</li><li>– Bit 1 - PIN2</li><li>– Bit 2 - UPIN</li><li>– Bit 3 - ADM</li></ul></li></ul>

<i>rawLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. raw value.</li> </ul>
<i>rawValue</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>Raw value of file attributes.</li> </ul>

### 8.172.2 Field Documentation

8.172.2.1 WORD fileAttributes::fileID

8.172.2.2 WORD fileAttributes::fileSize

8.172.2.3 BYTE fileAttributes::fileType

8.172.2.4 WORD fileAttributes::rawLen

8.172.2.5 BYTE fileAttributes::rawValue[255]

8.172.2.6 WORD fileAttributes::recordCount

8.172.2.7 WORD fileAttributes::recordSize

8.172.2.8 BYTE fileAttributes::secActivate

8.172.2.9 WORD fileAttributes::secActivateMask

8.172.2.10 BYTE fileAttributes::secDeactivate

8.172.2.11 WORD fileAttributes::secDeactivateMask

8.172.2.12 BYTE fileAttributes::secIncrease

8.172.2.13 WORD fileAttributes::secIncreaseMask

8.172.2.14 BYTE fileAttributes::secRead

8.172.2.15 WORD fileAttributes::secReadMask

8.172.2.16 BYTE fileAttributes::secWrite

8.172.2.17 WORD fileAttributes::secWriteMask

## 8.173 fileInfo Struct Reference

### Data Fields

- WORD fileID
- BYTE pathLen
- WORD path [255]

### 8.173.1 Detailed Description

This structure contains paramaters for file Information

## Parameters

<i>fileID</i>	<ul style="list-style-type: none"><li>• This is Identifier to SIM files; e.g. in UIM "6F07" is Identifier of IMSI File</li></ul>
<i>pathLen</i>	<ul style="list-style-type: none"><li>• Length of file Path</li></ul>
<i>path</i>	<ul style="list-style-type: none"><li>• Path value. This value must be the complete path of the file, which is a sequence block of 2 bytes (e.g., 0x3F00 0x7FFF).</li></ul>

## 8.173.2 Field Documentation

8.173.2.1 WORD fileInfo::fileID

8.173.2.2 WORD fileInfo::path[255]

8.173.2.3 BYTE fileInfo::pathLen

## 8.174 FirmwareUpdatStat Struct Reference

### Data Fields

- [ULONG ResCode](#)
- [BYTE \\* pImgType](#)
- [ULONG \\* pRefData](#)
- [BYTE \\* pRefStringLen](#)
- [BYTE \\* pRefString](#)
- [BYTE \\* pLogStringLen](#)
- [BYTE \\* pLogString](#)

### 8.174.1 Detailed Description

This structure is used to store Firmware Update Status



## Parameters

<i>ResCode</i> [OUT]	<ul style="list-style-type: none"> <li>FW Update Result Code</li> <li>Values: <ul style="list-style-type: none"> <li>0x00000001 - Successful</li> <li>0xFFFFFFFF - Unknown (due to power off reset after firmware update )</li> <li>0x100000nn - File update errors while nn will be the exact error number: <ul style="list-style-type: none"> <li>* 00 - General error</li> </ul> </li> <li>0x200000nn - NVUP update errors while nn will be the exact error number: <ul style="list-style-type: none"> <li>* 00 - General error</li> </ul> </li> <li>0x40000nnn - FOTA update agent errors while nnn will be the exact error number: <ul style="list-style-type: none"> <li>* 000 ~ 0FF - Insignia defined error code</li> <li>* 100 ~ 1FF - Sierra defined error code</li> <li>* See qaGobiApiTableFwDldErrorCodes.h for more detailed information</li> </ul> </li> <li>0x800000nn - FDT/SSDP reported errors while nn will be the exact error number <ul style="list-style-type: none"> <li>* See qaGobiApiTableFwDldErrorCodes.h for more detailed information</li> </ul> </li> </ul> </li> </ul>
<i>plmgType</i> [OUT]	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Firmware image type that failed the update</li> </ul>
<i>pRefData</i> [OUT]	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Failed image reference data</li> <li>This is normally the offset of the image that caused the failure</li> </ul>
<i>pRefStringLen</i> [I-N/OUT]	<ul style="list-style-type: none"> <li>Length of Reference String parameter to follow</li> <li>As input parameter specifies length assigned to pRefString parameter</li> <li>As output parameter specifies length of actual value retrieved from the device</li> </ul>
<i>pRefString</i> [OUT]	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Failed image reference string. This is normally the partition name of the image that caused the failure if applicable.</li> </ul>

<i>pLogStringLen</i> [I- N/OUT]	<ul style="list-style-type: none"> <li>• Length of Reference String parameter to follow</li> <li>• As input parameter specifies length assigned to pRefString parameter</li> <li>• As output parameter specifies length of actual value retrieved from the device</li> </ul>
<i>pLogString</i> [OUT]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Failed image reference string. This is normally the partition name of the image that caused the failure if applicable.</li> </ul>

### 8.174.2 Field Documentation

8.174.2.1 **BYTE\*** FirmwareUpdatStat::plmgType

8.174.2.2 **BYTE\*** FirmwareUpdatStat::pLogString

8.174.2.3 **BYTE\*** FirmwareUpdatStat::pLogStringLen

8.174.2.4 **ULONG\*** FirmwareUpdatStat::pRefData

8.174.2.5 **BYTE\*** FirmwareUpdatStat::pRefString

8.174.2.6 **BYTE\*** FirmwareUpdatStat::pRefStringLen

8.174.2.7 **ULONG** FirmwareUpdatStat::ResCode

## 8.175 FMSImageElement Struct Reference

### Data Fields

- uint8\_t [imageType](#)
- uint8\_t [imageId](#) [16]
- uint8\_t [buildIdLength](#)
- uint8\_t [buildId](#) [100]

### 8.175.1 Detailed Description

This structure contains the Image Element information

#### Parameters

<i>imageType</i>	<ul style="list-style-type: none"> <li>• Type of image 0 - Modem 1 - PRI</li> </ul>
<i>imageId</i>	<ul style="list-style-type: none"> <li>• Unique image identifier</li> </ul>

<i>buildIdLength</i>	<ul style="list-style-type: none"> <li>Length of the build ID string (may be zero)</li> </ul>
<i>pBuildId</i>	<ul style="list-style-type: none"> <li>Build ID ANSI string with length provided by the previous field</li> </ul>

## 8.175.2 Field Documentation

8.175.2.1 `uint8_t FMSImageElement::buildId[100]`

8.175.2.2 `uint8_t FMSImageElement::buildIdLength`

8.175.2.3 `uint8_t FMSImageElement::imageId[16]`

8.175.2.4 `uint8_t FMSImageElement::imageType`

## 8.176 FMSImageIdElement Struct Reference

### Data Fields

- `uint8_t` [storageIndex](#)
- `uint8_t` [failureCount](#)
- `uint8_t` [imageID](#) [16]
- `uint8_t` [buildIDLength](#)
- `uint8_t` [buildID](#) [100]

### 8.176.1 Detailed Description

This structure contains the Image ID list element Information

#### Parameters

<i>storageIndex</i>	<ul style="list-style-type: none"> <li>Index in storage where the image is located(a value of 0xFF indicates that the storage for this type of image is not relevant)</li> </ul>
<i>failureCount</i>	<ul style="list-style-type: none"> <li>Number of consecutive write attempts to this storage index that have failed(a value of 0xFF indicates unspecified)</li> </ul>
<i>imageID</i>	<ul style="list-style-type: none"> <li>Image unique identifier(max 16 chars.)</li> </ul>
<i>buildIDLength</i>	<ul style="list-style-type: none"> <li>Length of the build ID string. If there is no build ID, this field will be 0 and no data will follow.</li> </ul>

<i>buildID</i>	<ul style="list-style-type: none"> <li>String containing image build information( Max 100 characters )</li> </ul>
----------------	---

## 8.176.2 Field Documentation

8.176.2.1 `uint8_t FMSImageIDElement::buildID[100]`

8.176.2.2 `uint8_t FMSImageIDElement::buildIDLength`

8.176.2.3 `uint8_t FMSImageIDElement::failureCount`

8.176.2.4 `uint8_t FMSImageIDElement::imageID[16]`

8.176.2.5 `uint8_t FMSImageIDElement::storageIndex`

## 8.177 FMSImageIDEntries Struct Reference

### Data Fields

- `uint8_t imageType`
- `uint8_t maxImages`
- `uint8_t executingImage`
- `uint8_t imageIDSize`
- `FMSImageIDElement imageIDElement` [50]

### 8.177.1 Detailed Description

This structure contains the list entry Information

#### Parameters

<i>imageType</i>	<ul style="list-style-type: none"> <li>Type of image <ul style="list-style-type: none"> <li>0 - Modem</li> <li>1 - PRI</li> </ul> </li> </ul>
<i>maxImages</i>	<ul style="list-style-type: none"> <li>Maximum number of images of this type that may be stored concurrently on the device</li> </ul>
<i>executingImage</i>	<ul style="list-style-type: none"> <li>Index (into the next array) of image that is currently executing</li> </ul>
<i>imageIDSize</i>	<ul style="list-style-type: none"> <li>The number of elements in the image ID list</li> </ul>
<i>imageIDElement</i>	<ul style="list-style-type: none"> <li>Array of ImageIDElement Structure ( Max 50 elements )</li> <li>See <a href="#">FMSImageIDElement</a></li> </ul>

### 8.177.2 Field Documentation

8.177.2.1 `uint8_t` FMSImageIDEntries::executingImage

8.177.2.2 `FMSImageIDElement` FMSImageIDEntries::imageIDElement[50]

8.177.2.3 `uint8_t` FMSImageIDEntries::imageIDSize

8.177.2.4 `uint8_t` FMSImageIDEntries::imageType

8.177.2.5 `uint8_t` FMSImageIDEntries::maxImages

## 8.178 FMSImageList Struct Reference

### Data Fields

- `uint8_t` [listSize](#)
- [FMSImageIDEntries](#) [imageIDEntries](#) [2]

### 8.178.1 Detailed Description

This structure contains the Get Stored Images List

#### Parameters

<i>listSize</i>	<ul style="list-style-type: none"> <li>• The number of elements in the image list</li> </ul>
<i>imageIDEntries</i>	<ul style="list-style-type: none"> <li>• Array of <a href="#">ImageIDEntries</a> Structure ( Max 2 entries )</li> </ul>

### 8.178.2 Field Documentation

8.178.2.1 `FMSImageIDEntries` FMSImageList::imageIDEntries[2]

8.178.2.2 `uint8_t` FMSImageList::listSize

## 8.179 FMSPrefImageList Struct Reference

### Data Fields

- `uint8_t` [listSize](#)
- [FMSImageElement](#) [listEntries](#) [2]

### 8.179.1 Detailed Description

This structure contains the Preference Image List information

## Parameters

<i>listSize</i>	<ul style="list-style-type: none"> <li>The number of elements in the image list</li> </ul>
<i>pListEntries</i>	<ul style="list-style-type: none"> <li>Array of Image entries with size provided by previous field</li> <li>See <a href="#">FMSImageElement</a></li> </ul>

## 8.179.2 Field Documentation

## 8.179.2.1 FMSImageElement FMSPrefImageList::listEntries[2]

## 8.179.2.2 uint8\_t FMSPrefImageList::listSize

## 8.180 fwinfo\_s Struct Reference

## Data Fields

- [ULONG FirmwareID](#)
- [ULONG Technology](#)
- [ULONG Carrier](#)
- [ULONG Region](#)
- [ULONG GPSCapability](#)

## 8.180.1 Detailed Description

Gobi firmware image info structure

## Parameters

<i>FirmwareID</i>	<ul style="list-style-type: none"> <li>Firmware ID obtained from the firmware image</li> </ul>
<i>Technology</i>	<ul style="list-style-type: none"> <li>Technology (0xFFFFFFFF if unknown)</li> </ul>
<i>Carrier</i>	<ul style="list-style-type: none"> <li>Carrier (0xFFFFFFFF if unknown)</li> </ul>
<i>Region</i>	<ul style="list-style-type: none"> <li>Region (0xFFFFFFFF if unknown)</li> </ul>
<i>GPSCapability</i>	<ul style="list-style-type: none"> <li>GPS capability (0xFFFFFFFF if unknown)</li> </ul>

## 8.180.2 Field Documentation

## 8.180.2.1 ULONG fwinfo\_s::Carrier

8.180.2.2 `ULONG` `fwinfo_s::FirmwareID`8.180.2.3 `ULONG` `fwinfo_s::GPSCapability`8.180.2.4 `ULONG` `fwinfo_s::Region`8.180.2.5 `ULONG` `fwinfo_s::Technology`

## 8.181 GERANInfo Struct Reference

### Data Fields

- `ULONG` `cellID`
- `BYTE` `plmn` [3]
- `WORD` `lac`
- `WORD` `arfcn`
- `BYTE` `bsic`
- `ULONG` `timingAdvance`
- `WORD` `rxLev`
- `BYTE` `nmlnst`
- `nmlnst` `insNmlnst` [255]

### 8.181.1 Detailed Description

This structure contains information about the GERAN Network.

#### Parameters

<i>cellID</i>	<ul style="list-style-type: none"> <li>• Cell ID.</li> <li>• 0xFFFFFFFF indicates cell ID information is not present.</li> </ul>
<i>plmn</i> [ <i>PLMN_LENGTH</i> ]	<ul style="list-style-type: none"> <li>• MCC/MNC information coded as octet 3, 4, and 5.</li> <li>• This field is ignored when <code>nmlnst</code> is not present.</li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• This field is ignored when <code>nmlnst</code> is not present. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>arfcn</i>	<ul style="list-style-type: none"> <li>• Absolute RF channel number. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>

<i>bsic</i>	<ul style="list-style-type: none"> <li>• Base station identity code. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>timingAdvance</i>	<ul style="list-style-type: none"> <li>• Measured delay (in bit periods; 1 bit period = 48/13 microsecond) of access burst transmission on RACH or PRACH to the expected signal from an MS at zero distance under static channel conditions. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>rxLev</i>	<ul style="list-style-type: none"> <li>• Serving Cell Rx measurement.</li> <li>• Values range between 0 and 63.</li> <li>• Mapped to a measured signal level: <ul style="list-style-type: none"> <li>– Rxlev 0 is a signal strength less than -110 dBm</li> <li>– Rxlev 1 is -110 dBm to -109 dBm</li> <li>– Rxlev 2 is -109 dBm to -108 dBm</li> <li>– ...</li> <li>– Rxlev 62 is -49 dBm to -48 dBm</li> <li>– Rxlev 63 is greater than -48 dBm</li> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>nmrInst</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of instances which follow.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>insNmrCellInfo[ MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nmrCellInfo</a> for more information.</li> </ul>

## 8.181.2 Field Documentation

8.181.2.1 WORD GERANInfo::arfcn

8.181.2.2 BYTE GERANInfo::bsic

8.181.2.3 ULONG GERANInfo::cellID

8.181.2.4 nmrCellInfo GERANInfo::insNmrCellInfo[255]

8.181.2.5 WORD GERANInfo::lac

8.181.2.6 BYTE GERANInfo::nmrInst

8.181.2.7 BYTE GERANInfo::plmn[3]



8.181.2.8 WORD GERANInfo::rxLev

8.181.2.9 ULONG GERANInfo::timingAdvance

## 8.182 geranInstInfo Struct Reference

### Data Fields

- [WORD geranArfcn](#)
- [BYTE geranBsicNcc](#)
- [BYTE geranBsicBcc](#)
- [SHORT geranRssi](#)

### 8.182.1 Detailed Description

This structure contains information about the GERAN Instances in UMTS Network.

#### Parameters

<i>geranArfcn</i>	<ul style="list-style-type: none"> <li>• Absolute RF channel number.</li> </ul>
<i>geranBsicNcc</i>	<ul style="list-style-type: none"> <li>• Base station identity code network color code.</li> <li>• 0xFF indicates information is not present.</li> </ul>
<i>geranBsicBcc</i>	<ul style="list-style-type: none"> <li>• Base station identity code base station color code.</li> <li>• 0xFF indicates information is not present.</li> </ul>
<i>geranRssi</i>	<ul style="list-style-type: none"> <li>• Received signal strength indicator.</li> </ul>

### 8.182.2 Field Documentation

8.182.2.1 WORD geranInstInfo::geranArfcn

8.182.2.2 BYTE geranInstInfo::geranBsicBcc

8.182.2.3 BYTE geranInstInfo::geranBsicNcc

8.182.2.4 SHORT geranInstInfo::geranRssi

## 8.183 getAllCallInformation Struct Reference

### Data Fields

- [callInfo Callinfo](#)
- [BYTE isEmpty](#)
- [BYTE ALS](#)

### 8.183.1 Detailed Description

This structure contains information related to call state change.

## Parameters

<i>CallInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">callInfo</a> for more information.</li> </ul>
<i>isEmpty</i>	<ul style="list-style-type: none"> <li>• Multiparty indicator. <ul style="list-style-type: none"> <li>– 0x00 - False</li> <li>– 0x01 - True</li> </ul> </li> </ul>
<i>ALS</i>	<ul style="list-style-type: none"> <li>• Alternate Line Service line indicator.</li> <li>• Feature for supporting two different phone numbers on the same mobile device. <ul style="list-style-type: none"> <li>– 0x00 - ALS_LINE1 - Line 1 (default)</li> <li>– 0x01 - ALS_LINE2 - Line 2</li> </ul> </li> </ul>

## 8.183.2 Field Documentation

8.183.2.1 BYTE getAllCallInformation::ALS

8.183.2.2 callInfo getAllCallInformation::CallInfo

8.183.2.3 BYTE getAllCallInformation::isEmpty

## 8.184 getAllCallRmtPtyName Struct Reference

## Data Fields

- [BYTE callID](#)
- [remotePartyName RemotePartyName](#)

## 8.184.1 Detailed Description

This structure contains information for All Call Remote Party Names

## Parameters

<i>callID</i>	<ul style="list-style-type: none"> <li>• Unique call identifier for the call.</li> </ul>
<i>RemoteParty-Name</i>	<ul style="list-style-type: none"> <li>• See <a href="#">remotePartyName</a> for more information.</li> </ul>

## 8.184.2 Field Documentation

8.184.2.1 BYTE getAllCallRmtPtyName::callID

8.184.2.2 `remotePartyName` `getAllCallRmtPtyName::RemotePartyName`

## 8.185 `getAllCallRmtPtyNum` Struct Reference

### Data Fields

- [BYTE](#) `callID`
- [remotePartyNum](#) `RemotePartyNum`

### 8.185.1 Detailed Description

This structure contains information for All Call Remote Party Numbers

#### Parameters

<i>callID</i>	<ul style="list-style-type: none"><li>• Unique call identifier for the call.</li></ul>
<i>RemoteParty-Num</i>	<ul style="list-style-type: none"><li>• See <a href="#">remotePartyNum</a> for more information.</li></ul>

### 8.185.2 Field Documentation

8.185.2.1 `BYTE` `getAllCallRmtPtyNum::callID`

8.185.2.2 `remotePartyNum` `getAllCallRmtPtyNum::RemotePartyNum`

## 8.186 `GetAudioPathConfigReq` Struct Reference

### Data Fields

- [BYTE](#) `Profile`
- [BYTE](#) `Item`

### 8.186.1 Detailed Description

This structure contains the SLQSGetAudioPathConfig request parameters

## Parameters

<i>Profile</i>	<ul style="list-style-type: none"> <li>• Audio Profile <ul style="list-style-type: none"> <li>– 0-9</li> </ul> </li> </ul>
<i>Item</i>	<ul style="list-style-type: none"> <li>• Item <ul style="list-style-type: none"> <li>– 0 - AV_EC</li> <li>– 1 - AV_NS</li> <li>– 2 - AV_TXVOL</li> <li>– 3 - AV_DTMFTXG</li> <li>– 4 - AV_CODECSTG</li> <li>– 5 - AV_TXPCMIIRFLTR</li> <li>– 6 - AV_RXPCMIIRFLTR</li> <li>– 7 - AV_MICGAIN</li> <li>– 8 - AV_RXAGC</li> <li>– 9 - AV_TXAGC</li> <li>– 10 - AV_RXAGCLIST</li> <li>– 11 - AV_RXAVCLIST</li> <li>– 12 - AV_TXAGCLIST</li> </ul> </li> </ul>

## 8.186.2 Field Documentation

8.186.2.1 BYTE GetAudioPathConfigReq::Item

8.186.2.2 BYTE GetAudioPathConfigReq::Profile

## 8.187 GetAudioPathConfigResp Struct Reference

## Data Fields

- [BYTE \\* pECMode](#)
- [BYTE \\* pNSEnable](#)
- [WORD \\* pTXGain](#)
- [WORD \\* pDTMFTXGain](#)
- [WORD \\* pCodecSTGain](#)
- [TXPCMIIRFiltr \\* pTXPCMIIRFiltr](#)
- [RXPCMIIRFiltr \\* pRXPCMIIRFiltr](#)
- [BYTE \\* pMICGainSelect](#)
- [BYTE \\* pRXAVCAGCSwitch](#)
- [BYTE \\* pTXAVCSwitch](#)
- [RXAGCList \\* pRXAGCList](#)
- [RXAVCList \\* pRXAVCList](#)
- [TXAGCList \\* pTXAGCList](#)

### 8.187.1 Detailed Description

This structure contains the SLQSGetAudioPathConfig response parameters.

## Parameters

<i>pECMode</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_EC             <ul style="list-style-type: none"> <li>– 0 - Echo cancellation off</li> <li>– 1 - Handset mode</li> <li>– 2 - Headset mode</li> <li>– 3 - Car kit mode</li> <li>– 4 - Speaker Mode</li> </ul> </li> </ul>
<i>pNSEnable</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_NS             <ul style="list-style-type: none"> <li>– 0 - Noise suppression off</li> <li>– 1 - Noise suppression on</li> </ul> </li> </ul>
<i>pTXGain</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_TXVOL             <ul style="list-style-type: none"> <li>– 0x0000 - 0xffff</li> </ul> </li> </ul>
<i>pDTMFTXGain</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_DTMFTXG             <ul style="list-style-type: none"> <li>– 0x0000 - 0xffff</li> </ul> </li> </ul>
<i>pCodecSTGain</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_CODECASTG             <ul style="list-style-type: none"> <li>– 0x0000 - 0xffff</li> </ul> </li> </ul>
<i>pTXPCMIIRFiltr</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">TXPCMIIRFiltr</a> for more information</li> </ul>
<i>pRXPCMIIRFiltr</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">RXPCMIIRFiltr</a> for more information</li> </ul>
<i>pMICGainSelect</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_MICGAIN</li> </ul>
<i>pRXAVCAGC-Switch</i>	[Optional] <ul style="list-style-type: none"> <li>• RX AVC/AGC Switch</li> </ul>

<i>pTXAVCSwitch</i>	[Optional] <ul style="list-style-type: none"> <li>• TX AVC Switch</li> </ul>
<i>pRXAGCList</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">RXAGCList</a> for more information</li> </ul>
<i>pRXAVCList</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">RXAVCList</a> for more information</li> </ul>
<i>pTXAGCList</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">TXAGCList</a> for more information</li> </ul>

## 8.187.2 Field Documentation

- 8.187.2.1 **WORD\*** `GetAudioPathConfigResp::pCodecSTGain`
- 8.187.2.2 **WORD\*** `GetAudioPathConfigResp::pDTMFTXGain`
- 8.187.2.3 **BYTE\*** `GetAudioPathConfigResp::pECMode`
- 8.187.2.4 **BYTE\*** `GetAudioPathConfigResp::pMICGainSelect`
- 8.187.2.5 **BYTE\*** `GetAudioPathConfigResp::pNSEnable`
- 8.187.2.6 **RXAGCList\*** `GetAudioPathConfigResp::pRXAGCList`
- 8.187.2.7 **BYTE\*** `GetAudioPathConfigResp::pRXAVCAGCSwitch`
- 8.187.2.8 **RXAVCList\*** `GetAudioPathConfigResp::pRXAVCList`
- 8.187.2.9 **RXPCMIIRFitr\*** `GetAudioPathConfigResp::pRXPCMIIRFitr`
- 8.187.2.10 **TXAGCList\*** `GetAudioPathConfigResp::pTXAGCList`
- 8.187.2.11 **BYTE\*** `GetAudioPathConfigResp::pTXAVCSwitch`
- 8.187.2.12 **WORD\*** `GetAudioPathConfigResp::pTXGain`
- 8.187.2.13 **TXPCMIIRFitr\*** `GetAudioPathConfigResp::pTXPCMIIRFitr`

## 8.188 GetAudioProfileReq Struct Reference

### Data Fields

- [BYTE Generator](#)

### 8.188.1 Detailed Description

This structure contains the SLQSGetAudioProfile request parameters



## Parameters

<i>Generator</i>	<ul style="list-style-type: none"><li>• Audio Generator<ul style="list-style-type: none"><li>– 0 - Voice</li><li>– 1 - Key Beep</li><li>– 2 - MIDI</li></ul></li></ul>
------------------	--

## 8.188.2 Field Documentation

8.188.2.1 BYTE GetAudioProfileReq::Generator

## 8.189 GetAudioProfileResp Struct Reference

## Data Fields

- [BYTE Profile](#)
- [BYTE EarMute](#)
- [BYTE MicMute](#)
- [BYTE Volume](#)

## 8.189.1 Detailed Description

This structure contains the SLQSGetAudioProfile response parameters.

## Parameters

<i>Profile</i>	<ul style="list-style-type: none"> <li>• Audio Profile <ul style="list-style-type: none"> <li>– 0 - Handset</li> <li>– 1 - Headset</li> <li>– 2 - Car Kit</li> <li>– 3 - Speaker phone</li> <li>– 4 - Auxiliary</li> <li>– 5 - TTY</li> <li>– 6 - Auxiliary external PCM</li> <li>– 7 - Primary external PCM</li> <li>– 8 - External slave PCM</li> <li>– 9 - I2S</li> </ul> </li> </ul>
<i>EarMute</i>	<ul style="list-style-type: none"> <li>• Ear Mute Setting <ul style="list-style-type: none"> <li>– 0 - unmuted</li> <li>– 1 - muted</li> </ul> </li> </ul>
<i>MicMute</i>	<ul style="list-style-type: none"> <li>• MIC Mute Setting <ul style="list-style-type: none"> <li>– 0 - unmuted</li> <li>– 1 - muted</li> </ul> </li> </ul>
<i>Volume</i>	<ul style="list-style-type: none"> <li>• Audio Volume Level <ul style="list-style-type: none"> <li>– 0 to 7</li> </ul> </li> </ul>

## 8.189.2 Field Documentation

8.189.2.1 BYTE GetAudioProfileResp::EarMute

8.189.2.2 BYTE GetAudioProfileResp::MicMute

8.189.2.3 BYTE GetAudioProfileResp::Profile

8.189.2.4 BYTE GetAudioProfileResp::Volume

## 8.190 GetAudioVoTLBConfigReq Struct Reference

## Data Fields

- [BYTE Profile](#)
- [BYTE Generator](#)

- [BYTE Volume](#)
- [BYTE Item](#)

### 8.190.1 Detailed Description

This structure contains the SLQSGetAudioVolTLBConfig request parameters

#### Parameters

<i>Profile</i>	<ul style="list-style-type: none"><li>• Audio Profile<ul style="list-style-type: none"><li>– 0-9</li></ul></li></ul>
<i>Generator</i>	<ul style="list-style-type: none"><li>• Audio Generator<ul style="list-style-type: none"><li>– 0-2</li></ul></li></ul>
<i>Volume</i>	<ul style="list-style-type: none"><li>• Audio Volume Level<ul style="list-style-type: none"><li>– 0-7</li></ul></li></ul>
<i>Item</i>	<ul style="list-style-type: none"><li>• Item<ul style="list-style-type: none"><li>– 13 - AV_RXVOLDB</li><li>– 14 - AV_DTMFVOLDB</li><li>– 15 - AV_PAD</li></ul></li></ul>

### 8.190.2 Field Documentation

8.190.2.1 **BYTE** GetAudioVolTLBConfigReq::Generator

8.190.2.2 **BYTE** GetAudioVolTLBConfigReq::Item

8.190.2.3 **BYTE** GetAudioVolTLBConfigReq::Profile

8.190.2.4 **BYTE** GetAudioVolTLBConfigReq::Volume

## 8.191 GetAudioVolTLBConfigResp Struct Reference

#### Data Fields

- [WORD ResCode](#)

### 8.191.1 Detailed Description

This structure contains the SLQSGetAudioVolTLBConfig response parameters.

## Parameters

<i>ResCode</i>	<ul style="list-style-type: none"> <li>• Result of requested item</li> </ul>
----------------	--

## 8.191.2 Field Documentation

## 8.191.2.1 WORD GetAudioVolTLBConfigResp::ResCode

## 8.192 getCallFWExtInfo Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [callFWExtInfo CallFWExtInfo](#) [20]

## 8.192.1 Detailed Description

This structure contains an array of Call Forwarded Extended Information.

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of <a href="#">callFWExtInfo</a> that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>CallFWExtInfo[-MAX_NO_OF_CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of CallFWExtInfo. <ul style="list-style-type: none"> <li>– See <a href="#">CallFWExtInfo</a> for more information.</li> </ul> </li> </ul>

## 8.192.2 Field Documentation

## 8.192.2.1 callFWExtInfo getCallFWExtInfo::CallFWExtInfo[20]

## 8.192.2.2 BYTE getCallFWExtInfo::numInstances

## 8.193 getCallFWInfo Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [callFWInfo CallFWInfo](#) [20]

## 8.193.1 Detailed Description

This structure contains an array of Call Forwarded Information.

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of <a href="#">callFWInfo</a> that follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>CallFWInfo[MAX_NO_OF_CALLS]</i>	<ul style="list-style-type: none"> <li>• Array of <a href="#">callFWInfo</a>. <ul style="list-style-type: none"> <li>– See <a href="#">callFWInfo</a> for more information.</li> </ul> </li> </ul>

## 8.193.2 Field Documentation

8.193.2.1 [callFWInfo](#) getCallFWInfo::CallFWInfo[20]8.193.2.2 **BYTE** getCallFWInfo::numInstances

## 8.194 getCustomFeatureV2 Struct Reference

## Data Fields

- [getCustomInput](#) \* [pGetCustomInput](#)
- [custSettingInfo](#) \* [pCustSettingInfo](#)
- [custSettingList](#) \* [pCustSettingList](#)

## 8.194.1 Detailed Description

This struture contains the TLV required to get the Customization Info and customization list.

## Parameters

<i>IN]</i>	<p><a href="#">pGetCustomInput</a>[IN]</p> <ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• See <a href="#">getCustomInput</a> for more information</li> </ul>
<i>OUT]</i>	<p><a href="#">pCustSettingInfo</a>[OUT]</p> <ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• See <a href="#">custSettingInfo</a> for more information</li> </ul>
<i>OUT]</i>	<p><a href="#">pCustSettingList</a>[OUT]</p> <ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• See <a href="#">custSettingList</a> for more information</li> </ul>

## 8.194.2 Field Documentation

8.194.2.1 [custSettingInfo](#)\* getCustomFeatureV2::pCustSettingInfo

8.194.2.2 `custSettingList*` `getCustomFeatureV2::pCustSettingList`

8.194.2.3 `getCustomInput*` `getCustomFeatureV2::pGetCustomInput`

## 8.195 `getCustomInput` Struct Reference

### Data Fields

- [CHAR](#) `cust_id` [64+1]
- [BYTE](#) `list_type`

### 8.195.1 Detailed Description

This structure contains which customization id or the list type want to retrieve from modem. This TLV is only applicable for 9x30 modules so far

#### Parameters

<i>cust_id</i>	<ul style="list-style-type: none"> <li>• Customization ID (Maximum 64 bytes)</li> </ul>
<i>list_type</i>	<ul style="list-style-type: none"> <li>• list type requested</li> </ul>

### 8.195.2 Field Documentation

8.195.2.1 **CHAR** `getCustomInput::cust_id`[64+1]

8.195.2.2 **BYTE** `getCustomInput::list_type`

## 8.196 `getDUNCallInfoReq` Struct Reference

### Data Fields

- [ULONG](#) `Mask`
- [BYTE](#) \* `pReportConnStatus`
- [TransferStatInd](#) \* `pTransferStatInd`
- [BYTE](#) \* `pReportDormStatus`
- [BYTE](#) \* `pReportDataBearerTech`
- [BYTE](#) \* `pReportChannelRate`

### 8.196.1 Detailed Description

This structure contains the DUN Call Info Request parameters.

## Parameters

<i>Mask</i>	<ul style="list-style-type: none"> <li>• Mandatory parameter</li> <li>• Set the bits corresponding to the information requested to 1</li> <li>• All other bits must be set to 0.</li> <li>• If any values are not available or applicable, the corresponding TLVs are not returned in the response. <ul style="list-style-type: none"> <li>– Bit 0 - Connection Status</li> <li>– Bit 1 - Last call end reason</li> <li>– Bit 2 - Tx/Rx bytes OK</li> <li>– Bit 3 - Dormancy status</li> <li>– Bit 4 - Data bearer</li> <li>– Bit 5 - Channel rate</li> <li>– Bit 6 - Call active duration</li> </ul> </li> </ul>
<i>pReportConn-Status</i>	<ul style="list-style-type: none"> <li>• Connect Status Indicator <ul style="list-style-type: none"> <li>– 0 - Do not report</li> <li>– 1 - Report connection status and call end reason</li> </ul> </li> </ul>
<i>pTransferStatInd</i>	<ul style="list-style-type: none"> <li>• See <a href="#">TransferStatInd</a> for more information</li> </ul>
<i>pReportDorm-Status</i>	<ul style="list-style-type: none"> <li>• Dormancy Status Indicator <ul style="list-style-type: none"> <li>– 0 - Do not report</li> <li>– 1 - Report traffic channel state of interface used for data connection</li> </ul> </li> </ul>
<i>pReportData-BearerTech</i>	<ul style="list-style-type: none"> <li>• Current Data Bearer Technology Indicator <ul style="list-style-type: none"> <li>– 0 - Do not report</li> <li>– 1 - Report radio interface used for data transfer when it changes</li> </ul> </li> </ul>
<i>pReport-ChannelRate</i>	<ul style="list-style-type: none"> <li>• Channel Rate Indicator <ul style="list-style-type: none"> <li>– 0 - Do not report</li> <li>– 1 - Report channel rate</li> </ul> </li> </ul>

## 8.196.2 Field Documentation

- 8.196.2.1 **ULONG** `getDUNCallInfoReq::Mask`
- 8.196.2.2 **BYTE\*** `getDUNCallInfoReq::pReportChannelRate`
- 8.196.2.3 **BYTE\*** `getDUNCallInfoReq::pReportConnStatus`
- 8.196.2.4 **BYTE\*** `getDUNCallInfoReq::pReportDataBearerTech`
- 8.196.2.5 **BYTE\*** `getDUNCallInfoReq::pReportDormStatus`
- 8.196.2.6 **TransferStatInd\*** `getDUNCallInfoReq::pTransferStatInd`

## 8.197 getDUNCallInfoResp Struct Reference

### Data Fields

- [ConnectionStatus](#) \* `pConnectionStatus`
- **WORD** \* `pCallEndReason`
- **ULONGLONG** \* `pTXOKBytesCount`
- **ULONGLONG** \* `pRXOKBytesCount`
- **BYTE** \* `pDormancyStatus`
- **BYTE** \* `pDataBearerTech`
- **ChannelRate** \* `pChannelRate`
- **ULONGLONG** \* `pLastCallTXOKBytesCnt`
- **ULONGLONG** \* `pLastCallRXOKBytesCnt`
- **ULONGLONG** \* `pMdmCallDurationActive`
- **BYTE** \* `pLastCallDataBearerTech`

### 8.197.1 Detailed Description

This structure contains the DUN Call Info response parameters

#### Parameters

<i>pConnection-Status</i>	<ul style="list-style-type: none"> <li>• See <a href="#">ConnectionStatus</a> for more information</li> </ul>
<i>pCallEndReason</i>	<ul style="list-style-type: none"> <li>• Last modem call end reason</li> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason</li> <li>• Only valid if the last call made was DUN, else zero is returned</li> </ul>



<i>pTXOKBytes-Count</i>	<ul style="list-style-type: none"> <li>• Number of bytes transmitted without error</li> <li>• Returned only if a data call is up</li> </ul>
<i>pRXOKBytes-Count</i>	<ul style="list-style-type: none"> <li>• Number of bytes received without error</li> <li>• Returned only if a data call is up</li> </ul>
<i>pDormancy-Status</i>	<ul style="list-style-type: none"> <li>• Current traffic channel status</li> <li>• Returned if a data call is up <ul style="list-style-type: none"> <li>– 0x01 - Traffic channel dormant</li> <li>– 0x02 - Traffic channel active</li> </ul> </li> </ul>
<i>pDataBearer-Tech</i>	<ul style="list-style-type: none"> <li>• Current data bearer technology</li> <li>• Returned only if a data call is up <ul style="list-style-type: none"> <li>– 0x01 - cdma2000 1X</li> <li>– 0x02 - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 - GSM</li> <li>– 0x04 - UMTS</li> <li>– 0x05 - cdma200 HRPD ( 1xEV-DO RevA)</li> <li>– 0x06 - EDGE</li> <li>– 0x07 - HSDPA and WCDMA</li> <li>– 0x08 - WCDMA and HSUPA</li> <li>– 0x09 - HSDPA and HSUPA</li> <li>– 0x0A - LTE</li> <li>– 0x0B - cdma2000 EHRPD</li> <li>– 0x0C - HSDPA+ and WCDMA</li> <li>– 0x0D - HSDPA+ and HSUPA</li> <li>– 0x0E - DC_HSDPA+ and WCDMA</li> <li>– 0x0F - DC_HSDPA+ and HSUPA</li> <li>– 0x10 - HSDPA+ and 64QAM</li> <li>– 0x11 - HSDPA+, 64QAM and HSUPA</li> <li>– 0x12 - TDSCDMA</li> <li>– 0x13 - TDSCDMA and HSDPA</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>

<i>pChannelRate</i>	<ul style="list-style-type: none"> <li>• See <a href="#">ChannelRate</a> for more information</li> </ul>
<i>pLastCallTXOK-BytesCnt</i>	<ul style="list-style-type: none"> <li>• Number of bytes transmitted without error during the last data call ( 0 if no call was made ).</li> <li>• Return only if not in a call and the previous call was made using DUN.</li> </ul>
<i>pLastCallRXOK-BytesCnt</i>	<ul style="list-style-type: none"> <li>• Number of bytes transmitted without error during the last data call ( 0 if no call was made ).</li> <li>• Return only if not in a call and the previous call was made using DUN.</li> </ul>
<i>pMdmCall-DurationActive</i>	<ul style="list-style-type: none"> <li>• Duration that the call is active in milliseconds</li> <li>• If the modem connection status is connected, this represents the active duration of the current DUN call</li> <li>• If the modem connection status is disconnected, this represents the duration of the last DUN call since the device was powered up (0 if no call has been made or if the last call was not DUN)</li> </ul>
<i>pLastCallData-BearerTech</i>	<ul style="list-style-type: none"> <li>• Last Call Data Bearer Technology</li> <li>• Returned only if not in a call and when the previous call was made using DUN <ul style="list-style-type: none"> <li>– 0x01 - cdma2000 1X</li> <li>– 0x02 - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 - GSM</li> <li>– 0x04 - UMTS</li> <li>– 0x05 - cdma200 HRPD (1xEV-DO Rev A)</li> <li>– 0x06 - EDGE</li> <li>– 0x07 - HSDPA and WCDMA</li> <li>– 0x08 - WCDMA and HSUPA</li> <li>– 0x09 - HSDPA and HSUPA</li> <li>– 0x0A - LTE</li> <li>– 0x0B - cdma2000 EHRPD</li> <li>– 0x0C - HSDPA+ and WCDMA</li> <li>– 0x0D - HSDPA+ and HSUPA</li> <li>– 0x0E - DC_HSDPA+ and WCDMA</li> <li>– 0x0F - DC_HSDPA+ and HSUPA</li> <li>– 0x10 - HSDPA+ and 64QAM</li> <li>– 0x11 - HSDPA+, 64QAM and HSUPA</li> <li>– 0x12 - TDSCDMA</li> <li>– 0x13 - TDSCDMA and HSDPA</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>

### 8.197.2 Field Documentation

- 8.197.2.1 **WORD\*** `getDUNCallInfoResp::pCallEndReason`
- 8.197.2.2 **ChannelRate\*** `getDUNCallInfoResp::pChannelRate`
- 8.197.2.3 **ConnectionStatus\*** `getDUNCallInfoResp::pConnectionStatus`
- 8.197.2.4 **BYTE\*** `getDUNCallInfoResp::pDataBearerTech`
- 8.197.2.5 **BYTE\*** `getDUNCallInfoResp::pDormancyStatus`
- 8.197.2.6 **BYTE\*** `getDUNCallInfoResp::pLastCallDataBearerTech`
- 8.197.2.7 **ULONGLONG\*** `getDUNCallInfoResp::pLastCallRXOKBytesCnt`
- 8.197.2.8 **ULONGLONG\*** `getDUNCallInfoResp::pLastCallTXOKBytesCnt`
- 8.197.2.9 **ULONGLONG\*** `getDUNCallInfoResp::pMdmCallDurationActive`
- 8.197.2.10 **ULONGLONG\*** `getDUNCallInfoResp::pRXOKBytesCount`
- 8.197.2.11 **ULONGLONG\*** `getDUNCallInfoResp::pTXOKBytesCount`

## 8.198 getDyingGaspCfg Struct Reference

### Data Fields

- **BYTE \*** `pDestSMSNum`
- **BYTE \*** `pDestSMSContent`

### 8.198.1 Detailed Description

This structure contains the TLV required to get the Dying GASP Config.

#### Parameters

<i>OUT</i>	<p><code>pDestSMSNum[OUT]</code></p> <ul style="list-style-type: none"> <li>• SMS Destination Number as string of 8 bit ASCII Characters Max 20 chars.</li> <li>• Optional parameter.</li> </ul>
<i>OUT</i>	<p><code>pDestSMSContent[OUT]</code></p> <ul style="list-style-type: none"> <li>• SMS Content as a string of 8 bit ASCII text characters Max 160 chars.</li> <li>• Optional parameter.</li> </ul>

### 8.198.2 Field Documentation

- 8.198.2.1 **BYTE\*** `getDyingGaspCfg::pDestSMSContent`
- 8.198.2.2 **BYTE\*** `getDyingGaspCfg::pDestSMSNum`

## 8.199 getDyingGaspStatistics Struct Reference

### Data Fields

- [ULONG](#) \* [pTimeStamp](#)
- [BYTE](#) \* [pSMSAttemptedFlag](#)

### 8.199.1 Detailed Description

This struture contains the TLV required to get the Dying GASP Statistics.

#### Parameters

<i>OUT]</i>	<p>pDestSMSNum[OUT]</p> <ul style="list-style-type: none"> <li>• SMS Destination Number as string of 8 bit ASCII Characters Max 20 chars.</li> <li>• Optional parameter.</li> </ul>
<i>OUT]</i>	<p>pDestSMSContent[OUT]</p> <ul style="list-style-type: none"> <li>• SMS Content as a string of 8 bit ASCII text characters Max 160 chars.</li> <li>• Optional parameter.</li> </ul>

### 8.199.2 Field Documentation

8.199.2.1 [BYTE](#)\* [getDyingGaspStatistics::pSMSAttemptedFlag](#)

8.199.2.2 [ULONG](#)\* [getDyingGaspStatistics::pTimeStamp](#)

## 8.200 GetErrRateResp Struct Reference

### Data Fields

- [WORD](#) \* [pCDMAFrameErrRate](#)
- [WORD](#) \* [pHDRPackErrRate](#)
- [BYTE](#) \* [pGSMBER](#)
- [BYTE](#) \* [pWCDMABER](#)

### 8.200.1 Detailed Description

This structure contains information about the SLQSGetErrorRate response parameters.

## Parameters

<i>pCDMAFrameErrRate[Out]</i>	<ul style="list-style-type: none"> <li>• CDMA Frame Error Rate</li> <li>• Valid error rate values between 1 and 10000 are returned to indicate the percentage, e.g., a value of 300 means the error rate is 3%.</li> <li>• A value of 0xFFFF indicates that the error rate is unknown/unavailable.</li> </ul>
<i>pHDRPackErrRate[Out]</i>	<ul style="list-style-type: none"> <li>• HDR Packet Error Rate</li> <li>• Valid error rate values between 1 and 10000 are returned to indicate the percentage, e.g., a value of 300 means the error rate is 3%.</li> <li>• A value of 0xFFFF indicates that the error rate is unknown/unavailable.</li> </ul>
<i>pGSMBER[Out]</i>	<ul style="list-style-type: none"> <li>• GSM Bit Error Rate</li> <li>• Valid error rate values between 1 and 100 are returned to indicate the percentage value.</li> <li>• A 0% block error rate (BLER) indicates No Data.</li> </ul>
<i>pWCDMABER[Out]</i>	<ul style="list-style-type: none"> <li>• WCDMA Block Error Rate</li> <li>• Valid error rate values between 1 and 100 are returned to indicate the percentage value.</li> <li>• A value of 0xFF indicates that the error rate is unknown/unavailable.</li> </ul>

## 8.200.2 Field Documentation

8.200.2.1 WORD\* GetErrRateResp::pCDMAFrameErrRate

8.200.2.2 BYTE\* GetErrRateResp::pGSMBER

8.200.2.3 WORD\* GetErrRateResp::pHDRPackErrRate

8.200.2.4 BYTE\* GetErrRateResp::pWCDMABER

## 8.201 GetHRPDStatsResp Struct Reference

## Data Fields

- [DRCParams](#) \* [pDRCParams](#)
- [BYTE](#) \* [pUATI](#)
- [PilotSetData](#) \* [pPilotSetData](#)

## 8.201.1 Detailed Description

This structure contains information about the SLQSSwiGetHRPDStats response parameters.

## Parameters

<i>pDRCParams</i> [- Out]	<ul style="list-style-type: none"> <li>• See <a href="#">DRCParams</a> for more information.</li> </ul>
<i>pUATI</i> [Out]	<ul style="list-style-type: none"> <li>• A 128-bit address that includes the access terminal identifier and subnet ID</li> <li>• Size must be 16 bytes</li> </ul>
<i>pPilotSetData</i> [- Out]	<ul style="list-style-type: none"> <li>• See <a href="#">PilotSetData</a> for more information.</li> </ul>

## 8.201.2 Field Documentation

8.201.2.1 **DRCParams\*** GetHRPDStatsResp::pDRCParams8.201.2.2 **PilotSetData\*** GetHRPDStatsResp::pPilotSetData8.201.2.3 **BYTE\*** GetHRPDStatsResp::pUATI

## 8.202 GetIMSSMSConfigParams Struct Reference

## Data Fields

- **BYTE \*** [pSettingResp](#)
- **BYTE \*** [pSMSFormat](#)
- **BYTE \*** [pSMSOverlPNwInd](#)
- **BYTE \*** [pPhoneCtxtURLen](#)
- **BYTE \*** [pPhoneCtxtURI](#)

## 8.202.1 Detailed Description

This structure contains the SLQSGetIMSSMSConfig response parameters.

## Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"> <li>• Settings Response</li> </ul>
<i>pSMSFormat</i>	<ul style="list-style-type: none"> <li>• SMS format <ul style="list-style-type: none"> <li>– 0 - 3GPP</li> <li>– 1 - 3GPP2</li> </ul> </li> </ul>

<i>pSMSOverIPNwInd</i>	<ul style="list-style-type: none"> <li>SMS over IP Network Indication Flag <ul style="list-style-type: none"> <li>TRUE - Turn on mobile-originated SMS</li> <li>FALSE - Turn off mobile-originated SMS</li> </ul> </li> </ul>
<i>pPhoneCtxtURLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Size in bytes assigned to the Phone context Universal Resource Identifier to follow</li> </ul>
<i>pPhoneCtxtURI</i>	<ul style="list-style-type: none"> <li>Phone context universal resource identifier</li> <li>Length of this string must be specified in pPhoneCtxtURLen parameter</li> </ul>

## 8.202.2 Field Documentation

8.202.2.1 **BYTE\*** GetIMSSMSConfigParams::pPhoneCtxtURI

8.202.2.2 **BYTE\*** GetIMSSMSConfigParams::pPhoneCtxtURLen

8.202.2.3 **BYTE\*** GetIMSSMSConfigParams::pSettingResp

8.202.2.4 **BYTE\*** GetIMSSMSConfigParams::pSMSFormat

8.202.2.5 **BYTE\*** GetIMSSMSConfigParams::pSMSOverIPNwInd

## 8.203 GetIMSUserConfigParams Struct Reference

### Data Fields

- BYTE \*** [pSettingResp](#)
- BYTE \*** [pIMSDomainLen](#)
- BYTE \*** [pIMSDomain](#)

### 8.203.1 Detailed Description

This structure contains the SLQSGetIMSUserConfig response parameters.

#### Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"> <li>Settings Response</li> </ul>
<i>pIMSDomainLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Length of IMS <a href="#">Domain</a> Name to follow</li> </ul>
<i>pIMSDomain</i>	<ul style="list-style-type: none"> <li>IMS domain name</li> <li>Length of this string must be specified in pIMSDomainLen parameter</li> </ul>

### 8.203.2 Field Documentation

8.203.2.1 **BYTE\*** GetIMSUserConfigParams::pIMSDomain

8.203.2.2 **BYTE\*** GetIMSUserConfigParams::pIMSDomainLen

8.203.2.3 **BYTE\*** GetIMSUserConfigParams::pSettingResp

## 8.204 GetIMSVoIPConfigResp Struct Reference

### Data Fields

- **BYTE \*** pSettingResp
- **WORD \*** pSessionExpiryTimer
- **WORD \*** pMinSessionExpiryTimer
- **BYTE \*** pAmrWbEnable
- **BYTE \*** pScrAmrEnable
- **BYTE \*** pScrAmrWbEnable
- **BYTE \*** pAmrMode
- **WORD \*** pAmrWBMode
- **BYTE \*** pAmrOctetAligned
- **BYTE \*** pAmrWBOctetAligned
- **WORD \*** pRingingTimer
- **WORD \*** pRingBackTimer
- **WORD \*** pRTPRTCPInactTimer

### 8.204.1 Detailed Description

This structure contains the SLQSGetIMSVoIPConfig request parameters.

#### Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"> <li>Settings Response. A settings specific error code is returned when the standard response error type is QMI_ERR_CAUSE_CODE</li> </ul>
<i>pSessionExpiryTimer</i>	<ul style="list-style-type: none"> <li>Session duration, in seconds</li> </ul>
<i>pMinSessionExpiryTimer</i>	<ul style="list-style-type: none"> <li>Minimum allowed value for session expiry timer, in seconds</li> </ul>
<i>pAmrWbEnable</i>	<ul style="list-style-type: none"> <li>Flag to enable/disable Adaptive Multirate Codec(AMR) WideBand(WB) audio</li> <li>Values:             <ul style="list-style-type: none"> <li>True - Enable</li> <li>False - Disable</li> </ul> </li> </ul>



<i>pScrAmrEnable</i>	<ul style="list-style-type: none"> <li>• Flag to enable/disable Source Control Rate(SCR) for AMR NarrowBand (NB)</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Enable</li> <li>– False - Disable</li> </ul> </li> </ul>
<i>pScrAmrWb-Enable</i>	<ul style="list-style-type: none"> <li>• Flag to enable/disable SCR for AMR WB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Enable</li> <li>– False - Disable</li> </ul> </li> </ul>
<i>pAmrMode</i>	<ul style="list-style-type: none"> <li>• BitMask for AMR NB modes allowed</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x1 - 4.75 kbps</li> <li>– 0x2 - 5.15 kbps</li> <li>– 0x4 - 5.9 kbps</li> <li>– 0x8 - 6.17 kbps</li> <li>– 0x10 - 7.4 kbps</li> <li>– 0x20 - 7.95 kbps</li> <li>– 0x40 - 10.2 kbps</li> <li>– 0x80 - 12.2 kbps</li> </ul> </li> </ul>
<i>pAmrWBMode</i>	<ul style="list-style-type: none"> <li>• BitMask for AMR WB modes allowed</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x1 - 6.60 kbps</li> <li>– 0x2 - 8.85 kbps</li> <li>– 0x4 - 12.65 kbps</li> <li>– 0x8 - 14.25 kbps</li> <li>– 0x10 - 15.85 kbps</li> <li>– 0x20 - 18.25 kbps</li> <li>– 0x40 - 19.85 kbps</li> <li>– 0x80 - 23.05 kbps</li> <li>– 0x100 - 23.85 kbps</li> </ul> </li> </ul>

<i>pAmrOctet-Aligned</i>	<ul style="list-style-type: none"> <li>• Flag to indicate if the octet is aligned for AMR NB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Aligned</li> <li>– False - Not aligned, Bandwidth Efficient mode</li> </ul> </li> </ul>
<i>pAmrWBOctet-Aligned</i>	<ul style="list-style-type: none"> <li>• Flag to indicate if the octet is aligned for AMR WB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Aligned</li> <li>– False - Not aligned, Bandwidth Efficient mode</li> </ul> </li> </ul>
<i>pRingingTimer</i>	<ul style="list-style-type: none"> <li>• Duration of ringing timer, in seconds. The ringing timer starts on the ringing event. If the call is not answered within the duration of this timer, the call is disconnected.</li> </ul>
<i>pRingBackTimer</i>	<ul style="list-style-type: none"> <li>• Duration of ringback timer, in seconds. The ringback timer starts on the ringback event. If the call is not answered within the duration of this timer, the call is disconnected.</li> </ul>
<i>pRTPRTCP-InactTimer</i>	<ul style="list-style-type: none"> <li>• Duration of RTP/RTCP inactivity timer, in seconds. If no RTP/RTCP packet is received prior to the expiry of this timer, the call is disconnected.</li> </ul>

## 8.204.2 Field Documentation

8.204.2.1 **BYTE\*** GetIMSVoIPConfigResp::pAmrMode

8.204.2.2 **BYTE\*** GetIMSVoIPConfigResp::pAmrOctetAligned

8.204.2.3 **BYTE\*** GetIMSVoIPConfigResp::pAmrWbEnable

8.204.2.4 **WORD\*** GetIMSVoIPConfigResp::pAmrWBMode

8.204.2.5 **BYTE\*** GetIMSVoIPConfigResp::pAmrWBOctetAligned

8.204.2.6 **WORD\*** GetIMSVoIPConfigResp::pMinSessionExpiryTimer

8.204.2.7 **WORD\*** GetIMSVoIPConfigResp::pRingBackTimer

8.204.2.8 **WORD\*** GetIMSVoIPConfigResp::pRingingTimer

8.204.2.9 **WORD\*** GetIMSVoIPConfigResp::pRTPRTCPInactTimer

8.204.2.10 **BYTE\*** GetIMSVoIPConfigResp::pScrAmrEnable

8.204.2.11 **BYTE\*** GetIMSVoIPConfigResp::pScrAmrWbEnable

8.204.2.12 WORD\* GetIMSVolIPConfigResp::pSessionExpiryTimer

8.204.2.13 BYTE\* GetIMSVolIPConfigResp::pSettingResp

## 8.205 GetInstIDResp Struct Reference

### Data Fields

- [BYTE \\* pInstanceID](#)
- [BYTE \\* pIPFamily](#)

### 8.205.1 Field Documentation

8.205.1.1 BYTE\* GetInstIDResp::pInstanceID

8.205.1.2 BYTE\* GetInstIDResp::pIPFamily

## 8.206 GetM2MAudioProfileReq Struct Reference

### Data Fields

- [BYTE \\* pGenerator](#)

### 8.206.1 Detailed Description

This structure contains the SLQSGetM2MAudioProfile request parameters.

#### Parameters

<i>p- Generator[optional]</i>	<ul style="list-style-type: none"><li>• Generator<ul style="list-style-type: none"><li>– 0 - Voice</li></ul></li></ul>
-----------------------------------	--

### 8.206.2 Field Documentation

8.206.2.1 BYTE\* GetM2MAudioProfileReq::pGenerator

## 8.207 GetM2MAudioProfileResp Struct Reference

### Data Fields

- [BYTE Profile](#)
- [BYTE EarMute](#)
- [BYTE MicMute](#)
- [BYTE Generator](#)
- [BYTE Volume](#)
- [BYTE CwtMute](#)

### 8.207.1 Detailed Description

This structure contains the SLQSGetM2MAudioProfile response parameters.

## Parameters

<i>Profile</i>	<ul style="list-style-type: none"> <li>• Audio Profile <ul style="list-style-type: none"> <li>– 0-5</li> </ul> </li> </ul>
<i>EarMute</i>	<ul style="list-style-type: none"> <li>• Ear Mute <ul style="list-style-type: none"> <li>– 0 - Mute</li> <li>– 1 - Unmute</li> </ul> </li> </ul>
<i>MicMute</i>	<ul style="list-style-type: none"> <li>• MIC Mute <ul style="list-style-type: none"> <li>– 0 - Mute</li> <li>– 1 - Unmute</li> </ul> </li> </ul>
<i>Generator</i>	<ul style="list-style-type: none"> <li>• Generator <ul style="list-style-type: none"> <li>– 0 - Voice</li> </ul> </li> </ul>
<i>Volume</i>	<ul style="list-style-type: none"> <li>• RX volume level <ul style="list-style-type: none"> <li>– 0-5</li> </ul> </li> </ul>
<i>CwtMute</i>	<ul style="list-style-type: none"> <li>• Call waiting tone Mute <ul style="list-style-type: none"> <li>– 0 - Mute</li> <li>– 1 - Unmute</li> </ul> </li> </ul>

## 8.207.2 Field Documentation

8.207.2.1 BYTE GetM2MAudioProfileResp::CwtMute

8.207.2.2 BYTE GetM2MAudioProfileResp::EarMute

8.207.2.3 BYTE GetM2MAudioProfileResp::Generator

8.207.2.4 BYTE GetM2MAudioProfileResp::MicMute

8.207.2.5 BYTE GetM2MAudioProfileResp::Profile

8.207.2.6 BYTE GetM2MAudioProfileResp::Volume

## 8.208 GetM2MAudioVolumeReq Struct Reference

### Data Fields

- [BYTE Profile](#)
- [BYTE Generator](#)

### 8.208.1 Detailed Description

This structure contains the SLQSGetM2MAudioVolume request parameters.

#### Parameters

<i>Profile</i>	<ul style="list-style-type: none"><li>• Audio Profile<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>
<i>Generator</i>	<ul style="list-style-type: none"><li>• Generator<ul style="list-style-type: none"><li>– 0 - Voice</li></ul></li></ul>

### 8.208.2 Field Documentation

#### 8.208.2.1 BYTE GetM2MAudioVolumeReq::Generator

#### 8.208.2.2 BYTE GetM2MAudioVolumeReq::Profile

## 8.209 GetM2MAudioVolumeResp Struct Reference

### Data Fields

- [BYTE Level](#)

### 8.209.1 Detailed Description

This structure contains the SLQSGetM2MAudioVolume response parameters.

#### Parameters

<i>Level</i>	<ul style="list-style-type: none"><li>• The RX Volume Level<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>
--------------	--

### 8.209.2 Field Documentation

#### 8.209.2.1 BYTE GetM2MAudioVolumeResp::Level

## 8.210 GetM2MAVMuteReq Struct Reference

### Data Fields

- [BYTE Profile](#)

### 8.210.1 Detailed Description

This structure contains the SLQSGetM2MAVMute request parameters.

#### Parameters

<i>Profile</i>	<ul style="list-style-type: none"><li>• Audio Profile Number<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>
----------------	---

### 8.210.2 Field Documentation

#### 8.210.2.1 BYTE GetM2MAVMuteReq::Profile

## 8.211 GetM2MAVMuteResp Struct Reference

### Data Fields

- [BYTE EarMute](#)
- [BYTE MicMute](#)
- [BYTE CwtMute](#)

### 8.211.1 Detailed Description

This structure contains the SLQSGetM2MAVMute response parameters.

#### Parameters

<i>pEarMute</i>	<ul style="list-style-type: none"><li>• Ear Mute<ul style="list-style-type: none"><li>– 0-Mute</li><li>– 1-UnMute</li></ul></li></ul>
<i>pMicMute</i>	<ul style="list-style-type: none"><li>• Mic Mute<ul style="list-style-type: none"><li>– 0-Mute</li><li>– 1-unmute</li></ul></li></ul>
<i>CwtMute</i>	<ul style="list-style-type: none"><li>• Waiting tone Mute<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>

### 8.211.2 Field Documentation

8.211.2.1 BYTE GetM2MAVMuteResp::CwtMute

8.211.2.2 BYTE GetM2MAVMuteResp::EarMute

8.211.2.3 BYTE GetM2MAVMuteResp::MicMute

## 8.212 GetM2MSpkrGainReq Struct Reference

### Data Fields

- [BYTE Profile](#)

### 8.212.1 Detailed Description

This structure contains the SLQSGetM2MSpkrGain request parameters.

#### Parameters

<i>pProfile</i>	<ul style="list-style-type: none"><li>• Audio Profile Number<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>
-----------------	---

### 8.212.2 Field Documentation

8.212.2.1 BYTE GetM2MSpkrGainReq::Profile

## 8.213 GetM2MSpkrGainResp Struct Reference

### Data Fields

- [WORD Value](#)

### 8.213.1 Detailed Description

This structure contains the SLQSGetM2MSpkrGain response parameters.

#### Parameters

<i>Value</i>	<ul style="list-style-type: none"><li>• RX speakerphone gain<ul style="list-style-type: none"><li>– 0x0 - 0x7fff</li></ul></li></ul>
--------------	--

### 8.213.2 Field Documentation

8.213.2.1 WORD GetM2MSpkrGainResp::Value



## 8.214 getMsgWaitingInfo Struct Reference

### Data Fields

- [BYTE numInstances](#)
- [messageWaitingInfoContent msgWaitInfo](#) [0xFF]

### 8.214.1 Detailed Description

This structure contains Get Message Waiting Info Response parameters

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of sets of the elements in structure <a href="#">messageWaitingInfoContent</a></li> </ul>
<i>pMsgWaitInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">messageWaitingInfoContent</a>. <ul style="list-style-type: none"> <li>– See <a href="#">messageWaitingInfoContent</a> for more information.</li> </ul> </li> </ul>

### 8.214.2 Field Documentation

8.214.2.1 [messageWaitingInfoContent getMsgWaitingInfo::msgWaitInfo](#)[0xFF]

8.214.2.2 [BYTE getMsgWaitingInfo::numInstances](#)

## 8.215 GetNetworkTimeResp Struct Reference

### Data Fields

- [timeInfo](#) \* [p3GPP2TimeInfo](#)
- [timeInfo](#) \* [p3GPPTimeInfo](#)

### 8.215.1 Detailed Description

This structure contains information about the GetNetworkTime response parameters.

#### Parameters

<i>p3GPP2TimeInfo</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">timeInfo</a> for more information</li> </ul>
<i>p3GPPTimeInfo</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">timeInfo</a> for more information</li> </ul>

### 8.215.2 Field Documentation

8.215.2.1 [timeInfo](#)\* [GetNetworkTimeResp::p3GPP2TimeInfo](#)

8.215.2.2 **timeInfo\*** GetNetworkTimeResp::p3GPPTIMEInfo

## 8.216 GetRegMgrConfigParams Struct Reference

### Data Fields

- **BYTE** \* pSettingResp
- **WORD** \* pPCSCFPort
- **BYTE** \* pPriCSCFPortNameLen
- **BYTE** \* pPriCSCFPortName
- **BYTE** \* pIMSTestMode

### 8.216.1 Detailed Description

This structure contains the SLQSGetRegMgrConfig response parameters.

#### Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"> <li>• Settings Response</li> </ul>
<i>pPCSCFPort</i>	<ul style="list-style-type: none"> <li>• Proxy call session control function port</li> </ul>
<i>pPriCSCFPort- NameLen(IN/O- UT)</i>	<ul style="list-style-type: none"> <li>• Size in bytes assigned to the primary CSCF <a href="#">Port</a> name parameter to follow</li> </ul>
<i>pPriCSCFPort- Name</i>	<ul style="list-style-type: none"> <li>• Call Session control port, fully qualified domain name</li> <li>• Length of this string must be specified in pPriCSCFPortNameLen parameter</li> </ul>
<i>pIMSTestMode</i>	<ul style="list-style-type: none"> <li>• IMS Test mode Enabled. <ul style="list-style-type: none"> <li>– TRUE - Enabled</li> <li>– FALSE - Disabled</li> </ul> </li> </ul>

#### Note

pPriCSCFPortNameLen must be set to a valid value during API call to retrieve pPriCSCFPortName.

### 8.216.2 Field Documentation

8.216.2.1 **BYTE\*** GetRegMgrConfigParams::pIMSTestMode

8.216.2.2 **WORD\*** GetRegMgrConfigParams::pPCSCFPort

8.216.2.3 **BYTE\*** GetRegMgrConfigParams::pPriCSCFPortName

8.216.2.4 **BYTE\*** GetRegMgrConfigParams::pPriCSCFPortNameLen

8.216.2.5 **BYTE\*** GetRegMgrConfigParams::pSettingResp

## 8.217 GetSessionIDResp Struct Reference

### Data Fields

- **ULONG** \* pSessionIDv4
- **ULONG** \* pSessionIDv6

### 8.217.1 Field Documentation

8.217.1.1 **ULONG\*** GetSessionIDResp::pSessionIDv4

8.217.1.2 **ULONG\*** GetSessionIDResp::pSessionIDv6

## 8.218 GetSIPConfigResp Struct Reference

### Data Fields

- **BYTE** \* pSettingResp
- **WORD** \* pSIPLocalPort
- **ULONG** \* pTimerSIPReg
- **ULONG** \* pSubscribeTimer
- **ULONG** \* pTimerT1
- **ULONG** \* pTimerT2
- **ULONG** \* pTimerTf
- **BYTE** \* pSigCompEnabled

### 8.218.1 Detailed Description

This structure contains the SLQSGetSIPConfig response parameters.

## Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"> <li>• Settings Response</li> </ul>
<i>pSIPLocalPort</i>	<ul style="list-style-type: none"> <li>• Primary call session control function SIP port number</li> </ul>
<i>pTimerSIPReg</i>	<ul style="list-style-type: none"> <li>• Initial SIP registration duration from the User equipment, in seconds</li> </ul>
<i>pSubscribeTimer</i>	<ul style="list-style-type: none"> <li>• Duration of the subscription by the UE for IMS registration notifications, in seconds</li> </ul>
<i>pTimerT1</i>	<ul style="list-style-type: none"> <li>• RTT estimate, in milliseconds</li> </ul>
<i>pTimerT2</i>	<ul style="list-style-type: none"> <li>• The maximum retransmit interval for non-invite requests and invite responses, in milliseconds</li> </ul>
<i>pTimerTf</i>	<ul style="list-style-type: none"> <li>• Non-invite transaction timeout timer, in milliseconds</li> </ul>
<i>pSigComp-Enabled</i>	<ul style="list-style-type: none"> <li>• Sig Comp Status <ul style="list-style-type: none"> <li>– TRUE - Sig Comp Enabled</li> <li>– FALSE - Sig Comp Disabled</li> </ul> </li> </ul>

## 8.218.2 Field Documentation

8.218.2.1 **BYTE\*** GetSIPConfigResp::pSettingResp8.218.2.2 **BYTE\*** GetSIPConfigResp::pSigCompEnabled8.218.2.3 **WORD\*** GetSIPConfigResp::pSIPLocalPort8.218.2.4 **ULONG\*** GetSIPConfigResp::pSubscribeTimer8.218.2.5 **ULONG\*** GetSIPConfigResp::pTimerSIPReg8.218.2.6 **ULONG\*** GetSIPConfigResp::pTimerT18.218.2.7 **ULONG\*** GetSIPConfigResp::pTimerT28.218.2.8 **ULONG\*** GetSIPConfigResp::pTimerTf

## 8.219 GnssData Struct Reference

## Data Fields

- [ULONGLONG mask](#)

### 8.219.1 Detailed Description

This structure contains the GNSS data

## Parameters

mask	<ul style="list-style-type: none"> <li>• Mask for the GNSS data that is to be deleted</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– QMI_LOC_MASK_DELETE_GPS_SVDIR (0x00000001) - Mask to delete GPS SVDIR</li> <li>– QMI_LOC_MASK_DELETE_GPS_SVSTEER (0x00000002) - Mask to delete GPS SVSTEER</li> <li>– QMI_LOC_MASK_DELETE_GPS_TIME (0x00000004) - Mask to delete GPS time</li> <li>– QMI_LOC_MASK_DELETE_GPS_ALM_CORR (0x00000008) - Mask to delete almanac correlation</li> <li>– QMI_LOC_MASK_DELETE_GLO_SVDIR (0x00000010) - Mask to delete GLO-NASS SVDIR</li> <li>– QMI_LOC_MASK_DELETE_GLO_SVSTEER (0x00000020) - Mask to delete GLO-NASS SVSTEER</li> <li>– QMI_LOC_MASK_DELETE_GLO_TIME (0x00000040) - Mask to delete GLONASS time</li> <li>– QMI_LOC_MASK_DELETE_GLO_ALM_CORR (0x00000080) - Mask to delete GLONASS almanac correlation</li> <li>– QMI_LOC_MASK_DELETE_SBAS_SVDIR (0x00000100) - Mask to delete SBAS SVDIR</li> <li>– QMI_LOC_MASK_DELETE_SBAS_SVSTEER (0x00000200) - Mask to delete SBAS SVSTEER</li> <li>– QMI_LOC_MASK_DELETE_POSITION (0x00000400) - Mask to delete position estimate</li> <li>– QMI_LOC_MASK_DELETE_TIME (0x00000800) - Mask to delete time estimate</li> <li>– QMI_LOC_MASK_DELETE_IONO (0x00001000) - Mask to delete IONO</li> <li>– QMI_LOC_MASK_DELETE_UTC (0x00002000) - Mask to delete UTC estimate</li> <li>– QMI_LOC_MASK_DELETE_HEALTH (0x00004000) - Mask to delete <a href="#">SV</a> health record</li> <li>– QMI_LOC_MASK_DELETE_SADATA (0x00008000) - Mask to delete SADATA</li> <li>– QMI_LOC_MASK_DELETE_RTI (0x00010000) - Mask to delete RTI</li> <li>– QMI_LOC_MASK_DELETE_SV_NO_EXIST (0x00020000) - Mask to delete SV_NO_EXIST</li> <li>– QMI_LOC_MASK_DELETE_FREQ_BIAS_EST (0x00040000) - Mask to delete frequency bias estimate</li> <li>– QMI_LOC_MASK_DELETE_BDS_SVDIR (0x00080000) - Mask to delete BDS SVDIR</li> <li>– QMI_LOC_MASK_DELETE_BDS_SVSTEER (0x00100000) - Mask to delete BDS SVSTEER</li> <li>– QMI_LOC_MASK_DELETE_BDS_TIME (0x00200000) - Mask to delete BDS time</li> <li>– QMI_LOC_MASK_DELETE_BDS_ALM_CORR (0x00400000) - Mask to delete BDS almanac correlation</li> <li>– QMI_LOC_MASK_DELETE_GNSS_SV_BLACKLIST_GPS (0x00800000) - Mask to delete GNSS <a href="#">SV</a> blacklist GPS</li> <li>– QMI_LOC_MASK_DELETE_GNSS_SV_BLACKLIST_GLO (0x01000000) - Mask to delete GNSS <a href="#">SV</a> blacklist GLO</li> <li>– QMI_LOC_MASK_DELETE_GNSS_SV_BLACKLIST_BDS (0x02000000) - Mask to delete GNSS <a href="#">SV</a> blacklist BDS</li> </ul> </li> </ul>
	<p>Generated on Tue Jul 12 2016 10:59:49 for LinuxQMI SDK by Doxygen</p>

## 8.219.2 Field Documentation

### 8.219.2.1 ULONGLONG GnssData::mask

## 8.220 gnssSvInfoNotification Struct Reference

### Data Fields

- [BYTE bAltitudeAssumed](#)
- [satelliteInfo](#) \* [pSatelliteInfo](#)

### 8.220.1 Detailed Description

Contain the parameters passed for SetLocGnssSvInfoCallback by the device.

#### Parameters

<i>bAltitude- Assumed</i>	<ul style="list-style-type: none"> <li>• Indicates whether altitude is assumed or calculated <ul style="list-style-type: none"> <li>– 0x00 (FALSE) - Valid altitude is calculated</li> <li>– 0x01 (TRUE) - Valid altitude is assumed; there may not be enough satellites to determine precise altitude</li> </ul> </li> </ul>
<i>pSatelliteInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">satelliteInfo</a> for more information.</li> </ul>

#### Note

None

## 8.220.2 Field Documentation

### 8.220.2.1 BYTE gnssSvInfoNotification::bAltitudeAssumed

### 8.220.2.2 satelliteInfo\* gnssSvInfoNotification::pSatelliteInfo

## 8.221 GPRSQoS Struct Reference

### Data Fields

- [ULONG precedenceClass](#)
- [ULONG delayClass](#)
- [ULONG reliabilityClass](#)
- [ULONG peakThroughputClass](#)
- [ULONG meanThroughputClass](#)

### 8.221.1 Detailed Description

This structure contains the GPRS Quality Of Service Information

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>precedence-Class</i>	<ul style="list-style-type: none"> <li>• Precedence class</li> </ul>
<i>delayClass</i>	<ul style="list-style-type: none"> <li>• Delay class</li> </ul>
<i>reliabilityClass</i>	<ul style="list-style-type: none"> <li>• Reliability class</li> </ul>
<i>peak-Throughput-Class</i>	<ul style="list-style-type: none"> <li>• Peak throughput class</li> </ul>
<i>mean-Throughput-Class</i>	<ul style="list-style-type: none"> <li>• Mean throughput class</li> </ul>

## 8.221.2 Field Documentation

8.221.2.1 **ULONG** GPRSQoS::delayClass8.221.2.2 **ULONG** GPRSQoS::meanThroughputClass8.221.2.3 **ULONG** GPRSQoS::peakThroughputClass8.221.2.4 **ULONG** GPRSQoS::precedenceClass8.221.2.5 **ULONG** GPRSQoS::reliabilityClass

## 8.222 GPRSRequestedQoS Struct Reference

## Data Fields

- [ULONG precedenceClass](#)
- [ULONG delayClass](#)
- [ULONG reliabilityClass](#)
- [ULONG peakThroughputClass](#)
- [ULONG meanThroughputClass](#)

## 8.222.1 Detailed Description

This structure contains the GPRS Quality Of Service Information

## Parameters

<i>precedence-Class</i>	<ul style="list-style-type: none"> <li>• Precedence class</li> </ul>
-------------------------	--



<i>delayClass</i>	<ul style="list-style-type: none"> <li>• Delay class</li> </ul>
<i>reliabilityClass</i>	<ul style="list-style-type: none"> <li>• Reliability class</li> </ul>
<i>peak-Throughput-Class</i>	<ul style="list-style-type: none"> <li>• Peak throughput class</li> </ul>
<i>mean-Throughput-Class</i>	<ul style="list-style-type: none"> <li>• Mean throughput class</li> </ul>

### 8.222.2 Field Documentation

8.222.2.1 **ULONG** GPRSRequestedQoS::delayClass

8.222.2.2 **ULONG** GPRSRequestedQoS::meanThroughputClass

8.222.2.3 **ULONG** GPRSRequestedQoS::peakThroughputClass

8.222.2.4 **ULONG** GPRSRequestedQoS::precedenceClass

8.222.2.5 **ULONG** GPRSRequestedQoS::reliabilityClass

## 8.223 GPSSStateInfo Struct Reference

### Data Fields

- [BYTE](#) EngineState
- [ULONG](#) ValidMask
- [ULONGLONG](#) Latitude
- [ULONGLONG](#) Longitude
- [ULONG](#) HorizontalUncertainty
- [ULONG](#) Altitude
- [ULONG](#) VerticalUncertainty
- [ULONG](#) TimeStmp\_tow\_ms
- [WORD](#) TimeStmp\_gps\_week
- [ULONG](#) Time\_uncert\_ms
- [BYTE](#) lono\_valid
- [ULONG](#) gps\_ephemeris\_sv\_msk
- [ULONG](#) gps\_almanac\_sv\_msk
- [ULONG](#) gps\_health\_sv\_msk
- [ULONG](#) gps\_visible\_sv\_msk
- [ULONG](#) glo\_ephemeris\_sv\_msk
- [ULONG](#) glo\_almanac\_sv\_msk
- [ULONG](#) glo\_health\_sv\_msk
- [ULONG](#) glo\_visible\_sv\_msk
- [ULONG](#) sbas\_ephemeris\_sv\_msk
- [ULONG](#) sbas\_almanac\_sv\_msk
- [ULONG](#) sbas\_health\_sv\_msk
- [ULONG](#) sbas\_visible\_sv\_msk
- [WORD](#) xtra\_start\_gps\_week

- [WORD xtra\\_start\\_gps\\_minutes](#)
- [WORD xtra\\_valid\\_duration\\_hours](#)

### 8.223.1 Detailed Description

GPS state Info.

Parameters

<i>EngineState</i>	<ul style="list-style-type: none"> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - OFF</li> <li>– 1 - ON</li> </ul> </li> <li>• This field is always valid</li> </ul>
<i>ValidMask</i>	<ul style="list-style-type: none"> <li>• Mask of valid state information data.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00000001 - Position(latitude/longitude/horizontal uncertainty)</li> <li>– 0x00000002 - Altitude and vertical uncertainty</li> <li>– 0x00000004 - Time ms</li> <li>– 0x00000008 - Time week number</li> <li>– 0x00000010 - Time uncertainty</li> <li>– 0x00000020 - Iono validity</li> <li>– 0x00000040 - GPS ephemeris</li> <li>– 0x00000080 - GPS almanac</li> <li>– 0x00000100 - GPS health</li> <li>– 0x00000200 - GPS visible SVs</li> <li>– 0x00000400 - GLONASS ephemeris</li> <li>– 0x00000800 - GLONASS almanac</li> <li>– 0x00001000 - GLONASS health</li> <li>– 0x00002000 - GLONASS visible SVs</li> <li>– 0x00004000 - SBAS ephemeris</li> <li>– 0x00008000 - SBAS almanac</li> <li>– 0x00010000 - SBAS health</li> <li>– 0x00020000 - SBAS visible SVs</li> <li>– 0x00040000 - XTRA information</li> </ul> </li> </ul>

<i>Latitude</i>	<ul style="list-style-type: none"> <li>Latitude position referenced to the WGS-84 reference ellipsoid, counting positive angles north of the equator and negative angles south of the equator.</li> <li>Units: Decimal degrees</li> <li>Range: -90 to +90 degrees.</li> <li>Value is in double float format (refer to IEEE Std 754-1985)</li> </ul>
<i>Longitude</i>	<ul style="list-style-type: none"> <li>Longitude position referenced to the WGS-84 reference ellipsoid, counting positive angles east of the Greenwich Meridian and negative angles west of Greenwich meridian.</li> <li>Units: Decimal degrees</li> <li>Range: -180 to +180 degrees</li> <li>Value is in double float format (refer to IEEE Std 754-1985)</li> </ul>
<i>Horizontal-Uncertainty</i>	<ul style="list-style-type: none"> <li>Circular horizontal uncertainty (in meters). The uncertainty is provided at 63 percent confidence.</li> <li>Value is in single float format (refer to IEEE Std 754-1985)</li> </ul>
<i>Altitude</i>	<ul style="list-style-type: none"> <li>Height above the WGS-84 reference ellipsoid. Value conveys height (in meters) plus 500 m</li> <li>Range -500 to 15883</li> <li>Value in single float format (refer to IEEE Std 754-1985)</li> </ul>
<i>Vertical-Uncertainty</i>	<ul style="list-style-type: none"> <li>Vertical uncertainty (in meters). The uncertainty is provided at 68 percent confidence.</li> <li>Value in single float format (refer to IEEE Std 754-1985)</li> </ul>
<i>TimeStmp_tow_-ms</i>	<ul style="list-style-type: none"> <li>Time stamp in GPS time of week( in milliseconds)</li> </ul>
<i>TimeStmp_gps-_week</i>	<ul style="list-style-type: none"> <li>GPS week number</li> </ul>
<i>Time_uncert_ms</i>	<ul style="list-style-type: none"> <li>Time uncertainty (in milliseconds). The uncertainty is provided at 99 percent confidence.</li> </ul>
<i>Iono_valid</i>	<ul style="list-style-type: none"> <li>Iono validity.</li> <li>Values: <ul style="list-style-type: none"> <li>0 - Invalid</li> <li>1 - Valid</li> </ul> </li> </ul>

<i>gps_ephemeris_sv_msk</i>	<ul style="list-style-type: none"> <li>GPS <b>SV</b> mask for ephemeris; if the bit is set, ephemeris for that <b>SV</b> is available.</li> </ul>
<i>gps_almanac_sv_msk</i>	<ul style="list-style-type: none"> <li>GPS <b>SV</b> mask for almanac; if the bit is set, almanac for that <b>SV</b> is available.</li> </ul>
<i>gps_health_sv_msk</i>	<ul style="list-style-type: none"> <li>GPS <b>SV</b> mask for health; if the bit is set, health for that <b>SV</b> is available.</li> </ul>
<i>gps_visible_sv_msk</i>	<ul style="list-style-type: none"> <li>GPS <b>SV</b> mask for visible Svcs; if the bit is set, the <b>SV</b> is available.</li> </ul>
<i>glo_ephemeris_sv_msk</i>	<ul style="list-style-type: none"> <li>GLONASS <b>SV</b> mask for ephemeris; if the bit is set, ephemeris for that <b>SV</b> is available.</li> </ul>
<i>glo_almanac_sv_msk</i>	<ul style="list-style-type: none"> <li>GLONASS <b>SV</b> mask for almanac; if the bit is set, almanac for that <b>SV</b> is available.</li> </ul>
<i>glo_health_sv_msk</i>	<ul style="list-style-type: none"> <li>GLONASS <b>SV</b> mask for health; if the bit is set, health for that <b>SV</b> is available.</li> </ul>
<i>glo_visible_sv_msk</i>	<ul style="list-style-type: none"> <li>GLONASS <b>SV</b> mask for visible SVs; if the bit is set, the <b>SV</b> is available.</li> </ul>
<i>sbas_ephemeris_sv_msk</i>	<ul style="list-style-type: none"> <li>SBAS <b>SV</b> mask for ephemeris; if the bit is set, ephemeris for that <b>SV</b> is available.</li> </ul>
<i>sbas_almanac_sv_msk</i>	<ul style="list-style-type: none"> <li>SBAS <b>SV</b> mask for almanac; if the bit is set, almanac for that <b>SV</b> is available.</li> </ul>
<i>sbas_health_sv_msk</i>	<ul style="list-style-type: none"> <li>SBAS <b>SV</b> mask for health; if the bit is set, health for that <b>SV</b> is available.</li> </ul>
<i>sbas_visible_sv_msk</i>	<ul style="list-style-type: none"> <li>SBAS <b>SV</b> mask for visible SVs; if the bit is set, the <b>SV</b> is available.</li> </ul>
<i>xtra_start_gps_week</i>	<ul style="list-style-type: none"> <li>Current XTRA information is valid starting from this GPS week number</li> </ul>
<i>xtra_start_gps_minutes</i>	<ul style="list-style-type: none"> <li>Current XTRA information is valid starting from the GPS minutes with the GPS week</li> </ul>
<i>xtra_valid_duration_hours</i>	<ul style="list-style-type: none"> <li>XTRA information is valid for this many hours starting from the specified GPS week/minutes</li> </ul>

## 8.223.2 Field Documentation

### 8.223.2.1 ULONG GPSSateInfo::Altitude

- 8.223.2.2 **BYTE** GPSSStateInfo::EngineState
- 8.223.2.3 **ULONG** GPSSStateInfo::glo\_almanac\_sv\_msk
- 8.223.2.4 **ULONG** GPSSStateInfo::glo\_ephemeris\_sv\_msk
- 8.223.2.5 **ULONG** GPSSStateInfo::glo\_health\_sv\_msk
- 8.223.2.6 **ULONG** GPSSStateInfo::glo\_visible\_sv\_msk
- 8.223.2.7 **ULONG** GPSSStateInfo::gps\_almanac\_sv\_msk
- 8.223.2.8 **ULONG** GPSSStateInfo::gps\_ephemeris\_sv\_msk
- 8.223.2.9 **ULONG** GPSSStateInfo::gps\_health\_sv\_msk
- 8.223.2.10 **ULONG** GPSSStateInfo::gps\_visible\_sv\_msk
- 8.223.2.11 **ULONG** GPSSStateInfo::HorizontalUncertainty
- 8.223.2.12 **BYTE** GPSSStateInfo::lono\_valid
- 8.223.2.13 **ULONGLONG** GPSSStateInfo::Latitude
- 8.223.2.14 **ULONGLONG** GPSSStateInfo::Longitude
- 8.223.2.15 **ULONG** GPSSStateInfo::sbas\_almanac\_sv\_msk
- 8.223.2.16 **ULONG** GPSSStateInfo::sbas\_ephemeris\_sv\_msk
- 8.223.2.17 **ULONG** GPSSStateInfo::sbas\_health\_sv\_msk
- 8.223.2.18 **ULONG** GPSSStateInfo::sbas\_visible\_sv\_msk
- 8.223.2.19 **ULONG** GPSSStateInfo::Time\_uncert\_ms
- 8.223.2.20 **WORD** GPSSStateInfo::TimeStmp\_gps\_week
- 8.223.2.21 **ULONG** GPSSStateInfo::TimeStmp\_tow\_ms
- 8.223.2.22 **ULONG** GPSSStateInfo::ValidMask
- 8.223.2.23 **ULONG** GPSSStateInfo::VerticalUncertainty
- 8.223.2.24 **WORD** GPSSStateInfo::xtra\_start\_gps\_minutes
- 8.223.2.25 **WORD** GPSSStateInfo::xtra\_start\_gps\_week
- 8.223.2.26 **WORD** GPSSStateInfo::xtra\_valid\_duration\_hours

## 8.224 gpsTime\_s Struct Reference

### Data Fields

- [WORD](#) `gpsWeek`
- [ULONG](#) `gpsTimeOfWeekMs`

### 8.224.1 Detailed Description

This structure contains GPS Time info.

#### Parameters

<i>gpsWeek</i>	<ul style="list-style-type: none"><li>• Current GPS week as calculated from midnight, Jan. 6, 1980.</li><li>• Units - Weeks</li></ul>
<i>gpsTimeOf-WeekMs</i>	<ul style="list-style-type: none"><li>• Amount of time into the current GPS week.</li><li>• Units - Milliseconds</li></ul>

### 8.224.2 Field Documentation

8.224.2.1 **ULONG** *gpsTime\_s::gpsTimeOfWeekMs*

8.224.2.2 **WORD** *gpsTime\_s::gpsWeek*

## 8.225 gsmCellInfo Struct Reference

### Data Fields

- [WORD](#) *arfcn*
- [BYTE](#) *band1900*
- [BYTE](#) *cellIdValid*
- [BYTE](#) *bsicId*
- [SHORT](#) *rsi*
- [SHORT](#) *srxlev*

### 8.225.1 Detailed Description

This structure contains information about the GSM Cell.

#### Parameters

<i>arfcn</i>	<ul style="list-style-type: none"><li>• GSM frequency being reported.</li><li>• Range: 0 to 1023.</li></ul>
<i>band1900</i>	<ul style="list-style-type: none"><li>• Band indicator for the GSM ARFCN</li><li>• This field is only valid if <i>arfcn</i> is in the overlapping region.</li><li>• If TRUE and the cell is in the overlapping region, the ARFCN is on the 1900 band.</li><li>• If FALSE, it is on the 1800 band.</li></ul>

<i>cellIdValid</i>	<ul style="list-style-type: none"> <li>Flag indicating whether the base station identity code ID is valid.</li> </ul>
<i>bsicId</i>	<ul style="list-style-type: none"> <li>Base station identity code ID, including base station color code and network color code.</li> <li>The lower 6 bits can be set to any value.</li> </ul>
<i>rsSI</i>	<ul style="list-style-type: none"> <li>Measured RSSI value in 1/10 dB.</li> <li>Range: -200.0 dB to 0</li> </ul>
<i>srxlev</i>	<ul style="list-style-type: none"> <li>Cell selection Rx level (Srxlev) value.</li> <li>Range: -128 to 128.</li> <li>This field is only valid when ue_in_idle is TRUE.</li> </ul>

## 8.225.2 Field Documentation

8.225.2.1 WORD gsmCellInfo::arfcn

8.225.2.2 BYTE gsmCellInfo::band1900

8.225.2.3 BYTE gsmCellInfo::bsicId

8.225.2.4 BYTE gsmCellInfo::cellIdValid

8.225.2.5 SHORT gsmCellInfo::rsSI

8.225.2.6 SHORT gsmCellInfo::srxlev

## 8.226 GSMRSSIThresh Struct Reference

### Data Fields

- [BYTE GSMRSSIThreshListLen](#)
- [WORD \\* pGSMRSSIThreshList](#)

### 8.226.1 Detailed Description

This structure contains GSM RSSI threshold related parameters.

#### Parameters

<i>GSMRSSI- ThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the GSM RSSI threshold list parameter to follow</li> </ul>
-----------------------------------	---

<i>pGSMRSSI- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values</li> <li>• Range for RSSI values: -111 to -48 (in dBm)</li> </ul>
---------------------------------	---

## 8.226.2 Field Documentation

8.226.2.1 **BYTE** GSMRSSIthresh::GSMRSSIthreshListLen

8.226.2.2 **WORD\*** GSMRSSIthresh::pGSMRSSIthreshList

## 8.227 GSMSrvStatusInfo Struct Reference

### Data Fields

- [BYTE srvStatus](#)
- [BYTE trueSrvStatus](#)
- [BYTE isPrefDataPath](#)

### 8.227.1 Detailed Description

Structure for storing the service status information for GSM, WCDMA and LTE networks.

#### Parameters

<i>srvStatus</i>	<ul style="list-style-type: none"> <li>• Service status of the system. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - Power save</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
------------------	--



<i>trueSrvStatus</i>	<ul style="list-style-type: none"> <li>• True service status of the system.</li> <li>• Not applicable to CDMA/HDR. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - Power save</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>isPrefDataPath</i>	<ul style="list-style-type: none"> <li>• Whether the RAT is the preferred data path. <ul style="list-style-type: none"> <li>– 0x00 - Not preferred</li> <li>– 0x01 - Preferred</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

## 8.227.2 Field Documentation

8.227.2.1 **BYTE** GSMSrvStatusInfo::isPrefDataPath

8.227.2.2 **BYTE** GSMSrvStatusInfo::srvStatus

8.227.2.3 **BYTE** GSMSrvStatusInfo::trueSrvStatus

## 8.228 GSMSysInfo Struct Reference

### Data Fields

- [sysInfoCommon sysInfoGSM](#)
- [BYTE lacValid](#)
- [WORD lac](#)
- [BYTE cellIdValid](#)
- [ULONG cellId](#)
- [BYTE regRejectInfoValid](#)
- [BYTE rejectSrvDomain](#)
- [BYTE rejCause](#)
- [BYTE networkIdValid](#)
- [BYTE MCC \[3\]](#)
- [BYTE MNC \[3\]](#)
- [BYTE egprsSuppValid](#)
- [BYTE egprsSupp](#)
- [BYTE dtmSuppValid](#)
- [BYTE dtmSupp](#)

### 8.228.1 Detailed Description

Structure for storing the GSM System Information.

## Parameters

<i>sysInfoGSM</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
<i>lacValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the location area code is valid.. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• Only applies to 3GPP. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>cellIdValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the cell ID is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>cellId</i>	<ul style="list-style-type: none"> <li>• Cell ID. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>regRejectInfo-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the registration reject information is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>rejectSrvDomain</i>	<ul style="list-style-type: none"> <li>• Type of service domain in which the registration is rejected. <ul style="list-style-type: none"> <li>– 0x00 - SYS_SRV_DOMAIN_NO_SRV - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> <li>– 0x04 - Camped</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>rejCause</i>	<ul style="list-style-type: none"> <li>• Reject cause values sent are specified in [3GPP TS 24.008, Section 10.5.3.6]. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
	Generated on Tue Jul 12 2016 10:59:49 for LinuxQMISDK by Doxygen

<i>networkIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the network ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>MCC[PLMN_LE-NGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Country Code.</li> <li>MCC digits in ASCII characters</li> </ul>
<i>MNC[PLMN_LE-NGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Network Code.</li> <li>MNC digits in ASCII characters</li> <li>An unused byte is set to 0xFF.</li> <li>In case of two-digit MNC values, the third (unused) digit is set to 0xFF. For example, 15 (a two-digit MNC) is reported using the byte stream 0x31 0x35 0xFF.</li> </ul>
<i>egprsSuppValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the EGPRS support is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>egprsSupp</i>	<ul style="list-style-type: none"> <li>EGPRS support indication.</li> <li>Only applicable for GSM. <ul style="list-style-type: none"> <li>0x00 - Not available</li> <li>0x01 - Available</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>dtmSuppValid</i>	<ul style="list-style-type: none"> <li>Indicates whether Dual Transfer mode support is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

<i>dtmSupp</i>	<ul style="list-style-type: none"> <li>• Dual Transfer mode support indication.</li> <li>• Only applicable for GSM. <ul style="list-style-type: none"> <li>– 0x00 - Not available</li> <li>– 0x01 - Available</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
----------------	--

## 8.228.2 Field Documentation

8.228.2.1 **ULONG** GSMSysInfo::cellId

8.228.2.2 **BYTE** GSMSysInfo::cellIdValid

8.228.2.3 **BYTE** GSMSysInfo::dtmSupp

8.228.2.4 **BYTE** GSMSysInfo::dtmSuppValid

8.228.2.5 **BYTE** GSMSysInfo::egprsSupp

8.228.2.6 **BYTE** GSMSysInfo::egprsSuppValid

8.228.2.7 **WORD** GSMSysInfo::lac

8.228.2.8 **BYTE** GSMSysInfo::lacValid

8.228.2.9 **BYTE** GSMSysInfo::MCC[3]

8.228.2.10 **BYTE** GSMSysInfo::MNC[3]

8.228.2.11 **BYTE** GSMSysInfo::networkIdValid

8.228.2.12 **BYTE** GSMSysInfo::regRejectInfoValid

8.228.2.13 **BYTE** GSMSysInfo::rejCause

8.228.2.14 **BYTE** GSMSysInfo::rejectSrvDomain

8.228.2.15 **sysInfoCommon** GSMSysInfo::sysInfoGSM

## 8.229 gyroAcceptReady\_s Struct Reference

### Data Fields

- [BYTE](#) injectEnable
- [WORD](#) samplesPerBatch
- [WORD](#) batchPerSec

### 8.229.1 Detailed Description

This structure contains Gyroscope Accept Ready Info

## Parameters

<i>injectEnable</i>	<ul style="list-style-type: none"> <li>GNSS location engine is ready to accept data from sensor.</li> <li>Values</li> <li>0x01 - Ready to accept sensor data</li> <li>0x00 - Not ready to accept sensor data</li> </ul>
<i>samplesPerBatch</i>	<ul style="list-style-type: none"> <li>number of samples per batch the GNSS location engine is to receive.</li> <li>samplingFrequency = samplesPerBatch * batchesPerSecond</li> <li>samplesPerBatch must be a nonzero positive value.</li> </ul>
<i>batchPerSec</i>	<ul style="list-style-type: none"> <li>LTE NAS version minor</li> <li>Number of sensor-data batches the GNSS location engine is to receive per second.</li> <li>BatchesPerSecond must be a nonzero positive value.</li> </ul>

## 8.229.2 Field Documentation

8.229.2.1 WORD gyroAcceptReady\_s::batchPerSec

8.229.2.2 BYTE gyroAcceptReady\_s::injectEnable

8.229.2.3 WORD gyroAcceptReady\_s::samplesPerBatch

## 8.230 gyroTempAcceptReady\_s Struct Reference

## Data Fields

- [BYTE injectEnable](#)
- [WORD samplesPerBatch](#)
- [WORD batchPerSec](#)

## 8.230.1 Detailed Description

This structure contains Gyroscope Temperature Accept Ready Info

## Parameters

<i>injectEnable</i>	<ul style="list-style-type: none"> <li>GNSS location engine is ready to accept data from sensor.</li> <li>Values</li> <li>0x01 - Ready to accept sensor data</li> <li>0x00 - Not ready to accept sensor data</li> </ul>
<i>samplesPerBatch</i>	<ul style="list-style-type: none"> <li>number of samples per batch the GNSS location engine is to receive.</li> <li>samplingFrequency = samplesPerBatch * batchesPerSecond</li> <li>samplesPerBatch must be a nonzero positive value.</li> </ul>
<i>batchPerSec</i>	<ul style="list-style-type: none"> <li>LTE NAS version minor</li> <li>Number of sensor-data batches the GNSS location engine is to receive per second.</li> <li>BatchesPerSecond must be a nonzero positive value.</li> </ul>

## 8.230.2 Field Documentation

8.230.2.1 WORD gyroTempAcceptReady\_s::batchPerSec

8.230.2.2 BYTE gyroTempAcceptReady\_s::injectEnable

8.230.2.3 WORD gyroTempAcceptReady\_s::samplesPerBatch

## 8.231 HDRECIOThresh Struct Reference

## Data Fields

- BYTE HDRECIOThreshListLen
- WORD \* pHRECIOThreshList

## 8.231.1 Detailed Description

This structure contains HDR ECIO threshold related parameters.

## Parameters

<i>HDRECIO-ThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the HDR ECIO threshold list parameter to follow</li> </ul>
<i>pHDRECIO-ThreshList</i>	<ul style="list-style-type: none"> <li>Array of ECIO thresholds (in units of 0.1 dB)</li> <li>Maximum of 32 values</li> <li>Range for ECIO values: -31.5 to 0 (in dB).</li> </ul>

### 8.231.2 Field Documentation

8.231.2.1 **BYTE** HDRECIOTthresh::HDRECIOTthreshListLen

8.231.2.2 **WORD\*** HDRECIOTthresh::pHDRECIOTthreshList

## 8.232 HDRIOTthresh Struct Reference

### Data Fields

- [BYTE HDRIOTthreshListLen](#)
- [WORD \\* pHDRIOThreshList](#)

### 8.232.1 Detailed Description

This structure contains HDR IO threshold related parameters.

#### Parameters

<i>HDRIOTthresh-ListLen</i>	<ul style="list-style-type: none"> <li>• Length of the HDR IO threshold list parameter to follow</li> </ul>
<i>pHDRIOTthresh-List</i>	<ul style="list-style-type: none"> <li>• Array of IO thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values</li> <li>• Range for IO values: -128 to -13 (in dBm).</li> </ul>

### 8.232.2 Field Documentation

8.232.2.1 **BYTE** HDRIOTthresh::HDRIOTthreshListLen

8.232.2.2 **WORD\*** HDRIOTthresh::pHDRIOTthreshList

## 8.233 HDRPersonalityInd Struct Reference

### Data Fields

- [WORD \\* pCurrentPersonality](#)
- [BYTE \\* pPersonalityListLength](#)
- [protocolSubtypeElement \\* pProtocolSubtypeElement](#)

### 8.233.1 Field Documentation

8.233.1.1 **WORD\*** HDRPersonalityInd::pCurrentPersonality

8.233.1.2 **BYTE\*** HDRPersonalityInd::pPersonalityListLength

8.233.1.3 **protocolSubtypeElement\*** HDRPersonalityInd::pProtocolSubtypeElement

## 8.234 HDRPersonalityResp Struct Reference

### Data Fields

- [WORD](#) \* [pCurrentPersonality](#)
- [BYTE](#) \* [pPersonalityListLength](#)
- [protocolSubtypeElement](#) \* [pProtocolSubtypeElement](#)

### 8.234.1 Detailed Description

This structure contains information about the SLQSSwiGetHDRPersonality response parameters.

#### Parameters

<i>pCurrent-Personality[Out]</i>	<ul style="list-style-type: none"> <li>• Current active personality index.</li> </ul>
<i>pPersonalityList-Length[In/Out]</i>	<ul style="list-style-type: none"> <li>• Number of Personality Protocol Subtype contains in this response.</li> <li>• maximum input value is 3</li> </ul>
<i>pProtocol-Subtype-Element[Out]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">protocolSubtypeElement</a> for more information.</li> </ul>

### 8.234.2 Field Documentation

8.234.2.1 [WORD](#)\* HDRPersonalityResp::pCurrentPersonality

8.234.2.2 [BYTE](#)\* HDRPersonalityResp::pPersonalityListLength

8.234.2.3 [protocolSubtypeElement](#)\* HDRPersonalityResp::pProtocolSubtypeElement

## 8.235 HDRProtSubtypResp Struct Reference

### Data Fields

- [WORD](#) \* [pCurrentPrsnlty](#)
- [BYTE](#) \* [pPersonalityListLength](#)
- [protocolSubtypeElement](#) \* [pProtoSubTypElmnt](#)
- [ULONGLONG](#) \* [pAppSubType](#)

### 8.235.1 Detailed Description

This structure contains information about the SLQSSwiGetHDRProtSubtype response parameters.

#### Parameters

<i>pCurrent-Personality[Out]</i>	<ul style="list-style-type: none"> <li>• Current active personality index.</li> </ul>
----------------------------------	---



<i>pPersonalityListLength</i> [In/Out]	<ul style="list-style-type: none"> <li>• Number of Personality Protocol Subtype contains in this response.</li> <li>• maximum input value is 4</li> </ul>
<i>pProtocolSubtypeElement</i> [Out]	<ul style="list-style-type: none"> <li>• See <a href="#">protocolSubtypeElement</a> for more information.</li> </ul>
<i>pAppSubType</i> [Out]	<ul style="list-style-type: none"> <li>• Stream application subtype</li> <li>• Application subtype for each stream,</li> </ul>

## 8.235.2 Field Documentation

8.235.2.1 **ULONGLONG\*** HDRProtSubtypResp::pAppSubType

8.235.2.2 **WORD\*** HDRProtSubtypResp::pCurrentPrsnlty

8.235.2.3 **BYTE\*** HDRProtSubtypResp::pPersonalityListLength

8.235.2.4 **protocolSubtypeElement\*** HDRProtSubtypResp::pProtoSubTypeElmnt

## 8.236 HDRRSSIThresh Struct Reference

### Data Fields

- [BYTE HDRRSSIThreshListLen](#)
- [WORD \\* pHDRRSSIThreshList](#)

## 8.236.1 Detailed Description

This structure contains HDR RSSI threshold related parameters.

### Parameters

<i>HDRRSSIThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the HDR RSSI threshold list parameter to follow</li> </ul>
<i>pHDRRSSIThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values.</li> <li>• Range for RSSI values: -118 to -13 (in dBm).</li> </ul>

## 8.236.2 Field Documentation

8.236.2.1 **BYTE** HDRRSSIThresh::HDRRSSIThreshListLen

8.236.2.2 **WORD\*** HDRRSSIThresh::pHDRRSSIThreshList

## 8.237 HDRSINRThresh Struct Reference

### Data Fields

- [BYTE HDRSINRThresListLen](#)
- [BYTE \\* pHDRSINRThresList](#)

### 8.237.1 Detailed Description

This structure contains HDR SINR threshold related parameters.

#### Parameters

<i>HDRSINRThres- ListLen</i>	<ul style="list-style-type: none"> <li>• Length of the HDR SINR threshold list parameter to follow</li> </ul>
<i>pHDRSINR- ThresList</i>	<ul style="list-style-type: none"> <li>• Sequence of thresholds delimiting SINR event reporting bands</li> <li>• Every time a new SINR value crosses a threshold value, an event report indication message with the new SINR value is sent to the requesting control point. For this field               <ul style="list-style-type: none"> <li>– SINR is reported only for HDR</li> <li>– Each SINR threshold value is an unsigned 1 byte value</li> <li>– Maximum number of threshold values is 16</li> <li>– At least one value must be specified</li> </ul> </li> </ul>

### 8.237.2 Field Documentation

8.237.2.1 [BYTE HDRSINRThresh::HDRSINRThresListLen](#)

8.237.2.2 [BYTE\\* HDRSINRThresh::pHDRSINRThresList](#)

## 8.238 HDRSINRThreshold Struct Reference

### Data Fields

- [BYTE HDRSINRThreshListLen](#)
- [WORD \\* pHDRSINRThreshList](#)

### 8.238.1 Detailed Description

This structure contains HDR SINR threshold related parameters.

#### Parameters

<i>HDRSINR- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the HDR ECIO threshold list parameter to follow</li> </ul>
-----------------------------------	---

<i>pHDRSINR- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of SINR level thresholds (in units of 1)</li> <li>• maximum of 32 values.</li> <li>• Valid levels are 0 to 8 <ul style="list-style-type: none"> <li>– 0x00 - SINR_LEVEL_0 is -9 dB</li> <li>– 0x01 - SINR_LEVEL_1 is -6 dB</li> <li>– 0x02 - SINR_LEVEL_2 is -4.5 dB</li> <li>– 0x03 - SINR_LEVEL_3 is -3 dB</li> <li>– 0x04 - SINR_LEVEL_4 is -2 dB</li> <li>– 0x05 - SINR_LEVEL_5 is +1 dB</li> <li>– 0x06 - SINR_LEVEL_6 is +3 dB</li> <li>– 0x07 - SINR_LEVEL_7 is +6 dB</li> <li>– 0x08 - SINR_LEVEL_8 is +9 dB</li> </ul> </li> </ul>
---------------------------------	--

## 8.238.2 Field Documentation

8.238.2.1 **BYTE** HDRSINRThreshold::HDRSINRThreshListLen

8.238.2.2 **WORD\*** HDRSINRThreshold::pHDRSINRThreshList

## 8.239 HDRSSInfo Struct Reference

### Data Fields

- [INT8 rssi](#)
- [SHORT ecio](#)
- [BYTE sinr](#)
- [INT32 io](#)

### 8.239.1 Detailed Description

This structure contains the parameters for HDR Signal Strength Information

#### Parameters

<i>rssi</i>	<ul style="list-style-type: none"> <li>• RSSI in dBm (signed value).</li> <li>• A value of -125 dBm or lower is used to indicate No Signal.</li> </ul>
<i>ecio</i>	<ul style="list-style-type: none"> <li>• ECIO value representing negative 0.5 dBm increments, i.e., 2 means -1 dBm (14 means -7 dBm, 63 means -31.5 dBm).</li> </ul>

<i>sinr</i>	<ul style="list-style-type: none"> <li>• SINR level.</li> <li>• SINR is only applicable for 1xEV-DO.</li> <li>• Valid levels are 0 to 8, where the maximum value for: <ul style="list-style-type: none"> <li>– 0 - SINR_LEVEL_0 is -9 dB</li> <li>– 1 - SINR_LEVEL_1 is -6 dB</li> <li>– 2 - SINR_LEVEL_2 is -4.5 dB</li> <li>– 3 - SINR_LEVEL_3 is -3 dB</li> <li>– 4 - SINR_LEVEL_4 is -2 dB</li> <li>– 5 - SINR_LEVEL_5 is +1 dB</li> <li>– 6 - SINR_LEVEL_6 is +3 dB</li> <li>– 7 - SINR_LEVEL_7 is +6 dB</li> <li>– 8 - SINR_LEVEL_8 is +9 dB</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>io</i>	<ul style="list-style-type: none"> <li>• Received IO in dBm.</li> <li>• IO is only applicable for 1xEV-DO.</li> </ul>

## 8.239.2 Field Documentation

### 8.239.2.1 SHORT HDRSSInfo::ecio

### 8.239.2.2 INT32 HDRSSInfo::io

### 8.239.2.3 INT8 HDRSSInfo::rssi

### 8.239.2.4 BYTE HDRSSInfo::sinr

## 8.240 hdrSSInfo Struct Reference

### Data Fields

- int8\_t [rssi](#)
- int16\_t [ecio](#)
- uint8\_t [sinr](#)
- int32\_t [io](#)

### 8.240.1 Detailed Description

#### Parameters

<i>rssi</i>	RSSI in dBm.
<i>ecio</i>	ECIO value representing negative 0.5 dBm increment
<i>sinr</i>	SINR level.
<i>io</i>	Received IO in dBm.

### 8.240.2 Field Documentation

8.240.2.1 `int16_t` `hdrSSInfo::ecio`

8.240.2.2 `int32_t` `hdrSSInfo::io`

8.240.2.3 `int8_t` `hdrSSInfo::rssi`

8.240.2.4 `uint8_t` `hdrSSInfo::sinr`

## 8.241 HDRSysInfo Struct Reference

### Data Fields

- [sysInfoCommon sysInfoHDR](#)
- [BYTE isSysPrIMatchValid](#)
- [BYTE isSysPrIMatch](#)
- [BYTE hdrPersonalityValid](#)
- [BYTE hdrPersonality](#)
- [BYTE hdrActiveProtValid](#)
- [BYTE hdrActiveProt](#)
- [BYTE is856SysIdValid](#)
- [BYTE is856SysId](#) [16]

### 8.241.1 Detailed Description

Structure for storing the HDR System Information.

## Parameters

<i>sysInfoHDR</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
<i>isSysPrIMatch-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the system PRL match is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>isSysPrIMatch</i>	<ul style="list-style-type: none"> <li>• Indicates whether the system is in a PRL.</li> <li>• Only applies to CDMA/HDR. <ul style="list-style-type: none"> <li>– 0x00 - System is not in a PRL</li> <li>– 0x01 - System is in a PRL</li> <li>– 0xFF - Not Available</li> </ul> </li> <li>• If the system is not in a PRL, roam_status carries the value from the default roaming indicator in the PRL.</li> <li>• If the system is in a PRL, roam_status is set to the value based on the standard specification.</li> </ul>
<i>hdrPersonality-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the HDR personality is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>hdrPersonality</i>	<ul style="list-style-type: none"> <li>• HDR personality information.</li> <li>• Only applicable for HDR. <ul style="list-style-type: none"> <li>– 0x00 - None</li> <li>– 0x02 - HRPD</li> <li>– 0x03 - eHRPD</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>hdrActiveProtValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the HDR active protocol revision information is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>hdrActiveProt</i>	<ul style="list-style-type: none"> <li>HDR active protocol revision information .</li> <li>Only applicable for HDR. <ul style="list-style-type: none"> <li>0x00 - None</li> <li>0x02 - HDR Rel 0</li> <li>0x03 - HDR Rel A</li> <li>0x04 - HDR Rel B</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>is856SysIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the IS-856 system ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>is856SysId[SLQ-S_SYSTEM_ID_SIZE]</i>	<ul style="list-style-type: none"> <li>IS-856 system ID.</li> <li>Only applicable for HDR.</li> </ul>

## 8.241.2 Field Documentation

8.241.2.1 BYTE HDRSysInfo::hdrActiveProt

8.241.2.2 BYTE HDRSysInfo::hdrActiveProtValid

8.241.2.3 BYTE HDRSysInfo::hdrPersonality

8.241.2.4 BYTE HDRSysInfo::hdrPersonalityValid

8.241.2.5 BYTE HDRSysInfo::is856SysId[16]

8.241.2.6 BYTE HDRSysInfo::is856SysIdValid

8.241.2.7 BYTE HDRSysInfo::isSysPrIMatch

8.241.2.8 BYTE HDRSysInfo::isSysPrIMatchValid

8.241.2.9 sysInfoCommon HDRSysInfo::sysInfoHDR

## 8.242 homeSIDNID Struct Reference

### Data Fields

- [BYTE numInstances](#)
- [sidNid SidNid](#) [255]

### 8.242.1 Detailed Description

This structure contains the parameters for Home SID/NID Information

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"><li>• Number of sets of the following elements:<ul style="list-style-type: none"><li>– sid</li><li>– nid</li></ul></li><li>• If zero(0), then no information follows.</li></ul>
<i>SidNid</i>	<ul style="list-style-type: none"><li>• See <a href="#">sidNid</a> for more information</li></ul>

### 8.242.2 Field Documentation

8.242.2.1 **BYTE** homeSIDNID::numInstances

8.242.2.2 **sidNid** homeSIDNID::SidNid[255]

## 8.243 hotSwapStatus Struct Reference

### Data Fields

- [BYTE hotSwapLength](#)
- [BYTE hotSwap](#) [255]

### 8.243.1 Detailed Description

This structure contains Hot Swap Status Information.



## Parameters

<i>hotSwapLength</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements. i.e. hot_swap</li> </ul>
<i>hotSwap[<a href="#">MAX_DESCRIPTION_LENGTH</a>]</i>	<ul style="list-style-type: none"> <li>• Indicates the status of the hot-swap switch. <ul style="list-style-type: none"> <li>– 0 - Hot-swap is not supported</li> <li>– 1 - Hot-swap is supported, but the status of the switch is not supported</li> <li>– 2 - Switch indicates that the card is present</li> <li>– 3 - Switch indicates that the card is not present</li> </ul> </li> </ul>

## 8.243.2 Field Documentation

8.243.2.1 BYTE hotSwapStatus::hotSwap[255]

8.243.2.2 BYTE hotSwapStatus::hotSwapLength

## 8.244 image\_info\_t Struct Reference

## Data Fields

- [uint8\\_t imageType](#)
- [uint8\\_t uniqueID](#) [16]
- [uint8\\_t buildIDLen](#)
- [uint8\\_t buildID](#) [255]

## 8.244.1 Field Documentation

8.244.1.1 [uint8\\_t image\\_info\\_t::buildID](#)[255]8.244.1.2 [uint8\\_t image\\_info\\_t::buildIDLen](#)8.244.1.3 [uint8\\_t image\\_info\\_t::imageType](#)8.244.1.4 [uint8\\_t image\\_info\\_t::uniqueID](#)[16]

## 8.245 ImageElement Struct Reference

## Data Fields

- [BYTE imageType](#)
- [BYTE imageId](#) [16]
- [BYTE buildIdLength](#)
- [CHAR buildId](#) [100]

## 8.245.1 Detailed Description

push current alignment to stack set alignment to 1 byte boundary This structure contains the Image Element information

## Parameters

<i>imageType</i>	<ul style="list-style-type: none"> <li>• Type of image 0 - Modem 1 - PRI</li> </ul>
<i>imageId</i>	<ul style="list-style-type: none"> <li>• Unique image identifier</li> </ul>
<i>buildIdLength</i>	<ul style="list-style-type: none"> <li>• Length of the build ID string (may be zero)</li> </ul>
<i>buildId</i>	<ul style="list-style-type: none"> <li>• Build ID ANSI string( Max 100 characters )</li> </ul>

## 8.245.2 Field Documentation

8.245.2.1 CHAR ImageElement::buildId[100]

8.245.2.2 BYTE ImageElement::buildIdLength

8.245.2.3 BYTE ImageElement::imageId[16]

8.245.2.4 BYTE ImageElement::imageType

## 8.246 ImageIdElement Struct Reference

## Data Fields

- [BYTE storageIndex](#)
- [BYTE failureCount](#)
- [BYTE imageID \[16\]](#)
- [BYTE buildIDLength](#)
- [CHAR buildID \[100\]](#)

## 8.246.1 Detailed Description

push current alignment to stack set alignment to 1 byte boundary This structure contains the Image ID list element Information

## Parameters

<i>storageIndex</i>	<ul style="list-style-type: none"> <li>• Index in storage where the image is located(a value of 0xFF indicates that the storage for this type of image is not relevant)</li> </ul>
<i>failureCount</i>	<ul style="list-style-type: none"> <li>• Number of consecutive write attempts to this storage index that have failed(a value of 0xFF indicates unspecified)</li> </ul>
<i>imageID</i>	<ul style="list-style-type: none"> <li>• Image unique identifier(max 16 chars.)</li> </ul>
<i>buildIDLength</i>	<ul style="list-style-type: none"> <li>• Length of the build ID string. If there is no build ID, this field will be 0 and no data will follow.</li> </ul>
<i>buildID</i>	<ul style="list-style-type: none"> <li>• String containing image build information( Max 100 characters )</li> </ul>

## 8.246.2 Field Documentation

8.246.2.1 CHAR ImageIDElement::buildID[100]

8.246.2.2 BYTE ImageIDElement::buildIDLength

8.246.2.3 BYTE ImageIDElement::failureCount

8.246.2.4 BYTE ImageIDElement::imageID[16]

8.246.2.5 BYTE ImageIDElement::storageIndex

## 8.247 ImageIDEntries Struct Reference

## Data Fields

- [BYTE imageType](#)
- [BYTE maxImages](#)
- [BYTE executingImage](#)
- [BYTE imageIDSize](#)
- struct [ImageIDElement imageIDElement](#) [50]

## 8.247.1 Detailed Description

This structure contains the list entry Information

## Parameters

<i>imageType</i>	<ul style="list-style-type: none"> <li>Type of image <ul style="list-style-type: none"> <li>0 - Modem</li> <li>1 - PRI</li> </ul> </li> </ul>
<i>maxImages</i>	<ul style="list-style-type: none"> <li>Maximum number of images of this type that may be stored concurrently on the device</li> </ul>
<i>executingImage</i>	<ul style="list-style-type: none"> <li>Index (into the next array) of image that is currently executing</li> </ul>
<i>imageIDSize</i>	<ul style="list-style-type: none"> <li>The number of elements in the image ID list</li> </ul>
<i>imageIDElement</i>	<ul style="list-style-type: none"> <li>Array of ImageIDElement Structure ( Max 50 elements )</li> </ul>

## 8.247.2 Field Documentation

8.247.2.1 BYTE ImageIDEntries::executingImage

8.247.2.2 struct ImageIDElement ImageIDEntries::imageIDElement[50]

8.247.2.3 BYTE ImageIDEntries::imageIDSize

8.247.2.4 BYTE ImageIDEntries::imageType

8.247.2.5 BYTE ImageIDEntries::maxImages

## 8.248 ImageList Struct Reference

## Data Fields

- [BYTE listSize](#)
- struct [ImageIDEntries](#) [imageIDEntries](#) [2]

## 8.248.1 Detailed Description

This structure contains the Get Stored Images List

## Parameters

<i>listSize</i>	<ul style="list-style-type: none"> <li>The number of elements in the image list</li> </ul>
<i>imageIDEntries</i>	<ul style="list-style-type: none"> <li>Array of <a href="#">ImageIDEntries</a> Structure ( Max 2 entries )</li> </ul>

## 8.248.2 Field Documentation

8.248.2.1 struct ImageIDEntries ImageList::imageIDEntries[2]

8.248.2.2 BYTE ImageList::listSize

## 8.249 IMSAIndRegisterInfo Struct Reference

### Data Fields

- [BYTE \\* pRegStatusConfig](#)
- [BYTE \\* pServiceStatusConfig](#)
- [BYTE \\* pRatHandoverStatusConfig](#)
- [BYTE \\* pPdpStatusConfig](#)

### 8.249.1 Detailed Description

This structure contains parameters of IMSA Config Indication Register

#### Parameters

<i>pRegStatus-Config(optional)</i>	<ul style="list-style-type: none"> <li>• Register Indication For Registration status.</li> <li>• When this registration is enabled, the device learns of Registration status via the QMI_IMSA_REGISTRATION_STATUS_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>pServiceStatus-Config(optional)</i>	<ul style="list-style-type: none"> <li>• Register Indication For Service status Events.</li> <li>• When this registration is enabled, the device learns of Service status via the QMI_IMSA_SERVICE_STATUS_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>pRatHandover-Status-Config(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For RAT handover status.</li> <li>• When this registration is enabled, the device learns of RAT handover status via the QMI_IMSA_RAT_HANDOVER_STATUS_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>

<i>pPdpStatus-Config(optional)</i>	<ul style="list-style-type: none"> <li>• PDP Status Configuration. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
------------------------------------	--

**Note**

One of the optional parameter is mandatory to be present in the request.

**8.249.2 Field Documentation**

8.249.2.1 **BYTE\*** IMSAIndRegisterInfo::pPdpStatusConfig

8.249.2.2 **BYTE\*** IMSAIndRegisterInfo::pRatHandoverStatusConfig

8.249.2.3 **BYTE\*** IMSAIndRegisterInfo::pRegStatusConfig

8.249.2.4 **BYTE\*** IMSAIndRegisterInfo::pServiceStatusConfig

**8.250 imsaPdpStatusInfo Struct Reference****Data Fields**

- [BYTE](#) *connetionState*
- [ULONG \\*](#) *pFailErrorCode*

**8.250.1 Detailed Description**

Contains the parameters passed for SLQSSetIMSAPdpStatusCallback by the device.

**Parameters**

<i>connetionState</i>	<ul style="list-style-type: none"> <li>• IMS PDP connection state information.</li> <li>• Values <ul style="list-style-type: none"> <li>– TRUE – IMS PDP is connected</li> <li>– FALSE – IMS PDP is not connected</li> </ul> </li> </ul>
<i>pFailErrorCode</i>	<ul style="list-style-type: none"> <li>• IMS PDP connection failure error reason code when the IMS PDP Connection State TLV is FALSE.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Generic failure reason for other than specified</li> <li>– 1 - Option is unsubscribed.</li> <li>– 2 - PDP status was unknown.</li> </ul> </li> </ul>

### 8.250.2 Field Documentation

8.250.2.1 **BYTE** imsaPdpStatusInfo::connetionState

8.250.2.2 **ULONG\*** imsaPdpStatusInfo::pFailErrorCode

## 8.251 imsaRatStatusInfo Struct Reference

### Data Fields

- **ULONG \*** pRATStatus
- **ULONG \*** pSrcRAT
- **ULONG \*** pTgtRAT
- **BYTE \*** pErrorCodeStr

### 8.251.1 Detailed Description

Contains the parameters passed for SLQSSetIMSAStatusCallback by the device.

#### Parameters

<i>pRATStatus</i>	<ul style="list-style-type: none"> <li>• RAT handover Status</li> </ul>
<i>pSrcRAT</i>	<ul style="list-style-type: none"> <li>• Source RAT</li> </ul>
<i>pTgtRAT</i>	<ul style="list-style-type: none"> <li>• Target RAT</li> </ul>
<i>pErrorCodeStr</i>	<ul style="list-style-type: none"> <li>• Error Code String</li> </ul>

### 8.251.2 Field Documentation

8.251.2.1 **BYTE\*** imsaRatStatusInfo::pErrorCodeStr

8.251.2.2 **ULONG\*** imsaRatStatusInfo::pRATStatus

8.251.2.3 **ULONG\*** imsaRatStatusInfo::pSrcRAT

8.251.2.4 **ULONG\*** imsaRatStatusInfo::pTgtRAT

## 8.252 IMSARegistrationStatus Struct Reference

### Data Fields

- **BYTE \*** plmsRegStatus
- **WORD \*** plmsRegErrCode
- **ULONG \*** pNewImsRegStatus

### 8.252.1 Detailed Description

This structure contains response parameters of registration status.



## Parameters

<i>plmsRegStatus</i>	<ul style="list-style-type: none"> <li>• IMS Registration Status (Deprecated).</li> <li>• Values <ul style="list-style-type: none"> <li>– TRUE - UE is registered on the IMS network</li> <li>– FALSE - UE is not registered on the IMS network</li> </ul> </li> </ul>
<i>plmsRegErr-Code</i>	<ul style="list-style-type: none"> <li>• IMS Registration Error Code.</li> <li>• An error code is returned when the IMS registration status is IMSA_STATUS_NOT_REGISTERED. -Values <ul style="list-style-type: none"> <li>– 3xx – Redirection responses</li> <li>– 4xx – Client failure responses</li> <li>– 5xx – Server failure responses</li> <li>– 6xx – Global failure responses</li> </ul> </li> </ul>
<i>pNewImSReg-Status</i>	<ul style="list-style-type: none"> <li>• New IMS Registration Status</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Not registered for IMS</li> <li>– 1 - Registering for IMS</li> <li>– 2 - Registered for IMS</li> </ul> </li> </ul>

## 8.252.2 Field Documentation

8.252.2.1 WORD\* IMSARegistrationStatus::plmsRegErrCode

8.252.2.2 BYTE\* IMSARegistrationStatus::plmsRegStatus

8.252.2.3 ULONG\* IMSARegistrationStatus::pNewImSRegStatus

## 8.253 imsaRegStatusInfo Struct Reference

## Data Fields

- [BYTE](#) \* [pbIMSRegistered](#)
- [WORD](#) \* [pRegStatusErrorCode](#)
- [ULONG](#) \* [plmsRegStatus](#)

## 8.253.1 Detailed Description

Contains the parameters passed for SLQSSetIMSARegStatusCallback by the device.

## Parameters

<i>pbIMS-Registered</i>	<ul style="list-style-type: none"> <li>• TRUE/FALSE</li> </ul>
<i>pRegStatus-ErrorCode</i>	<ul style="list-style-type: none"> <li>• if IMSA_STATUS_NOT_REGISTERED. Values: 3xx – Redirection responses 4xx – Client failure responses 5xx – Server failure responses 6xx – Global failure responses</li> </ul>
<i>plmsRegStatus</i>	IMS registration status. Values: IMSA_STATUS_NOT_REGISTERED - 0 IMSA_STATUS_REGISTERING - 1 IMSA_STATUS_REGISTERED -2

## 8.253.2 Field Documentation

8.253.2.1 **BYTE\*** `imsaRegStatusInfo::pbIMSRegistered`8.253.2.2 **ULONG\*** `imsaRegStatusInfo::plmsRegStatus`8.253.2.3 **WORD\*** `imsaRegStatusInfo::pRegStatusErrorCode`

## 8.254 IMSAServiceStatus Struct Reference

## Data Fields

- [ULONG \\* pSmsServiceStatus](#)
- [ULONG \\* pVoipServiceStatus](#)
- [ULONG \\* pVtServiceStatus](#)
- [ULONG \\* pSmsServiceRat](#)
- [ULONG \\* pVoipServiceRat](#)
- [ULONG \\* pVtServiceRat](#)
- [ULONG \\* pUtServiceStatus](#)
- [ULONG \\* pUtServiceRat](#)
- [ULONG \\* pVsServiceStatus](#)
- [ULONG \\* pVsServiceRat](#)

## 8.254.1 Detailed Description

This structure contains response parameters of service status for various IMS services.

## Parameters

<i>pSmsService-Status</i>	<ul style="list-style-type: none"> <li>• SMS Service Status.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS SMS service is not available</li> <li>– 1 - IMS SMS is in limited service</li> <li>– 2 - IMS SMS is in full service</li> </ul> </li> </ul>
---------------------------	--

<i>pVoipServiceStatus</i>	<ul style="list-style-type: none"> <li>• VoIP Service Status. -Values <ul style="list-style-type: none"> <li>– 0 - IMS VoIP service is not available</li> <li>– 2 - IMS VoIP is in full service</li> </ul> </li> </ul>
<i>pVtServiceStatus</i>	<ul style="list-style-type: none"> <li>• VT Service Status</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS VT service is not available</li> <li>– 2 - IMS VT is in full service</li> </ul> </li> </ul>
<i>pSmsServiceRat</i>	<ul style="list-style-type: none"> <li>• SMS service RAT</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS service is registered on WLAN</li> <li>– 1 - IMS service is registered on WWAN</li> <li>– 2 - IMS service is registered on interworking WLAN</li> </ul> </li> </ul>
<i>pVoipServiceRat</i>	<ul style="list-style-type: none"> <li>• VoIP service RAT.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS service is registered on WLAN</li> <li>– 1 - IMS service is registered on WWAN</li> <li>– 2 - IMS service is registered on interworking WLAN</li> </ul> </li> </ul>
<i>pVtServiceRat</i>	<ul style="list-style-type: none"> <li>• VT service RAT.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS service is registered on WLAN</li> <li>– 1 - IMS service is registered on WWAN</li> <li>– 2 - IMS service is registered on interworking WLAN</li> </ul> </li> </ul>

<i>pUtService-Status</i>	<ul style="list-style-type: none"> <li>• UT service Status.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS UT service is not available</li> <li>– 2 - IMS UT is in full service</li> </ul> </li> </ul>
<i>pUtServiceRat</i>	<ul style="list-style-type: none"> <li>• UT service RAT.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS service is registered on WLAN</li> <li>– 1 - IMS service is registered on WWAN</li> <li>– 2 - IMS service is registered on interworking WLAN</li> </ul> </li> </ul>
<i>pVsService-Status</i>	<ul style="list-style-type: none"> <li>• VS service Status.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS UT service is not available</li> <li>– 2 - IMS UT is in full service</li> </ul> </li> </ul>
<i>pVsServiceRat</i>	<ul style="list-style-type: none"> <li>• VS service RAT.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - IMS service is registered on WLAN</li> <li>– 1 - IMS service is registered on WWAN</li> <li>– 2 - IMS service is registered on interworking WLAN</li> </ul> </li> </ul>

## 8.254.2 Field Documentation

8.254.2.1 **ULONG\*** IMSAServiceStatus::pSmsServiceRat

8.254.2.2 **ULONG\*** IMSAServiceStatus::pSmsServiceStatus

8.254.2.3 **ULONG\*** IMSAServiceStatus::pUtServiceRat

8.254.2.4 **ULONG\*** IMSAServiceStatus::pUtServiceStatus

8.254.2.5 **ULONG\*** IMSAServiceStatus::pVoipServiceRat

8.254.2.6 **ULONG\*** IMSAServiceStatus::pVoipServiceStatus

8.254.2.7 **ULONG\*** IMSAServiceStatus::pVsServiceRat

8.254.2.8 **ULONG\*** IMSAServiceStatus::pVsServiceStatus

8.254.2.9 **ULONG\*** IMSAServiceStatus::pVtServiceRat

8.254.2.10 **ULONG\*** IMSAServiceStatus::pVtServiceStatus

## 8.255 IMSASupportedFieldsResp Struct Reference

### Data Fields

- struct [ReqFieldsList](#) \* [pReqFieldsList](#)
- struct [RespFieldsList](#) \* [pRespFieldsList](#)
- struct [IndFieldsList](#) \* [pIndFieldsList](#)

### 8.255.1 Detailed Description

This structure contains response of supported fields by the currently running software.

#### Parameters

<i>pReqFieldsList</i>	<ul style="list-style-type: none"> <li>• List of Supported Request Fields.</li> <li>• See <a href="#">ReqFieldsList</a> for more information</li> </ul>
<i>pRespFieldsList</i>	<ul style="list-style-type: none"> <li>• List of Supported Request Fields.</li> <li>• See <a href="#">RespFieldsList</a> for more information</li> </ul>
<i>pIndFieldsList</i>	<ul style="list-style-type: none"> <li>• List of Supported Request Fields.</li> <li>• See <a href="#">IndFieldsList</a> for more information</li> </ul>

### 8.255.2 Field Documentation

8.255.2.1 **struct IndFieldsList\*** IMSASupportedFieldsResp::pIndFieldsList

8.255.2.2 **struct ReqFieldsList\*** IMSASupportedFieldsResp::pReqFieldsList

8.255.2.3 **struct RespFieldsList\*** IMSASupportedFieldsResp::pRespFieldsList

## 8.256 IMSASupportedMsgInfo Struct Reference

### Data Fields

- struct [SupportedMsgList](#) \* [pSupportedMsgList](#)

### 8.256.1 Detailed Description

This structure contains Queries the set of messages implemented by the currently running software.

## Parameters

<i>pSupportedMsgList</i>	<ul style="list-style-type: none"> <li>List of Supported Messages.</li> <li>See <a href="#">SupportedMsgList</a> for more information</li> </ul>
--------------------------	--

## 8.256.2 Field Documentation

8.256.2.1 struct SupportedMsgList\* IMSASupportedMsgInfo::pSupportedMsgList

## 8.257 imsaSvcStatusInfo Struct Reference

## Data Fields

- [ULONG](#) \* [pSMSSvcStatus](#)
- [ULONG](#) \* [pVOIPSvcStatus](#)
- [ULONG](#) \* [pVTSvcStatus](#)
- [ULONG](#) \* [pSMSSvcRAT](#)
- [ULONG](#) \* [pVOIPSvcRAT](#)
- [ULONG](#) \* [pVTSvcRAT](#)
- [ULONG](#) \* [pUTSvcStatus](#)
- [ULONG](#) \* [pUTSvcRAT](#)

## 8.257.1 Detailed Description

Contains the parameters passed for SLQSSetIMSASvcStatusCallback by the device.

## Parameters

<i>pSMSSvcStatus</i>	IMS SMS NOT AVAILABLE - 0 IMS SMS LIMITED SERVICE - 1 IMS SMS FULL SERVICE - 2
<i>pVOIPSvcStatus</i>	IMS VOIP NOT AVAILABLE - 0 IMS SMS FULL SERVICE - 2
<i>pVTSvcStatus</i>	IMS VT NOT AVAILABLE - 0 IMS VT FULL SERVICE - 2
<i>pSMSSvcRAT</i>	IMS service is registered on WLAN - 0 IMS service is registered on WWAN - 1 IMS service is registered on interworking WLAN - 2
<i>pVOIPSvcRAT</i>	IMS service is registered on WLAN - 0 IMS service is registered on WWAN - 1 IMS service is registered on interworking WLAN - 2 *
<i>pVTSvcRAT</i>	IMS service is registered on WLAN - 0 IMS service is registered on WWAN - 1 IMS service is registered on interworking WLAN - 2
<i>pUTSvcStatus</i>	IMS VOIP NOT AVAILABLE - 0 IMS SMS FULL SERVICE - 2
<i>pUTSvcRAT</i>	IMS service is registered on WLAN - 0 IMS service is registered on WWAN - 1 IMS service is registered on interworking WLAN - 2

## 8.257.2 Field Documentation

8.257.2.1 [ULONG](#)\* imsaSvcStatusInfo::pSMSSvcRAT8.257.2.2 [ULONG](#)\* imsaSvcStatusInfo::pSMSSvcStatus8.257.2.3 [ULONG](#)\* imsaSvcStatusInfo::pUTSvcRAT8.257.2.4 [ULONG](#)\* imsaSvcStatusInfo::pUTSvcStatus

8.257.2.5 **ULONG\*** `imsaSvcStatusInfo::pVOIPSvcRAT`8.257.2.6 **ULONG\*** `imsaSvcStatusInfo::pVOIPSvcStatus`8.257.2.7 **ULONG\*** `imsaSvcStatusInfo::pVTSvcRAT`8.257.2.8 **ULONG\*** `imsaSvcStatusInfo::pVTSvcStatus`

## 8.258 imsCfgIndRegisterInfo Struct Reference

### Data Fields

- **BYTE \*** `pSIPConfigEvents`
- **BYTE \*** `pRegMgrConfigEvents`
- **BYTE \*** `pSMSCConfigEvents`
- **BYTE \*** `pUserConfigEvents`
- **BYTE \*** `pVoIPConfigEvents`

### 8.258.1 Detailed Description

This structure contains parameters of IMS Config Indication Register

#### Parameters

<i>pSIPConfigEvents(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For SIP Configuration Events.</li> <li>• When this registration is enabled, the device learns of SIP config events via the QMI_ - IMS_SIP_CONFIG_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>pRegMgrConfigEvents(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For Registration Manager Configuration Events.</li> <li>• When this registration is enabled, the device learns of Reg Mgr config events via the QMI_ IMS_REG_MGR_CONFIG_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>

<i>pSMSConfig-Events(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For SMS Configuration Events.</li> <li>• When this registration is enabled, the device learns of SMS config events via the QMI-IMS_SMS_CONFIG_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>pUserConfig-Events(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For User Configuration Events.</li> <li>• When this registration is enabled, the device learns of user config events via the QMI-IMS_USER_CONFIG_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>pVoIPConfig-Events(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For VoIP Configuration Events.</li> <li>• When this registration is enabled, the device learns of VOIP config events via the QMI-IMS_VOIP_CONFIG_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>

**Note**

One of the optional parameter is mandatory to be present in the request.

**8.258.2 Field Documentation**

8.258.2.1 **BYTE\*** imsCfgIndRegisterInfo::pRegMgrConfigEvents

8.258.2.2 **BYTE\*** imsCfgIndRegisterInfo::pSIPConfigEvents

8.258.2.3 **BYTE\*** imsCfgIndRegisterInfo::pSMSConfigEvents

8.258.2.4 **BYTE\*** imsCfgIndRegisterInfo::pUserConfigEvents

8.258.2.5 **BYTE\*** imsCfgIndRegisterInfo::pVoIPConfigEvents

**8.259 imsRegMgrConfigInfo Struct Reference****Data Fields**

- **WORD \*** pPriCSCFPort
- **BYTE \*** pCSCFPortName
- **BYTE \*** pIMSTestMode



### 8.259.1 Detailed Description

Contains the parameters passed for SLQSSetRegMgrConfigCallback by the device.

## Parameters

<i>pPriCSCFPort</i>	<ul style="list-style-type: none"> <li>Primary call session control function port</li> </ul>
<i>pCSCFPort-Name</i>	<ul style="list-style-type: none"> <li>Call Session control port, fully qualified domain name</li> <li>Length of this string can be of maximum 255 bytes</li> </ul>
<i>pIMSTestMode</i>	<ul style="list-style-type: none"> <li>IMS Test mode Enabled. <ul style="list-style-type: none"> <li>TRUE - Enable, no IMS registration</li> <li>FALSE - Disable, IMS registration is initiated</li> </ul> </li> </ul>

## 8.259.2 Field Documentation

8.259.2.1 **BYTE\*** imsRegMgrConfigInfo::pCSCFPortName8.259.2.2 **BYTE\*** imsRegMgrConfigInfo::pIMSTestMode8.259.2.3 **WORD\*** imsRegMgrConfigInfo::pPriCSCFPort

## 8.260 imsSIPConfigInfo Struct Reference

## Data Fields

- WORD \*** pSIPLocalPort
- ULONG \*** pTimerSIPReg
- ULONG \*** pSubscribeTimer
- ULONG \*** pTimerT1
- ULONG \*** pTimerT2
- ULONG \*** pTimerTf
- BYTE \*** pSigCompEnabled

## 8.260.1 Detailed Description

Contains the parameters passed for SLQSSetSIPConfigCallback by the device.

## Parameters

<i>pSIPLocalPort</i>	<ul style="list-style-type: none"> <li>Primary call session control function SIP port number</li> </ul>
<i>pTimerSIPReg</i>	<ul style="list-style-type: none"> <li>Initial SIP registration duration from the User equipment, in seconds</li> </ul>

<i>pSubscribeTimer</i>	<ul style="list-style-type: none"> <li>Duration of the subscription by the UE for IMS registration notifications, in seconds</li> </ul>
<i>pTimerT1</i>	<ul style="list-style-type: none"> <li>RTT estimate, in milliseconds</li> </ul>
<i>pTimerT2</i>	<ul style="list-style-type: none"> <li>The maximum retransmit interval for non-invite requests and invite responses, in milliseconds</li> </ul>
<i>pTimerTf</i>	<ul style="list-style-type: none"> <li>Non-invite transaction timeout timer, in milliseconds</li> </ul>
<i>pSigCompEnabled</i>	<ul style="list-style-type: none"> <li>Sig Comp Status <ul style="list-style-type: none"> <li>TRUE - Enable</li> <li>FALSE - Disable</li> </ul> </li> </ul>

**Note**

None

**8.260.2 Field Documentation****8.260.2.1** **BYTE\*** **imsSIPConfigInfo::pSigCompEnabled****8.260.2.2** **WORD\*** **imsSIPConfigInfo::pSIPLocalPort****8.260.2.3** **ULONG\*** **imsSIPConfigInfo::pSubscribeTimer****8.260.2.4** **ULONG\*** **imsSIPConfigInfo::pTimerSIPReg****8.260.2.5** **ULONG\*** **imsSIPConfigInfo::pTimerT1****8.260.2.6** **ULONG\*** **imsSIPConfigInfo::pTimerT2****8.260.2.7** **ULONG\*** **imsSIPConfigInfo::pTimerTf****8.261 imsSMSConfigInfo Struct Reference****Data Fields**

- [BYTE \\*](#) [pSMSFormat](#)
- [BYTE \\*](#) [pSMSOverIPNwInd](#)
- [BYTE \\*](#) [pPhoneCtxtURI](#)

**8.261.1 Detailed Description**

Contains the parameters passed for SLQSSetIMSSMSConfigCallback by the device.

## Parameters

<i>pSMSFormat</i>	<ul style="list-style-type: none"> <li>• SMS format <ul style="list-style-type: none"> <li>– 0 - 3GPP</li> <li>– 1 - 3GPP2</li> </ul> </li> </ul>
<i>pSMSOverIPNwInd</i>	<ul style="list-style-type: none"> <li>• SMS over IP Network Indication Flag <ul style="list-style-type: none"> <li>– TRUE - Mobile-Originated(MO) SMS turned on</li> <li>– FALSE - MO SMS turned off</li> </ul> </li> </ul>
<i>pPhoneCtxtURI</i>	<ul style="list-style-type: none"> <li>• Phone context universal resource identifier</li> <li>• Length of this string can be of maximum 255 bytes</li> </ul>

## 8.261.2 Field Documentation

8.261.2.1 **BYTE\*** imsSMSConfigInfo::pPhoneCtxtURI8.261.2.2 **BYTE\*** imsSMSConfigInfo::pSMSFormat8.261.2.3 **BYTE\*** imsSMSConfigInfo::pSMSOverIPNwInd

## 8.262 imsUserConfigInfo Struct Reference

## Data Fields

- **BYTE \*** [pIMSDomain](#)

## 8.262.1 Detailed Description

Contains the parameters passed for SLQSSetIMSUserConfigCallback by the device.

## Parameters

<i>pIMSDomain</i>	<ul style="list-style-type: none"> <li>• IMS domain name</li> <li>• Length of this string can be of maximum 255 bytes</li> </ul>
-------------------	--

## 8.262.2 Field Documentation

8.262.2.1 **BYTE\*** imsUserConfigInfo::pIMSDomain

## 8.263 imsVoIPConfigInfo Struct Reference

## Data Fields

- WORD \* pSessionExpiryTimer
- WORD \* pMinSessionExpiryTimer
- BYTE \* pAmrWbEnable
- BYTE \* pScrAmrEnable
- BYTE \* pScrAmrWbEnable
- BYTE \* pAmrMode
- WORD \* pAmrWBMode
- BYTE \* pAmrOctetAligned
- BYTE \* pAmrWBOctetAligned
- WORD \* pRingingTimer
- WORD \* pRingBackTimer
- WORD \* pRTPRTCPInactTimer

## 8.263.1 Detailed Description

Contains the parameters passed for SLQSSetIMSVoIPConfigCallback by the device.

## Parameters

<i>pSessionExpiryTimer</i>	<ul style="list-style-type: none"> <li>• Session duration, in seconds</li> </ul>
<i>pMinSessionExpiryTimer</i>	<ul style="list-style-type: none"> <li>• Minimum allowed value for session expiry timer, in seconds</li> </ul>
<i>pAmrWbEnable</i>	<ul style="list-style-type: none"> <li>• Flag to enable/disable Adaptive Multirate Codec(AMR) WideBand(WB) audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Enabled</li> <li>– False - Disabled</li> </ul> </li> </ul>
<i>pScrAmrEnable</i>	<ul style="list-style-type: none"> <li>• Flag to enable/disable Source Control Rate(SCR) for AMR NarrowBand (NB)</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Enabled</li> <li>– False - Disabled</li> </ul> </li> </ul>
<i>pScrAmrWbEnable</i>	<ul style="list-style-type: none"> <li>• Flag to enable/disable SCR for AMR WB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Enabled</li> <li>– False - Disabled</li> </ul> </li> </ul>

<i>pAmrMode</i>	<ul style="list-style-type: none"> <li>• BitMask for AMR NB modes allowed</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x1 - 4.75 kbps</li> <li>– 0x2 - 5.15 kbps</li> <li>– 0x4 - 5.9 kbps</li> <li>– 0x8 - 6.17 kbps</li> <li>– 0x10 - 7.4 kbps</li> <li>– 0x20 - 7.95 kbps</li> <li>– 0x40 - 10.2 kbps</li> <li>– 0x80 - 12.2 kbps</li> </ul> </li> </ul>
<i>pAmrWBMode</i>	<ul style="list-style-type: none"> <li>• BitMask for AMR WB modes allowed</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x1 - 6.60 kbps</li> <li>– 0x2 - 8.85 kbps</li> <li>– 0x4 - 12.65 kbps</li> <li>– 0x8 - 14.25 kbps</li> <li>– 0x10 - 15.85 kbps</li> <li>– 0x20 - 18.25 kbps</li> <li>– 0x40 - 19.85 kbps</li> <li>– 0x80 - 23.05 kbps</li> <li>– 0x100 - 23.85 kbps</li> </ul> </li> </ul>
<i>pAmrOctet-Aligned</i>	<ul style="list-style-type: none"> <li>• Flag to indicate if the octet is aligned for AMR NB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Aligned</li> <li>– False - Not aligned, Bandwidth Efficient mode</li> </ul> </li> </ul>
<i>pAmrWBOctet-Aligned</i>	<ul style="list-style-type: none"> <li>• Flag to indicate if the octet is aligned for AMR WB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Aligned</li> <li>– False - Not aligned, Bandwidth Efficient mode</li> </ul> </li> </ul>

<i>pRingingTimer</i>	<ul style="list-style-type: none"> <li>Duration of ringing timer, in seconds. The ringing timer starts on the ringing event. If the call is not answered within the duration of this timer, the call is disconnected.</li> </ul>
<i>pRingBackTimer</i>	<ul style="list-style-type: none"> <li>Duration of ringback timer, in seconds. The ringback timer starts on the ringback event. If the call is not answered within the duration of this timer, the call is disconnected.</li> </ul>
<i>pRTPRTCP-InactTimer</i>	<ul style="list-style-type: none"> <li>Duration of RTP/RTCP inactivity timer, in seconds. If no RTP/RTCP packet is received prior to the expiry of this timer, the call is disconnected.</li> </ul>

## 8.263.2 Field Documentation

8.263.2.1 **BYTE\*** `imsVoIPConfigInfo::pAmrMode`

8.263.2.2 **BYTE\*** `imsVoIPConfigInfo::pAmrOctetAligned`

8.263.2.3 **BYTE\*** `imsVoIPConfigInfo::pAmrWbEnable`

8.263.2.4 **WORD\*** `imsVoIPConfigInfo::pAmrWBMode`

8.263.2.5 **BYTE\*** `imsVoIPConfigInfo::pAmrWBOctetAligned`

8.263.2.6 **WORD\*** `imsVoIPConfigInfo::pMinSessionExpiryTimer`

8.263.2.7 **WORD\*** `imsVoIPConfigInfo::pRingBackTimer`

8.263.2.8 **WORD\*** `imsVoIPConfigInfo::pRingingTimer`

8.263.2.9 **WORD\*** `imsVoIPConfigInfo::pRTPRTCPInactTimer`

8.263.2.10 **BYTE\*** `imsVoIPConfigInfo::pScrAmrEnable`

8.263.2.11 **BYTE\*** `imsVoIPConfigInfo::pScrAmrWbEnable`

8.263.2.12 **WORD\*** `imsVoIPConfigInfo::pSessionExpiryTimer`

## 8.264 IndFieldsList Struct Reference

### Data Fields

- [BYTE](#) `indicationFieldsLen`
- [BYTE](#) `indicationFields` [256]

### 8.264.1 Detailed Description

This structure contains the Supported Indication Fields List Information

## Parameters

<i>indicationFieldsLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the indication fields.</li> </ul>
<i>indicationFields</i>	<ul style="list-style-type: none"> <li>• Describes which optional field IDs are supported in QMI indication.</li> <li>• Format is same as request field.</li> </ul>

## 8.264.2 Field Documentation

8.264.2.1 BYTE IndFieldsList::indicationFields[256]

8.264.2.2 BYTE IndFieldsList::indicationFieldsLen

## 8.265 infoInterFreq Struct Reference

## Data Fields

- [WORD earfcn](#)
- [BYTE threshXLow](#)
- [BYTE threshXHigh](#)
- [BYTE cell\\_resel\\_priority](#)
- [BYTE cells\\_len](#)
- [cellParams cellInterFreqParams](#) [255]

## 8.265.1 Detailed Description

This structure contains information about the inter-frequency.

## Parameters

<i>earfcn</i>	<ul style="list-style-type: none"> <li>• E-UTRA absolute radio frequency channel number of the serving cell.</li> <li>• Range: 0 to 65535.</li> </ul>
<i>threshXLow</i>	<ul style="list-style-type: none"> <li>• Cell Srxlev low threshold.</li> <li>• Range: 0 to 31.</li> <li>• When the serving cell does not exceed thresh_serving_low, the value of an evaluated cell must be smaller than this value to be considered for re-selection.</li> </ul>



<i>threshXHigh</i>	<ul style="list-style-type: none"> <li>• Cell Srxlev high threshold.</li> <li>• Range: 0 to 31.</li> <li>• When the serving cell exceeds thresh_serving_low, the value of an evaluated cell must be greater than this value to be considered for re-selection.</li> </ul>
<i>cell_resel_priority</i>	<ul style="list-style-type: none"> <li>• Cell re-selection priority</li> <li>• Range: 0 to 7.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>
<i>cells_len</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of cell params.</li> </ul>
<i>cellInterFreqParams[MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">cellParams</a> for more information.</li> </ul>

## 8.265.2 Field Documentation

8.265.2.1 **BYTE** infoInterFreq::cell\_resel\_priority

8.265.2.2 **cellParams** infoInterFreq::cellInterFreqParams[255]

8.265.2.3 **BYTE** infoInterFreq::cells\_len

8.265.2.4 **WORD** infoInterFreq::earfcn

8.265.2.5 **BYTE** infoInterFreq::threshXHigh

8.265.2.6 **BYTE** infoInterFreq::threshXLow

## 8.266 IOTresh Struct Reference

### Data Fields

- [BYTE](#) IOTreshListLen
- [INT32](#) \* pIOTreshList

### 8.266.1 Detailed Description

This structure contains IO threshold related parameters.

#### Parameters

<i>IOTreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the LTE SNR threshold list parameter to follow</li> </ul>
-----------------------	--

<i>plIOThresList</i>	<ul style="list-style-type: none"> <li>• Sequence of thresholds delimiting IO event reporting bands</li> <li>• Every time a new IO value crosses a threshold value, an event report indication message with the new IO value is sent to the requesting control point. For this field <ul style="list-style-type: none"> <li>– IO is applicable only for HDR</li> <li>– Each IO threshold value is a signed 4 byte value</li> <li>– Maximum number of threshold values is 16</li> <li>– At least one value must be specified</li> </ul> </li> </ul>
----------------------	--

## 8.266.2 Field Documentation

8.266.2.1 BYTE IOThresh::IOThresListLen

8.266.2.2 INT32\* IOThresh::plIOThresList

## 8.267 IPv4Addr Struct Reference

### Data Fields

- [ULONG addr](#)
- [ULONG subnetMask](#)

### 8.267.1 Detailed Description

This structure contains the IPv4 filter address

#### Parameters

<i>addr</i>	IPv4 address
<i>subnetMask</i>	A packet matches if: <ul style="list-style-type: none"> <li>• (addr and subnetMask) == (IP pkt addr &amp; subnetMask) Callers to set up a filter with a range of source addresses, if needed; subnet mask of all 1s (255.255.255.255) specifies a single address value</li> </ul>

## 8.267.2 Field Documentation

8.267.2.1 ULONG IPv4Addr::addr

8.267.2.2 ULONG IPv4Addr::subnetMask

## 8.268 IPv6Addr Struct Reference

### Data Fields

- [BYTE addr](#) [16]
- [BYTE prefixLen](#)

### 8.268.1 Detailed Description

This structure contains the IPv6 filter address

## Parameters

<i>addr</i>	IPv6 address (in network byte order); this is a 16-byte byte array (in Big-endian format)
<i>prefixLen</i>	IPv6 filter prefix length; can take a value between 0 and 128 Note: A packet matches if the IPv6 source address bytes until the prefix lengths are equal. Therefore prefix length can be used to set a filter with a range of source addresses. A prefix length of 128 specifies a single address value.

## 8.268.2 Field Documentation

8.268.2.1 BYTE IPv6Addr::addr[16]

8.268.2.2 BYTE IPv6Addr::prefixLen

## 8.269 IPV6AddressInfo Struct Reference

## Data Fields

- [BYTE IPV6PrefixLen](#)
- [USHORT IPAddressV6](#) [8]

## 8.269.1 Detailed Description

This structure contains the IPV6 Address Information

## Parameters

<i>IPV6PrefixLen</i>	<ul style="list-style-type: none"> <li>• Length of the received IPv6 address in no. of bits; can take value between 0 and 128 – 0xFF - Not Available</li> </ul>
<i>IPAddressV6</i>	<ul style="list-style-type: none"> <li>• IPv6 address(in network byte order); This is an 8-element array of 16 bit numbers, each of which is in big endian format.</li> </ul>

## 8.269.2 Field Documentation

8.269.2.1 USHORT IPV6AddressInfo::IPAddressV6[8]

8.269.2.2 BYTE IPV6AddressInfo::IPV6PrefixLen

## 8.270 ipv6AddressInfo Struct Reference

## Data Fields

- [uint8\\_t IPV6PrefixLen](#)
- [uint16\\_t IPAddressV6](#) [8]

## 8.270.1 Detailed Description

## Parameters

<i>IPv6PrefixLen</i>	Length of the received IPv6 address
<i>IPAddressV6</i>	IPv6 address(in network byte order)

## 8.270.2 Field Documentation

8.270.2.1 uint16\_t ipv6AddressInfo::IPAddressV6[8]

8.270.2.2 uint8\_t ipv6AddressInfo::IPv6PrefixLen

## 8.271 IPV6GWAddressInfo Struct Reference

## Data Fields

- [BYTE](#) gwV6PrefixLen
- [USHORT](#) gwAddressV6 [8]

## 8.271.1 Detailed Description

This structure contains the IPV6 Gateway Address Information

## Parameters

<i>gwV6PrefixLen</i>	<ul style="list-style-type: none"> <li>• Length of the received IPv6 Gateway address in no. of bits; can take value between 0 and 128</li> </ul>
<i>IPAddressV6</i>	<ul style="list-style-type: none"> <li>• IPv6 Gateway address(in network byte order); This is an 8-element array of 16 bit numbers, each of which is in big endian format.</li> </ul>

## 8.271.2 Field Documentation

8.271.2.1 USHORT IPV6GWAddressInfo::gwAddressV6[8]

8.271.2.2 BYTE IPV6GWAddressInfo::gwV6PrefixLen

## 8.272 IPv6TrafCls Struct Reference

## Data Fields

- [BYTE](#) val
- [BYTE](#) mask

## 8.272.1 Detailed Description

This structure contains the IPv6 filter traffic class

## Parameters

<i>val</i>	The traffic class value
<i>mask</i>	<p>The packet matches the traffic class filter if: (IPv6_filter_traffic_class_val and IPv6_filter_traffic_class_mask) == (Traffic class value in the IP packet &amp; IPv6_filter_traffic_class_mask)</p> <p>Example:</p> <ul style="list-style-type: none"> <li>IPv6_filter_tc_val = 00101000</li> <li>IPv6_filter_tc_mask = 11111100 Filter will compare only the first 6 bits in IPv6_filter_traffic_class with the first 6 bits in the traffic class field of the IP packet; first 6 bits in the traffic class field of the IP packet must be 001010 to match filter; last 2 bits can be anything, since they are ignored by filtering</li> </ul>

## 8.272.2 Field Documentation

## 8.272.2.1 BYTE IPv6TrafCls::mask

## 8.272.2.2 BYTE IPv6TrafCls::val

## 8.273 LibPackGPRSRequestedQoS Struct Reference

## Data Fields

- uint32\_t [precedenceClass](#)
- uint32\_t [delayClass](#)
- uint32\_t [reliabilityClass](#)
- uint32\_t [peakThroughputClass](#)
- uint32\_t [meanThroughputClass](#)

## 8.273.1 Detailed Description

This structure contains the GPRS Quality Of Service Information

## Parameters

<i>precedence-Class</i>	<ul style="list-style-type: none"> <li>• Precedence class</li> </ul>
<i>delayClass</i>	<ul style="list-style-type: none"> <li>• Delay class</li> </ul>
<i>reliabilityClass</i>	<ul style="list-style-type: none"> <li>• Reliability class</li> </ul>
<i>peak-Throughput-Class</i>	<ul style="list-style-type: none"> <li>• Peak throughput class</li> </ul>
<i>mean-Throughput-Class</i>	<ul style="list-style-type: none"> <li>• Mean throughput class</li> </ul>

## 8.273.2 Field Documentation

- 8.273.2.1 `uint32_t LibPackGPRSRequestedQoS::delayClass`
- 8.273.2.2 `uint32_t LibPackGPRSRequestedQoS::meanThroughputClass`
- 8.273.2.3 `uint32_t LibPackGPRSRequestedQoS::peakThroughputClass`
- 8.273.2.4 `uint32_t LibPackGPRSRequestedQoS::precedenceClass`
- 8.273.2.5 `uint32_t LibPackGPRSRequestedQoS::reliabilityClass`

## 8.274 LibpackProfile3GPP Struct Reference

### Data Fields

- `uint8_t * pProfilename`
- `uint16_t * pProfilenameSize`
- `uint8_t * pPDType`
- `uint8_t * pPdpHdrCompType`
- `uint8_t * pPdpDataCompType`
- `uint8_t * pAPNName`
- `uint16_t * pAPNnameSize`
- `uint32_t * pPriDNSIPv4AddPref`
- `uint32_t * pSecDNSIPv4AddPref`
- `LibPackUMTSQoS * pUMTSReqQoS`
- `LibPackUMTSQoS * pUMTSMInQoS`
- `LibPackGPRSRequestedQoS * pGPRSRequestedQoS`
- `LibPackGPRSRequestedQoS * pGPRSMInQoS`
- `uint8_t * pUsername`
- `uint16_t * pUsernameSize`
- `uint8_t * pPassword`
- `uint16_t * pPasswordSize`
- `uint8_t * pAuthenticationPref`
- `uint32_t * pIPv4AddrPref`
- `uint8_t * pPcscfAddrUsingPCO`
- `uint8_t * pPdpAccessConFlag`
- `uint8_t * pPcscfAddrUsingDhcp`
- `uint8_t * pImCnFlag`
- `LibPackTFTIDParams * pTFTID1Params`
- `LibPackTFTIDParams * pTFTID2Params`
- `uint8_t * pPdpContext`
- `uint8_t * pSecondaryFlag`
- `uint8_t * pPrimaryID`
- `uint16_t * pIPv6AddPref`
- `LibPackUMTSReqQoSSigInd * pUMTSReqQoSSigInd`
- `LibPackUMTSReqQoSSigInd * pUMTSMInQoSsigInd`
- `uint16_t * pPriDNSIPv6addpref`
- `uint16_t * pSecDNSIPv6addpref`
- `uint8_t * pAddrAllocPref`
- `LibPackQoSClassID * pQoSClassID`
- `uint8_t * pAPNDisabledFlag`
- `uint32_t * pPDNInactivTimeout`
- `uint8_t * pAPNClass`

### 8.274.1 Detailed Description



## Parameters

<i>extended</i>	error
<i>profile</i>	<p>info This structure contains Input parameters of SLQSCreateProfile and SLQSModifyProfile and output parameters of SLQSGetProfileSettings</p> <ul style="list-style-type: none"> <li>Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.</li> </ul>
<i>pProfileName</i>	<ul style="list-style-type: none"> <li>One or more uint8_ts describing the profile</li> </ul>
<i>pProfilename-Size;</i>	<ul style="list-style-type: none"> <li>This parameter is an input parameter and should be initialised to the size of pProfile-Name field. Size of this parameter is 2 uint8_ts.</li> </ul>
<i>pPDPTYPE</i>	<ul style="list-style-type: none"> <li>Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile <ul style="list-style-type: none"> <li>0x00 - PDP-IP (IPv4)</li> <li>0x01 - PDP-PPP</li> <li>0x02 - PDP-IPV6</li> <li>0x03 - PDP-IPV4V6</li> </ul> </li> </ul>
<i>pPdpHdrComp-Type</i>	<ul style="list-style-type: none"> <li>PDP header compression type <ul style="list-style-type: none"> <li>0 - PDP header compression is OFF</li> <li>1 - Manufacturer preferred compression</li> <li>2 - PDP header compression based on RFC 1144</li> <li>3 - PDP header compression based on RFC 25074 PDP header compression based on RFC 3095</li> </ul> </li> </ul>
<i>pPdpDataComp-Type</i>	<ul style="list-style-type: none"> <li>PDP data compression type <ul style="list-style-type: none"> <li>0 - PDP data compression is OFF</li> <li>1 - Manufacturer preferred compression</li> <li>2 - V.42BIS data compression</li> <li>3 - V.44 data compression</li> </ul> </li> </ul>

<i>pAPNName</i>	<ul style="list-style-type: none"> <li>• Access point name</li> </ul>
<i>pAPNnameSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pAPN-Name field. Size of this parameter is 2 uint8_ts.</li> </ul>
<i>pPriDNSIPv4-AddPref</i>	<ul style="list-style-type: none"> <li>• Primary DNS IPv4 Address Preference</li> </ul>
<i>pSecDNSIPv4-AddPref</i>	<ul style="list-style-type: none"> <li>• Secondary DNS IPv4 Address Preference</li> </ul>
<i>pUMTSReqQoS</i>	<ul style="list-style-type: none"> <li>• UMTS Requested QoS</li> </ul>
<i>pUMTSMinQoS</i>	<ul style="list-style-type: none"> <li>• UMTS Minimum QoS</li> </ul>
<i>pGPRS-RequestedQoS</i>	<ul style="list-style-type: none"> <li>• GPRS Minimum QoS</li> </ul>
<i>pUsername</i>	<ul style="list-style-type: none"> <li>• User name</li> </ul>
<i>pUsernameSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pUsername field. Size of this parameter is 2 uint8_ts.</li> </ul>
<i>pPassword</i>	<ul style="list-style-type: none"> <li>• Password</li> </ul>
<i>pPasswordSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pPassword field. Size of this parameter is 2 uint8_ts.</li> </ul>
<i>pAuthentication-Pref</i>	<ul style="list-style-type: none"> <li>• Authentication Preference <ul style="list-style-type: none"> <li>– Bit map that indicates the authentication algorithm preference <ul style="list-style-type: none"> <li>* Bit 0 - PAP preference <ul style="list-style-type: none"> <li>• 0 - PAP is never performed</li> <li>• 1 - PAP may be performed</li> </ul> </li> <li>* Bit 1 - CHAP preference <ul style="list-style-type: none"> <li>• 0 - CHAP is never performed</li> <li>• 1 - CHAP may be performed</li> </ul> </li> <li>* If more than one bit is set, then the device decides which authentication procedure is performed while setting up the data session. For example, the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul> </li> </ul>

<i>pIPv4AddrPref</i>	<ul style="list-style-type: none"> <li>• IPv4 Address Preference</li> </ul>
<i>pPcscfAddr-UsingPCO</i>	<ul style="list-style-type: none"> <li>• P-CSCF Address using PCO Flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies request PCSCF address using PCO</li> <li>– 0 - (FALSE) implies do not request By default, this value is 0</li> </ul> </li> </ul>
<i>pPdpAccess-ConFlag</i>	<ul style="list-style-type: none"> <li>• PDP access control flag <ul style="list-style-type: none"> <li>– 0 - PDP access control none</li> <li>– 1 - PDP access control reject</li> <li>– 2 - PDP access control permission</li> </ul> </li> </ul>
<i>pPcscfAddr-UsingDhcp</i>	<ul style="list-style-type: none"> <li>• P-CSCF address using DHCP <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies Request PCSCF address using DHCP</li> <li>– 0 - (FALSE) implies do not request By default, value is 0</li> </ul> </li> </ul>
<i>plmCnFlag</i>	<ul style="list-style-type: none"> <li>• IM CN flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies request IM CN flag for this profile</li> <li>– 0 - (FALSE) implies do not request IM CN flag for this profile</li> </ul> </li> </ul>
<i>pTFTID1Params</i>	<ul style="list-style-type: none"> <li>• Traffic Flow Template</li> </ul>
<i>pTFTID2Params</i>	<ul style="list-style-type: none"> <li>• Traffic Flow Template</li> </ul>
<i>pPdpContext</i>	<ul style="list-style-type: none"> <li>• PDP context number</li> </ul>
<i>pSecondaryFlag</i>	<ul style="list-style-type: none"> <li>• PDP context secondary flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies this is secondary profile</li> <li>– 0 - (FALSE) implies this is not secondary profile</li> </ul> </li> </ul>
<i>pPrimaryID</i>	<ul style="list-style-type: none"> <li>• PDP context primary ID</li> <li>• function <a href="#">SLQSGetProfileSettings()</a> returns a default value 0xFF if this parameter is not returned by the device</li> </ul>

<i>pIPv6AddPref</i>	<ul style="list-style-type: none"> <li>IPv6 address preference Preferred IPv6 address to be assigned to the TE; actual assigned address is negotiated with the network and may differ from this value; if not specified, the IPv6 address is obtained automatically from the network</li> </ul>
<i>pUMTSReqQoS-SigInd</i>	<ul style="list-style-type: none"> <li>UMTS requested QoS with Signalling Indication flag</li> </ul>
<i>pUMTSMinQoS-SigInd</i>	<ul style="list-style-type: none"> <li>UMTS minimum QoS with Signalling Indication flag</li> </ul>
<i>pPrimaryDNSIPv6addpref</i>	<ul style="list-style-type: none"> <li>Primary DNS IPv6 address preference <ul style="list-style-type: none"> <li>The value may be used as a preference during negotiation with the network; if not specified, the wireless device will attempt to obtain the DNS address automatically from the network; the negotiated value is provided to the host via DHCP</li> </ul> </li> </ul>
<i>pSecondaryDNSIPv6addpref</i>	<ul style="list-style-type: none"> <li>Secondary DNS IPv6 address preference</li> </ul>
<i>paddrAllocation-Pref</i>	<ul style="list-style-type: none"> <li>DHCP/NAS preference <ul style="list-style-type: none"> <li>This enumerated value may be used to indicate the address allocation preference <ul style="list-style-type: none"> <li>* 0 - NAS signaling is used for address allocation</li> <li>* 1 - DHCP is used for address allocation</li> </ul> </li> </ul> </li> </ul>
<i>pQoSClassID</i>	<ul style="list-style-type: none"> <li>3GPP LTE QoS parameters</li> </ul>
<i>pAPNDisabled-Flag</i>	<ul style="list-style-type: none"> <li>Optional 1 uint8_t Flag indicating if the APN is disabled/enabled</li> <li>If set, the profile can not be used for making data calls</li> <li>Any data call is failed locally</li> <li>Values: <ul style="list-style-type: none"> <li>0 - FALSE(default)</li> <li>1 - True</li> </ul> </li> <li>This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

<i>pPDNInactiv-Timeout</i>	<ul style="list-style-type: none"> <li>• Optional 4 uint8_ts indicating the duration of inactivity timer in seconds</li> <li>• If the PDP context/PDN connection is inactive for this duration i.e. No data Tx/Rx occurs, the PDP context/PDN connection is disconnected</li> <li>• Default value of zero indicates infinite value</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pAPNClass</i>	<ul style="list-style-type: none"> <li>• Optional 1 uint8_t numeric identifier representing the APN in profile</li> <li>• Can be set and queried but is not used by the modem</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

## 8.274.2 Field Documentation

8.274.2.1 uint8\_t\* LibpackProfile3GPP::pAddrAllocPref

8.274.2.2 uint8\_t\* LibpackProfile3GPP::pAPNClass

8.274.2.3 uint8\_t\* LibpackProfile3GPP::pAPNDisabledFlag

8.274.2.4 uint8\_t\* LibpackProfile3GPP::pAPNName

8.274.2.5 uint16\_t\* LibpackProfile3GPP::pAPNNameSize

8.274.2.6 uint8\_t\* LibpackProfile3GPP::pAuthenticationPref

8.274.2.7 LibPackGPRSRequestedQoS\* LibpackProfile3GPP::pGPRSMinimumQoS

8.274.2.8 LibPackGPRSRequestedQoS\* LibpackProfile3GPP::pGPRSRequestedQoS

8.274.2.9 uint8\_t\* LibpackProfile3GPP::pImCnFlag

8.274.2.10 uint32\_t\* LibpackProfile3GPP::pIPv4AddrPref

8.274.2.11 uint16\_t\* LibpackProfile3GPP::pIPv6AddPref

8.274.2.12 uint8\_t\* LibpackProfile3GPP::pPassword

8.274.2.13 uint16\_t\* LibpackProfile3GPP::pPasswordSize

8.274.2.14 uint8\_t\* LibpackProfile3GPP::pPcscfAddrUsingDhcp

8.274.2.15 uint8\_t\* LibpackProfile3GPP::pPcscfAddrUsingPCO

8.274.2.16 uint32\_t\* LibpackProfile3GPP::pPDNInactivTimeout

8.274.2.17 uint8\_t\* LibpackProfile3GPP::pPdpAccessConFlag

- 8.274.2.18 `uint8_t*` `LibpackProfile3GPP::pPdpContext`
- 8.274.2.19 `uint8_t*` `LibpackProfile3GPP::pPdpDataCompType`
- 8.274.2.20 `uint8_t*` `LibpackProfile3GPP::pPdpHdrCompType`
- 8.274.2.21 `uint8_t*` `LibpackProfile3GPP::pPDPTtype`
- 8.274.2.22 `uint32_t*` `LibpackProfile3GPP::pPriDNSIPv4AddPref`
- 8.274.2.23 `uint16_t*` `LibpackProfile3GPP::pPriDNSIPv6addpref`
- 8.274.2.24 `uint8_t*` `LibpackProfile3GPP::pPrimaryID`
- 8.274.2.25 `uint8_t*` `LibpackProfile3GPP::pProfilename`
- 8.274.2.26 `uint16_t*` `LibpackProfile3GPP::pProfilenameSize`
- 8.274.2.27 `LibPackQosClassID*` `LibpackProfile3GPP::pQosClassID`
- 8.274.2.28 `uint32_t*` `LibpackProfile3GPP::pSecDNSIPv4AddPref`
- 8.274.2.29 `uint16_t*` `LibpackProfile3GPP::pSecDNSIPv6addpref`
- 8.274.2.30 `uint8_t*` `LibpackProfile3GPP::pSecondaryFlag`
- 8.274.2.31 `LibPackTFTIDParams*` `LibpackProfile3GPP::pTFTID1Params`
- 8.274.2.32 `LibPackTFTIDParams*` `LibpackProfile3GPP::pTFTID2Params`
- 8.274.2.33 `LibPackUMTSQoS*` `LibpackProfile3GPP::pUMTSMinQoS`
- 8.274.2.34 `LibPackUMTSReqQoSSigInd*` `LibpackProfile3GPP::pUMTSMinQoSsigInd`
- 8.274.2.35 `LibPackUMTSQoS*` `LibpackProfile3GPP::pUMTSReqQoS`
- 8.274.2.36 `LibPackUMTSReqQoSSigInd*` `LibpackProfile3GPP::pUMTSReqQoSSigInd`
- 8.274.2.37 `uint8_t*` `LibpackProfile3GPP::pUsername`
- 8.274.2.38 `uint16_t*` `LibpackProfile3GPP::pUsernameSize`

## 8.275 LibpackProfile3GPP2 Struct Reference

### Data Fields

- `uint8_t *` [pNegoDnsSrvrPref](#)
- `uint32_t *` [pPppSessCloseTimerDO](#)
- `uint32_t *` [pPppSessCloseTimer1x](#)
- `uint8_t *` [pAllowLinger](#)
- `uint16_t *` [pLcpAckTimeout](#)
- `uint16_t *` [pIpcpAckTimeout](#)
- `uint16_t *` [pAuthTimeout](#)
- `uint8_t *` [pLcpCreqRetryCount](#)
- `uint8_t *` [pIpcpCreqRetryCount](#)

- uint8\_t \* [pAuthRetryCount](#)
- uint8\_t \* [pAuthProtocol](#)
- uint8\_t \* [pUserId](#)
- uint16\_t \* [pUserIdSize](#)
- uint8\_t \* [pAuthPassword](#)
- uint16\_t \* [pAuthPasswordSize](#)
- uint8\_t \* [pDataRate](#)
- uint32\_t \* [pAppType](#)
- uint8\_t \* [pDataMode](#)
- uint8\_t \* [pAppPriority](#)
- uint8\_t \* [pApnString](#)
- uint16\_t \* [pApnStringSize](#)
- uint8\_t \* [pPdnType](#)
- uint8\_t \* [pIsPcscfAddressNedded](#)
- uint32\_t \* [pPrimaryV4DnsAddress](#)
- uint32\_t \* [pSecondaryV4DnsAddress](#)
- uint16\_t \* [pPriV6DnsAddress](#)
- uint16\_t \* [pSecV6DnsAddress](#)
- uint8\_t \* [pRATType](#)
- uint8\_t \* [pAPNEnabled3GPP2](#)
- uint32\_t \* [pPDNInactivTimeout3GPP2](#)
- uint8\_t \* [pAPNClass3GPP2](#)

### 8.275.1 Detailed Description

This structure contains the 3GPP2 profile parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>pNegoDnsSrvr-Pref</i>	<ul style="list-style-type: none"> <li>• Negotiate DNS Server Preference             <ul style="list-style-type: none"> <li>– 1 - (TRUE)implies request DNS addresses from the PDSN</li> <li>– 0 - (FALSE)implies do not request DNS addresses from the PDSN</li> <li>– Default value is 1 (TRUE)</li> </ul> </li> </ul>
<i>pPppSessClose-TimerDO</i>	<ul style="list-style-type: none"> <li>• PPP Session Close Timer for DO             <ul style="list-style-type: none"> <li>– Timer value (in seconds) on DO indicating how long the PPP Session should linger before closing down</li> </ul> </li> </ul>

<i>pPppSessCloseTimer1x</i>	<ul style="list-style-type: none"> <li>• PPP Session Close Timer for 1X <ul style="list-style-type: none"> <li>– Timer value (in seconds) on 1X indicating how long the PPP session should linger before closing down</li> </ul> </li> </ul>
<i>pAllowLinger</i>	<ul style="list-style-type: none"> <li>• Allow/disallow lingering of interface <ul style="list-style-type: none"> <li>– 1 -(TRUE) implies allow lingering</li> <li>– 0 -(FALSE) implies do not allow lingering</li> </ul> </li> </ul>
<i>pLcpAckTimeout</i>	<ul style="list-style-type: none"> <li>• LCP ACK Timeout <ul style="list-style-type: none"> <li>– Value of LCP ACK Timeout in milliseconds</li> </ul> </li> </ul>
<i>plpcpAckTimeout</i>	<ul style="list-style-type: none"> <li>• IPCP ACK Timeout <ul style="list-style-type: none"> <li>– Value of IPCP ACK Timeout in milliseconds</li> </ul> </li> </ul>
<i>pAuthTimeout</i>	<ul style="list-style-type: none"> <li>• AUTH Timeout <ul style="list-style-type: none"> <li>– Value of Authentication Timeout in milliseconds</li> </ul> </li> </ul>
<i>pLcpCreqRetryCount</i>	<ul style="list-style-type: none"> <li>• LCP Configuration Request Retry Count</li> </ul>
<i>plpcpCreqRetryCount</i>	<ul style="list-style-type: none"> <li>• IPCP Configuration Request Retry Count</li> </ul>
<i>pAuthRetryCount</i>	<ul style="list-style-type: none"> <li>• Authentication Retry Count value</li> </ul>
<i>pAuthProtocol</i>	<ul style="list-style-type: none"> <li>• Authentication Protocol <ul style="list-style-type: none"> <li>– 1 - PAP</li> <li>– 2 - CHAP</li> <li>– 3 - PAP or CHAP</li> </ul> </li> </ul>
<i>pUserId</i>	<ul style="list-style-type: none"> <li>• User ID to be used during data network authentication</li> <li>• maximum length allowed is 127 uint8_ts;</li> <li>• QMI_ERR_ARG_TOO_LONG will be returned if the storage on the wireless device is insufficient in size to hold the value.</li> </ul>



<i>pUserIdSize;</i>	<ul style="list-style-type: none"> <li>This parameter is an input parameter and should be initialised to the size of pUserId field. Size of this parameter is 2 uint8_ts.</li> </ul>
<i>pAuthPassword</i>	<ul style="list-style-type: none"> <li>Password to be used during data network authentication;</li> <li>maximum length allowed is 127 uint8_ts</li> <li>QMI_ERR_ARG_TOO_LONG will be returned if the storage on the wireless device is insufficient in size to hold the value.</li> </ul>
<i>pAuthPassword-Size;</i>	<ul style="list-style-type: none"> <li>This parameter is an input parameter and should be initialised to the size of pAuthPassword field. Size of this parameter is 2 uint8_ts.</li> </ul>
<i>pDataRate</i>	<ul style="list-style-type: none"> <li>Data Rate Requested <ul style="list-style-type: none"> <li>0 - Low (Low speed Service Options (SO15) only)</li> <li>1 - Medium (SO33 + low R-SCH)</li> <li>2 - High (SO33 + high R-SCH)</li> <li>Default is 2</li> </ul> </li> </ul>
<i>pAppType</i>	<ul style="list-style-type: none"> <li>Application Type: <ul style="list-style-type: none"> <li>0x00000001 - Default Application Type</li> <li>0x00000020 - LBS Application Type</li> <li>0x00000040 - Tethered Application Type</li> <li>This parameter is not used while creating/modifying a profile</li> </ul> </li> </ul>
<i>pDataMode</i>	<ul style="list-style-type: none"> <li>Data Mode to use: <ul style="list-style-type: none"> <li>0 - CDMA or HDR (Hybrid 1X/1xEV-DO)</li> <li>1 - CDMA Only (1X only)</li> <li>2 - HDR Only (1xEV-DO only)</li> <li>Default is 0</li> </ul> </li> </ul>
<i>pAppPriority</i>	<ul style="list-style-type: none"> <li>Application Priority <ul style="list-style-type: none"> <li>Numerical 1 uint8_t value defining the application priority; higher value implies higher priority</li> <li>This parameter is not used while creating/modifying a profile</li> </ul> </li> </ul>

<i>pApnString</i>	<ul style="list-style-type: none"> <li>String representing the Access Point Name</li> <li>maximum length allowed is 100 uint8_ts</li> <li>QMI_ERR_ARG_TOO_LONG will be returned if the APN name is too long.</li> </ul>
<i>pApnStringSize;</i>	<ul style="list-style-type: none"> <li>This parameter is an input parameter and should be initialised to the size of pApnString field. Size of this parameter is 2 uint8_ts.</li> </ul>
<i>pPdnType</i>	<ul style="list-style-type: none"> <li>Packed Data Network Type Requested: <ul style="list-style-type: none"> <li>0 - IPv4 PDN Type</li> <li>1 - IPv6 PDN Type</li> <li>2 - IPv4 or IPv6 PDN Type</li> <li>3 - Unspecified PDN Type (implying no preference)</li> </ul> </li> </ul>
<i>plsPcsf-AddressNedded</i>	<ul style="list-style-type: none"> <li>This boolean value is used to control if PCSCF address is requested from PDSN <ul style="list-style-type: none"> <li>1 -(TRUE) implies request for PCSCF value from the PDSN</li> <li>0 -(FALSE) implies do not request for PCSCF value from the PDSN</li> </ul> </li> </ul>
<i>pPrimaryV4Dns-Address</i>	<ul style="list-style-type: none"> <li>IPv4 Primary DNS address <ul style="list-style-type: none"> <li>The Primary IPv4 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pSecondaryV4-DnsAddress</i>	<ul style="list-style-type: none"> <li>IPv4 Secondary DNS address <ul style="list-style-type: none"> <li>The Secondary IPv4 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pPriV6Dns-Address</i>	<ul style="list-style-type: none"> <li>Primary IPv6 DNS address <ul style="list-style-type: none"> <li>The Primary IPv6 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pSecV6Dns-Address</i>	<ul style="list-style-type: none"> <li>Secondary IPv6 DNS address <ul style="list-style-type: none"> <li>The Secondary IPv6 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pRATType</i>	<ul style="list-style-type: none"> <li>Optional 1 uint8_t Flag indicating RAT Type</li> <li>Values: <ul style="list-style-type: none"> <li>1 - HRPD</li> <li>2 - EHRPD</li> <li>3 - HRPD_EHRPD</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>This parameter is currently read only and can be read by using the function <a href="#">QMI_RATType_Get</a> or <a href="#">ProfileSettings()</a>.</li> </ul>

<i>pAPNEnabled3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 1 uint8_t Flag indicating if the APN is disabled/enabled</li> <li>• If disabled, the profile can not be used for making data calls</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled(default value)</li> </ul> </li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pPDNInactivityTimeout3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 4 uint8_ts indicating the duration of inactivity timer in seconds</li> <li>• If the PDP context/PDN connection is inactive for this duration i.e. No data Tx/Rx occurs, the PDP context/PDN connection is disconnected</li> <li>• Default value of zero indicates infinite value</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pAPNClass3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 1 uint8_t numeric identifier representing the APN in profile</li> <li>• Can be set and queried but is not used by the modem</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

## 8.275.2 Field Documentation

8.275.2.1 uint8\_t\* LibpackProfile3GPP2::pAllowLinger

8.275.2.2 uint8\_t\* LibpackProfile3GPP2::pAPNClass3GPP2

8.275.2.3 uint8\_t\* LibpackProfile3GPP2::pAPNEnabled3GPP2

8.275.2.4 uint8\_t\* LibpackProfile3GPP2::pApnString

8.275.2.5 uint16\_t\* LibpackProfile3GPP2::pApnStringSize

8.275.2.6 uint8\_t\* LibpackProfile3GPP2::pAppPriority

8.275.2.7 uint32\_t\* LibpackProfile3GPP2::pAppType

8.275.2.8 uint8\_t\* LibpackProfile3GPP2::pAuthPassword

8.275.2.9 uint16\_t\* LibpackProfile3GPP2::pAuthPasswordSize

8.275.2.10 uint8\_t\* LibpackProfile3GPP2::pAuthProtocol

8.275.2.11 uint8\_t\* LibpackProfile3GPP2::pAuthRetryCount

8.275.2.12 uint16\_t\* LibpackProfile3GPP2::pAuthTimeout

8.275.2.13 uint8\_t\* LibpackProfile3GPP2::pDataMode

8.275.2.14 uint8\_t\* LibpackProfile3GPP2::pDataRate

8.275.2.15 uint16\_t\* LibpackProfile3GPP2::plpcpAckTimeout

8.275.2.16 uint8\_t\* LibpackProfile3GPP2::plpcpCreqRetryCount

8.275.2.17 uint8\_t\* LibpackProfile3GPP2::plsPcscfAddressNedded

8.275.2.18 uint16\_t\* LibpackProfile3GPP2::pLcpAckTimeout

8.275.2.19 uint8\_t\* LibpackProfile3GPP2::pLcpCreqRetryCount

8.275.2.20 uint8\_t\* LibpackProfile3GPP2::pNegoDnsSrvrPref

8.275.2.21 uint32\_t\* LibpackProfile3GPP2::pPDNInactivTimeout3GPP2

8.275.2.22 uint8\_t\* LibpackProfile3GPP2::pPdnType

8.275.2.23 uint32\_t\* LibpackProfile3GPP2::pPppSessCloseTimer1x

8.275.2.24 uint32\_t\* LibpackProfile3GPP2::pPppSessCloseTimerDO

8.275.2.25 uint32\_t\* LibpackProfile3GPP2::pPrimaryV4DnsAddress

8.275.2.26 uint16\_t\* LibpackProfile3GPP2::pPriv6DnsAddress

8.275.2.27 uint8\_t\* LibpackProfile3GPP2::pRATType

8.275.2.28 uint32\_t\* LibpackProfile3GPP2::pSecondaryV4DnsAddress

8.275.2.29 uint16\_t\* LibpackProfile3GPP2::pSecV6DnsAddress

8.275.2.30 uint8\_t\* LibpackProfile3GPP2::pUserId

8.275.2.31 uint16\_t\* LibpackProfile3GPP2::pUserIdSize

## 8.276 LibPackprofile\_3GPP Struct Reference

### Data Fields

- uint8\_t \* [pProfilename](#)
- uint16\_t \* [pProfilenameSize](#)
- uint8\_t \* [pPDPTtype](#)
- uint8\_t \* [pPdpHdrCompType](#)
- uint8\_t \* [pPdpDataCompType](#)
- uint8\_t \* [pAPNName](#)
- uint16\_t \* [pAPNnameSize](#)
- uint32\_t \* [pPriDNSIPv4AddPref](#)
- uint32\_t \* [pSecDNSIPv4AddPref](#)
- [LibPackUMTSQoS](#) \* [pUMTSReqQoS](#)
- [LibPackUMTSQoS](#) \* [pUMTSMInQoS](#)

- [LibPackGPRSRequestedQoS](#) \* [pGPRSRequestedQoS](#)
- [LibPackGPRSRequestedQoS](#) \* [pGPRSMinimumQoS](#)
- [uint8\\_t](#) \* [pUsername](#)
- [uint16\\_t](#) \* [pUsernameSize](#)
- [uint8\\_t](#) \* [pPassword](#)
- [uint16\\_t](#) \* [pPasswordSize](#)
- [uint8\\_t](#) \* [pAuthenticationPref](#)
- [uint32\\_t](#) \* [pIPv4AddrPref](#)
- [uint8\\_t](#) \* [pPcscfAddrUsingPCO](#)
- [uint8\\_t](#) \* [pPdpAccessConFlag](#)
- [uint8\\_t](#) \* [pPcscfAddrUsingDhcp](#)
- [uint8\\_t](#) \* [pImCnFlag](#)
- [LibPackTFTIDParams](#) \* [pTFTID1Params](#)
- [LibPackTFTIDParams](#) \* [pTFTID2Params](#)
- [uint8\\_t](#) \* [pPdpContext](#)
- [uint8\\_t](#) \* [pSecondaryFlag](#)
- [uint8\\_t](#) \* [pPrimaryID](#)
- [uint16\\_t](#) \* [pIPv6AddPref](#)
- [LibPackUMTSReqQoSSigInd](#) \* [pUMTSReqQoSSigInd](#)
- [LibPackUMTSReqQoSSigInd](#) \* [pUMTSMinQosSigInd](#)
- [uint16\\_t](#) \* [pPriDNSIPv6addpref](#)
- [uint16\\_t](#) \* [pSecDNSIPv6addpref](#)
- [uint8\\_t](#) \* [pAddrAllocPref](#)
- [LibPackQosClassID](#) \* [pQosClassID](#)
- [uint8\\_t](#) \* [pAPNDisabledFlag](#)
- [uint32\\_t](#) \* [pPDNInactivTimeout](#)
- [uint8\\_t](#) \* [pAPNClass](#)

### 8.276.1 Detailed Description

This structure contains Input parameters of SLQSCreateProfile and SLQSModifyProfile and output parameters of SLQSGetProfileSettings

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>pProfileName</i>	<ul style="list-style-type: none"> <li>• One or more bytes describing the profile</li> </ul>
<i>pProfilename-Size;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pProfile-Name field. Size of this parameter is 2 bytes.</li> </ul>
<i>pPDPTType</i>	<ul style="list-style-type: none"> <li>• Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile <ul style="list-style-type: none"> <li>– 0x00 - PDP-IP (IPv4)</li> <li>– 0x01 - PDP-PPP</li> <li>– 0x02 - PDP-IPV6</li> <li>– 0x03 - PDP-IPV4V6</li> </ul> </li> </ul>
<i>pPdpHdrComp-Type</i>	<ul style="list-style-type: none"> <li>• PDP header compression type <ul style="list-style-type: none"> <li>– 0 - PDP header compression is OFF</li> <li>– 1 - Manufacturer preferred compression</li> <li>– 2 - PDP header compression based on RFC 1144</li> <li>– 3 - PDP header compression based on RFC 25074 PDP header compression based on RFC 3095</li> </ul> </li> </ul>
<i>pPdpDataComp-Type</i>	<ul style="list-style-type: none"> <li>• PDP data compression type <ul style="list-style-type: none"> <li>– 0 - PDP data compression is OFF</li> <li>– 1 - Manufacturer preferred compression</li> <li>– 2 - V.42BIS data compression</li> <li>– 3 - V.44 data compression</li> </ul> </li> </ul>
<i>pAPNName</i>	<ul style="list-style-type: none"> <li>• Access point name</li> </ul>
<i>pAPNnameSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pAPN-Name field. Size of this parameter is 2 bytes.</li> </ul>
<i>pPriDNSIPv4-AddPref</i>	<ul style="list-style-type: none"> <li>• Primary DNS IPv4 Address Preference</li> </ul>
<i>pSecDNSIPv4-AddPref</i>	<ul style="list-style-type: none"> <li>• Secondary DNS IPv4 Address Preference</li> </ul>

<i>pUMTSReqQoS</i>	<ul style="list-style-type: none"> <li>• UMTS Requested QoS</li> </ul>
<i>pUMTSMinQoS</i>	<ul style="list-style-type: none"> <li>• UMTS Minimum QoS</li> </ul>
<i>pGPRS- RequestedQoS</i>	<ul style="list-style-type: none"> <li>• GPRS Minimum QoS</li> </ul>
<i>pUsername</i>	<ul style="list-style-type: none"> <li>• User name</li> </ul>
<i>pUsernameSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pUsername field. Size of this parameter is 2 bytes.</li> </ul>
<i>pPassword</i>	<ul style="list-style-type: none"> <li>• Password</li> </ul>
<i>pPasswordSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pPassword field. Size of this parameter is 2 bytes.</li> </ul>
<i>pAuthentication- Pref</i>	<ul style="list-style-type: none"> <li>• Authentication Preference <ul style="list-style-type: none"> <li>– Bit map that indicates the authentication algorithm preference <ul style="list-style-type: none"> <li>* Bit 0 - PAP preference <ul style="list-style-type: none"> <li>· 0 - PAP is never performed</li> <li>· 1 - PAP may be performed</li> </ul> </li> <li>* Bit 1 - CHAP preference <ul style="list-style-type: none"> <li>· 0 - CHAP is never performed</li> <li>· 1 - CHAP may be performed</li> </ul> </li> <li>* If more than one bit is set, then the device decides which authentication procedure is performed while setting up the data session. For example, the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul> </li> </ul>

<i>pIPv4AddrPref</i>	<ul style="list-style-type: none"> <li>• IPv4 Address Preference</li> </ul>
<i>pPcscfAddr-UsingPCO</i>	<ul style="list-style-type: none"> <li>• P-CSCF Address using PCO Flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies request PCSCF address using PCO</li> <li>– 0 - (FALSE) implies do not request By default, this value is 0</li> </ul> </li> </ul>
<i>pPdpAccess-ConFlag</i>	<ul style="list-style-type: none"> <li>• PDP access control flag <ul style="list-style-type: none"> <li>– 0 - PDP access control none</li> <li>– 1 - PDP access control reject</li> <li>– 2 - PDP access control permission</li> </ul> </li> </ul>
<i>pPcscfAddr-UsingDhcp</i>	<ul style="list-style-type: none"> <li>• P-CSCF address using DHCP <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies Request PCSCF address using DHCP</li> <li>– 0 - (FALSE) implies do not request By default, value is 0</li> </ul> </li> </ul>
<i>plmCnFlag</i>	<ul style="list-style-type: none"> <li>• IM CN flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies request IM CN flag for this profile</li> <li>– 0 - (FALSE) implies do not request IM CN flag for this profile</li> </ul> </li> </ul>
<i>pTFTID1Params</i>	<ul style="list-style-type: none"> <li>• Traffic Flow Template</li> </ul>
<i>pTFTID2Params</i>	<ul style="list-style-type: none"> <li>• Traffic Flow Template</li> </ul>
<i>pPdpContext</i>	<ul style="list-style-type: none"> <li>• PDP context number</li> </ul>
<i>pSecondaryFlag</i>	<ul style="list-style-type: none"> <li>• PDP context secondary flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies this is secondary profile</li> <li>– 0 - (FALSE) implies this is not secondary profile</li> </ul> </li> </ul>
<i>pPrimaryID</i>	<ul style="list-style-type: none"> <li>• PDP context primary ID</li> <li>• function <a href="#">SLQSGetProfileSettings()</a> returns a default value 0xFF if this parameter is not returned by the device</li> </ul>



<i>pIPv6AddPref</i>	<ul style="list-style-type: none"> <li>IPv6 address preference Preferred IPv6 address to be assigned to the TE; actual assigned address is negotiated with the network and may differ from this value; if not specified, the IPv6 address is obtained automatically from the network</li> </ul>
<i>pUMTSReqQoS-SigInd</i>	<ul style="list-style-type: none"> <li>UMTS requested QoS with Signalling Indication flag</li> </ul>
<i>pUMTSMinQoS-SigInd</i>	<ul style="list-style-type: none"> <li>UMTS minimum QoS with Signalling Indication flag</li> </ul>
<i>pPrimaryDNSIPv6addpref</i>	<ul style="list-style-type: none"> <li>Primary DNS IPv6 address preference <ul style="list-style-type: none"> <li>The value may be used as a preference during negotiation with the network; if not specified, the wireless device will attempt to obtain the DNS address automatically from the network; the negotiated value is provided to the host via DHCP</li> </ul> </li> </ul>
<i>pSecondaryDNSIPv6addpref</i>	<ul style="list-style-type: none"> <li>Secondary DNS IPv6 address preference</li> </ul>
<i>paddrAllocation-Pref</i>	<ul style="list-style-type: none"> <li>DHCP/NAS preference <ul style="list-style-type: none"> <li>This enumerated value may be used to indicate the address allocation preference <ul style="list-style-type: none"> <li>* 0 - NAS signaling is used for address allocation</li> <li>* 1 - DHCP is used for address allocation</li> </ul> </li> </ul> </li> </ul>
<i>pQosClassID</i>	<ul style="list-style-type: none"> <li>3GPP LTE QoS parameters</li> </ul>
<i>pAPNDisabled-Flag</i>	<ul style="list-style-type: none"> <li>Optional 1 uint8_t Flag indicating if the APN is disabled/enabled</li> <li>If set, the profile can not be used for making data calls</li> <li>Any data call is failed locally</li> <li>Values: <ul style="list-style-type: none"> <li>0 - FALSE(default)</li> <li>1 - True</li> </ul> </li> <li>This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

<i>pPDNInactivTimeout</i>	<ul style="list-style-type: none"> <li>• Optional 4 Bytes indicating the duration of inactivity timer in seconds</li> <li>• If the PDP context/PDN connection is inactive for this duration i.e. No data Tx/Rx occurs, the PDP context/PDN connection is disconnected</li> <li>• Default value of zero indicates infinite value</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pAPNClass</i>	<ul style="list-style-type: none"> <li>• Optional 1 uint8_t numeric identifier representing the APN in profile</li> <li>• Can be set and queried but is not used by the modem</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

## 8.276.2 Field Documentation

8.276.2.1 uint8\_t\* LibPackprofile\_3GPP::pAddrAllocPref

8.276.2.2 uint8\_t\* LibPackprofile\_3GPP::pAPNClass

8.276.2.3 uint8\_t\* LibPackprofile\_3GPP::pAPNDisabledFlag

8.276.2.4 uint8\_t\* LibPackprofile\_3GPP::pAPNName

8.276.2.5 uint16\_t\* LibPackprofile\_3GPP::pAPNnameSize

8.276.2.6 uint8\_t\* LibPackprofile\_3GPP::pAuthenticationPref

8.276.2.7 LibPackGPRSRequestedQoS\* LibPackprofile\_3GPP::pGPRSMinimumQoS

8.276.2.8 LibPackGPRSRequestedQoS\* LibPackprofile\_3GPP::pGPRSRequestedQoS

8.276.2.9 uint8\_t\* LibPackprofile\_3GPP::plmCnFlag

8.276.2.10 uint32\_t\* LibPackprofile\_3GPP::pIPv4AddrPref

8.276.2.11 uint16\_t\* LibPackprofile\_3GPP::pIPv6AddPref

8.276.2.12 uint8\_t\* LibPackprofile\_3GPP::pPassword

8.276.2.13 uint16\_t\* LibPackprofile\_3GPP::pPasswordSize

8.276.2.14 uint8\_t\* LibPackprofile\_3GPP::pPcscfAddrUsingDhcp

8.276.2.15 uint8\_t\* LibPackprofile\_3GPP::pPcscfAddrUsingPCO

8.276.2.16 uint32\_t\* LibPackprofile\_3GPP::pPDNInactivTimeout

8.276.2.17 uint8\_t\* LibPackprofile\_3GPP::pPdpAccessConFlag

- 8.276.2.18 uint8\_t\* LibPackprofile\_3GPP::pPdpContext
- 8.276.2.19 uint8\_t\* LibPackprofile\_3GPP::pPdpDataCompType
- 8.276.2.20 uint8\_t\* LibPackprofile\_3GPP::pPdpHdrCompType
- 8.276.2.21 uint8\_t\* LibPackprofile\_3GPP::pPDPTtype
- 8.276.2.22 uint32\_t\* LibPackprofile\_3GPP::pPriDNSIPv4AddPref
- 8.276.2.23 uint16\_t\* LibPackprofile\_3GPP::pPriDNSIPv6addpref
- 8.276.2.24 uint8\_t\* LibPackprofile\_3GPP::pPrimaryID
- 8.276.2.25 uint8\_t\* LibPackprofile\_3GPP::pProfilename
- 8.276.2.26 uint16\_t\* LibPackprofile\_3GPP::pProfilenameSize
- 8.276.2.27 LibPackQosClassID\* LibPackprofile\_3GPP::pQosClassID
- 8.276.2.28 uint32\_t\* LibPackprofile\_3GPP::pSecDNSIPv4AddPref
- 8.276.2.29 uint16\_t\* LibPackprofile\_3GPP::pSecDNSIPv6addpref
- 8.276.2.30 uint8\_t\* LibPackprofile\_3GPP::pSecondaryFlag
- 8.276.2.31 LibPackTFTIDParams\* LibPackprofile\_3GPP::pTFTID1Params
- 8.276.2.32 LibPackTFTIDParams\* LibPackprofile\_3GPP::pTFTID2Params
- 8.276.2.33 LibPackUMTSQoS\* LibPackprofile\_3GPP::pUMTSMinQoS
- 8.276.2.34 LibPackUMTSReqQoSSigInd\* LibPackprofile\_3GPP::pUMTSMinQoSSigInd
- 8.276.2.35 LibPackUMTSQoS\* LibPackprofile\_3GPP::pUMTSReqQoS
- 8.276.2.36 LibPackUMTSReqQoSSigInd\* LibPackprofile\_3GPP::pUMTSReqQoSSigInd
- 8.276.2.37 uint8\_t\* LibPackprofile\_3GPP::pUsername
- 8.276.2.38 uint16\_t\* LibPackprofile\_3GPP::pUsernameSize

## 8.277 LibPackprofile\_3GPP2 Struct Reference

### Data Fields

- uint8\_t \* [pNegoDnsSrvrPref](#)
- uint32\_t \* [pPppSessCloseTimerDO](#)
- uint32\_t \* [pPppSessCloseTimer1x](#)
- uint8\_t \* [pAllowLinger](#)
- uint16\_t \* [pLcpAckTimeout](#)
- uint16\_t \* [pIpcpAckTimeout](#)
- uint16\_t \* [pAuthTimeout](#)
- uint8\_t \* [pLcpCreqRetryCount](#)
- uint8\_t \* [pIpcpCreqRetryCount](#)

- uint8\_t \* [pAuthRetryCount](#)
- uint8\_t \* [pAuthProtocol](#)
- uint8\_t \* [pUserId](#)
- uint16\_t \* [pUserIdSize](#)
- uint8\_t \* [pAuthPassword](#)
- uint16\_t \* [pAuthPassword\\_tSize](#)
- uint8\_t \* [pDataRate](#)
- uint32\_t \* [pAppType](#)
- uint8\_t \* [pDataMode](#)
- uint8\_t \* [pAppPriority](#)
- uint8\_t \* [pApnString](#)
- uint16\_t \* [pApnStringSize](#)
- uint8\_t \* [pPdnType](#)
- uint8\_t \* [pIsPcscfAddressNedded](#)
- uint32\_t \* [pPrimaryV4DnsAddress](#)
- uint32\_t \* [pSecondaryV4DnsAddress](#)
- uint16\_t \* [pPriV6DnsAddress](#)
- uint16\_t \* [pSecV6DnsAddress](#)
- uint8\_t \* [pRATType](#)
- uint8\_t \* [pAPNEnabled3GPP2](#)
- uint32\_t \* [pPDNInactivTimeout3GPP2](#)
- uint8\_t \* [pAPNClass3GPP2](#)

### 8.277.1 Detailed Description

This structure contains the 3GPP2 profile parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>pNegoDnsSrvr-Pref</i>	<ul style="list-style-type: none"> <li>• Negotiate DNS Server Preference             <ul style="list-style-type: none"> <li>– 1 - (TRUE)implies request DNS addresses from the PDSN</li> <li>– 0 - (FALSE)implies do not request DNS addresses from the PDSN</li> <li>– Default value is 1 (TRUE)</li> </ul> </li> </ul>
<i>pPppSessClose-TimerDO</i>	<ul style="list-style-type: none"> <li>• PPP Session Close Timer for DO             <ul style="list-style-type: none"> <li>– Timer value (in seconds) on DO indicating how long the PPP Session should linger before closing down</li> </ul> </li> </ul>

<i>pPppSessCloseTimer1x</i>	<ul style="list-style-type: none"> <li>• PPP Session Close Timer for 1X <ul style="list-style-type: none"> <li>– Timer value (in seconds) on 1X indicating how long the PPP session should linger before closing down</li> </ul> </li> </ul>
<i>pAllowLinger</i>	<ul style="list-style-type: none"> <li>• Allow/disallow lingering of interface <ul style="list-style-type: none"> <li>– 1 -(TRUE) implies allow lingering</li> <li>– 0 -(FALSE) implies do not allow lingering</li> </ul> </li> </ul>
<i>pLcpAckTimeout</i>	<ul style="list-style-type: none"> <li>• LCP ACK Timeout <ul style="list-style-type: none"> <li>– Value of LCP ACK Timeout in milliseconds</li> </ul> </li> </ul>
<i>plpcpAckTimeout</i>	<ul style="list-style-type: none"> <li>• IPCP ACK Timeout <ul style="list-style-type: none"> <li>– Value of IPCP ACK Timeout in milliseconds</li> </ul> </li> </ul>
<i>pAuthTimeout</i>	<ul style="list-style-type: none"> <li>• AUTH Timeout <ul style="list-style-type: none"> <li>– Value of Authentication Timeout in milliseconds</li> </ul> </li> </ul>
<i>pLcpCreqRetryCount</i>	<ul style="list-style-type: none"> <li>• LCP Configuration Request Retry Count</li> </ul>
<i>plpcpCreqRetryCount</i>	<ul style="list-style-type: none"> <li>• IPCP Configuration Request Retry Count</li> </ul>
<i>pAuthRetryCount</i>	<ul style="list-style-type: none"> <li>• Authentication Retry Count value</li> </ul>
<i>pAuthProtocol</i>	<ul style="list-style-type: none"> <li>• Authentication Protocol <ul style="list-style-type: none"> <li>– 1 - PAP</li> <li>– 2 - CHAP</li> <li>– 3 - PAP or CHAP</li> </ul> </li> </ul>
<i>pUserId</i>	<ul style="list-style-type: none"> <li>• User ID to be used during data network authentication</li> <li>• maximum length allowed is 127 bytes;</li> <li>• QMI_ERR_ARG_TOO_LONG will be returned if the storage on the wireless device is insufficient in size to hold the value.</li> </ul>

<i>pUserIdSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pUserId field. Size of this parameter is 2 bytes.</li> </ul>
<i>pAuthPassword</i>	<ul style="list-style-type: none"> <li>• Password to be used during data network authentication;</li> <li>• maximum length allowed is 127 bytes</li> <li>• QMI_ERR_ARG_TOO_LONG will be returned if the storage on the wireless device is insufficient in size to hold the value.</li> </ul>
<i>pAuthPassword-Size;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pAuthPassword field. Size of this parameter is 2 bytes.</li> </ul>
<i>pDataRate</i>	<ul style="list-style-type: none"> <li>• Data Rate Requested <ul style="list-style-type: none"> <li>– 0 - Low (Low speed Service Options (SO15) only)</li> <li>– 1 - Medium (SO33 + low R-SCH)</li> <li>– 2 - High (SO33 + high R-SCH)</li> <li>– Default is 2</li> </ul> </li> </ul>
<i>pAppType</i>	<ul style="list-style-type: none"> <li>• Application Type: <ul style="list-style-type: none"> <li>– 0x00000001 - Default Application Type</li> <li>– 0x00000020 - LBS Application Type</li> <li>– 0x00000040 - Tethered Application Type</li> <li>– This parameter is not used while creating/modifying a profile</li> </ul> </li> </ul>
<i>pDataMode</i>	<ul style="list-style-type: none"> <li>• Data Mode to use: <ul style="list-style-type: none"> <li>– 0 - CDMA or HDR (Hybrid 1X/1xEV-DO)</li> <li>– 1 - CDMA Only (1X only)</li> <li>– 2 - HDR Only (1xEV-DO only)</li> <li>– Default is 0</li> </ul> </li> </ul>
<i>pAppPriority</i>	<ul style="list-style-type: none"> <li>• Application Priority <ul style="list-style-type: none"> <li>– Numerical 1 uint8_t value defining the application priority; higher value implies higher priority</li> <li>– This parameter is not used while creating/modifying a profile</li> </ul> </li> </ul>

<i>pApnString</i>	<ul style="list-style-type: none"> <li>String representing the Access Point Name</li> <li>maximum length allowed is 100 bytes</li> <li>QMI_ERR_ARG_TOO_LONG will be returned if the APN name is too long.</li> </ul>
<i>pApnStringSize;</i>	<ul style="list-style-type: none"> <li>This parameter is an input parameter and should be initialised to the size of pApnString field. Size of this parameter is 2 bytes.</li> </ul>
<i>pPdnType</i>	<ul style="list-style-type: none"> <li>Packed Data Network Type Requested: <ul style="list-style-type: none"> <li>0 - IPv4 PDN Type</li> <li>1 - IPv6 PDN Type</li> <li>2 - IPv4 or IPv6 PDN Type</li> <li>3 - Unspecified PDN Type (implying no preference)</li> </ul> </li> </ul>
<i>plsPcsf-AddressNedded</i>	<ul style="list-style-type: none"> <li>This boolean value is used to control if PCSCF address is requested from PDSN <ul style="list-style-type: none"> <li>1 -(TRUE) implies request for PCSCF value from the PDSN</li> <li>0 -(FALSE) implies do not request for PCSCF value from the PDSN</li> </ul> </li> </ul>
<i>pPrimaryV4Dns-Address</i>	<ul style="list-style-type: none"> <li>IPv4 Primary DNS address <ul style="list-style-type: none"> <li>The Primary IPv4 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pSecondaryV4-DnsAddress</i>	<ul style="list-style-type: none"> <li>IPv4 Secondary DNS address <ul style="list-style-type: none"> <li>The Secondary IPv4 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pPriV6Dns-Address</i>	<ul style="list-style-type: none"> <li>Primary IPv6 DNS address <ul style="list-style-type: none"> <li>The Primary IPv6 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pSecV6Dns-Address</i>	<ul style="list-style-type: none"> <li>Secondary IPv6 DNS address <ul style="list-style-type: none"> <li>The Secondary IPv6 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pRATType</i>	<ul style="list-style-type: none"> <li>Optional 1 uint8_t Flag indicating RAT Type</li> <li>Values: <ul style="list-style-type: none"> <li>1 - HRPD</li> <li>2 - EHRPD</li> <li>3 - HRPD_EHRPD</li> </ul> </li> </ul>
<p>Generated on Tue Jul 12 2016 10:59:45. This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</p>	

<i>pAPNEnabled3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 1 uint8_t Flag indicating if the APN is disabled/enabled</li> <li>• If disabled, the profile can not be used for making data calls</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled(default value)</li> </ul> </li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pPDNInactivityTimeout3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 4 Bytes indicating the duration of inactivity timer in seconds</li> <li>• If the PDP context/PDN connection is inactive for this duration i.e. No data Tx/Rx occurs, the PDP context/PDN connection is disconnected</li> <li>• Default value of zero indicates infinite value</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pAPNClass3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 1 uint8_t numeric identifier representing the APN in profile</li> <li>• Can be set and queried but is not used by the modem</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

## 8.277.2 Field Documentation

8.277.2.1 uint8\_t\* LibPackprofile\_3GPP2::pAllowLinger

8.277.2.2 uint8\_t\* LibPackprofile\_3GPP2::pAPNClass3GPP2

8.277.2.3 uint8\_t\* LibPackprofile\_3GPP2::pAPNEnabled3GPP2

8.277.2.4 uint8\_t\* LibPackprofile\_3GPP2::pApnString

8.277.2.5 uint16\_t\* LibPackprofile\_3GPP2::pApnStringSize

8.277.2.6 uint8\_t\* LibPackprofile\_3GPP2::pAppPriority

8.277.2.7 uint32\_t\* LibPackprofile\_3GPP2::pAppType

8.277.2.8 uint8\_t\* LibPackprofile\_3GPP2::pAuthPassword

8.277.2.9 uint16\_t\* LibPackprofile\_3GPP2::pAuthPassword\_tSize

8.277.2.10 uint8\_t\* LibPackprofile\_3GPP2::pAuthProtocol

8.277.2.11 uint8\_t\* LibPackprofile\_3GPP2::pAuthRetryCount



- 8.277.2.12 uint16\_t\* LibPackprofile\_3GPP2::pAuthTimeout
- 8.277.2.13 uint8\_t\* LibPackprofile\_3GPP2::pDataMode
- 8.277.2.14 uint8\_t\* LibPackprofile\_3GPP2::pDataRate
- 8.277.2.15 uint16\_t\* LibPackprofile\_3GPP2::plpcpAckTimeout
- 8.277.2.16 uint8\_t\* LibPackprofile\_3GPP2::plpcpCreqRetryCount
- 8.277.2.17 uint8\_t\* LibPackprofile\_3GPP2::plsPcscfAddressNedded
- 8.277.2.18 uint16\_t\* LibPackprofile\_3GPP2::pLcpAckTimeout
- 8.277.2.19 uint8\_t\* LibPackprofile\_3GPP2::pLcpCreqRetryCount
- 8.277.2.20 uint8\_t\* LibPackprofile\_3GPP2::pNegoDnsSrvrPref
- 8.277.2.21 uint32\_t\* LibPackprofile\_3GPP2::pPDNInactivTimeout3GPP2
- 8.277.2.22 uint8\_t\* LibPackprofile\_3GPP2::pPdnType
- 8.277.2.23 uint32\_t\* LibPackprofile\_3GPP2::pPppSessCloseTimer1x
- 8.277.2.24 uint32\_t\* LibPackprofile\_3GPP2::pPppSessCloseTimerDO
- 8.277.2.25 uint32\_t\* LibPackprofile\_3GPP2::pPrimaryV4DnsAddress
- 8.277.2.26 uint16\_t\* LibPackprofile\_3GPP2::pPriV6DnsAddress
- 8.277.2.27 uint8\_t\* LibPackprofile\_3GPP2::pRATType
- 8.277.2.28 uint32\_t\* LibPackprofile\_3GPP2::pSecondaryV4DnsAddress
- 8.277.2.29 uint16\_t\* LibPackprofile\_3GPP2::pSecV6DnsAddress
- 8.277.2.30 uint8\_t\* LibPackprofile\_3GPP2::pUserId
- 8.277.2.31 uint16\_t\* LibPackprofile\_3GPP2::pUserIdSize

## 8.278 LibPackQosClassID Struct Reference

### Data Fields

- uint8\_t [QCI](#)
- uint8\_t [gDIBitRate](#)
- uint32\_t [maxDIBitRate](#)
- uint32\_t [gUIBitRate](#)
- uint32\_t [maxUIBitRate](#)

### 8.278.1 Detailed Description

structure contains 3GPP LTE QoS parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>QCI</i>	<ul style="list-style-type: none"> <li>QOS specified using the QOS Class Identifier (QOS) values QCI value 0 - Requests the network to assign the appropriate QCI value QCI values 1-4 - Associated with guaranteed bit rates QCI values 5-9 - Associated with non-guaranteed bit rates</li> </ul>
<i>gDIBitRate</i>	<ul style="list-style-type: none"> <li>Guaranteed DL bit rate</li> </ul>
<i>maxDIBitRate</i>	<ul style="list-style-type: none"> <li>maxDIBitRate</li> </ul>
<i>gUIBitRate</i>	<ul style="list-style-type: none"> <li>Guaranteed UL bit rate</li> </ul>
<i>maxUIBitRate</i>	<ul style="list-style-type: none"> <li>Maximum UL bit rate</li> </ul>

## 8.278.2 Field Documentation

8.278.2.1 `uint8_t LibPackQosClassID::gDIBitRate`8.278.2.2 `uint32_t LibPackQosClassID::gUIBitRate`8.278.2.3 `uint32_t LibPackQosClassID::maxDIBitRate`8.278.2.4 `uint32_t LibPackQosClassID::maxUIBitRate`8.278.2.5 `uint8_t LibPackQosClassID::QCI`

## 8.279 LibPackTFTIDParams Struct Reference

## Data Fields

- `uint8_t filterId`
- `uint8_t eValid`
- `uint8_t ipVersion`
- `uint16_t * pSourceIP`
- `uint8_t sourceIPMask`
- `uint8_t nextHeader`
- `uint32_t destPortRangeStart`
- `uint16_t destPortRangeEnd`
- `uint16_t srcPortRangeStart`
- `uint16_t srcPortRangeEnd`
- `uint32_t IPSECSPi`
- `uint16_t tosMask`
- `uint32_t flowLabel`

## 8.279.1 Detailed Description

structure contains traffic flow template parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>filterId</i>	<ul style="list-style-type: none"> <li>• Filter identifier</li> </ul>
<i>eValid</i>	<ul style="list-style-type: none"> <li>• Evaluation precedence index</li> </ul>
<i>pVersion</i>	<ul style="list-style-type: none"> <li>• IP version number <ul style="list-style-type: none"> <li>– 4 - IPv4</li> <li>– 6 - IPv6</li> </ul> </li> </ul>
<i>sourceIP</i>	<ul style="list-style-type: none"> <li>• Source IP address <ul style="list-style-type: none"> <li>– IPv4 - Fill the first 4 uint8_ts</li> <li>– IPv6 - Fill all the 16 uint8_ts</li> </ul> </li> </ul>
<i>sourceIPMask</i>	<ul style="list-style-type: none"> <li>• Mask value for the source address</li> </ul>
<i>nextHeader</i>	<ul style="list-style-type: none"> <li>• Next header/protocol value</li> </ul>
<i>destPortRange-Start</i>	<ul style="list-style-type: none"> <li>• Start value of the destination port range</li> </ul>
<i>destPortRange-End</i>	<ul style="list-style-type: none"> <li>• End value of the destination port range</li> </ul>
<i>srcPortRange-Start</i>	<ul style="list-style-type: none"> <li>• Start value of the source port range</li> </ul>
<i>srcPortRange-End</i>	<ul style="list-style-type: none"> <li>• End value of the source port range</li> </ul>
<i>IPSECSPi</i>	<ul style="list-style-type: none"> <li>• IPSEC security parameter index</li> </ul>
<i>tosMask</i>	<ul style="list-style-type: none"> <li>• TOS mask (Traffic class for IPv6)</li> </ul>
<i>flowLabel</i>	<ul style="list-style-type: none"> <li>• Flow label</li> </ul>

## 8.279.2 Field Documentation

- 8.279.2.1 `uint16_t LibPackTFTIDParams::destPortRangeEnd`
- 8.279.2.2 `uint32_t LibPackTFTIDParams::destPortRangeStart`
- 8.279.2.3 `uint8_t LibPackTFTIDParams::eValid`
- 8.279.2.4 `uint8_t LibPackTFTIDParams::filterId`
- 8.279.2.5 `uint32_t LibPackTFTIDParams::flowLabel`
- 8.279.2.6 `uint32_t LibPackTFTIDParams::IPSECSPi`
- 8.279.2.7 `uint8_t LibPackTFTIDParams::ipVersion`
- 8.279.2.8 `uint8_t LibPackTFTIDParams::nextHeader`
- 8.279.2.9 `uint16_t* LibPackTFTIDParams::pSourceIP`
- 8.279.2.10 `uint8_t LibPackTFTIDParams::sourceIPMask`
- 8.279.2.11 `uint16_t LibPackTFTIDParams::srcPortRangeEnd`
- 8.279.2.12 `uint16_t LibPackTFTIDParams::srcPortRangeStart`
- 8.279.2.13 `uint16_t LibPackTFTIDParams::tosMask`

## 8.280 LibPackUMTSQoS Struct Reference

### Data Fields

- `uint8_t trafficClass`
- `uint32_t maxUplinkBitrate`
- `uint32_t maxDownlinkBitrate`
- `uint32_t grntUplinkBitrate`
- `uint32_t grntDownlinkBitrate`
- `uint8_t qosDeliveryOrder`
- `uint32_t maxSDUSize`
- `uint8_t sduErrorRatio`
- `uint8_t resBerRatio`
- `uint8_t deliveryErrSDU`
- `uint32_t transferDelay`
- `uint32_t trafficPriority`

### 8.280.1 Detailed Description

This structure contains the UMTS Quality Of Service Information

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>trafficClass</i>	<ul style="list-style-type: none"> <li>• 0x00 - Subscribed</li> <li>• 0x01 - Conversational</li> <li>• 0x02 - Streaming</li> <li>• 0x03 - Interactive</li> <li>• 0x04 - Background</li> </ul>
<i>maxUplinkBitrate</i>	<ul style="list-style-type: none"> <li>• Maximum uplink bit rate in bits/sec</li> </ul>
<i>maxDownlink-Bitrate</i>	<ul style="list-style-type: none"> <li>• Maximum downlink bit rate in bits/sec</li> </ul>
<i>grntUplinkBitrate</i>	<ul style="list-style-type: none"> <li>• Guaranteed uplink bit rate in bits/sec</li> </ul>
<i>grntDownlink-Bitrate</i>	<ul style="list-style-type: none"> <li>• Guranteed downlink bit rate in bits/sec</li> </ul>
<i>qosDelivery-Order</i>	<ul style="list-style-type: none"> <li>- Qos delivery order</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - delivery order on</li> <li>• 0x02 - delivery order off</li> </ul>
<i>maxSDUSize</i>	<ul style="list-style-type: none"> <li>• Maximum SDU size</li> </ul>
<i>sduErrorRatio</i>	<ul style="list-style-type: none"> <li>- SDU error ratio</li> <li>• Target value for fraction of SDUs lost or detected as erroneous.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>1 \cdot 10^{(-2)}</math></li> <li>• 0x02 - <math>7 \cdot 10^{(-3)}</math></li> <li>• 0x03 - <math>1 \cdot 10^{(-3)}</math></li> <li>• 0x04 - <math>1 \cdot 10^{(-4)}</math></li> <li>• 0x05 - <math>1 \cdot 10^{(-5)}</math></li> <li>• 0x06 - <math>1 \cdot 10^{(-6)}</math></li> <li>• 0x07 - <math>1 \cdot 10^{(-1)}</math></li> </ul>

<i>resBerRatio</i>	<p>- Residual bit error ratio</p> <ul style="list-style-type: none"> <li>• Target value for undetected bit error ratio in the delivered SDUs.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>5 \times 10^{-2}</math></li> <li>• 0x02 - <math>1 \times 10^{-2}</math></li> <li>• 0x03 - <math>5 \times 10^{-3}</math></li> <li>• 0x04 - <math>4 \times 10^{-3}</math></li> <li>• 0x05 - <math>1 \times 10^{-3}</math></li> <li>• 0x06 - <math>1 \times 10^{-4}</math></li> <li>• 0x07 - <math>1 \times 10^{-5}</math></li> <li>• 0x08 - <math>1 \times 10^{-6}</math></li> <li>• 0x09 - <math>1 \times 10^{-8}</math></li> </ul>
<i>deliveryErrSDU</i>	<p>- Delivery of erroneous SDUs</p> <ul style="list-style-type: none"> <li>• Indicates whether SDUs detected as erroneous shall be delivered or not.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>5 \times 10^{-2}</math></li> <li>• 0x02 - <math>1 \times 10^{-2}</math></li> <li>• 0x03 - <math>5 \times 10^{-3}</math></li> <li>• 0x04 - <math>4 \times 10^{-3}</math></li> <li>• 0x05 - <math>1 \times 10^{-3}</math></li> <li>• 0x06 - <math>1 \times 10^{-4}</math></li> <li>• 0x07 - <math>1 \times 10^{-5}</math></li> <li>• 0x08 - <math>1 \times 10^{-6}</math></li> <li>• 0x09 - <math>1 \times 10^{-8}</math></li> </ul>

<i>transferDelay</i>	- Transfer delay (ms) <ul style="list-style-type: none"> <li>Indicates the targeted time between a request to transfer an SDU at one SAP to its delivery at the other SAP in milliseconds.</li> </ul>
<i>trafficPriority</i>	- Transfer handling priority <ul style="list-style-type: none"> <li>Specifies the relative importance for handling of SDUs that belong to the UMTS bearer, compared to the SDUs of other bearers.</li> </ul>

## 8.280.2 Field Documentation

8.280.2.1 `uint8_t LibPackUMTSQoS::deliveryErrSDU`

8.280.2.2 `uint32_t LibPackUMTSQoS::grntDownlinkBitrate`

8.280.2.3 `uint32_t LibPackUMTSQoS::grntUplinkBitrate`

8.280.2.4 `uint32_t LibPackUMTSQoS::maxDownlinkBitrate`

8.280.2.5 `uint32_t LibPackUMTSQoS::maxSDUSize`

8.280.2.6 `uint32_t LibPackUMTSQoS::maxUplinkBitrate`

8.280.2.7 `uint8_t LibPackUMTSQoS::qosDeliveryOrder`

8.280.2.8 `uint8_t LibPackUMTSQoS::resBerRatio`

8.280.2.9 `uint8_t LibPackUMTSQoS::sduErrorRatio`

8.280.2.10 `uint8_t LibPackUMTSQoS::trafficClass`

8.280.2.11 `uint32_t LibPackUMTSQoS::trafficPriority`

8.280.2.12 `uint32_t LibPackUMTSQoS::transferDelay`

## 8.281 LibPackUMTSReqQoSsigInd Struct Reference

### Data Fields

- [LibPackUMTSQoS UMTSReqQoS](#)
- `uint8_t` [SigInd](#)

### 8.281.1 Detailed Description

structure contains UMTS requested QoS with Signaling Indication flag

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>UMTSReqQoS</i>	<ul style="list-style-type: none"> <li>• Contains the UMTS Quality Of Service Information</li> </ul>
<i>SigInd</i>	- Signaling Indication flag <ul style="list-style-type: none"> <li>• TRUE - Signaling indication ON</li> <li>• FALSE - Signaling indication OFF</li> </ul>

## 8.281.2 Field Documentation

8.281.2.1 `uint8_t LibPackUMTSReqQoSSigInd::SigInd`8.281.2.2 `LibPackUMTSQoS LibPackUMTSReqQoSSigInd::UMTSReqQoS`

## 8.282 lineCtrlInfo Struct Reference

## Data Fields

- [BYTE polarityIncluded](#)
- [BYTE toggleMode](#)
- [BYTE revPolarity](#)
- [BYTE pwrDenialTime](#)

## 8.282.1 Detailed Description

This structure contains Line Control Information

## Parameters

<i>polarityIncluded</i>	<ul style="list-style-type: none"> <li>• Included Polarity; Boolean Value</li> </ul>
<i>toggleMode</i>	<ul style="list-style-type: none"> <li>• Toggle mode; Boolean Value</li> </ul>
<i>revPolarity</i>	<ul style="list-style-type: none"> <li>• Reverse Polarity; Boolean Value</li> </ul>
<i>pwrDenialTime</i>	<ul style="list-style-type: none"> <li>• Power denial time; refer to [S1, Section 3.7.5.15 Line Control] for valid values</li> </ul>

## 8.282.2 Field Documentation

8.282.2.1 `BYTE lineCtrlInfo::polarityIncluded`8.282.2.2 `BYTE lineCtrlInfo::pwrDenialTime`8.282.2.3 `BYTE lineCtrlInfo::revPolarity`



## 8.282.2.4 BYTE lineCtrlInfo::toggleMode

## 8.283 loc\_BdsSV Struct Reference

## Data Fields

- uint16\_t [id](#)
- uint8\_t [mask](#)

## 8.283.1 Detailed Description

This structure contains the BDS [SV](#) Info

## Parameters

<i>id</i>	<ul style="list-style-type: none"><li>• <a href="#">SV</a> ID of the satellite whose data is to be deleted.<ul style="list-style-type: none"><li>– Range for BDS: 201 to 237</li></ul></li></ul>
<i>mask</i>	<ul style="list-style-type: none"><li>• Indicates if the ephemeris or almanac for a satellite is to be deleted</li><li>• Valid values:<ul style="list-style-type: none"><li>– QMI_LOC_MASK_DELETE_EPHEMERIS (0x01) - Delete ephemeris for the satellite</li><li>– QMI_LOC_MASK_DELETE_ALMANAC (0x02) - Delete almanac for the satellite</li></ul></li></ul>

## 8.283.2 Field Documentation

## 8.283.2.1 uint16\_t loc\_BdsSV::id

## 8.283.2.2 uint8\_t loc\_BdsSV::mask

## 8.284 loc\_BdsSVInfo Struct Reference

## Data Fields

- uint8\_t [len](#)
- [loc\\_BdsSV](#) \* [pSV](#)

## 8.284.1 Detailed Description

This structure contains the number of sets of the BDS SVN Info

## Parameters

<i>len</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements: <ul style="list-style-type: none"> <li>gnssSvId</li> <li>deleteSvInfoMask</li> </ul> </li> </ul>
<i>pSV</i>	<ul style="list-style-type: none"> <li>Pointer to struct <a href="#">loc_BdsSV</a>. See <a href="#">loc_BdsSV</a> for more information</li> </ul>

## 8.284.2 Field Documentation

8.284.2.1 `uint8_t loc_BdsSVInfo::len`

8.284.2.2 `loc_BdsSV* loc_BdsSVInfo::pSV`

## 8.285 loc\_CellDb Struct Reference

### Data Fields

- `uint32_t` [mask](#)

### 8.285.1 Detailed Description

This structure contains the cell database

#### Parameters

<i>mask</i>	<ul style="list-style-type: none"> <li>Mask for the cell database assistance data that is to be deleted</li> <li>Valid values: <ul style="list-style-type: none"> <li>0x00000001 - DELETE_CELLDB_POS</li> <li>0x00000002 - DELETE_CELLDB_LATEST_GPS_POS</li> <li>0x00000004 - DELETE_CELLDB_OTA_POS</li> <li>0x00000008 - DELETE_CELLDB_EXT_REF_POS</li> <li>0x00000010 - DELETE_CELLDB_TIMETAG</li> <li>0x00000020 - DELETE_CELLDB_CELLID</li> <li>0x00000040 - DELETE_CELLDB_CACHED_CELLID</li> <li>0x00000080 - DELETE_CELLDB_LAST_SRV_CELL</li> <li>0x00000100 - DELETE_CELLDB_CUR_SRV_CELL</li> <li>0x00000200 - DELETE_CELLDB_NEIGHBOR_INFO</li> </ul> </li> </ul>
-------------	--

## 8.285.2 Field Documentation

8.285.2.1 `uint32_t loc_CellDb::mask`

## 8.286 loc\_ClkInfo Struct Reference

### Data Fields

- uint32\_t [mask](#)

### 8.286.1 Detailed Description

This structure contains the clock Info

## Parameters

<i>mask</i>	<ul style="list-style-type: none"> <li>• Mask for the clock information assistance data that is to be deleted</li> <li>• Valid bitmasks: <ul style="list-style-type: none"> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_TIME_EST (0x00000001) - Mask to delete time estimate from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_FREQ_EST (0x00000002) - Mask to delete frequency estimate from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_WEEK_NUMBER (0x00000004) - Mask to delete week number from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_RTC_TIME (0x00000008) - Mask to delete RTC time from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_TIME_TRANSFER (0x00000010) - Mask to delete time transfer from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GPSTIME_EST (0x00000020) - Mask to delete GPS time estimate from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GLOTIME_EST (0x00000040) - Mask to delete GLONASS time estimate from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GLODAY_NUMBER (0x00000080) - Mask to delete GLONASS day number from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GLO4YEAR_NUMBER (0x00000100) - Mask to delete GLONASS four year number from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GLO_RF_GRP_DELAY (0x00000200) - Mask to delete GLONASS RF GRP delay from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_DISABLE_TT (0x00000400) - Mask to delete disable TT from clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GG_LEAPSEC (0x00000800) - Mask to delete a BDS time estimate from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GG_GGTB (0x00001000) - Mask to delete a BDS time estimate from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_BDSTIME_EST (0x00002000) - Mask to delete a BDS time estimate from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_GB_GBTB (0x00004000) - Mask to delete Glonass-to-BDS time bias-related information from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_BG_BGTB (0x00008000) - Mask to delete BDS-to-GLONASS time bias-related information from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_BDSWEEK_NUMBER (0x00010000) - Mask to delete the BDS week number from the clock information</li> <li>– QMI_LOC_MASK_DELETE_CLOCK_INFO_BDS_RF_GRP_DELAY (0x00020000) - Mask to delete the BDS RF GRP delay from the clock information</li> </ul> </li> </ul>
-------------	--

## 8.286.2 Field Documentation

8.286.2.1    `uint32_t loc_ClkInfo::mask`

## 8.287    loc\_GnssData Struct Reference

### Data Fields

- `uint64_t` [mask](#)

### 8.287.1    Detailed Description

This structure contains the GNSS data

## Parameters

mask	<ul style="list-style-type: none"> <li>• Mask for the GNSS data that is to be deleted</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– QMI_LOC_MASK_DELETE_GPS_SVDIR (0x00000001) - Mask to delete GPS SVDIR</li> <li>– QMI_LOC_MASK_DELETE_GPS_SVSTEER (0x00000002) - Mask to delete GPS SVSTEER</li> <li>– QMI_LOC_MASK_DELETE_GPS_TIME (0x00000004) - Mask to delete GPS time</li> <li>– QMI_LOC_MASK_DELETE_GPS_ALM_CORR (0x00000008) - Mask to delete almanac correlation</li> <li>– QMI_LOC_MASK_DELETE_GLO_SVDIR (0x00000010) - Mask to delete GLO-NASS SVDIR</li> <li>– QMI_LOC_MASK_DELETE_GLO_SVSTEER (0x00000020) - Mask to delete G-LONASS SVSTEER</li> <li>– QMI_LOC_MASK_DELETE_GLO_TIME (0x00000040) - Mask to delete GLONASS time</li> <li>– QMI_LOC_MASK_DELETE_GLO_ALM_CORR (0x00000080) - Mask to delete GLONASS almanac correlation</li> <li>– QMI_LOC_MASK_DELETE_SBAS_SVDIR (0x00000100) - Mask to delete SBAS SVDIR</li> <li>– QMI_LOC_MASK_DELETE_SBAS_SVSTEER (0x00000200) - Mask to delete SBAS SVSTEER</li> <li>– QMI_LOC_MASK_DELETE_POSITION (0x00000400) - Mask to delete position estimate</li> <li>– QMI_LOC_MASK_DELETE_TIME (0x00000800) - Mask to delete time estimate</li> <li>– QMI_LOC_MASK_DELETE_IONO (0x00001000) - Mask to delete IONO</li> <li>– QMI_LOC_MASK_DELETE_UTC (0x00002000) - Mask to delete UTC estimate</li> <li>– QMI_LOC_MASK_DELETE_HEALTH (0x00004000) - Mask to delete <a href="#">SV</a> health record</li> <li>– QMI_LOC_MASK_DELETE_SADATA (0x00008000) - Mask to delete SADATA</li> <li>– QMI_LOC_MASK_DELETE_RTI (0x00010000) - Mask to delete RTI</li> <li>– QMI_LOC_MASK_DELETE_SV_NO_EXIST (0x00020000) - Mask to delete SV_NO_EXIST</li> <li>– QMI_LOC_MASK_DELETE_FREQ_BIAS_EST (0x00040000) - Mask to delete frequency bias estimate</li> <li>– QMI_LOC_MASK_DELETE_BDS_SVDIR (0x00080000) - Mask to delete BDS SVDIR</li> <li>– QMI_LOC_MASK_DELETE_BDS_SVSTEER (0x00100000) - Mask to delete BDS SVSTEER</li> <li>– QMI_LOC_MASK_DELETE_BDS_TIME (0x00200000) - Mask to delete BDS time</li> <li>– QMI_LOC_MASK_DELETE_BDS_ALM_CORR (0x00400000) - Mask to delete BDS almanac correlation</li> <li>– QMI_LOC_MASK_DELETE_GNSS_SV_BLACKLIST_GPS (0x00800000) - Mask to delete GNSS <a href="#">SV</a> blacklist GPS</li> <li>– QMI_LOC_MASK_DELETE_GNSS_SV_BLACKLIST_GLO (0x01000000) - Mask to delete GNSS <a href="#">SV</a> blacklist GLO</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– QMI_LOC_MASK_DELETE_GNSS_SV_BLACKLIST_BDS (0x02000000) - Mask to delete GNSS <a href="#">SV</a> blacklist BDS</li> </ul>

## 8.287.2 Field Documentation

8.287.2.1 `uint64_t loc_GnssData::mask`

## 8.288 loc\_gpsTime Struct Reference

### Data Fields

- `uint16_t` [gpsWeek](#)
- `uint32_t` [gpsTimeOfWeekMs](#)

### 8.288.1 Detailed Description

This structure contains GPS Time info.

#### Parameters

<i>gpsWeek</i>	<ul style="list-style-type: none"> <li>• Current GPS week as calculated from midnight, Jan. 6, 1980.</li> <li>• Units - Weeks</li> </ul>
<i>gpsTimeOf-WeekMs</i>	<ul style="list-style-type: none"> <li>• Amount of time into the current GPS week.</li> <li>• Units - Milliseconds</li> </ul>

## 8.288.2 Field Documentation

8.288.2.1 `uint32_t loc_gpsTime::gpsTimeOfWeekMs`

8.288.2.2 `uint16_t loc_gpsTime::gpsWeek`

## 8.289 loc\_LocApplicationInfo Struct Reference

### Data Fields

- `uint8_t` [appProviderLength](#)
- `uint8_t *` [pAppProvider](#)
- `uint8_t` [appNameLength](#)
- `uint8_t *` [pAppName](#)
- `uint8_t` [appVersionValid](#)
- `uint8_t` [appVersionLength](#)
- `uint8_t *` [pAppVersion](#)

### 8.289.1 Detailed Description

This structure contains the Application Information

## Parameters

<i>appProviderLength</i>	<ul style="list-style-type: none"> <li>Length of the Application Provider</li> </ul>
<i>pAppProvider</i>	<ul style="list-style-type: none"> <li>Application Provider</li> <li>Depends upon the Length of application Provider</li> </ul>
<i>appNameLength</i>	<ul style="list-style-type: none"> <li>Length of Application Name</li> </ul>
<i>pAppName</i>	<ul style="list-style-type: none"> <li>Application Name</li> <li>Depends upon the Length of application Name</li> </ul>
<i>appVersionValid</i>	<ul style="list-style-type: none"> <li>Specifies whether the application version string contains a valid value</li> <li>0x00 (FALSE) Application version string is invalid</li> <li>0x01 (TRUE) Application version string is valid</li> </ul>
<i>appVersionLength</i>	<ul style="list-style-type: none"> <li>Length of Application Version</li> </ul>
<i>pAppVersion</i>	<ul style="list-style-type: none"> <li>Application Version</li> <li>Depends upon the Length of application Version</li> </ul>

## 8.289.2 Field Documentation

8.289.2.1 `uint8_t loc_LocApplicationInfo::appNameLength`8.289.2.2 `uint8_t loc_LocApplicationInfo::appProviderLength`8.289.2.3 `uint8_t loc_LocApplicationInfo::appVersionLength`8.289.2.4 `uint8_t loc_LocApplicationInfo::appVersionValid`8.289.2.5 `uint8_t* loc_LocApplicationInfo::pAppName`8.289.2.6 `uint8_t* loc_LocApplicationInfo::pAppProvider`8.289.2.7 `uint8_t* loc_LocApplicationInfo::pAppVersion`8.290 `loc_precisionDilution` Struct Reference

## Data Fields

- `uint32_t` [PDOP](#)



- uint32\_t [HDOP](#)
- uint32\_t [VDOP](#)

### 8.290.1 Detailed Description

This structure contains Dilution of precision associated with this position.

Parameters

<i>PDOP</i>	<ul style="list-style-type: none"> <li>• Position dilution of precision.</li> <li>• Range - 1 (highest accuracy) to 50 (lowest accuracy)</li> <li>• PDOP = square root of (Square of HDOP + Square of VDOP<sup>2</sup> )</li> </ul>
<i>HDOP</i>	<ul style="list-style-type: none"> <li>• Horizontal dilution of precision.</li> <li>• Range - 1 (highest accuracy) to 50 (lowest accuracy)</li> </ul>
<i>VDOP</i>	<ul style="list-style-type: none"> <li>• Vertical dilution of precision.</li> <li>• Range- 1 (highest accuracy) to 50 (lowest accuracy)</li> </ul>

### 8.290.2 Field Documentation

8.290.2.1 uint32\_t loc\_precisionDilution::HDOP

8.290.2.2 uint32\_t loc\_precisionDilution::PDOP

8.290.2.3 uint32\_t loc\_precisionDilution::VDOP

## 8.291 loc\_sensorDataUsage Struct Reference

Data Fields

- uint32\_t [usageMask](#)
- uint32\_t [aidingIndicatorMask](#)

### 8.291.1 Detailed Description

This structure contains Sensor Data Usage info.

Parameters

<i>usageMask</i>	<ul style="list-style-type: none"> <li>• Specifies which sensors were used in calculating the position in the position report.</li> </ul>
------------------	---

- Value
  - 0x00000001 - Accelerometer used
  - 0x00000002 - Gyroscope used

## Parameters

<i>aidingIndicatorMask</i>	
----------------------------	--

- Specifies which results were aided by sensors.

- Value

- 0x00000001 - AIDED\_HEADING
- 0x00000002 - AIDED\_SPEED
- 0x00000004 - AIDED\_POSITION
- 0x00000008 - AIDED\_VELOCITY

## 8.291.2 Field Documentation

8.291.2.1 `uint32_t loc_sensorDataUsage::aidingIndicatorMask`

8.291.2.2 `uint32_t loc_sensorDataUsage::usageMask`

## 8.292 loc\_SV Struct Reference

### Data Fields

- `uint16_t id`
- `uint32_t system`
- `uint8_t mask`

### 8.292.1 Detailed Description

This structure contains the Delete LOC [SV](#) Info

## Parameters

<i>id</i>	<ul style="list-style-type: none"> <li>• LOC <a href="#">SV</a> ID of the satellite whose data is to be deleted</li> <li>• Range: <ul style="list-style-type: none"> <li>– For GPS: 1 to 32</li> <li>– For SBAS: 33 to 64</li> <li>– For GLONASS: 65 to 96</li> </ul> </li> </ul>
-----------	---

<i>system</i>	<ul style="list-style-type: none"> <li>Indicates to which constellation this <a href="#">loc_SV</a> belongs</li> <li>Valid values: <ul style="list-style-type: none"> <li>eQMI_LOC_SV_SYSTEM_GPS (1) - GPS satellite</li> <li>eQMI_LOC_SV_SYSTEM_GALILEO (2) - GALILEO satellite</li> <li>eQMI_LOC_SV_SYSTEM_SBAS (3) - SBAS satellite</li> <li>eQMI_LOC_SV_SYSTEM_COMPASS (4) - COMPASS satellite</li> <li>eQMI_LOC_SV_SYSTEM_GLONASS (5) - GLONASS satellite</li> <li>eQMI_LOC_SV_SYSTEM_BDS (6) - BDS satellite</li> </ul> </li> </ul>
<i>mask</i>	<ul style="list-style-type: none"> <li>Indicates if the ephemeris or almanac for a satellite is to be deleted</li> <li>Valid values: <ul style="list-style-type: none"> <li>0x01 - DELETE_EPHEMERIS</li> <li>0x02 - DELETE_ALMANAC</li> </ul> </li> </ul>

## 8.292.2 Field Documentation

8.292.2.1 `uint16_t loc_SV::id`

8.292.2.2 `uint8_t loc_SV::mask`

8.292.2.3 `uint32_t loc_SV::system`

## 8.293 loc\_SVInfo Struct Reference

### Data Fields

- `uint8_t len`
- `loc_SV * pSV`

### 8.293.1 Detailed Description

This structure contains the elements of Delete LOC [SV](#) Info

#### Parameters

<i>len</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements in struct <a href="#">loc_SV</a>: <ul style="list-style-type: none"> <li>gnssSvId</li> <li>system</li> <li>deleteSvInfoMask</li> </ul> </li> </ul>
------------	--

<i>pSV</i>	<ul style="list-style-type: none"> <li>• Pointer to struct <a href="#">loc_SV</a>. See <a href="#">loc_SV</a> for more information</li> </ul>
------------	---

## 8.293.2 Field Documentation

8.293.2.1 `uint8_t loc_SVInfo::len`

8.293.2.2 `loc_SV* loc_SVInfo::pSV`

## 8.294 loc\_svUsedforFix Struct Reference

### Data Fields

- `uint8_t gnssSvUsedList_len`
- `uint16_t gnssSvUsedList [255]`

### 8.294.1 Detailed Description

This structure contains SVs Used to Calculate the Fix.

#### Parameters

<i>gnssSvUsedList_len</i>	<ul style="list-style-type: none"> <li>• Number of sets of gnssSvUsedList</li> </ul>
<i>pGnssSvUsedList</i>	<ul style="list-style-type: none"> <li>• Entry in the list contains the <a href="#">SV</a> ID of a satellite used for calculating this position report.</li> <li>• Following information is associated with each <a href="#">SV</a> ID: <ul style="list-style-type: none"> <li>– GPS - 1 to 32</li> <li>– SBAS - 33 to 64</li> <li>– GLONASS - 65 to 96</li> <li>– QZSS - 193 to 197</li> <li>– BDS - 201 to 237</li> </ul> </li> </ul>

## 8.294.2 Field Documentation

8.294.2.1 `uint16_t loc_svUsedforFix::gnssSvUsedList[255]`

8.294.2.2 `uint8_t loc_svUsedforFix::gnssSvUsedList_len`

## 8.295 LocApplicationInfo Struct Reference

### Data Fields

- `BYTE appProviderLength`
- `CHAR * pAppProvider`
- `BYTE appNameLength`

- [CHAR \\* pAppName](#)
- [BYTE appVersionValid](#)
- [CHAR appVersionLength](#)
- [CHAR \\* pAppVersion](#)

### 8.295.1 Detailed Description

This structure contains the Application Information

#### Parameters

<i>appProviderLength</i>	<ul style="list-style-type: none"> <li>• Length of the Application Provider</li> </ul>
<i>pAppProvider</i>	<ul style="list-style-type: none"> <li>• Application Provider</li> <li>• Depends upon the Length of application Provider</li> </ul>
<i>appNameLength</i>	<ul style="list-style-type: none"> <li>• Length of Application Name</li> </ul>
<i>pAppName</i>	<ul style="list-style-type: none"> <li>• Application Name</li> <li>• Depends upon the Length of application Name</li> </ul>
<i>appVersionValid</i>	<ul style="list-style-type: none"> <li>• Specifies whether the application version string contains a valid value</li> <li>• 0x00 (FALSE) – Application version string is invalid</li> <li>• 0x01 (TRUE) – Application version string is valid</li> </ul>
<i>appVersionLength</i>	<ul style="list-style-type: none"> <li>• Length of Application Version</li> </ul>
<i>pAppVersion</i>	<ul style="list-style-type: none"> <li>• Application Version</li> <li>• Depends upon the Length of application Version</li> </ul>

### 8.295.2 Field Documentation

8.295.2.1 **BYTE** LocApplicationInfo::appNameLength

8.295.2.2 **BYTE** LocApplicationInfo::appProviderLength

8.295.2.3 **CHAR** LocApplicationInfo::appVersionLength

8.295.2.4 **BYTE** LocApplicationInfo::appVersionValid

8.295.2.5 **CHAR\*** LocApplicationInfo::pAppName

8.295.2.6 **CHAR\*** LocApplicationInfo::pAppProvider

8.295.2.7 **CHAR\*** LocApplicationInfo::pAppVersion

## 8.296 LocDelAssDataReq Struct Reference

### Data Fields

- [SVInfo](#) \* [pSVInfo](#)
- [GnssData](#) \* [pGnssData](#)
- [CellDb](#) \* [pCellDb](#)
- [ClkInfo](#) \* [pClkInfo](#)
- [BdsSVInfo](#) \* [pBdsSVInfo](#)

### 8.296.1 Detailed Description

This structure contains LOC delete assist data request

#### Parameters

<i>pSVInfo</i> [IN]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">SVInfo</a>. See <a href="#">SVInfo</a> for more information</li> </ul>
<i>pGnssData</i> [IN]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">GnssData</a>. See <a href="#">GnssData</a> for more information</li> </ul>
<i>pCellDb</i> [IN]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">CellDb</a>. See <a href="#">CellDb</a> for more information</li> </ul>
<i>pClkInfo</i> [IN]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">ClkInfo</a>. See <a href="#">ClkInfo</a> for more information</li> </ul>
<i>pBdsSVInfo</i> [IN]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">BdsSVInfo</a>. See <a href="#">BdsSVInfo</a> for more information</li> </ul>

### 8.296.2 Field Documentation

8.296.2.1 **BdsSVInfo\*** LocDelAssDataReq::pBdsSVInfo

8.296.2.2 **CellDb\*** LocDelAssDataReq::pCellDb

8.296.2.3 **ClkInfo\*** LocDelAssDataReq::pClkInfo

8.296.2.4 **GnssData\*** LocDelAssDataReq::pGnssData

8.296.2.5 SVInfo\* LocDelAssDataReq::pSVInfo

## 8.297 LOCEventRegisterReqResp Struct Reference

### Data Fields

- [ULONGLONG eventRegister](#)

### 8.297.1 Detailed Description

This structure contains the Parameter for RegisterEvents

## Parameters

<i>pEventRegMask</i>	<ul style="list-style-type: none"> <li>• Specifies the events that the control point is interested in receiving. -Values             <ul style="list-style-type: none"> <li>– 0x00000001 - to receive position report event indications</li> <li>– 0x00000002 - to receive satellite report event indications. These reports are sent at a 1 Hz rate.</li> <li>– 0x00000004 - to receive NMEA reports for position and satellites in view. The report is at a 1 Hz rate.</li> <li>– 0x00000008 - to receive NI Notify/Verify request event indications</li> <li>– 0x00000010 - to receive time injection request event indications.</li> <li>– 0x00000020 - to receive predicted orbits request event indications.</li> <li>– 0x00000040 - to receive position injection request event indications.</li> <li>– 0x00000080 - to receive engine state report event indications.</li> <li>– 0x00000100 - to receive fix session status report event indications.</li> <li>– 0x00000200 - to receive Wi-Fi position request event indications.</li> <li>– 0x00000400 - to receive notifications from the location engine indicating its readiness to accept data from the sensors (accelerometer, gyroscope, etc.).</li> <li>– 0x00000800 - to receive time sync requests from the GPS engine. Time sync enables the GPS engine to synchronize its clock with the sensor processor's clock.</li> <li>– 0x00001000 - to receive Stationary Position Indicator (SPI) streaming report indications.</li> <li>– 0x00002000 - to receive location server requests. These requests are generated when the service wishes to establish a connection with a location server.</li> <li>– 0x00004000 - to receive notifications related to network-initiated Geofences. These events notify the client when a network-initiated Geofence is added, deleted, or edited.</li> <li>– 0x00008000 - to receive Geofence alerts. These alerts are generated to inform the client of the changes that may affect a Geofence, e.g., if GPS is turned off or if the network is unavailable.</li> <li>– 0x00010000 - to receive notifications when a Geofence is breached. These events are generated when a UE enters or leaves the perimeter of a Geofence. This breach report is for a single Geofence.</li> <li>– 0x00020000 - to register for pedometer control requests from the location engine. The location engine sends this event to control the injection of pedometer reports.</li> <li>– 0x00040000 - to register for motion data control requests from the location engine. The location engine sends this event to control the injection of motion data.</li> <li>– 0x00080000 - to receive notification when a batch is full. The location engine sends this event to notify of Batch Full for ongoing batching session.</li> <li>– 0x00100000 - to receive position report indications along with an ongoing batching session. The location engine sends this event to notify the batched position report while a batching session is ongoing.</li> <li>– 0x00200000 - to receive Wi-Fi Access Point (AP) data inject request event indications.</li> <li>– 0x00400000 - to receive notifications when a Geofence is breached. These events are generated when a UE enters or leaves the perimeter of a Geofence. This breach notification is for multiple Geofences. Breaches from multiple Geofences are all batched and sent in the same notification.</li> <li>– 0x00800000 - to receive notifications from the location engine indicating its readiness to accept vehicle data (vehicle accelerometer, vehicle angular rate, vehicle odometry, etc.).</li> </ul> </li> </ul>
	<p>Generated on Tue Jul 12 2016 10:59:49 for LinuxQMSDK by Doxygen</p> <ul style="list-style-type: none"> <li>– 0x01000000 - to receive system clock and satellite measurement report events (system clock, <a href="#">SV</a> time, Doppler, etc.).</li> <li>– 0x02000000 - to receive satellite position reports as polynomials. Reports are generated only for the GNSS satellite constellations that are enabled using Q-</li> </ul>



**Note**

Multiple events can be registered by OR the individual masks and sending them in this TLV. All unused bits in this mask must be set to 0.

**8.297.2 Field Documentation**

8.297.2.1 **ULONGLONG** LOCEventRegisterReqResp::eventRegister

**8.298 LOCExtPowerStateReqResp Struct Reference****Data Fields**

- [ULONG](#) extPowerState

**8.298.1 Detailed Description**

This structure contains the Parameter External Power Source State.

**Parameters**

<i>pLOCEvent-RegisterReq-Resp</i>	<ul style="list-style-type: none"> <li>• Specifies the Power state; injected by the control point.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Device is not connected to an external power source</li> <li>– 1 - Device is connected to an external power source</li> <li>– 2 - Unknown external power state</li> </ul> </li> </ul>
-----------------------------------	---

**8.298.2 Field Documentation**

8.298.2.1 **ULONG** LOCExtPowerStateReqResp::extPowerState

**8.299 LocInjectPositionReq Struct Reference****Data Fields**

- [ULONGLONG](#) \* pLatitude
- [ULONGLONG](#) \* pLongitude
- [ULONG](#) \* pHorUncCircular
- [BYTE](#) \* pHorConfidence
- [ULONG](#) \* pHorReliability
- [ULONG](#) \* pAltitudeWrtEllipsoid
- [ULONG](#) \* pAltitudeWrtMeanSeaLevel
- [ULONG](#) \* pVertUnc
- [BYTE](#) \* pVertConfidence
- [ULONG](#) \* pVertReliability
- altitudeSrcInfo \* pAltitudeSrcInfo
- [ULONGLONG](#) \* pTimestampUtc
- [ULONG](#) \* pTimestampAge
- [ULONG](#) \* pPositionSrc

- `ULONG * pRawHorUncCircular`

- `BYTE * pRawHorConfidence`

### 8.299.1 Detailed Description

This structure contains LOC Inject Position parameters

## Parameters

<i>pLatitude</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Type - Floating point</li> <li>• Units - Degrees</li> <li>• Range - -90.0 to 90.0</li> <li>• Positive values indicate northern latitude</li> <li>• Negative values indicate southern latitude</li> <li>• Note - This field must be specified together with pLongitude and pHorUncCircular.</li> </ul>
<i>pLongitude</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Type - Floating point</li> <li>• Units - Degrees</li> <li>• Range - -180.0 to 180.0</li> <li>• Positive values indicate eastern latitude</li> <li>• Negative values indicate western latitude</li> <li>• Note - This field must be specified together with pLatitude and pHorUncCircular.</li> </ul>
<i>pHorUncCircular</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Horizontal position uncertainty.</li> <li>• Units - Meters</li> <li>• Note - This field must be specified together with pLatitude and pLongitude.</li> </ul>
<i>pHorConfidence</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Horizontal confidence.</li> <li>• Units - Percent</li> <li>• Values <ul style="list-style-type: none"> <li>– Valid Values - 1 to 99</li> <li>– Invalid Values - 0, 101 to 255</li> <li>– If 100 is received, reinterpret to 99</li> </ul> </li> <li>• Note - This field must be specified together with horizontal uncertainty. If not specified when pHorUncCircular is set, the default value is 50.</li> </ul>
<i>pHorReliability</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> </ul>

- Values

- 0 - Location reliability is not set.
- 1 - Location reliability is very low; use it at your own risk
- 2 - Location reliability is low; little or no cross-checking is possible.
- 3 - Location reliability is medium; limited cross-check passed
- 4 - Location reliability is high; strong cross-check passed

## Parameters

<i>pAltitudeWrt-Ellipsoid</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Altitude With Respect to Ellipsoid.</li> <li>• Units - Meters</li> <li>• Values <ul style="list-style-type: none"> <li>– Positive - height</li> <li>– Negative = depth</li> </ul> </li> </ul>
<i>pAltitudeWrt-MeanSeaLevel</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Altitude With Respect to Sea Level.</li> <li>• Units - Meters</li> </ul>
<i>pVertUnc</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Vertical uncertainty.</li> <li>• Units - Meters</li> <li>• Note - This is mandatory if either <i>pAltitudeWrtEllipsoid</i> or <i>pAltitudeWrtMeanSeaLevel</i> is specified.</li> </ul>
<i>pVertConfidence</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Vertical confidence.</li> <li>• Units - Percentage</li> <li>• Values <ul style="list-style-type: none"> <li>– Valid Values - 0 to 99</li> <li>– Invalid Values - 0, 100-256</li> <li>– If 100 is received, reinterpret to 99</li> </ul> </li> <li>• Note - This field must be specified together with the vertical uncertainty. If not specified, the default value will be 50.</li> </ul>
<i>pVertReliability</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> </ul>

- Values
  - 0 - Location reliability is not set.
  - 1 - Location reliability is very low; use it at your own risk.
  - 2 - Location reliability is low; little or no cross-checking is possible
  - 3 - Location reliability is medium; limited cross-check passed
  - 4 - Location reliability is high; strong cross-check passed

## Parameters

<i>pAltitudeSrcInfo</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> </ul>
-------------------------	--

- Pointer to struct [altitudeSrcInfo](#). See [altitudeSrcInfo](#) for more information

## Parameters

<i>pTimestampUtc</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>UTC timestamp</li> <li>Units - Milliseconds since Jan. 1, 1970</li> </ul>
<i>pTimestampAge</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Position age, which is an estimate of how long ago this fix was made.</li> <li>Units - Milliseconds</li> </ul>
<i>pPositionSrc</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Source from which this position was obtained</li> <li>Valid values <ul style="list-style-type: none"> <li>0 - Position source is GNSS</li> <li>1 - Position source is Cell ID</li> <li>2 - Position source is Enhanced Cell ID</li> <li>3 - Position source is Wi-Fi</li> <li>4 - Position source is Terrestrial</li> <li>5 - Position source is GNSS Terrestrial Hybrid</li> <li>6 - Other sources</li> </ul> </li> <li>Note - If altitude is specified and the altitude source is not specified, the engine assumes that the altitude was obtained using the specified position source. <ul style="list-style-type: none"> <li>If both altitude and altitude source are specified, the engine assumes that only latitude and longitude were obtained using the specified position source.</li> </ul> </li> </ul>

<i>pRawHorUnc-Circular</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Horizontal position uncertainty (circular) without any optimization.</li> <li>• Units - Meters</li> </ul>
<i>pRawHor-Confidence</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Horizontal confidence associated with raw horizontal uncertainty</li> <li>• Units: Percent</li> <li>• Values <ul style="list-style-type: none"> <li>– Valid values - 1 to 99</li> <li>– Invalid values - 0, 101 to 255</li> <li>– If 100 is received, reinterpret to 99</li> </ul> </li> <li>• Note - This field must be specified together with raw horizontal uncertainty. If not specified when rawHorUncCircular is set, the default value is 50.</li> </ul>

## 8.299.2 Field Documentation

8.299.2.1 **altitudeSrcInfo\*** LocInjectPositionReq::pAltitudeSrcInfo

8.299.2.2 **ULONG\*** LocInjectPositionReq::pAltitudeWrtEllipsoid

8.299.2.3 **ULONG\*** LocInjectPositionReq::pAltitudeWrtMeanSeaLevel

8.299.2.4 **BYTE\*** LocInjectPositionReq::pHorConfidence

8.299.2.5 **ULONG\*** LocInjectPositionReq::pHorReliability

8.299.2.6 **ULONG\*** LocInjectPositionReq::pHorUncCircular

8.299.2.7 **ULONGLONG\*** LocInjectPositionReq::pLatitude

8.299.2.8 **ULONGLONG\*** LocInjectPositionReq::pLongitude

8.299.2.9 **ULONG\*** LocInjectPositionReq::pPositionSrc

8.299.2.10 **BYTE\*** LocInjectPositionReq::pRawHorConfidence

8.299.2.11 **ULONG\*** LocInjectPositionReq::pRawHorUncCircular

8.299.2.12 **ULONG\*** LocInjectPositionReq::pTimestampAge

8.299.2.13 **ULONGLONG\*** LocInjectPositionReq::pTimestampUtc

8.299.2.14 **BYTE\*** LocInjectPositionReq::pVertConfidence

8.299.2.15 **ULONG\*** LocInjectPositionReq::pVertReliability

8.299.2.16 **ULONG\*** LocInjectPositionReq::pVertUnc

## 8.300 LocInjectSensorDataReq Struct Reference

### Data Fields

- **ULONG** \* pOpaqueIdentifier
- **sensorData** \* pAcceleroData
- **sensorData** \* pGyroData
- **ULONG** \* pAcceleroTimeSrc
- **ULONG** \* pGyroTimeSrc
- **temperatureData** \* pAcceleroTempData
- **temperatureData** \* pGyroTempData

### 8.300.1 Detailed Description

This structure contains parameters to inject sensor data into the GNSS location engine

#### Parameters

<i>pOpaque- Identifier</i>	<ul style="list-style-type: none"> <li>• Opaque Identifier (Optional parameter)</li> <li>• An opaque identifier that is sent in by the client that will be echoed in the indication so the client can relate the indication to the request.</li> </ul>
<i>pAcceleroData</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">sensorData</a>. See <a href="#">sensorData</a> for more information</li> </ul>
<i>pGyroData</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">sensorData</a>. See <a href="#">sensorData</a> for more information</li> </ul>
<i>pAcceleroTime- Src</i>	<ul style="list-style-type: none"> <li>• 3-Axis Accelerometer Data Time Source (Optional parameter)</li> <li>• The location service uses this field to identify the time reference used in the accelerometer data time stamps.</li> <li>• If not specified, the location service assumes that the time source for the accelerometer data is unknown.</li> <li>• Valid values             <ul style="list-style-type: none"> <li>– 0 - Sensor time source is unspecified</li> <li>– 1 - Time source is common between the sensors and the location engine</li> </ul> </li> </ul>



<i>pGyroTimeSrc</i>	<ul style="list-style-type: none"> <li>• 3-Axis Gyroscope Data Time Source (Optional)</li> <li>• The location service uses this field to identify the time reference used in the gyroscope data time stamps.</li> <li>• If not specified, the location service assumes that the time source for the gyroscope data is unknown.</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 0 - Sensor time source is unspecified</li> <li>– 1 - Time source is common between the sensors and the location engine</li> </ul> </li> </ul>
<i>pAcceleroTempData</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">temperatureData</a>. See <a href="#">temperatureData</a> for more information</li> </ul>
<i>pGyroTempData</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Pointer to struct <a href="#">temperatureData</a>. See <a href="#">temperatureData</a> for more information</li> </ul>

## 8.300.2 Field Documentation

8.300.2.1 **sensorData\*** LocInjectSensorDataReq::pAcceleroData

8.300.2.2 **tempratureData\*** LocInjectSensorDataReq::pAcceleroTempData

8.300.2.3 **ULONG\*** LocInjectSensorDataReq::pAcceleroTimeSrc

8.300.2.4 **sensorData\*** LocInjectSensorDataReq::pGyroData

8.300.2.5 **tempratureData\*** LocInjectSensorDataReq::pGyroTempData

8.300.2.6 **ULONG\*** LocInjectSensorDataReq::pGyroTimeSrc

8.300.2.7 **ULONG\*** LocInjectSensorDataReq::pOpaquelIdentifier

## 8.301 LocSetCradleMountReq Struct Reference

### Data Fields

- [ULONG](#) state
- [BYTE](#) \* pConfidence

### 8.301.1 Detailed Description

This structure contains parameters to set current cradle mount configuration

## Parameters

<i>state</i>	<ul style="list-style-type: none"> <li>• Cradle Mount State</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– 0 - Device is mounted on the cradle</li> <li>– 1 - Device is not mounted on the cradle</li> <li>– 2 - Unknown cradle mount state</li> </ul> </li> </ul>
<i>pConfidence</i>	<ul style="list-style-type: none"> <li>• Cradle Mount Confidence (Optional)</li> <li>• Confidence in the Cradle Mount state expressed as a percentage.</li> <li>• Range - 0 to 100</li> </ul>

## 8.301.2 Field Documentation

8.301.2.1 **BYTE\*** LocSetCradleMountReq::pConfidence8.301.2.2 **ULONG** LocSetCradleMountReq::state

## 8.302 LOCStartReq Struct Reference

## Data Fields

- [BYTE](#) SessionId
- [ULONG](#) \* pRecurrenceType
- [ULONG](#) \* pHorizontalAccuracyLvl
- [ULONG](#) \* pIntermediateReportState
- [ULONG](#) \* pMinIntervalTime
- [struct LocApplicationInfo](#) \* pApplicationInfo
- [ULONG](#) \* pConfigAltitudeAssumed

## 8.302.1 Detailed Description

This structure contains the LOC Start Request

## Parameters

<i>SessionId[IN]</i>	<ul style="list-style-type: none"> <li>• ID of the session as identified by the control point.</li> <li>• Range: 0 to 255</li> </ul>
----------------------	--

<i>pRecurrence-Type</i> [IN]	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Specifies the type of session in which the control point is interested.</li> <li>• Defaults to SINGLE. -Values <ul style="list-style-type: none"> <li>– 1 - Request periodic position fixes</li> <li>– 2 - Request a single position fix</li> </ul> </li> </ul>
<i>pHorizontal-AccuracyLvl</i> [IN]	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Specifies the horizontal accuracy level required by the control point.</li> <li>• Defaults to LOW</li> <li>• Values <ul style="list-style-type: none"> <li>– 1 - Low accuracy</li> <li>– 2 - Medium accuracy</li> <li>– 3 - High accuracy</li> </ul> </li> </ul>
<i>pIntermediate-ReportState</i> [IN]	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Specifies if the control point is interested in receiving intermediate reports.</li> <li>• ON by default.</li> <li>• Values <ul style="list-style-type: none"> <li>– 1 - Intermediate reports are turned on</li> <li>– 2 - Intermediate reports are turned off</li> </ul> </li> </ul>
<i>pMinInterval-Time</i> [IN]	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Minimum time interval, specified by the control point, that must elapse between position reports.</li> <li>• Units - Milliseconds</li> <li>• Default - 1000 ms</li> </ul>
<i>LocApplication-Info</i> [IN]	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• LOC Application Parameters</li> <li>• See <a href="#">LocApplicationInfo</a> for more information</li> </ul>

<i>pConfigAltitudeAssumed</i> [IN]	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Configuration for Altitude Assumed Info in GNSS <a href="#">SV</a> Info Event</li> <li>• Defaults to ENABLED.</li> <li>• Values <ul style="list-style-type: none"> <li>– 1 - Enable Altitude Assumed information in GNSS <a href="#">SV</a> Info Event</li> <li>– 2 - Disable Altitude Assumed information in GNSS <a href="#">SV</a> Info Event</li> </ul> </li> </ul>
------------------------------------	--

## 8.302.2 Field Documentation

8.302.2.1 struct LocApplicationInfo\* LOCStartReq::pApplicationInfo

8.302.2.2 ULONG\* LOCStartReq::pConfigAltitudeAssumed

8.302.2.3 ULONG\* LOCStartReq::pHorizontalAccuracyLvl

8.302.2.4 ULONG\* LOCStartReq::pIntermediateReportState

8.302.2.5 ULONG\* LOCStartReq::pMinIntervalTime

8.302.2.6 ULONG\* LOCStartReq::pRecurrenceType

8.302.2.7 BYTE LOCStartReq::SessionId

## 8.303 LOCStopReq Struct Reference

### Data Fields

- [BYTE sessionId](#)

### 8.303.1 Detailed Description

This structure contains the LOC Stop Request

#### Parameters

<i>sessionId</i>	<ul style="list-style-type: none"> <li>• ID of the session as identified by the control point.</li> <li>• Range: 0 to 255</li> </ul>
------------------	--

## 8.303.2 Field Documentation

8.303.2.1 BYTE LOCStopReq::sessionId

## 8.304 LteCQIParm Struct Reference

**Data Fields**

- [BYTE ValidityCW0](#)
- [BYTE CQIValueCW0](#)
- [BYTE ValidityCW1](#)
- [BYTE CQIValueCW1](#)

**8.304.1 Detailed Description**

This structure contains information about the SLQSSwiGetLteCQI response parameters.

**Parameters**

<i>pValidityCW0[OUT]</i>	<ul style="list-style-type: none"> <li>• Values             <ul style="list-style-type: none"> <li>– 0- Invalid.</li> <li>– 1- Valid.</li> </ul> </li> </ul>
<i>pCQIValueCW0[OUT]</i>	<ul style="list-style-type: none"> <li>• Values             <ul style="list-style-type: none"> <li>– Range 0~15</li> </ul> </li> </ul>
<i>pValidityCW1[OUT]</i>	<ul style="list-style-type: none"> <li>• Values             <ul style="list-style-type: none"> <li>– 0- Invalid.</li> <li>– 1- Valid.</li> </ul> </li> </ul>
<i>pCQIValueCW1[OUT]</i>	<ul style="list-style-type: none"> <li>• Values             <ul style="list-style-type: none"> <li>– Range 0~15</li> </ul> </li> </ul>

**8.304.2 Field Documentation**

8.304.2.1 **BYTE** LteCQIParm::CQIValueCW0

8.304.2.2 **BYTE** LteCQIParm::CQIValueCW1

8.304.2.3 **BYTE** LteCQIParm::ValidityCW0

8.304.2.4 **BYTE** LteCQIParm::ValidityCW1

**8.305 lteEARFCN Struct Reference****Data Fields**

- [BYTE status](#)
- [ULONG earfcn0](#)
- [ULONG earfcn1](#)

### 8.305.1 Detailed Description

This structure contains the parameters for WCDMA UARFCN.

#### Parameters

<i>status</i>	<ul style="list-style-type: none"> <li>• 0 - Disable</li> <li>• 1 - Enable</li> </ul>
<i>earfcn0</i>	<ul style="list-style-type: none"> <li>• Primary DL EARFCN to which the UE is locked</li> </ul>
<i>earfcn1</i>	<ul style="list-style-type: none"> <li>• Secondary DL EARFCN to which the UE is locked</li> <li>• Note : Make earfcn1 value equal to earfcn0 if only one EARFCN is desired.</li> </ul>

### 8.305.2 Field Documentation

8.305.2.1 **ULONG** `IteEARFCN::earfcn0`

8.305.2.2 **ULONG** `IteEARFCN::earfcn1`

8.305.2.3 **BYTE** `IteEARFCN::status`

## 8.306 IteGsmCellInfo Struct Reference

### Data Fields

- [BYTE](#) `cellReselPriority`
- [BYTE](#) `threshGsmHigh`
- [BYTE](#) `threshGsmLow`
- [BYTE](#) `nccPermitted`
- [BYTE](#) `cells_len`
- [gsmCellInfo](#) `GsmCellInfo` [255]

### 8.306.1 Detailed Description

This structure contains information about the LTE GSM Cell.

#### Parameters

<i>cellReselPriority</i>	<ul style="list-style-type: none"> <li>• Priority of this frequency group.</li> <li>• Range: 0 to 7.</li> <li>• This field is only valid when <code>ue_in_idle</code> is TRUE.</li> </ul>
--------------------------	---

<i>threshGsmHigh</i>	<ul style="list-style-type: none"> <li>• Reselection threshold for high priority layers.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>
<i>threshGsmLow</i>	<ul style="list-style-type: none"> <li>• Reselection threshold for low priority layers.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>
<i>nccPermitted</i>	<ul style="list-style-type: none"> <li>• Bitmask specifying whether a neighbor with a specific network color code is to be reported.</li> <li>• Range: 0 to 255.</li> <li>• Bit n set to 1 means a neighbor with NCC n must be included in the report. This flag is synonymous with a blacklist in other RATs.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>
<i>cells_len</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of gsm cells.</li> </ul>
<i>GsmCellInfo[MAX_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">gsmCellInfo</a> for more information.</li> </ul>

## 8.306.2 Field Documentation

8.306.2.1 **BYTE** `IteGsmCellInfo::cellReselPriority`

8.306.2.2 **BYTE** `IteGsmCellInfo::cells_len`

8.306.2.3 **gsmCellInfo** `IteGsmCellInfo::GsmCellInfo[255]`

8.306.2.4 **BYTE** `IteGsmCellInfo::nccPermitted`

8.306.2.5 **BYTE** `IteGsmCellInfo::threshGsmHigh`

8.306.2.6 **BYTE** `IteGsmCellInfo::threshGsmLow`

## 8.307 LTEInfo Struct Reference

### Data Fields

- [BYTE](#) `band`
- [BYTE](#) `bandwidth`
- [WORD](#) `RXChan`
- [WORD](#) `TXChan`
- [BYTE](#) `emmState`
- [BYTE](#) `emmSubState`

- [BYTE emmConnState](#)

### 8.307.1 Detailed Description

Structure for storing the LTE information for the device.



## Parameters

<i>band</i>	<ul style="list-style-type: none"> <li>• LTE Band <ul style="list-style-type: none"> <li>– 1 ~ 41 (Band in decimal)</li> <li>– 0xFF - Invalid</li> </ul> </li> </ul>
<i>bandwidth</i>	<ul style="list-style-type: none"> <li>• BandWidth. <ul style="list-style-type: none"> <li>– 0x00 - 1.4 MHz</li> <li>– 0x01 - 3 MHz</li> <li>– 0x02 - 5 MHz</li> <li>– 0x03 - 10 MHz</li> <li>– 0x04 - 15 MHz</li> <li>– 0x05 - 20 MHz</li> <li>– 0x06 - Invalid</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>RXChan</i>	<ul style="list-style-type: none"> <li>• RX channel number in decimal <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>TXChan</i>	<ul style="list-style-type: none"> <li>• TX channel number in decimal <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>emmState</i>	<ul style="list-style-type: none"> <li>• EMM State. <ul style="list-style-type: none"> <li>– 0x00 - Deregistered</li> <li>– 0x01 - Reg Initiated</li> <li>– 0x02 - Registered</li> <li>– 0x03 - TAU Initiated</li> <li>– 0x04 - SR Initiated</li> <li>– 0x05 - Dereg Initiated</li> <li>– 0x06 - Invalid</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>emmSubState</i>	<ul style="list-style-type: none"> <li>• EMM Sub State. <ul style="list-style-type: none"> <li>– 0xFF - NOT Applicable</li> </ul> </li> <li>• When EMM_state is 0x00: <ul style="list-style-type: none"> <li>– 0x00 - No IMSI</li> <li>– 0x01 - PLMN Search</li> <li>– 0x02 - Attach Needed</li> <li>– 0x03 - No Cell</li> <li>– 0x04 - Attaching</li> <li>– 0x05 - Normal Service</li> </ul> </li> </ul>

<i>emmConnState</i>	<ul style="list-style-type: none"> <li>• EMM Connected Mode State. <ul style="list-style-type: none"> <li>– 0x00 - RRC Idle</li> <li>– 0x01 - Waiting RRC Cfm</li> <li>– 0x02 - RRC Connected</li> <li>– 0x03 - RRC Releasing</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
---------------------	--

## 8.307.2 Field Documentation

8.307.2.1 **BYTE** LTEInfo::band

8.307.2.2 **BYTE** LTEInfo::bandwidth

8.307.2.3 **BYTE** LTEInfo::emmConnState

8.307.2.4 **BYTE** LTEInfo::emmState

8.307.2.5 **BYTE** LTEInfo::emmSubState

8.307.2.6 **WORD** LTEInfo::RXChan

8.307.2.7 **WORD** LTEInfo::TXChan

## 8.308 LTEInfoInterfreq Struct Reference

### Data Fields

- [BYTE](#) ueInIdle
- [BYTE](#) freqsLen
- [infoInterFreq](#) [InfoInterfreq](#) [255]

### 8.308.1 Detailed Description

This structure contains information about the LTE Inter-Frequency Network.

#### Parameters

<i>ueInIdle</i>	<ul style="list-style-type: none"> <li>• TRUE if the UE is in Idle mode, otherwise FALSE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
-----------------	--

<i>freqsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of inter frequency information.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>InfoInterfreq[MA- X_DESCRIPTOR- ON_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">infoInterFreq</a> for more information.</li> </ul>

## 8.308.2 Field Documentation

8.308.2.1 BYTE LTEInfoInterfreq::freqsLen

8.308.2.2 infoInterFreq LTEInfoInterfreq::InfoInterfreq[255]

8.308.2.3 BYTE LTEInfoInterfreq::ueInIdle

## 8.309 LTEInfoIntrafreq Struct Reference

### Data Fields

- [BYTE ueInIdle](#)
- [BYTE plmn](#) [3]
- [WORD tac](#)
- [ULONG globalCellId](#)
- [WORD earfcn](#)
- [WORD servingCellId](#)
- [BYTE cellReselPriority](#)
- [BYTE sNonIntraSearch](#)
- [BYTE threshServingLow](#)
- [BYTE sIntraSearch](#)
- [BYTE cellsLen](#)
- [cellParams CellParams](#) [255]

### 8.309.1 Detailed Description

This structure contains information about the LTE Intra-Frequency Network.

#### Parameters

<i>ueInIdle</i>	<ul style="list-style-type: none"> <li>• TRUE if the UE is in Idle mode, otherwise FALSE.</li> <li>– 0xFF - Not Available</li> </ul>
-----------------	--

<i>plmn[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>• PLMN ID coded as octet 3, 4, and 5.</li> </ul>
<i>tac</i>	<ul style="list-style-type: none"> <li>• Tracking area code. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>globalCellId</i>	<ul style="list-style-type: none"> <li>• Global cell ID in the system information block. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>earfcn</i>	<ul style="list-style-type: none"> <li>• E-UTRA absolute radio frequency channel number of the serving cell.</li> <li>• Range: 0 to 65535. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>servingCellId</i>	<ul style="list-style-type: none"> <li>• LTE serving cell ID.</li> <li>• Range: 0 to 503.</li> <li>• This is the cell ID of the serving cell and can be found in the cell list. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>cellReselPriority</i>	<ul style="list-style-type: none"> <li>• Priority for serving frequency.</li> <li>• Range: 0 to 7.</li> <li>• This field is only valid when <i>ue_in_idle</i> is TRUE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>sNonIntraSearch</i>	<ul style="list-style-type: none"> <li>• S non-intra search threshold to control non-intrafrequency searches.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when <i>ue_in_idle</i> is TRUE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>threshServing-Low</i>	<ul style="list-style-type: none"> <li>• Serving cell low threshold.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when ue_in_idle is TRUE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>sIntraSearch</i>	<ul style="list-style-type: none"> <li>• S Intra search threshold.</li> <li>• Range: 0 to 31.</li> <li>• The current cell measurement must fall below this threshold to consider intrafrequency for reselection.</li> <li>• This field is only valid when ue_in_idle is TRUE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>cellsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of cell params.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>CellParams[MAX_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">cellParams</a> for more information.</li> </ul>

## 8.309.2 Field Documentation

8.309.2.1 **cellParams** LTEInfoIntrafreq::CellParams[255]

8.309.2.2 **BYTE** LTEInfoIntrafreq::cellReselPriority

8.309.2.3 **BYTE** LTEInfoIntrafreq::cellsLen

8.309.2.4 **WORD** LTEInfoIntrafreq::earfcn

8.309.2.5 **ULONG** LTEInfoIntrafreq::globalCellId

8.309.2.6 **BYTE** LTEInfoIntrafreq::plmn[3]

8.309.2.7 **WORD** LTEInfoIntrafreq::servingCellId

8.309.2.8 **BYTE** LTEInfoIntrafreq::sIntraSearch

8.309.2.9 **BYTE** LTEInfoIntrafreq::sNonIntraSearch

8.309.2.10 **WORD** LTEInfoIntrafreq::tac

8.309.2.11 **BYTE** LTEInfoIntrafreq::threshServingLow

8.309.2.12 **BYTE** LTEInfoIntrafreq::ueInIdle

## 8.310 LTEInfoNeighboringGSM Struct Reference

### Data Fields

- [BYTE ueInIdle](#)
- [BYTE freqsLen](#)
- [lteGsmCellInfo lteGsmCellInfo](#) [255]

### 8.310.1 Detailed Description

This structure contains information about the LTE Neighboring GSM Network.

#### Parameters

<i>ueInIdle</i>	<ul style="list-style-type: none"> <li>• TRUE if the UE is in Idle mode, otherwise FALSE.</li> <li>– 0xFF - Not Available</li> </ul>
<i>freqsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of LTE GSM cell information.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>LteGsmCellInfo[ MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">lteGsmCellInfo</a> for more information.</li> </ul>

### 8.310.2 Field Documentation

8.310.2.1 **BYTE** LTEInfoNeighboringGSM::freqsLen

8.310.2.2 **lteGsmCellInfo** LTEInfoNeighboringGSM::lteGsmCellInfo[255]

8.310.2.3 **BYTE** LTEInfoNeighboringGSM::ueInIdle

## 8.311 LTEInfoNeighboringWCDMA Struct Reference

### Data Fields

- [BYTE ueInIdle](#)
- [BYTE freqsLen](#)
- [lteWcdmaCellInfo lteWCDMACellInfo](#) [255]

### 8.311.1 Detailed Description

This structure contains information about the LTE Neighboring WCDMA Network.

#### Parameters

<i>ueInIdle</i>	<ul style="list-style-type: none"> <li>• TRUE if the UE is in Idle mode, otherwise FALSE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>freqsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of LTE WCDMA cell information.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>LTEWCDMA-CellInfo[MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">lteWcdmaCellInfo</a> for more information.</li> </ul>

### 8.311.2 Field Documentation

8.311.2.1 BYTE LteInfoNeighboringWCDMA::freqsLen

8.311.2.2 lteWcdmaCellInfo LteInfoNeighboringWCDMA::LTEWCDMACellInfo[255]

8.311.2.3 BYTE LteInfoNeighboringWCDMA::ueInIdle

## 8.312 LteNasReleaseInfo\_s Struct Reference

### Data Fields

- [BYTE nas\\_release](#)
- [BYTE nas\\_major](#)
- [BYTE nas\\_minor](#)

### 8.312.1 Detailed Description

This structure contains LTE Nas Release Information

#### Parameters

<i>nas_release</i>	<ul style="list-style-type: none"> <li>• LTE NAS release</li> </ul>
<i>nas_major</i>	<ul style="list-style-type: none"> <li>• LTE NAS version major</li> </ul>
<i>nas_minor</i>	<ul style="list-style-type: none"> <li>• LTE NAS version minor</li> </ul>

### 8.312.2 Field Documentation

8.312.2.1 BYTE LteNasReleaseInfo\_s::nas\_major

8.312.2.2 BYTE LteNasReleaseInfo\_s::nas\_minor

## 8.312.2.3 BYTE LteNasReleaseInfo\_s::nas\_release

## 8.313 ItePCI Struct Reference

## Data Fields

- [BYTE status](#)
- [ULONG earfcn](#)
- [ULONG pci](#)

## 8.313.1 Detailed Description

This structure contains the parameters for WCDMA UARFCN.

## Parameters

<i>status</i>	<ul style="list-style-type: none"> <li>• 0 - Disable</li> <li>• 1 - Enable</li> </ul>
<i>earfcn</i>	<ul style="list-style-type: none"> <li>• UARFCN to which UE is locked</li> </ul>
<i>pci</i>	<ul style="list-style-type: none"> <li>• PCI to which the UE is locked</li> </ul>

## 8.313.2 Field Documentation

## 8.313.2.1 ULONG ItePCI::earfcn

## 8.313.2.2 ULONG ItePCI::pci

## 8.313.2.3 BYTE ItePCI::status

## 8.314 IteRsrpinformation Struct Reference

## Data Fields

- [SHORT rsrplevel](#)

## 8.314.1 Detailed Description

This structure contains the LTE RSRP Information

## Parameters

<i>rsrplevel</i>	<ul style="list-style-type: none"> <li>• LTE RSRP in dBm as a mesaured by L1. Range: -44 to -140(-44 means -44dBm, -140 means -140dBm).</li> </ul>
------------------	--



### 8.314.2 Field Documentation

8.314.2.1 SHORT lteRsrpInformation::rsrplevel

## 8.315 LTERSRPThresh Struct Reference

### Data Fields

- [BYTE LTERSRPThreshListLen](#)
- [WORD \\* pLTERSRPThreshList](#)

### 8.315.1 Detailed Description

This structure contains LTE RSRP threshold related parameters.

#### Parameters

<i>LTERSRP- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the LTE RSRP threshold list parameter to follow</li> </ul>
<i>pLTERSRP- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSRP thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values</li> <li>• Range for RSRP values: -140 to -44 (in dBm).</li> </ul>

### 8.315.2 Field Documentation

8.315.2.1 BYTE LTERSRPThresh::LTERSRPThreshListLen

8.315.2.2 WORD\* LTERSRPThresh::pLTERSRPThreshList

## 8.316 LTERSRQThresh Struct Reference

### Data Fields

- [BYTE LTERSRQThreshListLen](#)
- [WORD \\* pLTERSRQThreshList](#)

### 8.316.1 Detailed Description

This structure contains LTE RSRQ threshold related parameters.

#### Parameters

<i>LTERSRQ- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the LTE RSRQ threshold list parameter to follow</li> </ul>
-----------------------------------	---

<i>pLTERSRQ- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSRQ thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values.</li> <li>• Range for RSRQ values: -20 to -3 (in dBm)</li> </ul>
---------------------------------	--

### 8.316.2 Field Documentation

8.316.2.1 **BYTE** LTERSRQThresh::LTERSRQThreshListLen

8.316.2.2 **WORD\*** LTERSRQThresh::pLTERSRQThreshList

## 8.317 LTERSSIThresh Struct Reference

### Data Fields

- [BYTE LTERSSIThreshListLen](#)
- [WORD \\* pLTERSSIThreshList](#)

### 8.317.1 Detailed Description

This structure contains LTE RSSI threshold related parameters.

#### Parameters

<i>LTERSSI- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the LTE RSSI threshold list parameter to follow</li> </ul>
<i>pLTERSSI- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values.</li> <li>• Range for RSSI values: -120 to 0 (in dBm)</li> </ul>

### 8.317.2 Field Documentation

8.317.2.1 **BYTE** LTERSSIThresh::LTERSSIThreshListLen

8.317.2.2 **WORD\*** LTERSSIThresh::pLTERSSIThreshList

## 8.318 LTESigRptCfg Struct Reference

### Data Fields

- [BYTE rptRate](#)
- [BYTE avgPeriod](#)

### 8.318.1 Detailed Description

This structure contains LTE Signal Report Config parameters.

## Parameters

<i>rptRate</i>	<ul style="list-style-type: none"> <li>• Rate on how often the LTE signal must be checked for reporting</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Report using the default configuration</li> <li>– 1 - Report every 1 sec</li> <li>– 2 - Report every 2 sec</li> <li>– 3 - Report every 3 sec</li> <li>– 4 - Report every 4 sec</li> <li>– 5 - Report every 5 sec</li> </ul> </li> </ul>
<i>avgPeriod</i>	<ul style="list-style-type: none"> <li>• Averaging period to be used for the LTE signal</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Average using the default configuration</li> <li>– 1 - Average over 1 sec</li> <li>– 2 - Average over 2 sec</li> <li>– 3 - Average over 3 sec</li> <li>– 4 - Average over 4 sec</li> <li>– 5 - Average over 5 sec</li> <li>– 6 - Average over 6 sec</li> <li>– 7 - Average over 7 sec</li> <li>– 8 - Average over 8 sec</li> <li>– 9 - Average over 9 sec</li> <li>– 10 - Average over 10 sec</li> </ul> </li> </ul>

## 8.318.2 Field Documentation

8.318.2.1 BYTE LTESigRptCfg::avgPeriod

8.318.2.2 BYTE LTESigRptCfg::rptRate

## 8.319 LTESigRptConfig Struct Reference

## Data Fields

- [BYTE rptRate](#)
- [BYTE avgPeriod](#)

## 8.319.1 Detailed Description

This structure contains LTE RSRP threshold related parameters.

## Parameters

<i>rptRate</i>	<ul style="list-style-type: none"> <li>• Rate on how often the LTE signal must be checked for reporting Values</li> <li>• 0 - Report using the default configuration</li> <li>• 1 - Report every 1 sec</li> <li>• 2 - Report every 2 sec</li> <li>• 3 - Report every 3 sec</li> <li>• 4 - Report every 4 sec</li> <li>• 5 - Report every 5 sec</li> </ul>
<i>avgPeriod</i>	<ul style="list-style-type: none"> <li>• Averaging period to be used for the LTE signal.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Average using the default configuration</li> <li>– 1 - Average over 1 sec</li> <li>– 2 - Average over 2 sec</li> <li>– 3 - Average over 3 sec</li> <li>– 4 - Average over 4 sec</li> <li>– 5 - Average over 5 sec</li> <li>– 6 - Average over 6 sec</li> <li>– 7 - Average over 7 sec</li> <li>– 8 - Average over 8 sec</li> <li>– 9 - Average over 9 sec</li> <li>– 10 - Average over 10 sec</li> </ul> </li> </ul>

## 8.319.2 Field Documentation

8.319.2.1 BYTE lteSigRptConfig::avgPeriod

8.319.2.2 BYTE lteSigRptConfig::rptRate

## 8.320 lteSnrinformation Struct Reference

## Data Fields

- [SHORT snrlevel](#)

## 8.320.1 Detailed Description

This structure contains the LTE SNR Information

## Parameters

<i>snrlevel</i>	<ul style="list-style-type: none"> <li>LTE SNR level as a scaled integer in units of 0.1dB e.g. -16dB has a value of -160 and 24.6dB has value of 246.</li> </ul>
-----------------	---

## 8.320.2 Field Documentation

## 8.320.2.1 SHORT lteSnrinformation::snrlevel

## 8.321 LTESNRThresh Struct Reference

## Data Fields

- [BYTE LTESNRThresListLen](#)
- [SHORT \\* pLTESNRThresList](#)

## 8.321.1 Detailed Description

This structure contains LTE SNR threshold related parameters.

## Parameters

<i>LTESNRThres-ListLen</i>	<ul style="list-style-type: none"> <li>Length of the LTE SNR threshold list parameter to follow</li> </ul>
<i>pLTESNRThres-List</i>	<ul style="list-style-type: none"> <li>Sequence of thresholds delimiting SNR event reporting bands</li> <li>Every time a SNR value crosses a threshold value, an event report indication message with the new SNR value is sent to the requesting control point. For this field               <ul style="list-style-type: none"> <li>For LTE, each SNR threshold value is a signed 2 Byte value</li> <li>Maximum number of threshold values is 16</li> <li>At least one value must be specified</li> <li>SNR level as a scaled integer in units of 0.1 dB; e.g., -16 dB has a value of -160 and 24.6 dB has a value of 246</li> </ul> </li> </ul>

## 8.321.2 Field Documentation

## 8.321.2.1 BYTE LTESNRThresh::LTESNRThresListLen

## 8.321.2.2 SHORT\* LTESNRThresh::pLTESNRThresList

## 8.322 LTESNRThreshold Struct Reference

## Data Fields

- [BYTE LTESNRThreshListLen](#)
- [WORD \\* pLTESNRThreshList](#)

### 8.322.1 Detailed Description

This structure contains LTE SNR threshold related parameters.

#### Parameters

<i>LTESNRThresh-ListLen</i>	<ul style="list-style-type: none"> <li>Length of the LTE SNR threshold list parameter to follow</li> </ul>
<i>pLTESNR-ThreshList</i>	<ul style="list-style-type: none"> <li>Array of SNR thresholds (in units of 0.1 dB)</li> <li>Maximum of 32 values</li> <li>Range for SNR values: -20 to 30 (in dB).</li> </ul>

### 8.322.2 Field Documentation

8.322.2.1 BYTE LTESNRThreshold::LTESNRThreshListLen

8.322.2.2 WORD\* LTESNRThreshold::pLTESNRThreshList

## 8.323 LTESInfo Struct Reference

#### Data Fields

- [INT8 rssi](#)
- [INT8 rsrq](#)
- [SHORT rsrp](#)
- [SHORT snr](#)

### 8.323.1 Detailed Description

This structure contains the parameters for LTE Signal Strength Information

#### Parameters

<i>rssi</i>	<ul style="list-style-type: none"> <li>RSSI in dBm (signed value).</li> <li>A value of -125 dBm or lower is used to indicate No Signal. <ul style="list-style-type: none"> <li>For CDMA and UMTS, this indicates forward link pilot Ec</li> <li>For GSM, this indicates received signal strength</li> </ul> </li> </ul>
-------------	---

<i>rsrq</i>	<ul style="list-style-type: none"> <li>• RSRQ value in dB (signed integer value) as measured by L1.</li> <li>• Range: -3 to -20 (-3 means -3 dB, -20 means -20 dB).</li> </ul>
<i>rsrp</i>	<ul style="list-style-type: none"> <li>• Current RSRP in dBm as measured by L1.</li> <li>• Range: -44 to -140 (-44 means -44 dBm, -140 means -140 dBm).</li> </ul>
<i>snr</i>	<ul style="list-style-type: none"> <li>• SNR level as a scaled integer in units of 0.1 dB. e.g., -16 dB has a value of -160 and 24.6 dB has a value of 246,</li> </ul>

### 8.323.2 Field Documentation

#### 8.323.2.1 SHORT LTESSInfo::rsrp

#### 8.323.2.2 INT8 LTESSInfo::rsrq

#### 8.323.2.3 INT8 LTESSInfo::rssi

#### 8.323.2.4 SHORT LTESSInfo::snr

## 8.324 lteSSInfo Struct Reference

### Data Fields

- int8\_t [rssi](#)
- int8\_t [rsrq](#)
- int16\_t [rsrp](#)
- int16\_t [snr](#)

### 8.324.1 Detailed Description

#### Parameters

<i>rssi</i>	RSSI in dBm.
<i>rsrq</i>	RSRQ value in dB
<i>rsrp</i>	Current RSRP in dBm as measured by L1.
<i>snr</i>	SNR level as a scaled integer in units of 0.1 dB.

### 8.324.2 Field Documentation

#### 8.324.2.1 int16\_t lteSSInfo::rsrp

#### 8.324.2.2 int8\_t lteSSInfo::rsrq

#### 8.324.2.3 int8\_t lteSSInfo::rssi

#### 8.324.2.4 int16\_t lteSSInfo::snr



## 8.325 LTESysInfo Struct Reference

### Data Fields

- [sysInfoCommon](#) [sysInfoLTE](#)
- [BYTE](#) [lacValid](#)
- [WORD](#) [lac](#)
- [BYTE](#) [cellIdValid](#)
- [ULONG](#) [cellId](#)
- [BYTE](#) [regRejectInfoValid](#)
- [BYTE](#) [rejectSrvDomain](#)
- [BYTE](#) [rejCause](#)
- [BYTE](#) [networkIdValid](#)
- [BYTE](#) [MCC](#) [3]
- [BYTE](#) [MNC](#) [3]
- [BYTE](#) [tacValid](#)
- [WORD](#) [tac](#)

### 8.325.1 Detailed Description

Structure for storing the LTE System Information.

#### Parameters

<i>sysInfoLTE</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
<i>lacValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the location area code is valid.. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• Only applies to 3GPP. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>cellIdValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the cell ID is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>cellId</i>	<ul style="list-style-type: none"> <li>Cell ID. <ul style="list-style-type: none"> <li>0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>regRejectInfoValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the registration reject information is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>rejectSrvDomain</i>	<ul style="list-style-type: none"> <li>Type of service domain in which the registration is rejected. <ul style="list-style-type: none"> <li>0x00 - SYS_SRV_DOMAIN_NO_SRV - No service</li> <li>0x01 - Circuit-switched only</li> <li>0x02 - Packet-switched only</li> <li>0x03 - Circuit-switched and packet-switched</li> <li>0x04 - Camped</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>rejCause</i>	<ul style="list-style-type: none"> <li>Reject cause values sent are specified in [3GPP TS 24.008, Section 10.5.3.6]. <ul style="list-style-type: none"> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>networkIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the network ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>MCC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Country Code.</li> <li>MCC digits in ASCII characters</li> </ul>
<i>MNC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Network Code.</li> <li>MNC digits in ASCII characters</li> <li>An unused byte is set to 0xFF.</li> <li>In case of two-digit MNC values, the third (unused) digit is set to 0xFF. For example, 15 (a two-digit MNC) is reported using the byte stream 0x31 0x35 0xFF.</li> </ul>

<i>tacValid</i>	<ul style="list-style-type: none"> <li>Indicates whether tracking area code is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>tac</i>	<ul style="list-style-type: none"> <li>Tracking area code.</li> <li>Only applicable for LTE. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>

## 8.325.2 Field Documentation

8.325.2.1 **ULONG** lteSysInfo::cellId

8.325.2.2 **BYTE** lteSysInfo::cellIdValid

8.325.2.3 **WORD** lteSysInfo::lac

8.325.2.4 **BYTE** lteSysInfo::lacValid

8.325.2.5 **BYTE** lteSysInfo::MCC[3]

8.325.2.6 **BYTE** lteSysInfo::MNC[3]

8.325.2.7 **BYTE** lteSysInfo::networkIdValid

8.325.2.8 **BYTE** lteSysInfo::regRejectInfoValid

8.325.2.9 **BYTE** lteSysInfo::rejCause

8.325.2.10 **BYTE** lteSysInfo::rejectSrvDomain

8.325.2.11 **sysInfoCommon** lteSysInfo::sysInfoLTE

8.325.2.12 **WORD** lteSysInfo::tac

8.325.2.13 **BYTE** lteSysInfo::tacValid

## 8.326 lteWcdmaCellInfo Struct Reference

### Data Fields

- [WORD](#) uarfcn
- [BYTE](#) cellReselPriority
- [WORD](#) threshXhigh
- [WORD](#) threshXlow
- [BYTE](#) cellsLen
- [wcdmaCellInfo](#) [WCDMACellInfo](#) [255]

### 8.326.1 Detailed Description

This structure contains information about the LTE WCDMA Cell.

#### Parameters

<i>uarfcn</i>	<ul style="list-style-type: none"> <li>• WCDMA layer frequency.</li> <li>• Range: 0 to 16383.</li> </ul>
<i>cellReselPriority</i>	<ul style="list-style-type: none"> <li>• Cell re-selection priority.</li> <li>• Range: 0 to 7.</li> <li>• This field is only valid when <i>ue_in_idle</i> is TRUE.</li> </ul>
<i>threshXhigh</i>	<ul style="list-style-type: none"> <li>• Re-selection low threshold.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when <i>ue_in_idle</i> is TRUE.</li> </ul>
<i>threshXlow</i>	<ul style="list-style-type: none"> <li>• Re-selection high threshold.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when <i>ue_in_idle</i> is TRUE.</li> </ul>
<i>cellsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of WCDMA cells.</li> </ul>
<i>WCDMACell-Info[<small>MAX_DESCRIPTION_LENGTH</small>]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">wcdmaCellInfo</a> for more information.</li> </ul>

### 8.326.2 Field Documentation

8.326.2.1 **BYTE** *IteWcdmaCellInfo::cellReselPriority*

8.326.2.2 **BYTE** *IteWcdmaCellInfo::cellsLen*

8.326.2.3 **WORD** *IteWcdmaCellInfo::threshXhigh*

8.326.2.4 **WORD** *IteWcdmaCellInfo::threshXlow*

8.326.2.5 **WORD** *IteWcdmaCellInfo::uarfcn*

8.326.2.6 **wcdmaCellInfo** *IteWcdmaCellInfo::WCDMACellInfo[255]*

## 8.327 messageModeTlv Struct Reference

## Data Fields

- [uint8\\_t TlvPresent](#)
- [sMSMessageModelInfo MessageModelInfo](#)

## 8.327.1 Detailed Description

## Parameters

<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Boolean indicating the presence of the TLV in the QMI response</li> </ul>
<i>MessageMode-Info</i>	<ul style="list-style-type: none"> <li>• Message Mode</li> <li>• See <a href="#">sMSMessageModelInfo</a> for more information</li> </ul>

## 8.327.2 Field Documentation

8.327.2.1 [sMSMessageModelInfo](#) `messageModeTlv::MessageModelInfo`8.327.2.2 [uint8\\_t](#) `messageModeTlv::TlvPresent`

## 8.328 messageWaitingInfoContent Struct Reference

## Data Fields

- [BYTE](#) `msgType`
- [BYTE](#) `activeInd`
- [BYTE](#) `msgCount`

## 8.328.1 Detailed Description

This structure contains message waiting information per instance

## Parameters

<i>msgType</i>	<ul style="list-style-type: none"> <li>• Message type <ul style="list-style-type: none"> <li>– 0x00 - MWI_MESSAGE_TYPE_VOICMAIL - Voicemail</li> <li>– 0x01 - MWI_MESSAGE_TYPE_FAX - Fax</li> <li>– 0x02 - MWI_MESSAGE_TYPE_EMAIL - Email</li> <li>– 0x03 - MWI_MESSAGE_TYPE_OTHER - Other</li> <li>– 0x04 - MWI_MESSAGE_TYPE_VIDEOMAIL - Videomail</li> </ul> </li> </ul>
----------------	--

<i>activeInd</i>	<ul style="list-style-type: none"> <li>Indicates whether the indication is active <ul style="list-style-type: none"> <li>0x00 - Inactive</li> <li>0x01 - Active</li> </ul> </li> </ul>
<i>msgCount</i>	<ul style="list-style-type: none"> <li>Number of messages</li> </ul>

### 8.328.2 Field Documentation

8.328.2.1 BYTE messageWaitingInfoContent::activeInd

8.328.2.2 BYTE messageWaitingInfoContent::msgCount

8.328.2.3 BYTE messageWaitingInfoContent::msgType

## 8.329 minBasedIMSI Struct Reference

### Data Fields

- [BYTE mccM](#) [3]
- [WORD imsiM1112](#)
- [BYTE imsiMS1](#) [7]
- [BYTE imsiMS2](#) [3]

### 8.329.1 Detailed Description

This structure contains the parameters for Min based IMSI Information

#### Parameters

<i>mccM</i>	<ul style="list-style-type: none"> <li>ASCII character representation of MCC_M</li> </ul>
<i>imsiM1112</i>	<ul style="list-style-type: none"> <li>ASCII character representation of IMSI_M_11_12 value <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>imsiMS1</i>	<ul style="list-style-type: none"> <li>ASCII character representation of IMSI_M_S1 value</li> </ul>
<i>imsiMS2</i>	<ul style="list-style-type: none"> <li>ASCII character representation of IMSI_M_S2 value</li> </ul>

### 8.329.2 Field Documentation

8.329.2.1 WORD minBasedIMSI::imsiM1112

8.329.2.2 **BYTE** minBasedIMSI::imsiMS1[7]

8.329.2.3 **BYTE** minBasedIMSI::imsiMS2[3]

8.329.2.4 **BYTE** minBasedIMSI::mccM[3]

## 8.330 mitigationDevList Struct Reference

### Data Fields

- [BYTE](#) mitigationDevIdLen
- [CHAR](#) mitigationDevId [255]
- [BYTE](#) maxMitigationLevel

### 8.330.1 Detailed Description

This structure contains mitigation devices list

#### Parameters

<i>mitigationDevIdLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements <ul style="list-style-type: none"> <li>– mitigation_dev_id</li> </ul> </li> </ul>
<i>mitigationDevId</i>	<ul style="list-style-type: none"> <li>• Mitigation device ID.</li> </ul>
<i>maxMitigationLevel</i>	<ul style="list-style-type: none"> <li>• Maximum valid mitigation level.</li> <li>• Valid range - 0 to max_mitigation_level.</li> </ul>

### 8.330.2 Field Documentation

8.330.2.1 **BYTE** mitigationDevList::maxMitigationLevel

8.330.2.2 **CHAR** mitigationDevList::mitigationDevId[255]

8.330.2.3 **BYTE** mitigationDevList::mitigationDevIdLen

## 8.331 MNRInfo Struct Reference

### Data Fields

- [WORD](#) mcc
- [WORD](#) mnc
- [ULONG](#) rat

### 8.331.1 Detailed Description

Structure contains Manual Network Register Information parameters

## Parameters

<i>mcc</i>	<ul style="list-style-type: none"> <li>• A 16-bit integer representation of Mobile Country Code. Range - 0 to 999.</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>• A 16-bit integer representation of Mobile Network Code. Range - 0 to 999.</li> </ul>
<i>rat</i>	<ul style="list-style-type: none"> <li>• Radio access technology for which to register. <ul style="list-style-type: none"> <li>– 0x04 - RADIO_IF_GSM</li> <li>– 0x05 - RADIO_IF_UMTS</li> <li>– 0x08 - RADIO_IF_LTE</li> </ul> </li> </ul>

## 8.331.2 Field Documentation

8.331.2.1 WORD MNRInfo::mcc

8.331.2.2 WORD MNRInfo::mnc

8.331.2.3 ULONG MNRInfo::rat

## 8.332 ModifyProfileIn Struct Reference

## Data Fields

- [BYTE \\* pProfileID](#)
- [BYTE \\* pProfileType](#)
- [QmiProfileInfo curProfile](#)

## 8.332.1 Detailed Description

This structure contains input parameters for SLQSMModifyProfile

## Parameters

<i>ProfileID</i>	<ul style="list-style-type: none"> <li>• 1 to 16 for 3GPP profile (EM/MC73xx or earlier)</li> <li>• 1 to 24 for 3GPP profile (EM/MC74xx onwards)</li> <li>• 101 to 106 for 3GPP2 profile</li> </ul>
------------------	---



<i>ProfileType</i>	<ul style="list-style-type: none"> <li>Identifies the technology type of the profile <ul style="list-style-type: none"> <li>0x00 - 3GPP</li> <li>0x01 - 3GPP2</li> <li>NULL is not allowed</li> </ul> </li> </ul>
<i>curProfile</i>	<ul style="list-style-type: none"> <li>Contains Union of profile(3GPP/3GPP2) structures</li> </ul>

### 8.332.2 Field Documentation

8.332.2.1 **QmiProfileInfo** ModifyProfileIn::curProfile

8.332.2.2 **BYTE\*** ModifyProfileIn::pProfileID

8.332.2.3 **BYTE\*** ModifyProfileIn::pProfileType

## 8.333 ModifyProfileOut Struct Reference

### Data Fields

- USHORT** \* [pExtErrorCode](#)

### 8.333.1 Detailed Description

This structure contains out parameters for SLQSMModifyProfile

#### Parameters

<i>pExtErrorCode</i>	<ul style="list-style-type: none"> <li>The extended error code received from DS Profile subsystem of type eWDS_ERR_PROFILE_REG_XXX.</li> <li>Error code will only be present if error code eQCWWAN_ERR_QMI_EXTENDED_INTERNAL is returned by device.</li> <li>See <a href="#">qm_wds_ds_profile_extended_err_codes</a> enum in <a href="#">qmerrno.h</a> for received error description.</li> </ul>
----------------------	--

### 8.333.2 Field Documentation

8.333.2.1 **USHORT\*** ModifyProfileOut::pExtErrorCode

## 8.334 msgWaitingInfo Struct Reference

### Data Fields

- BYTE** numInstances
- messageWaitingInfoContent** msgWaitInfo [0xFF]

### 8.334.1 Detailed Description

This structure holds information related to message waiting information

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of sets of the elements in structure <a href="#">messageWaitingInfoContent</a></li> </ul>
<i>msgWaitInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">messageWaitingInfoContent</a>. <ul style="list-style-type: none"> <li>– See <a href="#">messageWaitingInfoContent</a> for more information.</li> </ul> </li> </ul>

### 8.334.2 Field Documentation

8.334.2.1 [messageWaitingInfoContent](#) `msgWaitingInfo::msgWaitInfo[0xFF]`

8.334.2.2 `BYTE` `msgWaitingInfo::numInstances`

## 8.335 namName Struct Reference

#### Data Fields

- `BYTE` [namNameLen](#)
- `BYTE` [namName](#) [12]

### 8.335.1 Detailed Description

This structure contains the parameters for NAM Name Information

#### Parameters

<i>namNameLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements: <ul style="list-style-type: none"> <li>– <code>nam_name</code></li> </ul> </li> <li>• If zero(0), then no information follows.</li> </ul>
<i><a href="#">namName</a></i>	<ul style="list-style-type: none"> <li>• Name information in ASCII. The maximum length of <code>nam_name</code> is 12.</li> </ul>

### 8.335.2 Field Documentation

8.335.2.1 `BYTE` `namName::namName[12]`

8.335.2.2 `BYTE` `namName::namNameLen`

## 8.336 nas\_acqOrderPref Struct Reference

## Data Fields

- uint8\_t [acqOrdeLen](#)
- uint8\_t \* [pAcqOrder](#)

### 8.336.1 Detailed Description

Contain the Acquisition Order Preference.

#### Parameters

<i>acqOrdeLen</i>	<ul style="list-style-type: none"><li>• Number of sets of the following elements.</li></ul>
<i>pAcqOrder</i>	<ul style="list-style-type: none"><li>• Acquisition order preference to be set. Values:<ul style="list-style-type: none"><li>– 0x01 - NAS_RADIO_IF_CDMA_1X - cdma2000 1X</li><li>– 0x02 - NAS_RADIO_IF_CDMA_1XEVDO - cdma2000 HRPD (1xEV-DO)</li><li>– 0x04 - NAS_RADIO_IF_GSM - GSM</li><li>– 0x05 - NAS_RADIO_IF_UMTS - UMTS</li><li>– 0x08 - NAS_RADIO_IF_LTE - LTE</li><li>– 0x09 - NAS_RADIO_IF_TDSCDMA - TD-SCDMA</li></ul></li></ul>

### 8.336.2 Field Documentation

8.336.2.1 uint8\_t nas\_acqOrderPref::acqOrdeLen

8.336.2.2 uint8\_t\* nas\_acqOrderPref::pAcqOrder

## 8.337 nas\_AddCDMASysInfo Struct Reference

## Data Fields

- uint16\_t [geoSysIdx](#)
- uint16\_t [regPrd](#)

### 8.337.1 Detailed Description

Structure for storing the Additional CDMA System Information.

## Parameters

<i>geoSysIdx</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>regPrd</i>	<ul style="list-style-type: none"> <li>• Registration period after the CDMA system is acquired.</li> <li>• When the CDMA registration period is not valid, 0xFFFF is used.</li> </ul>

## 8.337.2 Field Documentation

8.337.2.1 uint16\_t nas\_AddCDMASysInfo::geoSysIdx

8.337.2.2 uint16\_t nas\_AddCDMASysInfo::regPrd

## 8.338 nas\_AddSysInfo Struct Reference

## Data Fields

- uint16\_t [geoSysIdx](#)
- uint32\_t [cellBroadcastCap](#)

## 8.338.1 Detailed Description

Structure for storing the Additional GSM and WCDMA System Information.

## Parameters

<i>geoSysIdx</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>cellBroadcast-Cap</i>	<ul style="list-style-type: none"> <li>• Cell broadcast capability of the serving system.</li> <li>• When the CDMA registration period is not valid, 0xFFFF is used. <ul style="list-style-type: none"> <li>– NAS_CELL_BROADCAST_CAP_UNKNOWN - Cell broadcast support is unknown</li> <li>– NAS_CELL_BROADCAST_CAP_OFF - Cell broadcast is not supported</li> <li>– NAS_CELL_BROADCAST_CAP_ON - Cell broadcast is supported</li> </ul> </li> </ul>

## 8.338.2 Field Documentation

8.338.2.1 uint32\_t nas\_AddSysInfo::cellBroadcastCap

8.338.2.2 uint16\_t nas\_AddSysInfo::geoSysIdx

## 8.339 nas\_CallBarringSysInfo Struct Reference

### Data Fields

- uint32\_t [csBarStatus](#)
- uint32\_t [psBarStatus](#)

### 8.339.1 Detailed Description

Structure for storing the GSM and WCDMA Call Barring System Information.

#### Parameters

<i>csBarStatus</i>	<ul style="list-style-type: none"> <li>• Call barring status for circuit-switched calls. <ul style="list-style-type: none"> <li>– NAS_CELL_ACCESS_NORMAL_ONLY - Cell access is allowed for normal calls only</li> <li>– NAS_CELL_ACCESS_EMERGENCY_ONLY - Cell access is allowed for emergency calls only</li> <li>– NAS_CELL_ACCESS_NO_CALLS - Cell access is not allowed for any call type</li> <li>– NAS_CELL_ACCESS_ALL_CALLS - Cell access is allowed for all call types</li> <li>– NAS_CELL_ACCESS_UNKNOWN - Cell access type is unknown</li> </ul> </li> </ul>
<i>psBarStatus</i>	<ul style="list-style-type: none"> <li>• Call barring status for packet-switched calls. <ul style="list-style-type: none"> <li>– NAS_CELL_ACCESS_NORMAL_ONLY - Cell access is allowed for normal calls only</li> <li>– NAS_CELL_ACCESS_EMERGENCY_ONLY - Cell access is allowed for emergency calls only</li> <li>– NAS_CELL_ACCESS_NO_CALLS - Cell access is not allowed for any call type</li> <li>– NAS_CELL_ACCESS_ALL_CALLS - Cell access is allowed for all call types</li> <li>– NAS_CELL_ACCESS_UNKNOWN - Cell access type is unknown</li> </ul> </li> </ul>

### 8.339.2 Field Documentation

8.339.2.1 uint32\_t nas\_CallBarringSysInfo::csBarStatus

8.339.2.2 uint32\_t nas\_CallBarringSysInfo::psBarStatus

## 8.340 nas\_callBarStatus Struct Reference

### Data Fields

- uint32\_t [csBarStatus](#)
- uint32\_t [psBarStatus](#)

### 8.340.1 Detailed Description

This structure contains Call Barring Status.

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>csBarStatus</i>	<ul style="list-style-type: none"> <li>• Call Barring Status for circuit-switched calls.</li> <li>• Values: <ul style="list-style-type: none"> <li>• NAS_CELL_ACCESS_NORMAL_ONLY - Cell access is allowed for normal calls only</li> <li>• NAS_CELL_ACCESS_EMERGENCY_ONLY - Cell access is allowed for emergency calls only</li> <li>• NAS_CELL_ACCESS_NO_CALLS - Cell access is not allowed for any call type</li> <li>• NAS_CELL_ACCESS_ALL_CALLS - Cell access is allowed for all call types</li> <li>• NAS_CELL_ACCESS_UNKNOWN - Cell access type is unknown</li> </ul> </li> </ul>
<i>psBarStatus</i>	<ul style="list-style-type: none"> <li>• Call Barring Status for packet-switched calls.</li> <li>• Values: <ul style="list-style-type: none"> <li>– NAS_CELL_ACCESS_NORMAL_ONLY - Cell access is allowed for normal calls only</li> <li>– NAS_CELL_ACCESS_EMERGENCY_ONLY - Cell access is allowed for emergency calls only</li> <li>– NAS_CELL_ACCESS_NO_CALLS - Cell access is not allowed for any call type</li> <li>– NAS_CELL_ACCESS_ALL_CALLS - Cell access is allowed for all call types</li> <li>– NAS_CELL_ACCESS_UNKNOWN - Cell access type is unknown</li> </ul> </li> </ul>

### 8.340.2 Field Documentation

8.340.2.1 `uint32_t nas_callBarStatus::csBarStatus`

8.340.2.2 `uint32_t nas_callBarStatus::psBarStatus`

## 8.341 nas\_CDMAECIOThresh Struct Reference

### Data Fields

- `uint8_t` [CDMAECIOThreshListLen](#)
- `int16_t *` [pCDMAECIOThreshList](#)

### 8.341.1 Detailed Description

This structure contains CDMA ECIO threshold related parameters.

## Parameters

<i>CDMAECIO- ThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the CDMA ECIO threshold list parameter to follow</li> </ul>
<i>pCDMAECIO- ThreshList</i>	<ul style="list-style-type: none"> <li>Array of ECIO thresholds (in units of 0.1 dB)</li> <li>Maximum of 32 values. Range for ECIO values: -31.5 to 0 (in dB)</li> </ul>

## 8.341.2 Field Documentation

8.341.2.1 uint8\_t nas\_CDMAECIOThresh::CDMAECIOThreshListLen

8.341.2.2 int16\_t\* nas\_CDMAECIOThresh::pCDMAECIOThreshList

## 8.342 nas\_CDMAInfo Struct Reference

## Data Fields

- uint16\_t [sid](#)
- uint16\_t [nid](#)
- uint16\_t [baseId](#)
- uint16\_t [refPn](#)
- uint32\_t [baseLat](#)
- uint32\_t [baseLong](#)

## 8.342.1 Detailed Description

This structure contains information about the CDMA Network.

## Parameters

<i>sid</i>	<ul style="list-style-type: none"> <li>System ID. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>nid</i>	<ul style="list-style-type: none"> <li>Network ID. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>baseId</i>	<ul style="list-style-type: none"> <li>Base station ID. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>

<i>refpn</i>	<ul style="list-style-type: none"> <li>Reference PN. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>baseLat</i>	<ul style="list-style-type: none"> <li>Latitude of the current base station in units of 0.25 sec. <ul style="list-style-type: none"> <li>0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>baseLong</i>	<ul style="list-style-type: none"> <li>Longitude of the current base station in units of 0.25 sec. <ul style="list-style-type: none"> <li>0xFFFFFFFF - Not Available</li> </ul> </li> </ul>

### 8.342.2 Field Documentation

8.342.2.1 `uint16_t nas_CDMAInfo::baseId`

8.342.2.2 `uint32_t nas_CDMAInfo::baseLat`

8.342.2.3 `uint32_t nas_CDMAInfo::baseLong`

8.342.2.4 `uint16_t nas_CDMAInfo::nid`

8.342.2.5 `uint16_t nas_CDMAInfo::refpn`

8.342.2.6 `uint16_t nas_CDMAInfo::sid`

## 8.343 nas\_CDMA RSSI Thresh Struct Reference

### Data Fields

- `uint8_t` [CDMARSSIThreshListLen](#)
- `int16_t *` [pCDMARSSIThreshList](#)

### 8.343.1 Detailed Description

This structure contains CDMA RSSI threshold related parameters.

#### Parameters

<i>CDMARSSI- ThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the CDMARSSI threshold list parameter to follow</li> </ul>
<i>pCDMARSSI- ThreshList</i>	<ul style="list-style-type: none"> <li>Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>maximum of 32 values.</li> <li>Range for RSSI values:-105 to -21 (in dBm).</li> </ul>



### 8.343.2 Field Documentation

8.343.2.1 `uint8_t` `nas_CDMARSSIThresh::CDMARSSIThreshListLen`

8.343.2.2 `int16_t*` `nas_CDMARSSIThresh::pCDMARSSIThreshList`

## 8.344 nas\_CDMASysInfo Struct Reference

### Data Fields

- [nas\\_sysInfoCommon](#) `sysInfoCDMA`
- `uint8_t` `isSysPrIMatchValid`
- `uint8_t` `isSysPrIMatch`
- `uint8_t` `pRevInUseValid`
- `uint8_t` `pRevInUse`
- `uint8_t` `bsPRevValid`
- `uint8_t` `bsPRev`
- `uint8_t` `ccsSupportedValid`
- `uint8_t` `ccsSupported`
- `uint8_t` `cdmaSysIdValid`
- `uint16_t` `systemID`
- `uint16_t` `networkID`
- `uint8_t` `bsInfoValid`
- `uint16_t` `baseId`
- `uint32_t` `baseLat`
- `uint32_t` `baseLong`
- `uint8_t` `packetZoneValid`
- `uint16_t` `packetZone`
- `uint8_t` `networkIdValid`
- `uint8_t` `MCC` [3]
- `uint8_t` `MNC` [3]

### 8.344.1 Detailed Description

Structure for storing the CDMA System Information.

#### Parameters

<i>sysInfoCDMA</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
<i>isSysPrIMatch-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the system PRL match is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>isSysPrIMatch</i>	<ul style="list-style-type: none"> <li>• Indicates whether the system is in a PRL.</li> <li>• Only applies to CDMA/HDR. <ul style="list-style-type: none"> <li>– 0x00 - System is not in a PRL</li> <li>– 0x01 - System is in a PRL</li> <li>– 0xFF - Not Available</li> </ul> </li> <li>• If the system is not in a PRL, roam_status carries the value from the default roaming indicator in the PRL.</li> <li>• If the system is in a PRL, roam_status is set to the value based on the standard specification.</li> </ul>
<i>pRevInUseValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the P_Rev in use is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pRevInUse</i>	<ul style="list-style-type: none"> <li>• The lesser of the base station P_Rev and mobile P_Rev</li> <li>• Only applicable for CDMA. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>bsPRevValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the base station P_Rev is valid <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>bsPRev</i>	<ul style="list-style-type: none"> <li>• Base station P_Rev.</li> <li>• Only applicable for CDMA. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>ccsSupported-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the supported concurrent service is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>ccsSupported</i>	<ul style="list-style-type: none"> <li>• Whether concurrent service is supported.</li> <li>• Only applicable for CDMA. <ul style="list-style-type: none"> <li>– 0x00 - Not supported</li> <li>– 0x01 - Supported</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>cdmaSysIdValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the CDMA system ID is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>systemID</i>	<ul style="list-style-type: none"> <li>• System ID. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>networkID</i>	<ul style="list-style-type: none"> <li>• Network ID. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>bsInfoValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the base station information is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>baseLat</i>	<ul style="list-style-type: none"> <li>• Base station latitude in units of 0.25 sec.</li> <li>• Expressed as a two's complement signed number with positive numbers signifying North latitudes. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>baseLong</i>	<ul style="list-style-type: none"> <li>• Base station longitude in units of 0.25 sec.</li> <li>• Expressed as a two's complement signed number with positive numbers signifying East latitudes. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>

<i>packetZoneValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the packet zone is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>packetZone</i>	<ul style="list-style-type: none"> <li>Packet zone (8-bit). <ul style="list-style-type: none"> <li>0xFFFF indicates no packet zone.</li> </ul> </li> <li>Only applicable for CDMA.</li> </ul>
<i>networkIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the network ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>MCC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Country Code.</li> <li>MCC digits in ASCII characters</li> <li>MCC wildcard value is returned as {'3', 0xFF, 0xFF}.</li> </ul>
<i>MNC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Network Code.</li> <li>MNC digits in ASCII characters</li> <li>An unused byte is set to 0xFF.</li> <li>MNC wildcard value is returned as {'7', 0xFF, 0xFF}.</li> </ul>

### 8.344.2 Field Documentation

8.344.2.1 uint16\_t nas\_CDMASysInfo::baseId

8.344.2.2 uint32\_t nas\_CDMASysInfo::baseLat

8.344.2.3 uint32\_t nas\_CDMASysInfo::baseLong

8.344.2.4 uint8\_t nas\_CDMASysInfo::bsInfoValid

8.344.2.5 uint8\_t nas\_CDMASysInfo::bsPRev

8.344.2.6 uint8\_t nas\_CDMASysInfo::bsPRevValid

8.344.2.7 uint8\_t nas\_CDMASysInfo::ccsSupported

- 8.344.2.8 uint8\_t nas\_CDMASysInfo::ccsSupportedValid
- 8.344.2.9 uint8\_t nas\_CDMASysInfo::cdmaSysIdValid
- 8.344.2.10 uint8\_t nas\_CDMASysInfo::isSysPrIMatch
- 8.344.2.11 uint8\_t nas\_CDMASysInfo::isSysPrIMatchValid
- 8.344.2.12 uint8\_t nas\_CDMASysInfo::MCC[3]
- 8.344.2.13 uint8\_t nas\_CDMASysInfo::MNC[3]
- 8.344.2.14 uint16\_t nas\_CDMASysInfo::networkID
- 8.344.2.15 uint8\_t nas\_CDMASysInfo::networkIdValid
- 8.344.2.16 uint16\_t nas\_CDMASysInfo::packetZone
- 8.344.2.17 uint8\_t nas\_CDMASysInfo::packetZoneValid
- 8.344.2.18 uint8\_t nas\_CDMASysInfo::pRevInUse
- 8.344.2.19 uint8\_t nas\_CDMASysInfo::pRevInUseValid
- 8.344.2.20 nas\_sysInfoCommon nas\_CDMASysInfo::sysInfoCDMA
- 8.344.2.21 uint16\_t nas\_CDMASysInfo::systemID

## 8.345 nas\_CDMASysInfoExt Struct Reference

### Data Fields

- uint16\_t [MCC](#)
- uint8\_t [imsi\\_11\\_12](#)

### 8.345.1 Detailed Description

This structure contains CDMA system information extension

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
<i>imsi_11_12</i>	<ul style="list-style-type: none"> <li>• IMSI_11_12</li> </ul>

### 8.345.2 Field Documentation

- 8.345.2.1 uint8\_t nas\_CDMASysInfoExt::imsi\_11\_12

8.345.2.2 uint16\_t nas\_CDMAInfoExt::MCC

## 8.346 nas\_cellParams Struct Reference

### Data Fields

- uint16\_t [pci](#)
- int16\_t [rsrq](#)
- int16\_t [rsrp](#)
- int16\_t [rssi](#)
- int16\_t [srxlev](#)

### 8.346.1 Detailed Description

This structure contains information about the Cell parameters.

#### Parameters

<i>pci</i>	<ul style="list-style-type: none"> <li>• Physical cell ID.</li> <li>• Range: 0 to 503.</li> </ul>
<i>rsrq</i>	<ul style="list-style-type: none"> <li>• Current RSRQ in 1/10 dB as measured by L1.</li> <li>• Range: -20.0 dB to -3.0 dB.</li> </ul>
<i>rsrp</i>	<ul style="list-style-type: none"> <li>• Current RSRP in 1/10 dBm as measured by L1.</li> <li>• Range: -140.0 dBm to -44.0 dBm.</li> </ul>
<i>rssi</i>	<ul style="list-style-type: none"> <li>• Current RSSI in 1/10 dBm as measured by L1.</li> <li>• Range: -120.0 dBm to 0.</li> </ul>
<i>srxlev</i>	<ul style="list-style-type: none"> <li>• Cell selection Rx level (Srxlev) value.</li> <li>• Range: -128 to 128.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>

### 8.346.2 Field Documentation

8.346.2.1 uint16\_t nas\_cellParams::pci

8.346.2.2 int16\_t nas\_cellParams::rsrp

8.346.2.3 int16\_t nas\_cellParams::rsrq

8.346.2.4 int16\_t nas\_cellParams::rssi

8.346.2.5 int16\_t nas\_cellParams::srxlev

## 8.347 nas\_CommlInfo Struct Reference

### Data Fields

- int8\_t [temperature](#)
- uint8\_t [modemMode](#)
- uint8\_t [systemMode](#)
- uint8\_t [imsRegState](#)
- uint8\_t [psState](#)

### 8.347.1 Detailed Description

Structure for storing the common information for the device.

#### Parameters

<i>temperature</i>	<ul style="list-style-type: none"><li>• Temperature.<ul style="list-style-type: none"><li>– 8-bit signed integer</li><li>– 0xFF - Not Available.</li></ul></li></ul>
<i>modemMode</i>	<ul style="list-style-type: none"><li>• Modem Operating Mode.<ul style="list-style-type: none"><li>– 0x00 - POWERING OFF</li><li>– 0x01 - FACTORY TEST</li><li>– 0x02 - OFFLINE</li><li>– 0x03 - OFFLINE_AMPS</li><li>– 0x04 - OFFLINE_CDMA</li><li>– 0x05 - ONLINE</li><li>– 0x06 - LOW POWER MODE</li><li>– 0x07 - RESETTING</li><li>– 0x08 - NETWORK TEST</li><li>– 0x09 - OFFLINE REQUEST</li><li>– 0x0A - PSEUDO ONLINE</li><li>– 0x0B - RESETTING MODEM</li><li>– 0xFF - Unknown</li></ul></li></ul>

<i>systemMode</i>	<ul style="list-style-type: none"> <li>• System Acquisition Mode. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - AMPS</li> <li>– 0x02 - CDMA</li> <li>– 0x03 - GSM</li> <li>– 0x04 - HDR</li> <li>– 0x05 - WCDMA</li> <li>– 0x06 - GPS</li> <li>– 0x08 - WLAN</li> <li>– 0x09 - LTE</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>imsRegState</i>	<ul style="list-style-type: none"> <li>• IMS Registration State. <ul style="list-style-type: none"> <li>– 0x00 - NO SRV</li> <li>– 0x01 - IN PROG</li> <li>– 0x02 - FAILED</li> <li>– 0x03 - LIMITED</li> <li>– 0x04 - FULL SRV</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>psState</i>	<ul style="list-style-type: none"> <li>• PS Attach State. <ul style="list-style-type: none"> <li>– 0x00 - Attached</li> <li>– 0x01 - Detached</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>

## 8.347.2 Field Documentation

8.347.2.1 `uint8_t nas_CommInfo::imsRegState`

8.347.2.2 `uint8_t nas_CommInfo::modemMode`

8.347.2.3 `uint8_t nas_CommInfo::psState`

8.347.2.4 `uint8_t nas_CommInfo::systemMode`

8.347.2.5 `int8_t nas_CommInfo::temperature`

## 8.348 nas\_CSGID Struct Reference



## Data Fields

- uint16\_t [mcc](#)
- uint16\_t [mnc](#)
- uint8\_t [mncPcsDigits](#)
- uint32\_t [id](#)
- uint8\_t [rat](#)

## 8.348.1 Detailed Description

Contain the [CSGID](#).

## Parameters

<i>mcc</i>	<ul style="list-style-type: none"> <li>• MCC value. Range 0 to 999</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>• MNC value. Range 0 to 999</li> </ul>
<i>mncPcsDigits</i>	<ul style="list-style-type: none"> <li>• TRUE - MNC is a three-digit value; e.g., a reported value of 90 corresponds to an MNC value of 090</li> <li>• FALSE - MNC is a two-digit value; e.g., a reported value of 90 corresponds to an MNC value of 90</li> </ul>
<i>id</i>	<ul style="list-style-type: none"> <li>• Closed subscriber group identifier.</li> </ul>
<i>rat</i>	<ul style="list-style-type: none"> <li>• Radio interface technology of the CSG network. Values: <ul style="list-style-type: none"> <li>– 0x04 - RADIO_IF_GSM - GSM</li> <li>– 0x05 - RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - RADIO_IF_LTE - LTE</li> <li>– 0x09 - RADIO_IF_TDSCDMA - TDS</li> </ul> </li> </ul>

## 8.348.2 Field Documentation

8.348.2.1 uint32\_t nas\_CSGID::id

8.348.2.2 uint16\_t nas\_CSGID::mcc

8.348.2.3 uint16\_t nas\_CSGID::mnc

8.348.2.4 uint8\_t nas\_CSGID::mncPcsDigits

8.348.2.5 uint8\_t nas\_CSGID::rat

## 8.349 nas\_currentPLMN Struct Reference

## Data Fields

- uint16\_t [MCC](#)
- uint16\_t [MNC](#)
- uint8\_t [netDescrLength](#)
- uint8\_t [netDescr](#) [255]

### 8.349.1 Detailed Description

This structure contains the current PLMN parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• mobile country code <ul style="list-style-type: none"> <li>– A 16 bit representation of MCC</li> <li>– Range 0 to 999</li> </ul> </li> </ul>
<i>MNC</i>	<ul style="list-style-type: none"> <li>• mobile network code <ul style="list-style-type: none"> <li>– A 16 bit representation of MNC</li> <li>– Range 0 to 999</li> </ul> </li> </ul>
<i>netDescrLength</i>	<ul style="list-style-type: none"> <li>• Length of Network description field</li> <li>• Defaults to zero</li> </ul>
<i>netDescr</i>	<ul style="list-style-type: none"> <li>• Network Description <ul style="list-style-type: none"> <li>– optional string containing network name or description</li> </ul> </li> </ul>

### 8.349.2 Field Documentation

8.349.2.1 uint16\_t nas\_currentPLMN::MCC

8.349.2.2 uint16\_t nas\_currentPLMN::MNC

8.349.2.3 uint8\_t nas\_currentPLMN::netDescr[255]

8.349.2.4 uint8\_t nas\_currentPLMN::netDescrLength

## 8.350 nas\_dataSrvCapabilities Struct Reference

## Data Fields

- uint8\_t [dataCapabilitiesLen](#)

- `uint8_t dataCapabilities` [32]

### 8.350.1 Detailed Description

This structure contains the data services capability

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>dataCapabilitiesLen</i>	<ul style="list-style-type: none"><li>• Length of data capabilities list</li><li>• Defaults to zero</li></ul>
<i>dataCapabilities</i>	<ul style="list-style-type: none"><li>• List of data capabilities</li><li>• Values:<ul style="list-style-type: none"><li>– 0x01 - GPRS</li><li>– 0x02 - EDGE</li><li>– 0x03 - HSDPA</li><li>– 0x04 - HSUPA</li><li>– 0x05 - WCDMA</li><li>– 0x06 - CDMA</li><li>– 0x07 - EV-DO Rev0</li><li>– 0x08 - EV-DO RevA</li><li>– 0x09 - GSM</li><li>– 0x0A - EV-DO Rev B</li><li>– 0x0B - LTE</li><li>– 0x0C - HSDPA+</li><li>– 0x0D - DC-HSDPA+</li></ul></li></ul>

### 8.350.2 Field Documentation

8.350.2.1 `uint8_t nas_dataSrvCapabilities::dataCapabilities`[32]

8.350.2.2 `uint8_t nas_dataSrvCapabilities::dataCapabilitiesLen`

## 8.351 nas\_detailSvcInfo Struct Reference

### Data Fields

- `uint8_t srvStatus`
- `uint8_t srvCapability`
- `uint8_t hdrSrvStatus`
- `uint8_t hdrHybrid`
- `uint8_t isSysForbidden`

### 8.351.1 Detailed Description

This structure contains Detailed Service information

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>srvStatus</i>	<ul style="list-style-type: none"> <li>• Service status</li> <li>• Values:             <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service available</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - MS in power save or deep sleep</li> </ul> </li> </ul>
<i>srvCapability</i>	<ul style="list-style-type: none"> <li>• System's service capability</li> <li>• Values:             <ul style="list-style-type: none"> <li>– 0x00 - No Service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> <li>– 0x04 - MS found the right system but not yet registered/attached</li> </ul> </li> </ul>
<i>hdrSrvStatus</i>	<ul style="list-style-type: none"> <li>• HDR service status</li> <li>• Values:             <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service available</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - MS in power save or deep sleep</li> </ul> </li> </ul>

<i>hdrHybrid</i>	<ul style="list-style-type: none"><li>• HDR hybrid information</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - System is not hybrid</li><li>– 0x01 - System is hybrid</li></ul></li></ul>
<i>isSysForbidden</i>	<ul style="list-style-type: none"><li>• Forbidden system information</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - System is not a forbidden system</li><li>– 0x01 - System is a forbidden system</li></ul></li></ul>

## 8.351.2 Field Documentation

8.351.2.1 `uint8_t nas_detailSvcInfo::hdrHybrid`

8.351.2.2 `uint8_t nas_detailSvcInfo::hdrSrvStatus`

8.351.2.3 `uint8_t nas_detailSvcInfo::isSysForbidden`

8.351.2.4 `uint8_t nas_detailSvcInfo::srvCapability`

8.351.2.5 `uint8_t nas_detailSvcInfo::srvStatus`

## 8.352 nas\_ecioListElement Struct Reference

### Data Fields

- `int16_t ecio`
- `uint8_t radiolf`

### 8.352.1 Detailed Description

This structure contains the ECIO Information

## Parameters

<i>ecio</i>	<ul style="list-style-type: none"> <li>• ECIO value in dBm</li> </ul>
<i>radiolf</i>	<ul style="list-style-type: none"> <li>• Radio interface technology of the signal being measured <ul style="list-style-type: none"> <li>– 0x00 – RADIO_IF_NO_SVC – None (no service)</li> <li>– 0x01 – RADIO_IF_CDMA_1X – cdma2000® 1X</li> <li>– 0x02 – RADIO_IF_CDMA_1XEVD0 – cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 – RADIO_IF_AMPS – AMPS</li> <li>– 0x04 – RADIO_IF_GSM – GSM</li> <li>– 0x05 – RADIO_IF_UMTS – UMTS</li> </ul> </li> </ul>

## 8.352.2 Field Documentation

8.352.2.1 int16\_t nas\_ecioListElement::ecio

8.352.2.2 uint8\_t nas\_ecioListElement::radiolf

## 8.353 nas\_errorRateListElement Struct Reference

## Data Fields

- uint16\_t [errorRate](#)

- uint8\_t [radiolf](#)

## 8.353.1 Detailed Description

This structure contains the Error Rate Information

## Parameters

<i>errorRate</i>	<ul style="list-style-type: none"> <li>• Error rate value corresponds to the RAT that is currently registered. <ul style="list-style-type: none"> <li>– For CDMA, the error rate reported is Frame Error Rate: <ul style="list-style-type: none"> <li>* Valid error rate values between 1 and 10000 are returned to indicate percentage, e.g., a value of 300 means the error rate is 3%</li> <li>* A value of 0xFFFF indicates that the error rate is unknown or unavailable</li> </ul> </li> <li>– For HDR, the error rate reported is Packet Error Rate: <ul style="list-style-type: none"> <li>* Valid error rate values between 1 and 10000 are returned to indicate percentage, e.g., a value of 300 means the error rate is 3%</li> <li>* A value of 0xFFFF indicates that the error rate is unknown or unavailable</li> </ul> </li> <li>– For GSM, the error rate reported is Bit Error Rate: <ul style="list-style-type: none"> <li>* Valid values are 0, 100, 200, 300, 400, 500, 600, and 700 The reported value divided by 100 gives the error rate as an RxQual value, e.g., a value of 300 represents an RxQual value of 3.</li> <li>* A value of 25500 indicates No Data</li> </ul> </li> <li>– For WCDMA, the error rate reported is Block Error Rate (BLER): <ul style="list-style-type: none"> <li>* Valid values are 1 to 10000</li> <li>* The reported value divided by 100 provides the error rate in percentages, e.g., a value of 300 represents a BLER of 3%.</li> <li>* A value of 0 indicates No Data</li> </ul> </li> </ul> </li> </ul>
<i>radioIf</i>	<ul style="list-style-type: none"> <li>• Radio interface technology of the signal being measured <ul style="list-style-type: none"> <li>– 0x00 – RADIO_IF_NO_SVC – None (no service)</li> <li>– 0x01 – RADIO_IF_CDMA_1X – cdma2000® 1X</li> <li>– 0x02 – RADIO_IF_CDMA_1xEVDO – cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 – RADIO_IF_AMPS – AMPS</li> <li>– 0x04 – RADIO_IF_GSM – GSM</li> <li>– 0x05 – RADIO_IF_UMTS – UMTS</li> </ul> </li> </ul>

### 8.353.2 Field Documentation

8.353.2.1 `uint16_t nas_errorRateListElement::errorRate`

8.353.2.2 `uint8_t nas_errorRateListElement::radioIlf`

## 8.354 `nas_GERANInfo` Struct Reference

### Data Fields

- `uint32_t cellID`
- `uint8_t plmn` [3]
- `uint16_t lac`
- `uint16_t arfcn`
- `uint8_t bsic`
- `uint32_t timingAdvance`
- `uint16_t rxLev`
- `uint8_t nmrInst`
- `nas_nmrCellInfo insNmrCellInfo` [255]

### 8.354.1 Detailed Description

This structure contains information about the GERAN Network.

#### Parameters

<i>cellID</i>	<ul style="list-style-type: none"> <li>• Cell ID.</li> <li>• 0xFFFFFFFF indicates cell ID information is not present.</li> </ul>
<i>plmn</i> [ <i>NAS_PLM-N_LENGTH</i> ]	<ul style="list-style-type: none"> <li>• MCC/MNC information coded as octet 3, 4, and 5.</li> <li>• This field is ignored when <i>nmrCellID</i> is not present.</li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• This field is ignored when <i>nmrCellID</i> is not present. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>



<i>arfcn</i>	<ul style="list-style-type: none"> <li>Absolute RF channel number. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>bsic</i>	<ul style="list-style-type: none"> <li>Base station identity code. <ul style="list-style-type: none"> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>timingAdvance</i>	<ul style="list-style-type: none"> <li>Measured delay (in bit periods; 1 bit period = 48/13 microsecond) of access burst transmission on RACH or PRACH to the expected signal from an MS at zero distance under static channel conditions. <ul style="list-style-type: none"> <li>0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>rxLev</i>	<ul style="list-style-type: none"> <li>Serving Cell Rx measurement.</li> <li>Values range between 0 and 63.</li> <li>Mapped to a measured signal level: <ul style="list-style-type: none"> <li>Rxlev 0 is a signal strength less than -110 dBm</li> <li>Rxlev 1 is -110 dBm to -109 dBm</li> <li>Rxlev 2 is -109 dBm to -108 dBm</li> <li>...</li> <li>Rxlev 62 is -49 dBm to -48 dBm</li> <li>Rxlev 63 is greater than -48 dBm</li> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>nmrInst</i>	<ul style="list-style-type: none"> <li>Provides the number of set of instances which follow.</li> <li>If 0(zero), then no information follows it.</li> </ul>
<i>insNmrCellInfo[ -NAS_MAX_DE- SCRIPTION_LE- NGTH]</i>	<ul style="list-style-type: none"> <li>See <a href="#">nas_nmrCellInfo</a> for more information.</li> </ul>

## 8.354.2 Field Documentation

8.354.2.1 uint16\_t nas\_GERANInfo::arfcn

8.354.2.2 uint8\_t nas\_GERANInfo::bsic

8.354.2.3 uint32\_t nas\_GERANInfo::cellID

8.354.2.4 nas\_nmrCellInfo nas\_GERANInfo::insNmrCellInfo[255]

8.354.2.5 uint16\_t nas\_GERANInfo::lac

8.354.2.6 uint8\_t nas\_GERANInfo::nmrInst

8.354.2.7 uint8\_t nas\_GERANInfo::plmn[3]

8.354.2.8 uint16\_t nas\_GERANInfo::rxLev

8.354.2.9 uint32\_t nas\_GERANInfo::timingAdvance

## 8.355 nas\_geranInstInfo Struct Reference

### Data Fields

- uint16\_t [geranArfcn](#)
- uint8\_t [geranBsicNcc](#)
- uint8\_t [geranBsicBcc](#)
- int16\_t [geranRssi](#)

### 8.355.1 Detailed Description

This structure contains information about the GERAN Instances in UMTS Network.

#### Parameters

<i>geranArfcn</i>	<ul style="list-style-type: none"> <li>• Absolute RF channel number.</li> </ul>
<i>geranBsicNcc</i>	<ul style="list-style-type: none"> <li>• Base station identity code network color code.</li> <li>• 0xFF indicates information is not present.</li> </ul>
<i>geranBsicBcc</i>	<ul style="list-style-type: none"> <li>• Base station identity code base station color code.</li> <li>• 0xFF indicates information is not present.</li> </ul>
<i>geranRssi</i>	<ul style="list-style-type: none"> <li>• Received signal strength indicator.</li> </ul>

### 8.355.2 Field Documentation

8.355.2.1 uint16\_t nas\_geranInstInfo::geranArfcn

8.355.2.2 uint8\_t nas\_geranInstInfo::geranBsicBcc

8.355.2.3 uint8\_t nas\_geranInstInfo::geranBsicNcc

8.355.2.4 int16\_t nas\_geranInstInfo::geranRssi

## 8.356 nas\_gsmCellInfo Struct Reference

## Data Fields

- uint16\_t [arfcn](#)
- uint8\_t [band1900](#)
- uint8\_t [cellIdValid](#)
- uint8\_t [bsicId](#)
- int16\_t [rssi](#)
- int16\_t [srxlev](#)

### 8.356.1 Detailed Description

This structure contains information about the GSM Cell.

#### Parameters

<i>arfcn</i>	<ul style="list-style-type: none"> <li>• GSM frequency being reported.</li> <li>• Range: 0 to 1023.</li> </ul>
<i>band1900</i>	<ul style="list-style-type: none"> <li>• Band indicator for the GSM ARFCN</li> <li>• This field is only valid if arfcn is in the overlapping region.</li> <li>• If TRUE and the cell is in the overlapping region, the ARFCN is on the 1900 band.</li> <li>• If FALSE, it is on the 1800 band.</li> </ul>
<i>cellIdValid</i>	<ul style="list-style-type: none"> <li>• Flag indicating whether the base station identity code ID is valid.</li> </ul>
<i>bsicId</i>	<ul style="list-style-type: none"> <li>• Base station identity code ID, including base station color code and network color code.</li> <li>• The lower 6 bits can be set to any value.</li> </ul>
<i>rssi</i>	<ul style="list-style-type: none"> <li>• Measured RSSI value in 1/10 dB.</li> <li>• Range: -200.0 dB to 0</li> </ul>
<i>srxlev</i>	<ul style="list-style-type: none"> <li>• Cell selection Rx level (Srxlev) value.</li> <li>• Range: -128 to 128.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>

### 8.356.2 Field Documentation

8.356.2.1 uint16\_t nas\_gsmCellInfo::arfcn

8.356.2.2 uint8\_t nas\_gsmCellInfo::band1900

8.356.2.3 uint8\_t nas\_gsmCellInfo::bsicId

8.356.2.4 `uint8_t nas_gsmCellInfo::celldValid`

8.356.2.5 `int16_t nas_gsmCellInfo::rssi`

8.356.2.6 `int16_t nas_gsmCellInfo::srxlev`

## 8.357 nas\_GSMRSSIThresh Struct Reference

### Data Fields

- `uint8_t` [GSMRSSIThreshListLen](#)
- `int16_t *` [pGSMRSSIThreshList](#)

### 8.357.1 Detailed Description

This structure contains GSM RSSI threshold related parameters.

#### Parameters

<i>GSMRSSI- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the GSM RSSI threshold list parameter to follow</li> </ul>
<i>pGSMRSSI- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values</li> <li>• Range for RSSI values: -111 to -48 (in dBm)</li> </ul>

### 8.357.2 Field Documentation

8.357.2.1 `uint8_t nas_GSMRSSIThresh::GSMRSSIThreshListLen`

8.357.2.2 `int16_t*` `nas_GSMRSSIThresh::pGSMRSSIThreshList`

## 8.358 nas\_GSMSrvStatusInfo Struct Reference

### Data Fields

- `uint8_t` [srvStatus](#)
- `uint8_t` [trueSrvStatus](#)
- `uint8_t` [isPrefDataPath](#)

### 8.358.1 Detailed Description

Structure for storing the service status information for GSM, WCDMA and LTE networks.

#### Parameters

<i>srvStatus</i>	<ul style="list-style-type: none"> <li>• Service status of the system. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - Power save</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>trueSrvStatus</i>	<ul style="list-style-type: none"> <li>• True service status of the system.</li> <li>• Not applicable to CDMA/HDR. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - Power save</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>isPrefDataPath</i>	<ul style="list-style-type: none"> <li>• Whether the RAT is the preferred data path. <ul style="list-style-type: none"> <li>– 0x00 - Not preferred</li> <li>– 0x01 - Preferred</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

## 8.358.2 Field Documentation

8.358.2.1 `uint8_t nas_GSMsInfo::isPrefDataPath`

8.358.2.2 `uint8_t nas_GSMsInfo::srvStatus`

8.358.2.3 `uint8_t nas_GSMsInfo::trueSrvStatus`

## 8.359 nas\_GSMsInfo Struct Reference

### Data Fields

- [nas\\_sysInfoCommon sysInfoGSM](#)
- `uint8_t lacValid`
- `uint16_t lac`
- `uint8_t cellIdValid`
- `uint32_t cellId`
- `uint8_t regRejectInfoValid`
- `uint8_t rejectSrvDomain`
- `uint8_t rejCause`

- uint8\_t [networkIdValid](#)
- uint8\_t [MCC](#) [3]
- uint8\_t [MNC](#) [3]
- uint8\_t [egprsSuppValid](#)
- uint8\_t [egprsSupp](#)
- uint8\_t [dtmSuppValid](#)
- uint8\_t [dtmSupp](#)

### 8.359.1 Detailed Description

Structure for storing the GSM System Information.

#### Parameters

<i>sysInfoGSM</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
<i>lacValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the location area code is valid.. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• Only applies to 3GPP. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>cellIdValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the cell ID is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>cellId</i>	<ul style="list-style-type: none"> <li>• Cell ID. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>regRejectInfoValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the registration reject information is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>rejectSrvDomain</i>	<ul style="list-style-type: none"> <li>Type of service domain in which the registration is rejected. <ul style="list-style-type: none"> <li>0x00 - SYS_SRV_DOMAIN_NO_SRV - No service</li> <li>0x01 - Circuit-switched only</li> <li>0x02 - Packet-switched only</li> <li>0x03 - Circuit-switched and packet-switched</li> <li>0x04 - Camped</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>rejCause</i>	<ul style="list-style-type: none"> <li>Reject cause values sent are specified in [3GPP TS 24.008, Section 10.5.3.6]. <ul style="list-style-type: none"> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>networkIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the network ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>MCC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Country Code.</li> <li>MCC digits in ASCII characters</li> </ul>
<i>MNC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Network Code.</li> <li>MNC digits in ASCII characters</li> <li>An unused byte is set to 0xFF.</li> <li>In case of two-digit MNC values, the third (unused) digit is set to 0xFF. For example, 15 (a two-digit MNC) is reported using the byte stream 0x31 0x35 0xFF.</li> </ul>
<i>egprsSuppValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the EGPRS support is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

<i>egprsSupp</i>	<ul style="list-style-type: none"> <li>• EGPRS support indication.</li> <li>• Only applicable for GSM. <ul style="list-style-type: none"> <li>– 0x00 - Not available</li> <li>– 0x01 - Available</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>dtmSuppValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether Dual Transfer mode support is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>dtmSupp</i>	<ul style="list-style-type: none"> <li>• Dual Transfer mode support indication.</li> <li>• Only applicable for GSM. <ul style="list-style-type: none"> <li>– 0x00 - Not available</li> <li>– 0x01 - Available</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

## 8.359.2 Field Documentation

8.359.2.1 `uint32_t nas_GSM.sysInfo::cellId`

8.359.2.2 `uint8_t nas_GSM.sysInfo::cellIdValid`

8.359.2.3 `uint8_t nas_GSM.sysInfo::dtmSupp`

8.359.2.4 `uint8_t nas_GSM.sysInfo::dtmSuppValid`

8.359.2.5 `uint8_t nas_GSM.sysInfo::egprsSupp`

8.359.2.6 `uint8_t nas_GSM.sysInfo::egprsSuppValid`

8.359.2.7 `uint16_t nas_GSM.sysInfo::lac`

8.359.2.8 `uint8_t nas_GSM.sysInfo::lacValid`

8.359.2.9 `uint8_t nas_GSM.sysInfo::MCC[3]`

8.359.2.10 `uint8_t nas_GSM.sysInfo::MNC[3]`

8.359.2.11 `uint8_t nas_GSM.sysInfo::networkIdValid`

8.359.2.12 `uint8_t nas_GSM.sysInfo::regRejectInfoValid`



8.359.2.13 uint8\_t nas\_GSMsInfo::rejCause

8.359.2.14 uint8\_t nas\_GSMsInfo::rejectSrvDomain

8.359.2.15 nas\_sysInfoCommon nas\_GSMsInfo::sysInfoGSM

## 8.360 nas\_HDRECIOTresh Struct Reference

### Data Fields

- uint8\_t [HDRECIOTreshListLen](#)
- int16\_t \* [pHDRECIOTreshList](#)

### 8.360.1 Detailed Description

This structure contains HDR ECIO threshold related parameters.

#### Parameters

<i>HDRECIOTreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the HDR ECIO threshold list parameter to follow</li> </ul>
<i>pHDRECIOTreshList</i>	<ul style="list-style-type: none"> <li>• Array of ECIO thresholds (in units of 0.1 dB)</li> <li>• Maximum of 32 values</li> <li>• Range for ECIO values: -31.5 to 0 (in dB).</li> </ul>

### 8.360.2 Field Documentation

8.360.2.1 uint8\_t nas\_HDRECIOTresh::HDRECIOTreshListLen

8.360.2.2 int16\_t\* nas\_HDRECIOTresh::pHDRECIOTreshList

## 8.361 nas\_HDRIOTresh Struct Reference

### Data Fields

- uint8\_t [HDRIOTreshListLen](#)
- int16\_t \* [pHDRIOTreshList](#)

### 8.361.1 Detailed Description

This structure contains HDR IO threshold related parameters.

## Parameters

<i>HDRIOTthresh-ListLen</i>	<ul style="list-style-type: none"> <li>Length of the HDR IO threshold list parameter to follow</li> </ul>
<i>pHDRIOTthresh-List</i>	<ul style="list-style-type: none"> <li>Array of IO thresholds (in units of 0.1 dBm)</li> <li>Maximum of 32 values</li> <li>Range for IO values: -128 to -13 (in dBm).</li> </ul>

## 8.361.2 Field Documentation

8.361.2.1 `uint8_t nas_HDRIOTthresh::HDRIOTthreshListLen`8.361.2.2 `int16_t* nas_HDRIOTthresh::pHDRIOTthreshList`8.362 `nas_HDRRSSIThresh` Struct Reference

## Data Fields

- `uint8_t HDRRSSIThreshListLen`
- `int16_t * pHDRRSSIThreshList`

## 8.362.1 Detailed Description

This structure contains HDR RSSI threshold related parameters.

## Parameters

<i>HDRRSSI-ThresholdListLen</i>	<ul style="list-style-type: none"> <li>Length of the HDR RSSI threshold list parameter to follow</li> </ul>
<i>pHDRRSSI-ThresholdList</i>	<ul style="list-style-type: none"> <li>Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>Maximum of 32 values.</li> <li>Range for RSSI values: -118 to -13 (in dBm).</li> </ul>

## 8.362.2 Field Documentation

8.362.2.1 `uint8_t nas_HDRRSSIThresh::HDRRSSIThreshListLen`8.362.2.2 `int16_t* nas_HDRRSSIThresh::pHDRRSSIThreshList`8.363 `nas_HDRSINRThreshold` Struct Reference

## Data Fields

- `uint8_t HDRSINRThresholdListLen`

- uint16\_t \* [pHDRSINRThreshList](#)

### 8.363.1 Detailed Description

This structure contains HDR SINR threshold related parameters.

#### Parameters

<i>HDRSINR- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the HDR ECIO threshold list parameter to follow</li> </ul>
<i>pHDRSINR- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of SINR level thresholds (in units of 1)</li> <li>• maximum of 32 values.</li> <li>• Valid levels are 0 to 8 <ul style="list-style-type: none"> <li>– 0x00 - SINR_LEVEL_0 is -9 dB</li> <li>– 0x01 - SINR_LEVEL_1 is -6 dB</li> <li>– 0x02 - SINR_LEVEL_2 is -4.5 dB</li> <li>– 0x03 - SINR_LEVEL_3 is -3 dB</li> <li>– 0x04 - SINR_LEVEL_4 is -2 dB</li> <li>– 0x05 - SINR_LEVEL_5 is +1 dB</li> <li>– 0x06 - SINR_LEVEL_6 is +3 dB</li> <li>– 0x07 - SINR_LEVEL_7 is +6 dB</li> <li>– 0x08 - SINR_LEVEL_8 is +9 dB</li> </ul> </li> </ul>

### 8.363.2 Field Documentation

8.363.2.1 uint8\_t nas\_HDRSINRThreshold::HDRSINRThreshListLen

8.363.2.2 uint16\_t\* nas\_HDRSINRThreshold::pHDRSINRThreshList

## 8.364 nas\_HDRSysInfo Struct Reference

### Data Fields

- [nas\\_sysInfoCommon sysInfoHDR](#)
- uint8\_t [isSysPrIMatchValid](#)
- uint8\_t [isSysPrIMatch](#)
- uint8\_t [hdrPersonalityValid](#)
- uint8\_t [hdrPersonality](#)
- uint8\_t [hdrActiveProtValid](#)
- uint8\_t [hdrActiveProt](#)
- uint8\_t [is856SysIdValid](#)
- uint8\_t [is856SysId](#) [16]

### 8.364.1 Detailed Description

Structure for storing the HDR System Information.

## Parameters

<i>sysInfoHDR</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
<i>isSysPrIMatch-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the system PRL match is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>isSysPrIMatch</i>	<ul style="list-style-type: none"> <li>• Indicates whether the system is in a PRL.</li> <li>• Only applies to CDMA/HDR. <ul style="list-style-type: none"> <li>– 0x00 - System is not in a PRL</li> <li>– 0x01 - System is in a PRL</li> <li>– 0xFF - Not Available</li> </ul> </li> <li>• If the system is not in a PRL, roam_status carries the value from the default roaming indicator in the PRL.</li> <li>• If the system is in a PRL, roam_status is set to the value based on the standard specification.</li> </ul>
<i>hdrPersonality-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the HDR personality is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>hdrPersonality</i>	<ul style="list-style-type: none"> <li>• HDR personality information.</li> <li>• Only applicable for HDR. <ul style="list-style-type: none"> <li>– 0x00 - None</li> <li>– 0x02 - HRPD</li> <li>– 0x03 - eHRPD</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>hdrActiveProtValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the HDR active protocol revision information is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>hdrActiveProt</i>	<ul style="list-style-type: none"> <li>HDR active protocol revision information .</li> <li>Only applicable for HDR. <ul style="list-style-type: none"> <li>0x00 - None</li> <li>0x02 - HDR Rel 0</li> <li>0x03 - HDR Rel A</li> <li>0x04 - HDR Rel B</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>is856SysIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the IS-856 system ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>is856SysId[SLQ-S_SYSTEM_ID_SIZE]</i>	<ul style="list-style-type: none"> <li>IS-856 system ID.</li> <li>Only applicable for HDR.</li> </ul>

### 8.364.2 Field Documentation

8.364.2.1 `uint8_t nas_HDRSysInfo::hdrActiveProt`

8.364.2.2 `uint8_t nas_HDRSysInfo::hdrActiveProtValid`

8.364.2.3 `uint8_t nas_HDRSysInfo::hdrPersonality`

8.364.2.4 `uint8_t nas_HDRSysInfo::hdrPersonalityValid`

8.364.2.5 `uint8_t nas_HDRSysInfo::is856SysId[16]`

8.364.2.6 `uint8_t nas_HDRSysInfo::is856SysIdValid`

8.364.2.7 `uint8_t nas_HDRSysInfo::isSysPrIMatch`

8.364.2.8 `uint8_t nas_HDRSysInfo::isSysPrIMatchValid`

8.364.2.9 `nas_sysInfoCommon nas_HDRSysInfo::sysInfoHDR`

## 8.365 nas\_infoInterFreq Struct Reference

### Data Fields

- uint16\_t [earfcn](#)
- uint8\_t [threshXLow](#)
- uint8\_t [threshXHigh](#)
- uint8\_t [cell\\_resel\\_priority](#)
- uint8\_t [cells\\_len](#)
- [nas\\_cellParams](#) [cellInterFreqParams](#) [255]

### 8.365.1 Detailed Description

This structure contains information about the inter-frequency.

#### Parameters

<i>earfcn</i>	<ul style="list-style-type: none"> <li>• E-UTRA absolute radio frequency channel number of the serving cell.</li> <li>• Range: 0 to 65535.</li> </ul>
<i>threshXLow</i>	<ul style="list-style-type: none"> <li>• Cell Srxlev low threshold.</li> <li>• Range: 0 to 31.</li> <li>• When the serving cell does not exceed <code>thresh_serving_low</code>, the value of an evaluated cell must be smaller than this value to be considered for re-selection.</li> </ul>
<i>threshXHigh</i>	<ul style="list-style-type: none"> <li>• Cell Srxlev high threshold.</li> <li>• Range: 0 to 31.</li> <li>• When the serving cell exceeds <code>thresh_serving_low</code>, the value of an evaluated cell must be greater than this value to be considered for re-selection.</li> </ul>
<i>cell_resel_ - priority</i>	<ul style="list-style-type: none"> <li>• Cell re-selection priority</li> <li>• Range: 0 to 7.</li> <li>• This field is only valid when <code>ue_in_idle</code> is TRUE.</li> </ul>
<i>cells_len</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of cell params.</li> </ul>
<i>cellInterFreqParams[NAS_MAX_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_cellParams</a> for more information.</li> </ul>

### 8.365.2 Field Documentation

#### 8.365.2.1 uint8\_t nas\_infoInterFreq::cell\_resel\_priority

8.365.2.2 `nas_cellParams` `nas_infoInterFreq::cellInterFreqParams[255]`

8.365.2.3 `uint8_t` `nas_infoInterFreq::cells_len`

8.365.2.4 `uint16_t` `nas_infoInterFreq::earfcn`

8.365.2.5 `uint8_t` `nas_infoInterFreq::threshXHigh`

8.365.2.6 `uint8_t` `nas_infoInterFreq::threshXLow`

## 8.366 nas\_lteGsmCellInfo Struct Reference

### Data Fields

- `uint8_t` [cellReselPriority](#)
- `uint8_t` [threshGsmHigh](#)
- `uint8_t` [threshGsmLow](#)
- `uint8_t` [nccPermitted](#)
- `uint8_t` [cells\\_len](#)
- [nas\\_gsmCellInfo](#) `GsmCellInfo` [255]

### 8.366.1 Detailed Description

This structure contains information about the LTE GSM Cell.

#### Parameters

<i>cellReselPriority</i>	<ul style="list-style-type: none"> <li>• Priority of this frequency group.</li> <li>• Range: 0 to 7.</li> <li>• This field is only valid when <code>ue_in_idle</code> is TRUE.</li> </ul>
<i>threshGsmHigh</i>	<ul style="list-style-type: none"> <li>• Reselection threshold for high priority layers.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when <code>ue_in_idle</code> is TRUE.</li> </ul>
<i>threshGsmLow</i>	<ul style="list-style-type: none"> <li>• Reselection threshold for low priority layers.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when <code>ue_in_idle</code> is TRUE.</li> </ul>

<i>nccPermitted</i>	<ul style="list-style-type: none"> <li>• Bitmask specifying whether a neighbor with a specific network color code is to be reported.</li> <li>• Range: 0 to 255.</li> <li>• Bit n set to 1 means a neighbor with NCC n must be included in the report. This flag is synonymous with a blacklist in other RATs.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>
<i>cells_len</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of gsm cells.</li> </ul>
<i>GsmCellInfo[NAS_MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_gsmCellInfo</a> for more information.</li> </ul>

### 8.366.2 Field Documentation

8.366.2.1 `uint8_t nas_lteGsmCellInfo::cellReselPriority`

8.366.2.2 `uint8_t nas_lteGsmCellInfo::cells_len`

8.366.2.3 `nas_gsmCellInfo nas_lteGsmCellInfo::GsmCellInfo[255]`

8.366.2.4 `uint8_t nas_lteGsmCellInfo::nccPermitted`

8.366.2.5 `uint8_t nas_lteGsmCellInfo::threshGsmHigh`

8.366.2.6 `uint8_t nas_lteGsmCellInfo::threshGsmLow`

## 8.367 nas\_LTEInfo Struct Reference

### Data Fields

- `uint8_t band`
- `uint8_t bandwidth`
- `uint16_t RXChan`
- `uint16_t TXChan`
- `uint8_t emmState`
- `uint8_t emmSubState`
- `uint8_t emmConnState`

### 8.367.1 Detailed Description

Structure for storing the LTE information for the device.

#### Parameters

---



<i>band</i>	<ul style="list-style-type: none"><li>• LTE Band<ul style="list-style-type: none"><li>– 1 ~ 40 (Band in decimal)</li><li>– 0xFF - Invalid</li></ul></li></ul>
<i>bandwidth</i>	<ul style="list-style-type: none"><li>• BandWidth.<ul style="list-style-type: none"><li>– 0x00 - 1.4 MHz</li><li>– 0x01 - 3 MHz</li><li>– 0x02 - 5 MHz</li><li>– 0x03 - 10 MHz</li><li>– 0x04 - 15 MHz</li><li>– 0x05 - 20 MHz</li><li>– 0x06 - Invalid</li><li>– 0xFF - Unknown</li></ul></li></ul>
<i>RXChan</i>	<ul style="list-style-type: none"><li>• RX channel number in decimal<ul style="list-style-type: none"><li>– 0xFFFF - Not Available</li></ul></li></ul>
<i>TXChan</i>	<ul style="list-style-type: none"><li>• TX channel number in decimal<ul style="list-style-type: none"><li>– 0xFFFF - Not Available</li></ul></li></ul>
<i>emmState</i>	<ul style="list-style-type: none"><li>• EMM State.<ul style="list-style-type: none"><li>– 0x00 - Deregistered</li><li>– 0x01 - Reg Initiated</li><li>– 0x02 - Registered</li><li>– 0x03 - TAU Initiated</li><li>– 0x04 - SR Initiated</li><li>– 0x05 - Dereg Initiated</li><li>– 0x06 - Invalid</li><li>– 0xFF - Unknown</li></ul></li></ul>

<i>emmSubState</i>	<ul style="list-style-type: none"><li>• EMM Sub State.<ul style="list-style-type: none"><li>– 0xFF - NOT Applicable</li></ul></li><li>• When EMM_state is 0x00:<ul style="list-style-type: none"><li>– 0x00 - No IMSI</li><li>– 0x01 - PLMN Search</li><li>– 0x02 - Attach Needed</li><li>– 0x03 - No Cell</li><li>– 0x04 - Attaching</li><li>– 0x05 - Normal Service</li><li>– 0x06 - Limited Service</li><li>– 0x07 - Waiting for PDN</li></ul></li><li>• When EMM_state is 0x01:<ul style="list-style-type: none"><li>– 0x00 - Waiting for NW</li><li>– 0x01 - Waiting for ESM</li></ul></li><li>• When EMM_state is 0x02:<ul style="list-style-type: none"><li>– 0x00 - Normal Service</li><li>– 0x01 - Update Needed</li><li>– 0x02 - Attempt Update</li><li>– 0x03 - No Cell</li><li>– 0x04 - PLMN Search</li><li>– 0x05 - Limited Service</li><li>– 0x06 - MM Update</li><li>– 0x07 - IMSI Detach</li><li>– 0x08 - Waiting for ESM</li></ul></li></ul>
--------------------	---

<i>emmConnState</i>	<ul style="list-style-type: none"><li>• EMM Connected Mode State.<ul style="list-style-type: none"><li>– 0x00 - RRC Idle</li><li>– 0x01 - Waiting RRC Cfm</li><li>– 0x02 - RRC Connected</li><li>– 0x03 - RRC Releasing</li><li>– 0xFF - Unknown</li></ul></li></ul>
---------------------	--

## 8.367.2 Field Documentation

8.367.2.1 `uint8_t nas_LTEInfo::band`

8.367.2.2 `uint8_t nas_LTEInfo::bandwidth`

8.367.2.3 `uint8_t nas_LTEInfo::emmConnState`

8.367.2.4 `uint8_t nas_LTEInfo::emmState`

8.367.2.5 `uint8_t nas_LTEInfo::emmSubState`

8.367.2.6 `uint16_t nas_LTEInfo::RXChan`

8.367.2.7 `uint16_t nas_LTEInfo::TXChan`

## 8.368 nas\_LTEInfoInterfreq Struct Reference

### Data Fields

- `uint8_t uelIdle`
- `uint8_t freqsLen`
- `nas_infoInterFreq InfoInterfreq` [255]

### 8.368.1 Detailed Description

This structure contains information about the LTE Inter-Frequency Network.

## Parameters

<i>ueInIdle</i>	<ul style="list-style-type: none"> <li>• TRUE if the UE is in Idle mode, otherwise FALSE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>freqsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of inter frequency information.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>InfoInterfreq[NAS_MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_infoInterFreq</a> for more information.</li> </ul>

## 8.368.2 Field Documentation

8.368.2.1 uint8\_t nas\_LTEInfoInterfreq::freqsLen

8.368.2.2 nas\_infoInterFreq nas\_LTEInfoInterfreq::InfoInterfreq[255]

8.368.2.3 uint8\_t nas\_LTEInfoInterfreq::ueInIdle

## 8.369 nas\_LTEInfoIntrafreq Struct Reference

## Data Fields

- uint8\_t [ueInIdle](#)
- uint8\_t [plmn](#) [3]
- uint16\_t [tac](#)
- uint32\_t [globalCellId](#)
- uint16\_t [earfcn](#)
- uint16\_t [servingCellId](#)
- uint8\_t [cellReselPriority](#)
- uint8\_t [sNonIntraSearch](#)
- uint8\_t [threshServingLow](#)
- uint8\_t [sIntraSearch](#)
- uint8\_t [cellsLen](#)
- [nas\\_cellParams](#) [CellParams](#) [255]

## 8.369.1 Detailed Description

This structure contains information about the LTE Intra-Frequency Network.

## Parameters

<i>ueInIdle</i>	<ul style="list-style-type: none"> <li>• TRUE if the UE is in Idle mode, otherwise FALSE.</li> <li>– 0xFF - Not Available</li> </ul>
<i>plmn[NAS_PLM-N_LENGTH]</i>	<ul style="list-style-type: none"> <li>• PLMN ID coded as octet 3, 4, and 5.</li> </ul>
<i>tac</i>	<ul style="list-style-type: none"> <li>• Tracking area code.</li> <li>– 0xFFFF - Not Available</li> </ul>
<i>globalCellId</i>	<ul style="list-style-type: none"> <li>• Global cell ID in the system information block.</li> <li>– 0xFFFFFFFF - Not Available</li> </ul>
<i>earfcn</i>	<ul style="list-style-type: none"> <li>• E-UTRA absolute radio frequency channel number of the serving cell.</li> <li>• Range: 0 to 65535.</li> <li>– 0xFFFF - Not Available</li> </ul>
<i>servingCellId</i>	<ul style="list-style-type: none"> <li>• LTE serving cell ID.</li> <li>• Range: 0 to 503.</li> <li>• This is the cell ID of the serving cell and can be found in the cell list.</li> <li>– 0xFFFF - Not Available</li> </ul>
<i>cellReselPriority</i>	<ul style="list-style-type: none"> <li>• Priority for serving frequency.</li> <li>• Range: 0 to 7.</li> <li>• This field is only valid when <i>ue_in_idle</i> is TRUE.</li> <li>– 0xFF - Not Available</li> </ul>

<i>sNonIntraSearch</i>	<ul style="list-style-type: none"> <li>• S non-intra search threshold to control non-intrafrequency searches.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when ue_in_idle is TRUE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>threshServing-Low</i>	<ul style="list-style-type: none"> <li>• Serving cell low threshold.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when ue_in_idle is TRUE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>sIntraSearch</i>	<ul style="list-style-type: none"> <li>• S Intra search threshold.</li> <li>• Range: 0 to 31.</li> <li>• The current cell measurement must fall below this threshold to consider intrafrequency for reselection.</li> <li>• This field is only valid when ue_in_idle is TRUE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>cellsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of cell params.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>CellParams[NAS_MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_cellParams</a> for more information.</li> </ul>

## 8.369.2 Field Documentation

8.369.2.1 `nas_cellParams nas_LTEInfoIntrafreq::CellParams[255]`

8.369.2.2 `uint8_t nas_LTEInfoIntrafreq::cellReselPriority`

8.369.2.3 `uint8_t nas_LTEInfoIntrafreq::cellsLen`

8.369.2.4 `uint16_t nas_LTEInfoIntrafreq::earfcn`

8.369.2.5 `uint32_t nas_LTEInfoIntrafreq::globalCellId`

8.369.2.6 `uint8_t nas_LTEInfoIntrafreq::plmn[3]`

8.369.2.7 `uint16_t nas_LTEInfoIntrafreq::servingCellId`

8.369.2.8 uint8\_t nas\_LTEInfoIntrafreq::sIntraSearch

8.369.2.9 uint8\_t nas\_LTEInfoIntrafreq::sNonIntraSearch

8.369.2.10 uint16\_t nas\_LTEInfoIntrafreq::tac

8.369.2.11 uint8\_t nas\_LTEInfoIntrafreq::threshServingLow

8.369.2.12 uint8\_t nas\_LTEInfoIntrafreq::ueInIdle

## 8.370 nas\_LTEInfoNeighboringGSM Struct Reference

### Data Fields

- uint8\_t [ueInIdle](#)
- uint8\_t [freqsLen](#)
- [nas\\_LteGsmCellInfo](#) [LteGsmCellInfo](#) [255]

### 8.370.1 Detailed Description

This structure contains information about the LTE Neighboring GSM Network.

#### Parameters

<i>ueInIdle</i>	<ul style="list-style-type: none"> <li>• TRUE if the UE is in Idle mode, otherwise FALSE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>freqsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of LTE GSM cell information.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>LteGsmCellInfo[-NAS_MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_LteGsmCellInfo</a> for more information.</li> </ul>

### 8.370.2 Field Documentation

8.370.2.1 uint8\_t nas\_LTEInfoNeighboringGSM::freqsLen

8.370.2.2 [nas\\_LteGsmCellInfo](#) [nas\\_LTEInfoNeighboringGSM::LteGsmCellInfo](#)[255]

8.370.2.3 uint8\_t nas\_LTEInfoNeighboringGSM::ueInIdle

## 8.371 nas\_LTEInfoNeighboringWCDMA Struct Reference

### Data Fields

- uint8\_t [ueInIdle](#)
- uint8\_t [freqsLen](#)
- [nas\\_LteWcdmaCellInfo](#) [LTEWCDMACellInfo](#) [255]

### 8.371.1 Detailed Description

This structure contains information about the LTE Neighboring WCDMA Network.

#### Parameters

<i>ueInIdle</i>	<ul style="list-style-type: none"> <li>• TRUE if the UE is in Idle mode, otherwise FALSE. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>freqsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of LTE WCDMA cell information.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>LTEWCDMA-CellInfo[NAS_MAX_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_lteWcdmaCellInfo</a> for more information.</li> </ul>

### 8.371.2 Field Documentation

8.371.2.1 `uint8_t nas_LTEInfoNeighboringWCDMA::freqsLen`

8.371.2.2 `nas_lteWcdmaCellInfo nas_LTEInfoNeighboringWCDMA::LTEWCDMACellInfo[255]`

8.371.2.3 `uint8_t nas_LTEInfoNeighboringWCDMA::ueInIdle`

## 8.372 nas\_lteRsrpInformation Struct Reference

### Data Fields

- `int16_t rsrplevel`

### 8.372.1 Detailed Description

This structure contains the LTE RSRP Information

#### Parameters

<i>rsrplevel</i>	<ul style="list-style-type: none"> <li>• LTE RSRP in dBm as a measured by L1. Range: -44 to -140(-44 means -44dBm, -140 means -140dBm).</li> </ul>
------------------	--

### 8.372.2 Field Documentation

8.372.2.1 `int16_t nas_lteRsrpInformation::rsrplevel`

## 8.373 nas\_LTEsrpThresh Struct Reference



## Data Fields

- uint8\_t [LTERSRPThreshListLen](#)
- int16\_t \* [pLTERSRPThreshList](#)

### 8.373.1 Detailed Description

This structure contains LTE RSRP threshold related parameters.

#### Parameters

<i>LTERSRP- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the LTE RSRP threshold list parameter to follow</li> </ul>
<i>pLTERSRP- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSRP thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values</li> <li>• Range for RSRP values: -140 to -44 (in dBm).</li> </ul>

### 8.373.2 Field Documentation

8.373.2.1 uint8\_t nas\_LTERSRPThresh::LTERSRPThreshListLen

8.373.2.2 int16\_t\* nas\_LTERSRPThresh::pLTERSRPThreshList

## 8.374 nas\_LTERSRQThresh Struct Reference

## Data Fields

- uint8\_t [LTERSRQThreshListLen](#)
- int16\_t \* [pLTERSRQThreshList](#)

### 8.374.1 Detailed Description

This structure contains LTE RSRQ threshold related parameters.

#### Parameters

<i>LTERSRQ- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the LTE RSRQ threshold list parameter to follow</li> </ul>
<i>pLTERSRQ- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSRQ thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values.</li> <li>• Range for RSRQ values: -20 to -3 (in dBm)</li> </ul>

### 8.374.2 Field Documentation

8.374.2.1 `uint8_t nas_LTERSRQThresh::LTERSRQThreshListLen`

8.374.2.2 `int16_t* nas_LTERSRQThresh::pLTERSRQThreshList`

## 8.375 nas\_LTERSSIThresh Struct Reference

### Data Fields

- `uint8_t LTERSSIThreshListLen`
- `int16_t * pLTERSSIThreshList`

### 8.375.1 Detailed Description

This structure contains LTE RSSI threshold related parameters.

#### Parameters

<i>LTERSSI- ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the LTE RSSI threshold list parameter to follow</li> </ul>
<i>pLTERSSI- ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values.</li> <li>• Range for RSSI values: -120 to 0 (in dBm)</li> </ul>

### 8.375.2 Field Documentation

8.375.2.1 `uint8_t nas_LTERSSIThresh::LTERSSIThreshListLen`

8.375.2.2 `int16_t* nas_LTERSSIThresh::pLTERSSIThreshList`

## 8.376 nas\_LTESigRptConfig Struct Reference

### Data Fields

- `uint8_t rptRate`
- `uint8_t avgPeriod`

### 8.376.1 Detailed Description

This structure contains LTE RSRP threshold related parameters.

## Parameters

<i>rptRate</i>	<ul style="list-style-type: none"> <li>• Rate on how often the LTE signal must be checked for reporting Values</li> <li>• 0 - Report using the default configuration</li> <li>• 1 - Report every 1 sec</li> <li>• 2 - Report every 2 sec</li> <li>• 3 - Report every 3 sec</li> <li>• 4 - Report every 4 sec</li> <li>• 5 - Report every 5 sec</li> </ul>
<i>avgPeriod</i>	<ul style="list-style-type: none"> <li>• Averaging period to be used for the LTE signal.</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Average using the default configuration</li> <li>– 1 - Average over 1 sec</li> <li>– 2 - Average over 2 sec</li> <li>– 3 - Average over 3 sec</li> <li>– 4 - Average over 4 sec</li> <li>– 5 - Average over 5 sec</li> <li>– 6 - Average over 6 sec</li> <li>– 7 - Average over 7 sec</li> <li>– 8 - Average over 8 sec</li> <li>– 9 - Average over 9 sec</li> <li>– 10 - Average over 10 sec</li> </ul> </li> </ul>

## 8.376.2 Field Documentation

8.376.2.1 uint8\_t nas\_LTESigRptConfig::avgPeriod

8.376.2.2 uint8\_t nas\_LTESigRptConfig::rptRate

## 8.377 nas\_IteSnrinformation Struct Reference

## Data Fields

- int16\_t [snrlevel](#)

## 8.377.1 Detailed Description

This structure contains the LTE SNR Information

## Parameters

<i>snrlevel</i>	<ul style="list-style-type: none"> <li>LTE SNR level as a scaled integer in units of 0.1dB e.g. -16dB has a value of -160 and 24.6dB has value of 246.</li> </ul>
-----------------	---

## 8.377.2 Field Documentation

8.377.2.1 int16\_t nas\_lteSnrinformation::snrlevel

## 8.378 nas\_LTESNRThreshold Struct Reference

## Data Fields

- uint8\_t [LTESNRThreshListLen](#)
- int16\_t \* [pLTESNRThreshList](#)

## 8.378.1 Detailed Description

This structure contains LTE SNR threshold related parameters.

## Parameters

<i>LTESNRThresh- ListLen</i>	<ul style="list-style-type: none"> <li>Length of the LTE SNR threshold list parameter to follow</li> </ul>
<i>pLTESNR- ThreshList</i>	<ul style="list-style-type: none"> <li>Array of SNR thresholds (in units of 0.1 dB)</li> <li>Maximum of 32 values</li> <li>Range for SNR values: -20 to 30 (in dB).</li> </ul>

## 8.378.2 Field Documentation

8.378.2.1 uint8\_t nas\_LTESNRThreshold::LTESNRThreshListLen

8.378.2.2 int16\_t\* nas\_LTESNRThreshold::pLTESNRThreshList

## 8.379 nas\_LTESysInfo Struct Reference

## Data Fields

- [nas\\_sysInfoCommon sysInfoLTE](#)
- uint8\_t [lacValid](#)
- uint16\_t [lac](#)
- uint8\_t [cellIdValid](#)
- uint32\_t [cellId](#)
- uint8\_t [regRejectInfoValid](#)
- uint8\_t [rejectSrvDomain](#)
- uint8\_t [rejCause](#)

- uint8\_t [networkIdValid](#)
- uint8\_t [MCC](#) [3]
- uint8\_t [MNC](#) [3]
- uint8\_t [tacValid](#)
- uint16\_t [tac](#)

### 8.379.1 Detailed Description

Structure for storing the LTE System Information.

#### Parameters

<i>sysInfoLTE</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
<i>lacValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the location area code is valid.. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• Only applies to 3GPP. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>cellIdValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the cell ID is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>cellId</i>	<ul style="list-style-type: none"> <li>• Cell ID. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>regRejectInfo-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the registration reject information is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>rejectSrvDomain</i>	<ul style="list-style-type: none"> <li>• Type of service domain in which the registration is rejected. <ul style="list-style-type: none"> <li>– 0x00 - SYS_SRV_DOMAIN_NO_SRV - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> <li>– 0x04 - Camped</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>rejCause</i>	<ul style="list-style-type: none"> <li>• Reject cause values sent are specified in [3GPP TS 24.008, Section 10.5.3.6]. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>networkIdValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the network ID is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>MCC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code.</li> <li>• MCC digits in ASCII characters</li> </ul>
<i>MNC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>• Mobile Network Code.</li> <li>• MNC digits in ASCII characters</li> <li>• An unused byte is set to 0xFF.</li> <li>• In case of two-digit MNC values, the third (unused) digit is set to 0xFF. For example, 15 (a two-digit MNC) is reported using the byte stream 0x31 0x35 0xFF.</li> </ul>
<i>tacValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether tracking area code is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>tac</i>	<ul style="list-style-type: none"> <li>Tracking area code.</li> <li>Only applicable for LTE. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
------------	---

## 8.379.2 Field Documentation

8.379.2.1 `uint32_t nas_LTESysInfo::cellId`

8.379.2.2 `uint8_t nas_LTESysInfo::cellIdValid`

8.379.2.3 `uint16_t nas_LTESysInfo::lac`

8.379.2.4 `uint8_t nas_LTESysInfo::lacValid`

8.379.2.5 `uint8_t nas_LTESysInfo::MCC[3]`

8.379.2.6 `uint8_t nas_LTESysInfo::MNC[3]`

8.379.2.7 `uint8_t nas_LTESysInfo::networkIdValid`

8.379.2.8 `uint8_t nas_LTESysInfo::regRejectInfoValid`

8.379.2.9 `uint8_t nas_LTESysInfo::rejCause`

8.379.2.10 `uint8_t nas_LTESysInfo::rejectSrvDomain`

8.379.2.11 `nas_sysInfoCommon nas_LTESysInfo::sysInfoLTE`

8.379.2.12 `uint16_t nas_LTESysInfo::tac`

8.379.2.13 `uint8_t nas_LTESysInfo::tacValid`

## 8.380 nas\_IteWcdmaCellInfo Struct Reference

### Data Fields

- `uint16_t uarfcn`
- `uint8_t cellReselPriority`
- `uint16_t threshXhigh`
- `uint16_t threshXlow`
- `uint8_t cellsLen`
- `nas_wcdmaCellInfo WCDMACellInfo` [255]

### 8.380.1 Detailed Description

This structure contains information about the LTE WCDMA Cell.

## Parameters

<i>uarfcn</i>	<ul style="list-style-type: none"> <li>• WCDMA layer frequency.</li> <li>• Range: 0 to 16383.</li> </ul>
<i>cellReselPriority</i>	<ul style="list-style-type: none"> <li>• Cell re-selection priority.</li> <li>• Range: 0 to 7.</li> <li>• This field is only valid when <code>ue_in_idle</code> is TRUE.</li> </ul>
<i>threshXhigh</i>	<ul style="list-style-type: none"> <li>• Re-selection low threshold.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when <code>ue_in_idle</code> is TRUE.</li> </ul>
<i>threshXlow</i>	<ul style="list-style-type: none"> <li>• Re-selection high threshold.</li> <li>• Range: 0 to 31.</li> <li>• This field is only valid when <code>ue_in_idle</code> is TRUE.</li> </ul>
<i>cellsLen</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of WCDMA cells.</li> </ul>
<i>WCDMACell-Info[NAS_MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">wcdmaCellInfo</a> for more information.</li> </ul>

## 8.380.2 Field Documentation

8.380.2.1 `uint8_t nas_lteWcdmaCellInfo::cellReselPriority`8.380.2.2 `uint8_t nas_lteWcdmaCellInfo::cellsLen`8.380.2.3 `uint16_t nas_lteWcdmaCellInfo::threshXhigh`8.380.2.4 `uint16_t nas_lteWcdmaCellInfo::threshXlow`8.380.2.5 `uint16_t nas_lteWcdmaCellInfo::uarfcn`8.380.2.6 `nas_wcdmaCellInfo nas_lteWcdmaCellInfo::WCDMACellInfo[255]`8.381 `nas_MNRInfo` Struct Reference

## Data Fields

- `uint16_t` [mcc](#)
- `uint16_t` [mnc](#)
- `uint32_t` [rat](#)



### 8.381.1 Detailed Description

Structure contains Manual Network Register Information parameters

Parameters

<i>mcc</i>	<ul style="list-style-type: none"><li>• A 16-bit integer representation of Mobile Country Code. Range - 0 to 999.</li></ul>
<i>mnc</i>	<ul style="list-style-type: none"><li>• A 16-bit integer representation of Mobile Network Code. Range - 0 to 999.</li></ul>
<i>rat</i>	<ul style="list-style-type: none"><li>• Radio access technology for which to register.<ul style="list-style-type: none"><li>– 0x04 - RADIO_IF_GSM</li><li>– 0x05 - RADIO_IF_UMTS</li><li>– 0x08 - RADIO_IF_LTE</li></ul></li></ul>

### 8.381.2 Field Documentation

8.381.2.1 uint16\_t nas\_MNRInfo::mcc

8.381.2.2 uint16\_t nas\_MNRInfo::mnc

8.381.2.3 uint32\_t nas\_MNRInfo::rat

## 8.382 nas\_netSelectionPref Struct Reference

Data Fields

- uint8\_t [netReg](#)
- uint16\_t [mcc](#)
- uint16\_t [mnc](#)

### 8.382.1 Detailed Description

Contain the network selection preference.

## Parameters

<i>netReg</i>	<ul style="list-style-type: none"> <li>• specifies one of the following actions: <ul style="list-style-type: none"> <li>– 0x00 - Automatic registration <ul style="list-style-type: none"> <li>* Device registers according to its provisioning; mcc and mnc fields are ignored</li> </ul> </li> <li>– 0x01 - Manual Registration <ul style="list-style-type: none"> <li>* Device registers to specified network; mcc and mnc must contain valid values</li> </ul> </li> </ul> </li> </ul>
<i>mcc</i>	<ul style="list-style-type: none"> <li>• MCC value. Range 0 to 999</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>• MNC value. Range 0 to 999</li> </ul>

## 8.382.2 Field Documentation

8.382.2.1 uint16\_t nas\_netSelectionPref::mcc

8.382.2.2 uint16\_t nas\_netSelectionPref::mnc

8.382.2.3 uint8\_t nas\_netSelectionPref::netReg

## 8.383 nas\_nmrCellInfo Struct Reference

## Data Fields

- uint32\_t [nmrCellID](#)
- uint8\_t [nmrPlmn](#) [3]
- uint16\_t [nmrLac](#)
- uint16\_t [nmrArfcn](#)
- uint8\_t [nmrBsic](#)
- uint16\_t [nmrRxLev](#)

## 8.383.1 Detailed Description

This structure contains information about the Network Measurement Report (NMR) Cell Information.

## Parameters

<i>nmrCellID</i>	<ul style="list-style-type: none"> <li>• Cell ID.</li> <li>• 0xFFFFFFFF indicates cell ID information is not present.</li> </ul>
<i>nmrPlmn[NAS_PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>• MCC/MNC information coded as octet 3, 4, and 5.</li> <li>• This field is ignored when nmrCellID is not present.</li> </ul>
<i>nmrLac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• This field is ignored when nmrCellID is not present. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>nmrArfcn</i>	<ul style="list-style-type: none"> <li>• Absolute RF channel number. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>nmrBsic</i>	<ul style="list-style-type: none"> <li>• Base station identity code. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>nmrRxLev</i>	<ul style="list-style-type: none"> <li>• Cell Rx measurement.</li> <li>• Values range between 0 and 63.</li> <li>• Mapped to a measured signal level: <ul style="list-style-type: none"> <li>– Rxlev 0 is a signal strength less than -110 dBm</li> <li>– Rxlev 1 is -110 dBm to -109 dBm</li> <li>– Rxlev 2 is -109 dBm to -108 dBm</li> <li>– ...</li> <li>– Rxlev 62 is -49 dBm to -48 dBm</li> <li>– Rxlev 63 is greater than -48 dBm</li> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>

## 8.383.2 Field Documentation

8.383.2.1 uint16\_t nas\_nmrCellInfo::nmrArfcn

8.383.2.2 uint8\_t nas\_nmrCellInfo::nmrBsic

8.383.2.3 uint32\_t nas\_nmrCellInfo::nmrCellID

8.383.2.4 `uint16_t nas_nmrCellInfo::nmrLac`

8.383.2.5 `uint8_t nas_nmrCellInfo::nmrPlmn[3]`

8.383.2.6 `uint16_t nas_nmrCellInfo::nmrRxLev`

## 8.384 nas\_qaQmi3Gpp2TimeZone Struct Reference

### Data Fields

- `uint8_t leapSeconds`
- `uint8_t localTimeOffset`
- `uint8_t daylightSavings`

### 8.384.1 Detailed Description

This structure contains the 3GPP2TimeZone parameters

#### Parameters

<i>leapSeconds</i>	<ul style="list-style-type: none"> <li>• leap seconds - Number of leap seconds since the start of CDMA system time.</li> </ul>
<i>localTimeOffset</i>	<ul style="list-style-type: none"> <li>• Local Time Offset - Offset of system time in units of 30 minutes; the value in this field conveys as 8 bit 2's compliment number.</li> </ul>
<i>daylightSavings</i>	<ul style="list-style-type: none"> <li>• Day Light Savings Indicator <ul style="list-style-type: none"> <li>– 0x00 - OFF (daylight savings not in effect)</li> <li>– 0x01 - ON (daylight savings in effect)</li> </ul> </li> </ul>

### 8.384.2 Field Documentation

8.384.2.1 `uint8_t nas_qaQmi3Gpp2TimeZone::daylightSavings`

8.384.2.2 `uint8_t nas_qaQmi3Gpp2TimeZone::leapSeconds`

8.384.2.3 `uint8_t nas_qaQmi3Gpp2TimeZone::localTimeOffset`

## 8.385 nas\_QmiNas3GppNetworkInfo Struct Reference

### Data Fields

- `uint16_t MCC`
- `uint16_t MNC`
- `uint32_t InUse`
- `uint32_t Roaming`
- `uint32_t Forbidden`
- `uint32_t Preferred`
- `char Description [255]`

### 8.385.1 Detailed Description

#### Parameters

<i>MCC</i>	Mobile Country Code
<i>MNC</i>	Mobile Network Code
<i>InUse</i>	current network or not
<i>Roaming</i>	Home/Roam Status of the Network
<i>Forbidden</i>	Network in the forbidden network list or not
<i>Preferred</i>	Network in the Preferred network list or not
<i>Description</i>	Network Name/Description

### 8.385.2 Field Documentation

8.385.2.1 `char nas_QmiNas3GppNetworkInfo::Description[255]`

8.385.2.2 `uint32_t nas_QmiNas3GppNetworkInfo::Forbidden`

8.385.2.3 `uint32_t nas_QmiNas3GppNetworkInfo::InUse`

8.385.2.4 `uint16_t nas_QmiNas3GppNetworkInfo::MCC`

8.385.2.5 `uint16_t nas_QmiNas3GppNetworkInfo::MNC`

8.385.2.6 `uint32_t nas_QmiNas3GppNetworkInfo::Preferred`

8.385.2.7 `uint32_t nas_QmiNas3GppNetworkInfo::Roaming`

## 8.386 nas\_QmiNas3GppNetworkRAT Struct Reference

#### Data Fields

- `uint16_t` [MCC](#)
- `uint16_t` [MNC](#)
- `uint8_t` [RAT](#)

### 8.386.1 Detailed Description

Contain the 3GPP radio access technology information.

## Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
<i>MNC</i>	<ul style="list-style-type: none"> <li>• Mobile Network Code</li> </ul>
<i>RAT</i>	<ul style="list-style-type: none"> <li>• Radio Access Technology <ul style="list-style-type: none"> <li>– 0x04 - GERAN</li> <li>– 0x05 - UMTS</li> <li>– 0x08 - LTE</li> <li>– 0x09 - TD-SCDMA</li> </ul> </li> </ul>

## 8.386.2 Field Documentation

8.386.2.1 uint16\_t nas\_QmiNas3GppNetworkRAT::MCC

8.386.2.2 uint16\_t nas\_QmiNas3GppNetworkRAT::MNC

8.386.2.3 uint8\_t nas\_QmiNas3GppNetworkRAT::RAT

## 8.387 nas\_QmisNasPcsDigit Struct Reference

## Data Fields

- uint16\_t [MCC](#)
- uint16\_t [MNC](#)
- uint8\_t [includes\\_pcs\\_digit](#)

## 8.387.1 Detailed Description

Contain the PCS Digit information

## Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
<i>MNC</i>	<ul style="list-style-type: none"> <li>• Mobile Network Code</li> </ul>
<i>includes_pcs_ - digit</i>	<ul style="list-style-type: none"> <li>• this field is use to interpret the length of corresponding MNC reported</li> <li>• 0x01 - MNC is a three-digit value</li> <li>• 0x00 - MNC is a two-digit value</li> </ul>

### 8.387.2 Field Documentation

8.387.2.1 uint8\_t nas\_QmisNasPcsDigit::includes\_pcs\_digit

8.387.2.2 uint16\_t nas\_QmisNasPcsDigit::MCC

8.387.2.3 uint16\_t nas\_QmisNasPcsDigit::MNC

## 8.388 nas\_RejectReasonTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint32\_t [serviceDomain](#)
- uint32\_t [rejectCause](#)

### 8.388.1 Detailed Description

#### Parameters

<i>TlvPresent</i>	indicating the presence of the TLV in the QMI ind
<i>serviceDomain</i>	service domain
<i>rejectCause</i>	cause of reject

### 8.388.2 Field Documentation

8.388.2.1 uint32\_t nas\_RejectReasonTlv::rejectCause

8.388.2.2 uint32\_t nas\_RejectReasonTlv::serviceDomain

8.388.2.3 uint8\_t nas\_RejectReasonTlv::TlvPresent

## 8.389 nas\_RFInfoTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint8\_t [radioInterfaceSize](#)
- uint32\_t [radioInterface](#) [255]
- uint32\_t [activeBandClass](#) [255]
- uint32\_t [activeChannel](#) [255]

### 8.389.1 Detailed Description

#### Parameters

<i>TlvPresent</i>	indicating the presence of the TLV in the QMI ind
<i>radioInterface</i>	radio interface technology of the signal being measured

<i>activeBandClass</i>	active band class
<i>activeChannel</i>	active channel

### 8.389.2 Field Documentation

8.389.2.1 uint32\_t nas\_RFInfoTlv::activeBandClass[255]

8.389.2.2 uint32\_t nas\_RFInfoTlv::activeChannel[255]

8.389.2.3 uint32\_t nas\_RFInfoTlv::radioInterface[255]

8.389.2.4 uint8\_t nas\_RFInfoTlv::radioInterfaceSize

8.389.2.5 uint8\_t nas\_RFInfoTlv::TlvPresent

## 8.390 nas\_roamIndList Struct Reference

### Data Fields

- uint8\_t [numInstances](#)
- uint8\_t [radioInterface](#) [32]
- uint8\_t [roamIndicator](#) [32]

### 8.390.1 Detailed Description

This structure contains the Roaming Indicator List

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• number of sets of radio interface currently in use and roaming indicator <ul style="list-style-type: none"> <li>– defaults to zero</li> </ul> </li> </ul>
<i>radioInterface</i>	<ul style="list-style-type: none"> <li>• Radio Interface currently in use</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - RADIO_IF_CDMA_1XEVD0 - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 - RADIO_IF_AMPS - AMPS</li> <li>– 0x04 - RADIO_IF_GSM - GSM</li> <li>– 0x05 - RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - RADIO_IF_LTE - LTE</li> </ul> </li> </ul>



<i>roamIndicator</i>	<ul style="list-style-type: none"> <li>• Roaming Indicator</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Roaming</li> <li>– 0x01 - Home</li> </ul> </li> </ul>
----------------------	---

### 8.390.2 Field Documentation

8.390.2.1 `uint8_t nas_roamIndList::numInstances`

8.390.2.2 `uint8_t nas_roamIndList::radioInterface[32]`

8.390.2.3 `uint8_t nas_roamIndList::roamIndicator[32]`

## 8.391 nas\_rsrqInformation Struct Reference

### Data Fields

- `int8_t` [rsrq](#)
- `uint8_t` [radioIf](#)

### 8.391.1 Detailed Description

This structure contains the RSRQ Information

#### Parameters

<i>rsrq</i>	<ul style="list-style-type: none"> <li>• RSRQ value in dB (signed integer value); valid range is -3 to -20 (-3 means -3 dB, -20 means -20 dB)</li> </ul>
<i>radioIf</i>	<ul style="list-style-type: none"> <li>• Radio interface technology of the signal being measured <ul style="list-style-type: none"> <li>– 0x08 – LTE</li> </ul> </li> </ul>

### 8.391.2 Field Documentation

8.391.2.1 `uint8_t nas_rsrqInformation::radioIf`

8.391.2.2 `int8_t nas_rsrqInformation::rsrq`

## 8.392 nas\_rxSignalStrengthListElement Struct Reference

### Data Fields

- `int16_t` [rxSignalStrength](#)
- `uint8_t` [radioIf](#)

### 8.392.1 Detailed Description

This structure contains the Received Signal Strength Information

#### Parameters

<i>rxSignalStrength</i>	<ul style="list-style-type: none"> <li>Received signal strength in dBm             <ul style="list-style-type: none"> <li>For CDMA and UMTS, this indicates forward link pilotEc.</li> <li>For GSM, the received signal strength.</li> <li>For LTE, this indicates the total received wideband power observed by UE.</li> </ul> </li> </ul>
<i>radiolf</i>	<ul style="list-style-type: none"> <li>Radio interface technology of the signal being radio_if measured             <ul style="list-style-type: none"> <li>0x00 – RADIO_IF_NO_SVC – None (no service)</li> <li>0x01 – RADIO_IF_CDMA_1X – cdma2000@ 1X</li> <li>0x02 – RADIO_IF_CDMA_1XEVDO – cdma2000 HRPD (1xEV-DO)</li> <li>0x03 – RADIO_IF_AMPS – AMPS</li> <li>0x04 – RADIO_IF_GSM – GSM</li> <li>0x05 – RADIO_IF_UMTS – UMTS</li> <li>0x08 – RADIO_IF_LTE – LTE</li> </ul> </li> </ul>

#### Note

First elemnet of the RSSI list always contains the current Signal strength and Radio Interface.

### 8.392.2 Field Documentation

8.392.2.1 `uint8_t nas_rxSignalStrengthListElement::radiolf`

8.392.2.2 `int16_t nas_rxSignalStrengthListElement::rxSignalStrength`

## 8.393 nas\_servSystem Struct Reference

#### Data Fields

- `uint8_t regState`
- `uint8_t csAttachState`
- `uint8_t psAttachState`
- `uint8_t selNetwork`
- `uint8_t numRadioInterfaces`
- `uint8_t radioInterface` [32]

### 8.393.1 Detailed Description

This structure contains the Serving System parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>regState</i>	<ul style="list-style-type: none"><li>• Registration state - Registration state of the mobile</li><li>• Values:<ul style="list-style-type: none"><li>– 0 - Not Registered; mobile is not currently searching for a new network to provide service</li><li>– 1 - Registered with a network</li><li>– 2 - Not registered, but mobile is currently searching for a new network to provide service</li><li>– 3 - Registration denied by visible network</li><li>– 4 - Registration state is unknown</li></ul></li></ul>
<i>csAttachState</i>	<ul style="list-style-type: none"><li>• CS Attach State - Circuit-switched domain attach state of the mobile</li><li>• Values:<ul style="list-style-type: none"><li>– 0 - Unknown or not applicable</li><li>– 1 - Attached</li><li>– 2 - Detached</li></ul></li></ul>
<i>psAttachState</i>	<ul style="list-style-type: none"><li>• PS Attach State - Packet-switched domain attach state of the mobile</li><li>• Values:<ul style="list-style-type: none"><li>– 0 - Unknown or not applicable</li><li>– 1 - Attached</li><li>– 2 - Detached</li></ul></li></ul>
<i>selNetwork</i>	<ul style="list-style-type: none"><li>• Selected Network - Type of selected radio access network</li><li>• Values:<ul style="list-style-type: none"><li>– 0 - Unknown</li><li>– 1 - 3GPP2 network</li><li>– 2 - 3GPP network</li></ul></li></ul>

<i>numRadio-Interfaces</i>	<ul style="list-style-type: none"> <li>• In Use Radio Interfaces Number <ul style="list-style-type: none"> <li>– Number of radio interfaces currently in use</li> <li>– defaults to zero</li> </ul> </li> </ul>
<i>radioInterface</i>	<ul style="list-style-type: none"> <li>• Radio Interface currently in use</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - RADIO_IF_NO_SVC - None(no service)</li> <li>– 0x01 - RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - RADIO_IF_CDMA_1XEVD0 - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 - RADIO_IF_AMPS - AMPS</li> <li>– 0x04 - RADIO_IF_GSM - GSM</li> <li>– 0x05 - RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - RADIO_IF_LTE - LTE</li> </ul> </li> </ul>

## 8.393.2 Field Documentation

8.393.2.1 `uint8_t nas_servSystem::csAttachState`

8.393.2.2 `uint8_t nas_servSystem::numRadioInterfaces`

8.393.2.3 `uint8_t nas_servSystem::psAttachState`

8.393.2.4 `uint8_t nas_servSystem::radioInterface[32]`

8.393.2.5 `uint8_t nas_servSystem::regState`

8.393.2.6 `uint8_t nas_servSystem::selNetwork`

## 8.394 nas\_SignalStrengthTlv Struct Reference

### Data Fields

- `uint8_t TlvPresent`
- `int8_t signalStrength`
- `uint32_t radioInterface`

### 8.394.1 Detailed Description

#### Parameters

<i>TlvPresent</i>	indicating the presence of the TLV in the QMI ind
-------------------	---

<i>signalStrength</i>	signal strength
<i>radioInterface</i>	radio interface technology of the signal being measured

## 8.394.2 Field Documentation

8.394.2.1 uint32\_t nas\_SignalStrengthTlv::radioInterface

8.394.2.2 int8\_t nas\_SignalStrengthTlv::signalStrength

8.394.2.3 uint8\_t nas\_SignalStrengthTlv::TlvPresent

## 8.395 nas\_SLQSSignalStrengthsIndReq Struct Reference

### Data Fields

- uint8\_t [rxSignalStrengthDelta](#)
- uint8\_t [ecioDelta](#)
- uint8\_t [ioDelta](#)
- uint8\_t [sinrDelta](#)
- uint8\_t [rsrqDelta](#)
- uint8\_t [ecioThresholdListLen](#)
- int16\_t [ecioThresholdList](#) [10]
- uint8\_t [sinrThresholdListLen](#)
- uint8\_t [sinrThresholdList](#) [5]
- uint16\_t [lteSnrDelta](#)
- uint8\_t [lteRsrpDelta](#)

## 8.395.1 Detailed Description

### Parameters

<i>rxSignalStrengthDelta</i>	RSSI delta(in dBm) at which an event report indication
<i>ecioDelta</i>	ecio delta
<i>ioDelta</i>	io delta
<i>sinrDelta</i>	sinr delta
<i>rsrqDelta</i>	rsrq delta
<i>ecioThresholdListLen</i>	
<i>ecioThresholdList</i>	
<i>sinrThresholdListLen</i>	
<i>sinrThresholdList</i>	
<i>lteSnrDelta</i>	lte snr delta
<i>lteRsrpDelta</i>	lte rsrp delta

## 8.395.2 Field Documentation

8.395.2.1 uint8\_t nas\_SLQSSignalStrengthsIndReq::ecioDelta

8.395.2.2 `int16_t nas_SLQSSignalStrengthsIndReq::ecioThresholdList[10]`

8.395.2.3 `uint8_t nas_SLQSSignalStrengthsIndReq::ecioThresholdListLen`

8.395.2.4 `uint8_t nas_SLQSSignalStrengthsIndReq::ioDelta`

8.395.2.5 `uint8_t nas_SLQSSignalStrengthsIndReq::lteRsrpDelta`

8.395.2.6 `uint16_t nas_SLQSSignalStrengthsIndReq::lteSnrDelta`

8.395.2.7 `uint8_t nas_SLQSSignalStrengthsIndReq::rsrqDelta`

8.395.2.8 `uint8_t nas_SLQSSignalStrengthsIndReq::rxSignalStrengthDelta`

8.395.2.9 `uint8_t nas_SLQSSignalStrengthsIndReq::sinrDelta`

8.395.2.10 `uint8_t nas_SLQSSignalStrengthsIndReq::sinrThresholdList[5]`

8.395.2.11 `uint8_t nas_SLQSSignalStrengthsIndReq::sinrThresholdListLen`

## 8.396 nas\_SLQSSignalStrengthsInformation Struct Reference

### Data Fields

- [nas\\_rxSignalStrengthListElement rxSignalStrengthInfo](#)
- [nas\\_ecioListElement ecioInfo](#)
- `uint32_t io`
- `uint8_t sinr`
- [nas\\_errorRateListElement errorRateInfo](#)
- [nas\\_rsrqInformation rsrqInfo](#)
- [nas\\_lteSnrinformation lteSnrinfo](#)
- [nas\\_lteRsrpinformation lteRsrpinfo](#)

### 8.396.1 Detailed Description

#### Parameters

<i>rxSignalStrengthInfo</i>	signal strength info list
<i>ecioInfo</i>	ecio info list
<i>io</i>	received IO in dBm; IO is only applicable for 1xEV-DO
<i>sinr</i>	SINR level
<i>errorRateInfo</i>	error rate info
<i>rsrqInfo</i>	rsrq info
<i>lteSnrinfo</i>	lte Snr information
<i>lteRsrpinfo</i>	lte rsrp info

### 8.396.2 Field Documentation

8.396.2.1 `nas_ecioListElement nas_SLQSSignalStrengthsInformation::ecioInfo`

8.396.2.2 `nas_errorRateListElement nas_SLQSSignalStrengthsInformation::errorRateInfo`

8.396.2.3 `uint32_t nas_SLQSSignalStrengthsInformation::io`

8.396.2.4 nas\_lteRsrpInformation nas\_SLQSSignalStrengthsInformation::lteRsrpinfo

8.396.2.5 nas\_lteSnrinformation nas\_SLQSSignalStrengthsInformation::lteSnrinfo

8.396.2.6 nas\_rsrqInformation nas\_SLQSSignalStrengthsInformation::rsrqInfo

8.396.2.7 nas\_rxSignalStrengthListElement nas\_SLQSSignalStrengthsInformation::rxSignalStrengthInfo

8.396.2.8 uint8\_t nas\_SLQSSignalStrengthsInformation::sinr

## 8.397 nas\_SLQSSignalStrengthsTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- [nas\\_SLQSSignalStrengthsInformation](#) sSLQSSignalStrengthsInfo

### 8.397.1 Detailed Description

#### Parameters

<i>TlvPresent</i>	indicating the presence of the TLV in the QMI ind
<i>sSLQSSignalStrengthsInfo</i>	signal strength info

### 8.397.2 Field Documentation

8.397.2.1 nas\_SLQSSignalStrengthsInformation nas\_SLQSSignalStrengthsTlv::sSLQSSignalStrengthsInfo

8.397.2.2 uint8\_t nas\_SLQSSignalStrengthsTlv::TlvPresent

## 8.398 nas\_SrvStatusInfo Struct Reference

### Data Fields

- uint8\_t [srvStatus](#)
- uint8\_t [isPrefDataPath](#)

### 8.398.1 Detailed Description

Structure for storing the service status information for CDMA and HDR networks.

## Parameters

<i>srvStatus</i>	<ul style="list-style-type: none"> <li>• Service status of the system. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - Power save</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>isPrefDataPath</i>	<ul style="list-style-type: none"> <li>• Whether the RAT is the preferred data path. <ul style="list-style-type: none"> <li>– 0x00 - Not preferred</li> <li>– 0x01 - Preferred</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

## 8.398.2 Field Documentation

8.398.2.1 `uint8_t nas_SrvStatusInfo::isPrefDataPath`8.398.2.2 `uint8_t nas_SrvStatusInfo::srvStatus`8.399 `nas_sysInfoCommon` Struct Reference

## Data Fields

- `uint8_t srvDomainValid`
- `uint8_t srvDomain`
- `uint8_t srvCapabilityValid`
- `uint8_t srvCapability`
- `uint8_t roamStatusValid`
- `uint8_t roamStatus`
- `uint8_t isSysForbiddenValid`
- `uint8_t isSysForbidden`

## 8.399.1 Detailed Description

Structure for storing the System Information common to CDMA, HDR, GSM, WCDMA and LTE networks.



## Parameters

<i>srvDomainValid</i>	<ul style="list-style-type: none"><li>• Indicates whether the service domain is valid.<ul style="list-style-type: none"><li>– 0x00 - Invalid</li><li>– 0x01 - Valid</li><li>– 0xFF - Not Available</li></ul></li></ul>
<i>srvDomain</i>	<ul style="list-style-type: none"><li>• Service domain registered on the system.<ul style="list-style-type: none"><li>– 0x00 - No service</li><li>– 0x01 - Circuit-switched only</li><li>– 0x02 - Packet-switched only</li><li>– 0x03 - Circuit-switched and packet-switched</li><li>– 0x04 - Camped</li><li>– 0xFF - Not Available</li></ul></li></ul>
<i>srvCapabilityValid</i>	<ul style="list-style-type: none"><li>• Indicates whether the service capability is valid.<ul style="list-style-type: none"><li>– 0x00 - Invalid</li><li>– 0x01 - Valid</li><li>– 0xFF - Not Available</li></ul></li></ul>
<i>srvCapability</i>	<ul style="list-style-type: none"><li>• Current system's service capability.<ul style="list-style-type: none"><li>– 0x00 - No service</li><li>– 0x01 - Circuit-switched only</li><li>– 0x02 - Packet-switched only</li><li>– 0x03 - Circuit-switched and packet-switched</li><li>– 0x04 - Camped</li><li>– 0xFF - Not Available</li></ul></li></ul>

<i>roamStatusValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the roaming status is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>roamStatus</i>	<ul style="list-style-type: none"> <li>Current roaming status. <ul style="list-style-type: none"> <li>0x00 - Off</li> <li>0x01 - On</li> <li>0x02 - Blinking</li> <li>0x03 - Out of the neighborhood</li> <li>0x04 - Out of the building</li> <li>0x05 - Preferred system</li> <li>0x06 - Available system</li> <li>0x07 - Alliance partner</li> <li>0x08 - Premium partner</li> <li>0x09 - Full service</li> <li>0x0A - Partial service</li> <li>0x0B - Banner is on</li> <li>0x0C - Banner is off</li> <li>0x0D to 0x3F - Reserved for Standard Enhanced Roaming Indicator Numbers</li> <li>0x40 to 0x7F - Reserved for Non-Standard Enhanced Roaming Indicator Numbers</li> <li>0x40 to 0xFF - Reserved.</li> <li>0xFF - Not Available</li> </ul> </li> <li>Values from 0x02 onward are only applicable for 3GPP2</li> </ul>

<i>isSysForbidden-Valid</i>	<ul style="list-style-type: none"> <li>Indicates whether the forbidden system is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>isSysForbidden</i>	<ul style="list-style-type: none"> <li>Whether the system is forbidden. <ul style="list-style-type: none"> <li>0x00 - Not forbidden</li> <li>0x01 - Forbidden</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

### 8.399.2 Field Documentation

8.399.2.1 `uint8_t nas_sysInfoCommon::isSysForbidden`

8.399.2.2 `uint8_t nas_sysInfoCommon::isSysForbiddenValid`

8.399.2.3 `uint8_t nas_sysInfoCommon::roamStatus`

8.399.2.4 `uint8_t nas_sysInfoCommon::roamStatusValid`

8.399.2.5 `uint8_t nas_sysInfoCommon::srvCapability`

8.399.2.6 `uint8_t nas_sysInfoCommon::srvCapabilityValid`

8.399.2.7 `uint8_t nas_sysInfoCommon::srvDomain`

8.399.2.8 `uint8_t nas_sysInfoCommon::srvDomainValid`

## 8.400 nas\_TDSCDMAECIOThresh Struct Reference

### Data Fields

- `uint8_t` [TDSCDMAECIOThreshListLen](#)
- `float *` [pTDSCDMAECIOThreshList](#)

### 8.400.1 Detailed Description

This structure contains TDSCDMA ECIO threshold related parameters.

#### Parameters

<i>TDSCDMAECIOThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the TDSCDMA ECIO threshold list parameter to follow</li> </ul>
---------------------------------	---

<i>pTDSCDMAECIOThreshList</i>	<ul style="list-style-type: none"> <li>• Array of ECIO thresholds (in dB) used by TD-SCDMA</li> <li>• Maximum of 32 values.</li> </ul>
-------------------------------	--

## 8.400.2 Field Documentation

8.400.2.1 `float* nas_TDSCDMAECIOThresh::pTDSCDMAECIOThreshList`

8.400.2.2 `uint8_t nas_TDSCDMAECIOThresh::TDSCDMAECIOThreshListLen`

## 8.401 nas\_TDSCDMARSCPThresh Struct Reference

### Data Fields

- `uint8_t` [TDSCDMARSCPThreshListLen](#)
- `int16_t *` [pTDSCDMARSCPThreshList](#)

### 8.401.1 Detailed Description

This structure contains TDSCDMA RSCP threshold related parameters.

#### Parameters

<i>TDSCDMARSCPThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the TDSCDMA RSCP threshold list parameter to follow</li> </ul>
<i>pTDSCDMARSCPThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSCP thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values</li> <li>• Range for RSCP values: -120 to -25 (in dBm).</li> </ul>

## 8.401.2 Field Documentation

8.401.2.1 `int16_t* nas_TDSCDMARSCPThresh::pTDSCDMARSCPThreshList`

8.401.2.2 `uint8_t nas_TDSCDMARSCPThresh::TDSCDMARSCPThreshListLen`

## 8.402 nas\_TDSCDMARSSIThresh Struct Reference

### Data Fields

- `uint8_t` [TDSCDMARSSIThreshListLen](#)
- `float *` [pTDSCDMARSSIThreshList](#)

### 8.402.1 Detailed Description

This structure contains TDSCDMA RSSI threshold related parameters.

## Parameters

<i>TDSCDMARSS- IThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the TDSCDMA RSSI threshold list parameter to follow</li> </ul>
<i>pTDSCDMARSS- SIThreshList</i>	<ul style="list-style-type: none"> <li>Array of RSSI thresholds (in dBm) used by TD-SCDMA</li> <li>Maximum of 32 values.</li> </ul>

## 8.402.2 Field Documentation

8.402.2.1 float\* nas\_TDSCDMARSSIThresh::pTDSCDMARSSIThreshList

8.402.2.2 uint8\_t nas\_TDSCDMARSSIThresh::TDSCDMARSSIThreshListLen

## 8.403 nas\_TDSCDMASINRThresh Struct Reference

## Data Fields

- uint8\_t [TDSCDMASINRThreshListLen](#)
- float \* [pTDSCDMASINRThreshList](#)

## 8.403.1 Detailed Description

This structure contains TDSCDMA SINR threshold related parameters.

## Parameters

<i>TDSCDMASIN- RThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the TDSCDMA SINR threshold list parameter to follow</li> </ul>
<i>pTDSCDMASIN- RThreshList</i>	<ul style="list-style-type: none"> <li>Array of SINR thresholds (in dB) used by TD-SCDMA</li> <li>Maximum of 32 values</li> </ul>

## 8.403.2 Field Documentation

8.403.2.1 float\* nas\_TDSCDMASINRThresh::pTDSCDMASINRThreshList

8.403.2.2 uint8\_t nas\_TDSCDMASINRThresh::TDSCDMASINRThreshListLen

## 8.404 nas\_timeInfo Struct Reference

## Data Fields

- uint16\_t [year](#)
- uint8\_t [month](#)
- uint8\_t [day](#)
- uint8\_t [hour](#)

- uint8\_t [minute](#)
- uint8\_t [second](#)
- uint8\_t [dayOfWeek](#)
- int8\_t [timeZone](#)
- uint8\_t [dayLtSavingAdj](#)
- uint8\_t [radioInterface](#)
- uint8\_t [TlvPresent](#)

#### 8.404.1 Detailed Description

This structure contains the parameters for Network Time.

##### Parameters

<i>year</i>	<ul style="list-style-type: none"> <li>• Year</li> </ul>
<i>month</i>	<ul style="list-style-type: none"> <li>• Month</li> <li>• 1 is January and 12 is December</li> </ul>
<i>day</i>	<ul style="list-style-type: none"> <li>• Day</li> <li>• Range - 1 to 31</li> </ul>
<i>hour</i>	<ul style="list-style-type: none"> <li>• Hour</li> <li>• Range - 0 to 59</li> </ul>
<i>minute</i>	<ul style="list-style-type: none"> <li>• Minute</li> <li>• Range - 0 to 59</li> </ul>
<i>second</i>	<ul style="list-style-type: none"> <li>• Second</li> <li>• Range - 0 to 59</li> </ul>
<i>dayOfWeek</i>	<ul style="list-style-type: none"> <li>• Day of the week</li> <li>• 0 is Monday and 6 is Sunday</li> </ul>
<i>timeZone</i>	<ul style="list-style-type: none"> <li>• Offset from Universal time</li> <li>• The difference between local time and Universal time, in increments of 15 min</li> <li>• Signed Value</li> </ul>

<i>dayLtSavingAdj</i>	<ul style="list-style-type: none"> <li>• Daylight saving adjustment in hours</li> <li>• Possible values - 0, 1, and 2.</li> <li>• This field is ignored if radio_if is NAS_RADIO_IF_CDMA_1XEVDO</li> </ul>
<i>radioInterface</i>	<ul style="list-style-type: none"> <li>• Radio interface from which the information comes</li> <li>• Values <ul style="list-style-type: none"> <li>– 0x01 - NAS_RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - NAS_RADIO_IF_CDMA_1XEVDO - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x04 - NAS_RADIO_IF_GSM - GSM</li> <li>– 0x05 - NAS_RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - NAS_RADIO_IF_LTE - LTE</li> <li>– 0x09 - NAS_RADIO_IF_TDSCDMA -TD-SCDMA</li> </ul> </li> </ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Tlv Present.</li> </ul>

## 8.404.2 Field Documentation

8.404.2.1 uint8\_t nas\_timeInfo::day

8.404.2.2 uint8\_t nas\_timeInfo::dayLtSavingAdj

8.404.2.3 uint8\_t nas\_timeInfo::dayOfWeek

8.404.2.4 uint8\_t nas\_timeInfo::hour

8.404.2.5 uint8\_t nas\_timeInfo::minute

8.404.2.6 uint8\_t nas\_timeInfo::month

8.404.2.7 uint8\_t nas\_timeInfo::radioInterface

8.404.2.8 uint8\_t nas\_timeInfo::second

8.404.2.9 int8\_t nas\_timeInfo::timeZone

8.404.2.10 uint8\_t nas\_timeInfo::TlvPresent

8.404.2.11 uint16\_t nas\_timeInfo::year

## 8.405 nas\_UMTSInfo Struct Reference

### Data Fields

- uint16\_t [cellID](#)
- uint8\_t [plmn](#) [3]

- uint16\_t [lac](#)
- uint16\_t [uarfcn](#)
- uint16\_t [psc](#)
- int16\_t [rscp](#)
- int16\_t [ecio](#)
- uint8\_t [umtsInst](#)
- [nas\\_UMTSInstInfo](#) [UMTSInstInfo](#) [255]
- uint8\_t [geranInst](#)
- [nas\\_geranInstInfo](#) [GeranInstInfo](#) [255]

### 8.405.1 Detailed Description

This structure contains information about the UMTS Network.

#### Parameters

<i>cellID</i>	<ul style="list-style-type: none"> <li>• Cell ID.</li> <li>• 0xFFFFFFFF indicates cell ID information is not present.</li> </ul>
<i>plmn[NAS_PLM-N_LENGTH]</i>	<ul style="list-style-type: none"> <li>• MCC/MNC information coded as octet 3, 4, and 5.</li> <li>• This field is ignored when nmrCellID is not present.</li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• This field is ignored when nmrCellID is not present. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>uarfcn</i>	<ul style="list-style-type: none"> <li>• UTRA absolute RF channel number. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>psc</i>	<ul style="list-style-type: none"> <li>• Primary scrambling code. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>rscp</i>	<ul style="list-style-type: none"> <li>• Received signal code power. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>



<i>ecio</i>	<ul style="list-style-type: none"> <li>• ECIO(Signal-to-Interference-ratio). <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>umtsInst</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of UMTS info instances.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>UMTSInstInfo[N-AS_MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_UMTSInstInfo</a> for more information.</li> </ul>
<i>geranInst</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of GERAN info instances.</li> <li>• If 0(zero), then no information follows it.</li> </ul>
<i>GeranInstInfo[N-AS_MAX_DESCRIPTION_LENGTH]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_geranInstInfo</a> for more information.</li> </ul>

## 8.405.2 Field Documentation

8.405.2.1 uint16\_t nas\_UMTSInfo::cellID

8.405.2.2 int16\_t nas\_UMTSInfo::ecio

8.405.2.3 uint8\_t nas\_UMTSInfo::geranInst

8.405.2.4 nas\_geranInstInfo nas\_UMTSInfo::GeranInstInfo[255]

8.405.2.5 uint16\_t nas\_UMTSInfo::lac

8.405.2.6 uint8\_t nas\_UMTSInfo::plmn[3]

8.405.2.7 uint16\_t nas\_UMTSInfo::psc

8.405.2.8 int16\_t nas\_UMTSInfo::rscp

8.405.2.9 uint16\_t nas\_UMTSInfo::uarfcn

8.405.2.10 uint8\_t nas\_UMTSInfo::umtsInst

8.405.2.11 nas\_UMTSInstInfo nas\_UMTSInfo::UMTSInstInfo[255]

## 8.406 nas\_UMTSInstInfo Struct Reference

### Data Fields

- uint16\_t [umtsUarfcn](#)
- uint16\_t [umtsPsc](#)

- int16\_t [umtsRscp](#)
- int16\_t [umtsEcio](#)

### 8.406.1 Detailed Description

This structure contains information about the UMTS Instances in UMTS Network.

#### Parameters

<i>umtsUarfcn</i>	<ul style="list-style-type: none"> <li>• UTRA absolute RF channel number.</li> </ul>
<i>umtsPsc</i>	<ul style="list-style-type: none"> <li>• Primary scrambling code.</li> </ul>
<i>umtsRscp</i>	<ul style="list-style-type: none"> <li>• Received signal code power.</li> </ul>
<i>umtsEcio</i>	<ul style="list-style-type: none"> <li>• ECIO(Signal-to-Interference-ratio).</li> </ul>

### 8.406.2 Field Documentation

8.406.2.1 int16\_t nas\_UMTSinstInfo::umtsEcio

8.406.2.2 uint16\_t nas\_UMTSinstInfo::umtsPsc

8.406.2.3 int16\_t nas\_UMTSinstInfo::umtsRscp

8.406.2.4 uint16\_t nas\_UMTSinstInfo::umtsUarfcn

## 8.407 nas\_umtsLTENbrCell Struct Reference

### Data Fields

- uint16\_t [earfcn](#)
- uint16\_t [pci](#)
- uint32\_t [rsrp](#)
- uint32\_t [rsrq](#)
- int16\_t [srxlev](#)
- uint8\_t [cellsTDD](#)

### 8.407.1 Detailed Description

This structure contains information about the UMTS LTE neighbour Cell.

## Parameters

<i>earfcn</i>	<ul style="list-style-type: none"> <li>E-UTRA absolute RF channel number of the detected cell.</li> </ul>
<i>pci</i>	<ul style="list-style-type: none"> <li>Physical cell ID of the detected cell.</li> <li>Range is defined in 3GPP TS 36.211</li> </ul>
<i>rsrp</i>	<ul style="list-style-type: none"> <li>Current received signal strength indication (in dBm) of the detected cell.</li> </ul>
<i>rsrq</i>	<ul style="list-style-type: none"> <li>Current reference signal received quality (in dB) of the detected cell.</li> </ul>
<i>srxlev</i>	<ul style="list-style-type: none"> <li>Cell selection Rx level (Srxlev) value of the detected cell in linear scale.</li> <li>This field is only valid when wcdma_rrc_state is not NAS_WCDMA_RRC_STATE_C-EL_FACH or NAS_WCDMA_RRC_STATE_CELL_DCH.</li> </ul>
<i>cellsTDD</i>	<ul style="list-style-type: none"> <li>TRUE if the cell is TDD; FALSE if the cell is FDD.</li> </ul>

## 8.407.2 Field Documentation

8.407.2.1 uint8\_t nas\_umtsLTENbrCell::cellsTDD

8.407.2.2 uint16\_t nas\_umtsLTENbrCell::earfcn

8.407.2.3 uint16\_t nas\_umtsLTENbrCell::pci

8.407.2.4 uint32\_t nas\_umtsLTENbrCell::rsrp

8.407.2.5 uint32\_t nas\_umtsLTENbrCell::rsrq

8.407.2.6 int16\_t nas\_umtsLTENbrCell::srxlev

## 8.408 nas\_UniversalTime Struct Reference

## Data Fields

- uint16\_t [year](#)
- uint8\_t [month](#)
- uint8\_t [day](#)
- uint8\_t [hour](#)
- uint8\_t [minute](#)
- uint8\_t [second](#)
- uint8\_t [dayOfWeek](#)

### 8.408.1 Detailed Description

This structure contains the parameters for Universal Time Information.

## Parameters

<i>year</i>	<ul style="list-style-type: none"><li>• Year.</li></ul>
<i>month</i>	<ul style="list-style-type: none"><li>• Month.<ul style="list-style-type: none"><li>– 1 is January and 12 is December.</li></ul></li></ul>
<i>day</i>	<ul style="list-style-type: none"><li>• Day.<ul style="list-style-type: none"><li>– Range 1 to 31.</li></ul></li></ul>
<i>hour</i>	<ul style="list-style-type: none"><li>• Hour.<ul style="list-style-type: none"><li>– Range 0 to 59.</li></ul></li></ul>
<i>minute</i>	<ul style="list-style-type: none"><li>• Minute.<ul style="list-style-type: none"><li>– Range 0 to 59.</li></ul></li></ul>
<i>second</i>	<ul style="list-style-type: none"><li>• Second.<ul style="list-style-type: none"><li>– Range 0 to 59.</li></ul></li></ul>
<i>dayOfWeek</i>	<ul style="list-style-type: none"><li>• Day of the Week.<ul style="list-style-type: none"><li>– 0 is Monday and 6 is Sunday.</li></ul></li></ul>

## 8.408.2 Field Documentation

8.408.2.1 `uint8_t nas_UniversalTime::day`

8.408.2.2 `uint8_t nas_UniversalTime::dayOfWeek`

8.408.2.3 `uint8_t nas_UniversalTime::hour`

8.408.2.4 `uint8_t nas_UniversalTime::minute`

8.408.2.5 `uint8_t nas_UniversalTime::month`

8.408.2.6 `uint8_t nas_UniversalTime::second`

8.408.2.7 `uint16_t nas_UniversalTime::year`

## 8.409 nas\_wcdmaCellInfo Struct Reference

### Data Fields

- uint16\_t [psc](#)
- int16\_t [cpich\\_rscp](#)
- int16\_t [cpich\\_ecno](#)
- int16\_t [srxlev](#)

### 8.409.1 Detailed Description

This structure contains information about the WCDMA Cell.

#### Parameters

<i>psc</i>	<ul style="list-style-type: none"> <li>• Primary scrambling code.</li> <li>• Range: 0 to 511.</li> </ul>
<i>cpich_rscp</i>	<ul style="list-style-type: none"> <li>• Absolute power level (in 1/10 dBm) of the common pilot channel as received by the UE.</li> <li>• Range: -120.0 dBm to -25.0 dBm</li> </ul>
<i>cpich_ecno</i>	<ul style="list-style-type: none"> <li>• CPICH Ec/No; ratio (in 1/10 dB) of the received energy per PN chip for the CPICH to the total received power spectral density at the UE antenna connector.</li> <li>• Range: -50.0 dB to 0.</li> </ul>
<i>srxlev</i>	<ul style="list-style-type: none"> <li>• Cell selection Rx level (Srxlev) value.</li> <li>• Range: -128 to 128.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>

### 8.409.2 Field Documentation

8.409.2.1 int16\_t nas\_wcdmaCellInfo::cpich\_ecno

8.409.2.2 int16\_t nas\_wcdmaCellInfo::cpich\_rscp

8.409.2.3 uint16\_t nas\_wcdmaCellInfo::psc

8.409.2.4 int16\_t nas\_wcdmaCellInfo::srxlev

## 8.410 nas\_WCDMAECIOThresh Struct Reference

### Data Fields

- uint8\_t [WCDMAECIOThreshListLen](#)
- int16\_t \* [pWCDMAECIOThreshList](#)

### 8.410.1 Detailed Description

This structure contains WCDMA ECIO threshold related parameters.

#### Parameters

<i>WCDMAECIO- ThreshListLen</i>	<ul style="list-style-type: none"><li>• Length of the WCDMA ECIO threshold list parameter to follow</li></ul>
<i>pWCDMAECIO- ThreshList</i>	<ul style="list-style-type: none"><li>• Array of ECIO thresholds (in units of 0.1 dB)</li><li>• Maximum of 32 values</li><li>• Range for ECIO values: -31.5 to 0 (in dB)</li></ul>

### 8.410.2 Field Documentation

8.410.2.1 `int16_t*` `nas_WCDMAECIOThresh::pWCDMAECIOThreshList`

8.410.2.2 `uint8_t` `nas_WCDMAECIOThresh::WCDMAECIOThreshListLen`

## 8.411 nas\_WCDMAInfoLTENeighborCell Struct Reference

### Data Fields

- `uint32_t` [wcdmaRRCTest](#)
- `uint8_t` [umtsLTENbrCellLen](#)
- [nas\\_umtsLTENbrCell](#) `UMTSLTENbrCell` [255]

### 8.411.1 Detailed Description

This structure contains information about the WCDMA - LTE Neighboring Cell Info Set.

## Parameters

<i>wcdmaRRC-State</i>	<ul style="list-style-type: none"> <li>• WCDMA RRC states.</li> <li>• Defined in 3GPP TS 25.331</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - NAS_WCDMA_RRC_STATE_DISCONNECTED <ul style="list-style-type: none"> <li>* WCDMA RRC State is IDLE</li> </ul> </li> <li>– 0x01 - NAS_WCDMA_RRC_STATE_CELL_PCH <ul style="list-style-type: none"> <li>* WCDMA RRC state is CELL_PCH</li> </ul> </li> <li>– 0x02 - NAS_WCDMA_RRC_STATE_URA_PCH <ul style="list-style-type: none"> <li>* WCDMA RRC state is URA_PCH</li> </ul> </li> <li>– 0x03 - NAS_WCDMA_RRC_STATE_CELL_FACH <ul style="list-style-type: none"> <li>* WCDMA RRC state is CELL_FACH</li> </ul> </li> <li>– 0x04 - NAS_WCDMA_RRC_STATE_CELL_DCH <ul style="list-style-type: none"> <li>* WCDMA RRC state is CELL_DCH</li> </ul> </li> </ul> </li> </ul>
<i>umtsLTENbr-CellLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of UMTS LTE Neighbors.</li> </ul>
<i>UMTSLTENbr-Cell</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_umtsLTENbrCell</a> for more information.</li> </ul>

## 8.411.2 Field Documentation

8.411.2.1 `nas_umtsLTENbrCell nas_WCDMAInfoLTENeighborCell::UMTSLTENbrCell[255]`8.411.2.2 `uint8_t nas_WCDMAInfoLTENeighborCell::umtsLTENbrCellLen`8.411.2.3 `uint32_t nas_WCDMAInfoLTENeighborCell::wcdmaRRCState`8.412 `nas_WCDMARSSIThresh` Struct Reference

## Data Fields

- `uint8_t` [WCDMARSSIThreshListLen](#)
- `int16_t *` [pWCDMARSSIThreshList](#)

## 8.412.1 Detailed Description

This structure contains WCDMA RSSI threshold related parameters.

## Parameters



<i>WCDMARSSI- ThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the WCDMA RSSI threshold list parameter to follow</li> </ul>
<i>pWCDMARSSI- ThreshList</i>	<ul style="list-style-type: none"> <li>Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>Maximum of 32 values.</li> <li>Range for RSSI values: -121 to 0 (in dBm)</li> </ul>

## 8.412.2 Field Documentation

8.412.2.1 `int16_t* nas_WCDMARSSIThresh::pWCDMARSSIThreshList`

8.412.2.2 `uint8_t nas_WCDMARSSIThresh::WCDMARSSIThreshListLen`

## 8.413 nas\_WCDMASysInfo Struct Reference

### Data Fields

- [nas\\_sysInfoCommon sysInfoWCDMA](#)
- `uint8_t lacValid`
- `uint16_t lac`
- `uint8_t cellIdValid`
- `uint32_t cellId`
- `uint8_t regRejectInfoValid`
- `uint8_t rejectSrvDomain`
- `uint8_t rejCause`
- `uint8_t networkIdValid`
- `uint8_t MCC [3]`
- `uint8_t MNC [3]`
- `uint8_t hsCallStatusValid`
- `uint8_t hsCallStatus`
- `uint8_t hsIndValid`
- `uint8_t hsInd`
- `uint8_t pscValid`
- `uint16_t psc`

### 8.413.1 Detailed Description

Structure for storing the WCDMA System Information.

#### Parameters

<i>sysInfoWCDMA</i>	<ul style="list-style-type: none"> <li>See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
---------------------	---

<i>lacValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the location area code is valid.. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>Location area code.</li> <li>Only applies to 3GPP. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>cellIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the cell ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>cellId</i>	<ul style="list-style-type: none"> <li>Cell ID. <ul style="list-style-type: none"> <li>0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>regRejectInfoValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the registration reject information is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>rejectSrvDomain</i>	<ul style="list-style-type: none"> <li>Type of service domain in which the registration is rejected. <ul style="list-style-type: none"> <li>0x00 - SYS_SRV_DOMAIN_NO_SRV - No service</li> <li>0x01 - Circuit-switched only</li> <li>0x02 - Packet-switched only</li> <li>0x03 - Circuit-switched and packet-switched</li> <li>0x04 - Camped</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

<i>rejCause</i>	<ul style="list-style-type: none"> <li>Reject cause values sent are specified in [3GPP TS 24.008, Section 10.5.3.6]. <ul style="list-style-type: none"> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>networkIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the network ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>MCC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Country Code.</li> <li>MCC digits in ASCII characters</li> </ul>
<i>MNC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Network Code.</li> <li>MNC digits in ASCII characters</li> <li>An unused byte is set to 0xFF.</li> <li>In case of two-digit MNC values, the third (unused) digit is set to 0xFF. For example, 15 (a two-digit MNC) is reported using the byte stream 0x31 0x35 0xFF.</li> </ul>
<i>hsCallStatusValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the high-speed call status is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>hsCallStatus</i>	<ul style="list-style-type: none"> <li>Call status on high speed.</li> <li>Only applicable for WCDMA. <ul style="list-style-type: none"> <li>0x00 - HSDPA and HSUPA are unsupported</li> <li>0x01 - HSDPA is supported</li> <li>0x02 - HSUPA is supported</li> <li>0x03 - HSDPA and HSUPA are supported</li> <li>0x04 - HSDPA+ is supported</li> <li>0x05 - HSDPA+ and HSUPA are supported</li> <li>0x06 - Dual-cell HSDPA+ is supported</li> <li>0x07 - Dual-cell HSDPA+ and HSUPA are supported</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

<i>hsIndValid</i>	<ul style="list-style-type: none"> <li>Indicates whether high-speed service indication is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>hsInd</i>	<ul style="list-style-type: none"> <li>High-speed service indication</li> <li>Only applicable for WCDMA. <ul style="list-style-type: none"> <li>0x00 - HSDPA and HSUPA are unsupported</li> <li>0x01 - HSDPA is supported</li> <li>0x02 - HSUPA is supported</li> <li>0x03 - HSDPA and HSUPA are supported</li> <li>0x04 - HSDPA+ is supported</li> <li>0x05 - HSDPA+ and HSUPA are supported</li> <li>0x06 - Dual-cell HSDPA+ is supported</li> <li>0x07 - Dual-cell HSDPA+ and HSUPA are supported</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>pscValid</i>	<ul style="list-style-type: none"> <li>Indicates whether primary scrambling code is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>psc</i>	<ul style="list-style-type: none"> <li>Primary scrambling code. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>

## 8.413.2 Field Documentation

8.413.2.1 `uint32_t nas_WCDMASysInfo::cellId`

8.413.2.2 `uint8_t nas_WCDMASysInfo::cellIdValid`

8.413.2.3 `uint8_t nas_WCDMASysInfo::hsCallStatus`

8.413.2.4 `uint8_t nas_WCDMASysInfo::hsCallStatusValid`

8.413.2.5 `uint8_t nas_WCDMASysInfo::hsInd`

8.413.2.6 `uint8_t nas_WCDMASysInfo::hsIndValid`

- 8.413.2.7 `uint16_t nas_WCDMASysInfo::lac`
- 8.413.2.8 `uint8_t nas_WCDMASysInfo::lacValid`
- 8.413.2.9 `uint8_t nas_WCDMASysInfo::MCC[3]`
- 8.413.2.10 `uint8_t nas_WCDMASysInfo::MNC[3]`
- 8.413.2.11 `uint8_t nas_WCDMASysInfo::networkIdValid`
- 8.413.2.12 `uint16_t nas_WCDMASysInfo::psc`
- 8.413.2.13 `uint8_t nas_WCDMASysInfo::pscValid`
- 8.413.2.14 `uint8_t nas_WCDMASysInfo::regRejectInfoValid`
- 8.413.2.15 `uint8_t nas_WCDMASysInfo::rejCause`
- 8.413.2.16 `uint8_t nas_WCDMASysInfo::rejectSrvDomain`
- 8.413.2.17 `nas_sysInfoCommon nas_WCDMASysInfo::sysInfoWCDMA`

## 8.414 NASBandPreferenceTlv Struct Reference

### Data Fields

- `uint8_t TlvPresent`
- `uint64_t band_pref`

### 8.414.1 Field Documentation

- 8.414.1.1 `uint64_t NASBandPreferenceTlv::band_pref`
- 8.414.1.2 `uint8_t NASBandPreferenceTlv::TlvPresent`

## 8.415 nasCellLocationInfoResp Struct Reference

### Data Fields

- `GERANInfo * pGERANInfo`
- `UMTSInfo * pUMTSInfo`
- `CDMAInfo * pCDMAInfo`
- `LTEInfoIntrafreq * pLTEInfoIntrafreq`
- `LTEInfoInterfreq * pLTEInfoInterfreq`
- `LTEInfoNeighboringGSM * pLTEInfoNeighboringGSM`
- `LTEInfoNeighboringWCDMA * pLTEInfoNeighboringWCDMA`
- `ULONG * pUMTSCellID`
- `WCDMAInfoLTENeighborCell * pWCDMAInfoLTENeighborCell`

### 8.415.1 Detailed Description

This structure contains information about the Get Cell Location response parameters.

## Parameters

<i>pGERANInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">GERANInfo</a> for more information.</li> </ul>
<i>pUMTSInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">UMTSInfo</a> for more information.</li> </ul>
<i>pCDMAInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">CDMAInfo</a> for more information.</li> </ul>
<i>pLTEInfo-Intrafreq</i>	<ul style="list-style-type: none"> <li>See <a href="#">LTEInfoIntrafreq</a> for more information.</li> </ul>
<i>pLTEInfo-Interfreq</i>	<ul style="list-style-type: none"> <li>See <a href="#">LTEInfoInterfreq</a> for more information.</li> </ul>
<i>pLTEInfo-NeighboringGSM</i>	<ul style="list-style-type: none"> <li>See <a href="#">LTEInfoNeighboringGSM</a> for more information.</li> </ul>
<i>pLTEInfo-NeighboringWCDMA</i>	<ul style="list-style-type: none"> <li>See <a href="#">LTEInfoNeighboringWCDMA</a> for more information.</li> </ul>
<i>pUMTSCellID</i>	<ul style="list-style-type: none"> <li>Cell ID.</li> <li>0xFFFFFFFF indicates cell ID information is not present.</li> </ul>
<i>pWCDMAInfoLT-ENeighborCell</i>	<ul style="list-style-type: none"> <li>See <a href="#">WCDMAInfoLTENeighborCell</a> for more information.</li> </ul>

## 8.415.2 Field Documentation

8.415.2.1 **CDMAInfo\*** nasCellLocationInfoResp::pCDMAInfo8.415.2.2 **GERANInfo\*** nasCellLocationInfoResp::pGERANInfo8.415.2.3 **LTEInfoInterfreq\*** nasCellLocationInfoResp::pLTEInfoInterfreq8.415.2.4 **LTEInfoIntrafreq\*** nasCellLocationInfoResp::pLTEInfoIntrafreq8.415.2.5 **LTEInfoNeighboringGSM\*** nasCellLocationInfoResp::pLTEInfoNeighboringGSM8.415.2.6 **LTEInfoNeighboringWCDMA\*** nasCellLocationInfoResp::pLTEInfoNeighboringWCDMA8.415.2.7 **ULONG\*** nasCellLocationInfoResp::pUMTSCellID8.415.2.8 **UMTSInfo\*** nasCellLocationInfoResp::pUMTSInfo8.415.2.9 **WCDMAInfoLTENeighborCell\*** nasCellLocationInfoResp::pWCDMAInfoLTENeighborCell

## 8.416 NASEmergencyModeTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint8\_t [EmerMode](#)

### 8.416.1 Field Documentation

8.416.1.1 uint8\_t NASEmergencyModeTlv::EmerMode

8.416.1.2 uint8\_t NASEmergencyModeTlv::TlvPresent

## 8.417 nasGet3GPP2SubscriptionInfoReq Struct Reference

### Data Fields

- [BYTE](#) [namID](#)

### 8.417.1 Detailed Description

This structure contains the Get3GPP2SubscriptionInfo request parameters

#### Parameters

<i>namID</i>	[Mandatory]
	<ul style="list-style-type: none"> <li>• NAM ID of the information to be retrieved. The index starts from 0. A <code>nam_id</code> of 0xFF is used to retrieve information of current NAM.</li> </ul>

### 8.417.2 Field Documentation

8.417.2.1 [BYTE](#) [nasGet3GPP2SubscriptionInfoReq::namID](#)

## 8.418 nasGet3GPP2SubscriptionInfoResp Struct Reference

### Data Fields

- [namName](#) \* [pNAMNameInfo](#)
- [dirNum](#) \* [pDirNum](#)
- [homeSIDNID](#) \* [pHomeSIDNID](#)
- [minBasedIMSI](#) \* [pMinBasedIMSI](#)
- [trueIMSI](#) \* [pTrueIMSI](#)
- [CDMAChannel](#) \* [pCDMAChannel](#)

### 8.418.1 Detailed Description

This structure contains the SLQSNasGet3GPP2Subscription response parameters.

## Parameters

<i>pNAMNameInfo</i>	[Optional] <ul style="list-style-type: none"><li>• See <a href="#">namName</a> for more information</li></ul>
<i>pDirNum</i>	[Optional] <ul style="list-style-type: none"><li>• See <a href="#">dirNum</a> for more information</li></ul>
<i>pHomeSIDNID</i>	[Optional] <ul style="list-style-type: none"><li>• See <a href="#">homeSIDNID</a> for more information</li></ul>
<i>pMinBasedIMSI</i>	[Optional] <ul style="list-style-type: none"><li>• See <a href="#">minBasedIMSI</a> for more information</li></ul>
<i>pTrueIMSI</i>	[Optional] <ul style="list-style-type: none"><li>• See <a href="#">trueIMSI</a> for more information</li></ul>
<i>pCDMAChannel</i>	[Optional] <ul style="list-style-type: none"><li>• See <a href="#">CDMAChannel</a> for more information</li></ul>

## 8.418.2 Field Documentation

8.418.2.1 **CDMAChannel\*** nasGet3GPP2SubscriptionInfoResp::pCDMAChannel8.418.2.2 **dirNum\*** nasGet3GPP2SubscriptionInfoResp::pDirNum8.418.2.3 **homeSIDNID\*** nasGet3GPP2SubscriptionInfoResp::pHomeSIDNID8.418.2.4 **minBasedIMSI\*** nasGet3GPP2SubscriptionInfoResp::pMinBasedIMSI8.418.2.5 **namName\*** nasGet3GPP2SubscriptionInfoResp::pNAMNameInfo8.418.2.6 **trueIMSI\*** nasGet3GPP2SubscriptionInfoResp::pTrueIMSI

## 8.419 nasGetHDRColorCodeResp Struct Reference

## Data Fields

- **BYTE \*** [pColorCode](#)

## 8.419.1 Detailed Description

Structure for storing the current preferred system selection settings for the device.



## Parameters

<i>pColorCode</i>	[Optional] <ul style="list-style-type: none"> <li>• Color code value</li> <li>• Color code corresponding to the sector to which the AT is sending the access probe</li> <li>• See 3GPP2 C.S0024-B V3.0, Section 7.11.6.2.1 for more information.             <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
-------------------	---

## 8.419.2 Field Documentation

8.419.2.1 BYTE\* nasGetHDRColorCodeResp::pColorCode

## 8.420 nasGetLTECphyCa Struct Reference

## Data Fields

- [PhyCaAggScellIndType](#) sPhyCaAggScellIndType
- [PhyCaAggScellDIBw](#) sPhyCaAggScellDIBw
- [PhyCaAggScellInfo](#) sPhyCaAggScellInfo
- [PhyCaAggPcellInfo](#) sPhyCaAggPcellInfo
- [PhyCaAggScellIndex](#) sPhyCaAggScellIndex

## 8.420.1 Field Documentation

8.420.1.1 [PhyCaAggPcellInfo](#) nasGetLTECphyCa::sPhyCaAggPcellInfo8.420.1.2 [PhyCaAggScellDIBw](#) nasGetLTECphyCa::sPhyCaAggScellDIBw8.420.1.3 [PhyCaAggScellIndex](#) nasGetLTECphyCa::sPhyCaAggScellIndex8.420.1.4 [PhyCaAggScellIndType](#) nasGetLTECphyCa::sPhyCaAggScellIndType8.420.1.5 [PhyCaAggScellInfo](#) nasGetLTECphyCa::sPhyCaAggScellInfo

## 8.421 NasGetLTECphyCaInfo Struct Reference

## Data Fields

- [NASPhyCaAggScellIndType](#) PhyCaAggScellIndType
- [NASPhyCaAggScellDIBw](#) PhyCaAggScellDIBw
- [NASPhyCaAggScellInfo](#) PhyCaAggScellInfo
- [NASPhyCaAggPcellInfo](#) PhyCaAggPcellInfo
- [NASPhyCaAggScellIndex](#) PhyCaAggScellIndex

## 8.421.1 Field Documentation

8.421.1.1 [NASPhyCaAggPcellInfo](#) NasGetLTECphyCaInfo::PhyCaAggPcellInfo8.421.1.2 [NASPhyCaAggScellDIBw](#) NasGetLTECphyCaInfo::PhyCaAggScellDIBw

8.421.1.3 **NASPhyCaAggScellIndex** `NasGetLTECphyCalInfo::PhyCaAggScellIndex`

8.421.1.4 **NASPhyCaAggScellIndType** `NasGetLTECphyCalInfo::PhyCaAggScellIndType`

8.421.1.5 **NASPhyCaAggScellInfo** `NasGetLTECphyCalInfo::PhyCaAggScellInfo`

## 8.422 nasGetLTECphyCaResp Struct Reference

### Data Fields

- [PhyCaAggScellIndType](#) \* [pPhyCaAggScellIndType](#)
- [PhyCaAggScellDIBw](#) \* [pPhyCaAggScellDIBw](#)
- [PhyCaAggScellInfo](#) \* [pPhyCaAggScellInfo](#)
- [PhyCaAggPcellInfo](#) \* [pPhyCaAggPcellInfo](#)
- [PhyCaAggScellIndex](#) \* [pPhyCaAggScellIndex](#)

### 8.422.1 Field Documentation

8.422.1.1 **PhyCaAggPcellInfo**\* `nasGetLTECphyCaResp::pPhyCaAggPcellInfo`

8.422.1.2 **PhyCaAggScellDIBw**\* `nasGetLTECphyCaResp::pPhyCaAggScellDIBw`

8.422.1.3 **PhyCaAggScellIndex**\* `nasGetLTECphyCaResp::pPhyCaAggScellIndex`

8.422.1.4 **PhyCaAggScellIndType**\* `nasGetLTECphyCaResp::pPhyCaAggScellIndType`

8.422.1.5 **PhyCaAggScellInfo**\* `nasGetLTECphyCaResp::pPhyCaAggScellInfo`

## 8.423 nasGetSigInfoResp Struct Reference

### Data Fields

- [CDMASSInfo](#) \* [pCDMASSInfo](#)
- [HDRSSInfo](#) \* [pHDRSSInfo](#)
- [INT8](#) \* [pGSMSSInfo](#)
- [CDMASSInfo](#) \* [pWCDMASSInfo](#)
- [LTESSInfo](#) \* [pLTESSInfo](#)
- [INT8](#) \* [pTDSCDMASigInfoRscp](#)
- [TDSCDMASigInfoExt](#) \* [pTDSCDMASigInfoExt](#)

### 8.423.1 Detailed Description

This structure contains the SLQSNasGetSigInfo response parameters.

#### Parameters

<i>pCDMASSInfo</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">CDMASSInfo</a> for more information</li> </ul>
--------------------	--

<i>pHDRSSInfo</i>	[Optional] <ul style="list-style-type: none"> <li>See <a href="#">HDRSSInfo</a> for more information</li> </ul>
<i>pGSMSSInfo</i>	[Optional] <ul style="list-style-type: none"> <li>GSM signal strength is the RSSI in dBm (signed value).</li> <li>A value of -125 dBm or lower is used to indicate No Signal.</li> </ul>
<i>pWCDMASSInfo</i>	[Optional] <ul style="list-style-type: none"> <li>See <a href="#">CDMASSInfo</a> for more information</li> </ul>
<i>pLTESSInfo</i>	[Optional] <ul style="list-style-type: none"> <li>See <a href="#">LTESSInfo</a> for more information</li> </ul>
<i>pTDSCDMASig-InfoRscp</i>	[Optional] <ul style="list-style-type: none"> <li>RSCP of the Primary Common Control Physical Channel (PCCPCH) in dBm.</li> <li>Measurement range: -120 dBm to -25 dBm.</li> </ul>
<i>pTDSCDMASig-InfoExt</i>	[Optional] <ul style="list-style-type: none"> <li>See <a href="#">TDSCDMASigInfoExt</a> for more information.</li> </ul>

## 8.423.2 Field Documentation

8.423.2.1 **CDMASSInfo\*** nasGetSigInfoResp::pCDMASSInfo

8.423.2.2 **INT8\*** nasGetSigInfoResp::pGSMSSInfo

8.423.2.3 **HDRSSInfo\*** nasGetSigInfoResp::pHDRSSInfo

8.423.2.4 **LTESSInfo\*** nasGetSigInfoResp::pLTESSInfo

8.423.2.5 **TDSCDMASigInfoExt\*** nasGetSigInfoResp::pTDSCDMASigInfoExt

8.423.2.6 **INT8\*** nasGetSigInfoResp::pTDSCDMASigInfoRscp

8.423.2.7 **CDMASSInfo\*** nasGetSigInfoResp::pWCDMASSInfo

## 8.424 nasGetSysInfoResp Struct Reference

### Data Fields

- [SrvStatusInfo](#) \* [pCDMASrvStatusInfo](#)
- [SrvStatusInfo](#) \* [pHDRSrvStatusInfo](#)
- [GSMSrvStatusInfo](#) \* [pGSMSrvStatusInfo](#)
- [GSMSrvStatusInfo](#) \* [pWCDMASrvStatusInfo](#)
- [GSMSrvStatusInfo](#) \* [pLTESrvStatusInfo](#)
- [CDMASysInfo](#) \* [pCDMASysInfo](#)
- [HDRSysInfo](#) \* [pHDRSysInfo](#)
- [GSMSysInfo](#) \* [pGSMSysInfo](#)
- [WCDMASysInfo](#) \* [pWCDMASysInfo](#)

- [LTESysInfo](#) \* [pLTESysInfo](#)
- [AddCDMASysInfo](#) \* [pAddCDMASysInfo](#)
- [WORD](#) \* [pAddHDRSysInfo](#)
- [AddSysInfo](#) \* [pAddGSMSysInfo](#)
- [AddSysInfo](#) \* [pAddWCDMASysInfo](#)
- [WORD](#) \* [pAddLTESysInfo](#)
- [CallBarringSysInfo](#) \* [pGSMCallBarringSysInfo](#)
- [CallBarringSysInfo](#) \* [pWCDMACallBarringSysInfo](#)
- [BYTE](#) \* [pLTEVoiceSupportSysInfo](#)
- [BYTE](#) \* [pGSMCipherDomainSysInfo](#)
- [BYTE](#) \* [pWCDMACipherDomainSysInfo](#)

### 8.424.1 Detailed Description

Structure for storing the SLQSNasGetSysInfo response parameters.

Parameters

<i>pCDMASrv-StatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SrvStatusInfo</a> for more information.</li> </ul>
<i>pHDRSrvStatus-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SrvStatusInfo</a> for more information.</li> </ul>
<i>pGSMSrvStatus-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pWCDMASrv-StatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pLTESrvStatus-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CDMASysInfo</a> for more information.</li> </ul>
<i>pHDRSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">HDRSysInfo</a> for more information.</li> </ul>
<i>pGSMSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSysInfo</a> for more information.</li> </ul>
<i>pWCDMASys-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">WCDMASysInfo</a> for more information.</li> </ul>
<i>pLTESysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">LTESysInfo</a> for more information.</li> </ul>
<i>pAddCDMASys-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddCDMASysInfo</a> for more information.</li> </ul>

<i>pAddHDRSys-Info</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>pAddGSMSys-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddSysInfo</a> for more information.</li> </ul>
<i>pAddWCDMA-SysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddSysInfo</a> for more information.</li> </ul>
<i>pAddLTESysInfo</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>pGSMCall-BarringSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CallBarringSysInfo</a> for more information.</li> </ul>
<i>pWCDMACall-BarringSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CallBarringSysInfo</a> for more information.</li> </ul>
<i>pLTEVoice-SupportSysInfo</i>	<ul style="list-style-type: none"> <li>• Indicates voice support status on LTE. <ul style="list-style-type: none"> <li>– 0x00 - Voice is not supported</li> <li>– 0x01 - Voice is supported</li> </ul> </li> </ul>
<i>pGSMCipher-DomainSysInfo</i>	<ul style="list-style-type: none"> <li>• Ciphering on the service domain. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> </ul> </li> </ul>
<i>pWCDMA-CipherDomain-SysInfo</i>	<ul style="list-style-type: none"> <li>• Ciphering on the service domain. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> </ul> </li> </ul>

## 8.424.2 Field Documentation

### 8.424.2.1 AddCDMASysInfo\* nasGetSysInfoResp::pAddCDMASysInfo

- 8.424.2.2 **AddSysInfo\*** nasGetSysInfoResp::pAddGSMSysInfo
- 8.424.2.3 **WORD\*** nasGetSysInfoResp::pAddHDRSysInfo
- 8.424.2.4 **WORD\*** nasGetSysInfoResp::pAddLTERSysInfo
- 8.424.2.5 **AddSysInfo\*** nasGetSysInfoResp::pAddWCDMASysInfo
- 8.424.2.6 **SrvStatusInfo\*** nasGetSysInfoResp::pCDMASrvStatusInfo
- 8.424.2.7 **CDMASysInfo\*** nasGetSysInfoResp::pCDMASysInfo
- 8.424.2.8 **CallBarringSysInfo\*** nasGetSysInfoResp::pGSMCallBarringSysInfo
- 8.424.2.9 **BYTE\*** nasGetSysInfoResp::pGSMCipherDomainSysInfo
- 8.424.2.10 **GSMSrvStatusInfo\*** nasGetSysInfoResp::pGSMSrvStatusInfo
- 8.424.2.11 **GSMSysInfo\*** nasGetSysInfoResp::pGSMSysInfo
- 8.424.2.12 **SrvStatusInfo\*** nasGetSysInfoResp::pHDRSrvStatusInfo
- 8.424.2.13 **HDRSysInfo\*** nasGetSysInfoResp::pHDRSysInfo
- 8.424.2.14 **GSMSrvStatusInfo\*** nasGetSysInfoResp::pLTESrvStatusInfo
- 8.424.2.15 **LTERSysInfo\*** nasGetSysInfoResp::pLTERSysInfo
- 8.424.2.16 **BYTE\*** nasGetSysInfoResp::pLTEVoiceSupportSysInfo
- 8.424.2.17 **CallBarringSysInfo\*** nasGetSysInfoResp::pWCDMACallBarringSysInfo
- 8.424.2.18 **BYTE\*** nasGetSysInfoResp::pWCDMACipherDomainSysInfo
- 8.424.2.19 **GSMSrvStatusInfo\*** nasGetSysInfoResp::pWCDMASrvStatusInfo
- 8.424.2.20 **WCDMASysInfo\*** nasGetSysInfoResp::pWCDMASysInfo

## 8.425 nasGetTxRxInfoReq Struct Reference

### Data Fields

- [BYTE radio\\_if](#)

### 8.425.1 Detailed Description

This structure contains the GetTxRxInfoReq request parameters

## Parameters

<i>radio_if</i>	[Mandatory] <ul style="list-style-type: none"> <li>Radio interface technology of the signal being measured</li> <li>Valid Values <ul style="list-style-type: none"> <li>0x01 - NAS_RADIO_IF_CDMA_1X - CDMA</li> <li>0x02 - NAS_RADIO_IF_CDMA_1XEVDO - HDR</li> <li>0x04 - NAS_RADIO_IF_GSM - GSM</li> <li>0x05 - NAS_RADIO_IF_UMTS - UMTS</li> <li>0x08 - NAS_RADIO_IF_LTE - LTE</li> </ul> </li> </ul>
-----------------	---

## 8.425.2 Field Documentation

8.425.2.1 BYTE nasGetTxRxInfoReq::radio\_if

## 8.426 nasGetTxRxInfoResp Struct Reference

## Data Fields

- [rxInfo](#) \* [pRXChain0Info](#)
- [rxInfo](#) \* [pRXChain1Info](#)
- [txInfo](#) \* [pTXInfo](#)

## 8.426.1 Detailed Description

This structure contains the GetTxRxInfoResp response parameters.

## Parameters

<i>pRXChain0Info</i>	[Optional] <ul style="list-style-type: none"> <li>See <a href="#">rxInfo</a> for more information.</li> </ul>
<i>pRXChain1Info</i>	[Optional] <ul style="list-style-type: none"> <li>See <a href="#">rxInfo</a> for more information.</li> </ul>
<i>pTXInfo</i>	[Optional] <ul style="list-style-type: none"> <li>See <a href="#">txInfo</a> for more information.</li> </ul>

## 8.426.2 Field Documentation

8.426.2.1 [rxInfo](#)\* nasGetTxRxInfoResp::pRXChain0Info8.426.2.2 [rxInfo](#)\* nasGetTxRxInfoResp::pRXChain1Info8.426.2.3 [txInfo](#)\* nasGetTxRxInfoResp::pTXInfo

## 8.427 NASGWAcqOrderPrefTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint32\_t [GWAcqOrderPref](#)

### 8.427.1 Field Documentation

8.427.1.1 uint32\_t NASGWAcqOrderPrefTlv::GWAcqOrderPref

8.427.1.2 uint8\_t NASGWAcqOrderPrefTlv::TlvPresent

## 8.428 nasIndicationRegisterReq Struct Reference

### Data Fields

- BYTE \* [pSystemSelectionInd](#)
- BYTE \* [pDDTMInd](#)
- BYTE \* [pServingSystemInd](#)
- BYTE \* [pDualStandByPrefInd](#)
- BYTE \* [pSubscriptionInfoInd](#)
- BYTE \* [pNetworkTimeInd](#)
- BYTE \* [pSysInfoInd](#)
- BYTE \* [pSignalStrengthInd](#)
- BYTE \* [pErrorRateInd](#)
- BYTE \* [pHDRNewUATIAssInd](#)
- BYTE \* [pHDRSessionCloseInd](#)
- BYTE \* [pManagedRoamingInd](#)
- BYTE \* [pLTECphyCa](#)

### 8.428.1 Detailed Description

This structure contains the SLQSNasIndicationRegisterExt request parameters.

#### Parameters

<i>pSystem-SelectionInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>• System Selection Preference indication registration. The following callbacks would not be invoked if the indication is disabled.  <a href="#">tFNRoamingIndicator</a> <a href="#">tFNDataCapabilities</a> and <a href="#">tFNServingSystem</a> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
-----------------------------	---



<i>pDDTMInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>DDTM (Data Dedicated Transmission Mode) indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p>tFNDDTM</p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pServing-SystemInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Serving System indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNBandPreference</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pDualStandBy-PrefInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Dual Standby Preference indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p>tFNDualStandByPref</p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pSubscription-InfoInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Subscription Information indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p>tFNSubscriptionInfo</p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pNetworkTime-Ind</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Network Time indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNNetworkTime</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>

<i>pSysInfoInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>System Information indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNSysInfo</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pSignalStrengthInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Signal Strength indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNSigInfo</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pErrorRateInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Error Rate indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNErrRate</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pHDRNewUATI-AssInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>HDR New UATI Assigned indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNHDRUATIUpdate</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pHDRSession-CloseInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>HDR Session Closed indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNHDRSessionClose</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>

<i>pManaged-RoamingInd</i>	[Optional] <ul style="list-style-type: none"> <li>Managed Roaming indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> tFNManagedRoaming <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
----------------------------	---

**Note**

Atleast one parameter must be provided as request. 'NULL' value confirms that the indication value is not sent.

**8.428.2 Field Documentation**

- 8.428.2.1 **BYTE\*** nasIndicationRegisterReq::pDDTMInd
- 8.428.2.2 **BYTE\*** nasIndicationRegisterReq::pDualStandByPrefInd
- 8.428.2.3 **BYTE\*** nasIndicationRegisterReq::pErrorRateInd
- 8.428.2.4 **BYTE\*** nasIndicationRegisterReq::pHDRNewUATIAssInd
- 8.428.2.5 **BYTE\*** nasIndicationRegisterReq::pHDRSessionCloseInd
- 8.428.2.6 **BYTE\*** nasIndicationRegisterReq::pLTECphyCa
- 8.428.2.7 **BYTE\*** nasIndicationRegisterReq::pManagedRoamingInd
- 8.428.2.8 **BYTE\*** nasIndicationRegisterReq::pNetworkTimeInd
- 8.428.2.9 **BYTE\*** nasIndicationRegisterReq::pServingSystemInd
- 8.428.2.10 **BYTE\*** nasIndicationRegisterReq::pSignalStrengthInd
- 8.428.2.11 **BYTE\*** nasIndicationRegisterReq::pSubscriptionInfoInd
- 8.428.2.12 **BYTE\*** nasIndicationRegisterReq::pSysInfoInd
- 8.428.2.13 **BYTE\*** nasIndicationRegisterReq::pSystemSelectionInd

**8.429 nasInitNetworkReg Struct Reference****Data Fields**

- [ULONG](#) regAction
- [MNRInfo](#) \* pMNRInfo
- [ULONG](#) \* pChangeDuration
- [BOOL](#) \* pMncPcsDigitStatus

**8.429.1 Detailed Description**

This structure contains Initiate Network Registration request parameters

## Parameters

<i>regAction</i>	<ul style="list-style-type: none"> <li>Specifies one of the following register actions : <ul style="list-style-type: none"> <li>AUTO_REGISTER - Device registers according to its provisioning and optional parameters supplied with the command are ignored.</li> <li>MANUAL_REGISTER - Device registers to a specified network and the optional Manual Network Register Information parameter pMNRInfo must also be included for the command to process successfully and supported only for 3GPP.</li> </ul> </li> </ul>
<i>pMNRInfo</i>	[Optional] <ul style="list-style-type: none"> <li>Pointer to structure <a href="#">MNRInfo</a> <ul style="list-style-type: none"> <li>See <a href="#">MNRInfo</a> for more information</li> </ul> </li> </ul>
<i>pChange-Duration</i>	[Optional] <ul style="list-style-type: none"> <li>Duration of the change. <ul style="list-style-type: none"> <li>0x00 - Power cycle - Remains active until the next device power cycle</li> <li>0x01 - Permanent - Remains active through power cycles until changed by the client</li> </ul> </li> </ul>
<i>pMncPcsDigit-Status</i>	[Optional] <ul style="list-style-type: none"> <li>MNC PCS Digit Include Status <ul style="list-style-type: none"> <li>True - MNC is a 3-digit value.</li> <li>False - MNC is a 2-digit value.</li> </ul> </li> </ul>

## 8.429.2 Field Documentation

8.429.2.1 ULONG\* nasInitNetworkReg::pChangeDuration

8.429.2.2 BOOL\* nasInitNetworkReg::pMncPcsDigitStatus

8.429.2.3 MNRInfo\* nasInitNetworkReg::pMNRInfo

8.429.2.4 ULONG nasInitNetworkReg::regAction

## 8.430 NASLTEBandPreferenceTlv Struct Reference

## Data Fields

- uint8\_t [TlvPresent](#)
- uint64\_t [LTEBandPref](#)

## 8.430.1 Field Documentation

8.430.1.1 uint64\_t NASLTEBandPreferenceTlv::LTEBandPref

8.430.1.2 uint8\_t NASLTEBandPreferenceTlv::TlvPresent

## 8.431 NASLteNasReleaseInfoTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint8\_t [nas\\_release](#)
- uint8\_t [nas\\_major](#)
- uint8\_t [nas\\_minor](#)

### 8.431.1 Field Documentation

8.431.1.1 uint8\_t NASLteNasReleaseInfoTlv::nas\_major

8.431.1.2 uint8\_t NASLteNasReleaseInfoTlv::nas\_minor

8.431.1.3 uint8\_t NASLteNasReleaseInfoTlv::nas\_release

8.431.1.4 uint8\_t NASLteNasReleaseInfoTlv::TlvPresent

## 8.432 NASModePreferenceTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint16\_t [ModePref](#)

### 8.432.1 Field Documentation

8.432.1.1 uint16\_t NASModePreferenceTlv::ModePref

8.432.1.2 uint8\_t NASModePreferenceTlv::TlvPresent

## 8.433 NASNetSelPreferenceTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint8\_t [NetSelPref](#)

### 8.433.1 Field Documentation

8.433.1.1 uint8\_t NASNetSelPreferenceTlv::NetSelPref

8.433.1.2 uint8\_t NASNetSelPreferenceTlv::TlvPresent

## 8.434 nasNetworkTime Struct Reference

### Data Fields

- [UniversalTime](#) universalTime
- [BYTE](#) \* pTimeZone

- [BYTE](#) \* [pDayltSavAdj](#)
- [BYTE](#) \* [pRadiolInterface](#)

### 8.434.1 Detailed Description

Structure for storing the [nasSysInfo](#) indication parameters.

Parameters

<i>universalTime</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UniversalTime</a> for more information.</li> </ul>
<i>pTimeZone</i>	<ul style="list-style-type: none"> <li>• Time Zone.</li> <li>• Offset from Universal time, i.e., the difference between local time and Universal time, in increments of 15 min (signed value).</li> </ul>
<i>pDayltSavAdj</i>	<ul style="list-style-type: none"> <li>• Daylight Saving Adjustment.</li> <li>• Daylight saving adjustment in hr. <ul style="list-style-type: none"> <li>– Possible values: 0, 1, and 2.</li> </ul> </li> </ul>
<i>pRadiolInterface</i>	<ul style="list-style-type: none"> <li>• Radio interface from which the information comes</li> <li>• Values <ul style="list-style-type: none"> <li>– 0x01 - NAS_RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - NAS_RADIO_IF_CDMA_1xEVDO - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x04 - NAS_RADIO_IF_GSM - GSM</li> <li>– 0x05 - NAS_RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - NAS_RADIO_IF_LTE - LTE</li> <li>– 0x09 - NAS_RADIO_IF_TDSCDMA - TD-SCDMA</li> </ul> </li> </ul>

### 8.434.2 Field Documentation

8.434.2.1 [BYTE](#)\* [nasNetworkTime::pDayltSavAdj](#)

8.434.2.2 [BYTE](#)\* [nasNetworkTime::pRadiolInterface](#)

8.434.2.3 [BYTE](#)\* [nasNetworkTime::pTimeZone](#)

8.434.2.4 [UniversalTime](#) [nasNetworkTime::universalTime](#)

## 8.435 nasOperatorNameResp Struct Reference

Data Fields

- [serviceProviderName](#) \* [pSrcProviderName](#)

- [operatorPLMNList](#) \* [pOperatorPLMNList](#)
- [PLMNNetworkName](#) \* [pPLMNNetworkName](#)
- [operatorNameString](#) \* [pOperatorNameString](#)
- [PLMNNetworkNameData](#) \* [pNITZInformation](#)

### 8.435.1 Detailed Description

This structure contains Operator Name Data related from multiple sources.

#### Parameters

<i>pSvcProvider-Name</i>	<ul style="list-style-type: none"> <li>• Refer <a href="#">serviceProviderName</a> for details (Optional).</li> <li>• Can provide NULL if this parameter is not required.</li> </ul>
<i>pOperatorPLM-List</i>	<ul style="list-style-type: none"> <li>• Refer <a href="#">operatorPLMNList</a> for details (Optional).</li> <li>• Can provide NULL if this parameter is not required.</li> </ul>
<i>pPLMNNetwork-Name</i>	<ul style="list-style-type: none"> <li>• Refer <a href="#">PLMNNetworkName</a> for details (Optional).</li> <li>• Can provide NULL if this parameter is not required.</li> </ul>
<i>pOperatorName-String</i>	<ul style="list-style-type: none"> <li>• Refer <a href="#">operatorNameString</a> for details (Optional).</li> <li>• Can provide NULL if this parameter is not required.</li> </ul>
<i>pNITZ-Information</i>	<ul style="list-style-type: none"> <li>• Refer <a href="#">PLMNNetworkNameData</a> for details (Optional).</li> <li>• Can provide NULL if this parameter is not required.</li> </ul>

### 8.435.2 Field Documentation

8.435.2.1 [PLMNNetworkNameData](#)\* [nasOperatorNameResp::pNITZInformation](#)

8.435.2.2 [operatorNameString](#)\* [nasOperatorNameResp::pOperatorNameString](#)

8.435.2.3 [operatorPLMNList](#)\* [nasOperatorNameResp::pOperatorPLMNList](#)

8.435.2.4 [PLMNNetworkName](#)\* [nasOperatorNameResp::pPLMNNetworkName](#)

8.435.2.5 [serviceProviderName](#)\* [nasOperatorNameResp::pSvcProviderName](#)

## 8.436 NASOTAMessageTlv Struct Reference

### Data Fields

- [uint8\\_t](#) [TlvPresent](#)
- [uint32\\_t](#) [message\\_type](#)

- uint16\_t [data\\_len](#)
- uint8\_t [data\\_buf](#) [2048]

### 8.436.1 Field Documentation

8.436.1.1 uint8\_t NASOTAMessageTlv::data\_buf[2048]

8.436.1.2 uint16\_t NASOTAMessageTlv::data\_len

8.436.1.3 uint32\_t NASOTAMessageTlv::message\_type

8.436.1.4 uint8\_t NASOTAMessageTlv::TlvPresent

## 8.437 NASPhyCaAggPcellInfo Struct Reference

### Data Fields

- uint32\_t [pci](#)
- uint32\_t [freq](#)
- [LIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB](#) dl\_bw\_value
- uint32\_t [iLTEbandValue](#)
- uint8\_t [TlvPresent](#)

### 8.437.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation of Pcell Information.

#### Parameters

<i>pci</i>	<ul style="list-style-type: none"> <li>• Physical cell ID of the SCell Range.</li> <li>• Range for ID values: 0 to 503.</li> </ul>
<i>freq</i>	<ul style="list-style-type: none"> <li>• Frequency of the absolute cell Range.</li> <li>• Range for ID values: 0 to 65535.</li> </ul>
<i>dl_bw_value</i>	<ul style="list-style-type: none"> <li>• Downlink Bandwidth Values.</li> <li>• See <a href="#">NAS_LTE_CPHY_CA_BW_NRB</a> for more information.</li> </ul>
<i>scell_state</i>	<ul style="list-style-type: none"> <li>• Scell state Values.</li> <li>• See <a href="#">NAS_LTE_CPHY_SCELL_STATE</a> for more information.</li> </ul>



<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Tlv Present.</li> </ul>
-------------------	--

### 8.437.2 Field Documentation

8.437.2.1 `LIBPACK_NAS_LTE_CPHY_CA_BW_NRB` NASPhyCaAggPcellInfo::dl\_bw\_value

8.437.2.2 `uint32_t` NASPhyCaAggPcellInfo::freq

8.437.2.3 `uint32_t` NASPhyCaAggPcellInfo::iLTEbandValue

8.437.2.4 `uint32_t` NASPhyCaAggPcellInfo::pci

8.437.2.5 `uint8_t` NASPhyCaAggPcellInfo::TlvPresent

## 8.438 NASPhyCaAggScellIDIBw Struct Reference

### Data Fields

- [LIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB](#) dl\_bw\_value
- `uint8_t` [TlvPresent](#)

### 8.438.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation Downlink Bandwidth of Scell.

#### Parameters

<i>dl_bw_value</i>	<ul style="list-style-type: none"> <li>• Downlink Bandwidth Values.</li> <li>• See <a href="#">NAS_LTE_CPHY_CA_BW_NRB</a> for more information.</li> </ul>
--------------------	--

### 8.438.2 Field Documentation

8.438.2.1 `LIBPACK_NAS_LTE_CPHY_CA_BW_NRB` NASPhyCaAggScellIDIBw::dl\_bw\_value

8.438.2.2 `uint8_t` NASPhyCaAggScellIDIBw::TlvPresent

## 8.439 NASPhyCaAggScellIndex Struct Reference

### Data Fields

- `uint8_t` [scell\\_idx](#)
- `uint8_t` [TlvPresent](#)

### 8.439.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation of Scell Index.

## Parameters

<i>scell_idx</i>	<ul style="list-style-type: none"> <li>Physical cell ID of the SCell Range.</li> <li>Range for ID values: 0 to 503.</li> </ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>Tlv Present.</li> </ul>

## 8.439.2 Field Documentation

8.439.2.1 uint8\_t NASPhyCaAggScellIndex::scell\_idx

8.439.2.2 uint8\_t NASPhyCaAggScellIndex::TlvPresent

## 8.440 NASPhyCaAggScellIndType Struct Reference

## Data Fields

- uint32\_t [pci](#)
- uint32\_t [freq](#)
- [LIBPACK\\_NAS\\_LTE\\_CPHY\\_SCELL\\_STATE](#) [scell\\_state](#)
- uint8\_t [TlvPresent](#)

## 8.440.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation of Scell Indicator Type.

## Parameters

<i>pci</i>	<ul style="list-style-type: none"> <li>Physical cell ID of the SCell Range.</li> <li>Range for ID values: 0 to 503.</li> </ul>
<i>freq</i>	<ul style="list-style-type: none"> <li>Frequency of the absolute cell Range.</li> <li>Range for ID values: 0 to 65535.</li> </ul>
<i>scell_state</i>	<ul style="list-style-type: none"> <li>Scell state Values.</li> <li>See <a href="#">NAS_LTE_CPHY_SCELL_STATE</a> for more information.</li> </ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>Tlv Present.</li> </ul>

## 8.440.2 Field Documentation

8.440.2.1 uint32\_t NASPhyCaAggScellIndType::freq

8.440.2.2 `uint32_t NASPhyCaAggScellIndType::pci`

8.440.2.3 `LIBPACK_NAS_LTE_CPHY_SCELL_STATE NASPhyCaAggScellIndType::scell_state`

8.440.2.4 `uint8_t NASPhyCaAggScellIndType::TlvPresent`

## 8.441 NASPhyCaAggScellInfo Struct Reference

### Data Fields

- `uint32_t pci`
- `uint32_t freq`
- `LIBPACK_NAS_LTE_CPHY_CA_BW_NRB dl_bw_value`
- `uint32_t iLTEbandValue`
- `LIBPACK_NAS_LTE_CPHY_SCELL_STATE scell_state`
- `uint8_t TlvPresent`

### 8.441.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation of Scell Information.

#### Parameters

<i>pci</i>	<ul style="list-style-type: none"> <li>• Physical cell ID of the SCell Range.</li> <li>• Range for ID values: 0 to 503.</li> </ul>
<i>freq</i>	<ul style="list-style-type: none"> <li>• Frequency of the absolute cell Range.</li> <li>• Range for ID values: 0 to 65535.</li> </ul>
<i>dl_bw_value</i>	<ul style="list-style-type: none"> <li>• Downlink Bandwidth Values.</li> <li>• See <a href="#">NAS_LTE_CPHY_CA_BW_NRB</a> for more information.</li> </ul>
<i>iLTEbandValue</i>	<ul style="list-style-type: none"> <li>• Band value.</li> <li>• Range for LTE Band class 120 to 160.</li> </ul>
<i>scell_state</i>	<ul style="list-style-type: none"> <li>• Scell state Values.</li> <li>• See <a href="#">NAS_LTE_CPHY_SCELL_STATE</a> for more information.</li> </ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Tlv Present.</li> </ul>

### 8.441.2 Field Documentation

8.441.2.1 LIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB NASPhyCaAggScellInfo::dl\_bw\_value

8.441.2.2 uint32\_t NASPhyCaAggScellInfo::freq

8.441.2.3 uint32\_t NASPhyCaAggScellInfo::lTEbandValue

8.441.2.4 uint32\_t NASPhyCaAggScellInfo::pci

8.441.2.5 LIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE NASPhyCaAggScellInfo::scell\_state

8.441.2.6 uint8\_t NASPhyCaAggScellInfo::TlvPresent

## 8.442 nasPLMNNameReq Struct Reference

### Data Fields

- WORD mcc
- WORD mnc
- BYTE \* pMncPcsStatus

### 8.442.1 Detailed Description

Structure for storing the PLMN Name request parameters

#### Parameters

<i>mcc</i>	<ul style="list-style-type: none"> <li>• A 16-bit integer representation of MCC. Range: 0 to 999</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>• A 16-bit integer representation of MNC. Range: 0 to 999</li> </ul>
<i>pMncPcsStatus</i>	<ul style="list-style-type: none"> <li>• MNC PCS Digit Include Status</li> <li>• Used to interpret the length of the corresponding MNC reported in the PLMN TLV(0x01).</li> <li>• Values             <ul style="list-style-type: none"> <li>– TRUE - MNC is a three-digit value. e.g. a reported value of 90 corresponds to an MNC value of 090</li> <li>– FALSE - MNC is a two-digit value. e.g. a reported value of 90 corresponds to an MNC value of 90</li> </ul> </li> </ul>

#### Note

If pMncPcsStatus is not present, an MNC smaller than 100 is assumed to be a two-digit value, and an MNC greater than or equal to 100 is assumed to be a three digit value.

### 8.442.2 Field Documentation

8.442.2.1 WORD nasPLMNNameReq::mcc

8.442.2.2 WORD nasPLMNNameReq::mnc

8.442.2.3 BYTE\* nasPLMNNameReq::pMncPcsStatus

## 8.443 nasPLMNNameResp Struct Reference

### Data Fields

- BYTE spnEncoding
- BYTE spnLength
- BYTE spn [255]
- BYTE shortNameEn
- BYTE shortNameCI
- BYTE shortNameSB
- BYTE shortNameLen
- BYTE shortName [255]
- BYTE longNameEn
- BYTE longNameCI
- BYTE longNameSB
- BYTE longNameLen
- BYTE longName [255]

### 8.443.1 Detailed Description

Structure for storing the PLMN Name response parameters

#### Parameters

<i>spnEncoding</i>	<ul style="list-style-type: none"><li>• Coding scheme used for service provider name. This value is ignored if spn_len is zero Values:<ul style="list-style-type: none"><li>– 0x00 - SMS default 7-bit coded alphabet as defined in 3GPP TS 23.038 with bit 8 set to 0</li><li>– 0x01 - UCS2 (16 bit, little-endian) 3GPP TS 23.038</li></ul></li></ul>
<i>spnLength</i>	<ul style="list-style-type: none"><li>• Length of SPN which follows</li></ul>
<i>spn</i>	<ul style="list-style-type: none"><li>• Service Provider name string</li></ul>
<i>shortNameEn</i>	<ul style="list-style-type: none"><li>• Coding scheme used for PLMN short name. This value is ignored if PLMN short name length is zero Values:<ul style="list-style-type: none"><li>– 0x00 - SMS default 7-bit coded alphabet as defined in 3GPP TS 23.038 with bit 8 set to 0</li><li>– 0x01 - UCS2 (16 bit, little-endian) 3GPP TS 23.038</li></ul></li></ul>

<i>shortNameCI</i>	<ul style="list-style-type: none"> <li>Indicates whether the country initials are to be added to the shortName. This value is ignored if shortNameLen is zero. Values: <ul style="list-style-type: none"> <li>0x00 - Do not add the letters for the countrys initials to the name</li> <li>0x01 - Add the countrys initials and a text string to the name</li> <li>0xFF - Not specified</li> </ul> </li> </ul>
<i>shortNameSB</i>	<ul style="list-style-type: none"> <li>PLMN short name spare bits. This value is ignored if shortNameLen is zero. Values: <ul style="list-style-type: none"> <li>0x01 - Bit 8 is spare and set to 0 in octet</li> <li>0x02 - Bits 7 and 8 are spare and set to 0 in octet n</li> <li>0x03 - Bits 6 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>0x04 - Bits 5 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>0x05 - Bits 4 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>0x06 - Bits 3 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>0x07 - Bits 2 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>0x00 - Carries no information about the number of spare bits in octet n</li> </ul> </li> </ul>
<i>shortNameLen</i>	<ul style="list-style-type: none"> <li>Length of shortName which follows</li> </ul>
<i>shortName</i>	<ul style="list-style-type: none"> <li>PLMN short name</li> </ul>
<i>longNameEn</i>	<ul style="list-style-type: none"> <li>Coding scheme used for PLMN long name. This value is ignored if PLMN long name length is zero Values: <ul style="list-style-type: none"> <li>0x00 - SMS default 7-bit coded alphabet as defined in 3GPP TS 23.038 with bit 8 set to 0</li> <li>0x01 - UCS2 (16 bit, little-endian) 3GPP TS 23.038</li> </ul> </li> </ul>
<i>longNameCI</i>	<ul style="list-style-type: none"> <li>Indicates whether the country initials are to be added to the longName. This value is ignored if longNameLen is zero. Values: <ul style="list-style-type: none"> <li>0x00 - Do not add the letters for the countrys initials to the name</li> <li>0x01 - Add the countrys initials and a text string to the name</li> <li>0xFF - Not specified</li> </ul> </li> </ul>

<i>longNameSB</i>	<ul style="list-style-type: none"> <li>• PLMN long name spare bits. This value is ignored if longNameLen is zero. Values: <ul style="list-style-type: none"> <li>– 0x01 - Bit 8 is spare and set to 0 in octet</li> <li>– 0x02 - Bits 7 and 8 are spare and set to 0 in octet n</li> <li>– 0x03 - Bits 6 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>– 0x04 - Bits 5 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>– 0x05 - Bits 4 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>– 0x06 - Bits 3 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>– 0x07 - Bits 2 to 8 (inclusive) are spare and set to 0 in octet n</li> <li>– 0x00 - Carries no information about the number of spare bits in octet n</li> </ul> </li> </ul>
<i>longNameLen</i>	<ul style="list-style-type: none"> <li>• Length of longName which follows</li> </ul>
<i>longName</i>	<ul style="list-style-type: none"> <li>• PLMN long name</li> </ul>

**Note**

None

**8.443.2 Field Documentation**8.443.2.1 **BYTE** nasPLMNNameResp::longName[255]8.443.2.2 **BYTE** nasPLMNNameResp::longNameCI8.443.2.3 **BYTE** nasPLMNNameResp::longNameEn8.443.2.4 **BYTE** nasPLMNNameResp::longNameLen8.443.2.5 **BYTE** nasPLMNNameResp::longNameSB8.443.2.6 **BYTE** nasPLMNNameResp::shortName[255]8.443.2.7 **BYTE** nasPLMNNameResp::shortNameCI8.443.2.8 **BYTE** nasPLMNNameResp::shortNameEn8.443.2.9 **BYTE** nasPLMNNameResp::shortNameLen8.443.2.10 **BYTE** nasPLMNNameResp::shortNameSB8.443.2.11 **BYTE** nasPLMNNameResp::spn[255]8.443.2.12 **BYTE** nasPLMNNameResp::spnEncoding8.443.2.13 **BYTE** nasPLMNNameResp::spnLength

## 8.444 NASPRLPreferenceTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint16\_t [PRLPref](#)

### 8.444.1 Field Documentation

8.444.1.1 uint16\_t NASPRLPreferenceTlv::PRLPref

8.444.1.2 uint8\_t NASPRLPreferenceTlv::TlvPresent

## 8.445 NASQmiCbkJnasSwtOTAMessageInd Struct Reference

### Data Fields

- [NASOTAMessageTlv](#) otaMsgTlv
- [NASLteNasReleaseInfoTlv](#) nasRelInfoTlv
- [NASTimeInfoTlv](#) timeTlv

### 8.445.1 Field Documentation

8.445.1.1 [NASLteNasReleaseInfoTlv](#) NASQmiCbkJnasSwtOTAMessageInd::nasRelInfoTlv

8.445.1.2 [NASOTAMessageTlv](#) NASQmiCbkJnasSwtOTAMessageInd::otaMsgTlv

8.445.1.3 [NASTimeInfoTlv](#) NASQmiCbkJnasSwtOTAMessageInd::timeTlv

## 8.446 NASQmiCbkJnasSystemSelPrefInd Struct Reference

### Data Fields

- [NASEmergencyModeTlv](#) EMTlv
- [NASModePreferenceTlv](#) MPTlv
- [NASBandPreferenceTlv](#) BPTlv
- [NASPRLPreferenceTlv](#) PRLPTlv
- [NASRoamPreferenceTlv](#) RPTlv
- [NASLTEBandPreferenceTlv](#) LBPTlv
- [NASNetSelPreferenceTlv](#) NSPTlv
- [NASServDomainPrefTlv](#) SDPTlv
- [NASGWAcqOrderPrefTlv](#) GWAOPTlv

### 8.446.1 Field Documentation

8.446.1.1 [NASBandPreferenceTlv](#) NASQmiCbkJnasSystemSelPrefInd::BPTlv

8.446.1.2 [NASEmergencyModeTlv](#) NASQmiCbkJnasSystemSelPrefInd::EMTlv

8.446.1.3 [NASGWAcqOrderPrefTlv](#) NASQmiCbkJnasSystemSelPrefInd::GWAOPTlv



- 8.446.1.4 **NASLTEBandPreferenceTlv** NASQmiCbkNasSystemSelPrefInd::LBPTlv
- 8.446.1.5 **NASModePreferenceTlv** NASQmiCbkNasSystemSelPrefInd::MPTlv
- 8.446.1.6 **NASNetSelPreferenceTlv** NASQmiCbkNasSystemSelPrefInd::NSPTlv
- 8.446.1.7 **NASPRLPreferenceTlv** NASQmiCbkNasSystemSelPrefInd::PRLPTlv
- 8.446.1.8 **NASRoamPreferenceTlv** NASQmiCbkNasSystemSelPrefInd::RPTlv
- 8.446.1.9 **NASServDomainPrefTlv** NASQmiCbkNasSystemSelPrefInd::SDPTlv

## 8.447 NASRoamPreferenceTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint16\_t [RoamPref](#)

### 8.447.1 Field Documentation

- 8.447.1.1 uint16\_t NASRoamPreferenceTlv::RoamPref
- 8.447.1.2 uint8\_t NASRoamPreferenceTlv::TlvPresent

## 8.448 NASServDomainPrefTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint32\_t [SrvDomainPref](#)

### 8.448.1 Field Documentation

- 8.448.1.1 uint32\_t NASServDomainPrefTlv::SrvDomainPref
- 8.448.1.2 uint8\_t NASServDomainPrefTlv::TlvPresent

## 8.449 NASServingSystemInfo Struct Reference

### Data Fields

- uint8\_t [registrationState](#)
- uint8\_t [csAttachState](#)
- uint8\_t [psAttachState](#)
- uint8\_t [selectedNetwork](#)
- uint8\_t [radioInterfaceNo](#)
- uint8\_t [radioInterfaceList](#) [255]
- uint8\_t [hdrPersonality](#)

### 8.449.1 Detailed Description

This structure will hold the serving system parameters information

## Parameters

<i>registrationState</i>	- Registration state of the mobile <ul style="list-style-type: none"> <li>• 0 - QMI_NAS_NOT_REGISTERED Not registered;mobile is not currently searching for a new network to provide service</li> <li>• 1 - QMI_NAS_REGISTERED Registered with a network</li> <li>• 2 - QMI_NAS_NOT_REGISTERED_SEARCHING Not registered, but mobile is currently searching for a new network to provide service</li> <li>• 3 - QMI_NAS_REGISTRATION_DENIED Registration denied by the visible network</li> <li>• 4 - QMI_NAS_REGISTRATION_UNKNOWN Registration state is unknown</li> </ul>
<i>csAttachState</i>	- Circuit Switch domain attach state of the mobile <ul style="list-style-type: none"> <li>• 0 - Unknown or not applicable</li> <li>• 1 - Attached</li> <li>• 2 - Detached</li> </ul>
<i>psAttachState</i>	- Packet domain attach state of the mobile <ul style="list-style-type: none"> <li>• 0 - Unknown or not applicable</li> <li>• 1 - Attached</li> <li>• 2 - Detached</li> </ul>
<i>selectedNetwork</i>	- Type of selected radio access network <ul style="list-style-type: none"> <li>• 0x00 - Unknown</li> <li>• 0x01 - 3GPP2 network</li> <li>• 0x02 - 3GPP network</li> </ul>
<i>radioInterfaceNo</i>	- Number of radio interfaces currently in use; this indicates how many radio_if identifiers follow this field
<i>radioInterface-List</i>	- Radio interface currently in use (each is 1 byte) <ul style="list-style-type: none"> <li>• 0x00 - None (no service)</li> <li>• 0x01 - cdma2000 1X</li> <li>• 0x02 - cdma2000 HRPD (1xEV-DO)</li> <li>• 0x03 - AMPS</li> <li>• 0x04 - GSM</li> <li>• 0x05 - UMTS</li> <li>• 0x08 - LTE</li> </ul>

<i>hdrPersonality</i>	- HDR personality information (valid only for EVDO) <ul style="list-style-type: none"> <li>• 0x00 - Unknown</li> <li>• 0x01 - HRPD</li> <li>• 0x02 - eHRPD</li> </ul>
-----------------------	---

Note: None

## 8.449.2 Field Documentation

8.449.2.1 uint8\_t NAServingSystemInfo::csAttachState

8.449.2.2 uint8\_t NAServingSystemInfo::hdrPersonality

8.449.2.3 uint8\_t NAServingSystemInfo::psAttachState

8.449.2.4 uint8\_t NAServingSystemInfo::radioInterfaceList[255]

8.449.2.5 uint8\_t NAServingSystemInfo::radioInterfaceNo

8.449.2.6 uint8\_t NAServingSystemInfo::registrationState

8.449.2.7 uint8\_t NAServingSystemInfo::selectedNetwork

## 8.450 nasSigInfo Struct Reference

### Data Fields

- [CDMASSInfo](#) \* [pCDMASigInfo](#)
- [HDRSSInfo](#) \* [pHDRSigInfo](#)
- [INT8](#) \* [pGSMSigInfo](#)
- [CDMASSInfo](#) \* [pWCDMASigInfo](#)
- [LTESSInfo](#) \* [pLTESigInfo](#)
- [INT8](#) \* [pRscp](#)
- [TDSCDMAInfoExt](#) \* [pTDSCMASigInfoExt](#)

### 8.450.1 Detailed Description

Structure for storing the [nasSigInfo](#) indication parameters.

## Parameters

<i>pCDMASigInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">CDMASSInfo</a> for more information.</li> </ul>
<i>pHDRSigInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">HDRSSInfo</a> for more information.</li> </ul>
<i>pGSMSigInfo</i>	<ul style="list-style-type: none"> <li>one byte value, GSM signal strength is the RSSI in dBm (signed value). A value of -125 dBm or lower is used to indicate No Signal</li> </ul>
<i>pWCDMASigInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">CDMASSInfo</a> for more information.</li> </ul>
<i>pLTESigInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">LTESSInfo</a> for more information.</li> </ul>
<i>pRscp</i>	<ul style="list-style-type: none"> <li>RSCP of the Primary Common Control Physical Channel (PCCPCH) in dBm. Measurement range: -120 dBm to -25 dBm.</li> </ul>
<i>pTDSCDMASig-InfoExt</i>	<ul style="list-style-type: none"> <li>See <a href="#">TDSCDMASigInfoExt</a> for more information.</li> </ul>

## 8.450.2 Field Documentation

8.450.2.1 CDMASSInfo\* nasSigInfo::pCDMASigInfo

8.450.2.2 INT8\* nasSigInfo::pGSMSigInfo

8.450.2.3 HDRSSInfo\* nasSigInfo::pHDRSigInfo

8.450.2.4 LTESSInfo\* nasSigInfo::pLTESigInfo

8.450.2.5 INT8\* nasSigInfo::pRscp

8.450.2.6 TDSCDMASigInfoExt\* nasSigInfo::pTDSCDMASigInfoExt

8.450.2.7 CDMASSInfo\* nasSigInfo::pWCDMASigInfo

## 8.451 nasSwtGetChannelLockResp Struct Reference

## Data Fields

- [wcdmaUARFCN](#) \* [pWcdmaUARFCN](#)
- [lteEARFCN](#) \* [pLteEARFCN](#)
- [ltePCI](#) \* [pLtePCI](#)

### 8.451.1 Detailed Description

This structure contains the SLQSNASSwiGetChannelLock response parameters.

## Parameters

<i>pWcdmaUARFCN</i>	[Optional] • See <a href="#">wcdmaUARFCN</a> for more information
<i>pLteEARFCN</i>	[Optional] • See <a href="#">lteEARFCN</a> for more information
<i>pLtePCI</i>	[Optional] • See <a href="#">ltePCI</a> for more information

## 8.451.2 Field Documentation

8.451.2.1 [lteEARFCN](#)\* nasSwiGetChannelLockResp::pLteEARFCN8.451.2.2 [ltePCI](#)\* nasSwiGetChannelLockResp::pLtePCI8.451.2.3 [wcdmaUARFCN](#)\* nasSwiGetChannelLockResp::pWcdmaUARFCN

## 8.452 NasSwiIndReg Struct Reference

## Data Fields

- [BYTE lteEsmUI](#)
- [BYTE lteEsmDI](#)
- [BYTE lteEmmUI](#)
- [BYTE lteEmmDI](#)
- [BYTE gsmUmtsUI](#)
- [BYTE gsmUmtsDI](#)
- [BYTE \\* pRankIndicatorInd](#)

## 8.452.1 Detailed Description

This structure contains the OTA message indication.

## Parameters

<i>lteEsmUI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report LTE ESM uplink messages</li> </ul>
<i>lteEsmDI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report LTE ESM downlink messages</li> </ul>
<i>lteEmmUI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report LTE EMM uplink messages</li> </ul>
<i>lteEmmDI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report GSM/UMTS uplink messages</li> </ul>
<i>gsmUmtsUI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report GSM/UMTS uplink messages</li> </ul>
<i>gsmUmtsDI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report GSM/UMTS downlink messages</li> </ul>
<i>pRankIndicator-Ind</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report Rank Indicator messages</li> </ul>

## 8.452.2 Field Documentation

8.452.2.1 BYTE NasSwiIndReg::gsmUmtsDI

8.452.2.2 BYTE NasSwiIndReg::gsmUmtsUI

8.452.2.3 BYTE NasSwiIndReg::lteEmmDI

8.452.2.4 BYTE NasSwiIndReg::lteEmmUI

8.452.2.5 BYTE NasSwiIndReg::lteEsmDI

8.452.2.6 BYTE NasSwiIndReg::lteEsmUI

8.452.2.7 BYTE\* NasSwiIndReg::pRankIndicatorInd

## 8.453 nasSwiSetChannelLockReq Struct Reference



## Data Fields

- [wcdmaUARFCN](#) \* [pWcdmaUARFCN](#)
- [lteEARFCN](#) \* [pLteEARFCN](#)
- [ltePCI](#) \* [pLtePCI](#)

### 8.453.1 Detailed Description

This structure contains the SLQSNASSwiSetChannelLock response parameters.

#### Parameters

<i>pWcdmaUARFCN</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">wcdmaUARFCN</a> for more information</li> </ul>
<i>pLteEARFCN</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">lteEARFCN</a> for more information</li> </ul>
<i>pLtePCI</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">ltePCI</a> for more information</li> </ul>

### 8.453.2 Field Documentation

8.453.2.1 [lteEARFCN](#)\* nasSwtSetChannelLockReq::pLteEARFCN

8.453.2.2 [ltePCI](#)\* nasSwtSetChannelLockReq::pLtePCI

8.453.2.3 [wcdmaUARFCN](#)\* nasSwtSetChannelLockReq::pWcdmaUARFCN

## 8.454 nasSysInfo Struct Reference

## Data Fields

- [SrvStatusInfo](#) \* [pCDMASrvStatusInfo](#)
- [SrvStatusInfo](#) \* [pHDRSrvStatusInfo](#)
- [GSMStatusInfo](#) \* [pGSMStatusInfo](#)
- [GSMStatusInfo](#) \* [pWCDMASrvStatusInfo](#)
- [GSMStatusInfo](#) \* [pLTESrvStatusInfo](#)
- [CDMASysInfo](#) \* [pCDMASysInfo](#)
- [HDRSysInfo](#) \* [pHDRSysInfo](#)
- [GSMStatusInfo](#) \* [pGSMStatusInfo](#)
- [WCDMASysInfo](#) \* [pWCDMASysInfo](#)
- [LTESysInfo](#) \* [pLTESysInfo](#)
- [AddCDMASysInfo](#) \* [pAddCDMASysInfo](#)
- [WORD](#) \* [pAddHDRSysInfo](#)
- [AddSysInfo](#) \* [pAddGSMStatusInfo](#)
- [AddSysInfo](#) \* [pAddWCDMASysInfo](#)
- [WORD](#) \* [pAddLTESysInfo](#)
- [CallBarringSysInfo](#) \* [pGSMCallBarringSysInfo](#)
- [CallBarringSysInfo](#) \* [pWCDMACallBarringSysInfo](#)
- [BYTE](#) \* [pLTEVoiceSupportSysInfo](#)
- [BYTE](#) \* [pGSMCipherDomainSysInfo](#)

- `BYTE * pWCDMACipherDomainSysInfo`

- `BYTE * pSysInfoNoChange`

#### 8.454.1 Detailed Description

Structure for storing the `nasSysInfo` indication parameters.

## Parameters

<i>pCDMASrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SrvStatusInfo</a> for more information.</li> </ul>
<i>pHDRSrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SrvStatusInfo</a> for more information.</li> </ul>
<i>pGSMSrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pWCDMASrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pLTESrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CDMASysInfo</a> for more information.</li> </ul>
<i>pHDRSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">HDRSysInfo</a> for more information.</li> </ul>
<i>pGSMSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSysInfo</a> for more information.</li> </ul>
<i>pWCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">WCDMASysInfo</a> for more information.</li> </ul>
<i>pLTESysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">LTESysInfo</a> for more information.</li> </ul>
<i>pAddCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddCDMASysInfo</a> for more information.</li> </ul>
<i>pAddHDRSysInfo</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>pAddGSMSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddSysInfo</a> for more information.</li> </ul>
<i>pAddWCDMA-SysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddSysInfo</a> for more information.</li> </ul>

<i>pAddLTESysInfo</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>pGSMCallBarringSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CallBarringSysInfo</a> for more information.</li> </ul>
<i>pWCDMACallBarringSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CallBarringSysInfo</a> for more information.</li> </ul>
<i>pLTEVoiceSupportSysInfo</i>	<ul style="list-style-type: none"> <li>• Indicates voice support status on LTE. <ul style="list-style-type: none"> <li>– 0x00 - Voice is not supported</li> <li>– 0x01 - Voice is supported</li> </ul> </li> </ul>
<i>pGSMCipherDomainSysInfo</i>	<ul style="list-style-type: none"> <li>• Ciphering on the service domain. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> </ul> </li> </ul>
<i>pWCDMACipherDomainSysInfo</i>	<ul style="list-style-type: none"> <li>• Ciphering on the service domain. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> </ul> </li> </ul>
<i>pSysInfoNoChange</i>	<ul style="list-style-type: none"> <li>• System Info No Change.</li> <li>• Flag used to notify clients that a request to select a network ended with no change in the PLMN. <ul style="list-style-type: none"> <li>– 0x01 - No change in system information</li> </ul> </li> </ul>

## 8.454.2 Field Documentation

8.454.2.1 **AddCDMASysInfo\*** nasSysInfo::pAddCDMASysInfo

8.454.2.2 **AddSysInfo\*** nasSysInfo::pAddGSMSysInfo

8.454.2.3 **WORD\*** nasSysInfo::pAddHDRSysInfo

- 8.454.2.4 WORD\* nasSysInfo::pAddLTESysInfo
- 8.454.2.5 AddSysInfo\* nasSysInfo::pAddWCDMASysInfo
- 8.454.2.6 SrvStatusInfo\* nasSysInfo::pCDMASrvStatusInfo
- 8.454.2.7 CDMA SysInfo\* nasSysInfo::pCDMA SysInfo
- 8.454.2.8 CallBarringSysInfo\* nasSysInfo::pGSMCallBarringSysInfo
- 8.454.2.9 BYTE\* nasSysInfo::pGSMCipherDomainSysInfo
- 8.454.2.10 GSMSrvStatusInfo\* nasSysInfo::pGSMSrvStatusInfo
- 8.454.2.11 GSMSysInfo\* nasSysInfo::pGSMSysInfo
- 8.454.2.12 SrvStatusInfo\* nasSysInfo::pHDRSrvStatusInfo
- 8.454.2.13 HDRSysInfo\* nasSysInfo::pHDRSysInfo
- 8.454.2.14 GSMSrvStatusInfo\* nasSysInfo::pLTESrvStatusInfo
- 8.454.2.15 LTESysInfo\* nasSysInfo::pLTESysInfo
- 8.454.2.16 BYTE\* nasSysInfo::pLTEVoiceSupportSysInfo
- 8.454.2.17 BYTE\* nasSysInfo::pSysInfoNoChange
- 8.454.2.18 CallBarringSysInfo\* nasSysInfo::pWCDMACallBarringSysInfo
- 8.454.2.19 BYTE\* nasSysInfo::pWCDMACipherDomainSysInfo
- 8.454.2.20 GSMSrvStatusInfo\* nasSysInfo::pWCDMASrvStatusInfo
- 8.454.2.21 WCDMA SysInfo\* nasSysInfo::pWCDMA SysInfo

## 8.455 NASTimeInfoTlv Struct Reference

### Data Fields

- uint8\_t [TlvPresent](#)
- uint64\_t [time](#)

### 8.455.1 Field Documentation

- 8.455.1.1 uint64\_t NASTimeInfoTlv::time
- 8.455.1.2 uint8\_t NASTimeInfoTlv::TlvPresent

## 8.456 netSelectionPref Struct Reference

### Data Fields

- BYTE [netReg](#)

- [WORD mcc](#)
- [WORD mnc](#)

### 8.456.1 Detailed Description

Contain the network selection preference.

#### Parameters

<i>netReg</i>	<ul style="list-style-type: none"> <li>• specifies one of the following actions: <ul style="list-style-type: none"> <li>– 0x00 - Automatic registration <ul style="list-style-type: none"> <li>* Device registers according to its provisioning; mcc and mnc fields are ignored</li> </ul> </li> <li>– 0x01 - Manual Registration <ul style="list-style-type: none"> <li>* Device registers to specified network; mcc and mnc must contain valid values</li> </ul> </li> </ul> </li> </ul>
<i>mcc</i>	<ul style="list-style-type: none"> <li>• MCC value. Range 0 to 999</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>• MNC value. Range 0 to 999</li> </ul>

### 8.456.2 Field Documentation

8.456.2.1 **WORD** netSelectionPref::mcc

8.456.2.2 **WORD** netSelectionPref::mnc

8.456.2.3 **BYTE** netSelectionPref::netReg

## 8.457 NetStats Struct Reference

### Data Fields

- [ULONG rx\\_packets](#)
- [ULONG tx\\_packets](#)
- [ULONGLONG rx\\_bytes](#)
- [ULONGLONG tx\\_bytes](#)
- [ULONG rx\\_errors](#)
- [ULONG tx\\_errors](#)
- [ULONG rx\\_overflows](#)
- [ULONG tx\\_overflows](#)

### 8.457.1 Detailed Description

This structure contains the SLQSGetNetStatistic Information

## Parameters

<i>rx_packets</i>	<ul style="list-style-type: none"> <li>• Number of received Packets without error</li> </ul>
<i>tx_packets</i>	<ul style="list-style-type: none"> <li>• Number of transmitted Packets without error</li> </ul>
<i>rx_bytes</i>	<ul style="list-style-type: none"> <li>• Number of bytes recieved without error</li> </ul>
<i>tx_bytes</i>	<ul style="list-style-type: none"> <li>• NNumbero of bytes transmitted without error</li> </ul>
<i>rx_error</i>	<ul style="list-style-type: none"> <li>• Number of incoming packets with framing errors</li> </ul>
<i>tx_error</i>	<ul style="list-style-type: none"> <li>• Number of outgoing packets with framing errors</li> </ul>
<i>rx_overflows</i>	<ul style="list-style-type: none"> <li>• Number of packets dropped because Rx buffer overflowed</li> </ul>
<i>tx_overflows</i>	<ul style="list-style-type: none"> <li>• Number of packets dropped because Tx buffer overflowed</li> </ul>

## 8.457.2 Field Documentation

8.457.2.1 **ULONGLONG** NetStats::rx\_bytes8.457.2.2 **ULONG** NetStats::rx\_errors8.457.2.3 **ULONG** NetStats::rx\_overflows8.457.2.4 **ULONG** NetStats::rx\_packets8.457.2.5 **ULONGLONG** NetStats::tx\_bytes8.457.2.6 **ULONG** NetStats::tx\_errors8.457.2.7 **ULONG** NetStats::tx\_overflows8.457.2.8 **ULONG** NetStats::tx\_packets

## 8.458 NetworkDebugResp Struct Reference

## Data Fields

- [BYTE](#) \* pObjectVer
- [NetworkStat1x](#) \* pNetworkStat1x
- [NetworkStatEVDO](#) \* pNetworkStatEVDO
- [DeviceConfigDetail](#) \* pDeviceConfigDetail

- [DataStatusDetail](#) \* [pDataStatusDetail](#)

### 8.458.1 Detailed Description

This structure contains information about the SLQSSwiNetworkDebug response parameters.

#### Parameters

<i>pObjectVer</i>	<ul style="list-style-type: none"> <li>• Object's version number for the host to handle <ul style="list-style-type: none"> <li>– 0xFF - NA</li> <li>– Others - shows in decimal</li> </ul> </li> </ul>
<i>pNetworkStat1x</i>	<ul style="list-style-type: none"> <li>• See <a href="#">NetworkStat1x</a> for more information</li> </ul>
<i>pNetworkStatE-VDO</i>	<ul style="list-style-type: none"> <li>• See <a href="#">NetworkStatEVDO</a> for more information.</li> </ul>
<i>pDeviceConfig-Detail</i>	<ul style="list-style-type: none"> <li>• See <a href="#">DeviceConfigDetail</a> for more information.</li> </ul>
<i>pDataStatus-Detail</i>	<ul style="list-style-type: none"> <li>• See <a href="#">DataStatusDetail</a> for more information.</li> </ul>

### 8.458.2 Field Documentation

8.458.2.1 [DataStatusDetail](#)\* [NetworkDebugResp::pDataStatusDetail](#)

8.458.2.2 [DeviceConfigDetail](#)\* [NetworkDebugResp::pDeviceConfigDetail](#)

8.458.2.3 [NetworkStat1x](#)\* [NetworkDebugResp::pNetworkStat1x](#)

8.458.2.4 [NetworkStatEVDO](#)\* [NetworkDebugResp::pNetworkStatEVDO](#)

8.458.2.5 [BYTE](#)\* [NetworkDebugResp::pObjectVer](#)

## 8.459 NetworkStat1x Struct Reference

#### Data Fields

- [BYTE](#) State
- [WORD](#) SO
- [ULONG](#) RX\_PWR
- [WORD](#) RX\_EC\_IO
- [ULONG](#) TX\_PWR
- [BYTE](#) ActSetCnt
- [ActPilotPNElement](#) \* [pActPilotPNElements](#)
- [BYTE](#) NeighborSetCnt
- [WORD](#) \* [pNeighborSetPilotPN](#)



### 8.459.1 Detailed Description

This structure contains 1x network status details

## Parameters

State	<ul style="list-style-type: none"> <li>• CDMA current access state               <ul style="list-style-type: none"> <li>– 0x01 - Searching</li> <li>– 0x02 - Idle</li> <li>– 0x03 - Traffic</li> <li>– Others - NA</li> </ul> </li> </ul>
SO	<ul style="list-style-type: none"> <li>• CDMA service option               <ul style="list-style-type: none"> <li>– 0xFFFF - Not in a call</li> <li>– 0x0001 - Basic Variable Rate Voice Service(8kbps)</li> <li>– 0x0002 - Mobile Station Loopback(8kbps)</li> <li>– 0x0003 - Enhanced Variable Rate Codec(EVRC) Voice Service(8kbps)</li> <li>– 0x0006 - Short message Services(Rate Set 1)</li> <li>– 0x0009 - Mobile Station Loopback(13kbps)</li> <li>– 0x000E - Short Message Service (Rate Set 2)</li> <li>– 0x0011 - High Rate Voice Service(13kbps)</li> <li>– 0x0020 - Test Data Service Option(TDSO)</li> <li>– 0x0021 - cdma2000 High Speed Packet Data Service, Internet or ISO Protocol Stack</li> <li>– 0x0044 - EVRC-B Voice Service(8 kbps)</li> <li>– 0x0046 - EVRC-WB Voice Service(8 kbps)</li> <li>– 0x0049 - Voice Echo mode supports smart blanking(EVRC-NW)</li> <li>– 0x004B - Enhanced loopback</li> <li>– 0x8000 - Proprietary Service Option (Qualcomm Inc.)</li> </ul> </li> </ul>

<i>RX_PWR</i>	<ul style="list-style-type: none"> <li>• RX Pwr(dBm) <ul style="list-style-type: none"> <li>– 0xABCD00EF - -ABCD.EF dBm</li> <li>– ABCD00EF should be transferred to decimal while displaying</li> <li>– Example: 0x12340056 - -4660.86dBm 0x1234 = 4660, 0x0056 = 86</li> <li>– 0xFFFFFFFF - NA</li> </ul> </li> </ul>
<i>RX_EC_IO</i>	<ul style="list-style-type: none"> <li>• RX EC/IO(dB) <ul style="list-style-type: none"> <li>– 0xABCD - -AB.CD dB</li> <li>– ABCD should be transferred to decimal while displaying</li> <li>– Example: 0x1234 - -18.52dB 0x12 = 18, 0x34 = 52</li> <li>– 0xFFFF - NA</li> </ul> </li> </ul>
<i>TX_PWR</i>	<ul style="list-style-type: none"> <li>• TX PWR(dBm) <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - NA</li> <li>– Others - display actual value in decimal</li> <li>– Example: 0x1234 - -4660dBm 0x1234 = 4660</li> </ul> </li> </ul>
<i>ActSetCnt(</i>	IN/OUT ) <ul style="list-style-type: none"> <li>• Count of active pilot PN elements</li> <li>• As input specifies number of sets of parameter pActPilotElements for which memory has been assigned</li> <li>• As output specifies the actual number of sets of parameter pActPilotElements returned by device</li> </ul>
<i>pActPilotPN-Elements</i>	<ul style="list-style-type: none"> <li>• See <a href="#">ActPilotPNElement</a> for more information</li> </ul>
<i>NeighborSetCnt(</i>	IN/OUT ) <ul style="list-style-type: none"> <li>• Count of neighbor pilot PN elements</li> <li>• As input specifies number of sets of parameter pNeighborSetPilotPN for which memory has been assigned</li> <li>• As output specifies the actual number of sets of parameter pNeighborSetPilotPN returned by device</li> </ul>

<i>pNeighborSet-PilotPN</i>	<ul style="list-style-type: none"><li>• Neighbor pilot PN</li></ul>
-----------------------------	---

## 8.459.2 Field Documentation

8.459.2.1 **BYTE** NetworkStat1x::ActSetCnt

8.459.2.2 **BYTE** NetworkStat1x::NeighborSetCnt

8.459.2.3 **ActPilotPNElement\*** NetworkStat1x::pActPilotPNElements

8.459.2.4 **WORD\*** NetworkStat1x::pNeighborSetPilotPN

8.459.2.5 **WORD** NetworkStat1x::RX\_EC\_IO

8.459.2.6 **ULONG** NetworkStat1x::RX\_PWR

8.459.2.7 **WORD** NetworkStat1x::SO

8.459.2.8 **BYTE** NetworkStat1x::State

8.459.2.9 **ULONG** NetworkStat1x::TX\_PWR

## 8.460 NetworkStatEVDO Struct Reference

### Data Fields

- [BYTE State](#)
- [BYTE MACIndex](#)
- [BYTE SectorIDLen](#)
- [WORD \\* pSectorID](#)
- [WORD RX\\_PWR](#)
- [WORD PER](#)
- [WORD PilotEnergy](#)
- [BYTE SNR](#)

### 8.460.1 Detailed Description

This structure contains EVDO network status details

## Parameters

<i>State</i>	<ul style="list-style-type: none"> <li>• EVDO network access state <ul style="list-style-type: none"> <li>– 0x00 - Sleep</li> <li>– 0x01 - Searching</li> <li>– 0x02 - Idle</li> <li>– 0x03 - Active</li> <li>– 0xFF - NA</li> </ul> </li> </ul>
<i>MACIndex</i>	<ul style="list-style-type: none"> <li>• HDR Mac index <ul style="list-style-type: none"> <li>– 0xFF - NA</li> <li>– Others - Display the actual value in decimal</li> <li>– Example: 0x12 - 18 0x12 = 18</li> </ul> </li> </ul>
<i>SectorIDLen</i>	(IN/OUT) <ul style="list-style-type: none"> <li>• Sector ID length</li> <li>• As input specifies length of parameter pSectorID for which memory has been assigned</li> <li>• As output specifies the actual length of parameter pSectorID returned by device</li> </ul>
<i>pSectorID</i>	<ul style="list-style-type: none"> <li>• Sector ID</li> </ul>
<i>RX_PWR</i>	<ul style="list-style-type: none"> <li>• TX PWR(dBm) <ul style="list-style-type: none"> <li>– 0xABCD - -ABCD dBm</li> <li>– ABCD should be transferred to decimal while displaying</li> <li>– Example: 0x1234 - -4660dBm 0x1234 = 4660</li> <li>– 0xFFFF - NA</li> </ul> </li> </ul>

<i>PER</i>	<ul style="list-style-type: none"> <li>• HDR Packet Error Rate <ul style="list-style-type: none"> <li>– 0xFFFF - Unknown</li> <li>– Others - display the actual value in decimal</li> <li>– Example: 0x1234 - -4660dBm 0x1234 = 4660</li> </ul> </li> </ul>
<i>PilotEnergy</i>	<ul style="list-style-type: none"> <li>• Pilt Energy (dB) <ul style="list-style-type: none"> <li>– 0xFFFF - NA</li> <li>– 0xABCD should be transferred to decimal while displaying</li> <li>– Example: 0x1234 - -4660dBm 0x1234 = 4660</li> </ul> </li> </ul>
<i>SNR</i>	<ul style="list-style-type: none"> <li>• Signal to Noise ratio (dB)</li> </ul>

## 8.460.2 Field Documentation

8.460.2.1 **BYTE** NetworkStatEVDO::MACIndex

8.460.2.2 **WORD** NetworkStatEVDO::PER

8.460.2.3 **WORD** NetworkStatEVDO::PilotEnergy

8.460.2.4 **WORD\*** NetworkStatEVDO::pSectorID

8.460.2.5 **WORD** NetworkStatEVDO::RX\_PWR

8.460.2.6 **BYTE** NetworkStatEVDO::SectorIDLen

8.460.2.7 **BYTE** NetworkStatEVDO::SNR

8.460.2.8 **BYTE** NetworkStatEVDO::State

## 8.461 newMTMessageTlv Struct Reference

### Data Fields

- [uint8\\_t TlvPresent](#)
- [sMSMTMessageInfo MTMessageInfo](#)

### 8.461.1 Detailed Description

## Parameters

<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Boolean indicating the presence of the TLV in the QMI response</li> </ul>
<i>MTMessageInfo</i>	<ul style="list-style-type: none"> <li>• MT Message</li> <li>• See <a href="#">sMSMTMessageInfo</a> for more information</li> </ul>

## 8.461.2 Field Documentation

8.461.2.1 [sMSMTMessageInfo](#) newMTMessageTlv::MTMessageInfo8.461.2.2 [uint8\\_t](#) newMTMessageTlv::TlvPresent

## 8.462 newPwdData Struct Reference

## Data Fields

- [BYTE](#) newPwd [4]
- [BYTE](#) newPwdAgain [4]

## 8.462.1 Detailed Description

This structure contains New Password Data.

## Parameters

<i>newPwd[PASS-WORD_LENGTH]</i>	<ul style="list-style-type: none"> <li>• New password. <ul style="list-style-type: none"> <li>– Password consists of 4 ASCII digits.</li> <li>– Range: 0000 to 9999.</li> </ul> </li> </ul>
<i>newPwdAgain[PASSWORD_LENGTH]</i>	<ul style="list-style-type: none"> <li>• New password again. <ul style="list-style-type: none"> <li>– Password consists of 4 ASCII digits.</li> <li>– Range: 0000 to 9999.</li> </ul> </li> </ul>

## 8.462.2 Field Documentation

8.462.2.1 [BYTE](#) newPwdData::newPwd[4]8.462.2.2 [BYTE](#) newPwdData::newPwdAgain[4]

## 8.463 nmrCellInfo Struct Reference

## Data Fields

- [ULONG nmrCellID](#)
- [BYTE nmrPlmn](#) [3]
- [WORD nmrLac](#)
- [WORD nmrArfcn](#)
- [BYTE nmrBsic](#)
- [WORD nmrRxLev](#)

### 8.463.1 Detailed Description

This structure contains information about the Network Measurement Report (NMR) Cell Information.



## Parameters

<i>nmrCellID</i>	<ul style="list-style-type: none"> <li>• Cell ID.</li> <li>• 0xFFFFFFFF indicates cell ID information is not present.</li> </ul>
<i>nmrPlmn[PLMN- _LENGTH]</i>	<ul style="list-style-type: none"> <li>• MCC/MNC information coded as octet 3, 4, and 5.</li> <li>• This field is ignored when nmrCellID is not present.</li> </ul>
<i>nmrLac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• This field is ignored when nmrCellID is not present. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>nmrArfcn</i>	<ul style="list-style-type: none"> <li>• Absolute RF channel number. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>nmrBsic</i>	<ul style="list-style-type: none"> <li>• Base station identity code. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>nmrRxLev</i>	<ul style="list-style-type: none"> <li>• Cell Rx measurement.</li> <li>• Values range between 0 and 63.</li> <li>• Mapped to a measured signal level: <ul style="list-style-type: none"> <li>– Rxlev 0 is a signal strength less than -110 dBm</li> <li>– Rxlev 1 is -110 dBm to -109 dBm</li> <li>– Rxlev 2 is -109 dBm to -108 dBm</li> <li>– ...</li> <li>– Rxlev 62 is -49 dBm to -48 dBm</li> <li>– Rxlev 63 is greater than -48 dBm</li> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>

## 8.463.2 Field Documentation

8.463.2.1 WORD nmrCellInfo::nmrArfcn

8.463.2.2 BYTE nmrCellInfo::nmrBsic

8.463.2.3 ULONG nmrCellInfo::nmrCellID

8.463.2.4 WORD nmrCellInfo::nmrLac

8.463.2.5 BYTE nmrCellInfo::nmrPlmn[3]

8.463.2.6 WORD nmrCellInfo::nmrRxLev

## 8.464 NSSAudioCtrl Struct Reference

### Data Fields

- [BYTE upLink](#)
- [BYTE downLink](#)

### 8.464.1 Detailed Description

This structure contains National Supplementary Services - Audio Control Information

#### Parameters

<i>upLink</i>	<ul style="list-style-type: none"> <li>• Values as per[ S24, 4.10 Reservation response].</li> </ul>
<i>downLink</i>	<ul style="list-style-type: none"> <li>• Values as per[ S24, 4.10 Reservation response].</li> </ul>

### 8.464.2 Field Documentation

8.464.2.1 BYTE NSSAudioCtrl::downLink

8.464.2.2 BYTE NSSAudioCtrl::upLink

## 8.465 NWProfile Struct Reference

### Data Fields

- [WORD tech](#)
- [BYTE \\* pProfSz](#)
- [WORD \\* pProfValues](#)

### 8.465.1 Detailed Description

This structure contains Network supported QoS profile

#### Parameters

<i>tech</i>	Technology on which the network supported QoS profiles are being returned: <ul style="list-style-type: none"> <li>• CDMA – 0x8001</li> </ul>
-------------	--

<i>exponent</i>	
-----------------	--

## 8.465.2 Field Documentation

8.465.2.1 **BYTE\*** NWProfile::pProfSz

8.465.2.2 **WORD\*** NWProfile::pProfValues

8.465.2.3 **WORD** NWProfile::tech

## 8.466 omaDmConfigTlv Struct Reference

### Data Fields

- [BYTE](#) state
- [BYTE](#) userInputReq
- [USHORT](#) userInputTimeout
- [USHORT](#) alertmsglength
- [BYTE](#) alertmsg [256]

### 8.466.1 Detailed Description

This structure will hold the SwiOmaDmConfig session parameters information.

#### Parameters

<i>state</i>	<ul style="list-style-type: none"> <li>• 0x01 - OMA-DM Read Request</li> <li>• 0x02 - OMA-DM Change Request</li> <li>• 0x03 - OMA-DM Config Complete</li> </ul>
<i>user_input_req</i>	- Bit mask of available user inputs <ul style="list-style-type: none"> <li>• 0x00 - No user input required. Informational indication</li> <li>• 0x01 - Accept</li> <li>• 0x02 - Reject</li> </ul>
<i>user_input_timeout</i>	<ul style="list-style-type: none"> <li>• Timeout for user input in minutes. A value of 0 means no time-out</li> </ul>
<i>alertmsglength</i>	<ul style="list-style-type: none"> <li>• Length of Alert message string in bytes</li> </ul>
<i>alertmsg</i>	<ul style="list-style-type: none"> <li>• Alert message in UCS2 (Max 256 characters)</li> </ul>

## 8.466.2 Field Documentation

8.466.2.1 **BYTE** omaDmConfigTlv::alertmsg[256]

8.466.2.2    **USHORT** omaDmConfigTlv::alertmsglength

8.466.2.3    **BYTE** omaDmConfigTlv::state

8.466.2.4    **BYTE** omaDmConfigTlv::userInputReq

8.466.2.5    **USHORT** omaDmConfigTlv::userInputTimeout

## 8.467    omaDmConfigTlvExt Struct Reference

### Data Fields

- [BYTE state](#)
- [BYTE userInputReq](#)
- [USHORT userInputTimeout](#)
- [USHORT alertmsglength](#)
- [BYTE alertmsg \[256\]](#)

### 8.467.1    Detailed Description

This structure will hold the SwiOmaDmConfig session parameters information.

## Parameters

<i>state</i>	<ul style="list-style-type: none"> <li>• 1 - reserved</li> <li>• 2 - reserved</li> <li>• 3 - reserved</li> <li>• 4 - CI DC Success</li> <li>• 5 - CI DC Failure</li> <li>• 6 - User/device initiated PRL update success.</li> <li>• 7 - User/device initiated PRL update failure.</li> <li>• 8 - HFA DC session start</li> <li>• 9 - HFA DC success.</li> <li>• 10 - HFA is cancelled.</li> <li>• 11 - HFA retry. UI Screen 13[1] with 0 percent progress bar should be shown.</li> <li>• 12 - HFA fail after 5 retries. UI Screen 2[1] should be displayed.</li> <li>• 13 - HFA retry down counter. Used to update the process bar of UI Screen 13[1].</li> <li>• 14 - HFA PRL session start, UI screen 4[1] should be displayed.</li> <li>• 15 - HFA PRL update success.</li> <li>• 16 - Device is launching a NI session. UI Screen 1[1] should be displayed.</li> <li>• 17 - An empty session. UI Screen 2[1] should be displayed.</li> <li>• 18 - No network coverage.</li> <li>• 19 - HFA is not enabled.</li> <li>• 20 - CI DC Start, UI Screen 1[1] should be displayed.</li> <li>• 21 - CI PRL start, UI screen 4[1] should be displayed.</li> <li>• 22 - HFA PRL updates fail.</li> <li>• 23 - Device reboot.</li> <li>• 24 - CI DC is cancelled.</li> <li>• 25 - User/device initiated PRL update is cancelled.</li> <li>• 26 - NI session is cancelled.</li> <li>• 27 - Current NI session is not enabled.</li> <li>• 28 - NI DC success.</li> <li>• 29 - NI DC Fail.</li> <li>• 30 - NI PRL success</li> <li>• 31 - NI PRL fail.</li> <li>• 32 - Reserved</li> <li>• 33 - NI fumo fail</li> <li>• 34 - NI session fail, unable to point out the session type.</li> </ul>
--------------	---

*user\_input\_req* - OMA task stop to wait user's input if this field is valid. until user input selection or after "UI Timer out (next field). In the case of timeout, a default selection of "YES/OK" is accepted. Note that this option is valid when DM state is 4/6/12/28/30. 0 - user/host doesn't need to input anything, and OMA task doesn't blocked by UI. 1 - user/host must input "YES/OK/CANCEL". 2 - User/host must input "NO/CANCEL". 3 - user/host must input "YES/OK/NO/CANCEL".

<i>user_input_timeout</i>	<ul style="list-style-type: none"> <li>Timeout for user input in seconds. This indicates how many seconds OMA task stop to wait for host/user's response.</li> </ul>
<i>alertmsglength</i>	<ul style="list-style-type: none"> <li>Length of Alert message string in word(16-bit)</li> </ul>
<i>alertmsg</i>	<ul style="list-style-type: none"> <li>Alert message in UCS2 (Max 256 characters)</li> <li>This string is printed by host</li> </ul>

## 8.467.2 Field Documentation

8.467.2.1 **BYTE** omaDmConfigTlvExt::alertmsg[256]

8.467.2.2 **USHORT** omaDmConfigTlvExt::alertmsglength

8.467.2.3 **BYTE** omaDmConfigTlvExt::state

8.467.2.4 **BYTE** omaDmConfigTlvExt::userInputReq

8.467.2.5 **USHORT** omaDmConfigTlvExt::userInputTimeout

## 8.468 omaDmFotaTlv Struct Reference

### Data Fields

- [BYTE](#) state
- [BYTE](#) userInputReq
- [USHORT](#) userInputTimeout
- [ULONG](#) fwdloadsize
- [ULONG](#) fwloadComplete
- [USHORT](#) updateCompleteStatus
- [BYTE](#) severity
- [USHORT](#) versionlength
- [BYTE](#) version [256]
- [USHORT](#) namelength
- [BYTE](#) package\_name [256]
- [USHORT](#) descriptionlength
- [BYTE](#) description [256]
- [BYTE](#) sessionType

### 8.468.1 Detailed Description

This structure will hold the SwiOmaDmFota session parameters information.

#### Parameters

---

<i>state</i>	<ul style="list-style-type: none"> <li>• 0x01 - No Firmware available</li> <li>• 0x02 - Query Firmware Download</li> <li>• 0x03 - Firmware Downloading</li> <li>• 0x04 - Firmware downloaded</li> <li>• 0x05 - Query Firmware Update</li> <li>• 0x06 - Firmware updating</li> <li>• 0x07 - Firmware updated</li> </ul>
<i>user_input_req</i>	<ul style="list-style-type: none"> <li>- Bit mask of available user inputs</li> <li>• 0x00 - No user input required. Informational indication</li> <li>• 0x01 - Accept</li> <li>• 0x02 - Reject</li> </ul>
<i>user_input_timeout</i>	<ul style="list-style-type: none"> <li>• Timeout for user input in minutes. A value of 0 means no time-out</li> </ul>
<i>fw_dload_size</i>	<ul style="list-style-type: none"> <li>• The size (in bytes) of the firmware update package</li> </ul>
<i>fw_dload_complete</i>	<ul style="list-style-type: none"> <li>• The number of bytes downloaded. Need to determine how often to send this message for progress bar notification. Every 500ms or 5% increment.</li> </ul>
<i>update_complete_status</i>	<ul style="list-style-type: none"> <li>• See table below.</li> </ul>
<i>severity</i>	<ul style="list-style-type: none"> <li>• 0x01 - Mandatory</li> <li>• 0x02 - Optional</li> </ul>
<i>versionlength</i>	<ul style="list-style-type: none"> <li>• Length of FW Version string in bytes</li> </ul>
<i>version</i>	<ul style="list-style-type: none"> <li>• FW Version string in ASCII (Max 256 characters)</li> </ul>
<i>namelength</i>	<ul style="list-style-type: none"> <li>• Length Package Name string in bytes</li> </ul>
<i>package_name</i>	<ul style="list-style-type: none"> <li>• Package Name in UCS2 (Max 256 characters)</li> </ul>
<i>descriptionlength</i>	<ul style="list-style-type: none"> <li>• Length of description in bytes</li> </ul>

<i>description</i>	<ul style="list-style-type: none"> <li>• Description of Update Package in USC2 (Max 256 characters)</li> </ul>
<i>sessionType</i>	<ul style="list-style-type: none"> <li>• 0x00 - Client initiated</li> <li>• 0x01 - Network initiated</li> </ul>

## 8.468.2 Field Documentation

8.468.2.1 **BYTE** omaDmFotaTlv::description[256]

8.468.2.2 **USHORT** omaDmFotaTlv::descriptionlength

8.468.2.3 **ULONG** omaDmFotaTlv::fwddownloadsize

8.468.2.4 **ULONG** omaDmFotaTlv::fwloadComplete

8.468.2.5 **USHORT** omaDmFotaTlv::namelength

8.468.2.6 **BYTE** omaDmFotaTlv::package\_name[256]

8.468.2.7 **BYTE** omaDmFotaTlv::sessionType

8.468.2.8 **BYTE** omaDmFotaTlv::severity

8.468.2.9 **BYTE** omaDmFotaTlv::state

8.468.2.10 **USHORT** omaDmFotaTlv::updateCompleteStatus

8.468.2.11 **BYTE** omaDmFotaTlv::userInputReq

8.468.2.12 **USHORT** omaDmFotaTlv::userInputTimeout

8.468.2.13 **BYTE** omaDmFotaTlv::version[256]

8.468.2.14 **USHORT** omaDmFotaTlv::versionlength

## 8.469 omaDmFotaTlvExt Struct Reference

### Data Fields

- [BYTE](#) state
- [BYTE](#) reserved
- [USHORT](#) userInputTimeout
- [ULONG](#) packageSize
- [ULONG](#) receivedBytes
- [USHORT](#) fumoResultCode
- [USHORT](#) versionlength
- [BYTE](#) version [256]
- [USHORT](#) namelength
- [BYTE](#) package\_name [256]
- [USHORT](#) descriptionlength
- [BYTE](#) description [256]



### 8.469.1 Detailed Description

This structure will hold the SwiOmaDmFota session parameters information.

#### Parameters

<i>state</i>	<ul style="list-style-type: none"><li>• 0x01 - No Firmware available</li><li>• 0x02 - reserved</li><li>• 0x03 - Update progress bar, UI screen 7[1] should be displayed</li><li>• 0x04 - reserved</li><li>• 0x05 - FUMO image download success, UI screen 8[1] should be displayed</li><li>• 0x06 - reserved</li><li>• 0x07 - FUMO image installation result, used to return error code.</li><li>• 0x08 - FUMO session start</li><li>• 0x09 - UI Screen 7[1] with 0 percent bar should be displayed</li><li>• 0x0A - FUMO image installation is cancelled by user.</li><li>• 0x0B - FUMO session fail</li><li>• 0x0C - Device is sending a report to OMA Server.</li><li>• 0x0D - Report to server success.</li><li>• 0x0E - Report to server fails.</li><li>• 0x0F - reserved</li><li>• 0x10 - FUMO session is cancelled before image download success.</li><li>• 0x11 - UI Screen 16[1] should be displayed, FUMO delay option, OMA task is blocked until a valid response is received.</li></ul>
--------------	---

<i>reserved</i>	- For sprint reserved
<i>user_input_timeout</i>	<ul style="list-style-type: none"> <li>How many seconds OMA task stop to wait for user/host response.</li> </ul>
<i>packageSize</i>	<ul style="list-style-type: none"> <li>The size (in bytes) of the firmware update package (only valid for states 3/5/7).</li> </ul>
<i>receivedBytes</i>	<ul style="list-style-type: none"> <li>The number of bytes downloaded. Useful for FUMO state 3.</li> </ul>
<i>fumoResultCode</i>	<ul style="list-style-type: none"> <li>Used when fumo state is 7/11. REsult code of FUMO image installation <ul style="list-style-type: none"> <li>200 image install success</li> </ul> </li> <li>Others: image install fail</li> </ul>
<i>versionlength</i>	<ul style="list-style-type: none"> <li>Length of FW Version string in bytes</li> </ul>
<i>version</i>	<ul style="list-style-type: none"> <li>FW Version string in ASCII (Max 256 characters)</li> </ul>
<i>namelength</i>	<ul style="list-style-type: none"> <li>Length Package Name string in bytes</li> </ul>
<i>package_name</i>	<ul style="list-style-type: none"> <li>Package Name in UCS2 (Max 256 characters)</li> </ul>
<i>descriptionlength</i>	<ul style="list-style-type: none"> <li>Length of description in bytes</li> </ul>
<i>description</i>	<ul style="list-style-type: none"> <li>Description of Update Package in USC2 (Max 256 characters)</li> </ul>

## 8.469.2 Field Documentation

8.469.2.1 **BYTE** omaDmFotaTlvExt::description[256]

8.469.2.2 **USHORT** omaDmFotaTlvExt::descriptionlength

8.469.2.3 **USHORT** omaDmFotaTlvExt::fumoResultCode

8.469.2.4 **USHORT** omaDmFotaTlvExt::namelength

8.469.2.5 **BYTE** omaDmFotaTlvExt::package\_name[256]

8.469.2.6 **ULONG** omaDmFotaTlvExt::packageSize

8.469.2.7 **ULONG** omaDmFotaTlvExt::receivedBytes

- 8.469.2.8 **BYTE** omaDmFotaTlvExt::reserved
- 8.469.2.9 **BYTE** omaDmFotaTlvExt::state
- 8.469.2.10 **USHORT** omaDmFotaTlvExt::userInputTimeout
- 8.469.2.11 **BYTE** omaDmFotaTlvExt::version[256]
- 8.469.2.12 **USHORT** omaDmFotaTlvExt::versionlength

## 8.470 omaDmNotificationsTlv Struct Reference

### Data Fields

- [BYTE](#) notification
- [USHORT](#) sessionStatus

### 8.470.1 Field Documentation

- 8.470.1.1 **BYTE** omaDmNotificationsTlv::notification
- 8.470.1.2 **USHORT** omaDmNotificationsTlv::sessionStatus

## 8.471 operatorNameString Struct Reference

### Data Fields

- [BYTE](#) [PLMNName](#) [255]

### 8.471.1 Detailed Description

This structure contains Operator Name String as defined in CPHS4\_2.WW6(Feb 27, 1997) (Section B.4.1.2) from multiple sources.

#### Parameters

<i>PLMNName</i>	<ul style="list-style-type: none"><li>• PLMN name must be coded in a default 7-bit alphabet with b8 set to 0.</li></ul>
-----------------	---

### 8.471.2 Field Documentation

- 8.471.2.1 **BYTE** operatorNameString::PLMNName[255]

## 8.472 OperatorPLMNData Struct Reference

### Data Fields

- [BYTE](#) mcc [3]
- [BYTE](#) mnc [3]
- [WORD](#) lac1
- [WORD](#) lac2
- [BYTE](#) PLMNRecID

### 8.472.1 Detailed Description

This structure contains Operator PLMN Data from multiple sources.

#### Parameters

<i>mcc</i>	<ul style="list-style-type: none"> <li>MCC in ASCII string (a value of D in any of the digits is to be used to indicate a "wild" value for that corresponding digit).</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>MNC in ASCII string (a value of D in any of the digits is to be used to indicate a "wild" value for that corresponding digit; digit 3 in MNC is optional and when not present, will be set as ASCII F).</li> </ul>
<i>lac1</i>	<ul style="list-style-type: none"> <li>Location area code 1.</li> </ul>
<i>lac2</i>	<ul style="list-style-type: none"> <li>Location area code 1.</li> </ul>
<i>PLMNRecID</i>	<ul style="list-style-type: none"> <li>PLMN network name record identifier.</li> </ul>

### 8.472.2 Field Documentation

8.472.2.1 WORD OperatorPLMNData::lac1

8.472.2.2 WORD OperatorPLMNData::lac2

8.472.2.3 BYTE OperatorPLMNData::mcc[3]

8.472.2.4 BYTE OperatorPLMNData::mnc[3]

8.472.2.5 BYTE OperatorPLMNData::PLMNRecID

## 8.473 operatorPLMNList Struct Reference

#### Data Fields

- [WORD numInstance](#)
- [OperatorPLMNData PLMNData](#) [255]

### 8.473.1 Detailed Description

This structure contains Operator PLMN List as defined in 3GPP TS 31.102 (Section 4.2.59) from multiple sources.

## Parameters

<i>numInstance</i>	<ul style="list-style-type: none"> <li>Number of sets of the elements.</li> </ul>
<i>PLMNData</i>	<ul style="list-style-type: none"> <li>Refer OperatorPLMNData for details (Optional).</li> </ul>

## 8.473.2 Field Documentation

8.473.2.1 WORD operatorPLMNList::numInstance

8.473.2.2 OperatorPLMNData operatorPLMNList::PLMNData[255]

## 8.474 pack\_dms\_GetCustFeaturesV2\_t Struct Reference

## Data Fields

- uint8\_t [cust\\_id](#) [64+1]
- uint8\_t [list\\_type](#)
- uint16\_t [Tlvresult](#)

## 8.474.1 Detailed Description

This structure contains which customization id or the list type want to retrieve from modem. This TLV is only applicable for 9x30 modules so far

## Parameters

<i>cust_id</i>	<ul style="list-style-type: none"> <li>Customization ID (Maximum 64 bytes)</li> </ul>
<i>list_type</i>	<ul style="list-style-type: none"> <li>list type requested</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>Pack Result</li> </ul>

## 8.474.2 Field Documentation

8.474.2.1 uint8\_t pack\_dms\_GetCustFeaturesV2\_t::cust\_id[64+1]

8.474.2.2 uint8\_t pack\_dms\_GetCustFeaturesV2\_t::list\_type

8.474.2.3 uint16\_t pack\_dms\_GetCustFeaturesV2\_t::Tlvresult

## 8.475 pack\_dms\_SetCrashAction\_t Struct Reference

## Data Fields

- uint8\_t [crashAction](#)

### 8.475.1 Detailed Description

Modem action in case of a crash

Parameters

<i>crashAction</i>	<ul style="list-style-type: none"> <li>• 0 - USB Memory Download. Modem will reset after a crash and will stay in USB download mode with only DM port enumerated.</li> <li>• 1 - Reset. Modem will reset and come back in ONLINE mode. Minimal crash data will be available and can be extracted with at!gcdump? AT command</li> <li>• 2 - No Action</li> </ul>
--------------------	---

### 8.475.2 Field Documentation

8.475.2.1 uint8\_t pack\_dms\_SetCrashAction\_t::crashAction

## 8.476 pack\_dms\_SetCustFeature\_t Struct Reference

## Data Fields

- uint32\_t [GpsEnable](#)
- uint8\_t [DisableIMSI](#)
- uint16\_t [IPFamSupport](#)
- uint8\_t [RMAutoConnect](#)
- uint8\_t [GPSSel](#)
- uint8\_t [SMSSupport](#)
- uint8\_t [IsVoiceEnabled](#)
- uint8\_t [DHCPRelayEnabled](#)
- uint8\_t [GPSLPM](#)

### 8.476.1 Field Documentation

8.476.1.1 uint8\_t pack\_dms\_SetCustFeature\_t::DHCPRelayEnabled

8.476.1.2 uint8\_t pack\_dms\_SetCustFeature\_t::DisableIMSI

8.476.1.3 uint32\_t pack\_dms\_SetCustFeature\_t::GpsEnable

8.476.1.4 uint8\_t pack\_dms\_SetCustFeature\_t::GPSLPM

8.476.1.5 uint8\_t pack\_dms\_SetCustFeature\_t::GPSSel

8.476.1.6 uint16\_t pack\_dms\_SetCustFeature\_t::IPFamSupport

8.476.1.7 uint8\_t pack\_dms\_SetCustFeature\_t::IsVoiceEnabled

8.476.1.8 uint8\_t pack\_dms\_SetCustFeature\_t::RMAutoConnect

8.476.1.9 uint8\_t pack\_dms\_SetCustFeature\_t::SMSSupport

## 8.477 pack\_dms\_SetCustFeaturesV2\_t Struct Reference

### Data Fields

- uint8\_t [cust\\_id](#) [64+1]
- uint16\_t [value\\_length](#)
- uint8\_t [cust\\_value](#) [8+1]
- uint16\_t [Tlvresult](#)

### 8.477.1 Detailed Description

This structure contains customization settings set to modem pack

#### Parameters

<i>cust_id</i>	<ul style="list-style-type: none"> <li>• Customization ID (Maximum 64 bytes)</li> </ul>
<i>value_length</i>	<ul style="list-style-type: none"> <li>• length of cust_value field</li> </ul>
<i>cust_value</i>	<ul style="list-style-type: none"> <li>• Customization Setting Value (Maximum 8 bytes)</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Pack Result</li> </ul>

### 8.477.2 Field Documentation

8.477.2.1 uint8\_t pack\_dms\_SetCustFeaturesV2\_t::cust\_id[64+1]

8.477.2.2 uint8\_t pack\_dms\_SetCustFeaturesV2\_t::cust\_value[8+1]

8.477.2.3 uint16\_t pack\_dms\_SetCustFeaturesV2\_t::Tlvresult

8.477.2.4 uint16\_t pack\_dms\_SetCustFeaturesV2\_t::value\_length

## 8.478 pack\_dms\_SetEventReport\_t Struct Reference

### Data Fields

- uint8\_t [mode](#)

### 8.478.1 Field Documentation

8.478.1.1 uint8\_t pack\_dms\_SetEventReport\_t::mode

## 8.479 pack\_dms\_SetPower\_t Struct Reference

### Data Fields

- uint32\_t [mode](#)
- uint16\_t [Tlvresult](#)

### 8.479.1 Field Documentation

8.479.1.1 uint32\_t pack\_dms\_SetPower\_t::mode

8.479.1.2 uint16\_t pack\_dms\_SetPower\_t::Tlvresult

## 8.480 pack\_dms\_SetUSBComp\_t Struct Reference

### Data Fields

- uint8\_t [USBComp](#)
- uint16\_t [Tlvresult](#)

### 8.480.1 Field Documentation

8.480.1.1 uint16\_t pack\_dms\_SetUSBComp\_t::Tlvresult

8.480.1.2 uint8\_t pack\_dms\_SetUSBComp\_t::USBComp

## 8.481 pack\_dms\_SLQSDmsSwiIndicationRegister\_t Struct Reference

### Data Fields

- uint8\_t [resetInfoInd](#)

### 8.481.1 Detailed Description

#### Parameters

<i>resetInfoInd</i> [IN]	<ul style="list-style-type: none"><li>• Values<ul style="list-style-type: none"><li>– 0 - Disable</li><li>– 1 - Enable</li></ul></li></ul>
--------------------------	--

### 8.481.2 Field Documentation

8.481.2.1 uint8\_t pack\_dms\_SLQSDmsSwiIndicationRegister\_t::resetInfoInd

## 8.482 pack\_dms\_SLQSSwiSetDyingGaspCfg\_t Struct Reference



## Data Fields

- uint8\_t \* [pDestSMSNum](#)
- uint8\_t \* [pDestSMSContent](#)

### 8.482.1 Detailed Description

#### Parameters

<i>pDestSMSNum</i> [-IN]	<ul style="list-style-type: none"> <li>• SMS Destination Number as string of 8 bit ASCII Characters Max 20 chars.</li> <li>• Optional parameter.</li> </ul>
<i>pDestSMS-Content</i> [IN]	<ul style="list-style-type: none"> <li>• SMS Content as a string of 8 bit ASCII text characters Max 160 chars.</li> <li>• Optional parameter.</li> </ul>

### 8.482.2 Field Documentation

8.482.2.1 uint8\_t\* pack\_dms\_SLQSSwiSetDyingGaspCfg\_t::pDestSMSContent

8.482.2.2 uint8\_t\* pack\_dms\_SLQSSwiSetDyingGaspCfg\_t::pDestSMSNum

## 8.483 pack\_dms\_UIMGetICCID\_t Struct Reference

## Data Fields

- uint16\_t [Tlvresult](#)

### 8.483.1 Detailed Description

This structure contains UIM Get ICCID pack

#### Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Pack result.</li> </ul>
------------------	--

### 8.483.2 Field Documentation

8.483.2.1 uint16\_t pack\_dms\_UIMGetICCID\_t::Tlvresult

## 8.484 pack\_fms\_GetImagesPreference\_t Struct Reference

## Data Fields

- uint16\_t [Tlvresult](#)

### 8.484.1 Detailed Description

This structure contains the Get Image Preference information pack

## Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Pack result</li></ul>
------------------	---

## 8.484.2 Field Documentation

8.484.2.1 uint16\_t pack\_fms\_GetImagesPreference\_t::Tlvresult

## 8.485 pack\_fms\_GetStoredImages\_t Struct Reference

## Data Fields

- uint16\_t [Tlvresult](#)

## 8.485.1 Detailed Description

This structure contains the Get Stored Images pack

## Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Pack result</li></ul>
------------------	---

## 8.485.2 Field Documentation

8.485.2.1 uint16\_t pack\_fms\_GetStoredImages\_t::Tlvresult

## 8.486 pack\_fms\_SetImagesPreference\_t Struct Reference

## Data Fields

- uint32\_t [imageListSize](#)
- [FMSPrefImageList](#) \* [pImageList](#)
- uint32\_t [bForceDownload](#)
- uint8\_t [modemindex](#)
- uint16\_t [Tlvresult](#)

## 8.486.1 Detailed Description

This structure contains the Set Images Preference pack

## Parameters

<i>imageListSize</i>	<ul style="list-style-type: none"><li>• Image List Size</li></ul>
----------------------	---

<i>pImageList</i>	<ul style="list-style-type: none"> <li>• Image List</li> <li>• See <a href="#">FMSPrefImageList</a></li> </ul>
<i>bForceDownload</i>	<ul style="list-style-type: none"> <li>• 0 - Not Force Download.</li> <li>• 1 - Force Download.</li> </ul>
<i>modemindex</i>	<ul style="list-style-type: none"> <li>• Modem Index.</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack result</li> </ul>

## 8.486.2 Field Documentation

8.486.2.1 `uint32_t pack_fms_SetImagesPreference_t::bForceDownload`

8.486.2.2 `uint32_t pack_fms_SetImagesPreference_t::imageListSize`

8.486.2.3 `uint8_t pack_fms_SetImagesPreference_t::modemindex`

8.486.2.4 `FMSPrefImageList* pack_fms_SetImagesPreference_t::pImageList`

8.486.2.5 `uint16_t pack_fms_SetImagesPreference_t::Tlvresult`

## 8.487 `pack_loc_Delete_Assist_Data_t` Struct Reference

### Data Fields

- `loc_SVInfo` \* `pSVInfo`
- `loc_GnssData` \* `pGnssData`
- `loc_CellDb` \* `pCellDb`
- `loc_ClkInfo` \* `pClkInfo`
- `loc_BdsSVInfo` \* `pBdsSVInfo`
- `uint16_t Tlvresult`

### 8.487.1 Detailed Description

This structure contains LOC delete assist data pack

#### Parameters

<i>pSVInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to struct <code>loc_SVInfo</code>. See <code>loc_SVInfo</code> for more information</li> </ul>
----------------	---

<i>pGnssData</i>	<ul style="list-style-type: none"> <li>• Pointer to struct <a href="#">loc_GnssData</a>. See <a href="#">loc_GnssData</a> for more information</li> </ul>
<i>pCellDb</i>	<ul style="list-style-type: none"> <li>• Pointer to struct <a href="#">loc_CellDb</a>. See <a href="#">loc_CellDb</a> for more information</li> </ul>
<i>pClkInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to struct <a href="#">loc_ClkInfo</a>. See <a href="#">loc_ClkInfo</a> for more information</li> </ul>
<i>pBdsSVInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to struct <a href="#">loc_BdsSVInfo</a>. See <a href="#">loc_BdsSVInfo</a> for more information</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Pack delete assist data request result.</li> </ul>

## 8.487.2 Field Documentation

8.487.2.1 `loc_BdsSVInfo*` `pack_loc_Delete_Assist_Data_t::pBdsSVInfo`

8.487.2.2 `loc_CellDb*` `pack_loc_Delete_Assist_Data_t::pCellDb`

8.487.2.3 `loc_ClkInfo*` `pack_loc_Delete_Assist_Data_t::pClkInfo`

8.487.2.4 `loc_GnssData*` `pack_loc_Delete_Assist_Data_t::pGnssData`

8.487.2.5 `loc_SVInfo*` `pack_loc_Delete_Assist_Data_t::pSVInfo`

8.487.2.6 `uint16_t` `pack_loc_Delete_Assist_Data_t::Tlvresult`

## 8.488 pack\_loc\_EventRegister\_t Struct Reference

### Data Fields

- `uint64_t` [eventRegister](#)
- `uint16_t` [Tlvresult](#)

### 8.488.1 Detailed Description

This structure contains the Parameter for RegisterEvents

## Parameters

<i>eventRegister</i>	<ul style="list-style-type: none"> <li>• Specifies the events that the control point is interested in receiving. -Values             <ul style="list-style-type: none"> <li>– 0x00000001 - to receive position report event indications</li> <li>– 0x00000002 - to receive satellite report event indications. These reports are sent at a 1 Hz rate.</li> <li>– 0x00000004 - to receive NMEA reports for position and satellites in view. The report is at a 1 Hz rate.</li> <li>– 0x00000008 - to receive NI Notify/Verify request event indications</li> <li>– 0x00000010 - to receive time injection request event indications.</li> <li>– 0x00000020 - to receive predicted orbits request event indications.</li> <li>– 0x00000040 - to receive position injection request event indications.</li> <li>– 0x00000080 - to receive engine state report event indications.</li> <li>– 0x00000100 - to receive fix session status report event indications.</li> <li>– 0x00000200 - to receive Wi-Fi position request event indications.</li> <li>– 0x00000400 - to receive notifications from the location engine indicating its readiness to accept data from the sensors (accelerometer, gyroscope, etc.).</li> <li>– 0x00000800 - to receive time sync requests from the GPS engine. Time sync enables the GPS engine to synchronize its clock with the sensor processor's clock.</li> <li>– 0x00001000 - to receive Stationary Position Indicator (SPI) streaming report indications.</li> <li>– 0x00002000 - to receive location server requests. These requests are generated when the service wishes to establish a connection with a location server.</li> <li>– 0x00004000 - to receive notifications related to network-initiated Geofences. These events notify the client when a network-initiated Geofence is added, deleted, or edited.</li> <li>– 0x00008000 - to receive Geofence alerts. These alerts are generated to inform the client of the changes that may affect a Geofence, e.g., if GPS is turned off or if the network is unavailable.</li> <li>– 0x00010000 - to receive notifications when a Geofence is breached. These events are generated when a UE enters or leaves the perimeter of a Geofence. This breach report is for a single Geofence.</li> <li>– 0x00020000 - to register for pedometer control requests from the location engine. The location engine sends this event to control the injection of pedometer reports.</li> <li>– 0x00040000 - to register for motion data control requests from the location engine. The location engine sends this event to control the injection of motion data.</li> <li>– 0x00080000 - to receive notification when a batch is full. The location engine sends this event to notify of Batch Full for ongoing batching session.</li> <li>– 0x00100000 - to receive position report indications along with an ongoing batching session. The location engine sends this event to notify the batched position report while a batching session is ongoing.</li> <li>– 0x00200000 - to receive Wi-Fi Access Point (AP) data inject request event indications.</li> <li>– 0x00400000 - to receive notifications when a Geofence is breached. These events are generated when a UE enters or leaves the perimeter of a Geofence. This breach notification is for multiple Geofences. Breaches from multiple Geofences are all batched and sent in the same notification.</li> <li>– 0x00800000 - to receive notifications from the location engine indicating its readiness to accept vehicle data (vehicle accelerometer, vehicle angular rate, vehicle odometry, etc.).</li> </ul> </li> </ul>
	<p style="text-align: right;">Generated on Tue Jul 12 2016 10:59:49 for LinuxQMISDK by Doxygen</p> <ul style="list-style-type: none"> <li>– 0x01000000 - to receive system clock and satellite measurement report events (system clock, <a href="#">SV</a> time, Doppler, etc.).</li> <li>– 0x02000000 - to receive satellite position reports as polynomials. Reports are generated only for the GNSS satellite constellations that are enabled using Q-</li> </ul>

**Note**

Multiple events can be registered by OR the individual masks and sending them in this TLV. All unused bits in this mask must be set to 0.

**Parameters**

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Pack result.</li></ul>
------------------	--

**8.488.2 Field Documentation**

8.488.2.1 uint64\_t pack\_loc\_EventRegister\_t::eventRegister

8.488.2.2 uint16\_t pack\_loc\_EventRegister\_t::Tlvresult

**8.489 pack\_loc\_SetExtPowerState\_t Struct Reference****Data Fields**

- uint32\_t [extPowerState](#)
- uint16\_t [Tlvresult](#)

**8.489.1 Detailed Description**

This structure contains the Parameter External Power Source State pack.

**Parameters**

<i>extPowerState</i>	<ul style="list-style-type: none"><li>• Specifies the Power state; injected by the control point.</li><li>• Values<ul style="list-style-type: none"><li>– 0 - Device is not connected to an external power source</li><li>– 1 - Device is connected to an external power source</li><li>– 2 - Unknown external power state</li></ul></li></ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Pack result.</li></ul>

**8.489.2 Field Documentation**

8.489.2.1 uint32\_t pack\_loc\_SetExtPowerState\_t::extPowerState

8.489.2.2 uint16\_t pack\_loc\_SetExtPowerState\_t::Tlvresult

**8.490 pack\_loc\_SetOperationMode\_t Struct Reference****Data Fields**

- uint32\_t [mode](#)

- uint16\_t [Tlvresult](#)

### 8.490.1 Detailed Description

This structure contains Set Operation Mode pack

#### Parameters

<i>mode</i>	<ul style="list-style-type: none"> <li>• 0 - Default Mode.</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Pack result.</li> </ul>

### 8.490.2 Field Documentation

8.490.2.1 uint32\_t pack\_loc\_SetOperationMode\_t::mode

8.490.2.2 uint16\_t pack\_loc\_SetOperationMode\_t::Tlvresult

## 8.491 pack\_loc\_Start\_t Struct Reference

### Data Fields

- uint8\_t [SessionId](#)
- uint32\_t \* [pRecurrenceType](#)
- uint32\_t \* [pHorizontalAccuracyLvl](#)
- uint32\_t \* [pIntermediateReportState](#)
- uint32\_t \* [pMinIntervalTime](#)
- loc\_LocApplicationInfo \* [pApplicationInfo](#)
- uint32\_t \* [pConfigAltitudeAssumed](#)
- uint16\_t [Tlvresult](#)

### 8.491.1 Detailed Description

This structure contains the LOC Start pack



## Parameters

<i>SessionId</i>	<ul style="list-style-type: none"> <li>• ID of the session as identified by the control point.</li> <li>• Range: 0 to 255</li> </ul>
<i>pRecurrence-Type</i>	<ul style="list-style-type: none"> <li>• Specifies the type of session in which the control point is interested.</li> <li>• Defaults to SINGLE. -Values <ul style="list-style-type: none"> <li>– 1 - Request periodic position fixes</li> <li>– 2 - Request a single position fix</li> </ul> </li> </ul>
<i>pHorizontal-AccuracyLvl</i>	<ul style="list-style-type: none"> <li>• Specifies the horizontal accuracy level required by the control point.</li> <li>• Defaults to LOW</li> <li>• Values <ul style="list-style-type: none"> <li>– 1 - Low accuracy</li> <li>– 2 - Medium accuracy</li> <li>– 3 - High accuracy</li> </ul> </li> </ul>
<i>pIntermediate-ReportState</i>	<ul style="list-style-type: none"> <li>• Specifies if the control point is interested in receiving intermediate reports.</li> <li>• ON by default.</li> <li>• Values <ul style="list-style-type: none"> <li>– 1 - Intermediate reports are turned on</li> <li>– 2 - Intermediate reports are turned off</li> </ul> </li> </ul>
<i>appVersionValid</i>	<ul style="list-style-type: none"> <li>• Specifies whether the application version string contains a valid value</li> <li>• 0x00 (FALSE) – Application version string is invalid</li> <li>• 0x01 (TRUE) – Application version string is valid</li> </ul>
<i>LocApplication-Info</i>	<ul style="list-style-type: none"> <li>• LOC Application Parameters</li> <li>• See <a href="#">loc_LocApplicationInfo</a> for more information</li> </ul>
<i>pConfigAltitude-Assumed</i>	<ul style="list-style-type: none"> <li>• Configuration for Altitude Assumed Info in GNSS <a href="#">SV</a> Info Event</li> <li>• Defaults to ENABLED.</li> <li>• Values <ul style="list-style-type: none"> <li>– 1 - Enable Altitude Assumed information in GNSS <a href="#">SV</a> Info Event</li> <li>– 2 - Disable Altitude Assumed information in GNSS <a href="#">SV</a> Info Event</li> </ul> </li> </ul>

## 8.491.2 Field Documentation

8.491.2.1 `loc_LocApplicationInfo*` `pack_loc_Start_t::pApplicationInfo`

8.491.2.2 `uint32_t*` `pack_loc_Start_t::pConfigAltitudeAssumed`

8.491.2.3 `uint32_t*` `pack_loc_Start_t::pHorizontalAccuracyLvl`

8.491.2.4 `uint32_t*` `pack_loc_Start_t::pIntermediateReportState`

8.491.2.5 `uint32_t*` `pack_loc_Start_t::pMinIntervalTime`

8.491.2.6 `uint32_t*` `pack_loc_Start_t::pRecurrenceType`

8.491.2.7 `uint8_t` `pack_loc_Start_t::SessionId`

8.491.2.8 `uint16_t` `pack_loc_Start_t::Tlvresult`

## 8.492 `pack_loc_Stop_t` Struct Reference

### Data Fields

- `uint8_t` [SessionId](#)
- `uint16_t` [Tlvresult](#)

### 8.492.1 Detailed Description

This structure contains Stop LOC pack

#### Parameters

<i>sessionId</i>	<ul style="list-style-type: none"> <li>• ID of the session as identified by the control point.</li> <li>• Range: 0 to 255</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack result.</li> </ul>

## 8.492.2 Field Documentation

8.492.2.1 `uint8_t` `pack_loc_Stop_t::SessionId`

8.492.2.2 `uint16_t` `pack_loc_Stop_t::Tlvresult`

## 8.493 `pack_nas_SetACCOLC_t` Struct Reference

### Data Fields

- `int8_t` [spc](#) [6]

- uint8\_t [accolc](#)

### 8.493.1 Detailed Description

#### Parameters

<i>spc</i>	servcie programming code
<i>accolc</i>	accolc

### 8.493.2 Field Documentation

8.493.2.1 uint8\_t pack\_nas\_SetACCOLC\_t::accolc

8.493.2.2 int8\_t pack\_nas\_SetACCOLC\_t::spc[6]

## 8.494 pack\_nas\_SetNetworkPreference\_t Struct Reference

#### Data Fields

- uint32\_t [TechnologyPref](#)
- uint32\_t [Duration](#)
- uint16\_t [Tlvresult](#)

### 8.494.1 Detailed Description

#### Parameters

<i>TechnologyPref</i> [IN]	<ul style="list-style-type: none"> <li>• Bitmask representing the radio technology preference set.</li> <li>• No bits set indicates to the device to automatically determine the technology to use</li> <li>• Values: <ul style="list-style-type: none"> <li>– Bit 0 - Technology is 3GPP2</li> <li>– Bit 1 - Technology is 3GPP</li> </ul> </li> <li>• Any combination of the following may be returned: <ul style="list-style-type: none"> <li>– Bit 2 - Analog - AMPS if 3GPP2, GSM if 3GPP</li> <li>– Bit 3 - Digital - CDMA if 3GPP2, WCDMA if 3GPP</li> <li>– Bit 4 - HDR</li> <li>– Bit 5 - LTE</li> <li>– Bits 6 to 15 - Reserved</li> </ul> </li> </ul>
-------------------------------	--

<i>Duration[IN]</i>	<ul style="list-style-type: none"> <li>• Duration of active preference <ul style="list-style-type: none"> <li>– 0 - Permanent</li> <li>– 1 - Power cycle</li> <li>– 2 - Until the end of the next call or a power cycle</li> <li>– 3 - Until the end of the next call, a specified time, or a power cycle</li> <li>– 4 to 6 - Until the end of the next call</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• pack result</li> </ul>

## 8.494.2 Field Documentation

8.494.2.1 uint32\_t pack\_nas\_SetNetworkPreference\_t::Duration

8.494.2.2 uint32\_t pack\_nas\_SetNetworkPreference\_t::TechnologyPref

8.494.2.3 uint16\_t pack\_nas\_SetNetworkPreference\_t::Tlvresult

## 8.495 pack\_nas\_SLQSGetPLMNName\_t Struct Reference

### Data Fields

- uint16\_t [mcc](#)
- uint16\_t [mnc](#)
- uint8\_t \* [pMncPcsStatus](#)

### 8.495.1 Detailed Description

#### Parameters

<i>mcc</i>	<ul style="list-style-type: none"> <li>• A 16-bit integer representation of MCC. Range: 0 to 999</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>• A 16-bit integer representation of MNC. Range: 0 to 999</li> </ul>
<i>pMncPcsStatus</i>	<ul style="list-style-type: none"> <li>• MNC PCS Digit Include Status</li> <li>• Used to interpret the length of the corresponding MNC reported in the PLMN TLV(0x01).</li> <li>• Values <ul style="list-style-type: none"> <li>– TRUE - MNC is a three-digit value. e.g. a reported value of 90 corresponds to an MNC value of 090</li> <li>– FALSE - MNC is a two-digit value. e.g. a reported value of 90 corresponds to an MNC value of 90</li> </ul> </li> </ul>

## Note

If pMncPcsStatus is not present, an MNC smaller than 100 is assumed to be a two-digit value, and an MNC greater than or equal to 100 is assumed to be a three digit value.

## 8.495.2 Field Documentation

8.495.2.1 uint16\_t pack\_nas\_SLQSGetPLMNName\_t::mcc

8.495.2.2 uint16\_t pack\_nas\_SLQSGetPLMNName\_t::mnc

8.495.2.3 uint8\_t\* pack\_nas\_SLQSGetPLMNName\_t::pMncPcsStatus

## 8.496 pack\_nas\_SLQSIInitiateNetworkRegistration\_t Struct Reference

## Data Fields

- uint32\_t [regAction](#)
- [nas\\_MNRInfo](#) \* [pMNRInfo](#)
- uint32\_t \* [pChangeDuration](#)
- uint8\_t \* [pMncPcsDigitStatus](#)

## 8.496.1 Detailed Description

This structure contains Initiate Network Registration request parameters

## Parameters

<i>regAction</i>	<ul style="list-style-type: none"> <li>• Specifies one of the following register actions : <ul style="list-style-type: none"> <li>– AUTO_REGISTER - Device registers according to its provisioning and optional parameters supplied with the command are ignored.</li> <li>– MANUAL_REGISTER - Device registers to a specified network and the optional Manual Network Register Information parameter pMNRInfo must also be included for the command to process successfully and supported only for 3GPP.</li> </ul> </li> </ul>
<i>pMNRInfo</i>	[Optional] <ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">MNRInfo</a> <ul style="list-style-type: none"> <li>– See <a href="#">nas_MNRInfo</a> for more information</li> </ul> </li> </ul>
<i>pChange-Duration</i>	[Optional] <ul style="list-style-type: none"> <li>• Duration of the change. <ul style="list-style-type: none"> <li>– 0x00 - Power cycle - Remains active until the next device power cycle</li> <li>– 0x01 - Permanent - Remains active through power cycles until changed by the client</li> </ul> </li> </ul>

<i>pMncPcsDigit-Status</i>	[Optional] <ul style="list-style-type: none"> <li>• MNC PCS Digit Include Status             <ul style="list-style-type: none"> <li>– True - MNC is a 3-digit value.</li> <li>– False - MNC is a 2-digit value.</li> </ul> </li> </ul>
----------------------------	--

## 8.496.2 Field Documentation

8.496.2.1 uint32\_t\* pack\_nas\_SLQSIInitiateNetworkRegistration\_t::pChangeDuration

8.496.2.2 uint8\_t\* pack\_nas\_SLQSIInitiateNetworkRegistration\_t::pMncPcsDigitStatus

8.496.2.3 nas\_MNRInfo\* pack\_nas\_SLQSIInitiateNetworkRegistration\_t::pMNRInfo

8.496.2.4 uint32\_t pack\_nas\_SLQSIInitiateNetworkRegistration\_t::regAction

## 8.497 pack\_nas\_SLQSNasConfigSigInfo2\_t Struct Reference

### Data Fields

- [nas\\_CDMARSSIThresh](#) \* [pCDMARSSIThresh](#)
- [uint16\\_t](#) \* [pCDMARSSIDelta](#)
- [nas\\_CDMAECIOThresh](#) \* [pCDMAECIOThresh](#)
- [uint16\\_t](#) \* [pCDMAECIODelta](#)
- [nas\\_HDRRSSIThresh](#) \* [pHDRRSSIThresh](#)
- [uint16\\_t](#) \* [pHDRRSSIDelta](#)
- [nas\\_HDRECIOThresh](#) \* [pHDRECIOThresh](#)
- [uint16\\_t](#) \* [pHDRECIODelta](#)
- [nas\\_HDRSINRThreshold](#) \* [pHDRSINRThreshold](#)
- [uint16\\_t](#) \* [pHDRSINRDelta](#)
- [nas\\_HDRIOThresh](#) \* [pHDRIOThresh](#)
- [uint16\\_t](#) \* [pHDRIODelta](#)
- [nas\\_GSMRSSIThresh](#) \* [pGSMRSSIThresh](#)
- [uint16\\_t](#) \* [pGSMRSSIDelta](#)
- [nas\\_WCDMARSSIThresh](#) \* [pWCDMARSSIThresh](#)
- [uint16\\_t](#) \* [pWCDMARSSIDelta](#)
- [nas\\_WCDMAECIOThresh](#) \* [pWCDMAECIOThresh](#)
- [uint16\\_t](#) \* [pWCDMAECIODelta](#)
- [nas\\_LTERSSIThresh](#) \* [pLTERSSIThresh](#)
- [uint16\\_t](#) \* [pLTERSSIDelta](#)
- [nas\\_LTESNRThreshold](#) \* [pLTESNRThreshold](#)
- [uint16\\_t](#) \* [pLTESNRDelta](#)
- [nas\\_LTERSRQThresh](#) \* [pLTERSRQThresh](#)
- [uint16\\_t](#) \* [pLTERSRQDelta](#)
- [nas\\_LTERSRPThresh](#) \* [pLTERSRPThresh](#)
- [uint16\\_t](#) \* [pLTERSRPDelta](#)
- [nas\\_LTESigRptConfig](#) \* [pLTESigRptConfig](#)
- [nas\\_TDSCDMARSCPTThresh](#) \* [pTDSCDMARSCPTThresh](#)
- [uint16\\_t](#) \* [pTDSCDMARSCPDelta](#)
- [nas\\_TDSCDMARSSIThresh](#) \* [pTDSCDMARSSIThresh](#)
- [float](#) \* [pTDSCDMARSSIDelta](#)
- [nas\\_TDSCDMAECIOThresh](#) \* [pTDSCDMAECIOThresh](#)

- float \* [pTDSCDMAECIODelta](#)
- [nas\\_TDSCDMASINRThresh](#) \* [pTDSCDMASINRThresh](#)
- float \* [pTDSCDMASINRDelta](#)

### 8.497.1 Detailed Description

#### Parameters

<i>pCDMARSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• CDMA RSSI threshold List</li> </ul>
<i>pCDMARSSI- Delta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm).</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pCDMAECIO- Thresh</i>	<ul style="list-style-type: none"> <li>• CDMA ECIO Threshold List</li> </ul>
<i>pCDMAECIO- Delta</i>	<ul style="list-style-type: none"> <li>• ECIO delta (in units of 0.1 dB).</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pHDRRSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• HDR RSSI Threshold List</li> </ul>
<i>pHDRRSSIDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pHDRECI- Thresh</i>	<ul style="list-style-type: none"> <li>• HDR ECIO Threshold List</li> </ul>
<i>pHDRECIODelta</i>	<ul style="list-style-type: none"> <li>• ECIO delta (in units of 0.1 dB)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pHDRSINR- Thresh</i>	<ul style="list-style-type: none"> <li>• HDR SINR Threshold List</li> </ul>
<i>pHDRSINRDelta</i>	<ul style="list-style-type: none"> <li>• SINR delta (in units of 1 SINR level)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pHDRIOTresh</i>	<ul style="list-style-type: none"> <li>• HDR IO Threshold List</li> </ul>
<i>pHDRIODelta</i>	<ul style="list-style-type: none"> <li>• IO delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>



<i>pGSMRSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• GSM RSSI Threshold List</li> <li>• See <a href="#">GSMRSSIThresh</a> for more details</li> </ul>
<i>pGSMRSSIDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pWCDMARSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• WCDMA RSSI Threshold List</li> <li>• See <a href="#">WCDMARSSIThresh</a> for more details</li> </ul>
<i>pWCDMARSSI- Delta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm).</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pWCDMAECIO- Thresh</i>	<ul style="list-style-type: none"> <li>• WCDMA ECIO Threshold List</li> </ul>
<i>pWCDMAECIO- Delta</i>	<ul style="list-style-type: none"> <li>• ECIO delta (in units of 0.1 dB)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• LTE RSSI Threshold List</li> </ul>
<i>pLTERSSIDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSNR- Thresh</i>	<ul style="list-style-type: none"> <li>• LTE SNR Threshold List</li> </ul>
<i>pLTERSNRDelta</i>	<ul style="list-style-type: none"> <li>• SNR delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSRQ- Thresh</i>	<ul style="list-style-type: none"> <li>• LTE RSRQ Threshold List</li> </ul>
<i>pLTERSRQ- Delta</i>	<ul style="list-style-type: none"> <li>• RSRQ delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSRP- Thresh</i>	<ul style="list-style-type: none"> <li>• LTE RSRP Threshold List</li> </ul>

<i>pLTERSRPDelta</i>	<ul style="list-style-type: none"> <li>• RSRP delta (in units of 0.1 dBm).</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSigRpt-Config</i>	<ul style="list-style-type: none"> <li>• LTE Signal Report Config</li> </ul>
<i>pTDSCDMARS-CPThresh</i>	<ul style="list-style-type: none"> <li>• TDSCDMA RSCP Threshold List</li> </ul>
<i>pTDSCDMARS-CPDelta</i>	<ul style="list-style-type: none"> <li>• RSCP delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pTDSCDMARS-SIThresh</i>	<ul style="list-style-type: none"> <li>• TDSCDMA RSSI Threshold List</li> </ul>
<i>pTDSCDMARS-SIDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in dBm) used by TD-SCDMA.</li> </ul>
<i>pTDSCDMAECIOThresh</i>	<ul style="list-style-type: none"> <li>• TDSCDMA ECIO Threshold List</li> </ul>
<i>pTDSCDMAECIODelta</i>	<ul style="list-style-type: none"> <li>• ECIO delta (in dB) used by TD-SCDMA</li> </ul>
<i>pTDSCDMASIN-RThresh</i>	<ul style="list-style-type: none"> <li>• TDSCDMA SINR Threshold List</li> </ul>
<i>pTDSCDMASIN-RDelta</i>	<ul style="list-style-type: none"> <li>• SINR delta (in dB) used by TD-SCDMA.</li> </ul>

## 8.497.2 Field Documentation

8.497.2.1 `uint16_t* pack_nas_SLQSNasConfigSigInfo2_t::pCDMAECIODelta`

8.497.2.2 `nas_CDMAECIOThresh* pack_nas_SLQSNasConfigSigInfo2_t::pCDMAECIOThresh`

8.497.2.3 `uint16_t* pack_nas_SLQSNasConfigSigInfo2_t::pCDMARSSIDelta`

8.497.2.4 `nas_CDMARSSIThresh* pack_nas_SLQSNasConfigSigInfo2_t::pCDMARSSIThresh`

8.497.2.5 `uint16_t* pack_nas_SLQSNasConfigSigInfo2_t::pGSMRSSIDelta`

8.497.2.6 `nas_GSMRSSIThresh* pack_nas_SLQSNasConfigSigInfo2_t::pGSMRSSIThresh`

8.497.2.7 `uint16_t* pack_nas_SLQSNasConfigSigInfo2_t::pHDRECIODelta`

8.497.2.8 `nas_HDRECIOThresh* pack_nas_SLQSNasConfigSigInfo2_t::pHDRECIOThresh`

- 8.497.2.9 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pHDRIODelta
- 8.497.2.10 nas\_HDRIOTresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pHDRIOTresh
- 8.497.2.11 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pHRRSSIDelta
- 8.497.2.12 nas\_HRRSSITresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pHRRSSITresh
- 8.497.2.13 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pHRSINRDelta
- 8.497.2.14 nas\_HRSINRThreshold\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pHRSINRThresh
- 8.497.2.15 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTERSRPDelta
- 8.497.2.16 nas\_LTERSRPThresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTERSRPThresh
- 8.497.2.17 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTERSRQDelta
- 8.497.2.18 nas\_LTERSRQThresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTERSRQThresh
- 8.497.2.19 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTERSSIDelta
- 8.497.2.20 nas\_LTERSSITresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTERSSITresh
- 8.497.2.21 nas\_LTESigRptConfig\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTESigRptConfig
- 8.497.2.22 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTESNRDelta
- 8.497.2.23 nas\_LTESNRThreshold\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pLTESNRThresh
- 8.497.2.24 float\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pTDSCDMAECIODelta
- 8.497.2.25 nas\_TDSCDMAECIOThresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pTDSCDMAECIOThresh
- 8.497.2.26 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pTDSCDMARSCPDelta
- 8.497.2.27 nas\_TDSCDMARSCPThresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pTDSCDMARSCPThresh
- 8.497.2.28 float\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pTDSCDMARSSIDelta
- 8.497.2.29 nas\_TDSCDMARSSITresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pTDSCDMARSSITresh
- 8.497.2.30 float\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pTDSCDMASINRDelta
- 8.497.2.31 nas\_TDSCDMASINRThresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pTDSCDMASINRThresh
- 8.497.2.32 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pWCMAECIODelta
- 8.497.2.33 nas\_WCMAECIOThresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pWCMAECIOThresh
- 8.497.2.34 uint16\_t\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pWCDMARSSIDelta
- 8.497.2.35 nas\_WCDMARSSITresh\* pack\_nas\_SLQSNasConfigSigInfo2\_t::pWCDMARSSITresh

## 8.498 pack\_nas\_SLQSNasIndicationRegisterExt\_t Struct Reference

## Data Fields

- uint8\_t \* [pSystemSelectionInd](#)
- uint8\_t \* [pDDTMInd](#)
- uint8\_t \* [pServingSystemInd](#)
- uint8\_t \* [pDualStandByPrefInd](#)
- uint8\_t \* [pSubscriptionInfoInd](#)
- uint8\_t \* [pNetworkTimeInd](#)
- uint8\_t \* [pSysInfoInd](#)
- uint8\_t \* [pSignalStrengthInd](#)
- uint8\_t \* [pErrorRateInd](#)
- uint8\_t \* [pHDRNewUATIAssInd](#)
- uint8\_t \* [pHDRSessionCloseInd](#)
- uint8\_t \* [pManagedRoamingInd](#)
- uint8\_t \* [pLTECphyCa](#)

### 8.498.1 Detailed Description

#### Parameters

<i>pSystem-SelectionInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>System Selection Preference indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNRoamingIndicator</a> <a href="#">tFNDataCapabilities</a> and <a href="#">tFNServingSystem</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pDDTMInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>DDTM (Data Dedicated Transmission Mode) indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNDDTM</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pServing-SystemInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Serving System indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p><a href="#">tFNBandPreference</a></p> <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>

<i>pDualStandBy-PrefInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Dual Standby Preference indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p>tFNDualStandByPref</p> <ul style="list-style-type: none"> <li>0x00 - Disable</li> <li>0x01 - Enable</li> </ul>
<i>pSubscription-InfoInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Subscription Information indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p>tFNSubscriptionInfo</p> <ul style="list-style-type: none"> <li>0x00 - Disable</li> <li>0x01 - Enable</li> </ul>
<i>pNetworkTime-Ind</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Network Time indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p>tFNNetworkTime</p> <ul style="list-style-type: none"> <li>0x00 - Disable</li> <li>0x01 - Enable</li> </ul>
<i>pSysInfoInd</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>System Information indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p>tFNSysInfo</p> <ul style="list-style-type: none"> <li>0x00 - Disable</li> <li>0x01 - Enable</li> </ul>
<i>pSignalStrength-Ind</i>	<p>[Optional]</p> <ul style="list-style-type: none"> <li>Signal Strength indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> <p>tFNSigInfo</p> <ul style="list-style-type: none"> <li>0x00 - Disable</li> <li>0x01 - Enable</li> </ul>

<i>pErrorRateInd</i>	[Optional] <ul style="list-style-type: none"> <li>Error Rate indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> tFNErrRate <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pHDRNewUATI-AssInd</i>	[Optional] <ul style="list-style-type: none"> <li>HDR New UATI Assigned indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> tFNHDRUATIUpdate <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pHDRSession-CloseInd</i>	[Optional] <ul style="list-style-type: none"> <li>HDR Session Closed indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> tFNHDRSessionClose <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pManaged-RoamingInd</i>	[Optional] <ul style="list-style-type: none"> <li>Managed Roaming indication registration. The following callbacks would not be invoked if the indication is disabled.</li> </ul> tFNManagedRoaming <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul>
<i>pLTECphyCa</i>	[Optional] <ul style="list-style-type: none"> <li>LTE Physical Carrier Aggregation Information. The following callbacks would not be invoked if the indication is disabled.</li> </ul> tFNManagedRoaming <ul style="list-style-type: none"> <li>– 0x00 - Disable (default value)</li> <li>– 0x01 - Enable</li> </ul>

## 8.498.2 Field Documentation

8.498.2.1 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pDDTMInd

8.498.2.2 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pDualStandByPrefInd

8.498.2.3 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pErrorRateInd

8.498.2.4 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pHDRNewUATIAssInd

- 8.498.2.5 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pHDRSessionCloseInd
- 8.498.2.6 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pLTECphyCa
- 8.498.2.7 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pManagedRoamingInd
- 8.498.2.8 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pNetworkTimeInd
- 8.498.2.9 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pServingSystemInd
- 8.498.2.10 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pSignalStrengthInd
- 8.498.2.11 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pSubscriptionInfoInd
- 8.498.2.12 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pSysInfoInd
- 8.498.2.13 uint8\_t\* pack\_nas\_SLQSNasIndicationRegisterExt\_t::pSystemSelectionInd

## 8.499 pack\_nas\_SLQSNasSwiOTAMessageCallback\_t Struct Reference

### Data Fields

- uint8\_t [lteEsmUI](#)
- uint8\_t [lteEsmDI](#)
- uint8\_t [lteEmmUI](#)
- uint8\_t [lteEmmDI](#)
- uint8\_t [gsmUmtsUI](#)
- uint8\_t [gsmUmtsDI](#)
- uint8\_t \* [pRankIndicatorInd](#)

### 8.499.1 Detailed Description

This structure contains the OTA message indication.

#### Parameters

<i>lteEsmUI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report LTE ESM uplink messages</li> </ul>
<i>lteEsmDI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report LTE ESM downlink messages</li> </ul>
<i>lteEmmUI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report LTE EMM uplink messages</li> </ul>

<i>lteEmmDI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report GSM/UMTS uplink messages</li> </ul>
<i>gsmUmtsUI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report GSM/UMTS uplink messages</li> </ul>
<i>gsmUmtsDI</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report GSM/UMTS downlink messages</li> </ul>
<i>pRankIndicator- Ind</i>	<ul style="list-style-type: none"> <li>• 0 - do not report</li> <li>• 1 - report Rank Indicator messages</li> </ul>

## 8.499.2 Field Documentation

8.499.2.1 `uint8_t pack_nas_SLQSNasSwiOTAMessageCallback_t::gsmUmtsDI`

8.499.2.2 `uint8_t pack_nas_SLQSNasSwiOTAMessageCallback_t::gsmUmtsUI`

8.499.2.3 `uint8_t pack_nas_SLQSNasSwiOTAMessageCallback_t::lteEmmDI`

8.499.2.4 `uint8_t pack_nas_SLQSNasSwiOTAMessageCallback_t::lteEmmUI`

8.499.2.5 `uint8_t pack_nas_SLQSNasSwiOTAMessageCallback_t::lteEsmDI`

8.499.2.6 `uint8_t pack_nas_SLQSNasSwiOTAMessageCallback_t::lteEsmUI`

8.499.2.7 `uint8_t* pack_nas_SLQSNasSwiOTAMessageCallback_t::pRankIndicatorInd`

## 8.500 `pack_nas_SLQSSetSignalStrengthsCallback_t` Struct Reference

### Data Fields

- `uint8_t bEnable`
- `nas_SLQSSignalStrengthsIndReq * pSigIndReq`

### 8.500.1 Detailed Description

#### Parameters

<i>bEnable</i>	0/1 to disable/enable RSSI signal strength indication
<i>pSigIndReq</i>	parameters to control signal strength indication

### 8.500.2 Field Documentation



8.500.2.1 uint8\_t pack\_nas\_SLQSSetSignalStrengthsCallback\_t::bEnable

8.500.2.2 nas\_SLQSSignalStrengthsIndReq\* pack\_nas\_SLQSSetSignalStrengthsCallback\_t::pSigIndReq

## 8.501 pack\_nas\_SLQSSetSysSelectionPref\_t Struct Reference

### Data Fields

- uint8\_t \* pEmerMode
- uint16\_t \* pModePref
- uint64\_t \* pBandPref
- uint16\_t \* pPRLPref
- uint16\_t \* pRoamPref
- uint64\_t \* pLTEBandPref
- struct nas\_netSelectionPref \* pNetSelPref
- uint8\_t \* pChgDuration
- uint8\_t \* pMNCIncPCSDigStat
- uint32\_t \* pSrvDomainPref
- uint32\_t \* pGWAcqOrderPref
- uint64\_t \* pTdsdmaBandPref
- struct nas\_acqOrderPref \* pAcqOrderPref
- uint32\_t \* pSrvRegRestriction
- struct nas\_CSGID \* pCSGID
- unsigned char \* pRAT

### 8.501.1 Detailed Description

Contain the system selection preferences.

## Parameters

<i>pEmerMode</i>	<ul style="list-style-type: none"> <li>• Optional parameter specifying the emergency Mode</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - OFF (normal)</li> <li>– 1 - ON (Emergency)</li> </ul> </li> </ul>
<i>pModePref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit Mask indicating the radio technology mode preference</li> <li>• Bit values: <ul style="list-style-type: none"> <li>– Bit 0 - cdma2000 1x</li> <li>– Bit 1 - cdma2000 HRPD(1xEV-DO)</li> <li>– Bit 2 - GSM</li> <li>– Bit 3 - UMTS</li> <li>– Bit 4 - LTE</li> </ul> </li> </ul>
<i>pBandPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit mask representing the band preference</li> <li>• Bit values: <ul style="list-style-type: none"> <li>– Bit 0 - Band Class 0, A-System</li> <li>– Bit 1 - Band Class 0, B-System, Band Class 0 AB, GSM 850 Band</li> <li>– Bit 2 - Band Class 1, all blocks</li> <li>– Bit 3 - Band Class 2 place holder</li> <li>– Bit 4 - Band Class 3, A-System</li> <li>– Bit 5 - Band Class 4, all blocks</li> <li>– Bit 6 - Band Class 5, all blocks</li> <li>– Bit 7 - GSM_DCS_1800 band</li> <li>– Bit 8 - GSM Extended GSM (E-GSM) 900 band</li> <li>– Bit 9 - GSM Primary GSM (P-GSM) 900 band</li> <li>– Bit 10 - Band Class 6</li> <li>– Bit 11 - Band Class 7</li> <li>– Bit 12 - Band Class 8</li> <li>– Bit 13 - Band Class 9</li> <li>– Bit 14 - Band Class 10</li> <li>– Bit 15 - Band Class 11</li> <li>– Bit 16 - GSM 450 band</li> <li>– Bit 17 - GSM 480 band</li> <li>– Bit 18 - GSM 750 band</li> <li>– Bit 19 - GSM 850 band</li> <li>– Bit 20 - GSM Railways GSM 900 Band</li> <li>– Bit 21 - GSM PCS 1900 band</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– Bit 22 - WCDMA Europe, Japan, and China IMT 2100 band</li> <li>– Bit 23 - WCDMA U.S. PCS 1900 band</li> <li>– Bit 24 - WCDMA Europe and China DCS 1800 band</li> </ul>

<i>pPRLPref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating the CDMA PRL Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x0001 - Acquire available system only on the A side</li> <li>0x0002 - Acquire available system only on the B side</li> <li>0x3FFF - Acquire any available systems</li> </ul> </li> </ul>
<i>pRoamPref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating the roaming Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x01 - Acquire only systems for which the roaming indicator is off</li> <li>0x02 - Acquire a system as long as its roaming indicator is not off</li> <li>0x03 - Acquire only systems for which the roaming indicator is off or solid on, i.e. not flashing; CDMA only</li> <li>0xFF - Acquire systems, regardless of their roaming indicator</li> </ul> </li> </ul>
<i>pLTEBandPref</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Bit mask representing the LTE band preference</li> <li>Bit Values <ul style="list-style-type: none"> <li>Bit 0 - E-UTRA Operating Band 1</li> <li>Bit 1 - E-UTRA Operating Band 2</li> <li>Bit 2 - E-UTRA Operating Band 3</li> <li>Bit 3 - E-UTRA Operating Band 4</li> <li>Bit 4 - E-UTRA Operating Band 5</li> <li>Bit 5 - E-UTRA Operating Band 6</li> <li>Bit 6 - E-UTRA Operating Band 7</li> <li>Bit 7 - E-UTRA Operating Band 8</li> <li>Bit 8 - E-UTRA Operating Band 9</li> <li>Bit 9 - E-UTRA Operating Band 10</li> <li>Bit 10 - E-UTRA Operating Band 11</li> <li>Bit 11 - E-UTRA Operating Band 12</li> <li>Bit 12 - E-UTRA Operating Band 13</li> <li>Bit 13 - E-UTRA Operating Band 14</li> <li>Bit 16 - E-UTRA Operating Band 17</li> <li>Bit 17 - E-UTRA Operating Band 18</li> <li>Bit 18 - E-UTRA Operating Band 19</li> <li>Bit 19 - E-UTRA Operating Band 20</li> <li>Bit 20 - E-UTRA Operating Band 21</li> <li>Bit 32 - E-UTRA Operating Band 33</li> <li>Bit 33 - E-UTRA Operating Band 34</li> <li>Bit 34 - E-UTRA Operating Band 35</li> <li>Bit 35 - E-UTRA Operating Band 36</li> <li>Bit 36 - E-UTRA Operating Band 37</li> <li>Bit 37 - E-UTRA Operating Band 38</li> <li>Bit 38 - E-UTRA Operating Band 39</li> <li>Bit 39 - E-UTRA Operating Band 40</li> </ul> </li> </ul>

<i>pNetSelPref</i>	<ul style="list-style-type: none"> <li>- <a href="#">netSelectionPref</a></li> <li>• Optional parameter for specifying Network Selection Preference</li> <li>• Modem selects networks based on this parameter(if present).</li> <li>• see <a href="#">netSelectionPref</a> for more information</li> </ul>
<i>pChgDuration</i>	<ul style="list-style-type: none"> <li>• Optional parameter specifying the duration of the change</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Power cycle - Remains active until the next device power cycle</li> <li>– 0x01 - Permanent - Remains active through power cycles until changed by client</li> <li>– Device will use "0x01 - permanent" as default if this parameter is omitted</li> </ul> </li> </ul>
<i>pMNCIncPCS-DigStat</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating if MNC includes PCS digit</li> <li>• Values: <ul style="list-style-type: none"> <li>– TRUE - MNC is a 3 digit value; e.g., a reported value of 90 corresponds to an MNC value of 090</li> <li>– FALSE - MNC is a 2-digit value; e.g., a reported value of 90 corresponds to an MNC value of 90</li> </ul> </li> </ul>
<i>pSrvDomainPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating Service domain preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Circuit switched only</li> <li>– 0x01 - Packet switched only</li> <li>– 0x02 - Circuit switched and packet switched</li> <li>– 0x03 - Packet switched attach</li> <li>– 0x04 - Packet switched detach</li> </ul> </li> </ul>
<i>pGWAcqOrder-Pref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating GSM/WCDMA Acquisition order Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Automatic</li> <li>– 0x01 - GSM then WCDMA</li> <li>– 0x02 - WCDMA then GSM</li> </ul> </li> </ul>

## 8.501.2 Field Documentation

8.501.2.1 struct nas\_acqOrderPref\* pack\_nas\_SLQSSetSysSelectionPref\_t::pAcqOrderPref

8.501.2.2 uint64\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pBandPref

- 8.501.2.3 uint8\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pChgDuration
- 8.501.2.4 struct nas\_CSGID\* pack\_nas\_SLQSSetSysSelectionPref\_t::pCSGID
- 8.501.2.5 uint8\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pEmerMode
- 8.501.2.6 uint32\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pGWAcqOrderPref
- 8.501.2.7 uint64\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pLTEBandPref
- 8.501.2.8 uint8\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pMNCIncPCSDigStat
- 8.501.2.9 uint16\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pModePref
- 8.501.2.10 struct nas\_netSelectionPref\* pack\_nas\_SLQSSetSysSelectionPref\_t::pNetSelPref
- 8.501.2.11 uint16\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pPRLPref
- 8.501.2.12 unsigned char\* pack\_nas\_SLQSSetSysSelectionPref\_t::pRAT
- 8.501.2.13 uint16\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pRoamPref
- 8.501.2.14 uint32\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pSrvDomainPref
- 8.501.2.15 uint32\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pSrvRegRestriction
- 8.501.2.16 uint64\_t\* pack\_nas\_SLQSSetSysSelectionPref\_t::pTdscdmaBandPref

## 8.502 pack\_qmi\_t Struct Reference

### Data Fields

- uint16\_t [xid](#)
- int [timeout](#)
- uint16\_t [msgid](#)
- uint8\_t [svc](#)

### 8.502.1 Detailed Description

qmi request context

#### Parameters

in	<i>xid</i>	transaction id
out	<i>timeout</i>	timeout recommended in seconds
out	<i>msgid</i>	message id
out	<i>svc</i>	qmi service

### 8.502.2 Field Documentation

8.502.2.1 uint16\_t pack\_qmi\_t::msgid

8.502.2.2 uint8\_t pack\_qmi\_t::svc

8.502.2.3 int pack\_qmi\_t::timeout

8.502.2.4 uint16\_t pack\_qmi\_t::xid

## 8.503 pack\_qos\_SLQSQosSwiReadApnExtraParams\_t Struct Reference

### Data Fields

- uint32\_t [apnId](#)

### 8.503.1 Detailed Description

Structure that contains the APN ID to obtain extra APN parameters

#### Parameters

<i>apnId</i> [IN]	<ul style="list-style-type: none"> <li>• APN id</li> </ul>
-------------------	--

### 8.503.2 Field Documentation

8.503.2.1 uint32\_t pack\_qos\_SLQSQosSwiReadApnExtraParams\_t::apnId

## 8.504 pack\_qos\_SLQSQosSwiReadDataStats\_t Struct Reference

### Data Fields

- uint32\_t [apnId](#)

### 8.504.1 Detailed Description

Structure that contains the APN ID to obtain data statistics

#### Parameters

<i>apnId</i> [IN]	<ul style="list-style-type: none"> <li>• APN id</li> </ul>
-------------------	--

### 8.504.2 Field Documentation

8.504.2.1 uint32\_t pack\_qos\_SLQSQosSwiReadDataStats\_t::apnId

## 8.505 pack\_qos\_SLQSSetQosEventCallback\_t Struct Reference

### Data Fields

- uint8\_t [enable](#)

### 8.505.1 Detailed Description

Structure that contains the APN ID to obtain data statistics

## Parameters

<i>enable</i> [IN]	<ul style="list-style-type: none"> <li>• 1 - Enable QoS event reporting</li> <li>• 0 - Disable QoS event reporting</li> </ul>
--------------------	---

## 8.505.2 Field Documentation

8.505.2.1 uint8\_t pack\_qos\_SLQSSetQosEventCallback\_t::enable

## 8.506 pack\_sms\_SendSMS\_t Struct Reference

## Data Fields

- uint32\_t [messageFormat](#)
- uint32\_t [messageSize](#)
- uint8\_t \* [pMessage](#)
- uint8\_t \* [pLinktimer](#)

## 8.506.1 Detailed Description

## Parameters

<i>messageFormat</i>	<ul style="list-style-type: none"> <li>• Message format <ul style="list-style-type: none"> <li>– 0 - CDMA (IS-637B)</li> <li>– 1 - 5 (Reserved)</li> <li>– 6 - GSM/WCDMA PP</li> </ul> </li> </ul>
<i>messageSize</i>	<ul style="list-style-type: none"> <li>• The length of the message contents in bytes</li> </ul>
<i>pLinktimer</i>	<ul style="list-style-type: none"> <li>• GW SMS link open for the specified number of second</li> </ul>
<i>pMessage</i>	<ul style="list-style-type: none"> <li>• The message contents in PDU format contains SMS header and payload message</li> </ul>

## 8.506.2 Field Documentation

8.506.2.1 uint32\_t pack\_sms\_SendSMS\_t::messageFormat

8.506.2.2 uint32\_t pack\_sms\_SendSMS\_t::messageSize

8.506.2.3 uint8\_t\* pack\_sms\_SendSMS\_t::pLinktimer

8.506.2.4 uint8\_t\* pack\_sms\_SendSMS\_t::pMessage



## 8.507 pack\_sms\_SetNewSMSCallback\_t Struct Reference

### Data Fields

- enum [eqmiCbkJSetStatus](#) *status*

### 8.507.1 Detailed Description

#### Parameters

<i>status</i>	callback parameter
---------------	--------------------

### 8.507.2 Field Documentation

8.507.2.1 enum [eqmiCbkJSetStatus](#) pack\_sms\_SetNewSMSCallback\_t::*status*

## 8.508 pack\_sms\_SLQSDDeleteSMS\_t Struct Reference

### Data Fields

- uint32\_t [storageType](#)
- uint32\_t \* [pMessageIndex](#)
- uint32\_t \* [pMessageTag](#)
- uint8\_t \* [pMessageMode](#)

### 8.508.1 Detailed Description

#### Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>• SMS message storage type <ul style="list-style-type: none"> <li>– 0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>– 1 - NV</li> </ul> </li> </ul>
<i>pMessageIndex</i>	<ul style="list-style-type: none"> <li>• (Optional) message index</li> </ul>
<i>pMessageTag</i>	<ul style="list-style-type: none"> <li>• (Optional) message tag <ul style="list-style-type: none"> <li>– 0 - Read</li> <li>– 1 - Not read</li> <li>– 2 - Mobile originated and sent</li> <li>– 3 - Mobile originated but not yet sent</li> </ul> </li> </ul>

<i>pMessageMode</i>	<ul style="list-style-type: none"> <li>• (Optional) message mode</li> <li>• this must be included if the device is capable of supporting more than one protocol</li> <li>• e.g. CDMA and GW <ul style="list-style-type: none"> <li>– 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>– 0x01 - GW, LTE (if network type is UMTS)</li> </ul> </li> </ul>
---------------------	--

## 8.508.2 Field Documentation

8.508.2.1 `uint32_t* pack_sms_SLQSDDeleteSMS_t::pMessageIndex`

8.508.2.2 `uint8_t* pack_sms_SLQSDDeleteSMS_t::pMessageMode`

8.508.2.3 `uint32_t* pack_sms_SLQSDDeleteSMS_t::pMessageTag`

8.508.2.4 `uint32_t pack_sms_SLQSDDeleteSMS_t::storageType`

## 8.509 pack\_sms\_SLQSGetSMS\_t Struct Reference

### Data Fields

- `uint32_t` [storageType](#)
- `uint32_t` [messageIndex](#)
- `uint8_t *` [pMessageMode](#)

### 8.509.1 Detailed Description

#### Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>• SMS message storage type <ul style="list-style-type: none"> <li>– 0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>– 1 - NV</li> </ul> </li> </ul>
<i>messageIndex</i>	<ul style="list-style-type: none"> <li>• Message index</li> </ul>
<i>pMessageMode</i>	<ul style="list-style-type: none"> <li>• 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>• 0x01 - GW, LTE (if network type is UMTS)</li> </ul>

## 8.509.2 Field Documentation

8.509.2.1 `uint32_t pack_sms_SLQSGetSMS_t::messageIndex`

8.509.2.2 uint8\_t\* pack\_sms\_SLQSGetSMS\_t::pMessageMode

8.509.2.3 uint32\_t pack\_sms\_SLQSGetSMS\_t::storageType

## 8.510 pack\_sms\_SLQSGetSMSList\_t Struct Reference

### Data Fields

- uint32\_t [storageType](#)
- uint32\_t \* [pRequestedTag](#)
- uint8\_t \* [pMessageMode](#)

### 8.510.1 Detailed Description

#### Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>• SMS message storage type <ul style="list-style-type: none"> <li>– 0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>– 1 - NV</li> </ul> </li> </ul>
<i>requestedTag</i>	<ul style="list-style-type: none"> <li>• (Optional) Message tag <ul style="list-style-type: none"> <li>– 0 - Read</li> <li>– 1 - Not read</li> <li>– 2 - Mobile originated and sent</li> <li>– 3 - Mobile originated but not yet sent</li> </ul> </li> </ul>
<i>messageMode</i>	<ul style="list-style-type: none"> <li>• 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>• 0x01 - GW, LTE (if network type is UMTS)</li> </ul>

### 8.510.2 Field Documentation

8.510.2.1 uint8\_t\* pack\_sms\_SLQSGetSMSList\_t::pMessageMode

8.510.2.2 uint32\_t\* pack\_sms\_SLQSGetSMSList\_t::pRequestedTag

8.510.2.3 uint32\_t pack\_sms\_SLQSGetSMSList\_t::storageType

## 8.511 pack\_sms\_SLQSMModifySMSStatus\_t Struct Reference

### Data Fields

- uint32\_t [storageType](#)
- uint32\_t [messageIndex](#)
- uint32\_t [messageTag](#)

- `uint8_t * pMessageMode`

### 8.511.1 Detailed Description

#### Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>• SMS message storage type <ul style="list-style-type: none"> <li>– 0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>– 1 - NV</li> </ul> </li> </ul>
<i>messageIndex</i>	<ul style="list-style-type: none"> <li>• Message index</li> </ul>
<i>messageTag</i>	<ul style="list-style-type: none"> <li>• Message tag <ul style="list-style-type: none"> <li>– 0 - Read</li> <li>– 1 - Not read</li> </ul> </li> </ul>
<i>pMessageMode</i>	<ul style="list-style-type: none"> <li>• 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>• 0x01 - GW, LTE (if network type is UMTS)</li> </ul>

### 8.511.2 Field Documentation

8.511.2.1 `uint32_t pack_sms_SLQSMModifySMSStatus_t::messageIndex`

8.511.2.2 `uint32_t pack_sms_SLQSMModifySMSStatus_t::messageTag`

8.511.2.3 `uint8_t* pack_sms_SLQSMModifySMSStatus_t::pMessageMode`

8.511.2.4 `uint32_t pack_sms_SLQSMModifySMSStatus_t::storageType`

## 8.512 `pack_swiloc_SwiLocSetAutoStart_t` Struct Reference

#### Data Fields

- `uint8_t function`
- `int set_function`
- `uint8_t fix_type`
- `int set_fix_type`
- `uint8_t max_time`
- `int set_max_time`
- `uint32_t max_dist`
- `int set_max_dist`
- `uint32_t fix_rate`
- `int set_fix_rate`

### 8.512.1 Detailed Description

This structure contains SWI LOC Get Auto Start setting

## Parameters

<i>function</i>	<ul style="list-style-type: none"> <li>• Setting to indicate when modem should start an automatic GNSS fix <ul style="list-style-type: none"> <li>– 0 - disabled</li> <li>– 1 - At bootup</li> <li>– 2 - When NMEA port is opened</li> </ul> </li> </ul>
<i>set_function</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
<i>fix_type</i>	<ul style="list-style-type: none"> <li>• Type of GNSS fix: <ul style="list-style-type: none"> <li>– 1 - Default Engine mode</li> <li>– 2 - MS-Based</li> <li>– 3 - MS-Assisted</li> <li>– 4 - Standalone</li> </ul> </li> </ul>
<i>set_fix_type</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
<i>max_time</i>	<ul style="list-style-type: none"> <li>• Maximum time allowed for the receiver to get a fix in seconds</li> <li>• Valid range: 1-255</li> </ul>
<i>set_max_time</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
<i>max_dist</i>	<ul style="list-style-type: none"> <li>• Maximum uncertainty of a fix measured by distance in meters</li> <li>• Valid range: 1 - 4294967280</li> </ul>
<i>set_max_dist</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
<i>fix_rate</i>	<ul style="list-style-type: none"> <li>• Time between fixes in seconds</li> <li>• Valid range: 1–65535</li> </ul>

<i>set_fix_rate</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
---------------------	---

### 8.512.2 Field Documentation

8.512.2.1 uint32\_t pack\_swiloc\_SwiLocSetAutoStart\_t::fix\_rate

8.512.2.2 uint8\_t pack\_swiloc\_SwiLocSetAutoStart\_t::fix\_type

8.512.2.3 uint8\_t pack\_swiloc\_SwiLocSetAutoStart\_t::function

8.512.2.4 uint32\_t pack\_swiloc\_SwiLocSetAutoStart\_t::max\_dist

8.512.2.5 uint8\_t pack\_swiloc\_SwiLocSetAutoStart\_t::max\_time

8.512.2.6 int pack\_swiloc\_SwiLocSetAutoStart\_t::set\_fix\_rate

8.512.2.7 int pack\_swiloc\_SwiLocSetAutoStart\_t::set\_fix\_type

8.512.2.8 int pack\_swiloc\_SwiLocSetAutoStart\_t::set\_function

8.512.2.9 int pack\_swiloc\_SwiLocSetAutoStart\_t::set\_max\_dist

8.512.2.10 int pack\_swiloc\_SwiLocSetAutoStart\_t::set\_max\_time

## 8.513 pack\_swisma\_SLQSOMADMCancelSession\_t Struct Reference

### Data Fields

- uint32\_t [sessionType](#)

### 8.513.1 Detailed Description

Structure that contains the session type for OMA cancel session command

#### Parameters

<i>sessionType[IN]</i>	<ul style="list-style-type: none"> <li>• Session type <ul style="list-style-type: none"> <li>– 0x01 - FOTA, to check availability of FW Update</li> <li>– 0xFF - Cancel any active OMADM session</li> </ul> </li> </ul>
------------------------	---

### 8.513.2 Field Documentation

8.513.2.1 uint32\_t pack\_swisma\_SLQSOMADMCancelSession\_t::sessionType

## 8.514 pack\_swisma\_SLQSOMADMGetSessionInfo\_t Struct Reference

## Data Fields

- uint32\_t [SessionType](#)

### 8.514.1 Detailed Description

Structure that contains the session type for OMA get session info command

#### Parameters

<i>SessionType</i> [IN]	<ul style="list-style-type: none"><li>• Session type<ul style="list-style-type: none"><li>– 0x01 - FOTA</li><li>– 0xFF - Any active OMADM session. If no active sessions are available, then previous OMADM session info is returned</li></ul></li></ul>
-------------------------	--

### 8.514.2 Field Documentation

8.514.2.1 uint32\_t pack\_swioama\_SLQSOMADMGetSessionInfo\_t::SessionType

## 8.515 pack\_swioama\_SLQSOMADMSelect\_t Struct Reference

## Data Fields

- uint32\_t [selection](#)
- uint32\_t \* [pDeferTime](#)
- uint32\_t \* [pRejectReason](#)

### 8.515.1 Detailed Description

Structure containing the OMA DM selection

#### Parameters

<i>selection</i> [IN]	<ul style="list-style-type: none"><li>• OMA-DM NIA Selection<ul style="list-style-type: none"><li>– 0x01 - Accept</li><li>– 0x02 - Reject</li><li>– 0x03 - Defer</li></ul></li></ul>
-----------------------	--



<i>pDeferTime</i> [IN]	<ul style="list-style-type: none"> <li>Defer time in minutes. A value of 0 will cause the prompt to be resent immediately.</li> <li>This TLV is mandatory if selection is set to 0x03.</li> </ul>
<i>pRejectReason</i> [IN]	<ul style="list-style-type: none"> <li>Reject Reason</li> <li>This TLV is processed if selection is set to 0x02. If it is not present, the reject reason 0 is used as default.</li> </ul>

## 8.515.2 Field Documentation

8.515.2.1 uint32\_t\* pack\_swima\_SLQSOMADMSelection\_t::pDeferTime

8.515.2.2 uint32\_t\* pack\_swima\_SLQSOMADMSelection\_t::pRejectReason

8.515.2.3 uint32\_t pack\_swima\_SLQSOMADMSelection\_t::selection

## 8.516 pack\_swima\_SLQSOMADMSetSettings\_t Struct Reference

### Data Fields

- uint8\_t [FOTAdownload](#)
- uint8\_t [FOTAUpdate](#)
- uint8\_t \* [pAutosdm](#)
- uint8\_t \* [pFwAutoCheck](#)

### 8.516.1 Detailed Description

Structure containing the OMA DM settings to be set on the device This maps to structure SLQSOMADMSettings-ReqParams3

#### Parameters

<i>FOTAdownload</i>	<ul style="list-style-type: none"> <li>1 Byte parameter indicating support for FOTA Automatic download <ul style="list-style-type: none"> <li>0x00 - Firmware autodownload FALSE</li> <li>0x01 - Firmware autodownload TRUE</li> </ul> </li> </ul>
<i>FOTAUpdate</i>	<ul style="list-style-type: none"> <li>1 byte parameter indicating FOTA Automatic update <ul style="list-style-type: none"> <li>0x00 - Firmware autoupdate FALSE</li> <li>0x01 - Firmware autoupdate TRUE</li> </ul> </li> </ul>

<i>pAutosdm</i> [IN]	<ul style="list-style-type: none"> <li>Optional 1 byte parameter indicating OMA Automatic UI Alert Response <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled Accept</li> <li>0x02 - Enabled Reject</li> </ul> </li> </ul>
<i>pFwAutoCheck</i> [-IN]	<ul style="list-style-type: none"> <li>Optional 1 byte parameter indicating OMA Automatic Check for Firmware Update on Power-Up Response <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> </ul>

## 8.516.2 Field Documentation

8.516.2.1 `uint8_t pack_swisma_SLQSOMADMSetSettings_t::FOTAdownload`

8.516.2.2 `uint8_t pack_swisma_SLQSOMADMSetSettings_t::FOTAUpdate`

8.516.2.3 `uint8_t* pack_swisma_SLQSOMADMSetSettings_t::pAutosdm`

8.516.2.4 `uint8_t* pack_swisma_SLQSOMADMSetSettings_t::pFwAutoCheck`

## 8.517 `pack_swisma_SLQSOMADMStartSession_t` Struct Reference

### Data Fields

- `uint32_t` [sessionType](#)

### 8.517.1 Detailed Description

Structure that contains the session type for OMA start session command

#### Parameters

<i>sessionType</i> [IN]	<ul style="list-style-type: none"> <li>Session type <ul style="list-style-type: none"> <li>0x01 - FOTA, to check availability of FW Update</li> <li>0x02 - DM, to check availability of DM Update</li> <li>0x03 - PRL, to check availability of PRL Update</li> </ul> </li> </ul>
-------------------------	---

## 8.517.2 Field Documentation

8.517.2.1 `uint32_t pack_swisma_SLQSOMADMStartSession_t::sessionType`

## 8.518 pack\_uim\_ChangePin\_t Struct Reference

### Data Fields

- [uim\\_encryptedPIN1](#) EncryptedPIN1
- [uint32\\_t \\* pIndicationToken](#)
- [uint8\\_t \\* pKeyReferenceID](#)
- [uim\\_sessionInformation](#) sessionInfo
- [uim\\_changeUIMPIN](#) changePIN
- [uint16\\_t Tlvresult](#)

### 8.518.1 Detailed Description

This structure contains information of the request parameters associated with a Change PIN API.

#### Parameters

<a href="#">sessionInfo</a>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<i>changePIN</i>	<ul style="list-style-type: none"> <li>• See <a href="#">changeUIMPIN</a> for more information.</li> </ul>
<i>pKeyReferenceID(optional)</i>	<ul style="list-style-type: none"> <li>• Indicates the PIN key reference ID.</li> <li>• Indicates the PIN key reference ID. Valid values are from 1 to 8, respectively, for application 1 to application 8.</li> <li>• This TLV is used only for PIN1 and PIN2 and is ignored in all other cases.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> <li>• Valid Values             <ul style="list-style-type: none"> <li>– 0 - Result of operation in response. Indication will not be generated by the modem</li> <li>– Any other positive number - Result of operation in indication. Indication will have same token value set by this function</li> </ul> </li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

### 8.518.2 Field Documentation

8.518.2.1 [uim\\_changeUIMPIN](#) [pack\\_uim\\_ChangePin\\_t::changePIN](#)

8.518.2.2 [uim\\_encryptedPIN1](#) [pack\\_uim\\_ChangePin\\_t::EncryptedPIN1](#)

8.518.2.3 [uint32\\_t\\*](#) [pack\\_uim\\_ChangePin\\_t::pIndicationToken](#)

8.518.2.4 uint8\_t\* pack\_uim\_ChangePin\_t::pKeyReferenceID

8.518.2.5 uim\_sessionInformation pack\_uim\_ChangePin\_t::sessionInfo

8.518.2.6 uint16\_t pack\_uim\_ChangePin\_t::Tlvresult

## 8.519 pack\_uim\_ReadTransparent\_t Struct Reference

### Data Fields

- [uim\\_sessionInformation sessionInfo](#)
- [uim\\_fileInfo fileIndex](#)
- [uim\\_readTransparentInfo readTransparent](#)
- uint32\_t \* [pIndicationToken](#)
- uint8\_t \* [pEncryptData](#)
- uint16\_t [Tlvresult](#)

### 8.519.1 Detailed Description

This structure contains information of the request parameters associated with a Read Transparent API.

#### Parameters

<a href="#">sessionInfo</a>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<a href="#">fileIndex</a>	<ul style="list-style-type: none"> <li>• See <a href="#">fileInfo</a> for more information.</li> </ul>
<a href="#">readTransparent</a>	<ul style="list-style-type: none"> <li>• See <a href="#">readTransparentInfo</a> for more information.</li> </ul>
<a href="#">pIndication-Token(optional)</a>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> <li>• Valid Values <ul style="list-style-type: none"> <li>– 0 - Result of operation in response. Indication will not be generated by the modem</li> <li>– Any other positive number - Result of operation in indication. Indication will have same token value set by this function</li> </ul> </li> </ul>
<a href="#">pEncrypt-Data(optional)</a>	<ul style="list-style-type: none"> <li>• Encrypt Data.</li> <li>• Indicates whether the data read from the card is to be encrypted.</li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

## 8.519.2 Field Documentation

8.519.2.1 uim\_fileInfo pack\_uim\_ReadTransparent\_t::fileIndex

8.519.2.2 uint8\_t\* pack\_uim\_ReadTransparent\_t::pEncryptData

8.519.2.3 uint32\_t\* pack\_uim\_ReadTransparent\_t::pIndicationToken

8.519.2.4 uim\_readTransparentInfo pack\_uim\_ReadTransparent\_t::readTransparent

8.519.2.5 uim\_sessionInformation pack\_uim\_ReadTransparent\_t::sessionInfo

8.519.2.6 uint16\_t pack\_uim\_ReadTransparent\_t::Tlvresult

## 8.520 pack\_uim\_SetPinProtection\_t Struct Reference

### Data Fields

- [uim\\_encryptedPIN1](#) EncryptedPIN1
- [uint32\\_t \\* pIndicationToken](#)
- [uint8\\_t \\* pKeyReferenceID](#)
- [uim\\_sessionInformation](#) sessionInfo
- [uim\\_setPINProtection](#) pinProtection
- [uint16\\_t Tlvresult](#)

### 8.520.1 Detailed Description

This structure contains information of the request parameters associated with a set pin protection API.

## Parameters

<i>sessionInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_sessionInformation</a> for more information.</li> </ul>
<i>pinProtection</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_setPINProtection</a> for more information.</li> </ul>
<i>pKeyReferenceID(optional)</i>	<ul style="list-style-type: none"> <li>• Indicates the PIN key reference ID.</li> <li>• Indicates the PIN key reference ID. Valid values are from 1 to 8, respectively, for application 1 to application 8.</li> <li>• This TLV is used only for PIN1 and PIN2 and is ignored in all other cases.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> <li>• Valid Values <ul style="list-style-type: none"> <li>– 0 - Result of operation in response. Indication will not be generated by the modem</li> <li>– Any other positive number - Result of operation in indication. Indication will have same token value set by this function</li> </ul> </li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

## 8.520.2 Field Documentation

8.520.2.1 `uim_encryptedPIN1` `pack_uim_SetPinProtection_t::EncryptedPIN1`

8.520.2.2 `uint32_t*` `pack_uim_SetPinProtection_t::pIndicationToken`

8.520.2.3 `uim_setPINProtection` `pack_uim_SetPinProtection_t::pinProtection`

8.520.2.4 `uint8_t*` `pack_uim_SetPinProtection_t::pKeyReferenceID`

8.520.2.5 `uim_sessionInformation` `pack_uim_SetPinProtection_t::sessionInfo`

8.520.2.6 `uint16_t` `pack_uim_SetPinProtection_t::Tlvresult`

8.521 `pack_uim_SLQSUIMEventRegister_t` Struct Reference

## Data Fields

- `uint32_t` `eventMask`

## 8.521.1 Detailed Description

## Parameters

<i>eventMask</i>	<ul style="list-style-type: none"><li>- bit 1 - card status</li><li>• bit 4 - physical slot status</li></ul>
------------------	--

## 8.521.2 Field Documentation

8.521.2.1 uint32\_t pack\_uim\_SLQSUIMEventRegister\_t::eventMask

## 8.522 pack\_uim\_SLQSUIMSwitchSlot\_t Struct Reference

## Data Fields

- uint8\_t [bLogicalSlot](#)
- uint32\_t [ulPhysicalSlot](#)

## 8.522.1 Detailed Description

This structure contains information of the request parameters associated with a Switch Slot.

## Parameters

<i>bLogicalSlot</i>	<ul style="list-style-type: none"><li>• Indicates the slot to be used.<ul style="list-style-type: none"><li>– 1 - Slot 1</li><li>– 2 - Slot 2</li><li>– 3 - Slot 3</li><li>– 4 - Slot 4</li><li>– 5 - Slot 5</li></ul></li></ul>
<i>ulPhysicalSlot</i>	<ul style="list-style-type: none"><li>• 1 - Slot 1</li><li>• 2 - Slot 2</li><li>• 3 - Slot 3</li><li>• 4 - Slot 4</li><li>• 5 - Slot 5</li></ul>

## 8.522.2 Field Documentation

8.522.2.1 uint8\_t pack\_uim\_SLQSUIMSwitchSlot\_t::bLogicalSlot

8.522.2.2 uint32\_t pack\_uim\_SLQSUIMSwitchSlot\_t::ulPhysicalSlot

## 8.523 pack\_uim\_UnblockPin\_t Struct Reference

## Data Fields

- [uim\\_encryptedPIN1](#) EncryptedPIN1
- [uint32\\_t \\* pIndicationToken](#)
- [uint8\\_t \\* pKeyReferenceID](#)
- [uim\\_sessionInformation](#) sessionInfo
- [uim\\_unblockUIMPIN](#) pinProtection
- [uint16\\_t](#) Tlvresult

### 8.523.1 Detailed Description

This structure contains information of the request parameters associated with a Unblock PIN API.

#### Parameters

<i>EncryptedPIN1</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_encryptedPIN1</a> for more information.</li> </ul>
<i><a href="#">sessionInfo</a></i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_sessionInformation</a> for more information.</li> </ul>
<i>pinProtection</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_unblockUIMPIN</a> for more information.</li> </ul>
<i>pKeyReferenceID(optional)</i>	<ul style="list-style-type: none"> <li>• Indicates the PIN key reference ID.</li> <li>• Indicates the PIN key reference ID. Valid values are from 1 to 8, respectively, for application 1 to application 8.</li> <li>• This TLV is used only for PIN1 and PIN2 and is ignored in all other cases.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> <li>• Valid Values               <ul style="list-style-type: none"> <li>– 0 - Result of operation in response. Indication will not be generated by the modem</li> <li>– Any other positive number - Result of operation in indication. Indication will have same token value set by this function</li> </ul> </li> </ul>



## 8.523.2 Field Documentation

8.523.2.1 uim\_encryptedPIN1 pack\_uim\_UnblockPin\_t::EncryptedPIN1

8.523.2.2 uint32\_t\* pack\_uim\_UnblockPin\_t::pIndicationToken

8.523.2.3 uim\_unblockUIMPIN pack\_uim\_UnblockPin\_t::pinProtection

8.523.2.4 uint8\_t\* pack\_uim\_UnblockPin\_t::pKeyReferenceID

8.523.2.5 uim\_sessionInformation pack\_uim\_UnblockPin\_t::sessionInfo

8.523.2.6 uint16\_t pack\_uim\_UnblockPin\_t::Tlvresult

## 8.524 pack\_uim\_VerifyPin\_t Struct Reference

### Data Fields

- [uim\\_encryptedPIN1](#) \* [pEncryptedPIN1](#)
- [uint32\\_t](#) \* [pIndicationToken](#)
- [uint8\\_t](#) \* [pKeyReferenceID](#)
- [uim\\_sessionInformation](#) [sessionInfo](#)
- [uim\\_verifyUIMPIN](#) [verifyPIN](#)
- [uint16\\_t](#) [Tlvresult](#)

### 8.524.1 Detailed Description

This structure contains information of the request parameters associated with a verify PIN API.

## Parameters

<i>sessionInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<i>verifyPIN</i>	<ul style="list-style-type: none"> <li>• See <a href="#">verifyUIMPIN</a> for more information.</li> </ul>
<i>pEncryptedPIN1(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">encryptedPIN1</a> for more information.</li> </ul>
<i>pKeyReferenceID(optional)</i>	<ul style="list-style-type: none"> <li>• Indicates the PIN key reference ID.</li> <li>• Indicates the PIN key reference ID. Valid values are from 1 to 8, respectively, for application 1 to application 8.</li> <li>• This TLV is used only for PIN1 and PIN2 and is ignored in all other cases.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> <li>• Valid Values <ul style="list-style-type: none"> <li>– 0 - Result of operation in response. Indication will not be generated by the modem</li> <li>– Any other positive number - Result of operation in indication. Indication will have same token value set by this function</li> </ul> </li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

## 8.524.2 Field Documentation

8.524.2.1 `uim_encryptedPIN1*` `pack_uim_VerifyPin_t::pEncryptedPIN1`

8.524.2.2 `uint32_t*` `pack_uim_VerifyPin_t::pIndicationToken`

8.524.2.3 `uint8_t*` `pack_uim_VerifyPin_t::pKeyReferenceID`

8.524.2.4 `uim_sessionInformation` `pack_uim_VerifyPin_t::sessionInfo`

8.524.2.5 `uint16_t` `pack_uim_VerifyPin_t::Tlvresult`

8.524.2.6 `uim_verifyUIMPIN` `pack_uim_VerifyPin_t::verifyPIN`

8.525 `pack_wds_GetDefaultProfile_t` Struct Reference

## Data Fields

- `uint32_t` [profiletype](#)

### 8.525.1 Detailed Description

#### Parameters

<i>profiletype</i>	profile type
--------------------	--------------

### 8.525.2 Field Documentation

8.525.2.1 uint32\_t pack\_wds\_GetDefaultProfile\_t::profiletype

## 8.526 pack\_wds\_GetDefaultProfileNum\_t Struct Reference

#### Data Fields

- uint8\_t [type](#)
- uint8\_t [family](#)

### 8.526.1 Detailed Description

#### Parameters

<i>type</i>	profile type <ul style="list-style-type: none"><li>• 0 - 3GPP</li><li>• 1 - 3GPP2</li></ul>
<i>type</i>	profile family <ul style="list-style-type: none"><li>• 0 - Embedded</li><li>• 1 - Tethered</li></ul>

### 8.526.2 Field Documentation

8.526.2.1 uint8\_t pack\_wds\_GetDefaultProfileNum\_t::family

8.526.2.2 uint8\_t pack\_wds\_GetDefaultProfileNum\_t::type

## 8.527 pack\_wds\_GetDormancyState\_t Struct Reference

## 8.528 pack\_wds\_GetLastMobileIPError\_t Struct Reference

## 8.529 pack\_wds\_GetMobileIP\_t Struct Reference

## 8.530 pack\_wds\_GetMobileIPProfile\_t Struct Reference

#### Data Fields

- uint8\_t [index](#)

### 8.530.1 Detailed Description

## Parameters

<i>index</i>	mobile ip profile identifier
--------------	------------------------------

## 8.530.2 Field Documentation

8.530.2.1 `uint8_t pack_wds_GetMobileIPProfile_t::index`

## 8.531 pack\_wds\_GetPacketStatus\_t Struct Reference

## Data Fields

- `uint32_t statmask`

## 8.531.1 Detailed Description

## Parameters

<i>statmask</i>	packet statistics mask
-----------------	------------------------

## 8.531.2 Field Documentation

8.531.2.1 `uint32_t pack_wds_GetPacketStatus_t::statmask`

## 8.532 pack\_wds\_GetSessionDuration\_t Struct Reference

## 8.533 pack\_wds\_RMSetTransferStatistics\_t Struct Reference

## Data Fields

- `rmTrasnferStaticsReq RmTrasnferStaticsReq`

## 8.533.1 Detailed Description

## Parameters

<i><a href="#">rmTrasnferStaticsReq</a></i>	RM Transfer Statistics Indicator
---	----------------------------------

## 8.533.2 Field Documentation

8.533.2.1 `rmTrasnferStaticsReq pack_wds_RMSetTransferStatistics_t::RmTrasnferStaticsReq`

## 8.534 pack\_wds\_SetDefaultProfile\_t Struct Reference

## Data Fields

- `uint32_t profileType`
- `uint32_t pdpType`
- `uint32_t ipAddress`

- uint32\_t [primaryDNS](#)
- uint32\_t [secondaryDNS](#)
- uint32\_t [authentication](#)
- uint8\_t \* [pName](#)
- uint8\_t \* [pUsername](#)
- uint8\_t \* [pApnname](#)
- uint8\_t \* [pPassword](#)

### 8.534.1 Detailed Description

#### Parameters

<i>profileType</i>	profile type
<i>pdpType</i>	Packet Data Protocol (PDP) type
<i>ipAddress</i>	ip address
<i>primaryDNS</i>	primary dns
<i>secondaryDNS</i>	secondry dns
<i>authentication</i>	authentication type
<i>name</i>	name of the profile
<i>apnname</i>	apn name
<i>username</i>	username of the profile
<i>password</i>	password of profile

### 8.534.2 Field Documentation

8.534.2.1 uint32\_t pack\_wds\_SetDefaultProfile\_t::authentication

8.534.2.2 uint32\_t pack\_wds\_SetDefaultProfile\_t::ipAddress

8.534.2.3 uint8\_t\* pack\_wds\_SetDefaultProfile\_t::pApnname

8.534.2.4 uint32\_t pack\_wds\_SetDefaultProfile\_t::pdpType

8.534.2.5 uint8\_t\* pack\_wds\_SetDefaultProfile\_t::pName

8.534.2.6 uint8\_t\* pack\_wds\_SetDefaultProfile\_t::pPassword

8.534.2.7 uint32\_t pack\_wds\_SetDefaultProfile\_t::primaryDNS

8.534.2.8 uint32\_t pack\_wds\_SetDefaultProfile\_t::profileType

8.534.2.9 uint8\_t\* pack\_wds\_SetDefaultProfile\_t::pUsername

8.534.2.10 uint32\_t pack\_wds\_SetDefaultProfile\_t::secondaryDNS

## 8.535 pack\_wds\_SetDefaultProfileNum\_t Struct Reference

#### Data Fields

- uint8\_t [type](#)
- uint8\_t [family](#)
- uint8\_t [index](#)

### 8.535.1 Field Documentation

8.535.1.1 uint8\_t pack\_wds\_SetDefaultProfileNum\_t::family

8.535.1.2 uint8\_t pack\_wds\_SetDefaultProfileNum\_t::index

8.535.1.3 uint8\_t pack\_wds\_SetDefaultProfileNum\_t::type

## 8.536 pack\_wds\_SetMobileIPProfile\_t Struct Reference

### Data Fields

- int8\_t [spc](#) [10]
- uint8\_t [index](#)
- uint8\_t \* [pEnabled](#)
- uint32\_t \* [pAddress](#)
- uint32\_t \* [pPrimaryHA](#)
- uint32\_t \* [pSecondaryHA](#)
- uint8\_t \* [pRevTunneling](#)
- int8\_t \* [pNAI](#)
- uint32\_t \* [pHASPI](#)
- uint32\_t \* [pAAASPI](#)
- int8\_t \* [pMNHA](#)
- int8\_t \* [pMNAAA](#)

### 8.536.1 Detailed Description

#### Parameters

<i>spc</i>	service programming code string
<i>index</i>	Index of the profile to modify
<i>pEnabled</i>	Enable profile 0-disable nonzero enable
<i>pAddress</i>	Home IPv4 address
<i>pPrimaryHA</i>	Primary home agent IPv4 address
<i>pSecondaryHA</i>	secondary home agent IPv4 address
<i>pRevTunneling</i>	Enable reverse tunneling 0-disable nonzero enable
<i>pNAI</i>	Network access identifier string
<i>pHASPI</i>	Home agent security parameter index
<i>pAAASPI</i>	AAA server security parameter index
<i>pMNHA</i>	MN-HA key string
<i>pMNAAA</i>	MN-AAA key string

### 8.536.2 Field Documentation

8.536.2.1 uint8\_t pack\_wds\_SetMobileIPProfile\_t::index

8.536.2.2 uint32\_t\* pack\_wds\_SetMobileIPProfile\_t::pAAASPI

8.536.2.3 uint32\_t\* pack\_wds\_SetMobileIPProfile\_t::pAddress

8.536.2.4 uint8\_t\* pack\_wds\_SetMobileIPProfile\_t::pEnabled

8.536.2.5 uint32\_t\* pack\_wds\_SetMobileIPProfile\_t::pHASPI

8.536.2.6 `int8_t* pack_wds_SetMobileIPProfile_t::pMNA`

8.536.2.7 `int8_t* pack_wds_SetMobileIPProfile_t::pMNA`

8.536.2.8 `int8_t* pack_wds_SetMobileIPProfile_t::pNAI`

8.536.2.9 `uint32_t* pack_wds_SetMobileIPProfile_t::pPrimaryHA`

8.536.2.10 `uint8_t* pack_wds_SetMobileIPProfile_t::pRevTunneling`

8.536.2.11 `uint32_t* pack_wds_SetMobileIPProfile_t::pSecondaryHA`

8.536.2.12 `int8_t pack_wds_SetMobileIPProfile_t::spc[10]`

## 8.537 `pack_wds_SLQSCreateProfile_t` Struct Reference

### Data Fields

- `uint8_t * pProfileId`
- `uint8_t * pProfileType`
- `wds_profileInfo * pCurProfile`

### 8.537.1 Detailed Description

#### Parameters

<i>ProfileID</i>	<ul style="list-style-type: none"> <li>• 1 to 16 for 3GPP profile (EM/MC73xx or earlier)</li> <li>• 1 to 24 for 3GPP profile (EM/MC74xx onwards)</li> <li>• 101 to 106 for 3GPP2 profile</li> </ul>
<i>ProfileType</i>	<ul style="list-style-type: none"> <li>• Identifies the technology type of the profile <ul style="list-style-type: none"> <li>– 0x00 - 3GPP</li> <li>– 0x01 - 3GPP2</li> <li>– NULL is not allowed</li> </ul> </li> </ul>
<i>curProfile</i>	<ul style="list-style-type: none"> <li>• union of 3GPP and 3GPP2 profile</li> </ul>

#### Note

- If profileID is NULL, 3GPP profile will be created and index will be assigned based on availability in device.
- If profileID is not NULL depending on pProfileType 3GPP/3GPP2 relevant profile will be created

### 8.537.2 Field Documentation

8.537.2.1 `wds_profileInfo* pack_wds_SLQSCreateProfile_t::pCurProfile`



8.537.2.2 uint8\_t\* pack\_wds\_SLQSCreateProfile\_t::pProfileId

8.537.2.3 uint8\_t\* pack\_wds\_SLQSCreateProfile\_t::pProfileType

## 8.538 pack\_wds\_SLQSDeleteProfile\_t Struct Reference

### Data Fields

- uint8\_t [profileType](#)
- uint8\_t [profileIndex](#)

### 8.538.1 Detailed Description

#### Parameters

<i>profileType</i>	profile type
<i>profileIndex</i>	profile index

### 8.538.2 Field Documentation

8.538.2.1 uint8\_t pack\_wds\_SLQSDeleteProfile\_t::profileIndex

8.538.2.2 uint8\_t pack\_wds\_SLQSDeleteProfile\_t::profileType

## 8.539 pack\_wds\_SLQSGetCurrDataSystemStat\_t Struct Reference

## 8.540 pack\_wds\_SLQSGetDataBearerTechnology\_t Struct Reference

## 8.541 pack\_wds\_SLQSGetDUNCallInfo\_t Struct Reference

### Data Fields

- uint32\_t [Mask](#)
- uint8\_t \* [pReportConnStatus](#)
- [transferStatInd](#) \* [pTransferStatInd](#)
- uint8\_t \* [pReportDormStatus](#)
- uint8\_t \* [pReportDataBearerTech](#)
- uint8\_t \* [pReportChannelRate](#)

### 8.541.1 Detailed Description

#### Parameters

<i>Mask</i>	mask bits corresponding to the information requested to 1
<i>pReportConn-Status</i>	Connect Status Indicator

<i>pTransferStatInd</i>	Transfer Statistics Indicator
<i>pReportDorm-Status</i>	Dormancy Status Indicator
<i>pReportData-BearerTech</i>	Current Data Bearer Technology Indicator
<i>pReport-ChannelRate</i>	Channel Rate Indicator

## 8.541.2 Field Documentation

8.541.2.1 `uint32_t pack_wds_SLQSGetDUNCallInfo_t::Mask`

8.541.2.2 `uint8_t* pack_wds_SLQSGetDUNCallInfo_t::pReportChannelRate`

8.541.2.3 `uint8_t* pack_wds_SLQSGetDUNCallInfo_t::pReportConnStatus`

8.541.2.4 `uint8_t* pack_wds_SLQSGetDUNCallInfo_t::pReportDataBearerTech`

8.541.2.5 `uint8_t* pack_wds_SLQSGetDUNCallInfo_t::pReportDormStatus`

8.541.2.6 `transferStatInd* pack_wds_SLQSGetDUNCallInfo_t::pTransferStatInd`

## 8.542 `pack_wds_SLQSGetProfileSettings_t` Struct Reference

### Data Fields

- `uint8_t` [ProfileId](#)
- `uint8_t` [ProfileType](#)

### 8.542.1 Detailed Description

#### Parameters

<i>ProfileID</i>	<ul style="list-style-type: none"> <li>• 1 to 16 for 3GPP profile (EM/MC73xx or earlier)</li> <li>• 1 to 24 for 3GPP profile (EM/MC74xx onwards)</li> <li>• 101 to 106 for 3GPP2 profile</li> </ul>
<i>ProfileType</i>	<ul style="list-style-type: none"> <li>• Identifies the technology type of the profile <ul style="list-style-type: none"> <li>– 0x00 - 3GPP</li> <li>– 0x01 - 3GPP2</li> </ul> </li> </ul>

#### Note

- If profileID is NULL, 3GPP profile will be fetched and index will be assigned based on availability in device.
- If profileID is not NULL depending on pProfileType 3GPP/3GPP2 relevant profile will be fetched

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 8.542.2 Field Documentation

8.542.2.1 uint8\_t pack\_wds\_SLQSGetProfileSettings\_t::ProfileId

8.542.2.2 uint8\_t pack\_wds\_SLQSGetProfileSettings\_t::ProfileType

## 8.543 pack\_wds\_SLQSGetRuntimeSettings\_t Struct Reference

#### Data Fields

- uint32\_t \* [pReqSettings](#)

### 8.543.1 Detailed Description

#### Parameters

<i>pReqSettings</i>	<p>Requested Settings (Optional Parameter)</p> <ul style="list-style-type: none"> <li>• Set bits to 1, corresponding to requested information. All other bits must be set to 0.</li> <li>• If the values are not available, the corresponding TLVs are not returned in the response.</li> <li>• Absence of this mask TLV results in the device returning all of the available information corresponding to bits 0 through 12.</li> <li>• In cases where the information from bit 13 or greater is required, this TLV with all the necessary bits set must be present in the request.</li> <li>• Values <ul style="list-style-type: none"> <li>– Bit 0 - Profile identifier</li> <li>– Bit 1 - Profile name</li> <li>– Bit 2 - PDP type</li> <li>– Bit 3 - APN name</li> <li>– Bit 4 - DNS address</li> <li>– Bit 5 - UMTS/GPRS granted QoS</li> <li>– Bit 6 - Username</li> <li>– Bit 7 - Authentication Protocol</li> <li>– Bit 8 - IP address</li> <li>– Bit 9 - Gateway info (address and subnet mask)</li> <li>– Bit 10 - PCSCF address using PCO flag</li> <li>– Bit 11 - PCSCF server address list</li> <li>– Bit 12 - PCSCF domain name list</li> <li>– Bit 13 - MTU</li> <li>– Bit 14 - domain name list</li> <li>– Bit 15 - IP family</li> <li>– Bit 16 - IM_CM flag</li> <li>– Bit 17 - Technology name</li> <li>– Bit 18 - Operator reserved PCO</li> </ul> </li> </ul>
---------------------	--

### 8.543.2 Field Documentation

8.543.2.1 `uint32_t* pack_wds_SLQSGetRuntimeSettings_t::pReqSettings`

## 8.544 `pack_wds_SLQSMModifyProfile_t` Struct Reference

#### Data Fields

- `uint8_t * pProfileId`
- `uint8_t * pProfileType`
- `wds_profileInfo curProfile`

### 8.544.1 Detailed Description

## Parameters

<i>ProfileID</i>	<ul style="list-style-type: none"> <li>• 1 to 16 for 3GPP profile (EM/MC73xx or earlier)</li> <li>• 1 to 24 for 3GPP profile (EM/MC74xx onwards)</li> <li>• 101 to 106 for 3GPP2 profile</li> </ul>
<i>ProfileType</i>	<ul style="list-style-type: none"> <li>• Identifies the technology type of the profile <ul style="list-style-type: none"> <li>– 0x00 - 3GPP</li> <li>– 0x01 - 3GPP2</li> <li>– NULL is not allowed</li> </ul> </li> </ul>
<i>curProfile</i>	<ul style="list-style-type: none"> <li>• union of 3GPP and 3GPP2 profile</li> </ul>

## Note

- If profileID is NULL, 3GPP profile will be created and index will be assigned based on availability in device.
- If profileID is not NULL depending on pProfileType 3GPP/3GPP2 relevant profile will be created

## 8.544.2 Field Documentation

8.544.2.1 wds\_profileInfo pack\_wds\_SLQSMModifyProfile\_t::curProfile

8.544.2.2 uint8\_t\* pack\_wds\_SLQSMModifyProfile\_t::pProfileId

8.544.2.3 uint8\_t\* pack\_wds\_SLQSMModifyProfile\_t::pProfileType

## 8.545 pack\_wds\_SLQSSet3GPPConfigItem\_t Struct Reference

## Data Fields

- uint16\_t [profileList](#) [5]
- uint8\_t [defaultPDNEnabled](#)
- uint8\_t [\\_3gppRelease](#)
- uint16\_t [LTEAttachProfileList](#) [24]
- uint16\_t [LTEAttachProfileListLen](#)

### 8.545.1 Detailed Description

#### Parameters

<i>profileList</i>	Profile List
<i>defaultPDN-Enabled</i>	<ul style="list-style-type: none"> <li>• 0 - disabled</li> <li>• 1 - enabled</li> </ul>
<i>_3gppRelease</i>	3GPP release <ul style="list-style-type: none"> <li>• 0 - Release_99</li> <li>• 1 - Release_5</li> <li>• 2 - Release_6</li> <li>• 3 - Release_7</li> <li>• 4 - Release_8</li> </ul>
<i>LTEAttach-ProfileList</i>	<ul style="list-style-type: none"> <li>• pointer to WORD array indicating LTE Attach Profile List               <ul style="list-style-type: none"> <li>– Optional parameter</li> <li>– possible values: 1-24</li> <li>– This setting is only supported for MC/EM74xx onwards</li> <li>– Please provide attach profiles in order of decreasing priority in this list.</li> </ul> </li> </ul>
<i>LTEAttach-ProfileListLen</i>	<ul style="list-style-type: none"> <li>• Number of element in pLTEAttachProfileList               <ul style="list-style-type: none"> <li>– valid range: 1-24</li> <li>– This setting is only supported for MC/EM74xx onwards</li> </ul> </li> </ul>

### 8.545.2 Field Documentation

8.545.2.1 uint8\_t pack\_wds\_SLQSSet3GPPConfigItem\_t::\_3gppRelease

8.545.2.2 uint8\_t pack\_wds\_SLQSSet3GPPConfigItem\_t::defaultPDNEnabled

8.545.2.3 uint16\_t pack\_wds\_SLQSSet3GPPConfigItem\_t::LTEAttachProfileList[24]

8.545.2.4 uint16\_t pack\_wds\_SLQSSet3GPPConfigItem\_t::LTEAttachProfileListLen

8.545.2.5 uint16\_t pack\_wds\_SLQSSet3GPPConfigItem\_t::profileList[5]

## 8.546 pack\_wds\_SLQSSetIPFamilyPreference\_t Struct Reference

#### Data Fields

- uint8\_t [IPFamilyPreference](#)

### 8.546.1 Detailed Description



## Parameters

<i>IPFamily-Preference</i>	IP Family preference <ul style="list-style-type: none"> <li>• PACK_WDS_IPV4 IP Version 4</li> <li>• PACK_WDS_IPV6 IP Version 6</li> </ul>
----------------------------	---

## 8.546.2 Field Documentation

8.546.2.1 uint8\_t pack\_wds\_SLQSSetIPFamilyPreference\_t::IPFamilyPreference

## 8.547 pack\_wds\_SLQSSetWdsEventCallback\_t Struct Reference

## Data Fields

- uint8\_t [dataBearer](#)
- uint8\_t [dormancyStatus](#)
- uint8\_t [mobileIP](#)
- uint8\_t [transferStats](#)
- uint8\_t [currentDataBearer](#)
- uint8\_t [dataSystemStatus](#)
- uint8\_t [interval](#)

## 8.547.1 Detailed Description

## Parameters

<i>dataBearer</i>	data bearer
<i>dormancyStatus</i>	dormancy status
<i>mobileIP</i>	mobile IP
<i>currentData-Bearer</i>	current data bearer
<i>dataSystem-Status</i>	data system status
<i>interval</i>	interval

## 8.547.2 Field Documentation

8.547.2.1 uint8\_t pack\_wds\_SLQSSetWdsEventCallback\_t::currentDataBearer

8.547.2.2 uint8\_t pack\_wds\_SLQSSetWdsEventCallback\_t::dataBearer

8.547.2.3 uint8\_t pack\_wds\_SLQSSetWdsEventCallback\_t::dataSystemStatus

8.547.2.4 uint8\_t pack\_wds\_SLQSSetWdsEventCallback\_t::dormancyStatus

8.547.2.5 uint8\_t pack\_wds\_SLQSSetWdsEventCallback\_t::interval

8.547.2.6 uint8\_t pack\_wds\_SLQSSetWdsEventCallback\_t::mobileIP

8.547.2.7 uint8\_t pack\_wds\_SLQSSetWdsEventCallback\_t::transferStats

## 8.548 pack\_wds\_SLQSSGetDHCPv4ClientConfig\_t Struct Reference

### Data Fields

- [wdsDhcpv4ProfileId](#) \* [pProfileId](#)

### 8.548.1 Detailed Description

#### Parameters

<i>pProfileId</i>	pointer to Profile Id structure
-------------------	---------------------------------

### 8.548.2 Field Documentation

8.548.2.1 [wdsDhcpv4ProfileId](#)\* [pack\\_wds\\_SLQSSGetDHCPv4ClientConfig\\_t::pProfileId](#)

## 8.549 pack\_wds\_SLQSStartDataSession\_t Struct Reference

### Data Fields

- [uint8\\_t](#) \* [pTech](#)
- [uint32\\_t](#) \* [pprofileid3gpp](#)
- [uint32\\_t](#) \* [pprofileid3gpp2](#)
- [uint32\\_t](#) \* [pAuth](#)
- [char](#) \* [pUser](#)
- [char](#) \* [pPass](#)

### 8.549.1 Detailed Description

#### Parameters

<i>pTech</i>	<ul style="list-style-type: none"> <li>• Indicates the technology preference <ul style="list-style-type: none"> <li>– 1 - UMTS</li> <li>– 2 - CDMA</li> <li>– 3 - eMBMS</li> <li>– 4 - Modem Link Label. Modem Link is an interface for transferring data between entities on AP and modem.</li> </ul> </li> <li>• optional</li> </ul>
--------------	--

<i>pprofileid3gpp</i>	<ul style="list-style-type: none"> <li>• pointer to 3GPP profile id</li> <li>• optional</li> </ul>
<i>pprofileid3gpp2</i>	<ul style="list-style-type: none"> <li>• pointer to 3GPPs profile id</li> <li>• optional</li> </ul>
<i>pAuth</i>	<ul style="list-style-type: none"> <li>• Authentication type, it can be PAP or CHAP</li> <li>• optional</li> </ul>
<i>pUser</i>	<ul style="list-style-type: none"> <li>• username for authentication process</li> <li>• optional</li> </ul>
<i>pPass</i>	<ul style="list-style-type: none"> <li>• password for authentication process</li> <li>• optional</li> </ul>

## 8.549.2 Field Documentation

8.549.2.1 `uint32_t* pack_wds_SLQSStartDataSession_t::pAuth`

8.549.2.2 `char* pack_wds_SLQSStartDataSession_t::pPass`

8.549.2.3 `uint32_t* pack_wds_SLQSStartDataSession_t::pprofileid3gpp`

8.549.2.4 `uint32_t* pack_wds_SLQSStartDataSession_t::pprofileid3gpp2`

8.549.2.5 `uint8_t* pack_wds_SLQSStartDataSession_t::pTech`

8.549.2.6 `char* pack_wds_SLQSStartDataSession_t::pUser`

## 8.550 pack\_wds\_SLQSStopDataSession\_t Struct Reference

### Data Fields

- `uint32_t * psid`

### 8.550.1 Detailed Description

#### Parameters

---

<i>sid</i>	session id
------------	------------

## 8.550.2 Field Documentation

8.550.2.1 uint32\_t\* pack\_wds\_SLQSSStopDataSession\_t::psid

## 8.551 pack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t Struct Reference

### Data Fields

- uint8\_t [contextId](#)
- uint8\_t [contextType](#)

### 8.551.1 Detailed Description

#### Parameters

<i>contextId</i>	Context Identifier
<i>contextType</i>	Context Type 0-3GPP 1-3GPP2

## 8.551.2 Field Documentation

8.551.2.1 uint8\_t pack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t::contextId

8.551.2.2 uint8\_t pack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t::contextType

## 8.552 PackCreateProfileOut Struct Reference

### Data Fields

- uint8\_t [ProfileType](#)
- uint8\_t [ProfileIndex](#)
- uint16\_t [ExtErrorCode](#)

### 8.552.1 Field Documentation

8.552.1.1 uint16\_t PackCreateProfileOut::ExtErrorCode

8.552.1.2 uint8\_t PackCreateProfileOut::ProfileIndex

8.552.1.3 uint8\_t PackCreateProfileOut::ProfileType

## 8.553 packgetDyingGaspCfg Struct Reference

### Data Fields

- uint8\_t \* [pDestSMSNum](#)
- uint8\_t \* [pDestSMSCContent](#)

### 8.553.1 Detailed Description

## Parameters

<i>pDestSMSNum</i> [-IN]	<ul style="list-style-type: none"> <li>• SMS Destination Number as string of 8 bit ASCII Characters Max 20 chars.</li> <li>• Optional parameter.</li> </ul>
<i>pDestSMSContent</i> [IN]	<ul style="list-style-type: none"> <li>• SMS Content as a string of 8 bit ASCII text characters Max 160 chars.</li> <li>• Optional parameter.</li> </ul>

## 8.553.2 Field Documentation

8.553.2.1 uint8\_t\* packgetDyingGaspCfg::pDestSMSContent

8.553.2.2 uint8\_t\* packgetDyingGaspCfg::pDestSMSNum

## 8.554 packgetDyingGaspStatistics Struct Reference

## Data Fields

- uint32\_t \* [pTimeStamp](#)
- uint8\_t \* [pSMSAttemptedFlag](#)

## 8.554.1 Detailed Description

## Parameters

<i>TimeStamp</i> [OUT]	<ul style="list-style-type: none"> <li>• Time Stamp.</li> </ul>
<i>SMSAttemptedFlag</i> [OUT]	<ul style="list-style-type: none"> <li>• SMS Attempted Flag.</li> </ul>

## 8.554.2 Field Documentation

8.554.2.1 uint8\_t\* packgetDyingGaspStatistics::pSMSAttemptedFlag

8.554.2.2 uint32\_t\* packgetDyingGaspStatistics::pTimeStamp

## 8.555 PCMparams Struct Reference

## Data Fields

- [BYTE iFaceTabLen](#)
- [BYTE iFaceTab](#) [255]

### 8.555.1 Detailed Description

This structure contains the PCM parameters.

## Parameters

<i>iFaceTabLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of iface table</li> </ul>
<i>iFaceTab</i>	<ul style="list-style-type: none"> <li>• Physical Interface Parameters</li> <li>• See <a href="#">qaGobiApiTableSwiAudio.h</a> for more information on physical interface parameters</li> </ul>

## 8.555.2 Field Documentation

8.555.2.1 BYTE PCMparams::iFaceTab[255]

8.555.2.2 BYTE PCMparams::iFaceTabLen

## 8.556 PCSCFFQDNAddress Struct Reference

## Data Fields

- [WORD fqdnLen](#)
- [CHAR fqdnAddr](#) [256]

## 8.556.1 Detailed Description

This structure contains the [PCSCFFQDNAddress](#) Information

## Parameters

<i>fqdnLen</i>	<ul style="list-style-type: none"> <li>• length of the received FQDN address</li> </ul>
<i>fqdnAddr</i>	<ul style="list-style-type: none"> <li>• FQDN address(Max 256 characters)</li> </ul>

## 8.556.2 Field Documentation

8.556.2.1 CHAR PCSCFFQDNAddress::fqdnAddr[256]

8.556.2.2 WORD PCSCFFQDNAddress::fqdnLen

## 8.557 PCSCFFQDNAddressList Struct Reference

## Data Fields

- [BYTE numInstances](#)
- struct [PCSCFFQDNAddress](#) [pcsfQDNAddress](#) [10]

### 8.557.1 Detailed Description

This structure contains the [PCSCFFQDNAddressList](#) Information



## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of FQDN addresses received</li> </ul>
<i>pcsfFQDN-Address</i>	<ul style="list-style-type: none"> <li>• FQDN address information(Max 10 addresses)</li> </ul>

## 8.557.2 Field Documentation

8.557.2.1 BYTE PCSCFFQDNAddressList::numInstances

8.557.2.2 struct PCSCFFQDNAddress PCSCFFQDNAddressList::pcsfFQDNAddress[10]

## 8.558 PCSCFIPv4ServerAddressList Struct Reference

## Data Fields

- [BYTE numInstances](#)
- [ULONG pcsfIPv4Addr](#) [64]

## 8.558.1 Detailed Description

This structure contains the [PCSCFIPv4ServerAddressList](#) Information

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• number of address following</li> </ul>
<i>pcsfIPv4Addr</i>	<ul style="list-style-type: none"> <li>• P-CSCF IPv4 server addresses(Max 16 address, 4 bytes each)</li> </ul>

## 8.558.2 Field Documentation

8.558.2.1 BYTE PCSCFIPv4ServerAddressList::numInstances

8.558.2.2 ULONG PCSCFIPv4ServerAddressList::pcsfIPv4Addr[64]

## 8.559 PDSPositionData Struct Reference

## Data Fields

- [ULONGLONG \\* pTimeStamp](#)
- [ULONGLONG \\* pLatitude](#)
- [ULONGLONG \\* pLongitude](#)
- [ULONG \\* pAltitudeWrtEllipsoid](#)
- [ULONG \\* pAltitudeWrtSealevel](#)
- [ULONG \\* pHorizontalUncCircular](#)
- [ULONG \\* pVerticalUnc](#)

- BYTE \* pHorizontalConfidence
- BYTE \* pVerticalConfidence
- BYTE \* pPositionSource
- BYTE \* pTimeType

### 8.559.1 Detailed Description

Position Data Parameters from the external source to be injected to PDS engine.

#### Parameters

<i>pTimeStamp</i>	<ul style="list-style-type: none"> <li>• Timestamp of the injected position in msec. The time can be of type UTC, GPS, or Age and is defined in the pTimeType parameter. If the pTimeType is not present, the timestamp shall be assumed to be UTC time</li> </ul>
<i>pLatitude</i>	<ul style="list-style-type: none"> <li>• Latitude position referenced to the WGS-84 reference ellipsoid, counting positive angles north of the equator and negative angles south of the equator. Value (in decimal degrees) in the range from -90 degrees to +90 degrees. Value in double float format (refer to IEEE Std 754-1985)</li> </ul>
<i>pLongitude</i>	<ul style="list-style-type: none"> <li>• Longitude position referenced to the WGS-84 reference ellipsoid, counting positive angles east of the Greenwich Meridian and negative angles west of Greenwich meridian. Value (in decimal degrees) in the range from -180 degrees to +180 degrees.</li> </ul>
<i>pAltitudeWrt-Ellipsoid</i>	<ul style="list-style-type: none"> <li>• Height above the WGS-84 reference ellipsoid. Value conveys height (in meters). When injecting altitude information, the control point should include either this parameter or the pAltitudeWrtSealevel parameter. Value in single float format (refer to IEEE Std 754-1985)</li> </ul>
<i>pAltitudeWrt-Sealevel</i>	<ul style="list-style-type: none"> <li>• Height of MS above the mean sea level in units (in meters). When injecting altitude information, the control point should include either this parameter or the pAltitudeWrt-Ellipsoid parameter. Value in single float format (refer to IEEE Std 754-1985)</li> </ul>
<i>pHorizontalUnc-Circular</i>	<ul style="list-style-type: none"> <li>• Circular horizontal uncertainty (in meters). This parameter must be included if the latitude and longitude parameters are specified. Value in single float format (refer to IEEE Std 754-1985)</li> </ul>
<i>pVerticalUnc</i>	<ul style="list-style-type: none"> <li>• Vertical uncertainty (in meters). This parameter must be included if one of the altitude parameter are specified. Value in single float format (refer to IEEE Std 754-1985)</li> </ul>
<i>pHorizontal-Confidence</i>	<ul style="list-style-type: none"> <li>• Confidence value of the location horizontal uncertainty, specified as percentage, 1 to 100. This parameter must be included if the latitude and longitude parameters are specified.</li> </ul>

<i>pVertical-Confidence</i>	<ul style="list-style-type: none"> <li>Confidence value of the location vertical uncertainty, specified as percentage, 1 to 100. This parameter must be included if one of the altitude paramters are specified.</li> </ul>
<i>pPositionSource</i>	<ul style="list-style-type: none"> <li>Source of injected position: <ul style="list-style-type: none"> <li>0x00 - Unknown</li> <li>0x01 - GPS</li> <li>0x02 - Cell ID</li> <li>0x03 - Enhanced cell ID</li> <li>0x04 - WiFi</li> <li>0x05 - Terrestrial</li> <li>0x06 - Terrestrial hybrid</li> <li>0x07 - Other</li> </ul> </li> </ul>
<i>pTimeType</i>	<ul style="list-style-type: none"> <li>Defines the time value set in the pTimeStamp parameter. <ul style="list-style-type: none"> <li>0x00 - UTC Time: starting Jan 1, 1970</li> <li>0x01 - GPS Time: starting Jan 6, 1980</li> <li>0x02 - Age: Age of position information</li> </ul> </li> </ul>

## 8.559.2 Field Documentation

8.559.2.1 **ULONG\*** PDSPositionData::pAltitudeWrtEllipsoid

8.559.2.2 **ULONG\*** PDSPositionData::pAltitudeWrtSealevel

8.559.2.3 **BYTE\*** PDSPositionData::pHorizontalConfidence

8.559.2.4 **ULONG\*** PDSPositionData::pHorizontalUncCircular

8.559.2.5 **ULONGLONG\*** PDSPositionData::pLatitude

8.559.2.6 **ULONGLONG\*** PDSPositionData::pLongitude

8.559.2.7 **BYTE\*** PDSPositionData::pPositionSource

8.559.2.8 **ULONGLONG\*** PDSPositionData::pTimeStamp

8.559.2.9 **BYTE\*** PDSPositionData::pTimeType

8.559.2.10 **BYTE\*** PDSPositionData::pVerticalConfidence

8.559.2.11 **ULONG\*** PDSPositionData::pVerticalUnc

## 8.560 PDSPosMethodStateReq Struct Reference

## Data Fields

- [BYTE \\* pXtraTimeState](#)
- [BYTE \\* pXtraDataState](#)
- [BYTE \\* pWifiState](#)

### 8.560.1 Detailed Description

Parameters to Set state of positioning method for a device.

#### Parameters

<i>pXtraTimeState</i>	<ul style="list-style-type: none"> <li>• XTRA Time Position Method State.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>pXtraDataState</i>	<ul style="list-style-type: none"> <li>• XTRA Data Position Method State.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>Latitude</i>	<ul style="list-style-type: none"> <li>• WiFi Position Method State</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>

### 8.560.2 Field Documentation

8.560.2.1 **BYTE\*** PDSPosMethodStateReq::pWifiState

8.560.2.2 **BYTE\*** PDSPosMethodStateReq::pXtraDataState

8.560.2.3 **BYTE\*** PDSPosMethodStateReq::pXtraTimeState

## 8.561 peerNumberInfo Struct Reference

### Data Fields

- [BYTE callID](#)
- [BYTE numPI](#)
- [BYTE numSI](#)
- [BYTE numType](#)

- [BYTE numPlan](#)
- [BYTE numLen](#)
- [BYTE number](#) [81]

### 8.561.1 Detailed Description

This structure contains information for Connected Peer Numbers.

#### Parameters

<i>callID</i>	<ul style="list-style-type: none"> <li>• Unique call identifier for the call.</li> </ul>
<i>numPI</i>	<ul style="list-style-type: none"> <li>• Number presentation indicator. <ul style="list-style-type: none"> <li>– 0x00 - PRESENTATION_ALLOWED - Allowed presentation</li> <li>– 0x01 - PRESENTATION_RESTRICTED - Restricted presentation</li> <li>– 0x02 - PRESENTATION_NUM_UNAVAILABLE - Unavailable presentation</li> <li>– 0x04 - PRESENTATION_PAYPHONE - Payphone presentation (GSM/UMTS specific)</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>numSI</i>	<ul style="list-style-type: none"> <li>• Number screening indicator. <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_SI_USER_PROVIDED_NOT_SCREENED - Provided user is not screened</li> <li>– 0x01 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_PASSED - Provided user passed verification</li> <li>– 0x02 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_FAILED - Provided user failed verification</li> <li>– 0x03 - QMI_VOICE_SI_NETWORK_PROVIDED - Provided network</li> </ul> </li> </ul>
<i>numType</i>	<ul style="list-style-type: none"> <li>• Number type. <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_TYPE_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_TYPE_INTERNATIONAL - International</li> <li>– 0x02 - QMI_VOICE_NUM_TYPE_NATIONAL - National</li> <li>– 0x03 - QMI_VOICE_NUM_TYPE_NETWORK_SPECIFIC - Network-specific</li> <li>– 0x04 - QMI_VOICE_NUM_TYPE_SUBSCRIBER - Subscriber</li> <li>– 0x05 - QMI_VOICE_NUM_TYPE_RESERVED - Reserved</li> <li>– 0x06 - QMI_VOICE_NUM_TYPE_ABBREVIATED - Abbreviated</li> <li>– 0x07 - QMI_VOICE_NUM_TYPE_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>

<i>numPlan</i>	<ul style="list-style-type: none"> <li>• Number plan. <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_PLAN_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_PLAN_ISDN - ISDN</li> <li>– 0x03 - QMI_VOICE_NUM_PLAN_DATA - Data</li> <li>– 0x04 - QMI_VOICE_NUM_PLAN_TELEX - Telex</li> <li>– 0x08 - QMI_VOICE_NUM_PLAN_NATIONAL - National</li> <li>– 0x09 - QMI_VOICE_NUM_PLAN_PRIVATE - Private</li> <li>– 0x0B - QMI_VOICE_NUM_PLAN_RESERVED_CTS - Reserved cordless telephony system</li> <li>– 0x0F - QMI_VOICE_NUM_PLAN_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>
<i>numLen</i>	<ul style="list-style-type: none"> <li>• Provides the length of number which follow.</li> </ul>
<i>number[<b>MAX_CALL_NO_LEN</b>]</i>	<ul style="list-style-type: none"> <li>• number of numLen length, NULL terminated.</li> </ul>

## 8.561.2 Field Documentation

8.561.2.1 **BYTE** peerNumberInfo::callID

8.561.2.2 **BYTE** peerNumberInfo::number[81]

8.561.2.3 **BYTE** peerNumberInfo::numLen

8.561.2.4 **BYTE** peerNumberInfo::numPl

8.561.2.5 **BYTE** peerNumberInfo::numPlan

8.561.2.6 **BYTE** peerNumberInfo::numSI

8.561.2.7 **BYTE** peerNumberInfo::numType

## 8.562 personalizationStatus Struct Reference

### Data Fields

- [BYTE](#) numFeatures
- [BYTE](#) feature [12]
- [BYTE](#) verifyLeft [12]
- [BYTE](#) unblockLeft [12]

### 8.562.1 Detailed Description

This structure contains the information about the card result.

## Parameters

<i>numFeatures</i>	<ul style="list-style-type: none"> <li>• Number of active personalization features. The following block is repeated for each feature.</li> </ul>
<i>feature</i>	<ul style="list-style-type: none"> <li>• Indicates the personalization feature to deactivate or unblock. Valid values: <ul style="list-style-type: none"> <li>– 0 - GW network personalization</li> <li>– 1 - GW network subset personalization</li> <li>– 2 - GW service provider personalization</li> <li>– 3 - GW corporate personalization</li> <li>– 4 - GW UIM personalization</li> <li>– 5 - 1X network type 1 personalization</li> <li>– 6 - 1X network type 2 personalization</li> <li>– 7 - 1X HRPD personalization</li> <li>– 8 - 1X service provider personalization</li> <li>– 9 - 1X corporate personalization</li> <li>– 10 - 1X RUIM personalization</li> </ul> </li> </ul>
<i>verifyLeft</i>	<ul style="list-style-type: none"> <li>• Number of the remaining attempts to verify the personalization feature.</li> </ul>
<i>unblockLeft</i>	<ul style="list-style-type: none"> <li>• Number of the remaining attempts to unblock the personalization feature.</li> </ul>

## 8.562.2 Field Documentation

8.562.2.1 BYTE personalizationStatus::feature[12]

8.562.2.2 BYTE personalizationStatus::numFeatures

8.562.2.3 BYTE personalizationStatus::unblockLeft[12]

8.562.2.4 BYTE personalizationStatus::verifyLeft[12]

## 8.563 PhyCaAggPcellInfo Struct Reference

## Data Fields

- int [pci](#)
- int [freq](#)
- [NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB dl\\_bw\\_value](#)
- int [iLTEbandValue](#)
- [BYTE TlvPresent](#)

### 8.563.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation of Pcell Information.



## Parameters

<i>pci</i>	<ul style="list-style-type: none"> <li>Physical cell ID of the SCell Range.</li> <li>Range for ID values: 0 to 503.</li> </ul>
<i>freq</i>	<ul style="list-style-type: none"> <li>Frequency of the absolute cell Range.</li> <li>Range for ID values: 0 to 65535.</li> </ul>
<i>dl_bw_value</i>	<ul style="list-style-type: none"> <li>Downlink Bandwidth Values.</li> <li>See <a href="#">NAS_LTE_CPHY_CA_BW_NRB</a> for more information.</li> </ul>
<i>scell_state</i>	<ul style="list-style-type: none"> <li>Scell state Values.</li> <li>See <a href="#">NAS_LTE_CPHY_SCELL_STATE</a> for more information.</li> </ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>Tlv Present.</li> </ul>

## 8.563.2 Field Documentation

8.563.2.1 NAS\_LTE\_CPHY\_CA\_BW\_NRB PhyCaAggPcellInfo::dl\_bw\_value

8.563.2.2 int PhyCaAggPcellInfo::freq

8.563.2.3 int PhyCaAggPcellInfo::lTEbandValue

8.563.2.4 int PhyCaAggPcellInfo::pci

8.563.2.5 BYTE PhyCaAggPcellInfo::TlvPresent

## 8.564 PhyCaAggScellIDIBw Struct Reference

## Data Fields

- [NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB dl\\_bw\\_value](#)
- [BYTE TlvPresent](#)

## 8.564.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation Downlink Bandwidth of Scell.

## Parameters

<i>dl_bw_value</i>	<ul style="list-style-type: none"> <li>• Downlink Bandwidth Values.</li> <li>• See <a href="#">NAS_LTE_CPHY_CA_BW_NRB</a> for more information.</li> </ul>
--------------------	--

## 8.564.2 Field Documentation

8.564.2.1 **NAS\_LTE\_CPHY\_CA\_BW\_NRB** `PhyCaAggScellIDIBw::dl_bw_value`

8.564.2.2 **BYTE** `PhyCaAggScellIDIBw::TlvPresent`

## 8.565 PhyCaAggScellIndex Struct Reference

### Data Fields

- [BYTE](#) `scell_idx`
- [BYTE](#) `TlvPresent`

### 8.565.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation of Scell Index.

#### Parameters

<i>scell_idx</i>	<ul style="list-style-type: none"> <li>• Physical cell ID of the SCell Range.</li> <li>• Range for ID values: 0 to 503.</li> </ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Tlv Present.</li> </ul>

## 8.565.2 Field Documentation

8.565.2.1 **BYTE** `PhyCaAggScellIndex::scell_idx`

8.565.2.2 **BYTE** `PhyCaAggScellIndex::TlvPresent`

## 8.566 PhyCaAggScellIndType Struct Reference

### Data Fields

- int `pci`
- int `freq`
- [NAS\\_LTE\\_CPHY\\_SCELL\\_STATE](#) `scell_state`
- [BYTE](#) `TlvPresent`

### 8.566.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation of Scell Indicator Type.

## Parameters

<i>pci</i>	<ul style="list-style-type: none"> <li>Physical cell ID of the SCell Range.</li> <li>Range for ID values: 0 to 503.</li> </ul>
<i>freq</i>	<ul style="list-style-type: none"> <li>Frequency of the absolute cell Range.</li> <li>Range for ID values: 0 to 65535.</li> </ul>
<i>scell_state</i>	<ul style="list-style-type: none"> <li>Scell state Values.</li> <li>See <a href="#">NAS_LTE_CPHY_SCELL_STATE</a> for more information.</li> </ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>Tlv Present.</li> </ul>

## 8.566.2 Field Documentation

8.566.2.1 int PhyCaAggScellIndType::freq

8.566.2.2 int PhyCaAggScellIndType::pci

8.566.2.3 NAS\_LTE\_CPHY\_SCELL\_STATE PhyCaAggScellIndType::scell\_state

8.566.2.4 BYTE PhyCaAggScellIndType::TlvPresent

## 8.567 PhyCaAggScellInfo Struct Reference

## Data Fields

- int [pci](#)
- int [freq](#)
- [NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB dl\\_bw\\_value](#)
- int [iLTEbandValue](#)
- [NAS\\_LTE\\_CPHY\\_SCELL\\_STATE](#) [scell\\_state](#)
- BYTE [TlvPresent](#)

## 8.567.1 Detailed Description

This structure contains the parameters for Physical Carrier aggregation of Scell Information.

## Parameters

<i>pci</i>	<ul style="list-style-type: none"> <li>Physical cell ID of the SCell Range.</li> <li>Range for ID values: 0 to 503.</li> </ul>
------------	--

<i>freq</i>	<ul style="list-style-type: none"> <li>• Frequency of the absolute cell Range.</li> <li>• Range for ID values: 0 to 65535.</li> </ul>
<i>dl_bw_value</i>	<ul style="list-style-type: none"> <li>• Downlink Bandwidth Values.</li> <li>• See <a href="#">NAS_LTE_CPHY_CA_BW_NRB</a> for more information.</li> </ul>
<i>iLTEbandValue</i>	<ul style="list-style-type: none"> <li>• Band value.</li> <li>• Range for LTE Band class 120 to 160. <ul style="list-style-type: none"> <li>– 120 - LTE E-UTRA Operating Band 1</li> <li>– 121 - LTE E-UTRA Operating Band 2</li> <li>– 122 - LTE E-UTRA Operating Band 3</li> <li>– 123 - LTE E-UTRA Operating Band 4</li> <li>– 124 - LTE E-UTRA Operating Band 5</li> <li>– 125 - LTE E-UTRA Operating Band 6</li> <li>– 126 - LTE E-UTRA Operating Band 7</li> <li>– 127 - LTE E-UTRA Operating Band 8</li> <li>– 128 - LTE E-UTRA Operating Band 9</li> <li>– 129 - LTE E-UTRA Operating Band 10</li> <li>– 130 - LTE E-UTRA Operating Band 11</li> <li>– 131 - LTE E-UTRA Operating Band 12</li> <li>– 132 - LTE E-UTRA Operating Band 13</li> <li>– 133 - LTE E-UTRA Operating Band 14</li> <li>– 134 - LTE E-UTRA Operating Band 17</li> <li>– 135 - LTE E-UTRA Operating Band 33</li> <li>– 136 - LTE E-UTRA Operating Band 34</li> <li>– 137 - LTE E-UTRA Operating Band 35</li> <li>– 138 - LTE E-UTRA Operating Band 36</li> <li>– 139 - LTE E-UTRA Operating Band 37</li> <li>– 140 - LTE E-UTRA Operating Band 38</li> <li>– 141 - LTE E-UTRA Operating Band 39</li> <li>– 142 - LTE E-UTRA Operating Band 40</li> <li>– 143 - LTE E-UTRA Operating Band 18</li> <li>– 144 - LTE E-UTRA Operating Band 19</li> <li>– 145 - LTE E-UTRA Operating Band 20</li> <li>– 146 - LTE E-UTRA Operating Band 21</li> <li>– 147 - LTE E-UTRA Operating Band 24</li> <li>– 148 - LTE E-UTRA Operating Band 25</li> <li>– 149 - LTE E-UTRA Operating Band 41</li> <li>– 150 - LTE E-UTRA Operating Band 42</li> <li>– 151 - LTE E-UTRA Operating Band 43</li> <li>– 152 - LTE E-UTRA Operating Band 23</li> <li>– 153 - LTE E-UTRA Operating Band 26</li> <li>– 154 - LTE E-UTRA Operating Band 32</li> <li>– 155 - LTE E-UTRA Operating Band 125</li> <li>– 156 - LTE E-UTRA Operating Band 126</li> <li>– 157 - LTE E-UTRA Operating Band 127</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– 154 - LTE E-UTRA Operating Band 32</li> <li>– 155 - LTE E-UTRA Operating Band 125</li> <li>– 156 - LTE E-UTRA Operating Band 126</li> <li>– 157 - LTE E-UTRA Operating Band 127</li> </ul>

<i>scell_state</i>	<ul style="list-style-type: none"><li>• Scell state Values.</li><li>• See <a href="#">NAS_LTE_CPHY_SCELL_STATE</a> for more information.</li></ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"><li>• Tlv Present.</li></ul>

## 8.567.2 Field Documentation

8.567.2.1 **NAS\_LTE\_CPHY\_CA\_BW\_NRB** `PhyCaAggScellInfo::dl_bw_value`

8.567.2.2 `int` `PhyCaAggScellInfo::freq`

8.567.2.3 `int` `PhyCaAggScellInfo::ltebandValue`

8.567.2.4 `int` `PhyCaAggScellInfo::pci`

8.567.2.5 **NAS\_LTE\_CPHY\_SCELL\_STATE** `PhyCaAggScellInfo::scell_state`

8.567.2.6 **BYTE** `PhyCaAggScellInfo::TlvPresent`

## 8.568 PilotSetData Struct Reference

### Data Fields

- [BYTE](#) `NumPilots`
- [PilotSetParams](#) \* `pPilotSetInfo`

### 8.568.1 Detailed Description

This structure contains Pilot Set Data

#### Parameters

<i>NumPilots(IN/O-UT)</i>	<ul style="list-style-type: none"><li>• Number of Pilot Sets</li><li>• As input specifies number of sets of parameter <code>pPilotSetInfo</code> for which memory has been assigned</li><li>• As output specifies the actual number of sets of parameter <code>pPilotSetInfo</code> returned by device</li></ul>
---------------------------	--

<i>pPilotSetInfo</i>	<ul style="list-style-type: none"> <li>• Pilot Set Parameters</li> <li>• See <a href="#">PilotSetParams</a> for more information.</li> </ul>
----------------------	--

note A buffer under sized error is returned if the number of sets of pPilotSetInfo returned by the device is greater than the value in NumPilots input parameter.

## 8.568.2 Field Documentation

### 8.568.2.1 BYTE PilotSetData::NumPilots

### 8.568.2.2 PilotSetParams\* PilotSetData::pPilotSetInfo

## 8.569 PilotSetParams Struct Reference

### Data Fields

- [ULONG PilotType](#)
- [WORD PilotPN](#)
- [WORD PilotStrength](#)

### 8.569.1 Detailed Description

This structure contains Pilot Set parameters

#### Parameters

<i>PilotType</i>	<ul style="list-style-type: none"> <li>• 0x00 - NAS_HRPD_PILOT_CURR_ACT_PLT Current Active Pilot</li> <li>• 0x01 - NAS_HRPD_PILOT_NEIGHBOR_PLT Neighbor pilot information</li> </ul>
<i>PilotPN</i>	<ul style="list-style-type: none"> <li>• Pilot PN sequence offset index</li> </ul>
<i>PilotStrength</i>	<ul style="list-style-type: none"> <li>• Strength of the pilot (in dB)</li> </ul>

## 8.569.2 Field Documentation

### 8.569.2.1 WORD PilotSetParams::PilotPN

### 8.569.2.2 WORD PilotSetParams::PilotStrength

### 8.569.2.3 ULONG PilotSetParams::PilotType

## 8.570 pktErrRate Struct Reference

### Data Fields

- [WORD multiplier](#)

- [WORD exponent](#)

### 8.570.1 Detailed Description

This structure contains the IP flow packet error rate

Parameters

<i>multiplier</i>	Factor m in calculating packet error rate: $E = m \cdot 10^{**}(-p)$
<i>exponent</i>	Factor p in calculating packet error rate (see above)

### 8.570.2 Field Documentation

8.570.2.1 [WORD pktErrRate::exponent](#)

8.570.2.2 [WORD pktErrRate::multiplier](#)

## 8.571 PLMNNetworkName Struct Reference

### Data Fields

- [BYTE numInstance](#)
- [PLMNNetworkNameData PLMNNetName](#) [255]

### 8.571.1 Detailed Description

This structure contains PLMN Network Name as defined in 3GPP TS 24.008 (Section 10.5.3.5a) from multiple sources.

Parameters

<i>numInstance</i>	<ul style="list-style-type: none"><li>• Number of sets of the elements.</li></ul>
<i>PLMNNetName</i>	<ul style="list-style-type: none"><li>• Refer <a href="#">PLMNNetworkNameData</a> for details (Optional).</li></ul>

### 8.571.2 Field Documentation

8.571.2.1 [BYTE PLMNNetworkName::numInstance](#)

8.571.2.2 [PLMNNetworkNameData PLMNNetworkName::PLMNNetName](#)[255]

## 8.572 PLMNNetworkNameData Struct Reference

### Data Fields

- [BYTE codingScheme](#)
- [BYTE countryInitials](#)
- [BYTE longNameSpareBits](#)
- [BYTE shortNameSpareBits](#)
- [BYTE longNameLen](#)

- [BYTE longName](#) [255]
- [BYTE shortNameLen](#)
- [BYTE shortName](#) [255]

### 8.572.1 Detailed Description

This structure contains PLMN Network Name Data from multiple sources.

#### Parameters

<i>codingScheme</i>	<ul style="list-style-type: none"> <li>• Coding scheme:             <ul style="list-style-type: none"> <li>– 0 - CODING_SCHEME_CELL_BROADCAST_GSM - Cell broadcast data coding scheme, GSM default alphabet, language unspecified;defined in 3GPP TS 23.-038.</li> <li>– 1 - CODING_SCHEME_UCS2 - UCS2 (16 bit);defined in ISO/IEC 10646</li> </ul> </li> </ul>
<i>countryInitials</i>	<ul style="list-style-type: none"> <li>• Country's initials:             <ul style="list-style-type: none"> <li>– 0 - COUNTRY_INITIALS_DO_NOT_ADD - MS should not add the letters for the country's initials to the text string.</li> <li>– 1 - COUNTRY_INITIALS_ADD - MS should add the letters for the country's initials and a separator, e.g., a space, to the text string.</li> </ul> </li> </ul>
<i>longNameSpare-Bits</i>	<ul style="list-style-type: none"> <li>• Long Name Spare Bits:             <ul style="list-style-type: none"> <li>– 1 - SPARE_BITS_8 - Bit 8 is spare and set to 0 in octet n</li> <li>– 2 - SPARE_BITS_7_TO_8 - Bits 7 and 8 are spare and set to 0 in octet n.</li> <li>– 3 - SPARE_BITS_6_TO_8 - Bits 6 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 4 - SPARE_BITS_5_TO_8 - Bits 5 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 5 - SPARE_BITS_4_TO_8 - Bits 4 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 6 - SPARE_BITS_3_TO_8 - Bits 3 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 7 - SPARE_BITS_2_TO_8 - Bits 2 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 0 - SPARE_BITS_UNKNOWN - Carries no information about the number of spare bits in octet n.</li> </ul> </li> </ul>



<i>shortName-SpareBits</i>	<ul style="list-style-type: none"> <li>• Short Name Spare Bits: <ul style="list-style-type: none"> <li>– 1 - SPARE_BITS_8 - Bit 8 is spare and set to 0 in octet n.</li> <li>– 2 - SPARE_BITS_7_TO_8 - Bits 7 and 8 are spare and set to 0 in octet n.</li> <li>– 3 - SPARE_BITS_6_TO_8 - Bits 6 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 4 - SPARE_BITS_5_TO_8 - Bits 5 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 5 - SPARE_BITS_4_TO_8 - Bits 4 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 6 - SPARE_BITS_3_TO_8 - Bits 3 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 7 - SPARE_BITS_2_TO_8 - Bits 2 to 8 (inclusive) are spare and set to 0 in octet n.</li> <li>– 0 - SPARE_BITS_UNKNOWN - Carries no information about the number of spare bits in octet n.</li> </ul> </li> </ul>
<i>longNameLen</i>	<ul style="list-style-type: none"> <li>• It provides the length of long name.</li> </ul>
<i>longName</i>	<ul style="list-style-type: none"> <li>• Long name string in coding_scheme.</li> </ul>
<i>shortNameLen</i>	<ul style="list-style-type: none"> <li>• It provides the length of short name.</li> </ul>
<i>shortName</i>	<ul style="list-style-type: none"> <li>• Short name string in coding_scheme.</li> </ul>

## 8.572.2 Field Documentation

8.572.2.1 BYTE PLMNNetworkNameData::codingScheme

8.572.2.2 BYTE PLMNNetworkNameData::countryInitials

8.572.2.3 BYTE PLMNNetworkNameData::longName[255]

8.572.2.4 BYTE PLMNNetworkNameData::longNameLen

8.572.2.5 BYTE PLMNNetworkNameData::longNameSpareBits

8.572.2.6 BYTE PLMNNetworkNameData::shortName[255]

8.572.2.7 BYTE PLMNNetworkNameData::shortNameLen

8.572.2.8 BYTE PLMNNetworkNameData::shortNameSpareBits

## 8.573 Port Struct Reference

## Data Fields

- [WORD port](#)
- [WORD range](#)

### 8.573.1 Detailed Description

This structure contains the [Port](#) Filter

#### Parameters

<i>port</i>	port value of the filter
<i>range</i>	range specifies the number of ports to be included in the filter starting from port; filter will match if port in the IP packet lies between port and (port + range ) Range value of 0 implies that only one value of the port is valid, as specified by the port

### 8.573.2 Field Documentation

#### 8.573.2.1 WORD Port::port

#### 8.573.2.2 WORD Port::range

## 8.574 precisionDilution\_s Struct Reference

## Data Fields

- [ULONG PDOP](#)
- [ULONG HDOP](#)
- [ULONG VDOP](#)

### 8.574.1 Detailed Description

This structure contains Dilution of precision associated with this position.

#### Parameters

<i>PDOP</i>	<ul style="list-style-type: none"> <li>• Position dilution of precision.</li> <li>• Range - 1 (highest accuracy) to 50 (lowest accuracy)</li> <li>• PDOP = square root of (Square of HDOP + Square of VDOP<sup>2</sup> )</li> </ul>
<i>HDOP</i>	<ul style="list-style-type: none"> <li>• Horizontal dilution of precision.</li> <li>• Range - 1 (highest accuracy) to 50 (lowest accuracy)</li> </ul>
<i>VDOP</i>	<ul style="list-style-type: none"> <li>• Vertical dilution of precision.</li> <li>• Range- 1 (highest accuracy) to 50 (lowest accuracy)</li> </ul>

### 8.574.2 Field Documentation

8.574.2.1 `ULONG` precisionDilution\_s::HDOP

8.574.2.2 `ULONG` precisionDilution\_s::PDOP

8.574.2.3 `ULONG` precisionDilution\_s::VDOP

## 8.575 PrefImageList Struct Reference

### Data Fields

- `BYTE` [listSize](#)
- struct [ImageElement](#) [listEntries](#) [2]

### 8.575.1 Detailed Description

This structure contains the Preference Image List information

#### Parameters

<i>listSize</i>	<ul style="list-style-type: none"><li>• The number of elements in the image list</li></ul>
<i>listEntries</i>	<ul style="list-style-type: none"><li>• Array of Image entries( Max array size 2 )</li><li>• See <a href="#">ImageElement</a></li></ul>

### 8.575.2 Field Documentation

8.575.2.1 struct [ImageElement](#) [PrefImageList::listEntries](#)[2]

8.575.2.2 `BYTE` [PrefImageList::listSize](#)

## 8.576 prefVoiceSO Struct Reference

### Data Fields

- `BYTE` [namID](#)
- `BYTE` [evrcCapability](#)
- `WORD` [homePageVoiceSO](#)
- `WORD` [homeOrigVoiceSO](#)
- `WORD` [roamOrigVoiceSO](#)

### 8.576.1 Detailed Description

This structure contains information about the Preferred Voice Service Options.

## Parameters

<i>namID</i>	<ul style="list-style-type: none"> <li>• Index of the NAM(Number Assignment Module) to be configured.</li> <li>• Range 0 to 3.</li> <li>• Some modems support only 1 or 2 NAMs.</li> <li>• 0xFF,if not available.</li> </ul>
<i>evrcCapability</i>	<ul style="list-style-type: none"> <li>• EVRC capability.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>homePageVoice-SO</i>	<ul style="list-style-type: none"> <li>• Home page voice SO; most preferred CDMA SO to be requested from the network when receiving an incoming (MT) voice call within the home network.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x0000 - VOICE_SO_WILD - Any service option</li> <li>– 0x0001 - VOICE_SO_IS_96A - IS-96A</li> <li>– 0x0003 - VOICE_SO_EVRC - EVRC</li> <li>– 0x0011 - VOICE_SO_13K_IS733 - 13K_IS733</li> <li>– 0x0038 - VOICE_SO_SELECTABLE_MODE_VOCODER - Selectable mode vocoder</li> <li>– 0x0044 - VOICE_SO_4GV_NARROW_BAND - 4GV narrowband</li> <li>– 0x0046 - VOICE_SO_4GV_WIDE_BAND - 4GV wideband</li> <li>– 0x8000 - VOICE_SO_13K - 13K</li> <li>– 0x8001 - VOICE_SO_IS_96 - IS-96</li> <li>– 0x8023 - VOICE_SO_WVRC - WVRC</li> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>

<i>homeOrigVoiceSO</i>	<ul style="list-style-type: none"> <li>• Home origination voice SO; most preferred CDMA SO to be requested from the network when receiving an incoming (MT) voice call within the home network.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x0000 - VOICE_SO_WILD - Any service option</li> <li>– 0x0001 - VOICE_SO_IS_96A - IS-96A</li> <li>– 0x0003 - VOICE_SO_EVRC - EVRC</li> <li>– 0x0011 - VOICE_SO_13K_IS733 - 13K_IS733</li> <li>– 0x0038 - VOICE_SO_SELECTABLE_MODE_VOCODER - Selectable mode vocoder</li> <li>– 0x0044 - VOICE_SO_4GV_NARROW_BAND - 4GV narrowband</li> <li>– 0x0046 - VOICE_SO_4GV_WIDE_BAND - 4GV wideband</li> <li>– 0x8000 - VOICE_SO_13K - 13K</li> <li>– 0x8001 - VOICE_SO_IS_96 - IS-96</li> <li>– 0x8023 - VOICE_SO_WVRC - WVRC</li> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>roamOrigVoiceSO</i>	<ul style="list-style-type: none"> <li>• Roaming origination voice SO; most preferred CDMA SO to be requested from the network when receiving an incoming (MT) voice call within the home network.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x0000 - VOICE_SO_WILD - Any service option</li> <li>– 0x0001 - VOICE_SO_IS_96A - IS-96A</li> <li>– 0x0003 - VOICE_SO_EVRC - EVRC</li> <li>– 0x0011 - VOICE_SO_13K_IS733 - 13K_IS733</li> <li>– 0x0038 - VOICE_SO_SELECTABLE_MODE_VOCODER - Selectable mode vocoder</li> <li>– 0x0044 - VOICE_SO_4GV_NARROW_BAND - 4GV narrowband</li> <li>– 0x0046 - VOICE_SO_4GV_WIDE_BAND - 4GV wideband</li> <li>– 0x8000 - VOICE_SO_13K - 13K</li> <li>– 0x8001 - VOICE_SO_IS_96 - IS-96</li> <li>– 0x8023 - VOICE_SO_WVRC - WVRC</li> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>

## 8.576.2 Field Documentation

### 8.576.2.1 BYTE prefVoiceSO::evrcCapability

### 8.576.2.2 WORD prefVoiceSO::homeOrigVoiceSO

### 8.576.2.3 WORD prefVoiceSO::homePageVoiceSO

### 8.576.2.4 BYTE prefVoiceSO::namID

8.576.2.5 WORD prefVoiceSO::roamOrigVoiceSO

## 8.577 Profile3GPP Struct Reference

### Data Fields

- CHAR \* pProfilename
- WORD \* pProfilenameSize
- BYTE \* pPDPtype
- BYTE \* pPdpHdrCompType
- BYTE \* pPdpDataCompType
- CHAR \* pAPNName
- WORD \* pAPNnameSize
- ULONG \* pPriDNSIPv4AddPref
- ULONG \* pSecDNSIPv4AddPref
- struct UMTSQoS \* pUMTSReqQoS
- struct UMTSQoS \* pUMTSMinQoS
- struct GPRSRequestedQoS \* pGPRSRequestedQoS
- struct GPRSRequestedQoS \* pGPRSMinimumQoS
- CHAR \* pUsername
- WORD \* pUsernameSize
- CHAR \* pPassword
- WORD \* pPasswordSize
- BYTE \* pAuthenticationPref
- ULONG \* pIPv4AddrPref
- BYTE \* pPcscfAddrUsingPCO
- BYTE \* pPdpAccessConFlag
- BYTE \* pPcscfAddrUsingDhcp
- BYTE \* plmCnFlag
- struct TFTIDParams \* pTFTID1Params
- struct TFTIDParams \* pTFTID2Params
- BYTE \* pPdpContext
- BYTE \* pSecondaryFlag
- BYTE \* pPrimaryID
- USHORT \* pIPv6AddPref
- struct UMTSReqQoSSigInd \* pUMTSReqQoSSigInd
- struct UMTSReqQoSSigInd \* pUMTSMinQoSsigInd
- USHORT \* pPriDNSIPv6addpref
- USHORT \* pSecDNSIPv6addpref
- BYTE \* pAddrAllocPref
- struct QoSClassID \* pQoSClassID
- BYTE \* pAPNDisabledFlag
- ULONG \* pPDNInactivTimeout
- BYTE \* pAPNClass

### 8.577.1 Detailed Description

This structure contains Input parameters of SLQSCreateProfile and SLQSModifyProfile and output parameters of SLQSGetProfileSettings

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>pProfileName</i>	<ul style="list-style-type: none"> <li>One or more bytes describing the profile</li> </ul>
<i>pProfileName-Size;</i>	<ul style="list-style-type: none"> <li>This parameter is an input parameter and should be initialised to the size of pProfile-Name field. Size of this parameter is 2 bytes.</li> </ul>
<i>pPDPTType</i>	<ul style="list-style-type: none"> <li>Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile <ul style="list-style-type: none"> <li>0x00 - PDP-IP (IPv4)</li> <li>0x01 - PDP-PPP</li> <li>0x02 - PDP-IPV6</li> <li>0x03 - PDP-IPV4V6</li> </ul> </li> </ul>
<i>pPdpHdrComp-Type</i>	<ul style="list-style-type: none"> <li>PDP header compression type <ul style="list-style-type: none"> <li>0 - PDP header compression is OFF</li> <li>1 - Manufacturer preferred compression</li> <li>2 - PDP header compression based on RFC 1144</li> <li>3 - PDP header compression based on RFC 25074 PDP header compression based on RFC 3095</li> </ul> </li> </ul>
<i>pPdpDataComp-Type</i>	<ul style="list-style-type: none"> <li>PDP data compression type <ul style="list-style-type: none"> <li>0 - PDP data compression is OFF</li> <li>1 - Manufacturer preferred compression</li> <li>2 - V.42BIS data compression</li> <li>3 - V.44 data compression</li> </ul> </li> </ul>
<i>pAPNName</i>	<ul style="list-style-type: none"> <li>Access point name</li> </ul>
<i>pAPNnameSize;</i>	<ul style="list-style-type: none"> <li>This parameter is an input parameter and should be initialised to the size of pAPN-Name field. Size of this parameter is 2 bytes.</li> </ul>
<i>pPriDNSIPv4-AddPref</i>	<ul style="list-style-type: none"> <li>Primary DNS IPv4 Address Preference</li> </ul>

<i>pSecDNSIPv4-AddPref</i>	<ul style="list-style-type: none"> <li>• Secondary DNS IPv4 Address Preference</li> </ul>
<i>pUMTSReqQoS</i>	<ul style="list-style-type: none"> <li>• UMTS Requested QoS</li> </ul>
<i>pUMTSMinQoS</i>	<ul style="list-style-type: none"> <li>• UMTS Minimum QoS</li> </ul>
<i>pGPRS-RequestedQoS</i>	<ul style="list-style-type: none"> <li>• GPRS Minimum QoS</li> </ul>
<i>pUsername</i>	<ul style="list-style-type: none"> <li>• User name</li> </ul>
<i>pUsernameSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pUsername field. Size of this parameter is 2 bytes.</li> </ul>
<i>pPassword</i>	<ul style="list-style-type: none"> <li>• Password</li> </ul>
<i>pPasswordSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pPassword field. Size of this parameter is 2 bytes.</li> </ul>
<i>pAuthentication-Pref</i>	<ul style="list-style-type: none"> <li>• Authentication Preference           <ul style="list-style-type: none"> <li>– Bit map that indicates the authentication algorithm preference               <ul style="list-style-type: none"> <li>* Bit 0 - PAP preference                   <ul style="list-style-type: none"> <li>· 0 - PAP is never performed</li> <li>· 1 - PAP may be performed</li> </ul> </li> <li>* Bit 1 - CHAP preference                   <ul style="list-style-type: none"> <li>· 0 - CHAP is never performed</li> <li>· 1 - CHAP may be performed</li> </ul> </li> <li>* If more than one bit is set, then the device decides which authentication procedure is performed while setting up the data session. For example, the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul> </li> </ul>



<i>pIPv4AddrPref</i>	<ul style="list-style-type: none"> <li>• IPv4 Address Preference</li> </ul>
<i>pPcscfAddr-UsingPCO</i>	<ul style="list-style-type: none"> <li>• P-CSCF Address using PCO Flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies request PCSCF address using PCO</li> <li>– 0 - (FALSE) implies do not request By default, this value is 0</li> </ul> </li> </ul>
<i>pPdpAccess-ConFlag</i>	<ul style="list-style-type: none"> <li>• PDP access control flag <ul style="list-style-type: none"> <li>– 0 - PDP access control none</li> <li>– 1 - PDP access control reject</li> <li>– 2 - PDP access control permission</li> </ul> </li> </ul>
<i>pPcscfAddr-UsingDhcp</i>	<ul style="list-style-type: none"> <li>• P-CSCF address using DHCP <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies Request PCSCF address using DHCP</li> <li>– 0 - (FALSE) implies do not request By default, value is 0</li> </ul> </li> </ul>
<i>plmCnFlag</i>	<ul style="list-style-type: none"> <li>• IM CN flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies request IM CN flag for this profile</li> <li>– 0 - (FALSE) implies do not request IM CN flag for this profile</li> </ul> </li> </ul>
<i>pTFTID1Params</i>	<ul style="list-style-type: none"> <li>• Traffic Flow Template</li> </ul>
<i>pTFTID2Params</i>	<ul style="list-style-type: none"> <li>• Traffic Flow Template</li> </ul>
<i>pPdpContext</i>	<ul style="list-style-type: none"> <li>• PDP context number</li> </ul>
<i>pSecondaryFlag</i>	<ul style="list-style-type: none"> <li>• PDP context secondary flag <ul style="list-style-type: none"> <li>– 1 - (TRUE) implies this is secondary profile</li> <li>– 0 - (FALSE) implies this is not secondary profile</li> </ul> </li> </ul>
<i>pPrimaryID</i>	<ul style="list-style-type: none"> <li>• PDP context primary ID</li> <li>• function <a href="#">SLQSGetProfileSettings()</a> returns a default value 0xFF if this parameter is not returned by the device</li> </ul>

<i>pIPv6AddPref</i>	<ul style="list-style-type: none"> <li>IPv6 address preference Preferred IPv6 address to be assigned to the TE; actual assigned address is negotiated with the network and may differ from this value; if not specified, the IPv6 address is obtained automatically from the network</li> </ul>
<i>pUMTSReqQoS-SigInd</i>	<ul style="list-style-type: none"> <li>UMTS requested QoS with Signalling Indication flag</li> </ul>
<i>pUMTSMInQoS-SigInd</i>	<ul style="list-style-type: none"> <li>UMTS minimum QoS with Signalling Indication flag</li> </ul>
<i>pPrimaryDNSIPv6addpref</i>	<ul style="list-style-type: none"> <li>Primary DNS IPv6 address preference <ul style="list-style-type: none"> <li>The value may be used as a preference during negotiation with the network; if not specified, the wireless device will attempt to obtain the DNS address automatically from the network; the negotiated value is provided to the host via DHCP</li> </ul> </li> </ul>
<i>pSecondaryDNSIPv6addpref</i>	<ul style="list-style-type: none"> <li>Secondary DNS IPv6 address preference</li> </ul>
<i>paddrAllocation-Pref</i>	<ul style="list-style-type: none"> <li>DHCP/NAS preference <ul style="list-style-type: none"> <li>This enumerated value may be used to indicate the address allocation preference <ul style="list-style-type: none"> <li>* 0 - NAS signaling is used for address allocation</li> <li>* 1 - DHCP is used for address allocation</li> </ul> </li> </ul> </li> </ul>
<i>pQoSClassID</i>	<ul style="list-style-type: none"> <li>3GPP LTE QoS parameters</li> </ul>
<i>pAPNDisabled-Flag</i>	<ul style="list-style-type: none"> <li>Optional 1 Byte Flag indicating if the APN is disabled/enabled</li> <li>If set, the profile can not be used for making data calls</li> <li>Any data call is failed locally</li> <li>Values: <ul style="list-style-type: none"> <li>0 - FALSE(default)</li> <li>1 - True</li> </ul> </li> <li>This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

<i>pPDNInactiv-Timeout</i>	<ul style="list-style-type: none"> <li>• Optional 4 Bytes indicating the duration of inactivity timer in seconds</li> <li>• If the PDP context/PDN connection is inactive for this duration i.e. No data Tx/Rx occurs, the PDP context/PDN connection is disconnected</li> <li>• Default value of zero indicates infinite value</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pAPNClass</i>	<ul style="list-style-type: none"> <li>• Optional 1 Byte numeric identifier representing the APN in profile</li> <li>• Can be set and queried but is not used by the modem</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

## 8.577.2 Field Documentation

8.577.2.1 **BYTE\*** Profile3GPP::pAddrAllocPref

8.577.2.2 **BYTE\*** Profile3GPP::pAPNClass

8.577.2.3 **BYTE\*** Profile3GPP::pAPNDisabledFlag

8.577.2.4 **CHAR\*** Profile3GPP::pAPNName

8.577.2.5 **WORD\*** Profile3GPP::pAPNnameSize

8.577.2.6 **BYTE\*** Profile3GPP::pAuthenticationPref

8.577.2.7 **struct GPRSRequestedQoS\*** Profile3GPP::pGPRSMinimumQoS

8.577.2.8 **struct GPRSRequestedQoS\*** Profile3GPP::pGPRSRequestedQoS

8.577.2.9 **BYTE\*** Profile3GPP::plmCnFlag

8.577.2.10 **ULONG\*** Profile3GPP::plPv4AddrPref

8.577.2.11 **USHORT\*** Profile3GPP::plPv6AddPref

8.577.2.12 **CHAR\*** Profile3GPP::pPassword

8.577.2.13 **WORD\*** Profile3GPP::pPasswordSize

8.577.2.14 **BYTE\*** Profile3GPP::pPcscfAddrUsingDhcp

8.577.2.15 **BYTE\*** Profile3GPP::pPcscfAddrUsingPCO

8.577.2.16 **ULONG\*** Profile3GPP::pPDNInactivTimeout

8.577.2.17 **BYTE\*** Profile3GPP::pPdpAccessConFlag

- 8.577.2.18 **BYTE\*** Profile3GPP::pPdpContext
- 8.577.2.19 **BYTE\*** Profile3GPP::pPdpDataCompType
- 8.577.2.20 **BYTE\*** Profile3GPP::pPdpHdrCompType
- 8.577.2.21 **BYTE\*** Profile3GPP::pPDPtype
- 8.577.2.22 **ULONG\*** Profile3GPP::pPriDNSIPv4AddPref
- 8.577.2.23 **USHORT\*** Profile3GPP::pPriDNSIPv6addpref
- 8.577.2.24 **BYTE\*** Profile3GPP::pPrimaryID
- 8.577.2.25 **CHAR\*** Profile3GPP::pProfilename
- 8.577.2.26 **WORD\*** Profile3GPP::pProfilenameSize
- 8.577.2.27 **struct QosClassID\*** Profile3GPP::pQosClassID
- 8.577.2.28 **ULONG\*** Profile3GPP::pSecDNSIPv4AddPref
- 8.577.2.29 **USHORT\*** Profile3GPP::pSecDNSIPv6addpref
- 8.577.2.30 **BYTE\*** Profile3GPP::pSecondaryFlag
- 8.577.2.31 **struct TFTIDParams\*** Profile3GPP::pTFTID1Params
- 8.577.2.32 **struct TFTIDParams\*** Profile3GPP::pTFTID2Params
- 8.577.2.33 **struct UMTSQoS\*** Profile3GPP::pUMTSMinQoS
- 8.577.2.34 **struct UMTSReqQoSSigInd\*** Profile3GPP::pUMTSMinQoSsigInd
- 8.577.2.35 **struct UMTSQoS\*** Profile3GPP::pUMTSReqQoS
- 8.577.2.36 **struct UMTSReqQoSSigInd\*** Profile3GPP::pUMTSReqQoSSigInd
- 8.577.2.37 **CHAR\*** Profile3GPP::pUsername
- 8.577.2.38 **WORD\*** Profile3GPP::pUsernameSize

## 8.578 Profile3GPP2 Struct Reference

### Data Fields

- [BYTE \\*](#) pNegoDnsSrvrPref
- [ULONG \\*](#) pPppSessCloseTimerDO
- [ULONG \\*](#) pPppSessCloseTimer1x
- [BYTE \\*](#) pAllowLinger
- [USHORT \\*](#) pLcpAckTimeout
- [USHORT \\*](#) plpcpAckTimeout
- [USHORT \\*](#) pAuthTimeout
- [BYTE \\*](#) pLcpCreqRetryCount
- [BYTE \\*](#) plpcpCreqRetryCount

- BYTE \* pAuthRetryCount
- BYTE \* pAuthProtocol
- CHAR \* pUserId
- WORD \* pUserIdSize
- CHAR \* pAuthPassword
- WORD \* pAuthPasswordSize
- BYTE \* pDataRate
- ULONG \* pAppType
- BYTE \* pDataMode
- BYTE \* pAppPriority
- CHAR \* pApnString
- WORD \* pApnStringSize
- BYTE \* pPdnType
- BYTE \* plsPcscfAddressNedded
- ULONG \* pPrimaryV4DnsAddress
- ULONG \* pSecondaryV4DnsAddress
- USHORT \* pPriV6DnsAddress
- USHORT \* pSecV6DnsAddress
- BYTE \* pRATType
- BYTE \* pAPNEnabled3GPP2
- ULONG \* pPDNInactivTimeout3GPP2
- BYTE \* pAPNClass3GPP2

### 8.578.1 Detailed Description

This structure contains the 3GPP2 profile parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>pNegoDnsSrvr-Pref</i>	<ul style="list-style-type: none"> <li>• Negotiate DNS Server Preference             <ul style="list-style-type: none"> <li>– 1 - (TRUE)implies request DNS addresses from the PDSN</li> <li>– 0 - (FALSE)implies do not request DNS addresses from the PDSN</li> <li>– Default value is 1 (TRUE)</li> </ul> </li> </ul>
<i>pPppSessClose-TimerDO</i>	<ul style="list-style-type: none"> <li>• PPP Session Close Timer for DO             <ul style="list-style-type: none"> <li>– Timer value (in seconds) on DO indicating how long the PPP Session should linger before closing down</li> </ul> </li> </ul>

<i>pPppSessClose-Timer1x</i>	<ul style="list-style-type: none"> <li>• PPP Session Close Timer for 1X <ul style="list-style-type: none"> <li>– Timer value (in seconds) on 1X indicating how long the PPP session should linger before closing down</li> </ul> </li> </ul>
<i>pAllowLinger</i>	<ul style="list-style-type: none"> <li>• Allow/disallow lingering of interface <ul style="list-style-type: none"> <li>– 1 -(TRUE) implies allow lingering</li> <li>– 0 -(FALSE) implies do not allow lingering</li> </ul> </li> </ul>
<i>pLcpAckTimeout</i>	<ul style="list-style-type: none"> <li>• LCP ACK Timeout <ul style="list-style-type: none"> <li>– Value of LCP ACK Timeout in milliseconds</li> </ul> </li> </ul>
<i>plpcpAck-Timeout</i>	<ul style="list-style-type: none"> <li>• IPCP ACK Timeout <ul style="list-style-type: none"> <li>– Value of IPCP ACK Timeout in milliseconds</li> </ul> </li> </ul>
<i>pAuthTimeout</i>	<ul style="list-style-type: none"> <li>• AUTH Timeout <ul style="list-style-type: none"> <li>– Value of Authentication Timeout in milliseconds</li> </ul> </li> </ul>
<i>pLcpCreqRetry-Count</i>	<ul style="list-style-type: none"> <li>• LCP Configuration Request Retry Count</li> </ul>
<i>plpcpCreqRetry-Count</i>	<ul style="list-style-type: none"> <li>• IPCP Configuration Request Retry Count</li> </ul>
<i>pAuthRetry-Count</i>	<ul style="list-style-type: none"> <li>• Authentication Retry Count value</li> </ul>
<i>pAuthProtocol</i>	<ul style="list-style-type: none"> <li>• Authentication Protocol <ul style="list-style-type: none"> <li>– 1 - PAP</li> <li>– 2 - CHAP</li> <li>– 3 - PAP or CHAP</li> </ul> </li> </ul>
<i>pUserId</i>	<ul style="list-style-type: none"> <li>• User ID to be used during data network authentication</li> <li>• maximum length allowed is 127 bytes;</li> <li>• QMI_ERR_ARG_TOO_LONG will be returned if the storage on the wireless device is insufficient in size to hold the value.</li> </ul>

<i>pUserIdSize;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pUserId field. Size of this parameter is 2 bytes.</li> </ul>
<i>pAuthPassword</i>	<ul style="list-style-type: none"> <li>• Password to be used during data network authentication;</li> <li>• maximum length allowed is 127 bytes</li> <li>• QMI_ERR_ARG_TOO_LONG will be returned if the storage on the wireless device is insufficient in size to hold the value.</li> </ul>
<i>pAuthPassword-Size;</i>	<ul style="list-style-type: none"> <li>• This parameter is an input parameter and should be initialised to the size of pAuthPassword field. Size of this parameter is 2 bytes.</li> </ul>
<i>pDataRate</i>	<ul style="list-style-type: none"> <li>• Data Rate Requested <ul style="list-style-type: none"> <li>– 0 - Low (Low speed Service Options (SO15) only)</li> <li>– 1 - Medium (SO33 + low R-SCH)</li> <li>– 2 - High (SO33 + high R-SCH)</li> <li>– Default is 2</li> </ul> </li> </ul>
<i>pAppType</i>	<ul style="list-style-type: none"> <li>• Application Type: <ul style="list-style-type: none"> <li>– 0x00000001 - Default Application Type</li> <li>– 0x00000020 - LBS Application Type</li> <li>– 0x00000040 - Tethered Application Type</li> <li>– This parameter is not used while creating/modifying a profile</li> </ul> </li> </ul>
<i>pDataMode</i>	<ul style="list-style-type: none"> <li>• Data Mode to use: <ul style="list-style-type: none"> <li>– 0 - CDMA or HDR (Hybrid 1X/1xEV-DO)</li> <li>– 1 - CDMA Only (1X only)</li> <li>– 2 - HDR Only (1xEV-DO only)</li> <li>– Default is 0</li> </ul> </li> </ul>
<i>pAppPriority</i>	<ul style="list-style-type: none"> <li>• Application Priority <ul style="list-style-type: none"> <li>– Numerical 1 byte value defining the application priority; higher value implies higher priority</li> <li>– This parameter is not used while creating/modifying a profile</li> </ul> </li> </ul>

<i>pApnString</i>	<ul style="list-style-type: none"> <li>String representing the Access Point Name</li> <li>maximum length allowed is 100 bytes</li> <li>QMI_ERR_ARG_TOO_LONG will be returned if the APN name is too long.</li> </ul>
<i>pApnStringSize;</i>	<ul style="list-style-type: none"> <li>This parameter is an input parameter and should be initialised to the size of pApnString field. Size of this parameter is 2 bytes.</li> </ul>
<i>pPdnType</i>	<ul style="list-style-type: none"> <li>Packed Data Network Type Requested: <ul style="list-style-type: none"> <li>0 - IPv4 PDN Type</li> <li>1 - IPv6 PDN Type</li> <li>2 - IPv4 or IPv6 PDN Type</li> <li>3 - Unspecified PDN Type (implying no preference)</li> </ul> </li> </ul>
<i>plsPcsf-AddressNedded</i>	<ul style="list-style-type: none"> <li>This boolean value is used to control if PCSCF address is requested from PDSN <ul style="list-style-type: none"> <li>1 -(TRUE) implies request for PCSCF value from the PDSN</li> <li>0 -(FALSE) implies do not request for PCSCF value from the PDSN</li> </ul> </li> </ul>
<i>pPrimaryV4Dns-Address</i>	<ul style="list-style-type: none"> <li>IPv4 Primary DNS address <ul style="list-style-type: none"> <li>The Primary IPv4 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pSecondaryV4-DnsAddress</i>	<ul style="list-style-type: none"> <li>IPv4 Secondary DNS address <ul style="list-style-type: none"> <li>The Secondary IPv4 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pPriV6Dns-Address</i>	<ul style="list-style-type: none"> <li>Primary IPv6 DNS address <ul style="list-style-type: none"> <li>The Primary IPv6 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pSecV6Dns-Address</i>	<ul style="list-style-type: none"> <li>Secondary IPv6 DNS address <ul style="list-style-type: none"> <li>The Secondary IPv6 DNS address that can be statically assigned to the UE</li> </ul> </li> </ul>
<i>pRATType</i>	<ul style="list-style-type: none"> <li>Optional 1 Byte Flag indicating RAT Type</li> <li>Values: <ul style="list-style-type: none"> <li>1 - HRPD</li> <li>2 - EHRPD</li> <li>3 - HRPD_EHRPD</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>This parameter is currently read only and can be read by using the function <a href="#">QMI_RATType_Get</a> or <a href="#">ProfileSettings()</a>.</li> </ul>



<i>pAPNEnabled3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 1 Byte Flag indicating if the APN is disabled/enabled</li> <li>• If disabled, the profile can not be used for making data calls</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled(default value)</li> </ul> </li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pPDNInactivityTimeout3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 4 Bytes indicating the duration of inactivity timer in seconds</li> <li>• If the PDP context/PDN connection is inactive for this duration i.e. No data Tx/Rx occurs, the PDP context/PDN connection is disconnected</li> <li>• Default value of zero indicates infinite value</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>
<i>pAPNClass3GPP2</i>	<ul style="list-style-type: none"> <li>• Optional 1 Byte numeric identifier representing the APN in profile</li> <li>• Can be set and queried but is not used by the modem</li> <li>• This parameter is currently read only and can be read by using the function <a href="#">SLQSGetProfileSettings()</a>.</li> </ul>

## 8.578.2 Field Documentation

8.578.2.1 **BYTE\*** Profile3GPP2::pAllowLinger

8.578.2.2 **BYTE\*** Profile3GPP2::pAPNClass3GPP2

8.578.2.3 **BYTE\*** Profile3GPP2::pAPNEnabled3GPP2

8.578.2.4 **CHAR\*** Profile3GPP2::pApnString

8.578.2.5 **WORD\*** Profile3GPP2::pApnStringSize

8.578.2.6 **BYTE\*** Profile3GPP2::pAppPriority

8.578.2.7 **ULONG\*** Profile3GPP2::pAppType

8.578.2.8 **CHAR\*** Profile3GPP2::pAuthPassword

8.578.2.9 **WORD\*** Profile3GPP2::pAuthPasswordSize

8.578.2.10 **BYTE\*** Profile3GPP2::pAuthProtocol

8.578.2.11 **BYTE\*** Profile3GPP2::pAuthRetryCount

- 8.578.2.12 **USHORT\*** Profile3GPP2::pAuthTimeout
- 8.578.2.13 **BYTE\*** Profile3GPP2::pDataMode
- 8.578.2.14 **BYTE\*** Profile3GPP2::pDataRate
- 8.578.2.15 **USHORT\*** Profile3GPP2::plpcpAckTimeout
- 8.578.2.16 **BYTE\*** Profile3GPP2::plpcpCreqRetryCount
- 8.578.2.17 **BYTE\*** Profile3GPP2::plsPcscfAddressNedded
- 8.578.2.18 **USHORT\*** Profile3GPP2::pLcpAckTimeout
- 8.578.2.19 **BYTE\*** Profile3GPP2::pLcpCreqRetryCount
- 8.578.2.20 **BYTE\*** Profile3GPP2::pNegoDnsSrvrPref
- 8.578.2.21 **ULONG\*** Profile3GPP2::pPDNInactivTimeout3GPP2
- 8.578.2.22 **BYTE\*** Profile3GPP2::pPdnType
- 8.578.2.23 **ULONG\*** Profile3GPP2::pPppSessCloseTimer1x
- 8.578.2.24 **ULONG\*** Profile3GPP2::pPppSessCloseTimerDO
- 8.578.2.25 **ULONG\*** Profile3GPP2::pPrimaryV4DnsAddress
- 8.578.2.26 **USHORT\*** Profile3GPP2::pPriV6DnsAddress
- 8.578.2.27 **BYTE\*** Profile3GPP2::pRATType
- 8.578.2.28 **ULONG\*** Profile3GPP2::pSecondaryV4DnsAddress
- 8.578.2.29 **USHORT\*** Profile3GPP2::pSecV6DnsAddress
- 8.578.2.30 **CHAR\*** Profile3GPP2::pUserId
- 8.578.2.31 **WORD\*** Profile3GPP2::pUserIdSize

## 8.579 ProfileIdentifier Struct Reference

### Data Fields

- [BYTE profileType](#)
- [BYTE profileIndex](#)

### 8.579.1 Detailed Description

This structure contains the Profile Identifier Information

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>Identifies the type of profile 0x00 = 3GPP</li> </ul>
<i>profileIndex</i>	<ul style="list-style-type: none"> <li>Index of profile whose settings were loaded prior to session parameter negotiation for the current call. If this TLV is not present, data call parameters are based on device default settings for each parameter</li> </ul>

## 8.579.2 Field Documentation

## 8.579.2.1 BYTE ProfileIdentifier::profileIndex

## 8.579.2.2 BYTE ProfileIdentifier::profileType

## 8.580 protocolSubtypeElement Struct Reference

## Data Fields

- [WORD PhysicalLayer](#)
- [WORD ControlMac](#)
- [WORD AccessMac](#)
- [WORD ForwardMac](#)
- [WORD ReverseMac](#)
- [WORD KeyExchange](#)
- [WORD AuthProt](#)
- [WORD EncryptProt](#)
- [WORD SecProt](#)
- [WORD IdleState](#)
- [WORD MultDisc](#)
- [WORD VirtStream](#)

## 8.580.1 Detailed Description

This structure contains Protocol Subtype Elements for Protocol Subtype List

## Parameters

<i>PhysicalLayer</i>	<ul style="list-style-type: none"> <li>Specifies Physical Layer Protocol subtype</li> </ul>
<i>ControlMac</i>	<ul style="list-style-type: none"> <li>Specifies Control Channel MAC Protocol subtype</li> </ul>
<i>AccessMac</i>	<ul style="list-style-type: none"> <li>Specifies Access Channel MAC Protocol subtype</li> </ul>

<i>ForwardMac</i>	<ul style="list-style-type: none"> <li>• Specifies Forward Traffic Channel MAC Protocol subtype</li> </ul>
<i>ReverseMac</i>	<ul style="list-style-type: none"> <li>• Specifies Reverse Traffic Channel MAC Protocol subtype</li> </ul>
<i>KeyExchange</i>	<ul style="list-style-type: none"> <li>• Specifies Key exchange Protocol subtype</li> </ul>
<i>AuthProt</i>	<ul style="list-style-type: none"> <li>• Specifies Authentication Protocol subtype</li> </ul>
<i>EncryptProt</i>	<ul style="list-style-type: none"> <li>• Specifies Encryption Protocol subtype</li> </ul>
<i>SecProt</i>	<ul style="list-style-type: none"> <li>• Specifies Security Protocol subtype</li> </ul>
<i>IdleState</i>	<ul style="list-style-type: none"> <li>• Specifies Idle state Protocol subtype</li> </ul>
<i>MultDisc</i>	<ul style="list-style-type: none"> <li>• Specifies Generic multimode capability discovery Protocol subtype</li> </ul>
<i>VirtStream</i>	<ul style="list-style-type: none"> <li>• Specifies Generic Virtual Stream Protocol subtype</li> </ul>

## 8.580.2 Field Documentation

8.580.2.1 WORD protocolSubtypeElement::AccessMac

8.580.2.2 WORD protocolSubtypeElement::AuthProt

8.580.2.3 WORD protocolSubtypeElement::ControlMac

8.580.2.4 WORD protocolSubtypeElement::EncryptProt

8.580.2.5 WORD protocolSubtypeElement::ForwardMac

8.580.2.6 WORD protocolSubtypeElement::IdleState

8.580.2.7 WORD protocolSubtypeElement::KeyExchange

8.580.2.8 WORD protocolSubtypeElement::MultDisc

8.580.2.9 WORD protocolSubtypeElement::PhysicalLayer

8.580.2.10 WORD protocolSubtypeElement::ReverseMac

8.580.2.11 WORD protocolSubtypeElement::SecProt

8.580.2.12 WORD protocolSubtypeElement::VirtStream

## 8.581 PSDetachReq Struct Reference

### Data Fields

- [BYTE](#) \* [pDetachAction](#)

### 8.581.1 Detailed Description

This structure contains information about the SLQSSwiPSDetach request parameters.

#### Parameters

<i>pDetachAction</i> [1- <i>N</i> ]	<ul style="list-style-type: none"><li>• Values<ul style="list-style-type: none"><li>– 2- Initiates an immediate packet domain detach.</li></ul></li></ul>
-------------------------------------	---

### 8.581.2 Field Documentation

8.581.2.1 [BYTE](#)\* PSDetachReq::pDetachAction

## 8.582 qaQmi3Gpp2TimeZone Struct Reference

### Data Fields

- [BYTE](#) [leapSeconds](#)
- [BYTE](#) [localTimeOffset](#)
- [BYTE](#) [daylightSavings](#)

### 8.582.1 Detailed Description

This structure contains the 3GPP2TimeZone parameters

#### Parameters

<i>leapSeconds</i>	<ul style="list-style-type: none"><li>• leap seconds - Number of leap seconds since the start of CDMA system time.</li></ul>
<i>localTimeOffset</i>	<ul style="list-style-type: none"><li>• Local Time Offset - Offset of system time in units of 30 minutes; the value in this field conveys as 8 bit 2's compliment number.</li></ul>
<i>daylightSavings</i>	<ul style="list-style-type: none"><li>• Day Light Savings Indicator<ul style="list-style-type: none"><li>– 0x00 - OFF (daylight savings not in effect)</li><li>– 0x01 - ON (daylight savings in effect)</li></ul></li></ul>

## 8.582.2 Field Documentation

8.582.2.1 **BYTE** `qaQmi3Gpp2TimeZone::daylightSavings`

8.582.2.2 **BYTE** `qaQmi3Gpp2TimeZone::leapSeconds`

8.582.2.3 **BYTE** `qaQmi3Gpp2TimeZone::localTimeOffset`

## 8.583 `qaQmiInterfaceInfo` Struct Reference

### Data Fields

- [BYTE](#) `qaQmiinstanceid`
- [eQaQMIService](#) `qaQmisvctype`
- [ULONG](#) `v4sessionId`
- [ULONG](#) `v6sessionId`

### 8.583.1 Detailed Description

Structure used to store the service, interface and session information

#### Parameters

<i>qaQmiinstanceid</i>	<ul style="list-style-type: none"> <li>• The interface instance ID <ul style="list-style-type: none"> <li>– 0x00 - PDP instance ID 0</li> <li>– 0x01 - PDP instance ID 1</li> <li>– 0x02 - PDP instance ID 2</li> </ul> </li> </ul>
<i>qaQmisvctype</i>	<ul style="list-style-type: none"> <li>• The service type information. See <a href="#">eQaQMIService</a> for more information</li> </ul>
<i>v4sessionId</i>	<ul style="list-style-type: none"> <li>• IPv4 QMI client session handle</li> </ul>
<i>v6sessionId</i>	<ul style="list-style-type: none"> <li>• IPv6 QMI client session handle</li> </ul>

## 8.583.2 Field Documentation

8.583.2.1 **BYTE** `qaQmiInterfaceInfo::qaQmiinstanceid`

8.583.2.2 **eQaQMIService** `qaQmiInterfaceInfo::qaQmisvctype`

8.583.2.3 **ULONG** `qaQmiInterfaceInfo::v4sessionId`

8.583.2.4 **ULONG** `qaQmiInterfaceInfo::v6sessionId`

## 8.584 `qaQmiServingSystemParam` Struct Reference

## Data Fields

- [servSystem](#) [ServingSystem](#)
- [BYTE](#) [roamIndicatorVal](#)
- [dataSrvCapabilities](#) [DataSrvCapabilities](#)
- [currentPLMN](#) [CurrentPLMN](#)
- [WORD](#) [SystemID](#)
- [WORD](#) [NetworkID](#)
- [WORD](#) [BasestationID](#)
- [ULONG](#) [BasestationLatitude](#)
- [ULONG](#) [BasestationLongitude](#)
- [roamIndList](#) [RoamingIndicatorList](#)
- [BYTE](#) [defaultRoamInd](#)
- [qaQmi3Gpp2TimeZone](#) [Gpp2TimeZone](#)
- [BYTE](#) [CDMA\\_P\\_Rev](#)
- [BYTE](#) [GppTimeZone](#)
- [BYTE](#) [GppNetworkDSTAdjustment](#)
- [WORD](#) [Lac](#)
- [ULONG](#) [CellID](#)
- [BYTE](#) [concSvcInfo](#)
- [BYTE](#) [PRLInd](#)
- [BYTE](#) [DTMInd](#)
- [detailSvcInfo](#) [DetailedSvcInfo](#)
- [CDMASysInfoExt](#) [CDMASystemInfoExt](#)
- [BYTE](#) [hdrPersonality](#)
- [WORD](#) [trackAreaCode](#)
- [callBarStatus](#) [CallBarStatus](#)

## 8.584.1 Detailed Description

This structure contains the Serving System parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>ServingSystem</i>	<ul style="list-style-type: none"> <li>• Serving System</li> <li>• See <a href="#">servSystem</a> for more information</li> </ul>
<i>roamIndicatorVal</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating Roaming Indicator value</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Roaming</li> <li>– 0x01 - Home</li> <li>– 0x02 - Flashing</li> <li>– 0x03 and above - Operator defined values</li> </ul> </li> </ul>

<i>DataSrv-Capabilities</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Data services capability</li> <li>See <a href="#">dataSrvCapabilities</a> for more information</li> </ul>
<i>CurrentPLMN</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Current PLMN</li> <li>See <a href="#">currentPLMN</a> for more information</li> </ul>
<i>SystemID</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating System ID</li> </ul>
<i>NetworkID</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Network ID</li> </ul>
<i>BaseStationID</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Base Station Identification Number</li> </ul>
<i>BaseStation-Latitude</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Base station latitude in units of 0.25 sec, expressed as a two's complement signed number with positive numbers signifying North latitude</li> </ul>
<i>Basestation-Longitude</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Base station longitude in units of 0.25 sec, expressed as a Two's complement signed number with positive numbers signifying East longitude</li> </ul>
<i>Roaming-IndicatorList</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Roaming Indicator List</li> <li>See <a href="#">roamIndList</a> for more information</li> </ul>
<i>defaultRoamInd</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Default Roaming Indicator</li> <li>Values: <ul style="list-style-type: none"> <li>– 0x00 - Roaming</li> <li>– 0x01 - Home</li> </ul> </li> </ul>
<i>Gpp2TimeZone</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating 3GPP2 Time Zone</li> <li>See <a href="#">qaQmi3Gpp2TimeZone</a> for more information</li> </ul>
<i>CDMA_P_Rev</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating CDMA P_Rev in use</li> </ul>
<i>GppTimeZone</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Offset from Universal time, i.e., difference between local time and Universal time, in increments of 15 min. (signed value).</li> </ul>



<i>GppNetworkDS-TAdjustment</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating 3GPP network daylight saving adjustment</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - No adjustment for Daylight Saving Time</li> <li>0x01 - 1 hr adjustment for Daylight Saving Time</li> <li>0x02 - 2 hr adjustment for Daylight Saving Time</li> </ul> </li> </ul>
<i>Lac</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating 3GPP Location Area Code</li> </ul>
<i>CellID</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating 3GPP Cell ID</li> </ul>
<i>concSvcInfo</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating 3GPP2 concurrent service Info</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Concurrent service not available</li> <li>0x01 - Concurrent service available</li> </ul> </li> </ul>
<i>PRLInd</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating 3GPP2 PRL Indicator</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - System not in PRL</li> <li>0x01 - System is in PRL</li> </ul> </li> </ul>
<i>DTMInd</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Dual Transfer Mode Indication(GSM Only)</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - DTM not supported</li> <li>0x01 - DTM supported</li> </ul> </li> </ul>
<i>DetailedSvcInfo</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Detailed service information</li> <li>See <a href="#">detailSvcInfo</a> for more information</li> </ul>
<i>CDMASystem-InfoExt</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating CDMA System Info Ext</li> <li>See <a href="#">CDMASysInfoExt</a> for more information</li> </ul>

<i>hdrPersonality</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating HDR Personality Information</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Unknown</li> <li>– 0x01 - HRPD</li> <li>– 0x02 - eHRPD</li> </ul> </li> </ul>
<i>trackAreaCode</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating Tracking area code information for LTE</li> </ul>
<i>CallBarStatus</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating Call Barring Status</li> <li>• See <a href="#">callBarStatus</a> for more information</li> </ul>

## 8.584.2 Field Documentation

8.584.2.1 **WORD** qaQmiServingSystemParam::BasestationID

8.584.2.2 **ULONG** qaQmiServingSystemParam::BasestationLatitude

8.584.2.3 **ULONG** qaQmiServingSystemParam::BasestationLongitude

8.584.2.4 **callBarStatus** qaQmiServingSystemParam::CallBarStatus

8.584.2.5 **BYTE** qaQmiServingSystemParam::CDMA\_P\_Rev

8.584.2.6 **CDMASysInfoExt** qaQmiServingSystemParam::CDMASystemInfoExt

8.584.2.7 **ULONG** qaQmiServingSystemParam::CellID

8.584.2.8 **BYTE** qaQmiServingSystemParam::concSvcInfo

8.584.2.9 **currentPLMN** qaQmiServingSystemParam::CurrentPLMN

8.584.2.10 **dataSrvCapabilities** qaQmiServingSystemParam::DataSrvCapabilities

8.584.2.11 **BYTE** qaQmiServingSystemParam::defaultRoamInd

8.584.2.12 **detailSvcInfo** qaQmiServingSystemParam::DetailedSvcInfo

8.584.2.13 **BYTE** qaQmiServingSystemParam::DTMInd

8.584.2.14 **qaQmi3Gpp2TimeZone** qaQmiServingSystemParam::Gpp2TimeZone

8.584.2.15 **BYTE** qaQmiServingSystemParam::GppNetworkDSTAdjustment

8.584.2.16 **BYTE** qaQmiServingSystemParam::GppTimeZone

8.584.2.17 **BYTE** qaQmiServingSystemParam::hdrPersonality

- 8.584.2.18 WORD qaQmiServingSystemParam::Lac
- 8.584.2.19 WORD qaQmiServingSystemParam::NetworkID
- 8.584.2.20 BYTE qaQmiServingSystemParam::PRLInd
- 8.584.2.21 BYTE qaQmiServingSystemParam::roamIndicatorVal
- 8.584.2.22 roamIndList qaQmiServingSystemParam::RoamingIndicatorList
- 8.584.2.23 servSystem qaQmiServingSystemParam::ServingSystem
- 8.584.2.24 WORD qaQmiServingSystemParam::SystemID
- 8.584.2.25 WORD qaQmiServingSystemParam::trackAreaCode

## 8.585 QmiCbkCatEventStatusReportInd Struct Reference

### Data Fields

- [BYTE event\\_Index](#)
- struct [CatCommonEventTlv CCETlv](#) [11]

### 8.585.1 Field Documentation

- 8.585.1.1 struct [CatCommonEventTlv](#) QmiCbkCatEventStatusReportInd::CCETlv[11]
- 8.585.1.2 [BYTE](#) QmiCbkCatEventStatusReportInd::event\_Index

## 8.586 QmiCbkLocCradleMountInd Struct Reference

### Data Fields

- [ULONG](#) [cradleMountConfigStatus](#)

### 8.586.1 Detailed Description

This structure contains LOC Cradle Mount Config Status

## Parameters

<i>cradleMount-ConfigStatus</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Request was completed successfully</li> <li>– 1 - Request failed because of a general failure.</li> <li>– 2 - Request failed because it is not supported.</li> <li>– 3 - Request failed because it contained invalid parameters</li> <li>– 4 - Request failed because the engine is busy</li> <li>– 5 - Request failed because the phone is offline</li> <li>– 6 - Request failed because it timed out</li> <li>– 7 - Request failed because an undefined configuration was requested</li> <li>– 8 - engine could not allocate sufficient memory</li> <li>– 9 - Request failed because the maximum number of Geofences are already programmed</li> <li>– 10 -Location service failed because of an XTRA version-based file format check failure</li> </ul> </li> </ul>
---------------------------------	---

## 8.586.2 Field Documentation

8.586.2.1 ULONG QmiCbkLocCradleMountInd::cradleMountConfigStatus

## 8.587 QmiCbkLocEngineStateInd Struct Reference

## Data Fields

- [ULONG engineState](#)

## 8.587.1 Detailed Description

This structure contains LOC Engine State field.

## Parameters

<i>engineState</i>	<ul style="list-style-type: none"> <li>• Location engine state.</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 1 - Location engine is on</li> <li>– 2 - Location engine is off</li> </ul> </li> </ul>
--------------------	---

## 8.587.2 Field Documentation

8.587.2.1 ULONG QmiCbkLocEngineStateInd::engineState

## 8.588 QmiCbkJocEventTimeSyncInd Struct Reference

### Data Fields

- [ULONG timeSyncRefCounter](#)

### 8.588.1 Detailed Description

This structure contains LOC Event Time Sync Reference Counter

#### Parameters

<i>timeSyncRef-Counter</i>	<ul style="list-style-type: none"><li>• Sent by the location engine when it needs to synchronize location engine and control point (sensor processor) times.</li></ul>
----------------------------	--

### 8.588.2 Field Documentation

8.588.2.1 [ULONG QmiCbkJocEventTimeSyncInd::timeSyncRefCounter](#)

## 8.589 QmiCbkJocInjectPositionInd Struct Reference

### Data Fields

- [ULONG status](#)

### 8.589.1 Detailed Description

Contain the parameters passed for SetLocInjectPositionCallback by the device.

## Parameters

<i>status</i>	<ul style="list-style-type: none"> <li>• UTC Position Injection Status</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– eQMI_LOC_SUCCESS (0) - Request was completed successfully</li> <li>– eQMI_LOC_GENERAL_FAILURE (1) - Request failed because of a general failure</li> <li>– eQMI_LOC_UNSUPPORTED (2) - Request failed because it is not supported</li> <li>– eQMI_LOC_INVALID_PARAMETER (3) - Request failed because it contained invalid parameters</li> <li>– eQMI_LOC_ENGINE_BUSY (4) - Request failed because the engine is busy</li> <li>– eQMI_LOC_PHONE_OFFLINE (5) - Request failed because the phone is offline</li> <li>– eQMI_LOC_TIMEOUT (6) - Request failed because it timed out</li> <li>– eQMI_LOC_CONFIG_NOT_SUPPORTED (7) - Request failed because an undefined configuration was requested</li> <li>– eQMI_LOC_INSUFFICIENT_MEMORY (8) - Request failed because the engine could not allocate sufficient memory for the request</li> <li>– eQMI_LOC_MAX_GEOFENCE_PROGRAMMED (9) - Request failed because the maximum number of Geofences are already programmed</li> <li>– eQMI_LOC_XTRA_VERSION_CHECK_FAILURE (10) - Location service failed because of an XTRA version-based file format check failure</li> </ul> </li> </ul>
---------------	--

## Note

None

## 8.589.2 Field Documentation

8.589.2.1 ULONG QmiCbkLocInjectPositionInd::status

## 8.590 QmiCbkLocInjectSensorDataInd Struct Reference

## Data Fields

- [ULONG injectSensorDataStatus](#)
- [ULONG \\* pOpaqueIdentifier](#)
- [BYTE \\* pAccelSamplesAccepted](#)
- [BYTE \\* pGyroSamplesAccepted](#)
- [BYTE \\* pAccelTempSamplesAccepted](#)
- [BYTE \\* pGyroTempSamplesAccepted](#)

## 8.590.1 Detailed Description

This structure contains LOC Inject Sensor Data

## Parameters

<i>injectSensor-DataStatus</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Request was completed successfully</li> <li>– 1 - Request failed because of a general failure.</li> <li>– 2 - Request failed because it is not supported.</li> <li>– 3 - Request failed because it contained invalid parameters</li> <li>– 4 - Request failed because the engine is busy</li> <li>– 5 - Request failed because the phone is offline</li> <li>– 6 - Request failed because it timed out</li> <li>– 7 - Request failed because an undefined configuration was requested</li> <li>– 8 - engine could not allocate sufficient memory</li> <li>– 9 - Request failed because the maximum number of Geofences are already programmed</li> <li>– 10 -Location service failed because of an XTRA version-based file format check failure</li> </ul> </li> </ul>
<i>pOpaque-Identifier</i>	<ul style="list-style-type: none"> <li>• Sent in by the client echoed so the client can relate the indication to the request.</li> </ul>
<i>pAccelSamples-Accepted</i>	<ul style="list-style-type: none"> <li>• Lets the client know how many 3-axis accelerometer samples were accepted.</li> <li>• This field is present only if the accelerometer samples were sent in the request.</li> </ul>
<i>pGyroSamples-Accepted</i>	<ul style="list-style-type: none"> <li>• Lets the client know how many 3-axis gyroscope samples were accepted.</li> <li>• This field is present only if the gyroscope samples were sent in the request.</li> </ul>
<i>pAccelTemp-Samples-Accepted</i>	<ul style="list-style-type: none"> <li>• Lets the client know how many accelerometer temperature samples were accepted.</li> <li>• This field is present only if the accelerometer temperature samples were sent in the request.</li> </ul>
<i>pGyroTemp-Samples-Accepted</i>	<ul style="list-style-type: none"> <li>• Lets the client know how many gyroscope temperature samples were accepted.</li> <li>• This field is present only if the gyroscope temperature samples were sent in the request.</li> </ul>

## 8.590.2 Field Documentation

8.590.2.1 **ULONG** QmiCbkLocInjectSensorDataInd::injectSensorDataStatus8.590.2.2 **BYTE\*** QmiCbkLocInjectSensorDataInd::pAccelSamplesAccepted8.590.2.3 **BYTE\*** QmiCbkLocInjectSensorDataInd::pAccelTempSamplesAccepted

8.590.2.4 **BYTE\*** QmiCbkLocInjectSensorDataInd::pGyroSamplesAccepted

8.590.2.5 **BYTE\*** QmiCbkLocInjectSensorDataInd::pGyroTempSamplesAccepted

8.590.2.6 **ULONG\*** QmiCbkLocInjectSensorDataInd::pOpaquelIdentifier

## 8.591 QmiCbkLocInjectTimeInd Struct Reference

### Data Fields

- [ULONG injectTimeSyncStatus](#)

### 8.591.1 Detailed Description

This structure contains LOC Inject Time Sync Data Status

#### Parameters

<i>injectTimeSync-Status</i>	<ul style="list-style-type: none"> <li>• Values           <ul style="list-style-type: none"> <li>– 0 - Request was completed successfully</li> <li>– 1 - Request failed because of a general failure.</li> <li>– 2 - Request failed because it is not supported.</li> <li>– 3 - Request failed because it contained invalid parameters</li> <li>– 4 - Request failed because the engine is busy</li> <li>– 5 - Request failed because the phone is offline</li> <li>– 6 - Request failed because it timed out</li> <li>– 7 - Request failed because an undefined configuration was requested</li> <li>– 8 - engine could not allocate sufficient memory</li> <li>– 9 - Request failed because the maximum number of Geofences are already programmed</li> <li>– 10 -Location service failed because of an XTRA version-based file format check failure</li> </ul> </li> </ul>
------------------------------	---

### 8.591.2 Field Documentation

8.591.2.1 **ULONG** QmiCbkLocInjectTimeInd::injectTimeSyncStatus

## 8.592 QmiCbkLocInjectUTCTimeInd Struct Reference

### Data Fields

- [ULONG status](#)

### 8.592.1 Detailed Description

Contain the parameters passed for SetLocInjectUTCTimeCallback by the device.



## Parameters

<i>status</i>	<ul style="list-style-type: none"> <li>• Status of the UTC Time Injection request</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– eQMI_LOC_SUCCESS (0) - Request was completed successfully</li> <li>– eQMI_LOC_GENERAL_FAILURE (1) - Request failed because of a general failure</li> <li>– eQMI_LOC_UNSUPPORTED (2) - Request failed because it is not supported</li> <li>– eQMI_LOC_INVALID_PARAMETER (3) - Request failed because it contained invalid parameters</li> <li>– eQMI_LOC_ENGINE_BUSY (4) - Request failed because the engine is busy</li> <li>– eQMI_LOC_PHONE_OFFLINE (5) - Request failed because the phone is offline</li> <li>– eQMI_LOC_TIMEOUT (6) - Request failed because it timed out</li> </ul> </li> </ul>
---------------	--

## Note

None

## 8.592.2 Field Documentation

## 8.592.2.1 ULONG QmiCbkLocInjectUTCTimeInd::status

## 8.593 QmiCbkLocPositionReportInd Struct Reference

## Data Fields

- [ULONG](#) `sessionStatus`
- [BYTE](#) `sessionId`
- [ULONGLONG](#) \* `pLatitude`
- [ULONGLONG](#) \* `pLongitude`
- [ULONG](#) \* `pHorUncCircular`
- [ULONG](#) \* `pHorUncEllipseSemiMinor`
- [ULONG](#) \* `pHorUncEllipseSemiMajor`
- [ULONG](#) \* `pHorUncEllipseOrientAzimuth`
- [BYTE](#) \* `pHorConfidence`
- [ULONG](#) \* `pHorReliability`
- [ULONG](#) \* `pSpeedHorizontal`
- [ULONG](#) \* `pSpeedUnc`
- [ULONG](#) \* `pAltitudeWrtEllipsoid`
- [ULONG](#) \* `pAltitudeWrtMeanSeaLevel`
- [ULONG](#) \* `pVertUnc`
- [BYTE](#) \* `pVertConfidence`
- [ULONG](#) \* `pVertReliability`
- [ULONG](#) \* `pSpeedVertical`
- [ULONG](#) \* `pHeading`
- [ULONG](#) \* `pHeadingUnc`
- [ULONG](#) \* `pMagneticDeviation`
- [ULONG](#) \* `pTechnologyMask`
- [precisionDilution](#) \* `pPrecisionDilution`

- ULONGLONG \* pTimestampUtc
- BYTE \* pLeapSeconds
- gpsTime \* pGpsTime
- ULONG \* pTimeUnc
- ULONG \* pTimeSrc
- sensorDataUsage \* pSensorDataUsage
- ULONG \* pFixId
- svUsedforFix \* pSvUsedforFix
- BYTE \* pAltitudeAssumed

### 8.593.1 Detailed Description

This structure contains Event Position Report

#### Parameters

<i>sessionStatus</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Session was successful</li> <li>– 1 - Session is still in progress; further position reports will be generated until either the fix criteria specified by the client are met or the client response timeout occurs.</li> <li>– 2 - Session failed..</li> <li>– 3 - Fix request failed because the session timed out.</li> <li>– 4 - Fix request failed because the session was ended by the user.</li> <li>– 5 - Fix request failed due to bad parameters in the request.</li> <li>– 6 - Fix request failed because the phone is offline.</li> <li>– 7 - Fix request failed because the engine is locked</li> </ul> </li> </ul>
<i>sessionId</i>	<ul style="list-style-type: none"> <li>• ID of the session that was specified in the Start request</li> <li>• Range - 0 to 255</li> </ul>
<i>pLatitude</i>	<ul style="list-style-type: none"> <li>• Latitude (specified in WGS84 datum)</li> <li>• Type - Floating point</li> <li>• Units - Degrees</li> <li>• Range - -90.0 to 90.0</li> <li>• Positive values indicate northern latitude</li> <li>• Negative values indicate southern latitude</li> </ul>

<i>pLongitude</i>	<ul style="list-style-type: none"> <li>• Longitude (specified in WGS84 datum)</li> <li>• Type - Floating point</li> <li>• Units - Degrees</li> <li>• Range - -180.0 to 180.0</li> <li>• Positive values indicate eastern latitude</li> <li>• Negative values indicate western latitude</li> </ul>
<i>pHorUncCircular</i>	<ul style="list-style-type: none"> <li>• Horizontal position uncertainty.</li> <li>• Units - Meters</li> </ul>
<i>pHorUncEllipse-SemiMinor</i>	<ul style="list-style-type: none"> <li>• Semi-minor axis of horizontal elliptical uncertainty.</li> <li>• Units - Meters</li> </ul>
<i>pHorUncEllipse-SemiMajor</i>	<ul style="list-style-type: none"> <li>• Semi-major axis of horizontal elliptical uncertainty.</li> <li>• Units: Meters</li> </ul>
<i>pHorUncEllipse-OrientAzimuth</i>	<ul style="list-style-type: none"> <li>• Elliptical horizontal uncertainty azimuth of orientation.</li> <li>• Units - Decimal degrees</li> <li>• Range - 0 to 180</li> </ul>
<i>pHorConfidence</i>	<ul style="list-style-type: none"> <li>• Horizontal uncertainty confidence.</li> <li>• If both elliptical and horizontal uncertainties are specified in this message, the confidence corresponds to the elliptical uncertainty.</li> <li>• Units - Percentage</li> <li>• Range 0-99</li> </ul>
<i>pHorReliability</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Location reliability is not set.</li> <li>– 1 - Location reliability is very low; use it at your own risk</li> <li>– 2 - Location reliability is low; little or no cross-checking is possible.</li> <li>– 3 - Location reliability is medium; limited cross-check passed</li> <li>– 4 - Location reliability is high; strong cross-check passed</li> </ul> </li> </ul>

<i>pSpeed-Horizontal</i>	<ul style="list-style-type: none"> <li>• Horizontal speed.</li> <li>• Units - Meters/second</li> </ul>
<i>pSpeedUnc</i>	<ul style="list-style-type: none"> <li>• 3-D Speed uncertainty.</li> <li>• Units - Meters/second.</li> </ul>
<i>pAltitudeWrt-Ellipsoid</i>	<ul style="list-style-type: none"> <li>• Altitude With Respect to WGS84 Ellipsoid.</li> <li>• Units - Meters</li> <li>• Range -500 to 15883</li> </ul>
<i>pAltitudeWrt-MeanSeaLevel</i>	<ul style="list-style-type: none"> <li>• Altitude With Respect to Sea Level.</li> <li>• Units - Meters</li> </ul>
<i>pVertUnc</i>	<ul style="list-style-type: none"> <li>• Vertical uncertainty.</li> <li>• Units - Meters</li> </ul>
<i>pVertConfidence</i>	<ul style="list-style-type: none"> <li>• Vertical uncertainty confidence.</li> <li>• Units - Percentage</li> <li>• Range 0 to 99</li> </ul>
<i>pVertReliability</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Location reliability is not set.</li> <li>– 1 - Location reliability is very low; use it at your own risk.</li> <li>– 2 - Location reliability is low; little or no cross-checking is possible</li> <li>– 3 - Location reliability is medium; limited cross-check passed</li> <li>– 4 - Location reliability is high; strong cross-check passed</li> </ul> </li> </ul>
<i>pSpeedVertical</i>	<ul style="list-style-type: none"> <li>• Vertical speed.</li> <li>• Units - Meters/second</li> </ul>
<i>pHeading</i>	<ul style="list-style-type: none"> <li>• Heading.</li> <li>• Units - Degree</li> <li>• Range 0 to 359.999</li> </ul>

<i>pHeadingUnc</i>	<ul style="list-style-type: none"> <li>• Heading uncertainty.</li> <li>• Units - Degree</li> <li>• Range 0 to 359.999</li> </ul>
<i>pMagnetic-Deviation</i>	<ul style="list-style-type: none"> <li>• Difference between the bearing to true north and the bearing shown on a magnetic compass. The deviation is positive when the magnetic north is east of true north.</li> </ul>
<i>pTechnology-Mask</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0x00000001 - Satellites were used to generate the fix</li> <li>– 0x00000002 - Cell towers were used to generate the fix</li> <li>– 0x00000004 - Wi-Fi access points were used to generate the fix</li> <li>– 0x00000008 - Sensors were used to generate the fix</li> <li>– 0x00000010 - Reference Location was used to generate the fix</li> <li>– 0x00000020 - Coarse position injected into the location engine was used to generate the fix</li> <li>– 0x00000040 - AFLT was used to generate the fix</li> <li>– 0x00000080 - GNSS and network-provided measurements were used to generate the fix</li> </ul> </li> </ul>
<i>-pPrecision-Dilution</i>	<ul style="list-style-type: none"> <li>• See <a href="#">precisionDilution</a> for more information</li> </ul>
<i>pTimestampUtc</i>	<ul style="list-style-type: none"> <li>• UTC timestamp</li> <li>• Units - Milliseconds since Jan. 1, 1970</li> </ul>
<i>pLeapSeconds</i>	<ul style="list-style-type: none"> <li>• Leap second information. If leapSeconds is not available, timestampUtc is calculated based on a hard-coded value for leap seconds.</li> <li>• Units - Seconds</li> </ul>
<i>-pGpsTime</i>	<ul style="list-style-type: none"> <li>• See <a href="#">gpsTime</a> for more information</li> </ul>
<i>pTimeUnc</i>	<ul style="list-style-type: none"> <li>• Time uncertainty.</li> <li>• Units - Milliseconds</li> </ul>
<i>pTimeSrc</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Invalid time.</li> <li>– 1 - Time is set by the 1X system.</li> <li>– 2 - Time is set by WCDMA/GSM time tagging.</li> <li>– 3 - Time is set by an external injection.</li> <li>– 4 - Time is set after decoding over-the-air GPS navigation data from one GPS satellite.</li> <li>– 5 - Time is set after decoding over-the-air GPS navigation data from multiple satellites.</li> </ul> </li> </ul>

<i>-pSensorData-Usage</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sensorDataUsage</a> for more information</li> </ul>
<i>pFixId</i>	<ul style="list-style-type: none"> <li>• Fix count for the session. Starts with 0 and increments by one for each successive position report for a particular session.</li> </ul>
<i>-pSvUsedforFix</i>	<ul style="list-style-type: none"> <li>• See <a href="#">svUsedforFix</a> for more information</li> </ul>
<i>pAltitude-Assumed</i>	<ul style="list-style-type: none"> <li>• Indicates whether altitude is assumed or calculated.</li> </ul>

- Value
  - 0x00 - Altitude is calculated
  - 0x01 - Altitude is assumed

## 8.593.2 Field Documentation

- 8.593.2.1 **BYTE\*** QmiCbkLocPositionReportInd::pAltitudeAssumed
- 8.593.2.2 **ULONG\*** QmiCbkLocPositionReportInd::pAltitudeWrtEllipsoid
- 8.593.2.3 **ULONG\*** QmiCbkLocPositionReportInd::pAltitudeWrtMeanSeaLevel
- 8.593.2.4 **ULONG\*** QmiCbkLocPositionReportInd::pFixId
- 8.593.2.5 **gpsTime\*** QmiCbkLocPositionReportInd::pGpsTime
- 8.593.2.6 **ULONG\*** QmiCbkLocPositionReportInd::pHeading
- 8.593.2.7 **ULONG\*** QmiCbkLocPositionReportInd::pHeadingUnc
- 8.593.2.8 **BYTE\*** QmiCbkLocPositionReportInd::pHorConfidence
- 8.593.2.9 **ULONG\*** QmiCbkLocPositionReportInd::pHorReliability
- 8.593.2.10 **ULONG\*** QmiCbkLocPositionReportInd::pHorUncCircular
- 8.593.2.11 **ULONG\*** QmiCbkLocPositionReportInd::pHorUncEllipseOrientAzimuth
- 8.593.2.12 **ULONG\*** QmiCbkLocPositionReportInd::pHorUncEllipseSemiMajor
- 8.593.2.13 **ULONG\*** QmiCbkLocPositionReportInd::pHorUncEllipseSemiMinor
- 8.593.2.14 **ULONGLONG\*** QmiCbkLocPositionReportInd::pLatitude
- 8.593.2.15 **BYTE\*** QmiCbkLocPositionReportInd::pLeapSeconds
- 8.593.2.16 **ULONGLONG\*** QmiCbkLocPositionReportInd::pLongitude
- 8.593.2.17 **ULONG\*** QmiCbkLocPositionReportInd::pMagneticDeviation

- 8.593.2.18 **precisionDilution\*** QmiCbkLocPositionReportInd::pPrecisionDilution
- 8.593.2.19 **sensorDataUsage\*** QmiCbkLocPositionReportInd::pSensorDataUsage
- 8.593.2.20 **ULONG\*** QmiCbkLocPositionReportInd::pSpeedHorizontal
- 8.593.2.21 **ULONG\*** QmiCbkLocPositionReportInd::pSpeedUnc
- 8.593.2.22 **ULONG\*** QmiCbkLocPositionReportInd::pSpeedVertical
- 8.593.2.23 **svUsedforFix\*** QmiCbkLocPositionReportInd::pSvUsedforFix
- 8.593.2.24 **ULONG\*** QmiCbkLocPositionReportInd::pTechnologyMask
- 8.593.2.25 **ULONG\*** QmiCbkLocPositionReportInd::pTimeSrc
- 8.593.2.26 **ULONGLONG\*** QmiCbkLocPositionReportInd::pTimestampUtc
- 8.593.2.27 **ULONG\*** QmiCbkLocPositionReportInd::pTimeUnc
- 8.593.2.28 **BYTE\*** QmiCbkLocPositionReportInd::pVertConfidence
- 8.593.2.29 **ULONG\*** QmiCbkLocPositionReportInd::pVertReliability
- 8.593.2.30 **ULONG\*** QmiCbkLocPositionReportInd::pVertUnc
- 8.593.2.31 **BYTE** QmiCbkLocPositionReportInd::sessionId
- 8.593.2.32 **ULONG** QmiCbkLocPositionReportInd::sessionStatus

## 8.594 QmiCbkLocSensorStreamingInd Struct Reference

### Data Fields

- [accelAcceptReady](#) \* [pAccelAcceptReady](#)
- [gyroAcceptReady](#) \* [pGyroAcceptReady](#)
- [accelTempAcceptReady](#) \* [pAccelTempAcceptReady](#)
- [gyroTempAcceptReady](#) \* [pGyroTempAcceptReady](#)

### 8.594.1 Detailed Description

This structure contains LOC Event Sensor Streaming Ready Status

#### Parameters

<i>-pAccelAcceptReady</i>	<ul style="list-style-type: none"> <li>• See <a href="#">accelAcceptReady</a> for more information</li> </ul>
<i>-pGyroAcceptReady</i>	<ul style="list-style-type: none"> <li>• See <a href="#">gyroAcceptReady</a> for more information</li> </ul>

<i>-pAccelTempAcceptReady</i>	<ul style="list-style-type: none"> <li>• See <a href="#">accelTempAcceptReady</a> for more information</li> </ul>
<i>-pGyroTempAcceptReady</i>	<ul style="list-style-type: none"> <li>• See <a href="#">gyroTempAcceptReady</a> for more information</li> </ul>

## 8.594.2 Field Documentation

8.594.2.1 `accelAcceptReady*` `QmiCbkLocSensorStreamingInd::pAccelAcceptReady`

8.594.2.2 `accelTempAcceptReady*` `QmiCbkLocSensorStreamingInd::pAccelTempAcceptReady`

8.594.2.3 `gyroAcceptReady*` `QmiCbkLocSensorStreamingInd::pGyroAcceptReady`

8.594.2.4 `gyroTempAcceptReady*` `QmiCbkLocSensorStreamingInd::pGyroTempAcceptReady`

## 8.595 QmiCbkLocSetExtPowerConfigInd Struct Reference

### Data Fields

- [ULONG status](#)

### 8.595.1 Detailed Description

This structure contains LOC Set External Power Config Status

#### Parameters

<i>status</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Request was completed successfully</li> <li>– 1 - Request failed because of a general failure.</li> <li>– 2 - Request failed because it is not supported.</li> <li>– 3 - Request failed because it contained invalid parameters</li> <li>– 4 - Request failed because the engine is busy</li> <li>– 5 - Request failed because the phone is offline</li> <li>– 6 - Request failed because it timed out</li> <li>– 7 - Request failed because an undefined configuration was requested</li> <li>– 8 - engine could not allocate sufficient memory</li> <li>– 9 - Request failed because the maximum number of Geofences are already programmed</li> <li>– 10 -Location service failed because of an XTRA version-based file format check failure</li> </ul> </li> </ul>
---------------	---

### 8.595.2 Field Documentation



8.595.2.1 ULONG QmiCbkLocSetExtPowerConfigInd::status

## 8.596 QmiCbkNasLTECphyCalInfo Struct Reference

### Data Fields

- [PhyCaAggScellIndType](#) sPhyCaAggScellIndType
- [PhyCaAggScellDIBw](#) sPhyCaAggScellDIBw
- [PhyCaAggScellInfo](#) sPhyCaAggScellInfo
- [PhyCaAggPcellInfo](#) sPhyCaAggPcellInfo
- [PhyCaAggScellIndex](#) sPhyCaAggScellIndex

### 8.596.1 Detailed Description

Structure for storing the LTEC PHY CA indication parameters.

#### Parameters

<i>pPhyCaAgg- ScellIndType</i>	<ul style="list-style-type: none"> <li>• See <a href="#">PhyCaAggScellIndType</a> for more information.</li> </ul>
<i>sPhyCaAgg- ScellDIBw</i>	<ul style="list-style-type: none"> <li>• See <a href="#">PhyCaAggScellDIBw</a> for more information.</li> </ul>
<i>sPhyCaAgg- ScellInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">PhyCaAggScellInfo</a> for more information.</li> </ul>
<i>sPhyCaAgg- PcellInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">PhyCaAggPcellInfo</a> for more information.</li> </ul>
<i>sPhyCaAgg- ScellIndex</i>	<ul style="list-style-type: none"> <li>• See <a href="#">PhyCaAggScellIndex</a> for more information.</li> </ul>

### 8.596.2 Field Documentation

8.596.2.1 [PhyCaAggPcellInfo](#) QmiCbkNasLTECphyCalInfo::sPhyCaAggPcellInfo

8.596.2.2 [PhyCaAggScellDIBw](#) QmiCbkNasLTECphyCalInfo::sPhyCaAggScellDIBw

8.596.2.3 [PhyCaAggScellIndex](#) QmiCbkNasLTECphyCalInfo::sPhyCaAggScellIndex

8.596.2.4 [PhyCaAggScellIndType](#) QmiCbkNasLTECphyCalInfo::sPhyCaAggScellIndType

8.596.2.5 [PhyCaAggScellInfo](#) QmiCbkNasLTECphyCalInfo::sPhyCaAggScellInfo

## 8.597 QmiCbkSwiOmaDmEventStatusReportInd Struct Reference

### Data Fields

- struct [sessionInfoTlv](#) SITlv

### 8.597.1 Field Documentation

8.597.1.1 struct `sessionInfoTlv` `QmiCbkSwiOmaDmEventStatusReportInd::SITlv`

## 8.598 QmiCbkSwiOmaDmEventStatusReportIndExt Struct Reference

### Data Fields

- struct [sessionInfoTlvExt](#) `SITlv`

### 8.598.1 Field Documentation

8.598.1.1 struct `sessionInfoTlvExt` `QmiCbkSwiOmaDmEventStatusReportIndExt::SITlv`

## 8.599 QmiCbkTmdMitiLvlRptInd Struct Reference

### Data Fields

- [\\_MitigationDevInfo](#) `MitigationDevInfo`
- `BYTE` `currentMitigationLvl`

### 8.599.1 Detailed Description

This structure contains LOC Cradle Mount Config Status

#### Parameters

<i>MitigationDev-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">MitigationDevInfo</a> for more information.</li> </ul>
<i>current-MitigationLvl</i>	<ul style="list-style-type: none"> <li>• Current Thermal Mitigation Level</li> </ul>

### 8.599.2 Field Documentation

8.599.2.1 `BYTE` `QmiCbkTmdMitiLvlRptInd::currentMitigationLvl`

8.599.2.2 `_MitigationDevInfo` `QmiCbkTmdMitiLvlRptInd::MitigationDevInfo`

## 8.600 QmiCbkWdsStatisticsIndState Struct Reference

### Data Fields

- `DataUlongTlv` `TxOkConutTlv`
- `DataUlongTlv` `RxOkConutTlv`
- `DataUlongLongTlv` `TxOkByteCountTlv`
- `DataUlongLongTlv` `RxOkByteCountTlv`
- `DataUlongTlv` `TxDropConutTlv`
- `DataUlongTlv` `RxDropConutTlv`

### 8.600.1 Detailed Description

WDS Pkt RM Transfer Statistics data structure for individual session

## Parameters

<i>TxOkConutTlv</i>	<ul style="list-style-type: none"> <li>• Tx Ok Packet Tlv Value.</li> </ul>
<i>RxOkConutTlv</i>	<ul style="list-style-type: none"> <li>• Rx Ok Packet Tlv Value.</li> </ul>
<i>TxOkByteCountTlv</i>	<ul style="list-style-type: none"> <li>• Tx Ok Byte Count Packet Tlv Value.</li> </ul>
<i>RxOkByteCountTlv</i>	<ul style="list-style-type: none"> <li>• Rx Ok Byte Count Packet Tlv Value.</li> </ul>
<i>TxDropConutTlv</i>	<ul style="list-style-type: none"> <li>• Tx Drop Count Packet Tlv Value.</li> </ul>
<i>RxDropConutTlv</i>	<ul style="list-style-type: none"> <li>• Rx Drop Count Packet Tlv Value.</li> </ul>

## 8.600.2 Field Documentation

8.600.2.1 DataULongTlv QmiCbkWdsStatisticsIndState::RxDropConutTlv

8.600.2.2 DataULongLongTlv QmiCbkWdsStatisticsIndState::RxOkByteCountTlv

8.600.2.3 DataULongTlv QmiCbkWdsStatisticsIndState::RxOkConutTlv

8.600.2.4 DataULongTlv QmiCbkWdsStatisticsIndState::TxDropConutTlv

8.600.2.5 DataULongLongTlv QmiCbkWdsStatisticsIndState::TxOkByteCountTlv

8.600.2.6 DataULongTlv QmiCbkWdsStatisticsIndState::TxOkConutTlv

## 8.601 qmifwinfo\_s Struct Reference

## Data Fields

- union {
  - struct fwinfo\_s g
  - struct slqsfwinfo\_s s
 } dev

## 8.601.1 Detailed Description

Top level structure for storing information about firmware images. union of structures depending on device type, MC77xx or MC83xx

## Parameters

<i>g</i>	- structure for MC83xx devices
<i>s</i>	- structure for devices with SPKG CWE file support

- List of various Firmware Images Supported

Technology	Initials	Carrier	Region	Network Technology
D3600	S	eGOBI_IMG_CAR_SPRINT	eGOBI_IMG_REG_NA	eGOBI_IMG_TECH_CDMA
D3600	V	eGOBI_IMG_CAR_VERIZON	eGOBI_IMG_REG_NA	eGOBI_IMG_TECH_CDMA
D3600	C	eGOBI_IMG_CAR_CHINA_TELECOM	eGOBI_IMG_REG_ASIA	eGOBI_IMG_TECH_CDMA
D3600	G	eGOBI_IMG_CAR_GENERIC_CDMA	eGOBI_IMG_REG_GLOBAL	eGOBI_IMG_TECH_CDMA (item for Generic
D3600	H	eGOBI_IMG_CAR_GENERIC_CDMA	eGOBI_IMG_REG_GLOBAL	eGOBI_IMG_TECH_CDMA (item for Generic
D3200	V	eGOBI_IMG_CAR_VODAFONE	eGOBI_IMG_REG_NA	eGOBI_IMG_TECH_UMTS
D3200	A	eGOBI_IMG_CAR_ATT	eGOBI_IMG_REG_NA	eGOBI_IMG_TECH_UMTS
D3200	L	eGOBI_IMG_CAR_TMOBILE	eGOBI_IMG_REG_EU	eGOBI_IMG_TECH_UMTS
D3200	G	eGOBI_IMG_CAR_GENERIC	eGOBI_IMG_REG_GLOBAL	eGOBI_IMG_TECH_UMTS
D3200	H	eGOBI_IMG_CAR_TELEFONICA	eGOBI_IMG_REG_EU	eGOBI_IMG_TECH_UMTS
D3200	I	eGOBI_IMG_CAR_TELCOM_ITALIA	eGOBI_IMG_REG_NA	eGOBI_IMG_TECH_UMTS
D3200	O	eGOBI_IMG_CAR_ORANGE	eGOBI_IMG_REG_NA	eGOBI_IMG_TECH_UMTS
D3200	U	eGOBI_IMG_CAR_GENERIC	eGOBI_IMG_REG_GLOBAL	eGOBI_IMG_TECH_UMTS
D3200	R	eGOBI_IMG_CAR_ROGERS	eGOBI_IMG_REG_NA	eGOBI_IMG_TECH_UMTS
D3600	A	eGOBI_IMG_CAR_AERIS	eGOBI_IMG_REG_NA	eGOBI_IMG_TECH_CDMA

## See Also

[fwinfo\\_s](#)  
[slqsfwinfo\\_s](#)

## 8.601.2 Field Documentation

8.601.2.1 union { ... } qmifwinfo\_s::dev

8.601.2.2 struct fwinfo\_s qmifwinfo\_s::g

8.601.2.3 struct slqsfwinfo\_s qmifwinfo\_s::s

## 8.602 QmiNas3GppNetworkInfo Struct Reference

## Data Fields

- [WORD pMCC](#)
- [WORD pMNC](#)
- [ULONG plnUse](#)
- [ULONG pRoaming](#)
- [ULONG pForbidden](#)
- [ULONG pPreferred](#)
- [CHAR pDescription](#) [255]

## 8.602.1 Detailed Description

This structure contains the PerformNetworkScan response parameters. This structure will hold the array of the network scan information.

## Parameters

<i>pMCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
<i>pMNC</i>	<ul style="list-style-type: none"> <li>• Mobile Networ Code</li> </ul>
<i>pInUse</i>	<ul style="list-style-type: none"> <li>• Is the Network the current serving Network <ul style="list-style-type: none"> <li>– 0 – Unknown</li> <li>– 1 – Current serving network</li> <li>– 2 – Not current serving network, available</li> </ul> </li> </ul>
<i>pRoaming</i>	<ul style="list-style-type: none"> <li>• Home/Roam Status of the Network <ul style="list-style-type: none"> <li>– 0 – Unknown</li> <li>– 1 – Home</li> <li>– 2 – Roam</li> </ul> </li> </ul>
<i>pForbidden</i>	<ul style="list-style-type: none"> <li>• Is the Network in the forbidden network list <ul style="list-style-type: none"> <li>– 0 – Unknown</li> <li>– 1 – Forbidden</li> <li>– 2 – Not Forbidden</li> </ul> </li> </ul>
<i>pPreferred</i>	<ul style="list-style-type: none"> <li>• Is the Network in the Preferred network list <ul style="list-style-type: none"> <li>– 0 – Unknown</li> <li>– 1 – Preferred</li> <li>– 2 – Not Preferred</li> </ul> </li> </ul>
<i>pDescription</i>	<ul style="list-style-type: none"> <li>• Network Name/Description</li> </ul>

## 8.602.2 Field Documentation

8.602.2.1 CHAR QmiNas3GppNetworkInfo::pDescription[255]

8.602.2.2 ULONG QmiNas3GppNetworkInfo::pForbidden

8.602.2.3 ULONG QmiNas3GppNetworkInfo::pInUse

8.602.2.4 WORD QmiNas3GppNetworkInfo::pMCC

8.602.2.5 WORD QmiNas3GppNetworkInfo::pMNC

8.602.2.6 ULONG QmiNas3GppNetworkInfo::pPreferred

8.602.2.7 ULONG QmiNas3GppNetworkInfo::pRoaming

## 8.603 QmiNasGetRFBandInfoResp Struct Reference

### Data Fields

- struct qmTlvResult [results](#)
- [BYTE](#) \* [pInstancesSize](#)
- struct [RFBandInfoElements](#) \* [pRFBandInfoElements](#)

### 8.603.1 Field Documentation

8.603.1.1 [BYTE](#)\* QmiNasGetRFBandInfoResp::pInstancesSize

8.603.1.2 struct [RFBandInfoElements](#)\* QmiNasGetRFBandInfoResp::pRFBandInfoElements

8.603.1.3 struct qmTlvResult QmiNasGetRFBandInfoResp::results

## 8.604 QmiNasPerformNetworkScanResp Struct Reference

### Data Fields

- struct qmTlvResult [results](#)
- [BYTE](#) \* [pInstanceSize](#)
- struct [QmiNas3GppNetworkInfo](#) \* [pInstances](#)

### 8.604.1 Field Documentation

8.604.1.1 struct [QmiNas3GppNetworkInfo](#)\* QmiNasPerformNetworkScanResp::pInstances

8.604.1.2 [BYTE](#)\* QmiNasPerformNetworkScanResp::pInstanceSize

8.604.1.3 struct qmTlvResult QmiNasPerformNetworkScanResp::results

## 8.605 qmiSmsMessageList Struct Reference

### Data Fields

- uint32\_t [messageIndex](#)
- uint32\_t [messageTag](#)

### 8.605.1 Detailed Description

## Parameters

<i>messageIndex</i>	<ul style="list-style-type: none"> <li>• Message index of each matched message</li> </ul>
<i>messageTag</i>	<ul style="list-style-type: none"> <li>• Messagetag</li> </ul>

## 8.605.2 Field Documentation

8.605.2.1 uint32\_t qmiSmsMessageList::messageIndex

8.605.2.2 uint32\_t qmiSmsMessageList::messageTag

## 8.606 qmiWSDDataBearerTechnology Struct Reference

## Data Fields

- uint8\_t [currentNetwork](#)
- uint32\_t [ratMask](#)
- uint32\_t [soMask](#)

## 8.606.1 Detailed Description

## Parameters

<i>currentNetwork</i>	current selected network
<i>Radio</i>	Access Technology (RAT) mask
<i>soMask</i>	Service Option (SO) mask

## 8.606.2 Field Documentation

8.606.2.1 uint8\_t qmiWSDDataBearerTechnology::currentNetwork

8.606.2.2 uint32\_t qmiWSDDataBearerTechnology::ratMask

8.606.2.3 uint32\_t qmiWSDDataBearerTechnology::soMask

## 8.607 QmiWdslpAddressInfo Struct Reference

## Data Fields

- [ULONG](#) \* [pIPAddressV4](#)
- [USHORT](#) \* [pIPAddressV6](#)
- [BYTE](#) \* [pIPv6prefixlen](#)

## 8.607.1 Detailed Description



## Parameters

<i>pIPAddressV4</i> [- OUT]	<ul style="list-style-type: none"> <li>Current IPv4 address</li> <li>default value of 0 if not reported by the device.</li> </ul>
<i>pIPAddressV6</i> [- OUT]	<ul style="list-style-type: none"> <li>Current IPv6 address</li> </ul> <p>Space for storing the 8 element array of type USHORT for the IPv6 address is allocated by the application.</p> <p>The IP Address is stored in the user supplied buffer as follows:</p> <p>User buffer:</p> <p>[&lt;U0&gt;..&lt;&lt;U7&gt;]</p> <p>IPv6 address from the network:</p> <p>1234:2A01:.....:5678</p> <p>User buffer contents:</p> <p>U0 corresponds to 1234</p> <p>U1 corresponds to 2A01</p> <p>-----</p> <p>-----</p> <p>U7 corresponds to 5678</p>
<i>pIPv6prefixlen</i> [- OUT]	<ul style="list-style-type: none"> <li>IPv6 prefix length in number of bits</li> </ul>

## 8.607.2 Field Documentation

8.607.2.1 ULONG\* QmiWdsIpAddressInfo::pIPAddressV4

8.607.2.2 USHORT\* QmiWdsIpAddressInfo::pIPAddressV6

8.607.2.3 BYTE\* QmiWdsIpAddressInfo::pIPv6prefixlen

## 8.608 qmiWdsRunTimeSettings Struct Reference

## Data Fields

- CHAR \* pProfileName
- ULONG \* pPDPTType
- CHAR \* pAPNName
- ULONG \* pPrimaryDNSV4
- ULONG \* pSecondaryDNSV4
- struct UMTSQoS \* pUMTSGrantedQoS
- struct GPRSQoS \* pGPRSGrantedQoS
- CHAR \* pUsername
- ULONG \* pAuthentication
- ULONG \* pIPAddressV4
- struct ProfileIdentifier \* pProfileID
- ULONG \* pGWAddressV4

- [ULONG](#) \* [pSubnetMaskV4](#)
- [BYTE](#) \* [pPCSCFAddrPCO](#)
- [struct](#) [PCSCFIPv4ServerAddressList](#) \* [pServerAddrList](#)
- [struct](#) [PCSCFFQDNAddressList](#) \* [pPCSCFFQDNAddrList](#)
- [USHORT](#) \* [pPrimaryDNSV6](#)
- [USHORT](#) \* [pSecondaryDNSV6](#)
- [ULONG](#) \* [pMtu](#)
- [struct](#) [DomainNameList](#) \* [pDomainList](#)
- [BYTE](#) \* [pIPFamilyPreference](#)
- [BYTE](#) \* [pIMCNflag](#)
- [WORD](#) \* [pTechnology](#)
- [struct](#) [IPv6AddressInfo](#) \* [pIPv6AddrInfo](#)
- [struct](#) [IPv6GWAddressInfo](#) \* [pIPv6GWAddrInfo](#)

### 8.608.1 Detailed Description

This structure contains the [WdsRunTimeSettings](#) Information

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>pProfileName</i>	<ul style="list-style-type: none"> <li>• Profile name</li> </ul> <p>One or more bytes describing the profile. Description may be a user-defined name for the profile.</p> <p>QMI_ERR_ARG_TOO_LONG is returned if profile_name is too long.</p>
<i>pPDPTType</i>	<ul style="list-style-type: none"> <li>• PDP type <ul style="list-style-type: none"> <li>– 0 – PDP-IP (IPv4)</li> <li>– 1 - PDP-PPP</li> <li>– 2 - PDP-IPv6</li> <li>– 3 - PDP-IPv4v6</li> <li>– 0xffffffff - invalid</li> </ul> </li> </ul>
<i>pAPNName</i>	<ul style="list-style-type: none"> <li>• Access point name</li> </ul> <p>String parameter that is a logical name used to select the GGSN and external packet data network.</p> <p>If value is NULL or omitted, then the subscription default value is requested.</p> <p>QMI_ERR_ARG_TOO_LONG is returned if the APN name is too long.</p>

<i>pPrimaryDNSV4</i>	<ul style="list-style-type: none"> <li>• Primary DNS IPv4 Address</li> </ul>
<i>pSecondaryDNSV4</i>	<ul style="list-style-type: none"> <li>• Secondary DNS IPv4 Address</li> </ul>
<i>pUMTSGrantedQoS</i>	<ul style="list-style-type: none"> <li>• UMTS Granted QoS</li> </ul>
<i>pGPRSGrantedQoS</i>	<ul style="list-style-type: none"> <li>• GPRS Granted QoS</li> </ul>
<i>pUsername</i>	<ul style="list-style-type: none"> <li>• User name used during data network authentication</li> </ul>
<i>pAuthentication</i>	<ul style="list-style-type: none"> <li>• Authentication preference <ul style="list-style-type: none"> <li>– Bit 0 – PAP preference <ul style="list-style-type: none"> <li>* 0 – PAP is never performed</li> <li>* 1 – PAP may be performed</li> </ul> </li> <li>– Bit 1 – CHAP preference <ul style="list-style-type: none"> <li>* 0 – CHAP is never performed</li> <li>* 1 – CHAP may be performed</li> </ul> </li> </ul> </li> </ul>
<i>pIPAddressV4</i>	<ul style="list-style-type: none"> <li>• IPV4 Address assigned to the TE</li> </ul>
<i>pProfileID</i>	<ul style="list-style-type: none"> <li>• Profile Identifier</li> </ul>
<i>pGWAddressV4</i>	<ul style="list-style-type: none"> <li>• IPV4 Gateway Address</li> </ul>
<i>pSubnetMaskV4</i>	<ul style="list-style-type: none"> <li>• IPV4 Subnet Mask</li> </ul>
<i>pPCSCFAddrPCO</i>	<ul style="list-style-type: none"> <li>• PCSCF address using PCO values <ul style="list-style-type: none"> <li>– 1 – (TRUE) implies request PCSCF address using PCO</li> <li>– 0 – (FALSE) implies do not request. This is the default value.</li> </ul> </li> </ul>
<i>pServerAddrList</i>	<ul style="list-style-type: none"> <li>• P-CSCF IPv4 Server Address List</li> </ul>
<i>pPCSCFFQDNAddrList</i>	<ul style="list-style-type: none"> <li>• P-CSCF FQDN Address List</li> </ul>
<i>pPrimaryDNSV6</i>	<ul style="list-style-type: none"> <li>• Primary DNS IPv6 Address</li> </ul>

<i>pSecondaryDN-SV6</i>	<ul style="list-style-type: none"> <li>• Secondary DNS IPv6 Address</li> </ul>
<i>mtu</i>	<ul style="list-style-type: none"> <li>• MTU</li> </ul>
<i>pDomainList</i>	<ul style="list-style-type: none"> <li>• Domain-Name List</li> </ul>
<i>pIPFamily-Preference</i>	<ul style="list-style-type: none"> <li>• IP family <ul style="list-style-type: none"> <li>– 0x04 – IPV4 ADDR</li> <li>– 0x06 – IPV6 ADDR</li> </ul> </li> </ul>
<i>pIMCNflag</i>	<ul style="list-style-type: none"> <li>• IM CN Flag <ul style="list-style-type: none"> <li>– 0x00 – FALSE</li> <li>– 0x01 – TRUE</li> </ul> </li> </ul>
<i>pTechnology</i>	<ul style="list-style-type: none"> <li>• Technology <ul style="list-style-type: none"> <li>– CDMA – 0x8001</li> <li>– UMTS – 0x8004</li> </ul> </li> </ul>
<i>pIPV6Address-Info</i>	<ul style="list-style-type: none"> <li>• IPV6 Address Information</li> </ul>
<i>pIPV6GW-AddressInfo</i>	<ul style="list-style-type: none"> <li>• IPV6 Gateway Address Information</li> </ul>

## 8.608.2 Field Documentation

8.608.2.1 **CHAR\*** qmiWdsRunTimeSettings::pAPNName

8.608.2.2 **ULONG\*** qmiWdsRunTimeSettings::pAuthentication

8.608.2.3 **struct DomainNameList\*** qmiWdsRunTimeSettings::pDomainList

8.608.2.4 **struct GPRSQoS\*** qmiWdsRunTimeSettings::pGPRSGrantedQoS

8.608.2.5 **ULONG\*** qmiWdsRunTimeSettings::pGWAddressV4

8.608.2.6 **BYTE\*** qmiWdsRunTimeSettings::pIMCNflag

8.608.2.7 **ULONG\*** qmiWdsRunTimeSettings::pIPAddressV4

8.608.2.8 **BYTE\*** qmiWdsRunTimeSettings::pIPFamilyPreference

- 8.608.2.9 struct IPV6AddressInfo\* qmiWdsRunTimeSettings::pIPv6AddrInfo
- 8.608.2.10 struct IPV6GWAddressInfo\* qmiWdsRunTimeSettings::pIPv6GWAddrInfo
- 8.608.2.11 ULONG\* qmiWdsRunTimeSettings::pMtu
- 8.608.2.12 BYTE\* qmiWdsRunTimeSettings::pPCSCFAddrPCO
- 8.608.2.13 struct PCSCFFQDNAddressList\* qmiWdsRunTimeSettings::pPCSCFFQDNAddrList
- 8.608.2.14 ULONG\* qmiWdsRunTimeSettings::pPDPTType
- 8.608.2.15 ULONG\* qmiWdsRunTimeSettings::pPrimaryDNSV4
- 8.608.2.16 USHORT\* qmiWdsRunTimeSettings::pPrimaryDNSV6
- 8.608.2.17 struct ProfileIdentifier\* qmiWdsRunTimeSettings::pProfileID
- 8.608.2.18 CHAR\* qmiWdsRunTimeSettings::pProfileName
- 8.608.2.19 ULONG\* qmiWdsRunTimeSettings::pSecondaryDNSV4
- 8.608.2.20 USHORT\* qmiWdsRunTimeSettings::pSecondaryDNSV6
- 8.608.2.21 struct PCSCFIPv4ServerAddressList\* qmiWdsRunTimeSettings::pServerAddrList
- 8.608.2.22 ULONG\* qmiWdsRunTimeSettings::pSubnetMaskV4
- 8.608.2.23 WORD\* qmiWdsRunTimeSettings::pTechnology
- 8.608.2.24 struct UMTSQoS\* qmiWdsRunTimeSettings::pUMTSGrantedQoS
- 8.608.2.25 CHAR\* qmiWdsRunTimeSettings::pUsername

## 8.609 QosClassID Struct Reference

### Data Fields

- [BYTE QCI](#)
- [ULONG gDIBitRate](#)
- [ULONG maxDIBitRate](#)
- [ULONG gUIBitRate](#)
- [ULONG maxUIBitRate](#)

### 8.609.1 Detailed Description

structure contains 3GPP LTE QoS parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>QCI</i>	<ul style="list-style-type: none"> <li>QOS specified using the QOS Class Identifier (QOS) values QCI value 0 - Requests the network to assign the appropriate QCI value QCI values 1-4 - Associated with guaranteed bit rates QCI values 5-9 - Associated with non-guaranteed bit rates</li> </ul>
<i>gDlBitRate</i>	<ul style="list-style-type: none"> <li>Guaranteed DL bit rate</li> </ul>
<i>maxDlBitRate</i>	<ul style="list-style-type: none"> <li>maxDlBitRate</li> </ul>
<i>gUlBitRate</i>	<ul style="list-style-type: none"> <li>Guaranteed UL bit rate</li> </ul>
<i>maxUlBitRate</i>	<ul style="list-style-type: none"> <li>Maximum UL bit rate</li> </ul>

## 8.609.2 Field Documentation

8.609.2.1 **ULONG** QosClassID::gDlBitRate8.609.2.2 **ULONG** QosClassID::gUlBitRate8.609.2.3 **ULONG** QosClassID::maxDlBitRate8.609.2.4 **ULONG** QosClassID::maxUlBitRate8.609.2.5 **BYTE** QosClassID::QCI

## 8.610 QosEventInfo Struct Reference

## Data Fields

- ULONG** \* [pDataBearer](#)
- ULONG** \* [pPacketsCountTX](#)
- ULONG** \* [pPacketsCountRX](#)
- ULONGLONG** \* [pTotalBytesTX](#)
- ULONGLONG** \* [pTotalBytesRX](#)

## 8.610.1 Detailed Description

Contains the WDS event information and information about the interface

## Parameters

<i>pQmiInterface-Info</i>	<ul style="list-style-type: none"> <li>See <a href="#">qaQmiInterfaceInfo</a> for more information</li> </ul>
---------------------------	---

<i>pDataBearer</i>	<ul style="list-style-type: none"><li>• Data bearer technology (NULL if not present)<ul style="list-style-type: none"><li>– 0x00 - Indicates that this field is ignored</li><li>– 0x01 - CDMA 1X</li><li>– 0x02 - EV-DO Rev 0</li><li>– 0x03 - GPRS</li><li>– 0x04 - WCDMA</li><li>– 0x05 - EV-DO Rev A</li><li>– 0x06 - EDGE</li><li>– 0x07 - HSDPA and WCDMA</li><li>– 0x08 - WCDMA and HSUPA</li><li>– 0x09 - HSDPA and HSUPA</li><li>– 0x0A - LTE</li><li>– 0x0B - EV-DO Rev A EHRPD</li><li>– 0x0C - HSDPA+ and WCDMA</li><li>– 0x0D - HSDPA+ and HSUPA</li><li>– 0x0E - DC_HSDPA+ and WCDMA</li><li>– 0x0F - DC_HSDPA+ and HSUPA</li><li>– 0x8000 - NULL Bearer</li><li>– 0xFF - Unknown Technology</li></ul></li></ul>
--------------------	---

<i>pDormancy-Status</i>	<ul style="list-style-type: none"> <li>• Dormancy status (NULL if not present) <ul style="list-style-type: none"> <li>– 1 - traffic channel dormant</li> <li>– 2 - traffic channel active</li> </ul> </li> </ul>
<i>pPacketsCount-TX</i>	<ul style="list-style-type: none"> <li>• Packets transmitted without error (NULL if not present)</li> </ul>
<i>pPacketsCount-RX</i>	<ul style="list-style-type: none"> <li>• Packets received without error (NULL if not present)</li> </ul>
<i>pTotalBytesTX</i>	<ul style="list-style-type: none"> <li>• Bytes transmitted without error (NULL if not present)</li> </ul>
<i>pTotalBytesRX</i>	<ul style="list-style-type: none"> <li>• Bytes received without error (NULL if not present)</li> </ul>

## 8.610.2 Field Documentation

8.610.2.1 **ULONG\*** QosEventInfo::pDataBearer

8.610.2.2 **ULONG\*** QosEventInfo::pPacketsCountRX

8.610.2.3 **ULONG\*** QosEventInfo::pPacketsCountTX

8.610.2.4 **ULONGLONG\*** QosEventInfo::pTotalBytesRX

8.610.2.5 **ULONGLONG\*** QosEventInfo::pTotalBytesTX

## 8.611 QosFlowInfo Struct Reference

### Data Fields

- [QosFlowInfoState](#) \* pQFlowState
- [swiQosFlow](#) \* pTxQFlowGranted
- [swiQosFlow](#) \* pRxQFlowGranted
- [swiQosFilter](#) \* pTxQFilter [MAX\_QOS\_FILTER\_TLV]
- [swiQosFilter](#) \* pRxQFilter [MAX\_QOS\_FILTER\_TLV]
- **BYTE** \* pBearerID

### 8.611.1 Detailed Description

This structure contains QoS flow info



## Parameters

<i>pQFlowState</i>	<ul style="list-style-type: none"> <li>QoS flow state information, please check <a href="#">QosFlowInfoState</a> for more information</li> </ul>
<i>pTxQFlow-Granted</i>	<ul style="list-style-type: none"> <li>pointer to the Tx Qos flow granted, please check <a href="#">swiQosFlow</a> for more information</li> </ul>
<i>pRxQFlow-Granted</i>	<ul style="list-style-type: none"> <li>pointer to the Rx Qos flow granted</li> </ul>
<i>pTxQFilter</i>	<ul style="list-style-type: none"> <li>pointer to the Tx Qos filter</li> </ul>
<i>pRxQFilter</i>	<ul style="list-style-type: none"> <li>pointer to the Rx Qos flow</li> </ul>
<i>pBearerID</i>	<ul style="list-style-type: none"> <li>pointer to the bearer ID</li> <li>Bearer ID or Radio Link Protocol (RLP) ID of the activated flow.</li> <li>Valid Values - 0 to 16</li> <li>0xFF - Invalid value.</li> </ul>

## 8.611.2 Field Documentation

8.611.2.1 **BYTE\*** QosFlowInfo::pBearerID8.611.2.2 **QosFlowInfoState\*** QosFlowInfo::pQFlowState8.611.2.3 **swiQosFilter\*** QosFlowInfo::pRxQFilter[MAX\_QOS\_FILTER\_TLV]8.611.2.4 **swiQosFlow\*** QosFlowInfo::pRxQFlowGranted8.611.2.5 **swiQosFilter\*** QosFlowInfo::pTxQFilter[MAX\_QOS\_FILTER\_TLV]8.611.2.6 **swiQosFlow\*** QosFlowInfo::pTxQFlowGranted

## 8.612 QosFlowInfoState Struct Reference

## Data Fields

- [ULONG](#) id
- [BYTE](#) isNewFlow
- [BYTE](#) state

## 8.612.1 Detailed Description

This structure contains QoS flow state

## Parameters

<i>id</i>	QoS identifier
<i>isNewFlow</i>	<ul style="list-style-type: none"> <li>• 1 – Newly added flow</li> <li>• 0 – Existing flow</li> </ul>
<i>state</i>	This indicates that the flow that was added/modified/deleted: <ul style="list-style-type: none"> <li>• 0x01 – Flow activated</li> <li>• 0x02 – Flow modified</li> <li>• 0x03 – Flow deleted</li> <li>• 0x04 – Flow suspended</li> <li>• 0x05 – Flow enabled</li> <li>• 0x06 – Flow disabled</li> </ul>

## 8.612.2 Field Documentation

8.612.2.1 **ULONG** QosFlowInfoState::id8.612.2.2 **BYTE** QosFlowInfoState::isNewFlow8.612.2.3 **BYTE** QosFlowInfoState::state

## 8.613 QosMap Struct Reference

## Data Fields

- [BYTE](#) dscp
- [ULONG](#) qos\_id
- [BYTE](#) state

## 8.613.1 Detailed Description

This structure contains the SLQSQosDumpMap Information

## Parameters

<i>dscp</i>	<ul style="list-style-type: none"> <li>• Differential Service Code Point(DSCP) value</li> </ul>
<i>qos_id</i>	<ul style="list-style-type: none"> <li>• QoS identifier</li> </ul>
<i>state</i>	<ul style="list-style-type: none"> <li>• QoS Flow state</li> </ul>

### 8.613.2 Field Documentation

8.613.2.1 **BYTE** QosMap::dscp

8.613.2.2 **ULONG** QosMap::qos\_id

8.613.2.3 **BYTE** QosMap::state

## 8.614 RankIndicatorInd Struct Reference

### Data Fields

- [WORD Count1](#)
- [WORD Count2](#)

### 8.614.1 Field Documentation

8.614.1.1 **WORD** RankIndicatorInd::Count1

8.614.1.2 **WORD** RankIndicatorInd::Count2

## 8.615 readResult Struct Reference

### Data Fields

- [WORD contentLen](#)
- [BYTE content](#) [255+1]

### 8.615.1 Detailed Description

This structure contains the information for write operation.

#### Parameters

<i>contentLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of content.</li> </ul>
<i>content</i> [ <i>MAX_DESCRIPTION_LENGTH</i> ]	<ul style="list-style-type: none"> <li>• Read content.</li> <li>• The content is the sequence of bytes as read from the card.</li> </ul>

### 8.615.2 Field Documentation

8.615.2.1 **BYTE** readResult::content[255+1]

8.615.2.2 **WORD** readResult::contentLen

## 8.616 readTransparentInfo Struct Reference

## Data Fields

- [WORD offset](#)
- [WORD length](#)

### 8.616.1 Detailed Description

This structure contains the information for read operation.

#### Parameters

<i>offset</i>	<ul style="list-style-type: none"> <li>• Offset for the read operation.</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>• Length of the content to be read.</li> <li>• The value 0 is used to read the complete file.</li> </ul>

### 8.616.2 Field Documentation

#### 8.616.2.1 WORD readTransparentInfo::length

#### 8.616.2.2 WORD readTransparentInfo::offset

## 8.617 redirNumInfo Struct Reference

## Data Fields

- [BYTE PI](#)
- [BYTE SI](#)
- [BYTE numType](#)
- [BYTE numPlan](#)
- [BYTE reason](#)
- [BYTE numLen](#)
- [BYTE number](#) [255]

### 8.617.1 Detailed Description

This structure contains Redirecting Number Information

#### Parameters

<i>PI</i>	<ul style="list-style-type: none"> <li>• Presentation indicator; refer to [S1, Table 2.7.4.4-1] for valid values.</li> </ul>
<i>SI</i>	<ul style="list-style-type: none"> <li>• Number of sets of following elements <ul style="list-style-type: none"> <li>– Caller Id</li> </ul> </li> </ul>

<i>SI</i>	<ul style="list-style-type: none"> <li>• Number screening indicator.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_SI_USER_PROVIDED_NOT_SCREENED - Provided user is not screened</li> <li>– 0x01 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_PASSED - Provided user passed verification</li> <li>– 0x02 - QMI_VOICE_SI_USER_PROVIDED_VERIFIED_FAILED - Provided user failed verification</li> <li>– 0x03 - QMI_VOICE_SI_NETWORK_PROVIDED - Provided network</li> </ul> </li> </ul>
<i>numType</i>	<ul style="list-style-type: none"> <li>• Number type.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_TYPE_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_TYPE_INTERNATIONAL - International</li> <li>– 0x02 - QMI_VOICE_NUM_TYPE_NATIONAL - National</li> <li>– 0x03 - QMI_VOICE_NUM_TYPE_NETWORK_SPECIFIC - Network-specific</li> <li>– 0x04 - QMI_VOICE_NUM_TYPE_SUBSCRIBER - Subscriber</li> <li>– 0x05 - QMI_VOICE_NUM_TYPE_RESERVED - Reserved</li> <li>– 0x06 - QMI_VOICE_NUM_TYPE_ABBREVIATED - Abbreviated</li> <li>– 0x07 - QMI_VOICE_NUM_TYPE_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>
<i>numPlan</i>	<ul style="list-style-type: none"> <li>• Number plan.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - QMI_VOICE_NUM_PLAN_UNKNOWN - Unknown</li> <li>– 0x01 - QMI_VOICE_NUM_PLAN_ISDN - ISDN</li> <li>– 0x03 - QMI_VOICE_NUM_PLAN_DATA - Data</li> <li>– 0x04 - QMI_VOICE_NUM_PLAN_TELEX - Telex</li> <li>– 0x08 - QMI_VOICE_NUM_PLAN_NATIONAL - National</li> <li>– 0x09 - QMI_VOICE_NUM_PLAN_PRIVATE - Private</li> <li>– 0x0B - QMI_VOICE_NUM_PLAN_RESERVED_CTS - Reserved cordless telephony system</li> <li>– 0x0F - QMI_VOICE_NUM_PLAN_RESERVED_EXTENSION - Reserved extension</li> </ul> </li> </ul>

<i>reason</i>	-Redirecting reason; refer to [S1, Table 3.7.5.11-1] for valid values
<i>numLen</i>	<ul style="list-style-type: none"> <li>Provides the length of number which follow.</li> </ul>
<i>number[255]</i>	<ul style="list-style-type: none"> <li>number of numLen length, NULL terminated.</li> </ul>

## 8.617.2 Field Documentation

8.617.2.1 **BYTE** `redirNumInfo::number[255]`

8.617.2.2 **BYTE** `redirNumInfo::numLen`

8.617.2.3 **BYTE** `redirNumInfo::numPlan`

8.617.2.4 **BYTE** `redirNumInfo::numType`

8.617.2.5 **BYTE** `redirNumInfo::PI`

8.617.2.6 **BYTE** `redirNumInfo::reason`

8.617.2.7 **BYTE** `redirNumInfo::SI`

## 8.618 registerRefresh Struct Reference

### Data Fields

- [BYTE](#) `registerFlag`
- [BYTE](#) `voteForInit`
- [WORD](#) `numFiles`
- [fileInfo](#) `arrfileInfo` [255]

### 8.618.1 Detailed Description

This structure contains paramaters of refresh Information

#### Parameters

<i>registerFlag</i>	<ul style="list-style-type: none"> <li>Flag that indicates whether to register or deregister for refresh indications. Valid values: <ul style="list-style-type: none"> <li>0 - Deregister</li> <li>1 - Register</li> </ul> </li> </ul>
---------------------	--

<i>voteForInit</i>	<ul style="list-style-type: none"> <li>Flag that indicates whether to vote for the init when there is a refresh. Valid values: <ul style="list-style-type: none"> <li>0 - Client does not vote for initialization</li> <li>1 - Client votes for initialization</li> </ul> </li> </ul>
<i>numFiles</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements: <ul style="list-style-type: none"> <li>file_id</li> <li>path_len</li> <li>path</li> </ul> </li> </ul>
<i>arrfileInfo</i>	<ul style="list-style-type: none"> <li>Array of file Information structure.</li> <li>See /ref <a href="#">fileInfo</a> for more information</li> </ul>

## 8.618.2 Field Documentation

8.618.2.1 **fileInfo** registerRefresh::arrfileInfo[255]

8.618.2.2 **WORD** registerRefresh::numFiles

8.618.2.3 **BYTE** registerRefresh::registerFlag

8.618.2.4 **BYTE** registerRefresh::voteForInit

## 8.619 remainingRetries Struct Reference

### Data Fields

- [BYTE](#) [verifyLeft](#)
- [BYTE](#) [unblockLeft](#)

### 8.619.1 Detailed Description

This structure contains the information about the retries remaining.

#### Parameters

<i>verifyLeft</i>	<ul style="list-style-type: none"> <li>Number of remaining attempts to verify the PIN.</li> <li>0xFF, if unavailable.</li> </ul>
<i>unblockLeft</i>	<ul style="list-style-type: none"> <li>Number of remaining attempts to unblock the PIN.</li> <li>0xFF, if unavailable.</li> </ul>

**Note**

This value is returned only when the enable/disable operation has failed. This information is not sent for a hidden key PIN type.

**8.619.2 Field Documentation**

8.619.2.1 **BYTE** remainingRetries::unlockLeft

8.619.2.2 **BYTE** remainingRetries::verifyLeft

**8.620 remotePartyName Struct Reference****Data Fields**

- [BYTE](#) namePI
- [BYTE](#) codingScheme
- [BYTE](#) nameLen
- [BYTE](#) callerName [255]

**8.620.1 Detailed Description**

This structure contains information about the names that are dialed from the device or from which a call is received on the device.

**Parameters**

<i>namePI</i>	<ul style="list-style-type: none"><li>• Name presentation indicator.<ul style="list-style-type: none"><li>– 0x00 - PRESENTATION_NAME_PRESENTATION_ALLOWED - Allowed presentation</li><li>– 0x01 - PRESENTATION_NAME_PRESENTATION_RESTRICTED - Restricted presentation</li><li>– 0x02 - PRESENTATION_NAME_UNAVAILABLE - Unavailable presentation</li><li>– 0x03 - PRESENTATION_NAME_NAME_PRESENTATION_RESTRICTED - Restricted name presentation</li><li>– 0xFF - Not Available</li></ul></li></ul>
---------------	---



<i>codingScheme</i>	<ul style="list-style-type: none"><li>• Refer to Table10 <a href="#">qaGobiApiTableCodingScheme.h</a> for coding schemes</li><li>• 0xFF - Not Available</li></ul>
<i>nameLen</i>	<ul style="list-style-type: none"><li>• Provides the length of name which follow.</li><li>• If zero(0) then no further information exists.</li></ul>
<i>callerName[MA-X_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"><li>• Name in ASCII, NULL ending.</li></ul>

## 8.620.2 Field Documentation

8.620.2.1 BYTE remotePartyName::callerName[255]

8.620.2.2 BYTE remotePartyName::codingScheme

8.620.2.3 BYTE remotePartyName::nameLen

8.620.2.4 BYTE remotePartyName::namePI

## 8.621 remotePartyNum Struct Reference

### Data Fields

- [BYTE presentationInd](#)
- [BYTE numLen](#)
- [BYTE remPartyNumber](#) [81]

### 8.621.1 Detailed Description

This structure contains information about the numbers that are dialed from the device or from which a call is received on the device.

## Parameters

<i>presentationInd</i>	<ul style="list-style-type: none"> <li>• Presentation indicator. <ul style="list-style-type: none"> <li>– 0x00 - PRESENTATION_ALLOWED - Allowed presentation</li> <li>– 0x01 - PRESENTATION_RESTRICTED - Restricted presentation</li> <li>– 0x02 - PRESENTATION_NUM_UNAVAILABLE - Unavailable presentation</li> <li>– 0x04 - PRESENTATION_PAYPHONE - Payphone presentation (GSM/UMTS specific)</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>numLen</i>	<ul style="list-style-type: none"> <li>• Provides the length of number which follow.</li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>remParty- Number[MAX_ CALL_NO_LEN]</i>	<ul style="list-style-type: none"> <li>• Array of numbers in ASCII, NULL ending.</li> </ul>

## 8.621.2 Field Documentation

8.621.2.1 BYTE remotePartyNum::numLen

8.621.2.2 BYTE remotePartyNum::presentationInd

8.621.2.3 BYTE remotePartyNum::remPartyNumber[81]

## 8.622 ReqFieldsList Struct Reference

## Data Fields

- [BYTE requestFieldsLen](#)
- [BYTE requestFields](#) [256]

## 8.622.1 Detailed Description

This structure contains the Supported Request Fields List Information

## Parameters

<i>requestFields- Len</i>	<ul style="list-style-type: none"> <li>• Number of sets of the request fields.</li> </ul>
<i>requestFields</i>	<ul style="list-style-type: none"> <li>• Describes which optional field IDs are supported in QMI Request.</li> <li>• Array of uint8 is a bitmask where each bit represents a field ID.</li> <li>• Field 0-15 are mandatory, First Bit represents field ID 16,</li> <li>• Starting with the LSB, bit 0 represents Field ID 16, bit 1 represents ID 17.</li> </ul>

### 8.622.2 Field Documentation

8.622.2.1 [BYTE](#) ReqFieldsList::requestFields[256]

8.622.2.2 [BYTE](#) ReqFieldsList::requestFieldsLen

## 8.623 RespFieldsList Struct Reference

### Data Fields

- [BYTE](#) responseFieldsLen
- [BYTE](#) responseFields [256]

### 8.623.1 Detailed Description

This structure contains the Supported Response Fields List Information

#### Parameters

<i>responseFieldsLen</i>	<ul style="list-style-type: none"><li>• Number of sets of the response fields.</li></ul>
<i>responseFields</i>	<ul style="list-style-type: none"><li>• Describes which optional field IDs are supported in QMI Response.</li><li>• Format is same as request field.</li></ul>

### 8.623.2 Field Documentation

8.623.2.1 [BYTE](#) RespFieldsList::responseFields[256]

8.623.2.2 [BYTE](#) RespFieldsList::responseFieldsLen

## 8.624 RFBandInfoElements Struct Reference

### Data Fields

- [BYTE](#) radioInterface
- [WORD](#) activeBandClass
- [WORD](#) activeChannel
- [uint8\\_t](#) radioInterface
- [uint16\\_t](#) activeBandClass
- [uint16\\_t](#) activeChannel

### 8.624.1 Detailed Description

This structure contains the RFBandInfo response parameters.

## Parameters

<i>radioInterface</i>	<ul style="list-style-type: none"> <li>Radio interface technology <ul style="list-style-type: none"> <li>– See <a href="#">Tables</a> for Radio Interface</li> </ul> </li> </ul>
<i>activeBandClass</i>	<ul style="list-style-type: none"> <li>Active Band Class <ul style="list-style-type: none"> <li>– See <a href="#">Tables</a> for Band Classes</li> </ul> </li> </ul>
<i>activeChannel</i>	<ul style="list-style-type: none"> <li>Active channel (0 if channel is not relevant to the reported technology)</li> </ul>
<i>radioInterface</i>	radio interface technology
<i>activeBandClass</i>	active band class
<i>activeChannel</i>	active channel

## 8.624.2 Field Documentation

8.624.2.1 WORD RFBandInfoElements::activeBandClass

8.624.2.2 uint16\_t RFBandInfoElements::activeBandClass

8.624.2.3 WORD RFBandInfoElements::activeChannel

8.624.2.4 uint16\_t RFBandInfoElements::activeChannel

8.624.2.5 BYTE RFBandInfoElements::radioInterface

8.624.2.6 uint8\_t RFBandInfoElements::radioInterface

## 8.625 rmTrasnferStaticsReq Struct Reference

## Data Fields

- uint8\_t [bResetStatistics](#)
- uint32\_t [ulMask](#)

## 8.625.1 Detailed Description

## Parameters

<i>bResetStatistics</i>	Clear RM statistics
<i>ulMask</i>	Requested statistic bit mask

## 8.625.2 Field Documentation

8.625.2.1 uint8\_t rmTrasnferStaticsReq::bResetStatistics

8.625.2.2 uint32\_t rmTrasnferStaticsReq::ulMask

## 8.626 roamIndList Struct Reference

### Data Fields

- [BYTE numInstances](#)
- [BYTE radiolInterface](#) [0x0A]
- [BYTE roamIndicator](#) [0x0A]

### 8.626.1 Detailed Description

This structure contains the Roaming Indicator List

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• number of sets of radio interface currently in use and roaming indicator <ul style="list-style-type: none"> <li>– defaults to zero</li> </ul> </li> </ul>
<i>radiolInterface</i>	<ul style="list-style-type: none"> <li>• Radio Interface currently in use</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - RADIO_IF_CDMA_1xEVDO - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 - RADIO_IF_AMPS - AMPS</li> <li>– 0x04 - RADIO_IF_GSM - GSM</li> <li>– 0x05 - RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - RADIO_IF_LTE - LTE</li> </ul> </li> </ul>
<i>roamIndicator</i>	<ul style="list-style-type: none"> <li>• Roaming Indicator</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Roaming</li> <li>– 0x01 - Home</li> </ul> </li> </ul>

### 8.626.2 Field Documentation

#### 8.626.2.1 BYTE roamIndList::numInstances

#### 8.626.2.2 BYTE roamIndList::radiolInterface[0x0A]

#### 8.626.2.3 BYTE roamIndList::roamIndicator[0x0A]

## 8.627 RoamingInfo Struct Reference

## Data Fields

- [BYTE TlvPresent](#)
- [BYTE roaming\\_ind](#)

### 8.627.1 Field Documentation

#### 8.627.1.1 BYTE RoamingInfo::roaming\_ind

#### 8.627.1.2 BYTE RoamingInfo::TlvPresent

## 8.628 roamTimer Struct Reference

## Data Fields

- [BYTE namID](#)
- [ULONG roamTimerValue](#)

### 8.628.1 Detailed Description

This structure contains information about the Roam Timer.

#### Parameters

<i>namID</i>	<ul style="list-style-type: none"> <li>• Index of the NAM(Number Assignment Module) to be configured.</li> <li>• Range 0 to 3.</li> <li>• Some modems support only 1 or 2 NAMs.</li> <li>• 0xFF,if not available.</li> </ul>
<i>roamTimerValue</i>	<ul style="list-style-type: none"> <li>• Time in minutes.</li> <li>• Cumulative air time is slammed.</li> <li>• 0xFFFFFFFF,if not available.</li> </ul>

### 8.628.2 Field Documentation

#### 8.628.2.1 BYTE roamTimer::namID

#### 8.628.2.2 ULONG roamTimer::roamTimerValue

## 8.629 RSRPThresh Struct Reference

## Data Fields

- [BYTE RSRPThresListLen](#)
- [SHORT \\* pRSRPThresList](#)

### 8.629.1 Detailed Description

This structure contains RSRP threshold related parameters.

## Parameters

<i>RSRPThresListLen</i>	<ul style="list-style-type: none"> <li>Length of the LTE RSRP threshold list parameter to follow</li> </ul>
<i>pRSRPThresList</i>	<ul style="list-style-type: none"> <li>Sequence of thresholds delimiting current RSRP event reporting bands</li> <li>Every time a new RSRP value crosses a specified threshold value, an event report indication message with the new RSRQ value is sent to the requesting control point. For this field <ul style="list-style-type: none"> <li>RSRP values are applicable only for LTE</li> <li>RSRP values are measured in dBm, with a range of -44 dBm to -140 dBm</li> <li>Each RSRP threshold value is a signed byte value</li> <li>Maximum number of threshold values is 16</li> <li>At least one value must be specified</li> </ul> </li> </ul>

## 8.629.2 Field Documentation

8.629.2.1 **SHORT\*** RSRPThresh::pRSRPThresList8.629.2.2 **BYTE** RSRPThresh::RSRPThresListLen

## 8.630 rsrqInformation Struct Reference

## Data Fields

- [INT8 rsrq](#)
- [BYTE radiolf](#)

## 8.630.1 Detailed Description

This structure contains the RSRQ Information

## Parameters

<i>rsrq</i>	<ul style="list-style-type: none"> <li>RSRQ value in dB (signed integer value); valid range is -3 to -20 (-3 means -3 dB, -20 means -20 dB)</li> </ul>
<i>radiolf</i>	<ul style="list-style-type: none"> <li>Radio interface technology of the signal being measured <ul style="list-style-type: none"> <li>0x08 - LTE</li> </ul> </li> </ul>

## 8.630.2 Field Documentation

8.630.2.1 **BYTE** rsrqInformation::radiolf



8.630.2.2 INT8 rsrqInformation::rsrq

## 8.631 RSRQThresh Struct Reference

### Data Fields

- [BYTE RSRQThresListLen](#)
- [INT8 \\* pRSRQThresList](#)

### 8.631.1 Detailed Description

This structure contains RSRQ threshold related parameters.

#### Parameters

<i>RSRQThresListLen</i>	<ul style="list-style-type: none"> <li>• Length of the LTE RSRQ threshold list parameter to follow</li> </ul>
<i>pRSRQThresList</i>	<ul style="list-style-type: none"> <li>• Sequence of thresholds delimiting current RSRQ event reporting bands</li> <li>• Every time a new RSRQ value crosses a threshold value, an event report indication message with the new RSRQ value is sent to the requesting control point. For this field             <ul style="list-style-type: none"> <li>– RSRQ values are applicable only for LTE</li> <li>– RSRQ values are measured in dBm, with a range of -20 dBm to -3 dBm</li> <li>– Each RSRQ threshold value is a signed byte value</li> <li>– Maximum number of threshold values is 16</li> <li>– At least one value must be specified</li> </ul> </li> </ul>

### 8.631.2 Field Documentation

8.631.2.1 INT8\* RSRQThresh::pRSRQThresList

8.631.2.2 BYTE RSRQThresh::RSRQThresListLen

## 8.632 RSSIThresh Struct Reference

### Data Fields

- [BYTE RSSIThresListLen](#)
- [INT8 \\* pRSSIThresList](#)

### 8.632.1 Detailed Description

This structure contains RSSI threshold related parameters.

## Parameters

<i>RSSIThresListLen</i>	<ul style="list-style-type: none"> <li>Length of the RSSI threshold list parameter to follow</li> </ul>
<i>pRSSIThresList</i>	<ul style="list-style-type: none"> <li>RSSI in dBm( signed bytes )</li> <li>A value of -125 dBm or lower is used to indicate No Signal</li> <li>RSSI values have the following ranges (in dBm) <ul style="list-style-type: none"> <li>CDMA is -105 to -21</li> <li>HDR is -118 to -13</li> <li>GSM is -111 to -48</li> <li>WCDMA is -121 to 0</li> <li>LTE is -120 to 0</li> </ul> </li> <li>Threshold values specified above are used for all RATs</li> <li>The maximum number of threshold values is 16, each a signed byte value.</li> </ul>

## 8.632.2 Field Documentation

8.632.2.1 INT8\* RSSIThresh::pRSSIThresList

8.632.2.2 BYTE RSSIThresh::RSSIThresListLen

## 8.633 RXAGCList Struct Reference

## Data Fields

- WORD \* [pRXStaticGain](#)
- WORD \* [pRXAIG](#)
- WORD \* [pRXExpThres](#)
- WORD \* [pRXExpSlope](#)
- WORD \* [pRXComprThres](#)
- WORD \* [pRXComprSlope](#)

## 8.633.1 Detailed Description

This structure contains the SLQSGetAudioPathConfig parameters related to AV\_RXAGCLIST.

## Parameters

<i>pRXStaticGain</i>	<ul style="list-style-type: none"> <li>RX pre-compressor static gain</li> </ul>
<i>pRXAIG</i>	<ul style="list-style-type: none"> <li>RX pre-compressor gain selection flag</li> </ul>

<i>pRXExpThres</i>	<ul style="list-style-type: none"> <li>• RX expansion threshold</li> </ul>
<i>pRXExpSlope</i>	<ul style="list-style-type: none"> <li>• RX expansion slope</li> </ul>
<i>pRXComprThres</i>	<ul style="list-style-type: none"> <li>• RX compression threshold</li> </ul>
<i>pRXComprSlope</i>	<ul style="list-style-type: none"> <li>• RX compression slope</li> </ul>

### 8.633.2 Field Documentation

8.633.2.1 **WORD\*** RXAGCList::pRXAIG

8.633.2.2 **WORD\*** RXAGCList::pRXComprSlope

8.633.2.3 **WORD\*** RXAGCList::pRXComprThres

8.633.2.4 **WORD\*** RXAGCList::pRXExpSlope

8.633.2.5 **WORD\*** RXAGCList::pRXExpThres

8.633.2.6 **WORD\*** RXAGCList::pRXStaticGain

## 8.634 RXAVCList Struct Reference

### Data Fields

- **WORD \*** pAVRXAVCSens
- **WORD \*** pAVRXAVCHeadroom

### 8.634.1 Detailed Description

This structure contains the SLQSGetAudioPathConfig parameters related to AV\_RXAVCLIST.

#### Parameters

<i>pAVRXAVC-Sens</i>	<ul style="list-style-type: none"> <li>• AVC variation from nominal sensitivity</li> </ul>
<i>pAVRXAVC-Headroom</i>	<ul style="list-style-type: none"> <li>• AVC headroom</li> </ul>

### 8.634.2 Field Documentation

8.634.2.1 **WORD\*** RXAVCList::pAVRXAVCHeadroom

## 8.634.2.2 WORD\* RXAVCList::pAVRXAVCSens

## 8.635 rxInfo Struct Reference

## Data Fields

- BYTE isRadioTuned
- INT32 rxPower
- INT32 ecio
- INT32 rscp
- INT32 rsrp
- ULONG phase

## 8.635.1 Detailed Description

This structure contains the Rx Information.

## Parameters

<i>isRadioTuned</i>	<ul style="list-style-type: none"> <li>• Whether Rx is tuned to a channel: <ul style="list-style-type: none"> <li>– 0x00 - Not tuned</li> <li>– 0x01 - Tuned</li> <li>– 0xFF - Not Available</li> </ul> </li> <li>• If the radio is tuned, instantaneous values are set for the signal information fields below.</li> <li>• If the radio is not tuned, or is delayed or invalid, the values are set depending on each technology.</li> </ul>
<i>rx_pwr</i>	<ul style="list-style-type: none"> <li>• Rx power value in 1/10 dbm resolution.</li> </ul>
<i>ecio</i>	<ul style="list-style-type: none"> <li>• ECIO in 1/10 dbm; valid for CDMA, HDR, GSM, WCDMA, and LTE.</li> </ul>
<i>rscp</i>	<ul style="list-style-type: none"> <li>• Received signal code power in 1/10 dbm.</li> <li>• Valid for WCDMA.</li> </ul>
<i>rsrp</i>	<ul style="list-style-type: none"> <li>• Current reference signal received power in 1/10 dbm valid for LTE.</li> </ul>
<i>phase</i>	<ul style="list-style-type: none"> <li>• Phase in 1/100 degrees; valid for LTE.</li> <li>• When the phase is unknown, 0xFFFFFFFF is used.</li> </ul>

## 8.635.2 Field Documentation

## 8.635.2.1 INT32 rxInfo::ecio

8.635.2.2 **BYTE** rxInfo::isRadioTuned8.635.2.3 **ULONG** rxInfo::phase8.635.2.4 **INT32** rxInfo::rscp8.635.2.5 **INT32** rxInfo::rsrp8.635.2.6 **INT32** rxInfo::rxPower

## 8.636 RXPCMIIRFitr Struct Reference

### Data Fields

- [WORD](#) \* pFlag
- [WORD](#) \* pStageCnt
- [BYTE](#) \* pStage0Val
- [BYTE](#) \* pStage1Val
- [BYTE](#) \* pStage2Val
- [BYTE](#) \* pStage3Val
- [BYTE](#) \* pStage4Val

### 8.636.1 Detailed Description

This structure contains the SLQSGetAudioPathConfig parameters related to AV\_RXPCMIIRFLTR.

#### Parameters

<i>pFlag</i>	<ul style="list-style-type: none"> <li>• Flag               <ul style="list-style-type: none"> <li>– 0x0000 - IIR filter disable</li> <li>– 0xffff - IIR filter enable</li> </ul> </li> </ul>
<i>pStageCnt</i>	<ul style="list-style-type: none"> <li>• Stage Count               <ul style="list-style-type: none"> <li>– 0-4</li> </ul> </li> </ul>
<i>pStage0Val</i>	<ul style="list-style-type: none"> <li>• A 20 BYTE sized parameter indicating Stage 0 value               <ul style="list-style-type: none"> <li>– A1</li> <li>– A2</li> <li>– B0</li> <li>– B1</li> <li>– B2</li> </ul> </li> </ul>

<i>pStage1Val</i>	<ul style="list-style-type: none"> <li>• A 20 BYTE sized parameter indicating Stage 1 value <ul style="list-style-type: none"> <li>– A1</li> <li>– A2</li> <li>– B0</li> <li>– B1</li> <li>– B2</li> </ul> </li> </ul>
<i>pStage2Val</i>	<ul style="list-style-type: none"> <li>• A 20 BYTE sized parameter indicating Stage 2 value <ul style="list-style-type: none"> <li>– A1</li> <li>– A2</li> <li>– B0</li> <li>– B1</li> <li>– B2</li> </ul> </li> </ul>
<i>pStage3Val</i>	<ul style="list-style-type: none"> <li>• A 20 BYTE sized parameter indicating Stage 3 value <ul style="list-style-type: none"> <li>– A1</li> <li>– A2</li> <li>– B0</li> <li>– B1</li> <li>– B2</li> </ul> </li> </ul>
<i>pStage4Val</i>	<ul style="list-style-type: none"> <li>• A 20 BYTE sized parameter indicating Stage 4 value <ul style="list-style-type: none"> <li>– A1</li> <li>– A2</li> <li>– B0</li> <li>– B1</li> <li>– B2</li> </ul> </li> </ul>

## 8.636.2 Field Documentation

8.636.2.1 WORD\* RXPCMIIRFitr::pFlag

8.636.2.2 BYTE\* RXPCMIIRFitr::pStage0Val

8.636.2.3 BYTE\* RXPCMIIRFitr::pStage1Val

8.636.2.4 BYTE\* RXPCMIIRFitr::pStage2Val

8.636.2.5 BYTE\* RXPCMIIRFitr::pStage3Val

8.636.2.6 **BYTE\*** RXPCMIIRFitr::pStage4Val

8.636.2.7 **WORD\*** RXPCMIIRFitr::pStageCnt

## 8.637 rxSignalStrengthListElement Struct Reference

### Data Fields

- [SHORT rxSignalStrength](#)
- [BYTE radiolf](#)

### 8.637.1 Detailed Description

This structure contains the Received Signal Strength Information

#### Parameters

<i>rxSignalStrength</i>	<ul style="list-style-type: none"> <li>Received signal strength in dBm <ul style="list-style-type: none"> <li>For CDMA and UMTS, this indicates forward link pilotEc.</li> <li>For GSM, the received signal strength.</li> <li>For LTE, this indicates the total received wideband power observed by UE.</li> </ul> </li> </ul>
<i>radiolf</i>	<ul style="list-style-type: none"> <li>Radio interface technology of the signal being radio_if measured <ul style="list-style-type: none"> <li>0x00 - RADIO_IF_NO_SVC - None (no service)</li> <li>0x01 - RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>0x02 - RADIO_IF_CDMA_1XEVD0 - cdma2000 HRPD (1xEV-DO)</li> <li>0x03 - RADIO_IF_AMPS - AMPS</li> <li>0x04 - RADIO_IF_GSM - GSM</li> <li>0x05 - RADIO_IF_UMTS - UMTS</li> <li>0x08 - RADIO_IF_LTE - LTE</li> </ul> </li> </ul>

#### Note

First element of the RSSI list always contains the current Signal strength and Radio Interface.

### 8.637.2 Field Documentation

8.637.2.1 **BYTE** rxSignalStrengthListElement::radiolf

8.637.2.2 **SHORT** rxSignalStrengthListElement::rxSignalStrength

## 8.638 sApnExtraParams Struct Reference

### Data Fields

- [ULONG apnId](#)

- [BYTE ambr\\_ul](#)
- [BYTE ambr\\_dl](#)
- [BYTE ambr\\_ul\\_ext](#)
- [BYTE ambr\\_dl\\_ext](#)
- [BYTE ambr\\_ul\\_ext2](#)
- [BYTE ambr\\_dl\\_ext2](#)

### 8.638.1 Detailed Description

This structure contains the Extra Apn Params

#### Parameters

<i>apnId</i>	<ul style="list-style-type: none"> <li>• APN id</li> <li>• ID identifying the APN that the client would like to query the AMBR params</li> </ul>
<i>ambr_ul</i>	<ul style="list-style-type: none"> <li>• APN AMBR uplink</li> <li>• APN AMBR uplink values from 1 kbps to 8640 kbps</li> </ul>
<i>ambr_dl</i>	<ul style="list-style-type: none"> <li>• APN AMBR downlink</li> <li>• APN AMBR downlink values from 1 kbps to 8640 kbps</li> </ul>
<i>ambr_ul_ext</i>	<ul style="list-style-type: none"> <li>• Extended APN AMBR uplink</li> <li>• APN AMBR uplink values from 8700 kbps to 256 Mbps</li> </ul>
<i>ambr_dl_ext</i>	<ul style="list-style-type: none"> <li>• Extended APN AMBR downlink</li> <li>• APN AMBR downlink values from 8700 kbps to 256 Mbps</li> </ul>
<i>ambr_ul_ext2</i>	<ul style="list-style-type: none"> <li>• Second extended APN AMBR uplink</li> <li>• APN AMBR uplink values from 256 Mbps to 65280 Mbps</li> </ul>
<i>ambr_dl_ext2</i>	<ul style="list-style-type: none"> <li>• Second extended APN AMBR downlink</li> <li>• APN AMBR downlink values from 256 Mbps to 65280 Mbps</li> </ul>

### 8.638.2 Field Documentation

8.638.2.1 **BYTE** sApnExtraParams::ambr\_dl

8.638.2.2 **BYTE** sApnExtraParams::ambr\_dl\_ext

8.638.2.3 **BYTE** sApnExtraParams::ambr\_dl\_ext2



8.638.2.4 **BYTE** sApnExtraParams::ambr\_ul

8.638.2.5 **BYTE** sApnExtraParams::ambr\_ul\_ext

8.638.2.6 **BYTE** sApnExtraParams::ambr\_ul\_ext2

8.638.2.7 **ULONG** sApnExtraParams::apnId

## 8.639 satelliteInfo Struct Reference

### Data Fields

- [BYTE](#) svListLen
- [ULONG](#) validMask
- [ULONG](#) system
- [WORD](#) gnssSvid
- [BYTE](#) healthStatus
- [ULONG](#) svStatus
- [BYTE](#) svInfoMask
- [FLOAT](#) elevation
- [FLOAT](#) azimuth
- [FLOAT](#) snr

### 8.639.1 Detailed Description

Contain fields in struct [satelliteInfo](#)

#### Parameters

<i>svListLen</i>	<ul style="list-style-type: none"><li>• number of sets of the following elements:<ul style="list-style-type: none"><li>– validMask</li><li>– system</li><li>– gnssSvid</li><li>– healthStatus</li><li>– svStatus</li><li>– svInfoMask</li><li>– elevation</li><li>– azimuth</li><li>– snr</li></ul></li></ul>
------------------	---

<i>validMask</i>	<ul style="list-style-type: none"> <li>Bitmask indicating which of the fields in this TLV are valid. Valid bitmasks: <ul style="list-style-type: none"> <li>0x00000001 - VALID_SYSTEM</li> <li>0x00000002 - VALID_GNSS_SVID</li> <li>0x00000004 - VALID_HEALTH_STATUS</li> <li>0x00000008 - VALID_PROCESS_STATUS</li> <li>0x00000010 - VALID_SVINFO_MASK</li> <li>0x00000020 - VALID_ELEVATION</li> <li>0x00000040 - VALID_AZIMUTH</li> <li>0x00000080 - VALID_SNR</li> </ul> </li> </ul>
<i>system</i>	<ul style="list-style-type: none"> <li>Indicates to which constellation this <a href="#">SV</a> belongs. Valid values: <ul style="list-style-type: none"> <li>eQMI_LOC_SV_SYSTEM_GPS (1) - GPS satellite</li> <li>eQMI_LOC_SV_SYSTEM_GALILEO (2) - GALILEO satellite</li> <li>eQMI_LOC_SV_SYSTEM_SBAS (3) - SBAS satellite</li> <li>eQMI_LOC_SV_SYSTEM_COMPASS (4) - COMPASS satellite</li> <li>eQMI_LOC_SV_SYSTEM_GLONASS (5) - GLONASS satellite</li> <li>eQMI_LOC_SV_SYSTEM_BDS (6) - BDS satellite</li> </ul> </li> </ul>
<i>gnssSvId</i>	<ul style="list-style-type: none"> <li>GNSS <a href="#">SV</a> ID. The GPS and GLONASS SVs can be disambiguated using the system field. Range: <ul style="list-style-type: none"> <li>FOR GPS: 1 to 32</li> <li>FOR GLONASS: 1 to 32</li> <li>FOR SBAS: 120 to 151</li> <li>for BDS: 201 to 237</li> </ul> </li> </ul>
<i>healthStatus</i>	<ul style="list-style-type: none"> <li>health status. Range: 0 - 1 <ul style="list-style-type: none"> <li>0 - unhealthy</li> <li>1 - healthy</li> </ul> </li> </ul>
<i>svStatus</i>	<ul style="list-style-type: none"> <li><a href="#">SV</a> process status. Valid values: <ul style="list-style-type: none"> <li>eQMI_LOC_SV_STATUS_IDLE (1) - <a href="#">SV</a> is not being actively processed</li> <li>eQMI_LOC_SV_STATUS_SEARCH (2) - The system is searching for this <a href="#">SV</a></li> <li>eQMI_LOC_SV_STATUS_TRACK (3) - <a href="#">SV</a> is being tracked</li> </ul> </li> </ul>
<i>svInfoMask</i>	<ul style="list-style-type: none"> <li>Indicates whether almanac and ephemeris information is available. Valid bitmasks: <ul style="list-style-type: none"> <li>0x01 - SVINFO_HAS_EPHEMERIS</li> <li>0x02 - SVINFO_HAS_ALMANAC</li> </ul> </li> </ul>
Generated on Tue Jul 12 2016 10:59:49 for LinuxQMI SDK by Doxygen	
<i>elevation</i>	<ul style="list-style-type: none"> <li><a href="#">SV</a> elevation angle. <ul style="list-style-type: none"> <li>Units: Degrees</li> </ul> </li> </ul>

Note

None

### 8.639.2 Field Documentation

8.639.2.1 **FLOAT** satelliteInfo::azimuth

8.639.2.2 **FLOAT** satelliteInfo::elevation

8.639.2.3 **WORD** satelliteInfo::gnssSvId

8.639.2.4 **BYTE** satelliteInfo::healthStatus

8.639.2.5 **FLOAT** satelliteInfo::snr

8.639.2.6 **BYTE** satelliteInfo::svInfoMask

8.639.2.7 **BYTE** satelliteInfo::svListLen

8.639.2.8 **ULONG** satelliteInfo::svStatus

8.639.2.9 **ULONG** satelliteInfo::system

8.639.2.10 **ULONG** satelliteInfo::validMask

## 8.640 sensorData Struct Reference

### Data Fields

- [ULONG timeOfFirstSample](#)
- [BYTE flags](#)
- [BYTE sensorDataLen](#)
- [WORD timeOffset](#) [64]
- [ULONG xAxis](#) [64]
- [ULONG yAxis](#) [64]
- [ULONG zAxis](#) [64]

### 8.640.1 Detailed Description

This structure specifies information regarding the 3-Axis Sensor Data.

#### Parameters

<i>timeOfFirst-Sample</i>	<ul style="list-style-type: none"><li>• Denotes a full 32-bit time stamp of the first (oldest) sample in this message.</li><li>• The time stamp is in the time reference scale that is used by the sensor time source.</li><li>• Units - Milliseconds</li></ul>
---------------------------	---

<i>flags</i>	<ul style="list-style-type: none"> <li>• Flags to indicate any deviation from the default measurement assumptions.</li> <li>• All unused bits in this field must be set to 0.</li> <li>• Valid bitmasks <ul style="list-style-type: none"> <li>– 0x01 - Bitmask to specify that a sign reversal is required while interpreting the sensor data; only applies to the accelerometer samples</li> <li>– 0x02 - Bitmask to specify that the sensor time stamp is the same as the modem time stamp</li> </ul> </li> </ul>
<i>sensorDataLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements <ul style="list-style-type: none"> <li>– timeOffset</li> <li>– xAxis</li> <li>– yAxis</li> <li>– zAxis</li> </ul> </li> </ul>
<i>timeOffset</i>	<ul style="list-style-type: none"> <li>• Sample time offset</li> <li>• Units - Milliseconds</li> </ul>
<i>xAxis</i>	<ul style="list-style-type: none"> <li>• Sensor x-axis sample.</li> <li>• Units Accelerometer - Meters/seconds square</li> <li>• Units Gyroscope - Radians/second</li> </ul>
<i>yAxis</i>	<ul style="list-style-type: none"> <li>• Sensor Y-axis sample.</li> <li>• Units Accelerometer - Meters/seconds square</li> <li>• Units Gyroscope - Radians/second</li> </ul>
<i>zAxis</i>	<ul style="list-style-type: none"> <li>• Sensor Z-axis sample.</li> <li>• Units Accelerometer - Meters/seconds square</li> <li>• Units Gyroscope - Radians/second</li> </ul>

## 8.640.2 Field Documentation

### 8.640.2.1 BYTE sensorData::flags

### 8.640.2.2 BYTE sensorData::sensorDataLen

### 8.640.2.3 ULONG sensorData::timeOfFirstSample

8.640.2.4 WORD sensorData::timeOffset[64]

8.640.2.5 ULONG sensorData::xAxis[64]

8.640.2.6 ULONG sensorData::yAxis[64]

8.640.2.7 ULONG sensorData::zAxis[64]

## 8.641 sensorDataUsage\_s Struct Reference

### Data Fields

- [ULONG usageMask](#)
- [ULONG aidingIndicatorMask](#)

### 8.641.1 Detailed Description

This structure contains Sensor Data Usage info.

#### Parameters

<i>usageMask</i>	<ul style="list-style-type: none"> <li>• Specifies which sensors were used in calculating the position in the position report.</li> </ul>
------------------	---

- Value
  - 0x00000001 - Accelerometer used
  - 0x00000002 - Gyroscope used

#### Parameters

<i>aidingIndicatorMask</i>	
----------------------------	--

- Specifies which results were aided by sensors.

- Value
  - 0x00000001 - AIDED\_HEADING
  - 0x00000002 - AIDED\_SPEED
  - 0x00000004 - AIDED\_POSITION
  - 0x00000008 - AIDED\_VELOCITY

### 8.641.2 Field Documentation

8.641.2.1 ULONG sensorDataUsage\_s::aidingIndicatorMask

8.641.2.2 ULONG sensorDataUsage\_s::usageMask

## 8.642 serialNumbersInfo Struct Reference

### Data Fields

- [BYTE esnSize](#)

- [CHAR \\* pESNString](#)
- [BYTE imeiSize](#)
- [CHAR \\* pIMEIString](#)
- [BYTE meidSize](#)
- [CHAR \\* pMEIDString](#)
- [BYTE imeiSvnSize](#)
- [CHAR \\* plmeiSvnString](#)

### 8.642.1 Detailed Description

Returns all the serial numbers assigned to the device. These serial numbers include the ESN (Electronic serial number of the device), the IMEI (International Mobile Equipment Identity) and MEID (Mobile Equipment Identifier).

#### Parameters

<i>esnSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the ESN string array can contain</li> </ul>
<i>pESNString[OUT]</i>	<ul style="list-style-type: none"> <li>• NULL-terminated ESN string. Empty string is returned when ESN is not supported/programmed</li> </ul>
<i>imeiSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the IMEI string array can contain</li> </ul>
<i>pIMEIString[OUT]</i>	<ul style="list-style-type: none"> <li>• NULL terminated IMEI string. Empty string is returned when IMEI is not supported/programmed</li> </ul>
<i>meidSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the MEID string array can contain</li> </ul>
<i>pMEIDString[OUT]</i>	<ul style="list-style-type: none"> <li>• NULL-terminated MEID string. Empty string is returned when MEID is not supported/programmed</li> </ul>
<i>imeiSvnSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the IMEI SVN string array can contain.</li> </ul>
<i>plmeiSvnString[OUT]</i>	<ul style="list-style-type: none"> <li>• NULL-terminated IMEI SVN string. Empty string is returned when IMEI SVN is not supported/programmed.</li> </ul>

### 8.642.2 Field Documentation

8.642.2.1 **BYTE** serialNumbersInfo::esnSize

8.642.2.2 **BYTE** serialNumbersInfo::imeiSize

8.642.2.3 **BYTE** serialNumbersInfo::imeiSvnSize

8.642.2.4 **BYTE** serialNumbersInfo::meidSize

8.642.2.5 **CHAR\*** serialNumbersInfo::pESNString

8.642.2.6 **CHAR\*** serialNumbersInfo::pIMEIString

8.642.2.7 **CHAR\*** serialNumbersInfo::pImeiSvnString

8.642.2.8 **CHAR\*** serialNumbersInfo::pMEIDString

## 8.643 serviceProviderName Struct Reference

### Data Fields

- [BYTE displayCondition](#)
- [BYTE spnLength](#)
- [BYTE spn \[255\]](#)

### 8.643.1 Detailed Description

This structure contains Service Provider Name as defined in 3GPP TS 31.102 (Section 4.2.12) from multiple sources.

#### Parameters

<i>displayCondition</i>	<ul style="list-style-type: none"> <li>• Display condition.</li> </ul>
<i>spnLength</i>	<ul style="list-style-type: none"> <li>• It provides length of spn.</li> </ul>
<i>spn</i>	<ul style="list-style-type: none"> <li>• Service provider name string must use: The SMS default 7-bit coded alphabet as defined in 3GPP TS 23.038 with bit 8 set to 9.</li> </ul>

### 8.643.2 Field Documentation

8.643.2.1 **BYTE** serviceProviderName::displayCondition

8.643.2.2 **BYTE** serviceProviderName::spn[255]

8.643.2.3 **BYTE** serviceProviderName::spnLength

## 8.644 ServingSystemInfo Struct Reference

### Data Fields

- [BYTE registrationState](#)
- [BYTE csAttachState](#)
- [BYTE psAttachState](#)

- [BYTE selectedNetwork](#)
- [BYTE radiolInterfaceNo](#)
- [BYTE radiolInterfaceList](#) [255]
- [BYTE hdrPersonality](#)

### 8.644.1 Detailed Description

This structure will hold the serving system parameters information

#### Parameters

<i>registrationState</i>	- Registration state of the mobile <ul style="list-style-type: none"> <li>• 0 - QMI_NAS_NOT_REGISTERED Not registered;mobile is not currently searching for a new network to provide service</li> <li>• 1 - QMI_NAS_REGISTERED Registered with a network</li> <li>• 2 - QMI_NAS_NOT_REGISTERED_SEARCHING Not registered, but mobile is currently searching for a new network to provide service</li> <li>• 3 - QMI_NAS_REGISTRATION_DENIED Registration denied by the visible network</li> <li>• 4 - QMI_NAS_REGISTRATION_UNKNOWN Registration state is unknown</li> </ul>
<i>csAttachState</i>	- Circuit Switch domain attach state of the mobile <ul style="list-style-type: none"> <li>• 0 - Unknown or not applicable</li> <li>• 1 - Attached</li> <li>• 2 - Detached</li> </ul>
<i>psAttachState</i>	- Packet domain attach state of the mobile <ul style="list-style-type: none"> <li>• 0 - Unknown or not applicable</li> <li>• 1 - Attached</li> <li>• 2 - Detached</li> </ul>
<i>selectedNetwork</i>	- Type of selected radio access network <ul style="list-style-type: none"> <li>• 0x00 - Unknown</li> <li>• 0x01 - 3GPP2 network</li> <li>• 0x02 - 3GPP network</li> </ul>



<i>radioInterfaceNo</i>	- Number of radio interfaces currently in use; this indicates how many radio_if identifiers follow this field
<i>radioInterface-List</i>	- Radio interface currently in use (each is 1 byte) <ul style="list-style-type: none"> <li>• 0x00 - None (no service)</li> <li>• 0x01 - cdma2000 1X</li> <li>• 0x02 - cdma2000 HRPD (1xEV-DO)</li> <li>• 0x03 - AMPS</li> <li>• 0x04 - GSM</li> <li>• 0x05 - UMTS</li> <li>• 0x08 - LTE</li> </ul>
<i>hdrPersonality</i>	- HDR personality information (valid only for EVDO) <ul style="list-style-type: none"> <li>• 0x00 - Unknown</li> <li>• 0x01 - HRPD</li> <li>• 0x02 - eHRPD</li> </ul>

Note: None

## 8.644.2 Field Documentation

8.644.2.1 **BYTE** ServingSystemInfo::csAttachState

8.644.2.2 **BYTE** ServingSystemInfo::hdrPersonality

8.644.2.3 **BYTE** ServingSystemInfo::psAttachState

8.644.2.4 **BYTE** ServingSystemInfo::radioInterfaceList[255]

8.644.2.5 **BYTE** ServingSystemInfo::radioInterfaceNo

8.644.2.6 **BYTE** ServingSystemInfo::registrationState

8.644.2.7 **BYTE** ServingSystemInfo::selectedNetwork

## 8.645 servSystem Struct Reference

### Data Fields

- [BYTE regState](#)
- [BYTE csAttachState](#)
- [BYTE psAttachState](#)
- [BYTE selNetwork](#)
- [BYTE numRadioInterfaces](#)
- [BYTE radioInterface](#) [0x0A]

### 8.645.1 Detailed Description

This structure contains the Serving System parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>regState</i>	<ul style="list-style-type: none"> <li>• Registration state - Registration state of the mobile</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Not Registered; mobile is not currently searching for a new network to provide service</li> <li>– 1 - Registered with a network</li> <li>– 2 - Not registered, but mobile is currently searching for a new network to provide service</li> <li>– 3 - Registration denied by visible network</li> <li>– 4 - Registration state is unknown</li> </ul> </li> </ul>
<i>csAttachState</i>	<ul style="list-style-type: none"> <li>• CS Attach State - Circuit-switched domain attach state of the mobile</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Unknown or not applicable</li> <li>– 1 - Attached</li> <li>– 2 - Detached</li> </ul> </li> </ul>
<i>psAttachState</i>	<ul style="list-style-type: none"> <li>• PS Attach State - Packet-switched domain attach state of the mobile</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Unknown or not applicable</li> <li>– 1 - Attached</li> <li>– 2 - Detached</li> </ul> </li> </ul>
<i>selNetwork</i>	<ul style="list-style-type: none"> <li>• Selected Network - Type of selected radio access network</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - 3GPP2 network</li> <li>– 2 - 3GPP network</li> </ul> </li> </ul>

<i>numRadio-Interfaces</i>	<ul style="list-style-type: none"> <li>• In Use Radio Interfaces Number <ul style="list-style-type: none"> <li>– Number of radio interfaces currently in use</li> <li>– defaults to zero</li> </ul> </li> </ul>
<i>radioInterface</i>	<ul style="list-style-type: none"> <li>• Radio Interface(s) modem discovered</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - RADIO_IF_NO_SVC - None(no service)</li> <li>– 0x01 - RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - RADIO_IF_CDMA_1XEVD0 - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x03 - RADIO_IF_AMPS - AMPS</li> <li>– 0x04 - RADIO_IF_GSM - GSM</li> <li>– 0x05 - RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - RADIO_IF_LTE - LTE</li> </ul> </li> </ul>

## 8.645.2 Field Documentation

8.645.2.1 **BYTE** servSystem::csAttachState

8.645.2.2 **BYTE** servSystem::numRadioInterfaces

8.645.2.3 **BYTE** servSystem::psAttachState

8.645.2.4 **BYTE** servSystem::radioInterface[0x0A]

8.645.2.5 **BYTE** servSystem::regState

8.645.2.6 **BYTE** servSystem::selNetwork

## 8.646 sessionInfo Union Reference

### Data Fields

- struct [omaDmFotaTlv](#) [omaDmFota](#)
- struct [omaDmConfigTlv](#) [omaDmConfig](#)
- struct [omaDmNotificationsTlv](#) [omaDmNotifications](#)

### 8.646.1 Detailed Description

This union [sessionInfo](#) consist of [omaDmFotaTlv](#), [omaDmConfigTlv](#) and [omaDmNotificationsTlv](#), out of which one will be unpacked against pEventFields.

### 8.646.2 Field Documentation

8.646.2.1 **struct** [omaDmConfigTlv](#) sessionInfo::omaDmConfig

8.646.2.2 struct **omaDmFotaTlv** sessionInfo::omaDmFota

8.646.2.3 struct **omaDmNotificationsTlv** sessionInfo::omaDmNotifications

## 8.647 sessionInfoExt Union Reference

### Data Fields

- struct [omaDmFotaTlvExt](#) omaDmFota
- struct [omaDmConfigTlvExt](#) omaDmConfig

### 8.647.1 Detailed Description

This union [sessionInfo](#) consist of [omaDmFotaTlv](#) and [omaDmConfigTlv](#), out of which one will be unpacked against pEventFields.

### 8.647.2 Field Documentation

8.647.2.1 struct **omaDmConfigTlvExt** sessionInfoExt::omaDmConfig

8.647.2.2 struct **omaDmFotaTlvExt** sessionInfoExt::omaDmFota

## 8.648 sessionInfoTlv Struct Reference

### Data Fields

- [BYTE](#) TlvPresent
- [ULONG](#) sessionType
- [sessionInformation](#) sessionInfo

### 8.648.1 Detailed Description

Structure used to store all [sessionInfo\(Union\)](#)TLV Value.

#### Parameters

<i>TlvPresent</i>	- Boolean indicating the presence of the TLV in the QMI response
<i>sessionType</i>	- sessiontype Value

### 8.648.2 Field Documentation

8.648.2.1 **sessionInformation** sessionInfoTlv::sessionInfo

8.648.2.2 **ULONG** sessionInfoTlv::sessionType

8.648.2.3 **BYTE** sessionInfoTlv::TlvPresent

## 8.649 sessionInfoTlvExt Struct Reference

### Data Fields

- [BYTE](#) TlvPresent

- [ULONG sessionType](#)
- [sessionInformationExt sessionInfo](#)

### 8.649.1 Detailed Description

Structure used to store all [sessionInfo\(Union\)](#)TLV Value.

Parameters

<i>TlvPresent</i>	- Boolean indicating the presence of the TLV in the QMI response
<i>sessionType</i>	- sessiontype Value

### 8.649.2 Field Documentation

8.649.2.1 [sessionInformationExt sessionInfoTlvExt::sessionInfo](#)

8.649.2.2 [ULONG sessionInfoTlvExt::sessionType](#)

8.649.2.3 [BYTE sessionInfoTlvExt::TlvPresent](#)

## 8.650 SetAudioPathConfigReq Struct Reference

Data Fields

- [BYTE Profile](#)
- [BYTE \\* pECMode](#)
- [BYTE \\* pNSEnable](#)
- [WORD \\* pTXGain](#)
- [WORD \\* pDTMF\\_TXGain](#)
- [WORD \\* pCodecSTGain](#)
- [TXPCMIIRFiltr \\* pTXPCMIIRFiltr](#)
- [RXPCMIIRFiltr \\* pRXPCMIIRFiltr](#)
- [BYTE \\* pRXAVCAGCSwitch](#)
- [BYTE \\* pTXAVCSwitch](#)
- [RXAGCList \\* pRXAGCList](#)
- [RXAVCList \\* pRXAVCList](#)
- [TXAGCList \\* pTXAGCList](#)

### 8.650.1 Detailed Description

This structure contains the SLQSSetAudioPathConfig request parameters.

Parameters

<i>Profile</i>	[Mandatory] <ul style="list-style-type: none"><li>• Audio Profile<ul style="list-style-type: none"><li>– 0-9</li></ul></li></ul>
----------------	--

<i>pECMode</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_EC             <ul style="list-style-type: none"> <li>– 0 - Echo cancellation off</li> <li>– 1 - Handset echo mode</li> <li>– 2 - Headset mode</li> <li>– 3 - Car kit mode</li> <li>– 4 - Speaker Mode</li> </ul> </li> </ul>
<i>pNSEnable</i>	[Optional] <ul style="list-style-type: none"> <li>• Noise Suppression             <ul style="list-style-type: none"> <li>– 0 - Noise suppression off</li> <li>– 1 - Noise suppression on</li> </ul> </li> </ul>
<i>pTXGain</i>	[Optional] <ul style="list-style-type: none"> <li>• TX Voice volume             <ul style="list-style-type: none"> <li>– 0x0000 - 0xffff</li> </ul> </li> </ul>
<i>pDTMFTXGain</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_DTMFTXG             <ul style="list-style-type: none"> <li>– 0x0000 - 0xffff</li> </ul> </li> </ul>
<i>pCodecSTGain</i>	[Optional] <ul style="list-style-type: none"> <li>• AV_CODEECSTG             <ul style="list-style-type: none"> <li>– 0x0000 - 0xffff</li> </ul> </li> </ul>
<i>pTXPCMIIRFtr</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">TXPCMIIRFtr</a> for more information</li> </ul>
<i>pRXPCMIIRFtr</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">RXPCMIIRFtr</a> for more information</li> </ul>
<i>pRXAVCAGC-Switch</i>	[Optional] <ul style="list-style-type: none"> <li>• RX AVC/AGC Switch</li> </ul>
<i>pTXAVCSwitch</i>	[Optional] <ul style="list-style-type: none"> <li>• TX AVC Switch</li> </ul>
<i>pRXAGCList</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">RXAGCList</a> for more information</li> </ul>

<i>pRXAVCList</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">RXAVCList</a> for more information</li> </ul>
<i>pTXAGCList</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">TXAGCList</a> for more information</li> </ul>

## 8.650.2 Field Documentation

8.650.2.1 **WORD\*** SetAudioPathConfigReq::pCodecSTGain

8.650.2.2 **WORD\*** SetAudioPathConfigReq::pDTMFTXGain

8.650.2.3 **BYTE\*** SetAudioPathConfigReq::pECMode

8.650.2.4 **BYTE\*** SetAudioPathConfigReq::pNSEnable

8.650.2.5 **BYTE** SetAudioPathConfigReq::Profile

8.650.2.6 **RXAGCList\*** SetAudioPathConfigReq::pRXAGCList

8.650.2.7 **BYTE\*** SetAudioPathConfigReq::pRXAVCAGCSwitch

8.650.2.8 **RXAVCList\*** SetAudioPathConfigReq::pRXAVCList

8.650.2.9 **RXPCMIIRFiltr\*** SetAudioPathConfigReq::pRXPCMIIRFiltr

8.650.2.10 **TXAGCList\*** SetAudioPathConfigReq::pTXAGCList

8.650.2.11 **BYTE\*** SetAudioPathConfigReq::pTXAVCSwitch

8.650.2.12 **WORD\*** SetAudioPathConfigReq::pTXGain

8.650.2.13 **TXPCMIIRFiltr\*** SetAudioPathConfigReq::pTXPCMIIRFiltr

## 8.651 SetAudioProfileReq Struct Reference

### Data Fields

- [BYTE](#) Profile
- [BYTE](#) EarMute
- [BYTE](#) MicMute
- [BYTE](#) Generator
- [BYTE](#) Volume

### 8.651.1 Detailed Description

This structure contains the SLQSSetAudioProfile request parameters.

## Parameters

<i>Profile</i>	<ul style="list-style-type: none"><li>• Audio Profile<ul style="list-style-type: none"><li>– 0 - Handset</li><li>– 1 - Headset</li><li>– 2 - Car Kit</li><li>– 3 - Speaker phone</li><li>– 4 - Auxiliary</li><li>– 5 - TTY</li><li>– 6 - Auxiliary external PCM</li><li>– 7 - Primary external PCM</li><li>– 8 - External slave PCM</li><li>– 9 - I2S</li></ul></li></ul>
<i>EarMute</i>	<ul style="list-style-type: none"><li>• Ear Mute Setting<ul style="list-style-type: none"><li>– 0 - unmuted</li><li>– 1 - muted</li></ul></li></ul>
<i>MicMute</i>	<ul style="list-style-type: none"><li>• MIC Mute Setting<ul style="list-style-type: none"><li>– 0 - unmuted</li><li>– 1 - muted</li></ul></li></ul>
<i>Generator</i>	<ul style="list-style-type: none"><li>• Audio Generator<ul style="list-style-type: none"><li>– 0 - Voice</li><li>– 1 - Key Beep</li><li>– 2 - MIDI</li></ul></li></ul>
<i>Volume</i>	<ul style="list-style-type: none"><li>• Audio Volume Level<ul style="list-style-type: none"><li>– 0 to 7</li></ul></li></ul>



## 8.651.2 Field Documentation

8.651.2.1 **BYTE** SetAudioProfileReq::EarMute

8.651.2.2 **BYTE** SetAudioProfileReq::Generator

8.651.2.3 **BYTE** SetAudioProfileReq::MicMute

8.651.2.4 **BYTE** SetAudioProfileReq::Profile

8.651.2.5 **BYTE** SetAudioProfileReq::Volume

## 8.652 SetAudioVolTLBConfigReq Struct Reference

### Data Fields

- [BYTE Profile](#)
- [BYTE Generator](#)
- [BYTE Volume](#)
- [BYTE Item](#)
- [WORD VolValue](#)

### 8.652.1 Detailed Description

This structure contains the SLQSSetAudioVolTLBConfig request parameters

#### Parameters

<i>Profile</i>	<ul style="list-style-type: none"><li>• Audio Profile<ul style="list-style-type: none"><li>– 0-9</li></ul></li></ul>
<i>Generator</i>	<ul style="list-style-type: none"><li>• Audio Generator<ul style="list-style-type: none"><li>– 0-2</li></ul></li></ul>
<i>Volume</i>	<ul style="list-style-type: none"><li>• Audio Volume Level<ul style="list-style-type: none"><li>– 0-7</li></ul></li></ul>

<i>Item</i>	<ul style="list-style-type: none"> <li>• Item <ul style="list-style-type: none"> <li>– 13 - AV_RXVOLDB</li> <li>– 14 - AV_DTMFVOLDB</li> <li>– 15 - AV_PAD</li> </ul> </li> </ul>
<i>Value</i>	<ul style="list-style-type: none"> <li>• Value to be set to the volume table</li> </ul>

### 8.652.2 Field Documentation

8.652.2.1 **BYTE** SetAudioVolTLBConfigReq::Generator

8.652.2.2 **BYTE** SetAudioVolTLBConfigReq::Item

8.652.2.3 **BYTE** SetAudioVolTLBConfigReq::Profile

8.652.2.4 **BYTE** SetAudioVolTLBConfigReq::Volume

8.652.2.5 **WORD** SetAudioVolTLBConfigReq::VolValue

## 8.653 SetAudioVolTLBConfigResp Struct Reference

### Data Fields

- [WORD ResCode](#)

### 8.653.1 Detailed Description

This structure contains the SLQSSetAudioVolTLBConfig response parameters.

#### Parameters

<i>ResCode</i>	<ul style="list-style-type: none"> <li>• Result of requested item</li> </ul>
----------------	--

### 8.653.2 Field Documentation

8.653.2.1 **WORD** SetAudioVolTLBConfigResp::ResCode

## 8.654 setCustomSettingV2 Struct Reference

### Data Fields

- [CHAR cust\\_id](#) [64+1]
- [WORD value\\_length](#)
- [BYTE cust\\_value](#) [8+1]

### 8.654.1 Detailed Description

This structure contains customization settings set to modem

## Parameters

<i>cust_id[IN]</i>	<ul style="list-style-type: none"> <li>Customization ID (Maximum 64 bytes)</li> </ul>
<i>value_length[IN]</i>	<ul style="list-style-type: none"> <li>length of cust_value field</li> </ul>
<i>cust_value[IN]</i>	<ul style="list-style-type: none"> <li>Customization Setting Value (Maximum 8 bytes)</li> </ul>

## 8.654.2 Field Documentation

8.654.2.1 CHAR setCustomSettingV2::cust\_id[64+1]

8.654.2.2 BYTE setCustomSettingV2::cust\_value[8+1]

8.654.2.3 WORD setCustomSettingV2::value\_length

## 8.655 setDyingGaspCfg Struct Reference

## Data Fields

- [BYTE](#) \* [pDestSMSNum](#)
- [BYTE](#) \* [pDestSMSContent](#)

## 8.655.1 Detailed Description

This struture contains the TLV required to get the Dying GASP Config.

## Parameters

<i>OUT]</i>	<p>pDestSMSNum[OUT]</p> <ul style="list-style-type: none"> <li>SMS Destination Number as string of 8 bit ASCII Characters Max 20 chars.</li> <li>Optional parameter.</li> </ul>
<i>OUT]</i>	<p>pDestSMSContent[OUT]</p> <ul style="list-style-type: none"> <li>SMS COnent as a string of 8 bit ASCII text characters Max 160 chars.</li> <li>Optional parameter.</li> </ul>

## 8.655.2 Field Documentation

8.655.2.1 BYTE\* setDyingGaspCfg::pDestSMSContent

8.655.2.2 BYTE\* setDyingGaspCfg::pDestSMSNum

## 8.656 SetIMSSMSConfigReq Struct Reference

## Data Fields

- [BYTE](#) \* [pSMSFormat](#)
- [BYTE](#) \* [pSMSOverIPNwInd](#)
- [BYTE](#) \* [pPhoneCtxtURLen](#)
- [BYTE](#) \* [pPhoneCtxtURI](#)

## 8.656.1 Detailed Description

This structure contains the SLQSSetIMSSMSConfig request parameters.

## Parameters

<i>pSMSFormat</i>	<ul style="list-style-type: none"> <li>• SMS format <ul style="list-style-type: none"> <li>– 0 - 3GPP</li> <li>– 1 - 3GPP2</li> </ul> </li> </ul>
<i>pSMSOverIPNwInd</i>	<ul style="list-style-type: none"> <li>• SMS over IP Network Indication Flag <ul style="list-style-type: none"> <li>– TRUE - Turn on mobile-originated SMS</li> <li>– FALSE - Turn off mobile-originated SMS</li> </ul> </li> </ul>
<i>pPhoneCtxtURLen</i>	<ul style="list-style-type: none"> <li>• Length of Phone context Universal Resource Identifier to follow</li> </ul>
<i>pPhoneCtxtURI</i>	<ul style="list-style-type: none"> <li>• Phone context universal resource identifier</li> <li>• Length of this string must be specified in pPhoneCtxtURLen parameter</li> </ul>

## 8.656.2 Field Documentation

8.656.2.1 [BYTE](#)\* SetIMSSMSConfigReq::pPhoneCtxtURI

8.656.2.2 [BYTE](#)\* SetIMSSMSConfigReq::pPhoneCtxtURLen

8.656.2.3 [BYTE](#)\* SetIMSSMSConfigReq::pSMSFormat

8.656.2.4 [BYTE](#)\* SetIMSSMSConfigReq::pSMSOverIPNwInd

## 8.657 SetIMSSMSConfigResp Struct Reference

## Data Fields

- [BYTE](#) \* [pSettingResp](#)

## 8.657.1 Detailed Description

This structure contains the SLQSSetIMSSMSConfig response parameters.

## Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"> <li>Settings standard response type. A settings specific error code is returned when the standard response error type is QMI_ERR_CAUSE_CODE</li> </ul>
---------------------	---

## 8.657.2 Field Documentation

8.657.2.1 BYTE\* SetIMSSMSConfigResp::pSettingResp

## 8.658 SetIMSUserConfigReq Struct Reference

## Data Fields

- BYTE \* [pIMSDomainLen](#)
- BYTE \* [pIMSDomain](#)

## 8.658.1 Detailed Description

This structure contains the SLQSSetIMSUserConfig request parameters.

## Parameters

<i>pIMSDomainLen</i>	<ul style="list-style-type: none"> <li>Length of IMS <a href="#">Domain</a> Name to follow</li> </ul>
<i>pIMSDomain</i>	<ul style="list-style-type: none"> <li>IMS domain name</li> </ul>

## 8.658.2 Field Documentation

8.658.2.1 BYTE\* SetIMSUserConfigReq::pIMSDomain

8.658.2.2 BYTE\* SetIMSUserConfigReq::pIMSDomainLen

## 8.659 SetIMSUserConfigResp Struct Reference

## Data Fields

- BYTE \* [pSettingResp](#)

## 8.659.1 Detailed Description

This structure contains the SLQSSetIMSUserConfig response parameters.

## Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"><li>• Settings standard response type. A settings specific error code is returned when the standard response error type is QMI_ERR_CAUSE_CODE</li></ul>
---------------------	---

## 8.659.2 Field Documentation

### 8.659.2.1 BYTE\* SetIMSUserConfigResp::pSettingResp

## 8.660 SetIMSVoIPConfigReq Struct Reference

### Data Fields

- WORD \* pSessionExpiryTimer
- WORD \* pMinSessionExpiryTimer
- BYTE \* pAmrWbEnable
- BYTE \* pScrAmrEnable
- BYTE \* pScrAmrWbEnable
- BYTE \* pAmrMode
- WORD \* pAmrWBMode
- BYTE \* pAmrOctetAligned
- BYTE \* pAmrWBOctetAligned
- WORD \* pRingingTimer
- WORD \* pRingBackTimer
- WORD \* pRTPRTCPInactTimer

### 8.660.1 Detailed Description

This structure contains the SLQSSetIMSVoIPConfig request parameters.

#### Parameters

<i>pSessionExpiryTimer</i>	<ul style="list-style-type: none"><li>• Session duration, in seconds</li></ul>
<i>pMinSessionExpiryTimer</i>	<ul style="list-style-type: none"><li>• Minimum allowed value for session expiry timer, in seconds</li></ul>
<i>pAmrWbEnable</i>	<ul style="list-style-type: none"><li>• Flag to enable/disable Adaptive Multirate Codec(AMR) WideBand(WB) audio</li><li>• Values:<ul style="list-style-type: none"><li>– True - Enable</li><li>– False - Disable</li></ul></li></ul>

<i>pScrAmrEnable</i>	<ul style="list-style-type: none"> <li>• Flag to enable/disable Source Control Rate(SCR) for AMR NarrowBand (NB)</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Enable</li> <li>– False - Disable</li> </ul> </li> </ul>
<i>pScrAmrWb-Enable</i>	<ul style="list-style-type: none"> <li>• Flag to enable/disable SCR for AMR WB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Enable</li> <li>– False - Disable</li> </ul> </li> </ul>
<i>pAmrMode</i>	<ul style="list-style-type: none"> <li>• BitMask for AMR NB modes allowed</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x1 - 4.75 kbps</li> <li>– 0x2 - 5.15 kbps</li> <li>– 0x4 - 5.9 kbps</li> <li>– 0x8 - 6.17 kbps</li> <li>– 0x10 - 7.4 kbps</li> <li>– 0x20 - 7.95 kbps</li> <li>– 0x40 - 10.2 kbps</li> <li>– 0x80 - 12.2 kbps</li> </ul> </li> </ul>
<i>pAmrWBMode</i>	<ul style="list-style-type: none"> <li>• BitMask for AMR WB modes allowed</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x1 - 6.60 kbps</li> <li>– 0x2 - 8.85 kbps</li> <li>– 0x4 - 12.65 kbps</li> <li>– 0x8 - 14.25 kbps</li> <li>– 0x10 - 15.85 kbps</li> <li>– 0x20 - 18.25 kbps</li> <li>– 0x40 - 19.85 kbps</li> <li>– 0x80 - 23.05 kbps</li> <li>– 0x100 - 23.85 kbps</li> </ul> </li> </ul>



<i>pAmrOctet-Aligned</i>	<ul style="list-style-type: none"> <li>• Flag to indicate if the octet is aligned for AMR NB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Aligned</li> <li>– False - Not aligned, Bandwidth Efficient mode</li> </ul> </li> </ul>
<i>pAmrWBOctet-Aligned</i>	<ul style="list-style-type: none"> <li>• Flag to indicate if the octet is aligned for AMR WB Audio</li> <li>• Values: <ul style="list-style-type: none"> <li>– True - Aligned</li> <li>– False - Not aligned, Bandwidth Efficient mode</li> </ul> </li> </ul>
<i>pRingingTimer</i>	<ul style="list-style-type: none"> <li>• Duration of ringing timer, in seconds. The ringing timer starts on the ringing event. If the call is not answered within the duration of this timer, the call is disconnected.</li> </ul>
<i>pRingBackTimer</i>	<ul style="list-style-type: none"> <li>• Duration of ringback timer, in seconds. The ringback timer starts on the ringback event. If the call is not answered within the duration of this timer, the call is disconnected.</li> </ul>
<i>pRTPRTCP-InactTimer</i>	<ul style="list-style-type: none"> <li>• Duration of RTP/RTCP inactivity timer, in seconds. If no RTP/RTCP packet is received prior to the expiry of this timer, the call is disconnected.</li> </ul>

## 8.660.2 Field Documentation

8.660.2.1 **BYTE\*** SetIMSVoIPConfigReq::pAmrMode

8.660.2.2 **BYTE\*** SetIMSVoIPConfigReq::pAmrOctetAligned

8.660.2.3 **BYTE\*** SetIMSVoIPConfigReq::pAmrWbEnable

8.660.2.4 **WORD\*** SetIMSVoIPConfigReq::pAmrWBMode

8.660.2.5 **BYTE\*** SetIMSVoIPConfigReq::pAmrWBOctetAligned

8.660.2.6 **WORD\*** SetIMSVoIPConfigReq::pMinSessionExpiryTimer

8.660.2.7 **WORD\*** SetIMSVoIPConfigReq::pRingBackTimer

8.660.2.8 **WORD\*** SetIMSVoIPConfigReq::pRingingTimer

8.660.2.9 **WORD\*** SetIMSVoIPConfigReq::pRTPRTCPInactTimer

8.660.2.10 **BYTE\*** SetIMSVoIPConfigReq::pScrAmrEnable

8.660.2.11 **BYTE\*** SetIMSVoIPConfigReq::pScrAmrWbEnable

8.660.2.12 WORD\* SetIMSVoIPConfigReq::pSessionExpiryTimer

## 8.661 SetIMSVoIPConfigResp Struct Reference

### Data Fields

- [BYTE](#) \* [pSettingResp](#)

### 8.661.1 Detailed Description

This structure contains the SLQSSetIMSVoIPConfig response parameters.

#### Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"> <li>• Settings standard response type. A settings specific error code is returned when the standard response error type is QMI_ERR_CAUSE_CODE</li> </ul>
---------------------	---

### 8.661.2 Field Documentation

8.661.2.1 [BYTE](#)\* SetIMSVoIPConfigResp::pSettingResp

## 8.662 SetM2MAudioAVCFGReq Struct Reference

### Data Fields

- [BYTE](#) Profile
- [BYTE](#) Device
- [BYTE](#) PIFACEId
- [PCMparams](#) \* [pPCMParams](#)

### 8.662.1 Detailed Description

This structure contains the SLQSSetM2MAudioAVCFG request parameters.

#### Parameters

<i>Profile</i>	<ul style="list-style-type: none"> <li>• Audio Profile <ul style="list-style-type: none"> <li>– 0-5</li> </ul> </li> </ul>
<i>Device</i>	<ul style="list-style-type: none"> <li>• ACDB Device</li> <li>• See <a href="#">qaGobiApiTableSwiAudio.h</a> for more information on ACDB Device</li> </ul>

<i>PIFACEId</i>	<ul style="list-style-type: none"> <li>Physical Interface</li> <li>See <a href="#">qaGobiApiTableSwiAudio.h</a> for more information on physical interface</li> </ul>
<i>pPCMPParams</i>	<ul style="list-style-type: none"> <li>PCM parameters</li> <li>See <a href="#">PCMparams</a> for more information</li> </ul>

### 8.662.2 Field Documentation

8.662.2.1 BYTE SetM2MAudioAVCFGReq::Device

8.662.2.2 BYTE SetM2MAudioAVCFGReq::PIFACEId

8.662.2.3 PCMparams\* SetM2MAudioAVCFGReq::pPCMPParams

8.662.2.4 BYTE SetM2MAudioAVCFGReq::Profile

## 8.663 SetM2MAudioLPBKReq Struct Reference

### Data Fields

- [BYTE Enable](#)

### 8.663.1 Detailed Description

This structure contains the SLQSSetM2MAudioLPBK request parameters.

#### Parameters

<i>Enable</i>	<ul style="list-style-type: none"> <li>Operation to be performed <ul style="list-style-type: none"> <li>0 - stop</li> <li>1 - VOCODER loop</li> <li>2 - internal codec loop</li> </ul> </li> </ul>
---------------	--

### 8.663.2 Field Documentation

8.663.2.1 BYTE SetM2MAudioLPBKReq::Enable

## 8.664 SetM2MAudioProfileReq Struct Reference

### Data Fields

- [BYTE Profile](#)
- [BYTE \\* pEarMute](#)
- [BYTE \\* pMicMute](#)

- [BYTE](#) \* [pGenerator](#)
- [BYTE](#) \* [pVolume](#)
- [BYTE](#) \* [pCwtMute](#)

### 8.664.1 Detailed Description

This structure contains the SLQSSetM2MAudioProfile request parameters.

#### Parameters

<i>Profile</i>	<ul style="list-style-type: none"> <li>• Audio Profile Number <ul style="list-style-type: none"> <li>– 0-5</li> </ul> </li> </ul>
<i>pEarMute</i>	<ul style="list-style-type: none"> <li>• Ear Mute <ul style="list-style-type: none"> <li>– 0 - mute</li> <li>– 1 - unmute</li> </ul> </li> </ul>
<i>pMicMute</i>	<ul style="list-style-type: none"> <li>• Mic Mute <ul style="list-style-type: none"> <li>– 0 - mute</li> <li>– 1 - unmute</li> </ul> </li> </ul>
<i>pGenerator</i>	<ul style="list-style-type: none"> <li>• Generator <ul style="list-style-type: none"> <li>– 0 - voice</li> </ul> </li> </ul>
<i>pVolume</i>	<ul style="list-style-type: none"> <li>• Set RX Volume level <ul style="list-style-type: none"> <li>– 0-5</li> </ul> </li> </ul>
<i>pCwtMute</i>	<ul style="list-style-type: none"> <li>• Call Waiting Tone Mute <ul style="list-style-type: none"> <li>– 0 - Mute</li> <li>– 1 - UnMute</li> </ul> </li> </ul>

### 8.664.2 Field Documentation

8.664.2.1 [BYTE](#)\* [SetM2MAudioProfileReq::pCwtMute](#)

8.664.2.2 [BYTE](#)\* [SetM2MAudioProfileReq::pEarMute](#)

8.664.2.3 [BYTE](#)\* [SetM2MAudioProfileReq::pGenerator](#)

8.664.2.4 **BYTE\*** SetM2MAudioProfileReq::pMicMute

8.664.2.5 **BYTE** SetM2MAudioProfileReq::Profile

8.664.2.6 **BYTE\*** SetM2MAudioProfileReq::pVolume

## 8.665 SetM2MAudioVolumeReq Struct Reference

### Data Fields

- [BYTE Profile](#)
- [BYTE Generator](#)
- [BYTE Level](#)

### 8.665.1 Detailed Description

This structure contains the SLQSSetM2MAudioProfile request parameters.

#### Parameters

<i>Profile</i>	<ul style="list-style-type: none"><li>• Audio Profile Number<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>
<i>Generator</i>	<ul style="list-style-type: none"><li>• Generator<ul style="list-style-type: none"><li>– 0 - voice</li></ul></li></ul>
<i>Level</i>	<ul style="list-style-type: none"><li>• Audio volume level<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>

### 8.665.2 Field Documentation

8.665.2.1 **BYTE** SetM2MAudioVolumeReq::Generator

8.665.2.2 **BYTE** SetM2MAudioVolumeReq::Level

8.665.2.3 **BYTE** SetM2MAudioVolumeReq::Profile

## 8.666 SetM2MAVMuteReq Struct Reference

### Data Fields

- [BYTE Profile](#)
- [BYTE EarMute](#)
- [BYTE MicMute](#)
- [BYTE \\* pCwtMute](#)

### 8.666.1 Detailed Description

This structure contains the SLQSSetM2MAVMute request parameters.

#### Parameters

<i>Profile</i>	<ul style="list-style-type: none"><li>• Audio Profile Number<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>
<i>EarMute</i>	<ul style="list-style-type: none"><li>• Ear Mute<ul style="list-style-type: none"><li>– 0-1</li></ul></li></ul>
<i>MicMute</i>	<ul style="list-style-type: none"><li>• Mic Mute<ul style="list-style-type: none"><li>– 0-1</li></ul></li></ul>
<i>pCwtMute</i>	[ Optional ] <ul style="list-style-type: none"><li>• Call Waiting Tone Mute<ul style="list-style-type: none"><li>– 0-1</li></ul></li></ul>

### 8.666.2 Field Documentation

8.666.2.1 **BYTE** SetM2MAVMuteReq::EarMute

8.666.2.2 **BYTE** SetM2MAVMuteReq::MicMute

8.666.2.3 **BYTE\*** SetM2MAVMuteReq::pCwtMute

8.666.2.4 **BYTE** SetM2MAVMuteReq::Profile

## 8.667 SetM2MSpkrGainReq Struct Reference

#### Data Fields

- [BYTE Profile](#)
- [WORD Value](#)

### 8.667.1 Detailed Description

This structure contains the SLQSSetM2MSpkrGain request parameters.

#### Parameters

---

<i>Profile</i>	<ul style="list-style-type: none"><li>• Audio Profile Number<ul style="list-style-type: none"><li>– 0-5</li></ul></li></ul>
<i>Value</i>	<ul style="list-style-type: none"><li>• RX speakerphone gain<ul style="list-style-type: none"><li>– 0x0 - 0x7fff</li></ul></li></ul>

### 8.667.2 Field Documentation

8.667.2.1 **BYTE** SetM2MSpkrGainReq::Profile

8.667.2.2 **WORD** SetM2MSpkrGainReq::Value

## 8.668 setPINProtection Struct Reference

### Data Fields

- [BYTE](#) pinID
- [BYTE](#) pinOperation
- [BYTE](#) pinLength
- [BYTE](#) pinValue [255]

### 8.668.1 Detailed Description

This structure contains the information about the pin protection parameters that need to be set.

#### Parameters

<i>pinID</i>	<ul style="list-style-type: none"><li>• Indicates the PIN ID to be enabled or disabled.<ul style="list-style-type: none"><li>– 1 - PIN1 (also called PIN)</li><li>– 2 - PIN2</li><li>– 3 - Universal PIN</li><li>– 4 - Hidden key</li></ul></li></ul>
--------------	---

<i>pinOperation</i>	<ul style="list-style-type: none"> <li>Indicates whether the PIN is enabled or disabled. <ul style="list-style-type: none"> <li>0 - Disable the PIN</li> <li>1 - Enable the PIN</li> </ul> </li> </ul>
<i>pinLength</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. pin value.</li> </ul>
<i>pinValue</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>PIN value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

## 8.668.2 Field Documentation

8.668.2.1 BYTE setPINProtection::pinID

8.668.2.2 BYTE setPINProtection::pinLength

8.668.2.3 BYTE setPINProtection::pinOperation

8.668.2.4 BYTE setPINProtection::pinValue[255]

## 8.669 SetRegMgrConfigReq Struct Reference

### Data Fields

- WORD \* pPriCSCFPort
- BYTE \* pCSCFPortNameLen
- BYTE \* pCSCFPortName
- BYTE \* pIMSTestMode

### 8.669.1 Detailed Description

This structure contains the SLQSSetRegMgrConfig request parameters.



## Parameters

<i>pPriCSCFPort</i>	<ul style="list-style-type: none"><li>• Primary call session control function port</li></ul>
<i>pCSCFPort-NameLen</i>	<ul style="list-style-type: none"><li>• Length of the CSCF <a href="#">Port</a> name parameter to follow</li></ul>
<i>pCSCFPort-Name</i>	<ul style="list-style-type: none"><li>• Call Session control port, fully qualified domain name</li><li>• Length of this string must be specified in pCSCFPortNameLen parameter</li></ul>
<i>pIMSTestMode</i>	<ul style="list-style-type: none"><li>• IMS Test mode Enabled.<ul style="list-style-type: none"><li>– TRUE - Enable, no IMS registration</li><li>– FALSE - Disable, IMS registration is initiated</li></ul></li></ul>

## 8.669.2 Field Documentation

8.669.2.1 **BYTE\*** SetRegMgrConfigReq::pCSCFPortName8.669.2.2 **BYTE\*** SetRegMgrConfigReq::pCSCFPortNameLen8.669.2.3 **BYTE\*** SetRegMgrConfigReq::pIMSTestMode8.669.2.4 **WORD\*** SetRegMgrConfigReq::pPriCSCFPort

## 8.670 SetRegMgrConfigResp Struct Reference

## Data Fields

- **BYTE \*** [pSettingResp](#)

## 8.670.1 Detailed Description

This structure contains the SLQSSetRegMgrConfig response parameters.

## Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"><li>• Settings standard response type. A settings specific error code is returned when the standard response error type is QMI_ERR_CAUSE_CODE</li></ul>
---------------------	---

## 8.670.2 Field Documentation

8.670.2.1 **BYTE\*** SetRegMgrConfigResp::pSettingResp

## 8.671 setSignalStrengthInfo Struct Reference

### Data Fields

- [CDMARSSIThresh](#) \* [pCDMARSSIThresh](#)
- [WORD](#) \* [pCDMARSSIDelta](#)
- [CDMAECIOThresh](#) \* [pCDMAECIOThresh](#)
- [WORD](#) \* [pCDMAECIODelta](#)
- [HDDRSSIThresh](#) \* [pHDDRSSIThresh](#)
- [WORD](#) \* [pHDDRSSIDelta](#)
- [HDRECIOThresh](#) \* [pHDRECIOThresh](#)
- [WORD](#) \* [pHDRECIODelta](#)
- [HDRSINRThreshold](#) \* [pHDRSINRThreshold](#)
- [WORD](#) \* [pHDRSINRDelta](#)
- [HDRIOThresh](#) \* [pHDRIOThresh](#)
- [WORD](#) \* [pHDRIODelta](#)
- [GSMRSSIThresh](#) \* [pGSMRSSIThresh](#)
- [WORD](#) \* [pGSMRSSIDelta](#)
- [WCDMARSSIThresh](#) \* [pWCDMARSSIThresh](#)
- [WORD](#) \* [pWCDMARSSIDelta](#)
- [WCDMAECIOThresh](#) \* [pWCDMAECIOThresh](#)
- [WORD](#) \* [pWCDMAECIODelta](#)
- [LTERSSIThresh](#) \* [pLTERSSIThresh](#)
- [WORD](#) \* [pLTERSSIDelta](#)
- [LTESNRThreshold](#) \* [pLTESNRThreshold](#)
- [WORD](#) \* [pLTESNRDelta](#)
- [LTERSRQThresh](#) \* [pLTERSRQThresh](#)
- [WORD](#) \* [pLTERSRQDelta](#)
- [LTERSRPThresh](#) \* [pLTERSRPThresh](#)
- [WORD](#) \* [pLTERSRPDelta](#)
- [LTERSigRptConfig](#) \* [pLTERSigRptConfig](#)
- [TDSCDMARSCPTThresh](#) \* [pTDSCDMARSCPTThresh](#)
- [WORD](#) \* [pTDSCDMARSCPDelta](#)
- [TDSCDMARSSIThresh](#) \* [pTDSCDMARSSIThresh](#)
- [ULONG](#) \* [pTDSCDMARSSIDelta](#)
- [TDSCDMAECIOThresh](#) \* [pTDSCDMAECIOThresh](#)
- [ULONG](#) \* [pTDSCDMAECIODelta](#)
- [TDSCDMASINRThreshold](#) \* [pTDSCDMASINRThreshold](#)
- [ULONG](#) \* [pTDSCDMASINRDelta](#)

### 8.671.1 Detailed Description

This structure contains the Signal Strength reporting thresholds Item information.

#### Parameters

<i>pCDMARSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• CDMA RSSI threshold List</li> <li>• See <a href="#">CDMARSSIThresh</a> for more details</li> </ul>
------------------------------	---

<i>pCDMARSSI-Delta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm).</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pCDMAECIO-Thresh</i>	<ul style="list-style-type: none"> <li>• CDMA ECIO Threshold List</li> <li>• See <a href="#">CDMAECIOThresh</a> for more details</li> </ul>
<i>pCDMAECIO-Delta</i>	<ul style="list-style-type: none"> <li>• ECIO delta (in units of 0.1 dB).</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pHDRRSSI-Thresh</i>	<ul style="list-style-type: none"> <li>• HDR RSSI Threshold List</li> <li>• See <a href="#">HDRRSSIThresh</a> for more details</li> </ul>
<i>pHDRRSSIDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pHDRECIOThresh</i>	<ul style="list-style-type: none"> <li>• HDR ECIO Threshold List</li> <li>• See <a href="#">HDRECIOThresh</a> for more details</li> </ul>
<i>pHDRECIODelta</i>	<ul style="list-style-type: none"> <li>• ECIO delta (in units of 0.1 dB)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pHDRSINR-Thresh</i>	<ul style="list-style-type: none"> <li>• HDR SINR Threshold List</li> <li>• See <a href="#">HDRSINRThreshold</a> for more details</li> </ul>
<i>pHDRSINRDelta</i>	<ul style="list-style-type: none"> <li>• SINR delta (in units of 1 SINR level)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pHDRIOThresh</i>	<ul style="list-style-type: none"> <li>• HDR IO Threshold List</li> <li>• See <a href="#">HDRIOThresh</a> for more details</li> </ul>
<i>pHDRIODelta</i>	<ul style="list-style-type: none"> <li>• IO delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>

<i>pGSMRSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• GSM RSSI Threshold List</li> <li>• See <a href="#">GSMRSSIThresh</a> for more details</li> </ul>
<i>pGSMRSSIDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pWCDMARSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• WCDMA RSSI Threshold List</li> <li>• See <a href="#">WCDMARSSIThresh</a> for more details</li> </ul>
<i>pWCDMARSSI- Delta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm).</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pWCDMAECIO- Thresh</i>	<ul style="list-style-type: none"> <li>• WCDMA ECIO Threshold List</li> <li>• See <a href="#">WCDMAECIOThresh</a> for more details</li> </ul>
<i>pWCDMAECIO- Delta</i>	<ul style="list-style-type: none"> <li>• ECIO delta (in units of 0.1 dB)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSSI- Thresh</i>	<ul style="list-style-type: none"> <li>• LTE RSSI Threshold List</li> <li>• See <a href="#">LTERSSIThresh</a> for more details</li> </ul>
<i>pLTERSSIDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSNR- Thresh</i>	<ul style="list-style-type: none"> <li>• LTE SNR Threshold List</li> <li>• See <a href="#">LTERSNRThreshold</a> for more details</li> </ul>
<i>pLTERSNRDelta</i>	<ul style="list-style-type: none"> <li>• SNR delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSRQ- Thresh</i>	<ul style="list-style-type: none"> <li>• LTE RSRQ Threshold List</li> <li>• See <a href="#">LTERSRQThresh</a> for more details</li> </ul>

<i>pLTERSQR-Delta</i>	<ul style="list-style-type: none"> <li>• RSRQ delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSRP-Thresh</i>	<ul style="list-style-type: none"> <li>• LTE RSRP Threshold List</li> <li>• See <a href="#">LTERSRPThresh</a> for more details</li> </ul>
<i>pLTERSRPDelta</i>	<ul style="list-style-type: none"> <li>• RSRP delta (in units of 0.1 dBm).</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pLTERSigRpt-Config</i>	<ul style="list-style-type: none"> <li>• LTE Signal Report Config</li> <li>• See <a href="#">LTERSigRptConfig</a> for more details</li> </ul>
<i>pTDSCDMARS-CPThresh</i>	<ul style="list-style-type: none"> <li>• TDSCDMA RSCP Threshold List</li> <li>• See <a href="#">TDSCDMARSCPThresh</a> for more details</li> </ul>
<i>pTDSCDMARS-CPDelta</i>	<ul style="list-style-type: none"> <li>• RSCP delta (in units of 0.1 dBm)</li> <li>• A value of 0 is rejected with a QMI_ERR_INVALID_ARG error.</li> </ul>
<i>pTDSCDMARS-SIThresh</i>	<ul style="list-style-type: none"> <li>• TDSCDMA RSSI Threshold List</li> <li>• See <a href="#">TDSCDMARSSIThresh</a> for more details</li> </ul>
<i>pTDSCDMARS-SIDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta (in dBm) used by TD-SCDMA.</li> </ul>
<i>pTDSCDMAECI-OTthresh</i>	<ul style="list-style-type: none"> <li>• TDSCDMA ECIO Threshold List</li> <li>• See <a href="#">TDSCDMAECIOTthresh</a> for more details</li> </ul>
<i>pTDSCDMAECI-ODelta</i>	<ul style="list-style-type: none"> <li>• ECIO delta (in dB) used by TD-SCDMA</li> </ul>
<i>pTDSCDMASIN-RThresh</i>	<ul style="list-style-type: none"> <li>• TDSCDMA SINR Threshold List</li> <li>• See <a href="#">TDSCDMASINRThresh</a> for more details</li> </ul>
<i>pTDSCDMASIN-RDelta</i>	<ul style="list-style-type: none"> <li>• SINR delta (in dB) used by TD-SCDMA.</li> </ul>

## 8.671.2 Field Documentation

- 8.671.2.1 **WORD\*** `setSignalStrengthInfo::pCDMAECIODelta`
- 8.671.2.2 **CDMAECIOThresh\*** `setSignalStrengthInfo::pCDMAECIOThresh`
- 8.671.2.3 **WORD\*** `setSignalStrengthInfo::pCDMARSSIDelta`
- 8.671.2.4 **CDMARSSIThresh\*** `setSignalStrengthInfo::pCDMARSSIThresh`
- 8.671.2.5 **WORD\*** `setSignalStrengthInfo::pGSMRSSIDelta`
- 8.671.2.6 **GSMRSSIThresh\*** `setSignalStrengthInfo::pGSMRSSIThresh`
- 8.671.2.7 **WORD\*** `setSignalStrengthInfo::pHDRECIODelta`
- 8.671.2.8 **HDRECIOThresh\*** `setSignalStrengthInfo::pHDRECIOThresh`
- 8.671.2.9 **WORD\*** `setSignalStrengthInfo::pHDRIODelta`
- 8.671.2.10 **HDRIOThresh\*** `setSignalStrengthInfo::pHDRIOThresh`
- 8.671.2.11 **WORD\*** `setSignalStrengthInfo::pHRRSSIDelta`
- 8.671.2.12 **HDRRSSIThresh\*** `setSignalStrengthInfo::pHDRRSSIThresh`
- 8.671.2.13 **WORD\*** `setSignalStrengthInfo::pHRSINRDelta`
- 8.671.2.14 **HDRSINRThreshold\*** `setSignalStrengthInfo::pHRSINRThresh`
- 8.671.2.15 **WORD\*** `setSignalStrengthInfo::pLTERSRPDelta`
- 8.671.2.16 **LTERSRPThresh\*** `setSignalStrengthInfo::pLTERSRPThresh`
- 8.671.2.17 **WORD\*** `setSignalStrengthInfo::pLTERSRQDelta`
- 8.671.2.18 **LTERSRQThresh\*** `setSignalStrengthInfo::pLTERSRQThresh`
- 8.671.2.19 **WORD\*** `setSignalStrengthInfo::pLTERSSIDelta`
- 8.671.2.20 **LTERSSIThresh\*** `setSignalStrengthInfo::pLTERSSIThresh`
- 8.671.2.21 **LTESigRptConfig\*** `setSignalStrengthInfo::pLTESigRptConfig`
- 8.671.2.22 **WORD\*** `setSignalStrengthInfo::pLTESNRDelta`
- 8.671.2.23 **LTESNRThreshold\*** `setSignalStrengthInfo::pLTESNRThresh`
- 8.671.2.24 **ULONG\*** `setSignalStrengthInfo::pTDSCDMAECIODelta`
- 8.671.2.25 **TDSCDMAECIOThresh\*** `setSignalStrengthInfo::pTDSCDMAECIOThresh`
- 8.671.2.26 **WORD\*** `setSignalStrengthInfo::pTDSCDMARSCPDelta`
- 8.671.2.27 **TDSCDMARSCPThresh\*** `setSignalStrengthInfo::pTDSCDMARSCPThresh`

- 8.671.2.28 **ULONG\*** setSignalStrengthInfo::pTDSCDMARSSIDelta
- 8.671.2.29 **TDSCDMARSSIThresh\*** setSignalStrengthInfo::pTDSCDMARSSIThresh
- 8.671.2.30 **ULONG\*** setSignalStrengthInfo::pTDSCDMASINRDelta
- 8.671.2.31 **TDSCDMASINRThresh\*** setSignalStrengthInfo::pTDSCDMASINRThresh
- 8.671.2.32 **WORD\*** setSignalStrengthInfo::pWCDMAECIODelta
- 8.671.2.33 **WCDMAECIOThresh\*** setSignalStrengthInfo::pWCDMAECIOThresh
- 8.671.2.34 **WORD\*** setSignalStrengthInfo::pWCDMARSSIDelta
- 8.671.2.35 **WCDMARSSIThresh\*** setSignalStrengthInfo::pWCDMARSSIThresh

## 8.672 SetSIPConfigReq Struct Reference

### Data Fields

- **WORD** \* pSIPLocalPort
- **ULONG** \* pTimerSIPReg
- **ULONG** \* pSubscribeTimer
- **ULONG** \* pTimerT1
- **ULONG** \* pTimerT2
- **ULONG** \* pTimerTf
- **BYTE** \* pSigCompEnabled

### 8.672.1 Detailed Description

This structure contains the SLQSSetSIPConfig request parameters.

#### Parameters

<i>pSIPLocalPort</i>	<ul style="list-style-type: none"> <li>• Primary call session control function SIP port number</li> </ul>
<i>pTimerSIPReg</i>	<ul style="list-style-type: none"> <li>• Initial SIP registration duration from the User equipment, in seconds</li> </ul>
<i>pSubscribeTimer</i>	<ul style="list-style-type: none"> <li>• Duration of the subscription by the UE for IMS registration notifications, in seconds</li> </ul>
<i>pTimerT1</i>	<ul style="list-style-type: none"> <li>• RTT estimate, in milliseconds</li> </ul>
<i>pTimerT2</i>	<ul style="list-style-type: none"> <li>• The maximum retransmit interval for non-invite requests and invite responses, in milliseconds</li> </ul>

<i>pTimerTf</i>	<ul style="list-style-type: none"> <li>• Non-invite transaction timeout timer, in milliseconds</li> </ul>
<i>pSigCompEnabled</i>	<ul style="list-style-type: none"> <li>• Sig Comp Status <ul style="list-style-type: none"> <li>– TRUE - Enable</li> <li>– FALSE - Disable</li> </ul> </li> </ul>

## 8.672.2 Field Documentation

8.672.2.1 **BYTE\*** SetSIPConfigReq::pSigCompEnabled

8.672.2.2 **WORD\*** SetSIPConfigReq::pSIPLocalPort

8.672.2.3 **ULONG\*** SetSIPConfigReq::pSubscribeTimer

8.672.2.4 **ULONG\*** SetSIPConfigReq::pTimerSIPReg

8.672.2.5 **ULONG\*** SetSIPConfigReq::pTimerT1

8.672.2.6 **ULONG\*** SetSIPConfigReq::pTimerT2

8.672.2.7 **ULONG\*** SetSIPConfigReq::pTimerTf

## 8.673 SetSIPConfigResp Struct Reference

### Data Fields

- [BYTE \\*](#) [pSettingResp](#)

### 8.673.1 Detailed Description

This structure contains the SLQSSetSIPConfig response parameters.

#### Parameters

<i>pSettingResp</i>	<ul style="list-style-type: none"> <li>• Settings standard response type. A settings specific error code is returned when the standard response error type is QMI_ERR_CAUSE_CODE</li> </ul>
---------------------	---

## 8.673.2 Field Documentation

8.673.2.1 **BYTE\*** SetSIPConfigResp::pSettingResp

## 8.674 sGetDeviceSeriesResult Struct Reference

### Data Fields

- enum [eGobiDeviceSeries](#) [eDevice](#)



- [ULONG uResult](#)

### 8.674.1 Detailed Description

This structure contains the Device Series

Parameters

<i>eGobiDeviceSeries</i>	<ul style="list-style-type: none"> <li>• The number of device in the device series</li> </ul>
<i>uResult</i>	-eQCWWAN_ERR_NONE on success, eQCWWAN_xxx error value otherwise

### 8.674.2 Field Documentation

8.674.2.1 enum eGobiDeviceSeries sGetDeviceSeriesResult::eDevice

8.674.2.2 ULONG sGetDeviceSeriesResult::uResult

## 8.675 sidNid Struct Reference

Data Fields

- [WORD nid](#)
- [WORD sid](#)

### 8.675.1 Detailed Description

This structure contains the parameters for SidNid Information

Parameters

<i>nid</i>	<ul style="list-style-type: none"> <li>• Network ID</li> </ul>
<i>sid</i>	<ul style="list-style-type: none"> <li>• System ID</li> </ul>

### 8.675.2 Field Documentation

8.675.2.1 WORD sidNid::nid

8.675.2.2 WORD sidNid::sid

## 8.676 sigInfo Struct Reference

Data Fields

- [RSSIThresh](#) \* [pRSSIThresh](#)
- [ECIOTThresh](#) \* [pECIOTThresh](#)
- [HRSINRThresh](#) \* [pHRSINRThresh](#)

- [LTESNRThresh](#) \* [pLTESNRThresh](#)
- [IOTthresh](#) \* [pIOTthresh](#)
- [RSRQThresh](#) \* [pRSRQThresh](#)
- [RSRPThresh](#) \* [pRSRPThresh](#)
- [LTESigRptCfg](#) \* [pLTESigRptCfg](#)
- [TDSCDMASINRCONFTthresh](#) \* [pTDSCDMASINRCONFTthresh](#)

### 8.676.1 Detailed Description

This structure contains the 3gpp Configuration Item information.

#### Parameters

<i>pRSSIThresh</i>	<ul style="list-style-type: none"> <li>• RSSI threshold List</li> <li>• See <a href="#">RSSIThresh</a> for more details</li> </ul>
<i>pECIOTthresh</i>	<ul style="list-style-type: none"> <li>• ECIO Threshold List</li> <li>• See <a href="#">ECIOTthresh</a> for more details</li> </ul>
<i>pHDRSINR- Thresh</i>	<ul style="list-style-type: none"> <li>• HDR SINR Threshold List</li> <li>• See <a href="#">HDRSINRThresh</a> for more details</li> </ul>
<i>pLTESNR- Thresh</i>	<ul style="list-style-type: none"> <li>• LTE SNR Threshold List</li> <li>• See <a href="#">LTESNRThresh</a> for more details</li> </ul>
<i>pIOTthresh</i>	<ul style="list-style-type: none"> <li>• IO Threshold List</li> <li>• See <a href="#">IOTthresh</a> for more details</li> </ul>
<i>pRSRQThresh</i>	<ul style="list-style-type: none"> <li>• RSRQ Threshold List</li> <li>• See <a href="#">RSRQThresh</a> for more details</li> </ul>
<i>pRSRPThresh</i>	<ul style="list-style-type: none"> <li>• RSRP Threshold List</li> <li>• See <a href="#">RSRPThresh</a> for more details</li> </ul>
<i>pLTESigRptCfg</i>	<ul style="list-style-type: none"> <li>• LTE signal report config</li> <li>• See <a href="#">LTESigRptCfg</a> for more details</li> </ul>

<i>pTDSCDMASIN- RCONFThresh</i>	<ul style="list-style-type: none"> <li>• TD-SCDMA SINR Threshold List</li> <li>• See <a href="#">TDSCDMASINRCONFThresh</a> for more details</li> </ul>
-------------------------------------	--

## 8.676.2 Field Documentation

8.676.2.1 **ECIOThresh\*** sigInfo::pECIOThresh

8.676.2.2 **HDRSINRThresh\*** sigInfo::pHRSINRThresh

8.676.2.3 **IOThresh\*** sigInfo::pIOThresh

8.676.2.4 **LTESigRptCfg\*** sigInfo::pLTESigRptCfg

8.676.2.5 **LTESNRThresh\*** sigInfo::pLTESNRThresh

8.676.2.6 **RSRPTHresh\*** sigInfo::pRSRPTHresh

8.676.2.7 **RSRQThresh\*** sigInfo::pRSRQThresh

8.676.2.8 **RSSIThresh\*** sigInfo::pRSSIThresh

8.676.2.9 **TDSCDMASINRCONFThresh\*** sigInfo::pTDSCDMASINRCONFThresh

## 8.677 signalInfo Struct Reference

### Data Fields

- [BYTE signalType](#)
- [BYTE alertPitch](#)
- [BYTE signal](#)

### 8.677.1 Detailed Description

This structure contains Signal Information

#### Parameters

<i>signalType</i>	<ul style="list-style-type: none"> <li>• Call identifier for the call.</li> </ul>
<i>alertPitch</i>	<ul style="list-style-type: none"> <li>• Signal Information</li> </ul>
<i>signal</i>	<ul style="list-style-type: none"> <li>• Caller ID Information</li> </ul>

### 8.677.2 Field Documentation

8.677.2.1 **BYTE** `signalInfo::alertPitch`

8.677.2.2 **BYTE** `signalInfo::signal`

8.677.2.3 **BYTE** `signalInfo::signalType`

## 8.678 SignalStrengthDataType Struct Reference

### Data Fields

- [BYTE](#) `thresholdsSize`
- [INT8](#) `thresholds` [5]

### 8.678.1 Field Documentation

8.678.1.1 **INT8** `SignalStrengthDataType::thresholds`[5]

8.678.1.2 **BYTE** `SignalStrengthDataType::thresholdsSize`

## 8.679 slot\_t Struct Reference

### Data Fields

- `uint32_t` [uPhyCardStatus](#)
- `uint32_t` [uPhySlotStatus](#)
- `uint8_t` [bLogicalSlot](#)
- `uint8_t` [bCCIDLength](#)
- `uint8_t` [bCCID](#) [255]

### 8.679.1 Detailed Description

This structure contains information of the response parameters associated with a Get Slots Status API.

#### Parameters

<i>uPhyCardStatus</i>	<ul style="list-style-type: none"> <li>• State of the card in the Pyhsical Slot Status. <ul style="list-style-type: none"> <li>– 0x00 - Unknown.</li> <li>– 0x01 - Absent.</li> <li>– 0x02 - Present.</li> </ul> </li> </ul>
-----------------------	--

<i>uPhySlotStatus</i>	<ul style="list-style-type: none"> <li>• State of the Physical Slot status. <ul style="list-style-type: none"> <li>– 0x00 Inactive.</li> <li>– 0x01 Activate.</li> </ul> </li> </ul>
<i>bLogicalSlot</i>	<ul style="list-style-type: none"> <li>• Logical Slot associated with this physical slot. This is valid if the physical slot is active. <ul style="list-style-type: none"> <li>– 1 - Slot 1.</li> <li>– 2 - Slot 2.</li> <li>– 3 - Slot 3.</li> <li>– 4 - Slot 4.</li> <li>– 5 - Slot 5.</li> </ul> </li> </ul>
<i>bLogicalSlot</i>	<ul style="list-style-type: none"> <li>• Number of sets the sets of ICCID</li> </ul>
<i>bICCID[MAX_ICCID_LENGTH]</i>	<ul style="list-style-type: none"> <li>• Contains the ICCID of the card in the physical slot.</li> </ul>

## 8.679.2 Field Documentation

8.679.2.1 `uint8_t slot_t::bICCID[255]`

8.679.2.2 `uint8_t slot_t::bICCIDLength`

8.679.2.3 `uint8_t slot_t::bLogicalSlot`

8.679.2.4 `uint32_t slot_t::uPhyCardStatus`

8.679.2.5 `uint32_t slot_t::uPhySlotStatus`

## 8.680 slotInf Struct Reference

### Data Fields

- `uint8_t cardState`
- `uint8_t upinState`
- `uint8_t upinRetries`
- `uint8_t upukRetries`
- `uint8_t errorState`
- `uint8_t numApp`
- `appStats AppStatus [10]`

### 8.680.1 Detailed Description

This structure contains information about the SLOTS present.

## Parameters

<i>cardState</i>	<ul style="list-style-type: none"> <li>Indicates the state of the card for each slot. <ul style="list-style-type: none"> <li>0 - Absent</li> <li>1 - Present</li> <li>2 - Error</li> </ul> </li> </ul>
<i>upinState</i>	<ul style="list-style-type: none"> <li>Indicates the state of UPIN. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>upinRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify the UPIN.</li> <li>If 0xFF, information not available.</li> </ul>
<i>upukRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock the UPIN.</li> <li>If 0xFF, information not available.</li> </ul>
<i>errorState</i>	<ul style="list-style-type: none"> <li>Indicates the reason for the card error, and is valid only when the card state is Error <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Power down</li> <li>2 - Poll error</li> <li>3 - No ATR received</li> <li>4 - Volt mismatch</li> <li>5 - Parity error</li> <li>6 - Unknown; possibly removed</li> <li>7 - Card returned technical problems</li> <li>0xFF - Not Available</li> </ul> </li> <li>Other values are possible and reserved for future use.</li> <li>When an unknown value is received, it is to be handled as "Unknown".</li> </ul>
<i>numApp</i>	<ul style="list-style-type: none"> <li>Indicates the number of applications available on the card.</li> <li>The following block is repeated for each application. i.e. AppStatus.</li> <li>If zero(0) then no AppStatus information exists.</li> </ul>

<i>AppStatus</i> [MAX_ _NO_OF_APPL- ICATIONS]	<ul style="list-style-type: none"><li>• See <a href="#">appStats</a> for more information.</li></ul>
---	--

## 8.680.2 Field Documentation

8.680.2.1 `appStats slotInf::AppStatus[10]`

8.680.2.2 `uint8_t slotInf::cardState`

8.680.2.3 `uint8_t slotInf::errorState`

8.680.2.4 `uint8_t slotInf::numApp`

8.680.2.5 `uint8_t slotInf::upinRetries`

8.680.2.6 `uint8_t slotInf::upinState`

8.680.2.7 `uint8_t slotInf::upukRetries`

## 8.681 slotInfo Struct Reference

### Data Fields

- [BYTE](#) `cardState`
- [BYTE](#) `upinState`
- [BYTE](#) `upinRetries`
- [BYTE](#) `upukRetries`
- [BYTE](#) `errorState`
- [BYTE](#) `numApp`
- [appStatus](#) [AppStatus](#) [10]

### 8.681.1 Detailed Description

This structure contains information about the SLOTS present.

#### Parameters

<i>cardState</i>	<ul style="list-style-type: none"><li>• Indicates the state of the card for each slot.<ul style="list-style-type: none"><li>– 0 - Absent</li><li>– 1 - Present</li><li>– 2 - Error</li></ul></li></ul>
------------------	--

<i>upinState</i>	<ul style="list-style-type: none"> <li>Indicates the state of UPIN. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>upinRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify the UPIN.</li> <li>If 0xFF, information not available.</li> </ul>
<i>upukRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock the UPIN.</li> <li>If 0xFF, information not available.</li> </ul>
<i>errorState</i>	<ul style="list-style-type: none"> <li>Indicates the reason for the card error, and is valid only when the card state is Error <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Power down</li> <li>2 - Poll error</li> <li>3 - No ATR received</li> <li>4 - Volt mismatch</li> <li>5 - Parity error</li> <li>6 - Unknown; possibly removed</li> <li>7 - Card returned technical problems</li> <li>0xFF - Not Available</li> </ul> </li> <li>Other values are possible and reserved for future use.</li> <li>When an unknown value is received, it is to be handled as "Unknown".</li> </ul>



<i>numApp</i>	<ul style="list-style-type: none"> <li>Indicates the number of applications available on the card.</li> <li>The following block is repeated for each application. i.e. AppStatus.</li> <li>If zero(0) then no AppStatus information exists.</li> </ul>
<i>AppStatus[MAX_NO_OF_APPLICATIONS]</i>	<ul style="list-style-type: none"> <li>See <a href="#">appStatus</a> for more information.</li> </ul>

## 8.681.2 Field Documentation

8.681.2.1 `appStatus slotInfo::AppStatus[10]`

8.681.2.2 `BYTE slotInfo::cardState`

8.681.2.3 `BYTE slotInfo::errorState`

8.681.2.4 `BYTE slotInfo::numApp`

8.681.2.5 `BYTE slotInfo::upinRetries`

8.681.2.6 `BYTE slotInfo::upinState`

8.681.2.7 `BYTE slotInfo::upukRetries`

## 8.682 slots\_t Struct Reference

### Data Fields

- [slot\\_t uimSlotStatus](#) [255]

## 8.682.1 Field Documentation

8.682.1.1 `slot_t slots_t::uimSlotStatus[255]`

## 8.683 slqsautoconnect Struct Reference

### Data Fields

- [BOOL action](#)
- [BYTE acsetting](#)
- [BYTE acroamsetting](#)

## 8.683.1 Detailed Description

structure contains autoconnect settings parameters

## Parameters

<i>action</i>	<ul style="list-style-type: none"> <li>• 0 - get autoconnect settings</li> <li>• 1 - set autoconnect settings</li> </ul>
<i>acsetting</i>	<ul style="list-style-type: none"> <li>• Current autoconnect setting: <ul style="list-style-type: none"> <li>– 0x00 - Autoconnect disabled</li> <li>– 0x01 - Autoconnect enabled</li> <li>– 0x02 - Autoconnect paused (resume on powercycle)</li> </ul> </li> </ul>
<i>acroamsetting</i>	<ul style="list-style-type: none"> <li>• Current autoconnect roaming status <ul style="list-style-type: none"> <li>– 0x00 - Autoconnect always allowed</li> <li>– 0x01 - Autoconnect while in home service area only</li> </ul> </li> </ul>

## 8.683.2 Field Documentation

8.683.2.1 BYTE slqsautoconnect::acroamsetting

8.683.2.2 BYTE slqsautoconnect::acsetting

8.683.2.3 BOOL slqsautoconnect::action

## 8.684 SLQSDeleteProfileParams Struct Reference

## Data Fields

- [BYTE profileType](#)
- [BYTE profileIndex](#)

## 8.684.1 Detailed Description

This structure contains the information about the profile to be deleted.

## Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>• Identifies the type of profile <ul style="list-style-type: none"> <li>– 0x00 – 3GPP</li> </ul> </li> <li>• Note: Deletion of 3GPP2 profiles is not supported.</li> </ul>
--------------------	---

<i>profileIndex</i>	<ul style="list-style-type: none"> <li>• Index of the configured profile to be deleted <ul style="list-style-type: none"> <li>– Value between 1 - 16 (EM/MC73xx or earlier)</li> <li>– Value between 1 - 24 (EM/MC74xx onwards)</li> </ul> </li> </ul>
---------------------	--

## 8.684.2 Field Documentation

8.684.2.1 BYTE SLQSDeleteProfileParams::profileIndex

8.684.2.2 BYTE SLQSDeleteProfileParams::profileType

## 8.685 slqsfwinfo\_s Struct Reference

### Data Fields

- [CHAR modelid\\_str](#) [20]
- [CHAR bootversion\\_str](#) [85]
- [CHAR appversion\\_str](#) [85]
- [CHAR sku\\_str](#) [15]
- [CHAR packageid\\_str](#) [85]
- [CHAR carrier\\_str](#) [20]
- [CHAR priversion\\_str](#) [16]
- [CHAR cur\\_carr\\_name](#) [17]
- [CHAR cur\\_carr\\_rev](#) [13]

### 8.685.1 Detailed Description

SPKG CWE firmware image info structure

#### Parameters

<i>modelid_str</i>	<ul style="list-style-type: none"> <li>• device model identifier string</li> </ul>
<i>bootversion_str</i>	<ul style="list-style-type: none"> <li>• firmware boot version string</li> </ul>
<i>appversion_str</i>	<ul style="list-style-type: none"> <li>• firmware application version string</li> </ul>
<i>sku_str</i>	<ul style="list-style-type: none"> <li>• SKU(PRI) string</li> </ul>
<i>packageid_str</i>	<ul style="list-style-type: none"> <li>• package identifier string</li> <li>• deprecated on EM/MC74xx(9x30) devices</li> </ul>

<i>carrier_str</i>	<ul style="list-style-type: none"> <li>• carrier string</li> <li>• See <a href="#">qaGobiApiTableCarrierCodes.h</a> for carrier codes</li> </ul>
<i>prversion_str</i>	<ul style="list-style-type: none"> <li>• PRI version string</li> </ul>
<i>cur_carr_name</i>	<ul style="list-style-type: none"> <li>• Current PRI Carrier Name</li> </ul>
<i>cur_carr_rev</i>	<ul style="list-style-type: none"> <li>• Current PRI Carrier Revision</li> </ul>

## 8.685.2 Field Documentation

8.685.2.1 **CHAR** slqsfwinfo\_s::appversion\_str[85]

8.685.2.2 **CHAR** slqsfwinfo\_s::bootversion\_str[85]

8.685.2.3 **CHAR** slqsfwinfo\_s::carrier\_str[20]

8.685.2.4 **CHAR** slqsfwinfo\_s::cur\_carr\_name[17]

8.685.2.5 **CHAR** slqsfwinfo\_s::cur\_carr\_rev[13]

8.685.2.6 **CHAR** slqsfwinfo\_s::modelid\_str[20]

8.685.2.7 **CHAR** slqsfwinfo\_s::packageid\_str[85]

8.685.2.8 **CHAR** slqsfwinfo\_s::prversion\_str[16]

8.685.2.9 **CHAR** slqsfwinfo\_s::sku\_str[15]

## 8.686 SlqsNas3GppNetworkInfo Struct Reference

### Data Fields

- [WORD MCC](#)
- [WORD MNC](#)
- [ULONG InUse](#)
- [ULONG Roaming](#)
- [ULONG Forbidden](#)
- [ULONG Preferred](#)
- [CHAR Description](#) [255]

### 8.686.1 Detailed Description

Contain the 3GPP network information.

## Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
<i>MNC</i>	<ul style="list-style-type: none"> <li>• Mobile Network Code</li> </ul>
<i>InUse</i>	<ul style="list-style-type: none"> <li>• Is the Network the current serving Network <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - Current serving network</li> <li>– 2 - Not current serving network, available</li> </ul> </li> </ul>
<i>Roaming</i>	<ul style="list-style-type: none"> <li>• Home/Roam Status of the Network <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - Home</li> <li>– 2 - Roam</li> </ul> </li> </ul>
<i>Forbidden</i>	<ul style="list-style-type: none"> <li>• Is the Network in the forbidden network list <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - Forbidden</li> <li>– 2 - Not Forbidden</li> </ul> </li> </ul>
<i>Preferred</i>	<ul style="list-style-type: none"> <li>• Is the Network in the Preferred network list <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - Preferred</li> <li>– 2 - Not Preferred</li> </ul> </li> </ul>
<i>Description</i>	<ul style="list-style-type: none"> <li>• Network Name/Description</li> <li>• This is a NULL terminated string.</li> </ul>

## 8.686.2 Field Documentation

8.686.2.1 CHAR SlqsNas3GppNetworkInfo::Description[255]

8.686.2.2 ULONG SlqsNas3GppNetworkInfo::Forbidden

8.686.2.3 ULONG SlqsNas3GppNetworkInfo::InUse

8.686.2.4 WORD SIqsNas3GppNetworkInfo::MCC

8.686.2.5 WORD SIqsNas3GppNetworkInfo::MNC

8.686.2.6 ULONG SIqsNas3GppNetworkInfo::Preferred

8.686.2.7 ULONG SIqsNas3GppNetworkInfo::Roaming

## 8.687 SIqsNasPcsDigit Struct Reference

### Data Fields

- [WORD MCC](#)
- [WORD MNC](#)
- [BYTE includes\\_pcs\\_digit](#)

### 8.687.1 Detailed Description

Contain the PCS Digit information

#### Parameters

<i>MCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
<i>MNC</i>	<ul style="list-style-type: none"> <li>• Mobile Network Code</li> </ul>
<i>includes_pcs_ - digit</i>	<ul style="list-style-type: none"> <li>• this field is use to interpret the length of corresponding MNC reported</li> <li>• 0x01 - MNC is a three-digit value</li> <li>• 0x00 - MNC is a two-digit value</li> </ul>

### 8.687.2 Field Documentation

8.687.2.1 BYTE SIqsNasPcsDigit::includes\_pcs\_digit

8.687.2.2 WORD SIqsNasPcsDigit::MCC

8.687.2.3 WORD SIqsNasPcsDigit::MNC

## 8.688 slqssendasyncsmsparams\_s Struct Reference

### Data Fields

- [ULONG messageFormat](#)
- [ULONG messageSize](#)
- [BYTE \\* pMessage](#)
- [BYTE \\* pForceOnDC](#)
- [BYTE \\* pServiceOption](#)
- [BYTE \\* pFollowOnDC](#)

- [BYTE](#) \* [pLinktimer](#)
- [BYTE](#) \* [pSmsOnlms](#)
- [BYTE](#) \* [pRetryMessage](#)
- [ULONG](#) \* [pRetryMessageld](#)
- [ULONG](#) \* [pUserData](#)

### 8.688.1 Detailed Description

This structure contains SMS parameters

#### Parameters

<i>messageFormat</i>	<ul style="list-style-type: none"> <li>• Message format</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - CDMA (IS-637B)</li> <li>– 1 - 5 (Reserved)</li> <li>– 6 - GSM/WCDMA PP</li> </ul> </li> </ul>
<i>messageSize</i>	<ul style="list-style-type: none"> <li>• The length of the message contents in bytes</li> </ul>
<i>pMessage</i>	<ul style="list-style-type: none"> <li>• The message contents</li> </ul>
<i>pForceOnDC</i>	<ul style="list-style-type: none"> <li>• Force the message to be sent on the CDMA dedicated channel.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Do not care about the channel on which the message is sent</li> <li>– 0x01 - Request to send the message over the dedicated channel</li> </ul> </li> </ul>
<i>pServiceOption</i>	<ul style="list-style-type: none"> <li>• Service option:</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - SO_AUTO - AUTO (choose the best service option)</li> <li>– 0x06 - SO_6 - Service option 6</li> <li>– 0x0E - SO_14 - Service option 14</li> </ul> </li> </ul>

<i>pFollowOnDC</i>	<ul style="list-style-type: none"> <li>• Flag to request not to disconnect the CDMA dedicated channel after the send operation is complete.</li> <li>• This TLV can be included if more messages are expected to follow.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - FOLLOW_ON_DC_ON - On (don't disconnect after send operation) Any value other than 0x01 is treated as an absence of this TLV.</li> </ul> </li> </ul>
<i>pLinktimer</i>	<ul style="list-style-type: none"> <li>• Keeps the GW SMS link open for the specified number of seconds; can be enabled if more messages are expected to follow</li> </ul>
<i>pSmsOnIms</i>	<ul style="list-style-type: none"> <li>• Indicates whether the message is to be sent on IMS.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Message is not to be sent on IMS</li> <li>– 0x01 - Message is to be sent on IMS</li> <li>– 0x02 to 0xFF - Reserved</li> </ul> </li> </ul>
<i>pRetryMessage</i>	<ul style="list-style-type: none"> <li>• Indicates this message is a retry message.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - WMS_MESSAGE_IS_A_RETRY - Message is a retry message Note: Any value other than 0x01 in this field is treated as an absence of this TLV.</li> </ul> </li> </ul>
<i>pRetryMessage-Id</i>	<ul style="list-style-type: none"> <li>• Message ID to be used in the retry message.</li> <li>• The message ID specified here is used instead of the message ID encoded in the raw message.</li> </ul>
<i>pUserData</i>	<ul style="list-style-type: none"> <li>• Enables the control point to associate the request with the corresponding indication.</li> <li>• The control point might send numerous requests.</li> <li>• This TLV will help the control point to identify the request for which the received indication belongs.</li> </ul>

## 8.688.2 Field Documentation

8.688.2.1 **ULONG** `slqssendasyncsmsparams_s::messageFormat`

8.688.2.2 **ULONG** `slqssendasyncsmsparams_s::messageSize`

8.688.2.3 **BYTE\*** `slqssendasyncsmsparams_s::pFollowOnDC`



- 8.688.2.4 **BYTE\*** slqssendasyncsmsparams\_s::pForceOnDC
- 8.688.2.5 **BYTE\*** slqssendasyncsmsparams\_s::pLinktimer
- 8.688.2.6 **BYTE\*** slqssendasyncsmsparams\_s::pMessage
- 8.688.2.7 **BYTE\*** slqssendasyncsmsparams\_s::pRetryMessage
- 8.688.2.8 **ULONG\*** slqssendasyncsmsparams\_s::pRetryMessageId
- 8.688.2.9 **BYTE\*** slqssendasyncsmsparams\_s::pServiceOption
- 8.688.2.10 **BYTE\*** slqssendasyncsmsparams\_s::pSmsOnlms
- 8.688.2.11 **ULONG\*** slqssendasyncsmsparams\_s::pUserData

## 8.689 slqssendsmsparams\_s Struct Reference

### Data Fields

- [ULONG messageFormat](#)
- [ULONG messageSize](#)
- [BYTE \\* pMessage](#)
- [USHORT messageID](#)
- [ULONG messageFailureCode](#)
- [BYTE \\* pLinktimer](#)
- [BYTE \\* pSmsOnlms](#)

### 8.689.1 Detailed Description

This structure contains SMS parameters

#### Parameters

<i>message-Format</i> [IN]	<ul style="list-style-type: none"> <li>• Message format               <ul style="list-style-type: none"> <li>– 0 - CDMA (IS-637B)</li> <li>– 1 - 5 (Reserved)</li> <li>– 6 - GSM/WCDMA PP</li> </ul> </li> </ul>
<i>messageSize</i> [IN]	<ul style="list-style-type: none"> <li>• The length of the message contents in bytes</li> </ul>
<i>pMessage</i> [IN]	<ul style="list-style-type: none"> <li>• The message contents in PDU format contains SMS header and payload message</li> </ul>
<i>pMessageID</i> [O-UT]	<ul style="list-style-type: none"> <li>• message reference ID</li> </ul>

<i>pMessageFailureCode</i> [OUT]	<ul style="list-style-type: none"> <li>• (Optional) Message Failure Code</li> <li>• If cause code is not provided, then value will be 0xFFFFFFFF</li> </ul>
<i>pSmsOnIms</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) SMS on IMS</li> <li>• Indicates whether the message is to be sent on IMS.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Message is not to be sent on IMS</li> <li>– 0x01 - Message is to be sent on IMS</li> <li>– 0x02 to 0xFF - Reserved</li> </ul> </li> </ul>
<i>pLinktimer</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Link Timer</li> <li>• Keeps the GW SMS link open for the specified number of seconds; can be enabled if more messages are expected to follow</li> </ul>

## 8.689.2 Field Documentation

8.689.2.1 **ULONG** `slqssendsmsparams_s::messageFailureCode`

8.689.2.2 **ULONG** `slqssendsmsparams_s::messageFormat`

8.689.2.3 **USHORT** `slqssendsmsparams_s::messageID`

8.689.2.4 **ULONG** `slqssendsmsparams_s::messageSize`

8.689.2.5 **BYTE\*** `slqssendsmsparams_s::pLinktimer`

8.689.2.6 **BYTE\*** `slqssendsmsparams_s::pMessage`

8.689.2.7 **BYTE\*** `slqssendsmsparams_s::pSmsOnIms`

## 8.690 slqsSessionStateInfo Struct Reference

### Data Fields

- [qaQmiInterfaceInfo](#) \* [pQmiInterfaceInfo](#)
- [ULONG](#) `reconfiguration_required`
- [ULONG](#) `state`
- [ULONG](#) `sessionEndReason`

### 8.690.1 Detailed Description

Contains the session state information and information about the interface

## Parameters

<i>pQmiInterface-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaQmiInterfaceInfo</a> for more information</li> </ul>
<i>state</i>	<ul style="list-style-type: none"> <li>• Current Link Status <ul style="list-style-type: none"> <li>– 1 Disconnected</li> <li>– 2 Connected</li> <li>– 3 Suspended (Unsupported)</li> <li>– 4 Authenticating</li> </ul> </li> </ul>
<i>reconfiguration_ -required</i>	<ul style="list-style-type: none"> <li>• Indicates if host needs to be reconfigured <ul style="list-style-type: none"> <li>– 0 No need to reconfigure</li> <li>– 1 Reconfiguration required</li> </ul> </li> </ul>
<i>sessionEnd-Reason</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason</li> </ul>

## 8.690.2 Field Documentation

8.690.2.1 `qaQmiInterfaceInfo* slqsSessionStateInfo::pQmiInterfaceInfo`8.690.2.2 `ULONG slqsSessionStateInfo::reconfiguration_required`8.690.2.3 `ULONG slqsSessionStateInfo::sessionEndReason`8.690.2.4 `ULONG slqsSessionStateInfo::state`

## 8.691 slqsSignalStrengthInfo Struct Reference

## Data Fields

- `USHORT signalStrengthReqMask`
- `USHORT rxSignalStrengthListLen`
- `struct rxSignalStrengthListElement rxSignalStrengthList [18]`
- `USHORT ecioListLen`
- `struct ecioListElement ecioList [18]`
- `INT32 lo`
- `BYTE sinr`
- `USHORT errorRateListLen`
- `struct errorRateListElement errorRateList [18]`
- `struct rsrqInformation rsrqInfo`
- `SHORT ltesnr`
- `SHORT ltersrp`

### 8.691.1 Detailed Description

This structure contains the Signal Strength Information

## Parameters

<i>signalStrength-ReqMask</i> [IN]	<ul style="list-style-type: none"> <li>• Request Mask <ul style="list-style-type: none"> <li>– Request additional signal information for: Bit 0 - RSSI Information bit Valid values are: 0 - Do Not Request Additional Info for RSSI 1 - Request Additional Info for RSSI</li> <li>Bit 1 - ECIO Information bit Valid values are: 0 - Do Not Request Additional Info for ECIO 1 - Request Additional Info for ECIO</li> <li>Bit 2 - IO Information bit Valid values are: 0 - Do Not Request Additional Info for IO 1 - Request Additional Info for IO</li> <li>Bit 3 - SINR Information bit Valid values are: 0 - Do Not Request Additional Info for SINR 1 - Request Additional Info for SINR</li> <li>Bit 4 - ERROR RATE Information bit Valid values are: 0 - Do Not Request Additional Info for Error Rate 1 - Request Additional Info for Error Rate</li> <li>Bit 5 - RSRQ Information bit Valid values are: 0 - Do Not Request Additional Info for RSRQ 1 - Request Additional Info for RSRQ</li> <li>Bit 6 - LTE SNR information bit Valid values are: 0 - Do not request additional information for LTE SNR 1 - Request additional information for LTE SNR</li> <li>Bit 7 - LTE RSRP Information bit Valid values are: 0 - Do not request additional information for LTE RSRP 1 - Request additional information for LTE RSRP</li> </ul> </li> </ul>
------------------------------------	--

<i>rxSignalStrengthListLen</i> [OUT]	<ul style="list-style-type: none"> <li>Number of elements in Receive Signal Strength List</li> </ul>
<i>rxSignalStrengthList</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">rxSignalStrengthListElement</a> for more information</li> </ul>
<i>ecioListLen</i> [OUT]	<ul style="list-style-type: none"> <li>Number of elements in ECIO List</li> </ul>
<i>ecioList</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">ecioListElement</a> for more information</li> </ul>
<i>Io</i> [OUT]	<ul style="list-style-type: none"> <li>Received Io in dBm; IO is only applicable for 1xEV-DO</li> </ul>
<i>sinr</i> [OUT]	<ul style="list-style-type: none"> <li>SINR level <ul style="list-style-type: none"> <li>SINR is only applicable for 1xEV-DO; valid levels are 0 to 8 where maximum value for 0 - SINR_LEVEL_0 is -9 dB 1 - SINR_LEVEL_1 is -6 dB 2 - SINR_LEVEL_2 is -4.5 dB 3 - SINR_LEVEL_3 is -3 dB 4 - SINR_LEVEL_4 is -2 dB 5 - SINR_LEVEL_5 is +1 dB 6 - SINR_LEVEL_6 is +3 dB 7 - SINR_LEVEL_7 is +6 dB 8 - SINR_LEVEL_8 is +9 dB</li> </ul> </li> </ul>
<i>errorRateListLen</i> [OUT]	<ul style="list-style-type: none"> <li>Number of elements in Error Rate List</li> </ul>
<i>errorRateList</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">errorRateListElement</a> for more information</li> </ul>
<i>rsrqInfo</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">rsrqInformation</a> for more information</li> </ul>
<i>ltesnr</i> [OUT]	<ul style="list-style-type: none"> <li>LTE SNR level as a scaled integer in units of 0.1 dB; e.g., -16 dB has a value of -160 and 24.6 dB has a value of 246. LTE SNR is included only when the current serving system is LTE</li> </ul>
<i>ltesrp</i> [OUT]	<ul style="list-style-type: none"> <li>LTE SNR level as a scaled integer in units of 0.1 dB; e.g., -16 dB has a value of -160 and 24.6 dB has a value of 246. LTE SNR is included only when the current serving system is LTE</li> </ul>

## 8.691.2 Field Documentation

8.691.2.1 struct `ecioListElement` `slqsSignalStrengthInfo::ecioList[18]`

8.691.2.2 USHORT `slqsSignalStrengthInfo::ecioListLen`

8.691.2.3 struct `errorRateListElement` `slqsSignalStrengthInfo::errorRateList[18]`

- 8.691.2.4 **USHORT** slqsSignalStrengthInfo::errorRateListLen
- 8.691.2.5 **INT32** slqsSignalStrengthInfo::lo
- 8.691.2.6 **SHORT** slqsSignalStrengthInfo::ltsrtp
- 8.691.2.7 **SHORT** slqsSignalStrengthInfo::ltsnr
- 8.691.2.8 **struct rsrqInformation** slqsSignalStrengthInfo::rsrqInfo
- 8.691.2.9 **struct rxSignalStrengthListElement** slqsSignalStrengthInfo::rxSignalStrengthList[18]
- 8.691.2.10 **USHORT** slqsSignalStrengthInfo::rxSignalStrengthListLen
- 8.691.2.11 **USHORT** slqsSignalStrengthInfo::signalStrengthReqMask
- 8.691.2.12 **BYTE** slqsSignalStrengthInfo::sinr

## 8.692 SLQSSignalStrengthsIndReq Struct Reference

### Data Fields

- [BYTE rxSignalStrengthDelta](#)
- [BYTE ecioDelta](#)
- [BYTE ioDelta](#)
- [BYTE sinrDelta](#)
- [BYTE rsrqDelta](#)
- [BYTE ecioThresholdListLen](#)
- [SHORT ecioThresholdList](#) [10]
- [BYTE sinrThresholdListLen](#)
- [BYTE sinrThresholdList](#) [5]
- [WORD lteSnrDelta](#)
- [BYTE lteRsrpDelta](#)

### 8.692.1 Detailed Description

Structure for storing the input parameters passed for SLQSSetSignalStrengthsCallback by the user.

#### Parameters

<i>rxSignalStrengthDelta</i>	<ul style="list-style-type: none"> <li>• RSSI delta(in dBm) at which an event report indication, including the current RSSI, will be sent to the requesting control point.</li> </ul>
<i>ecioDelta</i>	<ul style="list-style-type: none"> <li>• ECIO delta at which an event report indication, ecioDelta including the current ECIO, will be sent to the requesting control point.</li> <li>• ECIO delta is an unsigned 1 byte value that increments in negative 0.5 dBm, e.g., ecio_delta of 2 means a change of -1 dBm.</li> </ul>

<i>ioDelta</i>	<ul style="list-style-type: none"> <li>IO delta (in dBm) at which an event report indication, ioDelta including the current IO, will be sent to the requesting control point.</li> </ul>
<i>sinrDelta</i>	<ul style="list-style-type: none"> <li>SINR delta level at which an event report indication, sinrDelta including the current SINR, will be sent to the requesting control point.</li> </ul>
<i>rsrqDelta</i>	<ul style="list-style-type: none"> <li>RSRQ delta level at which an event report indication, including the current RSRQ, will be sent to the requesting control point.</li> </ul>
<i>ecioThreshold-ListLen</i>	<ul style="list-style-type: none"> <li>Number of elements in the ECIO threshold list.</li> </ul>
<i>ecioThreshold-List</i>	<ul style="list-style-type: none"> <li>A sequence of thresholds delimiting Ecio event reporting bands. Every time a new Ecio value crosses a threshold value, an event report indication message with the new ECIO value is sent to the requesting control point. For this field: <ul style="list-style-type: none"> <li>Maximum number of threshold values is 10</li> <li>At least one value must be specified.</li> </ul> </li> </ul>
<i>sinrThreshold-ListLen</i>	<ul style="list-style-type: none"> <li>Number of elements in the SINR threshold list.</li> </ul>
<i>sinrThreshold-List</i>	<ul style="list-style-type: none"> <li>A sequence of thresholds delimiting SINR event reporting bands. Every time a new SINR value crosses a threshold value, an event report indication message with the new sinr value is sent to the requesting control point. For this field: <ul style="list-style-type: none"> <li>Maximum number of threshold values is 5</li> <li>At least one value must be specified.</li> </ul> </li> </ul>
<i>ltesnrdelta</i>	<ul style="list-style-type: none"> <li>LTE SNR delta level at which an event report indication, including the current SNR, will be sent to the requesting control point. LTE SNR delta level is an unsigned 2 byte value, representing the delta in units of 0.1 dB, e.g., lte_snr_delta of 3 means a change 0.3dB.</li> </ul>
<i>ltersrpdelta</i>	<ul style="list-style-type: none"> <li>-LTE RSRP delta level at which an event report -indication, including the current RSRP, will be sent -to the requesting control point. LTE RSRP delta -level is an unsigned 1 byte value, representing the -delta in dB.</li> </ul>

**Note**

None

**8.692.2 Field Documentation****8.692.2.1 BYTE SLQSSignalStrengthsIndReq::ecioDelta**



8.692.2.2 **SHORT** SLQSSignalStrengthsIndReq::ecioThresholdList[10]

8.692.2.3 **BYTE** SLQSSignalStrengthsIndReq::ecioThresholdListLen

8.692.2.4 **BYTE** SLQSSignalStrengthsIndReq::ioDelta

8.692.2.5 **BYTE** SLQSSignalStrengthsIndReq::lteRsrpDelta

8.692.2.6 **WORD** SLQSSignalStrengthsIndReq::lteSnrDelta

8.692.2.7 **BYTE** SLQSSignalStrengthsIndReq::rsrqDelta

8.692.2.8 **BYTE** SLQSSignalStrengthsIndReq::rxSignalStrengthDelta

8.692.2.9 **BYTE** SLQSSignalStrengthsIndReq::sinrDelta

8.692.2.10 **BYTE** SLQSSignalStrengthsIndReq::sinrThresholdList[5]

8.692.2.11 **BYTE** SLQSSignalStrengthsIndReq::sinrThresholdListLen

## 8.693 SLQSSignalStrengthsInformation Struct Reference

### Data Fields

- struct [rxSignalStrengthListElement](#) rxSignalStrengthInfo
- struct [ecioListElement](#) ecioInfo
- [ULONG](#) io
- [BYTE](#) sinr
- struct [errorRateListElement](#) errorRateInfo
- struct [rsrqInformation](#) rsrqInfo
- struct [lteSnrinformation](#) lteSnrinfo
- struct [lteRsrpinformation](#) lteRsrpinfo

### 8.693.1 Detailed Description

Structure for Received Signal Strength Information.

## Parameters

<i>rxSignalStrengthInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">rxSignalStrengthListElement</a> for more information.</li> </ul>
<i>ecioInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">ecioListElement</a> for more information.</li> </ul>
<i>io</i>	<ul style="list-style-type: none"> <li>• Received IO in dBm; IO is only applicable for 1xEV-DO.</li> </ul>
<i>sinr</i>	<ul style="list-style-type: none"> <li>• SINR level           <ul style="list-style-type: none"> <li>– SINR is only applicable for 1xEV-DO; valid levels are 0 to 8 where maximum value for 0 - SINR_LEVEL_0 is -9 dB 1 - SINR_LEVEL_1 is -6 dB 2 - SINR_LEVEL_2 is -4.5 dB 3 - SINR_LEVEL_3 is -3 dB 4 - SINR_LEVEL_4 is -2 dB 5 - SINR_LEVEL_5 is +1 dB 6 - SINR_LEVEL_6 is +3 dB 7 - SINR_LEVEL_7 is +6 dB 8 - SINR_LEVEL_8 is +9 dB</li> </ul> </li> </ul>
<i>errorRateInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">errorRateListElement</a> for more information.</li> </ul>
<i>rsrqInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">rsrqInformation</a> for more information.</li> </ul>
<i>lteSnrinfor</i>	<ul style="list-style-type: none"> <li>• See <a href="#">lteSnrinformation</a> for more information.</li> </ul>
<i>lteRsrpinfor</i>	<ul style="list-style-type: none"> <li>• See <a href="#">lteRsrpinformation</a> for more information.</li> </ul>

## Note

None

## 8.693.2 Field Documentation

8.693.2.1 struct `ecioListElement` `SLQSSignalStrengthsInformation::ecioInfo`8.693.2.2 struct `errorRateListElement` `SLQSSignalStrengthsInformation::errorRateInfo`8.693.2.3 `ULONG` `SLQSSignalStrengthsInformation::io`8.693.2.4 struct `lteRsrpinformation` `SLQSSignalStrengthsInformation::lteRsrpinfor`8.693.2.5 struct `lteSnrinformation` `SLQSSignalStrengthsInformation::lteSnrinfor`8.693.2.6 struct `rsrqInformation` `SLQSSignalStrengthsInformation::rsrqInfo`8.693.2.7 struct `rxSignalStrengthListElement` `SLQSSignalStrengthsInformation::rxSignalStrengthInfo`

8.693.2.8 BYTE SLQSSignalStrengthsInformation::sinr

## 8.694 slqsWdsEventInfo Struct Reference

### Data Fields

- [qaQmiInterfaceInfo](#) \* [pQmiInterfaceInfo](#)
- ULONG \* [pDormancyStatus](#)
- ULONG \* [pDataBearer](#)
- ULONG \* [pPacketsCountTX](#)
- ULONG \* [pPacketsCountRX](#)
- ULONGLONG \* [pTotalBytesTX](#)
- ULONGLONG \* [pTotalBytesRX](#)

### 8.694.1 Detailed Description

Contains the WDS event information and information about the interface

## Parameters

<i>pQmiInterface-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaQmiInterfaceInfo</a> for more information</li> </ul>
<i>pDataBearer,-</i>	<p>Data bearer technology (NULL if not present)</p> <ul style="list-style-type: none"> <li>• 0x00 - Indicates that this field is ignored</li> <li>• 0x01 - CDMA 1X</li> <li>• 0x02 - EV-DO Rev 0</li> <li>• 0x03 - GPRS</li> <li>• 0x04 - WCDMA</li> <li>• 0x05 - EV-DO Rev A</li> <li>• 0x06 - EDGE</li> <li>• 0x07 - HSDPA and WCDMA</li> <li>• 0x08 - WCDMA and HSUPA</li> <li>• 0x09 - HSDPA and HSUPA</li> <li>• 0x0A - LTE</li> <li>• 0x0B - EV-DO Rev A EHRPD</li> <li>• 0x0C - HSDPA+ and WCDMA</li> <li>• 0x0D - HSDPA+ and HSUPA</li> <li>• 0x0E - DC_HSDPA+ and WCDMA</li> <li>• 0x0F - DC_HSDPA+ and HSUPA</li> <li>• 0x8000 - NULL Bearer</li> <li>• 0xFF - Unknown Technology</li> </ul>
<i>pDormancy-Status</i>	<ul style="list-style-type: none"> <li>• Dormancy status (NULL if not present) <ul style="list-style-type: none"> <li>– 1 - traffic channel dormant</li> <li>– 2 - traffic channel active</li> </ul> </li> </ul>
<i>pPacketsCount-TX</i>	<ul style="list-style-type: none"> <li>• Packets transmitted without error (NULL if not present)</li> </ul>
<i>pPacketsCount-RX</i>	<ul style="list-style-type: none"> <li>• Packets received without error (NULL if not present)</li> </ul>

<i>pTotalBytesTX</i>	<ul style="list-style-type: none"> <li>Bytes transmitted without error (NULL if not present)</li> </ul>
<i>pTotalBytesRX</i>	<ul style="list-style-type: none"> <li>Bytes received without error (NULL if not present)</li> </ul>

## 8.694.2 Field Documentation

8.694.2.1 **ULONG\*** `slqsWdsEventInfo::pDataBearer`

8.694.2.2 **ULONG\*** `slqsWdsEventInfo::pDormancyStatus`

8.694.2.3 **ULONG\*** `slqsWdsEventInfo::pPacketsCountRX`

8.694.2.4 **ULONG\*** `slqsWdsEventInfo::pPacketsCountTX`

8.694.2.5 **qaQmiInterfaceInfo\*** `slqsWdsEventInfo::pQmiInterfaceInfo`

8.694.2.6 **ULONGLONG\*** `slqsWdsEventInfo::pTotalBytesRX`

8.694.2.7 **ULONGLONG\*** `slqsWdsEventInfo::pTotalBytesTX`

## 8.695 SMSAsyncRawSend\_s Struct Reference

### Data Fields

- [WORD](#) `sendStatus`
- [WORD](#) `messageID`
- [WORD](#) `causeCode`
- [BYTE](#) `errorClass`
- [WORD](#) `RPCause`
- [BYTE](#) `TPCause`
- [BYTE](#) `msgDelFailureType`
- [BYTE](#) `msgDelFailureCause`
- [BYTE](#) `alphaIDLen`
- [BYTE \\*](#) `pAlphaID`
- [ULONG](#) `userData`

### 8.695.1 Detailed Description

This structure contains SMS parameters

## Parameters

<i>sendStatus</i>	<ul style="list-style-type: none"> <li>• Send Status</li> <li>• Values: <ul style="list-style-type: none"> <li>– QMI_ERR_NONE – No error in the request</li> <li>– QMI_ERR_CAUSE_CODE - SMS cause code</li> <li>– QMI_ERR_MESSAGE_DELIVERY_FAILURE - Message could not be delivered</li> <li>– QMI_ERR_NO_MEMORY - Device could not allocate memory to formulate a response</li> </ul> </li> </ul>
<i>messageID</i>	<ul style="list-style-type: none"> <li>• Unique ID assigned by WMS for non-retry messages.</li> </ul>
<i>causeCode</i>	<ul style="list-style-type: none"> <li>• WMS cause code</li> </ul>
<i>errorClass</i>	<ul style="list-style-type: none"> <li>• Error Class</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - ERROR_CLASS_TEMPORARY</li> <li>– 0x01 - ERROR_CLASS_PERMANENT</li> </ul> </li> </ul>
<i>RPCause</i>	<ul style="list-style-type: none"> <li>• GW RP cause</li> </ul>
<i>TPCause</i>	<ul style="list-style-type: none"> <li>• GW TP Cause</li> </ul>
<i>msgDelFailure-Type</i>	<ul style="list-style-type: none"> <li>• Message delivery failure type</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - WMS_MESSAGE_DELIVERY_FAILURE_TEMPORARY</li> <li>– 0x01 - WMS_MESSAGE_DELIVERY_FAILURE_PERMANENT</li> </ul> </li> </ul>
<i>msgDelFailure-Cause</i>	<ul style="list-style-type: none"> <li>• Message delivery failure cause</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - WMS_MESSAGE_BLOCKED_DUE_TO_CALL_CONTROL</li> </ul> </li> </ul>

<i>alphaIDLen</i>	<ul style="list-style-type: none"> <li>Number of sets of the pAlphaID</li> </ul>
<i>pAlphaID</i>	<ul style="list-style-type: none"> <li>Alpha ID</li> </ul>
<i>userData</i>	<ul style="list-style-type: none"> <li>Identifies the request associated with this indication.</li> </ul>

## 8.695.2 Field Documentation

8.695.2.1 **BYTE** SMSAsyncRawSend\_s::alphaIDLen

8.695.2.2 **WORD** SMSAsyncRawSend\_s::causeCode

8.695.2.3 **BYTE** SMSAsyncRawSend\_s::errorClass

8.695.2.4 **WORD** SMSAsyncRawSend\_s::messageID

8.695.2.5 **BYTE** SMSAsyncRawSend\_s::msgDelFailureCause

8.695.2.6 **BYTE** SMSAsyncRawSend\_s::msgDelFailureType

8.695.2.7 **BYTE\*** SMSAsyncRawSend\_s::pAlphaID

8.695.2.8 **WORD** SMSAsyncRawSend\_s::RPCause

8.695.2.9 **WORD** SMSAsyncRawSend\_s::sendStatus

8.695.2.10 **BYTE** SMSAsyncRawSend\_s::TPCause

8.695.2.11 **ULONG** SMSAsyncRawSend\_s::userData

## 8.696 sMSCAddress Struct Reference

### Data Fields

- uint8\_t [length](#)
- uint8\_t [data](#) [256]

### 8.696.1 Detailed Description

#### Parameters

<i>length</i>	<ul style="list-style-type: none"> <li>Number of sets of following element</li> </ul>
---------------	---

<i>data</i>	<ul style="list-style-type: none"><li>• SMSC address</li></ul>
-------------	--

## 8.696.2 Field Documentation

8.696.2.1 `uint8_t sMSCAddress::data[256]`

8.696.2.2 `uint8_t sMSCAddress::length`

## 8.697 sMSCAddress Struct Reference

### Data Fields

- [BYTE length](#)
- [BYTE data](#) [256]

### 8.697.1 Detailed Description

This structure holds SMSC information

#### Parameters

<i>length</i>	<ul style="list-style-type: none"><li>• Number of sets of following element</li></ul>
<i>data</i>	<ul style="list-style-type: none"><li>• SMSC address</li></ul>

## 8.697.2 Field Documentation

8.697.2.1 `BYTE sMSCAddress::data[256]`

8.697.2.2 `BYTE sMSCAddress::length`

## 8.698 sMSCAddressTlv Struct Reference

### Data Fields

- `uint8_t TlvPresent`
- `sMSCAddressInfo sMSCInfo`



### 8.698.1 Detailed Description

#### Parameters

<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Boolean indicating the presence of the TLV in the QMI response</li> </ul>
<i>SMSCInfo</i>	<ul style="list-style-type: none"> <li>• SMSC Address</li> <li>• See <a href="#">sMSCAddressInfo</a> for more information</li> </ul>

### 8.698.2 Field Documentation

8.698.2.1 [sMSCAddressInfo](#) [sMSCAddressTlv::SMSCInfo](#)

8.698.2.2 [uint8\\_t](#) [sMSCAddressTlv::TlvPresent](#)

## 8.699 sMSEtwsMessage Struct Reference

#### Data Fields

- [uint8\\_t](#) [notificationType](#)
- [uint16\\_t](#) [length](#)
- [uint8\\_t](#) [data](#) [1254]

### 8.699.1 Detailed Description

#### Parameters

<i>notificationType</i>	<ul style="list-style-type: none"> <li>• Message mode 0x00 - Primary 0x01 - Secondary GSM 0x02 - Secondary UMTS</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>• Number of sets of following elements</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>• Raw message data</li> </ul>

### 8.699.2 Field Documentation

8.699.2.1 [uint8\\_t](#) [sMSEtwsMessage::data](#)[1254]

8.699.2.2 [uint16\\_t](#) [sMSEtwsMessage::length](#)

8.699.2.3 [uint8\\_t](#) [sMSEtwsMessage::notificationType](#)

## 8.700 SMSEtwsMessage Struct Reference

## Data Fields

- [BYTE notificationType](#)
- [WORD length](#)
- [BYTE data](#) [1254]

### 8.700.1 Detailed Description

This structure holds information related earthquake and Tsunami warning system

#### Parameters

<i>notificationType</i>	<ul style="list-style-type: none"> <li>• Message mode 0x00 - Primary 0x01 - Secondary GSM 0x02 - Secondary UMTS</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>• Number of sets of following elements</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>• Raw message data</li> </ul>

### 8.700.2 Field Documentation

8.700.2.1 **BYTE** SMSEtwsMessage::data[1254]

8.700.2.2 **WORD** SMSEtwsMessage::length

8.700.2.3 **BYTE** SMSEtwsMessage::notificationType

## 8.701 sMSEtwsMessageTlv Struct Reference

## Data Fields

- [uint8\\_t TlvPresent](#)
- [sMSEtwsMessageInfo](#) [EtwsMessageInfo](#)

### 8.701.1 Detailed Description

#### Parameters

<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Boolean indicating the presence of the TLV in the QMI response</li> </ul>
<i>EtwsMessage-Info</i>	<ul style="list-style-type: none"> <li>• ETWS Message</li> <li>• See <a href="#">sMSEtwsMessageInfo</a> for more information</li> </ul>

### 8.701.2 Field Documentation

8.701.2.1 sMSEtwsMessageInfo sMSEtwsMessageTlv::EtwsMessageInfo

8.701.2.2 uint8\_t sMSEtwsMessageTlv::TlvPresent

## 8.702 sMSEtwsPlmn Struct Reference

### Data Fields

- uint16\_t [mobileCountryCode](#)
- uint16\_t [mobileNetworkCode](#)

### 8.702.1 Detailed Description

#### Parameters

<i>mobileCountry-Code</i>	<ul style="list-style-type: none"><li>• 16 bit representation of MCC value range : 0 -999</li></ul>
<i>mobileNetwork-Code</i>	<ul style="list-style-type: none"><li>• 16 bit representation of MNC value range : 0 -999</li></ul>

### 8.702.2 Field Documentation

8.702.2.1 uint16\_t sMSEtwsPlmn::mobileCountryCode

8.702.2.2 uint16\_t sMSEtwsPlmn::mobileNetworkCode

## 8.703 SMSEtwsPlmn Struct Reference

### Data Fields

- [WORD mobileCountryCode](#)
- [WORD mobileNetworkCode](#)

### 8.703.1 Detailed Description

This structure holds information related ETWS PLMN

#### Parameters

<i>mobileCountry-Code</i>	<ul style="list-style-type: none"><li>• 16 bit representation of MCC value range : 0 -999</li></ul>
<i>mobileNetwork-Code</i>	<ul style="list-style-type: none"><li>• 16 bit representation of MNC value range : 0 -999</li></ul>

### 8.703.2 Field Documentation

8.703.2.1 WORD SMSEtwsPlmn::mobileCountryCode

## 8.703.2.2 WORD SMSEtwsPlmn::mobileNetworkCode

## 8.704 SMSEventInfo\_s Struct Reference

## Data Fields

- [BYTE smsEventType](#)
- [SMSMTMessageInfo](#) \* [pMTMessageInfo](#)
- [SMSTransferRouteMTMessageInfo](#) \* [pTransferRouteMTMessageInfo](#)
- [SMSMessageModeInfo](#) \* [pMessageModeInfo](#)
- [SMSEtwsMessageInfo](#) \* [pEtwsMessageInfo](#)
- [SMSEtwsPlmnInfo](#) \* [pEtwsPlmnInfo](#)
- [SMSCAddressInfo](#) \* [pSMSCAddressInfo](#)
- [SMSOnIMSInfo](#) \* [pSMSOnIMSInfo](#)

## 8.704.1 Detailed Description

This structure will hold the information related to received SMS events

## Parameters

<i>smsEventType</i>	<ul style="list-style-type: none"> <li>• Type of the SMS events that are received. This is a bit map of <a href="#">SMSEventType</a>. Only the parameters (which follows) related to the events received would be filled, and the rest of the parameters would be NULL</li> </ul>
<i>pMTMessage-Info</i>	<ul style="list-style-type: none"> <li>• pointer to the <a href="#">SMSMTMessageInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pTransferRoute-MTMessageInfo</i>	<ul style="list-style-type: none"> <li>• pointer to the <a href="#">SMSTransferRouteMTMessageInfo</a> structure . NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pMessageMode-Info</i>	<ul style="list-style-type: none"> <li>• pointer to the <a href="#">SMSMessageModeInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pEtwsMessage-Info</i>	<ul style="list-style-type: none"> <li>• pointer to the <a href="#">SMSEtwsMessageInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pEtwsPlmnInfo</i>	<ul style="list-style-type: none"> <li>• pointer to the <a href="#">SMSEtwsPlmnInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pSMSCAddress-Info</i>	<ul style="list-style-type: none"> <li>• pointer to the <a href="#">SMSCAddressInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>

<i>pSMSOnIMSInfo</i>	<ul style="list-style-type: none"> <li>pointer to the <a href="#">SMSOnIMSInfo</a> structure</li> <li>NULL, if this event is not present in the smsEventType parameter Note: None</li> </ul>
----------------------	--

## 8.704.2 Field Documentation

8.704.2.1 **SMSEtwsMessageInfo\*** **SMSEventInfo\_s::pEtwsMessageInfo**

8.704.2.2 **SMSEtwsPlmnInfo\*** **SMSEventInfo\_s::pEtwsPlmnInfo**

8.704.2.3 **SMSMessageModelInfo\*** **SMSEventInfo\_s::pMessageModelInfo**

8.704.2.4 **SMSMTMessageInfo\*** **SMSEventInfo\_s::pMTMessageInfo**

8.704.2.5 **SMSCAddressInfo\*** **SMSEventInfo\_s::pSMSCAddressInfo**

8.704.2.6 **SMSOnIMSInfo\*** **SMSEventInfo\_s::pSMSOnIMSInfo**

8.704.2.7 **SMSTransferRouteMTMessageInfo\*** **SMSEventInfo\_s::pTransferRouteMTMessageInfo**

8.704.2.8 **BYTE** **SMSEventInfo\_s::smsEventType**

## 8.705 smsMaxStorageSizeReq Struct Reference

### Data Fields

- [BYTE](#) *storageType*
- [BYTE](#) \* *pMessageMode*

### 8.705.1 Detailed Description

This structure contains get store max size resquest parameters

#### Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>SMS message storage type <ul style="list-style-type: none"> <li>0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>1 - NV</li> </ul> </li> </ul>
<i>pMessage-Mode(optional)</i>	parameter) <ul style="list-style-type: none"> <li>0x00 - CDMA, LTE (if network type is CDMA)</li> <li>0x01 - GW, LTE (if network type is UMTS)</li> </ul>

**Note**

The Message Mode TLV must be included if the device is capable of supporting more than one protocol

**8.705.2 Field Documentation**

8.705.2.1 **BYTE\*** smsMaxStorageSizeReq::pMessageMode

8.705.2.2 **BYTE** smsMaxStorageSizeReq::storageType

**8.706 smsMaxStorageSizeResp Struct Reference****Data Fields**

- [ULONG maxStorageSize](#)
- [ULONG freeSlots](#)

**8.706.1 Detailed Description**

This structure contains get store max size response parameters

**Parameters**

<i>maxStorageSize</i>	-	<ul style="list-style-type: none"> <li>• Memory Store Size</li> </ul>
<i>freeSlots</i>	-	<ul style="list-style-type: none"> <li>• Optional parameter indicating how much Memory is available</li> <li>• function <a href="#">SLQSSmsGetMaxStorageSize()</a> returns a default value 0xFFFFFFFF for parameter values if no response is received from the device.</li> </ul>

**8.706.2 Field Documentation**

8.706.2.1 **ULONG** smsMaxStorageSizeResp::freeSlots

8.706.2.2 **ULONG** smsMaxStorageSizeResp::maxStorageSize

**8.707 SMSMemoryInfo Struct Reference****Data Fields**

- [BYTE storageType](#)
- [BYTE messageMode](#)

**8.707.1 Detailed Description**

This structure holds information related to memory

## Parameters

<i>storageType</i>	<ul style="list-style-type: none"><li>Indicates the type of memory storage 0x00 - STORAGE_TYPE_UIM 0x01 - STORAGE_TYPE_NV</li></ul>
<i>messageMode</i>	<ul style="list-style-type: none"><li>Indicates the type of memory mode 0x00 - MESSAGE_MODE_CDMA - CDMA 0x01 - MESSAGE_MODE_GW - GW</li></ul>

## 8.707.2 Field Documentation

8.707.2.1 BYTE SMSMemoryInfo::messageMode

8.707.2.2 BYTE SMSMemoryInfo::storageType

## 8.708 sSMMessageMode Struct Reference

## Data Fields

- uint8\_t [messageMode](#)

## 8.708.1 Detailed Description

## Parameters

<i>messageMode</i>	Message Mode
--------------------	--------------

## 8.708.2 Field Documentation

8.708.2.1 uint8\_t sSMMessageMode::messageMode

## 8.709 SMSMessageMode Struct Reference

## Data Fields

- BYTE [messageMode](#)

## 8.709.1 Detailed Description

This structure holds information related to message mode

## Parameters

<i>messageMode</i>	<ul style="list-style-type: none"><li>Message mode 0x00 - CDMA 0x01 - GW</li></ul>
--------------------	--

## 8.709.2 Field Documentation

8.709.2.1 **BYTE** SMSMessageMode::messageMode

## 8.710 smsMsgprotocolResp Struct Reference

### Data Fields

- [BYTE msgProtocol](#)

### 8.710.1 Detailed Description

This structure contains get message protocol response parameters

#### Parameters

<i>msgProtocol</i>	-
	<ul style="list-style-type: none"> <li>• Message Protocol</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - MESSAGE_PROTOCOL_CDMA</li> <li>– 0x01 - MESSAGE_PROTOCOL_WCDMA</li> </ul> </li> </ul>

### 8.710.2 Field Documentation

8.710.2.1 **BYTE** smsMsgprotocolResp::msgProtocol

## 8.711 sMSMTMessage Struct Reference

### Data Fields

- uint32\_t [storageType](#)
- uint32\_t [messageIndex](#)

### 8.711.1 Detailed Description

#### Parameters

<i>storageType</i>	memory storage 0x00-UIM 0x01-NV
<i>messageIndex</i>	MT Message index

### 8.711.2 Field Documentation

8.711.2.1 **uint32\_t** sMSMTMessage::messageIndex

8.711.2.2 **uint32\_t** sMSMTMessage::storageType

## 8.712 SMSMTMessage Struct Reference

### Data Fields

- [ULONG storageType](#)



- [ULONG messageIndex](#)

### 8.712.1 Detailed Description

This structure holds information related to MT SMS

#### Parameters

<i>storageType</i>	<ul style="list-style-type: none"><li>• SMS message storage type for the new message 0 - UIM 1 - NV</li></ul>
<i>messageIndex</i>	<ul style="list-style-type: none"><li>• Index of the new message</li></ul>

### 8.712.2 Field Documentation

8.712.2.1 [ULONG SMSMTMessage::messageIndex](#)

8.712.2.2 [ULONG SMSMTMessage::storageType](#)

## 8.713 sMSOnIMS Struct Reference

### Data Fields

- [uint8\\_t smsOnIMS](#)

### 8.713.1 Detailed Description

#### Parameters

<i>smsOnIMS</i>	SMS on IMS
-----------------	------------

### 8.713.2 Field Documentation

8.713.2.1 [uint8\\_t sMSOnIMS::smsOnIMS](#)

## 8.714 SMSOnIMS Struct Reference

### Data Fields

- [BYTE smsOnIMS](#)

### 8.714.1 Detailed Description

This structure holds information related to message mode

## Parameters

<i>smsOnIMS</i>	<ul style="list-style-type: none"> <li>Indicates whether the message is received from IMS 0x00 - Message is not received from IMS 0x01 - Message is received from IMS 0x02-0xFF - Reserved Note: In multiple modem solutions, this TLV may be used to help the client determine with which modem to communicate. This TLV may not be supported on all implementations.</li> </ul>
-----------------	---

## 8.714.2 Field Documentation

## 8.714.2.1 BYTE SMSOnIMS::smsOnIMS

## 8.715 sMSOnIMSTlv Struct Reference

## Data Fields

- [uint8\\_t TlvPresent](#)
- [sMSOnIMSInfo IMSInfo](#)

## 8.715.1 Detailed Description

## Parameters

<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>Boolean indicating the presence of the TLV in the QMI response</li> </ul>
<i>IMSInfo</i>	<ul style="list-style-type: none"> <li>SMS on IMS</li> <li>See <a href="#">sMSOnIMSInfo</a> for more information</li> </ul>

## 8.715.2 Field Documentation

## 8.715.2.1 sMSOnIMSInfo sMSOnIMSTlv::IMSInfo

## 8.715.2.2 uint8\_t sMSOnIMSTlv::TlvPresent

## 8.716 smsRouteEntry Struct Reference

## Data Fields

- [BYTE messageType](#)
- [BYTE messageClass](#)
- [BYTE routeStorage](#)
- [BYTE receiptAction](#)

## 8.716.1 Detailed Description

This structure contains SMS route entry details

## Parameters

<i>messageType</i>	- <ul style="list-style-type: none"> <li>• Message type matching this route</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - MESSAGE_TYPE_POINT_TO_POINT</li> </ul> </li> </ul>
<i>messageClass</i>	- <ul style="list-style-type: none"> <li>• Message Class</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - MESSAGE_CLASS_0</li> <li>– 0x01 - MESSAGE_CLASS_1</li> <li>– 0x02 - MESSAGE_CLASS_2</li> <li>– 0x03 - MESSAGE_CLASS_3</li> <li>– 0x04 - MESSAGE_CLASS_NONE</li> <li>– 0x05 - MESSAGE_CLASS_CDMA</li> </ul> </li> </ul>
<i>routeStorage</i>	- <ul style="list-style-type: none"> <li>• If the receiptAction is store where to store the message</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - STORAGE_TYPE_UIM</li> <li>– 0x01 - STORAGE_TYPE_NV</li> <li>– 0xFF - STORAGE_TYPE_NONE</li> </ul> </li> </ul>
<i>receiptAction</i>	- <ul style="list-style-type: none"> <li>• Action to be taken on receipt of a message matching the specified type and class for this route</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - DISCARD (discarded without notification)</li> <li>– 0x01 - STORE AND NOTIFY (stored and notified to the registered clients)</li> <li>– 0x02 - TRANSFER ONLY (transferred to the client, client expected to send the ACK)</li> <li>– 0x03 - TRANSFER AND ACK (transferred to the client, device expected to send the ACK)</li> </ul> </li> </ul>

## 8.716.2 Field Documentation

8.716.2.1 BYTE smsRouteEntry::messageClass

8.716.2.2 BYTE smsRouteEntry::messageType

8.716.2.3 BYTE smsRouteEntry::receiptAction

8.716.2.4 BYTE smsRouteEntry::routeStorage

## 8.717 smsSetRoutesReq Struct Reference

### Data Fields

- [WORD](#) [numOfRoutes](#)
- [smsRouteEntry](#) [routeList](#) [0x0A]
- [BYTE](#) \* [pTransferStatusReport](#)

### 8.717.1 Detailed Description

This structure contains SMS route request parameters

#### Parameters

<i>numOfRoutes</i>	- <ul style="list-style-type: none"><li>• Number of sets of the following element</li></ul>
<i>routeList</i>	- <ul style="list-style-type: none"><li>• Array containing the set of <a href="#">smsRouteEntry</a></li></ul>
<i>pTransferStatus-Report</i>	- <ul style="list-style-type: none"><li>• 0x01 - Status reoprt are transferred to the client (optional)</li></ul>

### 8.717.2 Field Documentation

8.717.2.1 **WORD** [smsSetRoutesReq::numOfRoutes](#)

8.717.2.2 **BYTE\*** [smsSetRoutesReq::pTransferStatusReport](#)

8.717.2.3 [smsRouteEntry](#) [smsSetRoutesReq::routeList](#)[0x0A]

## 8.718 sMSTransferRouteMTMessage Struct Reference

### Data Fields

- [uint8\\_t](#) [ackIndicator](#)
- [uint32\\_t](#) [transactionID](#)
- [uint8\\_t](#) [format](#)
- [uint16\\_t](#) [length](#)
- [uint8\\_t](#) [data](#) [256]

### 8.718.1 Detailed Description

#### Parameters

<i>ackIndicator</i>	<ul style="list-style-type: none"> <li>Parameter to indicate if ACK must be sent by the control point 0x00 - Send ACK 0x01 - Do not send ACK</li> </ul>
<i>transactionID</i>	<ul style="list-style-type: none"> <li>Transaction ID of the message</li> </ul>
<i>format</i>	<ul style="list-style-type: none"> <li>Message format 0x00 - CDMA 0x02 - 0x05 - Reserved 0x06 - GW_PP 0x07 - GW_BC</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>Length of the raw message. This length should not exceed the maximum WMS payload length of 256 bytes</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>Raw message data</li> </ul>

### 8.718.2 Field Documentation

8.718.2.1 `uint8_t sMSTransferRouteMTMessage::ackIndicator`

8.718.2.2 `uint8_t sMSTransferRouteMTMessage::data[256]`

8.718.2.3 `uint8_t sMSTransferRouteMTMessage::format`

8.718.2.4 `uint16_t sMSTransferRouteMTMessage::length`

8.718.2.5 `uint32_t sMSTransferRouteMTMessage::transactionID`

## 8.719 SMSTransferRouteMTMessage Struct Reference

#### Data Fields

- [BYTE](#) `ackIndicator`
- [ULONG](#) `transactionID`
- [BYTE](#) `format`
- [WORD](#) `length`
- [BYTE](#) `data` [256]

### 8.719.1 Detailed Description

This structure holds information related to transfer route MT SMS

## Parameters

<i>ackIndicator</i>	<ul style="list-style-type: none"> <li>Parameter to indicate if ACK must be sent by the control point 0x00 - Send ACK 0x01 - Do not send ACK</li> </ul>
<i>transactionID</i>	<ul style="list-style-type: none"> <li>Transaction ID of the message</li> </ul>
<i>format</i>	<ul style="list-style-type: none"> <li>Message format 0x00 - CDMA 0x02 - 0x05 - Reserved 0x06 - GW_PP 0x07 - GW_BC</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>Length of the raw message. This length should not exceed the maximum WMS payload length of 256 bytes</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>Raw message data</li> </ul>

## 8.719.2 Field Documentation

8.719.2.1 BYTE SMSTransferRouteMTMessage::ackIndicator

8.719.2.2 BYTE SMSTransferRouteMTMessage::data[256]

8.719.2.3 BYTE SMSTransferRouteMTMessage::format

8.719.2.4 WORD SMSTransferRouteMTMessage::length

8.719.2.5 ULONG SMSTransferRouteMTMessage::transactionID

## 8.720 sQosFlowStat Struct Reference

## Data Fields

- [ULONG bearerId](#)
- [ULONG tx\\_pkt](#)
- [ULONG tx\\_pkt\\_drp](#)
- [ULONGLONG tx\\_bytes](#)
- [ULONGLONG tx\\_bytes\\_drp](#)

## 8.720.1 Detailed Description

This structure contains the Data statistic per QoS flow

## Parameters

<i>bearerId</i>	<ul style="list-style-type: none"> <li>Bearer ID</li> </ul>
-----------------	---

<i>tx_pkt</i>	<ul style="list-style-type: none"> <li>• number of sent packets for the QoS flow ID</li> </ul>
<i>tx_pkt_drp</i>	<ul style="list-style-type: none"> <li>• number of dropped(TX) packets for the QoS flow ID</li> </ul>
<i>tx_bytes</i>	<ul style="list-style-type: none"> <li>• number of sent bytes for the QoS flow ID</li> </ul>
<i>tx_bytes_drp</i>	<ul style="list-style-type: none"> <li>• number of dropped(TX) bytes for the QoS flow ID</li> </ul>

## 8.720.2 Field Documentation

8.720.2.1 **ULONG** sQosFlowStat::bearerId

8.720.2.2 **ULONGLONG** sQosFlowStat::tx\_bytes

8.720.2.3 **ULONGLONG** sQosFlowStat::tx\_bytes\_drp

8.720.2.4 **ULONG** sQosFlowStat::tx\_pkt

8.720.2.5 **ULONG** sQosFlowStat::tx\_pkt\_drp

## 8.721 sQosStat Struct Reference

### Data Fields

- [ULONG](#) apnId
- [ULONG](#) total\_tx\_pkt
- [ULONG](#) total\_tx\_pkt\_drp
- [ULONG](#) total\_rx\_pkt
- [ULONGLONG](#) total\_tx\_bytes
- [ULONGLONG](#) total\_tx\_bytes\_drp
- [ULONGLONG](#) total\_rx\_bytes
- [ULONG](#) numQosFlow
- [sQosFlowStat](#) qosFlow [(10)]

### 8.721.1 Detailed Description

This structure contains the Data statistic per QoS flow

#### Parameters

<i>apnId</i>	<ul style="list-style-type: none"> <li>• APN id</li> <li>• ID identifying the connected APN that the client would like to query the data statistic for</li> </ul>
--------------	---

<i>total_tx_pkt</i>	<ul style="list-style-type: none"> <li>• sum of all packets sent</li> </ul>
<i>total_tx_pkt_drp</i>	<ul style="list-style-type: none"> <li>• sum of all(TX) packets dropped</li> </ul>
<i>total_rx_pkt</i>	<ul style="list-style-type: none"> <li>• sum of all packets received</li> </ul>
<i>total_tx_bytes</i>	<ul style="list-style-type: none"> <li>• sum of all bytes sent</li> </ul>
<i>total_tx_bytes_drp</i>	<ul style="list-style-type: none"> <li>• sum of all(TX) bytes dropped</li> </ul>
<i>total_rx_bytes</i>	<ul style="list-style-type: none"> <li>• number of received bytes for the QoS flow ID</li> </ul>
<i>numQosFlow</i>	<ul style="list-style-type: none"> <li>• pointer to number of QoS flow Stat</li> </ul>
<i>qosFlow[MAX_QOS_SPEC_PER_APN]</i>	<ul style="list-style-type: none"> <li>• Data statistic per QoS flow</li> <li>• See <a href="#">sQosFlowStat</a> for more information</li> <li>• See <a href="#">MAX_QOS_SPEC_PER_APN</a> for more information</li> </ul>

## 8.721.2 Field Documentation

8.721.2.1 **ULONG** sQosStat::apnId

8.721.2.2 **ULONG** sQosStat::numQosFlow

8.721.2.3 **sQosFlowStat** sQosStat::qosFlow[(10)]

8.721.2.4 **ULONGLONG** sQosStat::total\_rx\_bytes

8.721.2.5 **ULONG** sQosStat::total\_rx\_pkt

8.721.2.6 **ULONGLONG** sQosStat::total\_tx\_bytes

8.721.2.7 **ULONGLONG** sQosStat::total\_tx\_bytes\_drp

8.721.2.8 **ULONG** sQosStat::total\_tx\_pkt

8.721.2.9 **ULONG** sQosStat::total\_tx\_pkt\_drp

## 8.722 SrvStatusInfo Struct Reference



## Data Fields

- [BYTE srvStatus](#)
- [BYTE isPrefDataPath](#)

## 8.722.1 Detailed Description

Structure for storing the service status information for CDMA and HDR networks.

## Parameters

<i>srvStatus</i>	<ul style="list-style-type: none"> <li>• Service status of the system. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Limited service</li> <li>– 0x02 - Service</li> <li>– 0x03 - Limited regional service</li> <li>– 0x04 - Power save</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>isPrefDataPath</i>	<ul style="list-style-type: none"> <li>• Whether the RAT is the preferred data path. <ul style="list-style-type: none"> <li>– 0x00 - Not preferred</li> <li>– 0x01 - Preferred</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

## 8.722.2 Field Documentation

## 8.722.2.1 BYTE SrvStatusInfo::isPrefDataPath

## 8.722.2.2 BYTE SrvStatusInfo::srvStatus

## 8.723 ssdatasession\_params Struct Reference

## Data Fields

- [BOOL action](#)
- [BYTE instanceId](#)
- [ULONG \\* pTechnology](#)
- [ULONG \\* pProfileId3GPP](#)
- [ULONG \\* pProfileId3GPP2](#)
- [ULONG sessionId](#)
- [ULONG failureReason](#)
- [ULONG failureReasonv4](#)
- [ULONG failureReasonv6](#)
- [ULONG rcv4](#)
- [ULONG rcv6](#)
- [ULONG v4sessionId](#)

- [ULONG v6sessionId](#)
- [BYTE ipfamily](#)
- [ULONG \\* pAuthentication](#)
- [CHAR \\* pUsername](#)
- [CHAR \\* pPassword](#)
- [ULONG verbFailReasonType](#)
- [ULONG verbFailReason](#)

### 8.723.1 Detailed Description

This structure contains the start/stop data session params Information

#### Parameters

<i>action</i>	<ul style="list-style-type: none"> <li>• 1 - Start Session</li> <li>• 0 - Stop Session</li> </ul>
<i>pTechnology</i>	<ul style="list-style-type: none"> <li>• Indicates the technology preference (optional) <ul style="list-style-type: none"> <li>– 1 - UMTS</li> <li>– 2 - CDMA</li> <li>– 3 - eMBMS</li> <li>– 4 - Modem Link Label. Modem Link is an interface for transferring data between entities on AP and modem.</li> </ul> </li> </ul>
<i>pProfileId3GPP</i>	<ul style="list-style-type: none"> <li>• configured 3GPP profile identifier</li> </ul>
<i>pProfileId3GPP2</i>	<ul style="list-style-type: none"> <li>• configured 3GPP2 profile identifier</li> </ul>
<i>sessionId</i> [IN\OUT]	<ul style="list-style-type: none"> <li>• [IN] - Passed session ID when stopping the data session</li> <li>• [OUT] - Assigned session ID when starting a data session</li> </ul>
<i>failureReason</i>	<ul style="list-style-type: none"> <li>• Reason data session failed to be established</li> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason</li> </ul>
<i>failureReasonv4</i>	<ul style="list-style-type: none"> <li>• Reason v4 data session failed to be established</li> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason</li> </ul>

<i>failureReasonv6</i>	<ul style="list-style-type: none"> <li>Reason v6 data session failed to be established</li> <li>See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason</li> </ul>
<i>rc4</i>	<ul style="list-style-type: none"> <li>v4 result code</li> <li>See <a href="#">qmerrno.h</a></li> </ul>
<i>rc6</i>	<ul style="list-style-type: none"> <li>v6 result code</li> <li>See <a href="#">qmerrno.h</a></li> </ul>
<i>v4sessionId</i>	<ul style="list-style-type: none"> <li>Do not modify - used for internal management of data sessions</li> <li>Non zero value indicates that a session is active</li> </ul>
<i>v6sessionId</i>	<ul style="list-style-type: none"> <li>Do not modify - used for internal management of data sessions</li> <li>Non zero value indicates that a session is active</li> </ul>
<i>ipfamily</i>	<ul style="list-style-type: none"> <li>4 for an IPv4 data session</li> <li>6 for an IPv6 data session</li> <li>7 for an IPv4v6 data session</li> </ul>
<i>pAuthentication</i>	<ul style="list-style-type: none"> <li>Authentication type, it can be PAP or CHAP</li> </ul>
<i>pUsername</i>	<ul style="list-style-type: none"> <li>username for authentication process</li> </ul>
<i>pPassword</i>	<ul style="list-style-type: none"> <li>password for authentication process</li> </ul>
<i>verbFailReason-Type</i>	<ul style="list-style-type: none"> <li>Parameter describing type of verbose failure reason</li> <li>See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason Type</li> </ul>
<i>verbFailReason</i>	<ul style="list-style-type: none"> <li>Verbose reason explaining why call failed. Depends on verbFailReasonType parameter</li> <li>See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason</li> </ul>

## 8.723.2 Field Documentation

### 8.723.2.1 BOOL ssdatasession\_params::action

- 8.723.2.2 **ULONG** ssdatasession\_params::failureReason
- 8.723.2.3 **ULONG** ssdatasession\_params::failureReasonv4
- 8.723.2.4 **ULONG** ssdatasession\_params::failureReasonv6
- 8.723.2.5 **BYTE** ssdatasession\_params::instanceId
- 8.723.2.6 **BYTE** ssdatasession\_params::ipfamily
- 8.723.2.7 **ULONG\*** ssdatasession\_params::pAuthentication
- 8.723.2.8 **CHAR\*** ssdatasession\_params::pPassword
- 8.723.2.9 **ULONG\*** ssdatasession\_params::pProfileId3GPP
- 8.723.2.10 **ULONG\*** ssdatasession\_params::pProfileId3GPP2
- 8.723.2.11 **ULONG\*** ssdatasession\_params::pTechnology
- 8.723.2.12 **CHAR\*** ssdatasession\_params::pUsername
- 8.723.2.13 **ULONG** ssdatasession\_params::rcv4
- 8.723.2.14 **ULONG** ssdatasession\_params::rcv6
- 8.723.2.15 **ULONG** ssdatasession\_params::sessionId
- 8.723.2.16 **ULONG** ssdatasession\_params::v4sessionId
- 8.723.2.17 **ULONG** ssdatasession\_params::v6sessionId
- 8.723.2.18 **ULONG** ssdatasession\_params::verbFailReason
- 8.723.2.19 **ULONG** ssdatasession\_params::verbFailReasonType

## 8.724 SupportedMsgList Struct Reference

### Data Fields

- [WORD supportedMsgLen](#)
- [BYTE supportedMsgs](#) [256]

### 8.724.1 Detailed Description

This structure contains the Supported Messages List Information

#### Parameters

<i>supportedMsgLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the supported messages</li> </ul>
------------------------	--

<i>supportedMsgs</i>	<ul style="list-style-type: none"><li>• Array of uint8 is a bitmask where each bit represents a message ID.</li><li>• Starting with the LSB, bit 0 represents message ID 0, bit 1 represents message ID 1.</li></ul>
----------------------	--

## 8.724.2 Field Documentation

### 8.724.2.1 WORD SupportedMsgList::supportedMsgLen

### 8.724.2.2 BYTE SupportedMsgList::supportedMsgs[256]

## 8.725 SUPSInfo Struct Reference

### Data Fields

- [BYTE svcType](#)
- [BYTE isModByCC](#)

### 8.725.1 Detailed Description

This structure contains information about the Supplementary Services.

#### Parameters

<i>svcType</i>	<ul style="list-style-type: none"><li>• Service type.<ul style="list-style-type: none"><li>– 0x01 - SERVICE_TYPE_ACTIVATE - Activate</li><li>– 0x02 - SERVICE_TYPE_DEACTIVATE - Deactivate</li><li>– 0x03 - SERVICE_TYPE_REGISTER - Register</li><li>– 0x04 - SERVICE_TYPE_ERASE - Erase</li><li>– 0x05 - SERVICE_TYPE_INTERROGATE - Interrogate</li><li>– 0x06 - SERVICE_TYPE_REGISTER_PASSWORD - Register password</li><li>– 0x07 - SERVICE_TYPE_USSD - USSD</li></ul></li></ul>
----------------	--

<i>isModByCC</i>	<ul style="list-style-type: none"><li>• Indicates whether the supplementary service data is modified by the card (SIM/USIM) as part of the call control:<ul style="list-style-type: none"><li>– 0 - False</li><li>– 1 - True</li></ul></li></ul>
------------------	--

## 8.725.2 Field Documentation

### 8.725.2.1 BYTE SUPSInfo::isModByCC

### 8.725.2.2 BYTE SUPSInfo::svcType

## 8.726 SV Struct Reference

### Data Fields

- [WORD id](#)
- [ULONG system](#)
- [BYTE mask](#)

### 8.726.1 Detailed Description

This structure contains the Delete [SV](#) Info

## Parameters

<i>id</i>	<ul style="list-style-type: none"> <li>• <a href="#">SV</a> ID of the satellite whose data is to be deleted</li> <li>• Range: <ul style="list-style-type: none"> <li>– For GPS: 1 to 32</li> <li>– For SBAS: 33 to 64</li> <li>– For GLONASS: 65 to 96</li> </ul> </li> </ul>
<i>system</i>	<ul style="list-style-type: none"> <li>• Indicates to which constellation this <a href="#">SV</a> belongs</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– eQMI_LOC_SV_SYSTEM_GPS (1) - GPS satellite</li> <li>– eQMI_LOC_SV_SYSTEM_GALILEO (2) - GALILEO satellite</li> <li>– eQMI_LOC_SV_SYSTEM_SBAS (3) - SBAS satellite</li> <li>– eQMI_LOC_SV_SYSTEM_COMPASS (4) - COMPASS satellite</li> <li>– eQMI_LOC_SV_SYSTEM_GLONASS (5) - GLONASS satellite</li> <li>– eQMI_LOC_SV_SYSTEM_BDS (6) - BDS satellite</li> </ul> </li> </ul>
<i>mask</i>	<ul style="list-style-type: none"> <li>• Indicates if the ephemeris or almanac for a satellite is to be deleted</li> <li>• Valid values: <ul style="list-style-type: none"> <li>– 0x01 - DELETE_EPHEMERIS</li> <li>– 0x02 - DELETE_ALMANAC</li> </ul> </li> </ul>

## 8.726.2 Field Documentation

## 8.726.2.1 WORD SV::id

## 8.726.2.2 BYTE SV::mask

## 8.726.2.3 ULONG SV::system

## 8.727 SVInfo Struct Reference

## Data Fields

- [BYTE](#) len
- [SV](#) \* pSV

## 8.727.1 Detailed Description

This structure contains the elements of Delete [SV](#) Info

## Parameters

<i>len</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements in struct <a href="#">SV</a>: <ul style="list-style-type: none"> <li>gnssSvId</li> <li>system</li> <li>deleteSvInfoMask</li> </ul> </li> </ul>
<i>pSV</i>	<ul style="list-style-type: none"> <li>Pointer to struct <a href="#">SV</a>. See <a href="#">SV</a> for more information</li> </ul>

## 8.727.2 Field Documentation

## 8.727.2.1 BYTE SVInfo::len

## 8.727.2.2 SV\* SVInfo::pSV

## 8.728 svUsedforFix\_s Struct Reference

## Data Fields

- [BYTE gnssSvUsedList\\_len](#)
- [WORD gnssSvUsedList](#) [255]

## 8.728.1 Detailed Description

This structure contains SVs Used to Calculate the Fix.

## Parameters

<i>gnssSvUsedList_len</i>	<ul style="list-style-type: none"> <li>Number of sets of gnssSvUsedList</li> </ul>
<i>pGnssSvUsedList</i>	<ul style="list-style-type: none"> <li>Entry in the list contains the <a href="#">SV</a> ID of a satellite used for calculating this position report.</li> <li>Following information is associated with each <a href="#">SV</a> ID: <ul style="list-style-type: none"> <li>GPS - 1 to 32</li> <li>SBAS - 33 to 64</li> <li>GLONASS - 65 to 96</li> <li>QZSS - 193 to 197</li> <li>BDS - 201 to 237</li> </ul> </li> </ul>



## 8.728.2 Field Documentation

8.728.2.1 WORD svUsedforFix\_s::gnssSvUsedList[255]

8.728.2.2 BYTE svUsedforFix\_s::gnssSvUsedList\_len

## 8.729 SWI\_STRUCT\_CarrierImage Struct Reference

### Data Fields

- [ULONG m\\_nCarrierId](#)
- [ULONG m\\_nFolderId](#)
- [ULONG m\\_nStorage](#)
- [BYTE m\\_FwImageId](#) [16]
- [BYTE m\\_FwBuildId](#) [100]
- [BYTE m\\_PriImageId](#) [16]
- [BYTE m\\_PriBuildId](#) [100]

### 8.729.1 Detailed Description

This structure contains the Carrier Image parameters.

#### Parameters

<i>m_nCarrierId</i>	<ul style="list-style-type: none"> <li>• Unique numeric carrier ID indicating the carrier that the following images belong to</li> </ul>
<i>m_nFolderId</i>	<ul style="list-style-type: none"> <li>• Unique numeric folder ID indicating the folder where the images should reside on the host storage.</li> </ul>
<i>m_nStorage</i>	<ul style="list-style-type: none"> <li>• Information of storage type</li> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Device</li> <li>– 1 - Host</li> </ul> </li> </ul>
<i>m_FwImageId</i>	<ul style="list-style-type: none"> <li>• Firmware image ID</li> </ul>
<i>m_FwBuildId</i>	<ul style="list-style-type: none"> <li>• Firmware build ID</li> </ul>
<i>m_PriImageId</i>	<ul style="list-style-type: none"> <li>• PRI image ID</li> </ul>

<i>m_PriBuildId</i>	<ul style="list-style-type: none"> <li>• PRI build ID</li> </ul>
---------------------	--

## 8.729.2 Field Documentation

8.729.2.1 BYTE SWI\_STRUCT\_CarrierImage::m\_FwBuildId[100]

8.729.2.2 BYTE SWI\_STRUCT\_CarrierImage::m\_FwImageld[16]

8.729.2.3 ULONG SWI\_STRUCT\_CarrierImage::m\_nCarrierId

8.729.2.4 ULONG SWI\_STRUCT\_CarrierImage::m\_nFolderId

8.729.2.5 ULONG SWI\_STRUCT\_CarrierImage::m\_nStorage

8.729.2.6 BYTE SWI\_STRUCT\_CarrierImage::m\_PriBuildId[100]

8.729.2.7 BYTE SWI\_STRUCT\_CarrierImage::m\_PrImageld[16]

## 8.730 SwiLocGetAutoStartResp Struct Reference

### Data Fields

- [BYTE function](#)
- [BOOL function\\_reported](#)
- [BYTE fix\\_type](#)
- [BOOL fix\\_type\\_reported](#)
- [BYTE max\\_time](#)
- [BOOL max\\_time\\_reported](#)
- [ULONG max\\_dist](#)
- [BOOL max\\_dist\\_reported](#)
- [ULONG fix\\_rate](#)
- [BOOL fix\\_rate\\_reported](#)

### 8.730.1 Detailed Description

This structure contains SWI LOC Get Auto Start setting

#### Parameters

<i>function</i>	<ul style="list-style-type: none"> <li>• Setting to indicate when modem should start an automatic GNSS fix <ul style="list-style-type: none"> <li>– 0 - disabled</li> <li>– 1 - At bootup</li> <li>– 2 - When NMEA port is opened</li> </ul> </li> </ul>
-----------------	--

<i>function_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
<i>fix_type</i>	<ul style="list-style-type: none"> <li>• Type of GNSS fix: <ul style="list-style-type: none"> <li>– 1 - Default Engine mode</li> <li>– 2 - MS-Based</li> <li>– 3 - MS-Assisted</li> <li>– 4 - Standalone</li> </ul> </li> </ul>
<i>fix_type_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
<i>max_time</i>	<ul style="list-style-type: none"> <li>• Maximum time allowed for the receiver to get a fix in seconds</li> <li>• Valid range: 1-255</li> </ul>
<i>max_time_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
<i>max_dist</i>	<ul style="list-style-type: none"> <li>• Maximum uncertainty of a fix measured by distance in meters</li> <li>• Valid range: 1 - 4294967280</li> </ul>
<i>max_dist_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
<i>fix_rate</i>	<ul style="list-style-type: none"> <li>• Time between fixes in seconds</li> <li>• Valid range: 1–65535</li> </ul>
<i>fix_rate_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>

## 8.730.2 Field Documentation

### 8.730.2.1 ULONG SwiLocGetAutoStartResp::fix\_rate

### 8.730.2.2 BOOL SwiLocGetAutoStartResp::fix\_rate\_reported

8.730.2.3 **BYTE** SwiLocGetAutoStartResp::fix\_type

8.730.2.4 **BOOL** SwiLocGetAutoStartResp::fix\_type\_reported

8.730.2.5 **BYTE** SwiLocGetAutoStartResp::function

8.730.2.6 **BOOL** SwiLocGetAutoStartResp::function\_reported

8.730.2.7 **ULONG** SwiLocGetAutoStartResp::max\_dist

8.730.2.8 **BOOL** SwiLocGetAutoStartResp::max\_dist\_reported

8.730.2.9 **BYTE** SwiLocGetAutoStartResp::max\_time

8.730.2.10 **BOOL** SwiLocGetAutoStartResp::max\_time\_reported

## 8.731 SwiLocSetAutoStartReq Struct Reference

### Data Fields

- [BYTE function](#)
- [BOOL set\\_function](#)
- [BYTE fix\\_type](#)
- [BOOL set\\_fix\\_type](#)
- [BYTE max\\_time](#)
- [BOOL set\\_max\\_time](#)
- [ULONG max\\_dist](#)
- [BOOL set\\_max\\_dist](#)
- [ULONG fix\\_rate](#)
- [BOOL set\\_fix\\_rate](#)

### 8.731.1 Detailed Description

This structure contains SWI LOC Get Auto Start setting

#### Parameters

<i>function</i>	<ul style="list-style-type: none"><li>• Setting to indicate when modem should start an automatic GNSS fix<ul style="list-style-type: none"><li>– 0 - disabled</li><li>– 1 - At bootup</li><li>– 2 - When NMEA port is opened</li></ul></li></ul>
-----------------	--

<i>set_function</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
<i>fix_type</i>	<ul style="list-style-type: none"> <li>• Type of GNSS fix: <ul style="list-style-type: none"> <li>– 1 - Default Engine mode</li> <li>– 2 - MS-Based</li> <li>– 3 - MS-Assisted</li> <li>– 4 - Standalone</li> </ul> </li> </ul>
<i>set_fix_type</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
<i>max_time</i>	<ul style="list-style-type: none"> <li>• Maximum time allowed for the receiver to get a fix in seconds</li> <li>• Valid range: 1-255</li> </ul>
<i>set_max_time</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
<i>max_dist</i>	<ul style="list-style-type: none"> <li>• Maximum uncertainty of a fix measured by distance in meters</li> <li>• Valid range: 1 - 4294967280</li> </ul>
<i>set_max_dist</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>
<i>fix_rate</i>	<ul style="list-style-type: none"> <li>• Time between fixes in seconds</li> <li>• Valid range: 1–65535</li> </ul>
<i>set_fix_rate</i>	<ul style="list-style-type: none"> <li>• 0 - do not set to modem</li> <li>• 1 - set to modem</li> </ul>

## 8.731.2 Field Documentation

### 8.731.2.1 ULONG SwiLocSetAutoStartReq::fix\_rate

### 8.731.2.2 BYTE SwiLocSetAutoStartReq::fix\_type

- 8.731.2.3 **BYTE** `SwiLocSetAutoStartReq::function`
- 8.731.2.4 **ULONG** `SwiLocSetAutoStartReq::max_dist`
- 8.731.2.5 **BYTE** `SwiLocSetAutoStartReq::max_time`
- 8.731.2.6 **BOOL** `SwiLocSetAutoStartReq::set_fix_rate`
- 8.731.2.7 **BOOL** `SwiLocSetAutoStartReq::set_fix_type`
- 8.731.2.8 **BOOL** `SwiLocSetAutoStartReq::set_function`
- 8.731.2.9 **BOOL** `SwiLocSetAutoStartReq::set_max_dist`
- 8.731.2.10 **BOOL** `SwiLocSetAutoStartReq::set_max_time`

## 8.732 swiModemStatusResp Struct Reference

### Data Fields

- [CommInfo](#) `commonInfo`
- [LTEInfo](#) \* `pLTEInfo`

### 8.732.1 Detailed Description

Structure for storing the SLQS Nas Swi Modem Status response parameters.

#### Parameters

<i>commonInfo</i>	(mandatory) <ul style="list-style-type: none"> <li>• See <a href="#">CommInfo</a> for more information</li> </ul>
<i>pLTEInfo</i>	(optional) <ul style="list-style-type: none"> <li>• See <a href="#">LTEInfo</a> for more information</li> </ul>

### 8.732.2 Field Documentation

- 8.732.2.1 **CommInfo** `swiModemStatusResp::commonInfo`
- 8.732.2.2 **LTEInfo\*** `swiModemStatusResp::pLTEInfo`

## 8.733 SwiOTAMsg\_s Struct Reference

### Data Fields

- [ULONG](#) type
- [WORD](#) `data_len`
- [BYTE](#) `data` [2048]
- [LteNasReleaseInfo](#) \* `pLteNasRelInfo`
- [ULONGLONG](#) \* `pTime`

### 8.733.1 Detailed Description

This structure contains OTA message

## Parameters

<i>type</i>	<ul style="list-style-type: none"> <li>• message type <ul style="list-style-type: none"> <li>– 0 - LTE ESM uplink</li> <li>– 1 - LTE ESM downlink</li> <li>– 2 - LTE EMM uplink</li> <li>– 3 - LTE EMM downlink</li> <li>– 4 - GSM/UMTS uplink</li> <li>– 5 - GSM/UMTS downlink</li> </ul> </li> </ul>
<i>data_len</i>	<ul style="list-style-type: none"> <li>• OTA Message Content Length</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>• OTA Message Content</li> </ul>
<i>pLteNasRelInfo</i>	<ul style="list-style-type: none"> <li>• LTE NAS Release Info</li> <li>• see <a href="#">LteNasReleaseInfo</a> for details</li> </ul>
<i>pTime</i>	<ul style="list-style-type: none"> <li>• Seconds in local time since Jan. 6th 1980 00:00:00 UTC</li> </ul>

## 8.733.2 Field Documentation

8.733.2.1 BYTE SwiOTAMsg\_s::data[2048]

8.733.2.2 WORD SwiOTAMsg\_s::data\_len

8.733.2.3 LteNasReleaseInfo\* SwiOTAMsg\_s::pLteNasRelInfo

8.733.2.4 ULONGLONG\* SwiOTAMsg\_s::pTime

8.733.2.5 ULONG SwiOTAMsg\_s::type

## 8.734 swiPDPRuntimeSettingsReq Struct Reference

## Data Fields

- [BYTE contextId](#)
- [BYTE contextType](#)

## 8.734.1 Detailed Description

This structure contains the PDP Runtime Settings Request parameters.



## Parameters

<i>contextId</i>	<ul style="list-style-type: none"> <li>Context Identifier</li> </ul>
<i>v4sessionId</i>	<ul style="list-style-type: none"> <li>The v4 session ID for which the runtime settings are to be retrieved</li> <li>provide a NULL pointer if not applicable</li> </ul>
<i>v6sessionId</i>	<ul style="list-style-type: none"> <li>The v6 session ID for which the runtime settings are to be retrieved</li> <li>provide a NULL pointer if not applicable</li> </ul>

## 8.734.2 Field Documentation

8.734.2.1 BYTE swiPDPRuntimeSettingsReq::contextId

8.734.2.2 BYTE swiPDPRuntimeSettingsReq::contextType

## 8.735 swiPDPRuntimeSettingsResp Struct Reference

## Data Fields

- [BYTE \\* pContextId](#)
- [BYTE \\* pBearerId](#)
- [CHAR \\* pAPNName](#)
- [ULONG \\* pIPv4Address](#)
- [ULONG \\* pIPv4GWAddress](#)
- [ULONG \\* pPrDNSIPv4Address](#)
- [ULONG \\* pSeDNSIPv4Address](#)
- [struct IPV6AddressInfo \\* pIPv6Address](#)
- [struct IPV6AddressInfo \\* pIPv6GWAddress](#)
- [WORD \\* pPrDNSIPv6Address](#)
- [WORD \\* pSeDNSIPv6Address](#)
- [ULONG \\* pPrPCSCFIPv4Address](#)
- [ULONG \\* pSePCSCFIPv4Address](#)
- [WORD \\* pPrPCSCFIPv6Address](#)
- [WORD \\* pSePCSCFIPv6Address](#)

## 8.735.1 Detailed Description

This structure contains the response parameters retrieved by the API SLQSWdsSwiPDPRuntimeSettings

## Parameters

<i>pContextId</i>	(optional) <ul style="list-style-type: none"> <li>Context Identifier <ul style="list-style-type: none"> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>pBearerId</i>	(optional) <ul style="list-style-type: none"> <li>Bearer Identity</li> <li>An EPS bearer identity uniquely identifies an EPS bearer for one UE accessing via E-UTRAN. The EPS Bearer Identity is allocated by the MME. <ul style="list-style-type: none"> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>pAPNName</i>	(optional) <ul style="list-style-type: none"> <li>APN name associated with the context id <ul style="list-style-type: none"> <li>NULL terminated by default.</li> </ul> </li> </ul>
<i>pIPv4Address</i>	(optional) <ul style="list-style-type: none"> <li>IPv4 Address <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>pIPv4GW-Address</i>	(optional) <ul style="list-style-type: none"> <li>IPv4 Gateway Address <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>pPrDNSIPv4-Address</i>	(optional) <ul style="list-style-type: none"> <li>Primary DNS IPv4 Address <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>pSeDNSIPv4-Address</i>	(optional) <ul style="list-style-type: none"> <li>Secondary DNS IPv4 Address <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>
<i>pIPv6Address</i>	(optional) <ul style="list-style-type: none"> <li>IPv6 Address</li> <li>See <a href="#">IPV6AddressInfo</a> for more information</li> </ul>

<i>pIPv6GW-Address</i>	(optional) <ul style="list-style-type: none"> <li>IPv6 Gateway Address</li> <li>See <a href="#">IPV6AddressInfo</a> for more information</li> </ul>
<i>pPrDNSIPv6-Address</i>	(optional) <ul style="list-style-type: none"> <li>Primary IPv6 DNS Address(in network byte order)</li> <li>This is an 8-element array of 16-bit numbers, each of which is in big-endian format</li> </ul>
<i>pSeDNSIPv6-Address</i>	(optional) <ul style="list-style-type: none"> <li>Secondary IPv6 DNS Address(in network byte order)</li> <li>This is an 8-element array of 16-bit numbers, each of which is in big-endian format</li> </ul>
<i>pPrPCSCFIPv4-Address</i>	(optional) <ul style="list-style-type: none"> <li>Primary PCSCF IPv4 Address</li> </ul>
<i>pSePCSCFIPv4-Address</i>	(optional) <ul style="list-style-type: none"> <li>Secondary PCSCF IPv4 Address</li> </ul>
<i>pPrPCSCFIPv6-Address</i>	(optional) <ul style="list-style-type: none"> <li>Primary PCSCF IPv6 Address</li> <li>This is an 8-element array of 16-bit numbers, each of which is in big-endian format</li> </ul>
<i>pSePCSCFIPv6-Address</i>	(optional) <ul style="list-style-type: none"> <li>Secondary PCSCF IPv6 Address</li> <li>This is an 8-element array of 16-bit numbers, each of which is in big-endian format</li> </ul>

**Note**

Parameters which are mentioned as NULL will be ignored.

**8.735.2 Field Documentation**

**8.735.2.1 CHAR\*** swiPDPRuntimeSettingsResp::pAPNName

**8.735.2.2 BYTE\*** swiPDPRuntimeSettingsResp::pBearerId

**8.735.2.3 BYTE\*** swiPDPRuntimeSettingsResp::pContextId

**8.735.2.4 ULONG\*** swiPDPRuntimeSettingsResp::pIPv4Address

**8.735.2.5 ULONG\*** swiPDPRuntimeSettingsResp::pIPv4GWAddress

**8.735.2.6 struct IPV6AddressInfo\*** swiPDPRuntimeSettingsResp::pIPv6Address

**8.735.2.7 struct IPV6AddressInfo\*** swiPDPRuntimeSettingsResp::pIPv6GWAddress

**8.735.2.8 ULONG\*** swiPDPRuntimeSettingsResp::pPrDNSIPv4Address

- 8.735.2.9    **WORD\*** swiPDPRuntimeSettingsResp::pPrDNSIPv6Address
- 8.735.2.10   **ULONG\*** swiPDPRuntimeSettingsResp::pPrPCSCFIPv4Address
- 8.735.2.11   **WORD\*** swiPDPRuntimeSettingsResp::pPrPCSCFIPv6Address
- 8.735.2.12   **ULONG\*** swiPDPRuntimeSettingsResp::pSeDNSIPv4Address
- 8.735.2.13   **WORD\*** swiPDPRuntimeSettingsResp::pSeDNSIPv6Address
- 8.735.2.14   **ULONG\*** swiPDPRuntimeSettingsResp::pSePCSCFIPv4Address
- 8.735.2.15   **WORD\*** swiPDPRuntimeSettingsResp::pSePCSCFIPv6Address

## 8.736    swiQosFilter Struct Reference

### Data Fields

- [BYTE index](#)
- [BYTE version](#)
- [IPv4Addr \\* pIPv4SrcAddr](#)
- [IPv4Addr \\* pIPv4DstAddr](#)
- [BYTE \\* pNxtHdrProto](#)
- [Tos \\* pTos](#)
- [IPv6Addr \\* pIPv6SrcAddr](#)
- [IPv6Addr \\* pIPv6DstAddr](#)
- [IPv6TrafCls \\* pIPv6TrafCls](#)
- [ULONG \\* pIPv6Label](#)
- [Port \\* pTCPSrcPort](#)
- [Port \\* pTCPDstPort](#)
- [Port \\* pUDPSrcPort](#)
- [Port \\* pUDPDstPort](#)
- [ULONG \\* pEspSpi](#)
- [WORD \\* pPrecedence](#)
- [WORD \\* pId](#)
- [Port \\* pTranSrcPort](#)
- [Port \\* pTranDstPort](#)

### 8.736.1    Detailed Description

This structure contains the QoS Filter Request

## Parameters

<i>index</i>	IP filter index Integer that uniquely identifies each filter instance This TLV must be present in the request
<i>version</i>	IP filter version Identifies whether the filter is associated with IPv4 or IPv6; value specified also implies that only TLVs defined for that IP version, i.e., TLVs with IPv4 or IPv6 in the name, can be specified <ul style="list-style-type: none"> <li>• 0x04 – IPv4</li> <li>• 0x06 – Ipv6</li> </ul>
<i>pIPv4SrcAddr</i>	IPv4 filter soruce address See <a href="#">IPv4Addr</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>pIPv4DstAddr</i>	IPv4 filter destination address See <a href="#">IPv4Addr</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>pNxtHdrProto</i>	IP filter next header protocol This TLV must be present if any non-IP filter TLV(s) are provided If this field is specified, only IP packets belonging to specified higher layer protocol are considered when filtering The following protocols may be specified: <ul style="list-style-type: none"> <li>• 0x01 = ICMP</li> <li>• 0x06 = TCP</li> <li>• 0x11 = UDP</li> <li>• 0x32 = ESP Note: The next header protocol field will be set to 0xFD (TCP &amp; UDP) if a TFT is received specifying a source or destination port number, but IP next header type is not specified.</li> </ul>
<i>pTos</i>	IPv4 filter type of service See <a href="#">Tos</a> for more information
<i>pIPv6SrcAddr</i>	IPv6 filter soruce address See <a href="#">IPv6Addr</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>pIPv6DstAddr</i>	IPv6 filter destination address See <a href="#">IPv6Addr</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>pIPv6TrafCls</i>	IPv6 filter traffic class See <a href="#">IPv6TrafCls</a> for more information
<i>pIPv6Label</i>	IPv6 flow label Packet matches the IPv6 flow label filter if: ( *pIPv6Label == flow label in the IPv6 header) <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>pTCPSrcPort</i>	TCP filter source port filter See <a href="#">Port</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>

<i>pTCPDstPort</i>	TCP filter destination port filter See <a href="#">Port</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>pUDPSrcPort</i>	UDP filter source port filter See <a href="#">Port</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>pUDPDstPort</i>	UDP filter destination port filter See <a href="#">Port</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>pEspSpi</i>	ESP filter security policy index Security policy index to uniquely identify each IP flow for filtering encrypted packets for encapsulating security payload <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>pPrecedence</i>	Filter Precedence Specifies the order in which filters are applied; lower numerical value has higher precedence Note: This TLV only applies to network-initiated QoS; QoS requests containing this TLV from control points will be ignored
<i>pId</i>	Filter ID Unique identifier for each filter; filter ID is assigned by the modem Note: This TLV only applies to network-initiated QoS; QoS requests containing this TLV from control points will be ignored
<i>pTranSrcPort</i>	Transport protocol filter source port See <a href="#">Port</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>pUDPDstPort</i>	Transport protocol filter destination port See <a href="#">Port</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>

## 8.736.2 Field Documentation

8.736.2.1 **BYTE** swiQosFilter::index

8.736.2.2 **ULONG\*** swiQosFilter::pEspSpi

8.736.2.3 **WORD\*** swiQosFilter::pId

8.736.2.4 **IPv4Addr\*** swiQosFilter::pIPv4DstAddr

8.736.2.5 **IPv4Addr\*** swiQosFilter::pIPv4SrcAddr

8.736.2.6 **IPv6Addr\*** swiQosFilter::pIPv6DstAddr

8.736.2.7 **ULONG\*** swiQosFilter::pIPv6Label

8.736.2.8 **IPv6Addr\*** swiQosFilter::pIPv6SrcAddr

8.736.2.9 **IPv6TrafCls\*** swiQosFilter::pIPv6TrafCls

8.736.2.10 **BYTE\*** swiQosFilter::pNextHdrProto

8.736.2.11 **WORD\*** swiQosFilter::pPrecedence

8.736.2.12 **Port\*** swiQosFilter::pTCPDstPort

8.736.2.13 Port\* swiQosFilter::pTCPSrcPort

8.736.2.14 Tos\* swiQosFilter::pTos

8.736.2.15 Port\* swiQosFilter::pTranDstPort

8.736.2.16 Port\* swiQosFilter::pTranSrcPort

8.736.2.17 Port\* swiQosFilter::pUDPDstPort

8.736.2.18 Port\* swiQosFilter::pUDPSrcPort

8.736.2.19 BYTE swiQosFilter::version

## 8.737 swiQosFlow Struct Reference

### Data Fields

- [BYTE index](#)
- [WORD \\* pProfileId3GPP2](#)
- [BYTE \\* p3GPP2Pri](#)
- [BYTE \\* pTrafficClass](#)
- [dataRate \\* pDataRate](#)
- [tokenBucket \\* pTokenBucket](#)
- [ULONG \\* pLatency](#)
- [ULONG \\* pJitter](#)
- [pktErrRate \\* pPktErrRate](#)
- [ULONG \\* pMinPolicedPktSz](#)
- [ULONG \\* pMaxAllowedPktSz](#)
- [WORD \\* p3GPPResResidualBER](#)
- [BYTE \\* p3GPPTraHdlPri](#)
- [BYTE \\* p3GPPImCn](#)
- [BYTE \\* p3GPPSigInd](#)
- [BYTE \\* pLteQci](#)

### 8.737.1 Detailed Description

This structure contains the QoS Flow Request

#### Parameters

<i>index</i>	<ul style="list-style-type: none"><li>• IP flow index</li><li>• Integer that uniquely identifies each flow instance</li><li>• Unique index must be assigned by the control point to every flow_spec instance</li></ul>
--------------	--

<i>pProfileId3GPP2</i>	<ul style="list-style-type: none"> <li>• IP flow 3GPP2 profile ID</li> <li>• A profile ID is shorthand for a defined set of QoS flow parameters specified by the network; to be present while requesting QoS for a CDMA device</li> </ul>
<i>p3GPP2Pri</i>	<ul style="list-style-type: none"> <li>• IP flow 3GPP2 flow priority</li> <li>• Flow priority used by the network in case of contention between flows with same QoS; this parameter applies for CDMA devices</li> </ul>
<i>pTrafficClass</i>	<ul style="list-style-type: none"> <li>• IP flow traffic class</li> <li>• Integer that designates the requested traffic class:</li> <li>• 0 – Conversational</li> <li>• 1 – Streaming</li> <li>• 2 – Interactive</li> <li>• 3 – Background</li> </ul>
<i>pDataRate</i>	<ul style="list-style-type: none"> <li>• IP flow data rate min max</li> <li>• See <a href="#">dataRate</a> for more information</li> </ul>
<i>pTokenBucket</i>	<ul style="list-style-type: none"> <li>• IP flow data rate token bucket</li> <li>• See <a href="#">tokenBucket</a> for more information</li> </ul>
<i>pLatency</i>	<ul style="list-style-type: none"> <li>• IP flow latency</li> <li>• Maximum delay (in milliseconds) that can be tolerated by an IP packet during transfer through the wireless link</li> </ul>
<i>pJitter</i>	<ul style="list-style-type: none"> <li>• IP flow jitter</li> <li>• Difference between the maximum and minimum latency (in milliseconds) that can be tolerated by an IP packet during the transfer through the wireless link</li> </ul>
<i>pPktErrRate</i>	<ul style="list-style-type: none"> <li>• IP flow packet error rate</li> <li>• See <a href="#">pktErrRate</a> for more information</li> </ul>
<i>pMinPolicedPkt-Sz</i>	<ul style="list-style-type: none"> <li>• IP flow minimum policed packet size</li> <li>• Integer that defines the minimum packet size (in bytes) that will be policed for QoS guarantees; any IP packets that are smaller than the minimum specified policed size may not receive requested QoS</li> </ul>



<i>pMaxAllowed-PktSz</i>	<ul style="list-style-type: none"> <li>IP flow maximum allowed packet size</li> <li>Integer that defines the maximum packet size (in bytes) allowed in the IP flow; any IP packets greater in size than the maximum allowed packet size are not queued for transmission</li> </ul>
<i>p3GPPRes-ResidualBER</i>	<ul style="list-style-type: none"> <li>IP flow 3GPP residual bit error rate</li> <li>residual_bit_error_rate</li> <li>0 = <math>5 \times 10^{-2}</math> residual BER</li> <li>1 = <math>1 \times 10^{-2}</math> residual BER</li> <li>2 = <math>5 \times 10^{-3}</math> residual BER</li> <li>3 = <math>4 \times 10^{-3}</math> residual BER</li> <li>4 = <math>1 \times 10^{-3}</math> residual BER</li> <li>5 = <math>1 \times 10^{-4}</math> residual BER</li> <li>6 = <math>1 \times 10^{-5}</math> residual BER</li> <li>7 = <math>1 \times 10^{-6}</math> residual BER</li> <li>8 = <math>6 \times 10^{-8}</math> residual BER</li> <li>Integer that indicates the undetected BER for each IP flow in the delivered packets; Applies only to 3GPP networks</li> </ul>
<i>p3GPPTraHdlPri</i>	<ul style="list-style-type: none"> <li>3GPP traffic handling priority</li> <li>0 – Relative traffic handling priority 1</li> <li>1 – Relative traffic handling priority 2</li> <li>2 – Relative traffic handling priority 3</li> <li>Defines the relative priority of the flow; applies only to 3GPP networks</li> </ul>
<i>p3GPPImCn</i>	<ul style="list-style-type: none"> <li>IP flow 3GPP IM CN flag</li> <li>IM CN subsystem signaling flag:</li> <li>0x00 – FALSE</li> <li>0x01 – TRUE</li> <li>This parameter applies only to 3GPP networks</li> </ul>
<i>p3GPPSigInd</i>	<ul style="list-style-type: none"> <li>IP flow 3GPP signaling indication</li> <li>0x00 – FALSE</li> <li>0x01 – TRUE</li> <li>This parameter applies only to 3GPP networks</li> </ul>
<i>pLteQci</i>	
<p>Generated on Tue Jul 12 2016 10:59:45 by Doxygen 1.8.13</p>	
	<p><b>9.1 LTE QoS Class Identifier</b></p> <ul style="list-style-type: none"> <li>QoS Class Identifier(QCI) is a required parameter to request QoS in LTE</li> <li>QCI values:</li> </ul>

## 8.737.2 Field Documentation

8.737.2.1 **BYTE** swiQosFlow::index

8.737.2.2 **BYTE\*** swiQosFlow::p3GPP2Pri

8.737.2.3 **BYTE\*** swiQosFlow::p3GPPImpCn

8.737.2.4 **WORD\*** swiQosFlow::p3GPPResResidualBER

8.737.2.5 **BYTE\*** swiQosFlow::p3GPPSigInd

8.737.2.6 **BYTE\*** swiQosFlow::p3GPPTraHdlPri

8.737.2.7 **dataRate\*** swiQosFlow::pDataRate

8.737.2.8 **ULONG\*** swiQosFlow::pJitter

8.737.2.9 **ULONG\*** swiQosFlow::pLatency

8.737.2.10 **BYTE\*** swiQosFlow::pLteQci

8.737.2.11 **ULONG\*** swiQosFlow::pMaxAllowedPktSz

8.737.2.12 **ULONG\*** swiQosFlow::pMinPolicedPktSz

8.737.2.13 **pktErrRate\*** swiQosFlow::pPktErrRate

8.737.2.14 **WORD\*** swiQosFlow::pProfileId3GPP2

8.737.2.15 **tokenBucket\*** swiQosFlow::pTokenBucket

8.737.2.16 **BYTE\*** swiQosFlow::pTrafficClass

## 8.738 swiQosGranted Struct Reference

### Data Fields

- [swiQosFlow](#) \* [pTxFlow](#)
- [swiQosFlow](#) \* [pRxFlow](#)

### 8.738.1 Detailed Description

This structure contains the QoS granted flow

#### Parameters

<i>pTxFlow</i>	See <a href="#">swiQosFlow</a> for more information
<i>pRxFlow</i>	See <a href="#">swiQosFlow</a> for more information

## 8.738.2 Field Documentation

8.738.2.1 **swiQosFlow\*** swiQosGranted::pRxFlow

8.738.2.2 [swiQosFlow](#)\* [swiQosGranted::pTxFlow](#)

## 8.739 swiQosIds Struct Reference

### Data Fields

- [BYTE](#) *sz*
- [ULONG](#) \* *pIds*

### 8.739.1 Detailed Description

This structure contains the QoS Response parameters.

#### Parameters

<i>sz</i>	Number of QoS identifiers
<i>pIds</i>	Identifier for the QoS flow requested; number of QoS identifiers present will be equal to number of QoS specs requested in the QoS Request message

### 8.739.2 Field Documentation

8.739.2.1 [ULONG](#)\* [swiQosIds::pIds](#)8.739.2.2 [BYTE](#) [swiQosIds::sz](#)

## 8.740 swiQosModifyReq Struct Reference

### Data Fields

- [ULONG](#) *id*
- [swiQosFlow](#) \* *pTxFlow*
- [swiQosFlow](#) \* *pRxFlow*
- [swiQosFilter](#) \* *pTxFilter*
- [swiQosFilter](#) \* *pRxFilter*

### 8.740.1 Detailed Description

This structure contains the QoS Request parameters.

#### Parameters

<i>id</i>	Identifier for the QoS flow/instance that has been negotiated and that needs to be modified The QoS_identifier is used to reference the actual flow/filter specifications that are in effect as a result of the negotiation triggered by QMI_QOS_REQUEST_QOS_REQ
<i>pTxFlow</i>	See <a href="#">swiQosFlow</a> for more information
<i>pRxFlow</i>	See <a href="#">swiQosFlow</a> for more information
<i>pTxFilter</i>	See <a href="#">swiQosFilter</a> for more information
<i>pRxFilter</i>	See <a href="#">swiQosFilter</a> for more information

### 8.740.2 Field Documentation

8.740.2.1 [ULONG](#) [swiQosModifyReq::id](#)

8.740.2.2 **swiQosFilter\*** **swiQosModifyReq::pRxFilter**

8.740.2.3 **swiQosFlow\*** **swiQosModifyReq::pRxFlow**

8.740.2.4 **swiQosFilter\*** **swiQosModifyReq::pTxFilter**

8.740.2.5 **swiQosFlow\*** **swiQosModifyReq::pTxFlow**

## 8.741 swiQosReq Struct Reference

### Data Fields

- [BYTE index](#)
- [swiQosFlow](#) \* [pTxFlow](#)
- [swiQosFlow](#) \* [pRxFlow](#)
- [swiQosFilter](#) \* [pTxFilter](#)
- [swiQosFilter](#) \* [pRxFilter](#)

### 8.741.1 Detailed Description

This structure contains the QoS Request parameters.

#### Parameters

<i>index</i>	<ul style="list-style-type: none"> <li>• An integer that uniquely identifies each QoS spec included in the QoS request message</li> </ul>
<i>pTxFlow</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosFlow</a> for more information</li> </ul>
<i>pRxFlow</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosFlow</a> for more information</li> </ul>
<i>pTxFilter</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosFilter</a> for more information</li> </ul>
<i>pRxFilter</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosFilter</a> for more information</li> </ul>

### 8.741.2 Field Documentation

8.741.2.1 **BYTE** **swiQosReq::index**

8.741.2.2 **swiQosFilter\*** **swiQosReq::pRxFilter**

8.741.2.3 **swiQosFlow\*** **swiQosReq::pRxFlow**

8.741.2.4 **swiQosFilter\*** **swiQosReq::pTxFilter**

8.741.2.5 **swiQosFlow\*** **swiQosReq::pTxFlow**

## 8.742 swiRMTrasferStaticsReq Struct Reference

### Data Fields

- [BYTE bResetStatistics](#)
- [ULONG ulMask](#)

### 8.742.1 Detailed Description

RM Transfer Statistics Structure

#### Parameters

<i>bResetStatistics</i>	<ul style="list-style-type: none"><li>• Reset Statistics</li><li>• Values:<ul style="list-style-type: none"><li>• 0 - Not Reset</li><li>• Other - Reset</li></ul></li></ul>
<i>ulMask</i>	<ul style="list-style-type: none"><li>• Enable/Disable RM Transfer Satatistics Indiscation Mask</li><li>• Bit 0: Tx Packet Ok</li><li>• Bit 1: Rx Packet Ok</li><li>• Bit 2: Tx Bytes Ok</li><li>• Bit 3: Rx Bytes Ok</li><li>• Bit 4: Tx Packets Dropped</li><li>• Bit 5: Rx Packets Dropped</li><li>• Value: -0 - Disable -1 - Enable</li></ul>

### 8.742.2 Field Documentation

8.742.2.1 **BYTE** swiRMTrasferStaticsReq::bResetStatistics

8.742.2.2 **ULONG** swiRMTrasferStaticsReq::ulMask

## 8.743 sysInfoCommon Struct Reference

### Data Fields

- [BYTE srvDomainValid](#)
- [BYTE srvDomain](#)
- [BYTE srvCapabilityValid](#)
- [BYTE srvCapability](#)
- [BYTE roamStatusValid](#)
- [BYTE roamStatus](#)
- [BYTE isSysForbiddenValid](#)
- [BYTE isSysForbidden](#)

### 8.743.1 Detailed Description

Structure for storing the System Information common to CDMA, HDR, GSM, WCDMA and LTE networks.

#### Parameters

<i>srvDomainValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the service domain is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>srvDomain</i>	<ul style="list-style-type: none"> <li>Service domain registered on the system. <ul style="list-style-type: none"> <li>0x00 - No service</li> <li>0x01 - Circuit-switched only</li> <li>0x02 - Packet-switched only</li> <li>0x03 - Circuit-switched and packet-switched</li> <li>0x04 - Camped</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>srvCapabilityValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the service capability is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>srvCapability</i>	<ul style="list-style-type: none"> <li>Current system's service capability. <ul style="list-style-type: none"> <li>0x00 - No service</li> <li>0x01 - Circuit-switched only</li> <li>0x02 - Packet-switched only</li> <li>0x03 - Circuit-switched and packet-switched</li> <li>0x04 - Camped</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

<i>roamStatusValid</i>	<ul style="list-style-type: none"><li>• Indicates whether the roaming status is valid.<ul style="list-style-type: none"><li>– 0x00 - Invalid</li><li>– 0x01 - Valid</li><li>– 0xFF - Not Available</li></ul></li></ul>
<i>roamStatus</i>	<ul style="list-style-type: none"><li>• Current roaming status.<ul style="list-style-type: none"><li>– 0x00 - Off</li><li>– 0x01 - On</li><li>– 0x02 - Blinking</li><li>– 0x03 - Out of the neighborhood</li><li>– 0x04 - Out of the building</li><li>– 0x05 - Preferred system</li><li>– 0x06 - Available system</li><li>– 0x07 - Alliance partner</li><li>– 0x08 - Premium partner</li><li>– 0x09 - Full service</li><li>– 0x0A - Partial service</li><li>– 0x0B - Banner is on</li><li>– 0x0C - Banner is off</li><li>– 0x0D to 0x3F - Reserved for Standard Enhanced Roaming Indicator Numbers</li><li>– 0x40 to 0x7F - Reserved for Non-Standard Enhanced Roaming Indicator Numbers</li><li>– 0x40 to 0xFF - Reserved.</li><li>– 0xFF - Not Available</li></ul></li><li>• Values from 0x02 onward are only applicable for 3GPP2</li></ul>

<i>isSysForbiddenValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the forbidden system is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>isSysForbidden</i>	<ul style="list-style-type: none"> <li>Whether the system is forbidden. <ul style="list-style-type: none"> <li>0x00 - Not forbidden</li> <li>0x01 - Forbidden</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

## 8.743.2 Field Documentation

8.743.2.1 **BYTE** sysInfoCommon::isSysForbidden

8.743.2.2 **BYTE** sysInfoCommon::isSysForbiddenValid

8.743.2.3 **BYTE** sysInfoCommon::roamStatus

8.743.2.4 **BYTE** sysInfoCommon::roamStatusValid

8.743.2.5 **BYTE** sysInfoCommon::srvCapability

8.743.2.6 **BYTE** sysInfoCommon::srvCapabilityValid

8.743.2.7 **BYTE** sysInfoCommon::srvDomain

8.743.2.8 **BYTE** sysInfoCommon::srvDomainValid

## 8.744 TDSCDMAECIOThresh Struct Reference

### Data Fields

- [BYTE](#) TDSCDMAECIOThreshListLen
- [ULONG](#) \* pTDSCDMAECIOThreshList

### 8.744.1 Detailed Description

This structure contains TDSCDMA ECIO threshold related parameters.



## Parameters

<i>TDSCDMAECIOThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the TDSCDMA ECIO threshold list parameter to follow</li> </ul>
<i>pTDSCDMAECIOThreshList</i>	<ul style="list-style-type: none"> <li>Array of ECIO thresholds (in dB) used by TD-SCDMA</li> <li>Maximum of 32 values.</li> </ul>

## 8.744.2 Field Documentation

8.744.2.1 `ULONG*` TDSCDMAECIOThresh::pTDSCDMAECIOThreshList8.744.2.2 `BYTE` TDSCDMAECIOThresh::TDSCDMAECIOThreshListLen

## 8.745 TDSCDMARSCPThresh Struct Reference

## Data Fields

- `BYTE` TDSCDMARSCPThreshListLen
- `WORD *` pTDSCDMARSCPThreshList

## 8.745.1 Detailed Description

This structure contains TDSCDMA RSCP threshold related parameters.

## Parameters

<i>TDSCDMARSCPThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the TDSCDMA RSCP threshold list parameter to follow</li> </ul>
<i>pTDSCDMARSCPThreshList</i>	<ul style="list-style-type: none"> <li>Array of RSCP thresholds (in units of 0.1 dBm)</li> <li>Maximum of 32 values</li> <li>Range for RSCP values: -120 to -25 (in dBm).</li> </ul>

## 8.745.2 Field Documentation

8.745.2.1 `WORD*` TDSCDMARSCPThresh::pTDSCDMARSCPThreshList8.745.2.2 `BYTE` TDSCDMARSCPThresh::TDSCDMARSCPThreshListLen

## 8.746 TDSCDMARSSIThresh Struct Reference

## Data Fields

- `BYTE` TDSCDMARSSIThreshListLen
- `ULONG *` pTDSCDMARSSIThreshList

### 8.746.1 Detailed Description

This structure contains TDSCDMA RSSI threshold related parameters.

## Parameters

<i>TDSCDMARSSIThreshListLen</i>	<ul style="list-style-type: none"> <li>Length of the TDSCDMA RSSI threshold list parameter to follow</li> </ul>
<i>pTDSCDMARSSIThreshList</i>	<ul style="list-style-type: none"> <li>Array of RSSI thresholds (in dBm) used by TD-SCDMA</li> <li>Maximum of 32 values.</li> </ul>

## 8.746.2 Field Documentation

8.746.2.1 **ULONG\*** TDSCDMARSSIThresh::pTDSCDMARSSIThreshList8.746.2.2 **BYTE** TDSCDMARSSIThresh::TDSCDMARSSIThreshListLen

## 8.747 TDSCDMASigInfoExt Struct Reference

## Data Fields

- [FLOAT](#) rssi
- [FLOAT](#) rscp
- [FLOAT](#) ecio
- [FLOAT](#) sinr

## 8.747.1 Detailed Description

This structure contains the TDSCDMA Signal Strength Info Extended

## Parameters

<i>rssi</i>	<ul style="list-style-type: none"> <li>Measured RSSI in dB</li> </ul>
<i>rscp[Optional]</i>	<ul style="list-style-type: none"> <li>Measured RSCP in dBm</li> </ul>
<i>ecio[Optional]</i>	<ul style="list-style-type: none"> <li>Measured ECIO in dBm.</li> </ul>
<i>sinr[Optional]</i>	<ul style="list-style-type: none"> <li>Measured SINR in dB. -15 dB is sent to clients if the actual SINR is less than -15 dB</li> </ul>

## 8.747.2 Field Documentation

8.747.2.1 **FLOAT** TDSCDMASigInfoExt::ecio8.747.2.2 **FLOAT** TDSCDMASigInfoExt::rscp8.747.2.3 **FLOAT** TDSCDMASigInfoExt::rssi

## 8.747.2.4 FLOAT TDSCDMASigInfoExt::sinr

## 8.748 tdscdmaSigInfoExt Struct Reference

## Data Fields

- float [rssi](#)
- float [rscp](#)
- float [ecio](#)
- float [sinr](#)

## 8.748.1 Detailed Description

## Parameters

<i>rssi</i>	RSSI in dBm.
<i>rsrq</i>	RSRQ value in dB
<i>rsrp</i>	Current RSRP in dBm as measured by L1.
<i>snr</i>	SNR level as a scaled integer in units of 0.1 dB.

## 8.748.2 Field Documentation

8.748.2.1 float tdscdmaSigInfoExt::ecio

8.748.2.2 float tdscdmaSigInfoExt::rscp

8.748.2.3 float tdscdmaSigInfoExt::rssi

8.748.2.4 float tdscdmaSigInfoExt::sinr

## 8.749 TDSCDMASINRCONFThresh Struct Reference

## Data Fields

- [BYTE TDSCDMASINRCONFThreshListLen](#)
- [FLOAT \\* pTDSCDMASINRCONFThreshList](#)

## 8.749.1 Detailed Description

This structure contains TDSCDMA SINR threshold related parameters.

## Parameters

<i>TDSCDMASINRCONFThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the TDSCDMA SINR threshold list parameter to follow</li> </ul>
<i>pTDSCDMASINRCONFThreshList</i>	<ul style="list-style-type: none"> <li>• Array of SINR thresholds (in dB) used by TD-SCDMA</li> <li>• Maximum of 32 values</li> </ul>

## 8.749.2 Field Documentation

8.749.2.1 **FLOAT\*** TDSCDMASINRCONFThresh::pTDSCDMASINRCONFThreshList

8.749.2.2 **BYTE** TDSCDMASINRCONFThresh::TDSCDMASINRCONFThreshListLen

## 8.750 TDSCDMASINRThresh Struct Reference

### Data Fields

- [BYTE](#) TDSCDMASINRThreshListLen
- [ULONG](#) \* pTDSCDMASINRThreshList

### 8.750.1 Detailed Description

This structure contains TDSCDMA SINR threshold related parameters.

#### Parameters

<i>TDSCDMASIN- RThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the TDSCDMA SINR threshold list parameter to follow</li> </ul>
<i>pTDSCDMASIN- RThreshList</i>	<ul style="list-style-type: none"> <li>• Array of SINR thresholds (in dB) used by TD-SCDMA</li> <li>• Maximum of 32 values</li> </ul>

## 8.750.2 Field Documentation

8.750.2.1 **ULONG\*** TDSCDMASINRThresh::pTDSCDMASINRThreshList

8.750.2.2 **BYTE** TDSCDMASINRThresh::TDSCDMASINRThreshListLen

## 8.751 tempratureData Struct Reference

### Data Fields

- [ULONG](#) timeSource
- [ULONG](#) timeOfFirstSample
- [BYTE](#) temperatureDataLen
- [WORD](#) timeOffset [64]
- [ULONG](#) temperature [64]

### 8.751.1 Detailed Description

This structure specifies information regarding the Temperature Data.

#### Parameters

<i>timeSource</i>	<ul style="list-style-type: none"> <li>• Time source of the sensor data</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 0 - Sensor time source is unspecified</li> <li>– 1 - Time source is common between the sensors and the location engine</li> </ul> </li> </ul>
<i>timeOfFirst-Sample</i>	<ul style="list-style-type: none"> <li>• Denotes a full 32-bit time stamp of the first (oldest) sample in this message.</li> <li>• The time stamp is in the time reference scale that is used by the sensor time source.</li> <li>• Units - Milliseconds</li> </ul>
<i>temperature-DataLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements <ul style="list-style-type: none"> <li>– timeOffset</li> <li>– temperature</li> </ul> </li> </ul>
<i>timeOffset</i>	<ul style="list-style-type: none"> <li>• Sample time offset</li> <li>• Units - Milliseconds</li> </ul>
<i>temperature</i>	<ul style="list-style-type: none"> <li>• Sensor temperature.</li> <li>• Type - Floating point</li> <li>• Units - Degrees Celsius</li> <li>• Range -50 to +100.00</li> </ul>

## 8.751.2 Field Documentation

8.751.2.1 **ULONG** tempratureData::temperature[64]

8.751.2.2 **BYTE** tempratureData::temperatureDataLen

8.751.2.3 **ULONG** tempratureData::timeOfFirstSample

8.751.2.4 **WORD** tempratureData::timeOffset[64]

8.751.2.5 **ULONG** tempratureData::timeSource

## 8.752 TFTIDParams Struct Reference

### Data Fields

- [BYTE](#) filterId
- [BYTE](#) eValid
- [BYTE](#) ipVersion

- WORD \* pSourceIP
- BYTE sourceIPMask
- BYTE nextHeader
- WORD destPortRangeStart
- WORD destPortRangeEnd
- WORD srcPortRangeStart
- WORD srcPortRangeEnd
- ULONG IPSECSPi
- WORD tosMask
- ULONG flowLabel

### 8.752.1 Detailed Description

structure contains traffic flow template parameters

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

#### Parameters

<i>filterId</i>	<ul style="list-style-type: none"> <li>• Filter identifier</li> </ul>
<i>eValid</i>	<ul style="list-style-type: none"> <li>• Evaluation precedence index</li> </ul>
<i>pVersion</i>	<ul style="list-style-type: none"> <li>• IP version number <ul style="list-style-type: none"> <li>– 4 - IPv4</li> <li>– 6 - IPv6</li> </ul> </li> </ul>
<i>sourceIP</i>	<ul style="list-style-type: none"> <li>• Source IP address <ul style="list-style-type: none"> <li>– IPv4 - Fill the first 4 bytes</li> <li>– IPv6 - Fill all the 16 bytes</li> </ul> </li> </ul>
<i>sourceIPMask</i>	<ul style="list-style-type: none"> <li>• Mask value for the source address</li> </ul>
<i>nextHeader</i>	<ul style="list-style-type: none"> <li>• Next header/protocol value</li> </ul>
<i>destPortRange-Start</i>	<ul style="list-style-type: none"> <li>• Start value of the destination port range</li> </ul>
<i>destPortRange-End</i>	<ul style="list-style-type: none"> <li>• End value of the destination port range</li> </ul>

<i>srcPortRange-Start</i>	<ul style="list-style-type: none"> <li>• Start value of the source port range</li> </ul>
<i>srcPortRange-End</i>	<ul style="list-style-type: none"> <li>• End value of the source port range</li> </ul>
<i>IPSECSPi</i>	<ul style="list-style-type: none"> <li>• IPSEC security parameter index</li> </ul>
<i>tosMask</i>	<ul style="list-style-type: none"> <li>• TOS mask (Traffic class for IPv6)</li> </ul>
<i>flowLabel</i>	<ul style="list-style-type: none"> <li>• Flow label</li> </ul>

## 8.752.2 Field Documentation

8.752.2.1 WORD TFTIDParams::destPortRangeEnd

8.752.2.2 WORD TFTIDParams::destPortRangeStart

8.752.2.3 BYTE TFTIDParams::eValid

8.752.2.4 BYTE TFTIDParams::filterId

8.752.2.5 ULONG TFTIDParams::flowLabel

8.752.2.6 ULONG TFTIDParams::IPSECSPi

8.752.2.7 BYTE TFTIDParams::ipVersion

8.752.2.8 BYTE TFTIDParams::nextHeader

8.752.2.9 WORD\* TFTIDParams::pSourceIP

8.752.2.10 BYTE TFTIDParams::sourceIPMask

8.752.2.11 WORD TFTIDParams::srcPortRangeEnd

8.752.2.12 WORD TFTIDParams::srcPortRangeStart

8.752.2.13 WORD TFTIDParams::tosMask

## 8.753 timeInfo Struct Reference

### Data Fields

- [WORD year](#)
- [BYTE month](#)
- [BYTE day](#)
- [BYTE hour](#)
- [BYTE minute](#)



- [BYTE second](#)
- [BYTE dayOfWeek](#)
- [INT8 timeZone](#)
- [BYTE dayLtSavingAdj](#)
- [BYTE radiolInterface](#)
- [BYTE TlvPresent](#)

### 8.753.1 Detailed Description

This structure contains the parameters for Network Time.

#### Parameters

<i>year</i>	<ul style="list-style-type: none"><li>• Year</li></ul>
<i>month</i>	<ul style="list-style-type: none"><li>• Month</li><li>• 1 is January and 12 is December</li></ul>
<i>day</i>	<ul style="list-style-type: none"><li>• Day</li><li>• Range - 1 to 31</li></ul>
<i>hour</i>	<ul style="list-style-type: none"><li>• Hour</li><li>• Range - 0 to 59</li></ul>
<i>minute</i>	<ul style="list-style-type: none"><li>• Minute</li><li>• Range - 0 to 59</li></ul>
<i>second</i>	<ul style="list-style-type: none"><li>• Second</li><li>• Range - 0 to 59</li></ul>
<i>dayOfWeek</i>	<ul style="list-style-type: none"><li>• Day of the week</li><li>• 0 is Monday and 6 is Sunday</li></ul>
<i>timeZone</i>	<ul style="list-style-type: none"><li>• Offset from Universal time</li><li>• The difference between local time and Universal time, in increments of 15 min</li><li>• Signed Value</li></ul>

<i>dayLtSavingAdj</i>	<ul style="list-style-type: none"> <li>• Daylight saving adjustment in hours</li> <li>• Possible values - 0, 1, and 2.</li> <li>• This field is ignored if radio_if is NAS_RADIO_IF_CDMA_1XEVDO</li> </ul>
<i>radioInterface</i>	<ul style="list-style-type: none"> <li>• Radio interface from which the information comes</li> <li>• Values <ul style="list-style-type: none"> <li>– 0x01 - NAS_RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - NAS_RADIO_IF_CDMA_1XEVDO - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x04 - NAS_RADIO_IF_GSM - GSM</li> <li>– 0x05 - NAS_RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - NAS_RADIO_IF_LTE - LTE</li> <li>– 0x09 - NAS_RADIO_IF_TDSCDMA -TD-SCDMA</li> </ul> </li> </ul>
<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Tlv Present.</li> </ul>

## 8.753.2 Field Documentation

8.753.2.1 **BYTE** `timeInfo::day`

8.753.2.2 **BYTE** `timeInfo::dayLtSavingAdj`

8.753.2.3 **BYTE** `timeInfo::dayOfWeek`

8.753.2.4 **BYTE** `timeInfo::hour`

8.753.2.5 **BYTE** `timeInfo::minute`

8.753.2.6 **BYTE** `timeInfo::month`

8.753.2.7 **BYTE** `timeInfo::radioInterface`

8.753.2.8 **BYTE** `timeInfo::second`

8.753.2.9 **INT8** `timeInfo::timeZone`

8.753.2.10 **BYTE** `timeInfo::TlvPresent`

8.753.2.11 **WORD** `timeInfo::year`

## 8.754 TmdDeRegNotMitigationLvlReq Struct Reference

### Data Fields

- [BYTE](#) `mitigationDevIDLen`
- [CHAR](#) `mitigationDevID` [255]

### 8.754.1 Detailed Description

This structure contains mitigation devices Level deregister request parameters

#### Parameters

<i>mitigationDevID-Len</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements             <ul style="list-style-type: none"> <li>mitigation_dev_id</li> </ul> </li> </ul>
<i>mitigationDevID</i>	<ul style="list-style-type: none"> <li>Mitigation device ID</li> </ul>

### 8.754.2 Field Documentation

8.754.2.1 **CHAR** TmdDeRegNotMitigationLvlReq::mitigationDevID[255]

8.754.2.2 **BYTE** TmdDeRegNotMitigationLvlReq::mitigationDevIDLen

## 8.755 TmdGetMitigationDevListResp Struct Reference

### Data Fields

- [BYTE](#) \* pMitigationDevListLen
- [mitigationDevList](#) \* pMitigationDevList

### 8.755.1 Detailed Description

This structure contains mitigation devices list from the remote endpoint

#### Parameters

<i>pMitigationDev-ListLen</i>	<ul style="list-style-type: none"> <li>Mitigation Device List Length (Optional)</li> <li>Number of sets of the following elements</li> <li>pMitigationDevList</li> </ul>
<i>pMitigationDev-List</i>	<ul style="list-style-type: none"> <li>Mitigation Device List (Optional)</li> <li>See <a href="#">mitigationDevList</a> for more information.</li> </ul>

### 8.755.2 Field Documentation

8.755.2.1 **mitigationDevList\*** TmdGetMitigationDevListResp::pMitigationDevList

8.755.2.2 **BYTE\*** TmdGetMitigationDevListResp::pMitigationDevListLen

## 8.756 TmdGetMitigationLvlReq Struct Reference

### Data Fields

- [BYTE](#) [mitigationDevIDLen](#)
- [CHAR](#) [mitigationDevID](#) [255]

### 8.756.1 Detailed Description

This structure contains mitigation devices Level request parameters

#### Parameters

<i>mitigationDevIDLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements <ul style="list-style-type: none"> <li>– <code>mitigation_dev_id</code></li> </ul> </li> </ul>
<i>mitigationDevID</i>	<ul style="list-style-type: none"> <li>• Mitigation device ID</li> </ul>

### 8.756.2 Field Documentation

8.756.2.1 [CHAR](#) [TmdGetMitigationLvlReq::mitigationDevID](#)[255]

8.756.2.2 [BYTE](#) [TmdGetMitigationLvlReq::mitigationDevIDLen](#)

## 8.757 TmdGetMitigationLvlResp Struct Reference

### Data Fields

- [BYTE](#) \* [pCurrentmitigationLvl](#)
- [BYTE](#) \* [pReqMitigationLvl](#)

### 8.757.1 Detailed Description

This structure contains mitigation devices Level request parameters

#### Parameters

<i>pCurrentmitigationLvl</i>	<ul style="list-style-type: none"> <li>• Current thermal mitigation level (Optional)</li> </ul>
<i>pReqMitigationLvl</i>	<ul style="list-style-type: none"> <li>• Requested Thermal Mitigation Level (Optional)</li> <li>• The requested thermal mitigation level from the client. The default is zero if the client has not previously set the mitigation level.</li> </ul>

## 8.757.2 Field Documentation

8.757.2.1 **BYTE\*** TmdGetMitigationLvlResp::pCurrentmitigationLvl

8.757.2.2 **BYTE\*** TmdGetMitigationLvlResp::pReqMitigationLvl

## 8.758 TmdMitigationLvlIndReq Struct Reference

### Data Fields

- [BYTE mitigationDevIDLen](#)
- [CHAR mitigationDevID](#) [255]

### 8.758.1 Detailed Description

This structure contains mitigation Level Indication request parameters

#### Parameters

<i>mitigationDevIDLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements <ul style="list-style-type: none"> <li>– mitigation_dev_id</li> </ul> </li> </ul>
<i>mitigationDevID</i>	<ul style="list-style-type: none"> <li>• Mitigation device ID</li> </ul>

## 8.758.2 Field Documentation

8.758.2.1 **CHAR** TmdMitigationLvlIndReq::mitigationDevID[255]

8.758.2.2 **BYTE** TmdMitigationLvlIndReq::mitigationDevIDLen

## 8.759 TmdRegNotMitigationLvlReq Struct Reference

### Data Fields

- [BYTE mitigationDevIDLen](#)
- [CHAR mitigationDevID](#) [255]

### 8.759.1 Detailed Description

This structure contains mitigation devices Level register request parameters

## Parameters

<i>mitigationDevID-Len</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements <ul style="list-style-type: none"> <li>mitigation_dev_id</li> </ul> </li> </ul>
<i>mitigationDevID</i>	<ul style="list-style-type: none"> <li>Mitigation device ID</li> </ul>

## 8.759.2 Field Documentation

8.759.2.1 CHAR TmdRegNotMitigationLvlReq::mitigationDevID[255]

8.759.2.2 BYTE TmdRegNotMitigationLvlReq::mitigationDevIDLen

## 8.760 tokenBucket Struct Reference

## Data Fields

- ULONG peakRate
- ULONG tokenRate
- ULONG bucketSz

## 8.760.1 Detailed Description

This structure contains the TP flow data rate token bucket

## Parameters

<i>peakRate</i>	Maximum rate at which data can be transmitted when the token bucket is full (bits per second)
<i>tokenRate</i>	Rate at which tokens will be put in the token bucket (bits per second); a token is required to be present in the bucket to send a byte of data
<i>bucketSz</i>	Maximum number of tokens that can be accumulated at any instance (bytes); controls the size of the burst that is allowed at any given time

## 8.760.2 Field Documentation

8.760.2.1 ULONG tokenBucket::bucketSz

8.760.2.2 ULONG tokenBucket::peakRate

8.760.2.3 ULONG tokenBucket::tokenRate

## 8.761 Tos Struct Reference

## Data Fields

- BYTE val
- BYTE mask

### 8.761.1 Detailed Description

This structure contains the IPv4 filter type of service

## Parameters

<i>val</i>	Type of service value
<i>mask</i>	<p>Packet matches the TOS filter if: (IPv4_filter_tos_val and IPv4_filter_tos_mask) == (TOS value in the IP packet &amp; IPv4_filter_tos_mask) Example:</p> <ul style="list-style-type: none"> <li>• IPv4_filter_tos_val = 00101000</li> <li>• IPv4_filter_tos_mask = 11111100 The filter will compare only the first 6 bits in the IPv4_filter_type_of_service with the first 6 bits in the TOS field of the IP packet. The first 6 bits in the TOS field of the IP packet must be 001010 to match the filter. The last 2 bits can be anything since they are ignored by filtering.</li> </ul>

## 8.761.2 Field Documentation

## 8.761.2.1 BYTE Tos::mask

## 8.761.2.2 BYTE Tos::val

## 8.762 transferRouteMessageTlv Struct Reference

## Data Fields

- [uint8\\_t TlvPresent](#)
- [sMSTransferRouteMTMessageInfo TransferRouteMTMessageInfo](#)

## 8.762.1 Detailed Description

## Parameters

<i>TlvPresent</i>	<ul style="list-style-type: none"> <li>• Boolean indicating the presence of the TLV in the QMI response</li> </ul>
<i>TransferRouteMTMessageInfo</i>	<ul style="list-style-type: none"> <li>• Transfer Route MT Message</li> <li>• See <a href="#">sMSTransferRouteMTMessageInfo</a> for more information</li> </ul>

## 8.762.2 Field Documentation

## 8.762.2.1 uint8\_t transferRouteMessageTlv::TlvPresent

## 8.762.2.2 sMSTransferRouteMTMessageInfo transferRouteMessageTlv::TransferRouteMTMessageInfo

## 8.763 transferStatInd Struct Reference

## Data Fields

- [uint8\\_t StatsPeriod](#)
- [uint32\\_t StatsMask](#)



### 8.763.1 Detailed Description

## Parameters

<i>StatsPeriod</i>	Field Period between transfer statistic reports.
<i>StatsMask</i>	requested statistic bit mask.

## 8.763.2 Field Documentation

8.763.2.1 uint32\_t transferStatInd::StatsMask

8.763.2.2 uint8\_t transferStatInd::StatsPeriod

## 8.764 TransferStatInd Struct Reference

## Data Fields

- [BYTE StatsPeriod](#)
- [ULONG StatsMask](#)

## 8.764.1 Detailed Description

This structure contains Transfer Statistics Indicator

## Parameters

<i>StatsPeriod</i>	<ul style="list-style-type: none"> <li>• Period between transfer statistics reports <ul style="list-style-type: none"> <li>– 0 - Do not report</li> <li>– Other - Period between reports (seconds)</li> </ul> </li> </ul>
<i>StatsMask</i>	<ul style="list-style-type: none"> <li>• Requested statistic bit mask. Each bit set causes the corresponding optional TLV to be sent in the indication. All unlisted bits are reserved for future use and must be set to zero. <ul style="list-style-type: none"> <li>– 0x00000040 - Tx bytes OK</li> <li>– 0x00000080 - Rx bytes OK</li> </ul> </li> </ul>

## 8.764.2 Field Documentation

8.764.2.1 ULONG TransferStatInd::StatsMask

8.764.2.2 BYTE TransferStatInd::StatsPeriod

## 8.765 TransferStatsDataType Struct Reference

## Data Fields

- [BYTE interval](#)

### 8.765.1 Field Documentation

8.765.1.1 **BYTE** TransferStatsDataType::interval

## 8.766 TrStatInd Struct Reference

### Data Fields

- [BYTE statsPeriod](#)
- [ULONG statsMask](#)

### 8.766.1 Detailed Description

This structure contains the information about the Transfer Statistics Indicator parameters.

#### Parameters

<i>statsPeriod</i>	<ul style="list-style-type: none"> <li>• Period between transfer statistics reports. <ul style="list-style-type: none"> <li>– 0 - Do not report</li> <li>– Other - Period between reports (seconds)</li> </ul> </li> </ul>
<i>statsMask</i>	<ul style="list-style-type: none"> <li>• Requested statistic bit mask. <ul style="list-style-type: none"> <li>– 0x00000001 - Tx packets OK</li> <li>– 0x00000002 - Rx packets OK</li> <li>– 0x00000004 - Tx packet errors</li> <li>– 0x00000008 - Rx packet errors</li> <li>– 0x00000010 - Tx overflows</li> <li>– 0x00000020 - Rx overflows</li> <li>– 0x00000040 - Tx bytes OK</li> <li>– 0x00000080 - Rx bytes OK</li> </ul> </li> <li>• Each bit set causes the corresponding optional information to be sent in SLQSWds-EventReportCallBack.</li> <li>• All unlisted bits are reserved for future use and must be set to zero.</li> </ul>

### 8.766.2 Field Documentation

8.766.2.1 **ULONG** TrStatInd::statsMask

8.766.2.2 **BYTE** TrStatInd::statsPeriod

## 8.767 trueIMSI Struct Reference

### Data Fields

- [BYTE mccT](#) [3]

- [WORD imsiT1112](#)
- [BYTE imsiTS1 \[7\]](#)
- [BYTE imsiTS2 \[3\]](#)
- [BYTE imsiTaddrNum](#)

### 8.767.1 Detailed Description

This structure contains the parameters for True IMSI Information

#### Parameters

<i>mccT</i>	<ul style="list-style-type: none"> <li>• ASCII character representation of MCC_T</li> </ul>
<i>imsiT1112</i>	<ul style="list-style-type: none"> <li>• ASCII character representation of IMSI_T_11_12 value <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>imsiTS1</i>	<ul style="list-style-type: none"> <li>• ASCII character representation of IMSI_T_S1 value</li> </ul>
<i>imsiTS2</i>	<ul style="list-style-type: none"> <li>• ASCII character representation of IMSI_T_S2 value</li> </ul>
<i>imsiTaddrNum</i>	<ul style="list-style-type: none"> <li>• Value of IMSI_T_ADDR_NUM <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

### 8.767.2 Field Documentation

8.767.2.1 **WORD** trueIMSI::imsiT1112

8.767.2.2 **BYTE** trueIMSI::imsiTaddrNum

8.767.2.3 **BYTE** trueIMSI::imsiTS1[7]

8.767.2.4 **BYTE** trueIMSI::imsiTS2[3]

8.767.2.5 **BYTE** trueIMSI::mccT[3]

## 8.768 TXAGCList Struct Reference

#### Data Fields

- [WORD \\* pTXStaticGain](#)
- [WORD \\* pTXAIG](#)
- [WORD \\* pTXExpThres](#)
- [WORD \\* pTXExpSlope](#)
- [WORD \\* pTXComprThres](#)
- [WORD \\* pTXComprSlope](#)

### 8.768.1 Detailed Description

This structure contains the SLQSGetAudioPathConfig parameters related to AV\_TXAGCLIST.

#### Parameters

<i>pTXStaticGain</i>	<ul style="list-style-type: none"> <li>TX pre-compressor static gain</li> </ul>
<i>pTXAIG</i>	<ul style="list-style-type: none"> <li>TX pre-compressor gain selection flag</li> </ul>
<i>pTXExpThres</i>	<ul style="list-style-type: none"> <li>TX expansion threshold</li> </ul>
<i>pTXExpSlope</i>	<ul style="list-style-type: none"> <li>TX expansion slope</li> </ul>
<i>pTXComprThres</i>	<ul style="list-style-type: none"> <li>TX compression threshold</li> </ul>
<i>pTXComprSlope</i>	<ul style="list-style-type: none"> <li>TX compression slope</li> </ul>

### 8.768.2 Field Documentation

8.768.2.1 WORD\* TXAGCList::pTXAIG

8.768.2.2 WORD\* TXAGCList::pTXComprSlope

8.768.2.3 WORD\* TXAGCList::pTXComprThres

8.768.2.4 WORD\* TXAGCList::pTXExpSlope

8.768.2.5 WORD\* TXAGCList::pTXExpThres

8.768.2.6 WORD\* TXAGCList::pTXStaticGain

## 8.769 txInfo Struct Reference

#### Data Fields

- [BYTE isInTraffic](#)
- [INT32 txPower](#)

### 8.769.1 Detailed Description

This structure contains the Tx Information.

## Parameters

<i>isInTraffic</i>	<ul style="list-style-type: none"> <li>Whether the device is in traffic. <ul style="list-style-type: none"> <li>0x00 - not in traffic</li> <li>0x01 - in traffic</li> </ul> </li> <li>The txPower field is only meaningful when in the device is in traffic.</li> </ul>
<i>txPower</i>	<ul style="list-style-type: none"> <li>Tx power value in 1/10 dbm.</li> </ul>

## 8.769.2 Field Documentation

## 8.769.2.1 BYTE txInfo::isInTraffic

## 8.769.2.2 INT32 txInfo::txPower

## 8.770 TXPCMIIRFiltr Struct Reference

## Data Fields

- WORD \* pFlag
- WORD \* pStageCnt
- BYTE \* pStage0Val
- BYTE \* pStage1Val
- BYTE \* pStage2Val
- BYTE \* pStage3Val
- BYTE \* pStage4Val

## 8.770.1 Detailed Description

This structure contains the SLQSGetAudioPathConfig parameters related to AV\_TXPCMIIRFLTR.

## Parameters

<i>pFlag</i>	<ul style="list-style-type: none"> <li>Flag <ul style="list-style-type: none"> <li>0x0000 - IIR filter disable</li> <li>0xffff - IIR filter enable</li> </ul> </li> </ul>
<i>pStageCnt</i>	<ul style="list-style-type: none"> <li>Stage Count <ul style="list-style-type: none"> <li>0-4</li> </ul> </li> </ul>

<i>pStage0Val</i>	<ul style="list-style-type: none"><li>• A 20 BYTE sized parameter indicating Stage 0 value<ul style="list-style-type: none"><li>– A1</li><li>– A2</li><li>– B0</li><li>– B1</li><li>– B2</li></ul></li></ul>
<i>pStage1Val</i>	<ul style="list-style-type: none"><li>• A 20 BYTE sized parameter indicating Stage 1 value<ul style="list-style-type: none"><li>– A1</li><li>– A2</li><li>– B0</li><li>– B1</li><li>– B2</li></ul></li></ul>
<i>pStage2Val</i>	<ul style="list-style-type: none"><li>• A 20 BYTE sized parameter indicating Stage 2 value<ul style="list-style-type: none"><li>– A1</li><li>– A2</li><li>– B0</li><li>– B1</li><li>– B2</li></ul></li></ul>
<i>pStage3Val</i>	<ul style="list-style-type: none"><li>• A 20 BYTE sized parameter indicating Stage 3 value<ul style="list-style-type: none"><li>– A1</li><li>– A2</li><li>– B0</li><li>– B1</li><li>– B2</li></ul></li></ul>

<i>pStage4Val</i>	<ul style="list-style-type: none"> <li>• A 20 BYTE sized parameter indicating Stage 4 value <ul style="list-style-type: none"> <li>– A1</li> <li>– A2</li> <li>– B0</li> <li>– B1</li> <li>– B2</li> </ul> </li> </ul>
-------------------	--

## 8.770.2 Field Documentation

8.770.2.1 WORD\* TXPCMIIRFiltr::pFlag

8.770.2.2 BYTE\* TXPCMIIRFiltr::pStage0Val

8.770.2.3 BYTE\* TXPCMIIRFiltr::pStage1Val

8.770.2.4 BYTE\* TXPCMIIRFiltr::pStage2Val

8.770.2.5 BYTE\* TXPCMIIRFiltr::pStage3Val

8.770.2.6 BYTE\* TXPCMIIRFiltr::pStage4Val

8.770.2.7 WORD\* TXPCMIIRFiltr::pStageCnt

## 8.771 uim\_appStatus Struct Reference

### Data Fields

- uint8\_t [appType](#)
- uint8\_t [appState](#)
- uint8\_t [persoState](#)
- uint8\_t [persoFeature](#)
- uint8\_t [persoRetries](#)
- uint8\_t [persoUnblockRetries](#)
- uint8\_t [aidLength](#)
- uint8\_t [aidVal](#) [255]
- uint8\_t [univPin](#)
- uint8\_t [pin1State](#)
- uint8\_t [pin1Retries](#)
- uint8\_t [puk1Retries](#)
- uint8\_t [pin2State](#)
- uint8\_t [pin2Retries](#)
- uint8\_t [puk2Retries](#)

### 8.771.1 Detailed Description

This structure contains Application Status Information loaded on the card.



## Parameters

<i>appType</i>	<ul style="list-style-type: none"><li>• Indicates the type of the application.<ul style="list-style-type: none"><li>– 0 - Unknown</li><li>– 1 - SIM card</li><li>– 2 - USIM application</li><li>– 3 - RUIM card</li><li>– 4 - CSIM application</li><li>– 5 - ISIM application</li></ul></li><li>• Other values are reserved for the future and are to be handled as "Unknown".</li></ul>
<i>appState</i>	<ul style="list-style-type: none"><li>• Indicates the state of the application.<ul style="list-style-type: none"><li>– 0 - Unknown</li><li>– 1 - Detected</li><li>– 2 - PIN1 or UPIN is required</li><li>– 3 - PUK1 or PUK for UPIN is required</li><li>– 4 - Personalization state must be checked</li><li>– 5 - PIN1 is blocked</li><li>– 6 - Illegal</li><li>– 7 - Ready</li></ul></li></ul>
<i>persoState</i>	<ul style="list-style-type: none"><li>• Indicates the state of the personalization for the application.<ul style="list-style-type: none"><li>– 0 - Unknown</li><li>– 1 - Personalization operation is in progress</li><li>– 2 - Ready</li><li>– 3 - Personalization code is required</li><li>– 4 - PUK for personalization code is required</li><li>– 5 - Permanently blocked</li></ul></li></ul>

<i>persoFeature</i>	<ul style="list-style-type: none"> <li>Indicates the personalization feature.</li> <li>This applies only when a personalization code is required to deactivate or unblock personalization. <ul style="list-style-type: none"> <li>0 - GW network personalization</li> <li>1 - GW network subset personalization</li> <li>2 - GW service provider personalization</li> <li>3 - GW corporate personalization</li> <li>4 - GW UIM personalization</li> <li>5 - 1X network type 1 personalization</li> <li>6 - 1X network type 2 personalization</li> <li>7 - 1X HRPD personalization</li> <li>8 - 1X service provider personalization</li> <li>9 - 1X corporate personalization</li> <li>10 - 1X RUIM personalization</li> <li>11 - Unknown</li> </ul> </li> </ul>
<i>persoRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to disable the personalization.</li> </ul>
<i>persoUnblock-Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock the personalization.</li> </ul>
<i>aidLength</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements. i.e. aidVal</li> <li>If zero(0) then no aidVal information exists.</li> </ul>
<i>aidVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>Application identifier value.</li> </ul>
<i>univPin</i>	<ul style="list-style-type: none"> <li>Indicates whether UPIN replaces PIN1. <ul style="list-style-type: none"> <li>0 - PIN1 is used</li> <li>1 - UPIN replaces PIN1</li> </ul> </li> </ul>
<i>pin1State</i>	<ul style="list-style-type: none"> <li>Indicates the state of PIN1. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> </ul> </li> </ul>

<i>pin1Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify PIN1.</li> </ul>
<i>puk1Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock PIN1.</li> </ul>
<i>pin2State</i>	<ul style="list-style-type: none"> <li>Indicates the state of PIN2. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> </ul> </li> </ul>
<i>pin2Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify PIN2.</li> </ul>
<i>puk2Retries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock PIN2.</li> </ul>

## 8.771.2 Field Documentation

8.771.2.1 `uint8_t uim_appStatus::aidLength`

8.771.2.2 `uint8_t uim_appStatus::aidVal[255]`

8.771.2.3 `uint8_t uim_appStatus::appState`

8.771.2.4 `uint8_t uim_appStatus::appType`

8.771.2.5 `uint8_t uim_appStatus::persoFeature`

8.771.2.6 `uint8_t uim_appStatus::persoRetries`

8.771.2.7 `uint8_t uim_appStatus::persoState`

8.771.2.8 `uint8_t uim_appStatus::persoUnblockRetries`

8.771.2.9 `uint8_t uim_appStatus::pin1Retries`

8.771.2.10 `uint8_t uim_appStatus::pin1State`

8.771.2.11 `uint8_t uim_appStatus::pin2Retries`

8.771.2.12 `uint8_t uim_appStatus::pin2State`

8.771.2.13 `uint8_t uim_appStatus::puk1Retries`

8.771.2.14 `uint8_t uim_appStatus::puk2Retries`

8.771.2.15 `uint8_t uim_appStatus::univPin`

## 8.772 `uim_cardResult` Struct Reference

### Data Fields

- `uint8_t sw1`
- `uint8_t sw2`

### 8.772.1 Detailed Description

This structure contains the information about the card result.

#### Parameters

<i>sw1</i>	<ul style="list-style-type: none"><li>• SW1 received from the card.</li></ul>
<i>sw2</i>	<ul style="list-style-type: none"><li>• SW2 received from the card.</li></ul>

### 8.772.2 Field Documentation

8.772.2.1 `uint8_t uim_cardResult::sw1`

8.772.2.2 `uint8_t uim_cardResult::sw2`

## 8.773 `uim_cardStatus` Struct Reference

### Data Fields

- `uint16_t indexGwPri`
- `uint16_t index1xPri`
- `uint16_t indexGwSec`
- `uint16_t index1xSec`
- `uint8_t numSlot`
- `uim_slotInfo SlotInfo` [5]

### 8.773.1 Detailed Description

This structure contains Card Status Information.

## Parameters

<i>indexGwPri</i>	<ul style="list-style-type: none"> <li>• Index of the primary GW provisioning application.</li> <li>• The most significant byte indicates the slot (starting from 0), while the least significant byte indicates the application for that slot (starting from 0).</li> <li>• The value 0xFFFF identifies when the session does not exist.</li> </ul>
<i>index1xPri</i>	<ul style="list-style-type: none"> <li>• Index of the primary 1X provisioning application.</li> <li>• The most significant byte indicates the slot (starting from 0), while the least significant byte indicates the application for that slot (starting from 0).</li> <li>• The value 0xFFFF identifies when the session does not exist.</li> </ul>
<i>indexGwSec</i>	<ul style="list-style-type: none"> <li>• Index of the secondary GW provisioning application.</li> <li>• The most significant byte indicates the slot (starting from 0), while the least significant byte indicates the application for that slot (starting from 0).</li> <li>• The value 0xFFFF identifies when the session does not exist.</li> </ul>
<i>index1xSec</i>	<ul style="list-style-type: none"> <li>• Index of the secondary GW provisioning application.</li> <li>• The most significant byte indicates the slot (starting from 0), while the least significant byte indicates the application for that slot (starting from 0).</li> <li>• The value 0xFFFF identifies when the session does not exist.</li> </ul>
<i>numSlot</i>	<ul style="list-style-type: none"> <li>• Indicates the number of slots available on the device.</li> <li>• The following block is repeated for each slot. i.e. cardState</li> <li>• If zero(0) then no cardState information exists.</li> </ul>
<i>SlotInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_slotInfo</a> for more information.</li> </ul>

## 8.773.2 Field Documentation

8.773.2.1 uint16\_t uim\_cardStatus::index1xPri

8.773.2.2 uint16\_t uim\_cardStatus::index1xSec

8.773.2.3 uint16\_t uim\_cardStatus::indexGwPri

8.773.2.4 uint16\_t uim\_cardStatus::indexGwSec

8.773.2.5 uint8\_t uim\_cardStatus::numSlot

8.773.2.6 uim\_slotInfo uim\_cardStatus::SlotInfo[5]

## 8.774 uim\_changeUIMPIN Struct Reference

### Data Fields

- uint8\_t [pinID](#)
- uint8\_t [oldPINLen](#)
- uint8\_t [oldPINVal](#) [255]
- uint8\_t [pinLen](#)
- uint8\_t [pinVal](#) [255]

### 8.774.1 Detailed Description

This structure contains the information about the pin parameters that need to be verified.

#### Parameters

<i>pinID</i>	<ul style="list-style-type: none"> <li>• Indicates the PIN ID to be changed. <ul style="list-style-type: none"> <li>– 1 - PIN1 (also called PIN)</li> <li>– 2 - PIN2</li> <li>– 3 - Universal PIN</li> <li>– 4 - Hidden key</li> </ul> </li> </ul>
<i>oldPINLen</i>	<ul style="list-style-type: none"> <li>• Length of the following elements i.e. old pin value.</li> </ul>
<i>oldPINVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>• Old PIN value.</li> <li>• This value is a sequence of ASCII characters.</li> </ul>
<i>pinLen</i>	<ul style="list-style-type: none"> <li>• Length of the following elements i.e. new pin value.</li> </ul>
<i>pinVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>• New PIN value.</li> <li>• This value is a sequence of ASCII characters.</li> </ul>

### 8.774.2 Field Documentation

8.774.2.1 uint8\_t uim\_changeUIMPIN::oldPINLen

8.774.2.2 uint8\_t uim\_changeUIMPIN::oldPINVal[255]

8.774.2.3 uint8\_t uim\_changeUIMPIN::pinID

8.774.2.4 uint8\_t uim\_changeUIMPIN::pinLen

8.774.2.5 uint8\_t uim\_changeUIMPIN::pinVal[255]

## 8.775 uim\_encryptedPIN1 Struct Reference

### Data Fields

- uint8\_t [pin1Len](#)
- uint8\_t [pin1Val](#) [255]

### 8.775.1 Detailed Description

This structure contains the encrypted PIN1 Information.

#### Parameters

<i>pin1Len</i>	<ul style="list-style-type: none"><li>• Number of sets of the following elements ie encrypted PIN1 value.</li><li>• If zero(0), no information follows.</li></ul>
<i>pin1Val</i>	<ul style="list-style-type: none"><li>• Encrypted PIN1 value.</li></ul>

#### Note

This value is returned only when PIN1 is enabled successfully and the feature is supported.

### 8.775.2 Field Documentation

8.775.2.1 uint8\_t uim\_encryptedPIN1::pin1Len

8.775.2.2 uint8\_t uim\_encryptedPIN1::pin1Val[255]

## 8.776 uim\_fileInfo Struct Reference

### Data Fields

- uint16\_t [fileID](#)
- uint8\_t [pathLen](#)
- uint16\_t [path](#) [255]

### 8.776.1 Detailed Description

This structure contains paramaters for file Information

#### Parameters

<i>fileID</i>	<ul style="list-style-type: none"><li>• This is Identifier to SIM files; e.g. in UIM "6F07" is Identifier of IMSI File</li></ul>
---------------	--

<i>pathLen</i>	<ul style="list-style-type: none"> <li>Length of file Path</li> </ul>
<i>path</i>	<ul style="list-style-type: none"> <li>Path value. This value must be the complete path of the file, which is a sequence block of 2 bytes (e.g., 0x3F00 0x7FFF).</li> </ul>

## 8.776.2 Field Documentation

8.776.2.1 uint16\_t uim\_fileInfo::fileID

8.776.2.2 uint16\_t uim\_fileInfo::path[255]

8.776.2.3 uint8\_t uim\_fileInfo::pathLen

## 8.777 uim\_hotSwapStatus Struct Reference

### Data Fields

- uint8\_t [hotSwapLength](#)
- uint8\_t [hotSwap](#) [255]

### 8.777.1 Detailed Description

This structure contains Hot Swap Status Information.

#### Parameters

<i>hotSwapLength</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements. i.e. hot_swap</li> </ul>
<i>hotSwap</i>	<ul style="list-style-type: none"> <li>Indicates the status of the hot-swap switch. <ul style="list-style-type: none"> <li>0 - Hot-swap is not supported</li> <li>1 - Hot-swap is supported, but the status of the switch is not supported</li> <li>2 - Switch indicates that the card is present</li> <li>3 - Switch indicates that the card is not present</li> </ul> </li> </ul>

## 8.777.2 Field Documentation

8.777.2.1 uint8\_t uim\_hotSwapStatus::hotSwap[255]

8.777.2.2 uint8\_t uim\_hotSwapStatus::hotSwapLength

## 8.778 uim\_readResult Struct Reference



## Data Fields

- uint16\_t [contentLen](#)
- uint8\_t [content](#) [255]

### 8.778.1 Detailed Description

This structure contains the information for write operation.

#### Parameters

<i>contentLen</i>	<ul style="list-style-type: none"><li>• Number of sets of content.</li></ul>
<i>content</i> [255]	<ul style="list-style-type: none"><li>• Read content.</li><li>• The content is the sequence of bytes as read from the card.</li></ul>

### 8.778.2 Field Documentation

8.778.2.1 uint8\_t uim\_readResult::content[255]

8.778.2.2 uint16\_t uim\_readResult::contentLen

## 8.779 uim\_readTransparentInfo Struct Reference

## Data Fields

- uint16\_t [offset](#)
- uint16\_t [length](#)

### 8.779.1 Detailed Description

This structure contains the information for read operation.

#### Parameters

<i>offset</i>	<ul style="list-style-type: none"><li>• Offset for the read operation.</li></ul>
<i>length</i>	<ul style="list-style-type: none"><li>• Length of the content to be read.</li><li>• The value 0 is used to read the complete file.</li></ul>

### 8.779.2 Field Documentation

8.779.2.1 uint16\_t uim\_readTransparentInfo::length

8.779.2.2 uint16\_t uim\_readTransparentInfo::offset

## 8.780 uim\_remainingRetries Struct Reference

### Data Fields

- uint8\_t [verifyLeft](#)
- uint8\_t [unblockLeft](#)

### 8.780.1 Detailed Description

This structure contains the information about the retries remaining.

#### Parameters

<i>verifyLeft</i>	<ul style="list-style-type: none"><li>• Number of remaining attempts to verify the PIN.</li><li>• 0xFF, if unavailable.</li></ul>
<i>unblockLeft</i>	<ul style="list-style-type: none"><li>• Number of remaining attempts to unblock the PIN.</li><li>• 0xFF, if unavailable.</li></ul>

#### Note

This value is returned only when the enable/disable operation has failed. This information is not sent for a hidden key PIN type.

### 8.780.2 Field Documentation

8.780.2.1 uint8\_t uim\_remainingRetries::unblockLeft

8.780.2.2 uint8\_t uim\_remainingRetries::verifyLeft

## 8.781 uim\_sessionInformation Struct Reference

### Data Fields

- uint8\_t [sessionType](#)
- uint8\_t [aidLength](#)
- uint8\_t [aid](#) [255]

### 8.781.1 Detailed Description

This structure contains the Session Information.

## Parameters

<i>sessionType</i>	<ul style="list-style-type: none"> <li>Indicates the session type. <ul style="list-style-type: none"> <li>0 - Primary GW provisioning</li> <li>1 - Primary 1X provisioning</li> <li>2 - Secondary GW provisioning</li> <li>3 - Secondary 1X provisioning</li> <li>4 - Non-provisioning on slot 1</li> <li>5 - Non-provisioning on slot 2</li> <li>6 - Card on slot 1</li> <li>7 - Card on slot 2</li> <li>8 - Logical channel on slot 1</li> <li>9 - Logical channel on slot 2</li> </ul> </li> </ul>
<i>aidLength</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. Application Identifier.</li> </ul>
<i>aid</i>	<ul style="list-style-type: none"> <li>Application identifier value or channel ID.</li> <li>This value is required for non-provisioning and for logical channel session types. It is ignored in all other cases.</li> </ul>

## 8.781.2 Field Documentation

8.781.2.1 `uint8_t uim_sessionInformation::aid[255]`8.781.2.2 `uint8_t uim_sessionInformation::aidLength`8.781.2.3 `uint8_t uim_sessionInformation::sessionType`

## 8.782 uim\_setPINProtection Struct Reference

## Data Fields

- `uint8_t pinID`
- `uint8_t pinOperation`
- `uint8_t pinLength`
- `uint8_t pinValue [255]`

## 8.782.1 Detailed Description

This structure contains the information about the pin protection parameters that need to be set.

## Parameters

<i>pinID</i>	<ul style="list-style-type: none"> <li>Indicates the PIN ID to be enabled or disabled. <ul style="list-style-type: none"> <li>1 - PIN1 (also called PIN)</li> <li>2 - PIN2</li> <li>3 - Universal PIN</li> <li>4 - Hidden key</li> </ul> </li> </ul>
<i>pinOperation</i>	<ul style="list-style-type: none"> <li>Indicates whether the PIN is enabled or disabled. <ul style="list-style-type: none"> <li>0 - Disable the PIN</li> <li>1 - Enable the PIN</li> </ul> </li> </ul>
<i>pinLength</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. pin value.</li> </ul>
<i>pinValue</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>PIN value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

## 8.782.2 Field Documentation

8.782.2.1 `uint8_t uim_setPINProtection::pinID`8.782.2.2 `uint8_t uim_setPINProtection::pinLength`8.782.2.3 `uint8_t uim_setPINProtection::pinOperation`8.782.2.4 `uint8_t uim_setPINProtection::pinValue[255]`8.783 `uim_slotInfo` Struct Reference

## Data Fields

- `uint8_t cardState`
- `uint8_t upinState`
- `uint8_t upinRetries`
- `uint8_t upukRetries`
- `uint8_t errorState`
- `uint8_t numApp`
- `uim_appStatus AppStatus` [10]

## 8.783.1 Detailed Description

This structure contains information about the SLOTS present.

## Parameters

<i>cardState</i>	<ul style="list-style-type: none"> <li>Indicates the state of the card for each slot. <ul style="list-style-type: none"> <li>0 - Absent</li> <li>1 - Present</li> <li>2 - Error</li> </ul> </li> </ul>
<i>upinState</i>	<ul style="list-style-type: none"> <li>Indicates the state of UPIN. <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Enabled and not verified</li> <li>2 - Enabled and verified</li> <li>3 - Disabled</li> <li>4 - Blocked</li> <li>5 - Permanently blocked</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>upinRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to verify the UPIN.</li> <li>If 0xFF, information not available.</li> </ul>
<i>upukRetries</i>	<ul style="list-style-type: none"> <li>Indicates the number of retries remaining to unblock the UPIN.</li> <li>If 0xFF, information not available.</li> </ul>
<i>errorState</i>	<ul style="list-style-type: none"> <li>Indicates the reason for the card error, and is valid only when the card state is Error <ul style="list-style-type: none"> <li>0 - Unknown</li> <li>1 - Power down</li> <li>2 - Poll error</li> <li>3 - No ATR received</li> <li>4 - Volt mismatch</li> <li>5 - Parity error</li> <li>6 - Unknown; possibly removed</li> <li>7 - Card returned technical problems</li> <li>0xFF - Not Available</li> </ul> </li> <li>Other values are possible and reserved for future use.</li> <li>When an unknown value is received, it is to be handled as "Unknown".</li> </ul>
<i>numApp</i>	<ul style="list-style-type: none"> <li>Indicates the number of applications available on the card.</li> <li>The following block is repeated for each application. i.e. AppStatus.</li> <li>If zero(0) then no AppStatus information exists.</li> </ul>

<i>AppStatus</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_appStatus</a> for more information.</li> </ul>
------------------	---

## 8.783.2 Field Documentation

8.783.2.1 `uim_appStatus uim_slotInfo::AppStatus[10]`

8.783.2.2 `uint8_t uim_slotInfo::cardState`

8.783.2.3 `uint8_t uim_slotInfo::errorState`

8.783.2.4 `uint8_t uim_slotInfo::numApp`

8.783.2.5 `uint8_t uim_slotInfo::upinRetries`

8.783.2.6 `uint8_t uim_slotInfo::upinState`

8.783.2.7 `uint8_t uim_slotInfo::upukRetries`

## 8.784 uim\_UIMSessionInformation Struct Reference

### Data Fields

- `uint8_t sessionType`
- `uint8_t aidLength`
- `uint8_t aid [255]`

### 8.784.1 Detailed Description

This structure contains the Session Information.

#### Parameters

<i>sessionType</i>	<ul style="list-style-type: none"> <li>• Indicates the session type. <ul style="list-style-type: none"> <li>– 0 - Primary GW provisioning</li> <li>– 1 - Primary 1X provisioning</li> <li>– 2 - Secondary GW provisioning</li> <li>– 3 - Secondary 1X provisioning</li> <li>– 4 - Non-provisioning on slot 1</li> <li>– 5 - Non-provisioning on slot 2</li> <li>– 6 - Card on slot 1</li> <li>– 7 - Card on slot 2</li> <li>– 8 - Logical channel on slot 1</li> <li>– 9 - Logical channel on slot 2</li> </ul> </li> </ul>
--------------------	---

<i>aidLength</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. Application Identifier.</li> </ul>
<i>aid</i>	<ul style="list-style-type: none"> <li>Application identifier value or channel ID.</li> <li>This value is required for non-provisioning and for logical channel session types. It is ignored in all other cases.</li> </ul>

## 8.784.2 Field Documentation

8.784.2.1 `uint8_t uim_UIMSessionInformation::aid[255]`

8.784.2.2 `uint8_t uim_UIMSessionInformation::aidLength`

8.784.2.3 `uint8_t uim_UIMSessionInformation::sessionType`

## 8.785 uim\_unblockUIMPIN Struct Reference

### Data Fields

- `uint8_t pinID`
- `uint8_t pukLen`
- `uint8_t pukVal [255]`
- `uint8_t newPINLen`
- `uint8_t newPINVal [255]`

### 8.785.1 Detailed Description

This structure contains the information about the unblock pin parameters.

#### Parameters

<i>pinID</i>	<ul style="list-style-type: none"> <li>Indicates the PIN ID to be changed. <ul style="list-style-type: none"> <li>1 - PIN1 (also called PIN)</li> <li>2 - PIN2</li> <li>3 - Universal PIN</li> </ul> </li> </ul>
<i>pukLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. puk value.</li> </ul>
<i>pukVal[UIM_MAX_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"> <li>PIN Unlock Key value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

<i>newPINLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. new pin value.</li> </ul>
<i>newPINVal[UIM- _MAX_DESCR- PTION_LEN- GTH]</i>	<ul style="list-style-type: none"> <li>New PIN value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

## 8.785.2 Field Documentation

8.785.2.1 `uint8_t uim_unblockUIMPIN::newPINLen`

8.785.2.2 `uint8_t uim_unblockUIMPIN::newPINVal[255]`

8.785.2.3 `uint8_t uim_unblockUIMPIN::pinID`

8.785.2.4 `uint8_t uim_unblockUIMPIN::pukLen`

8.785.2.5 `uint8_t uim_unblockUIMPIN::pukVal[255]`

## 8.786 uim\_verifyUIMPIN Struct Reference

### Data Fields

- `uint8_t pinID`
- `uint8_t pinLen`
- `uint8_t pinVal [255]`

### 8.786.1 Detailed Description

This structure contains the information about the pin parameters that need to be verified.

#### Parameters

<i>pinID</i>	<ul style="list-style-type: none"> <li>Indicates the PIN ID to be verified. <ul style="list-style-type: none"> <li>1 - PIN1 (also called PIN)</li> <li>2 - PIN2</li> <li>3 - Universal PIN</li> <li>4 - Hidden key</li> </ul> </li> </ul>
--------------	---



<i>pinLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. pin value.</li> </ul>
<i>pinVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>PIN value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

## 8.786.2 Field Documentation

8.786.2.1 `uint8_t uim_verifyUIMPIN::pinID`

8.786.2.2 `uint8_t uim_verifyUIMPIN::pinLen`

8.786.2.3 `uint8_t uim_verifyUIMPIN::pinVal[255]`

## 8.787 UIMAuthenticateReq Struct Reference

### Data Fields

- [UIMSessionInformation sessionInfo](#)
- [authenticationData authData](#)
- [ULONG \\* pIndicationToken](#)

### 8.787.1 Detailed Description

This structure contains information of the request parameters associated with a Authenticate API.

#### Parameters

<a href="#">sessionInfo</a>	<ul style="list-style-type: none"> <li>See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<i>authData</i>	<ul style="list-style-type: none"> <li>See <a href="#">authenticationData</a> for more information.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>Response in Indication.</li> <li>When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

## 8.787.2 Field Documentation

8.787.2.1 `authenticationData UIMAuthenticateReq::authData`

8.787.2.2 `ULONG* UIMAuthenticateReq::pIndicationToken`

8.787.2.3 UIMSessionInformation UIMAuthenticateReq::sessionInfo

## 8.788 UIMAuthenticateResp Struct Reference

### Data Fields

- [cardResult](#) \* [pCardResult](#)
- [authenticateResult](#) \* [pAuthenticateResult](#)
- [ULONG](#) \* [pIndicationToken](#)

### 8.788.1 Detailed Description

This structure contains information of the response parameters associated with a Authenticate API.

#### Parameters

<i>pCard-Result(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">cardResult</a> for more information.</li> </ul>
<i>pAuthenticate-Result(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">authenticateResult</a> for more information.</li> </ul>
<i>pIndication-Token(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not returned.

### 8.788.2 Field Documentation

8.788.2.1 [authenticateResult](#)\* UIMAuthenticateResp::pAuthenticateResult

8.788.2.2 [cardResult](#)\* UIMAuthenticateResp::pCardResult

8.788.2.3 [ULONG](#)\* UIMAuthenticateResp::pIndicationToken

## 8.789 UIMChangePinReq Struct Reference

### Data Fields

- [UIMSessionInformation](#) sessionInfo
- [changeUIMPIN](#) changePIN
- [BYTE](#) \* [pKeyReferenceID](#)
- [ULONG](#) \* [pIndicationToken](#)

### 8.789.1 Detailed Description

This structure contains information of the request parameters associated with a Change PIN API.

## Parameters

<a href="#">sessionInfo</a>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<i>changePIN</i>	<ul style="list-style-type: none"> <li>• See <a href="#">changeUIMPIN</a> for more information.</li> </ul>
<i>pKeyReferenceID(optional)</i>	<ul style="list-style-type: none"> <li>• Indicates the PIN key reference ID.</li> <li>• Indicates the PIN key reference ID. Valid values are from 1 to 8, respectively, for application 1 to application 8.</li> <li>• This TLV is used only for PIN1 and PIN2 and is ignored in all other cases.</li> </ul>
<i>pIndication-Token(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

## 8.789.2 Field Documentation

8.789.2.1 [changeUIMPIN](#) `UIMChangePinReq::changePIN`

8.789.2.2 `ULONG*` `UIMChangePinReq::pIndicationToken`

8.789.2.3 `BYTE*` `UIMChangePinReq::pKeyReferenceID`

8.789.2.4 [UIMSessionInformation](#) `UIMChangePinReq::sessionInfo`

## 8.790 UIMDepersonalizationReq Struct Reference

## Data Fields

- [depersonalizationInformation](#) `depersonalisationInfo`

## 8.790.1 Detailed Description

This structure contains information of the request parameters associated with a Depersonalization API.

## Parameters

<i>depersonalisation-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">depersonalizationInformation</a> for more information.</li> </ul>
-------------------------------	--

## 8.790.2 Field Documentation

8.790.2.1 **depersonalizationInformation** UIMDepersonalizationReq::depersonalisationInfo

## 8.791 UIMDepersonalizationResp Struct Reference

### Data Fields

- [remainingRetries](#) \* [pRemainingRetries](#)

### 8.791.1 Detailed Description

This structure contains information of the response parameters associated with a Depersonalization API.

#### Parameters

<i>pRemainingRetries(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">remainingRetries</a> for more information.</li> </ul>
------------------------------------	--

#### Note

Using NULL for the pointers would make sure that the parameter is not returned.

### 8.791.2 Field Documentation

8.791.2.1 **remainingRetries\*** UIMDepersonalizationResp::pRemainingRetries

## 8.792 UIEventRegisterReqResp Struct Reference

### Data Fields

- [ULONG](#) [eventMask](#)

### 8.792.1 Detailed Description

This structure contains information of the request parameters associated with a SLQSUIMEventRegister.

#### Parameters

<i>eventMask(-Mandatory)</i>	<ul style="list-style-type: none"> <li>• Bitmask of the events that were successfully enabled. This result can be different from the mask used in the request when notifications are not supported. Additional bits are reserved for future use. <ul style="list-style-type: none"> <li>– Bit 0 - Card status</li> <li>– Bit 1 - SAP connection</li> </ul> </li> </ul>
------------------------------	--

### 8.792.2 Field Documentation

8.792.2.1 **ULONG** UIEventRegisterReqResp::eventMask

## 8.793 UIMGetCardStatusResp Struct Reference

### Data Fields

- [cardStatus](#) \* [pCardStatus](#)
- [hotSwapStatus](#) \* [pHotSwapStatus](#)

### 8.793.1 Detailed Description

This structure contains information of the response parameters associated with a Get Card Status API.

#### Parameters

<i>pCard-Status(optional)</i>	<ul style="list-style-type: none"><li>• See <a href="#">cardStatus</a> for more information.</li></ul>
<i>pHotSwap-Status(optional)</i>	<ul style="list-style-type: none"><li>• See <a href="#">hotSwapStatus</a> for more information.</li></ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not returned.

### 8.793.2 Field Documentation

8.793.2.1 [cardStatus](#)\* [UIMGetCardStatusResp::pCardStatus](#)

8.793.2.2 [hotSwapStatus](#)\* [UIMGetCardStatusResp::pHotSwapStatus](#)

## 8.794 UIMGetConfigurationReq Struct Reference

### Data Fields

- [ULONG](#) \* [pConfigurationMask](#)

### 8.794.1 Detailed Description

This structure contains information of the request parameters associated with to gets the modem configuration for the UIM module API.

#### Parameters

<i>pConfiguration-Mask(optional)</i>	<ul style="list-style-type: none"><li>• Requested configurations<ul style="list-style-type: none"><li>– Bit 0 - Automatic selection</li><li>– Bit 1 - Personalization status</li><li>– Bit 2 - Halt subscription</li><li>– All other bits are reserved for future use</li></ul></li></ul>
--------------------------------------	---

## Note

- if the TLV is missing, the service returns all configuration items in the response.

## 8.794.2 Field Documentation

### 8.794.2.1 ULONG\* UIMGetConfigurationReq::pConfigurationMask

## 8.795 UIMGetConfigurationResp Struct Reference

### Data Fields

- [BYTE](#) \* [pAutoSelection](#)
- [personalizationStatus](#) \* [pPersonalizationStatus](#)
- [BYTE](#) \* [pHaltSubscription](#)

### 8.795.1 Detailed Description

This structure contains information of the response parameters associated with a Read Transparent API.

#### Parameters

<i>pAuto-Selection(optional)</i>	<ul style="list-style-type: none"> <li>• Indicates whether the modem is configured to automatically select the provisioning sessions at powerup.</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 0 - Automatic provisioning is off</li> <li>– 1 - Automatic provisioning is on</li> </ul> </li> </ul>
<i>p-Personalization-Status(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">personalizationStatus</a> for more information.</li> </ul>
<i>pHalt-Subscription(optional)</i>	<ul style="list-style-type: none"> <li>• Indicates if the modem is configured to publish the subscription after successful initialization.</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 0 - Modem proceeds with publishing the subscription</li> <li>– 1 - Modem does not publish the subscription</li> </ul> </li> </ul>

## 8.795.2 Field Documentation

### 8.795.2.1 BYTE\* UIMGetConfigurationResp::pAutoSelection

### 8.795.2.2 BYTE\* UIMGetConfigurationResp::pHaltSubscription

### 8.795.2.3 personalizationStatus\* UIMGetConfigurationResp::pPersonalizationStatus

## 8.796 UIMGetFileAttributesReq Struct Reference

### Data Fields

- [UIMSessionInformation](#) sessionInfo
- [fileInfo](#) fileIndex
- [ULONG](#) \* pIndicationToken

### 8.796.1 Detailed Description

This structure contains information of the request parameters associated with a Get File Attributes API.

#### Parameters

<a href="#">sessionInfo</a>	<ul style="list-style-type: none"><li>• See <a href="#">UIMSessionInformation</a> for more information.</li></ul>
<a href="#">fileIndex</a>	<ul style="list-style-type: none"><li>• See <a href="#">fileInfo</a> for more information.</li></ul>
<a href="#">pIndication-Token(optional)</a>	<ul style="list-style-type: none"><li>• Response in Indication.</li><li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li></ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

### 8.796.2 Field Documentation

8.796.2.1 [fileInfo](#) UIMGetFileAttributesReq::fileIndex

8.796.2.2 [ULONG](#)\* UIMGetFileAttributesReq::pIndicationToken

8.796.2.3 [UIMSessionInformation](#) UIMGetFileAttributesReq::sessionInfo

## 8.797 UIMGetFileAttributesResp Struct Reference

### Data Fields

- [cardResult](#) \* pCardResult
- [fileAttributes](#) \* pFileAttributes
- [ULONG](#) \* pIndicationToken

### 8.797.1 Detailed Description

This structure contains information of the response parameters associated with a Get File Attributes API.

## Parameters

<i>pCard-Result(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">cardResult</a> for more information.</li> </ul>
<i>pFile-Attributes(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">fileAttributes</a> for more information.</li> </ul>
<i>pIndication-Token(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not returned.

## 8.797.2 Field Documentation

8.797.2.1 **cardResult\*** UIMGetFileAttributesResp::pCardResult

8.797.2.2 **fileAttributes\*** UIMGetFileAttributesResp::pFileAttributes

8.797.2.3 **ULONG\*** UIMGetFileAttributesResp::pIndicationToken

## 8.798 UIMGetSlotsStatusResp Struct Reference

## Data Fields

- **BYTE\*** [pNumberOfPhySlot](#)
- **UIMSlotsStatus\*** [pUimSlotsStatus](#)

## 8.798.1 Detailed Description

This structure contains information of the response parameters associated with a Get Slots Status API.

## Parameters

<i>pNumberOfPhy-Slot</i>	<ul style="list-style-type: none"> <li>• Number of sets of the Slot Status.</li> </ul>
<i>pUimSlotsStatus</i>	<ul style="list-style-type: none"> <li>• Slots Status See <a href="#">UIMSlotsStatus</a> for more information..</li> </ul>

## 8.798.2 Field Documentation

8.798.2.1 **BYTE\*** UIMGetSlotsStatusResp::pNumberOfPhySlot

8.798.2.2 **UIMSlotsStatus\*** UIMGetSlotsStatusResp::pUimSlotsStatus



## 8.799 UIMPinResp Struct Reference

### Data Fields

- [remainingRetries](#) \* [pRemainingRetries](#)
- [encryptedPIN1](#) \* [pEncryptedPIN1](#)
- [ULONG](#) \* [pIndicationToken](#)

### 8.799.1 Detailed Description

This structure contains information of the response parameters associated with a set of PIN related API's.

#### Parameters

<i>pRemainingRetries(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">remainingRetries</a> for more information.</li> </ul>
<i>pEncryptedPIN1(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">encryptedPIN1</a> for more information.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result is provided in a subsequent indication.</li> <li>• 0xFFFFFFFF, if unavailable</li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not returned.

### 8.799.2 Field Documentation

8.799.2.1 [encryptedPIN1](#)\* [UIMPinResp::pEncryptedPIN1](#)

8.799.2.2 [ULONG](#)\* [UIMPinResp::pIndicationToken](#)

8.799.2.3 [remainingRetries](#)\* [UIMPinResp::pRemainingRetries](#)

## 8.800 UIMPowerDownReq Struct Reference

### Data Fields

- [BYTE](#) slot

### 8.800.1 Detailed Description

This structure contains information of the request parameters associated with a Power Down.

## Parameters

<i>slot</i>	<ul style="list-style-type: none"> <li>Indicates the slot to be used. <ul style="list-style-type: none"> <li>1 - Slot 1</li> <li>2 - Slot 2</li> </ul> </li> </ul>
-------------	--

## 8.800.2 Field Documentation

## 8.800.2.1 BYTE UIMPowerDownReq::slot

## 8.801 UIMPowerUpReq Struct Reference

## Data Fields

- BYTE [slot](#)
- BYTE \* [plgnoreHotSwapSwitch](#)

## 8.801.1 Detailed Description

This structure contains information of the request parameters associated with a Power Down.

## Parameters

<i>slot</i>	<ul style="list-style-type: none"> <li>Indicates the slot to be used. <ul style="list-style-type: none"> <li>1 - Slot 1</li> <li>2 - Slot 2</li> </ul> </li> </ul>
<i>plgnoreHot-Swap-Switch(optional)</i>	<ul style="list-style-type: none"> <li>Hot-swap switch status. <ul style="list-style-type: none"> <li>0 - Checks the hot-swap switch status</li> <li>1 - Ignores the hot-swap switch status</li> </ul> </li> </ul>

## 8.801.2 Field Documentation

## 8.801.2.1 BYTE\* UIMPowerUpReq::plgnoreHotSwapSwitch

## 8.801.2.2 BYTE UIMPowerUpReq::slot

## 8.802 UIMReadTransparentReq Struct Reference

## Data Fields

- UIMSessionInformation [sessionInfo](#)
- fileInfo [fileIndex](#)

- [readTransparentInfo](#) [readTransparent](#)
- [ULONG](#) \* [pIndicationToken](#)
- [BYTE](#) \* [pEncryptData](#)

### 8.802.1 Detailed Description

This structure contains information of the request parameters associated with a Read Transparent API.

#### Parameters

<i><a href="#">sessionInfo</a></i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<i><a href="#">fileIndex</a></i>	<ul style="list-style-type: none"> <li>• See <a href="#">fileInfo</a> for more information.</li> </ul>
<i><a href="#">readTransparent</a></i>	<ul style="list-style-type: none"> <li>• See <a href="#">readTransparentInfo</a> for more information.</li> </ul>
<i><a href="#">pIndication-Token(optional)</a></i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>
<i><a href="#">pEncrypt-Data(optional)</a></i>	<ul style="list-style-type: none"> <li>• Encrypt Data.</li> <li>• Indicates whether the data read from the card is to be encrypted.</li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

### 8.802.2 Field Documentation

8.802.2.1 [fileInfo](#) [UIMReadTransparentReq::fileIndex](#)

8.802.2.2 [BYTE](#)\* [UIMReadTransparentReq::pEncryptData](#)

8.802.2.3 [ULONG](#)\* [UIMReadTransparentReq::pIndicationToken](#)

8.802.2.4 [readTransparentInfo](#) [UIMReadTransparentReq::readTransparent](#)

8.802.2.5 [UIMSessionInformation](#) [UIMReadTransparentReq::sessionInfo](#)

## 8.803 UIMReadTransparentResp Struct Reference

#### Data Fields

- [cardResult](#) \* [pCardResult](#)
- [readResult](#) \* [pReadResult](#)
- [ULONG](#) \* [pIndicationToken](#)
- [BYTE](#) \* [pEncryptedData](#)

### 8.803.1 Detailed Description

This structure contains information of the response parameters associated with a Read Transparent API.

#### Parameters

<i>pCardResult</i>	<ul style="list-style-type: none"> <li>• See <a href="#">cardResult</a> for more information.</li> </ul>
<i>pReadResult</i>	<ul style="list-style-type: none"> <li>• See <a href="#">readResult</a> for more information.</li> </ul>
<i>pIndication-Token(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>
<i>pEncrypted-Data(optional)</i>	<ul style="list-style-type: none"> <li>• Encrypted Data.</li> <li>• Indicates whether the data from the card passed in read_result is encrypted.</li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

### 8.803.2 Field Documentation

8.803.2.1 **cardResult\*** UIMReadTransparentResp::pCardResult

8.803.2.2 **BYTE\*** UIMReadTransparentResp::pEncryptedData

8.803.2.3 **ULONG\*** UIMReadTransparentResp::pIndicationToken

8.803.2.4 **readResult\*** UIMReadTransparentResp::pReadResult

## 8.804 UIMRefreshCompleteReq Struct Reference

### Data Fields

- [UIMSessionInformation sessionInfo](#)
- [BYTE refreshComplete](#)

### 8.804.1 Detailed Description

This structure contains information of the request parameters associated with a SLQSUIMRefreshComplete.

## Parameters

<i>sessionInfo</i> (-Mandatory)	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<i>refreshComplete</i> (-Mandatory)	<ul style="list-style-type: none"> <li>• Indicates whether the refresh was successful. Valid values: <ul style="list-style-type: none"> <li>– 0 - Refresh was not completed successfully</li> <li>– 1 - Refresh was completed successfully</li> </ul> </li> </ul>

## 8.804.2 Field Documentation

8.804.2.1 BYTE UIMRefreshCompleteReq::refreshComplete

8.804.2.2 UIMSessionInformation UIMRefreshCompleteReq::sessionInfo

## 8.805 UIMRefreshEvent Struct Reference

## Data Fields

- [BYTE stage](#)
- [BYTE mode](#)
- [BYTE sessionType](#)
- [BYTE aidLength](#)
- [BYTE aid](#) [255]
- [WORD numOfFiles](#)
- [fileInfo arrfileInfo](#) [255]

## 8.805.1 Detailed Description

This structure contains information of parameters associated with the Refresh Event.

## Parameters

<i>stage</i>	<ul style="list-style-type: none"> <li>• Indicates the stage of the Refresh procedure. <ul style="list-style-type: none"> <li>– 0 - Waiting for OK to refresh</li> <li>– 1 - Refresh started</li> <li>– 2 - Refresh ended successfully</li> <li>– 3 - Refresh failed</li> </ul> </li> </ul>
--------------	---

<i>mode</i>	<ul style="list-style-type: none"> <li>Indicates the Refresh mode. <ul style="list-style-type: none"> <li>0 - Reset</li> <li>1 - Init</li> <li>2 - Init and FCN</li> <li>3 - FCN</li> <li>4 - Init and Full FCN</li> <li>5 - Application reset</li> <li>6 - 3G session reset</li> </ul> </li> </ul>
<i>sessionType</i>	<ul style="list-style-type: none"> <li>Indicates the session type. <ul style="list-style-type: none"> <li>0 - Primary GW provisioning</li> <li>1 - Primary 1X provisioning</li> <li>2 - Secondary GW provisioning</li> <li>3 - Secondary 1X provisioning</li> <li>4 - Nonprovisioning on slot 1</li> <li>5 - Nonprovisioning on slot 2</li> <li>6 - Card on slot 1</li> <li>7 - Card on slot 2</li> <li>8 - Logical channel on slot 1</li> <li>9 - Logical channel on slot 2</li> </ul> </li> </ul>
<i>aidLength</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements <ul style="list-style-type: none"> <li>Application Identifier</li> </ul> </li> </ul>
<i>aid</i>	<ul style="list-style-type: none"> <li>Application identifier value or channel ID. This value is required for non-provisioning and for logical channel session types. It is ignored in all other cases</li> </ul>
<i>numFiles</i>	<ul style="list-style-type: none"> <li>Number of sets of the following elements: <ul style="list-style-type: none"> <li>file_id</li> <li>path_len</li> <li>path</li> </ul> </li> </ul>
<i>arrfileInfo</i>	<ul style="list-style-type: none"> <li>Array of file Information struct</li> </ul>

### 8.805.2 Field Documentation

- 8.805.2.1 **BYTE** UIMRefreshEvent::aid[255]
- 8.805.2.2 **BYTE** UIMRefreshEvent::aidLength
- 8.805.2.3 **fileInfo** UIMRefreshEvent::arrfileInfo[255]
- 8.805.2.4 **BYTE** UIMRefreshEvent::mode
- 8.805.2.5 **WORD** UIMRefreshEvent::numOfFiles
- 8.805.2.6 **BYTE** UIMRefreshEvent::sessionType
- 8.805.2.7 **BYTE** UIMRefreshEvent::stage

## 8.806 UIMRefreshGetLastEventReq Struct Reference

### Data Fields

- [UIMSessionInformation sessionInfo](#)

### 8.806.1 Detailed Description

This structure contains information of the request parameters associated with a SLQSUIMRefreshGetLastEvent.

#### Parameters

<i><a href="#">sessionInfo</a>(-Mandatory)</i>	<ul style="list-style-type: none"><li>• See <a href="#">UIMSessionInformation</a> for more information.</li></ul>
--	---

### 8.806.2 Field Documentation

- 8.806.2.1 **UIMSessionInformation** UIMRefreshGetLastEventReq::sessionInfo

## 8.807 UIMRefreshGetLastEventResp Struct Reference

### Data Fields

- [UIMRefreshEvent](#) \* [pRefreshEvent](#)

### 8.807.1 Detailed Description

This structure contains information of the response parameters associated with a SLQSUIMRefreshGetLastEvent.

#### Parameters

<i><a href="#">refreshEvent</a>(-Optional)</i>	<ul style="list-style-type: none"><li>• See <a href="#">UIMRefreshEvent</a> for more information.</li></ul>
--	---

### 8.807.2 Field Documentation

8.807.2.1 **UIMRefreshEvent\*** UIMRefreshGetLastEventResp::pRefreshEvent

## 8.808 UIMRefreshOKReq Struct Reference

### Data Fields

- [UIMSessionInformation sessionInfo](#)
- [BYTE OKtoRefresh](#)

### 8.808.1 Detailed Description

This structure contains Parameters of the Session Information

#### Parameters

<a href="#">sessionInfo</a>	<ul style="list-style-type: none"> <li>• Session Information</li> <li>• See <a href="#">UIMSessionInformation</a> for more information</li> </ul>
<a href="#">OKtoRefresh</a>	<ul style="list-style-type: none"> <li>• Indicates whether a refresh is OK. Valid values: <ul style="list-style-type: none"> <li>– 0 - Not OK to refresh</li> <li>– 1 - OK to refresh</li> </ul> </li> </ul>

### 8.808.2 Field Documentation

8.808.2.1 **BYTE** UIMRefreshOKReq::OKtoRefresh

8.808.2.2 **UIMSessionInformation** UIMRefreshOKReq::sessionInfo

## 8.809 UIMRefreshRegisterReq Struct Reference

### Data Fields

- [UIMSessionInformation sessionInfo](#)
- [registerRefresh regRefresh](#)

### 8.809.1 Detailed Description

This structure contains information of the request parameters associated with a Refresh Register.



## Parameters

<i><a href="#">sessionInfo</a></i>	<ul style="list-style-type: none"> <li>• Session Information params</li> <li>• See <a href="#">UIMSessionInformation</a> for more information</li> </ul>
<i><a href="#">regRefresh</a></i>	<ul style="list-style-type: none"> <li>• Register Refresh parameters</li> <li>• See <a href="#">registerRefresh</a> for more information</li> </ul>

## 8.809.2 Field Documentation

8.809.2.1 [registerRefresh](#) UIMRefreshRegisterReq::regRefresh8.809.2.2 [UIMSessionInformation](#) UIMRefreshRegisterReq::sessionInfo

## 8.810 UIMSessionInformation Struct Reference

## Data Fields

- [BYTE](#) [sessionType](#)
- [BYTE](#) [aidLength](#)
- [BYTE](#) [aid](#) [255]

## 8.810.1 Detailed Description

This structure contains the Session Information.

## Parameters

<i><a href="#">sessionType</a></i>	<ul style="list-style-type: none"> <li>• Indicates the session type. <ul style="list-style-type: none"> <li>– 0 - Primary GW provisioning</li> <li>– 1 - Primary 1X provisioning</li> <li>– 2 - Secondary GW provisioning</li> <li>– 3 - Secondary 1X provisioning</li> <li>– 4 - Non-provisioning on slot 1</li> <li>– 5 - Non-provisioning on slot 2</li> <li>– 6 - Card on slot 1</li> <li>– 7 - Card on slot 2</li> <li>– 8 - Logical channel on slot 1</li> <li>– 9 - Logical channel on slot 2</li> </ul> </li> </ul>
------------------------------------	---

<i>aidLength</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. Application Identifier.</li> </ul>
<i>aid</i>	<ul style="list-style-type: none"> <li>Application identifier value or channel ID.</li> <li>This value is required for non-provisioning and for logical channel session types. It is ignored in all other cases.</li> </ul>

## 8.810.2 Field Documentation

8.810.2.1 **BYTE** `UIMSessionInformation::aid[255]`

8.810.2.2 **BYTE** `UIMSessionInformation::aidLength`

8.810.2.3 **BYTE** `UIMSessionInformation::sessionType`

## 8.811 UIMSetPinProtectionReq Struct Reference

### Data Fields

- [UIMSessionInformation sessionInfo](#)
- [setPINProtection pinProtection](#)
- BYTE** \* `pKeyReferenceID`
- ULONG** \* `pIndicationToken`

### 8.811.1 Detailed Description

This structure contains information of the request parameters associated with a set pin protection API.

#### Parameters

<i><a href="#">sessionInfo</a></i>	<ul style="list-style-type: none"> <li>See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<i><a href="#">pinProtection</a></i>	<ul style="list-style-type: none"> <li>See <a href="#">setPINProtection</a> for more information.</li> </ul>
<i><a href="#">pKeyReferenceID(optional)</a></i>	<ul style="list-style-type: none"> <li>Indicates the PIN key reference ID.</li> <li>Indicates the PIN key reference ID. Valid values are from 1 to 8, respectively, for application 1 to application 8.</li> <li>This TLV is used only for PIN1 and PIN2 and is ignored in all other cases.</li> </ul>
<i><a href="#">pIndicationToken(optional)</a></i>	<ul style="list-style-type: none"> <li>Response in Indication.</li> <li>When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>

**Note**

Using NULL for the pointers would make sure that the parameter is not added to the request.

**8.811.2 Field Documentation**

8.811.2.1 **ULONG\*** UIMSetPinProtectionReq::pIndicationToken

8.811.2.2 **setPINProtection** UIMSetPinProtectionReq::pinProtection

8.811.2.3 **BYTE\*** UIMSetPinProtectionReq::pKeyReferenceID

8.811.2.4 **UIMSessionInformation** UIMSetPinProtectionReq::sessionInfo

**8.812 UIMSlotsStatus Struct Reference****Data Fields**

- [UIMSlotStatus uimSlotStatus](#) [255]

**8.812.1 Detailed Description**

This structure contains information of the response parameters associated with a Get Slots Status API.

**Parameters**

<i>uimSlotStatus</i> [- MAX_SLOTS_S- TATUS]	<ul style="list-style-type: none"><li>• Contain all slots status.</li></ul>
---	---

**8.812.2 Field Documentation**

8.812.2.1 **UIMSlotStatus** UIMSlotsStatus::uimSlotStatus[255]

**8.813 UIMSlotStatus Struct Reference****Data Fields**

- [ULONG uPhyCardStatus](#)
- [ULONG uPhySlotStatus](#)
- [BYTE bLogicalSlot](#)
- [BYTE bICCIDLength](#)
- [BYTE bICCID](#) [255]

**8.813.1 Detailed Description**

This structure contains information of the response parameters associated with a Get Slots Status API.

**Parameters**

<i>uPhyCardStatus</i>	<ul style="list-style-type: none"> <li>• State of the card in the Pyhsical Slot Status. <ul style="list-style-type: none"> <li>– 0x00 - Unknown.</li> <li>– 0x01 - Absent.</li> <li>– 0x02 - Present.</li> </ul> </li> </ul>
<i>uPhySlotStatus</i>	<ul style="list-style-type: none"> <li>• State of the Physical Slot status. <ul style="list-style-type: none"> <li>– 0x00 Inactive.</li> <li>– 0x01 Activate.</li> </ul> </li> </ul>
<i>bLogicalSlot</i>	<ul style="list-style-type: none"> <li>• Logical Slot associated with this physical slot. This is valid if the physical slot is active. <ul style="list-style-type: none"> <li>– 1 - Slot 1.</li> <li>– 2 - Slot 2.</li> <li>– 3 - Slot 3.</li> <li>– 4 - Slot 4.</li> <li>– 5 - Slot 5.</li> </ul> </li> </ul>
<i>bLogicalSlot</i>	<ul style="list-style-type: none"> <li>• Number of sets the sets of ICCID</li> </ul>
<i>bICCID[MAX_ICCID_LENGTH]</i>	<ul style="list-style-type: none"> <li>• Contains the ICCID of the card in the physical slot.</li> </ul>

## 8.813.2 Field Documentation

8.813.2.1 BYTE UIMSlotStatus::bICCID[255]

8.813.2.2 BYTE UIMSlotStatus::bICCIDLength

8.813.2.3 BYTE UIMSlotStatus::bLogicalSlot

8.813.2.4 ULONG UIMSlotStatus::uPhyCardStatus

8.813.2.5 ULONG UIMSlotStatus::uPhySlotStatus

## 8.814 UIMSlotStatusChangeInfo Struct Reference

### Data Fields

- [UIMSlotsStatus slotsstatusChange](#)
- [BYTE bNumberOfPhySlots](#)

### 8.814.1 Detailed Description

Structure consist of cardstatus params

## Parameters

<i>slotstatus-Change</i>	<ul style="list-style-type: none"><li>• See <a href="#">UIMSlotStatus</a> for more information</li></ul>
<i>bNumberOfPhy-Slots</i>	<ul style="list-style-type: none"><li>• Number of Physical Slot(s)</li></ul>

## 8.814.2 Field Documentation

8.814.2.1 BYTE UIMSlotStatusChangeInfo::bNumberOfPhySlots

8.814.2.2 UIMSlotsStatus UIMSlotStatusChangeInfo::slotsstatusChange

## 8.815 UIMStatusChangeInfo Struct Reference

## Data Fields

- [cardStatus](#) statusChange

### 8.815.1 Detailed Description

Structure consist of cardstatus params

## Parameters

<i>statusChange</i>	<ul style="list-style-type: none"><li>• See <a href="#">cardStatus</a> for more information</li></ul>
---------------------	---

## 8.815.2 Field Documentation

8.815.2.1 cardStatus UIMStatusChangeInfo::statusChange

## 8.816 UIMSwitchSlotReq Struct Reference

## Data Fields

- BYTE bLogicalSlot
- ULONG ulPhysicalSlot

### 8.816.1 Detailed Description

This structure contains information of the request parameters associated with a Switch Slot.

## Parameters

<i>bLogicalSlot</i>	<ul style="list-style-type: none"><li>• Indicates the slot to be used.<ul style="list-style-type: none"><li>– 1 - Slot 1</li><li>– 2 - Slot 2</li><li>– 3 - Slot 3</li><li>– 4 - Slot 4</li><li>– 5 - Slot 5</li></ul></li></ul>
<i>bPhysicalSlot</i>	<ul style="list-style-type: none"><li>• 1 - Slot 1</li><li>• 2 - Slot 2</li><li>• 3 - Slot 3</li><li>• 4 - Slot 4</li><li>• 5 - Slot 5</li></ul>

## 8.816.2 Field Documentation

8.816.2.1 **BYTE** UIMSwitchSlotReq::bLogicalSlot8.816.2.2 **ULONG** UIMSwitchSlotReq::ulPhysicalSlot

## 8.817 UIMUnblockPinReq Struct Reference

## Data Fields

- [UIMSessionInformation sessionInfo](#)
- [unblockUIMPIN unblockPIN](#)
- **BYTE** \* [pKeyReferenceID](#)
- **ULONG** \* [pIndicationToken](#)

## 8.817.1 Detailed Description

This structure contains information of the request parameters associated with a Unblock PIN API.

## Parameters

<i><a href="#">sessionInfo</a></i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<i><a href="#">unlockPIN</a></i>	<ul style="list-style-type: none"> <li>• See <a href="#">unlockUIMPIN</a> for more information.</li> </ul>
<i><a href="#">pKeyReferenceID(optional)</a></i>	<ul style="list-style-type: none"> <li>• Indicates the PIN key reference ID.</li> <li>• Indicates the PIN key reference ID. Valid values are from 1 to 8, respectively, for application 1 to application 8.</li> <li>• This TLV is used only for PIN1 and PIN2 and is ignored in all other cases.</li> </ul>
<i><a href="#">pIndicationToken(optional)</a></i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

## 8.817.2 Field Documentation

8.817.2.1 **ULONG\*** [UIMUnlockPinReq::pIndicationToken](#)

8.817.2.2 **BYTE\*** [UIMUnlockPinReq::pKeyReferenceID](#)

8.817.2.3 [UIMSessionInformation](#) [UIMUnlockPinReq::sessionInfo](#)

8.817.2.4 [unlockUIMPIN](#) [UIMUnlockPinReq::unlockPIN](#)

## 8.818 UIMVerifyPinReq Struct Reference

## Data Fields

- [UIMSessionInformation](#) [sessionInfo](#)
- [verifyUIMPIN](#) [verifyPIN](#)
- [encryptedPIN1](#) \* [pEncryptedPIN1](#)
- **BYTE** \* [pKeyReferenceID](#)
- **ULONG** \* [pIndicationToken](#)

## 8.818.1 Detailed Description

This structure contains information of the request parameters associated with a verify PIN API.



## Parameters

<a href="#">sessionInfo</a>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSessionInformation</a> for more information.</li> </ul>
<a href="#">verifyPIN</a>	<ul style="list-style-type: none"> <li>• See <a href="#">verifyUIMPIN</a> for more information.</li> </ul>
<a href="#">pEncryptedPIN1(optional)</a>	<ul style="list-style-type: none"> <li>• See <a href="#">encryptedPIN1</a> for more information.</li> </ul>
<a href="#">pKeyReferenceID(optional)</a>	<ul style="list-style-type: none"> <li>• Indicates the PIN key reference ID.</li> <li>• Indicates the PIN key reference ID. Valid values are from 1 to 8, respectively, for application 1 to application 8.</li> <li>• This TLV is used only for PIN1 and PIN2 and is ignored in all other cases.</li> </ul>
<a href="#">pIndicationToken(optional)</a>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

## 8.818.2 Field Documentation

8.818.2.1 [encryptedPIN1](#)\* [UIMVerifyPinReq::pEncryptedPIN1](#)

8.818.2.2 [ULONG](#)\* [UIMVerifyPinReq::pIndicationToken](#)

8.818.2.3 [BYTE](#)\* [UIMVerifyPinReq::pKeyReferenceID](#)

8.818.2.4 [UIMSessionInformation](#) [UIMVerifyPinReq::sessionInfo](#)

8.818.2.5 [verifyUIMPIN](#) [UIMVerifyPinReq::verifyPIN](#)

## 8.819 UMTSInfo Struct Reference

## Data Fields

- [WORD](#) [cellID](#)
- [BYTE](#) [plmn](#) [3]
- [WORD](#) [lac](#)
- [WORD](#) [uarfcn](#)
- [WORD](#) [psc](#)
- [SHORT](#) [rscp](#)
- [SHORT](#) [ecio](#)
- [BYTE](#) [umtsInst](#)
- [UMTSInstInfo](#) [UMTSInstInfo](#) [255]

- [BYTE geranInst](#)
- [geranInstInfo GeranInstInfo](#) [255]

### 8.819.1 Detailed Description

This structure contains information about the UMTS Network.

#### Parameters

<i>cellID</i>	<ul style="list-style-type: none"> <li>• Cell ID.</li> <li>• 0xFFFFFFFF indicates cell ID information is not present.</li> </ul>
<i>plmn[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>• MCC/MNC information coded as octet 3, 4, and 5.</li> <li>• This field is ignored when nmrCellID is not present.</li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• This field is ignored when nmrCellID is not present. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>uarfcn</i>	<ul style="list-style-type: none"> <li>• UTRA absolute RF channel number. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>psc</i>	<ul style="list-style-type: none"> <li>• Primary scrambling code. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>rscp</i>	<ul style="list-style-type: none"> <li>• Received signal code power. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>ecio</i>	<ul style="list-style-type: none"> <li>• ECIO(Signal-to-Interference-ratio). <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>umtsInst</i>	<ul style="list-style-type: none"> <li>• Provides the number of set of UMTS info instances.</li> <li>• If 0(zero), then no information follows it.</li> </ul>

<i>UMTSInstInfo[M-AX_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"> <li>See <a href="#">UMTSInstInfo</a> for more information.</li> </ul>
<i>geranInst</i>	<ul style="list-style-type: none"> <li>Provides the number of set of GERAN info instances.</li> <li>If 0(zero), then no information follows it.</li> </ul>
<i>GeranInstInfo[M-AX_DESCRIPTOR_LENGTH]</i>	<ul style="list-style-type: none"> <li>See <a href="#">geranInstInfo</a> for more information.</li> </ul>

## 8.819.2 Field Documentation

8.819.2.1 WORD UMTSInfo::cellID

8.819.2.2 SHORT UMTSInfo::ecio

8.819.2.3 BYTE UMTSInfo::geranInst

8.819.2.4 [geranInstInfo](#) UMTSInfo::GeranInstInfo[255]

8.819.2.5 WORD UMTSInfo::lac

8.819.2.6 BYTE UMTSInfo::plmn[3]

8.819.2.7 WORD UMTSInfo::psc

8.819.2.8 SHORT UMTSInfo::rscp

8.819.2.9 WORD UMTSInfo::uarfcn

8.819.2.10 BYTE UMTSInfo::umtsInst

8.819.2.11 [UMTSInstInfo](#) UMTSInfo::UMTSInstInfo[255]

## 8.820 UMTSInstInfo Struct Reference

### Data Fields

- [WORD](#) [umtsUarfcn](#)
- [WORD](#) [umtsPsc](#)
- [SHORT](#) [umtsRscp](#)
- [SHORT](#) [umtsEcio](#)

### 8.820.1 Detailed Description

This structure contains information about the UMTS Instances in UMTS Network.

## Parameters

<i>umtsUarfcn</i>	<ul style="list-style-type: none"> <li>• UTRA absolute RF channel number.</li> </ul>
<i>umtsPsc</i>	<ul style="list-style-type: none"> <li>• Primary scrambling code.</li> </ul>
<i>umtsRscp</i>	<ul style="list-style-type: none"> <li>• Received signal code power.</li> </ul>
<i>umtsEcio</i>	<ul style="list-style-type: none"> <li>• ECIO(Signal-to-Interference-ratio).</li> </ul>

## 8.820.2 Field Documentation

8.820.2.1 SHORT UMTSinstInfo::umtsEcio

8.820.2.2 WORD UMTSinstInfo::umtsPsc

8.820.2.3 SHORT UMTSinstInfo::umtsRscp

8.820.2.4 WORD UMTSinstInfo::umtsUarfcn

## 8.821 umtsLTENbrCell Struct Reference

## Data Fields

- [WORD earfcn](#)
- [WORD pci](#)
- [ULONG rsrp](#)
- [ULONG rsrq](#)
- [SHORT srxlev](#)
- [BYTE cellsTDD](#)

## 8.821.1 Detailed Description

This structure contains information about the UMTS LTE neighbour Cell.

## Parameters

<i>earfcn</i>	<ul style="list-style-type: none"> <li>• E-UTRA absolute RF channel number of the detected cell.</li> </ul>
<i>pci</i>	<ul style="list-style-type: none"> <li>• Physical cell ID of the detected cell.</li> <li>• Range is defined in 3GPP TS 36.211</li> </ul>

<i>rsrp</i>	<ul style="list-style-type: none"> <li>Current received signal strength indication (in dBm) of the detected cell.</li> </ul>
<i>rsrq</i>	<ul style="list-style-type: none"> <li>Current reference signal received quality (in dB) of the detected cell.</li> </ul>
<i>srxlev</i>	<ul style="list-style-type: none"> <li>Cell selection Rx level (Srxlev) value of the detected cell in linear scale.</li> <li>This field is only valid when wcdma_rrc_state is not NAS_WCDMA_RRC_STATE_CELL_FACH or NAS_WCDMA_RRC_STATE_CELL_DCH.</li> </ul>
<i>cellsTDD</i>	<ul style="list-style-type: none"> <li>TRUE if the cell is TDD; FALSE if the cell is FDD.</li> </ul>

## 8.821.2 Field Documentation

8.821.2.1 **BYTE** umtsLTENbrCell::cellsTDD

8.821.2.2 **WORD** umtsLTENbrCell::earfcn

8.821.2.3 **WORD** umtsLTENbrCell::pci

8.821.2.4 **ULONG** umtsLTENbrCell::rsrp

8.821.2.5 **ULONG** umtsLTENbrCell::rsrq

8.821.2.6 **SHORT** umtsLTENbrCell::srxlev

## 8.822 UMTSMinQoS Struct Reference

### Data Fields

- [BYTE](#) trafficClass
- [ULONG](#) maxUplinkBitrate
- [ULONG](#) maxDownlinkBitrate
- [ULONG](#) grntUplinkBitrate
- [ULONG](#) grntDownlinkBitrate
- [BYTE](#) qosDeliveryOrder
- [ULONG](#) maxSDUSize
- [BYTE](#) sduErrorRatio
- [BYTE](#) resBerRatio
- [BYTE](#) deliveryErrSDU
- [ULONG](#) transferDelay
- [ULONG](#) trafficPriority

## 8.822.1 Detailed Description

This structure contains the UMTS Quality Of Service Information

## Parameters

<i>trafficClass</i>	<ul style="list-style-type: none"> <li>• 0x00 - Subscribed</li> <li>• 0x01 - Conversational</li> <li>• 0x02 - Streaming</li> <li>• 0x03 - Interactive</li> <li>• 0x04 - Background</li> </ul>
<i>maxUplinkBitrate</i>	<ul style="list-style-type: none"> <li>• Maximum uplink bit rate in bits/sec</li> </ul>
<i>maxDownlink-Bitrate</i>	<ul style="list-style-type: none"> <li>• Maximum downlink bit rate in bits/sec</li> </ul>
<i>grntUplinkBitrate</i>	<ul style="list-style-type: none"> <li>• Guaranteed uplink bit rate in bits/sec</li> </ul>
<i>grntDownlink-Bitrate</i>	<ul style="list-style-type: none"> <li>• Guaranteed downlink bit rate in bits/sec</li> </ul>
<i>qosDelivery-Order</i>	<ul style="list-style-type: none"> <li>- Qos delivery order</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - Delivery order on</li> <li>• 0x02 - Delivery order off</li> </ul>
<i>maxSDUSize</i>	<ul style="list-style-type: none"> <li>• Maximum SDU size</li> </ul>
<i>sduErrorRatio</i>	<ul style="list-style-type: none"> <li>- SDU error ratio</li> <li>• Target value for fraction of SDUs lost or detected as erroneous.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>1 \times 10^{(-2)}</math></li> <li>• 0x02 - <math>7 \times 10^{(-3)}</math></li> <li>• 0x03 - <math>1 \times 10^{(-3)}</math></li> <li>• 0x04 - <math>1 \times 10^{(-4)}</math></li> <li>• 0x05 - <math>1 \times 10^{(-5)}</math></li> <li>• 0x06 - <math>1 \times 10^{(-6)}</math></li> <li>• 0x07 - <math>1 \times 10^{(-1)}</math></li> </ul>

<i>resBerRatio</i>	<p>- Residual bit error ratio</p> <ul style="list-style-type: none"> <li>• Target value for undetected bit error ratio in the delivered SDUs.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>5 \cdot 10^{-2}</math></li> <li>• 0x02 - <math>1 \cdot 10^{-2}</math></li> <li>• 0x03 - <math>5 \cdot 10^{-3}</math></li> <li>• 0x04 - <math>4 \cdot 10^{-3}</math></li> <li>• 0x05 - <math>1 \cdot 10^{-3}</math></li> <li>• 0x06 - <math>1 \cdot 10^{-4}</math></li> <li>• 0x07 - <math>1 \cdot 10^{-5}</math></li> <li>• 0x08 - <math>1 \cdot 10^{-6}</math></li> <li>• 0x09 - <math>1 \cdot 10^{-8}</math></li> </ul>
<i>deliveryErrSDU</i>	<p>- delivery of erroneous SDUs</p> <ul style="list-style-type: none"> <li>• Indicates whether SDUs detected as erroneous shall be delivered or not.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>5 \cdot 10^{-2}</math></li> <li>• 0x02 - <math>1 \cdot 10^{-2}</math></li> <li>• 0x03 - <math>5 \cdot 10^{-3}</math></li> <li>• 0x04 - <math>4 \cdot 10^{-3}</math></li> <li>• 0x05 - <math>1 \cdot 10^{-3}</math></li> <li>• 0x06 - <math>1 \cdot 10^{-4}</math></li> <li>• 0x07 - <math>1 \cdot 10^{-5}</math></li> <li>• 0x08 - <math>1 \cdot 10^{-6}</math></li> <li>• 0x09 - <math>1 \cdot 10^{-8}</math></li> </ul>
<i>transferDelay</i>	<p>- Transfer delay (ms)</p> <ul style="list-style-type: none"> <li>• Indicates the targeted time between a request to transfer an SDU at one SAP to its delivery at the other SAP in milliseconds.</li> </ul>
<i>trafficPriority</i>	<p>- Transfer handling priority</p> <ul style="list-style-type: none"> <li>• Specifies the relative importance for handling of SDUs that belong to the UMTS bearer, compared to the SDUs of other bearers.</li> </ul>

## 8.822.2 Field Documentation

### 8.822.2.1 BYTE UMTSMinQoS::deliveryErrSDU

### 8.822.2.2 ULONG UMTSMinQoS::grntDownlinkBitrate

- 8.822.2.3 **ULONG** UMTSMinQoS::grntUplinkBitrate
- 8.822.2.4 **ULONG** UMTSMinQoS::maxDownlinkBitrate
- 8.822.2.5 **ULONG** UMTSMinQoS::maxSDUSize
- 8.822.2.6 **ULONG** UMTSMinQoS::maxUplinkBitrate
- 8.822.2.7 **BYTE** UMTSMinQoS::qosDeliveryOrder
- 8.822.2.8 **BYTE** UMTSMinQoS::resBerRatio
- 8.822.2.9 **BYTE** UMTSMinQoS::sduErrorRatio
- 8.822.2.10 **BYTE** UMTSMinQoS::trafficClass
- 8.822.2.11 **ULONG** UMTSMinQoS::trafficPriority
- 8.822.2.12 **ULONG** UMTSMinQoS::transferDelay

## 8.823 UMTSQoS Struct Reference

### Data Fields

- [BYTE trafficClass](#)
- [ULONG maxUplinkBitrate](#)
- [ULONG maxDownlinkBitrate](#)
- [ULONG grntUplinkBitrate](#)
- [ULONG grntDownlinkBitrate](#)
- [BYTE qosDeliveryOrder](#)
- [ULONG maxSDUSize](#)
- [BYTE sduErrorRatio](#)
- [BYTE resBerRatio](#)
- [BYTE deliveryErrSDU](#)
- [ULONG transferDelay](#)
- [ULONG trafficPriority](#)

### 8.823.1 Detailed Description

This structure contains the UMTS Quality Of Service Information

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.



## Parameters

<i>trafficClass</i>	<ul style="list-style-type: none"> <li>• 0x00 - Subscribed</li> <li>• 0x01 - Conversational</li> <li>• 0x02 - Streaming</li> <li>• 0x03 - Interactive</li> <li>• 0x04 - Background</li> </ul>
<i>maxUplinkBitrate</i>	<ul style="list-style-type: none"> <li>• Maximum uplink bit rate in bits/sec</li> </ul>
<i>maxDownlink- Bitrate</i>	<ul style="list-style-type: none"> <li>• Maximum downlink bit rate in bits/sec</li> </ul>
<i>grntUplinkBitrate</i>	<ul style="list-style-type: none"> <li>• Guaranteed uplink bit rate in bits/sec</li> </ul>
<i>grntDownlink- Bitrate</i>	<ul style="list-style-type: none"> <li>• Guranteed downlink bit rate in bits/sec</li> </ul>
<i>qosDelivery- Order</i>	<ul style="list-style-type: none"> <li>- Qos delivery order</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - delivery order on</li> <li>• 0x02 - delivery order off</li> </ul>
<i>maxSDUSize</i>	<ul style="list-style-type: none"> <li>• Maximum SDU size</li> </ul>
<i>sduErrorRatio</i>	<ul style="list-style-type: none"> <li>- SDU error ratio</li> <li>• Target value for fraction of SDUs lost or detected as erroneous.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>1 \cdot 10^{-2}</math></li> <li>• 0x02 - <math>7 \cdot 10^{-3}</math></li> <li>• 0x03 - <math>1 \cdot 10^{-3}</math></li> <li>• 0x04 - <math>1 \cdot 10^{-4}</math></li> <li>• 0x05 - <math>1 \cdot 10^{-5}</math></li> <li>• 0x06 - <math>1 \cdot 10^{-6}</math></li> <li>• 0x07 - <math>1 \cdot 10^{-1}</math></li> </ul>

<i>resBerRatio</i>	<p>- Residual bit error ratio</p> <ul style="list-style-type: none"> <li>• Target value for undetected bit error ratio in the delivered SDUs.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>5 \cdot 10^{-2}</math></li> <li>• 0x02 - <math>1 \cdot 10^{-2}</math></li> <li>• 0x03 - <math>5 \cdot 10^{-3}</math></li> <li>• 0x04 - <math>4 \cdot 10^{-3}</math></li> <li>• 0x05 - <math>1 \cdot 10^{-3}</math></li> <li>• 0x06 - <math>1 \cdot 10^{-4}</math></li> <li>• 0x07 - <math>1 \cdot 10^{-5}</math></li> <li>• 0x08 - <math>1 \cdot 10^{-6}</math></li> <li>• 0x09 - <math>1 \cdot 10^{-8}</math></li> </ul>
<i>deliveryErrSDU</i>	<p>- Delivery of erroneous SDUs</p> <ul style="list-style-type: none"> <li>• Indicates whether SDUs detected as erroneous shall be delivered or not.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>5 \cdot 10^{-2}</math></li> <li>• 0x02 - <math>1 \cdot 10^{-2}</math></li> <li>• 0x03 - <math>5 \cdot 10^{-3}</math></li> <li>• 0x04 - <math>4 \cdot 10^{-3}</math></li> <li>• 0x05 - <math>1 \cdot 10^{-3}</math></li> <li>• 0x06 - <math>1 \cdot 10^{-4}</math></li> <li>• 0x07 - <math>1 \cdot 10^{-5}</math></li> <li>• 0x08 - <math>1 \cdot 10^{-6}</math></li> <li>• 0x09 - <math>1 \cdot 10^{-8}</math></li> </ul>

<i>transferDelay</i>	- Transfer delay (ms) <ul style="list-style-type: none"> <li>Indicates the targeted time between a request to transfer an SDU at one SAP to its delivery at the other SAP in milliseconds.</li> </ul>
<i>trafficPriority</i>	- Transfer handling priority <ul style="list-style-type: none"> <li>Specifies the relative importance for handling of SDUs that belong to the UMTS bearer, compared to the SDUs of other bearers.</li> </ul>

## 8.823.2 Field Documentation

8.823.2.1 **BYTE** UMTSQoS::deliveryErrSDU

8.823.2.2 **ULONG** UMTSQoS::grntDownlinkBitrate

8.823.2.3 **ULONG** UMTSQoS::grntUplinkBitrate

8.823.2.4 **ULONG** UMTSQoS::maxDownlinkBitrate

8.823.2.5 **ULONG** UMTSQoS::maxSDUSize

8.823.2.6 **ULONG** UMTSQoS::maxUplinkBitrate

8.823.2.7 **BYTE** UMTSQoS::qosDeliveryOrder

8.823.2.8 **BYTE** UMTSQoS::resBerRatio

8.823.2.9 **BYTE** UMTSQoS::sduErrorRatio

8.823.2.10 **BYTE** UMTSQoS::trafficClass

8.823.2.11 **ULONG** UMTSQoS::trafficPriority

8.823.2.12 **ULONG** UMTSQoS::transferDelay

## 8.824 UMTSReqQoSsigInd Struct Reference

### Data Fields

- struct [UMTSQoS](#) [UMTSReqQoS](#)
- [BYTE](#) [SigInd](#)

### 8.824.1 Detailed Description

structure contains UMTS requested QoS with Signaling Indication flag

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

## Parameters

<i>UMTSReqQoS</i>	<ul style="list-style-type: none"> <li>• Contains the UMTS Quality Of Service Information</li> </ul>
<i>SigInd</i>	<ul style="list-style-type: none"> <li>- Signaling Indication flag</li> <li>• TRUE - Signaling indication ON</li> <li>• FALSE - Signaling indication OFF</li> </ul>

## 8.824.2 Field Documentation

8.824.2.1 BYTE UMTSReqQoS*SigInd*::*SigInd*8.824.2.2 struct UMTSQoS UMTSReqQoS*SigInd*::UMTSReqQoS

## 8.825 unblockUIMPIN Struct Reference

## Data Fields

- [BYTE pinID](#)
- [BYTE pukLen](#)
- [BYTE pukVal \[255\]](#)
- [BYTE newPINLen](#)
- [BYTE newPINVal \[255\]](#)

## 8.825.1 Detailed Description

This structure contains the information about the unblock pin parameters.

## Parameters

<i>pinID</i>	<ul style="list-style-type: none"> <li>• Indicates the PIN ID to be changed. <ul style="list-style-type: none"> <li>– 1 - PIN1 (also called PIN)</li> <li>– 2 - PIN2</li> <li>– 3 - Universal PIN</li> </ul> </li> </ul>
<i>pukLen</i>	<ul style="list-style-type: none"> <li>• Length of the following elements i.e. puk value.</li> </ul>
<i>pukVal</i> [MAX_P-UK_LENGTH]	<ul style="list-style-type: none"> <li>• PIN Unlock Key value.</li> <li>• This value is a sequence of ASCII characters.</li> </ul>

<i>pinLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. new pin value.</li> </ul>
<i>pinVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>New PIN value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

## 8.825.2 Field Documentation

8.825.2.1 **BYTE** unblockUIMPIN::newPINLen

8.825.2.2 **BYTE** unblockUIMPIN::newPINVal[255]

8.825.2.3 **BYTE** unblockUIMPIN::pinID

8.825.2.4 **BYTE** unblockUIMPIN::pukLen

8.825.2.5 **BYTE** unblockUIMPIN::pukVal[255]

## 8.826 UniversalTime Struct Reference

### Data Fields

- [WORD](#) year
- [BYTE](#) month
- [BYTE](#) day
- [BYTE](#) hour
- [BYTE](#) minute
- [BYTE](#) second
- [BYTE](#) dayOfWeek

### 8.826.1 Detailed Description

This structure contains the parameters for Universal Time Information.

#### Parameters

<i>year</i>	<ul style="list-style-type: none"> <li>Year.</li> </ul>
<i>month</i>	<ul style="list-style-type: none"> <li>Month. <ul style="list-style-type: none"> <li>1 is January and 12 is December.</li> </ul> </li> </ul>

<i>day</i>	<ul style="list-style-type: none"> <li>• Day. <ul style="list-style-type: none"> <li>– Range 1 to 31.</li> </ul> </li> </ul>
<i>hour</i>	<ul style="list-style-type: none"> <li>• Hour. <ul style="list-style-type: none"> <li>– Range 0 to 59.</li> </ul> </li> </ul>
<i>minute</i>	<ul style="list-style-type: none"> <li>• Minute. <ul style="list-style-type: none"> <li>– Range 0 to 59.</li> </ul> </li> </ul>
<i>second</i>	<ul style="list-style-type: none"> <li>• Second. <ul style="list-style-type: none"> <li>– Range 0 to 59.</li> </ul> </li> </ul>
<i>dayOfWeek</i>	<ul style="list-style-type: none"> <li>• Day of the Week. <ul style="list-style-type: none"> <li>– 0 is Monday and 6 is Sunday.</li> </ul> </li> </ul>

## 8.826.2 Field Documentation

### 8.826.2.1 BYTE UniversalTime::day

### 8.826.2.2 BYTE UniversalTime::dayOfWeek

### 8.826.2.3 BYTE UniversalTime::hour

### 8.826.2.4 BYTE UniversalTime::minute

### 8.826.2.5 BYTE UniversalTime::month

### 8.826.2.6 BYTE UniversalTime::second

### 8.826.2.7 WORD UniversalTime::year

## 8.827 unpack\_dms\_GetActivationState\_t Struct Reference

### Data Fields

- [uint8\\_t state](#)

### 8.827.1 Detailed Description

## Parameters

<i>pActivation-State[OUT]</i>	<ul style="list-style-type: none"> <li>• Service Activation Code <ul style="list-style-type: none"> <li>0 - Service not activated</li> <li>1 - Service activated</li> <li>2 - Activation connecting</li> <li>3 - Activation connected</li> <li>4 - OTASP security authenticated</li> <li>5 - OTASP NAM downloaded</li> <li>6 - OTASP MDN downloaded</li> <li>7 - OTASP IMSI downloaded</li> <li>8 - OTASP PRL downloaded</li> <li>9 - OTASP SPC downloaded</li> <li>10 - OTASP settings committed</li> </ul> </li> </ul>
-------------------------------	--

## 8.827.2 Field Documentation

8.827.2.1 uint8\_t unpack\_dms\_GetActivationState\_t::state

## 8.828 unpack\_dms\_GetBandCapability\_t Struct Reference

## Data Fields

- uint32\_t [BandCapability](#)
- uint16\_t [Tlvresult](#)

## 8.828.1 Field Documentation

8.828.1.1 uint32\_t unpack\_dms\_GetBandCapability\_t::BandCapability

8.828.1.2 uint16\_t unpack\_dms\_GetBandCapability\_t::Tlvresult

## 8.829 unpack\_dms\_GetCrashAction\_t Struct Reference

## Data Fields

- uint8\_t [DevCrashState](#)
- uint16\_t [Tlvresult](#)

## 8.829.1 Field Documentation

8.829.1.1 uint8\_t unpack\_dms\_GetCrashAction\_t::DevCrashState

8.829.1.2 uint16\_t unpack\_dms\_GetCrashAction\_t::Tlvresult

## 8.830 unpack\_dms\_GetCustFeature\_t Struct Reference

## Data Fields

- uint32\_t [GpsEnable](#)
- uint8\_t [DisableIMSI](#)
- uint16\_t [IPFamSupport](#)
- uint8\_t [RMAutoConnect](#)
- uint8\_t [GPSSel](#)
- uint8\_t [SMSSupport](#)
- uint8\_t [IsVoiceEnabled](#)
- uint8\_t [DHCPRelayEnabled](#)
- uint8\_t [GPSLPM](#)
- uint16\_t [Tlvresult](#)

### 8.830.1 Field Documentation

8.830.1.1 uint8\_t unpack\_dms\_GetCustFeature\_t::DHCPRelayEnabled

8.830.1.2 uint8\_t unpack\_dms\_GetCustFeature\_t::DisableIMSI

8.830.1.3 uint32\_t unpack\_dms\_GetCustFeature\_t::GpsEnable

8.830.1.4 uint8\_t unpack\_dms\_GetCustFeature\_t::GPSPMP

8.830.1.5 uint8\_t unpack\_dms\_GetCustFeature\_t::GPSSel

8.830.1.6 uint16\_t unpack\_dms\_GetCustFeature\_t::IPFamSupport

8.830.1.7 uint8\_t unpack\_dms\_GetCustFeature\_t::IsVoiceEnabled

8.830.1.8 uint8\_t unpack\_dms\_GetCustFeature\_t::RMAutoConnect

8.830.1.9 uint8\_t unpack\_dms\_GetCustFeature\_t::SMSSupport

8.830.1.10 uint16\_t unpack\_dms\_GetCustFeature\_t::Tlvresult

## 8.831 unpack\_dms\_GetCustFeaturesV2\_t Struct Reference

### Data Fields

- [DMSgetCustomFeatureV2 GetCustomFeatureV2](#)
- uint16\_t [Tlvresult](#)

### 8.831.1 Detailed Description

This structure contains customization settings set to modem unpack

#### Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack Result</li> </ul>
------------------	---



### 8.831.2 Field Documentation

8.831.2.1 DMSgetCustomFeatureV2 unpack\_dms\_GetCustFeaturesV2\_t::GetCustomFeatureV2

8.831.2.2 uint16\_t unpack\_dms\_GetCustFeaturesV2\_t::Tlvresult

## 8.832 unpack\_dms\_GetDeviceCap\_t Struct Reference

### Data Fields

- uint32\_t [MaxTXChannelRate](#)
- uint32\_t [MaxRXChannelRate](#)
- uint32\_t [DataServiceCapability](#)
- uint32\_t [SimCapability](#)
- uint32\_t [RadiolfacesSize](#)
- uint8\_t [Radiolfaces](#) [64]
- uint16\_t [Tlvresult](#)

### 8.832.1 Field Documentation

8.832.1.1 uint32\_t unpack\_dms\_GetDeviceCap\_t::DataServiceCapability

8.832.1.2 uint32\_t unpack\_dms\_GetDeviceCap\_t::MaxRXChannelRate

8.832.1.3 uint32\_t unpack\_dms\_GetDeviceCap\_t::MaxTXChannelRate

8.832.1.4 uint8\_t unpack\_dms\_GetDeviceCap\_t::Radiolfaces[64]

8.832.1.5 uint32\_t unpack\_dms\_GetDeviceCap\_t::RadiolfacesSize

8.832.1.6 uint32\_t unpack\_dms\_GetDeviceCap\_t::SimCapability

8.832.1.7 uint16\_t unpack\_dms\_GetDeviceCap\_t::Tlvresult

## 8.833 unpack\_dms\_GetDeviceCapabilities\_t Struct Reference

### Data Fields

- uint32\_t [maxTxChannelRate](#)
- uint32\_t [maxRxChannelRate](#)
- uint32\_t [dataServiceCaCapability](#)
- uint32\_t [simCapability](#)
- uint32\_t [radiolfacesSize](#)
- uint8\_t [Radiolfaces](#) [255]

### 8.833.1 Detailed Description

#### Parameters

---

<i>maxTxChannel-Rate</i>	Maximum Tx transmission rate in bits per second.
<i>maxRxChannel-Rate</i>	Maximum Rx transmission rate in bits per second
<i>dataServiceCaCapability</i>	data service capability
<i>simCapability</i>	SIM Capability
<i>radiofacesSize</i>	radio interface length
<i>Radiofaces</i>	radio interfaces

### 8.833.2 Field Documentation

8.833.2.1 `uint32_t unpack_dms_GetDeviceCapabilities_t::dataServiceCaCapability`

8.833.2.2 `uint32_t unpack_dms_GetDeviceCapabilities_t::maxRxChannelRate`

8.833.2.3 `uint32_t unpack_dms_GetDeviceCapabilities_t::maxTxChannelRate`

8.833.2.4 `uint8_t unpack_dms_GetDeviceCapabilities_t::Radiofaces[255]`

8.833.2.5 `uint32_t unpack_dms_GetDeviceCapabilities_t::radiofacesSize`

8.833.2.6 `uint32_t unpack_dms_GetDeviceCapabilities_t::simCapability`

## 8.834 unpack\_dms\_GetDeviceHardwareRev\_t Struct Reference

### Data Fields

- `uint8_t stringSize`
- `char String [255]`
- `uint16_t Tlvresult`

### 8.834.1 Field Documentation

8.834.1.1 `char unpack_dms_GetDeviceHardwareRev_t::String[255]`

8.834.1.2 `uint8_t unpack_dms_GetDeviceHardwareRev_t::stringSize`

8.834.1.3 `uint16_t unpack_dms_GetDeviceHardwareRev_t::Tlvresult`

## 8.835 unpack\_dms\_GetDeviceMfr\_t Struct Reference

### Data Fields

- `uint8_t stringSize`
- `char String [255]`
- `uint16_t Tlvresult`

### 8.835.1 Field Documentation

8.835.1.1 `char unpack_dms_GetDeviceMfr_t::String[255]`

8.835.1.2 uint8\_t unpack\_dms\_GetDeviceMfr\_t::stringSize

8.835.1.3 uint16\_t unpack\_dms\_GetDeviceMfr\_t::Tlvresult

## 8.836 unpack\_dms\_GetDeviceSerialNumbers\_t Struct Reference

### Data Fields

- uint8\_t [esnSize](#)
- char [ESNString](#) [255]
- uint8\_t [imeiSize](#)
- char [IMEIString](#) [255]
- uint8\_t [meidSize](#)
- char [MEIDString](#) [255]
- uint8\_t [imeiSvnSize](#)
- char [ImeiSvnString](#) [255]
- uint16\_t [Tlvresult](#)

### 8.836.1 Field Documentation

8.836.1.1 uint8\_t unpack\_dms\_GetDeviceSerialNumbers\_t::esnSize

8.836.1.2 char unpack\_dms\_GetDeviceSerialNumbers\_t::ESNString[255]

8.836.1.3 uint8\_t unpack\_dms\_GetDeviceSerialNumbers\_t::imeiSize

8.836.1.4 char unpack\_dms\_GetDeviceSerialNumbers\_t::IMEIString[255]

8.836.1.5 uint8\_t unpack\_dms\_GetDeviceSerialNumbers\_t::imeiSvnSize

8.836.1.6 char unpack\_dms\_GetDeviceSerialNumbers\_t::ImeiSvnString[255]

8.836.1.7 uint8\_t unpack\_dms\_GetDeviceSerialNumbers\_t::meidSize

8.836.1.8 char unpack\_dms\_GetDeviceSerialNumbers\_t::MEIDString[255]

8.836.1.9 uint16\_t unpack\_dms\_GetDeviceSerialNumbers\_t::Tlvresult

## 8.837 unpack\_dms\_GetFirmwareInfo\_t Struct Reference

### Data Fields

- char [modelid\\_str](#) [20]
- char [bootversion\\_str](#) [85]
- char [appversion\\_str](#) [85]
- char [sku\\_str](#) [15]
- char [packageid\\_str](#) [85]
- char [carrier\\_str](#) [20]
- char [priversion\\_str](#) [16]
- char [cur\\_carr\\_name](#) [17]
- char [cur\\_carr\\_rev](#) [13]
- uint16\_t [Tlvresult](#)

### 8.837.1 Detailed Description

## Parameters

<i>modelid_str</i>	Mode ID String.
<i>bootversion_str</i>	Boot Version.
<i>appversion_str</i>	Application Version String.
<i>sku_str</i>	SKU String.
<i>packageid_str</i>	<ul style="list-style-type: none"> <li>• Package ID String.</li> <li>• deprecated on EM/MC74xx(9x30) devices</li> </ul>
<i>carrier_str</i>	Carrier String.
<i>priversion_str</i>	PRI Version String.
<i>priversion_str</i>	PRI Version String.
<i>cur_carr_name</i>	Current Carrier Name String.
<i>cur_carr_rev</i>	Current Carrier Revision String.
<i>Tlvresult</i>	Tlv Result.

## 8.837.2 Field Documentation

8.837.2.1 char unpack\_dms\_GetFirmwareInfo\_t::appversion\_str[85]

8.837.2.2 char unpack\_dms\_GetFirmwareInfo\_t::bootversion\_str[85]

8.837.2.3 char unpack\_dms\_GetFirmwareInfo\_t::carrier\_str[20]

8.837.2.4 char unpack\_dms\_GetFirmwareInfo\_t::cur\_carr\_name[17]

8.837.2.5 char unpack\_dms\_GetFirmwareInfo\_t::cur\_carr\_rev[13]

8.837.2.6 char unpack\_dms\_GetFirmwareInfo\_t::modelid\_str[20]

8.837.2.7 char unpack\_dms\_GetFirmwareInfo\_t::packageid\_str[85]

8.837.2.8 char unpack\_dms\_GetFirmwareInfo\_t::priversion\_str[16]

8.837.2.9 char unpack\_dms\_GetFirmwareInfo\_t::sku\_str[15]

8.837.2.10 uint16\_t unpack\_dms\_GetFirmwareInfo\_t::Tlvresult

## 8.838 unpack\_dms\_GetFirmwareRevision\_t Struct Reference

## Data Fields

- uint8\_t [amssSize](#)
- char [AMSSString](#) [255]
- char [PRIString](#) [255]
- uint16\_t [Tlvresult](#)

## 8.838.1 Field Documentation

8.838.1.1 uint8\_t unpack\_dms\_GetFirmwareRevision\_t::amssSize

8.838.1.2 char unpack\_dms\_GetFirmwareRevision\_t::AMSSString[255]

8.838.1.3 char unpack\_dms\_GetFirmwareRevision\_t::PRIString[255]

8.838.1.4 uint16\_t unpack\_dms\_GetFirmwareRevision\_t::Tlvresult

## 8.839 unpack\_dms\_GetFirmwareRevisions\_t Struct Reference

### Data Fields

- uint8\_t [amssSize](#)
- char [AMSSString](#) [255]
- uint8\_t [bootSize](#)
- char [BootString](#) [255]
- uint8\_t [priSize](#)
- char [PRIString](#) [255]
- uint16\_t [Tlvresult](#)

### 8.839.1 Detailed Description

#### Parameters

<i>amssstring</i>	AMSS revision string
<i>bootstring</i>	boot code revision string
<i>pristring</i>	PRI revision string

### 8.839.2 Field Documentation

8.839.2.1 uint8\_t unpack\_dms\_GetFirmwareRevisions\_t::amssSize

8.839.2.2 char unpack\_dms\_GetFirmwareRevisions\_t::AMSSString[255]

8.839.2.3 uint8\_t unpack\_dms\_GetFirmwareRevisions\_t::bootSize

8.839.2.4 char unpack\_dms\_GetFirmwareRevisions\_t::BootString[255]

8.839.2.5 uint8\_t unpack\_dms\_GetFirmwareRevisions\_t::priSize

8.839.2.6 char unpack\_dms\_GetFirmwareRevisions\_t::PRIString[255]

8.839.2.7 uint16\_t unpack\_dms\_GetFirmwareRevisions\_t::Tlvresult

## 8.840 unpack\_dms\_GetFSN\_t Struct Reference

### Data Fields

- char [String](#) [255]
- uint16\_t [Tlvresult](#)

### 8.840.1 Field Documentation

8.840.1.1 char unpack\_dms\_GetFSN\_t::String[255]

8.840.1.2 uint16\_t unpack\_dms\_GetFSN\_t::Tlvresult

## 8.841 unpack\_dms\_GetHardwareRevision\_t Struct Reference

### Data Fields

- char [hwVer](#) [255]

### 8.841.1 Detailed Description

#### Parameters

<i>hwVer</i>	hardware vesion
--------------	-----------------

### 8.841.2 Field Documentation

8.841.2.1 char unpack\_dms\_GetHardwareRevision\_t::hwVer[255]

## 8.842 unpack\_dms\_GetIMSI\_t Struct Reference

### Data Fields

- char [imsi](#) [255]
- uint16\_t [Tlvresult](#)

### 8.842.1 Field Documentation

8.842.1.1 char unpack\_dms\_GetIMSI\_t::imsi[255]

8.842.1.2 uint16\_t unpack\_dms\_GetIMSI\_t::Tlvresult

## 8.843 unpack\_dms\_GetModelID\_t Struct Reference

### Data Fields

- char [modelid](#) [255]
- uint16\_t [Tlvresult](#)

### 8.843.1 Detailed Description

#### Parameters

<i>modelid</i>	device model id
----------------	-----------------

### 8.843.2 Field Documentation

8.843.2.1 char unpack\_dms\_GetModelID\_t::modelid[255]

8.843.2.2 uint16\_t unpack\_dms\_GetModelID\_t::Tlvresult

## 8.844 unpack\_dms\_GetNetworkTime\_t Struct Reference

## Data Fields

- uint16\_t [source](#)
- uint64\_t [timestamp](#)
- uint16\_t [Tlvresult](#)

### 8.844.1 Detailed Description

#### Parameters

<i>source</i>	<ul style="list-style-type: none"> <li>• Source of timestamp 0 - 32 kHz device clock 1 - CDMA network 2 - cdma2000 1xEV-DO network</li> </ul>
<i>timestamp</i>	<ul style="list-style-type: none"> <li>• Count of 1.25 ms that have elapsed from the start of GPS time (Jan 6, 1980)</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack Result</li> </ul>

#### Note

The source of the timestamp provided specifies how the timestamp was determined. The first network time that is available will be returned. If no network time is available, the timestamp is taken from the 32 kHz slow-clock of the device.

### 8.844.2 Field Documentation

8.844.2.1 uint16\_t unpack\_dms\_GetNetworkTime\_t::source

8.844.2.2 uint64\_t unpack\_dms\_GetNetworkTime\_t::timestamp

8.844.2.3 uint16\_t unpack\_dms\_GetNetworkTime\_t::Tlvresult

### 8.845 unpack\_dms\_GetPower\_t Struct Reference

## Data Fields

- uint32\_t [OperationMode](#)
- uint32\_t [OfflineReason](#)
- uint32\_t [HardwareControlledMode](#)
- uint16\_t [Tlvresult](#)

### 8.845.1 Detailed Description



## Parameters

<i>OperationMode</i>	operating mode
<i>OfflineReason</i>	offline reason
<i>Hardware-ControlledMode</i>	hardware restricted mode

## 8.845.2 Field Documentation

8.845.2.1 uint32\_t unpack\_dms\_GetPower\_t::HardwareControlledMode

8.845.2.2 uint32\_t unpack\_dms\_GetPower\_t::OfflineReason

8.845.2.3 uint32\_t unpack\_dms\_GetPower\_t::OperationMode

8.845.2.4 uint16\_t unpack\_dms\_GetPower\_t::Tlvresult

## 8.846 unpack\_dms\_GetPRLVersion\_t Struct Reference

## Data Fields

- uint8\_t [u8PRLPreference](#)
- uint16\_t [u16PRLVersion](#)
- uint16\_t [Tlvresult](#)

## 8.846.1 Field Documentation

8.846.1.1 uint16\_t unpack\_dms\_GetPRLVersion\_t::Tlvresult

8.846.1.2 uint16\_t unpack\_dms\_GetPRLVersion\_t::u16PRLVersion

8.846.1.3 uint8\_t unpack\_dms\_GetPRLVersion\_t::u8PRLPreference

## 8.847 unpack\_dms\_GetSerialNumbers\_t Struct Reference

## Data Fields

- char [esn](#) [255]
- char [imei\\_no](#) [255]
- char [meid](#) [255]
- char [imeisv\\_svn](#) [255]

## 8.847.1 Detailed Description

## Parameters

<i>esn</i>	Electronic Serial Number of the device
<i>imei_no</i>	International Mobile Equipment Identity of the device.
<i>meid</i>	Mobile Equipment Identifier of the device.

<i>imeisv_svn</i>	imei software version revision
-------------------	--------------------------------

## 8.847.2 Field Documentation

8.847.2.1 char unpack\_dms\_GetSerialNumbers\_t::esn[255]

8.847.2.2 char unpack\_dms\_GetSerialNumbers\_t::imei\_no[255]

8.847.2.3 char unpack\_dms\_GetSerialNumbers\_t::imeisv\_svn[255]

8.847.2.4 char unpack\_dms\_GetSerialNumbers\_t::meid[255]

## 8.848 unpack\_dms\_GetUSBComp\_t Struct Reference

### Data Fields

- uint8\_t [USBComp](#) [255]
- uint8\_t [NumSupUSBComps](#)
- uint8\_t [SupUSBComps](#)
- uint16\_t [Tlvresult](#)

### 8.848.1 Field Documentation

8.848.1.1 uint8\_t unpack\_dms\_GetUSBComp\_t::NumSupUSBComps

8.848.1.2 uint8\_t unpack\_dms\_GetUSBComp\_t::SupUSBComps

8.848.1.3 uint16\_t unpack\_dms\_GetUSBComp\_t::Tlvresult

8.848.1.4 uint8\_t unpack\_dms\_GetUSBComp\_t::USBComp[255]

## 8.849 unpack\_dms\_GetVoiceNumber\_t Struct Reference

### Data Fields

- uint8\_t [voiceNumberSize](#)
- char [VoiceNumber](#) [255]
- uint8\_t [minSize](#)
- char [MIN](#) [255]
- uint16\_t [Tlvresult](#)

### 8.849.1 Field Documentation

8.849.1.1 char unpack\_dms\_GetVoiceNumber\_t::MIN[255]

8.849.1.2 uint8\_t unpack\_dms\_GetVoiceNumber\_t::minSize

8.849.1.3 uint16\_t unpack\_dms\_GetVoiceNumber\_t::Tlvresult

8.849.1.4 char unpack\_dms\_GetVoiceNumber\_t::VoiceNumber[255]

8.849.1.5 uint8\_t unpack\_dms\_GetVoiceNumber\_t::voiceNumberSize

## 8.850 unpack\_dms\_SetCrashAction\_t Struct Reference

### Data Fields

- uint8\_t [notused](#)

#### 8.850.1 Detailed Description

Modem response. Not used

#### 8.850.2 Field Documentation

8.850.2.1 uint8\_t unpack\_dms\_SetCrashAction\_t::notused

## 8.851 unpack\_dms\_SetCustFeature\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

#### 8.851.1 Field Documentation

8.851.1.1 uint16\_t unpack\_dms\_SetCustFeature\_t::Tlvresult

## 8.852 unpack\_dms\_SetCustFeaturesV2\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

#### 8.852.1 Detailed Description

This structure contains customization settings set to modem unpack

Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Unpack Result</li></ul>
------------------	---

#### 8.852.2 Field Documentation

8.852.2.1 uint16\_t unpack\_dms\_SetCustFeaturesV2\_t::Tlvresult

## 8.853 unpack\_dms\_SetEventReport\_ind\_t Struct Reference

## Data Fields

- [dms\\_ActivationStatusTlv](#) `ActivationStatusTlv`
- [dms\\_OperatingModeTlv](#) `OperatingModeTlv`
- `uint16_t` [Tlvresult](#)

### 8.853.1 Detailed Description

DMS Event Report indication structure

Parameters

<i>ActivationStatus-Tlv</i>	<ul style="list-style-type: none"> <li>• See <a href="#">dms_ActivationStatusTlv</a></li> </ul>
<i>OperatingMode-Tlv</i>	<ul style="list-style-type: none"> <li>• See <a href="#">dms_OperatingModeTlv</a></li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack Result</li> </ul>

### 8.853.2 Field Documentation

8.853.2.1 `dms_ActivationStatusTlv` `unpack_dms_SetEventReport_ind_t::ActivationStatusTlv`

8.853.2.2 `dms_OperatingModeTlv` `unpack_dms_SetEventReport_ind_t::OperatingModeTlv`

8.853.2.3 `uint16_t` `unpack_dms_SetEventReport_ind_t::Tlvresult`

## 8.854 `unpack_dms_SetEventReport_t` Struct Reference

### Data Fields

- `uint16_t` [Tlvresult](#)

### 8.854.1 Field Documentation

8.854.1.1 `uint16_t` `unpack_dms_SetEventReport_t::Tlvresult`

## 8.855 `unpack_dms_SetFirmwarePreference_t` Struct Reference

### Data Fields

- `uint16_t` [Tlvresult](#)

### 8.855.1 Field Documentation

8.855.1.1 `uint16_t` `unpack_dms_SetFirmwarePreference_t::Tlvresult`

## 8.856 unpack\_dms\_SetPower\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.856.1 Field Documentation

8.856.1.1 uint16\_t unpack\_dms\_SetPower\_t::Tlvresult

## 8.857 unpack\_dms\_SetUSBComp\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.857.1 Field Documentation

8.857.1.1 uint16\_t unpack\_dms\_SetUSBComp\_t::Tlvresult

## 8.858 unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind\_t Struct Reference

### Data Fields

- uint8\_t [type](#)
- uint8\_t [source](#)
- uint16\_t [Tlvresult](#)

### 8.858.1 Detailed Description

This structure contains the TLV required to Get Reset Info.

#### Parameters

<i>OUT</i>	type[OUT]
	<ul style="list-style-type: none"><li>• type of reset or power down, possible values listed below:<ul style="list-style-type: none"><li>– 0 - unknown</li><li>– 1 - warm</li><li>– 2 - hard</li><li>– 3 - crash</li><li>– 4 - power down</li></ul></li></ul>

<i>OUT]</i>	source[OUT] <ul style="list-style-type: none"> <li>entity which initiated the reset or power down, possible values listed below:             <ul style="list-style-type: none"> <li>0 - unknown</li> <li>1 - user requested ( AT!RESET, AT!BOOTHOLD, FW/PRI download – including host-initiated image switching)</li> <li>2 - hardware switch (W_DISABLE)</li> <li>3 - temperature critical</li> <li>4 - voltage critical</li> <li>5 - configuration update (SIM-based image switching, RMA reset, NVUPs which request a reset)</li> <li>6 - LWM2M (Light Weight M2M client (internal process for LWM2M))</li> <li>7 - OMA-DM</li> <li>8 - FOTA</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>Unpack Result</li> </ul>

## 8.858.2 Field Documentation

8.858.2.1 uint8\_t unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind\_t::source

8.858.2.2 uint16\_t unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind\_t::Tlvresult

8.858.2.3 uint8\_t unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind\_t::type

## 8.859 unpack\_dms\_SLQSDmsSwiGetResetInfo\_t Struct Reference

### Data Fields

- uint8\_t [type](#)
- uint8\_t [source](#)
- uint16\_t [Tlvresult](#)

### 8.859.1 Detailed Description

This structure contains the TLV required to Get Reset Info.

## Parameters

<i>OUT]</i>	type[OUT] <ul style="list-style-type: none"> <li>• type of reset or power down, possible values listed below:             <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - warm</li> <li>– 2 - hard</li> <li>– 3 - crash</li> <li>– 4 - power down</li> </ul> </li> </ul>
<i>OUT]</i>	source[OUT] <ul style="list-style-type: none"> <li>• entity which initiated the reset or power down, possible values listed below:             <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - user requested ( AT!RESET, AT!BOOTHOLD, FW/PRI download – including host-initiated image switching)</li> <li>– 2 - hardware switch (W_DISABLE)</li> <li>– 3 - temperature critical</li> <li>– 4 - voltage critical</li> <li>– 5 - configuration update (SIM-based image switching, RMA reset, NVUPs which request a reset)</li> <li>– 6 - LWM2M (Light Weight M2M client (internal process for LWM2M))</li> <li>– 7 - OMA-DM</li> <li>– 8 - FOTA</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack Result</li> </ul>

## 8.859.2 Field Documentation

8.859.2.1 uint8\_t unpack\_dms\_SLQSDmsSwiGetResetInfo\_t::source

8.859.2.2 uint16\_t unpack\_dms\_SLQSDmsSwiGetResetInfo\_t::Tlvresult

8.859.2.3 uint8\_t unpack\_dms\_SLQSDmsSwiGetResetInfo\_t::type

## 8.860 unpack\_dms\_SLQSDmsSwiIndicationRegister\_t Struct Reference

## Data Fields

- uint16\_t [Tlvresult](#)

## 8.860.1 Detailed Description

This structure contains set registration state for different indication unpack

## Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Unpack Result</li></ul>
------------------	---

## 8.860.2 Field Documentation

8.860.2.1 uint16\_t unpack\_dms\_SLQSDmsSwiIndicationRegister\_t::Tlvresult

## 8.861 unpack\_dms\_SLQSGetBandCapability\_t Struct Reference

### Data Fields

- uint64\_t [bandCapability](#)
- int [is\\_LteBandCapability\\_Available](#)
- uint64\_t [LteBandCapability](#)
- int [is\\_TdsBandCapability\\_Available](#)
- uint64\_t [TdsBandCapability](#)

### 8.861.1 Detailed Description

This structure contains the Band Capabilities response.

Please check is\_<Param\_Name>\_Available field for presence of optional parameters



## Parameters

<i>bandCapability[OUT]</i>	<p>Bitmask of bands supported by the device</p> <ul style="list-style-type: none"> <li>• Bit 0 - Band class 0, A-system</li> <li>• Bit 1 - Band class 0, B-system</li> <li>• Bit 2 - Band class 1, all blocks</li> <li>• Bit 3 - Band class 2</li> <li>• Bit 4 - Band class 3, A-system</li> <li>• Bit 5 - Band class 4, all blocks</li> <li>• Bit 6 - Band class 5, all blocks</li> <li>• Bit 7 - GSM DCS band (1800)</li> <li>• Bit 8 - GSM Extended GSM (E-GSM) band (900)</li> <li>• Bit 9 - GSM Primary GSM (P-GSM) band (900)</li> <li>• Bit 10 - Band class 6</li> <li>• Bit 11 - Band class 7</li> <li>• Bit 12 - Band class 8</li> <li>• Bit 13 - Band class 9</li> <li>• Bit 14 - Band class 10</li> <li>• Bit 15 - Band class 11</li> <li>• Bit 16 - GSM 450 band</li> <li>• Bit 17 - GSM 480 band</li> <li>• Bit 18 - GSM 750 band</li> <li>• Bit 19 - GSM 850 band</li> <li>• Bit 20 - GSM railways GSM band (900)</li> <li>• Bit 21 - GSM PCS band (1900)</li> <li>• Bit 22 - WCDMA (Europe, Japan, and China) 2100 band</li> <li>• Bit 23 - WCDMA US PCS 1900 band</li> <li>• Bit 24 - WCDMA (Europe and China) DCS 1800 band</li> <li>• Bit 25 - WCDMA US 1700 band</li> <li>• Bit 26 - WCDMA US 850 band</li> <li>• Bit 27 - WCDMA Japan 800 band</li> <li>• Bit 28 - Band class 12</li> <li>• Bit 29 - Band class 14</li> <li>• Bit 30 - Reserved</li> <li>• Bit 31 - Band class 15</li> <li>• Bits 32 through 47 - Reserved</li> <li>• Bit 48 - WCDMA Europe 2600 band</li> <li>• Bit 49 - WCDMA Europe and Japan 900 band</li> <li>• Bit 50 - WCDMA Japan 1700 band</li> <li>• Bits 51 through 55 - Reserved</li> </ul>
----------------------------	---

<i>TdsBand-Capability</i> [OUT]	Bitmask of TDS bands supported by the device. <ul style="list-style-type: none"> <li>• Bit 0 - TDS Band A 1900 to 1920 MHz, 2010 to 2020 MHz</li> <li>• Bit 1 - TDS Band B 1850 to 1910 MHz, 1930 to 1990 MHz</li> <li>• Bit 2 - TDS Band C 1910 to 1930 MHz</li> <li>• Bit 3 - TDS Band D 2570 to 2620 MHz</li> <li>• Bit 4 - TDS Band E 2300 to 2400 MHz</li> <li>• Bit 5 - TDS Band F 1880 to 1920 MHz</li> </ul>
---------------------------------	--

### 8.861.2 Field Documentation

8.861.2.1 `uint64_t unpack_dms_SLQSGetBandCapability_t::bandCapability`

8.861.2.2 `int unpack_dms_SLQSGetBandCapability_t::is_LteBandCapability_Available`

8.861.2.3 `int unpack_dms_SLQSGetBandCapability_t::is_TdsBandCapability_Available`

8.861.2.4 `uint64_t unpack_dms_SLQSGetBandCapability_t::LteBandCapability`

8.861.2.5 `uint64_t unpack_dms_SLQSGetBandCapability_t::TdsBandCapability`

## 8.862 `unpack_dms_SLQSSwiClearDyingGaspStatistics_t` Struct Reference

### Data Fields

- `uint16_t` [Tlvresult](#)

### 8.862.1 Detailed Description

This structure contains Clear Dying GASP unpack

#### Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack Result</li> </ul>
------------------	---

### 8.862.2 Field Documentation

8.862.2.1 `uint16_t unpack_dms_SLQSSwiClearDyingGaspStatistics_t::Tlvresult`

## 8.863 `unpack_dms_SLQSSwiGetDyingGaspCfg_t` Struct Reference

### Data Fields

- `packgetDyingGaspCfg * pGetDyingGaspCfg`
- `uint16_t` [Tlvresult](#)

### 8.863.1 Detailed Description

This structure contains Get Dying GASP Config unpack

## Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack Result</li> </ul>
------------------	---

## 8.863.2 Field Documentation

8.863.2.1 `packgetDyingGaspCfg*` `unpack_dms_SLQSSwiGetDyingGaspCfg_t::pGetDyingGaspCfg`

8.863.2.2 `uint16_t` `unpack_dms_SLQSSwiGetDyingGaspCfg_t::Tlvresult`

8.864 `unpack_dms_SLQSSwiGetDyingGaspStatistics_t` Struct Reference

## Data Fields

- `packgetDyingGaspStatistics*` `pGetDyingGaspStatistics`
- `uint16_t` `Tlvresult`

## 8.864.1 Detailed Description

This structure contains Get Dying GASP Statistics.

## Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack Result</li> </ul>
------------------	---

## 8.864.2 Field Documentation

8.864.2.1 `packgetDyingGaspStatistics*` `unpack_dms_SLQSSwiGetDyingGaspStatistics_t::pGetDyingGaspStatistics`

8.864.2.2 `uint16_t` `unpack_dms_SLQSSwiGetDyingGaspStatistics_t::Tlvresult`

8.865 `unpack_dms_SLQSSwiGetFirmwareCurr_t` Struct Reference

## Data Fields

- `uint8_t` `numEntries`
- `image_info_t*` `pCurrImgInfo`
- `char` `priver` [16]
- `char` `pkgver` [16]
- `char` `fwvers` [16]
- `char` `carrier` [16]

## 8.865.1 Detailed Description

## Parameters

<i>numEntries</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>• Number of entries in the image list to follow</li> <li>• The size of the list pCurrImgInfo must be specified when calling the API</li> </ul>
<i>pCurrImgInfo</i> [OUT]	<ul style="list-style-type: none"> <li>• Currently Active Image List</li> </ul>
<i>priver</i> [OUT]	<ul style="list-style-type: none"> <li>• PRI version of the currently running firmware</li> </ul>
<i>pkgver</i> [OUT]	<ul style="list-style-type: none"> <li>• Package version of the currently running firmware</li> </ul>
<i>fwvers</i> [OUT]	<ul style="list-style-type: none"> <li>• firmware version of the currently running firmware</li> </ul>
<i>carrier</i> [OUT]	<ul style="list-style-type: none"> <li>• Carrier string of the currently running firmware</li> </ul>

## 8.865.2 Field Documentation

8.865.2.1 char unpack\_dms\_SLQSSwiGetFirmwareCurr\_t::carrier[16]

8.865.2.2 char unpack\_dms\_SLQSSwiGetFirmwareCurr\_t::fwvers[16]

8.865.2.3 uint8\_t unpack\_dms\_SLQSSwiGetFirmwareCurr\_t::numEntries

8.865.2.4 image\_info\_t\* unpack\_dms\_SLQSSwiGetFirmwareCurr\_t::pCurrImgInfo

8.865.2.5 char unpack\_dms\_SLQSSwiGetFirmwareCurr\_t::pkgver[16]

8.865.2.6 char unpack\_dms\_SLQSSwiGetFirmwareCurr\_t::priver[16]

## 8.866 unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t Struct Reference

## Data Fields

- uint32\_t [ResCode](#)
- uint8\_t [imgType](#)
- uint32\_t [refData](#)
- uint8\_t [refString](#) [15]
- uint8\_t [logString](#) [255]
- uint16\_t [Tlvresult](#)

## 8.866.1 Detailed Description

This structure is used to store Firmware Update Status

## Parameters

<i>ResCode</i>	<ul style="list-style-type: none"> <li>FW Update Result Code</li> <li>Values: <ul style="list-style-type: none"> <li>0x00000001 - Successful</li> <li>0xFFFFFFFF - Unknown (due to power off reset after firmware update )</li> <li>0x100000nn - File update errors while nn will be the exact error number: <ul style="list-style-type: none"> <li>* 00 - General error</li> </ul> </li> <li>0x200000nn - NVUP update errors while nn will be the exact error number: <ul style="list-style-type: none"> <li>* 00 - General error</li> </ul> </li> <li>0x400000nnn - FOTA update agent errors while nnn will be the exact error number: <ul style="list-style-type: none"> <li>* 000 ~ 0FF - Insignia defined error code</li> <li>* 100 ~ 1FF - Sierra defined error code</li> <li>* See qaGobiApiTableFwDldErrorCodes.h for more detailed information</li> </ul> </li> <li>0x800000nn - FDT/SSDP reported errors while nn will be the exact error number <ul style="list-style-type: none"> <li>* See qaGobiApiTableFwDldErrorCodes.h for more detailed information</li> </ul> </li> </ul> </li> </ul>
<i>imgType</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Firmware image type that failed the update</li> </ul>
<i>refData</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Failed image reference data</li> <li>This is normally the offset of the image that caused the failure</li> </ul>
<i>refString</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Failed image reference string. This is normally the partition name of the image that caused the failure if applicable.</li> </ul>
<i>logString</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Failed image reference string. This is normally the partition name of the image that caused the failure if applicable.</li> </ul>

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Unpack Result</li></ul>
------------------	---

## 8.866.2 Field Documentation

8.866.2.1 uint8\_t unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t::imgType

8.866.2.2 uint8\_t unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t::logString[255]

8.866.2.3 uint32\_t unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t::refData

8.866.2.4 uint8\_t unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t::refString[15]

8.866.2.5 uint32\_t unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t::ResCode

8.866.2.6 uint16\_t unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t::Tlvresult

## 8.867 unpack\_dms\_SLQSSwiSetDyingGaspCfg\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.867.1 Detailed Description

This structure contains set Dying GASP Config unpack

#### Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Unpack Result</li></ul>
------------------	---

## 8.867.2 Field Documentation

8.867.2.1 uint16\_t unpack\_dms\_SLQSSwiSetDyingGaspCfg\_t::Tlvresult

## 8.868 unpack\_dms\_UIMGetICCID\_t Struct Reference

### Data Fields

- uint8\_t [stringSize](#)
- uint8\_t [String](#) [255]
- uint16\_t [Tlvresult](#)

### 8.868.1 Detailed Description

This structure contains Get ICCID pack

## Parameters

<i>stringSize</i>	<ul style="list-style-type: none"> <li>• Size of String.</li> </ul>
<i>String</i>	<ul style="list-style-type: none"> <li>• ICCID String.</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Pack result.</li> </ul>

## 8.868.2 Field Documentation

8.868.2.1 uint8\_t unpack\_dms\_UIMGetICCID\_t::String[255]

8.868.2.2 uint8\_t unpack\_dms\_UIMGetICCID\_t::stringSize

8.868.2.3 uint16\_t unpack\_dms\_UIMGetICCID\_t::Tlvresult

## 8.869 unpack\_fms\_GetImagesPreference\_t Struct Reference

## Data Fields

- uint32\_t [ImageListSize](#)
- [FMSPrefImageList](#) \* [pImageList](#)
- uint16\_t [Tlvresult](#)

## 8.869.1 Detailed Description

This structure contains the Get Image Preference information unpack

## Parameters

<i>listSize</i>	<ul style="list-style-type: none"> <li>• The number of elements in the image list</li> </ul>
<i>pListEntries</i>	<ul style="list-style-type: none"> <li>• Array of Image entries with size provided by previous field</li> <li>• See <a href="#">FMSImageElement</a></li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack result</li> </ul>

## 8.869.2 Field Documentation

8.869.2.1 uint32\_t unpack\_fms\_GetImagesPreference\_t::ImageListSize

8.869.2.2 [FMSPrefImageList](#)\* unpack\_fms\_GetImagesPreference\_t::pImageList



8.869.2.3 uint16\_t unpack\_fms\_GetImagesPreference\_t::Tlvresult

## 8.870 unpack\_fms\_GetStoredImages\_t Struct Reference

### Data Fields

- uint32\_t [imagelistSize](#)
- [FMSImageList](#) [imageList](#)
- uint16\_t [Tlvresult](#)

### 8.870.1 Detailed Description

This structure contains the Get Stored Images unpack

#### Parameters

<i>listSize</i>	<ul style="list-style-type: none"> <li>• The number of elements in the image list</li> </ul>
<i>imageList</i>	<ul style="list-style-type: none"> <li>• Array of Image entries with size provided by previous field</li> <li>• See <a href="#">FMSImageElement</a></li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack result</li> </ul>

### 8.870.2 Field Documentation

8.870.2.1 [FMSImageList](#) unpack\_fms\_GetStoredImages\_t::imageList

8.870.2.2 uint32\_t unpack\_fms\_GetStoredImages\_t::imagelistSize

8.870.2.3 uint16\_t unpack\_fms\_GetStoredImages\_t::Tlvresult

## 8.871 unpack\_fms\_SetImagesPreference\_t Struct Reference

### Data Fields

- uint32\_t [ImageTypesSize](#)
- uint8\_t [ImageTypes](#) [255]
- uint16\_t [Tlvresult](#)

### 8.871.1 Detailed Description

This structure contains the Set Images Preference unpack

#### Parameters

<i>ImageTypesSize</i>	<ul style="list-style-type: none"> <li>• Image Type Size</li> </ul>
<i>ImageTypes</i>	<ul style="list-style-type: none"> <li>• Image Type</li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack result</li> </ul>

### 8.871.2 Field Documentation

8.871.2.1 uint8\_t unpack\_fms\_SetImagesPreference\_t::ImageTypes[255]

8.871.2.2 uint32\_t unpack\_fms\_SetImagesPreference\_t::ImageTypesSize

8.871.2.3 uint16\_t unpack\_fms\_SetImagesPreference\_t::Tlvresult

## 8.872 unpack\_loc\_Delete\_Assist\_Data\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.872.1 Detailed Description

This structure contains LOC delete assist data unpack

#### Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack result.</li> </ul>
------------------	--

### 8.872.2 Field Documentation

8.872.2.1 uint16\_t unpack\_loc\_Delete\_Assist\_Data\_t::Tlvresult

## 8.873 unpack\_loc\_EngineState\_Ind\_t Struct Reference

### Data Fields

- uint32\_t [engineState](#)
- uint16\_t [Tlvresult](#)

### 8.873.1 Detailed Description

This structure contains LOC Engine State field.

## Parameters

<i>engineState</i>	<ul style="list-style-type: none"> <li>• Location engine state.</li> <li>• Valid values <ul style="list-style-type: none"> <li>– 1 - Location engine is on</li> <li>– 2 - Location engine is off</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• unpack result</li> </ul>

## 8.873.2 Field Documentation

8.873.2.1 uint32\_t unpack\_loc\_EngineState\_Ind\_t::engineState

8.873.2.2 uint16\_t unpack\_loc\_EngineState\_Ind\_t::Tlvresult

## 8.874 unpack\_loc\_EventRegister\_t Struct Reference

## Data Fields

- uint16\_t [Tlvresult](#)

## 8.874.1 Detailed Description

This structure contains Event Register unpack

## Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• Unpack result.</li> </ul>
------------------	--

## 8.874.2 Field Documentation

8.874.2.1 uint16\_t unpack\_loc\_EventRegister\_t::Tlvresult

## 8.875 unpack\_loc\_PositionRpt\_Ind\_t Struct Reference

## Data Fields

- uint32\_t [sessionStatus](#)
- uint8\_t [sessionId](#)
- uint64\_t \* [pLatitude](#)
- uint64\_t \* [pLongitude](#)
- uint32\_t \* [pHorUncCircular](#)
- uint32\_t \* [pHorUncEllipseSemiMinor](#)
- uint32\_t \* [pHorUncEllipseSemiMajor](#)
- uint32\_t \* [pHorUncEllipseOrientAzimuth](#)

- uint8\_t \* [pHorConfidence](#)
- uint32\_t \* [pHorReliability](#)
- uint32\_t \* [pSpeedHorizontal](#)
- uint32\_t \* [pSpeedUnc](#)
- uint32\_t \* [pAltitudeWrtEllipsoid](#)
- uint32\_t \* [pAltitudeWrtMeanSeaLevel](#)
- uint32\_t \* [pVertUnc](#)
- uint8\_t \* [pVertConfidence](#)
- uint32\_t \* [pVertReliability](#)
- uint32\_t \* [pSpeedVertical](#)
- uint32\_t \* [pHeading](#)
- uint32\_t \* [pHeadingUnc](#)
- uint32\_t \* [pMagneticDeviation](#)
- uint32\_t \* [pTechnologyMask](#)
- [loc\\_precisionDilution](#) \* [pPrecisionDilution](#)
- uint64\_t \* [pTimestampUtc](#)
- uint8\_t \* [pLeapSeconds](#)
- [loc\\_gpsTime](#) \* [pGpsTime](#)
- uint32\_t \* [pTimeUnc](#)
- uint32\_t \* [pTimeSrc](#)
- [loc\\_sensorDataUsage](#) \* [pSensorDataUsage](#)
- uint32\_t \* [pFixId](#)
- [loc\\_svUsedforFix](#) \* [pSvUsedforFix](#)
- uint8\_t \* [pAltitudeAssumed](#)
- uint16\_t [Tlvresult](#)

### 8.875.1 Detailed Description

This structure contains Event Position Report Indication unpack

#### Parameters

<i>sessionStatus</i>	<ul style="list-style-type: none"> <li>• Values             <ul style="list-style-type: none"> <li>– 0 - Session was successful</li> <li>– 1 - Session is still in progress; further position reports will be generated until either the fix criteria specified by the client are met or the client response timeout occurs.</li> <li>– 2 - Session failed..</li> <li>– 3 - Fix request failed because the session timed out.</li> <li>– 4 - Fix request failed because the session was ended by the user.</li> <li>– 5 - Fix request failed due to bad parameters in the request.</li> <li>– 6 - Fix request failed because the phone is offline.</li> <li>– 7 - Fix request failed because the engine is locked</li> </ul> </li> </ul>
----------------------	--

<i>sessionId</i>	<ul style="list-style-type: none"> <li>• ID of the session that was specified in the Start request</li> <li>• Range - 0 to 255</li> </ul>
<i>pLatitude</i>	<ul style="list-style-type: none"> <li>• Latitude (specified in WGS84 datum)</li> <li>• Type - Floating point</li> <li>• Units - Degrees</li> <li>• Range - -90.0 to 90.0</li> <li>• Positive values indicate northern latitude</li> <li>• Negative values indicate southern latitude</li> </ul>
<i>pLongitude</i>	<ul style="list-style-type: none"> <li>• Longitude (specified in WGS84 datum)</li> <li>• Type - Floating point</li> <li>• Units - Degrees</li> <li>• Range - -180.0 to 180.0</li> <li>• Positive values indicate eastern latitude</li> <li>• Negative values indicate western latitude</li> </ul>
<i>pHorUncCircular</i>	<ul style="list-style-type: none"> <li>• Horizontal position uncertainty.</li> <li>• Units - Meters</li> </ul>
<i>pHorUncEllipse-SemiMinor</i>	<ul style="list-style-type: none"> <li>• Semi-minor axis of horizontal elliptical uncertainty.</li> <li>• Units - Meters</li> </ul>
<i>pHorUncEllipse-SemiMajor</i>	<ul style="list-style-type: none"> <li>• Semi-major axis of horizontal elliptical uncertainty.</li> <li>• Units: Meters</li> </ul>
<i>pHorUncEllipse-OrientAzimuth</i>	<ul style="list-style-type: none"> <li>• Elliptical horizontal uncertainty azimuth of orientation.</li> <li>• Units - Decimal degrees</li> <li>• Range - 0 to 180</li> </ul>

<i>pHorConfidence</i>	<ul style="list-style-type: none"> <li>• Horizontal uncertainty confidence.</li> <li>• If both elliptical and horizontal uncertainties are specified in this message, the confidence corresponds to the elliptical uncertainty.</li> <li>• Units - Percentage</li> <li>• Range 0-99</li> </ul>
<i>pHorReliability</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Location reliability is not set.</li> <li>– 1 - Location reliability is very low; use it at your own risk</li> <li>– 2 - Location reliability is low; little or no cross-checking is possible.</li> <li>– 3 - Location reliability is medium; limited cross-check passed</li> <li>– 4 - Location reliability is high; strong cross-check passed</li> </ul> </li> </ul>
<i>pSpeed-Horizontal</i>	<ul style="list-style-type: none"> <li>• Horizontal speed.</li> <li>• Units - Meters/second</li> </ul>
<i>pSpeedUnc</i>	<ul style="list-style-type: none"> <li>• 3-D Speed uncertainty.</li> <li>• Units - Meters/second.</li> </ul>
<i>pAltitudeWrt-Ellipsoid</i>	<ul style="list-style-type: none"> <li>• Altitude With Respect to WGS84 Ellipsoid.</li> <li>• Units - Meters</li> <li>• Range -500 to 15883</li> </ul>
<i>pAltitudeWrt-MeanSeaLevel</i>	<ul style="list-style-type: none"> <li>• Altitude With Respect to Sea Level.</li> <li>• Units - Meters</li> </ul>
<i>pVertUnc</i>	<ul style="list-style-type: none"> <li>• Vertical uncertainty.</li> <li>• Units - Meters</li> </ul>
<i>pVertConfidence</i>	<ul style="list-style-type: none"> <li>• Vertical uncertainty confidence.</li> <li>• Units - Percentage</li> <li>• Range 0 to 99</li> </ul>

<i>pVertReliability</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Location reliability is not set.</li> <li>– 1 - Location reliability is very low; use it at your own risk.</li> <li>– 2 - Location reliability is low; little or no cross-checking is possible</li> <li>– 3 - Location reliability is medium; limited cross-check passed</li> <li>– 4 - Location reliability is high; strong cross-check passed</li> </ul> </li> </ul>
<i>pSpeedVertical</i>	<ul style="list-style-type: none"> <li>• Vertical speed.</li> <li>• Units - Meters/second</li> </ul>
<i>pHeading</i>	<ul style="list-style-type: none"> <li>• Heading.</li> <li>• Units - Degree</li> <li>• Range 0 to 359.999</li> </ul>
<i>pHeadingUnc</i>	<ul style="list-style-type: none"> <li>• Heading uncertainty.</li> <li>• Units - Degree</li> <li>• Range 0 to 359.999</li> </ul>
<i>pMagnetic-Deviation</i>	<ul style="list-style-type: none"> <li>• Difference between the bearing to true north and the bearing shown on a magnetic compass. The deviation is positive when the magnetic north is east of true north.</li> </ul>
<i>pTechnology-Mask</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0x00000001 - Satellites were used to generate the fix</li> <li>– 0x00000002 - Cell towers were used to generate the fix</li> <li>– 0x00000004 - Wi-Fi access points were used to generate the fix</li> <li>– 0x00000008 - Sensors were used to generate the fix</li> <li>– 0x00000010 - Reference Location was used to generate the fix</li> <li>– 0x00000020 - Coarse position injected into the location engine was used to generate the fix</li> <li>– 0x00000040 - AFLT was used to generate the fix</li> <li>– 0x00000080 - GNSS and network-provided measurements were used to generate the fix</li> </ul> </li> </ul>

<i>-pPrecisionDilution</i>	<ul style="list-style-type: none"> <li>• See <a href="#">loc_precisionDilution</a> for more information</li> </ul>
<i>pTimestampUtc</i>	<ul style="list-style-type: none"> <li>• UTC timestamp</li> <li>• Units - Milliseconds since Jan. 1, 1970</li> </ul>
<i>pLeapSeconds</i>	<ul style="list-style-type: none"> <li>• Leap second information. If leapSeconds is not available, timestampUtc is calculated based on a hard-coded value for leap seconds.</li> <li>• Units - Seconds</li> </ul>
<i>-pGpsTime</i>	<ul style="list-style-type: none"> <li>• See <a href="#">loc_gpsTime</a> for more information</li> </ul>
<i>pTimeUnc</i>	<ul style="list-style-type: none"> <li>• Time uncertainty.</li> <li>• Units - Milliseconds</li> </ul>
<i>pTimeSrc</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - Invalid time.</li> <li>– 1 - Time is set by the 1X system.</li> <li>– 2 - Time is set by WCDMA/GSM time tagging.</li> <li>– 3 - Time is set by an external injection.</li> <li>– 4 - Time is set after decoding over-the-air GPS navigation data from one GPS satellite.</li> <li>– 5 - Time is set after decoding over-the-air GPS navigation data from multiple satellites.</li> <li>– 6 - Both time of the week and the GPS week number are known.</li> <li>– 7 - Time is set by the position engine after the fix is obtained</li> <li>– 8 - Time is set by the position engine after performing SFT, this is done when the clock time uncertainty is large.</li> <li>– 9 - Time is set after decoding GLO satellites.</li> <li>– 10- Time is set after transforming the GPS to GLO time</li> <li>– 11- Time is set by the sleep time tag provided by the WCDMA network.</li> <li>– 12- Time is set by the sleep time tag provided by the GSM network</li> <li>– 13- Source of the time is unknown</li> <li>– 14- Time is derived from the system clock (better known as the slow clock); GNSS time is maintained irrespective of the GNSS receiver state</li> <li>– 15- Time is set after decoding QZSS satellites.</li> <li>– 16- Time is set after decoding BDS satellites.</li> </ul> </li> </ul>



<i>-pSensorData-Usage</i>	<ul style="list-style-type: none"> <li>• See <a href="#">loc_sensorDataUsage</a> for more information</li> </ul>
<i>pFixId</i>	<ul style="list-style-type: none"> <li>• Fix count for the session. Starts with 0 and increments by one for each successive position report for a particular session.</li> </ul>
<i>-pSvUsedforFix</i>	<ul style="list-style-type: none"> <li>• See <a href="#">loc_svUsedforFix</a> for more information</li> </ul>
<i>pAltitude-Assumed</i>	<ul style="list-style-type: none"> <li>• Indicates whether altitude is assumed or calculated.</li> </ul>

- Value
  - 0x00 - Altitude is calculated
  - 0x01 - Altitude is assumed

## 8.875.2 Field Documentation

- 8.875.2.1 `uint8_t* unpack_loc_PositionRpt_Ind_t::pAltitudeAssumed`
- 8.875.2.2 `uint32_t* unpack_loc_PositionRpt_Ind_t::pAltitudeWrtEllipsoid`
- 8.875.2.3 `uint32_t* unpack_loc_PositionRpt_Ind_t::pAltitudeWrtMeanSeaLevel`
- 8.875.2.4 `uint32_t* unpack_loc_PositionRpt_Ind_t::pFixId`
- 8.875.2.5 `loc_gpsTime* unpack_loc_PositionRpt_Ind_t::pGpsTime`
- 8.875.2.6 `uint32_t* unpack_loc_PositionRpt_Ind_t::pHeading`
- 8.875.2.7 `uint32_t* unpack_loc_PositionRpt_Ind_t::pHeadingUnc`
- 8.875.2.8 `uint8_t* unpack_loc_PositionRpt_Ind_t::pHorConfidence`
- 8.875.2.9 `uint32_t* unpack_loc_PositionRpt_Ind_t::pHorReliability`
- 8.875.2.10 `uint32_t* unpack_loc_PositionRpt_Ind_t::pHorUncCircular`
- 8.875.2.11 `uint32_t* unpack_loc_PositionRpt_Ind_t::pHorUncEllipseOrientAzimuth`
- 8.875.2.12 `uint32_t* unpack_loc_PositionRpt_Ind_t::pHorUncEllipseSemiMajor`
- 8.875.2.13 `uint32_t* unpack_loc_PositionRpt_Ind_t::pHorUncEllipseSemiMinor`
- 8.875.2.14 `uint64_t* unpack_loc_PositionRpt_Ind_t::pLatitude`
- 8.875.2.15 `uint8_t* unpack_loc_PositionRpt_Ind_t::pLeapSeconds`
- 8.875.2.16 `uint64_t* unpack_loc_PositionRpt_Ind_t::pLongitude`
- 8.875.2.17 `uint32_t* unpack_loc_PositionRpt_Ind_t::pMagneticDeviation`

- 8.875.2.18 `loc_precisionDilution*` `unpack_loc_PositionRpt_Ind_t::pPrecisionDilution`
- 8.875.2.19 `loc_sensorDataUsage*` `unpack_loc_PositionRpt_Ind_t::pSensorDataUsage`
- 8.875.2.20 `uint32_t*` `unpack_loc_PositionRpt_Ind_t::pSpeedHorizontal`
- 8.875.2.21 `uint32_t*` `unpack_loc_PositionRpt_Ind_t::pSpeedUnc`
- 8.875.2.22 `uint32_t*` `unpack_loc_PositionRpt_Ind_t::pSpeedVertical`
- 8.875.2.23 `loc_svUsedforFix*` `unpack_loc_PositionRpt_Ind_t::pSvUsedforFix`
- 8.875.2.24 `uint32_t*` `unpack_loc_PositionRpt_Ind_t::pTechnologyMask`
- 8.875.2.25 `uint32_t*` `unpack_loc_PositionRpt_Ind_t::pTimeSrc`
- 8.875.2.26 `uint64_t*` `unpack_loc_PositionRpt_Ind_t::pTimestampUtc`
- 8.875.2.27 `uint32_t*` `unpack_loc_PositionRpt_Ind_t::pTimeUnc`
- 8.875.2.28 `uint8_t*` `unpack_loc_PositionRpt_Ind_t::pVertConfidence`
- 8.875.2.29 `uint32_t*` `unpack_loc_PositionRpt_Ind_t::pVertReliability`
- 8.875.2.30 `uint32_t*` `unpack_loc_PositionRpt_Ind_t::pVertUnc`
- 8.875.2.31 `uint8_t` `unpack_loc_PositionRpt_Ind_t::sessionId`
- 8.875.2.32 `uint32_t` `unpack_loc_PositionRpt_Ind_t::sessionStatus`
- 8.875.2.33 `uint16_t` `unpack_loc_PositionRpt_Ind_t::Tlvresult`

## 8.876 `unpack_loc_SetExtPowerConfig_Ind_t` Struct Reference

### Data Fields

- `uint32_t` [status](#)
- `uint16_t` [Tlvresult](#)

### 8.876.1 Detailed Description

This structure contains LOC Set External Power Configure status field.

## Parameters

<i>status</i>	<ul style="list-style-type: none"> <li>Valid values <ul style="list-style-type: none"> <li>0 - Request was completed successfully</li> <li>1 - Request failed because of a general failure.</li> <li>2 - Request failed because it is not supported.</li> <li>3 - Request failed because it contained invalid parameters</li> <li>4 - Request failed because the engine is busy</li> <li>5 - Request failed because the phone is offline</li> <li>6 - Request failed because it timed out</li> <li>7 - Request failed because an undefined configuration was requested</li> <li>8 - engine could not allocate sufficient memory</li> <li>9 - Request failed because the maximum number of Geofences are already programmed</li> <li>10 -Location service failed because of an XTRA version-based file format check failure</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>unpack result</li> </ul>

## 8.876.2 Field Documentation

8.876.2.1 uint32\_t unpack\_loc\_SetExtPowerConfig\_Ind\_t::status

8.876.2.2 uint16\_t unpack\_loc\_SetExtPowerConfig\_Ind\_t::Tlvresult

## 8.877 unpack\_loc\_SetExtPowerState\_t Struct Reference

## Data Fields

- uint16\_t [Tlvresult](#)

## 8.877.1 Detailed Description

This structure contains Set Ext Power State unpack

## Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>Unpack result.</li> </ul>
------------------	--

## 8.877.2 Field Documentation

8.877.2.1 uint16\_t unpack\_loc\_SetExtPowerState\_t::Tlvresult

## 8.878 unpack\_loc\_SetOperationMode\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.878.1 Detailed Description

This structure contains Set Operation Mode unpack

#### Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Unpack result.</li></ul>
------------------	--

### 8.878.2 Field Documentation

8.878.2.1 uint16\_t unpack\_loc\_SetOperationMode\_t::Tlvresult

## 8.879 unpack\_loc\_Start\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.879.1 Detailed Description

This structure contains Start LOC unpack

#### Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• Unpack result.</li></ul>
------------------	--

### 8.879.2 Field Documentation

8.879.2.1 uint16\_t unpack\_loc\_Start\_t::Tlvresult

## 8.880 unpack\_loc\_Stop\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.880.1 Detailed Description

This structure contains Stop LOC unpack

## Parameters

<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>Unpack result.</li> </ul>
------------------	--

## 8.880.2 Field Documentation

8.880.2.1 uint16\_t unpack\_loc\_Stop\_t::Tlvresult

## 8.881 unpack\_nas\_GetCDMANetworkParameters\_t Struct Reference

## Data Fields

- uint8\_t [SCI](#)
- uint8\_t [SCM](#)
- uint8\_t [RegHomeSID](#)
- uint8\_t [RegForeignSID](#)
- uint8\_t [RegForeignNID](#)
- uint8\_t [ForceRev0](#)
- uint8\_t [CustomSCP](#)
- uint32\_t [Protocol](#)
- uint32\_t [Broadcast](#)
- uint32\_t [Application](#)
- uint32\_t [Roaming](#)

## 8.881.1 Detailed Description

## Parameters

<i>SCI</i>	slot cycle index
<i>SCM</i>	station class mark
<i>RegHomeSID</i>	register on home sid
<i>RegForeignSID</i>	register on foreign sid
<i>RegForeignNID</i>	register on foreign nid
<i>ForceRev0</i>	force header revision
<i>CustomSCP</i>	custom SCP
<i>Protocol</i>	protocol
<i>Booadcast</i>	broadcast
<i>Application</i>	application
<i>Roaming</i>	roaming

## 8.881.2 Field Documentation

8.881.2.1 uint32\_t unpack\_nas\_GetCDMANetworkParameters\_t::Application

8.881.2.2 uint32\_t unpack\_nas\_GetCDMANetworkParameters\_t::Broadcast

8.881.2.3 uint8\_t unpack\_nas\_GetCDMANetworkParameters\_t::CustomSCP

8.881.2.4 uint8\_t unpack\_nas\_GetCDMANetworkParameters\_t::ForceRev0

8.881.2.5 uint32\_t unpack\_nas\_GetCDMANetworkParameters\_t::Protocol

8.881.2.6 `uint8_t unpack_nas_GetCDMANetworkParameters_t::RegForeignNID`

8.881.2.7 `uint8_t unpack_nas_GetCDMANetworkParameters_t::RegForeignSID`

8.881.2.8 `uint8_t unpack_nas_GetCDMANetworkParameters_t::RegHomeSID`

8.881.2.9 `uint32_t unpack_nas_GetCDMANetworkParameters_t::Roaming`

8.881.2.10 `uint8_t unpack_nas_GetCDMANetworkParameters_t::SCI`

8.881.2.11 `uint8_t unpack_nas_GetCDMANetworkParameters_t::SCM`

## 8.882 `unpack_nas_GetHomeNetwork_t` Struct Reference

### Data Fields

- `uint16_t` [mcc](#)
- `uint16_t` [mnc](#)
- `char` [name](#) [255]
- `uint16_t` [sid](#)
- `uint16_t` [nid](#)

### 8.882.1 Detailed Description

#### Parameters

<i>mcc</i>	mobile country code
<i>mnc</i>	mobile network code
<i>name</i>	network name or description
<i>sid</i>	home network system id only applies to cdma2000
<i>nid</i>	home network id Only applies to cdma2000

### 8.882.2 Field Documentation

8.882.2.1 `uint16_t unpack_nas_GetHomeNetwork_t::mcc`

8.882.2.2 `uint16_t unpack_nas_GetHomeNetwork_t::mnc`

8.882.2.3 `char unpack_nas_GetHomeNetwork_t::name[255]`

8.882.2.4 `uint16_t unpack_nas_GetHomeNetwork_t::nid`

8.882.2.5 `uint16_t unpack_nas_GetHomeNetwork_t::sid`

## 8.883 `unpack_nas_GetNetworkPreference_t` Struct Reference

### Data Fields

- `uint32_t` [ActiveTechPref](#)
- `uint32_t` [Duration](#)
- `uint32_t` [PersistentTechPref](#)
- `uint16_t` [Tlvresult](#)

### 8.883.1 Detailed Description

## Parameters

<i>TechnologyPref[OUT]</i>	<ul style="list-style-type: none"> <li>• Bitmask representing the radio technology preference set.</li> <li>• No bits set indicates to the device to automatically determine the technology to use</li> <li>• Values: <ul style="list-style-type: none"> <li>– Bit 0 - Technology is 3GPP2</li> <li>– Bit 1 - Technology is 3GPP</li> </ul> </li> <li>• Any combination of the following may be returned: <ul style="list-style-type: none"> <li>– Bit 2 - Analog - AMPS if 3GPP2, GSM if 3GPP</li> <li>– Bit 3 - Digital - CDMA if 3GPP2, WCDMA if 3GPP</li> <li>– Bit 4 - HDR</li> <li>– Bit 5 - LTE</li> <li>– Bits 6 to 15 - Reserved</li> </ul> </li> </ul>
<i>Duration[OUT]</i>	<ul style="list-style-type: none"> <li>• Duration of active preference <ul style="list-style-type: none"> <li>– 0 - Permanent</li> <li>– 1 - Power cycle</li> <li>– 2 - Until the end of the next call or a power cycle</li> <li>– 3 - Until the end of the next call, a specified time, or a power cycle</li> <li>– 4 to 6 - Until the end of the next call</li> </ul> </li> </ul>
<i>Persistent-TechnologyPref[OUT]</i>	<ul style="list-style-type: none"> <li>• Bit field representing persistent radio technology preference <ul style="list-style-type: none"> <li>– Same representation as the pTechnologyPref parameter</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• unpack result</li> </ul>

## 8.883.2 Field Documentation

8.883.2.1 uint32\_t unpack\_nas\_GetNetworkPreference\_t::ActiveTechPref

8.883.2.2 uint32\_t unpack\_nas\_GetNetworkPreference\_t::Duration

8.883.2.3 uint32\_t unpack\_nas\_GetNetworkPreference\_t::PersistentTechPref

8.883.2.4 uint16\_t unpack\_nas\_GetNetworkPreference\_t::Tlvresult

## 8.884 unpack\_nas\_GetRFInfo\_t Struct Reference



## Data Fields

- uint8\_t [instancesSize](#)
- [RFBandInfoElements](#) [RFBandInfoElements](#) [255]

## 8.884.1 Detailed Description

## Parameters

<i>instancesSize</i>	number of elements in RF info instances array.
<i><a href="#">RFBandInfoElements</a></i>	RF info instances array

## 8.884.2 Field Documentation

8.884.2.1 uint8\_t unpack\_nas\_GetRFInfo\_t::instancesSize

8.884.2.2 [RFBandInfoElements](#) unpack\_nas\_GetRFInfo\_t::RFBandInfoElements[255]

## 8.885 unpack\_nas\_GetServingNetwork\_t Struct Reference

## Data Fields

- uint32\_t [RegistrationState](#)
- uint32\_t [CSDomain](#)
- uint32\_t [PSDomain](#)
- uint32\_t [RAN](#)
- uint8\_t [RadiolfacesSize](#)
- uint8\_t [Radiolfaces](#) [255]
- uint32\_t [Roaming](#)
- uint16\_t [MCC](#)
- uint16\_t [MNC](#)
- uint8\_t [nameSize](#)
- uint8\_t [Name](#) [255]
- uint8\_t [DataCapsLen](#)
- uint8\_t [DataCaps](#) [255]

## 8.885.1 Detailed Description

## Parameters

<i>Registration-State</i>	registration state
<i>CSDomain</i>	CS domain
<i>PSDomain</i>	PS domain
<i>RAN</i>	radio access network
<i>RadiolfacesSize</i>	radio interface size
<i>Radiolfaces</i>	radio interface list
<i>Roaming</i>	romaing indicator

<i>MCC</i>	Mobile country code
<i>MNC</i>	Mobile network code
<i>nameSize</i>	network name size
<i>Name</i>	network name
<i>DataCapsLen</i>	data capabilities len
<i>DataCap</i>	data capabilities

## 8.885.2 Field Documentation

8.885.2.1 uint32\_t unpack\_nas\_GetServingNetwork\_t::CSDomain

8.885.2.2 uint8\_t unpack\_nas\_GetServingNetwork\_t::DataCaps[255]

8.885.2.3 uint8\_t unpack\_nas\_GetServingNetwork\_t::DataCapsLen

8.885.2.4 uint16\_t unpack\_nas\_GetServingNetwork\_t::MCC

8.885.2.5 uint16\_t unpack\_nas\_GetServingNetwork\_t::MNC

8.885.2.6 uint8\_t unpack\_nas\_GetServingNetwork\_t::Name[255]

8.885.2.7 uint8\_t unpack\_nas\_GetServingNetwork\_t::nameSize

8.885.2.8 uint32\_t unpack\_nas\_GetServingNetwork\_t::PSDomain

8.885.2.9 uint8\_t unpack\_nas\_GetServingNetwork\_t::Radiofaces[255]

8.885.2.10 uint8\_t unpack\_nas\_GetServingNetwork\_t::RadiofacesSize

8.885.2.11 uint32\_t unpack\_nas\_GetServingNetwork\_t::RAN

8.885.2.12 uint32\_t unpack\_nas\_GetServingNetwork\_t::RegistrationState

8.885.2.13 uint32\_t unpack\_nas\_GetServingNetwork\_t::Roaming

## 8.886 unpack\_nas\_GetServingNetworkCapabilities\_t Struct Reference

### Data Fields

- uint8\_t [DataCapsLen](#)
- uint8\_t [DataCaps](#) [255]

### 8.886.1 Detailed Description

#### Parameters

<i>DataCapsLen</i>	data capabilities len
<i>DataCap</i>	data capabilities

## 8.886.2 Field Documentation

8.886.2.1 uint8\_t unpack\_nas\_GetServingNetworkCapabilities\_t::DataCaps[255]

8.886.2.2 uint8\_t unpack\_nas\_GetServingNetworkCapabilities\_t::DataCapsLen

## 8.887 unpack\_nas\_GetSignalStrengths\_t Struct Reference

### Data Fields

- uint32\_t [len](#)
- signed char [rssi](#) [8]
- uint32\_t [radio](#) [8]

### 8.887.1 Detailed Description

#### Parameters

<i>len</i>	number of rssi & radio items following
<i>rssi</i>	signal strength array
<i>radio</i>	radio interface array

### 8.887.2 Field Documentation

8.887.2.1 uint32\_t unpack\_nas\_GetSignalStrengths\_t::len

8.887.2.2 uint32\_t unpack\_nas\_GetSignalStrengths\_t::radio[8]

8.887.2.3 signed char unpack\_nas\_GetSignalStrengths\_t::rssi[8]

## 8.888 unpack\_nas\_PerformNetworkScan\_t Struct Reference

### Data Fields

- uint8\_t \* [p3GppNetworkInstanceSize](#)
- [nas\\_QmiNas3GppNetworkInfo](#) \* [p3GppNetworkInfoInstances](#)
- uint8\_t \* [pRATInstanceSize](#)
- [nas\\_QmiNas3GppNetworkRAT](#) \* [pRATInstance](#)
- uint8\_t \* [pPCSInstanceSize](#)
- [nas\\_QmisNasPcsDigit](#) \* [pPCSInstance](#)
- uint32\_t \* [pScanResult](#)

### 8.888.1 Detailed Description

#### Parameters

<i>InstanceSize</i>	total instances
<i>Instances</i>	info for instances

### 8.888.2 Field Documentation

8.888.2.1 [nas\\_QmiNas3GppNetworkInfo](#)\* unpack\_nas\_PerformNetworkScan\_t::p3GppNetworkInfoInstances

8.888.2.2 uint8\_t\* unpack\_nas\_PerformNetworkScan\_t::p3GppNetworkInstanceSize

8.888.2.3 `nas_QmisNasPcsDigit*` `unpack_nas_PerformNetworkScan_t::pPCSInstance`

8.888.2.4 `uint8_t*` `unpack_nas_PerformNetworkScan_t::pPCSInstanceSize`

8.888.2.5 `nas_QmiNas3GppNetworkRAT*` `unpack_nas_PerformNetworkScan_t::pRATInstance`

8.888.2.6 `uint8_t*` `unpack_nas_PerformNetworkScan_t::pRATInstanceSize`

8.888.2.7 `uint32_t*` `unpack_nas_PerformNetworkScan_t::pScanResult`

## 8.889 `unpack_nas_SetDataCapabilitiesCallback_ind_t` Struct Reference

### Data Fields

- `uint8_t` [dataCapsSize](#)
- `uint8_t` [dataCaps](#) [255]

### 8.889.1 Detailed Description

#### Parameters

<i>dataCapsSize</i>	Number of Data Capabilities
<i>dataCaps</i>	Data Capabilities

### 8.889.2 Field Documentation

8.889.2.1 `uint8_t` `unpack_nas_SetDataCapabilitiesCallback_ind_t::dataCaps[255]`

8.889.2.2 `uint8_t` `unpack_nas_SetDataCapabilitiesCallback_ind_t::dataCapsSize`

## 8.890 `unpack_nas_SetEventReportInd_t` Struct Reference

### Data Fields

- [nas\\_SignalStrengthTlv](#) SSTlv
- [nas\\_RFInfoTlv](#) RFTlv
- [nas\\_RejectReasonTlv](#) RRTlv
- [nas\\_SLQSSignalStrengthsTlv](#) SLQSSSTlv

### 8.890.1 Detailed Description

#### Parameters

<i>SSTlv</i>	signal strength tlv
<i>RFTlv</i>	RF tlv
<i>RRTlv</i>	RR tlv
<i>SLQSSSTlv</i>	signal strength complete info tlv

### 8.890.2 Field Documentation

8.890.2.1 `nas_RFInfoTlv` `unpack_nas_SetEventReportInd_t::RFTlv`

8.890.2.2 nas\_RejectReasonTlv unpack\_nas\_SetEventReportInd\_t::RRTlv

8.890.2.3 nas\_SLQSSignalStrengthsTlv unpack\_nas\_SetEventReportInd\_t::SLQSSSTlv

8.890.2.4 nas\_SignalStrengthTlv unpack\_nas\_SetEventReportInd\_t::SSTlv

## 8.891 unpack\_nas\_SetNetworkPreference\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.891.1 Detailed Description

#### Parameters

<i>TechnologyPref[OUT]</i>	<ul style="list-style-type: none"><li>• Bitmask representing the radio technology preference set.</li><li>• No bits set indicates to the device to automatically determine the technology to use</li><li>• Values:<ul style="list-style-type: none"><li>– Bit 0 - Technology is 3GPP2</li><li>– Bit 1 - Technology is 3GPP</li></ul></li><li>• Any combination of the following may be returned:<ul style="list-style-type: none"><li>– Bit 2 - Analog - AMPS if 3GPP2, GSM if 3GPP</li><li>– Bit 3 - Digital - CDMA if 3GPP2, WCDMA if 3GPP</li><li>– Bit 4 - HDR</li><li>– Bit 5 - LTE</li><li>– Bits 6 to 15 - Reserved</li></ul></li></ul>
----------------------------	--

<i>Duration[OUT]</i>	<ul style="list-style-type: none"> <li>• Duration of active preference <ul style="list-style-type: none"> <li>– 0 - Permanent</li> <li>– 1 - Power cycle</li> <li>– 2 - Until the end of the next call or a power cycle</li> <li>– 3 - Until the end of the next call, a specified time, or a power cycle</li> <li>– 4 to 6 - Until the end of the next call</li> </ul> </li> </ul>
<i>Persistent-TechnologyPref[OUT]</i>	<ul style="list-style-type: none"> <li>• Bit field representing persistent radio technology preference <ul style="list-style-type: none"> <li>– Same representation as the pTechnologyPref parameter</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• unpack result</li> </ul>

## 8.891.2 Field Documentation

8.891.2.1 uint16\_t unpack\_nas\_SetNetworkPreference\_t::Tlvresult

## 8.892 unpack\_nas\_SetRoamingIndicatorCallback\_ind\_t Struct Reference

### Data Fields

- uint8\_t [roaming](#)

### 8.892.1 Detailed Description

#### Parameters

<i>roaming</i>	<ul style="list-style-type: none"> <li>• Roaming Indication <ul style="list-style-type: none"> <li>– 0 - Roaming</li> <li>– 1 - Home</li> <li>– 2 - Roaming partner</li> <li>– &gt;2 - Operator defined values</li> </ul> </li> </ul>
----------------	---

### 8.892.2 Field Documentation

8.892.2.1 uint8\_t unpack\_nas\_SetRoamingIndicatorCallback\_ind\_t::roaming

## 8.893 unpack\_nas\_SetServingSystemCallback\_ind\_t Struct Reference

## Data Fields

- [NASServingSystemInfo SSInfo](#)
- uint16\_t [Tlvresult](#)

## 8.893.1 Detailed Description

## Parameters

<i>SSInfo</i>	<ul style="list-style-type: none"> <li>• Serving system parameters information <ul style="list-style-type: none"> <li>– See <a href="#">NASServingSystemInfo</a> for more details</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• unpack result</li> </ul>

## 8.893.2 Field Documentation

8.893.2.1 [NASServingSystemInfo](#) unpack\_nas\_SetServingSystemCallback\_ind\_t::SSInfo

8.893.2.2 uint16\_t unpack\_nas\_SetServingSystemCallback\_ind\_t::Tlvresult

## 8.894 unpack\_nas\_SlqsGetLTECphyCAInfo\_t Struct Reference

## Data Fields

- [NasGetLTECphyCAInfo LTECphyCAInfo](#)
- uint16\_t [Tlvresult](#)

## 8.894.1 Detailed Description

## Parameters

<i>LTECphyCa</i>	<ul style="list-style-type: none"> <li>• Carrier aggregation event information <ul style="list-style-type: none"> <li>– See <a href="#">NasGetLTECphyCAInfo</a> for more details</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• unpack result</li> </ul>

## 8.894.2 Field Documentation

8.894.2.1 [NasGetLTECphyCAInfo](#) unpack\_nas\_SlqsGetLTECphyCAInfo\_t::LTECphyCAInfo

8.894.2.2 uint16\_t unpack\_nas\_SlqsGetLTECphyCAInfo\_t::Tlvresult

## 8.895 unpack\_nas\_SLQSGetNetworkTime\_t Struct Reference

## Data Fields

- [nas\\_timeInfo](#) \* [p3GPP2TimeInfo](#)
- [nas\\_timeInfo](#) \* [p3GPPTimeInfo](#)

### 8.895.1 Detailed Description

This structure contains information about the GetNetworkTime response parameters.

#### Parameters

<i>p3GPP2TimeInfo</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">nas_timeInfo</a> for more information</li> </ul>
<i>p3GPPTimeInfo</i>	[Optional] <ul style="list-style-type: none"> <li>• See <a href="#">nas_timeInfo</a> for more information</li> </ul>

### 8.895.2 Field Documentation

8.895.2.1 [nas\\_timeInfo](#)\* [unpack\\_nas\\_SLQSGetNetworkTime\\_t::p3GPP2TimeInfo](#)

8.895.2.2 [nas\\_timeInfo](#)\* [unpack\\_nas\\_SLQSGetNetworkTime\\_t::p3GPPTimeInfo](#)

## 8.896 [unpack\\_nas\\_SLQSGetPLMNName\\_t](#) Struct Reference

## Data Fields

- [uint8\\_t](#) [spnEncoding](#)
- [uint8\\_t](#) [spnLength](#)
- [char](#) [spn](#) [255]
- [uint8\\_t](#) [shortNameEn](#)
- [uint8\\_t](#) [shortNameCI](#)
- [uint8\\_t](#) [shortNameSB](#)
- [char](#) [shortNameLen](#)
- [uint8\\_t](#) [shortName](#) [255]
- [uint8\\_t](#) [longNameEn](#)
- [uint8\\_t](#) [longNameCI](#)
- [uint8\\_t](#) [longNameSB](#)
- [uint8\\_t](#) [longNameLen](#)
- [char](#) [longName](#) [255]

### 8.896.1 Field Documentation

8.896.1.1 [char](#) [unpack\\_nas\\_SLQSGetPLMNName\\_t::longName](#)[255]

8.896.1.2 [uint8\\_t](#) [unpack\\_nas\\_SLQSGetPLMNName\\_t::longNameCI](#)

8.896.1.3 [uint8\\_t](#) [unpack\\_nas\\_SLQSGetPLMNName\\_t::longNameEn](#)

8.896.1.4 [uint8\\_t](#) [unpack\\_nas\\_SLQSGetPLMNName\\_t::longNameLen](#)



- 8.896.1.5 uint8\_t unpack\_nas\_SLQSGetPLMNName\_t::longNameSB
- 8.896.1.6 uint8\_t unpack\_nas\_SLQSGetPLMNName\_t::shortName[255]
- 8.896.1.7 uint8\_t unpack\_nas\_SLQSGetPLMNName\_t::shortNameCI
- 8.896.1.8 uint8\_t unpack\_nas\_SLQSGetPLMNName\_t::shortNameEn
- 8.896.1.9 char unpack\_nas\_SLQSGetPLMNName\_t::shortNameLen
- 8.896.1.10 uint8\_t unpack\_nas\_SLQSGetPLMNName\_t::shortNameSB
- 8.896.1.11 char unpack\_nas\_SLQSGetPLMNName\_t::spn[255]
- 8.896.1.12 uint8\_t unpack\_nas\_SLQSGetPLMNName\_t::spnEncoding
- 8.896.1.13 uint8\_t unpack\_nas\_SLQSGetPLMNName\_t::spnLength

## 8.897 unpack\_nas\_SLQSGetServingSystem\_t Struct Reference

### Data Fields

- [nas\\_servSystem](#) ServingSystem
- uint8\_t [RoamIndicatorVal](#)
- [nas\\_dataSrvCapabilities](#) DataSrvCapabilities
- [nas\\_currentPLMN](#) CurrentPLMN
- uint16\_t [SystemID](#)
- uint16\_t [NetworkID](#)
- uint16\_t [BasestationID](#)
- uint32\_t [BasestationLatitude](#)
- uint32\_t [BasestationLongitude](#)
- [nas\\_roamIndList](#) RoamingIndicatorList
- uint8\_t [DefaultRoamInd](#)
- [nas\\_qaQmi3Gpp2TimeZone](#) Gpp2TimeZone
- uint8\_t [CDMA\\_P\\_Rev](#)
- uint8\_t [GppTimeZone](#)
- uint8\_t [GppNetworkDSTAdjustment](#)
- uint16\_t [Lac](#)
- uint32\_t [CellID](#)
- uint8\_t [ConcSvcInfo](#)
- uint8\_t [PRLInd](#)
- uint8\_t [DTMInd](#)
- [nas\\_detailSvcInfo](#) DetailedSvcInfo
- [nas\\_CDMA SysInfoExt](#) CDMA SystemInfoExt
- uint8\_t [HdrPersonality](#)
- uint16\_t [TrackAreaCode](#)
- [nas\\_callBarStatus](#) CallBarStatus

### 8.897.1 Detailed Description

## Parameters

<i>ServingSystem</i>	serving system info
<i>RoamIndicator-Val</i>	roaming indicator value
<i>DataSrv-Capabilities</i>	data servcie capabilities
<i>CurrentPLMN</i>	current PLMN info
<i>SystemID</i>	system id
<i>NetworkID</i>	network id
<i>BasestationID</i>	base station id
<i>Basestation-Latitude</i>	base station latitude
<i>Basestation-Longitude</i>	base station longitude
<i>Roaming-IndicatorList</i>	roaming indicator list
<i>DefaultRoamInd</i>	default roaming indicator
<i>3Gpp2TimeZone</i>	3Gpp2 time zone
<i>pCDMA_P_Rev</i>	cdma P_Rev in use
<i>3GppTimeZone</i>	3Gpp time zone
<i>GppNetworkDS-TAdjustment</i>	3GPP network daylight saving adjustment
<i>Lac</i>	location area code
<i>CellID</i>	3GPP cell id
<i>ConcSvcInfo</i>	3GPP2 concurrent servcie info
<i>PRLInd</i>	3GPP2 PRL indicator
<i>DTMInd</i>	DTM indicator(GSM)
<i>DetailedSvcInfo</i>	detail servcie info
<i>CDMASystem-InfoExt</i>	extra cdma system info
<i>HdrPersonality</i>	hdr personality
<i>TrackAreaCode</i>	track area code
<i>CallBarStatus</i>	call barring status

## 8.897.2 Field Documentation

8.897.2.1 uint16\_t unpack\_nas\_SLQSGetServingSystem\_t::BasestationID

8.897.2.2 uint32\_t unpack\_nas\_SLQSGetServingSystem\_t::BasestationLatitude

8.897.2.3 uint32\_t unpack\_nas\_SLQSGetServingSystem\_t::BasestationLongitude

8.897.2.4 nas\_callBarStatus unpack\_nas\_SLQSGetServingSystem\_t::CallBarStatus

8.897.2.5 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::CDMA\_P\_Rev

8.897.2.6 nas\_CDMASysInfoExt unpack\_nas\_SLQSGetServingSystem\_t::CDMASystemInfoExt

8.897.2.7 uint32\_t unpack\_nas\_SLQSGetServingSystem\_t::CellID

8.897.2.8 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::ConcSvcInfo

8.897.2.9 nas\_currentPLMN unpack\_nas\_SLQSGetServingSystem\_t::CurrentPLMN

- 8.897.2.10 nas\_dataSrvCapabilities unpack\_nas\_SLQSGetServingSystem\_t::DataSrvCapabilities
- 8.897.2.11 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::DefaultRoamInd
- 8.897.2.12 nas\_detailSvcInfo unpack\_nas\_SLQSGetServingSystem\_t::DetailedSvcInfo
- 8.897.2.13 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::DTMInd
- 8.897.2.14 nas\_qaQmi3Gpp2TimeZone unpack\_nas\_SLQSGetServingSystem\_t::Gpp2TimeZone
- 8.897.2.15 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::GppNetworkDSTAdjustment
- 8.897.2.16 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::GppTimeZone
- 8.897.2.17 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::HdrPersonality
- 8.897.2.18 uint16\_t unpack\_nas\_SLQSGetServingSystem\_t::Lac
- 8.897.2.19 uint16\_t unpack\_nas\_SLQSGetServingSystem\_t::NetworkID
- 8.897.2.20 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::PRLInd
- 8.897.2.21 uint8\_t unpack\_nas\_SLQSGetServingSystem\_t::RoamIndicatorVal
- 8.897.2.22 nas\_roamIndList unpack\_nas\_SLQSGetServingSystem\_t::RoamingIndicatorList
- 8.897.2.23 nas\_servSystem unpack\_nas\_SLQSGetServingSystem\_t::ServingSystem
- 8.897.2.24 uint16\_t unpack\_nas\_SLQSGetServingSystem\_t::SystemID
- 8.897.2.25 uint16\_t unpack\_nas\_SLQSGetServingSystem\_t::TrackAreaCode

## 8.898 unpack\_nas\_SLQSGetSignalStrength\_t Struct Reference

### Data Fields

- uint16\_t [signalStrengthReqMask](#)
- uint16\_t [rxSignalStrengthListLen](#)
- [nas\\_rxSignalStrengthListElement](#) rxSignalStrengthList [18]
- uint16\_t [ecioListLen](#)
- [nas\\_ecioListElement](#) ecioList [18]
- int32\_t [lo](#)
- uint8\_t [sinr](#)
- uint16\_t [errorRateListLen](#)
- [nas\\_errorRateListElement](#) errorRateList [18]
- [nas\\_rsrqInformation](#) rsrqInfo
- int16\_t [ltesnr](#)
- int16\_t [ltersrp](#)

### 8.898.1 Detailed Description

## Parameters

<i>rxSignalStrengthListLen</i>	number of elements in Receive Signal Strength List
<i>rxSignalStrengthList</i>	signal strength list
<i>ecioListLen</i>	number of elements in ECIO List
<i>ecioList</i>	ecio list
<i>lo</i>	received lo in dBm; IO is only applicable for 1xEV-DO
<i>sinr</i>	SINR level; SINR is only applicable for 1xEV-DO
<i>errorRateListLen</i>	number of elements in Error Rate List
<i>errorRateList</i>	error rate list
<i>rsrqInfo</i>	rsrq info
<i>lte snr</i>	lte snr info
<i>lte srp</i>	lte srp info

## 8.898.2 Field Documentation

8.898.2.1 nas\_ecioListElement unpack\_nas\_SLQSGetSignalStrength\_t::ecioList[18]

8.898.2.2 uint16\_t unpack\_nas\_SLQSGetSignalStrength\_t::ecioListLen

8.898.2.3 nas\_errorRateListElement unpack\_nas\_SLQSGetSignalStrength\_t::errorRateList[18]

8.898.2.4 uint16\_t unpack\_nas\_SLQSGetSignalStrength\_t::errorRateListLen

8.898.2.5 int32\_t unpack\_nas\_SLQSGetSignalStrength\_t::lo

8.898.2.6 int16\_t unpack\_nas\_SLQSGetSignalStrength\_t::ltersrp

8.898.2.7 int16\_t unpack\_nas\_SLQSGetSignalStrength\_t::ltesnr

8.898.2.8 nas\_rsrqInformation unpack\_nas\_SLQSGetSignalStrength\_t::rsrqInfo

8.898.2.9 nas\_rxSignalStrengthListElement unpack\_nas\_SLQSGetSignalStrength\_t::rxSignalStrengthList[18]

8.898.2.10 uint16\_t unpack\_nas\_SLQSGetSignalStrength\_t::rxSignalStrengthListLen

8.898.2.11 uint16\_t unpack\_nas\_SLQSGetSignalStrength\_t::signalStrengthReqMask

8.898.2.12 uint8\_t unpack\_nas\_SLQSGetSignalStrength\_t::sinr

## 8.899 unpack\_nas\_SLQSGetSysInfo\_t Struct Reference

## Data Fields

- [nas\\_SrvStatusInfo](#) \* [pCDMASrvStatusInfo](#)
- [nas\\_SrvStatusInfo](#) \* [pHDRSrvStatusInfo](#)
- [nas\\_GSMSrvStatusInfo](#) \* [pGSMSrvStatusInfo](#)
- [nas\\_GSMSrvStatusInfo](#) \* [pWCDMASrvStatusInfo](#)
- [nas\\_GSMSrvStatusInfo](#) \* [pLTESrvStatusInfo](#)
- [nas\\_CDMASysInfo](#) \* [pCDMASysInfo](#)
- [nas\\_HDRSysInfo](#) \* [pHDRSysInfo](#)
- [nas\\_GSMSysInfo](#) \* [pGSMSysInfo](#)
- [nas\\_WCDMASysInfo](#) \* [pWCDMASysInfo](#)

- [nas\\_LTESysInfo](#) \* [pLTESysInfo](#)
- [nas\\_AddCDMASysInfo](#) \* [pAddCDMASysInfo](#)
- [uint16\\_t](#) \* [pAddHDRSysInfo](#)
- [nas\\_AddSysInfo](#) \* [pAddGSMSysInfo](#)
- [nas\\_AddSysInfo](#) \* [pAddWCDMASysInfo](#)
- [uint16\\_t](#) \* [pAddLTESysInfo](#)
- [nas\\_CallBarringSysInfo](#) \* [pGSMCallBarringSysInfo](#)
- [nas\\_CallBarringSysInfo](#) \* [pWCDMACallBarringSysInfo](#)
- [uint8\\_t](#) \* [pLTEVoiceSupportSysInfo](#)
- [uint8\\_t](#) \* [pGSMCipherDomainSysInfo](#)
- [uint8\\_t](#) \* [pWCDMACipherDomainSysInfo](#)

## 8.899.1 Detailed Description

### Parameters

<i>pCDMASrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SrvStatusInfo</a> for more information.</li> </ul>
<i>pHDRSrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SrvStatusInfo</a> for more information.</li> </ul>
<i>pGSMSrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pWCDMASrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pLTESrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CDMASysInfo</a> for more information.</li> </ul>
<i>pHDRSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">HDRSysInfo</a> for more information.</li> </ul>
<i>pGSMSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSysInfo</a> for more information.</li> </ul>
<i>pWCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">WCDMASysInfo</a> for more information.</li> </ul>
<i>pLTESysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">LTESysInfo</a> for more information.</li> </ul>
<i>pAddCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddCDMASysInfo</a> for more information.</li> </ul>
<i>pAddHDRSysInfo</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>pAddGSMSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddSysInfo</a> for more information.</li> </ul>
<i>pAddWCDMA-SysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddSysInfo</a> for more information.</li> </ul>
<i>pAddLTESysInfo</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>

<i>pGSMCallBarringSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CallBarringSysInfo</a> for more information.</li> </ul>
<i>pWCDMACallBarringSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CallBarringSysInfo</a> for more information.</li> </ul>
<i>pLTEVoiceSupportSysInfo</i>	<ul style="list-style-type: none"> <li>• Indicates voice support status on LTE. <ul style="list-style-type: none"> <li>– 0x00 - Voice is not supported</li> <li>– 0x01 - Voice is supported</li> </ul> </li> </ul>
<i>pGSMCipherDomainSysInfo</i>	<ul style="list-style-type: none"> <li>• Ciphering on the service domain. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> </ul> </li> </ul>
<i>pWCDMACipherDomainSysInfo</i>	<ul style="list-style-type: none"> <li>• Ciphering on the service domain. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> </ul> </li> </ul>

## 8.899.2 Field Documentation

8.899.2.1 **nas\_AddCDMASysInfo\*** `unpack_nas_SLQSGetSysInfo_t::pAddCDMASysInfo`

8.899.2.2 **nas\_AddSysInfo\*** `unpack_nas_SLQSGetSysInfo_t::pAddGSMSysInfo`

8.899.2.3 **uint16\_t\*** `unpack_nas_SLQSGetSysInfo_t::pAddHDRSysInfo`

8.899.2.4 **uint16\_t\*** `unpack_nas_SLQSGetSysInfo_t::pAddLTESysInfo`

8.899.2.5 **nas\_AddSysInfo\*** `unpack_nas_SLQSGetSysInfo_t::pAddWCDMASysInfo`

8.899.2.6 **nas\_SrvStatusInfo\*** `unpack_nas_SLQSGetSysInfo_t::pCDMASrvStatusInfo`

8.899.2.7 **nas\_CDMASysInfo\*** `unpack_nas_SLQSGetSysInfo_t::pCDMASysInfo`

8.899.2.8 **nas\_CallBarringSysInfo\*** `unpack_nas_SLQSGetSysInfo_t::pGSMCallBarringSysInfo`

8.899.2.9 **uint8\_t\*** `unpack_nas_SLQSGetSysInfo_t::pGSMCipherDomainSysInfo`

8.899.2.10 **nas\_GSMSrvStatusInfo\*** `unpack_nas_SLQSGetSysInfo_t::pGSMSrvStatusInfo`

- 8.899.2.11 `nas_GSMSSysInfo*` `unpack_nas_SLQSGetSysInfo_t::pGSMSSysInfo`
- 8.899.2.12 `nas_SrvStatusInfo*` `unpack_nas_SLQSGetSysInfo_t::pHDRSrvStatusInfo`
- 8.899.2.13 `nas_HDRSysInfo*` `unpack_nas_SLQSGetSysInfo_t::pHDRSysInfo`
- 8.899.2.14 `nas_GSMSrvStatusInfo*` `unpack_nas_SLQSGetSysInfo_t::pLTESrvStatusInfo`
- 8.899.2.15 `nas_LTESysInfo*` `unpack_nas_SLQSGetSysInfo_t::pLTESysInfo`
- 8.899.2.16 `uint8_t*` `unpack_nas_SLQSGetSysInfo_t::pLTEVoiceSupportSysInfo`
- 8.899.2.17 `nas_CallBarringSysInfo*` `unpack_nas_SLQSGetSysInfo_t::pWCDMACallBarringSysInfo`
- 8.899.2.18 `uint8_t*` `unpack_nas_SLQSGetSysInfo_t::pWCDMACipherDomainSysInfo`
- 8.899.2.19 `nas_GSMSrvStatusInfo*` `unpack_nas_SLQSGetSysInfo_t::pWCDMASrvStatusInfo`
- 8.899.2.20 `nas_WCDMASysInfo*` `unpack_nas_SLQSGetSysInfo_t::pWCDMASysInfo`

## 8.900 `unpack_nas_SLQSGetSysSelectionPref_t` Struct Reference

### Data Fields

- `uint8_t *` [pEmerMode](#)
- `uint16_t *` [pModePref](#)
- `uint64_t *` [pBandPref](#)
- `uint16_t *` [pPRLPref](#)
- `uint16_t *` [pRoamPref](#)
- `uint64_t *` [pLTEBandPref](#)
- `uint8_t *` [pNetSelPref](#)
- `uint32_t *` [pSrvDomainPref](#)
- `uint32_t *` [pGWAcqOrderPref](#)

### 8.900.1 Detailed Description

#### Parameters

<i>pEmerMode</i>	<ul style="list-style-type: none"> <li>• Optional parameter specifying the emergency Mode</li> <li>• Values:             <ul style="list-style-type: none"> <li>– 0 - OFF (normal)</li> <li>– 1 - ON (Emergency)</li> </ul> </li> </ul>
------------------	---



<i>pModePref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit Mask indicating the radio technology mode preference</li> <li>• Bit values: <ul style="list-style-type: none"> <li>– Bit 0 - cdma2000 1x</li> <li>– Bit 1 - cdma2000 HRPD(1xEV-DO)</li> <li>– Bit 2 - GSM</li> <li>– Bit 3 - UMTS</li> <li>– Bit 4 - LTE</li> </ul> </li> </ul>
<i>pBandPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit mask representing the band preference</li> <li>• Bit values: <ul style="list-style-type: none"> <li>– Bit 0 - Band Class 0, A-System</li> <li>– Bit 1 - Band Class 0, B-System, Band Class 0 AB, GSM 850 Band</li> <li>– Bit 2 - Band Class 1, all blocks</li> <li>– Bit 3 - Band Class 2 place holder</li> <li>– Bit 4 - Band Class 3, A-System</li> <li>– Bit 5 - Band Class 4, all blocks</li> <li>– Bit 6 - Band Class 5, all blocks</li> <li>– Bit 7 - GSM_DCS_1800 band</li> <li>– Bit 8 - GSM Extended GSM (E-GSM) 900 band</li> <li>– Bit 9 - GSM Primary GSM (P-GSM) 900 band</li> <li>– Bit 10 - Band Class 6</li> <li>– Bit 11 - Band Class 7</li> <li>– Bit 12 - Band Class 8</li> <li>– Bit 13 - Band Class 9</li> <li>– Bit 14 - Band Class 10</li> <li>– Bit 15 - Band Class 11</li> <li>– Bit 16 - GSM 450 band</li> <li>– Bit 17 - GSM 480 band</li> <li>– Bit 18 - GSM 750 band</li> <li>– Bit 19 - GSM 850 band</li> <li>– Bit 20 - GSM Railways GSM 900 Band</li> <li>– Bit 21 - GSM PCS 1900 band</li> <li>– Bit 22 - WCDMA Europe, Japan, and China IMT 2100 band</li> <li>– Bit 23 - WCDMA U.S. PCS 1900 band</li> <li>– Bit 24 - WCDMA Europe and China DCS 1800 band</li> <li>– Bit 25 - WCDMA U.S. 1700 band</li> <li>– Bit 26 - WCDMA U.S. 850 band</li> <li>– Bit 27 - WCDMA Japan 800 band</li> <li>– Bit 28 - Band Class 12</li> <li>– Bit 29 - Band Class 14</li> <li>– Bit 30 - Reserved</li> <li>– Bit 31 - Band Class 15</li> <li>– Bit 32 to 47 - Reserved</li> </ul> </li> </ul>

<i>pPRLPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating the CDMA PRL Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x0001 - Acquire available system only on the A side</li> <li>– 0x0002 - Acquire available system only on the B side</li> <li>– 0x3FFF - Acquire any available systems</li> </ul> </li> </ul>
<i>pRoamPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating the roaming Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - Acquire only systems for which the roaming indicator is off</li> <li>– 0x02 - Acquire a system as long as its roaming indicator is not off</li> <li>– 0x03 - Acquire only systems for which the roaming indicator is off or solid on, i.e. not flashing; CDMA only</li> <li>– 0xFF - Acquire systems, regardless of their roaming indicator</li> </ul> </li> </ul>
<i>pLTEBandPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit mask representing the LTE band preference</li> <li>• Bit Values <ul style="list-style-type: none"> <li>– Bit 0 - E-UTRA Operating Band 1</li> <li>– Bit 1 - E-UTRA Operating Band 2</li> <li>– Bit 2 - E-UTRA Operating Band 3</li> <li>– Bit 3 - E-UTRA Operating Band 4</li> <li>– Bit 4 - E-UTRA Operating Band 5</li> <li>– Bit 5 - E-UTRA Operating Band 6</li> <li>– Bit 6 - E-UTRA Operating Band 7</li> <li>– Bit 7 - E-UTRA Operating Band 8</li> <li>– Bit 8 - E-UTRA Operating Band 9</li> <li>– Bit 9 - E-UTRA Operating Band 10</li> <li>– Bit 10 - E-UTRA Operating Band 11</li> <li>– Bit 11 - E-UTRA Operating Band 12</li> <li>– Bit 12 - E-UTRA Operating Band 13</li> <li>– Bit 13 - E-UTRA Operating Band 14</li> <li>– Bit 16 - E-UTRA Operating Band 17</li> <li>– Bit 17 - E-UTRA Operating Band 18</li> <li>– Bit 18 - E-UTRA Operating Band 19</li> <li>– Bit 19 - E-UTRA Operating Band 20</li> <li>– Bit 20 - E-UTRA Operating Band 21</li> <li>– Bit 32 - E-UTRA Operating Band 33</li> <li>– Bit 33 - E-UTRA Operating Band 34</li> <li>– Bit 34 - E-UTRA Operating Band 35</li> <li>– Bit 35 - E-UTRA Operating Band 36</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– Bit 36 - E-UTRA Operating Band 37</li> <li>– Bit 37 - E-UTRA Operating Band 38</li> <li>– Bit 38 - E-UTRA Operating Band 39</li> <li>– Bit 39 - E-UTRA Operating Band 40</li> </ul>

<i>pNetSelPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating network selection preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Automatic network selection</li> <li>– 0x01 - Manual network selection.</li> </ul> </li> </ul>
<i>pSrvDomainPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating Service domain preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Circuit switched only</li> <li>– 0x01 - Packet switched only</li> <li>– 0x02 - Circuit switched and packet switched</li> <li>– 0x03 - Packet switched attach</li> <li>– 0x04 - Packet switched detach</li> </ul> </li> </ul>
<i>pGWAcqOrder-Pref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating GSM/WCDMA Acquisition order Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Automatic</li> <li>– 0x01 - GSM then WCDMA</li> <li>– 0x02 - WCDMA then GSM</li> </ul> </li> </ul>

## 8.900.2 Field Documentation

8.900.2.1 uint64\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pBandPref

8.900.2.2 uint8\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pEmerMode

8.900.2.3 uint32\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pGWAcqOrderPref

8.900.2.4 uint64\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pLTEBandPref

8.900.2.5 uint16\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pModePref

8.900.2.6 uint8\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pNetSelPref

8.900.2.7 uint16\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pPRLPref

8.900.2.8 uint16\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pRoamPref

8.900.2.9 uint32\_t\* unpack\_nas\_SLQSGetSysSelectionPref\_t::pSrvDomainPref

## 8.901 unpack\_nas\_SLQSNasGetCellLocationInfo\_t Struct Reference

## Data Fields

- [nas\\_GERANInfo](#) \* [pGERANInfo](#)
- [nas\\_UMTSInfo](#) \* [pUMTSInfo](#)
- [nas\\_CDMAInfo](#) \* [pCDMAInfo](#)
- [nas\\_LTEInfoIntrafreq](#) \* [pLTEInfoIntrafreq](#)
- [nas\\_LTEInfoInterfreq](#) \* [pLTEInfoInterfreq](#)
- [nas\\_LTEInfoNeighboringGSM](#) \* [pLTEInfoNeighboringGSM](#)
- [nas\\_LTEInfoNeighboringWCDMA](#) \* [pLTEInfoNeighboringWCDMA](#)
- [uint32\\_t](#) \* [pUMTSCellID](#)
- [nas\\_WCDMAInfoLTENeighborCell](#) \* [pWCDMAInfoLTENeighborCell](#)

### 8.901.1 Detailed Description

This structure contains information about the Get Cell Location response parameters.

#### Parameters

<i>pGERANInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_GERANInfo</a> for more information.</li> </ul>
<i>pUMTSInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_UMTSInfo</a> for more information.</li> </ul>
<i>pCDMAInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_CDMAInfo</a> for more information.</li> </ul>
<i>pLTEInfo-Intrafreq</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_LTEInfoIntrafreq</a> for more information.</li> </ul>
<i>pLTEInfo-Interfreq</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_LTEInfoInterfreq</a> for more information.</li> </ul>
<i>pLTEInfo-NeighboringGSM</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_LTEInfoNeighboringGSM</a> for more information.</li> </ul>
<i>pLTEInfo-NeighboringWCDMA</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_LTEInfoNeighboringWCDMA</a> for more information.</li> </ul>
<i>pUMTSCellID</i>	<ul style="list-style-type: none"> <li>• Cell ID.</li> <li>• 0xFFFFFFFF indicates cell ID information is not present.</li> </ul>
<i>pWCDMAInfoLTENeighborCell</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_WCDMAInfoLTENeighborCell</a> for more information.</li> </ul>

### 8.901.2 Field Documentation

8.901.2.1 [nas\\_CDMAInfo](#)\* [unpack\\_nas\\_SLQSNasGetCellLocationInfo\\_t::pCDMAInfo](#)

8.901.2.2 [nas\\_GERANInfo](#)\* [unpack\\_nas\\_SLQSNasGetCellLocationInfo\\_t::pGERANInfo](#)

- 8.901.2.3 nas\_LTEInfoInterfreq\* unpack\_nas\_SLQSNasGetCellLocationInfo\_t::pLTEInfoInterfreq
- 8.901.2.4 nas\_LTEInfoIntrafreq\* unpack\_nas\_SLQSNasGetCellLocationInfo\_t::pLTEInfoIntrafreq
- 8.901.2.5 nas\_LTEInfoNeighboringGSM\* unpack\_nas\_SLQSNasGetCellLocationInfo\_t::pLTEInfoNeighboringGSM
- 8.901.2.6 nas\_LTEInfoNeighboringWCDMA\* unpack\_nas\_SLQSNasGetCellLocationInfo\_t::pLTEInfoNeighboringWCDMA
- 8.901.2.7 uint32\_t\* unpack\_nas\_SLQSNasGetCellLocationInfo\_t::pUMTSCellID
- 8.901.2.8 nas\_UMTSInfo\* unpack\_nas\_SLQSNasGetCellLocationInfo\_t::pUMTSInfo
- 8.901.2.9 nas\_WCDMAInfoLTENeighborCell\* unpack\_nas\_SLQSNasGetCellLocationInfo\_t::pWCDMAInfoLTENeighborCell

## 8.902 unpack\_nas\_SLQSNasGetSigInfo\_t Struct Reference

### Data Fields

- [cdmaSSInfo](#) [CDMASSInfo](#)
- [hdrSSInfo](#) [HDRSSInfo](#)
- [int8\\_t](#) [GSMSSInfo](#)
- [cdmaSSInfo](#) [WCDMASSInfo](#)
- [lteSSInfo](#) [LTESSInfo](#)

### 8.902.1 Detailed Description

#### Parameters

<a href="#">CDMASSInfo</a>	CDMA Signal Strength Information
<a href="#">HDRSSInfo</a>	HDR Signal Strength Information
<a href="#">GSMSSInfo</a>	GSM signal strength is the RSSI in dBm.
<a href="#">WCDMASSInfo</a>	WCDMA Signal Strength Information
<a href="#">LTESSInfo</a>	LTE Signal Strength Information

### 8.902.2 Field Documentation

- 8.902.2.1 [cdmaSSInfo](#) [unpack\\_nas\\_SLQSNasGetSigInfo\\_t::CDMASSInfo](#)
- 8.902.2.2 [int8\\_t](#) [unpack\\_nas\\_SLQSNasGetSigInfo\\_t::GSMSSInfo](#)
- 8.902.2.3 [hdrSSInfo](#) [unpack\\_nas\\_SLQSNasGetSigInfo\\_t::HDRSSInfo](#)
- 8.902.2.4 [lteSSInfo](#) [unpack\\_nas\\_SLQSNasGetSigInfo\\_t::LTESSInfo](#)
- 8.902.2.5 [cdmaSSInfo](#) [unpack\\_nas\\_SLQSNasGetSigInfo\\_t::WCDMASSInfo](#)

## 8.903 unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t Struct Reference

### Data Fields

- [nas\\_UniversalTime](#) [universalTime](#)
- [uint8\\_t](#) \* [pTimeZone](#)

- uint8\_t \* [pDayltSavAdj](#)
- uint8\_t \* [pRadioInterface](#)

### 8.903.1 Detailed Description

Structure for storing the NAS Network Time indication parameters.

#### Parameters

<i>universalTime</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nas_UniversalTime</a> for more information.</li> </ul>
<i>pTimeZone</i>	<ul style="list-style-type: none"> <li>• Time Zone.</li> <li>• Offset from Universal time, i.e., the difference between local time and Universal time, in increments of 15 min (signed value).</li> </ul>
<i>pDayltSavAdj</i>	<ul style="list-style-type: none"> <li>• Daylight Saving Adjustment.</li> <li>• Daylight saving adjustment in hr. <ul style="list-style-type: none"> <li>– Possible values: 0, 1, and 2.</li> </ul> </li> </ul>
<i>pRadioInterface</i>	<ul style="list-style-type: none"> <li>• Radio interface from which the information comes</li> <li>• Values <ul style="list-style-type: none"> <li>– 0x01 - NAS_RADIO_IF_CDMA_1X - cdma2000 1X</li> <li>– 0x02 - NAS_RADIO_IF_CDMA_1xEVDO - cdma2000 HRPD (1xEV-DO)</li> <li>– 0x04 - NAS_RADIO_IF_GSM - GSM</li> <li>– 0x05 - NAS_RADIO_IF_UMTS - UMTS</li> <li>– 0x08 - NAS_RADIO_IF_LTE - LTE</li> <li>– 0x09 - NAS_RADIO_IF_TDSCDMA - TD-SCDMA</li> </ul> </li> </ul>

### 8.903.2 Field Documentation

- 8.903.2.1 uint8\_t\* unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t::pDayltSavAdj
- 8.903.2.2 uint8\_t\* unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t::pRadioInterface
- 8.903.2.3 uint8\_t\* unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t::pTimeZone
- 8.903.2.4 nas\_UniversalTime unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t::universalTime

## 8.904 unpack\_nas\_SLQSNasSigInfoCallback\_t Struct Reference

### Data Fields

- cdmaSSInfo \* pCDMASigInfo
- hdrSSInfo \* pHDRSigInfo
- int8\_t \* pGSMSigInfo
- cdmaSSInfo \* pWCDMASigInfo
- lteSSInfo \* pLTESigInfo
- int8\_t \* pRscp
- tdscdmaSigInfoExt \* pTDSCDMASigInfoExt

### 8.904.1 Detailed Description

#### Parameters

<i>pCDMASigInfo</i>	CDMA SS info
<i>pHDRSigInfo</i>	HDR SS info
<i>pGSMSigInfo</i>	GSM signal info
<i>pWCDMASigInfo</i>	WCDMA signal info
<i>pLTESigInfo</i>	LTE signal info
<i>pRscp</i>	RSCP of the Primary Common Control Physical Channel
<i>pTDSCDMASig-InfoExt</i>	extra CDMA sig info

### 8.904.2 Field Documentation

- 8.904.2.1 cdmaSSInfo\* unpack\_nas\_SLQSNasSigInfoCallback\_t::pCDMASigInfo
- 8.904.2.2 int8\_t\* unpack\_nas\_SLQSNasSigInfoCallback\_t::pGSMSigInfo
- 8.904.2.3 hdrSSInfo\* unpack\_nas\_SLQSNasSigInfoCallback\_t::pHDRSigInfo
- 8.904.2.4 lteSSInfo\* unpack\_nas\_SLQSNasSigInfoCallback\_t::pLTESigInfo
- 8.904.2.5 int8\_t\* unpack\_nas\_SLQSNasSigInfoCallback\_t::pRscp
- 8.904.2.6 tdscdmaSigInfoExt\* unpack\_nas\_SLQSNasSigInfoCallback\_t::pTDSCDMASigInfoExt
- 8.904.2.7 cdmaSSInfo\* unpack\_nas\_SLQSNasSigInfoCallback\_t::pWCDMASigInfo

## 8.905 unpack\_nas\_SLQSNasSwiModemStatus\_t Struct Reference

### Data Fields

- [nas\\_CommInfo](#) [commonInfo](#)
- [nas\\_LTEInfo](#) \* [pLTEInfo](#)

### 8.905.1 Detailed Description

Structure for storing the SLQS Nas Swi Modem Status response parameters.

#### Parameters

<i>commonInfo</i>	(mandatory) <ul style="list-style-type: none"> <li>• See <a href="#">CommInfo</a> for more information</li> </ul>
<i>pLTEInfo</i>	(optional) <ul style="list-style-type: none"> <li>• See <a href="#">LTEInfo</a> for more information</li> </ul>

### 8.905.2 Field Documentation

8.905.2.1 [nas\\_CommInfo](#) [unpack\\_nas\\_SLQSNasSwiModemStatus\\_t::commonInfo](#)

8.905.2.2 [nas\\_LTEInfo](#)\* [unpack\\_nas\\_SLQSNasSwiModemStatus\\_t::pLTEInfo](#)

## 8.906 unpack\_nas\_SLQSNasSwiOTAMessageCallback\_ind\_t Struct Reference

### Data Fields

- [NASQmiCbkJasSwiOTAMessageInd](#) [Info](#)
- [uint16\\_t](#) [Tlvresult](#)

### 8.906.1 Detailed Description

#### Parameters

<i>Info</i>	<ul style="list-style-type: none"> <li>• Structure used to store all QMI Notification Info. <ul style="list-style-type: none"> <li>– See <a href="#">NASQmiCbkJasSwiOTAMessageInd</a> for more details</li> </ul> </li> </ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"> <li>• unpack result</li> </ul>

### 8.906.2 Field Documentation

8.906.2.1 [NASQmiCbkJasSwiOTAMessageInd](#) [unpack\\_nas\\_SLQSNasSwiOTAMessageCallback\\_ind\\_t::Info](#)

8.906.2.2 [uint16\\_t](#) [unpack\\_nas\\_SLQSNasSwiOTAMessageCallback\\_ind\\_t::Tlvresult](#)



## 8.907 unpack\_nas\_SLQSSetSysSelectionPrefCallBack\_ind\_t Struct Reference

### Data Fields

- [NASQmiCbKnasSystemSelPrefInd Info](#)
- uint16\_t [Tlvresult](#)

### 8.907.1 Detailed Description

#### Parameters

<i>Info</i>	<ul style="list-style-type: none"><li>• Structure used to store all QMI Notification Info.<ul style="list-style-type: none"><li>– See <a href="#">NASQmiCbKnasSystemSelPrefInd</a> for more details</li></ul></li></ul>
<i>Tlvresult</i>	<ul style="list-style-type: none"><li>• unpack result</li></ul>

### 8.907.2 Field Documentation

8.907.2.1 [NASQmiCbKnasSystemSelPrefInd](#) unpack\_nas\_SLQSSetSysSelectionPrefCallBack\_ind\_t::Info

8.907.2.2 [uint16\\_t](#) unpack\_nas\_SLQSSetSysSelectionPrefCallBack\_ind\_t::Tlvresult

## 8.908 unpack\_nas\_SLQSSwiGetLteCQI\_t Struct Reference

### Data Fields

- [uint8\\_t](#) [ValidityCW0](#)
- [uint8\\_t](#) [CQIValueCW0](#)
- [uint8\\_t](#) [ValidityCW1](#)
- [uint8\\_t](#) [CQIValueCW1](#)

### 8.908.1 Detailed Description

#### Parameters

<i>ValidityCW0[OUT]</i>	<ul style="list-style-type: none"> <li>Values           <ul style="list-style-type: none"> <li>0- Invalid.</li> <li>1- Valid.</li> </ul> </li> </ul>
<i>CQIValueCW0[OUT]</i>	<ul style="list-style-type: none"> <li>Values           <ul style="list-style-type: none"> <li>Range 0~15</li> </ul> </li> </ul>
<i>ValidityCW1[OUT]</i>	<ul style="list-style-type: none"> <li>Values           <ul style="list-style-type: none"> <li>0- Invalid.</li> <li>1- Valid.</li> </ul> </li> </ul>
<i>CQIValueCW1[OUT]</i>	<ul style="list-style-type: none"> <li>Values           <ul style="list-style-type: none"> <li>Range 0~15</li> </ul> </li> </ul>

### 8.908.2 Field Documentation

8.908.2.1 `uint8_t unpack_nas_SLQSSwiGetLteCQI_t::CQIValueCW0`

8.908.2.2 `uint8_t unpack_nas_SLQSSwiGetLteCQI_t::CQIValueCW1`

8.908.2.3 `uint8_t unpack_nas_SLQSSwiGetLteCQI_t::ValidityCW0`

8.908.2.4 `uint8_t unpack_nas_SLQSSwiGetLteCQI_t::ValidityCW1`

### 8.909 `unpack_nas_SLQSSysInfoCallback_t` Struct Reference

#### Data Fields

- `nas_SrvStatusInfo * pCDMASrvStatusInfo`
- `nas_SrvStatusInfo * pHDRSrvStatusInfo`
- `nas_GSMSrvStatusInfo * pGSMSrvStatusInfo`
- `nas_GSMSrvStatusInfo * pWCDMASrvStatusInfo`
- `nas_GSMSrvStatusInfo * pLTESrvStatusInfo`
- `nas_CDMASysInfo * pCDMASysInfo`
- `nas_HDRSysInfo * pHDRSysInfo`
- `nas_GSMSysInfo * pGSMSysInfo`
- `nas_WCDMASysInfo * pWCDMASysInfo`
- `nas_LTESysInfo * pLTESysInfo`
- `nas_AddCDMASysInfo * pAddCDMASysInfo`

- uint16\_t \* [pAddHDRSysInfo](#)
- [nas\\_AddSysInfo](#) \* [pAddGSMSysInfo](#)
- [nas\\_AddSysInfo](#) \* [pAddWCDMASysInfo](#)
- uint16\_t \* [pAddLTESysInfo](#)
- [nas\\_CallBarringSysInfo](#) \* [pGSMCallBarringSysInfo](#)
- [nas\\_CallBarringSysInfo](#) \* [pWCDMACallBarringSysInfo](#)
- uint8\_t \* [pLTEVoiceSupportSysInfo](#)
- uint8\_t \* [pGSMCipherDomainSysInfo](#)
- uint8\_t \* [pWCDMACipherDomainSysInfo](#)
- uint8\_t \* [pSysInfoNoChange](#)

### 8.909.1 Detailed Description

#### Parameters

<i>pCDMASrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SrvStatusInfo</a> for more information.</li> </ul>
<i>pHDRSrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SrvStatusInfo</a> for more information.</li> </ul>
<i>pGSMSrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pWCDMASrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pLTESrvStatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSrvStatusInfo</a> for more information.</li> </ul>
<i>pCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CDMASysInfo</a> for more information.</li> </ul>
<i>pHDRSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">HDRSysInfo</a> for more information.</li> </ul>
<i>pGSMSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GSMSysInfo</a> for more information.</li> </ul>
<i>pWCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">WCDMASysInfo</a> for more information.</li> </ul>
<i>pLTESysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">LTESysInfo</a> for more information.</li> </ul>
<i>pAddCDMASysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddCDMASysInfo</a> for more information.</li> </ul>
<i>pAddHDRSysInfo</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>

<i>pAddGSMSys-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddSysInfo</a> for more information.</li> </ul>
<i>pAddWCDMA-SysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">AddSysInfo</a> for more information.</li> </ul>
<i>pAddLTESysInfo</i>	<ul style="list-style-type: none"> <li>• System table index referencing the beginning of the geo in which the current serving system is present.</li> <li>• When the system index is not known, 0xFFFF is used.</li> </ul>
<i>pGSMCall-BarringSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CallBarringSysInfo</a> for more information.</li> </ul>
<i>pWCDMACall-BarringSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CallBarringSysInfo</a> for more information.</li> </ul>
<i>pLTEVoice-SupportSysInfo</i>	<ul style="list-style-type: none"> <li>• Indicates voice support status on LTE. <ul style="list-style-type: none"> <li>– 0x00 - Voice is not supported</li> <li>– 0x01 - Voice is supported</li> </ul> </li> </ul>
<i>pGSMCipher-DomainSysInfo</i>	<ul style="list-style-type: none"> <li>• Ciphering on the service domain. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> </ul> </li> </ul>
<i>pWCDMA-CipherDomain-SysInfo</i>	<ul style="list-style-type: none"> <li>• Ciphering on the service domain. <ul style="list-style-type: none"> <li>– 0x00 - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> </ul> </li> </ul>
<i>pSysInfoNo-Change</i>	<ul style="list-style-type: none"> <li>• System Info No Change.</li> <li>• Flag used to notify clients that a request to select a network ended with no change in the PLMN. <ul style="list-style-type: none"> <li>– 0x01 - No change in system information</li> </ul> </li> </ul>

## 8.909.2 Field Documentation

- 8.909.2.1 `nas_AddCDMASysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pAddCDMASysInfo`
- 8.909.2.2 `nas_AddSysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pAddGSM SysInfo`
- 8.909.2.3 `uint16_t*` `unpack_nas_SLQSSysInfoCallback_t::pAddHDRSysInfo`
- 8.909.2.4 `uint16_t*` `unpack_nas_SLQSSysInfoCallback_t::pAddLTESysInfo`
- 8.909.2.5 `nas_AddSysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pAddWCDMASysInfo`
- 8.909.2.6 `nas_SrvStatusInfo*` `unpack_nas_SLQSSysInfoCallback_t::pCDMASrvStatusInfo`
- 8.909.2.7 `nas_CDMASysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pCDMASysInfo`
- 8.909.2.8 `nas_CallBarringSysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pGSMCallBarringSysInfo`
- 8.909.2.9 `uint8_t*` `unpack_nas_SLQSSysInfoCallback_t::pGSMCipherDomainSysInfo`
- 8.909.2.10 `nas_GSMSrvStatusInfo*` `unpack_nas_SLQSSysInfoCallback_t::pGSM SrvStatusInfo`
- 8.909.2.11 `nas_GSM SysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pGSM SysInfo`
- 8.909.2.12 `nas_SrvStatusInfo*` `unpack_nas_SLQSSysInfoCallback_t::pHDRSrvStatusInfo`
- 8.909.2.13 `nas_HDRSysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pHDRSysInfo`
- 8.909.2.14 `nas_GSMSrvStatusInfo*` `unpack_nas_SLQSSysInfoCallback_t::pLTESrvStatusInfo`
- 8.909.2.15 `nas_LTESysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pLTESysInfo`
- 8.909.2.16 `uint8_t*` `unpack_nas_SLQSSysInfoCallback_t::pLTEVoiceSupportSysInfo`
- 8.909.2.17 `uint8_t*` `unpack_nas_SLQSSysInfoCallback_t::pSysInfoNoChange`
- 8.909.2.18 `nas_CallBarringSysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pWCDMACallBarringSysInfo`
- 8.909.2.19 `uint8_t*` `unpack_nas_SLQSSysInfoCallback_t::pWCDMACipherDomainSysInfo`
- 8.909.2.20 `nas_GSMSrvStatusInfo*` `unpack_nas_SLQSSysInfoCallback_t::pWCDMASrvStatusInfo`
- 8.909.2.21 `nas_WCDMASysInfo*` `unpack_nas_SLQSSysInfoCallback_t::pWCDMASysInfo`

## 8.910 `unpack_omaDmConfigTlv_t` Struct Reference

### Data Fields

- `uint8_t` [state](#)
- `uint8_t` [userInputReq](#)
- `uint16_t` [userInputTimeout](#)
- `uint16_t` [alertmsglength](#)

- uint8\_t [alertmsg](#) [256]

### 8.910.1 Detailed Description

This structure will hold the SwiOmaDmConfig session parameters information.

#### Parameters

<i>state</i>	<ul style="list-style-type: none"> <li>• 0x01 - OMA-DM Read Request</li> <li>• 0x02 - OMA-DM Change Request</li> <li>• 0x03 - OMA-DM Config Complete</li> </ul>
<i>user_input_req</i>	<ul style="list-style-type: none"> <li>- Bit mask of available user inputs</li> <li>• 0x00 - No user input required. Informational indication</li> <li>• 0x01 - Accept</li> <li>• 0x02 - Reject</li> </ul>
<i>user_input_timeout</i>	<ul style="list-style-type: none"> <li>• Timeout for user input in minutes. A value of 0 means no time-out</li> </ul>
<i>alertmsglength</i>	<ul style="list-style-type: none"> <li>• Length of Alert message string in bytes</li> </ul>
<i>alertmsg</i>	<ul style="list-style-type: none"> <li>• Alert message in UCS2 (Max 256 characters)</li> </ul>

### 8.910.2 Field Documentation

8.910.2.1 uint8\_t unpack\_omaDmConfigTlv\_t::alertmsg[256]

8.910.2.2 uint16\_t unpack\_omaDmConfigTlv\_t::alertmsglength

8.910.2.3 uint8\_t unpack\_omaDmConfigTlv\_t::state

8.910.2.4 uint8\_t unpack\_omaDmConfigTlv\_t::userInputReq

8.910.2.5 uint16\_t unpack\_omaDmConfigTlv\_t::userInputTimeout

## 8.911 unpack\_omaDmFotaTlv\_t Struct Reference

#### Data Fields

- uint8\_t [state](#)
- uint8\_t [userInputReq](#)
- uint16\_t [userInputTimeout](#)
- uint32\_t [fwdloadsize](#)
- uint32\_t [fwloadComplete](#)
- uint16\_t [updateCompleteStatus](#)

- uint8\_t [severity](#)
- uint16\_t [versionlength](#)
- uint8\_t [version](#) [256]
- uint16\_t [namelength](#)
- uint8\_t [package\\_name](#) [256]
- uint16\_t [descriptionlength](#)
- uint8\_t [description](#) [256]
- uint8\_t [sessionType](#)

### 8.911.1 Detailed Description

This structure will hold the SwiOmaDmFota session parameters information.

#### Parameters

<i>state</i>	<ul style="list-style-type: none"> <li>• 0x01 - No Firmware available</li> <li>• 0x02 - Query Firmware Download</li> <li>• 0x03 - Firmware Downloading</li> <li>• 0x04 - Firmware downloaded</li> <li>• 0x05 - Query Firmware Update</li> <li>• 0x06 - Firmware updating</li> <li>• 0x07 - Firmware updated</li> </ul>
<i>user_input_req</i>	<ul style="list-style-type: none"> <li>- Bit mask of available user inputs</li> <li>• 0x00 - No user input required. Informational indication</li> <li>• 0x01 - Accept</li> <li>• 0x02 - Reject</li> </ul>
<i>user_input_timeout</i>	<ul style="list-style-type: none"> <li>• Timeout for user input in minutes. A value of 0 means no time-out</li> </ul>
<i>fw_dload_size</i>	<ul style="list-style-type: none"> <li>• The size (in bytes) of the firmware update package</li> </ul>
<i>fw_dload_complete</i>	<ul style="list-style-type: none"> <li>• The number of bytes downloaded. Need to determine how often to send this message for progress bar notification. Every 500ms or 5% increment.</li> </ul>
<i>update_complete_status</i>	<ul style="list-style-type: none"> <li>• See table below.</li> </ul>
<i>severity</i>	<ul style="list-style-type: none"> <li>• 0x01 - Mandatory</li> <li>• 0x02 - Optional</li> </ul>



<i>versionlength</i>	<ul style="list-style-type: none"> <li>Length of FW Version string in bytes</li> </ul>
<i>version</i>	<ul style="list-style-type: none"> <li>FW Version string in ASCII (Max 256 characters)</li> </ul>
<i>namelength</i>	<ul style="list-style-type: none"> <li>Length Package Name string in bytes</li> </ul>
<i>package_name</i>	<ul style="list-style-type: none"> <li>Package Name in UCS2 (Max 256 characters)</li> </ul>
<i>descriptionlength</i>	<ul style="list-style-type: none"> <li>Length of description in bytes</li> </ul>
<i>description</i>	<ul style="list-style-type: none"> <li>Description of Update Package in USC2 (Max 256 characters)</li> </ul>
<i>sessionType</i>	<ul style="list-style-type: none"> <li>0x00 - Client initiated</li> <li>0x01 - Network initiated</li> </ul>

## 8.911.2 Field Documentation

- 8.911.2.1 `uint8_t unpack_omaDmFotaTlv_t::description[256]`
- 8.911.2.2 `uint16_t unpack_omaDmFotaTlv_t::descriptionlength`
- 8.911.2.3 `uint32_t unpack_omaDmFotaTlv_t::fwdloadsize`
- 8.911.2.4 `uint32_t unpack_omaDmFotaTlv_t::fwloadComplete`
- 8.911.2.5 `uint16_t unpack_omaDmFotaTlv_t::namelength`
- 8.911.2.6 `uint8_t unpack_omaDmFotaTlv_t::package_name[256]`
- 8.911.2.7 `uint8_t unpack_omaDmFotaTlv_t::sessionType`
- 8.911.2.8 `uint8_t unpack_omaDmFotaTlv_t::severity`
- 8.911.2.9 `uint8_t unpack_omaDmFotaTlv_t::state`
- 8.911.2.10 `uint16_t unpack_omaDmFotaTlv_t::updateCompleteStatus`
- 8.911.2.11 `uint8_t unpack_omaDmFotaTlv_t::userInputReq`
- 8.911.2.12 `uint16_t unpack_omaDmFotaTlv_t::userInputTimeout`
- 8.911.2.13 `uint8_t unpack_omaDmFotaTlv_t::version[256]`
- 8.911.2.14 `uint16_t unpack_omaDmFotaTlv_t::versionlength`

## 8.912 unpack\_omaDmNotificationsTlv\_t Struct Reference

### Data Fields

- uint8\_t [notification](#)
- uint16\_t [sessionStatus](#)

### 8.912.1 Field Documentation

8.912.1.1 uint8\_t unpack\_omaDmNotificationsTlv\_t::notification

8.912.1.2 uint16\_t unpack\_omaDmNotificationsTlv\_t::sessionStatus

## 8.913 unpack\_qmi\_t Struct Reference

### Data Fields

- enum [msgtype](#) type
- uint16\_t [msgid](#)
- uint16\_t [xid](#)

### 8.913.1 Detailed Description

qmi response context

#### Parameters

out	<i>type</i>	message type
out	<i>msgid</i>	message id
out	<i>xid</i>	transaction id

### 8.913.2 Field Documentation

8.913.2.1 uint16\_t unpack\_qmi\_t::msgid

8.913.2.2 enum [msgtype](#) unpack\_qmi\_t::type

8.913.2.3 uint16\_t unpack\_qmi\_t::xid

## 8.914 unpack\_qos\_dataRate\_t Struct Reference

### Data Fields

- uint32\_t [dataRateMax](#)
- uint32\_t [guaranteedRate](#)

### 8.914.1 Detailed Description

This structure contains the IP flow data rate min max

## Parameters

<i>dataRateMax</i>	Maximum required data rate (bits per second)
<i>guaranteedRate</i>	Minimum guaranteed data rate (bits per second)

## 8.914.2 Field Documentation

8.914.2.1 uint32\_t unpack\_qos\_dataRate\_t::dataRateMax

8.914.2.2 uint32\_t unpack\_qos\_dataRate\_t::guaranteedRate

## 8.915 unpack\_qos\_IPv4Addr\_t Struct Reference

## Data Fields

- uint32\_t [addr](#)
- uint32\_t [subnetMask](#)

## 8.915.1 Detailed Description

This structure contains the IPv4 filter address

## Parameters

<i>addr</i>	IPv4 address
<i>subnetMask</i>	<p>A packet matches if:</p> <ul style="list-style-type: none"> <li>• (addr and subnetMask) == (IP pkt addr &amp; subnetMask) Callers to set up a filter with a range of source addresses, if needed; subnet mask of all 1s (255.255.255.255) specifies a single address value</li> </ul>

## 8.915.2 Field Documentation

8.915.2.1 uint32\_t unpack\_qos\_IPv4Addr\_t::addr

8.915.2.2 uint32\_t unpack\_qos\_IPv4Addr\_t::subnetMask

## 8.916 unpack\_qos\_IPv6Addr\_t Struct Reference

## Data Fields

- uint8\_t [addr](#) [16]
- uint8\_t [prefixLen](#)

## 8.916.1 Detailed Description

This structure contains the IPv6 filter address

## Parameters

<i>addr</i>	IPv6 address (in network byte order); this is a 16-byte byte array (in Big-endian format)
<i>prefixLen</i>	IPv6 filter prefix length; can take a value between 0 and 128 Note: A packet matches if the IPv6 source address bytes until the prefix lengths are equal. Therefore prefix length can be used to set a filter with a range of source addresses. A prefix length of 128 specifies a single address value.

## 8.916.2 Field Documentation

8.916.2.1 `uint8_t unpack_qos_IPv6Addr_t::addr[16]`8.916.2.2 `uint8_t unpack_qos_IPv6Addr_t::prefixLen`8.917 `unpack_qos_IPv6TrafCls_t` Struct Reference

## Data Fields

- `uint8_t val`
- `uint8_t mask`

## 8.917.1 Detailed Description

This structure contains the IPv6 filter traffic class

## Parameters

<i>val</i>	The traffic class value
<i>mask</i>	<p>The packet matches the traffic class filter if: <code>(IPv6_filter_traffic_class_val and IPv6_filter_traffic_class_mask) == (Traffic class value in the IP packet &amp; IPv6_filter_traffic_class_mask)</code></p> <p>Example:</p> <ul style="list-style-type: none"> <li>• <code>IPv6_filter_tc_val = 00101000</code></li> <li>• <code>IPv6_filter_tc_mask = 11111100</code> Filter will compare only the first 6 bits in <code>IPv6_filter_traffic_class</code> with the first 6 bits in the traffic class field of the IP packet; first 6 bits in the traffic class field of the IP packet must be 001010 to match filter; last 2 bits can be anything, since they are ignored by filtering</li> </ul>

## 8.917.2 Field Documentation

8.917.2.1 `uint8_t unpack_qos_IPv6TrafCls_t::mask`8.917.2.2 `uint8_t unpack_qos_IPv6TrafCls_t::val`8.918 `unpack_qos_pktErrRate_t` Struct Reference

## Data Fields

- `uint16_t multiplier`
- `uint16_t exponent`

### 8.918.1 Detailed Description

This structure contains the IP flow packet error rate

## Parameters

<i>multiplier</i>	Factor m in calculating packet error rate: $E = m \cdot 10^{**}(-p)$
<i>exponent</i>	Factor p in calculating packet error rate (see above)

## 8.918.2 Field Documentation

8.918.2.1 uint16\_t unpack\_qos\_pktErrRate\_t::exponent

8.918.2.2 uint16\_t unpack\_qos\_pktErrRate\_t::multiplier

## 8.919 unpack\_qos\_Port\_t Struct Reference

## Data Fields

- uint16\_t [port](#)
- uint16\_t [range](#)

## 8.919.1 Detailed Description

This structure contains the [Port](#) Filter

## Parameters

<i>port</i>	port value of the filter
<i>range</i>	range specifies the number of ports to be included in the filter starting from port; filter will match if port in the IP packet lies between port and (port + range ) Range value of 0 implies that only one value of the port is valid, as specified by the port

## 8.919.2 Field Documentation

8.919.2.1 uint16\_t unpack\_qos\_Port\_t::port

8.919.2.2 uint16\_t unpack\_qos\_Port\_t::range

## 8.920 unpack\_qos\_QosFlowInfo\_t Struct Reference

## Data Fields

- [unpack\\_qos\\_QosFlowInfoState\\_t](#) QFlowState
- uint8\_t [is\\_TxQFlowGranted\\_Available](#)
- [unpack\\_qos\\_swiQosFlow\\_t](#) TxQFlowGranted
- uint8\_t [is\\_RxQFlowGranted\\_Available](#)
- [unpack\\_qos\\_swiQosFlow\\_t](#) RxQFlowGranted
- uint8\_t [NumTxFilters](#)
- [unpack\\_qos\\_swiQosFilter\\_t](#) TxQFilter [25]
- uint8\_t [NumRxFilters](#)
- [unpack\\_qos\\_swiQosFilter\\_t](#) RxQFilter [25]
- uint8\_t [BearerID](#)

### 8.920.1 Detailed Description

Structure with QoS flow details.

Please check is\_<Param\_Name>\_Available field for presence of optional parameters

## Parameters

<i>QFlowState</i>	<ul style="list-style-type: none"> <li>QoS flow state information, please check <a href="#">unpack_qos_QosFlowInfoState_t</a> for more information</li> </ul>
<i>is_TxQFlowGranted_Available</i>	<ul style="list-style-type: none"> <li>TRUE if optional TxQFlowGranted is available</li> </ul>
<i>TxQFlowGranted</i>	<ul style="list-style-type: none"> <li>The Tx Qos flow granted, please check <a href="#">unpack_qos_swiQosFlow_t</a> for more information</li> </ul>
<i>is_RxQFlowGranted_Available</i>	<ul style="list-style-type: none"> <li>TRUE if optional RxQFlowGranted is available</li> </ul>
<i>RxQFlowGranted</i>	<ul style="list-style-type: none"> <li>The Rx Qos flow granted, please check <a href="#">unpack_qos_swiQosFlow_t</a> for more information</li> </ul>
<i>NumTxFilters</i>	<ul style="list-style-type: none"> <li>Number of Tx filters available</li> </ul>
<i>TxQFilter</i>	<ul style="list-style-type: none"> <li>The Tx Qos filter, please check <a href="#">unpack_qos_swiQosFilter_t</a> for more information</li> <li>See <a href="#">LIBPACK_MAX_QOS_FILTERS</a> for more information</li> </ul>
<i>NumRxFilters</i>	<ul style="list-style-type: none"> <li>Number of Tx filters available</li> </ul>
<i>RxQFilter</i>	<ul style="list-style-type: none"> <li>The Rx Qos filter, please check <a href="#">unpack_qos_swiQosFilter_t</a> for more information</li> <li>See <a href="#">LIBPACK_MAX_QOS_FILTERS</a> for more information</li> </ul>
<i>BearerID</i>	<ul style="list-style-type: none"> <li>The bearer ID</li> <li>Bearer ID or Radio Link Protocol (RLP) ID of the activated flow.</li> <li>Valid Values - 0 to 16</li> <li>0xFF - Invalid value.</li> </ul>

## 8.920.2 Field Documentation

8.920.2.1 `uint8_t unpack_qos_QosFlowInfo_t::BearerID`8.920.2.2 `uint8_t unpack_qos_QosFlowInfo_t::is_RxQFlowGranted_Available`8.920.2.3 `uint8_t unpack_qos_QosFlowInfo_t::is_TxQFlowGranted_Available`



- 8.920.2.4 `uint8_t unpack_qos_QosFlowInfo_t::NumRxFilters`
- 8.920.2.5 `uint8_t unpack_qos_QosFlowInfo_t::NumTxFilters`
- 8.920.2.6 `unpack_qos_QosFlowInfoState_t unpack_qos_QosFlowInfo_t::QFlowState`
- 8.920.2.7 `unpack_qos_swiQosFilter_t unpack_qos_QosFlowInfo_t::RxQFilter[25]`
- 8.920.2.8 `unpack_qos_swiQosFlow_t unpack_qos_QosFlowInfo_t::RxQFlowGranted`
- 8.920.2.9 `unpack_qos_swiQosFilter_t unpack_qos_QosFlowInfo_t::TxQFilter[25]`
- 8.920.2.10 `unpack_qos_swiQosFlow_t unpack_qos_QosFlowInfo_t::TxQFlowGranted`

## 8.921 unpack\_qos\_QosFlowInfoState\_t Struct Reference

### Data Fields

- `uint32_t id`
- `uint8_t isNewFlow`
- `uint8_t state`

### 8.921.1 Detailed Description

This structure contains QoS flow state

#### Parameters

<i>id</i>	QoS identifier
<i>isNewFlow</i>	<ul style="list-style-type: none"> <li>• 1 – Newly added flow</li> <li>• 0 – Existing flow</li> </ul>
<i>state</i>	<p>This indicates that the flow that was added/modified/deleted:</p> <ul style="list-style-type: none"> <li>• 0x01 – Flow activated</li> <li>• 0x02 – Flow modified</li> <li>• 0x03 – Flow deleted</li> <li>• 0x04 – Flow suspended</li> <li>• 0x05 – Flow enabled</li> <li>• 0x06 – Flow disabled</li> </ul>

### 8.921.2 Field Documentation

- 8.921.2.1 `uint32_t unpack_qos_QosFlowInfoState_t::id`
- 8.921.2.2 `uint8_t unpack_qos_QosFlowInfoState_t::isNewFlow`
- 8.921.2.3 `uint8_t unpack_qos_QosFlowInfoState_t::state`

## 8.922 unpack\_qos\_SLQSQosGetNetworkStatus\_t Struct Reference

### Data Fields

- uint8\_t [NWQoSStatus](#)

### 8.922.1 Detailed Description

Structure that contains the response to get NW QoS status command

#### Parameters

<i>NWQoSStatus</i>	Network QoS support status <ul style="list-style-type: none"> <li>• 0 – No QoS support in network</li> <li>• 1 – Network supports QoS</li> </ul>
--------------------	--

### 8.922.2 Field Documentation

8.922.2.1 uint8\_t unpack\_qos\_SLQSQosGetNetworkStatus\_t::NWQoSStatus

## 8.923 unpack\_qos\_SLQSQosSwiReadApnExtraParams\_t Struct Reference

### Data Fields

- uint32\_t [apnId](#)
- uint8\_t [ambr\\_ul](#)
- uint8\_t [ambr\\_dl](#)
- uint8\_t [ambr\\_ul\\_ext](#)
- uint8\_t [ambr\\_dl\\_ext](#)
- uint8\_t [ambr\\_ul\\_ext2](#)
- uint8\_t [ambr\\_dl\\_ext2](#)

### 8.923.1 Detailed Description

Structure that contains extra APN parameters

#### Parameters

<i>apnId</i>	<ul style="list-style-type: none"> <li>• APN id</li> <li>• ID identifying the APN that the client would like to query the AMBR params</li> </ul>
<i>ambr_ul</i>	<ul style="list-style-type: none"> <li>• APN AMBR uplink</li> <li>• APN AMBR uplink values from 1 kbps to 8640 kbps</li> </ul>

<i>ambr_dl</i>	<ul style="list-style-type: none"> <li>• APN AMBR downlink</li> <li>• APN AMBR downlink values from 1 kbps to 8640 kbps</li> </ul>
<i>ambr_ul_ext</i>	<ul style="list-style-type: none"> <li>• Extended APN AMBR uplink</li> <li>• APN AMBR uplink values from 8700 kbps to 256 Mbps</li> </ul>
<i>ambr_dl_ext</i>	<ul style="list-style-type: none"> <li>• Extended APN AMBR downlink</li> <li>• APN AMBR downlink values from 8700 kbps to 256 Mbps</li> </ul>
<i>ambr_ul_ext2</i>	<ul style="list-style-type: none"> <li>• Second extended APN AMBR uplink</li> <li>• APN AMBR uplink values from 256 Mbps to 65280 Mbps</li> </ul>
<i>ambr_dl_ext2</i>	<ul style="list-style-type: none"> <li>• Second extended APN AMBR downlink</li> <li>• APN AMBR downlink values from 256 Mbps to 65280 Mbps</li> </ul>

## 8.923.2 Field Documentation

8.923.2.1 `uint8_t unpack_qos_SLQSQoSwiReadApnExtraParams_t::ambr_dl`

8.923.2.2 `uint8_t unpack_qos_SLQSQoSwiReadApnExtraParams_t::ambr_dl_ext`

8.923.2.3 `uint8_t unpack_qos_SLQSQoSwiReadApnExtraParams_t::ambr_dl_ext2`

8.923.2.4 `uint8_t unpack_qos_SLQSQoSwiReadApnExtraParams_t::ambr_ul`

8.923.2.5 `uint8_t unpack_qos_SLQSQoSwiReadApnExtraParams_t::ambr_ul_ext`

8.923.2.6 `uint8_t unpack_qos_SLQSQoSwiReadApnExtraParams_t::ambr_ul_ext2`

8.923.2.7 `uint32_t unpack_qos_SLQSQoSwiReadApnExtraParams_t::apnId`

## 8.924 unpack\_qos\_SLQSQoSwiReadDataStats\_t Struct Reference

### Data Fields

- `uint32_t apnId`
- `uint32_t total_tx_pkt`
- `uint32_t total_tx_pkt_drp`
- `uint32_t total_rx_pkt`
- `uint64_t total_tx_bytes`
- `uint64_t total_tx_bytes_drp`
- `uint64_t total_rx_bytes`
- `uint32_t numQoSFlow`
- `unpack_QoSFlowStat_t qosFlow [10]`

### 8.924.1 Detailed Description

Structure that contains APN data statistics

Parameters

<i>apnId</i>	<ul style="list-style-type: none"> <li>• APN id</li> <li>• ID identifying the connected APN that the client would like to query the data statistic for</li> </ul>
<i>total_tx_pkt</i>	<ul style="list-style-type: none"> <li>• sum of all packets sent</li> </ul>
<i>total_tx_pkt_drp</i>	<ul style="list-style-type: none"> <li>• sum of all(TX) packets dropped</li> </ul>
<i>total_rx_pkt</i>	<ul style="list-style-type: none"> <li>• sum of all packets received</li> </ul>
<i>total_tx_bytes</i>	<ul style="list-style-type: none"> <li>• sum of all bytes sent</li> </ul>
<i>total_tx_bytes_drp</i>	<ul style="list-style-type: none"> <li>• sum of all(TX) bytes dropped</li> </ul>
<i>total_rx_bytes</i>	<ul style="list-style-type: none"> <li>• number of received bytes for the QoS flow ID</li> </ul>
<i>numQosFlow</i>	<ul style="list-style-type: none"> <li>• pointer to number of QoS flow Stat</li> </ul>
<i>qosFlow[LIBPACK_MAX_QOS_FLOW_PER_APN_STATS]</i>	<ul style="list-style-type: none"> <li>• Data statistic per QoS flow</li> <li>• See <a href="#">unpack_QosFlowStat_t</a> for more information</li> <li>• See <a href="#">LIBPACK_MAX_QOS_FLOW_PER_APN_STATS</a> for more information</li> </ul>

### 8.924.2 Field Documentation

8.924.2.1 `uint32_t unpack_qos_SLQSQosSwiReadDataStats_t::apnId`

8.924.2.2 `uint32_t unpack_qos_SLQSQosSwiReadDataStats_t::numQosFlow`

8.924.2.3 `unpack_QosFlowStat_t unpack_qos_SLQSQosSwiReadDataStats_t::qosFlow[10]`

8.924.2.4 `uint64_t unpack_qos_SLQSQosSwiReadDataStats_t::total_rx_bytes`

8.924.2.5 `uint32_t unpack_qos_SLQSQosSwiReadDataStats_t::total_rx_pkt`

8.924.2.6 `uint64_t unpack_qos_SLQSQosSwiReadDataStats_t::total_tx_bytes`

8.924.2.7 uint64\_t unpack\_qos\_SLQSQosSwiReadDataStats\_t::total\_tx\_bytes\_drp

8.924.2.8 uint32\_t unpack\_qos\_SLQSQosSwiReadDataStats\_t::total\_tx\_pkt

8.924.2.9 uint32\_t unpack\_qos\_SLQSQosSwiReadDataStats\_t::total\_tx\_pkt\_drp

## 8.925 unpack\_qos\_SLQSSetQosEventCallback\_ind\_t Struct Reference

### Data Fields

- uint8\_t [NumFlows](#)
- [unpack\\_qos\\_QosFlowInfo\\_t](#) [QosFlowInfo](#) [8]

### 8.925.1 Detailed Description

Structure with QoS event details

#### Parameters

<i>NumFlows</i>	<ul style="list-style-type: none"><li>• Number of QoS flows available</li></ul>
<i><a href="#">QosFlowInfo</a></i>	<ul style="list-style-type: none"><li>• The Qos flow details, please check <a href="#">unpack_qos_QosFlowInfo_t</a> for more information</li><li>• See <a href="#">LIBPACK_MAX_QOS_FLOWS</a> for more information</li></ul>

### 8.925.2 Field Documentation

8.925.2.1 uint8\_t unpack\_qos\_SLQSSetQosEventCallback\_ind\_t::NumFlows

8.925.2.2 [unpack\\_qos\\_QosFlowInfo\\_t](#) unpack\_qos\_SLQSSetQosEventCallback\_ind\_t::QosFlowInfo[8]

## 8.926 unpack\_qos\_SLQSSetQosNWStatusCallback\_ind\_t Struct Reference

### Data Fields

- uint8\_t [status](#)

### 8.926.1 Detailed Description

Structure with network's QoS status

#### Parameters

<i>status</i>	Network QoS support status <ul style="list-style-type: none"><li>• 0x00 – Current network does not support QoS</li><li>• 0x01 – Current network supports QoS</li></ul>
---------------	--

## Note

- Technology Supported: CDMA

## 8.926.2 Field Documentation

8.926.2.1 `uint8_t unpack_qos_SLQSSetQosNWStatusCallback_ind_t::status`

## 8.927 `unpack_qos_SLQSSetQosPriEventCallback_ind_t` Struct Reference

### Data Fields

- `uint16_t event`

### 8.927.1 Detailed Description

Structure with QoS primary flow events

#### Parameters

<i>event</i>	Event which causes this indication: <ul style="list-style-type: none"><li>• 0x0001 – Primary flow QoS modify operation success</li><li>• 0x0002 – Primary flow QoS modify operation failure</li></ul>
--------------	---

## 8.927.2 Field Documentation

8.927.2.1 `uint16_t unpack_qos_SLQSSetQosPriEventCallback_ind_t::event`

## 8.928 `unpack_qos_SLQSSetQosStatusCallback_ind_t` Struct Reference

### Data Fields

- `uint32_t id`
- `uint8_t status`
- `uint8_t event`
- `uint8_t reason`

### 8.928.1 Detailed Description

Structure with QoS status indication details

## Parameters

<i>id</i>	<ul style="list-style-type: none"> <li>• Index identifying the QoS flow whose status is being reported</li> </ul>
<i>status</i>	<p>Current QoS flow status:</p> <ul style="list-style-type: none"> <li>• 0x01 – QMI_QOS_STATUS_ACTIVATED</li> <li>• 0x02 – QMI_QOS_STATUS_SUSPENDED</li> <li>• 0x03 – QMI_QOS_STATUS_GONE</li> </ul>
<i>event</i>	<ul style="list-style-type: none"> <li>• 0x01 – QMI_QOS_ACTIVATED_EV</li> <li>• 0x02 – QMI_QOS_SUSPENDED_EV</li> <li>• 0x03 – QMI_QOS_GONE_EV</li> <li>• 0x04 – QMI_QOS_MODIFY_ACCEPTED_EV</li> <li>• 0x05 – QMI_QOS_MODIFY_REJECTED_EV</li> <li>• 0x06 – QMI_QOS_INFO_CODE_UPDATED_EV</li> </ul>
<i>reason</i>	<ul style="list-style-type: none"> <li>• 0x01 - QMI_QOS_INVALID_PARAMS</li> <li>• 0x02 - QMI_QOS_INTERNAL_CALL_ENDED</li> <li>• 0x03 - QMI_QOS_INTERNAL_ERROR</li> <li>• 0x04 - QMI_QOS_INSUFFICIENT_LOCAL_Resources</li> <li>• 0x05 - QMI_QOS_TIMED_OUT_OPERATION</li> <li>• 0x06 - QMI_QOS_INTERNAL_UNKNOWN_CAUSE_CODE</li> <li>• 0x07 - QMI_QOS_INTERNAL_MODIFY_IN_PROGRESS</li> <li>• 0x08 - QMI_QOS_NOT_SUPPORTED</li> <li>• 0x09 - QMI_QOS_NOT_AVAILABLE</li> <li>• 0x0A - QMI_QOS_NOT_GUARANTEED</li> <li>• 0x0B - QMI_QOS_INSUFFICIENT_NETWORK_RESOURCES</li> <li>• 0x0C - QMI_QOS_AWARE_SYSTEM</li> <li>• 0x0D - QMI_QOS_UNAWARE_SYSTEM</li> <li>• 0x0E - QOS_REJECTED_OPERATION</li> <li>• 0x0F - QMI_QOS_WILL_GRANT_WHEN_QOS_RESUMED</li> <li>• 0x10 - QMI_QOS_NETWORK_CALL_ENDED</li> <li>• 0x11 - QMI_QOS_NETWORK_SERVICE_NOT_AVAILABLE</li> <li>• 0x12 - QMI_QOS_NETWORK_L2_LINK_RELEASED</li> <li>• 0x13 - QMI_QOS_NETWORK_L2_LINK_REESTAB_REJ</li> <li>• 0x14 - QMI_QOS_NETWORK_L2_LINK_REESTAB_IND</li> <li>• 0x15 - QMI_QOS_NETWORK_UNKNOWN_CAUSE_CODE</li> </ul>
Generated on Tue Jul 12 2016 10:59:40 for QMI_CDS by Doxygen	

## 8.928.2 Field Documentation

8.928.2.1 `uint8_t unpack_qos_SLQSSetQosStatusCallback_ind_t::event`

8.928.2.2 `uint32_t unpack_qos_SLQSSetQosStatusCallback_ind_t::id`

8.928.2.3 `uint8_t unpack_qos_SLQSSetQosStatusCallback_ind_t::reason`

8.928.2.4 `uint8_t unpack_qos_SLQSSetQosStatusCallback_ind_t::status`

## 8.929 `unpack_qos_swiQosFilter_t` Struct Reference

### Data Fields

- `uint8_t index`
- `uint8_t version`
- `uint8_t is_IPv4SrcAddr_Available`
- `unpack_qos_IPv4Addr_t IPv4SrcAddr`
- `uint8_t is_IPv4DstAddr_Available`
- `unpack_qos_IPv4Addr_t IPv4DstAddr`
- `uint8_t is_NxtHdrProto_Available`
- `uint8_t NxtHdrProto`
- `uint8_t is_IPv4Tos_Available`
- `unpack_qos_Tos_t IPv4Tos`
- `uint8_t is_IPv6SrcAddr_Available`
- `unpack_qos_IPv6Addr_t IPv6SrcAddr`
- `uint8_t is_IPv6DstAddr_Available`
- `unpack_qos_IPv6Addr_t IPv6DstAddr`
- `uint8_t is_IPv6TrafCls_Available`
- `unpack_qos_IPv6TrafCls_t IPv6TrafCls`
- `uint8_t is_IPv6Label_Available`
- `uint32_t IPv6Label`
- `uint8_t is_TCPSrcPort_Available`
- `unpack_qos_Port_t TCPSrcPort`
- `uint8_t is_TCPDstPort_Available`
- `unpack_qos_Port_t TCPDstPort`
- `uint8_t is_UDPSrcPort_Available`
- `unpack_qos_Port_t UDPSrcPort`
- `uint8_t is_UDPDstPort_Available`
- `unpack_qos_Port_t UDPDstPort`
- `uint8_t is_EspSpi_Available`
- `uint32_t EspSpi`
- `uint8_t is_Precedence_Available`
- `uint16_t Precedence`
- `uint8_t is_Id_Available`
- `uint16_t Id`
- `uint8_t is_TranSrcPort_Available`
- `unpack_qos_Port_t TranSrcPort`
- `uint8_t is_TranDstPort_Available`
- `unpack_qos_Port_t TranDstPort`

### 8.929.1 Detailed Description

This structure contains the QoS Filter Request.

Please check `is_<Param_Name>_Available` field for presence of optional parameters



## Parameters

<i>index</i>	Mandatory parameter IP filter index Integer that uniquely identifies each filter instance This TLV must be present in the request
<i>version</i>	Mandatory parameter IP filter version Identifies whether the filter is associated with IPv4 or IPv6; value specified also implies that only TLVs defined for that IP version, i.e., TLVs with IPv4 or IPv6 in the name, can be specified <ul style="list-style-type: none"> <li>• 0x04 – IPv4</li> <li>• 0x06 – Ipv6</li> </ul>
<i>IPv4SrcAddr</i>	IPv4 filter soruce address See <a href="#">unpack_qos_IPv4Addr_t</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>IPv4DstAddr</i>	IPv4 filter destination address See <a href="#">unpack_qos_IPv4Addr_t</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>NxtHdrProto</i>	IP filter next header protocol This TLV must be present if any non-IP filter TLV(s) are provided If this field is specified, only IP packets belonging to specified higher layer protocol are considered when filtering The following protocols may be specified: <ul style="list-style-type: none"> <li>• 0x01 = ICMP</li> <li>• 0x06 = TCP</li> <li>• 0x11 = UDP</li> <li>• 0x32 = ESP Note: The next header protocol field will be set to 0xFD (TCP &amp; UDP) if a TFT is received specifying a source or destination port number, but IP next header type is not specified.</li> </ul>
<i>IPv4Tos</i>	IPv4 filter type of service See <a href="#">unpack_qos_Tos_t</a> for more information
<i>IPv6SrcAddr</i>	IPv6 filter soruce address See <a href="#">unpack_qos_IPv6Addr_t</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>IPv6DstAddr</i>	IPv6 filter destination address See <a href="#">unpack_qos_IPv6Addr_t</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>IPv6TrafCls</i>	IPv6 filter traffic class See <a href="#">unpack_qos_IPv6TrafCls_t</a> for more information
<i>IPv6Label</i>	IPv6 flow label Packet matches the IPv6 flow label filter if: ( *pIPv6Label == flow label in the IPv6 header) <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>
<i>TCPSrcPort</i>	TCP filter source port filter See <a href="#">unpack_qos_Port_t</a> for more information <ul style="list-style-type: none"> <li>• Implemented only for unsolicited indication</li> </ul>

<i>TCPDstPort</i>	TCP filter destination port filter See <a href="#">unpack_qos_Port_t</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>UDPSrcPort</i>	UDP filter source port filter See <a href="#">unpack_qos_Port_t</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>UDPDstPort</i>	UDP filter destination port filter See <a href="#">unpack_qos_Port_t</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>EspSpi</i>	ESP filter security policy index Security policy index to uniquely identify each IP flow for filtering encrypted packets for encapsulating security payload <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>Precedence</i>	Filter Precedence Specifies the order in which filters are applied; lower numerical value has higher precedence Note: This TLV only applies to network-initiated QoS; QoS requests containing this TLV from control points will be ignored
<i>Id</i>	Filter ID Unique identifier for each filter; filter ID is assigned by the modem Note: This TLV only applies to network-initiated QoS; QoS requests containing this TLV from control points will be ignored
<i>TranSrcPort</i>	Transport protocol filter source port See <a href="#">unpack_qos_Port_t</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>
<i>UDPDstPort</i>	Transport protocol filter destination port See <a href="#">unpack_qos_Port_t</a> for more information <ul style="list-style-type: none"> <li>Implemented only for unsolicited indication</li> </ul>

## 8.929.2 Field Documentation

8.929.2.1 `uint32_t unpack_qos_swiQosFilter_t::EspSpi`

8.929.2.2 `uint16_t unpack_qos_swiQosFilter_t::Id`

8.929.2.3 `uint8_t unpack_qos_swiQosFilter_t::index`

8.929.2.4 `unpack_qos_IPv4Addr_t unpack_qos_swiQosFilter_t::IPv4DstAddr`

8.929.2.5 `unpack_qos_IPv4Addr_t unpack_qos_swiQosFilter_t::IPv4SrcAddr`

8.929.2.6 `unpack_qos_Tos_t unpack_qos_swiQosFilter_t::IPv4Tos`

8.929.2.7 `unpack_qos_IPv6Addr_t unpack_qos_swiQosFilter_t::IPv6DstAddr`

8.929.2.8 `uint32_t unpack_qos_swiQosFilter_t::IPv6Label`

8.929.2.9 `unpack_qos_IPv6Addr_t unpack_qos_swiQosFilter_t::IPv6SrcAddr`

8.929.2.10 `unpack_qos_IPv6TrafCls_t unpack_qos_swiQosFilter_t::IPv6TrafCls`

8.929.2.11 `uint8_t unpack_qos_swiQosFilter_t::is_EspSpi_Available`

8.929.2.12 `uint8_t unpack_qos_swiQosFilter_t::is_Id_Available`

- 8.929.2.13 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_IPv4DstAddr\_Available
- 8.929.2.14 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_IPv4SrcAddr\_Available
- 8.929.2.15 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_IPv4Tos\_Available
- 8.929.2.16 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_IPv6DstAddr\_Available
- 8.929.2.17 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_IPv6Label\_Available
- 8.929.2.18 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_IPv6SrcAddr\_Available
- 8.929.2.19 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_IPv6TrafCls\_Available
- 8.929.2.20 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_NxtHdrProto\_Available
- 8.929.2.21 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_Precedence\_Available
- 8.929.2.22 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_TCPDstPort\_Available
- 8.929.2.23 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_TCPSrcPort\_Available
- 8.929.2.24 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_TranDstPort\_Available
- 8.929.2.25 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_TranSrcPort\_Available
- 8.929.2.26 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_UDPDstPort\_Available
- 8.929.2.27 uint8\_t unpack\_qos\_swiQosFilter\_t::is\_UDPSrcPort\_Available
- 8.929.2.28 uint8\_t unpack\_qos\_swiQosFilter\_t::NxtHdrProto
- 8.929.2.29 uint16\_t unpack\_qos\_swiQosFilter\_t::Precedence
- 8.929.2.30 unpack\_qos\_Port\_t unpack\_qos\_swiQosFilter\_t::TCPDstPort
- 8.929.2.31 unpack\_qos\_Port\_t unpack\_qos\_swiQosFilter\_t::TCPSrcPort
- 8.929.2.32 unpack\_qos\_Port\_t unpack\_qos\_swiQosFilter\_t::TranDstPort
- 8.929.2.33 unpack\_qos\_Port\_t unpack\_qos\_swiQosFilter\_t::TranSrcPort
- 8.929.2.34 unpack\_qos\_Port\_t unpack\_qos\_swiQosFilter\_t::UDPDstPort
- 8.929.2.35 unpack\_qos\_Port\_t unpack\_qos\_swiQosFilter\_t::UDPSrcPort
- 8.929.2.36 uint8\_t unpack\_qos\_swiQosFilter\_t::version

## 8.930 unpack\_qos\_swiQosFlow\_t Struct Reference

### Data Fields

- [uint8\\_t index](#)
- [uint8\\_t is\\_ProfileId3GPP2\\_Available](#)
- [uint16\\_t ProfileId3GPP2](#)
- [uint8\\_t is\\_val\\_3GPP2Pri\\_Available](#)

- uint8\_t val\_3GPP2Pri
- uint8\_t is\_TrafficClass\_Available
- uint8\_t TrafficClass
- uint8\_t is\_DataRate\_Available
- unpack\_qos\_dataRate\_t DataRate
- uint8\_t is\_TokenBucket\_Available
- unpack\_qos\_tokenBucket\_t TokenBucket
- uint8\_t is\_Latency\_Available
- uint32\_t Latency
- uint8\_t is\_Jitter\_Available
- uint32\_t Jitter
- uint8\_t is\_PktErrRate\_Available
- unpack\_qos\_pktErrRate\_t PktErrRate
- uint8\_t is\_MinPolicedPktSz\_Available
- uint32\_t MinPolicedPktSz
- uint8\_t is\_MaxAllowedPktSz\_Available
- uint32\_t MaxAllowedPktSz
- uint8\_t is\_val\_3GPPResResidualBER\_Available
- uint16\_t val\_3GPPResResidualBER
- uint8\_t is\_val\_3GPPTraHdlPri\_Available
- uint8\_t val\_3GPPTraHdlPri
- uint8\_t is\_val\_3GPPImCn\_Available
- uint8\_t val\_3GPPImCn
- uint8\_t is\_val\_3GPPSigInd\_Available
- uint8\_t val\_3GPPSigInd
- uint8\_t is\_LteQci\_Available
- uint8\_t LteQci

### 8.930.1 Detailed Description

This structure contains the QoS Flow Request.

Please check is\_<Param\_Name>\_Available field for presence of optional parameters

#### Parameters

<i>index</i>	<ul style="list-style-type: none"> <li>• Mandatory parameter</li> <li>• IP flow index</li> <li>• Integer that uniquely identifies each flow instance</li> <li>• Unique index must be assigned by the control point to every flow_spec instance</li> </ul>
<i>ProfileId3GPP2</i>	<ul style="list-style-type: none"> <li>• IP flow 3GPP2 profile ID</li> <li>• A profile ID is shorthand for a defined set of QoS flow parameters specified by the network; to be present while requesting QoS for a CDMA device</li> </ul>

<i>val_3GPP2Pri</i>	<ul style="list-style-type: none"> <li>• IP flow 3GPP2 flow priority</li> <li>• Flow priority used by the network in case of contention between flows with same QoS; this parameter applies for CDMA devices</li> </ul>
<i>TrafficClass</i>	<ul style="list-style-type: none"> <li>• IP flow traffic class</li> <li>• Integer that designates the requested traffic class:</li> <li>• 0 – Conversational</li> <li>• 1 – Streaming</li> <li>• 2 – Interactive</li> <li>• 3 – Background</li> </ul>
<i>DataRate</i>	<ul style="list-style-type: none"> <li>• IP flow data rate min max</li> <li>• See <a href="#">unpack_qos_dataRate_t</a> for more information</li> </ul>
<i>TokenBucket</i>	<ul style="list-style-type: none"> <li>• IP flow data rate token bucket</li> <li>• See <a href="#">unpack_qos_tokenBucket_t</a> for more information</li> </ul>
<i>Latency</i>	<ul style="list-style-type: none"> <li>• IP flow latency</li> <li>• Maximum delay (in milliseconds) that can be tolerated by an IP packet during transfer through the wireless link</li> </ul>
<i>Jitter</i>	<ul style="list-style-type: none"> <li>• IP flow jitter</li> <li>• Difference between the maximum and minimum latency (in milliseconds) that can be tolerated by an IP packet during the transfer through the wireless link</li> </ul>
<i>PktErrRate</i>	<ul style="list-style-type: none"> <li>• IP flow packet error rate</li> <li>• See <a href="#">unpack_qos_pktErrRate_t</a> for more information</li> </ul>
<i>MinPolicedPktSz</i>	<ul style="list-style-type: none"> <li>• IP flow minimum policed packet size</li> <li>• Integer that defines the minimum packet size (in bytes) that will be policed for QoS guarantees; any IP packets that are smaller than the minimum specified policed size may not receive requested QoS</li> </ul>

<i>MaxAllowedPktSz</i>	<ul style="list-style-type: none"> <li>• IP flow maximum allowed packet size</li> <li>• Integer that defines the maximum packet size (in bytes) allowed in the IP flow; any IP packets greater in size than the maximum allowed packet size are not queued for transmission</li> </ul>
<i>val_3GPPResResidualBER</i>	<ul style="list-style-type: none"> <li>• IP flow 3GPP residual bit error rate</li> <li>• residual_bit_error_rate</li> <li>• 0 = <math>5 \times 10^{-2}</math> residual BER</li> <li>• 1 = <math>1 \times 10^{-2}</math> residual BER</li> <li>• 2 = <math>5 \times 10^{-3}</math> residual BER</li> <li>• 3 = <math>4 \times 10^{-3}</math> residual BER</li> <li>• 4 = <math>1 \times 10^{-3}</math> residual BER</li> <li>• 5 = <math>1 \times 10^{-4}</math> residual BER</li> <li>• 6 = <math>1 \times 10^{-5}</math> residual BER</li> <li>• 7 = <math>1 \times 10^{-6}</math> residual BER</li> <li>• 8 = <math>6 \times 10^{-8}</math> residual BER</li> <li>• Integer that indicates the undetected BER for each IP flow in the delivered packets; Applies only to 3GPP networks</li> </ul>
<i>val_3GPPTraHdIPri</i>	<ul style="list-style-type: none"> <li>• 3GPP traffic handling priority</li> <li>• 0 – Relative traffic handling priority 1</li> <li>• 1 – Relative traffic handling priority 2</li> <li>• 2 – Relative traffic handling priority 3</li> <li>• Defines the relative priority of the flow; applies only to 3GPP networks</li> </ul>
<i>val_3GPPImCn</i>	<ul style="list-style-type: none"> <li>• IP flow 3GPP IM CN flag</li> <li>• IM CN subsystem signaling flag:</li> <li>• 0x00 – FALSE</li> <li>• 0x01 – TRUE</li> <li>• This parameter applies only to 3GPP networks</li> </ul>

<i>val_3GPPSigInd</i>	<ul style="list-style-type: none"> <li>• IP flow 3GPP signaling indication</li> <li>• 0x00 – FALSE</li> <li>• 0x01 – TRUE</li> <li>• This parameter applies only to 3GPP networks</li> </ul>
<i>LteQci</i>	<ul style="list-style-type: none"> <li>• LTE QoS Class Identifier</li> <li>• QoS Class Identifier(QCI) is a required parameter to request QoS in LTE</li> <li>• QCI values: <ul style="list-style-type: none"> <li>– QCI value 0 requests the network to assign the appropriate QCI value</li> <li>– QCI values 1-4 are associated with guaranteed bitrates</li> <li>– QCI values 5-9 are associated with nonguaranteed bitrates, so the values specified as guaranteed and maximum bitrates are ignored</li> </ul> </li> </ul>

## 8.930.2 Field Documentation

8.930.2.1 `unpack_qos_dataRate_t` `unpack_qos_swiQosFlow_t::DataRate`

8.930.2.2 `uint8_t` `unpack_qos_swiQosFlow_t::index`

8.930.2.3 `uint8_t` `unpack_qos_swiQosFlow_t::is_DataRate_Available`

8.930.2.4 `uint8_t` `unpack_qos_swiQosFlow_t::is_Jitter_Available`

8.930.2.5 `uint8_t` `unpack_qos_swiQosFlow_t::is_Latency_Available`

8.930.2.6 `uint8_t` `unpack_qos_swiQosFlow_t::is_LteQci_Available`

8.930.2.7 `uint8_t` `unpack_qos_swiQosFlow_t::is_MaxAllowedPktSz_Available`

8.930.2.8 `uint8_t` `unpack_qos_swiQosFlow_t::is_MinPolicedPktSz_Available`

8.930.2.9 `uint8_t` `unpack_qos_swiQosFlow_t::is_PktErrRate_Available`

8.930.2.10 `uint8_t` `unpack_qos_swiQosFlow_t::is_ProfileId3GPP2_Available`

8.930.2.11 `uint8_t` `unpack_qos_swiQosFlow_t::is_TokenBucket_Available`

8.930.2.12 `uint8_t` `unpack_qos_swiQosFlow_t::is_TrafficClass_Available`

8.930.2.13 `uint8_t` `unpack_qos_swiQosFlow_t::is_val_3GPP2Pri_Available`

8.930.2.14 `uint8_t` `unpack_qos_swiQosFlow_t::is_val_3GPPImCn_Available`

8.930.2.15 `uint8_t` `unpack_qos_swiQosFlow_t::is_val_3GPPResResidualBER_Available`

8.930.2.16 `uint8_t` `unpack_qos_swiQosFlow_t::is_val_3GPPSigInd_Available`

- 8.930.2.17 `uint8_t unpack_qos_swiQosFlow_t::is_val_3GPPTraHdlPri_Available`
- 8.930.2.18 `uint32_t unpack_qos_swiQosFlow_t::Jitter`
- 8.930.2.19 `uint32_t unpack_qos_swiQosFlow_t::Latency`
- 8.930.2.20 `uint8_t unpack_qos_swiQosFlow_t::LteQci`
- 8.930.2.21 `uint32_t unpack_qos_swiQosFlow_t::MaxAllowedPktSz`
- 8.930.2.22 `uint32_t unpack_qos_swiQosFlow_t::MinPolicedPktSz`
- 8.930.2.23 `unpack_qos_pktErrRate_t unpack_qos_swiQosFlow_t::PktErrRate`
- 8.930.2.24 `uint16_t unpack_qos_swiQosFlow_t::ProfileId3GPP2`
- 8.930.2.25 `unpack_qos_tokenBucket_t unpack_qos_swiQosFlow_t::TokenBucket`
- 8.930.2.26 `uint8_t unpack_qos_swiQosFlow_t::TrafficClass`
- 8.930.2.27 `uint8_t unpack_qos_swiQosFlow_t::val_3GPP2Pri`
- 8.930.2.28 `uint8_t unpack_qos_swiQosFlow_t::val_3GPPImCn`
- 8.930.2.29 `uint16_t unpack_qos_swiQosFlow_t::val_3GPPResResidualBER`
- 8.930.2.30 `uint8_t unpack_qos_swiQosFlow_t::val_3GPPSigInd`
- 8.930.2.31 `uint8_t unpack_qos_swiQosFlow_t::val_3GPPTraHdlPri`

## 8.931 `unpack_qos_tokenBucket_t` Struct Reference

### Data Fields

- `uint32_t` [peakRate](#)
- `uint32_t` [tokenRate](#)
- `uint32_t` [bucketSz](#)

### 8.931.1 Detailed Description

This structure contains the TP flow data rate token bucket

#### Parameters

<i>peakRate</i>	Maximum rate at which data can be transmitted when the token bucket is full (bits per second)
<i>tokenRate</i>	Rate at which tokens will be put in the token bucket (bits per second); a token is required to be present in the bucket to send a byte of data
<i>bucketSz</i>	Maximum number of tokens that can be accumulated at any instance (bytes); controls the size of the burst that is allowed at any given time

### 8.931.2 Field Documentation

- 8.931.2.1 `uint32_t unpack_qos_tokenBucket_t::bucketSz`



8.931.2.2 uint32\_t unpack\_qos\_tokenBucket\_t::peakRate

8.931.2.3 uint32\_t unpack\_qos\_tokenBucket\_t::tokenRate

## 8.932 unpack\_qos\_Tos\_t Struct Reference

### Data Fields

- uint8\_t [val](#)
- uint8\_t [mask](#)

### 8.932.1 Detailed Description

This structure contains the IPv4 filter type of service

#### Parameters

<i>val</i>	Type of service value
<i>mask</i>	Packet matches the TOS filter if: (IPv4_filter_tos_val and IPv4_filter_tos_mask) == (TOS value in the IP packet & IPv4_filter_tos_mask) Example: <ul style="list-style-type: none"> <li>• IPv4_filter_tos_val = 00101000</li> <li>• IPv4_filter_tos_mask = 11111100 The filter will compare only the first 6 bits in the IPv4_filter_type_of_service with the first 6 bits in the TOS field of the IP packet. The first 6 bits in the TOS field of the IP packet must be 001010 to match the filter. The last 2 bits can be anything since they are ignored by filtering.</li> </ul>

### 8.932.2 Field Documentation

8.932.2.1 uint8\_t unpack\_qos\_Tos\_t::mask

8.932.2.2 uint8\_t unpack\_qos\_Tos\_t::val

## 8.933 unpack\_QosFlowStat\_t Struct Reference

### Data Fields

- uint32\_t [bearerId](#)
- uint32\_t [tx\\_pkt](#)
- uint32\_t [tx\\_pkt\\_drp](#)
- uint64\_t [tx\\_bytes](#)
- uint64\_t [tx\\_bytes\\_drp](#)

### 8.933.1 Detailed Description

This structure contains the Data statistic per QoS flow

#### Parameters

<i>bearerId</i>	<ul style="list-style-type: none"> <li>• Bearer ID</li> </ul>
<i>tx_pkt</i>	<ul style="list-style-type: none"> <li>• number of sent packets for the QoS flow ID</li> </ul>
<i>tx_pkt_drp</i>	<ul style="list-style-type: none"> <li>• number of dropped(TX) packets for the QoS flow ID</li> </ul>
<i>tx_bytes</i>	<ul style="list-style-type: none"> <li>• number of sent bytes for the QoS flow ID</li> </ul>
<i>tx_bytes_drp</i>	<ul style="list-style-type: none"> <li>• number of dropped(TX) bytes for the QoS flow ID</li> </ul>

### 8.933.2 Field Documentation

8.933.2.1 `uint32_t unpack_QosFlowStat_t::bearerId`

8.933.2.2 `uint64_t unpack_QosFlowStat_t::tx_bytes`

8.933.2.3 `uint64_t unpack_QosFlowStat_t::tx_bytes_drp`

8.933.2.4 `uint32_t unpack_QosFlowStat_t::tx_pkt`

8.933.2.5 `uint32_t unpack_QosFlowStat_t::tx_pkt_drp`

## 8.934 `unpack_sms_SendSMS_t` Struct Reference

### Data Fields

- `uint16_t` [messageID](#)
- `uint32_t` [messageFailureCode](#)

### 8.934.1 Detailed Description

#### Parameters

<i>messageID</i>	<ul style="list-style-type: none"> <li>• WMS message ID</li> </ul>
<i>messageFailure-Code</i>	<ul style="list-style-type: none"> <li>• pointer to message failure code. If cause code is not provided, then value will be 0xF-FFFFFF</li> </ul>

### 8.934.2 Field Documentation

8.934.2.1 `uint32_t unpack_sms_SendSMS_t::messageFailureCode`

8.934.2.2 uint16\_t unpack\_sms\_SendSMS\_t::messageID

## 8.935 unpack\_sms\_SetNewSMSCallback\_ind\_t Struct Reference

### Data Fields

- struct [newMTMessageTlv](#) NewMMTlv
- struct [transferRouteMessageTlv](#) TRMessageTlv
- struct [messageModeTlv](#) MMTlv
- struct [sMSEtwsMessageTlv](#) ETWSTlv
- struct [eTWSPLMNInfoTlv](#) ETWSPLMNTlv
- struct [sMSCAddressTlv](#) SMSCtlv
- struct [sMSONIMSTlv](#) IMSTlv

### 8.935.1 Detailed Description

#### Parameters

<i>NewMMTlv</i>	<ul style="list-style-type: none"> <li>• MT message</li> </ul>
<i>TRMessageTlv</i>	<ul style="list-style-type: none"> <li>• Transfer Route MT Message</li> <li>• See <a href="#">transferRouteMessageTlv</a> for more information</li> </ul>
<i>MMTlv</i>	<ul style="list-style-type: none"> <li>• Message mode</li> <li>• See <a href="#">messageModeTlv</a> for more information</li> </ul>
<i>ETWSTlv</i>	<ul style="list-style-type: none"> <li>• ETWS Message</li> <li>• See <a href="#">sMSEtwsMessageTlv</a> for more information</li> </ul>
<i>ETWSPLMNTlv</i>	<ul style="list-style-type: none"> <li>• ETWS PLMN Information</li> <li>• See <a href="#">eTWSPLMNInfoTlv</a> for more information</li> </ul>
<i>SMSCtlv</i>	<ul style="list-style-type: none"> <li>• SMSC Address</li> <li>• See <a href="#">sMSCAddressTlv</a> for more information</li> </ul>
<i>IMSTlv</i>	<ul style="list-style-type: none"> <li>• SMS on IMS</li> <li>• See <a href="#">sMSONIMSTlv</a> for more information</li> </ul>

### 8.935.2 Field Documentation

- 8.935.2.1 struct `eTWSPLMNInfoTlv` `unpack_sms_SetNewSMSCallback_ind_t::ETWSPLMNTlv`
- 8.935.2.2 struct `sMSEtwsMessageTlv` `unpack_sms_SetNewSMSCallback_ind_t::ETWSTlv`
- 8.935.2.3 struct `sMSOnIMSTlv` `unpack_sms_SetNewSMSCallback_ind_t::IMSTlv`
- 8.935.2.4 struct `messageModeTlv` `unpack_sms_SetNewSMSCallback_ind_t::MMTlv`
- 8.935.2.5 struct `newMTMessageTlv` `unpack_sms_SetNewSMSCallback_ind_t::NewMMTlv`
- 8.935.2.6 struct `sMSCAddressTlv` `unpack_sms_SetNewSMSCallback_ind_t::SMSCSTlv`
- 8.935.2.7 struct `transferRouteMessageTlv` `unpack_sms_SetNewSMSCallback_ind_t::TRMessageTlv`

## 8.936 `unpack_sms_SetNewSMSCallback_t` Struct Reference

## 8.937 `unpack_sms_SLQSDeleteSMS_t` Struct Reference

## 8.938 `unpack_sms_SLQSGetSMS_t` Struct Reference

### Data Fields

- uint32\_t [messageTag](#)
- uint32\_t [messageFormat](#)
- uint32\_t [messageSize](#)
- uint8\_t [message](#) [2048]

### 8.938.1 Detailed Description

#### Parameters

<i>messageTag</i>	<ul style="list-style-type: none"> <li>• Message tag               <ul style="list-style-type: none"> <li>– 0 - Read</li> <li>– 1 - Not read</li> <li>– 2 - Mobile originated and sent</li> <li>– 3 - Mobile originated but not yet sent</li> </ul> </li> </ul>
-------------------	---

<i>messageFormat</i>	<ul style="list-style-type: none"><li>• Message format<ul style="list-style-type: none"><li>– 0 - CDMA (IS-637B)</li><li>– 1 - 5 (Reserved)</li><li>– 6 - GSM/WCDMA PP</li></ul></li></ul>
<i>messageSize</i>	<ul style="list-style-type: none"><li>• Upon input the maximum number of bytes that can be written to the message array.</li></ul>

- Upon successful output the actual number of bytes written to the message array.

#### Parameters

<i>message</i>	<ul style="list-style-type: none"><li>• The message contents array</li></ul>
----------------	--

### 8.938.2 Field Documentation

8.938.2.1 uint8\_t unpack\_sms\_SLQSGetSMS\_t::message[2048]

8.938.2.2 uint32\_t unpack\_sms\_SLQSGetSMS\_t::messageFormat

8.938.2.3 uint32\_t unpack\_sms\_SLQSGetSMS\_t::messageSize

8.938.2.4 uint32\_t unpack\_sms\_SLQSGetSMS\_t::messageTag

## 8.939 unpack\_sms\_SLQSGetSMSList\_t Struct Reference

### Data Fields

- uint32\_t [messageListSize](#)
- [qmiSmsMessageList](#) [messageList](#) [255]

### 8.939.1 Detailed Description

#### Parameters

<i>messageListSize</i>	<ul style="list-style-type: none"><li>• Upon input the maximum number of elements that the message list array can contain.</li><li>• Upon successful output the actual number of elements in the message list array.</li></ul>
<i>messageList</i>	<ul style="list-style-type: none"><li>• Message List</li><li>• See <a href="#">qmiSmsMessageList</a> for more information</li></ul>

## 8.939.2 Field Documentation

8.939.2.1 `qmiSmsMessageList unpack_sms_SLQSGetSMSList_t::messageList[255]`

8.939.2.2 `uint32_t unpack_sms_SLQSGetSMSList_t::messageListSize`

## 8.940 `unpack_sms_SLQSModifySMSStatus_t` Struct Reference

## 8.941 `unpack_sms_SLQSWmsMemoryFullCallBack_ind_t` Struct Reference

### Data Fields

- `uint8_t storageType`
- `uint8_t messageMode`

### 8.941.1 Detailed Description

#### Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>• SMS message storage type <ul style="list-style-type: none"> <li>– 0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>– 1 - NV</li> </ul> </li> </ul>
<i>messageMode</i>	<ul style="list-style-type: none"> <li>• 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>• 0x01 - GW, LTE (if network type is UMTS)</li> </ul>

## 8.941.2 Field Documentation

8.941.2.1 `uint8_t unpack_sms_SLQSWmsMemoryFullCallBack_ind_t::messageMode`

8.941.2.2 `uint8_t unpack_sms_SLQSWmsMemoryFullCallBack_ind_t::storageType`

## 8.942 `unpack_swiloc_SwiLocGetAutoStart_t` Struct Reference

### Data Fields

- `uint8_t function`
- `int function_reported`
- `uint8_t fix_type`
- `int fix_type_reported`
- `uint8_t max_time`
- `int max_time_reported`
- `uint32_t max_dist`
- `int max_dist_reported`
- `uint32_t fix_rate`
- `int fix_rate_reported`

### 8.942.1 Detailed Description

This structure contains SWI LOC Get Auto Start setting

## Parameters

<i>function</i>	<ul style="list-style-type: none"> <li>• Setting to indicate when modem should start an automatic GNSS fix <ul style="list-style-type: none"> <li>– 0 - disabled</li> <li>– 1 - At bootup</li> <li>– 2 - When NMEA port is opened</li> </ul> </li> </ul>
<i>function_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
<i>fix_type</i>	<ul style="list-style-type: none"> <li>• Type of GNSS fix: <ul style="list-style-type: none"> <li>– 1 - Default Engine mode</li> <li>– 2 - MS-Based</li> <li>– 3 - MS-Assisted</li> <li>– 4 - Standalone</li> </ul> </li> </ul>
<i>fix_type_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
<i>max_time</i>	<ul style="list-style-type: none"> <li>• Maximum time allowed for the receiver to get a fix in seconds</li> <li>• Valid range: 1-255</li> </ul>
<i>max_time_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
<i>max_dist</i>	<ul style="list-style-type: none"> <li>• Maximum uncertainty of a fix measured by distance in meters</li> <li>• Valid range: 1 - 4294967280</li> </ul>
<i>max_dist_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
<i>fix_rate</i>	<ul style="list-style-type: none"> <li>• Time between fixes in seconds</li> <li>• Valid range: 1–65535</li> </ul>



<i>fix_rate_ - reported</i>	<ul style="list-style-type: none"> <li>• 0 - not reported by modem</li> <li>• 1 - reported by modem</li> </ul>
---------------------------------	--

## 8.942.2 Field Documentation

8.942.2.1 uint32\_t unpack\_swiloc\_SwiLocGetAutoStart\_t::fix\_rate

8.942.2.2 int unpack\_swiloc\_SwiLocGetAutoStart\_t::fix\_rate\_reported

8.942.2.3 uint8\_t unpack\_swiloc\_SwiLocGetAutoStart\_t::fix\_type

8.942.2.4 int unpack\_swiloc\_SwiLocGetAutoStart\_t::fix\_type\_reported

8.942.2.5 uint8\_t unpack\_swiloc\_SwiLocGetAutoStart\_t::function

8.942.2.6 int unpack\_swiloc\_SwiLocGetAutoStart\_t::function\_reported

8.942.2.7 uint32\_t unpack\_swiloc\_SwiLocGetAutoStart\_t::max\_dist

8.942.2.8 int unpack\_swiloc\_SwiLocGetAutoStart\_t::max\_dist\_reported

8.942.2.9 uint8\_t unpack\_swiloc\_SwiLocGetAutoStart\_t::max\_time

8.942.2.10 int unpack\_swiloc\_SwiLocGetAutoStart\_t::max\_time\_reported

## 8.943 unpack\_swima\_SLQSOMADMAAlertCallback\_ind\_t Struct Reference

### Data Fields

- uint32\_t [eventType](#)
- [unpack\\_omaDmFotaTlv\\_t](#) [SessionInfoFota](#)
- [unpack\\_omaDmConfigTlv\\_t](#) [SessionInfoConfig](#)
- [unpack\\_omaDmNotificationsTlv\\_t](#) [SessionInfoNotification](#)

### 8.943.1 Detailed Description

Structure that contains OMA indication information based on eventType Structures for which the event is not valid will have values set to 0

## Parameters

<i>eventType</i>	<ul style="list-style-type: none"> <li>• 0x00 - SWIOMA-DM FOTA</li> <li>• 0x01 - SWIOMA-DM Config</li> <li>• 0x02 - SWIOMA-DM Notification</li> </ul>
<i>SessionInfo-Fota[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_omaDmFotaTlv_t</a> for more information</li> </ul>
<i>SessionInfo-Config[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_omaDmConfigTlv_t</a> for more information</li> </ul>
<i>SessionInfo-Notification[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_omaDmNotificationsTlv_t</a> for more information</li> </ul>

## 8.943.2 Field Documentation

8.943.2.1 uint32\_t unpack\_swioma\_SLQSOMADMAAlertCallback\_ind\_t::eventType

8.943.2.2 unpack\_omaDmConfigTlv\_t unpack\_swioma\_SLQSOMADMAAlertCallback\_ind\_t::SessionInfoConfig

8.943.2.3 unpack\_omaDmFotaTlv\_t unpack\_swioma\_SLQSOMADMAAlertCallback\_ind\_t::SessionInfoFota

8.943.2.4 unpack\_omaDmNotificationsTlv\_t unpack\_swioma\_SLQSOMADMAAlertCallback\_ind\_t::SessionInfoNotification

## 8.944 unpack\_swioma\_SLQSOMADMGetSessionInfo\_t Struct Reference

## Data Fields

- uint8\_t [Status](#)
- uint16\_t [UpdateCompleteStatus](#)
- uint8\_t [Severity](#)
- uint16\_t [SourceLength](#)
- uint8\_t [Source](#) [255]
- uint16\_t [PkgNameLength](#)
- uint8\_t [PkgName](#) [255]
- uint16\_t [PkgDescLength](#)
- uint8\_t [PkgDescription](#) [255]
- uint16\_t [DateLength](#)
- uint8\_t [Date](#) [255]
- uint16\_t [TimeLength](#)
- uint8\_t [Time](#) [255]
- uint8\_t [SessionType](#)
- uint8\_t [SessionState](#)
- uint16\_t [RetryCount](#)

## 8.944.1 Detailed Description

Structure that contains the session type for OMA get session info unpack command Also used as input parameter to specify the size of variable parameters. (ref. notes)

## Parameters

<i>Status</i>	<ul style="list-style-type: none"> <li>• 1 Byte parameter indicating status <ul style="list-style-type: none"> <li>– 0x01 - No Firmware available</li> <li>– 0x02 - Query Firmware Download</li> <li>– 0x03 - Firmware Downloading</li> <li>– 0x04 - Firmware Downloaded</li> <li>– 0x05 - Query Firmware Update</li> <li>– 0x06 - Firmware Updating</li> <li>– 0x07 - Firmware Updated</li> </ul> </li> </ul>
<i>Update-CompleteStatus</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Update Complete Status <ul style="list-style-type: none"> <li>– See <a href="#">qaGobiApiTableSwiOMADMUpdateCompleteStatus.h</a> Update Complete Status</li> </ul> </li> </ul>
<i>Severity</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating severity <ul style="list-style-type: none"> <li>– 0x01 - Mandatory</li> <li>– 0x02 - Optional</li> </ul> </li> </ul>
<i>SourceLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Vendor Name String in Bytes.</li> </ul>
<i>Source</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Vendor Name in ASCII</li> <li>• See <a href="#">LIBPACK_MAX_SWIOMA_STR_LEN</a> for more information</li> </ul>
<i>PkgNameLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Name String in Bytes.</li> </ul>
<i>PkgName</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Name in ASCII</li> <li>• See <a href="#">LIBPACK_MAX_SWIOMA_STR_LEN</a> for more information</li> </ul>
<i>PkgDescLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Description String in Bytes.</li> </ul>
<i>PkgDescription</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Description in ASCII</li> <li>• See <a href="#">LIBPACK_MAX_SWIOMA_STR_LEN</a> for more information</li> </ul>

<i>DateLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Description String in Bytes.</li> </ul>
<i>Date</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Description in ASCII</li> <li>• See <a href="#">LIBPACK_MAX_SWIOMA_STR_LEN</a> for more information</li> </ul>
<i>TimeLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Time String in Bytes.</li> </ul>
<i>Time</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Time String in ASCII</li> <li>• See <a href="#">LIBPACK_MAX_SWIOMA_STR_LEN</a> for more information</li> </ul>
<i>SessionType</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter reflects the last session started for Sprint <ul style="list-style-type: none"> <li>– 0x00 - No session since boot</li> <li>– 0x01 - Sprint CI-DC Session</li> <li>– 0x02 - Sprint CI-PRL Session</li> <li>– 0x03 - Sprint CI-FUMO Session</li> <li>– 0x04 - Sprint HFA-DC Session</li> <li>– 0x05 - Sprint HFA-PRL Session</li> <li>– 0x06 - Sprint HFA-FUMO Session</li> <li>– 0x07 - Sprint NI Session</li> </ul> </li> </ul>
<i>SessionState</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating session state <ul style="list-style-type: none"> <li>– 0x01 - idle</li> <li>– 0x02 - active</li> <li>– 0x03 - pending</li> </ul> </li> </ul>
<i>RetryCount</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating retries left count <ul style="list-style-type: none"> <li>– valid values 0 to 6</li> </ul> </li> </ul>

## 8.944.2 Field Documentation

8.944.2.1 uint8\_t unpack\_swioma\_SLQSOMADMGetSessionInfo\_t::Date[255]

8.944.2.2 uint16\_t unpack\_swioma\_SLQSOMADMGetSessionInfo\_t::DateLength

8.944.2.3 uint16\_t unpack\_swioma\_SLQSOMADMGetSessionInfo\_t::PkgDescLength

8.944.2.4 uint8\_t unpack\_swioma\_SLQSOMADMGetSessionInfo\_t::PkgDescription[255]

- 8.944.2.5 uint8\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::PkgName[255]
- 8.944.2.6 uint16\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::PkgNameLength
- 8.944.2.7 uint16\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::RetryCount
- 8.944.2.8 uint8\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::SessionState
- 8.944.2.9 uint8\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::SessionType
- 8.944.2.10 uint8\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::Severity
- 8.944.2.11 uint8\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::Source[255]
- 8.944.2.12 uint16\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::SourceLength
- 8.944.2.13 uint8\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::Status
- 8.944.2.14 uint8\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::Time[255]
- 8.944.2.15 uint16\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::TimeLength
- 8.944.2.16 uint16\_t unpack\_swisma\_SLQSOMADMGetSessionInfo\_t::UpdateCompleteStatus

## 8.945 unpack\_swisma\_SLQSOMADMGetSettings\_t Struct Reference

### Data Fields

- uint32\_t [OMADMEEnabled](#)
- uint8\_t [FOTAdownload](#)
- uint8\_t [FOTAUpdate](#)
- uint8\_t [Autosdm](#)
- uint8\_t [FwAutoCheck](#)

### 8.945.1 Detailed Description

Structure containing the OMA DM settings retrieved from the device

#### Parameters

<i>OMADM-Enabled[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional 4 byte parameter indicating OMADM service enabled               <ul style="list-style-type: none"> <li>– 0x00000001 - Client-initiated device configuration</li> <li>– 0x00000002 - Network-initiated device configuration</li> <li>– 0x00000010 - Client-initiated FUMO</li> <li>– 0x00000020 - Network-initiated FUMO</li> </ul> </li> <li>• function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFFFFFFFF in case this parameter is not returned by the modem.</li> </ul>
---------------------------	--

<i>FOTAdownload[OUT]</i>	<ul style="list-style-type: none"> <li>Optional 1 Byte parameter indicating support for FOTA Automatic download <ul style="list-style-type: none"> <li>0x00 - Host permission required before downloading</li> <li>0x01 - Automatically start downloading, no host permission required</li> <li>0x02 - Automatically start downloading, while not roaming</li> <li>0x03 - Automatically reject download</li> <li>0x04 - Automatically reject download with “Enterprise Reject Policy”</li> </ul> </li> <li>function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>
<i>FOTAUpdate[OUT]</i>	<ul style="list-style-type: none"> <li>Optional 1 byte parameter indicating FOTA Automatic update <ul style="list-style-type: none"> <li>0x00 - User permission required before updating firmware</li> <li>0x01 - No user permission required before updating firmware</li> <li>0x02 - User permission required, auto update on power up</li> </ul> </li> <li>function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>
<i>Autosdm[OUT]</i>	<ul style="list-style-type: none"> <li>Optional 1 byte parameter indicating OMA Automatic UI Alert Response <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled Accept</li> <li>0x02 - Enabled Reject</li> </ul> </li> <li>function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>
<i>FwAutoCheck[OUT]</i>	<ul style="list-style-type: none"> <li>Optional 1 byte parameter indicating OMA Automatic Check for Firmware Update on Power-Up Response <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> <li>function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>

## 8.945.2 Field Documentation

8.945.2.1 `uint8_t unpack_swima_SLQSOMADMGetSettings_t::Autosdm`

8.945.2.2 `uint8_t unpack_swima_SLQSOMADMGetSettings_t::FOTAdownload`

8.945.2.3 `uint8_t unpack_swima_SLQSOMADMGetSettings_t::FOTAUpdate`

8.945.2.4 `uint8_t unpack_swima_SLQSOMADMGetSettings_t::FwAutoCheck`

8.945.2.5 `uint32_t unpack_swima_SLQSOMADMGetSettings_t::OMADMEEnabled`

## 8.946 unpack\_swima\_SLQSOMADMStartSession\_t Struct Reference

### Data Fields

- uint32\_t [FwAvailability](#)

### 8.946.1 Detailed Description

Structure that contains the responses for OMA start session command

#### Parameters

<i>pFwAvailability</i> [-OUT]	<ul style="list-style-type: none"> <li>• OMA-DM CHECK FW Available <ul style="list-style-type: none"> <li>– 0x00000001 - FW Available. For CIDC and CIPRL, this value will be returned by the modem. CIDC and CIPRL are asynchronous OMADM sessions.</li> <li>– 0x00000002 - FW Not Available</li> <li>– 0x00000003 - FW Check Timed Out</li> </ul> </li> </ul>
----------------------------------	---

### 8.946.2 Field Documentation

8.946.2.1 uint32\_t unpack\_swima\_SLQSOMADMStartSession\_t::FwAvailability

## 8.947 unpack\_uim\_ChangePin\_t Struct Reference

### Data Fields

- uim\_remainingRetries \* [pRemainingRetries](#)
- uim\_encryptedPIN1 \* [pEncryptedPIN1](#)
- uint32\_t \* [pIndicationToken](#)
- uint16\_t [Tlvresult](#)

### 8.947.1 Detailed Description

This structure contains information of the response parameters associated with a set of PIN related API's.

#### Parameters

<i>pRemainingRetries</i> (optional)	<ul style="list-style-type: none"> <li>• See <a href="#">uim_remainingRetries</a> for more information.</li> </ul>
<i>pEncryptedPIN1</i> (optional)	<ul style="list-style-type: none"> <li>• See <a href="#">uim_encryptedPIN1</a> for more information.</li> </ul>
<i>pIndicationToken</i> (optional)	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result is provided in a subsequent indication.</li> <li>• 0xFFFFFFFF, if unavailable</li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not returned.

### 8.947.2 Field Documentation

8.947.2.1 `uim_encryptedPIN1*` `unpack_uim_ChangePin_t::pEncryptedPIN1`

8.947.2.2 `uint32_t*` `unpack_uim_ChangePin_t::pIndicationToken`

8.947.2.3 `uim_remainingRetries*` `unpack_uim_ChangePin_t::pRemainingRetries`

8.947.2.4 `uint16_t` `unpack_uim_ChangePin_t::Tlvresult`

## 8.948 `unpack_uim_GetCardStatus_t` Struct Reference

### Data Fields

- `uim_cardStatus` \* `pCardStatus`
- `uim_hotSwapStatus` \* `pHotSwapStatus`
- `uint16_t` `Tlvresult`

### 8.948.1 Detailed Description

This structure contains information of the response parameters associated with a Get Card Status API.

#### Parameters

<i>pCard- Status(optional)</i>	<ul style="list-style-type: none"> <li>• See <code>uim_cardStatus</code> for more information.</li> </ul>
<i>pHotSwap- Status(optional)</i>	<ul style="list-style-type: none"> <li>• See <code>uim_hotSwapStatus</code> for more information.</li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not returned.

### 8.948.2 Field Documentation

8.948.2.1 `uim_cardStatus*` `unpack_uim_GetCardStatus_t::pCardStatus`

8.948.2.2 `uim_hotSwapStatus*` `unpack_uim_GetCardStatus_t::pHotSwapStatus`

8.948.2.3 `uint16_t` `unpack_uim_GetCardStatus_t::Tlvresult`

## 8.949 `unpack_uim_ReadTransparent_t` Struct Reference

### Data Fields

- `uim_cardResult` \* `pCardResult`
- `uim_readResult` \* `pReadResult`
- `uint32_t` \* `pIndicationToken`



- uint8\_t \* [pEncryptedData](#)
- uint16\_t [Tlvresult](#)

### 8.949.1 Detailed Description

This structure contains information of the response parameters associated with a Read Transparent API.

#### Parameters

<i>pCardResult</i>	<ul style="list-style-type: none"> <li>• See <a href="#">cardResult</a> for more information.</li> </ul>
<i>pReadResult</i>	<ul style="list-style-type: none"> <li>• See <a href="#">readResult</a> for more information.</li> </ul>
<i>pIndication-Token(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result must be provided in a subsequent indication.</li> </ul>
<i>pEncrypted-Data(optional)</i>	<ul style="list-style-type: none"> <li>• Encrypted Data.</li> <li>• Indicates whether the data from the card passed in read_result is encrypted.</li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not added to the request.

### 8.949.2 Field Documentation

8.949.2.1 uim\_cardResult\* unpack\_uim\_ReadTransparent\_t::pCardResult

8.949.2.2 uint8\_t\* unpack\_uim\_ReadTransparent\_t::pEncryptedData

8.949.2.3 uint32\_t\* unpack\_uim\_ReadTransparent\_t::pIndicationToken

8.949.2.4 uim\_readResult\* unpack\_uim\_ReadTransparent\_t::pReadResult

8.949.2.5 uint16\_t unpack\_uim\_ReadTransparent\_t::Tlvresult

## 8.950 unpack\_uim\_SetPinProtection\_t Struct Reference

### Data Fields

- [uim\\_remainingRetries](#) \* [pRemainingRetries](#)
- [uim\\_encryptedPIN1](#) \* [pEncryptedPIN1](#)
- uint32\_t \* [pIndicationToken](#)
- uint16\_t [Tlvresult](#)

### 8.950.1 Detailed Description

This structure contains information of the response parameters associated with a set of PIN related API's.

## Parameters

<i>pRemainingRetries(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_remainingRetries</a> for more information.</li> </ul>
<i>pEncryptedPIN1(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_encryptedPIN1</a> for more information.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result is provided in a subsequent indication.</li> <li>• 0xFFFFFFFF, if unavailable</li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not returned.

## 8.950.2 Field Documentation

8.950.2.1 [uim\\_encryptedPIN1](#)\* [unpack\\_uim\\_SetPinProtection\\_t::pEncryptedPIN1](#)

8.950.2.2 [uint32\\_t](#)\* [unpack\\_uim\\_SetPinProtection\\_t::pIndicationToken](#)

8.950.2.3 [uim\\_remainingRetries](#)\* [unpack\\_uim\\_SetPinProtection\\_t::pRemainingRetries](#)

8.950.2.4 [uint16\\_t](#) [unpack\\_uim\\_SetPinProtection\\_t::Tlvresult](#)

8.951 [unpack\\_uim\\_SetUimSlotStatusChangeCallback\\_ind\\_t](#) Struct Reference

## Data Fields

- [slots\\_t slotsstatusChange](#)
- [uint8\\_t bNumberOfPhySlots](#)

## 8.951.1 Detailed Description

Structure consist of card status params

## Parameters

<i>slotsstatusChange</i>	<ul style="list-style-type: none"> <li>• See <a href="#">slot_t</a> for more information</li> </ul>
<i>bNumberOfPhySlots</i>	<ul style="list-style-type: none"> <li>• Number of Physical Slot(s)</li> </ul>

## 8.951.2 Field Documentation

8.951.2.1 [uint8\\_t](#) [unpack\\_uim\\_SetUimSlotStatusChangeCallback\\_ind\\_t::bNumberOfPhySlots](#)

8.951.2.2 slots\_t unpack\_uim\_SetUimSlotStatusChangeCallback\_ind\_t::slotsstatusChange

## 8.952 unpack\_uim\_SLQSUIMEventRegister\_t Struct Reference

### Data Fields

- uint32\_t [eventMask](#)

### 8.952.1 Detailed Description

#### Parameters

<i>eventMask</i>	- bit 1 - card status
------------------	-----------------------

### 8.952.2 Field Documentation

8.952.2.1 uint32\_t unpack\_uim\_SLQSUIMEventRegister\_t::eventMask

## 8.953 unpack\_uim\_SLQSUIMGetSlotsStatus\_t Struct Reference

### Data Fields

- uint8\_t \* [pNumberOfPhySlot](#)
- slots\_t \* [pUimSlotsStatus](#)

### 8.953.1 Detailed Description

This structure contains information of the response parameters associated with a Get Slots Status API.

#### Parameters

<i>pNumberOfPhySlot</i>	<ul style="list-style-type: none"><li>• Number of sets of the Slot Status.</li></ul>
<i>pUimSlotsStatus</i>	<ul style="list-style-type: none"><li>• Slots Status See <a href="#">slots_t</a> for more information..</li></ul>

### 8.953.2 Field Documentation

8.953.2.1 uint8\_t\* unpack\_uim\_SLQSUIMGetSlotsStatus\_t::pNumberOfPhySlot

8.953.2.2 slots\_t\* unpack\_uim\_SLQSUIMGetSlotsStatus\_t::pUimSlotsStatus

## 8.954 unpack\_uim\_SLQSUIMSetStatusChangeCallBack\_ind\_t Struct Reference

### Data Fields

- uim\_cardStatus \* [pCardStatus](#)

### 8.954.1 Detailed Description

This structure contains information about Status change callback.

## Parameters

<i>pCardStatus</i>	Card Status <ul style="list-style-type: none"> <li>See <a href="#">uim_cardStatus</a> for more information.</li> </ul>
--------------------	--

## 8.954.2 Field Documentation

8.954.2.1 `uim_cardStatus*` `unpack_uim_SLQSUIMSetStatusChangeCallBack_ind_t::pCardStatus`

## 8.955 unpack\_uim\_UnblockPin\_t Struct Reference

## Data Fields

- `uim_remainingRetries` \* `pRemainingRetries`
- `uim_encryptedPIN1` \* `pEncryptedPIN1`
- `uint32_t` \* `pIndicationToken`
- `uint16_t` `Tlvresult`

## 8.955.1 Detailed Description

This structure contains information of the response parameters associated with a set of PIN related API's.

## Parameters

<i>pRemainingRetries(optional)</i>	<ul style="list-style-type: none"> <li>See <a href="#">uim_remainingRetries</a> for more information.</li> </ul>
<i>pEncryptedPIN1(optional)</i>	<ul style="list-style-type: none"> <li>See <a href="#">uim_encryptedPIN1</a> for more information.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>Response in Indication.</li> <li>When this TLV is present, it indicates that the result is provided in a subsequent indication.</li> <li>0xFFFFFFFF, if unavailable</li> </ul>

## 8.955.2 Field Documentation

8.955.2.1 `uim_encryptedPIN1*` `unpack_uim_UnblockPin_t::pEncryptedPIN1`8.955.2.2 `uint32_t*` `unpack_uim_UnblockPin_t::pIndicationToken`8.955.2.3 `uim_remainingRetries*` `unpack_uim_UnblockPin_t::pRemainingRetries`8.955.2.4 `uint16_t` `unpack_uim_UnblockPin_t::Tlvresult`

## 8.956 unpack\_uim\_VerifyPin\_t Struct Reference

## Data Fields

- [uim\\_remainingRetries](#) \* [pRemainingRetries](#)
- [uim\\_encryptedPIN1](#) \* [pEncryptedPIN1](#)
- [uint32\\_t](#) \* [pIndicationToken](#)
- [uint16\\_t](#) [Tlvresult](#)

### 8.956.1 Detailed Description

This structure contains information of the response parameters associated with a set of PIN related API's.

#### Parameters

<i>pRemainingRetries(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_remainingRetries</a> for more information.</li> </ul>
<i>pEncryptedPIN1(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">uim_encryptedPIN1</a> for more information.</li> </ul>
<i>pIndicationToken(optional)</i>	<ul style="list-style-type: none"> <li>• Response in Indication.</li> <li>• When this TLV is present, it indicates that the result is provided in a subsequent indication.</li> <li>• 0xFFFFFFFF, if unavailable</li> </ul>

#### Note

Using NULL for the pointers would make sure that the parameter is not returned.

### 8.956.2 Field Documentation

8.956.2.1 [uim\\_encryptedPIN1](#)\* [unpack\\_uim\\_VerifyPin\\_t::pEncryptedPIN1](#)

8.956.2.2 [uint32\\_t](#)\* [unpack\\_uim\\_VerifyPin\\_t::pIndicationToken](#)

8.956.2.3 [uim\\_remainingRetries](#)\* [unpack\\_uim\\_VerifyPin\\_t::pRemainingRetries](#)

8.956.2.4 [uint16\\_t](#) [unpack\\_uim\\_VerifyPin\\_t::Tlvresult](#)

## 8.957 [unpack\\_wds\\_GetConnectionRate\\_t](#) Struct Reference

## Data Fields

- [uint32\\_t](#) [currentChannelTXRate](#)
- [uint32\\_t](#) [currentChannelRXRate](#)
- [uint32\\_t](#) [maxChannelTXRate](#)
- [uint32\\_t](#) [maxChannelRXRate](#)

### 8.957.1 Detailed Description

## Parameters

<i>currentChannel-TXRate</i>	Instantaneous channel Tx rate
<i>currentChannel-RXRate</i>	Instantaneous channel Rx rate
<i>maxChannelTX-Rate</i>	Maximum Tx rate
<i>maxChannelRX-Rate</i>	Maximum Rx rate

## 8.957.2 Field Documentation

8.957.2.1 `uint32_t unpack_wds_GetConnectionRate_t::currentChannelRXRate`

8.957.2.2 `uint32_t unpack_wds_GetConnectionRate_t::currentChannelTXRate`

8.957.2.3 `uint32_t unpack_wds_GetConnectionRate_t::maxChannelRXRate`

8.957.2.4 `uint32_t unpack_wds_GetConnectionRate_t::maxChannelTXRate`

## 8.958 unpack\_wds\_GetDefaultProfile\_t Struct Reference

## Data Fields

- `uint32_t pdptype`
- `uint32_t ipaddr`
- `uint32_t pridns`
- `uint32_t secdns`
- `uint16_t ipaddrv6`
- `uint16_t pridnsv6`
- `uint16_t secdnsv6`
- `uint32_t auth`
- `uint8_t namesize`
- `int8_t name` [255]
- `uint8_t apnsize`
- `int8_t apnname` [255]
- `uint8_t usersize`
- `int8_t username` [255]

### 8.958.1 Detailed Description

#### Parameters

<i>pdptype</i>	pdp type
<i>ipaddr</i>	ip address
<i>pridns</i>	primary dns
<i>secdns</i>	secondry dns
<i>ipaddrv6</i>	ip address v6
<i>pridnsv6</i>	primary dns v6
<i>secdnsv6</i>	secondry dns v6
<i>namesize</i>	profile name size
<i>name</i>	profile name
<i>apnsize</i>	apn size
<i>apnname</i>	apn name
<i>usersize</i>	username size
<i>username</i>	username

### 8.958.2 Field Documentation

- 8.958.2.1 `int8_t unpack_wds_GetDefaultProfile_t::apnname[255]`
- 8.958.2.2 `uint8_t unpack_wds_GetDefaultProfile_t::apnsize`
- 8.958.2.3 `uint32_t unpack_wds_GetDefaultProfile_t::auth`
- 8.958.2.4 `uint32_t unpack_wds_GetDefaultProfile_t::ipaddr`
- 8.958.2.5 `uint16_t unpack_wds_GetDefaultProfile_t::ipaddrv6`
- 8.958.2.6 `int8_t unpack_wds_GetDefaultProfile_t::name[255]`
- 8.958.2.7 `uint8_t unpack_wds_GetDefaultProfile_t::namesize`
- 8.958.2.8 `uint32_t unpack_wds_GetDefaultProfile_t::pdptype`
- 8.958.2.9 `uint32_t unpack_wds_GetDefaultProfile_t::pridns`
- 8.958.2.10 `uint16_t unpack_wds_GetDefaultProfile_t::pridnsv6`
- 8.958.2.11 `uint32_t unpack_wds_GetDefaultProfile_t::secdns`
- 8.958.2.12 `uint16_t unpack_wds_GetDefaultProfile_t::secdnsv6`
- 8.958.2.13 `int8_t unpack_wds_GetDefaultProfile_t::username[255]`
- 8.958.2.14 `uint8_t unpack_wds_GetDefaultProfile_t::usersize`

## 8.959 `unpack_wds_GetDefaultProfileNum_t` Struct Reference

#### Data Fields

- `uint8_t` [index](#)



### 8.959.1 Detailed Description

## Parameters

<i>index</i>	profile index
--------------	---------------

## 8.959.2 Field Documentation

8.959.2.1 uint8\_t unpack\_wds\_GetDefaultProfileNum\_t::index

## 8.960 unpack\_wds\_GetDormancyState\_t Struct Reference

### Data Fields

- uint32\_t [dormancyState](#)

### 8.960.1 Detailed Description

## Parameters

<i>dormancyState</i>	dormancy status
----------------------	-----------------

## 8.960.2 Field Documentation

8.960.2.1 uint32\_t unpack\_wds\_GetDormancyState\_t::dormancyState

## 8.961 unpack\_wds\_GetLastMobileIPError\_t Struct Reference

### Data Fields

- uint32\_t [error](#)

### 8.961.1 Detailed Description

## Parameters

<i>error</i>	last mip status 0-success >0- error code
--------------	--

## 8.961.2 Field Documentation

8.961.2.1 uint32\_t unpack\_wds\_GetLastMobileIPError\_t::error

## 8.962 unpack\_wds\_GetMobileIP\_t Struct Reference

### Data Fields

- uint32\_t [mipMode](#)

### 8.962.1 Detailed Description

## Parameters

<i>mipMode</i>	mobile IP mode
----------------	----------------

## 8.962.2 Field Documentation

8.962.2.1 uint32\_t unpack\_wds\_GetMobileIP\_t::mipMode

## 8.963 unpack\_wds\_GetMobileIPProfile\_t Struct Reference

## Data Fields

- uint8\_t [enabled](#)
- uint32\_t [address](#)
- uint32\_t [primaryHA](#)
- uint32\_t [secondaryHA](#)
- uint8\_t [revTunneling](#)
- uint8\_t [naiSize](#)
- int8\_t [NAI](#) [255]
- uint32\_t [HASPI](#)
- uint32\_t [AAASPI](#)
- uint32\_t [HASState](#)
- uint32\_t [AAASState](#)

## 8.963.1 Detailed Description

## Parameters

<i>enabled</i>	mobile ip profile state enabled/disabled
<i>address</i>	mobile ip profile home address
<i>primaryHA</i>	mobile ip profile home agent primary
<i>secondaryHA</i>	mobile ip profile secondary home agent address
<i>revTunneling</i>	mobile ip profile rev tunneling
<i>naiSize</i>	mobile ip profile NAI size
<i>NAI</i>	NAI string in ASCII text.
<i>HASPI</i>	HA security parameter index.
<i>AAASPI</i>	AAA server security parameter index.
<i>HASState</i>	Mobile IP Profile HA Key State
<i>AAASState</i>	Mobile IP Profile AAA Key State

## 8.963.2 Field Documentation

8.963.2.1 uint32\_t unpack\_wds\_GetMobileIPProfile\_t::AAASPI

8.963.2.2 uint32\_t unpack\_wds\_GetMobileIPProfile\_t::AAASState

8.963.2.3 uint32\_t unpack\_wds\_GetMobileIPProfile\_t::address

8.963.2.4 uint8\_t unpack\_wds\_GetMobileIPProfile\_t::enabled

8.963.2.5 uint32\_t unpack\_wds\_GetMobileIPProfile\_t::HASPI

8.963.2.6 uint32\_t unpack\_wds\_GetMobileIPProfile\_t::HASState

8.963.2.7 `int8_t unpack_wds_GetMobileIPProfile_t::NAI[255]`

8.963.2.8 `uint8_t unpack_wds_GetMobileIPProfile_t::naiSize`

8.963.2.9 `uint32_t unpack_wds_GetMobileIPProfile_t::primaryHA`

8.963.2.10 `uint8_t unpack_wds_GetMobileIPProfile_t::revTunneling`

8.963.2.11 `uint32_t unpack_wds_GetMobileIPProfile_t::secondaryHA`

## 8.964 `unpack_wds_GetPacketStatus_t` Struct Reference

### Data Fields

- `uint32_t tXPacketSuccesses`
- `uint32_t rXPacketSuccesses`
- `uint32_t tXPacketErrors`
- `uint32_t rXPacketErrors`
- `uint32_t tXPacketOverflows`
- `uint32_t rXPacketOverflows`
- `uint64_t tXOkBytesCount`
- `uint64_t rXOkBytesCount`
- `uint64_t tXOKBytesLastCall`
- `uint64_t rXOKBytesLastCall`
- `uint32_t tXDroppedCount`
- `uint32_t rXDroppedCount`

### 8.964.1 Detailed Description

#### Parameters

<i>tXPacket-Successes</i>	Tx Packets OK
<i>rXPacket-Successes</i>	Rx Packets OK
<i>tXPacketErrors</i>	Tx Packet Errors
<i>rXPacketErrors</i>	Rx Packet Errors
<i>tXPacket-Overflows</i>	Tx Overflows
<i>rXPacket-Overflows</i>	Rx Overflows
<i>tXOkBytesCount</i>	Tx Bytes OK
<i>rXOkBytesCount</i>	Rx Bytes OK
<i>tXOKBytesLast-Call</i>	Last call Tx Bytes OK
<i>rXOKBytesLast-Call</i>	Last call Rx Bytes OK
<i>tXDroppedCount</i>	Tx Packets Dropped
<i>rXDroppedCount</i>	Rx Packets Dropped

### 8.964.2 Field Documentation

8.964.2.1 `uint32_t unpack_wds_GetPacketStatus_t::rXDroppedCount`

- 8.964.2.2    uint64\_t unpack\_wds\_GetPacketStatus\_t::rXOkBytesCount
- 8.964.2.3    uint64\_t unpack\_wds\_GetPacketStatus\_t::rXOkBytesLastCall
- 8.964.2.4    uint32\_t unpack\_wds\_GetPacketStatus\_t::rXPacketErrors
- 8.964.2.5    uint32\_t unpack\_wds\_GetPacketStatus\_t::rXPacketOverflows
- 8.964.2.6    uint32\_t unpack\_wds\_GetPacketStatus\_t::rXPacketSuccesses
- 8.964.2.7    uint32\_t unpack\_wds\_GetPacketStatus\_t::tXDroppedCount
- 8.964.2.8    uint64\_t unpack\_wds\_GetPacketStatus\_t::tXOkBytesCount
- 8.964.2.9    uint64\_t unpack\_wds\_GetPacketStatus\_t::tXOkBytesLastCall
- 8.964.2.10    uint32\_t unpack\_wds\_GetPacketStatus\_t::tXPacketErrors
- 8.964.2.11    uint32\_t unpack\_wds\_GetPacketStatus\_t::tXPacketOverflows
- 8.964.2.12    uint32\_t unpack\_wds\_GetPacketStatus\_t::tXPacketSuccesses

## 8.965    unpack\_wds\_GetSessionDuration\_t Struct Reference

### Data Fields

- uint64\_t [callDuration](#)

### 8.965.1    Detailed Description

#### Parameters

<i>callDuration</i>	call duration in milliseconds
---------------------	-------------------------------

### 8.965.2    Field Documentation

- 8.965.2.1    uint64\_t unpack\_wds\_GetSessionDuration\_t::callDuration

## 8.966    unpack\_wds\_GetSessionState\_t Struct Reference

### Data Fields

- uint32\_t [connectionStatus](#)

### 8.966.1    Detailed Description

#### Parameters

<i>connection- Status</i>	state of the current packet data session
-------------------------------	--

## 8.966.2 Field Documentation

8.966.2.1 `uint32_t unpack_wds_GetSessionState_t::connectionStatus`

## 8.967 `unpack_wds_RMSetTransferStatistics_t` Struct Reference

## 8.968 `unpack_wds_SetMobileIPProfile_t` Struct Reference

## 8.969 `unpack_wds_SLQSCreateProfile_t` Struct Reference

### Data Fields

- [PackCreateProfileOut](#) \* [pCreateProfileOut](#)
- `uint8_t` \* [pProfileID](#)
- `uint16_t` [Tlvresult](#)

### 8.969.1 Detailed Description

#### Parameters

<i>profile</i>	type
<i>profile</i>	index
<i>extended</i>	error

## 8.969.2 Field Documentation

8.969.2.1 `PackCreateProfileOut*` `unpack_wds_SLQSCreateProfile_t::pCreateProfileOut`

8.969.2.2 `uint8_t*` `unpack_wds_SLQSCreateProfile_t::pProfileID`

8.969.2.3 `uint16_t` `unpack_wds_SLQSCreateProfile_t::Tlvresult`

## 8.970 `unpack_wds_SLQSDeleteProfile_t` Struct Reference

### Data Fields

- `uint16_t` [extendedErrorCode](#)

### 8.970.1 Detailed Description

#### Parameters

<i>extendedError-Code</i>	extended error code
---------------------------	---------------------

## 8.970.2 Field Documentation

8.970.2.1 `uint16_t` `unpack_wds_SLQSDeleteProfile_t::extendedErrorCode`

## 8.971 unpack\_wds\_SLQSGet3GPPConfigItem\_t Struct Reference

### Data Fields

- uint16\_t [profileList](#) [5]
- uint8\_t [defaultPDNEnabled](#)
- uint8\_t [\\_3gppRelease](#)
- uint16\_t [LTEAttachProfileList](#) [24]
- uint16\_t [LTEAttachProfileListLen](#)

### 8.971.1 Detailed Description

#### Parameters

	<i>profileList</i>	Profile List
out	<i>defaultPDN-Enabled</i>	<ul style="list-style-type: none"> <li>• 0 - disabled</li> <li>• 1 - enabled</li> </ul>
out	<i>_3gppRelease</i>	3GPP release <ul style="list-style-type: none"> <li>• 0 - Release_99</li> <li>• 1 - Release_5</li> <li>• 2 - Release_6</li> <li>• 3 - Release_7</li> <li>• 4 - Release_8</li> <li>• 5 - Release_9 (In 9x30 and towerads)</li> <li>• 6 - Release_10 (In 9x30 and towerads)</li> <li>• 7 - Release_11 (In 9x30 and towerads)</li> </ul>
out	<i>LTEAttach-ProfileList</i>	<ul style="list-style-type: none"> <li>• pointer to WORD array indicating LTE Attach Profile List               <ul style="list-style-type: none"> <li>– Optional parameter</li> <li>– possible values: 1-24</li> <li>– This setting is only supported for MC/EM74xx onwards</li> <li>– Please provide attach profiles in order of decreasing priority in this list.</li> </ul> </li> </ul>
in, out	<i>LTEAttach-ProfileListLen</i>	<ul style="list-style-type: none"> <li>• Number of element in pLTEAttachProfileList               <ul style="list-style-type: none"> <li>– valid range: 1-24</li> <li>– This setting is only supported for MC/EM74xx onwards</li> </ul> </li> </ul>

### 8.971.2 Field Documentation

8.971.2.1 `uint8_t unpack_wds_SLQSGet3GPPConfigItem_t::_3gppRelease`

8.971.2.2 `uint8_t unpack_wds_SLQSGet3GPPConfigItem_t::defaultPDNEnabled`

8.971.2.3 `uint16_t unpack_wds_SLQSGet3GPPConfigItem_t::LTEAttachProfileList[24]`

8.971.2.4 `uint16_t unpack_wds_SLQSGet3GPPConfigItem_t::LTEAttachProfileListLen`

8.971.2.5 `uint16_t unpack_wds_SLQSGet3GPPConfigItem_t::profileList[5]`

## 8.972 `unpack_wds_SLQSGetCurrDataSystemStat_t` Struct Reference

### Data Fields

- `uint8_t prefNetwork`
- `uint8_t networkInfoLen`
- `currNetworkInfo currNetworkInfo` [255]

### 8.972.1 Detailed Description

#### Parameters

<i>prefNetwork</i>	preferred network
<i>networkInfoLen</i>	number of set of <code>currNetworkInfo</code> elements
<i>currNetworkInfo</i>	current network infomation.

### 8.972.2 Field Documentation

8.972.2.1 `currNetworkInfo unpack_wds_SLQSGetCurrDataSystemStat_t::currNetworkInfo[255]`

8.972.2.2 `uint8_t unpack_wds_SLQSGetCurrDataSystemStat_t::networkInfoLen`

8.972.2.3 `uint8_t unpack_wds_SLQSGetCurrDataSystemStat_t::prefNetwork`

## 8.973 `unpack_wds_SLQSGetDataBearerTechnology_t` Struct Reference

### Data Fields

- `uint8_t dataBearerMask`
- `qmiWSDDataBearerTechnology curDataBearerTechnology`
- `qmiWSDDataBearerTechnology lastCallDataBearerTechnology`

### 8.973.1 Detailed Description

#### Parameters

<i>dataBearerMask</i>	bit mask indicates bearer info is for current and/or last call
<i>curDataBearer-Technology</i>	current data bearer technology value
<i>lastCallData- Bearer-Technology</i>	last call data bearer technology value



### 8.973.2 Field Documentation

8.973.2.1 qmiWSDDataBearerTechnology unpack\_wds\_SLQSGetDataBearerTechnology\_t::curDataBearerTechnology

8.973.2.2 uint8\_t unpack\_wds\_SLQSGetDataBearerTechnology\_t::dataBearerMask

8.973.2.3 qmiWSDDataBearerTechnology unpack\_wds\_SLQSGetDataBearerTechnology\_t::lastCallDataBearerTechnology

## 8.974 unpack\_wds\_SLQSGetDUNCallInfo\_t Struct Reference

### Data Fields

- [connectionStatus](#) connectionStatus
- uint16\_t [callEndReason](#)
- uint64\_t [txOKBytesCount](#)
- uint64\_t [rxOKBytesCount](#)
- uint8\_t [dormancyStatus](#)
- uint8\_t [dataBearerTech](#)
- [dunchannelRate](#) channelRate
- uint64\_t [lastCallTXOKBytesCnt](#)
- uint64\_t [lastCallRXOKBytesCnt](#)
- uint64\_t [mdmCallDurationActive](#)
- uint8\_t [lastCallDataBearerTech](#)

### 8.974.1 Detailed Description

#### Parameters

<a href="#">connectionStatus</a>	Connection Status
<a href="#">callEndReason</a>	Last Modem Call End Reason
<a href="#">txOKBytesCount</a>	Tx Bytes OK
<a href="#">rxOKBytesCount</a>	Rx Bytes OK
<a href="#">dormancyStatus</a>	Dormancy Status
<a href="#">dataBearerTech</a>	data bearer technology
<a href="#">channelRate</a>	data Channel Rate
<a href="#">lastCallTXOKBytesCnt</a>	Last Call Tx Bytes OK
<a href="#">lastCallRXOKBytesCnt</a>	Last Call Rx Bytes OK
<a href="#">mdmCallDurationActive</a>	Call active duration
<a href="#">lastCallDataBearerTech</a>	Last Call Data Bearer Technology

### 8.974.2 Field Documentation

8.974.2.1 uint16\_t unpack\_wds\_SLQSGetDUNCallInfo\_t::callEndReason

8.974.2.2 dunchannelRate unpack\_wds\_SLQSGetDUNCallInfo\_t::channelRate

8.974.2.3 connectionStatus unpack\_wds\_SLQSGetDUNCallInfo\_t::connectionStatus

- 8.974.2.4 `uint8_t unpack_wds_SLQSGetDUNCallInfo_t::dataBearerTech`
- 8.974.2.5 `uint8_t unpack_wds_SLQSGetDUNCallInfo_t::dormancyStatus`
- 8.974.2.6 `uint8_t unpack_wds_SLQSGetDUNCallInfo_t::lastCallDataBearerTech`
- 8.974.2.7 `uint64_t unpack_wds_SLQSGetDUNCallInfo_t::lastCallRXOKBytesCnt`
- 8.974.2.8 `uint64_t unpack_wds_SLQSGetDUNCallInfo_t::lastCallTXOKBytesCnt`
- 8.974.2.9 `uint64_t unpack_wds_SLQSGetDUNCallInfo_t::mdmCallDurationActive`
- 8.974.2.10 `uint64_t unpack_wds_SLQSGetDUNCallInfo_t::rxOKBytesCount`
- 8.974.2.11 `uint64_t unpack_wds_SLQSGetDUNCallInfo_t::txOKBytesCount`

## 8.975 `unpack_wds_SLQSGetProfileSettings_t` Struct Reference

### Data Fields

- [UnPackGetProfileSettingOut \\* pProfileSettings](#)
- `uint8_t` [ProfileType](#)
- `uint16_t` [Tlvresult](#)

### 8.975.1 Field Documentation

- 8.975.1.1 `UnPackGetProfileSettingOut* unpack_wds_SLQSGetProfileSettings_t::pProfileSettings`
- 8.975.1.2 `uint8_t unpack_wds_SLQSGetProfileSettings_t::ProfileType`
- 8.975.1.3 `uint16_t unpack_wds_SLQSGetProfileSettings_t::Tlvresult`

## 8.976 `unpack_wds_SLQSGetRuntimeSettings_t` Struct Reference

### Data Fields

- `uint32_t` [IPv4](#)
- `uint8_t` [ProfileName](#) [128]
- `uint32_t` [PDPTType](#)
- `uint8_t` [APNName](#) [128]
- `uint32_t` [PrimaryDNSV4](#)
- `uint32_t` [SecondaryDNSV4](#)
- [LibPackUMTSQoS](#) [UMTSGrantedQoS](#)
- `struct` [wds\\_GPRSQoS](#) [GPRSGrantedQoS](#)
- `uint8_t` [Username](#) [128]
- `uint32_t` [Authentication](#)
- `struct` [wds\\_ProfileIdentifier](#) [ProfileID](#)
- `uint32_t` [GWAddressV4](#)
- `uint32_t` [SubnetMaskV4](#)
- `uint8_t` [PCSCFAddrPCO](#)
- `struct`  
[wds\\_PCSCFIPv4ServerAddressList](#) [ServerAddrList](#)
- `struct` [wds\\_PCSCFFQDNAddressList](#) [PCSCFFQDNAddrList](#)

- uint16\_t [PrimaryDNSV6](#) [8]
- uint16\_t [SecondaryDNSV6](#) [8]
- uint32\_t [Mtu](#)
- struct [wds\\_DomainNameList](#) [DomainList](#)
- uint8\_t [IPFamilyPreference](#)
- uint8\_t [IMCNflag](#)
- uint16\_t [Technology](#)
- struct [wds\\_IPV6AddressInfo](#) [IPv6AddrInfo](#)
- struct [wds\\_IPV6GWAddressInfo](#) [IPv6GWAddrInfo](#)

### 8.976.1 Detailed Description

#### Parameters

<i>IPv4</i>	ipv4 address
<i>ProfileName</i>	profile name
<i>PDPTType</i>	PDP type
<i>APNName</i>	APN name
<i>PrimaryDNSV4</i>	
<i>SecondaryDNS-V4</i>	
<i>UMTSGranted-QoS</i>	UMTS Granted QoS
<i>GPRSGranted-QoS</i>	GPRS Granted QoS
<i>Username</i>	
<i>Authentication</i>	
<i>ProfileID</i>	
<i>GWAddressV4</i>	Gateway IPv4
<i>SubnetMaskV4</i>	Subnet mask IPV4
<i>PCSCFAddrPC-O</i>	
<i>PrimaryDNSV6</i>	Primary DNS IPV6
<i>SecondaryDNS-V6</i>	Secondary DNS IPV6
<i>UMTSGranted-QoS</i>	UMTS Granted QoS
<i>SecondaryDNS-V4</i>	
<i>Mtu</i>	Maximum Transfer Unit
<i>DomainList</i>	
<i>IPFamily-Preference</i>	

### 8.976.2 Field Documentation

8.976.2.1 uint8\_t unpack\_wds\_SLQSGetRuntimeSettings\_t::APNName[128]

8.976.2.2 uint32\_t unpack\_wds\_SLQSGetRuntimeSettings\_t::Authentication

8.976.2.3 struct wds\_DomainNameList unpack\_wds\_SLQSGetRuntimeSettings\_t::DomainList

8.976.2.4 struct wds\_GPRSQoS unpack\_wds\_SLQSGetRuntimeSettings\_t::GPRSGrantedQoS

8.976.2.5 uint32\_t unpack\_wds\_SLQSGetRuntimeSettings\_t::GWAddressV4

- 8.976.2.6 `uint8_t unpack_wds_SLQSGetRuntimeSettings_t::IMCNflag`
- 8.976.2.7 `uint8_t unpack_wds_SLQSGetRuntimeSettings_t::IPFamilyPreference`
- 8.976.2.8 `uint32_t unpack_wds_SLQSGetRuntimeSettings_t::IPv4`
- 8.976.2.9 `struct wds_IPV6AddressInfo unpack_wds_SLQSGetRuntimeSettings_t::IPv6AddrInfo`
- 8.976.2.10 `struct wds_IPV6GWAddressInfo unpack_wds_SLQSGetRuntimeSettings_t::IPv6GWAddrInfo`
- 8.976.2.11 `uint32_t unpack_wds_SLQSGetRuntimeSettings_t::Mtu`
- 8.976.2.12 `uint8_t unpack_wds_SLQSGetRuntimeSettings_t::PCSCFAddrPCO`
- 8.976.2.13 `struct wds_PCSCFFQDNAddressList unpack_wds_SLQSGetRuntimeSettings_t::PCSCFFQDNAddrList`
- 8.976.2.14 `uint32_t unpack_wds_SLQSGetRuntimeSettings_t::PDPTType`
- 8.976.2.15 `uint32_t unpack_wds_SLQSGetRuntimeSettings_t::PrimaryDNSV4`
- 8.976.2.16 `uint16_t unpack_wds_SLQSGetRuntimeSettings_t::PrimaryDNSV6[8]`
- 8.976.2.17 `struct wds_ProfileIdentifier unpack_wds_SLQSGetRuntimeSettings_t::ProfileID`
- 8.976.2.18 `uint8_t unpack_wds_SLQSGetRuntimeSettings_t::ProfileName[128]`
- 8.976.2.19 `uint32_t unpack_wds_SLQSGetRuntimeSettings_t::SecondaryDNSV4`
- 8.976.2.20 `uint16_t unpack_wds_SLQSGetRuntimeSettings_t::SecondaryDNSV6[8]`
- 8.976.2.21 `struct wds_PCSCFIPv4ServerAddressList unpack_wds_SLQSGetRuntimeSettings_t::ServerAddrList`
- 8.976.2.22 `uint32_t unpack_wds_SLQSGetRuntimeSettings_t::SubnetMaskV4`
- 8.976.2.23 `uint16_t unpack_wds_SLQSGetRuntimeSettings_t::Technology`
- 8.976.2.24 `LibPackUMTSQoS unpack_wds_SLQSGetRuntimeSettings_t::UMTSGrantedQoS`
- 8.976.2.25 `uint8_t unpack_wds_SLQSGetRuntimeSettings_t::Username[128]`

## 8.977 `unpack_wds_SLQSModifyProfile_t` Struct Reference

### Data Fields

- `uint16_t * pExtErrorCode`

### 8.977.1 Detailed Description

#### Parameters

<i>extended</i>	error
-----------------	-------

### 8.977.2 Field Documentation

8.977.2.1 uint16\_t\* unpack\_wds\_SLQSModifyProfile\_t::pExtErrorCode

## 8.978 unpack\_wds\_SLQSSetIPFamilyPreference\_t Struct Reference

### Data Fields

- uint16\_t [Tlvresult](#)

### 8.978.1 Detailed Description

#### Parameters

<i>Tlvresult</i>	unpack result
------------------	---------------

### 8.978.2 Field Documentation

8.978.2.1 uint16\_t unpack\_wds\_SLQSSetIPFamilyPreference\_t::Tlvresult

## 8.979 unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t Struct Reference

### Data Fields

- uint8\_t [conn\\_status](#)
- uint8\_t [reconfigReqd](#)
- uint16\_t [sessionEndReason](#)
- uint16\_t [verboseSessnEndReasonType](#)
- uint16\_t [verboseSessnEndReason](#)
- uint8\_t [ipFamily](#)
- uint16\_t [techName](#)
- uint8\_t [bearerID](#)

### 8.979.1 Detailed Description

#### Parameters

<i>conn_status</i>	connection status
<i>reconfigReqd</i>	Indicates whether the network interface on the host needs to be reconfigured.
<i>sessionEndReason</i>	Call End Reason
<i>verboseSessnEndReasonType</i>	Verbose call end reason type
<i>verboseSessnEndReason</i>	Reason the call ended (verbose)
<i>ipFamily</i>	IP family of the packet data connection.
<i>techName</i>	Technology name of the packet data connection.
<i>bearerID</i>	<ul style="list-style-type: none"> <li>• bearer ID (3GPP) or RLP ID (3GPP2) of the packet data connection.</li> <li>• Valid Values - 0 to 16</li> <li>• 0xFF - Invalid value.</li> </ul>

## 8.979.2 Field Documentation

- 8.979.2.1 `uint8_t unpack_wds_SLQSSetPacketSrvStatusCallback_t::bearerID`
- 8.979.2.2 `uint8_t unpack_wds_SLQSSetPacketSrvStatusCallback_t::conn_status`
- 8.979.2.3 `uint8_t unpack_wds_SLQSSetPacketSrvStatusCallback_t::ipFamily`
- 8.979.2.4 `uint8_t unpack_wds_SLQSSetPacketSrvStatusCallback_t::reconfigReqd`
- 8.979.2.5 `uint16_t unpack_wds_SLQSSetPacketSrvStatusCallback_t::sessionEndReason`
- 8.979.2.6 `uint16_t unpack_wds_SLQSSetPacketSrvStatusCallback_t::techName`
- 8.979.2.7 `uint16_t unpack_wds_SLQSSetPacketSrvStatusCallback_t::verboseSessnEndReason`
- 8.979.2.8 `uint16_t unpack_wds_SLQSSetPacketSrvStatusCallback_t::verboseSessnEndReasonType`

## 8.980 `unpack_wds_SLQSSetWdsEventCallback_ind_t` Struct Reference

### Data Fields

- `uint8_t xferStatAvail`
- `uint64_t tx_bytes`
- `uint64_t rx_bytes`
- `uint64_t tx_pkts`
- `uint64_t rx_pkts`
- `uint8_t mipstatAvail`
- `uint32_t mipStatus`
- `uint8_t dBTechAvail`
- `uint32_t dBTechnology`
- `uint8_t dormancyStatAvail`
- `uint32_t dormancyStatus`
- `uint8_t currDBTechAvail`
- `uint32_t ratMask`
- `uint32_t soMask`
- `uint8_t dataSysStatAvail`
- `uint8_t prefNetwork`
- `uint8_t netInfoLen`
- `wds_currNetworkInfo currNWInfo` [255]

### 8.980.1 Detailed Description

#### Parameters

<i>xferStatAvail</i>	transfer statistic available
<i>tx_bytes</i>	transmit bytes
<i>rx_bytes</i>	received bytes
<i>tx_pkts</i>	transmit packets
<i>rx_pkts</i>	received packets

<i>mipstatAvail</i>	Mobile IP status available
<i>mipStatus</i>	Mobile IP status
<i>dBTechAvail</i>	Data Bearer technology available
<i>dBTechnology</i>	Data Bearer technology
<i>dormancyStatAvail</i>	Dormancy status available
<i>dormancyStatus</i>	Dormancy status
<i>currDBTechAvail</i>	Current Data Bearer technology available
<i>ratMask</i>	RAT mask to indicate type of technology
<i>soMask</i>	SO mask to indicate the service type
<i>dataSysStatAvail</i>	Data System Status available
<i>prefNetwork</i>	preferred network
<i>currNWInfo</i>	Current Network Info

## 8.980.2 Field Documentation

8.980.2.1 `uint8_t unpack_wds_SLQSSetWdsEventCallback_ind_t::currDBTechAvail`

8.980.2.2 `wds_currNetworkInfo unpack_wds_SLQSSetWdsEventCallback_ind_t::currNWInfo[255]`

8.980.2.3 `uint8_t unpack_wds_SLQSSetWdsEventCallback_ind_t::dataSysStatAvail`

8.980.2.4 `uint8_t unpack_wds_SLQSSetWdsEventCallback_ind_t::dBTechAvail`

8.980.2.5 `uint32_t unpack_wds_SLQSSetWdsEventCallback_ind_t::dBTechnology`

8.980.2.6 `uint8_t unpack_wds_SLQSSetWdsEventCallback_ind_t::dormancyStatAvail`

8.980.2.7 `uint32_t unpack_wds_SLQSSetWdsEventCallback_ind_t::dormancyStatus`

8.980.2.8 `uint8_t unpack_wds_SLQSSetWdsEventCallback_ind_t::mipstatAvail`

8.980.2.9 `uint32_t unpack_wds_SLQSSetWdsEventCallback_ind_t::mipStatus`

8.980.2.10 `uint8_t unpack_wds_SLQSSetWdsEventCallback_ind_t::netInfoLen`

8.980.2.11 `uint8_t unpack_wds_SLQSSetWdsEventCallback_ind_t::prefNetwork`

8.980.2.12 `uint32_t unpack_wds_SLQSSetWdsEventCallback_ind_t::ratMask`

8.980.2.13 `uint64_t unpack_wds_SLQSSetWdsEventCallback_ind_t::rx_bytes`

8.980.2.14 `uint64_t unpack_wds_SLQSSetWdsEventCallback_ind_t::rx_pkts`

8.980.2.15 `uint32_t unpack_wds_SLQSSetWdsEventCallback_ind_t::soMask`

8.980.2.16 `uint64_t unpack_wds_SLQSSetWdsEventCallback_ind_t::tx_bytes`

8.980.2.17 `uint64_t unpack_wds_SLQSSetWdsEventCallback_ind_t::tx_pkts`

8.980.2.18 `uint8_t unpack_wds_SLQSSetWdsEventCallback_ind_t::xferStatAvail`

## 8.981 unpack\_wds\_SLQSSetDHCPv4ClientConfig\_t Struct Reference

## Data Fields

- [wdsDhcpv4HwConfig](#) \* [pHwConfig](#)
- [wdsDhcpv4OptionList](#) \* [pRequestOptionList](#)

### 8.981.1 Detailed Description

#### Parameters

<i>pHwConfig</i>	pointer to HW Config structure
<i>pRequestOptionList</i>	pointer to Option List structure to be sent in DHCP request

### 8.981.2 Field Documentation

8.981.2.1 [wdsDhcpv4HwConfig](#)\* [unpack\\_wds\\_SLQSSGetDHCPv4ClientConfig\\_t::pHwConfig](#)

8.981.2.2 [wdsDhcpv4OptionList](#)\* [unpack\\_wds\\_SLQSSGetDHCPv4ClientConfig\\_t::pRequestOptionList](#)

## 8.982 [unpack\\_wds\\_SLQSStartDataSession\\_t](#) Struct Reference

## Data Fields

- [uint32\\_t](#) \* [psid](#)
- [uint32\\_t](#) \* [pFailureReason](#)
- [uint32\\_t](#) \* [pVerboseFailReasonType](#)
- [uint32\\_t](#) \* [pVerboseFailureReason](#)

### 8.982.1 Detailed Description

#### Parameters

<i>psid</i>	<ul style="list-style-type: none"> <li>• Assigned session ID when starting a data session</li> </ul>
<i>pFailureReason</i>	<ul style="list-style-type: none"> <li>• Reason data session failed to be established</li> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason</li> </ul>
<i>pVerboseFailReasonType</i>	<ul style="list-style-type: none"> <li>• Parameter describing type of verbose failure reason</li> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason Type</li> </ul>
<i>pVerboseFailureReason</i>	<ul style="list-style-type: none"> <li>• Verbose reason explaining why call failed. Depends on verbFailReasonType parameter</li> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason</li> </ul>



## 8.982.2 Field Documentation

8.982.2.1 uint32\_t\* unpack\_wds\_SLQSStartDataSession\_t::pFailureReason

8.982.2.2 uint32\_t\* unpack\_wds\_SLQSStartDataSession\_t::psid

8.982.2.3 uint32\_t\* unpack\_wds\_SLQSStartDataSession\_t::pVerboseFailReasonType

8.982.2.4 uint32\_t\* unpack\_wds\_SLQSStartDataSession\_t::pVerboseFailureReason

## 8.983 unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t Struct Reference

### Data Fields

- uint8\_t [contextId](#)
- uint8\_t [bearerId](#)
- int8\_t [apnName](#) [100]
- uint32\_t [ipv4Address](#)
- uint32\_t [ipv4GWAddress](#)
- uint32\_t [prDNSIPv4Address](#)
- uint32\_t [seDNSIPv4Address](#)
- struct [ipv6AddressInfo](#) [ipv6Address](#)
- struct [ipv6AddressInfo](#) [ipv6GWAddress](#)
- uint16\_t [prDNSIPv6Address](#) [8]
- uint16\_t [seDNSIPv6Address](#) [8]
- uint32\_t [prPCSCFIPv4Address](#)
- uint32\_t [sePCSCFIPv4Address](#)
- uint16\_t [prPCSCFIPv6Address](#) [8]
- uint16\_t [sePCSCFIPv6Address](#) [8]

### 8.983.1 Detailed Description

#### Parameters

<i>contextId</i>	Context Identifier
<i>bearerId</i>	Bearer Identity
<i>apnName</i>	APN name associated with the context id
<i>ipv4Address</i>	IPv4 Address
<i>ipv4GWAddress</i>	IPv4 Gateway Address
<i>prDNSIPv4-Address</i>	Primary DNS IPv4 Address
<i>seDNSIPv4-Address</i>	Secondary DNS IPv4 Address
<i>ipv6Address</i>	IPv6 Address
<i>ipv6GWAddress</i>	IPv6 Gateway Address
<i>prDNSIPv6-Address</i>	Primary IPv6 DNS Address
<i>seDNSIPv6-Address</i>	Secondary IPv6 DNS Address
<i>prPCSCFIPv4-Address</i>	Primary PCSCF IPv4 Address
<i>sePCSCFIPv4-Address</i>	Secondary PCSCF IPv4 Address
<i>prPCSCFIPv6-Address</i>	Primary PCSCF IPv6 Address
<i>sePCSCFIPv6-Address</i>	Secondary PCSCF IPv6 Address

### 8.983.2 Field Documentation

8.983.2.1 `int8_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::apnName[100]`

8.983.2.2 `uint8_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::bearerId`

8.983.2.3 `uint8_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::contextId`

8.983.2.4 `uint32_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::ipv4Address`

8.983.2.5 `uint32_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::ipv4GWAddress`

8.983.2.6 `struct ipv6AddressInfo unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::ipv6Address`

8.983.2.7 `struct ipv6AddressInfo unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::ipv6GWAddress`

8.983.2.8 `uint32_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::prDNSIPv4Address`

8.983.2.9 `uint16_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::prDNSIPv6Address[8]`

8.983.2.10 `uint32_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::prPCSCFIPv4Address`

8.983.2.11 `uint16_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::prPCSCFIPv6Address[8]`

8.983.2.12 `uint32_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::seDNSIPv4Address`

8.983.2.13 `uint16_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::seDNSIPv6Address[8]`

8.983.2.14 `uint32_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::sePCSCFIPv4Address`

8.983.2.15 `uint16_t unpack_wds_SLQSWdsSwiPDPRuntimeSettings_t::sePCSCFIPv6Address[8]`

## 8.984 UnPackGetProfileSettingOut Struct Reference

### Data Fields

- [UnpackQmiProfileInfo curProfile](#)
- `uint16_t *` [pExtErrCode](#)

### 8.984.1 Field Documentation

8.984.1.1 `UnpackQmiProfileInfo UnPackGetProfileSettingOut::curProfile`

8.984.1.2 `uint16_t*` `UnPackGetProfileSettingOut::pExtErrCode`

## 8.985 unpackWdsProfileParam Union Reference

### Data Fields

- [LibpackProfile3GPP SlqsProfile3GPP](#)
- [LibpackProfile3GPP2 SlqsProfile3GPP2](#)

### 8.985.1 Field Documentation

8.985.1.1 `LibpackProfile3GPP unpackWdsProfileParam::SlqsProfile3GPP`

8.985.1.2 `LibpackProfile3GPP2 unpackWdsProfileParam::SlqsProfile3GPP2`

## 8.986 USBCompConfig Struct Reference

### Data Fields

- `BYTE *` [pUSBComp](#)

### 8.986.1 Detailed Description

This structure is used to store USB composition information

## Parameters

<i>pUSBComp</i> [IN]	<ul style="list-style-type: none"> <li>• Current USB Composition</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0..5 - Reserved (non-QMI)</li> <li>– 6 - DM NMEA AT QMI</li> <li>– 7 - DM NMEA AT QMI1 QMI2 QMI3</li> <li>– 8 - DM NMEA AT MBIM</li> <li>– 9 - MBIM</li> <li>– 10 - NMEA MBIM</li> <li>– 11 - DM MBIM</li> <li>– 12 - DM NMEA MBIM</li> <li>13-22 are combined compositions. One is for Win8 MBIM interfaces, another is for legacy QMI interfaces</li> <li>– 13 - 6 for QMI, 8 for MBIM</li> <li>– 14 - 6 for QMI, 9 for MBIM</li> <li>– 15 - 6 for QMI, 10 for MBIM</li> <li>– 16 - 6 for QMI, 11 for MBIM</li> <li>– 17 - 6 for QMI, 12 for MBIM</li> <li>– 18 - 7 for QMI, 8 for MBIM</li> <li>– 19 - 7 for QMI, 9 for MBIM</li> <li>– 20 - 7 for QMI, 10 for MBIM</li> <li>– 21 - 7 for QMI, 11 for MBIM</li> <li>– 22 - 7 for QMI, 12 for MBIM</li> </ul> </li> </ul>
----------------------	--

## 8.986.2 Field Documentation

8.986.2.1 BYTE\* USBCompConfig::pUSBComp

## 8.987 USBCompParams Struct Reference

## Data Fields

- [BYTE \\* pUSBComp](#)
- [BYTE \\* pNumSupUSBComps](#)
- [BYTE \\* pSupUSBComps](#)

## 8.987.1 Detailed Description

This structure is used to store retrieved USB Composition

## Parameters

<i>pUSBComp[OUT]</i>	<ul style="list-style-type: none"> <li>• Current USB Composition(optional parameter)</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0..5 - Reserved (non-QMI)</li> <li>– 6 - DM NMEA AT QMI</li> <li>– 7 - DM NMEA AT QMI1 QMI2 QMI3</li> <li>– 8 - DM NMEA AT MBIM</li> <li>– 9 - MBIM</li> <li>– 10 - NMEA MBIM</li> <li>– 11 - DM MBIM</li> <li>– 12 - DM NMEA MBIM</li> <li>13-22 are combined compositions. One is for Win8 MBIM interfaces, another is for legacy QMI interfaces</li> <li>– 13 - 6 for QMI, 8 for MBIM</li> <li>– 14 - 6 for QMI, 9 for MBIM</li> <li>– 15 - 6 for QMI, 10 for MBIM</li> <li>– 16 - 6 for QMI, 11 for MBIM</li> <li>– 17 - 6 for QMI, 12 for MBIM</li> <li>– 18 - 7 for QMI, 8 for MBIM</li> <li>– 19 - 7 for QMI, 9 for MBIM</li> <li>– 20 - 7 for QMI, 10 for MBIM</li> <li>– 21 - 7 for QMI, 11 for MBIM</li> <li>– 22 - 7 for QMI, 12 for MBIM</li> </ul> </li> </ul>
----------------------	--

<i>pNumSupUSB-Comps[OUT]</i>	<ul style="list-style-type: none"> <li>• Number of supported USB compositions in the parameter to follow</li> <li>• Range - 0-255</li> </ul>
<i>pSupUSB-Comps[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• List of supported USB compositions( 1 Byte each - Max 255 )</li> <li>• Total length is defined by pNumSupUSBComps parameter</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0..5 - Reserved (non-QMI)</li> <li>– 6 - DM NMEA AT QMI</li> <li>– 7 - DM NMEA AT QMI1 QMI2 QMI3</li> <li>– 8 - DM NMEA AT MBIM</li> <li>– 9 - MBIM</li> <li>– 10 - NMEA MBIM</li> <li>– 11 - DM MBIM</li> <li>– 12 - DM NMEA MBIM</li> <li>13-22 are combined compositions. One is for Win8 MBIM interfaces, another is for legacy QMI interfaces</li> <li>– 13 - 6 for QMI, 8 for MBIM</li> <li>– 14 - 6 for QMI, 9 for MBIM</li> <li>– 15 - 6 for QMI, 10 for MBIM</li> <li>– 16 - 6 for QMI, 11 for MBIM</li> <li>– 17 - 6 for QMI, 12 for MBIM</li> <li>– 18 - 7 for QMI, 8 for MBIM</li> <li>– 19 - 7 for QMI, 9 for MBIM</li> <li>– 20 - 7 for QMI, 10 for MBIM</li> <li>– 21 - 7 for QMI, 11 for MBIM</li> <li>– 22 - 7 for QMI, 12 for MBIM</li> </ul> </li> </ul>

## 8.987.2 Field Documentation

8.987.2.1 **BYTE\*** USBCompParams::pNumSupUSBComps

8.987.2.2 **BYTE\*** USBCompParams::pSupUSBComps

8.987.2.3 **BYTE\*** USBCompParams::pUSBComp

## 8.988 USSDNoWaitIndicationInfo Struct Reference

### Data Fields

- **BYTE \*** pError
- **BYTE \*** pFailureCause

- struct [USSInfo](#) \* [pUSSDData](#)
- [alphaIDInfo](#) \* [pAlphaIdentifier](#)

### 8.988.1 Detailed Description

Contains the parameters passed for USSDNoWaitIndicationCallback by the device.

Parameters

<i>pError</i>	<ul style="list-style-type: none"> <li>• Type of Error (if any)</li> </ul>
<i>pFailureCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause</li> </ul>
<i>pUSSDData</i>	<ul style="list-style-type: none"> <li>• USS Data from Network.</li> <li>• See <a href="#">USSInfo</a> for more details.</li> </ul>

### 8.988.2 Field Documentation

8.988.2.1 [alphaIDInfo](#)\* USSDNoWaitIndicationInfo::pAlphaIdentifier

8.988.2.2 [BYTE](#)\* USSDNoWaitIndicationInfo::pError

8.988.2.3 [BYTE](#)\* USSDNoWaitIndicationInfo::pFailureCause

8.988.2.4 struct [USSInfo](#)\* USSDNoWaitIndicationInfo::pUSSDData

## 8.989 USSDRespFNetwork Struct Reference

Data Fields

- char \* [pTypeCode](#)
- char \* [pRespData](#)

### 8.989.1 Detailed Description

This structure contains the response from the network

Parameters

<i>pTypeCode</i>	"0" USSD-Notify – text in pRespData "1" USSD-Request – text in pRespData "2" Session terminated by network "3" other local client (eg, SIM Toolkit) has responded "4" Operation not supported "5" Network timeout
<i>pRespData</i>	<ul style="list-style-type: none"> <li>• points to a message string received from the network</li> </ul>

### 8.989.2 Field Documentation

8.989.2.1 `char* USSDRespFNetwork::pRespData`

8.989.2.2 `char* USSDRespFNetwork::pTypeCode`

## 8.990 USSInfo Struct Reference

### Data Fields

- [BYTE `ussDCS`](#)
- [BYTE `ussLen`](#)
- [BYTE `ussData` \[182\]](#)

### 8.990.1 Detailed Description

This structure contains USS Information

#### Parameters

<i>ussDCS</i>	<ul style="list-style-type: none"> <li>• 1 - ASCII coding scheme</li> <li>• 2 - 8-BIT coding scheme</li> <li>• 3 - UCS2</li> </ul>
<i>ussLen</i>	<ul style="list-style-type: none"> <li>• Range 1 to 182</li> </ul>
<i>ussData</i>	<ul style="list-style-type: none"> <li>• Data encoded as per the DCS</li> </ul>

### 8.990.2 Field Documentation

8.990.2.1 **BYTE** `USSInfo::ussData[182]`

8.990.2.2 **BYTE** `USSInfo::ussDCS`

8.990.2.3 **BYTE** `USSInfo::ussLen`

## 8.991 USSResp Struct Reference

### Data Fields

- [WORD \\* `pfailureCause`](#)
- [alphaIDInfo \\* `pAlphaIDInfo`](#)
- [struct `USSInfo` \\* `pUSSDInfo`](#)
- [BYTE \\* `pCcResultType`](#)
- [BYTE \\* `pCallId`](#)
- [ccSUPSType \\* `pCCSuppsType`](#)



### 8.991.1 Field Documentation

8.991.1.1 `alphaIDInfo*` `USSResp::pAlphaIDInfo`

8.991.1.2 `BYTE*` `USSResp::pCallId`

8.991.1.3 `BYTE*` `USSResp::pCcResultType`

8.991.1.4 `ccSUPSType*` `USSResp::pCCSuppsType`

8.991.1.5 `WORD*` `USSResp::pFailureCause`

8.991.1.6 `struct UUSInfo*` `USSResp::pUSSDInfo`

## 8.992 UUSInfo Struct Reference

### Data Fields

- [BYTE UUSType](#)
- [BYTE UUSDcs](#)
- [BYTE UUSDatalen](#)
- [BYTE UUSData](#) [255]

### 8.992.1 Detailed Description

This structure contains User to User Signaling Service Information.

#### Parameters

<i>UUSType</i>	<ul style="list-style-type: none"><li>• UUS type values are:<ul style="list-style-type: none"><li>– 0x00 - UUS_DATA</li><li>– 0x01 - UUS_TYPE1_IMPLICIT</li><li>– 0x02 - UUS_TYPE1_REQUIRED</li><li>– 0x03 - UUS_TYPE1_NOT_REQUIRED</li><li>– 0x04 - UUS_TYPE2_REQUIRED</li><li>– 0x05 - UUS_TYPE2_NOT_REQUIRED</li><li>– 0x06 - UUS_TYPE3_REQUIRED</li><li>– 0x07 - UUS_TYPE3_NOT_REQUIRED</li><li>– 0xFF - Not Available</li></ul></li></ul>
----------------	--

<i>UUSDcs</i>	<ul style="list-style-type: none"> <li>• UUS data coding scheme values are: <ul style="list-style-type: none"> <li>– 0x01 - UUS_DCS_USP</li> <li>– 0x02 - UUS_DCS_OHLP</li> <li>– 0x03 - UUS_DCS_X244</li> <li>– 0x04 - UUS_DCS_SMCF</li> <li>– 0x05 - UUS_DCS_IA5</li> <li>– 0x06 - UUS_DCS_RV12RD</li> <li>– 0x07 - UUS_DCS_Q931UNCCM</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>UUSDatalen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the following elements. <ul style="list-style-type: none"> <li>– UUSData</li> </ul> </li> <li>• If zero(0) then no further information exists.</li> </ul>
<i>UUSData[<b>MAX_- DESCRIPTION- _LENGTH</b>]</i>	<ul style="list-style-type: none"> <li>• UUS data encoded as per coding scheme</li> </ul>

## 8.992.2 Field Documentation

8.992.2.1 **BYTE** UUSInfo::UUSData[255]

8.992.2.2 **BYTE** UUSInfo::UUSDatalen

8.992.2.3 **BYTE** UUSInfo::UUSDcs

8.992.2.4 **BYTE** UUSInfo::UUSType

## 8.993 verifyUIMPIN Struct Reference

### Data Fields

- [BYTE](#) pinID
- [BYTE](#) pinLen
- [BYTE](#) pinVal [255]

### 8.993.1 Detailed Description

This structure contains the information about the pin parameters that need to be verified.

## Parameters

<i>pinID</i>	<ul style="list-style-type: none"> <li>Indicates the PIN ID to be verified. <ul style="list-style-type: none"> <li>1 - PIN1 (also called PIN)</li> <li>2 - PIN2</li> <li>3 - Universal PIN</li> <li>4 - Hidden key</li> </ul> </li> </ul>
<i>pinLen</i>	<ul style="list-style-type: none"> <li>Length of the following elements i.e. pin value.</li> </ul>
<i>pinVal</i> [MAX_DESCRIPTION_LENGTH]	<ul style="list-style-type: none"> <li>PIN value.</li> <li>This value is a sequence of ASCII characters.</li> </ul>

## 8.993.2 Field Documentation

8.993.2.1 BYTE verifyUIMPIN::pinID

8.993.2.2 BYTE verifyUIMPIN::pinLen

8.993.2.3 BYTE verifyUIMPIN::pinVal[255]

## 8.994 voiceALSSelectLineInfo Struct Reference

## Data Fields

- [BYTE lineValue](#)

## 8.994.1 Detailed Description

This structure contains ALS Select Line Information Parameters.

## Parameters

<i>lineValue</i>	<ul style="list-style-type: none"> <li>ALS Line Value. <ul style="list-style-type: none"> <li>0x00 - ALS_LINE1 - Line 1 (default)</li> <li>0x01 - ALS_LINE2 - Line 2</li> </ul> </li> </ul>
------------------	---

## 8.994.2 Field Documentation

8.994.2.1 BYTE voiceALSSelectLineInfo::lineValue

## 8.995 voiceALSSetLineSwitchInfo Struct Reference

## Data Fields

- [BYTE switchOption](#)

### 8.995.1 Detailed Description

This structure contains ALS Set Line Switching Information Parameters.

#### Parameters

<i>switchOption</i>	<ul style="list-style-type: none"><li>• Switch Option.<ul style="list-style-type: none"><li>– 0x00 - VOICE_LINE_SWITCHING_NOT_ALLOWED - Line switching is not allowed</li><li>– 0x01 - VOICE_LINE_SWITCHING_ALLOWED - Line switching is allowed</li></ul></li></ul>
---------------------	---

### 8.995.2 Field Documentation

#### 8.995.2.1 BYTE voiceALSSetLineSwitchInfo::switchOption

## 8.996 voiceAnswerCall Struct Reference

## Data Fields

- [BYTE \\* pCallId](#)

### 8.996.1 Detailed Description

Contains the parameters passed for SLQSVoiceAnswerCall.

#### Parameters

<i>pCallId[IN/OUT]</i>	<ul style="list-style-type: none"><li>• Unique call identifier for the call that must be answered.</li></ul>
------------------------	--

### 8.996.2 Field Documentation

#### 8.996.2.1 BYTE\* voiceAnswerCall::pCallId

## 8.997 voiceBindSubscriptionInfo Struct Reference

## Data Fields

- [BYTE subType](#)

### 8.997.1 Detailed Description

This structure contains Bind Subscription Information Parameters.

## Parameters

<i>subsType</i>	<ul style="list-style-type: none"> <li>Subscription Type. <ul style="list-style-type: none"> <li>0x00 - VOICE_SUBS_TYPE_PRIMARY - Primary</li> <li>0x01 - VOICE_SUBS_TYPE_SECONDARY - Secondary</li> </ul> </li> </ul>
-----------------	--

## 8.997.2 Field Documentation

## 8.997.2.1 BYTE voiceBindSubscriptionInfo::subsType

## 8.998 voiceBurstDTMFInfo Struct Reference

## Data Fields

- [burstDTMFInfo](#) [BurstDTMFInfo](#)
- [DTMFLengths](#) \* [pBurstDTMFLengths](#)

## 8.998.1 Detailed Description

This structure contains parameters of burst Dual-Tone Multifrequency (DTMF)

## Parameters

<i>BurstDTMFInfo</i>	<ul style="list-style-type: none"> <li>Burst DTMF Information <ul style="list-style-type: none"> <li>See <a href="#">burstDTMFInfo</a> for more information</li> </ul> </li> </ul>
<i>pBurstDTMF- Lengths</i>	[optional] <ul style="list-style-type: none"> <li>DTMF Lengths <ul style="list-style-type: none"> <li>See <a href="#">DTMFLengths</a> for more information</li> </ul> </li> </ul>

## 8.998.2 Field Documentation

## 8.998.2.1 burstDTMFInfo voiceBurstDTMFInfo::BurstDTMFInfo

## 8.998.2.2 DTMFLengths\* voiceBurstDTMFInfo::pBurstDTMFLengths

## 8.999 voiceCallInfoReq Struct Reference

## Data Fields

- [BYTE](#) [callID](#)

## 8.999.1 Detailed Description

This structure contains information of the request parameters associated with a call.

## Parameters

<i>callID</i>	<ul style="list-style-type: none"> <li>• Call identifier for the call queried for information.</li> </ul>
---------------	---

## 8.999.2 Field Documentation

## 8.999.2.1 BYTE voiceCallInfoReq::callID

## 8.1000 voiceCallInfoResp Struct Reference

## Data Fields

- [callInfo](#) \* [pCallInfo](#)
- [remotePartyNum](#) \* [pRemotePartyNum](#)
- [WORD](#) \* [pSrvOpt](#)
- [BYTE](#) \* [pVoicePrivacy](#)
- [BYTE](#) \* [pOTASPStatus](#)
- [remotePartyName](#) \* [pRemotePartyName](#)
- [UUSInfo](#) \* [pUUSInfo](#)
- [BYTE](#) \* [pAlertType](#)
- [alphaIDInfo](#) \* [pAlphaIDInfo](#)
- [connectNumInfo](#) \* [pConnectNumInfo](#)
- [diagInfo](#) \* [pDiagInfo](#)
- [ULONG](#) \* [pAlertingPattern](#)

## 8.1000.1 Detailed Description

This structure contains information of the response parameters associated with a call.

## Parameters

<i>pCall-Info(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">callInfo</a> for more information.</li> </ul>
<i>pRemoteParty-Num(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">remotePartyNum</a> for more information.</li> </ul>
<i>pSrvOpt</i>	<ul style="list-style-type: none"> <li>• Service option(optional)</li> <li>• Applicable only for 3GPP2 devices.</li> <li>• See Table8 <a href="#">qaGobiApiTableServiceOptions.h</a> for standard service option number assignments.</li> </ul>

<i>pVoicePrivacy</i>	<ul style="list-style-type: none"> <li>• Voice Privacy.(optional)</li> <li>• Applicable only for 3GPP2 devices.</li> <li>• Values. <ul style="list-style-type: none"> <li>– 0x00 - VOICE_PRIVACY_STANDARD - Standard privacy</li> <li>– 0x01 - VOICE_PRIVACY_ENHANCED - Enhanced privacy</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pOTASPStatus</i>	<ul style="list-style-type: none"> <li>• OTASP status for the OTASP call.(optional)</li> <li>• Applicable only for 3GPP2 devices. <ul style="list-style-type: none"> <li>– 0x00 - OTASP_STATUS_SPL_UNLOCKED - SPL unlocked; only for user-initiated OTASP</li> <li>– 0x01 - OTASP_STATUS_SPRC_RETRIES_EXCEEDED - SPC retries exceeded; only for user-initiated OTASP</li> <li>– 0x02 - OTASP_STATUS_AKEY_EXCHANGED - A-key exchanged; only for user-initiated OTASP</li> <li>– 0x03 - OTASP_STATUS_SSD_UPDATED - SSD updated; for both user-initiated OTASP and network-initiated OTASP (OTAPA)</li> <li>– 0x04 - OTASP_STATUS_NAM_DOWNLOADED - NAM downloaded; only for user-initiated OTASP</li> <li>– 0x05 - OTASP_STATUS_MDN_DOWNLOADED - MDN downloaded; only for user-initiated OTASP</li> <li>– 0x06 - OTASP_STATUS_IMSI_DOWNLOADED - IMSI downloaded; only for user-initiated OTASP</li> <li>– 0x07 - OTASP_STATUS_PRL_DOWNLOADED - PRL downloaded; only for user-initiated OTASP</li> <li>– 0x08 - OTASP_STATUS_COMMITTED - Commit successful; only for user-initiated OTASP</li> <li>– 0x09 - OTASP_STATUS_OTAPA_STARTED - OTAPA started; only for network-initiated OTASP (OTAPA)</li> <li>– 0x0A - OTASP_STATUS_OTAPA_STOPPED - OTAPA stopped; only for network-initiated OTASP (OTAPA)</li> <li>– 0x0B - OTASP_STATUS_OTAPA_ABORTED - OTAPA aborted; only for network-initiated OTASP (OTAPA)</li> <li>– 0x0C - OTASP_STATUS_OTAPA_COMMITTED - OTAPA committed; only for network-initiated OTASP (OTAPA)</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pRemoteParty-Name(optional)</i>	<ul style="list-style-type: none"> <li>• Applicable only for 3GPP devices.</li> <li>• See <a href="#">remotePartyName</a> for more information.</li> </ul>
<i>pUUS-Info(optional)</i>	<ul style="list-style-type: none"> <li>• Applicable only for 3GPP devices.</li> <li>• See <a href="#">UUSInfo</a> for more information.</li> </ul>
<i>pAlertType(optional)</i>	<ul style="list-style-type: none"> <li>• Alerting type.</li> <li>• Applicable only for 3GPP devices.</li> </ul>

## 8.1000.2 Field Documentation

- 8.1000.2.1 **ULONG\*** voiceCallInfoResp::pAlertingPattern
- 8.1000.2.2 **BYTE\*** voiceCallInfoResp::pAlertType
- 8.1000.2.3 **alphaIDInfo\*** voiceCallInfoResp::pAlphaIDInfo
- 8.1000.2.4 **callInfo\*** voiceCallInfoResp::pCallInfo
- 8.1000.2.5 **connectNumInfo\*** voiceCallInfoResp::pConnectNumInfo
- 8.1000.2.6 **diagInfo\*** voiceCallInfoResp::pDiagInfo
- 8.1000.2.7 **BYTE\*** voiceCallInfoResp::pOTASPStatus
- 8.1000.2.8 **remotePartyName\*** voiceCallInfoResp::pRemotePartyName
- 8.1000.2.9 **remotePartyNum\*** voiceCallInfoResp::pRemotePartyNum
- 8.1000.2.10 **WORD\*** voiceCallInfoResp::pSrvOpt
- 8.1000.2.11 **UUSInfo\*** voiceCallInfoResp::pUUSInfo
- 8.1000.2.12 **BYTE\*** voiceCallInfoResp::pVoicePrivacy

## 8.1001 voiceCallRequestParams Struct Reference

### Data Fields

- [BYTE](#) callNumber [81]
- [BYTE \\*](#) pCallType
- [BYTE \\*](#) pCLIRType
- [UUSInfo \\*](#) pUUSInfo
- [CUGInfo \\*](#) pCUGInfo
- [BYTE \\*](#) pEmergencyCategory
- [calledPartySubAdd \\*](#) pCallPartySubAdd
- [ULONG \\*](#) pSvcType

### 8.1001.1 Detailed Description

This structure contains Voice Call Request Parameters

#### Parameters

<i>callNumber[81]</i>	<ul style="list-style-type: none"> <li>• Number to be dialed in ASCII string, NULL terminated.</li> <li>• Length Range [1 to 81]</li> </ul>
-----------------------	---



<i>pCall-Type(optional)</i>	<ul style="list-style-type: none"> <li>the type of call to be dialed. CALL_TYPE_VOICE is automatically selected if this parameter is not provided. When CALL_TYPE_NON_STD_OTASP is selected, the call is sent as a nonstandard OTASP call regardless of the digit string Call type values are: <ul style="list-style-type: none"> <li>0x00 - CALL_TYPE_VOICE - Voice (automatic selection)</li> <li>0x01 - CALL_TYPE_VOICE_FORCED - Avoid modem call classification</li> <li>0x08 - CALL_TYPE_NON_STD_OTASP - Nonstandard OTASP*</li> <li>0x09 - CALL_TYPE_EMERGENCY - Emergency</li> </ul> </li> </ul>
<i>pCLIR-Type(optional)</i>	<ul style="list-style-type: none"> <li>CLIR type values are: <ul style="list-style-type: none"> <li>0x01 - CLIR_SUPPRESSION - Suppression</li> <li>0x02 - CLIR_INVOCATION - Invocation</li> </ul> </li> </ul>
<i>pUUSInfo(optional)</i>	<ul style="list-style-type: none"> <li>Pointer to structure of <a href="#">UUSInfo</a> <ul style="list-style-type: none"> <li>See <a href="#">UUSInfo</a> for more information</li> </ul> </li> </ul>
<i>pCUG-Info(optional)</i>	<ul style="list-style-type: none"> <li>Pointer to structure of <a href="#">CUGInfo</a> <ul style="list-style-type: none"> <li>See <a href="#">CUGInfo</a> for more information</li> </ul> </li> </ul>
<i>pEmergency-Category(optional)</i>	<ul style="list-style-type: none"> <li>Bit mask of emergency number categories. This is only applicable when the call type is set to Emergency. <ul style="list-style-type: none"> <li>Bit 0 - VOICE_EMER_CAT_POLICE_BIT - Police</li> <li>Bit 1 - VOICE_EMER_CAT_AMBULANCE_BIT - Ambulance</li> <li>Bit 2 - VOICE_EMER_CAT_FIRE_BRIGADE_BIT - Fire brigade</li> <li>Bit 3 - VOICE_EMER_CAT_MARINE_GUARD_BIT - Marine guard</li> <li>Bit 4 - VOICE_EMER_CAT_MOUNTAIN_RESCUE_BIT - Mountain rescue</li> <li>Bit 5 - VOICE_EMER_CAT_MANUAL_ECALL_BIT - Manual emergency call</li> <li>Bit 6 - VOICE_EMER_CAT_AUTO_ECALL_BIT - Automatic emergency call</li> <li>Bit 7 - VOICE_EMER_CAT_SPARE_BIT - Spare bit</li> </ul> </li> </ul>
<i>pCallPartySub-Add(optional)</i>	<ul style="list-style-type: none"> <li>Pointer to structure of <a href="#">calledPartySubAdd</a> <ul style="list-style-type: none"> <li>See <a href="#">calledPartySubAdd</a> for more information</li> </ul> </li> </ul>
<i>pSvc-Type(optional)</i>	<ul style="list-style-type: none"> <li>Service Type. <ul style="list-style-type: none"> <li>0x01 - VOICE_DIAL_CALL_SRV_TYPE_AUTOMATIC - Automatic</li> <li>0x02 - VOICE_DIAL_CALL_SRV_TYPE_GSM - GSM</li> <li>0x03 - VOICE_DIAL_CALL_SRV_TYPE_WCDMA - WCDMA</li> <li>0x04 - VOICE_DIAL_CALL_SRV_TYPE_CDMA_AUTOMATIC - CDMA automatic</li> <li>0x05 - VOICE_DIAL_CALL_SRV_TYPE_GSM_WCDMA - GSM or WCDMA</li> <li>0x06 - VOICE_DIAL_CALL_SRV_TYPE_LTE -LTE</li> </ul> </li> </ul>

### 8.1001.2 Field Documentation

- 8.1001.2.1 **BYTE** voiceCallRequestParams::callNumber[81]
- 8.1001.2.2 **calledPartySubAdd\*** voiceCallRequestParams::pCallPartySubAdd
- 8.1001.2.3 **BYTE\*** voiceCallRequestParams::pCallType
- 8.1001.2.4 **BYTE\*** voiceCallRequestParams::pCLIRType
- 8.1001.2.5 **CUGInfo\*** voiceCallRequestParams::pCUGInfo
- 8.1001.2.6 **BYTE\*** voiceCallRequestParams::pEmergencyCategory
- 8.1001.2.7 **ULONG\*** voiceCallRequestParams::pSvcType
- 8.1001.2.8 **UUSInfo\*** voiceCallRequestParams::pUUSInFo

## 8.1002 voiceCallResponseParams Struct Reference

### Data Fields

- **BYTE \*** pCallID
- **alphaIDInfo \*** pAlphaIDInfo
- **BYTE \*** pCCResultType
- **ccSUPSType \*** pCCSUPSType

### 8.1002.1 Detailed Description

This structure contains Voice Call Response Parameters

#### Parameters

<i>pCallID(optional)</i>	<ul style="list-style-type: none"> <li>• Unique call identifier for the dialed call</li> </ul>
<i>pAlphaID-Info(optional)</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResult-Type(optional)</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type.               <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> </ul> </li> </ul>

<i>pCCSUPS-Type(optional)</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">ccSUPSType</a></li> <li>• Data is present when pCCResultType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>
-------------------------------	---

## 8.1002.2 Field Documentation

8.1002.2.1 **alphaIDInfo\*** voiceCallResponseParams::pAlphaIDInfo

8.1002.2.2 **BYTE\*** voiceCallResponseParams::pCallID

8.1002.2.3 **BYTE\*** voiceCallResponseParams::pCCResultType

8.1002.2.4 **ccSUPSType\*** voiceCallResponseParams::pCCSUPSType

## 8.1003 voiceContDTMFInfo Struct Reference

### Data Fields

- [BYTE \\*](#) pCallID
- [BYTE](#) DTMFdigit

### 8.1003.1 Detailed Description

This structure contains parameters of continuous DTMF

#### Parameters

<i>pCallID[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Call ID associated with call on which the DTMF information has to be sent. Start continuous DTMF request is sent to the current active/alerting call when pCallId is set to 0xFF.</li> <li>• This is IN/OUT parameter, value passed by user will be packed in request and value received from the device would be returned to the user.</li> <li>• If the call ID value received is 0, no value has been returned by the device</li> </ul>
<i>DTMFdigit[IN]</i>	<ul style="list-style-type: none"> <li>• DTMF digit in ASCII.</li> </ul>

## 8.1003.2 Field Documentation

8.1003.2.1 **BYTE** voiceContDTMFInfo::DTMFdigit

8.1003.2.2 **BYTE\*** voiceContDTMFInfo::pCallID

## 8.1004 voiceDTMFEventInfo Struct Reference

## Data Fields

- [DTMFInfo](#) DTMFInformation
- [BYTE](#) \* pOnLength
- [BYTE](#) \* pOffLength

### 8.1004.1 Detailed Description

This structure contains the parameters passed for SLQSVoiceSetDTMFEventCallBack by the device.

#### Parameters

<i>DTMF- Information(mandatory)</i>	• See <a href="#">DTMFInfo</a> for more information.
<i>pOn- Length(optional)</i>	<ul style="list-style-type: none"> <li>• DTMF Pulse Width <ul style="list-style-type: none"> <li>– 0x00 - DTMF_ONLENGTH_95MS - 95 ms</li> <li>– 0x01 - DTMF_ONLENGTH_150MS - 150 ms</li> <li>– 0x02 - DTMF_ONLENGTH_200MS - 200 ms</li> <li>– 0x03 - DTMF_ONLENGTH_250MS - 250 ms</li> <li>– 0x04 - DTMF_ONLENGTH_300MS - 300 ms</li> <li>– 0x05 - DTMF_ONLENGTH_350MS - 350 ms</li> <li>– 0x06 - DTMF_ONLENGTH_SMS - SMS Tx special pulse width</li> </ul> </li> </ul>
<i>pOff- Length(optional)</i>	<ul style="list-style-type: none"> <li>• DTMF Interdigit Interval <ul style="list-style-type: none"> <li>– 0x00 - DTMF_OFFLENGTH_60MS - 60 ms</li> <li>– 0x01 - DTMF_OFFLENGTH_100MS - 100 ms</li> <li>– 0x02 - DTMF_OFFLENGTH_150MS - 150 ms</li> <li>– 0x03 - DTMF_OFFLENGTH_200MS - 200 ms</li> </ul> </li> </ul>

#### Note

None

### 8.1004.2 Field Documentation

8.1004.2.1 [DTMFInfo](#) voiceDTMFEventInfo::DTMFInformation

8.1004.2.2 [BYTE](#)\* voiceDTMFEventInfo::pOffLength

8.1004.2.3 [BYTE](#)\* voiceDTMFEventInfo::pOnLength

## 8.1005 voiceFlashInfo Struct Reference

### Data Fields

- [BYTE](#) \* pCallID

- [BYTE \\* pFlashPayLd](#)
- [BYTE \\* pFlashType](#)

### 8.1005.1 Detailed Description

This structure contains the flash information associated with a call.

Parameters

<i>pCallID</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Unique call identifier associated with the current call.</li> </ul>
<i>pFlashPayLd</i> [I-N](optional)	<ul style="list-style-type: none"> <li>• Payload in ASCII to be sent in Flash.</li> <li>• Variable Length, NULL terminated.</li> </ul>
<i>pFlashType</i> [I-N](optional)	<ul style="list-style-type: none"> <li>• Flash type. <ul style="list-style-type: none"> <li>– 0 - Simple Flash (default)</li> <li>– 1 - Activate answer hold</li> <li>– 2 - Deactivate answer hold</li> </ul> </li> </ul>

### 8.1005.2 Field Documentation

8.1005.2.1 [BYTE\\* voiceFlashInfo::pCallID](#)

8.1005.2.2 [BYTE\\* voiceFlashInfo::pFlashPayLd](#)

8.1005.2.3 [BYTE\\* voiceFlashInfo::pFlashType](#)

## 8.1006 voiceGetAllCallInfo Struct Reference

### Data Fields

- [arrCallInfo \\* pArrCallInfo](#)
- [arrRemotePartyNum \\* pArrRemotePartyNum](#)
- [arrRemotePartyName \\* pArrRemotePartyName](#)
- [arrAlertingType \\* pArrAlertingType](#)
- [arrUUSInfo \\* pArrUUSInfo](#)
- [arrSvcOption \\* pArrSvcOption](#)
- [BYTE \\* pOTASPSStatus](#)
- [BYTE \\* pVoicePrivacy](#)
- [arrCallEndReason \\* pArrCallEndReason](#)
- [arrAlphaID \\* pArrAlphaID](#)
- [arrConnectPartyNum \\* pArrConnectPartyNum](#)
- [arrDiagInfo \\* pArrDiagInfo](#)
- [arrCalledPartyNum \\* pArrCalledPartyNum](#)
- [arrRedirPartyNum \\* pArrRedirPartyNum](#)
- [arrAlertingPattern \\* pArrAlertingPattern](#)

### 8.1006.1 Detailed Description

This structure contains information about the response parameters with all the calls originating or terminating from a particular device.

## Parameters

<i>pArrCall-Info(optional)</i>	<ul style="list-style-type: none"> <li>See <a href="#">arrCallInfo</a> for more information.</li> </ul>
<i>pArrRemote-Party-Num(optional)</i>	<ul style="list-style-type: none"> <li>See <a href="#">arrRemotePartyNum</a> for more information.</li> </ul>
<i>pArrRemote-Party-Name(optional)</i>	<ul style="list-style-type: none"> <li>See <a href="#">arrRemotePartyName</a> for more information.</li> </ul>
<i>pArrAlerting-Type(optional)</i>	<ul style="list-style-type: none"> <li>See <a href="#">arrAlertingType</a> for more information.</li> </ul>
<i>pArrUUS-Info(optional)</i>	<ul style="list-style-type: none"> <li>See <a href="#">arrUUSInfo</a> for more information.</li> </ul>
<i>pArrSvc-Option(optional)</i>	<ul style="list-style-type: none"> <li>See <a href="#">arrSvcOption</a> for more information.</li> </ul>
<i>pOTASP-Status(optional)</i>	<ul style="list-style-type: none"> <li>OTASP status for the OTASP call.</li> <li>Applicable only for 3GPP2 devices. <ul style="list-style-type: none"> <li>0x00 - OTASP_STATUS_SPL_UNLOCKED - SPL unlocked; only for user-initiated OTASP</li> <li>0x01 - OTASP_STATUS_SPRC_RETRIES_EXCEEDED - SPC retries exceeded; only for user-initiated OTASP</li> <li>0x02 - OTASP_STATUS_AKEY_EXCHANGED - A-key exchanged; only for user-initiated OTASP</li> <li>0x03 - OTASP_STATUS_SSD_UPDATED - SSD updated; for both user-initiated OTASP and network-initiated OTASP (OTAPA)</li> <li>0x04 - OTASP_STATUS_NAM_DOWNLOADED - NAM downloaded; only for user-initiated OTASP</li> <li>0x05 - OTASP_STATUS_MDN_DOWNLOADED - MDN downloaded; only for user-initiated OTASP</li> <li>0x06 - OTASP_STATUS_IMSI_DOWNLOADED - IMSI downloaded; only for user-initiated OTASP</li> <li>0x07 - OTASP_STATUS_PRL_DOWNLOADED - PRL downloaded; only for user-initiated OTASP</li> <li>0x08 - OTASP_STATUS_COMMITTED - Commit successful; only for user-initiated OTASP</li> <li>0x09 - OTASP_STATUS_OTAPA_STARTED - OTAPA started; only for network-initiated OTASP (OTAPA)</li> <li>0x0A - OTASP_STATUS_OTAPA_STOPPED - OTAPA stopped; only for network-initiated OTASP (OTAPA)</li> <li>0x0B - OTASP_STATUS_OTAPA_ABORTED - OTAPA aborted; only for network-initiated OTASP (OTAPA)</li> <li>0x0C - OTASP_STATUS_OTAPA_COMMITTED - OTAPA committed; only for network-initiated OTASP (OTAPA)</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>pVoice-Privacy(optional)</i>	<ul style="list-style-type: none"> <li>Voice Privacy.</li> <li>Values.</li> </ul>

<i>pArrCallEndReason(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">arrCallEndReason</a> for more information.</li> </ul>
<i>pArrAlphaID(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">arrAlphaID</a> for more information.</li> </ul>
<i>pArrConnectPartyNum(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">arrConnectPartyNum</a> for more information.</li> </ul>
<i>pArrDiagInfo(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">arrDiagInfo</a> for more information.</li> </ul>
<i>pArrCalledPartyNum(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">arrCalledPartyNum</a> for more information.</li> </ul>
<i>pArrRedirPartyNum(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">arrRedirPartyNum</a> for more information.</li> </ul>
<i>pArrAlertingPattern(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">arrAlertingPattern</a> for more information.</li> </ul>

## 8.1006.2 Field Documentation

8.1006.2.1 **arrAlertingPattern\*** voiceGetAllCallInfo::pArrAlertingPattern

8.1006.2.2 **arrAlertingType\*** voiceGetAllCallInfo::pArrAlertingType

8.1006.2.3 **arrAlphaID\*** voiceGetAllCallInfo::pArrAlphaID

8.1006.2.4 **arrCalledPartyNum\*** voiceGetAllCallInfo::pArrCalledPartyNum

8.1006.2.5 **arrCallEndReason\*** voiceGetAllCallInfo::pArrCallEndReason

8.1006.2.6 **arrCallInfo\*** voiceGetAllCallInfo::pArrCallInfo

8.1006.2.7 **arrConnectPartyNum\*** voiceGetAllCallInfo::pArrConnectPartyNum

8.1006.2.8 **arrDiagInfo\*** voiceGetAllCallInfo::pArrDiagInfo

8.1006.2.9 **arrRedirPartyNum\*** voiceGetAllCallInfo::pArrRedirPartyNum

8.1006.2.10 **arrRemotePartyName\*** voiceGetAllCallInfo::pArrRemotePartyName

8.1006.2.11 **arrRemotePartyNum\*** voiceGetAllCallInfo::pArrRemotePartyNum

8.1006.2.12 **arrSvcOption\*** voiceGetAllCallInfo::pArrSvcOption

8.1006.2.13 **arrUUSInfo\*** voiceGetAllCallInfo::pArrUUSInfo

8.1006.2.14 **BYTE\*** voiceGetAllCallInfo::pOTASPStatus



8.1006.2.15 **BYTE\*** voiceGetAllCallInfo::pVoicePrivacy

## 8.1007 voiceGetCallBarringReq Struct Reference

### Data Fields

- [BYTE reason](#)
- [BYTE \\* pSvcClass](#)

### 8.1007.1 Detailed Description

This structure contains Voice Get Call Barring Request Parameters

#### Parameters

<i>reason</i>	<ul style="list-style-type: none"><li>• Call Barring Reason</li><li>• Values:<ul style="list-style-type: none"><li>– 0x07 - QMI_VOICE_REASON_BARR_ALLOUTGOING - All outgoing</li><li>– 0x08 - QMI_VOICE_REASON_BARR_OUTGOINGINT - Outgoing internal</li><li>– 0x09 - QMI_VOICE_REASON_BARR_OUTGOINGINTEXTOHOM - Outgoing external to home</li><li>– 0x0A - QMI_VOICE_REASON_BARR_ALLINCOMING - All incoming</li><li>– 0x0B - QMI_VOICE_REASON_BARR_INCOMINGROAMING - Roaming incoming</li><li>– 0x0C - QMI_VOICE_REASON_BARR_ALLBARRING - All calls are barred</li><li>– 0x0D - QMI_VOICE_REASON_BARR_ALLOUTGOINGBARRING - All outgoing calls are barred</li><li>– 0x0E - QMI_VOICE_REASON_BARR_ALLINCOMINGBARRING - All incoming calls are barred</li></ul></li></ul>
---------------	--

<i>pSvcClass</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Service class is a combination (sum) of information class constants (optional)</li> <li>• See <a href="#">qaGobiApiTableSupServiceInfoClasses.h</a> for service classes.</li> <li>• Service Class is set to 0 if call waiting is not active for any of the information classes.</li> <li>• 0xFF,if Not Available</li> </ul>
---------------------------	--

## 8.1007.2 Field Documentation

8.1007.2.1 **BYTE\*** voiceGetCallBarringReq::pSvcClass

8.1007.2.2 **BYTE** voiceGetCallBarringReq::reason

## 8.1008 voiceGetCallBarringResp Struct Reference

### Data Fields

- **BYTE \*** pSvcClass
- **WORD \*** pFailCause
- **alphaIDInfo \*** pAlphaIDInfo
- **BYTE \*** pCCResType
- **BYTE \*** pCallID
- **ccSUPSType \*** pCCSUPSType

### 8.1008.1 Detailed Description

This structure contains Voice Get Call Barring Response Parameters

#### Parameters

<i>pSvcClass</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Service class is a combination (sum) of information class constants (optional)</li> <li>• See <a href="#">qaGobiApiTableSupServiceInfoClasses.h</a> for service classes.</li> <li>• Service Class is set to 0 if call waiting is not active for any of the information classes.</li> <li>• 0xFF,if Not Available</li> </ul>
<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF,if Not Available</li> </ul>

<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResType</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

**Note**

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

**8.1008.2 Field Documentation**

8.1008.2.1 **alphaIDInfo\*** voiceGetCallBarringResp::pAlphaIDInfo

8.1008.2.2 **BYTE\*** voiceGetCallBarringResp::pCallID

8.1008.2.3 **BYTE\*** voiceGetCallBarringResp::pCCResType

8.1008.2.4 **ccSUPSType\*** voiceGetCallBarringResp::pCCSUPSType

8.1008.2.5 **WORD\*** voiceGetCallBarringResp::pFailCause

8.1008.2.6 **BYTE\*** voiceGetCallBarringResp::pSvcClass

**8.1009 voiceGetCallFWReq Struct Reference****Data Fields**

- [BYTE Reason](#)
- [BYTE \\*](#) [pSvcClass](#)

### 8.1009.1 Detailed Description

This structure contains Voice Get Call Forwarding Status Request Parameters

## Parameters

<i>Reason</i>	<ul style="list-style-type: none"> <li>• Call Forwarding Reason</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - QMI_VOICE_REASON_FWDREASON_UNCONDITIONAL - Unconditional call forwarding</li> <li>– 0x02 - QMI_VOICE_REASON_FWDREASON_MOBILEBUSY - Forward when the mobile is busy</li> <li>– 0x03 - QMI_VOICE_REASON_FWDREASON_NOREPLY - Forward when there is no reply</li> <li>– 0x04 - QMI_VOICE_REASON_FWDREASON_UNREACHABLE - Forward when the call is unreachable</li> <li>– 0x05 - QMI_VOICE_REASON_FWDREASON_ALLFORWARDING - All forwarding</li> <li>– 0x06 - QMI_VOICE_REASON_FWDREASON_ALLCONDITIONAL - All conditional forwarding</li> </ul> </li> </ul>
<i>pSvc-Class(optional)</i>	<ul style="list-style-type: none"> <li>• Service Class is a combination (sum) of information class constants</li> <li>• See <a href="#">qaGobiApiTableSupServiceInfoClasses.h</a> for service classes.</li> </ul>

## 8.1009.2 Field Documentation

8.1009.2.1 BYTE\* voiceGetCallFWReq::pSvcClass

8.1009.2.2 BYTE voiceGetCallFWReq::Reason

## 8.1010 voiceGetCallFWResp Struct Reference

## Data Fields

- [getCallFWInfo](#) \* [pGetCallFWInfo](#)
- [WORD](#) \* [pFailCause](#)
- [alphaIDInfo](#) \* [pAlphaIDInfo](#)
- [BYTE](#) \* [pCCResType](#)
- [BYTE](#) \* [pCallID](#)
- [ccSUPSType](#) \* [pCCSUPSType](#)
- [getCallFWExtInfo](#) \* [pGetCallFWExtInfo](#)

## 8.1010.1 Detailed Description

This structure contains Voice Get Call Forwarding Status Response Parameters

## Parameters

<i>pGetCallFWInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">getCallFWInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">getCallFWInfo</a> for more information</li> </ul> </li> </ul>
<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF, if Not Available</li> </ul>
<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResType</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>
<i>pGetCallFWExt-Info</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">getCallFWExtInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">getCallFWExtInfo</a> for more information</li> </ul> </li> </ul>

**Note**

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

**8.1010.2 Field Documentation****8.1010.2.1 alphaIDInfo\* voiceGetCallFWResp::pAlphaIDInfo**

8.1010.2.2 **BYTE\*** voiceGetCallFWResp::pCallID

8.1010.2.3 **BYTE\*** voiceGetCallFWResp::pCCResType

8.1010.2.4 **ccSUPSType\*** voiceGetCallFWResp::pCCSUPSType

8.1010.2.5 **WORD\*** voiceGetCallFWResp::pFailCause

8.1010.2.6 **getCallFWExtInfo\*** voiceGetCallFWResp::pGetCallFWExtInfo

8.1010.2.7 **getCallFWInfo\*** voiceGetCallFWResp::pGetCallFWInfo

## 8.1011 voiceGetCallWaitInfo Struct Reference

### Data Fields

- **BYTE \*** pSvcClass
- **WORD \*** pFailCause
- **alphaIDInfo \*** pAlphaIDInfo
- **BYTE \*** pCCResType
- **BYTE \*** pCallID
- **ccSUPSType \*** pCCSUPSType

### 8.1011.1 Detailed Description

This structure contains Voice Get Call Waiting Response Parameters

#### Parameters

<i>pSvcClass</i> [ <i>IN/OUT</i> ]	<ul style="list-style-type: none"> <li>• Service class is a combination (sum) of information class constants (optional)</li> <li>• See <a href="#">qaGobiApiTableSupServiceInfoClasses.h</a> for service classes.</li> <li>• Service Class is set to 0 if call waiting is not active for any of the information classes.</li> <li>• 0xFF,if Not Available</li> </ul>
<i>pFailCause</i> [ <i>OUT</i> ]	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF,if Not Available</li> </ul>
<i>pAlphaIDInfo</i> [ <i>OUT</i> ]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>

<i>pCCResType[OUT]</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCallID[OUT]</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType[OUT]</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

**Note**

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

**8.1011.2 Field Documentation**

8.1011.2.1 **alphaIDInfo\*** voiceGetCallWaitInfo::pAlphaIDInfo

8.1011.2.2 **BYTE\*** voiceGetCallWaitInfo::pCallID

8.1011.2.3 **BYTE\*** voiceGetCallWaitInfo::pCCResType

8.1011.2.4 **ccSUPSType\*** voiceGetCallWaitInfo::pCCSUPSType

8.1011.2.5 **WORD\*** voiceGetCallWaitInfo::pFailCause

8.1011.2.6 **BYTE\*** voiceGetCallWaitInfo::pSvcClass

**8.1012 voiceGetCLIPResp Struct Reference****Data Fields**

- [CLIPResp](#) \* [pCLIPResp](#)
- [WORD](#) \* [pFailCause](#)
- [alphaIDInfo](#) \* [pAlphaIDInfo](#)
- [BYTE](#) \* [pCCResType](#)
- [BYTE](#) \* [pCallID](#)
- [ccSUPSType](#) \* [pCCSUPSType](#)



### 8.1012.1 Detailed Description

This structure contains Voice Get Calling Line Identification Presentation(CLIP) Response Parameters

## Parameters

<i>pCLIPResp</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">CLIPResp</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">CLIPResp</a> for more information</li> </ul> </li> </ul>
<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF,if Not Available</li> </ul>
<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResType</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResultType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

## 8.1012.2 Field Documentation

8.1012.2.1 [alphaIDInfo\\*](#) [voiceGetCLIPResp::pAlphaIDInfo](#)

8.1012.2.2 [BYTE\\*](#) [voiceGetCLIPResp::pCallID](#)

8.1012.2.3 [BYTE\\*](#) [voiceGetCLIPResp::pCCResType](#)

8.1012.2.4 `ccSUPSType*` `voiceGetCLIPResp::pCCSUPSType`

8.1012.2.5 `CLIPResp*` `voiceGetCLIPResp::pCLIPResp`

8.1012.2.6 `WORD*` `voiceGetCLIPResp::pFailCause`

## 8.1013 voiceGetCLIRResp Struct Reference

### Data Fields

- [CLIRResp](#) \* [pCLIRResp](#)
- [WORD](#) \* [pFailCause](#)
- [alphaIDInfo](#) \* [pAlphaIDInfo](#)
- [BYTE](#) \* [pCCResType](#)
- [BYTE](#) \* [pCallID](#)
- [ccSUPSType](#) \* [pCCSUPSType](#)

### 8.1013.1 Detailed Description

This structure contains Voice Get Calling Line Identification Restriction (CLIR) Response Parameters

#### Parameters

<i>pCLIRResp</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">CLIRResp</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">CLIRResp</a> for more information</li> </ul> </li> </ul>
<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF,if Not Available</li> </ul>
<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResType</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResultType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

**Note**

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

**8.1013.2 Field Documentation**

**8.1013.2.1** **alphaIDInfo\*** voiceGetCLIRResp::pAlphaIDInfo

**8.1013.2.2** **BYTE\*** voiceGetCLIRResp::pCallID

**8.1013.2.3** **BYTE\*** voiceGetCLIRResp::pCCResType

**8.1013.2.4** **ccSUPSType\*** voiceGetCLIRResp::pCCSUPSType

**8.1013.2.5** **CLIRResp\*** voiceGetCLIRResp::pCLIRResp

**8.1013.2.6** **WORD\*** voiceGetCLIRResp::pFailCause

**8.1014 voiceGetCNAPResp Struct Reference****Data Fields**

- [CNAPResp](#) \* pCNAPResp
- [WORD](#) \* pFailCause
- [alphaIDInfo](#) \* pAlphaIDInfo
- [BYTE](#) \* pCCResType
- [BYTE](#) \* pCallID
- [ccSUPSType](#) \* pCCSUPSType

**8.1014.1 Detailed Description**

This structure contains Voice Get Calling Name Presentation(CNAP) Response Parameters

## Parameters

<i>pCNAPResp</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">CNAPResp</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">CNAPResp</a> for more information</li> </ul> </li> </ul>
<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF,if Not Available</li> </ul>
<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResType</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResultType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

## 8.1014.2 Field Documentation

8.1014.2.1 [alphaIDInfo\\*](#) voiceGetCNAPResp::pAlphaIDInfo

8.1014.2.2 [BYTE\\*](#) voiceGetCNAPResp::pCallID

8.1014.2.3 [BYTE\\*](#) voiceGetCNAPResp::pCCResType

8.1014.2.4 **ccSUPSType\*** voiceGetCNAPResp::pCCSUPSType

8.1014.2.5 **CNAPResp\*** voiceGetCNAPResp::pCNAPResp

8.1014.2.6 **WORD\*** voiceGetCNAPResp::pFailCause

## 8.1015 voiceGetCOLPResp Struct Reference

### Data Fields

- [COLPResp](#) \* [pCOLPResp](#)
- [WORD](#) \* [pFailCause](#)
- [alphaIDInfo](#) \* [pAlphaIDInfo](#)
- [BYTE](#) \* [pCCResType](#)
- [BYTE](#) \* [pCallID](#)
- [ccSUPSType](#) \* [pCCSUPSType](#)

### 8.1015.1 Detailed Description

This structure contains Voice Get Connected Line Identification Presentation(COLP) Response Parameters

#### Parameters

<i>pCOLPResp</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">COLPResp</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">COLPResp</a> for more information</li> </ul> </li> </ul>
<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF,if Not Available</li> </ul>
<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResType</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResultType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

**Note**

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

**8.1015.2 Field Documentation**

8.1015.2.1 **alphaIDInfo\*** voiceGetCOLPResp::pAlphaIDInfo

8.1015.2.2 **BYTE\*** voiceGetCOLPResp::pCallID

8.1015.2.3 **BYTE\*** voiceGetCOLPResp::pCCResType

8.1015.2.4 **ccSUPSType\*** voiceGetCOLPResp::pCCSUPSType

8.1015.2.5 **COLPResp\*** voiceGetCOLPResp::pCOLPResp

8.1015.2.6 **WORD\*** voiceGetCOLPResp::pFailCause

**8.1016 voiceGetCOLRResp Struct Reference****Data Fields**

- [COLRResp](#) \* [pCOLRResp](#)
- [WORD](#) \* [pFailCause](#)
- [alphaIDInfo](#) \* [pAlphaIDInfo](#)
- [BYTE](#) \* [pCCResType](#)
- [BYTE](#) \* [pCallID](#)
- [ccSUPSType](#) \* [pCCSUPSType](#)

**8.1016.1 Detailed Description**

This structure contains Voice Get Connected Line Identification Restriction(COLR) Response Parameters

## Parameters

<i>pCOLRResp</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">COLRResp</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">COLRResp</a> for more information</li> </ul> </li> </ul>
<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF,if Not Available</li> </ul>
<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResType</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResultType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

## 8.1016.2 Field Documentation

8.1016.2.1 **alphaIDInfo\*** voiceGetCOLRResp::pAlphaIDInfo

8.1016.2.2 **BYTE\*** voiceGetCOLRResp::pCallID

8.1016.2.3 **BYTE\*** voiceGetCOLRResp::pCCResType



8.1016.2.4 ccSUPSType\* voiceGetCOLRResp::pCCSUPSType

8.1016.2.5 COLRResp\* voiceGetCOLRResp::pCOLRResp

8.1016.2.6 WORD\* voiceGetCOLRResp::pFailCause

## 8.1017 voiceGetConfigReq Struct Reference

### Data Fields

- BYTE \* pAutoAnswer
- BYTE \* pAirTimer
- BYTE \* pRoamTimer
- BYTE \* pTTYMode
- BYTE \* pPrefVoiceSO
- BYTE \* pAMRStatus
- BYTE \* pPrefVoicePrivacy
- BYTE \* pNamID
- BYTE \* pVoiceDomainPref

### 8.1017.1 Detailed Description

This structure contains Voice Get Configuration Request Parameters

#### Parameters

<i>pAuto-Answer(optional)</i>	<ul style="list-style-type: none"> <li>• Indicator to retrieve the Auto Answer Information. <ul style="list-style-type: none"> <li>– 0x01 - Include auto answer information</li> </ul> </li> </ul>
<i>pAir-Timer(optional)</i>	<ul style="list-style-type: none"> <li>• Indicator to retrieve the Air Timer Information. <ul style="list-style-type: none"> <li>– 0x01 - Include air calls timer count information</li> </ul> </li> <li>• Currently Not Supported.</li> </ul>
<i>pRoam-Timer(optional)</i>	<ul style="list-style-type: none"> <li>• Indicator to retrieve the Roam Timer Information. <ul style="list-style-type: none"> <li>– 0x01 - Include roam calls timer information</li> </ul> </li> <li>• Currently Not Supported.</li> </ul>
<i>pTTY-Mode(optional)</i>	<ul style="list-style-type: none"> <li>• Indicator to retrieve the TTY Mode Information. <ul style="list-style-type: none"> <li>– 0x01 - Include TTY configuration status information</li> </ul> </li> </ul>

<i>pPrefVoiceSO(optional)</i>	<ul style="list-style-type: none"> <li>Indicator to retrieve the Preferred Voice SO Information. <ul style="list-style-type: none"> <li>0x01 - Include preferred voice configuration status information</li> </ul> </li> <li>Currently Not Supported.</li> </ul>
<i>pAMR-Status(optional)</i>	<ul style="list-style-type: none"> <li>Indicator to retrieve the AMR Status Information. <ul style="list-style-type: none"> <li>0x01 - Include AMR status information</li> </ul> </li> </ul>
<i>pPrefVoice-Privacy(optional)</i>	<ul style="list-style-type: none"> <li>Indicator to retrieve the Preferred Voice Privacy Information. <ul style="list-style-type: none"> <li>0x01 - Include preferred voice privacy status information</li> </ul> </li> </ul>
<i>pNamID(optional)</i>	<ul style="list-style-type: none"> <li>Index of the Number Assignment Module Index (CDMA subscription) to be configured</li> <li>Range: 0 to 3.</li> <li>Some modems support only 1 or 2 NAMs.</li> <li>The NAM Index is valid only when the request contains at least one of Air Timer, Roam Timer, and Preferred Voice SO.</li> <li>If no nam_id value is specified in the request, the default value is 0.</li> </ul>
<i>pVoiceDomain-Pref(optional)</i>	<ul style="list-style-type: none"> <li>Indicator to retrieve the Preferred Voice <a href="#">Domain</a> Information. <ul style="list-style-type: none"> <li>0x01 - Include voice domain preference information</li> </ul> </li> </ul>

**Note**

Using NULL for the pointers would make sure that the parameter is not returned.

**8.1017.2 Field Documentation**

8.1017.2.1 **BYTE\*** voiceGetConfigReq::pAirTimer

8.1017.2.2 **BYTE\*** voiceGetConfigReq::pAMRStatus

8.1017.2.3 **BYTE\*** voiceGetConfigReq::pAutoAnswer

8.1017.2.4 **BYTE\*** voiceGetConfigReq::pNamID

8.1017.2.5 **BYTE\*** voiceGetConfigReq::pPrefVoicePrivacy

8.1017.2.6 **BYTE\*** voiceGetConfigReq::pPrefVoiceSO

8.1017.2.7 **BYTE\*** voiceGetConfigReq::pRoamTimer

8.1017.2.8 **BYTE\*** voiceGetConfigReq::pTTYMode

8.1017.2.9 **BYTE\*** voiceGetConfigReq::pVoiceDomainPref

## 8.1018 voiceGetConfigResp Struct Reference

### Data Fields

- **BYTE \*** [pAutoAnswerStat](#)
- **airTimer \*** [pAirTimerCnt](#)
- **roamTimer \*** [pRoamTimerCnt](#)
- **BYTE \*** [pCurrTTYMode](#)
- **prefVoiceSO \*** [pCurPrefVoiceSO](#)
- **curAMRConfig \*** [pCurAMRConfig](#)
- **BYTE \*** [pCurVoicePrivacyPref](#)
- **BYTE \*** [pCurVoiceDomainPref](#)

### 8.1018.1 Detailed Description

This structure contains Voice Get Configuration Response Parameters.

#### Parameters

<i>pAutoAnswer- Stat(optional)</i>	<ul style="list-style-type: none"> <li>• Auto Answer Status</li> <li>• Value returned is read from NV_AUTO_ANSWER_I. <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pAirTimer- Cnt(optional)</i>	<ul style="list-style-type: none"> <li>• Air Timer Count</li> <li>• Value returned is read from NV_AIR_CNT_I.</li> <li>• See <a href="#">airTimer</a> for more information</li> </ul>
<i>pRoamTimer- Cnt(optional)</i>	<ul style="list-style-type: none"> <li>• Roam Timer Count</li> <li>• Value returned is read from NV_ROAM_CNT_I.</li> <li>• See <a href="#">roamTimer</a> for more information</li> </ul>

<i>pCurrTTY-Mode(optional)</i>	<ul style="list-style-type: none"> <li>• Current TTY Mode</li> <li>• Value returned is read from NV_TTY_I. <ul style="list-style-type: none"> <li>– 0x00 - TTY_MODE_FULL - Full</li> <li>– 0x01 - TTY_MODE_VCO - Voice carry over</li> <li>– 0x02 - TTY_MODE_HCO - Hearing carry over</li> <li>– 0x03 - TTY_MODE_OFF - Off</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCurPrefVoiceSO(optional)</i>	<ul style="list-style-type: none"> <li>• Current Preferred Voice SO</li> <li>• Value returned is read from NV_PREF_VOICE_SO_I.</li> <li>• See <a href="#">prefVoiceSO</a> for more information</li> </ul>
<i>pCurAMR-Config(optional)</i>	<ul style="list-style-type: none"> <li>• Current Adaptive Multi-Rate Configuration.</li> <li>• Values returned are read from NV_GSM_ARM_CALL_CONFIG_I and NV_UMTS_A-MR_CODEEC_PREFERENCE_CONFIG_I.</li> <li>• See <a href="#">curAMRConfig</a> for more information</li> </ul>
<i>pCurVoice-Privacy-Pref(optional)</i>	<ul style="list-style-type: none"> <li>• Current Voice Privacy Preference</li> <li>• Value returned is read from NV_VOICE_PRIV_I. <ul style="list-style-type: none"> <li>– 0x00 - Standard privacy</li> <li>– 0x01 - Enhanced privacy</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCurVoice-Domain-Pref(optional)</i>	<ul style="list-style-type: none"> <li>• Current Voice <a href="#">Domain</a> Preference. <ul style="list-style-type: none"> <li>– 0x00 - Circuit-switched (CS) only</li> <li>– 0x01 - Packet-switched (PS) only</li> <li>– 0x02 - CS is preferred; PS is secondary</li> <li>– 0x03 - PS is preferred; CS is secondary</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>

**Note**

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

**8.1018.2 Field Documentation****8.1018.2.1 airTimer\* voiceGetConfigResp::pAirTimerCnt**

- 8.1018.2.2 **BYTE\*** voiceGetConfigResp::pAutoAnswerStat
- 8.1018.2.3 **curAMRConfig\*** voiceGetConfigResp::pCurAMRConfig
- 8.1018.2.4 **prefVoiceSO\*** voiceGetConfigResp::pCurPrefVoiceSO
- 8.1018.2.5 **BYTE\*** voiceGetConfigResp::pCurrTTYMode
- 8.1018.2.6 **BYTE\*** voiceGetConfigResp::pCurVoiceDomainPref
- 8.1018.2.7 **BYTE\*** voiceGetConfigResp::pCurVoicePrivacyPref
- 8.1018.2.8 **roamTimer\*** voiceGetConfigResp::pRoamTimerCnt

## 8.1019 voiceIndicationRegisterInfo Struct Reference

### Data Fields

- **BYTE \*** [pRegDTMFEvents](#)
- **BYTE \*** [pRegVoicePrivacyEvents](#)
- **BYTE \*** [pSuppsNotifEvents](#)

### 8.1019.1 Detailed Description

This structure contains parameters of Indication Register Information

#### Parameters

<i>pRegDTMF-Events(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For DTMF Events.</li> <li>• When this registration is enabled, the device learns of DTMF events via the QMI_VOICE_DTMF_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>pRegVoice-Privacy-Events(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For Voice Privacy Events.</li> <li>• When this registration is enabled, the device learns of DTMF events via the QMI_VOICE_PRIVACY_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>

<i>pSuppsNotif-Events(optional)</i>	<ul style="list-style-type: none"> <li>• Registration Indication For Supplementary Service Notification Events.</li> <li>• When this registration is enabled, the device learns of DTMF events via the QMI_VOICE_SUPS_NOTIFICATION_IND indication. <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
-------------------------------------	--

**Note**

One of the optional parameter is mandatory to be present in the request.

**8.1019.2 Field Documentation**

**8.1019.2.1** **BYTE\*** `voiceIndicationRegisterInfo::pRegDTMFEvents`

**8.1019.2.2** **BYTE\*** `voiceIndicationRegisterInfo::pRegVoicePrivacyEvents`

**8.1019.2.3** **BYTE\*** `voiceIndicationRegisterInfo::pSuppsNotifEvents`

**8.1020 voiceInfoRec Struct Reference****Data Fields**

- [BYTE](#) `callID`
- [signalInfo](#) \* [pSignalInfo](#)
- [callerIDInfo](#) \* [pCallerIDInfo](#)
- [BYTE](#) \* [pDispInfo](#)
- [BYTE](#) \* [pExtDispInfo](#)
- [BYTE](#) \* [pCallerNameInfo](#)
- [BYTE](#) \* [pCallWaitInd](#)
- [connectNumInfo](#) \* [pConnectNumInfo](#)
- [connectNumInfo](#) \* [pCallingPartyInfo](#)
- [calledPartyInfo](#) \* [pCalledPartyInfo](#)
- [redirNumInfo](#) \* [pRedirNumInfo](#)
- [BYTE](#) \* [pCLIRCause](#)
- [NSSAudioCtrl](#) \* [pNSSAudioCtrl](#)
- [BYTE](#) \* [pNSSRelease](#)
- [lineCtrlInfo](#) \* [pLineCtrlInfo](#)
- [extDispRecInfo](#) \* [pExtDispRecInfo](#)

**8.1020.1 Detailed Description**

This structure contains Voice record Information

## Parameters

<i>callID</i>	[Mandatory] <ul style="list-style-type: none"> <li>• Call identifier for the call.</li> </ul>
<i>pSignalInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Signal Information</li> <li>• See <a href="#">signalInfo</a> for more information</li> </ul>
<i>pCallerIDInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Caller ID Information</li> <li>• See <a href="#">callerIDInfo</a> for more information</li> </ul>
<i>pDispInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Display Information</li> </ul>
<i>pExtDispInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Extended Display Information</li> </ul>
<i>pCallerNameInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Caller Name Information</li> </ul>
<i>pCallWaitInd</i> [-Optional]	<ul style="list-style-type: none"> <li>• Call Waiting Indicator</li> </ul>
<i>pConnectNumInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Connected Number Information</li> <li>• see <a href="#">connectNumInfo</a> for more information</li> </ul>
<i>pCallingPartyInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Calling Party Number Information</li> <li>• This structure is having exactly same elements as <a href="#">connectNumInfo</a></li> <li>• see <a href="#">connectNumInfo</a> for more information</li> </ul>
<i>pCalledPartyInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Called Party Number Information</li> <li>• see <a href="#">calledPartyInfo</a> for more information</li> </ul>
<i>pRedirNumInfo</i> [-Optional]	<ul style="list-style-type: none"> <li>• Redirecting Number Information</li> <li>• see <a href="#">redirNumInfo</a> for more information</li> </ul>
<i>pCLIRCause</i> [-Optional]	<ul style="list-style-type: none"> <li>• National Supplementary Services - CLIR</li> <li>• see <a href="#">NSSAudioCtrl</a> for more information</li> </ul>

<i>pNSSAudioCtrl[-Optional]</i>	<ul style="list-style-type: none"> <li>National Supplementary Services - Audio Control</li> </ul>
<i>pNSSRelease[-Optional]</i>	<ul style="list-style-type: none"> <li>National Supplementary Services - Release</li> </ul>
<i>pLineCtrlInfo[-Optional]</i>	<ul style="list-style-type: none"> <li>Line Control Information</li> <li>see <a href="#">lineCtrlInfo</a> for more information</li> </ul>
<i>pExtDispRecInfo[Optional]</i>	<ul style="list-style-type: none"> <li>Extended Display Record Information</li> <li>see <a href="#">extDispRecInfo</a> for more information</li> </ul>

## 8.1020.2 Field Documentation

8.1020.2.1 **BYTE** `voicelInfoRec::callID`

8.1020.2.2 **calledPartyInfo\*** `voicelInfoRec::pCalledPartyInfo`

8.1020.2.3 **callerIDInfo\*** `voicelInfoRec::pCallerIDInfo`

8.1020.2.4 **BYTE\*** `voicelInfoRec::pCallerNameInfo`

8.1020.2.5 **connectNumInfo\*** `voicelInfoRec::pCallingPartyInfo`

8.1020.2.6 **BYTE\*** `voicelInfoRec::pCallWaitInd`

8.1020.2.7 **BYTE\*** `voicelInfoRec::pCLIRCause`

8.1020.2.8 **connectNumInfo\*** `voicelInfoRec::pConnectNumInfo`

8.1020.2.9 **BYTE\*** `voicelInfoRec::pDisplInfo`

8.1020.2.10 **BYTE\*** `voicelInfoRec::pExtDisplInfo`

8.1020.2.11 **extDispRecInfo\*** `voicelInfoRec::pExtDispRecInfo`

8.1020.2.12 **lineCtrlInfo\*** `voicelInfoRec::pLineCtrlInfo`

8.1020.2.13 **NSSAudioCtrl\*** `voicelInfoRec::pNSSAudioCtrl`

8.1020.2.14 **BYTE\*** `voicelInfoRec::pNSSRelease`

8.1020.2.15 **redirNumInfo\*** `voicelInfoRec::pRedirNumInfo`

8.1020.2.16 **signalInfo\*** `voicelInfoRec::pSignalInfo`

## 8.1021 voiceManageCallsReq Struct Reference



## Data Fields

- [BYTE SUPSType](#)
- [BYTE \\* pCallID](#)

### 8.1021.1 Detailed Description

This structure contains Manage Calls Information.

#### Parameters

<i>SUPSType</i>	<ul style="list-style-type: none"><li>• Supplementary service type during the call.<ul style="list-style-type: none"><li>– 0x01 - SUPS_TYPE_RELEASE_HELD_OR_WAITING<ul style="list-style-type: none"><li>* Release is held or waiting</li></ul></li><li>– 0x02 - SUPS_TYPE_RELEASE_ACTIVE_ACCEPT_HELD_OR_WAITING<ul style="list-style-type: none"><li>* Release is active and accepting held or waiting</li></ul></li><li>– 0x03 - SUPS_TYPE_HOLD_ACTIVE_ACCEPT_WAITING_OR_HELD<ul style="list-style-type: none"><li>* Hold is active and accepting waiting or held</li></ul></li><li>– 0x04 - SUPS_TYPE_HOLD_ALL_EXCEPT_SPECIFIED_CALL<ul style="list-style-type: none"><li>* Hold all calls except a specified one</li></ul></li><li>– 0x05 - SUPS_TYPE_MAKE_CONFERENCE_CALL<ul style="list-style-type: none"><li>* Make a conference call</li></ul></li><li>– 0x06 - SUPS_TYPE_EXPLICIT_CALL_TRANSFER<ul style="list-style-type: none"><li>* Explicit call transfer</li></ul></li><li>– 0x07 - SUPS_TYPE_CCBS_ACTIVATION<ul style="list-style-type: none"><li>* Activate completion of calls to busy subscriber</li></ul></li><li>– 0x08 - SUPS_TYPE_END_ALL_CALLS<ul style="list-style-type: none"><li>* End all calls</li></ul></li><li>– 0x09 - SUPS_TYPE_RELEASE_SPECIFIED_CALL<ul style="list-style-type: none"><li>* Release a specified call</li></ul></li></ul></li></ul>
-----------------	--

<i>pCallID[Optional]</i>	<ul style="list-style-type: none"> <li>• Applicable only for SUPSType 0x04, 0x07, and 0x09</li> </ul>
--------------------------	---

## 8.1021.2 Field Documentation

8.1021.2.1 **BYTE\*** voiceManageCallsReq::pCallID

8.1021.2.2 **BYTE** voiceManageCallsReq::SUPSType

## 8.1022 voiceManageCallsResp Struct Reference

### Data Fields

- **WORD\*** pFailCause

### 8.1022.1 Detailed Description

This structure contains Failure cause Information. Populated when API Fails.

#### Parameters

<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary service failure causes (optional, supply NULL if not required).</li> <li>• See Table8 <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for supplementary services failure cause <ul style="list-style-type: none"> <li>– 0xFFFF is the value when the information is not received from device</li> </ul> </li> </ul>
-------------------	--

## 8.1022.2 Field Documentation

8.1022.2.1 **WORD\*** voiceManageCallsResp::pFailCause

## 8.1023 voiceOrigUSSDNoWaitInfo Struct Reference

### Data Fields

- struct [USSInfo](#) USSInformation

### 8.1023.1 Detailed Description

This structure contains Orig USSD No Wait Information Parameters.

#### Parameters

<i>USSInformation</i>	<ul style="list-style-type: none"> <li>• See <a href="#">USSInfo</a> for more information.</li> </ul>
-----------------------	---

## 8.1023.2 Field Documentation

8.1023.2.1 struct USSInfo voiceOrigUSSDNoWaitInfo::USSInformation

## 8.1024 voiceOTASPStatusInfo Struct Reference

## Data Fields

- [BYTE callID](#)
- [BYTE OTASPStatus](#)

## 8.1024.1 Detailed Description

This structure consist of OTASP or OTAPA event params

## Parameters

<i>callID</i>	<ul style="list-style-type: none"> <li>• Call identifier for the call.</li> </ul>
<i>OTASPStatus</i>	<ul style="list-style-type: none"> <li>• OTASP status for the OTASP call. Values: <ul style="list-style-type: none"> <li>– 0x00 - OTASP_STATUS_SPL_UNLOCKED.SPL unlocked; only for user-initiated OTASP</li> <li>– 0x01 - OTASP_STATUS_SPRC_RETRIES_EXCEEDED. SPC retries exceeded; only for user-initiated OTASP</li> <li>– 0x02 - OTASP_STATUS_AKEY_EXCHANGED.A-key exchanged; only for user-initiated OTASP</li> <li>– 0x03 - OTASP_STATUS_SSD_UPDATED. SSD updated; for both user-initiated OTASP and network-initiated OTASP (OTAPA)</li> <li>– 0x04 - OTASP_STATUS_NAM_DOWNLOADED - NAM downloaded; only for user-initiated OTASP</li> <li>– 0x05 - OTASP_STATUS_MDN_DOWNLOADED - MDN downloaded; only for user-initiated OTASP</li> <li>– 0x06 - OTASP_STATUS_IMSI_DOWNLOADED - IMSI downloaded; only for user-initiated OTASP</li> <li>– 0x07 - OTASP_STATUS_PRL_DOWNLOADED - PRL downloaded; only for user-initiated OTASP</li> <li>– 0x08 - OTASP_STATUS_COMMITTED - Commit successful; only for user-initiated OTASP</li> <li>– 0x09 - OTASP_STATUS_OTAPA_STARTED - OTAPA started; only for network-initiated OTASP(OTAPA)</li> <li>– 0x0A - OTASP_STATUS_OTAPA_STOPPED - OTAPA stopped; only for network-initiated OTASP(OTAPA)</li> <li>– 0x0B - OTASP_STATUS_OTAPA_ABORTED - OTAPA aborted; only for network-initiated OTASP(OTAPA)</li> <li>– 0x0C - OTASP_STATUS_OTAPA_COMMITTED - OTAPA committed; only for network-initiated OTASP(OTAPA)</li> </ul> </li> </ul>

## 8.1024.2 Field Documentation

8.1024.2.1 BYTE voiceOTASPStatusInfo::callID

8.1024.2.2 BYTE voiceOTASPStatusInfo::OTASPStatus

## 8.1025 voicePrivacyInfo Struct Reference

### Data Fields

- [BYTE callID](#)
- [BYTE voicePrivacy](#)

### 8.1025.1 Detailed Description

Contains the parameters passed for SLQSVoiceSetPrivacyChangeCallBack by the device.

#### Parameters

<i>callID</i>	<ul style="list-style-type: none"> <li>• Unique identifier of the call for which the voice privacy is applicable. (mandatory)</li> </ul>
<i>voicePrivacy</i>	<ul style="list-style-type: none"> <li>• Voice Privacy (mandatory) <ul style="list-style-type: none"> <li>– 0x00 - VOICE_PRIVACY_STANDARD - Standard privacy</li> <li>– 0x01 - VOICE_PRIVACY_ENHANCED - Enhanced privacy</li> </ul> </li> </ul>

#### Note

None

## 8.1025.2 Field Documentation

8.1025.2.1 BYTE voicePrivacyInfo::callID

8.1025.2.2 BYTE voicePrivacyInfo::voicePrivacy

## 8.1026 voiceSetAllCallStatusCbklInfo Struct Reference

### Data Fields

- [arrCallInfo arrCallInfomation](#)
- [arrRemotePartyNum \\* pArrRemotePartyNum](#)
- [arrRemotePartyName \\* pArrRemotePartyName](#)
- [arrAlertingType \\* pArrAlertingType](#)
- [arrSvcOption \\* pArrSvcOption](#)
- [arrCallEndReason \\* pArrCallEndReason](#)
- [arrAlphaID \\* pArrAlphaID](#)
- [arrConnectPartyNum \\* pArrConnectPartyNum](#)
- [arrDiagInfo \\* pArrDiagInfo](#)
- [arrCalledPartyNum \\* pArrCalledPartyNum](#)

- [arrRedirPartyNum](#) \* [pArrRedirPartyNum](#)
- [arrAlertingPattern](#) \* [pArrAlertingPattern](#)

### 8.1026.1 Detailed Description

This structure contains VoiceCall Information parameters. [arrCallInfomation](#) will be populated in case of change in the call information. Other paramters are optional therefore are populated based on device and technology type being used.

#### Parameters

<i>arrCallInfomation</i>	[mandatory] <ul style="list-style-type: none"> <li>• Array of Call Information This must be populated if Indication is received See <a href="#">arrCallInfo</a> for more information.</li> <li>– Applicable for both "3GPP/3GPP2"</li> </ul>
<i>pArrRemote-PartyNum</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Remote Party Name.( NULL when not present) See <a href="#">arrRemotePartyNum</a> for more information.</li> <li>– Applicable only for "3GPP/3GPP2"</li> </ul>
<i>pArrRemote-PartyName</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Alerting Type.( NULL when not present) See <a href="#">arrRemotePartyName</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>
<i>pArrAlertingType</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Alerting Type( NULL when not present) See <a href="#">arrAlertingType</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>
<i>pArrSvcOption</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Service Option.(NULL when not present) See <a href="#">arrSvcOption</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>
<i>pArrCallEnd-Reason</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Call End Reason.( NULL when not present) See <a href="#">arrCallEndReason</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>

<i>pArrAlphaID</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Alpha Identifier( NULL when not present) See <a href="#">arrAlphaID</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>
<i>pArrConnect-PartyNum</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Connected Party Number.( NULL when not present) See <a href="#">arrConnectPartyNum</a> for more information.</li> <li>– Applicable for both "3GPP/3GPP2"</li> </ul>
<i>pArrDiagInfo</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Diagnostic Information.( NULL when not present) See <a href="#">arrDiagInfo</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>
<i>pArrCalledParty-Num</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Called Party Number.( NULL when not present) See <a href="#">arrCalledPartyNum</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>
<i>pArrRedirParty-Num</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Redirecting Party Number.( NULL when not present) See <a href="#">arrRedirPartyNum</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>
<i>pArrAlerting-Pattern</i>	[optional] <ul style="list-style-type: none"> <li>• Array of Alerting Pattern.( NULL when not present) See <a href="#">arrAlertingPattern</a> for more information.</li> <li>– Applicable only for "3GPP"</li> </ul>

#### Note

Optional paramters would be NULL, if not received from the device.

## 8.1026.2 Field Documentation

8.1026.2.1 **arrCallInfo** voiceSetAllCallStatusCbInfo::arrCallInfomation

8.1026.2.2 **arrAlertingPattern\*** voiceSetAllCallStatusCbInfo::pArrAlertingPattern

8.1026.2.3 **arrAlertingType\*** voiceSetAllCallStatusCbInfo::pArrAlertingType

8.1026.2.4 **arrAlphaID\*** voiceSetAllCallStatusCbInfo::pArrAlphaID

8.1026.2.5 **arrCalledPartyNum\*** voiceSetAllCallStatusCbInfo::pArrCalledPartyNum

8.1026.2.6 `arrCallEndReason*` `voiceSetAllCallStatusCbInfo::pArrCallEndReason`

8.1026.2.7 `arrConnectPartyNum*` `voiceSetAllCallStatusCbInfo::pArrConnectPartyNum`

8.1026.2.8 `arrDiagInfo*` `voiceSetAllCallStatusCbInfo::pArrDiagInfo`

8.1026.2.9 `arrRedirPartyNum*` `voiceSetAllCallStatusCbInfo::pArrRedirPartyNum`

8.1026.2.10 `arrRemotePartyName*` `voiceSetAllCallStatusCbInfo::pArrRemotePartyName`

8.1026.2.11 `arrRemotePartyNum*` `voiceSetAllCallStatusCbInfo::pArrRemotePartyNum`

8.1026.2.12 `arrSvcOption*` `voiceSetAllCallStatusCbInfo::pArrSvcOption`

## 8.1027 voiceSetCallBarringPwdInfo Struct Reference

### Data Fields

- [BYTE Reason](#)
- [BYTE oldPasswd](#) [4]
- [BYTE newPasswd](#) [4]
- [BYTE newPasswdAgain](#) [4]

### 8.1027.1 Detailed Description

This structure contains Voice Set Call Barring Password Request Parameters

#### Parameters

<i>Reason</i>	<ul style="list-style-type: none"> <li>• Call Barring Reason</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x07 - QMI_VOICE_REASON_BARR_ALLOUTGOING - All outgoing</li> <li>– 0x08 - QMI_VOICE_REASON_BARR_OUTGOINGINT - Outgoing internal</li> <li>– 0x09 - QMI_VOICE_REASON_BARR_OUTGOINGINTEXTOHOME - Outgoing external to home</li> <li>– 0x0A - QMI_VOICE_REASON_BARR_ALLINCOMING - All incoming</li> <li>– 0x0B - QMI_VOICE_REASON_BARR_INCOMINGROAMING - Roaming incoming</li> <li>– 0x0C - QMI_VOICE_REASON_BARR_ALLBARRING - All calls are barred</li> <li>– 0x0D - QMI_VOICE_REASON_BARR_ALLOUTGOINGBARRING - All outgoing calls are barred</li> <li>– 0x0E - QMI_VOICE_REASON_BARR_ALLINCOMINGBARRING - All incoming calls are barred</li> </ul> </li> </ul>
---------------	---

<i>oldPasswd[PASSWORD_LENGTH]</i>	<ul style="list-style-type: none"> <li>• Old password. <ul style="list-style-type: none"> <li>– Password consists of 4 ASCII digits.</li> <li>– Range: 0000 to 9999.</li> </ul> </li> </ul>
<i>newPasswd[PASSWORD_LENGTH]</i>	<ul style="list-style-type: none"> <li>• New password. <ul style="list-style-type: none"> <li>– Password consists of 4 ASCII digits.</li> <li>– Range: 0000 to 9999.</li> </ul> </li> </ul>
<i>newPasswd-Again[PASSWORD_LENGTH]</i>	<ul style="list-style-type: none"> <li>• New password Again. <ul style="list-style-type: none"> <li>– Password consists of 4 ASCII digits.</li> <li>– Range: 0000 to 9999.</li> </ul> </li> </ul>

## 8.1027.2 Field Documentation

8.1027.2.1 **BYTE** voiceSetCallBarringPwdInfo::newPasswd[4]

8.1027.2.2 **BYTE** voiceSetCallBarringPwdInfo::newPasswdAgain[4]

8.1027.2.3 **BYTE** voiceSetCallBarringPwdInfo::oldPasswd[4]

8.1027.2.4 **BYTE** voiceSetCallBarringPwdInfo::Reason

## 8.1028 voiceSetCallBarringPwdResp Struct Reference

### Data Fields

- **WORD** \* pFailCause
- **alphaIDInfo** \* pAlphaIDInfo
- **BYTE** \* pCCResType
- **BYTE** \* pCallID
- **ccSUPSType** \* pCCSUPSType

### 8.1028.1 Detailed Description

This structure contains Voice Set Call Barring Password Response Parameters



## Parameters

<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause (optional)</li> <li>• see <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> <li>• 0xFFFF,if Not Available</li> </ul>
<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a> (optional) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResType</i>	<ul style="list-style-type: none"> <li>• Call Control Result Type (optional) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Call ID of the voice call that resulted from call control. (optional)</li> <li>• It is present when pCCResType is present and is Voice.</li> <li>• If zero(0) then invalid.</li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Supplementary service data that resulted from call control (optional)</li> <li>• Data is present when pCCResType is present and is other than Voice. <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

## Note

Using NULL for the pointers would make sure that the parameter is not returned or has default value.

## 8.1028.2 Field Documentation

8.1028.2.1 **alphaIDInfo\*** voiceSetCallBarringPwdResp::pAlphaIDInfo

8.1028.2.2 **BYTE\*** voiceSetCallBarringPwdResp::pCallID

8.1028.2.3 **BYTE\*** voiceSetCallBarringPwdResp::pCCResType

8.1028.2.4 **ccSUPSType\*** voiceSetCallBarringPwdResp::pCCSUPSType

8.1028.2.5 **WORD\*** voiceSetCallBarringPwdResp::pFailCause

## 8.1029 voiceSetConfigReq Struct Reference

## Data Fields

- [BYTE](#) \* [pAutoAnswer](#)
- [airTimer](#) \* [pAirTimerConfig](#)
- [roamTimer](#) \* [pRoamTimerConfig](#)
- [BYTE](#) \* [pTTYMode](#)
- [prefVoiceSO](#) \* [pPrefVoiceSO](#)
- [BYTE](#) \* [pPrefVoiceDomain](#)

### 8.1029.1 Detailed Description

This structure contains information about the Set Configuration Request Parameters.

#### Parameters

<i>pAutoAnswer</i>	<ul style="list-style-type: none"> <li>• Value specified is written to NV_AUTO_ANSWER_I. (optional)</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disable</li> <li>– 0x01 - Enable</li> </ul> </li> </ul>
<i>pAirTimerConfig</i>	<ul style="list-style-type: none"> <li>• Value specified is written to NV_AIR_CNT_I. (optional)</li> <li>• See <a href="#">airTimer</a> for more information</li> </ul>
<i>pRoamTimer-Config</i>	<ul style="list-style-type: none"> <li>• Value specified is written to NV_ROAM_CNT_I. (optional)</li> <li>• See <a href="#">roamTimer</a> for more information</li> </ul>
<i>pTTYMode</i>	<ul style="list-style-type: none"> <li>• Value specified is written to NV_TTY_I. (optional)</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - TTY_MODE_FULL - Full</li> <li>– 0x01 - TTY_MODE_VCO - Voice carry over</li> <li>– 0x02 - TTY_MODE_HCO - Hearing carry over</li> <li>– 0x03 - TTY_MODE_OFF - Off</li> </ul> </li> </ul>

<i>pPrefVoiceSO</i>	<ul style="list-style-type: none"> <li>• Value specified is written to NV_PREF_VOICE_SO_I. (optional)</li> <li>• See <a href="#">prefVoiceSO</a> for more information</li> </ul>
<i>pPrefVoice-Domain</i>	<ul style="list-style-type: none"> <li>• Preferred Voice-Domain. (optional)</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - VOICE_DOMAIN_PREF_CS_ONLY - Circuit-switched (CS) only</li> <li>– 0x01 - VOICE_DOMAIN_PREF_PS_ONLY - Packet-switched (PS) only</li> <li>– 0x02 - VOICE_DOMAIN_PREF_CS_PREF - CS is preferred, PS is secondary</li> <li>– 0x03 - VOICE_DOMAIN_PREF_PS_PREF - PS is preferred, CS is secondary</li> </ul> </li> </ul>

**Note**

One of the optional parameters must be present in the request.

**8.1029.2 Field Documentation**

**8.1029.2.1** `airTimer*` voiceSetConfigReq::pAirTimerConfig

**8.1029.2.2** `BYTE*` voiceSetConfigReq::pAutoAnswer

**8.1029.2.3** `BYTE*` voiceSetConfigReq::pPrefVoiceDomain

**8.1029.2.4** `prefVoiceSO*` voiceSetConfigReq::pPrefVoiceSO

**8.1029.2.5** `roamTimer*` voiceSetConfigReq::pRoamTimerConfig

**8.1029.2.6** `BYTE*` voiceSetConfigReq::pTTYMode

**8.1030 voiceSetConfigResp Struct Reference****Data Fields**

- `BYTE *` [pAutoAnsStatus](#)
- `BYTE *` [pAirTimerStatus](#)
- `BYTE *` [pRoamTimerStatus](#)
- `BYTE *` [pTTYConfigStatus](#)
- `BYTE *` [pPrefVoiceSOStatus](#)
- `BYTE *` [pVoiceDomainPrefStatus](#)

**8.1030.1 Detailed Description**

This structure contains information about the Set Configuration Response Parameters.

## Parameters

<i>pAutoAnsStatus</i>	<ul style="list-style-type: none"><li>• Auto Answer Status. (optional)</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - Information was written successfully</li><li>– 0x01 - Information write failed</li><li>– 0xFF - Not Available.</li></ul></li></ul>
<i>pAirTimerStatus</i>	<ul style="list-style-type: none"><li>• Air Timer Status. (optional)</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - Information was written successfully</li><li>– 0x01 - Information write failed</li><li>– 0xFF - Not Available.</li></ul></li></ul>
<i>pRoamTimer- Status</i>	<ul style="list-style-type: none"><li>• Roam Timer Status. (optional)</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - Information was written successfully</li><li>– 0x01 - Information write failed</li><li>– 0xFF - Not Available.</li></ul></li></ul>
<i>pTTYConfig- Status</i>	<ul style="list-style-type: none"><li>• TTY Config Status. (optional)</li><li>• Values:<ul style="list-style-type: none"><li>– 0x00 - Information was written successfully</li><li>– 0x01 - Information write failed</li><li>– 0xFF - Not Available.</li></ul></li></ul>

<i>pPrefVoiceSO-Status</i>	<ul style="list-style-type: none"> <li>• Preferred Voice SO Status. (optional)</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Information was written successfully</li> <li>– 0x01 - Information write failed</li> <li>– 0xFF - Not Available.</li> </ul> </li> </ul>
<i>pVoiceDomain-PrefStatus</i>	<ul style="list-style-type: none"> <li>• Voice-Domain Preference Status. (optional)</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Information was written successfully</li> <li>– 0x01 - Information write failed</li> <li>– 0xFF - Not Available.</li> </ul> </li> </ul>

**Note**

Parameters which are mentioned as NULL will be ignored.

**8.1030.2 Field Documentation**

8.1030.2.1 **BYTE\*** voiceSetConfigResp::pAirTimerStatus

8.1030.2.2 **BYTE\*** voiceSetConfigResp::pAutoAnsStatus

8.1030.2.3 **BYTE\*** voiceSetConfigResp::pPrefVoiceSOStatus

8.1030.2.4 **BYTE\*** voiceSetConfigResp::pRoamTimerStatus

8.1030.2.5 **BYTE\*** voiceSetConfigResp::pTTYConfigStatus

8.1030.2.6 **BYTE\*** voiceSetConfigResp::pVoiceDomainPrefStatus

**8.1031 voiceSetPrefPrivacy Struct Reference****Data Fields**

- [BYTE privacyPref](#)

**8.1031.1 Detailed Description**

This structure contains the preferred voice privacy values.

## Parameters

<i>privacyPref</i>	<ul style="list-style-type: none"> <li>• Voice Privacy Preference <ul style="list-style-type: none"> <li>– 0x00 - VOICE_PRIVACY_STANDARD - Standard privacy</li> <li>– 0x01 - VOICE_PRIVACY_ENHANCED - Enhanced privacy</li> </ul> </li> </ul>
--------------------	--

## 8.1031.2 Field Documentation

## 8.1031.2.1 BYTE voiceSetPrefPrivacy::privacyPref

## 8.1032 voiceSetSUPSServiceReq Struct Reference

## Data Fields

- [BYTE voiceSvc](#)
- [BYTE reason](#)
- [BYTE \\* pServiceClass](#)
- [BYTE \\* pCallBarringPasswd](#)
- [BYTE \\* pCallForwardingNumber](#)
- [BYTE \\* pTimerVal](#)
- [callFwdTypeAndPlan \\* pCallFwdTypeAndPlan](#)

## 8.1032.1 Detailed Description

This structure contains Supplementary Service request parameters related to different features and their activation, deactivation, registration and erasure (applicable only for 3GPP)

## Parameters

<i>voiceSvc</i>	<ul style="list-style-type: none"> <li>• Manages all call-independent supplementary services, such as activation, deactivation, registration, and erasure (mandatory) <ul style="list-style-type: none"> <li>– 0x01 - VOICE_SERVICE_ACTIVATE</li> <li>– 0x02 - VOICE_SERVICE_DEACTIVATE</li> <li>– 0x03 - VOICE_SERVICE_REGISTER</li> <li>– 0x04 - VOICE_SERVICE_ERASE</li> </ul> </li> </ul>
-----------------	---

<i>reason</i>	<ul style="list-style-type: none"> <li>• supplementary service reason values (mandatory) <ul style="list-style-type: none"> <li>– 0x01 - QMI_VOICE_REASON_FWD_UNCONDITIONAL Unconditional call forwarding</li> <li>– 0x02 - QMI_VOICE_REASON_FWD_MOBILEBUSY Forward when the mobile is busy</li> <li>– 0x03 - QMI_VOICE_REASON_FWD_NOREPLY Forward when there is no reply</li> <li>– 0x04 - QMI_VOICE_REASON_FWD_UNREACHABLE Forward when the call is unreachable</li> <li>– 0x05 - QMI_VOICE_REASON_FWD_ALLFORWARDING All forwarding</li> <li>– 0x06 - QMI_VOICE_REASON_FWD_ALLCONDITIONAL All conditional forwarding</li> <li>– 0x07 - QMI_VOICE_REASON_BARR_ALLOUTGOING All outgoing calls are barred</li> <li>– 0x08 - QMI_VOICE_REASON_BARR_OUTGOINGINT Outgoing internal calls are barred</li> <li>– 0x09 - QMI_VOICE_REASON_BARR_OUTGOINGINTEXTTOHOME Outgoing calls external to home are barred</li> <li>– 0x0A - QMI_VOICE_REASON_BARR_ALLINCOMING All incoming calls are barred</li> <li>– 0x0B - QMI_VOICE_REASON_BARR_INCOMINGROAMING Roaming incoming calls are barred</li> <li>– 0x0C - QMI_VOICE_REASON_BARR_ALLBARRING All calls are barred</li> <li>– 0x0D - QMI_VOICE_REASON_BARR_ALLOUTGOINGBARRING All outgoing calls are barred</li> <li>– 0x0E - QMI_VOICE_REASON_BARR_ALLINCOMINGBARRING All incoming calls are barred</li> <li>– 0x0F - QMI_VOICE_REASON_CALLWAITING Call waiting</li> </ul> </li> </ul>
---------------	--

<i>pServiceClass</i>	<ul style="list-style-type: none"> <li>Service class is a combination (sum) of information class constants (optional) <ul style="list-style-type: none"> <li>See <a href="#">serviceClassInformation</a> for more information</li> </ul> </li> </ul>
<i>pCallBarring-Passwd</i>	<ul style="list-style-type: none"> <li>Password is required if call barring is provisioned using a password. Password consists of 4 ASCII digits. Range: 0000 to 9999 (optional)</li> </ul>
<i>pCallForwarding-Number</i>	<ul style="list-style-type: none"> <li>Call forwarding number to be registered with the network. This has to be included in the request only when the service is set to VOICE_SERVICE_REGISTER. NULL terminated ASCII string. (optional)</li> </ul>
<i>pTimerVal</i>	<ul style="list-style-type: none"> <li>Call forwarding no reply timer value in seconds. This has to be included in the request only when the service is set to VOICE_SERVICE_REGISTER and the reason is QMI_VOICE_REASON_FWD_NOREPLY. (optional) <ul style="list-style-type: none"> <li>Range: 5 to 30 in steps of 5</li> </ul> </li> </ul>
<i>pCallFwdType-AndPlan</i>	<ul style="list-style-type: none"> <li>Information about call forwarding type and plan. This parameter is ignored when the Call Forwarding Number is not included (optional) <ul style="list-style-type: none"> <li>See <a href="#">callFwdTypeAndPlan</a> for more information</li> </ul> </li> </ul>

## 8.1032.2 Field Documentation

8.1032.2.1 **BYTE\*** voiceSetSUPSServiceReq::pCallBarringPasswd

8.1032.2.2 **BYTE\*** voiceSetSUPSServiceReq::pCallForwardingNumber

8.1032.2.3 **callFwdTypeAndPlan\*** voiceSetSUPSServiceReq::pCallFwdTypeAndPlan

8.1032.2.4 **BYTE\*** voiceSetSUPSServiceReq::pServiceClass

8.1032.2.5 **BYTE\*** voiceSetSUPSServiceReq::pTimerVal

8.1032.2.6 **BYTE** voiceSetSUPSServiceReq::reason

8.1032.2.7 **BYTE** voiceSetSUPSServiceReq::voiceSvc

## 8.1033 voiceSetSUPSServiceResp Struct Reference

### Data Fields

- WORD\*** pFailCause
- alphaIDInfo\*** pAlphaIDInfo
- BYTE\*** pCCResultType
- BYTE\*** pCallID



- [ccSUPSType](#) \* [pCCSUPSType](#)

### 8.1033.1 Detailed Description

This structure contains Supplementary Service response parameters related to different features and their activation, deactivation, registration and erasure (applicable only for 3GPP)

#### Parameters

<i>pFailCause</i>	<ul style="list-style-type: none"> <li>• Supplementary service failure causes (optional, supply NULL if not required). <ul style="list-style-type: none"> <li>– 0xFFFF is the value when the information is not received from device</li> </ul> </li> </ul>
<i>pAlphaIDInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">alphaIDInfo</a>. The parameter used to pass the alpha (if any) given by the SIM/R-UIM after call control (optional, supply NULL if not required) <ul style="list-style-type: none"> <li>– See <a href="#">alphaIDInfo</a> for more information</li> </ul> </li> </ul>
<i>pCCResultType</i>	<ul style="list-style-type: none"> <li>• Call control result types (optional, supply NULL if not required) <ul style="list-style-type: none"> <li>– 0x00 - CC_RESULT_TYPE_VOICE - Voice</li> <li>– 0x01 - CC_RESULT_TYPE_SUPS - Supplementary service</li> <li>– 0x02 - CC_RESULT_TYPE_USSD - Unstructured supplementary service</li> <li>– 0xFF - if the device does not provide this information</li> </ul> </li> </ul>
<i>pCallID</i>	<ul style="list-style-type: none"> <li>• Unique call identifier for the dialed call (optional, supply NULL if not required) <ul style="list-style-type: none"> <li>– 0x00 - if the device does not provide this information</li> </ul> </li> </ul>
<i>pCCSUPSType</i>	<ul style="list-style-type: none"> <li>• Data is present when pCCResultType is present and is other than Voice. (optional, supply NULL if not required) <ul style="list-style-type: none"> <li>– See <a href="#">ccSUPSType</a> for more information</li> </ul> </li> </ul>

### 8.1033.2 Field Documentation

8.1033.2.1 **alphaIDInfo\*** voiceSetSUPSServiceResp::pAlphaIDInfo

8.1033.2.2 **BYTE\*** voiceSetSUPSServiceResp::pCallID

8.1033.2.3 **BYTE\*** voiceSetSUPSServiceResp::pCCResultType

8.1033.2.4 **ccSUPSType\*** voiceSetSUPSServiceResp::pCCSUPSType

8.1033.2.5 **WORD\*** voiceSetSUPSServiceResp::pFailCause

## 8.1034 voiceStopContDTMFInfo Struct Reference

### Data Fields

- [BYTE callID](#)

### 8.1034.1 Detailed Description

This structure contains parameters of stop continuous DTMF

#### Parameters

<i>pCallID</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Call ID associated with call on which the DTMF information has to be sent. Stop continuous DTMF request is sent to the current active/alerting call when pCallId is set to 0xFF.</li> <li>• This is IN/OUT parameter, value passed by user will be packed in request and value received from the device would be returned to the user.</li> <li>• If the call ID value received is 0, no value has been returned by the device</li> </ul>
-------------------------	--

### 8.1034.2 Field Documentation

#### 8.1034.2.1 BYTE voiceStopContDTMFInfo::callID

## 8.1035 voiceSUPSInfo Struct Reference

### Data Fields

- [SUPSInfo SUPSInformation](#)
- [BYTE \\* pSvcClass](#)
- [BYTE \\* pReason](#)
- [BYTE \\* pCallFWNum](#)
- [BYTE \\* pCallFWTimerVal](#)
- [struct USSInfo \\* pUSSInfo](#)
- [BYTE \\* pCallID](#)
- [alphaIDInfo \\* pAlphaIDInfo](#)
- [BYTE \\* pCallBarPasswd](#)
- [newPwdData \\* pNewPwdData](#)
- [BYTE \\* pDataSrc](#)
- [WORD \\* pFailCause](#)
- [getCallFWInfo \\* pCallFwdInfo](#)
- [CLIRResp \\* pCLIRstatus](#)
- [CLIPResp \\* pCLIPstatus](#)
- [COLPResp \\* pCOLPstatus](#)
- [COLRResp \\* pCOLRstatus](#)
- [CNAPResp \\* pCNAPstatus](#)

### 8.1035.1 Detailed Description

This structure contains the parameters passed for SLQSVoiceSetSUPSCallBack by the device.

## Parameters

<i>SUPS- Information(mandatory)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SUPSInfo</a> for more information.</li> </ul>
<i>pSvc- Class(optional)</i>	<ul style="list-style-type: none"> <li>• Service class is a combination (sum) of information class constants (optional)</li> <li>• See <a href="#">qaGobiApiTableSupServiceInfoClasses.h</a> for service classes.</li> </ul>
<i>p- Reason(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaGobiApiTableCallControlReturnReasons.h</a> for return reasons.</li> </ul>
<i>pCallFW- Num(optional)</i>	<ul style="list-style-type: none"> <li>• Call forwarding number to be registered with the network.</li> <li>• ASCII String, NULL terminated.</li> </ul>
<i>pCallFWTimer- Val(optional)</i>	<ul style="list-style-type: none"> <li>• Call Forwarding No Reply Timer. <ul style="list-style-type: none"> <li>– Range: 5 to 30 in steps of 5.</li> </ul> </li> </ul>
<i>pUSS- Info(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">USSInfo</a> for more information.</li> </ul>
<i>pCallID(optional)</i>	<ul style="list-style-type: none"> <li>• Call identifier of the voice call that has been modified to a supplementary service as a result of call control.</li> </ul>
<i>pAlphaID- Info(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">alphaIDInfo</a> for more information.</li> </ul>
<i>pCallBar- Passwd(optional)</i>	<ul style="list-style-type: none"> <li>• Password is required if call barring is provisioned using a password. <ul style="list-style-type: none"> <li>– Password consists of 4 ASCII digits.</li> <li>– Range: 0000 to 9999.</li> </ul> </li> <li>• This also serves as the old password in the register password scenario.</li> </ul>
<i>pNewPwd- Data(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">newPwdData</a> for more information.</li> </ul>
<i>pData- Src(optional)</i>	<ul style="list-style-type: none"> <li>• Sups Data Source.</li> <li>• Used to distinguish between the supplementary service data sent to the network and the response received from the network.</li> <li>• If absent, the supplementary service data in this indication can be assumed as a request sent to the network.</li> </ul>

<i>pFail-Cause(optional)</i>	<ul style="list-style-type: none"> <li>• Supplementary services failure cause.</li> <li>• See <a href="#">qaGobiApiTableVoiceCallEndReasons.h</a> for more information.</li> </ul>
<i>pCallFwd-Info(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">getCallFWInfo</a> for more information.</li> </ul>
<i>pCLI-Rstatus(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CLIRResp</a> for more information.</li> </ul>
<i>pCLI-Pstatus(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CLIPResp</a> for more information.</li> </ul>
<i>pCOL-Pstatus(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">COLPResp</a> for more information.</li> </ul>
<i>pCOL-Rstatus(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">COLRResp</a> for more information.</li> </ul>
<i>pCNA-Pstatus(optional)</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CNAPResp</a> for more information.</li> </ul>

## Note

None

## 8.1035.2 Field Documentation

- 8.1035.2.1 **alphaIDInfo\*** voiceSUPSInfo::pAlphaIDInfo
- 8.1035.2.2 **BYTE\*** voiceSUPSInfo::pCallBarPasswd
- 8.1035.2.3 **getCallFWInfo\*** voiceSUPSInfo::pCallFwdInfo
- 8.1035.2.4 **BYTE\*** voiceSUPSInfo::pCallFWNum
- 8.1035.2.5 **BYTE\*** voiceSUPSInfo::pCallFWTimerVal
- 8.1035.2.6 **BYTE\*** voiceSUPSInfo::pCallIID
- 8.1035.2.7 **CLIPResp\*** voiceSUPSInfo::pCLIPstatus
- 8.1035.2.8 **CLIRResp\*** voiceSUPSInfo::pCLIRstatus
- 8.1035.2.9 **CNAPResp\*** voiceSUPSInfo::pCNAPstatus
- 8.1035.2.10 **COLPResp\*** voiceSUPSInfo::pCOLPstatus
- 8.1035.2.11 **COLRResp\*** voiceSUPSInfo::pCOLRstatus
- 8.1035.2.12 **BYTE\*** voiceSUPSInfo::pDataSrc

8.1035.2.13 **WORD\*** voiceSUPSInfo::pFailCause

8.1035.2.14 **newPwdData\*** voiceSUPSInfo::pNewPwdData

8.1035.2.15 **BYTE\*** voiceSUPSInfo::pReason

8.1035.2.16 **BYTE\*** voiceSUPSInfo::pSvcClass

8.1035.2.17 **struct USSInfo\*** voiceSUPSInfo::pUSSInfo

8.1035.2.18 **SUPSInfo** voiceSUPSInfo::SUPSInformation

## 8.1036 voiceSUPSNotification Struct Reference

### Data Fields

- [BYTE](#) callID
- [BYTE](#) notifType
- [WORD](#) \* pCUGIndex
- [ECTNum](#) \* pECTNum

### 8.1036.1 Detailed Description

Contains the parameters passed for SLQSVoiceSetSUPSNotificationCallback by the device.

## Parameters

<i>callID</i>	<ul style="list-style-type: none"> <li>• Unique identifier of the call for which the notification is applicable. (mandatory)</li> </ul>
<i>notifType</i>	<ul style="list-style-type: none"> <li>• Notification type parameter (mandatory) <ul style="list-style-type: none"> <li>– 0x01 - NOTIFICATION_TYPE_OUTGOING_CALL_IS_FORWARDED Originated MO call is being forwarded to another user</li> <li>– 0x02 - NOTIFICATION_TYPE_OUTGOING_CALL_IS_WAITING Originated MO call is waiting at the called user</li> <li>– 0x03 - NOTIFICATION_TYPE_OUTGOING_CUG_CALL Outgoing call is a CUG call</li> <li>– 0x04 - NOTIFICATION_TYPE_OUTGOING_CALLS_BARRED Outgoing calls are barred</li> <li>– 0x05 - NOTIFICATION_TYPE_OUTGOING_CALL_IS_DEFLECTED Outgoing call is deflected</li> <li>– 0x06 - NOTIFICATION_TYPE_INCOMING_CUG_CALL Incoming call is a CUG call</li> <li>– 0x07 - NOTIFICATION_TYPE_INCOMING_CALLS_BARRED Incoming calls are barred</li> <li>– 0x08 - NOTIFICATION_TYPE_INCOMING_FORWARDED_CALL Incoming call received is a forwarded call</li> <li>– 0x09 - NOTIFICATION_TYPE_INCOMING_DEFLECTED_CALL Incoming call is a deflected call</li> <li>– 0x0A - NOTIFICATION_TYPE_INCOMING_CALL_IS_FORWARDED Incoming call is forwarded to another user</li> <li>– 0x0B - NOTIFICATION_TYPE_UNCOND_CALL_FORWARD_ACTIVE Unconditional call forwarding is active</li> <li>– 0x0C - NOTIFICATION_TYPE_COND_CALL_FORWARD_ACTIVE Conditional call forwarding is active</li> <li>– 0x0D - NOTIFICATION_TYPE_CLIR_SUPPRESSION_REJECTED CLIR suppression is rejected</li> <li>– 0x0E - NOTIFICATION_TYPE_CALL_IS_ON_HOLD Call is put on hold at the remote party</li> <li>– 0x0F - NOTIFICATION_TYPE_CALL_IS_RETRIEVED Call is retrieved at the remote party from the hold state</li> <li>– 0x10 - NOTIFICATION_TYPE_CALL_IS_IN_MPTY Call is in a conference</li> <li>– 0x11 - NOTIFICATION_TYPE_INCOMING_CALL_IS_ECT Incoming call is an explicit call transfer</li> </ul> </li> </ul>
<i>pCUGIndex</i>	<ul style="list-style-type: none"> <li>• The CUG Index used to indicate that the incoming/outgoing call is a CUG call. (optional, NULL when not present) Range: 0x00 to 0x7FFF.</li> </ul>

<i>pECTNum</i>	<ul style="list-style-type: none"> <li>The ECT Number is used to indicate that the incoming call is an explicitly transferred call. (optional, NULL when not present)</li> </ul> Refer <a href="#">ECTNum</a> for details.
----------------	--

## Note

None

## 8.1036.2 Field Documentation

8.1036.2.1 **BYTE** voiceSUPSNotification::callID8.1036.2.2 **BYTE** voiceSUPSNotification::notifType8.1036.2.3 **WORD\*** voiceSUPSNotification::pCUGIndex8.1036.2.4 **ECTNum\*** voiceSUPSNotification::pECTNum

## 8.1037 wcdmaCellInfo Struct Reference

## Data Fields

- [WORD](#) psc
- [SHORT](#) cpich\_rscp
- [SHORT](#) cpich\_ecno
- [SHORT](#) srxlev

## 8.1037.1 Detailed Description

This structure contains information about the WCDMA Cell.

## Parameters

<i>psc</i>	<ul style="list-style-type: none"> <li>Primary scrambling code.</li> <li>Range: 0 to 511.</li> </ul>
<i>cpich_rscp</i>	<ul style="list-style-type: none"> <li>Absolute power level (in 1/10 dBm) of the common pilot channel as received by the UE.</li> <li>Range: -120.0 dBm to -25.0 dBm</li> </ul>
<i>cpich_ecno</i>	<ul style="list-style-type: none"> <li>CPICH Ec/No; ratio (in 1/10 dB) of the received energy per PN chip for the CPICH to the total received power spectral density at the UE antenna connector.</li> <li>Range: -50.0 dB to 0.</li> </ul>

<i>srxlev</i>	<ul style="list-style-type: none"> <li>• Cell selection Rx level (Srxlev) value.</li> <li>• Range: -128 to 128.</li> <li>• This field is only valid when ue_in_idle is TRUE.</li> </ul>
---------------	---

## 8.1037.2 Field Documentation

8.1037.2.1 **SHORT** wcdmaCellInfo::cpich\_ecno

8.1037.2.2 **SHORT** wcdmaCellInfo::cpich\_rscp

8.1037.2.3 **WORD** wcdmaCellInfo::psc

8.1037.2.4 **SHORT** wcdmaCellInfo::srxlev

## 8.1038 WCDMAECIOThresh Struct Reference

### Data Fields

- [BYTE](#) WCDMAECIOThreshListLen
- [WORD](#) \* pWCDMAECIOThreshList

### 8.1038.1 Detailed Description

This structure contains WCDMA ECIO threshold related parameters.

#### Parameters

<i>WCDMAECIO-ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the WCDMA ECIO threshold list parameter to follow</li> </ul>
<i>pWCDMAECIO-ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of ECIO thresholds (in units of 0.1 dB)</li> <li>• Maximum of 32 values</li> <li>• Range for ECIO values: -31.5 to 0 (in dB)</li> </ul>

## 8.1038.2 Field Documentation

8.1038.2.1 **WORD\*** WCDMAECIOThresh::pWCDMAECIOThreshList

8.1038.2.2 **BYTE** WCDMAECIOThresh::WCDMAECIOThreshListLen

## 8.1039 WCDMAInfoLTENeighborCell Struct Reference

### Data Fields

- [ULONG](#) wcdmaRRCTest
- [BYTE](#) umtsLTENbrCellLen



- [umtsLTENbrCell](#) [UMTSLTENbrCell](#) [255]

### 8.1039.1 Detailed Description

This structure contains information about the WCDMA - LTE Neighboring Cell Info Set.

#### Parameters

<i>wcdmaRRC-State</i>	<ul style="list-style-type: none"> <li>• WCDMA RRC states.</li> <li>• Defined in 3GPP TS 25.331</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - NAS_WCDMA_RRC_STATE_DISCONNECTED * WCDMA RRC State is IDLE</li> <li>– 0x01 - NAS_WCDMA_RRC_STATE_CELL_PCH * WCDMA RRC state is CELL_PCH</li> <li>– 0x02 - NAS_WCDMA_RRC_STATE_URA_PCH * WCDMA RRC state is URA_PCH</li> <li>– 0x03 - NAS_WCDMA_RRC_STATE_CELL_FACH * WCDMA RRC state is CELL_FACH</li> <li>– 0x04 - NAS_WCDMA_RRC_STATE_CELL_DCH * WCDMA RRC state is CELL_DCH</li> </ul> </li> </ul>
<i>umtsLTENbr-CellLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of UMTS LTE Neighbors.</li> </ul>
<i>UMTSLTENbr-Cell</i>	<ul style="list-style-type: none"> <li>• See <a href="#">umtsLTENbrCell</a> for more information.</li> </ul>

### 8.1039.2 Field Documentation

8.1039.2.1 [umtsLTENbrCell](#) [WCDMAInfoLTENeighborCell::UMTSLTENbrCell](#)[255]

8.1039.2.2 **BYTE** [WCDMAInfoLTENeighborCell::umtsLTENbrCellLen](#)

8.1039.2.3 **ULONG** [WCDMAInfoLTENeighborCell::wcdmaRRCState](#)

## 8.1040 wcdmaLongMsgDecodingParams Struct Reference

### Data Fields

- **BYTE** \* [pMessage](#)
- **BYTE** \* [pSenderAddrLength](#)
- **CHAR** \* [pSenderAddr](#)
- **BYTE** \* [pTextMsgLength](#)
- **CHAR** \* [pTextMsg](#)
- **BYTE** \* [pScAddrLength](#)
- **CHAR** \* [pScAddr](#)

- [BYTE Time](#) [0x09]
- [BYTE Date](#) [0x09]
- [BYTE \\* pReferenceNum](#)
- [BYTE \\* pTotalNum](#)
- [BYTE \\* pPartNum](#)
- [BOOL \\* plsUDHPresent](#)

### 8.1040.1 Detailed Description

Structure contains parameters which need to be decoded from message

#### Parameters

<i>pMessage[IN]</i>	<ul style="list-style-type: none"> <li>• Message read off the device via SLQSGetSMS</li> </ul>
<i>pSenderAddrLength[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Upon input, indicates the maximum number of ASCII characters (including NULL termination) that the pSenderAddr buffer can accommodate. A length with 24 will be much safe since this address field can be up to 12 octets (24 bytes) Upon successful output, returns the length of destination address string.</li> </ul>
<i>pSenderAddr[OUT]</i>	<ul style="list-style-type: none"> <li>• Note that a length with 24 bytes will be much safe. Returns NULL-terminated ASCII String containing destination address</li> </ul>
<i>pTextMsgLength[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Upon input, specifies the number of characters the given text message buffer can accommodate. Upon successful output, returns the number of characters returns in the given text message buffer.</li> </ul>
<i>pTextMsg[OUT]</i>	<ul style="list-style-type: none"> <li>• Encoded PDU message</li> </ul>
<i>pScAddrLength[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• A length with 24 will be much safe since this address field can be up to 12 octets (24 bytes) Returns NULL-terminated ASCII String containing destination address</li> </ul>
<i>pScAddr[OUT]</i>	<ul style="list-style-type: none"> <li>• Note that a length with 24 bytes will be much safe. Returns NULL-terminated ASCII String containing service center address. This SMSC field contains the Type of Address. To get the exact SMSC address, skip the first two bytes. e.g, 9085290100334, 90 is the Type of Address, indicates international format of phone number</li> </ul>
<i>pTime[OUT]</i>	<ul style="list-style-type: none"> <li>• Time fetched from message</li> </ul>
<i>pReferenceNum[OUT]</i>	<ul style="list-style-type: none"> <li>• Reference number of the sms</li> </ul>
<i>pTotalNum[OUT]</i>	<ul style="list-style-type: none"> <li>• Total number of the concatenated message</li> </ul>

<i>pPartNum</i> [OUT]	<ul style="list-style-type: none"> <li>Sequence number of the current message</li> </ul>
<i>plsUDHPresent</i>	<ul style="list-style-type: none"> <li>Is User Data Header Present in the PDU? If yes, it means it is a concatenated SMS.</li> </ul>

## 8.1040.2 Field Documentation

8.1040.2.1 **BYTE** wcdmaLongMsgDecodingParams::Date[0x09]

8.1040.2.2 **BOOL\*** wcdmaLongMsgDecodingParams::plsUDHPresent

8.1040.2.3 **BYTE\*** wcdmaLongMsgDecodingParams::pMessage

8.1040.2.4 **BYTE\*** wcdmaLongMsgDecodingParams::pPartNum

8.1040.2.5 **BYTE\*** wcdmaLongMsgDecodingParams::pReferenceNum

8.1040.2.6 **CHAR\*** wcdmaLongMsgDecodingParams::pScAddr

8.1040.2.7 **BYTE\*** wcdmaLongMsgDecodingParams::pScAddrLength

8.1040.2.8 **CHAR\*** wcdmaLongMsgDecodingParams::pSenderAddr

8.1040.2.9 **BYTE\*** wcdmaLongMsgDecodingParams::pSenderAddrLength

8.1040.2.10 **CHAR\*** wcdmaLongMsgDecodingParams::pTextMsg

8.1040.2.11 **BYTE\*** wcdmaLongMsgDecodingParams::pTextMsgLength

8.1040.2.12 **BYTE\*** wcdmaLongMsgDecodingParams::pTotalNum

8.1040.2.13 **BYTE** wcdmaLongMsgDecodingParams::Time[0x09]

## 8.1041 wcdmaMsgDecodingParams Struct Reference

### Data Fields

- [BYTE \\*](#) pMessage
- [BYTE \\*](#) pSenderAddrLength
- [CHAR \\*](#) pSenderAddr
- [BYTE \\*](#) pTextMsgLength
- [CHAR \\*](#) pTextMsg
- [BYTE \\*](#) pScAddrLength
- [CHAR \\*](#) pScAddr
- [BYTE](#) Time [0x09]
- [BYTE](#) Date [0x09]

### 8.1041.1 Detailed Description

Structure contains parameters which need to be decoded from message

## Parameters

<i>pMessage</i> [IN]	<ul style="list-style-type: none"> <li>• Message read off the device via SLQSGetSMS</li> </ul>
<i>pSenderAddrLength</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Upon input, indicates the maximum number of ASCII characters (including NULL termination) that the pSenderAddr buffer can accommodate. A length with 24 will be much safe since this address field can be up to 12 octets (24 bytes) Upon successful output, returns the length of destination address string.</li> </ul>
<i>pSenderAddr</i> [OUT]	<ul style="list-style-type: none"> <li>• Note that a length with 24 bytes will be much safe. Returns NULL-terminated ASCII String containing destination address</li> </ul>
<i>pTextMsgLength</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Upon input, specifies the number of characters the given text message buffer can accommodate. Upon successful output, returns the number of characters returns in the given text message buffer.</li> </ul>
<i>pTextMsg</i> [OUT]	<ul style="list-style-type: none"> <li>• Encoded PDU message</li> </ul>
<i>pScAddrLength</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• A length with 24 will be much safe since this address field can be up to 12 octets (24 bytes) Returns NULL-terminated ASCII String containing destination address</li> </ul>
<i>pScAddr</i> [OUT]	<ul style="list-style-type: none"> <li>• Note that a length with 24 bytes will be much safe. Returns NULL-terminated ASCII String containing service center address. This SMSC field contains the Type of Address. To get the exact SMSC address, skip the first two bytes. e.g, 9085290100334, 90 is the Type of Address, indicates international format of phone number</li> </ul>
<i>pTime</i> [OUT]	<ul style="list-style-type: none"> <li>• Time fetched from message</li> </ul>
<i>pDate</i>	<ul style="list-style-type: none"> <li>• Date fetched from message</li> </ul>

## 8.1041.2 Field Documentation

8.1041.2.1 BYTE wcdmaMsgDecodingParams::Date[0x09]

8.1041.2.2 BYTE\* wcdmaMsgDecodingParams::pMessage

8.1041.2.3 CHAR\* wcdmaMsgDecodingParams::pScAddr

8.1041.2.4 BYTE\* wcdmaMsgDecodingParams::pScAddrLength

8.1041.2.5 CHAR\* wcdmaMsgDecodingParams::pSenderAddr

8.1041.2.6 BYTE\* wcdmaMsgDecodingParams::pSenderAddrLength

8.1041.2.7 CHAR\* wcdmaMsgDecodingParams::pTextMsg

8.1041.2.8 BYTE\* wcdmaMsgDecodingParams::pTextMsgLength

8.1041.2.9 BYTE wcdmaMsgDecodingParams::Time[0x09]

## 8.1042 wcdmaMsgEncodingParams Struct Reference

### Data Fields

- [ULONG](#) messageSize
- [CHAR](#) \* pDestAddr
- [CHAR](#) \* pTextMsg
- [CHAR](#) \* pPDUMessage
- [BYTE](#) alphabet

### 8.1042.1 Detailed Description

Structure contains parameters which need to encoded with message

#### Parameters

<i>messageSize</i>	<ul style="list-style-type: none"> <li>• The length of the message contents in bytes</li> </ul>
<i>pDestAddr[IN]</i>	<ul style="list-style-type: none"> <li>• Gives NULL-terminated ASCII String containing destination address</li> </ul>
<i>pTextMsg[IN]</i>	<ul style="list-style-type: none"> <li>• Text message to be encoded, maximum limit is 160 charaters</li> </ul>
<i>pPDUMessage[-OUT]</i>	<ul style="list-style-type: none"> <li>• Encoded PDU message</li> </ul>
<i>alphabet[IN]</i>	<ul style="list-style-type: none"> <li>• Encoding method to generate the PDU               <ul style="list-style-type: none"> <li>– 0 - 7 bit encoding</li> <li>– 4 - 8 bit encoding</li> <li>– 8 - 16 bit UCS2 encoding</li> <li>– others value will be treated as default 7 bit encoding</li> </ul> </li> </ul>

### 8.1042.2 Field Documentation

8.1042.2.1 BYTE wcdmaMsgEncodingParams::alphabet

8.1042.2.2 ULONG wcdmaMsgEncodingParams::messageSize

8.1042.2.3 CHAR\* wcdmaMsgEncodingParams::pDestAddr

8.1042.2.4 CHAR\* wcdmaMsgEncodingParams::pPDUMessage

8.1042.2.5 CHAR\* wcdmaMsgEncodingParams::pTextMsg

## 8.1043 WCDMARSSIThresh Struct Reference

### Data Fields

- [BYTE WCDMARSSIThreshListLen](#)
- [WORD \\* pWCDMARSSIThreshList](#)

### 8.1043.1 Detailed Description

This structure contains WCDMA RSSI threshold related parameters.

#### Parameters

<i>WCDMARSSI-ThreshListLen</i>	<ul style="list-style-type: none"> <li>• Length of the WCDMA RSSI threshold list parameter to follow</li> </ul>
<i>pWCDMARSSI-ThreshList</i>	<ul style="list-style-type: none"> <li>• Array of RSSI thresholds (in units of 0.1 dBm)</li> <li>• Maximum of 32 values.</li> <li>• Range for RSSI values: -121 to 0 (in dBm)</li> </ul>

### 8.1043.2 Field Documentation

8.1043.2.1 WORD\* WCDMARSSIThresh::pWCDMARSSIThreshList

8.1043.2.2 BYTE WCDMARSSIThresh::WCDMARSSIThreshListLen

## 8.1044 WCDMASysInfo Struct Reference

### Data Fields

- [sysInfoCommon sysInfoWCDMA](#)
- [BYTE lacValid](#)
- [WORD lac](#)
- [BYTE cellIdValid](#)
- [ULONG cellId](#)
- [BYTE regRejectInfoValid](#)
- [BYTE rejectSrvDomain](#)
- [BYTE rejCause](#)
- [BYTE networkIdValid](#)
- [BYTE MCC \[3\]](#)
- [BYTE MNC \[3\]](#)
- [BYTE hsCallStatusValid](#)
- [BYTE hsCallStatus](#)
- [BYTE hsIndValid](#)
- [BYTE hsInd](#)
- [BYTE pscValid](#)
- [WORD psc](#)

### 8.1044.1 Detailed Description

Structure for storing the WCDMA System Information.

## Parameters

<i>sysInfoWCDMA</i>	<ul style="list-style-type: none"> <li>• See <a href="#">sysInfoCommon</a> for more information.</li> </ul>
<i>lacValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the location area code is valid.. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>lac</i>	<ul style="list-style-type: none"> <li>• Location area code.</li> <li>• Only applies to 3GPP. <ul style="list-style-type: none"> <li>– 0xFFFF - Not Available</li> </ul> </li> </ul>
<i>cellIdValid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the cell ID is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>cellId</i>	<ul style="list-style-type: none"> <li>• Cell ID. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Not Available</li> </ul> </li> </ul>
<i>regRejectInfo-Valid</i>	<ul style="list-style-type: none"> <li>• Indicates whether the registration reject information is valid. <ul style="list-style-type: none"> <li>– 0x00 - Invalid</li> <li>– 0x01 - Valid</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>rejectSrvDomain</i>	<ul style="list-style-type: none"> <li>• Type of service domain in which the registration is rejected. <ul style="list-style-type: none"> <li>– 0x00 - SYS_SRV_DOMAIN_NO_SRV - No service</li> <li>– 0x01 - Circuit-switched only</li> <li>– 0x02 - Packet-switched only</li> <li>– 0x03 - Circuit-switched and packet-switched</li> <li>– 0x04 - Camped</li> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
<i>rejCause</i>	<ul style="list-style-type: none"> <li>• Reject cause values sent are specified in [3GPP TS 24.008, Section 10.5.3.6]. <ul style="list-style-type: none"> <li>– 0xFF - Not Available</li> </ul> </li> </ul>
	Generated on Tue Jul 12 2016 10:59:49 for LinuxQMI SDK by Doxygen



<i>networkIdValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the network ID is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>MCC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Country Code.</li> <li>MCC digits in ASCII characters</li> </ul>
<i>MNC[PLMN_LENGTH]</i>	<ul style="list-style-type: none"> <li>Mobile Network Code.</li> <li>MNC digits in ASCII characters</li> <li>An unused byte is set to 0xFF.</li> <li>In case of two-digit MNC values, the third (unused) digit is set to 0xFF. For example, 15 (a two-digit MNC) is reported using the byte stream 0x31 0x35 0xFF.</li> </ul>
<i>hsCallStatusValid</i>	<ul style="list-style-type: none"> <li>Indicates whether the high-speed call status is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>hsCallStatus</i>	<ul style="list-style-type: none"> <li>Call status on high speed.</li> <li>Only applicable for WCDMA. <ul style="list-style-type: none"> <li>0x00 - HSDPA and HSUPA are unsupported</li> <li>0x01 - HSDPA is supported</li> <li>0x02 - HSUPA is supported</li> <li>0x03 - HSDPA and HSUPA are supported</li> <li>0x04 - HSDPA+ is supported</li> <li>0x05 - HSDPA+ and HSUPA are supported</li> <li>0x06 - Dual-cell HSDPA+ is supported</li> <li>0x07 - Dual-cell HSDPA+ and HSUPA are supported</li> <li>0xFF - Not Available</li> </ul> </li> </ul>

<i>hsIndValid</i>	<ul style="list-style-type: none"> <li>Indicates whether high-speed service indication is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>hsInd</i>	<ul style="list-style-type: none"> <li>High-speed service indication</li> <li>Only applicable for WCDMA. <ul style="list-style-type: none"> <li>0x00 - HSDPA and HSUPA are unsupported</li> <li>0x01 - HSDPA is supported</li> <li>0x02 - HSUPA is supported</li> <li>0x03 - HSDPA and HSUPA are supported</li> <li>0x04 - HSDPA+ is supported</li> <li>0x05 - HSDPA+ and HSUPA are supported</li> <li>0x06 - Dual-cell HSDPA+ is supported</li> <li>0x07 - Dual-cell HSDPA+ and HSUPA are supported</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>pscValid</i>	<ul style="list-style-type: none"> <li>Indicates whether primary scrambling code is valid. <ul style="list-style-type: none"> <li>0x00 - Invalid</li> <li>0x01 - Valid</li> <li>0xFF - Not Available</li> </ul> </li> </ul>
<i>psc</i>	<ul style="list-style-type: none"> <li>Primary scrambling code. <ul style="list-style-type: none"> <li>0xFFFF - Not Available</li> </ul> </li> </ul>

## 8.1044.2 Field Documentation

8.1044.2.1 **ULONG** WCDMASysInfo::cellId

8.1044.2.2 **BYTE** WCDMASysInfo::cellIdValid

8.1044.2.3 **BYTE** WCDMASysInfo::hsCallStatus

8.1044.2.4 **BYTE** WCDMASysInfo::hsCallStatusValid

8.1044.2.5 **BYTE** WCDMASysInfo::hsInd

8.1044.2.6 **BYTE** WCDMASysInfo::hsIndValid

- 8.1044.2.7 WORD WCDMASysInfo::lac
- 8.1044.2.8 BYTE WCDMASysInfo::lacValid
- 8.1044.2.9 BYTE WCDMASysInfo::MCC[3]
- 8.1044.2.10 BYTE WCDMASysInfo::MNC[3]
- 8.1044.2.11 BYTE WCDMASysInfo::networkIdValid
- 8.1044.2.12 WORD WCDMASysInfo::psc
- 8.1044.2.13 BYTE WCDMASysInfo::pscValid
- 8.1044.2.14 BYTE WCDMASysInfo::regRejectInfoValid
- 8.1044.2.15 BYTE WCDMASysInfo::rejCause
- 8.1044.2.16 BYTE WCDMASysInfo::rejectSrvDomain
- 8.1044.2.17 sysInfoCommon WCDMASysInfo::sysInfoWCDMA

## 8.1045 wcdmaUARFCN Struct Reference

### Data Fields

- [BYTE status](#)
- [ULONG uarfcn](#)

### 8.1045.1 Detailed Description

This structure contains the parameters for WCDMA UARFCN.

#### Parameters

<i>status</i>	<ul style="list-style-type: none"> <li>• 0 - Disable</li> <li>• 1 - Enable</li> </ul>
<i>uarfcn</i>	<ul style="list-style-type: none"> <li>• UARFCN to which UE is locked</li> </ul>

### 8.1045.2 Field Documentation

- 8.1045.2.1 BYTE wcdmaUARFCN::status
- 8.1045.2.2 ULONG wcdmaUARFCN::uarfcn

## 8.1046 wds\_currNetworkInfo Struct Reference

## Data Fields

- uint8\_t [NetworkType](#)
- uint32\_t [RATMask](#)
- uint32\_t [SOMask](#)

### 8.1046.1 Detailed Description

Network information structure

Parameters

<i>NetworkType</i>	<ul style="list-style-type: none"> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - 3GPP</li> <li>– 1 - 3GPP2</li> </ul> </li> </ul>
<i>RATMask</i>	<ul style="list-style-type: none"> <li>• Radio Access Technology (RAT) mask to indicate the type of technology.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Don't Care</li> <li>– 0x8000 - NULL Bearer</li> </ul> </li> <li>• CDMA RAT mask values: <ul style="list-style-type: none"> <li>– 0x01 - CDMA_1x</li> <li>– 0x02 - EVDO_REV0</li> <li>– 0x04 - EVDO_REVA</li> <li>– 0x08 - EVDO_REVB</li> <li>– 0x10 - EHRPD</li> <li>– 0x20 - FMC</li> </ul> </li> <li>• UMTS RAT mask values: <ul style="list-style-type: none"> <li>– 0x01 - WCDMA</li> <li>– 0x02 - GPRS</li> <li>– 0x04 - HSDPA</li> <li>– 0x08 - HSUPA</li> <li>– 0x10 - EDGE</li> <li>– 0x20 - LTE</li> <li>– 0x40 - HSDPA+</li> <li>– 0x80 - DC_HSDPA+</li> <li>– 0x100 - 64_QAM</li> <li>– 0x200 - TDSCDMA</li> </ul> </li> </ul>

<i>SOMask</i>	<ul style="list-style-type: none"> <li>• Service Option (SO) mask to indicate the service option or type of application.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - Don't Care</li> </ul> </li> <li>• CDMA 1x SO mask values: <ul style="list-style-type: none"> <li>– 0x01 - CDMA_1X_IS95</li> <li>– 0x02 - CDMA_1X_IS2000</li> <li>– 0x04 - CDMA_1X_IS2000_REL_A</li> </ul> </li> <li>• CDMA EV-DO Rev 0 SO mask values: <ul style="list-style-type: none"> <li>– 0x01 - DPA</li> </ul> </li> <li>• CDMA EV-DO Rev A SO mask values: <ul style="list-style-type: none"> <li>– 0x01 - DPA</li> <li>– 0x02 - MFPA</li> <li>– 0x04 - EMPA</li> <li>– 0x08 - EMPA_EHRPD</li> </ul> </li> <li>• CDMA EV-DO Rev B SO mask values: <ul style="list-style-type: none"> <li>– 0x01 - DPA</li> <li>– 0x02 - MFPA</li> <li>– 0x04 - EMPA</li> <li>– 0x08 - EMPA_EHRPD</li> <li>– 0x10 - MMPA</li> <li>– 0x20 - MMPA_EHRPD</li> </ul> </li> </ul>
---------------	--

## 8.1046.2 Field Documentation

8.1046.2.1 `uint8_t wds_currNetworkInfo::NetworkType`

8.1046.2.2 `uint32_t wds_currNetworkInfo::RATMask`

8.1046.2.3 `uint32_t wds_currNetworkInfo::SOMask`

## 8.1047 wds\_Domain Struct Reference

### Data Fields

- `uint16_t domainLen`
- `uint8_t domainName` [256]

### 8.1047.1 Detailed Description

This structure contains the DomainName Information

## Parameters

<i>domainLen</i>	<ul style="list-style-type: none"><li>length of the recieved <a href="#">Domain</a> name</li></ul>
<i>domainName</i>	<ul style="list-style-type: none"><li><a href="#">Domain</a> name(Max 256 characters)</li></ul>

## 8.1047.2 Field Documentation

8.1047.2.1 `uint16_t wds_Domain::domainLen`

8.1047.2.2 `uint8_t wds_Domain::domainName[256]`

## 8.1048 wds\_DomainNameList Struct Reference

## Data Fields

- `uint8_t numInstances`
- struct [wds\\_Domain domain](#) [10]

### 8.1048.1 Detailed Description

This structure contains the [DomainNameList](#) Information

## Parameters

<i>numInstances</i>	<ul style="list-style-type: none"><li>Number of <a href="#">Domain</a> name received</li></ul>
<i>domain</i>	<ul style="list-style-type: none"><li><a href="#">Domain</a> name information(Max 10 Domain names)</li></ul>

## 8.1048.2 Field Documentation

8.1048.2.1 `struct wds_Domain wds_DomainNameList::domain[10]`

8.1048.2.2 `uint8_t wds_DomainNameList::numInstances`

## 8.1049 wds\_GPRSQoS Struct Reference

## Data Fields

- `uint32_t precedenceClass`
- `uint32_t delayClass`
- `uint32_t reliabilityClass`
- `uint32_t peakThroughputClass`
- `uint32_t meanThroughputClass`

### 8.1049.1 Detailed Description

This structure contains the GPRS Quality Of Service Information

## Parameters

<i>precedence-Class</i>	<ul style="list-style-type: none"> <li>• Precedence class</li> </ul>
<i>delayClass</i>	<ul style="list-style-type: none"> <li>• Delay class</li> </ul>
<i>reliabilityClass</i>	<ul style="list-style-type: none"> <li>• Reliability class</li> </ul>
<i>peak-Throughput-Class</i>	<ul style="list-style-type: none"> <li>• Peak throughput class</li> </ul>
<i>mean-Throughput-Class</i>	<ul style="list-style-type: none"> <li>• Mean throughput class</li> </ul>

## 8.1049.2 Field Documentation

8.1049.2.1 `uint32_t wds_GPRSQoS::delayClass`8.1049.2.2 `uint32_t wds_GPRSQoS::meanThroughputClass`8.1049.2.3 `uint32_t wds_GPRSQoS::peakThroughputClass`8.1049.2.4 `uint32_t wds_GPRSQoS::precedenceClass`8.1049.2.5 `uint32_t wds_GPRSQoS::reliabilityClass`8.1050 `wds_IPV6AddressInfo` Struct Reference

## Data Fields

- `uint8_t IPV6PrefixLen`
- `uint16_t IPAddressV6 [8]`

## 8.1050.1 Detailed Description

This structure contains the IPV6 Address Information

## Parameters

<i>IPV6PrefixLen</i>	<ul style="list-style-type: none"> <li>• Length of the received IPv6 address in no. of bits; can take value between 0 and 128 – 0xFF - Not Available</li> </ul>
<i>IPAddressV6</i>	<ul style="list-style-type: none"> <li>• IPv6 address(in network byte order); This is an 8-element array of 16 bit numbers, each of which is in big endian format.</li> </ul>



## 8.1050.2 Field Documentation

8.1050.2.1 uint16\_t wds\_IPV6AddressInfo::IPAddressV6[8]

8.1050.2.2 uint8\_t wds\_IPV6AddressInfo::IPv6PrefixLen

## 8.1051 wds\_IPV6GWAddressInfo Struct Reference

### Data Fields

- uint8\_t [gwV6PrefixLen](#)
- uint16\_t [gwAddressV6](#) [8]

### 8.1051.1 Detailed Description

This structure contains the IPV6 Gateway Address Information

#### Parameters

<i>gwV6PrefixLen</i>	<ul style="list-style-type: none"> <li>• Length of the received IPV6 Gateway address in no. of bits; can take value between 0 and 128</li> </ul>
<i>IPAddressV6</i>	<ul style="list-style-type: none"> <li>• IPV6 Gateway address(in network byte order); This is an 8-element array of 16 bit numbers, each of which is in big endian format.</li> </ul>

## 8.1051.2 Field Documentation

8.1051.2.1 uint16\_t wds\_IPV6GWAddressInfo::gwAddressV6[8]

8.1051.2.2 uint8\_t wds\_IPV6GWAddressInfo::gwV6PrefixLen

## 8.1052 wds\_PCSCFFQDNAddress Struct Reference

### Data Fields

- uint16\_t [fqdnLen](#)
- uint8\_t [fqdnAddr](#) [256]

### 8.1052.1 Detailed Description

This structure contains the [PCSCFFQDNAddress](#) Information

#### Parameters

<i>fqdnLen</i>	<ul style="list-style-type: none"> <li>• length of the received FQDN address</li> </ul>
<i>fqdnAddr</i>	<ul style="list-style-type: none"> <li>• FQDN address(Max 256 characters)</li> </ul>

### 8.1052.2 Field Documentation

8.1052.2.1 `uint8_t wds_PCSCFFQDNAddress::fqdnAddr[256]`

8.1052.2.2 `uint16_t wds_PCSCFFQDNAddress::fqdnLen`

## 8.1053 wds\_PCSCFFQDNAddressList Struct Reference

### Data Fields

- `uint8_t numInstances`
- `struct wds_PCSCFFQDNAddress pcsfFQDNAddress [10]`

### 8.1053.1 Detailed Description

This structure contains the [PCSCFFQDNAddressList](#) Information

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• Number of FQDN addresses received</li> </ul>
<i>pcsfFQDN-Address</i>	<ul style="list-style-type: none"> <li>• FQDN address information(Max 10 addresses)</li> </ul>

### 8.1053.2 Field Documentation

8.1053.2.1 `uint8_t wds_PCSCFFQDNAddressList::numInstances`

8.1053.2.2 `struct wds_PCSCFFQDNAddress wds_PCSCFFQDNAddressList::pcsfFQDNAddress[10]`

## 8.1054 wds\_PCSCFIPv4ServerAddressList Struct Reference

### Data Fields

- `uint8_t numInstances`
- `uint32_t pcsfIPv4Addr [64]`

### 8.1054.1 Detailed Description

This structure contains the [PCSCFIPv4ServerAddressList](#) Information

#### Parameters

<i>numInstances</i>	<ul style="list-style-type: none"> <li>• number of address following</li> </ul>
<i>pcsfIPv4Addr</i>	<ul style="list-style-type: none"> <li>• P-CSCF IPv4 server addresses(Max 16 address, 4 bytes each)</li> </ul>

## 8.1054.2 Field Documentation

8.1054.2.1 `uint8_t wds_PCSCFIPv4ServerAddressList::numInstances`

8.1054.2.2 `uint32_t wds_PCSCFIPv4ServerAddressList::pcscfIPv4Addr[64]`

## 8.1055 wds\_ProfileIdentifier Struct Reference

### Data Fields

- `uint8_t` [profileType](#)
- `uint8_t` [profileIndex](#)

### 8.1055.1 Detailed Description

This structure contains the Profile Identifier Information

#### Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>• Identifies the type of profile 0x00 = 3GPP</li> </ul>
<i>profileIndex</i>	<ul style="list-style-type: none"> <li>• Index of profile whose settings were loaded prior to session parameter negotiation for the current call. If this TLV is not present, data call parameters are based on device default settings for each parameter</li> </ul>

## 8.1055.2 Field Documentation

8.1055.2.1 `uint8_t wds_ProfileIdentifier::profileIndex`

8.1055.2.2 `uint8_t wds_ProfileIdentifier::profileType`

## 8.1056 wds\_profileInfo Union Reference

### Data Fields

- [LibPackprofile\\_3GPP](#) `SlqsProfile3GPP`
- [LibPackprofile\\_3GPP2](#) `SlqsProfile3GPP2`

### 8.1056.1 Detailed Description

This union consist of `profile_3GPP` and `profile_3GPP2` out of which one will be used to create profile.

## 8.1056.2 Field Documentation

8.1056.2.1 `LibPackprofile_3GPP wds_profileInfo::SlqsProfile3GPP`

8.1056.2.2 `LibPackprofile_3GPP2 wds_profileInfo::SlqsProfile3GPP2`

## 8.1057 wds\_UMTSMinQoS Struct Reference

### Data Fields

- uint8\_t [trafficClass](#)
- uint32\_t [maxUplinkBitrate](#)
- uint32\_t [maxDownlinkBitrate](#)
- uint32\_t [grntUplinkBitrate](#)
- uint32\_t [grntDownlinkBitrate](#)
- uint8\_t [qosDeliveryOrder](#)
- uint32\_t [maxSDUSize](#)
- uint8\_t [sduErrorRatio](#)
- uint8\_t [resBerRatio](#)
- uint8\_t [deliveryErrSDU](#)
- uint32\_t [transferDelay](#)
- uint32\_t [trafficPriority](#)

### 8.1057.1 Detailed Description

This structure contains the UMTS Quality Of Service Information

#### Parameters

<i>trafficClass</i>	<ul style="list-style-type: none"> <li>• 0x00 - Subscribed</li> <li>• 0x01 - Conversational</li> <li>• 0x02 - Streaming</li> <li>• 0x03 - Interactive</li> <li>• 0x04 - Background</li> </ul>
<i>maxUplinkBitrate</i>	<ul style="list-style-type: none"> <li>• Maximum uplink bit rate in bits/sec</li> </ul>
<i>maxDownlink- Bitrate</i>	<ul style="list-style-type: none"> <li>• Maximum downlink bit rate in bits/sec</li> </ul>
<i>grntUplinkBitrate</i>	<ul style="list-style-type: none"> <li>• Guaranteed uplink bit rate in bits/sec</li> </ul>
<i>grntDownlink- Bitrate</i>	<ul style="list-style-type: none"> <li>• Guaranteed downlink bit rate in bits/sec</li> </ul>
<i>qosDelivery- Order</i>	<ul style="list-style-type: none"> <li>- Qos delivery order</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - Delivery order on</li> <li>• 0x02 - Delivery order off</li> </ul>

<i>maxSDUSize</i>	<ul style="list-style-type: none"> <li>• Maximum SDU size</li> </ul>
<i>sduErrorRatio</i>	<p>- SDU error ratio</p> <ul style="list-style-type: none"> <li>• Target value for fraction of SDUs lost or detected as erroneous.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>1 \times 10^{-2}</math></li> <li>• 0x02 - <math>7 \times 10^{-3}</math></li> <li>• 0x03 - <math>1 \times 10^{-3}</math></li> <li>• 0x04 - <math>1 \times 10^{-4}</math></li> <li>• 0x05 - <math>1 \times 10^{-5}</math></li> <li>• 0x06 - <math>1 \times 10^{-6}</math></li> <li>• 0x07 - <math>1 \times 10^{-1}</math></li> </ul>
<i>resBerRatio</i>	<p>- Residual bit error ratio</p> <ul style="list-style-type: none"> <li>• Target value for undetected bit error ratio in the delivered SDUs.</li> <li>• 0x00 - Subscribe</li> <li>• 0x01 - <math>5 \times 10^{-2}</math></li> <li>• 0x02 - <math>1 \times 10^{-2}</math></li> <li>• 0x03 - <math>5 \times 10^{-3}</math></li> <li>• 0x04 - <math>4 \times 10^{-3}</math></li> <li>• 0x05 - <math>1 \times 10^{-3}</math></li> <li>• 0x06 - <math>1 \times 10^{-4}</math></li> <li>• 0x07 - <math>1 \times 10^{-5}</math></li> <li>• 0x08 - <math>1 \times 10^{-6}</math></li> <li>• 0x09 - <math>1 \times 10^{-8}</math></li> </ul>

<i>deliveryErrSDU</i>	- delivery of erroneous SDUs <ul style="list-style-type: none"> <li>Indicates whether SDUs detected as erroneous shall be delivered or not.</li> <li>0x00 - Subscribe</li> <li>0x01 - <math>5 \cdot 10^{-2}</math></li> <li>0x02 - <math>1 \cdot 10^{-2}</math></li> <li>0x03 - <math>5 \cdot 10^{-3}</math></li> <li>0x04 - <math>4 \cdot 10^{-3}</math></li> <li>0x05 - <math>1 \cdot 10^{-3}</math></li> <li>0x06 - <math>1 \cdot 10^{-4}</math></li> <li>0x07 - <math>1 \cdot 10^{-5}</math></li> <li>0x08 - <math>1 \cdot 10^{-6}</math></li> <li>0x09 - <math>1 \cdot 10^{-8}</math></li> </ul>
<i>transferDelay</i>	- Transfer delay (ms) <ul style="list-style-type: none"> <li>Indicates the targeted time between a request to transfer an SDU at one SAP to its delivery at the other SAP in milliseconds.</li> </ul>
<i>trafficPriority</i>	- Transfer handling priority <ul style="list-style-type: none"> <li>Specifies the relative importance for handling of SDUs that belong to the UMTS bearer, compared to the SDUs of other bearers.</li> </ul>

## 8.1057.2 Field Documentation

- 8.1057.2.1 `uint8_t wds_UMTSMInQoS::deliveryErrSDU`
- 8.1057.2.2 `uint32_t wds_UMTSMInQoS::grntDownlinkBitrate`
- 8.1057.2.3 `uint32_t wds_UMTSMInQoS::grntUplinkBitrate`
- 8.1057.2.4 `uint32_t wds_UMTSMInQoS::maxDownlinkBitrate`
- 8.1057.2.5 `uint32_t wds_UMTSMInQoS::maxSDUSize`
- 8.1057.2.6 `uint32_t wds_UMTSMInQoS::maxUplinkBitrate`
- 8.1057.2.7 `uint8_t wds_UMTSMInQoS::qosDeliveryOrder`
- 8.1057.2.8 `uint8_t wds_UMTSMInQoS::resBerRatio`
- 8.1057.2.9 `uint8_t wds_UMTSMInQoS::sduErrorRatio`
- 8.1057.2.10 `uint8_t wds_UMTSMInQoS::trafficClass`
- 8.1057.2.11 `uint32_t wds_UMTSMInQoS::trafficPriority`
- 8.1057.2.12 `uint32_t wds_UMTSMInQoS::transferDelay`

## 8.1058 WdsByteTotals Struct Reference

### Data Fields

- [ULONG](#) \* [pV4sessionId](#)
- [ULONG](#) \* [pV6sessionId](#)
- struct [WdsByteTotalsElmnts](#) [ByteTotalsElmntsV4](#)
- struct [WdsByteTotalsElmnts](#) [ByteTotalsElmntsV6](#)

### 8.1058.1 Detailed Description

WDS ByteTotals request data structure

#### Parameters

<i>pV4sessionId</i>	<ul style="list-style-type: none"> <li>• The v4 session ID for which the byte totals are to be retrieved</li> <li>• provide a NULL pointer if not applicable</li> </ul>
<i>pV6sessionId</i>	<ul style="list-style-type: none"> <li>• The v6 session ID for which the byte totals are to be retrieved</li> <li>• provide a NULL pointer if not applicable</li> </ul>
<i>ByteTotals-ElmntsV4</i>	<ul style="list-style-type: none"> <li>• data structure to be populated with the byte totals for V4 session</li> </ul>
<i>ByteTotals-ElmntsV6</i>	<ul style="list-style-type: none"> <li>• data structure to be populated with the byte totals for V6 session</li> </ul>

#### Note

At least one of [pV4sessionId](#) and [pV6sessionId](#) must point to a valid session ID.

### 8.1058.2 Field Documentation

8.1058.2.1 struct [WdsByteTotalsElmnts](#) [WdsByteTotals::ByteTotalsElmntsV4](#)

8.1058.2.2 struct [WdsByteTotalsElmnts](#) [WdsByteTotals::ByteTotalsElmntsV6](#)

8.1058.2.3 [ULONG](#)\* [WdsByteTotals::pV4sessionId](#)

8.1058.2.4 [ULONG](#)\* [WdsByteTotals::pV6sessionId](#)

## 8.1059 WdsByteTotalsElmnts Struct Reference

### Data Fields

- [ULONGLONG](#) \* [pTXTotalBytes](#)
- [ULONGLONG](#) \* [pRXTotalBytes](#)

### 8.1059.1 Detailed Description

WDS Bytes Totals request data structure for individual session



## Parameters

<i>pTXTotalBytes</i>	<ul style="list-style-type: none"> <li>No of transmitted bytes without error.</li> </ul>
<i>pRXTotalBytes</i>	<ul style="list-style-type: none"> <li>No of received bytes without error.</li> </ul>

## 8.1059.2 Field Documentation

8.1059.2.1 `ULONGLONG*` WdsByteTotalsElmnts::pRXTotalBytes8.1059.2.2 `ULONGLONG*` WdsByteTotalsElmnts::pTXTotalBytes

## 8.1060 WdsClientLeaseChange Struct Reference

## Data Fields

- `BYTE *` [pEnableNotification](#)

## 8.1060.1 Detailed Description

WDS SWI DHCPv4 Client Lease Change Structure

## Parameters

<i>pEnable-Notification</i>	[IN] <ul style="list-style-type: none"> <li>Enable Notification or not</li> </ul>
-----------------------------	---

## 8.1060.2 Field Documentation

8.1060.2.1 `BYTE*` WdsClientLeaseChange::pEnableNotification

## 8.1061 WdsConnectionRate Struct Reference

## Data Fields

- `ULONG *` [pV4sessionId](#)
- `ULONG *` [pV6sessionId](#)
- struct [WdsConnectionRateElmnts ConnRateElmntsV4](#)
- struct [WdsConnectionRateElmnts ConnRateElmntsV6](#)

## 8.1061.1 Detailed Description

WDS ConnectionRate request data structure

## Parameters

<i>pV4sessionId</i>	<ul style="list-style-type: none"> <li>• The v4 session ID for which the connection rate are to be retrieved</li> <li>• provide a NULL pointer if not applicable</li> </ul>
<i>pV6sessionId</i>	<ul style="list-style-type: none"> <li>• The v6 session ID for which the connection rate are to be retrieved</li> <li>• provide a NULL pointer if not applicable</li> </ul>
<i>ConnRate-ElmntsV4</i>	<ul style="list-style-type: none"> <li>• data structure to be populated with the connection rate for V4 session</li> </ul>
<i>ConnRate-ElmntsV6</i>	<ul style="list-style-type: none"> <li>• data structure to be populated with the connection rate for V6 session</li> </ul>

## Note

At least one of pV4sessionId and pV6sessionId must point to a valid session ID.

## 8.1061.2 Field Documentation

8.1061.2.1 struct WdsConnectionRateElmnts WdsConnectionRate::ConnRateElmntsV4

8.1061.2.2 struct WdsConnectionRateElmnts WdsConnectionRate::ConnRateElmntsV6

8.1061.2.3 ULONG\* WdsConnectionRate::pV4sessionId

8.1061.2.4 ULONG\* WdsConnectionRate::pV6sessionId

## 8.1062 WdsConnectionRateElmnts Struct Reference

## Data Fields

- ULONG \* pCurrentChannelTXRate
- ULONG \* pCurrentChannelRXRate
- ULONG \* pMaxChannelTXRate
- ULONG \* pMaxChannelRXRate

## 8.1062.1 Detailed Description

WDS Connection rates request data structure for individual session

## Parameters

<i>pCurrent-ChannelTX-Rate[OUT]</i>	<ul style="list-style-type: none"> <li>• Instantaneous channel Tx rate in bits per second.</li> </ul>
-------------------------------------	---

<i>pCurrentChannelRXRate[OUT]</i>	<ul style="list-style-type: none"> <li>Instantaneous channel Rx rate in bits per second.</li> </ul>
<i>pMaxChannelTXRate[OUT]</i>	<ul style="list-style-type: none"> <li>Maximum Tx rate that can be assigned to the device by the</li> <li>serving system in bits per second</li> </ul>
<i>pMaxChannelRXRate[OUT]</i>	<ul style="list-style-type: none"> <li>Maximum Rx rate that can be assigned to the device by the</li> <li>serving system in bits per second</li> </ul>

## 8.1062.2 Field Documentation

8.1062.2.1 **ULONG\*** WdsConnectionRateElmnts::pCurrentChannelRXRate

8.1062.2.2 **ULONG\*** WdsConnectionRateElmnts::pCurrentChannelTXRate

8.1062.2.3 **ULONG\*** WdsConnectionRateElmnts::pMaxChannelRXRate

8.1062.2.4 **ULONG\*** WdsConnectionRateElmnts::pMaxChannelTXRate

## 8.1063 WdsDHCPv4ClientLeaseInd Struct Reference

### Data Fields

- [WdsDHCPv4ProfileId](#) \* [pProfileId](#)
- [BYTE](#) \* [pLeaseState](#)
- [ULONG](#) \* [pIPv4Addr](#)
- [DHCPOptionList](#) \* [pOptList](#)

### 8.1063.1 Detailed Description

This structure contains DHCPv4 client lease status

## Parameters

<i>pProfileId</i>	<ul style="list-style-type: none"> <li>• Profile Type and Id</li> </ul>
<i>pLeaseState</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - active, newly acquired</li> <li>– 1 - active, renewed</li> <li>– 2 - active, renewing</li> <li>– 3 - active, rebinding</li> <li>– 4 - inactive, expired</li> <li>– 5 - inactive, renew refused</li> <li>– 6 - inactive, rebind refused</li> <li>– 7 - inactive, other</li> </ul> </li> </ul>
<i>pIPv4Addr</i>	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– IPv4 Address</li> </ul> </li> </ul>
<i>pOptList</i>	<ul style="list-style-type: none"> <li>• Option list</li> </ul>

## 8.1063.2 Field Documentation

8.1063.2.1 `ULONG*` WdsDHCPv4ClientLeaseInd::pIPv4Addr8.1063.2.2 `BYTE*` WdsDHCPv4ClientLeaseInd::pLeaseState8.1063.2.3 `DHCPOptionList*` WdsDHCPv4ClientLeaseInd::pOptList8.1063.2.4 `WdsDHCPv4ProfileId*` WdsDHCPv4ClientLeaseInd::pProfileId

## 8.1064 WdsDHCPv4Config Struct Reference

## Data Fields

- [WdsDHCPv4ProfileId](#) \* [pProfileId](#)
- [WdsDHCPv4HWConfig](#) \* [pHwConfig](#)
- [WdsDHCPv4OptionList](#) \* [pRequestOptionList](#)

## 8.1064.1 Detailed Description

WDS SWI DHCPv4 Config Structure

## Parameters

<i>pProfileId</i>	[IN] <ul style="list-style-type: none"> <li>• pointer to Profile Id structure</li> </ul>
<i>pHWConfig</i>	[IN/OUT] <ul style="list-style-type: none"> <li>• pointer to HW Config structure</li> </ul>
<i>pRequestOption-List</i>	[IN/OUT] <ul style="list-style-type: none"> <li>• pointer to Option List structure to be sent in DHCP request</li> </ul>

## 8.1064.2 Field Documentation

8.1064.2.1 WdsDHCPv4HWConfig\* WdsDHCPv4Config::pHwConfig

8.1064.2.2 WdsDHCPv4ProfileId\* WdsDHCPv4Config::pProfileId

8.1064.2.3 WdsDHCPv4OptionList\* WdsDHCPv4Config::pRequestOptionList

## 8.1065 wdsDhcpv4HwConfig Struct Reference

## Data Fields

- uint8\_t [hwType](#)
- uint8\_t [chaddrLen](#)
- uint8\_t [chaddr](#) [16]

## 8.1065.1 Detailed Description

## Parameters

<i>hwType</i>	DHCP HW Type, examples: <ul style="list-style-type: none"> <li>• 0 - Ethernet</li> <li>• 20 - Serial</li> </ul>
<i>chaddrLen</i>	Length of chaddr field, examples: <ul style="list-style-type: none"> <li>• 6 for Ethernet MAC address</li> </ul>
<i>chaddr</i>	Client hardware address

## 8.1065.2 Field Documentation

8.1065.2.1 uint8\_t wdsDhcpv4HwConfig::chaddr[16]

8.1065.2.2 uint8\_t wdsDhcpv4HwConfig::chaddrLen

8.1065.2.3 uint8\_t wdsDhcpv4HwConfig::hwType

## 8.1066 WdsDHCPv4HWConfig Struct Reference

### Data Fields

- [BYTE hwType](#)
- [BYTE chaddrLen](#)
- [BYTE chaddr](#) [16]

### 8.1066.1 Detailed Description

WDS SWI DHCPv4 HW Config Structure.

#### Parameters

<i>hwType</i>	<ul style="list-style-type: none"><li>• HW Type 1 - Ethernet 20 - Serial</li></ul>
<i>chaddrlen</i>	<ul style="list-style-type: none"><li>• chaddrlen</li></ul>
<i>chaddr</i>	<ul style="list-style-type: none"><li>• chaddr. Max size 16 bytes</li></ul>

### 8.1066.2 Field Documentation

8.1066.2.1 [BYTE WdsDHCPv4HWConfig::chaddr\[16\]](#)

8.1066.2.2 [BYTE WdsDHCPv4HWConfig::chaddrLen](#)

8.1066.2.3 [BYTE WdsDHCPv4HWConfig::hwType](#)

## 8.1067 WdsDHCPv4Option Struct Reference

### Data Fields

- [BYTE optCode](#)
- [BYTE optValLen](#)
- [BYTE optVal](#) [255]

### 8.1067.1 Detailed Description

WDS SWI DHCPv4 Option Structure

## Parameters

<i>optCode</i>	<ul style="list-style-type: none"> <li>Option code <ul style="list-style-type: none"> <li>– 0 - 255</li> </ul> </li> </ul>
<i>optValLen</i>	<ul style="list-style-type: none"> <li>Option value length <ul style="list-style-type: none"> <li>– 0 - 255</li> </ul> </li> </ul>
<i>optVal</i>	<ul style="list-style-type: none"> <li>Option value</li> </ul>

## 8.1067.2 Field Documentation

8.1067.2.1 BYTE WdsDHCPv4Option::optCode

8.1067.2.2 BYTE WdsDHCPv4Option::optVal[255]

8.1067.2.3 BYTE WdsDHCPv4Option::optValLen

## 8.1068 wdsDhcpv4Option Struct Reference

## Data Fields

- uint8\_t [optCode](#)
- uint8\_t [optValLen](#)
- uint8\_t [optVal](#) [255]

## 8.1068.1 Detailed Description

## Parameters

<i>optCode</i>	Option code <ul style="list-style-type: none"> <li>• 0 - 255</li> </ul>
<i>optValLen</i>	Option value length <ul style="list-style-type: none"> <li>• 0 - 255</li> </ul>
<i>optVal</i>	Option Value

## 8.1068.2 Field Documentation

8.1068.2.1 uint8\_t wdsDhcpv4Option::optCode

8.1068.2.2 uint8\_t wdsDhcpv4Option::optVal[255]

8.1068.2.3 uint8\_t wdsDhcpv4Option::optValLen

## 8.1069 wdsDhcpv4OptionList Struct Reference

### Data Fields

- [uint8\\_t numOpt](#)
- [wdsDhcpv4Option](#) \* [pOptList](#)

### 8.1069.1 Detailed Description

#### Parameters

<i>numOpt</i>	number of options <ul style="list-style-type: none"> <li>• 0 - 255</li> </ul>
<i>pOptList</i>	pointer to list of DHCP Options

### 8.1069.2 Field Documentation

8.1069.2.1 [uint8\\_t wdsDhcpv4OptionList::numOpt](#)

8.1069.2.2 [wdsDhcpv4Option](#)\* [wdsDhcpv4OptionList::pOptList](#)

## 8.1070 WdsDHCPv4OptionList Struct Reference

### Data Fields

- [BYTE numOpt](#)
- [WdsDHCPv4Option](#) \* [pOptList](#)

### 8.1070.1 Detailed Description

WDS SWI DHCPv4 Option List Structure

#### Parameters

<i>numOpt</i>	<ul style="list-style-type: none"> <li>• number of options  — 0 - 255</li> </ul>
<i>pOptList</i>	<ul style="list-style-type: none"> <li>• pointer to list of DHCP Options</li> </ul>

### 8.1070.2 Field Documentation

8.1070.2.1 [BYTE WdsDHCPv4OptionList::numOpt](#)

8.1070.2.2 [WdsDHCPv4Option](#)\* [WdsDHCPv4OptionList::pOptList](#)



## 8.1071 wdsDhcpv4ProfileId Struct Reference

### Data Fields

- uint8\_t [profileType](#)
- uint8\_t [profileId](#)

#### 8.1071.1 Detailed Description

##### Parameters

<i>profileType</i>	profile type <ul style="list-style-type: none"><li>• 0 - 3GPP</li></ul>
<i>profileId</i>	profile index <ul style="list-style-type: none"><li>• index identifying the profile 1-24 valid for 3GPP profile type (EM74xx and onwards)</li></ul>

#### 8.1071.2 Field Documentation

8.1071.2.1 uint8\_t wdsDhcpv4ProfileId::profileId

8.1071.2.2 uint8\_t wdsDhcpv4ProfileId::profileType

## 8.1072 WdsDHCPv4ProfileId Struct Reference

### Data Fields

- BYTE [profileType](#)
- BYTE [profileId](#)

#### 8.1072.1 Detailed Description

WDS SWI DHCPv4 Profile Identifier Structure

##### Parameters

<i>profileType</i>	<ul style="list-style-type: none"><li>• 0 for 3GPP</li></ul>
<i>profileId</i>	<ul style="list-style-type: none"><li>• 1 to 24 for 3GPP profile</li></ul>

#### 8.1072.2 Field Documentation

8.1072.2.1 BYTE WdsDHCPv4ProfileId::profileId

8.1072.2.2 BYTE WdsDHCPv4ProfileId::profileType

## 8.1073 WDSGetLoopbackData Struct Reference

### Data Fields

- [BYTE ByteLoopbackMode](#)
- [BYTE ByteLoopbackMultiplier](#)

### 8.1073.1 Detailed Description

This API to Queries Enable/disable Data Loopback Mode and set the value of loopback multiplier.

#### Parameters

<i>pReq</i>	[IN]
	<ul style="list-style-type: none"> <li>• See <a href="#">WDSSetLoopbackData</a> for more information</li> </ul>

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

WDS SWI Get Loopback Structure of Packet Data Connection Information.

#### Parameters

<i>ByteLoopback-Mode</i>	<ul style="list-style-type: none"> <li>• Loopback Mode. <ul style="list-style-type: none"> <li>– 0 - Disable</li> <li>– 1 - Enable</li> </ul> </li> </ul>
<i>ByteLoopback-Multiplier</i>	<ul style="list-style-type: none"> <li>• Loopback multiplier. Number of downlink bytes to send for each uplink byte.</li> </ul>

### 8.1073.2 Field Documentation

8.1073.2.1 **BYTE** WDSGetLoopbackData::ByteLoopbackMode

8.1073.2.2 **BYTE** WDSGetLoopbackData::ByteLoopbackMultiplier

## 8.1074 WdsIpAddressInfoReq Struct Reference

### Data Fields

- [ULONG](#) \* [pv4sessionId](#)
- [ULONG](#) \* [pv6sessionId](#)
- [QmiWdsIpAddressInfo](#) ip

### 8.1074.1 Field Documentation

8.1074.1.1 `QmiWdsIpAddressInfo WdsIpAddressInfoReq::ip`

8.1074.1.2 `ULONG* WdsIpAddressInfoReq::pv4sessionId`

8.1074.1.3 `ULONG* WdsIpAddressInfoReq::pv6sessionId`

## 8.1075 WdsPktStatisticsElmnts Struct Reference

### Data Fields

- `ULONG * pTXPacketSuccesses`
- `ULONG * pRXPacketSuccesses`
- `ULONG * pTXPacketErrors`
- `ULONG * pRXPacketErrors`
- `ULONG * pTXPacketOverflows`
- `ULONG * pRXPacketOverflows`
- `ULONGLONG * pTXOkBytesCount`
- `ULONGLONG * pRXOkBytesCount`
- `ULONGLONG * pTXOKBytesLastCall`
- `ULONGLONG * pRXOKBytesLastCall`
- `ULONG * pTXDroppedCount`
- `ULONG * pRXDroppedCount`

### 8.1075.1 Detailed Description

WDS Pkt Statistics request data structure for individual session

## Parameters

<i>pTXPacket-Successes</i>	<ul style="list-style-type: none"> <li>No of transmitted Packets without error.</li> </ul>
<i>pRXPacket-Successes</i>	<ul style="list-style-type: none"> <li>No of received Packets without error.</li> </ul>
<i>pTXPacketErrors</i>	<ul style="list-style-type: none"> <li>Number of outgoing packets with framing errors.</li> </ul>
<i>pRXPacket-Errors</i>	<ul style="list-style-type: none"> <li>Number of incoming packets with framing errors.</li> </ul>
<i>pTXPacket-Overflows</i>	<ul style="list-style-type: none"> <li>Number of packets dropped because Tx buffer overflowed (out of memory).</li> </ul>
<i>pRXPacket-Overflows</i>	<ul style="list-style-type: none"> <li>Number of packets dropped because Rx buffer overflowed (out of memory).</li> </ul>
<i>pTXOkBytes-Count</i>	<ul style="list-style-type: none"> <li>No of bytes transmitted without error.</li> </ul>
<i>pRXOkBytes-Count</i>	<ul style="list-style-type: none"> <li>No of bytes received without error.</li> </ul>
<i>pTXOKBytes-LastCall</i>	<ul style="list-style-type: none"> <li>No of bytes transmitted without error during the last data call (0 if no call was made earlier). Returned only if not in a call, and when the previous call was made using RmNet (for any devices that support</li> </ul>
<i>pRXOKBytes-LastCall</i>	<ul style="list-style-type: none"> <li>Number of bytes received without error during the last data call (0 if no call was made earlier). Returned only if not in a call, and when the previous call was made using RmNet (for any devices that support</li> </ul>
<i>pTXDropped-Count</i>	<ul style="list-style-type: none"> <li>Number of outgoing packets dropped.</li> </ul>
<i>pRXDropped-Count</i>	<ul style="list-style-type: none"> <li>Number of incoming packets dropped.</li> </ul>

## 8.1075.2 Field Documentation

8.1075.2.1 **ULONG\*** WdsPktStatisticsElmnts::pRXDroppedCount8.1075.2.2 **ULONGLONG\*** WdsPktStatisticsElmnts::pRXOkBytesCount8.1075.2.3 **ULONGLONG\*** WdsPktStatisticsElmnts::pRXOKBytesLastCall8.1075.2.4 **ULONG\*** WdsPktStatisticsElmnts::pRXPacketErrors

- 8.1075.2.5 **ULONG\*** WdsPktStatisticsElmnts::pRXPacketOverflows
- 8.1075.2.6 **ULONG\*** WdsPktStatisticsElmnts::pRXPacketSuccesses
- 8.1075.2.7 **ULONG\*** WdsPktStatisticsElmnts::pTXDroppedCount
- 8.1075.2.8 **ULONGLONG\*** WdsPktStatisticsElmnts::pTXOkBytesCount
- 8.1075.2.9 **ULONGLONG\*** WdsPktStatisticsElmnts::pTXOKBytesLastCall
- 8.1075.2.10 **ULONG\*** WdsPktStatisticsElmnts::pTXPacketErrors
- 8.1075.2.11 **ULONG\*** WdsPktStatisticsElmnts::pTXPacketOverflows
- 8.1075.2.12 **ULONG\*** WdsPktStatisticsElmnts::pTXPacketSuccesses

## 8.1076 WdsPktStatisticsReq Struct Reference

### Data Fields

- [ULONG](#) \* [pStatMask](#)

### 8.1076.1 Detailed Description

WDS PktStatistics request data structure

#### Parameters

<i>pStatMask</i>	<ul style="list-style-type: none"><li>• Packet Statistics Mask 0x00000001 - Tx packets OK 0x00000002 - Rx packets OK 0x00000004 - Tx packet errors 0x00000008 - Rx packet errors 0x00000010 - Tx overflows 0x00000020 - Rx overflows 0x00000040 - Tx bytes OK 0x00000080 - Rx bytes OK</li></ul>
------------------	--

### 8.1076.2 Field Documentation

- 8.1076.2.1 **ULONG\*** WdsPktStatisticsReq::pStatMask

## 8.1077 WdsPktStatisticsResp Struct Reference

### Data Fields

- [ULONG](#) \* [pV4sessionId](#)
- [ULONG](#) \* [pV6sessionId](#)
- struct [WdsPktStatisticsElmnts PktStatElmntsV4](#)
- struct [WdsPktStatisticsElmnts PktStatElmntsV6](#)

### 8.1077.1 Detailed Description

WDS PktStatistics response data structure

## Parameters

<i>pV4sessionId</i>	<ul style="list-style-type: none"> <li>• The v4 session ID for which the byte totals are to be retrieved</li> <li>• provide a NULL pointer if not applicable</li> </ul>
<i>pV6sessionId</i>	<ul style="list-style-type: none"> <li>• The v6 session ID for which the byte totals are to be retrieved</li> <li>• provide a NULL pointer if not applicable</li> </ul>
<i>PktStatElmntsV4</i>	<ul style="list-style-type: none"> <li>• data structure to be populated with the Pkt Statistics for V4 session</li> </ul>
<i>PktStatElmntsV6</i>	<ul style="list-style-type: none"> <li>• data structure to be populated with the Pkt Statistics for V6 session</li> </ul>

## Note

At least one of pV4sessionId and pV6sessionId must point to a valid session ID.

## 8.1077.2 Field Documentation

8.1077.2.1 struct `WdsPktStatisticsElmnts` `WdsPktStatisticsResp::PktStatElmntsV4`

8.1077.2.2 struct `WdsPktStatisticsElmnts` `WdsPktStatisticsResp::PktStatElmntsV6`

8.1077.2.3 `ULONG*` `WdsPktStatisticsResp::pV4sessionId`

8.1077.2.4 `ULONG*` `WdsPktStatisticsResp::pV6sessionId`

## 8.1078 WdsProfileParam Union Reference

## Data Fields

- struct [Profile3GPP](#) `SlqsProfile3GPP`
- struct [Profile3GPP2](#) `SlqsProfile3GPP2`

## 8.1078.1 Detailed Description

This union [WdsProfileParam](#) consist of [Profile3GPP](#) and [Profile3GPP2](#) out of which one will be used to create profile.

## 8.1078.2 Field Documentation

8.1078.2.1 struct `Profile3GPP` `WdsProfileParam::SlqsProfile3GPP`

8.1078.2.2 struct `Profile3GPP2` `WdsProfileParam::SlqsProfile3GPP2`

## 8.1079 WdsRunTimeSettings Struct Reference

## Data Fields

- [ULONG](#) \* [v4sessionId](#)
- [ULONG](#) \* [v6sessionId](#)
- struct [qmiWdsRunTimeSettings](#) [rts](#)

### 8.1079.1 Detailed Description

WDS runtime settings request data structure

#### Parameters

<a href="#">v4sessionId</a>	<ul style="list-style-type: none"> <li>• The v4 session ID for which the runtime settings are to be retrieved</li> <li>• provide a NULL pointer if not applicable</li> </ul>
<a href="#">v6sessionId</a>	<ul style="list-style-type: none"> <li>• The v6 session ID for which the runtime settings are to be retrieved</li> <li>• provide a NULL pointer if not applicable</li> </ul>
<a href="#">qmiWdsRunTimeSettings</a>	<ul style="list-style-type: none"> <li>• data structure to be populated with the runtime settings</li> </ul>

#### Note

At least one of [v4sessionId](#) and [v6sessionId](#) must point to a valid session ID.

### 8.1079.2 Field Documentation

8.1079.2.1 struct [qmiWdsRunTimeSettings](#) [WdsRunTimeSettings::rts](#)

8.1079.2.2 [ULONG](#)\* [WdsRunTimeSettings::v4sessionId](#)

8.1079.2.3 [ULONG](#)\* [WdsRunTimeSettings::v6sessionId](#)

## 8.1080 wdsSetEventReportReq Struct Reference

## Data Fields

- [BYTE](#) \* [pCurrChannelRateInd](#)
- [TrStatInd](#) \* [pTransferStatInd](#)
- [BYTE](#) \* [pDataBearerTechInd](#)
- [BYTE](#) \* [pDormancyStatusInd](#)
- [BYTE](#) \* [pMIPStatusInd](#)
- [BYTE](#) \* [pCurrDataBearerTechInd](#)
- [BYTE](#) \* [pDataCallStatusChangeInd](#)
- [BYTE](#) \* [pCurrPrefDataSysInd](#)
- [BYTE](#) \* [pEVDOPageMonPerChangeInd](#)
- [BYTE](#) \* [pDataSystemStatusChangeInd](#)

### 8.1080.1 Detailed Description

This structure contains the information about the Set Event Report Request parameters.



## Parameters

<i>pCurrChannel-RateInd</i>	(optional) <ul style="list-style-type: none"> <li>Current Channel Rate Indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report channel rate when it changes</li> </ul> </li> </ul>
<i>pTransferStatInd</i>	(optional) <ul style="list-style-type: none"> <li>See <a href="#">TrStatInd</a> for more information.</li> </ul>
<i>pDataBearer-TechInd</i>	(optional) <ul style="list-style-type: none"> <li>Data Bearer Technology Indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report radio interface used for data transfer when it changes</li> </ul> </li> </ul>
<i>pDormancy-StatusInd</i>	(optional) <ul style="list-style-type: none"> <li>Dormancy Status indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report traffic channel state of interface used for data connection</li> </ul> </li> </ul>
<i>pMIPStatusInd</i>	(optional) <ul style="list-style-type: none"> <li>MIP Status Indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report MIP status</li> </ul> </li> </ul>
<i>pCurrData-BearerTechInd</i>	(optional) <ul style="list-style-type: none"> <li>Current Data Bearer Technology Indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report current data bearer technology when it changes</li> </ul> </li> </ul>
<i>pDataCallStatus-ChangeInd</i>	(optional) <ul style="list-style-type: none"> <li>Data Call Status Change Indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report data call status change when it changes</li> </ul> </li> </ul>

<i>pCurrPrefData-SysInd</i>	(optional) <ul style="list-style-type: none"> <li>Current Preferred Data System Indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report preferred data system when it changes</li> </ul> </li> </ul>
<i>pEVDOPage-MonPerChange-Ind</i>	(optional) <ul style="list-style-type: none"> <li>EV-DO Page Monitor Period Change Indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report EV-DO page monitor period change event</li> </ul> </li> </ul>
<i>pDataSystem-StatusChange-Ind</i>	(optional) <ul style="list-style-type: none"> <li>Data System Status Change Indicator. <ul style="list-style-type: none"> <li>0 - Do not report</li> <li>1 - Report data system status change event</li> </ul> </li> </ul>

**Note**

At least one parameter should be present.

**8.1080.2 Field Documentation**

8.1080.2.1 **BYTE\*** wdsSetEventReportReq::pCurrChannelRateInd

8.1080.2.2 **BYTE\*** wdsSetEventReportReq::pCurrDataBearerTechInd

8.1080.2.3 **BYTE\*** wdsSetEventReportReq::pCurrPrefDataSysInd

8.1080.2.4 **BYTE\*** wdsSetEventReportReq::pDataBearerTechInd

8.1080.2.5 **BYTE\*** wdsSetEventReportReq::pDataCallStatusChangeInd

8.1080.2.6 **BYTE\*** wdsSetEventReportReq::pDataSystemStatusChangeInd

8.1080.2.7 **BYTE\*** wdsSetEventReportReq::pDormancyStatusInd

8.1080.2.8 **BYTE\*** wdsSetEventReportReq::pEVDOPageMonPerChangeInd

8.1080.2.9 **BYTE\*** wdsSetEventReportReq::pMIPStatusInd

8.1080.2.10 **TrStatInd\*** wdsSetEventReportReq::pTransferStatInd

**8.1081 WDSSetLoopbackData Struct Reference****Data Fields**

- BYTE\*** pLoopbackMode
- BYTE\*** pLoopbackMultiplier

### 8.1081.1 Detailed Description

WDS SWI Set Loopback Structure of Set Loopback Information.

## Parameters

<i>pLoopbackMode</i>	<ul style="list-style-type: none"> <li>• Loopback Mode. <ul style="list-style-type: none"> <li>– 0 - Disable</li> <li>– 1 - Enable</li> </ul> </li> </ul>
<i>pLoopback-Multiplier</i>	<ul style="list-style-type: none"> <li>• Loopback multiplier. Number of downlink bytes to send for each uplink byte.</li> </ul>

## 8.1081.2 Field Documentation

8.1081.2.1 BYTE\* WDSSetLoopbackData::pLoopbackMode

8.1081.2.2 BYTE\* WDSSetLoopbackData::pLoopbackMultiplier

## 8.1082 WDSSWICurrentChannelRates Struct Reference

## Data Fields

- unsigned long [current\\_channel\\_tx\\_rate](#)
- unsigned long [current\\_channel\\_rx\\_rate](#)
- unsigned long [max\\_channel\\_tx\\_rate](#)
- unsigned long [max\\_channel\\_rx\\_rate](#)

## 8.1082.1 Detailed Description

WDS SWI Current Channel Rates Structure of Packet Data Connection Information.

## Parameters

<i>current_channel-_tx_rate</i>	<ul style="list-style-type: none"> <li>• Current Channel Tx Rate.</li> </ul>
<i>current_channel-_rx_rate</i>	<ul style="list-style-type: none"> <li>• Current Channel Rx Rate.</li> </ul>
<i>max_channel_-tx_rate</i>	<ul style="list-style-type: none"> <li>• Max Channel Tx Rate.</li> </ul>
<i>max_channel_-rx_rate</i>	<ul style="list-style-type: none"> <li>• Max Channel Rx Rate.</li> </ul>

## 8.1082.2 Field Documentation

8.1082.2.1 unsigned long WDSSWICurrentChannelRates::current\_channel\_rx\_rate

8.1082.2.2 unsigned long WDSSWICurrentChannelRates::current\_channel\_tx\_rate

8.1082.2.3 unsigned long WDSSWICurrentChannelRates::max\_channel\_rx\_rate

8.1082.2.4 unsigned long WDSSWICurrentChannelRates::max\_channel\_tx\_rate



## Chapter 9

# File Documentation

### 9.1 apdoxypages.c File Reference

Contains the module declaration for the Doxygen output. Also contains the content of the main page and related pages.

#### Namespaces

- [Tables](#)

#### 9.1.1 Detailed Description

Contains the module declaration for the Doxygen output. Also contains the content of the main page and related pages.

### 9.2 common.h File Reference

#### Data Structures

- struct [pack\\_qmi\\_t](#)
- struct [unpack\\_qmi\\_t](#)

#### Macros

- `#define` [SDU\\_HDR\\_LEN](#) (3)
- `#define` [MINREQBKLEN](#) (2048)
- `#define` [MSGID\\_AND\\_LEN](#) (4)
- `#define` [MSGID\\_DONT\\_CARE](#) (0xffff)
- `#define` [UNUSEDPARAM](#)(x) (void)x
- `#define` [DEAULT\\_LOC\\_TIMEOUT\\_IN\\_SEC](#) 2
- `#define` [SDK\\_VALIDATE\\_INPUT\\_PACK\\_PARAM](#)(pCtx, pBuf, pLen)

#### Typedefs

- typedef void(\* [logger](#) )(uint8\_t lvl, const char \*buff)

## Enumerations

- enum `eLOG_LEVEL` {  
`eLOG_INFO`,  
`eLOG_DEBUG`,  
`eLOG_WARN`,  
`eLOG_FATAL` }
- enum `eTimeout` {  
`eTIMEOUT_2_S` = 2000,  
`eTIMEOUT_5_S` = 5000,  
`eTIMEOUT_8_S` = 8000,  
`eTIMEOUT_10_S` = 10000,  
`eTIMEOUT_20_S` = 20000,  
`eTIMEOUT_30_S` = 30000,  
`eTIMEOUT_60_S` = 60000,  
`eTIMEOUT_300_S` = 300000,  
`eTIMEOUT_DEFAULT` = `eTIMEOUT_8_S` }
- enum `eQMI_SVC` {  
`eCTL`,  
`eWDS`,  
`eDMS`,  
`eNAS` = 3,  
`eQOS`,  
`eSMS` = 5,  
`eUIM` = 0x0B,  
`eLOC` = 0x10,  
`eTMD` = 0x18,  
`eSWIOMA` = 240,  
`eSWILOC` = 246 }
- enum `msgtype` {  
`eREQ` = 0,  
`eRSP` = 2,  
`eIND` = 4 }

## Functions

- `uint16_t helper_get_xid (uint8_t *qmi_resp)`
- `const char * helper_get_resp_ctx (uint8_t svc, uint8_t *pbuf, uint32_t len, unpack\_qmi\_t *pCtx)`
- `unsigned unpack\_result\_code\_only (uint8_t *pMdmResp)`
- `int helper\_set\_log\_func (logger func)`
- `void libpack\_log (uint8_t lvl, const char *fmt,...)`
- `int helper\_set\_log\_lvl (uint8_t lvl)`
- `void fill\_sdu\_hdr (pack\_qmi\_t *pCtx, uint8_t *pReqBuf)`
- `void fill\_pack\_ctx (pack\_qmi\_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, uint8_t svc, int timeout)`
- `char * get\_version ()`
- `char * libpack\_GetVersion ()`

## Variables

- `logger glog`
- `uint8_t gloglvl`



## 9.2.1 Macro Definition Documentation

9.2.1.1 `#define DEAUULT_LOC_TIMEOUT_IN_SEC 2`

9.2.1.2 `#define MINREQBKLEN (2048)`

9.2.1.3 `#define MSGID_AND_LEN (4)`

9.2.1.4 `#define MSGID_DONT_CARE (0xffff)`

9.2.1.5 `#define SDK_VALIDATE_INPUT_PACK_PARAM( pCtx, pBuf, pLen )`

**Value:**

```
if ((pCtx == NULL) || (pBuf == NULL) || (pLen == NULL) ) \
{ \
    libpack_log(eLOG_DEBUG, "[ pack] %s parameter NULL\n", __func__); \
    return eQCWWAN_ERR_INVALID_ARG; \
}
```

9.2.1.6 `#define SDU_HDR_LEN (3)`

9.2.1.7 `#define UNUSEDPARAM( x ) (void)x`

## 9.2.2 Typedef Documentation

9.2.2.1 `typedef void(* logger)(uint8_t lvl, const char *buff)`

## 9.2.3 Enumeration Type Documentation

9.2.3.1 `enum eLOG_LEVEL`

log levels

Enumerator

***eLOG\_INFO***  
***eLOG\_DEBUG***  
***eLOG\_WARN***  
***eLOG\_FATAL***

9.2.3.2 `enum eQMI_SVC`

qmi service

Enumerator

***eCTL***  
***eWDS***  
***eDMS***  
***eNAS***  
***eQOS***  
***eSMS***  
***eUIM***

***eLOC***  
***eTMD***  
***eSWIOMA***  
***eSWILOC***

#### 9.2.3.3 enum eTimeout

eTimeout

Enumerator

***eTIMEOUT\_2\_S***  
***eTIMEOUT\_5\_S***  
***eTIMEOUT\_8\_S***  
***eTIMEOUT\_10\_S***  
***eTIMEOUT\_20\_S***  
***eTIMEOUT\_30\_S***  
***eTIMEOUT\_60\_S***  
***eTIMEOUT\_300\_S***  
***eTIMEOUT\_DEFAULT***

#### 9.2.3.4 enum msgtype

qmi message type

Enumerator

***eREQ***  
***eRSP***  
***eIND***

### 9.2.4 Function Documentation

9.2.4.1 void fill\_pack\_ctx ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, uint8\_t svc, int timeout )

9.2.4.2 void fill\_sdu\_hdr ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf )

9.2.4.3 char\* get\_version ( )

Returns

version string

9.2.4.4 const char\* helper\_get\_resp\_ctx ( uint8\_t svc, uint8\_t \* pbuf, uint32\_t len, unpack\_qmi\_t \* pCtx )

extract msgid/xid/type from modem reply

## Parameters

in	<i>svc</i>	qmi service
in	<i>pbuf</i>	qmi response/indication
in	<i>len</i>	response/indication length
out	<i>pCtx</i>	unpacked context

## Returns

qmi message string

9.2.4.5 `uint16_t helper_get_xid ( uint8_t * qmi_resp )`

9.2.4.6 `int helper_set_log_func ( logger func )`

set log function

9.2.4.7 `int helper_set_log_lvl ( uint8_t lvl )`

set log level

9.2.4.8 `char* libpack_GetVersion ( )`

## Returns

version string

9.2.4.9 `void libpack_log ( uint8_t lvl, const char * fmt, ... )`

9.2.4.10 `unsigned unpack_result_code_only ( uint8_t * pMdmResp )`

common handler for unpacking response with TLV type 0x02 only

## 9.2.5 Variable Documentation

9.2.5.1 `logger glog`

9.2.5.2 `uint8_t gloglvl`

## 9.3 dms.h File Reference

### Data Structures

- struct [unpack\\_dms\\_GetModelID\\_t](#)
- struct [unpack\\_dms\\_GetIMSI\\_t](#)
- struct [unpack\\_dms\\_GetFirmwareInfo\\_t](#)
- struct [unpack\\_dms\\_GetPower\\_t](#)
- struct [unpack\\_dms\\_GetSerialNumbers\\_t](#)
- struct [unpack\\_dms\\_GetHardwareRevision\\_t](#)
- struct [unpack\\_dms\\_SLQSGetBandCapability\\_t](#)
- struct [unpack\\_dms\\_GetDeviceCapabilities\\_t](#)
- struct [unpack\\_dms\\_GetFirmwareRevisions\\_t](#)

- struct [unpack\\_dms\\_GetFirmwareRevision\\_t](#)
- struct [unpack\\_dms\\_GetDeviceSerialNumbers\\_t](#)
- struct [unpack\\_dms\\_GetPRLVersion\\_t](#)
- struct [unpack\\_dms\\_GetNetworkTime\\_t](#)
- struct [unpack\\_dms\\_GetVoiceNumber\\_t](#)
- struct [unpack\\_dms\\_GetDeviceHardwareRev\\_t](#)
- struct [unpack\\_dms\\_GetFSN\\_t](#)
- struct [unpack\\_dms\\_GetDeviceCap\\_t](#)
- struct [pack\\_dms\\_SetPower\\_t](#)
- struct [unpack\\_dms\\_SetPower\\_t](#)
- struct [unpack\\_dms\\_GetBandCapability\\_t](#)
- struct [unpack\\_dms\\_GetUSBComp\\_t](#)
- struct [pack\\_dms\\_SetUSBComp\\_t](#)
- struct [unpack\\_dms\\_SetUSBComp\\_t](#)
- struct [pack\\_dms\\_SetCustFeature\\_t](#)
- struct [unpack\\_dms\\_SetCustFeature\\_t](#)
- struct [unpack\\_dms\\_GetCustFeature\\_t](#)
- struct [unpack\\_dms\\_SetFirmwarePreference\\_t](#)
- struct [unpack\\_dms\\_GetCrashAction\\_t](#)
- struct [pack\\_dms\\_SetCrashAction\\_t](#)
- struct [unpack\\_dms\\_SetCrashAction\\_t](#)
- struct [unpack\\_dms\\_GetDeviceMfr\\_t](#)
- struct [pack\\_dms\\_SetEventReport\\_t](#)
- struct [unpack\\_dms\\_SetEventReport\\_t](#)
- struct [dms\\_OperatingModeTlv](#)
- struct [dms\\_ActivationStatusTlv](#)
- struct [unpack\\_dms\\_SetEventReport\\_ind\\_t](#)
- struct [pack\\_dms\\_UIMGetICCID\\_t](#)
- struct [unpack\\_dms\\_UIMGetICCID\\_t](#)
- struct [pack\\_dms\\_SetCustFeaturesV2\\_t](#)
- struct [unpack\\_dms\\_SetCustFeaturesV2\\_t](#)
- struct [pack\\_dms\\_GetCustFeaturesV2\\_t](#)
- struct [DMSgetCustomInput](#)
- struct [DMScustSettingInfo](#)
- struct [DMScustSettingList](#)
- struct [DMSgetCustomFeatureV2](#)
- struct [unpack\\_dms\\_GetCustFeaturesV2\\_t](#)
- struct [unpack\\_dms\\_GetActivationState\\_t](#)
- struct [image\\_info\\_t](#)
- struct [unpack\\_dms\\_SLQSSwiGetFirmwareCurr\\_t](#)
- struct [pack\\_dms\\_SLQSSwiSetDyingGaspCfg\\_t](#)
- struct [unpack\\_dms\\_SLQSSwiSetDyingGaspCfg\\_t](#)
- struct [unpack\\_dms\\_SLQSSwiClearDyingGaspStatistics\\_t](#)
- struct [packgetDyingGaspStatistics](#)
- struct [unpack\\_dms\\_SLQSSwiGetDyingGaspStatistics\\_t](#)
- struct [packgetDyingGaspCfg](#)
- struct [unpack\\_dms\\_SLQSSwiGetDyingGaspCfg\\_t](#)
- struct [unpack\\_dms\\_SLQSDmsSwiGetResetInfo\\_t](#)
- struct [unpack\\_dms\\_SLQSDmsSwiGetResetInfo\\_Ind\\_t](#)
- struct [pack\\_dms\\_SLQSDmsSwiIndicationRegister\\_t](#)
- struct [unpack\\_dms\\_SLQSDmsSwiIndicationRegister\\_t](#)
- struct [unpack\\_dms\\_SLQSSwiGetFwUpdateStatus\\_t](#)

## Macros

- #define [DMS\\_UINT8\\_MAX\\_STRING\\_SZ](#) 255
- #define [DMS\\_MAX\\_CUST\\_ID\\_LEN](#) 64
- #define [DMS\\_MAX\\_CUST\\_VALUE\\_LEN](#) 8
- #define [DMS\\_IMGDETAILS\\_LEN](#) 16
- #define [DMS\\_MAX\\_FWUPDATE\\_LOG\\_STR\\_SZ](#) 255
- #define [DMS\\_MAX\\_FWUPDATE\\_REF\\_STR\\_SZ](#) 15
- #define [DMS\\_SLQSFWINFO\\_MODELID\\_SZ](#) 20
- #define [DMS\\_SLQSFWINFO\\_BOOTVERSION\\_SZ](#) 85
- #define [DMS\\_SLQSFWINFO\\_APPVERSION\\_SZ](#) 85
- #define [DMS\\_SLQSFWINFO\\_SKU\\_SZ](#) 15
- #define [DMS\\_SLQSFWINFO\\_PACKAGEID\\_SZ](#) 85
- #define [DMS\\_SLQSFWINFO\\_CARRIER\\_SZ](#) 20
- #define [DMS\\_SLQSFWINFO\\_PRIVERSION\\_SZ](#) 16
- #define [DMS\\_SLQSFWINFO\\_CUR\\_CARR\\_NAME](#) 17
- #define [DMS\\_SLQSFWINFO\\_CUR\\_CARR\\_REV](#) 13
- #define [MAX\\_BUILD\\_ID\\_LEN](#) 255
- #define [UNIQUE\\_ID\\_LEN](#) 16
- #define [SLQS\\_MAX\\_DYING\\_GASP\\_CFG\\_SMS\\_CONTENT\\_LENGTH](#) 160
- #define [SLQS\\_MAX\\_DYING\\_GASP\\_CFG\\_SMS\\_NUMBER\\_LENGTH](#) 20
- #define [DMS\\_PM\\_ONLINE](#) 0x00 /\* Online \*/
- #define [DMS\\_PM\\_LOW](#) 0x01 /\* Low Power \*/
- #define [DMS\\_PM\\_FACTORY](#) 0x02 /\* Factory Test Mode \*/
- #define [DMS\\_PM\\_OFFLINE](#) 0x03 /\* Offline \*/
- #define [DMS\\_PM\\_RESET](#) 0x04 /\* Reset \*/
- #define [DMS\\_PM\\_SHUT\\_DOWN](#) 0x05 /\* Shut Down \*/
- #define [DMS\\_PM\\_PERSISTENT\\_LOW](#) 0x06 /\* Persistent Low Power \*/
- #define [DMS\\_SET\\_REPORT\\_ENABLE](#) 1
- #define [DMS\\_SET\\_REPORT\\_DISABLE](#) 0
- #define [DMS\\_SWI\\_SET\\_IND\\_ENABLE](#) 1
- #define [DMS\\_SWI\\_SET\\_IND\\_DISABLE](#) 0

## Functions

- int [pack\\_dms\\_GetIMSI](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetIMSI](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetIMSI\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetModelID](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetModelID](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetModelID\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetFirmwareInfo](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetFirmwareInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetFirmwareInfo\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetPower](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetPower](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetPower\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetSerialNumbers](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetSerialNumbers](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetSerialNumbers\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetHardwareRevision](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetHardwareRevision](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetHardwareRevision\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSGetBandCapability](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_SLQSGetBandCapability](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSGetBandCapability\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetDeviceCapabilities](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)

- int [unpack\\_dms\\_GetDeviceCapabilities](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetDeviceCapabilities\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetFirmwareRevisions](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetFirmwareRevisions](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetFirmwareRevisions\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetFirmwareRevision](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetFirmwareRevision](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetFirmwareRevision\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetDeviceSerialNumbers](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetDeviceSerialNumbers](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetDeviceSerialNumbers\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetPRLVersion](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetPRLVersion](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetPRLVersion\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetNetworkTime](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetNetworkTime](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetNetworkTime\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetVoiceNumber](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetVoiceNumber](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetVoiceNumber\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetDeviceHardwareRev](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetDeviceHardwareRev](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetDeviceHardwareRev\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetFSN](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetFSN](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetFSN\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetDeviceCap](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetDeviceCap](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetDeviceCap\\_t](#) \*pOutput)
- int [pack\\_dms\\_SetPower](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_SetPower\\_t](#) \*reqArg)
- int [unpack\\_dms\\_SetPower](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SetPower\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetBandCapability](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetBandCapability](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetBandCapability\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetUSBComp](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetUSBComp](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetUSBComp\\_t](#) \*pOutput)
- int [pack\\_dms\\_SetUSBComp](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_SetUSBComp\\_t](#) \*reqArg)
- int [unpack\\_dms\\_SetUSBComp](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SetUSBComp\\_t](#) \*pOutput)
- int [pack\\_dms\\_SetCustFeature](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_SetCustFeature\\_t](#) \*reqArg)
- int [unpack\\_dms\\_SetCustFeature](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SetCustFeature\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetCustFeature](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetCustFeature](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetCustFeature\\_t](#) \*pOutput)
- int [pack\\_dms\\_SetFirmwarePreference](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_SetFirmwarePreference](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SetFirmwarePreference\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetCrashAction](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_dms\\_GetCrashAction](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetCrashAction\\_t](#) \*pOutput)
- int [pack\\_dms\\_SetCrashAction](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_SetCrashAction\\_t](#) reqArg)
- int [unpack\\_dms\\_SetCrashAction](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SetCrashAction\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetDeviceMfr](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)

- int [unpack\\_dms\\_GetDeviceMfr](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetDeviceMfr\\_t](#) \*pOutput)
- int [pack\\_dms\\_SetEventReport](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_SetEventReport\\_t](#) \*reqArg)
- int [unpack\\_dms\\_SetEventReport](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SetEventReport\\_t](#) \*pOutput)
- int [unpack\\_dms\\_SetEventReport\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SetEventReport\\_ind\\_t](#) \*pOutput)
- int [pack\\_dms\\_UIMGetICCID](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_UIMGetICCID\\_t](#) \*reqArg)
- int [unpack\\_dms\\_UIMGetICCID](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_UIMGetICCID\\_t](#) \*pOutput)
- int [pack\\_dms\\_SetCustFeaturesV2](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_SetCustFeaturesV2\\_t](#) \*reqArg)
- int [unpack\\_dms\\_SetCustFeaturesV2](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SetCustFeaturesV2\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetCustFeaturesV2](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_GetCustFeaturesV2\\_t](#) \*reqArg)
- int [unpack\\_dms\\_GetCustFeaturesV2](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetCustFeaturesV2\\_t](#) \*pOutput)
- int [pack\\_dms\\_GetActivationState](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_dms\\_GetActivationState](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_GetActivationState\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSSwiGetFirmwareCurr](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_dms\\_SLQSSwiGetFirmwareCurr](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSSwiGetFirmwareCurr\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSSwiSetDyingGaspCfg](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_SLQSSwiSetDyingGaspCfg\\_t](#) \*reqArg)
- int [unpack\\_dms\\_SLQSSwiSetDyingGaspCfg](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSSwiSetDyingGaspCfg\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSSwiClearDyingGaspStatistics](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_dms\\_SLQSSwiClearDyingGaspStatistics](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSSwiClearDyingGaspStatistics\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSSwiGetDyingGaspStatistics](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_dms\\_SLQSSwiGetDyingGaspStatistics](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSSwiGetDyingGaspStatistics\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSSwiGetDyingGaspCfg](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_dms\\_SLQSSwiGetDyingGaspCfg](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSSwiGetDyingGaspCfg\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSDmsSwiGetResetInfo](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_dms\\_SLQSDmsSwiGetResetInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSDmsSwiGetResetInfo\\_t](#) \*pOutput)
- int [unpack\\_dms\\_SLQSDmsSwiGetResetInfo\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSDmsSwiGetResetInfo\\_ind\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSDmsSwiIndicationRegister](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_dms\\_SLQSDmsSwiIndicationRegister\\_t](#) \*reqArg)
- int [unpack\\_dms\\_SLQSDmsSwiIndicationRegister](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSDmsSwiIndicationRegister\\_t](#) \*pOutput)
- int [pack\\_dms\\_SLQSSwiGetFwUpdateStatus](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_dms\\_SLQSSwiGetFwUpdateStatus](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_dms\\_SLQSSwiGetFwUpdateStatus\\_t](#) \*pOutput)

### 9.3.1 Macro Definition Documentation

9.3.1.1 `#define DMS_IMGDETAILS_LEN 16`

9.3.1.2 `#define DMS_MAX_CUST_ID_LEN 64`

```
9.3.1.3  #define DMS_MAX_CUST_VALUE_LEN 8

9.3.1.4  #define DMS_MAX_FWUPDATE_LOG_STR_SZ 255

9.3.1.5  #define DMS_MAX_FWUPDATE_REF_STR_SZ 15

9.3.1.6  #define DMS_PM_FACTORY 0x02 /* Factory Test Mode */

9.3.1.7  #define DMS_PM_LOW 0x01 /* Low Power */

9.3.1.8  #define DMS_PM_OFFLINE 0x03 /* Offline */

9.3.1.9  #define DMS_PM_ONLINE 0x00 /* Online */

9.3.1.10 #define DMS_PM_PERSISTENT_LOW 0x06 /* Persistent Low Power */

9.3.1.11 #define DMS_PM_RESET 0x04 /* Reset */

9.3.1.12 #define DMS_PM_SHUT_DOWN 0x05 /* Shut Down */

9.3.1.13 #define DMS_SET_REPORT_DISABLE 0

9.3.1.14 #define DMS_SET_REPORT_ENABLE 1

9.3.1.15 #define DMS_SLQSFWINFO_APPVERSION_SZ 85

9.3.1.16 #define DMS_SLQSFWINFO_BOOTVERSION_SZ 85

9.3.1.17 #define DMS_SLQSFWINFO_CARRIER_SZ 20

9.3.1.18 #define DMS_SLQSFWINFO_CUR_CARR_NAME 17

9.3.1.19 #define DMS_SLQSFWINFO_CUR_CARR_REV 13

9.3.1.20 #define DMS_SLQSFWINFO_MODELID_SZ 20

9.3.1.21 #define DMS_SLQSFWINFO_PACKAGEID_SZ 85

9.3.1.22 #define DMS_SLQSFWINFO_PRIVERSION_SZ 16

9.3.1.23 #define DMS_SLQSFWINFO_SKU_SZ 15

9.3.1.24 #define DMS_SWI_SET_IND_DISABLE 0

9.3.1.25 #define DMS_SWI_SET_IND_ENABLE 1

9.3.1.26 #define DMS_UINT8_MAX_STRING_SZ 255

9.3.1.27 #define MAX_BUILD_ID_LEN 255

9.3.1.28 #define SLQS_MAX_DYING_GASP_CFG_SMS_CONTENT_LENGTH 160

9.3.1.29 #define SLQS_MAX_DYING_GASP_CFG_SMS_NUMBER_LENGTH 20

9.3.1.30 #define UNIQUE_ID_LEN 16
```



### 9.3.2 Function Documentation

#### 9.3.2.1 int pack\_dms\_GetActivationState ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )

Get Activation State pack

Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.3.2.2 int pack\_dms\_GetBandCapability ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, void \* reqArg )

Get Band Capability pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.3.2.3 int pack\_dms\_GetCrashAction ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, void \* reqArg )

Get Crash Action pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.4 `int pack_dms_GetCustFeature ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

Get Custom Feature pack. This API is deprecated for EM74xx/MC74xx, please use [pack\\_dms\\_GetCustFeatures-V2\(\)](#) instead for EM74xx/MC74xx.

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.5 int pack\_dms\_GetCustFeaturesV2 ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, pack\_dms\_GetCustFeaturesV2\_t \* reqArg )

9.3.2.6 int pack\_dms\_GetDeviceCap ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, void \* reqArg )

Get Device Capabilities pack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.7 int pack\_dms\_GetDeviceCapabilities ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, void \* reqArg )

get device capability pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.8 int pack\_dms\_GetDeviceHardwareRev ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, void \* reqArg )

Get Hardware Revision pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.9** int pack\_dms\_GetDeviceMfr ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

Get Manufacture pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.10** int pack\_dms\_GetDeviceSerialNumbers ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

get Device Serial Number pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.11** int pack\_dms\_GetFirmwareInfo ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

get firmware info pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.12** `int pack_dms_GetFirmwareRevision ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

get Firmware Revision pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.13** `int pack_dms_GetFirmwareRevisions ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

get Firmware Revisions pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.14** `int pack_dms_GetFSN ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

Get FSN pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.15 `int pack_dms_GetHardwareRevision ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

get hardware revision pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.16 `int pack_dms_GetIMSI ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

get IMSI pack. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx-xx and all EM74xx firmware versions. Please use [pack\\_uim\\_ReadTransparent\(\)](#)(EF ID: 3F00 7F20 6F07 for 2G card and 3F00 7FFF 6F07 for 3G card) instead for new firmware versions and new modules.

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.17 `int pack_dms_GetModelID ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

get model id pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.18** int pack\_dms\_GetNetworkTime ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

Get Network Time pack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.19** int pack\_dms\_GetPower ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

get power pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.20** int pack\_dms\_GetPRLVersion ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

Get PRL Versions pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.21** int pack\_dms\_GetSerialNumbers ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

get serial numbers pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.22** int pack\_dms\_GetUSBComp ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

Get USB Comp pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.23** int pack\_dms\_GetVoiceNumber ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, void \* *reqArg* )

Get Voice Number pack



## Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.24 int pack\_dms\_SetCrashAction ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, pack\_dms\_SetCrashAction\_t reqArg )

Set Crash Action pack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

Set Crash Action unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.25 int pack\_dms\_SetCustFeature ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, pack\_dms\_SetCustFeature\_t \* reqArg )

Set Custom Feature pack. This API is deprecated for EM74xx/MC74xx, please use [pack\\_dms\\_SetCustFeatures-V2\(\)](#) instead for EM74xx/MC74xx.

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.26 `int pack_dms_SetCustFeaturesV2 ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_dms_SetCustFeaturesV2_t * reqArg )`

Set Cust Features pack.

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.27 `int pack_dms_SetEventReport ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_dms_SetEventReport_t * reqArg )`

Set Event Report pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.28 `int pack_dms_SetFirmwarePreference ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

Set Firmware Preference pack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.29 `int pack_dms_SetPower ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_dms_SetPower_t * reqArg )`

Set Power pack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.30 `int pack_dms_SetUSBComp ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_dms_SetUSBComp_t * reqArg )`

Set USB Comp pack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.31 `int pack_dms_SLQSDmsSwiGetResetInfo ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

To get reset info pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.32** `int pack_dms_SLQSDmsSwiIndicationRegister ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_dms_SLQSDmsSwiIndicationRegister_t * reqArg )`

Set the registration state for different indication pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**Note**

support EM/MC74xx onwards

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.33** `int pack_dms_SLQSGetBandCapability ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

get band capability pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.34** `int pack_dms_SLQSSwiClearDyingGaspStatistics ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

Clear Dying GASP Statistics pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.35** int pack\_dms\_SLQSSwiGetDyingGaspCfg ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

Get Dying GASP Config pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.36** int pack\_dms\_SLQSSwiGetDyingGaspStatistics ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

Get Dying GASP Statistics pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.37** int pack\_dms\_SLQSSwiGetFirmwareCurr ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

get currently active image pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.38** int pack\_dms\_SLQSSwiGetFwUpdateStatus ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

To get Firmware Update status pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.39** int pack\_dms\_SLQSSwiSetDyingGaspCfg ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_dms\_SLQSSwiSetDyingGaspCfg\_t \* *reqArg* )

Set Dying GASP Config pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.40** int pack\_dms\_UIMGetICCID ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_dms\_UIMGetICCID\_t \* *reqArg* )

Packs the UIMGetICCID response message to a user-provided response structure. This API is deprecated on MC73xx/EM73xx modules. Since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use [pack\\_uim\\_ReadTransparent\(\)](#)(EF ID: 3F00 2FE2) instead for new firmware versions and new modules.

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.41 int unpack\_dms\_GetActivationState ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetActivationState\_t \* *pOutput* )

Get Activation State unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.42 int unpack\_dms\_GetBandCapability ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetBandCapability\_t \* *pOutput* )

Get Band Capabilities unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.43 int unpack\_dms\_GetCrashAction ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetCrashAction\_t \* *pOutput* )

Get Crash Action unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.44** `int unpack_dms_GetCustFeature ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetCustFeature_t * pOutput )`

Get Custom Feature unpack. This API is deprecated for EM74xx/MC74xx, please use [unpack\\_dms\\_GetCustFeaturesV2\(\)](#) instead for EM74xx/MC74xx.

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.45** `int unpack_dms_GetCustFeaturesV2 ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetCustFeaturesV2_t * pOutput )`

**9.3.2.46** `int unpack_dms_GetDeviceCap ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetDeviceCap_t * pOutput )`

Get Device Capabilities unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.47** `int unpack_dms_GetDeviceCapabilities ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetDeviceCapabilities_t * pOutput )`

get device capability unpack



## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.48 int unpack\_dms\_GetDeviceHardwareRev ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetDeviceHardwareRev\_t \* *pOutput* )

Get Hardware Revision unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.49 int unpack\_dms\_GetDeviceMfr ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetDeviceMfr\_t \* *pOutput* )

Get Manufacture unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.50 int unpack\_dms\_GetDeviceSerialNumbers ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetDeviceSerialNumbers\_t \* *pOutput* )

get Device Serial Number unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.51** `int unpack_dms_GetFirmwareInfo ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetFirmwareInfo_t * pOutput )`

get firmware info unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.52** `int unpack_dms_GetFirmwareRevision ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetFirmwareRevision_t * pOutput )`

get Firmware Revision unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.53** `int unpack_dms_GetFirmwareRevisions ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetFirmwareRevisions_t * pOutput )`

get Firmware Revisions unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.54** `int unpack_dms_GetFSN ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetFSN_t * pOutput )`

Get FSN unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.55** `int unpack_dms_GetHardwareRevision ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetHardwareRevision_t * pOutput )`

get hardware revision unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.56** `int unpack_dms_GetIMSI ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetIMSI_t * pOutput )`

get IMSI unpack. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx-xx\_xx and all EM74xx firmware versions. Please use [unpack\\_uim\\_ReadTransparent\(\)](#)(EF ID: 3F00 7F20 6F07 for 2G card and 3F00 7FFF 6F07 for 3G card) instead for new firmware versions and new modules.

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.57 int unpack\_dms\_GetModelID ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetModelID\_t \* *pOutput* )

get model id unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.58 int unpack\_dms\_GetNetworkTime ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetNetworkTime\_t \* *pOutput* )

Get Network Time unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.59 int unpack\_dms\_GetPower ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetPower\_t \* *pOutput* )

get power unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.60 int unpack\_dms\_GetPRLVersion ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetPRLVersion\_t \* *pOutput* )

Get PRL Versions unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.61 int unpack\_dms\_GetSerialNumbers ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetSerialNumbers\_t \* *pOutput* )

get serial numbers unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.62 int unpack\_dms\_GetUSBComp ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_GetUSBComp\_t \* *pOutput* )

Get USB Comp unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.63 `int unpack_dms_GetVoiceNumber ( uint8_t * pResp, uint16_t respLen, unpack_dms_GetVoiceNumber_t * pOutput )`

Get Voice Number unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.64 `int unpack_dms_SetCrashAction ( uint8_t * pResp, uint16_t respLen, unpack_dms_SetCrashAction_t * pOutput )`

Set Crash Action unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response. Not used

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.65 `int unpack_dms_SetCustFeature ( uint8_t * pResp, uint16_t respLen, unpack_dms_SetCustFeature_t * pOutput )`

Set Custom Feature unpack. This API is deprecated for EM74xx/MC74xx, please use [unpack\\_dms\\_SetCustFeaturesV2\(\)](#) instead for EM74xx/MC74xx.

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.66** `int unpack_dms_SetCustFeaturesV2 ( uint8_t * pResp, uint16_t respLen, unpack_dms_SetCustFeaturesV2_t * pOutput )`

Set Cust features unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.67** `int unpack_dms_SetEventReport ( uint8_t * pResp, uint16_t respLen, unpack_dms_SetEventReport_t * pOutput )`

Set Event Report unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.68** `int unpack_dms_SetEventReport_ind ( uint8_t * pResp, uint16_t respLen, unpack_dms_SetEventReport_ind_t * pOutput )`

Event Report Indication unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.69** int unpack\_dms\_SetFirmwarePreference ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_SetFirmwarePreference\_t \* *pOutput* )

Set Firmware Preference unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.70** int unpack\_dms\_SetPower ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_SetPower\_t \* *pOutput* )

Set Power unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.71** int unpack\_dms\_SetUSBComp ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_SetUSBComp\_t \* *pOutput* )

Set USB Comp unpack



## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.72 `int unpack_dms_SLQSDmsSwiGetResetInfo ( uint8_t * pResp, uint16_t respLen,  
unpack_dms_SLQSDmsSwiGetResetInfo_t * pOutput )`

To get reset info unpack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.73 `int unpack_dms_SLQSDmsSwiGetResetInfo_Ind ( uint8_t * pResp, uint16_t respLen,  
unpack_dms_SLQSDmsSwiGetResetInfo_Ind_t * pOutput )`

DMS reset info Indication unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

support EM/MC74xx onwards

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.74 `int unpack_dms_SLQSDmsSwiIndicationRegister ( uint8_t * pResp, uint16_t respLen,  
unpack_dms_SLQSDmsSwiIndicationRegister_t * pOutput )`

Set the registration state for different indication unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**Note**

support EM/MC74xx onwards

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.75 int unpack\_dms\_SLQSGetBandCapability ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_SLQSGetBandCapability\_t \* *pOutput* )

get band capability unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.76 int unpack\_dms\_SLQSSwiClearDyingGaspStatistics ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_SLQSSwiClearDyingGaspStatistics\_t \* *pOutput* )

Clear Dying GASP Statistics unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.3.2.77 int unpack\_dms\_SLQSSwiGetDyingGaspCfg ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_SLQSSwiGetDyingGaspCfg\_t \* *pOutput* )

Get Dying GASP Config unpack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.78** `int unpack_dms_SLQSSwiGetDyingGaspStatistics ( uint8_t * pResp, uint16_t respLen, unpack_dms_SLQSSwiGetDyingGaspStatistics_t * pOutput )`

Get Dying GASP Statistics unpack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.79** `int unpack_dms_SLQSSwiGetFirmwareCurr ( uint8_t * pResp, uint16_t respLen, unpack_dms_SLQSSwiGetFirmwareCurr_t * pOutput )`

get currently active image unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.80** `int unpack_dms_SLQSSwiGetFwUpdateStatus ( uint8_t * pResp, uint16_t respLen, unpack_dms_SLQSSwiGetFwUpdateStatus_t * pOutput )`

To get Firmware Update status unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.81** int unpack\_dms\_SLQSSwiSetDyingGaspCfg ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_dms\_SLQSSwiSetDyingGaspCfg\_t \* *pOutput* )

Set Dying GASP Config unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.3.2.82** int unpack\_dms\_UIMGetICCID ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_dms\_UIMGetICCID\_t \* *pOutput* )

Unpacks the UIMGetICCID response message to a user-provided response structure.

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.4 fms.h File Reference

**Data Structures**

- struct [CarrierImage\\_t](#)

- struct [pack\\_fms\\_GetImagesPreference\\_t](#)
- struct [FMSImageElement](#)
- struct [FMSPrefImageList](#)
- struct [unpack\\_fms\\_GetImagesPreference\\_t](#)
- struct [pack\\_fms\\_GetStoredImages\\_t](#)
- struct [FMSImageElement](#)
- struct [FMSImageIDEntries](#)
- struct [FMSImageList](#)
- struct [unpack\\_fms\\_GetStoredImages\\_t](#)
- struct [pack\\_fms\\_SetImagesPreference\\_t](#)
- struct [unpack\\_fms\\_SetImagesPreference\\_t](#)

## Macros

- `#define FMS_GOBI_MBN_IMG_ID_STR_LEN 16`
- `#define FMS_GOBI_MBN_BUILD_ID_STR_LEN 100`
- `#define FMS_GOBI_LISTENTRIES_MAX 2`
- `#define FMS_MAX_IMAGE_PREFERENCE_IMAGE_SIZE 255`
- `#define FMS_MAX_IMAGE_ID_ELEMENT 50`
- `#define FMS_IMAGE_ID_MAX_ENTRIES 2`
- `#define FMS_FW_PRI_BUILD_MATCH_LEN 11`
- `#define FMS_IMAGE_ID_IMG_ID_LEN 16`
- `#define FMS_IMAGE_ID_BUILD_ID_LEN 32`
- `#define FMS_IMAGE_ID_PRI_IMGTYPE 0x01`

## Functions

- `int pack_fms_GetImagesPreference (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_fms_GetImagesPreference_t *reqArg)`
- `int unpack_fms_GetImagesPreference (uint8_t *pResp, uint16_t respLen, unpack_fms_GetImagesPreference_t *pOutput)`
- `int pack_fms_GetStoredImages (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_fms_GetStoredImages_t *reqArg)`
- `int unpack_fms_GetStoredImages (uint8_t *pResp, uint16_t respLen, unpack_fms_GetStoredImages_t *pOutput)`
- `int pack_fms_SetImagesPreference (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_fms_SetImagesPreference_t *reqArg)`
- `int unpack_fms_SetImagesPreference (uint8_t *pResp, uint16_t respLen, unpack_fms_SetImagesPreference_t *pOutput)`
- `uint32_t GetValidFwPriCombinations (FMSImageList *pStoredImageList, uint32_t *pValidCombinationSize, CarrierImage_t *pValidCombinations)`

### 9.4.1 Macro Definition Documentation

9.4.1.1 `#define FMS_FW_PRI_BUILD_MATCH_LEN 11`

9.4.1.2 `#define FMS_GOBI_LISTENTRIES_MAX 2`

9.4.1.3 `#define FMS_GOBI_MBN_BUILD_ID_STR_LEN 100`

9.4.1.4 `#define FMS_GOBI_MBN_IMG_ID_STR_LEN 16`

9.4.1.5 `#define FMS_IMAGE_ID_BUILD_ID_LEN 32`

9.4.1.6 `#define FMS_IMAGE_ID_IMG_ID_LEN 16`

9.4.1.7 `#define FMS_IMAGE_ID_MAX_ENTRIES 2`

9.4.1.8 `#define FMS_IMAGE_ID_PRI_IMGTYPE 0x01`

9.4.1.9 `#define FMS_MAX_IMAGE_ID_ELEMENT 50`

9.4.1.10 `#define FMS_MAX_IMAGE_PREFERENCE_IMAGE_SIZE 255`

## 9.4.2 Function Documentation

9.4.2.1 `uint32_t GetValidFwPriCombinations ( FMSImageList * pStoredImageList, uint32_t * pValidCombinationSize, CarrierImage_t * pValidCombinations )`

This API distills valid Firmware/PRI combinations from GetStoredImages result

### Parameters

in	<i>pStoredImageList</i>	<ul style="list-style-type: none"> <li>image list returned from GetStoredImages</li> <li>See <a href="#">FMSImageList</a></li> </ul>
in, out	<i>pValidCombinationSize</i>	<ul style="list-style-type: none"> <li>number of combination passed in and returned</li> </ul>
out	<i>pValidCombinations</i>	<ul style="list-style-type: none"> <li>valid combinations returned</li> <li>See <a href="#">CarrierImage_t</a></li> </ul>

### Returns

- eQCWWAN\_ERR\_INVALID\_ARG - Invalid parameters
- eQCWWAN\_ERR\_BUFFER\_SZ - No enough element to store combinatons returned

### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.4.2.2 `int pack_fms_GetImagesPreference ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_fms_GetImagesPreference_t * reqArg )`

Get Images Preference pack

### Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

in	<i>reqArg</i>	request parameter
----	---------------	-------------------

9.4.2.3 int pack\_fms\_GetStoredImages ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, pack\_fms\_GetStoredImages\_t \* reqArg )

Get Images Preference pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

9.4.2.4 int pack\_fms\_SetImagesPreference ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, pack\_fms\_SetImagesPreference\_t \* reqArg )

Set Images Preference pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

9.4.2.5 int unpack\_fms\_GetImagesPreference ( uint8\_t \* pResp, uint16\_t respLen, unpack\_fms\_GetImagesPreference\_t \* pOutput )

Get Images Preference unpack

Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

9.4.2.6 int unpack\_fms\_GetStoredImages ( uint8\_t \* pResp, uint16\_t respLen, unpack\_fms\_GetStoredImages\_t \* pOutput )

Get Images Preference unpack

Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

9.4.2.7 int unpack\_fms\_SetImagesPreference ( uint8\_t \* pResp, uint16\_t respLen, unpack\_fms\_SetImagesPreference\_t \* pOutput )

Set Images Preference unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## 9.5 loc.h File Reference

### Data Structures

- struct [loc\\_LocApplicationInfo](#)
- struct [loc\\_SV](#)
- struct [loc\\_SVInfo](#)
- struct [loc\\_GnssData](#)
- struct [loc\\_CellDb](#)
- struct [loc\\_ClkInfo](#)
- struct [loc\\_BdsSV](#)
- struct [loc\\_BdsSVInfo](#)
- struct [pack\\_loc\\_EventRegister\\_t](#)
- struct [unpack\\_loc\\_EventRegister\\_t](#)
- struct [pack\\_loc\\_SetExtPowerState\\_t](#)
- struct [unpack\\_loc\\_SetExtPowerState\\_t](#)
- struct [pack\\_loc\\_Start\\_t](#)
- struct [unpack\\_loc\\_Start\\_t](#)
- struct [pack\\_loc\\_Stop\\_t](#)
- struct [unpack\\_loc\\_Stop\\_t](#)
- struct [pack\\_loc\\_SetOperationMode\\_t](#)
- struct [unpack\\_loc\\_SetOperationMode\\_t](#)
- struct [pack\\_loc\\_Delete\\_Assist\\_Data\\_t](#)
- struct [unpack\\_loc\\_Delete\\_Assist\\_Data\\_t](#)
- struct [loc\\_precisionDilution](#)
- struct [loc\\_sensorDataUsage](#)
- struct [loc\\_svUsedforFix](#)
- struct [loc\\_gpsTime](#)
- struct [unpack\\_loc\\_PositionRpt\\_Ind\\_t](#)
- struct [unpack\\_loc\\_EngineState\\_Ind\\_t](#)
- struct [unpack\\_loc\\_SetExtPowerConfig\\_Ind\\_t](#)

### Macros

- [#define LOC\\_UINT8\\_MAX\\_STRING\\_SZ 255](#)
- [#define LOCEVENTMASKPOSITIONREPORT 0x00000001](#)
- [#define LOCEVENTMASKGNSSSVINFO 0x00000002](#)
- [#define LOCEVENTMASKNMEA 0x00000004](#)
- [#define LOCEVENTMASKNINOTIFYVERIFYREQ 0x00000008](#)
- [#define LOCEVENTMASKINJECTTIMERREQ 0x00000010](#)
- [#define LOCEVENTMASKINJECTPREDICTEDORBITSREQ 0x00000020](#)
- [#define LOCEVENTMASKINJECTPOSITIONREQ 0x00000040](#)
- [#define LOCEVENTMASKENGINESTATE 0x00000080](#)
- [#define LOCEVENTMASKFIXSESSIONSTATE 0x00000100](#)
- [#define LOCEVENTMASKWIFIREQ 0x00000200](#)
- [#define LOCEVENTMASKSENSORSTREAMINGREADYSTATUS 0x00000400](#)
- [#define LOCEVENTMASKTIMESYNCREQ 0x00000800](#)



- `#define LOCEVENTMASKSETSPISTREAMINGREPORT 0x00001000`
- `#define LOCEVENTMASKLOCATIONSERVERCONNECTIONREQ 0x00002000`
- `#define LOCEVENTMASKNIGEOFENCENOTIFICATION 0x00004000`
- `#define LOCEVENTMASKGEOFENCEGENALERT 0x00008000`
- `#define LOCEVENTMASKGEOFENCEBREACHNOTIFICATION 0x00010000`
- `#define LOCEVENTMASKPEDOMETERCONTROL 0x00020000`
- `#define LOCEVENTMASKMOTIONDATACONTROL 0x00040000`
- `#define LOCEVENTMASKBATCHFULLNOTIFICATION 0x00080000`
- `#define LOCEVENTMASKLIVEBATCHEDPOSITIONREPORT 0x00100000`
- `#define LOCEVENTMASKINJECTWIFIAPDATAREQ 0x00200000`
- `#define LOCEVENTMASKGEOFENCEBATCHBREACHNOTIFICATION 0x00400000`
- `#define LOCEVENTMASKVEHICLEDATAREADYSTATUS 0x00800000`
- `#define LOCEVENTMASKGNSSMEASUREMENTREPORT 0x01000000`
- `#define LOCEVENTMASKINVALIDVALUE 0xFFFFFFFF`

## Enumerations

- `enum {`  
`eQMI_LOC_SESS_STATUS_SUCCESS =0,`  
`eQMI_LOC_SESS_STATUS_IN_PROGRESS =1,`  
`eQMI_LOC_SESS_STATUS_FAILURE =2,`  
`eQMI_LOC_SESS_STATUS_TIMEOUT =3 }`

## Functions

- `int pack_loc_EventRegister (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_loc_EventRegister_t *reqArg)`
- `int unpack_loc_EventRegister (uint8_t *pResp, uint16_t respLen, unpack_loc_EventRegister_t *pOutput)`
- `int pack_loc_SetExtPowerState (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_loc_SetExtPowerState_t *reqArg)`
- `int unpack_loc_SetExtPowerState (uint8_t *pResp, uint16_t respLen, unpack_loc_SetExtPowerState_t *pOutput)`
- `int pack_loc_Start (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_loc_Start_t *reqArg)`
- `int unpack_loc_Start (uint8_t *pResp, uint16_t respLen, unpack_loc_Start_t *pOutput)`
- `int pack_loc_Stop (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_loc_Stop_t *reqArg)`
- `int unpack_loc_Stop (uint8_t *pResp, uint16_t respLen, unpack_loc_Stop_t *pOutput)`
- `int pack_loc_SetOperationMode (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_loc_SetOperationMode_t *reqArg)`
- `int unpack_loc_SetOperationMode (uint8_t *pResp, uint16_t respLen, unpack_loc_SetOperationMode_t *pOutput)`
- `int pack_loc_DeleteAssistData (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack_loc_Delete_Assist_Data_t *reqArg)`
- `int unpack_loc_DeleteAssistData (uint8_t *pResp, uint16_t respLen, unpack_loc_Delete_Assist_Data_t *pOutput)`
- `int unpack_loc_PositionRpt_Ind (uint8_t *pResp, uint16_t respLen, unpack_loc_PositionRpt_Ind_t *pOutput)`
- `int unpack_loc_EngineState_Ind (uint8_t *pResp, uint16_t respLen, unpack_loc_EngineState_Ind_t *pOutput)`
- `int unpack_loc_SetExtPowerConfig_Ind (uint8_t *pResp, uint16_t respLen, unpack_loc_SetExtPowerConfig_Ind_t *pOutput)`

## 9.5.1 Macro Definition Documentation

### 9.5.1.1 `#define LOC_UINT8_MAX_STRING_SZ 255`

### 9.5.1.2 `#define LOCEVENTMASKBATCHFULLNOTIFICATION 0x00080000`

The control point must enable this mask to receive notification when a batch is full. The location engine sends this event to notify of Batch Full for ongoing batching session.

### 9.5.1.3 `#define LOCEVENTMASKENGINESTATE 0x00000080`

The control point must enable this mask to receive engine state report event indications.

### 9.5.1.4 `#define LOCEVENTMASKFIXSESSIONSTATE 0x00000100`

The control point must enable this mask to receive fix session status report event indications.

### 9.5.1.5 `#define LOCEVENTMASKGEOFENCEBATCHBREACHNOTIFICATION 0x00400000`

The control point must enable this mask to receive notifications when a Geofence is breached. These events are generated when a UE enters or leaves the perimeter of a Geofence. This breach notification is for multiple Geofences. Breaches from multiple Geofences are all batched and sent in the same notification.

### 9.5.1.6 `#define LOCEVENTMASKGEOFENCEBREACHNOTIFICATION 0x00010000`

The control point must enable this mask to receive notifications when a Geofence is breached. These events are generated when a UE enters or leaves the perimeter of a Geofence. This breach report is for a single Geofence.

### 9.5.1.7 `#define LOCEVENTMASKGEOFENCEGENALERT 0x00008000`

The control point must enable this mask to receive Geofence alerts. These alerts are generated to inform the client of the changes that may affect a Geofence, for example, if GPS is turned off or if the network is unavailable.

### 9.5.1.8 `#define LOCEVENTMASKGNSSMEASUREMENTREPORT 0x01000000`

The control point must enable this mask to receive system clock and satellite measurement report events (system clock, [SV](#) time, Doppler, etc.). Reports are generated only for the GNSS satellite constellations that are enabled using `QMI_LOC_SET_GNSS_CONSTELL_REPORT_CONFIG`(Not yet supported).

### 9.5.1.9 `#define LOCEVENTMASKGNSSSVINFO 0x00000002`

The control point must enable this mask to receive satellite report event indications. These reports are sent at a 1 Hz rate.

### 9.5.1.10 `#define LOCEVENTMASKINJECTPOSITIONREQ 0x00000040`

The control point must enable this mask to receive position injection request event indications.

### 9.5.1.11 `#define LOCEVENTMASKINJECTPREDICTEDORBITSREQ 0x00000020`

The control point must enable this mask to receive predicted orbits request event indications.

**9.5.1.12 #define LOCEVENTMASKINJECTTIMERREQ 0x00000010**

The control point must enable this mask to receive time injection request event indications.

**9.5.1.13 #define LOCEVENTMASKINJECTWIFIAPDATAREQ 0x00200000**

The control point must enable this mask to receive Wi-Fi Access Point (AP) data inject request event indications.

**9.5.1.14 #define LOCEVENTMASKINVALIDVALUE 0xFFFFFFFF**

Invalid Event Mask

**9.5.1.15 #define LOCEVENTMASKLIVEBATCHEDPOSITIONREPORT 0x00100000**

The control point must enable this mask to receive position report indications along with an ongoing batching session. The location engine sends this event to notify the batched position report while a batching session is ongoing.

**9.5.1.16 #define LOCEVENTMASKLOCATIONSERVERCONNECTIONREQ 0x00002000**

The control point must enable this mask to receive location server requests. These requests are generated when the service wishes to establish a connection with a location server.

**9.5.1.17 #define LOCEVENTMASKMOTIONDATACONTROL 0x00040000**

The control point must enable this mask to register for motion data control requests from the location engine. The location engine sends this event to control the injection of motion data.

**9.5.1.18 #define LOCEVENTMASKNIGEOFENCENOTIFICATION 0x00004000**

The control point must enable this mask to receive notifications related to network-initiated Geofences. These events notify the client when a network-initiated Geofence is added, deleted, or edited.

**9.5.1.19 #define LOCEVENTMASKNINOTIFYVERIFYREQ 0x00000008**

The control point must enable this mask to receive NI Notify/Verify request event indications.

**9.5.1.20 #define LOCEVENTMASKNMEA 0x00000004**

The control point must enable this mask to receive NMEA reports for position and satellites in view. The report is at a 1 Hz rate.

**9.5.1.21 #define LOCEVENTMASKPEDOMETERCONTROL 0x00020000**

The control point must enable this mask to register for pedometer control requests from the location engine. The location engine sends this event to control the injection of pedometer reports.

**9.5.1.22 #define LOCEVENTMASKPOSITIONREPORT 0x00000001**

The control point must enable this mask to receive position report event indications.

#### 9.5.1.23 `#define LOCEVENTMASKSENSORSTREAMINGREADYSTATUS 0x00000400`

The control point must enable this mask to receive notifications from the location engine indicating its readiness to accept data from the sensors (accelerometer, gyroscope, etc.).

#### 9.5.1.24 `#define LOCEVENTMASKSETSPISTREAMINGREPORT 0x00001000`

The control point must enable this mask to receive Stationary Position Indicator (SPI) streaming report indications.

#### 9.5.1.25 `#define LOCEVENTMASKTIMESYNCREQ 0x00000800`

The control point must enable this mask to receive time sync requests from the GPS engine. Time sync enables the GPS engine to synchronize its clock with the sensor processor's clock.

#### 9.5.1.26 `#define LOCEVENTMASKVEHICLEDATAREADYSTATUS 0x00800000`

The control point must enable this mask to receive notifications from the location engine indicating its readiness to accept vehicle data (vehicle accelerometer, vehicle angular rate, vehicle odometry, etc.).

#### 9.5.1.27 `#define LOCEVENTMASKWIFIREQ 0x00000200`

The control point must enable this mask to receive Wi-Fi position request event indications.

### 9.5.2 Enumeration Type Documentation

#### 9.5.2.1 anonymous enum

Enumerator

```
eQMI_LOC_SESS_STATUS_SUCCESS
eQMI_LOC_SESS_STATUS_IN_PROGRESS
eQMI_LOC_SESS_STATUS_FAILURE
eQMI_LOC_SESS_STATUS_TIMEOUT
```

### 9.5.3 Function Documentation

#### 9.5.3.1 `int pack_loc_DeleteAssistData ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_loc_Delete_Assist_Data_t * reqArg )`

Delete Assistant Data pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.2 `int pack_loc_EventRegister ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_loc_EventRegister_t * reqArg )`

Event Register pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.3 `int pack_loc_SetExtPowerState ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_loc_SetExtPowerState_t * reqArg )`

Set Ext Power State pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.4 `int pack_loc_SetOperationMode ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_loc_SetOperationMode_t * reqArg )`

Set Operation Mode pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.5 `int pack_loc_Start ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_loc_Start_t * reqArg )`

LOC Start pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.6 int pack\_loc\_Stop ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen, pack\_loc\_Stop\_t \* reqArg )

Loc Stop pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.7 int unpack\_loc\_DeleteAssistData ( uint8\_t \* pResp, uint16\_t respLen, unpack\_loc\_Delete\_Assist\_Data\_t \* pOutput )

Delete Assistant Data unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.8 int unpack\_loc\_EngineState\_Ind ( uint8\_t \* pResp, uint16\_t respLen, unpack\_loc\_EngineState\_Ind\_t \* pOutput )

Loc Engine State Indication unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.9 int unpack\_loc\_EventRegister ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_loc\_EventRegister\_t \* *pOutput* )

Event Register unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.10 int unpack\_loc\_PositionRpt\_Ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_loc\_PositionRpt\_Ind\_t \* *pOutput* )

Loc Position Report Indication unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.11 int unpack\_loc\_SetExtPowerConfig\_Ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_loc\_SetExtPowerConfig\_Ind\_t \* *pOutput* )

Loc Set External Power Configure Indication unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.12 `int unpack_loc_SetExtPowerState ( uint8_t * pResp, uint16_t respLen, unpack_loc_SetExtPowerState_t * pOutput )`

Set Ext Power State unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.13 `int unpack_loc_SetOperationMode ( uint8_t * pResp, uint16_t respLen, unpack_loc_SetOperationMode_t * pOutput )`

Set Operation Mode unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.14 `int unpack_loc_Start ( uint8_t * pResp, uint16_t respLen, unpack_loc_Start_t * pOutput )`

Loc Start unpack



## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.5.3.15 int unpack\_loc\_Stop ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_loc\_Stop\_t \* *pOutput* )

Loc Stop unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.6 nas.h File Reference

## Data Structures

- struct [unpack\\_nas\\_GetSignalStrengths\\_t](#)
- struct [unpack\\_nas\\_SLQSGetSysSelectionPref\\_t](#)
- struct [nas\\_netSelectionPref](#)
- struct [nas\\_acqOrderPref](#)
- struct [nas\\_CSGID](#)
- struct [pack\\_nas\\_SLQSSetSysSelectionPref\\_t](#)
- struct [pack\\_nas\\_SLQSNasIndicationRegisterExt\\_t](#)
- struct [RFBandInfoElements](#)
- struct [unpack\\_nas\\_GetRFInfo\\_t](#)
- struct [cdmaSSInfo](#)
- struct [hdrSSInfo](#)
- struct [lteSSInfo](#)
- struct [tdscdmaSigInfoExt](#)
- struct [unpack\\_nas\\_SLQSNasGetSigInfo\\_t](#)
- struct [unpack\\_nas\\_SLQSNasSigInfoCallback\\_t](#)
- struct [unpack\\_nas\\_GetHomeNetwork\\_t](#)
- struct [nas\\_SrvStatusInfo](#)
- struct [nas\\_GSMSrvStatusInfo](#)

- struct [nas\\_sysInfoCommon](#)
- struct [nas\\_CDMASysInfo](#)
- struct [nas\\_HDRSysInfo](#)
- struct [nas\\_GSM SysInfo](#)
- struct [nas\\_WCDMASysInfo](#)
- struct [nas\\_LTESysInfo](#)
- struct [nas\\_AddCDMASysInfo](#)
- struct [nas\\_AddSysInfo](#)
- struct [nas\\_CallBarringSysInfo](#)
- struct [unpack\\_nas\\_SLQSGetSysInfo\\_t](#)
- struct [unpack\\_nas\\_SLQSSysInfoCallback\\_t](#)
- struct [unpack\\_nas\\_GetServingNetwork\\_t](#)
- struct [unpack\\_nas\\_GetServingNetworkCapabilities\\_t](#)
- struct [nas\\_QmiNas3GppNetworkInfo](#)
- struct [nas\\_QmiNas3GppNetworkRAT](#)
- struct [nas\\_QmisNasPcsDigit](#)
- struct [unpack\\_nas\\_PerformNetworkScan\\_t](#)
- struct [unpack\\_nas\\_SLQSSwiGetLteCQI\\_t](#)
- struct [nas\\_CommInfo](#)
- struct [nas\\_LTEInfo](#)
- struct [unpack\\_nas\\_SLQSNasSwiModemStatus\\_t](#)
- struct [nas\\_servSystem](#)
- struct [nas\\_dataSrvCapabilities](#)
- struct [nas\\_currentPLMN](#)
- struct [nas\\_roamIndList](#)
- struct [nas\\_qaQmi3Gpp2TimeZone](#)
- struct [nas\\_detailSvcInfo](#)
- struct [nas\\_CDMASysInfoExt](#)
- struct [nas\\_callBarStatus](#)
- struct [unpack\\_nas\\_SLQSGetServingSystem\\_t](#)
- struct [nas\\_rxSignalStrengthListElement](#)
- struct [nas\\_ecioListElement](#)
- struct [nas\\_errorRateListElement](#)
- struct [nas\\_rsrqInformation](#)
- struct [nas\\_lteSnrinformation](#)
- struct [nas\\_lteRsrpinformation](#)
- struct [unpack\\_nas\\_SLQSGetSignalStrength\\_t](#)
- struct [nas\\_SLQSSignalStrengthsIndReq](#)
- struct [pack\\_nas\\_SLQSSetSignalStrengthsCallback\\_t](#)
- struct [nas\\_SLQSSignalStrengthsInformation](#)
- struct [nas\\_RejectReasonTlv](#)
- struct [nas\\_SignalStrengthTlv](#)
- struct [nas\\_RFInfoTlv](#)
- struct [nas\\_SLQSSignalStrengthsTlv](#)
- struct [unpack\\_nas\\_SetEventReportInd\\_t](#)
- struct [unpack\\_nas\\_GetCDMANetworkParameters\\_t](#)
- struct [pack\\_nas\\_SetACCOLC\\_t](#)
- struct [nas\\_CDMARSSIThresh](#)
- struct [nas\\_CDMAECIOThresh](#)
- struct [nas\\_HDRRSSIThresh](#)
- struct [nas\\_HDRECIOThresh](#)
- struct [nas\\_HDRSINRThreshold](#)
- struct [nas\\_HDRIOThresh](#)
- struct [nas\\_GSMRSSIThresh](#)
- struct [nas\\_WCDMARSSIThresh](#)

- struct [nas\\_WCDMAECIOThresh](#)
- struct [nas\\_LTERSSIThresh](#)
- struct [nas\\_LTESNRThreshold](#)
- struct [nas\\_LTERSRQThresh](#)
- struct [nas\\_LTERSRPThresh](#)
- struct [nas\\_LTESigRptConfig](#)
- struct [nas\\_TDSCDMARSCPThresh](#)
- struct [nas\\_TDSCDMARSSIThresh](#)
- struct [nas\\_TDSCDMAECIOThresh](#)
- struct [nas\\_TDSCDMASINRThresh](#)
- struct [pack\\_nas\\_SLQSNasConfigSigInfo2\\_t](#)
- struct [unpack\\_nas\\_SetDataCapabilitiesCallback\\_ind\\_t](#)
- struct [unpack\\_nas\\_GetNetworkPreference\\_t](#)
- struct [pack\\_nas\\_SetNetworkPreference\\_t](#)
- struct [unpack\\_nas\\_SetNetworkPreference\\_t](#)
- struct [unpack\\_nas\\_SetRoamingIndicatorCallback\\_ind\\_t](#)
- struct [NAServingSystemInfo](#)
- struct [unpack\\_nas\\_SetServingSystemCallback\\_ind\\_t](#)
- struct [NASPhyCaAggScellIndType](#)
- struct [NASPhyCaAggScellIDBw](#)
- struct [NASPhyCaAggScellInfo](#)
- struct [NASPhyCaAggPcellInfo](#)
- struct [NASPhyCaAggScellIndex](#)
- struct [NasGetLTECphyCAInfo](#)
- struct [unpack\\_nas\\_SlqsGetLTECphyCAInfo\\_t](#)
- struct [NASEmergencyModeTlv](#)
- struct [NASModePreferenceTlv](#)
- struct [NASBandPreferenceTlv](#)
- struct [NASPRLPreferenceTlv](#)
- struct [NASRoamPreferenceTlv](#)
- struct [NASLTEBandPreferenceTlv](#)
- struct [NASNetSelPreferenceTlv](#)
- struct [NASServDomainPrefTlv](#)
- struct [NASGWAcqOrderPrefTlv](#)
- struct [NASQmiCbkNasSystemSelPrefInd](#)
- struct [unpack\\_nas\\_SLQSSetSysSelectionPrefCallBack\\_ind\\_t](#)
- struct [NASOTAMessageTlv](#)
- struct [NASLteNasReleaseInfoTlv](#)
- struct [NASTimeInfoTlv](#)
- struct [NASQmiCbkNasSwiOTAMessageInd](#)
- struct [unpack\\_nas\\_SLQSNasSwiOTAMessageCallback\\_ind\\_t](#)
- struct [nas\\_MNRInfo](#)
- struct [pack\\_nas\\_SLQSInitiateNetworkRegistration\\_t](#)
- struct [pack\\_nas\\_SLQSNasSwiOTAMessageCallback\\_t](#)
- struct [pack\\_nas\\_SLQSGetPLMNName\\_t](#)
- struct [unpack\\_nas\\_SLQSGetPLMNName\\_t](#)
- struct [nas\\_nmrCellInfo](#)
- struct [nas\\_GERANInfo](#)
- struct [nas\\_geranInstInfo](#)
- struct [nas\\_UMTSinstInfo](#)
- struct [nas\\_UMTSInfo](#)
- struct [nas\\_CDMAInfo](#)
- struct [nas\\_cellParams](#)
- struct [nas\\_LTEInfoIntraFreq](#)
- struct [nas\\_infoInterFreq](#)

- struct [nas\\_LTEInfoInterfreq](#)
- struct [nas\\_gsmCellInfo](#)
- struct [nas\\_lteGsmCellInfo](#)
- struct [nas\\_LTEInfoNeighboringGSM](#)
- struct [nas\\_wcdmaCellInfo](#)
- struct [nas\\_lteWcdmaCellInfo](#)
- struct [nas\\_LTEInfoNeighboringWCDMA](#)
- struct [nas\\_umtsLTENbrCell](#)
- struct [nas\\_WCDMAInfoLTENeighborCell](#)
- struct [unpack\\_nas\\_SLQSNasGetCellLocationInfo\\_t](#)
- struct [nas\\_timeInfo](#)
- struct [unpack\\_nas\\_SLQSGetNetworkTime\\_t](#)
- struct [nas\\_UniversalTime](#)
- struct [unpack\\_nas\\_SLQSNasNetworkTimeCallBack\\_ind\\_t](#)

## Macros

- [#define NAS\\_OTA\\_MESSAGE\\_MAX\\_BUF\\_SIZE](#) 2048
- [#define NAS\\_MAX\\_NUM\\_NETWORKS](#) 30
- [#define NAS\\_MAX\\_DESCRIPTION\\_LENGTH](#) 255
- [#define NAS\\_PLMN\\_LENGTH](#) 3
- [#define NAS\\_SERVING\\_SYSTEM\\_INFO\\_MAX\\_RADIO\\_INTERFACE\\_LIST](#) 255

## Enumerations

- enum [LIBPACK\\_NAS\\_LTE\\_CPHY\\_SCELL\\_STATE](#) {  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_SCELL\\_STATE\\_DECONFIGURED](#) =0x00,  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_SCELL\\_STATE\\_CONFIGURED\\_DEACTIVATED](#) =0x01,  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_SCELL\\_STATE\\_CONFIGURED\\_ACTIVATED](#) =0x02 }
- enum [LIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB](#) {  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_6](#) =0x00,  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_15](#) =0x01,  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_25](#) =0x02,  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_50](#) =0x03,  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_75](#) =0x04,  
[eLIBPACK\\_NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_100](#) =0x05 }

## Functions

- int [unpack\\_nas\\_GetSignalStrengths](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_GetSignalStrengths\\_t](#) \*pOutput)
- int [pack\\_nas\\_GetSignalStrengths](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReq, uint16\_t \*pLen)
- int [pack\\_nas\\_SLQSGetSysSelectionPref](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SLQSGetSysSelectionPref](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSGetSysSelectionPref\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSSetSysSelectionPref](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SLQSSetSysSelectionPref\\_t](#) \*pReqParam)
- int [unpack\\_nas\\_SLQSSetSysSelectionPref](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_nas\\_SLQSSetBandPreference](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, uint64\_t bandPref)
- int [unpack\\_nas\\_SLQSSetBandPreference](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_nas\\_SLQSNasIndicationRegisterExt](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SLQSNasIndicationRegisterExt\\_t](#) \*pReqParam)
- int [unpack\\_nas\\_SLQSNasIndicationRegisterExt](#) (uint8\_t \*pResp, uint16\_t respLen)

- int [pack\\_nas\\_GetRFInfo](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_GetRFInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_GetRFInfo\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSNasGetSigInfo](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SLQSNasGetSigInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSNasGetSigInfo\\_t](#) \*pOutput)
- int [unpack\\_nas\\_SLQSNasSigInfoCallback](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSNasSigInfoCallback\\_t](#) \*pOutput)
- int [unpack\\_nas\\_GetHomeNetwork](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_GetHomeNetwork\\_t](#) \*pOutput)
- int [pack\\_nas\\_GetHomeNetwork](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [pack\\_nas\\_SLQSSysInfo](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SLQSSysInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSSysInfo\\_t](#) \*pOutput)
- int [unpack\\_nas\\_SLQSNasSysInfoCallback](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSSysInfoCallback\\_t](#) \*pOutput)
- int [pack\\_nas\\_GetServingNetwork](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_GetServingNetwork](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_GetServingNetwork\\_t](#) \*pOutput)
- int [pack\\_nas\\_GetServingNetworkCapabilities](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_GetServingNetworkCapabilities](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_GetServingNetworkCapabilities\\_t](#) \*pOutput)
- int [pack\\_nas\\_PerformNetworkScan](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_PerformNetworkScan](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_PerformNetworkScan\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSSwiGetLteCQI](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SLQSSwiGetLteCQI](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSSwiGetLteCQI\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSNasSmiModemStatus](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SLQSNasSmiModemStatus](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSNasSmiModemStatus\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSServingSystem](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SLQSServingSystem](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSServingSystem\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSSignalStrength](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, uint16\_t reqMask)
- int [unpack\\_nas\\_SLQSSignalStrength](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSSignalStrength\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSSetSignalStrengthsCallback](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SLQSSetSignalStrengthsCallback\\_t](#) \*pReqParam)
- int [unpack\\_nas\\_SLQSSetSignalStrengthsCallback](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_nas\\_SetRFInfoCallback](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, uint8\_t \*pBenable)
- int [unpack\\_nas\\_SetRFInfoCallback](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_nas\\_SetLURejectCallback](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, uint8\_t \*pBenable)
- int [unpack\\_nas\\_SetLURejectCallback](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [unpack\\_nas\\_SetEventReportInd](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SetEventReportInd\\_t](#) \*pOutput)
- int [pack\\_nas\\_GetCDMANetworkParameters](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_GetCDMANetworkParameters](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_GetCDMA-NetworkParameters\\_t](#) \*pOutput)
- int [pack\\_nas\\_GetANAAAAuthenticationStatus](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_GetANAAAAuthenticationStatus](#) (uint8\_t \*pResp, uint16\_t respLen, uint32\_t \*pAuthStatus)
- int [pack\\_nas\\_GetACCOLC](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_GetACCOLC](#) (uint8\_t \*pResp, uint16\_t respLen, uint8\_t \*pAccolc)
- int [pack\\_nas\\_SetACCOLC](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SetACCOLC\\_t](#) reqParam)

- int [unpack\\_nas\\_SetACCOLC](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_nas\\_SLQSNasConfigSigInfo2](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SLQSNasConfigSigInfo2\\_t](#) \*pReqParam)
- int [unpack\\_nas\\_SLQSNasConfigSigInfo2](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [unpack\\_nas\\_SetDataCapabilitiesCallback\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SetDataCapabilitiesCallback\\_ind\\_t](#) \*pOutput)
- int [pack\\_nas\\_GetNetworkPreference](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_GetNetworkPreference](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_GetNetworkPreference\\_t](#) \*pOutput)
- int [pack\\_nas\\_SetNetworkPreference](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SetNetworkPreference\\_t](#) \*reqArg)
- int [unpack\\_nas\\_SetNetworkPreference](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SetNetworkPreference\\_t](#) \*pOutput)
- int [unpack\\_nas\\_SetRoamingIndicatorCallback\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SetRoamingIndicatorCallback\\_ind\\_t](#) \*pOutput)
- int [unpack\\_nas\\_SetServingSystemCallback\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SetServingSystemCallback\\_ind\\_t](#) \*pOutput)
- int [pack\\_nas\\_SlqsGetLTECphyCAInfo](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SlqsGetLTECphyCAInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SlqsGetLTECphyCAInfo\\_t](#) \*pOutput)
- int [unpack\\_nas\\_SLQSSetSysSelectionPrefCallBack\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSSetSysSelectionPrefCallBack\\_ind\\_t](#) \*pOutput)
- int [unpack\\_nas\\_SLQSNasSwiOTAMessageCallback\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSNasSwiOTAMessageCallback\\_ind\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSInitiateNetworkRegistration](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SLQSInitiateNetworkRegistration\\_t](#) \*pReqParam)
- int [unpack\\_nas\\_SLQSInitiateNetworkRegistration](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_nas\\_SLQSNasSwiOTAMessageCallback](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SLQSNasSwiOTAMessageCallback\\_t](#) \*pReqParam)
- int [unpack\\_nas\\_SLQSNasSwiOTAMessageCallback](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_nas\\_SLQSGetPLMNName](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_nas\\_SLQSGetPLMNName\\_t](#) \*reqArg)
- int [unpack\\_nas\\_SLQSGetPLMNName](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSGetPLMNName\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSNasGetCellLocationInfo](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SLQSNasGetCellLocationInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSNasGetCellLocationInfo\\_t](#) \*pOutput)
- int [pack\\_nas\\_SLQSGetNetworkTime](#) (pack\_qmi\_t \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_nas\\_SLQSGetNetworkTime](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSGetNetworkTime\\_t](#) \*pOutput)
- int [unpack\\_nas\\_SLQSNasNetworkTimeCallBack\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_nas\\_SLQSNasNetworkTimeCallBack\\_ind\\_t](#) \*pOutput)

## 9.6.1 Macro Definition Documentation

9.6.1.1 `#define NAS_MAX_DESCRIPTION_LENGTH 255`

9.6.1.2 `#define NAS_MAX_NUM_NETWORKS 30`

9.6.1.3 `#define NAS_OTA_MESSAGE_MAX_BUF_SIZE 2048`

9.6.1.4 `#define NAS_PLMN_LENGTH 3`

9.6.1.5 `#define NAS_SERVING_SYSTEM_INFO_MAX_RADIO_INTERFACE_LIST 255`

## 9.6.2 Enumeration Type Documentation

### 9.6.2.1 enum LIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB

Enumerator

***eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_6***  
***eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_15***  
***eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_25***  
***eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_50***  
***eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_75***  
***eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_100***

### 9.6.2.2 enum LIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE

Enumerator

***eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_DECONFIGURED***  
***eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_CONFIGURED\_DEACTIVATED***  
***eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_CONFIGURED\_ACTIVATED***

## 9.6.3 Function Documentation

### 9.6.3.1 int pack\_nas\_GetACCOLC ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )

Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.6.3.2 int pack\_nas\_GetANAAAuthenticationStatus ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )

Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.6.3.3 int pack\_nas\_GetCDMANetworkParameters ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.4 int pack\_nas\_GetHomeNetwork ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )**

get home network pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.5 int pack\_nas\_GetNetworkPreference ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )****Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**9.6.3.6 int pack\_nas\_GetRFInfo ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )**

get rf info pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values



9.6.3.7 int pack\_nas\_GetServingNetwork( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.8** int pack\_nas\_GetServingNetworkCapabilities ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.9** int pack\_nas\_GetSignalStrengths ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReq*, uint16\_t \* *pLen* )

get signal strengths pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.10** int pack\_nas\_PerformNetworkScan ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.11** int pack\_nas\_SetACCOLC ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_nas\_SetACCOLC\_t *reqParam* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request Parameters

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.12** int pack\_nas\_SetLURjectCallback ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, uint8\_t \* *pBenable* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>bEnable</i>	0/1 value to disable/enable indication respectively

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.13** int pack\_nas\_SetNetworkPreference ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_nas\_SetNetworkPreference\_t \* *reqArg* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>pack</i>	default prototype

**9.6.3.14** `int pack_nas_SetRFInfoCallback ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, uint8_t * pBenable )`

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>bEnable</i>	0/1 value to disable/enable indication respectively

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.15** `int pack_nas_SlqsGetLTECphyCAInfo ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**9.6.3.16** `int pack_nas_SLQSGetNetworkTime ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.17** `int pack_nas_SLQSGetPLMNName ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_nas_SLQSGetPLMNName_t * reqArg )`

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request prarmeters

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.18** int pack\_nas\_SLQSGetServingSystem ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.19** int pack\_nas\_SLQSGetSignalStrength ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, uint16\_t *reqMask* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqMask</i>	request mask for fetching extra signal info

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.20** int pack\_nas\_SLQSGetSysInfo ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.21** int pack\_nas\_SLQSGetSysSelectionPref ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.22** int pack\_nas\_SLQSIInitiateNetworkRegistration ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_nas\_SLQSIInitiateNetworkRegistration\_t \* *pReqParam* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>pReqParam</i>	request Parameters

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.23** int pack\_nas\_SLQSNasConfigSigInfo2 ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_nas\_SLQSNasConfigSigInfo2\_t \* *pReqParam* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request Parameters

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.24 int pack\_nas\_SLQSNasGetCellLocationInfo ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.25 int pack\_nas\_SLQSNasGetSigInfo ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

get sig info pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.26 int pack\_nas\_SLQSNasIndicationRegisterExt ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_nas\_SLQSNasIndicationRegisterExt\_t \* *pReqParam* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request Parameters

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.27** int pack\_nas\_SLQSNasSwiModemStatus ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.28** int pack\_nas\_SLQSNasSwiOTAMessageCallback ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_nas\_SLQSNasSwiOTAMessageCallback\_t \* *pReqParam* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>pReqParam</i>	request prarmeters

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.29** int pack\_nas\_SLQSSetBandPreference ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, uint64\_t *bandPref* )



## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>band</i>	preference

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.30** int pack\_nas\_SLQSSetSignalStrengthsCallback ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_nas\_SLQSSetSignalStrengthsCallback\_t \* *pReqParam* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>pReqParam</i>	request prarmeters

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.31** int pack\_nas\_SLQSSetSysSelectionPref ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_nas\_SLQSSetSysSelectionPref\_t \* *pReqParam* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request Parameters

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.32** int pack\_nas\_SLQSSwiGetLteCQI ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.33** int unpack\_nas\_GetACCOLC ( uint8\_t \* *pResp*, uint16\_t *respLen*, uint8\_t \* *pAccolc* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pAccolc</i>	accolc

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.34** int unpack\_nas\_GetANAAAuthenticationStatus ( uint8\_t \* *pResp*, uint16\_t *respLen*, uint32\_t \* *pAuthStatus* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>authStatus</i>	auth status

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.35** int unpack\_nas\_GetCDMANetworkParameters ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_nas\_GetCDMANetworkParameters\_t \* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	qmi output parameters

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.36 `int unpack_nas_GetHomeNetwork ( uint8_t * pResp, uint16_t respLen, unpack_nas_GetHomeNetwork_t * pOutput )`

get home network unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.37 `int unpack_nas_GetNetworkPreference ( uint8_t * pResp, uint16_t respLen, unpack_nas_GetNetworkPreference_t * pOutput )`

9.6.3.38 `int unpack_nas_GetRFInfo ( uint8_t * pResp, uint16_t respLen, unpack_nas_GetRFInfo_t * pOutput )`

get rf info unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.39 `int unpack_nas_GetServingNetwork ( uint8_t * pResp, uint16_t respLen, unpack_nas_GetServingNetwork_t * pOutput )`

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.40** int unpack\_nas\_GetServingNetworkCapabilities ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_nas\_GetServingNetworkCapabilities\_t \* *pOutput* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.41** int unpack\_nas\_GetSignalStrengths ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_GetSignalStrengths\_t \*  
*pOutput* )

get signal strengths unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.42** int unpack\_nas\_PerformNetworkScan ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_PerformNetworkScan\_t  
\* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.6.3.43 int unpack\_nas\_SetACCOLC ( uint8\_t \* *pResp*, uint16\_t *respLen* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.6.3.44 int unpack\_nas\_SetDataCapabilitiesCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SetDataCapabilitiesCallback\_ind\_t \* *pOutput* )

Data Capabilities indication unpack

## Parameters

in	<i>pResp</i>	qmi indication from modem
in	<i>respLen</i>	qmi indication length
out	<i>pOutput</i>	indication unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.6.3.45 int unpack\_nas\_SetEventReportInd ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SetEventReportInd\_t \* *pOutput* )

#### 9.6.3.46 int unpack\_nas\_SetLURejectCallback ( uint8\_t \* *pResp*, uint16\_t *respLen* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.47** int unpack\_nas\_SetNetworkPreference ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SetNetworkPreference\_t \* *pOutput* )

**9.6.3.48** int unpack\_nas\_SetRFInfoCallback ( uint8\_t \* *pResp*, uint16\_t *respLen* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.49** int unpack\_nas\_SetRoamingIndicatorCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SetRoamingIndicatorCallback\_ind\_t \* *pOutput* )

Roaming indication unpack

## Parameters

in	<i>pResp</i>	qmi indication from modem
in	<i>respLen</i>	qmi indication length
out	<i>pOutput</i>	indication unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.50** int unpack\_nas\_SetServingSystemCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SetServingSystemCallback\_ind\_t \* *pOutput* )

**9.6.3.51** int unpack\_nas\_SlqsGetLTECphyCAInfo ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SlqsGetLTECphyCAInfo\_t \* *pOutput* )

**9.6.3.52** int unpack\_nas\_SLQSGetNetworkTime ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSGetNetworkTime\_t \* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.53** int unpack\_nas\_SLQSGetPLMNName ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSGetPLMNName\_t \* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.54** int unpack\_nas\_SLQSGetServingSystem ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSGetServingSystem\_t \* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.55** int unpack\_nas\_SLQSGetSignalStrength ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSGetSignalStrength\_t \* *pOutput* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.56 int unpack\_nas\_SLQSGetSysInfo ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSGetSysInfo\_t \* *pOutput* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.57 int unpack\_nas\_SLQSGetSysSelectionPref ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSGetSysSelectionPref\_t \* *pOutput* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.58 int unpack\_nas\_SLQSIInitiateNetworkRegistration ( uint8\_t \* *pResp*, uint16\_t *respLen* )



## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.6.3.59 int unpack\_nas\_SLQSNasConfigSigInfo2 ( uint8\_t \* *pResp*, uint16\_t *respLen* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.6.3.60 int unpack\_nas\_SLQSNasGetCellLocationInfo ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSNasGetCellLocationInfo\_t \* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.6.3.61 int unpack\_nas\_SLQSNasGetSigInfo ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSNasGetSigInfo\_t \* *pOutput* )

get sig info unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.62** int unpack\_nas\_SLQSNasIndicationRegisterExt ( uint8\_t \* *pResp*, uint16\_t *respLen* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.63** int unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t \* *pOutput* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	sig info indication unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.6.3.64** int unpack\_nas\_SLQSNasSigInfoCallback ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_nas\_SLQSNasSigInfoCallback\_t \* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	sig info indication unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.65 int unpack\_nas\_SLQSNasSwiModemStatus ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_nas\_SLQSNasSwiModemStatus\_t \* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.66 int unpack\_nas\_SLQSNasSwiOTAMessageCallback ( uint8\_t \* *pResp*, uint16\_t *respLen* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.67 int unpack\_nas\_SLQSNasSwiOTAMessageCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_nas\_SLQSNasSwiOTAMessageCallback\_ind\_t \* *pOutput* )

OTA message indication unpack

**Parameters**

in	<i>pResp</i>	qmi indication from modem
in	<i>respLen</i>	qmi indication length
out	<i>pOutput</i>	indication unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.68 int unpack\_nas\_SLQSNasSysInfoCallback ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_nas\_SLQSSysInfoCallback\_t \* *pOutput* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.69 int unpack\_nas\_SLQSSetBandPreference ( uint8\_t \* *pResp*, uint16\_t *respLen* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

9.6.3.70 int unpack\_nas\_SLQSSetSignalStrengthsCallback ( uint8\_t \* *pResp*, uint16\_t *respLen* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.71 int unpack\_nas\_SLQSSetSysSelectionPref ( uint8\_t \* *pResp*, uint16\_t *respLen* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.72 int unpack\_nas\_SLQSSetSysSelectionPrefCallBack\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_nas\_SLQSSetSysSelectionPrefCallBack\_ind\_t \* *pOutput* )

System Selection Preference indication unpack

## Parameters

in	<i>pResp</i>	qmi indication from modem
in	<i>respLen</i>	qmi indication length
out	<i>pOutput</i>	indication unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.6.3.73 int unpack\_nas\_SLQSSwiGetLteCQI ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_nas\_SLQSSwiGetLteCQI\_t \*  
*pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.7 qaCbkCatEventReportInd.h File Reference

## Data Structures

- struct [CatEventIDDataTlv](#)

- struct [CatAlphaIdentifierTlv](#)
- struct [CatEventListTlv](#)
- struct [CatRefreshTlv](#)
- struct [CatEndProactiveSessionTlv](#)
- union [currentCatEvent](#)
- struct [CatCommonEventTlv](#)
- struct [QmiCbkCatEventStatusReportInd](#)

## Macros

- `#define QMI_MAX_CAT_EVENT_DATA_LENGTH 255`
- `#define QMI_CAN_COMMON_EVENT_TLV_NUMBER 11`

## Enumerations

- enum [eQMI\\_CAT\\_EVENT\\_REPORT\\_IND\\_TLV](#) {  
[eTLV\\_CBK\\_DISPLAY\\_TEXT](#) = 0x10,  
[eTLV\\_CBK\\_GET\\_IN\\_KEY](#) = 0x11,  
[eTLV\\_CBK\\_GET\\_INPUT](#) = 0x12,  
[eTLV\\_CBK\\_SETUP\\_MENU](#) = 0x13,  
[eTLV\\_CBK\\_SELECT\\_ITEM](#) = 0x14,  
[eTLV\\_CBK\\_ALPHA\\_IDENTIFIER](#) = 0x15,  
[eTLV\\_CBK\\_SETUP\\_EVENT\\_LIST](#) = 0x16,  
[eTLV\\_CBK\\_SETUP\\_IDLE\\_MODE\\_TEXT](#) = 0x17,  
[eTLV\\_CBK\\_LANGUAGE\\_NOTIFICATION](#) = 0x18,  
[eTLV\\_CBK\\_REFRESH](#) = 0x19,  
[eTLV\\_CBK\\_END\\_PROACTIVE\\_SESSION](#) = 0x1A }
- enum [eQMI\\_CAT\\_EVENT\\_REPORT\\_IND\\_TLV\\_LENGTH](#) {  
[eTLV\\_SETUP\\_EVENT\\_LIST\\_LENGTH](#) = 0x04,  
[eTLV\\_REFRESH\\_LENGTH](#) = 0x03,  
[eTLV\\_END\\_PROACTIVE\\_SESSION\\_LENGTH](#) = 0x01 }

## Functions

- enum [eQCWWANError UpkQmiCbkCatEventReportInd](#) (BYTE \*pMdmResp, struct [QmiCbkCatEventStatusReportInd](#) \*pAipResp)

### 9.7.1 Macro Definition Documentation

9.7.1.1 `#define QMI_CAN_COMMON_EVENT_TLV_NUMBER 11`

9.7.1.2 `#define QMI_MAX_CAT_EVENT_DATA_LENGTH 255`

### 9.7.2 Enumeration Type Documentation

9.7.2.1 enum [eQMI\\_CAT\\_EVENT\\_REPORT\\_IND\\_TLV](#)

#### Enumerator

***eTLV\_CBK\_DISPLAY\_TEXT***  
***eTLV\_CBK\_GET\_IN\_KEY***  
***eTLV\_CBK\_GET\_INPUT***  
***eTLV\_CBK\_SETUP\_MENU***  
***eTLV\_CBK\_SELECT\_ITEM***

***eTLV\_CBK\_ALPHA\_IDENTIFIER***  
***eTLV\_CBK\_SETUP\_EVENT\_LIST***  
***eTLV\_CBK\_SETUP\_IDLE\_MODE\_TEXT***  
***eTLV\_CBK\_LANGUAGE\_NOTIFICATION***  
***eTLV\_CBK\_REFRESH***  
***eTLV\_CBK\_END\_PROACTIVE\_SESSION***

#### 9.7.2.2 enum eQMI\_CAT\_EVENT\_REPORT\_IND\_TLV\_LENGTH

Enumerator

***eTLV\_SETUP\_EVENT\_LIST\_LENGTH***  
***eTLV\_REFRESH\_LENGTH***  
***eTLV\_END\_PROACTIVE\_SESSION\_LENGTH***

### 9.7.3 Function Documentation

9.7.3.1 enum eQCWWANError UpkQmiCbkCatEventReportInd ( BYTE \* *pMdmResp*, struct QmiCbkCatEventStatusReportInd \* *pAipResp* )

## 9.8 qaCbkSwiOmaDmEventReportInd.h File Reference

### Data Structures

- struct [sessionInfoTlv](#)
- struct [sessionInfoTlvExt](#)
- struct [QmiCbkSwiOmaDmEventStatusReportInd](#)
- struct [QmiCbkSwiOmaDmEventStatusReportIndExt](#)

### Macros

- #define [QMI\\_SWIOMA\\_DM\\_FOTA](#) 0x00
- #define [QMI\\_SWIOMA\\_DM\\_CONFIG](#) 0x01
- #define [QMI\\_SWIOMA\\_DM\\_NOT](#) 0x02

### Enumerations

- enum [eQMI\\_SWIOMA\\_DM\\_EVENT\\_REPORT\\_IND](#) {  
[eTLV\\_IND\\_OMA\\_DM\\_FOTA](#) = 0x10,  
[eTLV\\_IND\\_OMA\\_DM\\_CONFIG](#) = 0x11,  
[eTLV\\_IND\\_OMA\\_DM\\_NOT](#) = 0x12 }

### Functions

- enum [eQCWWANError](#) UpkQmiCbkSwiOmaDmEventReportInd (BYTE \**pMdmResp*, struct [QmiCbkSwiOmaDmEventStatusReportInd](#) \**pAipResp*)
- package enum [eQCWWANError](#) UpkQmiCbkSwiOmaDmEventReportIndExt (BYTE \**pMdmResp*, struct [QmiCbkSwiOmaDmEventStatusReportInd](#) \**pAipResp*)

### 9.8.1 Macro Definition Documentation

9.8.1.1 `#define QMI_SWIOMA_DM_CONFIG 0x01`

9.8.1.2 `#define QMI_SWIOMA_DM_FOTA 0x00`

9.8.1.3 `#define QMI_SWIOMA_DM_NOT 0x02`

### 9.8.2 Enumeration Type Documentation

9.8.2.1 `enum eQMI_SWIOMA_DM_EVENT_REPORT_IND`

Enumerator

***eTLV\_IND\_OMA\_DM\_FOTA***

***eTLV\_IND\_OMA\_DM\_CONFIG***

***eTLV\_IND\_OMA\_DM\_NOT***

### 9.8.3 Function Documentation

9.8.3.1 `enum eQCWWANError UpkQmiCbkSwiOmaDmEventReportInd ( BYTE * pMdmResp, struct QmiCbkSwiOmaDmEventStatusReportInd * pApiResp )`

9.8.3.2 `package enum eQCWWANError UpkQmiCbkSwiOmaDmEventReportIndExt ( BYTE * pMdmResp, struct QmiCbkSwiOmaDmEventStatusReportInd * pApiResp )`

## 9.9 qaGobiApiAudio.h File Reference

Audio Service API function prototypes.

### Data Structures

- struct [GetAudioProfileReq](#)
- struct [GetAudioProfileResp](#)
- struct [SetAudioProfileReq](#)
- struct [GetAudioPathConfigReq](#)
- struct [TXPCMIIRFtr](#)
- struct [RXPCMIIRFtr](#)
- struct [RXAGCList](#)
- struct [RXAVCList](#)
- struct [TXAGCList](#)
- struct [GetAudioPathConfigResp](#)
- struct [SetAudioPathConfigReq](#)
- struct [GetAudioVolTLBConfigReq](#)
- struct [GetAudioVolTLBConfigResp](#)
- struct [SetAudioVolTLBConfigReq](#)
- struct [SetAudioVolTLBConfigResp](#)

### Functions

- [ULONG SLQSGetAudioProfile](#) ([GetAudioProfileReq](#) \*pGetAudioProfileReq, [GetAudioProfileResp](#) \*pGetAudioProfileResp)
- [ULONG SLQSSetAudioProfile](#) ([SetAudioProfileReq](#) \*pSetAudioProfileReq)



- [ULONG SLQSGetAudioPathConfig](#) ([GetAudioPathConfigReq](#) \*pGetAudioPathConfigReq, [GetAudioPathConfigResp](#) \*pGetAudioPathConfigResp)
- [ULONG SLQSSetAudioPathConfig](#) ([SetAudioPathConfigReq](#) \*pSetAudioPathConfigReq)
- [ULONG SLQSGetAudioVolTLBConfig](#) ([GetAudioVolTLBConfigReq](#) \*pGetAudioVolTLBCfgReq, [GetAudioVolTLBConfigResp](#) \*pGetAudioVolTLBCfgResp)
- [ULONG SLQSSetAudioVolTLBConfig](#) ([SetAudioVolTLBConfigReq](#) \*pSetAudioVolTLBCfgReq, [SetAudioVolTLBConfigResp](#) \*pSetAudioVolTLBCfgResp)

### 9.9.1 Detailed Description

Audio Service API function prototypes.

### 9.9.2 Function Documentation

#### 9.9.2.1 [ULONG SLQSGetAudioPathConfig](#) ( [GetAudioPathConfigReq](#) \* *pGetAudioPathConfigReq*, [GetAudioPathConfigResp](#) \* *pGetAudioPathConfigResp* )

This API gets the audio path configuration parameters.

##### Parameters

<i>pGetAudioPathConfigReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">GetAudioPathConfigReq</a> for more information</li> </ul>
<i>pGetAudioPathConfigResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">GetAudioPathConfigResp</a> for more information</li> </ul>

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Device Supported: SL9090  
Timeout: 5 seconds

#### 9.9.2.2 [ULONG SLQSGetAudioProfile](#) ( [GetAudioProfileReq](#) \* *pGetAudioProfileReq*, [GetAudioProfileResp](#) \* *pGetAudioProfileResp* )

This API get the profile content of the requested audio generator.

##### Parameters

<i>pGetAudioProfileReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">GetAudioProfileReq</a> for more information</li> </ul>
---------------------------------	---

<i>pGetAudioProfileResp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetAudioProfileResp</a> for more information</li> </ul>
----------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Device Supported: SL9090  
Timeout: 5 seconds

### 9.9.2.3 ULONG SLQSGetAudioVolTLBConfig ( GetAudioVolTLBConfigReq \* pGetAudioVolTLBCfgReq, GetAudioVolTLBConfigResp \* pGetAudioVolTLBCfgResp )

This API gets the audio path configuration parameters.

**Parameters**

<i>pGetAudioVolTLBCfgReq[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetAudioVolTLBConfigReq</a> for more information</li> </ul>
<i>pGetAudioVolTLBCfgResp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetAudioVolTLBConfigResp</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Device Supported: SL9090  
Timeout: 5 seconds

### 9.9.2.4 ULONG SLQSSetAudioPathConfig ( SetAudioPathConfigReq \* pSetAudioPathConfigReq )

This API sets the audio path configuration parameters.

**Parameters**

<i>pSetAudioPath- ConfigReq[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">SetAudioPathConfigReq</a> for more information</li></ul>
---	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Device Supported: SL9090  
Timeout: 5 seconds

**9.9.2.5 ULONG SLQSSetAudioProfile ( SetAudioProfileReq \* pSetAudioProfileReq )**

This API sets an audio profile.

**Parameters**

<i>pSetAudio- ProfileReq[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">SetAudioProfileReq</a> for more information</li></ul>
--------------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Device Supported: SL9090  
Timeout: 5 seconds

**9.9.2.6 ULONG SLQSSetAudioVoITLBConfig ( SetAudioVoITLBConfigReq \* pSetAudioVoITLBcfgReq, SetAudioVoITLBConfigResp \* pSetAudioVoITLBcfgResp )**

This API sets the audio path configuration parameters.

**Parameters**

<i>pSetAudioVoITL- BCfgReq[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">SetAudioVoITLBConfigReq</a> for more information</li></ul>
--	--

<i>pSetAudioVolTL-BCfgResp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SetAudioVolTLBConfigResp</a> for more information</li> </ul>
-------------------------------------	---

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

Device Supported: SL9090  
Timeout: 5 seconds

## 9.10 qaGobiApiCat.h File Reference

Card Application Toolkit API function headers.

### Functions

- [ULONG CATSendEnvelopeCommand](#) (ULONG cmdID, ULONG dataLen, BYTE \*pData)
- [ULONG CATSendTerminalResponse](#) (ULONG refID, ULONG dataLen, BYTE \*pData)

#### 9.10.1 Detailed Description

Card Application Toolkit API function headers.

#### 9.10.2 Function Documentation

##### 9.10.2.1 ULONG CATSendEnvelopeCommand ( ULONG cmdID, ULONG dataLen, BYTE \* pData )

Sends the envelope command to the device.

#### Parameters

<i>cmdID</i>	<ul style="list-style-type: none"> <li>• Envelope command type <ul style="list-style-type: none"> <li>– 0x01 - Menu Selection</li> <li>– 0x02 - Event DL User activity</li> <li>– 0x03 - Event DL Idle Screen Available</li> <li>– 0x04 - Event DL Language Selection</li> </ul> </li> </ul>
--------------	--

<i>dataLen</i>	<ul style="list-style-type: none"> <li>Length of pData in bytes</li> </ul>
<i>pData</i> [IN]	<ul style="list-style-type: none"> <li>Encoded envelope data as defined in ETSI TS 102 223, section 7 [Smart Cards: Card Application Toolkit (CAT) – Release 4]</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS  
Timeout: 2 seconds

**9.10.2.2 ULONG CATSendTerminalResponse ( ULONG refID, ULONG dataLen, BYTE \* pData )**

Sends the terminal response to the device.

**Parameters**

<i>refID</i>	<ul style="list-style-type: none"> <li>Proactive command reference ID. The value should be the same as indicated in the CAT event callback data for the relevant proactive command.</li> </ul>
<i>dataLen</i>	<ul style="list-style-type: none"> <li>Terminal response data length</li> </ul>
<i>pData</i> [IN]	<ul style="list-style-type: none"> <li>Terminal response for the relevant proactive command encoded as per ETSI TS 102 223, section 6.8 [Smart Cards: Card Application Toolkit (CAT) – Release 4]</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS  
Timeout: 2 seconds

## 9.11 qaGobiApiCbK.h File Reference

Callback Service API function prototypes.

### Data Structures

- struct [qaQmiInterfaceInfo](#)
- struct [slqsSessionStateInfo](#)
- struct [slqsWdsEventInfo](#)
- struct [TransferStatsDataType](#)
- struct [SignalStrengthDataType](#)
- struct [SMSMTMessage](#)
- struct [SMSTransferRouteMTMessage](#)
- struct [SMSMessageMode](#)
- struct [SMSEtwsMessage](#)
- struct [SMSEtwsPlmn](#)
- struct [SMSCAddress](#)
- struct [SMSOnIMS](#)
- struct [SMSEventInfo\\_s](#)
- struct [CATEventDataType](#)
- struct [ServingSystemInfo](#)
- struct [RoamingInfo](#)
- struct [SLQSSignalStrengthsInformation](#)
- struct [SLQSSignalStrengthsIndReq](#)
- struct [ECTNum](#)
- struct [voiceSUPSNotification](#)
- struct [voiceSetAllCallStatusCbKInfo](#)
- struct [\\_transLayerInfoNotification](#)
- struct [\\_transNWRegInfoNotification](#)
- struct [UIMStatusChangeInfo](#)
- struct [voicePrivacyInfo](#)
- struct [voiceDTMFEventInfo](#)
- struct [voiceSUPSInfo](#)
- struct [nasSysInfo](#)
- struct [UniversalTime](#)
- struct [nasNetworkTime](#)
- struct [omaDmFotaTlv](#)
- struct [omaDmFotaTlvExt](#)
- struct [omaDmConfigTlvExt](#)
- struct [omaDmConfigTlv](#)
- struct [omaDmNotificationsTlv](#)
- union [sessionInfo](#)
- union [sessionInfoExt](#)
- struct [SMSMemoryInfo](#)
- struct [voiceOTASPStatusInfo](#)
- struct [signalInfo](#)
- struct [callerIDInfo](#)
- struct [callingPartyInfo](#)
- struct [calledPartyInfo](#)
- struct [redirNumInfo](#)
- struct [NSSAudioCtrl](#)
- struct [lineCtrlInfo](#)
- struct [extDispRecInfo](#)
- struct [voiceInfoRec](#)

- struct [msgWaitingInfo](#)
- struct [QosFlowInfoState](#)
- struct [QosFlowInfo](#)
- struct [QosEventInfo](#)
- struct [nasSigInfo](#)
- struct [\\_modemTempNotification](#)
- struct [\\_packetSrvStatus](#)
- struct [HDRPersonalityInd](#)
- struct [imsSIPConfigInfo](#)
- struct [imsRegMgrConfigInfo](#)
- struct [imsSMSConfigInfo](#)
- struct [imsUserConfigInfo](#)
- struct [imsVoIPConfigInfo](#)
- struct [USSDNoWaitIndicationInfo](#)
- struct [channelRate](#)
- struct [DUNCallInfoInd](#)
- struct [SMSAsyncRawSend\\_s](#)
- struct [LteNasReleaseInfo\\_s](#)
- struct [SwtOTAMsg\\_s](#)
- struct [DHCPOption](#)
- struct [DHCPOptionList](#)
- struct [WdsDHCPv4ClientLeaseInd](#)
- struct [QmiCbKLocCradleMountInd](#)
- struct [QmiCbKLocEventTimeSyncInd](#)
- struct [QmiCbKLocInjectTimeInd](#)
- struct [accelAcceptReady\\_s](#)
- struct [gyroAcceptReady\\_s](#)
- struct [accelTempAcceptReady\\_s](#)
- struct [gyroTempAcceptReady\\_s](#)
- struct [QmiCbKLocSensorStreamingInd](#)
- struct [QmiCbKLocInjectSensorDataInd](#)
- struct [precisionDilution\\_s](#)
- struct [gpsTime\\_s](#)
- struct [sensorDataUsage\\_s](#)
- struct [svUsedforFix\\_s](#)
- struct [QmiCbKLocPositionReportInd](#)
- struct [imsaRegStatusInfo](#)
- struct [imsaSvcStatusInfo](#)
- struct [imsaRatStatusInfo](#)
- struct [imsaPdpStatusInfo](#)
- struct [satelliteInfo](#)
- struct [gnssSvInfoNotification](#)
- struct [delAssistDataStatus](#)
- struct [QmiCbKLocNasLTECphyCaInfo](#)
- struct [RankIndicatorInd](#)
- struct [QmiCbKLocInjectUTCTimeInd](#)
- struct [QmiCbKLocInjectPositionInd](#)
- struct [UIMSlotStatusChangeInfo](#)
- struct [QmiCbKLocEngineStateInd](#)
- struct [\\_getResetInfoNotification](#)
- struct [\\_MitigationDevInfo](#)
- struct [QmiCbKLocTmdMitiLvlRptInd](#)
- struct [QmiCbKLocSetExtPowerConfigInd](#)

## Macros

- #define SIGSTRENGTH\_THRESHOLD\_ARR\_SZ 5
- #define QMI\_WMS\_MAX\_PAYLOAD\_LENGTH 256
- #define QMI\_ETWS\_MAX\_PAYLOAD\_LENGTH 1254 /\* Qualcomm defined max \*/
- #define QMI\_MAX\_VOICE\_NUMBER\_LENGTH 81
- #define MAX\_NO\_OF\_UUSINFO 20
- #define MAXUSSDLENGTH 182
- #define MAX\_NO\_OF\_CALLS 20
- #define CBK\_ENABLE\_EVENT 0x01
- #define CBK\_DISABLE\_EVENT 0x00
- #define CBK\_NOCHANGE 0xFF
- #define MAX\_NO\_OF\_APPLICATIONS 10
- #define MAX\_NO\_OF\_SLOTS 5
- #define MAX\_NO\_OF\_FILES 255
- #define MAX\_PATH\_LENGTH 255
- #define EVENT\_MASK\_CARD 0x00000001
- #define EVENT\_MASK\_PHY\_SLOT\_STATUS 0x00000010
- #define EVENT\_MASK\_DEREGISTER\_ALL 0x00000000
- #define REGISTER\_EVENT 0x01
- #define DEREGISTER\_EVENT 0x00
- #define FIRST\_INSTANCE 0x00
- #define SECOND\_INSTANCE 0x01
- #define THIRD\_INSTANCE 0x02
- #define INVALID\_INSTACNE 0x08
- #define REGISTER\_SRV 0x01
- #define DEREGISTER\_SRV 0x00
- #define WDS\_SRV 0x01
- #define NAS\_SRV 0x02
- #define PDS\_SRV 0x04
- #define VOICE\_SRV 0x08
- #define NUM\_OF\_SET 0xFF
- #define IPV4 4
- #define IPV6 6
- #define IPV4V6 7
- #define LOC\_EVENT\_MASK\_ENG\_STATE 0x00000080
- #define LOC\_EVENT\_MASK\_TIME\_SYNC 0x00000800
- #define LOC\_EVENT\_MASK\_INJECT\_TIME 0x00000010
- #define LOC\_EVENT\_MASK\_SENSOR\_STREAM 0x00000400
- #define LOC\_EVENT\_POSITION\_REPORT 0x00000001
- #define LOC\_EVENT\_MASK\_GNSS\_SV\_INFO 0x00000002
- #define DHCP\_MAX\_NUM\_OPTIONS 30
- #define DHCP\_OPTION\_DATA\_BUF\_SIZE 2048 /\* current max size of raw message in SDK process is 2048 \*/
- #define MAX\_MITIGATION\_DEV\_ID\_LEN 255
- #define MAX\_RADIO\_INTERFACE\_LIST 255
- #define USSD\_DCS\_ASCII 0x01 /\* ASCII coding scheme \*/
- #define USSD\_DCS\_8BIT 0x02 /\* 8-bit coding scheme \*/
- #define USSD\_DCS\_UCS2 0x03 /\* UCS2 coding scheme \*/



## Typedefs

- typedef void(\* tFNSLQSSessionState )(slqsSessionStateInfo \*pSessionStateInfo)
- typedef void(\* tFNSLQSWDSEvent )(slqsWdsEventInfo \*pWdsEventInfo)
- typedef void(\* tFNPower )(ULONG operatingMode)
- typedef void(\* tFNActivationStatus )(ULONG activationStatus)
- typedef void(\* tFNMobileIPStatus )(ULONG mipStatus)
- typedef void(\* tFNRoamingIndicator )(ULONG roaming)
- typedef void(\* tFNDataCapabilities )(BYTE dataCapsSize, BYTE \*pDataCaps)
- typedef void(\* tFNSignalStrength )(INT8 signalStrength, ULONG radiolInterface)
- typedef void(\* tFNRInfo )(ULONG radiolInterface, ULONG activeBandClass, ULONG activeChannel)
- typedef void(\* tFNUReject )(ULONG serviceDomain, ULONG rejectCause)
- typedef void(\* tFNNewSMS )(ULONG storageType, ULONG messageIndex)
- typedef enum SMSEventType eSMSEventType
- typedef struct SMSMTMessage SMSMTMessageInfo
- typedef struct SMSTransferRouteMTMessage SMSTransferRouteMTMessageInfo
- typedef struct SMSMessageMode SMSMessageModeInfo
- typedef struct SMSEtwsMessage SMSEtwsMessageInfo
- typedef struct SMSEtwsPlmn SMSEtwsPlmnInfo
- typedef struct SMSCAddress SMSCAddressInfo
- typedef struct SMSOnIMS SMSOnIMSInfo
- typedef struct SMSEventInfo\_s SMSEventInfo
- typedef void(\* tFNSMSEvents )(SMSEventInfo \*pSMSEventInfo)
- typedef void(\* tFNNewNMEA )(LPCSTR pNMEA)
- typedef void(\* tFNPDSSState )(ULONG enabledStatus, ULONG trackingStatus)
- typedef void(\* tFNCATEvent )(ULONG eventId, ULONG eventLen, BYTE \*pEventData)
- typedef enum device\_state\_enum eDevState
- typedef void(\* tFNDeviceStateChange )(eDevState device\_state)
- typedef void(\* tFNNet )(ULONG q\_depth, BYTE isThrottle, BYTE instanceId)
- typedef void(\* tFNFWdldCompletion )(ULONG fwdld\_completion\_status)
- typedef void(\* tFNSLQSSOMADMAAlert )(ULONG eventType, BYTE \*pEventFields)
- typedef void(\* tFNOMADMState )(ULONG sessionState, ULONG failureReason)
- typedef void(\* tFNServingSystem )(struct ServingSystemInfo \*pServingSystem, struct RoamingInfo \*pRoamingInfo)
- typedef void(\* tFNBandPreference )(ULONGLONG band\_pref)
- typedef void(\* tFNUSSDRelease )(void)
- typedef void(\* tFNUSSDNotification )(ULONG type, BYTE \*pNetworkInfo)
- typedef void(\* tFNSLQSSignalStrengths )(struct SLQSSignalStrengthsInformation sSLQSSignalStrengthsInfo)
- typedef void(\* tFNSUPSNotification )(voiceSUPSNotification \*pVoiceSUPSNotification)
- typedef void(\* tFNSDKTerminated )(BYTE \*psReason)
- typedef void(\* tFNAIAllCallStatus )(voiceSetAllCallStatusCbInfo \*pVoiceSetAllCallStatusCbInfo)
- typedef struct \_transLayerInfoNotification transLayerNotification
- typedef void(\* tFNtransLayerInfo )(transLayerNotification \*pTransLayerNotification)
- typedef struct \_transNWRegInfoNotification transNWRegInfoNotification
- typedef void(\* tFNtransNWRegInfo )(transNWRegInfoNotification \*pTransNWRegInfoNotification)
- typedef void(\* tFNSysSelectionPref )(sysSelectPrefInfo \*pSysSelectPrefInfo)
- typedef void(\* tFNUIMRefresh )(UIMRefreshEvent \*pUIMRefreshEvent)
- typedef void(\* tFNUIMStatusChangeInfo )(UIMStatusChangeInfo \*pUIMStatusChangeInfo)
- typedef void(\* tFNPrivacyChange )(voicePrivacyInfo \*pVoicePrivacyInfo)
- typedef void(\* tFNDTMFEvent )(voiceDTMFEventInfo \*pVoiceDTMFEventInfo)
- typedef void(\* tFNSUPSInfo )(voiceSUPSInfo \*pVoiceSUPSInfo)

- typedef void(\* tFNSysInfo )(nasSysInfo \*pNasSysInfo)
- typedef void(\* tFNNetworkTime )(nasNetworkTime \*pNasNetworkTime)
- typedef union sessionInfo sessionInformation
- typedef union sessionInfoExt sessionInformationExt
- typedef void(\* tFNMemoryFull )(SMSMemoryInfo \*pSMSMemoryFullInfo)
- typedef void(\* tFNOTASPStatus )(voiceOTASPStatusInfo \*pVoiceOTASPStatusInfo)
- typedef void(\* tFNInfoRec )(voiceInfoRec \*pVoiceInfoRec)
- typedef void(\* tFNMessageWaiting )(msgWaitingInfo \*pSMSMessageWaitingInfo)
- typedef void(\* tFNSLQSQOSEvent )(BYTE instance, QosFlowInfo \*pFlowInfo)
- typedef void(\* tFNQosStatus )(BYTE instance, ULONG id, BYTE status, BYTE event, BYTE reason)
- typedef void(\* tFNQosNWStatus )(BYTE status)
- typedef void(\* tFNQosPriEvent )(WORD event)
- typedef void(\* tFNSigInfo )(nasSigInfo \*pNasSigInfo)
- typedef struct  
\_modemTempNotification modemTempNotification
- typedef void(\* tFNModemTempInfo )(modemTempNotification \*pModemTempNotification)
- typedef struct \_packetSrvStatus packetSrvStatus
- typedef void(\* tFNPacketSrvState )(packetSrvStatus \*pPacketSrvStatus)
- typedef void(\* tFNHDRPersonality )(HDRPersonalityInd \*pHDRPers)
- typedef void(\* tFNImSIPConfig )(imsSIPConfigInfo \*pImSIPConfigInfo)
- typedef void(\* tFNImRegMgrConfig )(imsRegMgrConfigInfo \*pImRegMgrConfigInfo)
- typedef void(\* tFNImSMSConfig )(imsSMSConfigInfo \*pImSMSConfigInfo)
- typedef void(\* tFNImUserConfig )(imsUserConfigInfo \*pImUserConfigInfo)
- typedef void(\* tFNImVoIPConfig )(imsVoIPConfigInfo \*pImVoIPConfigInfo)
- typedef void(\* tFNUSSDNoWaitIndication )(USSDNoWaitIndicationInfo \*pNetworkInfo)
- typedef void(\* tFNDUNCAllInfo )(DUNCAllInfoInd \*pDUNCAllInfo)
- typedef void(\* tFNDataSysStatus )(CurrDataSysStat \*pCurrDataSysStat)
- typedef struct SMSAsyncRawSend\_s SMSAsyncRawSend
- typedef void(\* tFNAsyncRawSend )(SMSAsyncRawSend \*pSMSAsyncRawSend)
- typedef struct LteNasReleaseInfo\_s LteNasReleaseInfo
- typedef struct SwiOTAMsg\_s SwiOTAMsg
- typedef void(\* tFNASwiOTAMsg )(SwiOTAMsg \*pSwiOTAMsg)
- typedef void(\* tFNNewGPS )(double dLongitude, double dLatitude, BYTE session\_status, ULONG pos\_src)
- typedef void(\* tFNNewRMTransferStatistics )(QmiCbkWdsStatisticsIndState \*pMsg)
- typedef void(\* tFNDHCPv4ClientLeaseStatus )(BYTE instance, WdsDHCPv4ClientLeaseInd \*pMsg)
- typedef void(\* tFNSetCradleMount )(QmiCbkLocCradleMountInd \*pSetLocCradleMount)
- typedef void(\* tFNSetEventTimeSync )(QmiCbkLocEventTimeSyncInd \*pSetLocEventTimeSync)
- typedef void(\* tFNInjectTimeStatus )(QmiCbkLocInjectTimeInd \*pLocInjectTime)
- typedef struct accelAcceptReady\_s accelAcceptReady
- typedef struct gyroAcceptReady\_s gyroAcceptReady
- typedef struct  
accelTempAcceptReady\_s accelTempAcceptReady
- typedef struct  
gyroTempAcceptReady\_s gyroTempAcceptReady
- typedef void(\* tFNSensorStreaming )(QmiCbkLocSensorStreamingInd \*pLocSensorStream)
- typedef void(\* tFNInjectSensorData )(QmiCbkLocInjectSensorDataInd \*pLocInjectSensorData)
- typedef struct precisionDilution\_s precisionDilution
- typedef struct gpsTime\_s gpsTime
- typedef struct sensorDataUsage\_s sensorDataUsage
- typedef struct svUsedforFix\_s svUsedforFix
- typedef void(\* tFNEventPosition )(QmiCbkLocPositionReportInd \*pLocPositionReport)
- typedef void(\* tFNOpMode )(ULONG mode)
- typedef void(\* tFNImsaRegStatus )(imsaRegStatusInfo \*pImsaRegStatusInfo)
- typedef void(\* tFNImsaSvcStatus )(imsaSvcStatusInfo \*pImsaSvcStatusInfo)
- typedef void(\* tFNImsaRatStatus )(imsaRatStatusInfo \*pImsaRatStatusInfo)

- typedef void(\* tFNImsaPdpStatus )(imsaPdpStatusInfo \*pImsaPdpStatusInfo)
- typedef void(\* tFNGnssSvInfo )(gnssSvInfoNotification \*pGnssSvInfoNotification)
- typedef void(\* tFNDelAssistData )(delAssistDataStatus \*pAssistDataNotification)
- typedef void(\* tFNASwiLTECphyCalInfo )(QmiCbkNasLTECphyCalInfo \*pQmiCbkNasLTECphyCalInfo)
- typedef void(\* tFNRankIndicator )(RankIndicatorInd \*pRankIndicatorInd)
- typedef void(\* tFNInjectUTCTime )(QmiCbkLocInjectUTCTimeInd \*pInjectUTCTimeNotification)
- typedef void(\* tFNInjectPosition )(QmiCbkLocInjectPositionInd \*pInjectPositionNotification)
- typedef void(\* tFNCbkUimSlotStatusChangeInd )(UIMSlotStatusChangeInfo \*pQmiCbkUimSlotStatusChangeInd)
- typedef void(\* tFNSetEngineState )(QmiCbkLocEngineStateInd \*pSetLocEngineState)
- typedef struct  
    \_getResetInfoNotification ResetInfoNotification
- typedef void(\* tFNResetInfo )(ResetInfoNotification \*pResetInfoNotification)
- typedef void(\* tFNMitlLvIRpt )(QmiCbkTmdMitlLvIRptInd \*pSetLocCradleMount)
- typedef void(\* tFNSetExtPowerConfig )(QmiCbkLocSetExtPowerConfigInd \*pSetExtConfigIndStatus)

## Enumerations

- enum eQaQMIService {  
    eQA\_QMI\_SVC\_WDS = 0x01,  
    eQA\_QMI\_SVC\_NAS = 0x03,  
    eQA\_QMI\_SVC\_NA = 0xFF }
- enum SMSEventType {  
    SMS\_EVENT\_MT\_MESSAGE = 0x01,  
    SMS\_EVENT\_TRANSFER\_ROUTE\_MT\_MESSAGE = 0x02,  
    SMS\_EVENT\_MESSAGE\_MODE = 0x04,  
    SMS\_EVENT\_ETWS = 0x08,  
    SMS\_EVENT\_ETWS\_PLMN = 0x10,  
    SMS\_EVENT\_SMSC\_ADDRESS = 0x20,  
    SMS\_EVENT\_SMS\_ON\_IMS = 0x40 }
- enum device\_state\_enum {  
    DEVICE\_STATE\_DISCONNECTED,  
    DEVICE\_STATE\_READY,  
    DEVICE\_STATE\_BOOT }

## Functions

- ULONG SLQSSetSessionStateCallback (tFNSLQSSessionState pCallback)
- ULONG SLQSSetWdsEventCallback (tFNSLQSWDSEvent pCallback, BYTE interval, BYTE instanceid, BYTE ipfamily)
- ULONG SLQSSetWdsTransferStatisticCallback (tFNSLQSWDSEvent pXferStatsCb, BYTE interval, BYTE instanceid, BYTE ipfamily)
- ULONG iSLQSSetWdsFirstInstEventCallback (tFNSLQSWDSEvent pCallback)
- ULONG iSLQSSetWdsSecondInstEventCallback (tFNSLQSWDSEvent pCallback)
- ULONG iSLQSSetWdsThirdInstEventCallback (tFNSLQSWDSEvent pCallback)
- ULONG iSLQSSetWdsXferStatsFirstInstCallback (tFNSLQSWDSEvent pCallback)
- ULONG iSLQSSetWdsXferStatsSecondInstCallback (tFNSLQSWDSEvent pCallback)
- ULONG SetPowerCallback (tFNPower pCallback)
- ULONG SetActivationStatusCallback (tFNActivationStatus pCallback)
- ULONG SetMobileIPStatusCallback (tFNMobileIPStatus pCallback)
- ULONG SetRoamingIndicatorCallback (tFNRoamingIndicator pCallback)
- ULONG SetDataCapabilitiesCallback (tFNDataCapabilities pCallback)
- ULONG SetSignalStrengthCallback (tFNSignalStrength pCallback, BYTE thresholdsSize, INT8 \*p-Thresholds)
- ULONG iSetSignalStrengthCallback (tFNSignalStrength pCallback)

- [ULONG SetRFInfoCallback](#) ([tFNRInfo](#) pCallback)
- [ULONG SetLURejectCallback](#) ([tFNLURReject](#) pCallback)
- [ULONG SetNewSMSCallback](#) ([tFNNewSMS](#) pCallback)
- [ULONG SLQSSetSMSEventCallback](#) ([tFNSMSEvents](#) pCallback)
- [ULONG SetNMEACallback](#) ([tFNNewNMEA](#) pCallback)
- [ULONG SetPDSSStateCallback](#) ([tFNPDSState](#) pCallback)
- [ULONG SetCATEventCallback](#) ([tFNCATEvent](#) pCallback, [ULONG](#) eventMask, [ULONG](#) \*pErrorMask)
- [ULONG iSetCATEventCallback](#) ([tFNCATEvent](#) pCallback)
- [ULONG SetDeviceStateChangeCbk](#) ([tFNDeviceStateChange](#) pCallback)
- [ULONG SetNetChangeCbk](#) ([BYTE](#) instance, [tFNNet](#) pCallback, [ULONG](#) loMark, [ULONG](#) hiMark, [ULONG](#) period)
- [ULONG SetFwDidCompletionCbk](#) ([tFNFwDidCompletion](#) pCallback)
- [ULONG SetSLQSOMADMAAlertCallback](#) ([tFNSLQSOMADMAAlert](#) pCallback)
- [ULONG SetSLQSOMADMAAlertCallbackExt](#) ([tFNSLQSOMADMAAlert](#) pCallback)
- [ULONG SetOMADMStateCallback](#) ([tFNOMADMState](#) pCallback)
- [ULONG SLQSSetServingSystemCallback](#) ([tFNServingSystem](#) pCallback)
- [ULONG SLQSSetBandPreferenceCbk](#) ([tFNBandPreference](#) pCallback)
- [ULONG SetUSSDReleaseCallback](#) ([tFNUSSDRelease](#) pCallback)
- [ULONG SetUSSDNotificationCallback](#) ([tFNUSSDNotification](#) pCallback)
- [ULONG SLQSSetSignalStrengthsCallback](#) ([tFNSLQSSignalStrengths](#) pCallback, struct [SLQSSignalStrengthsIndReq](#) \*pSLQSSignalStrengthsIndReq)
- [ULONG iSLQSSetSignalStrengthsCallback](#) ([tFNSLQSSignalStrengths](#) pCallback)
- [ULONG SLQSVoiceSetSUPSNotificationCallback](#) ([tFNSUPSNotification](#) pCallback)
- [ULONG SLQSSetSDKTerminatedCallback](#) ([tFNSDKTerminated](#) pCallback)
- [ULONG SLQSVoiceSetAllCallStatusCallBack](#) ([tFNAIICallStatus](#) pCallback)
- [ULONG SLQSSetTransLayerInfoCallback](#) ([tFNtransLayerInfo](#) pCallback)
- [ULONG SLQSSetTransNWRegInfoCallback](#) ([tFNtransNWRegInfo](#) pCallback)
- [ULONG SLQSSetSysSelectionPrefCallBack](#) ([tFNSysSelectionPref](#) pCallback)
- [ULONG SLQSUIMSetRefreshCallBack](#) ([tFNUIMRefresh](#) pCallback)
- [ULONG SLQSUIMSetStatusChangeCallBack](#) ([tFNUIMStatusChangeInfo](#) pCallback)
- [ULONG SLQSVoiceSetPrivacyChangeCallBack](#) ([tFNPrivacyChange](#) pCallback)
- [ULONG SLQSVoiceSetDTMFEventCallBack](#) ([tFNDTMFEvent](#) pCallback)
- [ULONG SLQSVoiceSetSUPSCallBack](#) ([tFNSUPSInfo](#) pCallback)
- [ULONG SLQSNasSysInfoCallBack](#) ([tFNSysInfo](#) pCallback)
- [ULONG SLQSNasNetworkTimeCallBack](#) ([tFNNetworkTime](#) pCallback)
- [ULONG SLQSWmsMemoryFullCallBack](#) ([tFNMemoryFull](#) pCallback)
- [ULONG SLQSVoiceSetOTASPStatusCallBack](#) ([tFNOTASPStatus](#) pCallback)
- [ULONG SLQSVoiceInfoRecCallback](#) ([tFNInfoRec](#) pCallback)
- [ULONG SLQSWmsMessageWaitingCallBack](#) ([tFNMessageWaiting](#) pCallback)
- [ULONG SLQSSetQosEventCallback](#) ([BYTE](#) instance, [tFNSLQSQOSEvent](#) pCallback)
- [ULONG SLQSSetQosStatusCallback](#) ([BYTE](#) instance, [tFNQosStatus](#) pCallback)
- [ULONG SLQSSetQosNWStatusCallback](#) ([tFNQosNWStatus](#) pCallback)
- [ULONG SLQSSetQosPriEventCallback](#) ([tFNQosPriEvent](#) pCallback)
- [ULONG SLQSNasSigInfoCallBack](#) ([tFNSigInfo](#) pCallback, [sigInfo](#) \*pSigInfo)
- [ULONG SLQSSetModemTempCallback](#) ([tFNModemTempInfo](#) pCallback)
- [ULONG SLQSSetPacketSrvStatusCallback](#) ([tFNPacketSrvState](#) pCallback)
- [ULONG SLQSSetSwtHDPersCallback](#) ([tFNHDRPersonality](#) pCallback)
- [ULONG SLQSSetSIPConfigCallback](#) ([tFNImSIPConfig](#) pCallback)
- [ULONG SLQSSetRegMgrConfigCallback](#) ([tFNImRegMgrConfig](#) pCallback)
- [ULONG SLQSSetIMSSMSConfigCallback](#) ([tFNImSMSConfig](#) pCallback)
- [ULONG SLQSSetIMSUserConfigCallback](#) ([tFNImUserConfig](#) pCallback)
- [ULONG SLQSSetIMSVoIPConfigCallback](#) ([tFNImVoIPConfig](#) pCallback)
- [ULONG SetUSSDNoWaitIndicationCallback](#) ([tFNUSSDNoWaitIndication](#) pCallback)
- [ULONG SLQSSetDUNCallInfoCallback](#) ([BYTE](#) StatsPeriod, [tFNDUNCallInfo](#) pCallback)
- [ULONG iSLQSSetDUNCallInfoCallback](#) ([tFNDUNCallInfo](#) pCallback)

- [ULONG SLQSSetDataSystemStatusCallback](#) (tFNDataSysStatus pCallback)
- [ULONG SLQSWmsAsyncRawSendCallBack](#) (tFNAsyncRawSend pCallback)
- [ULONG SLQSNasSwiOTAMessageCallback](#) (NasSwiIndReg \*req, tFNASwiOTAMsg pCallback)
- [ULONG SetGPSCallback](#) (tFNNewGPS pCallback)
- [ULONG SetRMTransferStatisticsCallback](#) (tFNNewRMTransferStatistics pCallback)
- [ULONG SLQSSetDHCPv4ClientLeaseStatusCallback](#) (BYTE instance, tFNDHCPv4ClientLeaseStatus p-Callback)
- [ULONG SetLocCradleMountCallback](#) (tFNSetCradleMount pCallback)
- [ULONG SetLocEventTimeSyncCallback](#) (tFNSetEventTimeSync pCallback)
- [ULONG SetLocInjectTimeCallback](#) (tFNInjectTimeStatus pCallback)
- [ULONG SetLocSensorStreamingCallback](#) (tFNSensorStreaming pCallback)
- [ULONG SetLocInjectSensorDataCallback](#) (tFNInjectSensorData pCallback)
- [ULONG SetLocEventPositionCallback](#) (tFNEventPosition pCallback)
- [ULONG SetLocOpModeCallback](#) (tFNOpMode pCallback)
- [ULONG SLQSSetIMSARegStatusCallback](#) (tFNImsaRegStatus pCallback)
- [ULONG SLQSSetIMSASvcStatusCallback](#) (tFNImsaSvcStatus pCallback)
- [ULONG SLQSSetIMSARatStatusCallback](#) (tFNImsaRatStatus pCallback)
- [ULONG SLQSSetIMSAPdpStatusCallback](#) (tFNImsaPdpStatus pCallback)
- [ULONG SLQSNasSigInfo2CallBack](#) (tFNSigInfo pCallback, [setSignalStrengthInfo](#) \*pSigInfo2)
- [ULONG SetLocGnssSvInfoCallback](#) (tFNGnssSvInfo pCallback)
- [ULONG SetLocDeleteAssistDataCallback](#) (tFNDeIAssistData pCallback)
- [ULONG SetNasLTECphyCaIndCallback](#) (tFNASwiLTECphyCalInfo pCallback)
- [ULONG SetRankIndicatorCallback](#) (tFNRankIndicator pCallback)
- [ULONG SLQSSetLocInjectUTCTimeCallback](#) (tFNInjectUTCTime pCallback)
- [ULONG SLQSSetLocInjectPositionCallback](#) (tFNInjectPosition pCallback)
- [ULONG SetUimSlotStatusChangeCallback](#) (tFNCbkUimSlotStatusChangeInd pCallback)
- [ULONG SetLocEngineStateCallback](#) (tFNSetEngineState pCallback)
- [ULONG SLQSSetSwiGetResetInfoCallback](#) (tFNResetInfo pCallback)
- [ULONG SLQSTmdMitigationLvlRptCallback](#) (TmdMitigationLvlIndReq \*req, tFNMitLvlRpt pCallback)
- [ULONG SetLocSetExtPowerConfigCallback](#) (tFNSetExtPowerConfig pCallback)

### 9.11.1 Detailed Description

Callback Service API function prototypes.

### 9.11.2 Macro Definition Documentation

9.11.2.1 `#define CBK_DISABLE_EVENT 0x00`

9.11.2.2 `#define CBK_ENABLE_EVENT 0x01`

9.11.2.3 `#define CBK_NOCHANGE 0xFF`

9.11.2.4 `#define Deregister_Event 0x00`

9.11.2.5 `#define Deregister_Srv 0x00`

9.11.2.6 `#define DHCP_MAX_NUM_OPTIONS 30`

9.11.2.7 `#define DHCP_OPTION_DATA_BUF_SIZE 2048 /* current max size of raw message in SDK process is 2048 */`

9.11.2.8 `#define EVENT_MASK_CARD 0x00000001`

9.11.2.9 `#define EVENT_MASK_DEREGISTER_ALL 0x00000000`

9.11.2.10 `#define EVENT_MASK_PHY_SLOT_STATUS 0x00000010`

9.11.2.11 `#define FIRST_INSTANCE 0x00`

9.11.2.12 `#define INVALID_INSTACNE 0x08`

9.11.2.13 `#define IPV4 4`

9.11.2.14 `#define IPV4V6 7`

9.11.2.15 `#define IPV6 6`

9.11.2.16 `#define LOC_EVENT_MASK_ENG_STATE 0x00000080`

9.11.2.17 `#define LOC_EVENT_MASK_GNSS_SV_INFO 0x00000002`

9.11.2.18 `#define LOC_EVENT_MASK_INJECT_TIME 0x00000010`

9.11.2.19 `#define LOC_EVENT_MASK_SENSOR_STREAM 0x00000400`

9.11.2.20 `#define LOC_EVENT_MASK_TIME_SYNC 0x00000800`

9.11.2.21 `#define LOC_EVENT_POSITION_REPORT 0x00000001`

9.11.2.22 `#define MAX_MITIGATION_DEV_ID_LEN 255`

9.11.2.23 `#define MAX_NO_OF_APPLICATIONS 10`

9.11.2.24 `#define MAX_NO_OF_CALLS 20`

9.11.2.25 `#define MAX_NO_OF_FILES 255`

9.11.2.26 `#define MAX_NO_OF_SLOTS 5`

9.11.2.27 `#define MAX_NO_OF_UUSINFO 20`

9.11.2.28 `#define MAX_PATH_LENGTH 255`

9.11.2.29 `#define MAX_RADIO_INTERFACE_LIST 255`

9.11.2.30 `#define MAXUSSDLENGTH 182`

9.11.2.31 `#define NAS_SRV 0x02`

9.11.2.32 `#define NUM_OF_SET 0xFF`

9.11.2.33 `#define PDS_SRV 0x04`

9.11.2.34 `#define QMI_ETWS_MAX_PAYLOAD_LENGTH 1254 /* Qualcomm defined max */`

9.11.2.35 `#define QMI_MAX_VOICE_NUMBER_LENGTH 81`

9.11.2.36 `#define QMI_WMS_MAX_PAYLOAD_LENGTH 256`

9.11.2.37 `#define REGISTER_EVENT 0x01`

9.11.2.38 `#define REGISTER_SRV 0x01`

9.11.2.39 `#define SECOND_INSTANCE 0x01`

9.11.2.40 `#define SIGSTRENGTH_THRESHOLD_ARR_SZ 5`

9.11.2.41 `#define THIRD_INSTANCE 0x02`

9.11.2.42 `#define USSD_DCS_8BIT 0x02 /* 8-bit coding scheme */`

9.11.2.43 `#define USSD_DCS_ASCII 0x01 /* ASCII coding scheme */`

9.11.2.44 `#define USSD_DCS_UCS2 0x03 /* UCS2 coding scheme */`

9.11.2.45 `#define VOICE_SRV 0x08`

9.11.2.46 `#define WDS_SRV 0x01`

### 9.11.3 Typedef Documentation

#### 9.11.3.1 `typedef struct accelAcceptReady_s accelAcceptReady`

This structure contains Accelerometer Accept Ready Info

Parameters

<i>injectEnable</i>	<ul style="list-style-type: none"> <li>GNSS location engine is ready to accept data from sensor.</li> <li>Values</li> <li>0x01 - Ready to accept sensor data</li> <li>0x00 - Not ready to accept sensor data</li> </ul>
<i>samplesPerBatch</i>	<ul style="list-style-type: none"> <li>number of samples per batch the GNSS location engine is to receive.</li> <li><math>\text{samplingFrequency} = \text{samplesPerBatch} * \text{batchesPerSecond}</math></li> <li><code>samplesPerBatch</code> must be a nonzero positive value.</li> </ul>
<i>batchPerSec</i>	<ul style="list-style-type: none"> <li>LTE NAS version minor</li> <li>Number of sensor-data batches the GNSS location engine is to receive per second.</li> <li><code>BatchesPerSecond</code> must be a nonzero positive value.</li> </ul>

#### 9.11.3.2 `typedef struct accelTempAcceptReady_s accelTempAcceptReady`

This structure contains Accelerometer Temperature Accept Ready Info

## Parameters

<i>injectEnable</i>	<ul style="list-style-type: none"> <li>GNSS location engine is ready to accept data from sensor.</li> <li>Values</li> <li>0x01 - Ready to accept sensor data</li> <li>0x00 - Not ready to accept sensor data</li> </ul>
<i>samplesPerBatch</i>	<ul style="list-style-type: none"> <li>number of samples per batch the GNSS location engine is to receive.</li> <li>samplingFrequency = samplesPerBatch * batchesPerSecond</li> <li>samplesPerBatch must be a nonzero positive value.</li> </ul>
<i>batchPerSec</i>	<ul style="list-style-type: none"> <li>LTE NAS version minor</li> <li>Number of sensor-data batches the GNSS location engine is to receive per second.</li> <li>BatchesPerSecond must be a nonzero positive value.</li> </ul>

## 9.11.3.3 typedef enum device\_state\_enum eDevState

Device State enumeration

- See [device\\_state\\_enum](#) for more details

## 9.11.3.4 typedef enum SMSEventType eSMSEventType

This enumeration defines the different type of SMS events that are received

- See [SMSEventType](#) for more details

## 9.11.3.5 typedef struct gpsTime\_s gpsTime

This structure contains GPS Time info.

## Parameters

<i>gpsWeek</i>	<ul style="list-style-type: none"> <li>Current GPS week as calculated from midnight, Jan. 6, 1980.</li> <li>Units - Weeks</li> </ul>
----------------	--



<i>gpsTimeOf-WeekMs</i>	<ul style="list-style-type: none"> <li>• Amount of time into the current GPS week.</li> <li>• Units - Milliseconds</li> </ul>
-------------------------	---

#### 9.11.3.6 typedef struct gyroAcceptReady\_s gyroAcceptReady

This structure contains Gyroscope Accept Ready Info

##### Parameters

<i>injectEnable</i>	<ul style="list-style-type: none"> <li>• GNSS location engine is ready to accept data from sensor.</li> <li>• Values</li> <li>• 0x01 - Ready to accept sensor data</li> <li>• 0x00 - Not ready to accept sensor data</li> </ul>
<i>samplesPer-Batch</i>	<ul style="list-style-type: none"> <li>• number of samples per batch the GNSS location engine is to receive.</li> <li>• <math>\text{samplingFrequency} = \text{samplesPerBatch} * \text{batchesPerSecond}</math></li> <li>• samplesPerBatch must be a nonzero positive value.</li> </ul>
<i>batchPerSec</i>	<ul style="list-style-type: none"> <li>• LTE NAS version minor</li> <li>• Number of sensor-data batches the GNSS location engine is to receive per second.</li> <li>• BatchesPerSecond must be a nonzero positive value.</li> </ul>

#### 9.11.3.7 typedef struct gyroTempAcceptReady\_s gyroTempAcceptReady

This structure contains Gyroscope Temperature Accept Ready Info

## Parameters

<i>injectEnable</i>	<ul style="list-style-type: none"> <li>GNSS location engine is ready to accept data from sensor.</li> <li>Values</li> <li>0x01 - Ready to accept sensor data</li> <li>0x00 - Not ready to accept sensor data</li> </ul>
<i>samplesPerBatch</i>	<ul style="list-style-type: none"> <li>number of samples per batch the GNSS location engine is to receive.</li> <li><math>\text{samplingFrequency} = \text{samplesPerBatch} * \text{batchesPerSecond}</math></li> <li><i>samplesPerBatch</i> must be a nonzero positive value.</li> </ul>
<i>batchPerSec</i>	<ul style="list-style-type: none"> <li>LTE NAS version minor</li> <li>Number of sensor-data batches the GNSS location engine is to receive per second.</li> <li><i>BatchesPerSecond</i> must be a nonzero positive value.</li> </ul>

9.11.3.8 typedef struct **LteNasReleaseInfo\_s** **LteNasReleaseInfo**

This structure contains LTE Nas Release Information

## Parameters

<i>nas_release</i>	<ul style="list-style-type: none"> <li>LTE NAS release</li> </ul>
<i>nas_major</i>	<ul style="list-style-type: none"> <li>LTE NAS version major</li> </ul>
<i>nas_minor</i>	<ul style="list-style-type: none"> <li>LTE NAS version minor</li> </ul>

9.11.3.9 typedef struct **\_modemTempNotification** **modemTempNotification**

Contains the parameters passed for `SLQSSetModemTempCallback` by the device.

## Parameters

<i>ModemTemp-State</i>	<ul style="list-style-type: none"> <li>• provides the temperature state of the modem</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - normal</li> <li>– 2 - high(warning)</li> <li>– 3 - high(critical)</li> <li>– 4 - low(critical)</li> </ul> </li> </ul>
<i>Modem-Temperature</i>	<ul style="list-style-type: none"> <li>• provides the temperature of the modem</li> </ul>

## Note

None

## 9.11.3.10 typedef struct \_packetSrvStatus packetSrvStatus

Contains the parameters passed for SLQSSetPacketSrvStatusCallback by the device.

## Parameters

<i>pQmiInterface-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaQmiInterfaceInfo</a> for more information</li> </ul>
<i>connStatus</i>	<ul style="list-style-type: none"> <li>• Current Link Status <ul style="list-style-type: none"> <li>– 1 - Disconnected</li> <li>– 2 - Connected</li> <li>– 3 - Suspended</li> <li>– 4 - Authenticating</li> </ul> </li> </ul>
<i>reconfigReqd</i>	<ul style="list-style-type: none"> <li>• Indicates if the network interface on the host needs to be reconfigured <ul style="list-style-type: none"> <li>– 0 - No need to reconfigure</li> <li>– 1 - Reconfiguration required</li> </ul> </li> </ul>

<i>sessionEndReason</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Call End Reason, 0xFFFF means invalid value</li> </ul>
<i>verboseSessnEndReasonType</i>	<ul style="list-style-type: none"> <li>• Call End Reason Type <ul style="list-style-type: none"> <li>– 0 - Unspecified</li> <li>– 1 - Mobile IP</li> <li>– 2 - Internal</li> <li>– 3 - Call Manager defined</li> <li>– 6 - 3GPP Specification defined</li> <li>– 7 - PPP</li> <li>– 8 - EHRPD</li> <li>– 9 - IPv6</li> <li>– 0xFFFF - invalid value</li> </ul> </li> </ul>
<i>verboseSessnEndReason</i>	<ul style="list-style-type: none"> <li>• See <a href="#">qaGobiApiTableCallEndReasons.h</a> for verbose Call End Reason. The values depend on verboseSessnEndReasonType parameter 0xFFFF means invalid value</li> </ul>
<i>ipFamily</i>	<ul style="list-style-type: none"> <li>• IP Family of the packet data connection <ul style="list-style-type: none"> <li>– 4 - IPv4</li> <li>– 6 - IPv6</li> <li>– 0xFF - invalid value</li> </ul> </li> </ul>
<i>techName</i>	<ul style="list-style-type: none"> <li>• Technology name of the packet data connection. <ul style="list-style-type: none"> <li>– 32767 - CDMA</li> <li>– 32764 - UMTS</li> <li>– 30592 - EPC</li> <li>– 30590 - EMBMS</li> <li>– 30584 - Modem Link Local</li> <li>– 0xFFFF - invalid value EPC is a logical interface to support LTE/eHRPD handoff. Modem Link is an interface for transferring data between entities on the AP and modem.</li> </ul> </li> </ul>
<i>bearerID</i>	<ul style="list-style-type: none"> <li>• Bearer ID (3GPP) or RLP ID (3GPP2) of the packet data connection 0xFF means invalid value</li> </ul>

**Note**

Any parameter not returned by the device is returned as its maximum unsigned value by the callback.

#### 9.11.3.11 `typedef struct precisionDilution_s precisionDilution`

This structure contains Dilution of precision associated with this position.

## Parameters

<i>PDOP</i>	<ul style="list-style-type: none"> <li>• Position dilution of precision.</li> <li>• Range - 1 (highest accuracy) to 50 (lowest accuracy)</li> <li>• PDOP = square root of (Square of HDOP + Square of VDOP2 )</li> </ul>
<i>HDOP</i>	<ul style="list-style-type: none"> <li>• Horizontal dilution of precision.</li> <li>• Range - 1 (highest accuracy) to 50 (lowest accuracy)</li> </ul>
<i>VDOP</i>	<ul style="list-style-type: none"> <li>• Vertical dilution of precision.</li> <li>• Range- 1 (highest accuracy) to 50 (lowest accuracy)</li> </ul>

9.11.3.12 `typedef struct _getResetInfoNotification ResetInfoNotification`

Contains the parameters passed for SLQSSetSwiGetResetInfoCallback by the device.

## Parameters

<i>type</i>	<ul style="list-style-type: none"> <li>• type of reset or power down, possible values listed below: <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - warm</li> <li>– 2 - hard</li> <li>– 3 - crash</li> <li>– 4 - power down</li> </ul> </li> </ul>
<i>source</i>	<ul style="list-style-type: none"> <li>• entity which initiated the reset or power down, possible values listed below: <ul style="list-style-type: none"> <li>– 0 - unknown</li> <li>– 1 - user requested</li> <li>– 2 - hardware switch</li> <li>– 3 - temperature critical</li> <li>– 4 - voltage critical</li> <li>– 5 - configuration update</li> <li>– 6 - LWM2M</li> <li>– 7 - OMA-DM</li> <li>– 8 - FOTA</li> </ul> </li> </ul>

## Note

None

#### 9.11.3.13 `typedef struct sensorDataUsage_s sensorDataUsage`

This structure contains Sensor Data Usage info.

## Parameters

<i>usageMask</i>	<ul style="list-style-type: none"> <li>Specifies which sensors were used in calculating the position in the position report.</li> </ul>
------------------	---

- Value

- 0x00000001 - Accelerometer used
- 0x00000002 - Gyroscope used

## Parameters

<i>aidingIndicator-Mask</i>	
-----------------------------	--

- Specifies which results were aided by sensors.

- Value

- 0x00000001 - AIDED\_HEADING
- 0x00000002 - AIDED\_SPEED
- 0x00000004 - AIDED\_POSITION
- 0x00000008 - AIDED\_VELOCITY

9.11.3.14 `typedef union sessionInfo sessionInformation`

This union `sessionInfo` consist of `omaDmFotaTlv`, `omaDmConfigTlv` and `omaDmNotificationsTlv`, out of which one will be unpacked against `pEventFields`.

9.11.3.15 `typedef union sessionInfoExt sessionInformationExt`

This union `sessionInfo` consist of `omaDmFotaTlv` and `omaDmConfigTlv`, out of which one will be unpacked against `pEventFields`.

9.11.3.16 `typedef struct SMSAsyncRawSend_s SMSAsyncRawSend`

This structure contains SMS parameters

## Parameters

<i>sendStatus</i>	<ul style="list-style-type: none"> <li>Send Status</li> <li>Values:             <ul style="list-style-type: none"> <li>QMI_ERR_NONE – No error in the request</li> <li>QMI_ERR_CAUSE_CODE - SMS cause code</li> <li>QMI_ERR_MESSAGE_DELIVERY_FAILURE - Message could not be delivered</li> <li>QMI_ERR_NO_MEMORY - Device could not allocate memory to formulate a response</li> </ul> </li> </ul>
-------------------	--



<i>messageID</i>	<ul style="list-style-type: none"> <li>• Unique ID assigned by WMS for non-retry messages.</li> </ul>
<i>causeCode</i>	<ul style="list-style-type: none"> <li>• WMS cause code</li> </ul>
<i>errorClass</i>	<ul style="list-style-type: none"> <li>• Error Class</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - ERROR_CLASS_TEMPORARY</li> <li>– 0x01 - ERROR_CLASS_PERMANENT</li> </ul> </li> </ul>
<i>RPCause</i>	<ul style="list-style-type: none"> <li>• GW RP cause</li> </ul>
<i>TPCause</i>	<ul style="list-style-type: none"> <li>• GW TP Cause</li> </ul>
<i>msgDelFailure-Type</i>	<ul style="list-style-type: none"> <li>• Message delivery failure type</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - WMS_MESSAGE_DELIVERY_FAILURE_TEMPORARY</li> <li>– 0x01 - WMS_MESSAGE_DELIVERY_FAILURE_PERMANENT</li> </ul> </li> </ul>
<i>msgDelFailure-Cause</i>	<ul style="list-style-type: none"> <li>• Message delivery failure cause</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - WMS_MESSAGE_BLOCKED_DUE_TO_CALL_CONTROL</li> </ul> </li> </ul>
<i>alphaIDLen</i>	<ul style="list-style-type: none"> <li>• Number of sets of the pAlphaID</li> </ul>
<i>pAlphaID</i>	<ul style="list-style-type: none"> <li>• Alpha ID</li> </ul>
<i>userData</i>	<ul style="list-style-type: none"> <li>• Identifies the request associated with this indication.</li> </ul>

#### 9.11.3.17 typedef struct **SMSCAddress** **SMSCAddressInfo**

This structure holds SMSC information

## Parameters

<i>length</i>	<ul style="list-style-type: none"> <li>• Number of sets of following element</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>• SMSC address</li> </ul>

9.11.3.18 `typedef struct SMSEtwsMessage SMSEtwsMessageInfo`

This structure holds information related earthquake and Tsunami warning system

## Parameters

<i>notificationType</i>	<ul style="list-style-type: none"> <li>• Message mode 0x00 - Primary 0x01 - Secondary GSM 0x02 - Secondary UMTS</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>• Number of sets of following elements</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>• Raw message data</li> </ul>

9.11.3.19 `typedef struct SMSEtwsPlmn SMSEtwsPlmnInfo`

This structure holds information related ETWS PLMN

## Parameters

<i>mobileCountry-Code</i>	<ul style="list-style-type: none"> <li>• 16 bit representation of MCC value range : 0 -999</li> </ul>
<i>mobileNetwork-Code</i>	<ul style="list-style-type: none"> <li>• 16 bit representation of MNC value range : 0 -999</li> </ul>

9.11.3.20 `typedef struct SMSEventInfo_s SMSEventInfo`

This structure will hold the information related to received SMS events

## Parameters

<i>smsEventType</i>	<ul style="list-style-type: none"> <li>Type of the SMS events that are received. This is a bit map of <a href="#">SMSEventType</a>. Only the parameters (which follows) related to the events received would be filled, and the rest of the parameters would be NULL</li> </ul>
<i>pMTMessage-Info</i>	<ul style="list-style-type: none"> <li>pointer to the <a href="#">SMSMTMessageInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pTransferRoute-MTMessageInfo</i>	<ul style="list-style-type: none"> <li>pointer to the <a href="#">SMSTransferRouteMTMessageInfo</a> structure . NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pMessageMode-Info</i>	<ul style="list-style-type: none"> <li>pointer to the <a href="#">SMSMessageModeInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pEtwsMessage-Info</i>	<ul style="list-style-type: none"> <li>pointer to the <a href="#">SMSEtwsMessageInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pEtwsPlmnInfo</i>	<ul style="list-style-type: none"> <li>pointer to the <a href="#">SMSEtwsPlmnInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pSMSCAddress-Info</i>	<ul style="list-style-type: none"> <li>pointer to the <a href="#">SMSCAddressInfo</a> structure NULL, if this event is not present in the smsEventType parameter</li> </ul>
<i>pSMSOnIMSInfo</i>	<ul style="list-style-type: none"> <li>pointer to the <a href="#">SMSOnIMSInfo</a> structure NULL, if this event is not present in the smsEventType parameter Note: None</li> </ul>

## 9.11.3.21 typedef struct SMSMessageMode SMSMessageModeInfo

This structure holds information related to message mode

## Parameters

<i>messageMode</i>	<ul style="list-style-type: none"> <li>Message mode 0x00 - CDMA 0x01 - GW</li> </ul>
--------------------	--

## 9.11.3.22 typedef struct SMSMTMessage SMSMTMessageInfo

This structure holds information related to MT SMS

## Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>SMS message storage type for the new message</li> <li>0 - UIM 1 - NV</li> </ul>
<i>messageIndex</i>	<ul style="list-style-type: none"> <li>Index of the new message</li> </ul>

9.11.3.23 typedef struct **SMSONIMS** **SMSONIMSInfo**

This structure holds information related to message mode

## Parameters

<i>smsOnIMS</i>	<ul style="list-style-type: none"> <li>Indicates whether the message is received from IMS 0x00 - Message is not received from IMS 0x01 - Message is received from IMS 0x02-0xFF - Reserved Note: In multiple modem solutions, this TLV may be used to help the client determine with which modem to communicate. This TLV may not be supported on all implementations.</li> </ul>
-----------------	---

9.11.3.24 typedef struct **SMSTransferRouteMTMessage** **SMSTransferRouteMTMessageInfo**

This structure holds information related to transfer route MT SMS

## Parameters

<i>ackIndicator</i>	<ul style="list-style-type: none"> <li>Parameter to indicate if ACK must be sent by the control point 0x00 - Send ACK 0x01 - Do not send ACK</li> </ul>
<i>transactionID</i>	<ul style="list-style-type: none"> <li>Transaction ID of the message</li> </ul>
<i>format</i>	<ul style="list-style-type: none"> <li>Message format 0x00 - CDMA 0x02 - 0x05 - Reserved 0x06 - GW_PP 0x07 - GW_BC</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>Length of the raw message. This length should not exceed the maximum WMS payload length of 256 bytes</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>Raw message data</li> </ul>

9.11.3.25 typedef struct **svUsedforFix\_s** **svUsedforFix**

This structure contains SVs Used to Calculate the Fix.

## Parameters

<i>gnssSvUsedList_len</i>	<ul style="list-style-type: none"> <li>• Number of sets of gnssSvUsedList</li> </ul>
<i>pGnssSvUsedList</i>	<ul style="list-style-type: none"> <li>• Entry in the list contains the <a href="#">SV</a> ID of a satellite used for calculating this position report.</li> <li>• Following information is associated with each <a href="#">SV</a> ID: <ul style="list-style-type: none"> <li>– GPS - 1 to 32</li> <li>– SBAS - 33 to 64</li> <li>– GLONASS - 65 to 96</li> <li>– QZSS - 193 to 197</li> <li>– BDS - 201 to 237</li> </ul> </li> </ul>

## 9.11.3.26 typedef struct SwiOTAMsg\_s SwiOTAMsg

This structure contains OTA message

## Parameters

<i>type</i>	<ul style="list-style-type: none"> <li>• message type <ul style="list-style-type: none"> <li>– 0 - LTE ESM uplink</li> <li>– 1 - LTE ESM downlink</li> <li>– 2 - LTE EMM uplink</li> <li>– 3 - LTE EMM downlink</li> <li>– 4 - GSM/UMTS uplink</li> <li>– 5 - GSM/UMTS downlink</li> </ul> </li> </ul>
<i>data_len</i>	<ul style="list-style-type: none"> <li>• OTA Message Content Length</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>• OTA Message Content</li> </ul>
<i>pLteNasRelInfo</i>	<ul style="list-style-type: none"> <li>• LTE NAS Release Info</li> <li>• see <a href="#">LteNasReleaseInfo</a> for details</li> </ul>
<i>pTime</i>	<ul style="list-style-type: none"> <li>• Seconds in local time since Jan. 6th 1980 00:00:00 UTC</li> </ul>

## 9.11.3.27 typedef void(\* tFNActivationStatus)(ULONG activationStatus)

Activation status callback function.

## Parameters

<i>activationStatus</i>	<ul style="list-style-type: none"> <li>• Service Activation Code <ul style="list-style-type: none"> <li>– 0 - Service not activated</li> <li>– 1 - Service activated</li> <li>– 2 - Activation connecting</li> <li>– 3 - Activation connected</li> <li>– 4 - OTASP security authenticated</li> <li>– 5 - OTASP NAM downloaded</li> <li>– 6 - OTASP MDN downloaded</li> <li>– 7 - OTASP IMSI downloaded</li> <li>– 8 - OTASP PRL downloaded</li> <li>– 9 - OTASP SPC downloaded</li> <li>– 10 - OTASP settings committed</li> </ul> </li> </ul>
-------------------------	--

9.11.3.28 `typedef void(* tFNAllCallStatus)(voiceSetAllCallStatusCbInfo *pVoiceSetAllCallStatusCbInfo)`

Voice Call Status Callback function. This function pointer will be executed to process received Indication.

## Parameters

<i>pVoiceSetAll- CallStatusCb- Info</i>	<ul style="list-style-type: none"> <li>• Call back will populated memory pointed by this parameter when a call is originated, connected, or ended. See <a href="#">voiceSetAllCallStatusCbInfo</a> for more information.</li> </ul>
---	---

9.11.3.29 `typedef void(* tFNASwiLTECphyCalInfo)(QmiCbkNasLTECphyCalInfo *pQmiCbkNasLTECphyCalInfo)`

LTE CPHY CA message callback function.

## Parameters

<i>pQmiCbkNasLT- ECphyCalInfo[O- UT]</i>	<ul style="list-style-type: none"> <li>• Events related to NAS, see <a href="#">QmiCbkNasLTECphyCalInfo</a> for details.</li> </ul>
--	---

9.11.3.30 `typedef void(* tFNASwiOTAMsg)(SwiOTAMsg *pSwiOTAMsg)`

OTA message callback function.

## Parameters

<i>pSwiOTAMsg[O- UT]</i>	<ul style="list-style-type: none"> <li>• Events related to NAS, see <a href="#">SwiOTAMsg</a> for details</li> </ul>
------------------------------	--

9.11.3.31 `typedef void(* tFNAsyncRawSend)(SMSAsyncRawSend *pSMSAsyncRawSend)`

SMS event related callback function.

## Parameters

<i>pSMSEventInfo[OUT]</i>	<ul style="list-style-type: none"><li>• Events related to SMS, see <a href="#">SMSEventInfo</a> for details</li></ul>
---------------------------	---

9.11.3.32 `typedef void(* tFNBandPreference)(ULONGLONG band_pref)`

Band Preference Callback function



## Parameters

<i>pBandPref</i>	<p>- Bit mask representing the current band preference Bit position meanings:</p> <ul style="list-style-type: none"> <li>• 0 - BC0_A - Band Class 0, A-System</li> <li>• 1 - BC0_B - Band Class 0, B-System, Band Class 0 AB , GSM 850 Band</li> <li>• 2 - BC1 - Band Class 1, all blocks</li> <li>• 3 - BC2 - Band Class 2 place holder</li> <li>• 4 - BC3 - Band Class 3, A-System</li> <li>• 5 - BC4 - Band Class 4, all blocks</li> <li>• 6 - BC5 - Band Class 5, all blocks</li> <li>• 7 - GSM_DCS_1800 - GSM DCS band</li> <li>• 8 - GSM_EGSM_900 - GSM Extended GSM (E-GSM) band</li> <li>• 9 - GSM_PGSM_900 - GSM Primary GSM (P-GSM) band</li> <li>• 10 - BC6 - Band Class 6</li> <li>• 11 - BC7 - Band Class 7</li> <li>• 12 - BC8 - Band Class 8</li> <li>• 13 - BC9 - Band Class 9</li> <li>• 14 - BC10 - Band Class 10</li> <li>• 15 - BC11 - Band Class 11</li> <li>• 16 - GSM_450 - GSM 450 band</li> <li>• 17 - GSM_480 - GSM 480 band</li> <li>• 18 - GSM_750 - GSM 750 band</li> <li>• 19 - GSM_850 - GSM 850 band</li> <li>• 20 - GSM_RGSM_900 - GSM Railways GSM Band</li> <li>• 21 - GSM_PCS_1900 - GSM PCS band</li> <li>• 22 - WCDMA_I_IMT_2000 - WCDMA EUROPE JAPAN and CHINA IMT 2100 band</li> <li>• 23 - WCDMA_II_PCS_1900 - WCDMA US PCS 1900 band</li> <li>• 24 - WCDMA_III_1700 - WCDMA EUROPE and CHINA DCS 1800 band</li> <li>• 25 - WCDMA_IV_1700 - WCDMA US 1700 band</li> <li>• 26 - WCDMA_V_850 - WCDMA US 850 band</li> <li>• 27 - WCDMA_VI_800 - WCDMA JAPAN 800 band</li> <li>• 28 - BC12 - Band Class 12</li> <li>• 29 - BC14 - Band Class 14</li> <li>• 30 - RESERVED_2 - Reserved 2</li> <li>• 31 - BC15 - Band Class 15</li> <li>• 32 - 47 - Reserved</li> <li>• 48 - WCDMA_VII_2600 - WCDMA EUROPE 2600 band</li> <li>• 49 - WCDMA_VIII_900 - WCDMA EUROPE and JAPAN 900 band</li> <li>• 50 - WCDMA_IX_1700 - WCDMA JAPAN 1700 band</li> <li>• 51 to 55 - Reserved</li> </ul>
------------------	---

**Note**

Timeout: NA To set the band preference the API [SLQSSetBandPreference\(\)](#) should be used

**9.11.3.33** `typedef void(* tFNCATEvent)(ULONG eventID, ULONG eventLen, BYTE *pEventData)`

CAT event callback function.

**Parameters**

<i>eventID</i>	<ul style="list-style-type: none"> <li>• Event ID <ul style="list-style-type: none"> <li>– 16 - Display Text</li> <li>– 17 - Get In-Key</li> <li>– 18 - Get Input</li> <li>– 19 - Setup Menu</li> <li>– 20 - Select Item</li> <li>– 21 - Send SMS - Alpha Identifier</li> <li>– 22 - Setup Event List</li> <li>– 23 - Setup Idle Mode Text</li> <li>– 24 - Language Notification</li> <li>– 25 - Refresh</li> <li>– 26 - End Proactive Session</li> </ul> </li> </ul>
<i>eventLen</i>	<ul style="list-style-type: none"> <li>• Length of pData (in bytes)</li> </ul>
<i>pEventData</i>	<ul style="list-style-type: none"> <li>• Data specific to the CAT event ID See <a href="#">currentCatEvent</a> for details</li> </ul>

**Note**

Technology Supported: UMTS

**9.11.3.34** `typedef void(* tFNCbkUimSlotStatusChangeInd)(UIMSlotStatusChangeInfo *pQmiCbkUimSlotStatusChangeInd)`

Slot Status Change Notification callback.

**Parameters**

<i>pQmiCbkUimSlotStatusChangeInd</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMSlotStatusChangeInfo</a> for more information.</li> </ul>
--------------------------------------	---

**9.11.3.35** `typedef void(* tFNDataCapabilities)(BYTE dataCapsSize, BYTE *pDataCaps)`

Serving system data capabilities callback function.

## Parameters

<i>dataCapsSize</i>	<ul style="list-style-type: none"> <li>• Number of elements the data capability array contains</li> </ul>
<i>pDataCaps</i>	<ul style="list-style-type: none"> <li>• Data Capabilities Array. <ul style="list-style-type: none"> <li>– 1 - GPRS</li> <li>– 2 - EDGE</li> <li>– 3 - HSDPA</li> <li>– 4 - HSUPA</li> <li>– 5 - WCDMA</li> <li>– 6 - CDMA 1xRTT</li> <li>– 7 - CDMA 1xEV-DO Rev 0</li> <li>– 8 - CDMA 1xEV-DO Rev. A</li> <li>– 9 - GSM</li> <li>– 10 - EVDO Rev. B</li> <li>– 11 - LTE</li> <li>– 12 - HSDPA Plus</li> <li>– 13 - Dual Carrier HSDPA Plus</li> </ul> </li> </ul>

9.11.3.36 `typedef void(* tFNDataSysStatus)(CurrDataSysStat *pCurrDataSysStat)`

Data System Status callback.

## Parameters

<i>pCurrDataSys-Stat</i>	<ul style="list-style-type: none"> <li>• See <a href="#">CurrDataSysStat</a> for more information.</li> </ul>
--------------------------	---

9.11.3.37 `typedef void(* tFNDeIAssistData)(deIAssistDataStatus *pAssistDataNotification)`

Delete Assist Data Notification callback.

## Parameters

<i>pAssistData-Notification</i>	<ul style="list-style-type: none"> <li>• See <a href="#">deIAssistDataStatus</a> for more information.</li> </ul>
---------------------------------	---

9.11.3.38 `typedef void(* tFNDeviceStateChange)(eDevState device_state)`

Device State Change callback function prototype

## Parameters

<i>device_state</i>	<ul style="list-style-type: none"> <li>the current state of the device</li> </ul>
---------------------	---

## Note

Does not require communication with the device

**9.11.3.39** `typedef void(* tFNDHCPv4ClientLeaseStatus)(BYTE instance, WdsDHCPv4ClientLeaseInd *pMsg)`

DHCPv4 client lease status message callback function.

## Parameters

<i>pMsg[OUT]</i>	<ul style="list-style-type: none"> <li>Events related to DHCPv4 client lease, see <a href="#">WdsDHCPv4ClientLeaseInd</a> for details</li> </ul>
------------------	--

**9.11.3.40** `typedef void(* tFNDTMFEvent)(voiceDTMFEventInfo *pVoiceDTMFEventInfo)`

Preferred DTMF event indication callback.

## Parameters

<i>pVoiceDTMF-EventInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">voiceDTMFEventInfo</a> for more information.</li> </ul>
-----------------------------	--

**9.11.3.41** `typedef void(* tFNDUNCallInfo)(DUNCallInfoInd *pDUNCallInfo)`

DUN Call Info indication callback.

## Parameters

<i>pDUNCallInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">DUNCallInfoInd</a> for more information.</li> </ul>
---------------------	--

**9.11.3.42** `typedef void(* tFNEventPosition)(QmiCbkLocPositionReportInd *pLocPositionReport)`

**9.11.3.43** `typedef void(* tFNFwDldCompletion)(ULONG fwdld_completion_status)`

Firmware Download Completion callback function prototype

## Parameters

<i>error_code</i>	<ul style="list-style-type: none"> <li>error code returned from firmware download operation, the possible return values are listed below: <ul style="list-style-type: none"> <li>eQCWWAN_ERR_NONE - indicates firmware download/switching is successful</li> <li>eQCWWAN_ERR_SWIIM_FIRMWARE_NOT_DOWNLOADED - indicates no actual download takes place, this is the case of image switching stored on device</li> <li>eQCWWAN_ERR_SWIIM_FW_ENTER_DOWNLOAD_MODE - indicates modem enters firmware download mode, firmware flashing is going to be started.</li> <li>eQCWWAN_ERR_SWIIM_FW_FLASH_COMPLETE - indicates firmware flashing was complete, SDK is waiting for modem to reboot (can be more than one time), when modem is ready, SDK will send eQCWWAN_ERR_NONE to the host application.</li> </ul> </li> </ul>
-------------------	---

## Note

Does not require communication with the device

#### 9.11.3.44 `typedef void(* tFNGnssSvInfo)(gnssSvInfoNotification *pGnssSvInfoNotification)`

GNSS SVN Information Notification callback.

## Parameters

<i>pGnssSvInfoNotification</i>	<ul style="list-style-type: none"> <li>See <a href="#">gnssSvInfoNotification</a> for more information.</li> </ul>
--------------------------------	--

#### 9.11.3.45 `typedef void(* tFNHDRPersonality)(HDRPersonalityInd *pHDRPers)`

HDR Personality indication callback.

## Parameters

<i>pHDRPers</i>	<ul style="list-style-type: none"> <li>See <a href="#">HDRPersonalityInd</a> for more information.</li> </ul>
-----------------	---

## Note

Technology Supported: CDMA

#### 9.11.3.46 `typedef void(* tFNImsaPdpStatus)(imsaPdpStatusInfo *pImsaPdpStatusInfo)`

IMSA PDP status indication callback.

## Parameters

<i>plmsaPdp-StatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsaPdpStatusInfo</a> for more information.</li> </ul>
----------------------------	---

9.11.3.47 `typedef void( * tFNImsaRatStatus)(imsaRatStatusInfo *plmsaRatStatusInfo)`

IMSA RAT handover status indication callback.

## Parameters

<i>plmsaRatStatus-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsaRatStatusInfo</a> for more information.</li> </ul>
----------------------------	---

9.11.3.48 `typedef void( * tFNImsaRegStatus)(imsaRegStatusInfo *plmsaRegStatusInfo)`

IMSA Registration Status indication callback.

## Parameters

<i>plmsaReg-StatusInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsaRegStatusInfo</a> for more information.</li> </ul>
----------------------------	---

9.11.3.49 `typedef void( * tFNImsaSvcStatus)(imsaSvcStatusInfo *plmsaSvcStatusInfo)`

IMSA Service Status indication callback.

## Parameters

<i>plmsaSvcStatus-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsaSvcStatusInfo</a> for more information.</li> </ul>
----------------------------	---

9.11.3.50 `typedef void( * tFNImRegMgrConfig)(imsRegMgrConfigInfo *plmsRegMgrConfigInfo)`

IMS Reg Mgr Config indication callback.

## Parameters

<i>plmsRegMgr-ConfigInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsRegMgrConfigInfo</a> for more information.</li> </ul>
------------------------------	---

9.11.3.51 `typedef void( * tFNImSIPConfig)(imsSIPConfigInfo *plmsSIPConfigInfo)`

IMS SIP Config indication callback.

## Parameters

<i>plmsSIPConfig-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsSIPConfigInfo</a> for more information.</li> </ul>
---------------------------	--

9.11.3.52 `typedef void( * tFNImSMSConfig)(imsSMSConfigInfo *plmsSMSConfigInfo)`

IMS SMS Config indication callback.

## Parameters

<i>plmsSMSConfig-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsSMSConfigInfo</a> for more information.</li> </ul>
---------------------------	--

9.11.3.53 `typedef void( * tFNImUserConfig)(imsUserConfigInfo *plmsUserConfigInfo)`

IMS User Config indication callback.

## Parameters

<i>plmsUserConfig-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsUserConfigInfo</a> for more information.</li> </ul>
----------------------------	---

9.11.3.54 `typedef void( * tFNImVoIPConfig)(imsVoIPConfigInfo *plmsVoIPConfigInfo)`

IMS VoIP Config indication callback.

## Parameters

<i>plmsVoIPConfig-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">imsVoIPConfigInfo</a> for more information.</li> </ul>
----------------------------	---

9.11.3.55 `typedef void( * tFNInfoRec)(voiceInfoRec *pVoiceInfoRec)`

Voice Information Record callback.

## Parameters

<i>pVoiceInfoRec</i>	<ul style="list-style-type: none"> <li>• See <a href="#">voiceInfoRec</a> for more information.</li> </ul>
----------------------	--

## Note

Technology Supported: CDMA  
Device Supported: MC7750

9.11.3.56 `typedef void( * tFNInjectPosition)(QmiCbKLocInjectPositionInd *pInjectPositionNotification)`

Inject Position Notification callback.

## Parameters

<i>pInjectPosition-Notification</i>	<ul style="list-style-type: none"><li>• See <a href="#">QmiCbkLocInjectPositionInd</a> for more information.</li></ul>
-------------------------------------	--

9.11.3.57 `typedef void(* tFNInjectSensorData)(QmiCbkLocInjectSensorDataInd *pLocInjectSensorData)`

9.11.3.58 `typedef void(* tFNInjectTimeStatus)(QmiCbkLocInjectTimeInd *pLocInjectTime)`

9.11.3.59 `typedef void(* tFNInjectUTCtime)(QmiCbkLocInjectUTCtimeInd *pInjectUTCtimeNotification)`

Inject UTC Time Notification callback.

## Parameters

<i>pInjectUTCtime-Notification</i>	<ul style="list-style-type: none"><li>• See <a href="#">QmiCbkLocInjectUTCtimeInd</a> for more information.</li></ul>
------------------------------------	---

9.11.3.60 `typedef void(* tFNLUReject)(ULONG serviceDomain, ULONG rejectCause)`

LU reject callback function.



## Parameters

<i>serviceDomain</i>	<ul style="list-style-type: none"> <li>• Service domain <ul style="list-style-type: none"> <li>– 1 - Circuit Switched</li> <li>– 2 - Packet Switched</li> <li>– 3 - Circuit and Packet Switched</li> </ul> </li> </ul>
<i>rejectCause</i>	<ul style="list-style-type: none"> <li>• Reject cause</li> <li>• Valid Values <ul style="list-style-type: none"> <li>– 2 - IMSI unknown in HLR</li> <li>– 3 - Illegal MS</li> <li>– 4 - IMSI unknown in VLR</li> <li>– 5 - IMEI not accepted</li> <li>– 6 - Illegal ME</li> <li>– 11 - PLMN not allowed\</li> <li>– 12 - Location Area not allowed</li> <li>– 13 - Roaming not allowed in this location area</li> <li>– 15 - No Suitable Cells In Location Area</li> <li>– 17 - Network failure</li> <li>– 20 - MAC failure</li> <li>– 21 - Synch failure</li> <li>– 22 - Congestion</li> <li>– 23 - GSM authentication unacceptable</li> <li>– 25 - Not authorized for this CSG</li> <li>– 32 - Service option not supported</li> <li>– 33 - Requested service option not subscribed</li> <li>– 34 - Service option temporarily out of order</li> <li>– 38 - Call cannot be identified</li> <li>– 48 to 63 - retry upon entry into a new cell</li> <li>– 95 - Semantically incorrect message</li> <li>– 96 - Invalid mandatory information</li> <li>– 97 - Message type non-existent or not implemented</li> <li>– 98 - Message type not compatible with the protocol state</li> <li>– 99 - Information element non-existent or not implemented</li> <li>– 100 - Conditional IE error</li> <li>– 101 - Message not compatible with the protocol state</li> <li>– 111 - Protocol error, unspecified</li> <li>– Note - Any other value received by the mobile station shall be treated as 34, 'Service option temporarily out of order'.</li> <li>* Any other value received by the network shall be treated as 111, 'Protocol error, unspecified'.</li> </ul> </li> </ul> <p>See 3GPP TS 24.008, Section 4.4.4.7 and Section 10.5.3.6 See <a href="#">qaGobiApi-TableCallEndReasons.h</a> for Call End reasons</p>

## Note

Technology Supported: UMTS

9.11.3.61 `typedef void(* tFNMemoryFull)(SMSMemoryInfo *pSMSMemoryFullInfo)`

SMS Memory related callback function.

## Parameters

<i>pSMSMemory-FullInfo[OUT]</i>	<ul style="list-style-type: none"> <li>• pointer to <a href="#">SMSMemoryInfo</a>.</li> <li>• see <a href="#">SMSMemoryInfo</a> for details.</li> </ul>
---------------------------------	---

9.11.3.62 `typedef void(* tFNMessageWaiting)(msgWaitingInfo *pSMSMessageWaitingInfo)`

SMS Memory related callback function.

## Parameters

<i>pSMSMessage-WaitingInfo[OUT]</i>	<ul style="list-style-type: none"> <li>• pointer to <a href="#">msgWaitingInfo</a>.</li> <li>• see <a href="#">msgWaitingInfo</a> for details.</li> </ul>
-------------------------------------	---

9.11.3.63 `typedef void(* tFNMitlLvIRpt)(QmiCbkTmdMitlLvIRptInd *pSetLocCradleMount)`

9.11.3.64 `typedef void(* tFNMobileIPStatus)(ULONG mipStatus)`

Mobile IP status callback function.

## Parameters

<i>mipStatus</i>	<ul style="list-style-type: none"> <li>• Mobile IP Status             <ul style="list-style-type: none"> <li>– 0 - success</li> <li>– All others error codes as defined in RFC 2002 See <a href="#">qaGobiApiTableCallEndReasons.h</a> for mobile IP error codes</li> </ul> </li> </ul>
------------------	---

9.11.3.65 `typedef void(* tFNModemTempInfo)(modemTempNotification *pModemTempNotification)`

Modem Temperature Information callback.

## Parameters

<i>pModemTemp-Notification</i>	<ul style="list-style-type: none"> <li>• See <a href="#">modemTempNotification</a> for more information.</li> </ul>
--------------------------------	---

9.11.3.66 `typedef void(* tFNNet)(ULONG q_depth, BYTE isThrottle, BYTE instanceld)`

Transmit Queue Length Change callback function prototype

## Parameters

<i>q_depth</i>	<ul style="list-style-type: none"><li>• transmit queue length</li></ul>
<i>isThrottle</i>	<ul style="list-style-type: none"><li>• 0: unthrottle</li><li>• 1: throttle</li></ul>
<i>instanceId</i>	<ul style="list-style-type: none"><li>• qmi instance id</li></ul>

## Note

Does not require communication with the device

9.11.3.67 `typedef void (* tFNNetworkTime)(nasNetworkTime *pNasNetworkTime)`

Network Time indication callback.

## Parameters

<i>pNasNetworkTime</i>	<ul style="list-style-type: none"><li>• See <a href="#">nasNetworkTime</a> for more information.</li></ul>
------------------------	--

9.11.3.68 `typedef void(* tFNNewGPS)(double dLongitude, double dLatitude, BYTE session_status, ULONG pos_src)`

Set Current Location Data.

## Parameters

<i>dLongitude</i> [IN]	<ul style="list-style-type: none"> <li>• Current Longitude Value</li> </ul>
<i>dLatitude</i> [IN]	<ul style="list-style-type: none"> <li>• Current Latitude Value</li> </ul>
<i>session_status</i> [IN]	<ul style="list-style-type: none"> <li>• Session Status <ul style="list-style-type: none"> <li>– 0 - Success</li> <li>– 1 - In progress</li> <li>– 2 - General failure</li> <li>– 3 - Timeout</li> <li>– 4 - User ended the session</li> <li>– 5 - Bad parameter</li> <li>– 6 - Phone is offline</li> <li>– 7 - Engine is locked</li> <li>– 8 - E911 session in progress</li> </ul> </li> </ul>
<i>pos_src</i> [IN]	<ul style="list-style-type: none"> <li>• position source</li> <li>• Bitmasks <ul style="list-style-type: none"> <li>– 0x01 - GPS</li> <li>– 0x02 - Cell ID</li> <li>– 0x04 - GLONASS</li> <li>– 0x08 - Network</li> <li>– 0x10 - External positino injection</li> <li>– Others - unknown</li> </ul> </li> </ul>

## 9.11.3.69 typedef void(\* tFNNewNMEA)(LPCSTR pNMEA)

New NMEA sentence callback function.

## Parameters

<i>pNMEA</i>	<ul style="list-style-type: none"> <li>• NULL-terminated string containing the position data in NMEA sentence format</li> </ul>
--------------	---

## 9.11.3.70 typedef void(\* tFNNewRMTransferStatistics)(QmiCbkWdsStatisticsIndState \*pMsg)

PDS session state callback function.

## Parameters

<i>enabledStatus</i>	<ul style="list-style-type: none"> <li>• GPS enabled status <ul style="list-style-type: none"> <li>– 0 - Disable</li> <li>– 1 - Enable</li> </ul> </li> </ul>
<i>trackingStatus</i>	<ul style="list-style-type: none"> <li>• GPS tracking status <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - Inactive</li> <li>– 2 - Active RM Transfer Statistics message callback function.</li> </ul> </li> </ul>
<i>pMsg[OUT]</i>	<ul style="list-style-type: none"> <li>• Events related to NAS, see <a href="#">QmiCbkWdsStatisticsIndState</a> for details</li> </ul>

9.11.3.71 `typedef void(* tFNNewSMS)(ULONG storageType, ULONG messageIndex)`

New SMS message callback function.

## Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>• SMS message storage type for the new message <ul style="list-style-type: none"> <li>0 - UIM 1 - NV</li> </ul> </li> </ul>
<i>messageIndex</i>	<ul style="list-style-type: none"> <li>• Index of the new message</li> </ul>

9.11.3.72 `typedef void(* tFNOMADMState)(ULONG sessionState, ULONG failureReason)`

OMA-DM state callback function

## Parameters

<i>sessionState</i>	<ul style="list-style-type: none"> <li>• Session state <ul style="list-style-type: none"> <li>– 0x00 - Complete, information was updated</li> <li>– 0x01 - Complete, update information is unavailable</li> <li>– 0x02 - Failed</li> <li>– 0x03 - Retrying</li> <li>– 0x04 - Connecting</li> <li>– 0x05 - Connected</li> <li>– 0x06 - Authenticated</li> <li>– 0x07 - Mobile Directory Number (MDN) downloaded</li> <li>– 0x08 - Mobile Station Identifier (MSID) downloaded</li> <li>– 0x09 - PRL downloaded</li> <li>– 0x0A - Mobile IP (MIP) profile downloaded</li> </ul> </li> </ul>
<i>failureReason</i>	<ul style="list-style-type: none"> <li>• Session failure reason (when state indicates failure) <ul style="list-style-type: none"> <li>– 0x00 - Unknown</li> <li>– 0x01 - Network is unavailable</li> <li>– 0x02 - Server is unavailable</li> <li>– 0x03 - Authentication failed</li> <li>– 0x04 - Maximum retry exceeded</li> <li>– 0x05 - Session is cancelled</li> </ul> </li> </ul>

## Note

Technology Supported: CDMA

9.11.3.73 `typedef void(* tFNOpMode)(ULONG mode)`

9.11.3.74 `typedef void( * tFNOTASPStatus)(voiceOTASPStatusInfo *pVoiceOTASPStatusInfo)`

OTASP or OTAPA event Indication Callback function

## Parameters

<i>pVoiceOTASP-StatusInfo</i>	<ul style="list-style-type: none"> <li>• OTASP Status Information.</li> <li>• See <a href="#">voiceOTASPStatusInfo</a> for more information</li> </ul>
-------------------------------	--

## Note

Technology Supported: CDMA

9.11.3.75 `typedef void(* tFNPacketSrvState)(packetSrvStatus *pPacketSrvStatus)`

Packet Service state callback function.



## Parameters

<i>pPacketSrv-Status</i>	<ul style="list-style-type: none"> <li>• See <a href="#">packetSrvStatus</a> for more details</li> </ul>
--------------------------	--

## 9.11.3.76 typedef void(\* tFNPDSState)(ULONG enabledStatus, ULONG trackingStatus)

PDS session state callback function.

## Parameters

<i>enabledStatus</i>	<ul style="list-style-type: none"> <li>• GPS enabled status <ul style="list-style-type: none"> <li>– 0 - Disable</li> <li>– 1 - Enable</li> </ul> </li> </ul>
<i>trackingStatus</i>	<ul style="list-style-type: none"> <li>• GPS tracking status <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - Inactive</li> <li>– 2 - Active</li> </ul> </li> </ul>

## 9.11.3.77 typedef void(\* tFNPower)(ULONG operatingMode)

Power operating mode callback function.

## Parameters

<i>operatingMode</i>	<ul style="list-style-type: none"> <li>• Service Operating mode See <a href="#">Tables</a> for Operating Modes</li> </ul>
----------------------	---

## Note

Technology Supported: UMTS/CDMA  
Device Supported: MC83x5, MC7700/50

## 9.11.3.78 typedef void( \* tFNPrivacyChange)(voicePrivacyInfo \*pVoicePrivacyInfo)

Preferred voice privacy indication callback.

## Parameters

<i>pVoicePrivacy-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">voicePrivacyInfo</a> for more information.</li> </ul>
---------------------------	--

## Note

Technology Supported: CDMA

### 9.11.3.79 `typedef void(* tFNQosNWStatus)(BYTE status)`

QOS Network status callback function.

#### Parameters

<i>status</i>	Network QoS support status <ul style="list-style-type: none"> <li>• 0x00 – Current network does not support QoS</li> <li>• 0x01 – Current network supports QoS</li> </ul>
---------------	---

### 9.11.3.80 `typedef void(* tFNQosPriEvent)(WORD event)`

QOS primary flow callback function.

#### Parameters

<i>event</i>	Event which causes this indication: <ul style="list-style-type: none"> <li>• 0x0001 – Primary flow QoS modify operation success</li> <li>• 0x0002 – Primary flow QoS modify operation failure</li> </ul>
--------------	--

### 9.11.3.81 `typedef void(* tFNQosStatus)(BYTE instance, ULONG id, BYTE status, BYTE event, BYTE reason)`

QOS Status callback function.

#### Parameters

<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
<i>id</i>	<ul style="list-style-type: none"> <li>• Index identifying the QoS flow whose status is being reported</li> </ul>
<i>status</i>	Current QoS flow status: <ul style="list-style-type: none"> <li>• 0x01 – QMI_QOS_STATUS_ACTIVATED</li> <li>• 0x02 – QMI_QOS_STATUS_SUSPENDED</li> <li>• 0x03 – QMI_QOS_STATUS_GONE</li> </ul>

<i>event</i>	<ul style="list-style-type: none"> <li>• 0x01 – QMI_QOS_ACTIVATED_EV</li> <li>• 0x02 – QMI_QOS_SUSPENDED_EV</li> <li>• 0x03 – QMI_QOS_GONE_EV</li> <li>• 0x04 – QMI_QOS_MODIFY_ACCEPTED_EV</li> <li>• 0x05 – QMI_QOS_MODIFY_REJECTED_EV</li> <li>• 0x06 – QMI_QOS_INFO_CODE_UPDATED_EV</li> </ul>
<i>reason</i>	<ul style="list-style-type: none"> <li>• 0x01 - QMI_QOS_INVALID_PARAMS</li> <li>• 0x02 - QMI_QOS_INTERNAL_CALL_ENDED</li> <li>• 0x03 - QMI_QOS_INTERNAL_ERROR</li> <li>• 0x04 - QMI_QOS_INSUFFICIENT_LOCAL_Resources</li> <li>• 0x05 - QMI_QOS_TIMED_OUT_OPERATION</li> <li>• 0x06 - QMI_QOS_INTERNAL_UNKNOWN_CAUSE_CODE</li> <li>• 0x07 - QMI_QOS_INTERNAL_MODIFY_IN_PROGRESS</li> <li>• 0x08 - QMI_QOS_NOT_SUPPORTED</li> <li>• 0x09 - QMI_QOS_NOT_AVAILABLE</li> <li>• 0x0A - QMI_QOS_NOT_GUARANTEED</li> <li>• 0x0B - QMI_QOS_INSUFFICIENT_NETWORK_RESOURCES</li> <li>• 0x0C - QMI_QOS_AWARE_SYSTEM</li> <li>• 0x0D - QMI_QOS_UNAWARE_SYSTEM</li> <li>• 0x0E - QOS_REJECTED_OPERATION</li> <li>• 0x0F - QMI_QOS_WILL_GRANT_WHEN_QOS_RESUMED</li> <li>• 0x10 - QMI_QOS_NETWORK_CALL_ENDED</li> <li>• 0x11 - QMI_QOS_NETWORK_SERVICE_NOT_AVAILABLE</li> <li>• 0x12 - QMI_QOS_NETWORK_L2_LINK_RELEASED</li> <li>• 0x13 - QMI_QOS_NETWORK_L2_LINK_REESTAB_REJ</li> <li>• 0x14 - QMI_QOS_NETWORK_L2_LINK_REESTAB_IND</li> <li>• 0x15 - QMI_QOS_NETWORK_UNKNOWN_CAUSE_CODE</li> <li>• 0x16 - QMI_NETWORK_BUSY</li> </ul>

9.11.3.82 `typedef void(* tFNRankIndicator)(RankIndicatorInd *pRankIndicatorInd)`

9.11.3.83 `typedef void(* tFNResetInfo)(ResetInfoNotification *pResetInfoNotification)`

Get Reset Info Indication callback.

## Parameters

<i>pResetInfo-Notification</i>	<ul style="list-style-type: none"> <li>• See <a href="#">ResetInfoNotification</a> for more information.</li> </ul>
--------------------------------	---

9.11.3.84 `typedef void(* tFNRFInfo)(ULONG radiolInterface, ULONG activeBandClass, ULONG activeChannel)`

RF information callback function.

## Parameters

<i>radiolInterface</i>	<ul style="list-style-type: none"> <li>• Radio interface technology of the signal being measured See <a href="#">Tables</a> for Radio Interface</li> </ul>
<i>activeBandClass</i>	<ul style="list-style-type: none"> <li>• Active band class See <a href="#">Tables</a> for Active Band Class</li> </ul>
<i>activeChannel</i>	<ul style="list-style-type: none"> <li>• Active channel <ul style="list-style-type: none"> <li>– 0 - Channel is not relevant to the reported technology</li> </ul> </li> </ul>

9.11.3.85 `typedef void(* tFNRoamingIndicator)(ULONG roaming)`

Roaming indicator callback function.

## Parameters

<i>roaming</i>	<ul style="list-style-type: none"> <li>• Roaming Indication <ul style="list-style-type: none"> <li>– 0 - Roaming</li> <li>– 1 - Home</li> <li>– 2 - Roaming partner</li> <li>– &gt;2 - Operator defined values</li> </ul> </li> </ul>
----------------	---

9.11.3.86 `typedef void(* tFNSDKTerminated)(BYTE *psReason)`

SDK terminated callback function prototype

## Parameters

<i>psReason</i>	<ul style="list-style-type: none"> <li>• sdk termination reason string</li> </ul>
-----------------	---

## Note

Timeout: None  
Does not require communication with the device

9.11.3.87 `typedef void(* tFNSensorStreaming)(QmiCbkLocSensorStreamingInd *pLocSensorStream)`

9.11.3.88 `typedef void(* tFNServingSystem)(struct ServingSystemInfo *pServingSystem, struct RoamingInfo *pRoamingInfo)`

Serving System callback function

## Parameters

<i>pServingSystem</i>	<ul style="list-style-type: none"> <li><a href="#">ServingSystemInfo</a> structure</li> </ul>
-----------------------	---

9.11.3.89 `typedef void(* tFNSetCradleMount)(QmiCbkLocCradleMountInd *pSetLocCradleMount)`

9.11.3.90 `typedef void(* tFNSetEngineState)(QmiCbkLocEngineStateInd *pSetLocEngineState)`

9.11.3.91 `typedef void(* tFNSetEventTimeSync)(QmiCbkLocEventTimeSyncInd *pSetLocEventTimeSync)`

9.11.3.92 `typedef void(* tFNSetExtPowerConfig)(QmiCbkLocSetExtPowerConfigInd *pSetExtConfigIndStatus)`

9.11.3.93 `typedef void(* tFNSigInfo)(nasSigInfo *pNasSigInfo)`

Signal Strength Information indication callback.

## Parameters

<i>pNasSigInfo</i>	<ul style="list-style-type: none"> <li>See <a href="#">nasSigInfo</a> for more information.</li> </ul>
--------------------	--

9.11.3.94 `typedef void(* tFNSignalStrength)(INT8 signalStrength, ULONG radioInterface)`

Signal strength callback function.

## Parameters

<i>signalStrength</i>	<ul style="list-style-type: none"> <li>Received signal strength (in dBm)</li> </ul>
<i>radioInterface</i>	<ul style="list-style-type: none"> <li>Radio interface technology of the signal being measured See <a href="#">Tables</a> for Radio Interface</li> </ul>

9.11.3.95 `typedef void(* tFNSLQSOMADMAAlert)(ULONG eventType, BYTE *pEventFields)`

SWIOMA-DM network-initiated alert callback function

## Parameters

<i>eventType</i>	<ul style="list-style-type: none"> <li>• 0x00 - SWIOMA-DM FOTA</li> <li>• 0x01 - SWIOMA-DM Config</li> <li>• 0x02 - SWIOMA-DM Notification</li> </ul>
<i>pEventFields</i>	<ul style="list-style-type: none"> <li>• Pointer to structure containing info for that session type</li> <li>• See <a href="#">sessionInfo</a> for more details</li> </ul>

9.11.3.96 `typedef void(* tFNSLQSQOSEvent)(BYTE instance, QosFlowInfo *pFlowInfo)`

QOS Event callback function.

## Parameters

<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
<i>pFlowInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">QosFlowInfo</a> for more information</li> </ul>

9.11.3.97 `typedef void(* tFNSLQSSessionState)(slqsSessionStateInfo *pSessionStateInfo)`

Session state callback function.

## Parameters

<i>pSessionState-Info</i>	<ul style="list-style-type: none"> <li>• See <a href="#">slqsSessionStateInfo</a> for more details</li> </ul>
---------------------------	---

9.11.3.98 `typedef void(* tFNSLQSSignalStrengths)(struct SLQSSignalStrengthsInformation sSLQSSignalStrengthsInfo)`

Received Signal Strength Information callback function.

## Parameters

<i>sSLQSSignal-StrengthsInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SLQSSignalStrengthsInformation</a> for more information.</li> </ul>
----------------------------------	--

9.11.3.99 `typedef void(* tFNSLQSWDSEvent)(slqsWdsEventInfo *pWdsEventInfo)`

WDS Event callback function.

## Parameters

<i>pWdsEventInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">slqsWdsEventInfo</a> for more details</li> </ul>
----------------------	---

9.11.3.100 `typedef void(* tFNSMSEvents)(SMSEventInfo *pSMSEventInfo)`

SMS event related callback function.

## Parameters

<i>pSMSEventInfo[OUT]</i>	<ul style="list-style-type: none"> <li>• Events related to SMS, see <a href="#">SMSEventInfo</a> for details</li> </ul>
---------------------------	---

9.11.3.101 `typedef void(* tFNSUPSInfo)(voiceSUPSInfo *pVoiceSUPSInfo)`

Preferred SUPS indication callback.

## Parameters

<i>pVoiceSUPSInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">voiceSUPSInfo</a> for more information.</li> </ul>
-----------------------	---

## Note

Technology Supported: GSM

9.11.3.102 `typedef void(* tFNSUPSNotification)(voiceSUPSNotification *pVoiceSUPSNotification)`

Supplementary service notification callback.

## Parameters

<i>pVoiceSUPS-Notification</i>	<ul style="list-style-type: none"> <li>• See <a href="#">voiceSUPSNotification</a> for more information.</li> </ul>
--------------------------------	---

9.11.3.103 `typedef void(* tFNSysInfo)(nasSysInfo *pNasSysInfo)`

System Information indication callback.

## Parameters

<i>pNasSysInfo</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nasSysInfo</a> for more information.</li> </ul>
--------------------	--

9.11.3.104 `typedef void(* tFNSysSelectionPref)(sysSelectPrefInfo *pSysSelectPrefInfo)`

System Selection Preference Callback function

## Parameters

<i>pSysSelectPref-Info</i>	<ul style="list-style-type: none"> <li>• Current System Selection preferences for the device.</li> <li>• See <a href="#">sysSelectPrefInfo</a> for more information</li> </ul>
----------------------------	--

9.11.3.105 `typedef void(* tFNtransLayerInfo)(transLayerNotification *pTransLayerNotification)`

Transport Layer Information callback.

## Parameters

<i>transLayer-Notification</i>	<ul style="list-style-type: none"> <li>• See <a href="#">transLayerNotification</a> for more information.</li> </ul>
--------------------------------	--

9.11.3.106 `typedef void(* tFNtransNWRegInfo)(transNWRegInfoNotification *pTransNWRegInfoNotification)`

Transport Network Registration Information callback.

## Parameters

<i>pTransNWReg-InfoNotification</i>	<ul style="list-style-type: none"> <li>• See <a href="#">transNWRegInfoNotification</a> for more information.</li> </ul>
-------------------------------------	--

9.11.3.107 `typedef void(* tFNUIMRefresh)(UIMRefreshEvent *pUIMRefreshEvent)`

UIM Refresh Callback function

## Parameters

<i>pUIMRefresh-Event</i>	<ul style="list-style-type: none"> <li>• Pointer to Refresh Event structure.</li> <li>• See <a href="#">UIMRefreshEvent</a> for more information</li> </ul>
--------------------------	---

9.11.3.108 `typedef void(* tFNUIMStatusChangeInfo)(UIMStatusChangeInfo *pUIMStatusChangeInfo)`

UIM Status Change Callback function

## Parameters

<i>pUIMStatus-ChangeInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to UIM status change structure.</li> <li>• See <a href="#">UIMStatusChangeInfo</a> for more information</li> </ul>
------------------------------	---



9.11.3.109 `typedef void(* tFNUSSDNotification)(ULONG type, BYTE *pNetworkInfo)`

SetUSSDNotificationCallback function prototype

## Parameters

<i>type</i>	<ul style="list-style-type: none"> <li>- Notification type <ul style="list-style-type: none"> <li>• 0x01 - No action required</li> <li>• 0x02 - Action required</li> </ul> </li> </ul>
<i>pNetworkInfo</i>	<ul style="list-style-type: none"> <li>• USS information from the network (0 indicates that no info was received) <ul style="list-style-type: none"> <li>– See <a href="#">USSInfo</a> for more details</li> </ul> </li> </ul>

## Note

Technology Supported: UMTS

9.11.3.110 `typedef void(* tFNUSSDNoWaitIndication)(USSDNoWaitIndicationInfo *pNetworkInfo)`

9.11.3.111 `typedef void(* tFNUSSDRelease)(void)`

USSD releaserecallback function prototype

## Note

Technology Supported: UMTS

9.11.3.112 `typedef struct _transLayerInfoNotification transLayerNotification`

Contains the parameters passed for SLQSSetTransLayerInfoCallback by the device.

## Parameters

<i>regInd</i>	<ul style="list-style-type: none"> <li>• Indicates whether the transport layer is registered or not</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Transport layer is not registered</li> <li>– 0x01 - Transport layer is registered</li> </ul> </li> </ul>
<i>pTransLayerInfo</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• See <a href="#">transLayerInfo</a> for more information</li> </ul>

## Note

None

9.11.3.113 `typedef struct _transNWRegInfoNotification transNWRegInfoNotification`

Contains the parameters passed for SLQSSetTransNWRegInfoCallback by the device.

## Parameters

<i>NWRegStat</i>	<ul style="list-style-type: none"> <li>• provides the transport network registration information</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - No Service</li> <li>– 0x01 - In Progress</li> <li>– 0x02 - Failed</li> <li>– 0x03 - Limited Service</li> <li>– 0x04 - Full Service</li> </ul> </li> </ul>
------------------	---

## Note

None

## 9.11.4 Enumeration Type Documentation

## 9.11.4.1 enum device\_state\_enum

Device State enumeration

- See [device\\_state\\_enum](#) for more details

## Enumerator

***DEVICE\_STATE\_DISCONNECTED******DEVICE\_STATE\_READY******DEVICE\_STATE\_BOOT***

## 9.11.4.2 enum eQaQMIService

The QMI service information which is exposed to the application, only the services which are relevant to multiple PDP are listed in this enumeration as these are the only required services to be exposed.

## Enumerator

***eQA\_QMI\_SVC\_WDS******eQA\_QMI\_SVC\_NAS******eQA\_QMI\_SVC\_NA***

## 9.11.4.3 enum SMSEventType

This enumeration defines the different type of SMS events that are received

- See [SMSEventType](#) for more details

## Enumerator

***SMS\_EVENT\_MT\_MESSAGE******SMS\_EVENT\_TRANSFER\_ROUTE\_MT\_MESSAGE***

***SMS\_EVENT\_MESSAGE\_MODE***

***SMS\_EVENT\_ETWS***

***SMS\_EVENT\_ETWS\_PLMN***

***SMS\_EVENT\_SMSC\_ADDRESS***

***SMS\_EVENT\_SMS\_ON\_IMS***

### 9.11.5 Function Documentation

9.11.5.1 **ULONG** iSetCATEventCallback ( **tFNCATEvent** *pCallback* )

9.11.5.2 **ULONG** iSetSignalStrengthCallback ( **tFNSignalStrength** *pCallback* )

9.11.5.3 **ULONG** iLQSSetDUNCallInfoCallback ( **tFNDUNCallInfo** *pCallback* )

9.11.5.4 **ULONG** iLQSSetSignalStrengthsCallback ( **tFNSLQSSignalStrengths** *pCallback* )

9.11.5.5 **ULONG** iLQSSetWdsFirstInstEventCallback ( **tFNSLQSWDSEvent** *pCallback* )

9.11.5.6 **ULONG** iLQSSetWdsSecondInstEventCallback ( **tFNSLQSWDSEvent** *pCallback* )

9.11.5.7 **ULONG** iLQSSetWdsThirdInstEventCallback ( **tFNSLQSWDSEvent** *pCallback* )

9.11.5.8 **ULONG** iLQSSetWdsXferStatsFirstInstCallback ( **tFNSLQSWDSEvent** *pCallback* )

9.11.5.9 **ULONG** iLQSSetWdsXferStatsSecondInstCallback ( **tFNSLQSWDSEvent** *pCallback* )

9.11.5.10 **ULONG** SetActivationStatusCallback ( **tFNActivationStatus** *pCallback* )

Enables/disables the Activation Status callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

#### Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
-----------------------	---

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.11.5.11 **ULONG** SetCATEventCallback ( **tFNCATEvent** *pCallback*, **ULONG** *eventMask*, **ULONG** \* *pErrorMask* )

Enables/disables the CAT event callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
<i>eventMask</i>	<ul style="list-style-type: none"> <li>• bitmask of CAT events to register for <ul style="list-style-type: none"> <li>– 0x00000001 - Display Text</li> <li>– 0x00000002 - Get In-Key</li> <li>– 0x00000004 - Get Input</li> <li>– 0x00000008 - Setup Menu</li> <li>– 0x00000010 - Select Item</li> <li>– 0x00000020 - Send SMS - Alpha Identifier</li> <li>– 0x00000040 - Setup Event: User Activity</li> <li>– 0x00000080 - Setup Event: Idle Screen Notify</li> <li>– 0x00000100 - Setup Event: Language Sel Notify</li> <li>– 0x00000200 - Setup Idle Mode Text</li> <li>– 0x00000400 - Language Notification</li> <li>– 0x00000800 - Refresh</li> <li>– 0x00001000 - End Proactive Session</li> </ul> </li> </ul>
<i>pErrorMask</i> [OUT]	<ul style="list-style-type: none"> <li>• error bitmask. Each bit set indicates the proactive command that caused the error <ul style="list-style-type: none"> <li>– 0x00000001 - Display Text</li> <li>– 0x00000002 - Get In-Key</li> <li>– 0x00000004 - Get Input</li> <li>– 0x00000008 - Setup Menu</li> <li>– 0x00000010 - Select Item</li> <li>– 0x00000020 - Send SMS - Alpha Identifier</li> <li>– 0x00000040 - Setup Event: User Activity</li> <li>– 0x00000080 - Setup Event: Idle Screen Notify</li> <li>– 0x00000100 - Setup Event: Language Sel Notify</li> <li>– 0x00000200 - Setup Idle Mode Text</li> <li>– 0x00000400 - Language Notification</li> <li>– 0x00000800 - Refresh</li> <li>– 0x00001000 - End Proactive Session</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

Technology Supported: UMTS  
Timeout: 2 seconds

**9.11.5.12   ULONG SetDataCapabilitiesCallback ( tFNDataCapabilities *pCallback* )**

Enables/disables the data capabilities callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Does not require communication with the device

#### 9.11.5.13 ULONG SetDeviceStateChangeCbK ( tFNDeviceStateChange *pCallback* )

Used by the client application to register a Callback function for Device State Change (DSC) event notifications. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to be notified of DSC events</li> <li>• NULL to disable DSC event notification</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.11.5.14 ULONG SetFwDldCompletionCbK ( tFNFwDldCompletion *pCallback* )

Used by the client application to register a Callback function for a Firmware Download Completion (FDC) event notification. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to enable FDC event notification</li> <li>• NULL to disable FDC event notification</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: N/A

**9.11.5.15 ULONG SetGPSCallback ( tFNNewGPS pCallback )**

Enables/disables the NMEA sentence callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.16 ULONG SetLocCradleMountCallback ( tFNSetCradleMount pCallback )**

Enables/disables the Cradle Mount callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.17 ULONG SetLocDeleteAssistDataCallback ( tFNDelAssistData pCallback )**

Enables/disables Delete Assist Data callback function. This API is used to receive the SUCCESS/FAILURE status of API [SLQSLOCDeAssData\(\)](#).

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

**9.11.5.18 ULONG SetLocEngineStateCallback ( tFNSetEngineState pCallback )**

Sends the GPS State Information event to the control point.



## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.19    ULONG SetLocEventPositionCallback ( tFNEventPosition pCallback )**

Enables/disables the Event Position Report callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.20    ULONG SetLocEventTimeSyncCallback ( tFNSetEventTimeSync pCallback )**

Enables/disables the Event Time Sync callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.21    ULONG SetLocGnssSvInfoCallback ( tFNGnssSvInfo pCallback )**

Enables/disables the GNSS [SV](#) Info callback function. This API is used to send the satellite report to the application. The satellite reports are sent only to the application that invoked API [SLQSLOCStart\(\)](#) that generated the satellite report.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.11.5.22 **ULONG** SetLocInjectSensorDataCallback ( **tFNInjectSensorData** *pCallback* )

Enables/disables the Inject Sensor Data callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### 9.11.5.23 **ULONG** SetLocInjectTimeCallback ( **tFNInjectTimeStatus** *pCallback* )

Enables/disables the Inject Time Sync Data callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### 9.11.5.24 **ULONG** SetLocOpModeCallback ( **tFNOpMode** *pCallback* )

Enables/disables Set Operating Mode callback function. This API is used to receive the SUCCESS/FAILURE status of API [SLQSLOCSetOpMode\(\)](#).

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

#### 9.11.5.25 **ULONG** SetLocSensorStreamingCallback ( **tFNSensorStreaming** *pCallback* )

Enables/disables the Event Sensor Streaming Ready Status callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [!N]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

9.11.5.26 **ULONG** SetLocSetExtPowerConfigCallback ( **tFNSetExtPowerConfig** *pCallback* )

Enables/disables the Set External Power Config Status callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [!N]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

9.11.5.27 **ULONG** SetLURejectCallback ( **tFNLUReject** *pCallback* )

Enables/disables the LU reject callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [!N]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

9.11.5.28 **ULONG** SetMobileIPStatusCallback ( **tFNMobileIPStatus** *pCallback* )

Enables/disables the Mobile IP Status callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA  
Timeout: 2 seconds

**9.11.5.29    ULONG SetNasLTECphyCalndCallback ( tFNASwiLTECphyCalInfo *pCallback* )**

Enables/disables the LTE NAS CA Info callback function.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.11.5.30    ULONG SetNetChangeCbk ( BYTE *instance*, tFNNet *pCallback*, ULONG *loMark*, ULONG *hiMark*, ULONG *period* )**

Used by the client application to register a Callback function for USB Transmit Queue Length Change event notifications. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>instance</i> [IN]	<ul style="list-style-type: none"> <li>• PDP instance</li> </ul>
<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to be notified of the event</li> <li>• NULL to disable the event notification</li> </ul>
<i>loMark</i> [IN]	<ul style="list-style-type: none"> <li>• Transmit queue length smaller will trigger unthrottle event notification</li> </ul>
<i>hiMark</i> [IN]	<ul style="list-style-type: none"> <li>• Transmit queue length larger will trigger throttle event notification</li> </ul>
<i>period</i> [IN]	<ul style="list-style-type: none"> <li>• monitoring period in seconds, minimum 1 second</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.11.5.31 ULONG SetNewSMSCallback ( tFNNewSMS pCallback )

Enables/disables the new SMS callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

Timeout: 2 seconds

## 9.11.5.32 ULONG SetNMEACallback ( tFNNewNMEA pCallback )

Enables/disables the NMEA sentence callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

This API is deprecated on all MC/EM74xx firmware versions. Please use [SetLocEventPositionCallback\(\)](#)

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.33    ULONG SetOMADMStateCallback ( tFNOMADMState pCallback )**

Enables/disables the OMADM state callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

This API is deprecated on all MC/EM74xx firmware versions. Please use [SetSLQSOMADMAAlertCallback\(\)](#)

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• a valid function pointer to enable OMADMState notification</li><li>• NULL to disable OMADMState notification</li></ul>
-----------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

Technology Supported: CDMA  
Timeout: 2 seconds

**9.11.5.34    ULONG SetPDSServiceStateCallback ( tFNPDSState pCallback )**

Enables/disables the PDS service state callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.35    ULONG SetPowerCallback ( tFNPower pCallback )**

Enables/disables the Operating Mode callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.11.5.36   ULONG SetRankIndicatorCallback ( tFNRankIndicator pCallback )****9.11.5.37   ULONG SetRFInfoCallback ( tFNRFInfo pCallback )**

Enables/disables the radio frequency information callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.11.5.38   ULONG SetRMTransferStatisticsCallback ( tFNNewRMTransferStatistics pCallback )**

Enables/disables the RM Transfer Statistics callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0 - Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### 9.11.5.39 **ULONG** SetRoamingIndicatorCallback ( **tFN**RoamingIndicator *pCallback* )

Enables/disables the Roaming Indicator callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

This API is deprecated on all MC/EM74xx firmware versions. Please use [SLQSNasSysInfoCallBack\(\)](#) instead

##### Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
-----------------------	---

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Timeout: 2 seconds

#### 9.11.5.40 **ULONG** SetSignalStrengthCallback ( **tFN**SignalStrength *pCallback*, **BYTE** *thresholdsSize*, **INT8** \* *pThresholds* )

Enables/disables the Signal Strength callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This API is deprecated on MC73xx/-EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSNasIndicationRegisterExt\(\)](#) for new firmware versions and new modules

##### Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
<i>thresholdsSize</i>	<ul style="list-style-type: none"> <li>• Number of elements threshold array contains; a maximum of five thresholds is supported;</li> <li>• This parameter is not used when disabling the callback.</li> </ul>
<i>pThresholds</i> [IN]	<ul style="list-style-type: none"> <li>• Signal threshold array for each entry (in dBm).</li> <li>• This parameter is not used when disabling the callback.</li> </ul>

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values



**Note**

Timeout: 2 seconds

The signal strength callback function is called when a threshold in the threshold array is crossed.

**9.11.5.41    `ULONG SetSLQSOMADMAAlertCallback ( tFNSLQSOMADMAAlert pCallback )`**

Enables/disables the SWIOMADM network-initiated alert callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to enable SLQSOMADMAAlert notification</li> <li>• NULL to disable SLQSOMADMAAlert notification</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.42    `ULONG SetSLQSOMADMAAlertCallbackExt ( tFNSLQSOMADMAAlert pCallback )`**

Enables/disables the SWIOMADM network-initiated alert callback function for SL9090 module. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to enable SLQSOMADMAAlert notification</li> <li>• NULL to disable SLQSOMADMAAlert notification</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**Note**

Technology Supported: UMTS/CDMA

Device Supported: SL9090

Timeout: 2 seconds

**9.11.5.43    `ULONG SetUimSlotStatusChangeCallback ( tFNCbkUimSlotStatusChangeInd pCallback )`**

Enables/disables Slot Status Change callback function.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

#### 9.11.5.44 **ULONG** SetUSSDNotificationCallback ( **tFNUSSDNotification** *pCallback* )

Enables/disables the USSDNotification callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to enable ServingSystem notification</li> <li>• NULL to disable ServingSystem notification</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**Note**

Technology Supported: UMTS

Timeout: Does not require communication with device

#### 9.11.5.45 **ULONG** SetUSSDNoWaitIndicationCallback ( **tFNUSSDNoWaitIndication** *pCallback* )

SetUSSDNoWaitIndicationCallback

**Parameters**

<i>pNetworkInfo</i>	<ul style="list-style-type: none"> <li>• Data from the network.</li> <li>• See <a href="#">USSDNoWaitIndicationInfo</a> for more details.</li> </ul>
---------------------	--

**Note**

Technology Supported: UMTS

Device Supported: MC83x5

#### 9.11.5.46 **ULONG** SetUSSDReleaseCallback ( *tFNUSSDRelease* *pCallback* )

Enables/disables the USSD release callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to enable ServingSystem notification</li> <li>• NULL to disable ServingSystem notification</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

Technology Supported: UMTS

Timeout: Does not require communication with the device

#### 9.11.5.47 ULONG SLQSNasNetworkTimeCallBack ( tFNNetworkTime *pCallback* )

Enables/disables the Network Time callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

This callback is sent when the 3GPP or 3GPP2 network sends time information to the User Equipment.

#### 9.11.5.48 ULONG SLQSNasSigInfo2CallBack ( tFNSigInfo *pCallback*, setSignalStrengthInfo \* *pSigInfo2* )

Enables/disables the Signal Info callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

<i>pSigInfo2[IN]</i>	<ul style="list-style-type: none"> <li>• Structure containing the threshold values beyond which signal information is to be reported</li> <li>• See <a href="#">setSignalStrengthInfo</a> for more details</li> </ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

This callback is sent when the signal strength change occurs

#### 9.11.5.49 ULONG SLQSNasSigInfoCallBack ( tFNSigInfo pCallback, sigInfo \* pSigInfo )

Enables/disables the Signal Info callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This callback is deprecated on MC73xx/-EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use callback [SLQSNasSigInfo2CallBack\(\)](#) for new firmware versions and new modules

**Parameters**

<i>pCallback[IN]</i>	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
<i>pSigInfo[IN]</i>	<ul style="list-style-type: none"> <li>• Structure containing the threshold values beyond which signal information is to be reported</li> <li>• See <a href="#">sigInfo</a> for more details</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

This callback is sent when the signal strength change occurs

#### 9.11.5.50 ULONG SLQSNasSwtOTAMessageCallback ( NasSwtIndReg \* req, tFNASwtOTAMsg pCallback )

Enables/disables the SLQSNasSwtOTAMessageCallback callback function. To disable the callback, provide both req and pCallback as NULL pointer to the API

## Parameters

<i>req</i> [IN]	<ul style="list-style-type: none"> <li>the request to which kind of message type should be enabled, see <a href="#">NasSwiIndReg</a> for details</li> </ul>
<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>Callback function pointer (0-Disable)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.11.5.51 **ULONG SLQSNasSysInfoCallBack ( tFNSysInfo pCallback )**

Enables/disables the Sys Info callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

This callback provides current serving system information, including registration information and system property. The serving system information of the radio interfaces specified in mode\_pref are included in the response message. When any value in the sys\_info message changes, an indication message is sent. Indications contain all the values for all active RATs.

#### 9.11.5.52 **ULONG SLQSSetBandPreferenceCbk ( tFNBandPreference pCallback )**

Enables/disables the Band Preference callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to enable Band Preference Indication notification</li> <li>• NULL to disable Band Preference notification</li> </ul>
-----------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

Timeout: NA To set the band preference the API [SLQSSetBandPreference\(\)](#) should be used

#### 9.11.5.53 ULONG SLQSSetDataSystemStatusCallback ( tFNDataSysStatus *pCallback* )

Enables/disables the Data System Status callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.11.5.54 ULONG SLQSSetDHCPv4ClientLeaseStatusCallback ( BYTE *instance*, tFNDHCPv4ClientLeaseStatus *pCallback* )

Enables/disables the DHCP Client V4 Lease Status callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>instance</i> [IN]	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**9.11.5.55    ULONG SLQSSetDUNCallInfoCallback ( BYTE *StatsPeriod*, tFNDUNCallInfo *pCallback* )**

Enables/disables the DUN Call Info callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.



## Parameters

<i>StatsPeriod</i> [IN]	<ul style="list-style-type: none"> <li>• Period between reports(seconds)</li> <li>• 0 - Do not report</li> <li>• Only applicable to pTXOKBytesCount and pRXOKBytesCount parameters</li> </ul>
<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.11.5.56 ULONG SLQSSetIMSAPdpStatusCallback ( tFNImsaPdpStatus *pCallback* )

SLQSSetIMSAPdpStatusCallback

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.11.5.57 ULONG SLQSSetIMSAratStatusCallback ( tFNImsaRatStatus *pCallback* )

SLQSSetIMSAratStatusCallback

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.11.5.58    ULONG SLQSSetIMSARegStatusCallback ( tFNImsaRegStatus *pCallback* )**

SLQSSetIMSARegStatusCallback

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.11.5.59    ULONG SLQSSetIMSASvcStatusCallback ( tFNImsaSvcStatus *pCallback* )**

SLQSSetIMSASvcStatusCallback

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.11.5.60 ULONG SLQSSetIMSSMSConfigCallback ( tFNImSMSConfig pCallback )**

Enables/disables the SMS Config callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.11.5.61 ULONG SLQSSetIMSUserConfigCallback ( tFNImUserConfig pCallback )**

Enables/disables the User Config callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.11.5.62 ULONG SLQSSetIMSVoIPConfigCallback ( tFNImVoIPConfig pCallback )**

Enables/disables the VoIP Config callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.11.5.63 **ULONG** SLQSSetLocInjectPositionCallback ( **tFNInjectPosition** *pCallback* )

Enables/disables Inject Position callback function. This API is used to receive the SUCCESS/FAILURE status of API [SLQSLOCInjectPosition\(\)](#).

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

#### 9.11.5.64 **ULONG** SLQSSetLocInjectUTCTimeCallback ( **tFNInjectUTCTime** *pCallback* )

Enables/disables Inject UTC Time callback function. This API is used to receive the SUCCESS/FAILURE status of API [SLQSLOCInjectUTCTime\(\)](#).

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

#### 9.11.5.65 **ULONG** SLQSSetModemTempCallback ( **tFNModemTempInfo** *pCallback* )

Enables/disables the Modem Temperature information callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.11.5.66 ULONG SLQSSetPacketSrvStatusCallback ( tFNPacketSrvState pCallback )

Enables/disables the session state callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [!N]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: none; does not require communication with the device

#### 9.11.5.67 ULONG SLQSSetQosEventCallback ( BYTE instance, tFNSLQSQOSEvent pCallback )

Enables/disables the QoS event callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This callback provide extra information regarding the QoS flow state

## Parameters

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
in	<i>pCallback</i>	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

maximum number of tx/rx filters supported is 25 (pTxQFilter/pRxQFilter)

#### 9.11.5.68 **ULONG** SLQSSetQosNWStatusCallback ( **tFNQosNWStatus** *pCallback* )

Enables/disables the QoS event callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This callback provide extra information regarding the QoS Network supports status

##### Parameters

in	<i>pCallback[IN]</i>	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
----	----------------------	---

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.11.5.69 **ULONG** SLQSSetQosPriEventCallback ( **tFNQosPriEvent** *pCallback* )

Enables/disables the QoS event callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This callback provide extra information regarding the QoS Primary flow event

##### Parameters

in	<i>pCallback</i>	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
----	------------------	---

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Technology Supported: UMTS

#### 9.11.5.70 **ULONG** SLQSSetQosStatusCallback ( **BYTE** *instance*, **tFNQosStatus** *pCallback* )

Enables/disables the QoS event callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This callback provide extra information regarding the QoS status

##### Parameters

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
in	<i>pCallback[IN]</i>	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.11.5.71 ULONG SLQSSetRegMgrConfigCallback ( tFNlmsRegMgrConfig pCallback )**

Enables/disables the Reg Mgr Config callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback[IN]</i>	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.11.5.72 ULONG SLQSSetSDKTerminatedCallback ( tFNSDKTerminated pCallback )**

Used by the client application to register a Callback function for SDK terminated event notifications. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback[IN]</i>	<ul style="list-style-type: none"> <li>• a valid function pointer to be notified of SWI events</li> <li>• NULL to disable SWI event notification</li> </ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: N/A

Device Supported: N/A

Timeout: N/A

The following signals will trigger this callback:

2 INT	4 ILL	5 TRAP	6 ABRT	7 BUS
8 FPE	11 SEGV	13 PIPE	15 TERM	31 SYS

#### 9.11.5.73 **ULONG SLQSSetServingSystemCallback ( tFNServingSystem pCallback )**

Enables/disables the Serving System callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

This API is deprecated on all MC/EM74xx firmware versions. Please use [SLQSNasSysInfoCallBack\(\)](#)

##### Parameters

<i>pCallback[IN]</i>	<ul style="list-style-type: none"> <li>• a valid function pointer to enable ServingSystem notification</li> <li>• NULL to disable ServingSystem notification</li> </ul>
----------------------	---

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### 9.11.5.74 **ULONG SLQSSetSessionStateCallback ( tFNSLQSSessionState pCallback )**

Enables/disables the session state callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This callback provide extra information regarding the multiple PDP interface

##### Parameters

<i>pCallback[IN]</i>	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
----------------------	---

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Timeout: none; does not require communication with the device

#### 9.11.5.75 **ULONG SLQSSetSignalStrengthsCallback ( tFNSLQSSignalStrengths pCallback, struct SLQSSignalStrengthsIndReq \* pSLQSSignalStrengthsIndReq )**

Enables/disables the Received Signal Strength Information callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This API is same as API SetSignalStrengthsCallback() except providing more information of signal such as ECIO, SNR etc. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all E-M74xx firmware versions. Please use API [SLQSNasIndicationRegisterExt\(\)](#) for new firmware versions and new modules



## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
<i>pSLQSSignalStrengthsIndReq</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SLQSSignalStrengthsIndReq</a> for more information</li> <li>• This parameter is not used when disabling the callback.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

The signal strength callback function is called when a threshold in the threshold array is crossed.

#### 9.11.5.76 ULONG SLQSSetSIPConfigCallback ( tFNImSIPConfig pCallback )

Enables/disables the SIP Config callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.11.5.77 ULONG SLQSSetSMSEventCallback ( tFNSMSEvents pCallback )

Enables/disables the events related to SMS callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### 9.11.5.78 ULONG SLQSSetSwtGetResetInfoCallback ( tFNResetInfo pCallback )

Reset Info callback.

## Parameters

<i>pCallback</i>	<ul style="list-style-type: none"> <li>• See <a href="#">tFNResetInfo</a> for more information.</li> </ul>
------------------	--

#### 9.11.5.79 ULONG SLQSSetSwtHdRPersCallback ( tFNHDRPersonaity pCallback )

Enables/disables the HDR Personality callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA  
Timeout: 5 seconds

#### 9.11.5.80 ULONG SLQSSetSysSelectionPrefCallBack ( tFNSysSelectionPref pCallback )

Enables/disables the System Selection Preference callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to enable System Selection Preference Indication notification</li> <li>• NULL to disable Band Preference notification</li> </ul>
-----------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**Note**

Timeout: 2 seconds

To set the system selection preferences the API [SLQSSetSysSelectionPref\(\)](#) should be used

**9.11.5.81 ULONG SLQSSetTransLayerInfoCallback ( tFNtransLayerInfo pCallback )**

Enables/disables the Transport Layer information callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback[IN]</i>	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.11.5.82 ULONG SLQSSetTransNWRegInfoCallback ( tFNtransNWRegInfo pCallback )**

Enables/disables the Transport Network Registration information callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback[IN]</i>	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

9.11.5.83 **ULONG** SLQSSetWdsEventCallback ( **tFNSLQSWDSEvent** *pCallback*, **BYTE** *interval*, **BYTE** *instanceid*, **BYTE** *ipfamily* )

Enables/disables the WDS event callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This callback provide extra information regarding the multiple PDP interface. Transfer statistic are reported only when changed.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
<i>interval</i>	<ul style="list-style-type: none"> <li>• Interval in seconds.</li> <li>• ignored when disabling, should be non-zero when enabling</li> <li>• period only affect transfer statistic attributes</li> </ul>
<i>instanceid</i>	<ul style="list-style-type: none"> <li>• PDP instance id 0 - First PDP instance 1 - Second PDP instance 2 - Third PDP instance</li> </ul>
<i>ipfamily</i>	<ul style="list-style-type: none"> <li>• 4 for an IPv4 data session</li> <li>• 6 for an IPv6 data session</li> <li>• 7 for an IPv4v6 data session</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds Currently 3 PDP instances are supported in device. user of this callback can subscribe by passing instanceid of particular instance. All PDP instance can be subscribed by passing instanceid sequentially.

#### 9.11.5.84 ULONG SLQSSetWdsTransferStatisticCallback ( tFNSLQSWDSEvent *pXferStatsCb*, BYTE *interval*, BYTE *instanceid*, BYTE *ipfamily* )

Enables/disables the WDS transfer statistic callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. This callback provide extra information regarding the multiple PDP interface. Transfer statistic are reported only when changed.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0 - disable)</li> </ul>
<i>interval</i>	<ul style="list-style-type: none"> <li>• Interval in seconds.</li> <li>• ignored when disabling, should be non-zero when enabling</li> <li>• period only affect transfer statistic attributes</li> </ul>
<i>instanceid</i>	<ul style="list-style-type: none"> <li>• PDP instance id 0 - First PDP instance 1 - Second PDP instance 2 - Third PDP instance</li> </ul>
<i>ipfamily</i>	<ul style="list-style-type: none"> <li>• 4 for an IPv4 data session</li> <li>• 6 for an IPv6 data session</li> <li>• 7 for an IPv4v6 data session</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds Currently 3 PDP instances are supported in device. User of this callback can subscribe by passing instance id of particular instance. All PDP instance can be subscribed by passing instance id sequentially.

#### 9.11.5.85 ULONG SLQSTmdMitigationLvIRptCallback ( TmdMitigationLvIRptReq \* req, tFNMitLvIRpt pCallback )

Thermal Mitigation callback.

## Parameters

<i>req</i>	<ul style="list-style-type: none"> <li>• See <a href="#">TmdMitigationLvIRptReq</a> for more information.</li> </ul>
<i>pCallback</i>	<ul style="list-style-type: none"> <li>• See <a href="#">tFNMitLvIRpt</a> for more information.</li> </ul>

#### 9.11.5.86 ULONG SLQSUIMSetRefreshCallBack ( tFNUIMRefresh pCallback )

Enables/disables the UIM refresh callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• a valid function pointer to enable UIM Refresh Indication notification</li><li>• NULL to disable Band Preference notification</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

Timeout: 2 seconds

[SLQSUIMRefreshRegister\(\)](#) API should be invoked prior to the invocation of the callback for the events to be registered.

**9.11.5.87    ULONG SLQSUIMSetStatusChangeCallBack ( tFNUIMStatusChangeInfo pCallback )**

Enables/disables the UIM Status Change Callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• a valid function pointer to enable UIM Status Change Indication notification</li><li>• NULL to disable Band Preference notification</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

Timeout: 2 seconds

**9.11.5.88    ULONG SLQSVoiceInfoRecCallback ( tFNInfoRec pCallback )**

Enables/disables the Voice information Record callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs. (Applicable only for 3GPP2)

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 2 seconds

**9.11.5.89 ULONG SLQSVoiceSetAllCallStatusCallBack ( tFNAIICallStatus pCallback )**

Enables/disables Voice Call Status Callback function. User can subscribe this callback get the call state change notifications. eg:- Call originated, connected, or ended. Whenever there is a change in the call information, there will be a indication with the information.

**Parameters**

<i>pCallback[IN]</i>	<ul style="list-style-type: none"><li>• Callback function pointer (0 - Disable)</li></ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.11.5.90 ULONG SLQSVoiceSetDTMFEventCallBack ( tFNDTMFEvent pCallback )**

Enables/disables the DTMF Event callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback[IN]</i>	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds  
This callback communicates that a DTMF event has been received.

**9.11.5.91 ULONG SLQSVoiceSetOTASPStatusCallBack ( tFNOTASPStatus pCallback )**

Enables/disables OTASP(Over-The-Air Service Provisioning) or OTAPA(Over-The-Air Parameter Administration) event CallBack Function (applicable only for 3GPP2). The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.



## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• a valid function pointer to enable OTASP or OTAPA event Indication notification</li> <li>• NULL to disable OTASP or OTAPA event, Indication notification</li> </ul>
-----------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## Note

Technology Supported: CDMA

Timeout: 10 seconds

This indication communicates the occurrence of an OTASP or OTAPA event. This indication is only applicable for 3GPP2 devices.

#### 9.11.5.92 ULONG SLQSVoiceSetPrivacyChangeCallBack ( tFNPrivacyChange *pCallback* )

Enables/disables the voice privacy change callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA

Timeout: 2 seconds

This callback communicates a change in the voice privacy of a call. This is applicable only in 3GPP2 devices.

#### 9.11.5.93 ULONG SLQSVoiceSetSUPSCallBack ( tFNSUPSInfo *pCallback* )

Enables/disables the SUPS callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

## Parameters

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: GSM

Timeout: 2 seconds

This callback notifies clients about the modem-originated supplementary service requests and the responses received from the network.

**9.11.5.94 ULONG SLQSVoiceSetSUPSNotificationCallback ( tFNSUPSNotification pCallback )**

Enables/disables the supplementary service notification callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.11.5.95 ULONG SLQSWmsAsyncRawSendCallBack ( tFNAsyncRawSend pCallback )**

Enables/disables the SLQSWmsAsyncRawSendCallBack callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"><li>• Callback function pointer (0-Disable)</li></ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.11.5.96    ULONG SLQSWmsMemoryFullCallBack ( tFNMemoryFull pCallback )**

Enables/disables the event related to memory full status callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.11.5.97    ULONG SLQSWmsMessageWaitingCallBack ( tFNMessageWaiting pCallback )**

Enables/disables the event related to message waiting information callback function. The most recent successfully subscribed callback function will be the only function that is invoked when the corresponding event occurs.

**Parameters**

<i>pCallback</i> [IN]	<ul style="list-style-type: none"> <li>• Callback function pointer (0-Disable)</li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.12    qaGobiApiDcs.h File Reference

Device Connectivity Service API function prototypes.

**Data Structures**

- struct [DcsUsbPortNames](#)
- struct [QosMap](#)
- struct [NetStats](#)

**Macros**

- #define [LEN](#) 10
- #define [PORTNAM\\_LEN](#) 32

## Functions

- [ULONG QCWWAN2kEnumerateDevices](#) (BYTE \*pDevicesSize, BYTE \*pDevices)
- [ULONG QCWWAN2kConnect](#) (CHAR \*pDeviceID, CHAR \*pDeviceKey)
- [ULONG QCWWANDisconnect](#) ()
- [ULONG QCWWAN2kGetConnectedDeviceID](#) (ULONG deviceIDSize, CHAR \*pDeviceID, ULONG deviceKeySize, CHAR \*pDeviceKey)
- [ULONG QCWWANEnumerateDevices](#) (BYTE \*pDevicesSize, BYTE \*pDevices)
- [ULONG QCWWANConnect](#) (CHAR \*pDeviceID, CHAR \*pDeviceKey)
- [ULONG SetSDKImagePath](#) (LPCSTR pPath)
- [ULONG SLQSGetUsbPortNames](#) (struct [DcsUsbPortNames](#) \*pUsbPortNames)
- [ULONG SLQSStart\\_AVAgent](#) (BYTE modem\_index)
- [ULONG SLQSStart](#) (BYTE modem\_index, CHAR \*sn)
- [ULONG SLQSKillSDKProcess](#) ()
- [ULONG SLQSGetDeviceMode](#) (BYTE \*pDeviceMode)
- [ULONG SLQSStartSrv](#) (BYTE action, BYTE mask)
- [ULONG SLQSSetLoggingMask](#) (BYTE mask)
- [ULONG SLQSQosMap](#) (BYTE instance, BYTE dscp, ULONG qos\_id)
- [ULONG SLQSQosEditMap](#) (BYTE instance, BYTE dscp, ULONG qos\_id)
- [ULONG SLQSQosReadMap](#) (BYTE instance, BYTE dscp, ULONG \*qos\_id)
- [ULONG SLQSQosDumpMap](#) (BYTE instance, struct [QosMap](#) \*pmap, BYTE \*plen)
- [ULONG SLQSQosUnmap](#) (BYTE instance, BYTE dscp)
- [ULONG SLQSQosClearMap](#) (BYTE instance)
- [ULONG SLQSGetNetStatistic](#) (struct [NetStats](#) \*pNetStatistic, BYTE instance)

### 9.12.1 Detailed Description

Device Connectivity Service API function prototypes.

### 9.12.2 Macro Definition Documentation

#### 9.12.2.1 #define LEN 10

#### 9.12.2.2 #define PORTNAM\_LEN 32

This structure contains the SLQSGetUsbPortNames Information

#### Parameters

<i>AtCmdPort</i>	[OUT] • Name of AT command port
<i>NmeaPort</i>	[OUT] • Name of NMEA port
<i>DmPort</i>	[OUT] • Name of DM port

#### Note

Technology Supported: UMTS/CDMA  
 Device Supported: MC83x5, MC7700/10/50  
 Timeout: 2 seconds  
[Port](#) names are limited to 32 characters.

### 9.12.3 Function Documentation

#### 9.12.3.1 **ULONG QCWWAN2kConnect** ( **CHAR \* pDeviceID**, **CHAR \* pDeviceKey** )

Connects the Connection Manager API to the first detected QC WWAN device. This function **MUST** be called after QCWWAN2kEnumerateDevices has been called.

##### Parameters

<i>pDeviceID</i> [IN]	<ul style="list-style-type: none"> <li>Device path pertaining to the device for which the API is being invoked e.g. /dev/qcqmio.</li> </ul>
<i>pDeviceKey</i> [IN]	<ul style="list-style-type: none"> <li>Device key pertaining to the device for which the API is being invoked</li> </ul>

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_ERR\_NO\_DEVICE otherwise

##### Note

Timeout: 2 seconds

#### 9.12.3.2 **ULONG QCWWAN2kEnumerateDevices** ( **BYTE \* pDevicesSize**, **BYTE \* pDevices** )

Enumerates the QC WWAN devices currently attached to the host. This API **MUST** be called before any other API.

##### Parameters

<i>pDevicesSize</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>Upon input, maximum number of elements that the device array can contain.</li> <li>Upon successful output, actual number of elements in the device array.</li> </ul>
<i>pDevices</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Device array; array elements are structures with the following elements:            CHAR deviceID[256] - Device path (e.g. /dev/qcqmio)            CHAR deviceKey[16] - Device key stored in the device (e.g. A1000004B01051)</li> </ul>

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_ERR\_NO\_DEVICE on otherwise

##### Note

Timeout: 2 seconds

#### 9.12.3.3 **ULONG QCWWAN2kGetConnectedDeviceID** ( **ULONG deviceIDSize**, **CHAR \* pDeviceID**, **ULONG deviceKeySize**, **CHAR \* pDeviceKey** )

Returns the device ID and device key of the currently connected QC WWAN device.

## Parameters

<i>deviceIDSize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that the device ID array can contain.</li> </ul>
<i>pDeviceID[OUT]</i>	<ul style="list-style-type: none"> <li>Device path string</li> </ul>
<i>deviceKeySize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that the device key array can contain.</li> </ul>
<i>pDeviceKey[OUT]</i>	<ul style="list-style-type: none"> <li>Device key string</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE if device found, eQCWWAN\_ERR\_NO\_DEVICE otherwise

## Note

Timeout: 2 seconds

#### 9.12.3.4 **ULONG QCWWANConnect** ( **CHAR \* pDeviceID**, **CHAR \* pDeviceKey** )

Enumerates the QC WWAN devices currently attached to the host. This API MUST be called before any other API.

## Parameters

<i>pDeviceID[IN]</i>	<ul style="list-style-type: none"> <li>Device path pertaining to the device for which the API is being invoked e.g. /dev/qcqmio.</li> </ul>
<i>pDeviceKey[IN]</i>	<ul style="list-style-type: none"> <li>Device key pertaining to the device for which the API is being invoked</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE if device found, eQCWWAN\_ERR\_NO\_DEVICE otherwise

## Note

Timeout: 2 seconds

This API is deprecated; use [QCWWAN2kConnect\(\)](#) instead

#### 9.12.3.5 **ULONG QCWWANDisconnect** ( )

Disconnects the Connection Manager API from a previously connected QC device. This function de-registers all the callback functions that have been registered.

## Parameters

<i>none</i>	
-------------	--

## Returns

eQCWWAN\_ERR\_NONE

## Note

Timeout: 2 seconds

9.12.3.6 ULONG QCWWANEnumerateDevices ( BYTE \* *pDeviceSize*, BYTE \* *pDevices* )

Enumerates the QC WWAN devices currently attached to the host. This API is deprecated; use [QCWWAN2kEnumerateDevices\(\)](#) instead.

## Parameters

<i>pDeviceSize</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>Upon input, maximum number of elements that the device array can contain.</li> <li>Upon successful output, actual number of elements in the device array.</li> </ul>
<i>pDevices</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Device array; array elements are structures with the following elements:            CHAR deviceId[256] - Device path (e.g. /dev/qcqmio)            CHAR deviceKey[16] - Device key stored in the device</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE

## Note

Timeout: 2 seconds

This API must be called prior to any other APIs.

9.12.3.7 ULONG SetSDKImagePath ( LPCSTR *pPath* )

Set the location of the SLQS executable

## Parameters

<i>pPath</i> [IN]	- Pointer to fully qualified path of SLQS executable (includes the executable file's name)
-------------------	--

## Returns

eQCWWAN\_ERR\_NONE

## Note

Timeout: None

9.12.3.8 ULONG SLQSGetDeviceMode ( BYTE \* *pDeviceMode* )

Returns the Device Mode

## Parameters

<i>pDeviceMode</i> [O-UT]	<ul style="list-style-type: none"> <li>• Pointer to SLQS Device Mode of type <a href="#">eDevState</a></li> </ul>
---------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

### 9.12.3.9 ULONG SLQSGetNetStatistic ( struct NetStats \* pNetStatistic, BYTE instance )

Returns the usbnet statistics for a particular PDN.

## Parameters

	<i>pNetStatistic</i> [O-UT]	<ul style="list-style-type: none"> <li>• Pointer to the structure <a href="#">NetStats</a> which the value of every member is to be retrieved</li> </ul>
in	<i>instance</i>	<ul style="list-style-type: none"> <li>• PDP Instance id</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

### 9.12.3.10 ULONG SLQSGetUsbPortNames ( struct DcsUsbPortNames \* pUsbPortNames )

Returns the Usb [Port](#) Names currently in use.

## Parameters

<i>pUsbPortNames</i> [OUT]	<ul style="list-style-type: none"> <li>• Pointer to SLQS USB <a href="#">Port</a> Names Information</li> </ul>
----------------------------	--



**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.12.3.11 ULONG SLQSKillSDKProcess ( )**

Kill the SDK process

**Parameters**

<i>none</i>	
-------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: N/A

This API useful if the application was started with non-root privileges as subsequent attempt to start any application will fail because the SDK requires root permission to access /dev/qcqm device special files.

**9.12.3.12 ULONG SLQSQosClearMap ( BYTE *instance* )**

Clear Differential Service Code Point(DSCP) to QoS identifier association

**Parameters**

<i>in</i>	<i>instance</i>	<ul style="list-style-type: none"><li>• PDP Instance id</li></ul>
-----------	-----------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.12.3.13 ULONG SLQSQosDumpMap ( BYTE *instance*, struct QosMap \* *pmap*, BYTE \* *plen* )**

Dump all association of Differential Service Code Point(DSCP) with QoS identifier

**Parameters**

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• PDP Instance id</li> </ul>
out	<i>pmap</i>	<ul style="list-style-type: none"> <li>• Pointer to <a href="#">QoSMap</a> struct</li> </ul>
out	<i>plen</i>	<ul style="list-style-type: none"> <li>• number of QoSMap element</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.12.3.14 **ULONG SLQSQosEditMap ( BYTE *instance*, BYTE *dscp*, ULONG *qos\_id* )**

Edit association of Differential Service Code Point(DSCP) with QoS identifier

**Parameters**

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• PDP Instance id</li> </ul>
in	<i>dscp</i>	
in	<i>qos_id</i>	

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.12.3.15 **ULONG SLQSQosMap ( BYTE *instance*, BYTE *dscp*, ULONG *qos\_id* )**

Associate Differential Service Code Point(DSCP) with QoS identifier

**Parameters**

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• PDP Instance id</li> </ul>
in	<i>dscp</i>	
in	<i>qos_id</i>	

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.12.3.16 ULONG SLQSQosReadMap ( BYTE *instance*, BYTE *dscp*, ULONG \* *qos\_id* )

Read association of Differential Service Code Point(DSCP) with QoS identifier

## Parameters

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• PDP Instance id</li> </ul>
in	<i>dscp</i>	
out	<i>qos_id</i>	

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.12.3.17 ULONG SLQSQosUnmap ( BYTE *instance*, BYTE *dscp* )

Remove Differential Service Code Point(DSCP) to QoS identifier association

## Parameters

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• PDP Instance id</li> </ul>
in	<i>dscp</i>	

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.12.3.18 ULONG SLQSSetLoggingMask ( BYTE *mask* )

Limit Syslog messages according to the Mask provided by user

## Parameters

<i>mask</i>	<ul style="list-style-type: none"> <li>• Mask 0x01: disable all log</li> <li>• Mask 0xFF: enable all log</li> </ul>
-------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

**9.12.3.19 ULONG SLQSStart ( BYTE *modem\_index*, CHAR \* *sn* )**

Create the SDK process and IPC sockets for the Application and SDK processes to communicate over.

**Parameters**

in	<i>modem_index</i>	<ul style="list-style-type: none"> <li>• 0: first modem detected</li> <li>• 1: second modem detected</li> <li>• 2: third modem detected</li> <li>• ...</li> <li>• 7: seventh modem detected</li> </ul>
in	<i>sn</i>	This field is optional, it can be serial number or usb path for multiple modem feature, it can be retrieved from sytem command "dmesg" when specified, the modem_index will be mapping to sn or usb path Please set to NULL when not used

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: N/A

**9.12.3.20 ULONG SLQSStart\_AVAgent ( BYTE *modem\_index* )**

Create IPC sockets for AirVantage Agent and SDK processes to communicate over

**Parameters**

<i>none</i>
-------------

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: N/A

**9.12.3.21 ULONG SLQSStartSrv ( BYTE action, BYTE mask )**

Registers/deregisters for service with unsolicited notifications

**Parameters**

<i>action, 1</i> <i>mask</i>	for register, 0 for deregister
	<ul style="list-style-type: none"> <li>• Bit mask for unsolicited notifications <ul style="list-style-type: none"> <li>– Bit0 - WDS</li> <li>– Bit1 - NAS</li> <li>– Bit2 - PDS</li> <li>– Bit3 - VOICE</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds API is useful to register for the services which supports unsolicited notifications. Registration/deregistration can be done by using parameter action if action is set then the mask (set bits) will be used for registering service and if action is "0" mask(set bits) will be used to deregister services. For example : bit mask 0x03 - Registers for services WDS and NAS if action is "1" and deregisters WDS and NAS if action is "0".

**9.13 qaGobiApiDms.h File Reference**

Device Management Service API function prototypes.

**Data Structures**

- struct [serialNumbersInfo](#)
- struct [ERIFileparams](#)
- struct [custFeaturesInfo](#)
- struct [custFeaturesSetting](#)
- struct [dmsCurrentPRLInfo](#)
- struct [FactorySequenceNumber](#)
- struct [CurrImageInfo](#)

- struct [CurrentImgList](#)
- struct [FirmwareUpdatStat](#)
- struct [USBCompParams](#)
- struct [USBCompConfig](#)
- struct [CrashInfo](#)
- struct [CrashInfoParams](#)
- struct [\\_SLQSSwiGetHostDevInfoParams](#)
- struct [\\_SLQSSwiSetHostDevInfoParams](#)
- struct [\\_SLQSSwiGetOSInfoParams](#)
- struct [\\_SLQSSwiSetOSInfoParams](#)
- struct [\\_SLQSSwiGetSerialNoExtParams](#)
- struct [setCustomSettingV2](#)
- struct [getCustomInput](#)
- struct [custSettingInfo](#)
- struct [custSettingList](#)
- struct [getCustomFeatureV2](#)
- struct [getDyingGaspCfg](#)
- struct [setDyingGaspCfg](#)
- struct [getDyingGaspStatistics](#)
- struct [dmsIndicationRegisterReq](#)
- struct [dmsSwiGetResetInfo](#)
- struct [BandCapabilityResp](#)

## Macros

- #define [MAX\\_FSN\\_LENGTH](#) 255
- #define [MAX\\_BUILD\\_ID\\_LEN](#) 255
- #define [UNIQUE\\_ID\\_LEN](#) 16
- #define [IMGDETAILS\\_LEN](#) 16
- #define [MAX\\_CUST\\_ID\\_LEN](#) 64
- #define [MAX\\_CUST\\_VALUE\\_LEN](#) 8
- #define [MAX\\_DYING\\_GASP\\_CFG\\_SMS\\_CONTENT\\_LENGTH](#) 160
- #define [MAX\\_DYING\\_GASP\\_CFG\\_SMS\\_NUMBER\\_LENGTH](#) 20

## Typedefs

- typedef struct [serialNumbersInfo](#) serialNumbersInfo
- typedef struct [ERIFileparams](#) ERIFileparams
- typedef struct [custFeaturesInfo](#) custFeaturesInfo
- typedef struct [custFeaturesSetting](#) custFeaturesSetting
- typedef struct [dmsCurrentPRLInfo](#) dmsCurrentPRLInfo
- typedef struct [\\_SLQSSwiGetHostDevInfoParams](#) SLQSSwiGetHostDevInfoParams
- typedef struct [\\_SLQSSwiSetHostDevInfoParams](#) SLQSSwiSetHostDevInfoParams
- typedef struct [\\_SLQSSwiGetOSInfoParams](#) SLQSSwiGetOSInfoParams
- typedef struct [\\_SLQSSwiSetOSInfoParams](#) SLQSSwiSetOSInfoParams
- typedef struct [\\_SLQSSwiGetSerialNoExtParams](#) SLQSSwiGetSerialNoExtParams

## Functions

- [ULONG GetManufacturer](#) (BYTE stringSize, CHAR \*pString)
- [ULONG GetModelID](#) (BYTE stringSize, CHAR \*pString)
- [ULONG GetFirmwareRevision](#) (BYTE stringSize, CHAR \*pString)
- [ULONG GetFirmwareRevisions](#) (BYTE amssSize, CHAR \*pAMSSString, BYTE bootSize, CHAR \*pBootString, BYTE priSize, CHAR \*pPRIString)
- [ULONG GetPRLVersion](#) (WORD \*pPRLVersion)
- [ULONG GetIMSI](#) (BYTE stringSize, CHAR \*pString)
- [ULONG GetSerialNumbers](#) (BYTE esnSize, CHAR \*pESNString, BYTE imeiSize, CHAR \*pIMEIString, BYTE meidSize, CHAR \*pMEIDString)
- [ULONG SLQSGetSerialNumbers](#) (serialNumbersInfo \*pSerialNumbersInfo)
- [ULONG GetHardwareRevision](#) (BYTE stringSize, CHAR \*pString)
- [ULONG GetNetworkTime](#) (ULONGLONG \*pTimeStamp, ULONG \*pTimeSource)
- [ULONG UIMSetPINProtection](#) (ULONG id, ULONG bEnable, CHAR \*pValue, ULONG \*pVerifyRetriesLeft, ULONG \*pUnblockRetriesLeft)
- [ULONG UIMUnblockPIN](#) (ULONG id, CHAR \*pPUKValue, CHAR \*pNewValue, ULONG \*pVerifyRetriesLeft, ULONG \*pUnblockRetriesLeft)
- [ULONG UIMVerifyPIN](#) (ULONG id, CHAR \*pValue, ULONG \*pVerifyRetriesLeft, ULONG \*pUnblockRetriesLeft)
- [ULONG UIMChangePIN](#) (ULONG id, CHAR \*pOldValue, CHAR \*pNewValue, ULONG \*pVerifyRetriesLeft, ULONG \*pUnblockRetriesLeft)
- [ULONG GetVoiceNumber](#) (BYTE voiceNumberSize, CHAR \*pVoiceNumber, BYTE minSize, CHAR \*pMIN)
- [ULONG SetPower](#) (ULONG powerMode)
- [ULONG GetPower](#) (ULONG \*pPowerMode)
- [ULONG UIMGetControlKeyStatus](#) (ULONG id, ULONG \*pStatus, ULONG \*pVerifyRetriesLeft, ULONG \*pUnblockRetriesLeft)
- [ULONG UIMGetICCID](#) (BYTE stringSize, CHAR \*pString)
- [ULONG UIMGetPINStatus](#) (ULONG id, ULONG \*pStatus, ULONG \*pVerifyRetriesLeft, ULONG \*pUnblockRetriesLeft)
- [ULONG GetOfflineReason](#) (ULONG \*pReasonMask, ULONG \*pbPlatform)
- [ULONG UIMSetControlKeyProtection](#) (ULONG id, ULONG status, CHAR \*pValue, ULONG \*pVerifyRetriesLeft)
- [ULONG UIMUnblockControlKey](#) (ULONG id, CHAR \*pValue, ULONG \*pUnblockRetriesLeft)
- [ULONG GetDeviceCapabilities](#) (ULONG \*pMaxTXChannelRate, ULONG \*pMaxRXChannelRate, ULONG \*pDataServiceCapability, ULONG \*pSimCapability, ULONG \*pRadioIfacesSize, BYTE \*pRadioIfaces)
- [ULONG ResetToFactoryDefaults](#) (CHAR \*pSPC)
- [ULONG ValidateSPC](#) (CHAR \*pSPC)
- [ULONG ActivateAutomatic](#) (CHAR \*pActivationCode)
- [ULONG SLQSGetERIFile](#) (ERIFileparams \*pERIFileparams)
- [ULONG GetActivationState](#) (ULONG \*pActivationState)
- [ULONG SLQSUIMGetState](#) (ULONG \*pUIMState)
- [ULONG SLQSGetBandCapability](#) (ULONGLONG \*pBandCapability)
- [ULONG SLQSGetCustFeatures](#) (custFeaturesInfo \*pCustFeaturesInfo)
- [ULONG SLQSSetCustFeatures](#) (custFeaturesSetting \*pCustFeaturesSetting)
- [ULONG SLQSGetCurrentPRLInfo](#) (dmsCurrentPRLInfo \*pCurrentPRLInfo)
- [ULONG SLQSSwiGetFSN](#) (FactorySequenceNumber \*pFSNumber)
- [ULONG SLQSSwiGetFirmwareCurr](#) (CurrentImgList \*pCurrentImgList)
- [ULONG SLQSSwiGetFwUpdateStatus](#) (FirmwareUpdatStat \*pFirmwareUpdatStat)
- [ULONG SLQSSwiGetUSBComp](#) (USBCompParams \*pUSBCompParams)
- [ULONG SLQSSwiSetUSBComp](#) (USBCompConfig \*pUSBCompConfig)
- [ULONG SLQSSwiGetCrashInfo](#) (BYTE \*pClear, CrashInfoParams \*pCrashInfoParams)
- [ULONG SLQSSwiGetCrashAction](#) (BYTE \*pDevCrashState)
- [ULONG SLQSSwiSetCrashAction](#) (BYTE crashActionParams)
- [ULONG SLQSSwiGetHostDevInfo](#) (SLQSSwiGetHostDevInfoParams \*pGetHostDevInfoParams)

- [ULONG SLQSSwiSetHostDevInfo](#) ([SLQSSwiSetHostDevInfoParams](#) \*pSetHostDevInfoParams)
- [ULONG SLQSSwiGetOSInfo](#) ([SLQSSwiGetOSInfoParams](#) \*pParams)
- [ULONG SLQSSwiSetOSInfo](#) ([SLQSSwiSetOSInfoParams](#) \*pParams)
- [ULONG SLQSSwiGetSerialNoExt](#) ([SLQSSwiGetSerialNoExtParams](#) \*pParams)
- [ULONG SLQSSetCustFeaturesV2](#) ([setCustomSettingV2](#) \*pSetCustSetting)
- [ULONG SLQSGetCustFeaturesV2](#) ([getCustomFeatureV2](#) \*pGetCustomFeatureV2)
- [ULONG SLQSSwiGetDyingGaspCfg](#) ([getDyingGaspCfg](#) \*pConfig)
- [ULONG SLQSSwiSetDyingGaspCfg](#) ([setDyingGaspCfg](#) \*pConfig)
- [ULONG SLQSSwiGetDyingGaspStatistics](#) ([getDyingGaspStatistics](#) \*pStatistics)
- [ULONG SLQSSwiClearDyingGaspStatistics](#) ()
- [ULONG SLQSDmsSwiIndicationRegister](#) ([dmsIndicationRegisterReq](#) \*pIndicationRegisterReq)
- [ULONG SLQSDmsSwiGetResetInfo](#) ([dmsSwiGetResetInfo](#) \*pGetResetInfoResp)
- [ULONG SLQSGetBandCapabilities](#) ([BandCapabilityResp](#) \*pBandCapability)

### 9.13.1 Detailed Description

Device Management Service API function prototypes.

### 9.13.2 Macro Definition Documentation

9.13.2.1 `#define IMGDETAILS_LEN 16`

9.13.2.2 `#define MAX_BUILD_ID_LEN 255`

9.13.2.3 `#define MAX_CUST_ID_LEN 64`

9.13.2.4 `#define MAX_CUST_VALUE_LEN 8`

9.13.2.5 `#define MAX_DYING_GASP_CFG_SMS_CONTENT_LENGTH 160`

9.13.2.6 `#define MAX_DYING_GASP_CFG_SMS_NUMBER_LENGTH 20`

9.13.2.7 `#define MAX_FSN_LENGTH 255`

9.13.2.8 `#define UNIQUE_ID_LEN 16`

### 9.13.3 Typedef Documentation

9.13.3.1 `typedef struct custFeaturesInfo custFeaturesInfo`

This structure contains current settings of custom features



## Parameters

<i>GpsEnable</i> [OUT]	<ul style="list-style-type: none"> <li>describes if GPS is enabled or disabled</li> <li>values: <ul style="list-style-type: none"> <li>0x00 - GPS is disabled</li> <li>0x01 - GPS is enabled</li> </ul> </li> <li>function <a href="#">SLQSGetCustFeatures()</a> returns a default value FFFFFFFF if no value is returned by the modem</li> </ul>
<i>pDisableIMSI</i> [OUT]	<ul style="list-style-type: none"> <li>optional 1 byte parameter</li> <li>describes if IMSI display is enabled or disabled</li> <li>values: <ul style="list-style-type: none"> <li>0x00 - Allow display of IMSI</li> <li>0x01 - Do not display IMSI</li> </ul> </li> <li>function <a href="#">SLQSGetCustFeatures()</a> returns a default value FF if no value is returned by the modem</li> </ul>
<i>pIPFamSupport</i> [OUT]	<ul style="list-style-type: none"> <li>optional 2 byte BitMask</li> <li>bitmask representing the IP families supported</li> <li>values: <ul style="list-style-type: none"> <li>0x01 - IPv4</li> <li>0x02 - IPv6</li> <li>0x04 - IPv4v6</li> </ul> </li> <li>function <a href="#">SLQSGetCustFeatures()</a> returns a default value FFFF if no value is returned by the modem</li> </ul>
<i>pRMAutoConnect</i> [OUT]	<ul style="list-style-type: none"> <li>optional 1 byte parameter</li> <li>QMI Mode RM Net Auto Connect Support</li> <li>values: <ul style="list-style-type: none"> <li>0x00 - Not Supported</li> <li>0x01 - Supported</li> </ul> </li> <li>function <a href="#">SLQSGetCustFeatures()</a> returns a default value FF if no value is returned by the modem</li> </ul>

<i>pGPSSel[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• GPS Antenna Select</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Dedicated GPS <a href="#">Port</a></li> <li>– 0x01 - GPS Rx over AUX <a href="#">Port</a></li> <li>– 0x02 - GPS Rx over dedicated GPS port with no bias voltage applied</li> </ul> </li> <li>• function <a href="#">SLQSGetCustFeatures()</a> returns a default value FF if no value is returned by the modem</li> </ul>
<i>pSMSSupport[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• SMS support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Not supported</li> <li>– 0x01 - supported</li> </ul> </li> <li>• Used to determine whether or not to hide SMS from user</li> <li>• function <a href="#">SLQSGetCustFeatures()</a> returns a default value FF if no value is returned by the modem. In this case assume, SMS is supported.</li> </ul>
<i>plsVoiceEnabled[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• Voice support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Enable voice on both AT and QMI interface (default)</li> <li>– 0x01 - Reserved</li> <li>– 0x02 - Disable voice on both AT and QMI interface</li> </ul> </li> </ul>
<i>pDHCPRelayEnabled[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• DHCP Relay support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Disable DHCP relay</li> <li>– 0x01 - Enable DHCP relay</li> </ul> </li> </ul>

<i>pGPSLPM[OUT]</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• GPSLPM support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Enable GPS in Low Power Mode</li> <li>– 0x01 - Disable GPS in Low Power Mode</li> </ul> </li> </ul>
---------------------	---

### 9.13.3.2 typedef struct custFeaturesSetting custFeaturesSetting

This structure contains settings to be used for custom features

#### Parameters

<i>pGPSSel</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• GPS Antenna Select</li> <li>• values: <ul style="list-style-type: none"> <li>– 0x00 - Dedicated GPS <a href="#">Port</a></li> <li>– 0x01 - GPS Rx over AUX <a href="#">Port</a></li> <li>– 0x02 - GPS Rx over dedicated GPS port with no bias voltage applied</li> </ul> </li> </ul>
<i>pGPSEnable</i>	<ul style="list-style-type: none"> <li>• optional 4 byte parameter</li> <li>• GPS Enable/Disable</li> <li>• values: The value of 7 least significant bits: <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - MT &amp; MO enabled</li> <li>– 2 - MO enabled</li> <li>– 3 - MT enabled</li> <li>– 4 - MT &amp; MO enabled if GPS_DISABLE pin is not asserted</li> <li>– 5 - MO GPS enabled if GPS_DISABLE pin is not asserted</li> <li>– 6 - MT GPS enabled if GPS_DISABLE pin is not asserted</li> </ul> </li> </ul>

**Note**

Only MC7750 3.5.x firmware supports above 0x04, 0x05 and 0x06 settings. To disable GLONASS, set the most significant bit - 0x80. This setting is only applicable if GPS is not Disabled.

**Parameters**

<i>plsVoiceEnabled</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• voice enabled/disabled</li> <li>• values: <ul style="list-style-type: none"> <li>– 0 - Enable voice on both AT and QMI interface (default)</li> <li>– 1 - Reserved</li> <li>– 2 - Disable voice on both AT and QMI interface</li> </ul> </li> </ul>
<i>pDHCPRelay-Enabled</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• DHCPRELAYENABLE support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0 - Disable DHCP relay</li> <li>– 1 - Enable DHCP relay</li> </ul> </li> </ul>
<i>pGPSLPM</i>	<ul style="list-style-type: none"> <li>• optional 1 byte parameter</li> <li>• GPSLPM support</li> <li>• values: <ul style="list-style-type: none"> <li>– 0 - Enable GPS in Low Power Mode</li> <li>– 1 - Disable GPS in Low Power Mode</li> </ul> </li> </ul>

**9.13.3.3 typedef struct dmsCurrentPRLInfo dmsCurrentPRLInfo**

This structure contains GetCurrentPRLInfo response parameter

**Parameters**

<i>pPRLVersion[OUT]</i>	- Optional <ul style="list-style-type: none"> <li>• PRL version of device.</li> </ul>
<i>pPRLPreference</i>	[OUT]- Optional <ul style="list-style-type: none"> <li>• PRL Preference <ul style="list-style-type: none"> <li>– 0 - Unset</li> <li>– 1 - Set</li> </ul> </li> </ul>

## 9.13.3.4 typedef struct ERIFileparams ERIFileparams

This structure contains Extended Roaming Indicator(ERI) file parameters

## Parameters

<i>pFileSize</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Upon input, the maximum number of bytes that file contents array can contain.</li> <li>• Upon successful output, actual number of bytes written to file contents array</li> </ul>
<i>pFile</i> [OUT]	<ul style="list-style-type: none"> <li>• ERI data read from persistent storage( Max size is 1024 )</li> </ul>

## 9.13.3.5 typedef struct serialNumbersInfo serialNumbersInfo

Returns all the serial numbers assigned to the device. These serial numbers include the ESN (Electronic serial number of the device), the IMEI (International Mobile Equipment Identity) and MEID (Mobile Equipment Identifier).

## Parameters

<i>esnSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the ESN string array can contain</li> </ul>
<i>pESNString</i> [OUT]	<ul style="list-style-type: none"> <li>• NULL-terminated ESN string. Empty string is returned when ESN is not supported/programmed</li> </ul>
<i>imeiSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the IMEI string array can contain</li> </ul>
<i>pIMEIString</i> [OUT]	<ul style="list-style-type: none"> <li>• NULL terminated IMEI string. Empty string is returned when IMEI is not supported/programmed</li> </ul>
<i>meidSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the MEID string array can contain</li> </ul>
<i>pMEIDString</i> [OUT]	<ul style="list-style-type: none"> <li>• NULL-terminated MEID string. Empty string is returned when MEID is not supported/programmed</li> </ul>
<i>imeiSvnSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the IMEI SVN string array can contain.</li> </ul>

<i>pImeiSvnString</i> [-OUT]	<ul style="list-style-type: none"> <li>• NULL-terminated IMEI SVN string. Empty string is returned when IMEI SVN is not supported/programmed.</li> </ul>
------------------------------	--

#### 9.13.3.6 typedef struct \_SLQSSwiGetHostDevInfoParams SLQSSwiGetHostDevInfoParams

This structure is used to Get Host Device Information

##### Parameters

<i>bManSize</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Host Device Manufacturer String Size</li> </ul>
<i>pManString</i> [OUT]	<ul style="list-style-type: none"> <li>• Host Device Manufacturer Name(Optional parameter)</li> <li>• Null terminated ASCII String</li> </ul>
<i>bModelSize</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Host Device Model String Size</li> </ul>
<i>pModelString</i> [OUT]	<ul style="list-style-type: none"> <li>• Host Device Model String(Optional parameter)</li> <li>• Null terminated ASCII string.</li> </ul>
<i>bSWVerSize</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Host Device Software Version String Size</li> </ul>
<i>pSWVerString</i> [-OUT]	<ul style="list-style-type: none"> <li>• Host Device Software Version String(Optional parameter)</li> <li>• Null terminated ASCII string</li> </ul>
<i>bPlasmaIDSize</i> [-IN/OUT]	<ul style="list-style-type: none"> <li>• Host Device Plasma ID String Size</li> </ul>
<i>pPlasmaIDString</i> [OUT]	<ul style="list-style-type: none"> <li>• Host Device Plasma ID String(Optional parameter)</li> <li>• Null terminated alphanumeric ASCII String.</li> </ul>

#### 9.13.3.7 typedef struct \_SLQSSwiGetOSInfoParams SLQSSwiGetOSInfoParams

This structure is used to Get OS Information

## Parameters

<i>bNameSize</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>Size of Operating System Name</li> </ul>
<i>pNameString</i> [OUT]	<ul style="list-style-type: none"> <li>Operating System Name(Optional parameter)</li> <li>Null terminated ASCII string</li> </ul>
<i>bVersionSize</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Operating System Version Size</li> </ul>
<i>pVersionString</i> [OUT]	<ul style="list-style-type: none"> <li>Operating System Version String(Optional parameter)</li> <li>Null terminated ASCII string.</li> </ul>

## 9.13.3.8 typedef struct \_SLQSSwiGetSerialNoExtParams SLQSSwiGetSerialNoExtParams

This structure is used to store MEID Information

## Parameters

<i>meidLength</i> [OUT]	<ul style="list-style-type: none"> <li>String length of the of MEID received</li> </ul>
<i>pMeidString</i> [OUT]	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Pointer to receive String containing the Mobile Equipment Identifier(MEID) of the device.</li> </ul>

## 9.13.3.9 typedef struct \_SLQSSwiSetHostDevInfoParams SLQSSwiSetHostDevInfoParams

This structure is used to Set Host Device Information

## Parameters

<i>bManSize</i> [IN]	<ul style="list-style-type: none"> <li>• Host Device Manufacturer String Size</li> </ul>
<i>pManString</i> [IN]	<ul style="list-style-type: none"> <li>• Host Device Manufacturer Name(Optional parameter)</li> <li>• Null terminated ASCII String</li> </ul>
<i>bModelSize</i> [IN]	<ul style="list-style-type: none"> <li>• Host Device Model String Size</li> </ul>
<i>pModelString</i> [IN]	<ul style="list-style-type: none"> <li>• Host Device Model String(Optional parameter)</li> <li>• Null terminated ASCII string.</li> </ul>
<i>bSWVerSize</i> [IN]	<ul style="list-style-type: none"> <li>• Host Device Software Version String Size</li> </ul>
<i>pSWVerString</i> [I-N]	<ul style="list-style-type: none"> <li>• Host Device Software Version String(Optional parameter)</li> <li>• Null terminated ASCII string</li> </ul>
<i>bPlasmaIDSize</i> [IN]	<ul style="list-style-type: none"> <li>• Host Device Plasma ID String Size</li> </ul>
<i>pPlasmaID-String</i> [IN]	<ul style="list-style-type: none"> <li>• Host Device Plasma ID String(Optional parameter)</li> <li>• Null terminated alphanumeric ASCII String.</li> </ul>

## 9.13.3.10 typedef struct \_SLQSSwiSetOSInfoParams SLQSSwiSetOSInfoParams

This structure is used to Set OS Information



## Parameters

<i>bNameSize</i> [IN]	<ul style="list-style-type: none"> <li>• Size of Operating System Name</li> </ul>
<i>pNameString</i> [IN]	<ul style="list-style-type: none"> <li>• Operating System Name(Optional parameter)</li> <li>• Null terminated ASCII string</li> </ul>
<i>bVersionSize</i> [IN]	<ul style="list-style-type: none"> <li>• Operating System Version Size</li> </ul>
<i>pVersionString</i> [I-N]	<ul style="list-style-type: none"> <li>• Operating System Version String(Optional parameter)</li> <li>• Null terminated ASCII string.</li> </ul>

## 9.13.4 Function Documentation

9.13.4.1 ULONG ActivateAutomatic ( CHAR \* *pActivationCode* )

Requests the device to perform automatic service activation

## Parameters

<i>pActivationCode</i> [IN]	<ul style="list-style-type: none"> <li>• NULL-terminated string representing activation code (maximum string length of 12); specific carrier requirements may dictate actual activation code that is applicable, e.g., "*22899"</li> </ul>
-----------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Minutes

9.13.4.2 ULONG GetActivationState ( ULONG \* *pActivationState* )

Returns the device activation state.

## Parameters

<i>pActivation-State[OUT]</i>	<ul style="list-style-type: none"> <li>• Service Activation Code</li> <li>0 - Service not activated</li> <li>1 - Service activated</li> <li>2 - Activation connecting</li> <li>3 - Activation connected</li> <li>4 - OTASP security authenticated</li> <li>5 - OTASP NAM downloaded</li> <li>6 - OTASP MDN downloaded</li> <li>7 - OTASP IMSI downloaded</li> <li>8 - OTASP PRL downloaded</li> <li>9 - OTASP SPC downloaded</li> <li>10 - OTASP settings committed</li> </ul>
-------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA  
Timeout: 2 Seconds

#### 9.13.4.3 ULONG GetDeviceCapabilities ( ULONG \* pMaxTXChannelRate, ULONG \* pMaxRXChannelRate, ULONG \* pDataServiceCapability, ULONG \* pSimCapability, ULONG \* pRadiolfacesSize, BYTE \* pRadiolfaces )

Gets the device capabilities

## Parameters

<i>pMaxTX-ChannelRate[OUT]</i>	<ul style="list-style-type: none"> <li>• Maximum transmission rate (in bps) supported by the device</li> <li>• In multi-technology devices, this value will be the greatest rate among all supported technologies</li> </ul>
<i>pMaxRX-ChannelRate[OUT]</i>	<ul style="list-style-type: none"> <li>• Maximum reception rate (in bps) supported by the device</li> <li>• In multi-technology devices, this value will be the greatest rate among all supported technologies</li> </ul>

<i>pDataServiceCapability[OUT]</i>	<ul style="list-style-type: none"> <li>CS/PS data service capability <ul style="list-style-type: none"> <li>0 - No data services supported</li> <li>1 - Only Circuit Switched (CS) services supported</li> <li>2 - Only Packet Switched (PS) services supported</li> <li>3 - Simultaneous CS and PS</li> <li>4 - Non-simultaneous CS and PS</li> </ul> </li> </ul>
<i>pSimCapability[OUT]</i>	<ul style="list-style-type: none"> <li>Device SIM capability <ul style="list-style-type: none"> <li>0 - SIM not supported</li> <li>1 - SIM supported</li> </ul> </li> </ul>
<i>pRadioIfaceSize[IN/OUT]</i>	<ul style="list-style-type: none"> <li>Upon input, the maximum number of elements that the radio interface array can contain</li> <li>Upon successful output, actual number of elements in the radio interface array</li> </ul>
<i>pRadioIface[OUT]</i>	<ul style="list-style-type: none"> <li>Radio interface array. This is a structure of array containing the elements below. ULONG radioInterface <ul style="list-style-type: none"> <li>See <a href="#">qaGobiApiTableRadioInterfaces.h</a> for Radio Interfaces</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.13.4.4 ULONG GetFirmwareRevision ( BYTE stringSize, CHAR \* pString )**

Returns the device firmware revision

**Parameters**

<i>stringSize</i>	<ul style="list-style-type: none"> <li>The maximum number of characters (including NULL terminator) that the string array can contain</li> </ul>
-------------------	--

<i>pString[OUT]</i>	<ul style="list-style-type: none"> <li>• NULL terminated string</li> </ul>
---------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

#### 9.13.4.5 **ULONG** GetFirmwareRevisions ( **BYTE** *amssSize*, **CHAR** \* *pAMSSString*, **BYTE** *bootSize*, **CHAR** \* *pBootString*, **BYTE** *priSize*, **CHAR** \* *pPRIString* )

Returns the device firmware revisions (AMSS, boot, and PRI)

**Parameters**

<i>amssSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that the AMSS string array can contain</li> </ul>
<i>pAMSSString[OUT]</i>	<ul style="list-style-type: none"> <li>• NULL-terminated AMSS revision string</li> </ul>
<i>bootSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that the boot string array can contain</li> </ul>
<i>pBootString[OUT]</i>	<ul style="list-style-type: none"> <li>• NULL-terminated boot code revision string</li> </ul>
<i>priSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that the PRI string array can contain</li> </ul>
<i>pPRIString[OUT]</i>	<ul style="list-style-type: none"> <li>• NULL-terminated PRI revision string</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

#### 9.13.4.6 ULONG GetHardwareRevision ( BYTE *stringSize*, CHAR \* *pString* )

Returns the hardware revision of the device

## Parameters

<i>stringSize</i>	<ul style="list-style-type: none"><li>• The maximum number of characters (including NULL terminator) that the string array can contain</li></ul>
<i>pString[OUT]</i>	<ul style="list-style-type: none"><li>• NULL terminated string</li></ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.13.4.7 ULONG GetIMSI ( BYTE *stringSize*, CHAR \* *pString* )**

Returns the device IMSI. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use [SLQSUIReadTransparent\(\)](#)(EF ID: 3F00 7F20 6F07 for 2G card and 3F00 7FFF 6F07 for 3G card) instead for new firmware versions and new modules.

## Parameters

<i>stringSize</i>	<ul style="list-style-type: none"><li>• The maximum number of characters (including NULL terminator) that the string array can contain</li></ul>
<i>pString[OUT]</i>	<ul style="list-style-type: none"><li>• NULL terminated string</li></ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.13.4.8 ULONG GetManufacturer ( BYTE *stringSize*, CHAR \* *pString* )**

Returns the device manufacturer name

## Parameters

<i>stringSize</i>	<ul style="list-style-type: none"> <li>The maximum number of characters (including NULL terminator) that the string array can contain.</li> </ul>
<i>pString[OUT]</i>	<ul style="list-style-type: none"> <li>NULL terminated string</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.13.4.9 ULONG GetModelID ( BYTE *stringSize*, CHAR \* *pString* )

Returns the device model ID

## Parameters

<i>stringSize</i>	<ul style="list-style-type: none"> <li>The maximum number of characters (including NULL terminator) that the string array can contain</li> </ul>
<i>pString[OUT]</i>	<ul style="list-style-type: none"> <li>NULL terminated string</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.13.4.10 ULONG GetNetworkTime ( ULONGLONG \* *pTimeStamp*, ULONG \* *pTimeSource* )

Returns the current time of the device based on the value supported by the network.

## Parameters

<i>pTimeStamp</i> [O-UT]	<ul style="list-style-type: none"> <li>Count of 1.25 ms that have elapsed from the start of GPS time (Jan 6, 1980)</li> </ul>
<i>pTimeSource</i> [O-UT]	<ul style="list-style-type: none"> <li>Source of timestamp               <ul style="list-style-type: none"> <li>0 - 32 kHz device clock</li> <li>1 - CDMA network</li> <li>2 - cdma2000 1xEV-DO network</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

The source of the timestamp provided specifies how the timestamp was determined. The first network time that is available will be returned. If no network time is available, the timestamp is taken from the 32 kHz slow-clock of the device.

#### 9.13.4.11 ULONG GetOfflineReason ( ULONG \* *pReasonMask*, ULONG \* *pbPlatform* )

Returns reason why the operating mode of the device is currently offline.

## Parameters

<i>pReasonMask</i> [OUT]	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Bitmask of offline reasons               <ul style="list-style-type: none"> <li>0x00000001 - Host image configuration issue</li> <li>0x00000002 - PRI image configuration issue</li> <li>0x00000004 - PRI version incompatible</li> <li>0x00000008 - PRI copy issue</li> <li>All others - Reserved</li> </ul> </li> </ul>
--------------------------	--



<i>pbPlatform[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Is the device offline due to a platform restriction? <ul style="list-style-type: none"> <li>– 0 - No</li> <li>– 1 - Yes</li> </ul> </li> </ul>
------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Seconds

**9.13.4.12 ULONG GetPower ( ULONG \* pPowerMode )**

Returns the operating mode of the device.

**Parameters**

<i>pPowerMode[OUT]</i>	<ul style="list-style-type: none"> <li>• Selected operating mode <ul style="list-style-type: none"> <li>– See <a href="#">qaGobiApiTablePowerModes.h</a> for power modes</li> </ul> </li> </ul>
------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Seconds

**9.13.4.13 ULONG GetPRLVersion ( WORD \* pPRLVersion )**

Returns the version of the active Preferred Roaming List (PRL) in use by the device.

## Parameters

<i>pPRLVersion</i> [O-UT]	<ul style="list-style-type: none"> <li>PRL version number</li> </ul>
---------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.13.4.14 ULONG GetSerialNumbers ( BYTE *esnSize*, CHAR \* *pESNString*, BYTE *imeiSize*, CHAR \* *pIMEIString*, BYTE *meidSize*, CHAR \* *pMEIDString* )

Returns all the serial numbers assigned to the device. These serial numbers include the ESN (Electronic serial number of the device), the IMEI (International Mobile Equipment Identity) and MEID (Mobile Equipment Identifier).

## Parameters

<i>esnSize</i>	<ul style="list-style-type: none"> <li>The maximum number of characters (including NULL terminator) that the ESN string array can contain</li> </ul>
<i>pESNString</i> [O-UT]	<ul style="list-style-type: none"> <li>NULL-terminated ESN string. Empty string is returned when ESN is not supported/programmed</li> </ul>
<i>imeiSize</i>	<ul style="list-style-type: none"> <li>The maximum number of characters (including NULL terminator) that the IMEI string array can contain</li> </ul>
<i>pIMEIString</i> [O-UT]	<ul style="list-style-type: none"> <li>NULL terminated IMEI string. Empty string is returned when IMEI is not supported/programmed</li> </ul>
<i>meidSize</i>	<ul style="list-style-type: none"> <li>The maximum number of characters (including NULL terminator) that the MEID string array can contain</li> </ul>
<i>pMEIDString</i> [O-UT]	<ul style="list-style-type: none"> <li>NULL-terminated MEID string. Empty string is returned when MEID is not supported/programmed</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

For CDMA devices that use a RUIM, the MEID of the RUIM (if present) will be returned. Use [SLQSSwiGetSerialNoExt\(\)](#) to get MEID of CDMA modems. Timeout: 2 seconds

#### 9.13.4.15 ULONG GetVoiceNumber ( BYTE voiceNumberSize, CHAR \* pVoiceNumber, BYTE minSize, CHAR \* pMIN )

Returns the voice number in use by the device

## Parameters

<i>voiceNumberSize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that the voice number array can contain.</li> </ul>
<i>pVoiceNumber[OUT]</i>	<ul style="list-style-type: none"> <li>Voice number string: MDN or MS ISDN</li> </ul>
<i>minSize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that the MIN array can contain.</li> </ul>
<i>pMIN[OUT]</i>	<ul style="list-style-type: none"> <li>Optional Parameter</li> <li>MIN string: Empty string returned when MIN is not supported/ programmed.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.13.4.16 ULONG ResetToFactoryDefaults ( CHAR \* pSPC )

Resets to default factory settings of the device

## Parameters

<i>pSPC[IN]</i>	<ul style="list-style-type: none"> <li>NULL-terminated string representing a six-digit service programming code</li> </ul>
-----------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 minutes

**9.13.4.17 ULONG SetPower ( ULONG powerMode )**

Sets the operating mode of the device.

**Parameters**

<i>powerMode[IN]</i>	<ul style="list-style-type: none"> <li>Selected operating mode             <ul style="list-style-type: none"> <li>See <a href="#">qaGobiApiTablePowerModes.h</a> for power modes</li> </ul> </li> </ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS/CDMA  
 Device Supported: MC83x5, MC7700/50  
 Timeout: 2 seconds

**9.13.4.18 ULONG SLQSDmsSwiGetResetInfo ( dmsSwiGetResetInfo \* pGetResetInfoResp )**

This function is used to get reset info

**Parameters**

<i>pGetResetInfo-Resp</i>	<ul style="list-style-type: none"> <li>See <a href="#">dmsSwiGetResetInfo</a> for more information of the input structure</li> </ul>
---------------------------	--

**9.13.4.19 ULONG SLQSDmsSwiIndicationRegister ( dmsIndicationRegisterReq \* pIndicationRegisterReq )**

This function used to set Swi Indication Register

## Parameters

<i>pConfig</i>	<ul style="list-style-type: none"><li>• See <a href="#">dmsIndicationRegisterReq</a> for more information of the input structure</li></ul>
----------------	--

**9.13.4.20   ULONG SLQSGetBandCapabilities ( BandCapabilityResp \* pBandCapability )**

Returns the band capability of the device.

## Parameters

<i>pBand-Capability[OUT]</i>	See <a href="#">BandCapabilityResp</a> for more information of the input structure
------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

**9.13.4.21   ULONG SLQSGetBandCapability ( ULONGLONG \* pBandCapability )**

Returns the band capability of the device.

## Parameters

<p><i>pBand-Capability</i>[OUT]</p>	<p>Bitmask of bands supported by the device</p> <ul style="list-style-type: none"> <li>• Bit 0 - Band class 0, A-system</li> <li>• Bit 1 - Band class 0, B-system</li> <li>• Bit 2 - Band class 1, all blocks</li> <li>• Bit 3 - Band class 2</li> <li>• Bit 4 - Band class 3, A-system</li> <li>• Bit 5 - Band class 4, all blocks</li> <li>• Bit 6 - Band class 5, all blocks</li> <li>• Bit 7 - GSM DCS band (1800)</li> <li>• Bit 8 - GSM Extended GSM (E-GSM) band (900)</li> <li>• Bit 9 - GSM Primary GSM (P-GSM) band (900)</li> <li>• Bit 10 - Band class 6</li> <li>• Bit 11 - Band class 7</li> <li>• Bit 12 - Band class 8</li> <li>• Bit 13 - Band class 9</li> <li>• Bit 14 - Band class 10</li> <li>• Bit 15 - Band class 11</li> <li>• Bit 16 - GSM 450 band</li> <li>• Bit 17 - GSM 480 band</li> <li>• Bit 18 - GSM 750 band</li> <li>• Bit 19 - GSM 850 band</li> <li>• Bit 20 - GSM railways GSM band (900)</li> <li>• Bit 21 - GSM PCS band (1900)</li> <li>• Bit 22 - WCDMA (Europe, Japan, and China) 2100 band</li> <li>• Bit 23 - WCDMA US PCS 1900 band</li> <li>• Bit 24 - WCDMA (Europe and China) DCS 1800 band</li> <li>• Bit 25 - WCDMA US 1700 band</li> <li>• Bit 26 - WCDMA US 850 band</li> <li>• Bit 27 - WCDMA Japan 800 band</li> <li>• Bit 28 - Band class 12</li> <li>• Bit 29 - Band class 14</li> <li>• Bit 30 - Reserved</li> <li>• Bit 31 - Band class 15</li> <li>• Bits 32 through 47 - Reserved</li> <li>• Bit 48 - WCDMA Europe 2600 band</li> </ul>
	<ul style="list-style-type: none"> <li>• Bit 49 - WCDMA Europe and Japan 900 band</li> <li>• Bit 50 - WCDMA Japan 1700 band</li> <li>• Bits 51 through 55 - Reserved</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Seconds

**9.13.4.22 ULONG SLQSGetCurrentPRLInfo ( dmsCurrentPRLInfo \* pCurrentPRLInfo )**

This API get the currently active PRL information of the device.

**Parameters**

<i>pCurrentPRLInfo</i>	<ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">dmsCurrentPRLInfo</a></li> <li>• See <a href="#">dmsCurrentPRLInfo</a> for more information</li> </ul>
------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 2 Secs

**9.13.4.23 ULONG SLQSGetCustFeatures ( custFeaturesInfo \* pCustFeaturesInfo )**

This API fetches the current settings of custom features. This API is deprecated for EM74xx/MC74xx, please use [SLQSGetCustFeaturesV2\(\)](#) instead for EM74xx/MC74xx.

**Parameters**

<i>pCustFeatures-Info</i>	<ul style="list-style-type: none"> <li>• Structure containing settings of custom features.</li> <li>• See <a href="#">custFeaturesInfo</a> for more information</li> </ul>
---------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Secs

#### 9.13.4.24 **ULONG** SLQSGetCustFeaturesV2 ( **getCustomFeatureV2** \* *pGetCustomFeatureV2* )

This function queries the modem for a list of supported features. This function is for firmware version 2.0 and newer. Currently supported Customization features:

- GPIOSARENABLE
- GPSSEL
- IMSWITCHHIDE
- IPV6ENABLE
- WAKEHOSTEN

##### Parameters

<i>pGetCustom-FeatureV2</i>	<ul style="list-style-type: none"> <li>• See <a href="#">getCustomFeatureV2</a> for more information of the input structure</li> </ul>
-----------------------------	--

#### 9.13.4.25 **ULONG** SLQSGetERIFile ( **ERIFileparams** \* *pERIFileparams* )

Returns the Extended Roaming Indicator (ERI) file that is stored in EFS on the device at a predetermined location. See the carrier requirements for specific details.

##### Parameters

<i>pERIFileparams</i>	<ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">ERIFileparams</a></li> <li>• See <a href="#">ERIFileparams</a> for more information</li> </ul>
-----------------------	--

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Technology Supported: CDMA  
Timeout: 5 Seconds

#### 9.13.4.26 **ULONG** SLQSGetSerialNumbers ( **serialNumbersInfo** \* *pSerialNumbersInfo* )

Returns all the serial numbers assigned to the device. These serial numbers include the ESN (Electronic serial number of the device), the IMEI (International Mobile Equipment Identity), MEID (Mobile Equipment Identifier) and IMEI SVN (IMEI software version number).

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise



## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

For CDMA devices that use a RUIM, the MEID of the RUIM (if present) will be returned. Use [SLQSSwiGetSerialNoExt\(\)](#) to get MEID of CDMA modems. Timeout: 2 seconds

#### 9.13.4.27 ULONG SLQSSetCustFeatures ( custFeaturesSetting \* pCustFeaturesSetting )

This API changes the settings of custom features, a reset is required for any settings that are changed to take effect. This API is deprecated for EM74xx/MC74xx, please use [SLQSSetCustFeaturesV2\(\)](#) for EM74xx/MC74xx.

## Parameters

<i>pCustFeaturesSetting</i> [IN]	<ul style="list-style-type: none"> <li>• Structure containing settings of custom features.</li> <li>• See <a href="#">custFeaturesSetting</a> for more information</li> </ul>
----------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Secs

#### 9.13.4.28 ULONG SLQSSetCustFeaturesV2 ( setCustomSettingV2 \* pSetCustSetting )

This function sets the modem for a list of supported features. This function is for firmware version 2.0 and newer. Currently supported customization features:

- GPIOSARENABLE
- GPSSEL
- IMSWITCHHIDE
- IPV6ENABLE
- WAKEHOSTEN

## Parameters

<i>pSetCustSetting</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• See <a href="#">setCustomSettingV2</a> for more information</li> </ul>
------------------------	---

#### 9.13.4.29 **ULONG SLQSSwiClearDyingGaspStatistics ( )**

This function Clear Dying GASP Statistics.

#### 9.13.4.30 **ULONG SLQSSwiGetCrashAction ( BYTE \* *pDevCrashState* )**

This API queries the Crash State from the device.

##### Parameters

<i>pDevCrashState</i> [OUT]	<ul style="list-style-type: none"> <li>• Device Crash State</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - USB Memory Download Modem will reset after a crash and will stay in USB download mode with only ttyUSB0 enumerated. ramdump tool is to be used to recover the crash dump. Modem needs to be reset again to come back in ONLINE mode.</li> <li>– 1 - Reset Modem will reset and come back in ONLINE mode. Minimal crash data will be available and can be extracted with at!gcdump? AT command or <a href="#">SLQSSwiGetCrashInfo()</a> SDK API</li> <li>– 2 - No action</li> </ul> </li> </ul>
-----------------------------	--

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Technology Supported: NA

Please free two buffers after get crash report successfully

1. pCrashInfoParams->pCrashInfo->pCrashString
2. pCrashInfoParams->pCrashInfo->pGCDumpString Timeout: 5 Secs

#### 9.13.4.31 **ULONG SLQSSwiGetCrashInfo ( BYTE \* *pClear*, CrashInfoParams \* *pCrashInfoParams* )**

This API queries the Crash Information from the device.

##### Parameters

<i>pClear</i> [IN]	<ul style="list-style-type: none"> <li>• request parameter Clear(Optional parameter)</li> <li>• Values: 0 - Do not clear crash data after response 1 - Clear crash data after response</li> </ul>
--------------------	---

<i>pCrashInfo-Params[Out]</i>	<ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">CrashInfoParams</a></li> <li>• See <a href="#">CrashInfoParams</a> for more information</li> </ul>
-------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
Timeout: 5 Secs

**9.13.4.32 ULONG SLQSSwiGetDyingGaspCfg ( getDyingGaspCfg \* pConfig )**

This function queries Dying GASP Config.

**Parameters**

<i>pGetCustom-FeatureV2</i>	<ul style="list-style-type: none"> <li>• See <a href="#">getDyingGaspCfg</a> for more information of the input structure *</li> </ul>
-----------------------------	---

**9.13.4.33 ULONG SLQSSwiGetDyingGaspStatistics ( getDyingGaspStatistics \* pStatistics )**

This function queries Dying GASP Statistics.

**Parameters**

<i>pStatistics</i>	<ul style="list-style-type: none"> <li>• See <a href="#">getDyingGaspStatistics</a> for more information of the input structure *</li> </ul>
--------------------	--

**9.13.4.34 ULONG SLQSSwiGetFirmwareCurr ( CurrentImgList \* pCurrentImgList )**

This API gets the currently active images on the device.

**Parameters**

<i>pCurrentImgList</i>	<ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">CurrentImgList</a></li> <li>• See <a href="#">CurrentImgList</a> for more information</li> </ul>
------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
 Device Supported: MC73xx  
 Timeout: 5 Secs

**9.13.4.35 ULONG SLQSSwiGetFSN ( FactorySequenceNumber \* pFSNumber )**

This API get the Factory Sequence Number of the device.

**Parameters**

<i>pFSNumber</i>	<ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">FactorySequenceNumber</a></li> <li>• See <a href="#">FactorySequenceNumber</a> for more information</li> </ul>
------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
 Timeout: 5 Secs

**9.13.4.36 ULONG SLQSSwiGetFwUpdateStatus ( FirmwareUpdatStat \* pFirmwareUpdatStat )**

This API will be used to query last firmware update status. The firmware status is stored in RAM and can be retained over warm resets but not power off resets.

**Parameters**

<i>pFirmware-UpdatStat</i>	<ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">FirmwareUpdatStat</a></li> <li>• See <a href="#">FirmwareUpdatStat</a> for more information</li> </ul>
----------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
 Device Supported: MC73xx  
 Timeout: 5 Secs

**9.13.4.37    ULONG SLQSSwiGetHostDevInfo ( SLQSSwiGetHostDevInfoParams \* *pGetHostDevInfoParams* )**

This API Get Host Information from the device.

**Parameters**

<i>pGetHostDev- InfoParams</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SLQSSwiGetHostDevInfoParams</a> for more information</li> </ul>
------------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA

Timeout: 2 Secs

**9.13.4.38    ULONG SLQSSwiGetOSInfo ( SLQSSwiGetOSInfoParams \* *pParams* )**

This API queries the device operating system info configured on the modem for OMA-DM reporting

**Parameters**

<i>pParams</i>	<ul style="list-style-type: none"> <li>• - See <a href="#">SLQSSwiGetOSInfoParams</a> for more information</li> </ul>
----------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA

Timeout: 2 Secs

**9.13.4.39    ULONG SLQSSwiGetSerialNoExt ( SLQSSwiGetSerialNoExtParams \* *pParams* )**

This API is used to get the MEID of the modem. For CDMA devices that use a RUIM, the MEID of the modem will always be returned.

**Parameters**

<i>SLQSSwiGet-SerialNoExt-Params</i>	
--------------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
Timeout: 5 Secs

**9.13.4.40    ULONG SLQSSwiGetUSBComp (    USBCompParams \* *pUSBCompParams* )**

This API queries the modem's USB interface configuration and supported configuration parameters.

**Parameters**

<i>pUSBComp-Params</i>	<ul style="list-style-type: none"><li>• Pointer to structure <a href="#">USBCompParams</a></li><li>• See <a href="#">USBCompParams</a> for more information</li></ul>
------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
Timeout: 5 Secs

**9.13.4.41    ULONG SLQSSwiSetCrashAction (    BYTE *crashActionParams* )**

This API set the Crash Action to the device.

## Parameters

<i>crashAction-Params</i> [IN]	<ul style="list-style-type: none"> <li>• Crash Action</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - USB Memory Download Modem will reset after a crash and will stay in USB download mode with only ttyUSB0 enumerated. ramdump tool is to be used to recover the crash dump. Modem needs to be reset again to come back in ONLINE mode.</li> <li>– 1 - Reset Modem will reset and come back in ONLINE mode. Minimal crash data will be available and can be extracted with at!gcdump? AT command or <a href="#">SLQSSwiGetCrashInfo()</a> SDK API</li> <li>– 2 - No action</li> </ul> </li> </ul>
--------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: NA  
Timeout: 5 Secs

9.13.4.42 **ULONG** SLQSSwiSetDyingGaspCfg ( **setDyingGaspCfg** \* *pConfig* )

This function set Dying GASP Config.

## Parameters

<i>pConfig</i>	<ul style="list-style-type: none"> <li>• See <a href="#">setDyingGaspCfg</a> for more information of the input structure</li> </ul>
----------------	---

9.13.4.43 **ULONG** SLQSSwiSetHostDevInfo ( **SLQSSwiSetHostDevInfoParams** \* *pSetHostDevInfoParams* )

This API Sets the host device info configured on the modem for OMA-DM reporting

## Parameters

<i>pSetHostDev-InfoParams</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SLQSSwiSetHostDevInfoParams</a> for more information</li> </ul>
-------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
Timeout: 2 Secs

**9.13.4.44 ULONG SLQSSwiSetOSInfo ( SLQSSwiSetOSInfoParams \* *pParams* )**

This API Set OS Information to the device.

**Parameters**

<i>pParams</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SLQSSwiSetOSInfoParams</a> for more information</li> </ul>
----------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
Timeout: 2 Secs

**9.13.4.45 ULONG SLQSSwiSetUSBComp ( USBCompConfig \* *pUSBCompConfig* )**

This API is used to change the modem's USB interface configuration thus allowing a device to have multiple USB compositions. Devices will, by default, be configured to support a minimal set of interfaces to reduce end user modem installation time. Developers and some customers, however, require access to a custom set of interfaces. A reset is required for any change in the USB composition to take effect.

**Parameters**

<i>pUSBCompConfig</i>	<ul style="list-style-type: none"> <li>• Pointer to structure <a href="#">USBCompConfig</a></li> <li>• See <a href="#">USBCompConfig</a> for more information</li> </ul>
-----------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
Timeout: 5 Secs



#### 9.13.4.46 ULONG SLQSUIMGetState ( ULONG \* pUIMState )

Returns the UIM state. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSUIMGetCardStatus\(\)](#) for new firmware versions and new modules

##### Parameters

<i>pUIMState[OUT]</i>	<ul style="list-style-type: none"><li>• UIM state:<ul style="list-style-type: none"><li>– 0x00 - UIM initialization completed</li><li>– 0x01 - UIM locked or failed</li><li>– 0x02 - UIM not present</li><li>– 0x03 - 0xFE - Reserved</li><li>– 0xFF - UIM state currently unavailable</li></ul></li></ul>
-----------------------	--

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Timeout: 2 Seconds

#### 9.13.4.47 ULONG UIMChangePIN ( ULONG id, CHAR \* pOldValue, CHAR \* pNewValue, ULONG \* pVerifyRetriesLeft, ULONG \* pUnblockRetriesLeft )

Changes the PIN value for a given PIN. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSUIMChangePin\(\)](#) for new firmware versions and new modules

##### Parameters

<i>id[IN]</i>	<ul style="list-style-type: none"><li>• PIN ID<ul style="list-style-type: none"><li>– 1 ( PIN1 / CHV1 )</li><li>– 2 ( PIN2 / CHV2 )</li></ul></li></ul>
---------------	---

<i>pOldValue[IN]</i>	<ul style="list-style-type: none"> <li>• Old PIN value of PIN to change</li> </ul>
<i>pNewValue[IN]</i>	<ul style="list-style-type: none"> <li>• New PIN value of PIN to change</li> </ul>
<i>pVerifyRetriesLeft[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Upon operational failure, this will indicate number of retries left, after which PIN will be blocked. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pUnblockRetriesLeft[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Upon operational failure, this will indicate number of unblock retries left, after which the PIN will be permanently blocked; i.e. UIM is unusable. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

Timeout: 5 seconds

**9.13.4.48** `ULONG UIMGetControlKeyStatus ( ULONG id, ULONG * pStatus, ULONG * pVerifyRetriesLeft, ULONG * pUnblockRetriesLeft )`

Returns the status of the specified UIM facility control key. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use SLQSUIMGetConfiguration instead for new firmware versions and new modules.

## Parameters

<i>id</i> [IN]	<ul style="list-style-type: none"> <li>• Facility ID <ul style="list-style-type: none"> <li>– 0 - Network Personalization (PN)</li> <li>– 1 - Network Subset Personalization (PU)</li> <li>– 2 - Service Provider Personalization (PP)</li> <li>– 3 - Corporate Personalization (PC)</li> <li>– 4 - UIM Personalization (PF)</li> </ul> </li> </ul>
<i>pStatus</i> [OUT]	<ul style="list-style-type: none"> <li>• Control key status <ul style="list-style-type: none"> <li>– 0 - Deactivated</li> <li>– 1 - Activated</li> <li>– 2 - Blocked</li> </ul> </li> </ul>
<i>pVerifyRetriesLeft</i> [OUT]	<ul style="list-style-type: none"> <li>• The number of retries left, after which the control key will be blocked <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pUnblockRetriesLeft</i> [OUT]	<ul style="list-style-type: none"> <li>• The number of unblock retries left, after which the control key will be permanently blocked <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

9.13.4.49 ULONG UIMGetICCID ( BYTE *stringSize*, CHAR \* *pString* )

Returns the UIM ICCID. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15-C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use [SLQSUIMReadTransparent\(\)](#) (EF ID: 3F00 2FE2) instead for new firmware versions and new modules.

## Parameters

<i>stringSize</i>	<ul style="list-style-type: none"> <li>The maximum number of characters (including NULL terminator) that the string array can contain.</li> </ul>
<i>pString[OUT]</i>	<ul style="list-style-type: none"> <li>NULL terminated string</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.13.4.50 **ULONG** UIMGetPINStatus ( **ULONG** *id*, **ULONG** \* *pStatus*, **ULONG** \* *pVerifyRetriesLeft*, **ULONG** \* *pUnblockRetriesLeft* )

Gets the status of the SIM PINs. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSUIMGetCardStatus\(\)](#) for new firmware versions and new modules

## Parameters

<i>id</i>	<ul style="list-style-type: none"> <li>PIN ID <ul style="list-style-type: none"> <li>1 ( PIN1 / CHV1 )</li> <li>2 ( PIN2 / CHV2 )</li> </ul> </li> </ul>
<i>pStatus[OUT]</i>	<ul style="list-style-type: none"> <li>PIN status(0xFFFFFFFF - Unknown) <ul style="list-style-type: none"> <li>0 - PIN not initialized</li> <li>1 - PIN enabled, not verified</li> <li>2 - PIN enabled, verified</li> <li>3 - PIN disabled</li> <li>4 - PIN blocked</li> <li>5 - PIN permanently blocked</li> </ul> </li> </ul>

<i>pVerifyRetriesLeft</i> [OUT]	<ul style="list-style-type: none"> <li>Upon operational failure, this will indicate number of retries left, after which PIN will be blocked. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pUnblockRetriesLeft</i> [OUT]	<ul style="list-style-type: none"> <li>Upon operational failure, this will indicate number of unblock retries left, after which the PIN will be permanently blocked; i.e., UIM is unusable. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

#### 9.13.4.51 **ULONG** UIMSetControlKeyProtection ( **ULONG** *id*, **ULONG** *status*, **CHAR** \* *pValue*, **ULONG** \* *pVerifyRetriesLeft* )

Changes the specified UIM facility control key. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSUIMDepersonalization\(\)](#) for new firmware versions and new modules

**Parameters**

<i>id</i> [IN]	<ul style="list-style-type: none"> <li>Facility ID <ul style="list-style-type: none"> <li>– 0 - Network Personalization (PN)</li> <li>– 1 - Network Subset Personalization (PU)</li> <li>– 2 - Service Provider Personalization (PP)</li> <li>– 3 - Corporate Personalization (PC)</li> <li>– 4 - UIM Personalization (PF)</li> </ul> </li> </ul>
----------------	---

<i>status[IN]</i>	<ul style="list-style-type: none"> <li>Control key status <ul style="list-style-type: none"> <li>0 - Deactivated</li> </ul> </li> </ul>
<i>pValue[IN]</i>	<ul style="list-style-type: none"> <li>Control key de-personalization string (maximum length of 8 characters)</li> </ul>
<i>pVerifyRetriesLeft[OUT]</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Upon operational failure, this will indicate number of retries left, after which the control key will be blocked <ul style="list-style-type: none"> <li>0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

#### 9.13.4.52 **ULONG UIMSetPINProtection ( ULONG id, ULONG bEnable, CHAR \* pValue, ULONG \* pVerifyRetriesLeft, ULONG \* pUnblockRetriesLeft )**

Enables or disables protection of SIM contents for a given PIN, This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSUIMSet-PinProtection\(\)](#) for new firmware versions and new modules

**Parameters**

<i>id[IN]</i>	<ul style="list-style-type: none"> <li>PIN ID <ul style="list-style-type: none"> <li>1 ( PIN1 / CHV1 )</li> <li>2 ( PIN2 / CHV2 )</li> </ul> </li> </ul>
---------------	--

<i>bEnable</i> [IN]	<ul style="list-style-type: none"> <li>• Enable/disable PIN protection, 0 = Disable</li> </ul>
<i>pValue</i> [IN]	<ul style="list-style-type: none"> <li>• PIN value of the PIN to be enabled/disabled</li> </ul>
<i>pVerifyRetriesLeft</i> [OUT]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Upon operational failure, this will indicate number of retries left, after which PIN will be blocked. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pUnblockRetriesLeft</i> [OUT]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Upon operational failure, this will indicate number of unblock retries left, after which the PIN will be permanently blocked i.e. UIM is unusable. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

#### 9.13.4.53 ULONG UIMUnblockControlKey ( ULONG *id*, CHAR \* *pValue*, ULONG \* *pUnblockRetriesLeft* )

Unblocks the specified UIM facility control key. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSUIDepersonalization\(\)](#) for new firmware versions and new modules

## Parameters

<i>id</i> [IN]	<ul style="list-style-type: none"> <li>• Facility ID <ul style="list-style-type: none"> <li>– 0 - Network Personalization (PN)</li> <li>– 1 - Network Subset Personalization (PU)</li> <li>– 2 - Service Provider Personalization (PP)</li> <li>– 3 - Corporate Personalization (PC)</li> <li>– 4 - UIM Personalization (PF)</li> </ul> </li> </ul>
<i>pValue</i> [IN]	<ul style="list-style-type: none"> <li>• Control key de-personalization string (maximum length of 8 characters)</li> </ul>
<i>pUnblock-RetriesLeft</i> [OUT]	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Upon operational failure, this will indicate number of unblock retries left, after which the control key will be blocked <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.13.4.54** **ULONG** UIMUnblockPIN ( **ULONG** *id*, **CHAR** \* *pPUKValue*, **CHAR** \* *pNewValue*, **ULONG** \* *pVerifyRetriesLeft*, **ULONG** \* *pUnblockRetriesLeft* )

Unblocks a blocked SIM. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSUIMUnblockPin\(\)](#) for new firmware versions and new modules

## Parameters

<i>id</i> [IN]	<ul style="list-style-type: none"> <li>• PIN ID <ul style="list-style-type: none"> <li>– 1 ( PIN1 / CHV1 )</li> <li>– 2 ( PIN2 / CHV2 )</li> </ul> </li> </ul>
----------------	--



<i>pPUKValue[IN]</i>	<ul style="list-style-type: none"> <li>• PUK value of PIN to unblock</li> </ul>
<i>pNewValue[IN]</i>	<ul style="list-style-type: none"> <li>• New PIN value of PIN to unblock</li> </ul>
<i>pVerifyRetriesLeft[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Upon operational failure, this will indicate number of retries left, after which the PIN will be blocked. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pUnblockRetriesLeft[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Upon operational failure, this will indicate number of unblock retries left, after which the PIN will be permanently blocked; i.e. UIM is unusable <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

#### 9.13.4.55 **ULONG UIMVerifyPIN ( ULONG id, CHAR \* pValue, ULONG \* pVerifyRetriesLeft, ULONG \* pUnblockRetriesLeft )**

Verifies a SIM PIN. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_ - xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSUIMVerifyPin\(\)](#) for new firmware versions and new modules

**Parameters**

<i>id[IN]</i>	<ul style="list-style-type: none"> <li>• PIN ID <ul style="list-style-type: none"> <li>– 1 ( PIN1 / CHV1 )</li> <li>– 2 ( PIN2 / CHV2 )</li> </ul> </li> </ul>
---------------	--

<i>pValue[IN]</i>	<ul style="list-style-type: none"> <li>• Value of PIN to verify</li> </ul>
<i>pVerifyRetries-Left[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Upon operational failure, this will indicate number of retries left, after which the PIN will be blocked. <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pUnblock-RetriesLeft[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional Parameter</li> <li>• Upon operational failure, this will indicate number of unblock retries left, after which the PIN will be permanently blocked; i.e. UIM is unusable <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

**9.13.4.56 ULONG ValidateSPC ( CHAR \* pSPC )**

This function Validates Service Programming code of the device

**Parameters**

<i>pSPC[IN]</i>	<ul style="list-style-type: none"> <li>• NULL-terminated string representing a six-digit service programming code</li> </ul>
-----------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Device Supported: MC83x5, MC7750  
Timeout: 2 seconds

## 9.14 qaGobiApiFms.h File Reference

Firmware Management Service API function prototypes.

### Data Structures

- struct [fwinfo\\_s](#)
- struct [slqsfwinfo\\_s](#)
- struct [qmifwinfo\\_s](#)
- struct [ImageElement](#)
- struct [PrefImageList](#)
- struct [ImageIdElement](#)
- struct [ImageIDEntries](#)
- struct [ImageList](#)
- struct [sGetDeviceSeriesResult](#)
- struct [SWI\\_STRUCT\\_CarrierImage](#)

### Macros

- #define [SLQSFWINFO\\_MODELID\\_SZ](#) 20
- #define [SLQSFWINFO\\_BOOTVERSION\\_SZ](#) 85
- #define [SLQSFWINFO\\_APPVERSION\\_SZ](#) 85
- #define [SLQSFWINFO\\_SKU\\_SZ](#) 15
- #define [SLQSFWINFO\\_PACKAGEID\\_SZ](#) 85
- #define [SLQSFWINFO\\_CARRIER\\_SZ](#) 20
- #define [SLQSFWINFO\\_PRIVERSION\\_SZ](#) 16
- #define [SLQSFWINFO\\_CUR\\_CARR\\_NAME](#) 17
- #define [SLQSFWINFO\\_CUR\\_CARR\\_REV](#) 13
- #define [GOBI\\_MBN\\_IMG\\_ID\\_STR\\_LEN](#) 16
- #define [GOBI\\_MBN\\_BUILD\\_ID\\_STR\\_LEN](#) 100
- #define [GOBI\\_LISTENTRIES\\_MAX](#) 2
- #define [GOBI\\_SET\\_IMG\\_PREF\\_RSPLEN](#) 40
- #define [DEVICE\\_SHUTDOWN](#) 5
- #define [DEVICE\\_RESET](#) 4
- #define [DEVICE\\_OFFLINE](#) 3
- #define [FIRMWARE\\_UPDATE\\_SUCCESS](#) 0x01
- #define [FIRMWARE\\_UPDATE\\_FAIL](#) 0x01
- #define [PRI\\_UPDATE\\_FAIL](#) 0x02
- #define [FIRMWARE\\_UPGRADE\\_SUCCESS](#) 0x00
- #define [IMG\\_ID\\_LEN](#) 16
- #define [BUILD\\_ID\\_LEN](#) 100

### Enumerations

- enum [eGobiImageTech](#) {  
[eGOBI\\_IMG\\_TECH\\_CDMA](#) = 0,  
[eGOBI\\_IMG\\_TECH\\_UMTS](#) }

- enum `eGobiImageCarrier` {  
    `eGOBI_IMG_CAR_GENERIC` = 1,  
    `eGOBI_IMG_CAR_FACTORY`,  
    `eGOBI_IMG_CAR_NORF`,  
    `eGOBI_IMG_CAR_VERIZON` = 101,  
    `eGOBI_IMG_CAR_SPRINT`,  
    `eGOBI_IMG_CAR_ALLTEL`,  
    `eGOBI_IMG_CAR_BELL`,  
    `eGOBI_IMG_CAR_TELUS`,  
    `eGOBI_IMG_CAR_US`,  
    `eGOBI_IMG_CAR_TELSTRA1`,  
    `eGOBI_IMG_CAR_CHINA_UNICOM`,  
    `eGOBI_IMG_CAR_TELCOM_NZ`,  
    `eGOBI_IMG_CAR_SK_TELCOM1`,  
    `eGOBI_IMG_CAR_RELIANCE1`,  
    `eGOBI_IMG_CAR_TATA`,  
    `eGOBI_IMG_CAR_METROPCS`,  
    `eGOBI_IMG_CAR_LEAP`,  
    `eGOBI_IMG_CAR_KDDI`,  
    `eGOBI_IMG_CAR_IUSACELL`,  
    `eGOBI_IMG_CAR_CHINA_TELECOM`,  
    `eGOBI_IMG_CAR_OMH`,  
    `eGOBI_IMG_CAR_GENERIC_CDMA`,  
    `eGOBI_IMG_CAR_ATT` = 201,  
    `eGOBI_IMG_CAR_VODAFONE`,  
    `eGOBI_IMG_CAR_TMOBILE`,  
    `eGOBI_IMG_CAR_ORANGE`,  
    `eGOBI_IMG_CAR_TELEFONICA`,  
    `eGOBI_IMG_CAR_TELCOM_ITALIA`,  
    `eGOBI_IMG_CAR_3`,  
    `eGOBI_IMG_CAR_O2`,  
    `eGOBI_IMG_CAR_SFR`,  
    `eGOBI_IMG_CAR_SWISSCOM`,  
    `eGOBI_IMG_CAR_CHINA_MOBILE`,  
    `eGOBI_IMG_CAR_TELSTRA2`,  
    `eGOBI_IMG_CAR_SINGTEL_OPTUS`,  
    `eGOBI_IMG_CAR_RELIANCE2`,  
    `eGOBI_IMG_CAR_BHARTI`,  
    `eGOBI_IMG_CAR_NTT_DOCOMO`,  
    `eGOBI_IMG_CAR_EMOBILE`,  
    `eGOBI_IMG_CAR_SOFTBANK`,  
    `eGOBI_IMG_CAR_KT_FREETEL`,  
    `eGOBI_IMG_CAR_SK_TELCOM2`,  
    `eGOBI_IMG_CAR_TELENOR`,  
    `eGOBI_IMG_CAR_NETCOM`,  
    `eGOBI_IMG_CAR_TELIASONERA`,  
    `eGOBI_IMG_CAR_AMX_TELCEL`,  
    `eGOBI_IMG_CAR_BRASIL_VIVO`,  
    `eGOBI_IMG_CAR_AERIS`,  
    `eGOBI_IMG_CAR_ROGERS` }  
• enum `eGobiImageRegion` {  
    `eGOBI_IMG_REG_NA` = 0,  
    `eGOBI_IMG_REG_LA`,  
    `eGOBI_IMG_REG_EU`,  
    `eGOBI_IMG_REG_ASIA`,  
    `eGOBI_IMG_REG_AUS`,  
    `eGOBI_IMG_REG_GLOBAL` }  
• enum `eGobiImageGPS` {

```

    eGOBI_IMG_GPS_NONE = 0,
    eGOBI_IMG_GPS_STAND_ALONE,
    eGOBI_IMG_GPS_ASSISTED,
    eGOBI_IMG_GPS_NO_XTRA }
• enum eGobiDeviceSeries {
    eGOBI_DEV_SERIES_UNKNOWN = -1,
    eGOBI_DEV_SERIES_NON_GOBI = 0,
    eGOBI_DEV_SERIES_G3K,
    eGOBI_DEV_SERIES_SIERRA_GOBI,
    eGOBI_DEV_SERIES_9X15,
    eGOBI_DEV_SERIES_9X30,
    eGobi_DEV_SERIES_MC83 }

```

## Functions

- [ULONG GetImageStore](#) ([WORD](#) imageStorePathSize, [CHAR](#) \*pImageStorePath)
- [ULONG SLQSGetFirmwareInfo](#) (struct [qmifwinfo\\_s](#) \*pinfo)
- [ULONG SLQSGetImageInfoMC77xx](#) ([LPCSTR](#) path, struct [qmifwinfo\\_s](#) \*pinfo)
- [ULONG SLQSGetImageInfoMC83xx](#) ([LPCSTR](#) path, struct [qmifwinfo\\_s](#) \*pinfo)
- [ULONG SLQSGetImageInfo](#) ([LPCSTR](#) path, struct [qmifwinfo\\_s](#) \*pinfo)
- [ULONG UpgradeFirmware2k](#) ([CHAR](#) \*pDestinationPath)
- [ULONG GetImagesPreference](#) ([ULONG](#) \*pImageListSize, struct [PrefImageList](#) \*pImageList)
- [ULONG SetImagesPreference](#) ([ULONG](#) imageListSize, [BYTE](#) \*pImageList, [ULONG](#) bForceDownload, [BYTE](#) modemIndex, [ULONG](#) \*pImageTypesSize, [BYTE](#) \*pImageTypes)
- [ULONG GetStoredImages](#) ([ULONG](#) \*pImageListSize, [BYTE](#) \*pImageList)
- [ULONG DeleteStoredImage](#) ([ULONG](#) imageInfoSize, [BYTE](#) \*pImageInfo)
- [ULONG SLQSGetImageInfo\\_9x15](#) ([LPCSTR](#) path, [BYTE](#) imgType, struct [slqsfwinfo\\_s](#) \*pinfo)
- [ULONG SLQSUpgradeFirmware9x15](#) ([CHAR](#) \*pDestinationPath)
- [ULONG SLQSGetBootVersionNumber](#) ([ULONG](#) \*bootversion)
- [BOOL SLQSIspkgFormatRequired](#) (void)
- [ULONG upgrade\\_mc77xx\\_fw](#) ([LPCSTR](#) path)
- void [eGetDeviceSeries](#) (struct [sGetDeviceSeriesResult](#) \*)
- [ULONG SLQSSwiGetAllCarrierImages](#) ([ULONG](#) \*pNumOfItems, struct [SWI\\_STRUCT\\_CarrierImage](#) \*pCarrierImages, [char](#) \*pFolderPath)
- [ULONG SLQSDownloadFirmwareToSlot](#) ([CHAR](#) \*pPath, [BYTE](#) slot\_index, [BYTE](#) force\_download)
- [ULONG SLQSGetValidFwPriCombinations](#) (struct [ImageList](#) \*pStoredImageList, [ULONG](#) \*pValidCombinationSize, struct [SWI\\_STRUCT\\_CarrierImage](#) \*pValidCombinations)

### 9.14.1 Detailed Description

Firmware Management Service API function prototypes.

### 9.14.2 Macro Definition Documentation

9.14.2.1 `#define BUILD_ID_LEN 100`

9.14.2.2 `#define DEVICE_OFFLINE 3`

9.14.2.3 `#define DEVICE_RESET 4`

9.14.2.4 `#define DEVICE_SHUTDOWN 5`

9.14.2.5 `#define FIRMWARE_UPDATE_FAIL 0x01`

9.14.2.6 `#define FIRMWARE_UPDATE_SUCCESS 0x01`

9.14.2.7 `#define FIRMWARE_UPGRADE_SUCCESS 0x00`

9.14.2.8 `#define GOBI_LISTENTRIES_MAX 2`

9.14.2.9 `#define GOBI_MBN_BUILD_ID_STR_LEN 100`

9.14.2.10 `#define GOBI_MBN_IMG_ID_STR_LEN 16`

9.14.2.11 `#define GOBI_SET_IMG_PREF_RSLEN 40`

9.14.2.12 `#define IMG_ID_LEN 16`

9.14.2.13 `#define PRI_UPDATE_FAIL 0x02`

9.14.2.14 `#define SLQSFWINFO_APPVERSION_SZ 85`

9.14.2.15 `#define SLQSFWINFO_BOOTVERSION_SZ 85`

9.14.2.16 `#define SLQSFWINFO_CARRIER_SZ 20`

9.14.2.17 `#define SLQSFWINFO_CUR_CARR_NAME 17`

9.14.2.18 `#define SLQSFWINFO_CUR_CARR_REV 13`

9.14.2.19 `#define SLQSFWINFO_MODELID_SZ 20`

9.14.2.20 `#define SLQSFWINFO_PACKAGEID_SZ 85`

9.14.2.21 `#define SLQSFWINFO_PRIVERSION_SZ 16`

9.14.2.22 `#define SLQSFWINFO_SKU_SZ 15`

### 9.14.3 Enumeration Type Documentation

#### 9.14.3.1 `enum eGobiDeviceSeries`

enumeration which lists the Device Series

Enumerator

**`eGOBI_DEV_SERIES_UNKNOWN`**  
**`eGOBI_DEV_SERIES_NON_GOBI`**  
**`eGOBI_DEV_SERIES_G3K`**  
**`eGOBI_DEV_SERIES_SIERRA_GOBI`**  
**`eGOBI_DEV_SERIES_9X15`**  
**`eGOBI_DEV_SERIES_9X30`**  
**`eGobi_DEV_SERIES_MC83`**

#### 9.14.3.2 `enum eGobiImageCarrier`

enumeration which lists the carrier supported by the image

## Enumerator

*eGOBI\_IMG\_CAR\_GENERIC*  
*eGOBI\_IMG\_CAR\_FACTORY*  
*eGOBI\_IMG\_CAR\_NORF*  
*eGOBI\_IMG\_CAR\_VERIZON*  
*eGOBI\_IMG\_CAR\_SPRINT*  
*eGOBI\_IMG\_CAR\_ALLTEL*  
*eGOBI\_IMG\_CAR\_BELL*  
*eGOBI\_IMG\_CAR\_TELUS*  
*eGOBI\_IMG\_CAR\_US*  
*eGOBI\_IMG\_CAR\_TELSTRA1*  
*eGOBI\_IMG\_CAR\_CHINA\_UNICOM*  
*eGOBI\_IMG\_CAR\_TELCOM\_NZ*  
*eGOBI\_IMG\_CAR\_SK\_TELCOM1*  
*eGOBI\_IMG\_CAR\_RELIANCE1*  
*eGOBI\_IMG\_CAR\_TATA*  
*eGOBI\_IMG\_CAR\_METROPCS*  
*eGOBI\_IMG\_CAR\_LEAP*  
*eGOBI\_IMG\_CAR\_KDDI*  
*eGOBI\_IMG\_CAR\_IUSACELL*  
*eGOBI\_IMG\_CAR\_CHINA\_TELECOM*  
*eGOBI\_IMG\_CAR\_OMH*  
*eGOBI\_IMG\_CAR\_GENERIC\_CDMA*  
*eGOBI\_IMG\_CAR\_ATT*  
*eGOBI\_IMG\_CAR\_VODAFONE*  
*eGOBI\_IMG\_CAR\_TMOBILE*  
*eGOBI\_IMG\_CAR\_ORANGE*  
*eGOBI\_IMG\_CAR\_TELEFONICA*  
*eGOBI\_IMG\_CAR\_TELCOM\_ITALIA*  
*eGOBI\_IMG\_CAR\_3*  
*eGOBI\_IMG\_CAR\_O2*  
*eGOBI\_IMG\_CAR\_SFR*  
*eGOBI\_IMG\_CAR\_SWISSCOM*  
*eGOBI\_IMG\_CAR\_CHINA\_MOBILE*  
*eGOBI\_IMG\_CAR\_TELSTRA2*  
*eGOBI\_IMG\_CAR\_SINGTEL\_OPTUS*  
*eGOBI\_IMG\_CAR\_RELIANCE2*  
*eGOBI\_IMG\_CAR\_BHARTI*  
*eGOBI\_IMG\_CAR\_NTT\_DOCOMO*  
*eGOBI\_IMG\_CAR\_EMOBILE*  
*eGOBI\_IMG\_CAR\_SOFTBANK*  
*eGOBI\_IMG\_CAR\_KT\_FREETEL*  
*eGOBI\_IMG\_CAR\_SK\_TELCOM2*  
*eGOBI\_IMG\_CAR\_TELNOR*  
*eGOBI\_IMG\_CAR\_NETCOM*  
*eGOBI\_IMG\_CAR\_TELIASONERA*  
*eGOBI\_IMG\_CAR\_AMX\_TELCEL*  
*eGOBI\_IMG\_CAR\_BRASIL\_VIVO*  
*eGOBI\_IMG\_CAR\_AERIS*  
*eGOBI\_IMG\_CAR\_ROGERS*

#### 9.14.3.3 enum eGobiImageGPS

enumeration which lists the GPS type supported by the image

Enumerator

***eGOBI\_IMG\_GPS\_NONE***  
***eGOBI\_IMG\_GPS\_STAND\_ALONE***  
***eGOBI\_IMG\_GPS\_ASSISTED***  
***eGOBI\_IMG\_GPS\_NO\_XTRA***

#### 9.14.3.4 enum eGobiImageRegion

enumeration which lists the region supported by the image

Enumerator

***eGOBI\_IMG\_REG\_NA***  
***eGOBI\_IMG\_REG\_LA***  
***eGOBI\_IMG\_REG\_EU***  
***eGOBI\_IMG\_REG\_ASIA***  
***eGOBI\_IMG\_REG\_AUS***  
***eGOBI\_IMG\_REG\_GLOBAL***

#### 9.14.3.5 enum eGobiImageTech

enumeration which lists the technology supported by the image

Enumerator

***eGOBI\_IMG\_TECH\_CDMA***  
***eGOBI\_IMG\_TECH\_UMTS***

### 9.14.4 Function Documentation

#### 9.14.4.1 ULONG DeleteStoredImage ( ULONG *imageInfoSize*, BYTE \* *plmageInfo* )

Used to delete the specified image from the device. This API function is only relevant to devices with the ability to store multiple firmware images(see Device Supported section below).

Parameters

<i>imageInfoSize</i> [I-N]	<ul style="list-style-type: none"> <li>The size in BYTES of the image info array</li> </ul>
<i>plmageInfo</i> [IN]	<ul style="list-style-type: none"> <li>The image info list array containing information about the image to be deleted.</li> <li>See <a href="#">ImageElement</a></li> </ul>

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise



## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Device Supported: MC83x5/SL9090  
Timeout: 2 Secs

## 9.14.4.2 void eGetDeviceSeries ( struct sGetDeviceSeriesResult \* )

Name : eGetDeviceSeries

## Parameters

<i>none</i>	
-------------	--

## Returns

[sGetDeviceSeriesResult](#)

## Note

Get Devie Series

9.14.4.3 ULONG GetImagesPreference ( ULONG \* *plmImageListSize*, struct PrefImageList \* *plmImageList* )

restore original alignment from stack Gets the current images preference from the device.

## Parameters

<i>plmImageListSize</i> [-IN/OUT]	<ul style="list-style-type: none"> <li>• Upon input, the size of structure <a href="#">ImageList</a> <a href="#">ImageList</a></li> <li>• Upon successful output, the number of BYTEs copied to the image list array</li> </ul>
<i>plmImageList</i> [OUT]	<ul style="list-style-type: none"> <li>• The caller must supply a pointer to a <a href="#">ImageList</a> structure typecast as a BYTE pointer</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

9.14.4.4 ULONG GetImageStore ( WORD *imageStorePathSize*, CHAR \* *plmImageStorePath* )

Returns the image store folder, i.e., the folder containing one or more carrier-specific image subfolders compatible with the currently connected QC WWAN device.

## Parameters

<i>imageStorePath-Size</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that can be copied to the image store path array.</li> </ul>
<i>plImageStore-Path[OUT]</i>	<ul style="list-style-type: none"> <li>The path to the image store</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.14.4.5 **ULONG** GetStoredImages ( **ULONG** \* *plImageListSize*, **BYTE** \* *plImageList* )

restore original alignment from stack Gets the list of images stored on the device.

## Parameters

<i>plImageListSize[IN/OUT]</i>	<ul style="list-style-type: none"> <li>Upon input, the size of structure <a href="#">ImageList</a> <a href="#">ImageList</a></li> <li>Upon successful output, the number of BYTES copied to the image list array</li> </ul>
<i>plImageList[OUT]</i>	<ul style="list-style-type: none"> <li>The caller must supply a pointer to a <a href="#">ImageList</a> structure typecast as a BYTE pointer</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Device Supported: MC83x5/SL9090  
Timeout: 2 seconds

#### 9.14.4.6 **ULONG** SetImagesPreference ( **ULONG** *imageListSize*, **BYTE** \* *plImageList*, **ULONG** *bForceDownload*, **BYTE** *modemIndex*, **ULONG** \* *plImageTypesSize*, **BYTE** \* *plImageTypes* )

Sets the current images preference on the device. After this function successfully completes, the device must be reset for the selected image preference to be realized. Additionally, when the returned list of image types that require downloading is not empty, the device opens in QDL mode after the reset. At that point, the QDL portion of this API must be used to download the selected image preference to the device.

## Parameters

<i>imageListSize</i>	<ul style="list-style-type: none"> <li>The size in BYTES of the image list array</li> </ul>
<i>pImageList[IN]</i>	<ul style="list-style-type: none"> <li>The image info list array containing Image Elements <ul style="list-style-type: none"> <li>See <a href="#">PrefImageList</a></li> </ul> </li> </ul>
<i>bForce-Download[IN]</i>	<ul style="list-style-type: none"> <li>Force device to download images from host? 0 - No Nonzero - Yes</li> </ul>
<i>modemIndex</i>	<ul style="list-style-type: none"> <li>Desired storage index for downloaded modem image (optional, a value of 0xFF indicates unspecified)</li> </ul>
<i>pImageTypes-Size[IN/OUT]</i>	<ul style="list-style-type: none"> <li>Upon input, maximum number of elements that download image types array can contain</li> <li>Upon successful output, number of elements in download image types array</li> </ul>
<i>pImageTypes[OUT]</i>	-The download image types array.

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.14.4.7 ULONG SLQSDownloadFirmwareToSlot ( CHAR \* pPath, BYTE slot\_index, BYTE force\_download )

This API is used to download firmware to a specific slot id of the modem. It is only applicable for EM74xx variant. This API encapsulates all steps involved in the firmware download process. Hence it is a blocking API call.

This API will not return until the entire process has been completed. This API will takes significant amount of time (in order of minutes, normally should be less than 10 minutes).

This API Performs the following steps:

1. Verifies arguments.
2. Retrieve and store the details of the firmware and the PRI file
3. Enable device state change callback.
4. Enable firmware download callback.
5. Set Image preference on the device and reset the device.

6. Wait for the firmware to download and device to become ready.
7. Check the firmware update status. If fail, return an error.
8. If update status is OK, check if current image preference and preferred image preference( from step 2 ) match
9. If match, firmware download is successful. otherwise, report FW\_PREFERENCE\_MISMATCH
10. Disable callbacks and exit.

The call to this API blocks until step 7 or 10. This could be a significant amount of time ( in order of minutes ). Also note that the device state change callback and firmware download callback are used internally within this API. Hence the user application's instance of these callbacks (if any) are cleared. The user must re-enable these callbacks after a call to this API in order to use them.

#### Parameters

<i>pPath[IN]</i>	<ul style="list-style-type: none"> <li>fully qualified path to firmware image to download.</li> </ul>
<i>slot_index[IN]</i>	<ul style="list-style-type: none"> <li>slot id in the modem to store the firmware</li> </ul>
<i>force_download[IN]</i>	<ul style="list-style-type: none"> <li>a flag to force download take place. this feature is not supported</li> <li>currently. so just pass the argument as 0 when invoke this API.</li> </ul>

#### Returns

- eQCWWAN\_ERR\_NONE - Firmware download/Switch success.
- eQCWWAN\_ERR\_INVALID\_ARG - The path input does not contain any image
- eQCWWAN\_ERR\_SWIIM\_FW\_UPDATE\_FAIL - Firmware download/switch failed
- eQCWWAN\_ERR\_SWIIM\_FW\_PREFERENCE\_MISMATCH - Download success but device of-line due to image preference mismatch ( ref. syslogs for cause )

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

Timeout: NA

#### 9.14.4.8 ULONG SLQSGetBootVersionNumber ( ULONG \* bootversion )

Gets the boot loader version number

#### Parameters

<i>bootversion[OUT]</i>	<ul style="list-style-type: none"> <li>boot loader version presented by a 4 byte integer</li> </ul>
-------------------------	---

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Device Supported: MC9090/SL9090  
Timeout: 2 seconds

9.14.4.9 ULONG SLQSGetFirmwareInfo ( struct qmifwinfo\_s \* *pinfo* )

Returns firmware image information from the connected device

## Parameters

<i>pinfo</i> [OUT]	<ul style="list-style-type: none"> <li>firmware image information record</li> </ul>
--------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values  
struct [qmifwinfo\\_s](#)

## Note

Timeout: 2 Seconds.

9.14.4.10 ULONG SLQSGetImageInfo ( LPCSTR *path*, struct qmifwinfo\_s \* *pinfo* )

Returns firmware image information from a CWE file or mbn files stored on the host. For CWE, information is returned for the first CWE image found at the specified path. For MBN, the provided path must be located under the image store for the currently connected QC WWAN device. Note that as this API supports multiple firmware image types, it relies on the presence of a supported device. Otherwise, refer to SLQSGetImageInfoMC83xx and SLQSGetImageInfoMC77xx for APIs which do not rely on the presence of a supported device.

## Parameters

<i>path</i> [IN]	<ul style="list-style-type: none"> <li>fully qualified path to folder containing CWE image or MBN images</li> <li>should use a "/" at the end of the path.</li> </ul>
<i>pinfo</i> [OUT]	<ul style="list-style-type: none"> <li>firmware image information record</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values  
struct [qmifwinfo\\_s](#)

## Note

Timeout: N/A

#### 9.14.4.11 `ULONG SLQSGetImageInfo_9x15 ( LPCSTR path, BYTE imgType, struct slqsfwinfo_s * pinfo )`

Returns firmware image information from a CWE file(s) stored on the host. It does not rely on the presence of a supported device.

##### Parameters

<i>path</i> [IN]	<ul style="list-style-type: none"> <li>fully qualified path to folder containing the image(s)</li> <li>should use a "/" at the end of the path.</li> </ul>
<i>imgType</i> [IN]	<ul style="list-style-type: none"> <li>2 - Firmware Image( .cwe extension )</li> <li>3 - PRI Image ( .nvu extension )</li> </ul>
<i>pinfo</i> [OUT]	<ul style="list-style-type: none"> <li>firmware image information record</li> </ul>

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values  
struct [qmifwinfo\\_s](#)

##### Note

Device Supported: MC73xx  
Timeout: N/A

#### 9.14.4.12 `ULONG SLQSGetImageInfoMC77xx ( LPCSTR path, struct qmifwinfo_s * pinfo )`

Returns firmware image information from a SPKGS CWE file stored on the host. The information is returned for the first SPKGS CWE image found at the specified path. This API executes independent of a MC77xx being connected to the target.

##### Parameters

<i>path</i> [IN]	<ul style="list-style-type: none"> <li>fully qualified path to folder containing SPKG CWE image</li> <li>should use a "/" at the end of the path.</li> </ul>
<i>pinfo</i> [OUT]	<ul style="list-style-type: none"> <li>firmware image information record</li> </ul>

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values  
 struct [qmifwinfo\\_s](#)

## Note

Device Supported: MC77xx  
 Timeout: N/A

#### 9.14.4.13 ULONG SLQSGetImageInfoMC83xx ( LPCSTR path, struct qmifwinfo\_s \* pinfo )

Returns firmware image information from an MBN file located on the host. This API executes independent of a MC83xx being connected to the target.

## Parameters

<i>path</i> [IN]	<ul style="list-style-type: none"> <li>fully qualified path to folder containing MBN file</li> <li>should use a "/" at the end of the path.</li> </ul>
<i>pinfo</i> [OUT]	<ul style="list-style-type: none"> <li>firmware image information record</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values  
 struct [qmifwinfo\\_s](#)

## Note

Device Supported: MC83xx/SL9090  
 Timeout: N/A

#### 9.14.4.14 ULONG SLQSGetValidFwPriCombinations ( struct ImageList \* pStoredImageList, ULONG \* pValidCombinationSize, struct SWI\_STRUCT\_CarrierImage \* pValidCombinations )

This API distills valid Firmware/PRI combinations from GetStoredImages result

## Parameters

in	<i>pStoredImageList</i>	<ul style="list-style-type: none"> <li>image list returned from GetStoredImages</li> </ul>
----	-------------------------	--

in, out	<i>pValid-CombinationSize</i>	<ul style="list-style-type: none"> <li>• number of combination passed in and returned</li> </ul>
out	<i>pValid-Combinations</i>	<ul style="list-style-type: none"> <li>• valid combinations returned</li> </ul>

**Returns**

- eQCWWAN\_ERR\_INVALID\_ARG - Invalid parameters
- eQCWWAN\_ERR\_BUFFER\_SZ - No enough element to store combinatons returned

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.14.4.15 BOOL SLQSIspkgFormatRequired ( void )**

Check if SPKG format download is required for SL9090/MC9090

**Parameters**

<i>none</i>
-------------

**Returns**

return TRUE if required, otherwise, return FALSE

**Note**

Device Supported: MC9090/SL9090

Timeout: 2 seconds

**9.14.4.16 ULONG SLQSSwiGetAllCarrierImages ( ULONG \* pNumOfItems, struct SWI\_STRUCT\_CarrierImage \* pCarrierImages, char \* pFolderPath )**

This API gets a list of all images stored on both the host and the device

**Parameters**

<i>pNumOfItems</i>	<ul style="list-style-type: none"> <li>• Number of Images{IN/OUT}</li> </ul>
<i>pCarrierImages[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SWI_STRUCT_CarrierImage</a></li> </ul>
<i>pFolderPath</i>	<ul style="list-style-type: none"> <li>• Path of Input folder [IN]</li> </ul>

**Returns**

TRUE/FALSE



**Note**

In case pFolderPath is invalid, API does not return invalid path error as SLQSSwiGetAllCarrierImages get carrier images from device also.

**9.14.4.17 ULONG SLQSupgradeFirmware9x15 ( CHAR \* pDestinationPath )**

This API is used to upgrade firmware on a MC73xx device. This API encapsulates all steps involved in the firmware download process. It is an alternative to any firmware download application. Hence it is a blocking API call. This API will not return until the entire process has been completed.

This API Performs the following steps:

1. Verifies arguments.
2. Retrieve and store the details of the firmware and the PRI file
3. Enable device state change callback.
4. Enable firmware download callback.
5. Set Image preference on the device and reset the device.
6. Wait for the firmware to download and device to become ready.
7. Check the firmware update status. If fail, return an error.
8. If update status is OK, check if current image preference and preferred image preference( from step 2 ) match
9. If match, firmware download is successful.
10. If do not match, repeat from step 5 once more.
11. Disable callbacks and exit.

The call to this API blocks until step 7 or 11. This could be a significant amount of time ( in order of minutes ). Also note that the device state change callback and firmware download callback are used internally within this API. Hence the user application's instance of these callbacks (if any) are cleared. The user must re-enable these callbacks after a call to this API in order to use them.

**Parameters**

<i>pDestination-Path[IN]</i>	<ul style="list-style-type: none"><li>• fully qualified path to firmware image to download. The path must end with a forward slash.</li></ul>
------------------------------	---

**Returns**

- eQCWWAN\_ERR\_NONE - Firmware download/Switch success.
- eQCWWAN\_ERR\_INVALID\_ARG - The path input does not contain any image
- eQCWWAN\_ERR\_SWIIM\_FW\_UPDATE\_FAIL - Firmware download/switch failed
- eQCWWAN\_ERR\_SWIIM\_FW\_PREFERENCE\_MISMATCH - Download success but device offline due to image preference mismatch ( ref. syslogs for cause )

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: NA

#### 9.14.4.18 ULONG upgrade\_mc77xx\_fw ( LPCSTR path )

#### 9.14.4.19 ULONG UpgradeFirmware2k ( CHAR \* pDestinationPath )

This API is used to download firmware to a MC77xx or Gobi 3000 device.

This API Performs the following steps:

1. Verifies arguments.
2. Verify that device Crash State should be 1 (RESET State).
3. Informs the SDK of the firmware upgrade path
4. Updates the images preference on the currently connected device.
5. Requests the device reset (device will reset after all open handles are released).

Upon successful completion, the above steps will have been completed, however, the actual upgrade of the firmware will necessarily then follow.

#### Parameters

<i>pDestination-Path</i> [IN]	<ul style="list-style-type: none"> <li>• fully qualified path to firmware image to download. The path must end with a forward slash. For a Gobi 3000 device the path should specify the carrier image folder index i.e.  "&lt;path&gt;\to\carrier\image&gt;/&lt;carrier index&gt;/" where &lt;carrier index&gt;=""&gt; is a valid sub-directory entry. For 9x30 devices if pDestinationPath is not valid on host, it will use pseudo path for image switching.</li> </ul>
-------------------------------	---

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

Timeout: 12 seconds

## 9.15 qaGobiApilms.h File Reference

IMS Service API function prototypes.

#### Data Structures

- struct [SetSIPConfigReq](#)
- struct [SetSIPConfigResp](#)
- struct [SetRegMgrConfigReq](#)
- struct [SetRegMgrConfigResp](#)
- struct [SetIMSSMSConfigReq](#)

- struct [SetIMSSMSConfigResp](#)
- struct [SetIMSUserConfigReq](#)
- struct [SetIMSUserConfigResp](#)
- struct [SetIMSVoIPConfigReq](#)
- struct [SetIMSVoIPConfigResp](#)
- struct [GetSIPConfigResp](#)
- struct [GetRegMgrConfigParams](#)
- struct [GetIMSSMSConfigParams](#)
- struct [GetIMSUserConfigParams](#)
- struct [GetIMSVoIPConfigResp](#)
- struct [imsCfgIndRegisterInfo](#)

## Functions

- [ULONG SLQSSetSIPConfig](#) ([SetSIPConfigReq](#) \*pSetSIPConfigReq, [SetSIPConfigResp](#) \*pSetSIPConfigResp)
- [ULONG SLQSSetRegMgrConfig](#) ([SetRegMgrConfigReq](#) \*pSetRegMgrConfigReq, [SetRegMgrConfigResp](#) \*pSetRegMgrConfigResp)
- [ULONG SLQSSetIMSSMSConfig](#) ([SetIMSSMSConfigReq](#) \*pSetIMSSMSConfigReq, [SetIMSSMSConfigResp](#) \*pSetIMSSMSConfigResp)
- [ULONG SLQSSetIMSUserConfig](#) ([SetIMSUserConfigReq](#) \*pSetIMSUserConfigReq, [SetIMSUserConfigResp](#) \*pSetIMSUserConfigResp)
- [ULONG SLQSSetIMSVoIPConfig](#) ([SetIMSVoIPConfigReq](#) \*pSetIMSVoIPConfigReq, [SetIMSVoIPConfigResp](#) \*pSetIMSVoIPConfigResp)
- [ULONG SLQSGetSIPConfig](#) ([GetSIPConfigResp](#) \*pGetSIPConfigResp)
- [ULONG SLQSGetRegMgrConfig](#) ([GetRegMgrConfigParams](#) \*pGetRegMgrConfigParams)
- [ULONG SLQSGetIMSSMSConfig](#) ([GetIMSSMSConfigParams](#) \*pGetIMSSMSConfigParams)
- [ULONG SLQSGetIMSUserConfig](#) ([GetIMSUserConfigParams](#) \*pGetIMSUserConfigParams)
- [ULONG SLQSGetIMSVoIPConfig](#) ([GetIMSVoIPConfigResp](#) \*pGetIMSVoIPConfigResp)
- [ULONG SLQSImConfigIndicationRegister](#) ([imsCfgIndRegisterInfo](#) \*pImCfgIndRegisterInfo)

### 9.15.1 Detailed Description

IMS Service API function prototypes.

### 9.15.2 Function Documentation

#### 9.15.2.1 [ULONG SLQSGetIMSSMSConfig](#) ( [GetIMSSMSConfigParams](#) \* *pGetIMSSMSConfigParams* )

This API retrieves the SMS configuration parameters.

Parameters

<i>pGetIMSSMSConfigParams</i> [I-/OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">GetIMSSMSConfigParams</a> for more information</li> </ul>
--	--

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

### 9.15.2.2 **ULONG** SLQSGetIMSUserConfig ( **GetIMSUserConfigParams** \* *pGetIMSUserConfigParams* )

This API retrieves the IMS User configuration parameters.

**Parameters**

<i>pGetIMSUserConfigParams</i> [I-OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">GetIMSUserConfigParams</a> for more information</li> </ul>
--	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

### 9.15.2.3 **ULONG** SLQSGetIMSVoIPConfig ( **GetIMSVoIPConfigResp** \* *pGetIMSVoIPConfigResp* )

This API retrieves the IMS VoIP configuration parameters.

**Parameters**

<i>GetIMSVoIPConfigResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">GetIMSVoIPConfigResp</a> for more information</li> </ul>
-----------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

### 9.15.2.4 **ULONG** SLQSGetRegMgrConfig ( **GetRegMgrConfigParams** \* *pGetRegMgrConfigParams* )

This API retrieves the registration manager configuration parameters.

## Parameters

<i>pGetRegMgr- ConfigParams[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetRegMgrConfigResp</a> for more information</li> </ul>
---	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

#### 9.15.2.5 ULONG SLQSGetSIPConfig ( GetSIPConfigResp \* pGetSIPConfigResp )

This API retrieves the Session Initiation Protocol(SIP) configuration parameters.

## Parameters

<i>pGetSIPConfig- Resp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetSIPConfigResp</a> for more information</li> </ul>
-------------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

#### 9.15.2.6 ULONG SLQSImsConfigIndicationRegister ( imsCfgIndRegisterInfo \* plmsCfgIndRegisterInfo )

Sets the registration state for different QMI\_IMS indications for the requesting control point

## Parameters

<i>plmsCfgInd- RegisterInfo[IN]</i>	<ul style="list-style-type: none"> <li>• Structure containing Indication Register Information.           <ul style="list-style-type: none"> <li>– See <a href="#">imsCfgIndRegisterInfo</a> for more informtaion.</li> </ul> </li> </ul>
---	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 10 Secs

This API is used by a device to register/deregister for different QMI IMS indications. The device's registration state variables that control registration for indications will be modified to reflect the settings indicated in the request message. At least one optional parameter must be present in the request.

#### 9.15.2.7 **ULONG SLQSSetIMSSMSConfig ( SetIMSSMSConfigReq \* pSetIMSSMSConfigReq, SetIMSSMSConfigResp \* pSetIMSSMSConfigResp )**

This API sets the IMS SMS configuration parameters for the requesting control point.

**Parameters**

<i>pSetIMSSMS-ConfigReq[IN]</i>	<ul style="list-style-type: none"> <li>See <a href="#">SetIMSSMSConfigReq</a> for more information</li> </ul>
<i>pSetIMSSMS-ConfigResp[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">SetIMSSMSConfigResp</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

#### 9.15.2.8 **ULONG SLQSSetIMSUserConfig ( SetIMSUserConfigReq \* pSetIMSUserConfigReq, SetIMSUserConfigResp \* pSetIMSUserConfigResp )**

This API sets the IMS user configuration parameters for the requesting control point.

## Parameters

<i>pSetIMSUser-ConfigReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">SetIMSUserConfigReq</a> for more information</li> </ul>
<i>pSetIMSUser-ConfigResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">SetIMSUserConfigResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

#### 9.15.2.9 ULONG SLQSSetIMSVoIPConfig ( SetIMSVoIPConfigReq \* *pSetIMSVoIPConfigReq*, SetIMSVoIPConfigResp \* *pSetIMSVoIPConfigResp* )

This API sets the IMS Voice over Internet Protocol (VoIP) configuration parameters for the requesting control point.

## Parameters

<i>pSetIMSVoIP-ConfigReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">SetIMSVoIPConfigReq</a> for more information</li> </ul>
<i>pSetIMSVoIP-ConfigResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">SetIMSVoIPConfigResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

#### 9.15.2.10 ULONG SLQSSetRegMgrConfig ( SetRegMgrConfigReq \* *pSetRegMgrConfigReq*, SetRegMgrConfigResp \* *pSetRegMgrConfigResp* )

This API sets the IMS registration manager configuration parameters for the requesting control point.

## Parameters

<i>pSetRegMgr-ConfigReq[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SetRegMgrConfigReq</a> for more information</li> </ul>
<i>pSetRegMgr-ConfigResp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SetRegMgrConfigResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

#### 9.15.2.11 ULONG SLQSSetSIPConfig ( SetSIPConfigReq \* pSetSIPConfigReq, SetSIPConfigResp \* pSetSIPConfigResp )

This API sets the IMS Session Initiation Protocol(SIP) configuration parameters for the requesting control point.

## Parameters

<i>pSetSIPConfig-Req[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SetSIPConfigReq</a> for more information</li> </ul>
<i>pSetSIPConfig-Resp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">SetSIPConfigResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: NA  
 Device Supported: MC73xx, MC74xx and EM74xx  
 Timeout: 5 seconds

## 9.16 qaGobiApilmsa.h File Reference

IMSA Service API function prototypes.



## Data Structures

- struct [IMSALndRegisterInfo](#)
- struct [SupportedMsgList](#)
- struct [IMSASupportedMsgInfo](#)
- struct [ReqFieldsList](#)
- struct [RespFieldsList](#)
- struct [LndFieldsList](#)
- struct [IMSASupportedFieldsResp](#)
- struct [IMSARegistrationStatus](#)
- struct [IMSAServiceStatus](#)

## Functions

- [ULONG SLQSRegisterIMSAIndication](#) ([IMSALndRegisterInfo](#) \*pImsaIndRegisterInfo)
- [ULONG SLQSGetIMSASupportedMsg](#) ([IMSASupportedMsgInfo](#) \*pIMSASupportedMsgInfo)
- [ULONG SLQSGetIMSASupportedFields](#) ([WORD](#) messageID, [IMSASupportedFieldsResp](#) \*pIMSASupportedFieldsResp)
- [ULONG SLQSGetIMSARegStatus](#) ([IMSARegistrationStatus](#) \*pIMSARegistrationStatus)
- [ULONG SLQSGetIMSAServiceStatus](#) ([IMSAServiceStatus](#) \*pIMSAServiceStatus)

### 9.16.1 Detailed Description

IMSA Service API function prototypes.

### 9.16.2 Function Documentation

#### 9.16.2.1 [ULONG SLQSGetIMSARegStatus](#) ( [IMSARegistrationStatus](#) \* *pIMSARegistrationStatus* )

Queries the set of messages implemented by the currently running software.

##### Parameters

<i>pIMSARegistrationStatus</i> [OUT]	<ul style="list-style-type: none"> <li>• Structure containing response parameters for registration status. <ul style="list-style-type: none"> <li>– See <a href="#">IMSARegistrationStatus</a> for more information.</li> </ul> </li> </ul>
--------------------------------------	---

##### Returns

[eQCWWAN\\_ERR\\_NONE](#) on success, [eQCWWAN\\_xxx](#) error value otherwise

##### See Also

See [qmerrno.h](#) for [eQCWWAN\\_xxx](#) error values

##### Note

Timeout: 5 Secs

This API is used by a device to get the registration status for various IMS services for the requesting control point.

#### 9.16.2.2 [ULONG SLQSGetIMSAServiceStatus](#) ( [IMSAServiceStatus](#) \* *pIMSAServiceStatus* )

Gets the service status for various IMS services for the requesting control point.

## Parameters

<i>pIMSAService-Status</i> [OUT]	<ul style="list-style-type: none"> <li>• Structure containing response parameters for service status. <ul style="list-style-type: none"> <li>– See <a href="#">IMSAServiceStatus</a> for more information.</li> </ul> </li> </ul>
----------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Secs

This API is used by a device to Gets the service status for various IMS services for the requesting control point.

### 9.16.2.3 ULONG SLQSGetIMSA SupportedFields ( WORD *messageID*, IMSASupportedFieldsResp \* *pIMSA SupportedFieldsResp* )

Queries the set of supported fields implemented by the currently running software.

## Parameters

<i>messageID</i> [IN]	<ul style="list-style-type: none"> <li>• Service Message ID.</li> </ul>
<i>pIMSA-Supported-FieldsResp</i> [OUT]	<ul style="list-style-type: none"> <li>• Structure containing Supported Fields Response. <ul style="list-style-type: none"> <li>– See <a href="#">IMSA SupportedFieldsResp</a> for more information.</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Secs

This API is used by a device to query the fields supported for a single command as implemented by the currently running software.

### 9.16.2.4 ULONG SLQSGetIMSA SupportedMsg ( IMSASupportedMsgInfo \* *pIMSA SupportedMsgInfo* )

Queries the set of messages implemented by the currently running software.

## Parameters

<i>pIMSA-SupportedMsg-Info[OUT]</i>	<ul style="list-style-type: none"> <li>• Structure containing Supported Messages Information. <ul style="list-style-type: none"> <li>– See <a href="#">IMSASupportedMsgInfo</a> for more information.</li> </ul> </li> </ul>
-------------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Secs

This API is used by a device to query the set of messages implemented by the currently running software

#### 9.16.2.5 ULONG SLQSRegisterIMSAIndication ( IMSAIndRegisterInfo \* *plmsalndRegisterInfo* )

Sets the registration state for different QMI\_IMSA indications for the requesting control point

## Parameters

<i>plmsalnd-RegisterInfo[IN]</i>	<ul style="list-style-type: none"> <li>• Structure containing Indication Register Information. <ul style="list-style-type: none"> <li>– See <a href="#">IMSAIndRegisterInfo</a> for more information.</li> </ul> </li> </ul>
----------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Secs

This API is used by a device to register/deregister for different QMI\_IMSA indications. The device's registration state variables that control registration for indications will be modified to reflect the settings indicated in the request message. At least one optional parameter must be present in the request.

## 9.17 qaGobiApiLoc.h File Reference

Location API function prototypes.

## Data Structures

- struct [LOCEventRegisterReqResp](#)
- struct [LOCExtPowerStateReqResp](#)
- struct [LocApplicationInfo](#)
- struct [LOCStartReq](#)
- struct [LOCStopReq](#)
- struct [SV](#)
- struct [SVInfo](#)
- struct [GnssData](#)
- struct [CellDb](#)
- struct [CikInfo](#)
- struct [BdsSV](#)
- struct [BdsSVInfo](#)
- struct [LocDelAssDataReq](#)
- struct [SwiLocGetAutoStartResp](#)
- struct [SwiLocSetAutoStartReq](#)
- struct [altitudeSrcInfo](#)
- struct [LocInjectPositionReq](#)
- struct [LocSetCradleMountReq](#)
- struct [sensorData](#)
- struct [tempratureData](#)
- struct [LocInjectSensorDataReq](#)

## Macros

- `#define` [MAX\\_SENSOR\\_DATA\\_LEN](#) 64
- `#define` [MAX\\_TEMP\\_DATA\\_LEN](#) 64

## Functions

- [ULONG](#) [SLQSLOCEventRegister](#) ([LOCEventRegisterReqResp](#) \*pLOCEventRegisterReqResp)
- [ULONG](#) [SLQSLOCSetExtPowerState](#) ([LOCExtPowerStateReqResp](#) \*pLOCExtPowerStateReqResp)
- [ULONG](#) [SLQSLOCStart](#) ([LOCStartReq](#) \*pLOCStartReq)
- [ULONG](#) [SLQSLOCStop](#) ([LOCStopReq](#) \*pLOCStopReq)
- [ULONG](#) [SLQSLOCSetOpMode](#) ([ULONG](#) mode)
- [ULONG](#) [SLQSLOCDelAssData](#) ([LocDelAssDataReq](#) request)
- [ULONG](#) [SwiLocGetAutoStart](#) ([SwiLocGetAutoStartResp](#) \*resp)
- [ULONG](#) [SwiLocSetAutoStart](#) ([SwiLocSetAutoStartReq](#) \*req)
- [ULONG](#) [SLQSLOCInjectUTCTime](#) ([ULONGLONG](#) timeMsec, [ULONG](#) timeUncMsec)
- [ULONG](#) [SLQSLOCInjectPosition](#) ([LocInjectPositionReq](#) \*pLocInjectPositionReq)
- [ULONG](#) [SLQSLOCSetCradleMountConfig](#) ([LocSetCradleMountReq](#) \*pLocSetCradleMountReq)
- [ULONG](#) [SLQSLOCInjectSensorData](#) ([LocInjectSensorDataReq](#) \*pLocInjectSensorDataReq)

### 9.17.1 Detailed Description

Location API function prototypes.

## 9.17.2 Macro Definition Documentation

9.17.2.1 `#define MAX_SENSOR_DATA_LEN 64`

9.17.2.2 `#define MAX_TEMP_DATA_LEN 64`

## 9.17.3 Function Documentation

9.17.3.1 `ULONG SLQSLOCDeIAssData ( LocDeIAssDataReq request )`

Used by the control point to delete the location engine assistance data

### Parameters

<i>request</i> [IN]	<ul style="list-style-type: none"> <li>request structure parameters should contain all NULL pointers to delete all assistance data. Otherwise, specify optional fields to be deleted. See <a href="#">LocDeIAssDataReq</a> for more information</li> </ul>
---------------------	--

### Returns

`eQCWWAN_ERR_NONE` on success, `eQCWWAN_xxx` error value otherwise

### See Also

See [qmerrno.h](#) for `eQCWWAN_xxx` error values

### Note

Timeout: 5 seconds

9.17.3.2 `ULONG SLQSLOCEventRegister ( LOCEventRegisterReqResp * pLOCEventRegisterReqResp )`

Used by the control point to register for events from the location subsystem.

### Parameters

<i>pLOCEvent-RegisterReq-Resp</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">LOCEventRegisterReqResp</a> for more information</li> </ul>
--	--

### Returns

`eQCWWAN_ERR_NONE` on success, `eQCWWAN_xxx` error value otherwise

### See Also

See [qmerrno.h](#) for `eQCWWAN_xxx` error values

### Note

Timeout: 5 seconds

9.17.3.3 `ULONG SLQSLOCInjectPosition ( LocInjectPositionReq * pLocInjectPositionReq )`

Injects a position to the location engine.

## Parameters

<i>pLocInject- PositionReq[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">LocInjectPositionReq</a> for more information</li></ul>
--	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.17.3.4 ULONG SLQSLOCInjectSensorData ( LocInjectSensorDataReq \* pLocInjectSensorDataReq )

Control point to to inject sensor data into the GNSS location engine.

## Parameters

<i>pLocInject- SensorData- Req[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">LocInjectSensorDataReq</a> for more information</li></ul>
--	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.17.3.5 ULONG SLQSLOCInjectUTCtime ( ULONGLONG timeMsec, ULONG timeUncMsec )

Injects UTC time in the location engine.

## Parameters

<i>timeMsec[IN]</i>	<ul style="list-style-type: none"><li>• The UTC time since Jan. 1, 1970</li></ul>
---------------------	---

<i>timeUncMsec</i> [1-N]	<ul style="list-style-type: none"> <li>The time Uncertainty</li> </ul>
--------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

### 9.17.3.6 ULONG SLQSLocSetCradleMountConfig ( LocSetCradleMountReq \* pLocSetCradleMountReq )

Control point to set the current cradle mount configuration.

**Parameters**

<i>pLocSetCradleMountReq</i> [1N]	<ul style="list-style-type: none"> <li>See <a href="#">LocSetCradleMountReq</a> for more information</li> </ul>
-----------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

### 9.17.3.7 ULONG SLQSLocSetExtPowerState ( LOCExtPowerStateReqResp \* pLOCExtPowerStateReqResp )

Used by the control point to set the current external power configuration.

**Parameters**

<i>pLOCExtPowerStateReqResp</i> [1-N]	<ul style="list-style-type: none"> <li>See <a href="#">LOCExtPowerStateReqResp</a> for more information</li> </ul>
---------------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

### 9.17.3.8 **ULONG SLQSLOCSetOpMode ( ULONG mode )**

Used by the control point to tells the engine to use the specified operation mode while making the position fixes

#### Parameters

<i>mode</i> [IN]	<ul style="list-style-type: none"> <li>Valid values: <ul style="list-style-type: none"> <li>eQMI_LOC_OPER_MODE_DEFAULT (1) - Use the default engine mode</li> <li>eQMI_LOC_OPER_MODE_MSB (2) - Use the MS-based mode</li> <li>eQMI_LOC_OPER_MODE_MSA (3) - Use the MS-assisted mode</li> <li>eQMI_LOC_OPER_MODE_STANDALONE (4) - Use Standalone mode</li> <li>eQMI_LOC_OPER_MODE_CELL_ID (5) - Use cell ID; this mode is only valid for GSM/UMTS networks</li> <li>eQMI_LOC_OPER_MODE_WWAN (6) - Use WWAN measurements to calculate the position; if this mode is set, AFLT will be used for 1X networks and OTDOA will be used for LTE networks</li> </ul> </li> </ul>
------------------	---

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

Timeout: 5 seconds

### 9.17.3.9 **ULONG SLQSLOCStart ( LOCStartReq \* pLOCStartReq )**

Used by the control point to initiate a GPS session.

#### Parameters

<i>pLOCStartReq</i> - <i>Req</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">LOCStartReq</a> for more information</li> </ul>
--	--

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

Timeout: 5 seconds

### 9.17.3.10 **ULONG SLQSLOCStop ( LOCStopReq \* pLOCStopReq )**

Used by the control point to stop a GPS session.



## Parameters

<i>pLOCStopReq-Resp[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">LOCStopReq</a> for more information</li></ul>
-----------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.17.3.11    ULONG SwiLocGetAutoStart ( SwiLocGetAutoStartResp \* resp )**

Used by the control point to Get Loc Auto Start settings

## Parameters

<i>resp[OUT]</i>	<ul style="list-style-type: none"><li>• See <a href="#">SwiLocGetAutoStartResp</a> for more information</li></ul>
------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.17.3.12    ULONG SwiLocSetAutoStart ( SwiLocSetAutoStartReq \* req )**

Used by the control point to Set Loc Auto Start settings

## Parameters

<i>req[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">SwiLocSetAutoStartReq</a> for more information</li></ul>
----------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.18 qaGobiApiNas.h File Reference

Network Access Service API function prototypes.

### Data Structures

- struct [RFBandInfoElements](#)
- struct [servSystem](#)
- struct [dataSrvCapabilities](#)
- struct [currentPLMN](#)
- struct [roamIndList](#)
- struct [qaQmi3Gpp2TimeZone](#)
- struct [detailSvcInfo](#)
- struct [CDMASysInfoExt](#)
- struct [callBarStatus](#)
- struct [qaQmiServingSystemParam](#)
- struct [rxSignalStrengthListElement](#)
- struct [ecioListElement](#)
- struct [errorRateListElement](#)
- struct [rsrqInformation](#)
- struct [lteSnrinformation](#)
- struct [lteRsrpinformation](#)
- struct [slqsSignalStrengthInfo](#)
- struct [SlqsNas3GppNetworkInfo](#)
- struct [\\_SlqsNas3GppNetworkRAT\\_](#)
- struct [SlqsNasPcsDigit](#)
- struct [\\_slqsNetworkScanInfo](#)
- struct [netSelectionPref](#)
- struct [acqOrderPref](#)
- struct [CSGID](#)
- struct [\\_sysSelectPrefParams](#)
- struct [\\_sysSelectPrefInfo](#)
- struct [SrvStatusInfo](#)
- struct [GSMSrvStatusInfo](#)
- struct [sysInfoCommon](#)
- struct [CDMASysInfo](#)
- struct [HDRSysInfo](#)
- struct [GSMSysInfo](#)
- struct [WCDMASysInfo](#)
- struct [LTESysInfo](#)
- struct [AddCDMASysInfo](#)
- struct [AddSysInfo](#)
- struct [CallBarringSysInfo](#)
- struct [nasGetSysInfoResp](#)
- struct [CommInfo](#)
- struct [LTEInfo](#)
- struct [swiModemStatusResp](#)
- struct [nasGetHDRColorCodeResp](#)
- struct [nasGetTxRxInfoReq](#)
- struct [rxInfo](#)
- struct [txInfo](#)
- struct [nasGetTxRxInfoResp](#)
- struct [CDMASSInfo](#)
- struct [HDRSSInfo](#)

- struct [LTISSInfo](#)
- struct [TDSCDMASigInfoExt](#)
- struct [nasGetSigInfoResp](#)
- struct [nasIndicationRegisterReq](#)
- struct [nasPLMNNameReq](#)
- struct [nasPLMNNameResp](#)
- struct [OperatorPLMNData](#)
- struct [operatorPLMNList](#)
- struct [serviceProviderName](#)
- struct [PLMNNetworkNameData](#)
- struct [PLMNNetworkName](#)
- struct [operatorNameString](#)
- struct [nasOperatorNameResp](#)
- struct [nasGet3GPP2SubscriptionInfoReq](#)
- struct [namName](#)
- struct [dirNum](#)
- struct [sidNid](#)
- struct [homeSIDNID](#)
- struct [minBasedIMSI](#)
- struct [trueIMSI](#)
- struct [CDMAChannel](#)
- struct [nasGet3GPP2SubscriptionInfoResp](#)
- struct [nmrCellInfo](#)
- struct [GERANInfo](#)
- struct [geranInstInfo](#)
- struct [UMTSinstInfo](#)
- struct [UMTSInfo](#)
- struct [CDMAInfo](#)
- struct [cellParams](#)
- struct [LTEInfoIntrafreq](#)
- struct [infoInterFreq](#)
- struct [LTEInfoInterfreq](#)
- struct [gsmCellInfo](#)
- struct [lteGsmCellInfo](#)
- struct [LTEInfoNeighboringGSM](#)
- struct [wcdmaCellInfo](#)
- struct [lteWcdmaCellInfo](#)
- struct [LTEInfoNeighboringWCDMA](#)
- struct [umtsLTENbrCell](#)
- struct [WCDMAInfoLTENeighborCell](#)
- struct [nasCellLocationInfoResp](#)
- struct [MNRInfo](#)
- struct [nasInitNetworkReq](#)
- struct [protocolSubtypeElement](#)
- struct [HDRPersonalityResp](#)
- struct [HDRProtSubtypResp](#)
- struct [PSDetachReq](#)
- struct [GetErrRateResp](#)
- struct [DRCParams](#)
- struct [PilotSetParams](#)
- struct [PilotSetData](#)
- struct [GetHRPDStatsResp](#)
- struct [ActPilotPNElement](#)
- struct [NetworkStat1x](#)
- struct [NetworkStatEVDO](#)

- struct [DeviceConfigDetail](#)
- struct [DataStatusDetail](#)
- struct [NetworkDebugResp](#)
- struct [LteCQIParm](#)
- struct [RSSIThresh](#)
- struct [ECIOThresh](#)
- struct [HRSINRThresh](#)
- struct [LTSNRThresh](#)
- struct [IOThresh](#)
- struct [RSRQThresh](#)
- struct [RSRPThresh](#)
- struct [LTSigRptCfg](#)
- struct [TDSCDMASINRCONFTthresh](#)
- struct [sigInfo](#)
- struct [NasSwiIndReg](#)
- struct [CDMARSSIThresh](#)
- struct [CDMAECIOThresh](#)
- struct [HRRSSIThresh](#)
- struct [HDRECIOThresh](#)
- struct [HRSINRThreshold](#)
- struct [HDRIOThresh](#)
- struct [GSMRSSIThresh](#)
- struct [WCDMARSSIThresh](#)
- struct [WCDMAECIOThresh](#)
- struct [LTERSSIThresh](#)
- struct [LTSNRThreshold](#)
- struct [LTERSRQThresh](#)
- struct [LTERSRPThresh](#)
- struct [LTSigRptConfig](#)
- struct [TDSCDMARSCPTthresh](#)
- struct [TDSCDMARSSIThresh](#)
- struct [TDSCDMAECIOThresh](#)
- struct [TDSCDMASINRThresh](#)
- struct [setSignalStrengthInfo](#)
- struct [PhyCaAggScellIndType](#)
- struct [PhyCaAggScellIDBw](#)
- struct [PhyCaAggScellInfo](#)
- struct [PhyCaAggPcellInfo](#)
- struct [PhyCaAggScellIndex](#)
- struct [nasGetLTECphyCaResp](#)
- struct [nasGetLTECphyCa](#)
- struct [wcdmaUARFCN](#)
- struct [lteEARFCN](#)
- struct [ltePCI](#)
- struct [nasSwiGetChannelLockResp](#)
- struct [nasSwiSetChannelLockReq](#)
- struct [timeInfo](#)
- struct [GetNetworkTimeResp](#)

## Macros

- #define [SLQS\\_SS\\_INFO\\_LIST\\_MAX\\_ELEMENTS](#) 18
- #define [MAX\\_DESCRIPTION\\_LENGTH](#) 255
- #define [SLQS\\_SYSTEM\\_ID\\_SIZE](#) 16
- #define [PLMN\\_LENGTH](#) 3
- #define [MAX\\_SERV\\_SYSTEM\\_RADIO\\_INTERFACES](#) 0x0A
- #define [MAX\\_DATA\\_SRV\\_CAPABILITIES](#) 0x20
- #define [NAM\\_NAME\\_LENGTH](#) 12
- #define [IMSI\\_M\\_S1\\_LENGTH](#) 7
- #define [IMSI\\_M\\_S2\\_LENGTH](#) 3
- #define [MAX\\_PILOT\\_SETS](#) 0xFF
- #define [UATISIZE](#) 16
- #define [NAS\\_SIG\\_INFO\\_MAX\\_TDSCDMA\\_THRESHOLDS\\_LIST\\_SIZE](#) 16
- #define [NAS\\_SIG\\_INFO\\_MIN\\_dBm\\_FLOAT\\_VALUE](#) -125.0
- #define [NAS\\_SIG\\_INFO\\_MIN\\_dB\\_FLOAT\\_VALUE](#) -10.0

## Typedefs

- typedef struct [\\_SlqsNas3GppNetworkRAT](#) [SlqsNas3GppNetworkRAT](#)
- typedef struct [\\_slqsNetworkScanInfo](#) [slqsNetworkScanInfo](#)
- typedef struct [\\_sysSelectPrefParams](#) [sysSelectPrefParams](#)
- typedef struct [\\_sysSelectPrefInfo](#) [sysSelectPrefInfo](#)

## Enumerations

- enum [\\_NAMS\\_RADIO\\_IF\\_TECHNOLOGY](#) {  
[eNAS\\_RADIO\\_IF\\_GSM](#) = 0x04,  
[eNAS\\_RADIO\\_IF\\_UMTS](#) = 0x05,  
[eNAS\\_RADIO\\_IF\\_LTE](#) = 0x08,  
[eNAS\\_RADIO\\_IF\\_TDSCDMA](#) = 0x09 }
- enum [NAS\\_LTE\\_CPHY\\_SCELL\\_STATE](#) {  
[eNAS\\_LTE\\_CPHY\\_SCELL\\_STATE\\_DECONFIGURED](#) = 0x00,  
[eNAS\\_LTE\\_CPHY\\_SCELL\\_STATE\\_CONFIGURED\\_DEACTIVATED](#) = 0x01,  
[eNAS\\_LTE\\_CPHY\\_SCELL\\_STATE\\_CONFIGURED\\_ACTIVATED](#) = 0x02 }
- enum [NAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB](#) {  
[eNAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_6](#) = 0x00,  
[eNAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_15](#) = 0x01,  
[eNAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_25](#) = 0x02,  
[eNAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_50](#) = 0x03,  
[eNAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_75](#) = 0x04,  
[eNAS\\_LTE\\_CPHY\\_CA\\_BW\\_NRB\\_100](#) = 0x05 }
- enum [eSYS\\_SRV\\_DOMAIN](#) {  
[eSYS\\_SRV\\_DOMAIN\\_NO\\_SRV](#) = 0x00,  
[eSYS\\_SRV\\_DOMAIN\\_CS\\_ONLY](#) = 0x01,  
[eSYS\\_SRV\\_DOMAIN\\_PS\\_ONLY](#) = 0x02,  
[eSYS\\_SRV\\_DOMAIN\\_CS\\_PS](#) = 0x03,  
[eSYS\\_SRV\\_DOMAIN\\_CAMPED](#) = 0x04,  
[eSYS\\_SRV\\_DOMAIN\\_UNKNOWN](#) }

## Functions

- [ULONG GetSignalStrengths](#) ([ULONG](#) \*pArraySizes, [INT8](#) \*pSignalStrength, [ULONG](#) \*pRadioInterface)
- [ULONG PerformNetworkScan](#) ([BYTE](#) \*pInstanceSize, [BYTE](#) \*pInstances)
- [ULONG InitiateNetworkRegistration](#) ([ULONG](#) regType, [WORD](#) mcc, [WORD](#) mnc, [ULONG](#) rat)
- [ULONG GetServingNetwork](#) ([ULONG](#) \*pRegistrationState, [ULONG](#) \*pCSDomain, [ULONG](#) \*pPSDomain, [ULONG](#) \*pRAN, [BYTE](#) \*pRadiolfacesSize, [BYTE](#) \*pRadiolfaces, [ULONG](#) \*pRoaming, [WORD](#) \*pMCC, [WORD](#) \*pMNC, [BYTE](#) nameSize, [CHAR](#) \*pName)
- [ULONG GetHomeNetwork](#) ([WORD](#) \*pMCC, [WORD](#) \*pMNC, [BYTE](#) nameSize, [CHAR](#) \*pName, [WORD](#) \*pSID, [WORD](#) \*pNID)
- [ULONG GetServingNetworkCapabilities](#) ([BYTE](#) \*pDataCapsSize, [BYTE](#) \*pDataCaps)
- [ULONG SetNetworkPreference](#) ([ULONG](#) technologyPref, [ULONG](#) duration)
- [ULONG GetNetworkPreference](#) ([ULONG](#) \*pTechnologyPref, [ULONG](#) \*pDuration, [ULONG](#) \*pPersistentTechnologyPref)
- [ULONG GetRFInfo](#) ([BYTE](#) \*pInstanceSize, struct [RFBandInfoElements](#) \*pRFBandInfo)
- [ULONG InitiateDomainAttach](#) ([ULONG](#) action)
- [ULONG GetACCOLC](#) ([BYTE](#) \*pACCOLC)
- [ULONG SetACCOLC](#) ([CHAR](#) \*spc, [BYTE](#) acccolc)
- [ULONG SetCDMANetworkParameters](#) ([CHAR](#) \*pSPC, [BYTE](#) \*pForceRev0, [BYTE](#) \*pCustomSCP, [ULONG](#) \*pProtocol, [ULONG](#) \*pBroadcast, [ULONG](#) \*pApplication, [ULONG](#) \*pRoaming)
- [ULONG GetCDMANetworkParameters](#) ([BYTE](#) \*pSCI, [BYTE](#) \*pSCM, [BYTE](#) \*pRegHomeSID, [BYTE](#) \*pRegForeignSID, [BYTE](#) \*pRegForeignNID, [BYTE](#) \*pForceRev0, [BYTE](#) \*pCustomSCP, [ULONG](#) \*pProtocol, [ULONG](#) \*pBroadcast, [ULONG](#) \*pApplication, [ULONG](#) \*pRoaming)
- [ULONG GetANAAAAuthenticationStatus](#) ([ULONG](#) \*pStatus)
- [ULONG SLQSGetServingSystem](#) ([qaQmiServingSystemParam](#) \*pServingSystem)
- [ULONG SLQSSetBandPreference](#) ([ULONGLONG](#) bandpreference)
- [ULONG SLQSNasIndicationRegister](#) ([BYTE](#) systemSelectionInd, [BYTE](#) DDTMInd, [BYTE](#) servingSystemInd)
- [ULONG SLQSGetSignalStrength](#) (struct [slqsSignalStrengthInfo](#) \*pSignalInfo)
- [ULONG SLQSPerformNetworkScan](#) ([slqsNetworkScanInfo](#) \*pNetworkInfo)
- [ULONG SLQSSetSysSelectionPref](#) ([sysSelectPrefParams](#) \*pSysSelectPrefParams)
- [ULONG SLQSGetSysSelectionPref](#) ([sysSelectPrefInfo](#) \*pSysSelectPrefInfo)
- [ULONG SLQSNasGetSysInfo](#) ([nasGetSysInfoResp](#) \*pGetSysInfoResp)
- [ULONG SLQSNasSmiModemStatus](#) ([swiModemStatusResp](#) \*pModemStatusResp)
- [ULONG SLQSNasGetHDRColorCode](#) ([nasGetHDRColorCodeResp](#) \*pGetHDRColorCodeResp)
- [ULONG SLQSNasGetTxRxInfo](#) ([nasGetTxRxInfoReq](#) \*pGetTxRxInfoReq, [nasGetTxRxInfoResp](#) \*pGetTxRxInfoResp)
- [ULONG SLQSNasGetSigInfo](#) ([nasGetSigInfoResp](#) \*pGetSigInfoResp)
- [ULONG SLQSNasIndicationRegisterExt](#) ([nasIndicationRegisterReq](#) \*pIndicationRegisterReq)
- [ULONG SLQSGetPLMNName](#) ([nasPLMNNameReq](#) \*pPLMNNameReq, [nasPLMNNameResp](#) \*pPLMNNameResp)
- [ULONG SLQSGetOperatorNameData](#) ([nasOperatorNameResp](#) \*pOperatorNameData)
- [ULONG SLQSNasGet3GPP2Subscription](#) ([nasGet3GPP2SubscriptionInfoReq](#) \*pGet3GPP2SubsInfoReq, [nasGet3GPP2SubscriptionInfoResp](#) \*pGet3GPP2SubsInfoResp)
- [ULONG SLQSNasGetCellLocationInfo](#) ([nasCellLocationInfoResp](#) \*pNasCellLocationInfoResp)
- [ULONG SLQSInitiateNetworkRegistration](#) ([nasInitNetworkReg](#) \*pNasInitNetRegistrationReg)
- [ULONG SLQSSwiGetHDRPersonality](#) ([HDRPersonalityResp](#) \*pHDRPersonalityResp)
- [ULONG SLQSSwiGetHDRProtSubtype](#) ([HDRProtSubtypResp](#) \*pHDRProtSubtypResp)
- [ULONG SLQSSwiPSDetach](#) ([PSDetachReq](#) \*pPSDetachReq)
- [ULONG SLQSGetErrorRate](#) ([GetErrRateResp](#) \*pGetErrRateResp)
- [ULONG SLQSSwiGetHRPDStats](#) ([GetHRPDStatsResp](#) \*pGetHRPDStatsResp)
- [ULONG SLQSSwiNetworkDebug](#) ([NetworkDebugResp](#) \*pNetworkDebugResp)
- [ULONG SLQSSwiGetLteCQI](#) ([LteCQIParm](#) \*pLteCQIResp)
- [ULONG SLQSConfigSigInfo](#) ([sigInfo](#) \*pSigInfo)
- [ULONG SLQSNasSmiIndicationRegister](#) ([NasSmiIndReg](#) \*pIndRegReq)

- [ULONG GetHomeNetwork3GPP2](#) ([WORD \\*pMCC](#), [WORD \\*pMNC](#), [BYTE nameSize](#), [CHAR \\*pName](#), [WORD \\*pSID](#), [WORD \\*pNID](#), [WORD \\*pNw2MCC](#), [WORD \\*pNw2MNC](#), [BYTE \\*pNw2DescDisp](#), [BYTE \\*pNw2DescEnc](#), [BYTE \\*pNw2DescLen](#), [BYTE \\*pNw2Name](#))
- [ULONG SLQSNasConfigSigInfo2](#) ([setSignalStrengthInfo \\*pSetSignalStrengthInfo](#))
- [ULONG SLQSNASGetLTEPHYCaInfo](#) ([nasGetLTECphyCa \\*pLTECPhyCa](#))
- [ULONG SLQSNasIndicationRegisterLTECphyCa](#) ([BYTE \\*bStatus](#))
- [ULONG SLQSNASSwiGetChannelLock](#) ([nasSwiGetChannelLockResp \\*pNasSwiGetChannelLockResp](#))
- [ULONG SLQSNASSwiSetChannelLock](#) ([nasSwiSetChannelLockReq \\*pNasSwiSetChannelLockReq](#))
- [ULONG SLQSGetNetworkTime](#) ([GetNetworkTimeResp \\*pGetNetworkTimeResp](#))

### 9.18.1 Detailed Description

Network Access Service API function prototypes.

### 9.18.2 Macro Definition Documentation

9.18.2.1 `#define IMSI_M_S1_LENGTH 7`

9.18.2.2 `#define IMSI_M_S2_LENGTH 3`

9.18.2.3 `#define MAX_DATA_SRV_CAPABILITIES 0x20`

9.18.2.4 `#define MAX_DESCRIPTION_LENGTH 255`

9.18.2.5 `#define MAX_PILOT_SETS 0xFF`

9.18.2.6 `#define MAX_SERV_SYSTEM_RADIO_INTERFACES 0x0A`

9.18.2.7 `#define NAM_NAME_LENGTH 12`

9.18.2.8 `#define NAS_SIG_INFO_MAX_TDSCDMA_THRESHOLDS_LIST_SIZE 16`

9.18.2.9 `#define NAS_SIG_INFO_MIN_dB_FLOAT_VALUE -10.0`

9.18.2.10 `#define NAS_SIG_INFO_MIN_dBm_FLOAT_VALUE -125.0`

9.18.2.11 `#define PLMN_LENGTH 3`

9.18.2.12 `#define SLQS_SS_INFO_LIST_MAX_ELEMENTS 18`

9.18.2.13 `#define SLQS_SYSTEM_ID_SIZE 16`

9.18.2.14 `#define UATISIZE 16`

### 9.18.3 Typedef Documentation

9.18.3.1 `typedef struct _SlqsNas3GppNetworkRAT_SlqsNas3GppNetworkRAT`

Contain the 3GPP radio access technology information.

Parameters

---

<i>MCC</i>	<ul style="list-style-type: none"> <li>• Mobile Country Code</li> </ul>
<i>MNC</i>	<ul style="list-style-type: none"> <li>• Mobile Network Code</li> </ul>
<i>RAT</i>	<ul style="list-style-type: none"> <li>• Radio Access Technology <ul style="list-style-type: none"> <li>– 0x04 - GERAN</li> <li>– 0x05 - UMTS</li> <li>– 0x08 - LTE</li> <li>– 0x09 - TD-SCDMA</li> </ul> </li> </ul>

### 9.18.3.2 typedef struct \_slqsNetworkScanInfo slqsNetworkScanInfo

Contain the network scan information.

#### Parameters

<i>pNetworkInfoInstances[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Upon input, maximum number of elements that the network info instance array can contain.</li> <li>• Upon successful output, the actual number of elements in the network info instance array.</li> </ul>
<i>pNetworkInfo[OUT]</i>	<ul style="list-style-type: none"> <li>• Network info instance array <ul style="list-style-type: none"> <li>– See <a href="#">SlqsNas3GppNetworkInfo</a> for more information</li> </ul> </li> </ul>
<i>pRATInstances[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Upon input, maximum number of elements that the RAT info instance array can contain.</li> <li>• Upon successful output, the actual number of elements in the RAT info instance array.</li> </ul>
<i>pRATInfo[OUT]</i>	<ul style="list-style-type: none"> <li>• RAT info instance array <ul style="list-style-type: none"> <li>– See <a href="#">SlqsNas3GppNetworkRAT</a> for more information</li> </ul> </li> </ul>
<i>pPCSDigitInstances[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Upon input, maximum number of elements that the PCS Digit info instance array can contain.</li> <li>• Upon successful output, the actual number of elements in the PCS Digit info instance array.</li> </ul>



<i>pPCSDigitInfo[OUT]</i>	<ul style="list-style-type: none"> <li>• PCS Digit info instance array <ul style="list-style-type: none"> <li>– See <a href="#">SlqsNasPcsDigit</a> for more information</li> </ul> </li> </ul>
<i>pScanResult[OUT]</i>	<ul style="list-style-type: none"> <li>• status of network scan</li> <li>• 0x00 - scan successful</li> <li>• 0x01 - scan was aborted</li> <li>• 0x02 - scan did not complete due to a radio link failure recovery in progress</li> </ul>

### 9.18.3.3 typedef struct \_sysSelectPrefInfo sysSelectPrefInfo

Structure for storing the current preferred system selection settings for the device.

#### Parameters

<i>pEmerMode</i>	<ul style="list-style-type: none"> <li>• Optional parameter specifying the emergency Mode</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - OFF (normal)</li> <li>– 1 - ON (Emergency)</li> </ul> </li> <li>• function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FF if no value is returned by the device.</li> </ul>
<i>pModePref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit Mask indicating the radio technology mode preference</li> <li>• Bit values: <ul style="list-style-type: none"> <li>– Bit 0 - cdma2000 1x</li> <li>– Bit 1 - cdma2000 HRPD(1xEV-DO)</li> <li>– Bit 2 - GSM</li> <li>– Bit 3 - UMTS</li> <li>– Bit 4 - LTE</li> </ul> </li> <li>• function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FF if no value is returned by the device.</li> </ul>

<i>pBandPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit mask representing the band preference</li> <li>• Bit values: <ul style="list-style-type: none"> <li>– Bit 0 - Band Class 0, A-System</li> <li>– Bit 1 - Band Class 0, B-System, Band Class 0 AB, GSM 850 Band</li> <li>– Bit 2 - Band Class 1, all blocks</li> <li>– Bit 3 - Band Class 2 place holder</li> <li>– Bit 4 - Band Class 3, A-System</li> <li>– Bit 5 - Band Class 4, all blocks</li> <li>– Bit 6 - Band Class 5, all blocks</li> <li>– Bit 7 - GSM_DCS_1800 band</li> <li>– Bit 8 - GSM Extended GSM (E-GSM) 900 band</li> <li>– Bit 9 - GSM Primary GSM (P-GSM) 900 band</li> <li>– Bit 10 - Band Class 6</li> <li>– Bit 11 - Band Class 7</li> <li>– Bit 12 - Band Class 8</li> <li>– Bit 13 - Band Class 9</li> <li>– Bit 14 - Band Class 10</li> <li>– Bit 15 - Band Class 11</li> <li>– Bit 16 - GSM 450 band</li> <li>– Bit 17 - GSM 480 band</li> <li>– Bit 18 - GSM 750 band</li> <li>– Bit 19 - GSM 850 band</li> <li>– Bit 20 - GSM Railways GSM 900 Band</li> <li>– Bit 21 - GSM PCS 1900 band</li> <li>– Bit 22 - WCDMA Europe, Japan, and China IMT 2100 band</li> <li>– Bit 23 - WCDMA U.S. PCS 1900 band</li> <li>– Bit 24 - WCDMA Europe and China DCS 1800 band</li> <li>– Bit 25 - WCDMA U.S. 1700 band</li> <li>– Bit 26 - WCDMA U.S. 850 band</li> <li>– Bit 27 - WCDMA Japan 800 band</li> <li>– Bit 28 - Band Class 12</li> <li>– Bit 29 - Band Class 14</li> <li>– Bit 30 - Reserved</li> <li>– Bit 31 - Band Class 15</li> <li>– Bit 32 to 47 - Reserved</li> <li>– Bit 48 - WCDMA Europe 2600 band</li> <li>– Bit 49 - WCDMA Europe and Japan 900 band</li> <li>– Bit 50 - WCDMA Japan 1700 band</li> <li>– Bit 51 to 55 - Reserved</li> <li>– Bit 56 - Band Class 16</li> <li>– Bit 57 - Band Class 17</li> <li>– Bit 58 - Band Class 18</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– Bit 59 - Band Class 19</li> <li>– Bit 60 to 64 - Reserved</li> </ul> <p>Generated on Tue Jul 12 2016 10:59:49 for LinuxQMSDK by Doxygen</p> <ul style="list-style-type: none"> <li>• function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFFFFFFFFFFFFFF if no value is returned by the device.</li> </ul>

<i>pPRLPref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating the CDMA PRL Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x0001 - Acquire available system only on the A side</li> <li>0x0002 - Acquire available system only on the B side</li> <li>0x3FFF - Acquire any available systems</li> </ul> </li> <li>function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFF if no value is returned by the device.</li> </ul>
<i>pRoamPref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating the roaming Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x01 - Acquire only systems for which the roaming indicator is off</li> <li>0x02 - Acquire a system as long as its roaming indicator is not off</li> <li>0x03 - Acquire only systems for which the roaming indicator is off or solid on, i.e. not flashing; CDMA only</li> <li>0xFF - Acquire systems, regardless of their roaming indicator</li> </ul> </li> <li>function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFF if no value is returned by the device.</li> </ul>
<i>pLTEBandPref</i>	<ul style="list-style-type: none"> <li>Optional parameter</li> <li>Bit mask representing the LTE band preference</li> <li>Bit Values <ul style="list-style-type: none"> <li>Bit 0 - E-UTRA Operating Band 1</li> <li>Bit 1 - E-UTRA Operating Band 2</li> <li>Bit 2 - E-UTRA Operating Band 3</li> <li>Bit 3 - E-UTRA Operating Band 4</li> <li>Bit 4 - E-UTRA Operating Band 5</li> <li>Bit 5 - E-UTRA Operating Band 6</li> <li>Bit 6 - E-UTRA Operating Band 7</li> <li>Bit 7 - E-UTRA Operating Band 8</li> <li>Bit 8 - E-UTRA Operating Band 9</li> <li>Bit 9 - E-UTRA Operating Band 10</li> <li>Bit 10 - E-UTRA Operating Band 11</li> <li>Bit 11 - E-UTRA Operating Band 12</li> <li>Bit 12 - E-UTRA Operating Band 13</li> <li>Bit 13 - E-UTRA Operating Band 14</li> <li>Bit 16 - E-UTRA Operating Band 17</li> <li>Bit 17 - E-UTRA Operating Band 18</li> <li>Bit 18 - E-UTRA Operating Band 19</li> <li>Bit 19 - E-UTRA Operating Band 20</li> <li>Bit 20 - E-UTRA Operating Band 21</li> <li>Bit 32 - E-UTRA Operating Band 33</li> <li>Bit 33 - E-UTRA Operating Band 34</li> <li>Bit 34 - E-UTRA Operating Band 35</li> <li>Bit 35 - E-UTRA Operating Band 36</li> <li>Bit 36 - E-UTRA Operating Band 37</li> </ul> </li> </ul>

<i>pNetSelPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating network selection preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Automatic network selection</li> <li>– 0x01 - Manual network selection</li> </ul> </li> <li>• function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FF if no value is returned by the device.</li> </ul>
<i>pSrvDomainPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating Service domain preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Circuit switched only</li> <li>– 0x01 - Packet switched only</li> <li>– 0x02 - Circuit switched and packet switched</li> <li>– 0x03 - Packet switched attach</li> <li>– 0x04 - Packet switched detach</li> </ul> </li> <li>• function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFFFFFF if no value is returned by the device.</li> </ul>
<i>pGWAcqOrder-Pref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating GSM/WCDMA Acquisition order Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Automatic</li> <li>– 0x01 - GSM then WCDMA</li> <li>– 0x02 - WCDMA then GSM</li> </ul> </li> <li>• function <a href="#">SLQSGetSysSelectionPref()</a> returns a default value FFFFFFFF if no value is returned by the device.</li> </ul>

**Note**

None

**9.18.3.4 typedef struct \_sysSelectPrefParams sysSelectPrefParams**

Contain the system selection preferences.

## Parameters

<i>pEmerMode</i>	<ul style="list-style-type: none"> <li>• Optional parameter specifying the emergency Mode</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0 - OFF (normal)</li> <li>– 1 - ON (Emergency)</li> </ul> </li> </ul>
<i>pModePref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit Mask indicating the radio technology mode preference</li> <li>• Bit values: <ul style="list-style-type: none"> <li>– Bit 0 - cdma2000 1x</li> <li>– Bit 1 - cdma2000 HRPD(1xEV-DO)</li> <li>– Bit 2 - GSM</li> <li>– Bit 3 - UMTS</li> <li>– Bit 4 - LTE</li> </ul> </li> </ul>
<i>pBandPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit mask representing the band preference</li> <li>• Bit values: <ul style="list-style-type: none"> <li>– Bit 0 - Band Class 0, A-System</li> <li>– Bit 1 - Band Class 0, B-System, Band Class 0 AB, GSM 850 Band</li> <li>– Bit 2 - Band Class 1, all blocks</li> <li>– Bit 3 - Band Class 2 place holder</li> <li>– Bit 4 - Band Class 3, A-System</li> <li>– Bit 5 - Band Class 4, all blocks</li> <li>– Bit 6 - Band Class 5, all blocks</li> <li>– Bit 7 - GSM_DCS_1800 band</li> <li>– Bit 8 - GSM Extended GSM (E-GSM) 900 band</li> <li>– Bit 9 - GSM Primary GSM (P-GSM) 900 band</li> <li>– Bit 10 - Band Class 6</li> <li>– Bit 11 - Band Class 7</li> <li>– Bit 12 - Band Class 8</li> <li>– Bit 13 - Band Class 9</li> <li>– Bit 14 - Band Class 10</li> <li>– Bit 15 - Band Class 11</li> <li>– Bit 16 - GSM 450 band</li> <li>– Bit 17 - GSM 480 band</li> <li>– Bit 18 - GSM 750 band</li> <li>– Bit 19 - GSM 850 band</li> <li>– Bit 20 - GSM Railways GSM 900 Band</li> <li>– Bit 21 - GSM PCS 1900 band</li> <li>– Bit 22 - WCDMA Europe, Japan, and China IMT 2100 band</li> <li>– Bit 23 - WCDMA U.S. PCS 1900 band</li> <li>– Bit 24 - WCDMA Europe and China DCS 1800 band</li> </ul> </li> </ul>

<i>pPRLPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating the CDMA PRL Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x0001 - Acquire available system only on the A side</li> <li>– 0x0002 - Acquire available system only on the B side</li> <li>– 0x3FFF - Acquire any available systems</li> </ul> </li> </ul>
<i>pRoamPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating the roaming Preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - Acquire only systems for which the roaming indicator is off</li> <li>– 0x02 - Acquire a system as long as its roaming indicator is not off</li> <li>– 0x03 - Acquire only systems for which the roaming indicator is off or solid on, i.e. not flashing; CDMA only</li> <li>– 0xFF - Acquire systems, regardless of their roaming indicator</li> </ul> </li> </ul>
<i>pLTEBandPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter</li> <li>• Bit mask representing the LTE band preference</li> <li>• Bit Values <ul style="list-style-type: none"> <li>– Bit 0 - E-UTRA Operating Band 1</li> <li>– Bit 1 - E-UTRA Operating Band 2</li> <li>– Bit 2 - E-UTRA Operating Band 3</li> <li>– Bit 3 - E-UTRA Operating Band 4</li> <li>– Bit 4 - E-UTRA Operating Band 5</li> <li>– Bit 5 - E-UTRA Operating Band 6</li> <li>– Bit 6 - E-UTRA Operating Band 7</li> <li>– Bit 7 - E-UTRA Operating Band 8</li> <li>– Bit 8 - E-UTRA Operating Band 9</li> <li>– Bit 9 - E-UTRA Operating Band 10</li> <li>– Bit 10 - E-UTRA Operating Band 11</li> <li>– Bit 11 - E-UTRA Operating Band 12</li> <li>– Bit 12 - E-UTRA Operating Band 13</li> <li>– Bit 13 - E-UTRA Operating Band 14</li> <li>– Bit 16 - E-UTRA Operating Band 17</li> <li>– Bit 17 - E-UTRA Operating Band 18</li> <li>– Bit 18 - E-UTRA Operating Band 19</li> <li>– Bit 19 - E-UTRA Operating Band 20</li> <li>– Bit 20 - E-UTRA Operating Band 21</li> <li>– Bit 32 - E-UTRA Operating Band 33</li> <li>– Bit 33 - E-UTRA Operating Band 34</li> <li>– Bit 34 - E-UTRA Operating Band 35</li> <li>– Bit 35 - E-UTRA Operating Band 36</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– Bit 36 - E-UTRA Operating Band 37</li> <li>– Bit 37 - E-UTRA Operating Band 38</li> <li>– Bit 38 - E-UTRA Operating Band 39</li> <li>– Bit 39 - E-UTRA Operating Band 40</li> </ul>

<i>pNetSelPref</i>	<p>- <a href="#">netSelectionPref</a></p> <ul style="list-style-type: none"> <li>• Optional parameter for specifying Network Selection Preference</li> <li>• Modem selects networks based on this parameter(if present).</li> <li>• Either of pNetSelPref or pCSGID can be set.</li> <li>• see <a href="#">netSelectionPref</a> for more information</li> </ul>
<i>pChgDuration</i>	<ul style="list-style-type: none"> <li>• Optional parameter specifying the duration of the change</li> <li>• At least one system selection setting to be set if pChgDuration is populated.</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Power cycle - Remains active until the next device power cycle</li> <li>– 0x01 - Permanent - Remains active through power cycles until changed by client</li> <li>– Device will use "0x01 - permanent" as default if this parameter is omitted</li> </ul> </li> </ul>
<i>pMNCIncPCS-DigStat</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating if MNC includes PCS digit</li> <li>• pNetSelPref is expected if MNC includes PCS digit is set to 1.</li> <li>• Values: <ul style="list-style-type: none"> <li>– TRUE - MNC is a 3 digit value; e.g., a reported value of 90 corresponds to an MNC value of 090</li> <li>– FALSE - MNC is a 2-digit value; e.g., a reported value of 90 corresponds to an MNC value of 90</li> </ul> </li> </ul>
<i>pSrvDomainPref</i>	<ul style="list-style-type: none"> <li>• Optional parameter indicating Service domain preference</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Circuit switched only</li> <li>– 0x01 - Packet switched only</li> <li>– 0x02 - Circuit switched and packet switched</li> <li>– 0x03 - Packet switched attach</li> <li>– 0x04 - Packet switched detach</li> </ul> </li> </ul>

<i>pGWAcqOrder-Pref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating GSM/WCDMA Acquisition order Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Automatic</li> <li>0x01 - GSM then WCDMA</li> <li>0x02 - WCDMA then GSM</li> </ul> </li> </ul>
<i>pTdscdmaBand-Pref</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating bitmask representing the TD-SCDMA band preference to be set.</li> <li>Values: <ul style="list-style-type: none"> <li>0x01 - TD-SCDMA Band A</li> <li>0x02 - TD-SCDMA Band B</li> <li>0x04 - TD-SCDMA Band C</li> <li>0x08 - TD-SCDMA Band D</li> <li>0x10 - TD-SCDMA Band E</li> <li>0x20 - TD-SCDMA Band F</li> <li>All other bits are reserved</li> </ul> </li> </ul>
<i>pAcqOrderPref</i>	<ul style="list-style-type: none"> <li>- <a href="#">acqOrderPref</a></li> <li>Optional parameter for specifying Acquisition Order Preference</li> <li>see <a href="#">acqOrderPref</a> for more information</li> </ul>
<i>pSrvReg-Restriction</i>	<ul style="list-style-type: none"> <li>Optional parameter indicating Network Selection Registration Restriction Preference</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Device follows the normal registration process</li> <li>0x01 - Device camps on the network according to its provisioning, but does not register</li> <li>0x02 - Device selects the network for limited service</li> <li>All other values are reserved.</li> </ul> </li> </ul>



<i>pCSGID</i>	- <a href="#">CSGID</a> <ul style="list-style-type: none"> <li>• Optional parameter for specifying CSG ID</li> <li>• Either of pNetSelPref or pCSGID can be set.</li> <li>• see <a href="#">CSGID</a> for more information</li> </ul>
<i>pRAT</i>	<ul style="list-style-type: none"> <li>• Optional parameter Radio Access Technology order Preference</li> <li>• Values:             <ul style="list-style-type: none"> <li>– 0x04 - GSM</li> <li>– 0x05 - UMTS</li> <li>– 0x08 - LTE</li> <li>– 0x09 - TDSCDMA</li> </ul> </li> </ul>

### 9.18.4 Enumeration Type Documentation

#### 9.18.4.1 enum \_NAMS\_RADIO\_IF\_TECHNOLOGY\_

Enumerator

***eNAS\_RADIO\_IF\_GSM***  
***eNAS\_RADIO\_IF\_UMTS***  
***eNAS\_RADIO\_IF\_LTE***  
***eNAS\_RADIO\_IF\_TDSCDMA***

#### 9.18.4.2 enum eSYS\_SRV\_DOMAIN

Enumerator

***eSYS\_SRV\_DOMAIN\_NO\_SRV***  
***eSYS\_SRV\_DOMAIN\_CS\_ONLY***  
***eSYS\_SRV\_DOMAIN\_PS\_ONLY***  
***eSYS\_SRV\_DOMAIN\_CS\_PS***  
***eSYS\_SRV\_DOMAIN\_CAMPED***  
***eSYS\_SRV\_DOMAIN\_UNKNOWN***

#### 9.18.4.3 enum NAS\_LTE\_CPHY\_CA\_BW\_NRB

Enumerator

***eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_6***  
***eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_15***  
***eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_25***  
***eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_50***  
***eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_75***  
***eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_100***

#### 9.18.4.4 enum NAS\_LTE\_CPHY\_SELL\_STATE

##### Enumerator

***eNAS\_LTE\_CPHY\_SELL\_STATE\_DECONFIGURED***  
***eNAS\_LTE\_CPHY\_SELL\_STATE\_CONFIGURED\_DEACTIVATED***  
***eNAS\_LTE\_CPHY\_SELL\_STATE\_CONFIGURED\_ACTIVATED***

### 9.18.5 Function Documentation

#### 9.18.5.1 ULONG GetACCOLC ( BYTE \* pACCOLC )

Retrieves information about the access overload class (ACCOLC)

##### Parameters

<i>pACCOLC[OUT]</i>	<ul style="list-style-type: none"> <li>• ACCOLC : Valid range is 0 to 15</li> </ul>
---------------------	---

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Technology Supported: CDMA  
 Timeout: 2 seconds

#### 9.18.5.2 ULONG GetANAAAAuthenticationStatus ( ULONG \* pStatus )

AN-AAA authentication status of the device.

##### Parameters

<i>pStatus[OUT]</i>	<ul style="list-style-type: none"> <li>• Status of last AN-AAA authentication attempt               <ul style="list-style-type: none"> <li>– 0 - Failure</li> <li>– 1 - Success</li> <li>– 2 - Not Requested</li> </ul> </li> </ul>
---------------------	---

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Technology Supported: CDMA  
 Timeout: 2 seconds

**9.18.5.3** **ULONG** GetCDMANetworkParameters ( **BYTE** \* *pSCI*, **BYTE** \* *pSCM*, **BYTE** \* *pRegHomeSID*, **BYTE** \* *pRegForeignSID*, **BYTE** \* *pRegForeignNID*, **BYTE** \* *pForceRev0*, **BYTE** \* *pCustomSCP*, **ULONG** \* *pProtocol*, **ULONG** \* *pBroadcast*, **ULONG** \* *pApplication*, **ULONG** \* *pRoaming* )

Gets the current CDMA network parameters

Parameters

<i>pSCI</i> [OUT]	<ul style="list-style-type: none"> <li>Slot cycle index           <ul style="list-style-type: none"> <li>– 0xFF-Unknown</li> </ul> </li> </ul>
<i>pSCM</i> [OUT]	<ul style="list-style-type: none"> <li>Station class mark           <ul style="list-style-type: none"> <li>– 0xFF-Unknown</li> </ul> </li> </ul>
<i>pRegHomeSID</i> [OUT]	<ul style="list-style-type: none"> <li>Register on home SID           <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>pRegForeignSID</i> [OUT]	<ul style="list-style-type: none"> <li>Register on foreign SID           <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>pRegForeignNID</i> [OUT]	<ul style="list-style-type: none"> <li>Register on foreign NID           <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>pForceRev0</i> [OUT]	<ul style="list-style-type: none"> <li>Force CDMA 1x-EV-DO Rev. 0 mode           <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>

<i>pCustomSCP[OUT]</i>	<ul style="list-style-type: none"> <li>• Use a custom config for CDMA 1x-EV-DO SCP <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>pProtocol[OUT]</i>	<ul style="list-style-type: none"> <li>• Protocol mask for custom SCP config <ul style="list-style-type: none"> <li>– 0x00000001 - Subtype 2 Physical Layer</li> <li>– 0x00000002 - Enhanced CCMAC</li> <li>– 0x00000004 - Enhanced ACMAC</li> <li>– 0x00000008 - Enhanced FTCMAC</li> <li>– 0x00000010 - Subtype 3 RTCMAC</li> <li>– 0x00000020 - Subsystem 1 RTCMAC</li> <li>– 0x00000040 - Enhanced Idle</li> <li>– 0x00000080 - Generic Multimode Capable Disc <a href="#">Port</a></li> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pBroadcast[OUT]</i>	<ul style="list-style-type: none"> <li>• Broadcast mask for custom SCP config <ul style="list-style-type: none"> <li>– 0x00000001 - Generic broadcast enabled</li> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pApplication[OUT]</i>	<ul style="list-style-type: none"> <li>• Application mask for custom SCP config <ul style="list-style-type: none"> <li>– 0x00000001 - SN Multiflow Packet Application</li> <li>– 0x00000002 - SN Enhanced Multiflow Packet Application</li> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pRoaming[OUT]</i>	<ul style="list-style-type: none"> <li>• Roaming preference <ul style="list-style-type: none"> <li>– 0 - Automatic</li> <li>– 1 - Home Only</li> <li>– 2 - Affiliated Roaming Only</li> <li>– 3 - Home and Affiliated Roaming</li> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA  
Timeout: 5 seconds

#### 9.18.5.4 **ULONG** GetHomeNetwork ( **WORD** \* *pMCC*, **WORD** \* *pMNC*, **BYTE** *nameSize*, **CHAR** \* *pName*, **WORD** \* *pSID*, **WORD** \* *pNID* )

Retrieves information about the home network of the device. For 3GPP2 home network information use GetHomeNetwork3GPP2.

## Parameters

<i>pMCC[OUT]</i>	<ul style="list-style-type: none"> <li>• Mobile country code (UMTS only).</li> </ul>
<i>pMNC[OUT]</i>	<ul style="list-style-type: none"> <li>• Mobile network code (UMTS only).</li> </ul>
<i>nameSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that 8 network name array can contain (UMTS only).</li> </ul>
<i>pName[OUT]</i>	<ul style="list-style-type: none"> <li>• Network name or description represented as a NULL terminated string (empty string returned when unknown) (UMTS only).</li> </ul>
<i>pSID[OUT]</i>	<ul style="list-style-type: none"> <li>• Home network system ID <ul style="list-style-type: none"> <li>– 0xFFFF - Unknown.</li> <li>– Only applies to cdma2000</li> </ul> </li> </ul>
<i>pNID[OUT]</i>	<ul style="list-style-type: none"> <li>• Home network ID <ul style="list-style-type: none"> <li>– 0xFFFF - Unknown.</li> <li>– Only applies to cdma2000</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

9.18.5.5 **ULONG** GetHomeNetwork3GPP2 ( **WORD** \* *pMCC*, **WORD** \* *pMNC*, **BYTE** *nameSize*, **CHAR** \* *pName*,  
**WORD** \* *pSID*, **WORD** \* *pNID*, **WORD** \* *pNw2MCC*, **WORD** \* *pNw2MNC*, **BYTE** \* *pNw2DescDisp*, **BYTE** \*  
*pNw2DescEnc*, **BYTE** \* *pNw2DescLen*, **BYTE** \* *pNw2Name* )

Retrieves information about the home network of the device. It will extract 3GPP2 Network Information also.

## Parameters

<i>pMCC[OUT]</i>	<ul style="list-style-type: none"> <li>• Mobile country code (UMTS only).</li> </ul>
<i>pMNC[OUT]</i>	<ul style="list-style-type: none"> <li>• Mobile network code (UMTS only).</li> </ul>
<i>nameSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that 8 network name array can contain (UMTS only).</li> </ul>
<i>pName[OUT]</i>	<ul style="list-style-type: none"> <li>• Network name or description represented as a NULL terminated string (empty string returned when unknown) (UMTS only).</li> </ul>
<i>pSID[OUT]</i>	<ul style="list-style-type: none"> <li>• Home network system ID <ul style="list-style-type: none"> <li>– 0xFFFF - Unknown.</li> <li>– Only applies to cdma2000</li> </ul> </li> </ul>
<i>pNID[OUT]</i>	<ul style="list-style-type: none"> <li>• Home network ID <ul style="list-style-type: none"> <li>– 0xFFFF - Unknown.</li> <li>– Only applies to cdma2000</li> </ul> </li> </ul>
<i>pNw2MCC[OUT]</i>	<ul style="list-style-type: none"> <li>• Mobile country code (3GPP2 only).</li> <li>• Range : 0 to 999</li> </ul>
<i>pNw2MNC[OUT]</i>	<ul style="list-style-type: none"> <li>• Mobile network code (3GPP2 only).</li> <li>• Range : 0 to 999</li> </ul>
<i>pNw2DescDisp[OUT]</i>	<ul style="list-style-type: none"> <li>• Network Name Display (3GPP2 only). -Valid Value <ul style="list-style-type: none"> <li>– 0x00 - Do not display</li> <li>– 0x01 - Display</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>

<i>pNw2DescDisp[OUT]</i>	<ul style="list-style-type: none"> <li>• Encoding of the network description (3GPP2 only).</li> <li>• Valid Value <ul style="list-style-type: none"> <li>– 0x00 - Octet, unspecified</li> <li>– 0x02 - 7-bit ASCII</li> <li>– 0x04 - Unicode</li> <li>– 0x09 - GSM 7-bit default</li> </ul> </li> </ul>
<i>nw2DescLen[OUT]</i>	<ul style="list-style-type: none"> <li>• Network Description Length (3GPP2 only).</li> </ul>
<i>pNw2Name[OUT]</i>	<ul style="list-style-type: none"> <li>• Network Name (3GPP2 only).</li> </ul>

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

Timeout: 2 seconds

#### 9.18.5.6 ULONG GetNetworkPreference ( ULONG \* pTechnologyPref, ULONG \* pDuration, ULONG \* pPersistentTechnologyPref )

Returns the network registration preference. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQGetSysSelectionPref\(\)](#) for new firmware versions and new modules



## Parameters

<i>pTechnologyPref[OUT]</i>	<ul style="list-style-type: none"> <li>• Bitmask representing the radio technology preference set.</li> <li>• No bits set indicates to the device to automatically determine the technology to use</li> <li>• Values: <ul style="list-style-type: none"> <li>– Bit 0 - Technology is 3GPP2</li> <li>– Bit 1 - Technology is 3GPP</li> </ul> </li> <li>• Any combination of the following may be returned: <ul style="list-style-type: none"> <li>– Bit 2 - Analog - AMPS if 3GPP2, GSM if 3GPP</li> <li>– Bit 3 - Digital - CDMA if 3GPP2, WCDMA if 3GPP</li> <li>– Bit 4 - HDR</li> <li>– Bit 5 - LTE</li> <li>– Bits 6 to 15 - Reserved</li> </ul> </li> </ul>
<i>pDuration[OUT]</i>	<ul style="list-style-type: none"> <li>• Duration of active preference <ul style="list-style-type: none"> <li>– 0 - Permanent</li> <li>– 1 - Power cycle</li> <li>– 2 - Until the end of the next call or a power cycle</li> <li>– 3 - Until the end of the next call, a specified time, or a power cycle</li> <li>– 4 to 6 - Until the end of the next call</li> </ul> </li> </ul>
<i>pPersistentTechnologyPref[OUT]</i>	<ul style="list-style-type: none"> <li>• Bit field representing persistent radio technology preference <ul style="list-style-type: none"> <li>– Same representation as the pTechnologyPref parameter</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.18.5.7 ULONG GetRFInfo ( BYTE \* pInstanceSize, struct RFBandInfoElements \* pRFBandInfo )

Sets the RFInfoList

## Parameters

<i>pInstanceSize</i> [I- N/OUT]	<ul style="list-style-type: none"> <li>• Upon input, maximum number of elements that the RF info instances array can contain.</li> <li>• Upon successful output, actual number of elements in RF info instances array.</li> </ul>
<i>pInstances</i> [OUT]	<ul style="list-style-type: none"> <li>• RF info instances array <ul style="list-style-type: none"> <li>– See <a href="#">RFBandInfoElements</a> for more information</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.18.5.8** **ULONG** GetServingNetwork ( **ULONG** \* *pRegistrationState*, **ULONG** \* *pCSDomain*, **ULONG** \* *pPSDomain*, **ULONG** \* *pRAN*, **BYTE** \* *pRadiolfacesSize*, **BYTE** \* *pRadiolfaces*, **ULONG** \* *pRoaming*, **WORD** \* *pMCC*, **WORD** \* *pMNC*, **BYTE** *nameSize*, **CHAR** \* *pName* )

Provides information about the system that provides service to the device. This API is deprecated on MC73xx/E-M73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSNasGetSysInfo\(\)](#) for new firmware versions and new modules

## Parameters

<i>pRegistration- State</i> [OUT]	<ul style="list-style-type: none"> <li>• Registration state: <ul style="list-style-type: none"> <li>– 0 - Not registered</li> <li>– 1 - Registered</li> <li>– 2 - Searching/Not Registered</li> <li>– 3 - Registration Denied</li> <li>– 4 - Unknown</li> </ul> </li> </ul>
---------------------------------------	---

<i>pCSDomain[OUT]</i>	<ul style="list-style-type: none"> <li>• Circuit switch domain status: <ul style="list-style-type: none"> <li>– 0 - Unknown/Not Applicable</li> <li>– 1 - Attached</li> <li>– 2 - Detached</li> </ul> </li> </ul>
<i>pPSDomain[OUT]</i>	<ul style="list-style-type: none"> <li>• Packet switch domain status <ul style="list-style-type: none"> <li>– 0 - Unknown/Not Applicable</li> <li>– 1 - Attached</li> <li>– 2 - Detached</li> </ul> </li> </ul>
<i>pRAN[OUT]</i>	<ul style="list-style-type: none"> <li>• Type of radio access network on which mobile is registered: <ul style="list-style-type: none"> <li>– 0 - Unknown</li> <li>– 1 - cdma2000 network</li> <li>– 2 - UMTS network</li> </ul> </li> </ul>
<i>pRadioIfaceSize[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Upon input, maximum number of elements that the radio interface array contain.</li> <li>• Upon successful output, actual number of elements in the radio interface array.</li> </ul>
<i>pRadioIface[OUT]</i>	<ul style="list-style-type: none"> <li>• An array of Radio Interface Technology <ul style="list-style-type: none"> <li>– See <a href="#">qaGobiApiTableRadioInterfaces.h</a> for the Radio Interface Technologies</li> </ul> </li> </ul>
<i>pRoaming[OUT]</i>	<ul style="list-style-type: none"> <li>• Roaming indicator</li> </ul>
<i>pMCC[OUT]</i>	<ul style="list-style-type: none"> <li>• Mobile country code</li> </ul>
<i>pMNC[OUT]</i>	<ul style="list-style-type: none"> <li>• Mobile network code</li> </ul>
<i>nameSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that network name array can contain; applicable only for UMTS networks</li> </ul>
<i>pName[OUT]</i>	<ul style="list-style-type: none"> <li>• Network name or description represented as a NULL terminated string; empty string is returned when unknown; applicable only for UMTS networks</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

### 9.18.5.9 ULONG GetServingNetworkCapabilities ( BYTE \* pDataCapsSize, BYTE \* pDataCaps )

Returns information regarding the data capabilities of the system that currently provides service to the device.

**Parameters**

<i>pDataCapsSize</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Upon input, the maximum number of elements the data capabilities array can contain.</li> <li>• Upon output, the actual number of elements in the data capabilities array.</li> </ul>
<i>pDataCaps</i> [OUT]	<ul style="list-style-type: none"> <li>• Data capabilities array of unsigned long type <ul style="list-style-type: none"> <li>– 1 - GPRS</li> <li>– 2 - EDGE</li> <li>– 3 - HSDPA</li> <li>– 4 - HSUPA</li> <li>– 5 - WCDMA</li> <li>– 6 - CDMA 1xRTT</li> <li>– 7 - CDMA 1xEV-DO Rev 0</li> <li>– 8 - CDMA 1xEV-DO Rev. A</li> <li>– 9 - GSM</li> <li>– 10 - EVDO Rev. B</li> <li>– 11 - LTE</li> <li>– 12 - HSDPA Plus</li> <li>– 13 - Dual Carrier HSDPA Plus</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

9.18.5.10 **ULONG** GetSignalStrengths ( **ULONG** \* *pArraySizes*, **INT8** \* *pSignalStrength*, **ULONG** \* *pRadioInterface* )

Returns the available signal strengths ( in dBm ) as measured by the device in an array. The API also provides the corresponding radio radio interfaces in an array.

## Parameters

<i>pArraySizes</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>• Upon input maximum number of elements that each array can contain.</li> <li>• Upon successful output actual number of elements in the array.</li> </ul>
<i>pSignal-Strength</i> [OUT]	<ul style="list-style-type: none"> <li>• Received signal strength array (in dBm)</li> </ul>
<i>pRadio-Interface</i> [OUT]	<ul style="list-style-type: none"> <li>• Radio interface technology array of the signal being measured <ul style="list-style-type: none"> <li>– See <a href="#">qaGobiApiTableRadioInterfaces.h</a> for Radio Interface info</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

## 9.18.5.11 ULONG InitiateDomainAttach ( ULONG action )

Initiates a domain attach/detach of the device. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSSetSysSelectionPref\(\)](#) for new firmware versions and new modules

## Parameters

<i>action</i> [IN]	<ul style="list-style-type: none"> <li>• <a href="#">Domain</a> action to attempt <ul style="list-style-type: none"> <li>1 - Attach</li> <li>2 - Detach</li> </ul> </li> </ul>
--------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 seconds

**9.18.5.12** `ULONG InitiateNetworkRegistration ( ULONG regType, WORD mcc, WORD mnc, ULONG rat )`

Initiates the network registration process. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSSetSysSelectionPref\(\)](#) and [SLQSSetBandPreference\(\)](#) for new firmware versions and new modules

## Parameters

<i>regType</i>	<ul style="list-style-type: none"> <li>Registration type <ul style="list-style-type: none"> <li>1 - Automatic</li> <li>2 - Manual</li> </ul> </li> </ul>
<i>mcc</i>	<ul style="list-style-type: none"> <li>Mobile country code</li> </ul>
<i>mnc</i>	<ul style="list-style-type: none"> <li>Mobile network code</li> </ul>
<i>rat</i>	<ul style="list-style-type: none"> <li>Radio access technology <ul style="list-style-type: none"> <li>4 - GSM</li> <li>5 - UMTS</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Timeout: 30 seconds

### 9.18.5.13 ULONG PerformNetworkScan ( BYTE \* *pInstanceSize*, BYTE \* *pInstances* )

Performs scan for available networks.

## Parameters

<i>pInstanceSize</i> [I-N/OUT]	<ul style="list-style-type: none"> <li>Upon input, maximum number of elements that the network info instance array can contain.</li> <li>Upon successful output, the actual number of elements in the network info instance array.</li> </ul>
<i>pInstances</i> [OUT]	<ul style="list-style-type: none"> <li>Network info instance array <ul style="list-style-type: none"> <li>See <a href="#">QmiNas3GppNetworkInfo</a></li> </ul> </li> </ul>



**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS  
Timeout: 5 minutes

**9.18.5.14 ULONG SetACCOLC ( CHAR \* *spc*, BYTE *accolc* )**

Sets the access overload class (ACCOLC)

**Parameters**

<i>spc</i> [IN]	<ul style="list-style-type: none"> <li>• service programming code NULL-terminated string of six digit</li> </ul>
<i>ACCOLC</i> [IN]	<ul style="list-style-type: none"> <li>• ACCOLC : Valid range is 0 to 15</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 5 seconds

**9.18.5.15 ULONG SetCDMANetworkParameters ( CHAR \* *pSPC*, BYTE \* *pForceRev0*, BYTE \* *pCustomSCP*, ULONG \* *pProtocol*, ULONG \* *pBroadcast*, ULONG \* *pApplication*, ULONG \* *pRoaming* )**

Sets the CDMA network parameters. Currently the modified settings will not be utilized until the device has been reset. For this reason, the recommended approach when using SetCDMANetworkParameters is for the application to perform the following steps:

1 - Call [SetCDMANetworkParameters\(\)](#) 2 - Call SetPower( 5 ) 3 - Call [QCWWANDisconnect\(\)](#) 4 - Reconnect after the device power cycles

## Parameters

<i>pSPC</i> [IN]	<ul style="list-style-type: none"> <li>• Six digit service programming code (not necessary when only the roaming field is being set)</li> </ul>
<i>pForceRev0</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional)Force CDMA 1x-EV-DO Rev. 0 mode <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled Note: Enabled can only be specified if pCustomSCP state is set to Disabled</li> </ul> </li> </ul>
<i>pCustomSCP</i> [I-N]	<ul style="list-style-type: none"> <li>• (Optional)Use a custom config for CDMA 1x-EV-DO SCP <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled Note: Enabled can only be specified if pForceRev0 is set to Disabled</li> </ul> </li> </ul>
<i>pProtocol</i> [IN]	<ul style="list-style-type: none"> <li>• Protocol mask for custom SCP config <ul style="list-style-type: none"> <li>– 0x00000001 - Subtype 2 Physical Layer</li> <li>– 0x00000002 - Enhanced CCMAC</li> <li>– 0x00000004 - Enhanced ACMAC</li> <li>– 0x00000008 - Enhanced FTCMAC</li> <li>– 0x00000010 - Subtype 3 RTCMAC</li> <li>– 0x00000020 - Subsystem 1 RTCMAC</li> <li>– 0x00000040 - Enhanced Idle</li> <li>– 0x00000080 - Generic Multimode Capable Disc <a href="#">Port</a></li> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pBroadcast</i> [IN]	<ul style="list-style-type: none"> <li>• Broadcast mask for custom SCP config <ul style="list-style-type: none"> <li>– 0x00000001 - Generic broadcast enabled</li> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pApplication</i> [IN]	<ul style="list-style-type: none"> <li>• Application mask for custom SCP config <ul style="list-style-type: none"> <li>– 0x00000001 - SN Multiflow Packet Application</li> <li>– 0x00000002 - SN Enhanced Multiflow Packet Application</li> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

<i>pRoaming</i> [IN]	<ul style="list-style-type: none"> <li>• Roaming preference <ul style="list-style-type: none"> <li>– 0 - Automatic</li> <li>– 1 - Home Only</li> <li>– 2 - Affiliated Roaming Only</li> <li>– 3 - Home and Affiliated Roaming</li> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
----------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 5 seconds

#### 9.18.5.16 ULONG SetNetworkPreference ( ULONG *technologyPref*, ULONG *duration* )

Sets the network registration preference. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSSetSysSelectionPref\(\)](#) for new firmware versions and new modules

**Parameters**

<i>technologyPref</i> [IN]	<ul style="list-style-type: none"> <li>• 2 Byte Bitmask representing radio technology preference <ul style="list-style-type: none"> <li>– No bits set indicates device to automatically determine the technology to use.</li> <li>– Type of technology <ul style="list-style-type: none"> <li>* Bit 0 - Technology is 3GPP2</li> <li>* Bit 1 - Technology is 3GPP</li> </ul> </li> <li>– Technology-specific protocol bitmask <ul style="list-style-type: none"> <li>* Bit 2 - Analog <ul style="list-style-type: none"> <li>· AMPS if 3GPP2, GSM if 3GPP</li> </ul> </li> <li>* Bit 3 - Digital <ul style="list-style-type: none"> <li>· CDMA if 3GPP2, WCDMA if 3GPP</li> </ul> </li> <li>* Bit 4 - HDR</li> <li>* Bit 5 - LTE</li> <li>* All other bits are reserved.</li> </ul> </li> </ul> </li> </ul>
<i>duration</i> [IN]	<ul style="list-style-type: none"> <li>• Duration of active preference <ul style="list-style-type: none"> <li>– 0 - Persistent</li> <li>– 1 - Power cycle</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.18.5.17 ULONG SLQSCfgSigInfo ( sigInfo \* pSigInfo )**

Sets the signal reporting thresholds. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use [SLQSNasConfigSigInfo2\(\)](#) instead for new firmware versions and new modules.

**Parameters**

<i>pSigInfo[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">sigInfo</a> for more information</li></ul>
---------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

**9.18.5.18 ULONG SLQSGetErrorRate ( GetErrRateResp \* pGetErrRateResp )**

This API retrieves current error rate information

**Parameters**

<i>pGetErrRateResp[OUT]</i>	<ul style="list-style-type: none"><li>• See <a href="#">GetErrRateResp</a> for more information</li></ul>
-----------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

9.18.5.19 **ULONG** SLQSGetNetworkTime ( **GetNetworkTimeResp** \* *pGetNetworkTimeResp* )

This API retrieves the last known network time information from the UE.

## Parameters

<i>pGetNetworkTimeResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">GetNetworkTimeResp</a> for more information</li> </ul>
----------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.18.5.20 ULONG SLQSGetOperatorNameData ( nasOperatorNameResp \* pOperatorNameData )

Get the operator name data from the network. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSGetPLMNName\(\)](#) for new firmware versions and new modules

## Parameters

<i>pOperatorNameData</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">nasOperatorNameResp</a> for more information</li> </ul>
--------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 10 seconds

#### 9.18.5.21 ULONG SLQSGetPLMNName ( nasPLMNNameReq \* pPLMNNameReq, nasPLMNNameResp \* pPLMNNameResp )

Get the operator name data from the network.

## Parameters

<i>pPLMNNameReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">nasPLMNNameReq</a> for more information</li> </ul>
<i>pPLMNNameResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">nasPLMNNameResp</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 10 seconds

**9.18.5.22 ULONG SLQSGetServingSystem ( qaQmiServingSystemParam \* pServingSystem )**

Provides information about the system that provides service to the device. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSNasGetSysInfo\(\)](#) for new firmware versions and new modules. Also report available radio interface technology. If there are more than one radio interface, please choose the right interface(usually the first pair).

- See [SLQSSetSysSelectionPref](#)

**Parameters**

<i>pServing-System</i> [OUT]	<ul style="list-style-type: none"> <li>• serving system parameters obtained from the system</li> </ul>
------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise.

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values.

**Note**

Timeout: 2 seconds

**9.18.5.23 ULONG SLQSGetSignalStrength ( struct slqsSignalStrengthInfo \* pSignalInfo )**

Queries the current signal strength as measured by the device. This API is deprecated on MC73xx/EM73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSNasGetSigInfo\(\)](#) for new firmware versions and new modules

**Parameters**

<i>pSignalInfo</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">slqsSignalStrengthInfo</a> for more information</li> </ul>
------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.18.5.24 ULONG SLQSGetSysSelectionPref ( sysSelectPrefInfo \* pSysSelectPrefInfo )**

Queries the different system selection preferences of the device.

**Parameters**

<i>pSysSelectPref-Info</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">sysSelectPrefInfo</a> for more information</li> </ul>
----------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.18.5.25 ULONG SLQSInitiateNetworkRegistration ( nasInitNetworkReg \* pNasInitNetRegistrationReg )**

Initiates the network registration process.

**Parameters**

<i>pNasInitNet-Registration-Req</i> [IN]	<ul style="list-style-type: none"> <li>Pointer to structure nasInitNetworkReq             <ul style="list-style-type: none"> <li>See <a href="#">nasInitNetworkReg</a> for more information</li> </ul> </li> </ul>
--	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS

Timeout: 30 seconds

**9.18.5.26 ULONG SLQSNasConfigSigInfo2 ( setSignalStrengthInfo \* pSetSignalStrengthInfo )**

Sets the signal strength reporting thresholds



## Parameters

<i>pSetSignalStrengthInfo[IN]</i>	<ul style="list-style-type: none"> <li>See <a href="#">setSignalStrengthInfo</a> for more information</li> </ul>
-----------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

Mixture of threshold and delta values can be provided in the request. But for each type and RAT, only one of threshold list or delta value is to be provided.

**9.18.5.27** `ULONG SLQSNasGet3GPP2Subscription ( nasGet3GPP2SubscriptionInfoReq * pGet3GPP2SubsInfoReq, nasGet3GPP2SubscriptionInfoResp * pGet3GPP2SubsInfoResp )`

This API retrieves 3GPP2 subscription-related information.

## Parameters

<i>pGet3GPP2SubsInfoReq[IN]</i>	<ul style="list-style-type: none"> <li>See <a href="#">nasGet3GPP2SubscriptionInfoReq</a> for more information</li> </ul>
<i>pGet3GPP2SubsInfoResp[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">nasGet3GPP2SubscriptionInfoResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA

Timeout: 2 seconds

This command retrieves 3GPP2 subscription-related information. The QMI\_ERR\_INTERNAL error is returned when no information can be retrieved from the modem.

**9.18.5.28** `ULONG SLQSNasGetCellLocationInfo ( nasCellLocationInfoResp * pNasCellLocationInfoResp )`

This API retrieves cell location-related information

## Parameters

<i>pNasCell-LocationInfo-Resp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nasCellLocationInfoResp</a> for more information</li> </ul>
--	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

This API retrieves cell location-related information, depending on current serving system.

#### 9.18.5.29 ULONG SLQSNasGetHDRColorCode ( nasGetHDRColorCodeResp \* pGetHDRColorCodeResp )

This API retrieves the current HDR color code value.

## Parameters

<i>pGetHDRColor-CodeResp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nasGetHDRColorCodeResp</a> for more information</li> </ul>
-----------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.18.5.30 ULONG SLQSNASGetLTEPHYCaInfo ( nasGetLTECphyCa \* pLTECphyCa )

This API Get LTE CPHY Carrier Info

## Parameters

<i>pLTECphyCa[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">nasGetLTECphyCa</a> for more information.</li> </ul>
-----------------------	---

## Returns

eQCWWAN\_ERR\_sNONE on success, eQCWWAN\_xxx error value otherwise.

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values.

9.18.5.31 **ULONG** SLQSNasGetSigInfo ( *nasGetSigInfoResp* \* *pGetSigInfoResp* )

This API queries information regarding the signal strength.

## Parameters

<i>pGetSigInfoResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">nasGetSigInfoResp</a> for more information</li> </ul>
------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

This command queries the signal strength information for currently active RATs. Information is reported only if the corresponding RATs have signal strength values to be reported. If no signal strength information is available for any RAT, the response message contains only the mandatory response message

#### 9.18.5.32 ULONG SLQSNasGetSysInfo ( nasGetSysInfoResp \* pGetSysInfoResp )

Provides the system information. This API is preferred when trying to get the service status info and serving system info. The API [SLQSGetServingSystem\(\)](#) reports similar NAS information, but it is deprecated. Please refer to the header description of API [SLQSGetServingSystem\(\)](#) for more information.

## Parameters

<i>pGetSysInfoResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">nasGetSysInfoResp</a> for more information</li> </ul>
------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

This API queries current serving system information, including registration information and system property. The registration information for all RATs specified in the mode capability setting are included regardless of registration status. The RAT-specific system property are included only for RATs that are specified in the mode capability setting and which are not in either No Service or Power Save modes.

#### 9.18.5.33 ULONG SLQSNasGetTxRxInfo ( nasGetTxRxInfoReq \* pGetTxRxInfoReq, nasGetTxRxInfoResp \* pGetTxRxInfoResp )

This API retrieves the detailed Tx/Rx information.

## Parameters

<i>pGetTxRxInfoReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">nasGetTxRxInfoReq</a> for more information</li> </ul>
<i>pGetTxRxInfoResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">nasGetTxRxInfoResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

This command retrieves Tx/Rx information for a radio interface. The Rx chain are included in the response message only if they are enabled.

#### 9.18.5.34 ULONG SLQSNasIndicationRegister ( BYTE *systemSelectionInd*, BYTE *DDTMInd*, BYTE *servingSystemInd* )

Register/De-register from NAS (Network access service) broadcast indications. Some callbacks would not be invoked if the indications are not registered. The details are provided in the parameter description.

## Parameters

<i>system-SelectionInd</i> [IN]	<ul style="list-style-type: none"> <li>• system selection preference indication registration. The following callbacks would not be invoked if the indication is disabled.  <a href="#">tFNRoamingIndicator</a> <a href="#">tFNDataCapabilities</a> and <a href="#">tFNServingSystem</a> <ul style="list-style-type: none"> <li>– 0x00 - for disable</li> <li>– 0x01 - for enable</li> <li>– 0xFF - No change - Specifying this parameter indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>
---------------------------------	---

<i>DDTMInd</i> [IN]	<ul style="list-style-type: none"> <li>• DDTM (Data Dedicated Transmission Mode) indication registration. <ul style="list-style-type: none"> <li>– 0x00 - for disable</li> <li>– 0x01 - for enable</li> <li>– 0xFF - No change - Specifying this parameter indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>
<i>servingSystemInd</i> [IN]	<ul style="list-style-type: none"> <li>• Serving system indication registration. The following callbacks would not be invoked if the indication is disabled. <a href="#">tFNBandPreference</a> <ul style="list-style-type: none"> <li>– 0x00 - for disable</li> <li>– 0x01 - for enable</li> <li>– 0xFF - No change - Specifying this parameter indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_sNONE on success, eQCWWAN\_xxx error value otherwise.

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values.

**Note**

Timeout: 2 seconds

#### 9.18.5.35 ULONG SLQSNasIndicationRegisterExt ( nasIndicationRegisterReq \* *pIndicationRegisterReq* )

This API Registers/De-registers for different NAS (Network access service) indications.

**Parameters**

<i>pIndicationRegisterReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">nasIndicationRegisterReq</a> for more information</li> </ul>
------------------------------------	---

**Returns**

eQCWWAN\_ERR\_sNONE on success, eQCWWAN\_xxx error value otherwise.

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values.

## Note

Timeout: 2 seconds

This API is used by a control point to register/deregister for different QMI\_NAS indications. The control point's registration state variables, controlling registration for indications, are modified to reflect the settings indicated in the parameters that are present in the request message. At least one optional parameter must be present in the request.

#### 9.18.5.36 ULONG SLQSNasIndicationRegisterLTECphyCa ( BYTE \* *bStatus* )

This API Registers/De-registers for NAS CPHY Carrier Info.

## Parameters

<i>bStatus</i> [IN]	<ul style="list-style-type: none"> <li>• Values <ul style="list-style-type: none"> <li>– 0 - De-register.</li> <li>– 1 - Register.</li> </ul> </li> </ul>
---------------------	---

## Returns

eQCWWAN\_ERR\_SNONE on success, eQCWWAN\_xxx error value otherwise.

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values.

#### 9.18.5.37 ULONG SLQSNASSwiGetChannelLock ( nasSwiGetChannelLockResp \* *pNasSwiGetChannelLockResp* )

This API queries the channel or cell which the UE is locked into.

## Parameters

<i>pNasSwiGetChannelLock</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">nasSwiGetChannelLockResp</a> for more information.</li> </ul>
------------------------------------	--

## Returns

eQCWWAN\_ERR\_SNONE on success, eQCWWAN\_xxx error value otherwise.

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values.

#### 9.18.5.38 ULONG SLQSNasSwiIndicationRegister ( NasSwiIndReg \* *pIndRegReq* )

sets the registration state for different QMI\_NAS SWI indications

## Parameters

<i>pIndRegReq</i> [IN]	<ul style="list-style-type: none"><li>• See <a href="#">NasSwiIndReg</a> for more information</li></ul>
------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.18.5.39 ULONG SLQSNasSwiModemStatus ( swiModemStatusResp \* pModemStatusResp )**

This API requests the device to return the current status of modem.

## Parameters

<i>pModemStatus-Resp</i> [OUT]	<ul style="list-style-type: none"><li>• See <a href="#">swiModemStatusResp</a> for more information</li></ul>
--------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

**9.18.5.40 ULONG SLQSNASSwiSetChannelLock ( nasSwiSetChannelLockReq \* pNasSwiSetChannelLockReq )**

This API allows the host to lock the UE to a specific channel or cell.

## Parameters

<i>pNasSwiSet-ChannelLock-Req</i> [IN]	<ul style="list-style-type: none"><li>• See <a href="#">nasSwiSetChannelLockReq</a> for more information.</li></ul>
--	---

## Returns

eQCWWAN\_ERR\_sNONE on success, eQCWWAN\_xxx error value otherwise.



#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values.

#### Note

The settings are persistent across reboots.

#### 9.18.5.41 ULONG SLQSPerformNetworkScan ( [slqsNetworkScanInfo](#) \* *pNetworkInfo* )

Performs scan for available networks and scans for RAT info as well.

##### Parameters

<i>pNetworkInfo</i> [I- N/OUT]	<ul style="list-style-type: none"><li>• See <a href="#">slqsNetworkScanInfo</a> for more information</li><li>• Valid pointers to the following structure members are mandatory<ul style="list-style-type: none"><li>– <i>pNetworkInfoInstances</i></li><li>– <i>pNetworkInfo</i></li></ul></li></ul>
-----------------------------------	--

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS  
Timeout: 5 minutes

**9.18.5.42   ULONG SLQSSetBandPreference (   ULONGLONG *bandpreference* )**

Provides information about the band preference.

## Parameters

<i>bandpreference</i> [IN]	<ul style="list-style-type: none"> <li>• Bit mask representing the band preference to be set.</li> <li>• Bit position meanings: <ul style="list-style-type: none"> <li>– 0 - BC0_A - Band Class 0, A-System</li> <li>– 1 - BC0_B - Band Class 0, B-System, Band Class 0 AB , GSM 850 Band</li> <li>– 2 - BC1 - Band Class 1, all blocks</li> <li>– 3 - BC2 - Band Class 2 place holder</li> <li>– 4 - BC3 - Band Class 3, A-System</li> <li>– 5 - BC4 - Band Class 4, all blocks</li> <li>– 6 - BC5 - Band Class 5, all blocks</li> <li>– 7 - GSM_DCS_1800 - GSM DCS band</li> <li>– 8 - GSM_EGSM_900 - GSM Extended GSM (E-GSM) band</li> <li>– 9 - GSM_PGSM_900 - GSM Primary GSM (P-GSM) band</li> <li>– 10 - BC6 - Band Class 6</li> <li>– 11 - BC7 - Band Class 7</li> <li>– 12 - BC8 - Band Class 8</li> <li>– 13 - BC9 - Band Class 9</li> <li>– 14 - BC10 - Band Class 10</li> <li>– 15 - BC11 - Band Class 11</li> <li>– 16 - GSM_450 - GSM 450 band</li> <li>– 17 - GSM_480 - GSM 480 band</li> <li>– 18 - GSM_750 - GSM 750 band</li> <li>– 19 - GSM_850 - GSM 850 band</li> <li>– 20 - GSM_RGSM_900 - GSM Railways GSM Band</li> <li>– 21 - GSM_PCS_1900 - GSM PCS band</li> <li>– 22 - WCDMA_I_IMT_2000 - WCDMA EUROPE JAPAN and CHINA IMT 2100 band</li> <li>– 23 - WCDMA_II_PCS_1900 - WCDMA US PCS 1900 band</li> <li>– 24 - WCDMA_III_1700 - WCDMA EUROPE and CHINA DCS 1800 band</li> <li>– 25 - WCDMA_IV_1700 - WCDMA US 1700 band</li> <li>– 26 - WCDMA_V_850 - WCDMA US 850 band</li> <li>– 27 - WCDMA_VI_800 - WCDMA JAPAN 800 band</li> <li>– 28 - BC12 - Band Class 12</li> <li>– 29 - BC14 - Band Class 14</li> <li>– 30 - RESERVED_2 - Reserved 2</li> <li>– 31 - BC15 - Band Class 15</li> <li>– 32 - 47 - Reserved</li> <li>– 48 - WCDMA_VII_2600 - WCDMA EUROPE 2600 band</li> <li>– 49 - WCDMA_VIII_900 - WCDMA EUROPE and JAPAN 900 band</li> <li>– 50 - WCDMA_IX_1700 - WCDMA JAPAN 1700 band</li> <li>– 51 to 55 - Reserved</li> <li>– 56 - BBC16 - Band Class 16</li> <li>– 57 - BC17 - Band Class 17</li> <li>– 58 - BC18 - Band Class 18</li> <li>– 59 - BC19 - Band Class 19</li> <li>– 60 to 64 - Reserved</li> </ul> </li> </ul>
Generated on Tue Jul 12 2016 10:59:49 for LinuxQMSDK by Doxygen	

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise.

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values.

**Note**

Timeout: 2 seconds

**9.18.5.43 ULONG SLQSSetSysSelectionPref ( sysSelectPrefParams \* pSysSelectPrefParams )**

Sets the different system selection preferences of the device.

**Parameters**

<i>pSysSelectPrefParams</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">sysSelectPrefParams</a> for more information</li> </ul>
----------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.18.5.44 ULONG SLQSSwiGetHDRPersonality ( HDRPersonalityResp \* pHDRPersonalityResp )**

This API retrieves HDR Personality related information

**Parameters**

<i>pHDRPersonalityResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">HDRPersonalityResp</a> for more information</li> </ul>
----------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 5 seconds

**9.18.5.45 ULONG SLQSSwiGetHDRProtSubtype ( HDRProtSubtypResp \* pHDRProtSubtypResp )**

This API retrieves HDR Prototype Subtype related information

## Parameters

<i>pHDRProt-SubtypResp[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">HDRProtSubtypResp</a> for more information</li> </ul>
---------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA  
Timeout: 5 seconds

#### 9.18.5.46 ULONG SLQSSwiGetHRPDStats ( GetHRPDStatsResp \* pGetHRPDStatsResp )

This API retrieves currently acquired HRPD system statistics

## Parameters

<i>pGetHRPD-StatsResp[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">GetHRPDStatsResp</a> for more information</li> </ul>
--------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.18.5.47 ULONG SLQSSwiGetLteCQI ( LteCQIParm \* pLteCQIResp )

This API Fetch CQI parameters for LTE data session

## Parameters

<i>pLteCQIParm[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">LteCQIParm</a> for more information</li> </ul>
-------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

**9.18.5.48 ULONG SLQSSwiNetworkDebug ( NetworkDebugResp \* pNetworkDebugResp )**

This API retrieves device and network status details

**Parameters**

<i>pNetworkDebugResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">NetworkDebugResp</a> for more information</li> </ul>
--------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 seconds

**9.18.5.49 ULONG SLQSSwiPSDetach ( PSDetachReq \* pPSDetachReq )**

This API detaches PS connection.

**Parameters**

<i>pPSDetachReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">PSDetachReq</a> for more information</li> </ul>
--------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 5 seconds

**9.19 qaGobiApiOadm.h File Reference**

Open Mobile Alliance Device Management Service API function prototypes.

## Functions

- [ULONG OMADMStartSession](#) ([ULONG](#) sessionType)
- [ULONG OMADMCancelSession](#) ( )
- [ULONG OMADMGetSessionInfo](#) ([ULONG](#) \*pSessionState, [ULONG](#) \*pSessionType, [ULONG](#) \*pFailureReason, [BYTE](#) \*pRetryCount, [WORD](#) \*pSessionPause, [WORD](#) \*pTimeRemaining)
- [ULONG OMADMGetPendingNIA](#) ([ULONG](#) \*pSessionType, [USHORT](#) \*pSessionID)

### 9.19.1 Detailed Description

Open Mobile Alliance Device Management Service API function prototypes.

### 9.19.2 Function Documentation

#### 9.19.2.1 [ULONG OMADMCancelSession](#) ( )

Cancels an ongoing OMA-DM session.

##### Parameters

<i>None</i>	
-------------	--

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Technology Supported: CDMA  
Timeout: 2 seconds

#### 9.19.2.2 [ULONG OMADMGetPendingNIA](#) ( [ULONG](#) \* *pSessionType*, [USHORT](#) \* *pSessionID* )

Returns information about the pending network-initiated alert

##### Parameters

<i>SessionType[O-UT]</i>	<ul style="list-style-type: none"><li>• Session Type<ul style="list-style-type: none"><li>– 0x04 - Network-initiated PRL update</li><li>– 0x05 - Network-initiated device configure</li></ul></li></ul>
--------------------------	---

<i>SessionID[OUT]</i>	<ul style="list-style-type: none"> <li>• Session Id <ul style="list-style-type: none"> <li>– Unique session ID for NIA request</li> </ul> </li> </ul>
-----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 2 seconds

**9.19.2.3    `ULONG OMADMGetSessionInfo ( ULONG * pSessionState, ULONG * pSessionType, ULONG * pFailureReason, BYTE * pRetryCount, WORD * pSessionPause, WORD * pTimeRemaining )`**

Returns information related to the current (or previous if no session is active) OMA-DM session.

**Parameters**

<i>SessionState[OUT]</i>	<ul style="list-style-type: none"> <li>• Session state <ul style="list-style-type: none"> <li>– 0x00 - Complete, information was updated</li> <li>– 0x01 - Complete, update information is unavailable</li> <li>– 0x02 - Failed</li> <li>– 0x03 - Retrying</li> <li>– 0x04 - Connecting</li> <li>– 0x05 - Connected</li> <li>– 0x06 - Authenticated</li> <li>– 0x07 - Mobile Directory Number (MDN) downloaded</li> <li>– 0x08 - Mobile Station Identifier (MSID) downloaded</li> <li>– 0x09 - PRL downloaded</li> <li>– 0x0A - Mobile IP (MIP) profile downloaded</li> </ul> </li> </ul>
--------------------------	---



<i>sessionType[OUT]</i>	<ul style="list-style-type: none"> <li>• Session State <ul style="list-style-type: none"> <li>– 0x00 - Client-initiated device configure</li> <li>– 0x01 - Client-initiated PRL update</li> <li>– 0x02 - Client-initiated hands-free activation</li> <li>– 0x03 - Device-initiated hands-free activation</li> <li>– 0x04 - Network-initiated PRL update</li> <li>– 0x05 - Network-initiated device configure</li> </ul> </li> </ul>
<i>FailureReason[OUT]</i>	<ul style="list-style-type: none"> <li>• Session failure reason (when state indicates failure) <ul style="list-style-type: none"> <li>– 0x00 - Unknown</li> <li>– 0x01 - Network is unavailable</li> <li>– 0x02 - Server is unavailable</li> <li>– 0x03 - Authentication failed</li> <li>– 0x04 - Maximum retry exceeded</li> <li>– 0x05 - Session is cancelled</li> </ul> </li> </ul>
<i>RetryCount[OUT]</i>	<ul style="list-style-type: none"> <li>• Session retry count (when state indicates retrying)</li> </ul>
<i>SessionPause[OUT]</i>	<ul style="list-style-type: none"> <li>• Session pause timer (in seconds , when state indicates retrying)</li> </ul>
<i>Time-Remaining[OUT]</i>	<ul style="list-style-type: none"> <li>• Pause time remaining (in seconds , when state indicates retrying)</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 2 seconds

**9.19.2.4 ULONG OMADMStartSession ( ULONG sessionType )**

Starts an OMA-DM session.

## Parameters

<i>sessionType</i>	<ul style="list-style-type: none"> <li>• Session type <ul style="list-style-type: none"> <li>– 0x00 - Client-initiated device configure</li> <li>– 0x01 - Client-initiated PRL update</li> <li>– 0x02 - Client-initiated hands-free activation</li> </ul> </li> </ul>
--------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA  
Timeout: 2 seconds

## 9.20 qaGobiApiPds.h File Reference

Position Determination Service API function prototypes.

### Data Structures

- struct [PDSPositionData](#)
- struct [GPSSStateInfo](#)
- struct [PDSPosMethodStateReq](#)

### Macros

- #define [DEFAULTBYTEVALUE](#) 0xFF
- #define [DEFAULTWORDVALUE](#) 0xFFFF
- #define [DEFAULTLONGVALUE](#) 0xFFFFFFFF

### Enumerations

- enum {  
[eSetServiceAutomaticTrackingDisable](#) =0,  
[eSetServiceAutomaticTrackingEnable](#) =1 }

### Functions

- [ULONG](#) [GetPDSSState](#) ([ULONG](#) \*pEnabledStatus, [ULONG](#) \*pTrackingStatus)
- [ULONG](#) [SetPDSSState](#) ([ULONG](#) enable)
- [ULONG](#) [StartPDSTrackingSessionExt](#) ([BYTE](#) sessionControl, [BYTE](#) sessionType, [BYTE](#) sessionOperation, [BYTE](#) sessionServerOption, [BYTE](#) fixTimeout, [ULONG](#) fixInterval, [ULONG](#) fixCount, [ULONG](#) fixAccuracy)

- [ULONG StopPDSTrackingSession](#) ( )
- [ULONG PDSInjectTimeReference](#) ( [ULONGLONG](#) systemTime, [USHORT](#) systemDiscontinuities)
- [ULONG GetPDSDefaults](#) ( [ULONG](#) \*pOperation, [BYTE](#) \*pTimeout, [ULONG](#) \*pInterval, [ULONG](#) \*pAccuracy)
- [ULONG SetPDSDefaults](#) ( [ULONG](#) operation, [BYTE](#) timeout, [ULONG](#) interval, [ULONG](#) accuracy)
- [ULONG GetXTRAAutomaticDownload](#) ( [ULONG](#) \*pbEnabled, [USHORT](#) \*pInterval)
- [ULONG SetXTRAAutomaticDownload](#) ( [ULONG](#) bEnabled, [USHORT](#) interval)
- [ULONG GetXTRANetwork](#) ( [ULONG](#) \*pPreference)
- [ULONG SetXTRANetwork](#) ( [ULONG](#) preference)
- [ULONG GetXTRAValidity](#) ( [USHORT](#) \*pGPSWeek, [USHORT](#) \*pGPSWeekOffset, [USHORT](#) \*pDuration)
- [ULONG ForceXTRADownload](#) ( )
- [ULONG GetServiceAutomaticTracking](#) ( [ULONG](#) \*pbAuto)
- [ULONG SetServiceAutomaticTracking](#) ( [ULONG](#) bAuto)
- [ULONG GetPortAutomaticTracking](#) ( [ULONG](#) \*pbAuto)
- [ULONG SetPortAutomaticTracking](#) ( [ULONG](#) bAuto)
- [ULONG ResetPDSData](#) ( [ULONG](#) \*pGPSDataMask, [ULONG](#) \*pCellDataMask)
- [ULONG SLQSSetAGPSConfig](#) ( [ULONG](#) \*pServerAddress, [ULONG](#) \*pServerPort, [BYTE](#) \*pServerURL, [BYTE](#) \*pServerURLLength, [BYTE](#) \*pNetworkMode)
- [ULONG SLQSPDSInjectAbsoluteTimeReference](#) ( [ULONGLONG](#) timeMsec, [ULONG](#) timeUncMsec, [BYTE](#) timeBase, [BYTE](#) forceFlag)
- [ULONG SLQSGetAGPSConfig](#) ( [ULONG](#) \*pServerAddress, [ULONG](#) \*pServerPort, [BYTE](#) \*pServerURL, [BYTE](#) \*pServerURLLength, [BYTE](#) \*pNetworkMode)
- [ULONG SLQSPDSInjectPositionData](#) (struct [PDSPositionData](#) \*pPositionData)
- [ULONG SLQSPDSDeterminePosition](#) ( )
- [ULONG SLQSGetGPSSStateInfo](#) ( [GPSSStateInfo](#) \*pGPSSStateInfo)
- [ULONG SLQSSetPositionMethodState](#) ( [PDSPosMethodStateReq](#) \*pPDSPosMethodStateReq)

### 9.20.1 Detailed Description

Position Determination Service API function prototypes.

### 9.20.2 Macro Definition Documentation

9.20.2.1 `#define DEFAULTBYTEVALUE 0xFF`

9.20.2.2 `#define DEFAULTLONGVALUE 0xFFFFFFFF`

9.20.2.3 `#define DEFAULTWORDVALUE 0xFFFF`

### 9.20.3 Enumeration Type Documentation

9.20.3.1 anonymous enum

Enumerator

***eSetServiceAutomaticTrackingDisable***

***eSetServiceAutomaticTrackingEnable***

### 9.20.4 Function Documentation

9.20.4.1 [ULONG ForceXTRADownload](#) ( )

Forces the XTRA database to be downloaded to the device.

## Parameters

<i>none</i>	
-------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.2 ULONG GetPDSDefaults ( ULONG \* *pOperation*, BYTE \* *pTimeout*, ULONG \* *pInterval*, ULONG \* *pAccuracy* )

Returns the default tracking session configuration. The tracking session configuration is used when a tracking session is automatically started using SetServiceAutomaticTracking or due to the device detecting an application opening the NMEA port.

## Parameters

<i>pOperation</i> [OUT]	<ul style="list-style-type: none"> <li>Current session operating mode <ul style="list-style-type: none"> <li>0 - Standalone</li> <li>1 - MS based</li> <li>2 - MS assisted</li> </ul> </li> </ul>
<i>pTimeout</i> [OUT]	<ul style="list-style-type: none"> <li>Maximum amount of time (seconds) to work on each fix, maximum is 255</li> </ul>
<i>pInterval</i> [OUT]	<ul style="list-style-type: none"> <li>Interval (seconds) between fix requests</li> </ul>
<i>pAccuracy</i> [OUT]	<ul style="list-style-type: none"> <li>Preferred accuracy threshold (meters)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.3 ULONG GetPDSState ( ULONG \* *pEnabledStatus*, ULONG \* *pTrackingStatus* )

Returns the current PDS state.

## Parameters

<i>pEnabled-Status[OUT]</i>	<ul style="list-style-type: none"> <li>Current PDS state <ul style="list-style-type: none"> <li>0 - disable</li> <li>1 - enable</li> </ul> </li> </ul>
<i>pTracking-Status[OUT]</i>	<ul style="list-style-type: none"> <li>Current PDS tracking session state</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Unknown</li> <li>0x01 - Inactive</li> <li>0x02 - Active</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

## 9.20.4.4 ULONG GetPortAutomaticTracking ( ULONG \* pbAuto )

Returns the automatic tracking configuration for the NMEA COM port.

## Parameters

<i>pbAuto[OUT]</i>	<ul style="list-style-type: none"> <li>Automatic tracking enabled for NMEA COM port <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> </ul>
--------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

**9.20.4.5   ULONG   GetServiceAutomaticTracking (   ULONG \* *pbAuto* )**

Returns the automatic tracking state for the service.

## Parameters

<i>pbAuto</i> [OUT]	<ul style="list-style-type: none"> <li>Automatic tracking session started for service <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> </ul>
---------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.6 ULONG GetXTRAAutomaticDownload ( ULONG \* *pbEnabled*, USHORT \* *pInterval* )

Returns the XTRA automatic database download configuration.

## Parameters

<i>pbEnabled</i> [OUT]	<ul style="list-style-type: none"> <li>Automatic XTRA download status <ul style="list-style-type: none"> <li>0 - Disabled</li> <li>1 - Enabled</li> </ul> </li> </ul>
<i>pInterval</i> [OUT]	<ul style="list-style-type: none"> <li>Interval (hours) between XTRA downloads</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.7 ULONG GetXTRANetwork ( ULONG \* *pPreference* )

Returns the XTRA WWAN network preference. When automatic XTRA database downloading is enabled this preference determines which WWAN networks will be used to perform the XTRA database download.

## Parameters

<i>pPreference</i> [OUT]	<ul style="list-style-type: none"> <li>• XTRA WWAN network preference <ul style="list-style-type: none"> <li>– 0x00 - None (any available network)</li> <li>– 0x01 - Home-only, only when on home systems</li> <li>– 0x02 - Roam-only, only when on non-home systems</li> </ul> </li> </ul>
--------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.8 ULONG GetXTRAVValidity ( USHORT \* pGPSWeek, USHORT \* pGPSWeekOffset, USHORT \* pDuration )

Returns the XTRA database validity period. When automatic XTRA database downloading is enabled the validity period determines when the XTRA database will be updated through a new download.

## Parameters

<i>pGPSWeek</i> [OUT]	<ul style="list-style-type: none"> <li>• Starting GPS week of validity period</li> </ul>
<i>pGPSWeekOffset</i> [OUT]	<ul style="list-style-type: none"> <li>• Starting GPS week offset (minutes) of validity period</li> </ul>
<i>pDuration</i> [OUT]	<ul style="list-style-type: none"> <li>• Length of validity period (hours)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.9 ULONG PDSInjectTimeReference ( ULONGLONG systemTime, USHORT systemDiscontinuities )

Injects a system time into the PDS engine.



## Parameters

<i>systemTime</i>	<ul style="list-style-type: none"> <li>• System time( milliseconds )</li> </ul>
<i>system-Discontinuities</i>	<ul style="list-style-type: none"> <li>• Number of system time discontinuities</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.10 ULONG ResetPDSData ( ULONG \* pGPSDataMask, ULONG \* pCellDataMask )

Resets the specified PDS data.

## Parameters

<i>pGPSDataMask[IN]</i>	<ul style="list-style-type: none"> <li>• Bitmask of GPS data to clear (optional) <ul style="list-style-type: none"> <li>– 0x00000001 - EPH</li> <li>– 0x00000002 - ALM</li> <li>– 0x00000004 - POS</li> <li>– 0x00000008 - TIME</li> <li>– 0x00000010 - IONO</li> <li>– 0x00000020 - UTC</li> <li>– 0x00000040 - HEALTH</li> <li>– 0x00000080 - SVDIR</li> <li>– 0x00000100 - SVSTEER</li> <li>– 0x00000200 - SADATA</li> <li>– 0x00000400 - RTI</li> <li>– 0x00000800 - ALM_CORR</li> <li>– 0x00001000 - FREQ_BIAS_EST</li> </ul> </li> </ul>
-------------------------	--

<i>pCellDataMask</i> [-IN]	<ul style="list-style-type: none"> <li>• Bitmask of cell data to clear (optional) <ul style="list-style-type: none"> <li>– 0x00000001 - POS</li> <li>– 0x00000002 - LATEST_GPS_POS</li> <li>– 0x00000004 - OTA_POS</li> <li>– 0x00000008 - EXT_REF_POS</li> <li>– 0x00000010 - TIMETAG</li> <li>– 0x00000020 - CELLID</li> <li>– 0x00000040 - CACHED_CELLID</li> <li>– 0x00000080 - LAST_SRV_CELL</li> <li>– 0x00000100 - CUR_SRV_CELL</li> <li>– 0x00000200 - NEIGHBOR_INFO</li> </ul> </li> </ul>
----------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Seconds

#### 9.20.4.11 **ULONG** SetPDSDefaults ( **ULONG** operation, **BYTE** timeout, **ULONG** interval, **ULONG** accuracy )

Sets the default tracking session configuration. The tracking session configuration is used when a tracking session is automatically started using SetServiceAutomaticTracking or due to the device detecting an application opening the NMEA port.

**Parameters**

<i>operation</i>	<ul style="list-style-type: none"> <li>• Current session operating mode <ul style="list-style-type: none"> <li>– 0 - Standalone</li> <li>– 1 - MS based</li> <li>– 2 - MS assisted</li> </ul> </li> </ul>
------------------	---

<i>timeout</i>	<ul style="list-style-type: none"><li>• Maximum amount of time (seconds) to work on each fix, maximum is 255</li></ul>
<i>interval</i>	<ul style="list-style-type: none"><li>• Interval (seconds) between fix requests</li></ul>
<i>accuracy</i>	<ul style="list-style-type: none"><li>• Preferred accuracy threshold (meters)</li></ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Seconds

**9.20.4.12 ULONG SetPDSSState ( ULONG enable )**

Sets the PDS state.

**Parameters**

<i>enable[IN]</i>	<ul style="list-style-type: none"><li>• Desired PDS state<ul style="list-style-type: none"><li>– Zero - disable</li><li>– Non-Zero - enable</li></ul></li></ul>
-------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 Seconds

**9.20.4.13 ULONG SetPortAutomaticTracking ( ULONG bAuto )**

Sets the automatic tracking configuration for the NMEA COM port.

## Parameters

<i>bAuto</i> [IN]	<ul style="list-style-type: none"> <li>• Enable automatic tracking for NMEA COM port <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> </ul> </li> </ul>
-------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.14 ULONG SetServiceAutomaticTracking ( ULONG *bAuto* )

Sets the automatic tracking state for the service. Tracking session being started using the default session configuration. Auto-tracking continues to generate fixes indefinitely until requested to be disabled. In StartPDSTracking-SessionExt a tracking session get started using the specified session control method and input parameters. After completion of requested no. of position fixes or service times out to perform fix, tracking session ends and GPS service deactivates.

## Parameters

<i>bAuto</i> [IN]	<ul style="list-style-type: none"> <li>• Automatic tracking session started for service <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> </ul> </li> </ul>
-------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.15 ULONG SetXTRAAutomaticDownload ( ULONG *bEnabled*, USHORT *interval* )

Sets the XTRA automatic database download configuration.

## Parameters

<i>bEnabled</i> [IN]	<ul style="list-style-type: none"> <li>Automatic XTRA download status <ul style="list-style-type: none"> <li>0 - Disabled</li> <li>1 - Enabled</li> </ul> </li> </ul>
<i>interval</i> [IN]	<ul style="list-style-type: none"> <li>Interval (hours) between XTRA downloads</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

9.20.4.16 ULONG SetXTRANetwork ( ULONG *preference* )

Sets the XTRA WWAN network preference. When automatic XTRA database downloading is enabled this preference determines which WWAN networks will be used to perform the XTRA database download.

## Parameters

<i>preference</i> [IN]	<ul style="list-style-type: none"> <li>XTRA WWAN network preference <ul style="list-style-type: none"> <li>0x00 - None (any available network)</li> <li>0x01 - Home-only, only when on home systems</li> <li>0x02 - Roam-only, only when on non-home systems</li> </ul> </li> </ul>
------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

9.20.4.17 ULONG SLQSGetAGPSConfig ( ULONG \* *pServerAddress*, ULONG \* *pServerPort*, BYTE \* *pServerURL*, BYTE \* *pServerURLLength*, BYTE \* *pNetworkMode* )

Gets the PDS AGPS (MS-based) configuration.

## Parameters

<i>pServer-Address[OUT]</i>	<ul style="list-style-type: none"> <li>IPv4 address of AGPS server. "0" if not set</li> </ul>
<i>pServerPort[OUT]</i>	<ul style="list-style-type: none"> <li>Port number of AGPS server. "0" if not set</li> </ul>
<i>pServerURL[OUT]</i>	<ul style="list-style-type: none"> <li>URL of the AGPS server. "0" if not set</li> </ul>
<i>pServerURL-Length[OUT]</i>	<ul style="list-style-type: none"> <li>URL length of AGPS server. "0" if not set</li> </ul>
<i>pNetworkMode[IN]</i>	<ul style="list-style-type: none"> <li>Network Mode of AGPS Server [optional - should be present in Multimode Systems] <ul style="list-style-type: none"> <li>0x00 - UMTS</li> <li>0x01 - CDMA</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

#### 9.20.4.18 ULONG SLQSGetGPSStateInfo ( GPSStateInfo \* pGPSStateInfo )

Queries the MSM GPS server for receiver state information

## Parameters

<i>pGPSStateInfo[OUT]</i>	<ul style="list-style-type: none"> <li>contains the GPS State Info</li> <li>See <a href="#">GPSStateInfo</a> for more information</li> </ul>
---------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Seconds

**9.20.4.19    ULONG SLQSPDSDeterminePosition (    )**

Requests the MSM GPS service to obtain the current position for manually controlled tracking sessions.

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 5 Seconds

**9.20.4.20    ULONG SLQSPDSInjectAbsoluteTimeReference (    ULONGLONG *timeMsec*,    ULONG *timeUncMsec*,    BYTE *timeBase*,    BYTE *forceFlag* )**

Injects a absolute time reference into the PDS engine.

**Parameters**

<i>timeMsec</i> [IN]	<ul style="list-style-type: none"> <li>Represents the number of milliseconds elapsed since either a GPS or UTC time base. If the time base is UTC, this value should NOT include leap seconds</li> </ul>
<i>timeUncMsec</i> [IN]	<ul style="list-style-type: none"> <li>Time uncertainty in milliseconds</li> </ul>
<i>timeBase</i> [IN]	<ul style="list-style-type: none"> <li>Time base               <ul style="list-style-type: none"> <li>0x00 - GPS (midnight, Jan 6, 1980)</li> <li>0x01 - UTC (midnight, Jan 1, 1970)</li> </ul> </li> </ul>
<i>forceFlag</i> [IN]	<ul style="list-style-type: none"> <li>Force acceptance of data</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Seconds

**9.20.4.21    ULONG SLQSPDSInjectPositionData (    struct PDSPositionData \* *pPositionData* )**

Injects position data into the PDS engine.

## Parameters

<i>pPositionData</i> [I-N]	<ul style="list-style-type: none"> <li>contains the position data to be injected to the PDS engine</li> </ul>
----------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds

**9.20.4.22** **ULONG** SLQSSetAGPSConfig ( **ULONG** \* *pServerAddress*, **ULONG** \* *pServerPort*, **BYTE** \* *pServerURL*, **BYTE** \* *pServerURLLength*, **BYTE** \* *pNetworkMode* )

Sets the PDS AGPS (MS-based) configuration.

## Parameters

<i>pServerAddress</i> [IN]	<ul style="list-style-type: none"> <li>IPv4 address of AGPS server [optional]</li> </ul>
<i>pServerPort</i> [IN]	<ul style="list-style-type: none"> <li><a href="#">Port</a> number of AGPS server [optional - should be present when pServerAddress is present]</li> </ul>
<i>pServerURL</i> [IN]	<ul style="list-style-type: none"> <li>URL of the AGPS server [optional]</li> </ul>
<i>pServerURLLength</i> [IN]	<ul style="list-style-type: none"> <li>URL length of AGPS server [optional - should be present when pServerURL is present]</li> </ul>
<i>pNetworkMode</i> [IN]	<ul style="list-style-type: none"> <li>Network Mode of AGPS Server [optional - should be present in Multimode Systems] <ul style="list-style-type: none"> <li>0x00 - UMTS</li> <li>0x01 - CDMA</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Seconds



9.20.4.23 **ULONG** SLQSSetPositionMethodState ( **PDSPosMethodStateReq** \* *pPDSPosMethodStateReq* )

Sets the state of positioning methods for the device.

## Parameters

<i>pPDSPos-MethodState-Req</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">PDSPosMethodStateReq</a> for more information</li> </ul>
-------------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Seconds

**9.20.4.24** **ULONG** StartPDSTrackingSessionExt ( **BYTE** *sessionControl*, **BYTE** *sessionType*, **BYTE** *sessionOperation*, **BYTE** *sessionServerOption*, **BYTE** *fixTimeout*, **ULONG** *fixInterval*, **ULONG** *fixCount*, **ULONG** *fixAccuracy* )

This function starts a PDS tracking session.

## Parameters

<i>sessionControl</i> [IN]	<ul style="list-style-type: none"> <li>Control method: <ul style="list-style-type: none"> <li>0x0 - Manual</li> </ul> </li> </ul>
<i>sessionType</i> [IN]	<ul style="list-style-type: none"> <li>Type: <ul style="list-style-type: none"> <li>0x0 - New</li> </ul> </li> </ul>
<i>sessionOperation</i> [IN]	<ul style="list-style-type: none"> <li>Operating mode: <ul style="list-style-type: none"> <li>0x00 - Standalone</li> <li>0x01 - MS-based</li> </ul> </li> </ul>
<i>sessionServerOption</i> [IN]	<ul style="list-style-type: none"> <li>Location server option: <ul style="list-style-type: none"> <li>0x0 - Default</li> </ul> </li> </ul>

<i>fixTimeout</i> [IN]	<ul style="list-style-type: none"> <li>Maximum time to work on each fix (in seconds, max 255)</li> </ul>
<i>fixCount</i> [IN]	<ul style="list-style-type: none"> <li>Count of position fix requests for this session (must be at least 1)</li> </ul>
<i>fixInterval</i> [IN]	<ul style="list-style-type: none"> <li>interval between position fix requests (in seconds)</li> </ul>
<i>fixAccuracy</i> [IN]	<ul style="list-style-type: none"> <li>Preferred accuracy threshold(in meters)</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Seconds

**9.20.4.25 ULONG StopPDSTrackingSession ( )**

This function stops a PDS tracking session.

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Seconds

**9.21 qaGobiApiQos.h File Reference**

Quality of Service API function prototypes.

**Data Structures**

- struct [dataRate](#)
- struct [tokenBucket](#)
- struct [pktErrRate](#)
- struct [swiQosFlow](#)
- struct [IPv4Addr](#)

- struct [Tos](#)
- struct [IPv6Addr](#)
- struct [IPv6TrafCls](#)
- struct [Port](#)
- struct [swiQosFilter](#)
- struct [swiQosReq](#)
- struct [swiQosIds](#)
- struct [swiQosModifyReq](#)
- struct [swiQosGranted](#)
- struct [NWProfile](#)
- struct [sQosFlowStat](#)
- struct [sQosStat](#)
- struct [sApnExtraParams](#)

## Macros

- `#define MAX_QOS_SPEC_PER_APN (10)`
- `#define MAX_QOS_FILTER_TLV 25`

## Functions

- [ULONG SLQSQosReset](#) ([BYTE](#) instance)
- [ULONG SLQSQosReq](#) ([BYTE](#) instance, [swiQosReq](#) \*pQosReq, [swiQosIds](#) \*pQosResp)
- [ULONG SLQSQosRel](#) ([BYTE](#) instance, [swiQosIds](#) \*pQosIds)
- [ULONG SLQSQosSuspend](#) ([BYTE](#) instance, [swiQosIds](#) \*pQosIds)
- [ULONG SLQSQosResume](#) ([BYTE](#) instance, [swiQosIds](#) \*pQosIds)
- [ULONG SLQSQosModify](#) ([BYTE](#) instance, [swiQosModifyReq](#) \*pReq)
- [ULONG SLQSQosGetGranted](#) ([BYTE](#) instance, [ULONG](#) id, [swiQosGranted](#) \*pGranted)
- [ULONG SLQSQosGetFlowStatus](#) ([BYTE](#) instance, [ULONG](#) id, [BYTE](#) \*pStatus)
- [ULONG SLQSQosGetNetworkStatus](#) ([BYTE](#) instance, [BYTE](#) \*pStatus)
- [ULONG SLQSQosGetNWProf](#) ([BYTE](#) instance, [BYTE](#) \*pSz, [NWProfile](#) \*pProfile)
- [ULONG SLQSQosSwiReadDataStats](#) ([BYTE](#) instance, [ULONG](#) apnId, [sQosStat](#) \*pQosStat)
- [ULONG SLQSQosSwiReadApnExtraParams](#) ([BYTE](#) instance, [ULONG](#) apnId, [sApnExtraParams](#) \*pApnExtraParams)

### 9.21.1 Detailed Description

Quality of Service API function prototypes.

### 9.21.2 Macro Definition Documentation

9.21.2.1 `#define MAX_QOS_FILTER_TLV 25`

9.21.2.2 `#define MAX_QOS_SPEC_PER_APN (10)`

### 9.21.3 Function Documentation

9.21.3.1 `ULONG SLQSQosGetFlowStatus ( BYTE instance, ULONG id, BYTE * pStatus )`

Get the status of a QoS flow.

## Parameters

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
in	<i>id[IN]</i>	Qos identifier Index identifying the QoS flow that has been negotiated
out	<i>pStatus[OUT]</i>	Qos status Current QoS instance status: <ul style="list-style-type: none"> <li>• 0x01 – QMI_QOS_STATUS_ACTIVATED</li> <li>• 0x02 – QMI_QOS_STATUS_SUSPENDED</li> <li>• 0x03 – QMI_QOS_STATUS_GONE</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.21.3.2 ULONG SLQSQosGetGranted ( BYTE *instance*, ULONG *id*, swiQosGranted \* *pGranted* )

Retrieve the QoS parameters that are in effect for the specified QoS 16 flow as a result of network negotiation

## Parameters

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
in	<i>id[IN]</i>	<ul style="list-style-type: none"> <li>• Qos identifier</li> <li>• Index identifying the QoS flow that has been negotiated</li> </ul>
in	<i>pGranted[OUT]</i>	<ul style="list-style-type: none"> <li>• Tx/Rx Qos granted flow</li> <li>• See <a href="#">swiQosGranted</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.21.3.3 ULONG SLQSQosGetNetworkStatus ( BYTE *instance*, BYTE \* *pStatus* )

Queries whether the device is currently on a network that supports QoS

## Parameters

	<i>instance</i> [IN]	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
out	<i>pStatus</i> [OUT]	Network QoS support status <ul style="list-style-type: none"> <li>• 0 – No QoS support in network</li> <li>• 1 – Network supports QoS</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA

#### 9.21.3.4 ULONG SLQSQosGetNWProf ( BYTE *instance*, BYTE \* *pSz*, NWProfile \* *pProfile* )

Get network supported QoS profile information

## Parameters

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
	<i>in/out</i>	<i>pSz</i> Number of network supported QoS profiles for one technology
out	<i>pProfile</i>	Network supported QoS profiles

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.21.3.5 ULONG SLQSQosModify ( BYTE *instance*, swiQosModifyReq \* *pReq* )

Resume one or more existing QoS flows

## Warning

NOT IMPLEMENTED

## Parameters

<i>in</i>	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
	<i>pReq[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosModifyReq</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

9.21.3.6 ULONG SLQSQosRel ( BYTE *instance*, *swiQosIds* \* *pQosIds* )

Release one or more existing QoS flows

## Parameters

<i>in</i>	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
	<i>pQosIds[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosIds</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

9.21.3.7 ULONG SLQSQosReq ( BYTE *instance*, *swiQosReq* \* *pQosReq*, *swiQosIds* \* *pQosResp* )

Triggers QoS negotiation by providing QoS parameters

## Parameters

<i>instance[IN]</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
<i>pQoSReq[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosReq</a> for more information</li> </ul>

<i>pQosResp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosIds</a> for more information</li> </ul>
----------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS/CDMA

Device Supported: MC77XX

Timeout: 2 seconds

At least one pair of optional TLVs must be present; Tx QoS Flow Request and Tx QoS Filter Request TLVs must both be present if either one is present; Rx QoS Flow Request and Rx QoS Filter Request TLVs must both be present if either one is present

**9.21.3.8 ULONG SLQSQosReset ( BYTE *instance* )**

Reset the QoS service state variables of the requesting control point

**Parameters**

<i>in</i>	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
-----------	-----------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA, UMTS & LTE

Device Supported: MC7750

Timeout: 2 seconds

**9.21.3.9 ULONG SLQSQosResume ( BYTE *instance*, swiQosIds \* *pQosIds* )**

Resume one or more existing QoS flows

**Parameters**



<code>in</code>	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
	<i>pQosIds[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosIds</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.21.3.10 ULONG SLQSQoSSuspend ( BYTE *instance*, swiQosIds \* *pQosIds* )**

Suspend one or more existing QoS flows

**Parameters**

<code>in</code>	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
	<i>pQosIds[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">swiQosIds</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.21.3.11 ULONG SLQSQoSSwiReadApnExtraParams ( BYTE *instance*, ULONG *apnId*, sApnExtraParams \* *pApnExtraParams* )**

Queries extra APN parameters that are not reported by existing QCT QMI service

**Parameters**

<code>in</code>	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
<code>in</code>	<i>apnId</i>	<ul style="list-style-type: none"> <li>• APN id</li> </ul>

out	<i>pApnExtraParams</i>	See <a href="#">sApnExtraParams</a> for more information
-----	------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.21.3.12 ULONG SLQSQosSwiReadDataStats ( BYTE instance, ULONG apnId, sQosStat \* pQosStat )

Get the current number of packets and bytes sent, dropped and received for each UL, DL bearer and a sum of them for UL and DL direction in the modem.

**Parameters**

in	<i>instance</i>	<ul style="list-style-type: none"> <li>• QMI instance</li> </ul>
in	<i>apnId</i>	<ul style="list-style-type: none"> <li>• APN id</li> </ul>
out	<i>pQosStat</i>	See <a href="#">sQosStat</a> for more information

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.22 qaGobiApiRms.h File Reference

Remote Management Service API function prototypes.

**Functions**

- [ULONG GetSMSWake](#) ( [ULONG](#) \*pEnabled, [ULONG](#) \*pWakeMask )
- [ULONG SetSMSWake](#) ( [ULONG](#) bEnable, [ULONG](#) wakeMask )

### 9.22.1 Detailed Description

Remote Management Service API function prototypes.

### 9.22.2 Function Documentation

#### 9.22.2.1 ULONG GetSMSWake ( ULONG \* pEnabled, ULONG \* pWakeMask )

Queries the state of the SMS wake functionality. When enabled SMS wake functionality results in incoming messages being searched for the configured mask. Upon detection of the mask the incoming message is deleted (i.e. not stored in memory) and the device attempts to wake the host (requires host platform support).

## Parameters

<i>pEnabled</i> [OUT]	<ul style="list-style-type: none"> <li>• SMS wake functionality enabled <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> </ul> </li> </ul>
<i>pWakeMask</i> [OUT]	<ul style="list-style-type: none"> <li>• SMS wake mask to search for incoming messages (only relevant when enabled)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

9.22.2.2 ULONG SetSMSWake ( ULONG *bEnable*, ULONG *wakeMask* )

Configures the SMS wake functionality. When enabled SMS wake functionality results in incoming messages being searched for the configured mask. Upon detection of the mask the incoming message is deleted (i.e. not stored in memory) and the device attempts to wake the host (requires host platform support).

## Parameters

<i>bEnable</i>	<ul style="list-style-type: none"> <li>• Enable SMS wake functionality <ul style="list-style-type: none"> <li>– Zero - Disable</li> <li>– Non-Zero - Enable</li> </ul> </li> </ul>
<i>wakeMask</i>	<ul style="list-style-type: none"> <li>• SMS wake mask to search for incoming messages (only relevant when enabling)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

## 9.23 qaGobiApiSar.h File Reference

Specific Absorption Rate API function prototypes.

### Enumerations

- enum [eQMISARRFState](#) {  
[QMI\\_SAR\\_RF\\_STATE\\_DEFAULT](#) = 0,  
[QMI\\_SAR\\_RF\\_STATE\\_1](#),  
[QMI\\_SAR\\_RF\\_STATE\\_2](#),  
[QMI\\_SAR\\_RF\\_STATE\\_3](#),  
[QMI\\_SAR\\_RF\\_STATE\\_4](#),  
[QMI\\_SAR\\_RF\\_STATE\\_5](#),  
[QMI\\_SAR\\_RF\\_STATE\\_6](#),  
[QMI\\_SAR\\_RF\\_STATE\\_7](#),  
[QMI\\_SAR\\_RF\\_STATE\\_8](#) }

### Functions

- [ULONG SLQSGetRfSarState](#) ([ULONG](#) \*pSarRFState)
- [ULONG SLQSSetRfSarState](#) ([ULONG](#) RfSarState)

#### 9.23.1 Detailed Description

Specific Absorption Rate API function prototypes.

#### 9.23.2 Enumeration Type Documentation

##### 9.23.2.1 enum eQMISARRFState

This enum contains the SAR RF States

##### Parameters

SAR	RF State
	<ul style="list-style-type: none"> <li>• <a href="#">QMI_SAR_RF_STATE_DEFAULT</a> = 0</li> <li>• <a href="#">QMI_SAR_RF_STATE_1</a></li> <li>• <a href="#">QMI_SAR_RF_STATE_2</a></li> <li>• <a href="#">QMI_SAR_RF_STATE_3</a></li> <li>• <a href="#">QMI_SAR_RF_STATE_4</a></li> <li>• <a href="#">QMI_SAR_RF_STATE_5</a></li> <li>• <a href="#">QMI_SAR_RF_STATE_6</a></li> <li>• <a href="#">QMI_SAR_RF_STATE_7</a></li> <li>• <a href="#">QMI_SAR_RF_STATE_8</a></li> </ul>

##### Enumerator

**[QMI\\_SAR\\_RF\\_STATE\\_DEFAULT](#)**

***QMI\_SAR\_RF\_STATE\_1***  
***QMI\_SAR\_RF\_STATE\_2***  
***QMI\_SAR\_RF\_STATE\_3***  
***QMI\_SAR\_RF\_STATE\_4***  
***QMI\_SAR\_RF\_STATE\_5***  
***QMI\_SAR\_RF\_STATE\_6***  
***QMI\_SAR\_RF\_STATE\_7***  
***QMI\_SAR\_RF\_STATE\_8***

### 9.23.3 Function Documentation

#### 9.23.3.1 ULONG SLQSGetRfSarState ( ULONG \* *pSarRFState* )

Gets the specified RF SAR state.

Parameters

<i>pSarRFState</i>	<ul style="list-style-type: none"> <li>• SAR RF State             <ul style="list-style-type: none"> <li>– QMI_SAR_RF_STATE_DEFAULT</li> <li>– QMI_SAR_RF_STATE_1</li> <li>– QMI_SAR_RF_STATE_2</li> <li>– QMI_SAR_RF_STATE_3</li> <li>– QMI_SAR_RF_STATE_4</li> <li>– QMI_SAR_RF_STATE_5</li> <li>– QMI_SAR_RF_STATE_6</li> <li>– QMI_SAR_RF_STATE_7</li> <li>– QMI_SAR_RF_STATE_8</li> </ul> </li> </ul>
--------------------	--

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

Note

Timeout: 2 seconds

#### 9.23.3.2 ULONG SLQSSetRfSarState ( ULONG *RfSarState* )

Sets the specified RF SAR state.

## Parameters

<i>sar_rf_state</i>	<ul style="list-style-type: none"> <li>• SAR RF State <ul style="list-style-type: none"> <li>– QMI_SAR_RF_STATE_DEFAULT</li> <li>– QMI_SAR_RF_STATE_1</li> <li>– QMI_SAR_RF_STATE_2</li> <li>– QMI_SAR_RF_STATE_3</li> <li>– QMI_SAR_RF_STATE_4</li> <li>– QMI_SAR_RF_STATE_5</li> <li>– QMI_SAR_RF_STATE_6</li> <li>– QMI_SAR_RF_STATE_7</li> <li>– QMI_SAR_RF_STATE_8</li> </ul> </li> </ul>
---------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

## 9.24 qaGobiApiSms.h File Reference

Short Message Service API function prototypes.

### Data Structures

- struct [slqssendsmsparams\\_s](#)
- struct [BroadcastConfig](#)
- struct [\\_qaQmi3GPPBroadcastCfgInfo](#)
- struct [CDMABroadcastConfig](#)
- struct [\\_qaQmi3GPP2BroadcastCfgInfo](#)
- struct [cdmaMsgEncodingParams](#)
- struct [cdmaMsgDecodingParams](#)
- struct [wcdmaMsgEncodingParams](#)
- struct [wcdmaMsgDecodingParams](#)
- struct [wcdmaLongMsgDecodingParams](#)
- struct [\\_transLayerInfo](#)
- struct [\\_getTransLayerInfoResp](#)
- struct [\\_getTransNWRegInfoResp](#)
- struct [\\_getIndicationRegResp](#)
- struct [\\_setIndicationRegReq](#)
- struct [smsRouteEntry](#)
- struct [smsSetRoutesReq](#)

- struct [smsMsgprotocolResp](#)
- struct [smsMaxStorageSizeReq](#)
- struct [smsMaxStorageSizeResp](#)
- struct [messageWaitingInfoContent](#)
- struct [getMsgWaitingInfo](#)
- struct [slqssendasyncsmsparams\\_s](#)

## Macros

- #define [CONFIG\\_LEN](#) 0x05
- #define [TIME\\_STAMP\\_BUF](#) 0x08
- #define [ABSOLUTE\\_VALIDITY](#) 0x08
- #define [TIME\\_DATE\\_BUF](#) 0x09
- #define [MAX\\_SMS\\_ROUTES](#) 0x0A
- #define [NUM\\_OF\\_SET](#) 0xFF

## Typedefs

- typedef struct [\\_qaQmi3GPPBroadcastCfgInfo](#) [qaQmi3GPPBroadcastCfgInfo](#)
- typedef struct [\\_qaQmi3GPP2BroadcastCfgInfo](#) [qaQmi3GPP2BroadcastCfgInfo](#)
- typedef struct [\\_transLayerInfo](#) [transLayerInfo](#)
- typedef struct [\\_getTransLayerInfoResp](#) [getTransLayerInfoResp](#)
- typedef struct [\\_getTransNWRegInfoResp](#) [getTransNWRegInfoResp](#)
- typedef struct [\\_getIndicationRegResp](#) [getIndicationRegResp](#)
- typedef struct [\\_setIndicationRegReq](#) [setIndicationRegReq](#)

## Functions

- [ULONG SLQSDelSMS](#) ([ULONG](#) storageType, [ULONG](#) \*pMessageIndex, [ULONG](#) \*pMessageTag, [BYTE](#) \*pMessageMode)
- [ULONG SLQSGetSMS](#) ([ULONG](#) storageType, [ULONG](#) messageIndex, [ULONG](#) \*pMessageTag, [ULONG](#) \*pMessageFormat, [ULONG](#) \*pMessageSize, [BYTE](#) \*pMessage, [BYTE](#) \*pMessageMode)
- [ULONG SendSMS](#) ([ULONG](#) messageFormat, [ULONG](#) messageSize, [BYTE](#) \*pMessage, [ULONG](#) \*pMessageFailureCode, [BYTE](#) \*pSmsOnlms)
- [ULONG SLQSSendSMS](#) ([slqssendasyncsmsparams\\_s](#) \*pSendSmsParams)
- [ULONG GetSMSCAddress](#) ([BYTE](#) addressSize, [CHAR](#) \*pSMSCAddress, [BYTE](#) typeSize, [CHAR](#) \*pSMSCType)
- [ULONG SetSMSCAddress](#) ([CHAR](#) \*pSMSCAddress, [CHAR](#) \*pSMSCType)
- [ULONG SaveSMS](#) ([ULONG](#) storageType, [ULONG](#) messageFormat, [ULONG](#) messageSize, [BYTE](#) \*pMessage, [ULONG](#) \*pMessageIndex)
- [ULONG SLQSGetSMSList](#) ([ULONG](#) storageType, [ULONG](#) \*pRequestedTag, [ULONG](#) \*pMessageListSize, [BYTE](#) \*pMessageList, [BYTE](#) \*pMessageMode)
- [ULONG SLQSMModifySMSStatus](#) ([ULONG](#) storageType, [ULONG](#) messageIndex, [ULONG](#) messageTag, [BYTE](#) \*pMessageMode)
- [ULONG SLQSGetSmsBroadcastConfig](#) ([BYTE](#) mode, [qaQmi3GPPBroadcastCfgInfo](#) \*pBroadcastConfig, [qaQmi3GPP2BroadcastCfgInfo](#) \*pCDMABroadcastConfig)
- [ULONG SLQSSetSmsBroadcastConfig](#) ([BYTE](#) mode, [qaQmi3GPPBroadcastCfgInfo](#) \*pBroadcastConfig, [qaQmi3GPP2BroadcastCfgInfo](#) \*pCDMABroadcastConfig)
- [ULONG SLQSSetSmsBroadcastActivation](#) ([BYTE](#) mode, [BYTE](#) broadcastActivate)

- [ULONG SLQSCDMAEncodeMOTextMsg](#) (struct [cdmaMsgEncodingParams](#) \*pCdmaMsgEncodingParams)
- [ULONG SLQSCDMADecodeMTTextMsg](#) (struct [cdmaMsgDecodingParams](#) \*pCdmaMsgDecodingParams)
- [ULONG SLQSWCDMAEncodeMOTextMsg](#) (struct [wcdmaMsgEncodingParams](#) \*pWcdmaMsgEncodingParams)
- [ULONG SLQSWCDMADecodeMTTextMsg](#) (struct [wcdmaMsgDecodingParams](#) \*pWcdmaMsgDecodingParams)
- [ULONG SLQSWCDMADecodeLongTextMsg](#) (struct [wcdmaLongMsgDecodingParams](#) \*pWcdmaLongMsgDecodingParams)
- [ULONG SLQSGetTransLayerInfo](#) ([getTransLayerInfoResp](#) \*pGetTransLayerInfoResp)
- [ULONG SLQSGetTransNWRegInfo](#) ([getTransNWRegInfoResp](#) \*pGetTransNWRegInfoResp)
- [ULONG SLQSGetIndicationRegister](#) ([getIndicationRegResp](#) \*pGetIndicationRegInfo)
- [ULONG SLQSSetIndicationRegister](#) ([setIndicationRegReq](#) \*pSetIndicationRegReq)
- [ULONG SLQSSmsSetRoutes](#) ([smsSetRoutesReq](#) \*pSetRoutesReq)
- [ULONG SLQSSmsGetMessageProtocol](#) ([smsMsgprotocolResp](#) \*pMessageProtocol)
- [ULONG SLQSSmsGetMaxStorageSize](#) ([smsMaxStorageSizeReq](#) \*pMaxStorageSizeReq, [smsMaxStorageSizeResp](#) \*pMaxStorageSizeResp)
- [ULONG SLQSGetMessageWaiting](#) ([getMsgWaitingInfo](#) \*pGetMsgWaitingInfoResp)
- [ULONG SLQSSendAsyncSMS](#) ([slqssendasyncsmsparams\\_s](#) \*pSendSmsParams)
- [ULONG SLQSSetSmsStorage](#) ([BYTE](#) smsStorage)
- [ULONG SLQSSwiGetSMSSStorage](#) ([ULONG](#) \*pSmsStorage)
- [ULONG SLQSSendLongSMS](#) ([ULONG](#) messageFormat, [ULONG](#) messageSize, [CHAR](#) \*pMessage, [BYTE](#) encodingScheme, [ULONG](#) \*pMessageFailureCode, [CHAR](#) \*pMobileNum, [BYTE](#) \*pSmsOnIMS)

### 9.24.1 Detailed Description

Short Message Service API function prototypes.

### 9.24.2 Macro Definition Documentation

9.24.2.1 `#define ABSOLUTE_VALIDITY 0x08`

9.24.2.2 `#define CONFIG_LEN 0x05`

9.24.2.3 `#define MAX_SMS_ROUTES 0x0A`

9.24.2.4 `#define NUM_OF_SET 0xFF`

9.24.2.5 `#define TIME_DATE_BUF 0x09`

9.24.2.6 `#define TIME_STAMP_BUF 0x08`

### 9.24.3 Typedef Documentation

9.24.3.1 `typedef struct _getIndicationRegResp getIndicationRegResp`

This structure contains Get Indication Register Response parameters



## Parameters

<i>pRegTransLayerInfoEvt</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating registration status of transport layer information events</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> <li>function <a href="#">SLQSGetIndicationRegister()</a> returns a default value 0xFF if this parameter is allocated memory in the structure and no response is received from the device.</li> </ul>
<i>pRegTransNWRegInfoEvt</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating registration status of transport network registration information events</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> <li>function <a href="#">SLQSGetIndicationRegister()</a> returns a default value 0xFF if this parameter is allocated memory in the structure and no response is received from the device.</li> </ul>
<i>pRegCallStatInfoEvt</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating registration status of call status information events</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> <li>function <a href="#">SLQSGetIndicationRegister()</a> returns a default value 0xFF if this parameter is allocated memory in the structure and no response is received from the device.</li> </ul>

## 9.24.3.2 typedef struct \_getTransLayerInfoResp getTransLayerInfoResp

This structure contains Get Transport Layer Info Response parameters

## Parameters

<i>pRegInd</i>	- <ul style="list-style-type: none"> <li>Optional parameter indicating if transport layer is registered</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - Transport layer is not registered</li> <li>0x01 - Transport layer is registered</li> </ul> </li> <li>function <a href="#">SLQSGetTransLayerInfo()</a> returns a default value 0xFF if no response is received from the device.</li> </ul>
<i>pTransLayerInfo</i>	<ul style="list-style-type: none"> <li>Pointer to structure of transLayerInfo. <ul style="list-style-type: none"> <li>Optional parameter</li> <li>See <a href="#">transLayerInfo</a> for more information</li> </ul> </li> <li>function <a href="#">SLQSGetTransLayerInfo()</a> returns a default value 0xFF for parameter values if no response is received from the device.</li> </ul>

## 9.24.3.3 typedef struct \_getTransNWRegInfoResp getTransNWRegInfoResp

This structure contains transport network registration info parameter

## Parameters

<i>pRegStatus</i>	- <ul style="list-style-type: none"> <li>Optional 1 BYTE parameter indicating transport layer network registration status</li> <li>Values: <ul style="list-style-type: none"> <li>0x00 - No service</li> <li>0x01 - In progress</li> <li>0x02 - Failed</li> <li>0x03 - Limited Service</li> <li>0x04 - Full Service</li> </ul> </li> <li>function <a href="#">SLQSGetTransNWRegInfo()</a> returns a default value 0xFF if no response is received from the device.</li> </ul>
-------------------	---

## 9.24.3.4 typedef struct \_qaQmi3GPP2BroadcastCfgInfo qaQmi3GPP2BroadcastCfgInfo

This structure contains the 3GPP2 Broadcast Configuration Information parameters

## Parameters

<i>activated_ind</i>	<ul style="list-style-type: none"> <li>• Broadcast SMS <ul style="list-style-type: none"> <li>– 0x00 - Deactivated</li> <li>– 0x01 - Activated</li> </ul> </li> </ul>
<i>num_instances</i>	<ul style="list-style-type: none"> <li>• Number of sets (N) of parameters Following each set describes one entry in the broadcast configuration table. <ul style="list-style-type: none"> <li>– serviceCategory</li> <li>– language</li> <li>– selected</li> </ul> </li> </ul>
<i>broadcastConfig</i>	<ul style="list-style-type: none"> <li>• A <a href="#">CDMABroadcastConfig</a> structure array.</li> <li>• Further defined by the structure <a href="#">CDMABroadcastConfig</a></li> </ul>

## 9.24.3.5 typedef struct \_qaQmi3GPPBroadcastCfgInfo qaQmi3GPPBroadcastCfgInfo

This structure contains the 3GPP Broadcast Configuration Information parameters

## Parameters

<i>activated_ind</i>	<ul style="list-style-type: none"> <li>• Broadcast SMS <ul style="list-style-type: none"> <li>– 0x00 - Deactivated</li> <li>– 0x01 - Activated</li> </ul> </li> </ul>
<i>num_instances</i>	<ul style="list-style-type: none"> <li>• Number of sets (N) of parameters Following each set describes one entry in the broadcast configuration table. <ul style="list-style-type: none"> <li>– fromServiceId</li> <li>– toServiceId</li> <li>– selected</li> </ul> </li> </ul>

<i>broadcastConfig</i>	<ul style="list-style-type: none"> <li>• A <a href="#">BroadcastConfig</a> structure array.</li> <li>• Further defined by the structure <a href="#">BroadcastConfig</a></li> </ul>
------------------------	--

#### 9.24.3.6 typedef struct \_setIndicationRegReq setIndicationRegReq

This structure contains Indication Register request parameters

##### Parameters

<i>pRegTransLayerInfoEvt</i>	- <ul style="list-style-type: none"> <li>• Optional 1 BYTE parameter indicating registration status of transport layer information events</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> <li>– NULL - No change - specifying NULL indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>
<i>pRegTransNWRegInfoEvt</i>	- <ul style="list-style-type: none"> <li>• Optional 1 BYTE parameter indicating registration status of transport network registration information events</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> <li>– NULL - No change - specifying NULL indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>
<i>pRegCallStatInfoEvt</i>	- <ul style="list-style-type: none"> <li>• Optional 1 BYTE parameter indicating registration status of call status information events</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> <li>– NULL - No change - specifying NULL indicates that the device will continue to use the existing setting (disable/enable) which has been previously set for the device</li> </ul> </li> </ul>

#### 9.24.3.7 typedef struct \_transLayerinfo transLayerInfo

This structure contains Transport Layer Information

## Parameters

<i>TransType</i>	<ul style="list-style-type: none"> <li>• Transport Type <ul style="list-style-type: none"> <li>– 0x00 - IMS</li> </ul> </li> </ul>
<i>TransCap</i>	<ul style="list-style-type: none"> <li>• Transport Capability</li> <li>• Values: <ul style="list-style-type: none"> <li>– 0x00 - CDMA</li> <li>– 0x01 - GW</li> </ul> </li> </ul>

## 9.24.4 Function Documentation

9.24.4.1 **ULONG** GetSMSCAddress ( **BYTE** *addressSize*, **CHAR** \* *pSMSCAddress*, **BYTE** *typeSize*, **CHAR** \* *pSMSCType* )

Gets the SMS center address.

## Parameters

<i>addressSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the SMS center address array can contain.</li> </ul>
<i>pSMSC-Address[0UT]</i>	<ul style="list-style-type: none"> <li>• The SMS center address represented as a NULL terminated string.</li> </ul>
<i>typeSize</i>	<ul style="list-style-type: none"> <li>• The maximum number of characters (including NULL terminator) that the SMS center address type array can contain.</li> </ul>
<i>pSMSCType[0U-T]</i>	<ul style="list-style-type: none"> <li>• The SMS center address type represented as a NULL terminated string.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL  
Timeout: 2 seconds

9.24.4.2 **ULONG** SaveSMS ( **ULONG** *storageType*, **ULONG** *messageFormat*, **ULONG** *messageSize*, **BYTE** \* *pMessage*, **ULONG** \* *pMessageIndex* )

Saves an SMS message to device memory

## Parameters

<i>storageType</i> [IN]	<ul style="list-style-type: none"> <li>SMS message storage type <ul style="list-style-type: none"> <li>0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>1 - NV</li> </ul> </li> </ul>
<i>message-Format</i> [IN]	<ul style="list-style-type: none"> <li>Message format <ul style="list-style-type: none"> <li>0 - CDMA (IS-637B)</li> <li>1 - 5 (Reserved)</li> <li>6 - GSM/WCDMA PP</li> </ul> </li> </ul>
<i>messageSize</i>	<ul style="list-style-type: none"> <li>The length of the message contents in bytes</li> </ul>
<i>pMessage</i> [IN]	<ul style="list-style-type: none"> <li>The message contents</li> </ul>
<i>pMessage-Index</i> [OUT]	<ul style="list-style-type: none"> <li>The message index assigned by the device</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL  
Timeout: 10 seconds

**9.24.4.3** **ULONG** SendSMS ( **ULONG** *messageFormat*, **ULONG** *messageSize*, **BYTE** \* *pMessage*, **ULONG** \* *pMessageFailureCode*, **BYTE** \* *pSmsOnlms* )

Sends an SMS message for immediate over-the-air transmission

## Parameters

<i>message-Format</i> [IN]	<ul style="list-style-type: none"> <li>• Message format <ul style="list-style-type: none"> <li>– 0 - CDMA (IS-637B)</li> <li>– 1 - 5 (Reserved)</li> <li>– 6 - GSM/WCDMA PP</li> </ul> </li> </ul>
<i>messageSize</i> [IN]	<ul style="list-style-type: none"> <li>• The length of the message contents in bytes</li> </ul>
<i>pMessage</i> [IN]	<ul style="list-style-type: none"> <li>• The message contents in PDU format contains SMS header and payload message</li> </ul>
<i>pSmsOnIms</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) SMS on IMS</li> <li>• The message is to be sent on IMS. <ul style="list-style-type: none"> <li>– 0x00 Message is not to be sent on IMS.</li> <li>– 0x01 Message is to be sent on IMS.</li> <li>– 0x02 to 0xFF Reserved.</li> </ul> </li> </ul>
<i>pMessage-FailureCode</i> [OUT]	<ul style="list-style-type: none"> <li>• (Optional) Message Failure Code</li> <li>• pointer to message failure code. If cause code is not provided, then value will be 0xFFFFFFFF</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL  
Timeout: 5 minutes

#### 9.24.4.4 ULONG SetSMSCAddress ( CHAR \* pSMSCAddress, CHAR \* pSMSCType )

Sets the SMS center address.

## Parameters



<i>pSMSC-Address</i> [IN]	<ul style="list-style-type: none"> <li>The SMS center address represented as a NULL terminated string</li> </ul>
<i>pSMSCType</i> [IN]	<ul style="list-style-type: none"> <li>The SMS center address type represented as a NULL terminated string (optional).</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: ALL  
Timeout: 5 seconds

#### 9.24.4.5 ULONG SLQSCDMADecodeMTTextMsg ( struct cdmaMsgDecodingParams \* pCdmaMsgDecodingParams )

Decodes text message to CDMA PDU message

**Parameters**

<i>pMsgToBe-EncodedCDMA</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Pointer to structure containing parameters needed for decoding</li> </ul>
--------------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: None

#### 9.24.4.6 ULONG SLQSCDMAEncodeMOTextMsg ( struct cdmaMsgEncodingParams \* pCdmaMsgEncodingParams )

Encodes text message to CDMA PDU message.

**Parameters**

<i>pMsgToBe-EncodedCDMA</i> [IN/OUT]	<ul style="list-style-type: none"> <li>SLQS Runtime Settings Information</li> </ul>
--------------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: None

**9.24.4.7 ULONG SLQSDDeleteSMS ( ULONG *storageType*, ULONG \* *pMessageIndex*, ULONG \* *pMessageTag*, BYTE \* *pMessageMode* )**

Deletes one or more SMSs from device memory. If both of the optional parameters, *messageIndex* and *messageTag*, are NULL, all messages are deleted from the storage location specified in the mandatory *storageType* parameter. The optional index and tag parameters narrow the range of messages being deleted. If an index is specified, the single message with the index from the specified memory store will be deleted. If a tag is specified, all messages in the specified memory store whose tag matches that specified will be deleted.

There are three ways to use this message:

- Specify *storageType* only
  - Deletes all messages from memory storage
- Specify *storageType* and a tag
  - Deletes all messages from memory storage that match the given message tag
- Specify *storageType* and an index
  - Deletes only the message with the given index from memory storage

## Parameters

<i>storageType</i>	<ul style="list-style-type: none"> <li>SMS message storage type <ul style="list-style-type: none"> <li>0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>1 - NV</li> </ul> </li> </ul>
<i>pMessage-Index</i> [IN]	<ul style="list-style-type: none"> <li>(Optional) message index</li> </ul>
<i>pMessageTag</i> [I-N]	<ul style="list-style-type: none"> <li>(Optional) message tag <ul style="list-style-type: none"> <li>0 - Read</li> <li>1 - Not read</li> <li>2 - Mobile originated and sent</li> <li>3 - Mobile originated but not yet sent</li> </ul> </li> </ul>
<i>pMessage-Mode</i> [IN]	<ul style="list-style-type: none"> <li>(Optional) message mode</li> <li>0x00 - CDMA, LTE (if network type is CDMA)</li> <li>0x01 - GW, LTE (if network type is UMTS)</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL  
Timeout: 10 seconds

#### 9.24.4.8 ULONG SLQSGetIndicationRegister ( getIndicationRegResp \* pGetIndicationRegInfo )

This API provides registration state of different WMS indications.

## Parameters

<i>pGetIndication-RegInfo</i>	[OUT] <ul style="list-style-type: none"> <li>Pointer to structure of getIndicationRegResp <ul style="list-style-type: none"> <li>See <a href="#">getIndicationRegResp</a> for more information</li> </ul> </li> </ul>
-------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Secs

**9.24.4.9 ULONG SLQSGetMessageWaiting ( getMsgWaitingInfo \* pGetMsgWaitingInfoResp )**

This API provides information about the message waiting information.

**Parameters**

<i>pGetMsgWaitingInfoResp</i>	[OUT] <ul style="list-style-type: none"> <li>• Pointer to structure of getMsgWaitingInfoResp             <ul style="list-style-type: none"> <li>– See getMsgWaitingInfoResp for more information</li> </ul> </li> </ul>
-------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Secs

**9.24.4.10 ULONG SLQSGetSMS ( ULONG storageType, ULONG messageIndex, ULONG \* pMessageTag, ULONG \* pMessageFormat, ULONG \* pMessageSize, BYTE \* pMessage, BYTE \* pMessageMode )**

Returns an SMS from device memory.

**Parameters**

<i>storageType</i>	<ul style="list-style-type: none"> <li>• SMS message storage type             <ul style="list-style-type: none"> <li>– 0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>– 1 - NV</li> </ul> </li> </ul>
--------------------	--

<i>messageIndex</i>	<ul style="list-style-type: none"> <li>• Message index</li> </ul>
<i>pMessageTag[OUT]</i>	<ul style="list-style-type: none"> <li>• Message tag <ul style="list-style-type: none"> <li>– 0 - Read</li> <li>– 1 - Not read</li> <li>– 2 - Mobile originated and sent</li> <li>– 3 - Mobile originated but not yet sent</li> </ul> </li> </ul>
<i>pMessageFormat[OUT]</i>	<ul style="list-style-type: none"> <li>• Message format <ul style="list-style-type: none"> <li>– 0 - CDMA (IS-637B)</li> <li>– 1 - 5 (Reserved)</li> <li>– 6 - GSM/WCDMA PP</li> </ul> </li> </ul>
<i>pMessageSize[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Upon input the maximum number of bytes that can be written to the message array.</li> <li>• Upon successful output the actual number of bytes written to the message array.</li> </ul>
<i>pMessage[OUT]</i>	<ul style="list-style-type: none"> <li>• The message contents array</li> </ul>
<i>pMessageMode[IN]</i>	<ul style="list-style-type: none"> <li>• (Optional) Message Mode</li> <li>• 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>• 0x01 - GW, LTE (if network type is UMTS)</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: ALL  
Timeout: 5 seconds

**9.24.4.11** **ULONG** SLQSGetSmsBroadcastConfig ( **BYTE** *mode*, **qaQmi3GPPBroadcastCfgInfo** \* *pBroadcastConfig*, **qaQmi3GPP2BroadcastCfgInfo** \* *pCDMABroadcastConfig* )

Provides Information about the SMS BroadcastConfiguration

## Parameters

<i>mode</i> [IN]	<ul style="list-style-type: none"> <li>• Mode <ul style="list-style-type: none"> <li>– 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>– 0x01 - GW, LTE (if network type is UMTS)</li> </ul> </li> </ul>
<i>pBroadcast-Config</i> [OUT]	<ul style="list-style-type: none"> <li>• The data for 3GPP Broadcast Information(Optional).</li> </ul>
<i>pCDMA-Broadcast-Config</i> [OUT]	<ul style="list-style-type: none"> <li>• The data for 3GPP2 Broadcast Information(Optional).</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL

Timeout: 5 seconds

**9.24.4.12** **ULONG** SLQSGetSMSList ( **ULONG** *storageType*, **ULONG** \* *pRequestedTag*, **ULONG** \* *pMessageListSize*, **BYTE** \* *pMessageList*, **BYTE** \* *pMessageMode* )

Returns the list of SMS messages stored on the device.

## Parameters

<i>storageType</i> [IN]	<ul style="list-style-type: none"> <li>• SMS message storage type <ul style="list-style-type: none"> <li>– 0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>– 1 - NV</li> </ul> </li> </ul>
<i>pRequested-Tag</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Message tag <ul style="list-style-type: none"> <li>– 0 - Read</li> <li>– 1 - Not read</li> <li>– 2 - Mobile originated and sent</li> <li>– 3 - Mobile originated but not yet sent</li> </ul> </li> </ul>

<i>pMessageList-Size</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Upon input the maximum number of elements that the message list array can contain.</li> <li>• Upon successful output the actual number of elements in the message list array.</li> </ul>
<i>pMessageList</i> [OUT]	<ul style="list-style-type: none"> <li>• The message list array</li> </ul>
<i>pMessage-Mode</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Message Mode</li> <li>• 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>• 0x01 - GW, LTE (if network type is UMTS)</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: ALL  
Timeout: 5 seconds

#### 9.24.4.13 ULONG SLQSGetTransLayerInfo ( getTransLayerInfoResp \* pGetTransLayerInfoResp )

This API provides information about the transport layer.

**Parameters**

<i>pGetTransLayer-InfoResp</i>	[OUT] <ul style="list-style-type: none"> <li>• Pointer to structure of getTransLayerInfoResp <ul style="list-style-type: none"> <li>– See <a href="#">getTransLayerInfoResp</a> for more information</li> </ul> </li> </ul>
--------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 Secs

#### 9.24.4.14 ULONG SLQSGetTransNWRegInfo ( getTransNWRegInfoResp \* pGetTransNWRegInfoResp )

This API provides transport layer network registration info.

## Parameters

<i>pGetTransNW-RegInfoResp</i>	[OUT] <ul style="list-style-type: none"> <li>• Pointer to structure of <code>getTransNWRegInfoResp</code> <ul style="list-style-type: none"> <li>– See <a href="#">getTransNWRegInfoResp</a> for more information</li> </ul> </li> </ul>
--------------------------------	--

## Returns

`eQCWWAN_ERR_NONE` on success, `eQCWWAN_xxx` error value otherwise

## See Also

See [qmerrno.h](#) for `eQCWWAN_xxx` error values

## Note

Timeout: 2 Secs

**9.24.4.15** `ULONG SLQSMModifySMSStatus ( ULONG storageType, ULONG messageIndex, ULONG messageTag, BYTE * pMessageMode )`

Modifies the status of an SMS message saved in storage on the device.

## Parameters

<i>storageType</i> [IN]	<ul style="list-style-type: none"> <li>• SMS message storage type             <ul style="list-style-type: none"> <li>– 0 - UIM - Invalid in case of CDMA device that does not require SIM</li> <li>– 1 - NV</li> </ul> </li> </ul>
<i>messageIndex</i> [IN]	<ul style="list-style-type: none"> <li>• Message index</li> </ul>
<i>messageTag</i> [IN]	<ul style="list-style-type: none"> <li>• Message tag             <ul style="list-style-type: none"> <li>– 0 - Read</li> <li>– 1 - Not read</li> </ul> </li> </ul>
<i>pMessageMode</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Message Mode</li> <li>• 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>• 0x01 - GW, LTE (if network type is UMTS)</li> </ul>

## Returns

`eQCWWAN_ERR_NONE` on success, `eQCWWAN_xxx` error value otherwise



## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL  
Timeout: 5 seconds

**9.24.4.16 ULONG SLQSSendAsyncSMS ( slqssendasyncsmsparams\_s \* pSendSmsParams )**

Sends an SMS message for immediate over-the-air transmission

## Parameters

<i>pSendSms-Params</i>	<ul style="list-style-type: none"><li>• structure containing the SMS parameters. Refer <a href="#">slqssendasyncsmsparams_s</a></li></ul>
------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL  
Timeout: 5 minutes

**9.24.4.17 ULONG SLQSSendLongSMS ( ULONG messageFormat, ULONG messageSize, CHAR \* pMessage, BYTE encodingScheme, ULONG \* pMessageFailureCode, CHAR \* pMobileNum, BYTE \* pSmsOnIMS )**

Sends a long SMS message for immediate over-the-air transmission, a short SMS can be sent by this API as well, the input message is text string without any encoding

## Parameters

<i>message-Format[IN]</i>	<ul style="list-style-type: none"><li>• Message format<ul style="list-style-type: none"><li>– 0 - CDMA (IS-637B)</li><li>– 1 - 5 (Reserved)</li><li>– 6 - GSM/WCDMA PP</li></ul></li></ul>
---------------------------	--

<i>messageSize</i> [IN]	<ul style="list-style-type: none"> <li>• Message size of the input message text</li> </ul>
<i>pMessage</i> [IN]	<ul style="list-style-type: none"> <li>• Original message text</li> </ul>
<i>encoding-Scheme</i> [IN]	<ul style="list-style-type: none"> <li>• Encoding method to generate the PDU <ul style="list-style-type: none"> <li>– 0 - 7 bit encoding</li> <li>– 4 - 8 bit encoding</li> <li>– 8 - 16 bit UCS2 encoding</li> <li>– others value will be treated as default 7 bit encoding</li> </ul> </li> </ul>
<i>pMessage-FailureCode</i> [OUT]	<ul style="list-style-type: none"> <li>• message failure code. If cause code is not provided, then value will be 0xFFFFFFFF</li> </ul>
<i>pMobileNum</i> [IN]	<ul style="list-style-type: none"> <li>• Mobile number of the receiver</li> </ul>
<i>pSmsOnIMS</i> [IN]	<ul style="list-style-type: none"> <li>• A flag indicates whether SMS was sent through IMS</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: 3GPP and 3GPP2, but 3GPP2 does not support multiple sms  
Timeout: 5 minutes

**9.24.4.18 ULONG SLQSSendSMS ( slqssendsmsparams\_s \* pSendSmsParams )**

Sends an SMS message for immediate over-the-air transmission

**Parameters**

<i>pSendSms-Params</i>	<ul style="list-style-type: none"> <li>• structure containing the SMS parameters. Refer <a href="#">slqssendsmsparams_s</a></li> </ul>
------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL  
Timeout: 5 minutes

**9.24.4.19   ULONG SLQSSetIndicationRegister ( setIndicationRegReq \* pSetIndicationRegReq )**

This API sets the registration state of different WMS indications.

## Parameters

<i>pSetIndication- RegReq</i>	<div><div>[IN]</div><ul style="list-style-type: none"><li>• Pointer to structure of indicationRegReqParams<ul style="list-style-type: none"><li>– See <a href="#">setIndicationRegReq</a> for more information</li></ul></li></ul></div>
-----------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Secs

**9.24.4.20   ULONG SLQSSetSmsBroadcastActivation ( BYTE mode, BYTE broadcastActivate )**

Enables or disables the reception of broadcast SMS messages.

## Parameters

<i>Mode</i> [IN]	<div><ul style="list-style-type: none"><li>• Mode</li><li>• 0x00 - CDMA, LTE (if network type is CDMA)</li><li>• 0x01 - GW, LTE (if network type is UMTS)</li></ul></div>
<i>broadcast- Activate</i> [IN]	<div><ul style="list-style-type: none"><li>• 0x00 - Disable broadcast</li><li>• 0x01 - Activate broadcast</li></ul></div>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: ALL  
Timeout: 5 seconds

**9.24.4.21** **ULONG SLQSSetSmsBroadcastConfig ( BYTE mode, qaQmi3GPPBroadcastCfgInfo \* pBroadcastConfig, qaQmi3GPP2BroadcastCfgInfo \* pCDMABroadcastConfig )**

Sets the information about the SMS BroadcastConfiguration

**Parameters**

<i>mode</i> [IN]	<ul style="list-style-type: none"> <li>• Mode <ul style="list-style-type: none"> <li>– 0x00 - CDMA, LTE (if network type is CDMA)</li> <li>– 0x01 - GW, LTE (if network type is UMTS)</li> </ul> </li> </ul>
<i>pBroadcast-Config</i> [IN]	<ul style="list-style-type: none"> <li>• The data for 3GPP Broadcast Information(Optional).</li> </ul>
<i>pCDMA-Broadcast-Config</i> [IN]	<ul style="list-style-type: none"> <li>• The data for 3GPP2 Broadcast Information(Optional).</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: ALL  
Timeout: 5 seconds

**9.24.4.22** **ULONG SLQSSetSmsStorage ( BYTE smsStorage )**

Sets the SMS Storage on the device

## Parameters

<i>smsStorage</i> [IN]	<ul style="list-style-type: none"> <li>• SMS Storage <ul style="list-style-type: none"> <li>– 0x01 - device's permanent memory</li> <li>– 0x02 - UICC</li> </ul> </li> </ul>
------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: ALL  
Timeout: 5 seconds

#### 9.24.4.23 ULONG SLQSSmsGetMaxStorageSize ( smsMaxStorageSizeReq \* pMaxStorageSizeReq, smsMaxStorageSizeResp \* pMaxStorageSizeResp )

This API provides the maximum number of messages that can be stored in the specified memory storage. Also it provides the number of slots currently available

## Parameters

<i>pMaxStorageSizeReq</i> [IN]	<ul style="list-style-type: none"> <li>• Request parameters for SmsSLQSGetMaxStorageSize <ul style="list-style-type: none"> <li>– See <a href="#">smsMaxStorageSizeReq</a> for more information</li> </ul> </li> </ul>
<i>pMaxStorageSizeResp</i> [OUT]	<ul style="list-style-type: none"> <li>• Response parameters for SmsSLQSGetMaxStorageSize <ul style="list-style-type: none"> <li>– See <a href="#">smsMaxStorageSizeResp</a> for more information</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Secs

#### 9.24.4.24 ULONG SLQSSmsGetMessageProtocol ( smsMsgprotocolResp \* pMessageProtocol )

This API queries the message protocol currently in use for the WMS client.

## Parameters

<i>pMessage-Protocol</i>	[OUT] <ul style="list-style-type: none"> <li>• Pointer to <a href="#">smsMsgprotocolResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">smsMsgprotocolResp</a> for more information</li> </ul> </li> </ul>
--------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Secs

#### 9.24.4.25 ULONG SLQSSmsSetRoutes ( smsSetRoutesReq \* pSetRoutesReq )

This API sets the action performed on SMS message receipt for specified message routes. It also specifies the action performed on SMS receipt of status reports.

## Parameters

<i>pSetRoutesReq</i>	[IN] <ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">smsSetRoutesReq</a> <ul style="list-style-type: none"> <li>– See <a href="#">smsSetRoutesReq</a> for more information</li> </ul> </li> </ul>
----------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 Secs

#### 9.24.4.26 ULONG SLQSSwiGetSMSStorage ( ULONG \* pSmsStorage )

This API queries the device to return current SMS configuration that is applied to all incoming and outgoing messages.

## Parameters

<i>pSmsStorage[O-UT]</i>	<ul style="list-style-type: none"> <li>• Values: <ul style="list-style-type: none"> <li>– 0x01 - device's permanent memory</li> <li>– 0x02 - UICC</li> </ul> </li> </ul>
--------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Secs

#### 9.24.4.27 **ULONG** SLQSWCDMADecodeLongTextMsg ( struct wcdmaLongMsgDecodingParams \* *pWcdmaLongMsgDecodingParams* )

Decodes WCDMA Long SMS PDU message, returns structure filled with decoded parameters

## Parameters

<i>pwcdmaMsgDecodingParams[IN/OUT]</i>	<ul style="list-style-type: none"> <li>• Pointer to parameters required for decoding</li> </ul>
--	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Timeout: none

#### 9.24.4.28 **ULONG** SLQSWCDMADecodeMTTextMsg ( struct wcdmaMsgDecodingParams \* *pWcdmaMsgDecodingParams* )

Decodes WCDMA PDU message, returns structure filled with decoded parameters

## Parameters

<i>pwcdmaMsg- Decoding- Params</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Pointer to parameters required for decoding</li> </ul>
---	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Timeout: none

#### 9.24.4.29 **ULONG** SLQSWCDMAEncodeMOTextMsg ( struct wcdmaMsgEncodingParams \* *pWcdmaMsgEncodingParams* )

Returns the encoded WCDMA PDU message.

## Parameters

<i>pwcdmaMsg- Encoding- Params</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Pointer to parameters Required for encoding</li> </ul>
---	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Timeout: None

## 9.25 qaGobiApiSwi.h File Reference

SWI API function prototypes.

## Functions

- [ULONG](#) SLQSGetSdkVersion ([CHAR](#) \*\*sdkversionpp)
- [ULONG](#) SLQSSendRawQMI ([BYTE](#) \*pReqBuf, [USHORT](#) service, [USHORT](#) length, [ULONG](#) timeout, [BYTE](#) \*\*pInParm, [USHORT](#) \*pParamLength)
- [int](#) SLQSGetPidof ([CHAR](#) \*pProcName)



### 9.25.1 Detailed Description

SWI API function prototypes.

### 9.25.2 Function Documentation

#### 9.25.2.1 int SLQSGetPidof ( CHAR \* *pProcName* )

Internal Wrapper function for enabling invocation of SLQS implementation pidof() function

Parameters

<i>pProcName</i> [IN]	<ul style="list-style-type: none"> <li>Process name whose PID is to be retrieved</li> </ul>
-----------------------	---

Returns

pid if process exists else 0

See Also

NA

Note

NA

#### 9.25.2.2 ULONG SLQSGetSdkVersion ( CHAR \*\* *sdkversionpp* )

Returns the SDK version string

Parameters

<i>ppString</i> [OUT]	<ul style="list-style-type: none"> <li>pointer to pointer of NULL terminated string</li> </ul>
-----------------------	--

Returns

eQCWWAN\_ERR\_NONE success eQCWWAN\_ERR\_INVALID\_ARG provided pointer is NULL

Note

Technology Supported: N/A Timeout: 2 seconds

#### 9.25.2.3 ULONG SLQSSendRawQMI ( BYTE \* *pReqBuf*, USHORT *service*, USHORT *length*, ULONG *timeout*, BYTE \*\* *ppInParm*, USHORT \* *pParamLength* )

## 9.26 qaGobiApiSwiAudio.h File Reference

M2M Audio Service API function prototypes.

## Data Structures

- struct [GetM2MAudioProfileReq](#)
- struct [GetM2MAudioProfileResp](#)
- struct [SetM2MAudioProfileReq](#)
- struct [GetM2MAudioVolumeReq](#)
- struct [GetM2MAudioVolumeResp](#)
- struct [SetM2MAudioVolumeReq](#)
- struct [PCMparams](#)
- struct [SetM2MAudioAVCFGReq](#)
- struct [SetM2MAudioLPBKReq](#)
- struct [GetM2MSpkrGainReq](#)
- struct [GetM2MSpkrGainResp](#)
- struct [SetM2MSpkrGainReq](#)
- struct [GetM2MAVMuteReq](#)
- struct [GetM2MAVMuteResp](#)
- struct [SetM2MAVMuteReq](#)

## Macros

- `#define` [MAX\\_LEN\\_IFACE\\_TABLE](#) 255

## Functions

- `ULONG` [SLQSGetM2MAudioProfile](#) ([GetM2MAudioProfileReq](#) \*pGetM2MAudioProfileReq, [GetM2MAudioProfileResp](#) \*pGetM2MAudioProfileResp)
- `ULONG` [SLQSSetM2MAudioProfile](#) ([SetM2MAudioProfileReq](#) \*pSetM2MAudioProfileReq)
- `ULONG` [SLQSGetM2MAudioVolume](#) ([GetM2MAudioVolumeReq](#) \*pGetM2MAudioVolumeReq, [GetM2MAudioVolumeResp](#) \*pGetM2MAudioVolumeResp)
- `ULONG` [SLQSSetM2MAudioVolume](#) ([SetM2MAudioVolumeReq](#) \*pSetM2MAudioVolumeReq)
- `ULONG` [SLQSSetM2MAudioAVCFG](#) ([SetM2MAudioAVCFGReq](#) \*pSetM2MAudioAVCFGReq)
- `ULONG` [SLQSSetM2MAudioLPBK](#) ([SetM2MAudioLPBKReq](#) \*pSetM2MAudioLPBKReq)
- `ULONG` [SLQSSetM2MAudioNVDef](#) ()
- `ULONG` [SLQSGetM2MSpkrGain](#) ([GetM2MSpkrGainReq](#) \*pSpkrGainReq, [GetM2MSpkrGainResp](#) \*pSpkrGainResp)
- `ULONG` [SLQSSetM2MSpkrGain](#) ([SetM2MSpkrGainReq](#) \*pSpkrGainReq)
- `ULONG` [SLQSGetM2MAVMute](#) ([GetM2MAVMuteReq](#) \*pGetM2MAVMuteReq, [GetM2MAVMuteResp](#) \*pGetM2MAVMuteResp)
- `ULONG` [SLQSSetM2MAVMute](#) ([SetM2MAVMuteReq](#) \*pSetM2MAVMuteReq)

### 9.26.1 Detailed Description

M2M Audio Service API function prototypes.

### 9.26.2 Macro Definition Documentation

#### 9.26.2.1 `#define` [MAX\\_LEN\\_IFACE\\_TABLE](#) 255

### 9.26.3 Function Documentation

#### 9.26.3.1 `ULONG` [SLQSGetM2MAudioProfile](#) ( [GetM2MAudioProfileReq](#) \* *pGetM2MAudioProfileReq*, [GetM2MAudioProfileResp](#) \* *pGetM2MAudioProfileResp* )

This API gets the profile content.

## Parameters

<i>pGetM2MAudioProfileReq</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MAudioProfileReq</a> for more information</li> </ul>
<i>pGetM2MAudioProfileResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MAudioProfileResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

### 9.26.3.2 ULONG SLQSGetM2MAudioVolume ( GetM2MAudioVolumeReq \* pGetM2MAudioVolumeReq, GetM2MAudioVolumeResp \* pGetM2MAudioVolumeResp )

This API gets the Volume content.

## Parameters

<i>pGetM2MAudioVolumeReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MAudioVolumeReq</a> for more information</li> </ul>
<i>pGetM2MAudioVolumeResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MAudioVolumeResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

### 9.26.3.3 ULONG SLQSGetM2MAVMute ( GetM2MAVMuteReq \* pGetM2MAVMuteReq, GetM2MAVMuteResp \* pGetM2MAVMuteResp )

This API Gets the AV Mute content.

## Parameters

<i>pGetM2MAV-MuteReq[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MAVMuteReq</a> for more information</li> </ul>
<i>pGetM2MAV-MuteResp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MAVMuteResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.26.3.4 ULONG SLQSGetM2MSpkrGain ( GetM2MSpkrGainReq \* pSpkrGainReq, GetM2MSpkrGainResp \* pSpkrGainResp )

This API Gets the SPKRGAIN content.

## Parameters

<i>pSpkrGainReq[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MSpkrGainReq</a> for more information</li> </ul>
<i>pSpkrGain-Resp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MSpkrGainResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.26.3.5 ULONG SLQSSetM2MAudioAVCFG ( SetM2MAudioAVCFGReq \* pSetM2MAudioAVCFGReq )

This API sets the AVCFG content.

## Parameters

<i>pSetM2MAudioAVCFGReq</i> [IN]	<ul style="list-style-type: none"><li>See <a href="#">SetM2MAudioAVCFGReq</a> for more information</li></ul>
----------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.26.3.6 ULONG SLQSSetM2MAudioLPBK ( SetM2MAudioLPBKReq \* pSetM2MAudioLPBKReq )

This API sets the LPBK content.

## Parameters

<i>pSetM2MAudioLPBKReq</i> [IN]	<ul style="list-style-type: none"><li>See <a href="#">SetM2MAudioLPBKReq</a> for more information</li></ul>
---------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.26.3.7 ULONG SLQSSetM2MAudioNVDef ( )

This API sets the NVDef content.

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

#### 9.26.3.8 ULONG SLQSSetM2MAudioProfile ( SetM2MAudioProfileReq \* pSetM2MAudioProfileReq )

This API sets the profile content.

## Parameters

<i>pSetM2MAudioProfileReq</i> [IN]	<ul style="list-style-type: none"><li>• See <a href="#">SetM2MAudioProfileReq</a> for more information</li></ul>
------------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.26.3.9   ULONG SLQSSetM2MAudioVolume ( SetM2MAudioVolumeReq \* pSetM2MAudioVolumeReq )**

This API sets the Volume content.

## Parameters

<i>pSetM2MAudioVolumeReq</i> [IN]	<ul style="list-style-type: none"><li>• See <a href="#">SetM2MAudioVolumeReq</a> for more information</li></ul>
-----------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.26.3.10   ULONG SLQSSetM2MAVMute ( SetM2MAVMuteReq \* pSetM2MAVMuteReq )**

This API Sets the AV Mute content.

## Parameters

<i>pSetM2MAVMuteReq</i> [IN]	<ul style="list-style-type: none"><li>• See <a href="#">SetM2MAVMuteReq</a> for more information</li></ul>
------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_XXX error values

**Note**

Timeout: 5 seconds

**9.26.3.11 ULONG SLQSSetM2MSpkrGain ( SetM2MSpkrGainReq \* pSpkrGainReq )**

This API Sets the SPKRGAIN content.

**Parameters**

<i>pSpkrGainReq</i> [1-N]	<ul style="list-style-type: none"> <li>• See <a href="#">GetM2MSpkrGainReq</a> for more information</li> </ul>
---------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_XXX error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_XXX error values

**Note**

Timeout: 5 seconds

**9.27 qaGobiApiSwiOmadms.h File Reference**

SWI Open Mobile Alliance Device Management Service API function prototypes SWI OMA-DM QMI Service revision 1.6.

**Data Structures**

- struct [\\_SLQSOMADMSessionInfo](#)
- struct [\\_SLQSOMADMSettingsReqParams](#)
- struct [\\_SLQSOMADMSettings](#)
- struct [\\_SLQSOMADMSettingsReqParams3](#)

**Typedefs**

- typedef struct [\\_SLQSOMADMSessionInfo](#) SLQSOMADMSessionInfo
- typedef struct [\\_SLQSOMADMSettingsReqParams](#) SLQSOMADMSettingsReqParams
- typedef struct [\\_SLQSOMADMSettings](#) SLQSOMADMSettings
- typedef struct [\\_SLQSOMADMSettingsReqParams3](#) SLQSOMADMSettingsReqParams3

## Functions

- [ULONG SLQSOMADMStartSession](#) ([ULONG](#) sessionType)
- [ULONG SLQSOMADMCancelSession](#) ([ULONG](#) session)
- [ULONG SLQSOMADMGetSessionInfo](#) ([ULONG](#) \*pSessionType, [SLQSOMADMSessionInfo](#) \*pResp)
- [ULONG SLQSOMADMSendSelection](#) ([ULONG](#) selection)
- [ULONG SLQSOMADMGetSettings](#) ([ULONG](#) \*pbOMADMEEnabled, [ULONG](#) \*pbFOTAdownload, [ULONG](#) \*pbFOTAUpdate)
- [ULONG SLQSOMADMSetSettings](#) ([ULONG](#) bFOTAdownload, [ULONG](#) bFOTAUpdate)
- [ULONG SLQSOMADMSetSettings2](#) ([SLQSOMADMSettingsReqParams](#) \*pSLQSOMADMSettingsReqParams)
- [ULONG SLQSOMADMGetSettings2](#) ([SLQSOMADMSettings](#) \*pSLQSOMADMSettings)
- [ULONG SLQSOMADMStartSession2](#) ([ULONG](#) sessionType, [ULONG](#) \*pFwAvailability)
- [ULONG SLQSOMADMSendSelection2](#) ([ULONG](#) selection, [ULONG](#) \*pDeferTime, [ULONG](#) \*pRejectReason)
- [ULONG SLQSOMADMSetSettings3](#) ([SLQSOMADMSettingsReqParams3](#) \*pSLQSOMADMSettingsReqParams3)

### 9.27.1 Detailed Description

SWI Open Mobile Alliance Device Management Service API function prototypes SWI OMA-DM QMI Service revision 1.6.

### 9.27.2 Typedef Documentation

#### 9.27.2.1 typedef struct [\\_SLQSOMADMSessionInfo](#) [SLQSOMADMSessionInfo](#)

Structure containing the OMA DM Session Info returned by the device. Also used as input parameter to specify the size of variable parameters. (ref. notes)

##### Parameters

<i>pStatus</i>	<ul style="list-style-type: none"> <li>• 1 Byte parameter indicating status(optional)             <ul style="list-style-type: none"> <li>– 0x01 - No Firmware available</li> <li>– 0x02 - Query Firmware Download</li> <li>– 0x03 - Firmware Downloading</li> <li>– 0x04 - Firmware Downloaded</li> <li>– 0x05 - Query Firmware Update</li> <li>– 0x06 - Firmware Updating</li> <li>– 0x07 - Firmware Updated</li> </ul> </li> </ul>
----------------	--



<i>pUpdate-CompleteStatus</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Update Complete Status(optional) <ul style="list-style-type: none"> <li>– See <a href="#">qaGobiApiTableSwiOMADMUpdateCompleteStatus.h</a> Update Complete Status</li> </ul> </li> </ul>
<i>pSeverity</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating severity(optional) <ul style="list-style-type: none"> <li>– 0x01 - Mandatory</li> <li>– 0x02 - Optional</li> </ul> </li> </ul>
<i>pSourceLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Vendor Name String in Bytes.(optional)</li> </ul>
<i>pSource</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Vendor Name in ASCII(optional)</li> </ul>
<i>pPkgName-Length</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Name String in Bytes.(optional)</li> </ul>
<i>pPkgName</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Name in ASCII(optional)</li> </ul>
<i>pPkgDesc-Length</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Description String in Bytes.(optional)</li> </ul>
<i>pPkgDescription</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Description in ASCII(optional)</li> </ul>
<i>pDateLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Package Description String in Bytes.(optional)</li> </ul>
<i>pDate</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Package Description in ASCII</li> </ul>
<i>pTimeLength</i>	<ul style="list-style-type: none"> <li>• 2 byte parameter indicating Length of Time String in Bytes.(optional)</li> </ul>
<i>pTime</i>	<ul style="list-style-type: none"> <li>• Variable length parameter indicating Time String in ASCII(optional)</li> </ul>
<i>pSessionType</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter reflects the last session started for Sprint(optional) <ul style="list-style-type: none"> <li>– 0x00 - No session since boot</li> <li>– 0x01 - Sprint CI-DC Session</li> <li>– 0x02 - Sprint CI-PRL Session</li> <li>– 0x03 - Sprint CI-FUMO Session</li> <li>– 0x04 - Sprint HFA-DC Session</li> <li>– 0x05 - Sprint HFA-PRL Session</li> <li>– 0x06 - Sprint HFA-FUMO Session</li> <li>– 0x07 - Sprint NI Session</li> </ul> </li> </ul>

<i>pSessionState</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating session state(optional) <ul style="list-style-type: none"> <li>– 0x01 - idle</li> <li>– 0x02 - active</li> <li>– 0x03 - pending</li> </ul> </li> </ul>
<i>pRetryCount</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating retries left count(optional) <ul style="list-style-type: none"> <li>– valid values 0 to 6</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

As input parameter the members pSourceLength, pPkgNameLength pPkgDescLength, pDateLength, pTimeLength have to be specified. These should contain the initialized size of pSource, pPkgName, pPkgDescription, pDate, pTime respectively.

**9.27.2.2 typedef struct \_SLQSOMADMSettings SLQSOMADMSettings**

Structure containing the OMA DM settings retrieved from the device

**Parameters**

<i>pOMADM-Enabled[OUT]</i>	<ul style="list-style-type: none"> <li>• 4 byte parameter indicating OMADM service enabled <ul style="list-style-type: none"> <li>– 0x00000001 - Client-initiated device configuration</li> <li>– 0x00000002 - Network-initiated device configuration</li> <li>– 0x00000010 - Client-initiated FUMO</li> <li>– 0x00000020 - Network-initiated FUMO</li> </ul> </li> <li>• function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFFFFFFFF in case this parameter is not returned by the modem.</li> </ul>
----------------------------	---

<i>pFOTA- Adownload[OUT]</i>	<ul style="list-style-type: none"> <li>• 1 Byte parameter indicating support for FOTA Automatic download <ul style="list-style-type: none"> <li>– 0x00 - Host permission required before downloading</li> <li>– 0x01 - Automatically start downloading, no host permission required</li> <li>– 0x02 - Automatically start downloading, while not roaming</li> <li>– 0x03 - Automatically reject download</li> <li>– 0x04 - Automatically reject download with “Enterprise Reject Policy”</li> </ul> </li> <li>• function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>
<i>pFOTAUpdate[OUT]</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating FOTA Automatic update <ul style="list-style-type: none"> <li>– 0x00 - User permission required before updating firmware</li> <li>– 0x01 - No user permission required before updating firmware</li> <li>– 0x02 - User permission required, auto update on power up</li> </ul> </li> <li>• function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>
<i>pAutosdm[OUT]</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating OMA Automatic UI Alert Response <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled Accept</li> <li>– 0x02 - Enabled Reject</li> </ul> </li> <li>• function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>
<i>pFwAutoCheck[OUT]</i>	<ul style="list-style-type: none"> <li>• Optional 1 byte parameter indicating OMA Automatic Check for Firmware Update on Power-Up Response <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled</li> </ul> </li> <li>• function <a href="#">SLQSOMADMGetSettings2()</a> returns a default value 0xFF in case this parameter is not returned by the modem.</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.27.2.3 typedef struct \_SLQSOMADMSettingsReqParams SLQSOMADMSettingsReqParams**

Structure containing the OMA DM settings to be set on the device

## Parameters

<i>FOTAdownload</i>	<ul style="list-style-type: none"> <li>• 1 Byte parameter indicating support for FOTA Automatic download <ul style="list-style-type: none"> <li>– 0x00 - Firmware auto download FALSE</li> <li>– 0x01 - Firmware auto download TRUE</li> </ul> </li> </ul>
<i>FOTAUpdate</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating FOTA Automatic update <ul style="list-style-type: none"> <li>– 0x00 - Firmware auto update FALSE</li> <li>– 0x01 - Firmware auto update TRUE</li> </ul> </li> </ul>
<i>pAutosdm[IN]</i>	<ul style="list-style-type: none"> <li>• Optional 1 byte parameter indicating OMA Automatic UI Alert Response <ul style="list-style-type: none"> <li>– 0x00 - Disabled</li> <li>– 0x01 - Enabled Accept</li> <li>– 0x02 - Enabled Reject</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.27.2.4 typedef struct \_SLQSOMADMSettingsReqParams3 SLQSOMADMSettingsReqParams3

Structure containing the OMA DM settings to be set on the device

## Parameters

<i>FOTAdownload</i>	<ul style="list-style-type: none"> <li>• 1 Byte parameter indicating support for FOTA Automatic download <ul style="list-style-type: none"> <li>– 0x00 - Firmware auto download FALSE</li> <li>– 0x01 - Firmware auto download TRUE</li> </ul> </li> </ul>
<i>FOTAUpdate</i>	<ul style="list-style-type: none"> <li>• 1 byte parameter indicating FOTA Automatic update <ul style="list-style-type: none"> <li>– 0x00 - Firmware auto update FALSE</li> <li>– 0x01 - Firmware auto update TRUE</li> </ul> </li> </ul>

<i>pAutosdm</i> [IN]	<ul style="list-style-type: none"> <li>Optional 1 byte parameter indicating OMA Automatic UI Alert Response <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled Accept</li> <li>0x02 - Enabled Reject</li> </ul> </li> </ul>
<i>pFwAutoCheck</i> [-IN]	<ul style="list-style-type: none"> <li>Optional 1 byte parameter indicating OMA Automatic Check for Firmware Update on Power-Up Response <ul style="list-style-type: none"> <li>0x00 - Disabled</li> <li>0x01 - Enabled</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.27.3 Function Documentation****9.27.3.1 ULONG SLQSOMADMCancelSession ( ULONG session )**

Cancels an ongoing OMA-DM session.

**Parameters**

<i>session</i> [IN]	<ul style="list-style-type: none"> <li>Session <ul style="list-style-type: none"> <li>0x01 - FOTA, to check availability of FW Update</li> <li>0xFF - Cancel any active OMADM session</li> </ul> </li> </ul>
---------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

**9.27.3.2 ULONG SLQSOMADMGetSessionInfo ( ULONG \* pSessionType, SLQSOMADMSessionInfo \* pResp )**

Returns information related to the current (or previous if no session is active) OMA-DM session.

## Parameters

<i>SessionType</i> [IN]	<ul style="list-style-type: none"> <li>Session type <ul style="list-style-type: none"> <li>0x01 - FOTA</li> <li>0xFF - Any active OMADM session. If none active, then previous OMADM session</li> </ul> </li> </ul>
<i>pResp</i> [IN/OUT]	<ul style="list-style-type: none"> <li>See <a href="#">SLQSOMADMSessionInfo</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 20 seconds

### 9.27.3.3 ULONG SLQSOMADMGetSettings ( ULONG \* pbOMADMEabled, ULONG \* pbFOTAdownload, ULONG \* pbFOTAUpdate )

Returns the OMA-DM settings.

## Parameters

<i>pbOMADM-Enabled</i> [OUT]	<ul style="list-style-type: none"> <li>Device OMADM service enabled <ul style="list-style-type: none"> <li>0x00000001 - Client-initiated device configuration</li> <li>0x00000002 - Network-initiated device configuration</li> <li>0x00000010 - Client-initiated FUMO</li> <li>0x00000020 - Network-initiated FUMO</li> </ul> </li> </ul>
<i>pbFOTAdownload</i> [OUT]	<ul style="list-style-type: none"> <li>Firmware AutoDownload <ul style="list-style-type: none"> <li>0x00 - Firmware auto download FALSE</li> <li>0x01 - Firmware autod ownload TRUE</li> <li>0x02 - Automatically start downloading, while not roaming</li> <li>0x03 - Automatically reject download</li> <li>0x04 - Automatically reject download with "Enterprise Reject Policy"</li> </ul> </li> </ul>

<i>pbFOTA-Update[OUT]</i>	<ul style="list-style-type: none"> <li>Firmware AutoUpdate             <ul style="list-style-type: none"> <li>0x00 - Firmware auto update FALSE</li> <li>0x01 - Firmware auto update TRUE</li> </ul> </li> </ul>
---------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

#### 9.27.3.4 ULONG SLQSOMADMGetSettings2 ( SLQSOMADMSettings \* pSLQSOMADMSettings )

Retrieves the OMA-DM settings from the device.

**Parameters**

<i>SLQSOMADM-SettingsReq-Params</i>	<ul style="list-style-type: none"> <li>See <a href="#">SLQSOMADMSettings</a> for more information</li> </ul>
-------------------------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

#### 9.27.3.5 ULONG SLQSOMADMSendSelection ( ULONG selection )

Sends the specified OMA-DM selection for the current network initiated session.

**Parameters**

<i>selection[IN]</i>	<ul style="list-style-type: none"> <li>OMA-DM NIA Selection             <ul style="list-style-type: none"> <li>0x01 - Accept</li> <li>0x02 - Reject</li> <li>0x03 - Defer</li> </ul> </li> </ul>
----------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

### 9.27.3.6 **ULONG SLQSOMADMSendSelection2 ( ULONG *selection*, ULONG \* *pDeferTime*, ULONG \* *pRejectReason* )**

Sends the specified OMA-DM selection for the current network initiated session.

**Parameters**

<i>selection</i> [IN]	<ul style="list-style-type: none"> <li>• OMA-DM NIA Selection <ul style="list-style-type: none"> <li>– 0x01 - Accept</li> <li>– 0x02 - Reject</li> <li>– 0x03 - Defer</li> </ul> </li> </ul>
<i>pDeferTime</i> [IN]	<ul style="list-style-type: none"> <li>• Defer time in minutes. A value of 0 will cause the prompt to be resent immediately.</li> <li>• This TLV is mandatory if selection is set to 0x03.</li> </ul>
<i>pRejectReason</i> [IN]	<ul style="list-style-type: none"> <li>• Reject Reason</li> <li>• This TLV is processed if selection is set to 0x02. If it is not present, the reject reason 0 is used as default.</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

### 9.27.3.7 **ULONG SLQSOMADMSetSettings ( ULONG *bFOTAdownload*, ULONG *bFOTAUpdate* )**

Sets the OMA-DM settings requested.



## Parameters

<i>bFOTA-Adownload</i> [IN]	<ul style="list-style-type: none"> <li>Firmware Auto Download <ul style="list-style-type: none"> <li>0x00 - Host permission required before downloading</li> <li>0x01 - Automatically start downloading, no host permission required</li> <li>0x02 - Automatically start downloading, while not roaming</li> <li>0x03 - Automatically reject download</li> <li>0x04 - Automatically reject download with “Enterprise Reject Policy”</li> </ul> </li> </ul>
<i>bFOTAUpdate</i> [IN]	<ul style="list-style-type: none"> <li>Firmware Auto Update <ul style="list-style-type: none"> <li>0x00 - User permission required before updating firmware</li> <li>0x01 - No user permission required before updating firmware</li> <li>0x02 - User permission required, auto update on power up</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 20 seconds

#### 9.27.3.8 ULONG SLQSOMADMSetSettings2 ( SLQSOMADMSettingsReqParams \* pSLQSOMADMSettingsReqParams )

Sets the settings related to OMADM. These settings are saved on the modem across power cycles.

## Parameters

<i>pSLQSOMADM-SettingsReq-Params</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">SLQSOMADMSettingsReqParams</a> for more information</li> </ul>
---	---

## Note

Timeout: 20 seconds

#### 9.27.3.9 ULONG SLQSOMADMSetSettings3 ( SLQSOMADMSettingsReqParams3 \* pSLQSOMADMSettingsReqParams3 )

Sets the settings related to OMADM. These settings are saved on the modem across power cycles.

## Parameters

<i>SLQSOMADM-SettingsReq-ParamsExt</i> [IN]	<ul style="list-style-type: none"> <li>• See SLQSOMADMSettingsReqParamsExt for more information</li> </ul>
---	--

## Note

Timeout: 20 seconds

### 9.27.3.10 **ULONG** SLQSOMADMStartSession ( **ULONG** *sessionType* )

Starts an OMA-DM session.

## Parameters

<i>sessionType</i> [IN]	<ul style="list-style-type: none"> <li>• Session type <ul style="list-style-type: none"> <li>– 0x01 - FOTA, to check availability of FW Update</li> <li>– 0x02 - DM, to check availability of DM Update</li> <li>– 0x03 - PRL, to check availability of PRL Update</li> </ul> </li> </ul>
-------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 20 seconds

### 9.27.3.11 **ULONG** SLQSOMADMStartSession2 ( **ULONG** *sessionType*, **ULONG** \* *pFwAvailability* )

Starts an OMA-DM session.

## Parameters

<i>sessionType</i> [IN]	<ul style="list-style-type: none"> <li>• Session type <ul style="list-style-type: none"> <li>– 0x01 - FOTA, to check availability of FW Update</li> <li>– 0x02 - DM, to check availability of DM Update</li> <li>– 0x03 - PRL, to check availability of PRL Update</li> </ul> </li> </ul>
-------------------------	---

<i>pFwAvailability[-OUT]</i>	<ul style="list-style-type: none"> <li>• OMA-DM CHECK FW Available <ul style="list-style-type: none"> <li>– 0x00000001 - FW Available. For CIDC and CIPRL, this value will be returned by the modem. CIDC and CIPRL are asynchronous OMADM sessions.</li> <li>– 0x00000002 - FW Not Available</li> <li>– 0x00000003 - FW Check Timed Out</li> </ul> </li> </ul>
------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

## 9.28 qaGobiApiTableBandClasses.h File Reference

Network Access Service API Band Classes table.

### 9.28.1 Detailed Description

Network Access Service API Band Classes table.

### 9.28.2 Band Classes (Value - Description)

- 0 - CDMA Band Class 0
- 1 - CDMA Band Class 1
- 3 - CDMA Band Class 3
- 4 - CDMA Band Class 4
- 5 - CDMA Band Class 5
- 6 - CDMA Band Class 6
- 7 - CDMA Band Class 7
- 8 - CDMA Band Class 8
- 9 - CDMA Band Class 9
- 10 - CDMA Band Class 10
- 11 - CDMA Band Class 11
- 12 - CDMA Band Class 12
- 13 - CDMA Band Class 13

- 14 - CDMA Band Class 14
- 15 - CDMA Band Class 15
- 16 - CDMA Band Class 16
- 17 - CDMA Band Class 17
- 18 - CDMA Band Class 18
- 19 - CDMA Band Class 19
- 40 - GSM 450
- 41 - GSM 480
- 42 - GSM 750
- 43 - GSM 850
- 44 - GSM 900 (Extended)
- 45 - GSM 900 (Primary)
- 46 - GSM 900 (Railways)
- 47 - GSM 1800
- 48 - GSM 1900
- 80 - WCDMA 2100
- 81 - WCDMA PCS 1900
- 82 - WCDMA DCS 1800
- 83 - WCDMA 1700 (US)
- 84 - WCDMA 850
- 85 - WCDMA 800
- 86 - WCDMA 2600
- 87 - WCDMA 900
- 88 - WCDMA 1700 (Japan)
- 90 - WCDMA 1500 band (Japan)
- 91 - WCDMA 850 band (Japan)
- < Reserved 89, 92-109 for WCDMA band classes>
- 110 - WLAN US 2400 MHz
- 111 - WLAN JAPAN 2400 MHz
- 112 - WLAN EUROPEAN 2400 MHz
- 113 - WLAN FRANCE 2400 MHz
- 114 - WLAN SPAIN 2400 MHz
- 115 - WLAN US 5000 MHz band
- 116 - WLAN JAPAN 5000 MHz
- 117 - WLAN EUROPEAN 5000 MHz
- 118 - WLAN FRANCE 5000 MHz
- 119 - WLAN SPAIN 5000 MHz

## 9.28.2.1 LTE Bands

- 28 - LTE Band Class 28
- 39 - LTE Band Class 39
- 40 - LTE Band Class 40
- 41 - LTE Band Class 41
- 120 - FDD UL:1920-1980; DL:2110-2170; E-UTRA Operating Band 1
- 121 - FDD UL:1850-1910; DL:1930-1990; E-UTRA Operating Band 2
- 122 - FDD UL:1710-1785; DL:1805-1880; E-UTRA Operating Band 3
- 123 - FDD UL:1710-1755; DL:2110-2155; E-UTRA Operating Band 4
- 124 - FDD UL: 824- 849; DL: 869- 894; E-UTRA Operating Band 5
- 125 - FDD UL: 830- 840; DL: 875- 885; E-UTRA Operating Band 6
- 126 - FDD UL:2500-2570; DL:2620-2690; E-UTRA Operating Band 7
- 127 - FDD UL: 880- 915; DL: 925- 960; E-UTRA Operating Band 8
- 128 - FDD UL:1749.9-1784.9; DL:1844.9-1879.9; E-UTRA Operating Band 9
- 129 - FDD UL:1710-1770; DL:2110-2170; E-UTRA Operating Band 10
- 130 - FDD UL:1427.9-1452.9; DL:1475.9-1500.9; E-UTRA Operating Band 11
- 131 - FDD UL:698-716; DL:728-746; E-UTRA Operating Band 12
- 132 - FDD UL: 777- 787; DL: 746-756; E-UTRA Operating Band 13
- 133 - FDD UL: 788- 798; DL: 758-768; E-UTRA Operating Band 14
- 134 - FDD UL: 704-716; DL: 734-746; E-UTRA Operating Band 17
- 135 - TDD LTE UL: 1900-1920; DL: 1900-1920; E-UTRA Operating Band 33
- 136 - TDD LTE UL: 2010-2025; DL: 2010-2025; E-UTRA Operating Band 34
- 137 - TDD LTE UL: 1850-1910; DL: 1850-1910; E-UTRA Operating Band 35
- 138 - TDD LTE UL: 1930-1990; DL: 1930-1990; E-UTRA Operating Band 36
- 139 - TDD LTE UL: 1910-1930; DL: 1910-1930; E-UTRA Operating Band 37
- 140 - TDD LTE UL: 2570-2620; DL: 2570-2620; E-UTRA Operating Band 38
- 141 - TDD LTE UL: 1880-1920; DL: 1880-1920; E-UTRA Operating Band 39
- 142 - TDD LTE UL: 2300-2400; DL: 2300-2400; E-UTRA Operating Band 40
- 143 - FDD LTE UL: 815-830; DL: 860-875; E-UTRA Operating Band 18
- 144 - FDD LTE UL: 830-845; DL: 875-890; E-UTRA Operating Band 19
- 145 - FDD LTE UL: 832-862; DL: 791-821; E-UTRA Operating Band 20
- 146 - FDD LTE UL: 1447.9-1462.9; DL: 1495.9-1510.9; E-UTRA Operating Band 21
- 147 - FDD LTE UL: 1626.5-1660.5; DL: 1525-1559; E-UTRA Operating Band 24
- 148 - FDD LTE UL: 1850-1919.5; DL: 1930-1995; E-UTRA Operating Band 25
- 149 - TDD LTE UL: 2496-2690; DL: 2496-2690; E-UTRA Operating Band 41

- 150 - TDD LTE UL: 3400-3600; DL: 3400-3600; E-UTRA Operating Band 42
- 151 - TDD LTE UL: 3600-3800; DL: 3600-3800; E-UTRA Operating Band 43
- 200 - TD-SCDMA Band A
- 201 - TD-SCDMA Band B
- 202 - TD-SCDMA Band C
- 203 - TD-SCDMA Band D
- 204 - TD-SCDMA Band E
- 205 - TD-SCDMA Band F

Copyright: © 2011 Sierra Wireless, Inc. all rights reserved

## 9.29 qaGobiApiTableCallControlReturnReasons.h File Reference

Call Control Return Reasons table.

### 9.29.1 Detailed Description

Call Control Return Reasons table.

### 9.29.2 Call Control Result Reasons (Value - Name - Description)

- 0x01 - QMI\_VOICE\_REASON\_FWD\_UNCONDITIONAL - Unconditional call forwarding
- 0x02 - QMI\_VOICE\_REASON\_FWD\_MOBILEBUSY - Forward when the mobile is busy
- 0x03 - QMI\_VOICE\_REASON\_FWD\_NOREPLY - Forward when there is no reply
- 0x04 - QMI\_VOICE\_REASON\_FWD\_UNREACHABLE - Forward when the call is unreachable
- 0x05 - QMI\_VOICE\_REASON\_FWD\_ALLFORWARDING - All forwarding
- 0x06 - QMI\_VOICE\_REASON\_FWD\_ALLCONDITIONAL - All conditional forwarding
- 0x07 - QMI\_VOICE\_REASON\_BARR\_ALLOUTGOING - All outgoing
- 0x08 - QMI\_VOICE\_REASON\_BARR\_OUTGOINGINT - Outgoing internal
- 0x09 - QMI\_VOICE\_REASON\_BARR\_OUTGOINGINTEXTOHOM - Outgoing external to home
- 0x0A - QMI\_VOICE\_REASON\_BARR\_ALLINCOMING - All incoming
- 0x0B - QMI\_VOICE\_REASON\_BARR\_INCOMINGROAMING - Roaming incoming
- 0x0C - QMI\_VOICE\_REASON\_BARR\_ALLBARRING - All calls are barred
- 0x0D - QMI\_VOICE\_REASON\_BARR\_ALLOUTGOINGBARRING - All outgoing calls are barred
- 0x0E - QMI\_VOICE\_REASON\_BARR\_ALLINCOMINGBARRING - All incoming calls are barred
- 0x0F - QMI\_VOICE\_REASON\_CALLWAITING - Call waiting
- 0x10 - VOICE\_CC\_SUPS\_RESULT\_REASON\_CLIP - CLIP
- 0x11 - VOICE\_CC\_SUPS\_RESULT\_REASON\_CLIR - CLIR
- 0x12 - VOICE\_CC\_SUPS\_RESULT\_REASON\_COLP - COLP

- 0x13 - VOICE\_CC\_SUPS\_RESULT\_REASON\_COLR - COLR
- 0x14 - VOICE\_CC\_SUPS\_RESULT\_REASON\_CNAP - CNAP
- 0xFF - Not Available

Copyright: © 2012 Sierra Wireless, Inc. all rights reserved

## 9.30 qaGobiApiTableCallEndReasons.h File Reference

Wireless Data Service Call End Reasons.

### 9.30.1 Detailed Description

Wireless Data Service Call End Reasons.

### 9.30.2 Call end reason codes (Code - Reason)

#### 9.30.2.1 Technology-agnostic call end reasons

- 1 - Reason unspecified, check the verbose call end reason
- 2 - Client ended the call
- 3 - Device has no service
- 4 - Call ended abnormally
- 5 - Received release from base station; no reason given
- 6 - Access attempt already in progress; SD2.0 only
- 7 - Access failure for reason other than the above
- 8 - Call rejected because of redirection or handoff
- 9 - Call failed because close is in progress
- 10 - Authentication failed, 3GPP equivalent ESM(EPS Session Management) cause code value 29, User authentication failed
- 11 - Call ended because of internal call end. This error code is returned when data call is brought down due to some unknown error, such as not specific to any RAT
- 12 - Call ended because of internal error. This error code is returned when data call is brought down due to some unspecified internal error, such as NULL pointer
- 13 - Internal unknown cause code

#### 9.30.2.2 EVDO CDMA 1xEV-DO

- 500 - Device is CDMA-locked until power cycle
- 501 - Received intercept from base station; origination only
- 502 - Received reorder from base station; origination only
- 503 - Received release from base station; service option reject
- 504 - Received incoming call from base station

- 505 - Received alert stop from base station; incoming only
- 506 - Received end activation; OTASP call only
- 507 - Max access probes transmitted
- 508 - Concurrent service is not supported by base station
- 509 - No response received from base station
- 510 - Call rejected by the base station; CDMA only
- 511 - Concurrent services requested were not compatible; CDMA only
- 512 - Corresponds to CM CALL ORIG ERR ALREADY IN TC
- 513 - Used if Call manager subsystem is ending a GPS call in favor of a user call
- 514 - Used if Call manager subsystem is ending a SMS call in favor of a user call
- 515 - CDMA Only; Device has no service

#### 9.30.2.3 WCDMA/GSM call end reasons

- 1000 - Call origination request failed; WCDMA/GSM Only
- 1001 - Client rejected the incoming call; WCDMA/GSM Only
- 1002 - Device has no UMTS service; WCDMA/GSM Only
- 1003 - Network ended the call, look in cc call; WCDMA/GSM Only
- 1004 - LLC(Logical Link Control) or SNDSCP(Sub Network Dependent Convergence Protocol) failure
- 1005 - Insufficient resources, 3GPP equivalent ESM(EPS Session Management) cause code value 26, Insufficient resources
- 1006 - Service option temporarily out of order, 3GPP equivalent ESM(EPS Session Management) cause code value 34, Service option temporarily out of order
- 1007 - PTI already used, 3GPP equivalent ESM(EPS Session Management) cause code value 35, PTI(-Procedure Transaction Identity) already in use
- 1008 - Regular PDP context deactivation, 3GPP equivalent ESM(EPS Session Management) cause code value 36, Regular deactivation
- 1009 - Network failure, 3GPP equivalent ESM(EPS Session Management) cause code value 38, Network failure
- 1010 - Reactivation requested, 3GPP equivalent ESM(EPS Session Management) cause code value 39, Reactivation requested
- 1011 - Protocol error, unspecified, 3GPP equivalent ESM(EPS Session Management) cause code value 111, Protocol error, unspecified
- 1012 - Operator determined barring, 3GPP equivalent ESM(EPS Session Management) cause code value 8, Operator Determined Barring
- 1013 - Unknown or missing Access Point Name (APN), 3GPP equivalent ESM(EPS Session Management) cause code value 27, Missing or unknown APN
- 1014 - Unknown PDP address or PDP type, 3GPP equivalent ESM(EPS Session Management) cause code value 28, Unknown PDN type
- 1015 - Activation rejected by GGSN, 3GPP equivalent ESM(EPS Session Management) cause code value 30, Requested rejected by Serving GW or PDN GW



- 1016 - Activation rejected, unspecified, 3GPP equivalent ESM(EPS Session Management) cause code value 31, Request rejected, unspecified
- 1017 - Service option not supported, 3GPP equivalent ESM(EPS Session Management) cause code value 32, Service option not supported
- 1018 - Requested service option not subscribed, 3GPP equivalent ESM(EPS Session Management) cause code value 33, Requested service option not subscribed
- 1019 - EPS Quality of Service (QoS) not accepted, 3GPP equivalent ESM(EPS Session Management) cause code value 37, EPS QoS not accepted
- 1020 - Semantic error in the TFT operation, 3GPP equivalent ESM(EPS Session Management) cause code value 41, Semantic error in the TFT operation
- 1021 - Syntactical error in the TFT operation, 3GPP equivalent ESM(EPS Session Management) cause code value 42, Syntactical error in the TFT operation
- 1022 - Unknown PDP context, 3GPP equivalent ESM(EPS Session Management) cause code value 43, Invalid EPS bearer identity
- 1023 - Semantic errors in packet filter(s), 3GPP equivalent ESM(EPS Session Management) cause code value 44, Semantic errors in packet filter(s)
- 1024 - Syntactical error in packet filter(s), 3GPP equivalent ESM(EPS Session Management) cause code value 45, Syntactical errors in packet filter(s)
- 1025 - PDP context without TFT already activated, 3GPP equivalent ESM(EPS Session Management) cause code value 46, Unused
- 1026 - Invalid transaction identifier value, 3GPP equivalent ESM(EPS Session Management) cause code value 81, Invalid PTI value
- 1027 - Semantically incorrect message, 3GPP equivalent ESM(EPS Session Management) cause code value 95, Semantically incorrect message
- 1028 - Invalid mandatory information, 3GPP equivalent ESM(EPS Session Management) cause code value 96, Invalid mandatory information
- 1029 - Message type non-existent or not implemented, 3GPP equivalent ESM(EPS Session Management) cause code value 97, Message type non-existent or not implemented
- 1030 - Message not compatible with state, 3GPP equivalent ESM(EPS Session Management) cause code value 98, Message type not compatible with the protocol state
- 1031 - Information element nonexistent or not implemented, 3GPP equivalent ESM(EPS Session Management) cause code value 99, Information element non-existent or not implemented
- 1032 - Conditional information element error, 3GPP equivalent ESM(EPS Session Management) cause code value 100, Conditional IE error
- 1033 - Message not compatible with protocol state, 3GPP equivalent ESM(EPS Session Management) cause code value 101, Message not compatible with the protocol state
- 1034 - APN restriction value incompatible with active PDP context, 3GPP equivalent ESM(EPS Session Management) cause code value 112, APN restriction value incompatible with
  - active EPS bearer context
- 1035 - No GPRS context present
- 1036 - Requested feature not supported, 3GPP equivalent ESM(EPS Session Management) cause code value 40, Feature not supported
- 1037 - Illegal MS, 3GPP equivalent EMM(EPS Mobility Management) cause code value 3, Illegal UE (MS)

- 1038 - Illegal ME, 3GPP equivalent EMM(EPS Mobility Management) cause code value 6, Illegal ME. This error code is sent to the MS if the ME used is not acceptable
  - to the network, e.g. blacklisted
- 1039 - GPRS and non GPRS services not allowed
- 1040 - GPRS services not allowed
- 1041 - MS identity not derived by the network, 3GPP equivalent EMM(EPS Mobility Management) cause code value 9, UE (MS) Identify cannot be derived by the network
- 1042 - Implicitly detached, 3GPP equivalent EMM(EPS Mobility Management) cause code value 10, Implicitly Detached
- 1043 - PLMN not allowed, 3GPP equivalent EMM(EPS Mobility Management) cause code value 11, PLMN not allowed
- 1044 - LA not allowed, this cause is sent to the MS if it requests location updating in a location area where the HPLMN determines that the MS, by subscription, is not allowed to operate.
- 1045 - GPRS services not allowed in PLMN
- 1046 - PDP duplicate
- 1047 - UE radio access technology change
- 1048 - app preempted
- 1049 - Congestion, This cause is sent if the service request or LOCATION UPDATING REQUEST message cannot be actioned because of congestion (e.g. congestion of the MSC or SGSN or GGSN or PDN Gateway; no channel; facility busy/congested etc.).
- 1050 - No PDP context activated
- 1051 - Access class DSAC rejection

#### 9.30.2.4 EVDO CDMA 1xEV-DO

- 1500 - Abort connection setup due to the reception of a Connection Deny message with deny code set to either general or network busy.
- 1501 - Abort connection setup due to the reception of a Connection Deny message with deny code set to either billing or authentication failure.
- 1502 - Change HDR system due to redirection or PRL not preferred
- 1503 - Exit HDR due to redirection or PRL not preferred
- 1504 - No HDR session
- 1505 - Used if Call manager is ending an HDR call origination in favor of a GPS fix
- 1506 - Connection setup timeout
- 1507 - Call manager released HDR call so 1x call can continue

#### 9.30.2.5 call end reason type

- 1 - Mobile IP
- 2 - Internal
- 3 - Call Manager defined
- 6 - 3GPP specification defined
- 7 - PPP
- 8 - EHRPD
- 9 - IPv6

#### 9.30.2.6 Mobile IP call end reasons (Type=1)

- 64 - MIP(Mobile IP) FA(Foreign Agent) ERR REASON UNSPECIFIED, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration with unspecified reason
- 65 - MIP(Mobile IP) FA(Foreign Agent) ERR ADMINISTRATIVELY PROHIBITED, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent administratively prohibited MIP registration
- 66 - MIP(Mobile IP) FA(Foreign Agent) ERR INSUFFICIENT RESOURCES, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to insufficient resources
- 67 - MIP(Mobile IP) FA(Foreign Agent) ERR MOBILE NODE AUTHENTICATION FAILURE, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration because MN-AAA authenticator was wrong
- 68 - MIP(Mobile IP) FA(Foreign Agent) ERR HA AUTHENTICATION FAILURE, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration because of home agent authentication failure
- 69 - MIP(Mobile IP) FA(Foreign Agent) ERR REQUESTED LIFETIME TOO LONG, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration because requested lifetime is too long
- 70 - MIP(Mobile IP) FA(Foreign Agent) ERR MALFORMED REQUEST, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to malformed request
- 71 - MIP(Mobile IP) FA(Foreign Agent) ERR MALFORMED REPLY, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to malformed reply
- 72 - MIP(Mobile IP) FA(Foreign Agent) ERR ENCAPSULATION UNAVAILABLE, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration because requested encapsulation is unavailable
- 73 - MIP(Mobile IP) FA(Foreign Agent) ERR VJHC UNAVAILABLE, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration because VJ Header Compression is unavailable
- 74 - MIP(Mobile IP) FA(Foreign Agent) ERR REVERSE TUNNEL UNAVAILABLE, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration because reverse tunnel is unavailable
- 75 - MIP(Mobile IP) FA(Foreign Agent) ERR REVERSE TUNNEL IS MANDATORY AND T BIT NOT SET, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration because reverse tunnel is mandatory but not requested by device

- 79 - MIP(Mobile IP) FA(Foreign Agent) ERR DELIVERY STYLE NOT SUPPORTED, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration because delivery style is not supported
- 97 - MIP(Mobile IP) FA(Foreign Agent) ERR MISSING NAI, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to missing NAI
- 98 - MIP(Mobile IP) FA(Foreign Agent) ERR MISSING HA, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to missing Home Agent
- 99 - MIP(Mobile IP) FA(Foreign Agent) ERR MISSING HOME ADDR, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to missing Home Address
- 104 - MIP(Mobile IP) FA(Foreign Agent) ERR UNKNOWN CHALLENGE, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to unknown challenge
- 105 - MIP(Mobile IP) FA(Foreign Agent) ERR MISSING CHALLENGE, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to missing challenge
- 106 - MIP(Mobile IP) FA(Foreign Agent) ERR STALE CHALLENGE, this error code is returned when the data call bring up fails in MIP setup phase since foreign agent rejected MIP registration due to stale challenge
- 128 - MIP(Mobile IP) FA(Home Agent) ERR REASON UNSPECIFIED, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration with unspecified reason
- 129 - MIP(Mobile IP) FA(Home Agent) ERR ADMINISTRATIVELY PROHIBITED, this error code is returned when the data call bring up fails in MIP setup phase since home agent administratively prohibited MIP registration
- 130 - MIP(Mobile IP) FA(Home Agent) ERR INSUFFICIENT RESOURCES, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration due to insufficient resources
- 131 - MIP(Mobile IP) FA(Home Agent) ERR MOBILE NODE AUTHENTICATION FAILURE, this error code is returned when the data call bring up fails in MIP setup phase since home agent fails authentication because MN-HA authenticator was wrong
- 132 - MIP(Mobile IP) FA(Home Agent) ERR FA AUTHENTICATION FAILURE, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration due to FA authentication failure
- 133 - MIP(Mobile IP) FA(Home Agent) ERR REGISTRATION ID MISMATCH, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration due to registration id mismatch
- 134 - MIP(Mobile IP) FA(Home Agent) ERR MALFORMED REQUEST, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration due to malformed request
- 136 - MIP(Mobile IP) FA(Home Agent) ERR UNKNOWN HA ADDR, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration due to unknown Home Agent address. This code is returned by a home agent when the mobile node is performing dynamic home agent address resolution as described in RFC 3220 (IP Mobility Support for IPV4) Sections 3.6.1.1 and 3.6.1.2
- 137 - MIP(Mobile IP) FA(Home Agent) ERR REVERSE TUNNEL UNAVAILABLE, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration because reverse tunnel is unavailable
- 138 - MIP(Mobile IP) FA(Home Agent) ERR REVERSE TUNNEL IS MANDATORY AND T BIT NOT SET, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration because reverse tunnel is mandatory but not requested by device

- 139 - MIP(Mobile IP) FA(Home Agent) ERR ENCAPSULATION UNAVAILABLE, this error code is returned when the data call bring up fails in MIP setup phase since home agent rejected MIP registration due to encapsulation unavailable
- 65536 - MIP ERR REASON UNKNOWN

#### 9.30.2.7 Internal call end reasons (Type=2)

- 200 - INTERNAL MIN, internal error table offset value, no meaningful message to the error.
- 201 - INTERNAL ERROR, this error code is returned when data call is brought down due to some unspecified internal error
- 202 - CALL ENDED
- 203 - INTERNAL UNKNOWN CAUSE CODE, this error code is returned when data call is brought down due to some unknown error
- 204 - UNKNOWN CAUSE CODE, this error code is returned when data call is brought down due to some unknown error
- 205 - CLOSE IN PROGRESS
- 206 - NETWORK INITIATED TERMINATION
- 207 - APP PREEMPTED
- 208 - ERR PDN IPV4 CALL DISALLOWED, this error code is returned when V4 PDN is in throttled state due to network providing only V6 address during the previous VSNCP bring up (subs\_limited\_to\_v6). The time for which the IPv4 PDN is throttled is determined by the IPv4 throttling timers maintained in the profile
- 209 - ERR PDN IPV4 CALL THROTTLED, this error code is returned when V4 PDN is in throttled state due to previous VSNCP bring up failure(s). The time for which the IPv4 PDN is throttled is determined by the IPv4 throttling timers maintained in the profile
- 210 - ERR PDN IPV6 CALL DISALLOWED, this error code is returned when V6 PDN is in throttled state due to network providing only V4 address during the previous VSNCP bring up (subs\_limited\_to\_v4). The time for which the IPv6 PDN is throttled is determined by the IPv6 throttling timers maintained in the profile
- 211 - ERR PDN IPV6 CALL THROTTLED, this error code is returned when V6 PDN is in throttled state due to previous VSNCP bring up failure(s). The time for which the IPv6 PDN is throttled is determined by the IPv6 throttling timers maintained in the profile
- 212 - MODEM RESTART
- 213 - PDP PPP NOT SUPPORTED
- 214 - UNPREFERRED RAT, this error code is returned when data call is brought down since the RAT on which the data call is attempted/connected is no longer the preferred RAT
- 215 - PHYS LINK CLOSE IN PROGRESS, this error code is returned when data call bring up is rejected because physical link is in the process of cleanup
- 216 - APN PENDING HANDOVER, this error code is returned when interface bring up is attempted for an APN that is yet to be handed over to target RAT
- 217 - PROFILE BEARER INCOMPATIBLE
- 218 - MMGSDI CARD EVT, this error code is returned when data call is brought down because card got refreshed/removed
- 219 - LPM OR PWR DOWN, this error code is returned when data call is brought down because device is going into lower power mode or powering down
- 220 - APN DISABLED, this error code is returned when APN is disabled in card

- 221 - MPIT EXPIRED, this error code is returned when data call is brought down because maximum PPP inactivity timer expired
- 222 - IPV6 ADDR TRANSFER FAILED
- 223 - TRAT SWAP FAILED
- 224 - EHRPD TO HRPD FALLBACK, this error code is returned when data call is brought down because device falls back from eHRPD to HRPD (not because of OOS on eHRPD but due to operator/spec driven eHRPD to HRPD fallback requirements)
- 225 - MANDATORY APN DISABLED, this error code is returned when any mandatory APN is disabled, and MinApnList Disallow call config item is set to TRUE in device
- 226 - MIP CONFIG FAILURE, this error code is returned when UE is in MIP Only config (QCMIP=2) but MIP config fails on call bring up due to incorrect provisioning

#### 9.30.2.8 Call Manager defined call end reasons (Type=3)

- 500 - CDMA LOCK, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to device in CDMA locked state
- 501 - INTERCEPT, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since it received an intercept order from the base station
- 502 - REORDER, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) due to receiving a reorder from base station
- 503 - REL SO REJ, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to receiving a release from base station with reason: SO Reject
- 504 - INCOM CALL, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since it received an incoming call from base station
- 505 - ALERT STOP, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to RL/FL fade (or) receiving call release from base stations
- 506 - ACTIVATION, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to channel acquisition failures. This indicates that device has failed acquiring all the channels in the PRL
- 507 - MAX ACCESS PROBE, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) due maximum access probes transmitted
- 508 - CCS NOT SUPPORTED BY BS, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since concurrent service is not supported by base station
- 509 - NO RESPONSE FROM BS, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since there is no response received from base station
- 510 - REJECTED BY BS, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) due to base station rejecting the call
- 511 - INCOMPATIBLE, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since concurrent services requested were not compatible
- 512 - ALREADY IN TC, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since traffic channel is already up for voice calls
- 513 - USER CAL ORIG DURING GPS
- 514 - USER CAL ORIG DURING SMS, this error code is returned when data call is brought down because traffic channel request got rejected since SMS is ongoing

- 515 - NO CDMA SRV, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since device does not have CDMA service
- 516 - MC ABORT, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since MC aborted the origination/conversation
- 517 - PSIST NG, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to persistence test failure
- 518 - UIM NOT PRESENT, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to RUIM not present
- 519 - RETRY ORDER, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) due to receiving a retry order from base station
- 520 - ACCESS BLOCK, this error code is returned when data call is brought down because traffic channel rejected/released due to Access blocked by base station
- 521 - ACCESS BLOCK ALL, this error code is returned when data call is brought down because traffic channel rejected due to Access blocked by the base station for all mobile devices
- 522 - IS707B MAX ACC, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) due maximum access probes for IS-707B call
- 523 - THERMAL EMERGENCY, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) to put device in thermal emergency
- 524 - CALL ORIG THROTTLED, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since call origination is throttled by DCTM module
- 525 - USER CALL ORIGINATE DURING VOICE CALL, this error code is returned when data call is brought down because traffic channel got released by CM(Call Manager) in favor of voice call or SMS when concurrent voice and data are not supported
- 1000 - CONFERENCE FAILED
- 1001 - INCOMING REJECTED
- 1002 - NO GATEWAY SERVICE
- 1003 - NO GPRS CONTEXT
- 1004 - ILLEGAL MS, This cause is sent to the MS when the network refuses service to the MS either because an identity of the MS is not acceptable to the network or because the MS does not pass the authentication check, i.e. the SRES received from the MS is different from that generated by the network
- 1005 - ILLEGAL ME, This cause is sent to the MS if the ME used is not acceptable to the network, e.g. blacklisted
- 1006 - GPRS SERVICES AND NON GPRS SERVICES NOT ALLOWED
- 1007 - GPRS SERVICES NOT ALLOWED
- 1008 - MS IDENTITY CANNOT BE DERIVED BY THE NETWORK
- 1009 - IMPLICITLY DETACHED, this error code is sent to the MS either if the network has implicitly detached the MS, e.g. some while after the Mobile reachable timer has expired, or if the GMM context data related to the subscription does not exist in the SGSN e.g. because of a SGSN restart.
- 1010 - PLMN NOT ALLOWED, this error code is sent to the MS if it requests location updating in a PLMN where the MS, by subscription or due to operator determined barring is not allowed to operate
- 1011 - LOCAL AREA NOT ALLOWED
- 1012 - GPRS SERVICES NOT ALLOWED IN THIS PLMN
- 1013 - PDP DUPLICATE

- 1014 - USER EQUIPMENT RADIO ACCESS TECHNOLOGY CHANGE
- 1015 - CONGESTION
- 1016 - NO PDP CONEXT ACTIVATED
- 1017 - ACCESS CLASS DSAC REJECTION
- 1018 - PDP ACTIVATE MAX RETRY FAILED
- 1019 - RAB FAILURE
- 1020 - EPS SERVICE NOT ALLOWED
- 1021 - TRACKING AREA NOT ALLOWED
- 1022 - ROAMING NOT ALLOWED IN THIS TRACKING AREA
- 1023 - NO SUITABLE CELLS IN TRACKING AREA
- 1024 - NOT AUTHORIZED FOR THIS CLOSED SUBSCRIBER GROUP
- 1025 - ESM UNKNOWN EPS BEARER CONTEXT
- 1026 - DRB RELEASED AT RRC
- 1027 - NAS SIG CONN RELEASED
- 1028 - EPS MOBILITY MANAGEMENT DETACHED
- 1029 - EPS MOBILITY MANAGEMENT ATTACH FAILED
- 1030 - EPS MOBILITY MANAGEMENT ATTACH STARTED
- 1031 - LTE NAS SERVICE REQ FAILED
- 1032 - ESM(EPS Session Management) ACTIVE DEDICATED BEARER REACTIVATED BY NW
- 1033 - ESM(EPS Session Management) LOWER LAYER FAILURE
- 1034 - ESM(EPS Session Management) SYNC UP WITH NW
- 1035 - ESM(EPS Session Management) NW ACTIVATED DED BEARER WITH ID OF DEF BEARER
- 1036 - ESM(EPS Session Management) BAD OTA MESSAGE
- 1037 - ESM DS REJECTED THE CALL
- 1038 - ESM(EPS Session Management) CONTEXT TRANSFERRED DUE TO IRAT
- 1039 - DS EXPLICIT DEACT
- 1040 - ESM(EPS Session Management) LOCAL CAUSE NONE
- 1041 - LTE NAS SERVICE REQ FAILED NO THROTTLE
- 1042 - ACL FAILURE, This error code should rarely triggered and reported to the application
- 1043 - LTE NAS SERVICE REQ FAILED DS DISALLOW
- 1044 - EMM(EPS Mobility Management) T3417 EXPIRED
- 1045 - EMM(EPS Mobility Management) T3417 EXT EXPIRED
- 1046 - LRR(LTE Radio Resource Control) UL DATA CNF FAILURE TXN - Light Radio Resource Controller Uplink data confirmation failure
- 1047 - LRR(LTE Radio Resource Control) UL DATA CNF FAILURE HO
- 1048 - LRR(LTE Radio Resource Control) UL DATA CNF FAILURE CONN REL



- 1049 - LRRRC(LTE Radio Resource Control) UL DATA CNF FAILURE RLF
- 1050 - LRRRC(LTE Radio Resource Control) UL DATA CNF FAILURE CTRL NOT CONN
- 1051 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE
- 1052 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE ABORTED
- 1053 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE ACCESS BARRED
- 1054 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE CELL RESEL
- 1055 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE CONFIG FAILURE
- 1056 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE TIMER EXPIRED
- 1057 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE LINK FAILURE
- 1058 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE NOT CAMPED
- 1059 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE SI FAILURE
- 1060 - LRRRC(LTE Radio Resource Control) CONN EST FAILURE CONN REJECT
- 1061 - LRRRC(LTE Radio Resource Control) CONN REL NORMAL
- 1062 - LRRRC(LTE Radio Resource Control) CONN REL RLF
- 1063 - LRRRC(LTE Radio Resource Control) CONN REL CRE FAILURE
- 1064 - LRRRC(LTE Radio Resource Control) CONN REL OOS DURING CRE
- 1065 - LRRRC(LTE Radio Resource Control) CONN REL ABORTED
- 1066 - LRRRC(LTE Radio Resource Control) CONN REL SIB READ ERROR
- 1067 - DETACH WITH REATTACH LTE NW DETACH
- 1068 - DETACH WITH OUT REATTACH LTE NW DETACH
- 1069 - ESM(EPS Session Management) PROC TIME OUT
- 1070 - MESSAGE EXCEED MAX L2 LIMIT
- 1500 - CD GEN OR BUSY, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to the reception of a Connection Deny message with a deny code of general or network busy
- 1501 - CD BILL OR AUTH, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to the reception of a Connection Deny message with a deny code of billing failure or authentication failure
- 1502 - CHG HDR, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since there is a change to HDR system due to redirection or PRL not preferred
- 1503 - EXIT HDR, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since device exited HDR due to redirection or PRL not preferred
- 1504 - HDR NO SESSION, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since device does not have a HDR session
- 1505 - HDR ORIG DURING GPS FIX, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since it is ending an HDR call origination in favor of a GPS fix
- 1506 - HDR CS TIMEOUT, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since connection setup on HDR system timed out

- 1507 - HDR RELEASED BY CM, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) when it wants to release a HDR call so a 1X call can continue
- 1508 - COLLOC ACQ FAIL, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) when device failed to acquire co-located HDR for origination
- 1509 - OTASP COMMIT IN PROG, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since an OTASP commit is in progress
- 1510 - NO HYBR HDR SRV, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since device has no Hybrid HDR service
- 1511 - HDR NO LOCK GRANTED, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since HDR module could not get the RF lock
- 1512 - HOLD OTHER IN PROG, this error code is returned when data call is brought down by CM(Call Manager) because DBM or SMS is in progress
- 1513 - HDR FADE, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since HDR module released the call due to fade
- 1514 - HDR ACC FAIL, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to HDR system Access Failure
- 2000 - CLIENT END, this error code is returned when client ends the data call
- 2001 - NO SRV, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since device has no service
- 2002 - FADE, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since device lost the system due to fade
- 2003 - REL NORMAL, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to receiving a release from base station with no reason
- 2004 - ACC IN PROG, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to Access attempt already in progress
- 2005 - ACC FAIL, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) due to Access Failure
- 2006 - REDIR OR HANDOFF, this error code is returned when data call is brought down because device is in the process of redirecting/handing off to a different target system
- 2500 - OFFLINE, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since device went offline
- 2501 - EMERGENCY MODE, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since device is operating in Emergency mode
- 2502 - PHONE IN USE, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since device is in use (e.g voice call)
- 2503 - INVALID MODE, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since the device's operational mode is different from the mode requested in the traffic channel bring up
- 2504 - INVALID SIM STATE, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since the SIM was marked by network as invalid for circuit and/or packet service domain
- 2505 - NO COLLOC HDR, this error code is returned when data call is brought down because traffic channel got rejected/released by CM(Call Manager) since there is no collocated HDR
- 2506 - CALL CONTROL REJECTED, this error code is returned when data call is brought down because traffic channel request got rejected by CM(Call Manager) since Call control module rejected the request

## 9.30.2.9 3GPP specification defined call end reasons (Type=6)

- 8 - OPERATOR DETERMINED BARRING, this reason code is posted by the MME(Mobility Management Entity) to indicate operator has barred the UE
- 25 - LLC SNDCP FAILURE, PDP context deactivation initiated by the MS or by the Network
- 26 - INSUFFICIENT RESOURCES, this reason is posted to indicate that the network cannot provide the requested service due to insufficient resources
- 27 - MISSING OR UNKNOWN APN, the APN was required and not specified or APN could not be resolved. In LTE mode of operation, this is a PDN throttling cause code, meaning the UE may end up throttling further requests to the same APN
- 28 - UNKNOWN PDN TYPE, the reason is posted by the network to indicate that the PDN type was not recognized
- 29 - AUTH FAILED, the reason is posted when authentication fails. In LTE mode of operation, this is a PDN throttling cause code, meaning the UE may end up throttling further requests to the same APN
- 30 - GGSN REJECT, the reason is posted when the request was rejected by Serving GW or PDN GW. In LTE mode of operation, this is a PDN throttling cause code, meaning the UE may end up throttling further requests to the same APN
- 31 - ACTIVATION REJECT, the reason is posted when the request is rejected by the network due to unspecified reasons
- 32 - OPTION NOT SUPPORTED, the reason is posted when UE requested a service not supported by the PLMN
- 33 - OPTION UNSUBSCRIBED, This cause is sent when the MS requests a service option for which it has no subscription
- 34 - OPTION TEMP OOO, service option temporarily out of order, this reason is posted when the network is temporarily out of resources to service the request
- 35 - PTI ALREADY USED, the reason is posted to indicate that PTI (Procedure Transaction Identifier) used in the request is already active via another UE requested procedure
- 36 - REGULAR DEACTIVATION, this reason is posted by the network to initiate a regular release of bearer resources
- 37 - EPS QOS NOT ACCEPTED, this reason is posted by the network to indicate that the QoS requested by the UE could not be accepted
- 38 - NETWORK FAILURE, this reason is posted when an error occurs in the network
- 39 - UMTS REACTIVATION REQ, this reason is posted by the network to request for bearer reactivation. This code may be posted during network congestion
- 40 - FEATURE NOT SUPPORTED, Unsuccessful MBMS context activation requested by the network
- 41 - TFT SEMANTIC ERROR, the reason is posted by the network to indicate semantic error(s) in specifying TFT operation included in the request
- 42 - TFT SYNTAX ERROR, the reason is posted by the network to indicate syntactic error(s) in specifying TFT operation included in the request
- 43 - UNKNOWN PDP CONTEXT, the reason is posted when the bearer identity (or linked bearer identity) in the request is invalid (or inactive)
- 44 - FILTER SEMANTIC ERROR, the reason is posted by the network to indicate semantic error(s) in specifying packet filter(s) associated with a TFT
- 45 - FILTER SYNTAX ERROR, the reason is posted by the network to indicate syntactic error(s) in specifying packet filter(s) associated with a TFT

- 46 - PDP WITHOUT ACTIVE TFT, the reason is posted by the network when UW requested more than one PDP connection without TFT
- 50 - IPV4 ONLY ALLOWED, 3GPP equivalent ESM(EPS Session Management) cause code value 50, PDN type IPv4 only allowed.
- 51 - IPV6 ONLY ALLOWED, 3GPP equivalent ESM(EPS Session Management) cause code value 51, PDN type IPv6 only allowed
- 52 - SINGLE ADDRESS BEARER ONLY, 3GPP equivalent ESM(EPS Session Management) cause code value 52, Single address bearers only allowed. The reason is posted when the network supports single address bearers only, meaning dual IP bearers are not supported
- 53 - ESM INFORMATION NOT RECEIVED, 3GPP equivalent ESM(EPS Session Management) cause code value 53, ESM information not received. The reason is posted by the network to indicate that the PDN connection request was rejected because ESM information was not received
- 54 - PND CONNECTION DOES NOT EXIST, 3GPP equivalent ESM(EPS Session Management) cause code value 54, PDN connection does not exist The reason is posted by the network during handover from a non-3G-PP network to indicate that the MME does not have any information regarding the requested PDN connection
- 55 - MULTIPLE CONNECTION TO SAME PDN NOT ALLOWED, 3GPP equivalent ESM(EPS Session Management) cause code value 55, Multiple PDN connections for a given APN not allowed. The reason is posted by the network to indicate that the UE is already connected to the requested APN via another PDN/PDN connection
- 81 - INVALID TRANSACTION ID, the reason is posted by the network to indicate that the PTI used in the request is unassigned or reserved
- 95 - MESSAGE INCORRECT SEMANTIC, the reason is posted by the network to indicate receipt of an invalid message
- 96 - INVALID MANDATORY INFO, the reason is posted by the network to indicate receipt of a message with semantic error in a mandatory information element
- 97 - MESSAGE TYPE UNSUPPORTED, the reason is posted by the network to indicate receipt of a message that is either undefined or defined but not implemented by the equipment sending this ESM cause
- 98 - MSG TYPE NONCOMPATIBLE STATE, the reason is posted by the network to indicate receipt of a message type that cannot be handled in the current network protocol state
- 99 - UNKNOWN INFO ELEMENT, the reason is posted by the network to indicate receipt of a message that includes an information element that is either not defined or defined but not implemented by the equipment sending the ESM cause
- 100 - CONDITIONAL IE ERROR, the reason is posted by the network to indicate receipt of a message that includes a syntactically incorrect information element. This message is ignored by the network.
- 101 - MSG AND PROTOCOL STATE UNCOMPATIBLE, the reason is posted by the network to indicate receipt of a message that cannot be handled in the current network protocol state
- 111 - PROTOCOL ERROR, the reason is posted by the network to indicate a protocol error when no other error applies
- 112 - APN TYPE CONFLICT
- 113 - INVALID PROXY-CALL SESSION CONTROL FUNCTION ADDRESS

#### 9.30.2.10 PPP call end reasons (Type=7)

- 1 - TIMEOUT, this error code is returned when the data call bring up fails in PPP setup due to timeout (For e.g: LCP Conf Ack not received from network)
- 2 - AUTH FAILURE, this error code is returned when the data call bring up fails in PPP setup due to authentication failure
- 3 - OPTION MISMATCH, this error code is returned when the data call bring up fails in PPP setup due option mismatch (e.g: Authentication is required, but not negotiated with network during LCP phase)
- 31 - PAP FAILURE, this error code is returned when the data call bring up fails in PPP setup due to PAP failure
- 32 - CHAP FAILURE, this error code is returned when the data call bring up fails in PPP setup due to CHAP failure
- 33 - CLOSE IN PROGRESS, this error code is returned when the data call bring up fails in PPP setup since PPP is in the process of cleaning the previous PPP session
- -1 - UNKNOWN, this error code is unused

#### 9.30.2.11 EHRPD call end reasons (Type=8)

- 1 - SUBS LIMITED TO V4, this error code is returned when the V6 interface bring up fails because network provided only V4 address for the upcoming PDN
- 2 - SUBS LIMITED TO V6, this error code is returned when the V4 interface bring up fails because network provided only V6 address for the upcoming PDN
- 4 - VSNCP(Vendor Specific Network Control Protocol) TIMEOUT, this error code is returned when the data call bring up fails in VSNCP phase due to VSNCP timeout error
- 5 - VSNCP(Vendor Specific Network Control Protocol) FAILURE, this error code is returned when VSNCP configuration failed during call bring up
- 6 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I GEN ERROR, this error code is returned when the data call bring up fails in VSNCP phase due to general error
- 7 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I UNAUTH APN, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason requested APN is unauthorized
- 8 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I PDN LIMIT EXCEED, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason PDN limit exceeded
- 9 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I NO PDN GW, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason no PDN gateway
- 10 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I PDN GW UNREACH, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason PDN gateway unreachable
- 11 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I PDN GW REJ, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason PDN gateway reject
- 12 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I INSUFF PARAM, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason insufficient parameter

- 13 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I RESOURCE UNAVAIL, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason resource unavailable
- 14 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I ADMIN PROHIBIT, this error code is returned when the data call bring up fails in SNCP phase since network rejected VSNCP config request with reason admin prohibited
- 15 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I PDN ID IN USE, this error code is returned when the data call bring up fails in VSNCP phase because network rejected with reason PDN ID IN USE (or) All existing PDNs are brought down with this end reason because one of the PDN bring up got rejected by network with reason PDN ID IN USE
- 16 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I SUBSCR LIMITATION, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason subscriber limitation
- 17 - VSNCP(Vendor Specific Network Control Protocol) 3GPP2I PDN EXISTS FOR THIS APN, this error code is returned when the data call bring up fails in VSNCP phase since network rejected VSNCP config request with reason PDN exists for this APN

#### 9.30.2.12 IPV6 call end reasons (Type=9)

- 1 - PREFIX UNAVAILABLE, this error code is returned when V6 data call is brought down because device failed to get the prefix from network
- 2 - IPV6 ERR HRPD IPV6 DISABLED, this error code is returned when V6 data call bring up is rejected because IPV6 is disabled in 1X/HRPD mode
- 3 - IPV6 DISABLED, this error code is returned when IPv6 data call bring up is rejected because NV1896 (IPV6 enable) is disabled

Copyright: © 2011-2013 Sierra Wireless, Inc. all rights reserved

## 9.31 qaGobiApiTableCarrierCodes.h File Reference

Carrier Codes table.

### 9.31.1 Detailed Description

Carrier Codes table.

#### 9.31.2 Carrier Codes (Number - Carrier)

- 0 - no carrier specified
- 1 - Generic
- 2 - Telstra
- 4 - AT&T
- 5 - Verizon
- 11 - Sprint
- 12 - Telefonica

- 101 - Verizon
- 102 - Sprint
- 103 - Alltel
- 104 - Bell Mobility
- 105 - Telus
- 106 - U.S. Cellular
- 107 - Telstra
- 108 - China Unicom
- 109 - Telecom New Zealand
- 110 - SK Telecom
- 111 - Reliance Communications
- 112 - Tata Communications
- 113 - MetroPCS Communications
- 114 - Leap Wireless
- 115 - KDDI
- 116 - Grupo Iusacell
- 117 - China Telecom
- 118 - Open Mobile Handset
- 176 - Rogers
- 177 - NetIndex
- 178 - DNA
- 179 - Big Pond
- 201 - AT&T
- 202 - Vodafone
- 203 - T-Mobile
- 204 - Orange
- 205 - Telefonica
- 206 - Telecom Italia
- 207 - 3
- 208 - O2
- 209 - SFR
- 210 - Swisscom AG
- 211 - China Mobile
- 212 - Telstra
- 213 - Singapore Telecommunications
- 214 - Reliance Telecommunications

- 215 - Bharti Airtel
- 216 - NTT docomo
- 217 - E Mobile
- 218 - Softbank
- 219 - Korea Telecom Freetel
- 220 - SK Telecom
- 221 - Telenor
- 222 - NetCom Norway
- 223 - TeliaSonera
- 224 - América Móvil
- 225 - Brasil Vivo
- 0xFFFFFFFF - Unknown

Copyright: © 2011-2014 Sierra Wireless, Inc. all rights reserved

## 9.32 qaGobiApiTableCodingScheme.h File Reference

Data Coding Scheme.

### Macros

- `#define __GOBI_API_CODING_SCHEME_H__`

### 9.32.1 Detailed Description

Data Coding Scheme.

### 9.32.2 Call Control Result Reasons (Value - Name - Description)

#### 9.32.2.1 Use of bits 3..0

- Language using the GSM 7 bit default alphabet Bits 3..0 indicate the language:
  - 0000 German
  - 0001 English
  - 0010 Italian
  - 0011 French
  - 0100 Spanish
  - 0101 Dutch
  - 0110 Swedish
  - 0111 Danish
  - 1000 Portuguese
  - 1001 Finnish



1010 Norwegian  
1011 Greek  
1100 Turkish  
1101 Hungarian  
1110 Polish  
1111 Language unspecified

### 9.32.3 Coding Group Bits 7..4(0001)

#### 9.32.3.1 use of bits 3..0

- 0000 GSM 7 bit default alphabet; message preceded by language indication.  
The first 3 characters of the message are a two-character representation of the language encoded according to ISO 639 [12], followed by a CR character. The CR character is then followed by 90 characters of text.
- 0001 UCS2; message preceded by language indication  
The message starts with a two GSM 7-bit default alphabet character representation of the language encoded according to ISO 639. This is padded to the octet boundary with two bits set to 0 and then followed by 40 characters of UCS2-encoded message.  
An MS not supporting UCS2 coding will present the two character language identifier followed by improperly interpreted user data.

### 9.32.4 Coding Group Bits 7..4(0010)

#### 9.32.4.1 use of bits 3..0

- 0000 Czech  
0001 Hebrew  
0010 Arabic  
0011 Russian  
0100 Icelandic  
0101..1111 Reserved for other languages using the GSM 7 bit default alphabet, with unspecified handling at the MS

### 9.32.5 Coding Group Bits 7..4(0011)

#### 9.32.5.1 use of bits 3..0

- 0000..1111 Reserved for other languages using the GSM 7 bit default alphabet, with unspecified handling at the MS

### 9.32.6 Coding Group Bits 7..4(01xx)

#### 9.32.6.1 use of bits 3..0

- General Data Coding indication
  - Bits 5..0 indicate the following:
    - Bit 5, if set to 0, indicates the text is uncompressed
    - Bit 5, if set to 1, indicates the text is compressed using the compression algorithm defined in 3GPP TS 23.042
    - Bit 4, if set to 0, indicates that bits 1 to 0 are reserved and have no message class meaning
    - Bit 4, if set to 1, indicates that bits 1 to 0 have a message class meaning: Bit 1 Bit 0 Message Class:
      - 0 0 Class 0
      - 0 1 Class 1 Default meaning: ME-specific.
      - 1 0 Class 2 (U)SIM specific message.
      - 1 1 Class 3 Default meaning: TE-specific (see 3GPP TS 27.005 )
  - Bits 3 and 2 indicate the character set being used, as follows:
    - Bit 3 Bit 2 Character set:
      - 0 0 GSM 7 bit default alphabet 0 1 8 bit data
      - 1 0 UCS2 (16 bit) [10]
      - 1 1 Reserved

### 9.32.7 Coding Group Bits 7..4(1001)

#### 9.32.7.1 Reserved coding groups

- Message with User Data Header (UDH) structure:
  - Bit 1 Bit 0 Message Class:
    - 0 0 Class 0
    - 0 1 Class 1 Default meaning: ME-specific.
    - 1 0 Class 2 (U)SIM specific message.
    - 1 1 Class 3 Default meaning: TE-specific (see 3GPP TS 27.005 [8])
  - Bits 3 and 2 indicate the alphabet being used, as follows:
    - Bit 3 Bit 2 Alphabet:
      - 0 0 GSM 7 bit default alphabet
      - 0 1 8 bit data
      - 1 0 USC2 (16 bit) [10]
      - 1 1 Reserved

### 9.32.8 Coding Group Bits 7..4(1010..1101)

#### 9.32.8.1 Reserved coding groups

### 9.32.9 Coding Group Bits 7..4(1110)

#### 9.32.9.1 Defined by the WAP Forum

### 9.32.10 Coding Group Bits 7..4 (1111)

**9.32.10.1 Data coding / message handling**

- Bit 3 is reserved, set to 0.

Bit 2 Message coding:

0 GSM 7 bit default alphabet

1 8 bit data

Bit 1 Bit 0 Message Class:

0 0 No message class.

0 1 Class 1 user defined.

1 0 Class 2 user defined.

1 1 Class 3

default meaning: TE specific(3GPP TS 27.005)

Copyright: © 2012 Sierra Wireless, Inc. all rights reserved

**9.32.11 Macro Definition Documentation**

9.32.11.1 `#define __GOBI_API_CODING_SCHEME_H__`

**9.33 qaGobiApiTableGpsCapabilityCodes.h File Reference**

Position Determination Service API GPS Capability Codes.

**9.33.1 Detailed Description**

Position Determination Service API GPS Capability Codes.

**9.33.2 GPS capability (Value - Capability)**

- 0 - None
- 1 - Standalone
- 2 - Assisted (including XTRA and implying standalone is also supported)
- 3 - Assisted (without XTRA and implying standalone is also supported)
- 0xFFFFFFFF - Unknown

Copyright: © 2011 Sierra Wireless, Inc. all rights reserved

**9.34 qaGobiApiTablePowerModes.h File Reference**

Device Management Service API Power Modes table.

**9.34.1 Detailed Description**

Device Management Service API Power Modes table.

### 9.34.2 Power Modes (Value - Description)

- 0 - Online (default)
- 1 - Low power (airplane) mode
- 2 - Factory test mode
- 3 - Offline
- 4 - Reset
- 5 - Power off
- 6 - Persistent low power (airplane) mode
- 7 - Mode - only low power

Copyright: © 2011 Sierra Wireless, Inc. all rights reserved

## 9.35 qaGobiApiTableRadioInterfaces.h File Reference

Network Access Service API Radio Interfaces table.

### 9.35.1 Detailed Description

Network Access Service API Radio Interfaces table.

### 9.35.2 Radio interface

#### 9.35.2.1 Technology (Value - Radio Interface Technology)

- 0 - No service
- 1 - CDMA 1xRTT
- 2 - CDMA 1xEV-DO
- 3 - AMPS (Unsupported)
- 4 - GSM
- 5 - UMTS
- 6 - WLAN
- 7 - GPS
- 8 - LTE

Copyright: © 2011 Sierra Wireless, Inc. all rights reserved

## 9.36 qaGobiApiTableRegionCodes.h File Reference

Region Codes table.

### 9.36.1 Detailed Description

Region Codes table.

### 9.36.2 Region Codes (Code - Region)

- 0 - North America
- 1 - Latin America
- 2 - Europe
- 3 - Asia
- 4 - Australia
- 5 - Global
- 0xFFFFFFFF - Unknown

Copyright: © 2011 Sierra Wireless, Inc. all rights reserved

## 9.37 qaGobiApiTableServiceOptions.h File Reference

Voice Service Options.

### 9.37.1 Detailed Description

Voice Service Options.

### 9.37.2 Service Option codes (Code - Reason)

#### 9.37.2.1 Description

- 0x0001 - Basic variable rate voice service (8 kbps)
- 0x0002 - Mobile station loopback (8 kbps)
- 0x0003 - Enhanced variable rate voice service (8 kbps)
- 0x0004 - Asynchronous data service (9.6 kbps)
- 0x0005 - Group 3 facsimile (9.6 kbps)
- 0x0006 - Short message service (rate set 1)
- 0x0007 - Packet data service: Internet or ISO Protocol stack (9.6 kbps)
- 0x0008 - Packet data service: CDPD Protocol stack (9.6 kbps)
- 0x0009 - Mobile station loopback (13 kbps)
- 0x000A - transparent service
- 0x000B - III nontransparent service
- 0x000C - Asynchronous data service (14.4 or 9.6 kbps)
- 0x000D - Group 3 facsimile (14.4 or 9.6 kbps)

- 0x000E - Short message service (rate set 2)
- 0x000F - Packet data service: Internet or ISO Protocol stack (14.4 kbps)
- 0x0010 - Packet data service: CDPD Protocol stack (14.4 kbps)
- 0x0011 - High-rate voice service (13 kbps)
- 0x0012 - Over-the-air parameter administration (rate set 1)
- 0x0013 - Over-the-air parameter administration (rate set 2)
- 0x0014 - Group 3 analog facsimile (rate set 1)
- 0x0015 - Group 3 analog facsimile (rate set 2)
- 0x0016 - High-speed packet data service: Internet or ISO Protocol stack (RS1 forward, RS1 reverse)
- 0x0017 - High-speed packet data service: Internet or ISO Protocol stack (RS1 forward, RS2 reverse)
- 0x0018 - High-speed packet data service: Internet or ISO Protocol stack (RS2 forward, RS1 reverse)
- 0x0019 - High-speed packet data service: Internet or ISO Protocol stack (RS2 forward, RS2 reverse)
- 0x001A - High-speed packet data service: CDPD Protocol stack (RS1 forward, RS1 reverse)
- 0x001B - High-speed packet data service: CDPD Protocol stack (RS1 forward, RS2 reverse)
- 0x001C - High-speed packet data service: CDPD Protocol stack (RS2 forward, RS1 reverse)
- 0x001D - High-speed packet data service: CDPD Protocol stack (RS2 forward, RS2 reverse)
- 0x001E - RATE\_SET\_1 Supplemental channel loopback test for rate set 1
- 0x001F - RATE\_SET\_2 Supplemental channel loopback test for rate set 2
- 0x0020 - Test Data Service Option (TDSO)
- 0x0021 - cdma2000 high-speed packet data service, Internet or ISO Protocol stack
- 0x0022 - cdma2000 high-speed packet data service, CDPD Protocol
- 0x0023 - Location services, rate set 1 (9.6 kbps)
- 0x0024 - Location services, rate set 2 (14.4 kbps)
- 0x0025 - ISDN interworking service (64 kbps)
- 0x0026 - GSM voice
- 0x0027 - GSM circuit data
- 0x0028 - GSM packet data
- 0x0029 - GSM short message service
- 0x0036 - Markov Service Option (MSO)
- 0x0037 - Loopback Service Option (LSO)
- 0x0038 - Selectable mode vocoder
- 0x0039 - 32 kbps circuit video conferencing
- 0x003A - CONFERENCING 64 kbps circuit video conferencing
- 0x003B - HRPD packet data service, which when used in paging over the 1X air interface, a page response is not required
- 0x003C - Link Layer Assisted Robust Header Compression (LLA ROHC) - header removal

- 0x003D - LLA ROHC - Header Compression
- 0x003E - Source-controlled Variable-Rate Multimode Wideband (VMR-WB) speech codec rate set 2
- 0x003F - Source-controlled VMR-WB speech codec rate set 1
- 0x0040 - HRPD auxiliary packet data service instance
- 0x0041 - cdma2000/GPRS interworking
- 0x0042 - ISO\_PROTOCOL\_SO\_66 cdma2000 high-speed packet data service, Internet or ISO Protocol stack
- 0x0043 - HRPD packet data IP service where higher layer protocol is IP or ROHC
- 0x0044 - Enhanced variable rate voice service (EVRC-B)
- 0x0045 - HRPD packet data service, which when used in paging over the 1X air interface, a page response is required
- 0x0046 - Enhanced variable rate voice service (EVRC-WB)
- 0x1004 - Asynchronous data service, Revision 1 (9.6 or 14.4 kbps)
- 0x1005 - Group 3 facsimile, Revision 1 (9.6 or 14.4 kbps)
- 0x1007 - Packet data service: Internet or ISO Protocol stack, Revision 1 (9.6 or 14.4 kbps)
- 0x1008 - Packet data service: CDPD Protocol stack, Revision 1 (9.6 or 14.4 kbps)
- 0x7FF8 - Identifies service reference identifier 0
- 0x7FF9 - Identifies service reference identifier 1
- 0x7FFA - Identifies service reference identifier 2
- 0x7FFB - Identifies service reference identifier 3
- 0x7FFC - Identifies service reference identifier 4
- 0x7FFD - Identifies service reference identifier 5
- 0x7FFE - Identifies service reference identifier 6
- 0x7FFF - Identifies service reference identifier 7

Copyright: © 2012 Sierra Wireless, Inc. all rights reserved

## 9.38 qaGobiApiTableSupServiceInfoClasses.h File Reference

Voice Supplementary Service Information Classes.

### 9.38.1 Detailed Description

Voice Supplementary Service Information Classes.

### 9.38.2 Supplementary Service Information Classes (Value - Service Class)

- 0X00 - CLASS\_NONE
- 0X01 - CLASS\_VOICE
- 0X02 - CLASS\_DATA
- 0X04 - CLASS\_FAX
- 0X08 - CLASS\_SMS
- 0X10 - CLASS\_DATA\_CIRCUITSYNC
- 0X20 - CLASS\_DATA\_CIRCUITASYNC
- 0X40 - CLASS\_PACKETACCESS
- 0X80 - CLASS\_PADACCESS

Copyright: © 2012 Sierra Wireless, Inc. all rights reserved

## 9.39 qaGobiApiTableSwiAudio.h File Reference

Swi Audio related tables.

### 9.39.1 Detailed Description

Swi Audio related tables.

### 9.39.2 ACDB Device (Device ID - description)

- 0 - Vehicle HF
- 1 - Handset
- 2 - TTY
- 3 - USB
- 4 - NA

### 9.39.3 Physical Interface (Device ID - description - Interface parameters)

- 0 - PCM - Mode: 0-slave, 1-master, 2-Auxiliary PCM; Rate: 0-8k, 1-16k; Format: 0-linear, 1-u-law, 2-A-law; Padding: 0-disable, 1-enable; Bits-frame: 0-8BPF, 1-16BPF, 2-32BPF, 3-64BPF, 4-128BPF, 5-256BPF;
- 1 - I2S - None
- 2 - Analog(with internal codec) - None
- 3 - USB - None

Copyright: © 2013 Sierra Wireless, Inc. all rights reserved

## 9.40 qaGobiApiTableSwiOMADMUpdateCompleteStatus.h File Reference

Update Complete Status table.



### 9.40.1 Detailed Description

Update Complete Status table.

### 9.40.2 OMA DM Update Complete Status (Update Complete Status - Meaning - Usage)

- 200 - Successful - The request has succeeded
- 250-299 - Successful(vendor specified) - successful operation with vendor specified ResultCode
- 400 - Management Client Error - Management Client error - based on User or Device behavior
- 401 - User Cancelled - User chose not to accept the operation when prompted
- 402 - Corrupted Firmware Update Package - Corrupted firmware update package did not store correctly. Detected for example, by mismatch CRCs between actual and expected
- 403 - Firmware UpdatePackage( Device Mismatch ) - Wrong firmware update package delivered to device based on current device characteristics
- 404 - Failed Firmware Update Package Validation - Failure to positively validate digital signature of firmware update package
- 405 - Firmware Update Package Not acceptable - firmware update package is not acceptable
- 406 - Alternate Download Authentication Failure - authentication required but authentication failure was encountered when downloading firmware update package
- 407 - Alternate Download Request Timeout - client has encountered a timeout when downloading firmware update package
- 408 - Not Implemented - the device does not support the requested operation
- 409 - Undefined Error - indicates failure not defined by any other error code
- 410 - Firmware Update Failed - firmware update operation failed in device
- 411 - Malformed or Bad URL - the URL provided for alternate download is bad
- 412 - Alternate Download Server Unavailable - the alternate download server is unavailable or does not respond
- 450 - Client Error ( OMADM General ) - Vendor defined client error
- 451 - Client Error ( OMADM SyncML ) - Vendor defined client error
- 452 - Client Error ( OMADM Auth ) - Vendor defined client error
- 453 - Client Error ( OMADM Protocol )- Vendor defined client error
- 454 - Client Error ( OMADM Tree ) - Vendor defined client error
- 455 - Client Error ( OMADM DStore ) - Vendor defined client error
- 456 - Client Error ( OMADM Trigger ) - Vendor defined client error
- 457 - Client Error ( OMADM Fumo ) - Vendor defined client error
- 458 - Client Error ( OMADM Comms ) - Vendor defined client error
- 459 - Client Error ( OMADM Parse ) - Vendor defined client error
- 460 - Client Error ( OMADM TNDS ) - Vendor defined client error
- 461 - Client Error ( OMADM SCM ) - Vendor defined client error
- 462 - Client Error ( OMADM Impl ) - Vendor defined client error

- 463-499 - Client Error ( Vendor Specified ) - client error encountered for operation with vendor specified result code
- 500 - Alternate Download Server Error - Alternate download server error encountered
- 501 - Download fails due to device out of memory - The download fails due to insufficient memory in the device to save the firmware update package
- 502 - Firmware update fails due to device out of memory - The update fails because there isn't sufficient memory to update the device
- 503 - Download fails due to network issues - The download fails due to network/transport level errors
- 550-599 - Alternate Download Server Error (vendor specified)- Alternate download server error encountered for operation with vendor specified result code

Copyright: © 2013 Sierra Wireless, Inc. all rights reserved

## 9.41 qaGobiApiTableVoiceCallEndReasons.h File Reference

Voice Service Call and supplementary services end reasons.

### 9.41.1 Detailed Description

Voice Service Call and supplementary services end reasons.

### 9.41.2 Voice Call and supplementary services end reason codes (Code - Reason)

#### 9.41.2.1 General

- 0 - Phone is offline
- 20 - Phone is CDMA locked until a power cycle; CDMA only
- 21 - Phone has no service, this is for backward compatibility
- 22 - Call has ended abnormally; CDMA only
- 23 - Received intercept from the base station; originating only; CDMA only
- 24 - Received reorder from the base station; originating only; CDMA only
- 25 - Received release from the base station; no reason was given
- 26 - Received release from the base station; SO reject; CDMA only
- 27 - Received incoming call from the base station
- 28 - Received alert stop from the base station; incoming only; CDMA only
- 29 - Client ended the call
- 30 - Received end activation; OTASP call only; CDMA only
- 31 - MC aborted the origination/conversation; CDMA only
- 32 - Maximum access probes were transmitted; CDMA only
- 33 - Persistence test failure; FEATURE\_JCDMA only; CDMA only
- 34 - R-UIM is not present

- 35 - Access attempt is already in progress
- 36 - Access failure for a reason other than the above
- 37 - Received retry order; originating only; IS 2000; CDMA only
- 38 - BYBS Concurrent service is not supported by the base station
- 39 - No response was received from the base station
- 40 - Call was rejected by the base station; CDMA only
- 41 - Concurrent services requested were not compatible; CDMA only
- 42 - Access is blocked by the base station; CDMA only
- 43 - Corresponds to CM\_CALL\_ORIG\_ERR\_ALREADY\_IN\_TC
- 44 - Call is ended because an emergency call is flashed over this call; CDMA only
- 45 - Used if CM is ending a GPS call in preference of a user call
- 46 - Used if CM is ending an SMS call in preference of a user call
- 47 - Used if CM is ending a data call in preference of an emergency call
- 48 - Call was rejected because of a redirection or handoff
- 49 - Access is blocked by the base station for all mobiles; KDDI-specific; CDMA only
- 50 - To support OTASP SPC Error indication
- 51 - Maximum access probes for an IS-707B call; CDMA only
- 52 - Base station reject order
- 53 - Base station retry order
- 54 - Timer T42 is expired
- 55 - Timer T40 is expired
- 56 - Service initialization failure - Traffic Channel Initialization
- 57 - Timer T50m is expired - Traffic Channel Initialization
- 58 - Timer T51m is expired - Traffic Channel Initialization
- 59 - Acknowledgement timeout due to 12 retransmissions
- 60 - Bad forward link or timer T5M is expired
- 61 - Transceiver Resource Manager request failed
- 62 - Timer T41 is expired
- 100 - WCDMA/GSM/TDS only; call end LL cause, Received a reason for ending the call from the lower layer
- 101 - WCDMA/GSM only; Call origination request failed
- 102 - WCDMA/GSM only; client rejected an incoming call
- 103 - WCDMA/GSM only; client rejected a setup indication
- 104 - WCDMA/GSM only; network ended the call
- 105 - WCDMA/GSM only
- 106 - GWM/WCDMA only; phone has no service
- 107 - 1X only; phone has no service
- 108 - Full service is unavailable
- 109 - Indicates resources are not available to handle a new MO/MT PS call

#### 9.41.2.2 service Errors

- 110 - Unknown subscriber
- 111 - Illegal subscriber
- 112 - Bearer service not provisioned
- 113 - Tele service not provisioned
- 114 - Illegal equipment
- 115 - Call barred
- 116 - Illegal ss operation
- 117 - Ss error status
- 118 - Ss not available
- 119 - Ss subscription violation
- 120 - Ss incompatibility
- 121 - Facility not supported
- 122 - Absent subscriber
- 123 - Short term denial
- 124 - Long term denial
- 125 - System failure
- 126 - Data missing
- 127 - Unexpected data value
- 128 - Pwd registration failure
- 129 - Negative pwd check
- 130 - Num of pwd attempts violation
- 131 - Position method failure
- 132 - Unknown alphabet
- 133 - Ussd busy
- 134 - Rejected by user
- 135 - Rejected by network
- 136 - Deflection to served subscriber
- 137 - Special service code
- 138 - Invalid deflected to number
- 139 - Mpty participants exceeded
- 140 - Resources not available

## 9.41.2.3 control cause values

- 141 - Unassigned number
- 142 - No route to destination
- 143 - Channel unacceptable
- 144 - Operator determined barring
- 145 - Normal call clearing
- 146 - User busy sEE [s3, aNNEX h]
- 147 - No user responding sEE [s3, aNNEX h]
- 148 - User alerting no answer
- 149 - Call rejected sEE [s3, aNNEX h]
- 150 - Number changed sEE [s3, aNNEX h]
- 151 - Preemption sEE [s3, aNNEX h]
- 152 - Destination out of order
- 153 - Invalid number format
- 154 - Facility rejected
- 155 - Resp to status enquiry
- 156 - Normal unspecified
- 157 - No circuit or channel available
- 158 - Network out of order
- 159 - Temporary failure
- 160 - Switching equipment congestion
- 161 - Access information discarded
- 162 - Requested circuit or channel not available
- 163 - Resources unavailable or unspecified
- 164 - Qos unavailable
- 165 - Requested facility not subscribed
- 166 - Incoming calls barred within cug
- 167 - Bearer capability not auth
- 168 - Bearer capability unavailable
- 169 - Service option not available
- 170 - Acn limit exceeded
- 171 - Bearer service not implemented
- 172 - Requested facility not implemented
- 173 - Only digital information bearer available
- 174 - Service or option not implemented

- 175 - Invalid transaction identifier
- 176 - USER NOT MEMBER OF CUG
- 177 - Incompatible destination
- 178 - Invalid transit nw selection
- 179 - Semantically incorrect message
- 180 - Invalid mandatory information
- 181 - Message type non implemented
- 182 - Message type not compatible with protocol state
- 183 - Information element non existent
- 184 - Conditional ie error
- 185 - Message not compatible with protocol state
- 186 - Recovery on timer expired
- 187 - Protocol error unspecified
- 188 - Interworking unspecified
- 189 - Outgoing calls barred within cug
- 190 - No cug selection
- 191 - Unknown cug index
- 192 - Cug index incompatible
- 193 - Cug call failure unspecified
- 194 - Clir not subscribed
- 195 - Ccbs possible sEE
- 196 - Ccbs not possible

#### 9.41.2.4 reject causes

- 197 - Imsi unknown in hlr
- 198 - Illegal ms
- 199 - Imsi unknown in vlr
- 200 - Imei not accepted
- 201 - Illegal me sEE
- 202 - Plmn not allowed
- 203 - Location area not allowed
- 204 - Roaming not allowed in this location area
- 205 - No suitable cells in location area
- 206 - Network failure sEE
- 207 - mac failure sEE
- 208 - Synch failure

- 209 - Network congestion
- 210 - GSM authentication unacceptable
- 211 - Service not subscribed
- 212 - Service temporarily out of order
- 213 - Call cannot be identified
- 214 - Incorrect semantics in message
- 215 - Mandatory information invalid
- 216 - Call failed due to other access stratum failures
- 217 - SIM is invalid
- 218 - Invalid call state
- 219 - Access class is blocked
- 220 - No resources are in the protocol stack to allow the call
- 221 - Invalid user data was received

#### 9.41.2.5 reject causes

- 222 - Timer T3230 is expired
- 223 - No cell is available
- 224 - Abort message was received
- 225 - Radio link was lost due to other lower layer causes

#### 9.41.2.6 reject causes

- 226 - Timer T303 is expired
- 227 - CNM MM release is pending

#### 9.41.2.7 stratum reject causes

- 228 - Access stratum RR release indication
- 229 - Access stratum random access failure
- 230 - RRC\_REL\_IND Access stratum RRC release indication
- 231 - Access stratum close session indication
- 232 - Access stratum open session failure
- 233 - Access stratum low level failure
- 234 - Access stratum low level failure redial is not allowed
- 235 - Access stratum low level immediate retry
- 236 - Access stratum abort radio is unavailable

#### 9.41.2.8 reject causes

- 237 - Service option is not supported

#### 9.41.2.9 IP end reasons

- 300 - Received SIP 400 bad request;waiting for INVITE response
- 301 - Received SIP 400 bad request;waiting for INVITE response
- 302 - Received SIP 404 not found; call failed; called party does not exist
- 303 - Received SIP 415 unsupported media type; call failed; called party does not support media
- 304 - Received SIP 480 temporarily unavailable; call failed; called party is not in the LTE area
- 305 - No network response; call failed
- 306 - No network response; unable to put call on hold
- 307 - Moved to eHRPD; call failed or dropped; not in the LTE area
- 308 - Upgrade/downgrade rejected (200 OK with the current call SDP)
- 309 - Received 403 call forbidden; waiting for INVITE response
- 310 - Generic timeout; did not receive a response from the server or other end
- 311 - Reported on the MO side for generic internal software errors; user can try again if the call still exists
- 312 - Reported on the MT side if the upgrade timer has been cancelled or cannot complete the request for some reason after notifying the user of a re-invite request
- 313 - Call origination is rejected due to a Service-Specific Access Control (SSAC) barring
- 314 - Phone was put in thermal emergency
- 315 - 1XCSFB call ended because of a soft failure
- 316 - 1XCSFB call ended because of a hard failure

Copyright: © 2012 Sierra Wireless, Inc. all rights reserved

## 9.42 qaGobiApiTmd.h File Reference

Thermal Mitigation Device API function prototypes.

### Data Structures

- struct [mitigationDevList](#)
- struct [TmdGetMitigationDevListResp](#)
- struct [TmdGetMitigationLvlReq](#)
- struct [TmdGetMitigationLvlResp](#)
- struct [TmdRegNotMitigationLvlReq](#)
- struct [TmdDeRegNotMitigationLvlReq](#)
- struct [TmdMitigationLvlIndReq](#)



## Macros

- `#define MAX_MITIGATION_DEV_LIST_LEN 255`
- `#define MAX_MITIGATION_DEV_ID_LEN 255`

## Functions

- `ULONG SLQSTmdGetMitigationDevList (TmdGetMitigationDevListResp *pTmdGetMitigationDevListResp)`
- `ULONG SLQSTmdGetMitigationLvl (TmdGetMitigationLvlReq *pTmdGetMitigationLvlReq, TmdGetMitigationLvlResp *pTmdGetMitigationLvlResp)`
- `ULONG SLQSTmdRegNotMitigationLvl (TmdRegNotMitigationLvlReq *pTmdRegNotMitigationLvlReq)`
- `ULONG SLQSTmdDeRegNotMitigationLvl (TmdDeRegNotMitigationLvlReq *pTmdDeRegNotMitigationLvlReq)`

### 9.42.1 Detailed Description

Thermal Mitigation Device API function prototypes.

### 9.42.2 Macro Definition Documentation

9.42.2.1 `#define MAX_MITIGATION_DEV_ID_LEN 255`

9.42.2.2 `#define MAX_MITIGATION_DEV_LIST_LEN 255`

### 9.42.3 Function Documentation

9.42.3.1 `ULONG SLQSTmdDeRegNotMitigationLvl ( TmdDeRegNotMitigationLvlReq * pTmdDeRegNotMitigationLvlReq )`

Deregisters the notification for mitigation device level changes.

#### Parameters

<i>pTmdDeRegNotMitigationLvlReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">TmdDeRegNotMitigationLvlReq</a> for more information</li> </ul>
--	--

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.42.3.2 `ULONG SLQSTmdGetMitigationDevList ( TmdGetMitigationDevListResp * pTmdGetMitigationDevListResp )`

Used by the control point to gets the list of mitigation devices from the remote endpoint.

#### Parameters

<i>pTmdGetMitigationDevListResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">TmdGetMitigationDevListResp</a> for more information</li> </ul>
---	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.42.3.3 **ULONG** SLQSTmdGetMitigationLvl ( **TmdGetMitigationLvlReq** \* *pTmdGetMitigationLvlReq*, **TmdGetMitigationLvlResp** \* *pTmdGetMitigationLvlResp* )

Gets the thermal mitigation level for the mitigation device

**Parameters**

<i>pTmdGetMitigationLvlReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">TmdGetMitigationLvlReq</a> for more information</li> </ul>
<i>pTmdGetMitigationLvlResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">TmdGetMitigationLvlResp</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.42.3.4 **ULONG** SLQSTmdRegNotMitigationLvl ( **TmdRegNotMitigationLvlReq** \* *pTmdRegNotMitigationLvlReq* )

Registers for notification of mitigation device level changes.

**Parameters**

<i>pTmdRegNotMitigationLvlReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">TmdRegNotMitigationLvlReq</a> for more information</li> </ul>
--	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.43 qaGobiApiUim.h File Reference

Uim Service API function prototypes.

## Data Structures

- struct [UIMPowerDownReq](#)
- struct [fileInfo](#)
- struct [UIMRefreshEvent](#)
- struct [appStatus](#)
- struct [slotInfo](#)
- struct [cardStatus](#)
- struct [hotSwapStatus](#)
- struct [UIMGetCardStatusResp](#)
- struct [UIMSessionInformation](#)
- struct [setPINProtection](#)
- struct [UIMSetPinProtectionReq](#)
- struct [remainingRetries](#)
- struct [encryptedPIN1](#)
- struct [UIMPinResp](#)
- struct [verifyUIMPIN](#)
- struct [UIMVerifyPinReq](#)
- struct [changeUIMPIN](#)
- struct [UIMChangePinReq](#)
- struct [unblockUIMPIN](#)
- struct [UIMUnblockPinReq](#)
- struct [UIMEventRegisterReqResp](#)
- struct [UIMRefreshOKReq](#)
- struct [registerRefresh](#)
- struct [UIMRefreshRegisterReq](#)
- struct [UIMRefreshCompleteReq](#)
- struct [UIMRefreshGetLastEventResp](#)
- struct [UIMRefreshGetLastEventReq](#)
- struct [UIMGetFileAttributesReq](#)
- struct [cardResult](#)
- struct [fileAttributes](#)
- struct [UIMGetFileAttributesResp](#)
- struct [depersonalizationInformation](#)
- struct [UIMDepersonalizationReq](#)
- struct [UIMDepersonalizationResp](#)
- struct [authenticationData](#)
- struct [UIMAuthenticateReq](#)
- struct [authenticateResult](#)
- struct [UIMAuthenticateResp](#)
- struct [readResult](#)
- struct [readTransparentInfo](#)
- struct [UIMReadTransparentReq](#)
- struct [UIMReadTransparentResp](#)
- struct [UIMPowerUpReq](#)
- struct [UIMSlotStatus](#)
- struct [UIMSlotsStatus](#)
- struct [UIMGetSlotsStatusResp](#)
- struct [UIMSwitchSlotReq](#)
- struct [personalizationStatus](#)
- struct [UIMGetConfigurationReq](#)
- struct [UIMGetConfigurationResp](#)

## Macros

- `#define MAX_DESCRIPTION_LENGTH 255`
- `#define MAX_CONTENT_LENGTH 1024`
- `#define MAX_NO_OF_APPLICATIONS 10`
- `#define MAX_NO_OF_SLOTS 5`
- `#define MAX_PUK_LENGTH 8`
- `#define MAX_PATH_LENGTH 255`
- `#define MAX_ICCID_LENGTH 255`
- `#define MAX_SLOTS_STATUS 255`
- `#define MAX_ACTIVE_PERS_FEATURES 12`

## Functions

- `ULONG SLQSUIReset ()`
- `ULONG SLQSUIPowerDown (UIMPowerDownReq *pUIMPowerDownReq)`
- `ULONG SLQSUIGetCardStatus (UIMGetCardStatusResp *pUIMGetCardStatusResp)`
- `ULONG SLQSUISetPinProtection (UIMSetPinProtectionReq *pUIMSetPinProtectionReq, UIMPinResp *pUIMSetPinProtectionResp)`
- `ULONG SLQSUIVerifyPin (UIMVerifyPinReq *pUIMVerifyPinReq, UIMPinResp *pUIMVerifyPinResp)`
- `ULONG SLQSUIChangePin (UIMChangePinReq *pUIMChangePinReq, UIMPinResp *pUIMChangePinResp)`
- `ULONG SLQSUIUnblockPin (UIMUnblockPinReq *pUIMUnblockPinReq, UIMPinResp *pUIMUnblockPinResp)`
- `ULONG SLQSUIEventRegister (UIMEventRegisterReqResp *pUIMEventRegisterReqResp)`
- `ULONG SLQSUIRefreshOK (UIMRefreshOKReq *pUIMRefreshOKReq)`
- `ULONG SLQSUIRefreshRegister (UIMRefreshRegisterReq *pUIMRefreshRegisterReq)`
- `ULONG SLQSUIRefreshComplete (UIMRefreshCompleteReq *pUIMRefreshCompleteReq)`
- `ULONG SLQSUIRefreshGetLastEvent (UIMRefreshGetLastEventReq *pUIMRefreshGetLastEventReq, UIMRefreshGetLastEventResp *pUIMRefreshGetLastEventResp)`
- `ULONG SLQSUIGetFileAttributes (UIMGetFileAttributesReq *pUIMGetFileAttributesReq, UIMGetFileAttributesResp *pUIMGetFileAttributesResp)`
- `ULONG SLQSUIDepersonalization (UIMDepersonalizationReq *pUIMDepersonalizationReq, UIMDepersonalizationResp *pUIMDepersonalizationResp)`
- `ULONG SLQSUIAuthenticate (UIMAuthenticateReq *pUIMAuthenticateReq, UIMAuthenticateResp *pUIMAuthenticateResp)`
- `ULONG SLQSUIReadTransparent (UIMReadTransparentReq *pUIMReadTransparentReq, UIMReadTransparentResp *pUIMReadTransparentResp)`
- `ULONG SLQSUIPowerUp (UIMPowerUpReq *pUIMPowerUpReq)`
- `ULONG SLQSUIGetSlotsStatus (UIMGetSlotsStatusResp *pResp)`
- `ULONG SLQSUISwitchSlot (UIMSwitchSlotReq *pReq)`
- `ULONG SLQSUIGetConfiguration (UIMGetConfigurationReq *pUIMGetConfigurationReq, UIMGetConfigurationResp *pUIMGetConfigurationResp)`

### 9.43.1 Detailed Description

Uim Service API function prototypes.

### 9.43.2 Macro Definition Documentation

9.43.2.1 `#define MAX_ACTIVE_PERS_FEATURES 12`

9.43.2.2 `#define MAX_CONTENT_LENGTH 1024`

9.43.2.3 `#define MAX_DESCRIPTION_LENGTH 255`

9.43.2.4 `#define MAX_ICCID_LENGTH 255`

9.43.2.5 `#define MAX_NO_OF_APPLICATIONS 10`

9.43.2.6 `#define MAX_NO_OF_SLOTS 5`

9.43.2.7 `#define MAX_PATH_LENGTH 255`

9.43.2.8 `#define MAX_PUK_LENGTH 8`

9.43.2.9 `#define MAX_SLOTS_STATUS 255`

### 9.43.3 Function Documentation

9.43.3.1 **ULONG SLQSUIAuthenticate ( UIMAuthenticateReq \* *pUIMAuthenticateReq*, UIMAuthenticateResp \* *pUIMAuthenticateResp* )**

This API executes the authentication algorithm on the card.

#### Parameters

<i>pUIM-Authenticate-Req</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">UIMAuthenticateReq</a> for more information.</li> </ul>
<i>pUIM-Authenticate-Resp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">UIMAuthenticateResp</a> for more information.</li> </ul>

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

Timeout: 30 Secs

This API executes a security command on the card that depends on the card type.

The response contains the status code received from the card (SW1 and SW2) when the card responded to the read request.

The client can pass a token in the request to receive the result in a subsequent SLQSUIAuthenticateCallback

9.43.3.2 **ULONG SLQSUIChangePin ( UIMChangePinReq \* *pUIMChangePinReq*, UIMPinResp \* *pUIMChangePinResp* )**

This API changes the value of the specified PIN.

## Parameters

<i>pUIMChange-PinReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">UIMChangePinReq</a> for more information.</li> </ul>
<i>pUIMChange-PinResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">UIMPinResp</a> for more information.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API changes the value of the specified PIN.  
 The application must pass both the new and the old values of the PIN to complete the operation  
 The same PIN can be used by multiple sessions (i.e., the PIN is shared between GSM and RUIM in an ICC card).  
 The PIN is automatically set for all the sessions when the API is executed.  
 The client can pass a token in the request to receive the result in a subsequent SLQSUIMChangePinCallback.

#### 9.43.3.3 ULONG SLQSUIDepersonalization ( UIMDepersonalizationReq \* pUIMDepersonilizationReq, UIMDepersonalizationResp \* pUIMDepersonilizationResp )

This API de-activates or unblocks the personalization on the phone.

## Parameters

<i>pUIM-Depersonilization-Req</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">UIMDepersonalizationReq</a> for more information.</li> </ul>
<i>pUIM-Depersonilization-Resp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">UIMDepersonalizationResp</a> for more information.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API deactivates or unblocks the personalization on the phone.  
 Each feature can be deactivated/unblocked independently of the other features.

#### 9.43.3.4 ULONG SLQSUIMEventRegister ( UIIMEventRegisterReqResp \* *pUIIMEventRegisterReqResp* )

This API Registers for event notifications from the card.

## Parameters

<i>pUIMEventRegisterReqResp</i> [IN/OUT]	<ul style="list-style-type: none"> <li>See <a href="#">UIMEventRegisterReqResp</a> for more information.</li> </ul>
--	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This function registers for event notifications from the card. The client must verify the mask in the response to determine which events were registered successfully. Events not supported correctly are not registered. The client can deregister from all event notifications by passing "0x00000000" bitmask in the request.

#### 9.43.3.5 ULONG SLQSUIMGetCardStatus ( UIMGetCardStatusResp \* pUIMGetCardStatusResp )

This API retrieves the current status of the card.

## Parameters

<i>pUIMGetCardStatusResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">UIMGetCardStatusResp</a> for more information.</li> </ul>
------------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This function retrieves the current status of the card(activated) and the status of all applications available on the card. The function also returns support information for the hot-swap feature and the status of the switch used to detect a card removal/insertion.

Please use \ref SLQSUIMGetSlotsStatus to retrieves active and inactivate SIMs status.

#### 9.43.3.6 ULONG SLQSUIMGetConfiguration ( UIMGetConfigurationReq \* pUIMGetConfigurationReq, UIMGetConfigurationResp \* pUIMGetConfigurationResp )

This API Gets the modem configuration for the UIM module.



## Parameters

<i>pUIMGet-Configuration-Req[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMGetConfigurationReq</a> for more information.</li> </ul>
<i>pUIMGet-Configuration-Resp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMGetConfigurationResp</a> for more information.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

#### 9.43.3.7 ULONG SLQSUIMGetFileAttributes ( UIMGetFileAttributesReq \* pUIMGetFileAttributesReq, UIMGetFileAttributesResp \* pUIMGetFileAttributesResp )

This API retrieves the file attributes for any Elementary File(EF) or Dedicated File(DF) in the card and provides access by the path.

## Parameters

<i>pUIMGetFile-AttributesReq[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMGetFileAttributesReq</a> for more information.</li> </ul>
<i>pUIMGetFile-AttributesResp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMGetFileAttributesResp</a> for more information.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API retrieves the file attributes for any Elementary File(EF) or Dedicated File(DF) in the card and provides access by the path. The response contains the status code received from the card (SW1 and SW2) when the card responded to the select request. The client can pass a token in the request to receive the result in a subsequent SLQSUIMGetFileAttributesCallback.

#### 9.43.3.8 ULONG SLQSUIMGetSlotsStatus ( UIMGetSlotsStatusResp \* pResp )

This API Retrieves the current of the physical and logical slots.

## Parameters

<i>pResp[OUT]</i>	<ul style="list-style-type: none"><li>• See <a href="#">UIMGetSlotsStatusResp</a> for more information.</li></ul>
-------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

#### 9.43.3.9 ULONG SLQSUIMPowerDown ( UIMPowerDownReq \* pUIMPowerDownReq )

This API powers down the SIM card.

## Parameters

<i>pUIMPower-DownReq[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">UIMPowerDownReq</a> for more information.</li></ul>
------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This function powers down the card.  
This is usually performed when the phone is switched off or when it is set to Airplane mode.

#### 9.43.3.10 ULONG SLQSUIMPowerUp ( UIMPowerUpReq \* pUIMPowerUpReq )

This API powers up the SIM card.

## Parameters

<i>pUIMPowerUp-Req[IN]</i>	<ul style="list-style-type: none"><li>• See <a href="#">UIMPowerUpReq</a> for more information.</li></ul>
----------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 30 Secs

This function powers up the card.  
This is usually performed when the phone is switched off or when it is set to Airplane mode.

#### 9.43.3.11 **ULONG SLQSUIReadTransparent ( UIMReadTransparentReq \* pUIMReadTransparentReq, UIMReadTransparentResp \* pUIMReadTransparentResp )**

This API executes the Read Transparent algorithm on the card.

**Parameters**

<i>pUIMRead-Transparent-Req[IN]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMReadTransparentReq</a> for more information.</li> </ul>
<i>pUIMRead-Transparent-Resp[OUT]</i>	<ul style="list-style-type: none"> <li>• See <a href="#">UIMReadTransparentResp</a> for more information.</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 30 Secs

This API Provides read access to any transparent file in the card and provides access by the path.  
The response contains the status code received from the card (SW1 and SW2) when the card responded to the read request.  
The client can pass a token in the request to receive the result in a subsequent QMI\_UIM\_READ\_TRANSPARENT\_IND indication.

#### 9.43.3.12 **ULONG SLQSUIRefreshComplete ( UIMRefreshCompleteReq \* pUIMRefreshCompleteReq )**

This API invoked when the client has finished the Refresh procedure.

## Parameters

<i>pUIMRefreshCompleteReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">UIMRefreshCompleteReq</a> for more information.</li> </ul>
------------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This function is invoked when the client has finished the Refresh procedure (has reread all the cached files) and communicates this to the modem. This function enables the terminal response to be sent to the card

#### 9.43.3.13 ULONG SLQSUIRefreshGetLastEvent ( UIMRefreshGetLastEventReq \* pUIMRefreshGetLastEventReq, UIMRefreshGetLastEventResp \* pUIMRefreshGetLastEventResp )

This API provides the ability to retrieve the last refresh event.

## Parameters

<i>pUIMRefreshGetLastEventReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">UIMRefreshGetLastEventReq</a> for more information.</li> </ul>
<i>pUIMRefreshGetLastEventResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">UIMRefreshGetLastEventResp</a> for more information.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This function provides the ability to retrieve the last refresh event. The event information is usually passed in as an indication from the QMI to the application and is saved by the application at that time. If the event information is not saved, the client can retrieve the last refresh event.

Details regarding the Refresh procedure (i.e., the stages and actions that an application must complete) are described in document: 80-VM566-1 (NAA Refresh High Level Guide )

#### 9.43.3.14 ULONG SLQSUIRefreshOK ( UIMRefreshOKReq \* pUIMRefreshOKReq )

This API Enables the client to indicate whether it is OK to start the Refresh procedure.

## Parameters

<i>pUIMRefreshOKReq</i> [IN]	<ul style="list-style-type: none"> <li>Consist of parameters for SLQSUIMRefreshOK. Please see /ref <a href="#">UIMRefreshOKReq</a> for details.</li> </ul>
------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This function enables the client to indicate whether it is OK to start the Refresh procedure. This command is used only after a refresh event is received, which indicates the need to vote.

#### 9.43.3.15 ULONG SLQSUIMRefreshRegister ( UIMRefreshRegisterReq \* pUIMRefreshRegisterReq )

This API Registers for file change notifications triggered by the card.

## Parameters

<i>pUIMRefreshRegisterReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">UIMRefreshRegisterReq</a> for more information.</li> </ul>
------------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This function registers for file change notifications triggered by the card. The client can specify a list of files. The client is notified only when one of the files is modified by the Refresh procedure. This function can be invoked multiple times for each session type. If the function is invoked twice with the same session type, the new values overwrite the previous values. The client can also use this function to stop receiving indications of the refresh. This API should be invoked prior to the invocation of the SLQSUIMSetRefreshCallBack for the events to be registered.

#### 9.43.3.16 ULONG SLQSUIMReset ( )

This API resets the issuing control points state kept by the service.

## Parameters

<i>None</i>
-------------

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

The list of events to which the client is registered is emptied.  
The client must register again using the SLQSUIEventReg API to start receiving the events again. This would mean that the callback registrations would be reset after this API.

#### 9.43.3.17 ULONG SLQSUIMSetPinProtection ( UIMSetPinProtectionReq \* pUIMSetPinProtectionReq, UIMPinResp \* pUIMSetPinProtectionResp )

This API enables or disables the protection of the UIM contents by a specific PIN.

## Parameters

<i>pUIMSetPinProtectionReq</i> [I-N]	<ul style="list-style-type: none"> <li>See <a href="#">UIMSetPinProtectionReq</a> for more information.</li> </ul>
<i>pUIMSetPinProtectionResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">UIMPinResp</a> for more information.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API enables or disables the protection of UIM contents by a specific PIN.  
The same PIN can be used by multiple sessions (i.e., the PIN is shared between GSM and RUIM in an ICC card).  
The PIN is automatically set for all the sessions when the API is executed.  
The client can pass a token in the request to receive the result in a subsequent SLQSUIMSetPinProtectionCallback indication.

#### 9.43.3.18 ULONG SLQSUISSwitchSlot ( UIMSwitchSlotReq \* pReq )

This API Switches the binding between a logical slot and a physical slot.

## Parameters

<i>pReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">UIMSwitchSlotReq</a> for more information.</li> </ul>
------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

Please wait at least one second before this API call again.

#### 9.43.3.19 ULONG SLQSUIUnblockPin ( UIMUnblockPinReq \* *pUIMUnblockPinReq*, UIMPinResp \* *pUIMUnblockPinResp* )

This API unblocks a blocked PIN using the PUK code.

## Parameters

<i>pUIMUnblock-PinReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">UIMUnblockPinReq</a> for more information.</li> </ul>
<i>pUIMUnblock-PinResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">UIMPinResp</a> for more information.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API unblocks a blocked PIN using the PUK code.  
 The client must pass PUK1 to unblock PIN1 or PUK2 to unblock PIN2.  
 The same PIN can be used by multiple sessions (i.e., the PIN is shared between GSM and RUIM in an ICC card).  
 The PIN is automatically set for all the sessions when the API is executed.  
 The client can pass a token in the request to receive the result in a subsequent SLQSUIUnblockPinCallback.

#### 9.43.3.20 ULONG SLQSUIVerifyPin ( UIMVerifyPinReq \* *pUIMVerifyPinReq*, UIMPinResp \* *pUIMVerifyPinResp* )

This API verifies the PIN before the card content is accessed.

## Parameters

<i>pUIMVerifyPinReq</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">UIMVerifyPinReq</a> for more information.</li> </ul>
<i>pUIMVerifyPinResp</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">UIMPinResp</a> for more information.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API verifies the PIN before the card content is accessed. The same PIN can be used by multiple sessions (i.e., the PIN is shared between GSM and RUIM in an ICC card). The PIN is automatically set for all the sessions when the API is executed. The client can pass a token in the request to receive the result in a subsequent SLQSUIMVerifyPinCallback.

## 9.44 qaGobiApiVoice.h File Reference

Voice Service API function prototypes.

### Data Structures

- struct [USSInfo](#)
- struct [UUSInfo](#)
- struct [CUGInfo](#)
- struct [calledPartySubAdd](#)
- struct [voiceCallRequestParams](#)
- struct [alphaIDInfo](#)
- struct [ccSUPSType](#)
- struct [voiceCallResponseParams](#)
- struct [callFwdTypeAndPlan](#)
- struct [voiceSetSUPSServiceReq](#)
- struct [voiceSetSUPSServiceResp](#)
- struct [airTimer](#)
- struct [roamTimer](#)
- struct [prefVoiceSO](#)
- struct [voiceSetConfigReq](#)
- struct [voiceSetConfigResp](#)
- struct [voiceAnswerCall](#)
- struct [CLIRResp](#)
- struct [voiceGetCLIRResp](#)
- struct [CLIPResp](#)



- struct [voiceGetCLIPResp](#)
- struct [voiceGetCallWaitInfo](#)
- struct [voiceGetCallBarringReq](#)
- struct [voiceGetCallBarringResp](#)
- struct [voiceGetCallFWReq](#)
- struct [callFWInfo](#)
- struct [callFWExtInfo](#)
- struct [getCallFWInfo](#)
- struct [getCallFWExtInfo](#)
- struct [voiceGetCallFWResp](#)
- struct [voiceSetCallBarringPwdInfo](#)
- struct [voiceSetCallBarringPwdResp](#)
- struct [callInfo](#)
- struct [remotePartyNum](#)
- struct [remotePartyName](#)
- struct [connectNumInfo](#)
- struct [diagInfo](#)
- struct [voiceCallInfoReq](#)
- struct [voiceCallInfoResp](#)
- struct [getAllCallInformation](#)
- struct [getAllCallRmtPtyNum](#)
- struct [getAllCallRmtPtyName](#)
- struct [allCallsUUSInfo](#)
- struct [allCallsAlphaIDInfo](#)
- struct [allCallsDiagInfo](#)
- struct [peerNumberInfo](#)
- struct [arrCallInfo](#)
- struct [arrRemotePartyNum](#)
- struct [arrRemotePartyName](#)
- struct [arrAlertingType](#)
- struct [arrUUSInfo](#)
- struct [arrSvcOption](#)
- struct [arrCallEndReason](#)
- struct [arrAlphaID](#)
- struct [arrConnectPartyNum](#)
- struct [arrDiagInfo](#)
- struct [arrCalledPartyNum](#)
- struct [arrRedirPartyNum](#)
- struct [arrAlertingPattern](#)
- struct [voiceGetAllCallInfo](#)
- struct [voiceManageCallsReq](#)
- struct [voiceManageCallsResp](#)
- struct [burstDTMFInfo](#)
- struct [DTMFLengths](#)
- struct [voiceBurstDTMFInfo](#)
- struct [voiceContDTMFInfo](#)
- struct [voiceStopContDTMFInfo](#)
- struct [voiceFlashInfo](#)
- struct [voiceSetPrefPrivacy](#)
- struct [voiceIndicationRegisterInfo](#)
- struct [DTMFInfo](#)
- struct [SUPSInfo](#)
- struct [newPwdData](#)
- struct [COLPResp](#)
- struct [COLRResp](#)

- struct [CNAPResp](#)
- struct [voiceGetConfigReq](#)
- struct [curAMRConfig](#)
- struct [voiceGetConfigResp](#)
- struct [voiceOrigUSSDNoWaitInfo](#)
- struct [voiceBindSubscriptionInfo](#)
- struct [voiceALSSetLineSwitchInfo](#)
- struct [voiceALSSelectLineInfo](#)
- struct [voiceGetCOLPResp](#)
- struct [voiceGetCOLRResp](#)
- struct [voiceGetCNAPResp](#)
- struct [USSResp](#)
- struct [USSDRespFNetwork](#)

## Macros

- #define [MAXUSSDLENGTH](#) 182
- #define [MAX\\_CALL\\_NO\\_LEN](#) 81
- #define [MAX\\_DESCRIPTION\\_LENGTH](#) 255
- #define [PASSWORD\\_LENGTH](#) 4
- #define [MAX\\_NO\\_OF\\_CALLS](#) 20

## Enumerations

- enum [serviceClassInformation](#) {  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_NONE](#) = 0x00,  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_VOICE](#) = 0x01,  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_DATA](#) = 0x02,  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_FAX](#) = 0x04,  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_SMS](#) = 0x08,  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_DATACIRCUITSYNC](#) = 0x10,  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_DATACIRCUITASYNC](#) = 0x20,  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_PACKETACCESS](#) = 0x40,  
[VOICE\\_SUPS\\_SRV\\_CLASS\\_PADACCESS](#) = 0x80 }

## Functions

- [ULONG OriginateUSSD](#) ([BYTE \\*pInfo](#))
- [ULONG AnswerUSSD](#) ([BYTE \\*pInfo](#))
- [ULONG CancelUSSD](#) ()
- [ULONG SLQSVoiceDialCall](#) ([voiceCallRequestParams \\*pCallRequestParams](#), [voiceCallResponseParams \\*pCallResponseParams](#))
- [ULONG SLQSVoiceEndCall](#) ([BYTE \\*pCallId](#))
- [ULONG SLQSVoiceSetSUPSService](#) ([voiceSetSUPSServiceReq \\*pVoiceSetSUPSServiceReq](#), [voiceSetSUPSServiceResp \\*pVoiceSetSUPSServiceResp](#))
- [ULONG SLQSVoiceSetConfig](#) ([voiceSetConfigReq \\*pVoiceSetConfigReq](#), [voiceSetConfigResp \\*pVoiceSetConfigResp](#))
- [ULONG SLQSVoiceAnswerCall](#) ([voiceAnswerCall \\*pVoiceAnswerCall](#))
- [ULONG SLQSVoiceGetCLIR](#) ([voiceGetCLIRResp \\*pVoiceGetCLIRResp](#))
- [ULONG SLQSVoiceGetCLIP](#) ([voiceGetCLIPResp \\*pVoiceGetCLIPResp](#))
- [ULONG SLQSVoiceGetCallWaiting](#) ([voiceGetCallWaitInfo \\*pVoiceGetCallWaitInfo](#))
- [ULONG SLQSVoiceGetCallBarring](#) ([voiceGetCallBarringReq \\*pVoiceGetCallBarringReq](#), [voiceGetCallBarringResp \\*pVoiceGetCallBarringResp](#))

- [ULONG SLQSVoiceGetCallForwardingStatus](#) ([voiceGetCallFWReq](#) \*pVoiceGetCallFWReq, [voiceGetCallFWResp](#) \*pVoiceGetCallFWResp)
- [ULONG SLQSVoiceSetCallBarringPassword](#) ([voiceSetCallBarringPwdInfo](#) \*pVoiceSetCallBarringPwdInfo, [voiceSetCallBarringPwdResp](#) \*pSetCallBarringPwdResp)
- [ULONG SLQSVoiceGetCallInfo](#) ([voiceCallInfoReq](#) \*pGetCallInfoReq, [voiceCallInfoResp](#) \*pGetCallInfoResp)
- [ULONG SLQSVoiceGetAllCallInfo](#) ([voiceGetAllCallInfo](#) \*pGetAllCallInfo)
- [ULONG SLQSVoiceManageCalls](#) ([voiceManageCallsReq](#) \*pVoiceManageCallsReq, [voiceManageCallsResp](#) \*pVoiceManageCallsResp)
- [ULONG SLQSVoiceBurstDTMF](#) ([voiceBurstDTMFInfo](#) \*pBurstDTMFInfo)
- [ULONG SLQSVoiceStartContDTMF](#) ([voiceContDTMFInfo](#) \*pContDTMFInfo)
- [ULONG SLQSVoiceStopContDTMF](#) ([voiceStopContDTMFInfo](#) \*pVoiceStopContDTMFInfo)
- [ULONG SLQSVoiceSendFlash](#) ([voiceFlashInfo](#) \*pFlashInfo)
- [ULONG SLQSVoiceSetPreferredPrivacy](#) ([voiceSetPrefPrivacy](#) \*pSetPrefPrivacy)
- [ULONG SLQSVoiceIndicationRegister](#) ([voiceIndicationRegisterInfo](#) \*pVoiceIndicationRegisterInfo)
- [ULONG SLQSVoiceGetConfig](#) ([voiceGetConfigReq](#) \*pVoiceGetConfigReq, [voiceGetConfigResp](#) \*pVoiceGetConfigResp)
- [ULONG SLQSVoiceOrigUSSDNoWait](#) ([voiceOrigUSSDNoWaitInfo](#) \*pVoiceOrigUSSDNoWaitInfo)
- [ULONG SLQSVoiceBindSubscription](#) ([voiceBindSubscriptionInfo](#) \*pVoiceBindSubscriptionInfo)
- [ULONG SLQSVoiceALSSetLineSwitching](#) ([voiceALSSetLineSwitchInfo](#) \*pVoiceALSSetLineSwitchInfo)
- [ULONG SLQSVoiceALSSelectLine](#) ([voiceALSSelectLineInfo](#) \*pVoiceALSSelectLineInfo)
- [ULONG SLQSVoiceGetCOLP](#) ([voiceGetCOLPResp](#) \*pVoiceGetCOLPResp)
- [ULONG SLQSVoiceGetCOLR](#) ([voiceGetCOLRResp](#) \*pVoiceGetCOLRResp)
- [ULONG SLQSVoiceGetCNAP](#) ([voiceGetCNAPResp](#) \*pVoiceGetCNAPResp)
- [ULONG SLQSOriinateUSSD](#) (struct [USSInfo](#) \*pReq, struct [USSResp](#) \*pResp)

#### 9.44.1 Detailed Description

Voice Service API function prototypes.

#### 9.44.2 Macro Definition Documentation

9.44.2.1 `#define MAX_CALL_NO_LEN 81`

9.44.2.2 `#define MAX_DESCRIPTION_LENGTH 255`

9.44.2.3 `#define MAX_NO_OF_CALLS 20`

9.44.2.4 `#define MAXUSSDLENGTH 182`

9.44.2.5 `#define PASSWORD_LENGTH 4`

#### 9.44.3 Enumeration Type Documentation

9.44.3.1 `enum serviceClassInformation`

Service Class information

Enumerator

```
VOICE_SUPS_SRV_CLASS_NONE
VOICE_SUPS_SRV_CLASS_VOICE
VOICE_SUPS_SRV_CLASS_DATA
VOICE_SUPS_SRV_CLASS_FAX
VOICE_SUPS_SRV_CLASS_SMS
```

**VOICE\_SUPS\_SRV\_CLASS\_DATA\_CIRCUITSYNC**  
**VOICE\_SUPS\_SRV\_CLASS\_DATA\_CIRCUITASYNC**  
**VOICE\_SUPS\_SRV\_CLASS\_PACKETACCESS**  
**VOICE\_SUPS\_SRV\_CLASS\_PADACCESS**

#### 9.44.4 Function Documentation

##### 9.44.4.1 **ULONG** AnswerUSSD ( **BYTE** \* *pInfo* )

Responds to a USSD request from the network.

###### Parameters

<i>pInfo</i> [IN]	<ul style="list-style-type: none"><li>• USS information</li></ul>
-------------------	---

###### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

###### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

###### Note

Technology Supported: UMTS  
Timeout: 5 mins

##### 9.44.4.2 **ULONG** CancelUSSD ( )

Cancels an in-progress USSD operation.

###### Parameters

<i>None</i>
-------------

###### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

###### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

###### Note

Technology Supported: UMTS  
Timeout: 30 Secs

##### 9.44.4.3 **ULONG** OriginateUSSD ( **BYTE** \* *pInfo* )

Initiates a USSD operation.

## Parameters

<i>pInfo</i> [IN]	<ul style="list-style-type: none"><li>• USS information</li><li>• See <a href="#">USSInfo</a> for more details</li></ul>
-------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Timeout: 5 mins

**9.44.4.4 ULONG SLQSOriinateUSSD ( struct USSInfo \* *pReq*, struct USSResp \* *pResp* )**

Initiates a USSD session.

## Parameters

<i>pReq</i> [IN]	<ul style="list-style-type: none"><li>• USS information</li><li>• See <a href="#">USSInfo</a> for more details</li></ul>
<i>pResp</i> [OUT]	<ul style="list-style-type: none"><li>• USS information</li></ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Device Supported: MC83x5  
Timeout: 5 mins

**9.44.4.5 ULONG SLQSVoiceALSSelectLine ( voiceALSSelectLineInfo \* *pVoiceALSSelectLineInfo* )**

This API allows the user to select the preferred line.

## Parameters

<i>pVoiceALS-SelectLineInfo</i> [1-N]	<ul style="list-style-type: none"> <li>See <a href="#">voiceALSSelectLineInfo</a> for more information.</li> </ul>
---------------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS

Timeout: 30 Secs

This API allows the user to select the preferred line, and the status is updated on the card. The API is supported only for specific SIM/USIMs that support alternate line service. This command is applicable only in 3GPP devices. A No Effect error is returned if the update on the card fails.

#### 9.44.4.6 ULONG SLQSVoiceALSSetLineSwitching ( voiceALSSetLineSwitchInfo \* *pVoiceALSSetLineSwitchInfo* )

This API sets the line switch setting on the card.

## Parameters

<i>pVoiceALSSetLineSwitchInfo</i> [1-N]	<ul style="list-style-type: none"> <li>See <a href="#">voiceALSSetLineSwitchInfo</a> for more information.</li> </ul>
---	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS

Timeout: 30 Secs

This API sets a line to be switchable or unswitchable, and the switch status is updated on the card. The API is supported only for specific SIM/USIMs that support alternate line service. This command is applicable only in 3GPP devices. A No Effect error is returned if the update on the card fails.

#### 9.44.4.7 ULONG SLQSVoiceAnswerCall ( voiceAnswerCall \* *pVoiceAnswerCall* )

Answers an incoming voice call.

## Parameters

<i>pVoiceAnswer-Call</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceAnswerCall</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceAnswerCall</a> for more information</li> </ul> </li> </ul>
-----------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 10 Secs

This API is used to answer an incoming voice call when the incoming voice call is the only call present at that time. If there are other calls while an incoming call (waiting call) is received, API "SLQSVoiceSendFlash" can be used case of 3GPP2(CDMA) and API "SLQSVoiceManageCalls" in the case of 3GPP(UMTS). If the result indicates success, the device has started the requested operation and it does not mean that the call has been answered. "SLQSVoiceSetAllCallStatusCallback" can be subscribed to check the call Information/State.

#### 9.44.4.8 ULONG SLQSVoiceBindSubscription ( voiceBindSubscriptionInfo \* pVoiceBindSubscriptionInfo )

This API binds a subscription type to a specific voice client ID.

## Parameters

<i>pVoiceBind-Subscription-Info</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">voiceBindSubscriptionInfo</a> for more information.</li> </ul>
--	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

Some versions of the modem support the Dual SIM feature. With this feature the modem can register with two different cellular networks simultaneously. Each network registration is associated with a different subscription, e.g., phone number, such that the modem appears to the network to be two different users. By default, the Voice client is bound to the primary subscription. This command allows the Voice client to change this binding. After receiving a successful response to this command, all future commands sent by the client will affect the newly bound subscription only.

#### 9.44.4.9 ULONG SLQSVoiceBurstDTMF ( voiceBurstDTMFInfo \* pBurstDTMFInfo )

Sends a burst Dual-Tone Multi frequency (DTMF) (applicable only for 3GPP2)

## Parameters

<i>pBurstDTMF-Info</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Structure containing parameters of burst DTMF.</li> <li>• See <a href="#">voiceBurstDTMFInfo</a> for more information</li> </ul>
---------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA

Timeout: 30 Secs

Applicable only for 3GPP2. This API sends a burst DTMF. If API result indicates success, this means the device has started the requested operation. It does not mean that the burst DTMF request has been sent to the network. A burst DTMF request is sent to the current active/alerting call when CallId is set to 0xFF. This API is applicable only in 3GPP2.

#### 9.44.4.10 ULONG SLQSVoiceDialCall ( voiceCallRequestParams \* pCallRequestParams, voiceCallResponseParams \* pCallResponseParams )

Originates a voice call (MO call).

## Parameters

<i>pCallRequest-Params</i> [IN]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceCallRequestParams</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceCallRequestParams</a> for more information</li> </ul> </li> </ul>
<i>pCallResponse-Params</i> [OUT]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceCallResponseParams</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceCallResponseParams</a> for more information</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API originates a voice call (MO). If the function returns success with a call\_id, the device has started the requested operation. It does not mean that the call has been connected. SLQSVoiceSetAllCallStatus-Callback() callback can be subscribed to learn if the call was successful.



#### 9.44.4.11 ULONG SLQSVoiceEndCall ( BYTE \* *pCallId* )

This message ends a voice call

## Parameters

<i>pCallId</i>	[IN/OUT] <ul style="list-style-type: none"> <li>Unique call identifier for the call that must be ended</li> </ul>
----------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

If the function returns success, the device has started the requested operation. It does not mean that the call has been ended. The application should always process the SLQSVoiceSetAllCallStatusCallback() callback to learn if the call was ended.

#### 9.44.4.12 ULONG SLQSVoiceGetAllCallInfo ( voiceGetAllCallInfo \* pGetAllCallInfo )

This API queries the information associated with all the calls originating or terminating from a particular device.

## Parameters

<i>pGetAllCallInfo</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">voiceGetAllCallInfo</a> for more information.</li> </ul>
------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This command is used by the control point to get information of all the calls to and fro from the device in progress. The information keeps on updating constantly, as the state of a call changes example, from incoming to conversation to terminated.

This API requires a firmware with at least voice 2.0 support.

#### 9.44.4.13 ULONG SLQSVoiceGetCallBarring ( voiceGetCallBarringReq \* pVoiceGetCallBarringReq, voiceGetCallBarringResp \* pVoiceGetCallBarringResp )

Queries the status of Call Barring Supplementary Service (applicable only for 3GPP).

## Parameters

<i>pVoiceGetCallBarringReq</i> [IN]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCallBarringReq</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCallBarringReq</a> for more information</li> </ul> </li> </ul>
<i>pVoiceGetCallBarringResp</i> [OUT]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCallBarringResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCallBarringResp</a> for more information</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS

Timeout: 30 Secs

This API queries the status of the call barring supplementary service, i.e., to find whether the call barring supplementary service is active and, if active, for which service classes it is active. The request is a blocking request, i.e., the response is sent only after confirmation is received from the network. The maximum time it takes for the response to be sent is approximately 30 sec. This API is applicable only in 3GPP devices.

#### 9.44.4.14 ULONG SLQSVoiceGetCallForwardingStatus ( voiceGetCallFWReq \* pVoiceGetCallFWReq, voiceGetCallFWResp \* pVoiceGetCallFWResp )

Queries the status of Call Forwarding Supplementary Service.

## Parameters

<i>pVoiceGetCallFWReq</i> [IN]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCallFWReq</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCallFWReq</a> for more information</li> </ul> </li> </ul>
<i>pVoiceGetCallFWResp</i> [OUT]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCallFWResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCallFWResp</a> for more information</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS

Timeout: 30 Secs

This API queries the status of the call forwarding supplementary service, i.e., to find whether the call forwarding supplementary service is active and, if active, for which service classes and call forwarding number it is active. The request is a blocking request, i.e., the response is sent only after confirmation is received from the network. The maximum time it takes for the response to be sent is approximately 30 sec. This API is applicable only in 3GPP devices.

**9.44.4.15** `ULONG SLQSVoiceGetCallInfo ( voiceCallInfoReq * pGetCallInfoReq, voiceCallInfoResp * pGetCallInfoResp )`

This API queries the information associated with a call and gives information about a particular call whose call Id is sent in as request.

**Parameters**

<i>pGetCallInfo-Req[IN]</i>	<ul style="list-style-type: none"> <li>See <a href="#">voiceCallInfoReq</a> for more information.</li> </ul>
<i>pGetCallInfo-Resp[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">voiceCallInfoResp</a> for more information.</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 30 Secs

If no voice call is in progress or an invalid call\_id is sent in the request, an error is returned as the response.

This API requires a firmware with atleast voice 2.0 support.

**9.44.4.16** `ULONG SLQSVoiceGetCallWaiting ( voiceGetCallWaitInfo * pVoiceGetCallWaitInfo )`

Queries the status of Call Waiting Supplementary Service (applicable only for 3GPP).

**Parameters**

<i>pVoiceGetCall-WaitInfo[IN/OUT]</i>	<ul style="list-style-type: none"> <li>Pointer to structure of <a href="#">voiceGetCallWaitInfo</a> <ul style="list-style-type: none"> <li>See <a href="#">voiceGetCallWaitInfo</a> for more information</li> </ul> </li> </ul>
---------------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS

Timeout: 30 Secs

This API queries the status of the call waiting supplementary service, i.e., to find whether the call waiting supplementary service is active. The request is a blocking request, i.e., the response is sent only after confirmation is received from the network. The maximum time it takes for the response to be sent is approximately 30 sec. This API is applicable only in 3GPP devices.

#### 9.44.4.17 ULONG SLQSVoiceGetCLIP ( voiceGetCLIPResp \* pVoiceGetCLIPResp )

Queries the status of the Calling Line Identification Presentation (CLIP) supplementary service (applicable only for 3GPP).

## Parameters

<i>pVoiceGetCLIP-Resp[OUT]</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCLIPResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCLIPResp</a> for more information</li> </ul> </li> </ul>
--------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS

Timeout: 30 Secs

This API queries the status of the CLIP supplementary service. The active\_status field is only applicable when provision\_status is PROVISIONED, i.e., there is not any case where provision\_status is NOT\_PROVISIONED and active\_status is ACTIVE. The request is a blocking request, i.e., the response is sent only after confirmation is received from the network. The maximum time it takes for the response to be sent is approximately 30 sec. This API is applicable only in 3GPP devices.

#### 9.44.4.18 ULONG SLQSVoiceGetCLIR ( voiceGetCLIRResp \* pVoiceGetCLIRResp )

Queries the status of the Calling Line Identification Restriction (CLIR) supplementary service (applicable only for 3GPP).

## Parameters

<i>pVoiceGetCLIR-Resp[OUT]</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCLIRResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCLIRResp</a> for more information</li> </ul> </li> </ul>
--------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS

Timeout: 30 Secs

This API queries the status of the CLIR supplementary service. The active\_status field is only applicable when provision\_status is PROVISIONED, i.e., there is not any case where provision\_status is NOT\_PROVISIONED and active\_status is ACTIVE. The request is a blocking request, i.e., the response is sent only after confirmation is received from the network. The maximum time it takes for the response to be sent is approximately 30 sec. This API is applicable only in 3GPP devices.

**9.44.4.19 ULONG SLQSVoiceGetCNAP ( voiceGetCNAPResp \* pVoiceGetCNAPResp )**

Queries the status of the Calling Name Presentation(CNAP) supplementary service (applicable only for 3GPP).

**Parameters**

<i>pVoiceGetCNAPResp[OUT]</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCNAPResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCNAPResp</a> for more information</li> </ul> </li> </ul>
-------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS

Timeout: 30 Secs

This API queries the status of the CNAP supplementary service. A response indicates whether CNAP is active/inactive and provisioned/not provisioned in the network. The active\_status field is only applicable when provision\_status is PROVISIONED, i.e., there is not any case where provision\_status is NOT\_PROVISIONED and active\_status is ACTIVE. This API is applicable only in 3GPP devices.

**9.44.4.20 ULONG SLQSVoiceGetCOLP ( voiceGetCOLPResp \* pVoiceGetCOLPResp )**

Queries the status of the Connected Line Identification Presentation (COLP) supplementary service (applicable only for 3GPP).

## Parameters

<i>pVoiceGetCOL- PResp[OUT]</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCOLPResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCOLPResp</a> for more information</li> </ul> </li> </ul>
-------------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Timeout: 30 Secs

This API queries the status of the COLP supplementary service. A response indicates whether COLP is active/inactive and provisioned/not provisioned in the network. The active\_status field is only applicable when provision\_status is PROVISIONED, i.e., there is not any case where provision\_status is NOT\_PROVISIONED and active\_status is ACTIVE. This API is applicable only in 3GPP devices.

#### 9.44.4.21 ULONG SLQSVoiceGetCOLR ( voiceGetCOLRResp \* pVoiceGetCOLRResp )

Queries the status of the Connected Line Identification Restriction (COLR) supplementary service (applicable only for 3GPP).

## Parameters

<i>pVoiceGetCOL- RResp[OUT]</i>	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceGetCOLRResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetCOLRResp</a> for more information</li> </ul> </li> </ul>
-------------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Timeout: 30 Secs

This API queries the status of the COLR supplementary service. A response indicates whether COLR is active/inactive and provisioned/not provisioned in the network. The active\_status field is only applicable when provision\_status is PROVISIONED, i.e., there is not any case where provision\_status is NOT\_PROVISIONED and active\_status is ACTIVE. This API is applicable only in 3GPP devices.

9.44.4.22 **ULONG** SLQSVoiceGetConfig ( **voiceGetConfigReq** \* *pVoiceGetConfigReq*, **voiceGetConfigResp** \* *pVoiceGetConfigResp* )

This API retrieves various configuration parameters that control the modem behavior related to circuit switched services.



## Parameters

<i>pVoiceGet-ConfigReq</i>	<ul style="list-style-type: none"> <li>• Structure containing Get Config request parameters. <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetConfigReq</a> for more information.</li> </ul> </li> </ul>
<i>pVoiceGet-ConfigResp</i>	<ul style="list-style-type: none"> <li>• Structure containing Get Config response parameters. <ul style="list-style-type: none"> <li>– See <a href="#">voiceGetConfigResp</a> for more information.</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

Any invalid value in a request message causes the service point to reject the message without retrieving any configuration information.

#### 9.44.4.23 ULONG SLQSVoiceIndicationRegister ( voiceIndicationRegisterInfo \* pVoiceIndicationRegisterInfo )

Sets the registration state for different QMI\_VOICE indications for the requesting control point

## Parameters

<i>pVoice-Indication-RegisterInfo[IN]</i>	<ul style="list-style-type: none"> <li>• Structure containing Indication Register Information. <ul style="list-style-type: none"> <li>– See <a href="#">voiceIndicationRegisterInfo</a> for more information.</li> </ul> </li> </ul>
---	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 10 Secs

This API is used by a device to register/deregister for different QMI\_VOICE indications. The device's registration state variables that control registration for indications will be modified to reflect the settings indicated in the request message. At least one optional parameter must be present in the request.

#### 9.44.4.24 **ULONG SLQSVoiceManageCalls ( voiceManageCallsReq \* pVoiceManageCallsReq, voiceManageCallsResp \* pVoiceManageCallsResp )**

Manages the calls by using the supplementary service applicable during the call. In cases of successful API completion if the state of any call is changed, it is indicated using Callback SLQSVoiceSetAllCallStatusCallback. If there are other calls while an incoming voice call (waiting call) is received, this API is used to answer the call. This API is applicable only in "3GPP devices".

##### Parameters

<i>pVoiceManageCallsReq[IN]</i>	<ul style="list-style-type: none"> <li>Request structure of to manage calls.</li> </ul>
<i>pVoiceManageCallsResp[OUT]</i>	<ul style="list-style-type: none"> <li>Response Structure to manage Calls</li> </ul>

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Technology Supported: UMTS  
 Timeout: 10 Secs  
 Applicable only for "3GPP"

#### 9.44.4.25 **ULONG SLQSVoiceOrigUSSDNoWait ( voiceOrigUSSDNoWaitInfo \* pVoiceOrigUSSDNoWaitInfo )**

This API initiates a USSD operation such that the response for this request is returned immediately and the data is returned via an indication.

##### Parameters

<i>pVoiceOrigUSSDNoWaitInfo[IN]</i>	<ul style="list-style-type: none"> <li>See <a href="#">voiceOrigUSSDNoWaitInfo</a> for more information.</li> </ul>
-------------------------------------	---

##### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

##### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

##### Note

Technology Supported: UMTS  
 Timeout: 30 Secs  
 This API starts a new USSD operation. The response to the request is sent immediately. The response result is sent to the client via the SLQSVoiceOrigUSSDNoWaitCallback. This command is applicable only in 3GPP devices.

#### 9.44.4.26 ULONG SLQSVoiceSendFlash ( voiceFlashInfo \* pFlashInfo )

This API sends a simple flash message. Applicable only for 3GPP2 devices.

## Parameters

<i>pFlashInfo</i> [IN/OUT]	<ul style="list-style-type: none"> <li>See <a href="#">voiceFlashInfo</a> for more information.</li> </ul>
----------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA

Timeout: 10 Secs

If success, it only means the device has started the requested operation and not that the Flash has been sent. If the optional parameter Flash Type is not set, the default flash type is assumed to be a simple flash. If the parameter Flash Type is set to 1 the call ID corresponding to it is either an incoming or waiting call's call ID. If the parameter Flash Type is set to 2 the call ID corresponding to it is a held call's call ID. A Flash request is sent to the appropriate call when call\_id is set to 0xFF.

#### 9.44.4.27 ULONG SLQSVoiceSetCallBarringPassword ( voiceSetCallBarringPwdInfo \* pVoiceSetCallBarringPwdInfo, voiceSetCallBarringPwdResp \* pSetCallBarringPwdResp )

Sets a Call Barring Password (applicable only for 3GPP).

## Parameters

<i>pVoiceSetCallBarringPwdInfo</i> [IN]	<ul style="list-style-type: none"> <li>Pointer to structure of <a href="#">voiceSetCallBarringPwdInfo</a> <ul style="list-style-type: none"> <li>See <a href="#">voiceSetCallBarringPwdInfo</a> for more information</li> </ul> </li> </ul>
<i>pSetCallBarringPwdResp</i> [OUT]	<ul style="list-style-type: none"> <li>Pointer to structure of <a href="#">voiceSetCallBarringPwdResp</a> <ul style="list-style-type: none"> <li>See <a href="#">voiceSetCallBarringPwdResp</a> for more information</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS

Timeout: 30 Secs

This API changes the call barring supplementary service password. The request is a blocking request, i.e., the response is sent only after confirmation is received from the network. The maximum time it takes for the response to be sent is approximately 30 sec. This API is applicable only in 3GPP devices.

9.44.4.28 **ULONG** SLQSVoiceSetConfig ( **voiceSetConfigReq** \* *pVoiceSetConfigReq*, **voiceSetConfigResp** \* *pVoiceSetConfigResp* )

This message sets various configuration parameters that control the modem behavior related to circuit-switched services.

## Parameters

<i>pVoiceSet-ConfigReq</i> [IN]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceSetConfigReq</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceSetConfigReq</a> for more information</li> </ul> </li> </ul>
<i>pVoiceSet-ConfigResp</i> [OUT]	<ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceSetConfigResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceSetConfigResp</a> for more information</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

Any invalid value in a request message causes the device to reject the message without updating any configuration information. In the case of a successful update of all requested information, a QMI\_ERR\_NONE error is returned. In the case where a subset of information failed to be written, a QMI\_ERR\_INTERNAL error is returned with corresponding optional information requested in the request message.

#### 9.44.4.29 ULONG SLQSVoiceSetPreferredPrivacy ( voiceSetPrefPrivacy \* pSetPrefPrivacy )

This API sets the voice privacy preference. Applicable only for 3GPP2 devices.

## Parameters

<i>pSetPref-Privacy</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">voiceSetPrefPrivacy</a> for more information.</li> </ul>
------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA

Device Supported: SL9090

Timeout: 10 Secs

9.44.4.30 **ULONG** SLQSVoiceSetSUPSService ( **voiceSetSUPSServiceReq** \* *pVoiceSetSUPSServiceReq*,  
**voiceSetSUPSServiceResp** \* *pVoiceSetSUPSServiceResp* )

This API manages call-independent supplementary services, e.g., activation of call forwarding (to forward incoming calls to a third party), activation of call barring (to request the network to block some of the call attempts), and activation of call waiting (to be notified of an incoming call even when the user is engaged in an active or held call).

## Parameters

<i>pVoiceSetSUPS-ServiceReq</i>	[IN] <ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceSetSUPSServiceReq</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceSetSUPSServiceReq</a> for more information</li> </ul> </li> </ul>
<i>pVoiceSetSUPS-ServiceResp</i>	[OUT] <ul style="list-style-type: none"> <li>• Pointer to structure of <a href="#">voiceSetSUPSServiceResp</a> <ul style="list-style-type: none"> <li>– See <a href="#">voiceSetSUPSServiceResp</a> for more information</li> </ul> </li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS

Timeout: 30 Secs

Some of the call-independent services are provided by the network operator as part of the service agreement. If they are not provided by default, the user has to explicitly request them. This API provides the facility to the control point for sending the explicit request to the network for enabling/disabling

#### 9.44.4.31 ULONG SLQSVoiceStartContDTMF ( voiceContDTMFInfo \* pContDTMFInfo )

Starts a continuous DTMF.

## Parameters

<i>pContDTMF-Info</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Structure containing Continuous DTMF Information.             <ul style="list-style-type: none"> <li>– See <a href="#">voiceContDTMFInfo</a> for more Information.</li> </ul> </li> </ul>
--------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API starts a continuous DTMF. If the API results indicates success, it means that the device has started the requested operation. It does not mean that the start continuous DTMF request has been sent to the network. A start continuous DTMF request is sent to the current active/alerting call when CallId is set to 0xFF.



9.44.4.32 **ULONG** SLQSVoiceStopContDTMF ( **voiceStopContDTMFinfo** \* *pVoiceStopContDTMFinfo* )

Stops a continuous DTMF.

## Parameters

<i>pVoiceStopContDTMFinfo</i>	<ul style="list-style-type: none"> <li>Structure containing Continuous Stop DTMF Information. <ul style="list-style-type: none"> <li>See <a href="#">voiceStopContDTMFinfo</a> for more information.</li> </ul> </li> <li>Start continuous DTMF request is sent to the current active/alerting call when CallId is set to 0xFF.</li> <li>This is IN/OUT params, value passed by user will packed in request and before unpacking response this will be assigned with an invalid callID value "0". It change to a valid value if received as part of response otherwise Invalid value will be present.</li> </ul>
-------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 30 Secs

This API starts a continuous DTMF. If the API results indicates success, it means that the device has started the requested operation. It does not mean that the start continuous DTMF request has been sent to the network. A stop continuous DTMF request is sent to the current active/alerting call when CallId is set to 0xFF.

## 9.45 qaGobiApiWds.h File Reference

Wireless Data Service API function prototypes.

### Data Structures

- struct [dataBearerTechnology](#)
- struct [dataBearers](#)
- struct [QmiWdsIpAddressInfo](#)
- struct [WdsIpAddressInfoReq](#)
- struct [UMTSQoS](#)
- struct [ProfileIdentifier](#)
- struct [GPRSQoS](#)
- struct [PCSCFIPv4ServerAddressList](#)
- struct [PCSCFFQDNAddress](#)
- struct [PCSCFFQDNAddressList](#)
- struct [Domain](#)
- struct [DomainNameList](#)
- struct [IPv6AddressInfo](#)
- struct [IPv6GWAddressInfo](#)
- struct [qmiWdsRunTimeSettings](#)
- struct [WdsRunTimeSettings](#)
- struct [ssdatasession\\_params](#)
- struct [SLQSDDeleteProfileParams](#)
- struct [Profile3GPP](#)

- struct [Profile3GPP2](#)
- union [WdsProfileParam](#)
- struct [CreateProfileIn](#)
- struct [UMTSMinQoS](#)
- struct [GPRSRequestedQoS](#)
- struct [TFTIDParams](#)
- struct [UMTSReqQoSsigInd](#)
- struct [QosClassID](#)
- struct [CreateProfileOut](#)
- struct [slqsautoconnect](#)
- struct [ModifyProfileIn](#)
- struct [ModifyProfileOut](#)
- struct [\\_slqs3GPPConfigItem](#)
- struct [\\_GetProfileSettingIn](#)
- struct [\\_GetProfileSettingOut](#)
- struct [TrStatInd](#)
- struct [wdsSetEventReportReq](#)
- struct [swiPDPRuntimeSettingsReq](#)
- struct [swiPDPRuntimeSettingsResp](#)
- struct [WdsConnectionRateElmnts](#)
- struct [WdsConnectionRate](#)
- struct [WdsByteTotalsElmnts](#)
- struct [WdsByteTotals](#)
- struct [GetInstIDResp](#)
- struct [GetSessionIDResp](#)
- struct [TransferStatInd](#)
- struct [getDUNCallInfoReq](#)
- struct [ConnectionStatus](#)
- struct [ChannelRate](#)
- struct [getDUNCallInfoResp](#)
- struct [WdsPktStatisticsElmnts](#)
- struct [WdsPktStatisticsResp](#)
- struct [WdsPktStatisticsReq](#)
- struct [CurrNetworkInfo](#)
- struct [CurrDataSysStat](#)
- struct [swiRMTrasnferStaticsReq](#)
- struct [DataULongTlv](#)
- struct [DataULongLongTlv](#)
- struct [QmiCbkWdsStatisticsIndState](#)
- struct [DataBearerTech](#)
- struct [DataBearerTechExt](#)
- struct [WDSSWICurrentChannelRates](#)
- struct [WDSSetLoopbackData](#)
- struct [WDSGetLoopbackData](#)
- struct [WdsDHCPv4ProfileId](#)
- struct [WdsDHCPv4HWConfig](#)
- struct [WdsDHCPv4Option](#)
- struct [WdsDHCPv4OptionList](#)
- struct [WdsDHCPv4Config](#)
- struct [WdsClientLeaseChange](#)

## Macros

- `#define` [IPV6\\_ADDRESS\\_ARRAY\\_SIZE](#) 8

## Typedefs

- typedef struct [dataBearerTechnology](#) [QmiWSDDataBearerTechnology](#)
- typedef struct [dataBearers](#) [QmiWSDDataBearers](#)
- typedef union [WdsProfileParam](#) [QmiProfileInfo](#)
- typedef struct [\\_slqs3GPPConfigItem](#) [slqs3GPPConfigItem](#)
- typedef struct [\\_GetProfileSettingIn](#) [GetProfileSettingIn](#)
- typedef struct [\\_GetProfileSettingOut](#) [GetProfileSettingOut](#)

## Enumerations

- enum [qmiDataBearerMasks](#) {  
[QMI\\_WDS\\_CURRENT\\_CALL\\_DB\\_MASK](#) = 0x01,  
[QMI\\_WDS\\_LAST\\_CALL\\_DB\\_MASK](#) = 0x02 }

## Functions

- [ULONG SetMobileIP](#) ([ULONG](#) mode)
- [ULONG GetMobileIP](#) ([ULONG](#) \*pMode)
- [ULONG SetMobileIPParameters](#) ([CHAR](#) \*pSPC, [ULONG](#) \*pMode, [BYTE](#) \*pRetryLimit, [BYTE](#) \*pRetryInterval, [BYTE](#) \*pReRegPeriod, [BYTE](#) \*pReRegTraffic, [BYTE](#) \*pHAAAuthenticator, [BYTE](#) \*pHA2002bis)
- [ULONG SetAutoconnect](#) ([ULONG](#) setting)
- [ULONG GetAutoconnect](#) ([ULONG](#) \*pSetting)
- [ULONG SetDefaultProfile](#) ([ULONG](#) profileType, [ULONG](#) \*pPDPTType, [ULONG](#) \*pIPAddress, [ULONG](#) \*pPrimaryDNS, [ULONG](#) \*pSecondaryDNS, [ULONG](#) \*pAuthentication, [CHAR](#) \*pName, [CHAR](#) \*pAPNName, [CHAR](#) \*pUsername, [CHAR](#) \*pPassword)
- [ULONG SetDefaultProfileLTE](#) ([ULONG](#) profileType, [ULONG](#) \*pPDPTType, [ULONG](#) \*pIPv4Address, [ULONG](#) \*pPrimaryDNSv4, [ULONG](#) \*pSecondaryDNSv4, [USHORT](#) \*pIPv6Address, [USHORT](#) \*pPrimaryDNSv6, [USHORT](#) \*pSecondaryDNSv6, [ULONG](#) \*pAuthentication, [CHAR](#) \*pName, [CHAR](#) \*pAPNName, [CHAR](#) \*pUsername, [CHAR](#) \*pPassword)
- [ULONG SetDefaultProfileLTEV2](#) ([ULONG](#) profileType, [ULONG](#) \*pPDPTType, [ULONG](#) \*pIPv4Address, [ULONG](#) \*pPrimaryDNSv4, [ULONG](#) \*pSecondaryDNSv4, [USHORT](#) \*pIPv6Address, [USHORT](#) \*pPrimaryDNSv6, [USHORT](#) \*pSecondaryDNSv6, [ULONG](#) \*pAuthentication, [CHAR](#) \*pName, [CHAR](#) \*pAPNName, [CHAR](#) \*pUsername, [CHAR](#) \*pPassword)
- [ULONG GetDefaultProfile](#) ([ULONG](#) profileType, [ULONG](#) \*pPDPTType, [ULONG](#) \*pIPAddress, [ULONG](#) \*pPrimaryDNS, [ULONG](#) \*pSecondaryDNS, [ULONG](#) \*pAuthentication, [BYTE](#) nameSize, [CHAR](#) \*pName, [BYTE](#) apnSize, [CHAR](#) \*pAPNName, [BYTE](#) userSize, [CHAR](#) \*pUsername)
- [ULONG GetDefaultProfileLTE](#) ([ULONG](#) profileType, [ULONG](#) \*pPDPTType, [ULONG](#) \*pIPv4Address, [ULONG](#) \*pPrimaryDNSv4, [ULONG](#) \*pSecondaryDNSv4, [USHORT](#) \*pIPv6Address, [USHORT](#) \*pPrimaryDNSv6, [USHORT](#) \*pSecondaryDNSv6, [ULONG](#) \*pAuthentication, [BYTE](#) nameSize, [CHAR](#) \*pName, [BYTE](#) apnSize, [CHAR](#) \*pAPNName, [BYTE](#) userSize, [CHAR](#) \*pUsername)
- [ULONG GetSessionState](#) ([ULONG](#) \*pState, [BYTE](#) instance)
- [ULONG GetPacketStatus](#) ([ULONG](#) \*pTXPacketSuccesses, [ULONG](#) \*pRXPacketSuccesses, [ULONG](#) \*pTXPacketErrors, [ULONG](#) \*pRXPacketErrors, [ULONG](#) \*pTXPacketOverflows, [ULONG](#) \*pRXPacketOverflows, [BYTE](#) instance)
- [ULONG GetByteTotals](#) ([ULONGLONG](#) \*pTXTotalBytes, [ULONGLONG](#) \*pRXTotalBytes, [BYTE](#) instance)
- [ULONG GetDormancyState](#) ([ULONG](#) \*pDormancyState, [BYTE](#) instance)
- [ULONG GetDataBearerTechnology](#) ([ULONG](#) \*pDataBearer, [BYTE](#) instance)
- [ULONG SLQSGetDataBearerTechnology](#) ([QmiWSDDataBearers](#) \*pDataBearers, [BYTE](#) instance)
- [ULONG GetSessionDuration](#) ([ULONGLONG](#) \*pDuration, [BYTE](#) instance)
- [ULONG GetIPAddressLTE](#) ([WdsIpAddressInfoReq](#) \*)
- [ULONG GetConnectionRate](#) ([ULONG](#) \*pCurrentChannelTXRate, [ULONG](#) \*pCurrentChannelIRXRate, [ULONG](#) \*pMaxChannelTXRate, [ULONG](#) \*pMaxChannelIRXRate, [BYTE](#) instance)

- [ULONG GetMobileIPProfile](#) (BYTE index, [BYTE](#) \*pEnabled, [ULONG](#) \*pAddress, [ULONG](#) \*pPrimaryHA, [ULONG](#) \*pSecondaryHA, [BYTE](#) \*pRevTunneling, [BYTE](#) naiSize, [CHAR](#) \*pNAI, [ULONG](#) \*pHASPI, [ULONG](#) \*pAAASPI, [ULONG](#) \*pHASState, [ULONG](#) \*pAAAState)
- [ULONG GetLastMobileIPError](#) ([ULONG](#) \*pError)
- [ULONG iSLQSMISetIPFamilyPreference](#) ([BYTE](#) IPFamilyPreference, [BYTE](#) instance)
- [BOOL WDS\\_IsGobiDevice](#) ()
- [ULONG SetActiveMobileIPProfile](#) ([CHAR](#) \*pSPC, [BYTE](#) index)
- [ULONG SetMobileIPProfile](#) ([CHAR](#) \*pSPC, [BYTE](#) index, [BYTE](#) \*pEnabled, [ULONG](#) \*pAddress, [ULONG](#) \*pPrimaryHA, [ULONG](#) \*pSecondaryHA, [BYTE](#) \*pRevTunneling, [CHAR](#) \*pNAI, [ULONG](#) \*pHASPI, [ULONG](#) \*pAAASPI, [CHAR](#) \*pMNHA, [CHAR](#) \*pMNAAA)
- [ULONG SLQSGetRuntimeSettings](#) (struct [WdsRunTimeSettings](#) \*pRunTimeSettings)
- [ULONG SLQSSetProfile](#) ([ULONG](#) profileType, [BYTE](#) profileId, [ULONG](#) \*pPDPTType, [ULONG](#) \*pIPAddress, [ULONG](#) \*pPrimaryDNS, [ULONG](#) \*pSecondaryDNS, [ULONG](#) \*pAuthentication, [CHAR](#) \*pName, [CHAR](#) \*pAPNName, [CHAR](#) \*pUsername, [CHAR](#) \*pPassword)
- [ULONG SLQSGetProfile](#) ([ULONG](#) profileType, [BYTE](#) profileId, [ULONG](#) \*pPDPTType, [ULONG](#) \*pIPAddress, [ULONG](#) \*pPrimaryDNS, [ULONG](#) \*pSecondaryDNS, [ULONG](#) \*pAuthentication, [BYTE](#) nameSize, [CHAR](#) \*pName, [BYTE](#) apnSize, [CHAR](#) \*pAPNName, [BYTE](#) userSize, [CHAR](#) \*pUsername, [WORD](#) \*pExtendedErrorCode)
- [ULONG SLQSStartStopDataSession](#) (struct [ssdatasession\\_params](#) \*pin)
- [ULONG SLQSDeleteProfile](#) (struct [SLQSDeleteProfileParams](#) \*pProfileToDelete, [WORD](#) \*pExtendedErrorCode)
- [ULONG SLQSCreateProfile](#) (struct [CreateProfileIn](#) \*pReq, struct [CreateProfileOut](#) \*pResp)
- [ULONG SLQSAutoConnect](#) (struct [slqsaautoconnect](#) \*pacreq)
- [ULONG SLQSModifyProfile](#) (struct [ModifyProfileIn](#) \*pReq, struct [ModifyProfileOut](#) \*pResp)
- [ULONG SLQSSet3GPPConfigItem](#) ([slqs3GPPConfigItem](#) \*pSLQS3GPPConfigItem)
- [ULONG SLQSGet3GPPConfigItem](#) ([slqs3GPPConfigItem](#) \*pSLQS3GPPConfigItem)
- [ULONG SLQSGetProfileSettings](#) ([GetProfileSettingIn](#) \*pReq, [GetProfileSettingOut](#) \*pResp)
- [ULONG SLQSWdsSetEventReport](#) ([wdsSetEventReportReq](#) \*pSetEventReportReq)
- [ULONG SLQSWdsSwiPDPRuntimeSettings](#) ([swiPDPRuntimeSettingsReq](#) \*pPDPRuntimeSettingsReq, [swiPDPRuntimeSettingsResp](#) \*pPDPRuntimeSettingsResp)
- [ULONG iGetConnectionRate](#) ([ULONG](#) \*pv4sessionId, [ULONG](#) \*pv6sessionId, struct [WdsConnectionRateElmnts](#) \*pConnectionRateElmnt)
- [ULONG SLQSGetConnectionRate](#) (struct [WdsConnectionRate](#) \*pConnectionRate)
- [ULONG iGetByteTotals](#) ([ULONG](#) \*pv4sessionId, [ULONG](#) \*pv6sessionId, struct [WdsByteTotalsElmnts](#) \*pByteTotalsElmnt)
- [ULONG SLQSGetByteTotals](#) (struct [WdsByteTotals](#) \*pByteTotals)
- [ULONG SLQSWdsGoDormant](#) (void)
- [ULONG SLQSWdsGoActive](#) (void)
- [ULONG SLQSGetSessionState](#) ([ULONG](#) \*pStateV4, [ULONG](#) \*pStateV6, [BYTE](#) instance)
- [ULONG SLQSGetDUNCallInfo](#) ([getDUNCallInfoReq](#) \*pGetDUNCallInfoReq, [getDUNCallInfoResp](#) \*pGetDUNCallInfoResp)
- [ULONG GetPacketStatistics](#) (struct [WdsPktStatisticsReq](#) \*pStatMask, struct [WdsPktStatisticsElmnts](#) \*pPktStatisticsElmnt, [BYTE](#) instance)
- [ULONG iGetPacketStatistics](#) ([ULONG](#) \*pV4sessionId, [ULONG](#) \*pV6sessionId, struct [WdsPktStatisticsReq](#) \*pStatMask, struct [WdsPktStatisticsElmnts](#) \*pPktStatisticsElmnt)
- [ULONG SLQSGetPacketStatistics](#) (struct [WdsPktStatisticsReq](#) \*pStatMask, struct [WdsPktStatisticsResp](#) \*pPktStatistics)
- [ULONG SLQSGetCurrDataSystemStat](#) ([CurrDataSysStat](#) \*pCurrDataSysStat)
- [ULONG RMSetTransferStatistics](#) ([swiRMTrasferStaticsReq](#) \*pSwiRMTrasferStaticsReq)
- [ULONG SLQSResetPacketStatics](#) ()
- [ULONG SLQSGetDataBearerTechnologyExt](#) ([DataBearerTechExt](#) \*pDataBearerTech, [BYTE](#) instance)
- [ULONG SLQSGetCurrentChannelRate](#) ([WDSSWICurrentChannelRates](#) \*pRates, [BYTE](#) instance)
- [ULONG SLQSSetLoopback](#) ([WDSSetLoopbackData](#) \*pReq)
- [ULONG SLQSSetLoopback](#) ([WDSGetLoopbackData](#) \*data)
- [ULONG GetDefaultProfileNum](#) ([BYTE](#) profile\_type, [BYTE](#) profile\_family, [BYTE](#) \*pProfile\_no)
- [ULONG SetDefaultProfileNum](#) ([BYTE](#) profile\_type, [BYTE](#) profile\_family, [BYTE](#) profile\_index)
- [ULONG SLQSSetDHCPv4ClientConfig](#) ([WdsDHCPv4Config](#) \*pReq)
- [ULONG SLQSSetDHCPv4ClientConfig](#) ([WdsDHCPv4Config](#) \*pReqResp)

### 9.45.1 Detailed Description

Wireless Data Service API function prototypes.

### 9.45.2 Macro Definition Documentation

#### 9.45.2.1 `#define IPV6_ADDRESS_ARRAY_SIZE 8`

### 9.45.3 Typedef Documentation

#### 9.45.3.1 `typedef struct _GetProfileSettingIn GetProfileSettingIn`

This structure contains the input parameters for `SLQSGetProfileSettings`

Parameters

<i>ProfileType</i>	<ul style="list-style-type: none"> <li>Identifies the technology type of the profile               <ul style="list-style-type: none"> <li>0x00 - 3GPP</li> <li>0x01 - 3GPP2</li> </ul> </li> </ul>
<i>ProfileID</i>	<ul style="list-style-type: none"> <li>index identifying the profile</li> </ul>

#### 9.45.3.2 `typedef struct _GetProfileSettingOut GetProfileSettingOut`

This structure contains the profile settings retrieved by the API `SLQSGetProfileSettings`

Parameters

<i>curProfile</i>	<ul style="list-style-type: none"> <li>Structure containing details of the profile</li> <li>See <a href="#">QmiProfileInfo</a> for more details</li> </ul>
<i>pExtErrCode</i>	<ul style="list-style-type: none"> <li>pointer to a 2 byte extended error code</li> <li>Error code will only will be present if error code <code>eQCWWAN_ERR_QMI_EXTENDED_INTERNAL</code> is returned by device.</li> <li>See <a href="#">qm_wds_ds_profile_extended_err_codes</a> enum in <a href="#">qmerrno.h</a> for received error description.</li> </ul>

#### 9.45.3.3 `typedef union WdsProfileParam QmiProfileInfo`

This union [WdsProfileParam](#) consist of [Profile3GPP](#) and [Profile3GPP2](#) out of which one will be used to create profile.

#### 9.45.3.4 typedef struct dataBearers QmiWSDDataBearers

Structure to hold the data bearer technology values

## Parameters

<i>dataBearerMask[OUT]</i>	<ul style="list-style-type: none"> <li>This bit mask indicates if data bearer information for the current and/or last call has been received from the device. If a bit is set, then the information is available in the corresponding structure i.e. the one provided by the caller. Refer to <a href="#">qmiDataBearerMasks</a> for bit-mask positions.</li> </ul>
<i>pCurDataBearerTechnology[OUT]</i>	<ul style="list-style-type: none"> <li>current data bearer technology value. <ul style="list-style-type: none"> <li>– NULL if the parameter is not required</li> </ul> </li> </ul>
<i>pLastCallDataBearerTechnology[OUT]</i>	<ul style="list-style-type: none"> <li>last call data bearer technology value. <ul style="list-style-type: none"> <li>– NULL if the parameter is not required</li> </ul> </li> </ul>

## 9.45.3.5 typedef struct dataBearerTechnology QmiWSDDataBearerTechnology

Structure to hold the current data bearer technology values



## Parameters

<i>pCurrent-Network[OUT]</i>	<ul style="list-style-type: none"> <li>current selected network <ul style="list-style-type: none"> <li>0 - UNKNOWN</li> <li>1 - 3GPP2</li> <li>2 - 3GPP</li> </ul> </li> </ul>
<i>pRatMask[OUT]</i>	<ul style="list-style-type: none"> <li>Radio Access Technology (RAT) mask to indicate the type of technology (RAT mask value of zero indicates that this field is ignored) <ul style="list-style-type: none"> <li>0x8000 - NULL Bearer</li> <li>0x0000 - DO_NOT_CARE CDMA RAT mask</li> <li>0x01 - CDMA_1X</li> <li>0x02 - EVDO_REV0</li> <li>0x04 - EVDO_REVA UMTS RAT mask</li> <li>0x01 - WCDMA</li> <li>0x02 - GPRS</li> <li>0x04 - HSDPA</li> <li>0x08 - HSUPA</li> <li>0x10 - EDGE</li> <li>0x20 - LTE</li> <li>0x40 - HSDPA+</li> <li>0x80 - DC_HSDPA+</li> </ul> </li> </ul>
<i>pSoMask[OUT]</i>	<ul style="list-style-type: none"> <li>Service Option (SO) mask to indicate the SO or type of application (SO mask value of zero indicates that this field is ignored) <ul style="list-style-type: none"> <li>0x00 - DO_NOT_CARE CDMA 1X SO mask</li> <li>0x01 - CDMA_1X_IS95</li> <li>0x02 - CDMA_1X_IS2000</li> <li>0x04 - CDMA_1X_IS2000_REL_A CDMA EV-DO Rev A SO mask</li> <li>0x01 - EVDO_REVA_DPA</li> <li>0x02 - EVDO_REVA_MFPA</li> <li>0x04 - EVDO_REVA_EMPA</li> <li>0x08 - EVDO_REVA_EMPA_EHRPD</li> </ul> </li> </ul>

## 9.45.3.6 typedef struct \_slqs3GPPConfigItem slqs3GPPConfigItem

This structure contains the 3gpp Configuration Item information.

## Parameters

<i>pLTEAttach-Profile</i>	<ul style="list-style-type: none"> <li>• LTE Attach Profile <ul style="list-style-type: none"> <li>– points to a single WORD Value indicating the attached LTE Profile</li> <li>– Optional parameter with possible values 1-16 (EM/MC73xx or earlier)</li> <li>– Optional parameter with possible values 1-24 (EM/MC74xx onwards)</li> <li>– function <a href="#">SLQSGet3GPPConfigItem()</a> returns a default value 255 if no LTE Attach Profile is configured</li> </ul> </li> <li>• This setting is deprecated on MC/EM74xx</li> </ul>
<i>pProfileList</i>	<ul style="list-style-type: none"> <li>• Profile List <ul style="list-style-type: none"> <li>– an array of 4 profile configurations</li> <li>– Each element points to a single WORD value indicating profile</li> <li>– Optional parameter with possible values <ul style="list-style-type: none"> <li>* 1 - 16 (MC/EM73xx and before)</li> <li>* 1 - 24 (MC/EM74xx and onwards)</li> </ul> </li> <li>– function <a href="#">SLQSGet3GPPConfigItem()</a> returns a default value 255 if no 3gpp configuration is present</li> </ul> </li> </ul>
<i>pDefaultPDN-Enabled</i>	<ul style="list-style-type: none"> <li>• Always Connect Default PDN <ul style="list-style-type: none"> <li>– A single BYTE value indicating the status of Always connect default PDN <ul style="list-style-type: none"> <li>* 0 - disabled</li> <li>* 1 - enabled</li> </ul> </li> <li>– Optional parameter</li> <li>– function <a href="#">SLQSGet3GPPConfigItem()</a> returns a default value 255 if no 3gpp configuration is present</li> </ul> </li> </ul>
<i>p3gppRelease</i>	<ul style="list-style-type: none"> <li>• 3gpp release <ul style="list-style-type: none"> <li>– A single BYTE value indicating the 3gpp release <ul style="list-style-type: none"> <li>* 0 - Release 99</li> <li>* 1 - Release 5</li> <li>* 2 - Release 6</li> <li>* 3 - Release 7</li> <li>* 4 - Release 8</li> </ul> </li> <li>– Optional parameter</li> <li>– function <a href="#">SLQSGet3GPPConfigItem()</a> returns a default value 255 if no 3gpp configuration is present</li> </ul> </li> </ul>
<i>pLTEAttach-ProfileList</i>	<ul style="list-style-type: none"> <li>• pointer to WORD array indicating LTE Attach Profile List <ul style="list-style-type: none"> <li>– Optional parameter</li> <li>– possible values: 1-24</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>– This setting is only supported for MC/EM74xx onwards</li> <li>– The new equivalent option for "pLTEAttachProfile" on 74xx modems is "pLTEAttachProfileList". Please provide attach profiles in order of decreasing priority in this list.</li> </ul>

<i>LTEAttach-ProfileListLen</i>	<ul style="list-style-type: none"> <li>• Number of element in pLTEAttachProfileList <ul style="list-style-type: none"> <li>– valid range: 0-2</li> <li>* This setting is only supported for MC/EM74xx onwards</li> </ul> </li> </ul>
---------------------------------	--

## 9.45.4 Enumeration Type Documentation

### 9.45.4.1 enum qmiDataBearerMasks

Bit mask values to indicate the presence of data bearer information for the current and last data calls

Enumerator

***QMI\_WDS\_CURRENT\_CALL\_DB\_MASK***

***QMI\_WDS\_LAST\_CALL\_DB\_MASK***

## 9.45.5 Function Documentation

### 9.45.5.1 ULONG GetAutoconnect ( ULONG \* pSetting )

Returns the current auto connect data session setting.

Parameters

<i>pSetting[OUT]</i>	<ul style="list-style-type: none"> <li>• NDIS auto connect setting <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> </ul> </li> </ul>
----------------------	--

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

Note

Timeout: 2 seconds

### 9.45.5.2 ULONG GetByteTotals ( ULONGLONG \* pTXTotalBytes, ULONGLONG \* pRXTotalBytes, BYTE instance )

Returns the Rx/Tx byte counts since the start of the last packet data session for IPV4 session only.

## Parameters

<i>pTXTotalBytes[OUT]</i>	<ul style="list-style-type: none"> <li>Bytes transmitted without error</li> </ul>
<i>pRXTotalBytes[OUT]</i>	<ul style="list-style-type: none"> <li>Bytes received without error</li> </ul>
<i>instance</i>	<ul style="list-style-type: none"> <li>PDP instance</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds, Rx/Tx byte counts for IPV4 only

**9.45.5.3** **ULONG** GetConnectionRate ( **ULONG** \* *pCurrentChannelTXRate*, **ULONG** \* *pCurrentChannelRXRate*, **ULONG** \* *pMaxChannelTXRate*, **ULONG** \* *pMaxChannelRXRate*, **BYTE** *instance* )

Returns connection rate information for the packet data connection. This API is not applicable when multiple data session is up. For multiple PDN, please use API [SLQSGetConnectionRate\(\)](#)

## Parameters

<i>pCurrent-ChannelTX-Rate[OUT]</i>	<ul style="list-style-type: none"> <li>Current channel Tx rate (in bps)</li> </ul>
<i>pCurrent-ChannelRX-Rate[OUT]</i>	<ul style="list-style-type: none"> <li>Current channel Rx rate (in bps)</li> </ul>
<i>pMaxChannelTXRate[OUT]</i>	<ul style="list-style-type: none"> <li>Maximum Tx rate (bps) that may be assigned to device by serving system.</li> </ul>
<i>pMaxChannelRXRate[OUT]</i>	<ul style="list-style-type: none"> <li>Maximum Rx rate (bps) that may be assigned to device by serving system.</li> </ul>
<i>instance</i>	<ul style="list-style-type: none"> <li>PDP instance</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

#### 9.45.5.4 ULONG GetDataBearerTechnology ( ULONG \* pDataBearer, BYTE instance )

Retrieves the current data bearer technology (only valid when connected). This API is deprecated on MC73xx/E-M73xx modules since firmware version SWI9X15C\_05\_xx\_xx\_xx and all EM74xx firmware versions. Please use API [SLQSGetDataBearerTechnologyExt\(\)](#) for new firmware versions and new modules.

## Parameters

<i>pDataBearer[O-UT]</i>	<ul style="list-style-type: none"> <li>• Data bearer technology <ul style="list-style-type: none"> <li>– 0x01 - CDMA2000 1x</li> <li>– 0x02 - CDMA 1xEV-DO Rev 0</li> <li>– 0x03 - GSM</li> <li>– 0x04 - UMTS</li> <li>– 0x05 - CDMA2000 HRPD (1xEV-DO Rev A)</li> <li>– 0x06 - EDGE</li> <li>– 0x07 - HSDPA AND WCDMA</li> <li>– 0x08 - WCDMA AND HSUPA</li> <li>– 0x09 - HSDPA AND HSUPA</li> <li>– 0x0A - LTE</li> <li>– 0x0B - CDMA2000 EHRPD</li> <li>– 0x0C - HSDPA+ and WCDMA</li> <li>– 0x0D - HSDPA+ and HSUPA</li> <li>– 0x0E - DC_HSDPA+ and WCDMA</li> <li>– 0x0F - DC_HSDPA+ and HSUPA</li> <li>– 0x10 - HSDPA+ and 64QAM</li> <li>– 0x11 - HSDPA+, 64QAM and HSUPA</li> <li>– 0x12 - TDSCDMA</li> <li>– 0x13 - TDSCDMA and HSDPA</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
--------------------------	---

<i>instance</i>	<ul style="list-style-type: none"><li>• PDP instance</li></ul>
-----------------	--

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### Note

The QMI command of this API is deprecated. Use [SLQSGetDataBearerTechnologyExt\(\)](#) for new modules (chipset 9x15, 9x30). Version Introduced: Major-1, Minor-12 Version Deprecated: Major-1, Minor-40 Timeout: 2 seconds

**9.45.5.5** `ULONG GetDefaultProfile ( ULONG profileType, ULONG * pPDPTType, ULONG * pIPAddress, ULONG * pPrimaryDNS, ULONG * pSecondaryDNS, ULONG * pAuthentication, BYTE nameSize, CHAR * pName, BYTE apnSize, CHAR * pAPNName, BYTE userSize, CHAR * pUsername )`

Reads the default profile settings from the device. The default profile is used to establish an auto connect data session.

## Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>Type of profile <ul style="list-style-type: none"> <li>0 - UMTS</li> </ul> </li> </ul>
<i>pPDPTType[OUT]</i>	<ul style="list-style-type: none"> <li>Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile <ul style="list-style-type: none"> <li>0 - PDP-IP (IPv4)</li> </ul> </li> </ul>
<i>pIPAddress[OUT]</i>	<ul style="list-style-type: none"> <li>Preferred IPv4 address to be assigned to device</li> </ul>
<i>pPrimaryDNS[OUT]</i>	<ul style="list-style-type: none"> <li>Primary DNS Ipv4 address preference</li> </ul>
<i>pSecondaryDNS[OUT]</i>	<ul style="list-style-type: none"> <li>Secondary DNS Ipv4 address preference</li> </ul>
<i>pAuthentication[OUT]</i>	<ul style="list-style-type: none"> <li>Bitmap that indicates authentication algorithm preference <ul style="list-style-type: none"> <li>0x00000001 - PAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>0x00000002 - CHAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>All other bits are reserved and must be set to 0</li> <li>If more than 1 bit is set, then device decides which authentication procedure is performed while setting up data session e.g. the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul>
<i>nameSize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that profile name array can contain.</li> </ul>
<i>pName[OUT]</i>	<ul style="list-style-type: none"> <li>Profile name</li> </ul>
<i>apnSize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that APN name array can contain</li> </ul>

<i>pAPNName</i> [OUT]	<ul style="list-style-type: none"> <li>• Access point name. NULL-terminated string parameter that is a logical name used to select GGSN and external packet data network.</li> <li>• If value is NULL or omitted, then subscription default value will be requested.</li> </ul>
<i>userSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that username array can contain.</li> </ul>
<i>pUsername</i> [OUT]	<ul style="list-style-type: none"> <li>• Username used during network authentication</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.45.5.6** **ULONG** GetDefaultProfileLTE ( **ULONG** *profileType*, **ULONG** \* *pPDPTType*, **ULONG** \* *pIPAddressv4*, **ULONG** \* *pPrimaryDNSv4*, **ULONG** \* *pSecondaryDNSv4*, **USHORT** \* *pIPAddressv6*, **USHORT** \* *pPrimaryDNSv6*, **USHORT** \* *pSecondaryDNSv6*, **ULONG** \* *pAuthentication*, **BYTE** *nameSize*, **CHAR** \* *pName*, **BYTE** *apnSize*, **CHAR** \* *pAPNName*, **BYTE** *userSize*, **CHAR** \* *pUsername* )

Reads the default profile settings from the device. The default profile is used to establish an auto connect data session.

**Parameters**

<i>profileType</i>	<ul style="list-style-type: none"> <li>• Type of profile <ul style="list-style-type: none"> <li>– 0 - UMTS</li> </ul> </li> </ul>
<i>pPDPTType</i> [OUT]	<ul style="list-style-type: none"> <li>• Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile <ul style="list-style-type: none"> <li>– 0 - PDP-IP (IPv4)</li> </ul> </li> </ul>



<i>pIPvAddressv4[-OUT]</i>	<ul style="list-style-type: none"> <li>Preferred IPv4 addr to be assigned to device</li> </ul>
<i>pPrimaryDN-Sv4[OUT]</i>	<ul style="list-style-type: none"> <li>Primary DNS Ipv4 address preference</li> </ul>
<i>pSecondaryDN-Sv4[OUT]</i>	<ul style="list-style-type: none"> <li>Secondary DNS Ipv4 address preference</li> </ul>
<i>pIPvAddressv6[-OUT]</i>	<ul style="list-style-type: none"> <li>Preferred IPv6 addr to be assigned to device Space for storing 8 element array for the IPv6 addresses is allocated by the application. The IP Address will be retrieved in the big endian format. For example User buffer contents: [&lt;U0&gt;..&lt;&lt;U7&gt;]</li></ul> <p>IPv6 address:  1234:2A01:.....:5678  U0 corresponds to 1234  U1 corresponds to 2A01  -----  -----  U7 corresponds to 5678</p>
<i>pPrimaryDN-Sv6[OUT]</i>	<ul style="list-style-type: none"> <li>Primary DNS Ipv6 address preference</li> </ul>
<i>pSecondaryDN-Sv6[OUT]</i>	<ul style="list-style-type: none"> <li>Secondary DNS Ipv6 address preference</li> </ul>
<i>pAuthentication[-OUT]</i>	<ul style="list-style-type: none"> <li>Bitmap that indicates authentication algorithm preference <ul style="list-style-type: none"> <li>0x00000001 - PAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>0x00000002 - CHAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>All other bits are reserved and must be set to 0</li> <li>If more than 1 bit is set, then device decides which authentication procedure is performed while setting up data session e.g. the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul>

<i>nameSize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that Profile name array can contain</li> </ul>
<i>pName[OUT]</i>	<ul style="list-style-type: none"> <li>Profile name</li> </ul>
<i>apnSize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters (including NULL terminator) that APN name array can contain</li> </ul>
<i>pAPNName[IN]</i>	<ul style="list-style-type: none"> <li>Access point name. NULL-terminated string parameter that is a logical name used to select GGSN and external packet data network.</li> <li>If value is NULL or omitted, then subscription default value will be requested.</li> </ul>
<i>userSize</i>	<ul style="list-style-type: none"> <li>Maximum number of characters including NULL terminator) that username array can contain.</li> </ul>
<i>pUsername[OUT]</i>	<ul style="list-style-type: none"> <li>Username used during network authentication</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: LTE  
Timeout: 2 seconds

#### 9.45.5.7 ULONG GetDefaultProfileNum ( BYTE *profile\_type*, BYTE *profile\_family*, BYTE \* *pProfile\_no* )

This API to Get default profile number

**Parameters**

<i>profile_type</i>	[IN] <ul style="list-style-type: none"> <li>0 - 3GPP</li> <li>1 - 3GPP2</li> </ul>
---------------------	--

<i>profile_family</i>	[IN] <ul style="list-style-type: none"><li>• 0 - Embedded</li><li>• 1 - Tethered</li></ul>
<i>pProfile_no</i>	[OUT]

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

**9.45.5.8 ULONG GetDormancyState ( ULONG \* pDormancyState, BYTE instance )**

Returns the dormancy state of the current packet data session when connected.

**Parameters**

<i>pDormancy-State[OUT]</i>	<ul style="list-style-type: none"> <li>• Dormancy state of current packet data session <ul style="list-style-type: none"> <li>– 1 - Traffic channel dormant</li> <li>– 2 - Traffic channel active</li> </ul> </li> </ul>
<i>instance</i>	<ul style="list-style-type: none"> <li>• PDP instance</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.45.5.9 ULONG GetIPAddressLTE ( WdsIpAddressInfoReq \* )**

Returns the current packet data session IP address(es)

- Parameter values default to their data type's maximum unsigned value unless explicitly stated otherwise.

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: LTE  
Timeout: 2 seconds.

**9.45.5.10 ULONG GetLastMobileIPError ( ULONG \* pError )**

Returns the last mobile IP error.

**Parameters**

<i>pError[OUT]</i>	<ul style="list-style-type: none"><li>• Status of last MIP call (or attempt)<ul style="list-style-type: none"><li>– Zero - Success</li><li>– NonZero - Error code</li></ul>See <a href="#">qaGobiApiTableCallEndReasons.h</a> for Mobile IP Error codes</li></ul>
--------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Device Supported: MC83x5  
Timeout: 2 seconds

**9.45.5.11 ULONG GetMobileIP ( ULONG \* pMode )**

Returns the current mobile IP setting.

**Parameters**

<i>mode[OUT]</i>	<ul style="list-style-type: none"><li>• Mobile IP setting<ul style="list-style-type: none"><li>– 0 - Mobile IP off (simple IP only)</li><li>– 1 - Mobile IP preferred</li><li>– 2 - Mobile IP only</li></ul></li></ul>
------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA  
Timeout: 2 seconds

**9.45.5.12** **ULONG** GetMobileIPProfile ( **BYTE** *index*, **BYTE** \* *pEnabled*, **ULONG** \* *pAddress*, **ULONG** \* *pPrimaryHA*, **ULONG** \* *pSecondaryHA*, **BYTE** \* *pRevTunneling*, **BYTE** *naiSize*, **CHAR** \* *pNAI*, **ULONG** \* *pHASPI*, **ULONG** \* *pAAASPI*, **ULONG** \* *pHASState*, **ULONG** \* *pAAASState* )

Returns the specified mobile IP profile settings.

## Parameters

<i>index</i>	<ul style="list-style-type: none"> <li>• Mobile IP profile ID</li> </ul>
<i>pEnabled</i> [OUT]	<ul style="list-style-type: none"> <li>• Profile enabled: <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>
<i>pAddress</i> [OUT]	<ul style="list-style-type: none"> <li>• Home IPv4 address: <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pPrimaryHA</i> [OUT]	<ul style="list-style-type: none"> <li>• Primary home agent IPv4 address <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pSecondaryHA</i> [OUT]	<ul style="list-style-type: none"> <li>• Secondary home agent IPv4 address <ul style="list-style-type: none"> <li>– 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pRevTunneling</i> [OUT]	<ul style="list-style-type: none"> <li>• Reverse tunneling enabled <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> <li>– 0xFF - Unknown</li> </ul> </li> </ul>

<i>naiSize</i>	<ul style="list-style-type: none"> <li>The maximum number of characters (including NULL terminator) that the NAI array can contain.</li> </ul>
<i>pNAI[OUT]</i>	<ul style="list-style-type: none"> <li>Network access identifier string</li> </ul>
<i>pHASPI[OUT]</i>	<ul style="list-style-type: none"> <li>Home agent security parameter index</li> </ul>
<i>pAAASPI[OUT]</i>	<ul style="list-style-type: none"> <li>AAA server security parameter index <ul style="list-style-type: none"> <li>0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pHASState[OUT]</i>	<ul style="list-style-type: none"> <li>Home agent key state <ul style="list-style-type: none"> <li>0 - Unset</li> <li>1 - Set, default value</li> <li>2 - Set, modified from default</li> <li>3 - 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>
<i>pAAASState[OUT]</i>	<ul style="list-style-type: none"> <li>AAA key state <ul style="list-style-type: none"> <li>0 - Unset</li> <li>1 - Set, default value</li> <li>2 - Set, modified from default</li> <li>3 - 0xFFFFFFFF - Unknown</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA

Timeout: 2 seconds

**9.45.5.13** **ULONG** GetPacketStatistics ( struct WdsPktStatisticsReq \* *pStatMask*, struct WdsPktStatisticsElmnts \* *pPktStatisticsElmnt*, BYTE *instance* )

Returns the current packet transfer counter values from the device. Since the start of the last packet data session.

## Parameters

<i>pStatMask[IN]</i>	<ul style="list-style-type: none"> <li>See <a href="#">WdsPktStatisticsReq</a> for more information</li> </ul>
<i>pPktStatistics-Elmnt[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">WdsPktStatisticsElmnts</a> for more information</li> </ul>
<i>instance</i>	<ul style="list-style-type: none"> <li>PDP instance</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.45.5.14** **ULONG** GetPacketStatus ( **ULONG** \* *pTXPacketSuccesses*, **ULONG** \* *pRXPacketSuccesses*, **ULONG** \* *pTXPacketErrors*, **ULONG** \* *pRXPacketErrors*, **ULONG** \* *pTXPacketOverflows*, **ULONG** \* *pRXPacketOverflows*, **BYTE** *instance* )

Returns the packet data transfer statistics since the start of the current packet data.

## Parameters

<i>pTXPacket-Successes[OUT]</i>	<ul style="list-style-type: none"> <li>No. of packets transmitted without error</li> </ul>
<i>pRXPacket-Successes[OUT]</i>	<ul style="list-style-type: none"> <li>No. of packets received without error</li> </ul>
<i>pTXPacket-Errors[OUT]</i>	<ul style="list-style-type: none"> <li>No. of outgoing packets with framing errors</li> </ul>
<i>pRXPacket-Errors[OUT]</i>	<ul style="list-style-type: none"> <li>No. of incoming packets with framing errors</li> </ul>
<i>pTXPacket-Overflows[OUT]</i>	<ul style="list-style-type: none"> <li>Number of packets dropped because Tx buffer overflowed</li> </ul>
<i>pRXPacket-Overflows[OUT]</i>	<ul style="list-style-type: none"> <li>Number of packets dropped because Rx buffer overflowed</li> </ul>

<i>instance</i>	<ul style="list-style-type: none"><li>• PDP instance</li></ul>
-----------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.45.5.15 ULONG GetSessionDuration ( ULONGLONG \* pDuration, BYTE instance )**

Returns the duration of the current packet data session.

**Parameters**

<i>pDuration[OUT]</i>	<ul style="list-style-type: none"><li>• Duration of the current packet session in milliseconds</li></ul>
<i>instance</i>	<ul style="list-style-type: none"><li>• PDP instance</li></ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: UMTS/CDMA  
Device Supported: MC83x5, MC7700/50  
Timeout: 2 seconds

**9.45.5.16 ULONG GetSessionState ( ULONG \* pState, BYTE instance )**

Returns the state of the current packet data session.



## Parameters

<i>pState</i> [OUT]	<ul style="list-style-type: none"> <li>Current link status <ul style="list-style-type: none"> <li>1 - DISCONNECTED</li> <li>2 - CONNECTED</li> <li>3 - SUSPENDED (not supported)</li> <li>4 - AUTHENTICATING</li> </ul> </li> </ul>
<i>instance</i>	<ul style="list-style-type: none"> <li>PDP instance</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

9.45.5.17 **ULONG** iGetByteTotals ( **ULONG** \* *pv4sessionId*, **ULONG** \* *pv6sessionId*, struct WdsByteTotalsElmnts \* *pByteTotalsElmnt* )

9.45.5.18 **ULONG** iGetConnectionRate ( **ULONG** \* *pv4sessionId*, **ULONG** \* *pv6sessionId*, struct WdsConnectionRateElmnts \* *pConnectionRateElmnt* )

9.45.5.19 **ULONG** iGetPacketStatistics ( **ULONG** \* *pV4sessionId*, **ULONG** \* *pV6sessionId*, struct WdsPktStatisticsReq \* *pStatMask*, struct WdsPktStatisticsElmnts \* *pPktStatisticsElmnt* )

9.45.5.20 **ULONG** iSLQSMISetIPFamilyPreference ( **BYTE** *IPFamilyPreference*, **BYTE** *instance* )

9.45.5.21 **ULONG** RMSetTransferStatistics ( **swiRMTrasferStaticsReq** \* *pSwiRMTrasferStaticsReq* )

This API request the device to fetch current data system transfer Statistics.

## Parameters

<i>pSwiRMTrasferStaticsReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">swiRMTrasferStaticsReq</a> for more information</li> </ul>
-------------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

**9.45.5.22** **ULONG** SetActiveMobileIPProfile ( **CHAR** \* *pSPC*, **BYTE** *index* )

Sets active mobile IP profile.

## Parameters

<i>pSPC</i> [IN]	<ul style="list-style-type: none"> <li>• NULL-terminated string representing six digit service programming code</li> </ul>
<i>index</i> [IN]	<ul style="list-style-type: none"> <li>• Index of the profile to be set as the active profile</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA

Timeout: 2 seconds

9.45.5.23 ULONG SetAutoconnect ( ULONG *setting* )

Sets the auto connect data session setting.

## Parameters

<i>setting</i> [IN]	<ul style="list-style-type: none"> <li>• NDIS autoconnect setting <ul style="list-style-type: none"> <li>– 0 - Disabled</li> <li>– 1 - Enabled</li> </ul> </li> </ul>
---------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

When enabling, timeout is 5 minutes,

When disabling, timeout is 5 seconds

9.45.5.24 ULONG SetDefaultProfile ( ULONG *profileType*, ULONG \* *pPDPTType*, ULONG \* *pIPAddress*, ULONG \* *pPrimaryDNS*, ULONG \* *pSecondaryDNS*, ULONG \* *pAuthentication*, CHAR \* *pName*, CHAR \* *pAPNName*, CHAR \* *pUsername*, CHAR \* *pPassword* )

Writes the default profile settings to the device. The default profile is used to establish an autoconnect data session.

## Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>Type of profile <ul style="list-style-type: none"> <li>0 - UMTS</li> </ul> </li> </ul>
<i>pPDPTType[IN]</i>	<ul style="list-style-type: none"> <li>Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile (optional) <ul style="list-style-type: none"> <li>0 - PDP-IP (IPv4)</li> </ul> </li> </ul>
<i>pIPAddress[IN]</i>	<ul style="list-style-type: none"> <li>Preferred IPv4 addr to be assigned to device (optional)</li> </ul>
<i>pPrimaryDNS[IN]</i>	<ul style="list-style-type: none"> <li>Primary DNS Ipv4 address preference (optional)</li> </ul>
<i>pSecondaryDNS[IN]</i>	<ul style="list-style-type: none"> <li>Secondary DNS Ipv4 address preference (optional)</li> </ul>
<i>pAuthentication[IN]</i>	<ul style="list-style-type: none"> <li>Bitmap that indicates authentication algorithm preference (optional) <ul style="list-style-type: none"> <li>0x00000001 - PAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>0x00000002 - CHAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>All other bits are reserved and must be set to 0</li> <li>If more than 1 bit is set, then device decides which authentication procedure is performed while setting up data session e.g. the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul>

<i>pName</i> [IN]	<ul style="list-style-type: none"> <li>• profile Name (optional)</li> </ul>
<i>pAPNName</i> [IN]	<ul style="list-style-type: none"> <li>• Access point name. NULL-terminated string parameter that is a logical name used to select GGSN and external packet data network (optional)</li> <li>• If value is NULL or omitted, then subscription default value will be requested.</li> </ul>
<i>pUsername</i> [IN]	<ul style="list-style-type: none"> <li>• Username used during network authentication (optional)</li> </ul>
<i>pPassword</i> [IN]	<ul style="list-style-type: none"> <li>• Password used during network authentication (optional)</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout is 2 seconds.

**9.45.5.25** **ULONG** SetDefaultProfileLTE ( **ULONG** *profileType*, **ULONG** \* *pPDPTType*, **ULONG** \* *pIPAddressv4*, **ULONG** \* *pPrimaryDNSv4*, **ULONG** \* *pSecondaryDNSv4*, **USHORT** \* *pIPAddressv6*, **USHORT** \* *PrimaryDNSv6*, **USHORT** \* *pSecondaryDNSv6*, **ULONG** \* *pAuthentication*, **CHAR** \* *pName*, **CHAR** \* *pAPNName*, **CHAR** \* *pUsername*, **CHAR** \* *pPassword* )

Writes the default profile settings to the device. The default profile is used to establish an auto connect data session.

**Parameters**

<i>profileType</i>	<ul style="list-style-type: none"> <li>• Type of profile <ul style="list-style-type: none"> <li>– 0 - UMTS</li> </ul> </li> </ul>
<i>pPDPTType</i> [IN]	<ul style="list-style-type: none"> <li>• Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile (optional) <ul style="list-style-type: none"> <li>– 0 - PDP-IP (IPv4)</li> </ul> </li> </ul>

<i>pIPvAddressv4</i> [I-N]	<ul style="list-style-type: none"> <li>Preferred IPv4 address to be assigned to device (optional)</li> </ul>
<i>pPrimaryDN-Sv4</i> [IN]	<ul style="list-style-type: none"> <li>Primary DNS Ipv4 address preference (optional)</li> </ul>
<i>pSecondaryDN-Sv4</i> [IN]	<ul style="list-style-type: none"> <li>Secondary DNS Ipv4 address preference (optional)</li> </ul>
<i>pIPvAddressv6</i> [I-N]	<ul style="list-style-type: none"> <li>Preferred IPv6 address to be assigned to device (optional)</li> </ul>
<i>pPrimaryDN-Sv6</i> [IN]	<ul style="list-style-type: none"> <li>Primary DNS Ipv6 address preference (optional)</li> </ul>
<i>pSecondaryDN-Sv6</i> [IN]	<ul style="list-style-type: none"> <li>Secondary DNS Ipv6 address preference (optional)</li> </ul>
<i>pAuthentication</i> [I-N]	<ul style="list-style-type: none"> <li>Bitmap that indicates authentication algorithm preference (optional) <ul style="list-style-type: none"> <li>0x00000001 - PAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>0x00000002 - CHAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>All other bits are reserved and must be set to 0</li> <li>If more than 1 bit is set, then device decides which authentication procedure is performed while setting up data session e.g.the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul>
<i>pName</i> [IN]	<ul style="list-style-type: none"> <li>profile Name (optional)</li> </ul>
<i>pAPNName</i> [IN]	<ul style="list-style-type: none"> <li>Access point name. NULL-terminated string parameter that is a logical name used to select GGSN and external packet data network (optional)</li> <li>If value is NULL or omitted, then subscription default value will be requested</li> </ul>
<i>pUsername</i> [IN]	<ul style="list-style-type: none"> <li>Username used during network authentication (optional)</li> </ul>
<i>pPassword</i> [IN]	<ul style="list-style-type: none"> <li>Password used during network authentication (optional)</li> </ul>

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_XXX error values

#### Note

Deprecated, please use SetDefaultProfileLTEV2 instead  
Technology Supported: LTE  
Timeout: 2 seconds

**9.45.5.26** `ULONG SetDefaultProfileLTEV2 ( ULONG profileType, ULONG * pPDPTtype, ULONG * pIPAddressv4,  
ULONG * pPrimaryDNSv4, ULONG * pSecondaryDNSv4, USHORT * pIPAddressv6, USHORT *  
PrimaryDNSv6, USHORT * pSecondaryDNSv6, ULONG * pAuthentication, CHAR * pName, CHAR *  
pAPNName, CHAR * pUsername, CHAR * pPassword )`

Writes the default profile settings to the device. The default profile is used to establish an auto connect data session.

## Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>Type of profile <ul style="list-style-type: none"> <li>0 - UMTS</li> </ul> </li> </ul>
<i>pPDPTYPE[IN]</i>	<ul style="list-style-type: none"> <li>Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile (optional) <ul style="list-style-type: none"> <li>0 - PDP-IP (IPv4)</li> </ul> </li> </ul>
<i>pIPv4Address[IN]</i>	<ul style="list-style-type: none"> <li>Preferred IPv4 address to be assigned to device (optional)</li> </ul>
<i>pPrimaryDNSv4[IN]</i>	<ul style="list-style-type: none"> <li>Primary DNS IPv4 address preference (optional)</li> </ul>
<i>pSecondaryDNSv4[IN]</i>	<ul style="list-style-type: none"> <li>Secondary DNS IPv4 address preference (optional)</li> </ul>
<i>pIPv6Address[IN]</i>	<ul style="list-style-type: none"> <li>Preferred IPv6 addr to be assigned to device (optional)</li> </ul>
<i>pPrimaryDNSv6[IN]</i>	<ul style="list-style-type: none"> <li>Primary DNS IPv6 address preference (optional)</li> </ul>
<i>pSecondaryDNSv6[IN]</i>	<ul style="list-style-type: none"> <li>Secondary DNS IPv6 address preference (optional)</li> </ul>
<i>pAuthentication[IN]</i>	<ul style="list-style-type: none"> <li>Bitmap that indicates authentication algorithm preference (optional) <ul style="list-style-type: none"> <li>0x00000001 - PAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>0x00000002 - CHAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>All other bits are reserved and must be set to 0</li> <li>If more than 1 bit is set, then device decides which authentication procedure is performed while setting up data session e.g.the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul>
<i>pName[IN]</i>	<ul style="list-style-type: none"> <li>profile Name (optional)</li> </ul>



<i>pAPNName</i> [IN]	<ul style="list-style-type: none"> <li>• Access point name. NULL-terminated string parameter that is a logical name used to select GGSN and external packet data network (optional)</li> <li>• If value is NULL or omitted, then subscription default value will be requested</li> </ul>
<i>pUsername</i> [IN]	<ul style="list-style-type: none"> <li>• Username used during network authentication (optional)</li> </ul>
<i>pPassword</i> [IN]	<ul style="list-style-type: none"> <li>• Password used during network authentication (optional)</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: LTE

Timeout: 2 seconds

Replaces deprecated Function SetDefaultProfileLTE

#### 9.45.5.27 **ULONG** SetDefaultProfileNum ( **BYTE** *profile\_type*, **BYTE** *profile\_family*, **BYTE** *profile\_index* )

This API to Set default profile number

**Parameters**

<i>profile_type</i>	[IN] <ul style="list-style-type: none"> <li>• 0 - 3GPP</li> <li>• 1 - 3GPP2</li> </ul>
<i>profile_family</i>	[IN] <ul style="list-style-type: none"> <li>• 0 - Embedded</li> <li>• 1 - Tethered</li> </ul>
<i>profile_index</i>	[IN]

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

#### 9.45.5.28 **ULONG** SetMobileIP ( **ULONG** *mode* )

Sets the current mobile IP setting.

## Parameters

<i>mode</i> [IN]	<ul style="list-style-type: none"> <li>• Mobile IP setting <ul style="list-style-type: none"> <li>– 0 - Mobile IP off (simple IP only)</li> <li>– 1 - Mobile IP preferred</li> <li>– 2 - Mobile IP only</li> </ul> </li> </ul>
------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA  
Timeout: 2 seconds

**9.45.5.29** **ULONG** SetMobileIPParameters ( **CHAR** \* *pSPC*, **ULONG** \* *pMode*, **BYTE** \* *pRetryLimit*, **BYTE** \* *pRetryInterval*, **BYTE** \* *pReRegPeriod*, **BYTE** \* *pReRegTraffic*, **BYTE** \* *pHAAAuthenticator*, **BYTE** \* *pHA2002bis* )

Sets the specified mobile IP parameters.

## Parameters

<i>pSPC</i> [IN]	<ul style="list-style-type: none"> <li>• NULL-terminated string representing six digit service programming code.</li> </ul>
<i>pMode</i> [IN]	<ul style="list-style-type: none"> <li>• Mode to be set (optional) <ul style="list-style-type: none"> <li>– 0 - Mobile IP off (simple IP only)</li> <li>– 1 - Mobile IP preferred</li> <li>– 2 - Mobile IP only</li> </ul> </li> </ul>
<i>pRetryLimit</i> [IN]	<ul style="list-style-type: none"> <li>• Registration retry attempt limit (optional)</li> </ul>
<i>pRetryInterval</i> [I-N]	<ul style="list-style-type: none"> <li>• Registration retry attempt interval used to determine the time between registration attempts (optional)</li> </ul>

<i>pReRegPeriod</i> [I-N]	<ul style="list-style-type: none"> <li>Period (in minutes) to attempt re-registration before current registration expires (optional)</li> </ul>
<i>pReRegTraffic</i> [I-N]	<ul style="list-style-type: none"> <li>Re-registration only if traffic since last attempt (optional) <ul style="list-style-type: none"> <li>Zero - Disabled</li> <li>NonZero - Enabled</li> </ul> </li> </ul>
<i>pHA-Authenticator</i> [IN]	<ul style="list-style-type: none"> <li>MH-HA authenticator calculator (optional) <ul style="list-style-type: none"> <li>Zero - Disabled</li> <li>NonZero - Enabled</li> </ul> </li> </ul>
<i>pHA2002bis</i> [IN]	<ul style="list-style-type: none"> <li>MH-HA RFC 2002bis authentication instead of RFC2002 (optional) <ul style="list-style-type: none"> <li>Zero - Disabled</li> <li>NonZero - Enabled</li> </ul> </li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Device Supported: None  
Timeout: 2 seconds

**9.45.5.30** **ULONG** SetMobileIPProfile ( **CHAR** \* *pSPC*, **BYTE** *index*, **BYTE** \* *pEnabled*, **ULONG** \* *pAddress*, **ULONG** \* *pPrimaryHA*, **ULONG** \* *pSecondaryHA*, **BYTE** \* *pRevTunneling*, **CHAR** \* *pNAI*, **ULONG** \* *pHASPI*, **ULONG** \* *pAAASPI*, **CHAR** \* *pmNHA*, **CHAR** \* *pmNAAA* )

Sets the mobile IP parameters.

**Parameters**

<i>pSPC</i> [IN]	<ul style="list-style-type: none"> <li>Six digit service programming code string</li> </ul>
------------------	---

<i>index</i> [IN]	<ul style="list-style-type: none"> <li>• Index of the profile to modify</li> </ul>
<i>pEnabled</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Enable profile? 0 - Disabled Nonzero - Enabled</li> </ul>
<i>pAddress</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Home IPv4 address</li> </ul>
<i>pPrimaryHA</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Primary home agent IPv4 address</li> </ul>
<i>pSecondaryHA</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Secondary home agent IPv4 address</li> </ul>
<i>pRevTunneling</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Enable reverse tunneling? 0 - Disabled Nonzero - Enabled</li> </ul>
<i>pNAI</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Network access identifier string</li> </ul>
<i>pHASPI</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) Home agent security parameter index</li> </ul>
<i>pAAASPI</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) AAA server security parameter index</li> </ul>
<i>pMNHA</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) MN-HA key string</li> </ul>
<i>pMNAAA</i> [IN]	<ul style="list-style-type: none"> <li>• (Optional) MN-AAA key string</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Technology Supported: CDMA  
Timeout: 2 seconds

**9.45.5.31 ULONG SLQSAutoConnect ( struct slqsaautoconnect \* pacreq )**

Returns auto connect settings

## Parameters

<i>slqsautoconnect</i> [- <i>IN</i> ]	<ul style="list-style-type: none"> <li>• SLQS auto connect settings</li> </ul>
--	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: CDMA/UMTS  
Device Supported: MC83x5, MC7700  
Timeout: 2 seconds

#### 9.45.5.32 ULONG SLQSCreateProfile ( struct CreateProfileIn \* *pReq*, struct CreateProfileOut \* *pResp* )

Create a new profile with the specified parameters. Note that some firmware versions do not support the optional Profile ID parameter. In this case an error will be returned and the caller can subsequently create a profile by specifying a NULL pointer for the Profile ID parameter. The Profile ID pertaining to the newly created profile is returned in the response structure (*pResp*).

## Parameters

<i>pReq</i> [IN]	<ul style="list-style-type: none"> <li>• SLQS Create profile Information</li> </ul>
<i>pResp</i> [OUT]	<ul style="list-style-type: none"> <li>• SLQS profile identifier information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS  
Device Supported: MC83x5, MC7700  
Timeout: 2 seconds

#### 9.45.5.33 ULONG SLQSDeleteProfile ( struct SLQSDeleteProfileParams \* *pProfileToDelete*, WORD \* *pExtendedErrorCode* )

Deletes a configured profile stored on the device. The deletion of a profile does not affect profile index assignments.

## Parameters

<i>pProfileToDelete</i> [IN]	<ul style="list-style-type: none"> <li>Information about the profile to be deleted.</li> <li>See <a href="#">SLQSDDeleteProfileParams</a> for more details.</li> </ul>
<i>pExtendedErrorCode</i> [OUT]	<ul style="list-style-type: none"> <li>The extended error code received from DS Profile subsystem of type eWDS_ERR_PROFILE_REG_XXX.</li> <li>Error code will only be present if error code eQCWWAN_ERR_QMI_EXTENDED_INTERNAL is returned by device.</li> <li>See <a href="#">qm_wds_ds_profile_extended_err_codes</a> enum in <a href="#">qmerrno.h</a> for received error description.</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_XXX error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_XXX error values.

## Note

Timeout: 2 seconds

#### 9.45.5.34 ULONG SLQSGet3GPPConfigItem ( slqs3GPPConfigItem \* pSLQS3GPPConfigItem )

Reads the 3gpp configuration item.

## Parameters

<i>pSLQS3GPPConfigItem</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">slqs3GPPConfigItem</a> for more information</li> </ul>
----------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_XXX error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_XXX error values

## Note

Technology Supported: UMTS/LTE  
Timeout: 2 seconds

#### 9.45.5.35 ULONG SLQSGetByteTotals ( struct WdsByteTotals \* pByteTotals )

This API request the device to fetch ByteTotals for IPV4 and IPV6.

## Parameters

<i>pByteTotals</i> [IN/-OUT]	<ul style="list-style-type: none"> <li>See <a href="#">WdsByteTotals</a> for more information</li> </ul>
------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

#### 9.45.5.36 ULONG SLQSGetConnectionRate ( struct WdsConnectionRate \* pConnectionRate )

This API request the device to fetch ConnectionRate. It can be used for both mono and multiple PDN use case.

## Parameters

<i>pConnectionRate</i> [IN/OUT]	<ul style="list-style-type: none"> <li>See <a href="#">WdsConnectionRate</a> for more information</li> </ul>
---------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS/CDMA  
Device Supported: MC77XX  
Timeout: 2 seconds

#### 9.45.5.37 ULONG SLQSGetCurrDataSystemStat ( CurrDataSysStat \* pCurrDataSysStat )

This API request the device to fetch current data system status.

## Parameters

<i>pCurrDataSysStat</i> [IN/OUT]	<ul style="list-style-type: none"> <li>See <a href="#">CurrDataSysStat</a> for more information</li> </ul>
----------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 5 seconds\n

9.45.5.38 **ULONG** SLQSGGetCurrentChannelRate ( **WDSSWICurrentChannelRates** \* *pRates*, **BYTE** *instance* )

This API Queries current bitrate of a packet data connection.



## Parameters

<i>pRates</i>	[IN] <ul style="list-style-type: none"> <li>See <a href="#">WDSSWICurrentChannelRates</a> for more information</li> </ul>
---------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

This feature depends on custom feature setting IPCHANNELRATEEN which can be set via SLQSSetCust-Features

Timeout: 2 seconds

#### 9.45.5.39 ULONG SLQSGetDataBearerTechnology ( QmiWDSDataBearers \* pDataBearers, BYTE instance )

Retrieves the data bearer technology values for current and/or last data calls. The device must be in a data call for this function to execute successfully.

## Parameters

<i>qmiWDSData-Bearers[OUT]</i>	<ul style="list-style-type: none"> <li>Indicates the current and the last call data bearer technology. Should not be NULL, on input.</li> </ul>
<i>instance</i>	<ul style="list-style-type: none"> <li>PDP instance</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS/CDMA  
 Device Supported: MC7750,GOBI,MC7700  
 Timeout: 2 seconds

#### 9.45.5.40 ULONG SLQSGetDataBearerTechnologyExt ( DataBearerTechExt \* pDataBearerTech, BYTE instance )

This API Get Data Bearer Technology. This is a new API to replace API [GetDataBearerTechnology\(\)](#). see the description of [GetDataBearerTechnology\(\)](#) to get more information

## Parameters

<i>pDataBearer-Tech</i>	[IN] <ul style="list-style-type: none"> <li>See <a href="#">DataBearerTechExt</a> for more information</li> </ul>
<i>instance</i>	[IN] <ul style="list-style-type: none"> <li>PDP instance</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

**9.45.5.41** **ULONG** SLQSGetDUNCallInfo ( **getDUNCallInfoReq** \* *pGetDUNCallInfoReq*, **getDUNCallInfoResp** \* *pGetDUNCallInfoResp* )

This API queries the current modem connection status.

## Parameters

<i>pGetDUNCall-InfoReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">getDUNCallInfoReq</a> for more information</li> </ul>
<i>pGetDUNCall-InfoResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">getDUNCallInfoResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 seconds

**9.45.5.42** **ULONG** SLQSGetPacketStatistics ( **struct WdsPktStatisticsReq** \* *pStatMask*, **struct WdsPktStatisticsResp** \* *pPktStatistics* )

This API request the device to fetch current packet transfer counter values from the device

•

## Parameters

<i>pStatMask</i> [IN]	– See <a href="#">WdsPktStatisticsReq</a> for more information
<i>pPktStatistics</i> [OUT]	– See <a href="#">WdsPktStatisticsResp</a> for more information

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 5 seconds\n

**9.45.5.43** `ULONG SLQSGetProfile ( ULONG profileType, BYTE profileId, ULONG * pPDPTType, ULONG * pIPAddress, ULONG * pPrimaryDNS, ULONG * pSecondaryDNS, ULONG * pAuthentication, BYTE nameSize, CHAR * pName, BYTE apnSize, CHAR * pAPNName, BYTE userSize, CHAR * pUsername, WORD * pExtendedErrorCode )`

Reads the profile settings from the device for the specified profile id.

## Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>Type of profile <ul style="list-style-type: none"> <li>0 - UMTS</li> </ul> </li> </ul>
<i>profileId</i>	<ul style="list-style-type: none"> <li>Index of the configured profile for which settings are read <ul style="list-style-type: none"> <li>Value between 1 - 16 (EM/MC73xx or earlier)</li> <li>Value between 1 - 24 (EM/MC74xx onwards)</li> </ul> </li> </ul>
<i>pPDPTType</i> [OUT]	<ul style="list-style-type: none"> <li>Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile <ul style="list-style-type: none"> <li>0 - PDP-IP (IPv4)</li> </ul> </li> </ul>
<i>pIPAddress</i> [OUT]	<ul style="list-style-type: none"> <li>Preferred IPv4 address to be assigned to device</li> </ul>
<i>pPrimaryDNS</i> [OUT]	<ul style="list-style-type: none"> <li>Primary DNS Ipv4 address preference</li> </ul>

<i>pSecondaryDNS[OUT]</i>	<ul style="list-style-type: none"> <li>• Secondary DNS Ipv4 address preference</li> </ul>
<i>pAuthentication[OUT]</i>	<ul style="list-style-type: none"> <li>• Bitmap that indicates authentication algorithm preference             <ul style="list-style-type: none"> <li>– 0x00000001 - PAP preference                 <ul style="list-style-type: none"> <li>* 0 - Never performed</li> <li>* 1 - May be performed</li> </ul> </li> <li>– 0x00000002 - CHAP preference                 <ul style="list-style-type: none"> <li>* 0 - Never performed</li> <li>* 1 - May be performed</li> </ul> </li> <li>– All other bits are reserved and must be set to 0</li> <li>– If more than 1 bit is set, then device decides which authentication procedure is performed while setting up data session e.g. the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul>
<i>nameSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that profile name array can contain.</li> </ul>
<i>pName[OUT]</i>	<ul style="list-style-type: none"> <li>• Profile name</li> </ul>
<i>apnSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that APN name array can contain</li> </ul>
<i>pAPNName[OUT]</i>	<ul style="list-style-type: none"> <li>• Access point name. NULL-terminated string parameter that is a logical name used to select GGSN and external packet data network.</li> <li>• If value is NULL or omitted, then subscription default value will be requested.</li> </ul>
<i>userSize</i>	<ul style="list-style-type: none"> <li>• Maximum number of characters (including NULL terminator) that username array can contain.</li> </ul>
<i>pUsername[OUT]</i>	<ul style="list-style-type: none"> <li>• Username used during network authentication</li> </ul>
<i>pExtendedErrorCode</i>	<ul style="list-style-type: none"> <li>• The extended error code received from DS Profile subsystem of type eWDS_ERR_PROFILE_REG_XXX.</li> <li>• Error code will only be present if error code eQCWWAN_ERR_QMI_EXTENDED_INTERNAL is returned by device.</li> <li>• See <a href="#">qm_wds_ds_profile_extended_err_codes</a> enum in <a href="#">qmerrno.h</a> for received error description.</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.45.5.44 ULONG SLQSGetProfileSettings ( GetProfileSettingIn \* pReq, GetProfileSettingOut \* pResp )**

Retrieves a profile(3GPP/3GPP2) with the specified parameters.

**Parameters**

<i>pReq[IN]</i>	<ul style="list-style-type: none"><li>• details of the profile to be fetched</li><li>• See <a href="#">GetProfileSettingIn</a> for more information</li></ul>
<i>pResp[OUT]</i>	<ul style="list-style-type: none"><li>• The profile settings and/or extended error code returned by the device based on input parameters.</li><li>• See <a href="#">GetProfileSettingOut</a> for more information</li></ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

**9.45.5.45 ULONG SLQSGetRuntimeSettings ( struct WdsRunTimeSettings \* pRunTimeSettings )**

Returns the packet data session settings currently in use.

**Parameters**

<i>pRunTime-Settings[OUT]</i>	<ul style="list-style-type: none"><li>• SLQS Runtime Settings Information</li></ul>
-------------------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

#### 9.45.5.46 **ULONG SLQSGetSessionState ( ULONG \* pStateV4, ULONG \* pStateV6, BYTE instance )**

Returns the state of the current packet data session.

**Parameters**

<i>pStateV4[OUT]</i>	<ul style="list-style-type: none"> <li>• Current link status for IPV4 Session <ul style="list-style-type: none"> <li>– 1 - DISCONNECTED</li> <li>– 2 - CONNECTED</li> <li>– 3 - SUSPENDED (not supported)</li> <li>– 4 - AUTHENTICATING</li> </ul> </li> </ul>
<i>pStateV6[OUT]</i>	<ul style="list-style-type: none"> <li>• Current link status for IPV6 Session <ul style="list-style-type: none"> <li>– 1 - DISCONNECTED</li> <li>– 2 - CONNECTED</li> <li>– 3 - SUSPENDED (not supported)</li> <li>– 4 - AUTHENTICATING</li> </ul> </li> </ul>
<i>instance</i>	<ul style="list-style-type: none"> <li>• PDP instance</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 2 seconds

#### 9.45.5.47 **ULONG SLQSModifyProfile ( struct ModifyProfileIn \* pReq, struct ModifyProfileOut \* pResp )**

Modify a profile(3GPP/3GPP2) with the specified parameters.

## Parameters

<i>pReq[IN]</i>	<ul style="list-style-type: none"> <li>Contains parameters which can be modified</li> </ul>
<i>pResp[OUT]</i>	<ul style="list-style-type: none"> <li>Contains parameters which indicates modification success or failure</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

9.45.5.48 **ULONG SLQSResetPacketStatics ( )**

This API request the device to reset packet data transfer statistics.

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

9.45.5.49 **ULONG SLQSSet3GPPConfigItem ( slqs3GPPConfigItem \* pSLQS3GPPConfigItem )**

Sets the 3gpp configuration item.

## Parameters

<i>pSLQS3GPP-ConfigItem[IN]</i>	<ul style="list-style-type: none"> <li>See <a href="#">slqs3GPPConfigItem</a> for more information</li> </ul>
---------------------------------	---

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS/LTE

Timeout: 2 seconds

9.45.5.50 `ULONG SLQSSetProfile ( ULONG profileType, BYTE profileId, ULONG * pPDPTType, ULONG * pIPAddress,  
ULONG * pPrimaryDNS, ULONG * pSecondaryDNS, ULONG * pAuthentication, CHAR * pName, CHAR *  
pAPNName, CHAR * pUsername, CHAR * pPassword )`

Writes the profile settings for the specified profile Id.



## Parameters

<i>profileType</i>	<ul style="list-style-type: none"> <li>Type of profile <ul style="list-style-type: none"> <li>0 - UMTS</li> </ul> </li> </ul>
<i>profileId</i>	<ul style="list-style-type: none"> <li>Profile number to be modified <ul style="list-style-type: none"> <li>Value between 1 - 16 (EM/MC73xx or earlier)</li> <li>Value between 1 - 24 (EM/MC74xx onwards)</li> </ul> </li> </ul>
<i>pPDPTType[IN]</i>	<ul style="list-style-type: none"> <li>Packet Data Protocol (PDP) type specifies the type of data payload exchanged over the air link when the packet data session is established with this profile (optional) <ul style="list-style-type: none"> <li>0 - PDP-IP (IPv4)</li> </ul> </li> </ul>
<i>pIPAddress[IN]</i>	<ul style="list-style-type: none"> <li>Preferred IPv4 address to be assigned to device (optional)</li> </ul>
<i>pPrimaryDNS[IN]</i>	<ul style="list-style-type: none"> <li>Primary DNS Ipv4 address preference (optional)</li> </ul>
<i>pSecondaryDNS[IN]</i>	<ul style="list-style-type: none"> <li>Secondary DNS Ipv4 address preference (optional)</li> </ul>
<i>pAuthentication[IN]</i>	<ul style="list-style-type: none"> <li>Bitmap that indicates authentication algorithm preference (optional) <ul style="list-style-type: none"> <li>0x00000001 - PAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>0x00000002 - CHAP preference <ul style="list-style-type: none"> <li>0 - Never performed</li> <li>1 - May be performed</li> </ul> </li> <li>All other bits are reserved and must be set to 0</li> <li>If more than 1 bit is set, then device decides which authentication procedure is performed while setting up data session e.g. the device may have a policy to select the most secure authentication mechanism.</li> </ul> </li> </ul>

<i>pName</i> [IN]	<ul style="list-style-type: none"> <li>• profile Name (optional)</li> </ul>
<i>pAPNName</i> [IN]	<ul style="list-style-type: none"> <li>• Access point name. NULL-terminated string parameter that is a logical name used to select GGSN and external packet data network (optional)</li> <li>• If value is NULL or omitted, then subscription default value will be requested.</li> </ul>
<i>pUsername</i> [IN]	<ul style="list-style-type: none"> <li>• Username used during network authentication (optional)</li> </ul>
<i>pPassword</i> [IN]	<ul style="list-style-type: none"> <li>• Password used during network authentication (optional)</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout is 2 seconds.

#### 9.45.5.51 ULONG SLQSSGetDHCPv4ClientConfig ( WdsDHCPv4Config \* *pReqResp* )

This API gets the DHCP Client V4 Configuration.

**Parameters**

<i>pReq</i>	[IN]	<ul style="list-style-type: none"> <li>• See <a href="#">WdsDHCPv4Config</a> for more information</li> </ul>
-------------	------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

#### 9.45.5.52 ULONG SLQSSGetLoopback ( WDSGetLoopbackData \* *data* )

This API to Get the value of loopback mode and multiplier.

## Parameters

<i>pReq</i>	[IN]
<ul style="list-style-type: none"> <li>• See <a href="#">WDSGetLoopbackData</a> for more information</li> </ul>	

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

#### 9.45.5.53 ULONG SLQSSetDHCPv4ClientConfig ( WdsDHCPv4Config \* *pReq* )

This API sets the DHCP Client V4 Configuration.

## Parameters

<i>pReq</i>	[IN]
<ul style="list-style-type: none"> <li>• See <a href="#">WdsDHCPv4Config</a> for more information</li> </ul>	

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

#### 9.45.5.54 ULONG SLQSSetLoopback ( WDSSetLoopbackData \* *pReq* )

This API to Enable/disable Data Loopback Mode and set the value of loopback multiplier.

## Parameters

<i>pReq</i>	[IN]
<ul style="list-style-type: none"> <li>• See <a href="#">WDSSetLoopbackData</a> for more information</li> </ul>	

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

Timeout: 2 seconds\n

#### 9.45.5.55 ULONG SLQSStartStopDataSession ( struct ssdatasession\_params \* *pin* )

Starts or stops a 3GPP/3GPP2 data session on a preconfigured profile. To set the IP family for the data session, execute SLQSSetIPFamilyPreference prior to calling this API.

## Parameters

<i>pin</i> [IN]	<ul style="list-style-type: none"><li>• <a href="#">ssdatasession_params</a> structure</li><li>• See <a href="#">ssdatasession_params</a> for more details</li></ul>
-----------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 5 Minutes

Use [SLQSSetProfile](#) to configure 3GPP profiles

**9.45.5.56    ULONG SLQSWdsGoActive ( void )**

Forces the device to immediately reestablish the traffic channel on the serving radio interface

## Parameters

<i>None</i>	
-------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

This channel can go dormant any time after it has been reactivated. There is no assurance that the channel remains active for any guaranteed period. Timeout: 5 seconds

**9.45.5.57    ULONG SLQSWdsGoDormant ( void )**

Forces the device to immediately drop the traffic channel on the serving radio interface

## Parameters

<i>None</i>	
-------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

This channel can be reactivated as soon as data is sent over the network interface. There is no assurance that the channel remains dormant for any guaranteed period. Timeout: 5 seconds

#### 9.45.5.58 ULONG SLQSWdsSetEventReport ( wdsSetEventReportReq \* pSetEventReportReq )

This API sets the wireless data connection state reporting conditions for the requesting control point.

## Parameters

<i>pSetEventReportReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">wdsSetEventReportReq</a> for more information.</li> </ul>
--------------------------------	--

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 2 seconds

The control point event reporting state variables are modified to reflect the settings indicated in the request message. The service maintains a set of state variables for each control point. Relevant wireless data connection state changes are communicated to the registered WDS control point via the SLQSWdsSetEventReport-CallBack. The AT command equivalents to this command are AT+CMER, AT+CIND, and AT+CIEV

#### 9.45.5.59 ULONG SLQSWdsSwpDPRuntimeSettings ( swiPDPRuntimeSettingsReq \* pPDPRuntimeSettingsReq, swiPDPRuntimeSettingsResp \* pPDPRuntimeSettingsResp )

This API requests the device to return the active PDP context associated with a context id.

## Parameters

<i>pPDPRuntimeSettingsReq</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">swiPDPRuntimeSettingsReq</a> for more information</li> </ul>
<i>pPDPRuntimeSettingsResp</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">swiPDPRuntimeSettingsResp</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

see [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Technology Supported: UMTS/CDMA  
 Device Supported: MC77XX  
 Timeout: 2 seconds  
 The AT command equivalent to this command is AT+CGCONTRDP

9.45.5.60 **BOOL** WDS\_IsGobiDevice ( )

## 9.46 qaNasGetRFBandInfo.h File Reference

### Data Structures

- struct [QmiNasGetRFBandInfoResp](#)

### Enumerations

- enum [eQMI\\_NAS\\_GET\\_RF\\_INFO\\_RESP](#) { [eTLV\\_RF\\_BAND\\_INFO](#) = 0x01 }

### Functions

- enum [eQCWWANError](#) [PkQmiNasGetRFBandInfo](#) ([WORD](#) \**pMlength*, [BYTE](#) \**pBuffer*)
- enum [eQCWWANError](#) [UpkQmiNasGetRFBandInfo](#) ([BYTE](#) \**pMdmResp*, struct [QmiNasGetRFBandInfoResp](#) \**pApiResp*)

#### 9.46.1 Enumeration Type Documentation

9.46.1.1 enum [eQMI\\_NAS\\_GET\\_RF\\_INFO\\_RESP](#)

##### Enumerator

***eTLV\_RF\_BAND\_INFO***

#### 9.46.2 Function Documentation

9.46.2.1 enum [eQCWWANError](#) [PkQmiNasGetRFBandInfo](#) ( [WORD](#) \* *pMlength*, [BYTE](#) \* *pBuffer* )

9.46.2.2 enum [eQCWWANError](#) [UpkQmiNasGetRFBandInfo](#) ( [BYTE](#) \* *pMdmResp*, struct [QmiNasGetRFBandInfoResp](#) \* *pApiResp* )

## 9.47 qaNasPerformNetworkScan.h File Reference

### Data Structures

- struct [QmiNas3GppNetworkInfo](#)
- struct [QmiNasPerformNetworkScanResp](#)

### Macros

- #define [QMI\\_NAS\\_NETSTATUS\\_MASK](#) 0x03
- #define [QMI\\_NAS\\_MAX\\_INSTANCES](#) 20
- #define [INDEX\\_ZERO](#) 0

- #define [ROAMING\\_INDEX](#) 2
- #define [FORBIDDEN\\_INDEX](#) 4
- #define [PREFERRED\\_INDEX](#) 6
- #define [MAX\\_DESCRIPTION\\_LENGTH](#) 255

## Enumerations

- enum [eQMI\\_NAS\\_PERFORM\\_NETWORK\\_SCAN\\_RESP](#) { [eTLV\\_3GPP\\_NETWORK\\_INFO](#) = 0x10 }

## Functions

- enum [eQCWWANError](#) [PkQmiNasPerformNetworkScan](#) (WORD \*pMlength, BYTE \*pParamField)
- enum [eQCWWANError](#) [UpkQmiNasPerformNetworkScan](#) (BYTE \*pMdmResp, struct [QmiNasPerformNetworkScanResp](#) \*pAipResp)

### 9.47.1 Macro Definition Documentation

9.47.1.1 #define [FORBIDDEN\\_INDEX](#) 4

9.47.1.2 #define [INDEX\\_ZERO](#) 0

9.47.1.3 #define [MAX\\_DESCRIPTION\\_LENGTH](#) 255

9.47.1.4 #define [PREFERRED\\_INDEX](#) 6

9.47.1.5 #define [QMI\\_NAS\\_MAX\\_INSTANCES](#) 20

9.47.1.6 #define [QMI\\_NAS\\_NETSTATUS\\_MASK](#) 0x03

9.47.1.7 #define [ROAMING\\_INDEX](#) 2

### 9.47.2 Enumeration Type Documentation

9.47.2.1 enum [eQMI\\_NAS\\_PERFORM\\_NETWORK\\_SCAN\\_RESP](#)

Enumerator

**[eTLV\\_3GPP\\_NETWORK\\_INFO](#)**

### 9.47.3 Function Documentation

9.47.3.1 enum [eQCWWANError](#) [PkQmiNasPerformNetworkScan](#) ( WORD \* *pMlength*, BYTE \* *pParamField* )

9.47.3.2 enum [eQCWWANError](#) [UpkQmiNasPerformNetworkScan](#) ( BYTE \* *pMdmResp*, struct [QmiNasPerformNetworkScanResp](#) \* *pAipResp* )

## 9.48 qmerrno.h File Reference

## Enumerations

- enum eQCWWANError {
  - eQCWWAN\_ERR\_ENUM\_BEGIN = -1,
  - eQCWWAN\_ERR\_NONE,
  - eQCWWAN\_ERR\_GENERAL,
  - eQCWWAN\_ERR\_INTERNAL,
  - eQCWWAN\_ERR\_MEMORY,
  - eQCWWAN\_ERR\_INVALID\_ARG,
  - eQCWWAN\_ERR\_BUFFER\_SZ,
  - eQCWWAN\_ERR\_NO\_DEVICE,
  - eQCWWAN\_ERR\_INVALID\_DEVID,
  - eQCWWAN\_ERR\_NO\_CONNECTION,
  - eQCWWAN\_ERR\_QMI\_IFACE,
  - eQCWWAN\_ERR\_QMI\_CONNECT,
  - eQCWWAN\_ERR\_QMI\_REQ\_SCH,
  - eQCWWAN\_ERR\_QMI\_REQ,
  - eQCWWAN\_ERR\_QMI\_RSP,
  - eQCWWAN\_ERR\_QMI\_REQ\_TO,
  - eQCWWAN\_ERR\_QMI\_RSP\_TO,
  - eQCWWAN\_ERR\_MALFORMED\_QMI\_RSP,
  - eQCWWAN\_ERR\_INVALID\_QMI\_RSP,
  - eQCWWAN\_ERR\_INVALID\_FILE,
  - eQCWWAN\_ERR\_FILE\_OPEN,
  - eQCWWAN\_ERR\_FILE\_COPY,
  - eQCWWAN\_ERR\_OFFLINE = 27,
  - eQCWWAN\_ERR\_RESET,
  - eQCWWAN\_ERR\_NO\_SIGNAL,
  - eQCWWAN\_ERR\_MULTIPLE\_DEVICES,
  - eQCWWAN\_ERR\_DRIVER,
  - eQCWWAN\_ERR\_NO\_CANCELABLE\_OP,
  - eQCWWAN\_ERR\_CANCEL\_OP,
  - eQCWWAN\_ERR\_API\_MUTEX\_TIMEOUT,
  - eQCWWAN\_ERR\_PDU\_GENERATION,
  - eQCWWAN\_ERR\_INVALID\_XID,
  - eQCWWAN\_ERR\_MULTIPLE\_SMS\_UNSUPPORTED,
  - eQCWWAN\_ERR\_ENUM\_END,
  - eQCWWAN\_ERR\_QMI\_OFFSET = 1000,
  - eQCWWAN\_ERR\_QMI\_MALFORMED\_MSG = 1001,
  - eQCWWAN\_ERR\_QMI\_NO\_MEMORY,
  - eQCWWAN\_ERR\_QMI\_INTERNAL,
  - eQCWWAN\_ERR\_QMI\_ABORTED,
  - eQCWWAN\_ERR\_QMI\_CLIENT\_IDS\_EXHAUSTED,
  - eQCWWAN\_ERR\_QMI\_UNABORTABLE\_TRANSACTION,
  - eQCWWAN\_ERR\_QMI\_INVALID\_CLIENT\_ID,
  - eQCWWAN\_ERR\_QMI\_NO\_THRESHOLDS,
  - eQCWWAN\_ERR\_QMI\_INVALID\_HANDLE,
  - eQCWWAN\_ERR\_QMI\_INVALID\_PROFILE,
  - eQCWWAN\_ERR\_QMI\_INVALID\_PINID,
  - eQCWWAN\_ERR\_QMI\_INCORRECT\_PIN,
  - eQCWWAN\_ERR\_QMI\_NO\_NETWORK\_FOUND,
  - eQCWWAN\_ERR\_QMI\_CALL\_FAILED,
  - eQCWWAN\_ERR\_QMI\_OUT\_OF\_CALL,
  - eQCWWAN\_ERR\_QMI\_NOT\_PROVISIONED,
  - eQCWWAN\_ERR\_QMI\_MISSING\_ARG,
  - eQCWWAN\_ERR\_QMI\_ARG\_TOO\_LONG = 1019,
  - eQCWWAN\_ERR\_QMI\_INVALID\_TX\_ID = 1022,
  - eQCWWAN\_ERR\_QMI\_DEVICE\_IN\_USE,
  - eQCWWAN\_ERR\_QMI\_OP\_NETWORK\_UNSUPPORTED,
  - eQCWWAN\_ERR\_QMI\_OP\_DEVICE\_UNSUPPORTED,
  - eQCWWAN\_ERR\_QMI\_NO\_EFFECT,
  - eQCWWAN\_ERR\_QMI\_NO\_FREE\_PROFILE,
  - eQCWWAN\_ERR\_QMI\_INVALID\_PDP\_TYPE,
  - eQCWWAN\_ERR\_QMI\_INVALID\_TECH\_PREF,
  - eQCWWAN\_ERR\_QMI\_INVALID\_PROFILE\_TYPE



```

    eQCWWAN_ERR_QMI_WIDTH = 0xFFFF }
• enum qm_wds_ds_profile_extended_err_codes {
    eWDS_ERR_PROFILE_REG_RESULT_FAIL = 1,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_INVALID_HNDL,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_INVALID_OP,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_INVALID_PROFILE_TYPE,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_INVALID_PROFILE_NUM,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_INVALID_IDENT,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_INVALID,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_LIB_NOT_INITED,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_LEN_INVALID,
    eWDS_ERR_PROFILE_REG_RESULT_LIST_END,
    eWDS_ERR_PROFILE_REG_RESULT_ERR_INVALID_SUBS_ID,
    eWDS_ERR_PROFILE_REG_INVALID_PROFILE_FAMILY,
    eWDS_ERR_PROFILE_REG_3GPP_INVALID_PROFILE_FAMILY = 1001,
    eWDS_ERR_PROFILE_REG_3GPP_ACCESS_ERR,
    eWDS_ERR_PROFILE_REG_3GPP_CONTEXT_NOT_DEFINED,
    eWDS_ERR_PROFILE_REG_3GPP_VALID_FLAG_NOT_SET,
    eWDS_ERR_PROFILE_REG_3GPP_READ_ONLY_FLAG_SET,
    eWDS_ERR_PROFILE_REG_3GPP_ERR_OUT_OF_PROFILES,
    eWDS_ERR_PROFILE_REG_3GPP2_ERR_INVALID_IDENT_FOR_PROFILE = 1101,
    eWDS_ERR_PROFILE_REG_END }

```

## 9.48.1 Enumeration Type Documentation

### 9.48.1.1 enum eQCWWANError

#### QMI Error Code Enumeration

Enumerator

```

eQCWWAN_ERR_ENUM_BEGIN
eQCWWAN_ERR_NONE 00 - Success
eQCWWAN_ERR_GENERAL 01 - General error
eQCWWAN_ERR_INTERNAL 02 - Internal error
eQCWWAN_ERR_MEMORY 03 - Memory error
eQCWWAN_ERR_INVALID_ARG 04 - Invalid argument
eQCWWAN_ERR_BUFFER_SZ 05 - Buffer too small
eQCWWAN_ERR_NO_DEVICE 06 - Unable to detect WWAN device
eQCWWAN_ERR_INVALID_DEVID 07 - Invalid WWAN device ID
eQCWWAN_ERR_NO_CONNECTION 08 - No connection to WWAN device
eQCWWAN_ERR_QMI_IFACE 09 - Unable to obtain QMI interface
eQCWWAN_ERR_QMI_CONNECT 10 - Unable to connect to QMI interface
eQCWWAN_ERR_QMI_REQ_SCH 11 - Unable to schedule QMI request
eQCWWAN_ERR_QMI_REQ 12 - Error sending QMI request
eQCWWAN_ERR_QMI_RSP 13 - Error receiving QMI response
eQCWWAN_ERR_QMI_REQ_TO 14 - Timeout while sending QMI request
eQCWWAN_ERR_QMI_RSP_TO 15 - Timeout while receiving QMI response
eQCWWAN_ERR_MALFORMED_QMI_RSP 16 - Malformed QMI response received
eQCWWAN_ERR_INVALID_QMI_RSP 17 - Invalid QMI response received
eQCWWAN_ERR_INVALID_FILE 18 - Invalid file path
eQCWWAN_ERR_FILE_OPEN 19 - Unable to open file

```

**eQCWWAN\_ERR\_FILE\_COPY** 20 - Unable to copy file  
**eQCWWAN\_ERR\_OFFLINE** 27 - Unable to set WWAN device offline  
**eQCWWAN\_ERR\_RESET** 28 - Unable to reset WWAN device  
**eQCWWAN\_ERR\_NO\_SIGNAL** 29 - No available signal  
**eQCWWAN\_ERR\_MULTIPLE\_DEVICES** 30 - Multiple WWAN devices detected  
**eQCWWAN\_ERR\_DRIVER** 31 - Error interfacing to driver  
**eQCWWAN\_ERR\_NO\_CANCELABLE\_OP** 32 - No cancelable operation is pending  
**eQCWWAN\_ERR\_CANCEL\_OP** 33- Error canceling outstanding operation  
**eQCWWAN\_ERR\_API\_MUTEX\_TIMEOUT** 34- api mutex lock timeout  
**eQCWWAN\_ERR\_PDU\_GENERATION** 35- PDU generation error  
**eQCWWAN\_ERR\_INVALID\_XID** 36- Invalid transaction id  
**eQCWWAN\_ERR\_MULTIPLE\_SMS\_UNSUPPORTED** 37- Unsupported multiple SMS  
**eQCWWAN\_ERR\_ENUM\_END** End of SLQS SDK specific error codes  
**eQCWWAN\_ERR\_QMI\_OFFSET** 1000 - This is not an error code but the offset from which mapped QMI error codes start from  
**eQCWWAN\_ERR\_QMI\_MALFORMED\_MSG** 1001 - Malformed or Corrupted QMI msg  
**eQCWWAN\_ERR\_QMI\_NO\_MEMORY** 1002 - Device could not allocate memory for QMI Resp  
**eQCWWAN\_ERR\_QMI\_INTERNAL** 1003 - Unexpected error occurred during processing  
**eQCWWAN\_ERR\_QMI\_ABORTED** 1004 - Processing aborted  
**eQCWWAN\_ERR\_QMI\_CLIENT\_IDS\_EXHAUSTED** 1005 - QMI client IDs have been exhausted  
**eQCWWAN\_ERR\_QMI\_UNABORTABLE\_TRANSACTION** 1006 - Unable to abort QMI transaction  
**eQCWWAN\_ERR\_QMI\_INVALID\_CLIENT\_ID** 1007 - Invalid QMI client ID  
**eQCWWAN\_ERR\_QMI\_NO\_THRESHOLDS** 1008 - No thresholds were provided  
**eQCWWAN\_ERR\_QMI\_INVALID\_HANDLE** 1009 - Invalid Handle provided in the QMI request  
**eQCWWAN\_ERR\_QMI\_INVALID\_PROFILE** 1010 - Profile specified is invalid  
**eQCWWAN\_ERR\_QMI\_INVALID\_PINID** 1011 - Invalid PIN ID specified  
**eQCWWAN\_ERR\_QMI\_INCORRECT\_PIN** 1012 - Incorrect PIN ID specified  
**eQCWWAN\_ERR\_QMI\_NO\_NETWORK\_FOUND** 1013 - No network found  
**eQCWWAN\_ERR\_QMI\_CALL\_FAILED** 1014 - Call failed  
**eQCWWAN\_ERR\_QMI\_OUT\_OF\_CALL** 1015 - Device is not in a call  
**eQCWWAN\_ERR\_QMI\_NOT\_PROVISIONED** 1016 - Requested information element not provisioned on device  
**eQCWWAN\_ERR\_QMI\_MISSING\_ARG** 1017 - Mandatory QMI TLV not provided  
**eQCWWAN\_ERR\_QMI\_ARG\_TOO\_LONG** 1019 - Arg passed in QMI TLV larger than available storage in device  
**eQCWWAN\_ERR\_QMI\_INVALID\_TX\_ID** 1022 - Invalid TX ID specified  
**eQCWWAN\_ERR\_QMI\_DEVICE\_IN\_USE** 1023 - Device currently in a call  
**eQCWWAN\_ERR\_QMI\_OP\_NETWORK\_UNSUPPORTED** 1024 - The selected operation is not supported by the network  
**eQCWWAN\_ERR\_QMI\_OP\_DEVICE\_UNSUPPORTED** 1025 - The selected operation is not supported by the device  
**eQCWWAN\_ERR\_QMI\_NO\_EFFECT** 1026 - Requested operation would have no effect  
**eQCWWAN\_ERR\_QMI\_NO\_FREE\_PROFILE** 1027 - No space for a profile is available  
**eQCWWAN\_ERR\_QMI\_INVALID\_PDP\_TYPE** 1028 - Invalid PDP type specified  
**eQCWWAN\_ERR\_QMI\_INVALID\_TECH\_PREF** 1029 - Invalid technology preference specified  
**eQCWWAN\_ERR\_QMI\_INVALID\_PROFILE\_TYPE** 1030 - Invalid profile type specified

**eQCWWAN\_ERR\_QMI\_INVALID\_SERVICE\_TYPE** 1031 - Invalid service type specified

**eQCWWAN\_ERR\_QMI\_INVALID\_REGISTER\_ACTION** 1032 - Invalid register action specified

**eQCWWAN\_ERR\_QMI\_INVALID\_PS\_ATTACH\_ACTION** 1033 - Invalid PS attach/detach action specified

**eQCWWAN\_ERR\_QMI\_AUTHENTICATION\_FAILED** 1034 - Authentication of supplied information element failed

**eQCWWAN\_ERR\_QMI\_PIN\_BLOCKED** 1035 - PIN is blocked; an unblock operation needs to be issued

**eQCWWAN\_ERR\_QMI\_PIN\_PERM\_BLOCKED** 1036 - PIN is permanently blocked; the UIM is unusable

**eQCWWAN\_ERR\_QMI\_SIM\_NOT\_INITIALIZED** 1037 - UIM initialization has not completed

**eQCWWAN\_ERR\_QMI\_MAX\_QOS\_REQUESTS\_IN\_USE** 1038 - Max QOS requests are used

**eQCWWAN\_ERR\_QMI\_INCORRECT\_FLOW\_FILTER** 1039 - The Flow filter is incorrect

**eQCWWAN\_ERR\_QMI\_NETWORK\_QOS\_UNAWARE** 1040 - Network unaware of the QOS requested

**eQCWWAN\_ERR\_QMI\_INVALID\_ID** 1041 - Invalid QOS ID

**eQCWWAN\_ERR\_QMI\_INVALID\_QOS\_ID** 1041 - Invalid QOS ID

**eQCWWAN\_ERR\_QMI\_REQUESTED\_NUM\_UNSUPPORTED** 1042 - The request number is not supported

**eQCWWAN\_ERR\_QMI\_INTERFACE\_NOT\_FOUND** 1043 - Unable to find the interface

**eQCWWAN\_ERR\_QMI\_FLOW\_SUSPENDED** 1044 - Flow suspended

**eQCWWAN\_ERR\_QMI\_INVALID\_DATA\_FORMAT** 1045 - Data format is invalid

**eQCWWAN\_ERR\_QMI\_GENERAL** 1046 - General error

**eQCWWAN\_ERR\_QMI\_UNKNOWN** 1047 - Unknown error

**eQCWWAN\_ERR\_QMI\_INVALID\_ARG** 1048 - A specified argument is invalid

**eQCWWAN\_ERR\_QMI\_INVALID\_INDEX** 1049 - A specified index is invalid

**eQCWWAN\_ERR\_QMI\_NO\_ENTRY** 1050 - No information element exists at specified memory designation

**eQCWWAN\_ERR\_QMI\_DEVICE\_STORAGE\_FULL** 1051 - The memory storage specified in the request is full

**eQCWWAN\_ERR\_QMI\_DEVICE\_NOT\_READY** 1052 - Device not in a ready state

**eQCWWAN\_ERR\_QMI\_NETWORK\_NOT\_READY** 1053 - Network not in a ready state

**eQCWWAN\_ERR\_QMI\_CAUSE\_CODE** 1054 - Error provided in SMS cause code

**eQCWWAN\_ERR\_QMI\_MESSAGE\_NOT\_SENT** 1055 - The message could not be sent

**eQCWWAN\_ERR\_QMI\_MESSAGE\_DELIVERY\_FAILURE** 1056 - The message could not be delivered

**eQCWWAN\_ERR\_QMI\_INVALID\_MESSAGE\_ID** 1057 - The message ID specified for the message is invalid

**eQCWWAN\_ERR\_QMI\_ENCODING** 1058 - The message is not encoded properly

**eQCWWAN\_ERR\_QMI\_AUTHENTICATION\_LOCK** 1059 - Maximum number of authentication failures has been reached

**eQCWWAN\_ERR\_QMI\_INVALID\_TRANSITION** 1060 - Operating mode transition from the current mode is invalid

**eQCWWAN\_ERR\_QMI\_NOT\_A\_MCAST\_IFACE** 1061 - The intercase is not muticast

**eQCWWAN\_ERR\_QMI\_MAX\_MCAST\_REQUESTS\_IN\_USE** 1062 - Maximum requests in use

**eQCWWAN\_ERR\_QMI\_INVALID\_MCAST\_HANDLE** 1063 - Invalid muticast handle

**eQCWWAN\_ERR\_QMI\_INVALID\_IP\_FAMILY\_PREF** 1064 - Invalid IP family preference

**eQCWWAN\_ERR\_QMI\_SESSION\_INACTIVE** 1065 - No tracking session has been started

**eQCWWAN\_ERR\_QMI\_SESSION\_INVALID** 1066 - Current session does not allow this operation

**eQCWWAN\_ERR\_QMI\_SESSION\_OWNERSHIP** 1067 - Current tracking session not started by this QMI control point

**eQCWWAN\_ERR\_QMI\_INSUFFICIENT\_RESOURCES** 1068 - Device GPS service resources insufficient for request

**eQCWWAN\_ERR\_QMI\_DISABLED** 1069 - Device GPS service disabled  
**eQCWWAN\_ERR\_QMI\_INVALID\_OPERATION** 1070 - Invalid operation specified  
**eQCWWAN\_ERR\_QMI\_INVALID\_QMI\_CMD** 1071 - Invalid/unknown QMI command specified  
**eQCWWAN\_ERR\_QMI\_TPDU\_TYPE** 1072 - Message contains TPDU type that cannot be read as raw message  
**eQCWWAN\_ERR\_QMI\_SMSC\_ADDR** 1073 - The SMSC address specified is invalid  
**eQCWWAN\_ERR\_QMI\_INFO\_UNAVAILABLE** 1074 - Information element is unavailable at this point  
**eQCWWAN\_ERR\_QMI\_SEGMENT\_TOO\_LONG** 1075 - Segment size too large  
**eQCWWAN\_ERR\_QMI\_SEGMENT\_ORDER** 1076 - Segment order is incorrect  
**eQCWWAN\_ERR\_QMI\_BUNDLING\_NOT\_SUPPORTED** 1077 - Bundling not supported  
**eQCWWAN\_ERR\_QMI\_OP\_PARTIAL\_FAILURE** 1078 - The operation failed partially  
**eQCWWAN\_ERR\_QMI\_POLICY\_MISMATCH** 1079 - Policy mismatch  
**eQCWWAN\_ERR\_QMI\_SIM\_FILE\_NOT\_FOUND** 1080 - SIM file not found  
**eQCWWAN\_ERR\_QMI\_EXTENDED\_INTERNAL** 1081 - Extended internal error  
**eQCWWAN\_ERR\_QMI\_ACCESS\_DENIED** 1082 - Access to a required entity is not available  
**eQCWWAN\_ERR\_QMI\_HARDWARE\_RESTRICTED** 1083 - Selected operating mode is invalid with current hardware setting  
**eQCWWAN\_ERR\_QMI\_ACK\_NOT\_SENT** 1084 - ACK not sent  
**eQCWWAN\_ERR\_QMI\_INJECT\_TIMEOUT** 1084 - Inject a timeout for the request  
**eQCWWAN\_ERR\_QMI\_INCOMPATIBLE\_STATE** 1090 - Incompatible state  
**eQCWWAN\_ERR\_QMI\_FDN\_RESTRICT** 1091 - FDN Restrict  
**eQCWWAN\_ERR\_QMI\_SUPS\_FAILURE\_CAUSE** 1092 - SUPS failure cause  
**eQCWWAN\_ERR\_QMI\_NO\_RADIO** 1093 - No Radio  
**eQCWWAN\_ERR\_QMI\_NOT\_SUPPORTED** 1094 - Not Supported  
**eQCWWAN\_ERR\_QMI\_NO\_SUBSCRIPTION** 1095 - No Subscription  
**eQCWWAN\_ERR\_QMI\_CARD\_CALL\_CONTROL\_FAILED** 1096 - Card call control failed  
**eQCWWAN\_ERR\_QMI\_NETWORK\_ABORTED** 1097 - Network Aborted  
**eQCWWAN\_ERR\_QMI\_MSG\_BLOCKED** 1098 - Open Error  
**eQCWWAN\_ERR\_QMI\_MAX** Error - End of QMI specific defines  
**eQCWWAN\_ERR\_SWICM\_START** Vendor defines - Connection Manager error codes  
**eQCWWAN\_ERR\_SWICM\_NOT\_IMPLEMENTED** 0xE001 - The API is yet to be implemented  
**eQCWWAN\_ERR\_SWICM\_QMI\_SVC\_NOT\_SUPPORTED** 0xE002 - The service is not supported  
**eQCWWAN\_ERR\_SWICM\_QMI\_CLNT\_NOT\_SUPPORTED** 0xE003 - The client is not supported  
**eQCWWAN\_ERR\_SWICM\_TIMEOUT** 0xE004 - API Timeout  
**eQCWWAN\_ERR\_SWICM\_SOCKET\_IN\_USE** 0xE005 - The communication socket is in use  
**eQCWWAN\_ERR\_SWICM\_AM\_VERS\_ERROR** 0xE006 - SLQS API and SDK version mismatch  
**eQCWWAN\_ERR\_SWICM\_FAILED\_TO\_KILL\_SDK\_PROCESS** 0xE007 - Failed to kill SDK process  
**eQCWWAN\_ERR\_SWICM\_CALL\_IN\_PROGRESS** 0xE008 - Call in progress  
**eQCWWAN\_ERR\_SWICM\_V4DWN\_V6DWN** 0xE009 - IPV4 and IPV6 is down  
**eQCWWAN\_ERR\_SWICM\_V4DWN\_V6UP** 0xE00A - IPV4 is down and IPV6 is up  
**eQCWWAN\_ERR\_SWICM\_V4UP\_V6DWN** 0xE00B - IPV4 is up and IPV6 is down  
**eQCWWAN\_ERR\_SWICM\_V4UP\_V6UP** 0xE00C - IPV4 and IPV6 is up  
**eQCWWAN\_ERR\_SWICM\_INVALID\_SESSION\_ID** 0xE00D - Invalid V4 Session ID  
**eQCWWAN\_ERR\_SWICM\_INVALID\_V4\_SESSION\_ID** 0xE00E - Invalid V4 Session ID  
**eQCWWAN\_ERR\_SWICM\_INVALID\_V6\_SESSION\_ID** 0xE00F - Invalid V6 Session ID

**eQCWWAN\_ERR\_SWICM\_SM\_NO\_AVAILABLE\_SESSIONS** 0xE010 - No available Session Manager slots for additional data sessions

**eQCWWAN\_ERR\_SWICM\_END** 0xE011 - End of connection manager specific codes

**eQCWWAN\_ERR\_SWISMS\_START** Vendor defines - SMS Error codes

**eQCWWAN\_ERR\_SWISMS\_MSG\_LEN\_TOO\_LONG** 0xE101 - SMS message length is long

**eQCWWAN\_ERR\_SWISMS\_MSG\_CORRUPTED** 0xE102 - The SMS message is corrupted (encoding wrong)

**eQCWWAN\_ERR\_SWISMS\_SMSC\_NUM\_CORRUPTED** 0xE103 - The SMS number is corrupted (incorrect number)

**eQCWWAN\_ERR\_SWISMS\_BEARER\_DATA\_NOT\_FOUND** 0xE104 - The SMS bearer data is not available

**eQCWWAN\_ERR\_SWISM\_END**

**eQCWWAN\_ERR\_SWIIM\_START** Vendor defines - Image Management error codes

**eQCWWAN\_ERR\_SWIIM\_INVALID\_PATH** 0xE801 - Invalid directory path

**eQCWWAN\_ERR\_SWIIM\_OPENING\_DIR** 0xE802 - Unable to open the directory

**eQCWWAN\_ERR\_SWIIM\_FILE\_NOT\_FOUND** 0xE803 - No Firmware image present in the path

**eQCWWAN\_ERR\_SWIIM\_OPENING\_FILE** 0xE804 - Unable to open the file

**eQCWWAN\_ERR\_SWIIM\_CORRUPTED\_FW\_IMAGE** 0xE805 - Firmware image is corrupted

**eQCWWAN\_ERR\_SWIIM\_FIRMWARE\_NOT\_DOWNLOADED** 0xE806 - No Firmware image download needed

**eQCWWAN\_ERR\_SWIIM\_FW\_UPDATE\_FAIL** 0xE807 - Firmware update failed

**eQCWWAN\_ERR\_SWIIM\_FW\_PREFERENCE\_MISMATCH** 0xE808 - Update success but pri/fw preference mismatch

**eQCWWAN\_ERR\_SWIIM\_FW\_UPDATE\_SUCCESS** 0xE809 - Update successful

**eQCWWAN\_ERR\_SWIIM\_FW\_ENTER\_DOWNLOAD\_MODE** 0xE80A - Enter Download Mode

**eQCWWAN\_ERR\_SWIIM\_FW\_FLASH\_COMPLETE** 0xE80B - File transfer to modem complete

**eQCWWAN\_ERR\_SWIIM\_FW\_WAIT\_FOR\_REBOOT** 0xE80C - Wait for modem to reboot

**eQCWWAN\_ERR\_SWIIM\_INVALID\_CRASH\_STATE** 0xE80D - Invalid Crash State for Firmware Download

**eQCWWAN\_ERR\_SWIIM\_END**

**eQCWWAN\_ERR\_SWIDCS\_START** Vendor defines - Device Connectivity error codes

**eQCWWAN\_ERR\_SWIDCS\_IOCTL\_ERR** 0xE901 - IO Control error

**eQCWWAN\_ERR\_SWIDCS\_FILEIO\_ERR** 0xE902 - file open/read/write error

**eQCWWAN\_ERR\_SWIDCS\_DEVNODE\_NOT\_FOUND** 0xE903 - The device is not found

**eQCWWAN\_ERR\_SWIDCS\_APP\_DISCONNECTED** 0xE904 - Application is disconnected from SDK

**eQCWWAN\_ERR\_SWIDCS\_END**

**eQCWWAN\_ERR\_QMI\_CAT\_START** QMI errors related to CAT

**eQCWWAN\_ERR\_QMI\_EVENT\_REG\_FAILED** 62441 - CAT event registration failed

**eQCWWAN\_ERR\_QMI\_INVALID\_TERMINAL\_RSP** 62442 - Invalid terminal response

**eQCWWAN\_ERR\_QMI\_INVALID\_ENVELOPE\_CMD** 62443 - Invalid envelope command

**eQCWWAN\_ERR\_QMI\_CARD\_BUSY\_RSP** 62444 - Card busy response for envelope command

**eQCWWAN\_ERR\_QMI\_ENVELOPE\_CMD\_FAILURE** 62445 - Envelope command failure

**eQCWWAN\_ERR\_QMI\_CAT\_END**

**eQCWWAN\_ERR\_NULL\_TLV**

**eQCWWAN\_ERR\_QMI\_WIDTH** 0xFFFF - Not an error, represent the end of QMI errors

## 9.48.1.2 enum qm\_wds\_ds\_profile\_extended\_err\_codes

## WDS DS profile extended error codes

## Enumerator

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_FAIL** 1 - General Failure

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_HANDLE** 2 - The request contains an invalid profile handle

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_OP** 3 - An invalid operation was requested.

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_PROFILE\_TYPE** 4 - The request contains an invalid technology type

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_PROFILE\_NUM** 5 - The request contains an invalid profile number

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_IDENT** 6 - The request contains an invalid profile identifier

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID** 7 - The request contains an invalid argument other than profile number and profile identifier received.

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_LIB\_NOT\_INITED** 8 - Profile registry has not been initialized yet

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_LEN\_INVALID** 9 - The request contains a parameter with invalid length.

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_LIST\_END** 10 - End of the profile list was reached while searching for the requested profile.

**eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_SUBS\_ID** 11 - The request contains an invalid subscription identifier.

**eWDS\_ERR\_PROFILE\_REG\_INVALID\_PROFILE\_FAMILY** 12 - The request contains an invalid profile family.

**eWDS\_ERR\_PROFILE\_REG\_3GPP\_INVALID\_PROFILE\_FAMILY** 1001 - The request contains an invalid 3GPP profile family.

**eWDS\_ERR\_PROFILE\_REG\_3GPP\_ACCESS\_ERR** 1002 - An error was encountered while accessing the 3GPP profiles.

**eWDS\_ERR\_PROFILE\_REG\_3GPP\_CONTEXT\_NOT\_DEFINED** 1003 - The given 3GPP profile doesn't have a valid context.

**eWDS\_ERR\_PROFILE\_REG\_3GPP\_VALID\_FLAG\_NOT\_SET** 1004 - The given 3GPP profile is marked invalid.

**eWDS\_ERR\_PROFILE\_REG\_3GPP\_READ\_ONLY\_FLAG\_SET** 1005 - The given 3GPP profile is marked read-only.

**eWDS\_ERR\_PROFILE\_REG\_3GPP\_ERR\_OUT\_OF\_PROFILES** 1006 - Creation of a new 3GPP profile failed because the limit of 16 profiles has already been reached.

**eWDS\_ERR\_PROFILE\_REG\_3GPP2\_ERR\_INVALID\_IDENT\_FOR\_PROFILE** 1101 - An invalid profile identifier was received as part of the 3GPP2 profile modification request.

**eWDS\_ERR\_PROFILE\_REG\_END**

## 9.49 qos.h File Reference

## Data Structures

- struct [unpack\\_qos\\_SLQSQosGetNetworkStatus\\_t](#)
- struct [pack\\_qos\\_SLQSQosSmiReadApnExtraParams\\_t](#)
- struct [unpack\\_qos\\_SLQSQosSmiReadApnExtraParams\\_t](#)

- struct [pack\\_qos\\_SLQSQosSwiReadDataStats\\_t](#)
- struct [unpack\\_QosFlowStat\\_t](#)
- struct [unpack\\_qos\\_SLQSQosSwiReadDataStats\\_t](#)
- struct [unpack\\_qos\\_SLQSSetQosNWStatusCallback\\_ind\\_t](#)
- struct [unpack\\_qos\\_SLQSSetQosStatusCallback\\_ind\\_t](#)
- struct [unpack\\_qos\\_SLQSSetQosPriEventCallback\\_ind\\_t](#)
- struct [pack\\_qos\\_SLQSSetQosEventCallback\\_t](#)
- struct [unpack\\_qos\\_QosFlowInfoState\\_t](#)
- struct [unpack\\_qos\\_dataRate\\_t](#)
- struct [unpack\\_qos\\_tokenBucket\\_t](#)
- struct [unpack\\_qos\\_pktErrRate\\_t](#)
- struct [unpack\\_qos\\_swiQosFlow\\_t](#)
- struct [unpack\\_qos\\_IPv4Addr\\_t](#)
- struct [unpack\\_qos\\_Tos\\_t](#)
- struct [unpack\\_qos\\_IPv6Addr\\_t](#)
- struct [unpack\\_qos\\_IPv6TrafCls\\_t](#)
- struct [unpack\\_qos\\_Port\\_t](#)
- struct [unpack\\_qos\\_swiQosFilter\\_t](#)
- struct [unpack\\_qos\\_QosFlowInfo\\_t](#)
- struct [unpack\\_qos\\_SLQSSetQosEventCallback\\_ind\\_t](#)

## Macros

- `#define LIBPACK_MAX_QOS_FLOW_PER_APN_STATS 10`
- `#define LIBPACK_MAX_QOS_FILTERS 25`
- `#define LIBPACK_MAX_QOS_FLOWS 8`

## Functions

- `int pack_qos_SLQSQosGetNetworkStatus (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen)`
- `int unpack_qos_SLQSQosGetNetworkStatus (uint8_t *pResp, uint16_t respLen, unpack\_qos\_SLQSQosGetNetworkStatus\_t *pOutput)`
- `int pack_qos_SLQSQosSwiReadApnExtraParams (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack\_qos\_SLQSQosSwiReadApnExtraParams\_t reqParam)`
- `int unpack_qos_SLQSQosSwiReadApnExtraParams (uint8_t *pResp, uint16_t respLen, unpack\_qos\_SLQSQosSwiReadApnExtraParams\_t *pOutput)`
- `int pack_qos_SLQSQosSwiReadDataStats (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack\_qos\_SLQSQosSwiReadDataStats\_t reqParam)`
- `int unpack_qos_SLQSQosSwiReadDataStats (uint8_t *pResp, uint16_t respLen, unpack\_qos\_SLQSQosSwiReadDataStats\_t *pOutput)`
- `int unpack_qos_SLQSSetQosNWStatusCallback_ind (uint8_t *pResp, uint16_t respLen, unpack\_qos\_SLQSSetQosNWStatusCallback\_ind\_t *pOutput)`
- `int unpack_qos_SLQSSetQosStatusCallback_ind (uint8_t *pResp, uint16_t respLen, unpack\_qos\_SLQSSetQosStatusCallback\_ind\_t *pOutput)`
- `int unpack_qos_SLQSSetQosPriEventCallback_ind (uint8_t *pResp, uint16_t respLen, unpack\_qos\_SLQSSetQosPriEventCallback\_ind\_t *pOutput)`
- `int pack_qos_SLQSSetQosEventCallback (pack_qmi_t *pCtx, uint8_t *pReqBuf, uint16_t *pLen, pack\_qos\_SLQSSetQosEventCallback\_t reqParam)`
- `int unpack_qos_SLQSSetQosEventCallback (uint8_t *pResp, uint16_t respLen)`
- `int unpack_qos_SLQSSetQosEventCallback_ind (uint8_t *pResp, uint16_t respLen, unpack\_qos\_SLQSSetQosEventCallback\_ind\_t *pOutput)`

## 9.49.1 Macro Definition Documentation

9.49.1.1 `#define LIBPACK_MAX_QOS_FILTERS 25`

9.49.1.2 `#define LIBPACK_MAX_QOS_FLOW_PER_APN_STATS 10`

9.49.1.3 `#define LIBPACK_MAX_QOS_FLOWS 8`

## 9.49.2 Function Documentation

9.49.2.1 `int pack_qos_SLQSQosGetNetworkStatus ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

Function to pack command to retrieve QoS status of the network. This maps to SLQSQosGetNetworkStatus

Parameters

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Buffer for packed QMI command to be provided by the host application</li> <li>Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>On input, size of pReqBuf</li> <li>On output, number of bytes actually packed</li> </ul>

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

Note

- Timeout: 2 seconds
- Technology Supported: CDMA
- PDN Specific: No

9.49.2.2 `int pack_qos_SLQSQosSwiReadApnExtraParams ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_qos_SLQSQosSwiReadApnExtraParams_t reqParam )`

Function to pack QMI command to query extra APN parameters This maps to SLQSQosSwiReadApnExtraParams



## Parameters

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Buffer for packed QMI command to be provided by the host application</li> <li>• Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• On input, size of pReqBuf</li> <li>• On output, number of bytes actually packed</li> </ul>
<i>reqParam</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qos_SLQSQosSwiReadApnExtraParams_t</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

- Timeout: 2 seconds
- PDN Specific: Yes

**9.49.2.3** `int pack_qos_SLQSQosSwiReadDataStats ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_qos_SLQSQosSwiReadDataStats_t reqParam )`

Function to pack QMI command to query APN data statistics This maps to SLQSQosSwiReadDataStats

## Parameters

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Buffer for packed QMI command to be provided by the host application</li> <li>• Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• On input, size of pReqBuf</li> <li>• On output, number of bytes actually packed</li> </ul>

<i>reqParam</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qos_SLQSQosSwiReadDataStats_t</a> for more information</li> </ul>
----------------------	---

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

- Timeout: 2 seconds
- PDN Specific: Yes

9.49.2.4 `int pack_qos_SLQSSetQosEventCallback ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_qos_SLQSSetQosEventCallback_t reqParam )`

Function to pack QMI command to enable QoS event indications This maps to SLQSSetQosEventCallback

**Parameters**

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Buffer for packed QMI command to be provided by the host application</li> <li>• Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• On input, size of pReqBuf</li> <li>• On output, number of bytes actually packed</li> </ul>
<i>reqParam</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qos_SLQSSetQosEventCallback_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

- Timeout: 2 seconds
- PDN Specific: Yes

9.49.2.5 `int unpack_qos_SLQSQosGetNetworkStatus ( uint8_t * pResp, uint16_t respLen,  
unpack_qos_SLQSQosGetNetworkStatus_t * pOutput )`

Function to unpack the response to get NW QoS status command This maps to SLQSQosGetNetworkStatus

## Parameters

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_qos_SLQSQosGetNetworkStatus_t</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.49.2.6 int unpack\_qos\_SLQSQosSwiReadApnExtraParams ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_qos\_SLQSQosSwiReadApnExtraParams\_t \* *pOutput* )

Function to unpack the response to get NW QoS status command This maps to SLQSQosSwiReadApnExtraParams

## Parameters

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_qos_SLQSQosSwiReadApnExtraParams_t</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.49.2.7 int unpack\_qos\_SLQSQosSwiReadDataStats ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_qos\_SLQSQosSwiReadDataStats\_t \* *pOutput* )

Function to unpack APN data statistics response This maps to SLQSQosSwiReadDataStats

## Parameters

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_qos_SLQSQosSwiReadDataStats_t</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.49.2.8 int unpack\_qos\_SLQSSetQosEventCallback ( uint8\_t \* *pResp*, uint16\_t *respLen* )

Function to unpack enable QoS event indications command's response This maps to SLQSSetQosEventCallback

## Parameters

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.49.2.9 int unpack\_qos\_SLQSSetQosEventCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_qos\_SLQSSetQosEventCallback\_ind\_t \* *pOutput* )

Function to unpack QoS event indications This maps to SLQSSetQosEventCallback

## Parameters

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
-------------------	---

<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">unpack_qos_SLQSSetQosEventCallback_ind_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

- This is a broadcast notification that is sent to the registered QoS service
- No explicit function to register for this indication is needed
- Please use eQMI\_QOS\_NETWORK\_STATUS\_IND indication to identify this event from QOS service read function

9.49.2.10 int unpack\_qos\_SLQSSetQosNWStatusCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_qos\_SLQSSetQosNWStatusCallback\_ind\_t \* *pOutput* )

Function to unpack QoS NW status indication. This maps to SLQSSetQosNWStatusCallback

**Parameters**

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">unpack_qos_SLQSSetQosNWStatusCallback_ind_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

- Technology Supported: CDMA
- This is a broadcast notification that is sent to the registered QoS service
- No explicit function to register for this indication is needed
- Please use eQMI\_QOS\_NETWORK\_STATUS\_IND indication to identify this event from QOS service read function

9.49.2.11 `int unpack_qos_SLQSSetQosPriEventCallback_ind ( uint8_t * pResp, uint16_t respLen,  
unpack_qos_SLQSSetQosPriEventCallback_ind_t * pOutput )`

Function to unpack QoS primary flow events. This maps to SLQSSetQosPriEventCallback

## Parameters

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_qos_SLQSSetQosPriEventCallback_ind_t</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

- This is a broadcast notification that is sent to the registered QoS service
- No explicit function to register for this indication is needed
- Please use eQMI\_QOS\_PRIMARY\_QOS\_EVENT\_IND indication to identify this event from QOS service read function
- This is only generated when the primary flow is modified by the host

9.49.2.12 `int unpack_qos_SLQSSetQosStatusCallback_ind ( uint8_t * pResp, uint16_t respLen, unpack_qos_SLQSSetQosStatusCallback_ind_t * pOutput )`

Function to unpack QoS status indications. This maps to SLQSSetQosStatusCallback

## Parameters

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_qos_SLQSSetQosStatusCallback_ind_t</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values



**Note**

- This is a broadcast notification that is sent to the registered QoS service
- No explicit function to register for this indication is needed
- Please use eQMI\_QOS\_FLOW\_STATUS\_IND indication to identify this event from QOS service read function

**9.50 sms.h File Reference****Data Structures**

- struct [pack\\_sms\\_SLQSGetSMS\\_t](#)
- struct [unpack\\_sms\\_SLQSGetSMS\\_t](#)
- struct [pack\\_sms\\_SLQSGetSMSList\\_t](#)
- struct [qmiSmsMessageList](#)
- struct [unpack\\_sms\\_SLQSGetSMSList\\_t](#)
- struct [pack\\_sms\\_SLQSMModifySMSStatus\\_t](#)
- struct [unpack\\_sms\\_SLQSMModifySMSStatus\\_t](#)
- struct [pack\\_sms\\_SLQSDDeleteSMS\\_t](#)
- struct [unpack\\_sms\\_SLQSDDeleteSMS\\_t](#)
- struct [pack\\_sms\\_SendSMS\\_t](#)
- struct [unpack\\_sms\\_SendSMS\\_t](#)
- struct [pack\\_sms\\_SetNewSMSCallback\\_t](#)
- struct [unpack\\_sms\\_SetNewSMSCallback\\_t](#)
- struct [sMSMTMessage](#)
- struct [newMTMessageTlv](#)
- struct [sMSTransferRouteMTMessage](#)
- struct [transferRouteMessageTlv](#)
- struct [sMSMessageMode](#)
- struct [messageModeTlv](#)
- struct [sMSEtwsMessage](#)
- struct [sMSEtwsMessageTlv](#)
- struct [sMSEtwsPlmn](#)
- struct [eTWSPLMNInfoTlv](#)
- struct [sMSCAddress](#)
- struct [sMSCAddressTlv](#)
- struct [sMSOnIMS](#)
- struct [sMSOnIMSTlv](#)
- struct [unpack\\_sms\\_SetNewSMSCallback\\_ind\\_t](#)
- struct [unpack\\_sms\\_SLQSWmsMemoryFullCallBack\\_ind\\_t](#)

**Macros**

- [#define MAX\\_SMS\\_MESSAGE\\_SIZE 2048](#)
- [#define MAX\\_SMS\\_LIST\\_SIZE 255](#)
- [#define MAX\\_MS\\_TRANSFER\\_ROUTE\\_MSG 256](#)
- [#define MAX\\_MSE\\_TWS\\_MSG 1254](#)
- [#define MAX\\_MSC\\_ADDRESS\\_SIZE 256](#)
- [#define MAX\\_CDMA\\_ENC\\_MO\\_TXT\\_MSG\\_SIZE 255](#)

## Typedefs

- typedef struct [sMSMTMessage](#) [sMSMTMessageInfo](#)
- typedef struct [sMSTransferRouteMTMessage](#) [sMSTransferRouteMTMessageInfo](#)
- typedef struct [sMSMessageMode](#) [sMSMessageModelInfo](#)
- typedef struct [sMSEtwsMessage](#) [sMSEtwsMessageInfo](#)
- typedef struct [sMSEtwsPlmn](#) [sMSEtwsPlmnInfo](#)
- typedef struct [sMSCAddress](#) [sMSCAddressInfo](#)
- typedef struct [sMSONIMS](#) [sMSONIMSInfo](#)

## Enumerations

- enum [eqmiCbKSetStatus](#) {  
[LIBPACK\\_QMI\\_CBK\\_PARAM\\_RESET](#) = 0,  
[LIBPACK\\_QMI\\_CBK\\_PARAM\\_SET](#) = 1,  
[LIBPACK\\_QMI\\_CBK\\_PARAM\\_NOCHANGE](#) }

## Functions

- int [pack\\_sms\\_SLQSGetSMS](#) ([pack\\_qmi\\_t](#) \*pCtx, [uint8\\_t](#) \*pReqBuf, [uint16\\_t](#) \*pLen, [pack\\_sms\\_SLQSGetSMS\\_t](#) \*reqParam)
- int [unpack\\_sms\\_SLQSGetSMS](#) ([uint8\\_t](#) \*pResp, [uint16\\_t](#) respLen, [unpack\\_sms\\_SLQSGetSMS\\_t](#) \*pOutput)
- int [pack\\_sms\\_SLQSGetSMSList](#) ([pack\\_qmi\\_t](#) \*pCtx, [uint8\\_t](#) \*pReqBuf, [uint16\\_t](#) \*pLen, [pack\\_sms\\_SLQSGetSMSList\\_t](#) \*reqParam)
- int [unpack\\_sms\\_SLQSGetSMSList](#) ([uint8\\_t](#) \*pResp, [uint16\\_t](#) respLen, [unpack\\_sms\\_SLQSGetSMSList\\_t](#) \*pOutput)
- int [pack\\_sms\\_SLQSModifySMSStatus](#) ([pack\\_qmi\\_t](#) \*pCtx, [uint8\\_t](#) \*pReqBuf, [uint16\\_t](#) \*pLen, [pack\\_sms\\_SLQSModifySMSStatus\\_t](#) \*reqParam)
- int [unpack\\_sms\\_SLQSModifySMSStatus](#) ([uint8\\_t](#) \*pResp, [uint16\\_t](#) respLen, [unpack\\_sms\\_SLQSModifySMSStatus\\_t](#) \*pOutput)
- int [pack\\_sms\\_SLQSDeleteSMS](#) ([pack\\_qmi\\_t](#) \*pCtx, [uint8\\_t](#) \*pReqBuf, [uint16\\_t](#) \*pLen, [pack\\_sms\\_SLQSDeleteSMS\\_t](#) \*reqParam)
- int [unpack\\_sms\\_SLQSDeleteSMS](#) ([uint8\\_t](#) \*pResp, [uint16\\_t](#) respLen, [unpack\\_sms\\_SLQSDeleteSMS\\_t](#) \*pOutput)
- int [pack\\_sms\\_SendSMS](#) ([pack\\_qmi\\_t](#) \*pCtx, [uint8\\_t](#) \*pReqBuf, [uint16\\_t](#) \*pLen, [pack\\_sms\\_SendSMS\\_t](#) \*reqParam)
- int [unpack\\_sms\\_SendSMS](#) ([uint8\\_t](#) \*pResp, [uint16\\_t](#) respLen, [unpack\\_sms\\_SendSMS\\_t](#) \*pOutput)
- int [pack\\_sms\\_SetNewSMSCallback](#) ([pack\\_qmi\\_t](#) \*pCtx, [uint8\\_t](#) \*pReqBuf, [uint16\\_t](#) \*pLen, [pack\\_sms\\_SetNewSMSCallback\\_t](#) reqParam)
- int [unpack\\_sms\\_SetNewSMSCallback](#) ([uint8\\_t](#) \*pResp, [uint16\\_t](#) respLen, [unpack\\_sms\\_SetNewSMSCallback\\_t](#) \*Output)
- int [unpack\\_sms\\_SetNewSMSCallback\\_ind](#) ([uint8\\_t](#) \*pResp, [uint16\\_t](#) respLen, [unpack\\_sms\\_SetNewSMSCallback\\_ind\\_t](#) \*pOutput)
- int [unpack\\_sms\\_SLQSWmsMemoryFullCallBack\\_ind](#) ([uint8\\_t](#) \*pResp, [uint16\\_t](#) respLen, [unpack\\_sms\\_SLQSWmsMemoryFullCallBack\\_ind\\_t](#) \*pOutput)

### 9.50.1 Macro Definition Documentation

9.50.1.1 [#define MAX\\_CDMA\\_ENC\\_MO\\_TXT\\_MSG\\_SIZE](#) 255

9.50.1.2 [#define MAX\\_MS\\_TRANSFER\\_ROUTE\\_MSG](#) 256

9.50.1.3 [#define MAX\\_MSC\\_ADDRESS\\_SIZE](#) 256

9.50.1.4 `#define MAX_MSE_TWS_MSG 1254`

9.50.1.5 `#define MAX_SMS_LIST_SIZE 255`

9.50.1.6 `#define MAX_SMS_MESSAGE_SIZE 2048`

## 9.50.2 Typedef Documentation

### 9.50.2.1 typedef struct `sMSCAddress` `sMSCAddressInfo`

#### Parameters

<i>length</i>	<ul style="list-style-type: none"> <li>Number of sets of following element</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>SMSC address</li> </ul>

### 9.50.2.2 typedef struct `sMSEtwsMessage` `sMSEtwsMessageInfo`

#### Parameters

<i>notificationType</i>	<ul style="list-style-type: none"> <li>Message mode 0x00 - Primary 0x01 - Secondary GSM 0x02 - Secondary UMTS</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>Number of sets of following elements</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>Raw message data</li> </ul>

### 9.50.2.3 typedef struct `sMSEtwsPlmn` `sMSEtwsPlmnInfo`

#### Parameters

<i>mobileCountry-Code</i>	<ul style="list-style-type: none"> <li>16 bit representation of MCC value range : 0 -999</li> </ul>
<i>mobileNetwork-Code</i>	<ul style="list-style-type: none"> <li>16 bit representation of MNC value range : 0 -999</li> </ul>

### 9.50.2.4 typedef struct `sSMSMessageMode` `sSMSMessageModelInfo`

#### Parameters

---

<i>messageMode</i>	Message Mode
--------------------	--------------

#### 9.50.2.5 typedef struct **sMSMTMessage** **sMSMTMessageInfo**

##### Parameters

<i>storageType</i>	memory storage 0x00-UIM 0x01-NV
<i>messageIndex</i>	MT Message index

#### 9.50.2.6 typedef struct **sMSOnIMS** **sMSOnIMSInfo**

##### Parameters

<i>smsOnIMS</i>	SMS on IMS
-----------------	------------

#### 9.50.2.7 typedef struct **sMSTransferRouteMTMessage** **sMSTransferRouteMTMessageInfo**

##### Parameters

<i>ackIndicator</i>	<ul style="list-style-type: none"> <li>Parameter to indicate if ACK must be sent by the control point 0x00 - Send ACK 0x01 - Do not send ACK</li> </ul>
<i>transactionID</i>	<ul style="list-style-type: none"> <li>Transaction ID of the message</li> </ul>
<i>format</i>	<ul style="list-style-type: none"> <li>Message format 0x00 - CDMA 0x02 - 0x05 - Reserved 0x06 - GW_PP 0x07 - GW_BC</li> </ul>
<i>length</i>	<ul style="list-style-type: none"> <li>Length of the raw message. This length should not exceed the maximum WMS payload length of 256 bytes</li> </ul>
<i>data</i>	<ul style="list-style-type: none"> <li>Raw message data</li> </ul>

### 9.50.3 Enumeration Type Documentation

#### 9.50.3.1 enum **eqmiCbkJSetStatus**

##### Enumerator

**LIBPACK\_QMI\_CBK\_PARAM\_RESET**  
**LIBPACK\_QMI\_CBK\_PARAM\_SET**  
**LIBPACK\_QMI\_CBK\_PARAM\_NOCHANGE**

### 9.50.4 Function Documentation

9.50.4.1 int pack\_sms\_SendSMS ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_sms\_SendSMS\_t \* *reqParam* )

send sms list pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
	<i>reqParam</i>	packed request

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.2 `int pack_sms_SetNewSMSCallback ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_sms_SetNewSMSCallback_t reqParam )`

set new sms callback pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
	<i>reqParam</i>	packed request

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.3 `int pack_sms_SLQSDeleteSMS ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_sms_SLQSDeleteSMS_t reqParam )`

delete sms pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
	<i>reqParam</i>	packed request

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.4 `int pack_sms_SLQSGetSMS ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_sms_SLQSGetSMS_t reqParam )`

get sms pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
	<i>reqParam</i>	packed request

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.5 int pack\_sms\_SLQSGetSMSList ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_sms\_SLQSGetSMSList\_t \* *reqParam* )

get sms list pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
	<i>reqParam</i>	packed request

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.6 int pack\_sms\_SLQSModifySMSStatus ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_sms\_SLQSModifySMSStatus\_t \* *reqParam* )

modify sms status pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
	<i>reqParam</i>	packed request

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.7 int unpack\_sms\_SendSMS ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_sms\_SendSMS\_t \* *pOutput* )

send sms unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.8 int unpack\_sms\_SetNewSMSCallback ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_sms\_SetNewSMSCallback\_t \* *Output* )

set new sms callback unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.9 int unpack\_sms\_SetNewSMSCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_sms\_SetNewSMSCallback\_ind\_t \* *pOutput* )

set new sms callback indication unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.10 int unpack\_sms\_SLQSDDeleteSMS ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_sms\_SLQSDDeleteSMS\_t \* *pOutput* )

delete sms unpack



## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.11 int unpack\_sms\_SLQSGetSMS ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_sms\_SLQSGetSMS\_t \* *pOutput* )

get sms unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.12 int unpack\_sms\_SLQSGetSMSList ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_sms\_SLQSGetSMSList\_t \* *pOutput* )

get sms list unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.13 int unpack\_sms\_SLQSMModifySMSStatus ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_sms\_SLQSMModifySMSStatus\_t \* *pOutput* )

modify sms status unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.50.4.14 int unpack\_sms\_SLQSWmsMemoryFullCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_sms\_SLQSWmsMemoryFullCallback\_ind\_t \* *pOutput* )

sms full callback indication unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.51 SwiDataTypes.h File Reference

SWI data types.

**Macros**

- #define [SWI\\_API](#)
- #define [QMI\\_NO\\_LTE\\_FW\\_SUPPORT](#) 0
- #define [QMI\\_TLV\\_PLACEHOLDER](#) 0x8F
- #define [UNUSEDPARAM\(x\)](#) (void)x

**Typedefs**

- typedef unsigned long [ULONG](#)
- typedef unsigned long long [ULONGLONG](#)
- typedef signed char [INT8](#)
- typedef unsigned char [BYTE](#)
- typedef char [CHAR](#)
- typedef unsigned short [WORD](#)
- typedef unsigned short [USHORT](#)
- typedef const char \* [LPCSTR](#)
- typedef int [BOOL](#)
- typedef signed short [SHORT](#)
- typedef signed int [INT32](#)
- typedef float [FLOAT](#)

### 9.51.1 Detailed Description

SWI data types.

### 9.51.2 Macro Definition Documentation

9.51.2.1 `#define QMI_NO_LTE_FW_SUPPORT 0`

9.51.2.2 `#define QMI_TLV_PLACEHOLDER 0x8F`

9.51.2.3 `#define SWI_API`

9.51.2.4 `#define UNUSEDPARAM( x ) (void)x`

Macro used to avoid "unused variable" compiler warnings generated due to the inclusion of the "-Wextra" flag in our make files.

### 9.51.3 Typedef Documentation

9.51.3.1 `typedef int BOOL`

9.51.3.2 `typedef unsigned char BYTE`

9.51.3.3 `typedef char CHAR`

9.51.3.4 `typedef float FLOAT`

9.51.3.5 `typedef signed int INT32`

9.51.3.6 `typedef signed char INT8`

9.51.3.7 `typedef const char* LPCSTR`

9.51.3.8 `typedef signed short SHORT`

9.51.3.9 `typedef unsigned long ULONG`

9.51.3.10 `typedef unsigned long long ULONGLONG`

9.51.3.11 `typedef unsigned short USHORT`

9.51.3.12 `typedef unsigned short WORD`

## 9.52 swiloc.h File Reference

### Data Structures

- struct [unpack\\_swiloc\\_SwiLocGetAutoStart\\_t](#)
- struct [pack\\_swiloc\\_SwiLocSetAutoStart\\_t](#)

### Functions

- int [pack\\_swiloc\\_SwiLocGetAutoStart](#) ([pack\\_qmi\\_t](#) \*pCtx, [uint8\\_t](#) \*pReqBuf, [uint16\\_t](#) \*pLen)

- int [unpack\\_swiloc\\_SwiLocGetAutoStart](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_swiloc\\_SwiLocGetAutoStart\\_t](#) \*pOutput)
- int [pack\\_swiloc\\_SwiLocSetAutoStart](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_swiloc\\_SwiLocSetAutoStart\\_t](#) \*reqArg)
- int [unpack\\_swiloc\\_SwiLocSetAutoStart](#) (uint8\_t \*pResp, uint16\_t respLen)

## 9.52.1 Function Documentation

### 9.52.1.1 int [pack\\_swiloc\\_SwiLocGetAutoStart](#) ( [pack\\_qmi\\_t](#) \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

Get Auto Start pack

#### Parameters

in	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.52.1.2 int [pack\\_swiloc\\_SwiLocSetAutoStart](#) ( [pack\\_qmi\\_t](#) \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, [pack\\_swiloc\\_SwiLocSetAutoStart\\_t](#) \* *reqArg* )

Set Auto Start pack

#### Parameters

in	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.52.1.3 int [unpack\\_swiloc\\_SwiLocGetAutoStart](#) ( uint8\_t \* *pResp*, uint16\_t *respLen*, [unpack\\_swiloc\\_SwiLocGetAutoStart\\_t](#) \* *pOutput* )

Get Auto Start unpack

#### Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.52.1.4 int unpack\_swiloc\_SwiLocSetAutoStart ( uint8\_t \* *pResp*, uint16\_t *respLen* )

Set Auto Start unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.53 swioma.h File Reference

**Data Structures**

- struct [pack\\_swioma\\_SLQSOMADMStartSession\\_t](#)
- struct [unpack\\_swioma\\_SLQSOMADMStartSession\\_t](#)
- struct [pack\\_swioma\\_SLQSOMADMCancelSession\\_t](#)
- struct [unpack\\_swioma\\_SLQSOMADMGetSettings\\_t](#)
- struct [pack\\_swioma\\_SLQSOMADMSetSettings\\_t](#)
- struct [pack\\_swioma\\_SLQSOMADMSelectSession\\_t](#)
- struct [pack\\_swioma\\_SLQSOMADMGetSessionInfo\\_t](#)
- struct [unpack\\_swioma\\_SLQSOMADMGetSessionInfo\\_t](#)
- struct [unpack\\_omaDmFotaTlv\\_t](#)
- struct [unpack\\_omaDmConfigTlv\\_t](#)
- struct [unpack\\_omaDmNotificationsTlv\\_t](#)
- struct [unpack\\_swioma\\_SLQSOMADMAAlertCallback\\_ind\\_t](#)

**Macros**

- #define [LIBPACK\\_MAX\\_SWIOMA\\_STR\\_LEN](#) 255

## Functions

- int [pack\\_swima\\_SLQSOMADMStartSession](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_swima\\_SLQSOMADMStartSession\\_t](#) reqParam)
- int [unpack\\_swima\\_SLQSOMADMStartSession](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_swima\\_SLQSOMADMStartSession\\_t](#) \*pOutput)
- int [pack\\_swima\\_SLQSOMADMCancelSession](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_swima\\_SLQSOMADMCancelSession\\_t](#) reqParam)
- int [unpack\\_swima\\_SLQSOMADMCancelSession](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_swima\\_SLQSOMADMGetSettings](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_swima\\_SLQSOMADMGetSettings](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_swima\\_SLQSOMADMGetSettings\\_t](#) \*pOutput)
- int [pack\\_swima\\_SLQSOMADMSetSettings](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_swima\\_SLQSOMADMSetSettings\\_t](#) reqParam)
- int [unpack\\_swima\\_SLQSOMADMSetSettings](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_swima\\_SLQSOMADMSendSelection](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_swima\\_SLQSOMADMSendSelection\\_t](#) reqParam)
- int [unpack\\_swima\\_SLQSOMADMSendSelection](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_swima\\_SLQSOMADMGetSessionInfo](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_swima\\_SLQSOMADMGetSessionInfo\\_t](#) reqParam)
- int [unpack\\_swima\\_SLQSOMADMGetSessionInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_swima\\_SLQSOMADMGetSessionInfo\\_t](#) \*pOutput)
- int [pack\\_swima\\_SLQSOMADMAAlertCallback](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_swima\\_SLQSOMADMAAlertCallback](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [unpack\\_swima\\_SLQSOMADMAAlertCallback\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_swima\\_SLQSOMADMAAlertCallback\\_ind\\_t](#) \*pOutput)

### 9.53.1 Macro Definition Documentation

9.53.1.1 `#define LIBPACK_MAX_SWIOMA_STR_LEN 255`

### 9.53.2 Function Documentation

9.53.2.1 `int pack_swima_SLQSOMADMAAlertCallback ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

Function to pack QMI command to enable the SWIOMADM network-initiated alert callback function. This maps to SetSLQSOMADMAAlertCallback

#### Parameters

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Buffer for packed QMI command to be provided by the host application</li> <li>• Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• On input, size of pReqBuf</li> <li>• On output, number of bytes actually packed</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

**9.53.2.2** `int pack_swioma_SLQSOMADMCancelSession ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_swioma_SLQSOMADMCancelSession_t reqParam )`

Function to pack cancel OMA-DM session command This maps to SLQSOMADMCancelSession

**Parameters**

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Buffer for packed QMI command to be provided by the host application</li> <li>• Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• On input, size of pReqBuf</li> <li>• On output, number of bytes actually packed</li> </ul>
<i>reqParam</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_swioma_SLQSOMADMCancelSession_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

**9.53.2.3** `int pack_swioma_SLQSOMADMGetSessionInfo ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_swioma_SLQSOMADMGetSessionInfo_t reqParam )`

Function to pack QMI command to return information related to the current (or previous if no session is active) OMA-DM session. This maps to SLQSOMADMGetSessionInfo

## Parameters

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Buffer for packed QMI command to be provided by the host application</li> <li>Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>On input, size of <i>pReqBuf</i></li> <li>On output, number of bytes actually packed</li> </ul>
<i>reqParam</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">pack_swima_SLQSOMADMGetSessionInfo_t</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 20 seconds

#### 9.53.2.4 int pack\_swima\_SLQSOMADMGetSettings ( pack\_qmi\_t \* pCtx, uint8\_t \* pReqBuf, uint16\_t \* pLen )

Function to pack command to retrieve the OMA-DM settings from the device. This maps to SLQSOMADMGetSettings2

## Parameters

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Buffer for packed QMI command to be provided by the host application</li> <li>Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>On input, size of <i>pReqBuf</i></li> <li>On output, number of bytes actually packed</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise



## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 20 seconds

**9.53.2.5** `int pack_swioma_SLQSOMADMSendSelection ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_swioma_SLQSOMADMSendSelection_t reqParam )`

Function to pack OMA-DM send selection command This maps to SLQSOMADMSendSelection2

## Parameters

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>Buffer for packed QMI command to be provided by the host application</li> <li>Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>On input, size of pReqBuf</li> <li>On output, number of bytes actually packed</li> </ul>
<i>reqParam</i> [IN]	<ul style="list-style-type: none"> <li>See <a href="#">pack_swioma_SLQSOMADMSendSelection_t</a> for more information</li> </ul>

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

Timeout: 20 seconds

**9.53.2.6** `int pack_swioma_SLQSOMADMSetSettings ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_swioma_SLQSOMADMSetSettings_t reqParam )`

Function to pack OMA-DM set settings command This maps to SLQSOMADMSetSettings3

## Parameters

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Buffer for packed QMI command to be provided by the host application</li> <li>• Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• On input, size of pReqBuf</li> <li>• On output, number of bytes actually packed</li> </ul>
<i>reqParam</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_swima_SLQSOMADMSetSettings_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

**9.53.2.7** `int pack_swima_SLQSOMADMStartSession ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_swima_SLQSOMADMStartSession_t reqParam )`

Function to pack Start OMA-DM session command This maps to SLQSOMADMStartSession2

**Parameters**

<i>pCtx</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_qmi_t</a> for more information</li> </ul>
<i>pReqBuf</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• Buffer for packed QMI command to be provided by the host application</li> <li>• Minimum expected size is 2048 bytes</li> </ul>
<i>pLen</i> [IN/OUT]	<ul style="list-style-type: none"> <li>• On input, size of pReqBuf</li> <li>• On output, number of bytes actually packed</li> </ul>

<i>reqParam</i> [IN]	<ul style="list-style-type: none"> <li>• See <a href="#">pack_swioma_SLQSOMADMStartSession_t</a> for more information</li> </ul>
----------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

Timeout: 20 seconds

### 9.53.2.8 int unpack\_swioma\_SLQSOMADMAAlertCallback ( uint8\_t \* *pResp*, uint16\_t *respLen* )

Function to unpack response of QMI command to enable the SWIOMADM network-initiated alert callback function. This maps to SetSLQSOMADMAAlertCallback

**Parameters**

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

- Please use eQMI\_SWIOMA\_EVENT\_IND indication to identify this event from SWIOMA service read function

### 9.53.2.9 int unpack\_swioma\_SLQSOMADMAAlertCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_swioma\_SLQSOMADMAAlertCallback\_ind\_t \* *pOutput* )

Function to unpack SWIOMADM alert indications This maps to SetSLQSOMADMAAlertCallback

**Parameters**

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_swioama_SLQSOMADMAAlertCallback_ind_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.53.2.10 int unpack\_swioama\_SLQSOMADMCancelSession ( uint8\_t \* *pResp*, uint16\_t *respLen* )

Function to pack cancel OMA-DM session command This maps to SLQSOMADMCancelSession

**Parameters**

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.53.2.11 int unpack\_swioama\_SLQSOMADMGetSessionInfo ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_swioama\_SLQSOMADMGetSessionInfo\_t \* *pOutput* )

Function to unpack information related to the current (or previous if no session is active) OMA-DM session. This maps to SLQSOMADMGetSessionInfo

**Parameters**

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
-------------------	---

<i>respLen[IN]</i>	<ul style="list-style-type: none"> <li>Length of pResp from modem</li> </ul>
<i>pOutput[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">unpack_swioma_SLQSOMADMGetSessionInfo_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.53.2.12** `int unpack_swioma_SLQSOMADMGetSettings ( uint8_t * pResp, uint16_t respLen, unpack_swioma_SLQSOMADMGetSettings_t * pOutput )`

Function to unpack OMA-DM get settings response from modem This maps to SLQSOMADMGetSettings2

**Parameters**

<i>pResp[IN]</i>	<ul style="list-style-type: none"> <li>Response from modem</li> </ul>
<i>respLen[IN]</i>	<ul style="list-style-type: none"> <li>Length of pResp from modem</li> </ul>
<i>pOutput[OUT]</i>	<ul style="list-style-type: none"> <li>See <a href="#">unpack_swioma_SLQSOMADMGetSettings_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.53.2.13** `int unpack_swioma_SLQSOMADMSendSelection ( uint8_t * pResp, uint16_t respLen )`

Function to unpack OMA-DM send selection command This maps to SLQSOMADMSendSelection2

**Parameters**

<i>pResp[IN]</i>	<ul style="list-style-type: none"> <li>Response from modem</li> </ul>
------------------	---

<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>
---------------------	--

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.53.2.14 int unpack\_swima\_SLQSOMADMSetSettings ( uint8\_t \* *pResp*, uint16\_t *respLen* )

Function to unpack OMA-DM set settings command This maps to SLQSOMADMSetSettings3

**Parameters**

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.53.2.15 int unpack\_swima\_SLQSOMADMStartSession ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_swima\_SLQSOMADMStartSession\_t \* *pOutput* )

Function to unpack Start OMA-DM session response from modem This maps to SLQSOMADMStartSession2

**Parameters**

<i>pResp</i> [IN]	<ul style="list-style-type: none"> <li>• Response from modem</li> </ul>
<i>respLen</i> [IN]	<ul style="list-style-type: none"> <li>• Length of pResp from modem</li> </ul>
<i>pOutput</i> [OUT]	<ul style="list-style-type: none"> <li>• See <a href="#">unpack_swima_SLQSOMADMStartSession_t</a> for more information</li> </ul>

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.54 SWIWWANCMAPI.h File Reference

## 9.55 uim.h File Reference

### Data Structures

- struct [uim\\_appStatus](#)
- struct [uim\\_slotInfo](#)
- struct [uim\\_cardStatus](#)
- struct [uim\\_hotSwapStatus](#)
- struct [unpack\\_uim\\_GetCardStatus\\_t](#)
- struct [uim\\_encryptedPIN1](#)
- struct [uim\\_remainingRetries](#)
- struct [uim\\_sessionInformation](#)
- struct [uim\\_verifyUIMPIN](#)
- struct [uim\\_unblockUIMPIN](#)
- struct [uim\\_cardResult](#)
- struct [uim\\_setPINProtection](#)
- struct [uim\\_changeUIMPIN](#)
- struct [uim\\_fileInfo](#)
- struct [uim\\_UIMSessionInformation](#)
- struct [uim\\_readTransparentInfo](#)
- struct [uim\\_readResult](#)
- struct [pack\\_uim\\_VerifyPin\\_t](#)
- struct [unpack\\_uim\\_VerifyPin\\_t](#)
- struct [pack\\_uim\\_UnblockPin\\_t](#)
- struct [unpack\\_uim\\_UnblockPin\\_t](#)
- struct [pack\\_uim\\_SetPinProtection\\_t](#)
- struct [unpack\\_uim\\_SetPinProtection\\_t](#)
- struct [pack\\_uim\\_ChangePin\\_t](#)
- struct [unpack\\_uim\\_ChangePin\\_t](#)
- struct [pack\\_uim\\_ReadTransparent\\_t](#)
- struct [unpack\\_uim\\_ReadTransparent\\_t](#)
- struct [pack\\_uim\\_SLQSUIEventRegister\\_t](#)
- struct [unpack\\_uim\\_SLQSUIEventRegister\\_t](#)
- struct [appStats](#)
- struct [slotInf](#)
- struct [unpack\\_uim\\_SLQSUISetStatusChangeCallBack\\_ind\\_t](#)
- struct [slot\\_t](#)
- struct [slots\\_t](#)
- struct [unpack\\_uim\\_SLQSUIGetSlotsStatus\\_t](#)
- struct [pack\\_uim\\_SLQSUISwitchSlot\\_t](#)
- struct [unpack\\_uim\\_SetUimSlotStatusChangeCallback\\_ind\\_t](#)

### Macros

- [#define UIM\\_UINT8\\_MAX\\_STRING\\_SZ 255](#)
- [#define UIM\\_MAX\\_DESCRIPTION\\_LENGTH 255](#)
- [#define UIM\\_MAX\\_NO\\_OF\\_SLOTS 5](#)
- [#define UIM\\_MAX\\_NO\\_OF\\_APPLICATIONS 10](#)
- [#define MAX\\_NO\\_OF\\_SLOTS 5](#)
- [#define MAX\\_NO\\_OF\\_APPLICATIONS 10](#)
- [#define MAX\\_DESCRIPTION\\_LENGTH 255](#)
- [#define MAX\\_SLOTS\\_STATUS 255](#)
- [#define MAX\\_ICCID\\_LENGTH 255](#)

## Functions

- int [pack\\_uim\\_GetCardStatus](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, void \*reqArg)
- int [unpack\\_uim\\_GetCardStatus](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_GetCardStatus\\_t](#) \*pOutput)
- int [pack\\_uim\\_VerifyPin](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_uim\\_VerifyPin\\_t](#) \*reqArg)
- int [unpack\\_uim\\_VerifyPin](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_VerifyPin\\_t](#) \*pOutput)
- int [pack\\_uim\\_UnblockPin](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_uim\\_UnblockPin\\_t](#) \*reqArg)
- int [unpack\\_uim\\_UnblockPin](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_UnblockPin\\_t](#) \*pOutput)
- int [pack\\_uim\\_SetPinProtection](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_uim\\_SetPinProtection\\_t](#) \*reqArg)
- int [unpack\\_uim\\_SetPinProtection](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_SetPinProtection\\_t](#) \*pOutput)
- int [pack\\_uim\\_ChangePin](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_uim\\_ChangePin\\_t](#) \*reqArg)
- int [unpack\\_uim\\_ChangePin](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_ChangePin\\_t](#) \*pOutput)
- int [pack\\_uim\\_ReadTransparent](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_uim\\_ReadTransparent\\_t](#) \*reqArg)
- int [unpack\\_uim\\_ReadTransparent](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_ReadTransparent\\_t](#) \*pOutput)
- int [pack\\_uim\\_SLQSUIMEventRegister](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_uim\\_SLQSUIMEventRegister\\_t](#) \*reqArg)
- int [unpack\\_uim\\_SLQSUIMEventRegister](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_SLQSUIMEventRegister\\_t](#) \*pOutput)
- int [unpack\\_uim\\_SLQSUIMSetStatusChangeCallBack\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_SLQSUIMSetStatusChangeCallBack\\_ind\\_t](#) \*pOutput)
- int [pack\\_uim\\_SLQSUIMGetSlotsStatus](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_uim\\_SLQSUIMGetSlotsStatus](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_SLQSUIMGetSlotsStatus\\_t](#) \*pOutput)
- int [pack\\_uim\\_SLQSUIMSwitchSlot](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_uim\\_SLQSUIMSwitchSlot\\_t](#) \*reqArg)
- int [unpack\\_uim\\_SLQSUIMSwitchSlot](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [unpack\\_uim\\_SetUimSlotStatusChangeCallBack\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_uim\\_SetUimSlotStatusChangeCallBack\\_ind\\_t](#) \*pOutput)

## 9.55.1 Macro Definition Documentation

9.55.1.1 `#define MAX_DESCRIPTION_LENGTH 255`

9.55.1.2 `#define MAX_ICCID_LENGTH 255`

9.55.1.3 `#define MAX_NO_OF_APPLICATIONS 10`

9.55.1.4 `#define MAX_NO_OF_SLOTS 5`

9.55.1.5 `#define MAX_SLOTS_STATUS 255`

9.55.1.6 `#define UIM_MAX_DESCRIPTION_LENGTH 255`

9.55.1.7 `#define UIM_MAX_NO_OF_APPLICATIONS 10`

9.55.1.8 `#define UIM_MAX_NO_OF_SLOTS 5`

9.55.1.9 `#define UIM_UINT8_MAX_STRING_SZ 255`



## 9.55.2 Function Documentation

9.55.2.1 `int pack_uim_ChangePin ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_uim_ChangePin_t * reqArg )`

Change Pin pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.2 `int pack_uim_GetCardStatus ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, void * reqArg )`

Get Card Status pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.3 `int pack_uim_ReadTransparent ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_uim_ReadTransparent_t * reqArg )`

SLQS ReadTransparent pack

Parameters

in	<i>pResp</i>	qmi response
in	<i>pespLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.4 `int pack_uim_SetPinProtection ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_uim_SetPinProtection_t * reqArg )`

Set Pin Protection pack

#### Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.5 `int pack_uim_SLQSUIEventRegister ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_uim_SLQSUIEventRegister_t * reqArg )`

UIM Status Change callback enable pack

#### Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.6 `int pack_uim_SLQSUIGetSlotsStatus ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

#### Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

#### Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

#### See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.7 int pack\_uim\_SLQSUIMSwitchSlot ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_uim\_SLQSUIMSwitchSlot\_t \* *reqArg* )

switch slot pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.8 int pack\_uim\_UnblockPin ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_uim\_UnblockPin\_t \* *reqArg* )

Unblock Pin pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.9 int pack\_uim\_VerifyPin ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_uim\_VerifyPin\_t \* *reqArg* )

Verify Pin Status pack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response
in	<i>reqArg</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.10 int unpack\_uim\_ChangePin ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_uim\_ChangePin\_t \* *pOutput* )

Change Pin unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.11 int unpack\_uim\_GetCardStatus ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_uim\_GetCardStatus\_t \* *pOutput* )

Get Card Status unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.12 int unpack\_uim\_ReadTransparent ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_uim\_ReadTransparent\_t \* *pOutput* )

SLQS ReadTransparent unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.13 int unpack\_uim\_SetPinProtection ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_uim\_SetPinProtection\_t \* *pOutput* )

Set Pin Protection unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.14 int unpack\_uim\_SetUimSlotStatusChangeCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_uim\_SetUimSlotStatusChangeCallback\_ind\_t \* *pOutput* )

UIM Slot Status Change indication unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

use pack\_uim\_SLQSUIEventRegister to subscribe

9.55.2.15 int unpack\_uim\_SLQSUIEventRegister ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_uim\_SLQSUIEvent-  
Register\_t \* *pOutput* )

UIM Status Change callback enable unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.16 int unpack\_uim\_SLQSUIGetSlotsStatus ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_uim\_SLQSUIGetSlotsStatus\_t \* *pOutput* )

get slot status unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.17 int unpack\_uim\_SLQSUIMSetStatusChangeCallBack\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_uim\_SLQSUIMSetStatusChangeCallBack\_ind\_t \* *pOutput* )

UIM Status Change indication unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

use pack\_uim\_SLQSUIMEventRegister to subscribe

9.55.2.18 int unpack\_uim\_SLQSUIMSwitchSlot ( uint8\_t \* *pResp*, uint16\_t *respLen* )

switch slot unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.19 int unpack\_uim\_UnblockPin ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_uim\_UnblockPin\_t \* *pOutput* )

Unblock Pin unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.55.2.20 int unpack\_uim\_VerifyPin ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_uim\_VerifyPin\_t \* *pOutput* )

Verify Pin unpack

**Parameters**

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	unpacked response

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## 9.56 wds.h File Reference

**Data Structures**

- struct [LibPackQosClassID](#)
- struct [LibPackTFTIDParams](#)
- struct [LibPackGPRSRequestedQoS](#)
- struct [LibPackUMTSQoS](#)
- struct [LibPackUMTSReqQoSSigInd](#)
- struct [pack\\_wds\\_SLQSStartDataSession\\_t](#)
- struct [unpack\\_wds\\_SLQSStartDataSession\\_t](#)
- struct [unpack\\_wds\\_SLQSSetPacketSrvStatusCallback\\_t](#)
- struct [pack\\_wds\\_SLQSStopDataSession\\_t](#)
- struct [wds\\_ProfileIdentifier](#)
- struct [wds\\_GPRSQoS](#)
- struct [wds\\_PCSCFIPv4ServerAddressList](#)
- struct [wds\\_PCSCFFQDNAddress](#)
- struct [wds\\_PCSCFFQDNAddressList](#)
- struct [wds\\_Domain](#)
- struct [wds\\_DomainNameList](#)
- struct [wds\\_IPV6AddressInfo](#)
- struct [wds\\_IPV6GWAddressInfo](#)



- struct [unpack\\_wds\\_SLQSGetRuntimeSettings\\_t](#)
- struct [wds\\_currNetworkInfo](#)
- struct [unpack\\_wds\\_SLQSSetWdsEventCallback\\_ind\\_t](#)
- struct [pack\\_wds\\_SLQSSetWdsEventCallback\\_t](#)
- struct [pack\\_wds\\_SLQSGetRuntimeSettings\\_t](#)
- struct [wds\\_UMTSMinQoS](#)
- struct [LibPackprofile\\_3GPP](#)
- struct [LibPackprofile\\_3GPP2](#)
- union [wds\\_profileInfo](#)
- struct [pack\\_wds\\_SLQSCreateProfile\\_t](#)
- struct [PackCreateProfileOut](#)
- struct [unpack\\_wds\\_SLQSCreateProfile\\_t](#)
- struct [pack\\_wds\\_SLQSMModifyProfile\\_t](#)
- struct [unpack\\_wds\\_SLQSMModifyProfile\\_t](#)
- struct [pack\\_wds\\_SLQSGetProfileSettings\\_t](#)
- struct [LibpackProfile3GPP](#)
- struct [LibpackProfile3GPP2](#)
- union [unpackWdsProfileParam](#)
- struct [UnPackGetProfileSettingOut](#)
- struct [unpack\\_wds\\_SLQSGetProfileSettings\\_t](#)
- struct [unpack\\_wds\\_GetSessionState\\_t](#)
- struct [pack\\_wds\\_GetDefaultProfile\\_t](#)
- struct [unpack\\_wds\\_GetDefaultProfile\\_t](#)
- struct [unpack\\_wds\\_GetConnectionRate\\_t](#)
- struct [pack\\_wds\\_GetPacketStatus\\_t](#)
- struct [unpack\\_wds\\_GetPacketStatus\\_t](#)
- struct [unpack\\_wds\\_GetSessionDuration\\_t](#)
- struct [pack\\_wds\\_GetSessionDuration\\_t](#)
- struct [unpack\\_wds\\_GetDormancyState\\_t](#)
- struct [pack\\_wds\\_GetDormancyState\\_t](#)
- struct [pack\\_wds\\_SLQSDDeleteProfile\\_t](#)
- struct [unpack\\_wds\\_SLQSDDeleteProfile\\_t](#)
- struct [pack\\_wds\\_SetDefaultProfile\\_t](#)
- struct [unpack\\_wds\\_SLQSGet3GPPConfigItem\\_t](#)
- struct [pack\\_wds\\_SLQSSet3GPPConfigItem\\_t](#)
- struct [unpack\\_wds\\_GetMobileIP\\_t](#)
- struct [pack\\_wds\\_GetMobileIP\\_t](#)
- struct [pack\\_wds\\_GetMobileIPProfile\\_t](#)
- struct [unpack\\_wds\\_GetMobileIPProfile\\_t](#)
- struct [currNetworkInfo](#)
- struct [unpack\\_wds\\_SLQSGetCurrDataSystemStat\\_t](#)
- struct [pack\\_wds\\_SLQSGetCurrDataSystemStat\\_t](#)
- struct [unpack\\_wds\\_GetLastMobileIPError\\_t](#)
- struct [pack\\_wds\\_GetLastMobileIPError\\_t](#)
- struct [rmTrasnferStaticsReq](#)
- struct [pack\\_wds\\_RMSetTransferStatistics\\_t](#)
- struct [unpack\\_wds\\_RMSetTransferStatistics\\_t](#)
- struct [pack\\_wds\\_SetMobileIPProfile\\_t](#)
- struct [unpack\\_wds\\_SetMobileIPProfile\\_t](#)
- struct [pack\\_wds\\_SLQSWdsSwiPDPRuntimeSettings\\_t](#)
- struct [ipv6AddressInfo](#)
- struct [unpack\\_wds\\_SLQSWdsSwiPDPRuntimeSettings\\_t](#)
- struct [transferStatInd](#)
- struct [pack\\_wds\\_SLQSGetDUNCallInfo\\_t](#)
- struct [connectionStatus](#)

- struct [dunchannelRate](#)
- struct [unpack\\_wds\\_SLQSGetDUNCallInfo\\_t](#)
- struct [qmiWSDDataBearerTechnology](#)
- struct [unpack\\_wds\\_SLQSGetDataBearerTechnology\\_t](#)
- struct [pack\\_wds\\_SLQSGetDataBearerTechnology\\_t](#)
- struct [unpack\\_wds\\_SLQSSetIPFamilyPreference\\_t](#)
- struct [pack\\_wds\\_SLQSSetIPFamilyPreference\\_t](#)
- struct [pack\\_wds\\_SetDefaultProfileNum\\_t](#)
- struct [pack\\_wds\\_GetDefaultProfileNum\\_t](#)
- struct [unpack\\_wds\\_GetDefaultProfileNum\\_t](#)
- struct [wdsDhcpv4ProfileId](#)
- struct [wdsDhcpv4HwConfig](#)
- struct [wdsDhcpv4Option](#)
- struct [wdsDhcpv4OptionList](#)
- struct [pack\\_wds\\_SLQSSetDHCPv4ClientConfig\\_t](#)
- struct [unpack\\_wds\\_SLQSSetDHCPv4ClientConfig\\_t](#)

## Macros

- [#define IPV6\\_ADDRESS\\_ARRAY\\_SIZE 8](#)
- [#define MAX\\_WDS\\_3GPP\\_CONF\\_LTE\\_ATTACH\\_PROFILE\\_LIST\\_SIZE 24](#)
- [#define PACK\\_WDS\\_IPV4 4](#)
- [#define PACK\\_WDS\\_IPV6 6](#)

## Typedefs

- typedef union [unpackWdsProfileParam](#) [UnpackQmiProfileInfo](#)

## Functions

- int [pack\\_wds\\_SLQSStartDataSession](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSStartDataSession\\_t](#) \*reqArg)
- int [unpack\\_wds\\_SLQSStartDataSession](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSStartDataSession\\_t](#) \*pOutput)
- int [unpack\\_wds\\_SLQSSetPacketSrvStatusCallback](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSSetPacketSrvStatusCallback\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSStopDataSession](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSStopDataSession\\_t](#) \*reqArg)
- int [unpack\\_wds\\_SLQSStopDataSession](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [unpack\\_wds\\_SLQSGetRuntimeSettings](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSGetRuntimeSettings\\_t](#) \*pOutput)
- int [unpack\\_wds\\_SLQSSetWdsEventCallback\\_ind](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSSetWdsEventCallback\\_ind\\_t](#) \*pOutput)
- int [unpack\\_wds\\_SLQSSetWdsEventCallback](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_wds\\_SLQSSetWdsEventCallback](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSSetWdsEventCallback\\_t](#) \*reqArg)
- int [pack\\_wds\\_SLQSGetRuntimeSettings](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSGetRuntimeSettings\\_t](#) \*reqArg)
- int [pack\\_wds\\_SLQSCreateProfile](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSCreateProfile\\_t](#) \*reqArg)
- int [unpack\\_wds\\_SLQSCreateProfile](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSCreateProfile\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSModifyProfile](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSModifyProfile\\_t](#) \*reqArg)

- int [unpack\\_wds\\_SLQSModifyProfile](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSModifyProfile\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSGetProfileSettings](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSGetProfileSettings\\_t](#) \*reqArg)
- int [unpack\\_wds\\_SLQSGetProfileSettings](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSGetProfileSettings\\_t](#) \*pOutput)
- int [pack\\_wds\\_GetSessionState](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_wds\\_GetSessionState](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetSessionState\\_t](#) \*pOutput)
- int [pack\\_wds\\_GetDefaultProfile](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_GetDefaultProfile\\_t](#) \*reqParam)
- int [unpack\\_wds\\_GetDefaultProfile](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetDefaultProfile\\_t](#) \*pOutput)
- int [pack\\_wds\\_GetConnectionRate](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_wds\\_GetConnectionRate](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetConnectionRate\\_t](#) \*pOutput)
- int [pack\\_wds\\_GetPacketStatus](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_GetPacketStatus\\_t](#) \*reqParam)
- int [unpack\\_wds\\_GetPacketStatus](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetPacketStatus\\_t](#) \*pOutput)
- int [pack\\_wds\\_GetSessionDuration](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_GetSessionDuration\\_t](#) \*reqParam)
- int [unpack\\_wds\\_GetSessionDuration](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetSessionDuration\\_t](#) \*pOutput)
- int [pack\\_wds\\_GetDormancyState](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_GetDormancyState\\_t](#) \*reqParam)
- int [unpack\\_wds\\_GetDormancyState](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetDormancyState\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSDeleteProfile](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSDeleteProfile\\_t](#) \*reqParam)
- int [unpack\\_wds\\_SLQSDeleteProfile](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSDeleteProfile\\_t](#) \*pOutput)
- int [pack\\_wds\\_SetDefaultProfile](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SetDefaultProfile\\_t](#) \*reqParam)
- int [unpack\\_wds\\_SetDefaultProfile](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_wds\\_SLQSGet3GPPConfigItem](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen)
- int [unpack\\_wds\\_SLQSGet3GPPConfigItem](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSGet3GPPConfigItem\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSSet3GPPConfigItem](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSSet3GPPConfigItem\\_t](#) \*reqParam)
- int [unpack\\_wds\\_SLQSSet3GPPConfigItem](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_wds\\_GetMobileIP](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_GetMobileIP\\_t](#) \*pReqParam)
- int [unpack\\_wds\\_GetMobileIP](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetMobileIP\\_t](#) \*pOutput)
- int [pack\\_wds\\_GetMobileIPProfile](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_GetMobileIPProfile\\_t](#) \*reqParam)
- int [unpack\\_wds\\_GetMobileIPProfile](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetMobileIPProfile\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSGetCurrDataSystemStat](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSGetCurrDataSystemStat\\_t](#) \*pReqParam)
- int [unpack\\_wds\\_SLQSGetCurrDataSystemStat](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSGetCurrDataSystemStat\\_t](#) \*pOutput)
- int [pack\\_wds\\_GetLastMobileIPError](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_GetLastMobileIPError\\_t](#) \*pReqParam)
- int [unpack\\_wds\\_GetLastMobileIPError](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetLastMobileIPError\\_t](#) \*pOutput)

- int [pack\\_wds\\_RMSetTransferStatistics](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_RMSetTransferStatistics\\_t](#) \*reqParam)
- int [unpack\\_wds\\_RMSetTransferStatistics](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_RMSetTransferStatistics\\_t](#) \*pOutput)
- int [pack\\_wds\\_SetMobileIPProfile](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SetMobileIPProfile\\_t](#) \*reqParam)
- int [unpack\\_wds\\_SetMobileIPProfile](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SetMobileIPProfile\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSWdsSwiPDPRuntimeSettings](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSWdsSwiPDPRuntimeSettings\\_t](#) \*reqParam)
- int [unpack\\_wds\\_SLQSWdsSwiPDPRuntimeSettings](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSWdsSwiPDPRuntimeSettings\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSGetDUNCallInfo](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSGetDUNCallInfo\\_t](#) \*reqParam)
- int [unpack\\_wds\\_SLQSGetDUNCallInfo](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSGetDUNCallInfo\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSGetDataBearerTechnology](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSGetDataBearerTechnology\\_t](#) \*pReqParam)
- int [unpack\\_wds\\_SLQSGetDataBearerTechnology](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSGetDataBearerTechnology\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSSetIPFamilyPreference](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSSetIPFamilyPreference\\_t](#) \*pReqParam)
- int [unpack\\_wds\\_SLQSSetIPFamilyPreference](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSSetIPFamilyPreference\\_t](#) \*pOutput)
- int [pack\\_wds\\_SetDefaultProfileNum](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SetDefaultProfileNum\\_t](#) \*pReqParam)
- int [unpack\\_wds\\_SetDefaultProfileNum](#) (uint8\_t \*pResp, uint16\_t respLen)
- int [pack\\_wds\\_GetDefaultProfileNum](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_GetDefaultProfileNum\\_t](#) \*pReqParam)
- int [unpack\\_wds\\_GetDefaultProfileNum](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_GetDefaultProfileNum\\_t](#) \*pOutput)
- int [pack\\_wds\\_SLQSSGetDHCPv4ClientConfig](#) ([pack\\_qmi\\_t](#) \*pCtx, uint8\_t \*pReqBuf, uint16\_t \*pLen, [pack\\_wds\\_SLQSSGetDHCPv4ClientConfig\\_t](#) \*pReq)
- int [unpack\\_wds\\_SLQSSGetDHCPv4ClientConfig](#) (uint8\_t \*pResp, uint16\_t respLen, [unpack\\_wds\\_SLQSSGetDHCPv4ClientConfig\\_t](#) \*pOutput)

## 9.56.1 Macro Definition Documentation

9.56.1.1 `#define IPV6_ADDRESS_ARRAY_SIZE 8`

9.56.1.2 `#define MAX_WDS_3GPP_CONF_LTE_ATTACH_PROFILE_LIST_SIZE 24`

9.56.1.3 `#define PACK_WDS_IPV4 4`

9.56.1.4 `#define PACK_WDS_IPV6 6`

## 9.56.2 Typedef Documentation

9.56.2.1 `typedef union unpackWdsProfileParam UnpackQmiProfileInfo`

## 9.56.3 Function Documentation

9.56.3.1 `int pack_wds_GetConnectionRate ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

get connection rate pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: No

**9.56.3.2** int pack\_wds\_GetDefaultProfile ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_GetDefaultProfile\_t \* *reqParam* )

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

**9.56.3.3** int pack\_wds\_GetDefaultProfileNum ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_GetDefaultProfileNum\_t \* *pReqParam* )

get default profile number pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.4 int pack\_wds\_GetDormancyState ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_GetDormancyState\_t \* *reqParam* )

get dormancy state pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: No

**9.56.3.5** `int pack_wds_GetLastMobileIPError ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_GetLastMobileIPError_t * pReqParam )`

get current data system pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: No

**9.56.3.6** `int pack_wds_GetMobileIP ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_GetMobileIP_t * pReqParam )`

get mobile ip mode pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: No

9.56.3.7 `int pack_wds_GetMobileIPProfile ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_GetMobileIPProfile_t * reqParam )`

get mobile ip profile pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: Yes

9.56.3.8 `int pack_wds_GetPacketStatus ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_GetPacketStatus_t * reqParam )`

get packet status pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: Yes

9.56.3.9 `int pack_wds_GetSessionDuration ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_GetSessionDuration_t * reqParam )`

get session duration pack



## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: No

9.56.3.10 int pack\_wds\_GetSessionState ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen* )

get session state pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

9.56.3.11 int pack\_wds\_RMSetTransferStatistics ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_wds\_RMSetTransferStatistics\_t \* *reqParam* )

rm set transfer statistics pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
out	<i>reqParam</i>	request parameter

## Note

PDN Specific: No

9.56.3.12 `int pack_wds_SetDefaultProfile ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen,  
pack_wds_SetDefaultProfile_t * reqParam )`

set default profile pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

**9.56.3.13** int pack\_wds\_SetDefaultProfileNum ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_wds\_SetDefaultProfileNum\_t \* *pReqParam* )

set default profile number pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.14** int pack\_wds\_SetMobileIPProfile ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_wds\_SetMobileIPProfile\_t \* *reqParam* )

set mobile ip profile pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
out	<i>reqParam</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

9.56.3.15 `int pack_wds_SLQSCreateProfile ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_SLQSCreateProfile_t * reqArg )`

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

9.56.3.16 `int pack_wds_SLQSDeleteProfile ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_SLQSDeleteProfile_t * reqParam )`

delete stored profile pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

9.56.3.17 `int pack_wds_SLQSGet3GPPConfigItem ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen )`

get 3Gpp config items pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

**9.56.3.18** int pack\_wds\_SLQSGetCurrDataSystemStat ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_wds\_SLQSGetCurrDataSystemStat\_t \* *pReqParam* )

get current data system pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

**9.56.3.19** int pack\_wds\_SLQSGetDataBearerTechnology ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*, pack\_wds\_SLQSGetDataBearerTechnology\_t \* *pReqParam* )

get data bearer technology pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

out	<i>reqParam</i>	request parameter
-----	-----------------	-------------------

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: Yes

**9.56.3.20** int pack\_wds\_SLQSGetDUNCallInfo ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_SLQSGetDUNCallInfo\_t \* *reqParam* )

get dun call info pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
out	<i>reqParam</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: Yes

**9.56.3.21** int pack\_wds\_SLQSGetProfileSettings ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_SLQSGetProfileSettings\_t \* *reqArg* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: Yes

9.56.3.22 `int pack_wds_SLQSGetRuntimeSettings ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_SLQSGetRuntimeSettings_t * reqArg )`

get runtime settings pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: Yes

**9.56.3.23** int pack\_wds\_SLQSModifyProfile ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_SLQSModifyProfile\_t \* *reqArg* )

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: Yes

**9.56.3.24** int pack\_wds\_SLQSSet3GPPConfigItem ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_SLQSSet3GPPConfigItem\_t \* *reqParam* )

set 3Gpp config items pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise



## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

**9.56.3.25** `int pack_wds_SLQSSetIPFamilyPreference ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_SLQSSetIPFamilyPreference_t * pReqParam )`

Set IP Family Preference pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
out	<i>reqParam</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.26** `int pack_wds_SLQSSetWdsEventCallback ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_SLQSSetWdsEventCallback_t * reqArg )`

set event callback pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: No

**9.56.3.27** `int pack_wds_SLQSSetDHCPv4ClientConfig ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_SLQSSetDHCPv4ClientConfig_t * pReq )`

get DHCPv4 Client Config pack

**Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>pReq</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.28 int pack\_wds\_SLQSStartDataSession ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_SLQSStartDataSession\_t \* *reqArg* )

**Start data session****Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**Note**

PDN Specific: Yes

9.56.3.29 int pack\_wds\_SLQSStopDataSession ( pack\_qmi\_t \* *pCtx*, uint8\_t \* *pReqBuf*, uint16\_t \* *pLen*,  
pack\_wds\_SLQSStopDataSession\_t \* *reqArg* )

**stop data session pack****Parameters**

in, out	<i>pCtx</i>	qmi request context
out	<i>pReqBuf</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
in	<i>reqParam</i>	request parameter

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

9.56.3.30 `int pack_wds_SLQSWdsSwiPDPRuntimeSettings ( pack_qmi_t * pCtx, uint8_t * pReqBuf, uint16_t * pLen, pack_wds_SLQSWdsSwiPDPRuntimeSettings_t * reqParam )`

swi pdp runtime settings pack

## Parameters

in, out	<i>pCtx</i>	qmi request context
out	<i>pReq</i>	qmi request buffer
out	<i>pLen</i>	qmi request length
out	<i>reqParam</i>	request parameter

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

## Note

PDN Specific: Yes

9.56.3.31 `int unpack_wds_GetConnectionRate ( uint8_t * pResp, uint16_t respLen, unpack_wds_GetConnectionRate_t * pOutput )`

get connection rate unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.32 `int unpack_wds_GetDefaultProfile ( uint8_t * pResp, uint16_t respLen, unpack_wds_GetDefaultProfile_t * pOutput )`

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.33** int unpack\_wds\_GetDefaultProfileNum ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_GetDefaultProfileNum\_t \* *pOutput* )

get default profile number unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.34** int unpack\_wds\_GetDormancyState ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_GetDormancyState\_t \* *pOutput* )

get dormancy state unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.35** int unpack\_wds\_GetLastMobileIPError ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_GetLastMobileIPError\_t \* *pOutput* )

get current data system unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.36 int unpack\_wds\_GetMobileIP ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_GetMobileIP\_t \* *pOutput* )

get mobile ip mode unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.37 int unpack\_wds\_GetMobileIPProfile ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_GetMobileIPProfile\_t \* *pOutput* )

get mobile ip profile unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.38 int unpack\_wds\_GetPacketStatus ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_GetPacketStatus\_t \* *pOutput* )

get packet status unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.39** int unpack\_wds\_GetSessionDuration ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_GetSessionDuration\_t \* *pOutput* )

get session duration unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.40** int unpack\_wds\_GetSessionState ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_GetSessionState\_t \* *pOutput* )

get session state unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.41** int unpack\_wds\_RMSetTransferStatistics ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_RMSetTransferStatistics\_t \* *pOutput* )

rm set transfer statistics unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.56.3.42 int unpack\_wds\_SetDefaultProfile ( uint8\_t \* *pResp*, uint16\_t *respLen* )

set default profile unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.56.3.43 int unpack\_wds\_SetDefaultProfileNum ( uint8\_t \* *pResp*, uint16\_t *respLen* )

set default profile number unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

#### 9.56.3.44 int unpack\_wds\_SetMobileIPProfile ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SetMobileIPProfile\_t \* *pOutput* )

set mobile ip profile unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.45** int unpack\_wds\_SLQSCreateProfile ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSCreateProfile\_t \* *pOutput* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response structure to fill
in	<i>pProfileId</i>	profile id pointer passed in req

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.46** int unpack\_wds\_SLQSDeleteProfile ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSDeleteProfile\_t \* *pOutput* )

delete stored profile unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.47** int unpack\_wds\_SLQSGet3GPPConfigItem ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSGet3GPPConfigItem\_t \* *pOutput* )

get 3GPP config items unpack



## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.48** int unpack\_wds\_SLQSGetCurrDataSystemStat ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_wds\_SLQSGetCurrDataSystemStat\_t \* *pOutput* )

get current data system unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.49** int unpack\_wds\_SLQSGetDataBearerTechnology ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_wds\_SLQSGetDataBearerTechnology\_t \* *pOutput* )

get data bearer technology unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.50** int unpack\_wds\_SLQSGetDUNCallInfo ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSGetDUNCall-  
Info\_t \* *pOutput* )

get dun call info unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.51 int unpack\_wds\_SLQSGetProfileSettings ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_wds\_SLQSGetProfileSettings\_t \* *pOutput* )

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response structure to fill

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.52 int unpack\_wds\_SLQSGetRuntimeSettings ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_wds\_SLQSGetRuntimeSettings\_t \* *pOutput* )

get runtime settings unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.53 int unpack\_wds\_SLQSModifyProfile ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSModifyProfile\_t  
\* *pOutput* )

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.54 int unpack\_wds\_SLQSSet3GPPConfigItem ( uint8\_t \* *pResp*, uint16\_t *respLen* )

set 3GPP config items unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

9.56.3.55 int unpack\_wds\_SLQSSetIPFamilyPreference ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_wds\_SLQSSetIPFamilyPreference\_t \* *pOutput* )

Set IP Family Preference unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

9.56.3.56 int unpack\_wds\_SLQSSetPacketSrvStatusCallback ( uint8\_t \* *pResp*, uint16\_t *respLen*,  
unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t \* *pOutput* )

set packet srv status callback unpack

## Parameters

in	<i>pResp</i>	qmi response
in	<i>respLen</i>	length

out	<i>pOutput</i>	unpacked response
-----	----------------	-------------------

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.56.3.57 int unpack\_wds\_SLQSSetWdsEventCallback ( uint8\_t \* *pResp*, uint16\_t *respLen* )

set event callback unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.56.3.58 int unpack\_wds\_SLQSSetWdsEventCallback\_ind ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t \* *pOutput* )

set event callback unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

### 9.56.3.59 int unpack\_wds\_SLQSSetDHCPv4ClientConfig ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSSetDHCPv4ClientConfig\_t \* *pOutput* )

get DHCPv4 Client Config unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.60** int unpack\_wds\_SLQSStartDataSession ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSStartDataSession\_t \* *pOutput* )

start data session unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.61** int unpack\_wds\_SLQSStopDataSession ( uint8\_t \* *pResp*, uint16\_t *respLen* )

stop data session unpack

## Parameters

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length

## Returns

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

## See Also

See [qmerrno.h](#) for eQCWWAN\_xxx error values

**9.56.3.62** int unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings ( uint8\_t \* *pResp*, uint16\_t *respLen*, unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t \* *pOutput* )

get current data system unpack

**Parameters**

in	<i>pResp</i>	qmi response from modem
in	<i>respLen</i>	qmi response length
out	<i>pOutput</i>	response unpacked

**Returns**

eQCWWAN\_ERR\_NONE on success, eQCWWAN\_xxx error value otherwise

**See Also**

See [qmerrno.h](#) for eQCWWAN\_xxx error values

# Index

- [\\_3gppRelease](#)
  - [pack\\_wds\\_SLQSSet3GPPConfigItem\\_t, 649](#)
    - [unpack\\_wds\\_SLQSGet3GPPConfigItem\\_t, 1078](#)
  - [\\_GetProfileSettingIn, 56](#)
    - [ProfileID, 57](#)
    - [ProfileType, 57](#)
  - [\\_GetProfileSettingOut, 57](#)
    - [curProfile, 57](#)
    - [pExtErrCode, 57](#)
  - [\\_MitigationDevInfo, 61](#)
    - [deviceId, 61](#)
    - [deviceIdLen, 61](#)
  - [\\_SLQSOMADMSessionInfo, 72](#)
    - [pDate, 74](#)
    - [pDateLength, 74](#)
    - [pPkgDescLength, 74](#)
    - [pPkgDescription, 74](#)
    - [pPkgName, 74](#)
    - [pPkgNameLength, 74](#)
    - [pRetryCount, 74](#)
    - [pSessionState, 74](#)
    - [pSessionType, 74](#)
    - [pSeverity, 74](#)
    - [pSource, 74](#)
    - [pSourceLength, 74](#)
    - [pStatus, 74](#)
    - [pTime, 74](#)
    - [pTimeLength, 75](#)
    - [pUpdateCompleteStatus, 75](#)
  - [\\_SLQSOMADMSettings, 75](#)
    - [pAutosdm, 76](#)
    - [pFOTAUpdate, 76](#)
    - [pFOTAdownload, 76](#)
    - [pFwAutoCheck, 76](#)
    - [pOMADMEEnabled, 76](#)
  - [\\_SLQSOMADMSettingsReqParams, 76](#)
    - [FOTAUpdate, 77](#)
    - [FOTAdownload, 77](#)
    - [pAutosdm, 77](#)
  - [\\_SLQSOMADMSettingsReqParams3, 77](#)
    - [FOTAUpdate, 78](#)
    - [FOTAdownload, 78](#)
    - [pAutosdm, 78](#)
    - [pFwAutoCheck, 78](#)
  - [\\_SLQSSwiGetHostDevInfoParams, 78](#)
    - [bManSize, 79](#)
    - [bModelSize, 79](#)
    - [bPlasmaIDSize, 80](#)
    - [bSWVerSize, 80](#)
    - [pManString, 80](#)
    - [pModelString, 80](#)
    - [pPlasmaIDString, 80](#)
    - [pSWVerString, 80](#)
  - [\\_SLQSSwiGetOSInfoParams, 80](#)
    - [bNameSize, 80](#)
    - [bVersionSize, 80](#)
    - [pNameString, 80](#)
    - [pVersionString, 80](#)
  - [\\_SLQSSwiGetSerialNoExtParams, 81](#)
    - [meidLength, 81](#)
    - [pMeidString, 81](#)
  - [\\_SLQSSwiSetHostDevInfoParams, 81](#)
    - [bManSize, 82](#)
    - [bModelSize, 82](#)
    - [bPlasmaIDSize, 82](#)
    - [bSWVerSize, 82](#)
    - [pManString, 82](#)
    - [pModelString, 82](#)
    - [pPlasmaIDString, 82](#)
    - [pSWVerString, 82](#)
  - [\\_SLQSSwiSetOSInfoParams, 82](#)
    - [bNameSize, 83](#)
    - [bVersionSize, 83](#)
    - [pNameString, 83](#)
    - [pVersionString, 83](#)
  - [\\_SlqsNas3GppNetworkRAT\\_, 69](#)
    - [MCC, 70](#)
    - [MNC, 70](#)
    - [RAT, 70](#)
  - [\\_getIndicationRegResp, 55](#)
    - [pRegCallStatInfoEvt, 56](#)
    - [pRegTransLayerInfoEvt, 56](#)
    - [pRegTransNWRegInfoEvt, 56](#)
  - [\\_getResetInfoNotification, 57](#)
    - [source, 59](#)
    - [type, 59](#)
  - [\\_getTransLayerInfoResp, 59](#)
    - [pRegInd, 60](#)
    - [pTransLayerInfo, 60](#)
  - [\\_getTransNWRegInfoResp, 60](#)
    - [pRegStatus, 61](#)
  - [\\_modemTempNotification, 61](#)
    - [ModemTempState, 62](#)
    - [ModemTemperature, 62](#)
  - [\\_packetSrvStatus, 62](#)
    - [bearerID, 64](#)
    - [connStatus, 64](#)
    - [ipFamily, 64](#)

- pQmiInterfaceInfo, 64
- reconfigReqd, 64
- sessionEndReason, 64
- techName, 64
- verboseSessnEndReason, 64
- verboseSessnEndReasonType, 64
- \_qaQmi3GPP2BroadcastCfgInfo, 64
  - activated\_ind, 65
  - CDMABroadcastConfig, 65
  - num\_instances, 65
- \_qaQmi3GPPBroadcastCfgInfo, 65
  - activated\_ind, 66
  - broadcastConfig, 66
  - num\_instances, 66
- \_setIndicationRegReq, 66
  - pRegCallStatInfoEvt, 67
  - pRegTransLayerInfoEvt, 67
  - pRegTransNWRegInfoEvt, 67
- \_slqs3GPPConfigItem, 67
  - LTEAttachProfileListLen, 69
  - p3gppRelease, 69
  - pDefaultPDNEnabled, 69
  - pLTEAttachProfile, 69
  - pLTEAttachProfileList, 69
  - pProfileList, 69
- \_slqsNetworkScanInfo, 70
  - pNetworkInfo, 71
  - pNetworkInfoInstances, 71
  - pPCSDigitInfo, 71
  - pPCSDigitInstances, 71
  - pRATInfo, 71
  - pRATInstances, 71
  - pScanResult, 71
- \_sysSelectPrefInfo, 83
  - pBandPref, 87
  - pEmerMode, 87
  - pGWAcqOrderPref, 87
  - pLTETBandPref, 87
  - pModePref, 87
  - pNetSelPref, 87
  - pPRLPref, 87
  - pRoamPref, 88
  - pSrvDomainPref, 88
- \_sysSelectPrefParams, 88
  - pAcqOrderPref, 93
  - pBandPref, 93
  - pCSGID, 93
  - pChgDuration, 93
  - pEmerMode, 93
  - pGWAcqOrderPref, 93
  - pLTETBandPref, 93
  - pMNCIncPCSDigStat, 93
  - pModePref, 93
  - pNetSelPref, 93
  - pPRLPref, 93
  - pRAT, 93
  - pRoamPref, 93
  - pSrvDomainPref, 93
  - pSrvRegRestriction, 93
  - pTdsdmaBandPref, 93
  - \_transLayerInfoNotification, 94
    - pTransLayerInfo, 95
    - regInd, 95
  - \_transLayerinfo, 93
    - TransCap, 94
    - TransType, 94
  - \_transNWRegInfoNotification, 95
    - NWRegStat, 96
- AAASPI
  - unpack\_wds\_GetMobileIPProfile\_t, 1074
- AAASState
  - unpack\_wds\_GetMobileIPProfile\_t, 1074
- ABSOLUTE\_VALIDITY
  - qaGobiApiSms.h, 1558
- ALS
  - getAllCallInformation, 253
- AMSSString
  - unpack\_dms\_GetFirmwareRevision\_t, 959
  - unpack\_dms\_GetFirmwareRevisions\_t, 959
- APNName
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, 1082
- absoluteValidity
  - cdmaMsgDecodingParams, 156
- accelAcceptReady
  - qaGobiApiCbK.h, 1305
- accelAcceptReady\_s, 96
  - batchPerSec, 96
  - injectEnable, 96
  - samplesPerBatch, 96
- accelTempAcceptReady
  - qaGobiApiCbK.h, 1305
- accelTempAcceptReady\_s, 96
  - batchPerSec, 97
  - injectEnable, 97
  - samplesPerBatch, 97
- AccessMac
  - protocolSubtypeElement, 694
- accclc
  - pack\_nas\_SetACCOLC\_t, 597
- ackIndicator
  - SMSTransferRouteMTMessage, 841
  - sMSTransferRouteMTMessage, 840
- acqOrdeLen
  - acqOrderPref, 98
  - nas\_acqOrderPref, 433
- acqOrderPref, 97
  - acqOrdeLen, 98
  - pAcqOrder, 98
- acroamsetting
  - slqsautoconnect, 804
- acsetting
  - slqsautoconnect, 804
- ActPilotPNElement, 98
  - ActSetPilotPN, 98
  - ActSetPilotPNStrength, 98
- ActSetCnt



- NetworkStat1x, 565
- ActSetPilotPN
  - ActPilotPNElement, 98
- ActSetPilotPNStrength
  - ActPilotPNElement, 98
- action
  - slqsautoconnect, 804
  - ssdatasession\_params, 846
- ActivateAutomatic
  - qaGobiApiDms.h, 1412
- activated\_ind
  - \_qaQmi3GPP2BroadcastCfgInfo, 65
  - \_qaQmi3GPPBroadcastCfgInfo, 66
- activationStatus
  - dms\_ActivationStatusTlv, 220
- ActivationStatusTlv
  - unpack\_dms\_SetEventReport\_ind\_t, 965
- activeBandClass
  - nas\_RFInfoTlv, 494
  - RFBandInfoElements, 742
- activeChannel
  - nas\_RFInfoTlv, 494
  - RFBandInfoElements, 742
- activeInd
  - messageWaitingInfoContent, 427
- ActiveStatus
  - CLIPResp, 169
  - CLIRResp, 170
  - CNAPResp, 173
  - COLPResp, 174
  - COLRResp, 175
- ActiveTechPref
  - unpack\_nas\_GetNetworkPreference\_t, 993
- AddCDMASysInfo, 98
  - geoSysIdx, 99
  - regPrd, 99
- AddSysInfo, 99
  - cellBroadcastCap, 100
  - geoSysIdx, 100
- addr
  - IPv4Addr, 337
  - IPv6Addr, 339
  - unpack\_qos\_IPv4Addr\_t, 1028
  - unpack\_qos\_IPv6Addr\_t, 1029
- address
  - unpack\_wds\_GetMobileIPProfile\_t, 1074
- aid
  - uim\_sessionInformation, 908
  - uim\_UIMSessionInformation, 912
  - UIMRefreshEvent, 928
  - UIMSessionInformation, 931
- aidLength
  - appStats, 108
  - appStatus, 112
  - uim\_appStatus, 900
  - uim\_sessionInformation, 908
  - uim\_UIMSessionInformation, 912
  - UIMRefreshEvent, 928
  - UIMSessionInformation, 931
- aidVal
  - appStats, 108
  - appStatus, 112
  - uim\_appStatus, 900
- aidingIndicatorMask
  - loc\_sensorDataUsage, 385
  - sensorDataUsage\_s, 760
- airTimer, 100
  - airTimerValue, 100
  - namID, 100
- airTimerValue
  - airTimer, 100
- alertPitch
  - signalInfo, 797
- alertingPattern
  - arrAlertingPattern, 113
- AlertingType
  - arrAlertingType, 114
- alertmsg
  - omaDmConfigTlv, 572
  - omaDmConfigTlvExt, 575
  - unpack\_omaDmConfigTlv\_t, 1024
- alertmsglength
  - omaDmConfigTlv, 572
  - omaDmConfigTlvExt, 575
  - unpack\_omaDmConfigTlv\_t, 1024
- allCallsAlphaIDInfo, 101
  - AlphaIDInfo, 101
  - callID, 101
- allCallsAlphaIDInfoArr
  - arrAlphaID, 114
- allCallsDiagInfo, 101
  - callID, 101
  - DiagInfo, 101
- AllCallsUUSInfo
  - arrUUSInfo, 121
- allCallsUUSInfo, 102
  - callID, 102
  - uusInfo, 102
- alphaDcs
  - alphaIDInfo, 103
- AlphaID
  - CatAlPhalIdentifierTlv, 147
- AlphaIDInfo
  - allCallsAlphaIDInfo, 101
- alphaIDInfo, 102
  - alphaDcs, 103
  - alphaLen, 103
  - alphaText, 103
- alphaIDLen
  - SMSAsyncRawSend\_s, 825
- AlphaIDLength
  - CatAlPhalIdentifierTlv, 147
- alphaLen
  - alphaIDInfo, 103
- alphaText
  - alphaIDInfo, 103

- alphabet
  - wcdmaMsgEncodingParams, 1166
- Altitude
  - GPSSStateInfo, 292
- altitudeSrcInfo, 103
  - coverage, 104
  - linkage, 104
  - source, 104
- ambr\_dl
  - sApnExtraParams, 755
  - unpack\_qos\_SLQSQosSwiReadApnExtraParams-\_t, 1034
- ambr\_dl\_ext
  - sApnExtraParams, 755
  - unpack\_qos\_SLQSQosSwiReadApnExtraParams-\_t, 1034
- ambr\_dl\_ext2
  - sApnExtraParams, 755
  - unpack\_qos\_SLQSQosSwiReadApnExtraParams-\_t, 1034
- ambr\_ul
  - sApnExtraParams, 755
  - unpack\_qos\_SLQSQosSwiReadApnExtraParams-\_t, 1034
- ambr\_ul\_ext
  - sApnExtraParams, 755
  - unpack\_qos\_SLQSQosSwiReadApnExtraParams-\_t, 1034
- ambr\_ul\_ext2
  - sApnExtraParams, 755
  - unpack\_qos\_SLQSQosSwiReadApnExtraParams-\_t, 1034
- amssSize
  - unpack\_dms\_GetFirmwareRevision\_t, 959
  - unpack\_dms\_GetFirmwareRevisions\_t, 959
- AnswerUSSD
  - qaGobiApiVoice.h, 1658
- apdoxypages.c, 1209
- apnId
  - pack\_qos\_SLQSQosSwiReadApnExtraParams\_t, 616
  - pack\_qos\_SLQSQosSwiReadDataStats\_t, 616
  - sApnExtraParams, 755
  - sQosStat, 843
  - unpack\_qos\_SLQSQosSwiReadApnExtraParams-\_t, 1034
  - unpack\_qos\_SLQSQosSwiReadDataStats\_t, 1035
- apnName
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings-\_t, 1088
- apnname
  - unpack\_wds\_GetDefaultProfile\_t, 1071
- apnsize
  - unpack\_wds\_GetDefaultProfile\_t, 1071
- appNameLength
  - loc\_LocApplicationInfo, 383
  - LocApplicationInfo, 388
- appProviderLength
  - loc\_LocApplicationInfo, 383
  - LocApplicationInfo, 388
- appState
  - appStats, 108
  - appStatus, 112
  - uim\_appStatus, 900
- appStats, 104
  - aidLength, 108
  - aidVal, 108
  - appState, 108
  - appType, 108
  - persoFeature, 108
  - persoRetries, 108
  - persoState, 108
  - persoUnblockRetries, 108
  - pin1Retries, 108
  - pin1State, 108
  - pin2Retries, 108
  - pin2State, 108
  - puk1Retries, 108
  - puk2Retries, 108
  - univPin, 108
- AppStatus
  - slotInf, 801
  - slotInfo, 803
  - uim\_slotInfo, 911
- appStatus, 108
  - aidLength, 112
  - aidVal, 112
  - appState, 112
  - appType, 112
  - persoFeature, 112
  - persoRetries, 112
  - persoState, 112
  - persoUnblockRetries, 112
  - pin1Retries, 112
  - pin1State, 112
  - pin2Retries, 112
  - pin2State, 112
  - puk1Retries, 112
  - puk2Retries, 112
  - univPin, 112
- appType
  - appStats, 108
  - appStatus, 112
  - uim\_appStatus, 900
- appVersionLength
  - loc\_LocApplicationInfo, 383
  - LocApplicationInfo, 388
- appVersionValid
  - loc\_LocApplicationInfo, 383
  - LocApplicationInfo, 388
- Application
  - unpack\_nas\_GetCDMANetworkParameters\_t, 990
- appversion\_str
  - slqsfwinfno\_s, 806
  - unpack\_dms\_GetFirmwareInfo\_t, 958
- arfcn

- GERANInfo, [251](#)
- gsmCellInfo, [295](#)
- nas\_GERANInfo, [455](#)
- nas\_gsmCellInfo, [457](#)
- arrAlertingPattern, [112](#)
  - alertingPattern, [113](#)
  - callID, [113](#)
  - numInstances, [113](#)
- arrAlertingType, [113](#)
  - AlertingType, [114](#)
  - callID, [114](#)
  - numInstances, [114](#)
- arrAlphaID, [114](#)
  - allCallsAlphaIDInfoArr, [114](#)
  - numInstances, [114](#)
- arrCallEndReason, [115](#)
  - callEndReason, [116](#)
  - callID, [116](#)
  - numInstances, [116](#)
- arrCallInfo, [116](#)
  - getAllCallInfo, [116](#)
  - numInstances, [116](#)
- arrCallInformation
  - voiceSetAllCallStatusCbInfo, [1143](#)
- arrCalledPartyNum, [114](#)
  - CalledPartyNum, [115](#)
  - numInstances, [115](#)
- arrConnectPartyNum, [116](#)
  - ConnectedPartyNum, [117](#)
  - numInstances, [117](#)
- arrDiagInfo, [117](#)
  - DiagInfo, [117](#)
  - numInstances, [117](#)
- arrRedirPartyNum, [118](#)
  - numInstances, [118](#)
  - RedirPartyNum, [118](#)
- arrRemotePartyName, [118](#)
  - GetAllCallRmtPtyName, [119](#)
  - numInstances, [119](#)
- arrRemotePartyNum, [119](#)
  - numInstances, [119](#)
  - RmtPtyNum, [119](#)
- arrSvcOption, [119](#)
  - callID, [120](#)
  - numInstances, [120](#)
  - srvOption, [120](#)
- arrUUSInfo, [120](#)
  - AllCallsUUSInfo, [121](#)
  - numInstances, [121](#)
- arrfileInfo
  - registerRefresh, [737](#)
  - UIMRefreshEvent, [928](#)
- AtCmdPort
  - DcsUsbPortNames, [210](#)
- Audio Service (AUDIO), [47](#)
- auth
  - unpack\_wds\_GetDefaultProfile\_t, [1071](#)
- authData
  - UIMAuthenticateReq, [914](#)
- AuthProt
  - protocolSubtypeElement, [694](#)
- authenticateResult, [121](#)
  - content, [121](#)
  - contentLen, [121](#)
- Authentication
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1082](#)
- authentication
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
- authenticationData, [121](#)
  - context, [123](#)
  - data, [123](#)
  - dataLen, [123](#)
- Autosdm
  - unpack\_swima\_SLQSOMADMGetSettings\_t, [1062](#)
- avgPeriod
  - LTESigRptCfg, [418](#)
  - LTESigRptConfig, [419](#)
  - nas\_LTESigRptConfig, [481](#)
- azimuth
  - satelliteInfo, [758](#)
- bAltitudeAssumed
  - gnssSvInfoNotification, [287](#)
- bEnable
  - pack\_nas\_SLQSSetSignalStrengthsCallback\_t, [611](#)
- bForceDownload
  - pack\_fms\_SetImagesPreference\_t, [589](#)
- bICCID
  - slot\_t, [799](#)
  - UIMSlotStatus, [934](#)
- bICCIDLength
  - slot\_t, [799](#)
  - UIMSlotStatus, [934](#)
- bLogicalSlot
  - pack\_uim\_SLQSUIMSwitchSlot\_t, [633](#)
  - slot\_t, [799](#)
  - UIMSlotStatus, [934](#)
  - UIMSwitchSlotReq, [936](#)
- bManSize
  - \_SLQSSwiGetHostDevInfoParams, [79](#)
  - \_SLQSSwiSetHostDevInfoParams, [82](#)
- bModelSize
  - \_SLQSSwiGetHostDevInfoParams, [79](#)
  - \_SLQSSwiSetHostDevInfoParams, [82](#)
- bNameSize
  - \_SLQSSwiGetOSInfoParams, [80](#)
  - \_SLQSSwiSetOSInfoParams, [83](#)
- bNumberOfPhySlots
  - UIMSlotStatusChangeInfo, [934](#)
  - unpack\_uim\_SetUimSlotStatusChangeCallback\_ind\_t, [1066](#)
- BOOL
  - SwiDataTypes.h, [1761](#)
- BPTiv
  - NASQmiCbkNasSystemSelPrefInd, [550](#)

- bPlasmaIDSize
  - \_SLQSSwiGetHostDevInfoParams, 80
  - \_SLQSSwiSetHostDevInfoParams, 82
- bResetStatistics
  - rmTrasferStaticsReq, 742
  - swiRMTrasferStaticsReq, 871
- bSWVerSize
  - \_SLQSSwiGetHostDevInfoParams, 80
  - \_SLQSSwiSetHostDevInfoParams, 82
- BUILD\_ID\_LEN
  - qaGobiApiFms.h, 1448
- bVersionSize
  - \_SLQSSwiGetOSInfoParams, 80
  - \_SLQSSwiSetOSInfoParams, 83
- BYTE
  - SwiDataTypes.h, 1761
- band
  - LTEInfo, 408
  - nas\_LTEInfo, 472
- band1900
  - gsmCellInfo, 295
  - nas\_gsmCellInfo, 457
- band\_pref
  - NASBandPreferenceTlv, 523
- BandCapability
  - unpack\_dms\_GetBandCapability\_t, 953
- bandCapability
  - BandCapabilityResp, 125
  - unpack\_dms\_SLQSSetBandCapability\_t, 971
- BandCapabilityResp, 123
  - bandCapability, 125
  - pLteBandCapability, 125
  - pTdsBandCapability, 125
- bandwidth
  - LTEInfo, 408
  - nas\_LTEInfo, 472
- baseId
  - CDMAInfo, 154
  - CDMASysInfo, 164
  - nas\_CDMAInfo, 438
  - nas\_CDMASysInfo, 442
- baseLat
  - CDMAInfo, 154
  - CDMASysInfo, 164
  - nas\_CDMAInfo, 438
  - nas\_CDMASysInfo, 442
- baseLong
  - CDMAInfo, 154
  - CDMASysInfo, 164
  - nas\_CDMAInfo, 438
  - nas\_CDMASysInfo, 442
- BasestationID
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSSetServingSystem\_t, 1003
- BasestationLatitude
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSSetServingSystem\_t, 1003
- BasestationLongitude
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSSetServingSystem\_t, 1003
- batchPerSec
  - accelAcceptReady\_s, 96
  - accelTempAcceptReady\_s, 97
  - gyroAcceptReady\_s, 301
  - gyroTempAcceptReady\_s, 302
- BdsSV, 125
  - id, 125
  - mask, 125
- BdsSVInfo, 126
  - len, 126
  - pSV, 126
- BearerID
  - unpack\_qos\_QosFlowInfo\_t, 1032
- bearerID
  - \_packetSrvStatus, 64
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t, 1084
- bearerId
  - sQosFlowStat, 842
  - unpack\_QosFlowStat\_t, 1050
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t, 1088
- bootSize
  - unpack\_dms\_GetFirmwareRevisions\_t, 959
- BootString
  - unpack\_dms\_GetFirmwareRevisions\_t, 959
- bootversion\_str
  - slqsfwinfo\_s, 806
  - unpack\_dms\_GetFirmwareInfo\_t, 958
- Broadcast
  - unpack\_nas\_GetCDMANetworkParameters\_t, 990
- BroadcastConfig, 126
  - fromServiceId, 127
  - selected, 127
  - toServiceId, 127
- broadcastConfig
  - \_qaQmi3GPPBroadcastCfgInfo, 66
- bsInfoValid
  - CDMASysInfo, 164
  - nas\_CDMASysInfo, 442
- bsPRev
  - CDMASysInfo, 164
  - nas\_CDMASysInfo, 442
- bsPRevValid
  - CDMASysInfo, 164
  - nas\_CDMASysInfo, 442
- bsic
  - GERANInfo, 251
  - nas\_GERANInfo, 455
- bsicId
  - gsmCellInfo, 295
  - nas\_gsmCellInfo, 457
- bucketSz
  - tokenBucket, 887
  - unpack\_qos\_tokenBucket\_t, 1048
- buildID

- CurrImageInfo, 191
  - FMSImageIdElement, 246
  - image\_info\_t, 313
  - ImageIdElement, 314
- buildIDLen
  - CurrImageInfo, 191
  - image\_info\_t, 313
- buildIDLength
  - FMSImageIdElement, 246
  - ImageIdElement, 314
- buildId
  - FMSImageElement, 245
  - ImageElement, 313
- buildIdLength
  - FMSImageElement, 245
  - ImageElement, 313
- BurstDTMFInfo
  - voiceBurstDTMFInfo, 1101
- burstDTMFInfo, 127
  - digitCnt, 128
  - pCallID, 128
  - pDigitBuff, 128
- ByteLoopbackMode
  - WDSGetLoopbackData, 1196
- ByteLoopbackMultiplier
  - WDSGetLoopbackData, 1196
- ByteTotalsElmntsV4
  - WdsByteTotals, 1186
- ByteTotalsElmntsV6
  - WdsByteTotals, 1186
- CATEventDataType, 148
  - eventMask, 148
  - pErrorMask, 148
- CATSendEnvelopeCommand
  - qaGobiApiCat.h, 1294
- CATSendTerminalResponse
  - qaGobiApiCat.h, 1295
- CBK\_DISABLE\_EVENT
  - qaGobiApiCbK.h, 1303
- CBK\_ENABLE\_EVENT
  - qaGobiApiCbK.h, 1303
- CBK\_NOCHANGE
  - qaGobiApiCbK.h, 1303
- CCETlv
  - QmiCbKCatEventStatusReportInd, 701
- CDMA\_P\_Rev
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSGetServingSystem\_t, 1003
- CDMABroadcastConfig, 150
  - \_qaQmi3GPP2BroadcastCfgInfo, 65
  - language, 151
  - selected, 151
  - serviceCategory, 151
- CDMAChannel, 151
  - priChA, 152
  - priChB, 152
  - secChA, 152
  - secChB, 152
- CDMAECIOThresh, 152
  - CDMAECIOThreshListLen, 153
  - pCDMAECIOThreshList, 153
- CDMAECIOThreshListLen
  - CDMAECIOThresh, 153
  - nas\_CDMAECIOThresh, 437
- CDMAInfo, 153
  - baseId, 154
  - baseLat, 154
  - baseLong, 154
  - nid, 154
  - refpn, 154
  - sid, 154
- CDMARSSIThresh, 159
  - CDMARSSIThreshListLen, 159
  - pCDMARSSIThreshList, 159
- CDMARSSIThreshListLen
  - CDMARSSIThresh, 159
  - nas\_CDMARSSIThresh, 439
- CDMASSInfo, 159
  - ecio, 160
  - rssI, 160
  - unpack\_nas\_SLQSNasGetSigInfo\_t, 1014
- CDMASysInfo, 160
  - baseId, 164
  - baseLat, 164
  - baseLong, 164
  - bsInfoValid, 164
  - bsPRev, 164
  - bsPRevValid, 164
  - ccsSupported, 164
  - ccsSupportedValid, 164
  - cdmaSysIdValid, 164
  - isSysPriMatch, 164
  - isSysPriMatchValid, 164
  - MCC, 164
  - MNC, 164
  - networkID, 164
  - networkIdValid, 164
  - pRevInUse, 164
  - pRevInUseValid, 164
  - packetZone, 164
  - packetZoneValid, 164
  - sysInfoCDMA, 164
  - systemID, 164
- CDMASysInfoExt, 164
  - imsi\_11\_12, 165
  - MCC, 165
- CDMASystemInfoExt
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSGetServingSystem\_t, 1003
- CHAR
  - SwiDataTypes.h, 1761
- CLIPResp, 169
  - ActiveStatus, 169
  - ProvisionStatus, 169
- CLIRResp, 170
  - ActiveStatus, 170

- ProvisionStatus, 170
- CNAPResp, 173
  - ActiveStatus, 173
  - ProvisionStatus, 173
- COLPResp, 173
  - ActiveStatus, 174
  - ProvisionStatus, 174
- COLRResp, 174
  - ActiveStatus, 175
  - ProvisionStatus, 175
- CONFIG\_LEN
  - qaGobiApiSms.h, 1558
- CQIValueCW0
  - LteCQIParm, 403
  - unpack\_nas\_SLQSSwiGetLteCQI\_t, 1019
- CQIValueCW1
  - LteCQIParm, 403
  - unpack\_nas\_SLQSSwiGetLteCQI\_t, 1019
- CSDomain
  - unpack\_nas\_GetServingNetwork\_t, 995
- CSGID, 184
  - id, 185
  - mcc, 185
  - mnc, 185
  - mncPcsDigits, 185
  - rat, 185
- CUGIndex
  - CUGInfo, 186
- CUGInfo, 185
  - CUGIndex, 186
  - SuppOA, 186
  - SuppPrefCUG, 186
- CallBackK registration (CBK), 35
- CallBarStatus
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSGetServingSystem\_t, 1003
- callBarStatus, 129
  - csBarStatus, 130
  - psBarStatus, 130
- CallBarringSysInfo, 128
  - csBarStatus, 129
  - psBarStatus, 129
- callDuration
  - unpack\_wds\_GetSessionDuration\_t, 1076
- CallEndReason
  - DUNCallInfoInd, 230
- callEndReason
  - arrCallEndReason, 116
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, 1080
- CallFWExtInfo
  - getCallFWExtInfo, 261
- callFWExtInfo, 135
  - noReplyTimer, 137
  - numLen, 137
  - numPlan, 137
  - numType, 137
  - number, 137
  - PI, 137
  - SI, 137
  - SvcClass, 137
  - SvcStatus, 137
- CallFWInfo
  - getCallFWInfo, 262
- callFWInfo, 137
  - noReplyTimer, 138
  - numLen, 138
  - number, 138
  - SvcClass, 138
  - SvcStatus, 138
- callFwdTypeAndPlan, 134
  - numberPlan, 135
  - numberType, 135
- callIID
  - allCallsAlphaIDInfo, 101
  - allCallsDiagInfo, 101
  - allCallsUUSInfo, 102
  - arrAlertingPattern, 113
  - arrAlertingType, 114
  - arrCallEndReason, 116
  - arrSvcOption, 120
  - callInfo, 140
  - DTMFInfo, 229
  - getAllCallRmtPtyName, 253
  - getAllCallRmtPtyNum, 254
  - peerNumberInfo, 664
  - voiceCallInfoReq, 1101
  - voiceInfoRec, 1137
  - voiceOTASPStatusInfo, 1141
  - voicePrivacyInfo, 1141
  - voiceStopContDTMFInfo, 1155
  - voiceSUPSNotification, 1160
- callInfo, 138
  - callID, 140
  - callState, 140
  - callType, 140
  - direction, 140
  - mode, 140
- callNumber
  - voiceCallRequestParams, 1107
- callState
  - callInfo, 140
- callType
  - callInfo, 140
- calledPartyInfo, 130
  - numLen, 132
  - numPlan, 132
  - numType, 132
  - number, 132
  - PI, 132
  - SI, 132
- CalledPartyNum
  - arrCalledPartyNum, 115
- calledPartySubAdd, 132
  - extBit, 133
  - oddEvenInd, 133
  - subAddr, 133

- subAddrLen, 133
  - subAddrType, 133
- callerID
  - callerIDInfo, 134
  - connectNumInfo, 181
- callerIDInfo, 133
  - callerID, 134
  - callerIDLen, 134
  - PI, 134
- callerIDLen
  - callerIDInfo, 134
  - connectNumInfo, 181
- callerName
  - remotePartyName, 739
- Callinfo
  - getAllCallInformation, 253
- callingPartyInfo, 140
  - numLen, 142
  - numPlan, 142
  - numType, 142
  - number, 142
  - PI, 142
  - SI, 142
- CancelUSSD
  - qaGobiApiVoice.h, 1658
- Card Application Toolkit (CAT), 38
- cardResult, 142
  - sw1, 143
  - sw2, 143
- cardState
  - slotInf, 801
  - slotInfo, 803
  - uim\_slotInfo, 911
- cardStatus, 143
  - index1xPri, 144
  - index1xSec, 144
  - indexGwPri, 144
  - indexGwSec, 144
  - numSlot, 144
  - SlotInfo, 144
- Carrier
  - fwinfo\_s, 249
- carrier
  - CurrentImgList, 189
  - unpack\_dms\_SLQSSwiGetFirmwareCurr\_t, 974
- carrier\_str
  - slqsfwinfo\_s, 806
  - unpack\_dms\_GetFirmwareInfo\_t, 958
- CarrierImage\_t, 144
  - m\_FwBuildId, 146
  - m\_FwImageld, 146
  - m\_PriBuildId, 146
  - m\_PrImageld, 146
  - m\_nCarrierId, 146
  - m\_nFolderId, 146
  - m\_nStorage, 146
- CatAlPhalIdentifierTlv, 146
  - AlphaID, 147
  - AlphaIDLength, 147
  - ReferenceID, 147
- CatAlphaldtfr
  - currentCatEvent, 189
- CatCommonEventTlv, 147
  - CatEvent, 147
  - EventID, 147
  - EventLength, 147
  - TlvPresent, 147
- CatEndPS
  - currentCatEvent, 189
- CatEndProactiveSessionTlv, 147
  - EndProactiveSession, 148
- CatEviDData
  - currentCatEvent, 189
- CatEvent
  - CatCommonEventTlv, 147
- CatEventIDDDataTlv, 148
  - Data, 148
  - DataLength, 148
  - ReferenceID, 148
- CatEventListTlv, 148
  - SetupEventList, 149
- CatEventLst
  - currentCatEvent, 189
- CatRefresh
  - currentCatEvent, 189
- CatRefreshTlv, 149
  - RefreshMode, 149
  - RefreshStage, 149
- causeCode
  - SMSAsyncRawSend\_s, 825
- ccSUPSType, 149
  - reason, 150
  - svcType, 150
- ccsSupported
  - CDMASysInfo, 164
  - nas\_CDMASysInfo, 442
- ccsSupportedValid
  - CDMASysInfo, 164
  - nas\_CDMASysInfo, 442
- cdmaMsgDecodingParams, 154
  - absoluteValidity, 156
  - mcTimeStamp, 156
  - messageLength, 156
  - pAlertPriority, 156
  - pCallbkAddr, 156
  - pCallbkAddrLength, 157
  - pDisplayMode, 157
  - pLanguage, 157
  - pMessage, 157
  - pMessageID, 157
  - pPriority, 157
  - pPrivacy, 157
  - pReadAcknowledgementReq, 157
  - pRelativeValidity, 157
  - pSenderAddr, 157
  - pSenderAddrLength, 157



- pTextMsg, [157](#)
  - pTextMsgLength, [157](#)
  - pUserAcknowledgementReq, [157](#)
- cdmaMsgEncodingParams, [157](#)
  - messageId, [158](#)
  - pCallbackAddr, [159](#)
  - pDestAddr, [159](#)
  - pEncodingAlphabet, [159](#)
  - pMessage, [159](#)
  - pMessageSize, [159](#)
  - pPriority, [159](#)
  - pRelValidity, [159](#)
  - pTextMsg, [159](#)
  - textMsgLength, [159](#)
- cdmaSSInfo, [160](#)
  - ecio, [160](#)
  - rsqi, [160](#)
- cdmaSysIdValid
  - CDMASysInfo, [164](#)
  - nas\_CDMASysInfo, [443](#)
- cell\_resel\_priority
  - infoInterFreq, [336](#)
  - nas\_infoInterFreq, [468](#)
- cellBroadcastCap
  - AddSysInfo, [100](#)
  - nas\_AddSysInfo, [434](#)
- CellDb, [165](#)
  - mask, [165](#)
- CellID
  - qaQmiServingSystemParam, [700](#)
  - unpack\_nas\_SLQSGetservingSystem\_t, [1003](#)
- cellID
  - GERANInfo, [251](#)
  - nas\_GERANInfo, [455](#)
  - nas\_UMTSInfo, [511](#)
  - UMTSInfo, [940](#)
- cellId
  - GSMSysInfo, [300](#)
  - LTESysInfo, [425](#)
  - nas\_GSMSysInfo, [462](#)
  - nas\_LTESysInfo, [484](#)
  - nas\_WCDMASysInfo, [522](#)
  - WCDMASysInfo, [1171](#)
- cellIdValid
  - gsmCellInfo, [295](#)
  - GSMSysInfo, [300](#)
  - LTESysInfo, [425](#)
  - nas\_gsmCellInfo, [457](#)
  - nas\_GSMSysInfo, [462](#)
  - nas\_LTESysInfo, [484](#)
  - nas\_WCDMASysInfo, [522](#)
  - WCDMASysInfo, [1171](#)
- cellInterFreqParams
  - infoInterFreq, [336](#)
  - nas\_infoInterFreq, [468](#)
- cellsTDD
  - nas\_umtsLTENbrCell, [513](#)
  - umtsLTENbrCell, [942](#)
- CellParams
  - LTEInfoIntraFreq, [411](#)
  - nas\_LTEInfoIntraFreq, [475](#)
- cellParams, [166](#)
  - pci, [166](#)
  - rsrp, [166](#)
  - rsrq, [166](#)
  - rsqi, [166](#)
  - srxlev, [166](#)
- cellReselPriority
  - lteGsmCellInfo, [405](#)
  - LTEInfoIntraFreq, [411](#)
  - lteWcdmaCellInfo, [426](#)
  - nas\_lteGsmCellInfo, [470](#)
  - nas\_LTEInfoIntraFreq, [475](#)
  - nas\_lteWcdmaCellInfo, [486](#)
- cells\_len
  - infoInterFreq, [336](#)
  - lteGsmCellInfo, [405](#)
  - nas\_infoInterFreq, [469](#)
  - nas\_lteGsmCellInfo, [470](#)
- cellsLen
  - LTEInfoIntraFreq, [411](#)
  - lteWcdmaCellInfo, [426](#)
  - nas\_LTEInfoIntraFreq, [475](#)
  - nas\_lteWcdmaCellInfo, [486](#)
- chaddr
  - WdsDHCPv4HWConfig, [1192](#)
  - wdsDhcpv4HwConfig, [1191](#)
- chaddrLen
  - WdsDHCPv4HWConfig, [1192](#)
  - wdsDhcpv4HwConfig, [1191](#)
- changePIN
  - pack\_uim\_ChangePin\_t, [629](#)
  - UIMChangePinReq, [916](#)
- changeUIMPIN, [167](#)
  - oldPINLen, [167](#)
  - oldPINVal, [167](#)
  - pinID, [167](#)
  - pinLen, [167](#)
  - pinVal, [167](#)
- ChannelRate, [168](#)
  - CurrChanRxRate, [168](#)
  - CurrChanTxRate, [168](#)
  - DUNCallInfoInd, [230](#)
  - MaxChanRxRate, [168](#)
  - MaxChanTxRate, [168](#)
- channelRate, [168](#)
  - CurrChanRxRate, [169](#)
  - CurrChanTxRate, [169](#)
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, [1080](#)
- Chipset
  - DeviceConfigDetail, [216](#)
- ckLen
  - depersonalizationInformation, [213](#)
- ckVal
  - depersonalizationInformation, [213](#)
- ClkInfo, [170](#)



- mask, [172](#)
- codingScheme
  - PLMNNetworkNameData, [675](#)
  - remotePartyName, [739](#)
- CommInfo, [175](#)
  - imsRegState, [177](#)
  - modemMode, [177](#)
  - psState, [177](#)
  - systemMode, [177](#)
  - temperature, [177](#)
- common.h
  - eCTL, [1211](#)
  - eDMS, [1211](#)
  - eIND, [1212](#)
  - eLOC, [1211](#)
  - eLOG\_DEBUG, [1211](#)
  - eLOG\_FATAL, [1211](#)
  - eLOG\_INFO, [1211](#)
  - eLOG\_WARN, [1211](#)
  - eNAS, [1211](#)
  - eQOS, [1211](#)
  - eREQ, [1212](#)
  - eRSP, [1212](#)
  - eSMS, [1211](#)
  - eSWILOC, [1212](#)
  - eSWIOMA, [1212](#)
  - eTIMEOUT\_10\_S, [1212](#)
  - eTIMEOUT\_20\_S, [1212](#)
  - eTIMEOUT\_2\_S, [1212](#)
  - eTIMEOUT\_300\_S, [1212](#)
  - eTIMEOUT\_30\_S, [1212](#)
  - eTIMEOUT\_5\_S, [1212](#)
  - eTIMEOUT\_60\_S, [1212](#)
  - eTIMEOUT\_8\_S, [1212](#)
  - eTIMEOUT\_DEFAULT, [1212](#)
  - eTMD, [1212](#)
  - eUIM, [1211](#)
  - eWDS, [1211](#)
- common.h, [1209](#)
  - eLOG\_LEVEL, [1211](#)
  - eQMI\_SVC, [1211](#)
  - eTimeout, [1212](#)
  - fill\_pack\_ctx, [1212](#)
  - fill\_sdu\_hdr, [1212](#)
  - get\_version, [1212](#)
  - glog, [1213](#)
  - gloglvl, [1213](#)
  - helper\_get\_resp\_ctx, [1212](#)
  - helper\_get\_xid, [1213](#)
  - helper\_set\_log\_func, [1213](#)
  - helper\_set\_log\_lvl, [1213](#)
  - libpack\_GetVersion, [1213](#)
  - libpack\_log, [1213](#)
  - logger, [1211](#)
  - MINREQBKLEN, [1211](#)
  - MSGID\_AND\_LEN, [1211](#)
  - MSGID\_DONT\_CARE, [1211](#)
  - msgtype, [1212](#)
  - SDU\_HDR\_LEN, [1211](#)
  - UNUSEDPARAM, [1211](#)
  - unpack\_result\_code\_only, [1213](#)
- commonInfo
  - swiModemStatusResp, [857](#)
  - unpack\_nas\_SLQSNasSwiModemStatus\_t, [1017](#)
- ConcSvcInfo
  - unpack\_nas\_SLQSGetServingSystem\_t, [1003](#)
- concSvcInfo
  - qaQmiServingSystemParam, [700](#)
- conn\_status
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t, [1084](#)
- ConnRateElmntsV4
  - WdsConnectionRate, [1188](#)
- ConnRateElmntsV6
  - WdsConnectionRate, [1188](#)
- connStatus
  - \_packetSrvStatus, [64](#)
- connectNumInfo, [178](#)
  - callerID, [181](#)
  - callerIDLen, [181](#)
  - numPlan, [181](#)
  - numPresInd, [181](#)
  - numType, [181](#)
  - screeningInd, [181](#)
- ConnectedPartyNum
  - arrConnectPartyNum, [117](#)
- ConnectionStatus, [177](#)
  - MDMCallDuration, [178](#)
  - MDMConnStatus, [178](#)
- connectionStatus, [178](#)
  - MDMCallDuration, [178](#)
  - MDMConnStatus, [178](#)
  - unpack\_wds\_GetSessionState\_t, [1076](#)
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, [1080](#)
- connetionState
  - imsaPdpStatusInfo, [318](#)
- content
  - authenticateResult, [121](#)
  - readResult, [733](#)
  - uim\_readResult, [906](#)
- contentLen
  - authenticateResult, [121](#)
  - readResult, [733](#)
  - uim\_readResult, [906](#)
- context
  - authenticationData, [123](#)
- contextId
  - pack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t, [654](#)
  - swiPDPRuntimeSettingsReq, [859](#)
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t, [1088](#)
- contextType
  - pack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t, [654](#)
  - swiPDPRuntimeSettingsReq, [859](#)

- ControlMac
  - protocolSubtypeElement, [694](#)
- Count1
  - RankIndicatorInd, [733](#)
- Count2
  - RankIndicatorInd, [733](#)
- countryInitials
  - PLMNNetworkNameData, [675](#)
- coverage
  - altitudeSrcInfo, [104](#)
- cpich\_ecno
  - nas\_wcdmaCellInfo, [516](#)
  - wcdmaCellInfo, [1161](#)
- cpich\_rscp
  - nas\_wcdmaCellInfo, [516](#)
  - wcdmaCellInfo, [1161](#)
- cradleMountConfigStatus
  - QmiCbkLocCradleMountInd, [702](#)
- crashAction
  - pack\_dms\_SetCrashAction\_t, [583](#)
- crashData
  - CrashInfo, [182](#)
- crashId
  - CrashInfo, [182](#)
- CrashInfo, [181](#)
  - crashData, [182](#)
  - crashId, [182](#)
  - crashStrLen, [182](#)
  - gcDumpStrLen, [182](#)
  - numCrashes, [182](#)
  - pCrashString, [182](#)
  - pGCDumpString, [182](#)
- CrashInfoParams, [182](#)
  - pCrashInfo, [183](#)
  - pDevCrashStatus, [183](#)
- crashStrLen
  - CrashInfo, [182](#)
- CreateProfileIn, [183](#)
  - curProfile, [183](#)
  - pProfileID, [183](#)
  - pProfileType, [184](#)
- CreateProfileOut, [184](#)
  - pExtErrorCode, [184](#)
  - pProfileIndex, [184](#)
  - pProfileType, [184](#)
- csAttachState
  - nas\_servSystem, [498](#)
  - NASServingSystemInfo, [552](#)
  - ServingSystemInfo, [764](#)
  - servSystem, [766](#)
- csBarStatus
  - CallBarringSysInfo, [129](#)
  - callBarStatus, [130](#)
  - nas\_CallBarringSysInfo, [435](#)
  - nas\_callBarStatus, [436](#)
- cur\_carr\_name
  - slqsfwinfo\_s, [806](#)
  - unpack\_dms\_GetFirmwareInfo\_t, [958](#)
- cur\_carr\_rev
  - slqsfwinfo\_s, [806](#)
  - unpack\_dms\_GetFirmwareInfo\_t, [958](#)
- curAMRConfig, [186](#)
  - gsmAmrStat, [187](#)
  - wcdmaAmrStat, [187](#)
- curDataBearerTechnology
  - unpack\_wds\_SLQSGetDataBearerTechnology\_t, [1079](#)
- curProfile
  - \_GetProfileSettingOut, [57](#)
  - CreateProfileIn, [183](#)
  - ModifyProfileIn, [431](#)
  - pack\_wds\_SLQSModifyProfile\_t, [648](#)
  - UnPackGetProfileSettingOut, [1089](#)
- CurrChanRxRate
  - ChannelRate, [168](#)
  - channelRate, [169](#)
  - dunchannelRate, [230](#)
- CurrChanTxRate
  - ChannelRate, [168](#)
  - channelRate, [169](#)
  - dunchannelRate, [230](#)
- currDBTechAvail
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- CurrDataSysStat, [187](#)
  - pCurrNetworkInfo, [188](#)
  - pNetworkInfoLen, [188](#)
  - pPrefNetwork, [188](#)
- CurrImageInfo, [191](#)
  - buildID, [191](#)
  - buildIDLen, [191](#)
  - imageType, [191](#)
  - uniqueID, [191](#)
- currNWInfo
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- CurrNetworkInfo, [192](#)
  - NetworkType, [194](#)
  - RATMask, [194](#)
  - SOMask, [194](#)
- currNetworkInfo, [194](#)
  - NetworkType, [194](#)
  - RATMask, [194](#)
  - SOMask, [194](#)
  - unpack\_wds\_SLQSGetCurrDataSystemStat\_t, [1079](#)
- current\_channel\_rx\_rate
  - WDSSWICurrentChannelRates, [1206](#)
- current\_channel\_tx\_rate
  - WDSSWICurrentChannelRates, [1206](#)
- currentCatEvent, [188](#)
  - CatAlphaIdtfr, [189](#)
  - CatEndPS, [189](#)
  - CatEvIDData, [189](#)
  - CatEventLst, [189](#)
  - CatRefresh, [189](#)

- currentChannelRXRate
  - unpack\_wds\_GetConnectionRate\_t, [1071](#)
- currentChannelTXRate
  - unpack\_wds\_GetConnectionRate\_t, [1071](#)
- currentDataBearer
  - pack\_wds\_SLQSSetWdsEventCallback\_t, [651](#)
- CurrentImgList, [189](#)
  - carrier, [189](#)
  - fwvers, [189](#)
  - numEntries, [190](#)
  - pCurrImgInfo, [190](#)
  - pkgver, [190](#)
  - priver, [190](#)
- currentMitigationLvl
  - QmiCbkTmdMitiLvlRptInd, [716](#)
- currentNetwork
  - dataBearerTechnology, [207](#)
  - qmiWSDDataBearerTechnology, [722](#)
- CurrentPLMN
  - qaQmiServingSystemParam, [700](#)
  - unpack\_nas\_SLQSGetServingSystem\_t, [1003](#)
- currentPLMN, [190](#)
  - MCC, [190](#)
  - MNC, [191](#)
  - netDescr, [191](#)
  - netDescrLength, [191](#)
- cust\_attr
  - custSettingInfo, [200](#)
  - DMScustSettingInfo, [222](#)
- cust\_id
  - custSettingInfo, [200](#)
  - DMScustSettingInfo, [222](#)
  - DMSgetCustomInput, [224](#)
  - getCustomInput, [263](#)
  - pack\_dms\_GetCustFeaturesV2\_t, [582](#)
  - pack\_dms\_SetCustFeaturesV2\_t, [584](#)
  - setCustomSettingV2, [774](#)
- cust\_value
  - custSettingInfo, [200](#)
  - DMScustSettingInfo, [222](#)
  - pack\_dms\_SetCustFeaturesV2\_t, [584](#)
  - setCustomSettingV2, [774](#)
- custFeaturesInfo, [194](#)
  - GpsEnable, [197](#)
  - pDHCPRelayEnabled, [197](#)
  - pDisableIMSI, [197](#)
  - pGPSLPM, [197](#)
  - pGPSSel, [197](#)
  - plPFamSupport, [197](#)
  - plsVoiceEnabled, [197](#)
  - pRMAutoConnect, [197](#)
  - pSMSSupport, [197](#)
  - qaGobiApiDms.h, [1404](#)
- custFeaturesSetting, [197](#)
  - pDHCPRelayEnabled, [199](#)
  - pGPSEnable, [199](#)
  - pGPSLPM, [199](#)
  - pGPSSel, [199](#)
  - plsVoiceEnabled, [199](#)
  - qaGobiApiDms.h, [1406](#)
- custSetting
  - custSettingList, [202](#)
  - DMScustSettingList, [223](#)
- custSettingInfo, [199](#)
  - cust\_attr, [200](#)
  - cust\_id, [200](#)
  - cust\_value, [200](#)
  - id\_length, [200](#)
  - value\_length, [200](#)
- custSettingList, [200](#)
  - custSetting, [202](#)
  - list\_type, [202](#)
  - num\_instances, [202](#)
- CustomSCP
  - unpack\_nas\_GetCDMANetworkParameters\_t, [990](#)
- CwtMute
  - GetM2MAudioProfileResp, [277](#)
  - GetM2MAVMuteResp, [279](#)
- DEVICE\_STATE\_BOOT
  - qaGobiApiCbk.h, [1349](#)
- DEVICE\_STATE\_DISCONNECTED
  - qaGobiApiCbk.h, [1349](#)
- DEVICE\_STATE\_READY
  - qaGobiApiCbk.h, [1349](#)
- dBTechAvail
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- dBTechnology
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- DEFAULTBYTEVALUE
  - qaGobiApiPds.h, [1529](#)
- DEFAULTLONGVALUE
  - qaGobiApiPds.h, [1529](#)
- DEFAULTWORDVALUE
  - qaGobiApiPds.h, [1529](#)
- DEREGISTER\_EVENT
  - qaGobiApiCbk.h, [1303](#)
- DEREGISTER\_SRV
  - qaGobiApiCbk.h, [1303](#)
- DEVICE\_OFFLINE
  - qaGobiApiFms.h, [1448](#)
- DEVICE\_RESET
  - qaGobiApiFms.h, [1448](#)
- DEVICE\_SHUTDOWN
  - qaGobiApiFms.h, [1448](#)
- DHCPOption, [216](#)
  - optCode, [217](#)
  - optValLen, [217](#)
  - pOptVal, [217](#)
- DHCPOptionList, [217](#)
  - numOpt, [218](#)
  - pOptions, [218](#)
- DHCPRelayEnabled
  - pack\_dms\_SetCustFeature\_t, [583](#)
  - unpack\_dms\_GetCustFeature\_t, [954](#)

- DMS\_IMGDETAILS\_LEN
  - dms.h, [1217](#)
- DMS\_PM\_FACTORY
  - dms.h, [1218](#)
- DMS\_PM\_LOW
  - dms.h, [1218](#)
- DMS\_PM\_OFFLINE
  - dms.h, [1218](#)
- DMS\_PM\_ONLINE
  - dms.h, [1218](#)
- DMS\_PM\_RESET
  - dms.h, [1218](#)
- DMS\_PM\_SHUT\_DOWN
  - dms.h, [1218](#)
- DMScustSettingInfo, [221](#)
  - cust\_attr, [222](#)
  - cust\_id, [222](#)
  - cust\_value, [222](#)
  - id\_length, [222](#)
  - value\_length, [222](#)
- DMScustSettingList, [222](#)
  - custSetting, [223](#)
  - list\_type, [223](#)
  - num\_instances, [223](#)
- DMSgetCustomFeatureV2, [223](#)
  - pCustSettingInfo, [223](#)
  - pCustSettingList, [223](#)
  - pGetCustomInput, [223](#)
- DMSgetCustomInput, [224](#)
  - cust\_id, [224](#)
  - list\_type, [224](#)
- DRCover
  - DRCParams, [228](#)
- DRCParams, [226](#)
  - DRCover, [228](#)
  - DRCValue, [228](#)
- DRCValue
  - DRCParams, [228](#)
- DTMFEvent
  - DTMFInfo, [229](#)
- DTMFInfo, [228](#)
  - callID, [229](#)
  - DTMFEvent, [229](#)
  - digitBuff, [229](#)
  - digitCnt, [229](#)
- DTMFInformation
  - voiceDTMFEventInfo, [1110](#)
- DTMFInterdigitInterval
  - DTMFLengths, [229](#)
- DTMFLengths, [229](#)
  - DTMFInterdigitInterval, [229](#)
  - DTMFPulseWidth, [229](#)
- DTMFPulseWidth
  - DTMFLengths, [229](#)
- DTMFdigit
  - voiceContDTMFInfo, [1109](#)
- DTMInd
  - qaQmiServingSystemParam, [700](#)
  - unpack\_nas\_SLQSGetservingSystem\_t, [1004](#)
- DUNCallInfoInd, [229](#)
  - CallEndReason, [230](#)
  - ChannelRate, [230](#)
  - DataBearerTech, [230](#)
  - DormancyStatus, [230](#)
  - MdmConnStatus, [230](#)
  - RXOKBytesCount, [230](#)
  - TXOKBytesCount, [230](#)
- Data
  - CatEventIDDDataTlv, [148](#)
- data
  - authenticationData, [123](#)
  - SMSCAddress, [826](#)
  - sMSCAddress, [826](#)
  - SMSEtwsMessage, [828](#)
  - sMSEtwsMessage, [827](#)
  - SMSTransferRouteMTMessage, [841](#)
  - sMSTransferRouteMTMessage, [840](#)
  - SwiOTAMsg\_s, [858](#)
- data\_buf
  - NASOTAMessageTlv, [542](#)
- data\_len
  - NASOTAMessageTlv, [542](#)
  - SwiOTAMsg\_s, [858](#)
- dataBearer
  - pack\_wds\_SLQSSetWdsEventCallback\_t, [651](#)
- dataBearerMask
  - dataBearers, [203](#)
  - unpack\_wds\_SLQSGetDataBearerTechnology\_t, [1079](#)
- DataBearerTech, [203](#)
  - DUNCallInfoInd, [230](#)
  - ratValue, [205](#)
  - soMask, [205](#)
  - techType, [205](#)
- dataBearerTech
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, [1080](#)
- DataBearerTechExt, [205](#)
  - pBearerTech, [205](#)
  - pLastBearerTech, [205](#)
- dataBearerTechnology, [205](#)
  - currentNetwork, [207](#)
  - ratMask, [207](#)
  - soMask, [207](#)
- dataBearers, [202](#)
  - dataBearerMask, [203](#)
  - pCurDataBearerTechnology, [203](#)
  - pLastCallDataBearerTechnology, [203](#)
- dataCapabilities
  - dataSrvCapabilities, [208](#)
  - nas\_dataSrvCapabilities, [449](#)
- dataCapabilitiesLen
  - dataSrvCapabilities, [208](#)
  - nas\_dataSrvCapabilities, [449](#)
- DataCaps
  - unpack\_nas\_GetServingNetwork\_t, [995](#)

- unpack\_nas\_GetServingNetworkCapabilities\_t, 995
- dataCaps
  - unpack\_nas\_SetDataCapabilitiesCallback\_ind\_t, 997
- DataCapsLen
  - unpack\_nas\_GetServingNetwork\_t, 995
  - unpack\_nas\_GetServingNetworkCapabilities\_t, 995
- dataCapsSize
  - unpack\_nas\_SetDataCapabilitiesCallback\_ind\_t, 997
- dataLen
  - authenticationData, 123
- DataLength
  - CatEventIDDDataTlv, 148
- DataRate
  - unpack\_qos\_swiQosFlow\_t, 1047
- dataRate, 207
  - dataRateMax, 207
  - guaranteedRate, 207
- dataRateMax
  - dataRate, 207
  - unpack\_qos\_dataRate\_t, 1028
- dataServiceCaCapability
  - unpack\_dms\_GetDeviceCapabilities\_t, 956
- DataServiceCapability
  - unpack\_dms\_GetDeviceCap\_t, 955
- DataSrvCapabilities
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSGetServingSystem\_t, 1003
- dataSrvCapabilities, 207
  - dataCapabilities, 208
  - dataCapabilitiesLen, 208
- DataStatusDetail, 208
  - IPAddress, 210
  - LastErrCode, 210
- dataSysStatAvail
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, 1086
- dataSystemStatus
  - pack\_wds\_SLQSSetWdsEventCallback\_t, 651
- DataULongLongTlv, 210
  - TlvPresent, 210
  - ulldata, 210
- DataULongTlv, 210
  - TlvPresent, 210
  - ulldata, 210
- Date
  - unpack\_swioma\_SLQSOMADMGetSessionInfo\_t, 1059
  - wcdmaLongMsgDecodingParams, 1164
  - wcdmaMsgDecodingParams, 1165
- DateLength
  - unpack\_swioma\_SLQSOMADMGetSessionInfo\_t, 1060
- day
  - nas\_timeInfo, 509
- nas\_UniversalTime, 515
  - timeInfo, 883
  - UniversalTime, 952
- dayLtSavingAdj
  - nas\_timeInfo, 509
  - timeInfo, 883
- dayOfWeek
  - nas\_timeInfo, 509
  - nas\_UniversalTime, 515
  - timeInfo, 883
  - UniversalTime, 952
- daylightSavings
  - nas\_qaQmi3Gpp2TimeZone, 490
  - qaQmi3Gpp2TimeZone, 696
- DcsUsbPortNames, 210
  - AtCmdPort, 210
  - DmPort, 210
  - NmeaPort, 210
- defaultPDNEnabled
  - pack\_wds\_SLQSSet3GPPConfigItem\_t, 649
  - unpack\_wds\_SLQSGet3GPPConfigItem\_t, 1078
- DefaultRoamInd
  - unpack\_nas\_SLQSGetServingSystem\_t, 1004
- defaultRoamInd
  - qaQmiServingSystemParam, 700
- delAssistDataStatus, 210
  - status, 211
- delayClass
  - GPRSQoS, 288
  - GPRSRequestedQoS, 289
  - LibPackGPRSRequestedQoS, 342
  - wds\_GPRSQoS, 1176
- DeleteStoredImage
  - qaGobiApiFms.h, 1451
- deliveryErrSDU
  - LibPackUMTSQoS, 374
  - UMTSMinQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMinQoS, 1185
- depersonalizationInformation, 211
  - ckLen, 213
  - ckVal, 213
  - feature, 213
  - operation, 213
- depersonalisationInfo
  - UIMDepersonalizationReq, 916
- Description
  - SlqsNas3GppNetworkInfo, 807
- description
  - omaDmFotaTlv, 577
  - omaDmFotaTlvExt, 579
  - unpack\_omaDmFotaTlv\_t, 1026
- descriptionlength
  - omaDmFotaTlv, 577
  - omaDmFotaTlvExt, 579
  - unpack\_omaDmFotaTlv\_t, 1026
- Desription
  - nas\_QmiNas3GppNetworkInfo, 491

- destPortRangeEnd
  - LibPackTFTIDParams, [371](#)
  - TFTIDParams, [881](#)
- destPortRangeStart
  - LibPackTFTIDParams, [371](#)
  - TFTIDParams, [881](#)
- detailSvcInfo, [213](#)
  - hdrHybrid, [215](#)
  - hdrSrvStatus, [215](#)
  - isSysForbidden, [215](#)
  - srvCapability, [215](#)
  - srvStatus, [215](#)
- DetailedSvcInfo
  - qaQmiServingSystemParam, [700](#)
  - unpack\_nas\_SLQSGetServingSystem\_t, [1004](#)
- dev
  - qmifwinfo\_s, [719](#)
- DevCrashState
  - unpack\_dms\_GetCrashAction\_t, [953](#)
- Device
  - SetM2MAudioAVCFGRReq, [781](#)
- Device Connectivity Service (DCS), [31](#)
- Device Management Service (DMS), [33](#)
- device\_state\_enum
  - qaGobiApiCbK.h, [1349](#)
- DeviceConfigDetail, [215](#)
  - Chipset, [216](#)
  - HWVersion, [216](#)
  - QLIC, [216](#)
  - Technology, [216](#)
- deviceId
  - \_MitigationDevInfo, [61](#)
- deviceIdLen
  - \_MitigationDevInfo, [61](#)
- DiagInfo
  - allCallsDiagInfo, [101](#)
  - arrDiagInfo, [117](#)
- diagInfo, [218](#)
  - diagInfoLen, [218](#)
  - diagnosticInfo, [218](#)
- diagInfoLen
  - diagInfo, [218](#)
- diagnosticInfo
  - diagInfo, [218](#)
- digitBuff
  - DTMFInfo, [229](#)
- digitCnt
  - burstDTMFInfo, [128](#)
  - DTMFInfo, [229](#)
- dirNum, [218](#)
  - dirNum, [219](#)
  - dirNumLen, [219](#)
  - dirNum, [219](#)
- dirNumLen
  - dirNum, [219](#)
- direction
  - callInfo, [140](#)
- DisableIMSI
  - pack\_dms\_SetCustFeature\_t, [583](#)
  - unpack\_dms\_GetCustFeature\_t, [954](#)
- dispType
  - extDispRecInfo, [237](#)
- displayCondition
  - serviceName, [762](#)
- dl\_bw\_value
  - NASPhyCaAggPcellInfo, [543](#)
  - NASPhyCaAggScellIDBw, [543](#)
  - NASPhyCaAggScellInfo, [545](#)
  - PhyCaAggPcellInfo, [667](#)
  - PhyCaAggScellIDBw, [668](#)
  - PhyCaAggScellInfo, [671](#)
- DmPort
  - DcsUsbPortNames, [210](#)
- dms.h, [1213](#)
  - DMS\_IMGDETAILS\_LEN, [1217](#)
  - DMS\_PM\_FACTORY, [1218](#)
  - DMS\_PM\_LOW, [1218](#)
  - DMS\_PM\_OFFLINE, [1218](#)
  - DMS\_PM\_ONLINE, [1218](#)
  - DMS\_PM\_RESET, [1218](#)
  - DMS\_PM\_SHUT\_DOWN, [1218](#)
  - MAX\_BUILD\_ID\_LEN, [1218](#)
  - pack\_dms\_GetActivationState, [1219](#)
  - pack\_dms\_GetBandCapability, [1219](#)
  - pack\_dms\_GetCrashAction, [1219](#)
  - pack\_dms\_GetCustFeature, [1219](#)
  - pack\_dms\_GetCustFeaturesV2, [1221](#)
  - pack\_dms\_GetDeviceCap, [1221](#)
  - pack\_dms\_GetDeviceCapabilities, [1221](#)
  - pack\_dms\_GetDeviceHardwareRev, [1221](#)
  - pack\_dms\_GetDeviceMfr, [1222](#)
  - pack\_dms\_GetDeviceSerialNumbers, [1222](#)
  - pack\_dms\_GetFSN, [1223](#)
  - pack\_dms\_GetFirmwareInfo, [1222](#)
  - pack\_dms\_GetFirmwareRevision, [1223](#)
  - pack\_dms\_GetFirmwareRevisions, [1223](#)
  - pack\_dms\_GetHardwareRevision, [1224](#)
  - pack\_dms\_GetIMSI, [1224](#)
  - pack\_dms\_GetModelID, [1224](#)
  - pack\_dms\_GetNetworkTime, [1225](#)
  - pack\_dms\_GetPRLVersion, [1225](#)
  - pack\_dms\_GetPower, [1225](#)
  - pack\_dms\_GetSerialNumbers, [1226](#)
  - pack\_dms\_GetUSBComp, [1226](#)
  - pack\_dms\_GetVoiceNumber, [1226](#)
  - pack\_dms\_SLQSDmsSwiGetResetInfo, [1229](#)
  - pack\_dms\_SLQSDmsSwiIndicationRegister, [1230](#)
  - pack\_dms\_SLQSGetBandCapability, [1230](#)
  - pack\_dms\_SLQSSwiClearDyingGaspStatistics, [1230](#)
  - pack\_dms\_SLQSSwiGetDyingGaspCfg, [1231](#)
  - pack\_dms\_SLQSSwiGetDyingGaspStatistics, [1231](#)
  - pack\_dms\_SLQSSwiGetFirmwareCurr, [1231](#)
  - pack\_dms\_SLQSSwiGetFwUpdateStatus, [1232](#)
  - pack\_dms\_SLQSSwiSetDyingGaspCfg, [1232](#)



- pack\_dms\_SetCrashAction, [1227](#)
- pack\_dms\_SetCustFeature, [1227](#)
- pack\_dms\_SetCustFeaturesV2, [1228](#)
- pack\_dms\_SetEventReport, [1228](#)
- pack\_dms\_SetFirmwarePreference, [1228](#)
- pack\_dms\_SetPower, [1229](#)
- pack\_dms\_SetUSBComp, [1229](#)
- pack\_dms\_UIMGetICCID, [1232](#)
- UNIQUE\_ID\_LEN, [1218](#)
- unpack\_dms\_GetActivationState, [1233](#)
- unpack\_dms\_GetBandCapability, [1233](#)
- unpack\_dms\_GetCrashAction, [1233](#)
- unpack\_dms\_GetCustFeature, [1234](#)
- unpack\_dms\_GetCustFeaturesV2, [1234](#)
- unpack\_dms\_GetDeviceCap, [1234](#)
- unpack\_dms\_GetDeviceCapabilities, [1234](#)
- unpack\_dms\_GetDeviceHardwareRev, [1235](#)
- unpack\_dms\_GetDeviceMfr, [1235](#)
- unpack\_dms\_GetDeviceSerialNumbers, [1235](#)
- unpack\_dms\_GetFSN, [1237](#)
- unpack\_dms\_GetFirmwareInfo, [1236](#)
- unpack\_dms\_GetFirmwareRevision, [1236](#)
- unpack\_dms\_GetFirmwareRevisions, [1236](#)
- unpack\_dms\_GetHardwareRevision, [1237](#)
- unpack\_dms\_GetIMSI, [1237](#)
- unpack\_dms\_GetModelID, [1238](#)
- unpack\_dms\_GetNetworkTime, [1238](#)
- unpack\_dms\_GetPRLVersion, [1239](#)
- unpack\_dms\_GetPower, [1238](#)
- unpack\_dms\_GetSerialNumbers, [1239](#)
- unpack\_dms\_GetUSBComp, [1239](#)
- unpack\_dms\_GetVoiceNumber, [1240](#)
- unpack\_dms\_SLQSDmsSwiGetResetInfo, [1243](#)
- unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind, [1243](#)
- unpack\_dms\_SLQSDmsSwiIndicationRegister, [1243](#)
- unpack\_dms\_SLQSGetBandCapability, [1244](#)
- unpack\_dms\_SLQSSwiClearDyingGaspStatistics, [1244](#)
- unpack\_dms\_SLQSSwiGetDyingGaspCfg, [1244](#)
- unpack\_dms\_SLQSSwiGetDyingGaspStatistics, [1245](#)
- unpack\_dms\_SLQSSwiGetFirmwareCurr, [1245](#)
- unpack\_dms\_SLQSSwiGetFwUpdateStatus, [1245](#)
- unpack\_dms\_SLQSSwiSetDyingGaspCfg, [1246](#)
- unpack\_dms\_SetCrashAction, [1240](#)
- unpack\_dms\_SetCustFeature, [1240](#)
- unpack\_dms\_SetCustFeaturesV2, [1241](#)
- unpack\_dms\_SetEventReport, [1241](#)
- unpack\_dms\_SetEventReport\_ind, [1241](#)
- unpack\_dms\_SetFirmwarePreference, [1242](#)
- unpack\_dms\_SetPower, [1242](#)
- unpack\_dms\_SetUSBComp, [1242](#)
- unpack\_dms\_UIMGetICCID, [1246](#)
- dms\_ActivationStatusTlv, [219](#)
- activationStatus, [220](#)
- TlvPresent, [220](#)
- dms\_OperatingModeTlv, [220](#)
- operatingMode, [221](#)
- TlvPresent, [221](#)
- dmsCurrentPRLInfo, [221](#)
- pPRLPreference, [221](#)
- pPRLVersion, [221](#)
- qaGobiApiDms.h, [1408](#)
- dmsIndicationRegisterReq, [224](#)
- pSwiGetResetInd, [224](#)
- dmsSwiGetResetInfo, [225](#)
- source, [225](#)
- type, [225](#)
- Domain, [225](#)
- domainLen, [226](#)
- domainName, [226](#)
- domain
- DomainNameList, [226](#)
- wds\_DomainNameList, [1176](#)
- domainLen
- Domain, [226](#)
- wds\_Domain, [1175](#)
- DomainList
- unpack\_wds\_SLQSGetRuntimeSettings\_t, [1082](#)
- domainName
- Domain, [226](#)
- wds\_Domain, [1175](#)
- DomainNameList, [226](#)
- domain, [226](#)
- numInstances, [226](#)
- dormancyStatAvail
- unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- dormancyState
- unpack\_wds\_GetDormancyState\_t, [1073](#)
- DormancyStatus
- DUNCallInfoInd, [230](#)
- dormancyStatus
- pack\_wds\_SLQSSetWdsEventCallback\_t, [651](#)
- unpack\_wds\_SLQSGetDUNCallInfo\_t, [1080](#)
- unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- downLink
- NSSAudioCtrl, [571](#)
- dscp
- QosMap, [733](#)
- dtmSupp
- GSMSysInfo, [300](#)
- nas\_GSMSysInfo, [462](#)
- dtmSuppValid
- GSMSysInfo, [300](#)
- nas\_GSMSysInfo, [462](#)
- dunchannelRate, [230](#)
- CurrChanRxRate, [230](#)
- CurrChanTxRate, [230](#)
- MaxChanRxRate, [230](#)
- MaxChanTxRate, [230](#)
- Duration
- pack\_nas\_SetNetworkPreference\_t, [598](#)

- unpack\_nas\_GetNetworkPreference\_t, 993
- eCTL
  - common.h, 1211
- eDMS
  - common.h, 1211
- eGOBI\_DEV\_SERIES\_9X15
  - qaGobiApiFms.h, 1449
- eGOBI\_DEV\_SERIES\_9X30
  - qaGobiApiFms.h, 1449
- eGOBI\_DEV\_SERIES\_G3K
  - qaGobiApiFms.h, 1449
- eGOBI\_DEV\_SERIES\_NON\_GOBI
  - qaGobiApiFms.h, 1449
- eGOBI\_DEV\_SERIES\_SIERRA\_GOBI
  - qaGobiApiFms.h, 1449
- eGOBI\_DEV\_SERIES\_UNKNOWN
  - qaGobiApiFms.h, 1449
- eGOBI\_IMG\_CAR\_3
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_AERIS
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_ALLTEL
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_AMX\_TELCEL
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_ATT
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_BELL
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_BHARTI
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_BRASIL\_VIVO
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_CHINA\_MOBILE
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_CHINA\_TELECOM
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_CHINA\_UNICOM
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_EMOBILE
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_FACTORY
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_GENERIC
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_GENERIC\_CDMA
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_IUSACELL
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_KDDI
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_KT\_FREETEL
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_LEAP
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_METROPCS
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_NETCOM
  - qaGobiApiFms.h, 1450
- qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_NORF
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_NTT\_DOCOMO
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_O2
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_OMH
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_ORANGE
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_RELIANCE1
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_RELIANCE2
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_ROGERS
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_SFR
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_SINGTEL\_OPTUS
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_SK\_TELCOM1
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_SK\_TELCOM2
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_SOFTBANK
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_SPRINT
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_SWISSCOM
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TATA
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TELCOM\_ITALIA
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TELCOM\_NZ
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TELEFONICA
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TELNOR
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TELIASONERA
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TELSTRA1
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TELSTRA2
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TELUS
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_TMOBILE
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_US
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_VERIZON
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_CAR\_VODAFONE
  - qaGobiApiFms.h, 1450
- eGOBI\_IMG\_GPS\_ASSISTED



- qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_GPS\_NO\_XTRA
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_GPS\_NONE
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_GPS\_STAND\_ALONE
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_REG\_ASIA
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_REG\_AUS
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_REG\_EU
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_REG\_GLOBAL
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_REG\_LA
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_REG\_NA
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_TECH\_CDMA
  - qaGobiApiFms.h, [1451](#)
- eGOBI\_IMG\_TECH\_UMTS
  - qaGobiApiFms.h, [1451](#)
- eGobi\_DEV\_SERIES\_MC83
  - qaGobiApiFms.h, [1449](#)
- eIND
  - common.h, [1212](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_100
  - nas.h, [1265](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_15
  - nas.h, [1265](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_25
  - nas.h, [1265](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_50
  - nas.h, [1265](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_6
  - nas.h, [1265](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_75
  - nas.h, [1265](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_CONFIGURED\_ACTIVATED
  - nas.h, [1265](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_CONFIGURED\_DEACTIVATED
  - nas.h, [1265](#)
- eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_DECONFIGURED
  - nas.h, [1265](#)
- eLOC
  - common.h, [1211](#)
- eLOG\_DEBUG
  - common.h, [1211](#)
- eLOG\_FATAL
  - common.h, [1211](#)
- eLOG\_INFO
  - common.h, [1211](#)
- eLOG\_WARN
  - common.h, [1211](#)
- eNAS
  - common.h, [1211](#)
- eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_100
  - qaGobiApiNas.h, [1492](#)
- eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_15
  - qaGobiApiNas.h, [1492](#)
- eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_25
  - qaGobiApiNas.h, [1492](#)
- eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_50
  - qaGobiApiNas.h, [1492](#)
- eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_6
  - qaGobiApiNas.h, [1492](#)
- eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_75
  - qaGobiApiNas.h, [1492](#)
- eNAS\_LTE\_CPHY\_SCELL\_STATE\_CONFIGURED\_ACTIVATED
  - qaGobiApiNas.h, [1493](#)
- eNAS\_LTE\_CPHY\_SCELL\_STATE\_CONFIGURED\_DEACTIVATED
  - qaGobiApiNas.h, [1493](#)
- eNAS\_LTE\_CPHY\_SCELL\_STATE\_DECONFIGURED
  - qaGobiApiNas.h, [1493](#)
- eNAS\_RADIO\_IF\_GSM
  - qaGobiApiNas.h, [1492](#)
- eNAS\_RADIO\_IF\_LTE
  - qaGobiApiNas.h, [1492](#)
- eNAS\_RADIO\_IF\_TDSCDMA
  - qaGobiApiNas.h, [1492](#)
- eNAS\_RADIO\_IF\_UMTS
  - qaGobiApiNas.h, [1492](#)
- eQA\_QMI\_SVC\_NA
  - qaGobiApiCbk.h, [1349](#)
- eQA\_QMI\_SVC\_NAS
  - qaGobiApiCbk.h, [1349](#)
- eQA\_QMI\_SVC\_WDS
  - qaGobiApiCbk.h, [1349](#)
- eQCWWAN\_ERR\_API\_MUTEX\_TIMEOUT
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_BUFFER\_SZ
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_CANCEL\_OP
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_DRIVER
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_ENUM\_BEGIN
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_ENUM\_END
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_FILE\_COPY
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_FILE\_OPEN
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_GENERAL
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_INTERNAL
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_INVALID\_ARG
  - qmerrno.h, [1735](#)

eQCWWAN\_ERR\_INVALID\_DEVID  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_INVALID\_FILE  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_INVALID\_QMI\_RSP  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_INVALID\_XID  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_MALFORMED\_QMI\_RSP  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_MEMORY  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_MULTIPLE\_DEVICES  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_MULTIPLE\_SMS\_UNSUPPORTED  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_NO\_CANCELABLE\_OP  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_NO\_CONNECTION  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_NO\_DEVICE  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_NO\_SIGNAL  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_NONE  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_NULL\_TLV  
     qmerrno.h, [1739](#)  
 eQCWWAN\_ERR\_OFFLINE  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_PDU\_GENERATION  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_ABORTED  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_ACCESS\_DENIED  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_ACK\_NOT\_SENT  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_ARG\_TOO\_LONG  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_AUTHENTICATION\_FAILED  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_AUTHENTICATION\_LOCK  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_BUNDLING\_NOT\_SUPPORTED  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_CALL\_FAILED  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_CARD\_BUSY\_RSP  
     qmerrno.h, [1739](#)  
 eQCWWAN\_ERR\_QMI\_CARD\_CALL\_CONTROL\_FAILED  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_CAT\_END  
     qmerrno.h, [1739](#)  
 eQCWWAN\_ERR\_QMI\_CAT\_START  
     qmerrno.h, [1739](#)  
 eQCWWAN\_ERR\_QMI\_CAUSE\_CODE  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_CLIENT\_IDS\_EXHAUSTED  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_CONNECT  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_QMI\_DEVICE\_IN\_USE  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_DEVICE\_NOT\_READY  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_DEVICE\_STORAGE\_FULL  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_DISABLED  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_ENCODING  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_ENVELOPE\_CMD\_FAILURE  
     qmerrno.h, [1739](#)  
 eQCWWAN\_ERR\_QMI\_EVENT\_REG\_FAILED  
     qmerrno.h, [1739](#)  
 eQCWWAN\_ERR\_QMI\_EXTENDED\_INTERNAL  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_FDN\_RESTRICT  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_FLOW\_SUSPENDED  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_GENERAL  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_HARDWARE\_RESTRICTED  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_IFACE  
     qmerrno.h, [1735](#)  
 eQCWWAN\_ERR\_QMI\_INCOMPATIBLE\_STATE  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_INCORRECT\_FLOW\_FILTER  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_INCORRECT\_PIN  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_INFO\_UNAVAILABLE  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_INJECT\_TIMEOUT  
     qmerrno.h, [1738](#)  
 eQCWWAN\_ERR\_QMI\_INSUFFICIENT\_RESOURCE-  
     S  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_INTERFACE\_NOT\_FOUND  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_INTERNAL  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_INVALID\_ARG  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_INVALID\_CLIENT\_ID  
     qmerrno.h, [1736](#)  
 eQCWWAN\_ERR\_QMI\_INVALID\_DATA\_FORMAT  
     qmerrno.h, [1737](#)  
 eQCWWAN\_ERR\_QMI\_INVALID\_ENVELOPE\_CMD  
     qmerrno.h, [1739](#)  
 eQCWWAN\_ERR\_QMI\_INVALID\_HANDLE

- qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_ID
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_INDEX
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_IP\_FAMILY\_PREF
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_MCAST\_HANDLE
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_MESSAGE\_ID
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_OPERATION
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PDP\_TYPE
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PINID
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PROFILE
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PROFILE\_TYPE
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PS\_ATTACH\_ACTI-  
ON
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_QMI\_CMD
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_QOS\_ID
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_REGISTER\_ACTIO-  
N
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_SERVICE\_TYPE
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_TECH\_PREF
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_TERMINAL\_RSP
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_TRANSITION
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_TX\_ID
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_MALFORMED\_MSG
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_MAX
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_MAX\_MCAST\_REQUESTS\_I-  
N\_USE
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_MAX\_QOS\_REQUESTS\_IN\_  
USE
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_MESSAGE\_DELIVERY\_FAIL-  
URE
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_MESSAGE\_NOT\_SENT
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_MISSING\_ARG
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_MSG\_BLOCKED
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_NETWORK\_ABORTED
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_NETWORK\_NOT\_READY
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_NETWORK\_QOS\_UNAWARE
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_NO\_EFFECT
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_NO\_ENTRY
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_NO\_FREE\_PROFILE
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_NO\_MEMORY
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_NO\_NETWORK\_FOUND
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_NO\_RADIO
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_NO\_SUBSCRIPTION
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_NO\_THRESHOLDS
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_NOT\_A\_MCAST\_IFACE
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_NOT\_PROVISIONED
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_NOT\_SUPPORTED
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_OFFSET
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_OP\_DEVICE\_UNSUPPORTE-  
D
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_OP\_NETWORK\_UNSUPPOR-  
TED
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_OP\_PARTIAL\_FAILURE
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_OUT\_OF\_CALL
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_PIN\_BLOCKED
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_PIN\_PERM\_BLOCKED
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_POLICY\_MISMATCH
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_REQ
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_QMI\_REQ\_SCH
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_QMI\_REQ\_TO
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_QMI\_REQUESTED\_NUM\_UNSUP-  
PORTED
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_RSP

- qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_QMI\_RSP\_TO
  - qmerrno.h, [1735](#)
- eQCWWAN\_ERR\_QMI\_SEGMENT\_ORDER
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_SEGMENT\_TOO\_LONG
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_SESSION\_INACTIVE
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_SESSION\_INVALID
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_SESSION\_OWNERSHIP
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_SIM\_FILE\_NOT\_FOUND
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_SIM\_NOT\_INITIALIZED
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_SMSC\_ADDR
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_SUPS\_FAILURE\_CAUSE
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_TPDU\_TYPE
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_QMI\_UNABORTABLE\_TRANSACTION
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_QMI\_UNKNOWN
  - qmerrno.h, [1737](#)
- eQCWWAN\_ERR\_QMI\_WIDTH
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_RESET
  - qmerrno.h, [1736](#)
- eQCWWAN\_ERR\_SWICM\_AM\_VERS\_ERROR
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_CALL\_IN\_PROGRESS
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_END
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWICM\_FAILED\_TO\_KILL\_SDK\_PROCESS
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_INVALID\_SESSION\_ID
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_INVALID\_V4\_SESSION\_ID
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_INVALID\_V6\_SESSION\_ID
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_NOT\_IMPLEMENTED
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_QMI\_CLNT\_NOT\_SUPPORTED
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_QMI\_SVC\_NOT\_SUPPORTED
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_SM\_NO\_AVAILABLE\_SESSIONS
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_SOCKET\_IN\_USE
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_START
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_TIMEOUT
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_V4DWN\_V6DWN
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_V4DWN\_V6UP
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_V4UP\_V6DWN
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWICM\_V4UP\_V6UP
  - qmerrno.h, [1738](#)
- eQCWWAN\_ERR\_SWIDCS\_APP\_DISCONNECTED
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_DEVNODE\_NOT\_FOUND
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_END
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_FILEIO\_ERR
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_IOCTL\_ERR
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_START
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_CORRUPTED\_FW\_IMAGE
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_END
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FILE\_NOT\_FOUND
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FIRMWARE\_NOT\_DOWNLOADED
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_ENTER\_DOWNLOAD\_MODE
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_FLASH\_COMPLETE
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_PREFERENCE\_MISMATCH
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_UPDATE\_FAIL
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_UPDATE\_SUCCESS
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_WAIT\_FOR\_REBOOT
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_INVALID\_CRASH\_STATE
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_INVALID\_PATH
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_OPENING\_DIR

- qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_OPENING\_FILE
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_START
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWISM\_END
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_BEARER\_DATA\_NOT\_FOUND
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_MSG\_CORRUPTED
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_MSG\_LEN\_TOO\_LONG
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_SMSC\_NUM\_CORRUPTED
  - qmerrno.h, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_START
  - qmerrno.h, [1739](#)
- eQMI\_LOC\_SESS\_STATUS\_FAILURE
  - loc.h, [1254](#)
- eQMI\_LOC\_SESS\_STATUS\_IN\_PROGRESS
  - loc.h, [1254](#)
- eQMI\_LOC\_SESS\_STATUS\_SUCCESS
  - loc.h, [1254](#)
- eQMI\_LOC\_SESS\_STATUS\_TIMEOUT
  - loc.h, [1254](#)
- eQOS
  - common.h, [1211](#)
- eREQ
  - common.h, [1212](#)
- eRSP
  - common.h, [1212](#)
- eSMS
  - common.h, [1211](#)
- eSWILOC
  - common.h, [1212](#)
- eSWIOMA
  - common.h, [1212](#)
- eSYS\_SRV\_DOMAIN\_CAMPED
  - qaGobiApiNas.h, [1492](#)
- eSYS\_SRV\_DOMAIN\_CS\_ONLY
  - qaGobiApiNas.h, [1492](#)
- eSYS\_SRV\_DOMAIN\_CS\_PS
  - qaGobiApiNas.h, [1492](#)
- eSYS\_SRV\_DOMAIN\_NO\_SRV
  - qaGobiApiNas.h, [1492](#)
- eSYS\_SRV\_DOMAIN\_PS\_ONLY
  - qaGobiApiNas.h, [1492](#)
- eSYS\_SRV\_DOMAIN\_UNKNOWN
  - qaGobiApiNas.h, [1492](#)
- eSetServiceAutomaticTrackingDisable
  - qaGobiApiPds.h, [1529](#)
- eSetServiceAutomaticTrackingEnable
  - qaGobiApiPds.h, [1529](#)
- eTIMEOUT\_10\_S
  - common.h, [1212](#)
- eTIMEOUT\_20\_S
  - common.h, [1212](#)
- eTIMEOUT\_2\_S
  - common.h, [1212](#)
- eTIMEOUT\_300\_S
  - common.h, [1212](#)
- eTIMEOUT\_30\_S
  - common.h, [1212](#)
- eTIMEOUT\_5\_S
  - common.h, [1212](#)
- eTIMEOUT\_60\_S
  - common.h, [1212](#)
- eTIMEOUT\_8\_S
  - common.h, [1212](#)
- eTIMEOUT\_DEFAULT
  - common.h, [1212](#)
- eTLV\_3GPP\_NETWORK\_INFO
  - qaNasPerformNetworkScan.h, [1733](#)
- eTLV\_CBK\_ALPHA\_IDENTIFIER
  - qaCbkCatEventReportInd.h, [1288](#)
- eTLV\_CBK\_DISPLAY\_TEXT
  - qaCbkCatEventReportInd.h, [1288](#)
- eTLV\_CBK\_END\_PROACTIVE\_SESSION
  - qaCbkCatEventReportInd.h, [1289](#)
- eTLV\_CBK\_GET\_IN\_KEY
  - qaCbkCatEventReportInd.h, [1288](#)
- eTLV\_CBK\_GET\_INPUT
  - qaCbkCatEventReportInd.h, [1288](#)
- eTLV\_CBK\_LANGUAGE\_NOTIFICATION
  - qaCbkCatEventReportInd.h, [1289](#)
- eTLV\_CBK\_REFRESH
  - qaCbkCatEventReportInd.h, [1289](#)
- eTLV\_CBK\_SELECT\_ITEM
  - qaCbkCatEventReportInd.h, [1288](#)
- eTLV\_CBK\_SETUP\_EVENT\_LIST
  - qaCbkCatEventReportInd.h, [1289](#)
- eTLV\_CBK\_SETUP\_IDLE\_MODE\_TEXT
  - qaCbkCatEventReportInd.h, [1289](#)
- eTLV\_CBK\_SETUP\_MENU
  - qaCbkCatEventReportInd.h, [1288](#)
- eTLV\_END\_PROACTIVE\_SESSION\_LENGTH
  - qaCbkCatEventReportInd.h, [1289](#)
- eTLV\_IND\_OMA\_DM\_CONFIG
  - qaCbkSwiOmaDmEventReportInd.h, [1290](#)
- eTLV\_IND\_OMA\_DM\_FOTA
  - qaCbkSwiOmaDmEventReportInd.h, [1290](#)
- eTLV\_IND\_OMA\_DM\_NOT
  - qaCbkSwiOmaDmEventReportInd.h, [1290](#)
- eTLV\_REFRESH\_LENGTH
  - qaCbkCatEventReportInd.h, [1289](#)
- eTLV\_RF\_BAND\_INFO
  - qaNasGetRFBandInfo.h, [1732](#)
- eTLV\_SETUP\_EVENT\_LIST\_LENGTH
  - qaCbkCatEventReportInd.h, [1289](#)
- eTMD
  - common.h, [1212](#)
- eUIM
  - common.h, [1211](#)
- eWDS

- common.h, [1211](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP2\_ERR\_INVALID\_IDENT\_FOR\_PROFILE
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_ACCESS\_ERR
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_CONTEXT\_NOT\_DEFINED
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_ERR\_OUT\_OF\_PROFILES
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_INVALID\_PROFILE\_FAMILY
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_READ\_ONLY\_FLAG\_SET
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_VALID\_FLAG\_NOT\_SET
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_END
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_INVALID\_PROFILE\_FAMILY
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_HNDL
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_IDENT
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_OP
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_PROFILE\_NUM
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_PROFILE\_TYPE
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_SUBS\_ID
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_LEN\_INVALID
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_LIB\_NOT\_INITED
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_FAIL
  - qmerrno.h, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_LIST\_END
  - qmerrno.h, [1740](#)
- ECIOThresListLen
  - ECIOThresh, [232](#)
- ECIOThresh, [231](#)
  - ECIOThresListLen, [232](#)
  - pECIOThresList, [232](#)
- ECTCallState
  - ECTNum, [233](#)
- ECTNum, [232](#)
  - ECTCallState, [233](#)
  - number, [233](#)
  - presentationInd, [233](#)
- eDevState
  - qaGobiApiCbk.h, [1306](#)
- eDevice
  - sGetDeviceSeriesResult, [795](#)
- eGetDeviceSeries
  - qaGobiApiFms.h, [1452](#)
- eGobiDeviceSeries
  - qaGobiApiFms.h, [1449](#)
- eGobiImageCarrier
  - qaGobiApiFms.h, [1449](#)
- eGobiImageGPS
  - qaGobiApiFms.h, [1450](#)
- eGobiImageRegion
  - qaGobiApiFms.h, [1451](#)
- eGobiImageTech
  - qaGobiApiFms.h, [1451](#)
- eLOG\_LEVEL
  - common.h, [1211](#)
- EMTlv
  - NASQmiCbkNasSystemSelPrefInd, [550](#)
- eQCWWANError
  - qmerrno.h, [1735](#)
- eQMI\_SVC
  - common.h, [1211](#)
- eQMISARRFState
  - qaGobiApiSar.h, [1554](#)
- eQaQMIService
  - qaGobiApiCbk.h, [1349](#)
- ERIFileparams, [234](#)
  - pFile, [234](#)
  - pFileSize, [234](#)
  - qaGobiApiDms.h, [1408](#)
- eSMSEventType
  - qaGobiApiCbk.h, [1306](#)
- ESNString
  - unpack\_dms\_GetDeviceSerialNumbers\_t, [957](#)
- eSYS\_SRV\_DOMAIN
  - qaGobiApiNas.h, [1492](#)
- ETWSPLMNInfo
  - eTWSPLMNInfoTlv, [236](#)
- eTWSPLMNInfoTlv, [236](#)
  - ETWSPLMNInfo, [236](#)
  - TlvPresent, [236](#)
- ETWSPLMNTlv
  - unpack\_sms\_SetNewSMSCallback\_ind\_t, [1052](#)
- ETWSTlv
  - unpack\_sms\_SetNewSMSCallback\_ind\_t, [1052](#)
- eTimeout
  - common.h, [1212](#)



- EVENT\_MASK\_CARD
  - qaGobiApiCbk.h, [1303](#)
- eValid
  - LibPackTFTIDParams, [371](#)
  - TFTIDParams, [881](#)
- EarMute
  - GetAudioProfileResp, [259](#)
  - GetM2MAudioProfileResp, [277](#)
  - GetM2MAVMuteResp, [279](#)
  - SetAudioProfileReq, [771](#)
  - SetM2MAVMuteReq, [784](#)
- earfcn
  - infoInterFreq, [336](#)
  - LTEInfoIntrafreq, [411](#)
  - ltePCI, [414](#)
  - nas\_infoInterFreq, [469](#)
  - nas\_LTEInfoIntrafreq, [475](#)
  - nas\_umtsLTENbrCell, [513](#)
  - umtsLTENbrCell, [942](#)
- earfcn0
  - lteEARFCN, [404](#)
- earfcn1
  - lteEARFCN, [404](#)
- ecio
  - CDMASSInfo, [160](#)
  - cdmaSSInfo, [160](#)
  - ecioListElement, [231](#)
  - HDRSSInfo, [308](#)
  - hdrSSInfo, [309](#)
  - nas\_ecioListElement, [452](#)
  - nas\_UMTSInfo, [511](#)
  - rxInfo, [750](#)
  - TDSCDMASigInfoExt, [876](#)
  - tdscdmaSigInfoExt, [876](#)
  - UMTSInfo, [940](#)
- ecioDelta
  - nas\_SLQSSignalStrengthsIndReq, [499](#)
  - SLQSSignalStrengthsIndReq, [818](#)
- ecioInfo
  - nas\_SLQSSignalStrengthsInformation, [500](#)
  - SLQSSignalStrengthsInformation, [820](#)
- ecioList
  - slqsSignalStrengthInfo, [816](#)
  - unpack\_nas\_SLQSGetSignalStrength\_t, [1005](#)
- ecioListElement, [231](#)
  - ecio, [231](#)
  - radiolf, [231](#)
- ecioListLen
  - slqsSignalStrengthInfo, [816](#)
  - unpack\_nas\_SLQSGetSignalStrength\_t, [1005](#)
- ecioThresholdList
  - nas\_SLQSSignalStrengthsIndReq, [499](#)
  - SLQSSignalStrengthsIndReq, [818](#)
- ecioThresholdListLen
  - nas\_SLQSSignalStrengthsIndReq, [499](#)
  - SLQSSignalStrengthsIndReq, [819](#)
- egprsSupp
  - GSMSysInfo, [300](#)
  - nas\_GSMSysInfo, [462](#)
- egprsSuppValid
  - GSMSysInfo, [300](#)
  - nas\_GSMSysInfo, [462](#)
- elevation
  - satelliteInfo, [758](#)
- EmerMode
  - NASEmergencyModeTlv, [525](#)
- emmConnState
  - LTEInfo, [408](#)
  - nas\_LTEInfo, [472](#)
- emmState
  - LTEInfo, [408](#)
  - nas\_LTEInfo, [472](#)
- emmSubState
  - LTEInfo, [408](#)
  - nas\_LTEInfo, [473](#)
- Enable
  - SetM2MAudioLPBKReq, [781](#)
- enable
  - pack\_qos\_SLQSSetQosEventCallback\_t, [618](#)
- enabled
  - unpack\_wds\_GetMobileIPProfile\_t, [1074](#)
- EncryptProt
  - protocolSubtypeElement, [694](#)
- EncryptedPIN1
  - pack\_uim\_ChangePin\_t, [629](#)
  - pack\_uim\_SetPinProtection\_t, [631](#)
  - pack\_uim\_UnblockPin\_t, [634](#)
- encryptedPIN1, [233](#)
  - pin1Len, [234](#)
  - pin1Val, [234](#)
- EndProactiveSession
  - CatEndProactiveSessionTlv, [148](#)
- EngineState
  - GPSSStateInfo, [292](#)
- engineState
  - QmiCbkLocEngineStateInd, [702](#)
  - unpack\_loc\_EngineState\_Ind\_t, [980](#)
- eqmiCbkSetStatus
  - sms.h, [1754](#)
- error
  - unpack\_wds\_GetLastMobileIPError\_t, [1073](#)
- errorClass
  - SMSAsyncRawSend\_s, [825](#)
- errorRate
  - errorRateListElement, [236](#)
  - nas\_errorRateListElement, [453](#)
- errorRateInfo
  - nas\_SLQSSignalStrengthsInformation, [500](#)
  - SLQSSignalStrengthsInformation, [820](#)
- errorRateList
  - slqsSignalStrengthInfo, [816](#)
  - unpack\_nas\_SLQSGetSignalStrength\_t, [1005](#)
- errorRateListElement, [234](#)
  - errorRate, [236](#)
  - radiolf, [236](#)
- errorRateListLen

- slqsSignalStrengthInfo, 816
- unpack\_nas\_SLQSGetSignalStrength\_t, 1005
- errorState
  - slotInf, 801
  - slotInfo, 803
  - uim\_slotInfo, 911
- esn
  - unpack\_dms\_GetSerialNumbers\_t, 963
- esnSize
  - serialNumbersInfo, 761
  - unpack\_dms\_GetDeviceSerialNumbers\_t, 957
- EspSpi
  - unpack\_qos\_swIQosFilter\_t, 1042
- EtwsMessageInfo
  - sMSEtwsMessageTlv, 828
- event
  - unpack\_qos\_SLQSSetQosPriEventCallback\_ind\_t, 1038
  - unpack\_qos\_SLQSSetQosStatusCallback\_ind\_t, 1040
- event\_Index
  - QmiCbkCatEventStatusReportInd, 701
- EventID
  - CatCommonEventTlv, 147
- EventLength
  - CatCommonEventTlv, 147
- eventMask
  - CATEventDataType, 148
  - pack\_uim\_SLQSUIEventRegister\_t, 632
  - UIEventRegisterReqResp, 917
  - unpack\_uim\_SLQSUIEventRegister\_t, 1067
- eventRegister
  - LOCEventRegisterReqResp, 392
  - pack\_loc\_EventRegister\_t, 592
- eventType
  - unpack\_swioima\_SLQSOMADMAAlertCallback\_ind\_t, 1057
- evrcCapability
  - prefVoiceSO, 679
- executingImage
  - FMSImageIDEntries, 247
  - ImageIDEntries, 315
- exponent
  - pktErrRate, 673
  - unpack\_qos\_pktErrRate\_t, 1030
- extBit
  - calledPartySubAdd, 133
- extDispInfo
  - extDispRecInfo, 237
- extDispInfoLen
  - extDispRecInfo, 237
- extDispRecInfo, 236
  - dispType, 237
  - extDispInfo, 237
  - extDispInfoLen, 237
- ExtErrorCode
  - PackCreateProfileOut, 654
- extPowerState
  - LOCExtPowerStateReqResp, 392
  - pack\_loc\_SetExtPowerState\_t, 592
- extendedErrorCode
  - unpack\_wds\_SLQSDeleteProfile\_t, 1077
- FIRST\_INSTANCE
  - qaGobiApiCbk.h, 1304
- FLOAT
  - SwiDataTypes.h, 1761
- FMSImageElement, 244
  - buildId, 245
  - buildIdLength, 245
  - imageId, 245
  - imageType, 245
- FMSImageIDEntries, 246
  - executingImage, 247
  - imageIDElement, 247
  - imageIDSize, 247
  - imageType, 247
  - maxImages, 247
- FMSImageIDElement, 245
  - buildID, 246
  - buildIDLength, 246
  - failureCount, 246
  - imageID, 246
  - storageIndex, 246
- FMSImageList, 247
  - imageIDEntries, 247
  - listSize, 247
- FMSPrefImageList, 248
  - listEntries, 248
  - listSize, 248
- FORBIDDEN\_INDEX
  - qaNasPerformNetworkScan.h, 1733
- FOTAUpdate
  - \_SLQSOMADMSettingsReqParams, 77
  - \_SLQSOMADMSettingsReqParams3, 78
  - pack\_swioima\_SLQSOMADMSetSettings\_t, 628
  - unpack\_swioima\_SLQSOMADMGetSettings\_t, 1062
- FOTAdownload
  - \_SLQSOMADMSettingsReqParams, 77
  - \_SLQSOMADMSettingsReqParams3, 78
  - pack\_swioima\_SLQSOMADMSetSettings\_t, 628
  - unpack\_swioima\_SLQSOMADMGetSettings\_t, 1062
- FSNumber
  - FactorySequenceNumber, 237
- FactorySequenceNumber, 237
  - FSNumber, 237
- failureCount
  - FMSImageIDElement, 246
  - ImageIDElement, 314
- failureReason
  - ssdatasession\_params, 846
- failureReasonv4
  - ssdatasession\_params, 847
- failureReasonv6
  - ssdatasession\_params, 847



- family
  - pack\_wds\_GetDefaultProfileNum\_t, 637
  - pack\_wds\_SetDefaultProfileNum\_t, 641
- feature
  - depersonalizationInformation, 213
  - personalizationStatus, 665
- fileAttributes, 237
  - fileID, 241
  - fileSize, 241
  - fileType, 241
  - rawLen, 241
  - rawValue, 241
  - recordCount, 241
  - recordSize, 241
  - secActivate, 241
  - secActivateMask, 241
  - secDeactivate, 241
  - secDeactivateMask, 241
  - secIncrease, 241
  - secIncreaseMask, 241
  - secRead, 242
  - secReadMask, 242
  - secWrite, 242
  - secWriteMask, 242
- fileID
  - fileAttributes, 241
  - fileInfo, 242
  - uim\_fileInfo, 905
- fileIndex
  - pack\_uim\_ReadTransparent\_t, 630
  - UIMGetFileAttributesReq, 920
  - UIMReadTransparentReq, 924
- fileInfo, 242
  - fileID, 242
  - path, 242
  - pathLen, 242
- fileSize
  - fileAttributes, 241
- fileType
  - fileAttributes, 241
- fill\_pack\_ctx
  - common.h, 1212
- fill\_sdu\_hdr
  - common.h, 1212
- filterId
  - LibPackTFTIDParams, 371
  - TFTIDParams, 881
- Firmware Management Service (FMS), 40
- FirmwareID
  - fwinfo\_s, 249
- FirmwareUpdatStat, 242
  - plmgType, 244
  - pLogString, 244
  - pLogStringLength, 244
  - pRefData, 244
  - pRefString, 244
  - pRefStringLength, 244
  - ResCode, 244
- fix\_rate
  - pack\_swilloc\_SwiLocSetAutoStart\_t, 625
  - SwiLocGetAutoStartResp, 855
  - SwiLocSetAutoStartReq, 857
  - unpack\_swilloc\_SwiLocGetAutoStart\_t, 1056
- fix\_rate\_reported
  - SwiLocGetAutoStartResp, 855
  - unpack\_swilloc\_SwiLocGetAutoStart\_t, 1056
- fix\_type
  - pack\_swilloc\_SwiLocSetAutoStart\_t, 625
  - SwiLocGetAutoStartResp, 855
  - SwiLocSetAutoStartReq, 857
  - unpack\_swilloc\_SwiLocGetAutoStart\_t, 1056
- fix\_type\_reported
  - SwiLocGetAutoStartResp, 855
  - unpack\_swilloc\_SwiLocGetAutoStart\_t, 1056
- flags
  - sensorData, 759
- flowLabel
  - LibPackTFTIDParams, 371
  - TFTIDParams, 881
- fms.h, 1246
  - GetValidFwPriCombinations, 1248
  - pack\_fms\_GetImagesPreference, 1248
  - pack\_fms\_GetStoredImages, 1249
  - pack\_fms\_SetImagesPreference, 1249
  - unpack\_fms\_GetImagesPreference, 1249
  - unpack\_fms\_GetStoredImages, 1249
  - unpack\_fms\_SetImagesPreference, 1249
- Forbidden
  - nas\_QmiNas3GppNetworkInfo, 491
  - SlqsNas3GppNetworkInfo, 807
- ForceRev0
  - unpack\_nas\_GetCDMANetworkParameters\_t, 990
- ForceXTRADownload
  - qaGobiApiPds.h, 1529
- format
  - SMSTransferRouteMTMessage, 841
  - sMSTransferRouteMTMessage, 840
- ForwardMac
  - protocolSubtypeElement, 694
- fqdnAddr
  - PCSCFFQDNAddress, 657
  - wds\_PCSCFFQDNAddress, 1178
- fqdnLen
  - PCSCFFQDNAddress, 657
  - wds\_PCSCFFQDNAddress, 1178
- freeSlots
  - smsMaxStorageSizeResp, 832
- freq
  - NASPhyCaAggPcellInfo, 543
  - NASPhyCaAggScellIndType, 544
  - NASPhyCaAggScellInfo, 546
  - PhyCaAggPcellInfo, 667
  - PhyCaAggScellIndType, 669
  - PhyCaAggScellInfo, 671
- freqsLen
  - LTEInfoInterfreq, 409

- LTEInfoNeighboringGSM, [412](#)
  - LTEInfoNeighboringWCDMA, [413](#)
  - nas\_LTEInfoInterfreq, [473](#)
  - nas\_LTEInfoNeighboringGSM, [476](#)
  - nas\_LTEInfoNeighboringWCDMA, [477](#)
- fromServiceId
  - BroadcastConfig, [127](#)
- fumoResultCode
  - omaDmFotaTlvExt, [579](#)
- function
  - pack\_swiloc\_SwiLocSetAutoStart\_t, [625](#)
  - SwiLocGetAutoStartResp, [855](#)
  - SwiLocSetAutoStartReq, [857](#)
  - unpack\_swiloc\_SwiLocGetAutoStart\_t, [1056](#)
- function\_reported
  - SwiLocGetAutoStartResp, [855](#)
  - unpack\_swiloc\_SwiLocGetAutoStart\_t, [1056](#)
- FwAutoCheck
  - unpack\_swima\_SLQSOMADMGetSettings\_t, [1062](#)
- FwAvailability
  - unpack\_swima\_SLQSOMADMStartSession\_t, [1062](#)
- fwloadsize
  - omaDmFotaTlv, [577](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- fwinfo\_s, [248](#)
  - Carrier, [249](#)
  - FirmwareID, [249](#)
  - GPSCapability, [249](#)
  - Region, [249](#)
  - Technology, [249](#)
- fwloadComplete
  - omaDmFotaTlv, [577](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- fwvers
  - CurrentImgList, [189](#)
  - unpack\_dms\_SLQSSwiGetFirmwareCurr\_t, [974](#)
- g
  - qmifwinfo\_s, [719](#)
- gDIBitRate
  - LibPackQosClassID, [369](#)
  - QosClassID, [728](#)
- GERANInfo, [249](#)
  - arfcn, [251](#)
  - bsic, [251](#)
  - cellID, [251](#)
  - insNmrCellInfo, [251](#)
  - lac, [251](#)
  - nmrInst, [251](#)
  - plmn, [251](#)
  - rxLev, [251](#)
  - timingAdvance, [251](#)
- GPRSGrantedQoS
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1082](#)
- GPRSQoS, [287](#)
  - delayClass, [288](#)
  - meanThroughputClass, [288](#)
  - peakThroughputClass, [288](#)
  - precedenceClass, [288](#)
  - reliabilityClass, [288](#)
- GPRSRequestedQoS, [288](#)
  - delayClass, [289](#)
  - meanThroughputClass, [289](#)
  - peakThroughputClass, [289](#)
  - precedenceClass, [289](#)
  - reliabilityClass, [289](#)
- GPSCapability
  - fwinfo\_s, [249](#)
- GPSSLPM
  - pack\_dms\_SetCustFeature\_t, [583](#)
  - unpack\_dms\_GetCustFeature\_t, [954](#)
- GPSSel
  - pack\_dms\_SetCustFeature\_t, [583](#)
  - unpack\_dms\_GetCustFeature\_t, [954](#)
- GPSStateInfo, [289](#)
  - Altitude, [292](#)
  - EngineState, [292](#)
  - glo\_almanac\_sv\_msk, [293](#)
  - glo\_ephemeris\_sv\_msk, [293](#)
  - glo\_health\_sv\_msk, [293](#)
  - glo\_visible\_sv\_msk, [293](#)
  - gps\_almanac\_sv\_msk, [293](#)
  - gps\_ephemeris\_sv\_msk, [293](#)
  - gps\_health\_sv\_msk, [293](#)
  - gps\_visible\_sv\_msk, [293](#)
  - HorizontalUncertainty, [293](#)
  - lono\_valid, [293](#)
  - Latitude, [293](#)
  - Longitude, [293](#)
  - sbas\_almanac\_sv\_msk, [293](#)
  - sbas\_ephemeris\_sv\_msk, [293](#)
  - sbas\_health\_sv\_msk, [293](#)
  - sbas\_visible\_sv\_msk, [293](#)
  - Time\_uncert\_ms, [293](#)
  - TimeStmp\_gps\_week, [293](#)
  - TimeStmp\_tow\_ms, [293](#)
  - ValidMask, [293](#)
  - VerticalUncertainty, [293](#)
  - xtra\_start\_gps\_minutes, [293](#)
  - xtra\_start\_gps\_week, [293](#)
  - xtra\_valid\_duration\_hours, [293](#)
- GSMRSSIThresh, [295](#)
  - GSMRSSIThreshListLen, [296](#)
  - pGSMRSSIThreshList, [296](#)
- GSMRSSIThreshListLen
  - GSMRSSIThresh, [296](#)
  - nas\_GSMRSSIThresh, [458](#)
- GSMSSInfo
  - unpack\_nas\_SLQSNasGetSigInfo\_t, [1014](#)
- GSMSrvStatusInfo, [296](#)
  - isPrefDataPath, [297](#)
  - srvStatus, [297](#)
  - trueSrvStatus, [297](#)
- GSMSysInfo, [297](#)
  - cellId, [300](#)

- cellIdValid, [300](#)
- dtmSupp, [300](#)
- dtmSuppValid, [300](#)
- egprsSupp, [300](#)
- egprsSuppValid, [300](#)
- lac, [300](#)
- lacValid, [300](#)
- MCC, [300](#)
- MNC, [300](#)
- networkIdValid, [300](#)
- regRejectInfoValid, [300](#)
- rejCause, [300](#)
- rejectSrvDomain, [300](#)
- sysInfoGSM, [300](#)
- gUIBitRate
  - LibPackQosClassID, [369](#)
  - QosClassID, [728](#)
- GWAOPTlv
  - NASQmiCbkNasSystemSelPrefInd, [550](#)
- GWAcqOrderPref
  - NASGWAcqOrderPrefTlv, [534](#)
- GWAddressV4
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1082](#)
- gcDumpStrLen
  - CrashInfo, [182](#)
- Generator
  - GetAudioProfileReq, [257](#)
  - GetAudioVolTLBConfigReq, [260](#)
  - GetM2MAudioProfileResp, [277](#)
  - GetM2MAudioVolumeReq, [278](#)
  - SetAudioProfileReq, [771](#)
  - SetAudioVolTLBConfigReq, [773](#)
  - SetM2MAudioVolumeReq, [783](#)
- geoSysIdx
  - AddCDMASysInfo, [99](#)
  - AddSysInfo, [100](#)
  - nas\_AddCDMASysInfo, [434](#)
  - nas\_AddSysInfo, [434](#)
- geranArfcn
  - geranInstInfo, [252](#)
  - nas\_geranInstInfo, [456](#)
- geranBsicBcc
  - geranInstInfo, [252](#)
  - nas\_geranInstInfo, [456](#)
- geranBsicNcc
  - geranInstInfo, [252](#)
  - nas\_geranInstInfo, [456](#)
- geranInst
  - nas\_UMTSInfo, [511](#)
  - UMTSInfo, [940](#)
- GeranInstInfo
  - nas\_UMTSInfo, [511](#)
  - UMTSInfo, [940](#)
- geranInstInfo, [251](#)
  - geranArfcn, [252](#)
  - geranBsicBcc, [252](#)
  - geranBsicNcc, [252](#)
  - geranRssi, [252](#)
- geranRssi
  - geranInstInfo, [252](#)
  - nas\_geranInstInfo, [456](#)
- get\_version
  - common.h, [1212](#)
- GetACCOLC
  - qaGobiApiNas.h, [1493](#)
- GetANAAAAAuthenticationStatus
  - qaGobiApiNas.h, [1493](#)
- GetActivationState
  - qaGobiApiDms.h, [1412](#)
- getAllCallInfo
  - arrCallInfo, [116](#)
- getAllCallInformation, [252](#)
  - ALS, [253](#)
  - Callinfo, [253](#)
  - isEmpty, [253](#)
- GetAllCallRmtPtyName
  - arrRemotePartyName, [119](#)
- getAllCallRmtPtyName, [253](#)
  - callID, [253](#)
  - RemotePartyName, [253](#)
- getAllCallRmtPtyNum, [253](#)
  - callID, [254](#)
  - RemotePartyNum, [254](#)
- GetAudioPathConfigReq, [254](#)
  - Item, [254](#)
  - Profile, [255](#)
- GetAudioPathConfigResp, [255](#)
  - pCodecSTGain, [256](#)
  - pDTMFTXGain, [256](#)
  - pECMode, [256](#)
  - pMICGainSelect, [256](#)
  - pNSEnable, [256](#)
  - pRXAGCList, [257](#)
  - pRXAVCAGCSwitch, [257](#)
  - pRXAVCList, [257](#)
  - pRXPCMIIRFtr, [257](#)
  - pTXAGCList, [257](#)
  - pTXAVCSwitch, [257](#)
  - pTXGain, [257](#)
  - pTXPCMIIRFtr, [257](#)
- GetAudioProfileReq, [257](#)
  - Generator, [257](#)
- GetAudioProfileResp, [257](#)
  - EarMute, [259](#)
  - MicMute, [259](#)
  - Profile, [259](#)
  - Volume, [259](#)
- GetAudioVolTLBConfigReq, [259](#)
  - Generator, [260](#)
  - Item, [260](#)
  - Profile, [260](#)
  - Volume, [260](#)
- GetAudioVolTLBConfigResp, [260](#)
  - ResCode, [261](#)
- GetAutoconnect
  - qaGobiApiWds.h, [1689](#)

- GetByteTotals
  - qaGobiApiWds.h, 1690
- GetCDMANetworkParameters
  - qaGobiApiNas.h, 1493
- getCallFWExtInfo, 261
  - CallFWExtInfo, 261
  - numInstances, 261
- getCallFWInfo, 261
  - CallFWInfo, 262
  - numInstances, 262
- GetConnectionRate
  - qaGobiApiWds.h, 1690
- GetCustomFeatureV2
  - unpack\_dms\_GetCustFeaturesV2\_t, 955
- getCustomFeatureV2, 262
  - pCustSettingInfo, 262
  - pCustSettingList, 262
  - pGetCustomInput, 263
- getCustomInput, 263
  - cust\_id, 263
  - list\_type, 263
- getDUNCallInfoReq, 263
  - Mask, 264
  - pReportChannelRate, 265
  - pReportConnStatus, 265
  - pReportDataBearerTech, 265
  - pReportDormStatus, 265
  - pTransferStatInd, 265
- getDUNCallInfoResp, 265
  - pCallEndReason, 268
  - pChannelRate, 268
  - pConnectionStatus, 268
  - pDataBearerTech, 268
  - pDormancyStatus, 268
  - pLastCallDataBearerTech, 268
  - pLastCallRXOKBytesCnt, 268
  - pLastCallTXOKBytesCnt, 268
  - pMdmCallDurationActive, 268
  - pRXOKBytesCount, 268
  - pTXOKBytesCount, 268
- GetDataBearerTechnology
  - qaGobiApiWds.h, 1691
- GetDefaultProfile
  - qaGobiApiWds.h, 1692
- GetDefaultProfileLTE
  - qaGobiApiWds.h, 1694
- GetDefaultProfileNum
  - qaGobiApiWds.h, 1696
- GetDeviceCapabilities
  - qaGobiApiDms.h, 1413
- GetDormancyState
  - qaGobiApiWds.h, 1697
- getDyingGaspCfg, 268
  - pDestSMSContent, 268
  - pDestSMSNum, 268
- getDyingGaspStatistics, 269
  - pSMSAttemptedFlag, 269
  - pTimeStamp, 269
- GetErrRateResp, 269
  - pCDMAFrameErrRate, 270
  - pGSMBER, 270
  - pHDRPackErrRate, 270
  - pWCDMABER, 270
- GetFirmwareRevision
  - qaGobiApiDms.h, 1414
- GetFirmwareRevisions
  - qaGobiApiDms.h, 1415
- GetHRPDStatsResp, 270
  - pDRCParams, 271
  - pPilotSetData, 271
  - pUATI, 271
- GetHardwareRevision
  - qaGobiApiDms.h, 1415
- GetHomeNetwork
  - qaGobiApiNas.h, 1496
- GetHomeNetwork3GPP2
  - qaGobiApiNas.h, 1497
- GetIMSI
  - qaGobiApiDms.h, 1417
- GetIMSSMSConfigParams, 271
  - pPhoneCtxtURI, 272
  - pPhoneCtxtURILen, 272
  - pSMSFormat, 272
  - pSMSOverIPNwInd, 272
  - pSettingResp, 272
- GetIMSUserConfigParams, 272
  - pIMSDomain, 273
  - pIMSDomainLen, 273
  - pSettingResp, 273
- GetIMSVolIPConfigResp, 273
  - pAmrMode, 275
  - pAmrOctetAligned, 275
  - pAmrWBMode, 275
  - pAmrWBOctetAligned, 275
  - pAmrWbEnable, 275
  - pMinSessionExpiryTimer, 275
  - pRTPRTCPInactTimer, 275
  - pRingBackTimer, 275
  - pRingingTimer, 275
  - pScrAmrEnable, 275
  - pScrAmrWbEnable, 275
  - pSessionExpiryTimer, 275
  - pSettingResp, 275
- GetIPAddressLTE
  - qaGobiApiWds.h, 1697
- GetImageStore
  - qaGobiApiFms.h, 1452
- GetImagesPreference
  - qaGobiApiFms.h, 1452
- getIndicationRegResp
  - qaGobiApiSms.h, 1558
- GetInstIDResp, 275
  - pIPFamily, 275
  - pInstanceID, 275
- GetLastMobileIPError
  - qaGobiApiWds.h, 1698

- GetM2MAVMuteReq, [278](#)
  - Profile, [279](#)
- GetM2MAVMuteResp, [279](#)
  - CwtMute, [279](#)
  - EarMute, [279](#)
  - MicMute, [279](#)
- GetM2MAudioProfileReq, [275](#)
  - pGenerator, [276](#)
- GetM2MAudioProfileResp, [276](#)
  - CwtMute, [277](#)
  - EarMute, [277](#)
  - Generator, [277](#)
  - MicMute, [277](#)
  - Profile, [277](#)
  - Volume, [277](#)
- GetM2MAudioVolumeReq, [277](#)
  - Generator, [278](#)
  - Profile, [278](#)
- GetM2MAudioVolumeResp, [278](#)
  - Level, [278](#)
- GetM2MSpkrGainReq, [280](#)
  - Profile, [280](#)
- GetM2MSpkrGainResp, [280](#)
  - Value, [280](#)
- GetManufacturer
  - qaGobiApiDms.h, [1417](#)
- GetMobileIP
  - qaGobiApiWds.h, [1698](#)
- GetMobileIPProfile
  - qaGobiApiWds.h, [1699](#)
- GetModelID
  - qaGobiApiDms.h, [1418](#)
- getMsgWaitingInfo, [280](#)
  - msgWaitInfo, [282](#)
  - numInstances, [282](#)
- GetNetworkPreference
  - qaGobiApiNas.h, [1498](#)
- GetNetworkTime
  - qaGobiApiDms.h, [1418](#)
- GetNetworkTimeResp, [282](#)
  - p3GPP2TimeInfo, [282](#)
  - p3GPPTIMEInfo, [282](#)
- GetOfflineReason
  - qaGobiApiDms.h, [1419](#)
- GetPDSDetails
  - qaGobiApiPds.h, [1530](#)
- GetPDSSState
  - qaGobiApiPds.h, [1530](#)
- GetPRLVersion
  - qaGobiApiDms.h, [1420](#)
- GetPacketStatistics
  - qaGobiApiWds.h, [1700](#)
- GetPacketStatus
  - qaGobiApiWds.h, [1701](#)
- GetPortAutomaticTracking
  - qaGobiApiPds.h, [1531](#)
- GetPower
  - qaGobiApiDms.h, [1420](#)
- GetProfileSettingIn
  - qaGobiApiWds.h, [1684](#)
- GetProfileSettingOut
  - qaGobiApiWds.h, [1684](#)
- GetRFInfo
  - qaGobiApiNas.h, [1499](#)
- GetRegMgrConfigParams, [282](#)
  - pIMSTestMode, [283](#)
  - pPCSCFPort, [283](#)
  - pPriCSCFPortName, [283](#)
  - pPriCSCFPortNameLen, [283](#)
  - pSettingResp, [283](#)
- GetSIPConfigResp, [284](#)
  - pSIPLocalPort, [285](#)
  - pSettingResp, [284](#)
  - pSigCompEnabled, [285](#)
  - pSubscribeTimer, [285](#)
  - pTimerSIPReg, [285](#)
  - pTimerT1, [285](#)
  - pTimerT2, [285](#)
  - pTimerTf, [285](#)
- GetSMSCAddress
  - qaGobiApiSms.h, [1563](#)
- GetSMSWake
  - qaGobiApiRms.h, [1552](#)
- GetSerialNumbers
  - qaGobiApiDms.h, [1421](#)
- GetServiceAutomaticTracking
  - qaGobiApiPds.h, [1531](#)
- GetServingNetwork
  - qaGobiApiNas.h, [1500](#)
- GetServingNetworkCapabilities
  - qaGobiApiNas.h, [1502](#)
- GetSessionDuration
  - qaGobiApiWds.h, [1702](#)
- GetSessionIDResp, [283](#)
  - pSessionIDv4, [283](#)
  - pSessionIDv6, [283](#)
- GetSessionState
  - qaGobiApiWds.h, [1702](#)
- GetSignalStrengths
  - qaGobiApiNas.h, [1503](#)
- GetStoredImages
  - qaGobiApiFms.h, [1453](#)
- getTransLayerInfoResp
  - qaGobiApiSms.h, [1559](#)
- getTransNWRegInfoResp
  - qaGobiApiSms.h, [1560](#)
- GetValidFwPriCombinations
  - fms.h, [1248](#)
- GetVoiceNumber
  - qaGobiApiDms.h, [1422](#)
- GetXTRAAutomaticDownload
  - qaGobiApiPds.h, [1533](#)
- GetXTRANetwork
  - qaGobiApiPds.h, [1533](#)
- GetXTRAValidity
  - qaGobiApiPds.h, [1534](#)

- glo\_almanac\_sv\_msk
  - GPSSStateInfo, 293
- glo\_ephemeris\_sv\_msk
  - GPSSStateInfo, 293
- glo\_health\_sv\_msk
  - GPSSStateInfo, 293
- glo\_visible\_sv\_msk
  - GPSSStateInfo, 293
- globalCellId
  - LTEInfoIntrafreq, 411
  - nas\_LTEInfoIntrafreq, 476
- glog
  - common.h, 1213
- gloglvl
  - common.h, 1213
- GnssData, 285
  - mask, 287
- gnssSvId
  - satelliteInfo, 758
- gnssSvInfoNotification, 287
  - bAltitudeAssumed, 287
  - pSatelliteInfo, 287
- gnssSvUsedList
  - loc\_svUsedforFix, 387
  - svUsedforFix\_s, 851
- gnssSvUsedList\_len
  - loc\_svUsedforFix, 387
  - svUsedforFix\_s, 851
- Gpp2TimeZone
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSGetServingSystem\_t, 1004
- GppNetworkDSTAdjustment
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSGetServingSystem\_t, 1004
- GppTimeZone
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSGetServingSystem\_t, 1004
- gps\_almanac\_sv\_msk
  - GPSSStateInfo, 293
- gps\_ephemeris\_sv\_msk
  - GPSSStateInfo, 293
- gps\_health\_sv\_msk
  - GPSSStateInfo, 293
- gps\_visible\_sv\_msk
  - GPSSStateInfo, 293
- GpsEnable
  - custFeaturesInfo, 197
  - pack\_dms\_SetCustFeature\_t, 583
  - unpack\_dms\_GetCustFeature\_t, 954
- gpsTime
  - qaGobiApiCbK.h, 1306
- gpsTime\_s, 293
  - gpsTimeOfWeekMs, 294
  - gpsWeek, 294
- gpsTimeOfWeekMs
  - gpsTime\_s, 294
  - loc\_gpsTime, 382
- gpsWeek
  - gpsTime\_s, 294
  - loc\_gpsTime, 382
- grntDownlinkBitrate
  - LibPackUMTSQoS, 374
  - UMTSMinQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMinQoS, 1185
- grntUplinkBitrate
  - LibPackUMTSQoS, 374
  - UMTSMinQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMinQoS, 1185
- gsmAmrStat
  - curAMRConfig, 187
- GsmCellInfo
  - IteGsmCellInfo, 405
  - nas\_IteGsmCellInfo, 470
- gsmCellInfo, 294
  - arfcn, 295
  - band1900, 295
  - bsicId, 295
  - cellIdValid, 295
  - rsi, 295
  - srlev, 295
- gsmUmtsDI
  - NasSwiIndReg, 555
  - pack\_nas\_SLQSNasSwiOTAMessageCallback\_t, 610
- gsmUmtsUI
  - NasSwiIndReg, 555
  - pack\_nas\_SLQSNasSwiOTAMessageCallback\_t, 610
- guaranteedRate
  - dataRate, 207
  - unpack\_qos\_dataRate\_t, 1028
- gwAddressV6
  - IPV6GWAddressInfo, 340
  - wds\_IPV6GWAddressInfo, 1178
- gwV6PrefixLen
  - IPV6GWAddressInfo, 340
  - wds\_IPV6GWAddressInfo, 1178
- gyroAcceptReady
  - qaGobiApiCbK.h, 1306
- gyroAcceptReady\_s, 300
  - batchPerSec, 301
  - injectEnable, 301
  - samplesPerBatch, 301
- gyroTempAcceptReady
  - qaGobiApiCbK.h, 1308
- gyroTempAcceptReady\_s, 301
  - batchPerSec, 302
  - injectEnable, 302
  - samplesPerBatch, 302
- HASPI
  - unpack\_wds\_GetMobileIPProfile\_t, 1074
- HASState
  - unpack\_wds\_GetMobileIPProfile\_t, 1074
- HDOP



- loc\_precisionDilution, [384](#)
- precisionDilution\_s, [677](#)
- HDRECIOTresh, [302](#)
  - HDRECIOTreshListLen, [303](#)
  - pHDRECIOTreshList, [303](#)
- HDRECIOTreshListLen
  - HDRECIOTresh, [303](#)
  - nas\_HDRECIOTresh, [463](#)
- HDRIOTresh, [303](#)
  - HDRIOTreshListLen, [303](#)
  - pHDRIOTreshList, [303](#)
- HDRIOTreshListLen
  - HDRIOTresh, [303](#)
  - nas\_HDRIOTresh, [463](#)
- HDRPersonalityInd, [303](#)
  - pCurrentPersonality, [303](#)
  - pPersonalityListLength, [303](#)
  - pProtocolSubtypeElement, [303](#)
- HDRPersonalityResp, [304](#)
  - pCurrentPersonality, [304](#)
  - pPersonalityListLength, [304](#)
  - pProtocolSubtypeElement, [304](#)
- HDRProtSubtypResp, [304](#)
  - pAppSubType, [305](#)
  - pCurrentPrsnlty, [305](#)
  - pPersonalityListLength, [305](#)
  - pProtoSubTypElmnt, [305](#)
- HDRRSSITresh, [305](#)
  - HDRRSSITreshListLen, [305](#)
  - pHDRRSSITreshList, [305](#)
- HDRRSSITreshListLen
  - HDRRSSITresh, [305](#)
  - nas\_HDRRSSITresh, [464](#)
- HDRSINRThresListLen
  - HDRSINRThresh, [306](#)
- HDRSINRThresh, [306](#)
  - HDRSINRThresListLen, [306](#)
  - pHDRSINRThresList, [306](#)
- HDRSINRThreshListLen
  - HDRSINRThreshold, [307](#)
  - nas\_HDRSINRThreshold, [465](#)
- HDRSINRThreshold, [306](#)
  - HDRSINRThresListLen, [307](#)
  - pHDRSINRThresList, [307](#)
- HDRSSInfo, [307](#)
  - ecio, [308](#)
  - io, [308](#)
  - rss, [308](#)
  - sinr, [308](#)
  - unpack\_nas\_SLQSNasGetSigInfo\_t, [1014](#)
- HDRSysInfo, [309](#)
  - hdrActiveProt, [311](#)
  - hdrActiveProtValid, [311](#)
  - hdrPersonality, [311](#)
  - hdrPersonalityValid, [311](#)
  - is856SysId, [311](#)
  - is856SysIdValid, [311](#)
  - isSysPrIMatch, [311](#)
  - isSysPrIMatchValid, [311](#)
  - sysInfoHDR, [311](#)
- HWVersion
  - DeviceConfigDetail, [216](#)
- HardwareControlledMode
  - unpack\_dms\_GetPower\_t, [962](#)
- hdrActiveProt
  - HDRSysInfo, [311](#)
  - nas\_HDRSysInfo, [467](#)
- hdrActiveProtValid
  - HDRSysInfo, [311](#)
  - nas\_HDRSysInfo, [467](#)
- hdrHybrid
  - detailSvcInfo, [215](#)
  - nas\_detailSvcInfo, [451](#)
- HdrPersonality
  - unpack\_nas\_SLQSGetServingSystem\_t, [1004](#)
- hdrPersonality
  - HDRSysInfo, [311](#)
  - nas\_HDRSysInfo, [467](#)
  - NASServingSystemInfo, [552](#)
  - qaQmiServingSystemParam, [700](#)
  - ServingSystemInfo, [764](#)
- hdrPersonalityValid
  - HDRSysInfo, [311](#)
  - nas\_HDRSysInfo, [467](#)
- hdrSSInfo, [308](#)
  - ecio, [309](#)
  - io, [309](#)
  - rss, [309](#)
  - sinr, [309](#)
- hdrSrvStatus
  - detailSvcInfo, [215](#)
  - nas\_detailSvcInfo, [451](#)
- healthStatus
  - satelliteInfo, [758](#)
- helper\_get\_resp\_ctx
  - common.h, [1212](#)
- helper\_get\_xid
  - common.h, [1213](#)
- helper\_set\_log\_func
  - common.h, [1213](#)
- helper\_set\_log\_lvl
  - common.h, [1213](#)
- homeOrigVoiceSO
  - prefVoiceSO, [679](#)
- homePageVoiceSO
  - prefVoiceSO, [679](#)
- homeSIDNID, [311](#)
  - numInstances, [312](#)
  - SidNid, [312](#)
- HorizontalUncertainty
  - GPSSStateInfo, [293](#)
- hotSwap
  - hotSwapStatus, [312](#)
  - uim\_hotSwapStatus, [905](#)
- hotSwapLength
  - hotSwapStatus, [312](#)

- uim\_hotSwapStatus, 905
- hotSwapStatus, 312
  - hotSwap, 312
  - hotSwapLength, 312
- hour
  - nas\_timeInfo, 509
  - nas\_UniversalTime, 515
  - timeInfo, 883
  - UniversalTime, 952
- hsCallStatus
  - nas\_WCDMASysInfo, 522
  - WCDMASysInfo, 1171
- hsCallStatusValid
  - nas\_WCDMASysInfo, 522
  - WCDMASysInfo, 1171
- hsInd
  - nas\_WCDMASysInfo, 522
  - WCDMASysInfo, 1171
- hsIndValid
  - nas\_WCDMASysInfo, 522
  - WCDMASysInfo, 1171
- hwType
  - WdsDHCPv4HWConfig, 1192
  - wdsDhcpv4HwConfig, 1191
- hwVer
  - unpack\_dms\_GetHardwareRevision\_t, 960
- iFaceTab
  - PCMparams, 657
- iFaceTabLen
  - PCMparams, 657
- iGetByteTotals
  - qaGobiApiWds.h, 1703
- iGetConnectionRate
  - qaGobiApiWds.h, 1703
- iGetPacketStatistics
  - qaGobiApiWds.h, 1703
- iLTEbandValue
  - NASPhyCaAggPcellInfo, 543
  - NASPhyCaAggScellInfo, 546
  - PhyCaAggPcellInfo, 667
  - PhyCaAggScellInfo, 671
- IMCNflag
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, 1082
- IMEIString
  - unpack\_dms\_GetDeviceSerialNumbers\_t, 957
- IMG\_ID\_LEN
  - qaGobiApiFms.h, 1449
- IMGDETAILS\_LEN
  - qaGobiApiDms.h, 1404
- IMS Service (IMS), 49
- IMSALndRegisterInfo, 316
  - pPdpStatusConfig, 317
  - pRatHandoverStatusConfig, 317
  - pRegStatusConfig, 317
  - pServiceStatusConfig, 317
- IMSARegistrationStatus, 319
  - plmsRegErrCode, 320
  - plmsRegStatus, 320
- pNewImsRegStatus, 320
- IMSAServiceStatus, 321
  - pSmsServiceRat, 323
  - pSmsServiceStatus, 323
  - pUtServiceRat, 323
  - pUtServiceStatus, 323
  - pVoipServiceRat, 323
  - pVoipServiceStatus, 323
  - pVsServiceRat, 323
  - pVsServiceStatus, 323
  - pVtServiceRat, 323
  - pVtServiceStatus, 324
- IMSASupportedFieldsResp, 324
  - pIndFieldsList, 324
  - pReqFieldsList, 324
  - pRespFieldsList, 324
- IMSASupportedMsgInfo, 324
  - pSupportedMsgList, 325
- IMSI\_M\_S1\_LENGTH
  - qaGobiApiNas.h, 1482
- IMSI\_M\_S2\_LENGTH
  - qaGobiApiNas.h, 1482
- IMSInfo
  - sMSOnIMSTlv, 837
- IMSTlv
  - unpack\_sms\_SetNewSMSCallback\_ind\_t, 1052
- INDEX\_ZERO
  - qaNasPerformNetworkScan.h, 1733
- INT32
  - SwiDataTypes.h, 1761
- INT8
  - SwiDataTypes.h, 1761
- INVALID\_INSTACNE
  - qaGobiApiCbk.h, 1304
- IOThresListLen
  - IOThresh, 337
- IOThresh, 336
  - IOThresListLen, 337
  - pIOThresList, 337
- IPAddress
  - DataStatusDetail, 210
- IPAddressV6
  - IPV6AddressInfo, 339
  - ipv6AddressInfo, 340
  - wds\_IPV6AddressInfo, 1177
- IPFamSupport
  - pack\_dms\_SetCustFeature\_t, 583
  - unpack\_dms\_GetCustFeature\_t, 954
- IPFamilyPreference
  - pack\_wds\_SLQSSetIPFamilyPreference\_t, 651
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, 1082
- IPSECSPI
  - LibPackTFTIDParams, 371
  - TFTIDParams, 881
- IPV4
  - qaGobiApiCbk.h, 1304
- IPV4V6
  - qaGobiApiCbk.h, 1304



- IPv6
  - qaGobiApiCbK.h, [1304](#)
- IPv6AddrInfo
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1082](#)
- IPv6AddressInfo, [339](#)
  - IPAddressV6, [339](#)
  - IPv6PrefixLen, [339](#)
- IPv6GWAddrInfo
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1082](#)
- IPv6GWAddressInfo, [340](#)
  - gwAddressV6, [340](#)
  - gwV6PrefixLen, [340](#)
- IPv6PrefixLen
  - IPv6AddressInfo, [339](#)
  - ipv6AddressInfo, [340](#)
  - wds\_IPV6AddressInfo, [1177](#)
- IPv4
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1082](#)
- IPv4Addr, [337](#)
  - addr, [337](#)
  - subnetMask, [337](#)
- IPv4DstAddr
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
- IPv4SrcAddr
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
- IPv4Tos
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
- IPv6Addr, [337](#)
  - addr, [339](#)
  - prefixLen, [339](#)
- IPv6DstAddr
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
- IPv6Label
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
- IPv6SrcAddr
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
- IPv6TrafCls, [340](#)
  - mask, [341](#)
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
  - val, [341](#)
- iSLQSMISetIPFamilyPreference
  - qaGobiApiWds.h, [1703](#)
- iSLQSSetDUNCallInfoCallback
  - qaGobiApiCbK.h, [1350](#)
- iSLQSSetSignalStrengthsCallback
  - qaGobiApiCbK.h, [1350](#)
- iSLQSSetWdsFirstInstEventCallback
  - qaGobiApiCbK.h, [1350](#)
- iSLQSSetWdsSecondInstEventCallback
  - qaGobiApiCbK.h, [1350](#)
- iSLQSSetWdsThirdInstEventCallback
  - qaGobiApiCbK.h, [1350](#)
- iSLQSSetWdsXferStatsFirstInstCallback
  - qaGobiApiCbK.h, [1350](#)
- iSLQSSetWdsXferStatsSecondInstCallback
  - qaGobiApiCbK.h, [1350](#)
- iSetCATEventCallback
  - qaGobiApiCbK.h, [1350](#)
- iSetSignalStrengthCallback
  - qaGobiApiCbK.h, [1350](#)
- Id
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
- id
  - BdsSV, [125](#)
  - CSGID, [185](#)
  - loc\_BdsSV, [376](#)
  - loc\_SV, [386](#)
  - nas\_CSGID, [447](#)
  - QosFlowInfoState, [732](#)
  - SV, [849](#)
  - swiQosModifyReq, [869](#)
  - unpack\_qos\_QosFlowInfoState\_t, [1033](#)
  - unpack\_qos\_SLQSSetQosStatusCallback\_ind\_t, [1040](#)
- id\_length
  - custSettingInfo, [200](#)
  - DMScustSettingInfo, [222](#)
- IdleState
  - protocolSubtypeElement, [694](#)
- image\_info\_t, [313](#)
  - buildID, [313](#)
  - buildIDLen, [313](#)
  - imageType, [313](#)
  - uniqueID, [313](#)
- ImageElement, [313](#)
  - buildId, [313](#)
  - buildIdLength, [313](#)
  - imageId, [314](#)
  - imageType, [314](#)
- imageID
  - FMSImageIdElement, [246](#)
  - ImageIdElement, [314](#)
- imageIDElement
  - FMSImageIDEntries, [247](#)
  - ImageIDEntries, [315](#)
- ImageIDEntries, [315](#)
  - executingImage, [315](#)
  - imageIDElement, [315](#)
  - imageIDSize, [315](#)
  - imageType, [315](#)
  - maxImages, [315](#)
- imageIDEntries
  - FMSImageList, [247](#)
  - ImageList, [316](#)
- imageIDSize
  - FMSImageIDEntries, [247](#)
  - ImageIDEntries, [315](#)
- imageId
  - FMSImageElement, [245](#)
  - ImageElement, [314](#)
- ImageIdElement, [314](#)
  - buildID, [314](#)
  - buildIDLength, [314](#)
  - failureCount, [314](#)
  - imageID, [314](#)
  - storageIndex, [314](#)

- ImageList, 315
  - imageIDEntries, 316
  - listSize, 316
- imageList
  - unpack\_fms\_GetStoredImages\_t, 978
- ImageListSize
  - unpack\_fms\_GetImagesPreference\_t, 977
- imageListSize
  - pack\_fms\_SetImagesPreference\_t, 589
- imageType
  - CurrImageInfo, 191
  - FMSImageElement, 245
  - FMSImageIDEntries, 247
  - image\_info\_t, 313
  - ImageElement, 314
  - ImageIDEntries, 315
- ImageTypes
  - unpack\_fms\_SetImagesPreference\_t, 979
- ImageTypesSize
  - unpack\_fms\_SetImagesPreference\_t, 979
- imagelistSize
  - unpack\_fms\_GetStoredImages\_t, 978
- imei\_no
  - unpack\_dms\_GetSerialNumbers\_t, 963
- imeiSize
  - serialNumbersInfo, 761
  - unpack\_dms\_GetDeviceSerialNumbers\_t, 957
- imeiSvnSize
  - serialNumbersInfo, 761
  - unpack\_dms\_GetDeviceSerialNumbers\_t, 957
- ImeiSvnString
  - unpack\_dms\_GetDeviceSerialNumbers\_t, 957
- imeisv\_svn
  - unpack\_dms\_GetSerialNumbers\_t, 963
- imgType
  - unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t, 976
- imsCfgIndRegisterInfo, 326
  - pRegMgrConfigEvents, 327
  - pSIPConfigEvents, 327
  - pSMSConfigEvents, 327
  - pUserConfigEvents, 327
  - pVoIPConfigEvents, 327
- imsRegMgrConfigInfo, 327
  - pCSCFPortName, 329
  - pIMSTestMode, 329
  - pPriCSCFPort, 329
- imsRegState
  - CommInfo, 177
  - nas\_CommInfo, 446
- imsSIPConfigInfo, 329
  - pSIPLocalPort, 330
  - pSigCompEnabled, 330
  - pSubscribeTimer, 330
  - pTimerSIPReg, 330
  - pTimerT1, 330
  - pTimerT2, 330
  - pTimerTf, 330
- imsSMSConfigInfo, 330
  - pPhoneCtxtURI, 331
  - pSMSFormat, 331
  - pSMSOverIPNwInd, 331
- imsUserConfigInfo, 331
  - pIMSDomain, 331
- imsVoIPConfigInfo, 331
  - pAmrMode, 334
  - pAmrOctetAligned, 334
  - pAmrWBMode, 334
  - pAmrWBOctetAligned, 334
  - pAmrWbEnable, 334
  - pMinSessionExpiryTimer, 334
  - pRTPRTCPInactTimer, 334
  - pRingBackTimer, 334
  - pRingingTimer, 334
  - pScrAmrEnable, 334
  - pScrAmrWbEnable, 334
  - pSessionExpiryTimer, 334
- imsaPdpStatusInfo, 317
  - connetionState, 318
  - pFailErrorCode, 318
- imsaRatStatusInfo, 318
  - pErrorCodeStr, 319
  - pRATStatus, 319
  - pSrcRAT, 319
  - pTgtRAT, 319
- imsaRegStatusInfo, 320
  - pImmsRegStatus, 321
  - pRegStatusErrorCode, 321
  - pbIMSRegistered, 321
- imsaSvcStatusInfo, 325
  - pSMSSvcRAT, 325
  - pSMSSvcStatus, 325
  - pUTSvcRAT, 325
  - pUTSvcStatus, 325
  - pVOIPSvcRAT, 325
  - pVOIPSvcStatus, 326
  - pVTSvcRAT, 326
  - pVTSvcStatus, 326
- imsi
  - unpack\_dms\_GetIMSI\_t, 960
- imsi\_11\_12
  - CDMASysInfoExt, 165
  - nas\_CDMASysInfoExt, 443
- imsiM1112
  - minBasedIMSI, 428
- imsiMS1
  - minBasedIMSI, 428
- imsiMS2
  - minBasedIMSI, 428
- imsiT1112
  - trueIMSI, 893
- imsiTS1
  - trueIMSI, 893
- imsiTS2
  - trueIMSI, 893
- imsiTaddrNum
  - trueIMSI, 893

- InUse
  - nas\_QmiNas3GppNetworkInfo, [491](#)
  - SlqsNas3GppNetworkInfo, [807](#)
- includes\_pcs\_digit
  - nas\_QmisNasPcsDigit, [493](#)
  - SlqsNasPcsDigit, [808](#)
- IndFieldsList, [334](#)
  - indicationFields, [335](#)
  - indicationFieldsLen, [335](#)
- index
  - pack\_wds\_GetMobileIPProfile\_t, [639](#)
  - pack\_wds\_SetDefaultProfileNum\_t, [641](#)
  - pack\_wds\_SetMobileIPProfile\_t, [641](#)
  - swiQosFilter, [864](#)
  - swiQosFlow, [867](#)
  - swiQosReq, [870](#)
  - unpack\_qos\_swiQosFilter\_t, [1042](#)
  - unpack\_qos\_swiQosFlow\_t, [1047](#)
  - unpack\_wds\_GetDefaultProfileNum\_t, [1072](#)
- index1xPri
  - cardStatus, [144](#)
  - uim\_cardStatus, [902](#)
- index1xSec
  - cardStatus, [144](#)
  - uim\_cardStatus, [902](#)
- indexGwPri
  - cardStatus, [144](#)
  - uim\_cardStatus, [902](#)
- indexGwSec
  - cardStatus, [144](#)
  - uim\_cardStatus, [902](#)
- indicationFields
  - IndFieldsList, [335](#)
- indicationFieldsLen
  - IndFieldsList, [335](#)
- Info
  - unpack\_nas\_SLQSNasSwiOTAMessageCallback-\_ind\_t, [1018](#)
  - unpack\_nas\_SLQSSetSysSelectionPrefCallBack-\_ind\_t, [1018](#)
- infoInterFreq, [335](#)
  - cell\_resel\_priority, [336](#)
  - cellInterFreqParams, [336](#)
  - cells\_len, [336](#)
  - earfcn, [336](#)
  - threshXHigh, [336](#)
  - threshXLow, [336](#)
- InfoInterfreq
  - LTEInfoInterfreq, [409](#)
  - nas\_LTEInfoInterfreq, [473](#)
- InitiateDomainAttach
  - qaGobiApiNas.h, [1503](#)
- InitiateNetworkRegistration
  - qaGobiApiNas.h, [1504](#)
- injectEnable
  - accelAcceptReady\_s, [96](#)
  - accelTempAcceptReady\_s, [97](#)
  - gyroAcceptReady\_s, [301](#)
  - gyroTempAcceptReady\_s, [302](#)
- injectSensorDataStatus
  - QmiCbkLocInjectSensorDataInd, [705](#)
- injectTimeSyncStatus
  - QmiCbkLocInjectTimeInd, [706](#)
- insNmrCellInfo
  - GERANInfo, [251](#)
  - nas\_GERANInfo, [455](#)
- instanceId
  - ssdatasession\_params, [847](#)
- instancesSize
  - unpack\_nas\_GetRFInfo\_t, [994](#)
- interval
  - pack\_wds\_SLQSSetWdsEventCallback\_t, [651](#)
  - TransferStatsDataType, [892](#)
- Io
  - slqsSignalStrengthInfo, [817](#)
  - unpack\_nas\_SLQSGetSignalStrength\_t, [1005](#)
- io
  - HDRSSInfo, [308](#)
  - hdrSSInfo, [309](#)
  - nas\_SLQSSignalStrengthsInformation, [500](#)
  - SLQSSignalStrengthsInformation, [820](#)
- ioDelta
  - nas\_SLQSSignalStrengthsIndReq, [499](#)
  - SLQSSignalStrengthsIndReq, [819](#)
- lono\_valid
  - GPSSStateInfo, [293](#)
- ip
  - WdsIpAddressInfoReq, [1196](#)
- ipAddress
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
- ipFamily
  - \_packetSrvStatus, [64](#)
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback\_-\_t, [1084](#)
- ipVersion
  - LibPackTFTIDParams, [371](#)
  - TFTIDParams, [881](#)
- ipaddr
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- ipaddrv6
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- ipfamily
  - ssdatasession\_params, [847](#)
- ipv4Address
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings-\_t, [1088](#)
- ipv4GWAddress
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings-\_t, [1088](#)
- ipv6Address
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings-\_t, [1088](#)
- ipv6AddressInfo, [339](#)
  - IPAddressV6, [340](#)
  - IPV6PrefixLen, [340](#)
- ipv6GWAddress

- unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t, 1089
- is856SysId
  - HDRSysInfo, 311
  - nas\_HDRSysInfo, 467
- is856SysIdValid
  - HDRSysInfo, 311
  - nas\_HDRSysInfo, 467
- is\_DataRate\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_EspSpi\_Available
  - unpack\_qos\_swiQosFilter\_t, 1042
- is\_IPv4DstAddr\_Available
  - unpack\_qos\_swiQosFilter\_t, 1042
- is\_IPv4SrcAddr\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_IPv4Tos\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_IPv6DstAddr\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_IPv6Label\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_IPv6SrcAddr\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_IPv6TrafCls\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_Id\_Available
  - unpack\_qos\_swiQosFilter\_t, 1042
- is\_Jitter\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_Latency\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_LteBandCapability\_Available
  - unpack\_dms\_SLQSGetBandCapability\_t, 971
- is\_LteQci\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_MaxAllowedPktSz\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_MinPolicedPktSz\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_NxtHdrProto\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_PktErrRate\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_Precedence\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_ProfileId3GPP2\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_RxQFlowGranted\_Available
  - unpack\_qos\_QosFlowInfo\_t, 1032
- is\_TCPDstPort\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_TCPSrcPort\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_TdsBandCapability\_Available
  - unpack\_dms\_SLQSGetBandCapability\_t, 971
- is-TokenBucket\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_TrafficClass\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_TranDstPort\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_TranSrcPort\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_TxQFlowGranted\_Available
  - unpack\_qos\_QosFlowInfo\_t, 1032
- is\_UDPDstPort\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_UDPSrcPort\_Available
  - unpack\_qos\_swiQosFilter\_t, 1043
- is\_val\_3GPP2Pri\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_val\_3GPPImCn\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_val\_3GPPResResidualBER\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_val\_3GPPSigInd\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- is\_val\_3GPPTraHdlPri\_Available
  - unpack\_qos\_swiQosFlow\_t, 1047
- isEmpty
  - getAllCallInformation, 253
- isInTraffic
  - txInfo, 895
- isModByCC
  - SUPInfo, 848
- isNewFlow
  - QosFlowInfoState, 732
  - unpack\_qos\_QosFlowInfoState\_t, 1033
- isPrefDataPath
  - GSMSrvStatusInfo, 297
  - nas\_GSMSrvStatusInfo, 459
  - nas\_SrvStatusInfo, 502
  - SrvStatusInfo, 844
- isRadioTuned
  - rxInfo, 750
- isSysForbidden
  - detailSvcInfo, 215
  - nas\_detailSvcInfo, 451
  - nas\_sysInfoCommon, 505
  - sysInfoCommon, 873
- isSysForbiddenValid
  - nas\_sysInfoCommon, 505
  - sysInfoCommon, 873
- isSysPriMatch
  - CDMASysInfo, 164
  - HDRSysInfo, 311
  - nas\_CDMASysInfo, 443
  - nas\_HDRSysInfo, 467
- isSysPriMatchValid
  - CDMASysInfo, 164
  - HDRSysInfo, 311
  - nas\_CDMASysInfo, 443
  - nas\_HDRSysInfo, 467
- IsVoiceEnabled
  - pack\_dms\_SetCustFeature\_t, 583

- unpack\_dms\_GetCustFeature\_t, 954
- Item
  - GetAudioPathConfigReq, 254
  - GetAudioVolTLBConfigReq, 260
  - SetAudioVolTLBConfigReq, 773
- Jitter
  - unpack\_qos\_swiQosFlow\_t, 1048
- KeyExchange
  - protocolSubtypeElement, 694
- LIBPACK\_QMI\_CBK\_PARAM\_NOCHANGE
  - sms.h, 1754
- LIBPACK\_QMI\_CBK\_PARAM\_RESET
  - sms.h, 1754
- LIBPACK\_QMI\_CBK\_PARAM\_SET
  - sms.h, 1754
- LBPTlv
  - NASQmiCbkNasSystemSelPrefInd, 550
- LEN
  - qaGobiApiDcs.h, 1391
- LOCEVENTMASKGNSSVININFO
  - loc.h, 1252
- LOCEVENTMASKNMEA
  - loc.h, 1253
- LOCEVENTMASKWIFIREQ
  - loc.h, 1254
- LOCEventRegisterReqResp, 390
  - eventRegister, 392
- LOCExtPowerStateReqResp, 392
  - extPowerState, 392
- LOCStartReq, 400
  - pApplicationInfo, 402
  - pConfigAltitudeAssumed, 402
  - pHorizontalAccuracyLvl, 402
  - pIntermediateReportState, 402
  - pMinIntervalTime, 402
  - pRecurrenceType, 402
  - SessionId, 402
- LOCStopReq, 402
  - sessionId, 402
- LPCSTR
  - SwiDataTypes.h, 1761
- LTEAttachProfileList
  - pack\_wds\_SLQSSet3GPPConfigItem\_t, 649
  - unpack\_wds\_SLQSGet3GPPConfigItem\_t, 1078
- LTEAttachProfileListLen
  - \_slqs3GPPConfigItem, 69
  - pack\_wds\_SLQSSet3GPPConfigItem\_t, 649
  - unpack\_wds\_SLQSGet3GPPConfigItem\_t, 1078
- LTEBandPref
  - NASLTEBandPreferenceTlv, 538
- LTECphyCAInfo
  - unpack\_nas\_SlqsGetLTECphyCAInfo\_t, 1000
- LTEInfo, 405
  - band, 408
  - bandwidth, 408
  - emmConnState, 408
  - emmState, 408
  - emmSubState, 408
  - RXChan, 408
  - TXChan, 408
- LTEInfoInterfreq, 408
  - freqsLen, 409
  - InfoInterfreq, 409
  - ueInIdle, 409
- LTEInfoIntrafreq, 409
  - CellParams, 411
  - cellReselPriority, 411
  - cellsLen, 411
  - earfcn, 411
  - globalCellId, 411
  - plmn, 411
  - sIntraSearch, 411
  - sNonIntraSearch, 411
  - servingCellId, 411
  - tac, 411
  - threshServingLow, 411
  - ueInIdle, 411
- LTEInfoNeighboringGSM, 412
  - freqsLen, 412
  - LteGsmCellInfo, 412
  - ueInIdle, 412
- LTEInfoNeighboringWCDMA, 412
  - freqsLen, 413
  - LTEWCDMACellInfo, 413
  - ueInIdle, 413
- LTERSRPThresh, 415
  - LTERSRPThreshListLen, 415
  - pLTERSRPThreshList, 415
- LTERSRPThreshListLen
  - LTERSRPThresh, 415
  - nas\_LTERSRPThresh, 478
- LTERSRQThresh, 415
  - LTERSRQThreshListLen, 416
  - pLTERSRQThreshList, 416
- LTERSRQThreshListLen
  - LTERSRQThresh, 416
  - nas\_LTERSRQThresh, 479
- LTERSSIThresh, 416
  - LTERSSIThreshListLen, 416
  - pLTERSSIThreshList, 416
- LTERSSIThreshListLen
  - LTERSSIThresh, 416
  - nas\_LTERSSIThresh, 479
- LTESNRThresListLen
  - LTESNRThresh, 420
- LTESNRThresh, 420
  - LTESNRThresListLen, 420
  - pLTESNRThresList, 420
- LTESNRThreshListLen
  - LTESNRThreshold, 421
  - nas\_LTESNRThreshold, 482
- LTESNRThreshold, 420
  - LTESNRThreshListLen, 421
  - pLTESNRThreshList, 421

- LTESInfo, 421
  - rsrp, 422
  - rsrq, 422
  - rsqi, 422
  - snr, 422
  - unpack\_nas\_SLQSNasGetSigInfo\_t, 1014
- LTESigRptCfg, 416
  - avgPeriod, 418
  - rptRate, 418
- LTESigRptConfig, 418
  - avgPeriod, 419
  - rptRate, 419
- LTESysInfo, 423
  - cellId, 425
  - cellIdValid, 425
  - lac, 425
  - lacValid, 425
  - MCC, 425
  - MNC, 425
  - networkIdValid, 425
  - regRejectInfoValid, 425
  - rejCause, 425
  - rejectSrvDomain, 425
  - sysInfoLTE, 425
  - tac, 425
  - tacValid, 425
- LTEWCDMACellInfo
  - LTEInfoNeighboringWCDMA, 413
  - nas\_LTEInfoNeighboringWCDMA, 477
- Lac
  - qaQmiServingSystemParam, 700
  - unpack\_nas\_SLQSGetServingSystem\_t, 1004
- lac
  - GERANInfo, 251
  - GSMSysInfo, 300
  - LTESysInfo, 425
  - nas\_GERANInfo, 455
  - nas\_GSMSysInfo, 462
  - nas\_LTESysInfo, 484
  - nas\_UMTSInfo, 511
  - nas\_WCDMASysInfo, 522
  - UMTSInfo, 940
  - WCDMASysInfo, 1171
- lac1
  - OperatorPLMNData, 581
- lac2
  - OperatorPLMNData, 581
- lacValid
  - GSMSysInfo, 300
  - LTESysInfo, 425
  - nas\_GSMSysInfo, 462
  - nas\_LTESysInfo, 484
  - nas\_WCDMASysInfo, 523
  - WCDMASysInfo, 1172
- language
  - CDMABroadcastConfig, 151
- lastCallDataBearerTech
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, 1080
- lastCallDataBearerTechnology
  - unpack\_wds\_SLQSGetDataBearerTechnology\_t, 1079
- lastCallRXOKBytesCnt
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, 1080
- lastCallTXOKBytesCnt
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, 1080
- LastErrCode
  - DataStatusDetail, 210
- Latency
  - unpack\_qos\_swiQosFlow\_t, 1048
- Latitude
  - GPSSStateInfo, 293
- leapSeconds
  - nas\_qaQmi3Gpp2TimeZone, 490
  - qaQmi3Gpp2TimeZone, 696
- len
  - BdsSVInfo, 126
  - loc\_BdsSVInfo, 377
  - loc\_SVInfo, 387
  - SVInfo, 850
  - unpack\_nas\_GetSignalStrengths\_t, 996
- length
  - readTransparentInfo, 734
  - SMSCAddress, 826
  - sMSCAddress, 826
  - SMSEtwSMessage, 828
  - sMSEtwSMessage, 827
  - SMSTransferRouteMTMessage, 841
  - sMSTransferRouteMTMessage, 840
  - uim\_readTransparentInfo, 906
- Level
  - GetM2MAudioVolumeResp, 278
  - SetM2MAudioVolumeReq, 783
- LibPackGPRSRequestedQoS, 341
  - delayClass, 342
  - meanThroughputClass, 342
  - peakThroughputClass, 342
  - precedenceClass, 342
  - reliabilityClass, 342
- LibPackQosClassID, 368
  - gDIBitRate, 369
  - gUIBitRate, 369
  - maxDIBitRate, 369
  - maxUIBitRate, 369
  - QCI, 369
- LibPackTFTIDParams, 369
  - destPortRangeEnd, 371
  - destPortRangeStart, 371
  - eValid, 371
  - filterId, 371
  - flowLabel, 371
  - IPSECSPi, 371
  - ipVersion, 371
  - nextHeader, 371
  - pSourceIP, 371
  - sourceIPMask, 371
  - srcPortRangeEnd, 371



- srcPortRangeStart, 371
- tosMask, 371
- LibPackUMTSQoS, 371
  - deliveryErrSDU, 374
  - grntDownlinkBitrate, 374
  - grntUplinkBitrate, 374
  - maxDownlinkBitrate, 374
  - maxSDUSize, 374
  - maxUplinkBitrate, 374
  - qosDeliveryOrder, 374
  - resBerRatio, 374
  - sduErrorRatio, 374
  - trafficClass, 374
  - trafficPriority, 374
  - transferDelay, 374
- LibPackUMTSReqQoSsigInd, 374
  - SigInd, 375
  - UMTSReqQoS, 375
- LibPackprofile\_3GPP, 355
  - pAPNClass, 361
  - pAPNDisabledFlag, 361
  - pAPNName, 361
  - pAPNnameSize, 361
  - pAddrAllocPref, 361
  - pAuthenticationPref, 361
  - pGPRSMinimumQoS, 361
  - pGPRSRequestedQos, 361
  - pIPv4AddrPref, 361
  - pIPv6AddPref, 361
  - pImCnFlag, 361
  - pPDNInactivTimeout, 361
  - pPDPtype, 362
  - pPassword, 361
  - pPasswordSize, 361
  - pPcscfAddrUsingDhcp, 361
  - pPcscfAddrUsingPCO, 361
  - pPdpAccessConFlag, 361
  - pPdpContext, 361
  - pPdpDataCompType, 362
  - pPdpHdrCompType, 362
  - pPriDNSIPv4AddPref, 362
  - pPriDNSIPv6addpref, 362
  - pPrimaryID, 362
  - pProfilename, 362
  - pProfilenameSize, 362
  - pQosClassID, 362
  - pSecDNSIPv4AddPref, 362
  - pSecDNSIPv6addpref, 362
  - pSecondaryFlag, 362
  - pTFTID1Params, 362
  - pTFTID2Params, 362
  - pUMTSMinQoS, 362
  - pUMTSMinQosSigInd, 362
  - pUMTSReqQoS, 362
  - pUMTSReqQoSsigInd, 362
  - pUsername, 362
  - pUsernameSize, 362
- LibPackprofile\_3GPP2, 362
  - pAPNClass3GPP2, 367
  - pAPNEnabled3GPP2, 367
  - pAllowLinger, 367
  - pApnString, 367
  - pApnStringSize, 367
  - pAppPriority, 367
  - pAppType, 367
  - pAuthPassword, 367
  - pAuthPassword\_tSize, 367
  - pAuthProtocol, 367
  - pAuthRetryCount, 367
  - pAuthTimeout, 367
  - pDataMode, 368
  - pDataRate, 368
  - plpcpAckTimeout, 368
  - plpcpCreqRetryCount, 368
  - plsPcscfAddressNedded, 368
  - pLcpAckTimeout, 368
  - pLcpCreqRetryCount, 368
  - pNegoDnsSrvrPref, 368
  - pPDNInactivTimeout3GPP2, 368
  - pPdnType, 368
  - pPppSessCloseTimer1x, 368
  - pPppSessCloseTimerDO, 368
  - pPriV6DnsAddress, 368
  - pPrimaryV4DnsAddress, 368
  - pRATType, 368
  - pSecV6DnsAddress, 368
  - pSecondaryV4DnsAddress, 368
  - pUserId, 368
  - pUserIdSize, 368
- libpack\_GetVersion
  - common.h, 1213
- libpack\_log
  - common.h, 1213
- LibpackProfile3GPP, 342
  - pAPNClass, 348
  - pAPNDisabledFlag, 348
  - pAPNName, 348
  - pAPNnameSize, 348
  - pAddrAllocPref, 348
  - pAuthenticationPref, 348
  - pGPRSMinimumQoS, 348
  - pGPRSRequestedQos, 348
  - pIPv4AddrPref, 348
  - pIPv6AddPref, 348
  - pImCnFlag, 348
  - pPDNInactivTimeout, 348
  - pPDPtype, 349
  - pPassword, 348
  - pPasswordSize, 348
  - pPcscfAddrUsingDhcp, 348
  - pPcscfAddrUsingPCO, 348
  - pPdpAccessConFlag, 348
  - pPdpContext, 348
  - pPdpDataCompType, 349
  - pPdpHdrCompType, 349
  - pPriDNSIPv4AddPref, 349

- pPriDNSIPv6addpref, [349](#)
- pPrimaryID, [349](#)
- pProfilename, [349](#)
- pProfilenameSize, [349](#)
- pQosClassID, [349](#)
- pSecDNSIPv4AddPref, [349](#)
- pSecDNSIPv6addpref, [349](#)
- pSecondaryFlag, [349](#)
- pTFTID1Params, [349](#)
- pTFTID2Params, [349](#)
- pUMTSMinQoS, [349](#)
- pUMTSMinQoSSigInd, [349](#)
- pUMTSReqQoS, [349](#)
- pUMTSReqQoSSigInd, [349](#)
- pUsername, [349](#)
- pUsernameSize, [349](#)
- LibpackProfile3GPP2, [349](#)
  - pAPNClass3GPP2, [354](#)
  - pAPNEnabled3GPP2, [354](#)
  - pAllowLinger, [354](#)
  - pApnString, [354](#)
  - pApnStringSize, [354](#)
  - pAppPriority, [354](#)
  - pAppType, [354](#)
  - pAuthPassword, [354](#)
  - pAuthPasswordSize, [354](#)
  - pAuthProtocol, [354](#)
  - pAuthRetryCount, [354](#)
  - pAuthTimeout, [354](#)
  - pDataMode, [355](#)
  - pDataRate, [355](#)
  - plpcpAckTimeout, [355](#)
  - plpcpCreqRetryCount, [355](#)
  - plsPcscfAddressNedded, [355](#)
  - pLcpAckTimeout, [355](#)
  - pLcpCreqRetryCount, [355](#)
  - pNegoDnsSrvrPref, [355](#)
  - pPDNInactivTimeout3GPP2, [355](#)
  - pPdnType, [355](#)
  - pPppSessCloseTimer1x, [355](#)
  - pPppSessCloseTimerDO, [355](#)
  - pPriV6DnsAddress, [355](#)
  - pPrimaryV4DnsAddress, [355](#)
  - pRATType, [355](#)
  - pSecV6DnsAddress, [355](#)
  - pSecondaryV4DnsAddress, [355](#)
  - pUserId, [355](#)
  - pUserIdSize, [355](#)
- lineCtrlInfo, [375](#)
  - polarityIncluded, [375](#)
  - pwrDenialTime, [375](#)
  - revPolarity, [375](#)
  - toggleMode, [375](#)
- lineValue
  - voiceALSSelectLineInfo, [1099](#)
- linkage
  - altitudeSrcInfo, [104](#)
- list\_type
  - custSettingList, [202](#)
  - DMScustSettingList, [223](#)
  - DMSgetCustomInput, [224](#)
  - getCustomInput, [263](#)
  - pack\_dms\_GetCustFeaturesV2\_t, [582](#)
- listEntries
  - FMSPrefImageList, [248](#)
  - PrefImageList, [677](#)
- listSize
  - FMSImageList, [247](#)
  - FMSPrefImageList, [248](#)
  - ImageList, [316](#)
  - PrefImageList, [677](#)
- loc.h
  - eQMI\_LOC\_SESS\_STATUS\_FAILURE, [1254](#)
  - eQMI\_LOC\_SESS\_STATUS\_IN\_PROGRESS, [1254](#)
  - eQMI\_LOC\_SESS\_STATUS\_SUCCESS, [1254](#)
  - eQMI\_LOC\_SESS\_STATUS\_TIMEOUT, [1254](#)
- loc.h, [1250](#)
  - LOCEVENTMASKNMEA, [1253](#)
  - LOCEVENTMASKWIFIREQ, [1254](#)
  - pack\_loc\_DeleteAssistData, [1254](#)
  - pack\_loc\_EventRegister, [1254](#)
  - pack\_loc\_SetExtPowerState, [1255](#)
  - pack\_loc\_SetOperationMode, [1255](#)
  - pack\_loc\_Start, [1255](#)
  - pack\_loc\_Stop, [1256](#)
  - unpack\_loc\_DeleteAssistData, [1256](#)
  - unpack\_loc\_EngineState\_Ind, [1256](#)
  - unpack\_loc\_EventRegister, [1257](#)
  - unpack\_loc\_PositionRpt\_Ind, [1257](#)
  - unpack\_loc\_SetExtPowerConfig\_Ind, [1257](#)
  - unpack\_loc\_SetExtPowerState, [1258](#)
  - unpack\_loc\_SetOperationMode, [1258](#)
  - unpack\_loc\_Start, [1258](#)
  - unpack\_loc\_Stop, [1259](#)
- loc\_BdsSV, [376](#)
  - id, [376](#)
  - mask, [376](#)
- loc\_BdsSVInfo, [376](#)
  - len, [377](#)
  - pSV, [377](#)
- loc\_CellDb, [377](#)
  - mask, [377](#)
- loc\_ClkInfo, [378](#)
  - mask, [379](#)
- loc\_GnssData, [380](#)
  - mask, [382](#)
- loc\_LocApplicationInfo, [382](#)
  - appNameLength, [383](#)
  - appProviderLength, [383](#)
  - appVersionLength, [383](#)
  - appVersionValid, [383](#)
  - pAppName, [383](#)
  - pAppProvider, [383](#)
  - pAppVersion, [383](#)
- loc\_SV, [385](#)



- id, [386](#)
- mask, [386](#)
- system, [386](#)
- loc\_SVInfo, [386](#)
  - len, [387](#)
  - pSV, [387](#)
- loc\_gpsTime, [382](#)
  - gpsTimeOfWeekMs, [382](#)
  - gpsWeek, [382](#)
- loc\_precisionDilution, [383](#)
  - HDOP, [384](#)
  - PDOP, [384](#)
  - VDOP, [384](#)
- loc\_sensorDataUsage, [384](#)
  - aidingIndicatorMask, [385](#)
  - usageMask, [385](#)
- loc\_svUsedforFix, [387](#)
  - gnssSvUsedList, [387](#)
  - gnssSvUsedList\_len, [387](#)
- LocApplicationInfo, [387](#)
  - appNameLength, [388](#)
  - appProviderLength, [388](#)
  - appVersionLength, [388](#)
  - appVersionValid, [388](#)
  - pAppName, [388](#)
  - pAppProvider, [388](#)
  - pAppVersion, [389](#)
- LocDelAssDataReq, [389](#)
  - pBdsSVInfo, [389](#)
  - pCellDb, [389](#)
  - pClkInfo, [389](#)
  - pGnssData, [389](#)
  - pSVInfo, [389](#)
- LocInjectPositionReq, [392](#)
  - pAltitudeSrcInfo, [397](#)
  - pAltitudeWrtEllipsoid, [397](#)
  - pAltitudeWrtMeanSeaLevel, [397](#)
  - pHorConfidence, [397](#)
  - pHorReliability, [397](#)
  - pHorUncCircular, [397](#)
  - pLatitude, [397](#)
  - pLongitude, [397](#)
  - pPositionSrc, [397](#)
  - pRawHorConfidence, [397](#)
  - pRawHorUncCircular, [397](#)
  - pTimestampAge, [397](#)
  - pTimestampUtc, [397](#)
  - pVertConfidence, [397](#)
  - pVertReliability, [397](#)
  - pVertUnc, [397](#)
- LocInjectSensorDataReq, [398](#)
  - pAcceleroData, [399](#)
  - pAcceleroTempData, [399](#)
  - pAcceleroTimeSrc, [399](#)
  - pGyroData, [399](#)
  - pGyroTempData, [399](#)
  - pGyroTimeSrc, [399](#)
  - pOpaqueIdentifier, [399](#)
- LocSetCradleMountReq, [399](#)
  - pConfidence, [400](#)
  - state, [400](#)
- localTimeOffset
  - nas\_qaQmi3Gpp2TimeZone, [490](#)
  - qaQmi3Gpp2TimeZone, [696](#)
- Location Service(LOC), [51](#)
- logString
  - unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t, [976](#)
- logger
  - common.h, [1211](#)
- longName
  - nasPLMNNameResp, [549](#)
  - PLMNNetworkNameData, [675](#)
  - unpack\_nas\_SLQSGetPLMNName\_t, [1001](#)
- longNameCI
  - nasPLMNNameResp, [549](#)
  - unpack\_nas\_SLQSGetPLMNName\_t, [1001](#)
- longNameEn
  - nasPLMNNameResp, [549](#)
  - unpack\_nas\_SLQSGetPLMNName\_t, [1001](#)
- longNameLen
  - nasPLMNNameResp, [549](#)
  - PLMNNetworkNameData, [675](#)
  - unpack\_nas\_SLQSGetPLMNName\_t, [1001](#)
- longNameSB
  - nasPLMNNameResp, [549](#)
  - unpack\_nas\_SLQSGetPLMNName\_t, [1001](#)
- longNameSpareBits
  - PLMNNetworkNameData, [675](#)
- Longitude
  - GPSSStateInfo, [293](#)
- LteBandCapability
  - unpack\_dms\_SLQSGetBandCapability\_t, [971](#)
- LteCQIParm, [402](#)
  - CQIValueCW0, [403](#)
  - CQIValueCW1, [403](#)
  - ValidityCW0, [403](#)
  - ValidityCW1, [403](#)
- LteEARFCN, [403](#)
  - earfcn0, [404](#)
  - earfcn1, [404](#)
  - status, [404](#)
- LteEmmDI
  - NasSwiIndReg, [555](#)
  - pack\_nas\_SLQSNasSwiOTAMessageCallback\_t, [610](#)
- LteEmmUI
  - NasSwiIndReg, [555](#)
  - pack\_nas\_SLQSNasSwiOTAMessageCallback\_t, [610](#)
- LteEsmDI
  - NasSwiIndReg, [555](#)
  - pack\_nas\_SLQSNasSwiOTAMessageCallback\_t, [610](#)
- LteEsmUI
  - NasSwiIndReg, [556](#)

- pack\_nas\_SLQSNasSwiOTAMessageCallback\_t, 610
- LteGsmCellInfo
  - LTEInfoNeighboringGSM, 412
  - nas\_LTEInfoNeighboringGSM, 476
- LteGsmCellInfo, 404
  - cellReselPriority, 405
  - cells\_len, 405
  - GsmCellInfo, 405
  - nccPermitted, 405
  - threshGsmHigh, 405
  - threshGsmLow, 405
- LteNasReleaseInfo
  - qaGobiApiCbk.h, 1308
- LteNasReleaseInfo\_s, 413
  - nas\_major, 413
  - nas\_minor, 413
  - nas\_release, 413
- LtePCI, 414
  - earfcn, 414
  - pci, 414
  - status, 414
- LteQci
  - unpack\_qos\_swiQosFlow\_t, 1048
- LteRsrpDelta
  - nas\_SLQSSignalStrengthsIndReq, 499
  - SLQSSignalStrengthsIndReq, 819
- LteRsrpinfo
  - nas\_SLQSSignalStrengthsInformation, 500
  - SLQSSignalStrengthsInformation, 820
- LteRsrpinformation, 414
  - rsrplevel, 415
- LteSSInfo, 422
  - rsrp, 423
  - rsrq, 423
  - rssi, 423
  - snr, 423
- LteSnrDelta
  - nas\_SLQSSignalStrengthsIndReq, 500
  - SLQSSignalStrengthsIndReq, 819
- LteSnrinfo
  - nas\_SLQSSignalStrengthsInformation, 500
  - SLQSSignalStrengthsInformation, 820
- LteSnrinformation, 419
  - snrlevel, 420
- LteWcdmaCellInfo, 425
  - cellReselPriority, 426
  - cellsLen, 426
  - threshXhigh, 426
  - threshXlow, 426
  - uarfcn, 426
  - WCDMACellInfo, 426
- ltersrp
  - slqsSignalStrengthInfo, 817
  - unpack\_nas\_SLQSGetSignalStrength\_t, 1005
- ltesnr
  - slqsSignalStrengthInfo, 817
  - unpack\_nas\_SLQSGetSignalStrength\_t, 1005
- m\_FwBuildId
  - CarrierImage\_t, 146
  - SWI\_STRUCT\_CarrierImage, 852
- m\_FwImageld
  - CarrierImage\_t, 146
  - SWI\_STRUCT\_CarrierImage, 852
- m\_PriBuildId
  - CarrierImage\_t, 146
  - SWI\_STRUCT\_CarrierImage, 852
- m\_Prilmageld
  - CarrierImage\_t, 146
  - SWI\_STRUCT\_CarrierImage, 852
- m\_nCarrierId
  - CarrierImage\_t, 146
  - SWI\_STRUCT\_CarrierImage, 852
- m\_nFolderId
  - CarrierImage\_t, 146
  - SWI\_STRUCT\_CarrierImage, 852
- m\_nStorage
  - CarrierImage\_t, 146
  - SWI\_STRUCT\_CarrierImage, 852
- MACIndex
  - NetworkStatEVDO, 567
- MAX\_BUILD\_ID\_LEN
  - dms.h, 1218
  - qaGobiApiDms.h, 1404
- MAX\_CALL\_NO\_LEN
  - qaGobiApiVoice.h, 1657
- MAX\_CONTENT\_LENGTH
  - qaGobiApiUim.h, 1643
- MAX\_CUST\_ID\_LEN
  - qaGobiApiDms.h, 1404
- MAX\_FSN\_LENGTH
  - qaGobiApiDms.h, 1404
- MAX\_ICCID\_LENGTH
  - qaGobiApiUim.h, 1643
  - uim.h, 1774
- MAX\_MSE\_TWS\_MSG
  - sms.h, 1752
- MAX\_NO\_OF\_CALLS
  - qaGobiApiCbk.h, 1304
  - qaGobiApiVoice.h, 1657
- MAX\_NO\_OF\_FILES
  - qaGobiApiCbk.h, 1304
- MAX\_NO\_OF\_SLOTS
  - qaGobiApiCbk.h, 1304
  - qaGobiApiUim.h, 1643
  - uim.h, 1774
- MAX\_NO\_OF\_UUSINFO
  - qaGobiApiCbk.h, 1304
- MAX\_PATH\_LENGTH
  - qaGobiApiCbk.h, 1304
  - qaGobiApiUim.h, 1643
- MAX\_PILOT\_SETS
  - qaGobiApiNas.h, 1482
- MAX\_PUK\_LENGTH
  - qaGobiApiUim.h, 1643
- MAX\_SLOTS\_STATUS

- qaGobiApiUim.h, 1643
- uim.h, 1774
- MAX\_SMS\_LIST\_SIZE
  - sms.h, 1753
- MAX\_SMS\_ROUTES
  - qaGobiApiSms.h, 1558
- MAX\_TEMP\_DATA\_LEN
  - qaGobiApiLoc.h, 1472
- MAXUSSDLENGTH
  - qaGobiApiCbk.h, 1304
  - qaGobiApiVoice.h, 1657
- MCC
  - \_SlqsNas3GppNetworkRAT\_, 70
  - CDMASysInfo, 164
  - CDMASysInfoExt, 165
  - currentPLMN, 190
  - GSMSysInfo, 300
  - LTESysInfo, 425
  - nas\_CDMASysInfo, 443
  - nas\_CDMASysInfoExt, 443
  - nas\_currentPLMN, 448
  - nas\_GSMSysInfo, 462
  - nas\_LTESysInfo, 484
  - nas\_QmiNas3GppNetworkInfo, 491
  - nas\_QmiNas3GppNetworkRAT, 492
  - nas\_QmisNasPcsDigit, 493
  - nas\_WCDMASysInfo, 523
  - SlqsNas3GppNetworkInfo, 807
  - SlqsNasPcsDigit, 808
  - unpack\_nas\_GetServingNetwork\_t, 995
  - WCDMASysInfo, 1172
- MDMCallDuration
  - ConnectionStatus, 178
  - connectionStatus, 178
- MDMConnStatus
  - ConnectionStatus, 178
  - connectionStatus, 178
- MEIDString
  - unpack\_dms\_GetDeviceSerialNumbers\_t, 957
- MIN
  - unpack\_dms\_GetVoiceNumber\_t, 963
- MINREQBKLEN
  - common.h, 1211
- MMTlv
  - unpack\_sms\_SetNewSMSCallback\_ind\_t, 1052
- MNC
  - \_SlqsNas3GppNetworkRAT\_, 70
  - CDMASysInfo, 164
  - currentPLMN, 191
  - GSMSysInfo, 300
  - LTESysInfo, 425
  - nas\_CDMASysInfo, 443
  - nas\_currentPLMN, 448
  - nas\_GSMSysInfo, 462
  - nas\_LTESysInfo, 484
  - nas\_QmiNas3GppNetworkInfo, 491
  - nas\_QmiNas3GppNetworkRAT, 492
  - nas\_QmisNasPcsDigit, 493
  - nas\_WCDMASysInfo, 523
  - SlqsNas3GppNetworkInfo, 808
  - unpack\_nas\_GetServingNetwork\_t, 995
  - WCDMASysInfo, 1172
- MNRInfo, 429
  - mcc, 430
  - mnc, 430
  - rat, 430
- MPTlv
  - NASQmiCbkNasSystemSelPrefInd, 550
- MSGID\_AND\_LEN
  - common.h, 1211
- MSGID\_DONT\_CARE
  - common.h, 1211
- MTMessageInfo
  - newMTMessageTlv, 568
- Mask
  - getDUNCallInfoReq, 264
  - pack\_wds\_SLQSGetDUNCallInfo\_t, 644
- mask
  - BdsSV, 125
  - CellDb, 165
  - ClkInfo, 172
  - GnssData, 287
  - IPv6TrafCls, 341
  - loc\_BdsSV, 376
  - loc\_CellDb, 377
  - loc\_ClkInfo, 379
  - loc\_GnssData, 382
  - loc\_SV, 386
  - SV, 849
  - Tos, 889
  - unpack\_qos\_IPv6TrafCls\_t, 1029
  - unpack\_qos\_Tos\_t, 1049
- max\_channel\_rx\_rate
  - WDSSWICurrentChannelRates, 1206
- max\_channel\_tx\_rate
  - WDSSWICurrentChannelRates, 1207
- max\_dist
  - pack\_swiloc\_SwiLocSetAutoStart\_t, 625
  - SwiLocGetAutoStartResp, 855
  - SwiLocSetAutoStartReq, 857
  - unpack\_swiloc\_SwiLocGetAutoStart\_t, 1056
- max\_dist\_reported
  - SwiLocGetAutoStartResp, 855
  - unpack\_swiloc\_SwiLocGetAutoStart\_t, 1056
- max\_time
  - pack\_swiloc\_SwiLocSetAutoStart\_t, 625
  - SwiLocGetAutoStartResp, 855
  - SwiLocSetAutoStartReq, 857
  - unpack\_swiloc\_SwiLocGetAutoStart\_t, 1056
- max\_time\_reported
  - SwiLocGetAutoStartResp, 855
  - unpack\_swiloc\_SwiLocGetAutoStart\_t, 1056
- MaxAllowedPktSz
  - unpack\_qos\_swiQosFlow\_t, 1048
- MaxChanRxRate

- ChannelRate, 168
- dunchannelRate, 230
- MaxChanTxRate
  - ChannelRate, 168
  - dunchannelRate, 230
- maxChannelRXRate
  - unpack\_wds\_GetConnectionRate\_t, 1071
- maxChannelTXRate
  - unpack\_wds\_GetConnectionRate\_t, 1071
- maxDIBitRate
  - LibPackQosClassID, 369
  - QosClassID, 728
- maxDownlinkBitrate
  - LibPackUMTSQoS, 374
  - UMTSMInQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMInQoS, 1185
- maxImages
  - FMSImageIDEntries, 247
  - ImageIDEntries, 315
- maxMitigationLevel
  - mitigationDevList, 429
- MaxRXChannelRate
  - unpack\_dms\_GetDeviceCap\_t, 955
- maxRxChannelRate
  - unpack\_dms\_GetDeviceCapabilities\_t, 956
- maxSDUSize
  - LibPackUMTSQoS, 374
  - UMTSMInQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMInQoS, 1185
- maxStorageSize
  - smsMaxStorageSizeResp, 832
- MaxTXChannelRate
  - unpack\_dms\_GetDeviceCap\_t, 955
- maxTxChannelRate
  - unpack\_dms\_GetDeviceCapabilities\_t, 956
- maxUIBitRate
  - LibPackQosClassID, 369
  - QosClassID, 728
- maxUplinkBitrate
  - LibPackUMTSQoS, 374
  - UMTSMInQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMInQoS, 1185
- mcTimeStamp
  - cdmaMsgDecodingParams, 156
- mcc
  - CSGID, 185
  - MNRInfo, 430
  - nas\_CSGID, 447
  - nas\_MNRInfo, 487
  - nas\_netSelectionPref, 487
  - nasPLMNNameReq, 546
  - netSelectionPref, 560
  - OperatorPLMNData, 581
  - pack\_nas\_SLQSGetPLMNName\_t, 599
  - unpack\_nas\_GetHomeNetwork\_t, 991
- mccM
  - minBasedIMSI, 428
- mccT
  - trueIMSI, 893
- mdmCallDurationActive
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, 1080
- MdmConnStatus
  - DUNCallInfoInd, 230
- meanThroughputClass
  - GPRSQoS, 288
  - GPRSRequestedQoS, 289
  - LibPackGPRSRequestedQoS, 342
  - wds\_GPRSQoS, 1176
- meid
  - unpack\_dms\_GetSerialNumbers\_t, 963
- meidLength
  - \_SLQSSwiGetSerialNoExtParams, 81
- meidSize
  - serialNumbersInfo, 762
  - unpack\_dms\_GetDeviceSerialNumbers\_t, 957
- message
  - unpack\_sms\_SLQSGetSMS\_t, 1053
- message\_type
  - NASOTAMessageTlv, 542
- messageClass
  - smsRouteEntry, 839
- messageFailureCode
  - slqssendsmsparams\_s, 812
  - unpack\_sms\_SendSMS\_t, 1050
- messageFormat
  - pack\_sms\_SendSMS\_t, 618
  - slqssendasyncsmsparams\_s, 810
  - slqssendsmsparams\_s, 812
  - unpack\_sms\_SLQSGetSMS\_t, 1053
- messageID
  - slqssendsmsparams\_s, 812
  - SMSAsyncRawSend\_s, 825
  - unpack\_sms\_SendSMS\_t, 1050
- messageId
  - cdmaMsgEncodingParams, 158
- messageIndex
  - pack\_sms\_SLQSGetSMS\_t, 621
  - pack\_sms\_SLQSMModifySMSStatus\_t, 623
  - qmiSmsMessageList, 722
  - SMSMTMessage, 836
  - sMSMTMessage, 835
- messageLength
  - cdmaMsgDecodingParams, 156
- messageList
  - unpack\_sms\_SLQSGetSMSList\_t, 1054
- messageListSize
  - unpack\_sms\_SLQSGetSMSList\_t, 1054
- messageMode
  - SMSMemoryInfo, 834
  - SMSMessageMode, 834
  - sMSMessageMode, 834
  - unpack\_sms\_SLQSWmsMemoryFullCallBack\_ind\_t, 1054

- MessageModelInfo
  - messageModeTlv, [427](#)
- messageModeTlv, [426](#)
  - MessageModelInfo, [427](#)
  - TlvPresent, [427](#)
- messageSize
  - pack\_sms\_SendSMS\_t, [618](#)
  - slqssendasyncsmsparams\_s, [810](#)
  - slqssendsmsparams\_s, [812](#)
  - unpack\_sms\_SLQSGetSMS\_t, [1053](#)
  - wcdmaMsgEncodingParams, [1166](#)
- messageTag
  - pack\_sms\_SLQSModifySMSStatus\_t, [623](#)
  - qmiSmsMessageList, [722](#)
  - unpack\_sms\_SLQSGetSMS\_t, [1053](#)
- messageType
  - smsRouteEntry, [839](#)
- messageWaitingInfoContent, [427](#)
  - activeInd, [427](#)
  - msgCount, [428](#)
  - msgType, [428](#)
- MicMute
  - GetAudioProfileResp, [259](#)
  - GetM2MAudioProfileResp, [277](#)
  - GetM2MAVMuteResp, [279](#)
  - SetAudioProfileReq, [771](#)
  - SetM2MAVMuteReq, [784](#)
- minBasedIMSI, [428](#)
  - imsiM1112, [428](#)
  - imsiMS1, [428](#)
  - imsiMS2, [428](#)
  - mccM, [428](#)
- MinPolicedPktSz
  - unpack\_qos\_swiQosFlow\_t, [1048](#)
- minSize
  - unpack\_dms\_GetVoiceNumber\_t, [963](#)
- minute
  - nas\_timeInfo, [509](#)
  - nas\_UniversalTime, [515](#)
  - timeInfo, [883](#)
  - UniversalTime, [952](#)
- mipMode
  - unpack\_wds\_GetMobileIP\_t, [1073](#)
- mipStatus
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- mipstatAvail
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- mitigationDevID
  - TmdDeRegNotMitigationLvIReq, [884](#)
  - TmdGetMitigationLvIReq, [885](#)
  - TmdMitigationLvIIndReq, [886](#)
  - TmdRegNotMitigationLvIReq, [887](#)
- mitigationDevIDLen
  - TmdDeRegNotMitigationLvIReq, [884](#)
  - TmdGetMitigationLvIReq, [885](#)
  - TmdMitigationLvIIndReq, [886](#)
- TmdRegNotMitigationLvIReq, [887](#)
- mitigationDevId
  - mitigationDevList, [429](#)
- mitigationDevIdLen
  - mitigationDevList, [429](#)
- MitigationDevInfo
  - QmiCbkTmdMitiLvIRptInd, [716](#)
- mitigationDevList, [428](#)
  - maxMitigationLevel, [429](#)
  - mitigationDevId, [429](#)
  - mitigationDevIdLen, [429](#)
- mnc
  - CSGID, [185](#)
  - MNRInfo, [430](#)
  - nas\_CSGID, [447](#)
  - nas\_MNRInfo, [487](#)
  - nas\_netSelectionPref, [487](#)
  - nasPLMNNameReq, [546](#)
  - netSelectionPref, [560](#)
  - OperatorPLMNData, [581](#)
  - pack\_nas\_SLQSGetPLMNName\_t, [599](#)
  - unpack\_nas\_GetHomeNetwork\_t, [991](#)
- mncPcsDigits
  - CSGID, [185](#)
  - nas\_CSGID, [447](#)
- mobileCountryCode
  - SMSEtwsPlmn, [830](#)
  - sMSEtwsPlmn, [829](#)
- mobileIP
  - pack\_wds\_SLQSSetWdsEventCallback\_t, [651](#)
- mobileNetworkCode
  - SMSEtwsPlmn, [830](#)
  - sMSEtwsPlmn, [829](#)
- mode
  - callInfo, [140](#)
  - pack\_dms\_SetEventReport\_t, [584](#)
  - pack\_dms\_SetPower\_t, [585](#)
  - pack\_loc\_SetOperationMode\_t, [593](#)
  - UIMRefreshEvent, [928](#)
- ModePref
  - NASModePreferenceTlv, [539](#)
- modelid
  - unpack\_dms\_GetModelID\_t, [961](#)
- modelid\_str
  - slqsfwinfo\_s, [806](#)
  - unpack\_dms\_GetFirmwareInfo\_t, [958](#)
- modemMode
  - CommInfo, [177](#)
  - nas\_CommInfo, [446](#)
- modemTempNotification
  - qaGobiApiCbk.h, [1309](#)
- ModemTempState
  - \_modemTempNotification, [62](#)
- ModemTemperature
  - \_modemTempNotification, [62](#)
- modemindex
  - pack\_fms\_SetImagesPreference\_t, [589](#)
- ModifyProfileIn, [430](#)

- curProfile, [431](#)
  - pProfileID, [431](#)
  - pProfileType, [431](#)
- ModifyProfileOut, [431](#)
- pExtErrorCode, [431](#)
- month
  - nas\_timeInfo, [509](#)
  - nas\_UniversalTime, [515](#)
  - timeInfo, [883](#)
  - UniversalTime, [952](#)
- msgCount
  - messageWaitingInfoContent, [428](#)
- msgDelFailureCause
  - SMSAsyncRawSend\_s, [825](#)
- msgDelFailureType
  - SMSAsyncRawSend\_s, [825](#)
- msgProtocol
  - smsMsgprotocolResp, [835](#)
- msgType
  - messageWaitingInfoContent, [428](#)
- msgWaitInfo
  - getMsgWaitingInfo, [282](#)
  - msgWaitingInfo, [432](#)
- msgWaitingInfo, [432](#)
  - msgWaitInfo, [432](#)
  - numInstances, [432](#)
- msgid
  - pack\_qmi\_t, [615](#)
  - unpack\_qmi\_t, [1027](#)
- msgtype
  - common.h, [1212](#)
- Mtu
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1082](#)
- MultDisc
  - protocolSubtypeElement, [694](#)
- multiplier
  - pktErrRate, [673](#)
  - unpack\_qos\_pktErrRate\_t, [1030](#)
- NAI
  - unpack\_wds\_GetMobileIPProfile\_t, [1074](#)
- NAM\_NAME\_LENGTH
  - qaGobiApiNas.h, [1482](#)
- NAS\_PLMN\_LENGTH
  - nas.h, [1264](#)
- NAS\_SRV
  - qaGobiApiCbk.h, [1304](#)
- NASBandPreferenceTlv, [523](#)
  - band\_pref, [523](#)
  - TlvPresent, [523](#)
- NASEmergencyModeTlv, [525](#)
  - EmerMode, [525](#)
  - TlvPresent, [525](#)
- NASGWAcqOrderPrefTlv, [534](#)
  - GWAcqOrderPref, [534](#)
  - TlvPresent, [534](#)
- NASLTEBandPreferenceTlv, [538](#)
  - LTEBandPref, [538](#)
  - TlvPresent, [538](#)
- NASLteNasReleaseInfoTlv, [539](#)
  - nas\_major, [539](#)
  - nas\_minor, [539](#)
  - nas\_release, [539](#)
  - TlvPresent, [539](#)
- NASModePreferenceTlv, [539](#)
  - ModePref, [539](#)
  - TlvPresent, [539](#)
- NASNetSelPreferenceTlv, [539](#)
  - NetSelPref, [539](#)
  - TlvPresent, [539](#)
- NASOTAMessageTlv, [541](#)
  - data\_buf, [542](#)
  - data\_len, [542](#)
  - message\_type, [542](#)
  - TlvPresent, [542](#)
- NASPRLPreferenceTlv, [549](#)
  - PRLPref, [549](#)
  - TlvPresent, [549](#)
- NASPhyCaAggPcellInfo, [542](#)
  - dl\_bw\_value, [543](#)
  - freq, [543](#)
  - iLTEbandValue, [543](#)
  - pci, [543](#)
  - TlvPresent, [543](#)
- NASPhyCaAggScellIDIBw, [543](#)
  - dl\_bw\_value, [543](#)
  - TlvPresent, [543](#)
- NASPhyCaAggScellIndType, [544](#)
  - freq, [544](#)
  - pci, [544](#)
  - scell\_state, [545](#)
  - TlvPresent, [545](#)
- NASPhyCaAggScellIndex, [543](#)
  - scell\_idx, [544](#)
  - TlvPresent, [544](#)
- NASPhyCaAggScellInfo, [545](#)
  - dl\_bw\_value, [545](#)
  - freq, [546](#)
  - iLTEbandValue, [546](#)
  - pci, [546](#)
  - scell\_state, [546](#)
  - TlvPresent, [546](#)
- NASQmiCbkNasSwiOTAMessageInd, [549](#)
  - nasRelInfoTlv, [550](#)
  - otaMsgTlv, [550](#)
  - timeTlv, [550](#)
- NASQmiCbkNasSystemSelPrefInd, [550](#)
  - BPTlv, [550](#)
  - EMTlv, [550](#)
  - GWAOPTlv, [550](#)
  - LBPTlv, [550](#)
  - MPTlv, [550](#)
  - NSPTlv, [550](#)
  - PRLPTlv, [550](#)
  - RPTlv, [550](#)
  - SDPTlv, [550](#)
- NASRoamPreferenceTlv, [550](#)



- RoamPref, [550](#)
- TlvPresent, [550](#)
- NASServDomainPrefTlv, [551](#)
  - SrvDomainPref, [551](#)
  - TlvPresent, [551](#)
- NASServingSystemInfo, [551](#)
  - csAttachState, [552](#)
  - hdrPersonality, [552](#)
  - psAttachState, [552](#)
  - radiInterfaceList, [552](#)
  - radiInterfaceNo, [552](#)
  - registrationState, [553](#)
  - selectedNetwork, [553](#)
- NASTimeInfoTlv, [559](#)
  - time, [559](#)
  - TlvPresent, [559](#)
- NSPTlv
  - NASQmiCbkNasSystemSelPrefInd, [550](#)
- NSSAudioCtrl, [571](#)
  - downLink, [571](#)
  - upLink, [571](#)
- NUM\_OF\_SET
  - qaGobiApiCbk.h, [1304](#)
  - qaGobiApiSms.h, [1558](#)
- NWProfile, [571](#)
  - pProfSz, [572](#)
  - pProfValues, [572](#)
  - tech, [572](#)
- NWQoSStatus
  - unpack\_qos\_SLQSQosGetNetworkStatus\_t, [1033](#)
- NWRegStat
  - \_transNWRegInfoNotification, [96](#)
- naiSize
  - unpack\_wds\_GetMobileIPProfile\_t, [1074](#)
- namID
  - airTimer, [100](#)
  - nasGet3GPP2SubscriptionInfoReq, [525](#)
  - prefVoiceSO, [679](#)
  - roamTimer, [744](#)
- namName, [432](#)
  - namName, [433](#)
  - namNameLen, [433](#)
  - namName, [433](#)
- namNameLen
  - namName, [433](#)
- Name
  - unpack\_nas\_GetServingNetwork\_t, [995](#)
- name
  - unpack\_nas\_GetHomeNetwork\_t, [991](#)
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- nameLen
  - remotePartyName, [739](#)
- namePI
  - remotePartyName, [739](#)
- nameSize
  - unpack\_nas\_GetServingNetwork\_t, [995](#)
- namelength
  - omaDmFotaTlv, [577](#)
  - omaDmFotaTlvExt, [579](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- namesize
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- nas.h
  - eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_100, [1265](#)
  - eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_15, [1265](#)
  - eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_25, [1265](#)
  - eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_50, [1265](#)
  - eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_6, [1265](#)
  - eLIBPACK\_NAS\_LTE\_CPHY\_CA\_BW\_NRB\_75, [1265](#)
  - eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_C-CONFIGURED\_ACTIVATED, [1265](#)
  - eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_C-CONFIGURED\_DEACTIVATED, [1265](#)
  - eLIBPACK\_NAS\_LTE\_CPHY\_SCELL\_STATE\_D-ECONFIGURED, [1265](#)
- nas.h, [1259](#)
  - NAS\_PLMN\_LENGTH, [1264](#)
  - pack\_nas\_GetACCOLC, [1265](#)
  - pack\_nas\_GetANAAAAuthenticationStatus, [1265](#)
  - pack\_nas\_GetCDMANetworkParameters, [1265](#)
  - pack\_nas\_GetHomeNetwork, [1266](#)
  - pack\_nas\_GetNetworkPreference, [1266](#)
  - pack\_nas\_GetRFInfo, [1266](#)
  - pack\_nas\_GetServingNetwork, [1266](#)
  - pack\_nas\_GetServingNetworkCapabilities, [1268](#)
  - pack\_nas\_GetSignalStrengths, [1268](#)
  - pack\_nas\_PerformNetworkScan, [1268](#)
  - pack\_nas\_SLQSGetNetworkTime, [1270](#)
  - pack\_nas\_SLQSGetPLMNName, [1270](#)
  - pack\_nas\_SLQSGetServingSystem, [1271](#)
  - pack\_nas\_SLQSGetSignalStrength, [1271](#)
  - pack\_nas\_SLQSGetSysInfo, [1271](#)
  - pack\_nas\_SLQSGetSysSelectionPref, [1272](#)
  - pack\_nas\_SLQSInitiateNetworkRegistration, [1272](#)
  - pack\_nas\_SLQSNasConfigSigInfo2, [1272](#)
  - pack\_nas\_SLQSNasGetCellLocationInfo, [1273](#)
  - pack\_nas\_SLQSNasGetSigInfo, [1273](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt, [1273](#)
  - pack\_nas\_SLQSNasSwiModemStatus, [1274](#)
  - pack\_nas\_SLQSNasSwiOTAMessageCallback, [1274](#)
  - pack\_nas\_SLQSSetBandPreference, [1274](#)
  - pack\_nas\_SLQSSetSignalStrengthsCallback, [1275](#)
  - pack\_nas\_SLQSSetSysSelectionPref, [1275](#)
  - pack\_nas\_SLQSSwiGetLteCQI, [1275](#)
  - pack\_nas\_SetACCOLC, [1269](#)
  - pack\_nas\_SetLURRejectCallback, [1269](#)
  - pack\_nas\_SetNetworkPreference, [1269](#)
  - pack\_nas\_SetRFInfoCallback, [1270](#)

- pack\_nas\_SlqsGetLTECphyCAInfo, 1270
- unpack\_nas\_GetACCOLC, 1276
- unpack\_nas\_GetANAAAAAuthenticationStatus, 1276
- unpack\_nas\_GetCDMANetworkParameters, 1276
- unpack\_nas\_GetHomeNetwork, 1277
- unpack\_nas\_GetNetworkPreference, 1277
- unpack\_nas\_GetRFInfo, 1277
- unpack\_nas\_GetServingNetwork, 1277
- unpack\_nas\_GetServingNetworkCapabilities, 1278
- unpack\_nas\_GetSignalStrengths, 1278
- unpack\_nas\_PerformNetworkScan, 1278
- unpack\_nas\_SLQSGetNetworkTime, 1280
- unpack\_nas\_SLQSGetPLMNName, 1281
- unpack\_nas\_SLQSGetServingSystem, 1281
- unpack\_nas\_SLQSGetSignalStrength, 1281
- unpack\_nas\_SLQSGetSysInfo, 1282
- unpack\_nas\_SLQSGetSysSelectionPref, 1282
- unpack\_nas\_SLQSInitiateNetworkRegistration, 1282
- unpack\_nas\_SLQSNasConfigSigInfo2, 1283
- unpack\_nas\_SLQSNasGetCellLocationInfo, 1283
- unpack\_nas\_SLQSNasGetSigInfo, 1283
- unpack\_nas\_SLQSNasIndicationRegisterExt, 1284
- unpack\_nas\_SLQSNasNetworkTimeCallback\_ind, 1284
- unpack\_nas\_SLQSNasSigInfoCallback, 1284
- unpack\_nas\_SLQSNasSwiModemStatus, 1285
- unpack\_nas\_SLQSNasSwiOTAMessageCallback, 1285
- unpack\_nas\_SLQSNasSwiOTAMessageCallback\_ind, 1285
- unpack\_nas\_SLQSNasSysInfoCallback, 1286
- unpack\_nas\_SLQSSetBandPreference, 1286
- unpack\_nas\_SLQSSetSignalStrengthsCallback, 1286
- unpack\_nas\_SLQSSetSysSelectionPref, 1286
- unpack\_nas\_SLQSSetSysSelectionPrefCallback\_ind, 1287
- unpack\_nas\_SLQSSwiGetLteCQI, 1287
- unpack\_nas\_SetACCOLC, 1279
- unpack\_nas\_SetDataCapabilitiesCallback\_ind, 1279
- unpack\_nas\_SetEventReportInd, 1279
- unpack\_nas\_SetLURRejectCallback, 1279
- unpack\_nas\_SetNetworkPreference, 1280
- unpack\_nas\_SetRFInfoCallback, 1280
- unpack\_nas\_SetRoamingIndicatorCallback\_ind, 1280
- unpack\_nas\_SetServingSystemCallback\_ind, 1280
- unpack\_nas\_SlqsGetLTECphyCAInfo, 1280
- nas\_AddCDMASysInfo, 433
  - geoSysIdx, 434
  - regPrd, 434
- nas\_AddSysInfo, 434
  - cellBroadcastCap, 434
  - geoSysIdx, 434
- nas\_CDMAECIOThresh, 436
  - CDMAECIOThreshListLen, 437
  - pCDMAECIOThreshList, 437
- nas\_CDMAInfo, 437
  - baseId, 438
  - baseLat, 438
  - baseLong, 438
  - nid, 438
  - refpn, 438
  - sid, 438
- nas\_CDMARSSIThresh, 438
  - CDMARSSIThreshListLen, 439
  - pCDMARSSIThreshList, 439
- nas\_CDMASysInfo, 439
  - baseId, 442
  - baseLat, 442
  - baseLong, 442
  - bsInfoValid, 442
  - bsPRev, 442
  - bsPRevValid, 442
  - ccsSupported, 442
  - ccsSupportedValid, 442
  - cdmaSysIdValid, 443
  - isSysPrIMatch, 443
  - isSysPrIMatchValid, 443
  - MCC, 443
  - MNC, 443
  - networkID, 443
  - networkIdValid, 443
  - pRevInUse, 443
  - pRevInUseValid, 443
  - packetZone, 443
  - packetZoneValid, 443
  - sysInfoCDMA, 443
  - systemID, 443
- nas\_CDMASysInfoExt, 443
  - imsi\_11\_12, 443
  - MCC, 443
- nas\_CSGID, 446
  - id, 447
  - mcc, 447
  - mnc, 447
  - mncPcsDigits, 447
  - rat, 447
- nas\_CallBarringSysInfo, 435
  - csBarStatus, 435
  - psBarStatus, 435
- nas\_CommInfo, 445
  - imsRegState, 446
  - modemMode, 446
  - psState, 446
  - systemMode, 446
  - temperature, 446
- nas\_GERANInfo, 453
  - arfcn, 455
  - bsic, 455



- cellID, [455](#)
- insNmrCellInfo, [455](#)
- lac, [455](#)
- nmrInst, [455](#)
- plmn, [455](#)
- rxLev, [455](#)
- timingAdvance, [455](#)
- nas\_GSMRSSIThresh, [457](#)
  - GSMRSSIThreshListLen, [458](#)
  - pGSMRSSIThreshList, [458](#)
- nas\_GSMSrvStatusInfo, [458](#)
  - isPrefDataPath, [459](#)
  - srvStatus, [459](#)
  - trueSrvStatus, [459](#)
- nas\_GSMSysInfo, [459](#)
  - cellId, [462](#)
  - cellIdValid, [462](#)
  - dtmSupp, [462](#)
  - dtmSuppValid, [462](#)
  - egprsSupp, [462](#)
  - egprsSuppValid, [462](#)
  - lac, [462](#)
  - lacValid, [462](#)
  - MCC, [462](#)
  - MNC, [462](#)
  - networkIdValid, [462](#)
  - regRejectInfoValid, [462](#)
  - rejCause, [462](#)
  - rejectSrvDomain, [462](#)
  - sysInfoGSM, [462](#)
- nas\_HDRECIOThresh, [462](#)
  - HDRECIOThreshListLen, [463](#)
  - pHDRECIOThreshList, [463](#)
- nas\_HDRIOThresh, [463](#)
  - HDRIOThreshListLen, [463](#)
  - pHDRIOThreshList, [463](#)
- nas\_HDRRSSIThresh, [463](#)
  - HDRRSSIThreshListLen, [464](#)
  - pHDRRSSIThreshList, [464](#)
- nas\_HDRSINRThreshold, [464](#)
  - HDRSINRThresholdListLen, [465](#)
  - pHDRSINRThresholdList, [465](#)
- nas\_HDRSysInfo, [465](#)
  - hdrActiveProt, [467](#)
  - hdrActiveProtValid, [467](#)
  - hdrPersonality, [467](#)
  - hdrPersonalityValid, [467](#)
  - is856SysId, [467](#)
  - is856SysIdValid, [467](#)
  - isSysPrIMatch, [467](#)
  - isSysPrIMatchValid, [467](#)
  - sysInfoHDR, [467](#)
- nas\_LTEInfo, [470](#)
  - band, [472](#)
  - bandwidth, [472](#)
  - emmConnState, [472](#)
  - emmState, [472](#)
  - emmSubState, [473](#)
  - RXChan, [473](#)
  - TXChan, [473](#)
- nas\_LTEInfoInterfreq, [473](#)
  - freqsLen, [473](#)
  - InfoInterfreq, [473](#)
  - ueInIdle, [473](#)
- nas\_LTEInfoIntrafreq, [473](#)
  - CellParams, [475](#)
  - cellReselPriority, [475](#)
  - cellsLen, [475](#)
  - earfcn, [475](#)
  - globalCellId, [476](#)
  - plmn, [476](#)
  - sIntraSearch, [476](#)
  - sNonIntraSearch, [476](#)
  - servingCellId, [476](#)
  - tac, [476](#)
  - threshServingLow, [476](#)
  - ueInIdle, [476](#)
- nas\_LTEInfoNeighboringGSM, [476](#)
  - freqsLen, [476](#)
  - LteGsmCellInfo, [476](#)
  - ueInIdle, [476](#)
- nas\_LTEInfoNeighboringWCDMA, [477](#)
  - freqsLen, [477](#)
  - ueInIdle, [477](#)
- nas\_LTERSRPThresh, [478](#)
  - LTERSRPThreshListLen, [478](#)
  - pLTERSRPThreshList, [478](#)
- nas\_LTERSRQThresh, [478](#)
  - LTERSRQThreshListLen, [479](#)
  - pLTERSRQThreshList, [479](#)
- nas\_LTERSSIThresh, [479](#)
  - LTERSSIThreshListLen, [479](#)
  - pLTERSSIThreshList, [479](#)
- nas\_LTESNRThreshold, [481](#)
  - LTESNRThresholdListLen, [482](#)
  - pLTESNRThresholdList, [482](#)
- nas\_LTESigRptConfig, [479](#)
  - avgPeriod, [481](#)
  - rptRate, [481](#)
- nas\_LTESysInfo, [482](#)
  - cellId, [484](#)
  - cellIdValid, [484](#)
  - lac, [484](#)
  - lacValid, [484](#)
  - MCC, [484](#)
  - MNC, [484](#)
  - networkIdValid, [484](#)
  - regRejectInfoValid, [484](#)
  - rejCause, [484](#)
  - rejectSrvDomain, [484](#)
  - sysInfoLTE, [484](#)
  - tac, [484](#)
  - tacValid, [485](#)
- nas\_MNRInfo, [486](#)
  - mcc, [487](#)
  - mnc, [487](#)

- rat, [487](#)
- nas\_QmiNas3GppNetworkInfo, [490](#)
  - Description, [491](#)
  - Forbidden, [491](#)
  - InUse, [491](#)
  - MCC, [491](#)
  - MNC, [491](#)
  - Preferred, [491](#)
  - Roaming, [491](#)
- nas\_QmiNas3GppNetworkRAT, [491](#)
  - MCC, [492](#)
  - MNC, [492](#)
  - RAT, [492](#)
- nas\_QmisNasPcsDigit, [492](#)
  - includes\_pcs\_digit, [493](#)
  - MCC, [493](#)
  - MNC, [493](#)
- nas\_RFInfoTlv, [493](#)
  - activeBandClass, [494](#)
  - activeChannel, [494](#)
  - radiInterface, [494](#)
  - radiInterfaceSize, [494](#)
  - TlvPresent, [494](#)
- nas\_RejectReasonTlv, [493](#)
  - rejectCause, [493](#)
  - serviceDomain, [493](#)
  - TlvPresent, [493](#)
- nas\_SLQSSignalStrengthsIndReq, [499](#)
  - ecioDelta, [499](#)
  - ecioThresholdList, [499](#)
  - ecioThresholdListLen, [499](#)
  - ioDelta, [499](#)
  - lteRsrpDelta, [499](#)
  - lteSnrDelta, [500](#)
  - rsrqDelta, [500](#)
  - rxSignalStrengthDelta, [500](#)
  - sinrDelta, [500](#)
  - sinrThresholdList, [500](#)
  - sinrThresholdListLen, [500](#)
- nas\_SLQSSignalStrengthsInformation, [500](#)
  - ecioInfo, [500](#)
  - errorRateInfo, [500](#)
  - io, [500](#)
  - lteRsrpinfo, [500](#)
  - lteSnrinfo, [500](#)
  - rsrqInfo, [500](#)
  - rxSignalStrengthInfo, [500](#)
  - sinr, [501](#)
- nas\_SLQSSignalStrengthsTlv, [501](#)
  - sSLQSSignalStrengthsInfo, [501](#)
  - TlvPresent, [501](#)
- nas\_SignalStrengthTlv, [498](#)
  - radiInterface, [499](#)
  - signalStrength, [499](#)
  - TlvPresent, [499](#)
- nas\_SrvStatusInfo, [501](#)
  - isPrefDataPath, [502](#)
  - srvStatus, [502](#)
- nas\_TDSCDMAECIOThresh, [505](#)
- nas\_TDSCDMARSCPTThresh, [506](#)
- nas\_TDSCDMARSSIThresh, [506](#)
- nas\_TDSCDMASINRThresh, [507](#)
- nas\_UMTSInfo, [509](#)
  - cellID, [511](#)
  - ecio, [511](#)
  - geranInst, [511](#)
  - GeranInstInfo, [511](#)
  - lac, [511](#)
  - plmn, [511](#)
  - psc, [511](#)
  - rscp, [511](#)
  - UMTSInstInfo, [511](#)
  - uarfcn, [511](#)
  - umtsInst, [511](#)
- nas\_UMTSinstInfo, [511](#)
  - umtsEcio, [512](#)
  - umtsPsc, [512](#)
  - umtsRscp, [512](#)
  - umtsUarfcn, [512](#)
- nas\_UniversalTime, [513](#)
  - day, [515](#)
  - dayOfWeek, [515](#)
  - hour, [515](#)
  - minute, [515](#)
  - month, [515](#)
  - second, [515](#)
  - year, [515](#)
- nas\_WCDMAECIOThresh, [516](#)
- nas\_WCDMAInfoLTENeighborCell, [517](#)
  - umtsLTENbrCellLen, [518](#)
  - wcdmaRRCState, [518](#)
- nas\_WCDMARSSIThresh, [518](#)
- nas\_WCDMASysInfo, [519](#)
  - cellId, [522](#)
  - cellIdValid, [522](#)
  - hsCallStatus, [522](#)
  - hsCallStatusValid, [522](#)
  - hsInd, [522](#)
  - hsIndValid, [522](#)
  - lac, [522](#)
  - lacValid, [523](#)
  - MCC, [523](#)
  - MNC, [523](#)
  - networkIdValid, [523](#)
  - psc, [523](#)
  - pscValid, [523](#)
  - regRejectInfoValid, [523](#)
  - rejCause, [523](#)
  - rejectSrvDomain, [523](#)
  - sysInfoWCDMA, [523](#)
- nas\_acqOrderPref, [433](#)
  - acqOrdeLen, [433](#)
  - pAcqOrder, [433](#)
- nas\_callBarStatus, [435](#)
  - csBarStatus, [436](#)
  - psBarStatus, [436](#)

- nas\_cellParams, 444
  - pci, 444
  - rsrp, 444
  - rsrq, 444
  - rsqi, 444
  - srxlev, 444
- nas\_currentPLMN, 447
  - MCC, 448
  - MNC, 448
  - netDescr, 448
  - netDescrLength, 448
- nas\_dataSrvCapabilities, 448
  - dataCapabilities, 449
  - dataCapabilitiesLen, 449
- nas\_detailSvcInfo, 449
  - hdrHybrid, 451
  - hdrSrvStatus, 451
  - isSysForbidden, 451
  - srvCapability, 451
  - srvStatus, 451
- nas\_ecioListElement, 451
  - ecio, 452
  - radioIf, 452
- nas\_errorRateListElement, 452
  - errorRate, 453
  - radioIf, 453
- nas\_geranInstInfo, 455
  - geranArfcn, 456
  - geranBsicBcc, 456
  - geranBsicNcc, 456
  - geranRssi, 456
- nas\_gsmCellInfo, 456
  - arfcn, 457
  - band1900, 457
  - bsicId, 457
  - cellIdValid, 457
  - rssi, 457
  - srxlev, 457
- nas\_infoInterFreq, 468
  - cell\_resel\_priority, 468
  - cellInterFreqParams, 468
  - cells\_len, 469
  - earfcn, 469
  - threshXHigh, 469
  - threshXLow, 469
- nas\_lteGsmCellInfo, 469
  - cellReselPriority, 470
  - cells\_len, 470
  - GsmCellInfo, 470
  - nccPermitted, 470
  - threshGsmHigh, 470
  - threshGsmLow, 470
- nas\_lteRsrpInformation, 477
  - rsrpLevel, 478
- nas\_lteSnrInformation, 481
  - snrLevel, 481
- nas\_lteWcdmaCellInfo, 485
  - cellReselPriority, 486
  - cellsLen, 486
  - threshXhigh, 486
  - threshXlow, 486
  - uarfcn, 486
  - WCDMACellInfo, 486
- nas\_major
  - LteNasReleaseInfo\_s, 413
  - NASLteNasReleaseInfoTlv, 539
- nas\_minor
  - LteNasReleaseInfo\_s, 413
  - NASLteNasReleaseInfoTlv, 539
- nas\_netSelectionPref, 487
  - mcc, 487
  - mnc, 487
  - netReg, 487
- nas\_nmrCellInfo, 487
  - nmrArfcn, 489
  - nmrBsic, 489
  - nmrCellId, 489
  - nmrLac, 489
  - nmrPlmn, 490
  - nmrRxLev, 490
- nas\_qaQmi3Gpp2TimeZone, 490
  - daylightSavings, 490
  - leapSeconds, 490
  - localTimeOffset, 490
- nas\_release
  - LteNasReleaseInfo\_s, 413
  - NASLteNasReleaseInfoTlv, 539
- nas\_roamIndList, 494
  - numInstances, 495
  - radioInterface, 495
  - roamIndicator, 495
- nas\_rsrqInformation, 495
  - radioIf, 495
  - rsrq, 495
- nas\_rxSignalStrengthListElement, 495
  - radioIf, 496
  - rxSignalStrength, 496
- nas\_servSystem, 496
  - csAttachState, 498
  - numRadioInterfaces, 498
  - psAttachState, 498
  - radioInterface, 498
  - regState, 498
  - selNetwork, 498
- nas\_sysInfoCommon, 502
  - isSysForbidden, 505
  - isSysForbiddenValid, 505
  - roamStatus, 505
  - roamStatusValid, 505
  - srvCapability, 505
  - srvCapabilityValid, 505
  - srvDomain, 505
  - srvDomainValid, 505
- nas\_timeInfo, 507
  - day, 509
  - dayLtSavingAdj, 509

- dayOfWeek, [509](#)
- hour, [509](#)
- minute, [509](#)
- month, [509](#)
- radiolInterface, [509](#)
- second, [509](#)
- timeZone, [509](#)
- TlvPresent, [509](#)
- year, [509](#)
- nas\_umtsLTENbrCell, [512](#)
  - cellsTDD, [513](#)
  - earfcn, [513](#)
  - pci, [513](#)
  - rsrp, [513](#)
  - rsrq, [513](#)
  - srxlev, [513](#)
- nas\_wcdmaCellInfo, [516](#)
  - cpich\_ecno, [516](#)
  - cpich\_rscp, [516](#)
  - psc, [516](#)
  - srxlev, [516](#)
- nasCellLocationInfoResp, [523](#)
  - pCDMAInfo, [524](#)
  - pGERANInfo, [524](#)
  - pLTEInfoInterfreq, [524](#)
  - pLTEInfoIntrafreq, [524](#)
  - pLTEInfoNeighboringGSM, [524](#)
  - pLTEInfoNeighboringWCDMA, [524](#)
  - pUMTSCellID, [524](#)
  - pUMTSInfo, [524](#)
  - pWCDMAInfoLTENeighborCell, [524](#)
- nasGet3GPP2SubscriptionInfoReq, [525](#)
  - namID, [525](#)
- nasGet3GPP2SubscriptionInfoResp, [525](#)
  - pCDMAChannel, [526](#)
  - pDirNum, [526](#)
  - pHomeSIDNID, [526](#)
  - pMinBasedIMSI, [526](#)
  - pNAMNameInfo, [526](#)
  - pTrueIMSI, [526](#)
- nasGetHDRColorCodeResp, [526](#)
  - pColorCode, [527](#)
- nasGetLTECphyCa, [527](#)
  - sPhyCaAggPcellInfo, [527](#)
  - sPhyCaAggScellIDBw, [527](#)
  - sPhyCaAggScellIndType, [527](#)
  - sPhyCaAggScellIndex, [527](#)
  - sPhyCaAggScellInfo, [527](#)
- NasGetLTECphyCaInfo, [527](#)
  - PhyCaAggPcellInfo, [527](#)
  - PhyCaAggScellIDBw, [527](#)
  - PhyCaAggScellIndType, [528](#)
  - PhyCaAggScellIndex, [527](#)
  - PhyCaAggScellInfo, [528](#)
- nasGetLTECphyCaResp, [528](#)
  - pPhyCaAggPcellInfo, [528](#)
  - pPhyCaAggScellIDBw, [528](#)
  - pPhyCaAggScellIndType, [528](#)
  - pPhyCaAggScellIndex, [528](#)
  - pPhyCaAggScellInfo, [528](#)
- nasGetSigInfoResp, [528](#)
  - pPhyCaAggScellIndex, [528](#)
  - pPhyCaAggScellInfo, [528](#)
- nasGetSysInfoResp, [529](#)
  - pAddCDMASysInfo, [531](#)
  - pAddGSMsSysInfo, [531](#)
  - pAddHDRSysInfo, [532](#)
  - pAddLTESysInfo, [532](#)
  - pAddWCDMASysInfo, [532](#)
  - pCDMASrvStatusInfo, [532](#)
  - pCDMASysInfo, [532](#)
  - pGSMCallBarringSysInfo, [532](#)
  - pGSMCipherDomainSysInfo, [532](#)
  - pGSMsSrvStatusInfo, [532](#)
  - pGSMsSysInfo, [532](#)
  - pHDRSrvStatusInfo, [532](#)
  - pHDRSysInfo, [532](#)
  - pLTESrvStatusInfo, [532](#)
  - pLTESysInfo, [532](#)
  - pLTEVoiceSupportSysInfo, [532](#)
  - pWCDMACallBarringSysInfo, [532](#)
  - pWCDMACipherDomainSysInfo, [532](#)
  - pWCDMASrvStatusInfo, [532](#)
  - pWCDMASysInfo, [532](#)
- nasGetTxRxInfoReq, [532](#)
  - radio\_if, [533](#)
- nasGetTxRxInfoResp, [533](#)
  - pRXChain0Info, [533](#)
  - pRXChain1Info, [533](#)
  - pTXInfo, [533](#)
- nasIndicationRegisterReq, [534](#)
  - pDDTMInd, [537](#)
  - pDualStandByPrefInd, [537](#)
  - pErrorRateInd, [537](#)
  - pHDRNewUATIAssInd, [537](#)
  - pHDRSessionCloseInd, [537](#)
  - pLTECphyCa, [537](#)
  - pManagedRoamingInd, [537](#)
  - pNetworkTimeInd, [537](#)
  - pServingSystemInd, [537](#)
  - pSignalStrengthInd, [537](#)
  - pSubscriptionInfoInd, [537](#)
  - pSysInfoInd, [537](#)
  - pSystemSelectionInd, [537](#)
- nasInitNetworkReg, [537](#)
  - pChangeDuration, [538](#)
  - pMNRInfo, [538](#)
  - pMncPcsDigitStatus, [538](#)
  - regAction, [538](#)
- nasNetworkTime, [539](#)
  - pDayltSavAdj, [540](#)

- pRadioInterface, [540](#)
  - pTimeZone, [540](#)
  - universalTime, [540](#)
- nasOperatorNameResp, [540](#)
  - pNITZInformation, [541](#)
  - pOperatorNameString, [541](#)
  - pOperatorPLMNList, [541](#)
  - pPLMNNetworkName, [541](#)
  - pSrvProviderName, [541](#)
- nasPLMNNameReq, [546](#)
  - mcc, [546](#)
  - mnc, [546](#)
  - pMncPcsStatus, [547](#)
- nasPLMNNameResp, [547](#)
  - longName, [549](#)
  - longNameCI, [549](#)
  - longNameEn, [549](#)
  - longNameLen, [549](#)
  - longNameSB, [549](#)
  - shortName, [549](#)
  - shortNameCI, [549](#)
  - shortNameEn, [549](#)
  - shortNameLen, [549](#)
  - shortNameSB, [549](#)
  - spn, [549](#)
  - spnEncoding, [549](#)
  - spnLength, [549](#)
- nasRelInfoTlv
  - NASQmiCbkNasSwiOTAMessageInd, [550](#)
- nasSigInfo, [553](#)
  - pCDMASigInfo, [553](#)
  - pGSMSigInfo, [553](#)
  - pHDRSigInfo, [554](#)
  - pLTESigInfo, [554](#)
  - pRscp, [554](#)
  - pTDSCDMASigInfoExt, [554](#)
  - pWCDMASigInfo, [554](#)
- nasSwiGetChannelLockResp, [554](#)
  - pLteEARFCN, [554](#)
  - pLtePCI, [554](#)
  - pWcdmaUARFCN, [554](#)
- NasSwiIndReg, [554](#)
  - gsmUmtsDI, [555](#)
  - gsmUmtsUI, [555](#)
  - lteEmmDI, [555](#)
  - lteEmmUI, [555](#)
  - lteEsmDI, [555](#)
  - lteEsmUI, [556](#)
  - pRankIndicatorInd, [556](#)
- nasSwiSetChannelLockReq, [556](#)
  - pLteEARFCN, [556](#)
  - pLtePCI, [556](#)
  - pWcdmaUARFCN, [556](#)
- nasSysInfo, [556](#)
  - pAddCDMASysInfo, [559](#)
  - pAddGSMSysInfo, [559](#)
  - pAddHDRSysInfo, [559](#)
  - pAddLTESysInfo, [559](#)
  - pAddWCDMASysInfo, [559](#)
  - pCDMASrvStatusInfo, [559](#)
  - pCDMASysInfo, [559](#)
  - pGSMCallBarringSysInfo, [559](#)
  - pGSMCipherDomainSysInfo, [559](#)
  - pGSMSrvStatusInfo, [559](#)
  - pGSMSysInfo, [559](#)
  - pHDRSrvStatusInfo, [559](#)
  - pHDRSysInfo, [559](#)
  - pLTESrvStatusInfo, [559](#)
  - pLTESysInfo, [559](#)
  - pLTEVoiceSupportSysInfo, [559](#)
  - pSysInfoNoChange, [559](#)
  - pWCDMACallBarringSysInfo, [559](#)
  - pWCDMACipherDomainSysInfo, [559](#)
  - pWCDMASrvStatusInfo, [559](#)
  - pWCDMASysInfo, [559](#)
- nccPermitted
  - lteGsmCellInfo, [405](#)
  - nas\_lteGsmCellInfo, [470](#)
- NeighborSetCnt
  - NetworkStat1x, [565](#)
- netDescr
  - currentPLMN, [191](#)
  - nas\_currentPLMN, [448](#)
- netDescrLength
  - currentPLMN, [191](#)
  - nas\_currentPLMN, [448](#)
- netInfoLen
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- netReg
  - nas\_netSelectionPref, [487](#)
  - netSelectionPref, [560](#)
- NetSelPref
  - NASNetSelPreferenceTlv, [539](#)
- netSelectionPref, [560](#)
  - mcc, [560](#)
  - mnc, [560](#)
  - netReg, [560](#)
- NetStats, [560](#)
  - rx\_bytes, [561](#)
  - rx\_errors, [561](#)
  - rx\_overflows, [561](#)
  - rx\_packets, [561](#)
  - tx\_bytes, [561](#)
  - tx\_errors, [561](#)
  - tx\_overflows, [561](#)
  - tx\_packets, [561](#)
- Network Access Service (NAS), [34](#)
- NetworkDebugResp, [561](#)
  - pDataStatusDetail, [562](#)
  - pDeviceConfigDetail, [562](#)
  - pNetworkStat1x, [562](#)
  - pNetworkStatEVDO, [562](#)
  - pObjectVer, [562](#)
- NetworkID
  - qaQmiServingSystemParam, [701](#)

- unpack\_nas\_SLQSGetservingSystem\_t, 1004
- networkID
  - CDMASysInfo, 164
  - nas\_CDMASysInfo, 443
- networkIdValid
  - CDMASysInfo, 164
  - GSMSysInfo, 300
  - LTESysInfo, 425
  - nas\_CDMASysInfo, 443
  - nas\_GSMSysInfo, 462
  - nas\_LTESysInfo, 484
  - nas\_WCDMASysInfo, 523
  - WCDMASysInfo, 1172
- networkInfoLen
  - unpack\_wds\_SLQSGetCurrDataSystemStat\_t, 1079
- NetworkStat1x, 562
  - ActSetCnt, 565
  - NeighborSetCnt, 565
  - pActPilotPNElements, 565
  - pNeighborSetPilotPN, 565
  - RX\_EC\_IO, 565
  - RX\_PWR, 565
  - SO, 565
  - State, 565
  - TX\_PWR, 565
- NetworkStatEVDO, 565
  - MACIndex, 567
  - PER, 567
  - pSectorID, 567
  - PilotEnergy, 567
  - RX\_PWR, 567
  - SNR, 567
  - SectorIDLen, 567
  - State, 567
- NetworkType
  - CurrNetworkInfo, 194
  - currNetworkInfo, 194
  - wds\_currNetworkInfo, 1175
- NewMMTlv
  - unpack\_sms\_SetNewSMSCallback\_ind\_t, 1052
- newMTMessageTlv, 567
  - MTMessageInfo, 568
  - TlvPresent, 568
- newPINLen
  - uim\_unblockUIMPIN, 913
  - unblockUIMPIN, 951
- newPINVal
  - uim\_unblockUIMPIN, 913
  - unblockUIMPIN, 951
- newPasswd
  - voiceSetCallBarringPwdInfo, 1145
- newPasswdAgain
  - voiceSetCallBarringPwdInfo, 1145
- newPwd
  - newPwdData, 568
- newPwdAgain
  - newPwdData, 568
- newPwdData, 568
  - newPwd, 568
  - newPwdAgain, 568
- nextHeader
  - LibPackTFTIDParams, 371
  - TFTIDParams, 881
- nid
  - CDMAInfo, 154
  - nas\_CDMAInfo, 438
  - sidNid, 795
  - unpack\_nas\_GetHomeNetwork\_t, 991
- NmeaPort
  - DcsUsbPortNames, 210
- nmrArfcn
  - nas\_nmrCellInfo, 489
  - nmrCellInfo, 570
- nmrBsic
  - nas\_nmrCellInfo, 489
  - nmrCellInfo, 570
- nmrCellID
  - nas\_nmrCellInfo, 489
  - nmrCellInfo, 570
- nmrCellInfo, 568
  - nmrArfcn, 570
  - nmrBsic, 570
  - nmrCellID, 570
  - nmrLac, 570
  - nmrPlmn, 571
  - nmrRxLev, 571
- nmrInst
  - GERANInfo, 251
  - nas\_GERANInfo, 455
- nmrLac
  - nas\_nmrCellInfo, 489
  - nmrCellInfo, 570
- nmrPlmn
  - nas\_nmrCellInfo, 490
  - nmrCellInfo, 571
- nmrRxLev
  - nas\_nmrCellInfo, 490
  - nmrCellInfo, 571
- noReplyTimer
  - callFWExtInfo, 137
  - callFWInfo, 138
- Non-service specific APIs (SWI), 45
- notifType
  - voiceSUPSNotification, 1160
- notification
  - omaDmNotificationsTlv, 580
  - unpack\_omaDmNotificationsTlv\_t, 1027
- notificationType
  - SMSEtwsMessage, 828
  - sMSEtwsMessage, 827
- notused
  - unpack\_dms\_SetCrashAction\_t, 964
- num\_instances
  - \_qaQmi3GPP2BroadcastCfgInfo, 65
  - \_qaQmi3GPPBroadcastCfgInfo, 66

- custSettingList, [202](#)
  - DMScustSettingList, [223](#)
- numApp
  - slotInf, [801](#)
  - slotInfo, [803](#)
  - uim\_slotInfo, [911](#)
- numCrashes
  - CrashInfo, [182](#)
- numEntries
  - CurrentImgList, [190](#)
  - unpack\_dms\_SLQSSwiGetFirmwareCurr\_t, [974](#)
- numFeatures
  - personalizationStatus, [665](#)
- numFiles
  - registerRefresh, [737](#)
- NumFlows
  - unpack\_qos\_SLQSSetQosEventCallback\_ind\_t, [1036](#)
- numInstance
  - operatorPLMNList, [582](#)
  - PLMNNetworkName, [673](#)
- numInstances
  - arrAlertingPattern, [113](#)
  - arrAlertingType, [114](#)
  - arrAlphaID, [114](#)
  - arrCalledPartyNum, [115](#)
  - arrCallEndReason, [116](#)
  - arrCallInfo, [116](#)
  - arrConnectPartyNum, [117](#)
  - arrDiagInfo, [117](#)
  - arrRedirPartyNum, [118](#)
  - arrRemotePartyName, [119](#)
  - arrRemotePartyNum, [119](#)
  - arrSvcOption, [120](#)
  - arrUUSInfo, [121](#)
  - DomainNameList, [226](#)
  - getCallFWExtInfo, [261](#)
  - getCallFWInfo, [262](#)
  - getMsgWaitingInfo, [282](#)
  - homeSIDNID, [312](#)
  - msgWaitingInfo, [432](#)
  - nas\_roamIndList, [495](#)
  - PCSCFFQDNAddressList, [659](#)
  - PCSCFIPv4ServerAddressList, [659](#)
  - roamIndList, [743](#)
  - wds\_DomainNameList, [1176](#)
  - wds\_PCSCFFQDNAddressList, [1180](#)
  - wds\_PCSCFIPv4ServerAddressList, [1180](#)
- numLen
  - calledPartyInfo, [132](#)
  - callFWExtInfo, [137](#)
  - callFWInfo, [138](#)
  - callingPartyInfo, [142](#)
  - peerNumberInfo, [664](#)
  - redirNumInfo, [736](#)
  - remotePartyNum, [740](#)
- numOfFiles
  - UIMRefreshEvent, [928](#)
- numOfRoutes
  - smsSetRoutesReq, [839](#)
- numOpt
  - DHCPOptionList, [218](#)
  - WdsDHCPv4OptionList, [1194](#)
  - wdsDhcpv4OptionList, [1193](#)
- numPI
  - peerNumberInfo, [664](#)
- NumPilots
  - PilotSetData, [672](#)
- numPlan
  - calledPartyInfo, [132](#)
  - callFWExtInfo, [137](#)
  - callingPartyInfo, [142](#)
  - connectNumInfo, [181](#)
  - peerNumberInfo, [664](#)
  - redirNumInfo, [736](#)
- numPresInd
  - connectNumInfo, [181](#)
- numQosFlow
  - sQosStat, [843](#)
  - unpack\_qos\_SLQSQosSwiReadDataStats\_t, [1036](#)
- numRadiolInterfaces
  - nas\_servSystem, [498](#)
  - servSystem, [766](#)
- NumRxFilters
  - unpack\_qos\_QosFlowInfo\_t, [1032](#)
- numSI
  - peerNumberInfo, [664](#)
- numSlot
  - cardStatus, [144](#)
  - uim\_cardStatus, [902](#)
- NumSupUSBComps
  - unpack\_dms\_GetUSBComp\_t, [963](#)
- NumTxFilters
  - unpack\_qos\_QosFlowInfo\_t, [1032](#)
- numType
  - calledPartyInfo, [132](#)
  - callFWExtInfo, [137](#)
  - callingPartyInfo, [142](#)
  - connectNumInfo, [181](#)
  - peerNumberInfo, [664](#)
  - redirNumInfo, [736](#)
- number
  - calledPartyInfo, [132](#)
  - callFWExtInfo, [137](#)
  - callFWInfo, [138](#)
  - callingPartyInfo, [142](#)
  - ECTNum, [233](#)
  - peerNumberInfo, [664](#)
  - redirNumInfo, [736](#)
- numberPlan
  - callFwdTypeAndPlan, [135](#)
- numberType
  - callFwdTypeAndPlan, [135](#)
- NxtHdrProto
  - unpack\_qos\_swiQosFilter\_t, [1043](#)
- OKtoRefresh



- UIMRefreshOKReq, 929
- OMADMCancelSession
  - qaGobiApiOadm.h, 1525
- OMADMEnabled
  - unpack\_swima\_SLQSOMADMGetSettings\_t, 1062
- OMADMGetPendingNIA
  - qaGobiApiOadm.h, 1525
- OMADMGetSessionInfo
  - qaGobiApiOadm.h, 1526
- OMADMStartSession
  - qaGobiApiOadm.h, 1527
- OTASPStatus
  - voiceOTASPStatusInfo, 1141
- oddEvenInd
  - calledPartySubAdd, 133
- OfflineReason
  - unpack\_dms\_GetPower\_t, 962
- offset
  - readTransparentInfo, 734
  - uim\_readTransparentInfo, 906
- oldPINLen
  - changeUIMPIN, 167
  - uim\_changeUIMPIN, 903
- oldPINVal
  - changeUIMPIN, 167
  - uim\_changeUIMPIN, 903
- oldPasswd
  - voiceSetCallBarringPwdInfo, 1145
- omaDmConfig
  - sessionInfo, 766
  - sessionInfoExt, 767
- omaDmConfigTlv, 572
  - alertmsg, 572
  - alertmsglength, 572
  - state, 573
  - userInputReq, 573
  - userInputTimeout, 573
- omaDmConfigTlvExt, 573
  - alertmsg, 575
  - alertmsglength, 575
  - state, 575
  - userInputReq, 575
  - userInputTimeout, 575
- omaDmFota
  - sessionInfo, 766
  - sessionInfoExt, 767
- omaDmFotaTlv, 575
  - description, 577
  - descriptionlength, 577
  - fwloadsize, 577
  - fwloadComplete, 577
  - namelength, 577
  - package\_name, 577
  - sessionType, 577
  - severity, 577
  - state, 577
  - updateCompleteStatus, 577
- userInputReq, 577
- userInputTimeout, 577
- version, 577
- versionlength, 577
- omaDmFotaTlvExt, 577
  - description, 579
  - descriptionlength, 579
  - fumoResultCode, 579
  - namelength, 579
  - package\_name, 579
  - packageSize, 579
  - receivedBytes, 579
  - reserved, 579
  - state, 580
  - userInputTimeout, 580
  - version, 580
  - versionlength, 580
- omaDmNotifications
  - sessionInfo, 767
- omaDmNotificationsTlv, 580
  - notification, 580
  - sessionStatus, 580
- Open Mobile Alliance Service (OMA), 41
- operatingMode
  - dms\_OperatingModeTlv, 221
- OperatingModeTlv
  - unpack\_dms\_SetEventReport\_ind\_t, 965
- operation
  - depersonalizationInformation, 213
- OperationMode
  - unpack\_dms\_GetPower\_t, 962
- operatorNameString, 580
  - PLMNName, 580
- OperatorPLMNData, 580
  - lac1, 581
  - lac2, 581
  - mcc, 581
  - mnc, 581
  - PLMNRecID, 581
- operatorPLMNList, 581
  - numInstance, 582
  - PLMNData, 582
- optCode
  - DHCPOption, 217
  - WdsDHCPv4Option, 1192
  - wdsDhcpv4Option, 1193
- optVal
  - WdsDHCPv4Option, 1192
  - wdsDhcpv4Option, 1193
- optValLen
  - DHCPOption, 217
  - WdsDHCPv4Option, 1192
  - wdsDhcpv4Option, 1193
- OriginateUSSD
  - qaGobiApiVoice.h, 1658
- otaMsgTlv
  - NASQmiCbkNasSwiOTAMessageInd, 550
- p3GPP2Pri



- swiQosFlow, [867](#)
- p3GPP2TimeInfo
  - GetNetworkTimeResp, [282](#)
  - unpack\_nas\_SLQSGetNetworkTime\_t, [1001](#)
- p3GPPImCn
  - swiQosFlow, [867](#)
- p3GPPResResidualBER
  - swiQosFlow, [867](#)
- p3GPPSigInd
  - swiQosFlow, [867](#)
- p3GPPTimeInfo
  - GetNetworkTimeResp, [282](#)
  - unpack\_nas\_SLQSGetNetworkTime\_t, [1001](#)
- p3GPPTraHdlPri
  - swiQosFlow, [867](#)
- p3GppNetworkInfoInstances
  - unpack\_nas\_PerformNetworkScan\_t, [996](#)
- p3GppNetworkInstanceSize
  - unpack\_nas\_PerformNetworkScan\_t, [996](#)
- p3gppRelease
  - \_slqs3GPPConfigItem, [69](#)
- pAAASPI
  - pack\_wds\_SetMobileIPProfile\_t, [641](#)
- PACK\_WDS\_IPV4
  - wds.h, [1786](#)
- PACK\_WDS\_IPV6
  - wds.h, [1786](#)
- pAMRStatus
  - voiceGetConfigReq, [1131](#)
- pAPNClass
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pAPNClass3GPP2
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAPNDisabledFlag
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pAPNEnabled3GPP2
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAPNName
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
  - qmiWdsRunTimeSettings, [726](#)
  - swiPDPRuntimeSettingsResp, [861](#)
- pAPNNameSize
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- PASSWORD\_LENGTH
  - qaGobiApiVoice.h, [1657](#)
- pAVRXAVCHeadroom
  - RXAVCList, [749](#)
- pAVRXAVCSens
  - RXAVCList, [749](#)
- pAccelAcceptReady
  - QmiCbKLocSensorStreamingInd, [714](#)
- pAccelSamplesAccepted
  - QmiCbKLocInjectSensorDataInd, [705](#)
- pAccelTempAcceptReady
  - QmiCbKLocSensorStreamingInd, [714](#)
- pAccelTempSamplesAccepted
  - QmiCbKLocInjectSensorDataInd, [705](#)
- pAcceleroData
  - LocInjectSensorDataReq, [399](#)
- pAcceleroTempData
  - LocInjectSensorDataReq, [399](#)
- pAcceleroTimeSrc
  - LocInjectSensorDataReq, [399](#)
- pAcqOrder
  - acqOrderPref, [98](#)
  - nas\_acqOrderPref, [433](#)
- pAcqOrderPref
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [614](#)
- pActPilotPNElements
  - NetworkStat1x, [565](#)
- pAddCDMASysInfo
  - nasGetSysInfoResp, [531](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pAddGSMSysInfo
  - nasGetSysInfoResp, [531](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pAddHDRSysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pAddLTESysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pAddWCDMASysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pAddrAllocPref
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pAddress
  - pack\_wds\_SetMobileIPProfile\_t, [641](#)
- pAirTimer
  - voiceGetConfigReq, [1131](#)

- pAirTimerCnt
  - voiceGetConfigResp, [1133](#)
- pAirTimerConfig
  - voiceSetConfigReq, [1148](#)
- pAirTimerStatus
  - voiceSetConfigResp, [1150](#)
- pAlertPriority
  - cdmaMsgDecodingParams, [156](#)
- pAlertType
  - voiceCallInfoResp, [1104](#)
- pAlertingPattern
  - voiceCallInfoResp, [1104](#)
- pAllowLinger
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAlphaID
  - SMSAsyncRawSend\_s, [825](#)
- pAlphaIDInfo
  - USSResp, [1096](#)
  - voiceCallInfoResp, [1104](#)
  - voiceCallResponseParams, [1108](#)
  - voiceGetCallBarringResp, [1116](#)
  - voiceGetCallFWResp, [1119](#)
  - voiceGetCallWaitInfo, [1121](#)
  - voiceGetCLIPResp, [1123](#)
  - voiceGetCLIRResp, [1125](#)
  - voiceGetCNAPResp, [1126](#)
  - voiceGetCOLPResp, [1128](#)
  - voiceGetCOLRResp, [1129](#)
  - voiceSetCallBarringPwdResp, [1146](#)
  - voiceSetSUPSServiceResp, [1154](#)
  - voiceSUPSInfo, [1157](#)
- pAlphaIdentifier
  - USSDNoWaitIndicationInfo, [1094](#)
- pAltitudeAssumed
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pAltitudeSrcInfo
  - LocInjectPositionReq, [397](#)
- pAltitudeWrtEllipsoid
  - LocInjectPositionReq, [397](#)
  - PDSPositionData, [661](#)
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pAltitudeWrtMeanSeaLevel
  - LocInjectPositionReq, [397](#)
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pAltitudeWrtSealevel
  - PDSPositionData, [661](#)
- pAmrMode
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pAmrOctetAligned
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
- SetIMSVoIPConfigReq, [779](#)
- pAmrWBMode
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pAmrWBOctetAligned
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pAmrWbEnable
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pApnString
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pApnStringSize
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pApnname
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
- pAppName
  - loc\_LocApplicationInfo, [383](#)
  - LocApplicationInfo, [388](#)
- pAppPriority
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAppProvider
  - loc\_LocApplicationInfo, [383](#)
  - LocApplicationInfo, [388](#)
- pAppSubType
  - HDRProtSubtypResp, [305](#)
- pAppType
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAppVersion
  - loc\_LocApplicationInfo, [383](#)
  - LocApplicationInfo, [389](#)
- pApplicationInfo
  - LOCStartReq, [402](#)
  - pack\_loc\_Start\_t, [595](#)
- pArrAlertingPattern
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkInfo, [1143](#)
- pArrAlertingType
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkInfo, [1143](#)
- pArrAlphaID
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkInfo, [1143](#)
- pArrCallEndReason
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkInfo, [1143](#)
- pArrCallInfo

- voiceGetAllCallInfo, [1113](#)
- pArrCalledPartyNum
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkJInfo, [1143](#)
- pArrConnectPartyNum
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkJInfo, [1144](#)
- pArrDiagInfo
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkJInfo, [1144](#)
- pArrRedirPartyNum
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkJInfo, [1144](#)
- pArrRemotePartyName
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkJInfo, [1144](#)
- pArrRemotePartyNum
  - voiceGetAllCallInfo, [1113](#)
  - voiceSetAllCallStatusCbkJInfo, [1144](#)
- pArrSvcOption
  - voiceGetAllCallInfo, [1114](#)
  - voiceSetAllCallStatusCbkJInfo, [1144](#)
- pArrUUSInfo
  - voiceGetAllCallInfo, [1114](#)
- pAuth
  - pack\_wds\_SLQSSStartDataSession\_t, [653](#)
- pAuthPassword
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAuthPassword\_tSize
  - LibPackprofile\_3GPP2, [367](#)
- pAuthPasswordSize
  - LibpackProfile3GPP2, [354](#)
  - Profile3GPP2, [691](#)
- pAuthProtocol
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAuthRetryCount
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAuthTimeout
  - LibpackProfile3GPP2, [354](#)
  - LibPackprofile\_3GPP2, [367](#)
  - Profile3GPP2, [691](#)
- pAuthenticateResult
  - UIMAuthenticateResp, [915](#)
- pAuthentication
  - qmiWdsRunTimeSettings, [726](#)
  - ssdatasession\_params, [847](#)
- pAuthenticationPref
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pAutoAnsStatus
  - voiceSetConfigResp, [1150](#)
- pAutoAnswer
  - voiceGetConfigReq, [1131](#)
  - voiceSetConfigReq, [1148](#)
- pAutoAnswerStat
  - voiceGetConfigResp, [1133](#)
- pAutoSelection
  - UIMGetConfigurationResp, [920](#)
- pAutosdm
  - \_SLQSOMADMSettings, [76](#)
  - \_SLQSOMADMSettingsReqParams, [77](#)
  - \_SLQSOMADMSettingsReqParams3, [78](#)
  - pack\_swima\_SLQSOMADMSetSettings\_t, [628](#)
- pBandPref
  - \_sysSelectPrefInfo, [87](#)
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [614](#)
  - unpack\_nas\_SLQSGetSysSelectionPref\_t, [1012](#)
- pBdsSVInfo
  - LocDelAssDataReq, [389](#)
  - pack\_loc\_Delete\_Assist\_Data\_t, [590](#)
- pBearerID
  - QosFlowInfo, [731](#)
- pBearerId
  - swiPDPRuntimeSettingsResp, [861](#)
- pBearerTech
  - DataBearerTechExt, [205](#)
- pBurstDTMFLengths
  - voiceBurstDTMFInfo, [1101](#)
- pCCResType
  - voiceGetCallBarringResp, [1116](#)
  - voiceGetCallFWResp, [1120](#)
  - voiceGetCallWaitInfo, [1121](#)
  - voiceGetCLIPResp, [1123](#)
  - voiceGetCLIRResp, [1125](#)
  - voiceGetCNAPResp, [1126](#)
  - voiceGetCOLPResp, [1128](#)
  - voiceGetCOLRResp, [1129](#)
  - voiceSetCallBarringPwdResp, [1146](#)
- pCCResultType
  - voiceCallResponseParams, [1108](#)
  - voiceSetSUPSServiceResp, [1154](#)
- pCCSUPSType
  - voiceCallResponseParams, [1108](#)
  - voiceGetCallBarringResp, [1116](#)
  - voiceGetCallFWResp, [1120](#)
  - voiceGetCallWaitInfo, [1121](#)
  - voiceGetCLIPResp, [1123](#)
  - voiceGetCLIRResp, [1125](#)
  - voiceGetCNAPResp, [1126](#)
  - voiceGetCOLPResp, [1128](#)
  - voiceGetCOLRResp, [1129](#)
  - voiceSetCallBarringPwdResp, [1146](#)
  - voiceSetSUPSServiceResp, [1154](#)
- pCCSuppsType
  - USSResp, [1096](#)
- pCDMAChannel
  - nasGet3GPP2SubscriptionInfoResp, [526](#)
- pCDMAECIODelta

- pack\_nas\_SLQSNasConfigSigInfo2\_t, 604
- setSignalStrengthInfo, 792
- pCDMAECIOThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, 604
  - setSignalStrengthInfo, 792
- pCDMAECIOThreshList
  - CDMAECIOThresh, 153
  - nas\_CDMAECIOThresh, 437
- pCDMAFrameErrRate
  - GetErrRateResp, 270
- pCDMAInfo
  - nasCellLocationInfoResp, 524
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, 1013
- pCDMARSSIDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, 604
  - setSignalStrengthInfo, 792
- pCDMARSSIThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, 604
  - setSignalStrengthInfo, 792
- pCDMARSSIThreshList
  - CDMARSSIThresh, 159
  - nas\_CDMARSSIThresh, 439
- pCDMASSInfo
  - nasGetSigInfoResp, 529
- pCDMASigInfo
  - nasSigInfo, 553
  - unpack\_nas\_SLQSNasSigInfoCallback\_t, 1017
- pCDMASrvStatusInfo
  - nasGetSysInfoResp, 532
  - nasSysInfo, 559
  - unpack\_nas\_SLQSGetSysInfo\_t, 1008
  - unpack\_nas\_SLQSSysInfoCallback\_t, 1022
- pCDMASysInfo
  - nasGetSysInfoResp, 532
  - nasSysInfo, 559
  - unpack\_nas\_SLQSGetSysInfo\_t, 1008
  - unpack\_nas\_SLQSSysInfoCallback\_t, 1022
- pCLIPResp
  - voiceGetCLIPResp, 1124
- pCLIPstatus
  - voiceSUPSInfo, 1157
- pCLIRCause
  - voiceInfoRec, 1137
- pCLIRResp
  - voiceGetCLIRResp, 1125
- pCLIRType
  - voiceCallRequestParams, 1107
- pCLIRstatus
  - voiceSUPSInfo, 1157
- PCMparams, 655
  - iFaceTab, 657
  - iFaceTabLen, 657
- pCNAPResp
  - voiceGetCNAPResp, 1127
- pCNAPstatus
  - voiceSUPSInfo, 1157
- pCOLPResp
  - voiceGetCOLPResp, 1128
- pCOLPstatus
  - voiceSUPSInfo, 1157
- pCOLRResp
  - voiceGetCOLRResp, 1130
- pCOLRstatus
  - voiceSUPSInfo, 1157
- PCSCFAddrPCO
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, 1082
- PCSCFFQDNAddrList
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, 1083
- PCSCFFQDNAddress, 657
  - fqdnAddr, 657
  - fqdnLen, 657
- PCSCFFQDNAddressList, 657
  - numInstances, 659
  - pcsfFQDNAddress, 659
- PCSCFIPv4ServerAddressList, 659
  - numInstances, 659
  - pcsfIPv4Addr, 659
- pCSCFPortName
  - imsRegMgrConfigInfo, 329
  - SetRegMgrConfigReq, 787
- pCSCFPortNameLen
  - SetRegMgrConfigReq, 787
- pCSGID
  - \_sysSelectPrefParams, 93
  - pack\_nas\_SLQSSetSysSelectionPref\_t, 615
- pCUGIndex
  - voiceSUPSNotification, 1160
- pCUGInfo
  - voiceCallRequestParams, 1107
- pCallBarPasswd
  - voiceSUPSInfo, 1157
- pCallBarringPasswd
  - voiceSetSUPSServiceReq, 1153
- pCallEndReason
  - getDUNCallInfoResp, 268
- pCallFWNum
  - voiceSUPSInfo, 1157
- pCallFWTimerVal
  - voiceSUPSInfo, 1157
- pCallForwardingNumber
  - voiceSetSUPSServiceReq, 1153
- pCallFwdInfo
  - voiceSUPSInfo, 1157
- pCallFwdTypeAndPlan
  - voiceSetSUPSServiceReq, 1153
- pCallID
  - burstDTMFInfo, 128
  - voiceCallResponseParams, 1108
  - voiceContDTMFInfo, 1109
  - voiceFlashInfo, 1111
  - voiceGetCallBarringResp, 1116
  - voiceGetCallFWResp, 1119
  - voiceGetCallWaitInfo, 1121
  - voiceGetCLIPResp, 1123
  - voiceGetCLIRResp, 1125

- voiceGetCNAPResp, [1126](#)
- voiceGetCOLPResp, [1128](#)
- voiceGetCOLRResp, [1129](#)
- voiceManageCallsReq, [1139](#)
- voiceSetCallBarringPwdResp, [1146](#)
- voiceSetSUPSServiceResp, [1154](#)
- voiceSUPSInfo, [1157](#)
- pCallId
  - USSResp, [1096](#)
  - voiceAnswerCall, [1100](#)
- pCallInfo
  - voiceCallInfoResp, [1104](#)
- pCallPartySubAdd
  - voiceCallRequestParams, [1107](#)
- pCallType
  - voiceCallRequestParams, [1107](#)
- pCallWaitInd
  - voiceInfoRec, [1137](#)
- pCallbackAddr
  - cdmaMsgEncodingParams, [159](#)
- pCallbkAddr
  - cdmaMsgDecodingParams, [156](#)
- pCallbkAddrLength
  - cdmaMsgDecodingParams, [157](#)
- pCalledPartyInfo
  - voiceInfoRec, [1137](#)
- pCallerIDInfo
  - voiceInfoRec, [1137](#)
- pCallerNameInfo
  - voiceInfoRec, [1137](#)
- pCallingPartyInfo
  - voiceInfoRec, [1137](#)
- pCardResult
  - UIMAuthenticateResp, [915](#)
  - UIMGetFileAttributesResp, [921](#)
  - UIMReadTransparentResp, [925](#)
  - unpack\_uim\_ReadTransparent\_t, [1065](#)
- pCardStatus
  - UIMGetCardStatusResp, [918](#)
  - unpack\_uim\_GetCardStatus\_t, [1064](#)
  - unpack\_uim\_SLQSUIMSetStatusChangeCall-Back\_ind\_t, [1068](#)
- pCcResultType
  - USSResp, [1096](#)
- pCellDb
  - LocDelAssDataReq, [389](#)
  - pack\_loc\_Delete\_Assist\_Data\_t, [590](#)
- pChangeDuration
  - nasInitNetworkReq, [538](#)
  - pack\_nas\_SLQSIInitiateNetworkRegistration\_t, [600](#)
- pChannelRate
  - getDUNCallInfoResp, [268](#)
- pChgDuration
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [614](#)
- pCikInfo
  - LocDelAssDataReq, [389](#)
  - pack\_loc\_Delete\_Assist\_Data\_t, [590](#)
- pCodecSTGain
  - GetAudioPathConfigResp, [256](#)
  - SetAudioPathConfigReq, [770](#)
- pColorCode
  - nasGetHDRColorCodeResp, [527](#)
- pConfidence
  - LocSetCradleMountReq, [400](#)
- pConfigAltitudeAssumed
  - LOCStartReq, [402](#)
  - pack\_loc\_Start\_t, [595](#)
- pConfigurationMask
  - UIMGetConfigurationReq, [919](#)
- pConnectNumInfo
  - voiceCallInfoResp, [1104](#)
  - voiceInfoRec, [1137](#)
- pConnectionStatus
  - getDUNCallInfoResp, [268](#)
- pContextId
  - swiPDPRuntimeSettingsResp, [861](#)
- pCrashInfo
  - CrashInfoParams, [183](#)
- pCrashString
  - CrashInfo, [182](#)
- pCreateProfileOut
  - unpack\_wds\_SLQSCreateProfile\_t, [1077](#)
- pCurAMRConfig
  - voiceGetConfigResp, [1134](#)
- pCurDataBearerTechnology
  - dataBearers, [203](#)
- pCurPrefVoiceSO
  - voiceGetConfigResp, [1134](#)
- pCurProfile
  - pack\_wds\_SLQSCreateProfile\_t, [642](#)
- pCurVoiceDomainPref
  - voiceGetConfigResp, [1134](#)
- pCurVoicePrivacyPref
  - voiceGetConfigResp, [1134](#)
- pCurrChannelRateInd
  - wdsSetEventReportReq, [1204](#)
- pCurrDataBearerTechInd
  - wdsSetEventReportReq, [1204](#)
- pCurrImgInfo
  - CurrentImgList, [190](#)
  - unpack\_dms\_SLQSSwiGetFirmwareCurr\_t, [974](#)
- pCurrNetworkInfo
  - CurrDataSysStat, [188](#)
- pCurrPrefDataSysInd
  - wdsSetEventReportReq, [1204](#)
- pCurrTTYMode
  - voiceGetConfigResp, [1134](#)
- pCurrentChannelIRXRate
  - WdsConnectionRateElmnts, [1189](#)
- pCurrentChannelTXRate
  - WdsConnectionRateElmnts, [1189](#)
- pCurrentPersonality
  - HDRPersonalityInd, [303](#)
  - HDRPersonalityResp, [304](#)
- pCurrentPrsnlty

- HDRProtSubtypResp, [305](#)
- pCurrentmitigationLvl
  - TmdGetMitigationLvlResp, [886](#)
- pCustSettingInfo
  - DMSgetCustomFeatureV2, [223](#)
  - getCustomFeatureV2, [262](#)
- pCustSettingList
  - DMSgetCustomFeatureV2, [223](#)
  - getCustomFeatureV2, [262](#)
- pCwtMute
  - SetM2MAudioProfileReq, [782](#)
  - SetM2MAVMuteReq, [784](#)
- pDDTMInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [608](#)
- pDHCPRelayEnabled
  - custFeaturesInfo, [197](#)
  - custFeaturesSetting, [199](#)
- PDOP
  - loc\_precisionDilution, [384](#)
  - precisionDilution\_s, [677](#)
- PDType
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- pDRCPParams
  - GetHRPDStatsResp, [271](#)
- PDS\_SRV
  - qaGobiApiCbK.h, [1304](#)
- PDSInjectTimeReference
  - qaGobiApiPds.h, [1534](#)
- PDSPosMethodStateReq, [661](#)
  - pWifiState, [662](#)
  - pXtraDataState, [662](#)
  - pXtraTimeState, [662](#)
- PDSPositionData, [659](#)
  - pAltitudeWrtEllipsoid, [661](#)
  - pAltitudeWrtSealevel, [661](#)
  - pHorizontalConfidence, [661](#)
  - pHorizontalUncCircular, [661](#)
  - pLatitude, [661](#)
  - pLongitude, [661](#)
  - pPositionSource, [661](#)
  - pTimeStamp, [661](#)
  - pTimeType, [661](#)
  - pVerticalConfidence, [661](#)
  - pVerticalUnc, [661](#)
- pDTMFXTXGain
  - GetAudioPathConfigResp, [256](#)
  - SetAudioPathConfigReq, [770](#)
- pDataBearer
  - QosEventInfo, [730](#)
  - slqsWdsEventInfo, [823](#)
- pDataBearerTech
  - getDUNCallInfoResp, [268](#)
- pDataBearerTechInd
  - wdsSetEventReportReq, [1204](#)
- pDataCallStatusChangeInd
  - wdsSetEventReportReq, [1204](#)
- pDataMode
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pDataRate
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
  - swiQosFlow, [867](#)
- pDataSrc
  - voiceSUPSInfo, [1157](#)
- pDataStatusDetail
  - NetworkDebugResp, [562](#)
- pDataSystemStatusChangeInd
  - wdsSetEventReportReq, [1204](#)
- pDate
  - \_SLQSOMADMSessionInfo, [74](#)
- pDateLength
  - \_SLQSOMADMSessionInfo, [74](#)
- pDayltSavAdj
  - nasNetworkTime, [540](#)
  - unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind-  
\_t, [1015](#)
- pDefaultPDNEnabled
  - \_slqs3GPPConfigItem, [69](#)
- pDeferTime
  - pack\_swima\_SLQSOMADMSelectSelection\_t,  
[627](#)
- pDescription
  - QmiNas3GppNetworkInfo, [720](#)
- pDestAddr
  - cdmaMsgEncodingParams, [159](#)
  - wcdmaMsgEncodingParams, [1166](#)
- pDestSMSContent
  - getDyingGaspCfg, [268](#)
  - pack\_dms\_SLQSSwiSetDyingGaspCfg\_t, [586](#)
  - packgetDyingGaspCfg, [655](#)
  - setDyingGaspCfg, [774](#)
- pDestSMSNum
  - getDyingGaspCfg, [268](#)
  - pack\_dms\_SLQSSwiSetDyingGaspCfg\_t, [586](#)
  - packgetDyingGaspCfg, [655](#)
  - setDyingGaspCfg, [774](#)
- pDetachAction
  - PSDetachReq, [695](#)
- pDevCrashStatus
  - CrashInfoParams, [183](#)
- pDeviceConfigDetail
  - NetworkDebugResp, [562](#)
- pDiagInfo
  - voiceCallInfoResp, [1104](#)
- pDigitBuff
  - burstDTMFInfo, [128](#)
- pDirNum
  - nasGet3GPP2SubscriptionInfoResp, [526](#)
- pDisableIMSI
  - custFeaturesInfo, [197](#)
- pDisplInfo
  - voiceInfoRec, [1137](#)



- pDisplayMode
  - cdmaMsgDecodingParams, 157
- pDomainList
  - qmiWdsRunTimeSettings, 726
- pDormancyStatus
  - getDUNCallInfoResp, 268
  - slqsWdsEventInfo, 823
- pDormancyStatusInd
  - wdsSetEventReportReq, 1204
- pDualStandByPrefInd
  - nasIndicationRegisterReq, 537
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, 608
- pECIOThresList
  - ECIOThresh, 232
- pECIOThresh
  - sigInfo, 797
- pECMode
  - GetAudioPathConfigResp, 256
  - SetAudioPathConfigReq, 770
- pECTNum
  - voiceSUPSNotification, 1160
- PER
  - NetworkStatEVDO, 567
- pESNString
  - serialNumbersInfo, 762
- pEVDOPageMonPerChangeInd
  - wdsSetEventReportReq, 1204
- pEarMute
  - SetM2MAudioProfileReq, 782
- pEmerMode
  - \_sysSelectPrefInfo, 87
  - \_sysSelectPrefParams, 93
  - pack\_nas\_SLQSSetSysSelectionPref\_t, 615
  - unpack\_nas\_SLQSGetSysSelectionPref\_t, 1012
- pEmergencyCategory
  - voiceCallRequestParams, 1107
- pEnableNotification
  - WdsClientLeaseChange, 1187
- pEnabled
  - pack\_wds\_SetMobileIPProfile\_t, 641
- pEncodingAlphabet
  - cdmaMsgEncodingParams, 159
- pEncryptData
  - pack\_uim\_ReadTransparent\_t, 630
  - UIMReadTransparentReq, 924
- pEncryptedData
  - UIMReadTransparentResp, 925
  - unpack\_uim\_ReadTransparent\_t, 1065
- pEncryptedPIN1
  - pack\_uim\_VerifyPin\_t, 636
  - UIMPinResp, 922
  - UIMVerifyPinReq, 938
  - unpack\_uim\_ChangePin\_t, 1063
  - unpack\_uim\_SetPinProtection\_t, 1066
  - unpack\_uim\_UnblockPin\_t, 1068
  - unpack\_uim\_VerifyPin\_t, 1070
- pError
  - USSDNoWaitIndicationInfo, 1094
- pErrorCodeStr
  - imsaRatStatusInfo, 319
- pErrorMask
  - CATEventDataType, 148
- pErrorRateInd
  - nasIndicationRegisterReq, 537
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, 608
- pEspSpi
  - swiQosFilter, 864
- pEtwsMessageInfo
  - SMSEventInfo\_s, 831
- pEtwsPlmnInfo
  - SMSEventInfo\_s, 831
- pExtDispInfo
  - voiceInfoRec, 1137
- pExtDispRecInfo
  - voiceInfoRec, 1137
- pExtErrCode
  - \_GetProfileSettingOut, 57
  - UnPackGetProfileSettingOut, 1089
- pExtErrorCode
  - CreateProfileOut, 184
  - ModifyProfileOut, 431
  - unpack\_wds\_SLQSModifyProfile\_t, 1083
- pFOTAUpdate
  - \_SLQSOMADMSettings, 76
- pFOTAdownload
  - \_SLQSOMADMSettings, 76
- pFailCause
  - voiceGetCallBarringResp, 1116
  - voiceGetCallFWResp, 1120
  - voiceGetCallWaitInfo, 1121
  - voiceGetCLIPResp, 1124
  - voiceGetCLIRResp, 1125
  - voiceGetCNAPResp, 1127
  - voiceGetCOLPResp, 1128
  - voiceGetCOLRResp, 1130
  - voiceManageCallsResp, 1139
  - voiceSetCallBarringPwdResp, 1146
  - voiceSetSUPSServiceResp, 1154
  - voiceSUPSInfo, 1157
- pFailErrorCode
  - imsaPdpStatusInfo, 318
- pFailureCause
  - USSDNoWaitIndicationInfo, 1094
- pFailureReason
  - unpack\_wds\_SLQSStartDataSession\_t, 1087
- pFile
  - ERIFileparams, 234
- pFileAttributes
  - UIMGetFileAttributesResp, 921
- pFileSize
  - ERIFileparams, 234
- pFixId
  - QmiCbkLocPositionReportInd, 712
  - unpack\_loc\_PositionRpt\_Ind\_t, 986
- pFlag
  - RXPCMIIRFltr, 753

- TXPCMIIRFiltr, [897](#)
- pFlashPayLd
  - voiceFlashInfo, [1111](#)
- pFlashType
  - voiceFlashInfo, [1111](#)
- pFollowOnDC
  - slqssendasyncsmsparams\_s, [810](#)
- pForbidden
  - QmiNas3GppNetworkInfo, [720](#)
- pForceOnDC
  - slqssendasyncsmsparams\_s, [810](#)
- pFwAutoCheck
  - \_SLQSOMADMSettings, [76](#)
  - \_SLQSOMADMSettingsReqParams3, [78](#)
  - pack\_swioama\_SLQSOMADMSetSettings\_t, [628](#)
- pGCDumpString
  - CrashInfo, [182](#)
- pGERANInfo
  - nasCellLocationInfoResp, [524](#)
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1013](#)
- pGPRSGrantedQoS
  - qmiWdsRunTimeSettings, [726](#)
- pGPRSMInumQoS
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pGPRSRequestedQoS
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pGPSEnable
  - custFeaturesSetting, [199](#)
- pGPSLPM
  - custFeaturesInfo, [197](#)
  - custFeaturesSetting, [199](#)
- pGPSSel
  - custFeaturesInfo, [197](#)
  - custFeaturesSetting, [199](#)
- pGSMBER
  - GetErrRateResp, [270](#)
- pGSMCallBarringSysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pGSMCipherDomainSysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pGSMRSSIDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [604](#)
  - setSignalStrengthInfo, [792](#)
- pGSMRSSIThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [604](#)
  - setSignalStrengthInfo, [792](#)
- pGSMRSSIThreshList
  - GSMRSSIThresh, [296](#)
  - nas\_GSMRSSIThresh, [458](#)
- pGSMSSInfo
  - nasGetSigInfoResp, [529](#)
- pGSMSigInfo
  - nasSigInfo, [553](#)
  - unpack\_nas\_SLQSNasSigInfoCallback\_t, [1017](#)
- pGSMSSrvStatusInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pGSMSSysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1008](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pGWAacqOrderPref
  - \_sysSelectPrefInfo, [87](#)
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [615](#)
  - unpack\_nas\_SLQSGetSysSelectionPref\_t, [1012](#)
- pGWAddressV4
  - qmiWdsRunTimeSettings, [726](#)
- pGenerator
  - GetM2MAudioProfileReq, [276](#)
  - SetM2MAudioProfileReq, [782](#)
- pGetCallFWExtInfo
  - voiceGetCallFWResp, [1120](#)
- pGetCallFWInfo
  - voiceGetCallFWResp, [1120](#)
- pGetCustomInput
  - DMSgetCustomFeatureV2, [223](#)
  - getCustomFeatureV2, [263](#)
- pGetDyingGaspCfg
  - unpack\_dms\_SLQSSwiGetDyingGaspCfg\_t, [973](#)
- pGetDyingGaspStatistics
  - unpack\_dms\_SLQSSwiGetDyingGaspStatistics\_t, [973](#)
- pGnssData
  - LocDelAssDataReq, [389](#)
  - pack\_loc\_Delete\_Assist\_Data\_t, [590](#)
- pGpsTime
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pGyroAcceptReady
  - QmiCbkLocSensorStreamingInd, [714](#)
- pGyroData
  - LocInjectSensorDataReq, [399](#)
- pGyroSamplesAccepted
  - QmiCbkLocInjectSensorDataInd, [705](#)
- pGyroTempAcceptReady
  - QmiCbkLocSensorStreamingInd, [714](#)
- pGyroTempData
  - LocInjectSensorDataReq, [399](#)
- pGyroTempSamplesAccepted
  - QmiCbkLocInjectSensorDataInd, [706](#)
- pGyroTimeSrc



- LocInjectSensorDataReq, [399](#)
- pHASPI
  - pack\_wds\_SetMobileIPProfile\_t, [641](#)
- pHDRECIODelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [604](#)
  - setSignalStrengthInfo, [792](#)
- pHDRECIOThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [604](#)
  - setSignalStrengthInfo, [792](#)
- pHDRECIOThreshList
  - HDRECIOThresh, [303](#)
  - nas\_HDRECIOThresh, [463](#)
- pHDRIODelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [604](#)
  - setSignalStrengthInfo, [792](#)
- pHDRIOTThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pHDRIOTThreshList
  - HDRIOTThresh, [303](#)
  - nas\_HDRIOTThresh, [463](#)
- pHDRNewUATIAssInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [608](#)
- pHDRPackErrRate
  - GetErrRateResp, [270](#)
- pHRRSSIDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pHRRSSIThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pHRRSSIThreshList
  - HDRSSIThresh, [305](#)
  - nas\_HDRSSIThresh, [464](#)
- pHRSINRDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pHRSINRThresList
  - HDRSINRThresh, [306](#)
- pHRSINRThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
  - sigInfo, [797](#)
- pHRSINRThreshList
  - HDRSINRThreshold, [307](#)
  - nas\_HDRSINRThreshold, [465](#)
- pHRRSSInfo
  - nasGetSigInfoResp, [529](#)
- pHDRSessionCloseInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [608](#)
- pHDRSigInfo
  - nasSigInfo, [554](#)
  - unpack\_nas\_SLQSNasSigInfoCallback\_t, [1017](#)
- pHDRSrvStatusInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
- unpack\_nas\_SLQSGetSysInfo\_t, [1009](#)
- unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pHDRSysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1009](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pHaltSubscription
  - UIMGetConfigurationResp, [920](#)
- pHeading
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pHeadingUnc
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pHomeSIDNID
  - nasGet3GPP2SubscriptionInfoResp, [526](#)
- pHorConfidence
  - LocInjectPositionReq, [397](#)
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pHorReliability
  - LocInjectPositionReq, [397](#)
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pHorUncCircular
  - LocInjectPositionReq, [397](#)
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pHorUncEllipseOrientAzimuth
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pHorUncEllipseSemiMajor
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pHorUncEllipseSemiMinor
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pHorizontalAccuracyLvl
  - LOCStartReq, [402](#)
  - pack\_loc\_Start\_t, [595](#)
- pHorizontalConfidence
  - PDSPositionData, [661](#)
- pHorizontalUncCircular
  - PDSPositionData, [661](#)
- pHotSwapStatus
  - UIMGetCardStatusResp, [918](#)
  - unpack\_uim\_GetCardStatus\_t, [1064](#)
- pHwConfig
  - unpack\_wds\_SLQSSGetDHCPv4ClientConfig\_t, [1087](#)
  - WdsDHCPv4Config, [1190](#)
- PI
  - calledPartyInfo, [132](#)
  - callerIDInfo, [134](#)
  - callFWExtInfo, [137](#)
  - callingPartyInfo, [142](#)
  - redirNumInfo, [736](#)

- PIFACEId
  - SetM2MAudioAVCFGReq, [781](#)
- plMCNflag
  - qmiWdsRunTimeSettings, [726](#)
- plMEIString
  - serialNumbersInfo, [762](#)
- plMSDomain
  - GetIMSUserConfigParams, [273](#)
  - imsUserConfigInfo, [331](#)
  - SetIMSUserConfigReq, [776](#)
- plMSDomainLen
  - GetIMSUserConfigParams, [273](#)
  - SetIMSUserConfigReq, [776](#)
- plMSTestMode
  - GetRegMgrConfigParams, [283](#)
  - imsRegMgrConfigInfo, [329](#)
  - SetRegMgrConfigReq, [787](#)
- plOThresList
  - IOThresh, [337](#)
- plOThresh
  - sigInfo, [797](#)
- plIPv4AddressV4
  - QmiWdsIpAddressInfo, [723](#)
  - qmiWdsRunTimeSettings, [726](#)
- plIPv4AddressV6
  - QmiWdsIpAddressInfo, [723](#)
- plPFamSupport
  - custFeaturesInfo, [197](#)
- plPFfamily
  - GetInstIDResp, [275](#)
- plPFfamilyPreference
  - qmiWdsRunTimeSettings, [726](#)
- plIPv6AddrInfo
  - qmiWdsRunTimeSettings, [726](#)
- plIPv6GWAddrInfo
  - qmiWdsRunTimeSettings, [727](#)
- plIPv4Addr
  - WdsDHCPv4ClientLeaseInd, [1190](#)
- plIPv4AddrPref
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- plIPv4Address
  - swiPDPRuntimeSettingsResp, [861](#)
- plIPv4DstAddr
  - swiQosFilter, [864](#)
- plIPv4GWAddress
  - swiPDPRuntimeSettingsResp, [861](#)
- plIPv4SrcAddr
  - swiQosFilter, [864](#)
- plIPv6AddPref
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- plIPv6Address
  - swiPDPRuntimeSettingsResp, [861](#)
- plIPv6DstAddr
  - swiQosFilter, [864](#)
- plIPv6GWAddress
  - swiPDPRuntimeSettingsResp, [862](#)
- plIPv6Label
  - swiQosFilter, [864](#)
- plIPv6SrcAddr
  - swiQosFilter, [864](#)
- plIPv6TrafCls
  - swiQosFilter, [864](#)
- plIPv6prefixlen
  - QmiWdsIpAddressInfo, [723](#)
- plId
  - swiQosFilter, [864](#)
- plds
  - swiQosIds, [869](#)
- plIgnoreHotSwapSwitch
  - UIMPowerUpReq, [924](#)
- plmCnFlag
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- plImageList
  - pack\_fms\_SetImagesPreference\_t, [589](#)
  - unpack\_fms\_GetImagesPreference\_t, [977](#)
- plmeiSvnString
  - serialNumbersInfo, [762](#)
- plmgType
  - FirmwareUpdatStat, [244](#)
- plmsRegErrCode
  - IMSARegistrationStatus, [320](#)
- plmsRegStatus
  - IMSARegistrationStatus, [320](#)
  - imsaRegStatusInfo, [321](#)
- plnUse
  - QmiNas3GppNetworkInfo, [720](#)
- plIndFieldsList
  - IMSASupportedFieldsResp, [324](#)
- plIndicationToken
  - pack\_uim\_ChangePin\_t, [629](#)
  - pack\_uim\_ReadTransparent\_t, [630](#)
  - pack\_uim\_SetPinProtection\_t, [631](#)
  - pack\_uim\_UnblockPin\_t, [634](#)
  - pack\_uim\_VerifyPin\_t, [636](#)
  - UIMAuthenticateReq, [914](#)
  - UIMAuthenticateResp, [915](#)
  - UIMChangePinReq, [916](#)
  - UIMGetFileAttributesReq, [920](#)
  - UIMGetFileAttributesResp, [921](#)
  - UIMPinResp, [922](#)
  - UIMReadTransparentReq, [924](#)
  - UIMReadTransparentResp, [925](#)
  - UIMSetPinProtectionReq, [932](#)
  - UIMUnblockPinReq, [937](#)
  - UIMVerifyPinReq, [938](#)
  - unpack\_uim\_ChangePin\_t, [1063](#)
  - unpack\_uim\_ReadTransparent\_t, [1065](#)
  - unpack\_uim\_SetPinProtection\_t, [1066](#)
  - unpack\_uim\_UnblockPin\_t, [1068](#)
  - unpack\_uim\_VerifyPin\_t, [1070](#)

- pInstanceId
  - GetInstIDResp, [275](#)
- pInstanceSize
  - QmiNasPerformNetworkScanResp, [721](#)
- pInstances
  - QmiNasPerformNetworkScanResp, [721](#)
- pInstancesSize
  - QmiNasGetRFBandInfoResp, [721](#)
- pIntermediateReportState
  - LOCStartReq, [402](#)
  - pack\_loc\_Start\_t, [595](#)
- plpcpAckTimeout
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- plpcpCreqRetryCount
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- plsPcscfAddressNedded
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- plsUDHPresent
  - wcdmaLongMsgDecodingParams, [1164](#)
- plsVoiceEnabled
  - custFeaturesInfo, [197](#)
  - custFeaturesSetting, [199](#)
- pJitter
  - swiQosFlow, [868](#)
- pKeyReferenceID
  - pack\_uim\_ChangePin\_t, [629](#)
  - pack\_uim\_SetPinProtection\_t, [632](#)
  - pack\_uim\_UnblockPin\_t, [634](#)
  - pack\_uim\_VerifyPin\_t, [636](#)
  - UIMChangePinReq, [916](#)
  - UIMSetPinProtectionReq, [932](#)
  - UIMUnblockPinReq, [937](#)
  - UIMVerifyPinReq, [938](#)
- PLMN\_LENGTH
  - qaGobiApiNas.h, [1482](#)
- PLMNData
  - operatorPLMNList, [582](#)
- PLMNName
  - operatorNameString, [580](#)
- PLMNNetName
  - PLMNNetworkName, [673](#)
- PLMNNetworkName, [673](#)
  - numInstance, [673](#)
  - PLMNNetName, [673](#)
- PLMNNetworkNameData, [673](#)
  - codingScheme, [675](#)
  - countryInitials, [675](#)
  - longName, [675](#)
  - longNameLen, [675](#)
  - longNameSpareBits, [675](#)
  - shortName, [675](#)
  - shortNameLen, [675](#)
  - shortNameSpareBits, [675](#)
- PLMNRecID
  - OperatorPLMNData, [581](#)
- pLTEAttachProfile
  - \_slqs3GPPConfigItem, [69](#)
- pLTEAttachProfileList
  - \_slqs3GPPConfigItem, [69](#)
- pLTEBandPref
  - \_sysSelectPrefInfo, [87](#)
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [615](#)
  - unpack\_nas\_SLQSGetSysSelectionPref\_t, [1012](#)
- pLTECphyCa
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [609](#)
- pLTEInfo
  - swiModemStatusResp, [857](#)
  - unpack\_nas\_SLQSNasSwiModemStatus\_t, [1017](#)
- pLTEInfoInterfreq
  - nasCellLocationInfoResp, [524](#)
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1013](#)
- pLTEInfoIntrafreq
  - nasCellLocationInfoResp, [524](#)
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1013](#)
- pLTEInfoNeighboringGSM
  - nasCellLocationInfoResp, [524](#)
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1013](#)
- pLTEInfoNeighboringWCDMA
  - nasCellLocationInfoResp, [524](#)
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1013](#)
- pLTERSRPDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pLTERSRPThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pLTERSRPThreshList
  - LTERSRPThresh, [415](#)
  - nas\_LTERSRPThresh, [478](#)
- pLTERSRQDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pLTERSRQThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pLTERSRQThreshList
  - LTERSRQThresh, [416](#)
  - nas\_LTERSRQThresh, [479](#)
- pLTERSSIDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pLTERSSIThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)

- pLTERSSIThreshList
  - LTERSSIThresh, [416](#)
  - nas\_LTERSSIThresh, [479](#)
- pLTESNRDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pLTESNRThreshList
  - LTERSNRThresh, [420](#)
- pLTESNRThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
  - sigInfo, [797](#)
- pLTESNRThreshList
  - LTERSNRThreshold, [421](#)
  - nas\_LTERSNRThreshold, [482](#)
- pLTISSInfo
  - nasGetSigInfoResp, [529](#)
- pLTESigInfo
  - nasSigInfo, [554](#)
  - unpack\_nas\_SLQSNasSigInfoCallback\_t, [1017](#)
- pLTESigRptCfg
  - sigInfo, [797](#)
- pLTESigRptConfig
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pLTESrvStatusInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSSysInfo\_t, [1009](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pLTESysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSSysInfo\_t, [1009](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pLTEVoiceSupportSysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSSysInfo\_t, [1009](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pLanguage
  - cdmaMsgDecodingParams, [157](#)
- pLastBearerTech
  - DataBearerTechExt, [205](#)
- pLastCallDataBearerTech
  - getDUNCallInfoResp, [268](#)
- pLastCallDataBearerTechnology
  - dataBearers, [203](#)
- pLastCallRXOKBytesCnt
  - getDUNCallInfoResp, [268](#)
- pLastCallTXOKBytesCnt
  - getDUNCallInfoResp, [268](#)
- pLatency
  - swiQosFlow, [868](#)
- pLatitude
  - LocInjectPositionReq, [397](#)
  - PDSPositionData, [661](#)
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pLcpAckTimeout
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pLcpCreqRetryCount
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pLeapSeconds
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pLeaseState
  - WdsDHCPv4ClientLeaseInd, [1190](#)
- pLineCtrlInfo
  - voiceInfoRec, [1137](#)
- pLinktimer
  - pack\_sms\_SendSMS\_t, [618](#)
  - slqssendasyncsmsparams\_s, [811](#)
  - slqssendsmsparams\_s, [812](#)
- pLogString
  - FirmwareUpdatStat, [244](#)
- pLogStringLength
  - FirmwareUpdatStat, [244](#)
- pLongitude
  - LocInjectPositionReq, [397](#)
  - PDSPositionData, [661](#)
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pLoopbackMode
  - WDSSetLoopbackData, [1206](#)
- pLoopbackMultiplier
  - WDSSetLoopbackData, [1206](#)
- pLteBandCapability
  - BandCapabilityResp, [125](#)
- pLteEARFCN
  - nasSwiGetChannelLockResp, [554](#)
  - nasSwiSetChannelLockReq, [556](#)
- pLteNasRelInfo
  - SwiOTAMsg\_s, [858](#)
- pLtePCI
  - nasSwiGetChannelLockResp, [554](#)
  - nasSwiSetChannelLockReq, [556](#)
- pLteQci
  - swiQosFlow, [868](#)
- pMCC
  - QmiNas3GppNetworkInfo, [720](#)
- pMEIDString
  - serialNumbersInfo, [762](#)
- pMICGainSelect
  - GetAudioPathConfigResp, [256](#)
- pMIPStatusInd
  - wdsSetEventReportReq, [1204](#)
- pMNAAB
  - pack\_wds\_SetMobileIPProfile\_t, [641](#)
- pMNC
  - QmiNas3GppNetworkInfo, [720](#)
- pMNCLncPCSDigStat

- [\\_sysSelectPrefParams](#), 93
  - [pack\\_nas\\_SLQSSetSysSelectionPref\\_t](#), 615
- pMNHA
  - [pack\\_wds\\_SetMobileIPProfile\\_t](#), 642
- pMNRInfo
  - [nasInitNetworkReg](#), 538
  - [pack\\_nas\\_SLQSInitiateNetworkRegistration\\_t](#), 600
- pMTMessageInfo
  - [SMSEventInfo\\_s](#), 831
- pMagneticDeviation
  - [QmiCbkLocPositionReportInd](#), 712
  - [unpack\\_loc\\_PositionRpt\\_Ind\\_t](#), 986
- pManString
  - [\\_SLQSSwiGetHostDevInfoParams](#), 80
  - [\\_SLQSSwiSetHostDevInfoParams](#), 82
- pManagedRoamingInd
  - [nasIndicationRegisterReq](#), 537
  - [pack\\_nas\\_SLQSNasIndicationRegisterExt\\_t](#), 609
- pMaxAllowedPktSz
  - [swiQosFlow](#), 868
- pMaxChannelRXRate
  - [WdsConnectionRateElmnts](#), 1189
- pMaxChannelTXRate
  - [WdsConnectionRateElmnts](#), 1189
- pMdmCallDurationActive
  - [getDUNCallInfoResp](#), 268
- pMeidString
  - [\\_SLQSSwiGetSerialNoExtParams](#), 81
- pMessage
  - [cdmaMsgDecodingParams](#), 157
  - [cdmaMsgEncodingParams](#), 159
  - [pack\\_sms\\_SendSMS\\_t](#), 618
  - [slqssendasyncsmsparams\\_s](#), 811
  - [slqssendsmsparams\\_s](#), 812
  - [wcdmaLongMsgDecodingParams](#), 1164
  - [wcdmaMsgDecodingParams](#), 1165
- pMessageID
  - [cdmaMsgDecodingParams](#), 157
- pMessageIndex
  - [pack\\_sms\\_SLQSDDeleteSMS\\_t](#), 620
- pMessageMode
  - [pack\\_sms\\_SLQSDDeleteSMS\\_t](#), 620
  - [pack\\_sms\\_SLQSGetSMS\\_t](#), 621
  - [pack\\_sms\\_SLQSGetSMSList\\_t](#), 622
  - [pack\\_sms\\_SLQSMModifySMSStatus\\_t](#), 623
  - [smsMaxStorageSizeReq](#), 832
- pMessageModelInfo
  - [SMSEventInfo\\_s](#), 831
- pMessageSize
  - [cdmaMsgEncodingParams](#), 159
- pMessageTag
  - [pack\\_sms\\_SLQSDDeleteSMS\\_t](#), 620
- pMicMute
  - [SetM2MAudioProfileReq](#), 782
- pMinBasedIMSI
  - [nasGet3GPP2SubscriptionInfoResp](#), 526
- pMinIntervalTime
  - [LOCStartReq](#), 402
- [pack\\_loc\\_Start\\_t](#), 595
- pMinPolicedPktSz
  - [swiQosFlow](#), 868
- pMinSessionExpiryTimer
  - [GetIMSVoIPConfigResp](#), 275
  - [imsVoIPConfigInfo](#), 334
  - [SetIMSVoIPConfigReq](#), 779
- pMitigationDevList
  - [TmdGetMitigationDevListResp](#), 884
- pMitigationDevListLen
  - [TmdGetMitigationDevListResp](#), 884
- pMncPcsDigitStatus
  - [nasInitNetworkReg](#), 538
  - [pack\\_nas\\_SLQSInitiateNetworkRegistration\\_t](#), 600
- pMncPcsStatus
  - [nasPLMNNameReq](#), 547
  - [pack\\_nas\\_SLQSGetPLMNName\\_t](#), 599
- pModePref
  - [\\_sysSelectPrefInfo](#), 87
  - [\\_sysSelectPrefParams](#), 93
  - [pack\\_nas\\_SLQSSetSysSelectionPref\\_t](#), 615
  - [unpack\\_nas\\_SLQSGetSysSelectionPref\\_t](#), 1012
- pModelString
  - [\\_SLQSSwiGetHostDevInfoParams](#), 80
  - [\\_SLQSSwiSetHostDevInfoParams](#), 82
- pMtu
  - [qmiWdsRunTimeSettings](#), 727
- pNAI
  - [pack\\_wds\\_SetMobileIPProfile\\_t](#), 642
- pNAMNameInfo
  - [nasGet3GPP2SubscriptionInfoResp](#), 526
- pNITZInformation
  - [nasOperatorNameResp](#), 541
- pNSEnable
  - [GetAudioPathConfigResp](#), 256
  - [SetAudioPathConfigReq](#), 770
- pNSSAudioCtrl
  - [voiceInfoRec](#), 1137
- pNSSRelease
  - [voiceInfoRec](#), 1137
- pNamID
  - [voiceGetConfigReq](#), 1131
- pName
  - [pack\\_wds\\_SetDefaultProfile\\_t](#), 640
- pNameString
  - [\\_SLQSSwiGetOSInfoParams](#), 80
  - [\\_SLQSSwiSetOSInfoParams](#), 83
- pNegoDnsSrvrPref
  - [LibpackProfile3GPP2](#), 355
  - [LibPackprofile\\_3GPP2](#), 368
  - [Profile3GPP2](#), 692
- pNeighborSetPilotPN
  - [NetworkStat1x](#), 565
- pNetSelPref
  - [\\_sysSelectPrefInfo](#), 87
  - [\\_sysSelectPrefParams](#), 93
  - [pack\\_nas\\_SLQSSetSysSelectionPref\\_t](#), 615
  - [unpack\\_nas\\_SLQSGetSysSelectionPref\\_t](#), 1012

- pNetworkInfo
  - \_slqsNetworkScanInfo, [71](#)
- pNetworkInfoInstances
  - \_slqsNetworkScanInfo, [71](#)
- pNetworkInfoLen
  - CurrDataSysStat, [188](#)
- pNetworkStat1x
  - NetworkDebugResp, [562](#)
- pNetworkStatEVDO
  - NetworkDebugResp, [562](#)
- pNetworkTimeInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [609](#)
- pNewImsRegStatus
  - IMSARegistrationStatus, [320](#)
- pNewPwdData
  - voiceSUPSInfo, [1158](#)
- pNumSupUSBComps
  - USBCompParams, [1093](#)
- pNumberOfPhySlot
  - UIMGetSlotsStatusResp, [922](#)
  - unpack\_uim\_SLQSUIMGetSlotsStatus\_t, [1067](#)
- pNxtHdrProto
  - swiQosFilter, [864](#)
- pOMADMEEnabled
  - \_SLQSOMADMS settings, [76](#)
- PORTNAM\_LEN
  - qaGobiApiDcs.h, [1391](#)
- pOTASPStatus
  - voiceCallInfoResp, [1105](#)
  - voiceGetAllCallInfo, [1114](#)
- pObjectVer
  - NetworkDebugResp, [562](#)
- pOffLength
  - voiceDTMFEventInfo, [1110](#)
- pOnLength
  - voiceDTMFEventInfo, [1110](#)
- pOpaqueIdentifier
  - LocInjectSensorDataReq, [399](#)
  - QmiCbkLocInjectSensorDataInd, [706](#)
- pOperatorNameString
  - nasOperatorNameResp, [541](#)
- pOperatorPLMNList
  - nasOperatorNameResp, [541](#)
- pOptList
  - WdsDHCPv4ClientLeaseInd, [1190](#)
  - WdsDHCPv4OptionList, [1194](#)
  - wdsDhcpv4OptionList, [1193](#)
- pOptVal
  - DHCPOption, [217](#)
- pOptions
  - DHCPOptionList, [218](#)
- pPCMPParams
  - SetM2MAudioAVCFGReq, [781](#)
- pPCSCFAddrPCO
  - qmiWdsRunTimeSettings, [727](#)
- pPCSCFFQDNAddrList
  - qmiWdsRunTimeSettings, [727](#)
- pPCSCFPort
  - GetRegMgrConfigParams, [283](#)
- pPCSDigitInfo
  - \_slqsNetworkScanInfo, [71](#)
- pPCSDigitInstances
  - \_slqsNetworkScanInfo, [71](#)
- pPCSInstance
  - unpack\_nas\_PerformNetworkScan\_t, [996](#)
- pPCSInstanceSize
  - unpack\_nas\_PerformNetworkScan\_t, [997](#)
- pPDNInactivTimeout
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pPDNInactivTimeout3GPP2
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pPDType
  - qmiWdsRunTimeSettings, [727](#)
- pPDType
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pPDUMessage
  - wcdmaMsgEncodingParams, [1166](#)
- pPLMNNetworkName
  - nasOperatorNameResp, [541](#)
- pPRLPref
  - \_sysSelectPrefInfo, [87](#)
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [615](#)
  - unpack\_nas\_SLQSGetSysSelectionPref\_t, [1012](#)
- pPRLPreference
  - dmsCurrentPRLInfo, [221](#)
- pPRLVersion
  - dmsCurrentPRLInfo, [221](#)
- pPacketsCountRX
  - QosEventInfo, [730](#)
  - slqsWdsEventInfo, [823](#)
- pPacketsCountTX
  - QosEventInfo, [730](#)
  - slqsWdsEventInfo, [823](#)
- pPartNum
  - wcdmaLongMsgDecodingParams, [1164](#)
- pPass
  - pack\_wds\_SLQSStartDataSession\_t, [653](#)
- pPassword
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
  - Profile3GPP, [685](#)
  - ssdatasession\_params, [847](#)
- pPasswordSize
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pPscfAddrUsingDhcp



- LibpackProfile3GPP, [348](#)
- LibPackprofile\_3GPP, [361](#)
- Profile3GPP, [685](#)
- pPcscfAddrUsingPCO
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pPdnType
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pPdpAccessConFlag
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pPdpContext
  - LibpackProfile3GPP, [348](#)
  - LibPackprofile\_3GPP, [361](#)
  - Profile3GPP, [685](#)
- pPdpDataCompType
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pPdpHdrCompType
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pPdpStatusConfig
  - IMSAIndRegisterInfo, [317](#)
- pPersonalityListLength
  - HDRPersonalityInd, [303](#)
  - HDRPersonalityResp, [304](#)
  - HDRProtSubtypResp, [305](#)
- pPersonalizationStatus
  - UIMGetConfigurationResp, [920](#)
- pPhoneCtxtURI
  - GetIMSSMSConfigParams, [272](#)
  - imsSMSConfigInfo, [331](#)
  - SetIMSSMSConfigReq, [775](#)
- pPhoneCtxtURILen
  - GetIMSSMSConfigParams, [272](#)
  - SetIMSSMSConfigReq, [775](#)
- pPhyCaAggPcellInfo
  - nasGetLTECphyCaResp, [528](#)
- pPhyCaAggScellIDBw
  - nasGetLTECphyCaResp, [528](#)
- pPhyCaAggScellIndType
  - nasGetLTECphyCaResp, [528](#)
- pPhyCaAggScellIndex
  - nasGetLTECphyCaResp, [528](#)
- pPhyCaAggScellInfo
  - nasGetLTECphyCaResp, [528](#)
- pPilotSetData
  - GetHRPDStatsResp, [271](#)
- pPilotSetInfo
  - PilotSetData, [672](#)
- pPkgDescLength
  - \_SLQSOMADMSessionInfo, [74](#)
- pPkgDescription
  - \_SLQSOMADMSessionInfo, [74](#)
- pPkgName
  - \_SLQSOMADMSessionInfo, [74](#)
- pPkgNameLength
  - \_SLQSOMADMSessionInfo, [74](#)
- pPktErrRate
  - swiQosFlow, [868](#)
- pPlasmaIDString
  - \_SLQSSwiGetHostDevInfoParams, [80](#)
  - \_SLQSSwiSetHostDevInfoParams, [82](#)
- pPositionSource
  - PDSPositionData, [661](#)
- pPositionSrc
  - LocInjectPositionReq, [397](#)
- pPppSessCloseTimer1x
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pPppSessCloseTimerDO
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pPrDNSIPv4Address
  - swiPDPRuntimeSettingsResp, [862](#)
- pPrDNSIPv6Address
  - swiPDPRuntimeSettingsResp, [862](#)
- pPrPCSCFIPv4Address
  - swiPDPRuntimeSettingsResp, [862](#)
- pPrPCSCFIPv6Address
  - swiPDPRuntimeSettingsResp, [862](#)
- pPrecedence
  - swiQosFilter, [864](#)
- pPrecisionDilution
  - QmiCbkLocPositionReportInd, [712](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [986](#)
- pPrefNetwork
  - CurrDataSysStat, [188](#)
- pPrefVoiceDomain
  - voiceSetConfigReq, [1148](#)
- pPrefVoicePrivacy
  - voiceGetConfigReq, [1131](#)
- pPrefVoiceSO
  - voiceGetConfigReq, [1131](#)
  - voiceSetConfigReq, [1148](#)
- pPrefVoiceSOStatus
  - voiceSetConfigResp, [1150](#)
- pPreferred
  - QmiNas3GppNetworkInfo, [721](#)
- pPriCSCFPort
  - imsRegMgrConfigInfo, [329](#)
  - SetRegMgrConfigReq, [787](#)
- pPriCSCFPortName
  - GetRegMgrConfigParams, [283](#)
- pPriCSCFPortNameLen
  - GetRegMgrConfigParams, [283](#)
- pPriDNSIPv4AddPref
  - LibpackProfile3GPP, [349](#)

- LibPackprofile\_3GPP, 362
- Profile3GPP, 686
- pPriDNSIPv6addpref
  - LibpackProfile3GPP, 349
  - LibPackprofile\_3GPP, 362
  - Profile3GPP, 686
- pPriV6DnsAddress
  - LibpackProfile3GPP2, 355
  - LibPackprofile\_3GPP2, 368
  - Profile3GPP2, 692
- pPrimaryDNSV4
  - qmiWdsRunTimeSettings, 727
- pPrimaryDNSV6
  - qmiWdsRunTimeSettings, 727
- pPrimaryHA
  - pack\_wds\_SetMobileIPProfile\_t, 642
- pPrimaryID
  - LibpackProfile3GPP, 349
  - LibPackprofile\_3GPP, 362
  - Profile3GPP, 686
- pPrimaryV4DnsAddress
  - LibpackProfile3GPP2, 355
  - LibPackprofile\_3GPP2, 368
  - Profile3GPP2, 692
- pPriority
  - cdmaMsgDecodingParams, 157
  - cdmaMsgEncodingParams, 159
- pPrivacy
  - cdmaMsgDecodingParams, 157
- pProfSz
  - NWProfile, 572
- pProfValues
  - NWProfile, 572
- pProfileID
  - CreateProfileIn, 183
  - ModifyProfileIn, 431
  - qmiWdsRunTimeSettings, 727
  - unpack\_wds\_SLQSCreateProfile\_t, 1077
- pProfileId
  - pack\_wds\_SLQSCreateProfile\_t, 642
  - pack\_wds\_SLQSModifyProfile\_t, 648
  - pack\_wds\_SLQSSetDHCPv4ClientConfig\_t, 652
  - WdsDHCPv4ClientLeaseInd, 1190
  - WdsDHCPv4Config, 1190
- pProfileId3GPP
  - ssdatasession\_params, 847
- pProfileId3GPP2
  - ssdatasession\_params, 847
  - swiQosFlow, 868
- pProfileIndex
  - CreateProfileOut, 184
- pProfileList
  - \_slqs3GPPConfigItem, 69
- pProfileName
  - qmiWdsRunTimeSettings, 727
- pProfileSettings
  - unpack\_wds\_SLQSGetProfileSettings\_t, 1081
- pProfileType
  - CreateProfileIn, 184
  - CreateProfileOut, 184
  - ModifyProfileIn, 431
  - pack\_wds\_SLQSCreateProfile\_t, 643
  - pack\_wds\_SLQSModifyProfile\_t, 648
- pProfilename
  - LibpackProfile3GPP, 349
  - LibPackprofile\_3GPP, 362
  - Profile3GPP, 686
- pProfilenameSize
  - LibpackProfile3GPP, 349
  - LibPackprofile\_3GPP, 362
  - Profile3GPP, 686
- pProtoSubTypElmnt
  - HDRProtSubtypResp, 305
- pProtocolSubtypeElement
  - HDRPersonalityInd, 303
  - HDRPersonalityResp, 304
- pQFlowState
  - QosFlowInfo, 731
- pQmiInterfaceInfo
  - \_packetSrvStatus, 64
  - slqsSessionStateInfo, 813
  - slqsWdsEventInfo, 823
- pQosClassID
  - LibpackProfile3GPP, 349
  - LibPackprofile\_3GPP, 362
  - Profile3GPP, 686
- pRAT
  - \_sysSelectPrefParams, 93
  - pack\_nas\_SLQSSetSysSelectionPref\_t, 615
- pRATInstance
  - unpack\_nas\_PerformNetworkScan\_t, 997
- pRATInfo
  - \_slqsNetworkScanInfo, 71
- pRATInstanceSize
  - unpack\_nas\_PerformNetworkScan\_t, 997
- pRATInstances
  - \_slqsNetworkScanInfo, 71
- pRATStatus
  - imsaRatStatusInfo, 319
- pRATType
  - LibpackProfile3GPP2, 355
  - LibPackprofile\_3GPP2, 368
  - Profile3GPP2, 692
- PREFERRED\_INDEX
  - qaNasPerformNetworkScan.h, 1733
- pRFBandInfoElements
  - QmiNasGetRFBandInfoResp, 721
- PRI\_UPDATE\_FAIL
  - qaGobiApiFms.h, 1449
- PRIString
  - unpack\_dms\_GetFirmwareRevision\_t, 959
  - unpack\_dms\_GetFirmwareRevisions\_t, 959
- PRLInd
  - qaQmiServingSystemParam, 701
  - unpack\_nas\_SLQSGetServingSystem\_t, 1004
- PRLPTiv



- NASQmiCbkNasSystemSelPrefInd, 550
- PRLPref
  - NASPRPreferenceTlv, 549
- pRMAutoConnect
  - custFeaturesInfo, 197
- pRSRPThresList
  - RSRPThresh, 746
- pRSRPThresh
  - sigInfo, 797
- pRSRQThresList
  - RSRQThresh, 747
- pRSRQThresh
  - sigInfo, 797
- pRSSIThresList
  - RSSIThresh, 748
- pRSSIThresh
  - sigInfo, 797
- pRTPRTCPInactTimer
  - GetIMSVoIPConfigResp, 275
  - imsVoIPConfigInfo, 334
  - SetIMSVoIPConfigReq, 779
- pRXAGCList
  - GetAudioPathConfigResp, 257
  - SetAudioPathConfigReq, 770
- pRXAIG
  - RXAGCList, 749
- pRXAVCAGCSwitch
  - GetAudioPathConfigResp, 257
  - SetAudioPathConfigReq, 770
- pRXAVCList
  - GetAudioPathConfigResp, 257
  - SetAudioPathConfigReq, 770
- pRXChain0Info
  - nasGetTxRxInfoResp, 533
- pRXChain1Info
  - nasGetTxRxInfoResp, 533
- pRXComprSlope
  - RXAGCList, 749
- pRXComprThres
  - RXAGCList, 749
- pRXDroppedCount
  - WdsPktStatisticsElmnts, 1198
- pRXExpSlope
  - RXAGCList, 749
- pRXExpThres
  - RXAGCList, 749
- pRXOKBytesCount
  - getDUNCallInfoResp, 268
- pRXOKBytesLastCall
  - WdsPktStatisticsElmnts, 1198
- pRXOKBytesCount
  - WdsPktStatisticsElmnts, 1198
- pRXPCMIIRFtr
  - GetAudioPathConfigResp, 257
  - SetAudioPathConfigReq, 770
- pRXPacketErrors
  - WdsPktStatisticsElmnts, 1198
- pRXPacketOverflows
  - WdsPktStatisticsElmnts, 1198
- pRXPacketSuccesses
  - WdsPktStatisticsElmnts, 1199
- pRXStaticGain
  - RXAGCList, 749
- pRXTotalBytes
  - WdsByteTotalsElmnts, 1186
- pRadioInterface
  - nasNetworkTime, 540
  - unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t, 1015
- pRankIndicatorInd
  - NasSwIndReg, 556
  - pack\_nas\_SLQSNasSwiOTAMessageCallback\_t, 610
- pRatHandoverStatusConfig
  - IMSAIndRegisterInfo, 317
- pRawHorConfidence
  - LocInjectPositionReq, 397
- pRawHorUncCircular
  - LocInjectPositionReq, 397
- pReadAcknowledgementReq
  - cdmaMsgDecodingParams, 157
- pReadResult
  - UIMReadTransparentResp, 925
  - unpack\_uim\_ReadTransparent\_t, 1065
- pReason
  - voiceSUPSInfo, 1158
- pRecurrenceType
  - LOCStartReq, 402
  - pack\_loc\_Start\_t, 595
- pRedirNumInfo
  - voiceInfoRec, 1137
- pRefData
  - FirmwareUpdatStat, 244
- pRefString
  - FirmwareUpdatStat, 244
- pRefStringLen
  - FirmwareUpdatStat, 244
- pReferenceNum
  - wcdmaLongMsgDecodingParams, 1164
- pRefreshEvent
  - UIMRefreshGetLastEventResp, 929
- pRegCallStatInfoEvt
  - \_getIndicationRegResp, 56
  - \_setIndicationRegReq, 67
- pRegDTMFEvents
  - voiceIndicationRegisterInfo, 1135
- pRegInd
  - \_getTransLayerInfoResp, 60
- pRegMgrConfigEvents
  - imsCfgIndRegisterInfo, 327
- pRegStatus
  - \_getTransNWRegInfoResp, 61
- pRegStatusConfig
  - IMSAIndRegisterInfo, 317
- pRegStatusErrorCode
  - imsaRegStatusInfo, 321

- pRegTransLayerInfoEvt
  - \_getIndicationRegResp, [56](#)
  - \_setIndicationRegReq, [67](#)
- pRegTransNWRRegInfoEvt
  - \_getIndicationRegResp, [56](#)
  - \_setIndicationRegReq, [67](#)
- pRegVoicePrivacyEvents
  - voiceIndicationRegisterInfo, [1135](#)
- pRejectReason
  - pack\_swioama\_SLQSOMADMSendSelection\_t, [627](#)
- pRelValidity
  - cdmaMsgEncodingParams, [159](#)
- pRelativeValidity
  - cdmaMsgDecodingParams, [157](#)
- pRemainingRetries
  - UIMDepersonalizationResp, [917](#)
  - UIMPinResp, [922](#)
  - unpack\_uim\_ChangePin\_t, [1063](#)
  - unpack\_uim\_SetPinProtection\_t, [1066](#)
  - unpack\_uim\_UnblockPin\_t, [1068](#)
  - unpack\_uim\_VerifyPin\_t, [1070](#)
- pRemotePartyName
  - voiceCallInfoResp, [1105](#)
- pRemotePartyNum
  - voiceCallInfoResp, [1105](#)
- pReportChannelRate
  - getDUNCallInfoReq, [265](#)
  - pack\_wds\_SLQSGetDUNCallInfo\_t, [644](#)
- pReportConnStatus
  - getDUNCallInfoReq, [265](#)
  - pack\_wds\_SLQSGetDUNCallInfo\_t, [644](#)
- pReportDataBearerTech
  - getDUNCallInfoReq, [265](#)
  - pack\_wds\_SLQSGetDUNCallInfo\_t, [644](#)
- pReportDormStatus
  - getDUNCallInfoReq, [265](#)
  - pack\_wds\_SLQSGetDUNCallInfo\_t, [644](#)
- pReqFieldsList
  - IMSASupportedFieldsResp, [324](#)
- pReqMitigationLvl
  - TmdGetMitigationLvlResp, [886](#)
- pReqSettings
  - pack\_wds\_SLQSGetRuntimeSettings\_t, [646](#)
- pRequestOptionList
  - unpack\_wds\_SLQSSetDHCPv4ClientConfig\_t, [1087](#)
  - WdsDHCPv4Config, [1190](#)
- pRequestedTag
  - pack\_sms\_SLQSGetSMSList\_t, [622](#)
- pRespData
  - USSDRespFNetwork, [1094](#)
- pRespFieldsList
  - IMSASupportedFieldsResp, [324](#)
- pRetryCount
  - \_SLQSOMADMSessionInfo, [74](#)
- pRetryMessage
  - slqssendasyncsmsparams\_s, [811](#)
- pRetryMessageId
  - slqssendasyncsmsparams\_s, [811](#)
- pRevInUse
  - CDMASysInfo, [164](#)
  - nas\_CDMASysInfo, [443](#)
- pRevInUseValid
  - CDMASysInfo, [164](#)
  - nas\_CDMASysInfo, [443](#)
- pRevTunneling
  - pack\_wds\_SetMobileIPProfile\_t, [642](#)
- pRingBackTimer
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pRingingTimer
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pRoamPref
  - \_sysSelectPrefInfo, [88](#)
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [615](#)
  - unpack\_nas\_SLQSGetSysSelectionPref\_t, [1012](#)
- pRoamTimer
  - voiceGetConfigReq, [1131](#)
- pRoamTimerCnt
  - voiceGetConfigResp, [1134](#)
- pRoamTimerConfig
  - voiceSetConfigReq, [1148](#)
- pRoamTimerStatus
  - voiceSetConfigResp, [1150](#)
- pRoaming
  - QmiNas3GppNetworkInfo, [721](#)
- pRscp
  - nasSigInfo, [554](#)
  - unpack\_nas\_SLQSNasSigInfoCallback\_t, [1017](#)
- pRxFilter
  - swiQosModifyReq, [869](#)
  - swiQosReq, [870](#)
- pRxFlow
  - swiQosGranted, [868](#)
  - swiQosModifyReq, [869](#)
  - swiQosReq, [870](#)
- pRxQFilter
  - QosFlowInfo, [731](#)
- pRxQFlowGranted
  - QosFlowInfo, [731](#)
- PSDetachReq, [695](#)
  - pDetachAction, [695](#)
- PSDomain
  - unpack\_nas\_GetServingNetwork\_t, [995](#)
- pSIPConfigEvents
  - imsCfgIndRegisterInfo, [327](#)
- pSIPLocalPort
  - GetSIPConfigResp, [285](#)
  - imsSIPConfigInfo, [330](#)
  - SetSIPConfigReq, [794](#)
- pSMSAttemptedFlag

- getDyingGaspStatistics, [269](#)
- packgetDyingGaspStatistics, [655](#)
- pSMSCAddressInfo
  - SMSEventInfo\_s, [831](#)
- pSMSConfigEvents
  - imsCfgIndRegisterInfo, [327](#)
- pSMSFormat
  - GetIMSSMSConfigParams, [272](#)
  - imsSMSConfigInfo, [331](#)
  - SetIMSSMSConfigReq, [775](#)
- pSMSONIMSInfo
  - SMSEventInfo\_s, [831](#)
- pSMSOverIPNwInd
  - GetIMSSMSConfigParams, [272](#)
  - imsSMSConfigInfo, [331](#)
  - SetIMSSMSConfigReq, [775](#)
- pSMSSupport
  - custFeaturesInfo, [197](#)
- pSMSSvcRAT
  - imsaSvcStatusInfo, [325](#)
- pSMSSvcStatus
  - imsaSvcStatusInfo, [325](#)
- pSV
  - BdsSVInfo, [126](#)
  - loc\_BdsSVInfo, [377](#)
  - loc\_SVInfo, [387](#)
  - SVInfo, [850](#)
- pSVInfo
  - LocDelAssDataReq, [389](#)
  - pack\_loc\_Delete\_Assist\_Data\_t, [590](#)
- pSWVerString
  - \_SLQSSwiGetHostDevInfoParams, [80](#)
  - \_SLQSSwiSetHostDevInfoParams, [82](#)
- pSatelliteInfo
  - gnssSvInfoNotification, [287](#)
- pScAddr
  - wcdmaLongMsgDecodingParams, [1164](#)
  - wcdmaMsgDecodingParams, [1165](#)
- pScAddrLength
  - wcdmaLongMsgDecodingParams, [1164](#)
  - wcdmaMsgDecodingParams, [1165](#)
- pScanResult
  - \_slqsNetworkScanInfo, [71](#)
  - unpack\_nas\_PerformNetworkScan\_t, [997](#)
- pScrAmrEnable
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pScrAmrWbEnable
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pSeDNSIPv4Address
  - swiPDPRuntimeSettingsResp, [862](#)
- pSeDNSIPv6Address
  - swiPDPRuntimeSettingsResp, [862](#)
- pSePCSCFIPv4Address
  - swiPDPRuntimeSettingsResp, [862](#)
- pSePCSCFIPv6Address
  - swiPDPRuntimeSettingsResp, [862](#)
- pSecDNSIPv4AddPref
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pSecDNSIPv6addpref
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pSecV6DnsAddress
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pSecondaryDNSV4
  - qmiWdsRunTimeSettings, [727](#)
- pSecondaryDNSV6
  - qmiWdsRunTimeSettings, [727](#)
- pSecondaryFlag
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pSecondaryHA
  - pack\_wds\_SetMobileIPProfile\_t, [642](#)
- pSecondaryV4DnsAddress
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pSectorID
  - NetworkStatEVDO, [567](#)
- pSenderAddr
  - cdmaMsgDecodingParams, [157](#)
  - wcdmaLongMsgDecodingParams, [1164](#)
  - wcdmaMsgDecodingParams, [1165](#)
- pSenderAddrLength
  - cdmaMsgDecodingParams, [157](#)
  - wcdmaLongMsgDecodingParams, [1164](#)
  - wcdmaMsgDecodingParams, [1165](#)
- pSensorDataUsage
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pServerAddrList
  - qmiWdsRunTimeSettings, [727](#)
- pServiceClass
  - voiceSetSUPSServiceReq, [1153](#)
- pServiceOption
  - slqssendasyncsmsparams\_s, [811](#)
- pServiceStatusConfig
  - IMSAIndRegisterInfo, [317](#)
- pServingSystemInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [609](#)
- pSessionExpiryTimer
  - GetIMSVoIPConfigResp, [275](#)
  - imsVoIPConfigInfo, [334](#)
  - SetIMSVoIPConfigReq, [779](#)
- pSessionIDv4
  - GetSessionIDResp, [283](#)

- pSessionIDv6
  - GetSessionIDResp, [283](#)
- pSessionState
  - \_SLQSOMADMSessionInfo, [74](#)
- pSessionType
  - \_SLQSOMADMSessionInfo, [74](#)
- pSettingResp
  - GetIMSSMSConfigParams, [272](#)
  - GetIMSUserConfigParams, [273](#)
  - GetIMSVoIPConfigResp, [275](#)
  - GetRegMgrConfigParams, [283](#)
  - GetSIPConfigResp, [284](#)
  - SetIMSSMSConfigResp, [776](#)
  - SetIMSUserConfigResp, [777](#)
  - SetIMSVoIPConfigResp, [780](#)
  - SetRegMgrConfigResp, [787](#)
  - SetSIPConfigResp, [794](#)
- pSeverity
  - \_SLQSOMADMSessionInfo, [74](#)
- pSigCompEnabled
  - GetSIPConfigResp, [285](#)
  - imsSIPConfigInfo, [330](#)
  - SetSIPConfigReq, [794](#)
- pSigIndReq
  - pack\_nas\_SLQSSetSignalStrengthsCallback\_t, [611](#)
- pSignalInfo
  - voiceInfoRec, [1137](#)
- pSignalStrengthInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [609](#)
- pSmsOnlms
  - slqssendasyncsmsparams\_s, [811](#)
  - slqssendsmsparams\_s, [812](#)
- pSmsServiceRat
  - IMSAServiceStatus, [323](#)
- pSmsServiceStatus
  - IMSAServiceStatus, [323](#)
- pSource
  - \_SLQSOMADMSessionInfo, [74](#)
- pSourceIP
  - LibPackTFTIDParams, [371](#)
  - TFTIDParams, [881](#)
- pSourceLength
  - \_SLQSOMADMSessionInfo, [74](#)
- pSpeedHorizontal
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pSpeedUnc
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pSpeedVertical
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pSrcRAT
  - imsaRatStatusInfo, [319](#)
- pSrvDomainPref
  - \_sysSelectPrefInfo, [88](#)
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [615](#)
  - unpack\_nas\_SLQSGetSysSelectionPref\_t, [1012](#)
- pSrvOpt
  - voiceCallInfoResp, [1105](#)
- pSrvRegRestriction
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [615](#)
- pSrvcProviderName
  - nasOperatorNameResp, [541](#)
- pStage0Val
  - RXPCMIIRFiltr, [753](#)
  - TXPCMIIRFiltr, [897](#)
- pStage1Val
  - RXPCMIIRFiltr, [753](#)
  - TXPCMIIRFiltr, [897](#)
- pStage2Val
  - RXPCMIIRFiltr, [753](#)
  - TXPCMIIRFiltr, [897](#)
- pStage3Val
  - RXPCMIIRFiltr, [753](#)
  - TXPCMIIRFiltr, [897](#)
- pStage4Val
  - RXPCMIIRFiltr, [753](#)
  - TXPCMIIRFiltr, [897](#)
- pStageCnt
  - RXPCMIIRFiltr, [753](#)
  - TXPCMIIRFiltr, [897](#)
- pStatMask
  - WdsPktStatisticsReq, [1199](#)
- pStatus
  - \_SLQSOMADMSessionInfo, [74](#)
- pSubnetMaskV4
  - qmiWdsRunTimeSettings, [727](#)
- pSubscribeTimer
  - GetSIPConfigResp, [285](#)
  - imsSIPConfigInfo, [330](#)
  - SetSIPConfigReq, [794](#)
- pSubscriptionInfoInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [609](#)
- pSupUSBComps
  - USBCompParams, [1093](#)
- pSupportedMsgList
  - IMSASupportedMsgInfo, [325](#)
- pSuppsNotifEvents
  - voiceIndicationRegisterInfo, [1135](#)
- pSvUsedforFix
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pSvcClass
  - voiceGetCallBarringReq, [1115](#)
  - voiceGetCallBarringResp, [1116](#)
  - voiceGetCallFWReq, [1118](#)
  - voiceGetCallWaitInfo, [1121](#)
  - voiceSUPSInfo, [1158](#)
- pSvcType
  - voiceCallRequestParams, [1107](#)

- pSwiGetResetInd
  - dmsIndicationRegisterReq, [224](#)
- pSysInfoInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [609](#)
- pSysInfoNoChange
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pSystemSelectionInd
  - nasIndicationRegisterReq, [537](#)
  - pack\_nas\_SLQSNasIndicationRegisterExt\_t, [609](#)
- pTCPDstPort
  - swiQosFilter, [864](#)
- pTCPSrcPort
  - swiQosFilter, [864](#)
- pTDSCDMAECIODelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pTDSCDMAECIOTresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pTDSCDMAECIOTreshList
  - nas\_TDSCDMAECIOTresh, [506](#)
  - TDSCDMAECIOTresh, [874](#)
- pTDSCDMARSCPDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pTDSCDMARSCPTresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pTDSCDMARSCPTreshList
  - nas\_TDSCDMARSCPTresh, [506](#)
  - TDSCDMARSCPTresh, [875](#)
- pTDSCDMARSSIDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [792](#)
- pTDSCDMARSSITresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [793](#)
- pTDSCDMARSSITreshList
  - nas\_TDSCDMARSSITresh, [507](#)
  - TDSCDMARSSITresh, [875](#)
- pTDSCDMASINRCONFThresh
  - sigInfo, [797](#)
- pTDSCDMASINRDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [793](#)
- pTDSCDMASINRThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [793](#)
- pTDSCDMASINRThreshList
  - nas\_TDSCDMASINRThresh, [507](#)
  - TDSCDMASINRThresh, [878](#)
- pTDSCDMASigInfoExt
  - nasGetSigInfoResp, [529](#)
  - nasSigInfo, [554](#)
  - unpack\_nas\_SLQSNasSigInfoCallback\_t, [1017](#)
- pTDSCDMASigInfoRscp
  - nasGetSigInfoResp, [529](#)
- pTFTID1Params
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pTFTID2Params
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pTTYConfigStatus
  - voiceSetConfigResp, [1150](#)
- pTTYMode
  - voiceGetConfigReq, [1131](#)
  - voiceSetConfigReq, [1148](#)
- pTXAGCList
  - GetAudioPathConfigResp, [257](#)
  - SetAudioPathConfigReq, [770](#)
- pTXAIG
  - TXAGCList, [894](#)
- pTXAVCSwitch
  - GetAudioPathConfigResp, [257](#)
  - SetAudioPathConfigReq, [770](#)
- pTXComprSlope
  - TXAGCList, [894](#)
- pTXComprThres
  - TXAGCList, [894](#)
- pTXDroppedCount
  - WdsPktStatisticsElmnts, [1199](#)
- pTXExpSlope
  - TXAGCList, [894](#)
- pTXExpThres
  - TXAGCList, [894](#)
- pTXGain
  - GetAudioPathConfigResp, [257](#)
  - SetAudioPathConfigReq, [770](#)
- pTXInfo
  - nasGetTxRxInfoResp, [533](#)
- pTXOKBytesCount
  - getDUNCallInfoResp, [268](#)
- pTXOKBytesLastCall
  - WdsPktStatisticsElmnts, [1199](#)
- pTXOkBytesCount
  - WdsPktStatisticsElmnts, [1199](#)
- pTXPCMIIRFitr
  - GetAudioPathConfigResp, [257](#)
  - SetAudioPathConfigReq, [770](#)
- pTXPacketErrors
  - WdsPktStatisticsElmnts, [1199](#)
- pTXPacketOverflows
  - WdsPktStatisticsElmnts, [1199](#)
- pTXPacketSuccesses
  - WdsPktStatisticsElmnts, [1199](#)
- pTXStaticGain
  - TXAGCList, [894](#)
- pTXTotalBytes
  - WdsByteTotalsElmnts, [1187](#)
- pTdsBandCapability
  - BandCapabilityResp, [125](#)

- pTdsdmaBandPref
  - \_sysSelectPrefParams, [93](#)
  - pack\_nas\_SLQSSetSysSelectionPref\_t, [615](#)
- pTech
  - pack\_wds\_SLQSStartDataSession\_t, [653](#)
- pTechnology
  - qmiWdsRunTimeSettings, [727](#)
  - ssdatasession\_params, [847](#)
- pTechnologyMask
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pTextMsg
  - cdmaMsgDecodingParams, [157](#)
  - cdmaMsgEncodingParams, [159](#)
  - wcdmaLongMsgDecodingParams, [1164](#)
  - wcdmaMsgDecodingParams, [1165](#)
  - wcdmaMsgEncodingParams, [1166](#)
- pTextMsgLength
  - cdmaMsgDecodingParams, [157](#)
  - wcdmaLongMsgDecodingParams, [1164](#)
  - wcdmaMsgDecodingParams, [1166](#)
- pTgtRAT
  - imsaRatStatusInfo, [319](#)
- pTime
  - \_SLQSOMADMSessionInfo, [74](#)
  - SwiOTAMsg\_s, [858](#)
- pTimeLength
  - \_SLQSOMADMSessionInfo, [75](#)
- pTimeSrc
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pTimeStamp
  - getDyingGaspStatistics, [269](#)
  - packgetDyingGaspStatistics, [655](#)
  - PDSPositionData, [661](#)
- pTimeType
  - PDSPositionData, [661](#)
- pTimeUnc
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pTimeZone
  - nasNetworkTime, [540](#)
  - unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t, [1015](#)
- pTimerSIPReg
  - GetSIPConfigResp, [285](#)
  - imsSIPConfigInfo, [330](#)
  - SetSIPConfigReq, [794](#)
- pTimerT1
  - GetSIPConfigResp, [285](#)
  - imsSIPConfigInfo, [330](#)
  - SetSIPConfigReq, [794](#)
- pTimerT2
  - GetSIPConfigResp, [285](#)
  - imsSIPConfigInfo, [330](#)
  - SetSIPConfigReq, [794](#)
- pTimerTf
  - GetSIPConfigResp, [285](#)
- imsSIPConfigInfo, [330](#)
- SetSIPConfigReq, [794](#)
- pTimerVal
  - voiceSetSUPSServiceReq, [1153](#)
- pTimestampAge
  - LocInjectPositionReq, [397](#)
- pTimestampUtc
  - LocInjectPositionReq, [397](#)
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pTokenBucket
  - swiQosFlow, [868](#)
- pTos
  - swiQosFilter, [864](#)
- pTotalBytesRX
  - QosEventInfo, [730](#)
  - slqsWdsEventInfo, [823](#)
- pTotalBytesTX
  - QosEventInfo, [730](#)
  - slqsWdsEventInfo, [823](#)
- pTotalNum
  - wcdmaLongMsgDecodingParams, [1164](#)
- pTrafficClass
  - swiQosFlow, [868](#)
- pTranDstPort
  - swiQosFilter, [864](#)
- pTranSrcPort
  - swiQosFilter, [864](#)
- pTransLayerInfo
  - \_getTransLayerInfoResp, [60](#)
  - \_transLayerInfoNotification, [95](#)
- pTransferRouteMTMessageInfo
  - SMSEventInfo\_s, [831](#)
- pTransferStatInd
  - getDUNCallInfoReq, [265](#)
  - pack\_wds\_SLQSGetDUNCallInfo\_t, [644](#)
  - wdsSetEventReportReq, [1204](#)
- pTransferStatusReport
  - smsSetRoutesReq, [839](#)
- pTrueIMSI
  - nasGet3GPP2SubscriptionInfoResp, [526](#)
- pTxFilter
  - swiQosModifyReq, [869](#)
  - swiQosReq, [870](#)
- pTxFlow
  - swiQosGranted, [868](#)
  - swiQosModifyReq, [869](#)
  - swiQosReq, [870](#)
- pTxQFilter
  - QosFlowInfo, [731](#)
- pTxQFlowGranted
  - QosFlowInfo, [731](#)
- pTypeCode
  - USSDRespFNetwork, [1095](#)
- pUATI
  - GetHRPDStatsResp, [271](#)
- pUDPDstPort
  - swiQosFilter, [864](#)



- pUDPSrcPort
  - swiQosFilter, [864](#)
- pUMTSCellID
  - nasCellLocationInfoResp, [524](#)
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1013](#)
- pUMTSGrantedQoS
  - qmiWdsRunTimeSettings, [727](#)
- pUMTSInfo
  - nasCellLocationInfoResp, [524](#)
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1013](#)
- pUMTSMinQoS
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pUMTSMinQoSSigInd
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pUMTSReqQoS
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pUMTSReqQoSSigInd
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pUSBComp
  - USBCompConfig, [1091](#)
  - USBCompParams, [1093](#)
- pUSSDData
  - USSDNoWaitIndicationInfo, [1094](#)
- pUSSDInfo
  - USSResp, [1096](#)
- pUSSInfo
  - voiceSUPSInfo, [1158](#)
- pUTSvcRAT
  - imsaSvcStatusInfo, [325](#)
- pUTSvcStatus
  - imsaSvcStatusInfo, [325](#)
- pUUSInFo
  - voiceCallRequestParams, [1107](#)
- pUUSInfo
  - voiceCallInfoResp, [1105](#)
- pUimSlotsStatus
  - UIMGetSlotsStatusResp, [922](#)
  - unpack\_uim\_SLQSUIMGetSlotsStatus\_t, [1067](#)
- pUpdateCompleteStatus
  - \_SLQSOMADMSessionInfo, [75](#)
- pUser
  - pack\_wds\_SLQSSStartDataSession\_t, [653](#)
- pUserAcknowledgementReq
  - cdmaMsgDecodingParams, [157](#)
- pUserConfigEvents
  - imsCfgIndRegisterInfo, [327](#)
- pUserData
  - slqssendasyncsmsparams\_s, [811](#)
- pUserId
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pUserIdSize
  - LibpackProfile3GPP2, [355](#)
  - LibPackprofile\_3GPP2, [368](#)
  - Profile3GPP2, [692](#)
- pUsername
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
  - Profile3GPP, [686](#)
  - qmiWdsRunTimeSettings, [727](#)
  - ssdatasession\_params, [847](#)
- pUsernameSize
  - LibpackProfile3GPP, [349](#)
  - LibPackprofile\_3GPP, [362](#)
  - Profile3GPP, [686](#)
- pUtServiceRat
  - IMSAServiceStatus, [323](#)
- pUtServiceStatus
  - IMSAServiceStatus, [323](#)
- pV4sessionId
  - WdsByteTotals, [1186](#)
  - WdsConnectionRate, [1188](#)
  - WdsPktStatisticsResp, [1200](#)
- pV6sessionId
  - WdsByteTotals, [1186](#)
  - WdsConnectionRate, [1188](#)
  - WdsPktStatisticsResp, [1200](#)
- pVOIPSvcRAT
  - imsaSvcStatusInfo, [325](#)
- pVOIPSvcStatus
  - imsaSvcStatusInfo, [326](#)
- pVTSvcRAT
  - imsaSvcStatusInfo, [326](#)
- pVTSvcStatus
  - imsaSvcStatusInfo, [326](#)
- pVerboseFailReasonType
  - unpack\_wds\_SLQSSStartDataSession\_t, [1087](#)
- pVerboseFailureReason
  - unpack\_wds\_SLQSSStartDataSession\_t, [1087](#)
- pVersionString
  - \_SLQSSwiGetOSInfoParams, [80](#)
  - \_SLQSSwiSetOSInfoParams, [83](#)
- pVertConfidence
  - LocInjectPositionReq, [397](#)
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pVertReliability
  - LocInjectPositionReq, [397](#)
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
- pVertUnc
  - LocInjectPositionReq, [397](#)
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)

- pVerticalConfidence
  - PDSPositionData, [661](#)
- pVerticalUnc
  - PDSPositionData, [661](#)
- pVoIPConfigEvents
  - imsCfgIndRegisterInfo, [327](#)
- pVoiceDomainPref
  - voiceGetConfigReq, [1132](#)
- pVoiceDomainPrefStatus
  - voiceSetConfigResp, [1150](#)
- pVoicePrivacy
  - voiceCallInfoResp, [1105](#)
  - voiceGetAllCallInfo, [1114](#)
- pVoipServiceRat
  - IMSAServiceStatus, [323](#)
- pVoipServiceStatus
  - IMSAServiceStatus, [323](#)
- pVolume
  - SetM2MAudioProfileReq, [783](#)
- pVsServiceRat
  - IMSAServiceStatus, [323](#)
- pVsServiceStatus
  - IMSAServiceStatus, [323](#)
- pVtServiceRat
  - IMSAServiceStatus, [323](#)
- pVtServiceStatus
  - IMSAServiceStatus, [324](#)
- pWCDMABER
  - GetErrRateResp, [270](#)
- pWCDMACallBarringSysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1009](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pWCDMACipherDomainSysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1009](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pWCDMAECIODelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [793](#)
- pWCDMAECIOThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [793](#)
- pWCDMAECIOThreshList
  - nas\_WCDMAECIOThresh, [517](#)
  - WCDMAECIOThresh, [1161](#)
- pWCDMAInfoLTENeighborCell
  - nasCellLocationInfoResp, [524](#)
  - unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1013](#)
- pWCDMARSSIDelta
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [793](#)
- pWCDMARSSIThresh
  - pack\_nas\_SLQSNasConfigSigInfo2\_t, [605](#)
  - setSignalStrengthInfo, [793](#)
- pWCDMARSSIThreshList
  - nas\_WCDMARSSIThresh, [519](#)
  - WCDMARSSIThresh, [1167](#)
- pWCDMASSInfo
  - nasGetSigInfoResp, [529](#)
- pWCDMASigInfo
  - nasSigInfo, [554](#)
  - unpack\_nas\_SLQSNasSigInfoCallback\_t, [1017](#)
- pWCDMASrvStatusInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1009](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pWCDMASysInfo
  - nasGetSysInfoResp, [532](#)
  - nasSysInfo, [559](#)
  - unpack\_nas\_SLQSGetSysInfo\_t, [1009](#)
  - unpack\_nas\_SLQSSysInfoCallback\_t, [1022](#)
- pWcdmaUARFCN
  - nasSwiGetChannelLockResp, [554](#)
  - nasSwiSetChannelLockReq, [556](#)
- pWifiState
  - PDSPosMethodStateReq, [662](#)
- pXtraDataState
  - PDSPosMethodStateReq, [662](#)
- pXtraTimeState
  - PDSPosMethodStateReq, [662](#)
- pack\_dms\_GetActivationState
  - dms.h, [1219](#)
- pack\_dms\_GetBandCapability
  - dms.h, [1219](#)
- pack\_dms\_GetCrashAction
  - dms.h, [1219](#)
- pack\_dms\_GetCustFeature
  - dms.h, [1219](#)
- pack\_dms\_GetCustFeaturesV2
  - dms.h, [1221](#)
- pack\_dms\_GetCustFeaturesV2\_t, [582](#)
  - cust\_id, [582](#)
  - list\_type, [582](#)
  - Tlvresult, [582](#)
- pack\_dms\_GetDeviceCap
  - dms.h, [1221](#)
- pack\_dms\_GetDeviceCapabilities
  - dms.h, [1221](#)
- pack\_dms\_GetDeviceHardwareRev
  - dms.h, [1221](#)
- pack\_dms\_GetDeviceMfr
  - dms.h, [1222](#)
- pack\_dms\_GetDeviceSerialNumbers
  - dms.h, [1222](#)
- pack\_dms\_GetFSN
  - dms.h, [1223](#)
- pack\_dms\_GetFirmwareInfo
  - dms.h, [1222](#)
- pack\_dms\_GetFirmwareRevision
  - dms.h, [1223](#)
- pack\_dms\_GetFirmwareRevisions



- dms.h, [1223](#)
- pack\_dms\_GetHardwareRevision
  - dms.h, [1224](#)
- pack\_dms\_GetIMSI
  - dms.h, [1224](#)
- pack\_dms\_GetModelID
  - dms.h, [1224](#)
- pack\_dms\_GetNetworkTime
  - dms.h, [1225](#)
- pack\_dms\_GetPRLVersion
  - dms.h, [1225](#)
- pack\_dms\_GetPower
  - dms.h, [1225](#)
- pack\_dms\_GetSerialNumbers
  - dms.h, [1226](#)
- pack\_dms\_GetUSBComp
  - dms.h, [1226](#)
- pack\_dms\_GetVoiceNumber
  - dms.h, [1226](#)
- pack\_dms\_SLQSDmsSwiGetResetInfo
  - dms.h, [1229](#)
- pack\_dms\_SLQSDmsSwiIndicationRegister
  - dms.h, [1230](#)
- pack\_dms\_SLQSDmsSwiIndicationRegister\_t, [585](#)
  - resetInfoInd, [585](#)
- pack\_dms\_SLQSGetBandCapability
  - dms.h, [1230](#)
- pack\_dms\_SLQSSwiClearDyingGaspStatistics
  - dms.h, [1230](#)
- pack\_dms\_SLQSSwiGetDyingGaspCfg
  - dms.h, [1231](#)
- pack\_dms\_SLQSSwiGetDyingGaspStatistics
  - dms.h, [1231](#)
- pack\_dms\_SLQSSwiGetFirmwareCurr
  - dms.h, [1231](#)
- pack\_dms\_SLQSSwiGetFwUpdateStatus
  - dms.h, [1232](#)
- pack\_dms\_SLQSSwiSetDyingGaspCfg
  - dms.h, [1232](#)
- pack\_dms\_SLQSSwiSetDyingGaspCfg\_t, [585](#)
  - pDestSMSContent, [586](#)
  - pDestSMSNum, [586](#)
- pack\_dms\_SetCrashAction
  - dms.h, [1227](#)
- pack\_dms\_SetCrashAction\_t, [582](#)
  - crashAction, [583](#)
- pack\_dms\_SetCustFeature
  - dms.h, [1227](#)
- pack\_dms\_SetCustFeature\_t, [583](#)
  - DHCPRelayEnabled, [583](#)
  - DisableIMSI, [583](#)
  - GPSPMP, [583](#)
  - GPSSel, [583](#)
  - GpsEnable, [583](#)
  - IPFamSupport, [583](#)
  - IsVoiceEnabled, [583](#)
  - RMAutoConnect, [583](#)
  - SMSSupport, [584](#)
- pack\_dms\_SetCustFeaturesV2
  - dms.h, [1228](#)
- pack\_dms\_SetCustFeaturesV2\_t, [584](#)
  - cust\_id, [584](#)
  - cust\_value, [584](#)
  - Tlvresult, [584](#)
  - value\_length, [584](#)
- pack\_dms\_SetEventReport
  - dms.h, [1228](#)
- pack\_dms\_SetEventReport\_t, [584](#)
  - mode, [584](#)
- pack\_dms\_SetFirmwarePreference
  - dms.h, [1228](#)
- pack\_dms\_SetPower
  - dms.h, [1229](#)
- pack\_dms\_SetPower\_t, [585](#)
  - mode, [585](#)
  - Tlvresult, [585](#)
- pack\_dms\_SetUSBComp
  - dms.h, [1229](#)
- pack\_dms\_SetUSBComp\_t, [585](#)
  - Tlvresult, [585](#)
  - USBComp, [585](#)
- pack\_dms\_UIMGetICCID
  - dms.h, [1232](#)
- pack\_dms\_UIMGetICCID\_t, [586](#)
  - Tlvresult, [586](#)
- pack\_fms\_GetImagesPreference
  - fms.h, [1248](#)
- pack\_fms\_GetImagesPreference\_t, [586](#)
  - Tlvresult, [588](#)
- pack\_fms\_GetStoredImages
  - fms.h, [1249](#)
- pack\_fms\_GetStoredImages\_t, [588](#)
  - Tlvresult, [588](#)
- pack\_fms\_SetImagesPreference
  - fms.h, [1249](#)
- pack\_fms\_SetImagesPreference\_t, [588](#)
  - bForceDownload, [589](#)
  - imageListSize, [589](#)
  - modemindex, [589](#)
  - pImageList, [589](#)
  - Tlvresult, [589](#)
- pack\_loc\_Delete\_Assist\_Data\_t, [589](#)
  - pBdsSVInfo, [590](#)
  - pCellDb, [590](#)
  - pClkInfo, [590](#)
  - pGnssData, [590](#)
  - pSVInfo, [590](#)
  - Tlvresult, [590](#)
- pack\_loc\_DeleteAssistData
  - loc.h, [1254](#)
- pack\_loc\_EventRegister
  - loc.h, [1254](#)
- pack\_loc\_EventRegister\_t, [590](#)
  - eventRegister, [592](#)
  - Tlvresult, [592](#)
- pack\_loc\_SetExtPowerState

- loc.h, [1255](#)
- pack\_loc\_SetExtPowerState\_t, [592](#)
  - extPowerState, [592](#)
  - Tlvresult, [592](#)
- pack\_loc\_SetOperationMode
  - loc.h, [1255](#)
- pack\_loc\_SetOperationMode\_t, [592](#)
  - mode, [593](#)
  - Tlvresult, [593](#)
- pack\_loc\_Start
  - loc.h, [1255](#)
- pack\_loc\_Start\_t, [593](#)
  - pApplicationInfo, [595](#)
  - pConfigAltitudeAssumed, [595](#)
  - pHorizontalAccuracyLvl, [595](#)
  - pIntermediateReportState, [595](#)
  - pMinIntervalTime, [595](#)
  - pRecurrenceType, [595](#)
  - SessionId, [595](#)
  - Tlvresult, [595](#)
- pack\_loc\_Stop
  - loc.h, [1256](#)
- pack\_loc\_Stop\_t, [595](#)
  - SessionId, [595](#)
  - Tlvresult, [595](#)
- pack\_nas\_GetACCOLC
  - nas.h, [1265](#)
- pack\_nas\_GetANAAAAuthenticationStatus
  - nas.h, [1265](#)
- pack\_nas\_GetCDMANetworkParameters
  - nas.h, [1265](#)
- pack\_nas\_GetHomeNetwork
  - nas.h, [1266](#)
- pack\_nas\_GetNetworkPreference
  - nas.h, [1266](#)
- pack\_nas\_GetRFInfo
  - nas.h, [1266](#)
- pack\_nas\_GetServingNetwork
  - nas.h, [1266](#)
- pack\_nas\_GetServingNetworkCapabilities
  - nas.h, [1268](#)
- pack\_nas\_GetSignalStrengths
  - nas.h, [1268](#)
- pack\_nas\_PerformNetworkScan
  - nas.h, [1268](#)
- pack\_nas\_SLQSGetNetworkTime
  - nas.h, [1270](#)
- pack\_nas\_SLQSGetPLMNName
  - nas.h, [1270](#)
- pack\_nas\_SLQSGetPLMNName\_t, [598](#)
  - mcc, [599](#)
  - mnc, [599](#)
  - pMncPcsStatus, [599](#)
- pack\_nas\_SLQSGetServingSystem
  - nas.h, [1271](#)
- pack\_nas\_SLQSGetSignalStrength
  - nas.h, [1271](#)
- pack\_nas\_SLQSGetSysInfo
  - nas.h, [1271](#)
- pack\_nas\_SLQSGetSysSelectionPref
  - nas.h, [1272](#)
- pack\_nas\_SLQSInitiateNetworkRegistration
  - nas.h, [1272](#)
- pack\_nas\_SLQSInitiateNetworkRegistration\_t, [599](#)
  - pChangeDuration, [600](#)
  - pMNRInfo, [600](#)
  - pMncPcsDigitStatus, [600](#)
  - regAction, [600](#)
- pack\_nas\_SLQSNasConfigSigInfo2
  - nas.h, [1272](#)
- pack\_nas\_SLQSNasConfigSigInfo2\_t, [600](#)
  - pHDRIODelta, [604](#)
  - pHDRIOThresh, [605](#)
  - pLTESigRptConfig, [605](#)
- pack\_nas\_SLQSNasGetCellLocationInfo
  - nas.h, [1273](#)
- pack\_nas\_SLQSNasGetSigInfo
  - nas.h, [1273](#)
- pack\_nas\_SLQSNasIndicationRegisterExt
  - nas.h, [1273](#)
- pack\_nas\_SLQSNasIndicationRegisterExt\_t, [605](#)
  - pDDTMInd, [608](#)
  - pDualStandByPrefInd, [608](#)
  - pErrorRateInd, [608](#)
  - pHDRSessionCloseInd, [608](#)
  - pLTECphyCa, [609](#)
  - pManagedRoamingInd, [609](#)
  - pNetworkTimeInd, [609](#)
  - pServingSystemInd, [609](#)
  - pSignalStrengthInd, [609](#)
  - pSubscriptionInfoInd, [609](#)
  - pSysInfoInd, [609](#)
  - pSystemSelectionInd, [609](#)
- pack\_nas\_SLQSNasSwiModemStatus
  - nas.h, [1274](#)
- pack\_nas\_SLQSNasSwiOTAMessageCallback
  - nas.h, [1274](#)
- pack\_nas\_SLQSNasSwiOTAMessageCallback\_t, [609](#)
  - gsmUmtsDI, [610](#)
  - gsmUmtsUI, [610](#)
  - lteEmmDI, [610](#)
  - lteEmmUI, [610](#)
  - lteEsmDI, [610](#)
  - lteEsmUI, [610](#)
  - pRankIndicatorInd, [610](#)
- pack\_nas\_SLQSSetBandPreference
  - nas.h, [1274](#)
- pack\_nas\_SLQSSetSignalStrengthsCallback
  - nas.h, [1275](#)
- pack\_nas\_SLQSSetSignalStrengthsCallback\_t, [610](#)
  - bEnable, [611](#)
  - pSigIndReq, [611](#)
- pack\_nas\_SLQSSetSysSelectionPref
  - nas.h, [1275](#)
- pack\_nas\_SLQSSetSysSelectionPref\_t, [611](#)
  - pAcqOrderPref, [614](#)

- pBandPref, [614](#)
- pCSGID, [615](#)
- pChgDuration, [614](#)
- pEmerMode, [615](#)
- pGWAcqOrderPref, [615](#)
- pLTEBandPref, [615](#)
- pModePref, [615](#)
- pNetSelPref, [615](#)
- pPRLPref, [615](#)
- pRAT, [615](#)
- pRoamPref, [615](#)
- pSrvDomainPref, [615](#)
- pSrvRegRestriction, [615](#)
- pTdsdmaBandPref, [615](#)
- pack\_nas\_SLQSSwiGetLteCQI
  - nas.h, [1275](#)
- pack\_nas\_SetACCOLC
  - nas.h, [1269](#)
- pack\_nas\_SetACCOLC\_t, [595](#)
  - accolc, [597](#)
  - spc, [597](#)
- pack\_nas\_SetLURejectCallback
  - nas.h, [1269](#)
- pack\_nas\_SetNetworkPreference
  - nas.h, [1269](#)
- pack\_nas\_SetNetworkPreference\_t, [597](#)
  - Duration, [598](#)
  - TechnologyPref, [598](#)
  - Tlvresult, [598](#)
- pack\_nas\_SetRFInfoCallback
  - nas.h, [1270](#)
- pack\_nas\_SlqsGetLTECphyCAInfo
  - nas.h, [1270](#)
- pack\_qmi\_t, [615](#)
  - msgid, [615](#)
  - svc, [615](#)
  - timeout, [615](#)
  - xid, [616](#)
- pack\_qos\_SLQSQosGetNetworkStatus
  - qos.h, [1742](#)
- pack\_qos\_SLQSQosSwiReadApnExtraParams
  - qos.h, [1742](#)
- pack\_qos\_SLQSQosSwiReadApnExtraParams\_t, [616](#)
  - apnId, [616](#)
- pack\_qos\_SLQSQosSwiReadDataStats
  - qos.h, [1743](#)
- pack\_qos\_SLQSQosSwiReadDataStats\_t, [616](#)
  - apnId, [616](#)
- pack\_qos\_SLQSSetQosEventCallback
  - qos.h, [1744](#)
- pack\_qos\_SLQSSetQosEventCallback\_t, [616](#)
  - enable, [618](#)
- pack\_sms\_SLQSDeleteSMS
  - sms.h, [1756](#)
- pack\_sms\_SLQSDeleteSMS\_t, [619](#)
  - pMessageIndex, [620](#)
  - pMessageMode, [620](#)
  - pMessageTag, [620](#)
  - storageType, [620](#)
- pack\_sms\_SLQSGetSMS
  - sms.h, [1756](#)
- pack\_sms\_SLQSGetSMS\_t, [620](#)
  - messageIndex, [621](#)
  - pMessageMode, [621](#)
  - storageType, [621](#)
- pack\_sms\_SLQSGetSMSList
  - sms.h, [1757](#)
- pack\_sms\_SLQSGetSMSList\_t, [621](#)
  - pMessageMode, [622](#)
  - pRequestedTag, [622](#)
  - storageType, [622](#)
- pack\_sms\_SLQSModifySMSStatus
  - sms.h, [1757](#)
- pack\_sms\_SLQSModifySMSStatus\_t, [622](#)
  - messageIndex, [623](#)
  - messageTag, [623](#)
  - pMessageMode, [623](#)
  - storageType, [623](#)
- pack\_sms\_SendSMS
  - sms.h, [1754](#)
- pack\_sms\_SendSMS\_t, [618](#)
  - messageFormat, [618](#)
  - messageSize, [618](#)
  - pLinktimer, [618](#)
  - pMessage, [618](#)
- pack\_sms\_SetNewSMSCallback
  - sms.h, [1756](#)
- pack\_sms\_SetNewSMSCallback\_t, [619](#)
  - status, [619](#)
- pack\_swiloc\_SwiLocGetAutoStart
  - swiloc.h, [1762](#)
- pack\_swiloc\_SwiLocSetAutoStart
  - swiloc.h, [1762](#)
- pack\_swiloc\_SwiLocSetAutoStart\_t, [623](#)
  - fix\_rate, [625](#)
  - fix\_type, [625](#)
  - function, [625](#)
  - max\_dist, [625](#)
  - max\_time, [625](#)
  - set\_fix\_rate, [625](#)
  - set\_fix\_type, [625](#)
  - set\_function, [625](#)
  - set\_max\_dist, [625](#)
  - set\_max\_time, [625](#)
- pack\_swioa\_SLQSOMADMAAlertCallback
  - swioa.h, [1764](#)
- pack\_swioa\_SLQSOMADMCancelSession
  - swioa.h, [1765](#)
- pack\_swioa\_SLQSOMADMCancelSession\_t, [625](#)
  - sessionType, [625](#)
- pack\_swioa\_SLQSOMADMGetSessionInfo
  - swioa.h, [1765](#)
- pack\_swioa\_SLQSOMADMGetSessionInfo\_t, [625](#)
  - SessionType, [626](#)
- pack\_swioa\_SLQSOMADMGetSettings
  - swioa.h, [1766](#)

- pack\_swima\_SLQSOMADMSendSelection
  - swioma.h, [1767](#)
- pack\_swima\_SLQSOMADMSendSelection\_t, [626](#)
  - pDeferTime, [627](#)
  - pRejectReason, [627](#)
  - selection, [627](#)
- pack\_swima\_SLQSOMADMSetSettings
  - swioma.h, [1767](#)
- pack\_swima\_SLQSOMADMSetSettings\_t, [627](#)
  - FOTAdownload, [628](#)
  - pAutosdm, [628](#)
  - pFwAutoCheck, [628](#)
- pack\_swima\_SLQSOMADMStartSession
  - swioma.h, [1768](#)
- pack\_swima\_SLQSOMADMStartSession\_t, [628](#)
  - sessionType, [628](#)
- pack\_uim\_ChangePin
  - uim.h, [1775](#)
- pack\_uim\_ChangePin\_t, [628](#)
  - changePIN, [629](#)
  - EncryptedPIN1, [629](#)
  - pIndicationToken, [629](#)
  - pKeyReferenceID, [629](#)
  - sessionInfo, [629](#)
  - Tlvresult, [629](#)
- pack\_uim\_GetCardStatus
  - uim.h, [1775](#)
- pack\_uim\_ReadTransparent
  - uim.h, [1775](#)
- pack\_uim\_ReadTransparent\_t, [629](#)
  - fileIndex, [630](#)
  - pEncryptData, [630](#)
  - pIndicationToken, [630](#)
  - readTransparent, [630](#)
  - sessionInfo, [630](#)
  - Tlvresult, [631](#)
- pack\_uim\_SLQSUIEventRegister
  - uim.h, [1776](#)
- pack\_uim\_SLQSUIEventRegister\_t, [632](#)
  - eventMask, [632](#)
- pack\_uim\_SLQSUIGetSlotsStatus
  - uim.h, [1776](#)
- pack\_uim\_SLQSUIMSwitchSlot
  - uim.h, [1776](#)
- pack\_uim\_SLQSUIMSwitchSlot\_t, [632](#)
  - bLogicalSlot, [633](#)
  - ulPhysicalSlot, [633](#)
- pack\_uim\_SetPinProtection
  - uim.h, [1775](#)
- pack\_uim\_SetPinProtection\_t, [631](#)
  - EncryptedPIN1, [631](#)
  - pIndicationToken, [631](#)
  - pKeyReferenceID, [632](#)
  - pinProtection, [632](#)
  - sessionInfo, [632](#)
  - Tlvresult, [632](#)
- pack\_uim\_UnblockPin
  - uim.h, [1778](#)
- pack\_uim\_UnblockPin\_t, [633](#)
  - EncryptedPIN1, [634](#)
  - pIndicationToken, [634](#)
  - pKeyReferenceID, [634](#)
  - pinProtection, [634](#)
  - sessionInfo, [634](#)
  - Tlvresult, [634](#)
- pack\_uim\_VerifyPin
  - uim.h, [1778](#)
- pack\_uim\_VerifyPin\_t, [634](#)
  - pEncryptedPIN1, [636](#)
  - pIndicationToken, [636](#)
  - pKeyReferenceID, [636](#)
  - sessionInfo, [636](#)
  - Tlvresult, [636](#)
  - verifyPIN, [636](#)
- pack\_wds\_GetConnectionRate
  - wds.h, [1786](#)
- pack\_wds\_GetDefaultProfile
  - wds.h, [1787](#)
- pack\_wds\_GetDefaultProfile\_t, [636](#)
  - profiletype, [637](#)
- pack\_wds\_GetDefaultProfileNum
  - wds.h, [1787](#)
- pack\_wds\_GetDefaultProfileNum\_t, [637](#)
  - family, [637](#)
  - type, [637](#)
- pack\_wds\_GetDormancyState
  - wds.h, [1787](#)
- pack\_wds\_GetDormancyState\_t, [637](#)
- pack\_wds\_GetLastMobileIPError
  - wds.h, [1789](#)
- pack\_wds\_GetLastMobileIPError\_t, [637](#)
- pack\_wds\_GetMobileIP
  - wds.h, [1789](#)
- pack\_wds\_GetMobileIP\_t, [637](#)
- pack\_wds\_GetMobileIPProfile
  - wds.h, [1790](#)
- pack\_wds\_GetMobileIPProfile\_t, [637](#)
  - index, [639](#)
- pack\_wds\_GetPacketStatus
  - wds.h, [1790](#)
- pack\_wds\_GetPacketStatus\_t, [639](#)
  - statmask, [639](#)
- pack\_wds\_GetSessionDuration
  - wds.h, [1790](#)
- pack\_wds\_GetSessionDuration\_t, [639](#)
- pack\_wds\_GetSessionState
  - wds.h, [1791](#)
- pack\_wds\_RMSetTransferStatistics
  - wds.h, [1791](#)
- pack\_wds\_RMSetTransferStatistics\_t, [639](#)
  - RmTrasnferStaticsReq, [639](#)
- pack\_wds\_SLQSCreateProfile
  - wds.h, [1794](#)
- pack\_wds\_SLQSCreateProfile\_t, [642](#)
  - pCurProfile, [642](#)
  - pProfileId, [642](#)

- pProfileType, [643](#)
- pack\_wds\_SLQSDDeleteProfile
  - wds.h, [1794](#)
- pack\_wds\_SLQSDDeleteProfile\_t, [643](#)
  - profileIndex, [643](#)
  - profileType, [643](#)
- pack\_wds\_SLQSGet3GPPConfigItem
  - wds.h, [1794](#)
- pack\_wds\_SLQSGetCurrDataSystemStat
  - wds.h, [1795](#)
- pack\_wds\_SLQSGetCurrDataSystemStat\_t, [643](#)
- pack\_wds\_SLQSGetDUNCallInfo
  - wds.h, [1796](#)
- pack\_wds\_SLQSGetDUNCallInfo\_t, [643](#)
  - Mask, [644](#)
  - pReportChannelRate, [644](#)
  - pReportConnStatus, [644](#)
  - pReportDataBearerTech, [644](#)
  - pReportDormStatus, [644](#)
  - pTransferStatInd, [644](#)
- pack\_wds\_SLQSGetDataBearerTechnology
  - wds.h, [1795](#)
- pack\_wds\_SLQSGetDataBearerTechnology\_t, [643](#)
- pack\_wds\_SLQSGetProfileSettings
  - wds.h, [1796](#)
- pack\_wds\_SLQSGetProfileSettings\_t, [644](#)
  - ProfileId, [645](#)
  - ProfileType, [645](#)
- pack\_wds\_SLQSGetRuntimeSettings
  - wds.h, [1796](#)
- pack\_wds\_SLQSGetRuntimeSettings\_t, [645](#)
  - pReqSettings, [646](#)
- pack\_wds\_SLQSModifyProfile
  - wds.h, [1797](#)
- pack\_wds\_SLQSModifyProfile\_t, [646](#)
  - curProfile, [648](#)
  - pProfileId, [648](#)
  - pProfileType, [648](#)
- pack\_wds\_SLQSSGetDHCPv4ClientConfig
  - wds.h, [1798](#)
- pack\_wds\_SLQSSGetDHCPv4ClientConfig\_t, [652](#)
  - pProfileId, [652](#)
- pack\_wds\_SLQSSet3GPPConfigItem
  - wds.h, [1797](#)
- pack\_wds\_SLQSSet3GPPConfigItem\_t, [648](#)
  - \_3gppRelease, [649](#)
  - defaultPDNEnabled, [649](#)
  - profileList, [649](#)
- pack\_wds\_SLQSSetIPFamilyPreference
  - wds.h, [1798](#)
- pack\_wds\_SLQSSetIPFamilyPreference\_t, [649](#)
  - IPFamilyPreference, [651](#)
- pack\_wds\_SLQSSetWdsEventCallback
  - wds.h, [1798](#)
- pack\_wds\_SLQSSetWdsEventCallback\_t, [651](#)
  - currentDataBearer, [651](#)
  - dataBearer, [651](#)
  - dataSystemStatus, [651](#)
  - dormancyStatus, [651](#)
  - interval, [651](#)
  - mobileIP, [651](#)
  - transferStats, [651](#)
- pack\_wds\_SLQSStartDataSession
  - wds.h, [1799](#)
- pack\_wds\_SLQSStartDataSession\_t, [652](#)
  - pAuth, [653](#)
  - pPass, [653](#)
  - pTech, [653](#)
  - pUser, [653](#)
  - pprofileid3gpp, [653](#)
  - pprofileid3gpp2, [653](#)
- pack\_wds\_SLQSStopDataSession
  - wds.h, [1799](#)
- pack\_wds\_SLQSStopDataSession\_t, [653](#)
  - psid, [654](#)
- pack\_wds\_SLQSWdsSwiPDPRuntimeSettings
  - wds.h, [1800](#)
- pack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t, [654](#)
  - contextId, [654](#)
  - contextType, [654](#)
- pack\_wds\_SetDefaultProfile
  - wds.h, [1791](#)
- pack\_wds\_SetDefaultProfile\_t, [639](#)
  - authentication, [640](#)
  - ipAddress, [640](#)
  - pApnname, [640](#)
  - pName, [640](#)
  - pPassword, [640](#)
  - pUsername, [640](#)
  - pdpType, [640](#)
  - primaryDNS, [640](#)
  - profileType, [640](#)
  - secondaryDNS, [640](#)
- pack\_wds\_SetDefaultProfileNum
  - wds.h, [1793](#)
- pack\_wds\_SetDefaultProfileNum\_t, [640](#)
  - family, [641](#)
  - index, [641](#)
  - type, [641](#)
- pack\_wds\_SetMobileIPProfile
  - wds.h, [1793](#)
- pack\_wds\_SetMobileIPProfile\_t, [641](#)
  - index, [641](#)
  - pAAASPI, [641](#)
  - pAddress, [641](#)
  - pEnabled, [641](#)
  - pHASPI, [641](#)
  - pMNAAA, [641](#)
  - pMNHA, [642](#)
  - pNAI, [642](#)
  - pPrimaryHA, [642](#)
  - pRevTunneling, [642](#)
  - pSecondaryHA, [642](#)
  - spc, [642](#)
- PackCreateProfileOut, [654](#)
  - ExtErrorCode, [654](#)

- ProfileIndex, [654](#)
- ProfileType, [654](#)
- package\_name
  - omaDmFotaTlv, [577](#)
  - omaDmFotaTlvExt, [579](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- packageSize
  - omaDmFotaTlvExt, [579](#)
- packageid\_str
  - slqsfwinfo\_s, [806](#)
  - unpack\_dms\_GetFirmwareInfo\_t, [958](#)
- packetSrvStatus
  - qaGobiApiCbk.h, [1309](#)
- packetZone
  - CDMASysInfo, [164](#)
  - nas\_CDMASysInfo, [443](#)
- packetZoneValid
  - CDMASysInfo, [164](#)
  - nas\_CDMASysInfo, [443](#)
- packgetDyingGaspCfg, [654](#)
  - pDestSMSContent, [655](#)
  - pDestSMSNum, [655](#)
- packgetDyingGaspStatistics, [655](#)
  - pSMSAttemptedFlag, [655](#)
  - pTimeStamp, [655](#)
- path
  - fileInfo, [242](#)
  - uim\_fileInfo, [905](#)
- pathLen
  - fileInfo, [242](#)
  - uim\_fileInfo, [905](#)
- pblMSRegistered
  - imsaRegStatusInfo, [321](#)
- pci
  - cellParams, [166](#)
  - ltePCI, [414](#)
  - nas\_cellParams, [444](#)
  - nas\_umtsLTENbrCell, [513](#)
  - NASPhyCaAggPcellInfo, [543](#)
  - NASPhyCaAggScellIndType, [544](#)
  - NASPhyCaAggScellInfo, [546](#)
  - PhyCaAggPcellInfo, [667](#)
  - PhyCaAggScellIndType, [669](#)
  - PhyCaAggScellInfo, [671](#)
  - umtsLTENbrCell, [942](#)
- pcsfQDNAddress
  - PCSCFFQDNAddressList, [659](#)
  - wds\_PCSCFFQDNAddressList, [1180](#)
- pdpType
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
- pdptype
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- peakRate
  - tokenBucket, [887](#)
  - unpack\_qos\_tokenBucket\_t, [1048](#)
- peakThroughputClass
  - GPRSQoS, [288](#)
  - GPRSRequestedQoS, [289](#)
- LibPackGPRSRequestedQoS, [342](#)
- wds\_GPRSQoS, [1176](#)
- peerNumberInfo, [662](#)
  - callID, [664](#)
  - numLen, [664](#)
  - numPI, [664](#)
  - numPlan, [664](#)
  - numSI, [664](#)
  - numType, [664](#)
  - number, [664](#)
- PerformNetworkScan
  - qaGobiApiNas.h, [1505](#)
- PersistentTechPref
  - unpack\_nas\_GetNetworkPreference\_t, [993](#)
- persoFeature
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- persoRetries
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- persoState
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- persoUnblockRetries
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- personalizationStatus, [664](#)
  - feature, [665](#)
  - numFeatures, [665](#)
  - unblockLeft, [665](#)
  - verifyLeft, [665](#)
- pfailureCause
  - USSResp, [1096](#)
- phase
  - rxInfo, [751](#)
- PhyCaAggPcellInfo, [665](#)
  - dl\_bw\_value, [667](#)
  - freq, [667](#)
  - iLTEbandValue, [667](#)
  - NasGetLTECphyCaInfo, [527](#)
  - pci, [667](#)
  - TlvPresent, [667](#)
- PhyCaAggScellDIBw, [667](#)
  - dl\_bw\_value, [668](#)
  - NasGetLTECphyCaInfo, [527](#)
  - TlvPresent, [668](#)
- PhyCaAggScellIndType, [668](#)
  - freq, [669](#)
  - NasGetLTECphyCaInfo, [528](#)
  - pci, [669](#)
  - scell\_state, [669](#)
  - TlvPresent, [669](#)
- PhyCaAggScellIndex, [668](#)
  - NasGetLTECphyCaInfo, [527](#)

- scell\_idx, [668](#)
  - TlvPresent, [668](#)
- PhyCaAggScellInfo, [669](#)
  - dl\_bw\_value, [671](#)
  - freq, [671](#)
  - iLTEbandValue, [671](#)
  - NasGetLTECphyCaInfo, [528](#)
  - pci, [671](#)
  - scell\_state, [671](#)
  - TlvPresent, [671](#)
- PhysicalLayer
  - protocolSubtypeElement, [694](#)
- PilotEnergy
  - NetworkStatEVDO, [567](#)
- PilotPN
  - PilotSetParams, [672](#)
- PilotSetData, [671](#)
  - NumPilots, [672](#)
  - pPilotSetInfo, [672](#)
- PilotSetParams, [672](#)
  - PilotPN, [672](#)
  - PilotStrength, [672](#)
  - PilotType, [672](#)
- PilotStrength
  - PilotSetParams, [672](#)
- PilotType
  - PilotSetParams, [672](#)
- pin1Len
  - encryptedPIN1, [234](#)
  - uim\_encryptedPIN1, [904](#)
- pin1Retries
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- pin1State
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- pin1Val
  - encryptedPIN1, [234](#)
  - uim\_encryptedPIN1, [904](#)
- pin2Retries
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- pin2State
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- pinID
  - changeUIMPIN, [167](#)
  - setPINProtection, [786](#)
  - uim\_changeUIMPIN, [903](#)
  - uim\_setPINProtection, [909](#)
  - uim\_unblockUIMPIN, [913](#)
  - uim\_verifyUIMPIN, [914](#)
  - unblockUIMPIN, [951](#)
  - verifyUIMPIN, [1098](#)
- pinLen
  - changeUIMPIN, [167](#)
  - uim\_changeUIMPIN, [903](#)
  - uim\_verifyUIMPIN, [914](#)
  - verifyUIMPIN, [1098](#)
- pinLength
  - setPINProtection, [786](#)
  - uim\_setPINProtection, [909](#)
- pinOperation
  - setPINProtection, [786](#)
  - uim\_setPINProtection, [909](#)
- pinProtection
  - pack\_uim\_SetPinProtection\_t, [632](#)
  - pack\_uim\_UnblockPin\_t, [634](#)
  - UIMSetPinProtectionReq, [932](#)
- pinVal
  - changeUIMPIN, [167](#)
  - uim\_changeUIMPIN, [903](#)
  - uim\_verifyUIMPIN, [914](#)
  - verifyUIMPIN, [1098](#)
- pinValue
  - setPINProtection, [786](#)
  - uim\_setPINProtection, [909](#)
- PkQmiNasGetRFBandInfo
  - qaNasGetRFBandInfo.h, [1732](#)
- PkQmiNasPerformNetworkScan
  - qaNasPerformNetworkScan.h, [1733](#)
- PkgDescLength
  - unpack\_swioma\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- PkgDescription
  - unpack\_swioma\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- PkgName
  - unpack\_swioma\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- PkgNameLength
  - unpack\_swioma\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- pkgver
  - CurrentImgList, [190](#)
  - unpack\_dms\_SLQSSwiGetFirmwareCurr\_t, [974](#)
- PktErrRate
  - unpack\_qos\_swiQosFlow\_t, [1048](#)
- pktErrRate, [672](#)
  - exponent, [673](#)
  - multiplier, [673](#)
- PktStatElmntsV4
  - WdsPktStatisticsResp, [1200](#)
- PktStatElmntsV6
  - WdsPktStatisticsResp, [1200](#)
- plmn
  - GERANInfo, [251](#)
  - LTEInfoIntrafreq, [411](#)
  - nas\_GERANInfo, [455](#)
  - nas\_LTEInfoIntrafreq, [476](#)
  - nas\_UMTSInfo, [511](#)
  - UMTSInfo, [940](#)



- polarityIncluded
  - lineCtrlInfo, [375](#)
- Port, [675](#)
  - port, [676](#)
  - range, [676](#)
- port
  - Port, [676](#)
  - unpack\_qos\_Port\_t, [1030](#)
- Position Determination Service (PDS), [37](#)
- pprofileid3gpp
  - pack\_wds\_SLQSSStartDataSession\_t, [653](#)
- pprofileid3gpp2
  - pack\_wds\_SLQSSStartDataSession\_t, [653](#)
- prDNSIPv4Address
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings-\_t, [1089](#)
- prDNSIPv6Address
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings-\_t, [1089](#)
- prPCSCFIPv4Address
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings-\_t, [1089](#)
- prPCSCFIPv6Address
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings-\_t, [1089](#)
- Precedence
  - unpack\_qos\_swiQosFilter\_t, [1043](#)
- precedenceClass
  - GPRSQoS, [288](#)
  - GPRSRequestedQoS, [289](#)
  - LibPackGPRSRequestedQoS, [342](#)
  - wds\_GPRSQoS, [1177](#)
- precisionDilution
  - qaGobiApiCbk.h, [1311](#)
- precisionDilution\_s, [676](#)
  - HDOP, [677](#)
  - PDOP, [677](#)
  - VDOP, [677](#)
- PrefImageList, [677](#)
  - listEntries, [677](#)
  - listSize, [677](#)
- prefNetwork
  - unpack\_wds\_SLQSGetCurrDataSystemStat\_t, [1079](#)
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- prefVoiceSO, [677](#)
  - evrcCapability, [679](#)
  - homeOrigVoiceSO, [679](#)
  - homePageVoiceSO, [679](#)
  - namID, [679](#)
  - roamOrigVoiceSO, [679](#)
- Preferred
  - nas\_QmiNas3GppNetworkInfo, [491](#)
  - SlqsNas3GppNetworkInfo, [808](#)
- prefixLen
  - IPv6Addr, [339](#)
  - unpack\_qos\_IPv6Addr\_t, [1029](#)
- presentationInd
  - ECTNum, [233](#)
  - remotePartyNum, [740](#)
- priChA
  - CDMAChannel, [152](#)
- priChB
  - CDMAChannel, [152](#)
- priSize
  - unpack\_dms\_GetFirmwareRevisions\_t, [959](#)
- pridns
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- pridnsv6
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- primaryDNS
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
- PrimaryDNSV4
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- PrimaryDNSV6
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- primaryHA
  - unpack\_wds\_GetMobileIPProfile\_t, [1074](#)
- privacyPref
  - voiceSetPrefPrivacy, [1151](#)
- priver
  - CurrentImgList, [190](#)
  - unpack\_dms\_SLQSSwiGetFirmwareCurr\_t, [974](#)
- priversion\_str
  - slqsfwinfo\_s, [806](#)
  - unpack\_dms\_GetFirmwareInfo\_t, [958](#)
- Profile
  - GetAudioPathConfigReq, [255](#)
  - GetAudioProfileResp, [259](#)
  - GetAudioVolTLBConfigReq, [260](#)
  - GetM2MAudioProfileResp, [277](#)
  - GetM2MAudioVolumeReq, [278](#)
  - GetM2MAVMuteReq, [279](#)
  - GetM2MSpkrGainReq, [280](#)
  - SetAudioPathConfigReq, [770](#)
  - SetAudioProfileReq, [771](#)
  - SetAudioVolTLBConfigReq, [773](#)
  - SetM2MAudioAVCFGReq, [781](#)
  - SetM2MAudioProfileReq, [783](#)
  - SetM2MAudioVolumeReq, [783](#)
  - SetM2MAVMuteReq, [784](#)
  - SetM2MSpkrGainReq, [785](#)
- Profile3GPP, [680](#)
  - pAPNClass, [685](#)
  - pAPNDisabledFlag, [685](#)
  - pAPNName, [685](#)
  - pAPNnameSize, [685](#)
  - pAddrAllocPref, [685](#)
  - pAuthenticationPref, [685](#)
  - pGPRSMinimumQoS, [685](#)
  - pGPRSRequestedQos, [685](#)
  - pIPv4AddrPref, [685](#)
  - pIPv6AddrPref, [685](#)
  - pImCnFlag, [685](#)
  - pPDNInactivTimeout, [685](#)



- pPDType, [686](#)
- pPassword, [685](#)
- pPasswordSize, [685](#)
- pPcscfAddrUsingDhcp, [685](#)
- pPcscfAddrUsingPCO, [685](#)
- pPdpAccessConFlag, [685](#)
- pPdpContext, [685](#)
- pPdpDataCompType, [686](#)
- pPdpHdrCompType, [686](#)
- pPriDNSIPv4AddPref, [686](#)
- pPriDNSIPv6addpref, [686](#)
- pPrimaryID, [686](#)
- pProfileName, [686](#)
- pProfileNameSize, [686](#)
- pQosClassID, [686](#)
- pSecDNSIPv4AddPref, [686](#)
- pSecDNSIPv6addpref, [686](#)
- pSecondaryFlag, [686](#)
- pTFTID1Params, [686](#)
- pTFTID2Params, [686](#)
- pUMTSMinQoS, [686](#)
- pUMTSMinQoSsigInd, [686](#)
- pUMTSReqQoS, [686](#)
- pUMTSReqQoSsigInd, [686](#)
- pUsername, [686](#)
- pUsernameSize, [686](#)
- Profile3GPP2, [686](#)
  - pAPNClass3GPP2, [691](#)
  - pAPNEnabled3GPP2, [691](#)
  - pAllowLinger, [691](#)
  - pApnString, [691](#)
  - pApnStringSize, [691](#)
  - pAppPriority, [691](#)
  - pAppType, [691](#)
  - pAuthPassword, [691](#)
  - pAuthPasswordSize, [691](#)
  - pAuthProtocol, [691](#)
  - pAuthRetryCount, [691](#)
  - pAuthTimeout, [691](#)
  - pDataMode, [692](#)
  - pDataRate, [692](#)
  - plpcpAckTimeout, [692](#)
  - plpcpCreqRetryCount, [692](#)
  - plsPcscfAddressNedded, [692](#)
  - pLcpAckTimeout, [692](#)
  - pLcpCreqRetryCount, [692](#)
  - pNegoDnsSrvrPref, [692](#)
  - pPDNInactivTimeout3GPP2, [692](#)
  - pPdnType, [692](#)
  - pPppSessCloseTimer1x, [692](#)
  - pPppSessCloseTimerDO, [692](#)
  - pPriV6DnsAddress, [692](#)
  - pPrimaryV4DnsAddress, [692](#)
  - pRATType, [692](#)
  - pSecV6DnsAddress, [692](#)
  - pSecondaryV4DnsAddress, [692](#)
  - pUserId, [692](#)
  - pUserIdSize, [692](#)
- ProfileID
  - \_GetProfileSettingIn, [57](#)
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- ProfileId
  - pack\_wds\_SLQSGetProfileSettings\_t, [645](#)
- profileId
  - WdsDHCPv4ProfileId, [1195](#)
  - wdsDhcpv4ProfileId, [1194](#)
- ProfileId3GPP2
  - unpack\_qos\_swiQosFlow\_t, [1048](#)
- ProfileIdentifier, [692](#)
  - profileIndex, [693](#)
  - profileType, [693](#)
- ProfileIndex
  - PackCreateProfileOut, [654](#)
- profileIndex
  - pack\_wds\_SLQSDeleteProfile\_t, [643](#)
  - ProfileIdentifier, [693](#)
  - SLQSDeleteProfileParams, [805](#)
  - wds\_ProfileIdentifier, [1181](#)
- profileList
  - pack\_wds\_SLQSSet3GPPConfigItem\_t, [649](#)
  - unpack\_wds\_SLQSGet3GPPConfigItem\_t, [1078](#)
- ProfileName
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- ProfileType
  - \_GetProfileSettingIn, [57](#)
  - pack\_wds\_SLQSGetProfileSettings\_t, [645](#)
  - PackCreateProfileOut, [654](#)
  - unpack\_wds\_SLQSGetProfileSettings\_t, [1081](#)
- profileType
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
  - pack\_wds\_SLQSDeleteProfile\_t, [643](#)
  - ProfileIdentifier, [693](#)
  - SLQSDeleteProfileParams, [805](#)
  - wds\_ProfileIdentifier, [1181](#)
  - WdsDHCPv4ProfileId, [1195](#)
  - wdsDhcpv4ProfileId, [1194](#)
- profiletype
  - pack\_wds\_GetDefaultProfile\_t, [637](#)
- Protocol
  - unpack\_nas\_GetCDMANetworkParameters\_t, [990](#)
- protocolSubtypeElement, [693](#)
  - AccessMac, [694](#)
  - AuthProt, [694](#)
  - ControlMac, [694](#)
  - EncryptProt, [694](#)
  - ForwardMac, [694](#)
  - IdleState, [694](#)
  - KeyExchange, [694](#)
  - MultDisc, [694](#)
  - PhysicalLayer, [694](#)
  - ReverseMac, [694](#)
  - SecProt, [694](#)
  - VirtStream, [694](#)
- ProvisionStatus
  - CLIPResp, [169](#)
  - CLIRResp, [170](#)

- CNAPResp, [173](#)
- COLPResp, [174](#)
- COLRResp, [175](#)
- psAttachState
  - nas\_servSystem, [498](#)
  - NASServingSystemInfo, [552](#)
  - ServingSystemInfo, [764](#)
  - servSystem, [766](#)
- psBarStatus
  - CallBarringSysInfo, [129](#)
  - callBarStatus, [130](#)
  - nas\_CallBarringSysInfo, [435](#)
  - nas\_callBarStatus, [436](#)
- psState
  - CommInfo, [177](#)
  - nas\_CommInfo, [446](#)
- psc
  - nas\_UMTSInfo, [511](#)
  - nas\_wcdmaCellInfo, [516](#)
  - nas\_WCDMASysInfo, [523](#)
  - UMTSInfo, [940](#)
  - wcdmaCellInfo, [1161](#)
  - WCDMASysInfo, [1172](#)
- pscValid
  - nas\_WCDMASysInfo, [523](#)
  - WCDMASysInfo, [1172](#)
- pcscfIPv4Addr
  - PCSCFIPv4ServerAddressList, [659](#)
  - wds\_PCSCFIPv4ServerAddressList, [1180](#)
- psid
  - pack\_wds\_SLQSSStopDataSession\_t, [654](#)
  - unpack\_wds\_SLQSSStartDataSession\_t, [1087](#)
- puk1Retries
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- puk2Retries
  - appStats, [108](#)
  - appStatus, [112](#)
  - uim\_appStatus, [900](#)
- pukLen
  - uim\_unblockUIMPIN, [913](#)
  - unblockUIMPIN, [951](#)
- pukVal
  - uim\_unblockUIMPIN, [913](#)
  - unblockUIMPIN, [951](#)
- pv4sessionId
  - WdsIpAddressInfoReq, [1196](#)
- pv6sessionId
  - WdsIpAddressInfoReq, [1196](#)
- pwrDenialTime
  - lineCtrlInfo, [375](#)
- QMI\_SAR\_RF\_STATE\_1
  - qaGobiApiSar.h, [1554](#)
- QMI\_SAR\_RF\_STATE\_2
  - qaGobiApiSar.h, [1555](#)
- QMI\_SAR\_RF\_STATE\_3
  - qaGobiApiSar.h, [1555](#)
- QMI\_SAR\_RF\_STATE\_4
  - qaGobiApiSar.h, [1555](#)
- QMI\_SAR\_RF\_STATE\_5
  - qaGobiApiSar.h, [1555](#)
- QMI\_SAR\_RF\_STATE\_6
  - qaGobiApiSar.h, [1555](#)
- QMI\_SAR\_RF\_STATE\_7
  - qaGobiApiSar.h, [1555](#)
- QMI\_SAR\_RF\_STATE\_8
  - qaGobiApiSar.h, [1555](#)
- QMI\_SAR\_RF\_STATE\_DEFAULT
  - qaGobiApiSar.h, [1554](#)
- QMI\_WDS\_CURRENT\_CALL\_DB\_MASK
  - qaGobiApiWds.h, [1689](#)
- QMI\_WDS\_LAST\_CALL\_DB\_MASK
  - qaGobiApiWds.h, [1689](#)
- QCI
  - LibPackQosClassID, [369](#)
  - QosClassID, [728](#)
- QCWWAN2kConnect
  - qaGobiApiDcs.h, [1392](#)
- QCWWAN2kEnumerateDevices
  - qaGobiApiDcs.h, [1393](#)
- QCWWAN2kGetConnectedDeviceId
  - qaGobiApiDcs.h, [1393](#)
- QCWWANConnect
  - qaGobiApiDcs.h, [1394](#)
- QCWWANDisconnect
  - qaGobiApiDcs.h, [1394](#)
- QCWWANEnumerateDevices
  - qaGobiApiDcs.h, [1394](#)
- QFlowState
  - unpack\_qos\_QosFlowInfo\_t, [1032](#)
- QLIC
  - DeviceConfigDetail, [216](#)
- qaCbkCatEventReportInd.h
  - eTLV\_CBK\_ALPHA\_IDENTIFIER, [1288](#)
  - eTLV\_CBK\_DISPLAY\_TEXT, [1288](#)
  - eTLV\_CBK\_END\_PROACTIVE\_SESSION, [1289](#)
  - eTLV\_CBK\_GET\_IN\_KEY, [1288](#)
  - eTLV\_CBK\_GET\_INPUT, [1288](#)
  - eTLV\_CBK\_LANGUAGE\_NOTIFICATION, [1289](#)
  - eTLV\_CBK\_REFRESH, [1289](#)
  - eTLV\_CBK\_SELECT\_ITEM, [1288](#)
  - eTLV\_CBK\_SETUP\_EVENT\_LIST, [1289](#)
  - eTLV\_CBK\_SETUP\_IDLE\_MODE\_TEXT, [1289](#)
  - eTLV\_CBK\_SETUP\_MENU, [1288](#)
  - eTLV\_END\_PROACTIVE\_SESSION\_LENGTH, [1289](#)
  - eTLV\_REFRESH\_LENGTH, [1289](#)
  - eTLV\_SETUP\_EVENT\_LIST\_LENGTH, [1289](#)
- qaCbkSwiOmaDmEventReportInd.h
  - eTLV\_IND\_OMA\_DM\_CONFIG, [1290](#)
  - eTLV\_IND\_OMA\_DM\_FOTA, [1290](#)
  - eTLV\_IND\_OMA\_DM\_NOT, [1290](#)
- qaGobiApiCbk.h
  - DEVICE\_STATE\_BOOT, [1349](#)
  - DEVICE\_STATE\_DISCONNECTED, [1349](#)

- DEVICE\_STATE\_READY, [1349](#)
- eQA\_QMI\_SVC\_NA, [1349](#)
- eQA\_QMI\_SVC\_NAS, [1349](#)
- eQA\_QMI\_SVC\_WDS, [1349](#)
- SMS\_EVENT\_ETWS, [1350](#)
- SMS\_EVENT\_ETWS\_PLMN, [1350](#)
- SMS\_EVENT\_MESSAGE\_MODE, [1349](#)
- SMS\_EVENT\_MT\_MESSAGE, [1349](#)
- SMS\_EVENT\_SMS\_ON\_IMS, [1350](#)
- SMS\_EVENT\_SMSC\_ADDRESS, [1350](#)
- SMS\_EVENT\_TRANSFER\_ROUTE\_MT\_MESSAGE, [1349](#)
- qaGobiApiFms.h
  - eGOBI\_DEV\_SERIES\_9X15, [1449](#)
  - eGOBI\_DEV\_SERIES\_9X30, [1449](#)
  - eGOBI\_DEV\_SERIES\_G3K, [1449](#)
  - eGOBI\_DEV\_SERIES\_NON\_GOBI, [1449](#)
  - eGOBI\_DEV\_SERIES\_SIERRA\_GOBI, [1449](#)
  - eGOBI\_DEV\_SERIES\_UNKNOWN, [1449](#)
  - eGOBI\_IMG\_CAR\_3, [1450](#)
  - eGOBI\_IMG\_CAR\_AERIS, [1450](#)
  - eGOBI\_IMG\_CAR\_ALLTEL, [1450](#)
  - eGOBI\_IMG\_CAR\_AMX\_TELCEL, [1450](#)
  - eGOBI\_IMG\_CAR\_ATT, [1450](#)
  - eGOBI\_IMG\_CAR\_BELL, [1450](#)
  - eGOBI\_IMG\_CAR\_BHARTI, [1450](#)
  - eGOBI\_IMG\_CAR\_BRASIL\_VIVO, [1450](#)
  - eGOBI\_IMG\_CAR\_CHINA\_MOBILE, [1450](#)
  - eGOBI\_IMG\_CAR\_CHINA\_TELECOM, [1450](#)
  - eGOBI\_IMG\_CAR\_CHINA\_UNICOM, [1450](#)
  - eGOBI\_IMG\_CAR\_EMOBILE, [1450](#)
  - eGOBI\_IMG\_CAR\_FACTORY, [1450](#)
  - eGOBI\_IMG\_CAR\_GENERIC, [1450](#)
  - eGOBI\_IMG\_CAR\_GENERIC\_CDMA, [1450](#)
  - eGOBI\_IMG\_CAR\_IUSACELL, [1450](#)
  - eGOBI\_IMG\_CAR\_KDDI, [1450](#)
  - eGOBI\_IMG\_CAR\_KT\_FREETEL, [1450](#)
  - eGOBI\_IMG\_CAR\_LEAP, [1450](#)
  - eGOBI\_IMG\_CAR\_METROPCS, [1450](#)
  - eGOBI\_IMG\_CAR\_NETCOM, [1450](#)
  - eGOBI\_IMG\_CAR\_NORF, [1450](#)
  - eGOBI\_IMG\_CAR\_NTT\_DOCOMO, [1450](#)
  - eGOBI\_IMG\_CAR\_O2, [1450](#)
  - eGOBI\_IMG\_CAR\_OMH, [1450](#)
  - eGOBI\_IMG\_CAR\_ORANGE, [1450](#)
  - eGOBI\_IMG\_CAR\_RELIANCE1, [1450](#)
  - eGOBI\_IMG\_CAR\_RELIANCE2, [1450](#)
  - eGOBI\_IMG\_CAR\_ROGERS, [1450](#)
  - eGOBI\_IMG\_CAR\_SFR, [1450](#)
  - eGOBI\_IMG\_CAR\_SINGTEL\_OPTUS, [1450](#)
  - eGOBI\_IMG\_CAR\_SK\_TELCOM1, [1450](#)
  - eGOBI\_IMG\_CAR\_SK\_TELCOM2, [1450](#)
  - eGOBI\_IMG\_CAR\_SOFTBANK, [1450](#)
  - eGOBI\_IMG\_CAR\_SPRINT, [1450](#)
  - eGOBI\_IMG\_CAR\_SWISSCOM, [1450](#)
  - eGOBI\_IMG\_CAR\_TATA, [1450](#)
  - eGOBI\_IMG\_CAR\_TELCOM\_ITALIA, [1450](#)
  - eGOBI\_IMG\_CAR\_TELCOM\_NZ, [1450](#)
  - eGOBI\_IMG\_CAR\_TELEFONICA, [1450](#)
  - eGOBI\_IMG\_CAR\_TELNOR, [1450](#)
  - eGOBI\_IMG\_CAR\_TELIASONERA, [1450](#)
  - eGOBI\_IMG\_CAR\_TELSTRA1, [1450](#)
  - eGOBI\_IMG\_CAR\_TELSTRA2, [1450](#)
  - eGOBI\_IMG\_CAR\_TELUS, [1450](#)
  - eGOBI\_IMG\_CAR\_TMOBILE, [1450](#)
  - eGOBI\_IMG\_CAR\_US, [1450](#)
  - eGOBI\_IMG\_CAR\_VERIZON, [1450](#)
  - eGOBI\_IMG\_CAR\_VODAFONE, [1450](#)
  - eGOBI\_IMG\_GPS\_ASSISTED, [1451](#)
  - eGOBI\_IMG\_GPS\_NO\_XTRA, [1451](#)
  - eGOBI\_IMG\_GPS\_NONE, [1451](#)
  - eGOBI\_IMG\_GPS\_STAND\_ALONE, [1451](#)
  - eGOBI\_IMG\_REG\_ASIA, [1451](#)
  - eGOBI\_IMG\_REG\_AUS, [1451](#)
  - eGOBI\_IMG\_REG\_EU, [1451](#)
  - eGOBI\_IMG\_REG\_GLOBAL, [1451](#)
  - eGOBI\_IMG\_REG\_LA, [1451](#)
  - eGOBI\_IMG\_REG\_NA, [1451](#)
  - eGOBI\_IMG\_TECH\_CDMA, [1451](#)
  - eGOBI\_IMG\_TECH\_UMTS, [1451](#)
  - eGobi\_DEV\_SERIES\_MC83, [1449](#)
- qaGobiApiNas.h
  - eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_100, [1492](#)
  - eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_15, [1492](#)
  - eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_25, [1492](#)
  - eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_50, [1492](#)
  - eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_6, [1492](#)
  - eNAS\_LTE\_CPHY\_CA\_BW\_NRB\_75, [1492](#)
  - eNAS\_LTE\_CPHY\_SCELL\_STATE\_CONFIGURED\_ACTIVATED, [1493](#)
  - eNAS\_LTE\_CPHY\_SCELL\_STATE\_CONFIGURED\_DEACTIVATED, [1493](#)
  - eNAS\_LTE\_CPHY\_SCELL\_STATE\_DECONFIGURED, [1493](#)
  - eNAS\_RADIO\_IF\_GSM, [1492](#)
  - eNAS\_RADIO\_IF\_LTE, [1492](#)
  - eNAS\_RADIO\_IF\_TDSCDMA, [1492](#)
  - eNAS\_RADIO\_IF\_UMTS, [1492](#)
  - eSYS\_SRV\_DOMAIN\_CAMPED, [1492](#)
  - eSYS\_SRV\_DOMAIN\_CS\_ONLY, [1492](#)
  - eSYS\_SRV\_DOMAIN\_CS\_PS, [1492](#)
  - eSYS\_SRV\_DOMAIN\_NO\_SRV, [1492](#)
  - eSYS\_SRV\_DOMAIN\_PS\_ONLY, [1492](#)
  - eSYS\_SRV\_DOMAIN\_UNKNOWN, [1492](#)
- qaGobiApiPds.h
  - eSetServiceAutomaticTrackingDisable, [1529](#)
  - eSetServiceAutomaticTrackingEnable, [1529](#)
- qaGobiApiSar.h
  - QMI\_SAR\_RF\_STATE\_1, [1554](#)
  - QMI\_SAR\_RF\_STATE\_2, [1555](#)
  - QMI\_SAR\_RF\_STATE\_3, [1555](#)
  - QMI\_SAR\_RF\_STATE\_4, [1555](#)
  - QMI\_SAR\_RF\_STATE\_5, [1555](#)
  - QMI\_SAR\_RF\_STATE\_6, [1555](#)
  - QMI\_SAR\_RF\_STATE\_7, [1555](#)
  - QMI\_SAR\_RF\_STATE\_8, [1555](#)

- QMI\_SAR\_RF\_STATE\_DEFAULT, 1554
- qaGobiApiVoice.h
  - VOICE\_SUPS\_SRV\_CLASS\_DATA, 1657
  - VOICE\_SUPS\_SRV\_CLASS\_DATACIRCUITASYNC, 1658
  - VOICE\_SUPS\_SRV\_CLASS\_DATACIRCUITSYN-C, 1657
  - VOICE\_SUPS\_SRV\_CLASS\_FAX, 1657
  - VOICE\_SUPS\_SRV\_CLASS\_NONE, 1657
  - VOICE\_SUPS\_SRV\_CLASS\_PACKETACCESS, 1658
  - VOICE\_SUPS\_SRV\_CLASS\_PADACCESS, 1658
  - VOICE\_SUPS\_SRV\_CLASS\_SMS, 1657
  - VOICE\_SUPS\_SRV\_CLASS\_VOICE, 1657
- qaGobiApiWds.h
  - QMI\_WDS\_CURRENT\_CALL\_DB\_MASK, 1689
  - QMI\_WDS\_LAST\_CALL\_DB\_MASK, 1689
- qaNasGetRFBandInfo.h
  - eTLV\_RF\_BAND\_INFO, 1732
- qaNasPerformNetworkScan.h
  - eTLV\_3GPP\_NETWORK\_INFO, 1733
- qaCbkCatEventReportInd.h, 1287
  - UpkQmiCbkCatEventReportInd, 1289
- qaCbkSwiOmaDmEventReportInd.h, 1289
  - UpkQmiCbkSwiOmaDmEventReportInd, 1290
  - UpkQmiCbkSwiOmaDmEventReportIndExt, 1290
- qaGobiApiAudio.h, 1290
  - SLQSGetAudioPathConfig, 1291
  - SLQSGetAudioProfile, 1291
  - SLQSGetAudioVoITLBConfig, 1292
  - SLQSSetAudioPathConfig, 1292
  - SLQSSetAudioProfile, 1293
  - SLQSSetAudioVoITLBConfig, 1293
- qaGobiApiCat.h, 1294
  - CATSendEnvelopeCommand, 1294
  - CATSendTerminalResponse, 1295
- qaGobiApiCbk.h, 1296
  - accelAcceptReady, 1305
  - accelTempAcceptReady, 1305
  - CBK\_ENABLE\_EVENT, 1303
  - CBK\_NOCHANGE, 1303
  - DEREGISTER\_EVENT, 1303
  - DEREGISTER\_SRV, 1303
  - device\_state\_enum, 1349
  - eDevState, 1306
  - eQaQMIService, 1349
  - eSMSEventType, 1306
  - EVENT\_MASK\_CARD, 1303
  - FIRST\_INSTANCE, 1304
  - gpsTime, 1306
  - gyroAcceptReady, 1306
  - gyroTempAcceptReady, 1308
  - INVALID\_INSTACNE, 1304
  - IPV4, 1304
  - IPV4V6, 1304
  - IPV6, 1304
  - iSLQSSetDUNCallInfoCallback, 1350
  - iSLQSSetSignalStrengthsCallback, 1350
  - iSLQSSetWdsFirstInstEventCallback, 1350
  - iSLQSSetWdsSecondInstEventCallback, 1350
  - iSLQSSetWdsThirdInstEventCallback, 1350
  - iSLQSSetWdsXferStatsFirstInstCallback, 1350
  - iSLQSSetWdsXferStatsSecondInstCallback, 1350
  - iSetCATEventCallback, 1350
  - iSetSignalStrengthCallback, 1350
  - LteNasReleaseInfo, 1308
  - MAX\_NO\_OF\_CALLS, 1304
  - MAX\_NO\_OF\_FILES, 1304
  - MAX\_NO\_OF\_SLOTS, 1304
  - MAX\_PATH\_LENGTH, 1304
  - MAXUSSDLENGTH, 1304
  - modemTempNotification, 1309
  - NAS\_SRV, 1304
  - NUM\_OF\_SET, 1304
  - PDS\_SRV, 1304
  - packetSrvStatus, 1309
  - precisionDilution, 1311
  - REGISTER\_EVENT, 1304
  - REGISTER\_SRV, 1305
  - ResetInfoNotification, 1312
  - SECOND\_INSTANCE, 1305
  - SLQSNasNetworkTimeCallBack, 1365
  - SLQSNasSigInfo2CallBack, 1365
  - SLQSNasSigInfoCallBack, 1366
  - SLQSNasSwiOTAMessageCallback, 1366
  - SLQSNasSysInfoCallBack, 1367
  - SLQSSetBandPreferenceCbk, 1367
  - SLQSSetDHCPv4ClientLeaseStatusCallback, 1369
  - SLQSSetDUNCallInfoCallback, 1369
  - SLQSSetDataSystemStatusCallback, 1367
  - SLQSSetIMSAPdpStatusCallback, 1370
  - SLQSSetIMSARatStatusCallback, 1370
  - SLQSSetIMSARegStatusCallback, 1370
  - SLQSSetIMSASvcStatusCallback, 1371
  - SLQSSetIMSSMSConfigCallback, 1371
  - SLQSSetIMSUserConfigCallback, 1372
  - SLQSSetIMSVoIPConfigCallback, 1372
  - SLQSSetLocInjectPositionCallback, 1372
  - SLQSSetLocInjectUTCTimeCallback, 1373
  - SLQSSetModemTempCallback, 1373
  - SLQSSetPacketSrvStatusCallback, 1373
  - SLQSSetQosEventCallback, 1374
  - SLQSSetQosNWStatusCallback, 1374
  - SLQSSetQosPriEventCallback, 1374
  - SLQSSetQosStatusCallback, 1376
  - SLQSSetRegMgrConfigCallback, 1376
  - SLQSSetSDKTerminatedCallback, 1377
  - SLQSSetSIPConfigCallback, 1378
  - SLQSSetSMSEventCallback, 1380
  - SLQSSetServingSystemCallback, 1377
  - SLQSSetSessionStateCallback, 1377
  - SLQSSetSignalStrengthsCallback, 1378
  - SLQSSetSwiGetResetInfoCallback, 1380
  - SLQSSetSwiHDRPersCallback, 1380
  - SLQSSetSysSelectionPrefCallBack, 1381

- SLQSSetTransLayerInfoCallback, [1381](#)
- SLQSSetTransNWRegInfoCallback, [1381](#)
- SLQSSetWdsEventCallback, [1383](#)
- SLQSSetWdsTransferStatisticCallback, [1384](#)
- SLQSTmdMitigationLvlRptCallback, [1384](#)
- SLQSUIMSetRefreshCallBack, [1385](#)
- SLQSUIMSetStatusChangeCallBack, [1385](#)
- SLQSVoiceInfoRecCallback, [1385](#)
- SLQSVoiceSetAllCallStatusCallBack, [1386](#)
- SLQSVoiceSetDTMFEventCallBack, [1386](#)
- SLQSVoiceSetOTASPStatusCallBack, [1387](#)
- SLQSVoiceSetPrivacyChangeCallBack, [1387](#)
- SLQSVoiceSetSUPSCallBack, [1387](#)
- SLQSVoiceSetSUPSNotificationCallback, [1389](#)
- SLQSWmsAsyncRawSendCallBack, [1389](#)
- SLQSWmsMemoryFullCallBack, [1390](#)
- SLQSWmsMessageWaitingCallBack, [1390](#)
- SMSAsyncRawSend, [1313](#)
- SMSCAddressInfo, [1315](#)
- SMSEtwsMessageInfo, [1315](#)
- SMSEtwsPlmnInfo, [1315](#)
- SMSEventInfo, [1315](#)
- SMSEventType, [1349](#)
- SMSMTMessageInfo, [1317](#)
- SMSMessageModelInfo, [1317](#)
- SMSOnIMSInfo, [1318](#)
- SMSTransferRouteMTMessageInfo, [1318](#)
- sensorDataUsage, [1313](#)
- sessionInformation, [1313](#)
- sessionInformationExt, [1313](#)
- SetActivationStatusCallback, [1350](#)
- SetCATEventCallback, [1350](#)
- SetDataCapabilitiesCallback, [1352](#)
- SetDeviceStateChangeCb, [1352](#)
- SetFwDldCompletionCb, [1352](#)
- SetGPSCallback, [1353](#)
- SetLURRejectCallback, [1357](#)
- SetLocCradleMountCallback, [1353](#)
- SetLocDeleteAssistDataCallback, [1353](#)
- SetLocEngineStateCallback, [1355](#)
- SetLocEventPositionCallback, [1355](#)
- SetLocEventTimeSyncCallback, [1355](#)
- SetLocGnssSvInfoCallback, [1355](#)
- SetLocInjectSensorDataCallback, [1356](#)
- SetLocInjectTimeCallback, [1356](#)
- SetLocOpModeCallback, [1356](#)
- SetLocSensorStreamingCallback, [1357](#)
- SetLocSetExtPowerConfigCallback, [1357](#)
- SetMobileIPStatusCallback, [1358](#)
- SetNMEACallback, [1359](#)
- SetNasLTECphyCalndCallback, [1358](#)
- SetNetChangeCb, [1358](#)
- SetNewSMSCallback, [1359](#)
- SetOMADMStateCallback, [1360](#)
- SetPDSSStateCallback, [1360](#)
- SetPowerCallback, [1360](#)
- SetRFInfoCallback, [1361](#)
- SetRMTransferStatisticsCallback, [1361](#)
- SetRankIndicatorCallback, [1361](#)
- SetRoamingIndicatorCallback, [1361](#)
- SetSLQSOMADMAAlertCallback, [1363](#)
- SetSLQSOMADMAAlertCallbackExt, [1363](#)
- SetSignalStrengthCallback, [1362](#)
- SetUSSDNoWaitIndicationCallback, [1364](#)
- SetUSSDNotificationCallback, [1364](#)
- SetUSSDReleaseCallback, [1364](#)
- SetUimSlotStatusChangeCallback, [1363](#)
- svUsedforFix, [1318](#)
- SwiOTAMsg, [1319](#)
- tFNASwiLTECphyCallInfo, [1320](#)
- tFNASwiOTAMsg, [1320](#)
- tFNActivationStatus, [1319](#)
- tFNAllCallStatus, [1320](#)
- tFNAsyncRawSend, [1320](#)
- tFNBandPreference, [1322](#)
- tFNCATEvent, [1324](#)
- tFNCbkUimSlotStatusChangeInd, [1324](#)
- tFNDHCPv4ClientLeaseStatus, [1326](#)
- tFNDTMFEvent, [1326](#)
- tFNDUNCallInfo, [1326](#)
- tFNDataCapabilities, [1324](#)
- tFNDataSysStatus, [1325](#)
- tFNDeIAssistData, [1325](#)
- tFNDeviceStateChange, [1325](#)
- tFNEventPosition, [1326](#)
- tFNFwDldCompletion, [1326](#)
- tFNGnssSvInfo, [1327](#)
- tFNHDRPersonality, [1327](#)
- tFNImRegMgrConfig, [1328](#)
- tFNImSIPConfig, [1328](#)
- tFNImSMSConfig, [1329](#)
- tFNImUserConfig, [1329](#)
- tFNImVoIPConfig, [1329](#)
- tFNImsaPdpStatus, [1327](#)
- tFNImsaRatStatus, [1328](#)
- tFNImsaRegStatus, [1328](#)
- tFNImsaSvcStatus, [1328](#)
- tFNInfoRec, [1329](#)
- tFNInjectPosition, [1329](#)
- tFNInjectSensorData, [1330](#)
- tFNInjectTimeStatus, [1330](#)
- tFNInjectUTCTime, [1330](#)
- tFNLURReject, [1330](#)
- tFNMemoryFull, [1332](#)
- tFNMessageWaiting, [1332](#)
- tFNMiniLvlRpt, [1332](#)
- tFNMobIPStatus, [1332](#)
- tFNModemTempInfo, [1332](#)
- tFNNet, [1332](#)
- tFNNetworkTime, [1334](#)
- tFNNewGPS, [1334](#)
- tFNNewNMEA, [1335](#)
- tFNNewRMTransferStatistics, [1335](#)
- tFNNewSMS, [1336](#)
- tFNOMADMState, [1336](#)
- tFNOTASPStatus, [1337](#)



- tFNOpMode, [1337](#)
- tFNPDSState, [1339](#)
- tFNPacketSrvState, [1337](#)
- tFNPower, [1339](#)
- tFNPrivacyChange, [1339](#)
- tFNQosNWStatus, [1340](#)
- tFNQosPriEvent, [1340](#)
- tFNQosStatus, [1340](#)
- tFNRFInfo, [1342](#)
- tFNRankIndicator, [1341](#)
- tFNResetInfo, [1341](#)
- tFNRoamingIndicator, [1342](#)
- tFNSDKTerminated, [1342](#)
- tFNSLQSOADMAAlert, [1343](#)
- tFNSLQSQOSEvent, [1344](#)
- tFNSLQSSessionState, [1344](#)
- tFNSLQSSignalStrengths, [1344](#)
- tFNSLQSWDSEvent, [1344](#)
- tFNSMSEvents, [1345](#)
- tFNSUPSInfo, [1345](#)
- tFNSUPSNotification, [1345](#)
- tFNSensorStreaming, [1343](#)
- tFNServingSystem, [1343](#)
- tFNSetCradleMount, [1343](#)
- tFNSetEngineState, [1343](#)
- tFNSetEventTimeSync, [1343](#)
- tFNSetExtPowerConfig, [1343](#)
- tFNSigInfo, [1343](#)
- tFNSignalStrength, [1343](#)
- tFNSysInfo, [1345](#)
- tFNSysSelectionPref, [1345](#)
- tFNUIMRefresh, [1346](#)
- tFNUIMStatusChangeInfo, [1346](#)
- tFNUSSDNoWaitIndication, [1348](#)
- tFNUSSDNotification, [1346](#)
- tFNUSSDRelease, [1348](#)
- tFNtransLayerInfo, [1346](#)
- tFNtransNWRRegInfo, [1346](#)
- THIRD\_INSTANCE, [1305](#)
- transLayerNotification, [1348](#)
- transNWRRegInfoNotification, [1348](#)
- USSD\_DCS\_8BIT, [1305](#)
- USSD\_DCS\_ASCII, [1305](#)
- USSD\_DCS\_UCS2, [1305](#)
- VOICE\_SRV, [1305](#)
- WDS\_SRV, [1305](#)
- qaGobiApiDcs.h, [1391](#)
- LEN, [1391](#)
- PORTNAM\_LEN, [1391](#)
- QCWWAN2kConnect, [1392](#)
- QCWWAN2kEnumerateDevices, [1393](#)
- QCWWAN2kGetConnectedDeviceID, [1393](#)
- QCWWANConnect, [1394](#)
- QCWWANDisconnect, [1394](#)
- QCWWANEnumerateDevices, [1394](#)
- SLQSGetDeviceMode, [1395](#)
- SLQSGetNetStatistic, [1395](#)
- SLQSGetUsbPortNames, [1396](#)
- SLQSKillSDKProcess, [1396](#)
- SLQSQosClearMap, [1397](#)
- SLQSQosDumpMap, [1397](#)
- SLQSQosEditMap, [1397](#)
- SLQSQosMap, [1398](#)
- SLQSQosReadMap, [1398](#)
- SLQSQosUnmap, [1398](#)
- SLQSSetLoggingMask, [1399](#)
- SLQSStart, [1399](#)
- SLQSStart\_AVAgent, [1400](#)
- SLQSStartSrv, [1400](#)
- SetSDKImagePath, [1395](#)
- qaGobiApiDms.h, [1401](#)
- ActivateAutomatic, [1412](#)
- custFeaturesInfo, [1404](#)
- custFeaturesSetting, [1406](#)
- dmsCurrentPRLInfo, [1408](#)
- ERIFileparams, [1408](#)
- GetActivationState, [1412](#)
- GetDeviceCapabilities, [1413](#)
- GetFirmwareRevision, [1414](#)
- GetFirmwareRevisions, [1415](#)
- GetHardwareRevision, [1415](#)
- GetIMSI, [1417](#)
- GetManufacturer, [1417](#)
- GetModelID, [1418](#)
- GetNetworkTime, [1418](#)
- GetOfflineReason, [1419](#)
- GetPRLVersion, [1420](#)
- GetPower, [1420](#)
- GetSerialNumbers, [1421](#)
- GetVoiceNumber, [1422](#)
- IMGDETAILS\_LEN, [1404](#)
- MAX\_CUST\_ID\_LEN, [1404](#)
- MAX\_FSN\_LENGTH, [1404](#)
- ResetToFactoryDefaults, [1422](#)
- SLQSDmsSwiGetResetInfo, [1423](#)
- SLQSDmsSwiIndicationRegister, [1423](#)
- SLQSGetBandCapabilities, [1424](#)
- SLQSGetBandCapability, [1424](#)
- SLQSGetCurrentPRLInfo, [1426](#)
- SLQSGetCustFeatures, [1426](#)
- SLQSGetCustFeaturesV2, [1426](#)
- SLQSGetERIFile, [1427](#)
- SLQSGetSerialNumbers, [1427](#)
- SLQSSetCustFeatures, [1428](#)
- SLQSSetCustFeaturesV2, [1428](#)
- SLQSSwiClearDyingGaspStatistics, [1428](#)
- SLQSSwiGetCrashAction, [1429](#)
- SLQSSwiGetCrashInfo, [1429](#)
- SLQSSwiGetDyingGaspCfg, [1430](#)
- SLQSSwiGetDyingGaspStatistics, [1430](#)
- SLQSSwiGetFSN, [1430](#)
- SLQSSwiGetFirmwareCurr, [1430](#)
- SLQSSwiGetFwUpdateStatus, [1431](#)
- SLQSSwiGetHostDevInfo, [1431](#)
- SLQSSwiGetHostDevInfoParams, [1409](#)
- SLQSSwiGetOSInfo, [1432](#)

- SLQSSwiGetOSInfoParams, [1410](#)
- SLQSSwiGetSerialNoExt, [1432](#)
- SLQSSwiGetSerialNoExtParams, [1410](#)
- SLQSSwiGetUSBComp, [1433](#)
- SLQSSwiSetCrashAction, [1433](#)
- SLQSSwiSetDyingGaspCfg, [1434](#)
- SLQSSwiSetHostDevInfo, [1434](#)
- SLQSSwiSetHostDevInfoParams, [1411](#)
- SLQSSwiSetOSInfo, [1434](#)
- SLQSSwiSetOSInfoParams, [1411](#)
- SLQSSwiSetUSBComp, [1435](#)
- SLQSUIMGetState, [1435](#)
- serialNumbersInfo, [1408](#)
- SetPower, [1423](#)
- UIMChangePIN, [1436](#)
- UIMGetControlKeyStatus, [1437](#)
- UIMGetICCID, [1438](#)
- UIMGetPINStatus, [1439](#)
- UIMSetControlKeyProtection, [1440](#)
- UIMSetPINProtection, [1441](#)
- UIMUnblockControlKey, [1442](#)
- UIMUnblockPIN, [1443](#)
- UIMVerifyPIN, [1444](#)
- UNIQUE\_ID\_LEN, [1404](#)
- ValidateSPC, [1445](#)
- qaGobiApiFms.h, [1446](#)
  - BUILD\_ID\_LEN, [1448](#)
  - DEVICE\_OFFLINE, [1448](#)
  - DEVICE\_RESET, [1448](#)
  - DEVICE\_SHUTDOWN, [1448](#)
  - DeleteStoredImage, [1451](#)
  - eGetDeviceSeries, [1452](#)
  - eGobiDeviceSeries, [1449](#)
  - eGobiImageCarrier, [1449](#)
  - eGobiImageGPS, [1450](#)
  - eGobiImageRegion, [1451](#)
  - eGobiImageTech, [1451](#)
  - GetImageStore, [1452](#)
  - GetImagesPreference, [1452](#)
  - GetStoredImages, [1453](#)
  - IMG\_ID\_LEN, [1449](#)
  - PRI\_UPDATE\_FAIL, [1449](#)
  - SLQSDownloadFirmwareToSlot, [1454](#)
  - SLQSGetBootVersionNumber, [1455](#)
  - SLQSGetFirmwareInfo, [1456](#)
  - SLQSGetImageInfo, [1456](#)
  - SLQSGetImageInfo\_9x15, [1456](#)
  - SLQSGetImageInfoMC77xx, [1457](#)
  - SLQSGetImageInfoMC83xx, [1458](#)
  - SLQSGetValidFwPriCombinations, [1458](#)
  - SLQSLsSpkgFormatRequired, [1459](#)
  - SLQSSwiGetAllCarrierImages, [1459](#)
  - SLQSUpgradeFirmware9x15, [1459](#)
  - SetImagesPreference, [1453](#)
  - upgrade\_mc77xx\_fw, [1460](#)
  - UpgradeFirmware2k, [1461](#)
- qaGobiApiIms.h, [1461](#)
  - SLQSGetIMSSMSConfig, [1462](#)
  - SLQSGetIMSUserConfig, [1463](#)
  - SLQSGetIMSVoIPConfig, [1463](#)
  - SLQSGetRegMgrConfig, [1463](#)
  - SLQSGetSIPConfig, [1464](#)
  - SLQSLmsConfigIndicationRegister, [1464](#)
  - SLQSSetIMSSMSConfig, [1465](#)
  - SLQSSetIMSUserConfig, [1465](#)
  - SLQSSetIMSVoIPConfig, [1466](#)
  - SLQSSetRegMgrConfig, [1466](#)
  - SLQSSetSIPConfig, [1467](#)
- qaGobiApiImsa.h, [1467](#)
  - SLQSGetIMSAREgStatus, [1468](#)
  - SLQSGetIMSAServiceStatus, [1468](#)
  - SLQSGetIMSASupportedFields, [1469](#)
  - SLQSGetIMSASupportedMsg, [1469](#)
  - SLQSRegisterIMSIndication, [1470](#)
- qaGobiApiLoc.h, [1470](#)
  - SLQSLOCDeIAssData, [1472](#)
  - SLQSLOCEventRegister, [1472](#)
  - SLQSLOCInjectPosition, [1472](#)
  - SLQSLOCInjectSensorData, [1473](#)
  - SLQSLOCInjectUTCTime, [1473](#)
  - SLQSLOCSetCradleMountConfig, [1474](#)
  - SLQSLOCSetExtPowerState, [1474](#)
  - SLQSLOCSetOpMode, [1474](#)
  - SLQSLOCStart, [1475](#)
  - SLQSLOCStop, [1475](#)
  - SwiLocGetAutoStart, [1476](#)
  - SwiLocSetAutoStart, [1476](#)
- qaGobiApiNas.h, [1477](#)
  - eSYS\_SRV\_DOMAIN, [1492](#)
  - GetACCOLC, [1493](#)
  - GetANAAAAAuthenticationStatus, [1493](#)
  - GetCDMANetworkParameters, [1493](#)
  - GetHomeNetwork, [1496](#)
  - GetHomeNetwork3GPP2, [1497](#)
  - GetNetworkPreference, [1498](#)
  - GetRFInfo, [1499](#)
  - GetServingNetwork, [1500](#)
  - GetServingNetworkCapabilities, [1502](#)
  - GetSignalStrengths, [1503](#)
  - IMSI\_M\_S1\_LENGTH, [1482](#)
  - IMSI\_M\_S2\_LENGTH, [1482](#)
  - InitiateDomainAttach, [1503](#)
  - InitiateNetworkRegistration, [1504](#)
  - MAX\_PILOT\_SETS, [1482](#)
  - NAM\_NAME\_LENGTH, [1482](#)
  - PLMN\_LENGTH, [1482](#)
  - PerformNetworkScan, [1505](#)
  - SLQSConfigSigInfo, [1508](#)
  - SLQSGetErrorRate, [1509](#)
  - SLQSGetNetworkTime, [1509](#)
  - SLQSGetOperatorNameData, [1510](#)
  - SLQSGetPLMNName, [1510](#)
  - SLQSGetServingSystem, [1510](#)
  - SLQSGetSignalStrength, [1511](#)
  - SLQSGetSysSelectionPref, [1511](#)
  - SLQSInitiateNetworkRegistration, [1512](#)

- SLQSNASGetLTECPHYCaInfo, 1514
- SLQSNASSwiGetChannelLock, 1518
- SLQSNASSwiSetChannelLock, 1519
- SLQSNasConfigSigInfo2, 1512
- SLQSNasGet3GPP2Subscription, 1513
- SLQSNasGetCellLocationInfo, 1513
- SLQSNasGetHDRColorCode, 1514
- SLQSNasGetSigInfo, 1514
- SLQSNasGetSysInfo, 1515
- SLQSNasGetTxRxInfo, 1515
- SLQSNasIndicationRegister, 1516
- SLQSNasIndicationRegisterExt, 1517
- SLQSNasIndicationRegisterLTECphyCa, 1518
- SLQSNasSwiIndicationRegister, 1519
- SLQSNasSwiModemStatus, 1519
- SLQSPerformNetworkScan, 1520
- SLQSSetBandPreference, 1520
- SLQSSetSysSelectionPref, 1522
- SLQSSwiGetHDRPersonality, 1522
- SLQSSwiGetHDRProtSubtype, 1522
- SLQSSwiGetHRPDStats, 1523
- SLQSSwiGetLteCQI, 1523
- SLQSSwiNetworkDebug, 1524
- SLQSSwiPSDetach, 1524
- SetACCOLC, 1505
- SetCDMANetworkParameters, 1506
- SetNetworkPreference, 1507
- SlqsNas3GppNetworkRAT, 1482
- slqsNetworkScanInfo, 1483
- sysSelectPrefInfo, 1484
- sysSelectPrefParams, 1487
- UATISIZE, 1482
- qaGobiApiOmadm.h, 1524
  - OMADMCancelSession, 1525
  - OMADMGetPendingNIA, 1525
  - OMADMGetSessionInfo, 1526
  - OMADMStartSession, 1527
- qaGobiApiPds.h, 1528
  - DEFAULTBYTEVALUE, 1529
  - DEFAULTLONGVALUE, 1529
  - DEFAULTWORDVALUE, 1529
  - ForceXTRADownload, 1529
  - GetPDSDDefaults, 1530
  - GetPDSSState, 1530
  - GetPortAutomaticTracking, 1531
  - GetServiceAutomaticTracking, 1531
  - GetXTRAAutomaticDownload, 1533
  - GetXTRANetwork, 1533
  - GetXTRAVality, 1534
  - PDSInjectTimeReference, 1534
  - ResetPDSDData, 1535
  - SLQSGetAGPSConfig, 1539
  - SLQSGetGPSSStateInfo, 1540
  - SLQSPDSDeterminePosition, 1540
  - SLQSPDSInjectAbsoluteTimeReference, 1541
  - SLQSPDSInjectPositionData, 1541
  - SLQSSetAGPSConfig, 1542
  - SLQSSetPositionMethodState, 1542
  - SetPDSDDefaults, 1536
  - SetPDSSState, 1537
  - SetPortAutomaticTracking, 1537
  - SetServiceAutomaticTracking, 1538
  - SetXTRAAutomaticDownload, 1538
  - SetXTRANetwork, 1539
  - StartPDSTrackingSessionExt, 1544
  - StopPDSTrackingSession, 1545
- qaGobiApiQos.h, 1545
  - SLQSQosGetFlowStatus, 1546
  - SLQSQosGetGranted, 1547
  - SLQSQosGetNWProf, 1548
  - SLQSQosGetNetworkStatus, 1547
  - SLQSQosModify, 1548
  - SLQSQosRel, 1549
  - SLQSQosReq, 1549
  - SLQSQosReset, 1550
  - SLQSQosResume, 1550
  - SLQSQosSuspend, 1551
  - SLQSQosSwiReadApnExtraParams, 1551
  - SLQSQosSwiReadDataStats, 1552
- qaGobiApiRms.h, 1552
  - GetSMSWake, 1552
  - SetSMSWake, 1553
- qaGobiApiSar.h, 1554
  - eQMISARRFState, 1554
  - SLQSGetRfSarState, 1555
  - SLQSSetRfSarState, 1555
- qaGobiApiSms.h, 1556
  - ABSOLUTE\_VALIDITY, 1558
  - CONFIG\_LEN, 1558
  - getIndicationRegResp, 1558
  - GetSMSCAddress, 1563
  - getTransLayerInfoResp, 1559
  - getTransNWRegInfoResp, 1560
  - MAX\_SMS\_ROUTES, 1558
  - NUM\_OF\_SET, 1558
  - qaQmi3GPP2BroadcastCfgInfo, 1560
  - qaQmi3GPPBroadcastCfgInfo, 1561
  - SLQSCDMADecodeMTTextMsg, 1566
  - SLQSCDMAEncodeMOTextMsg, 1566
  - SLQSDeleteSMS, 1567
  - SLQSGetIndicationRegister, 1568
  - SLQSGetMessageWaiting, 1569
  - SLQSGetSMS, 1569
  - SLQSGetSMSList, 1571
  - SLQSGetSmsBroadcastConfig, 1570
  - SLQSGetTransLayerInfo, 1572
  - SLQSGetTransNWRegInfo, 1572
  - SLQSModifySMSStatus, 1573
  - SLQSSendAsyncSMS, 1574
  - SLQSSendLongSMS, 1574
  - SLQSSendSMS, 1575
  - SLQSSetIndicationRegister, 1576
  - SLQSSetSmsBroadcastActivation, 1576
  - SLQSSetSmsBroadcastConfig, 1577
  - SLQSSetSmsStorage, 1578
  - SLQSSmsGetMaxStorageSize, 1578



SLQSSmsGetMessageProtocol, [1579](#)  
SLQSSmsSetRoutes, [1579](#)  
SLQSSwiGetSMSSStorage, [1579](#)  
SLQSWCDMADecodeLongTextMsg, [1581](#)  
SLQSWCDMADecodeMTTTextMsg, [1581](#)  
SLQSWCDMAEncodeMOTextMsg, [1582](#)  
SaveSMS, [1563](#)  
SendSMS, [1564](#)  
setIndicationRegReq, [1561](#)  
SetSMSCAddress, [1565](#)  
TIME\_DATE\_BUF, [1558](#)  
TIME\_STAMP\_BUF, [1558](#)  
transLayerInfo, [1562](#)  
qaGobiApiSwi.h, [1582](#)  
SLQSGetPidof, [1583](#)  
SLQSGetSdkVersion, [1583](#)  
SLQSSendRawQMI, [1583](#)  
qaGobiApiSwiAudio.h, [1583](#)  
SLQSGetM2MAVMute, [1585](#)  
SLQSGetM2MAudioProfile, [1584](#)  
SLQSGetM2MAudioVolume, [1585](#)  
SLQSGetM2MSpkrGain, [1586](#)  
SLQSSetM2MAVMute, [1588](#)  
SLQSSetM2MAudioAVCFG, [1586](#)  
SLQSSetM2MAudioLPBK, [1587](#)  
SLQSSetM2MAudioNVDef, [1587](#)  
SLQSSetM2MAudioProfile, [1587](#)  
SLQSSetM2MAudioVolume, [1588](#)  
SLQSSetM2MSpkrGain, [1589](#)  
qaGobiApiSwiOmadms.h, [1589](#)  
SLQSOMADMCancelSession, [1595](#)  
SLQSOMADMGetSessionInfo, [1595](#)  
SLQSOMADMGetSettings, [1596](#)  
SLQSOMADMGetSettings2, [1597](#)  
SLQSOMADMSendSelection, [1597](#)  
SLQSOMADMSendSelection2, [1598](#)  
SLQSOMADMSessionInfo, [1590](#)  
SLQSOMADMSetSettings, [1598](#)  
SLQSOMADMSetSettings2, [1599](#)  
SLQSOMADMSetSettings3, [1599](#)  
SLQSOMADMSettings, [1592](#)  
SLQSOMADMSettingsReqParams, [1593](#)  
SLQSOMADMSettingsReqParams3, [1594](#)  
SLQSOMADMStartSession, [1600](#)  
SLQSOMADMStartSession2, [1600](#)  
qaGobiApiTableBandClasses.h, [1601](#)  
qaGobiApiTableCallControlReturnReasons.h, [1604](#)  
qaGobiApiTableCallEndReasons.h, [1605](#)  
qaGobiApiTableCarrierCodes.h, [1620](#)  
qaGobiApiTableCodingScheme.h, [1622](#)  
qaGobiApiTableGpsCapabilityCodes.h, [1625](#)  
qaGobiApiTablePowerModes.h, [1625](#)  
qaGobiApiTableRadioInterfaces.h, [1626](#)  
qaGobiApiTableRegionCodes.h, [1626](#)  
qaGobiApiTableServiceOptions.h, [1627](#)  
qaGobiApiTableSupServiceInfoClasses.h, [1629](#)  
qaGobiApiTableSwiAudio.h, [1630](#)  
qaGobiApiTableSwiOMADMUpdateCompleteStatus.h, [1630](#)  
qaGobiApiTableVoiceCallEndReasons.h, [1632](#)  
qaGobiApiTmd.h, [1638](#)  
SLQSTmdDeRegNotMitigationLvl, [1639](#)  
SLQSTmdGetMitigationDevList, [1639](#)  
SLQSTmdGetMitigationLvl, [1640](#)  
SLQSTmdRegNotMitigationLvl, [1640](#)  
qaGobiApiUim.h, [1640](#)  
MAX\_ICCID\_LENGTH, [1643](#)  
MAX\_NO\_OF\_SLOTS, [1643](#)  
MAX\_PATH\_LENGTH, [1643](#)  
MAX\_PUK\_LENGTH, [1643](#)  
MAX\_SLOTS\_STATUS, [1643](#)  
SLQSUIMAuthenticate, [1643](#)  
SLQSUIMChangePin, [1643](#)  
SLQSUIMDepersonalization, [1644](#)  
SLQSUIEventRegister, [1644](#)  
SLQSUIMGetCardStatus, [1646](#)  
SLQSUIMGetConfiguration, [1646](#)  
SLQSUIMGetFileAttributes, [1647](#)  
SLQSUIMGetSlotsStatus, [1647](#)  
SLQSUIPowerDown, [1648](#)  
SLQSUIPowerUp, [1648](#)  
SLQSUIReadTransparent, [1649](#)  
SLQSUIRefreshComplete, [1649](#)  
SLQSUIRefreshGetLastEvent, [1650](#)  
SLQSUIRefreshOK, [1650](#)  
SLQSUIRefreshRegister, [1651](#)  
SLQSUIReset, [1651](#)  
SLQSUISetPinProtection, [1652](#)  
SLQSUISwitchSlot, [1652](#)  
SLQSUIUnblockPin, [1653](#)  
SLQSUIVerifyPin, [1653](#)  
qaGobiApiVoice.h, [1654](#)  
AnswerUSSD, [1658](#)  
CancelUSSD, [1658](#)  
MAX\_CALL\_NO\_LEN, [1657](#)  
MAX\_NO\_OF\_CALLS, [1657](#)  
MAXUSSDLENGTH, [1657](#)  
OriginateUSSD, [1658](#)  
PASSWORD\_LENGTH, [1657](#)  
SLQSOriginateUSSD, [1659](#)  
SLQSVoiceALSSelectLine, [1659](#)  
SLQSVoiceALSSetLineSwitching, [1660](#)  
SLQSVoiceAnswerCall, [1660](#)  
SLQSVoiceBindSubscription, [1661](#)  
SLQSVoiceBurstDTMF, [1661](#)  
SLQSVoiceDialCall, [1662](#)  
SLQSVoiceEndCall, [1662](#)  
SLQSVoiceGetAllCallInfo, [1664](#)  
SLQSVoiceGetCLIP, [1667](#)  
SLQSVoiceGetCLIR, [1667](#)  
SLQSVoiceGetCNAP, [1668](#)  
SLQSVoiceGetCOLP, [1668](#)  
SLQSVoiceGetCOLR, [1669](#)  
SLQSVoiceGetCallBarring, [1664](#)  
SLQSVoiceGetCallForwardingStatus, [1665](#)

- SLQSVoiceGetCallInfo, 1666
- SLQSVoiceGetCallWaiting, 1666
- SLQSVoiceGetConfig, 1669
- SLQSVoiceIndicationRegister, 1671
- SLQSVoiceManageCalls, 1671
- SLQSVoiceOrigUSSDNoWait, 1672
- SLQSVoiceSendFlash, 1672
- SLQSVoiceSetCallBarringPassword, 1674
- SLQSVoiceSetConfig, 1674
- SLQSVoiceSetPreferredPrivacy, 1676
- SLQSVoiceSetSUPSService, 1676
- SLQSVoiceStartContDTMF, 1678
- SLQSVoiceStopContDTMF, 1678
- serviceClassInformation, 1657
- qaGobiApiWds.h, 1680
  - GetAutoconnect, 1689
  - GetByteTotals, 1690
  - GetConnectionRate, 1690
  - GetDataBearerTechnology, 1691
  - GetDefaultProfile, 1692
  - GetDefaultProfileLTE, 1694
  - GetDefaultProfileNum, 1696
  - GetDormancyState, 1697
  - GetIPAddressLTE, 1697
  - GetLastMobileIPError, 1698
  - GetMobileIP, 1698
  - GetMobileIPProfile, 1699
  - GetPacketStatistics, 1700
  - GetPacketStatus, 1701
  - GetProfileSettingIn, 1684
  - GetProfileSettingOut, 1684
  - GetSessionDuration, 1702
  - GetSessionState, 1702
  - iGetByteTotals, 1703
  - iGetConnectionRate, 1703
  - iGetPacketStatistics, 1703
  - iSLQSMISetIPFamilyPreference, 1703
  - qmiDataBearerMasks, 1689
  - QmiProfileInfo, 1684
  - QmiWDSDataBearerTechnology, 1686
  - QmiWDSDataBearers, 1684
  - RMSetTransferStatistics, 1703
  - SLQSAutoConnect, 1714
  - SLQSCreateProfile, 1715
  - SLQSDeleteProfile, 1715
  - SLQSGet3GPPConfigItem, 1716
  - SLQSGetByteTotals, 1716
  - SLQSGetConnectionRate, 1717
  - SLQSGetCurrDataSystemStat, 1717
  - SLQSGetCurrentChannelRate, 1717
  - SLQSGetDUNCallInfo, 1720
  - SLQSGetDataBearerTechnology, 1719
  - SLQSGetDataBearerTechnologyExt, 1719
  - SLQSGetPacketStatistics, 1720
  - SLQSGetProfile, 1721
  - SLQSGetProfileSettings, 1723
  - SLQSGetRuntimeSettings, 1723
  - SLQSGetSessionState, 1724
  - SLQSModifyProfile, 1724
  - SLQSResetPacketStatics, 1725
  - SLQSSetDHCPv4ClientConfig, 1728
  - SLQSSetLoopback, 1728
  - SLQSSetDHCPv4ClientConfig, 1729
  - SLQSSetLoopback, 1729
  - SLQSSet3GPPConfigItem, 1725
  - SLQSSetProfile, 1725
  - SLQSStartStopDataSession, 1729
  - SLQSWdsGoActive, 1730
  - SLQSWdsGoDormant, 1730
  - SLQSWdsSetEventReport, 1731
  - SLQSWdsSwiPDPRuntimeSettings, 1731
  - SetActiveMobileIPProfile, 1703
  - SetAutoconnect, 1705
  - SetDefaultProfile, 1705
  - SetDefaultProfileLTE, 1707
  - SetDefaultProfileLTEV2, 1709
  - SetDefaultProfileNum, 1711
  - SetMobileIP, 1711
  - SetMobileIPParameters, 1712
  - SetMobileIPProfile, 1713
  - slqs3GPPConfigItem, 1688
  - WDS\_IsGobiDevice, 1732
- qaNasGetRFBandInfo.h, 1732
  - PkQmiNasGetRFBandInfo, 1732
  - UpkQmiNasGetRFBandInfo, 1732
- qaNasPerformNetworkScan.h, 1732
  - FORBIDDEN\_INDEX, 1733
  - INDEX\_ZERO, 1733
  - PREFERRED\_INDEX, 1733
  - PkQmiNasPerformNetworkScan, 1733
  - ROAMING\_INDEX, 1733
  - UpkQmiNasPerformNetworkScan, 1733
- qaQmi3GPP2BroadcastCfgInfo
  - qaGobiApiSms.h, 1560
- qaQmi3GPPBroadcastCfgInfo
  - qaGobiApiSms.h, 1561
- qaQmi3Gpp2TimeZone, 695
  - daylightSavings, 696
  - leapSeconds, 696
  - localTimeOffset, 696
- qaQmiInterfaceInfo, 696
  - qaQmiinstanceid, 696
  - qaQmisvctype, 696
  - v4sessionId, 696
  - v6sessionId, 696
- qaQmiServingSystemParam, 696
  - BasestationID, 700
  - BasestationLatitude, 700
  - BasestationLongitude, 700
  - CDMA\_P\_Rev, 700
  - CDMASystemInfoExt, 700
  - CallBarStatus, 700
  - CellID, 700
  - concSvcInfo, 700
  - CurrentPLMN, 700
  - DTMInd, 700

- DataSrvCapabilities, [700](#)
- defaultRoamInd, [700](#)
- DetailedSvcInfo, [700](#)
- Gpp2TimeZone, [700](#)
- GppNetworkDSTAdjustment, [700](#)
- GppTimeZone, [700](#)
- hdrPersonality, [700](#)
- Lac, [700](#)
- NetworkID, [701](#)
- PRLInd, [701](#)
- roamIndicatorVal, [701](#)
- RoamingIndicatorList, [701](#)
- ServingSystem, [701](#)
- SystemID, [701](#)
- trackAreaCode, [701](#)
- qaQmiinstanceid
  - qaQmiInterfaceInfo, [696](#)
- qaQmisvctype
  - qaQmiInterfaceInfo, [696](#)
- qm\_wds\_ds\_profile\_extended\_err\_codes
  - qmerrno.h, [1739](#)
- qmerrno.h
  - eQCWWAN\_ERR\_API\_MUTEX\_TIMEOUT, [1736](#)
  - eQCWWAN\_ERR\_BUFFER\_SZ, [1735](#)
  - eQCWWAN\_ERR\_CANCEL\_OP, [1736](#)
  - eQCWWAN\_ERR\_DRIVER, [1736](#)
  - eQCWWAN\_ERR\_ENUM\_BEGIN, [1735](#)
  - eQCWWAN\_ERR\_ENUM\_END, [1736](#)
  - eQCWWAN\_ERR\_FILE\_COPY, [1735](#)
  - eQCWWAN\_ERR\_FILE\_OPEN, [1735](#)
  - eQCWWAN\_ERR\_GENERAL, [1735](#)
  - eQCWWAN\_ERR\_INTERNAL, [1735](#)
  - eQCWWAN\_ERR\_INVALID\_ARG, [1735](#)
  - eQCWWAN\_ERR\_INVALID\_DEVID, [1735](#)
  - eQCWWAN\_ERR\_INVALID\_FILE, [1735](#)
  - eQCWWAN\_ERR\_INVALID\_QMI\_RSP, [1735](#)
  - eQCWWAN\_ERR\_INVALID\_XID, [1736](#)
  - eQCWWAN\_ERR\_MALFORMED\_QMI\_RSP, [1735](#)
  - eQCWWAN\_ERR\_MEMORY, [1735](#)
  - eQCWWAN\_ERR\_MULTIPLE\_DEVICES, [1736](#)
  - eQCWWAN\_ERR\_MULTIPLE\_SMS\_UNSUPPORTED, [1736](#)
  - eQCWWAN\_ERR\_NO\_CANCELABLE\_OP, [1736](#)
  - eQCWWAN\_ERR\_NO\_CONNECTION, [1735](#)
  - eQCWWAN\_ERR\_NO\_DEVICE, [1735](#)
  - eQCWWAN\_ERR\_NO\_SIGNAL, [1736](#)
  - eQCWWAN\_ERR\_NONE, [1735](#)
  - eQCWWAN\_ERR\_NULL\_TLV, [1739](#)
  - eQCWWAN\_ERR\_OFFLINE, [1736](#)
  - eQCWWAN\_ERR\_PDU\_GENERATION, [1736](#)
  - eQCWWAN\_ERR\_QMI\_ABORTED, [1736](#)
  - eQCWWAN\_ERR\_QMI\_ACCESS\_DENIED, [1738](#)
  - eQCWWAN\_ERR\_QMI\_ACK\_NOT\_SENT, [1738](#)
  - eQCWWAN\_ERR\_QMI\_ARG\_TOO\_LONG, [1736](#)
  - eQCWWAN\_ERR\_QMI\_AUTHENTICATION\_FAILED, [1737](#)
  - eQCWWAN\_ERR\_QMI\_AUTHENTICATION\_LOCK, [1737](#)
  - eQCWWAN\_ERR\_QMI\_BUNDLING\_NOT\_SUPPORTED, [1738](#)
  - eQCWWAN\_ERR\_QMI\_CALL\_FAILED, [1736](#)
  - eQCWWAN\_ERR\_QMI\_CARD\_BUSY\_RSP, [1739](#)
  - eQCWWAN\_ERR\_QMI\_CARD\_CALL\_CONTROL\_FAILED, [1738](#)
  - eQCWWAN\_ERR\_QMI\_CAT\_END, [1739](#)
  - eQCWWAN\_ERR\_QMI\_CAT\_START, [1739](#)
  - eQCWWAN\_ERR\_QMI\_CAUSE\_CODE, [1737](#)
  - eQCWWAN\_ERR\_QMI\_CLIENT\_IDS\_EXHAUSTED, [1736](#)
  - eQCWWAN\_ERR\_QMI\_CONNECT, [1735](#)
  - eQCWWAN\_ERR\_QMI\_DEVICE\_IN\_USE, [1736](#)
  - eQCWWAN\_ERR\_QMI\_DEVICE\_NOT\_READY, [1737](#)
  - eQCWWAN\_ERR\_QMI\_DEVICE\_STORAGE\_FULL, [1737](#)
  - eQCWWAN\_ERR\_QMI\_DISABLED, [1737](#)
  - eQCWWAN\_ERR\_QMI\_ENCODING, [1737](#)
  - eQCWWAN\_ERR\_QMI\_ENVELOPE\_CMD\_FAILURE, [1739](#)
  - eQCWWAN\_ERR\_QMI\_EVENT\_REG\_FAILED, [1739](#)
  - eQCWWAN\_ERR\_QMI\_EXTENDED\_INTERNAL, [1738](#)
  - eQCWWAN\_ERR\_QMI\_FDN\_RESTRICT, [1738](#)
  - eQCWWAN\_ERR\_QMI\_FLOW\_SUSPENDED, [1737](#)
  - eQCWWAN\_ERR\_QMI\_GENERAL, [1737](#)
  - eQCWWAN\_ERR\_QMI\_HARDWARE\_RESTRICTED, [1738](#)
  - eQCWWAN\_ERR\_QMI\_IFACE, [1735](#)
  - eQCWWAN\_ERR\_QMI\_INCOMPATIBLE\_STATE, [1738](#)
  - eQCWWAN\_ERR\_QMI\_INCORRECT\_FLOW\_FILTER, [1737](#)
  - eQCWWAN\_ERR\_QMI\_INCORRECT\_PIN, [1736](#)
  - eQCWWAN\_ERR\_QMI\_INFO\_UNAVAILABLE, [1738](#)
  - eQCWWAN\_ERR\_QMI\_INJECT\_TIMEOUT, [1738](#)
  - eQCWWAN\_ERR\_QMI\_INSUFFICIENT\_RESOURCES, [1737](#)
  - eQCWWAN\_ERR\_QMI\_INTERFACE\_NOT\_FOUND, [1737](#)
  - eQCWWAN\_ERR\_QMI\_INTERNAL, [1736](#)
  - eQCWWAN\_ERR\_QMI\_INVALID\_ARG, [1737](#)
  - eQCWWAN\_ERR\_QMI\_INVALID\_CLIENT\_ID, [1736](#)
  - eQCWWAN\_ERR\_QMI\_INVALID\_DATA\_FORMAT, [1737](#)
  - eQCWWAN\_ERR\_QMI\_INVALID\_ENVELOPE\_CMD, [1739](#)
  - eQCWWAN\_ERR\_QMI\_INVALID\_HANDLE, [1736](#)
  - eQCWWAN\_ERR\_QMI\_INVALID\_ID, [1737](#)
  - eQCWWAN\_ERR\_QMI\_INVALID\_INDEX, [1737](#)

- eQCWWAN\_ERR\_QMI\_INVALID\_IP\_FAMILY\_P-REF, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_MCAST\_HAN-DLE, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_MESSAGE\_ID, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_OPERATION, [1738](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PDP\_TYPE, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PINID, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PROFILE, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PROFILE\_TY-PE, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_PS\_ATTACH\_-ACTION, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_QMI\_CMD, [1738](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_QOS\_ID, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_REGISTER\_A-CTION, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_SERVICE\_TY-PE, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_TECH\_PREF, [1736](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_TERMINAL\_R-SP, [1739](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_TRANSITION, [1737](#)
- eQCWWAN\_ERR\_QMI\_INVALID\_TX\_ID, [1736](#)
- eQCWWAN\_ERR\_QMI\_MALFORMED\_MSG, [1736](#)
- eQCWWAN\_ERR\_QMI\_MAX, [1738](#)
- eQCWWAN\_ERR\_QMI\_MAX\_MCAST\_REQUES-TS\_IN\_USE, [1737](#)
- eQCWWAN\_ERR\_QMI\_MAX\_QOS\_REQUESTS-\_IN\_USE, [1737](#)
- eQCWWAN\_ERR\_QMI\_MESSAGE\_DELIVERY\_-FAILURE, [1737](#)
- eQCWWAN\_ERR\_QMI\_MESSAGE\_NOT\_SENT, [1737](#)
- eQCWWAN\_ERR\_QMI\_MISSING\_ARG, [1736](#)
- eQCWWAN\_ERR\_QMI\_MSG\_BLOCKED, [1738](#)
- eQCWWAN\_ERR\_QMI\_NETWORK\_ABORTED, [1738](#)
- eQCWWAN\_ERR\_QMI\_NETWORK\_NOT\_READ-Y, [1737](#)
- eQCWWAN\_ERR\_QMI\_NETWORK\_QOS\_UNA-WARE, [1737](#)
- eQCWWAN\_ERR\_QMI\_NO\_EFFECT, [1736](#)
- eQCWWAN\_ERR\_QMI\_NO\_ENTRY, [1737](#)
- eQCWWAN\_ERR\_QMI\_NO\_FREE\_PROFILE, [1736](#)
- eQCWWAN\_ERR\_QMI\_NO\_MEMORY, [1736](#)
- eQCWWAN\_ERR\_QMI\_NO\_NETWORK\_FOUN-D, [1736](#)
- eQCWWAN\_ERR\_QMI\_NO\_RADIO, [1738](#)
- eQCWWAN\_ERR\_QMI\_NO\_SUBSCRIPTION, [1738](#)
- eQCWWAN\_ERR\_QMI\_NO\_THRESHOLDS, [1736](#)
- eQCWWAN\_ERR\_QMI\_NOT\_A\_MCAST\_IFACE, [1737](#)
- eQCWWAN\_ERR\_QMI\_NOT\_PROVISIONED, [1736](#)
- eQCWWAN\_ERR\_QMI\_NOT\_SUPPORTED, [1738](#)
- eQCWWAN\_ERR\_QMI\_OFFSET, [1736](#)
- eQCWWAN\_ERR\_QMI\_OP\_DEVICE\_UNSUPP-ORTED, [1736](#)
- eQCWWAN\_ERR\_QMI\_OP\_NETWORK\_UNSUP-PORTED, [1736](#)
- eQCWWAN\_ERR\_QMI\_OP\_PARTIAL\_FAILURE, [1738](#)
- eQCWWAN\_ERR\_QMI\_OUT\_OF\_CALL, [1736](#)
- eQCWWAN\_ERR\_QMI\_PIN\_BLOCKED, [1737](#)
- eQCWWAN\_ERR\_QMI\_PIN\_PERM\_BLOCKED, [1737](#)
- eQCWWAN\_ERR\_QMI\_POLICY\_MISMATCH, [1738](#)
- eQCWWAN\_ERR\_QMI\_REQ, [1735](#)
- eQCWWAN\_ERR\_QMI\_REQ\_SCH, [1735](#)
- eQCWWAN\_ERR\_QMI\_REQ\_TO, [1735](#)
- eQCWWAN\_ERR\_QMI\_REQUESTED\_NUM\_UN-SUPPORTED, [1737](#)
- eQCWWAN\_ERR\_QMI\_RSP, [1735](#)
- eQCWWAN\_ERR\_QMI\_RSP\_TO, [1735](#)
- eQCWWAN\_ERR\_QMI\_SEGMENT\_ORDER, [1738](#)
- eQCWWAN\_ERR\_QMI\_SEGMENT\_TOO\_LONG, [1738](#)
- eQCWWAN\_ERR\_QMI\_SESSION\_INACTIVE, [1737](#)
- eQCWWAN\_ERR\_QMI\_SESSION\_INVALID, [1737](#)
- eQCWWAN\_ERR\_QMI\_SESSION\_OWNERSHIP, [1737](#)
- eQCWWAN\_ERR\_QMI\_SIM\_FILE\_NOT\_FOUND, [1738](#)
- eQCWWAN\_ERR\_QMI\_SIM\_NOT\_INITIALIZED, [1737](#)
- eQCWWAN\_ERR\_QMI\_SMSC\_ADDR, [1738](#)
- eQCWWAN\_ERR\_QMI\_SUPS\_FAILURE\_CAUS-E, [1738](#)
- eQCWWAN\_ERR\_QMI\_TPDU\_TYPE, [1738](#)
- eQCWWAN\_ERR\_QMI\_UNABORTABLE\_TRAN-SACTION, [1736](#)
- eQCWWAN\_ERR\_QMI\_UNKNOWN, [1737](#)
- eQCWWAN\_ERR\_QMI\_WIDTH, [1739](#)
- eQCWWAN\_ERR\_RESET, [1736](#)
- eQCWWAN\_ERR\_SWICM\_AM\_VERS\_ERROR, [1738](#)
- eQCWWAN\_ERR\_SWICM\_CALL\_IN\_PROGRES-S, [1738](#)
- eQCWWAN\_ERR\_SWICM\_END, [1739](#)

- eQCWWAN\_ERR\_SWICM\_FAILED\_TO\_KILL\_S-DK\_PROCESS, [1738](#)
- eQCWWAN\_ERR\_SWICM\_INVALID\_SESSION\_ID, [1738](#)
- eQCWWAN\_ERR\_SWICM\_INVALID\_V4\_SESSION\_ID, [1738](#)
- eQCWWAN\_ERR\_SWICM\_INVALID\_V6\_SESSION\_ID, [1738](#)
- eQCWWAN\_ERR\_SWICM\_NOT\_IMPLEMENTED, [1738](#)
- eQCWWAN\_ERR\_SWICM\_QMI\_CLNT\_NOT\_SUPPORTED, [1738](#)
- eQCWWAN\_ERR\_SWICM\_QMI\_SVC\_NOT\_SUPPORTED, [1738](#)
- eQCWWAN\_ERR\_SWICM\_SM\_NO\_AVAILABLE\_SESSIONS, [1738](#)
- eQCWWAN\_ERR\_SWICM\_SOCKET\_IN\_USE, [1738](#)
- eQCWWAN\_ERR\_SWICM\_START, [1738](#)
- eQCWWAN\_ERR\_SWICM\_TIMEOUT, [1738](#)
- eQCWWAN\_ERR\_SWICM\_V4DWN\_V6DWN, [1738](#)
- eQCWWAN\_ERR\_SWICM\_V4DWN\_V6UP, [1738](#)
- eQCWWAN\_ERR\_SWICM\_V4UP\_V6DWN, [1738](#)
- eQCWWAN\_ERR\_SWICM\_V4UP\_V6UP, [1738](#)
- eQCWWAN\_ERR\_SWIDCS\_APP\_DISCONNECTED, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_DEVNODE\_NOT\_FOUND, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_END, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_FILEIO\_ERR, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_IOCTL\_ERR, [1739](#)
- eQCWWAN\_ERR\_SWIDCS\_START, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_CORRUPTED\_FW\_IMAGE, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_END, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FILE\_NOT\_FOUND, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FIRMWARE\_NOT\_DOWNLOADED, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_ENTER\_DOWNLOAD\_MODE, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_FLASH\_COMPLETE, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_PREFERENCE\_MISMATCH, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_UPDATE\_FAIL, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_UPDATE\_SUCCESS, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_FW\_WAIT\_FOR\_REBOOT, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_INVALID\_CRASH\_STATE, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_INVALID\_PATH, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_OPENING\_DIR, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_OPENING\_FILE, [1739](#)
- eQCWWAN\_ERR\_SWIIM\_START, [1739](#)
- eQCWWAN\_ERR\_SWISM\_END, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_BEARER\_DATA\_NOT\_FOUND, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_MSG\_CORRUPTED, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_MSG\_LEN\_TOO\_LONG, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_SMSC\_NUM\_CORRUPTED, [1739](#)
- eQCWWAN\_ERR\_SWISMS\_START, [1739](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP2\_ERR\_INVALID\_IDENT\_FOR\_PROFILE, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_ACCESS\_ERR, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_CONTEXT\_NOT\_DEFINED, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_ERR\_OUT\_OF\_PROFILES, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_INVALID\_PROFILE\_FAMILY, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_READ\_ONLY\_FLAG\_SET, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_3GPP\_VALID\_FLAG\_NOT\_SET, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_END, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_INVALID\_PROFILE\_FAMILY, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_HNDL, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_IDENT, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_OP, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_PROFILE\_NUM, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_PROFILE\_TYPE, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_INVALID\_SUBS\_ID, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_LEN\_INVALID, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_ERR\_LIB\_NOT\_INITED, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_FAIL, [1740](#)
- eWDS\_ERR\_PROFILE\_REG\_RESULT\_LIST\_END, [1740](#)
- qmerrno.h, [1733](#)
  - eQCWWANError, [1735](#)
  - qm\_wds\_ds\_profile\_extended\_err\_codes, [1739](#)
- QmiCbkCatEventStatusReportInd, [701](#)
  - CCETlv, [701](#)
  - event\_Index, [701](#)
- QmiCbkLocCradleMountInd, [701](#)
  - cradleMountConfigStatus, [702](#)
- QmiCbkLocEngineStateInd, [702](#)



- engineState, 702
- QmiCbkLocEventTimeSyncInd, 703
  - timeSyncRefCounter, 703
- QmiCbkLocInjectPositionInd, 703
  - status, 704
- QmiCbkLocInjectSensorDataInd, 704
  - injectSensorDataStatus, 705
  - pAccelSamplesAccepted, 705
  - pAccelTempSamplesAccepted, 705
  - pGyroSamplesAccepted, 705
  - pGyroTempSamplesAccepted, 706
  - pOpaqueIdentifier, 706
- QmiCbkLocInjectTimeInd, 706
  - injectTimeSyncStatus, 706
- QmiCbkLocInjectUTCTimeInd, 706
  - status, 707
- QmiCbkLocPositionReportInd, 707
  - pAltitudeAssumed, 712
  - pAltitudeWrtEllipsoid, 712
  - pAltitudeWrtMeanSeaLevel, 712
  - pFixId, 712
  - pGpsTime, 712
  - pHeading, 712
  - pHeadingUnc, 712
  - pHorConfidence, 712
  - pHorReliability, 712
  - pHorUncCircular, 712
  - pHorUncEllipseOrientAzimuth, 712
  - pHorUncEllipseSemiMajor, 712
  - pHorUncEllipseSemiMinor, 712
  - pLatitude, 712
  - pLeapSeconds, 712
  - pLongitude, 712
  - pMagneticDeviation, 712
  - pPrecisionDilution, 712
  - pSensorDataUsage, 713
  - pSpeedHorizontal, 713
  - pSpeedUnc, 713
  - pSpeedVertical, 713
  - pSvUsedforFix, 713
  - pTechnologyMask, 713
  - pTimeSrc, 713
  - pTimeUnc, 713
  - pTimestampUtc, 713
  - pVertConfidence, 713
  - pVertReliability, 713
  - pVertUnc, 713
  - sessionId, 713
  - sessionStatus, 713
- QmiCbkLocSensorStreamingInd, 713
  - pAccelAcceptReady, 714
  - pAccelTempAcceptReady, 714
  - pGyroAcceptReady, 714
  - pGyroTempAcceptReady, 714
- QmiCbkLocSetExtPowerConfigInd, 714
  - status, 714
- QmiCbkNasLTECphyCaInfo, 715
  - sPhyCaAggPcellInfo, 715
  - sPhyCaAggScellIDIBw, 715
  - sPhyCaAggScellIndType, 715
  - sPhyCaAggScellIndex, 715
  - sPhyCaAggScellInfo, 715
- QmiCbkSwiOmaDmEventStatusReportInd, 715
  - SITlv, 716
- QmiCbkSwiOmaDmEventStatusReportIndExt, 716
  - SITlv, 716
- QmiCbkTmdMitiLvlRptInd, 716
  - currentMitigationLvl, 716
  - MitigationDevInfo, 716
- QmiCbkWdsStatisticsIndState, 716
  - RxDropConutTlv, 718
  - RxOkByteCountTlv, 718
  - RxOkConutTlv, 718
  - TxDropConutTlv, 718
  - TxOkByteCountTlv, 718
  - TxOkConutTlv, 718
- qmiDataBearerMasks
  - qaGobiApiWds.h, 1689
- QmiNas3GppNetworkInfo, 719
  - pDescription, 720
  - pForbidden, 720
  - pInUse, 720
  - pMCC, 720
  - pMNC, 720
  - pPreferred, 721
  - pRoaming, 721
- QmiNasGetRFBandInfoResp, 721
  - pInstancesSize, 721
  - pRFBandInfoElements, 721
  - results, 721
- QmiNasPerformNetworkScanResp, 721
  - pInstanceSize, 721
  - pInstances, 721
  - results, 721
- QmiProfileInfo
  - qaGobiApiWds.h, 1684
- qmiSmsMessageList, 721
  - messageIndex, 722
  - messageTag, 722
- QmiWSDDataBearerTechnology
  - qaGobiApiWds.h, 1686
- qmiWSDDataBearerTechnology, 722
  - currentNetwork, 722
  - ratMask, 722
  - soMask, 722
- QmiWSDDataBearers
  - qaGobiApiWds.h, 1684
- QmiWdsIpAddressInfo, 722
  - pIPAddressV4, 723
  - pIPAddressV6, 723
  - pIPv6prefixlen, 723
- qmiWdsRunTimeSettings, 723
  - pAPNName, 726
  - pAuthentication, 726
  - pDomainList, 726
  - pGPRSGrantedQoS, 726

- pGWAddressV4, 726
- pIMCNflag, 726
- pIPAddressV4, 726
- pIPFamilyPreference, 726
- pIPv6AddrInfo, 726
- pIPv6GWAddrInfo, 727
- pMtu, 727
- pPCSCFAddrPCO, 727
- pPCSCFFQDNAddrList, 727
- pPDPTType, 727
- pPrimaryDNSV4, 727
- pPrimaryDNSV6, 727
- pProfileID, 727
- pProfileName, 727
- pSecondaryDNSV4, 727
- pSecondaryDNSV6, 727
- pServerAddrList, 727
- pSubnetMaskV4, 727
- pTechnology, 727
- pUMTSGrantedQoS, 727
- pUsername, 727
- qmifwinfo\_s, 718
  - dev, 719
  - g, 719
  - s, 719
- qos.h, 1740
  - pack\_qos\_SLQSQoSGetNetworkStatus, 1742
  - pack\_qos\_SLQSQoSSwiReadApnExtraParams, 1742
  - pack\_qos\_SLQSQoSSwiReadDataStats, 1743
  - pack\_qos\_SLQSSetQoSEventCallback, 1744
  - unpack\_qos\_SLQSQoSGetNetworkStatus, 1744
  - unpack\_qos\_SLQSQoSSwiReadApnExtraParams, 1746
  - unpack\_qos\_SLQSQoSSwiReadDataStats, 1746
  - unpack\_qos\_SLQSSetQoSEventCallback, 1747
  - unpack\_qos\_SLQSSetQoSEventCallback\_ind, 1747
  - unpack\_qos\_SLQSSetQoSNWStatusCallback\_ind, 1748
  - unpack\_qos\_SLQSSetQoSPrEventCallback\_ind, 1748
  - unpack\_qos\_SLQSSetQoSStatusCallback\_ind, 1750
- qos\_id
  - QoSMap, 733
- QoSClassID, 727
  - gDIBitRate, 728
  - gUIBitRate, 728
  - maxDIBitRate, 728
  - maxUIBitRate, 728
  - QCI, 728
- qosDeliveryOrder
  - LibPackUMTSQoS, 374
  - UMTSMInQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMInQoS, 1185
- QoSEventInfo, 728
  - pDataBearer, 730
  - pPacketsCountRX, 730
  - pPacketsCountTX, 730
  - pTotalBytesRX, 730
  - pTotalBytesTX, 730
- qosFlow
  - sQoSStat, 843
  - unpack\_qos\_SLQSQoSSwiReadDataStats\_t, 1036
- QoSFlowInfo, 730
  - pBearerID, 731
  - pQFlowState, 731
  - pRxQFilter, 731
  - pRxQFlowGranted, 731
  - pTxQFilter, 731
  - pTxQFlowGranted, 731
  - unpack\_qos\_SLQSSetQoSEventCallback\_ind\_t, 1036
- QoSFlowInfoState, 731
  - id, 732
  - isNewFlow, 732
  - state, 732
- QoSMap, 732
  - dscp, 733
  - qos\_id, 733
  - state, 733
- Quality of Service (QOS), 48
- RAN
  - unpack\_nas\_GetServingNetwork\_t, 995
- RAT
  - \_SlqsNas3GppNetworkRAT\_, 70
  - nas\_QmiNas3GppNetworkRAT, 492
- RATMask
  - CurrNetworkInfo, 194
  - currNetworkInfo, 194
  - wds\_currNetworkInfo, 1175
- REGISTER\_EVENT
  - qaGobiApiCbK.h, 1304
- REGISTER\_SRV
  - qaGobiApiCbK.h, 1305
- RFBandInfoElements, 741
  - activeBandClass, 742
  - activeChannel, 742
  - radioInterface, 742
  - unpack\_nas\_GetRFInfo\_t, 994
- RFTIv
  - unpack\_nas\_SetEventReportInd\_t, 997
- RMAutoConnect
  - pack\_dms\_SetCustFeature\_t, 583
  - unpack\_dms\_GetCustFeature\_t, 954
- RMSetTransferStatistics
  - qaGobiApiWds.h, 1703
- ROAMING\_INDEX
  - qaNasPerformNetworkScan.h, 1733
- RPCause
  - SMSAsyncRawSend\_s, 825
- RPTIv
  - NASQmiCbK\_NasSystemSelPrefInd, 550
- RRTIv

- unpack\_nas\_SetEventReportInd\_t, 997
- RSRPThresListLen
  - RSRPThresh, 746
- RSRPThresh, 744
  - pRSRPThresList, 746
  - RSRPThresListLen, 746
- RSRQThresListLen
  - RSRQThresh, 747
- RSRQThresh, 747
  - pRSRQThresList, 747
  - RSRQThresListLen, 747
- RSSIThresListLen
  - RSSIThresh, 748
- RSSIThresh, 747
  - pRSSIThresList, 748
  - RSSIThresListLen, 748
- RX\_EC\_IO
  - NetworkStat1x, 565
- RX\_PWR
  - NetworkStat1x, 565
  - NetworkStatEVDO, 567
- RXAGCList, 748
  - pRXAIG, 749
  - pRXComprSlope, 749
  - pRXComprThres, 749
  - pRXExpSlope, 749
  - pRXExpThres, 749
  - pRXStaticGain, 749
- RXAVCList, 749
  - pAVRXAVCHheadroom, 749
  - pAVRXAVCSens, 749
- RXChan
  - LTEInfo, 408
  - nas\_LTEInfo, 473
- rXDroppedCount
  - unpack\_wds\_GetPacketStatus\_t, 1075
- RXOKBytesCount
  - DUNCallInfoInd, 230
- rXOKBytesLastCall
  - unpack\_wds\_GetPacketStatus\_t, 1075
- rXOkBytesCount
  - unpack\_wds\_GetPacketStatus\_t, 1075
- RXPCMIIRFiltr, 751
  - pFlag, 753
  - pStage0Val, 753
  - pStage1Val, 753
  - pStage2Val, 753
  - pStage3Val, 753
  - pStage4Val, 753
  - pStageCnt, 753
- rXPacketErrors
  - unpack\_wds\_GetPacketStatus\_t, 1075
- rXPacketOverflows
  - unpack\_wds\_GetPacketStatus\_t, 1075
- rXPacketSuccesses
  - unpack\_wds\_GetPacketStatus\_t, 1075
- radio
  - unpack\_nas\_GetSignalStrengths\_t, 996
- radio\_if
  - nasGetTxRxInfoReq, 533
- radiolf
  - ecioListElement, 231
  - errorRateListElement, 236
  - nas\_ecioListElement, 452
  - nas\_errorRateListElement, 453
  - nas\_rsrqInformation, 495
  - nas\_rxSignalStrengthListElement, 496
  - rsrqInformation, 746
  - rxSignalStrengthListElement, 754
- Radiolfaces
  - unpack\_dms\_GetDeviceCap\_t, 955
  - unpack\_dms\_GetDeviceCapabilities\_t, 956
  - unpack\_nas\_GetServingNetwork\_t, 995
- RadiolfacesSize
  - unpack\_dms\_GetDeviceCap\_t, 955
  - unpack\_nas\_GetServingNetwork\_t, 995
- radiolfacesSize
  - unpack\_dms\_GetDeviceCapabilities\_t, 956
- radioInterface
  - nas\_RFInfoTlv, 494
  - nas\_roamIndList, 495
  - nas\_servSystem, 498
  - nas\_SignalStrengthTlv, 499
  - nas\_timeInfo, 509
  - RFBandInfoElements, 742
  - roamIndList, 743
  - servSystem, 766
  - timeInfo, 883
- radioInterfaceList
  - NASServingSystemInfo, 552
  - ServingSystemInfo, 764
- radioInterfaceNo
  - NASServingSystemInfo, 552
  - ServingSystemInfo, 764
- radioInterfaceSize
  - nas\_RFInfoTlv, 494
- range
  - Port, 676
  - unpack\_qos\_Port\_t, 1030
- RankIndicatorInd, 733
  - Count1, 733
  - Count2, 733
- rat
  - CSGID, 185
  - MNRInfo, 430
  - nas\_CSGID, 447
  - nas\_MNRInfo, 487
- ratMask
  - dataBearerTechnology, 207
  - qmiWSDDataBearerTechnology, 722
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, 1086
- ratValue
  - DataBearerTech, 205
- rawLen
  - fileAttributes, 241



- rawValue
  - fileAttributes, [241](#)
- rcv4
  - ssdatasession\_params, [847](#)
- rcv6
  - ssdatasession\_params, [847](#)
- readResult, [733](#)
  - content, [733](#)
  - contentLen, [733](#)
- readTransparent
  - pack\_uim\_ReadTransparent\_t, [630](#)
  - UIMReadTransparentReq, [924](#)
- readTransparentInfo, [733](#)
  - length, [734](#)
  - offset, [734](#)
- Reason
  - voiceGetCallFWReq, [1118](#)
  - voiceSetCallBarringPwdInfo, [1145](#)
- reason
  - ccSUPSType, [150](#)
  - redirNumInfo, [736](#)
  - unpack\_qos\_SLQSSetQosStatusCallback\_ind\_t, [1040](#)
  - voiceGetCallBarringReq, [1115](#)
  - voiceSetSUPSServiceReq, [1153](#)
- receiptAction
  - smsRouteEntry, [839](#)
- receivedBytes
  - omaDmFotaTlvExt, [579](#)
- reconfigReqd
  - \_packetSrvStatus, [64](#)
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t, [1084](#)
- reconfiguration\_required
  - slqsSessionStateInfo, [813](#)
- recordCount
  - fileAttributes, [241](#)
- recordSize
  - fileAttributes, [241](#)
- redirNumInfo, [734](#)
  - numLen, [736](#)
  - numPlan, [736](#)
  - numType, [736](#)
  - number, [736](#)
  - PI, [736](#)
  - reason, [736](#)
  - SI, [736](#)
- RedirPartyNum
  - arrRedirPartyNum, [118](#)
- refData
  - unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t, [976](#)
- refString
  - unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t, [976](#)
- ReferenceID
  - CatAlPhalIdentifierTlv, [147](#)
  - CatEventIDDDataTlv, [148](#)
- refpn
  - CDMAInfo, [154](#)
  - nas\_CDMAInfo, [438](#)
- refreshComplete
  - UIMRefreshCompleteReq, [926](#)
- RefreshMode
  - CatRefreshTlv, [149](#)
- RefreshStage
  - CatRefreshTlv, [149](#)
- regAction
  - nasInitNetworkReg, [538](#)
  - pack\_nas\_SLQSInitiateNetworkRegistration\_t, [600](#)
- RegForeignNID
  - unpack\_nas\_GetCDMANetworkParameters\_t, [990](#)
- RegForeignSID
  - unpack\_nas\_GetCDMANetworkParameters\_t, [991](#)
- RegHomeSID
  - unpack\_nas\_GetCDMANetworkParameters\_t, [991](#)
- regInd
  - \_transLayerInfoNotification, [95](#)
- regPrd
  - AddCDMASysInfo, [99](#)
  - nas\_AddCDMASysInfo, [434](#)
- regRefresh
  - UIMRefreshRegisterReq, [930](#)
- regRejectInfoValid
  - GSMSysInfo, [300](#)
  - LTESysInfo, [425](#)
  - nas\_GSMSysInfo, [462](#)
  - nas\_LTESysInfo, [484](#)
  - nas\_WCDMASysInfo, [523](#)
  - WCDMASysInfo, [1172](#)
- regState
  - nas\_servSystem, [498](#)
  - servSystem, [766](#)
- Region
  - fwinfow\_s, [249](#)
- registerFlag
  - registerRefresh, [737](#)
- registerRefresh, [736](#)
  - arrfileInfo, [737](#)
  - numFiles, [737](#)
  - registerFlag, [737](#)
  - voteForInit, [737](#)
- RegistrationState
  - unpack\_nas\_GetServingNetwork\_t, [995](#)
- registrationState
  - NASServingSystemInfo, [553](#)
  - ServingSystemInfo, [764](#)
- rejCause
  - GSMSysInfo, [300](#)
  - LTESysInfo, [425](#)
  - nas\_GSMSysInfo, [462](#)
  - nas\_LTESysInfo, [484](#)
  - nas\_WCDMASysInfo, [523](#)
  - WCDMASysInfo, [1172](#)
- rejectCause
  - nas\_RejectReasonTlv, [493](#)
- rejectSrvDomain
  - GSMSysInfo, [300](#)

- LTESysInfo, [425](#)
  - nas\_GSMsSysInfo, [462](#)
  - nas\_LTESysInfo, [484](#)
  - nas\_WCDMASysInfo, [523](#)
  - WCDMASysInfo, [1172](#)
- reliabilityClass
  - GPRSQoS, [288](#)
  - GPRSRequestedQoS, [289](#)
  - LibPackGPRSRequestedQoS, [342](#)
  - wds\_GPRSQoS, [1177](#)
- remPartyNumber
  - remotePartyNum, [740](#)
- remainingRetries, [737](#)
  - unblockLeft, [738](#)
  - verifyLeft, [738](#)
- Remote Management Service (RMS), [39](#)
- RemotePartyName
  - getAllCallRmtPtyName, [253](#)
- remotePartyName, [738](#)
  - callerName, [739](#)
  - codingScheme, [739](#)
  - nameLen, [739](#)
  - namePI, [739](#)
- RemotePartyNum
  - getAllCallRmtPtyNum, [254](#)
- remotePartyNum, [739](#)
  - numLen, [740](#)
  - presentationInd, [740](#)
  - remPartyNumber, [740](#)
- ReqFieldsList, [740](#)
  - requestFields, [741](#)
  - requestFieldsLen, [741](#)
- requestFields
  - ReqFieldsList, [741](#)
- requestFieldsLen
  - ReqFieldsList, [741](#)
- resBerRatio
  - LibPackUMTSQoS, [374](#)
  - UMTSMinQoS, [945](#)
  - UMTSQoS, [949](#)
  - wds\_UMTSMinQoS, [1185](#)
- ResCode
  - FirmwareUpdatStat, [244](#)
  - GetAudioVoITLBConfigResp, [261](#)
  - SetAudioVoITLBConfigResp, [773](#)
  - unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t, [976](#)
- reserved
  - omaDmFotaTlvExt, [579](#)
- resetInfoInd
  - pack\_dms\_SLQSDmsSwiIndicationRegister\_t, [585](#)
- ResetInfoNotification
  - qaGobiApiCbK.h, [1312](#)
- ResetPDSDData
  - qaGobiApiPds.h, [1535](#)
- ResetToFactoryDefaults
  - qaGobiApiDms.h, [1422](#)
- RespFieldsList, [741](#)
  - responseFields, [741](#)
- responseFieldsLen, [741](#)
- responseFields
  - RespFieldsList, [741](#)
- responseFieldsLen
  - RespFieldsList, [741](#)
- results
  - QmiNasGetRFBandInfoResp, [721](#)
  - QmiNasPerformNetworkScanResp, [721](#)
- RetryCount
  - unpack\_swioma\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- revPolarity
  - lineCtrlInfo, [375](#)
- revTunneling
  - unpack\_wds\_GetMobileIPProfile\_t, [1074](#)
- ReverseMac
  - protocolSubtypeElement, [694](#)
- RmTrasnferStaticsReq
  - pack\_wds\_RMSetTransferStatistics\_t, [639](#)
- rmTrasnferStaticsReq, [742](#)
  - bResetStatistics, [742](#)
  - ulMask, [742](#)
- RmtPtyNum
  - arrRemotePartyNum, [119](#)
- roamIndList, [743](#)
  - numInstances, [743](#)
  - radioInterface, [743](#)
  - roamIndicator, [743](#)
- roamIndicator
  - nas\_roamIndList, [495](#)
  - roamIndList, [743](#)
- RoamIndicatorVal
  - unpack\_nas\_SLQSGetServingSystem\_t, [1004](#)
- roamIndicatorVal
  - qaQmiServingSystemParam, [701](#)
- roamOrigVoiceSO
  - prefVoiceSO, [679](#)
- RoamPref
  - NASRoamPreferenceTlv, [550](#)
- roamStatus
  - nas\_sysInfoCommon, [505](#)
  - sysInfoCommon, [873](#)
- roamStatusValid
  - nas\_sysInfoCommon, [505](#)
  - sysInfoCommon, [873](#)
- roamTimer, [744](#)
  - namID, [744](#)
  - roamTimerValue, [744](#)
- roamTimerValue
  - roamTimer, [744](#)
- Roaming
  - nas\_QmiNas3GppNetworkInfo, [491](#)
  - SlqsNas3GppNetworkInfo, [808](#)
  - unpack\_nas\_GetCDMANetworkParameters\_t, [991](#)
  - unpack\_nas\_GetServingNetwork\_t, [995](#)
- roaming
  - unpack\_nas\_SetRoamingIndicatorCallback\_ind\_t, [999](#)

- roaming\_ind
  - RoamingInfo, [744](#)
- RoamingIndicatorList
  - qaQmiServingSystemParam, [701](#)
  - unpack\_nas\_SLQSSGetServingSystem\_t, [1004](#)
- RoamingInfo, [743](#)
  - roaming\_ind, [744](#)
  - TlvPresent, [744](#)
- routeList
  - smsSetRoutesReq, [839](#)
- routeStorage
  - smsRouteEntry, [839](#)
- rptRate
  - LTESigRptCfg, [418](#)
  - LTESigRptConfig, [419](#)
  - nas\_LTESigRptConfig, [481](#)
- rscp
  - nas\_UMTSInfo, [511](#)
  - rxInfo, [751](#)
  - TDSCDMASigInfoExt, [876](#)
  - tdscdmaSigInfoExt, [877](#)
  - UMTSInfo, [940](#)
- rsrp
  - cellParams, [166](#)
  - LTESSInfo, [422](#)
  - lteSSInfo, [423](#)
  - nas\_cellParams, [444](#)
  - nas\_umtsLTENbrCell, [513](#)
  - rxInfo, [751](#)
  - umtsLTENbrCell, [942](#)
- rsrpIlevel
  - lteRsrpInformation, [415](#)
  - nas\_lteRsrpInformation, [478](#)
- rsrq
  - cellParams, [166](#)
  - LTESSInfo, [422](#)
  - lteSSInfo, [423](#)
  - nas\_cellParams, [444](#)
  - nas\_rsrqInformation, [495](#)
  - nas\_umtsLTENbrCell, [513](#)
  - rsrqInformation, [746](#)
  - umtsLTENbrCell, [942](#)
- rsrqDelta
  - nas\_SLQSSignalStrengthsIndReq, [500](#)
  - SLQSSignalStrengthsIndReq, [819](#)
- rsrqInfo
  - nas\_SLQSSignalStrengthsInformation, [500](#)
  - slqsSignalStrengthInfo, [817](#)
  - SLQSSignalStrengthsInformation, [820](#)
  - unpack\_nas\_SLQSSGetSignalStrength\_t, [1005](#)
- rsrqInformation, [746](#)
  - radiolf, [746](#)
  - rsrq, [746](#)
- rsri
  - CDMASSInfo, [160](#)
  - cdmaSSInfo, [160](#)
  - cellParams, [166](#)
  - gsmCellInfo, [295](#)
  - HDRSSInfo, [308](#)
  - hdrSSInfo, [309](#)
  - LTESSInfo, [422](#)
  - lteSSInfo, [423](#)
  - nas\_cellParams, [444](#)
  - nas\_gsmCellInfo, [457](#)
  - TDSCDMASigInfoExt, [876](#)
  - tdscdmaSigInfoExt, [877](#)
  - unpack\_nas\_GetSignalStrengths\_t, [996](#)
- rts
  - WdsRunTimeSettings, [1201](#)
- rx\_bytes
  - NetStats, [561](#)
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- rx\_errors
  - NetStats, [561](#)
- rx\_overflows
  - NetStats, [561](#)
- rx\_packets
  - NetStats, [561](#)
- rx\_pkts
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- RxDropConutTlv
  - QmiCbkWdsStatisticsIndState, [718](#)
- rxInfo, [750](#)
  - ecio, [750](#)
  - isRadioTuned, [750](#)
  - phase, [751](#)
  - rscp, [751](#)
  - rsrp, [751](#)
  - rxPower, [751](#)
- rxLev
  - GERANInfo, [251](#)
  - nas\_GERANInfo, [455](#)
- rxOKBytesCount
  - unpack\_wds\_SLQSSGetDUNCallInfo\_t, [1081](#)
- RxOkByteCountTlv
  - QmiCbkWdsStatisticsIndState, [718](#)
- RxOkConutTlv
  - QmiCbkWdsStatisticsIndState, [718](#)
- rxPower
  - rxInfo, [751](#)
- RxQFilter
  - unpack\_qos\_QosFlowInfo\_t, [1032](#)
- RxQFlowGranted
  - unpack\_qos\_QosFlowInfo\_t, [1032](#)
- rxSignalStrength
  - nas\_rxSignalStrengthListElement, [496](#)
  - rxSignalStrengthListElement, [754](#)
- rxSignalStrengthDelta
  - nas\_SLQSSignalStrengthsIndReq, [500](#)
  - SLQSSignalStrengthsIndReq, [819](#)
- rxSignalStrengthInfo
  - nas\_SLQSSignalStrengthsInformation, [500](#)
  - SLQSSignalStrengthsInformation, [820](#)
- rxSignalStrengthList

- slqsSignalStrengthInfo, [817](#)
- unpack\_nas\_SLQSGetSignalStrength\_t, [1005](#)
- rxSignalStrengthListElement, [753](#)
  - radioIlf, [754](#)
  - rxSignalStrength, [754](#)
- rxSignalStrengthListLen
  - slqsSignalStrengthInfo, [817](#)
  - unpack\_nas\_SLQSGetSignalStrength\_t, [1005](#)
- s
  - qmifwinfo\_s, [719](#)
- SMS\_EVENT\_ETWS
  - qaGobiApiCbK.h, [1350](#)
- SMS\_EVENT\_ETWS\_PLMN
  - qaGobiApiCbK.h, [1350](#)
- SMS\_EVENT\_MESSAGE\_MODE
  - qaGobiApiCbK.h, [1349](#)
- SMS\_EVENT\_MT\_MESSAGE
  - qaGobiApiCbK.h, [1349](#)
- SMS\_EVENT\_SMS\_ON\_IMS
  - qaGobiApiCbK.h, [1350](#)
- SMS\_EVENT\_SMSC\_ADDRESS
  - qaGobiApiCbK.h, [1350](#)
- SMS\_EVENT\_TRANSFER\_ROUTE\_MT\_MESSAGE
  - qaGobiApiCbK.h, [1349](#)
- sApnExtraParams, [754](#)
  - ambr\_dl, [755](#)
  - ambr\_dl\_ext, [755](#)
  - ambr\_dl\_ext2, [755](#)
  - ambr\_ul, [755](#)
  - ambr\_ul\_ext, [755](#)
  - ambr\_ul\_ext2, [755](#)
  - apnId, [755](#)
- SCI
  - unpack\_nas\_GetCDMANetworkParameters\_t, [991](#)
- SCM
  - unpack\_nas\_GetCDMANetworkParameters\_t, [991](#)
- SDPTlv
  - NASQmiCbK NasSystemSelPrefInd, [550](#)
- SDU\_HDR\_LEN
  - common.h, [1211](#)
- SECOND\_INSTANCE
  - qaGobiApiCbK.h, [1305](#)
- sGetDeviceSeriesResult, [794](#)
  - eDevice, [795](#)
  - uResult, [795](#)
- SHORT
  - SwiDataTypes.h, [1761](#)
- SI
  - calledPartyInfo, [132](#)
  - callFWExtInfo, [137](#)
  - callingPartyInfo, [142](#)
  - redirNumInfo, [736](#)
- SITlv
  - QmiCbKSwiOmaDmEventStatusReportInd, [716](#)
  - QmiCbKSwiOmaDmEventStatusReportIndExt, [716](#)
- sIntraSearch
  - LTEInfoIntraFreq, [411](#)
  - nas\_LTEInfoIntraFreq, [476](#)
- SLQSAutoConnect
  - qaGobiApiWds.h, [1714](#)
- SLQSCDMADecodeMTTextMsg
  - qaGobiApiSms.h, [1566](#)
- SLQSCDMAEncodeMOTextMsg
  - qaGobiApiSms.h, [1566](#)
- SLQSCfgSigInfo
  - qaGobiApiNas.h, [1508](#)
- SLQSCreateProfile
  - qaGobiApiWds.h, [1715](#)
- SLQSDeleteProfile
  - qaGobiApiWds.h, [1715](#)
- SLQSDeleteProfileParams, [804](#)
  - profileIndex, [805](#)
  - profileType, [805](#)
- SLQSDeleteSMS
  - qaGobiApiSms.h, [1567](#)
- SLQSDmsSwiGetResetInfo
  - qaGobiApiDms.h, [1423](#)
- SLQSDmsSwiIndicationRegister
  - qaGobiApiDms.h, [1423](#)
- SLQSDownloadFirmwareToSlot
  - qaGobiApiFms.h, [1454](#)
- SLQSFWINFO\_SKU\_SZ
  - qaGobiApiFms.h, [1449](#)
- SLQSGet3GPPConfigItem
  - qaGobiApiWds.h, [1716](#)
- SLQSGetAGPSCfg
  - qaGobiApiPds.h, [1539](#)
- SLQSGetAudioPathConfig
  - qaGobiApiAudio.h, [1291](#)
- SLQSGetAudioProfile
  - qaGobiApiAudio.h, [1291](#)
- SLQSGetAudioVolTLBConfig
  - qaGobiApiAudio.h, [1292](#)
- SLQSGetBandCapabilities
  - qaGobiApiDms.h, [1424](#)
- SLQSGetBandCapability
  - qaGobiApiDms.h, [1424](#)
- SLQSGetBootVersionNumber
  - qaGobiApiFms.h, [1455](#)
- SLQSGetByteTotals
  - qaGobiApiWds.h, [1716](#)
- SLQSGetConnectionRate
  - qaGobiApiWds.h, [1717](#)
- SLQSGetCurrDataSystemStat
  - qaGobiApiWds.h, [1717](#)
- SLQSGetCurrentChannelRate
  - qaGobiApiWds.h, [1717](#)
- SLQSGetCurrentPRLInfo
  - qaGobiApiDms.h, [1426](#)
- SLQSGetCustFeatures
  - qaGobiApiDms.h, [1426](#)
- SLQSGetCustFeaturesV2
  - qaGobiApiDms.h, [1426](#)
- SLQSGetDUNCallInfo
  - qaGobiApiWds.h, [1720](#)
- SLQSGetDataBearerTechnology

- qaGobiApiWds.h, [1719](#)
- SLQSGetDataBearerTechnologyExt
  - qaGobiApiWds.h, [1719](#)
- SLQSGetDeviceMode
  - qaGobiApiDcs.h, [1395](#)
- SLQSGetERIFile
  - qaGobiApiDms.h, [1427](#)
- SLQSGetErrorRate
  - qaGobiApiNas.h, [1509](#)
- SLQSGetFirmwareInfo
  - qaGobiApiFms.h, [1456](#)
- SLQSGetGPSSStateInfo
  - qaGobiApiPds.h, [1540](#)
- SLQSGetIMSARegStatus
  - qaGobiApilmsa.h, [1468](#)
- SLQSGetIMSAServiceStatus
  - qaGobiApilmsa.h, [1468](#)
- SLQSGetIMSASupportedFields
  - qaGobiApilmsa.h, [1469](#)
- SLQSGetIMSASupportedMsg
  - qaGobiApilmsa.h, [1469](#)
- SLQSGetIMSSMSConfig
  - qaGobiApilms.h, [1462](#)
- SLQSGetIMSUserConfig
  - qaGobiApilms.h, [1463](#)
- SLQSGetIMSVolPConfig
  - qaGobiApilms.h, [1463](#)
- SLQSGetImageInfo
  - qaGobiApiFms.h, [1456](#)
- SLQSGetImageInfo\_9x15
  - qaGobiApiFms.h, [1456](#)
- SLQSGetImageInfoMC77xx
  - qaGobiApiFms.h, [1457](#)
- SLQSGetImageInfoMC83xx
  - qaGobiApiFms.h, [1458](#)
- SLQSGetIndicationRegister
  - qaGobiApiSms.h, [1568](#)
- SLQSGetM2MAVMute
  - qaGobiApiSwiAudio.h, [1585](#)
- SLQSGetM2MAudioProfile
  - qaGobiApiSwiAudio.h, [1584](#)
- SLQSGetM2MAudioVolume
  - qaGobiApiSwiAudio.h, [1585](#)
- SLQSGetM2MSpkrGain
  - qaGobiApiSwiAudio.h, [1586](#)
- SLQSGetMessageWaiting
  - qaGobiApiSms.h, [1569](#)
- SLQSGetNetStatistic
  - qaGobiApiDcs.h, [1395](#)
- SLQSGetNetworkTime
  - qaGobiApiNas.h, [1509](#)
- SLQSGetOperatorNameData
  - qaGobiApiNas.h, [1510](#)
- SLQSGetPLMNName
  - qaGobiApiNas.h, [1510](#)
- SLQSGetPacketStatistics
  - qaGobiApiWds.h, [1720](#)
- SLQSGetPidof
  - qaGobiApiSwi.h, [1583](#)
- SLQSGetProfile
  - qaGobiApiWds.h, [1721](#)
- SLQSGetProfileSettings
  - qaGobiApiWds.h, [1723](#)
- SLQSGetRegMgrConfig
  - qaGobiApilms.h, [1463](#)
- SLQSGetRfSarState
  - qaGobiApiSar.h, [1555](#)
- SLQSGetRuntimeSettings
  - qaGobiApiWds.h, [1723](#)
- SLQSGetSIPConfig
  - qaGobiApilms.h, [1464](#)
- SLQSGetSMS
  - qaGobiApiSms.h, [1569](#)
- SLQSGetSMSList
  - qaGobiApiSms.h, [1571](#)
- SLQSGetSdkVersion
  - qaGobiApiSwi.h, [1583](#)
- SLQSGetSerialNumbers
  - qaGobiApiDms.h, [1427](#)
- SLQSGetServingSystem
  - qaGobiApiNas.h, [1510](#)
- SLQSGetSessionState
  - qaGobiApiWds.h, [1724](#)
- SLQSGetSignalStrength
  - qaGobiApiNas.h, [1511](#)
- SLQSGetSmsBroadcastConfig
  - qaGobiApiSms.h, [1570](#)
- SLQSGetSysSelectionPref
  - qaGobiApiNas.h, [1511](#)
- SLQSGetTransLayerInfo
  - qaGobiApiSms.h, [1572](#)
- SLQSGetTransNWRRegInfo
  - qaGobiApiSms.h, [1572](#)
- SLQSGetUsbPortNames
  - qaGobiApiDcs.h, [1396](#)
- SLQSGetValidFwPriCombinations
  - qaGobiApiFms.h, [1458](#)
- SLQSImsConfigIndicationRegister
  - qaGobiApilms.h, [1464](#)
- SLQSInitiateNetworkRegistration
  - qaGobiApiNas.h, [1512](#)
- SLQSIspkgFormatRequired
  - qaGobiApiFms.h, [1459](#)
- SLQSKillSDKProcess
  - qaGobiApiDcs.h, [1396](#)
- SLQSLOCDelAssData
  - qaGobiApiLoc.h, [1472](#)
- SLQSLOCEventRegister
  - qaGobiApiLoc.h, [1472](#)
- SLQSLOCInjectPosition
  - qaGobiApiLoc.h, [1472](#)
- SLQSLOCInjectSensorData
  - qaGobiApiLoc.h, [1473](#)
- SLQSLOCInjectUTCTime
  - qaGobiApiLoc.h, [1473](#)
- SLQSLOCSetCradleMountConfig

- qaGobiApiLoc.h, [1474](#)
- SLQSLOCSetExtPowerState
  - qaGobiApiLoc.h, [1474](#)
- SLQSLOCSetOpMode
  - qaGobiApiLoc.h, [1474](#)
- SLQSLOCStart
  - qaGobiApiLoc.h, [1475](#)
- SLQSLOCStop
  - qaGobiApiLoc.h, [1475](#)
- SLQSModifyProfile
  - qaGobiApiWds.h, [1724](#)
- SLQSModifySMSStatus
  - qaGobiApiSms.h, [1573](#)
- SLQSNASGetLTECPHYCaInfo
  - qaGobiApiNas.h, [1514](#)
- SLQSNASSwiGetChannelLock
  - qaGobiApiNas.h, [1518](#)
- SLQSNASSwiSetChannelLock
  - qaGobiApiNas.h, [1519](#)
- SLQSNasConfigSigInfo2
  - qaGobiApiNas.h, [1512](#)
- SLQSNasGet3GPP2Subscription
  - qaGobiApiNas.h, [1513](#)
- SLQSNasGetCellLocationInfo
  - qaGobiApiNas.h, [1513](#)
- SLQSNasGetHDRColorCode
  - qaGobiApiNas.h, [1514](#)
- SLQSNasGetSigInfo
  - qaGobiApiNas.h, [1514](#)
- SLQSNasGetSysInfo
  - qaGobiApiNas.h, [1515](#)
- SLQSNasGetTxRxInfo
  - qaGobiApiNas.h, [1515](#)
- SLQSNasIndicationRegister
  - qaGobiApiNas.h, [1516](#)
- SLQSNasIndicationRegisterExt
  - qaGobiApiNas.h, [1517](#)
- SLQSNasIndicationRegisterLTECphyCa
  - qaGobiApiNas.h, [1518](#)
- SLQSNasNetworkTimeCallBack
  - qaGobiApiCbk.h, [1365](#)
- SLQSNasSigInfo2CallBack
  - qaGobiApiCbk.h, [1365](#)
- SLQSNasSigInfoCallBack
  - qaGobiApiCbk.h, [1366](#)
- SLQSNasSwiIndicationRegister
  - qaGobiApiNas.h, [1519](#)
- SLQSNasSwiModemStatus
  - qaGobiApiNas.h, [1519](#)
- SLQSNasSwiOTAMessageCallback
  - qaGobiApiCbk.h, [1366](#)
- SLQSNasSysInfoCallBack
  - qaGobiApiCbk.h, [1367](#)
- SLQSOMADMCancelSession
  - qaGobiApiSwiOmadms.h, [1595](#)
- SLQSOMADMGetSessionInfo
  - qaGobiApiSwiOmadms.h, [1595](#)
- SLQSOMADMGetSettings
  - qaGobiApiSwiOmadms.h, [1596](#)
- SLQSOMADMGetSettings2
  - qaGobiApiSwiOmadms.h, [1597](#)
- SLQSOMADMSendSelection
  - qaGobiApiSwiOmadms.h, [1597](#)
- SLQSOMADMSendSelection2
  - qaGobiApiSwiOmadms.h, [1598](#)
- SLQSOMADMSessionInfo
  - qaGobiApiSwiOmadms.h, [1590](#)
- SLQSOMADMSetSettings
  - qaGobiApiSwiOmadms.h, [1598](#)
- SLQSOMADMSetSettings2
  - qaGobiApiSwiOmadms.h, [1599](#)
- SLQSOMADMSetSettings3
  - qaGobiApiSwiOmadms.h, [1599](#)
- SLQSOMADMSettings
  - qaGobiApiSwiOmadms.h, [1592](#)
- SLQSOMADMSettingsReqParams
  - qaGobiApiSwiOmadms.h, [1593](#)
- SLQSOMADMSettingsReqParams3
  - qaGobiApiSwiOmadms.h, [1594](#)
- SLQSOMADMStartSession
  - qaGobiApiSwiOmadms.h, [1600](#)
- SLQSOMADMStartSession2
  - qaGobiApiSwiOmadms.h, [1600](#)
- SLQSOriginateUSSD
  - qaGobiApiVoice.h, [1659](#)
- SLQSPDSDeterminePosition
  - qaGobiApiPds.h, [1540](#)
- SLQSPDSInjectAbsoluteTimeReference
  - qaGobiApiPds.h, [1541](#)
- SLQSPDSInjectPositionData
  - qaGobiApiPds.h, [1541](#)
- SLQSPerformNetworkScan
  - qaGobiApiNas.h, [1520](#)
- SLQSQosClearMap
  - qaGobiApiDcs.h, [1397](#)
- SLQSQosDumpMap
  - qaGobiApiDcs.h, [1397](#)
- SLQSQosEditMap
  - qaGobiApiDcs.h, [1397](#)
- SLQSQosGetFlowStatus
  - qaGobiApiQos.h, [1546](#)
- SLQSQosGetGranted
  - qaGobiApiQos.h, [1547](#)
- SLQSQosGetNWProf
  - qaGobiApiQos.h, [1548](#)
- SLQSQosGetNetworkStatus
  - qaGobiApiQos.h, [1547](#)
- SLQSQosMap
  - qaGobiApiDcs.h, [1398](#)
- SLQSQosModify
  - qaGobiApiQos.h, [1548](#)
- SLQSQosReadMap
  - qaGobiApiDcs.h, [1398](#)
- SLQSQosRel
  - qaGobiApiQos.h, [1549](#)
- SLQSQosReq



- qaGobiApiQos.h, [1549](#)
- SLQSQosReset
  - qaGobiApiQos.h, [1550](#)
- SLQSQosResume
  - qaGobiApiQos.h, [1550](#)
- SLQSQosSuspend
  - qaGobiApiQos.h, [1551](#)
- SLQSQosSwiReadApnExtraParams
  - qaGobiApiQos.h, [1551](#)
- SLQSQosSwiReadDataStats
  - qaGobiApiQos.h, [1552](#)
- SLQSQosUnmap
  - qaGobiApiDcs.h, [1398](#)
- SLQSRegisterIMSAIndication
  - qaGobiApilmsa.h, [1470](#)
- SLQSResetPacketStatics
  - qaGobiApiWds.h, [1725](#)
- SLQSSGetDHCPv4ClientConfig
  - qaGobiApiWds.h, [1728](#)
- SLQSSGetLoopback
  - qaGobiApiWds.h, [1728](#)
- SLQSSSTlv
  - unpack\_nas\_SetEventReportInd\_t, [998](#)
- SLQSSSetDHCPv4ClientConfig
  - qaGobiApiWds.h, [1729](#)
- SLQSSSetLoopback
  - qaGobiApiWds.h, [1729](#)
- SLQSSendAsyncSMS
  - qaGobiApiSms.h, [1574](#)
- SLQSSendLongSMS
  - qaGobiApiSms.h, [1574](#)
- SLQSSendRawQMI
  - qaGobiApiSwi.h, [1583](#)
- SLQSSendSMS
  - qaGobiApiSms.h, [1575](#)
- SLQSSet3GPPConfigItem
  - qaGobiApiWds.h, [1725](#)
- SLQSSetAGPSConfig
  - qaGobiApiPds.h, [1542](#)
- SLQSSetAudioPathConfig
  - qaGobiApiAudio.h, [1292](#)
- SLQSSetAudioProfile
  - qaGobiApiAudio.h, [1293](#)
- SLQSSetAudioVolTLBConfig
  - qaGobiApiAudio.h, [1293](#)
- SLQSSetBandPreference
  - qaGobiApiNas.h, [1520](#)
- SLQSSetBandPreferenceCbk
  - qaGobiApiCbk.h, [1367](#)
- SLQSSetCustFeatures
  - qaGobiApiDms.h, [1428](#)
- SLQSSetCustFeaturesV2
  - qaGobiApiDms.h, [1428](#)
- SLQSSetDHCPv4ClientLeaseStatusCallback
  - qaGobiApiCbk.h, [1369](#)
- SLQSSetDUNCallInfoCallback
  - qaGobiApiCbk.h, [1369](#)
- SLQSSetDataSystemStatusCallback
  - qaGobiApiCbk.h, [1367](#)
- SLQSSetIMSApdpStatusCallback
  - qaGobiApiCbk.h, [1370](#)
- SLQSSetIMSARegStatusCallback
  - qaGobiApiCbk.h, [1370](#)
- SLQSSetIMSARegStatusCallback
  - qaGobiApiCbk.h, [1370](#)
- SLQSSetIMSARegStatusCallback
  - qaGobiApiCbk.h, [1371](#)
- SLQSSetIMSSMSConfig
  - qaGobiApilms.h, [1465](#)
- SLQSSetIMSSMSConfigCallback
  - qaGobiApiCbk.h, [1371](#)
- SLQSSetIMSUserConfig
  - qaGobiApilms.h, [1465](#)
- SLQSSetIMSUserConfigCallback
  - qaGobiApiCbk.h, [1372](#)
- SLQSSetIMSVoIPConfig
  - qaGobiApilms.h, [1466](#)
- SLQSSetIMSVoIPConfigCallback
  - qaGobiApiCbk.h, [1372](#)
- SLQSSetIndicationRegister
  - qaGobiApiSms.h, [1576](#)
- SLQSSetLocInjectPositionCallback
  - qaGobiApiCbk.h, [1372](#)
- SLQSSetLocInjectUTCtimeCallback
  - qaGobiApiCbk.h, [1373](#)
- SLQSSetLoggingMask
  - qaGobiApiDcs.h, [1399](#)
- SLQSSetM2MAVMute
  - qaGobiApiSwiAudio.h, [1588](#)
- SLQSSetM2MAudioAVCFG
  - qaGobiApiSwiAudio.h, [1586](#)
- SLQSSetM2MAudioLPBK
  - qaGobiApiSwiAudio.h, [1587](#)
- SLQSSetM2MAudioNVDef
  - qaGobiApiSwiAudio.h, [1587](#)
- SLQSSetM2MAudioProfile
  - qaGobiApiSwiAudio.h, [1587](#)
- SLQSSetM2MAudioVolume
  - qaGobiApiSwiAudio.h, [1588](#)
- SLQSSetM2MSpkrGain
  - qaGobiApiSwiAudio.h, [1589](#)
- SLQSSetModemTempCallback
  - qaGobiApiCbk.h, [1373](#)
- SLQSSetPacketSrvStatusCallback
  - qaGobiApiCbk.h, [1373](#)
- SLQSSetPositionMethodState
  - qaGobiApiPds.h, [1542](#)
- SLQSSetProfile
  - qaGobiApiWds.h, [1725](#)
- SLQSSetQosEventCallback
  - qaGobiApiCbk.h, [1374](#)
- SLQSSetQosNWStatusCallback
  - qaGobiApiCbk.h, [1374](#)
- SLQSSetQosPriEventCallback
  - qaGobiApiCbk.h, [1374](#)
- SLQSSetQosStatusCallback

- qaGobiApiCbk.h, [1376](#)
- SLQSSetRegMgrConfig
  - qaGobiApiIms.h, [1466](#)
- SLQSSetRegMgrConfigCallback
  - qaGobiApiCbk.h, [1376](#)
- SLQSSetRfSarState
  - qaGobiApiSar.h, [1555](#)
- SLQSSetSDKTerminatedCallback
  - qaGobiApiCbk.h, [1377](#)
- SLQSSetSIPConfig
  - qaGobiApiIms.h, [1467](#)
- SLQSSetSIPConfigCallback
  - qaGobiApiCbk.h, [1378](#)
- SLQSSetSMSEventCallback
  - qaGobiApiCbk.h, [1380](#)
- SLQSSetServingSystemCallback
  - qaGobiApiCbk.h, [1377](#)
- SLQSSetSessionStateCallback
  - qaGobiApiCbk.h, [1377](#)
- SLQSSetSignalStrengthsCallback
  - qaGobiApiCbk.h, [1378](#)
- SLQSSetSmsBroadcastActivation
  - qaGobiApiSms.h, [1576](#)
- SLQSSetSmsBroadcastConfig
  - qaGobiApiSms.h, [1577](#)
- SLQSSetSmsStorage
  - qaGobiApiSms.h, [1578](#)
- SLQSSetSwiGetResetInfoCallback
  - qaGobiApiCbk.h, [1380](#)
- SLQSSetSwiHDRPersCallback
  - qaGobiApiCbk.h, [1380](#)
- SLQSSetSysSelectionPref
  - qaGobiApiNas.h, [1522](#)
- SLQSSetSysSelectionPrefCallBack
  - qaGobiApiCbk.h, [1381](#)
- SLQSSetTransLayerInfoCallback
  - qaGobiApiCbk.h, [1381](#)
- SLQSSetTransNWRegInfoCallback
  - qaGobiApiCbk.h, [1381](#)
- SLQSSetWdsEventCallback
  - qaGobiApiCbk.h, [1383](#)
- SLQSSetWdsTransferStatisticCallback
  - qaGobiApiCbk.h, [1384](#)
- SLQSSignalStrengthsIndReq, [817](#)
  - ecioDelta, [818](#)
  - ecioThresholdList, [818](#)
  - ecioThresholdListLen, [819](#)
  - ioDelta, [819](#)
  - lteRsrpDelta, [819](#)
  - lteSnrDelta, [819](#)
  - rsrqDelta, [819](#)
  - rxSignalStrengthDelta, [819](#)
  - sinrDelta, [819](#)
  - sinrThresholdList, [819](#)
  - sinrThresholdListLen, [819](#)
- SLQSSignalStrengthsInformation, [819](#)
  - ecioInfo, [820](#)
  - errorRateInfo, [820](#)
  - io, [820](#)
  - lteRsrpinfo, [820](#)
  - lteSnrinfo, [820](#)
  - rsrqInfo, [820](#)
  - rxSignalStrengthInfo, [820](#)
  - sinr, [820](#)
- SLQSSmsGetMaxStorageSize
  - qaGobiApiSms.h, [1578](#)
- SLQSSmsGetMessageProtocol
  - qaGobiApiSms.h, [1579](#)
- SLQSSmsSetRoutes
  - qaGobiApiSms.h, [1579](#)
- SLQSSstart
  - qaGobiApiDcs.h, [1399](#)
- SLQSSstart\_AVAgent
  - qaGobiApiDcs.h, [1400](#)
- SLQSSstartSrv
  - qaGobiApiDcs.h, [1400](#)
- SLQSSstartStopDataSession
  - qaGobiApiWds.h, [1729](#)
- SLQSSwiClearDyingGaspStatistics
  - qaGobiApiDms.h, [1428](#)
- SLQSSwiGetAllCarrierImages
  - qaGobiApiFms.h, [1459](#)
- SLQSSwiGetCrashAction
  - qaGobiApiDms.h, [1429](#)
- SLQSSwiGetCrashInfo
  - qaGobiApiDms.h, [1429](#)
- SLQSSwiGetDyingGaspCfg
  - qaGobiApiDms.h, [1430](#)
- SLQSSwiGetDyingGaspStatistics
  - qaGobiApiDms.h, [1430](#)
- SLQSSwiGetFSN
  - qaGobiApiDms.h, [1430](#)
- SLQSSwiGetFirmwareCurr
  - qaGobiApiDms.h, [1430](#)
- SLQSSwiGetFwUpdateStatus
  - qaGobiApiDms.h, [1431](#)
- SLQSSwiGetHDRPersonality
  - qaGobiApiNas.h, [1522](#)
- SLQSSwiGetHDRProtSubtype
  - qaGobiApiNas.h, [1522](#)
- SLQSSwiGetHRPDStats
  - qaGobiApiNas.h, [1523](#)
- SLQSSwiGetHostDevInfo
  - qaGobiApiDms.h, [1431](#)
- SLQSSwiGetHostDevInfoParams
  - qaGobiApiDms.h, [1409](#)
- SLQSSwiGetLteCQI
  - qaGobiApiNas.h, [1523](#)
- SLQSSwiGetOSInfo
  - qaGobiApiDms.h, [1432](#)
- SLQSSwiGetOSInfoParams
  - qaGobiApiDms.h, [1410](#)
- SLQSSwiGetSMSStorage
  - qaGobiApiSms.h, [1579](#)
- SLQSSwiGetSerialNoExt
  - qaGobiApiDms.h, [1432](#)



- SLQSSwiGetSerialNoExtParams
  - qaGobiApiDms.h, [1410](#)
- SLQSSwiGetUSBComp
  - qaGobiApiDms.h, [1433](#)
- SLQSSwiNetworkDebug
  - qaGobiApiNas.h, [1524](#)
- SLQSSwiPSDetach
  - qaGobiApiNas.h, [1524](#)
- SLQSSwiSetCrashAction
  - qaGobiApiDms.h, [1433](#)
- SLQSSwiSetDyingGaspCfg
  - qaGobiApiDms.h, [1434](#)
- SLQSSwiSetHostDevInfo
  - qaGobiApiDms.h, [1434](#)
- SLQSSwiSetHostDevInfoParams
  - qaGobiApiDms.h, [1411](#)
- SLQSSwiSetOSInfo
  - qaGobiApiDms.h, [1434](#)
- SLQSSwiSetOSInfoParams
  - qaGobiApiDms.h, [1411](#)
- SLQSSwiSetUSBComp
  - qaGobiApiDms.h, [1435](#)
- SLQSTmdDeRegNotMitigationLvl
  - qaGobiApiTmd.h, [1639](#)
- SLQSTmdGetMitigationDevList
  - qaGobiApiTmd.h, [1639](#)
- SLQSTmdGetMitigationLvl
  - qaGobiApiTmd.h, [1640](#)
- SLQSTmdMitigationLvlRptCallback
  - qaGobiApiCbk.h, [1384](#)
- SLQSTmdRegNotMitigationLvl
  - qaGobiApiTmd.h, [1640](#)
- SLQSUIAuthenticate
  - qaGobiApiUim.h, [1643](#)
- SLQSUIChangePin
  - qaGobiApiUim.h, [1643](#)
- SLQSUIDepersonalization
  - qaGobiApiUim.h, [1644](#)
- SLQSUIEventRegister
  - qaGobiApiUim.h, [1644](#)
- SLQSUIGetCardStatus
  - qaGobiApiUim.h, [1646](#)
- SLQSUIGetConfiguration
  - qaGobiApiUim.h, [1646](#)
- SLQSUIGetFileAttributes
  - qaGobiApiUim.h, [1647](#)
- SLQSUIGetSlotsStatus
  - qaGobiApiUim.h, [1647](#)
- SLQSUIGetState
  - qaGobiApiDms.h, [1435](#)
- SLQSUIPowerDown
  - qaGobiApiUim.h, [1648](#)
- SLQSUIPowerUp
  - qaGobiApiUim.h, [1648](#)
- SLQSUIReadTransparent
  - qaGobiApiUim.h, [1649](#)
- SLQSUIRefreshComplete
  - qaGobiApiUim.h, [1649](#)
- SLQSUIRefreshGetLastEvent
  - qaGobiApiUim.h, [1650](#)
- SLQSUIRefreshOK
  - qaGobiApiUim.h, [1650](#)
- SLQSUIRefreshRegister
  - qaGobiApiUim.h, [1651](#)
- SLQSUIReset
  - qaGobiApiUim.h, [1651](#)
- SLQSUISetPinProtection
  - qaGobiApiUim.h, [1652](#)
- SLQSUISetRefreshCallBack
  - qaGobiApiCbk.h, [1385](#)
- SLQSUISetStatusChangeCallBack
  - qaGobiApiCbk.h, [1385](#)
- SLQSUISwitchSlot
  - qaGobiApiUim.h, [1652](#)
- SLQSUIUnblockPin
  - qaGobiApiUim.h, [1653](#)
- SLQSUIVerifyPin
  - qaGobiApiUim.h, [1653](#)
- SLQSupgradeFirmware9x15
  - qaGobiApiFms.h, [1459](#)
- SLQSVoiceALSSelectLine
  - qaGobiApiVoice.h, [1659](#)
- SLQSVoiceALSSetLineSwitching
  - qaGobiApiVoice.h, [1660](#)
- SLQSVoiceAnswerCall
  - qaGobiApiVoice.h, [1660](#)
- SLQSVoiceBindSubscription
  - qaGobiApiVoice.h, [1661](#)
- SLQSVoiceBurstDTMF
  - qaGobiApiVoice.h, [1661](#)
- SLQSVoiceDialCall
  - qaGobiApiVoice.h, [1662](#)
- SLQSVoiceEndCall
  - qaGobiApiVoice.h, [1662](#)
- SLQSVoiceGetAllCallInfo
  - qaGobiApiVoice.h, [1664](#)
- SLQSVoiceGetCLIP
  - qaGobiApiVoice.h, [1667](#)
- SLQSVoiceGetCLIR
  - qaGobiApiVoice.h, [1667](#)
- SLQSVoiceGetCNAP
  - qaGobiApiVoice.h, [1668](#)
- SLQSVoiceGetCOLP
  - qaGobiApiVoice.h, [1668](#)
- SLQSVoiceGetCOLR
  - qaGobiApiVoice.h, [1669](#)
- SLQSVoiceGetCallBarring
  - qaGobiApiVoice.h, [1664](#)
- SLQSVoiceGetCallForwardingStatus
  - qaGobiApiVoice.h, [1665](#)
- SLQSVoiceGetCallInfo
  - qaGobiApiVoice.h, [1666](#)
- SLQSVoiceGetCallWaiting
  - qaGobiApiVoice.h, [1666](#)
- SLQSVoiceGetConfig
  - qaGobiApiVoice.h, [1669](#)

- SLQSVoiceIndicationRegister
  - qaGobiApiVoice.h, [1671](#)
- SLQSVoiceInfoRecCallback
  - qaGobiApiCbK.h, [1385](#)
- SLQSVoiceManageCalls
  - qaGobiApiVoice.h, [1671](#)
- SLQSVoiceOrigUSSDNoWait
  - qaGobiApiVoice.h, [1672](#)
- SLQSVoiceSendFlash
  - qaGobiApiVoice.h, [1672](#)
- SLQSVoiceSetAllCallStatusCallBack
  - qaGobiApiCbK.h, [1386](#)
- SLQSVoiceSetCallBarringPassword
  - qaGobiApiVoice.h, [1674](#)
- SLQSVoiceSetConfig
  - qaGobiApiVoice.h, [1674](#)
- SLQSVoiceSetDTMFEventCallBack
  - qaGobiApiCbK.h, [1386](#)
- SLQSVoiceSetOTASPStatusCallBack
  - qaGobiApiCbK.h, [1387](#)
- SLQSVoiceSetPreferredPrivacy
  - qaGobiApiVoice.h, [1676](#)
- SLQSVoiceSetPrivacyChangeCallBack
  - qaGobiApiCbK.h, [1387](#)
- SLQSVoiceSetSUPSCallBack
  - qaGobiApiCbK.h, [1387](#)
- SLQSVoiceSetSUPSNotificationCallback
  - qaGobiApiCbK.h, [1389](#)
- SLQSVoiceSetSUPSService
  - qaGobiApiVoice.h, [1676](#)
- SLQSVoiceStartContDTMF
  - qaGobiApiVoice.h, [1678](#)
- SLQSVoiceStopContDTMF
  - qaGobiApiVoice.h, [1678](#)
- SLQSWCDMADecodeLongTextMsg
  - qaGobiApiSms.h, [1581](#)
- SLQSWCDMADecodeMTTextMsg
  - qaGobiApiSms.h, [1581](#)
- SLQSWCDMAEncodeMOTextMsg
  - qaGobiApiSms.h, [1582](#)
- SLQSWdsGoActive
  - qaGobiApiWds.h, [1730](#)
- SLQSWdsGoDormant
  - qaGobiApiWds.h, [1730](#)
- SLQSWdsSetEventReport
  - qaGobiApiWds.h, [1731](#)
- SLQSWdsSwiPDPRuntimeSettings
  - qaGobiApiWds.h, [1731](#)
- SLQSWmsAsyncRawSendCallBack
  - qaGobiApiCbK.h, [1389](#)
- SLQSWmsMemoryFullCallBack
  - qaGobiApiCbK.h, [1390](#)
- SLQSWmsMessageWaitingCallBack
  - qaGobiApiCbK.h, [1390](#)
- SMSAsyncRawSend
  - qaGobiApiCbK.h, [1313](#)
- SMSAsyncRawSend\_s, [823](#)
  - alphaIDLen, [825](#)
  - causeCode, [825](#)
  - errorClass, [825](#)
  - messageID, [825](#)
  - msgDelFailureCause, [825](#)
  - msgDelFailureType, [825](#)
  - pAlphaID, [825](#)
  - RPCause, [825](#)
  - sendStatus, [825](#)
  - TPCause, [825](#)
  - userData, [825](#)
- SMSCAddress, [826](#)
  - data, [826](#)
  - length, [826](#)
- sMSCAddress, [825](#)
  - data, [826](#)
  - length, [826](#)
- SMSCAddressInfo
  - qaGobiApiCbK.h, [1315](#)
- sMSCAddressInfo
  - sms.h, [1753](#)
- sMSCAddressTlv, [826](#)
  - SMSCInfo, [827](#)
  - TlvPresent, [827](#)
- SMSCInfo
  - sMSCAddressTlv, [827](#)
- SMSCtlv
  - unpack\_sms\_SetNewSMSCallback\_ind\_t, [1052](#)
- SMSEtwsMessage, [827](#)
  - data, [828](#)
  - length, [828](#)
  - notificationType, [828](#)
- sMSEtwsMessage, [827](#)
  - data, [827](#)
  - length, [827](#)
  - notificationType, [827](#)
- SMSEtwsMessageInfo
  - qaGobiApiCbK.h, [1315](#)
- sMSEtwsMessageInfo
  - sms.h, [1753](#)
- sMSEtwsMessageTlv, [828](#)
  - EtwsMessageInfo, [828](#)
  - TlvPresent, [829](#)
- SMSEtwsPlmn, [829](#)
  - mobileCountryCode, [830](#)
  - mobileNetworkCode, [830](#)
- sMSEtwsPlmn, [829](#)
  - mobileCountryCode, [829](#)
  - mobileNetworkCode, [829](#)
- SMSEtwsPlmnInfo
  - qaGobiApiCbK.h, [1315](#)
- sMSEtwsPlmnInfo
  - sms.h, [1753](#)
- SMSEventInfo
  - qaGobiApiCbK.h, [1315](#)
- SMSEventInfo\_s, [830](#)
  - pEtwsMessageInfo, [831](#)
  - pEtwsPlmnInfo, [831](#)
  - pMTMessageInfo, [831](#)

- pMessageModelInfo, [831](#)
  - pSMSCAddressInfo, [831](#)
  - pSMSOnIMSInfo, [831](#)
  - pTransferRouteMTMessageInfo, [831](#)
  - smsEventType, [831](#)
- SMSEventType
  - qaGobiApiCbk.h, [1349](#)
- SMSMTMessage, [835](#)
  - messageIndex, [836](#)
  - storageType, [836](#)
- sMSMTMessage, [835](#)
  - messageIndex, [835](#)
  - storageType, [835](#)
- SMSMTMessageInfo
  - qaGobiApiCbk.h, [1317](#)
- sMSMTMessageInfo
  - sms.h, [1754](#)
- SMSMemoryInfo, [832](#)
  - messageMode, [834](#)
  - storageType, [834](#)
- SMSMessageMode, [834](#)
  - messageMode, [834](#)
- sMSMessageMode, [834](#)
  - messageMode, [834](#)
- SMSMessageModelInfo
  - qaGobiApiCbk.h, [1317](#)
- sMSMessageModelInfo
  - sms.h, [1753](#)
- SMSOnIMS, [836](#)
  - smsOnIMS, [837](#)
- sMSOnIMS, [836](#)
  - smsOnIMS, [836](#)
- SMSOnIMSInfo
  - qaGobiApiCbk.h, [1318](#)
- sMSOnIMSInfo
  - sms.h, [1754](#)
- sMSOnIMSTlv, [837](#)
  - IMSInfo, [837](#)
  - TlvPresent, [837](#)
- SMSSupport
  - pack\_dms\_SetCustFeature\_t, [584](#)
  - unpack\_dms\_GetCustFeature\_t, [954](#)
- SMSTransferRouteMTMessage, [840](#)
  - ackIndicator, [841](#)
  - data, [841](#)
  - format, [841](#)
  - length, [841](#)
  - transactionID, [841](#)
- sMSTransferRouteMTMessage, [839](#)
  - ackIndicator, [840](#)
  - data, [840](#)
  - format, [840](#)
  - length, [840](#)
  - transactionID, [840](#)
- SMSTransferRouteMTMessageInfo
  - qaGobiApiCbk.h, [1318](#)
- sMSTransferRouteMTMessageInfo
  - sms.h, [1754](#)
- SNR
  - NetworkStatEVDO, [567](#)
- sNonIntraSearch
  - LTEInfoIntrafreq, [411](#)
  - nas\_LTEInfoIntrafreq, [476](#)
- SO
  - NetworkStat1x, [565](#)
- SOMask
  - CurrNetworkInfo, [194](#)
  - currNetworkInfo, [194](#)
  - wds\_currNetworkInfo, [1175](#)
- sPhyCaAggPcellInfo
  - nasGetLTECphyCa, [527](#)
  - QmiCbkNasLTECphyCaInfo, [715](#)
- sPhyCaAggScellDIBw
  - nasGetLTECphyCa, [527](#)
  - QmiCbkNasLTECphyCaInfo, [715](#)
- sPhyCaAggScellIndType
  - nasGetLTECphyCa, [527](#)
  - QmiCbkNasLTECphyCaInfo, [715](#)
- sPhyCaAggScellIndex
  - nasGetLTECphyCa, [527](#)
  - QmiCbkNasLTECphyCaInfo, [715](#)
- sPhyCaAggScellInfo
  - nasGetLTECphyCa, [527](#)
  - QmiCbkNasLTECphyCaInfo, [715](#)
- sQosFlowStat, [841](#)
  - bearerId, [842](#)
  - tx\_bytes, [842](#)
  - tx\_bytes\_drp, [842](#)
  - tx\_pkt, [842](#)
  - tx\_pkt\_drp, [842](#)
- sQosStat, [842](#)
  - apnId, [843](#)
  - numQosFlow, [843](#)
  - qosFlow, [843](#)
  - total\_rx\_bytes, [843](#)
  - total\_rx\_pkt, [843](#)
  - total\_tx\_bytes, [843](#)
  - total\_tx\_bytes\_drp, [843](#)
  - total\_tx\_pkt, [843](#)
  - total\_tx\_pkt\_drp, [843](#)
- SSInfo
  - unpack\_nas\_SetServingSystemCallback\_ind\_t, [1000](#)
- sSLQSSignalStrengthsInfo
  - nas\_SLQSSignalStrengthsTlv, [501](#)
- SSTlv
  - unpack\_nas\_SetEventReportInd\_t, [998](#)
- SUPInfo, [848](#)
  - isModByCC, [848](#)
  - svcType, [849](#)
- SUPInformation
  - voiceSUPInfo, [1158](#)
- SUPSType
  - voiceManageCallsReq, [1139](#)
- SV, [849](#)
  - id, [849](#)

- mask, [849](#)
- system, [850](#)
- SVInfo, [850](#)
  - len, [850](#)
  - pSV, [850](#)
- SWI Audio Service(SWIAUDIO), [50](#)
- SWI Open Mobile Alliance Service (SWIOMA), [43](#)
- SWI\_API
  - SwiDataTypes.h, [1761](#)
- SWI\_STRUCT\_CarrierImage, [851](#)
  - m\_FwBuildId, [852](#)
  - m\_FwImageld, [852](#)
  - m\_PriBuildId, [852](#)
  - m\_PrImageld, [852](#)
  - m\_nCarrierId, [852](#)
  - m\_nFolderId, [852](#)
  - m\_nStorage, [852](#)
- SWIWWANCMAPI.h, [1773](#)
- samplesPerBatch
  - accelAcceptReady\_s, [96](#)
  - accelTempAcceptReady\_s, [97](#)
  - gyroAcceptReady\_s, [301](#)
  - gyroTempAcceptReady\_s, [302](#)
- satelliteInfo, [755](#)
  - azimuth, [758](#)
  - elevation, [758](#)
  - gnssSvId, [758](#)
  - healthStatus, [758](#)
  - snr, [758](#)
  - svInfoMask, [758](#)
  - svListLen, [758](#)
  - svStatus, [758](#)
  - system, [758](#)
  - validMask, [758](#)
- SaveSMS
  - qaGobiApiSms.h, [1563](#)
- sbas\_almanac\_sv\_msk
  - GPSSStateInfo, [293](#)
- sbas\_ephemeris\_sv\_msk
  - GPSSStateInfo, [293](#)
- sbas\_health\_sv\_msk
  - GPSSStateInfo, [293](#)
- sbas\_visible\_sv\_msk
  - GPSSStateInfo, [293](#)
- scell\_idx
  - NASPhyCaAggScellIndex, [544](#)
  - PhyCaAggScellIndex, [668](#)
- scell\_state
  - NASPhyCaAggScellIndType, [545](#)
  - NASPhyCaAggScellInfo, [546](#)
  - PhyCaAggScellIndType, [669](#)
  - PhyCaAggScellInfo, [671](#)
- screeningInd
  - connectNumInfo, [181](#)
- sduErrorRatio
  - LibPackUMTSQoS, [374](#)
  - UMTSMInQoS, [945](#)
  - UMTSQoS, [949](#)
  - wds\_UMTSMInQoS, [1185](#)
- seDNSIPv4Address
  - unpack\_wds\_SLQSWdsSwpDPRuntimeSettings\_t, [1089](#)
- seDNSIPv6Address
  - unpack\_wds\_SLQSWdsSwpDPRuntimeSettings\_t, [1089](#)
- sePCSCFIPv4Address
  - unpack\_wds\_SLQSWdsSwpDPRuntimeSettings\_t, [1089](#)
- sePCSCFIPv6Address
  - unpack\_wds\_SLQSWdsSwpDPRuntimeSettings\_t, [1089](#)
- secActivate
  - fileAttributes, [241](#)
- secActivateMask
  - fileAttributes, [241](#)
- secChA
  - CDMAChannel, [152](#)
- secChB
  - CDMAChannel, [152](#)
- secDeactivate
  - fileAttributes, [241](#)
- secDeactivateMask
  - fileAttributes, [241](#)
- secIncrease
  - fileAttributes, [241](#)
- secIncreaseMask
  - fileAttributes, [241](#)
- SecProt
  - protocolSubtypeElement, [694](#)
- secRead
  - fileAttributes, [242](#)
- secReadMask
  - fileAttributes, [242](#)
- secWrite
  - fileAttributes, [242](#)
- secWriteMask
  - fileAttributes, [242](#)
- secdns
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- secdnsv6
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- second
  - nas\_timeInfo, [509](#)
  - nas\_UniversalTime, [515](#)
  - timeInfo, [883](#)
  - UniversalTime, [952](#)
- secondaryDNS
  - pack\_wds\_SetDefaultProfile\_t, [640](#)
- SecondaryDNSV4
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- SecondaryDNSV6
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- secondaryHA
  - unpack\_wds\_GetMobileIPProfile\_t, [1074](#)
- SectorIDLen
  - NetworkStatEVDO, [567](#)

- selNetwork
  - nas\_servSystem, 498
  - servSystem, 766
- selected
  - BroadcastConfig, 127
  - CDMABroadcastConfig, 151
- selectedNetwork
  - NASServingSystemInfo, 553
  - ServingSystemInfo, 764
- selection
  - pack\_swima\_SLQSOMADMSendSelection\_t, 627
- SendSMS
  - qaGobiApiSms.h, 1564
- sendStatus
  - SMSAsyncRawSend\_s, 825
- sensorData, 758
  - flags, 759
  - sensorDataLen, 759
  - timeOfFirstSample, 759
  - timeOffset, 759
  - xAxis, 760
  - yAxis, 760
  - zAxis, 760
- sensorDataLen
  - sensorData, 759
- sensorDataUsage
  - qaGobiApiCbk.h, 1313
- sensorDataUsage\_s, 760
  - aidingIndicatorMask, 760
  - usageMask, 760
- serialNumbersInfo, 760
  - esnSize, 761
  - imeiSize, 761
  - imeiSvnSize, 761
  - meidSize, 762
  - pESNString, 762
  - pIMEIString, 762
  - pImeiSvnString, 762
  - pMEIDString, 762
  - qaGobiApiDms.h, 1408
- servSystem, 764
  - csAttachState, 766
  - numRadioInterfaces, 766
  - psAttachState, 766
  - radioInterface, 766
  - regState, 766
  - selNetwork, 766
- ServerAddrList
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, 1083
- serviceCategory
  - CDMABroadcastConfig, 151
- serviceClassInformation
  - qaGobiApiVoice.h, 1657
- serviceDomain
  - nas\_RejectReasonTlv, 493
- serviceProviderName, 762
  - displayCondition, 762
  - spn, 762
  - spnLength, 762
- servingCellId
  - LTEInfoIntrafreq, 411
  - nas\_LTEInfoIntrafreq, 476
- ServingSystem
  - qaQmiServingSystemParam, 701
  - unpack\_nas\_SLQSGetServingSystem\_t, 1004
- ServingSystemInfo, 762
  - csAttachState, 764
  - hdrPersonality, 764
  - psAttachState, 764
  - radioInterfaceList, 764
  - radioInterfaceNo, 764
  - registrationState, 764
  - selectedNetwork, 764
- sessionEndReason
  - \_packetSrvStatus, 64
  - slqsSessionStateInfo, 813
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t, 1084
- SessionId
  - LOCStartReq, 402
  - pack\_loc\_Start\_t, 595
  - pack\_loc\_Stop\_t, 595
- sessionId
  - LOCStopReq, 402
  - QmiCbkLocPositionReportInd, 713
  - ssdatasession\_params, 847
  - unpack\_loc\_PositionRpt\_Ind\_t, 987
- sessionInfo, 766
  - omaDmConfig, 766
  - omaDmFota, 766
  - omaDmNotifications, 767
  - pack\_uim\_ChangePin\_t, 629
  - pack\_uim\_ReadTransparent\_t, 630
  - pack\_uim\_SetPinProtection\_t, 632
  - pack\_uim\_UnblockPin\_t, 634
  - pack\_uim\_VerifyPin\_t, 636
  - sessionInfoTlv, 767
  - sessionInfoTlvExt, 768
  - UIMAuthenticateReq, 914
  - UIMChangePinReq, 916
  - UIMGetFileAttributesReq, 920
  - UIMReadTransparentReq, 925
  - UIMRefreshCompleteReq, 926
  - UIMRefreshGetLastEventReq, 929
  - UIMRefreshOKReq, 929
  - UIMRefreshRegisterReq, 930
  - UIMSetPinProtectionReq, 932
  - UIMUnblockPinReq, 937
  - UIMVerifyPinReq, 938
- SessionInfoConfig
  - unpack\_swima\_SLQSOMADMAAlertCallback\_ind\_t, 1057
- sessionInfoExt, 767
  - omaDmConfig, 767
  - omaDmFota, 767

- SessionInfoFota
  - unpack\_swima\_SLQSOMADMAAlertCallback\_ind\_t, [1057](#)
- SessionInfoNotification
  - unpack\_swima\_SLQSOMADMAAlertCallback\_ind\_t, [1057](#)
- sessionInfoTlv, [767](#)
  - sessionInfo, [767](#)
  - sessionType, [767](#)
  - TlvPresent, [767](#)
- sessionInfoTlvExt, [767](#)
  - sessionInfo, [768](#)
  - sessionType, [768](#)
  - TlvPresent, [768](#)
- sessionInformation
  - qaGobiApiCbk.h, [1313](#)
- sessionInformationExt
  - qaGobiApiCbk.h, [1313](#)
- SessionState
  - unpack\_swima\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- sessionStatus
  - omaDmNotificationsTlv, [580](#)
  - QmiCbkLocPositionReportInd, [713](#)
  - unpack\_loc\_PositionRpt\_Ind\_t, [987](#)
  - unpack\_omaDmNotificationsTlv\_t, [1027](#)
- SessionType
  - pack\_swima\_SLQSOMADMGetSessionInfo\_t, [626](#)
  - unpack\_swima\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- sessionType
  - omaDmFotaTlv, [577](#)
  - pack\_swima\_SLQSOMADMCancelSession\_t, [625](#)
  - pack\_swima\_SLQSOMADMStartSession\_t, [628](#)
  - sessionInfoTlv, [767](#)
  - sessionInfoTlvExt, [768](#)
  - uim\_sessionInformation, [908](#)
  - uim\_UIMSessionInformation, [912](#)
  - UIMRefreshEvent, [928](#)
  - UIMSessionInformation, [931](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- set\_fix\_rate
  - pack\_swiloc\_SwiLocSetAutoStart\_t, [625](#)
  - SwiLocSetAutoStartReq, [857](#)
- set\_fix\_type
  - pack\_swiloc\_SwiLocSetAutoStart\_t, [625](#)
  - SwiLocSetAutoStartReq, [857](#)
- set\_function
  - pack\_swiloc\_SwiLocSetAutoStart\_t, [625](#)
  - SwiLocSetAutoStartReq, [857](#)
- set\_max\_dist
  - pack\_swiloc\_SwiLocSetAutoStart\_t, [625](#)
  - SwiLocSetAutoStartReq, [857](#)
- set\_max\_time
  - pack\_swiloc\_SwiLocSetAutoStart\_t, [625](#)
  - SwiLocSetAutoStartReq, [857](#)
- SetACCOLC
  - qaGobiApiNas.h, [1505](#)
- SetActivationStatusCallback
  - qaGobiApiCbk.h, [1350](#)
- SetActiveMobileIPProfile
  - qaGobiApiWds.h, [1703](#)
- SetAudioPathConfigReq, [768](#)
  - pCodecSTGain, [770](#)
  - pDTMFTXGain, [770](#)
  - pECMode, [770](#)
  - pNSEnable, [770](#)
  - pRXAGCList, [770](#)
  - pRXAVCAGCSwitch, [770](#)
  - pRXAVCList, [770](#)
  - pRXPCMIIRFtr, [770](#)
  - pTXAGCList, [770](#)
  - pTXAVCSwitch, [770](#)
  - pTXGain, [770](#)
  - pTXPCMIIRFtr, [770](#)
  - Profile, [770](#)
- SetAudioProfileReq, [770](#)
  - EarMute, [771](#)
  - Generator, [771](#)
  - MicMute, [771](#)
  - Profile, [771](#)
  - Volume, [772](#)
- SetAudioVolTLBConfigReq, [772](#)
  - Generator, [773](#)
  - Item, [773](#)
  - Profile, [773](#)
  - VolValue, [773](#)
  - Volume, [773](#)
- SetAudioVolTLBConfigResp, [773](#)
  - ResCode, [773](#)
- SetAutoconnect
  - qaGobiApiWds.h, [1705](#)
- SetCATEventCallback
  - qaGobiApiCbk.h, [1350](#)
- SetCDMANetworkParameters
  - qaGobiApiNas.h, [1506](#)
- setCustomSettingV2, [773](#)
  - cust\_id, [774](#)
  - cust\_value, [774](#)
  - value\_length, [774](#)
- SetDataCapabilitiesCallback
  - qaGobiApiCbk.h, [1352](#)
- SetDefaultProfile
  - qaGobiApiWds.h, [1705](#)
- SetDefaultProfileLTE
  - qaGobiApiWds.h, [1707](#)
- SetDefaultProfileLTEV2
  - qaGobiApiWds.h, [1709](#)
- SetDefaultProfileNum
  - qaGobiApiWds.h, [1711](#)
- SetDeviceStateChangeCbk
  - qaGobiApiCbk.h, [1352](#)
- setDyingGaspCfg, [774](#)
  - pDestSMSContent, [774](#)



- pDestSMSNum, [774](#)
- SetFwDldCompletionCbK
  - qaGobiApiCbK.h, [1352](#)
- SetGPSCallback
  - qaGobiApiCbK.h, [1353](#)
- SetIMSSMSConfigReq, [774](#)
  - pPhoneCtxtURI, [775](#)
  - pPhoneCtxtURILen, [775](#)
  - pSMSFormat, [775](#)
  - pSMSOverIPNwInd, [775](#)
- SetIMSSMSConfigResp, [775](#)
  - pSettingResp, [776](#)
- SetIMSUserConfigReq, [776](#)
  - pIMSDomain, [776](#)
  - pIMSDomainLen, [776](#)
- SetIMSUserConfigResp, [776](#)
  - pSettingResp, [777](#)
- SetIMSVoIPConfigReq, [777](#)
  - pAmrMode, [779](#)
  - pAmrOctetAligned, [779](#)
  - pAmrWBMode, [779](#)
  - pAmrWBOctetAligned, [779](#)
  - pAmrWbEnable, [779](#)
  - pMinSessionExpiryTimer, [779](#)
  - pRTPRTCPInactTimer, [779](#)
  - pRingBackTimer, [779](#)
  - pRingingTimer, [779](#)
  - pScrAmrEnable, [779](#)
  - pScrAmrWbEnable, [779](#)
  - pSessionExpiryTimer, [779](#)
- SetIMSVoIPConfigResp, [780](#)
  - pSettingResp, [780](#)
- SetImagesPreference
  - qaGobiApiFms.h, [1453](#)
- setIndicationRegReq
  - qaGobiApiSms.h, [1561](#)
- SetLURejectCallback
  - qaGobiApiCbK.h, [1357](#)
- SetLocCradleMountCallback
  - qaGobiApiCbK.h, [1353](#)
- SetLocDeleteAssistDataCallback
  - qaGobiApiCbK.h, [1353](#)
- SetLocEngineStateCallback
  - qaGobiApiCbK.h, [1355](#)
- SetLocEventPositionCallback
  - qaGobiApiCbK.h, [1355](#)
- SetLocEventTimeSyncCallback
  - qaGobiApiCbK.h, [1355](#)
- SetLocGnssSvInfoCallback
  - qaGobiApiCbK.h, [1355](#)
- SetLocInjectSensorDataCallback
  - qaGobiApiCbK.h, [1356](#)
- SetLocInjectTimeCallback
  - qaGobiApiCbK.h, [1356](#)
- SetLocOpModeCallback
  - qaGobiApiCbK.h, [1356](#)
- SetLocSensorStreamingCallback
  - qaGobiApiCbK.h, [1357](#)
- SetLocSetExtPowerConfigCallback
  - qaGobiApiCbK.h, [1357](#)
- SetM2MAVMuteReq, [783](#)
  - EarMute, [784](#)
  - MicMute, [784](#)
  - pCwtMute, [784](#)
  - Profile, [784](#)
- SetM2MAudioAVCFGReq, [780](#)
  - Device, [781](#)
  - PIFACEId, [781](#)
  - pPCMPParams, [781](#)
  - Profile, [781](#)
- SetM2MAudioLPBKReq, [781](#)
  - Enable, [781](#)
- SetM2MAudioProfileReq, [781](#)
  - pCwtMute, [782](#)
  - pEarMute, [782](#)
  - pGenerator, [782](#)
  - pMicMute, [782](#)
  - pVolume, [783](#)
  - Profile, [783](#)
- SetM2MAudioVolumeReq, [783](#)
  - Generator, [783](#)
  - Level, [783](#)
  - Profile, [783](#)
- SetM2MSpkrGainReq, [784](#)
  - Profile, [785](#)
  - Value, [785](#)
- SetMobileIP
  - qaGobiApiWds.h, [1711](#)
- SetMobileIPParameters
  - qaGobiApiWds.h, [1712](#)
- SetMobileIPProfile
  - qaGobiApiWds.h, [1713](#)
- SetMobileIPStatusCallback
  - qaGobiApiCbK.h, [1358](#)
- SetNMEACallback
  - qaGobiApiCbK.h, [1359](#)
- SetNasLTECphyCaIndCallback
  - qaGobiApiCbK.h, [1358](#)
- SetNetChangeCbK
  - qaGobiApiCbK.h, [1358](#)
- SetNetworkPreference
  - qaGobiApiNas.h, [1507](#)
- SetNewSMSCallback
  - qaGobiApiCbK.h, [1359](#)
- SetOMADMStateCallback
  - qaGobiApiCbK.h, [1360](#)
- SetPDSDDefaults
  - qaGobiApiPds.h, [1536](#)
- SetPDSSState
  - qaGobiApiPds.h, [1537](#)
- SetPDSSStateCallback
  - qaGobiApiCbK.h, [1360](#)
- setPINProtection, [785](#)
  - pinID, [786](#)
  - pinLength, [786](#)
  - pinOperation, [786](#)

- pinValue, [786](#)
- SetPortAutomaticTracking
  - qaGobiApiPds.h, [1537](#)
- SetPower
  - qaGobiApiDms.h, [1423](#)
- SetPowerCallback
  - qaGobiApiCbk.h, [1360](#)
- SetRFInfoCallback
  - qaGobiApiCbk.h, [1361](#)
- SetRMTransferStatisticsCallback
  - qaGobiApiCbk.h, [1361](#)
- SetRankIndicatorCallback
  - qaGobiApiCbk.h, [1361](#)
- SetRegMgrConfigReq, [786](#)
  - pCSCFPortName, [787](#)
  - pCSCFPortNameLen, [787](#)
  - pIMSTestMode, [787](#)
  - pPriCSCFPort, [787](#)
- SetRegMgrConfigResp, [787](#)
  - pSettingResp, [787](#)
- SetRoamingIndicatorCallback
  - qaGobiApiCbk.h, [1361](#)
- SetSDKImagePath
  - qaGobiApiDcs.h, [1395](#)
- SetSIPConfigReq, [793](#)
  - pSIPLocalPort, [794](#)
  - pSigCompEnabled, [794](#)
  - pSubscribeTimer, [794](#)
  - pTimerSIPReg, [794](#)
  - pTimerT1, [794](#)
  - pTimerT2, [794](#)
  - pTimerTf, [794](#)
- SetSIPConfigResp, [794](#)
  - pSettingResp, [794](#)
- SetSLQSOMADMAAlertCallback
  - qaGobiApiCbk.h, [1363](#)
- SetSLQSOMADMAAlertCallbackExt
  - qaGobiApiCbk.h, [1363](#)
- SetSMSCAddress
  - qaGobiApiSms.h, [1565](#)
- SetSMSWake
  - qaGobiApiRms.h, [1553](#)
- SetServiceAutomaticTracking
  - qaGobiApiPds.h, [1538](#)
- SetSignalStrengthCallback
  - qaGobiApiCbk.h, [1362](#)
- setSignalStrengthInfo, [788](#)
  - pCDMAECIODelta, [792](#)
  - pCDMAECIOThresh, [792](#)
  - pCDMARSSIDelta, [792](#)
  - pCDMARSSIThresh, [792](#)
  - pGSMRSSIDelta, [792](#)
  - pGSMRSSIThresh, [792](#)
  - pHDRECIODelta, [792](#)
  - pHDRECIOThresh, [792](#)
  - pHDRIODelta, [792](#)
  - pHDRIOThresh, [792](#)
  - pHRRSSIDelta, [792](#)
  - pHRRSSIThresh, [792](#)
  - pHRSINRDelta, [792](#)
  - pHRSINRThresh, [792](#)
  - pLTERSRPDelta, [792](#)
  - pLTERSRPThresh, [792](#)
  - pLTERSRQDelta, [792](#)
  - pLTERSRQThresh, [792](#)
  - pLTERSSIDelta, [792](#)
  - pLTERSSIThresh, [792](#)
  - pLTESNRDelta, [792](#)
  - pLTESNRThresh, [792](#)
  - pLTESigRptConfig, [792](#)
  - pTDSCDMAECIODelta, [792](#)
  - pTDSCDMAECIOThresh, [792](#)
  - pTDSCDMARSCPDelta, [792](#)
  - pTDSCDMARSCPThresh, [792](#)
  - pTDSCDMARSSIDelta, [792](#)
  - pTDSCDMARSSIThresh, [793](#)
  - pTDSCDMASINRDelta, [793](#)
  - pTDSCDMASINRThresh, [793](#)
  - pWCDMAECIODelta, [793](#)
  - pWCDMAECIOThresh, [793](#)
  - pWCDMARSSIDelta, [793](#)
  - pWCDMARSSIThresh, [793](#)
- SetUSSDNoWaitIndicationCallback
  - qaGobiApiCbk.h, [1364](#)
- SetUSSDNotificationCallback
  - qaGobiApiCbk.h, [1364](#)
- SetUSSDReleaseCallback
  - qaGobiApiCbk.h, [1364](#)
- SetUimSlotStatusChangeCallback
  - qaGobiApiCbk.h, [1363](#)
- SetXTRAAutomaticDownload
  - qaGobiApiPds.h, [1538](#)
- SetXTRANetwork
  - qaGobiApiPds.h, [1539](#)
- SetupEventList
  - CatEventListTlv, [149](#)
- Severity
  - unpack\_swioama\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- severity
  - omaDmFotaTlv, [577](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- Short Message Service (SMS), [36](#)
- shortName
  - nasPLMNNNameResp, [549](#)
  - PLMNNNetworkNameData, [675](#)
  - unpack\_nas\_SLQSGetPLMNNName\_t, [1002](#)
- shortNameCI
  - nasPLMNNNameResp, [549](#)
  - unpack\_nas\_SLQSGetPLMNNName\_t, [1002](#)
- shortNameEn
  - nasPLMNNNameResp, [549](#)
  - unpack\_nas\_SLQSGetPLMNNName\_t, [1002](#)
- shortNameLen
  - nasPLMNNNameResp, [549](#)
  - PLMNNNetworkNameData, [675](#)



- unpack\_nas\_SLQSGetPLMNName\_t, 1002
- shortNameSB
  - nasPLMNNameResp, 549
  - unpack\_nas\_SLQSGetPLMNName\_t, 1002
- shortNameSpareBits
  - PLMNNetworkNameData, 675
- sid
  - CDMAInfo, 154
  - nas\_CDMAInfo, 438
  - sidNid, 795
  - unpack\_nas\_GetHomeNetwork\_t, 991
- SidNid
  - homeSIDNID, 312
- sidNid, 795
  - nid, 795
  - sid, 795
- SigInd
  - LibPackUMTSReqQoSSigInd, 375
  - UMTSReqQoSSigInd, 950
- sigInfo, 795
  - pECIOThresh, 797
  - pHRSINRThresh, 797
  - pIOTThresh, 797
  - pLTESNRThresh, 797
  - pLTESigRptCfg, 797
  - pRSRPThresh, 797
  - pRSRQThresh, 797
  - pRSSIThresh, 797
  - pTDSCDMASINRCONFTThresh, 797
- signal
  - signalInfo, 798
- signalInfo, 797
  - alertPitch, 797
  - signal, 798
  - signalType, 798
- signalStrength
  - nas\_SignalStrengthTlv, 499
- SignalStrengthDataType, 798
  - thresholds, 798
  - thresholdsSize, 798
- signalStrengthReqMask
  - slqsSignalStrengthInfo, 817
  - unpack\_nas\_SLQSGetSignalStrength\_t, 1005
- signalType
  - signalInfo, 798
- SimCapability
  - unpack\_dms\_GetDeviceCap\_t, 955
- simCapability
  - unpack\_dms\_GetDeviceCapabilities\_t, 956
- sinr
  - HDRSSInfo, 308
  - hdrSSInfo, 309
  - nas\_SLQSSignalStrengthsInformation, 501
  - slqsSignalStrengthInfo, 817
  - SLQSSignalStrengthsInformation, 820
  - TDSCDMASigInfoExt, 876
  - tdscdmaSigInfoExt, 877
  - unpack\_nas\_SLQSGetSignalStrength\_t, 1005
- sinrDelta
  - nas\_SLQSSignalStrengthsIndReq, 500
  - SLQSSignalStrengthsIndReq, 819
- sinrThresholdList
  - nas\_SLQSSignalStrengthsIndReq, 500
  - SLQSSignalStrengthsIndReq, 819
- sinrThresholdListLen
  - nas\_SLQSSignalStrengthsIndReq, 500
  - SLQSSignalStrengthsIndReq, 819
- sku\_str
  - slqsfwinfo\_s, 806
  - unpack\_dms\_GetFirmwareInfo\_t, 958
- slot
  - UIMPowerDownReq, 923
  - UIMPowerUpReq, 924
- slot\_t, 798
  - bICCID, 799
  - bICCIDLength, 799
  - bLogicalSlot, 799
  - uPhyCardStatus, 799
  - uPhySlotStatus, 799
- slotInf, 799
  - AppStatus, 801
  - cardState, 801
  - errorState, 801
  - numApp, 801
  - upinRetries, 801
  - upinState, 801
  - upukRetries, 801
- SlotInfo
  - cardStatus, 144
  - uim\_cardStatus, 902
- slotInfo, 801
  - AppStatus, 803
  - cardState, 803
  - errorState, 803
  - numApp, 803
  - upinRetries, 803
  - upinState, 803
  - upukRetries, 803
- slots\_t, 803
  - uimSlotStatus, 803
- slotsstatusChange
  - UIMSlotStatusChangeInfo, 934
  - unpack\_uim\_SetUimSlotStatusChangeCallback\_ind\_t, 1066
- slqs3GPPConfigItem
  - qaGobiApiWds.h, 1688
- SlqsNas3GppNetworkInfo, 806
  - Description, 807
  - Forbidden, 807
  - InUse, 807
  - MCC, 807
  - MNC, 808
  - Preferred, 808
  - Roaming, 808
- SlqsNas3GppNetworkRAT
  - qaGobiApiNas.h, 1482

- SlqsNasPcsDigit, 808
  - includes\_pcs\_digit, 808
  - MCC, 808
  - MNC, 808
- slqsNetworkScanInfo
  - qaGobiApiNas.h, 1483
- SlqsProfile3GPP
  - unpackWdsProfileParam, 1089
  - wds\_profileInfo, 1181
  - WdsProfileParam, 1200
- SlqsProfile3GPP2
  - unpackWdsProfileParam, 1089
  - wds\_profileInfo, 1181
  - WdsProfileParam, 1200
- slqsSessionStateInfo, 812
  - pQmiInterfaceInfo, 813
  - reconfiguration\_required, 813
  - sessionEndReason, 813
  - state, 813
- slqsSignalStrengthInfo, 813
  - ecioList, 816
  - ecioListLen, 816
  - errorRateList, 816
  - errorRateListLen, 816
  - lo, 817
  - ltersrp, 817
  - ltesnr, 817
  - rsrqInfo, 817
  - rxSignalStrengthList, 817
  - rxSignalStrengthListLen, 817
  - signalStrengthReqMask, 817
  - sinr, 817
- slqsWdsEventInfo, 821
  - pDataBearer, 823
  - pDormancyStatus, 823
  - pPacketsCountRX, 823
  - pPacketsCountTX, 823
  - pQmiInterfaceInfo, 823
  - pTotalBytesRX, 823
  - pTotalBytesTX, 823
- slqsautoconnect, 803
  - acroamsetting, 804
  - acsetting, 804
  - action, 804
- slqsfwinfo\_s, 805
  - appversion\_str, 806
  - bootversion\_str, 806
  - carrier\_str, 806
  - cur\_carr\_name, 806
  - cur\_carr\_rev, 806
  - modelid\_str, 806
  - packageid\_str, 806
  - priversion\_str, 806
  - sku\_str, 806
- slqssendasyncsmsparams\_s, 808
  - messageFormat, 810
  - messageSize, 810
  - pFollowOnDC, 810
  - pForceOnDC, 810
  - pLinktimer, 811
  - pMessage, 811
  - pRetryMessage, 811
  - pRetryMessageId, 811
  - pServiceOption, 811
  - pSmsOnIms, 811
  - pUserData, 811
- slqssendsmsparams\_s, 811
  - messageFailureCode, 812
  - messageFormat, 812
  - messageID, 812
  - messageSize, 812
  - pLinktimer, 812
  - pMessage, 812
  - pSmsOnIms, 812
- sms.h
  - LIBPACK\_QMI\_CBK\_PARAM\_NOCHANGE, 1754
  - LIBPACK\_QMI\_CBK\_PARAM\_RESET, 1754
  - LIBPACK\_QMI\_CBK\_PARAM\_SET, 1754
- sms.h, 1751
  - eqmiCbkSetStatus, 1754
  - MAX\_MSE\_TWS\_MSG, 1752
  - MAX\_SMS\_LIST\_SIZE, 1753
  - pack\_sms\_SLQSDDeleteSMS, 1756
  - pack\_sms\_SLQSGetSMS, 1756
  - pack\_sms\_SLQSGetSMSList, 1757
  - pack\_sms\_SLQSMModifySMSStatus, 1757
  - pack\_sms\_SendSMS, 1754
  - pack\_sms\_SetNewSMSCallback, 1756
  - sMSCAddressInfo, 1753
  - sMSEtwSMSMessageInfo, 1753
  - sMSEtwSPIMnInfo, 1753
  - sMSMTMessageInfo, 1754
  - sMSMessageModelInfo, 1753
  - sMSOnIMSInfo, 1754
  - sMSTransferRouteMTMessageInfo, 1754
  - unpack\_sms\_SLQSDDeleteSMS, 1758
  - unpack\_sms\_SLQSGetSMS, 1759
  - unpack\_sms\_SLQSGetSMSList, 1759
  - unpack\_sms\_SLQSMModifySMSStatus, 1759
  - unpack\_sms\_SLQSWmsMemoryFullCallback\_ind, 1760
  - unpack\_sms\_SendSMS, 1757
  - unpack\_sms\_SetNewSMSCallback, 1758
  - unpack\_sms\_SetNewSMSCallback\_ind, 1758
- smsEventType
  - SMSEventInfo\_s, 831
- smsMaxStorageSizeReq, 831
  - pMessageMode, 832
  - storageType, 832
- smsMaxStorageSizeResp, 832
  - freeSlots, 832
  - maxStorageSize, 832
- smsMsgprotocolResp, 835
  - msgProtocol, 835
- smsOnIMS
  - SMSOnIMS, 837

- sMSONIMS, [836](#)
- smsRouteEntry, [837](#)
  - messageClass, [839](#)
  - messageType, [839](#)
  - receiptAction, [839](#)
  - routeStorage, [839](#)
- smsSetRoutesReq, [839](#)
  - numOfRoutes, [839](#)
  - pTransferStatusReport, [839](#)
  - routeList, [839](#)
- snr
  - LTSSInfo, [422](#)
  - lteSSInfo, [423](#)
  - satelliteInfo, [758](#)
- snrlevel
  - lteSnrinformation, [420](#)
  - nas\_lteSnrinformation, [481](#)
- soMask
  - DataBearerTech, [205](#)
  - dataBearerTechnology, [207](#)
  - qmiWSDDataBearerTechnology, [722](#)
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, [1086](#)
- Source
  - unpack\_swima\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- source
  - \_getResetInfoNotification, [59](#)
  - altitudeSrcInfo, [104](#)
  - dmsSwiGetResetInfo, [225](#)
  - unpack\_dms\_GetNetworkTime\_t, [961](#)
  - unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind\_t, [967](#)
  - unpack\_dms\_SLQSDmsSwiGetResetInfo\_t, [968](#)
- sourceIPMask
  - LibPackTFTIDParams, [371](#)
  - TFTIDParams, [881](#)
- SourceLength
  - unpack\_swima\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- spc
  - pack\_nas\_SetACCOLC\_t, [597](#)
  - pack\_wds\_SetMobileIPProfile\_t, [642](#)
- Specific Absorption Rate (SAR), [42](#)
- spn
  - nasPLMNNameResp, [549](#)
  - serviceProviderName, [762](#)
  - unpack\_nas\_SLQSGetPLMNName\_t, [1002](#)
- spnEncoding
  - nasPLMNNameResp, [549](#)
  - unpack\_nas\_SLQSGetPLMNName\_t, [1002](#)
- spnLength
  - nasPLMNNameResp, [549](#)
  - serviceProviderName, [762](#)
  - unpack\_nas\_SLQSGetPLMNName\_t, [1002](#)
- srcPortRangeEnd
  - LibPackTFTIDParams, [371](#)
  - TFTIDParams, [881](#)
- srcPortRangeStart
  - LibPackTFTIDParams, [371](#)
  - TFTIDParams, [881](#)
- srvCapability
  - detailSvcInfo, [215](#)
  - nas\_detailSvcInfo, [451](#)
  - nas\_sysInfoCommon, [505](#)
  - sysInfoCommon, [873](#)
- srvCapabilityValid
  - nas\_sysInfoCommon, [505](#)
  - sysInfoCommon, [874](#)
- srvDomain
  - nas\_sysInfoCommon, [505](#)
  - sysInfoCommon, [874](#)
- SrvDomainPref
  - NASServDomainPrefTlv, [551](#)
- srvDomainValid
  - nas\_sysInfoCommon, [505](#)
  - sysInfoCommon, [874](#)
- srvOption
  - arrSvcOption, [120](#)
- srvStatus
  - detailSvcInfo, [215](#)
  - GSMSrvStatusInfo, [297](#)
  - nas\_detailSvcInfo, [451](#)
  - nas\_GSMSrvStatusInfo, [459](#)
  - nas\_SrvStatusInfo, [502](#)
  - SrvStatusInfo, [844](#)
- SrvStatusInfo, [844](#)
  - isPrefDataPath, [844](#)
  - srvStatus, [844](#)
- srxlev
  - cellParams, [166](#)
  - gsmCellInfo, [295](#)
  - nas\_cellParams, [444](#)
  - nas\_gsmCellInfo, [457](#)
  - nas\_umtsLTENbrCell, [513](#)
  - nas\_wcdmaCellInfo, [516](#)
  - umtsLTENbrCell, [942](#)
  - wcdmaCellInfo, [1161](#)
- ssdatasession\_params, [844](#)
  - action, [846](#)
  - failureReason, [846](#)
  - failureReasonv4, [847](#)
  - failureReasonv6, [847](#)
  - instanceId, [847](#)
  - ipfamily, [847](#)
  - pAuthentication, [847](#)
  - pPassword, [847](#)
  - pProfileId3GPP, [847](#)
  - pProfileId3GPP2, [847](#)
  - pTechnology, [847](#)
  - pUsername, [847](#)
  - rcv4, [847](#)
  - rcv6, [847](#)
  - sessionId, [847](#)
  - v4sessionId, [847](#)
  - v6sessionId, [847](#)

- verbFailReason, [847](#)
- verbFailReasonType, [847](#)
- stage
  - UIMRefreshEvent, [928](#)
- StartPDSTrackingSessionExt
  - qaGobiApiPds.h, [1544](#)
- State
  - NetworkStat1x, [565](#)
  - NetworkStatEVDO, [567](#)
- state
  - LocSetCradleMountReq, [400](#)
  - omaDmConfigTlv, [573](#)
  - omaDmConfigTlvExt, [575](#)
  - omaDmFotaTlv, [577](#)
  - omaDmFotaTlvExt, [580](#)
  - QosFlowInfoState, [732](#)
  - QosMap, [733](#)
  - slqsSessionStateInfo, [813](#)
  - unpack\_dms\_GetActivationState\_t, [953](#)
  - unpack\_omaDmConfigTlv\_t, [1024](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
  - unpack\_qos\_QosFlowInfoState\_t, [1033](#)
- statmask
  - pack\_wds\_GetPacketStatus\_t, [639](#)
- StatsMask
  - TransferStatInd, [891](#)
  - transferStatInd, [891](#)
- statsMask
  - TrStatInd, [892](#)
- StatsPeriod
  - TransferStatInd, [891](#)
  - transferStatInd, [891](#)
- statsPeriod
  - TrStatInd, [892](#)
- Status
  - unpack\_swima\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- status
  - delAssistDataStatus, [211](#)
  - lteEARFCN, [404](#)
  - ltePCI, [414](#)
  - pack\_sms\_SetNewSMSCallback\_t, [619](#)
  - QmiCbkLocInjectPositionInd, [704](#)
  - QmiCbkLocInjectUTCTimeInd, [707](#)
  - QmiCbkLocSetExtPowerConfigInd, [714](#)
  - unpack\_loc\_SetExtPowerConfig\_Ind\_t, [988](#)
  - unpack\_qos\_SLQSSetQosNWStatusCallback\_ind\_t, [1038](#)
  - unpack\_qos\_SLQSSetQosStatusCallback\_ind\_t, [1040](#)
  - wcdmaUARFCN, [1172](#)
- statusChange
  - UIMStatusChangeInfo, [936](#)
- StopPDSTrackingSession
  - qaGobiApiPds.h, [1545](#)
- storageIndex
  - FMSImageIdElement, [246](#)
  - ImageIdElement, [314](#)
- storageType
  - pack\_sms\_SLQSDeleteSMS\_t, [620](#)
  - pack\_sms\_SLQSGetSMS\_t, [621](#)
  - pack\_sms\_SLQSGetSMSList\_t, [622](#)
  - pack\_sms\_SLQSModifySMSStatus\_t, [623](#)
  - smsMaxStorageSizeReq, [832](#)
  - SMSMemoryInfo, [834](#)
  - SMSMTMessage, [836](#)
  - sMSMTMessage, [835](#)
  - unpack\_sms\_SLQSWmsMemoryFullCallBack\_ind\_t, [1054](#)
- String
  - unpack\_dms\_GetDeviceHardwareRev\_t, [956](#)
  - unpack\_dms\_GetDeviceMfr\_t, [957](#)
  - unpack\_dms\_GetFSN\_t, [960](#)
  - unpack\_dms\_UIMGetICCID\_t, [977](#)
- stringSize
  - unpack\_dms\_GetDeviceHardwareRev\_t, [956](#)
  - unpack\_dms\_GetDeviceMfr\_t, [957](#)
  - unpack\_dms\_UIMGetICCID\_t, [977](#)
- subAddr
  - calledPartySubAdd, [133](#)
- subAddrLen
  - calledPartySubAdd, [133](#)
- subAddrType
  - calledPartySubAdd, [133](#)
- subnetMask
  - IPv4Addr, [337](#)
  - unpack\_qos\_IPv4Addr\_t, [1028](#)
- SubnetMaskV4
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- subsType
  - voiceBindSubscriptionInfo, [1100](#)
- SupUSBComps
  - unpack\_dms\_GetUSBComp\_t, [963](#)
- SuppOA
  - CUGInfo, [186](#)
- SuppPrefCUG
  - CUGInfo, [186](#)
- supportedMsgLen
  - SupportedMsgList, [848](#)
- SupportedMsgList, [847](#)
  - supportedMsgLen, [848](#)
  - supportedMsgs, [848](#)
- supportedMsgs
  - SupportedMsgList, [848](#)
- svInfoMask
  - satelliteInfo, [758](#)
- svListLen
  - satelliteInfo, [758](#)
- svStatus
  - satelliteInfo, [758](#)
- svUsedforFix
  - qaGobiApiCbk.h, [1318](#)
- svUsedforFix\_s, [850](#)
  - gnssSvUsedList, [851](#)
  - gnssSvUsedList\_len, [851](#)
- svc

- pack\_qmi\_t, 615
- SvcClass
  - callFWExtInfo, 137
  - callFWInfo, 138
- SvcStatus
  - callFWExtInfo, 137
  - callFWInfo, 138
- svcType
  - ccSUPSType, 150
  - SUPSType, 849
- sw1
  - cardResult, 143
  - uim\_cardResult, 901
- sw2
  - cardResult, 143
  - uim\_cardResult, 901
- SwiDataTypes.h, 1760
  - BOOL, 1761
  - BYTE, 1761
  - CHAR, 1761
  - FLOAT, 1761
  - INT32, 1761
  - INT8, 1761
  - LPCSTR, 1761
  - SHORT, 1761
  - SWI\_API, 1761
  - ULONG, 1761
  - ULONGLONG, 1761
  - UNUSEDPARAM, 1761
  - USHORT, 1761
  - WORD, 1761
- SwiLocGetAutoStart
  - qaGobiApiLoc.h, 1476
- SwiLocGetAutoStartResp, 852
  - fix\_rate, 855
  - fix\_rate\_reported, 855
  - fix\_type, 855
  - fix\_type\_reported, 855
  - function, 855
  - function\_reported, 855
  - max\_dist, 855
  - max\_dist\_reported, 855
  - max\_time, 855
  - max\_time\_reported, 855
- SwiLocSetAutoStart
  - qaGobiApiLoc.h, 1476
- SwiLocSetAutoStartReq, 855
  - fix\_rate, 857
  - fix\_type, 857
  - function, 857
  - max\_dist, 857
  - max\_time, 857
  - set\_fix\_rate, 857
  - set\_fix\_type, 857
  - set\_function, 857
  - set\_max\_dist, 857
  - set\_max\_time, 857
- swiModemStatusResp, 857
  - commonInfo, 857
  - pLTEInfo, 857
- SwiOTAMsg
  - qaGobiApiCbk.h, 1319
- SwiOTAMsg\_s, 858
  - data, 858
  - data\_len, 858
  - pLteNasRelInfo, 858
  - pTime, 858
  - type, 859
- swiPDPRuntimeSettingsReq, 859
  - contextId, 859
  - contextType, 859
- swiPDPRuntimeSettingsResp, 859
  - pAPNName, 861
  - pBearerId, 861
  - pContextId, 861
  - pIPv4Address, 861
  - pIPv4GWAddress, 861
  - pIPv6Address, 861
  - pIPv6GWAddress, 862
  - pPrDNSIPv4Address, 862
  - pPrDNSIPv6Address, 862
  - pPrPCSCFIPv4Address, 862
  - pPrPCSCFIPv6Address, 862
  - pSeDNSIPv4Address, 862
  - pSeDNSIPv6Address, 862
  - pSePCSCFIPv4Address, 862
  - pSePCSCFIPv6Address, 862
- swiQosFilter, 862
  - index, 864
  - pEspSpi, 864
  - pIPv4DstAddr, 864
  - pIPv4SrcAddr, 864
  - pIPv6DstAddr, 864
  - pIPv6Label, 864
  - pIPv6SrcAddr, 864
  - pIPv6TrafCls, 864
  - pId, 864
  - pNxtHdrProto, 864
  - pPrecedence, 864
  - pTCPDstPort, 864
  - pTCPSrcPort, 864
  - pTos, 864
  - pTranDstPort, 864
  - pTranSrcPort, 864
  - pUDPDstPort, 864
  - pUDPSrcPort, 864
  - version, 864
- swiQosFlow, 864
  - index, 867
  - p3GPP2Pri, 867
  - p3GPPImCn, 867
  - p3GPPResResidualBER, 867
  - p3GPPSigInd, 867
  - p3GPPTraHdlPri, 867
  - pDataRate, 867
  - pJitter, 868

- pLatency, [868](#)
  - pLteQci, [868](#)
  - pMaxAllowedPktSz, [868](#)
  - pMinPolicedPktSz, [868](#)
  - pPktErrRate, [868](#)
  - pProfileId3GPP2, [868](#)
  - pTokenBucket, [868](#)
  - pTrafficClass, [868](#)
- swiQosGranted, [868](#)
  - pRxFlow, [868](#)
  - pTxFlow, [868](#)
- swiQosIds, [868](#)
  - pIds, [869](#)
  - sz, [869](#)
- swiQosModifyReq, [869](#)
  - id, [869](#)
  - pRxFilter, [869](#)
  - pRxFlow, [869](#)
  - pTxFilter, [869](#)
  - pTxFlow, [869](#)
- swiQosReq, [869](#)
  - index, [870](#)
  - pRxFilter, [870](#)
  - pRxFlow, [870](#)
  - pTxFilter, [870](#)
  - pTxFlow, [870](#)
- swiRMTrasferStaticsReq, [870](#)
  - bResetStatistics, [871](#)
  - ulMask, [871](#)
- swiloc.h, [1761](#)
  - pack\_swiloc\_SwiLocGetAutoStart, [1762](#)
  - pack\_swiloc\_SwiLocSetAutoStart, [1762](#)
  - unpack\_swiloc\_SwiLocGetAutoStart, [1762](#)
  - unpack\_swiloc\_SwiLocSetAutoStart, [1763](#)
- swioma.h, [1763](#)
  - pack\_swioima\_SLQSOMADMAAlertCallback, [1764](#)
  - pack\_swioima\_SLQSOMADMCancelSession, [1765](#)
  - pack\_swioima\_SLQSOMADMGetSessionInfo, [1765](#)
  - pack\_swioima\_SLQSOMADMGetSettings, [1766](#)
  - pack\_swioima\_SLQSOMADMSelectSelection, [1767](#)
  - pack\_swioima\_SLQSOMADMSetSettings, [1767](#)
  - pack\_swioima\_SLQSOMADMStartSession, [1768](#)
  - unpack\_swioima\_SLQSOMADMAAlertCallback, [1769](#)
  - unpack\_swioima\_SLQSOMADMAAlertCallback\_ind, [1769](#)
  - unpack\_swioima\_SLQSOMADMCancelSession, [1770](#)
  - unpack\_swioima\_SLQSOMADMGetSessionInfo, [1770](#)
  - unpack\_swioima\_SLQSOMADMGetSettings, [1771](#)
  - unpack\_swioima\_SLQSOMADMSelectSelection, [1771](#)
  - unpack\_swioima\_SLQSOMADMSetSettings, [1772](#)
  - unpack\_swioima\_SLQSOMADMStartSession, [1772](#)
- switchOption
  - voiceALSSetLineSwitchInfo, [1099](#)
- sysInfoCDMA
  - CDMASysInfo, [164](#)
  - nas\_CDMASysInfo, [443](#)
- sysInfoCommon, [871](#)
  - isSysForbidden, [873](#)
  - isSysForbiddenValid, [873](#)
  - roamStatus, [873](#)
  - roamStatusValid, [873](#)
  - srvCapability, [873](#)
  - srvCapabilityValid, [874](#)
  - srvDomain, [874](#)
  - srvDomainValid, [874](#)
- sysInfoGSM
  - GSMSysInfo, [300](#)
  - nas\_GSMSysInfo, [462](#)
- sysInfoHDR
  - HDRSysInfo, [311](#)
  - nas\_HDRSysInfo, [467](#)
- sysInfoLTE
  - LTESysInfo, [425](#)
  - nas\_LTESysInfo, [484](#)
- sysInfoWCDMA
  - nas\_WCDMASysInfo, [523](#)
  - WCDMASysInfo, [1172](#)
- sysSelectPrefInfo
  - qaGobiApiNas.h, [1484](#)
- sysSelectPrefParams
  - qaGobiApiNas.h, [1487](#)
- system
  - loc\_SV, [386](#)
  - satelliteInfo, [758](#)
  - SV, [850](#)
- SystemID
  - qaQmiServingSystemParam, [701](#)
  - unpack\_nas\_SLQSGetServingSystem\_t, [1004](#)
- systemID
  - CDMASysInfo, [164](#)
  - nas\_CDMASysInfo, [443](#)
- systemMode
  - CommInfo, [177](#)
  - nas\_CommInfo, [446](#)
- sz
  - swiQosIds, [869](#)
- TCPDstPort
  - unpack\_qos\_swiQosFilter\_t, [1043](#)
- TCPsrcPort
  - unpack\_qos\_swiQosFilter\_t, [1043](#)
- TDSCDMAECIOThresh, [874](#)
- TDSCDMAECIOThreshListLen
  - nas\_TDSCDMAECIOThresh, [506](#)
  - TDSCDMAECIOThresh, [874](#)
- TDSCDMARSCPTthresh, [874](#)
- TDSCDMARSCPTthreshListLen
  - nas\_TDSCDMARSCPTthresh, [506](#)
  - TDSCDMARSCPTthresh, [875](#)
- TDSCDMARSSIThresh, [875](#)
- TDSCDMARSSIThreshListLen



- nas\_TDSCDMARSSIThresh, [507](#)
- TDSCDMARSSIThresh, [875](#)
- TDSCDMASINRCONFTthresh, [877](#)
- TDSCDMASINRThresh, [877](#)
- TDSCDMASINRThreshListLen
  - nas\_TDSCDMASINRThresh, [507](#)
  - TDSCDMASINRThresh, [878](#)
- TDSCDMASigInfoExt, [875](#)
  - ecio, [876](#)
  - rscp, [876](#)
  - rsi, [876](#)
  - sinr, [876](#)
- tFNASwiLTECphyCallInfo
  - qaGobiApiCbk.h, [1320](#)
- tFNASwiOTAMsg
  - qaGobiApiCbk.h, [1320](#)
- tFNActivationStatus
  - qaGobiApiCbk.h, [1319](#)
- tFNAllCallStatus
  - qaGobiApiCbk.h, [1320](#)
- tFNAsyncRawSend
  - qaGobiApiCbk.h, [1320](#)
- tFNBandPreference
  - qaGobiApiCbk.h, [1322](#)
- tFNCATEvent
  - qaGobiApiCbk.h, [1324](#)
- tFNCbkUimSlotStatusChangeInd
  - qaGobiApiCbk.h, [1324](#)
- tFNDHCPv4ClientLeaseStatus
  - qaGobiApiCbk.h, [1326](#)
- tFNDTMFEvent
  - qaGobiApiCbk.h, [1326](#)
- tFNDUNCallInfo
  - qaGobiApiCbk.h, [1326](#)
- tFNDataCapabilities
  - qaGobiApiCbk.h, [1324](#)
- tFNDataSysStatus
  - qaGobiApiCbk.h, [1325](#)
- tFNDelAssistData
  - qaGobiApiCbk.h, [1325](#)
- tFNDeviceStateChange
  - qaGobiApiCbk.h, [1325](#)
- tFNEventPosition
  - qaGobiApiCbk.h, [1326](#)
- tFNFWdldCompletion
  - qaGobiApiCbk.h, [1326](#)
- tFNGnssSvInfo
  - qaGobiApiCbk.h, [1327](#)
- tFNHDRPersonality
  - qaGobiApiCbk.h, [1327](#)
- tFNlmsRegMgrConfig
  - qaGobiApiCbk.h, [1328](#)
- tFNlmsSIPConfig
  - qaGobiApiCbk.h, [1328](#)
- tFNlmsSMSConfig
  - qaGobiApiCbk.h, [1329](#)
- tFNlmsUserConfig
  - qaGobiApiCbk.h, [1329](#)
- tFNlmsVoIPConfig
  - qaGobiApiCbk.h, [1329](#)
- tFNlmsaPdpStatus
  - qaGobiApiCbk.h, [1327](#)
- tFNlmsaRatStatus
  - qaGobiApiCbk.h, [1328](#)
- tFNlmsaRegStatus
  - qaGobiApiCbk.h, [1328](#)
- tFNlmsaSvcStatus
  - qaGobiApiCbk.h, [1328](#)
- tFNInfoRec
  - qaGobiApiCbk.h, [1329](#)
- tFNInjectPosition
  - qaGobiApiCbk.h, [1329](#)
- tFNInjectSensorData
  - qaGobiApiCbk.h, [1330](#)
- tFNInjectTimeStatus
  - qaGobiApiCbk.h, [1330](#)
- tFNInjectUTCTime
  - qaGobiApiCbk.h, [1330](#)
- tFNLURreject
  - qaGobiApiCbk.h, [1330](#)
- tFNMemoryFull
  - qaGobiApiCbk.h, [1332](#)
- tFNMessageWaiting
  - qaGobiApiCbk.h, [1332](#)
- tFNMitlVlRpt
  - qaGobiApiCbk.h, [1332](#)
- tFNMobileIPStatus
  - qaGobiApiCbk.h, [1332](#)
- tFNModemTempInfo
  - qaGobiApiCbk.h, [1332](#)
- tFNNet
  - qaGobiApiCbk.h, [1332](#)
- tFNNetworkTime
  - qaGobiApiCbk.h, [1334](#)
- tFNNewGPS
  - qaGobiApiCbk.h, [1334](#)
- tFNNewNMEA
  - qaGobiApiCbk.h, [1335](#)
- tFNNewRMTransferStatistics
  - qaGobiApiCbk.h, [1335](#)
- tFNNewSMS
  - qaGobiApiCbk.h, [1336](#)
- tFNOMADMState
  - qaGobiApiCbk.h, [1336](#)
- tFNOTASPStatus
  - qaGobiApiCbk.h, [1337](#)
- tFNOpMode
  - qaGobiApiCbk.h, [1337](#)
- tFNPDSSState
  - qaGobiApiCbk.h, [1339](#)
- tFNPacketSrvState
  - qaGobiApiCbk.h, [1337](#)
- tFNPower
  - qaGobiApiCbk.h, [1339](#)
- tFNPrivacyChange
  - qaGobiApiCbk.h, [1339](#)

- tFNQosNWStatus
  - qaGobiApiCbK.h, [1340](#)
- tFNQosPriEvent
  - qaGobiApiCbK.h, [1340](#)
- tFNQosStatus
  - qaGobiApiCbK.h, [1340](#)
- tFNRInfo
  - qaGobiApiCbK.h, [1342](#)
- tFNRankIndicator
  - qaGobiApiCbK.h, [1341](#)
- tFNResetInfo
  - qaGobiApiCbK.h, [1341](#)
- tFNRoamingIndicator
  - qaGobiApiCbK.h, [1342](#)
- tFNSDKTerminated
  - qaGobiApiCbK.h, [1342](#)
- tFNSLQSOMADMAAlert
  - qaGobiApiCbK.h, [1343](#)
- tFNSLQSQOSEvent
  - qaGobiApiCbK.h, [1344](#)
- tFNSLQSSessionState
  - qaGobiApiCbK.h, [1344](#)
- tFNSLQSSignalStrengths
  - qaGobiApiCbK.h, [1344](#)
- tFNSLQSWDSEvent
  - qaGobiApiCbK.h, [1344](#)
- tFNSMSEvents
  - qaGobiApiCbK.h, [1345](#)
- tFNSUPSInfo
  - qaGobiApiCbK.h, [1345](#)
- tFNSUPSNotification
  - qaGobiApiCbK.h, [1345](#)
- tFNSensorStreaming
  - qaGobiApiCbK.h, [1343](#)
- tFNServingSystem
  - qaGobiApiCbK.h, [1343](#)
- tFNSetCradleMount
  - qaGobiApiCbK.h, [1343](#)
- tFNSetEngineState
  - qaGobiApiCbK.h, [1343](#)
- tFNSetEventTimeSync
  - qaGobiApiCbK.h, [1343](#)
- tFNSetExtPowerConfig
  - qaGobiApiCbK.h, [1343](#)
- tFNSigInfo
  - qaGobiApiCbK.h, [1343](#)
- tFNSignalStrength
  - qaGobiApiCbK.h, [1343](#)
- tFNSysInfo
  - qaGobiApiCbK.h, [1345](#)
- tFNSysSelectionPref
  - qaGobiApiCbK.h, [1345](#)
- tFNUIMRefresh
  - qaGobiApiCbK.h, [1346](#)
- tFNUIMStatusChangeInfo
  - qaGobiApiCbK.h, [1346](#)
- tFNUSSDNoWaitIndication
  - qaGobiApiCbK.h, [1348](#)
- tFNUSSDNotification
  - qaGobiApiCbK.h, [1346](#)
- tFNUSSDRelease
  - qaGobiApiCbK.h, [1348](#)
- tFNtransLayerInfo
  - qaGobiApiCbK.h, [1346](#)
- tFNtransNWRegInfo
  - qaGobiApiCbK.h, [1346](#)
- TFTIDParams, [879](#)
  - destPortRangeEnd, [881](#)
  - destPortRangeStart, [881](#)
  - eValid, [881](#)
  - filterId, [881](#)
  - flowLabel, [881](#)
  - IPSECSPi, [881](#)
  - ipVersion, [881](#)
  - nextHeader, [881](#)
  - pSourceIP, [881](#)
  - sourceIPMask, [881](#)
  - srcPortRangeEnd, [881](#)
  - srcPortRangeStart, [881](#)
  - tosMask, [881](#)
- THIRD\_INSTANCE
  - qaGobiApiCbK.h, [1305](#)
- TIME\_DATE\_BUF
  - qaGobiApiSms.h, [1558](#)
- TIME\_STAMP\_BUF
  - qaGobiApiSms.h, [1558](#)
- TPCause
  - SMSAsyncRawSend\_s, [825](#)
- TRMessageTlv
  - unpack\_sms\_SetNewSMSCallback\_ind\_t, [1052](#)
- TX\_PWR
  - NetworkStat1x, [565](#)
- TXAGCList, [893](#)
  - pTXAIG, [894](#)
  - pTXComprSlope, [894](#)
  - pTXComprThres, [894](#)
  - pTXExpSlope, [894](#)
  - pTXExpThres, [894](#)
  - pTXStaticGain, [894](#)
- TXChan
  - LTEInfo, [408](#)
  - nas\_LTEInfo, [473](#)
- tXDroppedCount
  - unpack\_wds\_GetPacketStatus\_t, [1075](#)
- TXOKBytesCount
  - DUNCallInfoInd, [230](#)
- tXOKBytesLastCall
  - unpack\_wds\_GetPacketStatus\_t, [1075](#)
- tXOKBytesCount
  - unpack\_wds\_GetPacketStatus\_t, [1075](#)
- TXPCMIIRFilter, [895](#)
  - pFlag, [897](#)
  - pStage0Val, [897](#)
  - pStage1Val, [897](#)
  - pStage2Val, [897](#)
  - pStage3Val, [897](#)



- pStage4Val, [897](#)
  - pStageCnt, [897](#)
- tXPacketErrors
  - unpack\_wds\_GetPacketStatus\_t, [1075](#)
- tXPacketOverflows
  - unpack\_wds\_GetPacketStatus\_t, [1075](#)
- tXPacketSuccesses
  - unpack\_wds\_GetPacketStatus\_t, [1075](#)
- Tables, [53](#)
- tac
  - LTEInfoIntraFreq, [411](#)
  - LTESysInfo, [425](#)
  - nas\_LTEInfoIntraFreq, [476](#)
  - nas\_LTESysInfo, [484](#)
- tacValid
  - LTESysInfo, [425](#)
  - nas\_LTESysInfo, [485](#)
- TdsBandCapability
  - unpack\_dms\_SLQSGetBandCapability\_t, [971](#)
- tdscdmaSigInfoExt, [876](#)
  - ecio, [876](#)
  - rscp, [877](#)
  - rssr, [877](#)
  - sinr, [877](#)
- tech
  - NWPProfile, [572](#)
- techName
  - \_packetSrvStatus, [64](#)
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t, [1084](#)
- techType
  - DataBearerTech, [205](#)
- Technology
  - DeviceConfigDetail, [216](#)
  - fwinfo\_s, [249](#)
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- TechnologyPref
  - pack\_nas\_SetNetworkPreference\_t, [598](#)
- temperature
  - CommInfo, [177](#)
  - nas\_CommInfo, [446](#)
  - tempratureData, [879](#)
- temperatureDataLen
  - tempratureData, [879](#)
- tempratureData, [878](#)
  - temperature, [879](#)
  - temperatureDataLen, [879](#)
  - timeOfFirstSample, [879](#)
  - timeOffset, [879](#)
  - timeSource, [879](#)
- textMsgLength
  - cdmaMsgEncodingParams, [159](#)
- Thermal Mitigation Device(TMD), [52](#)
- threshGsmHigh
  - lteGsmCellInfo, [405](#)
  - nas\_lteGsmCellInfo, [470](#)
- threshGsmLow
  - lteGsmCellInfo, [405](#)
- nas\_lteGsmCellInfo, [470](#)
- threshServingLow
  - LTEInfoIntraFreq, [411](#)
  - nas\_LTEInfoIntraFreq, [476](#)
- threshXHigh
  - infoInterFreq, [336](#)
  - nas\_infoInterFreq, [469](#)
- threshXLow
  - infoInterFreq, [336](#)
  - nas\_infoInterFreq, [469](#)
- threshXhigh
  - lteWcdmaCellInfo, [426](#)
  - nas\_lteWcdmaCellInfo, [486](#)
- threshXlow
  - lteWcdmaCellInfo, [426](#)
  - nas\_lteWcdmaCellInfo, [486](#)
- thresholds
  - SignalStrengthDataType, [798](#)
- thresholdsSize
  - SignalStrengthDataType, [798](#)
- Time
  - unpack\_swima\_SLQSOMADMGetSessionInfo\_t, [1060](#)
  - wcdmaLongMsgDecodingParams, [1164](#)
  - wcdmaMsgDecodingParams, [1166](#)
- time
  - NASTimeInfoTlv, [559](#)
- Time\_uncert\_ms
  - GPSSStateInfo, [293](#)
- timeInfo, [881](#)
  - day, [883](#)
  - dayLtSavingAdj, [883](#)
  - dayOfWeek, [883](#)
  - hour, [883](#)
  - minute, [883](#)
  - month, [883](#)
  - radioInterface, [883](#)
  - second, [883](#)
  - timeZone, [883](#)
  - TlvPresent, [883](#)
  - year, [883](#)
- TimeLength
  - unpack\_swima\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- timeOfFirstSample
  - sensorData, [759](#)
  - tempratureData, [879](#)
- timeOffset
  - sensorData, [759](#)
  - tempratureData, [879](#)
- timeSource
  - tempratureData, [879](#)
- TimeStmp\_gps\_week
  - GPSSStateInfo, [293](#)
- TimeStmp\_tow\_ms
  - GPSSStateInfo, [293](#)
- timeSyncRefCounter
  - QmiCbkLocEventTimeSyncInd, [703](#)

- timeTlv
  - NASQmiCbkNasSwiOTAMessageInd, 550
- timeZone
  - nas\_timeInfo, 509
  - timeInfo, 883
- timeout
  - pack\_qmi\_t, 615
- timestamp
  - unpack\_dms\_GetNetworkTime\_t, 961
- timingAdvance
  - GERANInfo, 251
  - nas\_GERANInfo, 455
- TlvPresent
  - CatCommonEventTlv, 147
  - DataULongLongTlv, 210
  - DataULongTlv, 210
  - dms\_ActivationStatusTlv, 220
  - dms\_OperatingModeTlv, 221
  - eTWSPLMNInfoTlv, 236
  - messageModeTlv, 427
  - nas\_RejectReasonTlv, 493
  - nas\_RFInfoTlv, 494
  - nas\_SignalStrengthTlv, 499
  - nas\_SLQSSignalStrengthsTlv, 501
  - nas\_timeInfo, 509
  - NASBandPreferenceTlv, 523
  - NASEmergencyModeTlv, 525
  - NASGWAqOrderPrefTlv, 534
  - NASLTEBandPreferenceTlv, 538
  - NASLteNasReleaseInfoTlv, 539
  - NASModePreferenceTlv, 539
  - NASNetSelPreferenceTlv, 539
  - NASOTAMessageTlv, 542
  - NASPhyCaAggPcellInfo, 543
  - NASPhyCaAggScellIDIBw, 543
  - NASPhyCaAggScellIndex, 544
  - NASPhyCaAggScellIndType, 545
  - NASPhyCaAggScellInfo, 546
  - NASPRPreferenceTlv, 549
  - NASRoamPreferenceTlv, 550
  - NASServDomainPrefTlv, 551
  - NASTimeInfoTlv, 559
  - newMTMessageTlv, 568
  - PhyCaAggPcellInfo, 667
  - PhyCaAggScellIDIBw, 668
  - PhyCaAggScellIndex, 668
  - PhyCaAggScellIndType, 669
  - PhyCaAggScellInfo, 671
  - RoamingInfo, 744
  - sessionInfoTlv, 767
  - sessionInfoTlvExt, 768
  - sMSCAddressTlv, 827
  - sMSEtwsMessageTlv, 829
  - sMSOnIMSTlv, 837
  - timeInfo, 883
  - transferRouteMessageTlv, 889
- Tlvresult
  - pack\_dms\_GetCustFeaturesV2\_t, 582
  - pack\_dms\_SetCustFeaturesV2\_t, 584
  - pack\_dms\_SetPower\_t, 585
  - pack\_dms\_SetUSBComp\_t, 585
  - pack\_dms\_UIMGetICCID\_t, 586
  - pack\_fms\_GetImagesPreference\_t, 588
  - pack\_fms\_GetStoredImages\_t, 588
  - pack\_fms\_SetImagesPreference\_t, 589
  - pack\_loc\_Delete\_Assist\_Data\_t, 590
  - pack\_loc\_EventRegister\_t, 592
  - pack\_loc\_SetExtPowerState\_t, 592
  - pack\_loc\_SetOperationMode\_t, 593
  - pack\_loc\_Start\_t, 595
  - pack\_loc\_Stop\_t, 595
  - pack\_nas\_SetNetworkPreference\_t, 598
  - pack\_uim\_ChangePin\_t, 629
  - pack\_uim\_ReadTransparent\_t, 631
  - pack\_uim\_SetPinProtection\_t, 632
  - pack\_uim\_UnblockPin\_t, 634
  - pack\_uim\_VerifyPin\_t, 636
  - unpack\_dms\_GetBandCapability\_t, 953
  - unpack\_dms\_GetCrashAction\_t, 953
  - unpack\_dms\_GetCustFeature\_t, 954
  - unpack\_dms\_GetCustFeaturesV2\_t, 955
  - unpack\_dms\_GetDeviceCap\_t, 955
  - unpack\_dms\_GetDeviceHardwareRev\_t, 956
  - unpack\_dms\_GetDeviceMfr\_t, 957
  - unpack\_dms\_GetDeviceSerialNumbers\_t, 957
  - unpack\_dms\_GetFirmwareInfo\_t, 958
  - unpack\_dms\_GetFirmwareRevision\_t, 959
  - unpack\_dms\_GetFirmwareRevisions\_t, 959
  - unpack\_dms\_GetFSN\_t, 960
  - unpack\_dms\_GetIMSI\_t, 960
  - unpack\_dms\_GetModelID\_t, 961
  - unpack\_dms\_GetNetworkTime\_t, 961
  - unpack\_dms\_GetPower\_t, 962
  - unpack\_dms\_GetPRLVersion\_t, 962
  - unpack\_dms\_GetUSBComp\_t, 963
  - unpack\_dms\_GetVoiceNumber\_t, 963
  - unpack\_dms\_SetCustFeature\_t, 964
  - unpack\_dms\_SetCustFeaturesV2\_t, 964
  - unpack\_dms\_SetEventReport\_ind\_t, 965
  - unpack\_dms\_SetEventReport\_t, 965
  - unpack\_dms\_SetFirmwarePreference\_t, 965
  - unpack\_dms\_SetPower\_t, 966
  - unpack\_dms\_SetUSBComp\_t, 966
  - unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind\_t, 967
  - unpack\_dms\_SLQSDmsSwiGetResetInfo\_t, 968
  - unpack\_dms\_SLQSDmsSwiIndicationRegister\_t, 969
  - unpack\_dms\_SLQSSwiClearDyingGaspStatistics\_t, 971
  - unpack\_dms\_SLQSSwiGetDyingGaspCfg\_t, 973
  - unpack\_dms\_SLQSSwiGetDyingGaspStatistics\_t, 973
  - unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t, 976
  - unpack\_dms\_SLQSSwiSetDyingGaspCfg\_t, 976
  - unpack\_dms\_UIMGetICCID\_t, 977

- unpack\_fms\_GetImagesPreference\_t, 977
- unpack\_fms\_GetStoredImages\_t, 978
- unpack\_fms\_SetImagesPreference\_t, 979
- unpack\_loc\_Delete\_Assist\_Data\_t, 979
- unpack\_loc\_EngineState\_Ind\_t, 980
- unpack\_loc\_EventRegister\_t, 980
- unpack\_loc\_PositionRpt\_Ind\_t, 987
- unpack\_loc\_SetExtPowerConfig\_Ind\_t, 988
- unpack\_loc\_SetExtPowerState\_t, 988
- unpack\_loc\_SetOperationMode\_t, 989
- unpack\_loc\_Start\_t, 989
- unpack\_loc\_Stop\_t, 990
- unpack\_nas\_GetNetworkPreference\_t, 993
- unpack\_nas\_SetNetworkPreference\_t, 999
- unpack\_nas\_SetServingSystemCallback\_ind\_t, 1000
- unpack\_nas\_SlqsGetLTECphyCAInfo\_t, 1000
- unpack\_nas\_SLQSNasSwiOTAMessageCallback\_ind\_t, 1018
- unpack\_nas\_SLQSSetSysSelectionPrefCallBack\_ind\_t, 1018
- unpack\_uim\_ChangePin\_t, 1063
- unpack\_uim\_GetCardStatus\_t, 1064
- unpack\_uim\_ReadTransparent\_t, 1065
- unpack\_uim\_SetPinProtection\_t, 1066
- unpack\_uim\_UnblockPin\_t, 1068
- unpack\_uim\_VerifyPin\_t, 1070
- unpack\_wds\_SLQSCreateProfile\_t, 1077
- unpack\_wds\_SLQSGetProfileSettings\_t, 1081
- unpack\_wds\_SLQSSetIPFamilyPreference\_t, 1084
- TmdDeRegNotMitigationLvlReq, 883
  - mitigationDevID, 884
  - mitigationDevIDLen, 884
- TmdGetMitigationDevListResp, 884
  - pMitigationDevList, 884
  - pMitigationDevListLen, 884
- TmdGetMitigationLvlReq, 885
  - mitigationDevID, 885
  - mitigationDevIDLen, 885
- TmdGetMitigationLvlResp, 885
  - pCurrentmitigationLvl, 886
  - pReqMitigationLvl, 886
- TmdMitigationLvlIndReq, 886
  - mitigationDevID, 886
  - mitigationDevIDLen, 886
- TmdRegNotMitigationLvlReq, 886
  - mitigationDevID, 887
  - mitigationDevIDLen, 887
- toServiceId
  - BroadcastConfig, 127
- toggleMode
  - lineCtrlInfo, 375
- TokenBucket
  - unpack\_qos\_swiQosFlow\_t, 1048
- tokenBucket, 887
  - bucketSz, 887
  - peakRate, 887
  - tokenRate, 887
- tokenRate
  - tokenBucket, 887
  - unpack\_qos\_tokenBucket\_t, 1049
- Tos, 887
  - mask, 889
  - val, 889
- tosMask
  - LibPackTFTIDParams, 371
  - TFTIDParams, 881
- total\_rx\_bytes
  - sQosStat, 843
  - unpack\_qos\_SLQSQosSwiReadDataStats\_t, 1036
- total\_rx\_pkt
  - sQosStat, 843
  - unpack\_qos\_SLQSQosSwiReadDataStats\_t, 1036
- total\_tx\_bytes
  - sQosStat, 843
  - unpack\_qos\_SLQSQosSwiReadDataStats\_t, 1036
- total\_tx\_bytes\_drp
  - sQosStat, 843
  - unpack\_qos\_SLQSQosSwiReadDataStats\_t, 1036
- total\_tx\_pkt
  - sQosStat, 843
  - unpack\_qos\_SLQSQosSwiReadDataStats\_t, 1036
- total\_tx\_pkt\_drp
  - sQosStat, 843
  - unpack\_qos\_SLQSQosSwiReadDataStats\_t, 1036
- TrStatInd, 892
  - statsMask, 892
  - statsPeriod, 892
- TrackAreaCode
  - unpack\_nas\_SLQSGetServingSystem\_t, 1004
- trackAreaCode
  - qaQmiServingSystemParam, 701
- TrafficClass
  - unpack\_qos\_swiQosFlow\_t, 1048
- trafficClass
  - LibPackUMTSQoS, 374
  - UMTSMinQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMinQoS, 1185
- trafficPriority
  - LibPackUMTSQoS, 374
  - UMTSMinQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMinQoS, 1185
- TranDstPort
  - unpack\_qos\_swiQosFilter\_t, 1043
- TranSrcPort
  - unpack\_qos\_swiQosFilter\_t, 1043
- TransCap
  - \_transLayerinfo, 94
- transLayerInfo
  - qaGobiApiSms.h, 1562
- transLayerNotification
  - qaGobiApiCbK.h, 1348
- transNWRegInfoNotification

- qaGobiApiCbk.h, 1348
- TransType
  - \_transLayerInfo, 94
- transactionID
  - SMSTransferRouteMTMessage, 841
  - sMSTransferRouteMTMessage, 840
- transferDelay
  - LibPackUMTSQoS, 374
  - UMTSMInQoS, 945
  - UMTSQoS, 949
  - wds\_UMTSMInQoS, 1185
- TransferRouteMTMessageInfo
  - transferRouteMessageTlv, 889
- transferRouteMessageTlv, 889
  - TlvPresent, 889
  - TransferRouteMTMessageInfo, 889
- TransferStatInd, 891
  - StatsMask, 891
  - StatsPeriod, 891
- transferStatInd, 889
  - StatsMask, 891
  - StatsPeriod, 891
- transferStats
  - pack\_wds\_SLQSSetWdsEventCallback\_t, 651
- TransferStatsDataType, 891
  - interval, 892
- trueIMSI, 892
  - imsiT1112, 893
  - imsiTS1, 893
  - imsiTS2, 893
  - imsiTaddrNum, 893
  - mccT, 893
- trueSrvStatus
  - GSMSrvStatusInfo, 297
  - nas\_GSMSrvStatusInfo, 459
- tx\_bytes
  - NetStats, 561
  - sQosFlowStat, 842
  - unpack\_QosFlowStat\_t, 1050
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, 1086
- tx\_bytes\_drp
  - sQosFlowStat, 842
  - unpack\_QosFlowStat\_t, 1050
- tx\_errors
  - NetStats, 561
- tx\_overflows
  - NetStats, 561
- tx\_packets
  - NetStats, 561
- tx\_pkt
  - sQosFlowStat, 842
  - unpack\_QosFlowStat\_t, 1050
- tx\_pkt\_drp
  - sQosFlowStat, 842
  - unpack\_QosFlowStat\_t, 1050
- tx\_pkts
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, 1086
- TxDropConutTlv
  - QmiCbkWdsStatisticsIndState, 718
- txInfo, 894
  - isInTraffic, 895
  - txPower, 895
- txOKBytesCount
  - unpack\_wds\_SLQSGetDUNCallInfo\_t, 1081
- TxOkByteCountTlv
  - QmiCbkWdsStatisticsIndState, 718
- TxOkConutTlv
  - QmiCbkWdsStatisticsIndState, 718
- txPower
  - txInfo, 895
- TxQFilter
  - unpack\_qos\_QosFlowInfo\_t, 1032
- TxQFlowGranted
  - unpack\_qos\_QosFlowInfo\_t, 1032
- type
  - \_getResetInfoNotification, 59
  - dmsSwiGetResetInfo, 225
  - pack\_wds\_GetDefaultProfileNum\_t, 637
  - pack\_wds\_SetDefaultProfileNum\_t, 641
  - SwiOTAMsg\_s, 859
  - unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind\_t, 967
  - unpack\_dms\_SLQSDmsSwiGetResetInfo\_t, 968
  - unpack\_qmi\_t, 1027
- u16PRLVersion
  - unpack\_dms\_GetPRLVersion\_t, 962
- u8PRLPreference
  - unpack\_dms\_GetPRLVersion\_t, 962
- UATISIZE
  - qaGobiApiNas.h, 1482
- UDPDstPort
  - unpack\_qos\_swiQosFilter\_t, 1043
- UDPSrcPort
  - unpack\_qos\_swiQosFilter\_t, 1043
- UIMAuthenticateReq, 914
  - authData, 914
  - pIndicationToken, 914
  - sessionInfo, 914
- UIMAuthenticateResp, 915
  - pAuthenticateResult, 915
  - pCardResult, 915
  - pIndicationToken, 915
- UIMChangePIN
  - qaGobiApiDms.h, 1436
- UIMChangePinReq, 915
  - changePIN, 916
  - pIndicationToken, 916
  - pKeyReferenceID, 916
  - sessionInfo, 916
- UIMDepersonalizationReq, 916
  - depersonalisationInfo, 916
- UIMDepersonalizationResp, 917
  - pRemainingRetries, 917

- UIMEventRegisterReqResp, 917
  - eventMask, 917
- UIMGetCardStatusResp, 918
  - pCardStatus, 918
  - pHotSwapStatus, 918
- UIMGetConfigurationReq, 918
  - pConfigurationMask, 919
- UIMGetConfigurationResp, 919
  - pAutoSelection, 920
  - pHaltSubscription, 920
  - pPersonalizationStatus, 920
- UIMGetControlKeyStatus
  - qaGobiApiDms.h, 1437
- UIMGetFileAttributesReq, 920
  - fileIndex, 920
  - pIndicationToken, 920
  - sessionInfo, 920
- UIMGetFileAttributesResp, 920
  - pCardResult, 921
  - pFileAttributes, 921
  - pIndicationToken, 921
- UIMGetICCID
  - qaGobiApiDms.h, 1438
- UIMGetPINStatus
  - qaGobiApiDms.h, 1439
- UIMGetSlotsStatusResp, 921
  - pNumberOfPhySlot, 922
  - pUimSlotsStatus, 922
- UIMPinResp, 922
  - pEncryptedPIN1, 922
  - pIndicationToken, 922
  - pRemainingRetries, 922
- UIMPowerDownReq, 923
  - slot, 923
- UIMPowerUpReq, 923
  - pIgnoreHotSwapSwitch, 924
  - slot, 924
- UIMReadTransparentReq, 924
  - fileIndex, 924
  - pEncryptData, 924
  - pIndicationToken, 924
  - readTransparent, 924
  - sessionInfo, 925
- UIMReadTransparentResp, 925
  - pCardResult, 925
  - pEncryptedData, 925
  - pIndicationToken, 925
  - pReadResult, 925
- UIMRefreshCompleteReq, 925
  - refreshComplete, 926
  - sessionInfo, 926
- UIMRefreshEvent, 926
  - aid, 928
  - aidLength, 928
  - arrfileInfo, 928
  - mode, 928
  - numOfFiles, 928
  - sessionType, 928
  - stage, 928
- UIMRefreshGetLastEventReq, 928
  - sessionInfo, 929
- UIMRefreshGetLastEventResp, 929
  - pRefreshEvent, 929
- UIMRefreshOKReq, 929
  - OKtoRefresh, 929
  - sessionInfo, 929
- UIMRefreshRegisterReq, 930
  - regRefresh, 930
  - sessionInfo, 930
- UIMSessionInformation, 930
  - aid, 931
  - aidLength, 931
  - sessionType, 931
- UIMSetControlKeyProtection
  - qaGobiApiDms.h, 1440
- UIMSetPINProtection
  - qaGobiApiDms.h, 1441
- UIMSetPinProtectionReq, 931
  - pIndicationToken, 932
  - pKeyReferenceID, 932
  - pinProtection, 932
  - sessionInfo, 932
- UIMSlotStatus, 933
  - bICCID, 934
  - bICCIDLength, 934
  - bLogicalSlot, 934
  - uPhyCardStatus, 934
  - uPhySlotStatus, 934
- UIMSlotStatusChangeInfo, 934
  - bNumberOfPhySlots, 934
  - slotsstatusChange, 934
- UIMSlotsStatus, 932
  - uimSlotStatus, 933
- UIMStatusChangeInfo, 934
  - statusChange, 936
- UIMSwitchSlotReq, 936
  - bLogicalSlot, 936
  - uPhysicalSlot, 936
- UIMUnblockControlKey
  - qaGobiApiDms.h, 1442
- UIMUnblockPIN
  - qaGobiApiDms.h, 1443
- UIMUnblockPinReq, 936
  - pIndicationToken, 937
  - pKeyReferenceID, 937
  - sessionInfo, 937
  - unblockPIN, 937
- UIMVerifyPIN
  - qaGobiApiDms.h, 1444
- UIMVerifyPinReq, 937
  - pEncryptedPIN1, 938
  - pIndicationToken, 938
  - pKeyReferenceID, 938
  - sessionInfo, 938
  - verifyPIN, 938
- ULONG

- SwiDataTypes.h, 1761
- ULONGLONG
  - SwiDataTypes.h, 1761
- UMTSGrantedQoS
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, 1083
- UMTSInfo, 938
  - cellID, 940
  - ecio, 940
  - geranInst, 940
  - GeranInstInfo, 940
  - lac, 940
  - plmn, 940
  - psc, 940
  - rsc, 940
  - UMTSInstInfo, 940
  - uarfcn, 940
  - umtsInst, 940
- UMTSInstInfo
  - nas\_UMTSInfo, 511
  - UMTSInfo, 940
- UMTSLTENbrCell
  - nas\_WCDMAInfoLTENNeighborCell, 518
  - WCDMAInfoLTENNeighborCell, 1162
- UMTSMInQoS, 942
  - deliveryErrSDU, 945
  - grntDownlinkBitrate, 945
  - grntUplinkBitrate, 945
  - maxDownlinkBitrate, 945
  - maxSDUSize, 945
  - maxUplinkBitrate, 945
  - qosDeliveryOrder, 945
  - resBerRatio, 945
  - sduErrorRatio, 945
  - trafficClass, 945
  - trafficPriority, 945
  - transferDelay, 945
- UMTSQoS, 946
  - deliveryErrSDU, 949
  - grntDownlinkBitrate, 949
  - grntUplinkBitrate, 949
  - maxDownlinkBitrate, 949
  - maxSDUSize, 949
  - maxUplinkBitrate, 949
  - qosDeliveryOrder, 949
  - resBerRatio, 949
  - sduErrorRatio, 949
  - trafficClass, 949
  - trafficPriority, 949
  - transferDelay, 949
- UMTSReqQoS
  - LibPackUMTSReqQoSSigInd, 375
  - UMTSReqQoSSigInd, 950
- UMTSReqQoSSigInd, 949
  - SigInd, 950
  - UMTSReqQoS, 950
- UMTSinstInfo, 940
  - umtsEcio, 941
  - umtsPsc, 941
  - umtsRsc, 941
  - umtsUarfcn, 941
- UNIQUE\_ID\_LEN
  - dms.h, 1218
  - qaGobiApiDms.h, 1404
- UNUSEDPARAM
  - common.h, 1211
  - SwiDataTypes.h, 1761
- uPhyCardStatus
  - slot\_t, 799
  - UIMSlotStatus, 934
- uPhySlotStatus
  - slot\_t, 799
  - UIMSlotStatus, 934
- uResult
  - sGetDeviceSeriesResult, 795
- USBComp
  - pack\_dms\_SetUSBComp\_t, 585
  - unpack\_dms\_GetUSBComp\_t, 963
- USBCompConfig, 1089
  - pUSBComp, 1091
- USBCompParams, 1091
  - pNumSupUSBComps, 1093
  - pSupUSBComps, 1093
  - pUSBComp, 1093
- USHORT
  - SwiDataTypes.h, 1761
- USSD\_DCS\_8BIT
  - qaGobiApiCbk.h, 1305
- USSD\_DCS\_ASCII
  - qaGobiApiCbk.h, 1305
- USSD\_DCS\_UCS2
  - qaGobiApiCbk.h, 1305
- USSDNoWaitIndicationInfo, 1093
  - pAlphaIdentifier, 1094
  - pError, 1094
  - pFailureCause, 1094
  - pUSSDData, 1094
- USSDRespFNetwork, 1094
  - pRespData, 1094
  - pTypeCode, 1095
- USSInfo, 1095
  - ussDCS, 1095
  - ussData, 1095
  - ussLen, 1095
- USSInformation
  - voiceOrigUSSDNoWaitInfo, 1140
- USSResp, 1095
  - pAlphaIDInfo, 1096
  - pCCSuppsType, 1096
  - pCallId, 1096
  - pCcResultType, 1096
  - pUSSDInfo, 1096
  - pfailureCause, 1096
- UUSData
  - UUSInfo, 1097
- UUSDatalen
  - UUSInfo, 1097



- UUSDcs
  - UUSInfo, [1097](#)
- UUSInfo, [1096](#)
  - UUSData, [1097](#)
  - UUSDatalen, [1097](#)
  - UUSDcs, [1097](#)
  - UUSType, [1097](#)
- UUSType
  - UUSInfo, [1097](#)
- uarfcn
  - lteWcdmaCellInfo, [426](#)
  - nas\_lteWcdmaCellInfo, [486](#)
  - nas\_UMTSInfo, [511](#)
  - UMTSInfo, [940](#)
  - wcdmaUARFCN, [1172](#)
- ueInIdle
  - LTEInfoInterfreq, [409](#)
  - LTEInfoIntrafreq, [411](#)
  - LTEInfoNeighboringGSM, [412](#)
  - LTEInfoNeighboringWCDMA, [413](#)
  - nas\_LTEInfoInterfreq, [473](#)
  - nas\_LTEInfoIntrafreq, [476](#)
  - nas\_LTEInfoNeighboringGSM, [476](#)
  - nas\_LTEInfoNeighboringWCDMA, [477](#)
- uim.h, [1773](#)
  - MAX\_ICCID\_LENGTH, [1774](#)
  - MAX\_NO\_OF\_SLOTS, [1774](#)
  - MAX\_SLOTS\_STATUS, [1774](#)
  - pack\_uim\_ChangePin, [1775](#)
  - pack\_uim\_GetCardStatus, [1775](#)
  - pack\_uim\_ReadTransparent, [1775](#)
  - pack\_uim\_SLQSUIEventRegister, [1776](#)
  - pack\_uim\_SLQSUIMGetSlotsStatus, [1776](#)
  - pack\_uim\_SLQSUIMSwitchSlot, [1776](#)
  - pack\_uim\_SetPinProtection, [1775](#)
  - pack\_uim\_UnblockPin, [1778](#)
  - pack\_uim\_VerifyPin, [1778](#)
  - unpack\_uim\_ChangePin, [1778](#)
  - unpack\_uim\_GetCardStatus, [1779](#)
  - unpack\_uim\_ReadTransparent, [1779](#)
  - unpack\_uim\_SLQSUIEventRegister, [1780](#)
  - unpack\_uim\_SLQSUIMGetSlotsStatus, [1780](#)
  - unpack\_uim\_SLQSUIMSetStatusChangeCall-  
Back\_ind, [1781](#)
  - unpack\_uim\_SLQSUIMSwitchSlot, [1781](#)
  - unpack\_uim\_SetPinProtection, [1779](#)
  - unpack\_uim\_SetUimSlotStatusChangeCallback\_-  
ind, [1780](#)
  - unpack\_uim\_UnblockPin, [1781](#)
  - unpack\_uim\_VerifyPin, [1782](#)
- uim\_UIMSessionInformation, [911](#)
  - aid, [912](#)
  - aidLength, [912](#)
  - sessionType, [912](#)
- uim\_appStatus, [897](#)
  - aidLength, [900](#)
  - aidVal, [900](#)
  - appState, [900](#)
  - appType, [900](#)
  - persoFeature, [900](#)
  - persoRetries, [900](#)
  - persoState, [900](#)
  - persoUnblockRetries, [900](#)
  - pin1Retries, [900](#)
  - pin1State, [900](#)
  - pin2Retries, [900](#)
  - pin2State, [900](#)
  - puk1Retries, [900](#)
  - puk2Retries, [900](#)
  - univPin, [901](#)
- uim\_cardResult, [901](#)
  - sw1, [901](#)
  - sw2, [901](#)
- uim\_cardStatus, [901](#)
  - index1xPri, [902](#)
  - index1xSec, [902](#)
  - indexGwPri, [902](#)
  - indexGwSec, [902](#)
  - numSlot, [902](#)
  - SlotInfo, [902](#)
- uim\_changeUIMPIN, [903](#)
  - oldPINLen, [903](#)
  - oldPINVal, [903](#)
  - pinID, [903](#)
  - pinLen, [903](#)
  - pinVal, [903](#)
- uim\_encryptedPIN1, [904](#)
  - pin1Len, [904](#)
  - pin1Val, [904](#)
- uim\_fileInfo, [904](#)
  - fileID, [905](#)
  - path, [905](#)
  - pathLen, [905](#)
- uim\_hotSwapStatus, [905](#)
  - hotSwap, [905](#)
  - hotSwapLength, [905](#)
- uim\_readResult, [906](#)
  - content, [906](#)
  - contentLen, [906](#)
- uim\_readTransparentInfo, [906](#)
  - length, [906](#)
  - offset, [906](#)
- uim\_remainingRetries, [907](#)
  - unblockLeft, [907](#)
  - verifyLeft, [907](#)
- uim\_sessionInformation, [907](#)
  - aid, [908](#)
  - aidLength, [908](#)
  - sessionType, [908](#)
- uim\_setPINProtection, [908](#)
  - pinID, [909](#)
  - pinLength, [909](#)
  - pinOperation, [909](#)
  - pinValue, [909](#)
- uim\_slotInfo, [909](#)
  - AppStatus, [911](#)

- cardState, 911
- errorState, 911
- numApp, 911
- upinRetries, 911
- upinState, 911
- upukRetries, 911
- uim\_unblockUIMPIN, 912
  - newPINLen, 913
  - newPINVal, 913
  - pinID, 913
  - pukLen, 913
  - pukVal, 913
- uim\_verifyUIMPIN, 913
  - pinID, 914
  - pinLen, 914
  - pinVal, 914
- uimSlotStatus
  - slots\_t, 803
  - UIMSlotsStatus, 933
- ulData
  - DataULongTlv, 210
- ulMask
  - rmTrasferStaticsReq, 742
  - swiRMTrasferStaticsReq, 871
- ulPhysicalSlot
  - pack\_uim\_SLQSUIMSwitchSlot\_t, 633
  - UIMSwitchSlotReq, 936
- ulldata
  - DataULongLongTlv, 210
- umtsEcio
  - nas\_UMTSinstInfo, 512
  - UMTSinstInfo, 941
- umtsInst
  - nas\_UMTSInfo, 511
  - UMTSInfo, 940
- umtsLTENbrCell, 941
  - cellsTDD, 942
  - earfcn, 942
  - pci, 942
  - rsrp, 942
  - rsrq, 942
  - srxlev, 942
- umtsLTENbrCellLen
  - nas\_WCDMAInfoLTENeighborCell, 518
  - WCDMAInfoLTENeighborCell, 1162
- umtsPsc
  - nas\_UMTSinstInfo, 512
  - UMTSinstInfo, 941
- umtsRscp
  - nas\_UMTSinstInfo, 512
  - UMTSinstInfo, 941
- umtsUarfcn
  - nas\_UMTSinstInfo, 512
  - UMTSinstInfo, 941
- UnPackGetProfileSettingOut, 1089
  - curProfile, 1089
  - pExtErrCode, 1089
- unblockLeft
  - personalizationStatus, 665
  - remainingRetries, 738
  - uim\_remainingRetries, 907
- unblockPIN
  - UIMUnblockPinReq, 937
- unblockUIMPIN, 950
  - newPINLen, 951
  - newPINVal, 951
  - pinID, 951
  - pukLen, 951
  - pukVal, 951
- uniqueID
  - CurrImageInfo, 191
  - image\_info\_t, 313
- univPin
  - appStats, 108
  - appStatus, 112
  - uim\_appStatus, 901
- UniversalTime, 951
  - day, 952
  - dayOfWeek, 952
  - hour, 952
  - minute, 952
  - month, 952
  - second, 952
  - year, 952
- universalTime
  - nasNetworkTime, 540
  - unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind-  
\_t, 1015
- unpack\_QosFlowStat\_t, 1049
  - bearerId, 1050
  - tx\_bytes, 1050
  - tx\_bytes\_drp, 1050
  - tx\_pkt, 1050
  - tx\_pkt\_drp, 1050
- unpack\_dms\_GetActivationState
  - dms.h, 1233
- unpack\_dms\_GetActivationState\_t, 952
  - state, 953
- unpack\_dms\_GetBandCapability
  - dms.h, 1233
- unpack\_dms\_GetBandCapability\_t, 953
  - BandCapability, 953
  - Tlvresult, 953
- unpack\_dms\_GetCrashAction
  - dms.h, 1233
- unpack\_dms\_GetCrashAction\_t, 953
  - DevCrashState, 953
  - Tlvresult, 953
- unpack\_dms\_GetCustFeature
  - dms.h, 1234
- unpack\_dms\_GetCustFeature\_t, 953
  - DHCPRelayEnabled, 954
  - DisableIMSI, 954
  - GPSPMP, 954
  - GPSSel, 954
  - GpsEnable, 954



- IPFamSupport, [954](#)
- IsVoiceEnabled, [954](#)
- RMAutoConnect, [954](#)
- SMSSupport, [954](#)
- Tlvresult, [954](#)
- unpack\_dms\_GetCustFeaturesV2
  - dms.h, [1234](#)
- unpack\_dms\_GetCustFeaturesV2\_t, [954](#)
  - GetCustomFeatureV2, [955](#)
  - Tlvresult, [955](#)
- unpack\_dms\_GetDeviceCap
  - dms.h, [1234](#)
- unpack\_dms\_GetDeviceCap\_t, [955](#)
  - DataServiceCapability, [955](#)
  - MaxRXChannelRate, [955](#)
  - MaxTXChannelRate, [955](#)
  - Radiolfaces, [955](#)
  - RadiolfacesSize, [955](#)
  - SimCapability, [955](#)
  - Tlvresult, [955](#)
- unpack\_dms\_GetDeviceCapabilities
  - dms.h, [1234](#)
- unpack\_dms\_GetDeviceCapabilities\_t, [955](#)
  - dataServiceCaCapability, [956](#)
  - maxRxChannelRate, [956](#)
  - maxTxChannelRate, [956](#)
  - Radiolfaces, [956](#)
  - radiolfacesSize, [956](#)
  - simCapability, [956](#)
- unpack\_dms\_GetDeviceHardwareRev
  - dms.h, [1235](#)
- unpack\_dms\_GetDeviceHardwareRev\_t, [956](#)
  - String, [956](#)
  - stringSize, [956](#)
  - Tlvresult, [956](#)
- unpack\_dms\_GetDeviceMfr
  - dms.h, [1235](#)
- unpack\_dms\_GetDeviceMfr\_t, [956](#)
  - String, [957](#)
  - stringSize, [957](#)
  - Tlvresult, [957](#)
- unpack\_dms\_GetDeviceSerialNumbers
  - dms.h, [1235](#)
- unpack\_dms\_GetDeviceSerialNumbers\_t, [957](#)
  - ESNString, [957](#)
  - esnSize, [957](#)
  - IMEIString, [957](#)
  - imeiSize, [957](#)
  - imeiSvnSize, [957](#)
  - ImeiSvnString, [957](#)
  - MEIDString, [957](#)
  - meidSize, [957](#)
  - Tlvresult, [957](#)
- unpack\_dms\_GetFSN
  - dms.h, [1237](#)
- unpack\_dms\_GetFSN\_t, [959](#)
  - String, [960](#)
  - Tlvresult, [960](#)
- unpack\_dms\_GetFirmwareInfo
  - dms.h, [1236](#)
- unpack\_dms\_GetFirmwareInfo\_t, [957](#)
  - appversion\_str, [958](#)
  - bootversion\_str, [958](#)
  - carrier\_str, [958](#)
  - cur\_carr\_name, [958](#)
  - cur\_carr\_rev, [958](#)
  - modelid\_str, [958](#)
  - packageid\_str, [958](#)
  - priversion\_str, [958](#)
  - sku\_str, [958](#)
  - Tlvresult, [958](#)
- unpack\_dms\_GetFirmwareRevision
  - dms.h, [1236](#)
- unpack\_dms\_GetFirmwareRevision\_t, [958](#)
  - AMSSString, [959](#)
  - amssSize, [959](#)
  - PRISString, [959](#)
  - Tlvresult, [959](#)
- unpack\_dms\_GetFirmwareRevisions
  - dms.h, [1236](#)
- unpack\_dms\_GetFirmwareRevisions\_t, [959](#)
  - AMSSString, [959](#)
  - amssSize, [959](#)
  - bootSize, [959](#)
  - BootString, [959](#)
  - PRISString, [959](#)
  - priSize, [959](#)
  - Tlvresult, [959](#)
- unpack\_dms\_GetHardwareRevision
  - dms.h, [1237](#)
- unpack\_dms\_GetHardwareRevision\_t, [960](#)
  - hwVer, [960](#)
- unpack\_dms\_GetIMSI
  - dms.h, [1237](#)
- unpack\_dms\_GetIMSI\_t, [960](#)
  - imsi, [960](#)
  - Tlvresult, [960](#)
- unpack\_dms\_GetModelID
  - dms.h, [1238](#)
- unpack\_dms\_GetModelID\_t, [960](#)
  - modelid, [961](#)
  - Tlvresult, [961](#)
- unpack\_dms\_GetNetworkTime
  - dms.h, [1238](#)
- unpack\_dms\_GetNetworkTime\_t, [961](#)
  - source, [961](#)
  - timestamp, [961](#)
  - Tlvresult, [961](#)
- unpack\_dms\_GetPRLVersion
  - dms.h, [1239](#)
- unpack\_dms\_GetPRLVersion\_t, [962](#)
  - Tlvresult, [962](#)
  - u16PRLVersion, [962](#)
  - u8PRLPreference, [962](#)
- unpack\_dms\_GetPower
  - dms.h, [1238](#)

- unpack\_dms\_GetPower\_t, 961
  - HardwareControlledMode, 962
  - OfflineReason, 962
  - OperationMode, 962
  - Tlvresult, 962
- unpack\_dms\_GetSerialNumbers
  - dms.h, 1239
- unpack\_dms\_GetSerialNumbers\_t, 962
  - esn, 963
  - imei\_no, 963
  - imeisv\_svn, 963
  - meid, 963
- unpack\_dms\_GetUSBComp
  - dms.h, 1239
- unpack\_dms\_GetUSBComp\_t, 963
  - NumSupUSBComps, 963
  - SupUSBComps, 963
  - Tlvresult, 963
  - USBComp, 963
- unpack\_dms\_GetVoiceNumber
  - dms.h, 1240
- unpack\_dms\_GetVoiceNumber\_t, 963
  - MIN, 963
  - minSize, 963
  - Tlvresult, 963
  - VoiceNumber, 963
  - voiceNumberSize, 964
- unpack\_dms\_SLQSDmsSwiGetResetInfo
  - dms.h, 1243
- unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind
  - dms.h, 1243
- unpack\_dms\_SLQSDmsSwiGetResetInfo\_Ind\_t, 966
  - source, 967
  - Tlvresult, 967
  - type, 967
- unpack\_dms\_SLQSDmsSwiGetResetInfo\_t, 967
  - source, 968
  - Tlvresult, 968
  - type, 968
- unpack\_dms\_SLQSDmsSwiIndicationRegister
  - dms.h, 1243
- unpack\_dms\_SLQSDmsSwiIndicationRegister\_t, 968
  - Tlvresult, 969
- unpack\_dms\_SLQSSwiGetBandCapability
  - dms.h, 1244
- unpack\_dms\_SLQSSwiGetBandCapability\_t, 969
  - bandCapability, 971
  - LteBandCapability, 971
  - TdsBandCapability, 971
- unpack\_dms\_SLQSSwiClearDyingGaspStatistics
  - dms.h, 1244
- unpack\_dms\_SLQSSwiClearDyingGaspStatistics\_t, 971
  - Tlvresult, 971
- unpack\_dms\_SLQSSwiGetDyingGaspCfg
  - dms.h, 1244
- unpack\_dms\_SLQSSwiGetDyingGaspCfg\_t, 971
  - pGetDyingGaspCfg, 973
  - Tlvresult, 973
- unpack\_dms\_SLQSSwiGetDyingGaspStatistics
  - dms.h, 1245
- unpack\_dms\_SLQSSwiGetDyingGaspStatistics\_t, 973
  - pGetDyingGaspStatistics, 973
  - Tlvresult, 973
- unpack\_dms\_SLQSSwiGetFirmwareCurr
  - dms.h, 1245
- unpack\_dms\_SLQSSwiGetFirmwareCurr\_t, 973
  - carrier, 974
  - fwvers, 974
  - numEntries, 974
  - pCurrImgInfo, 974
  - pkgver, 974
  - priver, 974
- unpack\_dms\_SLQSSwiGetFwUpdateStatus
  - dms.h, 1245
- unpack\_dms\_SLQSSwiGetFwUpdateStatus\_t, 974
  - imgType, 976
  - logString, 976
  - refData, 976
  - refString, 976
  - ResCode, 976
  - Tlvresult, 976
- unpack\_dms\_SLQSSwiSetDyingGaspCfg
  - dms.h, 1246
- unpack\_dms\_SLQSSwiSetDyingGaspCfg\_t, 976
  - Tlvresult, 976
- unpack\_dms\_SetCrashAction
  - dms.h, 1240
- unpack\_dms\_SetCrashAction\_t, 964
  - notused, 964
- unpack\_dms\_SetCustFeature
  - dms.h, 1240
- unpack\_dms\_SetCustFeature\_t, 964
  - Tlvresult, 964
- unpack\_dms\_SetCustFeaturesV2
  - dms.h, 1241
- unpack\_dms\_SetCustFeaturesV2\_t, 964
  - Tlvresult, 964
- unpack\_dms\_SetEventReport
  - dms.h, 1241
- unpack\_dms\_SetEventReport\_ind
  - dms.h, 1241
- unpack\_dms\_SetEventReport\_ind\_t, 964
  - ActivationStatusTlv, 965
  - OperatingModeTlv, 965
  - Tlvresult, 965
- unpack\_dms\_SetEventReport\_t, 965
  - Tlvresult, 965
- unpack\_dms\_SetFirmwarePreference
  - dms.h, 1242
- unpack\_dms\_SetFirmwarePreference\_t, 965
  - Tlvresult, 965
- unpack\_dms\_SetPower
  - dms.h, 1242
- unpack\_dms\_SetPower\_t, 966
  - Tlvresult, 966

- unpack\_dms\_SetUSBComp
  - dms.h, [1242](#)
- unpack\_dms\_SetUSBComp\_t, [966](#)
  - Tlvresult, [966](#)
- unpack\_dms\_UIMGetICCID
  - dms.h, [1246](#)
- unpack\_dms\_UIMGetICCID\_t, [976](#)
  - String, [977](#)
  - stringSize, [977](#)
  - Tlvresult, [977](#)
- unpack\_fms\_GetImagesPreference
  - fms.h, [1249](#)
- unpack\_fms\_GetImagesPreference\_t, [977](#)
  - ImageListSize, [977](#)
  - pImageList, [977](#)
  - Tlvresult, [977](#)
- unpack\_fms\_GetStoredImages
  - fms.h, [1249](#)
- unpack\_fms\_GetStoredImages\_t, [978](#)
  - imageList, [978](#)
  - imagelistSize, [978](#)
  - Tlvresult, [978](#)
- unpack\_fms\_SetImagesPreference
  - fms.h, [1249](#)
- unpack\_fms\_SetImagesPreference\_t, [978](#)
  - ImageTypes, [979](#)
  - ImageTypesSize, [979](#)
  - Tlvresult, [979](#)
- unpack\_loc\_Delete\_Assist\_Data\_t, [979](#)
  - Tlvresult, [979](#)
- unpack\_loc\_DeleteAssistData
  - loc.h, [1256](#)
- unpack\_loc\_EngineState\_Ind
  - loc.h, [1256](#)
- unpack\_loc\_EngineState\_Ind\_t, [979](#)
  - engineState, [980](#)
  - Tlvresult, [980](#)
- unpack\_loc\_EventRegister
  - loc.h, [1257](#)
- unpack\_loc\_EventRegister\_t, [980](#)
  - Tlvresult, [980](#)
- unpack\_loc\_PositionRpt\_Ind
  - loc.h, [1257](#)
- unpack\_loc\_PositionRpt\_Ind\_t, [980](#)
  - pAltitudeAssumed, [986](#)
  - pAltitudeWrtEllipsoid, [986](#)
  - pAltitudeWrtMeanSeaLevel, [986](#)
  - pFixId, [986](#)
  - pGpsTime, [986](#)
  - pHeading, [986](#)
  - pHeadingUnc, [986](#)
  - pHorConfidence, [986](#)
  - pHorReliability, [986](#)
  - pHorUncCircular, [986](#)
  - pHorUncEllipseOrientAzimuth, [986](#)
  - pHorUncEllipseSemiMajor, [986](#)
  - pHorUncEllipseSemiMinor, [986](#)
  - pLatitude, [986](#)
  - pLeapSeconds, [986](#)
  - pLongitude, [986](#)
  - pMagneticDeviation, [986](#)
  - pPrecisionDilution, [986](#)
  - pSensorDataUsage, [987](#)
  - pSpeedHorizontal, [987](#)
  - pSpeedUnc, [987](#)
  - pSpeedVertical, [987](#)
  - pSvUsedforFix, [987](#)
  - pTechnologyMask, [987](#)
  - pTimeSrc, [987](#)
  - pTimeUnc, [987](#)
  - pTimestampUtc, [987](#)
  - pVertConfidence, [987](#)
  - pVertReliability, [987](#)
  - pVertUnc, [987](#)
  - sessionId, [987](#)
  - sessionStatus, [987](#)
  - Tlvresult, [987](#)
- unpack\_loc\_SetExtPowerConfig\_Ind
  - loc.h, [1257](#)
- unpack\_loc\_SetExtPowerConfig\_Ind\_t, [987](#)
  - status, [988](#)
  - Tlvresult, [988](#)
- unpack\_loc\_SetExtPowerState
  - loc.h, [1258](#)
- unpack\_loc\_SetExtPowerState\_t, [988](#)
  - Tlvresult, [988](#)
- unpack\_loc\_SetOperationMode
  - loc.h, [1258](#)
- unpack\_loc\_SetOperationMode\_t, [989](#)
  - Tlvresult, [989](#)
- unpack\_loc\_Start
  - loc.h, [1258](#)
- unpack\_loc\_Start\_t, [989](#)
  - Tlvresult, [989](#)
- unpack\_loc\_Stop
  - loc.h, [1259](#)
- unpack\_loc\_Stop\_t, [989](#)
  - Tlvresult, [990](#)
- unpack\_nas\_GetACCOLC
  - nas.h, [1276](#)
- unpack\_nas\_GetANAAAAAuthenticationStatus
  - nas.h, [1276](#)
- unpack\_nas\_GetCDMANetworkParameters
  - nas.h, [1276](#)
- unpack\_nas\_GetCDMANetworkParameters\_t, [990](#)
  - Application, [990](#)
  - Broadcast, [990](#)
  - CustomSCP, [990](#)
  - ForceRev0, [990](#)
  - Protocol, [990](#)
  - RegForeignNID, [990](#)
  - RegForeignSID, [991](#)
  - RegHomeSID, [991](#)
  - Roaming, [991](#)
  - SCI, [991](#)
  - SCM, [991](#)

- unpack\_nas\_GetHomeNetwork
  - nas.h, [1277](#)
- unpack\_nas\_GetHomeNetwork\_t, [991](#)
  - mcc, [991](#)
  - mnc, [991](#)
  - name, [991](#)
  - nid, [991](#)
  - sid, [991](#)
- unpack\_nas\_GetNetworkPreference
  - nas.h, [1277](#)
- unpack\_nas\_GetNetworkPreference\_t, [991](#)
  - ActiveTechPref, [993](#)
  - Duration, [993](#)
  - PersistentTechPref, [993](#)
  - Tlvresult, [993](#)
- unpack\_nas\_GetRFInfo
  - nas.h, [1277](#)
- unpack\_nas\_GetRFInfo\_t, [993](#)
  - instancesSize, [994](#)
  - RFBandInfoElements, [994](#)
- unpack\_nas\_GetServingNetwork
  - nas.h, [1277](#)
- unpack\_nas\_GetServingNetwork\_t, [994](#)
  - CSDomain, [995](#)
  - DataCaps, [995](#)
  - DataCapsLen, [995](#)
  - MCC, [995](#)
  - MNC, [995](#)
  - Name, [995](#)
  - nameSize, [995](#)
  - PSDomain, [995](#)
  - RAN, [995](#)
  - Radiolfaces, [995](#)
  - RadiolfacesSize, [995](#)
  - RegistrationState, [995](#)
  - Roaming, [995](#)
- unpack\_nas\_GetServingNetworkCapabilities
  - nas.h, [1278](#)
- unpack\_nas\_GetServingNetworkCapabilities\_t, [995](#)
  - DataCaps, [995](#)
  - DataCapsLen, [995](#)
- unpack\_nas\_GetSignalStrengths
  - nas.h, [1278](#)
- unpack\_nas\_GetSignalStrengths\_t, [996](#)
  - len, [996](#)
  - radio, [996](#)
  - rsi, [996](#)
- unpack\_nas\_PerformNetworkScan
  - nas.h, [1278](#)
- unpack\_nas\_PerformNetworkScan\_t, [996](#)
  - p3GppNetworkInfoInstances, [996](#)
  - p3GppNetworkInstanceSize, [996](#)
  - pPCSInstance, [996](#)
  - pPCSInstanceSize, [997](#)
  - pRATInstance, [997](#)
  - pRATInstanceSize, [997](#)
  - pScanResult, [997](#)
- unpack\_nas\_SLQSGetNetworkTime
  - nas.h, [1280](#)
- unpack\_nas\_SLQSGetNetworkTime\_t, [1000](#)
  - p3GPP2TimeInfo, [1001](#)
  - p3GPPTIMEInfo, [1001](#)
- unpack\_nas\_SLQSGetPLMNName
  - nas.h, [1281](#)
- unpack\_nas\_SLQSGetPLMNName\_t, [1001](#)
  - longName, [1001](#)
  - longNameCI, [1001](#)
  - longNameEn, [1001](#)
  - longNameLen, [1001](#)
  - longNameSB, [1001](#)
  - shortName, [1002](#)
  - shortNameCI, [1002](#)
  - shortNameEn, [1002](#)
  - shortNameLen, [1002](#)
  - shortNameSB, [1002](#)
  - spn, [1002](#)
  - spnEncoding, [1002](#)
  - spnLength, [1002](#)
- unpack\_nas\_SLQSGetServingSystem
  - nas.h, [1281](#)
- unpack\_nas\_SLQSGetServingSystem\_t, [1002](#)
  - BasestationID, [1003](#)
  - BasestationLatitude, [1003](#)
  - BasestationLongitude, [1003](#)
  - CDMASystemInfoExt, [1003](#)
  - CallBarStatus, [1003](#)
  - CellID, [1003](#)
  - ConcSvcInfo, [1003](#)
  - CurrentPLMN, [1003](#)
  - DTMInd, [1004](#)
  - DataSrvCapabilities, [1003](#)
  - DefaultRoamInd, [1004](#)
  - DetailedSvcInfo, [1004](#)
  - Gpp2TimeZone, [1004](#)
  - GppNetworkDSTAdjustment, [1004](#)
  - GppTimeZone, [1004](#)
  - HdrPersonality, [1004](#)
  - Lac, [1004](#)
  - NetworkID, [1004](#)
  - PRLInd, [1004](#)
  - RoamIndicatorVal, [1004](#)
  - RoamingIndicatorList, [1004](#)
  - ServingSystem, [1004](#)
  - SystemID, [1004](#)
  - TrackAreaCode, [1004](#)
- unpack\_nas\_SLQSGetSignalStrength
  - nas.h, [1281](#)
- unpack\_nas\_SLQSGetSignalStrength\_t, [1004](#)
  - ecioList, [1005](#)
  - ecioListLen, [1005](#)
  - errorRateList, [1005](#)
  - errorRateListLen, [1005](#)
  - lo, [1005](#)
  - ltsr, [1005](#)
  - ltsnr, [1005](#)
  - rsrqInfo, [1005](#)

- rxSignalStrengthList, [1005](#)
- rxSignalStrengthListLen, [1005](#)
- signalStrengthReqMask, [1005](#)
- sinr, [1005](#)
- unpack\_nas\_SLQSGetSysInfo
  - nas.h, [1282](#)
- unpack\_nas\_SLQSGetSysInfo\_t, [1005](#)
  - pAddCDMASysInfo, [1008](#)
  - pAddGSMSysInfo, [1008](#)
  - pAddHDRSysInfo, [1008](#)
  - pAddLTERSysInfo, [1008](#)
  - pCDMASrvStatusInfo, [1008](#)
  - pCDMASysInfo, [1008](#)
  - pGSMCallBarringSysInfo, [1008](#)
  - pGSMCipherDomainSysInfo, [1008](#)
  - pGSMStatusInfo, [1008](#)
  - pGSMStatusInfo, [1008](#)
  - pHRSrvStatusInfo, [1009](#)
  - pHRSysInfo, [1009](#)
  - pLTERStatusInfo, [1009](#)
  - pLTERSysInfo, [1009](#)
  - pLTERVoiceSupportSysInfo, [1009](#)
  - pWCDMASysInfo, [1009](#)
- unpack\_nas\_SLQSGetSysSelectionPref
  - nas.h, [1282](#)
- unpack\_nas\_SLQSGetSysSelectionPref\_t, [1009](#)
  - pBandPref, [1012](#)
  - pEmerMode, [1012](#)
  - pGWAcqOrderPref, [1012](#)
  - pLTEBandPref, [1012](#)
  - pModePref, [1012](#)
  - pNetSelPref, [1012](#)
  - pPRLPref, [1012](#)
  - pRoamPref, [1012](#)
  - pSrvDomainPref, [1012](#)
- unpack\_nas\_SLQSIInitiateNetworkRegistration
  - nas.h, [1282](#)
- unpack\_nas\_SLQSNasConfigSigInfo2
  - nas.h, [1283](#)
- unpack\_nas\_SLQSNasGetCellLocationInfo
  - nas.h, [1283](#)
- unpack\_nas\_SLQSNasGetCellLocationInfo\_t, [1012](#)
  - pCDMAInfo, [1013](#)
  - pLTEInfoInterfreq, [1013](#)
  - pLTEInfoIntrafreq, [1013](#)
  - pUMTSInfo, [1013](#)
- unpack\_nas\_SLQSNasGetSigInfo
  - nas.h, [1283](#)
- unpack\_nas\_SLQSNasGetSigInfo\_t, [1014](#)
  - CDMASSInfo, [1014](#)
  - GSMSSInfo, [1014](#)
  - HDRSSInfo, [1014](#)
  - LTESSInfo, [1014](#)
- unpack\_nas\_SLQSNasIndicationRegisterExt
  - nas.h, [1284](#)
- unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind
  - nas.h, [1284](#)
- unpack\_nas\_SLQSNasNetworkTimeCallBack\_ind\_t,
  - [1014](#)
  - pDayltSavAdj, [1015](#)
  - pRadioInterface, [1015](#)
  - pTimeZone, [1015](#)
  - universalTime, [1015](#)
- unpack\_nas\_SLQSNasSigInfoCallback
  - nas.h, [1284](#)
- unpack\_nas\_SLQSNasSigInfoCallback\_t, [1015](#)
  - pCDMASigInfo, [1017](#)
  - pGSMSigInfo, [1017](#)
  - pHRSigInfo, [1017](#)
  - pLTERSigInfo, [1017](#)
  - pRscp, [1017](#)
- unpack\_nas\_SLQSNasSmiModemStatus
  - nas.h, [1285](#)
- unpack\_nas\_SLQSNasSmiModemStatus\_t, [1017](#)
  - commonInfo, [1017](#)
  - pLTEInfo, [1017](#)
- unpack\_nas\_SLQSNasSmiOTAMessageCallback
  - nas.h, [1285](#)
- unpack\_nas\_SLQSNasSmiOTAMessageCallback\_ind
  - nas.h, [1285](#)
- unpack\_nas\_SLQSNasSmiOTAMessageCallback\_ind\_
  - t, [1018](#)
  - Info, [1018](#)
  - Tlvresult, [1018](#)
- unpack\_nas\_SLQSNasSysInfoCallback
  - nas.h, [1286](#)
- unpack\_nas\_SLQSSetBandPreference
  - nas.h, [1286](#)
- unpack\_nas\_SLQSSetSignalStrengthsCallback
  - nas.h, [1286](#)
- unpack\_nas\_SLQSSetSysSelectionPref
  - nas.h, [1286](#)
- unpack\_nas\_SLQSSetSysSelectionPrefCallBack\_ind
  - nas.h, [1287](#)
- unpack\_nas\_SLQSSetSysSelectionPrefCallBack\_ind\_t,
  - [1018](#)
  - Info, [1018](#)
  - Tlvresult, [1018](#)
- unpack\_nas\_SLQSSwiGetLteCQI
  - nas.h, [1287](#)
- unpack\_nas\_SLQSSwiGetLteCQI\_t, [1019](#)
  - ValidityCW0, [1019](#)
  - ValidityCW1, [1019](#)
- unpack\_nas\_SLQSSysInfoCallback\_t, [1019](#)
  - pAddCDMASysInfo, [1022](#)
  - pAddGSMSysInfo, [1022](#)
  - pAddHDRSysInfo, [1022](#)
  - pAddLTERSysInfo, [1022](#)
  - pCDMASrvStatusInfo, [1022](#)
  - pCDMASysInfo, [1022](#)
  - pGSMCallBarringSysInfo, [1022](#)
  - pGSMCipherDomainSysInfo, [1022](#)
  - pGSMStatusInfo, [1022](#)
  - pGSMStatusInfo, [1022](#)
  - pHRSrvStatusInfo, [1022](#)

- pHDRSysInfo, 1022
- pLTESrvStatusInfo, 1022
- pLTESysInfo, 1022
- pLTEVoiceSupportSysInfo, 1022
- pSysInfoNoChange, 1022
- pWCDMASysInfo, 1022
- unpack\_nas\_SetACCOLC
  - nas.h, 1279
- unpack\_nas\_SetDataCapabilitiesCallback\_ind
  - nas.h, 1279
- unpack\_nas\_SetDataCapabilitiesCallback\_ind\_t, 997
  - dataCaps, 997
  - dataCapsSize, 997
- unpack\_nas\_SetEventReportInd
  - nas.h, 1279
- unpack\_nas\_SetEventReportInd\_t, 997
  - RFTlv, 997
  - RRTlv, 997
  - SLQSSSTlv, 998
  - SSTlv, 998
- unpack\_nas\_SetLURejectCallback
  - nas.h, 1279
- unpack\_nas\_SetNetworkPreference
  - nas.h, 1280
- unpack\_nas\_SetNetworkPreference\_t, 998
  - Tlvresult, 999
- unpack\_nas\_SetRFInfoCallback
  - nas.h, 1280
- unpack\_nas\_SetRoamingIndicatorCallback\_ind
  - nas.h, 1280
- unpack\_nas\_SetRoamingIndicatorCallback\_ind\_t, 999
  - roaming, 999
- unpack\_nas\_SetServingSystemCallback\_ind
  - nas.h, 1280
- unpack\_nas\_SetServingSystemCallback\_ind\_t, 999
  - SSInfo, 1000
  - Tlvresult, 1000
- unpack\_nas\_SlqsGetLTECphyCAInfo
  - nas.h, 1280
- unpack\_nas\_SlqsGetLTECphyCAInfo\_t, 1000
  - LTECphyCAInfo, 1000
  - Tlvresult, 1000
- unpack\_omaDmConfigTlv\_t, 1022
  - alertmsg, 1024
  - alertmsglength, 1024
  - state, 1024
  - userInputReq, 1024
  - userInputTimeout, 1024
- unpack\_omaDmFotaTlv\_t, 1024
  - description, 1026
  - descriptionlength, 1026
  - fwloadsize, 1026
  - fwloadComplete, 1026
  - namelength, 1026
  - package\_name, 1026
  - sessionType, 1026
  - severity, 1026
  - state, 1026
  - updateCompleteStatus, 1026
  - userInputReq, 1026
  - userInputTimeout, 1026
  - version, 1026
  - versionlength, 1026
- unpack\_omaDmNotificationsTlv\_t, 1026
  - notification, 1027
  - sessionStatus, 1027
- unpack\_qmi\_t, 1027
  - msgid, 1027
  - type, 1027
  - xid, 1027
- unpack\_qos\_IPv4Addr\_t, 1028
  - addr, 1028
  - subnetMask, 1028
- unpack\_qos\_IPv6Addr\_t, 1028
  - addr, 1029
  - prefixLen, 1029
- unpack\_qos\_IPv6TrafCls\_t, 1029
  - mask, 1029
  - val, 1029
- unpack\_qos\_Port\_t, 1030
  - port, 1030
  - range, 1030
- unpack\_qos\_QosFlowInfo\_t, 1030
  - BearerID, 1032
  - is\_RxQFlowGranted\_Available, 1032
  - is\_TxQFlowGranted\_Available, 1032
  - NumRxFilters, 1032
  - NumTxFilters, 1032
  - QFlowState, 1032
  - RxQFilter, 1032
  - RxQFlowGranted, 1032
  - TxQFilter, 1032
  - TxQFlowGranted, 1032
- unpack\_qos\_QosFlowInfoState\_t, 1032
  - id, 1033
  - isNewFlow, 1033
  - state, 1033
- unpack\_qos\_SLQSQosGetNetworkStatus
  - qos.h, 1744
- unpack\_qos\_SLQSQosGetNetworkStatus\_t, 1033
  - NWQoSStatus, 1033
- unpack\_qos\_SLQSQosSwiReadApnExtraParams
  - qos.h, 1746
- unpack\_qos\_SLQSQosSwiReadApnExtraParams\_t, 1033
  - ambr\_dl, 1034
  - ambr\_dl\_ext, 1034
  - ambr\_dl\_ext2, 1034
  - ambr\_ul, 1034
  - ambr\_ul\_ext, 1034
  - ambr\_ul\_ext2, 1034
  - apnId, 1034
- unpack\_qos\_SLQSQosSwiReadDataStats
  - qos.h, 1746
- unpack\_qos\_SLQSQosSwiReadDataStats\_t, 1034
  - apnId, 1035



- numQosFlow, [1036](#)
- qosFlow, [1036](#)
- total\_rx\_bytes, [1036](#)
- total\_rx\_pkt, [1036](#)
- total\_tx\_bytes, [1036](#)
- total\_tx\_pkt, [1036](#)
- unpack\_qos\_SLQSSetQosEventCallback
  - qos.h, [1747](#)
- unpack\_qos\_SLQSSetQosEventCallback\_ind
  - qos.h, [1747](#)
- unpack\_qos\_SLQSSetQosEventCallback\_ind\_t, [1036](#)
  - NumFlows, [1036](#)
  - QosFlowInfo, [1036](#)
- unpack\_qos\_SLQSSetQosNWStatusCallback\_ind
  - qos.h, [1748](#)
- unpack\_qos\_SLQSSetQosNWStatusCallback\_ind\_t, [1036](#)
  - status, [1038](#)
- unpack\_qos\_SLQSSetQosPriEventCallback\_ind
  - qos.h, [1748](#)
- unpack\_qos\_SLQSSetQosPriEventCallback\_ind\_t, [1038](#)
  - event, [1038](#)
- unpack\_qos\_SLQSSetQosStatusCallback\_ind
  - qos.h, [1750](#)
- unpack\_qos\_SLQSSetQosStatusCallback\_ind\_t, [1038](#)
  - event, [1040](#)
  - id, [1040](#)
  - reason, [1040](#)
  - status, [1040](#)
- unpack\_qos\_Tos\_t, [1049](#)
  - mask, [1049](#)
  - val, [1049](#)
- unpack\_qos\_dataRate\_t, [1027](#)
  - dataRateMax, [1028](#)
  - guaranteedRate, [1028](#)
- unpack\_qos\_pktErrRate\_t, [1029](#)
  - exponent, [1030](#)
  - multiplier, [1030](#)
- unpack\_qos\_swiQosFilter\_t, [1040](#)
  - EspSpi, [1042](#)
  - IPv4DstAddr, [1042](#)
  - IPv4SrcAddr, [1042](#)
  - IPv4Tos, [1042](#)
  - IPv6DstAddr, [1042](#)
  - IPv6Label, [1042](#)
  - IPv6SrcAddr, [1042](#)
  - IPv6TrafCls, [1042](#)
  - Id, [1042](#)
  - index, [1042](#)
  - is\_EspSpi\_Available, [1042](#)
  - is\_IPv4DstAddr\_Available, [1042](#)
  - is\_IPv4SrcAddr\_Available, [1043](#)
  - is\_IPv4Tos\_Available, [1043](#)
  - is\_IPv6DstAddr\_Available, [1043](#)
  - is\_IPv6Label\_Available, [1043](#)
  - is\_IPv6SrcAddr\_Available, [1043](#)
  - is\_IPv6TrafCls\_Available, [1043](#)
  - is\_Id\_Available, [1042](#)
  - is\_NxtHdrProto\_Available, [1043](#)
  - is\_Precedence\_Available, [1043](#)
  - is\_TCPDstPort\_Available, [1043](#)
  - is\_TCPSrcPort\_Available, [1043](#)
  - is\_TransDstPort\_Available, [1043](#)
  - is\_TransSrcPort\_Available, [1043](#)
  - is\_UDPDstPort\_Available, [1043](#)
  - is\_UDPSrcPort\_Available, [1043](#)
  - NxtHdrProto, [1043](#)
  - Precedence, [1043](#)
  - TCPDstPort, [1043](#)
  - TCPSrcPort, [1043](#)
  - TransDstPort, [1043](#)
  - TransSrcPort, [1043](#)
  - UDPDstPort, [1043](#)
  - UDPSrcPort, [1043](#)
  - version, [1043](#)
- unpack\_qos\_swiQosFlow\_t, [1043](#)
  - DataRate, [1047](#)
  - index, [1047](#)
  - is\_DataRate\_Available, [1047](#)
  - is\_Jitter\_Available, [1047](#)
  - is\_Latency\_Available, [1047](#)
  - is\_LteQci\_Available, [1047](#)
  - is\_MaxAllowedPktSz\_Available, [1047](#)
  - is\_MinPolicedPktSz\_Available, [1047](#)
  - is\_PktErrRate\_Available, [1047](#)
  - is\_ProfileId3GPP2\_Available, [1047](#)
  - is-TokenBucket\_Available, [1047](#)
  - is\_TrafficClass\_Available, [1047](#)
  - is\_val\_3GPP2Pri\_Available, [1047](#)
  - is\_val\_3GPPImCn\_Available, [1047](#)
  - is\_val\_3GPPSigInd\_Available, [1047](#)
  - Jitter, [1048](#)
  - Latency, [1048](#)
  - LteQci, [1048](#)
  - MaxAllowedPktSz, [1048](#)
  - MinPolicedPktSz, [1048](#)
  - PktErrRate, [1048](#)
  - ProfileId3GPP2, [1048](#)
  - TokenBucket, [1048](#)
  - TrafficClass, [1048](#)
  - val\_3GPP2Pri, [1048](#)
  - val\_3GPPImCn, [1048](#)
  - val\_3GPPResResidualBER, [1048](#)
  - val\_3GPPSigInd, [1048](#)
  - val\_3GPPTraHdIPri, [1048](#)
- unpack\_qos\_tokenBucket\_t, [1048](#)
  - bucketSz, [1048](#)
  - peakRate, [1048](#)
  - tokenRate, [1049](#)
- unpack\_result\_code\_only
  - common.h, [1213](#)
- unpack\_sms\_SLQSDeleteSMS
  - sms.h, [1758](#)
- unpack\_sms\_SLQSDeleteSMS\_t, [1052](#)
- unpack\_sms\_SLQSGetSMS

- sms.h, [1759](#)
- unpack\_sms\_SLQSGetSMS\_t, [1052](#)
  - message, [1053](#)
  - messageFormat, [1053](#)
  - messageSize, [1053](#)
  - messageTag, [1053](#)
- unpack\_sms\_SLQSGetSMSList
  - sms.h, [1759](#)
- unpack\_sms\_SLQSGetSMSList\_t, [1053](#)
  - messageList, [1054](#)
  - messageListSize, [1054](#)
- unpack\_sms\_SLQSMModifySMSStatus
  - sms.h, [1759](#)
- unpack\_sms\_SLQSMModifySMSStatus\_t, [1054](#)
- unpack\_sms\_SLQSWmsMemoryFullCallBack\_ind
  - sms.h, [1760](#)
- unpack\_sms\_SLQSWmsMemoryFullCallBack\_ind\_t, [1054](#)
  - messageMode, [1054](#)
  - storageType, [1054](#)
- unpack\_sms\_SendSMS
  - sms.h, [1757](#)
- unpack\_sms\_SendSMS\_t, [1050](#)
  - messageFailureCode, [1050](#)
  - messageID, [1050](#)
- unpack\_sms\_SetNewSMSCallback
  - sms.h, [1758](#)
- unpack\_sms\_SetNewSMSCallback\_ind
  - sms.h, [1758](#)
- unpack\_sms\_SetNewSMSCallback\_ind\_t, [1051](#)
  - ETWSTlv, [1052](#)
  - IMSTlv, [1052](#)
  - MMTlv, [1052](#)
  - NewMMTlv, [1052](#)
  - SMSCTlv, [1052](#)
  - TRMessageTlv, [1052](#)
- unpack\_sms\_SetNewSMSCallback\_t, [1052](#)
- unpack\_swiloc\_SwiLocGetAutoStart
  - swiloc.h, [1762](#)
- unpack\_swiloc\_SwiLocGetAutoStart\_t, [1054](#)
  - fix\_rate, [1056](#)
  - fix\_rate\_reported, [1056](#)
  - fix\_type, [1056](#)
  - fix\_type\_reported, [1056](#)
  - function, [1056](#)
  - function\_reported, [1056](#)
  - max\_dist, [1056](#)
  - max\_dist\_reported, [1056](#)
  - max\_time, [1056](#)
  - max\_time\_reported, [1056](#)
- unpack\_swiloc\_SwiLocSetAutoStart
  - swiloc.h, [1763](#)
- unpack\_swisma\_SLQSOMADMAAlertCallback
  - swisma.h, [1769](#)
- unpack\_swisma\_SLQSOMADMAAlertCallback\_ind
  - swisma.h, [1769](#)
- unpack\_swisma\_SLQSOMADMAAlertCallback\_ind\_t, [1056](#)
- eventType, [1057](#)
- unpack\_swisma\_SLQSOMADMCancelSession
  - swisma.h, [1770](#)
- unpack\_swisma\_SLQSOMADMGetSessionInfo
  - swisma.h, [1770](#)
- unpack\_swisma\_SLQSOMADMGetSessionInfo\_t, [1057](#)
  - Date, [1059](#)
  - DateLength, [1060](#)
  - PkgDescLength, [1060](#)
  - PkgDescription, [1060](#)
  - PkgName, [1060](#)
  - PkgNameLength, [1060](#)
  - RetryCount, [1060](#)
  - SessionState, [1060](#)
  - SessionType, [1060](#)
  - Severity, [1060](#)
  - Source, [1060](#)
  - SourceLength, [1060](#)
  - Status, [1060](#)
  - Time, [1060](#)
  - TimeLength, [1060](#)
  - UpdateCompleteStatus, [1060](#)
- unpack\_swisma\_SLQSOMADMGetSettings
  - swisma.h, [1771](#)
- unpack\_swisma\_SLQSOMADMGetSettings\_t, [1060](#)
  - Autosdm, [1062](#)
  - FOTAdownload, [1062](#)
  - FwAutoCheck, [1062](#)
- unpack\_swisma\_SLQSOMADMSendSelection
  - swisma.h, [1771](#)
- unpack\_swisma\_SLQSOMADMSetSettings
  - swisma.h, [1772](#)
- unpack\_swisma\_SLQSOMADMStartSession
  - swisma.h, [1772](#)
- unpack\_swisma\_SLQSOMADMStartSession\_t, [1062](#)
  - FwAvailability, [1062](#)
- unpack\_uim\_ChangePin
  - uim.h, [1778](#)
- unpack\_uim\_ChangePin\_t, [1062](#)
  - pEncryptedPIN1, [1063](#)
  - pIndicationToken, [1063](#)
  - pRemainingRetries, [1063](#)
  - Tlvresult, [1063](#)
- unpack\_uim\_GetCardStatus
  - uim.h, [1779](#)
- unpack\_uim\_GetCardStatus\_t, [1063](#)
  - pCardStatus, [1064](#)
  - pHotSwapStatus, [1064](#)
  - Tlvresult, [1064](#)
- unpack\_uim\_ReadTransparent
  - uim.h, [1779](#)
- unpack\_uim\_ReadTransparent\_t, [1064](#)
  - pCardResult, [1065](#)
  - pEncryptedData, [1065](#)
  - pIndicationToken, [1065](#)
  - pReadResult, [1065](#)
  - Tlvresult, [1065](#)
- unpack\_uim\_SLQSUIEventRegister



- uim.h, [1780](#)
- unpack\_uim\_SLQSUIEventRegister\_t, [1066](#)
  - eventMask, [1067](#)
- unpack\_uim\_SLQSUIGetSlotsStatus
  - uim.h, [1780](#)
- unpack\_uim\_SLQSUIGetSlotsStatus\_t, [1067](#)
  - pNumberOfPhySlot, [1067](#)
  - pUimSlotsStatus, [1067](#)
- unpack\_uim\_SLQSUISetStatusChangeCallBack\_ind
  - uim.h, [1781](#)
- unpack\_uim\_SLQSUISetStatusChangeCallBack\_ind\_t, [1067](#)
- unpack\_uim\_SLQSUISwitchSlot
  - uim.h, [1781](#)
- unpack\_uim\_SetPinProtection
  - uim.h, [1779](#)
- unpack\_uim\_SetPinProtection\_t, [1065](#)
  - pEncryptedPIN1, [1066](#)
  - pIndicationToken, [1066](#)
  - pRemainingRetries, [1066](#)
  - Tlvresult, [1066](#)
- unpack\_uim\_SetUimSlotStatusChangeCallback\_ind
  - uim.h, [1780](#)
- unpack\_uim\_SetUimSlotStatusChangeCallback\_ind\_t, [1066](#)
  - bNumberOfPhySlots, [1066](#)
  - slotsstatusChange, [1066](#)
- unpack\_uim\_UnblockPin
  - uim.h, [1781](#)
- unpack\_uim\_UnblockPin\_t, [1068](#)
  - pEncryptedPIN1, [1068](#)
  - pIndicationToken, [1068](#)
  - pRemainingRetries, [1068](#)
  - Tlvresult, [1068](#)
- unpack\_uim\_VerifyPin
  - uim.h, [1782](#)
- unpack\_uim\_VerifyPin\_t, [1068](#)
  - pEncryptedPIN1, [1070](#)
  - pIndicationToken, [1070](#)
  - pRemainingRetries, [1070](#)
  - Tlvresult, [1070](#)
- unpack\_wds\_GetConnectionRate
  - wds.h, [1800](#)
- unpack\_wds\_GetConnectionRate\_t, [1070](#)
  - currentChannelRXRate, [1071](#)
  - currentChannelTXRate, [1071](#)
  - maxChannelRXRate, [1071](#)
  - maxChannelTXRate, [1071](#)
- unpack\_wds\_GetDefaultProfile
  - wds.h, [1800](#)
- unpack\_wds\_GetDefaultProfile\_t, [1071](#)
  - apnname, [1071](#)
  - apnsize, [1071](#)
  - auth, [1071](#)
  - ipaddr, [1072](#)
  - ipaddrv6, [1072](#)
  - name, [1072](#)
  - namesize, [1072](#)
  - pdptype, [1072](#)
  - pridns, [1072](#)
  - pridnsv6, [1072](#)
  - secdns, [1072](#)
  - secdnsv6, [1072](#)
  - username, [1072](#)
  - usersize, [1072](#)
- unpack\_wds\_GetDefaultProfileNum
  - wds.h, [1801](#)
- unpack\_wds\_GetDefaultProfileNum\_t, [1072](#)
  - index, [1072](#)
- unpack\_wds\_GetDormancyState
  - wds.h, [1801](#)
- unpack\_wds\_GetDormancyState\_t, [1072](#)
  - dormancyState, [1073](#)
- unpack\_wds\_GetLastMobileIPError
  - wds.h, [1801](#)
- unpack\_wds\_GetLastMobileIPError\_t, [1073](#)
  - error, [1073](#)
- unpack\_wds\_GetMobileIP
  - wds.h, [1802](#)
- unpack\_wds\_GetMobileIP\_t, [1073](#)
  - mipMode, [1073](#)
- unpack\_wds\_GetMobileIPProfile
  - wds.h, [1802](#)
- unpack\_wds\_GetMobileIPProfile\_t, [1073](#)
  - AAASPI, [1074](#)
  - AAASState, [1074](#)
  - address, [1074](#)
  - enabled, [1074](#)
  - HASPI, [1074](#)
  - HASState, [1074](#)
  - NAI, [1074](#)
  - naiSize, [1074](#)
  - primaryHA, [1074](#)
  - revTunneling, [1074](#)
  - secondaryHA, [1074](#)
- unpack\_wds\_GetPacketStatus
  - wds.h, [1802](#)
- unpack\_wds\_GetPacketStatus\_t, [1074](#)
  - rXDroppedCount, [1075](#)
  - rXOKBytesLastCall, [1075](#)
  - rXOkBytesCount, [1075](#)
  - rXPacketErrors, [1075](#)
  - rXPacketOverflows, [1075](#)
  - rXPacketSuccesses, [1075](#)
  - tXDroppedCount, [1075](#)
  - tXOKBytesLastCall, [1075](#)
  - tXOkBytesCount, [1075](#)
  - tXPacketErrors, [1075](#)
  - tXPacketOverflows, [1075](#)
  - tXPacketSuccesses, [1075](#)
- unpack\_wds\_GetSessionDuration
  - wds.h, [1803](#)
- unpack\_wds\_GetSessionDuration\_t, [1076](#)
  - callDuration, [1076](#)
- unpack\_wds\_GetSessionState
  - wds.h, [1803](#)

- unpack\_wds\_GetSessionState\_t, 1076
  - connectionStatus, 1076
- unpack\_wds\_RMSetTransferStatistics
  - wds.h, 1803
- unpack\_wds\_RMSetTransferStatistics\_t, 1076
- unpack\_wds\_SLQSCreateProfile
  - wds.h, 1805
- unpack\_wds\_SLQSCreateProfile\_t, 1076
  - pCreateProfileOut, 1077
  - pProfileID, 1077
  - Tlvresult, 1077
- unpack\_wds\_SLQSDeleteProfile
  - wds.h, 1805
- unpack\_wds\_SLQSDeleteProfile\_t, 1077
  - extendedErrorCode, 1077
- unpack\_wds\_SLQSGet3GPPConfigItem
  - wds.h, 1805
- unpack\_wds\_SLQSGet3GPPConfigItem\_t, 1077
  - \_3gppRelease, 1078
  - defaultPDNEnabled, 1078
  - profileList, 1078
- unpack\_wds\_SLQSGetCurrDataSystemStat
  - wds.h, 1806
- unpack\_wds\_SLQSGetCurrDataSystemStat\_t, 1079
  - currNetworkInfo, 1079
  - networkInfoLen, 1079
  - prefNetwork, 1079
- unpack\_wds\_SLQSGetDUNCallInfo
  - wds.h, 1806
- unpack\_wds\_SLQSGetDUNCallInfo\_t, 1080
  - callEndReason, 1080
  - channelRate, 1080
  - connectionStatus, 1080
  - dataBearerTech, 1080
  - dormancyStatus, 1080
  - lastCallDataBearerTech, 1080
  - mdmCallDurationActive, 1080
  - rxOKBytesCount, 1081
  - txOKBytesCount, 1081
- unpack\_wds\_SLQSGetDataBearerTechnology
  - wds.h, 1806
- unpack\_wds\_SLQSGetDataBearerTechnology\_t, 1079
  - curDataBearerTechnology, 1079
  - dataBearerMask, 1079
  - lastCallDataBearerTechnology, 1079
- unpack\_wds\_SLQSGetProfileSettings
  - wds.h, 1807
- unpack\_wds\_SLQSGetProfileSettings\_t, 1081
  - pProfileSettings, 1081
  - ProfileType, 1081
  - Tlvresult, 1081
- unpack\_wds\_SLQSGetRuntimeSettings
  - wds.h, 1807
- unpack\_wds\_SLQSGetRuntimeSettings\_t, 1081
  - APNName, 1082
  - Authentication, 1082
  - DomainList, 1082
  - GPRSGrantedQoS, 1082
  - GWAddressV4, 1082
  - IMCNflag, 1082
  - IPFamilyPreference, 1082
  - IPv6AddrInfo, 1082
  - IPv6GWAddrInfo, 1082
  - IPv4, 1082
  - Mtu, 1082
  - PDPTType, 1083
  - PrimaryDNSV4, 1083
  - PrimaryDNSV6, 1083
  - ProfileID, 1083
  - ProfileName, 1083
  - SecondaryDNSV4, 1083
  - SecondaryDNSV6, 1083
  - ServerAddrList, 1083
  - SubnetMaskV4, 1083
  - Technology, 1083
  - UMTSGrantedQoS, 1083
  - Username, 1083
- unpack\_wds\_SLQSModifyProfile
  - wds.h, 1807
- unpack\_wds\_SLQSModifyProfile\_t, 1083
  - pExtErrorCode, 1083
- unpack\_wds\_SLQSSetDHCPv4ClientConfig
  - wds.h, 1809
- unpack\_wds\_SLQSSetDHCPv4ClientConfig\_t, 1086
  - pHwConfig, 1087
- unpack\_wds\_SLQSSet3GPPConfigItem
  - wds.h, 1808
- unpack\_wds\_SLQSSetIPFamilyPreference
  - wds.h, 1808
- unpack\_wds\_SLQSSetIPFamilyPreference\_t, 1083
  - Tlvresult, 1084
- unpack\_wds\_SLQSSetPacketSrvStatusCallback
  - wds.h, 1808
- unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t, 1084
  - bearerID, 1084
  - conn\_status, 1084
  - ipFamily, 1084
  - reconfigReqd, 1084
  - sessionEndReason, 1084
  - techName, 1084
  - verboseSessnEndReason, 1085
  - verboseSessnEndReasonType, 1085
- unpack\_wds\_SLQSSetWdsEventCallback
  - wds.h, 1809
- unpack\_wds\_SLQSSetWdsEventCallback\_ind
  - wds.h, 1809
- unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t, 1085
  - currDBTechAvail, 1086
  - currNWInfo, 1086
  - dBTechAvail, 1086
  - dBTechnology, 1086
  - dataSysStatAvail, 1086
  - dormancyStatAvail, 1086
  - dormancyStatus, 1086
  - mipStatus, 1086

- mipstatAvail, [1086](#)
- netInfoLen, [1086](#)
- prefNetwork, [1086](#)
- ratMask, [1086](#)
- rx\_bytes, [1086](#)
- rx\_pkts, [1086](#)
- soMask, [1086](#)
- tx\_bytes, [1086](#)
- tx\_pkts, [1086](#)
- xferStatAvail, [1086](#)
- unpack\_wds\_SLQSSStartDataSession
  - wds.h, [1809](#)
- unpack\_wds\_SLQSSStartDataSession\_t, [1087](#)
  - pFailureReason, [1087](#)
  - pVerboseFailReasonType, [1087](#)
  - pVerboseFailureReason, [1087](#)
  - psid, [1087](#)
- unpack\_wds\_SLQSStopDataSession
  - wds.h, [1811](#)
- unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings
  - wds.h, [1811](#)
- unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings\_t, [1087](#)
  - apnName, [1088](#)
  - bearerId, [1088](#)
  - contextId, [1088](#)
  - ipv4Address, [1088](#)
  - ipv4GWAddress, [1088](#)
  - ipv6Address, [1088](#)
  - ipv6GWAddress, [1089](#)
- unpack\_wds\_SetDefaultProfile
  - wds.h, [1804](#)
- unpack\_wds\_SetDefaultProfileNum
  - wds.h, [1804](#)
- unpack\_wds\_SetMobileIPProfile
  - wds.h, [1804](#)
- unpack\_wds\_SetMobileIPProfile\_t, [1076](#)
- UnpackQmiProfileInfo
  - wds.h, [1786](#)
- unpackWdsProfileParam, [1089](#)
  - SlqsProfile3GPP, [1089](#)
  - SlqsProfile3GPP2, [1089](#)
- upLink
  - NSSAudioCtrl, [571](#)
- UpdateCompleteStatus
  - unpack\_swima\_SLQSOMADMGetSessionInfo\_t, [1060](#)
- updateCompleteStatus
  - omaDmFotaTlv, [577](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- upgrade\_mc77xx\_fw
  - qaGobiApiFms.h, [1460](#)
- UpgradeFirmware2k
  - qaGobiApiFms.h, [1461](#)
- upinRetries
  - slotInf, [801](#)
  - slotInfo, [803](#)
  - uim\_slotInfo, [911](#)
- upinState
  - slotInf, [801](#)
  - slotInfo, [803](#)
  - uim\_slotInfo, [911](#)
- UpkQmiCbkCatEventReportInd
  - qaCbkCatEventReportInd.h, [1289](#)
- UpkQmiCbkSwiOmaDmEventReportInd
  - qaCbkSwiOmaDmEventReportInd.h, [1290](#)
- UpkQmiCbkSwiOmaDmEventReportIndExt
  - qaCbkSwiOmaDmEventReportInd.h, [1290](#)
- UpkQmiNasGetRFBandInfo
  - qaNasGetRFBandInfo.h, [1732](#)
- UpkQmiNasPerformNetworkScan
  - qaNasPerformNetworkScan.h, [1733](#)
- upukRetries
  - slotInf, [801](#)
  - slotInfo, [803](#)
  - uim\_slotInfo, [911](#)
- usageMask
  - loc\_sensorDataUsage, [385](#)
  - sensorDataUsage\_s, [760](#)
- User Identity Module Service (UIM), [46](#)
- userData
  - SMSAsyncRawSend\_s, [825](#)
- userInputReq
  - omaDmConfigTlv, [573](#)
  - omaDmConfigTlvExt, [575](#)
  - omaDmFotaTlv, [577](#)
  - unpack\_omaDmConfigTlv\_t, [1024](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- userInputTimeout
  - omaDmConfigTlv, [573](#)
  - omaDmConfigTlvExt, [575](#)
  - omaDmFotaTlv, [577](#)
  - omaDmFotaTlvExt, [580](#)
  - unpack\_omaDmConfigTlv\_t, [1024](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- Username
  - unpack\_wds\_SLQSGetRuntimeSettings\_t, [1083](#)
- username
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- usersize
  - unpack\_wds\_GetDefaultProfile\_t, [1072](#)
- ussDCS
  - USSInfo, [1095](#)
- ussData
  - USSInfo, [1095](#)
- ussLen
  - USSInfo, [1095](#)
- uusInfo
  - allCallsUUSInfo, [102](#)
- v4sessionId
  - qaQmiInterfaceInfo, [696](#)
  - ssdatasession\_params, [847](#)
  - WdsRunTimeSettings, [1201](#)
- v6sessionId
  - qaQmiInterfaceInfo, [696](#)
  - ssdatasession\_params, [847](#)

- WdsRunTimeSettings, [1201](#)
- VOICE\_SUPS\_SRV\_CLASS\_DATA
  - qaGobiApiVoice.h, [1657](#)
- VOICE\_SUPS\_SRV\_CLASS\_DATA\_CIRCUITASYNC
  - qaGobiApiVoice.h, [1658](#)
- VOICE\_SUPS\_SRV\_CLASS\_DATA\_CIRCUITSYNC
  - qaGobiApiVoice.h, [1657](#)
- VOICE\_SUPS\_SRV\_CLASS\_FAX
  - qaGobiApiVoice.h, [1657](#)
- VOICE\_SUPS\_SRV\_CLASS\_NONE
  - qaGobiApiVoice.h, [1657](#)
- VOICE\_SUPS\_SRV\_CLASS\_PACKETACCESS
  - qaGobiApiVoice.h, [1658](#)
- VOICE\_SUPS\_SRV\_CLASS\_PADACCESS
  - qaGobiApiVoice.h, [1658](#)
- VOICE\_SUPS\_SRV\_CLASS\_SMS
  - qaGobiApiVoice.h, [1657](#)
- VOICE\_SUPS\_SRV\_CLASS\_VOICE
  - qaGobiApiVoice.h, [1657](#)
- VDOP
  - loc\_precisionDilution, [384](#)
  - precisionDilution\_s, [677](#)
- VOICE\_SRV
  - qaGobiApiCbK.h, [1305](#)
- val
  - IPv6TrafCls, [341](#)
  - Tos, [889](#)
  - unpack\_qos\_IPv6TrafCls\_t, [1029](#)
  - unpack\_qos\_Tos\_t, [1049](#)
- val\_3GPP2Pri
  - unpack\_qos\_swiQosFlow\_t, [1048](#)
- val\_3GPPIImCn
  - unpack\_qos\_swiQosFlow\_t, [1048](#)
- val\_3GPPResResidualBER
  - unpack\_qos\_swiQosFlow\_t, [1048](#)
- val\_3GPPSigInd
  - unpack\_qos\_swiQosFlow\_t, [1048](#)
- val\_3GPPTraHdlPri
  - unpack\_qos\_swiQosFlow\_t, [1048](#)
- ValidMask
  - GPSSStateInfo, [293](#)
- validMask
  - satelliteInfo, [758](#)
- ValidateSPC
  - qaGobiApiDms.h, [1445](#)
- ValidityCW0
  - LteCQIParm, [403](#)
  - unpack\_nas\_SLQSSwiGetLteCQI\_t, [1019](#)
- ValidityCW1
  - LteCQIParm, [403](#)
  - unpack\_nas\_SLQSSwiGetLteCQI\_t, [1019](#)
- Value
  - GetM2MSprkGainResp, [280](#)
  - SetM2MSprkGainReq, [785](#)
- value\_length
  - custSettingInfo, [200](#)
  - DMScustSettingInfo, [222](#)
  - pack\_dms\_SetCustFeaturesV2\_t, [584](#)
  - setCustomSettingV2, [774](#)
- verbFailReason
  - ssdatasession\_params, [847](#)
- verbFailReasonType
  - ssdatasession\_params, [847](#)
- verboseSessnEndReason
  - \_packetSrvStatus, [64](#)
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t, [1085](#)
- verboseSessnEndReasonType
  - \_packetSrvStatus, [64](#)
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback\_t, [1085](#)
- verifyLeft
  - personalizationStatus, [665](#)
  - remainingRetries, [738](#)
  - uim\_remainingRetries, [907](#)
- verifyPIN
  - pack\_uim\_VerifyPin\_t, [636](#)
  - UIMVerifyPinReq, [938](#)
- verifyUIMPIN, [1097](#)
- pinID, [1098](#)
- pinLen, [1098](#)
- pinVal, [1098](#)
- version
  - omaDmFotaTlv, [577](#)
  - omaDmFotaTlvExt, [580](#)
  - swiQosFilter, [864](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
  - unpack\_qos\_swiQosFilter\_t, [1043](#)
- versionlength
  - omaDmFotaTlv, [577](#)
  - omaDmFotaTlvExt, [580](#)
  - unpack\_omaDmFotaTlv\_t, [1026](#)
- VerticalUncertainty
  - GPSSStateInfo, [293](#)
- VirtStream
  - protocolSubtypeElement, [694](#)
- Voice Service (VOICE), [44](#)
- voiceALSSelectLineInfo, [1098](#)
  - lineValue, [1099](#)
- voiceALSSetLineSwitchInfo, [1099](#)
  - switchOption, [1099](#)
- voiceAnswerCall, [1099](#)
  - pCallId, [1100](#)
- voiceBindSubscriptionInfo, [1100](#)
  - subsType, [1100](#)
- voiceBurstDTMFInfo, [1100](#)
  - BurstDTMFInfo, [1101](#)
  - pBurstDTMFLengths, [1101](#)
- voiceCallInfoReq, [1101](#)
  - callID, [1101](#)
- voiceCallInfoResp, [1101](#)
  - pAlertType, [1104](#)
  - pAlertingPattern, [1104](#)
  - pAlphaIDInfo, [1104](#)
  - pCallInfo, [1104](#)
  - pConnectNumInfo, [1104](#)

- pDiagInfo, [1104](#)
- pOTASPStatus, [1105](#)
- pRemotePartyName, [1105](#)
- pRemotePartyNum, [1105](#)
- pSrvOpt, [1105](#)
- pUUSInfo, [1105](#)
- pVoicePrivacy, [1105](#)
- voiceCallRequestParams, [1105](#)
  - callNumber, [1107](#)
  - pCLIRType, [1107](#)
  - pCUGInfo, [1107](#)
  - pCallPartySubAdd, [1107](#)
  - pCallType, [1107](#)
  - pEmergencyCategory, [1107](#)
  - pSvcType, [1107](#)
  - pUUSInfo, [1107](#)
- voiceCallResponseParams, [1107](#)
  - pAlphaIDInfo, [1108](#)
  - pCCResultType, [1108](#)
  - pCCSUPSType, [1108](#)
  - pCallID, [1108](#)
- voiceContDTMFInfo, [1108](#)
  - DTMFdigit, [1109](#)
  - pCallID, [1109](#)
- voiceDTMFEventInfo, [1109](#)
  - DTMFInformation, [1110](#)
  - pOffLength, [1110](#)
  - pOnLength, [1110](#)
- voiceFlashInfo, [1110](#)
  - pCallID, [1111](#)
  - pFlashPayLd, [1111](#)
  - pFlashType, [1111](#)
- voiceGetAllCallInfo, [1111](#)
  - pArrAlertingPattern, [1113](#)
  - pArrAlertingType, [1113](#)
  - pArrAlphaID, [1113](#)
  - pArrCallEndReason, [1113](#)
  - pArrCallInfo, [1113](#)
  - pArrCalledPartyNum, [1113](#)
  - pArrConnectPartyNum, [1113](#)
  - pArrDiagInfo, [1113](#)
  - pArrRedirPartyNum, [1113](#)
  - pArrRemotePartyName, [1113](#)
  - pArrRemotePartyNum, [1113](#)
  - pArrSvcOption, [1114](#)
  - pArrUUSInfo, [1114](#)
  - pOTASPStatus, [1114](#)
  - pVoicePrivacy, [1114](#)
- voiceGetCLIPResp, [1121](#)
  - pAlphaIDInfo, [1123](#)
  - pCCResType, [1123](#)
  - pCCSUPSType, [1123](#)
  - pCLIPResp, [1124](#)
  - pCallID, [1123](#)
  - pFailCause, [1124](#)
- voiceGetCLIRResp, [1124](#)
  - pAlphaIDInfo, [1125](#)
  - pCCResType, [1125](#)
- pCCSUPSType, [1125](#)
- pCLIRResp, [1125](#)
- pCallID, [1125](#)
- pFailCause, [1125](#)
- voiceGetCNAPResp, [1125](#)
  - pAlphaIDInfo, [1126](#)
  - pCCResType, [1126](#)
  - pCCSUPSType, [1126](#)
  - pCNAPResp, [1127](#)
  - pCallID, [1126](#)
  - pFailCause, [1127](#)
- voiceGetCOLPResp, [1127](#)
  - pAlphaIDInfo, [1128](#)
  - pCCResType, [1128](#)
  - pCCSUPSType, [1128](#)
  - pCOLPResp, [1128](#)
  - pCallID, [1128](#)
  - pFailCause, [1128](#)
- voiceGetCOLRResp, [1128](#)
  - pAlphaIDInfo, [1129](#)
  - pCCResType, [1129](#)
  - pCCSUPSType, [1129](#)
  - pCOLRResp, [1130](#)
  - pCallID, [1129](#)
  - pFailCause, [1130](#)
- voiceGetCallBarringReq, [1114](#)
  - pSvcClass, [1115](#)
  - reason, [1115](#)
- voiceGetCallBarringResp, [1115](#)
  - pAlphaIDInfo, [1116](#)
  - pCCResType, [1116](#)
  - pCCSUPSType, [1116](#)
  - pCallID, [1116](#)
  - pFailCause, [1116](#)
  - pSvcClass, [1116](#)
- voiceGetCallFWReq, [1116](#)
  - pSvcClass, [1118](#)
  - Reason, [1118](#)
- voiceGetCallFWResp, [1118](#)
  - pAlphaIDInfo, [1119](#)
  - pCCResType, [1120](#)
  - pCCSUPSType, [1120](#)
  - pCallID, [1119](#)
  - pFailCause, [1120](#)
  - pGetCallFWExtInfo, [1120](#)
  - pGetCallFWInfo, [1120](#)
- voiceGetCallWaitInfo, [1120](#)
  - pAlphaIDInfo, [1121](#)
  - pCCResType, [1121](#)
  - pCCSUPSType, [1121](#)
  - pCallID, [1121](#)
  - pFailCause, [1121](#)
  - pSvcClass, [1121](#)
- voiceGetConfigReq, [1130](#)
  - pAMRStatus, [1131](#)
  - pAirTimer, [1131](#)
  - pAutoAnswer, [1131](#)
  - pNamID, [1131](#)

- pPrefVoicePrivacy, 1131
  - pPrefVoiceSO, 1131
  - pRoamTimer, 1131
  - pTTYMode, 1131
  - pVoiceDomainPref, 1132
- voiceGetConfigResp, 1132
  - pAirTimerCnt, 1133
  - pAutoAnswerStat, 1133
  - pCurAMRConfig, 1134
  - pCurPrefVoiceSO, 1134
  - pCurVoiceDomainPref, 1134
  - pCurVoicePrivacyPref, 1134
  - pCurrTTYMode, 1134
  - pRoamTimerCnt, 1134
- voiceIndicationRegisterInfo, 1134
  - pRegDTMFEvents, 1135
  - pRegVoicePrivacyEvents, 1135
  - pSuppsNotifEvents, 1135
- voiceInfoRec, 1135
  - callID, 1137
  - pCLIRCause, 1137
  - pCallWaitInd, 1137
  - pCalledPartyInfo, 1137
  - pCallerIDInfo, 1137
  - pCallerNameInfo, 1137
  - pCallingPartyInfo, 1137
  - pConnectNumInfo, 1137
  - pDisplInfo, 1137
  - pExtDisplInfo, 1137
  - pExtDispRecInfo, 1137
  - pLineCtrlInfo, 1137
  - pNSSAudioCtrl, 1137
  - pNSSRelease, 1137
  - pRedirNumInfo, 1137
  - pSignalInfo, 1137
- voiceManageCallsReq, 1137
  - pCallID, 1139
  - SUPSType, 1139
- voiceManageCallsResp, 1139
  - pFailCause, 1139
- VoiceNumber
  - unpack\_dms\_GetVoiceNumber\_t, 963
- voiceNumberSize
  - unpack\_dms\_GetVoiceNumber\_t, 964
- voiceOTASPStatusInfo, 1140
  - callID, 1141
  - OTASPStatus, 1141
- voiceOrigUSSDNoWaitInfo, 1139
  - USSInformation, 1140
- voicePrivacy
  - voicePrivacyInfo, 1141
- voicePrivacyInfo, 1141
  - callID, 1141
  - voicePrivacy, 1141
- voiceSUPSInfo, 1155
  - pAlphaIDInfo, 1157
  - pCLIPstatus, 1157
  - pCLIRstatus, 1157
  - pCNAPstatus, 1157
  - pCOLPstatus, 1157
  - pCOLRstatus, 1157
  - pCallBarPasswd, 1157
  - pCallFWNum, 1157
  - pCallFWTimerVal, 1157
  - pCallFwdInfo, 1157
  - pCallID, 1157
  - pDataSrc, 1157
  - pFailCause, 1157
  - pNewPwdData, 1158
  - pReason, 1158
  - pSvcClass, 1158
  - pUSSInfo, 1158
  - SUPSInformation, 1158
- voiceSUPSNotification, 1158
  - callID, 1160
  - notifType, 1160
  - pCUGIndex, 1160
  - pECTNum, 1160
- voiceSetAllCallStatusCbklInfo, 1141
  - arrCallInformation, 1143
  - pArrAlertingPattern, 1143
  - pArrAlertingType, 1143
  - pArrAlphaID, 1143
  - pArrCallEndReason, 1143
  - pArrCalledPartyNum, 1143
  - pArrConnectPartyNum, 1144
  - pArrDiagInfo, 1144
  - pArrRedirPartyNum, 1144
  - pArrRemotePartyName, 1144
  - pArrRemotePartyNum, 1144
  - pArrSvcOption, 1144
- voiceSetCallBarringPwdInfo, 1144
  - newPasswd, 1145
  - newPasswdAgain, 1145
  - oldPasswd, 1145
  - Reason, 1145
- voiceSetCallBarringPwdResp, 1145
  - pAlphaIDInfo, 1146
  - pCCResType, 1146
  - pCCSUPSType, 1146
  - pCallID, 1146
  - pFailCause, 1146
- voiceSetConfigReq, 1146
  - pAirTimerConfig, 1148
  - pAutoAnswer, 1148
  - pPrefVoiceDomain, 1148
  - pPrefVoiceSO, 1148
  - pRoamTimerConfig, 1148
  - pTTYMode, 1148
- voiceSetConfigResp, 1148
  - pAirTimerStatus, 1150
  - pAutoAnsStatus, 1150
  - pPrefVoiceSOStatus, 1150
  - pRoamTimerStatus, 1150
  - pTTYConfigStatus, 1150
  - pVoiceDomainPrefStatus, 1150



- voiceSetPrefPrivacy, 1150
  - privacyPref, 1151
- voiceSetSUPSServiceReq, 1151
  - pCallBarringPasswd, 1153
  - pCallForwardingNumber, 1153
  - pCallFwdTypeAndPlan, 1153
  - pServiceClass, 1153
  - pTimerVal, 1153
  - reason, 1153
  - voiceSvc, 1153
- voiceSetSUPSServiceResp, 1153
  - pAlphaIDInfo, 1154
  - pCCResultType, 1154
  - pCCSUPSType, 1154
  - pCallID, 1154
  - pFailCause, 1154
- voiceStopContDTMFInfo, 1155
  - callID, 1155
- voiceSvc
  - voiceSetSUPSServiceReq, 1153
- VolValue
  - SetAudioVolTLBConfigReq, 773
- Volume
  - GetAudioProfileResp, 259
  - GetAudioVolTLBConfigReq, 260
  - GetM2MAudioProfileResp, 277
  - SetAudioProfileReq, 772
  - SetAudioVolTLBConfigReq, 773
- voteForInit
  - registerRefresh, 737
- WCDMACellInfo
  - lteWcdmaCellInfo, 426
  - nas\_lteWcdmaCellInfo, 486
- WCDMAECIOThresh, 1161
  - pWCDMAECIOThreshList, 1161
  - WCDMAECIOThreshListLen, 1161
- WCDMAECIOThreshListLen
  - nas\_WCDMAECIOThresh, 517
  - WCDMAECIOThresh, 1161
- WCDMAInfoLTENeighborCell, 1161
  - UMTSLTENbrCell, 1162
  - umtsLTENbrCellLen, 1162
  - wcdmaRRCTest, 1162
- WCDMARSSIThresh, 1167
  - pWCDMARSSIThreshList, 1167
  - WCDMARSSIThreshListLen, 1167
- WCDMARSSIThreshListLen
  - nas\_WCDMARSSIThresh, 519
  - WCDMARSSIThresh, 1167
- WCDMASSInfo
  - unpack\_nas\_SLQSNasGetSigInfo\_t, 1014
- WCDMASysInfo, 1167
  - cellId, 1171
  - cellIdValid, 1171
  - hsCallStatus, 1171
  - hsCallStatusValid, 1171
  - hsInd, 1171
  - hsIndValid, 1171
  - lac, 1171
  - lacValid, 1172
  - MCC, 1172
  - MNC, 1172
  - networkIdValid, 1172
  - psc, 1172
  - pscValid, 1172
  - regRejectInfoValid, 1172
  - rejCause, 1172
  - rejectSrvDomain, 1172
  - sysInfoWCDMA, 1172
- WDS\_IsGobiDevice
  - qaGobiApiWds.h, 1732
- WDS\_SRV
  - qaGobiApiCbk.h, 1305
- WDSGetLoopbackData, 1195
  - ByteLoopbackMode, 1196
  - ByteLoopbackMultiplier, 1196
- WDSSWiCurrentChannelRates, 1206
  - current\_channel\_rx\_rate, 1206
  - current\_channel\_tx\_rate, 1206
  - max\_channel\_rx\_rate, 1206
  - max\_channel\_tx\_rate, 1207
- WDSSetLoopbackData, 1204
  - pLoopbackMode, 1206
  - pLoopbackMultiplier, 1206
- WORD
  - SwiDataTypes.h, 1761
- wcdmaAmrStat
  - curAMRConfig, 187
- wcdmaCellInfo, 1160
  - cpich\_ecno, 1161
  - cpich\_rscp, 1161
  - psc, 1161
  - srxlev, 1161
- wcdmaLongMsgDecodingParams, 1162
  - Date, 1164
  - plsUDHPresent, 1164
  - pMessage, 1164
  - pPartNum, 1164
  - pReferenceNum, 1164
  - pScAddr, 1164
  - pScAddrLength, 1164
  - pSenderAddr, 1164
  - pSenderAddrLength, 1164
  - pTextMsg, 1164
  - pTextMsgLength, 1164
  - pTotalNum, 1164
  - Time, 1164
- wcdmaMsgDecodingParams, 1164
  - Date, 1165
  - pMessage, 1165
  - pScAddr, 1165
  - pScAddrLength, 1165
  - pSenderAddr, 1165
  - pSenderAddrLength, 1165
  - pTextMsg, 1165
  - pTextMsgLength, 1166

- Time, 1166
- wcdmaMsgEncodingParams, 1166
  - alphabet, 1166
  - messageSize, 1166
  - pDestAddr, 1166
  - pPDUMessage, 1166
  - pTextMsg, 1166
- wcdmaRRCTest
  - nas\_WCDMAInfoLTENeighborCell, 518
  - WCDMAInfoLTENeighborCell, 1162
- wcdmaUARFCN, 1172
  - status, 1172
  - uarfcn, 1172
- wds.h, 1782
  - PACK\_WDS\_IPV4, 1786
  - PACK\_WDS\_IPV6, 1786
  - pack\_wds\_GetConnectionRate, 1786
  - pack\_wds\_GetDefaultProfile, 1787
  - pack\_wds\_GetDefaultProfileNum, 1787
  - pack\_wds\_GetDormancyState, 1787
  - pack\_wds\_GetLastMobileIPError, 1789
  - pack\_wds\_GetMobileIP, 1789
  - pack\_wds\_GetMobileIPProfile, 1790
  - pack\_wds\_GetPacketStatus, 1790
  - pack\_wds\_GetSessionDuration, 1790
  - pack\_wds\_GetSessionState, 1791
  - pack\_wds\_RMSetTransferStatistics, 1791
  - pack\_wds\_SLQSCreateProfile, 1794
  - pack\_wds\_SLQSDeleteProfile, 1794
  - pack\_wds\_SLQSGet3GPPConfigItem, 1794
  - pack\_wds\_SLQSGetCurrDataSystemStat, 1795
  - pack\_wds\_SLQSGetDUNCallInfo, 1796
  - pack\_wds\_SLQSGetDataBearerTechnology, 1795
  - pack\_wds\_SLQSGetProfileSettings, 1796
  - pack\_wds\_SLQSGetRuntimeSettings, 1796
  - pack\_wds\_SLQSModifyProfile, 1797
  - pack\_wds\_SLQSSetDHCPv4ClientConfig, 1798
  - pack\_wds\_SLQSSet3GPPConfigItem, 1797
  - pack\_wds\_SLQSSetIPFamilyPreference, 1798
  - pack\_wds\_SLQSSetWdsEventCallback, 1798
  - pack\_wds\_SLQSStartDataSession, 1799
  - pack\_wds\_SLQSStopDataSession, 1799
  - pack\_wds\_SLQSWdsSwiPDPRuntimeSettings, 1800
  - pack\_wds\_SetDefaultProfile, 1791
  - pack\_wds\_SetDefaultProfileNum, 1793
  - pack\_wds\_SetMobileIPProfile, 1793
  - unpack\_wds\_GetConnectionRate, 1800
  - unpack\_wds\_GetDefaultProfile, 1800
  - unpack\_wds\_GetDefaultProfileNum, 1801
  - unpack\_wds\_GetDormancyState, 1801
  - unpack\_wds\_GetLastMobileIPError, 1801
  - unpack\_wds\_GetMobileIP, 1802
  - unpack\_wds\_GetMobileIPProfile, 1802
  - unpack\_wds\_GetPacketStatus, 1802
  - unpack\_wds\_GetSessionDuration, 1803
  - unpack\_wds\_GetSessionState, 1803
  - unpack\_wds\_RMSetTransferStatistics, 1803
  - unpack\_wds\_SLQSCreateProfile, 1805
  - unpack\_wds\_SLQSDeleteProfile, 1805
  - unpack\_wds\_SLQSGet3GPPConfigItem, 1805
  - unpack\_wds\_SLQSGetCurrDataSystemStat, 1806
  - unpack\_wds\_SLQSGetDUNCallInfo, 1806
  - unpack\_wds\_SLQSGetDataBearerTechnology, 1806
  - unpack\_wds\_SLQSGetProfileSettings, 1807
  - unpack\_wds\_SLQSGetRuntimeSettings, 1807
  - unpack\_wds\_SLQSModifyProfile, 1807
  - unpack\_wds\_SLQSSetDHCPv4ClientConfig, 1809
  - unpack\_wds\_SLQSSet3GPPConfigItem, 1808
  - unpack\_wds\_SLQSSetIPFamilyPreference, 1808
  - unpack\_wds\_SLQSSetPacketSrvStatusCallback, 1808
  - unpack\_wds\_SLQSSetWdsEventCallback, 1809
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind, 1809
  - unpack\_wds\_SLQSStartDataSession, 1809
  - unpack\_wds\_SLQSStopDataSession, 1811
  - unpack\_wds\_SLQSWdsSwiPDPRuntimeSettings, 1811
  - unpack\_wds\_SetDefaultProfile, 1804
  - unpack\_wds\_SetDefaultProfileNum, 1804
  - unpack\_wds\_SetMobileIPProfile, 1804
  - UnpackQmiProfileInfo, 1786
- wds\_Domain, 1175
  - domainLen, 1175
  - domainName, 1175
- wds\_DomainNameList, 1175
  - domain, 1176
  - numInstances, 1176
- wds\_GPRSQoS, 1176
  - delayClass, 1176
  - meanThroughputClass, 1176
  - peakThroughputClass, 1176
  - precedenceClass, 1177
  - reliabilityClass, 1177
- wds\_IPV6AddressInfo, 1177
  - IPAddressV6, 1177
  - IPV6PrefixLen, 1177
- wds\_IPV6GWAddressInfo, 1177
  - gwAddressV6, 1178
  - gwV6PrefixLen, 1178
- wds\_PCSCFFQDNAddress, 1178
  - fqdnAddr, 1178
  - fqdnLen, 1178
- wds\_PCSCFFQDNAddressList, 1178
  - numInstances, 1180
  - pcsfFQDNAddress, 1180
- wds\_PCSCFIPv4ServerAddressList, 1180
  - numInstances, 1180
  - pcsfIPv4Addr, 1180
- wds\_ProfileIdentifier, 1180
  - profileIndex, 1181
  - profileType, 1181
- wds\_UMTSMInQoS, 1181



- deliveryErrSDU, 1185
- grntDownlinkBitrate, 1185
- grntUplinkBitrate, 1185
- maxDownlinkBitrate, 1185
- maxSDUSize, 1185
- maxUplinkBitrate, 1185
- qosDeliveryOrder, 1185
- resBerRatio, 1185
- sduErrorRatio, 1185
- trafficClass, 1185
- trafficPriority, 1185
- transferDelay, 1185
- wds\_currNetworkInfo, 1172
  - NetworkType, 1175
  - RATMask, 1175
  - SOMask, 1175
- wds\_profileInfo, 1181
  - SlqsProfile3GPP, 1181
  - SlqsProfile3GPP2, 1181
- WdsByteTotals, 1185
  - ByteTotalsElmntsV4, 1186
  - ByteTotalsElmntsV6, 1186
  - pV4sessionId, 1186
  - pV6sessionId, 1186
- WdsByteTotalsElmnts, 1186
  - pRXTotalBytes, 1186
  - pTXTotalBytes, 1187
- WdsClientLeaseChange, 1187
  - pEnableNotification, 1187
- WdsConnectionRate, 1187
  - ConnRateElmntsV4, 1188
  - ConnRateElmntsV6, 1188
  - pV4sessionId, 1188
  - pV6sessionId, 1188
- WdsConnectionRateElmnts, 1188
  - pCurrentChannelRXRate, 1189
  - pCurrentChannelTXRate, 1189
  - pMaxChannelRXRate, 1189
  - pMaxChannelTXRate, 1189
- WdsDHCPv4ClientLeaseInd, 1189
  - pIPv4Addr, 1190
  - pLeaseState, 1190
  - pOptList, 1190
  - pProfileId, 1190
- WdsDHCPv4Config, 1190
  - pHwConfig, 1190
  - pProfileId, 1190
  - pRequestOptionList, 1190
- WdsDHCPv4HWConfig, 1191
  - chaddr, 1192
  - chaddrLen, 1192
  - hwType, 1192
- WdsDHCPv4Option, 1192
  - optCode, 1192
  - optVal, 1192
  - optValLen, 1192
- WdsDHCPv4OptionList, 1193
  - numOpt, 1194
- pOptList, 1194
- WdsDHCPv4ProfileId, 1195
  - profileId, 1195
  - profileType, 1195
- wdsDhcpv4HwConfig, 1191
  - chaddr, 1191
  - chaddrLen, 1191
  - hwType, 1191
- wdsDhcpv4Option, 1192
  - optCode, 1193
  - optVal, 1193
  - optValLen, 1193
- wdsDhcpv4OptionList, 1193
  - numOpt, 1193
  - pOptList, 1193
- wdsDhcpv4ProfileId, 1194
  - profileId, 1194
  - profileType, 1194
- WdsIpAddressInfoReq, 1196
  - ip, 1196
  - pV4sessionId, 1196
  - pV6sessionId, 1196
- WdsPktStatisticsElmnts, 1196
  - pRXDroppedCount, 1198
  - pRXOKBytesLastCall, 1198
  - pRXOkBytesCount, 1198
  - pRXPacketErrors, 1198
  - pRXPacketOverflows, 1198
  - pRXPacketSuccesses, 1199
  - pTXDroppedCount, 1199
  - pTXOKBytesLastCall, 1199
  - pTXOkBytesCount, 1199
  - pTXPacketErrors, 1199
  - pTXPacketOverflows, 1199
  - pTXPacketSuccesses, 1199
- WdsPktStatisticsReq, 1199
  - pStatMask, 1199
- WdsPktStatisticsResp, 1199
  - pV4sessionId, 1200
  - pV6sessionId, 1200
  - PktStatElmntsV4, 1200
  - PktStatElmntsV6, 1200
- WdsProfileParam, 1200
  - SlqsProfile3GPP, 1200
  - SlqsProfile3GPP2, 1200
- WdsRunTimeSettings, 1200
  - rts, 1201
  - v4sessionId, 1201
  - v6sessionId, 1201
- wdsSetEventReportReq, 1201
  - pCurrChannelRateInd, 1204
  - pCurrDataBearerTechInd, 1204
  - pCurrPrefDataSysInd, 1204
  - pDataBearerTechInd, 1204
  - pDataCallStatusChangeInd, 1204
  - pDataSystemStatusChangeInd, 1204
  - pDormancyStatusInd, 1204
  - pEVDOPageMonPerChangeInd, 1204

- pMIPStatusInd, [1204](#)
  - pTransferStatInd, [1204](#)
- Wireless Data Service (WDS), [32](#)
- xAxis
  - sensorData, [760](#)
- xferStatAvail
  - unpack\_wds\_SLQSSetWdsEventCallback\_ind\_t,  
[1086](#)
- xid
  - pack\_qmi\_t, [616](#)
  - unpack\_qmi\_t, [1027](#)
- xtra\_start\_gps\_minutes
  - GPSSStateInfo, [293](#)
- xtra\_start\_gps\_week
  - GPSSStateInfo, [293](#)
- xtra\_valid\_duration\_hours
  - GPSSStateInfo, [293](#)
- yAxis
  - sensorData, [760](#)
- year
  - nas\_timeInfo, [509](#)
  - nas\_UniversalTime, [515](#)
  - timeInfo, [883](#)
  - UniversalTime, [952](#)
- zAxis
  - sensorData, [760](#)