



# IBSTOCK FIRE RATED CONCRETE LINTELS

CLICK TO FIND OUT MORE

**WE ARE**Lintels and more.





We offer a diverse range of building products, solutions and expert technical and design services that enable our customers to create inspirational spaces and places.

Everything we do revolves around our valued customers and we continuously strive to exceed their expectations. We pride ourselves on leading for new, innovative and sustainable products and solutions, both for today and for a new era of building.

WE ARE at the heart of building. WE ARE Ibstock.

















**Bricks and Masonry** 

Facade Systems

Roofing

**Flooring and Lintels** 

Staircases and Lift Shafts

Fencing and Landscaping

**Retaining Walls** 


Rail and Infrastructure



Design and Technical Services

We are committed to providing the best possible design and technical support to our customers. From expert advice to a sector-leading training and CPD provision, Ibstock's range of design and technical services are especially configured to give architects and specifiers the access to the support they need at every stage on their project journey – from concept to build.







## Accreditation built in

Here at Ibstock, we are proud to offer you our new, highly comprehensive and full range of high-quality fire-rated lintels that have been tested to cover all industry specifications and are unique in that they are all fully BSI Kitemarked.

And with the introduction of our latest Extreme range, we are one of the very few companies based in the UK, able to offer you a choice of fire rated lintels, proven by our stringent tests to maintain a 300 minute load bearing capability, when subject to fire conditions.







#### High Fire Rated Lintels


- 90 minute and 120 minute protection.
- Textured finish.
- BSI Kitemarked.
- First-rate structural loadings.
- Supporting Fire Fighters Charity.







### High Fire Rated Lintels



PRODUCT TABLE					
LINTEL REF*	WIDTH (MM)	HEIGHT (MM)	LENGTHS (MM)	FIRE RATING (MINS)	
HIGH FIRE R	ATED (90-120	OMIN)			
HF R15*	140	100	600 - 4200	R90	
HF S15	140	150	600 - 4200	R90	
HF R21	215	140	600 - 4200	R120	
HF R21A*	140	215	600 - 4200	R90	
HF R23	215	215	600 - 4200	R120	



<sup>\*</sup> To be used in correct orientation. Installer to rotate product as per markings shown.

	LINTEL REFERENCE	HF R15	HF S15	HF R21	HF R21A	HF R23
	SECTION PROFILE	140 x 100*	140 x 150	215 x 140	140 x 215	215 x 215
SIZE TO ORDER	CLEAR SPAN (MM)	MAXIMUM SERVICE LOAD IN kN/m (IN ADDITION TO SELF WEIGHT				
600	300	80.70	113.39	175.77	170.94	237.78
750	450	58.60	82.33	127.64	124.12	172.63
900	600	39.87	64.58	100.14	97.37	135.41
1050	750	26.93	53.10	82.34	80.06	111.32
1200	900	19.37	45.06	60.61	67.95	94.46
1350	1050	14.56	39.12	45.66	58.99	82.00
1500	1200	11.33	34.55	35.57	52.10	72.41
1650	1350	9.04	28.00	28.46	46.64	64.81
1800	1500	7.36	22.90	23.24	42.20	56.90
2100	1800	5.13	16.10	16.28	33.35	40.03
2400	2100	3.74	11.88	11.96	24.69	29.58
2700	2400	2.82	9.09	9.10	18.96	22.66
3000	2700	2.18	7.15	7.11	14.97	17.85
3300	3000	1.72	5.74	5.67	12.09	14.36
3600	3300	1.37	4.69	4.60	9.93	11.75
4200	3900	0.90	3.25	3.12	6.98	8.19

<sup>\*</sup> Width x height

Safe working loads indicated are based on the clear span plus 150mm of bearing each end. Our lintels can be cut to length as required.





#### Extreme Fire Rated Lintels

- 300 minute protection.
- Textured Finish.
- BSI Kitemarked.
- Vermiculite fire-resistant coating.
- Dependable and safe, no dangerous or poisonous omissions.
- First-rate structural loadings.
- Supporting Fire Fighters Charity.









#### Extreme Fire Rated Lintels



PRODUCT TABLE						
LINTEL REF	WIDTH (MM)	HEIGHT (MM)	LENGTHS (MM)	FIRE RATING (MINS)		
EXTREME FIRE RATED (300MIN)						
XF R23	215	215	600 - 3600	R300		
XF R24	105	140	600 - 3600	R300		
XF R25	105	215	600 - 3600	R300		
XF R26	140	215	600 - 3600	R300		
XF R27	140	140	600 - 3600	R300		



LOAD-SPAN TABLE (300 minute fire rating)						
	LINTEL REFERENCE	XF R23	XF R24	XF R25	XF R26	XF R27
	SECTION PROFILE	215 x 215 *	105 x 140 *	105 x 215 *	140 x 215 *	140 x 140 *
SIZE TO ORDER	CLEAR SPAN (MM)	MAXIMUM SERVICE LOAD IN kN/m (IN ADDITION TO SELF WEIGHT)				
900	600	97.87	28.90	49.99	76.38	47.43
1050	750	80.48	23.76	41.11	62.81	37.50
1200	900	68.30	18.68	34.89	53.31	27.00
1350	1050	59.30	14.07	30.30	46.29	20.34
1500	1200	52.37	10.97	24.11	37.70	15.84
1650	1350	45.83	8.77	19.32	30.20	12.67
1800	1500	37.51	7.17	15.8	24.71	10.35
2100	1800	26.40	5.02	11.11	17.38	7.24
2400	2100	19.51	3.69	8.20	12.83	5.32
2700	2400	14.95	2.81	6.28	9.82	4.04
3000	2700	11.77	2.20	4.94	7.73	3.16
3300	3000	9.47	1.75	3.97	6.21	2.51
3600	3300	7.76	1.42	3.24	5.08	2.03



<sup>\*</sup> Width x height (the width includes the fire proof coating)
Safe working loads indicated are based on the clear span plus 150mm of bearing each end.
The Extreme Fire Rated Lintels cannot be cut.

<sup>\*</sup> To be used in correct orientation. Installer to rotate product as per markings shown





For orders and enquiries, please call us on **0333 999 2220** or email **supreme.sales@ibstock.co.uk** 

- Technical experience to provide help and support when selecting products.
- Robust testing to ensure products fit for purpose.
- Conformance with the NBS BIM Object Standard.
- Continuous innovation of products and processes to enable innovative designs.


www.ibstock.co.uk





**Information at:** <a href="www.firefighterscharity.org.uk">www.firefighterscharity.org.uk</a> **Donate at:** <a href="www.firefighterscharity.org.uk/donate">www.firefighterscharity.org.uk/donate</a>

#### Our full range









**HEAD OFFICE** 

Ibstock plc, Leicester Road, Ibstock, Leicestershire LE67 6HS

T: 0333 999 2220 E: beamsales@supremeconcrete.co.uk

www.ibstock.co.uk



ADDRESS CLIMATE CHANGE IMPROVE LIVES MANUFACTURE MATERIALS FOR LIFE

