
WORKING CATALOGUE 2026



FLOS

Architectural

FLOS

WORKING CATALOGUE 2026

ENGLISH / ESPAÑOL

NEW This marker appears alongside Product News / Este marcador aparece en las novedades de Producto

INDEX

LIGHT STRUCTURES

- **12** – The Glowing Track 
- **50** – My Circuit 
- **76** – Belt 
- **80** – Infra-Structure 
- **110** – Zero Track Pro 
- **170** – Zero Track 
- **184** – The Micro Running Magnet 
- **206** – The Running Magnet 
- **250** – The Tracking Magnet 
- **286** – The Tracking Power EVO 
- **306** – The Fast Track 
- **316** – In-Finity 
- **330** – Light Cut Mini 

HIGH COMFORT

- **338** – Gustave 
- **342** – EMI 
- **348** – Oblique 
- **350** – Oblique Floor 
- **352** – Workmates 
- **418** – Light Shadow Mini 
- **434** – Light Shadow 
- **520** – Light Shadow Pro / Light Shadow Dots 
- **558** – Eclectic
- **586** – Circle of Light 

INDEX

DOWNLIGHTS

592 – Kap



656 – Bon Jour



660 – UT Downlight



668 – Light Supply



680 – Johnny



SPOTLIGHTS

694 – Light Shadow Spot



• **704** – My Spot



720 – Find Me



726 – UT Spot&Pro



742 – Wan Spot



INDEX

CEILING / WALL

446 – C1



756 – UT Pro Surface



760 – Kap Surface /
Kap Suspension



770 – Super Line /
Super Line Pro



776 – Light Bell



780 – Fort Knox Wall /
Fort Knox Wall Mini



782 – Thin LED



784 – G-O



786 – TheBlockofLight



SOFT – 3D

815 – Juncos



817 – Soft Spun



817 – Abajourd'Hui



INDEX

SOFT – IN

819 – G-O IN



820 – Teardrop



820 – USO



821 – USO Cove Lighting



823 – Round Light



824 – Square Light



824 – Vertical Light



788 – TRACKS

794 – DRIVERS

804 – TECHNICAL INFORMATION

830 – QUICK SEARCH OF PRODUCT

866 – DISTRIBUTION

FLOS
Architectural

	Glass	White	Matte White	Textured White	Off White	Black	Matte Black	Anodized Black	Grey	Anodice Grey	Polished Silver	Anodized Silver	Polished Aluminium	Brushed Aluminium	Chrome	Smoke Glass	Stainless Steel	Steel	Concrete	Anthracite	Salvia
THE GLOWING TRACK		•				•															
MY CIRCUIT		•																			
BELT						•															
INFRA-STRUCTURE		•				•						•			•						
ZERO TRACK PRO		•				•															
ZERO TRACK		•				•					•				•						
THE MICRO RUNNING MAGNET		•				•															
THE RUNNING MAGNET		•				•					•	•									
THE TRACKING MAGNET		•				•					•										
THE TRACKING POWER EVO		•				•						•								•	
THE FAST TRACK		•				•															
IN-FINITY		•				•				•											
LIGHT CUT MINI		•				•															
WORKMATES		•				•						•									
GUSTAVE				•							•									•	
EMI					•																
OBLIQUE / OBLIQUE FLOOR				•					•											•	•
LIGHT SHADOW MINI		•				•												•			
LIGHT SHADOW		•				•												•			
LIGHT SHADOW PRO&DOTS		•				•												•			
ECLECTIC		•				•															
CIRCLE OF LIGHT						•															
KAP		•				•															
BON JOUR		•				•															
UT DOWNLIGHT		•				•															
LIGHT SUPPLY		•				•															
JOHNNY		•				•													•		
LIGHT SHADOW SPOT		•				•															
MY SPOT		•				•															
FIND ME		•				•					•										
UT SPOT		•				•															
WAN SPOT		•				•					•										
C1		•																		•	
UT PRO SURFACE		•				•															
KAP SURFACE		•				•							•								
SUPER LINE		•				•			•												
LIGHT BELL	•	•					•				•		•						•		
FORT KNOX WALL		•				•					•										
THIN LED		•									•		•								
G-O		•					•				•						•				
THEBLOCKOFLIGHT			•				•		•												

FLOS
Soft Architecture

JUNCOS		•				•								•							







	Deep Brown	Dark Brown	Laquered Brown	Anodized Bronze	Bronze	Gold	Matte Gold	Galvanic Copper	Rust	Red Glass	Deep Red	Deep Green	Deep Blue	Green	Laquered Green	Brushed Copper	Brushed Steel	Brushed Bronze	Natural Leather	Green Leather	Grey Olive	Copper Brown
THE GLOWING TRACK																•	•					
MY CIRCUIT																						
BELT																		•	•	•	•	
INFRA-STRUCTURE						•				•						•	•	•				
ZERO TRACK PRO																•	•	•				
ZERO TRACK	•			•																		
THE MICRO RUNNING MAGNET																						
THE RUNNING MAGNET																•	•	•				
THE TRACKING MAGNET																•	•	•				
THE TRACKING POWER EVO																						
THE FAST TRACK																						
IN-FINITY																						
LIGHT CUT MINI																						
WORKMATES																						
GUSTAVE			•												•							
EMI											•	•	•									
OBLIQUE / OBLIQUE FLOOR	•								•													
LIGHT SHADOW MINI					•																	
LIGHT SHADOW					•											•	•	•				
LIGHT SHADOW PRO&DOTS					•											•	•	•				
ECLECTIC																						
CIRCLE OF LIGHT																						
KAP							•															
BON JOUR																						
UT DOWNLIGHT																						
LIGHT SUPPLY																						
JOHNNY																						
LIGHT SHADOW SPOT																•	•	•				
MY SPOT																•	•	•				
FIND ME																						
UT SPOT																						
WAN SPOT														•								
C1																•	•	•				
UT PRO SURFACE																						
KAP SURFACE	•						•															
SUPER LINE																						
LIGHT BELL						•		•														
FORT KNOX WALL																						
THIN LED				•																		
G-O					•																	
THEBLOCKOFLIGHT																						

JUNCOS																							

LIGHT STRUCTURES

The Glowing Track, My Circuit, Belt, Infra-Structure, Zero Track PRO, Zero Track, The Micro Running Magnet, The Running Magnet, The Tracking Magnet, The Tracking Power EVO, The Fast Track, In-Finity, Light Cut Mini.

LIGHT STRUCTURES OVERVIEW



		MY CIRCUIT	THE GLOWING TRACK		ZERO TRACK PRO			ZERO TRACK	THE MICRO RUNNING MAGNET	
										
PHYSICAL CHARACTERISTICS	**MOUNTING**	SURFACE	SURFACE	SUSPENSION	RECESSED	SURFACE	SUSPENSION Down Up & Down	SURFACE	RECESSED	SURFACE
	COLORS	☐	☐ ■		☐ ■			☐	☐ ■	
	VOLTAGE / TRACK ADAPTER	48 Vdc In-Track	24 Vdc In-Track		24 Vdc In-Track			24 Vdc In-Track	24 Vdc In-Track	
	INNER GAP (mm)	-	11,5		11,5			8	5	
	OUTER GAP (mm)	-	47	47	-	19	20	17	-	9
	RECESSED DEPTH (mm)	-	-	-	-	-	-	-	17	-
	HEIGHT (mm)	27	50 75	47	23 / 10 18	10,5	25,2 38,9	7	14,5 / 17	14
	LENGTH (mm)	8000 / 15000 / 20000	600 / 1200 / 1800 / 2200		1000 / 1500 / 2000 / 2500 / 3000			1000 / 2000 / 3000	1000 / 2000 / 3000	
CONTROL CHARACTERISTICS	**PROFILE EMISSION**	✗	✓		✓ Upper integrated			✗	✗	
	NON DIMMABLE	✓	✓		✓			✓	✓	
	DALI	✗	✓		✓			✗	✓ [1]	
	CASAMBI	✓	✓		✓			✓	✓	
	1 - 10V	✓ [1]	✗		✓ [1]			✗	✓ [1]	
	PUSH	✗	✗		✗			✗	✓ [1]	
	MAINS DIMMING	✗	✗		✗			✗	✗	
	UP&DOWN (Indep)	–	–		–			–	–	
COMPATIBLE LIGHT MODULES	**ACCENT LIGHTING**	 My Circuit Spot Ø25 · My Circuit Spot Ø35 · My Circuit Light Shadow Spot Ø30 · My Circuit Light Shadow Spot Ø45	 Find Me 0 1 / 2 / 3 · Find Me 1 1 / 2 / 3 · Find Me 2 1 / 2 / 3 · Multi Spot Mini 1 / 2 · Light Shadow Spot 30 1 / 2 · Light Shadow Spot 45 1 / 2 · Find Me 1 Suspension 2 / 3 · Atom 90 1 / 2 / 3 · Atom 120 1 / 2 / 3 · My Spot Ø25 Short / Long 2 · My Spot Ø35 Short / Long 2				 Nano Spot · Light Shadow Spot · Micro Spot · Spot · Find Me 0 · Find Me 1	
	DIFFUSED LIGHTING	 My Circuit Disc · My Circuit Dome · My Circuit Sphere · My Circuit Lines	–		 Light Stripe 600 / 900 / 1200 * · Magic Stick * · Atom 200 · Magic Stick Asymmetric *				 Light Stripe Diffused · Light Stripe Wall-Washer	

[1] The Glowing Track | [2] Zero Track Pro | [3] Zero Track

* Only for Zero Track Pro

✓ [1] Broadcast ✓ [2] On Board Dimmer ✓ [3] Non Dimmable ✓ [4] Only Remote Drivers ✓ [5] DALI

LIGHT STRUCTURES OVERVIEW

THE RUNNING MAGNET			THE TRACKING MAGNET			INFRA_ STRUCTURE	THE TRACKING POWER EVO	THE FAST TRACK	
									
RECESSED	SURFACE	SUSPENSION Down Up & Down	RECESSED	SURFACE SUSPENSION Down	SUSPENSION Up & Down	SURFACE & SUSPENSION	RECESSED	RECESSED	SURFACE
									
24 Vdc In-Track			48 Vdc In-Track			48 Vdc In-Track	220-240V In-Track	48 Vdc In-Track	
35			15			-	18,5	35	
-	41		-	25		-	-	-	49
73,5	-	-	31,5	-	-	-	27	73,5	-
73 / 86	100	100	31 / 45	46	52	100 / 300 / 400 / 700	42,8	73 / 86	92
1000 / 1500 / 2000 / 2500 / 3000			1000 / 1500 / 2000 / 2500 / 3000			1100 / 1600	1000 / 2000 / 3000	1000 / 1500 / 2000 / 3000	
✓ Upper integrated			✓ Upper integrated			✓ Upper & direct by light modules	✗	✗	
✓			✓ [2]			✓ [2]	✓ [2 / 3 / 5]	✗	
✓			✓			✓	✗	✗	
✓			✓			✓	✗	✓	
✗			✓			✓	✗	✗	
✗			✗			✗	✗	✗	
✗			✗			✗	✗	✗	
✓			✓ [4]			✓	–	–	
 Light Shadow Spot 30	 Light Shadow Spot 45	 Multi Spot 4	 Spot 50	 Spot 90	 Spot 120	 Spot 150	 UT Pro 150 [2]	 Spot 100	
 Find Me 1 Suspension	 Spot Module	 Light Shadow	 Light Shadow Spot 30	 Light Shadow Spot 45	 Light Shadow Spot 60	 Anthony Spot Track*	 Multi Spot Mini	 UT Pro 175 [2]	 Spot 150
	 Spot 120	 Light Shadow Wall-Washer							
	 Anthony Spot Track								
			* Only for The Tracking Magnet						
 Light Stripe	 Mini Glo-Ball	 Workmates	 Light Stripe	 Wallee		 Suspension Panel 600	 UT Pro Wall-Washer [3]	–	
 String Light Ball	 String Light Cone	Mini Glo-Ball Suspension				 Suspension Glass Downlight 110			
						 Light Tube Direct / Indirect / Blind	 Workmates [3 / 5]		

NEW


THE GLOWING TRACK

DESIGNED BY FLOS ARCHITECTURAL

SURFACE
REMOTE DRIVER

SURFACE
INTEGRATED DRIVER

SUSPENSION



White
Blanco



Black
Negro



Brushed Steel
Acero Cepillado



Brushed Bronze
Bronce Cepillado



NEW

Description
Modular and versatile lighting system that combines innovation, high performance, and sophisticated design in a single solution. It provides enveloping, homogeneous, and balanced ambient light that integrates naturally into any space.

Models
Available in four lengths (*600 mm, 1200 mm, 1800 mm, and 2400 mm) with a diameter of only 47 mm. The Glowing Track comes in suspended, surface (with or without driver), and vertical versions, adapting to all types of architectural projects.
Each model offers three configurations:
- Light + Track: Creates a warm and enveloping atmosphere, with the option to add modules for directed or accent lighting.
- Light 360º: Provides uniform coverage without the need for additional tracks.
- Only Track (Blind): For minimalist designs, prioritizing track functionality without side lighting.
**Available only in The Glowing Track 360º Surface Remote Driver, with Casambi control.*

Optical System
The Light + Track and 360º versions feature an optimized methacrylate diffuser, ensuring uniform light and reducing glare while softening shadows. A wide range of spotlights and accent modules is also available to meet specific project needs.

Power Units
Power units are supplied separately, except for the surface version, which offers the choice of integrated or remote driver. A 1200 mm surface model with integrated Plug & Play driver is also available.

Control System
Compatible with Casambi and DALI2, providing maximum flexibility in lighting management. Profiles can be independently controlled, managing each side separately, as well as modules installed on the track.

Connectivity
Profiles are designed with a precise and secure mechanical connector assembly system, ensuring versatile, scalable installations with a flawless finish without compromising aesthetics.

Standards and Quality Marks
Luminaire compliant with European Standard EN60598-1 and subsequent parts.

Before placing your order, consult product details on the Flos professional website, technical datasheet, and installation instructions to obtain complete information that may not be included in this catalog but is relevant to your specific project or installation.

Descripción
Sistema de iluminación modular y versátil que combina innovación, alto rendimiento y diseño sofisticado en una solución única. Ofrece una luz ambiental envolvente, homogénea y equilibrada, que se integra de forma natural en cualquier espacio.

Modelos
Disponible en cuatro longitudes (*600 mm, 1200 mm, 1800 mm y 2400 mm) y con un diámetro de solo 47 mm. The Glowing Track se presenta en versiones suspendida, de superficie (con o sin driver) y vertical, adaptándose a todo tipo de proyectos arquitectónicos.
Cada modelo ofrece tres configuraciones:
- Light + Track: Genera una atmósfera cálida y envolvente, con la opción de añadir módulos para una iluminación dirigida o de acento.
- Light 360º: Aporta una cobertura uniforme, sin necesidad de carriles adicionales.
- Only Track (Blind): Para diseños minimalistas, priorizando la funcionalidad del carril sin iluminación lateral.
**Disponible solo en The Glowing Track 360º Surface Remote Driver, con control Casambi.*

Sistema Óptico
Las versiones Light + Track y 360º incorporan un difusor de metacrilato optimizado, que garantiza una luz uniforme y reduce el deslumbramiento, suavizando las sombras. Además, se ofrece una amplia gama de proyectores y módulos de acento para responder a las necesidades específicas de cada proyecto.

Unidades de Alimentación
Los equipos de alimentación se suministran por separado, excepto en la versión de superficie, que ofrece la posibilidad de elegir entre controlador integrado o remoto. Además, se dispone de un modelo de superficie de 1200 mm con driver integrado Plug & Play.

Sistema de Control
Compatible con Casambi y DALI2, ofreciendo máxima flexibilidad en la gestión de la iluminación. Gracias a las opciones de control, los perfiles se pueden regular de forma independiente, gestionando por separado cada lado, así como los módulos instalados en el carril.

Conectividad
Perfiles diseñados con un sistema de ensamblaje de conectores mecánicos preciso y seguro, que asegura instalaciones versátiles, escalables y con un acabado impecable sin comprometer la estética.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play

NEW

THE GLOWING TRACK

DESIGNED BY FLOS ARCHITECTURAL

PROFILES

THE GLOWING TRACK



LIGHT SOURCE
TOP LED
20,7W/m
2054 lm/m
2200K/CRI 90
2354 lm/m
2700K/CRI 90
2474 lm/m
3000K/CRI 90

THE GLOWING TRACK 360



LIGHT SOURCE
TOP LED
20,7W/m
2054 lm/m
2200K/CRI 90
2354 lm/m
2700K/CRI 90
2474 lm/m
3000K/CRI 90

THE GLOWING TRACK BLIND



LIGHTING MODULES

MULTI SPOT MINI



LIGHT SOURCE
POWER LED
6,1W
636 lm
2700K/CRI 90
672 lm
3000K/CRI 90

FIND ME 0



LIGHT SOURCE
POWER LED
3,5W
300 lm
2700K/CRI 90
325 lm
3000K/CRI 90

FIND ME 1



LIGHT SOURCE
POWER LED
5,5W
450 lm
2700K/CRI 90
485 lm
3000K/CRI 90

FIND ME 2



LIGHT SOURCE
POWER LED
10,5W
650 lm
2700K/CRI 90
700 lm
3000K/CRI 90

LIGHT SHADOW SPOT 30



LIGHT SOURCE
POWER LED
4,7W
298 lm
2700K/CRI 90
318 lm
3000K/CRI 90

LIGHT SHADOW SPOT 45



LIGHT SOURCE
LED ARRAY
11W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

ATOM 90



LIGHT SOURCE
POWER LED
5,5W
450 lm
2700K/CRI 90
485 lm
3000K/CRI 90

ATOM 120



LIGHT SOURCE
POWER LED
8W
635 lm
2700K/CRI 90
680 lm
3000K/CRI 90

NEW

Multi Spot Mini

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Find Me

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Light Shadow Spot

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Atom

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



NEW

HOW TO ORDER

1 CHOOSE YOUR PROFILE & LENGTH

2 COMPLETE WITH MOUNTING ACCESSORIES

SUSPENSION PROFILES

The Glowing Track Suspension



L: 1,2 / 1,8 / 2,2 m

Suspension

Linear Joint



Corner Joint 2



Corner Joint 3



Corner Joint 4



The Glowing Track Vertical



L: 1,2 / 1,8 / 2,2 m

Vertical

Corner Joint 2



SURFACE PROFILES

The Glowing Track Surface Remote Driver



L: 0,6 / 1,2 / 1,8 / 2,2 m

Surface Remote Driver

Linear Joint



Corner Joint 2



Corner Joint 3



Corner Joint 4



The Glowing Track Surface Integrated Driver



L: 1,2 / 1,8 / 2,2 m

Surface Integrated Driver

Linear Joint



Corner Joint 2



Corner Joint 3



Corner Joint 4



Fixed ceiling kit



NEW

3 SELECT POWER SUPPLY

Suspension



Remote Power Supply Kit



Surface Power Supply Kit



Recessed Power Supply Kit

Surface Remote Driver & Vertical
Remote Installation Driver



60W - 24V



120W - 24V

Surface Driver Integrated
Power Supply Included

4 SELECT A LIGHT MODULE AND CONTROL OPTION

No DIM / DALI

Multi Spot Mini



S/M/F

Light Shadow Spot 30



S/M/F/WF

Light Shadow Spot 45



S/M/F

No DIM / DALI / Casambi

Find Me 0



S/M

Find Me 1



S/M

Find Me 2



S/M/F

Atom 90



Atom 120




S/M

The Glowing Track Suspension

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90
L: 1800 mm - 37,2W - 3696 lm - 2200K/CRI 90 / 4236 lm - 2700K/CRI 90 / 4452 lm - 3000K/CRI 90
L: 2400 mm - 49,6W - 4928 lm - 2200K/CRI 90 / 5648 lm - 2700K/CRI 90 / 5936 lm - 3000K/CRI 90





GWT 850°

IP 20

LED INCL

1 - 100%

Suspended lighting system that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included (Accessory kit for remote or surface driver).
Available power on the track:
1200mm / 1800mm: 78W
2400mm: 70W


Sistema de iluminación suspendido que combina iluminación ambiental con un carril que permite la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver no incluido (kit de accesorios para driver remoto o de superficie).
Potencia disponible en el carril:
1200mm / 1800mm: 78W
2400mm: 70W

2200K

L: 1200 mm

Dali
- 05.4600.40.DA
- 05.4600.14.DA
- 05.4600.ER.DA
- 05.4600.ES.DA

Casambi
- 05.4600.40.CB
- 05.4600.14.CB
- 05.4600.ER.CB
- 05.4600.ES.CB




Luminous flux luminaire
1523 lm

L: 1800 mm

Dali
- 05.4602.40.DA
- 05.4602.14.DA
- 05.4602.ER.DA
- 05.4602.ES.DA

Casambi
- 05.4602.40.CB
- 05.4602.14.CB
- 05.4602.ER.CB
- 05.4602.ES.CB




Luminous flux luminaire
2285 lm

L: 2400 mm

Dali
- 05.4604.40.DA
- 05.4604.14.DA
- 05.4604.ER.DA
- 05.4604.ES.DA

Casambi
- 05.4604.40.CB
- 05.4604.14.CB
- 05.4604.ER.CB
- 05.4604.ES.CB




Luminous flux luminaire
3047 lm

2700K

L: 1200 mm

Dali
- 05.4500.40.DA
- 05.4500.14.DA
- 05.4500.ER.DA
- 05.4500.ES.DA

Casambi
- 05.4500.40.CB
- 05.4500.14.CB
- 05.4500.ER.CB
- 05.4500.ES.CB




Luminous flux luminaire
1746 lm

L: 1800 mm

Dali
- 05.4502.40.DA
- 05.4502.14.DA
- 05.4502.ER.DA
- 05.4502.ES.DA

Casambi
- 05.4502.40.CB
- 05.4502.14.CB
- 05.4502.ER.CB
- 05.4502.ES.CB




Luminous flux luminaire
2619 lm

L: 2400 mm

Dali
- 05.4504.40.DA
- 05.4504.14.DA
- 05.4504.ER.DA
- 05.4504.ES.DA

Casambi
- 05.4504.40.CB
- 05.4504.14.CB
- 05.4504.ER.CB
- 05.4504.ES.CB




Luminous flux luminaire
3492 lm

3000K

L: 1200 mm

Dali
- 05.4501.40.DA
- 05.4501.14.DA
- 05.4501.ER.DA
- 05.4501.ES.DA

Casambi
- 05.4501.40.CB
- 05.4501.14.CB
- 05.4501.ER.CB
- 05.4501.ES.CB




Luminous flux luminaire
1834 lm

L: 1800 mm

Dali
- 05.4503.40.DA
- 05.4503.14.DA
- 05.4503.ER.DA
- 05.4503.ES.DA

Casambi
- 05.4503.40.CB
- 05.4503.14.CB
- 05.4503.ER.CB
- 05.4503.ES.CB




Luminous flux luminaire
2752 lm

3000K

L: 2400 mm

Dali
- 05.4505.40.DA
- 05.4505.14.DA
- 05.4505.ER.DA
- 05.4505.ES.DA

Casambi
- 05.4505.40.CB
- 05.4505.14.CB
- 05.4505.ER.CB
- 05.4505.ES.CB




Luminous flux luminaire
3670 lm

NEW

The Glowing Track 360 Suspension

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90
L: 1800 mm - 37,2W - 3696 lm - 2200K/CRI 90 / 4236 lm - 2700K/CRI 90 / 4452 lm - 3000K/CRI 90
L: 2400 mm - 49,6W - 4928 lm - 2200K/CRI 90 / 5648 lm - 2700K/CRI 90 / 5936 lm - 3000K/CRI 90






GWT 850° | IP 20 | LED INCL | 1 - 100%

360º suspended ambient lighting system that provides uniform light distribution. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included (Accessory kit for remote or surface driver).

Sistema de iluminación ambiental suspendido 360º que proporciona una distribución uniforme de la luz. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver no incluido (kit de accesorios para driver remoto o de superficie).


2200K

L: 1200 mm
Dali
05.4650.40.DA
05.4650.14.DA
05.4650.ER.DA
05.4650.ES.DA
Casambi
05.4650.40.CB
05.4650.14.CB
05.4650.ER.CB
05.4650.ES.CB




Luminous flux luminaire
1768 lm

L: 1800 mm
Dali
05.4652.40.DA
05.4652.14.DA
05.4652.ER.DA
05.4652.ES.DA
Casambi
05.4652.40.CB
05.4652.14.CB
05.4652.ER.CB
05.4652.ES.CB



Luminous flux luminaire
2652 lm


L: 2400 mm
Dali
05.4654.40.DA
05.4654.14.DA
05.4654.ER.DA
05.4654.ES.DA
Casambi
05.4654.40.CB
05.4654.14.CB
05.4654.ER.CB
05.4654.ES.CB



Luminous flux luminaire
3536 lm


2700K

L: 1200 mm
Dali
05.4550.40.DA
05.4550.14.DA
05.4550.ER.DA
05.4550.ES.DA
Casambi
05.4550.40.CB
05.4550.14.CB
05.4550.ER.CB
05.4550.ES.CB




Luminous flux luminaire
2026 lm

L: 1800 mm
Dali
05.4552.40.DA
05.4552.14.DA
05.4552.ER.DA
05.4552.ES.DA
Casambi
05.4552.40.CB
05.4552.14.CB
05.4552.ER.CB
05.4552.ES.CB



Luminous flux luminaire
3040 lm


L: 2400 mm
Dali
05.4554.40.DA
05.4554.14.DA
05.4554.ER.DA
05.4554.ES.DA
Casambi
05.4554.40.CB
05.4554.14.CB
05.4554.ER.CB
05.4554.ES.CB



Luminous flux luminaire
4053 lm


3000K

L: 1200 mm
Dali
05.4551.40.DA
05.4551.14.DA
05.4551.ER.DA
05.4551.ES.DA
Casambi
05.4551.40.CB
05.4551.14.CB
05.4551.ER.CB
05.4551.ES.CB



Luminous flux luminaire
2130 lm


L: 1800 mm
Dali
05.4553.40.DA
05.4553.14.DA
05.4553.ER.DA
05.4553.ES.DA
Casambi
05.4553.40.CB
05.4553.14.CB
05.4553.ER.CB
05.4553.ES.CB



Luminous flux luminaire
3195 lm

3000K


L: 2400 mm
Dali
05.4555.40.DA
05.4555.14.DA
05.4555.ER.DA
05.4555.ES.DA
Casambi
05.4555.40.CB
05.4555.14.CB
05.4555.ER.CB
05.4555.ES.CB




Luminous flux luminaire
4260 lm

The Glowing Track Blind Suspension







Suspended electrified track designed for maximum versatility, allowing the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included (Accessory kit for remote or surface driver).

Carril electrificado suspendido diseñado para ofrecer la máxima versatilidad, permitiendo la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver no incluido (kit de accesorios para driver remoto o de superficie).

L: 1200 mm

Dimmable

- 06.2660.40
- 06.2660.14
- 06.2660.ER
- 06.2660.ES

Non Dimmable

- 06.2661.40
- 06.2661.14
- 06.2661.ER
- 06.2661.ES

L: 1800 mm

Dimmable

- 06.2662.40
- 06.2662.14
- 06.2662.ER
- 06.2662.ES

Non Dimmable

- 06.2663.40
- 06.2663.14
- 06.2663.ER
- 06.2663.ES

L: 2400 mm

Dimmable

- 06.2664.40
- 06.2664.14
- 06.2664.ER
- 06.2664.ES

Non Dimmable

- 06.2665.40
- 06.2665.14
- 06.2665.ER
- 06.2665.ES

NEW


SUSPENSION INSTALLATION


Accessories / Accesorios

Remote Power Supply Kit / Kit de fuente de alimentación en remoto

Accessory kit for remote driver.
Driver Included.

Kit accesorio para driver remoto.
Driver incluido.






120W	150W
06.0501.40	06.0508.40
06.0501.14	06.0508.14
06.0501.ER	06.0508.ER
06.0501.ES	06.0508.ES

Surface Power Supply Kit / Kit de fuente de alimentación en superficie

Accessory kit for surface driver.
Driver Included. 150W.

Kit de accesorios para driver en superficie. Driver incluido. 150W.





L: 500 mm	L: 700 mm	L: 900 mm
06.0502.40	06.0503.40	06.0504.40
06.0502.14	06.0503.14	06.0504.14
06.0502.ER	06.0503.ER	06.0504.ER
06.0502.ES	06.0503.ES	06.0504.ES

Recessed Power Supply Kit / Kit de fuente de alimentación empotrable

Accessory kit for recessed driver.
Driver Included. 150W.

Kit de accesorios para driver empotrable. Driver incluido. 150W.





L: 500 mm	L: 700 mm	L: 900 mm
06.0505.40	06.0506.40	06.0507.40
06.0505.14	06.0506.14	06.0507.14
06.0505.ER	06.0506.ER	06.0507.ER
06.0505.ES	06.0506.ES	06.0507.ES

White
Blanco

Black
Negro


Brushed Steel
Acero Cepillado

Brushed Bronze
Bronce Cepillado

Remote



Surface




Recessed




NEW

THE GLOWING TRACK — PROFILES





SUSPENSION INSTALLATION



SURFACE REMOTE DRIVER INSTALLATION



Accessories / Accesorios

Linear Joint for Suspension Linear connection used to join components in a straight line in suspended systems.	**Unión Lineal para Suspensión** Conexión lineal utilizada para unir componentes en línea recta en sistemas de suspensión.			08.1213.40 08.1213.14 08.1213.ER 08.1213.ES
Linear Joint for Surface Mounting Linear connection used to join components in a straight line in surface-mounted installations.	**Unión Lineal para Superficie** Conexión lineal utilizada para unir componentes en línea recta en instalaciones de superficie.			08.1205.40 08.1205.14 08.1205.ER 08.1205.ES
Corner Joint 2 90° corner connector used to join components in the horizontal and vertical plane.	**Unión de Esquina 2** Conector de esquina a 90° utilizado para unir componentes en plano horizontal y vertical.			08.1206.40 08.1206.14 08.1206.ER 08.1206.ES
Corner Joint 3 Connector used to join three components at right angles	**Unión de Esquina 3** Conector utilizado para unir tres componentes en ángulo recto.			08.1207.40 08.1207.14 08.1207.ER 08.1207.ES
Corner Joint 4 Connector used to join four components at right angles.	**Unión de Esquina 4** Conector utilizado para unir cuatro componentes en ángulo recto.			08.1208.40 08.1208.14 08.1208.ER 08.1208.ES
Ceiling Fixing Kit	Kit de sujeción a techo.			08.0615.00


Profile (mm)	Fixation points	Ceiling Kit to order
600	2	1
1200	3	2
1800	4	2
2400	4	2

NEW

The Glowing Track Surface Remote Driver

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90
L: 1800 mm - 37,2W - 3696 lm - 2200K/CRI 90 / 4236 lm - 2700K/CRI 90 / 4452 lm - 3000K/CRI 90
L: 2400 mm - 49,6W - 4928 lm - 2200K/CRI 90 / 5648 lm - 2700K/CRI 90 / 5936 lm - 3000K/CRI 90





GWT 850° | IP 20 | LED INCL | 1 - 100%

Surface lighting system that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included.
Available power on the track:
1200mm / 1800mm: 78W
2400mm: 70W

Sistema de iluminación de superficie que combina iluminación ambiental con un carril que permite la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver no incluido.
Potencia disponible en el carril:
1200mm / 1800mm: 78W
2400mm: 70W

Recommended power supply / Equipo recomendado*:

	120W
Non Dimmable 24V	60.9777A


* Refer to the Drivers chapter / Ver capítulo Drivers

2200K

L: 1200 mm

Dali
- 05.4620.40.DA
- 05.4620.14.DA
- 05.4620.ER.DA
- 05.4620.ES.DA

Casambi
- 05.4620.40.CB
- 05.4620.14.CB
- 05.4620.ER.CB
- 05.4620.ES.CB




Luminous flux luminaire
1523 lm

L: 1800 mm

Dali
- 05.4622.40.DA
- 05.4622.14.DA
- 05.4622.ER.DA
- 05.4622.ES.DA

Casambi
- 05.4622.40.CB
- 05.4622.14.CB
- 05.4622.ER.CB
- 05.4622.ES.CB




Luminous flux luminaire
2285 lm

L: 2400 mm

Dali
- 05.4624.40.DA
- 05.4624.14.DA
- 05.4624.ER.DA
- 05.4624.ES.DA

Casambi
- 05.4624.40.CB
- 05.4624.14.CB
- 05.4624.ER.CB
- 05.4624.ES.CB




Luminous flux luminaire
3047 lm

2700K

L: 1200 mm

Dali
- 05.4520.40.DA
- 05.4520.14.DA
- 05.4520.ER.DA
- 05.4520.ES.DA

Casambi
- 05.4520.40.CB
- 05.4520.14.CB
- 05.4520.ER.CB
- 05.4520.ES.CB




Luminous flux luminaire
1746 lm

L: 1800 mm

Dali
- 05.4522.40.DA
- 05.4522.14.DA
- 05.4522.ER.DA
- 05.4522.ES.DA

Casambi
- 05.4522.40.CB
- 05.4522.14.CB
- 05.4522.ER.CB
- 05.4522.ES.CB




Luminous flux luminaire
2619 lm

L: 2400 mm

Dali
- 05.4524.40.DA
- 05.4524.14.DA
- 05.4524.ER.DA
- 05.4524.ES.DA

Casambi
- 05.4524.40.CB
- 05.4524.14.CB
- 05.4524.ER.CB
- 05.4524.ES.CB




Luminous flux luminaire
3492 lm

3000K

L: 1200 mm

Dali
- 05.4521.40.DA
- 05.4521.14.DA
- 05.4521.ER.DA
- 05.4521.ES.DA

Casambi
- 05.4521.40.CB
- 05.4521.14.CB
- 05.4521.ER.CB
- 05.4521.ES.CB




Luminous flux luminaire
1834 lm

L: 1800 mm

Dali
- 05.4523.40.DA
- 05.4523.14.DA
- 05.4523.ER.DA
- 05.4523.ES.DA

Casambi
- 05.4523.40.CB
- 05.4523.14.CB
- 05.4523.ER.CB
- 05.4523.ES.CB




Luminous flux luminaire
2752 lm

3000K

L: 2400 mm

Dali
- 05.4525.40.DA
- 05.4525.14.DA
- 05.4525.ER.DA
- 05.4525.ES.DA

Casambi
- 05.4525.40.CB
- 05.4525.14.CB
- 05.4525.ER.CB
- 05.4525.ES.CB




Luminous flux luminaire
3670 lm

The Glowing Track 360 Surface Remote Driver

Top LED - L: 600 mm - 12,4W - 1232 lm - 2200K/CRI 90 / 1412 lm - 2700K/CRI 90 / 1484 lm - 3000K/CRI 90
L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90
L: 1800 mm - 37,2W - 3696 lm - 2200K/CRI 90 / 4236 lm - 2700K/CRI 90 / 4452 lm - 3000K/CRI 90
L: 2400 mm - 49,6W - 4928 lm - 2200K/CRI 90 / 5648 lm - 2700K/CRI 90 / 5936 lm - 3000K/CRI 90





GWT 850°

IP 20

LED INCL.

1 - 100%

360º surface ambient lighting system that provides uniform light distribution. Available in four lengths (600 mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.

Sistema de iluminación ambiental de superficie 360º que proporciona una distribución uniforme de la luz. Disponible en cuatro longitudes (600 mm, 1200 mm, 1800 mm y 2400 mm). Fuente de alimentación no incluida.

Recommended power supply / Equipo recomendado*:

	60W
Non Dimmable 24V	60.9705A

* Refer to the Drivers chapter / Ver capítulo Drivers

2200K


L: 600 mm

Dali

05.4695.40.DA
05.4695.14.DA
05.4695.ER.DA
05.4695.ES.DA

Casambi

05.4695.40.CB
05.4695.14.CB
05.4695.ER.CB
05.4695.ES.CB



Luminous flux luminaire
884 lm


L: 1200 mm

Dali

05.4670.40.DA
05.4670.14.DA
05.4670.ER.DA
05.4670.ES.DA

Casambi

05.4670.40.CB
05.4670.14.CB
05.4670.ER.CB
05.4670.ES.CB



Luminous flux luminaire
1768 lm


L: 1800 mm

Dali

05.4672.40.DA
05.4672.14.DA
05.4672.ER.DA
05.4672.ES.DA

Casambi

05.4672.40.CB
05.4672.14.CB
05.4672.ER.CB
05.4672.ES.CB



Luminous flux luminaire
2652 lm


L: 2400 mm

Dali

05.4674.40.DA
05.4674.14.DA
05.4674.ER.DA
05.4674.ES.DA

Casambi

05.4674.40.CB
05.4674.14.CB
05.4674.ER.CB
05.4674.ES.CB



Luminous flux luminaire
3536 lm

2700K


L: 600 mm

Dali

05.4595.40.DA
05.4595.14.DA
05.4595.ER.DA
05.4595.ES.DA

Casambi

05.4595.40.CB
05.4595.14.CB
05.4595.ER.CB
05.4595.ES.CB



Luminous flux luminaire
1013 lm


L: 1200 mm

Dali

05.4570.40.DA
05.4570.14.DA
05.4570.ER.DA
05.4570.ES.DA

Casambi

05.4570.40.CB
05.4570.14.CB
05.4570.ER.CB
05.4570.ES.CB



Luminous flux luminaire
2026 lm


L: 1800 mm

Dali

05.4572.40.DA
05.4572.14.DA
05.4572.ER.DA
05.4572.ES.DA

Casambi

05.4572.40.CB
05.4572.14.CB
05.4572.ER.CB
05.4572.ES.CB



Luminous flux luminaire
3040 lm


L: 2400 mm

Dali

05.4574.40.DA
05.4574.14.DA
05.4574.ER.DA
05.4574.ES.DA

Casambi

05.4574.40.CB
05.4574.14.CB
05.4574.ER.CB
05.4574.ES.CB



Luminous flux luminaire
4053 lm

NEW

3000K


L: 600 mm

Dali

05.4596.40.DA
05.4596.14.DA
05.4596.ER.DA
05.4596.ES.DA

Casambi

05.4596.40.CB
05.4596.14.CB
05.4596.ER.CB
05.4596.ES.CB



Luminous flux luminaire
1065 lm


L: 1200 mm

Dali

05.4571.40.DA
05.4571.14.DA
05.4571.ER.DA
05.4571.ES.DA

Casambi

05.4571.40.CB
05.4571.14.CB
05.4571.ER.CB
05.4571.ES.CB



Luminous flux luminaire
2130 lm


L: 1800 mm

Dali

05.4573.40.DA
05.4573.14.DA
05.4573.ER.DA
05.4573.ES.DA

Casambi

05.4573.40.CB
05.4573.14.CB
05.4573.ER.CB
05.4573.ES.CB



Luminous flux luminaire
3195 lm


L: 2400 mm

Dali

05.4575.40.DA
05.4575.14.DA
05.4575.ER.DA
05.4575.ES.DA

Casambi


05.4575.40.CB
05.4575.14.CB
05.4575.ER.CB
05.4575.ES.CB



Luminous flux luminaire
4260 lm

The Glowing Track Blind Surface Remote Driver





GWT 850°

IP 20

LED INCL.

1 - 100%

Surface electrified track designed for maximum versatility, allowing the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included.

Carril electrificado de superficie diseñado para ofrecer la máxima versatilidad, permitiendo la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver no incluido.

Recommended power supply / Equipo recomendado*:

	60W	120W
Non Dimmable 24V	60.9705A	60.9777A

* Refer to the Drivers chapter / Ver capítulo Drivers

L: 1200 mm

Dimmable

- 06.2672.40
- 06.2672.14
- 06.2672.ER
- 06.2672.ES

Non Dimmable

- 06.2673.40
- 06.2673.14
- 06.2673.ER
- 06.2673.ES

L: 1800 mm

Dimmable

- 06.2674.40
- 06.2674.14
- 06.2674.ER
- 06.2674.ES

Non Dimmable

- 06.2675.40
- 06.2675.14
- 06.2675.ER
- 06.2675.ES

L: 2400 mm

Dimmable

- 06.2676.40
- 06.2676.14
- 06.2676.ER
- 06.2676.ES

Non Dimmable


- 06.2677.40
- 06.2677.14
- 06.2677.ER
- 06.2677.ES

NEW

The Glowing Track Surface + Wall PSU

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90





GWT 850° | IP 20 | LED INCL | 1 - 100%

Surface lighting system that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in 1200 mm. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA.
Available power on the track:
1200mm: 10,5W


Sistema de iluminación de superficie que combina luz ambiental con un carril que permite la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en 1200 mm. Fuente de alimentación y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA.
Potencia disponible en el carril:
1200mm: 10,5W

2200K

L: 1200 mm

Casambi

- 05.4690.40.CB
- 05.4690.14.CB
- 05.4690.ER.CB
- 05.4690.ES.CB




Luminous flux luminaire
1523 lm

3000K

L: 1200 mm

Casambi

- 05.4591.40.CB
- 05.4591.14.CB
- 05.4591.ER.CB
- 05.4591.ES.CB




Luminous flux luminaire
1834 lm

2700K

L: 1200 mm

Casambi

- 05.4590.40.CB
- 05.4590.14.CB
- 05.4590.ER.CB
- 05.4590.ES.CB




Luminous flux luminaire
1746 lm

The Glowing Track 360 Surface + Wall PSU

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90





GWT 850° | IP 20 | LED INCL | 1 - 100%

360° surface ambient lighting system that provides uniform light distribution. Available in 1200 mm. Driver not included. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA.


Sistema de iluminación ambiental de superficie 360° que proporciona una distribución uniforme de la luz. Disponible en 1200 mm. Fuente de alimentación no incluida. Fuente de alimentación y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA.

2200K

L: 1200 mm

Casambi

- 05.4692.40.CB
- 05.4692.14.CB
- 05.4692.ER.CB
- 05.4692.ES.CB




Luminous flux luminaire
1768 lm

3000K

L: 1200 mm

Casambi

- 05.4593.40.CB
- 05.4593.14.CB
- 05.4593.ER.CB
- 05.4593.ES.CB




Luminous flux luminaire
2130 lm

2700K

L: 1200 mm

Casambi

- 05.4592.40.CB
- 05.4592.14.CB
- 05.4592.ER.CB
- 05.4592.ES.CB





Luminous flux luminaire
2026 lm

The Glowing Track Surface Integrated Driver

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90
L: 1800 mm - 37,2W - 3696 lm - 2200K/CRI 90 / 4236 lm - 2700K/CRI 90 / 4452 lm - 3000K/CRI 90
L: 2400 mm - 49,6W - 4928 lm - 2200K/CRI 90 / 5648 lm - 2700K/CRI 90 / 5936 lm - 3000K/CRI 90







Surface lighting system that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver included.
Available power on the track:
1200mm / 1800mm: 78W
2400mm: 70W


Sistema de iluminación de superficie que combina iluminación ambiental con un carril que permite la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver incluido.
Potencia disponible en el carril:
1200mm / 1800mm: 78W
2400mm: 70W

2200K

L: 1200 mm

Dali
- 05.4610.40.DA
- 05.4610.14.DA
- 05.4610.ER.DA
- 05.4610.ES.DA

Casambi
- 05.4610.40.CB
- 05.4610.14.CB
- 05.4610.ER.CB
- 05.4610.ES.CB




Luminous flux luminaire
1523 lm

L: 1800 mm

Dali
- 05.4612.40.DA
- 05.4612.14.DA
- 05.4612.ER.DA
- 05.4612.ES.DA

Casambi
- 05.4612.40.CB
- 05.4612.14.CB
- 05.4612.ER.CB
- 05.4612.ES.CB




Luminous flux luminaire
2285 lm

L: 2400 mm

Dali
- 05.4614.40.DA
- 05.4614.14.DA
- 05.4614.ER.DA
- 05.4614.ES.DA

Casambi
- 05.4614.40.CB
- 05.4614.14.CB
- 05.4614.ER.CB
- 05.4614.ES.CB




Luminous flux luminaire
3047 lm

2700K

L: 1200 mm

Dali
- 05.4510.40.DA
- 05.4510.14.DA
- 05.4510.ER.DA
- 05.4510.ES.DA

Casambi
- 05.4510.40.CB
- 05.4510.14.CB
- 05.4510.ER.CB
- 05.4510.ES.CB




Luminous flux luminaire
1746 lm

L: 1800 mm

Dali
- 05.4512.40.DA
- 05.4512.14.DA
- 05.4512.ER.DA
- 05.4512.ES.DA

Casambi
- 05.4512.40.CB
- 05.4512.14.CB
- 05.4512.ER.CB
- 05.4512.ES.CB




Luminous flux luminaire
2619 lm

L: 2400 mm

Dali
- 05.4514.40.DA
- 05.4514.14.DA
- 05.4514.ER.DA
- 05.4514.ES.DA

Casambi
- 05.4514.40.CB
- 05.4514.14.CB
- 05.4514.ER.CB
- 05.4514.ES.CB




Luminous flux luminaire
3492 lm

3000K

L: 1200 mm

Dali
- 05.4511.40.DA
- 05.4511.14.DA
- 05.4511.ER.DA
- 05.4511.ES.DA

Casambi
- 05.4511.40.CB
- 05.4511.14.CB
- 05.4511.ER.CB
- 05.4511.ES.CB




Luminous flux luminaire
1834 lm

L: 1800 mm

Dali
- 05.4513.40.DA
- 05.4513.14.DA
- 05.4513.ER.DA
- 05.4513.ES.DA

Casambi
- 05.4513.40.CB
- 05.4513.14.CB
- 05.4513.ER.CB
- 05.4513.ES.CB




Luminous flux luminaire
2752 lm

3000K

L: 2400 mm

Dali
- 05.4515.40.DA
- 05.4515.14.DA
- 05.4515.ER.DA
- 05.4515.ES.DA

Casambi
- 05.4515.40.CB
- 05.4515.14.CB
- 05.4515.ER.CB
- 05.4515.ES.CB




Luminous flux luminaire
3670 lm

NEW

The Glowing Track 360 Surface Integrated Driver

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90
L: 1800 mm - 37,2W - 3696 lm - 2200K/CRI 90 / 4236 lm - 2700K/CRI 90 / 4452 lm - 3000K/CRI 90
L: 2400 mm - 49,6W - 4928 lm - 2200K/CRI 90 / 5648 lm - 2700K/CRI 90 / 5936 lm - 3000K/CRI 90





GWT 850° | IP 20 | LED INCL | 1 - 100%

360º surface ambient lighting system that provides uniform light distribution. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver included.


Sistema de iluminación ambiental de superficie 360º que proporciona una distribución uniforme de la luz. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver incluido.

2200K

L: 1200 mm

Dali
- 05.4660.40.DA
- 05.4660.14.DA
- 05.4660.ER.DA
- 05.4660.ES.DA

Casambi
- 05.4660.40.CB
- 05.4660.14.CB
- 05.4660.ER.CB
- 05.4660.ES.CB




Luminous flux luminaire
1768 lm

L: 1800 mm

Dali
- 05.4662.40.DA
- 05.4662.14.DA
- 05.4662.ER.DA
- 05.4662.ES.DA

Casambi
- 05.4662.40.CB
- 05.4662.14.CB
- 05.4662.ER.CB
- 05.4662.ES.CB




Luminous flux luminaire
2652 lm

L: 2400 mm

Dali
- 05.4664.40.DA
- 05.4664.14.DA
- 05.4664.ER.DA
- 05.4664.ES.DA

Casambi
- 05.4664.40.CB
- 05.4664.14.CB
- 05.4664.ER.CB
- 05.4664.ES.CB




Luminous flux luminaire
3536 lm

3000K

L: 1200 mm

Dali
- 05.4561.40.DA
- 05.4561.14.DA
- 05.4561.ER.DA
- 05.4561.ES.DA

Casambi
- 05.4561.40.CB
- 05.4561.14.CB
- 05.4561.ER.CB
- 05.4561.ES.CB




Luminous flux luminaire
2130 lm

L: 1800 mm

Dali
- 05.4563.40.DA
- 05.4563.14.DA
- 05.4563.ER.DA
- 05.4563.ES.DA

Casambi
- 05.4563.40.CB
- 05.4563.14.CB
- 05.4563.ER.CB
- 05.4563.ES.CB




Luminous flux luminaire
3195 lm

2700K

L: 1200 mm

Dali
- 05.4560.40.DA
- 05.4560.14.DA
- 05.4560.ER.DA
- 05.4560.ES.DA

Casambi
- 05.4560.40.CB
- 05.4560.14.CB
- 05.4560.ER.CB
- 05.4560.ES.CB




Luminous flux luminaire
2026 lm

L: 1800 mm

Dali
- 05.4562.40.DA
- 05.4562.14.DA
- 05.4562.ER.DA
- 05.4562.ES.DA

Casambi
- 05.4562.40.CB
- 05.4562.14.CB
- 05.4562.ER.CB
- 05.4562.ES.CB




Luminous flux luminaire
3040 lm

L: 2400 mm

Dali
- 05.4564.40.DA
- 05.4564.14.DA
- 05.4564.ER.DA
- 05.4564.ES.DA

Casambi
- 05.4564.40.CB
- 05.4564.14.CB
- 05.4564.ER.CB
- 05.4564.ES.CB




Luminous flux luminaire
4053 lm

3000K

L: 2400 mm

Dali
- 05.4565.40.DA
- 05.4565.14.DA
- 05.4565.ER.DA
- 05.4565.ES.DA


Casambi
- 05.4565.40.CB
- 05.4565.14.CB
- 05.4565.ER.CB
- 05.4565.ES.CB




Luminous flux luminaire
4260 lm

The Glowing Track Blind Surface Integrated Driver







Surface electrified track designed for maximum versatility, allowing the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver included.

Carril electrificado de superficie diseñado para ofrecer la máxima versatilidad, permitiendo la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver incluido.

L: 1200 mm

Dimmable

- 06.2666.40
- 06.2666.14
- 06.2666.ER
- 06.2666.ES

Non Dimmable

- 06.2667.40
- 06.2667.14
- 06.2667.ER
- 06.2667.ES

L: 1800 mm

Dimmable

- 06.2668.40
- 06.2668.14
- 06.2668.ER
- 06.2668.ES

Non Dimmable

- 06.2669.40
- 06.2669.14
- 06.2669.ER
- 06.2669.ES

L: 2400 mm

Dimmable

- 06.2670.40
- 06.2670.14
- 06.2670.ER
- 06.2670.ES


Non Dimmable

- 06.2671.40
- 06.2671.14
- 06.2671.ER
- 06.2671.ES






NEW

THE GLOWING TRACK — PROFILES

SURFACE INTEGRATED DRIVER INSTALLATION



Accessories / Accesorios


Linear Joint Linear connection used to join components in a straight line.	**Unión Lineal** Conexión lineal utilizada para unir componentes en línea recta.			08.1209.40 08.1209.14 08.1209.ER 08.1209.ES
Corner Joint 2 90° corner connector used to join components in the horizontal and vertical plane.	**Unión de Esquina 2** Conector de esquina a 90° utilizado para unir componentes en plano horizontal y vertical.			08.1210.40 08.1210.14 08.1210.ER 08.1210.ES
Corner Joint 3 Connector used to join three components at right angles	**Unión de Esquina 3** Conector utilizado para unir tres componentes en ángulo recto.			08.1211.40 08.1211.14 08.1211.ER 08.1211.ES
Corner Joint 4 Connector used to join four components at right angles.	**Unión de Esquina 4** Conector utilizado para unir cuatro componentes en ángulo recto.			08.1212.40 08.1212.14 08.1212.ER 08.1212.ES
Ceiling Fixing Kit	Kit de sujeción a techo.			08.0615.00

Profile (mm)	Fixation points	Ceiling Kit to order
1200	3	2
1800	4	2
2400	4	2

The Glowing Track Vertical

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90
L: 1800 mm - 37,2W - 3696 lm - 2200K/CRI 90 / 4236 lm - 2700K/CRI 90 / 4452 lm - 3000K/CRI 90
L: 2400 mm - 49,6W - 4928 lm - 2200K/CRI 90 / 5648 lm - 2700K/CRI 90 / 5936 lm - 3000K/CRI 90





GWT 850°

IP 20

LED INCL

1 - 100%

Surface lighting system with a vertical orientation that combines ambient lighting with a track that allows the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included. Available power on the track:
1200mm / 1800mm: 78W
2400mm: 70W

Sistema de iluminación de superficie con orientación vertical que combina la iluminación ambiental con una guía que permite la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver no incluido. Potencia disponible en el carril:
1200mm / 1800mm: 78W
2400mm: 70W

Recommended power supply / Equipo recomendado*:

	120W
Non Dimmable 24V	60.9777A


* Refer to the Drivers chapter / Ver capítulo Drivers

2200K

L: 1200 mm

Dali
- 05.4630.40.DA
- 05.4630.14.DA
- 05.4630.ER.DA
- 05.4630.ES.DA

Casambi
- 05.4630.40.CB
- 05.4630.14.CB
- 05.4630.ER.CB
- 05.4630.ES.CB




Luminous flux luminaire
1523 lm

L: 1800 mm

Dali
- 05.4632.40.DA
- 05.4632.14.DA
- 05.4632.ER.DA
- 05.4632.ES.DA

Casambi
- 05.4632.40.CB
- 05.4632.14.CB
- 05.4632.ER.CB
- 05.4632.ES.CB




Luminous flux luminaire
2285 lm

L: 2400 mm

Dali
- 05.4634.40.DA
- 05.4634.14.DA
- 05.4634.ER.DA
- 05.4634.ES.DA

Casambi
- 05.4634.40.CB
- 05.4634.14.CB
- 05.4634.ER.CB
- 05.4634.ES.CB




Luminous flux luminaire
3047 lm

3000K

L: 1200 mm

Dali
- 05.4531.40.DA
- 05.4531.14.DA
- 05.4531.ER.DA
- 05.4531.ES.DA

Casambi
- 05.4531.40.CB
- 05.4531.14.CB
- 05.4531.ER.CB
- 05.4531.ES.CB




Luminous flux luminaire
1834 lm

L: 1800 mm

Dali
- 05.4533.40.DA
- 05.4533.14.DA
- 05.4533.ER.DA
- 05.4533.ES.DA

Casambi
- 05.4533.40.CB
- 05.4533.14.CB
- 05.4533.ER.CB
- 05.4533.ES.CB




Luminous flux luminaire
2752 lm

2700K

L: 1200 mm

Dali
- 05.4530.40.DA
- 05.4530.14.DA
- 05.4530.ER.DA
- 05.4530.ES.DA

Casambi
- 05.4530.40.CB
- 05.4530.14.CB
- 05.4530.ER.CB
- 05.4530.ES.CB




Luminous flux luminaire
1746 lm

L: 1800 mm

Dali
- 05.4532.40.DA
- 05.4532.14.DA
- 05.4532.ER.DA
- 05.4532.ES.DA

Casambi
- 05.4532.40.CB
- 05.4532.14.CB
- 05.4532.ER.CB
- 05.4532.ES.CB




Luminous flux luminaire
2619 lm

L: 2400 mm

Dali
- 05.4534.40.DA
- 05.4534.14.DA
- 05.4534.ER.DA
- 05.4534.ES.DA

Casambi
- 05.4534.40.CB
- 05.4534.14.CB
- 05.4534.ER.CB
- 05.4534.ES.CB




Luminous flux luminaire
3492 lm

3000K

L: 2400 mm

Dali
- 05.4535.40.DA
- 05.4535.14.DA
- 05.4535.ER.DA
- 05.4535.ES.DA

Casambi
- 05.4535.40.CB
- 05.4535.14.CB
- 05.4535.ER.CB
- 05.4535.ES.CB




Luminous flux luminaire
3670 lm

NEW

The Glowing Track 360 Vertical

Top LED - L: 1200 mm - 24,8W - 2464 lm - 2200K/CRI 90 / 2824 lm - 2700K/CRI 90 / 2968 lm - 3000K/CRI 90
L: 1800 mm - 37,2W - 3696 lm - 2200K/CRI 90 / 4236 lm - 2700K/CRI 90 / 4452 lm - 3000K/CRI 90
L: 2400 mm - 49,6W - 4928 lm - 2200K/CRI 90 / 5648 lm - 2700K/CRI 90 / 5936 lm - 3000K/CRI 90





GWT 850° | IP 20 | LED INCL | 1 - 100%

360º surface ambient lighting system with a vertical orientation that provides uniform light distribution. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included.

Sistema de iluminación ambiental de superficie 360º con orientación vertical que proporciona una distribución uniforme de la luz. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver no incluido.


Recommended power supply / Equipo recomendado*:

	60W
Non Dimmable 24V	60.9705A

* Refer to the Drivers chapter / Ver capítulo Drivers


2200K

L: 1200 mm
Dali
05.4680.40.DA
05.4680.14.DA
05.4680.ER.DA
05.4680.ES.DA
Casambi
05.4680.40.CB
05.4680.14.CB
05.4680.ER.CB
05.4680.ES.CB




Luminous flux luminaire
1768 lm

L: 1800 mm
Dali
05.4682.40.DA
05.4682.14.DA
05.4682.ER.DA
05.4682.ES.DA
Casambi
05.4682.40.CB
05.4682.14.CB
05.4682.ER.CB
05.4682.ES.CB



Luminous flux luminaire
2652 lm


L: 2400 mm
Dali
05.4684.40.DA
05.4684.14.DA
05.4684.ER.DA
05.4684.ES.DA
Casambi
05.4684.40.CB
05.4684.14.CB
05.4684.ER.CB
05.4684.ES.CB



Luminous flux luminaire
3536 lm


2700K

L: 1200 mm
Dali
05.4580.40.DA
05.4580.14.DA
05.4580.ER.DA
05.4580.ES.DA
Casambi
05.4580.40.CB
05.4580.14.CB
05.4580.ER.CB
05.4580.ES.CB




Luminous flux luminaire
2026 lm

L: 1800 mm
Dali
05.4582.40.DA
05.4582.14.DA
05.4582.ER.DA
05.4582.ES.DA
Casambi
05.4582.40.CB
05.4582.14.CB
05.4582.ER.CB
05.4582.ES.CB



Luminous flux luminaire
3040 lm


L: 2400 mm
Dali
05.4584.40.DA
05.4584.14.DA
05.4584.ER.DA
05.4584.ES.DA
Casambi
05.4584.40.CB
05.4584.14.CB
05.4584.ER.CB
05.4584.ES.CB



Luminous flux luminaire
4053 lm


3000K

L: 1200 mm
Dali
05.4581.40.DA
05.4581.14.DA
05.4581.ER.DA
05.4581.ES.DA
Casambi
05.4581.40.CB
05.4581.14.CB
05.4581.ER.CB
05.4581.ES.CB



Luminous flux luminaire
2130 lm


L: 1800 mm
Dali
05.4583.40.DA
05.4583.14.DA
05.4583.ER.DA
05.4583.ES.DA
Casambi
05.4583.40.CB
05.4583.14.CB
05.4583.ER.CB
05.4583.ES.CB



Luminous flux luminaire
3195 lm

3000K


L: 2400 mm
Dali
05.4585.40.DA
05.4585.14.DA
05.4585.ER.DA
05.4585.ES.DA
Casambi
05.4585.40.CB
05.4585.14.CB
05.4585.ER.CB
05.4585.ES.CB



Luminous flux luminaire
4260 lm

The Glowing Track Blind Vertical





GWT 850°

IP 20

LED INCL.

1 - 100%

Surface electrified track designed for maximum versatility, allowing the installation of a wide range of projectors and accent lighting modules. Available in three lengths (1200 mm, 1800 mm, and 2400 mm). Driver not included.

Carril electrificado de superficie diseñado para ofrecer la máxima versatilidad, permitiendo la instalación de una amplia gama de proyectores y módulos de iluminación de acento. Disponible en tres longitudes (1200 mm, 1800 mm y 2400 mm). Driver no incluido.

Recommended power supply / Equipo recomendado*:

	60W	120W
Non Dimmable 24V	60.9705A	60.9777A

* Refer to the Drivers chapter / Ver capítulo Drivers

L: 1200 mm

Dimmable

- 06.2678.40
- 06.2678.14
- 06.2678.ER
- 06.2678.ES

Non Dimmable

- 06.2679.40
- 06.2679.14
- 06.2679.ER
- 06.2679.ES

L: 1800 mm

Dimmable

- 06.2680.40
- 06.2680.14
- 06.2680.ER
- 06.2680.ES

Non Dimmable

- 06.2681.40
- 06.2681.14
- 06.2681.ER
- 06.2681.ES

L: 2400 mm

Dimmable


- 06.2682.40
- 06.2682.14
- 06.2682.ER
- 06.2682.ES

Non Dimmable


- 06.2683.40
- 06.2683.14
- 06.2683.ER
- 06.2683.ES

THE GLOWING TRACK — PROFILES

VERTICAL INSTALLATION





Accessory / Accesorio

Corner Joint 2 90° corner connector used to join components in the horizontal and vertical plane.	**Unión de Esquina 2** Conector de esquina a 90° utilizado para unir componentes en plano horizontal y vertical.			08.1206.40 08.1206.14 08.1206.ER 08.1206.ES

Drivers / Equipos


Remote Installation


Power supply source with constant voltage 24V - 60W, 220-240W-50/60Hz.	Fuente de alimentación de tensión constante 24V - 60W, 220-240W-50/60Hz.			60.9705A
Power supply source with constant voltage 24V - 120W, 220-240W-50/60Hz.	Fuente de alimentación de tensión constante 24V - 120W, 220-240W-50/60Hz.			60.9777A

Multi Spot Mini

Power LED 6,1W - 636 lm - 2700K/CRI 90 / 672 lm - 3000K/CRI 90







LED lighting module with 12 spotlights and low glare, to be installed in The Glowing Track System.

Módulo de iluminación LED de 12 focos y bajo deslumbramiento para ser instalado en el sistema The Glowing Track.

Optic Spot - 2700K


Non Dimmable

05.3560.40A
05.3560.14A
05.3560.ERA
05.3560.ESA

Dali 2

05.3560.40.DA
05.3560.14.DA
05.3560.ER.DA
05.3560.ES.DA

15°
SPOT



Luminous flux luminaire
408 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	3961	0.26
2	990	0.53
3	440	0.79
4	248	1.05
5	158	1.32

Optic Spot - 3000K


Non Dimmable

05.3561.40A
05.3561.14A
05.3561.ERA
05.3561.ESA

Dali 2

05.3561.40.DA
05.3561.14.DA
05.3561.ER.DA
05.3561.ES.DA

15°
SPOT



Luminous flux luminaire
415 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	4032	0.26
2	1008	0.53
3	448	0.79
4	252	1.05
5	161	1.32

Optic Medium - 2700K


Non Dimmable

05.3562.40A
05.3562.14A
05.3562.ERA
05.3562.ESA

Dali 2

05.3562.40.DA
05.3562.14.DA
05.3562.ER.DA
05.3562.ES.DA

19°
MEDIUM



Luminous flux luminaire
433 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2895	0.33
2	724	0.66
3	322	0.99
4	181	1.32
5	116	1.65

Optic Medium - 3000K


Non Dimmable

05.3563.40A
05.3563.14A
05.3563.ERA
05.3563.ESA

Dali 2

05.3563.40.DA
05.3563.14.DA
05.3563.ER.DA
05.3563.ES.DA

19°
MEDIUM



Luminous flux luminaire
440 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2947	0.33
2	737	0.66
3	327	0.99
4	184	1.32
5	118	1.65

Optic Flood - 2700K


Non Dimmable

05.3564.40A
05.3564.14A
05.3564.ERA
05.3564.ESA

Dali 2

05.3564.40.DA
05.3564.14.DA
05.3564.ER.DA
05.3564.ES.DA

31°
FLOOD



Luminous flux luminaire
401 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	1118	0.55
2	279	1.09
3	124	1.64
4	70	2.18
5	45	2.73

Optic Flood - 3000K


Non Dimmable

05.3565.40A
05.3565.14A
05.3565.ERA
05.3565.ESA

Dali 2

05.3565.40.DA
05.3565.14.DA
05.3565.ER.DA
05.3565.ES.DA

31°
FLOOD



Luminous flux luminaire
408 lm

Beam Angle: 31°


h(m)	E(lx)	D(m)
1	1138	0.55
2	284	1.09
3	126	1.64
4	71	2.18
5	46	2.73


NEW

Light Shadow Spot 30

Power LED 4,7W - 298 lm - 2700K/CRI 90 / 318 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual control via DALI protocol.

Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI.

Optic Spot - 2700K


Non Dimmable

- 05.5170.40
- 05.5170.14
- 05.5170.ER
- 05.5170.ES

Dali

- 05.5170.40.DA
- 05.5170.14.DA
- 05.5170.ER.DA
- 05.5170.ES.DA





Luminous flux luminaire
253 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4044	0.20
2	1011	0.40
3	449	0.60
4	253	0.80
5	162	1.00

Optic Spot - 3000K


Non Dimmable

- 05.5175.40
- 05.5175.14
- 05.5175.ER
- 05.5175.ES

Dali

- 05.5175.40.DA
- 05.5175.14.DA
- 05.5175.ER.DA
- 05.5175.ES.DA





Luminous flux luminaire
270 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4316	0.20
2	1079	0.40
3	480	0.60
4	270	0.80
5	173	1.00

Optic Medium - 2700K


Non Dimmable

- 05.5171.40
- 05.5171.14
- 05.5171.ER
- 05.5171.ES

Dali

- 05.5171.40.DA
- 05.5171.14.DA
- 05.5171.ER.DA
- 05.5171.ES.DA





Luminous flux luminaire
257 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1797	0.39
2	449	0.78
3	200	1.17
4	112	1.56
5	72	1.95

Optic Medium - 3000K


Non Dimmable

- 05.5176.40
- 05.5176.14
- 05.5176.ER
- 05.5176.ES

Dali

- 05.5176.40.DA
- 05.5176.14.DA
- 05.5176.ER.DA
- 05.5176.ES.DA





Luminous flux luminaire
274 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1916	0.39
2	479	0.78
3	213	1.17
4	120	1.56
5	77	1.95

Optic Flood - 2700K


Non Dimmable

- 05.5172.40
- 05.5172.14
- 05.5172.ER
- 05.5172.ES

Dali

- 05.5172.40.DA
- 05.5172.14.DA
- 05.5172.ER.DA
- 05.5172.ES.DA





Luminous flux luminaire
246 lm

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	953	0.52
2	238	1.04
3	106	1.57
4	60	2.09
5	38	2.61

Optic Flood - 3000K


Non Dimmable

- 05.5177.40
- 05.5177.14
- 05.5177.ER
- 05.5177.ES

Dali

- 05.5177.40.DA
- 05.5177.14.DA
- 05.5177.ER.DA
- 05.5177.ES.DA





Luminous flux luminaire
263 lm

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	1019	0.52
2	255	1.04
3	113	1.57
4	64	2.09
5	41	2.61

Optic Wide Flood - 2700K


Non Dimmable

- 05.5173.40
- 05.5173.14
- 05.5173.ER
- 05.5173.ES

Dali

- 05.5173.40.DA
- 05.5173.14.DA
- 05.5173.ER.DA
- 05.5173.ES.DA





Luminous flux luminaire
246 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	524	0.80
2	131	1.59
3	58	2.39
4	33	3.19
5	21	3.99

Optic Wide Flood - 3000K


Non Dimmable

- 05.5178.40
- 05.5178.14
- 05.5178.ER
- 05.5178.ES

Dali

- 05.5178.40.DA
- 05.5178.14.DA
- 05.5178.ER.DA
- 05.5178.ES.DA





Luminous flux luminaire
262 lm


Beam Angle: 43°


h(m)	E(lx)	D(m)
1	559	0.80
2	140	1.59
3	62	2.39
4	35	3.19
5	22	3.99

Light Shadow Spot 45

LED Array 11W - 799 lm - 2700K/CRI 90 / 844 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual control via DALI protocol.

Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI.

Optic Spot - 2700K


Non Dimmable

05.5180.40
05.5180.14
05.5180.ER
05.5180.ES

Dali

05.5180.40.DA
05.5180.14.DA
05.5180.ER.DA
05.5180.ES.DA

15°
SPOT



Luminous flux luminaire
650 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8012	0.27
2	2003	0.54
3	890	0.80
4	501	1.07
5	320	1.34

Optic Spot - 3000K


Non Dimmable

05.5185.40
05.5185.14
05.5185.ER
05.5185.ES

Dali

05.5185.40.DA
05.5185.14.DA
05.5185.ER.DA
05.5185.ES.DA

15°
SPOT



Luminous flux luminaire
686 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8456	0.27
2	2114	0.54
3	940	0.80
4	528	1.07
5	338	1.34

Optic Medium - 2700K


Non Dimmable

05.5181.40
05.5181.14
05.5181.ER
05.5181.ES

Dali

05.5181.40.DA
05.5181.14.DA
05.5181.ER.DA
05.5181.ES.DA

21°
MEDIUM



Luminous flux luminaire
645 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5163	0.36
2	1291	0.73
3	574	1.09
4	323	1.46
5	207	1.82

Optic Medium - 3000K


Non Dimmable

05.5186.40
05.5186.14
05.5186.ER
05.5186.ES

Dali

05.5186.40.DA
05.5186.14.DA
05.5186.ER.DA
05.5186.ES.DA

21°
MEDIUM



Luminous flux luminaire
682 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5459	0.36
2	1365	0.73
3	607	1.09
4	341	1.46
5	218	1.82

Optic Flood - 2700K


Non Dimmable

05.5182.40
05.5182.14
05.5182.ER
05.5182.ES

Dali

05.5182.40.DA
05.5182.14.DA
05.5182.ER.DA
05.5182.ES.DA

31°
FLOOD



Luminous flux luminaire
646 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2296	0.56
2	574	1.11
3	255	1.67
4	144	2.22
5	92	2.78

Optic Flood - 3000K


Non Dimmable

05.5187.40
05.5187.14
05.5187.ER
05.5187.ES

Dali

05.5187.40.DA
05.5187.14.DA
05.5187.ER.DA
05.5187.ES.DA

31°
FLOOD



Luminous flux luminaire
682 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2424	0.56
2	606	1.11
3	269	1.67
4	152	2.22
5	97	2.78

NEW

Accessories / Accesorios

Light Shadow Spot 30

Honeycomb	Panel de abeja		08.0790.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0791.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0792.00


Light Shadow Spot 45


Honeycomb	Panel de abeja		08.0793.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0794.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0795.00

Find Me 0 by Jorge Herrera

Power LED 3,5W - 276 lm - 2700K/CRI 90 / 302 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Accessories included (honeycomb grid and protection bar).

Módulo de iluminación LED de proyeción para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play). Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Optic Spot - 2700K


Non Dimmable

05.5100.40
05.5100.14
05.5100.ER
05.5100.ES

Casambi

05.5100.40.CB
05.5100.14.CB
05.5100.ER.CB
05.5100.ES.CB





Luminous flux luminaire
169 lm

Beam Angle:	15°
h(m) E(lx)	D(m)
1 1925	0.26
2 481	0.52
3 214	0.77
4 120	1.03
5 77	1.29

Optic Spot - 3000K


Non Dimmable

05.5105.40
05.5105.14
05.5105.ER
05.5105.ES

Casambi

05.5105.40.CB
05.5105.14.CB
05.5105.ER.CB
05.5105.ES.CB





Luminous flux luminaire
183 lm

Beam Angle:	15°
h(m) E(lx)	D(m)
1 2085	0.26
2 521	0.52
3 232	0.77
4 130	1.03
5 83	1.29

Optic Medium - 2700K


Non Dimmable

05.5101.40
05.5101.14
05.5101.ER
05.5101.ES

Casambi

05.5101.40.CB
05.5101.14.CB
05.5101.ER.CB
05.5101.ES.CB





Luminous flux luminaire
179 lm

Beam Angle:	25°
h(m) E(lx)	D(m)
1 928	0.45
2 232	0.89
3 103	1.34
4 58	1.79
5 37	2.23

Optic Medium - 3000K


Non Dimmable

05.5106.40
05.5106.14
05.5106.ER
05.5106.ES

Casambi

05.5106.40.CB
05.5106.14.CB
05.5106.ER.CB
05.5106.ES.CB





Luminous flux luminaire
194 lm

Beam Angle:	25°
h(m) E(lx)	D(m)
1 1006	0.45
2 251	0.89
3 112	1.34
4 63	1.79
5 40	2.23


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Find Me 0 by Jorge Herrera

Power LED 3,5W - 276 lm - 2700K/CRI 90 / 302 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual control via DALI protocol. Accessories included (honeycomb grid and protection bar).


Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DAL. Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Optic Spot - 2700K

Dali

- 05.5100.40.DA
- 05.5100.14.DA
- 05.5100.ER.DA
- 05.5100.ES.DA

15° SPOT



Luminous flux luminaire
169 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	1925	0.26
2	481	0.52
3	214	0.77
4	120	1.03
5	77	1.29

Optic Spot - 3000K

Dali

- 05.5105.40.DA
- 05.5105.14.DA
- 05.5105.ER.DA
- 05.5105.ES.DA

15° SPOT



Luminous flux luminaire
183 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	2085	0.26
2	521	0.52
3	232	0.77
4	130	1.03
5	83	1.29

Optic Medium - 2700K

Dali

- 05.5101.40.DA
- 05.5101.14.DA
- 05.5101.ER.DA
- 05.5101.ES.DA

25° MEDIUM



Luminous flux luminaire
179 lm

Beam Angle: 25°


h(m)	E(lx)	D(m)
1	928	0.45
2	232	0.89
3	103	1.34
4	58	1.79
5	37	2.23

Optic Medium - 3000K

Dali

- 05.5106.40.DA
- 05.5106.14.DA
- 05.5106.ER.DA
- 05.5106.ES.DA

25° MEDIUM



Luminous flux luminaire
194 lm


Beam Angle: 25°


h(m)	E(lx)	D(m)
1	1006	0.45
2	251	0.89
3	112	1.34
4	63	1.79
5	40	2.23

Find Me 1 by Jorge Herrera

Power LED 5,5W - 432 lm - 2700K/CRI 90 / 446 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Accessories included (honeycomb grid and protection bar).

Módulo de iluminación LED de proyeción para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play). Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Optic Spot - 2700K


Non Dimmable

05.5110.40
05.5110.14
05.5110.ER
05.5110.ES

Casambi

05.5110.40.CB
05.5110.14.CB
05.5110.ER.CB
05.5110.ES.CB





Luminous flux luminaire
309 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	4167	0.24
2	1042	0.48
3	463	0.72
4	260	0.95
5	167	1.19

Optic Spot - 3000K


Non Dimmable

05.5115.40
05.5115.14
05.5115.ER
05.5115.ES

Casambi

05.5115.40.CB
05.5115.14.CB
05.5115.ER.CB
05.5115.ES.CB





Luminous flux luminaire
314 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	4196	0.24
2	1049	0.49
3	466	0.73
4	262	0.97
5	168	1.21

Optic Medium - 2700K


Non Dimmable

05.5111.40
05.5111.14
05.5111.ER
05.5111.ES

Casambi

05.5111.40.CB
05.5111.14.CB
05.5111.ER.CB
05.5111.ES.CB





Luminous flux luminaire
284 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	1893	0.35
2	473	0.70
3	210	1.06
4	118	1.41
5	76	1.76

Optic Medium - 3000K


Non Dimmable

05.5116.40
05.5116.14
05.5116.ER
05.5116.ES

Casambi

05.5116.40.CB
05.5116.14.CB
05.5116.ER.CB
05.5116.ES.CB





Luminous flux luminaire
289 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	1927	0.35
2	482	0.70
3	214	1.06
4	120	1.41
5	77	1.76


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Find Me 1 by Jorge Herrera

Power LED 5,5W - 450 lm - 2700K/CRI 90 / 485 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual control via DALI protocol. Accessories included (honeycomb grid and protection bar).


Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI. Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Optic Spot - 2700K

Dali

05.5110.40.DA
05.5110.14.DA
05.5110.ER.DA
05.5110.ES.DA





Luminous flux luminaire
309 lm

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	4167	0.24
2	1042	0.48
3	463	0.72
4	260	0.95
5	167	1.19

Optic Spot - 3000K

Dali

05.5115.40.DA
05.5115.14.DA
05.5115.ER.DA
05.5115.ES.DA





Luminous flux luminaire
314 lm

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	4196	0.24
2	1049	0.49
3	466	0.73
4	262	0.97
5	168	1.21

Optic Medium - 2700K

Dali

05.5111.40.DA
05.5111.14.DA
05.5111.ER.DA
05.5111.ES.DA





Luminous flux luminaire
284 lm

Beam Angle: 20°


h(m)	E(lx)	D(m)
1	1893	0.35
2	473	0.70
3	210	1.06
4	118	1.41
5	76	1.76

Optic Medium - 3000K

Dali

05.5116.40.DA
05.5116.14.DA
05.5116.ER.DA
05.5116.ES.DA





Luminous flux luminaire
289 lm


Beam Angle: 20°


h(m)	E(lx)	D(m)
1	1927	0.35
2	482	0.70
3	214	1.06
4	120	1.41
5	77	1.76

Find Me 2 by Jorge Herrera

Power LED 10,5W - 724 lm - 2700K/CRI90 / 781 lm - 3000K/CRI90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Accessories included (honeycomb grid and protection bar).
Warning: Not suitable for vertical installation.

Módulo de iluminación LED de proyeción para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play). Accesorios incluidos (honeycomb y cruceta de apantallamiento).
Advertencia: No apto para instalación en vertical.


Optic Spot - 2700K

Non Dimmable

05.5120.40
05.5120.14
05.5120.ER
05.5120.ES

Casambi

05.5120.40.CB
05.5120.14.CB
05.5120.ER.CB
05.5120.ES.CB



Luminous flux luminaire
479 lm

Beam Angle:	10°
h(m) E(lx)	D(m)
1 9243	0.18
2 2311	0.35
3 1027	0.53
4 578	0.70
5 370	0.88


Optic Spot - 3000K

Non Dimmable

05.5125.40
05.5125.14
05.5125.ER
05.5125.ES

Casambi

05.5125.40.CB
05.5125.14.CB
05.5125.ER.CB
05.5125.ES.CB



Luminous flux luminaire
531 lm

Beam Angle:	10°
h(m) E(lx)	D(m)
1 10246	0.18
2 2562	0.35
3 1138	0.53
4 640	0.70
5 410	0.88


Optic Medium - 2700K

Non Dimmable

05.5121.40
05.5121.14
05.5121.ER
05.5121.ES

Casambi

05.5121.40.CB
05.5121.14.CB
05.5121.ER.CB
05.5121.ES.CB



Luminous flux luminaire
441 lm

Beam Angle:	19°
h(m) E(lx)	D(m)
1 1989	0.34
2 497	0.67
3 221	1.01
4 124	1.34
5 80	1.68


Optic Medium - 3000K

Non Dimmable

05.5126.40
05.5126.14
05.5126.ER
05.5126.ES

Casambi

05.5126.40.CB
05.5126.14.CB
05.5126.ER.CB
05.5126.ES.CB



Luminous flux luminaire
489 lm

Beam Angle:	19°
h(m) E(lx)	D(m)
1 2206	0.34
2 551	0.67
3 245	1.01
4 138	1.34
5 88	1.68


Optic Flood - 2700K

Non Dimmable

05.5122.40
05.5122.14
05.5122.ER
05.5122.ES

Casambi

05.5122.40.CB
05.5122.14.CB
05.5122.ER.CB
05.5122.ES.CB



Luminous flux luminaire
364 lm

Beam Angle:	32°
h(m) E(lx)	D(m)
1 722	0.57
2 180	1.15
3 80	1.72
4 45	2.29
5 29	2.87


Optic Flood - 3000K

Non Dimmable

05.5127.40
05.5127.14
05.5127.ER
05.5127.ES

Casambi

05.5127.40.CB
05.5127.14.CB
05.5127.ER.CB
05.5127.ES.CB



Luminous flux luminaire
404 lm

Beam Angle:	32°
h(m) E(lx)	D(m)
1 801	0.57
2 200	1.15
3 89	1.72
4 50	2.29
5 32	2.87


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Find Me 2 by Jorge Herrera

Power LED 10,5W - 724 lm - 2700K/CRI90 / 781 lm - 3000K/CRI90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/ DC converter incorporated. Individual control via DALI protocol. Accessories included (honeycomb grid and protection bar).
Warning: Not suitable for vertical installation.


Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI. Accesorios incluidos (honeycomb y cruceta de apantallamiento).
Advertencia: No apto para instalación en vertical.

Optic Spot - 2700K

Dali

- 05.5120.40.DA
- 05.5120.14.DA
- 05.5120.ER.DA
- 05.5120.ES.DA





Luminous flux luminaire
479 lm


Beam Angle:	10°	
h(m)	E(lx)	D(m)
1	9243	0.18
2	2311	0.35
3	1027	0.53
4	578	0.70
5	370	0.88

Optic Spot - 3000K

Dali

- 05.5125.40.DA
- 05.5125.14.DA
- 05.5125.ER.DA
- 05.5125.ES.DA





Luminous flux luminaire
531 lm


Beam Angle:	10°	
h(m)	E(lx)	D(m)
1	10246	0.18
2	2562	0.35
3	1138	0.53
4	640	0.70
5	410	0.88

Optic Medium - 2700K

Dali

- 05.5121.40.DA
- 05.5121.14.DA
- 05.5121.ER.DA
- 05.5121.ES.DA





Luminous flux luminaire
441 lm


Beam Angle:	19°	
h(m)	E(lx)	D(m)
1	1989	0.34
2	497	0.67
3	221	1.01
4	124	1.34
5	80	1.68

Optic Medium - 3000K

Dali

- 05.5126.40.DA
- 05.5126.14.DA
- 05.5126.ER.DA
- 05.5126.ES.DA





Luminous flux luminaire
489 lm


Beam Angle:	19°	
h(m)	E(lx)	D(m)
1	2206	0.34
2	551	0.67
3	245	1.01
4	138	1.34
5	88	1.68

Optic Flood - 2700K

Dali

- 05.5122.40.DA
- 05.5122.14.DA
- 05.5122.ER.DA
- 05.5122.ES.DA





Luminous flux luminaire
364 lm


Beam Angle:	32°	
h(m)	E(lx)	D(m)
1	722	0.57
2	180	1.15
3	80	1.72
4	45	2.29
5	29	2.87

Optic Flood - 3000K

Dali

- 05.5127.40.DA
- 05.5127.14.DA
- 05.5127.ER.DA
- 05.5127.ES.DA






Luminous flux luminaire
404 lm


Beam Angle:	32°	
h(m)	E(lx)	D(m)
1	801	0.57
2	200	1.15
3	89	1.72
4	50	2.29
5	32	2.87

Atom 90 by Piero Lissoni

Power LED 5,5W - 432 lm - 2700K/CRI 90 / 446 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play).

Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play).

Optic Spot - 2700K


Non Dimmable

- 05.5140.40
- 05.5140.14
- 05.5140.ER
- 05.5140.ES

Casambi

- 05.5140.40.CB
- 05.5140.14.CB
- 05.5140.ER.CB
- 05.5140.ES.CB





Luminous flux luminaire
224 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	2564	0.25
2	641	0.51
3	285	0.76
4	160	1.02
5	103	1.27

Optic Spot - 3000K


Non Dimmable

- 05.5145.40
- 05.5145.14
- 05.5145.ER
- 05.5145.ES

Casambi

- 05.5145.40.CB
- 05.5145.14.CB
- 05.5145.ER.CB
- 05.5145.ES.CB





Luminous flux luminaire
247 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	2827	0.25
2	707	0.51
3	314	0.76
4	177	1.02
5	113	1.27

Optic Medium - 2700K


Non Dimmable

- 05.5141.40
- 05.5141.14
- 05.5141.ER
- 05.5141.ES

Casambi

- 05.5141.40.CB
- 05.5141.14.CB
- 05.5141.ER.CB
- 05.5141.ES.CB





Luminous flux luminaire
261 lm

Beam Angle:		25°
h(m)	E(lx)	D(m)
1	1353	0.45
2	338	0.89
3	150	1.34
4	85	1.79
5	54	2.23

Optic Medium - 3000K


Non Dimmable

- 05.5146.40
- 05.5146.14
- 05.5146.ER
- 05.5146.ES

Casambi

- 05.5146.40.CB
- 05.5146.14.CB
- 05.5146.ER.CB
- 05.5146.ES.CB





Luminous flux luminaire
289 lm

Beam Angle:		25°
h(m)	E(lx)	D(m)
1	1498	0.45
2	375	0.89
3	166	1.34
4	94	1.79
5	60	2.23


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Atom 90 by Piero Lissoni

Power LED 5,5W - 432 lm - 2700K/CRI 90 / 446 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual control via DALI protocol.


Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI.

Optic Spot - 2700K

Dali

05.5140.40.DA
05.5140.14.DA
05.5140.ER.DA
05.5140.ES.DA





Luminous flux luminaire
224 lm

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	2564	0.25
2	641	0.51
3	285	0.76
4	160	1.02
5	103	1.27

Optic Spot - 3000K

Dali

05.5145.40.DA
05.5145.14.DA
05.5145.ER.DA
05.5145.ES.DA





Luminous flux luminaire
247 lm

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	2827	0.25
2	707	0.51
3	314	0.76
4	177	1.02
5	113	1.27

Optic Medium - 2700K

Dali

05.5141.40.DA
05.5141.14.DA
05.5141.ER.DA
05.5141.ES.DA





Luminous flux luminaire
261 lm

Beam Angle: 25°


h(m)	E(lx)	D(m)
1	1353	0.45
2	338	0.89
3	150	1.34
4	85	1.79
5	54	2.23

Optic Medium - 3000K

Dali

05.5146.40.DA
05.5146.14.DA
05.5146.ER.DA
05.5146.ES.DA





Luminous flux luminaire
289 lm


Beam Angle: 25°


h(m)	E(lx)	D(m)
1	1498	0.45
2	375	0.89
3	166	1.34
4	94	1.79
5	60	2.23

Atom 120 by Piero Lissoni

Power LED 8W - 600 lm - 2700K/CRI 90 / 648 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play).

Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play).

Optic Spot - 2700K


Non Dimmable

- 05.5150.40
- 05.5150.14
- 05.5150.ER
- 05.5150.ES

Casambi

- 05.5150.40.CB
- 05.5150.14.CB
- 05.5150.ER.CB
- 05.5150.ES.CB





Luminous flux luminaire
224 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	2564	0.25
2	641	0.51
3	285	0.76
4	160	1.02
5	103	1.27

Optic Spot - 3000K


Non Dimmable

- 05.5155.40
- 05.5155.14
- 05.5155.ER
- 05.5155.ES

Casambi

- 05.5155.40.CB
- 05.5155.14.CB
- 05.5155.ER.CB
- 05.5155.ES.CB





Luminous flux luminaire
247 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	2827	0.25
2	707	0.51
3	314	0.76
4	177	1.02
5	113	1.27

Optic Medium - 2700K


Non Dimmable

- 05.5151.40
- 05.5151.14
- 05.5151.ER
- 05.5151.ES

Casambi

- 05.5151.40.CB
- 05.5151.14.CB
- 05.5151.ER.CB
- 05.5151.ES.CB





Luminous flux luminaire
261 lm

Beam Angle:		25°
h(m)	E(lx)	D(m)
1	1353	0.45
2	338	0.89
3	150	1.34
4	85	1.79
5	54	2.23

Optic Medium - 3000K


Non Dimmable

- 05.5156.40
- 05.5156.14
- 05.5156.ER
- 05.5156.ES

Casambi

- 05.5156.40.CB
- 05.5156.14.CB
- 05.5156.ER.CB
- 05.5156.ES.CB





Luminous flux luminaire
289 lm

Beam Angle:		25°
h(m)	E(lx)	D(m)
1	1498	0.45
2	375	0.89
3	166	1.34
4	94	1.79
5	60	2.23


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Atom 120 by Piero Lissoni

Power LED 8W - 600 lm - 2700K/CRI 90 / 648 lm - 3000K/CRI 90







LED projection lighting module for installation in the The Glowing Track system. Electronic DC/DC converter incorporated. Individual control via DALI protocol.


Módulo de iluminación LED de proyección para ser instalado en el sistema The Glowing Track. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI.

Optic Spot - 2700K

Dali

05.5150.40.DA
05.5150.14.DA
05.5150.ER.DA
05.5150.ES.DA





Luminous flux luminaire
224 lm

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	2564	0.25
2	641	0.51
3	285	0.76
4	160	1.02
5	103	1.27

Optic Spot - 3000K

Dali

05.5155.40.DA
05.5155.14.DA
05.5155.ER.DA
05.5155.ES.DA





Luminous flux luminaire
247 lm

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	2827	0.25
2	707	0.51
3	314	0.76
4	177	1.02
5	113	1.27

Optic Medium - 2700K

Dali

05.5151.40.DA
05.5151.14.DA
05.5151.ER.DA
05.5151.ES.DA





Luminous flux luminaire
261 lm

Beam Angle: 25°


h(m)	E(lx)	D(m)
1	1353	0.45
2	338	0.89
3	150	1.34
4	85	1.79
5	54	2.23

Optic Medium - 3000K

Dali

05.5156.40.DA
05.5156.14.DA
05.5156.ER.DA
05.5156.ES.DA






Luminous flux luminaire
289 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1498	0.45
2	375	0.89
3	166	1.34
4	94	1.79
5	60	2.23

MY CIRCUIT

DESIGNED BY MICHAEL ANASTASSIADES



Description
My Circuit, designed by Michael Anastassiades, is the first structure for indoor lighting consisting of a flexible profile that allows the drawing of continuous and completely free paths on the ceiling, combining linear sections with curves of various radii (from R 500 to R 3000 mm).
The system, for surface installation, can hold light modules, projectors with technical performance and suspended luminaires with an attractive decorative appearance.

Design, installation and assembly
To design a layout, it is essential to select and consecutively combine the fixing modules that will be joined to form a central spine that will be fixed to the ceiling, thus defining the shape of My Circuit. Depending on the desired number of luminaires, their position in the layout and their consumption requirements, modules can be added along the circuit where needed to power (48V) the system (a module for remote power supply and another module where the power supply unit is located in a decorative suspension box are available). These power supply modules have their own fixing segment which is added (at an intermediate position or at one end) to the central spine track.
Once the layout has been completed - and installed on the ceiling - the total length of the central spine track is obtained. The flexible profile is installed on this spine track, so that it can be adapted to its core shape and anchored on the ceiling in the desired position. The flexible profile externally embraces the central spine along the entire circuit and is inserted into the power adapters. The flexible profile's layout ends and segment joints - if present - are covered with the corresponding cover caps (end or intermediate).
The implementation of My Circuit is thus finally completed. Last but not least, the various luminaires and light modules are installed on the structure with their respective adapters.

Light Modules
The following light modules are available:
- MyCircuit Light Shadow Spot Ø30 / Ø45
- MyCircuit Spot Ø25 / Ø35

The following decorative luminaires are also available:
- MyCircuit Lines
- MyCircuit Disc
- MyCircuit Dome
- MyCircuit Sphere

Control Systems
My Circuit is available in on/off version and with Casambi wireless dimming system for individual control of each luminaire and/or light module.

Additional Information
My Circuit can only be installed on ceilings perpendicular to the vertical plane.
Use only a soft cloth to clean the system. For stubborn dirt, damp the cloth with water. Warning: do not use alcohol or other solvents.
The installation surface must be flat. When mounting, use suitable dowels and screws, depending on the ceiling material.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
Luminaire conforms to European Technical Standard EN60598-1 and secondary parts.

Descripción
MyCircuit, diseñado por Michael Anastassiades, es la primera estructura para iluminación de interiores compuesta por un perfil flexible que permite dibujar en el techo recorridos continuos y completamente libres, combinando formas de línea recta con curvas de diferente radio (de R 500 a R 3000 mm).
El sistema, de instalación en superficie, permite albergar módulos de luz proyectores de prestaciones técnicas y luminarias suspendidas de una atractiva presencia decorativa.

Diseño, instalación y montaje
Para diseñar un trazado se deben seleccionar y combinar de manera consecutiva los módulos de fijación que se unirán entre sí hasta dibujar una espina central que se fija en el techo y define la forma de MyCircuit.
Según el número de luminarias deseadas, su posición en el diseño de la estructura y sus requisitos de consumo, en los puntos necesarios del recorrido se añaden los módulos que permiten la alimentación 48V del sistema (existe un módulo para alimentación con equipo remoto y otro módulo donde el equipo de alimentación se ubica en una caja decorativa de suspensión). Estos módulos de alimentación cuentan con su propio segmento de fijación que se añade al recorrido de la espina central (en posición intermedia o en un extremo).
Completado el trazado -e instalado éste en el techo-, se obtiene la longitud total del recorrido de la espina central. Sobre ella se instalará el perfil flexible, a fin de que éste se amolde a su forma a modo de alma y quede anclado en la posición deseada en el techo. El perfil flexible abraza exteriormente la espina central en todo el trazado y se inserta en el interior de los adaptadores de alimentación. Los extremos de la configuración y las uniones de segmentos del perfil flexible -si existen- se cubren con las tapas embellecedoras correspondientes (final o intermedia).
De esta manera, la implementación de MyCircuit queda finalmente completada. Por último, las diferentes luminarias y módulos de luz se instalan en la estructura con sus respectivos adaptadores.

Módulos de luz
Existen los siguientes módulos de luz:
- MyCircuit Light Shadow Spot Ø30 / Ø45
- MyCircuit Spot Ø25 / Ø35

También están disponibles las siguientes luminarias decorativas:
- MyCircuit Lines
- MyCircuit Disc
- MyCircuit Dome
- MyCircuit Sphere

Sistemas de Control
My Circuit está disponible en versión on/off y con sistema de regulación inalámbrico Casambi para el control individual de cada luminaria y/o módulo de luz.

Información Adicional
La superficie de instalación debe ser plana. La instalación de My Circuit sólo es posible en techos perpendiculares a la vertical.
Para limpieza del sistema, utilizar exclusivamente un paño suave. En caso de suciedad más resistente, humedecer el paño con agua.
Advertencia: No emplear alcohol ni disolventes. En el montaje, emplear los tacos y tornillos adecuados, según el material del techo.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.


FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play

My Circuit Profile

☐ C5 White
C5 Blanco



Spots · My Circuit Profile

☐ C5 White
C5 Blanco

MY CIRCUIT
SPOT Ø25



☐

LIGHT SOURCE
POWER LED
Up to 4W
260 lm
2700K/CRI 90
262 lm
3000K/CRI 90

MY CIRCUIT
SPOT Ø35



☐

LIGHT SOURCE
LED ARRAY
Up to 8W
623 lm
2700K/CRI 90
641 lm
3000K/CRI 90

MY CIRCUIT
LIGHT SHADOW
SPOT Ø30



☐

LIGHT SOURCE
POWER LED
Up to 4W
256 lm
2700K/CRI 90
294 lm
3000K/CRI 90

MY CIRCUIT
LIGHT SHADOW
SPOT Ø45




☐

LIGHT SOURCE
LED ARRAY
Up to 8W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

Suspension Fixtures · My Circuit Profile

☐ C5 White
C5 Blanco

MY CIRCUIT DISC



☐

LIGHT SOURCE
TOP LED
42W
4310 lm
2700K/CRI 90
4515 lm
3000K/CRI 90


MY CIRCUIT LINES



☐

LIGHT SOURCE
TOP LED
2 x 23W
2 x 2360 lm
2700K/CRI 90
2 x 2470 lm
3000K/CRI 90

MY CIRCUIT DOME



☐


LIGHT SOURCE
TOP LED
40W
2110 lm
2700K / CRI 90
2296 lm
3000K / CRI 90

MY CIRCUIT SPHERE



☐


LIGHT SOURCE
TOP LED
40W
2278 lm
2700K / CRI 90
2467 lm
3000K / CRI 90



PHYSICAL CHARACTERISTICS	
Mounting	Surface
Voltage	48Vdc
Track Adapter	My Circuit Adapter
Height	40 mm
Width	24 mm
Length	8 / 15 / 20 m
CONTROL CHARACTERISTICS	
No Dim	✓
Casambi	✓

COMPATIBLE LIGHT MODULES

Accent Lighting



My Circuit Light Shadow Spot Ø30

My Circuit Spot Ø25

My Circuit Light Shadow Spot Ø45

My Circuit Spot Ø35

Diffused Lighting



My Circuit Dome

My Circuit Sphere


My Circuit Disc

My Circuit Lines

My Circuit - Installation Details / Instalación


1. Simply select, splice and install your chosen fixations on the ceiling to configure the My Circuit route.

1. Selecciona, empalma e instala en el techo las fijaciones elegidas para configurar el recorrido de My Circuit.




2. Cut the My Circuit profile segment to the required length. Press to insert the flexible track. Start at one end of the profile.

2. Corta el segmento de My Circuit profile en la longitud necesaria. Inserta por presión el carril flexible. La implementación debe empezar por un extremo.




3. Insert a Middle Cap accessory in intermediate cuts in the flexible track. At the end of the circuit, insert an End Cap.

3. En los cortes intermedios de carril flexible, aplica el accesorio Middle Cap. Al final del recorrido, el End Cap.




Middle Cap



End Cap


4. Install the power module (remote or suspended) in the desired position (intermediate or at one end). This module includes its own ceiling fixation.

4. En la posición deseada (intermedia o en un extremo), implementa el módulo de alimentación (remoto o suspendido). Este módulo incluye su fijación a techo propia.




5. Place the luminaires in the desired position using their My Circuit-specific adapters. See the installation instructions for more details.

5. Coloca las luminarias en la posición deseada, gracias a sus adaptadores específicos para My Circuit. Ver detalles en instrucciones de instalación.



Step 1



Step 2


HOW TO ORDER

1 DESIGN YOUR LAYOUT & SELECT MY CIRCUIT FIXATIONS


My Circuit Power Supply Fixation
L= 48 / Included in Power Supplies




My Circuit Fixation Straight
L= 250 / 1000 / 1500 / 2000 / 2500 / 3000




My Circuit Fixation Curve R 500
30° / 90° / 180°




My Circuit Fixation Curve R 750
22,5° / 45° / 90° / 135° / 180°




My Circuit Fixation Curve R 1000
15° / 45° / 90° / 135° / 180°




My Circuit Fixation Curve R 1500
9° / 45° / 90° / 135° / 180°




My Circuit Fixation Curve R 2000
7,5° / 45° / 90° / 135° / 180°




My Circuit Fixation Curve R 2500
5° / 45° / 90° / 135° / 180°



My Circuit Fixation Curve R 3000
5° / 45° / 90° / 135° / 180°



My Circuit Fixation Curve R Custom



2 SELECT & DEFINE PLACEMENT OF LIGHT MODULES IN YOUR LAYOUT

No DIM / Casambi

My Circuit Light Shadow Spot Ø30



S/M/F

My Circuit Light Shadow Pro Ø45



S/M/F

My Circuit Spot Ø25



S/M/F

My Circuit Spot Ø35



S/M/F

Casambi

My Circuit Dome



General lighting

My Circuit Sphere

General lighting

My Circuit Disc



General lighting

My Circuit Lines



General lighting

3 SELECT POWER SUPPLY & ADJUST YOUR FINAL LAYOUT

Power Supply Remote

Accessories

Feed Connector End Remote



Feed Connector Middle Remote



Drivers

320W



240W



150W



Suspended Power Supply

Power Supply End Suspended
240W / 150W



Power Supply Middle Suspended
240W / 150W



4 SELECT MY CIRCUIT PROFILE & ACCESSORIES

My Circuit Profile
L: 8000 / 15000 / 20000 mm





My Circuit Mounting Tool
(included)

Accessories

End Cap



Middle Cap




My Circuit Profiles

Flexible electromechanical profile available in various lengths, designed to be cut by the customer to the exact length required for each project. The profile is supplied in a spiral roll. It must be unrolled before installation.

Select the required length based on the sum of the lengths of: the straight fixations, the arcs of the curved fixations and the track inserts in the power adapter fixations (marked on its dimensional drawings).

Perfil electro-mecánico flexible disponible en varias longitudes, diseñado para ser cortado por el cliente en la longitud exacta deseada en cada proyecto. El perfil se sirve enrollado en espiral. Desplegar antes de instalar.

Seleccionar la longitud necesaria según la suma de longitudes de: las fijaciones rectas, los arcos de las fijaciones curvas y las inserciones del carril en las fijaciones de los adaptadores de alimentación (marcadas en sus dibujos dimensionales).




L: 8 m / 15 m / 20 m

CE

III

IP
20



L: 8000 mm
☐ 06.0330.C5

L: 15000 mm
☐ 06.0331.C5

L: 20000 mm
☐ 06.0332.C5



My Circuit Mounting Tool (included).


Herramienta de montaje de My Circuit (incluida).

My Circuit Fixation Straight

Straight fixture. Minimum section 250 mm. Kits of different lengths made up of several minimum splicable sections.

Fijación recta. Tramo mínimo de 250mm. Kits de diferentes longitudes compuestos por varios tramos mínimos empalmables.





L: 250 mm
06.0335.00

Kit L: 1000 mm (4x 06.0335.00)
06.0366.00

Kit L: 1500 mm (6x 06.0335.00)
06.0367.00

Kit L: 2000 mm (8x 06.0335.00)
06.0368.00

Kit L: 2500 mm (10x 06.0335.00)
06.0369.00

Kit L: 3000 mm (12x 06.0335.00)
06.0370.00


My Circuit Fixation Curve R 500


R 500 curved fixture. Minimum angle 30º. 90º and 180º kits are available, made up of several minimum splicable angles.

Fijación curva R 500. Ángulo mínimo de 30º. Kits de 90º y 180º disponibles, compuestos por varios ángulos mínimos empalmables.




Minimum angle 30º
Kit angles 90º / 180º






R 500 - 30º
L_a: 262 mm
06.0336.00



R 500 - Kit 90º (3x 06.0336.00)
L_a: 785 mm
L1: 500 mm L2: 500 mm
06.0371.00



R 500 - Kit 180º (6x 06.0336.00)
L_a: 1571 mm
L1: 500 mm L3: 1000 mm
06.0372.00


My Circuit Fixation Curve R 750


R 750 curved fixture. Minimum angle 22.5º. 45º, 90º, 135º and 180º kits available, made up of several minimum splicable angles.

Fijación curva R 750. Ángulo mínimo de 22,5º. Kits de 45º, 90º, 135º y 180º disponibles, compuestos por varios ángulos mínimos empalmables.



Minimum angle 22,5º
Kit angles 45º / 90º / 135º / 180º







R 750 - 22,5º
L_a: 294,5 mm
06.0337.00




R 750 - Kit 45º (2x 06.0337.00)
L_a: 589 mm
L1: 530 mm L3: 220 mm
06.0373.00



R 750 - Kit 90º (4x 06.0337.00)
L_a: 1178 mm
L2: 750 mm L4: 750 mm
06.0374.00



R 750 - Kit 135º (6x 06.0337.00)
L_a: 1767 mm
L2: 750 mm L5: 1280 mm
06.0375.00



R 750 - Kit 180º (8x 06.0337.00)
L_a: 2356 mm
L2: 750 mm L6: 1500 mm
06.0376.00


My Circuit Fixation Curve R 1000


R 1000 curved fixture. Minimum angle 15º. 45º, 90º, 135º and 180º kits available, made up of several minimum splicable angles.

Fijación curva R 1000. Ángulo mínimo de 15º. Kits de 45º, 90º, 135º y 180º disponibles, compuestos por varios ángulos mínimos empalmables.



Minimum angle 15º
Kit angles 45º / 90º / 135º / 180º







R 1000 - 15º
L_a: 262 mm
06.0338.00




R 1000 - Kit 45º (3x 06.0338.00)
L_a: 785 mm
L1: 707 mm L3: 293 mm
06.0377.00



R 1000 - Kit 90º (6x 06.0338.00)
L_a: 1570 mm
L2: 1000 mm L4: 1000 mm
06.0378.00



R 1000 - Kit 135º (9x 06.0338.00)
L_a: 2356 mm
L2: 1000 mm L5: 1707 mm
06.0379.00



R 1000 - Kit 180º (12x 06.0338.00)
L_a: 3141 mm
L2: 1000 mm L6: 2000 mm
06.0380.00


My Circuit Fixation Curve R 1500


R 1500 curved fixture. Minimum angle 9º. 45º, 90º, 135º and 180º kits available, made up of several minimum splicable angles.

Fijación curva R 1500. Ángulo mínimo de 9º. Kits de 45º, 90º, 135º y 180º disponibles, compuestos por varios ángulos mínimos empalmables.



Minimum angle 9º
Kit angles 45º / 90º / 135º / 180º







R 1500 - 9º
L_a: 236 mm
06.0339.00




R 1500 - Kit 45º (5x 06.0339.00)
L_a: 1178 mm
L1: 1061 mm L3: 439 mm
06.0381.00



R 1500 - Kit 90º (10x 06.0339.00)
L_a: 2356 mm
L2: 1500 mm L4: 1500 mm
06.0382.00



R 1500 - Kit 135º (15x 06.0339.00)
L_a: 3534 mm
L2: 1500 mm L5: 2561 mm
06.0383.00



R 1500 - Kit 180º (20x 06.0339.00)
AL: 4712 mm
L2: 1500 mm L6: 3000 mm
06.0384.00


My Circuit Fixation Curve R 2000


R 2000 curved fixture. Minimum angle 7.5º. 45º, 90º, 135º and 180º kits available, made up of several minimum splicable angles.

Fijación curva R 2000. Ángulo mínimo de 7,5º. Kits de 45º, 90º, 135º y 180º disponibles, compuestos por varios ángulos mínimos empalmables.



Minimum angle 7,5º
Kit angles 45º / 90º / 135º / 180º







R 2000 - 7,5º
L_a: 262 mm
06.0340.00




R 2000 - Kit 45º (6x 06.0340.00)
L_a: 1571 mm
L1: 1414 mm L3: 586 mm
06.0385.00



R 2000 - Kit 90º (12x 06.0340.00)
L_a: 3142 mm
L2: 2000 mm L4: 2000 mm
06.0386.00



R 2000 - Kit 135º (18x 06.0340.00)
L_a: 4712 mm
L2: 2000 mm L5: 3414 mm
06.0387.00




R 2000 - Kit 180º (24x 06.0340.00)
L_a: 6283 mm
L2: 2000 mm L6: 4000 mm
06.0388.00

My Circuit Fixation Curve R 2500

R 2500 curved fixture. Minimum angle 5º. 45º, 90º, 135º and 180º kits available, made up of several minimum splicable angles.

Fijación curva R 2500. Ángulo mínimo de 5º. Kits de 45º, 90º, 135º y 180º disponibles, compuestos por varios ángulos mínimos empalmables.







R 2500 - 5º
L_a: 218 mm
06.0341.00



R 2500 - Kit 45º (9x 06.0341.00)
L_a: 1963 mm
L1: 1768 mm L3: 732 mm
06.0389.00





R 2500 - Kit 90º (18x 06.0341.00)
L_a: 3927 mm
L2: 2500 mm L4: 2500 mm
06.0390.00



R 2500 - Kit 135º (27x 06.0341.00)
L_a: 5890 mm
L2: 2500 mm L5: 4268 mm
06.0391.00

Minimum angle 5º
Kit angles 45º / 90º / 135º / 180º






R 2500 - Kit 180º (36x 06.0341.00)
L_a: 7854 mm
L2: 2500 mm L6: 5000 mm
06.0392.00

My Circuit Fixation Curve R 3000

R 3000 curved fixture. Minimum angle 5º. 45º, 90º, 135º and 180º kits available, made up of several minimum splicable angles.

Fijación curva R 3000. Ángulo mínimo de 5º. Kits de 45º, 90º, 135º y 180º disponibles, compuestos por varios ángulos mínimos empalmables.







R 3000 - 5º
L_a: 262 mm
06.0342.00



R 3000 - Kit 45º (9x 06.0342.00)
L_a: 2356 mm
L1: 2121 mm L3: 879 mm
06.0393.00





R 3000 - Kit 90º (18x 06.0342.00)
L_a: 4712 mm
L2: 3000 mm L4: 3000 mm
06.0394.00



R 3000 - Kit 135º (27x 06.0342.00)
L_a: 7069 mm
L2: 3000 mm L5: 5121 mm
06.0395.00

Minimum angle 5 º
Kit angles 45º / 90º / 135º / 180º











R 3000 - Kit 180º (36x 06.0342.00)
L_a: 9425 mm
L2: 3000 mm L6: 6000 mm
06.0396.00

MY CIRCUIT — ACCESSORIES




Accessories / Accesorios

End trim cap. For use at the ends of the My Circuit circuit (only if necessary).	Tapa embellecedora final. Para aplicar en los extremos del recorrido de My Circuit (sólo si es necesario).			06.0350.C5
Intermediate trim cap. For use on cuts in the My Circuit flexible track (only if necessary).	Tapa embellecedora intermedia. Para aplicar en los cortes del carril flexible de My Circuit (sólo si es necesario).			06.0351.C5
Accessory for closed loop installations. To join the ends of the My Circuit route (Mandatory for this type of installation).	Accesorio para instalaciones en circuito cerrado. Para juntar los extremos del recorrido de My Circuit (Obligatorio para este tipo de instalación).			06.0343.00
Profile fixing tool. To ensure that the profile is clipped along its entire length once installed.	Herramienta para fijar el perfil. Para asegurar que el perfil esta clipado en toda la longitud una vez instalado.			08.1042.00



Remote Drivers Accessories

Accessory for connecting My Circuit to the remote power supply. Driver not included. For use at the ends of the circuit (if necessary).	Accesorio para la conexión de My Circuit a la alimentación remota. Driver no incluido. Para aplicar en los extremos del recorrido (si es necesario).			06.0352.C5
Accessory for connecting My Circuit to the remote power supply. Driver not included. For use in intermediate positions along the circuit (if necessary).	Accesorio para la conexión de My Circuit a la alimentación remota. Driver no incluido. Para aplicar en posición intermedia del recorrido (si es necesario).			06.0353.C5

Remote Drivers

Constant voltage power supply 48V - 320W, 100 -110V / 120/277V - 50/60Hz.	Fuente de alimentación de tensión constante 48V - 320W, 100-110V / 120/277V - 50/60Hz.			60.9741
Constant voltage power supply 48V - 240W, 100 -110V / 120/277V - 50/60Hz.	Fuente de alimentación de tensión constante 48V - 240W, 100-110V / 120/277V - 50/60Hz.			60.8723
Constant voltage power supply 48V - 150W, 100-110V / 120/277V - 50/60Hz.	Fuente de alimentación de tensión constante 48V - 150W, 100-110V / 120/277V - 50/60Hz.			60.9781


Control Units / Unidades de Control

Wireless Dimmer Bridge. From 1-10V to Casambi. For remote installation. See product specifications in the Flos Control manual.	Pasarela de regulación inalámbrica. De 1-10V a Casambi. Para instalación remota. Consulte las especificaciones de producto en el manual Flos Control.			DIM 1-10V >> Casambi 08.0824.14
Wireless dimming gateway Casambi ↔ DALI. For remote installation. Refer to the product specifications in the Flos Control manual.	Pasarela de regulación inalámbrica Casambi ↔ DALI. Para instalación remota. Consulte las especificaciones del producto en el manual Flos Control.			DIM Casambi << >> DALI 08.0961.00

Suspended Drivers

Accessory for connecting My Circuit to the suspended power supply. Driver included (48V). For use at the ends of the circuit (if necessary).
My Circuit Power Supply Fixation, included.

Accesorio para la conexión de My Circuit a la alimentación suspendida. Driver incluido (48V). Para aplicar en los extremos del recorrido (si es necesario).
Fijación de la fuente de alimentación de My Circuit (incluida).




240W · 100-240Vac
240W · 180-240Vac
180W · 100-180Vac
06.0354.C5

150W · 100-240Vac
150W · 180-240Vac
105W · 100-180Vac
06.0403.C5

Accessory for connecting My Circuit to the suspended power supply. Driver included (48V). For use in intermediate positions along the circuit (if necessary).
My Circuit Power Supply Fixation, included.

Accesorio para la conexión de My Circuit a la alimentación suspendida. Driver incluido (48V). Para aplicar en posición intermedia del recorrido (si es necesario).
Fijación de la fuente de alimentación de My Circuit (incluida).



240W · 100-240Vac
240W · 180-240Vac
180W · 100-180Vac
06.0355.C5

150W · 100-240Vac
150W · 180-240Vac
105W · 100-180Vac
06.0404.C5

Drivers & Track Configuration Requirements / Requisitos de configuración de los drivers y de los carriles

Maximum length of secondary cable (section 1.5mm²): 5 metres from the driver to the track.
Maximum track length 20 metres.

Longitud máxima del cable secundario (seccion 1.5mm²):
5 metros desde el driver al track.
Longitud máxima track 20 metros.

		Remote Drivers			Suspended Drivers	
Light Modules	Fixture W	150W 60.9781	240W 60.8723	320W 60.9741	150W 06.0403.C5 / 06.0404.C5	240W 06.0354.C5 / 06.0355.C5
	3,5W	42 units	68 units	91 units	42 units	68 units
	4W	32 units	50 units	68 units	32 units	50 units
	7,5W	20 units	32 units	42 units	20 units	32 units
	8W	16 units	25 units	34 units	16 units	25 units
	40W	3 units	5 units	6 units	3 units	5 units
	40W	3 units	5 units	6 units	3 units	5 units
	42W	3 units	5 units	6 units	3 units	5 units
	44W	3 units	4 units	6 units	3 units	4 units

Configuration examples / Ejemplos de configuración


Example of incorrect configuration:
Distance KO.


Ejemplo de configuración incorrecta:
Distancia KO.

Example of correct configuration:
Distance OK.


Ejemplo de configuración correcta:
Distancia OK.


Power Suply - Position End





Power Suply - Position Middle







Example of incorrect configuration:
Distance OK / Power KO.

Ejemplo de configuración incorrecta:
Distancia OK / Power KO.

Example of correct configuration:
Distance OK / Power OK.

Ejemplo de configuración correcta:
Distancia OK / Power OK.







My Circuit Spot Ø25

Power LED Non Dimmable 3,5W - 260 lm - 2700K/CRI 90 / 262 lm - 3000K/ CRI 90
Power LED Casambi 4W - 260 lm - 2700K/CRI 90 / 262 lm - 3000K/ CRI 90







LED lighting module for installation in the My Circuit system. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product. Casambi version for wireless control. Casambi, maximum distance between fixtures: 12m.
* Ask us about bespoke track connector arm lengths.


Módulo de iluminación LED para ser instalado en el sistema My Circuit. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión al carril queda perfectamente enrasado con el producto. Casambi para control inalámbrico. Casambi, distancia máxima entre luminarias: 12m.
* Para longitud personalizada del brazo de conexión a carril, consultar.

Optic Spot - 2700K

Non Dimmable
☐ 05.2900.C5

Casambi
☐ 05.2920.C5





Luminous flux luminaire
132 lm

Beam Angle: 11°


h(m)	E(lx)	D(m)
1	2393	0.18
2	598	0.37
3	266	0.55
4	150	0.74
5	96	0.92

Optic Spot - 3000K

Non Dimmable
☐ 05.2905.C5

Casambi
☐ 05.2925.C5





Luminous flux luminaire
115 lm

Beam Angle: 13°


h(m)	E(lx)	D(m)
1	1619	0.22
2	405	0.44
3	180	0.66
4	101	0.88
5	65	1.10

Optic Medium - 2700K

Non Dimmable
☐ 05.2901.C5

Casambi
☐ 05.2921.C5





Luminous flux luminaire
145 lm

Beam Angle: 22°


h(m)	E(lx)	D(m)
1	1079	0.39
2	270	0.77
3	120	1.16
4	67	1.54
5	43	1.93

Optic Medium - 3000K

Non Dimmable
☐ 05.2906.C5

Casambi
☐ 05.2926.C5





Luminous flux luminaire
148 lm

Beam Angle: 21°


h(m)	E(lx)	D(m)
1	1202	0.37
2	300	0.75
3	134	1.12
4	75	1.49
5	48	1.86

Optic Flood - 2700K

Non Dimmable
☐ 05.2902.C5

Casambi
☐ 05.2922.C5





Luminous flux luminaire
135 lm

Beam Angle: 35°


h(m)	E(lx)	D(m)
1	397	0.63
2	99	1.26
3	44	1.89
4	25	2.51
5	16	3.14

Optic Flood - 3000K

Non Dimmable
☐ 05.2907.C5

Casambi
☐ 05.2927.C5





Luminous flux luminaire
142 lm


Beam Angle: 32°


h(m)	E(lx)	D(m)
1	444	0.58
2	111	1.16
3	49	1.75
4	28	2.33
5	18	2.91

My Circuit Spot Ø35

LED Array Non Dimmable 7,5W - 623 lm - 2700K/CRI 90 / 641 lm - 3000K/ CRI 90
LED Array Casambi 8W - 623 lm - 2700K/CRI 90 / 641 lm - 3000K/ CRI 90







LED lighting module for installation in the My Circuit system. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product. Casambi version for wireless control. Casambi, maximum distance between fixtures: 6m.
* Ask us about bespoke track connector arm lengths.


Módulo de iluminación LED para ser instalado en el sistema My Circuit. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión al carril queda perfectamente enrasado con el producto. Casambi para control inalámbrico. Casambi, distancia máxima entre luminarias: 6m.
* Para longitud personalizada del brazo de conexión a carril, consultar.

Optic Spot - 2700K

Non Dimmable
☐ 05.2910.C5

Casambi
☐ 05.2930.C5





Luminous flux luminaire
487 lm


Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	6779	0.26
2	1695	0.51
3	753	0.77
4	424	1.02
5	271	1.28

Optic Spot - 3000K

Non Dimmable
☐ 05.2915.C5

Casambi
☐ 05.2935.C5





Luminous flux luminaire
507 lm


Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	7037	0.26
2	1759	0.52
3	782	0.78
4	440	1.04
5	281	1.30

Optic Medium - 2700K

Non Dimmable
☐ 05.2911.C5

Casambi
☐ 05.2931.C5





Luminous flux luminaire
525 lm


Beam Angle:	19°	
h(m)	E(lx)	D(m)
1	4936	0.34
2	1234	0.68
3	548	1.02
4	308	1.36
5	197	1.70

Optic Medium - 3000K

Non Dimmable
☐ 05.2916.C5

Casambi
☐ 05.2936.C5





Luminous flux luminaire
548 lm


Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	4968	0.35
2	1242	0.69
3	552	1.04
4	311	1.39
5	199	1.73

Optic Flood - 2700K

Non Dimmable
☐ 05.2912.C5

Casambi
☐ 05.2932.C5





Luminous flux luminaire
538 lm


Beam Angle:	30°	
h(m)	E(lx)	D(m)
1	1970	0.54
2	492	1.09
3	219	1.63
4	123	2.18
5	79	2.72

Optic Flood - 3000K

Non Dimmable
☐ 05.2917.C5

Casambi
☐ 05.2937.C5






Luminous flux luminaire
559 lm


Beam Angle:	31°	
h(m)	E(lx)	D(m)
1	1983	0.56
2	496	1.11
3	220	1.67
4	124	2.22
5	79	2.78

My Circuit Light Shadow Spot Ø30

Power LED Non Dimmable 3,5W - 276 lm - 2700K/CRI 90 / 294 lm - 3000K/ CRI 90
Power LED Casambi 4W - 276 lm - 2700K/CRI 90 / 294 lm - 3000K/ CRI 90







LED lighting module for installation in the My Circuit system. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product. Casambi version for wireless control. Casambi, maximum distance between fixtures: 12m.
* Ask us about bespoke track connector arm lengths.


Módulo de iluminación LED para ser instalado en el sistema My Circuit. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión al carril queda perfectamente enrasado con el producto. Casambi para control inalámbrico. Casambi, distancia máxima entre luminarias: 12m.
* Para longitud personalizada del brazo de conexión a carril, consultar.

Optic Spot - 2700K

Non Dimmable
☐ 05.2950.C5A

Casambi
☐ 05.2970.C5A





Luminous flux luminaire
234 lm

Beam Angle: 11°


h(m)	E(lx)	D(m)
1	3740	0.20
2	935	0.40
3	416	0.60
4	234	0.80
5	150	1.00

Optic Spot - 3000K

Non Dimmable
☐ 05.2955.C5A

Casambi
☐ 05.2975.C5A





Luminous flux luminaire
249 lm

Beam Angle: 11°


h(m)	E(lx)	D(m)
1	3980	0.20
2	995	0.40
3	442	0.60
4	249	0.80
5	159	1.00

Optic Medium - 2700K

Non Dimmable
☐ 05.2951.C5A

Casambi
☐ 05.2971.C5A





Luminous flux luminaire
238 lm

Beam Angle: 22°


h(m)	E(lx)	D(m)
1	1664	0.39
2	416	0.78
3	185	1.17
4	104	1.56
5	67	1.95

Optic Medium - 3000K

Non Dimmable
☐ 05.2956.C5A

Casambi
☐ 05.2976.C5A





Luminous flux luminaire
253 lm

Beam Angle: 22°


h(m)	E(lx)	D(m)
1	1769	0.39
2	442	0.78
3	197	1.17
4	111	1.56
5	71	1.95

Optic Flood - 2700K

Non Dimmable
☐ 05.2952.C5A

Casambi
☐ 05.2972.C5A





Luminous flux luminaire
228 lm

Beam Angle: 29°


h(m)	E(lx)	D(m)
1	884	0.52
2	221	1.04
3	98	1.57
4	55	2.09
5	35	2.61

Optic Flood - 3000K

Non Dimmable
☐ 05.2957.C5A

Casambi
☐ 05.2977.C5A





Luminous flux luminaire
243 lm

Beam Angle: 29°


h(m)	E(lx)	D(m)
1	942	0.52
2	235	1.04
3	105	1.57
4	59	2.09
5	38	2.61

Optic Wide Flood - 2700K

Non Dimmable
☐ 05.2953.C5A

Casambi
☐ 05.2973.C5A





Luminous flux luminaire
227 lm

Beam Angle: 43°


h(m)	E(lx)	D(m)
1	484	0.80
2	121	1.59
3	54	2.39
4	30	3.19
5	19	3.99

Optic Wide Flood - 3000K

Non Dimmable
☐ 05.2958.C5A

Casambi
☐ 05.2978.C5A





Luminous flux luminaire
242 lm


Beam Angle: 43°


h(m)	E(lx)	D(m)
1	516	0.80
2	129	1.59
3	57	2.39
4	32	3.19
5	21	3.99

My Circuit Light Shadow Spot Ø45

LED Array Non Dimmable 7,5W - 799 lm - 2700K/CRI 90 / 844 lm - 3000K/ CRI 90
LED Array Casambi 8W - 799 lm - 2700K/CRI 90 / 844 lm - 3000K/ CRI 90







LED lighting module for installation in the My Circuit system. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product. Casambi version for wireless control. Casambi, maximum distance between fixtures: 12m.
* Ask us about bespoke track connector arm lengths.


Módulo de iluminación LED para ser instalado en el sistema My Circuit. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión al carril queda perfectamente enrasado con el producto. Casambi para control inalámbrico. Casambi, distancia máxima entre luminarias: 12m.
* Para longitud personalizada del brazo de conexión a carril, consultar.

Optic Spot - 2700K

Non Dimmable
☐ 05.2960.C5

Casambi
☐ 05.2980.C5

15°



Luminous flux luminaire
650 lm


Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	8012	0.27
2	2003	0.54
3	890	0.80
4	501	1.07
5	320	1.34

Optic Spot - 3000K

Non Dimmable
☐ 05.2965.C5

Casambi
☐ 05.2985.C5

15°



Luminous flux luminaire
686 lm


Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	8456	0.27
2	2114	0.54
3	940	0.80
4	528	1.07
5	338	1.34

Optic Medium - 2700K

Non Dimmable
☐ 05.2961.C5

Casambi
☐ 05.2981.C5

21°



Luminous flux luminaire
645 lm


Beam Angle:	21°	
h(m)	E(lx)	D(m)
1	5163	0.36
2	1291	0.73
3	574	1.09
4	323	1.46
5	207	1.82

Optic Medium - 3000K

Non Dimmable
☐ 05.2966.C5

Casambi
☐ 05.2986.C5

21°



Luminous flux luminaire
682 lm


Beam Angle:	21°	
h(m)	E(lx)	D(m)
1	5459	0.36
2	1365	0.73
3	607	1.09
4	341	1.46
5	218	1.82

Optic Flood - 2700K

Non Dimmable
☐ 05.2962.C5

Casambi
☐ 05.2982.C5

31°



Luminous flux luminaire
646 lm


Beam Angle:	31°	
h(m)	E(lx)	D(m)
1	2296	0.56
2	574	1.11
3	255	1.67
4	144	2.22
5	92	2.78

Optic Flood - 3000K

Non Dimmable
☐ 05.2967.C5

Casambi
☐ 05.2987.C5

31°





Luminous flux luminaire
682 lm


Beam Angle:	31°	
h(m)	E(lx)	D(m)
1	2424	0.56
2	606	1.11
3	269	1.67
4	152	2.22
5	97	2.78

My Circuit Disc

TOP LED 42W - 4310 lm - 2700K/CRI 90 / 42W - 4515 lm - 3000K/CRI 90








Suspended luminaire for installation in the My Circuit system. Diffused Down emission. Adjustable suspension height. Casambi version for wireless control.

Luminaria de suspensión para ser instalada en el sistema My Circuit. Emisión difusa Down. Altura de suspensión ajustable. Casambi para control inalámbrico.

2700K
Casambi
☐ 05.2990.C5






Luminous flux luminaire
2194 lm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	805	2.87
2	201	5.73
3	89	8.60
4	50	11.46
5	32	14.33

3000K
Casambi
☐ 05.2992.C5





Luminous flux luminaire
2298 lm


Beam Angle: 110°


h(m)	E(lx)	D(m)
1	805	2.87
2	201	5.73
3	89	8.60
4	50	11.46
5	32	14.33

My Circuit Lines

TOP LED 2 x 23W - 2 x 2360 lm - 2700K/CRI 90 / 2 x 23W - 2 x 2470 lm - 3000K/CRI 90








Suspended luminaire for installation in the My Circuit system. Lateral, independently adjustable diffuse emission (by rotating on the axis of the product) for each line. Adjustable suspension height. In principle, we recommend a suspension distance in order to achieve the same functionality as a freestanding luminaire. Casambi version for wireless control.

Luminaria de suspensión para ser instalada en el sistema My Circuit. Emisión difusa lateral de orientación independiente (por giro sobre el eje del producto) en cada línea. Altura de suspensión ajustable. Conceptualmente, se recomienda una distancia de suspensión para cumplir la funcionalidad equivalente a la de una luminaria de pie. Casambi para control inalámbrico.

2700K
Casambi
☐ 05.2991.C5






Luminous flux luminaire
2 x 1393 lm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	296	3.01
2	74	6.03
3	33	9.04
4	19	12.06
5	12	15.07

3000K
Casambi
☐ 05.2993.C5






Luminous flux luminaire
2 x 1460 lm


Beam Angle: 110°


h(m)	E(lx)	D(m)
1	296	3.01
2	74	6.03
3	33	9.04
4	19	12.06
5	12	15.07

My Circuit Dome

TOP LED 40W - 2110 lm - 2700K/CRI 90 / 40W - 2296 lm - 3000K/CRI 90








Suspended luminaire for installation in the My Circuit system. Diffused downlight emission. Adjustable suspension height. Casambi version for wireless control.

Luminaria de suspensión para ser instalada en el sistema My Circuit. Emisión difusa downlight. Altura de suspensión ajustable. Versión Casambi para control inalámbrico.

2700K
Casambi
☐ 05.2994.C5






Luminous flux luminaire
2110 lm

Beam Angle:		110°
h(m)	E(lx)	D(m)
1	754	2.84
2	189	5.68
3	84	8.51
4	47	11.35
5	30	14.19

3000K
Casambi
☐ 05.2996.C5






Luminous flux luminaire
2296 lm

Beam Angle:		110°
h(m)	E(lx)	D(m)
1	821	2.84
2	205	5.68
3	91	8.51
4	51	11.35
5	33	14.19

My Circuit Sphere

TOP LED 40W - 2278 lm - 2700K/CRI 90 / 40W - 2467 lm - 3000K/CRI 90






IP 20 · LED INCL · 5,70 Kg · 1 - 100%

Suspended luminaire for installation in the My Circuit system. Diffused omnidirectional emission. Adjustable suspension height. Casambi version for wireless control.

Luminaria de suspensión para ser instalada en el sistema My Circuit. Emisión difusa omnidireccional. Altura de suspensión ajustable. Versión Casambi para control inalámbrico.

2700K
Casambi
☐ 05.2995.C5




Luminous flux luminaire
2268 lm

Beam Angle:

h(m)	E(lx)	D(m)
1	0	
2	0	
3	0	
4	0	
5	0	

3000K
Casambi
☐ 05.2997.C5



Luminous flux luminaire
2457 lm

Beam Angle:

h(m)	E(lx)	D(m)
1	0	
2	0	
3	0	
4	0	
5	0	

Decorative Collection


MY DOME



MY SPHERE



MY DISC




MY LINES



*Refer to Decorative Catalogue / Ver Catálogo Decorativo.

BELT

DESIGNED BY RONAN&ERWAN BOUROULLEC



LIGHT SOURCE
TOP LED
27,5W/m

915 lm/m Up
2000 lm/m Down
2700K/CRI 95

1050 lm/m Up
2450 lm/m Down
3000K/CRI 95

Leather

GN Green



18 Natural Leather



14 Black



Fabric

GO Grey olive



M5 Copper Brown



Description
This iconic profile for suspended installation features a leather or textile Surface developed specifically for Flos Architectural to respond to the needs of safety and cleanliness in public and private environments.
Belt is pure flexibility, a sinuous line that creates a balance between the softness of leather and the rigidity of aluminium. The soft part is represented by the connection to the electrical network, while the rigid parts correspond to the light source of the long lines of light.
Each profile is equipped with integrated direct and indirect lighting, and each light source can be controlled individually via remote control.
The product is installed with the use of straps to hang the lighting profile, sliding the straps through dedicated metal clasps that act as hooks on the ceiling. Each strap may be regulated to match the shape of the environment.
A special microconnector integrated into the terminal of the lighting profile allows for electrical connection through a simple snap. The electrical connection is hidden within the strap, which supports the composition.
Profiles available with 2- and 3-m lengths in leather finishes (black, natural leather and green), as well as in textile finishes (grey olive and copper brown).

Optic system
Linear Up&Down profile – direct/indirect emission: General Lighting.

Power Supply
The system may be powered only with remote power sources not included with the profiles. Recommended drivers sold separately.

Regulation System
Dimmable system with 1–10 V, DALI, or CASAMBI controller integrated inside the fixture. Individual direct and indirect emission may be regulated through a Casambi or DALI control system.

Additional Information
Electrical system powered at 48V.
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Este perfil icónico para instalación suspendida se caracteriza por una cobertura de cuero o textil desarrolladas a medida para Flos Architectural con el fin de responder a las exigencias de seguridad y limpieza de entornos públicos y privados.
Belt es pura flexibilidad, una línea sinuosa cuya característica es el equilibrio entre la ductilidad del cuero y la rigidez del aluminio. El elemento blando está representado por la conexión a la red eléctrica, mientras que las partes rígidas corresponden a las fuentes luminosas de las largas líneas de luz.
Cada perfil está dotado de iluminación integrada directa e indirecta y se puede controlar cada emisión de forma individual mediante el control remoto de la instalación.
La instalación del producto se realiza mediante tirantes que sirven para suspender el perfil luminoso haciendo que se deslice a través de hebillas metálicas específicas que hacen las veces de ganchos de techo. Cada tirante puede ser ajustado para respetar la conformación del entorno.
Gracias a un microconector especial integrado en el terminal del perfil luminoso permite hacer la conexión eléctrica con un simple clic. El elemento de conexión está escondido en el interior de la trabilla, que actúa como una suspensión para sujetar la composición.
Perfiles disponibles con longitudes de 2 y 3 m, con acabados en cuero (negro, cuero natural y verde) y en textil (grey olive y copper brown).

Sistema Óptico
Perfil lineal Up&Down - emisión directa/indirecta: Iluminación general.

Unidades de Alimentación
El sistema solo se puede alimentar con una fuente de alimentación remota que no se incluye con los perfiles. Los drivers recomendados se deben encargar por separado.


Sistema de Regulación
Sistema regulable con controlador de 1-10 V, DALI o CASAMBI integrado en la luminaria. La regulación individual de la emisión directa y la indirecta solo se puede gestionar a través de un control Casambi o DALI.


Información Adicional
Sistema eléctrico alimentado a 48V.
Índice de protección IP20.
Instalable sobre superficies normalmente inflamables.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Belt

Top LED 27,5W/m - 915 lm/m UP - 2000 lm/m DOWN - 2700K/CRI 95 / 27,5W/m - 1050 lm/m UP - 2450 lm/m DOWN - 3000K/CRI 95





Electromechanical profile for interior use with integrated linear lighting for suspended installation available with 2 or 3 m lengths. Installation via suspension straps on the ceiling and remote power kit, to be ordered separately. Up&Down system controlled via DALI or CASAMBI individually and via 1-10V all together (Broadcast).

Perfil electromecánico de interiores con iluminación rectilínea integrada para instalación suspendida disponible con una longitud de 2 a 3 m. Instalación a través de correas de suspensión en el techo y kit de alimentación remoto, que se deben pedir por separado. Sistema Up&Down controlado vía DALI o CASAMBI individualmente y vía 1-10V conjuntamente (Broadcast).

2700K

L: 2000 mm

Dali Version


03.8500.GN.DA
03.8500.18.DA
03.8500.14.DA
03.8500.GO.DA
03.8500.M5.DA

1-10V (Broadcast)

03.8500.GN.1V
03.8500.18.1V
03.8500.14.1V
03.8500.GO.1V
03.8500.M5.1V

Casambi integrated

03.8500.GN.CB
03.8500.18.CB
03.8500.14.CB
03.8500.GO.CB
03.8500.M5.CB



Luminous flux luminaire
1694 lm

Beam Angle:		60°
h(m)	E(lx)	D(m)
1	517	1.16
2	129	2.31
3	57	3.47
4	32	4.63
5	21	5.79

3000K

L: 2000 mm

Dali Version


03.8505.GN.DA
03.8505.18.DA
03.8505.14.DA
03.8505.GO.DA
03.8505.M5.DA

1-10V (Broadcast)

03.8505.GN.1V
03.8505.18.1V
03.8505.14.1V
03.8505.GO.1V
03.8505.M5.1V

Casambi integrated

03.8505.GN.CB
03.8505.18.CB
03.8505.14.CB
03.8505.GO.CB
03.8505.M5.CB



Luminous flux luminaire
1915 lm

Beam Angle:		60°
h(m)	E(lx)	D(m)
1	584	1.16
2	146	2.31
3	65	3.47
4	37	4.63
5	23	5.79

2700K

L: 3000 mm

Dali Version


03.8501.GN.DA
03.8501.18.DA
03.8501.14.DA
03.8501.GO.DA
03.8501.M5.DA

1-10V (Broadcast)

03.8501.GN.1V
03.8501.18.1V
03.8501.14.1V
03.8501.GO.1V
03.8501.M5.1V

Casambi integrated

03.8501.GN.CB
03.8501.18.CB
03.8501.14.CB
03.8501.GO.CB
03.8501.M5.CB



Luminous flux luminaire
2542 lm

Beam Angle:		60°
h(m)	E(lx)	D(m)
1	776	1.16
2	194	2.31
3	86	3.47
4	48	4.63
5	31	5.79

3000K

L: 3000 mm

Dali Version


03.8506.GN.DA
03.8506.18.DA
03.8506.14.DA
03.8506.GO.DA
03.8506.M5.DA

1-10V (Broadcast)

03.8506.GN.1V
03.8506.18.1V
03.8506.14.1V
03.8506.GO.1V
03.8506.M5.1V

Casambi integrated


03.8506.GN.CB
03.8506.18.CB
03.8506.14.CB
03.8506.GO.CB
03.8506.M5.CB



Luminous flux luminaire
2872 lm

Beam Angle:		60°
h(m)	E(lx)	D(m)
1	877	1.16
2	219	2.31
3	97	3.47
4	55	4.63
5	35	5.79

BELT — INSTALLATION



Accessories / Accesorios

Suspension strap. 2 units.

Correa de suspensión. 2 unidades.


L: 1000 mm
- 03.8510.GN
- 03.8510.18
- 03.8510.14
- 03.8510.GO
- 03.8510.M5

L: 1500 mm
- 03.8513.GN
- 03.8513.18
- 03.8513.14
- 03.8513.GO
- 03.8513.M5

L: 2000 mm
- 03.8511.GN
- 03.8511.18
- 03.8511.14
- 03.8511.GO
- 03.8511.M5

L: 2500 mm
- 03.8514.GN
- 03.8514.18
- 03.8514.14
- 03.8514.GO
- 03.8514.M5

L: 3000 mm
- 03.8512.GN
- 03.8512.18
- 03.8512.14
- 03.8512.GO
- 03.8512.M5




48-V power loop.

Loop de alimentación de 48V.

L: 1500 mm
- 03.8520.GN
- 03.8520.18
- 03.8520.14
- 03.8520.GO
- 03.8520.M5







L: 2500 mm
- 03.8521.GN
- 03.8521.18
- 03.8521.14
- 03.8521.GO
- 03.8521.M5

L: 3500 mm
- 03.8522.GN
- 03.8522.18
- 03.8522.14
- 03.8522.GO
- 03.8522.M5





Suspension Strap (mm)	Power Loop (mm)
1000	1500
1500	2500
2000	
2500	3500
3000	


Accessories / Accesorios

Individual ceiling feed box. Driver not included.	Unidad de alimentación individual de techo. Driver no incluido.			08.0180.00
Double ceiling feed box. Driver not included.	Unidad de alimentación doble de techo. Driver no incluido.			08.0181.00
Wall mounted feed box. To be install in parallel to the Belt profile. Driver not included.	Unidad de alimentación individual de pared. Para instalar en paralelo al perfil Belt. Driver no incluido.			08.0182.00
Individual surface feed box. Driver not included.	Unidad de alimentación individual de superficie. Driver no incluido.			08.0194.00
Double surface feed box. Driver not included.	Unidad de alimentación doble de superficie. Driver no incluido.			08.0195.00
Surface driver box 96W - 48V, 110-240V.	Caja de superficie con driver de 96W - 48V, 110-240V.			06.0173.14


Drivers / Equipos


LED power supply source for remote installation, 110Vac-135W / 220Vac-200W.	Fuente de alimentación LED para instalación remota, 110Vac-135W / 220Vac-200W.			*60.9607
LED power supply source for remote installation, 48V/120W. 220/240 Vac.	Fuente de alimentación LED para instalación remota, 48V/120W. 220/240 Vac.			*60.9170


Control Units / Unidades de Control

Wireless Dimmer Bridge. From 1-10V to Casambi. For remote installation. See product specifications in the Flos Control manual. Recommended to act as a gateway from Lutron to Casambi.	Pasarela de regulación inalámbrica. De 1-10V a Casambi. Para instalación remota. Consulte las especificaciones de producto en el manual Flos Control. Aconsejado para actuar como pasarela de Lutron a Casambi.		DIM 1-10V >> Casambi 08.0824.14

Remote Driver Installations







* For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source / Para el dimensionado de la instalación mantener un margen de seguridad de un 15% de la potencia máxima de la fuente de alimentación LED.



Profiles
■ 14 Black
14 Negro

□ 40 White
40 Blanco





INFRA-STRUCTURE

Description
Groundbreaking lighting system designed by Vincent Van Duysen for surface installation on ceiling with rigid and adjustable rods.
In the new proposal, beside the successful “On Board Dimmer” version, FLOS goes one step beyond, launching both track and luminaries designed for system management in a variety of options: DALI, 1-10V and Casambi.
Both profile version are manufactured with aluminium profiling extruded in white or black, provided with electric tracks powered at 48V.
The system controlled versions (DALI, 1-10V) are also equipped with graphite data bus for regulation.
The LED light fixtures are installed by means of a magnetic fixture system with mechanical safety fastening.
The light fixtures product group is composed of accent lighting modules with different optics, direct and indirect light ambient lighting systems and decorative light fixtures with the distinctive Flos design.
All light fixtures are available with potentiometer incorporated, dimmable DALI, 1-10V and Casambi to adjust the light intensity.

Control
- For installation of “On Board Dimmer” fixtures use “On Board Dimmer” track version.
Luminaries DALI and 1-10V are only compatible with track DALI and 1-10V.
Casambi luminaires can be installed on all profiles available in the system.
- To manage using DALI protocol, it is necessary to connect the control data bus directly to the profile.
- For 1-10V management, the control system must be active and the data bus must be connected directly to the profile. In this case, regulation will be uniform in all the connected luminaires.
- For Casambi management (Max. 200 luminaires) it is mandatory to use fixtures in the Casambi version, these are compatible with all profiles available in the system.
For managing and controlling the Casambi system, the FLOS Control® app powered by Casambi for mobile devices is necessary (available in the Apple Store and Google Play).
Maximum number of track interconnections to guarantee the communication of the DALI or 1-10V signal: 20 interconnections.

Optic system
- Light Tube Direct / Light Tube Indirect / Suspension Glass Downlight 110 / Suspension Panel 600: diffuse ambient light.
- Spot 50: Medium.
- Spot 90: Spot, Medium.
- Spot 120 Power LED (same light source as the Spot 50 and Spot 90): Spot, Medium.
- Spot 120 LED Array (same light source as the Spot 150): Medium, Flood.
- Spot 150: Spot, Medium, Flood.
- Light Shadow Spot 30: Spot, Medium, Flood, Wide Flood.
- Light Shadow Spot 45: Spot, Medium, Flood.
- Light Shadow Spot 60: Super Spot, Spot, Medium, Flood, Wide Flood.
- Multi Spot Mini: Spot, Medium, Flood.

Power Supply
Remote 48V power supply not included. Max 6A - 320W.

Accessories
For Spot and Light Shadow Spot lighting modules, shielding accessories (honeycomb and crossheads) and color temperature correction filters are available. Please check model availability.

Additional Information
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Innovador sistema de iluminación diseñado por Vincent Van Duysen para instalación de superficie en techo mediante varillas rígidas y ajustables.
En esta versión renovada, además de la ya conocida versión “On Board Dimmer”, FLOS ha dado un paso más, añadiendo opción de perfil y luminarias que pueden controlarse con varios sistemas de control remoto: DALI, 1-10V y Casambi.
Ambas versiones de perfiles estructurales se fabrican con perfilería tubular de aluminio extruido en color negro o blanco, y son provistas de pistas eléctricas alimentadas a 48V.
Las versiones controlables como sistema (DALI, 1-10V) además llevan bus de datos en grafito para su regulación. Las versiones Casambi son compatibles con cualquier perfil.
Las luminarias se instalan mediante un sistema de fijación magnética y sujeción de seguridad mecánica.
La familia de luminarias está compuesta por módulos de iluminación de acento con distintas ópticas, sistemas de iluminación ambiental de luz directa e indirecta y luminarias decorativas con el diseño distintivo de Flos.
Todas las luminarias están disponibles con potenciómetro integrado, dimmable DALI o 1-10V para regular la intensidad luminosa, y en versión Casambi para una regulación inalámbrica.

Control
- Para instalaciones de luminaria con sistema de dimado “On Board Dimmer” y FLOS Control, usar perfil en versión “On Board Dimmer”.
Las luminarias DALI y 1-10V solo son compatibles con perfil versión DALI y 1-10V.
Las luminarias Casambi son compatibles con todos los perfiles.
- Para gestión mediante protocolo DALI es necesario conectar el bus de datos de control directamente al perfil.
- Para gestión 1-10V es necesario que el sistema de control sea activo y conectar el bus de datos de control directamente al perfil. En este caso la regulación será uniforme en todas las luminarias conectadas.
- Para gestión mediante Casambi (máximo 200 luminarias) es necesario pedir luminarias versión Casambi, estas son compatibles con cualquier tipo de perfil del sistema.
Necesaria app FLOS Control® powered by Casambi para dispositivos móviles (disponible en Apple Store y Google Play).
Número máximo de interconexiones de carriles para garantizar la comunicación de la señal DALI o 1-10V: 20 interconexiones.

Sistema Óptico
- Light Tube Direct / Light Tube Indirect / Suspension Glass Downlight 110 / Suspension Panel 600: luz ambiental difusa.
- Spot 50: Medium.
- Spot 90: Spot, Medium.
- Spot 120 Power LED (misma fuente de luz de los Spot 50 y Spot 90): Spot, Medium.
- Spot 120 LED Array (misma fuente de luz del Spot 150): Medium, Flood.
- Spot 150: Spot, Medium, Flood.
- Light Shadow Spot 30: Spot, Medium, Flood, Wide Flood.
- Light Shadow Spot 45: Spot, Medium, Flood.
- Light Shadow Spot 60: Super Spot, Spot, Medium, Flood, Wide Flood.
- Multi Spot Mini: Spot, Medium, Flood.

Unidades de Alimentación
Fuente de alimentación remota de 48V no incluida. Max 6A - 320W.

Accesorios
Para los módulos de iluminación Spot y Light Shadow Spot, existen accesorios de apantallamiento (honeycomb y crucetas) y filtros correctores de temperatura de color. Consultar disponibilidad según modelos.

Información Adicional
Índice de protección IP20.
Instalable en superficies normalmente inflamables.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

LIGHT MODULES

LIGHT TUBE DIRECT-INDIRECT



LIGHT SOURCE
TOP LED
23W/m
1978 lm/m
2700K/CRI 90
2227 lm/m
3000K/CRI 90

SPOT 50



LIGHT SOURCE
POWER LED
3,5W
286 lm
2700K/CRI 90
307 lm
3000K/CRI 90

SPOT 90



LIGHT SOURCE
POWER LED
8,5W
610 lm
2700K/CRI 90
656 lm
3000K/CRI 90

SPOT 120



LIGHT SOURCE
POWER LED
12W
724 lm
2700K/CRI 90
779 lm
3000K/CRI 90

SPOT 120



LIGHT SOURCE
LED ARRAY
12,5W
1075 lm
2700K/CRI 90
1138 lm
3000K/CRI 90

SPOT 150



LIGHT SOURCE
LED ARRAY
22,5W
2411 lm
2700K/CRI 90
2569 lm
3000K/CRI 90

LIGHT SHADOW SPOT 30



LIGHT SOURCE
POWER LED
4,5W
298 lm
2700K/CRI 90
318 lm
3000K/CRI 90

LIGHT SHADOW SPOT 45



LIGHT SOURCE
LED ARRAY
10W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

LIGHT SHADOW SPOT 60



LIGHT SOURCE
LED ARRAY
Up to 20W
Up to 1563 lm
2700K/CRI 90
Up to 1751 lm
3000K/CRI 90

SUSPENSION PANEL 600



LIGHT SOURCE
TOP LED
25,6W
3332 lm
2700K/CRI 90
3540 lm
3000K/CRI 90

SUSPENSION GLASS DOWNLIGHT 110



LIGHT SOURCE
LED ARRAY
13,5W
1296 lm
2700K/CRI 90
1371 lm
3000K/CRI 90

MULTI SPOT MINI



LIGHT SOURCE
TOP LED
7,5W
635 lm
2700K/CRI 90
650 lm
3000K/CRI 90

MULTIFUNCTION SMART DEVICE



FLOS CONTROL®
by Casambi

Light Tube

40 White
40 Blanco



14 Black
14 Negro

Spot

40 White
40 Blanco



05 Polished Aluminium
05 Polished Aluminium



14 Black
14 Negro



Light Shadow Spot

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Suspension Glass Downlight 110

00 Transparent Glass
00 Cristal Transparente



FU Smoked Glass
FU Cristal Fumé



RC Red Glass
RC Cristal Rojo



Suspension Panel

40 White / White
40 Blanco / Blanco



14 Black / Gold
14 Negro / Oro



Multi Spot Mini

40 White
40 Blanco



14 Black
14 Negro




Multifunction Smart Device

40 White
40 Blanco



14 Black
14 Negro





L1	L2
1055 mm	1100 mm
1555 mm	1600 mm

Profiles


Tubular electromagnetic profile for surface installation in ceilings through rigid and adjustable rods (25 mm). Not adjustable rigid rods available on request.
Profiles and closure terminals are available in version compatible with luminaries "on board dimmer" and versions compatible with system controlled luminaries (DALI, 1-10V, FLOS Control® by Casambi).
Tubular profiles available in two lengths: 1055 mm (1100 mm separation between rods) and 1555 mm (1600 mm separation between rods).
The closure terminals will also be electrified and must be ordered separately.
Mechanical and electrical rods are the same for the two profile versions and they are all available in multiple lengths (100, 300, 400, 700mm).
Different versions of fastening rods:
• Mechanic rod with a Ø50 or Ø140 connection rose: to fasten profiles.
• Electrical rod with a Ø50 connection rose: a supply rod for remote installation of the power supply in an accessible place.
• Electrical rod with a Ø140 connection rose: a supply rod for remote installation of the power supply through the connection rose.
• Data connection rod with a Ø50 or Ø140 connection rose: for connection to DALI or 1-10V bus signal.
• Aluminium stencil to mark the points for installing the rods available as separate item.

Perfiles


Perfil electro-magnético tubular para instalación de superficie en techo con fijación mediante varillas rígidas y regulables (25 mm). Varillas rígidas no regulables, pedir bajo demanda.
Perfil y terminal de cierre disponibles en versión compatible con luminarias "on board dimmer" y versión compatible con luminarias controlables como sistma (DALI, 1-10V o FLOS Control® by Casambi).
Perfiles tubulares disponibles en dos longitudes: 1055mm (separación entre varillas 1100mm) y 1555mm (separación entre varillas 1600mm).
Los terminales de cierre admiten instalación de luminarias y han de pedirse por separado.
Todas las varillas mecánicas y eléctricas son comunes para las dos versiones y están disponibles en diferentes alturas (100, 300, 400, 700mm).
Distintas versiones de varilla de sujeción:
• Varilla mecánica con rosetón de Ø50 o de Ø140: para fijación de perfiles.
• Varilla eléctrica con rosetón de Ø50: varilla de alimentación para instalación remota de la fuente de alimentación en lugar accesible.
• Varilla eléctrica con rosetón de Ø140: varilla de alimentación para instalación remota de la fuente de alimentación a través del rosetón.
• Varilla de conexión datos con rosetón de Ø50 o de Ø140: para conexión a fuente de señal DALI o 1-10V.
• Plantilla de aluminio, para marcar los puntos de fijación para la instalación de las varillas, disponible como producto separado.

C Straight elements.

C Elementos lineales.



L1	L2
1055 mm	1100 mm
1555 mm	1600 mm



On board dimmer / Casambi


L1: 1055 mm
06.5140.40
06.5140.14
L1: 1555 mm
06.5141.40
06.5141.14

DALI / 1-10V / Casambi

L1: 1055 mm
06.5100.40
06.5100.14
L1: 1555 mm
06.5101.40
06.5101.14

Aluminium Installation Stencil

Plantilla de aluminio de instalación



L2: 1100 mm
08.0032.00
L2: 1600 mm
08.0033.00

A End cap.

A Terminal.




On board dimmer / Casambi
06.5142.40A
06.5142.14A

DALI / 1-10V / Casambi
06.5135.40A
06.5135.14A

B Mechanical rod rose ø140 mm. Adjustable 25 mm, to adapt it to irregular ceilings.


B Varilla mecánica rosetón ø140 mm. Ajustable 25 mm, para adaptarse a techos irregulares.



H: 100 mm
06.5115.40
06.5115.14
H: 300 mm
06.5116.40
06.5116.14
H: 400 mm
06.5117.40
06.5117.14
H: 700 mm
06.5118.40
06.5118.14

B Electrical feed rod rose ø140 mm. Adjustable 25 mm, to adapt it to irregular ceilings.


B Varilla eléctrica de alimentación rosetón ø140 mm. Ajustable 25 mm, para adaptarse a techos irregulares.




H: 100 mm
06.5125.40
06.5125.14
H: 300 mm
06.5126.40
06.5126.14
H: 400 mm
06.5127.40
06.5127.14
H: 700 mm
06.5128.40
06.5128.14

B Data connection rod rose ø140mm.
Use one for each line of the installation, for connection to DALI or 1-10V signal source.
Adjustable 25 mm, to adapt it to irregular ceilings.

B Varilla de conexión datos con rosetón ø140 mm.
Usar una para cada linea de la instalación, para conectar a fuente de señal DALI o 1-10V.
Ajustable 25 mm, para adaptarse a techos irregulares.



H: 100 mm
06.5155.40
06.5155.14
H: 300 mm
06.5156.40
06.5156.14
H: 400 mm
06.5157.40
06.5157.14
H: 700 mm
06.5158.40
06.5158.14




L1	L2
1055 mm	1100 mm
1555 mm	1600 mm

Blind tube.

A mechanical module (without lighting) to be installed in the system infrastructure. Fixing components that rotate 0°-90°, with a magnetic connection and a mechanical safety lock. To be installed transversely between two profile lines.

Tubo Ciego.


Módulo mecánico (sin iluminación) para ser instalado en el sistema Infra-Structure. Elementos de fijación giratorios 0º-90º, con conexión magnética y bloqueo de seguridad mecánico, para instalación transversal entre dos líneas de perfil.



L: 900 mm
03.8120.40
03.8120.14
L: 1200 mm
03.8121.40
03.8121.14
L: 1500 mm
03.8122.40
03.8122.14

D Mechanical rod rose ø50 mm. Adjustable 25 mm, to adapt it to irregular ceilings.

D Varilla mecánica rosetón ø50 mm. Ajustable 25 mm, para adaptarse a techos irregulares.




H: 100 mm
06.5110.40
06.5110.14
H: 300 mm
06.5111.40
06.5111.14
H: 400 mm
06.5112.40
06.5112.14
H: 700 mm
06.5113.40
06.5113.14

D Electrical feed rod rose ø50 mm. Adjustable 25 mm, to adapt it to irregular ceilings.

D Varilla eléctrica de alimentación rosetón ø50 mm. Ajustable 25 mm, para adaptarse a techos irregulares.






H: 100 mm
06.5120.40
06.5120.14
H: 300 mm
06.5121.40
06.5121.14
H: 400 mm
06.5122.40
06.5122.14
H: 700 mm
06.5123.40
06.5123.14

D Data connection rod rose ø50mm. Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

D Varilla de conexión datos con rosetón ø50 mm. Usar una para cada linea de la instalación, para conectar a fuente de señal DALI o 1-10V. Ajustable 25 mm, para adaptarse a techos irregulares.






H: 100 mm
06.5150.40
06.5150.14
H: 300 mm
06.5151.40
06.5151.14
H: 400 mm
06.5152.40
06.5152.14
H: 700 mm
06.5153.40
06.5153.14

Drivers / Equipos

LED power supply source for remote installation, 48V/320W. 100/240 Vac.

Fuente de alimentación LED para instalación remota, 48V/320W. 100/240 Vac.






*60.8919

LED power supply source for remote installation, 110Vac-135W / 220Vac-200W.

Fuente de alimentación LED para instalación remota, 110Vac-135W / 220Vac-200W.






*60.9607

LED power supply source for remote installation, 48V/120W. 220/240 Vac.

Fuente de alimentación LED para instalación remota, 48V/120W. 220/240 Vac.






*60.9170

Control dimming box, 1-10V, 24/48V. For remote installation. For transforming passive systems (SINK) into active systems (SOURCE). It must be positioned between the control unit and the track. Important note: Maximum of 25 light modules.


Caja de control dimable 1-10V, 24/48V. Para instalación remota. Para transformar sistemas pasivos (SINK) en activos (SOURCE). Debe ubicarse entre la unidad de control y el carril. Nota importante: Máx. 25 módulos de luz.



DIM 1-10V - 24/48V
**08.0613.14A

Wireless Dimmer Bridge. From 1-10V to Casambi. For remote installation. See product specifications in the Flos Control manual. Recommended to act as a gateway from Lutron to Casambi.

Pasarela de regulación inalámbrica. De 1-10V a Casambi. Para instalación remota. Consulte las especificaciones de producto en el manual Flos Control. Aconsejado para actuar como pasarela de Lutron a Casambi.




DIM 1-10V >> Casambi
08.0824.14

Accessories / Accesorios

Multifunction Smart Device. Triple functionality 3x1: Casambi signal repeater, light sensor and presence detector. FLOS Control® by Casambi.

Dispositivo multifunción inteligente. Triple funcionalidad 3x1: repetidor de señal Casambi, sensor de luz ambiental y detector de presencia. FLOS Control® by Casambi.





06.1988.40
06.1988.14


* For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source / Para el dimensionado de la instalación mantener un margen de seguridad de un 15% de la potencia máxima de la fuente de alimentación LED.


** An active control system (SOURCE) is required and the data bus must be connected directly to the profile. For passive systems (SINK), a Dimming BOX Control unit is required (located between the control unit and the profile). / Es necesario un sistema de control activo (SOURCE) y conectar el bus de datos de control directamente al perfil. Para sistemas pasivos (SINK), es necesaria la unidad Control Dimming BOX (ubicada entre la unidad de control y el carril).

Light Tube ø30 Direct

Top LED 23W/m - 1978 lm/m - 2700K/CRI 90 / 23W/m - 2227 lm/m - 3000K/CRI 90







Diffused LED light module to be installed in The Infra-Structure. System turning fastening elements 0°-90° with a magnetic connection and mechanic security bock for a transversally installation between two lines of the profile.
The Light Tube are only fed by one od the ends and do not communicate current through the other end.
For wireless lighting control, choose Casambi versions.

Módulo de iluminación LED de luz difusa para ser instalado en el sistema Infra-Structure.
Elementos de fijación giratorios 0°-90°, con conexión magnética y bloqueo de seguridad mecánico, para instalación transversal entre dos líneas de perfil.
Los Light Tubes solo se alimentan por uno de los extremos y no comunican corriente a través del otro extremo.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.


2700K
L: 900 mm - 23W - 1820 lm
On board dimmer
- 03.8100.40A
- 03.8100.14A

Dali 2
- 03.8100.40ADA
- 03.8100.14ADA

1-10V
- 03.8100.40A1V
- 03.8100.14A1V

Casambi
- 03.8100.40ACB
- 03.8100.14ACB

150°



Luminous flux luminaire 1503 lm

Beam Angle: 150°

h(m)	E(lx)	D(m)
1	370	7.40
2	93	14.80
3	41	22.19
4	23	29.59
5	15	36.99


3000K
L: 900 mm - 23W - 2048 lm
On board dimmer
- 03.8105.40A
- 03.8105.14A

Dali 2
- 03.8105.40ADA
- 03.8105.14ADA

1-10V
- 03.8105.40A1V
- 03.8105.14A1V

Casambi
- 03.8105.40ACB
- 03.8105.14ACB

150°



Luminous flux luminaire 1550 lm

Beam Angle: 150°

h(m)	E(lx)	D(m)
1	382	7.40
2	95	14.80
3	42	22.19
4	24	29.59
5	15	36.99


2700K
L: 1200 mm - 30W - 2366 lm
On board dimmer
- 03.8101.40A
- 03.8101.14A

Dali 2
- 03.8101.40ADA
- 03.8101.14ADA

1-10V
- 03.8101.40A1V
- 03.8101.14A1V

Casambi
- 03.8101.40ACB
- 03.8101.14ACB

150°



Luminous flux luminaire 2005 lm

Beam Angle: 150°

h(m)	E(lx)	D(m)
1	494	7.40
2	123	14.80
3	55	22.19
4	31	29.59
5	20	36.99


3000K
L: 1200 mm - 30W - 2663 lm
On board dimmer
- 03.8106.40A
- 03.8106.14A

Dali 2
- 03.8106.40ADA
- 03.8106.14ADA

1-10V
- 03.8106.40A1V
- 03.8106.14A1V

Casambi
- 03.8106.40ACB
- 03.8106.14ACB

150°



Luminous flux luminaire 2068 lm

Beam Angle: 150°

h(m)	E(lx)	D(m)
1	509	7.40
2	127	14.80
3	57	22.19
4	32	29.59
5	20	36.99


2700K
L: 1500 mm - 38W - 2912 lm
On board dimmer
- 03.8102.40A
- 03.8102.14A

Dali 2
- 03.8102.40ADA
- 03.8102.14ADA

1-10V
- 03.8102.40A1V
- 03.8102.14A1V

Casambi
- 03.8102.40ACB
- 03.8102.14ACB

150°



Luminous flux luminaire 2506 lm

Beam Angle: 150°

h(m)	E(lx)	D(m)
1	617	7.40
2	154	14.80
3	69	22.19
4	39	29.59
5	25	36.99


3000K
L: 1500 mm - 38W - 3278 lm
On board dimmer
- 03.8107.40A
- 03.8107.14A

Dali 2
- 03.8107.40ADA
- 03.8107.14ADA

1-10V
- 03.8107.40A1V
- 03.8107.14A1V

Casambi
- 03.8107.40ACB
- 03.8107.14ACB

150°



Luminous flux luminaire 2584 lm


Beam Angle: 150°

h(m)	E(lx)	D(m)
1	636	7.40
2	159	14.80
3	71	22.19
4	40	29.59
5	25	36.99

Light Tube ø30 Indirect

Top LED 23W/m - 1978 lm/m - 2700K/CRI 90 / 23W/m - 2227 lm/m - 3000K/CRI 90







Diffused LED light module to be installed in The Infra-Structure. System turning fastening elements 0º-90º with a magnetic connection and mechanic security bock for a transversally installation between two lines of the profile.
The Light Tube are only fed by one od the ends and do not communicate current through the other end.
For wireless lighting control, choose Casambi versions.


Módulo de iluminación LED de luz difusa para ser instalado en el sistema Infra-Structure.
Elementos de fijación giratorios 0º-90º, con conexión magnética y bloqueo de seguridad mecánico, para instalación transversal entre dos líneas de perfil.
Los Light Tubes solo se alimentan por uno de los extremos y no comunican corriente a través del otro extremo.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

2700K
L: 900 mm - 23W - 1820 lm
On board dimmer
- ☐ 03.8110.40A
- ■ 03.8110.14A

Dali 2
- ☐ 03.8110.40ADA
- ■ 03.8110.14ADA

1-10V
- ☐ 03.8110.40A1V
- ■ 03.8110.14A1V

Casambi
- ☐ 03.8110.40ACB
- ■ 03.8110.14ACB



Luminous flux luminaire
1260 lm

Beam Angle: 93°


h(m)	E(lx)	D(m)
1	541	2.10
2	135	4.20
3	60	6.30
4	34	8.40
5	22	10.51

3000K
L: 900 mm - 23W - 2048 lm
On board dimmer
- ☐ 03.8115.40A
- ■ 03.8115.14A

Dali 2
- ☐ 03.8115.40ADA
- ■ 03.8115.14ADA

1-10V
- ☐ 03.8115.40A1V
- ■ 03.8115.14A1V

Casambi
- ☐ 03.8115.40ACB
- ■ 03.8115.14ACB



Luminous flux luminaire
1299 lm

Beam Angle: 93°


h(m)	E(lx)	D(m)
1	558	2.10
2	139	4.20
3	62	6.30
4	35	8.40
5	22	10.51

2700K
L: 1200 mm - 30W - 2366 lm
On board dimmer
- ☐ 03.8111.40A
- ■ 03.8111.14A

Dali 2
- ☐ 03.8111.40ADA
- ■ 03.8111.14ADA

1-10V
- ☐ 03.8111.40A1V
- ■ 03.8111.14A1V

Casambi
- ☐ 03.8111.40ACB
- ■ 03.8111.14ACB



Luminous flux luminaire
1679 lm

Beam Angle: 93°


h(m)	E(lx)	D(m)
1	721	2.10
2	180	4.20
3	80	6.30
4	45	8.40
5	29	10.51

3000K
L: 1200 mm - 30W - 2663 lm
On board dimmer
- ☐ 03.8116.40A
- ■ 03.8116.14A

Dali 2
- ☐ 03.8116.40ADA
- ■ 03.8116.14ADA

1-10V
- ☐ 03.8116.40A1V
- ■ 03.8116.14A1V

Casambi
- ☐ 03.8116.40ACB
- ■ 03.8116.14ACB



Luminous flux luminaire
1732 lm

Beam Angle: 93°


h(m)	E(lx)	D(m)
1	744	2.10
2	186	4.20
3	83	6.30
4	46	8.40
5	30	10.51

2700K
L: 1500 mm - 38W - 2912 lm
On board dimmer
- ☐ 03.8112.40A
- ■ 03.8112.14A

Dali 2
- ☐ 03.8112.40ADA
- ■ 03.8112.14ADA

1-10V
- ☐ 03.8112.40A1V
- ■ 03.8112.14A1V

Casambi
- ☐ 03.8112.40ACB
- ■ 03.8112.14ACB



Luminous flux luminaire
2099 lm

Beam Angle: 93°


h(m)	E(lx)	D(m)
1	902	2.10
2	225	4.20
3	100	6.30
4	56	8.40
5	36	10.51

3000K
L: 1500 mm - 38W - 3278 lm
On board dimmer
- ☐ 03.8117.40A
- ■ 03.8117.14A

Dali 2
- ☐ 03.8117.40ADA
- ■ 03.8117.14ADA

1-10V
- ☐ 03.8117.40A1V
- ■ 03.8117.14A1V

Casambi
- ☐ 03.8117.40ACB
- ■ 03.8117.14ACB



Luminous flux luminaire
2164 lm


Beam Angle: 93°


h(m)	E(lx)	D(m)
1	929	2.10
2	232	4.20
3	103	6.30
4	58	8.40
5	37	10.51

Spot 50

Power LED 3,5W - 286 lm - 2700K/CRI 90 / 3,5W - 307 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Infra-Structure System.
For wireless lighting control, choose Casambi versions.

Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Accesorios incluidos (honeycomb y cruceta de apantallamiento).


2700K

On board dimmer
- 03.8032.40A
- 03.8032.05B
- 03.8032.14A

Dali 2
- 03.8032.40ADA
- 03.8032.05BDA
- 03.8032.14ADA

1-10V
- 03.8032.40A1V
- 03.8032.05B1V
- 03.8032.14A1V

Casambi
- 03.8032.40ACB
- 03.8032.05BCB
- 03.8032.14ACB



Luminous flux luminaire
205 lm (EXTREME CUT OFF)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	977	0.47
2	244	0.94
3	109	1.41
4	61	1.88
5	39	2.35


3000K

On board dimmer
- 03.8033.40A
- 03.8033.05B
- 03.8033.14A

Dali 2
- 03.8033.40ADA
- 03.8033.05BDA
- 03.8033.14ADA

1-10V
- 03.8033.40A1V
- 03.8033.05B1V
- 03.8033.14A1V

Casambi
- 03.8033.40ACB
- 03.8033.05BCB
- 03.8033.14ACB



Luminous flux luminaire
212 lm (EXTREME CUT OFF)


Beam Angle: 26°


h(m)	E(lx)	D(m)
1	1012	0.47
2	253	0.94
3	112	1.41
4	63	1.88
5	40	2.35

Spot 90

Power LED 8,5W - 610 lm - 2700K/CRI 90 / 8,5W - 656 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Infra-Structure System.
For wireless lighting control, choose Casambi versions.

Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Accesorios incluidos (honeycomb y cruceta de apantallamiento).


2700K
On board dimmer
- 03.8042.40A
- 03.8042.05B
- 03.8042.14A

Dali 2
- 03.8042.40ADA
- 03.8042.05BDA
- 03.8042.14ADA

1-10V
- 03.8042.40A1V
- 03.8042.05B1V
- 03.8042.14A1V

Casambi
- 03.8042.40ACB
- 03.8042.05BCB
- 03.8042.14ACB

14° SPOT



Luminous flux luminaire 428 lm (EXTREME CUT OFF)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5601	0.25
2	1400	0.49
3	622	0.74
4	350	0.98
5	224	1.23


3000K
On board dimmer
- 03.8043.40A
- 03.8043.05B
- 03.8043.14A

Dali 2
- 03.8043.40ADA
- 03.8043.05BDA
- 03.8043.14ADA

1-10V
- 03.8043.40A1V
- 03.8043.05B1V
- 03.8043.14A1V

Casambi
- 03.8043.40ACB
- 03.8043.05BCB
- 03.8043.14ACB

14° SPOT



Luminous flux luminaire 443 lm (EXTREME CUT OFF)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5805	0.25
2	1451	0.49
3	645	0.74
4	363	0.98
5	232	1.23


2700K
On board dimmer
- 03.8044.40A
- 03.8044.05B
- 03.8044.14A

Dali 2
- 03.8044.40ADA
- 03.8044.05BDA
- 03.8044.14ADA

1-10V
- 03.8044.40A1V
- 03.8044.05B1V
- 03.8044.14A1V

Casambi
- 03.8044.40ACB
- 03.8044.05BCB
- 03.8044.14ACB

22° MEDIUM



Luminous flux luminaire 392 lm (EXTREME CUT OFF)

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	2319	0.38
2	580	0.77
3	258	1.15
4	145	1.54
5	93	1.92


3000K
On board dimmer
- 03.8045.40A
- 03.8045.05B
- 03.8045.14A

Dali 2
- 03.8045.40ADA
- 03.8045.05BDA
- 03.8045.14ADA

1-10V
- 03.8045.40A1V
- 03.8045.05B1V
- 03.8045.14A1V

Casambi
- 03.8045.40ACB
- 03.8045.05BCB
- 03.8045.14ACB

22° MEDIUM



Luminous flux luminaire 406 lm (EXTREME CUT OFF)


Beam Angle: 22°


h(m)	E(lx)	D(m)
1	2403	0.38
2	601	0.77
3	267	1.15
4	150	1.54
5	96	1.92

Spot 120

Power LED 12W - 724 lm - 2700K/CRI 90 / 12W - 779 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Infra-Structure System.
For wireless lighting control, choose Casambi versions.

Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Accesorios incluidos (honeycomb y cruceta de apantallamiento).


2700K
On board dimmer
- 03.8052.40A
- 03.8052.05B
- 03.8052.14A

Dali 2
- 03.8052.40ADA
- 03.8052.05BDA
- 03.8052.14ADA

1-10V
- 03.8052.40A1V
- 03.8052.05B1V
- 03.8052.14A1V

Casambi
- 03.8052.40ACB
- 03.8052.05BCB
- 03.8052.14ACB

11° SPOT



Luminous flux luminaire 539 lm (EXTREME CUT OFF)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	11417	0.19
2	2854	0.37
3	1269	0.56
4	714	0.75
5	457	0.93


3000K
On board dimmer
- 03.8053.40A
- 03.8053.05B
- 03.8053.14A

Dali 2
- 03.8053.40ADA
- 03.8053.05BDA
- 03.8053.14ADA

1-10V
- 03.8053.40A1V
- 03.8053.05B1V
- 03.8053.14A1V

Casambi
- 03.8053.40ACB
- 03.8053.05BCB
- 03.8053.14ACB

11° SPOT



Luminous flux luminaire 558 lm (EXTREME CUT OFF)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	11834	0.19
2	2958	0.37
3	1315	0.56
4	740	0.75
5	473	0.93


2700K
On board dimmer
- 03.8054.40A
- 03.8054.05B
- 03.8054.14A

Dali 2
- 03.8054.40ADA
- 03.8054.05BDA
- 03.8054.14ADA

1-10V
- 03.8054.40A1V
- 03.8054.05B1V
- 03.8054.14A1V

Casambi
- 03.8054.40ACB
- 03.8054.05BCB
- 03.8054.14ACB

17° MEDIUM



Luminous flux luminaire 487 lm (EXTREME CUT OFF)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	3865	0.29
2	966	0.59
3	429	0.88
4	242	1.18
5	155	1.47


3000K
On board dimmer
- 03.8055.40A
- 03.8055.05B
- 03.8055.14A

Dali 2
- 03.8055.40ADA
- 03.8055.05BDA
- 03.8055.14ADA

1-10V
- 03.8055.40A1V
- 03.8055.05B1V
- 03.8055.14A1V

Casambi
- 03.8055.40ACB
- 03.8055.05BCB
- 03.8055.14ACB

17° MEDIUM



Luminous flux luminaire 505 lm (EXTREME CUT OFF)


Beam Angle: 17°


h(m)	E(lx)	D(m)
1	4006	0.29
2	1001	0.59
3	445	0.88
4	250	1.18
5	160	1.47

Spot 120

LED Array 12,5W - 1075 lm - 2700K/CRI 90 / 12,5W - 1138 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Infra-Structure System.
For wireless lighting control, choose Casambi versions.

Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Accesorios incluidos (honeycomb y cruceta de apantallamiento).


2700K
On board dimmer
- 03.8154.40
- 03.8154.05A
- 03.8154.14

Dali 2
- 03.8154.40.DA
- 03.8154.05ADA
- 03.8154.14.DA

1-10V
- 03.8154.40.1V
- 03.8154.05A1V
- 03.8154.14.1V

Casambi
- 03.8154.40.CB
- 03.8154.05ACB
- 03.8154.14.CB

17° MEDIUM



Luminous flux luminaire 654 lm

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	4547	0.31
2	1137	0.61
3	505	0.92
4	284	1.23
5	182	1.53


3000K
On board dimmer
- 03.8155.40
- 03.8155.05A
- 03.8155.14

Dali 2
- 03.8155.40.DA
- 03.8155.05ADA
- 03.8155.14.DA

1-10V
- 03.8155.40.1V
- 03.8155.05A1V
- 03.8155.14.1V

Casambi
- 03.8155.40.CB
- 03.8155.05ACB
- 03.8155.14.CB

17° MEDIUM



Luminous flux luminaire 687 lm

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	4780	0.31
2	1195	0.61
3	531	0.92
4	299	1.23
5	191	1.53


2700K
On board dimmer
- 03.8156.40
- 03.8156.05A
- 03.8156.14

Dali 2
- 03.8156.40.DA
- 03.8156.05ADA
- 03.8156.14.DA

1-10V
- 03.8156.40.1V
- 03.8156.05A1V
- 03.8156.14.1V

Casambi
- 03.8156.40.CB
- 03.8156.05ACB
- 03.8156.14.CB

40° FLOOD



Luminous flux luminaire 599 lm

Beam Angle: 40°

h(m)	E(lx)	D(m)
1	1367	0.73
2	342	1.45
3	152	2.18
4	85	2.91
5	55	3.64


3000K
On board dimmer
- 03.8157.40
- 03.8157.05A
- 03.8157.14

Dali 2
- 03.8157.40.DA
- 03.8157.05ADA
- 03.8157.14.DA

1-10V
- 03.8157.40.1V
- 03.8157.05A1V
- 03.8157.14.1V

Casambi
- 03.8157.40.CB
- 03.8157.05ACB
- 03.8157.14.CB

40° FLOOD



Luminous flux luminaire 629 lm


Beam Angle: 40°


h(m)	E(lx)	D(m)
1	1437	0.73
2	359	1.45
3	160	2.18
4	90	2.91
5	57	3.64

Spot 150

LED Array 22,5W - 2411 lm - 2700K/CRI 90 / 22,5W - 2569 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Infra-Structure System.
For wireless lighting control, choose Casambi versions.

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

2700K


On board dimmer
- 03.8072.40A
- 03.8072.05B
- 03.8072.14A

Dali 2
- 03.8072.40ADA
- 03.8072.05BDA
- 03.8072.14ADA

1-10V
- 03.8072.40A1V
- 03.8072.05B1V
- 03.8072.14A1V

Casambi
- 03.8072.40ACB
- 03.8072.05BCB
- 03.8072.14ACB

21° SPOT



Luminous flux luminaire
1818 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	11239	0.37
2	2810	0.74
3	1249	1.11
4	702	1.48
5	450	1.85

3000K


On board dimmer
- 03.8073.40A
- 03.8073.05B
- 03.8073.14A

Dali 2
- 03.8073.40ADA
- 03.8073.05BDA
- 03.8073.14ADA

1-10V
- 03.8073.40A1V
- 03.8073.05B1V
- 03.8073.14A1V

Casambi
- 03.8073.40ACB
- 03.8073.05BCB
- 03.8073.14ACB

21° SPOT



Luminous flux luminaire
1937 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	11975	0.37
2	2994	0.74
3	1331	1.11
4	748	1.48
5	479	1.85

2700K


On board dimmer
- 03.8074.40A
- 03.8074.05B
- 03.8074.14A

Dali 2
- 03.8074.40ADA
- 03.8074.05BDA
- 03.8074.14ADA

1-10V
- 03.8074.40A1V
- 03.8074.05B1V
- 03.8074.14A1V

Casambi
- 03.8074.40ACB
- 03.8074.05BCB
- 03.8074.14ACB

27° MEDIUM



Luminous flux luminaire
1564 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	7167	0.49
2	1792	0.98
3	796	1.47
4	448	1.96
5	287	2.44

3000K


On board dimmer
- 03.8075.40A
- 03.8075.05B
- 03.8075.14A

Dali 2
- 03.8075.40ADA
- 03.8075.05BDA
- 03.8075.14ADA

1-10V
- 03.8075.40A1V
- 03.8075.05B1V
- 03.8075.14A1V

Casambi
- 03.8075.40ACB
- 03.8075.05BCB
- 03.8075.14ACB

27° MEDIUM



Luminous flux luminaire
1667 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	7638	0.49
2	1910	0.98
3	849	1.47
4	477	1.96
5	306	2.44

2700K


On board dimmer
- 03.8076.40A
- 03.8076.05B
- 03.8076.14A

Dali 2
- 03.8076.40ADA
- 03.8076.05BDA
- 03.8076.14ADA

1-10V
- 03.8076.40A1V
- 03.8076.05B1V
- 03.8076.14A1V

Casambi
- 03.8076.40ACB
- 03.8076.05BCB
- 03.8076.14ACB

36° FLOOD



Luminous flux luminaire
1569 lm

Beam Angle: 36°

h(m)	E(lx)	D(m)
1	4586	0.64
2	1146	1.28
3	510	1.92
4	287	2.56
5	183	3.20

3000K


On board dimmer
- 03.8077.40A
- 03.8077.05B
- 03.8077.14A

Dali 2
- 03.8077.40ADA
- 03.8077.05BDA
- 03.8077.14ADA

1-10V
- 03.8077.40A1V
- 03.8077.05B1V
- 03.8077.14A1V

Casambi
- 03.8077.40ACB
- 03.8077.05BCB
- 03.8077.14ACB

36° FLOOD



Luminous flux luminaire
1672 lm

Beam Angle: 36°

h(m)	E(lx)	D(m)
1	4887	0.64
2	1222	1.28
3	543	1.92
4	305	2.56
5	195	3.20

Accessories / Accesorios

Spot 150

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.
Installation compatible with honeycomb + lense at the same time.


Cruceta de apantallamiento, lentes y honeycomb directamente instalables en la cabeza de la luminaria sin necesidad de accesorio de sujeción.
Compatibilidad de instalación de honeycomb + lente al mismo tiempo.


Screening crosspiece.	Cruceta de apantallamiento.		08.8429.00
Elliptical lens.	Lente elíptica.		08.8431.00
Flood lens.	Lente flood.		08.8432.00
Honeycomb.	Honeycomb.		08.8428.00
Snoot shielding cone.	Cono apantallador.		08.0526.00 08.0526.40 08.0526.BW

Light Shadow Spot 30

Power LED 4,5W - 298 lm - 2700K/CRI 90 / 4,5W - 318 lm - 3000K/CRI 90







LED accent lighting module for installation in Infra-Structure system. For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Spot - 2700K


On board dimmer
- 05.9000.40
- 05.9000.14
- 05.9000.ER
- 05.9000.ES

Dali 2
- 05.9000.40.DA
- 05.9000.14.DA
- 05.9000.ER.DA
- 05.9000.ES.DA

1-10V
- 05.9000.40.1V
- 05.9000.14.1V
- 05.9000.ER.1V
- 05.9000.ES.1V

Casambi
- 05.9000.40.CB
- 05.9000.14.CB
- 05.9000.ER.CB
- 05.9000.ES.CB





Luminous flux luminaire 253 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4044	0.20
2	1011	0.40
3	449	0.60
4	253	0.80
5	162	1.00

Optic Spot - 3000K


On board dimmer
- 05.9005.40
- 05.9005.14
- 05.9005.ER
- 05.9005.ES

Dali 2
- 05.9005.40.DA
- 05.9005.14.DA
- 05.9005.ER.DA
- 05.9005.ES.DA

1-10V
- 05.9005.40.1V
- 05.9005.14.1V
- 05.9005.ER.1V
- 05.9005.ES.1V

Casambi
- 05.9005.40.CB
- 05.9005.14.CB
- 05.9005.ER.CB
- 05.9005.ES.CB





Luminous flux luminaire 270 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4316	0.20
2	1079	0.40
3	480	0.60
4	270	0.80
5	173	1.00

Optic Medium - 2700K


On board dimmer
- 05.9001.40
- 05.9001.14
- 05.9001.ER
- 05.9001.ES

Dali 2
- 05.9001.40.DA
- 05.9001.14.DA
- 05.9001.ER.DA
- 05.9001.ES.DA

1-10V
- 05.9001.40.1V
- 05.9001.14.1V
- 05.9001.ER.1V
- 05.9001.ES.1V

Casambi
- 05.9001.40.CB
- 05.9001.14.CB
- 05.9001.ER.CB
- 05.9001.ES.CB





Luminous flux luminaire 257 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1797	0.39
2	449	0.78
3	200	1.17
4	112	1.56
5	72	1.95

Optic Medium - 3000K


On board dimmer
- 05.9006.40
- 05.9006.14
- 05.9006.ER
- 05.9006.ES

Dali 2
- 05.9006.40.DA
- 05.9006.14.DA
- 05.9006.ER.DA
- 05.9006.ES.DA

1-10V
- 05.9006.40.1V
- 05.9006.14.1V
- 05.9006.ER.1V
- 05.9006.ES.1V

Casambi
- 05.9006.40.CB
- 05.9006.14.CB
- 05.9006.ER.CB
- 05.9006.ES.CB





Luminous flux luminaire 274 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1916	0.39
2	479	0.78
3	213	1.17
4	120	1.56
5	77	1.95

Optic Flood - 2700K


On board dimmer
- 05.9002.40
- 05.9002.14
- 05.9002.ER
- 05.9002.ES

Dali 2
- 05.9002.40.DA
- 05.9002.14.DA
- 05.9002.ER.DA
- 05.9002.ES.DA

1-10V
- 05.9002.40.1V
- 05.9002.14.1V
- 05.9002.ER.1V
- 05.9002.ES.1V

Casambi
- 05.9002.40.CB
- 05.9002.14.CB
- 05.9002.ER.CB
- 05.9002.ES.CB





Luminous flux luminaire
246 lm

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	953	0.52
2	238	1.04
3	106	1.57
4	60	2.09
5	38	2.61

Optic Flood - 3000K


On board dimmer
- 05.9007.40
- 05.9007.14
- 05.9007.ER
- 05.9007.ES

Dali 2
- 05.9007.40.DA
- 05.9007.14.DA
- 05.9007.ER.DA
- 05.9007.ES.DA

1-10V
- 05.9007.40.1V
- 05.9007.14.1V
- 05.9007.ER.1V
- 05.9007.ES.1V

Casambi
- 05.9007.40.CB
- 05.9007.14.CB
- 05.9007.ER.CB
- 05.9007.ES.CB





Luminous flux luminaire
263 lm

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	1019	0.52
2	255	1.04
3	113	1.57
4	64	2.09
5	41	2.61

Optic Wide Flood - 2700K


On board dimmer
- 05.9003.40
- 05.9003.14
- 05.9003.ER
- 05.9003.ES

Dali 2
- 05.9003.40.DA
- 05.9003.14.DA
- 05.9003.ER.DA
- 05.9003.ES.DA

1-10V
- 05.9003.40.1V
- 05.9003.14.1V
- 05.9003.ER.1V
- 05.9003.ES.1V

Casambi
- 05.9003.40.CB
- 05.9003.14.CB
- 05.9003.ER.CB
- 05.9003.ES.CB





Luminous flux luminaire
246 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	524	0.80
2	131	1.59
3	58	2.39
4	33	3.19
5	21	3.99

Optic Wide Flood - 3000K


On board dimmer
- 05.9008.40
- 05.9008.14
- 05.9008.ER
- 05.9008.ES

Dali 2
- 05.9008.40.DA
- 05.9008.14.DA
- 05.9008.ER.DA
- 05.9008.ES.DA

1-10V
- 05.9008.40.1V
- 05.9008.14.1V
- 05.9008.ER.1V
- 05.9008.ES.1V

Casambi
- 05.9008.40.CB
- 05.9008.14.CB
- 05.9008.ER.CB
- 05.9008.ES.CB





Luminous flux luminaire
262 lm


Beam Angle: 43°


h(m)	E(lx)	D(m)
1	559	0.80
2	140	1.59
3	62	2.39
4	35	3.19
5	22	3.99

Light Shadow Spot 45

LED Array 10W - 799 lm - 2700K/CRI 90 / 10W - 844 lm - 3000K/CRI 90







LED accent lighting module for installation in Infra-Structure system. For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Spot - 2700K


On board dimmer
- 05.9030.40
- 05.9030.14
- 05.9030.ER
- 05.9030.ES

Dali 2
- 05.9030.40.DA
- 05.9030.14.DA
- 05.9030.ER.DA
- 05.9030.ES.DA

1-10V
- 05.9030.40.1V
- 05.9030.14.1V
- 05.9030.ER.1V
- 05.9030.ES.1V

Casambi
- 05.9030.40.CB
- 05.9030.14.CB
- 05.9030.ER.CB
- 05.9030.ES.CB





Luminous flux luminaire
650 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8012	0.27
2	2003	0.54
3	890	0.80
4	501	1.07
5	320	1.34

Optic Spot - 3000K


On board dimmer
- 05.9035.40
- 05.9035.14
- 05.9035.ER
- 05.9035.ES

Dali 2
- 05.9035.40.DA
- 05.9035.14.DA
- 05.9035.ER.DA
- 05.9035.ES.DA

1-10V
- 05.9035.40.1V
- 05.9035.14.1V
- 05.9035.ER.1V
- 05.9035.ES.1V

Casambi
- 05.9035.40.CB
- 05.9035.14.CB
- 05.9035.ER.CB
- 05.9035.ES.CB





Luminous flux luminaire
686 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8456	0.27
2	2114	0.54
3	940	0.80
4	528	1.07
5	338	1.34

Optic Medium - 2700K


On board dimmer
- 05.9031.40
- 05.9031.14
- 05.9031.ER
- 05.9031.ES

Dali 2
- 05.9031.40.DA
- 05.9031.14.DA
- 05.9031.ER.DA
- 05.9031.ES.DA

1-10V
- 05.9031.40.1V
- 05.9031.14.1V
- 05.9031.ER.1V
- 05.9031.ES.1V

Casambi
- 05.9031.40.CB
- 05.9031.14.CB
- 05.9031.ER.CB
- 05.9031.ES.CB





Luminous flux luminaire
645 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5163	0.36
2	1291	0.73
3	574	1.09
4	323	1.46
5	207	1.82

Optic Medium - 3000K


On board dimmer
- 05.9036.40
- 05.9036.14
- 05.9036.ER
- 05.9036.ES

Dali 2
- 05.9036.40.DA
- 05.9036.14.DA
- 05.9036.ER.DA
- 05.9036.ES.DA

1-10V
- 05.9036.40.1V
- 05.9036.14.1V
- 05.9036.ER.1V
- 05.9036.ES.1V

Casambi
- 05.9036.40.CB
- 05.9036.14.CB
- 05.9036.ER.CB
- 05.9036.ES.CB





Luminous flux luminaire
682 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5459	0.36
2	1365	0.73
3	607	1.09
4	341	1.46
5	218	1.82

Optic Flood - 2700K

On board dimmer

- 05.9032.40
- 05.9032.14
- 05.9032.ER
- 05.9032.ES

Dali 2

- 05.9032.40.DA
- 05.9032.14.DA
- 05.9032.ER.DA
- 05.9032.ES.DA

1-10V


- 05.9032.40.1V
- 05.9032.14.1V
- 05.9032.ER.1V
- 05.9032.ES.1V

Casambi

- 05.9032.40.CB
- 05.9032.14.CB
- 05.9032.ER.CB
- 05.9032.ES.CB



FLOOD



Luminous flux luminaire
646 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2296	0.56
2	574	1.11
3	255	1.67
4	144	2.22
5	92	2.78

Optic Flood - 3000K

On board dimmer

- 05.9037.40
- 05.9037.14
- 05.9037.ER
- 05.9037.ES

Dali 2

- 05.9037.40.DA
- 05.9037.14.DA
- 05.9037.ER.DA
- 05.9037.ES.DA

1-10V


- 05.9037.40.1V
- 05.9037.14.1V
- 05.9037.ER.1V
- 05.9037.ES.1V

Casambi

- 05.9037.40.CB
- 05.9037.14.CB
- 05.9037.ER.CB
- 05.9037.ES.CB



FLOOD



Luminous flux luminaire
682 lm


Beam Angle: 31°


h(m)	E(lx)	D(m)
1	2424	0.56
2	606	1.11
3	269	1.67
4	152	2.22
5	97	2.78

Light Shadow Spot 60

Super Spot: LED Array 10W - 799 lm - 2700K/CRI 90 / 10W - 844 lm - 3000K/CRI 90
S/M/F/WF: LED Array 20W - 1563 lm - 2700K/CRI 90 / 20W - 1751 lm - 3000K/CRI 90







LED accent lighting module for installation in Infra-Structure system. For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Super Spot - 2700K


On board dimmer
- 05.9060.40
- 05.9060.14
- 05.9060.ER
- 05.9060.ES

Dali 2
- 05.9060.40.DA
- 05.9060.14.DA
- 05.9060.ER.DA
- 05.9060.ES.DA

1-10V
- 05.9060.40.1V
- 05.9060.14.1V
- 05.9060.ER.1V
- 05.9060.ES.1V

Casambi
- 05.9060.40.CB
- 05.9060.14.CB
- 05.9060.ER.CB
- 05.9060.ES.CB





Luminous flux luminaire 765 lm

Beam Angle: 9°

h(m)	E(lx)	D(m)
1	24922	0.16
2	6230	0.32
3	2769	0.48
4	1558	0.64
5	997	0.80

Optic Super Spot - 3000K


On board dimmer
- 05.9065.40
- 05.9065.14
- 05.9065.ER
- 05.9065.ES

Dali 2
- 05.9065.40.DA
- 05.9065.14.DA
- 05.9065.ER.DA
- 05.9065.ES.DA

1-10V
- 05.9065.40.1V
- 05.9065.14.1V
- 05.9065.ER.1V
- 05.9065.ES.1V

Casambi
- 05.9065.40.CB
- 05.9065.14.CB
- 05.9065.ER.CB
- 05.9065.ES.CB





Luminous flux luminaire 808 lm

Beam Angle: 9°

h(m)	E(lx)	D(m)
1	26322	0.16
2	6581	0.32
3	2925	0.48
4	1645	0.64
5	1053	0.80

Optic Spot - 2700K


On board dimmer
- 05.9061.40
- 05.9061.14
- 05.9061.ER
- 05.9061.ES

Dali 2
- 05.9061.40.DA
- 05.9061.14.DA
- 05.9061.ER.DA
- 05.9061.ES.DA

1-10V
- 05.9061.40.1V
- 05.9061.14.1V
- 05.9061.ER.1V
- 05.9061.ES.1V

Casambi
- 05.9061.40.CB
- 05.9061.14.CB
- 05.9061.ER.CB
- 05.9061.ES.CB





Luminous flux luminaire 1251 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	14350	0.27
2	3587	0.54
3	1594	0.81
4	897	1.09
5	574	1.36

Optic Spot - 3000K


On board dimmer
- 05.9066.40
- 05.9066.14
- 05.9066.ER
- 05.9066.ES

Dali 2
- 05.9066.40.DA
- 05.9066.14.DA
- 05.9066.ER.DA
- 05.9066.ES.DA

1-10V
- 05.9066.40.1V
- 05.9066.14.1V
- 05.9066.ER.1V
- 05.9066.ES.1V

Casambi
- 05.9066.40.CB
- 05.9066.14.CB
- 05.9066.ER.CB
- 05.9066.ES.CB





Luminous flux luminaire 1375 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	15772	0.27
2	3943	0.54
3	1752	0.81
4	986	1.09
5	631	1.36


Optic Medium - 2700K

On board dimmer
- 05.9062.40
- 05.9062.14
- 05.9062.ER
- 05.9062.ES

Dali 2
- 05.9062.40.DA
- 05.9062.14.DA
- 05.9062.ER.DA
- 05.9062.ES.DA

1-10V
- 05.9062.40.1V
- 05.9062.14.1V
- 05.9062.ER.1V
- 05.9062.ES.1V

Casambi
- 05.9062.40.CB
- 05.9062.14.CB
- 05.9062.ER.CB
- 05.9062.ES.CB



Luminous flux luminaire
1298 lm

Beam Angle:	26°
h(m) E(lx)	D(m)
1 7377	0.45
2 1844	0.91
3 820	1.36
4 461	1.82
5 295	2.27


Optic Medium - 3000K

On board dimmer
- 05.9067.40
- 05.9067.14
- 05.9067.ER
- 05.9067.ES

Dali 2
- 05.9067.40.DA
- 05.9067.14.DA
- 05.9067.ER.DA
- 05.9067.ES.DA

1-10V
- 05.9067.40.1V
- 05.9067.14.1V
- 05.9067.ER.1V
- 05.9067.ES.1V

Casambi
- 05.9067.40.CB
- 05.9067.14.CB
- 05.9067.ER.CB
- 05.9067.ES.CB



Luminous flux luminaire
1427 lm

Beam Angle:	26°
h(m) E(lx)	D(m)
1 8110	0.45
2 2027	0.91
3 901	1.36
4 507	1.82
5 324	2.27


Optic Flood - 2700K

On board dimmer
- 05.9063.40
- 05.9063.14
- 05.9063.ER
- 05.9063.ES

Dali 2
- 05.9063.40.DA
- 05.9063.14.DA
- 05.9063.ER.DA
- 05.9063.ES.DA

1-10V
- 05.9063.40.1V
- 05.9063.14.1V
- 05.9063.ER.1V
- 05.9063.ES.1V

Casambi
- 05.9063.40.CB
- 05.9063.14.CB
- 05.9063.ER.CB
- 05.9063.ES.CB



Luminous flux luminaire
1304 lm

Beam Angle:	33°
h(m) E(lx)	D(m)
1 4472	0.60
2 1118	1.20
3 497	1.80
4 279	2.40
5 179	3.00


Optic Flood - 3000K

On board dimmer
- 05.9068.40
- 05.9068.14
- 05.9068.ER
- 05.9068.ES

Dali 2
- 05.9068.40.DA
- 05.9068.14.DA
- 05.9068.ER.DA
- 05.9068.ES.DA

1-10V
- 05.9068.40.1V
- 05.9068.14.1V
- 05.9068.ER.1V
- 05.9068.ES.1V

Casambi
- 05.9068.40.CB
- 05.9068.14.CB
- 05.9068.ER.CB
- 05.9068.ES.CB




Luminous flux luminaire
1431 lm


Beam Angle:	33°
h(m) E(lx)	D(m)
1 4907	0.60
2 1227	1.20
3 545	1.80
4 307	2.40
5 196	3.00

Light Shadow Spot 60

Super Spot: LED Array 10W - 799 lm - 2700K/CRI 90 / 10W - 844 lm - 3000K/CRI 90
S/M/F/WF: LED Array 20W - 1563 lm - 2700K/CRI 90 / 20W - 1751 lm - 3000K/CRI 90







LED accent lighting module for installation in Infra-Structure system. For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Wide Flood - 2700K


On board dimmer
- 05.9064.40
- 05.9064.14
- 05.9064.ER
- 05.9064.ES

Dali 2
- 05.9064.40.DA
- 05.9064.14.DA
- 05.9064.ER.DA
- 05.9064.ES.DA

1-10V
- 05.9064.40.1V
- 05.9064.14.1V
- 05.9064.ER.1V
- 05.9064.ES.1V

Casambi
- 05.9064.40.CB
- 05.9064.14.CB
- 05.9064.ER.CB
- 05.9064.ES.CB





Luminous flux luminaire
1268 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	2761	0.79
2	690	1.59
3	307	2.38
4	173	3.17
5	110	3.97

Optic Wide Flood - 3000K


On board dimmer
- 05.9069.40
- 05.9069.14
- 05.9069.ER
- 05.9069.ES

Dali 2
- 05.9069.40.DA
- 05.9069.14.DA
- 05.9069.ER.DA
- 05.9069.ES.DA

1-10V
- 05.9069.40.1V
- 05.9069.14.1V
- 05.9069.ER.1V
- 05.9069.ES.1V

Casambi
- 05.9069.40.CB
- 05.9069.14.CB
- 05.9069.ER.CB
- 05.9069.ES.CB





Luminous flux luminaire
1390 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	3026	0.79
2	757	1.59
3	336	2.38
4	189	3.17
5	121	3.97

Accessories / Accesorios

Light Shadow Spot 30

Honeycomb	Panel de abeja		08.0790.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0791.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0792.00

Light Shadow Spot 45

Honeycomb	Panel de abeja		08.0793.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0794.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0795.00


Light Shadow Spot 60


Honeycomb	Panel de abeja		Super Spot 08.0175.14
			Spot / Medium / Flood / Wide Flood 08.0176.14
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase Super Spot 2700K >> 3125±75K 3000K >> 3600±75K 08.0796.00
			Spot / Medium / Flood / Wide Flood 2700K >> 3125±75K 3000K >> 3600±75K 08.0798.00
			Decrease Super Spot 2700K >> 2450±75K 3000K >> 2700±75K 08.0797.00
			Spot / Medium / Flood / Wide Flood 2700K >> 2450±75K 3000K >> 2700±75K 08.0799.00

Suspension Glass Downlight 110

LED Array 13,5W - 1296 lm - 2700K/CRI 90 / 13,5W - 1371 lm - 3000K/CRI 90







Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.
For wireless lighting control, choose Casambi versions.

Luminaria suspendida con varilla rígida y cristal soplado en distintos acabados para ser instalada en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

2700K

Black Rod
L: 100 mm
On board dimmer
- 03.8130.00
- 03.8130.FU
- 03.8130.RC

Dali 2
- 03.8130.00.DA
- 03.8130.FU.DA
- 03.8130.RC.DA

1-10V
- 03.8130.00.1V
- 03.8130.FU.1V
- 03.8130.RC.1V

Casambi
- 03.8130.00.CB
- 03.8130.FU.CB
- 03.8130.RC.CB

Black Rod
L: 400 mm
On board dimmer
- 03.8131.00
- 03.8131.FU
- 03.8131.RC

Dali 2
- 03.8131.00.DA
- 03.8131.FU.DA
- 03.8131.RC.DA

1-10V
- 03.8131.00.1V
- 03.8131.FU.1V
- 03.8131.RC.1V

Casambi
- 03.8131.00.CB
- 03.8131.FU.CB
- 03.8131.RC.CB


White Rod
L: 100 mm
On board dimmer
- 03.8135.00
- 03.8135.FU
- 03.8135.RC

Dali 2
- 03.8135.00.DA
- 03.8135.FU.DA
- 03.8135.RC.DA

1-10V
- 03.8135.00.1V
- 03.8135.FU.1V
- 03.8135.RC.1V

Casambi
- 03.8135.00.CB
- 03.8135.FU.CB
- 03.8135.RC.CB


82° .00



Luminous flux luminaire 706 lm

Beam Angle:	82°
h(m)	E(lx) D(m)
1	449 1.74
2	112 3.48
3	50 5.22
4	28 6.96
5	18 8.71


47° .FU



Luminous flux luminaire 483 lm

Beam Angle:	47°
h(m)	E(lx) D(m)
1	449 0.86
2	112 1.72
3	50 2.58
4	28 3.45
5	18 4.31

42° .RC



Luminous flux luminaire 292 lm

Beam Angle:	42°
h(m)	E(lx) D(m)
1	435 0.76
2	109 1.52
3	48 2.28
4	27 3.04
5	17 3.80

3000K

Black Rod
L: 100 mm
On board dimmer
- 03.8132.00
- 03.8132.FU
- 03.8132.RC

Dali 2
- 03.8132.00.DA
- 03.8132.FU.DA
- 03.8132.RC.DA

1-10V
- 03.8132.00.1V
- 03.8132.FU.1V
- 03.8132.RC.1V

Casambi
- 03.8132.00.CB
- 03.8132.FU.CB
- 03.8132.RC.CB

Black Rod
L: 400 mm
On board dimmer
- 03.8133.00
- 03.8133.FU
- 03.8133.RC

Dali 2
- 03.8133.00.DA
- 03.8133.FU.DA
- 03.8133.RC.DA

1-10V
- 03.8133.00.1V
- 03.8133.FU.1V
- 03.8133.RC.1V

Casambi
- 03.8133.00.CB
- 03.8133.FU.CB
- 03.8133.RC.CB


White Rod
L: 100 mm
On board dimmer
- 03.8137.00
- 03.8137.FU
- 03.8137.RC

Dali 2
- 03.8137.00.DA
- 03.8137.FU.DA
- 03.8137.RC.DA

1-10V
- 03.8137.00.1V
- 03.8137.FU.1V
- 03.8137.RC.1V

Casambi
- 03.8137.00.CB
- 03.8137.FU.CB
- 03.8137.RC.CB


82° .00



Luminous flux luminaire 746 lm

Beam Angle:	82°
h(m)	E(lx) D(m)
1	474 1.74
2	119 3.48
3	53 5.22
4	30 6.96
5	19 8.71


47° .FU



Luminous flux luminaire 510 lm

Beam Angle:	47°
h(m)	E(lx) D(m)
1	474 0.86
2	119 1.72
3	53 2.58
4	30 3.45
5	19 4.31

42° .RC



Luminous flux luminaire 309 lm

Beam Angle:	42°
h(m)	E(lx) D(m)
1	459 0.76
2	115 1.52
3	51 2.28
4	29 3.04
5	18 3.80


White Rod
L: 400 mm
On board dimmer
03.8136.00
03.8136.FU
03.8136.RC
Dali 2
03.8136.00.DA
03.8136.FU.DA
03.8136.RC.DA
1-10V
03.8136.00.1V
03.8136.FU.1V
03.8136.RC.1V
Casambi
03.8136.00.CB
03.8136.FU.CB
03.8136.RC.CB


White Rod
L: 400 mm
On board dimmer
03.8138.00
03.8138.FU
03.8138.RC
Dali 2
03.8138.00.DA
03.8138.FU.DA
03.8138.RC.DA
1-10V
03.8138.00.1V
03.8138.FU.1V
03.8138.RC.1V
Casambi
03.8138.00.CB
03.8138.FU.CB
03.8138.RC.CB

Suspension Panel 600

Top LED 25,6W - 3332 lm - 2700K/CRI 90 / 40W - 3540 lm - 3000K/ CRI 90







Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.
For wireless lighting control, choose Casambi versions.

E= External Finish
I= Internal Finish

Luminaria suspendida con varilla rígida para ser instalada en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

E= Acabado Externo
I= Acabado Interno

2700K

L: 100 mm

E I On board dimmer
03.8140.40A

E I Dali 2
03.8140.40ADA

E I 1-10V
03.8140.40A1V

E I Casambi
03.8140.40ACB


L: 400 mm

E I On board dimmer
03.8141.40A

E I Dali 2
03.8141.40ADA

E I 1-10V
03.8141.40A1V

E I Casambi
03.8141.40ACB



Luminous flux luminaire
1595 lm

Beam Angle: 113°

h(m)	E(lx)	D(m)
1	554	3.05
2	139	6.09
3	62	9.14
4	35	12.19
5	22	15.24

3000K

L: 100 mm

E I On board dimmer
03.8142.40A

E I Dali 2
03.8142.40ADA

E I 1-10V
03.8142.40A1V

E I Casambi
03.8142.40ACB


L: 400 mm

E I On board dimmer
03.8143.40A

E I Dali 2
03.8143.40ADA

E I 1-10V
03.8143.40A1V

E I Casambi
03.8143.40ACB



Luminous flux luminaire
1694 lm

Beam Angle: 113°

h(m)	E(lx)	D(m)
1	589	3.05
2	147	6.09
3	65	9.14
4	37	12.19
5	24	15.24

2700K

L: 100 mm

E I On board dimmer
03.8140.14A

E I Dali 2
03.8140.14ADA

E I 1-10V
03.8140.14A1V

E I Casambi
03.8140.14ACB


L: 400 mm

E I On board dimmer
03.8141.14A

E I Dali 2
03.8141.14ADA

E I 1-10V
03.8141.14A1V

E I Casambi
03.8141.14ACB



Luminous flux luminaire
1550 lm

Beam Angle: 113°

h(m)	E(lx)	D(m)
1	539	3.05
2	135	6.09
3	60	9.14
4	34	12.19
5	22	15.24

3000K

L: 100 mm

E I On board dimmer
03.8142.14A

E I Dali 2
03.8142.14ADA

E I 1-10V
03.8142.14A1V

E I Casambi
03.8142.14ACB


L: 400 mm

E I On board dimmer
03.8143.14A

E I Dali 2
03.8143.14ADA

E I 1-10V
03.8143.14A1V

E I Casambi
03.8143.14ACB



Luminous flux luminaire
1647 lm


Beam Angle: 113°


h(m)	E(lx)	D(m)
1	572	3.05
2	143	6.09
3	64	9.14
4	36	12.19
5	23	15.24

Multi Spot Mini

Power LED 7,5W - 635 lm - 2700K/CRI 90 / 7,5W - 650 lm - 3000K/CRI 90







LED lighting module with 14 spotlights and low glare, to be installed in The Infra-Structure system.
For wireless lighting control, choose integrated Casambi versions.

Módulo de iluminación LED de 14 focos y bajo deslumbramiento para ser instalado en el sistema Infra-Structure.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Optic Spot - 2700K


On board dimmer
- ☐ 05.3550.40
- ■ 05.3550.14

Dali 2
- ☐ 05.3550.40.DA
- ■ 05.3550.14.DA

1-10V
- ☐ 05.3550.40.1V
- ■ 05.3550.14.1V

Casambi
- ☐ 05.3550.40.CB
- ■ 05.3550.14.CB

15° SPOT



Luminous flux luminaire 398 lm (EXTREME CUT OFF)

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	3719	0.27
2	930	0.54
3	413	0.81
4	232	1.08
5	149	1.35

Optic Spot - 3000K


On board dimmer
- ☐ 05.3551.40
- ■ 05.3551.14

Dali 2
- ☐ 05.3551.40.DA
- ■ 05.3551.14.DA

1-10V
- ☐ 05.3551.40.1V
- ■ 05.3551.14.1V

Casambi
- ☐ 05.3551.40.CB
- ■ 05.3551.14.CB

15° SPOT



Luminous flux luminaire 405 lm (EXTREME CUT OFF)

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	3783	0.27
2	946	0.54
3	420	0.81
4	236	1.08
5	151	1.35

Optic Medium - 2700K


On board dimmer
- ☐ 05.3552.40
- ■ 05.3552.14

Dali 2
- ☐ 05.3552.40.DA
- ■ 05.3552.14.DA

1-10V
- ☐ 05.3552.40.1V
- ■ 05.3552.14.1V

Casambi
- ☐ 05.3552.40.CB
- ■ 05.3552.14.CB

20° MEDIUM



Luminous flux luminaire 424 lm (EXTREME CUT OFF)

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	2520	0.36
2	630	0.72
3	280	1.08
4	158	1.44
5	101	1.80

Optic Medium - 3000K


On board dimmer
- ☐ 05.3553.40
- ■ 05.3553.14

Dali 2
- ☐ 05.3553.40.DA
- ■ 05.3553.14.DA

1-10V
- ☐ 05.3553.40.1V
- ■ 05.3553.14.1V

Casambi
- ☐ 05.3553.40.CB
- ■ 05.3553.14.CB

20° MEDIUM



Luminous flux luminaire 431 lm (EXTREME CUT OFF)

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	2564	0.36
2	641	0.72
3	285	1.08
4	160	1.44
5	103	1.80

Optic Flood - 2700K


On board dimmer
- ☐ 05.3554.40
- ■ 05.3554.14

Dali 2
- ☐ 05.3554.40.DA
- ■ 05.3554.14.DA

1-10V
- ☐ 05.3554.40.1V
- ■ 05.3554.14.1V

Casambi
- ☐ 05.3554.40.CB
- ■ 05.3554.14.CB

32° FLOOD



Luminous flux luminaire 391 lm (EXTREME CUT OFF)

Beam Angle: 32°

h(m)	E(lx)	D(m)
1	1086	0.58
2	271	1.15
3	121	1.73
4	68	2.30
5	43	2.88

Optic Flood - 3000K


On board dimmer
- ☐ 05.3555.40
- ■ 05.3555.14

Dali 2
- ☐ 05.3555.40.DA
- ■ 05.3555.14.DA

1-10V
- ☐ 05.3555.40.1V
- ■ 05.3555.14.1V

Casambi
- ☐ 05.3555.40.CB
- ■ 05.3555.14.CB

32° FLOOD



Luminous flux luminaire 397 lm (EXTREME CUT OFF)

Beam Angle: 32°


h(m)	E(lx)	D(m)
1	1105	0.58
2	276	1.15
3	123	1.73
4	69	2.30
5	44	2.88

Accessories / Accesorios

Multifunction Smart Device.
Triple functionality 3x1: Casambi signal repeater, light sensor and presence detector.
FLOS Control® by Casambi.

Dispositivo multifunción inteligente.
Triple funcionalidad 3x1: repetidor de señal Casambi, sensor de luz ambiental y detector de presencia.
FLOS Control® by Casambi.







06.1988.40
06.1988.14

Multifunction Smart Device. Triple Functionality 3x1


Repeater



Daylight Sensor



Presence Sensor




▲ Casambi object

NEW


ZERO TRACK PRO

DESIGNED BY FLOS ARCHITECTURAL



Recessed Profiles

Black
Negro




Surface & Suspension Profiles

White
Blanco

Black
Negro

Brushed Steel
Acero Cepillado

Brushed Bronze
Bronce Cepillado



NEW

Description
Zero Track Pro is a low-voltage (24V) profile available in three versions: recessed, surface-mounted, and suspended, allowing it to integrate into different types of spaces. Its sleek and elegant design provides a modern and minimalist aesthetic.
Its reduced dimensions also hold the technology to control adjustment with protocols that allow professional management of appliances through data paths or wirelessly (either in broadcast mode or individually, point to point).

Control system
The system can be powered either by a remote power supply or by the surface-mounted Power Supply Drivers, which are available as accessories.
The integration of the tracks and electrical components into the profile allows the Pro version to have professional control systems that can manage appliances individually, point to point. Zero Track Pro therefore offers DALI and Casambi control protocols and in broadcast mode 1-10V (See the protocols available for each appliance).
To manage appliances through Casambi, you need the FLOS Control® mobile app (available to download from Apple Store and Google Play). There is an integrated Casambi electronics option on all appliances, except for Light Shadow Spot, Magic Stick and Light Stripes.
The initial power connector (live end feed) has space for cables either from the top or the back. The other elements that need power (feed) only have space for cables on the top.

Additional information
Zero Track Pro is supplied with a voltage of 24 VDC and is limited to a maximum current of 8A and to a maximum system power of 192W. It is also limited to a maximum of 10 metres and 10 interconnections.
For a 1-10V setting, you need an active control system (SOURCE) and a direct connection for the data control bus to the profile. You can connect a maximum of 25 appliances to the same control (each appliance requires a maximum of 2 mA). To transform passive control systems (SINK) into active systems (SOURCE), you need a "*Control Dimming Box*" located between the control unit and the track. It is best to use the "*Control Dimming Box*" recommended by Flos.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Regulatory Compliance and Quality Labels
Appliance compliant with the European Technical Regulation EN60598-1 and Part 2

Descripción
Zero Track Pro es un perfil de baja tensión (24V) disponible en tres versiones: empotrada, de superficie y suspensión, lo que permite su integración en diferentes tipos de espacios. Su diseño elegante y estilizado ofrece una estética moderna y minimalista.
Además alberga, en sus pequeñas dimensiones, la tecnología para el control de la regulación con protocolos que permiten la gestión profesional de las luminarias por pista de datos o de manera inalámbrica (tanto en broadcast, como individualmente punto a punto).

Sistema de Control
El sistema puede alimentarse mediante fuente de alimentación remota o con los "Power Supply Dirvers" para la versión de superficie -que se ofrecen como accesorios-.
La integración de las pistas y elementos eléctricos en el perfil permite a esta versión 'Pro' contar con sistemas de control profesionales capaces de gestionar las luminarias de manera individual, punto a punto. Así, Zero Track Pro ofrece protocolos de control DALI y Casambi y broadcast 1-10V (Consultar los protocolos disponibles en cada luminaria).
La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play). Todas las luminarias cuentan con opción de electrónica Casambi integrada -salvo los Light Shadow Spot, Magic Stick y las Light Stripes-.
El conector de alimentación inicial (live end feed) dispone de reserva para la entrada de los cables tanto por la parte superior como por la trasera. El resto de elementos alimentables ('feed') tienen reserva para la entrada de cables solo por la parte superior.

Información Adicional
Zero Track Pro se alimenta a una tensión de 24Vdc y está limitado a una corriente máxima de 8A y una potencia máxima del sistema de 192W. Además, está restrigido a un máximo de 10 metros y 10 interconexiones.
Para regulación 1-10V es necesario un sistema de control activo (SOURCE) y conectar el bus de datos de control directamente al perfil. Se podrán conectar un máximo 25 luminarias sobre el mismo control (cada luminaria precisa, como máximo, 2mA). Para transformar sistemas de control pasivos (SINK) en activos (SOURCE) es necesaria una *'Control Dimming Box'* ubicada entre la unidad de control y el carril. Se recomienda emplear la *'Control Dimming Box'* recomendada por Flos.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play

NEW

ZERO TRACK PRO

LIGHT MODULES

LIGHT STRIPE 600



LIGHT SOURCE
TOP LED
7W
555 lm
2700K/CRI 90
582 lm
3000K/CRI 90

LIGHT STRIPE 900

LIGHT SOURCE
TOP LED
10W
1111 lm
2700K/CRI 90
1166 lm
3000K/CRI 90

LIGHT STRIPE 1200

LIGHT SOURCE
TOP LED
13,5W
1667 lm
2700K/CRI 90
1750 lm
3000K/CRI 90

MAGIC STICK



LIGHT SOURCE
Power LED
10,5W
1200 lm
2700K/CRI 90
1200 lm
3000K/CRI 90

MAGIC STICK ASYMMETRIC



LIGHT SOURCE
Power LED
12W
1450 lm
2700K/CRI 90
1490 lm
3000K/CRI 90

FIND ME 0



LIGHT SOURCE
POWER LED
3,5W
276 lm
2700K/CRI 90
302 lm
3000K/CRI 90

FIND ME 1



LIGHT SOURCE
POWER LED
5,5W
432 lm
2700K/CRI 90
446 lm
3000K/CRI 90

FIND ME 2



LIGHT SOURCE
POWER LED
10,5W
724 lm
2700K/CRI 90
781 lm
3000K/CRI 90

FIND ME 1 SUSPENSION



LIGHT SOURCE
POWER LED
5,5W
432 lm
2700K/CRI 90
446 lm
3000K/CRI 90

MY SPOT Ø25 SHORT / LONG



LIGHT SOURCE
POWER LED
Up to 4,7W
231 lm
2700K/CRI 90
235 lm
3000K/CRI 90

MY SPOT Ø35 SHORT / LONG



LIGHT SOURCE
LED ARRAY
Up to 11W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

MULTI SPOT MINI



LIGHT SOURCE
POWER LED
6,1W
636 lm
2700K/CRI 90
672 lm
3000K/CRI 90

LIGHT SHADOW SPOT 30



LIGHT SOURCE
POWER LED
4,9W
297 lm
2700K/CRI 90
326 lm
3000K/CRI 90

LIGHT SHADOW SPOT 45



LIGHT SOURCE
LED ARRAY
11W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

ATOM 90



LIGHT SOURCE
POWER LED
5,5W
432 lm
2700K/CRI 90
446 lm
3000K/CRI 90

ATOM 120



LIGHT SOURCE
POWER LED
8W
600 lm
2700K/CRI 90
648 lm
3000K/CRI 90

ATOM 200



LIGHT SOURCE
TOP LED
10,5W
1005 lm
2700K/CRI 90
1080 lm
3000K/CRI 90

NEW

Magic Stick

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Multi Spot Mini

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Light Shadow Spot

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Find Me

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Atom

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



My Spot

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



NEW

HOW TO ORDER

1 CHOOSE YOUR PROFILE & LENGTH

RECESSED PROFILES
Non Dimmable / Dim

Zero Track Pro Standard



Zero Track Pro Reinforced



L: 1 / 2 / 3 m

SURFACE PROFILE
Non Dimmable / Dim



L: 1 / 2 / 3 m

2 COMPLETE WITH MOUNTING ACCESSORIES

Accessories
Standard

Fixed ceiling kit



or

Adjustable ceiling kit



Accessories
Standard & Reinforced

Live End Feed



Non Dimmable / Dim

Blind End



Straight Connector



Inner Corner



90° Corner



T Connector



X Connector



Live End Feed



Non Dimmable / Dim

Blind End



Track Cover



Straight Connector



Linear Connector Feed



Non Dimmable / Dim

Inner Corner



90° Corner Feed



Non Dimmable / Dim

X Connector Feed



Non Dimmable / Dim

T Connector Feed



Non Dimmable / Dim

NEW

3 SELECT POWER SUPPLY

Remote Installation Driver
Surface & Recessed



60W - 220/240V



120W - 220/240V



200W - 100/240V

Surface Installation Driver

Power Supply
Surface End



100W - 220/240V

or

Power Supply
Surface Middle



100W - 220/240V

4 SELECT A LIGHT MODULE AND CONTROL OPTION

No DIM / DALI / 1-10V

Light Stripe Surface
600 / 900 / 1200



General Lighting

Light Stripe Recessed
600 / 900 / 1200



General Lighting

Magic Stick
Magic Stick Asymmetric



General Lighting

Multi Spot Mini



S/M/F
Not available for Recessed Profile

Light Shadow Spot 30 / 45



S/M/F/WF

No DIM / DALI / 1-10V / Casambi

Find Me 0 / 1 / 2



S/M/F

Find Me Suspension



S/M

My Spot Ø25 / Ø35
Short / Long



S/M/F

Atom 90 / 120



S/M

Atom 200



General Lighting

NEW

HOW TO ORDER

1 CHOOSE YOUR PROFILE & LENGTH

2 COMPLETE WITH MOUNTING ACCESSORIES

SUSPENSION DOWN PROFILE
Non Dimmable / Dim
Coming Soon



L: 1 / 1,5 / 2 / 2,5 / 3 m

Electrical Accessories

Initial Electrical Kit	Intermediate Electrical Kit	Electrical linear joint	Electrical 90° Corner	Electrical T Connector	Electrical X Connector	Electrical Blind End
						

Mechanical Accessories

Initial Mechanical Kit	Intermediate Mechanical Kit	Mechanical linear joint	Mechanical 90° Corner	Mechanical T Connector	Mechanical X Connector	Mechanical Blind End
						

Accessories

Recessed Mechanical Kit	Surface Mechanical Kit	Rigid rod	Straight Connector	90° Corner Feed	X Connector Feed	T Connector Feed
						

SUSPENSION UP&DOWN PROFILE
Non Dimmable / Dim



L: 1 / 1,5 / 2 / 2,5 / 3 m

Electrical Accessories

Initial Electrical Kit	Intermediate Electrical Kit	Electrical linear joint	Electrical 90° Corner	Electrical T Connector	Electrical X Connector	Electrical Blind End
						

Mechanical Accessories

Initial Mechanical Kit	Intermediate Mechanical Kit	Mechanical linear joint	Mechanical 90° Corner	Mechanical T Connector	Mechanical X Connector	Mechanical Blind End
						

Accessories

Recessed Mechanical Kit	Surface Mechanical Kit	Rigid rod	Straight Connector	90° Corner Feed	X Connector Feed	T Connector Feed
						

NEW

3 SELECT POWER SUPPLY

Remote Installation Driver
Suspension Down/ Up&Down

Remote Kit
Non Dimmable



Dimmable



Surface Installation Driver
Suspension Down/ Up&Down

Surface Kit Initial
Non Dimmable



Surface Kit Intermediate
Dimmable



Surface Kit Initial
Non Dimmable



Surface Kit Intermediate
Dimmable



4 SELECT A LIGHT MODULE AND CONTROL OPTION

No DIM / DALI

Light Stripe Suspension
600 / 900 / 1200



General Lighting

Magic Stick
Magic Stick Asymmetric



General Lighting

Multi Spot Mini



S/M/F

Light Shadow Spot 30 / 45



S/M/F/WF

No DIM / DALI / Casambi

Find Me 0 / 1 / 2



S/M/F

Find Me Suspension



S/M

My Spot Ø25 / Ø35
Short / Long



S/M/F

Atom 90 / 120



S/M

Atom 200




General Lighting

NEW

ZERO TRACK PRO — PROFILES

RECESSED INSTALLATION





Profiles

Interior electromechanical recessed profile (24Vdc) from 1 to 3m long for wall or ceiling installation. Request power connectors, intermediate connectors, and covers separately. Unit joints available in L, T, and X shapes in the same plane. Also includes a linear electric connector for joining two track sections in the same plane and a 90º electromechanical connector for joining profile sections in different planes (interior wall-wall, ceiling-wall).
Two alternative profiles are available to fit any type of ceiling construction.


Perfiles

Perfil empotrado electromecánico interior (24Vdc) de 1 a 3 metros de largo para instalación en pared o techo. Solicitar conectores de alimentación, conectores intermedios y cubiertas por separado. Uniones disponibles en formas de L, T y X en el mismo plano. Incluye también un conector eléctrico lineal para unir dos secciones de carril en el mismo plano y un conector electromecánico de 90º para unir secciones de perfil en diferentes planos (pared interior-pared, techo-pared).
Hay dos perfiles alternativos disponibles para adaptarse a cualquier tipo de construcción de techo.






Zero Track Pro Standard



Zero Track Pro Reinforced



Non Dimmable
L: 1000 mm
06.2643.14
L: 2000 mm
06.2644.14
L: 3000 mm
06.2645.14

Dimmable
L: 1000 mm
06.2640.14
L: 2000 mm
06.2641.14
L: 3000 mm
06.2642.14

Non Dimmable
L: 1000 mm
06.0453.14
L: 2000 mm
06.0454.14
L: 3000 mm
06.0455.14


Dimmable
L: 1000 mm
06.0450.14
L: 2000 mm
06.0451.14
L: 3000 mm
06.0452.14

L: 1 m / 2 m / 3 m

Live End Feed
Power supply unit for the remote power source unit. Includes preinstalled power cable and is compatible with both on/off and dimmable versions.

Conector alimentación inicial
Unidad de alimentación para la unidad de fuente de alimentación remota. Incluye cable de alimentación preinstalado y es compatible con versiones on/off y regulables.






06.0456.14

90º Corner
90º flat corner with no feed entry.

Esquina 90º
Esquina plana de 90º sin entrada de alimentación.






06.0457.14

Inner Corner
Ceiling/wall - wall/wall inner corner with no feed entry.

Esquina interior
Esquina interior techo/pared - pared/pared. Sin entrada de alimentación.






06.0458.14

T Connector
T-shaped connector with no feed entry.

Conector en forma de «T»
Conector en forma de "T" sin entrada de alimentación.






06.0459.14

X Connector
Cross-shaped connector with no feed entry.

Conector en forma de cruz
Conector en forma de "X" sin entrada de alimentación.






06.0460.14

Blind End
End Cap. 2 unit kit.

Terminal de cierre
Tapa. Kit de 2 unidades.





06.0461.14

Straight Connector
Intermediate connector with no feed entry.

Conector recto
Conector intermedio sin entrada de alimentación.





06.2608.14


Accessories / Accesorios

Compatible only with Zero Track Pro Standard

Fixed ceiling kit (optional).
2 unit kit.

Kit de sujeción a techo fijo (opcional). Kit de 2 unidades.






08.8866.14

Profile (mm)	Fixation points	Ceiling Kit to order
1000	2	1
2000	3	2
3000	4	2

Adjustable ceiling kit (optional).
2 unit kit.

Kit de sujeción a techo ajustable (opcional). Kit de 2 unidades.






08.8867.14

Profile (mm)	Fixation points	Ceiling Kit to order
1000	2	1
2000	3	2
3000	4	2

NEW

ZERO TRACK PRO — PROFILES

SURFACE INSTALLATION




Profiles

Interior electromechanical profile (24Vdc) from 1 to 3m long for wall or ceiling installation, fastened with special screws and plugs provided with the profile. Request power connectors, intermediate connectors and covers separately. Feed unit joints available in the form of L, T and X in the same plane. It also has a linear electric connector for joining two track sections in the same plane and a 90º electromechanical connector for joining profile sections in different planes (interior wall-wall, ceiling-wall). Aesthetic covers for the inner profile gap available as an option.

Perfiles

Perfil electromecánico (24Vdc) de interior - con longitudes de 1 a 3m- para su instalación en superficie (techo o pared) con fijación mediante tornillos y tacos específicos servidos con el perfil. Necesario pedir por separado conector de alimentación, conectores intermedios y tapas. Disponibles uniones mecánicas alimentables en forma de L, T y X en el mismo plano. También dispone de un conector eléctrico lineal para unir dos segmentos de carril en el mismo plano y un conector electro-mecánico en forma de esquina de 90º para unir segmentos del perfil en distinto plano (techo-pared y pared-pared interior). También se ofrecen tapas estéticas opcionales para cubrir el hueco interior del perfil.



L: 1 m / 2 m / 3 m


Non Dimmable	Dimmable
L: 1000 mm	L: 1000 mm
06.2603.40	06.2600.40
06.2603.14	06.2600.14
06.2603.ER	06.2600.ER
06.2603.ES	06.2600.ES
L: 2000 mm	L: 2000 mm
06.2604.40	06.2601.40
06.2604.14	06.2601.14
06.2604.ER	06.2601.ER
06.2604.ES	06.2601.ES
L: 3000 mm	L: 3000 mm
06.2605.40	06.2602.40
06.2605.14	06.2602.14

NEW

Live End Feed
Feed unit for remote power supply unit. Power cable inserting is possible both from the Rear and the side.

Conector alimentación inicial
Unidad de alimentación para fuente de alimentación remota. La inserción del cable de alimentación es posible tanto desde la parte trasera como desde el lateral.






Non Dimmable
06.2613.40
06.2613.14
06.2613.ER
06.2613.ES

Dimmable
06.2606.40
06.2606.14
06.2606.ER
06.2606.ES

Linear Connector Feed
Feed intermediate connector. Rear feeding cable entry.

Conector alimentación lineal
Conector de alimentación intermedio. Entrada del cable de alimentación por la parte trasera.





Non Dimmable
06.2621.40
06.2621.14
06.2621.ER
06.2621.ES

Dimmable
06.2607.40
06.2607.14
06.2607.ER
06.2607.ES

Straight Connector
Intermediate connector with no feed entry.

Conector recto
Conector intermedio sin entrada de alimentación.






06.2608.40
06.2608.14

90º Corner Feed
90º flat corner. Can be powered. It has a rear space for the supply connection. Rear feeding cable entry.

Alimentación Esquina 90º
Esquina plana 90º. Alimentable. Con reserva para acometida por la parte trasera. Entrada del cable de alimentación por la parte trasera.






Non Dimmable
06.2614.40
06.2614.14
06.2614.ER
06.2614.ES

Dimmable
06.2609.40
06.2609.14
06.2609.ER
06.2609.ES

Inner Corner
Ceiling/wall - wall/wall inner corner. Rear feeding cable entry.

Esquina interior
Esquina interior techo/pared - pared/pared. Entrada del cable de alimentación por la parte trasera.






06.2610.40
06.2610.14

HOW TO INSTALL ZERO TRACK PRO


Installation Examples. Valid for: Feed Elements [A], Connectors [A], Inner Corner [A], Power Supply Boxes [A], Blind End [B] and Track Covers [C].

Ejemplos de instalación. Válidos para: Feed Elements [A], Connectors [A], Inner Corner [A], Power Supply Boxes [A], Blind End [B] y Track Covers [C].


A




A



B




C



T Connector Feed
T-shaped connector. Can be powered via connections on the back. Rear feeding cable entry.

Conector alimentación en forma de «T»
Conector en forma de «T». Alimentable, con acometida por la parte trasera. Entrada del cable de alimentación por la parte trasera.






Non Dimmable
06.2615.40
06.2615.14
06.2615.ER
06.2615.ES

Dimmable
06.2611.40
06.2611.14
06.2611.ER
06.2611.ES

X Connector Feed
Cross-shaped connector. Can be powered via connections on the back. Rear feeding cable entry.

Conector alimentación en forma de cruz
Conector en forma de cruz. Alimentable, con acometida por la parte trasera. Entrada del cable de alimentación por la parte trasera.






Non Dimmable
06.2616.40
06.2616.14
06.2616.ER
06.2616.ES

Dimmable
06.2612.40
06.2612.14
06.2612.ER
06.2612.ES

Blind End
End Cap.

Terminal de cierre
Tapa.






06.2617.40
06.2617.14
06.2617.ER
06.2617.ES

Track Cover
Attractive cover for the inside of the profile. Only available in black and white.

Tapa embellecedora
Tapa embellecedora para cubrir el interior del perfil. Sólo disponible en blanco y negro.





06.2618.40A
06.2618.14A

NEW


Drivers / Equipos

Surface Installation Driver (Only Surface Track)

Power supply surface end.

Fuente de alimentación inicial para instalación en superficie.






96W - 220/240V
06.2619.40
06.2619.14
06.2619.ER
06.2619.ES

Power supply surface middle.

Fuente de alimentación intermedia para instalación en superficie.






96W - 220/240V
06.2620.40
06.2620.14
06.2620.ER
06.2620.ES

Remote Installation (Recessed and Surface Track)

LED power supply source for remote installation in 24V/200W electric control panel.

Fuente de alimentación LED para instalación remota en cuadro eléctrico 24V/200W.






200W - 100/240V
60.9352

Power supply source with constant voltage 24V - 120W, 220-240W-50/60Hz.

Fuente de alimentación de tensión constante 24V - 120W, 220-240W-50/60Hz.






120W - 220/240V
60.9777A

Power supply source with constant voltage 24V - 60W, 220-240W-50/60Hz.

Fuente de alimentación de tensión constante 24V - 60W, 220-240W-50/60Hz.






60W - 220/240V
60.9705A

Control Units / Unidades de Control

Control dimming box, 1-10V, 24/48V. For remote installation. For transforming passive systems (SINK) into active systems (SOURCE). It must be positioned between the control unit and the track. Important note: Maximum of 25 light modules.

Caja de control dimable 1-10V, 24/48V. Para instalación remota. Para transformar sistemas pasivos (SINK) en activos (SOURCE). Debe ubicarse entre la unidad de control y el carril. Nota importante: Máx. 25 módulos de luz.




DIM 1-10V - 24/48V
08.0613.14A

NEW

ZERO TRACK PRO — PROFILES

SUSPENSION DOWN INSTALLATION




Profiles

Interior electromechanical profile (24Vdc) from 1 to 3m long for suspended installation, fastened with special screws and plugs provided with the profile. Request power connectors, intermediate connectors, and covers separately. Unit joints available in the form of L, T, and X in the same plane. It also has a linear electric connector for joining two track sections in the same plane.

Perfiles

Perfil electromecánico interior (24Vdc) de 1 a 3m de longitud para instalación suspendida, fijado con tornillos especiales y tacos proporcionados con el perfil. Solicitar conectores de alimentación, conectores intermedios y cubiertas por separado. Juntas de unidades disponibles en forma de L, T y X en el mismo plano. También cuenta con un conector eléctrico lineal para unir dos secciones de la vía en el mismo plano.



L: 1 m / 1,5 m / 2 m / 2,5 m / 3 m

NEW

ZERO TRACK PRO — PROFILES

SUSPENSION DOWN INSTALLATION

Non Dimmable Profile Feed

L: 1000 mm
- 06.0560.40
- 06.0560.14
- 06.0560.ER
- 06.0560.ES

L: 1500 mm
- 06.0561.40
- 06.0561.14
- 06.0561.ER
- 06.0561.ES

L: 2000 mm
- 06.0562.40
- 06.0562.14
- 06.0562.ER
- 06.0562.ES

L: 2500 mm
- 06.0563.40
- 06.0563.14

L: 3000 mm
- 06.0564.40
- 06.0565.14

Non Dimmable Profile Intermediate

L: 1000 mm
- 06.0565.40
- 06.0565.14
- 06.0565.ER
- 06.0565.ES

L: 1500 mm
- 06.0566.40
- 06.0566.14
- 06.0566.ER
- 06.0566.ES

L: 2000 mm
- 06.0567.40
- 06.0567.14
- 06.0567.ER
- 06.0567.ES

L: 2500 mm
- 06.0568.40
- 06.0568.14

L: 3000 mm
- 06.0569.40
- 06.0569.14

Dali Profile Feed

L: 1000 mm
- 06.0550.40
- 06.0550.14
- 06.0550.ER
- 06.0550.ES

L: 1500 mm
- 06.0551.40
- 06.0551.14
- 06.0551.ER
- 06.0551.ES

L: 2000 mm
- 06.0552.40
- 06.0552.14
- 06.0552.ER
- 06.0552.ES

L: 2500 mm
- 06.0553.40
- 06.0553.14

L: 3000 mm
- 06.0554.40
- 06.0555.14

Dali Profile Intermediate

L: 1000 mm
- 06.0555.40
- 06.0555.14
- 06.0555.ER
- 06.0555.ES

L: 1500 mm
- 06.0556.40
- 06.0556.14
- 06.0556.ER
- 06.0556.ES

L: 2000 mm
- 06.0557.40
- 06.0557.14
- 06.0557.ER
- 06.0557.ES


L: 2500 mm
- 06.0558.40
- 06.0558.14

L: 3000 mm
- 06.0559.40
- 06.0559.14

Initial Electrical Kit
Electrical kit required for the initial system connection.

Kit Eléctrico Inicial
Kit eléctrico necesario para la conexión inicial del sistema.






■ 06.0683.00

Intermediate Electrical Kit
Intermediate electrical kit to extend or connect multiple modules.

Kit Eléctrico Intermedio
Kit eléctrico intermedio para extender o conectar múltiples módulos.






■ 06.0684.00

Electrical linear joint
Linear connection used to distribute power in a straight line.

Junta Lineal Eléctrica
Conexión lineal utilizada para distribuir energía en línea recta.






□ 06.0574.40
■ 06.0574.14
□ 06.0574.ER
■ 06.0574.ES

Electrical 90° Corner
90° corner connector used to distribute power at right angles.

Esquina de 90° Eléctrica
Conector de esquina de 90° utilizado para distribuir energía en ángulos rectos.






□ 06.0575.40
■ 06.0575.14
□ 06.0575.ER
■ 06.0575.ES

Electrical T Connector
"T" connector used to distribute power to three different points at right angles.

Conector Eléctrico en forma de "T"
Conector en forma de "T" utilizado para distribuir energía a tres puntos diferentes en ángulos rectos.






□ 06.0576.40
■ 06.0576.14
□ 06.0576.ER
■ 06.0576.ES

Electrical X Connector
"X" connector used to distribute power to four different points at right angles.

Conector Eléctrico en formaa de "X"
Conector en forma de "X" utilizado para distribuir energía a cuatro puntos diferentes en ángulos rectos.






□ 06.0577.40
■ 06.0577.14
□ 06.0577.ER
■ 06.0577.ES

Rod Initial Electrical Kit
Electrical kit required for the initial connection of the system with rigid rod.

Rod Kit Eléctrico Inicial
Kit eléctrico necesario para la conexión inicial del sistema con varilla rígida.






□ 06.0731.40
■ 06.0731.14

Rod Intermediate Electrical Kit
Intermediate electrical kit to extend or connect multiple modules with rigid rod.

Rod Kit Eléctrico Intermedio
Kit eléctrico intermedio para extender o conectar múltiples módulos con varilla rígida.





□ 06.0733.40
■ 06.0733.14

Rigid rod
2 m suspension rod, cuttable to size. Recommended to prevent profile tilting in linear structures or in installations where a more rigid fixing system is required. Not compatible with surface-mounted power supply box.

Varilla rígida
Varilla de suspensión de 2 m, cortable a medida. Recomendada para evitar la inclinación del perfil en estructuras lineales donde se requiere un sistema de fijación más rígido. No aplicable con caja de alimentación de superficie.



2 pcs.
□ 06.0737.40
■ 06.0737.14
□ 06.0737.ER
■ 06.0737.ES


3 pcs.
□ 06.0738.40
■ 06.0738.14
□ 06.0738.ER
■ 06.0738.ES

NEW

Initial Mechanical Kit
Mechanical kit for the initial structural installation.

Kit Mecánico Inicial
Kit mecánico para la instalación estructural inicial.






■ 06.0670.00

Intermediate Mechanical Kit
Intermediate mechanical kit to connect additional sections.

Kit Mecánico Intermedio
Kit mecánico intermedio para conectar secciones adicionales.






■ 06.0671.00

Mechanical linear joint
Linear connection used to join components in a straight line.

Junta Lineal Mecánica
Conexión lineal utilizada para distribuir energía en línea recta.






□ 06.0570.40
■ 06.0570.14
▨ 06.0570.ER
▩ 06.0570.ES

Mechanical 90° Corner
90° corner connector used to join components at a right angle.

Esquina de 90° Mecánica
Conector de esquina de 90° utilizado para distribuir energía en ángulos rectos.






□ 06.0571.40
■ 06.0571.14
▨ 06.0571.ER
▩ 06.0571.ES

Mechanical T Connector
"T" connector used to join three components at right angles.

Conector Mecánico en forma de "T"
Conector en forma de "T" utilizado para distribuir energía a tres puntos diferentes en ángulos rectos.






□ 06.0572.40
■ 06.0572.14
▨ 06.0572.ER
▩ 06.0572.ES

Mechanical X Connector
"X" connector used to join four components at right angles.

Conector Mecánico en forma de "X"
Conector en forma de "X" utilizado para distribuir energía a cuatro puntos diferentes en ángulos rectos.






□ 06.0573.40
■ 06.0573.14
▨ 06.0573.ER
▩ 06.0573.ES

Rod Initial Mechanical Kit
Mechanical kit required for the initial connection of the system with rigid rod.

Rod Kit Mecánico Inicial
Kit mecánico necesario para la conexión inicial del sistema con varilla rígida.






□ 06.0735.40
■ 06.0735.14

Rod Intermediate Mechanical Kit
Intermediate mechanical kit to extend or connect multiple modules with rigid rod.

Rod Kit Mecánico Intermedio
Kit mecánico intermedio para extender o conectar múltiples módulos con varilla rígida.






□ 06.0736.40
■ 06.0736.14

Blind End
End Cap.

Terminal de cierre
Tapa.






□ 06.0578.40
■ 06.0578.14
▨ 06.0578.ER
▩ 06.0578.ES

NEW

ZERO TRACK PRO — PROFILES

SUSPENSION UP&DOWN INSTALLATION




Profiles


Interior electromechanical profile (24Vdc) from 1 to 3 m in length for suspended installation with indirect lighting on the upper side. Linear profiles are available in two versions: power profiles, for driver connection, and intermediate profiles. Corners do not include indirect lighting.
Power connectors, intermediate connectors and end caps must be ordered separately. Mechanical and electrical joints are available in linear form, as well as in L, T and X shapes on the same plane.

Perfiles

Perfil electromecánico interior (24Vdc) de 1 a 3m de longitud para instalación suspendida con iluminación indirecta en la parte superior. Perfiles lineales disponibles en dos versiones: perfiles de alimentación, para conexión a driver, y perfiles intermedios. Las esquinas no llevan iluminación indirecta.
Solicitar conectores de alimentación, conectores intermedios y tapas por separado. Juntas mecánicas y eléctricas disponibles en forma lineal, así como en L, T y X en el mismo plano.




2700K



Luminous flux luminaire
460 lm

Beam Angle:	85°
h(m)	E(lx) D(m)
1	205 1.85
2	51 3.70
3	23 5.55
4	13 7.39
5	8 9.24

3000K



Luminous flux luminaire
496 lm

Beam Angle:	85°
h(m)	E(lx) D(m)
1	222 1.85
2	55 3.70
3	25 5.55
4	14 7.39
5	9 9.24

L: 1 m / 1,5 m / 2 m / 2,5 m / 3 m

Power LED 5,6W/m - 640 lm/m - 2700K/CRI 90 / 691 lm/m - 3000K/CRI 90

NEW

ZERO TRACK PRO — PROFILES

SUSPENSION UP&DOWN INSTALLATION

Non Dimmable Profile Feed

2700K

L: 1000 mm
- 06.0600.40
- 06.0600.14
- 06.0600.ER
- 06.0600.ES

L: 1500 mm
- 06.0603.40
- 06.0603.14
- 06.0603.ER
- 06.0603.ES

L: 2000 mm
- 06.0606.40
- 06.0606.14
- 06.0606.ER
- 06.0606.ES

L: 2500 mm
- 06.0609.40
- 06.0609.14

L: 3000 mm
- 06.0612.40
- 06.0612.14

3000K

L: 1000 mm
- 06.0620.40
- 06.0620.14
- 06.0620.ER
- 06.0620.ES

L: 1500 mm
- 06.0623.40
- 06.0623.14
- 06.0623.ER
- 06.0623.ES

L: 2000 mm
- 06.0626.40
- 06.0626.14
- 06.0626.ER
- 06.0626.ES

L: 2500 mm
- 06.0629.40
- 06.0629.14

L: 3000 mm
- 06.0632.40
- 06.0632.14

Non Dimmable / Casambi Profile Intermediate

2700K

L: 1000 mm
- 06.0640.40
- 06.0640.14
- 06.0640.ER
- 06.0640.ES

L: 1500 mm
- 06.0642.40
- 06.0642.14
- 06.0642.ER
- 06.0642.ES

L: 2000 mm
- 06.0644.40
- 06.0644.14
- 06.0644.ER
- 06.0644.ES

L: 2500 mm
- 06.0646.40
- 06.0646.14

L: 3000 mm
- 06.0648.40
- 06.0648.14

3000K

L: 1000 mm
- 06.0650.40
- 06.0650.14
- 06.0650.ER
- 06.0650.ES

L: 1500 mm
- 06.0652.40
- 06.0652.14
- 06.0652.ER
- 06.0652.ES

L: 2000 mm
- 06.0654.40
- 06.0654.14
- 06.0654.ER
- 06.0654.ES

L: 2500 mm
- 06.0656.40
- 06.0656.14

L: 3000 mm
- 06.0658.40
- 06.0658.14

Casambi Profile Feed

2700K

L: 1000 mm
- 06.0602.40
- 06.0602.14
- 06.0602.ER
- 06.0602.ES

L: 1500 mm
- 06.0605.40
- 06.0605.14
- 06.0605.ER
- 06.0605.ES

L: 2000 mm
- 06.0608.40
- 06.0608.14
- 06.0608.ER
- 06.0608.ES

L: 2500 mm
- 06.0611.40
- 06.0611.14

L: 3000 mm
- 06.0614.40
- 06.0614.14

3000K

L: 1000 mm
- 06.0622.40
- 06.0622.14
- 06.0622.ER
- 06.0622.ES

L: 1500 mm
- 06.0625.40
- 06.0625.14
- 06.0625.ER
- 06.0625.ES

L: 2000 mm
- 06.0628.40
- 06.0628.14
- 06.0628.ER
- 06.0628.ES

L: 2500 mm
- 06.0631.40
- 06.0631.14

L: 3000 mm
- 06.0634.40
- 06.0634.14

Dali Profile Feed

2700K

L: 1000 mm
- 06.0601.40
- 06.0601.14
- 06.0601.ER
- 06.0601.ES

L: 1500 mm
- 06.0604.40
- 06.0604.14
- 06.0604.ER
- 06.0604.ES

L: 2000 mm
- 06.0607.40
- 06.0607.14
- 06.0607.ER
- 06.0607.ES

L: 2500 mm
- 06.0610.40
- 06.0610.14

L: 3000 mm
- 06.0613.40
- 06.0613.14

3000K

L: 1000 mm
- 06.0621.40
- 06.0621.14
- 06.0621.ER
- 06.0621.ES

L: 1500 mm
- 06.0624.40
- 06.0624.14
- 06.0624.ER
- 06.0624.ES

L: 2000 mm
- 06.0627.40
- 06.0627.14
- 06.0627.ER
- 06.0627.ES

L: 2500 mm
- 06.0630.40
- 06.0630.14

L: 3000 mm
- 06.0633.40
- 06.0633.14

Dali Profile Intermediate

2700K

L: 1000 mm
- 06.0641.40
- 06.0641.14
- 06.0641.ER
- 06.0641.ES

L: 1500 mm
- 06.0643.40
- 06.0643.14
- 06.0643.ER
- 06.0643.ES

L: 2000 mm
- 06.0645.40
- 06.0645.14
- 06.0645.ER
- 06.0645.ES

L: 2500 mm
- 06.0647.40
- 06.0647.14

L: 3000 mm
- 06.0649.40
- 06.0649.14

3000K

L: 1000 mm
- 06.0651.40
- 06.0651.14
- 06.0651.ER
- 06.0651.ES

L: 1500 mm
- 06.0653.40
- 06.0653.14
- 06.0653.ER
- 06.0653.ES

L: 2000 mm
- 06.0655.40
- 06.0655.14
- 06.0655.ER
- 06.0655.ES


L: 2500 mm
- 06.0657.40
- 06.0657.14

L: 3000 mm
- 06.0659.40
- 06.0659.14

Initial Electrical Kit
Electrical kit required for the initial system connection.

Kit Eléctrico Inicial
Kit eléctrico necesario para la conexión inicial del sistema.






■ 06.0672.00

Intermediate Electrical Kit
Intermediate electrical kit to extend or connect multiple modules.

Kit Eléctrico Intermedio
Kit eléctrico intermedio para extender o conectar múltiples módulos.






■ 06.0673.00

Electrical linear joint
Linear connection used to distribute power in a straight line.

Junta Lineal Eléctrica
Conexión lineal utilizada para distribuir energía en línea recta.






□ 06.0664.40
■ 06.0664.14
06.0664.ER
06.0664.ES

Electrical 90° Corner
90° corner connector used to distribute power at right angles.

Esquina de 90° Eléctrica
Conector de esquina de 90° utilizado para distribuir energía en ángulos rectos.






□ 06.0665.40
■ 06.0665.14
06.0665.ER
06.0665.ES

Electrical T Connector
"T" connector used to distribute power to three different points at right angles.

Conector Eléctrico en forma de "T"
Conector en forma de "T" utilizado para distribuir energía a tres puntos diferentes en ángulos rectos.






□ 06.0666.40
■ 06.0666.14
06.0666.ER
06.0666.ES

Electrical X Connector
"X" connector used to distribute power to four different points at right angles.

Conector Eléctrico en forma de "X"
Conector en forma de "X" utilizado para distribuir energía a cuatro puntos diferentes en ángulos rectos.






□ 06.0667.40
■ 06.0667.14
06.0667.ER
06.0667.ES

Rod Initial Electrical Kit
Electrical kit required for the initial connection of the system with rigid rod.

Rod Kit Eléctrico Inicial
Kit eléctrico necesario para la conexión inicial del sistema con varilla rígida.






□ 06.0732.40
■ 06.0732.14

Rod Intermediate Electrical Kit
Intermediate electrical kit to extend or connect multiple modules with rigid rod.

Rod Kit Eléctrico Intermedio
Kit eléctrico intermedio para extender o conectar múltiples módulos con varilla rígida.





□ 06.0734.40
■ 06.0734.14

Rigid rod
2 m suspension rod, cuttable to size. Recommended to prevent profile tilting in linear structures or in installations where a more rigid fixing system is required. Not compatible with surface-mounted power supply box.

Varilla rígida
Varilla de suspensión de 2 m, cortable a medida. Recomendada para evitar la inclinación del perfil en estructuras lineales donde se requiere un sistema de fijación más rígido. No aplicable con caja de alimentación de superficie.




2 pcs.
□ 06.0737.40
■ 06.0737.14
06.0737.ER
06.0737.ES
3 pcs.
□ 06.0738.40
■ 06.0738.14
06.0738.ER
06.0738.ES

NEW

Initial Mechanical Kit
Mechanical kit for the initial structural installation.

Kit Mecánico Inicial
Kit mecánico para la instalación estructural inicial.






■ 06.0670.00

Intermediate Mechanical Kit
Intermediate mechanical kit to connect additional sections.

Kit Mecánico Intermedio
Kit mecánico intermedio para conectar secciones adicionales.






■ 06.0671.00

Mechanical linear joint
Linear connection used to join components in a straight line.

Junta Lineal Mecánica
Conexión lineal utilizada para distribuir energía en línea recta.






□ 06.0660.40
■ 06.0660.14
06.0660.ER
06.0660.ES

Mechanical 90° Corner
90° corner connector used to join components at a right angle.

Esquina de 90° Mecánica
Conector de esquina de 90° utilizado para distribuir energía en ángulos rectos.






□ 06.0661.40
■ 06.0661.14
06.0661.ER
06.0661.ES

Mechanical T Connector
"T" connector used to join three components at right angles.

Conector Mecánico en forma de "T"
Conector en forma de "T" utilizado para distribuir energía a tres puntos diferentes en ángulos rectos.






□ 06.0662.40
■ 06.0662.14
06.0662.ER
06.0662.ES

Mechanical X Connector
"X" connector used to join four components at right angles.

Conector Mecánico en forma de "X"
Conector en forma de "X" utilizado para distribuir energía a cuatro puntos diferentes en ángulos rectos.






□ 06.0663.40
■ 06.0663.14
06.0663.ER
06.0663.ES

Rod Initial Mechanical Kit
Mechanical kit required for the initial connection of the system with rigid rod.

Rod Kit Mecánico Inicial
Kit mecánico necesario para la conexión inicial del sistema con varilla rígida.






□ 06.0735.40
■ 06.0735.14

Rod Intermediate Mechanical Kit
Intermediate mechanical kit to extend or connect multiple modules with rigid rod.

Rod Kit Mecánico Intermedio
Kit mecánico intermedio para extender o conectar múltiples módulos con varilla rígida.






□ 06.0736.40
■ 06.0736.14

Blind End
End Cap.

Terminal de cierre
Tapa.





□ 06.0668.40
■ 06.0668.14
06.0668.ER
06.0668.ES

NEW

ZERO TRACK PRO — ACCESSORIES & ADAPTERS

SUSPENSION DOWN & UP&DOWN ACCESSORIES

Mounting Accessories* / Accesorios de montaje*

Recessed Mechanical Kit
Suspension Kit for recessed installations.

Kit Mecánico Empotrado
Kit de suspensión para instalaciones empotradas.





- 06.0674.40
- 06.0674.14
- 06.0674.ER
- 06.0674.ES

Surface Mechanical Kit
Suspension Kit for surface installations.

Kit Mecánico de superficie
Kit de suspensión para instalaciones de superficie.





06.0675.00

Feed Connectors / Conectores de alimentación

Straight Connector
Intermediate connector with no feed entry.

Conector lineal
Conector intermedio sin entrada de alimentación.






- 06.2608.14

90° Corner
90° flat corner with no feed entry.

Esquina de 90°
Esquina plana de 90° sin entrada de alimentación.






- 06.0457.14

T-Shaped Connector
T-shaped connector with no feed entry.

Conector en forma de "T"
Conector en forma de "T" sin entrada de alimentación.






- 06.0459.14

X-Shaped Connector
Cross-shaped connector with no feed entry.

Conector en forma de "X"
Conector en forma de "X" sin entrada de alimentación.





- 06.0460.14

---

*For profiles of 2.5 or 3 meters, an additional accessory is required in the middle section because it comes with one more tensioner.
*Para perfiles de 2,5 o 3 metros, se requiere un accesorio adicional en la sección central, ya que incluye un tensor adicional.

NEW

Drivers / Equipos

Remote Kit No Dim
Power supply for remote installation Non-Dimmable.

Kit Remoto No Regulable
Fuente de alimentación para instalación remota No regulable.






60W
08.1230.40
08.1230.14
08.1230.ER
08.1230.ES
120W
08.1236.40
08.1236.14
08.1236.ER
08.1236.ES
200W
08.1238.40
08.1238.14
08.1238.ER
08.1238.ES

Remote Kit Dimmable
Power supply for remote installation Dimmable.

Kit Remoto Regulable
Fuente de alimentación para instalación remota Regulable.






60W
08.1231.40
08.1231.14
08.1231.ER
08.1231.ES
120W
08.1237.40
08.1237.14
08.1237.ER
08.1237.ES
200W
08.1239.40
08.1239.14
08.1239.ER
08.1239.ES

Surface Kit Initial No Dim*
Initial power supply for surface installation Non-Dimmable.

Kit de Superficie Inicial No Regulable*
Fuente de alimentación inicial para instalación en superficie No regulable.






150W
08.1232.40
08.1232.14

Surface Kit Intermediate No Dim*
Power supply surface middle Non-Dimmable.

Kit de Superficie Intermedio No Regulable*
Fuente de alimentación de superficie media No regulable.






150W
08.1233.40
08.1233.14

Surface Kit Initial Dimmable*
Initial power supply for surface installation Dimmable.

Kit de Superficie Inicial Regulable*
Fuente de alimentación inicial para instalación en superficie Regulable.







150W
08.1234.40
08.1234.14

Surface Kit Intermediate Dimmable*
Power supply surface middle Dimmable.

Kit de Superficie Intermedio Regulable*
Fuente de alimentación de superficie media Regulable.





150W
08.1235.40
08.1235.14

---

*Use the initial or the intermediate one depending on where the power supply point is located on the ceiling.
*Utiliza el inicial o el intermedio según la ubicación del punto de alimentación en el techo.

• What is the maximum distance allowed between the power supply and the profile?
With the available power supplies, the maximum allowed distance is 5 meters.

• What is the maximum length that can be powered by a single power supply in a structure?
The maximum profile length that can be powered by a single power supply is 9 m.


• Is it necessary to pay special attention to the position of the lighting modules in linear installations to avoid profile swinging?
Yes. It is important to distribute the weight of the modules correctly to prevent any profile movement. For total stability, we offer an optional rigid rod that replaces the cable and ensures excellent performance, especially in linear installations.

• ¿Cuál es la distancia máxima permitida entre la fuente de alimentación y el perfil?
Con las fuentes de alimentación que se ofrecen, la distancia máxima permitida es de 5 metros.


• ¿Cuál es la longitud máxima que se puede alimentar con una fuente de alimentación en una estructura?
La longitud máxima de perfil que puede alimentarse con una única fuente de alimentación es de 9 m.

• ¿Es necesario prestar especial atención a la posición de los módulos de iluminación en instalaciones lineales para evitar el balanceo del perfil?
Sí. Es importante repartir correctamente el peso de los módulos para evitar cualquier oscilación del perfil. Para aportar una estabilidad total, disponemos de una varilla rígida opcional que sustituye al cable y garantiza un excelente comportamiento, especialmente en instalaciones lineales.

Non Dimmable / Casambi Version




Dali Version




Single Profile Ceilling Installation

Profile (mm)	Nº Susp.	L (mm)	Single Susp.
1000	2	1000	980
1500	2	1500	1480
2000	2	2000	1980
2500	3	1250	1240 + 1240
3000	3	1500	1490 + 1490




Installation Example


Profile (mm)	Nº Susp.	L (mm)	End Susp.	Middle Susp.
1000	2	2	L-10	L+25
1500	2	2	L-10	L+25
2000	2	2	L-10	L+25
2500	3	3	L-10	L+25
3000	3	3	L-10	L+25




Cable Length Supplied
(3 m)




Suspension Cable Length Supplied
(3 m)






PROFILE




Light Stripe for Recessed Profile

Top LED - L: 600 mm - 7W - 555 lm - 2700K/CRI 90 / 582 lm - 3000K/CRI 90
L: 900 mm - 10W - 1111 lm - 2700K/CRI 90 / 1166 lm - 3000K/CRI 90
L: 1200 mm - 13,5W - 1667 lm - 2700K/CRI 90 / 1750 lm - 3000K/CRI 90







LED diffuse lighting module for installation in the Zero Track Pro recessed system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.


Módulo de iluminación difusa LED para instalación en el sistema empotrado Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V.

L: 600 - 2700K

Non Dimmable
05.5290.14

Dali
05.5290.14.DA

1-10V
05.5290.14.1V



Luminous flux luminaire
259 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	87	3.15
2	22	6.29
3	10	9.44
4	5	12.59
5	3	15.73

L: 600 - 3000K

Non Dimmable
05.5291.14

Dali
05.5291.14.DA

1-10V
05.5291.14.1V



Luminous flux luminaire
272 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	91	3.15
2	23	6.29
3	10	9.44
4	6	12.59
5	4	15.73

L: 900 - 2700K

Non Dimmable
05.5292.14

Dali
05.5292.14.DA

1-10V
05.5292.14.1V



Luminous flux luminaire
518 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	174	3.15
2	43	6.29
3	19	9.44
4	11	12.59
5	7	15.73

L: 900 - 3000K

Non Dimmable
05.5293.14

Dali
05.5293.14.DA

1-10V
05.5293.14.1V



Luminous flux luminaire
544 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	182	3.15
2	46	6.29
3	20	9.44
4	11	12.59
5	7	15.73

L: 1200 - 2700K

Non Dimmable
05.5294.14

Dali
05.5294.14.DA

1-10V
05.5294.14.1V



Luminous flux luminaire
777 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	261	3.15
2	65	6.29
3	29	9.44
4	16	12.59
5	10	15.73

L: 1200 - 3000K

Non Dimmable
05.5295.14

Dali
05.5295.14.DA

1-10V
05.5295.14.1V



Luminous flux luminaire
816 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	274	3.15
2	68	6.29
3	30	9.44
4	17	12.59
5	11	15.73


NEW

Light Stripe for Surface Profile

Top LED - L: 600 mm - 7W - 555 lm - 2700K/CRI 90 / 582 lm - 3000K/CRI 90
L: 900 mm - 10W - 1111 lm - 2700K/CRI 90 / 1166 lm - 3000K/CRI 90
L: 1200 mm - 13,5W - 1667 lm - 2700K/CRI 90 / 1750 lm - 3000K/CRI 90







LED diffuse lighting module for installation in the Zero Track Pro Surface system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1–10V.


Módulo de iluminación LED difusa para instalación en el sistema Zero Track Pro Surface. Convertidor electrónico DC/DC incorporado. Control individual mediante protocolo DALI y modo broadcast mediante 1–10V.

L: 600 - 2700K

Non Dimmable
05.5190.14

Dali
05.5190.14.DA

1-10V
05.5190.14.1V



Luminous flux luminaire
259 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	87	3.15
2	22	6.29
3	10	9.44
4	5	12.59
5	3	15.73

L: 600 - 3000K

Non Dimmable
05.5191.14

Dali
05.5191.14.DA

1-10V
05.5191.14.1V



Luminous flux luminaire
272 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	91	3.15
2	23	6.29
3	10	9.44
4	6	12.59
5	4	15.73

L: 900 - 2700K

Non Dimmable
05.5192.14

Dali
05.5192.14.DA

1-10V
05.5192.14.1V



Luminous flux luminaire
518 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	174	3.15
2	43	6.29
3	19	9.44
4	11	12.59
5	7	15.73

L: 900 - 3000K

Non Dimmable
05.5193.14

Dali
05.5193.14.DA

1-10V
05.5193.14.1V



Luminous flux luminaire
544 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	182	3.15
2	46	6.29
3	20	9.44
4	11	12.59
5	7	15.73

L: 1200 - 2700K

Non Dimmable
05.5194.14

Dali
05.5194.14.DA

1-10V
05.5194.14.1V



Luminous flux luminaire
777 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	261	3.15
2	65	6.29
3	29	9.44
4	16	12.59
5	10	15.73

L: 1200 - 3000K

Non Dimmable
05.5195.14

Dali
05.5195.14.DA

1-10V
05.5195.14.1V




Luminous flux luminaire
816 lm


Beam Angle: 115°		
h(m)	E(lx)	D(m)
1	274	3.15
2	68	6.29
3	30	9.44
4	17	12.59
5	11	15.73

Light Stripe for Suspension Profile

Coming soon







LED diffuse lighting module for installation in the Zero Track Pro suspended system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Módulo de iluminación LED difusa para instalación en el sistema suspendido Zero Track Pro. Incorpora convertidor electrónico DC/DC. Control individual mediante protocolo DALI y modo broadcast mediante 1-10V.


L: 600 - 2700K

Non Dimmable

05.5390.14

Dali

05.5390.14.DA



Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

PENDING


L: 600 - 3000K

Non Dimmable

05.5391.14

Dali

05.5391.14.DA



Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

PENDING


L: 900 - 2700K

Non Dimmable

05.5392.14

Dali

05.5392.14.DA



Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

PENDING


L: 900 - 3000K

Non Dimmable

05.5393.14

Dali

05.5393.14.DA



Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

PENDING


L: 1200 - 2700K

Non Dimmable

05.5394.14

Dali

05.5394.14.DA



Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

PENDING


L: 1200 - 3000K

Non Dimmable

05.5395.14

Dali

05.5395.14.DA




Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX


PENDING

Multi Spot Mini for Surface Profile

Power LED 6,1W - 636 lm - 2700K/CRI 90 / 672 lm - 3000K/CRI 90







LED lighting module with 12 spotlights and low glare, to be installed in Zero Track Pro Surface.

Módulo de iluminación LED con 12 focos y bajo deslumbramiento, para instalar en el sistema Zero Track Pro Surface.


Optic Spot - 2700K

Non Dimmable
- 05.3560.40A
- 05.3560.14A
- 05.3560.ERA
- 05.3560.ESA

Dali 2
- 05.3560.40.DA
- 05.3560.14.DA
- 05.3560.ER.DA
- 05.3560.ES.DA

1-10V
- 05.3560.40.1V
- 05.3560.14.1V
- 05.3560.ER.1V
- 05.3560.ES.1V

15° SPOT



Luminous flux luminaire 408 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	3961	0.26
2	990	0.53
3	440	0.79
4	248	1.05
5	158	1.32


Optic Spot - 3000K

Non Dimmable
- 05.3561.40A
- 05.3561.14A
- 05.3561.ERA
- 05.3561.ESA

Dali 2
- 05.3561.40.DA
- 05.3561.14.DA
- 05.3561.ER.DA
- 05.3561.ES.DA

1-10V
- 05.3561.40.1V
- 05.3561.14.1V
- 05.3561.ER.1V
- 05.3561.ES.1V

15° SPOT



Luminous flux luminaire 415 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	4032	0.26
2	1008	0.53
3	448	0.79
4	252	1.05
5	161	1.32


Optic Medium - 2700K

Non Dimmable
- 05.3562.40A
- 05.3562.14A
- 05.3562.ERA
- 05.3562.ESA

Dali 2
- 05.3562.40.DA
- 05.3562.14.DA
- 05.3562.ER.DA
- 05.3562.ES.DA

1-10V
- 05.3562.40.1V
- 05.3562.14.1V
- 05.3562.ER.1V
- 05.3562.ES.1V

19° MEDIUM



Luminous flux luminaire 433 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2895	0.33
2	724	0.66
3	322	0.99
4	181	1.32
5	116	1.65


Optic Medium - 3000K

Non Dimmable
- 05.3563.40A
- 05.3563.14A
- 05.3563.ERA
- 05.3563.ESA

Dali 2
- 05.3563.40.DA
- 05.3563.14.DA
- 05.3563.ER.DA
- 05.3563.ES.DA

1-10V
- 05.3563.40.1V
- 05.3563.14.1V
- 05.3563.ER.1V
- 05.3563.ES.1V

19° MEDIUM



Luminous flux luminaire 440 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2947	0.33
2	737	0.66
3	327	0.99
4	184	1.32
5	118	1.65


Optic Flood - 2700K

Non Dimmable
- 05.3564.40A
- 05.3564.14A
- 05.3564.ERA
- 05.3564.ESA

Dali 2
- 05.3564.40.DA
- 05.3564.14.DA
- 05.3564.ER.DA
- 05.3564.ES.DA

1-10V
- 05.3564.40.1V
- 05.3564.14.1V
- 05.3564.ER.1V
- 05.3564.ES.1V

31° FLOOD



Luminous flux luminaire 401 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	1118	0.55
2	279	1.09
3	124	1.64
4	70	2.18
5	45	2.73


Optic Flood - 3000K

Non Dimmable
- 05.3565.40A
- 05.3565.14A
- 05.3565.ERA
- 05.3565.ESA

Dali 2
- 05.3565.40.DA
- 05.3565.14.DA
- 05.3565.ER.DA
- 05.3565.ES.DA

1-10V
- 05.3565.40.1V
- 05.3565.14.1V
- 05.3565.ER.1V
- 05.3565.ES.1V

31° FLOOD



Luminous flux luminaire 408 lm

Beam Angle: 31°


h(m)	E(lx)	D(m)
1	1138	0.55
2	284	1.09
3	126	1.64
4	71	2.18
5	46	2.73


NEW

Multi Spot Mini for Surface or Suspension Profile

Coming soon







Ultrathin LED module with 12 spots, low glare, and compatible with Zero Track Pro Surface and Suspension. It includes a side adapter, so only two consecutive modules can be installed. After them, a minimum gap of 15 cm must be maintained.

Módulo LED ultrafino de 12 focos, con bajo deslumbramiento y compatible con Zero Track Pro Surface y Suspension. Incluye adaptador lateral, por lo que solo pueden instalarse dos módulos seguidos. Después, debe dejarse una separación mínima de 15 cm.

Optic Spot - 2700K

Non Dimmable

- 05.3570.40
- 05.3570.14
- 05.3570.ER
- 05.3570.ES


Dali 2

- 05.3570.40.DA
- 05.3570.14.DA
- 05.3570.ER.DA
- 05.3570.ES.DA

1-10V

- 05.3570.40.1V
- 05.3570.14.1V
- 05.3570.ER.1V
- 05.3570.ES.1V

SPOT



PENDING

Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

Optic Spot - 3000K

Non Dimmable

- 05.3571.40
- 05.3571.14
- 05.3571.ER
- 05.3571.ES


Dali 2

- 05.3571.40.DA
- 05.3571.14.DA
- 05.3571.ER.DA
- 05.3571.ES.DA

1-10V

- 05.3571.40.1V
- 05.3571.14.1V
- 05.3571.ER.1V
- 05.3571.ES.1V

SPOT



PENDING

Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

Optic Medium - 2700K

Non Dimmable

- 05.3572.40
- 05.3572.14
- 05.3572.ER
- 05.3572.ES


Dali 2

- 05.3572.40.DA
- 05.3572.14.DA
- 05.3572.ER.DA
- 05.3572.ES.DA

1-10V

- 05.3572.40.1V
- 05.3572.14.1V
- 05.3572.ER.1V
- 05.3572.ES.1V

MEDIUM



PENDING

Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

Optic Medium - 3000K

Non Dimmable

- 05.3573.40
- 05.3573.14
- 05.3573.ER
- 05.3573.ES


Dali 2

- 05.3573.40.DA
- 05.3573.14.DA
- 05.3573.ER.DA
- 05.3573.ES.DA

1-10V

- 05.3573.40.1V
- 05.3573.14.1V
- 05.3573.ER.1V
- 05.3573.ES.1V

MEDIUM



PENDING

Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

Optic Flood - 2700K

Non Dimmable

- 05.3574.40
- 05.3574.14
- 05.3574.ER
- 05.3574.ES


Dali 2

- 05.3574.40.DA
- 05.3574.14.DA
- 05.3574.ER.DA
- 05.3574.ES.DA

1-10V

- 05.3574.40.1V
- 05.3574.14.1V
- 05.3574.ER.1V
- 05.3574.ES.1V

FLOOD



PENDING

Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX

Optic Flood - 3000K

Non Dimmable

- 05.3575.40
- 05.3575.14
- 05.3575.ER
- 05.3575.ES


Dali 2

- 05.3575.40.DA
- 05.3575.14.DA
- 05.3575.ER.DA
- 05.3575.ES.DA

1-10V

- 05.3575.40.1V
- 05.3575.14.1V
- 05.3575.ER.1V
- 05.3575.ES.1V

FLOOD



PENDING

Beam Angle:	XX°
h(m)	E(lx) D(m)
1	XXX XX
2	XXX XX
3	XXX XX
4	XXX XX
5	XXX XX


Luminaires with 1–10V dimming are not compatible with suspension profiles.


Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

Find Me 0 Designed By Jorge Herrera

Power LED 3,5W - 276 lm - 2700K/CRI 90 / 302 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Accessories included (honeycomb grid and protection bar).

Módulo de iluminación LED de proyeción para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play). Accesorios incluidos (honeycomb y cruceta de apantallamiento).


Optic Spot - 2700K

Non Dimmable

- 05.5100.40
- 05.5100.14
- 05.5100.ER
- 05.5100.ES

Casambi

- 05.5100.40.CB
- 05.5100.14.CB
- 05.5100.ER.CB
- 05.5100.ES.CB



Luminous flux luminaire
169 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	1925	0.26
2	481	0.52
3	214	0.77
4	120	1.03
5	77	1.29


Optic Spot - 3000K

Non Dimmable

- 05.5105.40
- 05.5105.14
- 05.5105.ER
- 05.5105.ES

Casambi

- 05.5105.40.CB
- 05.5105.14.CB
- 05.5105.ER.CB
- 05.5105.ES.CB



Luminous flux luminaire
183 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	2085	0.26
2	521	0.52
3	232	0.77
4	130	1.03
5	83	1.29


Optic Medium - 2700K

Non Dimmable

- 05.5101.40
- 05.5101.14
- 05.5101.ER
- 05.5101.ES

Casambi

- 05.5101.40.CB
- 05.5101.14.CB
- 05.5101.ER.CB
- 05.5101.ES.CB



Luminous flux luminaire
179 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	928	0.45
2	232	0.89
3	103	1.34
4	58	1.79
5	37	2.23


Optic Medium - 3000K

Non Dimmable

- 05.5106.40
- 05.5106.14
- 05.5106.ER
- 05.5106.ES

Casambi

- 05.5106.40.CB
- 05.5106.14.CB
- 05.5106.ER.CB
- 05.5106.ES.CB



Luminous flux luminaire
194 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1006	0.45
2	251	0.89
3	112	1.34
4	63	1.79
5	40	2.23


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Find Me 0 Designed By Jorge Herrera

Power LED 3,5W - 276 lm - 2700K/CRI 90 / 302 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V. Accessories included (honeycomb grid and protection bar).

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V. Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Optic Spot - 2700K


Dali

- 05.5100.40.DA
- 05.5100.14.DA
- 05.5100.ER.DA
- 05.5100.ES.DA

1-10V

- 05.5100.40.1V
- 05.5100.14.1V
- 05.5100.ER.1V
- 05.5100.ES.1V





Luminous flux luminaire
169 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	1925	0.26
2	481	0.52
3	214	0.77
4	120	1.03
5	77	1.29

Optic Spot - 3000K


Dali

- 05.5105.40.DA
- 05.5105.14.DA
- 05.5105.ER.DA
- 05.5105.ES.DA

1-10V

- 05.5105.40.1V
- 05.5105.14.1V
- 05.5105.ER.1V
- 05.5105.ES.1V





Luminous flux luminaire
183 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	2085	0.26
2	521	0.52
3	232	0.77
4	130	1.03
5	83	1.29

Optic Medium - 2700K


Dali

- 05.5101.40.DA
- 05.5101.14.DA
- 05.5101.ER.DA
- 05.5101.ES.DA

1-10V

- 05.5101.40.1V
- 05.5101.14.1V
- 05.5101.ER.1V
- 05.5101.ES.1V





Luminous flux luminaire
179 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	928	0.45
2	232	0.89
3	103	1.34
4	58	1.79
5	37	2.23

Optic Medium - 3000K


Dali

- 05.5106.40.DA
- 05.5106.14.DA
- 05.5106.ER.DA
- 05.5106.ES.DA

1-10V

- 05.5106.40.1V
- 05.5106.14.1V
- 05.5106.ER.1V
- 05.5106.ES.1V





Luminous flux luminaire
194 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1006	0.45
2	251	0.89
3	112	1.34
4	63	1.79
5	40	2.23

Luminaires with 1–10V dimming are not compatible with suspension profiles.

Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.


NEW


ZERO TRACK PRO — LIGHT MODULES

Find Me 1 Designed By Jorge Herrera

Power LED 5,5W - 432 lm - 2700K/CRI 90 / 446 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Accessories included (honeycomb grid and protection bar).

Módulo de iluminación LED de proyeción para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play). Accesorios incluidos (honeycomb y cruceta de apantallamiento).


Optic Spot - 2700K

Non Dimmable

- 05.5110.40
- 05.5110.14
- 05.5110.ER
- 05.5110.ES

Casambi

- 05.5110.40.CB
- 05.5110.14.CB
- 05.5110.ER.CB
- 05.5110.ES.CB



Luminous flux luminaire
309 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4167	0.24
2	1042	0.48
3	463	0.72
4	260	0.95
5	167	1.19


Optic Spot - 3000K

Non Dimmable

- 05.5115.40
- 05.5115.14
- 05.5115.ER
- 05.5115.ES

Casambi

- 05.5115.40.CB
- 05.5115.14.CB
- 05.5115.ER.CB
- 05.5115.ES.CB



Luminous flux luminaire
314 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4196	0.24
2	1049	0.49
3	466	0.73
4	262	0.97
5	168	1.21


Optic Medium - 2700K

Non Dimmable

- 05.5111.40
- 05.5111.14
- 05.5111.ER
- 05.5111.ES

Casambi

- 05.5111.40.CB
- 05.5111.14.CB
- 05.5111.ER.CB
- 05.5111.ES.CB



Luminous flux luminaire
284 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1893	0.35
2	473	0.70
3	210	1.06
4	118	1.41
5	76	1.76


Optic Medium - 3000K

Non Dimmable

- 05.5116.40
- 05.5116.14
- 05.5116.ER
- 05.5116.ES

Casambi

- 05.5116.40.CB
- 05.5116.14.CB
- 05.5116.ER.CB
- 05.5116.ES.CB



Luminous flux luminaire
289 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1927	0.35
2	482	0.70
3	214	1.06
4	120	1.41
5	77	1.76


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Find Me 1 Designed By Jorge Herrera

Power LED 5,5W - 450 lm - 2700K/CRI 90 / 485 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V. Accessories included (honeycomb grid and protection bar).

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V. Accesorios incluidos (honeycomb y cruceta de apantallamiento).


Optic Spot - 2700K

Dali

- 05.5110.40.DA
- 05.5110.14.DA
- 05.5110.ER.DA
- 05.5110.ES.DA

1-10V

- 05.5110.40.1V
- 05.5110.14.1V
- 05.5110.ER.1V
- 05.5110.ES.1V



Luminous flux luminaire
309 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4167	0.24
2	1042	0.48
3	463	0.72
4	260	0.95
5	167	1.19


Optic Spot - 3000K

Dali

- 05.5115.40.DA
- 05.5115.14.DA
- 05.5115.ER.DA
- 05.5115.ES.DA

1-10V

- 05.5115.40.1V
- 05.5115.14.1V
- 05.5115.ER.1V
- 05.5115.ES.1V



Luminous flux luminaire
314 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4196	0.24
2	1049	0.49
3	466	0.73
4	262	0.97
5	168	1.21


Optic Medium - 2700K

Dali

- 05.5111.40.DA
- 05.5111.14.DA
- 05.5111.ER.DA
- 05.5111.ES.DA

1-10V

- 05.5111.40.1V
- 05.5111.14.1V
- 05.5111.ER.1V
- 05.5111.ES.1V



Luminous flux luminaire
284 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1893	0.35
2	473	0.70
3	210	1.06
4	118	1.41
5	76	1.76


Optic Medium - 3000K

Dali

- 05.5116.40.DA
- 05.5116.14.DA
- 05.5116.ER.DA
- 05.5116.ES.DA

1-10V

- 05.5116.40.1V
- 05.5116.14.1V
- 05.5116.ER.1V
- 05.5116.ES.1V



Luminous flux luminaire
289 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1927	0.35
2	482	0.70
3	214	1.06
4	120	1.41
5	77	1.76


Luminaires with 1–10V dimming are not compatible with suspension profiles.


Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

Find Me 2 Designed By Jorge Herrera

Power LED 10,5W - 724 lm - 2700K/CRI90 / 781 lm - 3000K/CRI90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Accessories included (honeycomb grid and protection bar). Warning: Only ceiling installation.

Módulo de iluminación LED de proyeción para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play). Accesorios incluidos (honeycomb y cruceta de apantallamiento). Advertencia: Solo instalación en techo.

Optic Spot - 2700K


Non Dimmable

- 05.5120.40
- 05.5120.14
- 05.5120.ER
- 05.5120.ES

Casambi

- 05.5120.40.CB
- 05.5120.14.CB
- 05.5120.ER.CB
- 05.5120.ES.CB

10° SPOT



Luminous flux luminaire 479 lm

Beam Angle:	10°
h(m)	E(lx) D(m)
1	9243 0.18
2	2311 0.35
3	1027 0.53
4	578 0.70
5	370 0.88

Optic Spot - 3000K


Non Dimmable

- 05.5125.40
- 05.5125.14
- 05.5125.ER
- 05.5125.ES

Casambi

- 05.5125.40.CB
- 05.5125.14.CB
- 05.5125.ER.CB
- 05.5125.ES.CB

10° SPOT



Luminous flux luminaire 531 lm

Beam Angle:	10°
h(m)	E(lx) D(m)
1	10246 0.18
2	2562 0.35
3	1138 0.53
4	640 0.70
5	410 0.88

Optic Medium - 2700K


Non Dimmable

- 05.5121.40
- 05.5121.14
- 05.5121.ER
- 05.5121.ES

Casambi

- 05.5121.40.CB
- 05.5121.14.CB
- 05.5121.ER.CB
- 05.5121.ES.CB

19° MEDIUM



Luminous flux luminaire 441 lm

Beam Angle:	19°
h(m)	E(lx) D(m)
1	1989 0.34
2	497 0.67
3	221 1.01
4	124 1.34
5	80 1.68

Optic Medium - 3000K


Non Dimmable

- 05.5126.40
- 05.5126.14
- 05.5126.ER
- 05.5126.ES

Casambi

- 05.5126.40.CB
- 05.5126.14.CB
- 05.5126.ER.CB
- 05.5126.ES.CB

19° MEDIUM



Luminous flux luminaire 489 lm

Beam Angle:	19°
h(m)	E(lx) D(m)
1	2206 0.34
2	551 0.67
3	245 1.01
4	138 1.34
5	88 1.68

Optic Flood - 2700K


Non Dimmable

- 05.5122.40
- 05.5122.14
- 05.5122.ER
- 05.5122.ES

Casambi

- 05.5122.40.CB
- 05.5122.14.CB
- 05.5122.ER.CB
- 05.5122.ES.CB

32° FLOOD



Luminous flux luminaire 364 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	722 0.57
2	180 1.15
3	80 1.72
4	45 2.29
5	29 2.87

Optic Flood - 3000K


Non Dimmable

- 05.5127.40
- 05.5127.14
- 05.5127.ER
- 05.5127.ES

Casambi

- 05.5127.40.CB
- 05.5127.14.CB
- 05.5127.ER.CB
- 05.5127.ES.CB

32° FLOOD



Luminous flux luminaire 404 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	801 0.57
2	200 1.15
3	89 1.72
4	50 2.29
5	32 2.87


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Find Me 2 Designed By Jorge Herrera

Power LED 10,5W - 724 lm - 2700K/CRI90 / 781 lm - 3000K/CRI90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V. Accessories included (honeycomb grid and protection bar).
Warning: Only ceiling installation.

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V. Accesorios incluidos (honeycomb y cruceta de apantallamiento).
Advertencia: Solo instalación en techo.

Optic Spot - 2700K


Dali

- 05.5120.40.DA
- 05.5120.14.DA
- 05.5120.ER.DA
- 05.5120.ES.DA

1-10V

- 05.5120.40.1V
- 05.5120.14.1V
- 05.5120.ER.1V
- 05.5120.ES.1V

10° SPOT



Luminous flux luminaire
479 lm

Beam Angle:	10°
h(m)	E(lx) D(m)
1	9243 0.18
2	2311 0.35
3	1027 0.53
4	578 0.70
5	370 0.88

Optic Spot - 3000K


Dali

- 05.5125.40.DA
- 05.5125.14.DA
- 05.5125.ER.DA
- 05.5125.ES.DA

1-10V

- 05.5125.40.1V
- 05.5125.14.1V
- 05.5125.ER.1V
- 05.5125.ES.1V

10° SPOT



Luminous flux luminaire
531 lm

Beam Angle:	10°
h(m)	E(lx) D(m)
1	10246 0.18
2	2562 0.35
3	1138 0.53
4	640 0.70
5	410 0.88

Optic Medium - 2700K


Dali

- 05.5121.40.DA
- 05.5121.14.DA
- 05.5121.ER.DA
- 05.5121.ES.DA

1-10V

- 05.5121.40.1V
- 05.5121.14.1V
- 05.5121.ER.1V
- 05.5121.ES.1V

19° MEDIUM



Luminous flux luminaire
441 lm

Beam Angle:	19°
h(m)	E(lx) D(m)
1	1989 0.34
2	497 0.67
3	221 1.01
4	124 1.34
5	80 1.68

Optic Medium - 3000K


Dali

- 05.5126.40.DA
- 05.5126.14.DA
- 05.5126.ER.DA
- 05.5126.ES.DA

1-10V

- 05.5126.40.1V
- 05.5126.14.1V
- 05.5126.ER.1V
- 05.5126.ES.1V

19° MEDIUM



Luminous flux luminaire
489 lm

Beam Angle:	19°
h(m)	E(lx) D(m)
1	2206 0.34
2	551 0.67
3	245 1.01
4	138 1.34
5	88 1.68

Optic Flood - 2700K


Dali

- 05.5122.40.DA
- 05.5122.14.DA
- 05.5122.ER.DA
- 05.5122.ES.DA

1-10V

- 05.5122.40.1V
- 05.5122.14.1V
- 05.5122.ER.1V
- 05.5122.ES.1V

32° FLOOD



Luminous flux luminaire
364 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	722 0.57
2	180 1.15
3	80 1.72
4	45 2.29
5	29 2.87

Optic Flood - 3000K


Dali

- 05.5127.40.DA
- 05.5127.14.DA
- 05.5127.ER.DA
- 05.5127.ES.DA

1-10V

- 05.5127.40.1V
- 05.5127.14.1V
- 05.5127.ER.1V
- 05.5127.ES.1V

32° FLOOD



Luminous flux luminaire
404 lm


Beam Angle:	32°
h(m)	E(lx) D(m)
1	801 0.57
2	200 1.15
3	89 1.72
4	50 2.29
5	32 2.87


Luminaires with 1–10V dimming are not compatible with suspension profiles.
Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

Find Me 1 Suspension Designed By Jorge Herrera

Power LED 5,5W - 432 lm - 2700K/CRI 90 / 446 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Cannot be installed on vertical tracks. Accessories included (honeycomb grid and protection bar).

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play). No se puede instalar en carriles verticales. Accesorios incluidos (honeycomb y cruceta de apantallamiento).


Optic Spot - 2700K

Non Dimmable

- 05.5130.40
- 05.5130.14
- 05.5130.ER
- 05.5130.ES

Casambi

- 05.5130.40.CB
- 05.5130.14.CB
- 05.5130.ER.CB
- 05.5130.ES.CB



Luminous flux luminaire
309 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	4167	0.24
2	1042	0.48
3	463	0.72
4	260	0.95
5	167	1.19


Optic Spot - 3000K

Non Dimmable

- 05.5135.40
- 05.5135.14
- 05.5135.ER
- 05.5135.ES

Casambi

- 05.5135.40.CB
- 05.5135.14.CB
- 05.5135.ER.CB
- 05.5135.ES.CB



Luminous flux luminaire
314 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	4196	0.24
2	1049	0.49
3	466	0.73
4	262	0.97
5	168	1.21


Optic Medium - 2700K

Non Dimmable

- 05.5131.40
- 05.5131.14
- 05.5131.ER
- 05.5131.ES

Casambi

- 05.5131.40.CB
- 05.5131.14.CB
- 05.5131.ER.CB
- 05.5131.ES.CB



Luminous flux luminaire
186 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	1240	0.35
2	310	0.70
3	138	1.06
4	77	1.41
5	50	1.76


Optic Medium - 3000K

Non Dimmable

- 05.5136.40
- 05.5136.14
- 05.5136.ER
- 05.5136.ES

Casambi

- 05.5136.40.CB
- 05.5136.14.CB
- 05.5136.ER.CB
- 05.5136.ES.CB



Luminous flux luminaire
193 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	1287	0.35
2	322	0.70
3	143	1.06
4	80	1.41
5	51	1.76


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Find Me 1 Suspension Designed By Jorge Herrera

Power LED 5,5W - 432 lm - 2700K/CRI 90 / 446 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V. Cannot be installed on vertical tracks. Accessories included (honeycomb grid and protection bar).

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V. No se puede instalar en carriles verticales. Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Optic Spot - 2700K


Dali

- 05.5130.40.DA
- 05.5130.14.DA
- 05.5130.ER.DA
- 05.5130.ES.DA

1-10V

- 05.5130.40.1V
- 05.5130.14.1V
- 05.5130.ER.1V
- 05.5130.ES.1V





Luminous flux luminaire
309 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	4167	0.24
2	1042	0.48
3	463	0.72
4	260	0.95
5	167	1.19

Optic Spot - 3000K


Dali

- 05.5135.40.DA
- 05.5135.14.DA
- 05.5135.ER.DA
- 05.5135.ES.DA

1-10V

- 05.5135.40.1V
- 05.5135.14.1V
- 05.5135.ER.1V
- 05.5135.ES.1V





Luminous flux luminaire
314 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	4196	0.24
2	1049	0.49
3	466	0.73
4	262	0.97
5	168	1.21

Optic Medium - 2700K


Dali

- 05.5131.40.DA
- 05.5131.14.DA
- 05.5131.ER.DA
- 05.5131.ES.DA

1-10V

- 05.5131.40.1V
- 05.5131.14.1V
- 05.5131.ER.1V
- 05.5131.ES.1V





Luminous flux luminaire
186 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	1240	0.35
2	310	0.70
3	138	1.06
4	77	1.41
5	50	1.76

Optic Medium - 3000K


Dali

- 05.5136.40.DA
- 05.5136.14.DA
- 05.5136.ER.DA
- 05.5136.ES.DA

1-10V

- 05.5136.40.1V
- 05.5136.14.1V
- 05.5136.ER.1V
- 05.5136.ES.1V





Luminous flux luminaire
193 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	1287	0.35
2	322	0.70
3	143	1.06
4	80	1.41
5	51	1.76


Luminaires with 1–10V dimming are not compatible with suspension profiles.


Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

Light Shadow Spot 30

Power LED 4,9W - 297 lm - 2700K/CRI 90 / 326 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V.

Optic Spot - 2700K

Non Dimmable

- 05.5170.40A
- 05.5170.14A
- 05.5170.ERA
- 05.5170.ESA


Dali

- 05.5170.40ADA
- 05.5170.14ADA
- 05.5170.ERADA
- 05.5170.ESADA

1-10V

- 05.5170.40A1V
- 05.5170.14A1V
- 05.5170.ERA1V
- 05.5170.ESA1V





Luminous flux luminaire
253 lm

Beam Angle:	11°
h(m)	E(lx)	D(m)
1	4044	0.20
2	1011	0.40
3	449	0.60
4	253	0.80
5	162	1.00

Optic Flood - 2700K

Non Dimmable

- 05.5172.40A
- 05.5172.14A
- 05.5172.ERA
- 05.5172.ESA


Dali

- 05.5172.40ADA
- 05.5172.14ADA
- 05.5172.ERADA
- 05.5172.ESADA

1-10V

- 05.5172.40A1V
- 05.5172.14A1V
- 05.5172.ERA1V
- 05.5172.ESA1V





Luminous flux luminaire
246 lm

Beam Angle:	29°
h(m)	E(lx)	D(m)
1	953	0.52
2	238	1.04
3	106	1.57
4	60	2.09
5	38	2.61

Optic Medium - 2700K

Non Dimmable

- 05.5171.40A
- 05.5171.14A
- 05.5171.ERA
- 05.5171.ESA


Dali

- 05.5171.40ADA
- 05.5171.14ADA
- 05.5171.ERADA
- 05.5171.ESADA

1-10V

- 05.5171.40A1V
- 05.5171.14A1V
- 05.5171.ERA1V
- 05.5171.ESA1V





Luminous flux luminaire
257 lm

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	1797	0.39
2	449	0.78
3	200	1.17
4	112	1.56
5	72	1.95

Optic Wide Flood - 2700K

Non Dimmable

- 05.5173.40A
- 05.5173.14A
- 05.5173.ERA
- 05.5173.ESA


Dali

- 05.5173.40ADA
- 05.5173.14ADA
- 05.5173.ERADA
- 05.5173.ESADA

1-10V

- 05.5173.40A1V
- 05.5173.14A1V
- 05.5173.ERA1V
- 05.5173.ESA1V





Luminous flux luminaire
246 lm

Beam Angle:	43°
h(m)	E(lx)	D(m)
1	524	0.80
2	131	1.59
3	58	2.39
4	33	3.19
5	21	3.99

Luminaires with 1–10V dimming are not compatible with suspension profiles.

Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

NEW

Optic Spot - 3000K

Non Dimmable

- 05.5175.40A
- 05.5175.14A
- 05.5175.ERA
- 05.5175.ESA


Dali

- 05.5175.40ADA
- 05.5175.14ADA
- 05.5175.ERADA
- 05.5175.ESADA

1-10V

- 05.5175.40A1V
- 05.5175.14A1V
- 05.5175.ERA1V
- 05.5175.ESA1V





Luminous flux luminaire
270 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4316	0.20
2	1079	0.40
3	480	0.60
4	270	0.80
5	173	1.00

Optic Flood - 3000K

Non Dimmable

- 05.5177.40A
- 05.5177.14A
- 05.5177.ERA
- 05.5177.ESA


Dali

- 05.5177.40ADA
- 05.5177.14ADA
- 05.5177.ERADA
- 05.5177.ESADA

1-10V

- 05.5177.40A1V
- 05.5177.14A1V
- 05.5177.ERA1V
- 05.5177.ESA1V





Luminous flux luminaire
263 lm

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	1019	0.52
2	255	1.04
3	113	1.57
4	64	2.09
5	41	2.61

Optic Medium - 3000K

Non Dimmable

- 05.5176.40A
- 05.5176.14A
- 05.5176.ERA
- 05.5176.ESA


Dali

- 05.5176.40ADA
- 05.5176.14ADA
- 05.5176.ERADA
- 05.5176.ESADA

1-10V

- 05.5176.40A1V
- 05.5176.14A1V
- 05.5176.ERA1V
- 05.5176.ESA1V





Luminous flux luminaire
274 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1916	0.39
2	479	0.78
3	213	1.17
4	120	1.56
5	77	1.95

Optic Wide Flood - 3000K

Non Dimmable

- 05.5178.40A
- 05.5178.14A
- 05.5178.ERA
- 05.5178.ESA


Dali

- 05.5178.40ADA
- 05.5178.14ADA
- 05.5178.ERADA
- 05.5178.ESADA

1-10V

- 05.5178.40A1V
- 05.5178.14A1V
- 05.5178.ERA1V
- 05.5178.ESA1V





Luminous flux luminaire
262 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	559	0.80
2	140	1.59
3	62	2.39
4	35	3.19
5	22	3.99

Accessories / Accesorios


Light Shadow Spot 30


Honeycomb	Panel de abeja		08.0790.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0791.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0792.00

Light Shadow Spot 45

LED Array 11W - 799 lm - 2700K/CRI 90 / 844 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V.

Optic Spot - 2700K

Non Dimmable

- 05.5180.40
- 05.5180.14
- 05.5180.ER
- 05.5180.ES


Dali

- 05.5180.40.DA
- 05.5180.14.DA
- 05.5180.ER.DA
- 05.5180.ES.DA

1-10V

- 05.5180.40.1V
- 05.5180.14.1V
- 05.5180.ER.1V
- 05.5180.ES.1V





Luminous flux luminaire
650 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8012	0.27
2	2003	0.54
3	890	0.80
4	501	1.07
5	320	1.34

Optic Flood - 2700K

Non Dimmable

- 05.5182.40
- 05.5182.14
- 05.5182.ER
- 05.5182.ES


Dali

- 05.5182.40.DA
- 05.5182.14.DA
- 05.5182.ER.DA
- 05.5182.ES.DA

1-10V

- 05.5182.40.1V
- 05.5182.14.1V
- 05.5182.ER.1V
- 05.5182.ES.1V





Luminous flux luminaire
646 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2296	0.56
2	574	1.11
3	255	1.67
4	144	2.22
5	92	2.78

Optic Medium - 2700K

Non Dimmable

- 05.5181.40
- 05.5181.14
- 05.5181.ER
- 05.5181.ES


Dali

- 05.5181.40.DA
- 05.5181.14.DA
- 05.5181.ER.DA
- 05.5181.ES.DA

1-10V

- 05.5181.40.1V
- 05.5181.14.1V
- 05.5181.ER.1V
- 05.5181.ES.1V





Luminous flux luminaire
645 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5163	0.36
2	1291	0.73
3	574	1.09
4	323	1.46
5	207	1.82

Luminaires with 1–10V dimming are not compatible with suspension profiles.

Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

NEW

Optic Spot - 3000K

Non Dimmable

- 05.5185.40
- 05.5185.14
- 05.5185.ER
- 05.5185.ES


Dali

- 05.5185.40.DA
- 05.5185.14.DA
- 05.5185.ER.DA
- 05.5185.ES.DA

1-10V

- 05.5185.40.1V
- 05.5185.14.1V
- 05.5185.ER.1V
- 05.5185.ES.1V





Luminous flux luminaire
686 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8456	0.27
2	2114	0.54
3	940	0.80
4	528	1.07
5	338	1.34

Optic Flood - 3000K

Non Dimmable

- 05.5187.40
- 05.5187.14
- 05.5187.ER
- 05.5187.ES


Dali

- 05.5187.40.DA
- 05.5187.14.DA
- 05.5187.ER.DA
- 05.5187.ES.DA

1-10V

- 05.5187.40.1V
- 05.5187.14.1V
- 05.5187.ER.1V
- 05.5187.ES.1V





Luminous flux luminaire
682 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2424	0.56
2	606	1.11
3	269	1.67
4	152	2.22
5	97	2.78

Optic Medium - 3000K

Non Dimmable

- 05.5186.40
- 05.5186.14
- 05.5186.ER
- 05.5186.ES


Dali

- 05.5186.40.DA
- 05.5186.14.DA
- 05.5186.ER.DA
- 05.5186.ES.DA

1-10V

- 05.5186.40.1V
- 05.5186.14.1V
- 05.5186.ER.1V
- 05.5186.ES.1V





Luminous flux luminaire
682 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5459	0.36
2	1365	0.73
3	607	1.09
4	341	1.46
5	218	1.82

Accessories / Accesorios


Light Shadow Spot 45


Honeycomb	Panel de abeja		08.0793.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0794.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0795.00

My Spot Ø25 Short By Michael Anastassiades

Power LED
Non Dimming / 1-10V / Dali: 4,7W - 231 lm - 2700K/CRI 90 / 235 lm - 3000K/CRI 90
Casambi: 3,8W - 208 lm - 2700K/CRI 90 / 212 lm - 3000K/CRI 90







LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.
Warning: Only ceiling installation.

Módulo de iluminación LED para ser instalado en el sistema Zero Track Pro. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión al carril queda perfectamente enrasado con el producto.
Advertencia: Solo instalación en techo.

Optic Spot - 2700K


Non Dimmable
- 05.5300.40A
- 05.5300.14A
- 05.5300.ERA
- 05.5300.ESA

Dali
- 05.5300.40ADA
- 05.5300.14ADA
- 05.5300.ERADA
- 05.5300.ESADA

1-10V
- 05.5300.40A1V
- 05.5300.14A1V
- 05.5300.ERA1V
- 05.5300.ESA1V

Casambi
- 05.5300.40ACB
- 05.5300.14ACB
- 05.5300.ERACB
- 05.5300.ESACB





Luminous flux luminaire
222 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4457	0.19
2	1114	0.37
3	495	0.56
4	279	0.75
5	178	0.93

Optic Spot - 3000K


Non Dimmable
- 05.5305.40A
- 05.5305.14A
- 05.5305.ERA
- 05.5305.ESA

Dali
- 05.5305.40ADA
- 05.5305.14ADA
- 05.5305.ERADA
- 05.5305.ESADA

1-10V
- 05.5305.40A1V
- 05.5305.14A1V
- 05.5305.ERA1V
- 05.5305.ESA1V

Casambi
- 05.5305.40ACB
- 05.5305.14ACB
- 05.5305.ERACB
- 05.5305.ESACB





Luminous flux luminaire
244 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4898	0.19
2	1225	0.37
3	544	0.56
4	306	0.75
5	196	0.93

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

NEW

Optic Medium - 2700K

Non Dimmable

- 05.5301.40A
- 05.5301.14A
- 05.5301.ERA
- 05.5301.ESA

Dali

- 05.5301.40ADA
- 05.5301.14ADA
- 05.5301.ERADA
- 05.5301.ESADA

1-10V


- 05.5301.40A1V
- 05.5301.14A1V
- 05.5301.ERA1V
- 05.5301.ESA1V

Casambi

- 05.5301.40ACB
- 05.5301.14ACB
- 05.5301.ERACB
- 05.5301.ESACB



MEDIUM



Luminous flux luminaire
227 lm

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	1520	0.41
2	380	0.82
3	169	1.23
4	95	1.64
5	61	2.05

Optic Medium - 3000K

Non Dimmable

- 05.5306.40A
- 05.5306.14A
- 05.5306.ERA
- 05.5306.ESA

Dali

- 05.5306.40ADA
- 05.5306.14ADA
- 05.5306.ERADA
- 05.5306.ESADA

1-10V


- 05.5306.40A1V
- 05.5306.14A1V
- 05.5306.ERA1V
- 05.5306.ESA1V

Casambi

- 05.5306.40ACB
- 05.5306.14ACB
- 05.5306.ERACB
- 05.5306.ESACB



MEDIUM



Luminous flux luminaire
249 lm

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	1668	0.41
2	417	0.82
3	185	1.23
4	104	1.64
5	67	2.05

Optic Flood - 2700K

Non Dimmable

- 05.5302.40A
- 05.5302.14A
- 05.5302.ERA
- 05.5302.ESA

Dali

- 05.5302.40ADA
- 05.5302.14ADA
- 05.5302.ERADA
- 05.5302.ESADA

1-10V


- 05.5302.40A1V
- 05.5302.14A1V
- 05.5302.ERA1V
- 05.5302.ESA1V

Casambi

- 05.5302.40ACB
- 05.5302.14ACB
- 05.5302.ERACB
- 05.5302.ESACB



FLOOD



Luminous flux luminaire
205 lm

Beam Angle:		34°
h(m)	E(lx)	D(m)
1	649	0.62
2	162	1.23
3	72	1.85
4	41	2.46
5	26	3.08

Optic Flood - 3000K

Non Dimmable

- 05.5307.40A
- 05.5307.14A
- 05.5307.ERA
- 05.5307.ESA

Dali

- 05.5307.40ADA
- 05.5307.14ADA
- 05.5307.ERADA
- 05.5307.ESADA

1-10V


- 05.5307.40A1V
- 05.5307.14A1V
- 05.5307.ERA1V
- 05.5307.ESA1V

Casambi

- 05.5307.40ACB
- 05.5307.14ACB
- 05.5307.ERACB
- 05.5307.ESACB



FLOOD



Luminous flux luminaire
225 lm

Beam Angle:		34°
h(m)	E(lx)	D(m)
1	712	0.62
2	178	1.23
3	79	1.85
4	44	2.46
5	28	3.08


Luminaires with 1–10V dimming are not compatible with suspension profiles.


Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

My Spot Ø25 Long By Michael Anastassiades

Power LED
Non Dimming / 1-10V / Dali: 4,7W - 231 lm - 2700K/CRI 90 / 235 lm - 3000K/CRI 90
Casambi: 3,8W - 208 lm - 2700K/CRI 90 / 212 lm - 3000K/CRI 90







LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.
Warning: Only ceiling installation.

Módulo de iluminación LED para ser instalado en el sistema Zero Track Pro. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión al carril queda perfectamente enrasado con el producto.
Advertencia: Solo instalación en techo.


Optic Spot - 2700K

Non Dimmable
- 05.5310.40A
- 05.5310.14A
- 05.5310.ERA
- 05.5310.ESA

Dali
- 05.5310.40ADA
- 05.5310.14ADA
- 05.5310.ERADA
- 05.5310.ESADA

1-10V
- 05.5310.40A1V
- 05.5310.14A1V
- 05.5310.ERA1V
- 05.5310.ESA1V

Casambi
- 05.5310.40ACB
- 05.5310.14ACB
- 05.5310.ERACB
- 05.5310.ESACB



Luminous flux luminaire
222 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4457	0.19
2	1114	0.37
3	495	0.56
4	279	0.75
5	178	0.93


Optic Spot - 3000K

Non Dimmable
- 05.5315.40A
- 05.5315.14A
- 05.5315.ERA
- 05.5315.ESA

Dali
- 05.5315.40ADA
- 05.5315.14ADA
- 05.5315.ERADA
- 05.5315.ESADA

1-10V
- 05.5315.40A1V
- 05.5315.14A1V
- 05.5315.ERA1V
- 05.5315.ESA1V

Casambi
- 05.5315.40ACB
- 05.5315.14ACB
- 05.5315.ERACB
- 05.5315.ESACB



Luminous flux luminaire
244 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4898	0.19
2	1225	0.37
3	544	0.56
4	306	0.75
5	196	0.93

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

NEW

Optic Medium - 2700K

Non Dimmable

- 05.5311.40A
- 05.5311.14A
- 05.5311.ERA
- 05.5311.ESA

Dali


- 05.5311.40ADA
- 05.5311.14ADA
- 05.5311.ERADA
- 05.5311.ESADA

1-10V

- 05.5311.40A1V
- 05.5311.14A1V
- 05.5311.ERA1V
- 05.5311.ESA1V

Casambi

- 05.5311.40ACB
- 05.5311.14ACB
- 05.5311.ERACB
- 05.5311.ESACB



Luminous flux luminaire
227 lm

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	1520	0.41
2	380	0.82
3	169	1.23
4	95	1.64
5	61	2.05

Optic Medium - 3000K

Non Dimmable

- 05.5316.40A
- 05.5316.14A
- 05.5316.ERA
- 05.5316.ESA

Dali


- 05.5316.40ADA
- 05.5316.14ADA
- 05.5316.ERADA
- 05.5316.ESADA

1-10V

- 05.5316.40A1V
- 05.5316.14A1V
- 05.5316.ERA1V
- 05.5316.ESA1V

Casambi

- 05.5316.40ACB
- 05.5316.14ACB
- 05.5316.ERACB
- 05.5316.ESACB



Luminous flux luminaire
249 lm

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	1668	0.41
2	417	0.82
3	185	1.23
4	104	1.64
5	67	2.05

Optic Flood - 2700K

Non Dimmable

- 05.5312.40A
- 05.5312.14A
- 05.5312.ERA
- 05.5312.ESA

Dali


- 05.5312.40ADA
- 05.5312.14ADA
- 05.5312.ERADA
- 05.5312.ESADA

1-10V

- 05.5312.40A1V
- 05.5312.14A1V
- 05.5312.ERA1V
- 05.5312.ESA1V

Casambi

- 05.5312.40ACB
- 05.5312.14ACB
- 05.5312.ERACB
- 05.5312.ESACB



Luminous flux luminaire
205 lm

Beam Angle:		34°
h(m)	E(lx)	D(m)
1	649	0.62
2	162	1.23
3	72	1.85
4	41	2.46
5	26	3.08

Optic Flood - 3000K

Non Dimmable

- 05.5317.40A
- 05.5317.14A
- 05.5317.ERA
- 05.5317.ESA

Dali


- 05.5317.40ADA
- 05.5317.14ADA
- 05.5317.ERADA
- 05.5317.ESADA

1-10V

- 05.5317.40A1V
- 05.5317.14A1V
- 05.5317.ERA1V
- 05.5317.ESA1V

Casambi

- 05.5317.40ACB
- 05.5317.14ACB
- 05.5317.ERACB
- 05.5317.ESACB



Luminous flux luminaire
225 lm

Beam Angle:		34°
h(m)	E(lx)	D(m)
1	712	0.62
2	178	1.23
3	79	1.85
4	44	2.46
5	28	3.08


Luminaires with 1–10V dimming are not compatible with suspension profiles.


Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

My Spot Ø35 Short By Michael Anastassiades

LED Array
Non Dimming / 1-10V / Dali: 11W - 799 lm - 2700K/CRI 90 / 844 lm - 3000K/CRI 90
Casambi: 8W - 759 lm - 2700K/CRI 90 / 804 lm - 3000K/CRI 90







LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.
Warning: Only ceiling installation.

Módulo de iluminación LED para ser instalado en el sistema Zero Track Pro. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión al carril queda perfectamente enrasado con el producto.
Advertencia: Solo instalación en techo.

Optic Spot - 2700K


Non Dimmable
- 05.5320.40
- 05.5320.14
- 05.5320.ER
- 05.5320.ES

Dali
- 05.5320.40.DA
- 05.5320.14.DA
- 05.5320.ER.DA
- 05.5320.ES.DA

1-10V
- 05.5320.40.1V
- 05.5320.14.1V
- 05.5320.ER.1V
- 05.5320.ES.1V

Casambi
- 05.5320.40.CB
- 05.5320.14.CB
- 05.5320.ER.CB
- 05.5320.ES.CB





Luminous flux luminaire
512 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6775	0.27
2	1694	0.53
3	753	0.80
4	423	1.07
5	271	1.34

Optic Spot - 3000K


Non Dimmable
- 05.5325.40
- 05.5325.14
- 05.5325.ER
- 05.5325.ES

Dali
- 05.5325.40.DA
- 05.5325.14.DA
- 05.5325.ER.DA
- 05.5325.ES.DA

1-10V
- 05.5325.40.1V
- 05.5325.14.1V
- 05.5325.ER.1V
- 05.5325.ES.1V

Casambi
- 05.5325.40.CB
- 05.5325.14.CB
- 05.5325.ER.CB
- 05.5325.ES.CB





Luminous flux luminaire
540 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	7146	0.27
2	1786	0.53
3	794	0.80
4	447	1.07
5	286	1.34

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

NEW

Optic Medium - 2700K

Non Dimmable

- 05.5321.40
- 05.5321.14
- 05.5321.ER
- 05.5321.ES

Dali

- 05.5321.40.DA
- 05.5321.14.DA
- 05.5321.ER.DA
- 05.5321.ES.DA

1-10V


- 05.5321.40.1V
- 05.5321.14.1V
- 05.5321.ER.1V
- 05.5321.ES.1V

Casambi

- 05.5321.40.CB
- 05.5321.14.CB
- 05.5321.ER.CB
- 05.5321.ES.CB



MEDIUM



Luminous flux luminaire
567 lm

Beam Angle:	21°
h(m)	E(lx) D(m)
1	4662 0.38
2	1166 0.75
3	518 1.13
4	291 1.51
5	186 1.88

Optic Medium - 3000K

Non Dimmable

- 05.5326.40
- 05.5326.14
- 05.5326.ER
- 05.5326.ES

Dali

- 05.5326.40.DA
- 05.5326.14.DA
- 05.5326.ER.DA
- 05.5326.ES.DA

1-10V


- 05.5326.40.1V
- 05.5326.14.1V
- 05.5326.ER.1V
- 05.5326.ES.1V

Casambi

- 05.5326.40.CB
- 05.5326.14.CB
- 05.5326.ER.CB
- 05.5326.ES.CB



MEDIUM



Luminous flux luminaire
598 lm

Beam Angle:	21°
h(m)	E(lx) D(m)
1	4917 0.38
2	1229 0.75
3	546 1.13
4	307 1.51
5	197 1.88

Optic Flood - 2700K

Non Dimmable

- 05.5322.40
- 05.5322.14
- 05.5322.ER
- 05.5322.ES

Dali

- 05.5322.40.DA
- 05.5322.14.DA
- 05.5322.ER.DA
- 05.5322.ES.DA

1-10V


- 05.5322.40.1V
- 05.5322.14.1V
- 05.5322.ER.1V
- 05.5322.ES.1V

Casambi

- 05.5322.40.CB
- 05.5322.14.CB
- 05.5322.ER.CB
- 05.5322.ES.CB



FLOOD



Luminous flux luminaire
565 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	1761 0.58
2	440 1.16
3	196 1.75
4	110 2.33
5	70 2.91

Optic Flood - 3000K

Non Dimmable

- 05.5327.40
- 05.5327.14
- 05.5327.ER
- 05.5327.ES

Dali

- 05.5327.40.DA
- 05.5327.14.DA
- 05.5327.ER.DA
- 05.5327.ES.DA

1-10V


- 05.5327.40.1V
- 05.5327.14.1V
- 05.5327.ER.1V
- 05.5327.ES.1V

Casambi

- 05.5327.40.CB
- 05.5327.14.CB
- 05.5327.ER.CB
- 05.5327.ES.CB



FLOOD



Luminous flux luminaire
597 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	1861 0.58
2	465 1.16
3	207 1.75
4	116 2.33
5	74 2.91


Luminaires with 1–10V dimming are not compatible with suspension profiles.


Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

My Spot Ø35 Long By Michael Anastassiades

LED Array
Non Dimming / 1-10V / Dali: 11W - 799 lm - 2700K/CRI 90 / 844 lm - 3000K/CRI 90
Casambi: 8W - 759 lm - 2700K/CRI 90 / 804 lm - 3000K/CRI 90







LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.
Warning: Only ceiling installation.

Módulo de iluminación LED para ser instalado en el sistema Zero Track Pro. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión al carril queda perfectamente enrasado con el producto.
Advertencia: Solo instalación en techo.

Optic Spot - 2700K


Non Dimmable
- 05.5330.40
- 05.5330.14
- 05.5330.ER
- 05.5330.ES

Dali
- 05.5330.40.DA
- 05.5330.14.DA
- 05.5330.ER.DA
- 05.5330.ES.DA

1-10V
- 05.5330.40.1V
- 05.5330.14.1V
- 05.5330.ER.1V
- 05.5330.ES.1V

Casambi
- 05.5330.40.CB
- 05.5330.14.CB
- 05.5330.ER.CB
- 05.5330.ES.CB





Luminous flux luminaire
512 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6775	0.27
2	1694	0.53
3	753	0.80
4	423	1.07
5	271	1.34

Optic Spot - 3000K


Non Dimmable
- 05.5335.40
- 05.5335.14
- 05.5335.ER
- 05.5335.ES

Dali
- 05.5335.40.DA
- 05.5335.14.DA
- 05.5335.ER.DA
- 05.5335.ES.DA

1-10V
- 05.5335.40.1V
- 05.5335.14.1V
- 05.5335.ER.1V
- 05.5335.ES.1V

Casambi
- 05.5335.40.CB
- 05.5335.14.CB
- 05.5335.ER.CB
- 05.5335.ES.CB





Luminous flux luminaire
540 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	7146	0.27
2	1786	0.53
3	794	0.80
4	447	1.07
5	286	1.34

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

NEW

Optic Medium - 2700K

Non Dimmable

- 05.5331.40
- 05.5331.14
- 05.5331.ER
- 05.5331.ES

Dali

- 05.5331.40.DA
- 05.5331.14.DA
- 05.5331.ER.DA
- 05.5331.ES.DA

1-10V


- 05.5331.40.1V
- 05.5331.14.1V
- 05.5331.ER.1V
- 05.5331.ES.1V

Casambi

- 05.5331.40.CB
- 05.5331.14.CB
- 05.5331.ER.CB
- 05.5331.ES.CB



MEDIUM



Luminous flux luminaire
567 lm

Beam Angle:	21°
h(m)	E(lx) D(m)
1	4662 0.38
2	1166 0.75
3	518 1.13
4	291 1.51
5	186 1.88

Optic Medium - 3000K

Non Dimmable

- 05.5336.40
- 05.5336.14
- 05.5336.ER
- 05.5336.ES

Dali

- 05.5336.40.DA
- 05.5336.14.DA
- 05.5336.ER.DA
- 05.5336.ES.DA

1-10V


- 05.5336.40.1V
- 05.5336.14.1V
- 05.5336.ER.1V
- 05.5336.ES.1V

Casambi

- 05.5336.40.CB
- 05.5336.14.CB
- 05.5336.ER.CB
- 05.5336.ES.CB



MEDIUM



Luminous flux luminaire
598 lm

Beam Angle:	21°
h(m)	E(lx) D(m)
1	4917 0.38
2	1229 0.75
3	546 1.13
4	307 1.51
5	197 1.88

Optic Flood - 2700K

Non Dimmable

- 05.5332.40
- 05.5332.14
- 05.5332.ER
- 05.5332.ES

Dali

- 05.5332.40.DA
- 05.5332.14.DA
- 05.5332.ER.DA
- 05.5332.ES.DA

1-10V


- 05.5332.40.1V
- 05.5332.14.1V
- 05.5332.ER.1V
- 05.5332.ES.1V

Casambi

- 05.5332.40.CB
- 05.5332.14.CB
- 05.5332.ER.CB
- 05.5332.ES.CB



FLOOD



Luminous flux luminaire
565 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	1761 0.58
2	440 1.16
3	196 1.75
4	110 2.33
5	70 2.91

Optic Flood - 3000K

Non Dimmable

- 05.5337.40
- 05.5337.14
- 05.5337.ER
- 05.5337.ES

Dali

- 05.5337.40.DA
- 05.5337.14.DA
- 05.5337.ER.DA
- 05.5337.ES.DA

1-10V


- 05.5337.40.1V
- 05.5337.14.1V
- 05.5337.ER.1V
- 05.5337.ES.1V

Casambi

- 05.5337.40.CB
- 05.5337.14.CB
- 05.5337.ER.CB
- 05.5337.ES.CB



FLOOD



Luminous flux luminaire
597 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	1861 0.58
2	465 1.16
3	207 1.75
4	116 2.33
5	74 2.91

Luminaires with 1–10V dimming are not compatible with suspension profiles.

Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.


NEW


ZERO TRACK PRO — LIGHT MODULES

Atom 90 Designed By Piero Lissoni

Power LED 5,5W - 432 lm - 2700K/CRI 90 / 446 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play).

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play).


Optic Spot - 2700K

Non Dimmable

- 05.5140.40
- 05.5140.14
- 05.5140.ER
- 05.5140.ES

Casambi

- 05.5140.40.CB
- 05.5140.14.CB
- 05.5140.ER.CB
- 05.5140.ES.CB



Luminous flux luminaire
224 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	2564	0.25
2	641	0.51
3	285	0.76
4	160	1.02
5	103	1.27


Optic Spot - 3000K

Non Dimmable

- 05.5145.40
- 05.5145.14
- 05.5145.ER
- 05.5145.ES

Casambi

- 05.5145.40.CB
- 05.5145.14.CB
- 05.5145.ER.CB
- 05.5145.ES.CB



Luminous flux luminaire
247 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	2827	0.25
2	707	0.51
3	314	0.76
4	177	1.02
5	113	1.27


Optic Medium - 2700K

Non Dimmable

- 05.5141.40
- 05.5141.14
- 05.5141.ER
- 05.5141.ES

Casambi

- 05.5141.40.CB
- 05.5141.14.CB
- 05.5141.ER.CB
- 05.5141.ES.CB



Luminous flux luminaire
261 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1353	0.45
2	338	0.89
3	150	1.34
4	85	1.79
5	54	2.23


Optic Medium - 3000K

Non Dimmable

- 05.5146.40
- 05.5146.14
- 05.5146.ER
- 05.5146.ES

Casambi

- 05.5146.40.CB
- 05.5146.14.CB
- 05.5146.ER.CB
- 05.5146.ES.CB



Luminous flux luminaire
289 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1498	0.45
2	375	0.89
3	166	1.34
4	94	1.79
5	60	2.23


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Atom 90 Designed By Piero Lissoni

Power LED 5,5W - 432 lm - 2700K/CRI 90 / 446 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V.

Optic Spot - 2700K


Dali

- 05.5140.40.DA
- 05.5140.14.DA
- 05.5140.ER.DA
- 05.5140.ES.DA

1-10V

- 05.5140.40.1V
- 05.5140.14.1V
- 05.5140.ER.1V
- 05.5140.ES.1V





Luminous flux luminaire
224 lm

Beam Angle:	14°	
h(m)	E(lx)	D(m)
1	2564	0.25
2	641	0.51
3	285	0.76
4	160	1.02
5	103	1.27

Optic Spot - 3000K


Dali

- 05.5145.40.DA
- 05.5145.14.DA
- 05.5145.ER.DA
- 05.5145.ES.DA

1-10V

- 05.5145.40.1V
- 05.5145.14.1V
- 05.5145.ER.1V
- 05.5145.ES.1V





Luminous flux luminaire
247 lm

Beam Angle:	14°	
h(m)	E(lx)	D(m)
1	2827	0.25
2	707	0.51
3	314	0.76
4	177	1.02
5	113	1.27

Optic Medium - 2700K


Dali

- 05.5141.40.DA
- 05.5141.14.DA
- 05.5141.ER.DA
- 05.5141.ES.DA

1-10V

- 05.5141.40.1V
- 05.5141.14.1V
- 05.5141.ER.1V
- 05.5141.ES.1V





Luminous flux luminaire
261 lm

Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	1353	0.45
2	338	0.89
3	150	1.34
4	85	1.79
5	54	2.23

Optic Medium - 3000K


Dali

- 05.5146.40.DA
- 05.5146.14.DA
- 05.5146.ER.DA
- 05.5146.ES.DA

1-10V

- 05.5146.40.1V
- 05.5146.14.1V
- 05.5146.ER.1V
- 05.5146.ES.1V





Luminous flux luminaire
289 lm

Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	1498	0.45
2	375	0.89
3	166	1.34
4	94	1.79
5	60	2.23


Luminaires with 1–10V dimming are not compatible with suspension profiles.


Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

Atom 120 Designed By Piero Lissoni

Power LED 8W - 600 lm - 2700K/CRI 90 / 648 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play).

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play).

Optic Spot - 2700K


Non Dimmable

- 05.5150.40
- 05.5150.14
- 05.5150.ER
- 05.5150.ES

Casambi

- 05.5150.40.CB
- 05.5150.14.CB
- 05.5150.ER.CB
- 05.5150.ES.CB

14°
SPOT



Luminous flux luminaire
433 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	5839	0.24
2	1460	0.48
3	649	0.72
4	365	0.95
5	234	1.19

Optic Spot - 3000K


Non Dimmable

- 05.5155.40
- 05.5155.14
- 05.5155.ER
- 05.5155.ES

Casambi

- 05.5155.40.CB
- 05.5155.14.CB
- 05.5155.ER.CB
- 05.5155.ES.CB

14°
SPOT



Luminous flux luminaire
440 lm

Beam Angle:		14°
h(m)	E(lx)	D(m)
1	5879	0.24
2	1470	0.49
3	653	0.73
4	367	0.97
5	235	1.21

Optic Medium - 2700K


Non Dimmable

- 05.5151.40
- 05.5151.14
- 05.5151.ER
- 05.5151.ES

Casambi

- 05.5151.40.CB
- 05.5151.14.CB
- 05.5151.ER.CB
- 05.5151.ES.CB

20°
MEDIUM



Luminous flux luminaire
364 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	2557	0.35
2	639	0.70
3	284	1.06
4	160	1.41
5	102	1.76

Optic Medium - 3000K


Non Dimmable

- 05.5156.40
- 05.5156.14
- 05.5156.ER
- 05.5156.ES

Casambi

- 05.5156.40.CB
- 05.5156.14.CB
- 05.5156.ER.CB
- 05.5156.ES.CB

20°
MEDIUM



Luminous flux luminaire
373 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	2621	0.35
2	655	0.70
3	291	1.06
4	164	1.41
5	105	1.76


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Atom 120 Designed By Piero Lissoni

Power LED 8W - 600 lm - 2700K/CRI 90 / 648 lm - 3000K/CRI 90







LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Módulo de iluminación LED de proyección para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V.

Optic Spot - 2700K


Dali

- 05.5150.40.DA
- 05.5150.14.DA
- 05.5150.ER.DA
- 05.5150.ES.DA

1-10V

- 05.5150.40.1V
- 05.5150.14.1V
- 05.5150.ER.1V
- 05.5150.ES.1V





Luminous flux luminaire
433 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5839	0.24
2	1460	0.48
3	649	0.72
4	365	0.95
5	234	1.19

Optic Spot - 3000K


Dali

- 05.5155.40.DA
- 05.5155.14.DA
- 05.5155.ER.DA
- 05.5155.ES.DA

1-10V

- 05.5155.40.1V
- 05.5155.14.1V
- 05.5155.ER.1V
- 05.5155.ES.1V





Luminous flux luminaire
440 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5879	0.24
2	1470	0.49
3	653	0.73
4	367	0.97
5	235	1.21

Optic Medium - 2700K


Dali

- 05.5151.40.DA
- 05.5151.14.DA
- 05.5151.ER.DA
- 05.5151.ES.DA

1-10V

- 05.5151.40.1V
- 05.5151.14.1V
- 05.5151.ER.1V
- 05.5151.ES.1V





Luminous flux luminaire
364 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	2557	0.35
2	639	0.70
3	284	1.06
4	160	1.41
5	102	1.76

Optic Medium - 3000K


Dali

- 05.5156.40.DA
- 05.5156.14.DA
- 05.5156.ER.DA
- 05.5156.ES.DA

1-10V

- 05.5156.40.1V
- 05.5156.14.1V
- 05.5156.ER.1V
- 05.5156.ES.1V





Luminous flux luminaire
373 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	2621	0.35
2	655	0.70
3	291	1.06
4	164	1.41
5	105	1.76


Luminaires with 1–10V dimming are not compatible with suspension profiles.


Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

Atom 200 Designed By Piero Lissoni

Top LED 10,5W - 1005 lm - 2700K/CRI 90 / 1080 lm - 3000K/CRI 90







LED general lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play).
Warning: Only ceiling installation.

Módulo de iluminación LED de luz general para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable inalámbricamente de manera individual mediante Casambi. La gestión a través de Casambi se realiza a través de la APP FLOS Control® para dispositivos móviles (disponible en Apple Store y Google Play).
Advertencia: Solo instalación en techo.

2700K


Non Dimmable

- 05.5160.40
- 05.5160.14
- 05.5160.ER
- 05.5160.ES

Casambi

- 05.5160.40.CB
- 05.5160.14.CB
- 05.5160.ER.CB
- 05.5160.ES.CB





Luminous flux luminaire
395 lm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	145	2.86
2	36	5.73
3	16	8.59
4	9	11.45
5	6	14.32

3000K


Non Dimmable

- 05.5161.40
- 05.5161.14
- 05.5161.ER
- 05.5161.ES

Casambi

- 05.5161.40.CB
- 05.5161.14.CB
- 05.5161.ER.CB
- 05.5161.ES.CB





Luminous flux luminaire
424 lm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	156	2.86
2	39	5.73
3	17	8.59
4	10	11.45
5	6	14.32


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


NEW

Atom 200 Designed By Piero Lissoni

Top LED 10,5W - 1005 lm - 2700K/CRI 90 / 1080 lm - 3000K/CRI 90







LED general lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.
Warning: Only ceiling installation.

Módulo de iluminación LED de luz general para ser instalado en el sistema Zero Track Pro. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V.
Advertencia: Solo instalación en techo.

2700K


Dali

- 05.5160.40.DA
- 05.5160.14.DA
- 05.5160.ER.DA
- 05.5160.ES.DA

1-10V

- 05.5160.40.1V
- 05.5160.14.1V
- 05.5160.ER.1V
- 05.5160.ES.1V





Luminous flux luminaire
395 lm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	145	2.86
2	36	5.73
3	16	8.59
4	9	11.45
5	6	14.32

3000K


Dali

- 05.5161.40.DA
- 05.5161.14.DA
- 05.5161.ER.DA
- 05.5161.ES.DA

1-10V

- 05.5161.40.1V
- 05.5161.14.1V
- 05.5161.ER.1V
- 05.5161.ES.1V





Luminous flux luminaire
424 lm

Beam Angle: 110°


h(m)	E(lx)	D(m)
1	156	2.86
2	39	5.73
3	17	8.59
4	10	11.45
5	6	14.32


Luminaires with 1–10V dimming are not compatible with suspension profiles.
Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

Magic Stick by Jorge Herrera

Power LED 10,5W - 1200 lm - 2700K/CRI 90 / 1200 lm - 3000K/CRI 90







LED diffuse lighting module for installation in the Zero Track Pro system. Can be adjusted by rotating from its central line. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V. Warning: Only ceiling installation.


Módulo de iluminación LED de luz difusa para ser instalado en el sistema Zero Track Pro. Orientable por rotación desde su eje central. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V. Advertencia: Solo instalación en techo.

Rod 100 - 2700K

Non Dimmable
- 05.3200.40
- 05.3200.14
- 05.3200.ER
- 05.3200.ES

Dali
- 05.3200.40.DA
- 05.3200.14.DA
- 05.3200.ER.DA
- 05.3200.ES.DA

1-10V
- 05.3200.40.1V
- 05.3200.14.1V
- 05.3200.ER.1V
- 05.3200.ES.1V



Luminous flux luminaire
587 lm

Beam Angle: - 112°


h(m)	E(lx)	D(m)
1	153	4.34
2	38	8.69
3	17	13.03
4	10	17.38
5	6	21.72

Rod 100 - 3000K

Non Dimmable
- 05.3201.40
- 05.3201.14
- 05.3201.ER
- 05.3201.ES

Dali
- 05.3201.40.DA
- 05.3201.14.DA
- 05.3201.ER.DA
- 05.3201.ES.DA

1-10V
- 05.3201.40.1V
- 05.3201.14.1V
- 05.3201.ER.1V
- 05.3201.ES.1V



Luminous flux luminaire
608 lm

Beam Angle: - 112°


h(m)	E(lx)	D(m)
1	158	4.34
2	40	8.69
3	18	13.03
4	10	17.38
5	6	21.72

Rod 145 - 2700K

Non Dimmable
- 05.3220.40
- 05.3220.14
- 05.3220.ER
- 05.3220.ES

Dali
- 05.3220.40.DA
- 05.3220.14.DA
- 05.3220.ER.DA
- 05.3220.ES.DA

1-10V
- 05.3220.40.1V
- 05.3220.14.1V
- 05.3220.ER.1V
- 05.3220.ES.1V



Luminous flux luminaire
587 lm

Beam Angle: - 112°


h(m)	E(lx)	D(m)
1	153	4.34
2	38	8.69
3	17	13.03
4	10	17.38
5	6	21.72

Rod 145 - 3000K

Non Dimmable
- 05.3221.40
- 05.3221.14
- 05.3221.ER
- 05.3221.ES

Dali
- 05.3221.40.DA
- 05.3221.14.DA
- 05.3221.ER.DA
- 05.3221.ES.DA

1-10V
- 05.3221.40.1V
- 05.3221.14.1V
- 05.3221.ER.1V
- 05.3221.ES.1V



Luminous flux luminaire
608 lm

Beam Angle: - 112°

h(m)	E(lx)	D(m)
1	158	4.34
2	40	8.69
3	18	13.03
4	10	17.38
5	6	21.72


Luminaires with 1–10V dimming are not compatible with suspension profiles.
Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.


NEW

Magic Stick Asymmetric by Jorge Herrera

Power LED 12W - 1450 lm - 2700K/CRI 90 / 1490 lm - 3000K/CRI 90







LED diffuse and accent lighting module for installation in the Zero Track Pro system. Can be adjusted by rotating from its axis located in an asymmetrical position. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V. Warning: Only ceiling installation.


Módulo de iluminación LED, que combina luz difusa y de acento, para ser instalado en el sistema Zero Track Pro. Orientable por rotación desde su eje ubicado en posición asimétrica. Convertidor electrónico DC/DC incorporado. Regulable de manera individual mediante protocolo DALI y broadcast mediante 1-10V. Advertencia: Solo instalación en techo.

Rod 100 - 2700K

Non Dimmable
- 05.3210.40
- 05.3210.14
- 05.3210.ER
- 05.3210.ES

Dali
- 05.3210.40.DA
- 05.3210.14.DA
- 05.3210.ER.DA
- 05.3210.ES.DA


1-10V
- 05.3210.40.1V
- 05.3210.14.1V
- 05.3210.ER.1V
- 05.3210.ES.1V



Luminous flux luminaire 587 lm

Beam Angle: - 112°

h(m)	E(lx)	D(m)
1	153	4.34
2	38	8.69
3	17	13.03
4	10	17.38
5	6	21.72



Luminous flux luminaire 136 lm

Beam Angle: 17°


h(m)	E(lx)	D(m)
1	675	0.29
2	169	0.59
3	75	0.88
4	42	1.18
5	27	1.47

Rod 100 - 3000K

Non Dimmable
- 05.3211.40
- 05.3211.14
- 05.3211.ER
- 05.3211.ES

Dali
- 05.3211.40.DA
- 05.3211.14.DA
- 05.3211.ER.DA
- 05.3211.ES.DA


1-10V
- 05.3211.40.1V
- 05.3211.14.1V
- 05.3211.ER.1V
- 05.3211.ES.1V



Luminous flux luminaire 608 lm

Beam Angle: - 112°

h(m)	E(lx)	D(m)
1	158	4.34
2	40	8.69
3	18	13.03
4	10	17.38
5	6	21.72



Luminous flux luminaire 140 lm

Beam Angle: 17°


h(m)	E(lx)	D(m)
1	698	0.29
2	174	0.59
3	78	0.88
4	44	1.18
5	28	1.47

Rod 145 - 2700K

Non Dimmable
- 05.3230.40
- 05.3230.14
- 05.3230.ER
- 05.3230.ES

Dali
- 05.3230.40.DA
- 05.3230.14.DA
- 05.3230.ER.DA
- 05.3230.ES.DA


1-10V
- 05.3230.40.1V
- 05.3230.14.1V
- 05.3230.ER.1V
- 05.3230.ES.1V



Luminous flux luminaire 587 lm

Beam Angle: - 112°

h(m)	E(lx)	D(m)
1	153	4.34
2	38	8.69
3	17	13.03
4	10	17.38
5	6	21.72



Luminous flux luminaire 136 lm

Beam Angle: 17°


h(m)	E(lx)	D(m)
1	675	0.29
2	169	0.59
3	75	0.88
4	42	1.18
5	27	1.47

Rod 145 - 3000K

Non Dimmable
- 05.3231.40
- 05.3231.14
- 05.3231.ER
- 05.3231.ES

Dali
- 05.3231.40.DA
- 05.3231.14.DA
- 05.3231.ER.DA
- 05.3231.ES.DA


1-10V
- 05.3231.40.1V
- 05.3231.14.1V
- 05.3231.ER.1V
- 05.3231.ES.1V



Luminous flux luminaire 608 lm

Beam Angle: - 112°

h(m)	E(lx)	D(m)
1	158	4.34
2	40	8.69
3	18	13.03
4	10	17.38
5	6	21.72



Luminous flux luminaire 140 lm

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	698	0.29
2	174	0.59
3	78	0.88
4	44	1.18
5	28	1.47


Luminaires with 1–10V dimming are not compatible with suspension profiles.

Las luminarias con regulación 1–10V no son compatibles con los perfiles de suspensión.

ZERO TRACK

DESIGNED BY FLOS ARCHITECTURAL

SURFACE



40 White
40 Blanco

05 Polished Silver
05 Plata Pulida

06 Chrome
06 Cromo

14 Black
14 Negro

CZ Bronce
CZ Bronze

18 Deep brown
18 Deep brown

LIGHT MODULES

FIND ME 0



LIGHT SOURCE
POWER LED
3,5W
300 lm
2700K/CRI 90
325 lm
3000K/CRI 90

FIND ME 1



LIGHT SOURCE
POWER LED
5,5W
450 lm
2700K/CRI 90
485 lm
3000K/CRI 90

FIND ME 2



LIGHT SOURCE
POWER LED
10,5W
650 lm
2700K/CRI 90
700 lm
3000K/CRI 90

FIND ME 1 SUSPENSION



LIGHT SOURCE
POWER LED
5,5W
450 lm
2700K/CRI 90
485 lm
3000K/CRI 90

ATOM 90



LIGHT SOURCE
POWER LED
5,5W
450 lm
2700K/CRI 90
485 lm
3000K/CRI 90

ATOM 120



LIGHT SOURCE
POWER LED
8W
635 lm
2700K/CRI 90
680 lm
3000K/CRI 90

ATOM 200



LIGHT SOURCE
POWER LED
10,5W
1050 lm
2700K/CRI 90
1150 lm
3000K/CRI 90

Description
This new system of profiles for surface installation is characterized by its reduced dimensions, providing a minimalist aesthetic which is highly appreciated in various architectural spaces. For non-accessible ceilings, the system has integrated dimmable power supplies, dimmable through Casambi control systems.
The Casambi system for individual Bluetooth dimming of each light point can be managed through the FLOS Control® app powered by Casambi for mobile devices (available on the Apple Store and Google Play).
The system of extruded aluminum tracks up to 3 meters in white, black, deep brown bronze and chrome.
They are equipped with electric tracks supporting 24Vdc power supplies.

Optic system
- Find Me 0: Spot, Medium.
- Find Me 1: Spot, Medium.
- Find Me 2: Spot, Medium, Flood.
- Find Me 1 Suspension: Spot, Medium.
- Atom 90: Spot, Medium.
- Atom 120: Spot, Medium.
- Atom 200: General lighting.

Power Supply
The system can be powered by a remote power supply (not included) or by power supply equipments to be inserted in the track, which include a power supply.
The initial power connector has a space for cable insertion through both the upper and side parts. The power connector, middle power supply and 90° corners can be powered only from the back.
The maximum length of the track with the same driver is 10 meters.

Additional Information
Electrical system powered at 24Vdc and limited to a maximum current of 5A and a maximum power of 120W.
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Este nuevo sistema de perfiles para su instalación en superficie se caracteriza por sus dimensiones reducidas lo que le confiere una estética minimalista muy apreciada en diversos espacios arquitectónicos. Para soluciones en techos no accesibles, el sistema dispone de fuentes de alimentación atenuables integradas, mediante sistemas de control Casambi.
El sistema Casambi para regulación individual bluetooth de cada punto de luz se realiza mediante APP FLOS Control® powered by Casambi para dispositivos móviles (disponible en Apple Store y Google Play).
El sistema de carriles de aluminio de hasta 3m extruido en blanco, negro, deep brown, bronce y cromo.
Están dotados de pistas eléctricas para ser alimentadas a 24Vdc.

Sistema Óptico
- Find Me 0: Spot, Medium.
- Find Me 1: Spot, Medium.
- Find Me 2: Spot, Medium, Flood.
- Find Me 1 Suspension: Spot, Medium.
- Atom 90: Spot, Medium.
- Atom 120: Spot, Medium.
- Atom 200: General lighting.

Unidades de Alimentación
El sistema puede alimentarse mediante fuente de alimentación remota no incluida o con los equipos de alimentación para insertar en el carril que sí incluyen una fuente de alimentación.
El conector de alimentación inicial dispone de reserva para la entrada de los cables tanto por la parte superior como por el lateral. El conector de alimentación, el alimentador intermedio y las esquinas de 90º son alimentables solo por la parte trasera.
La longitud máxima del carril con un mismo driver es de 10 m.

Información Adicional
Sistema eléctrico alimentado a 24Vdc y limitado a una corriente máxima de 5A y 120W.
Índice de protección IP20.
Instalable sobre superficies normalmente inflamables.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

FLOS
CONTROL BY CASAMBI
Available on the App Store
GET IT ON Google Play

HOW TO ORDER

1 CHOOSE YOUR PROFILE AND LENGTH

SURFACE PROFILE







L: 1 / 2 / 3 m

2 COMPLETE WITH MOUNTING ACCESSORIES

Feed connector



Right & Left

End cap



Intermediate Feed connector



Straight

Stopper



Intermediate connector



Feed 90° Corner



Feed Inner 90° Corner



Feed T piece



Feed Cross piece



3 SELECT POWER SUPPLY AND CONTROL OPTION

Recessed installation remote driver

(select the driver with the appropriate power according to the needs of your project)

Non Dimmable



60W / 100W / 120W

Casambi



60W / 100W / 120W

+



Casambi

Surface Installation Driver

Non Dimmable


Power Supply Surface End



96W

or

Power Supply Surface Middle



96W

4 SELECT A LIGHT MODULE AND CONTROL OPTION

Standard / Casambi Integrated (individual control)

Find Me 0





S/M

Atom 90





S/M

Find Me 1





S/M

Atom 120





S/M

Find Me 2





S/M/F

Atom 200





General Lighting

Find Me Suspension





S/M


ZERO TRACK SURFACE — PROFILES

Profiles

Electro-mechanical indoor profile for surface installation (ceiling or wall). To be fixed with specific screw plugs that come with the profile. 1-meter to 3-meters lengths.
It is necessary to order the power connector, intermediate connectors and covers separately.
Feed unit connectors available as 90° flat corner and curve (symmetric element for left/right corner), ceiling/wall - wall/wall inner corner, as well as “T” and “X” shape.
For vertical installations, installing the stopper is mandatory. It must be ordered separately.

Perfiles

Perfil electromecánico de interior para su instalación en superficie (techo o pared) con fijación mediante tornillos tacos específicos servidos con el perfil. Con longitudes de 1 a 3m.
Necesario pedir por separado conector de alimentación, conectores intermedios y tapas.
Disponibles esquinas mecánicas alimentables de 90° y curva en el mismo plano (elemento simétrico para esquina izquierda y derecha) y esquina de 90° en distinto plano (techo-pared y pared-pared interior), así como uniones en “T” y cruces.
Para instalaciones verticales es necesario instalar el tope de fijación (stopper) que se tiene que pedir por separado.




L: 1 m / 2 m / 3 m

L: 1000 mm
06.2500.40
06.2500.06
06.2500.14
06.2500.CZ
06.2500.18
L: 2000 mm
06.2501.40
06.2501.06
06.2501.14
06.2501.CZ
06.2501.18
L: 3000 mm
06.2502.40
06.2502.06
06.2502.14
06.2502.CZ
06.2502.18

Feed unit for remote power supply unit. Power cable inserting is possible both from the top and the side.

Conector de alimentación para equipo remoto. Posible entrada del cable de alimentación tanto superior como lateral.






06.2540.40
06.2540.14
06.2540.CZ
06.2540.18

Feed intermediate connector. Upper feeding cable entry.

Conector de alimentación intermedio. Entrada del cable de alimentación superior.






06.2541.40
06.2541.14
06.2541.CZ
06.2541.18

Intermediate connector.

Conector intermedio.






06.2506.40
06.2506.14

90° flat corner. Can be powered. It has a rear space for the supply connection.

Esquina plana 90°. Alimentable, con reserva para acometida por la parte trasera.






06.2542.40
06.2542.14
06.2542.CZ
06.2542.18

Ceiling/wall - wall/wall inner corner. Can be powered. It has two spaces for the supply connection located on each side at the rear.

Esquina interior techo/pared - pared/pared. Alimentable, con dos reservas para acometida por la parte trasera en cada lado.






06.2543.40
06.2543.14
06.2543.CZ
06.2543.18

Interior ceiling/ceiling-wall/ wall curve. Can be powered via connections on the back.

Curva interior techo/techo - pared/pared. Alimentable, con acometida por la parte trasera.






06.2544.40
06.2544.14
06.2544.CZ
06.2544.18

T-shaped connector. Can be powered via connections on the back.

Conector en forma de “T” . Alimentable, con acometida por la parte trasera.






06.2545.40
06.2545.14
06.2545.CZ
06.2545.18

Cross-shaped connector. Can be powered via connections on the back.

Conector en forma de cruz . Alimentable, con acometida por la parte trasera.





06.2546.40
06.2546.14
06.2546.CZ
06.2546.18

End cap.

Terminal.





06.2509.40
06.2509.14
06.2509.CZ
06.2509.18

Stopper. For fixing luminaires in vertical track installations.

Stopper. Para fijación de luminarias en instalaciones de carril vertical.







08.0630.40
08.0630.14

Find Me 0 Designed By Jorge Herrera

Power LED 3,5W - 300 lm - 2700K/CRI 90 / 3,5W - 325 lm - 3000K/CRI 90







LED accent lighting module to be installed in the Zero Track system.
Incorporated DC/DC electronic converter.
To individually control the lights, select integrated Casambi versions.
Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Zero Track.
Convertidor electrónico DC/DC incorporado.
Para el control individual de las luminarias seleccionar versiones Casambi integrated.
Accesorios incluidos (honeycomb y cruceta de apantallamiento).


2700K

- 09.3801.40A
- 09.3801.05A
- 09.3801.14A
- 09.3801.CZA
- 09.3801.18A

**Casambi integrated

- 09.3901.40A
- 09.3901.05A
- 09.3901.14A
- 09.3901.CZA
- 09.3901.18A

15° SPOT



Luminous flux luminaire 169 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	1922	0.26
2	481	0.52
3	214	0.77
4	120	1.03
5	77	1.29


3000K

- 09.3800.40A
- 09.3800.05A
- 09.3800.14A
- 09.3800.CZA
- 09.3800.18A

**Casambi integrated

- 09.3900.40A
- 09.3900.05A
- 09.3900.14A
- 09.3900.CZA
- 09.3900.18A

15° SPOT



Luminous flux luminaire 183 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	2084	0.26
2	521	0.52
3	232	0.77
4	130	1.03
5	83	1.29


2700K

- 09.3803.40A
- 09.3803.05A
- 09.3803.14A
- 09.3803.CZA
- 09.3803.18A

**Casambi integrated

- 09.3903.40A
- 09.3903.05A
- 09.3903.14A
- 09.3903.CZA
- 09.3903.18A

25° MEDIUM



Luminous flux luminaire 179 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	929	0.45
2	232	0.89
3	103	1.34
4	58	1.79
5	37	2.23


3000K

- 09.3802.40A
- 09.3802.05A
- 09.3802.14A
- 09.3802.CZA
- 09.3802.18A

**Casambi integrated

- 09.3902.40A
- 09.3902.05A
- 09.3902.14A
- 09.3902.CZA
- 09.3902.18A

25° MEDIUM



Luminous flux luminaire 194 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1007	0.45
2	252	0.89
3	112	1.34
4	63	1.79
5	40	2.23


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.


** El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Find Me 1 Designed By Jorge Herrera

Power LED 5,5W - 450 lm - 2700K/CRI 90 / 5,5W - 485 lm - 3000K/CRI 90







LED accent lighting module to be installed in the Zero Track system.
Incorporated DC/DC electronic converter.
To individually control the lights, select integrated Casambi versions.
Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Zero Track.
Convertidor electrónico DC/DC incorporado.
Para el control individual de las luminarias seleccionar versiones Casambi integrated.
Accesorios incluidos (honeycomb y cruceta de apantallamiento).


2700K

- 09.3812.40A
- 09.3812.05A
- 09.3812.14A
- 09.3812.CZA
- 09.3812.18A

**Casambi integrated

- 09.3912.40A
- 09.3912.05A
- 09.3912.14A
- 09.3912.CZA
- 09.3912.18A

14° SPOT



Luminous flux luminaire
309 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4168	0.24
2	1042	0.48
3	463	0.72
4	261	0.95
5	167	1.19


3000K

- 09.3810.40A
- 09.3810.05A
- 09.3810.14A
- 09.3810.CZA
- 09.3810.18A

**Casambi integrated

- 09.3910.40A
- 09.3910.05A
- 09.3910.14A
- 09.3910.CZA
- 09.3910.18A

14° SPOT



Luminous flux luminaire
314 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4193	0.24
2	1048	0.49
3	466	0.73
4	262	0.97
5	168	1.21


2700K

- 09.3813.40A
- 09.3813.05A
- 09.3813.14A
- 09.3813.CZA
- 09.3813.18A

**Casambi integrated

- 09.3913.40A
- 09.3913.05A
- 09.3913.14A
- 09.3913.CZA
- 09.3913.18A

20° MEDIUM



Luminous flux luminaire
284 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1893	0.35
2	473	0.70
3	210	1.06
4	118	1.41
5	76	1.76


3000K

- 09.3811.40A
- 09.3811.05A
- 09.3811.14A
- 09.3811.CZA
- 09.3811.18A

**Casambi integrated

- 09.3911.40A
- 09.3911.05A
- 09.3911.14A
- 09.3911.CZA
- 09.3911.18A

20° MEDIUM



Luminous flux luminaire
289 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1923	0.35
2	481	0.70
3	214	1.06
4	120	1.41
5	77	1.76


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.


** El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Find Me 2 Designed By Jorge Herrera

Power LED 10,5W* - 650 lm - 2700K/CRI90 / 10,5W* - 700 lm - 3000K/CRI90







LED accent lighting module to be installed in the Zero Track system.
Incorporated DC/DC electronic converter.
To individually control the lights, select integrated Casambi versions.
Accessories included (honeycomb and screening crosspiece).
Warning: Only ceiling installation.

Módulo de iluminación LED de acento para ser instalado en el sistema Zero Track.
Convertidor electrónico DC/DC incorporado.
Para el control individual de las luminarias seleccionar versiones Casambi integrated.
Accesorios incluidos (honeycomb y cruceta de apantallamiento).
Advertencia: Solo instalación en techo.


2700K

- 09.3862.40A
- 09.3862.05A*
- 09.3862.14A
- 09.3862.CZA
- 09.3862.18A

**Casambi integrated

- 09.3962.40A
- 09.3962.05A*
- 09.3962.14A
- 09.3962.CZA
- 09.3962.18A

10° SPOT



Luminous flux luminaire 479 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	9244	0.18
2	2311	0.35
3	1027	0.53
4	578	0.70
5	370	0.88


3000K

- 09.3860.40A
- 09.3860.05A*
- 09.3860.14A
- 09.3860.CZA
- 09.3860.18A

**Casambi integrated

- 09.3960.40A
- 09.3960.05A*
- 09.3960.14A
- 09.3960.CZA
- 09.3960.18A

10° SPOT



Luminous flux luminaire 531 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	10249	0.18
2	2562	0.35
3	1139	0.53
4	641	0.70
5	410	0.88


2700K

- 09.3863.40A
- 09.3863.05A*
- 09.3863.14A
- 09.3863.CZA
- 09.3863.18A

**Casambi integrated

- 09.3963.40A
- 09.3963.05A*
- 09.3963.14A
- 09.3963.CZA
- 09.3963.18A

19° MEDIUM



Luminous flux luminaire 441 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	1991	0.34
2	498	0.67
3	221	1.01
4	124	1.34
5	80	1.68


3000K

- 09.3861.40A
- 09.3861.05A*
- 09.3861.14A
- 09.3861.CZA
- 09.3861.18A

**Casambi integrated

- 09.3961.40A
- 09.3961.05A*
- 09.3961.14A
- 09.3961.CZA
- 09.3961.18A

19° MEDIUM



Luminous flux luminaire 489 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2208	0.34
2	552	0.67
3	245	1.01
4	138	1.34
5	88	1.68


2700K

- 09.3865.40A
- 09.3865.05A*
- 09.3865.14A
- 09.3865.CZA
- 09.3865.18A

**Casambi integrated

- 09.3965.40A
- 09.3965.05A*
- 09.3965.14A
- 09.3965.CZA
- 09.3965.18A

32° FLOOD



Luminous flux luminaire 364 lm

Beam Angle: 32°

h(m)	E(lx)	D(m)
1	722	0.57
2	180	1.15
3	80	1.72
4	45	2.29
5	29	2.87


3000K

- 09.3864.40A
- 09.3864.05A*
- 09.3864.14A
- 09.3864.CZA
- 09.3864.18A

**Casambi integrated

- 09.3964.40A
- 09.3964.05A*
- 09.3964.14A
- 09.3964.CZA
- 09.3964.18A

32° FLOOD



Luminous flux luminaire 404 lm

Beam Angle: 32°

h(m)	E(lx)	D(m)
1	800	0.57
2	200	1.15
3	89	1.72
4	50	2.29
5	32	2.87

* For polished silver finishes their power is 8W / Para el decorado plata pulida la potencia es 8W.


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.


** El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Find Me 1 Suspension Designed By Jorge Herrera

Power LED 5,5W - 450 lm - 2700K/CRI 90 / 5,5W - 485 lm - 3000K/CRI 90







LED accent lighting module to be installed in the Zero Track system.
Incorporated DC/DC electronic converter.
To individually control the lights, select integrated Casambi versions.
Not suitable for vertical installations.
Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Zero Track.
Convertidor electrónico DC/DC incorporado.
Para el control individual de las luminarias seleccionar versiones Casambi integrated.
No se puede instalar en carriles verticales.
Accesorios incluidos (honeycomb y cruceta de apantallamiento).


2700K

- 09.3822.40A
- 09.3822.05A
- 09.3822.14A
- 09.3822.CZA
- 09.3822.18A

**Casambi integrated

- 09.3922.40A
- 09.3922.05A
- 09.3922.14A
- 09.3922.CZA
- 09.3922.18A

14° SPOT



Luminous flux luminaire 309 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4168	0.24
2	1042	0.48
3	463	0.72
4	261	0.95
5	167	1.19


3000K

- 09.3820.40A
- 09.3820.05A
- 09.3820.14A
- 09.3820.CZA
- 09.3820.18A

**Casambi integrated

- 09.3920.40A
- 09.3920.05A
- 09.3920.14A
- 09.3920.CZA
- 09.3920.18A

14° SPOT



Luminous flux luminaire 314 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4193	0.24
2	1048	0.49
3	466	0.73
4	262	0.97
5	168	1.21


2700K

- 09.3823.40A
- 09.3823.05A
- 09.3823.14A
- 09.3823.CZA
- 09.3823.18A

**Casambi integrated

- 09.3923.40A
- 09.3923.05A
- 09.3923.14A
- 09.3923.CZA
- 09.3923.18A

20° MEDIUM



Luminous flux luminaire 186 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1238	0.35
2	310	0.70
3	138	1.06
4	77	1.41
5	50	1.76


3000K

- 09.3821.40A
- 09.3821.05A
- 09.3821.14A
- 09.3821.CZA
- 09.3821.18A

**Casambi integrated

- 09.3921.40A
- 09.3921.05A
- 09.3921.14A
- 09.3921.CZA
- 09.3921.18A

20° MEDIUM



Luminous flux luminaire 193 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1285	0.35
2	321	0.70
3	143	1.06
4	80	1.41
5	51	1.76


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.


** El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Atom 90 Designed By Piero Lissoni

Power LED 5,5W* - 450 lm - 2700K/CRI 90 / 5,5W* - 485 lm - 3000K/CRI 90








LED accent lighting module to be installed in the Zero Track system.
Incorporated DC/DC electronic converter.
To individually control the lights, select integrated Casambi versions.
Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Zero Track.
Convertidor electrónico DC/DC incorporado.
Para el control individual de las luminarias seleccionar versiones Casambi integrated.
Accesorios incluidos (honeycomb y cruceta de apantallamiento).

2700K
- 09.3831.40A
- 09.3831.05*
- 09.3831.14A
- 09.3831.CZA
- 09.3831.18A

**Casambi integrated
- 09.3931.40A
- 09.3931.05*
- 09.3931.14A
- 09.3931.CZA
- 09.3931.18A

14° SPOT



Luminous flux luminaire 224 lm


Beam Angle: 14°

h(m)	E(lx)	D(m)
1	2558	0.25
2	640	0.51
3	284	0.76
4	160	1.02
5	102	1.27

3000K
- 09.3830.40A
- 09.3830.05*
- 09.3830.14A
- 09.3830.CZA
- 09.3830.18A

**Casambi integrated
- 09.3930.40A
- 09.3930.05*
- 09.3930.14A
- 09.3930.CZA
- 09.3930.18A

14° SPOT



Luminous flux luminaire 247 lm


Beam Angle: 14°

h(m)	E(lx)	D(m)
1	2832	0.25
2	708	0.51
3	315	0.76
4	177	1.02
5	113	1.27

2700K
- 09.3833.40A
- 09.3833.05*
- 09.3833.14A
- 09.3833.CZA
- 09.3833.18A

**Casambi integrated
- 09.3933.40A
- 09.3933.05*
- 09.3933.14A
- 09.3933.CZA
- 09.3933.18A

25° MEDIUM



Luminous flux luminaire 261 lm


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1355	0.45
2	339	0.89
3	151	1.34
4	85	1.79
5	54	2.23

3000K
- 09.3832.40A
- 09.3832.05*
- 09.3832.14A
- 09.3832.CZA
- 09.3832.18A

**Casambi integrated
- 09.3932.40A
- 09.3932.05*
- 09.3932.14A
- 09.3932.CZA
- 09.3932.18A

25° MEDIUM



Luminous flux luminaire 289 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1500	0.45
2	375	0.89
3	167	1.34
4	94	1.79
5	60	2.23

* For polished silver finishes their power is 4.7W / Para el decorado plata pulida la potencia es 4.7W.


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.


** El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Atom 120 Designed By Piero Lissoni

Power LED 8W* - 635 lm - 2700K/CRI 90 / 8W* - 680 lm - 3000K/CRI 90








LED accent lighting module to be installed in the Zero Track system.
Incorporated DC/DC electronic converter.
To individually control the lights, select integrated Casambi versions.
Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema Zero Track.
Convertidor electrónico DC/DC incorporado.
Para el control individual de las luminarias seleccionar versiones Casambi integrated.
Accesorios incluidos (honeycomb y cruceta de apantallamiento).

2700K
- 09.3841.40A
- 09.3841.05*
- 09.3841.14A
- 09.3841.CZA
- 09.3841.18A

**Casambi integrated
- 09.3941.40A
- 09.3941.05*
- 09.3941.14A
- 09.3941.CZA
- 09.3941.18A

14° SPOT



Luminous flux luminaire 433 lm


Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5843	0.24
2	1461	0.48
3	649	0.72
4	365	0.95
5	234	1.19

3000K
- 09.3840.40A
- 09.3840.05*
- 09.3840.14A
- 09.3840.CZA
- 09.3840.18A

**Casambi integrated
- 09.3940.40A
- 09.3940.05*
- 09.3940.14A
- 09.3940.CZA
- 09.3940.18A

14° SPOT



Luminous flux luminaire 440 lm


Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5878	0.24
2	1469	0.49
3	653	0.73
4	367	0.97
5	235	1.21

2700K
- 09.3843.40A
- 09.3843.05*
- 09.3843.14A
- 09.3843.CZA
- 09.3843.18A

**Casambi integrated
- 09.3943.40A
- 09.3943.05*
- 09.3943.14A
- 09.3943.CZA
- 09.3943.18A

20° MEDIUM



Luminous flux luminaire 364 lm


Beam Angle: 20°

h(m)	E(lx)	D(m)
1	2557	0.35
2	639	0.70
3	284	1.06
4	160	1.41
5	102	1.76

3000K
- 09.3842.40A
- 09.3842.05*
- 09.3842.14A
- 09.3842.CZA
- 09.3842.18A

**Casambi integrated
- 09.3942.40A
- 09.3942.05*
- 09.3942.14A
- 09.3942.CZA
- 09.3942.18A

20° MEDIUM



Luminous flux luminaire 373 lm


Beam Angle: 20°


h(m)	E(lx)	D(m)
1	2624	0.35
2	656	0.70
3	292	1.06
4	164	1.41
5	105	1.76

Atom 200 Designed By Piero Lissoni

Power LED 10,5W - 1050 lm - 2700K/CRI 90 / 10,5W - 1150 lm - 3000K/CRI 90








LED general lighting module to be installed in the Zero Track system.
Incorporated DC/DC electronic converter.
To individually control the lights, select integrated Casambi versions.
Not suitable for vertical installations.
Warning: Only ceiling installation.

Módulo de iluminación LED general para ser instalado en el sistema Zero Track.
Convertidor electrónico DC/DC incorporado.
Para el control individual de las luminarias seleccionar versiones Casambi integrated.
No se puede instalar en carriles verticales.
Advertencia: Solo instalación en techo.

2700K
- 09.3851.40
- 09.3851.05
- 09.3851.14
- 09.3851.CZ
- 09.3851.18

**Casambi integrated
- 09.3951.40
- 09.3951.05
- 09.3951.14
- 09.3951.CZ
- 09.3951.18

110°



Luminous flux luminaire 395 lm


Beam Angle: 110°

h(m)	E(lx)	D(m)
1	145	2.86
2	36	5.73
3	16	8.59
4	9	11.45
5	6	14.32

3000K
- 09.3850.40
- 09.3850.05
- 09.3850.14
- 09.3850.CZ
- 09.3850.18

**Casambi integrated
- 09.3950.40
- 09.3950.05
- 09.3950.14
- 09.3950.CZ
- 09.3950.18

110°



Luminous flux luminaire 424 lm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	156	2.86
2	39	5.73
3	17	8.59
4	10	11.45
5	6	14.32

* For polished silver finishes their power is 6W / Para el decorado plata pulida la potencia es 6W.

** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.

** El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.


Drivers / Equipos

Remote Installation

Remote power supply.
Non Dimmable. 220/240V.

Fuente de alimentación remota.
No Dimable. 220/240V.





120W - 220/240V
L1: 300 - L2: 40 - L3: 30
60.9516

120W - 220/240V
L1: 268 - L2: 45 - L3: 31
60.9777A

100W - 220/240V
L1: 295 - L2: 43 - L3: 30
60.9443

60W - 220/240V
L1: 180 - L2: 52 - L3: 30
60.9515


60W - 220/240V
L1: 225 - L2: 43 - L3: 30
60.9374

Surface Installation Driver

Power supply surface end. Non Dimmable.

Fuente de alimentación inicial para instalación en superficie. No Dimable.






96W
06.2510.40A
06.2510.05A
06.2510.14A
06.2510.CZA
06.2510.18A

Power supply surface middle. Non Dimmable.

Fuente de alimentación intermedia para instalación en superficie. No Dimable.






96W
06.2511.40A
06.2511.05A
06.2511.14A
06.2511.CZA
06.2511.18A

Control Units / Unidades de Control


Wireless Dimmer Bridge. From 1-10V to Casambi. For remote installation. See product specifications in the Flos Control manual. Recommended to act as a gateway from Lutron to Casambi.

Pasarela de regulación inalámbrica. De 1-10V a Casambi. Para instalación remota. Consulte las especificaciones de producto en el manual Flos Control. Aconsejado para actuar como pasarela de Lutron a Casambi.



DIM 1-10V >> Casambi
08.0824.14

Track Lenght (m)	% Driver Nominal Power
1	95
2	95
3	95
4	95
5	95
6	93
7	91
8	89
9	87
10	85





Example:
Ref. 60.9515: 60W / 4 m track
60W x 0,95= 57W available


	W luminary	Nº luminaries	W luminaries
Find Me 0	3,5	3	10,5
Find Me 1	5,5	0	0
Find Me 2	10,5	0	0
Atom 90	5,5	3	16,5
Atom 120	8	2	16
Atom 200	10,5	1	10,5
	Total system power: 53,5W		

Maximum cable lenght: (driver to track): 5 m . **Cable section:** 2x1,5 mm² . **Maximum track lenght:** 10 m . **Maximum power:** 120W


Remote Driver Installations







Individual Casambi / No DIM



FLOS
CONTROL BY CASAMBI

RECESSED

SURFACE



Recessed Profiles ■ 14 Black
14 Negro

Surface Profiles □ 40 White
40 Blanco ■ 14 Black
14 Negro

Description
Innovative program of ultra-miniaturized structures in recessed and surface versions. Compatible with a wide range of professional lighting solutions by means of magnetic fixing. The Micro Running Magnet is the ultimate solution for exhibition lighting. A complete and professional program that, in addition to its reduced dimensions, provides a balanced and attractive light to highlight each object in the best way and in 360°.
The quintessence of integrated light obtained thanks to a profile of only 5 mm that allows the total integration of micro-devices designed to be combined with the structure until they disappear almost completely.
The incredibly small profile size that characterizes the program enhances the light's flexibility and its relationship with the architecture. The light¬ing bodies are installed by means of a magnetic support inside the profile, providing an unparalleled ease of use.
Magnetic fixing of the luminaries, which allows hot handling. The lighting bodies can be orientated when they are still on, achieving enormous flexibility and adaptability in the configuration at any time.
The profile of all The Micro Running Magnet structural tracks is extruded aluminum, painted black or white, housing a graphite electric track fed at 24V, on which all magnetic luminaries are installed simply by insertion.
Complete range of micro-projectors available in various powers and sizes. They all include professional acrylic stabilized micro-lenses for a maximum control of lighting effects.

Control
- DALI: broadcasting remote control (dimming of all the luminaires in a single group).
- 1/10V: broadcasting remote control (dimming of all the luminaires in a single group).
- Casambi: individual and broadcast control through a tablet or smartphone application (FLOS Control®).
App needed for mobile devices (available in Apple Store y Google Play).

Optic system
The accent light modules are available with intensive optics (spot lens) and extensive optics (medium, flood and wide flood lens).
Linear lighting modules with direct diffused or wall-washer light emission, available in different lengths from 300mm up to 1200mm.

Power Supply
Remote 24V power supply not included.

Additional Information
The Micro Running Magnet is a 24V electrical system limited to a maximum power current of 5A and 120W to avoid overloads. After every 120W make a new connection with a feed unit profile.
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.
For Recessed version, installation on 12.5 mm-thick plasterboard surfaces is recommended. PWM Voltage output dimmable drivers shall be used at. Frequencies between 250 and 500 Hz.
In few cases, depending on the installation, the broadcast dimming can produce an audible buzz.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
EN60598-1 European Technical Standards and anysubsequent additions.

Descripción
Innovador programa de estructuras ultra miniaturizadas en versión empotrada y de superficie. Compatible con una amplia gama de soluciones de iluminación profesional mediante fijación magnética.
The Micro Running Magnet es la solución definitiva para la iluminación de exposiciones. Un programa completo y profesional que además de dimensiones reducidas proporciona una luz equilibrada y atractiva para resaltar cada objeto de la mejor manera en 360°.
La quinta esencia de la luz integrada, obtenida gracias a un perfil de solo 5 mm que permite la integración total de micro dispositivos diseñados para combinarse con la estructura hasta casi desaparecer.
El increíble tamaño reducido del perfil que caracteriza el programa realza la flexibilidad de la luz y su relación con la arquitectura.
La instalación de los cuerpos iluminantes se realiza mediante un soporte magnético dentro del perfil para una facilidad de uso sin igual.
Fijación magnética de las luminarias, lo que permite su manipulación en caliente. Los cuerpos iluminantes se pueden orientar estando encendidos, consiguiendo así una gran flexibilidad y adaptabilidad de la configuración en cualquier momento.
Todos los perfiles estructurales de Micro Running Magnet han sido fabricados con perfilería de aluminio extruido en blanco y negro, provisto de pistas eléctricas alimentadas a 24V, sobre las cuales se instalan mediante un sistema de fijación magnética las luminarias LED.
Gama completa de micro proyectores disponibles en varias potencias y tamaños. Todos incluyen micro lentes profesionales estabilizadas en acrílico para un control máximo de los efectos de iluminación.

Control
- DALI: control broadcast, todas las luminarias a la vez.
- 1/10V: control remoto en broadcasting (dimado de todas las luminarias en grupo).
- Casambi: control individual y broadcast a través de una aplicación para tablet o smartphone (FLOS Control®).
Necesaria app para dispositivos móviles (disponible en Apple Store y Google Play).

Sistema Óptico
Los módulos de luz de acento se encuentran disponibles con óptica intensiva (spot lens) y con ópticas extensivas (medium, flood y wide flood).
Módulos de iluminación lineal de entre 300mm y hasta 1200mm en versiones de luz directa para iluminación general y bañador de pared.

Unidades de Alimentación
Fuente de alimentación remota de 24V no incluida.

Información Adicional
The Micro Running Magnet es un sistema eléctrico alimentado a 24V y limitado a una corriente máxima de 5A y 120W para evitar sobrecargas. Cada vez que completemos los 120W deberemos realizar nuevamente la conexión mediante un perfil de alimentación.
Índice de protección IP20.
Instalable sobre superficies normalmente inflamables.
Se recomienda su instalación en superficies de cartón yeso de 12,5mm de espesor para la versión Recessed. Deben utilizarse drivers regulables con tensión de salida PWM en frecuencias de entre 250 y 500 Hz.
En algunos casos, dependiendo de la instalación, la regulación broadcast puede producir un zumbido.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

THE MICRO RUNNING MAGNET

DESIGNED BY FLOS ARCHITECTURAL

LIGHT MODULES

NANO SPOT



LIGHT SOURCE
POWER LED
2W
165 lm
2700K/CRI 90
170 lm
3000K/CRI 90
185 lm
4000K/CRI 90
200 lm
5000K/CRI 90

MICRO SPOT



LIGHT SOURCE
POWER LED
3W
275 lm
2700K/CRI 90
295 lm
3000K/CRI 90
315 lm
4000K/CRI 90
335 lm
5000K/CRI 90

SPOT



LIGHT SOURCE
POWER LED
6W
545 lm
2700K/CRI 90
585 lm
3000K/CRI 90
625 lm
4000K/CRI 90
665 lm
5000K/CRI 90

LIGHT SHADOW SPOT Ø30



LIGHT SOURCE
POWER LED
3W
293 lm
2700K/CRI 90
311 lm
3000K/CRI 90
335 lm
4000K/CRI 90
419 lm
5000K/CRI 90

FIND ME 0



LIGHT SOURCE
POWER LED
3,5W
249 lm
2700K/CRI 90
270 lm
3000K/CRI 90

FIND ME 1



LIGHT SOURCE
POWER LED
5,5W
446 lm
2700K/CRI 90
463 lm
3000K/CRI 90

LIGHT STRIPE DIFFUSED



LIGHT STRIPE WALL-WASHER



LIGHT SOURCE
TOP LED
15W/m
1440 lm/m
2700K/CRI 90
1550 lm/m
3000K/CRI 90
1660 lm
4000K/CRI 90
1775 lm
5000K/CRI 90

Recessed Profile

14 Black
14 Negro



Surface Profile

40 White
40 Blanco



14 Black
14 Negro



Spots & Light Shadow Spot Ø30

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel*
ER Acero Cepillado*



ES Brushed Bronze*
ES Bronce Cepillado*



*On Demand - Metallic Colours

Find Me

40 White
40 Blanco



14 Black
14 Negro



Light Stripes


14 Black
14 Negro



HOW TO ORDER


1 CHOOSE YOUR PROFILE AND LENGTH

RECESSED PROFILE



L: 1 / 1,5 / 2 / 2,5 / 3 m

SURFACE PROFILE



L: 1 / 1,5 / 2 / 2,5 / 3 m

2 COMPLETE WITH MOUNTING ACCESSORIES

Feed connector



Intermediate connector



Straight

End cap



90º Corner



Electrical / Mechanical joint

Inner corner



Electrical / Mechanical joint

Feed connector



Intermediate connector



Straight

End cap



90º Corner



Electrical / Mechanical

Inner corner



Electrical / Mechanical

3 SELECT POWER SUPPLY

Installation remote driver


(select the driver with the appropriate power according to the needs of your project)

Non Dimmable / Casambi Individual




60W / 100W / 120W

0/1-10V · Push broadcast



Dimmer + 60W / 100W / 120W

DALI · Push broadcast



Dimmer + 60W / 100W / 120W

Casambi broadcast



Dimmer + 60W / 100W / 120W + No DIM

4 SELECT A LIGHT MODULE

No DIM / Broadcast DIM

Light Stripe Diffused



L: 300 mm / 600 mm / 900 mm / 1200 mm

General lighting

Light Stripe Wall-Washer



L: 300 mm / 600 mm / 900 mm / 1200 mm

Wall-Washer

Nano Spot



M/F

Micro Spot



S/M/F

Spot



S/M

Light Shadow Spot Ø30



S/M/F/WF

*On Demand - Metallic Colours

Casambi Individual DIM

Find Me 0



S/M

Find Me 1




S/M


Profiles

Electromechanical profile of reduced size for recessed installation in plasterboard ceilings/walls with lengths from 1 to 3 m.
Fastening accessories included with the profiles.
90° corners available in the same plane (symmetrical element for left and right corners).

Perfiles

Perfil electro-mecánico de dimensiones mínimas para instalaciones empotradas en techos/paredes de cartón yeso con longitudes de 1 m a 3 m.
Accesorios de fijación incluidos en los perfiles.
Disponibles esquinas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha).






L: 1000 mm
06.6000.14
L: 1500 mm
06.6001.14
L: 2000 mm
06.6002.14
L: 2500 mm
06.6003.14
L: 3000 mm
06.6004.14

L: 1 m / 1,5 m / 2m / 2,5m / 3 m

90° Corner.
Electrical/mechanical connection.
Non-feedable. Luminaires cannot be located on corners.

Esquina 90°.
Conexión eléctrica/mecánica.
No alimentable. No se pueden ubicar luminarias en las esquinas.






06.6030.14

Inner corner.
Electrical/mechanical connection.
Non-feedable. Luminaires cannot be located on corners.

Esquina interior.
Conexión eléctrica/mecánica.
No alimentable. No se pueden ubicar luminarias en las esquinas.






06.6032.14

Feed connector.
2m cable included.
Electrical connection. Luminaires cannot be located in the connector.

Conector de alimentación.
Cable de 2m incluido.
Conexión eléctrica. No se pueden ubicar luminarias en el conector.






06.6034.14

Intermediate connector.
Electrical connection. Luminaires cannot be located in the connector.

Conector intermedio.
Conexión eléctrica. No se pueden ubicar luminarias en el conector.





06.6035.14

End cap. 1 unit kit.

Tapa. Kit de 1 unidad.




06.6036.14

Profiles

Electromechanical profile of reduced size for installation on surfaces (ceiling or wall) with lengths from 1 to 3 m.
Fastening accessories included with the profiles.
90° corners available in the same plane (symmetrical element for left and right corners).
The inner part of the profile is always supplied in black.

Perfiles

Perfil electro-mecánico de dimensiones mínimas para instalaciones en superficie (techo o pared) con longitudes de 1 m a 3 m.
Accesorios de fijación incluidos en los perfiles.
Disponibles esquinas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha).
La parte interior del perfil se suministra siempre en negro.






L: 1 m / 1,5 m / 2m / 2,5m / 3 m

L: 1000 mm
06.6010.40
06.6010.14
L: 1500 mm
06.6011.40
06.6011.14
L: 2000 mm
06.6012.40
06.6012.14
L: 2500 mm
06.6013.40
06.6013.14
L: 3000 mm
06.6014.40
06.6014.14

90° Corner.
Electrical/mechanical connection.
Non-feedable. Luminaires cannot be located on corners.

Esquina 90°.
Conexión eléctrica/mecánica.
No alimentable. No se pueden ubicar luminarias en las esquinas.






06.6031.40
06.6031.14

Inner corner.
Electrical/mechanical connection.
Non-feedable. Luminaires cannot be located on corners.

Esquina interior.
Conexión eléctrica/mecánica.
No alimentable. No se pueden ubicar luminarias en las esquinas.






06.6033.40
06.6033.14

Feed connector.
2m cable included.
Electrical connection. Luminaires cannot be located in the connector.

Conector de alimentación.
Cable de 2m incluido.
Conexión eléctrica. No se pueden ubicar luminarias en el conector.






06.6034.40
06.6034.14

Intermediate connector.
Electrical connection. Luminaires cannot be located in the connector.

Conector intermedio.
Conexión eléctrica. No se pueden ubicar luminarias en el conector.





06.6035.14


End cap. 1 unit kit.

Tapa. Kit de 1 unidad.




06.6036.40
06.6036.14

SURFACE INSTALLATION




RECESSED INSTALLATION



• Can I cut the profiles?
Yes. The profiles can be cut at any point and the electrical connection continued using the intermediate connector.

• ¿Puedo cortar los perfiles?
Sí, los perfiles se pueden cortar en cualquier punto y se continúa la conexión eléctrica con el conector intermedio.



• Can I place a spotlight in the corners or between two profiles?
No, the corner pieces have no free space for luminaires, the corner and the joints between profiles contain the electrical connections as intermediate connectors.


• ¿Puedo ubicar un foco en las esquinas o entre dos perfiles?
No, las piezas de las esquinas no tienen hueco libre para albergar las luminarias, la esquina y las uniones entre perfiles contienen las conexiones eléctricas a modo de conectores intermedios.

• Can I dim the luminaires individually?
No. By using the recommended equipment, they can be adjusted, but all at once.

• ¿Puedo atenuar la luz de las luminarias individualmente?
No, utilizando los equipos recomendados es posible regular, pero siempre se regularán todas las luminarias a la vez.

• What is the maximum length that can be powered with one power supply on a structure?
The maximum length of a profile that can be powered with one power source is 10 metres.

• ¿Cuál es la longitud máxima que se puede alimentar con una fuente de alimentación en una estructura?
La longitud máxima de un perfil que puede alimentarse con una fuente de alimentación es de 10 metros.




• Can I power a structure from a corner or intermediate connector?
No. The corners and intermediate connector of this system cannot be powered.


• ¿Puedo alimentar una estructura desde una esquina o conector intermedio?
No, las esquinas y el conector intermedio de este sistema no son alimentables.

Light Stripe Diffused

Top LED 15W/m - 1440 lm/m - 2700K/CRI 90 / 15W/m - 1550 lm/m - 3000K/CRI 90 / 15W/m - 1660 lm/m - 4000K/CRI 90 / 15W/m -1775 lm/m - 5000K/CRI 90








Diffused LED light module to be installed in The Micro Running Magnet System. Built-in DC/DC electronic voltage converter.

Módulo de iluminación LED de luz difusa para ser instalado en el sistema The Micro Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.


2700K
L: 300 mm - 4,5W
03.2260.14



Luminous flux luminaire 205 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	57	3.11
2	14	6.21
3	6	9.32
4	4	12.43
5	2	15.53


3000K
L: 300 mm - 4,5W
03.2261.14



Luminous flux luminaire 230 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	64	3.11
2	16	6.21
3	7	9.32
4	4	12.43
5	3	15.53


2700K
L: 600 mm - 9W
03.2264.14



Luminous flux luminaire 411 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	114	3.11
2	29	6.21
3	13	9.32
4	7	12.43
5	5	15.53


3000K
L: 600 mm - 9W
03.2265.14



Luminous flux luminaire 460 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	128	3.11
2	32	6.21
3	14	9.32
4	8	12.43
5	5	15.53


2700K
L: 900 mm - 13,5W
03.2268.14



Luminous flux luminaire 616 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	172	3.11
2	43	6.21
3	19	9.32
4	11	12.43
5	7	15.53


3000K
L: 900 mm - 13,5W
03.2269.14



Luminous flux luminaire 689 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	192	3.11
2	48	6.21
3	21	9.32
4	12	12.43
5	8	15.53


2700K
L: 1200 mm - 18W
03.2272.14



Luminous flux luminaire 821 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	229	3.11
2	57	6.21
3	25	9.32
4	14	12.43
5	9	15.53


3000K
L: 1200 mm - 18W
03.2273.14



Luminous flux luminaire 919 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	256	3.11
2	64	6.21
3	28	9.32
4	16	12.43
5	10	15.53


4000K
L: 300 mm - 4,5W
03.2262.14



Luminous flux luminaire 237 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	66	3.11
2	16	6.21
3	7	9.32
4	4	12.43
5	3	15.53


5000K
L: 300 mm - 4,5W
03.2263.14



Luminous flux luminaire 226 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	63	3.11
2	16	6.21
3	7	9.32
4	4	12.43
5	3	15.53


4000K
L: 600 mm - 9W
03.2266.14



Luminous flux luminaire 473 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	132	3.11
2	33	6.21
3	15	9.32
4	8	12.43
5	5	15.53


5000K
L: 600 mm - 9W
03.2267.14



Luminous flux luminaire 452 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	126	3.11
2	31	6.21
3	14	9.32
4	8	12.43
5	5	15.53


4000K
L: 900 mm - 13,5W
03.2270.14



Luminous flux luminaire 710 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	198	3.11
2	49	6.21
3	22	9.32
4	12	12.43
5	8	15.53


5000K
L: 900 mm - 13,5W
03.2271.14



Luminous flux luminaire 678 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	189	3.11
2	47	6.21
3	21	9.32
4	12	12.43
5	8	15.53


4000K
L: 1200 mm - 18W
03.2274.14



Luminous flux luminaire 947 lm

Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	264	3.11
2	66	6.21
3	29	9.32
4	16	12.43
5	11	15.53

5000K
L: 1200 mm - 18W
03.2275.14




Luminous flux luminaire 904 lm


Beam Angle: 114°		
h(m)	E(lx)	D(m)
1	252	3.11
2	63	6.21
3	28	9.32
4	16	12.43
5	10	15.53

Light Stripe Wall-Washer

Top LED 15W/m - 1440 lm/m - 2700K/CRI 90 / 15W/m - 1550 lm/m - 3000K/CRI 90 / 15W/m - 1660 lm/m - 4000K/CRI 90 / 15W/m -1775 lm/m - 5000K/CRI 90








Asymmetric wall-washer LED light module to be installed in The Micro Running Magnet System. Built-in DC/DC electronic voltage converter.


Módulo de iluminación LED de luz asimétrica wall-washer para ser instalado en el sistema The Micro Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.

2700K
L: 300 mm - 4,5W
03.2280.14




Luminous flux luminaire
185 lm

3000K
L: 300 mm - 4,5W
03.2281.14




Luminous flux luminaire
207 lm

2700K
L: 600 mm - 9W
03.2284.14




Luminous flux luminaire
370 lm

3000K
L: 600 mm - 9W
03.2285.14




Luminous flux luminaire
414 lm

2700K
L: 900 mm - 13,5W
03.2288.14




Luminous flux luminaire
555 lm

3000K
L: 900 mm - 13,5W
03.2289.14




Luminous flux luminaire
621 lm

2700K
L: 1200 mm - 18W
03.2292.14




Luminous flux luminaire
740 lm

3000K
L: 1200 mm - 18W
03.2293.14




Luminous flux luminaire
829 lm

4000K
L: 300 mm - 4,5W
03.2282.14




Luminous flux luminaire
213 lm

5000K
L: 300 mm - 4,5W
03.2283.14




Luminous flux luminaire
204 lm

4000K
L: 600 mm - 9W
03.2286.14




Luminous flux luminaire
427 lm

5000K
L: 600 mm - 9W
03.2287.14




Luminous flux luminaire
408 lm

4000K
L: 900 mm - 13,5W
03.2290.14




Luminous flux luminaire
640 lm

5000K
L: 900 mm - 13,5W
03.2291.14




Luminous flux luminaire
611 lm

4000K
L: 1200 mm - 18W
03.2294.14



Luminous flux luminaire
853 lm

5000K
L: 1200 mm - 18W
03.2295.14





Luminous flux luminaire
815 lm

Nano Spot

Power LED 2W - 165 lm - 2700K/CRI 90 / 2W - 170 lm - 3000K/CRI 90 / 2W - 185 lm - 4000K/CRI 90 / 2W -200 lm - 5000K/CRI 90








Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Módulo de iluminación LED de acento para ser instalado en el sistema The Micro Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.

Optic Medium

2700K
- 03.2210.40A
- 03.2210.14A






Luminous flux luminaire 73 lm

Beam Angle:	23°
h(m)	E(lx) D(m)
1	286 0.41
2	72 0.83
3	32 1.24
4	18 1.65
5	11 2.06

3000K
- 03.2211.40A
- 03.2211.14A






Luminous flux luminaire 70 lm

Beam Angle:	23°
h(m)	E(lx) D(m)
1	278 0.41
2	69 0.83
3	31 1.24
4	17 1.65
5	11 2.06

4000K
- 03.2212.40A
- 03.2212.14A






Luminous flux luminaire 81 lm

Beam Angle:	23°
h(m)	E(lx) D(m)
1	319 0.41
2	80 0.83
3	35 1.24
4	20 1.65
5	13 2.06

5000K
- 03.2213.40A
- 03.2213.14A






Luminous flux luminaire 82 lm

Beam Angle:	23°
h(m)	E(lx) D(m)
1	324 0.41
2	81 0.83
3	36 1.24
4	20 1.65
5	13 2.06

Optic Flood

2700K
- 03.2215.40A
- 03.2215.14A






Luminous flux luminaire 77 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	238 0.57
2	60 1.15
3	26 1.72
4	15 2.29
5	10 2.87

3000K
- 03.2216.40A
- 03.2216.14A






Luminous flux luminaire 75 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	231 0.57
2	58 1.15
3	26 1.72
4	14 2.29
5	9 2.87

4000K
- 03.2217.40A
- 03.2217.14A






Luminous flux luminaire 86 lm

Beam Angle:	32°
h(m)	E(lx) D(m)
1	266 0.57
2	66 1.15
3	30 1.72
4	17 2.29
5	11 2.87

5000K
- 03.2218.40A
- 03.2218.14A






Luminous flux luminaire 87 lm


Beam Angle:	32°
h(m)	E(lx) D(m)
1	269 0.57
2	67 1.15
3	30 1.72
4	17 2.29
5	11 2.87

Micro Spot

Power LED 3W - 275 lm - 2700K/CRI 90 / 3W - 295 lm - 3000K/CRI 90 / 3W - 315 lm - 4000K/CRI 90 / 3W - 335 lm - 5000K/CRI 90







Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Honeycomb accessory available. Must be ordered separately.


Módulo de iluminación LED de acento para ser instalado en el sistema The Micro Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.

Accesorio honeycomb disponible. Se ha de pedir por separadao.

Optic Spot

2700K
03.2300.40A
03.2300.14A

16° SPOT




Luminous flux luminaire 216 lm

Beam Angle:	16°
h(m) E(lx)	D(m)
1 2028	0.27
2 507	0.54
3 225	0.82
4 127	1.09
5 81	1.36

3000K
03.2301.40A
03.2301.14A

16° SPOT




Luminous flux luminaire 224 lm

Beam Angle:	16°
h(m) E(lx)	D(m)
1 2103	0.27
2 526	0.54
3 234	0.82
4 131	1.09
5 84	1.36

4000K
03.2302.40A
03.2302.14A

16° SPOT




Luminous flux luminaire 240 lm

Beam Angle:	16°
h(m) E(lx)	D(m)
1 2249	0.27
2 562	0.54
3 250	0.82
4 141	1.09
5 90	1.36

5000K
03.2303.40A
03.2303.14A

16° SPOT




Luminous flux luminaire 243 lm

Beam Angle:	16°
h(m) E(lx)	D(m)
1 2278	0.27
2 570	0.54
3 253	0.82
4 142	1.09
5 91	1.36

Optic Flood

2700K
03.2225.40A
03.2225.14A

31° FLOOD




Luminous flux luminaire 183 lm

Beam Angle:	31°
h(m) E(lx)	D(m)
1 538	0.54
2 134	1.09
3 60	1.63
4 34	2.17
5 22	2.72

3000K
03.2226.40A
03.2226.14A

31° FLOOD




Luminous flux luminaire 189 lm

Beam Angle:	31°
h(m) E(lx)	D(m)
1 558	0.54
2 139	1.09
3 62	1.63
4 35	2.17
5 22	2.72

4000K
03.2227.40A
03.2227.14A

31° FLOOD




Luminous flux luminaire 217 lm

Beam Angle:	31°
h(m) E(lx)	D(m)
1 639	0.54
2 160	1.09
3 71	1.63
4 40	2.17
5 26	2.72

5000K
03.2228.40A
03.2228.14A

31° FLOOD




Luminous flux luminaire 205 lm

Beam Angle:	31°
h(m) E(lx)	D(m)
1 605	0.54
2 151	1.09
3 67	1.63
4 38	2.17
5 24	2.72

Optic Medium

2700K
03.2220.40A
03.2220.14A

28° MEDIUM




Luminous flux luminaire 200 lm

Beam Angle:	28°
h(m) E(lx)	D(m)
1 747	0.51
2 187	1.02
3 83	1.54
4 47	2.05
5 30	2.56

3000K
03.2221.40A
03.2221.14A

28° MEDIUM




Luminous flux luminaire 207 lm

Beam Angle:	28°
h(m) E(lx)	D(m)
1 775	0.51
2 194	1.02
3 86	1.54
4 48	2.05
5 31	2.56

4000K
03.2222.40A
03.2222.14A

28° MEDIUM




Luminous flux luminaire 231 lm

Beam Angle:	28°
h(m) E(lx)	D(m)
1 865	0.51
2 216	1.02
3 96	1.54
4 54	2.05
5 35	2.56

5000K
03.2223.40A
03.2223.14A

28° MEDIUM




Luminous flux luminaire 224 lm


Beam Angle:	28°
h(m) E(lx)	D(m)
1 840	0.51
2 210	1.02
3 93	1.54
4 52	2.05
5 34	2.56

Spot

Power LED 6W - 545 lm - 2700K/CRI 90 / 6W - 585 lm - 3000K/CRI 90 / 6W - 625 lm - 4000K/CRI 90 / 6W - 665 lm - 5000K/CRI 90







Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Honeycomb accessory available. Must be ordered separately.

Módulo de iluminación LED de acento para ser instalado en el sistema The Micro Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.


Accesorio honeycomb disponible. Se ha de pedir por separadao.

Optic Spot

2700K

☐ 03.2230.40A
■ 03.2230.14A

13° SPOT




Luminous flux luminaire 340 lm

Beam Angle:	13°	
h(m)	E(lx)	D(m)
1	5646	0.23
2	1411	0.45
3	627	0.68
4	353	0.90
5	226	1.13

3000K

☐ 03.2231.40A
■ 03.2231.14A

13° SPOT




Luminous flux luminaire 324 lm

Beam Angle:	13°	
h(m)	E(lx)	D(m)
1	5394	0.23
2	1349	0.45
3	599	0.68
4	337	0.90
5	216	1.13

4000K

☐ 03.2232.40A
■ 03.2232.14A

13° SPOT




Luminous flux luminaire 369 lm

Beam Angle:	13°	
h(m)	E(lx)	D(m)
1	6134	0.23
2	1534	0.45
3	682	0.68
4	383	0.90
5	245	1.13

5000K

☐ 03.2233.40A
■ 03.2233.14A

13° SPOT



Luminous flux luminaire 384 lm


Beam Angle:	13°	
h(m)	E(lx)	D(m)
1	6386	0.23
2	1597	0.45
3	710	0.68
4	399	0.90
5	255	1.13

Optic Medium

2700K

☐ 03.2235.40A
■ 03.2235.14A

20° MEDIUM




Luminous flux luminaire 315 lm

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	1861	0.35
2	465	0.71
3	207	1.06
4	116	1.41
5	74	1.77

3000K

☐ 03.2236.40A
■ 03.2236.14A

20° MEDIUM




Luminous flux luminaire 301 lm

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	1777	0.35
2	444	0.71
3	197	1.06
4	111	1.41
5	71	1.77

4000K

☐ 03.2237.40A
■ 03.2237.14A

20° MEDIUM




Luminous flux luminaire 342 lm

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	2022	0.35
2	505	0.71
3	225	1.06
4	126	1.41
5	81	1.77

5000K

☐ 03.2238.40A
■ 03.2238.14A

20° MEDIUM




Luminous flux luminaire 356 lm


Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	2105	0.35
2	526	0.71
3	234	1.06
4	132	1.41
5	84	1.77

Light Shadow Spot Ø30

Power LED 3W - 293 lm - 2700K/CRI 90 / 3W - 311 lm - 3000K/CRI 90 / 3W - 335 lm - 4000K/CRI 90 / 3W - 419 lm - 5000K/CRI 90








Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Módulo de iluminación LED de acento para ser instalado en el sistema The Micro Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.

Optic Spot

2700K
- 03.2240.40A
- 03.2240.14A

11° SPOT




Luminous flux luminaire 249 lm

Beam Angle:	11°	
h(m)	E(lx)	D(m)
1	3980	0.20
2	995	0.40
3	442	0.60
4	249	0.80
5	159	1.00

3000K
- 03.2241.40A
- 03.2241.14A

11° SPOT




Luminous flux luminaire 264 lm

Beam Angle:	11°	
h(m)	E(lx)	D(m)
1	4220	0.20
2	1055	0.40
3	469	0.60
4	264	0.80
5	169	1.00

4000K
- 03.2242.40A
- 03.2242.14A

11° SPOT




Luminous flux luminaire 284 lm

Beam Angle:	11°	
h(m)	E(lx)	D(m)
1	4540	0.20
2	1135	0.40
3	504	0.60
4	284	0.80
5	182	1.00

5000K
- 03.2243.40A
- 03.2243.14A

11° SPOT




Luminous flux luminaire 356 lm

Beam Angle:	11°	
h(m)	E(lx)	D(m)
1	5691	0.20
2	1423	0.40
3	632	0.60
4	356	0.80
5	228	1.00

Optic Medium

2700K
- 03.2245.40A
- 03.2245.14A

22° MEDIUM




Luminous flux luminaire 252 lm

Beam Angle:	22°	
h(m)	E(lx)	D(m)
1	1762	0.39
2	441	0.78
3	196	1.17
4	110	1.56
5	70	1.95

3000K
- 03.2246.40A
- 03.2246.14A

22° MEDIUM




Luminous flux luminaire 268 lm

Beam Angle:	22°	
h(m)	E(lx)	D(m)
1	1874	0.39
2	469	0.78
3	208	1.17
4	117	1.56
5	75	1.95

4000K
- 03.2247.40A
- 03.2247.14A

22° MEDIUM




Luminous flux luminaire 289 lm

Beam Angle:	22°	
h(m)	E(lx)	D(m)
1	2021	0.39
2	505	0.78
3	225	1.17
4	126	1.56
5	81	1.95

5000K
- 03.2248.40A
- 03.2248.14A

22° MEDIUM




Luminous flux luminaire 361 lm

Beam Angle:	22°	
h(m)	E(lx)	D(m)
1	2525	0.39
2	631	0.78
3	281	1.17
4	158	1.56
5	101	1.95

Optic Flood

2700K
- 03.2250.40A
- 03.2250.14A

29° FLOOD




Luminous flux luminaire 242 lm

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	938	0.52
2	234	1.04
3	104	1.57
4	59	2.09
5	38	2.61

3000K
- 03.2251.40A
- 03.2251.14A

29° FLOOD




Luminous flux luminaire 257 lm

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	996	0.52
2	249	1.04
3	111	1.57
4	62	2.09
5	40	2.61

4000K
- 03.2252.40A
- 03.2252.14A

29° FLOOD




Luminous flux luminaire 277 lm

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	1073	0.52
2	268	1.04
3	119	1.57
4	67	2.09
5	43	2.61

5000K
- 03.2253.40A
- 03.2253.14A

29° FLOOD




Luminous flux luminaire 347 lm

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	1345	0.52
2	336	1.04
3	149	1.57
4	84	2.09
5	54	2.61

Optic Wide Flood

2700K
- 03.2255.40A
- 03.2255.14A

43° WIDE FLOOD




Luminous flux luminaire 241 lm

Beam Angle:	43°	
h(m)	E(lx)	D(m)
1	514	0.80
2	128	1.59
3	57	2.39
4	32	3.19
5	21	3.99

3000K
- 03.2256.40A
- 03.2256.14A

43° WIDE FLOOD




Luminous flux luminaire 256 lm

Beam Angle:	43°	
h(m)	E(lx)	D(m)
1	546	0.80
2	136	1.59
3	61	2.39
4	34	3.19
5	22	3.99

4000K
- 03.2257.40A
- 03.2257.14A

43° WIDE FLOOD




Luminous flux luminaire 276 lm

Beam Angle:	43°	
h(m)	E(lx)	D(m)
1	588	0.80
2	147	1.59
3	65	2.39
4	37	3.19
5	24	3.99

5000K
- 03.2258.40A
- 03.2258.14A

43° WIDE FLOOD



Luminous flux luminaire 345 lm

Beam Angle:	43°	
h(m)	E(lx)	D(m)
1	736	0.80
2	184	1.59
3	82	2.39
4	46	3.19
5	29	3.99

Accessories / Accesorios


Light Shadow Spot Ø30


Honeycomb	Panel de abeja		08.0790.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0791.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0792.00

Find Me 0

Power LED 3,5W - 249 lm - 2700K/CRI 90 / 3,5W - 270 lm - 3000K/CRI 90







LED accent lighting module to be installed in the Micro Running Magnet system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights. Accessories included (honeycomb and screening crosspiece).


Módulo de iluminación LED de acento para ser instalado en el sistema Micro Running Magnet. Convertidor electrónico DC/DC incorporado. Casambi vía Flos Control App para el control individual de las luminarias. Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Optic Spot
2700K

*Casambi integrated

03.2322.40
03.2322.14

15° SPOT



Luminous flux luminaire
169 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	1922	0.26
2	481	0.52
3	214	0.77
4	120	1.03
5	77	1.29

3000K

*Casambi integrated

03.2320.40
03.2320.14

15° SPOT



Luminous flux luminaire
183 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	2084	0.26
2	521	0.52
3	232	0.77
4	130	1.03
5	83	1.29

Optic Medium
2700K

*Casambi integrated

03.2323.40
03.2323.14

25° MEDIUM



Luminous flux luminaire
179 lm

Beam Angle: 25°


h(m)	E(lx)	D(m)
1	929	0.45
2	232	0.89
3	103	1.34
4	58	1.79
5	37	2.23

3000K

*Casambi integrated

03.2321.40
03.2321.14

25° MEDIUM



Luminous flux luminaire
194 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1007	0.45
2	252	0.89
3	112	1.34
4	63	1.79
5	40	2.23


* The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.


* El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Find Me 1

Power LED 5,5W - 446 lm - 2700K/CRI 90 / 5,5W - 463 lm - 3000K/CRI 90







LED accent lighting module to be installed in the Micro Running Magnet system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights. Accessories included (honeycomb and screening crosspiece).


Módulo de iluminación LED de acento para ser instalado en el sistema Micro Running Magnet. Convertidor electrónico DC/DC incorporado. Casambi vía Flos Control App para el control individual de las luminarias. Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Optic Spot
2700K

*Casambi integrated

☐ 03.2332.40
■ 03.2332.14

14° SPOT



Luminous flux luminaire 309 lm


Beam Angle:	14°	
h(m)	E(lx)	D(m)
1	4168	0.24
2	1042	0.48
3	463	0.72
4	261	0.95
5	167	1.19

3000K

*Casambi integrated

☐ 03.2330.40
■ 03.2330.14

14° SPOT



Luminous flux luminaire 314 lm


Beam Angle:	14°	
h(m)	E(lx)	D(m)
1	4193	0.24
2	1048	0.49
3	466	0.73
4	262	0.97
5	168	1.21

Optic Medium
2700K

*Casambi integrated

☐ 03.2333.40
■ 03.2333.14

20° MEDIUM



Luminous flux luminaire 284 lm


Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	1893	0.35
2	473	0.70
3	210	1.06
4	118	1.41
5	76	1.76

3000K

*Casambi integrated

☐ 03.2331.40
■ 03.2331.14

20° MEDIUM



Luminous flux luminaire 289 lm

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	1923	0.35
2	481	0.70
3	214	1.06
4	120	1.41
5	77	1.76

* The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.

* El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Accessories / Accesorios

Micro Spot

Honeycomb.

Honeycomb.



08.0190.14

Spot

Honeycomb.

Honeycomb.



08.0191.14


Non Dimmable

Remote Installation

Remote power supply.
Non Dimmable. 220/240V.

Fuente de alimentación remota.
No Dimable. 220/240V.





120W - 220/240V
L1: 300 - L2: 40 - L3: 30
60.9516

120W - 220/240V
L1: 268 - L2: 45 - L3: 31
60.9777A

100W - 220/240V
L1: 295 - L2: 43 - L3: 30
60.9443

60W - 220/240V
L1: 180 - L2: 52 - L3: 30
60.9515

60W - 220/240V
L1: 225 - L2: 43 - L3: 30
60.9374


Dimmer

Remote Installation

Dimmable Control Unit 12-24Vdc. Requires driver. It must be ordered separately.
Dimming range 20-100%.

Unidad de Control Dimable 12-24Vdc Requiere driver, pedir por separado.
Rango de regulación 20-100%.





L1: 57 - L2: 19 - L3: 44


Max. 10A 0/1-10V · Push
60.9394

Remote Installation

Dimmable Control Unit 12-24-48Vdc. Requires driver. It must be ordered separately. Dimming range 10-100%.
'Power supply not included.
Dimming range 10-100%.
120W@12Vdc / 240W@24Vdc / 480W@48Vdc /

Unidad de control dimable Dali de módulos LED, para equipos de 12-24-48V. No incluye fuente de alimentación.
Rango de regulación 10-100%.
120W@12Vdc / 240W@24Vdc / 480W@48Vdc /





L1: 57 - L2: 25 - L3: 44,5


Max. 10A DALI · Push
60.9677A

Remote Installation

Dimmable Control Unit 12-48V, 10A max. Requires driver. It must be ordered separately.

Unidad de Control Dimable 12-48V, 10A max. Requiere driver, pedir por separado.






Max. 10A Casambi · Push
60.9938

Control Units / Unidades de Control


Wireless Dimmer Bridge. From 1-10V to Casambi. For remote installation. See product specifications in the Flos Control manual. Recommended to act as a gateway from Lutron to Casambi.

Pasarela de regulación inalámbrica. De 1-10V a Casambi. Para instalación remota. Consulte las especificaciones de producto en el manual Flos Control. Aconsejado para actuar como pasarela de Lutron a Casambi.




DIM 1-10V >> Casambi
08.0824.14


Remote Driver Installations




No DIM / Casambi individual




0/1-10V · Push broadcast



DALI · Push broadcast



Casambi broadcast



NEW


THE RUNNING MAGNET

DESIGNED BY FLOS ARCHITECTURAL

RECESSED

SURFACE

SUSPENSION
UP&DOWN / DOWN



Recessed Profiles ■ 14 Black
14 Negro

Surface/Suspension Profiles ■ 14 Black
14 Negro

□ 40 White
40 Blanco







Light Stripe

Spot

Surface

Suspension

Recessed
Flos Kit
Installation

Recessed
Conventional
Installation

Description
Innovative lighting system for indoor use, for surface, suspended or recessed mounting on plasterboard walls or ceilings, comprising a series of magnetic tracks that house the LED lighting modules.
The profile of all The Running Magnet structural tracks is extruded aluminum, painted black or white, housing a graphite electric track fed at 24V, on which all magnetic luminaries are installed simply by insertion.
Suspended track is also available with the option of indirect lighting.
The Running Magnet family is completed with ambient lighting units and accent units with different optics, as well as a selection of decorative luminaires taken and adapted from FLOS Home Collection.
The lighting modules incorporate a magnetic mounting system for total mobility and flexibility. All light modules are available with on board potentiometer, DALI dimmable option and Casambi.

Control
- To manage using DALI protocol, it is necessary to connect the control data bus directly to the profile.
- To manage using Casambi (Max. 200 luminaires) it is necessary to order fixtures in the Casambi version, these are compatible with all profiles available for the system.
The app FLOS Control® powered by Casambi for mobile devices is also necessary (available on Apple Store and Google Play).

Power Supply
Remote 24V power supply not included.

Accessories
- Different lenses for Spot Module and Multi Spot 4.
- Screening external ring for Spot Module.
- Elliptical, flood lens and honeycomb for Anthony Spot Track.
- Honeycomb and crosspiece included in Spot 120.
- Light Shadow Spots has honeycomb accessories and CCT dichroic filters but they are not included.

Additional Information
The Recessed version can only be installed on 12.5 mm thick plasterboard surfaces.
The Running Magnet 2.0 is a 24V electrical system limited to a maximum power current of 8A and 185W to avoid overloads.
After every 185W make a new connection with a feed unit profile.
In the Up&Down version indirect illumination and the electromechanical track are powered independently.
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Innovador sistema de iluminación para interior en versiones superficie, suspendida o empotrada en pared/techo de cartón yeso. Compuesto por perfilería magnética donde se posicionan, mediante sistema de fijación magnética, módulos de iluminación.
Todos los perfiles estructurales de Running Magnet han sido fabricados con perfilería de aluminio extruido en blanco y negro, provisto de pistas elécticas de grafito alimentadas a 24V, sobre las cuales se instalan mediante un sistema de fijación magnética las luminarias LED.
La versión suspendida también está disponible para luz indirecta.
La familia The Running Magnet se completa con módulos de iluminación ambiental y de acento con diferentes ópticas además de una selección de luminarias decorativas extraídas y adaptadas de FLOS Home Collection.
Los módulos de iluminación incorporan un sistema de fijación magnética que permite una completa movilidad y flexibilidad.
Todos los módulos de luz disponen de un potenciómetro instalado, regulación DALI o Casambi según se desee.

Control
- Para gestión mediante protocolo DALI es necesario conectar el bus de datos de control directamente al perfil.
- Para gestión mediante Casambi (Máximo 200 luminarias) es necesario pedir luminarias versión Casambi, estas son compatibles con cualquier tipo de perfil del sistema.
Necesaria app FLOS Control® powered by Casambi para dispositivos móviles (disponible en Apple Store y Google Play).

Unidades de Alimentación
Fuente de alimentación remota de 24V no incluida.

Accesorios
- Diferentes lentes para Spot Module y Multi Spot 4.
- Aro exterior apantallador para Spot Module.
- Lente elíptica, flood y honeycomb para Anthony Spot track.
- Honeycomb y cruceta incluidos en Spot 120.
- Light Shadow Spots dispone de accesorios honeycomb y filtros dicroicos CCT como accesorios no incluidos.

Información Adicional
Únicamente instalable en superficies de cartón yeso de 12,5mm de espesor para la versión Recessed.
The Running Magnet es un sistema eléctrico alimentado a 24V y limitado a una corriente máxima de 8A y 185W para evitar sobrecargas.
Cada vez que completemos los 185W deberemos realizar nuevamente la conexión mediante un perfil de alimentación.
En la versión Up&Down la iluminación indirecta y el Perfil electro-mecánico tienen alimentaciones independientes.
Índice de protección IP20.
Instalable sobre superficies normalmente inflamables.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play

LIGHT MODULES

LIGHT STRIPE



LIGHT SOURCE
TOP LED
25W/m
2060 lm/m
2700K/CRI 90
2178 lm/m
3000K/CRI 90

STRING LIGHT



LIGHT SOURCE
POWER LED
14W
930 lm
2700K/CRI 90
930 lm
3000K/CRI 90

MINI GLO-BALL



LIGHT SOURCE
POWER LED
3,5/7W
2700K/CRI 80
3000K/CRI 80

LIGHT SHADOW SPOT 30



LIGHT SOURCE
POWER LED
4W
298 lm
2700K/CRI 90
318 lm
3000K/CRI 90

LIGHT SHADOW SPOT 45



LIGHT SOURCE
LED ARRAY
10W
756 lm
2700K/CRI 90
799 lm
3000K/CRI 90

SPOT MODULE



LIGHT SOURCE
POWER LED
8W
560 lm
2700K/CRI 90
600 lm
3000K/CRI 90

SPOT 120



LIGHT SOURCE
POWER LED
12,5W/14W DALI
1003 lm
2700K/CRI 90
1002 lm
3000K/CRI 90

ANTHONY SPOT TRACK



LIGHT SOURCE
POWER LED
14W
1045 lm
2700K/CRI 90
1308 lm
3000K/CRI 90

WORKMATES SMALL



LIGHT SOURCE
TOP LED
HIGH EFFICIENCY
Up to 10,5W
CRI 90
1382 lm / 3000K
1416 lm / 3500K
1440 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM
Up to 10,5W
CRI 98
1013 lm / 3000K
1021 lm / 3500K
1032 lm / 4000K

WORKMATES LARGE



LIGHT SOURCE
TOP LED
HIGH EFFICIENCY
Up to 13,5W
CRI 90
1853 lm / 3000K
1886 lm / 3500K
1896 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM
Up to 13,5W
CRI 98
1358 lm / 3000K
1368 lm / 3500K
1382 lm / 4000K

LIGHT SHADOW



LIGHT SOURCE
POWER LED
10,8W
4x298 lm
2700K/CRI 90
4x318 lm
3000K/CRI 90

LIGHT SHADOW WALL-WASHER



LIGHT SOURCE
POWER LED
10,8W
4x270 lm
2700K/CRI 90
4x285 lm
3000K/CRI 90

MULTI SPOT 4



LIGHT SOURCE
POWER LED
10W
840 lm
2700K/CRI 90
896 lm
3000K/CRI 90

FIND ME SUSPENSION



LIGHT SOURCE
POWER LED
8W
560 lm
2700K/CRI 90
600 lm
3000K/CRI 90

MULTIFUNCTION SMART DEVICE



FLOS CONTROL®
by Casambi

NEW

Light Stripe, Spot Module, Multi Spot 4, String Lights, Mini Glo-Ball

14 Black
14 Negro




Light Shadow Spot

40 White
40 Blanco

14 Black
14 Negro

ER Brushed Steel
ER Acero Cepillado

ES Brushed Bronze
ES Bronce Cepillado



Workmates

All White
All White

White
Blanco

Black
Negro

Anodized Silver
Anodized Silver



Light Shadow


HIGH COMFORT

White
Blanco

Black
Negro

Steel
Acero

Bronze
Bronce




HIGH COMFORT

White
Blanco

Black
Negro

Steel
Acero

Bronze
Bronce



Spot 120

40 White
40 Blanco

14 Black
14 Negro



Light Shadow Wall-Washer

40 White
40 Blanco


14 Black
14 Negro



Anthony Spot Track

40 White
40 Blanco

14 Black
14 Negro



Find Me Suspension

40 White
40 Blanco

05 Polished Silver
05 Plata Pulida

14 Black
14 Negro



Multifunction Smart Device

40 White
40 Blanco

14 Black
14 Negro




NEW

HOW TO ORDER


1 CHOOSE YOUR PROFILE AND LENGTH


RECESSED PROFILE



L: 1 / 1,5 / 2 / 2,5 / 3 m


SURFACE / SUSPENSION DOWN PROFILE





L: 1 / 1,5 / 2 / 2,5 / 3 m

SUSPENSION UP&DOWN PROFILE



L: 1 / 1,5 / 2 / 2,5 / 3 m

2 COMPLETE WITH MOUNTING ACCESSORIES

End cap



Included with feed profile

90° Corner



Electrical / mechanical joint

Inner corner



Electrical / mechanical joint

Outer corner



Electrical / mechanical joint

Surface

Inner corner



Electrical / mechanical joint

Surface / Suspension Down

End cap



Included with feed profile

90° Corner



Electrical / mechanical joint

Suspension Down

Corner 90° Grid



T-Joint



X-Joint



Electrical / mechanical joint

End cap



Included with feed profile

90° Corner



Electrical / mechanical joint

Accessories

Fixed ceiling kit



or

Adjustable ceiling kit



Surface Accessories

Fixed ceiling kit
(Included)



Suspension Accessories

Suspension kit
(Included)



+

Surface rose
(not Included)



or

Recessed rose
(not Included)



Suspension Accessories

Suspension kit
(Included)



+

Surface rose
(not Included)



or

Recessed rose
(not Included)



NEW

3 SELECT POWER SUPPLY AND CONTROL OPTION

(select the driver with the appropriate power according to the needs of your project)

Remote power supply
Profiles: Recessed, Surface, Suspension Down



60W 120W 200W

Remote power supply
Profile: Suspension Up & Down

Down
Non Dimmable / Casambi / DALI



60W 120W 200W

Up



60W

120W

DALI


200W

Casambi

Surface power supply
Profile: Surface




Surface power supply
Profile: Suspension Down / Up & Down



185W

Non Dimmable / Casambi*
*(only light modules, up light no dim)



185W

DALI
(Up&Down Dimming synchronized)

4 SELECT A LIGHT MODULE AND CONTROL OPTION

Non Dimmable / Dali / Casambi

Light Stripe



General lighting

Light Shadow Spot 30



S/M/F/WF

Light Shadow Spot 45



S/M/F

Spot Module



S

Spot 120



S

Anthony Spot Track



S/M

Multi Spot 4



S/M

Light Shadow



S/M/F/WF

Light Shadow W-W



Wall - Washer

Workmates Small



WF/O/HC

Workmates Large



WF/O/HC

String Light



Mini Glo-Ball



General lighting

Find Me Suspension




General lighting

Multifunction Smart Device
FLOS Control® by Casambi



RECESSED INSTALLATION




* Corners can be powered / Esquinas alimentables.

Profiles

Electromechanical profile for recessed installation in plasterboard ceilings and walls.
Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles. Both versions available in lengths from 1 m to 3 m. Covers included with the power feed profiles.
90° corners available in the same plane (symmetrical element for left and right corners), symmetrical 90° inner and outer corners in different planes.
For connection to the driver.
Permanent or adjustable fastening kits available (optional). The fastening kits for the roof permit installing without using aluminimum fastening profiles.
Recommended for installations where the Running Magnet can be installed before the suspended plasterboard ceiling.

Perfiles

Perfil electro-mecánico para instalaciones empotradas en techos/paredes de cartón yeso.
Perfiles lineales disponibles en dos versiones: perfiles de alimentación, para conexión a driver, y perfiles intermedios. Ambas versiones con longitudes de 1 m a 3 m. Tapas incluidas en los perfiles de alimentación.
Disponibles esquinas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha), esquinas simétricas de 90° en distinto plano en interior y exterior. Provistos para conexión a driver.
Kits de sujeción, fijo o ajustable, disponibles (opcional). Los kits de sujeción a techo permiten la instalación sin necesidad de perfiles de aluminio de sujeción. Recomendado para instalaciones en las que se puede instalar el perfil Running Magnet antes que el falso techo de cartón yeso.



L: 1 m / 1,5 m / 2 m / 2,5 m / 3 m

Feed Unit Profiles

L: 1000 mm
06.1638.14
L: 1500 mm
06.1639.14
L: 2000 mm
06.1640.14
L: 2500 mm
06.1641.14
L: 3000 mm
06.1642.14


Intermediate Profiles

L: 1000 mm
06.1643.14
L: 1500 mm
06.1644.14
L: 2000 mm
06.1645.14
L: 2500 mm
06.1646.14
L: 3000 mm
06.1647.14

90° Corner.
Can be powered.

Esquina 90°.
Alimentable.






06.1648.14

Inner corner.
Can be powered.

Esquina interior.
Alimentable.






06.1650.14

Outer corner.
Can be powered.

Esquina exterior.
Alimentable.






06.1651.14

End caps come complete with all the feed unit profiles. These should only be ordered separately if the installation is exclusively composed of intermediate profiles and fed by corners.

Las tapas van incluidas con todos los perfiles de alimentación. Se deben pedir por separado, solo si la instalación está compuesta por perfiles intermedios y alimentada en las esquinas, exclusivamente.






08.8865.14A

Fixed ceiling kit (optional).
2 unit kit.

Kit de sujeción a techo fijo (opcional). Kit de 2 unidades.






08.8866.14

Profile (mm)	Fixation points	Ceiling Kit to order
1000 / 1500	2	1
2000 / 2500	3	2
3000	4	2

Adjustable ceiling kit (optional).
2 unit kit.

Kit de sujeción a techo ajustable (opcional). Kit de 2 unidades.





08.8867.14


Profile (mm)	Fixation points	Ceiling Kit to order
1000 / 1500	2	1
2000 / 2500	3	2
3000	4	2

Drivers / Equipos

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.

Fuente de alimentación LED para instalación remota en cuadro eléctrico 24V/200W. Para evitar problemas de sobrecarga se recomienda instalar una fuente de alimentación cada 185W. 100/240V.






60.9352

Electronic transformer with constant voltage (24V) for LED. 100/240V.

Transformador electrónico de tensión constante (24V) para LED. 100/240V.






60W
60.9089

Electronic transformer with constant voltage (24V) for LED. 100/240V.

Transformador electrónico de tensión constante (24V) para LED. 100/240V.






120W
60.9407

For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source / Para el dimensionado de la instalación mantener un margen de seguridad de un 15% de la potencia máxima de la fuente de alimentación LED.

SURFACE INSTALLATION




* Corners can be powered / Esquinas alimentables.


Profiles

Electromechanical profile for surface-mounting.
Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles. Both versions available in lengths from 1 m to 3 m.
Covers included with the power feed profiles. Attachment accessories included with all products.
90° corners available in the same plane (symmetrical element for left and right corner) and 90° symmetrical internal corners in a different plane, for the Surface and Down versions. For connection to the driver.
The inner part of the profile is always supplied in black.

Perfiles

Perfil electro-mecánico para instalaciones en superficie.
Perfiles lineales disponibles en dos versiones: perfil de alimentación, para conexión a driver, y perfiles intermedios. Ambas versiones con longitudes de 1 m a 3 m.
Tapas incluidas en los perfiles de alimentación. Accesorios de fijación incluidos en todos los productos.
Disponibles esquinas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha) y esquinas simétricas de 90° en distinto plano en interior, comunes en versiones Surface y Down. Provistos para conexión a driver.
La parte interior del perfil se suministra siempre en negro.







L: 1 m / 1,5 m / 2 m / 2,5 m / 3 m

Feed Unit Profiles





L: 1000 mm
06.1600.40
06.1600.14
L: 1500 mm
06.1601.40
06.1601.14
L: 2000 mm
06.1602.40
06.1602.14
L: 2500 mm
06.1603.40
06.1603.14
L: 3000 mm
06.1604.40
06.1604.14

Intermediate Profiles

L: 1000 mm
06.1605.40
06.1605.14
L: 1500 mm
06.1606.40
06.1606.14
L: 2000 mm
06.1607.40
06.1607.14
L: 2500 mm
06.1608.40
06.1608.14
L: 3000 mm
06.1609.40
06.1609.14


90° Corner. Can be powered.	Esquina 90°. Alimentable.			06.1610.40 06.1610.14
Inner corner. Can be powered.	Esquina interior. Alimentable.			06.1612.40 06.1612.14
End caps come complete with all the feed unit profiles. These should only be ordered separately if the installation is exclusively composed of intermediate profiles and fed by corners.	Las tapas van incluidas con todos los perfiles de alimentación. Se deben pedir por separado, solo si la instalación está compuesta por perfiles intermedios y alimentada en las esquinas, exclusivamente.			08.8887.40A 08.8887.14A

Drivers / Equipos

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.	Fuente de alimentación LED para instalación remota en cuadro eléctrico 24V/200W. Para evitar problemas de sobrecarga se recomienda instalar una fuente de alimentación cada 185W. 100/240V.			60.9352
Electronic transformer with constant voltage (24V) for LED. 100/240V.	Transformador electrónico de tensión constante (24V) para LED. 100/240V.			60W 60.9089
Electronic transformer with constant voltage (24V) for LED. 100/240V.	Transformador electrónico de tensión constante (24V) para LED. 100/240V.			120W 60.9407
Power Supply Surface Profile. 24V/250W. 220-240 Vac.	Perfil de Superficie con Fuente de Alimentación. 24V/250W. 220-240 Vac.			06.1150.40 06.1150.14

For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source / Para el dimensionado de la instalación mantener un margen de seguridad de un 15% de la potencia máxima de la fuente de alimentación LED.

SUSPENSION DOWN INSTALLATION




* Corners can be powered / Esquinas alimentables.


Profiles

Electromechanical profile for suspended installations.
Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles. Both versions available in lengths from 1 m to 3 m.
Covers included with the power feed profiles.
Ceiling connection (4.2 m feed cable) and suspension (4 m steel cable) accessories included in all linear feed or intermediate products. 90° corners in the same plane (symmetrical element for right and left corners) for the Surface and Down versions. Provided for connection to the driver.
The inner part of the profile is always supplied in black.

Perfiles

Perfil electro-mecánico para instalaciones suspendidas.
Perfiles lineales disponibles en dos versiones: perfiles de alimentación, para conexión a driver, y perfiles intermedios. Ambas versiones con longitudes de 1 m a 3 m.
Tapas incluidas en los perfiles de alimentación.
Accesorios para conexión (cable alimentación 4,2 m) y suspensión (cable de acero 4 m) a techo incluidos en todos los productos lineales de alimentación o intermedios.
Disponibles esquinas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha), comunes en versiones Surface y Down.
Provistos para conexión a driver.
La parte interior del perfil se suministra siempre en negro.





L: 1 m / 1,5 m / 2 m / 2,5 m / 3 m

Feed Unit Profiles

L: 1000 mm
06.1626.40
06.1626.14
L: 1500 mm
06.1627.40
06.1627.14
L: 2000 mm
06.1628.40
06.1628.14
L: 2500 mm
06.1629.40
06.1629.14
L: 3000 mm
06.1630.40
06.1630.14

Intermediate Profiles

L: 1000 mm
06.1631.40
06.1631.14
L: 1500 mm
06.1632.40
06.1632.14
L: 2000 mm
06.1633.40
06.1633.14
L: 2500 mm
06.1634.40
06.1634.14
L: 3000 mm
06.1635.40
06.1635.14

Remote Drivers / Equipos remotos

References shared with Up&Down suspension version. Please see next page.
Referencias compartidas con versión suspension Up&Down. Ver página siguiente.







90° Corner.

Cannot be powered. Includes 1 cable suspension kit.

Can be powered. Includes 2 cable suspension kits.

Esquina 90°.

No alimentable. Incluye 1 kit de suspensión con cable.

Alimentable. Incluye 2 kits de suspensión con cable.





Cannot be powered
06.1657.40
06.1657.14

Can be powered
06.1656.40
06.1656.14

End caps come complete with all the feed unit profiles. These should only be ordered separately if the installation is exclusively composed of intermediate profiles and fed by corners.

Las tapas van incluidas con todos los perfiles de alimentación. Se deben pedir por separado, solo si la instalación está compuesta por perfiles intermedios y alimentada en las esquinas, exclusivamente.




08.8887.40A
08.8887.14A

Down grid structures (square or rectangle shapes) / Para estructuras cerradas (cuadrados o rectángulos)

Corner 90º Grid.
Corner to build grig structures perfectly closed. Feed unit.
Dimensions 153x153.

Esquina 90º para estructuras en cuadrículas.
Esquina para la construcción de estructuras en cuadrícula perfectamente cerradas.
Alimentable. Dimensiones 153x153.






06.1740.14

T-Joint Grid Down.
T piece to build grid structures perfectly closed. Feed unit.
Dimensions 265x153.

Unión en T para estructuras en cuadrículas.
Pieza en forma de T, para la construcción de estructuras en cuadrícula perfectamente cerradas.
Alimentable. Dimensiones 265x153.






06.1741.14

X-Joint Grid Down.
Cross piece to build grid structures perfectly closed. Feed unit.
Dimensions 265x265.

Unión en cruz para estructuras en cuadrículas.
Pieza en forma de cruz, para la construcción de estructuras en cuadrícula perfectamente cerradas.
Alimentable. Dimensiones 265x265.






06.1742.14

Suspension Down / Suspension Up&Down
Surface Drivers / Equipos de superficie

Surface power supply for direct and indirect lighting with housing for the driver. 24V/185W - 110/240V equipment included. Cables not included.


Caja de alimentación de superficie tanto para luz directa como luz directa e indirecta con alojamiento para driver. Equipo 24V/185W - 110/240V incluido. Cables no incluidos.



Non Dimmable
08.8886.40
08.8886.14

DALI controller and 24V/185W - 110/240V equipment to supply and control both the direct and indirect lighting, included. Cables not included.


Controlador DALI y equipo 24V/185W - 110/240V para alimentar y controlar tanto la iluminación directa como la indirecta, incluido. Cables no incluidos.



Dali
08.8886.40.DA
08.8886.14.DA

Casambi controller and 24V/185W - 110/240V equipment to supply and control both the direct and indirect lighting, included. Cables not included.

Controlador Casambi y equipo 24V/185W - 110/240V para alimentar y controlar tanto la iluminación directa como la indirecta, incluido. Cables no incluidos.




Casambi
08.8886.40.CB
08.8886.14.CB

Suspension Down / Suspension Up&Down
Remote Drivers Accessories / Accesorios para equipos remotos

Surface rose. Equipment, power cable and suspension cable not included. They must be ordered separately.


Rosetón de alimentación de superficie. Equipo, cable de alimentación y de suspensión no incluidos, pedir por separado.



08.8883.40A
08.8883.14A

Recessed power supply rose. Equipment not included. To be ordered separately.


Rosetón de alimentación empotrado. Equipo no incluido, pedir por separado.



08.8889.40
08.8889.14

For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source / Para el dimensionado de la instalación mantener un margen de seguridad de un 15% de la potencia máxima de la fuente de alimentación LED.

SUSPENSION UP&DOWN INSTALLATION




* Corners can be powered / Esquinas alimentables.

Profiles


Electromechanical profile for suspended installations.
Linear elements in the Up&Down version include indirect LED illumination in the upper part of the profile. Shared or separate power feed.
Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles. Both versions available in lengths from 1 m to 3 m.
Covers included with the power feed profiles. Ceiling connection (4.2 m feed cable) and suspension (4m steel cable) accessories included in all linear feed or intermediate products.
90° corners in the same plane (symmetrical element for right and left corners). Not provided for connection to the driver.
The corners of the Suspended Running Magnet versions are not fitted with indirect illumination. Indirect illumination can be managed as a separate circuit if powered by a dedicated driver and, in the case of the DALI installation,if equipped with a dedicated optional DALI controller. To be ordered separately.
Profiles cannot be cut.
The inner part of the profile is always supplied in black.

Perfiles


Perfil electro-mecánico para instalaciones suspendidas.
Los elementos lineales en versión Up&Down incluyen iluminación LED indirecta en la parte superior del perfil. Pueden alimentarse con alimentación común o independiente.
Perfiles lineales disponibles en dos versiones: perfiles de alimentación, para conexión a driver, y perfiles intermedios. Ambas versiones con longitudes de 1 m a 3 m.
Tapas incluidas en los perfiles de alimentación. Accesorios para conexión (cable alimentación 4,2 m) y suspensión (cable de acero 4 m) a techo incluidos en todos los productos lineales de alimentación o intermedios.
Disponibles esquinas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha). No provistos para conexión a driver.
Las esquinas de las versiones Suspendidas del Running Magnet no incorporan iluminación indirecta. La iluminación indirecta puede ser controlada como un circuito separado si se alimenta con un equipo especial y, en el caso de una instalación DALI, equipada con un equipo opcional de control DALI se debe pedir por separado.
Los perfiles no se pueden cortar.
La parte interior del perfil se suministra siempre en negro.



L: 1 m / 1,5 m / 2 m / 2,5 m / 3 m







Luminous flux luminaire
844 lm *L: 1000 mm

Beam Angle:	91°
h(m)	E(lx) D(m)
1	364 2.05
2	91 4.10
3	40 6.15
4	23 8.20
5	15 10.25

Top LED 8,4W/m Up - 950 lm/m Up - 3000K/CRI 90

Feed Unit Profiles

L: 1000 mm
06.1614.40A
06.1614.14A
L: 1500 mm
06.1615.40A
06.1615.14A
L: 2000 mm
06.1616.40A
06.1616.14A
L: 2500 mm
06.1617.40A
06.1617.14A
L: 3000 mm
06.1618.40A
06.1618.14A


Intermediate Profiles

L: 1000 mm
06.1619.40A
06.1619.14A
L: 1500 mm
06.1620.40A
06.1620.14A
L: 2000 mm
06.1621.40A
06.1621.14A
L: 2500 mm
06.1622.40A
06.1622.14A
L: 3000 mm
06.1623.40A
06.1623.14A

90° Corner.
Cannot be powered. Includes 1 cable suspension kit.

Esquina 90°.
No alimentable. Incluye 1 kit de suspensión con cable.





□ 06.1624.40
■ 06.1624.14

End caps come complete with all the feed unit profiles. These should only be ordered separately if the installation is exclusively composed of intermediate profiles and fed by corners.

Las tapas van incluidas con todos los perfiles de alimentación. Se deben pedir por separado, solo si la instalación está compuesta por perfiles intermedios y alimentada en las esquinas, exclusivamente.




□ 08.8887.40A
■ 08.8887.14A

Suspension Down / Suspension Up&Down
Remote Drivers / Equipos remotos

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.

Fuente de alimentación LED para instalación remota en cuadro eléctrico 24V/200W. Para evitar problemas de sobrecarga se recomienda instalar una fuente de alimentación cada 185W. 100/240V.






60.9352

Electronic transformer with constant voltage (24V) for LED. 100/240V.

Transformador electrónico de tensión constante (24V) para LED. 100/240V.






60W
60.9089
Up lighting max. 6m

Electronic transformer with constant voltage (24V) for LED. 100/240V.

Transformador electrónico de tensión constante (24V) para LED. 100/240V.






120W
60.9407
Up lighting max. 8m

Suspension Up&Down
Remote Dimmable Control Unit / Unidad de control regulable remoto

Dimmable Dali control unit for 12-24-48V LED modules. Power supply not included. For controlling indirect lighting (UP).

Unidad de control dimable Dali para la regulación de módulos LED, para equipos de 12-24-48V. No incluye fuente de alimentación. Para control de la iluminación indirecta (UP).






Dali · Push
Max. 10A
60.9678A

Dimmable Control Unit 12-48V, 10A max. Requires driver. It must be ordered separately.

Unidad de Control Dimable 12-48V, 10A max. Requiere driver, pedir por separado.





Casambi · Push
Max. 10A
60.9938

Surface Drivers & Remote Drivers Accessories / Equipos de superficie y accesorios para equipos remotos

References shared with Down suspension version. Please see previous page.
Referencias compartidas con versión suspension Down. Ver página anterior.



Surface Driver



Surface Rose



Recessed Rose


For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source / Para el dimensionado de la instalación mantener un margen de seguridad de un 15% de la potencia máxima de la fuente de alimentación LED.

• Can I feed a structure directly from a corner without using a feed unit profile?
Yes, corners are prepared to feed a structure in both directions without the need for a feed unit profile. Simply remember that you'll have to order the End cap profiles separately because they are not included in corners and intermediate profiles.
Take note that corners in Up&Down versions cannot be fed.

• Can I use a feed unit profile to feed a surface structure from the center?
Yes, to feed a surface structure from the center (in both directions), you'll need to use two feed unit profiles with two power supplies connected, one to each feed unit profile, or connect the same power supply to both feed unit profiles, respecting any potential electrical limitations. The mechanical connection can be made between profiles without any problem.


• ¿Puedo alimentar una estructura directamente desde una esquina sin utilizar un perfil de alimentación?
Sí, las esquinas están preparadas para alimentar una estructura en ambas direcciones sin la necesidad de utilizar un perfil de alimentación. Simplemente se ha de tener en cuenta que se deberán pedir por separado las tapas de los perfiles ya que no están incluidas en las esquinas y perfiles intermedios.
Las esquinas en la versión Up&Down no se pueden alimentar.


• ¿Puedo utilizar un perfil de alimentación para alimentar una estructura de superficie desde el centro?
Sí, para alimentar una estructura de superficie desde el centro (en ambas direcciones), se necesitarán dos perfiles de alimentación con dos fuentes de alimentación, una para cada perfil de alimentación, o la misma fuente de alimentación para ambos perfiles de alimentación, respetando las limitaciones eléctricas. La conexión mecánica entre los dos perfiles se puede realizar sin ningún problema.



• Can I cut a profile?
Yes, profiles can be cut to the desired length (except Up&Down version). Once a profile is cut, the electrical continuity is lost. If the cut element is not the one that closes the structure (in that case you don't need electrical continuity) the next section must to be fed with a corner or a feed unit profile.
If the cut side is at the end, the metallic end cap must be electrically insulated.

• ¿Puedo cortar un perfil?
Sí, los perfiles se pueden cortar a la medida deseada (excepto en la versión Up&Down). Una vez se corta un perfil se pierde la continuidad eléctrica. Si el perfil cortado no es el que cierra la estructura (en ese caso no se necesita continuidad eléctrica) el siguiente tramo se deberá volver a alimentar con una esquina o un perfil de alimentación.
Si el lado cortado es final, hay que aislar eléctricamente la tapa (end cap) metálica.






* Included with feed profiles or end caps /
Incluido en los perfiles de alimentación o end caps.

• Can I independently control the Up Light and the Down Light in the Up&Down version?
Yes, to control the Up Light and Down Light independently you just have to connect one power supply to the down electrical connector and another one to the up electrical connector. This allows you to manage the different light sources independently.
If you want to use a DALI Dimmable system for the Up Light and the Down Light, then the power supply connected to Up Light must be connected to a Dali controller (60.9678A).

• ¿Puedo controlar de manera independiente la iluminación directa e indirecta en la versión Up&Down?
Sí, para controlar la iluminación directa e indirecta de forma independiente simplemente se ha de conectar una fuente de alimentación a la conexión de iluminación indirecta y otra a la directa, permitiendo de esta forma controlar las diferentes fuentes de manera independiente.
Si se desea usar un sistema de regulación DALI, entonces la fuente de alimentación conectada a la iluminación indirecta tiene que conectarse a un controlador DALI (60.9678A).



• Can I independently control the luminaires installed in the structure with a DALI controller?
Yes, the DALI system will identify each luminaire installed in the profile with a unique address, and will allow you to independently manage each one.

• ¿Puedo controlar de manera independiente las luminarias instaladas en una estructura con un controlador DALI?
Sí, el sistema DALI identificará cada luminaria que se instale individualmente y permitirá su control de manera independiente.

• Do I need the Dimmable Dali controller 60.9678A to make the DALI structure?
The luminaries to be installed in the track are already equipped with Dali electronic, so a Dali controller is not required for these.
The 60.9678A DALI Controller is only required to make the Up indirect Light controllable with a DALI system in the Up&Down version.

• ¿Necesito la unidad de control dimmable DALI 60.9678A para hacer la estructura DALI?
Las luminarias ya van equipadas con electrónica DALI, por lo que la unidad de control DALI no será necesaria.
La unidad de control DALI 60.9678A solo será necesaria para controlar la iluminación indirecta con un sistema DALI en la versión Up&Down.

• What is the maximum distance allowed between the driver and the profile?
With the 200W power supply (60.9352) in our catalogue, the maximum distance allowed is:
. Ø 1.5 mm^2 cable: 2,5 m
. Ø 2.5 mm^2 cable: 4 m

• ¿Cuál es la distancia máxima permitida entre la fuente de alimentación y el perfil?
Con la fuente de alimentación de 200W (60.9352) de nuestro catálogo, la distancia máxima permitida es:
. Cable de Ø 1,5 mm^2 : 2,5 m
. Cable de Ø 2,5 mm^2 : 4 m

• What is the maximum length that can be fed with one power supply?
The maximum profile length that can be fed with a power supply is 8 m.

• ¿Cuál es la longitud máxima que se puede alimentar con una fuente de alimentación en una estructura?
La longitud máxima de un perfil que puede alimentarse con una fuente de alimentación es 8 m.


• Can I use a different, less powerful power supply?
All the information published on our website, and in our catalogue and installation instructions sheets is adjusted to the tests we perform with our 200W power supply (60.9352), which we recommend for our products.
However, a different power supply can be used to feed the profiles but the electrical limitations that it will have to accomplish should be taken into account.
It should be a 24V power supply with a maximum electric current of 8A.


• ¿Puedo utilizar una fuente de alimentación diferente - menos potente?
Toda la información publicada en nuestra web, catálogo e instrucciones de instalación se ajusta a los tests realizados con nuestra fuente de alimentación de 200W (60.9352) recomendada para nuestros productos.
De todas formas, se puede utilizar una fuente de alimentación diferente para alimentar los perfiles, pero teniendo en cuenta las limitaciones eléctricas que debe cumplir.
Debe ser una fuente de alimentación de 24V con una corriente eléctrica máxima de 8A.

Light Stripe

Top LED 25W/m - 2060 lm/m - 2700K/CRI 90 / 25W/m - 2178 lm/m - 3000K/CRI 90








Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included. For wireless lighting control, choose integrated Casambi versions.

Módulo de iluminación LED de luz difusa para ser instalado en el sistema The Running Magnet. Tapas opalinas para crear líneas de luz continuas incluidas. Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.


2700K
L: 300 mm - 7,5W - 618lm
On board dimmer
03.7000.14
Dali 2
03.7000.14ADA
**Casambi Integrated
03.7000.14.CB



Luminous flux luminaire
416 lm

Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	149	2.76
2	37	5.52
3	17	8.28
4	9	11.04
5	6	13.81


3000K
L: 300 mm - 7,5W - 653lm
On board dimmer
03.7001.14
Dali 2
03.7001.14ADA
**Casambi Integrated
03.7001.14.CB



Luminous flux luminaire
440 lm

Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	158	2.76
2	39	5.52
3	18	8.28
4	10	11.04
5	6	13.81


2700K
L: 600 mm - 15W - 1237lm
On board dimmer
03.7002.14
Dali 2
03.7002.14ADA
**Casambi Integrated
03.7002.14.CB



Luminous flux luminaire
833 lm

Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	298	2.76
2	75	5.52
3	33	8.28
4	19	11.04
5	12	13.81


3000K
L: 600 mm - 15W - 1307lm
On board dimmer
03.7003.14
Dali 2
03.7003.14ADA
**Casambi Integrated
03.7003.14.CB



Luminous flux luminaire
880 lm

Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	315	2.76
2	79	5.52
3	35	8.28
4	20	11.04
5	13	13.81


2700K
On board dimmer
L: 900 mm - 22,5W - 1855lm
03.7004.14
Dali 2
03.7004.14ADA
**Casambi Integrated
03.7004.14.CB



Luminous flux luminaire
1249 lm

Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	447	2.76
2	112	5.52
3	50	8.28
4	28	11.04
5	18	13.81


3000K
On board dimmer
L: 900 mm - 22,5W - 1960lm
03.7005.14
Dali 2
03.7005.14ADA
**Casambi Integrated
03.7005.14.CB



Luminous flux luminaire
1320 lm

Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	473	2.76
2	118	5.52
3	53	8.28
4	30	11.04
5	19	13.81


2700K
On board dimmer
L: 1200 mm - 30W - 2473lm
03.7006.14
Dali 2
03.7006.14ADA
**Casambi Integrated
03.7006.14.CB



Luminous flux luminaire
1665 lm

Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	596	2.76
2	149	5.52
3	66	8.28
4	37	11.04
5	24	13.81

3000K
On board dimmer
L: 1200 mm - 30W - 2614lm
03.7007.14
Dali 2
03.7007.14ADA
**Casambi Integrated
03.7007.14.CB



Luminous flux luminaire
1760 lm


Beam Angle: 105°		
h(m)	E(lx)	D(m)
1	630	2.76
2	158	5.52
3	70	8.28
4	39	11.04
5	25	13.81


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Light Shadow Spot 30

Power LED 4W - 298 lm - 2700K/CRI 90 / 4W - 318 lm - 3000K/CRI 90







LED accent lighting module for installation in The Running Magnet system.
For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema The Running Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Spot - 2700K


On board dimmer
- 05.9100.40A
- 05.9100.14A
- 05.9100.ERA
- 05.9100.ESA

Dali 2
- 05.9100.40ADA
- 05.9100.14ADA
- 05.9100.ERADA
- 05.9100.ESADA

1-10V
- 05.9100.40A1V
- 05.9100.14A1V
- 05.9100.ERA1V
- 05.9100.ESA1V

Casambi integrated
- 05.9100.40ACB
- 05.9100.14ACB
- 05.9100.ERACB
- 05.9100.ESACB





Luminous flux luminaire 253 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4044	0.20
2	1011	0.40
3	449	0.60
4	253	0.80
5	162	1.00

Optic Spot - 3000K


On board dimmer
- 05.9105.40A
- 05.9105.14A
- 05.9105.ERA
- 05.9105.ESA

Dali 2
- 05.9105.40ADA
- 05.9105.14ADA
- 05.9105.ERADA
- 05.9105.ESADA

1-10V
- 05.9105.40A1V
- 05.9105.14A1V
- 05.9105.ERA1V
- 05.9105.ESA1V

Casambi integrated
- 05.9105.40ACB
- 05.9105.14ACB
- 05.9105.ERACB
- 05.9105.ESACB





Luminous flux luminaire 270 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4316	0.20
2	1079	0.40
3	480	0.60
4	270	0.80
5	173	1.00

Optic Medium - 2700K


On board dimmer
- 05.9101.40A
- 05.9101.14A
- 05.9101.ERA
- 05.9101.ESA

Dali 2
- 05.9101.40ADA
- 05.9101.14ADA
- 05.9101.ERADA
- 05.9101.ESADA

1-10V
- 05.9101.40A1V
- 05.9101.14A1V
- 05.9101.ERA1V
- 05.9101.ESA1V

Casambi integrated
- 05.9101.40ACB
- 05.9101.14ACB
- 05.9101.ERACB
- 05.9101.ESACB





Luminous flux luminaire 257 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1797	0.39
2	449	0.78
3	200	1.17
4	112	1.56
5	72	1.95

Optic Medium - 3000K


On board dimmer
- 05.9106.40A
- 05.9106.14A
- 05.9106.ERA
- 05.9106.ESA

Dali 2
- 05.9106.40ADA
- 05.9106.14ADA
- 05.9106.ERADA
- 05.9106.ESADA

1-10V
- 05.9106.40A1V
- 05.9106.14A1V
- 05.9106.ERA1V
- 05.9106.ESA1V

Casambi integrated
- 05.9106.40ACB
- 05.9106.14ACB
- 05.9106.ERACB
- 05.9106.ESACB





Luminous flux luminaire 274 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1916	0.39
2	479	0.78
3	213	1.17
4	120	1.56
5	77	1.95

Optic Flood - 2700K

On board dimmer

- 05.9102.40A
- 05.9102.14A
- 05.9102.ERA
- 05.9102.ESA

Dali 2

- 05.9102.40ADA
- 05.9102.14ADA
- 05.9102.ERADA
- 05.9102.ESADA


1-10V

- 05.9102.40A1V
- 05.9102.14A1V
- 05.9102.ERA1V
- 05.9102.ESA1V

Casambi integrated

- 05.9102.40ACB
- 05.9102.14ACB
- 05.9102.ERACB
- 05.9102.ESACB





Luminous flux luminaire
246 lm

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	953	0.52
2	238	1.04
3	106	1.57
4	60	2.09
5	38	2.61

Optic Flood - 3000K

On board dimmer

- 05.9107.40A
- 05.9107.14A
- 05.9107.ERA
- 05.9107.ESA

Dali 2

- 05.9107.40ADA
- 05.9107.14ADA
- 05.9107.ERADA
- 05.9107.ESADA


1-10V

- 05.9107.40A1V
- 05.9107.14A1V
- 05.9107.ERA1V
- 05.9107.ESA1V

Casambi integrated

- 05.9107.40ACB
- 05.9107.14ACB
- 05.9107.ERACB
- 05.9107.ESACB





Luminous flux luminaire
263 lm

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	1019	0.52
2	255	1.04
3	113	1.57
4	64	2.09
5	41	2.61

Optic Wide Flood - 2700K

On board dimmer

- 05.9103.40A
- 05.9103.14A
- 05.9103.ERA
- 05.9103.ESA

Dali 2

- 05.9103.40ADA
- 05.9103.14ADA
- 05.9103.ERADA
- 05.9103.ESADA


1-10V

- 05.9103.40A1V
- 05.9103.14A1V
- 05.9103.ERA1V
- 05.9103.ESA1V

Casambi integrated

- 05.9103.40ACB
- 05.9103.14ACB
- 05.9103.ERACB
- 05.9103.ESACB





Luminous flux luminaire
246 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	524	0.80
2	131	1.59
3	58	2.39
4	33	3.19
5	21	3.99

Optic Wide Flood - 3000K

On board dimmer

- 05.9108.40A
- 05.9108.14A
- 05.9108.ERA
- 05.9108.ESA

Dali 2

- 05.9108.40ADA
- 05.9108.14ADA
- 05.9108.ERADA
- 05.9108.ESADA


1-10V

- 05.9108.40A1V
- 05.9108.14A1V
- 05.9108.ERA1V
- 05.9108.ESA1V

Casambi integrated

- 05.9108.40ACB
- 05.9108.14ACB
- 05.9108.ERACB
- 05.9108.ESACB





Luminous flux luminaire
262 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	559	0.80
2	140	1.59
3	62	2.39
4	35	3.19
5	22	3.99

Accessories / Accesorios


Light Shadow Spot 30


Honeycomb	Panel de abeja		08.0790.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0791.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0792.00

Light Shadow Spot 45

LED Array 10W - 756 lm - 2700K/CRI 90 / 10W - 799 lm - 3000K/CRI 90







LED accent lighting module for installation in The Running Magnet system.
For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema The Running Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).


Optic Spot - 2700K

On board dimmer
- 05.9130.40
- 05.9130.14
- 05.9130.ER
- 05.9130.ES

Dali 2
- 05.9130.40.DA
- 05.9130.14.DA
- 05.9130.ER.DA
- 05.9130.ES.DA

1-10V
- 05.9130.40.1V
- 05.9130.14.1V
- 05.9130.ER.1V
- 05.9130.ES.1V

Casambi integrated
- 05.9130.40.CB
- 05.9130.14.CB
- 05.9130.ER.CB
- 05.9130.ES.CB



Luminous flux luminaire 650 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8012	0.27
2	2003	0.54
3	890	0.80
4	501	1.07
5	320	1.34


Optic Spot - 3000K

On board dimmer
- 05.9135.40
- 05.9135.14
- 05.9135.ER
- 05.9135.ES

Dali 2
- 05.9135.40.DA
- 05.9135.14.DA
- 05.9135.ER.DA
- 05.9135.ES.DA

1-10V
- 05.9135.40.1V
- 05.9135.14.1V
- 05.9135.ER.1V
- 05.9135.ES.1V

Casambi integrated
- 05.9135.40.CB
- 05.9135.14.CB
- 05.9135.ER.CB
- 05.9135.ES.CB



Luminous flux luminaire 650 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8012	0.27
2	2003	0.54
3	890	0.80
4	501	1.07
5	320	1.34


Optic Medium - 2700K

On board dimmer
- 05.9131.40
- 05.9131.14
- 05.9131.ER
- 05.9131.ES

Dali 2
- 05.9131.40.DA
- 05.9131.14.DA
- 05.9131.ER.DA
- 05.9131.ES.DA

1-10V
- 05.9131.40.1V
- 05.9131.14.1V
- 05.9131.ER.1V
- 05.9131.ES.1V

Casambi integrated
- 05.9131.40.CB
- 05.9131.14.CB
- 05.9131.ER.CB
- 05.9131.ES.CB



Luminous flux luminaire 645 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5163	0.36
2	1291	0.73
3	574	1.09
4	323	1.46
5	207	1.82


Optic Medium - 3000K

On board dimmer
- 05.9136.40
- 05.9136.14
- 05.9136.ER
- 05.9136.ES

Dali 2
- 05.9136.40.DA
- 05.9136.14.DA
- 05.9136.ER.DA
- 05.9136.ES.DA

1-10V
- 05.9136.40.1V
- 05.9136.14.1V
- 05.9136.ER.1V
- 05.9136.ES.1V

Casambi integrated
- 05.9136.40.CB
- 05.9136.14.CB
- 05.9136.ER.CB
- 05.9136.ES.CB



Luminous flux luminaire 645 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5163	0.36
2	1291	0.73
3	574	1.09
4	323	1.46
5	207	1.82

Optic Flood - 2700K

On board dimmer

- 05.9132.40
- 05.9132.14
- 05.9132.ER
- 05.9132.ES

Dali 2

- 05.9132.40.DA
- 05.9132.14.DA
- 05.9132.ER.DA
- 05.9132.ES.DA


1-10V

- 05.9132.40.1V
- 05.9132.14.1V
- 05.9132.ER.1V
- 05.9132.ES.1V

Casambi integrated

- 05.9132.40.CB
- 05.9132.14.CB
- 05.9132.ER.CB
- 05.9132.ES.CB





Luminous flux luminaire 646 lm

Beam Angle:	31°
h(m)	E(lx) D(m)
1	2296 0.56
2	574 1.11
3	255 1.67
4	144 2.22
5	92 2.78

Optic Flood - 3000K

On board dimmer

- 05.9137.40
- 05.9137.14
- 05.9137.ER
- 05.9137.ES

Dali 2

- 05.9137.40.DA
- 05.9137.14.DA
- 05.9137.ER.DA
- 05.9137.ES.DA


1-10V

- 05.9137.40.1V
- 05.9137.14.1V
- 05.9137.ER.1V
- 05.9137.ES.1V

Casambi integrated

- 05.9137.40.CB
- 05.9137.14.CB
- 05.9137.ER.CB
- 05.9137.ES.CB





Luminous flux luminaire 646 lm

Beam Angle:	31°
h(m)	E(lx) D(m)
1	2296 0.56
2	574 1.11
3	255 1.67
4	144 2.22
5	92 2.78

Accessories / Accesorios


Light Shadow Spot 45


Honeycomb	Panel de abeja		08.0793.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0794.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0795.00

Spot Module

Power LED 8W - 560 lm - 2700K/CRI 90 / 8W - 600 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.
For wireless lighting control, choose integrated Casambi versions.

Spot Module No DALI:
Maximum 21 spots for a single driver.
Spot Module DALI:
Maximum 14 spots for a single driver.

Maximum 64 spots for a single DALI controller.

See available accessories.


Módulo de iluminación LED de acento para ser instalado en el sistema The Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.

Spot Module No DALI:
Máximo 21 spots para un mismo driver.
Spot Module DALI:
Máximo 14 spots para un mismo driver.

Máximo 64 spots para un mismo controlador DALI.

Ver accesorios disponibles.

2700K
On board dimmer
03.6303.14B
Dali 2
03.6303.14CDA
**Casambi Integrated
03.6303.14BCB




Luminous flux luminaire
403 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5763	0.24
2	1441	0.49
3	640	0.73
4	360	0.98
5	231	1.22

3000K
On board dimmer
03.6302.14B
Dali 2
03.6302.14CDA
**Casambi Integrated
03.6302.14BCB



Luminous flux luminaire
418 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5973	0.24
2	1493	0.49
3	664	0.73
4	373	0.98
5	239	1.22

Accessories / Accesorios

Spot Module

Screening external ring for Running Magnet spot module in aluminium with a black finish to enhance the visual comfort.

Aro exterior apantallador para spot module Running Magnet realizado en aluminio y acabado en negro, para un incremento del confort visual.




08.8427.14


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Spot 120

Power LED 13W - 1003 lm - 2700K/CRI 90 / 1002 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.
For wireless lighting control, choose integrated Casambi versions.

Spot Module No DALI 2:
Maximum 14 spots for a single driver.
Spot Module DALI 2:
Maximum 11 spots for a single driver.

Accessories included (honeycomb and screening crosspiece).

Módulo de iluminación LED de acento para ser instalado en el sistema The Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.

Spot Module No DALI 2:
Máximo 14 spots para un mismo driver.
Spot Module DALI 2:
Máximo 11 spots para un mismo driver.


Accesorios incluidos (honeycomb y cruceta de apantallamiento).

2700K
On board dimmer
- ☐ 03.6285.40C
- ■ 03.6285.14C

Dali 2
- ☐ 03.6285.40CDA
- ■ 03.6285.14CDA

**Casambi Integrated
- ☐ 03.6285.40CCB
- ■ 03.6285.14CCB

16° SPOT



Luminous flux luminaire
773 lm


Beam Angle:		16°
h(m)	E(lx)	D(m)
1	7301	0.28
2	1825	0.57
3	811	0.85
4	456	1.14
5	292	1.42

3000K
On board dimmer
- ☐ 03.6284.40C
- ■ 03.6284.14C

Dali 2
- ☐ 03.6284.40CDA
- ■ 03.6284.14CDA

**Casambi Integrated
- ☐ 03.6284.40CCB
- ■ 03.6284.14CCB

16° SPOT



Luminous flux luminaire
851 lm


Beam Angle:		16°
h(m)	E(lx)	D(m)
1	8038	0.28
2	2009	0.57
3	893	0.85
4	502	1.14
5	322	1.42

2700K
On board dimmer
- ☐ 03.6286.40C
- ■ 03.6286.14C

Dali 2
- ☐ 03.6286.40CDA
- ■ 03.6286.14CDA

**Casambi Integrated
- ☐ 03.6286.40CCB
- ■ 03.6286.14CCB

32° MEDIUM



Luminous flux luminaire
448 lm


Beam Angle:		32°
h(m)	E(lx)	D(m)
1	1494	0.57
2	374	1.14
3	166	1.71
4	93	2.27
5	60	2.84

3000K
On board dimmer
- ☐ 03.6287.40C
- ■ 03.6287.14C

Dali 2
- ☐ 03.6287.40CDA
- ■ 03.6287.14CDA

**Casambi Integrated
- ☐ 03.6287.40CCB
- ■ 03.6287.14CCB

32° MEDIUM



Luminous flux luminaire
493 lm


Beam Angle:		32°
h(m)	E(lx)	D(m)
1	1644	0.57
2	411	1.14
3	183	1.71
4	103	2.27
5	66	2.84


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Anthony Spot Track By Antonio Citterio

Power LED 14W - 1045 lm - 2700K/CRI 90 / 14W - 1308 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.
For wireless lighting control, choose integrated Casambi versions.

Spot Module No DALI:
Maximum 9 spots for a single driver.

See available accessories.

Módulo de iluminación LED de acento para ser instalado en el sistema The Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.


Spot Module No DALI:
Máximo 9 spots para un mismo driver.

Ver accesorios disponibles.

2700K
On board dimmer
- 03.6277.40B
- 03.6277.14B

Dali 2
- 03.6277.40BDA
- 03.6277.14BDA

**Casambi Integrated
- 03.6277.40BCB
- 03.6277.14BCB



Luminous flux luminaire
847 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	9404	0.27
2	2351	0.54
3	1045	0.81
4	588	1.08
5	376	1.35

3000K
On board dimmer
- 03.6274.40B
- 03.6274.14B

Dali 2
- 03.6274.40BDA
- 03.6274.14BDA

**Casambi Integrated
- 03.6274.40BCB
- 03.6274.14BCB



Luminous flux luminaire
1060 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	11765	0.27
2	2941	0.54
3	1307	0.81
4	735	1.08
5	471	1.35

2700K
On board dimmer
- 03.6278.40B
- 03.6278.14B

Dali 2
- 03.6278.40BDA
- 03.6278.14BDA

**Casambi Integrated
- 03.6278.40BCB
- 03.6278.14BCB



Luminous flux luminaire
870 lm


Beam Angle: 23°

h(m)	E(lx)	D(m)
1	4534	0.40
2	1134	0.81
3	504	1.21
4	283	1.61
5	181	2.02

3000K
On board dimmer
- 03.6275.40B
- 03.6275.14B

Dali 2
- 03.6275.40BDA
- 03.6275.14BDA

**Casambi Integrated
- 03.6275.40BCB
- 03.6275.14BCB



Luminous flux luminaire
1087 lm

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	5664	0.40
2	1416	0.81
3	629	1.21
4	354	1.61
5	227	2.02

** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Accessories / Accesorios


Anthony Spot Track


Elliptical lens.	Lente elíptica.		08.8418.68A
Honeycomb.	Honeycomb.		08.8419.14A
Flood lens. To obtain flood optics (35º) order Anthony Spot Medium + flood lens.	Lente flood. Para alcanzar óptica flood (35º) pedir Anthony Spot Medium + lente flood.		08.0050.00

Workmates Small

Top LED High Efficiency
Non Dimming / 1-10V: 10W - 1382 lm - 3000K/CRI 90 / 1416 lm - 3500K/CRI 90 / 1440 lm - 4000K/CRI 90
Dali 2 / Casambi: 10,5W - 1382 lm - 3000K/CRI 90 / 1416 lm - 3500K/CRI 90 / 1440 lm - 4000K/CRI 90







Luminaire for use on The Running Magnet system. High-efficiency light source. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant. Casambi, máximum distance between fixtures: 50m.

Luminaria para aplicación en el sistema The Running Magnet. Fuente de luz de alta eficiencia. Sobre el eje de su brazo trasero, puede girar 360° para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65°<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K


Non Dimming
- 05.6420.40
- 05.6420.40.78
- 05.6420.14
- 05.6420.AP

Dali 2
- 05.6420.40.DA
- 05.6420.40.YU
- 05.6420.14.DA
- 05.6420.AP.DA

1-10V
- 05.6420.40.1V
- 05.6420.40.RX
- 05.6420.14.1V
- 05.6420.AP.1V

Casambi
- 05.6420.40.CB
- 05.6420.40.C6
- 05.6420.14.CB
- 05.6420.AP.CB





Luminous flux luminaire
1022 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	661	1.55
2	165	3.10
3	73	4.66
4	41	6.21
5	26	7.76

Optic Wide Flood - 4000K


Non Dimming
- 05.6422.40
- 05.6422.40.78
- 05.6422.14
- 05.6422.AP

Dali 2
- 05.6422.40.DA
- 05.6422.40.YU
- 05.6422.14.DA
- 05.6422.AP.DA

1-10V
- 05.6422.40.1V
- 05.6422.40.RX
- 05.6422.14.1V
- 05.6422.AP.1V

Casambi
- 05.6422.40.CB
- 05.6422.40.C6
- 05.6422.14.CB
- 05.6422.AP.CB





Luminous flux luminaire
1046 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	676	1.55
2	169	3.10
3	75	4.66
4	42	6.21
5	27	7.76

Optic Wide Flood - 3500K


Non Dimming
- 05.6421.40
- 05.6421.40.78
- 05.6421.14
- 05.6421.AP

Dali 2
- 05.6421.40.DA
- 05.6421.40.YU
- 05.6421.14.DA
- 05.6421.AP.DA

1-10V
- 05.6421.40.1V
- 05.6421.40.RX
- 05.6421.14.1V
- 05.6421.AP.1V

Casambi
- 05.6421.40.CB
- 05.6421.40.C6
- 05.6421.14.CB
- 05.6421.AP.CB





Luminous flux luminaire
1031 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	666	1.55
2	167	3.10
3	74	4.66
4	42	6.21
5	27	7.76

NEW

Optic Oval - 3000K

Non Dimming

- 05.6425.40
- 05.6425.40.78
- 05.6425.14
- 05.6425.AP

Dali 2

- 05.6425.40.DA
- 05.6425.40.YU
- 05.6425.14.DA
- 05.6425.AP.DA


1-10V

- 05.6425.40.1V
- 05.6425.40.RX
- 05.6425.14.1V
- 05.6425.AP.1V

Casambi

- 05.6425.40.CB
- 05.6425.40.C6
- 05.6425.14.CB
- 05.6425.AP.CB

72° OVAL



Luminous flux luminaire
994 lm

Beam Angle:		72°
h(m)	E(lx)	D(m)
1	633	1.45
2	158	2.89
3	70	4.34
4	40	5.78
5	25	7.23

Optic High Comfort - 3000K

Non Dimming

- 05.5920.40
- 05.5920.40.78
- 05.5920.14
- 05.5920.AP

Dali 2

- 05.5920.40.DA
- 05.5920.40.YU
- 05.5920.14.DA
- 05.5920.AP.DA


1-10V

- 05.5920.40.1V
- 05.5920.40.RX
- 05.5920.14.1V
- 05.5920.AP.1V

Casambi

- 05.5920.40.CB
- 05.5920.40.C6
- 05.5920.14.CB
- 05.5920.AP.CB

66° HIGH COMFORT



Luminous flux luminaire
1104 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1062	1.31
2	266	2.61
3	118	3.92
4	66	5.23
5	42	6.54

Optic Oval - 3500K

Non Dimming

- 05.6426.40
- 05.6426.40.78
- 05.6426.14
- 05.6426.AP

Dali 2

- 05.6426.40.DA
- 05.6426.40.YU
- 05.6426.14.DA
- 05.6426.AP.DA


1-10V

- 05.6426.40.1V
- 05.6426.40.RX
- 05.6426.14.1V
- 05.6426.AP.1V

Casambi

- 05.6426.40.CB
- 05.6426.40.C6
- 05.6426.14.CB
- 05.6426.AP.CB

72° OVAL



Luminous flux luminaire
1003 lm

Beam Angle:		72°
h(m)	E(lx)	D(m)
1	639	1.45
2	160	2.89
3	71	4.34
4	40	5.78
5	26	7.23

Optic High Comfort - 3500K

Non Dimming

- 05.5921.40
- 05.5921.40.78
- 05.5921.14
- 05.5921.AP

Dali 2

- 05.5921.40.DA
- 05.5921.40.YU
- 05.5921.14.DA
- 05.5921.AP.DA


1-10V

- 05.5921.40.1V
- 05.5921.40.RX
- 05.5921.14.1V
- 05.5921.AP.1V

Casambi

- 05.5921.40.CB
- 05.5921.40.C6
- 05.5921.14.CB
- 05.5921.AP.CB

66° HIGH COMFORT



Luminous flux luminaire
1115 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1073	1.31
2	268	2.61
3	119	3.92
4	67	5.23
5	43	6.54

Optic Oval - 4000K

Non Dimming

- 05.6427.40
- 05.6427.40.78
- 05.6427.14
- 05.6427.AP

Dali 2

- 05.6427.40.DA
- 05.6427.40.YU
- 05.6427.14.DA
- 05.6427.AP.DA


1-10V

- 05.6427.40.1V
- 05.6427.40.RX
- 05.6427.14.1V
- 05.6427.AP.1V

Casambi

- 05.6427.40.CB
- 05.6427.40.C6
- 05.6427.14.CB
- 05.6427.AP.CB

72° OVAL



Luminous flux luminaire
1017 lm

Beam Angle:		72°
h(m)	E(lx)	D(m)
1	648	1.45
2	162	2.89
3	72	4.34
4	40	5.78
5	26	7.23

Optic High Comfort - 4000K

Non Dimming

- 05.5922.40
- 05.5922.40.78
- 05.5922.14
- 05.5922.AP

Dali 2

- 05.5922.40.DA
- 05.5922.40.YU
- 05.5922.14.DA
- 05.5922.AP.DA


1-10V

- 05.5922.40.1V
- 05.5922.40.RX
- 05.5922.14.1V
- 05.5922.AP.1V

Casambi

- 05.5922.40.CB
- 05.5922.40.C6
- 05.5922.14.CB
- 05.5922.AP.CB

66° HIGH COMFORT




Luminous flux luminaire
1133 lm


Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1090	1.31
2	272	2.61
3	121	3.92
4	68	5.23
5	44	6.54

Workmates Small

Top LED Full Spectrum
Non Dimming / 1-10V: 10W - 1013 lm - 3000K/CRI 98 / 1021 lm - 3500K/CRI 98 / 1032 lm - 4000K/CRI 98
Dali 2 / Casambi: 10,5W - 1013 lm - 3000K/CRI 98 / 1021 lm - 3500K/CRI 98 / 1032 lm - 4000K/CRI 98







Luminaire for use on The Running Magnet system. High-quality colour rendering Full Spectrum light source. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, máximum distance between fixtures: 50m.

Luminaria para aplicación en el sistema The Running Magnet. Fuente de luz Full Spectrum de alta calidad en la reproducción cromática. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.


Optic Wide Flood - 3000K

Non Dimming
- 05.6430.40
- 05.6430.40.78
- 05.6430.14
- 05.6430.AP

Dali 2
- 05.6430.40.DA
- 05.6430.40.YU
- 05.6430.14.DA
- 05.6430.AP.DA

1-10V
- 05.6430.40.1V
- 05.6430.40.RX
- 05.6430.14.1V
- 05.6430.AP.1V

Casambi
- 05.6430.40.CB
- 05.6430.40.C6
- 05.6430.14.CB
- 05.6430.AP.CB



Luminous flux luminaire
758 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	490	1.55
2	122	3.10
3	54	4.66
4	31	6.21
5	20	7.76


Optic Wide Flood - 4000K

Non Dimming
- 05.6432.40
- 05.6432.40.78
- 05.6432.14
- 05.6432.AP

Dali 2
- 05.6432.40.DA
- 05.6432.40.YU
- 05.6432.14.DA
- 05.6432.AP.DA

1-10V
- 05.6432.40.1V
- 05.6432.40.RX
- 05.6432.14.1V
- 05.6432.AP.1V

Casambi
- 05.6432.40.CB
- 05.6432.40.C6
- 05.6432.14.CB
- 05.6432.AP.CB



Luminous flux luminaire
771 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	498	1.55
2	125	3.10
3	55	4.66
4	31	6.21
5	20	7.76


Optic Wide Flood - 3500K

Non Dimming
- 05.6431.40
- 05.6431.40.78
- 05.6431.14
- 05.6431.AP

Dali 2
- 05.6431.40.DA
- 05.6431.40.YU
- 05.6431.14.DA
- 05.6431.AP.DA

1-10V
- 05.6431.40.1V
- 05.6431.40.RX
- 05.6431.14.1V
- 05.6431.AP.1V

Casambi
- 05.6431.40.CB
- 05.6431.40.C6
- 05.6431.14.CB
- 05.6431.AP.CB



Luminous flux luminaire
764 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	494	1.55
2	123	3.10
3	55	4.66
4	31	6.21
5	20	7.76

NEW

Optic Oval - 3000K

Non Dimming

- 05.6435.40
- 05.6435.40.78
- 05.6435.14
- 05.6435.AP

Dali 2

- 05.6435.40.DA
- 05.6435.40.YU
- 05.6435.14.DA
- 05.6435.AP.DA


1-10V

- 05.6435.40.1V
- 05.6435.40.RX
- 05.6435.14.1V
- 05.6435.AP.1V

Casambi

- 05.6435.40.CB
- 05.6435.40.C6
- 05.6435.14.CB
- 05.6435.AP.CB

72° OVAL



Luminous flux luminaire
737 lm

Beam Angle:	72°
h(m)	E(lx) D(m)
1	469 1.45
2	117 2.89
3	52 4.34
4	29 5.78
5	19 7.23

Optic High Comfort - 3000K

Non Dimming

- 05.5930.40
- 05.5930.40.78
- 05.5930.14
- 05.5930.AP

Dali 2

- 05.5930.40.DA
- 05.5930.40.YU
- 05.5930.14.DA
- 05.5930.AP.DA


1-10V

- 05.5930.40.1V
- 05.5930.40.RX
- 05.5930.14.1V
- 05.5930.AP.1V

Casambi

- 05.5930.40.CB
- 05.5930.40.C6
- 05.5930.14.CB
- 05.5930.AP.CB

66° HIGH COMFORT



Luminous flux luminaire
840 lm

Beam Angle:	66°
h(m)	E(lx) D(m)
1	808 1.31
2	202 2.61
3	90 3.92
4	51 5.23
5	32 6.54

Optic Oval - 3500K

Non Dimming

- 05.6436.40
- 05.6436.40.78
- 05.6436.14
- 05.6436.AP

Dali 2

- 05.6436.40.DA
- 05.6436.40.YU
- 05.6436.14.DA
- 05.6436.AP.DA


1-10V

- 05.6436.40.1V
- 05.6436.40.RX
- 05.6436.14.1V
- 05.6436.AP.1V

Casambi

- 05.6436.40.CB
- 05.6436.40.C6
- 05.6436.14.CB
- 05.6436.AP.CB

72° OVAL



Luminous flux luminaire
743 lm

Beam Angle:	72°
h(m)	E(lx) D(m)
1	473 1.45
2	118 2.89
3	53 4.34
4	30 5.78
5	19 7.23

Optic High Comfort - 3500K

Non Dimming

- 05.5931.40
- 05.5931.40.78
- 05.5931.14
- 05.5931.AP

Dali 2

- 05.5931.40.DA
- 05.5931.40.YU
- 05.5931.14.DA
- 05.5931.AP.DA


1-10V

- 05.5931.40.1V
- 05.5931.40.RX
- 05.5931.14.1V
- 05.5931.AP.1V

Casambi

- 05.5931.40.CB
- 05.5931.40.C6
- 05.5931.14.CB
- 05.5931.AP.CB

66° HIGH COMFORT



Luminous flux luminaire
851 lm

Beam Angle:	66°
h(m)	E(lx) D(m)
1	819 1.31
2	205 2.61
3	91 3.92
4	51 5.23
5	33 6.54

Optic Oval - 4000K

Non Dimming

- 05.6437.40
- 05.6437.40.78
- 05.6437.14
- 05.6437.AP

Dali 2

- 05.6437.40.DA
- 05.6437.40.YU
- 05.6437.14.DA
- 05.6437.AP.DA


1-10V

- 05.6437.40.1V
- 05.6437.40.RX
- 05.6437.14.1V
- 05.6437.AP.1V

Casambi

- 05.6437.40.CB
- 05.6437.40.C6
- 05.6437.14.CB
- 05.6437.AP.CB

72° OVAL



Luminous flux luminaire
750 lm

Beam Angle:	72°
h(m)	E(lx) D(m)
1	478 1.45
2	119 2.89
3	53 4.34
4	30 5.78
5	19 7.23

Optic High Comfort - 4000K

Non Dimming

- 05.5932.40
- 05.5932.40.78
- 05.5932.14
- 05.5932.AP

Dali 2

- 05.5932.40.DA
- 05.5932.40.YU
- 05.5932.14.DA
- 05.5932.AP.DA


1-10V

- 05.5932.40.1V
- 05.5932.40.RX
- 05.5932.14.1V
- 05.5932.AP.1V

Casambi

- 05.5932.40.CB
- 05.5932.40.C6
- 05.5932.14.CB
- 05.5932.AP.CB

66° HIGH COMFORT




Luminous flux luminaire
869 lm


Beam Angle:	66°
h(m)	E(lx) D(m)
1	836 1.31
2	209 2.61
3	93 3.92
4	52 5.23
5	33 6.54

Workmates Large

Top LED High Efficiency
Non Dimming / 1-10V: 12,5W - 1853 lm - 3000K/CRI 90 / 1886 lm - 3500K/CRI 90 / 1896 lm - 4000K/CRI 90
Dali 2 / Casambi: 13,5W - 1853 lm - 3000K/CRI 90 / 1886 lm - 3500K/CRI 90 / 1896 lm - 4000K/CRI 90







Luminaire for use on The Running Magnet system. High-efficiency light source. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant. Casambi, máximum distance between fixtures: 50m.

Luminaria para aplicación en el sistema The Running Magnet. Fuente de luz de alta eficiencia. Sobre el eje de su brazo trasero, puede girar 360° para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65°<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K


Non Dimming
- 05.6440.40
- 05.6440.40.78
- 05.6440.14
- 05.6440.AP

Dali 2
- 05.6440.40.DA
- 05.6440.40.YU
- 05.6440.14.DA
- 05.6440.AP.DA

1-10V
- 05.6440.40.1V
- 05.6440.40.RX
- 05.6440.14.1V
- 05.6440.AP.1V

Casambi
- 05.6440.40.CB
- 05.6440.40.C6
- 05.6440.14.CB
- 05.6440.AP.CB





Luminous flux luminaire
1411 lm

Beam Angle:	74°	
h(m)	E(lx)	D(m)
1	893	1.50
2	223	3.00
3	99	4.51
4	56	6.01
5	36	7.51

Optic Wide Flood - 4000K


Non Dimming
- 05.6442.40
- 05.6442.40.78
- 05.6442.14
- 05.6442.AP

Dali 2
- 05.6442.40.DA
- 05.6442.40.YU
- 05.6442.14.DA
- 05.6442.AP.DA

1-10V
- 05.6442.40.1V
- 05.6442.40.RX
- 05.6442.14.1V
- 05.6442.AP.1V

Casambi
- 05.6442.40.CB
- 05.6442.40.C6
- 05.6442.14.CB
- 05.6442.AP.CB





Luminous flux luminaire
1453 lm

Beam Angle:	74°	
h(m)	E(lx)	D(m)
1	920	1.50
2	230	3.00
3	102	4.51
4	57	6.01
5	37	7.51

Optic Wide Flood - 3500K


Non Dimming
- 05.6441.40
- 05.6441.40.78
- 05.6441.14
- 05.6441.AP

Dali 2
- 05.6441.40.DA
- 05.6441.40.YU
- 05.6441.14.DA
- 05.6441.AP.DA

1-10V
- 05.6441.40.1V
- 05.6441.40.RX
- 05.6441.14.1V
- 05.6441.AP.1V

Casambi
- 05.6441.40.CB
- 05.6441.40.C6
- 05.6441.14.CB
- 05.6441.AP.CB





Luminous flux luminaire
1432 lm

Beam Angle:	74°	
h(m)	E(lx)	D(m)
1	906	1.50
2	227	3.00
3	101	4.51
4	57	6.01
5	36	7.51

NEW

Optic Oval - 3000K

Non Dimming

05.6445.40
05.6445.40.78
05.6445.14
05.6445.AP

Dali 2

05.6445.40.DA
05.6445.40.YU
05.6445.14.DA
05.6445.AP.DA


1-10V

05.6445.40.1V
05.6445.40.RX
05.6445.14.1V
05.6445.AP.1V

Casambi

05.6445.40.CB
05.6445.40.C6
05.6445.14.CB
05.6445.AP.CB

72°
OVAL



Luminous flux luminaire
1396 lm

Beam Angle:	72°
h(m)	E(lx)	D(m)
1	894	1.45
2	224	2.89
3	99	4.34
4	56	5.79
5	36	7.23

Optic High Comfort - 3000K

Non Dimming

05.5940.40
05.5940.40.78
05.5940.14
05.5940.AP

Dali 2

05.5940.40.DA
05.5940.40.YU
05.5940.14.DA
05.5940.AP.DA


1-10V

05.5940.40.1V
05.5940.40.RX
05.5940.14.1V
05.5940.AP.1V

Casambi

05.5940.40.CB
05.5940.40.C6
05.5940.14.CB
05.5940.AP.CB

66°
HIGH
COMFORT



Luminous flux luminaire
1493 lm

Beam Angle:	66°
h(m)	E(lx)	D(m)
1	1436	1.31
2	359	2.61
3	160	3.92
4	90	5.23
5	57	6.54

Optic Oval - 3500K

Non Dimming

05.6446.40
05.6446.40.78
05.6446.14
05.6446.AP

Dali 2

05.6446.40.DA
05.6446.40.YU
05.6446.14.DA
05.6446.AP.DA


1-10V

05.6446.40.1V
05.6446.40.RX
05.6446.14.1V
05.6446.AP.1V

Casambi

05.6446.40.CB
05.6446.40.C6
05.6446.14.CB
05.6446.AP.CB

72°
OVAL



Luminous flux luminaire
1417 lm

Beam Angle:	72°
h(m)	E(lx)	D(m)
1	908	1.45
2	227	2.89
3	101	4.34
4	57	5.79
5	36	7.23

Optic High Comfort - 3500K

Non Dimming

05.5941.40
05.5941.40.78
05.5941.14
05.5941.AP

Dali 2

05.5941.40.DA
05.5941.40.YU
05.5941.14.DA
05.5941.AP.DA


1-10V

05.5941.40.1V
05.5941.40.RX
05.5941.14.1V
05.5941.AP.1V

Casambi

05.5941.40.CB
05.5941.40.C6
05.5941.14.CB
05.5941.AP.CB

66°
HIGH
COMFORT



Luminous flux luminaire
1504 lm

Beam Angle:	66°
h(m)	E(lx)	D(m)
1	1447	1.31
2	362	2.61
3	161	3.92
4	90	5.23
5	58	6.54

Optic Oval - 4000K

Non Dimming

05.6447.40
05.6447.40.78
05.6447.14
05.6447.AP

Dali 2

05.6447.40.DA
05.6447.40.YU
05.6447.14.DA
05.6447.AP.DA


1-10V

05.6447.40.1V
05.6447.40.RX
05.6447.14.1V
05.6447.AP.1V

Casambi

05.6447.40.CB
05.6447.40.C6
05.6447.14.CB
05.6447.AP.CB

72°
OVAL



Luminous flux luminaire
1438 lm

Beam Angle:	72°
h(m)	E(lx)	D(m)
1	921	1.45
2	230	2.89
3	102	4.34
4	58	5.79
5	37	7.23

Optic High Comfort - 4000K

Non Dimming

05.5942.40
05.5942.40.78
05.5942.14
05.5942.AP

Dali 2

05.5942.40.DA
05.5942.40.YU
05.5942.14.DA
05.5942.AP.DA


1-10V

05.5942.40.1V
05.5942.40.RX
05.5942.14.1V
05.5942.AP.1V

Casambi

05.5942.40.CB
05.5942.40.C6
05.5942.14.CB
05.5942.AP.CB

66°
HIGH
COMFORT




Luminous flux luminaire
1522 lm


Beam Angle:	66°
h(m)	E(lx)	D(m)
1	1464	1.31
2	366	2.61
3	163	3.92
4	92	5.23
5	59	6.54

Workmates Large

Top LED Full Spectrum
Non Dimming / 1-10V: 12,5W - 1358 lm - 3000K/CRI 98 / 1368 lm - 3500K/CRI 98 / 1382 lm - 4000K/CRI 98
Dali 2 / Casambi: 13,5W - 1358 lm - 3000K/CRI 98 / 1368 lm - 3500K/CRI 98 / 1382 lm - 4000K/CRI 98







Luminaire for use on The Running Magnet system. High-quality colour rendering Full Spectrum light source. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, máximum distance between fixtures: 50m.

Luminaria para aplicación en el sistema The Running Magnet. Fuente de luz Full Spectrum de alta calidad en la reproducción cromática. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.


Optic Wide Flood - 3000K

Non Dimming
- 05.6450.40
- 05.6450.40.78
- 05.6450.14
- 05.6450.AP

Dali 2
- 05.6450.40.DA
- 05.6450.40.YU
- 05.6450.14.DA
- 05.6450.AP.DA

1-10V
- 05.6450.40.1V
- 05.6450.40.RX
- 05.6450.14.1V
- 05.6450.AP.1V

Casambi
- 05.6450.40.CB
- 05.6450.40.C6
- 05.6450.14.CB
- 05.6450.AP.CB



Luminous flux luminaire
1005 lm

Beam Angle:	75°
h(m)	E(lx)	D(m)
1	659	1.52
2	165	3.05
3	73	4.57
4	41	6.10
5	26	7.62


Optic Wide Flood - 4000K

Non Dimming
- 05.6452.40
- 05.6452.40.78
- 05.6452.14
- 05.6452.AP

Dali 2
- 05.6452.40.DA
- 05.6452.40.YU
- 05.6452.14.DA
- 05.6452.AP.DA

1-10V
- 05.6452.40.1V
- 05.6452.40.RX
- 05.6452.14.1V
- 05.6452.AP.1V

Casambi
- 05.6452.40.CB
- 05.6452.40.C6
- 05.6452.14.CB
- 05.6452.AP.CB



Luminous flux luminaire
1022 lm

Beam Angle:	75°
h(m)	E(lx)	D(m)
1	670	1.52
2	168	3.05
3	74	4.57
4	42	6.10
5	27	7.62


Optic Wide Flood - 3500K

Non Dimming
- 05.6451.40
- 05.6451.40.78
- 05.6451.14
- 05.6451.AP

Dali 2
- 05.6451.40.DA
- 05.6451.40.YU
- 05.6451.14.DA
- 05.6451.AP.DA

1-10V
- 05.6451.40.1V
- 05.6451.40.RX
- 05.6451.14.1V
- 05.6451.AP.1V

Casambi
- 05.6451.40.CB
- 05.6451.40.C6
- 05.6451.14.CB
- 05.6451.AP.CB



Luminous flux luminaire
1014 lm

Beam Angle:	75°
h(m)	E(lx)	D(m)
1	665	1.52
2	166	3.05
3	74	4.57
4	42	6.10
5	27	7.62

NEW

Optic Oval - 3000K

Non Dimming

- 05.6455.40
- 05.6455.40.78
- 05.6455.14
- 05.6455.AP

Dali 2

- 05.6455.40.DA
- 05.6455.40.YU
- 05.6455.14.DA
- 05.6455.AP.DA


1-10V

- 05.6455.40.1V
- 05.6455.40.RX
- 05.6455.14.1V
- 05.6455.AP.1V

Casambi

- 05.6455.40.CB
- 05.6455.40.C6
- 05.6455.14.CB
- 05.6455.AP.CB

72° OVAL



Luminous flux luminaire 995 lm

Beam Angle: 72°

h(m)	E(lx)	D(m)
1	637	1.45
2	159	2.89
3	71	4.34
4	40	5.79
5	25	7.23

Optic High Comfort - 3000K

Non Dimming

- 05.5950.40
- 05.5950.40.78
- 05.5950.14
- 05.5950.AP

Dali 2

- 05.5950.40.DA
- 05.5950.40.YU
- 05.5950.14.DA
- 05.5950.AP.DA


1-10V

- 05.5950.40.1V
- 05.5950.40.RX
- 05.5950.14.1V
- 05.5950.AP.1V

Casambi

- 05.5950.40.CB
- 05.5950.40.C6
- 05.5950.14.CB
- 05.5950.AP.CB

66° HIGH COMFORT



Luminous flux luminaire 1087 lm

Beam Angle: 66°

h(m)	E(lx)	D(m)
1	1046	1.31
2	261	2.61
3	116	3.92
4	65	5.23
5	42	6.54

Optic Oval - 3500K

Non Dimming

- 05.6456.40
- 05.6456.40.78
- 05.6456.14
- 05.6456.AP

Dali 2

- 05.6456.40.DA
- 05.6456.40.YU
- 05.6456.14.DA
- 05.6456.AP.DA


1-10V

- 05.6456.40.1V
- 05.6456.40.RX
- 05.6456.14.1V
- 05.6456.AP.1V

Casambi

- 05.6456.40.CB
- 05.6456.40.C6
- 05.6456.14.CB
- 05.6456.AP.CB

72° OVAL



Luminous flux luminaire 1004 lm

Beam Angle: 72°

h(m)	E(lx)	D(m)
1	643	1.45
2	161	2.89
3	71	4.34
4	40	5.79
5	26	7.23

Optic High Comfort - 3500K

Non Dimming

- 05.5951.40
- 05.5951.40.78
- 05.5951.14
- 05.5951.AP

Dali 2

- 05.5951.40.DA
- 05.5951.40.YU
- 05.5951.14.DA
- 05.5951.AP.DA


1-10V

- 05.5951.40.1V
- 05.5951.40.RX
- 05.5951.14.1V
- 05.5951.AP.1V

Casambi

- 05.5951.40.CB
- 05.5951.40.C6
- 05.5951.14.CB
- 05.5951.AP.CB

66° HIGH COMFORT



Luminous flux luminaire 1098 lm

Beam Angle: 66°

h(m)	E(lx)	D(m)
1	1056	1.31
2	264	2.61
3	117	3.92
4	66	5.23
5	42	6.54

Optic Oval - 4000K

Non Dimming

- 05.6457.40
- 05.6457.40.78
- 05.6457.14
- 05.6457.AP

Dali 2

- 05.6457.40.DA
- 05.6457.40.YU
- 05.6457.14.DA
- 05.6457.AP.DA


1-10V

- 05.6457.40.1V
- 05.6457.40.RX
- 05.6457.14.1V
- 05.6457.AP.1V

Casambi

- 05.6457.40.CB
- 05.6457.40.C6
- 05.6457.14.CB
- 05.6457.AP.CB

72° OVAL



Luminous flux luminaire 1012 lm

Beam Angle: 72°

h(m)	E(lx)	D(m)
1	648	1.45
2	162	2.89
3	72	4.34
4	41	5.79
5	26	7.23

Optic High Comfort - 4000K

Non Dimming

- 05.5952.40
- 05.5952.40.78
- 05.5952.14
- 05.5952.AP

Dali 2

- 05.5952.40.DA
- 05.5952.40.YU
- 05.5952.14.DA
- 05.5952.AP.DA


1-10V

- 05.5952.40.1V
- 05.5952.40.RX
- 05.5952.14.1V
- 05.5952.AP.1V

Casambi

- 05.5952.40.CB
- 05.5952.40.C6
- 05.5952.14.CB
- 05.5952.AP.CB

66° HIGH COMFORT



Luminous flux luminaire 1116 lm


Beam Angle: 66°


h(m)	E(lx)	D(m)
1	1074	1.31
2	268	2.61
3	119	3.92
4	67	5.23
5	43	6.54

Light Shadow

Power LED 10,8W - 4x270 lm - 2700K/CRI 90 / 10,8W - 4x285 lm - 3000K/CRI 90







LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system.
DC/DC, built-in electronic current converter.
For wireless lighting control, choose integrated Casambi versions.

E= External Finish
I= Internal Finish


Módulo de iluminación LED de 4 focos y bajo deslumbramiento para ser instalado en el sistema The Running Magnet.
Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I On board dimmer
03.8948.40C
03.8948.14C
E I Dali 2
03.8948.40CDA
03.8948.14CDA
E I **Casambi Integrated
03.8948.40CCB
03.8948.14CCB

10° SPOT



Luminous flux luminaire
751 lm (EXTREME CUT OFF)


Beam Angle: 10°

h(m)	E(lx)	D(m)
1	13743	0.17
2	3436	0.35
3	1527	0.52
4	859	0.70
5	550	0.87

Optic Spot 3000K

E I On board dimmer
03.8952.40C
03.8952.14C
E I Dali 2
03.8952.40CDA
03.8952.14CDA
E I **Casambi Integrated
03.8952.40CCB
03.8952.14CCB

10° SPOT



Luminous flux luminaire
801 lm (EXTREME CUT OFF)


Beam Angle: 10°

h(m)	E(lx)	D(m)
1	14660	0.17
2	3665	0.35
3	1629	0.52
4	916	0.70
5	586	0.87

2700K

E I On board dimmer
03.8949.40C
03.8949.14C
E I Dali 2
03.8949.40CDA
03.8949.14CDA
E I **Casambi Integrated
03.8949.40CCB
03.8949.14CCB

10° SPOT



Luminous flux luminaire
724 lm (EXTREME CUT OFF)


Beam Angle: 10°

h(m)	E(lx)	D(m)
1	13076	0.18
2	3269	0.36
3	1453	0.54
4	817	0.72
5	523	0.90

3000K

E I On board dimmer
03.8953.40C
03.8953.14C
E I Dali 2
03.8953.40CDA
03.8953.14CDA
E I **Casambi Integrated
03.8953.40CCB
03.8953.14CCB

10° SPOT



Luminous flux luminaire
773 lm (EXTREME CUT OFF)


Beam Angle: 10°

h(m)	E(lx)	D(m)
1	13948	0.18
2	3487	0.36
3	1550	0.54
4	872	0.72
5	558	0.90

2700K

E I On board dimmer
05.1801.40C
05.1801.14C
E I Dali 2
05.1801.40CDA
05.1801.14CDA
E I **Casambi Integrated
05.1801.40CCB
05.1801.14CCB

13° SPOT



Luminous flux luminaire
784 lm (EXTREME CUT OFF)


Beam Angle: 13°

h(m)	E(lx)	D(m)
1	9237	0.23
2	2309	0.45
3	1027	0.68
4	578	0.90
5	370	1.13

3000K

E I On board dimmer
05.1806.40C
05.1806.14C
E I Dali 2
05.1806.40CDA
05.1806.14CDA
E I **Casambi Integrated
05.1806.40CCB
05.1806.14CCB

13° SPOT



Luminous flux luminaire
800 lm (EXTREME CUT OFF)


Beam Angle: 13°

h(m)	E(lx)	D(m)
1	9431	0.23
2	2358	0.45
3	1048	0.68
4	590	0.90
5	378	1.13

2700K

E I On board dimmer
05.1802.40C
05.1802.14C
E I Dali 2
05.1802.40CDA
05.1802.14CDA
E I **Casambi Integrated
05.1802.40CCB
05.1802.14CCB

12° SPOT



Luminous flux luminaire
841 lm (EXTREME CUT OFF)


Beam Angle: 12°

h(m)	E(lx)	D(m)
1	13375	0.20
2	3344	0.41
3	1486	0.61
4	836	0.82
5	535	1.02

3000K

E I On board dimmer
05.1807.40C
05.1807.14C
E I Dali 2
05.1807.40CDA
05.1807.14CDA
E I **Casambi Integrated
05.1807.40CCB
05.1807.14CCB

12° SPOT



Luminous flux luminaire
859 lm (EXTREME CUT OFF)

Beam Angle: 12°


h(m)	E(lx)	D(m)
1	13656	0.20
2	3414	0.41
3	1517	0.61
4	853	0.82
5	546	1.02

** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Optic Medium
2700K

E I On board dimmer
03.9620.40C
03.9620.14C
E I Dali 2
03.9620.40CDA
03.9620.14CDA
E I **Casambi Integrated
03.9620.40CCB
03.9620.14CCB

22° MEDIUM



Luminous flux luminaire
744 lm (EXTREME CUT OFF)


Beam Angle: 22°

h(m)	E(lx)	D(m)
1	4970	0.39
2	1243	0.78
3	552	1.17
4	311	1.56
5	199	1.95

Optic Medium
3000K

E I On board dimmer
03.9630.40C
03.9630.14C
E I Dali 2
03.9630.40CDA
03.9630.14CDA
E I **Casambi Integrated
03.9630.40CCB
03.9630.14CCB

22° MEDIUM



Luminous flux luminaire
793 lm (EXTREME CUT OFF)


Beam Angle: 22°

h(m)	E(lx)	D(m)
1	5302	0.39
2	1325	0.78
3	589	1.17
4	331	1.56
5	212	1.95

2700K

E I On board dimmer
03.9621.40C
03.9621.14C
E I Dali 2
03.9621.40CDA
03.9621.14CDA
E I **Casambi Integrated
03.9621.40CCB
03.9621.14CCB

22° MEDIUM



Luminous flux luminaire
744 lm (EXTREME CUT OFF)


Beam Angle: 22°

h(m)	E(lx)	D(m)
1	5086	0.39
2	1272	0.78
3	565	1.17
4	318	1.56
5	203	1.95

3000K

E I On board dimmer
03.9631.40C
03.9631.14C
E I Dali 2
03.9631.40CDA
03.9631.14CDA
E I **Casambi Integrated
03.9631.40CCB
03.9631.14CCB

22° MEDIUM



Luminous flux luminaire
793 lm (EXTREME CUT OFF)


Beam Angle: 22°

h(m)	E(lx)	D(m)
1	5425	0.39
2	1356	0.78
3	603	1.17
4	339	1.56
5	217	1.95

2700K

E I On board dimmer
05.1811.40C
05.1811.14C
E I Dali 2
05.1811.40CDA
05.1811.14CDA
E I **Casambi Integrated
05.1811.40CCB
05.1811.14CCB

21° MEDIUM



Luminous flux luminaire
827 lm (EXTREME CUT OFF)


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	6094	0.36
2	1523	0.73
3	677	1.09
4	381	1.45
5	244	1.81

3000K

E I On board dimmer
05.1816.40C
05.1816.14C
E I Dali 2
05.1816.40CDA
05.1816.14CDA
E I **Casambi Integrated
05.1816.40CCB
05.1816.14CCB

21° MEDIUM



Luminous flux luminaire
844 lm (EXTREME CUT OFF)


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	6222	0.36
2	1555	0.73
3	692	1.09
4	389	1.45
5	249	1.81

2700K

E I On board dimmer
05.1812.40C
05.1812.14C
E I Dali 2
05.1812.40CDA
05.1812.14CDA
E I **Casambi Integrated
05.1812.40CCB
05.1812.14CCB

22° MEDIUM



Luminous flux luminaire
827 lm (EXTREME CUT OFF)


Beam Angle: 22°

h(m)	E(lx)	D(m)
1	5802	0.38
2	1451	0.76
3	645	1.14
4	363	1.52
5	232	1.91

3000K

E I On board dimmer
05.1817.40C
05.1817.14C
E I Dali 2
05.1817.40CDA
05.1817.14CDA
E I **Casambi Integrated
05.1817.40CCB
05.1817.14CCB

22° MEDIUM



Luminous flux luminaire
844 lm (EXTREME CUT OFF)

Beam Angle: 22°


h(m)	E(lx)	D(m)
1	5924	0.38
2	1481	0.76
3	658	1.14
4	370	1.52
5	237	1.91


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Light Shadow

Power LED 10,8W - 4x270 lm - 2700K/CRI 90 / 10,8W - 4x285 lm - 3000K/CRI 90







LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system.
DC/DC, built-in electronic current converter.
For wireless lighting control, choose integrated Casambi versions.


E= External Finish
I= Internal Finish

Módulo de iluminación LED de 4 focos y bajo deslumbramiento para ser instalado en el sistema The Running Magnet.
Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I On board dimmer
03.9625.40C
03.9625.14C
E I Dali 2
03.9625.40CDA
03.9625.14CDA
E I **Casambi Integrated
03.9625.40CCB
03.9625.14CCB




Luminous flux luminaire
741 lm (EXTREME CUT OFF)

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2310	0.59
2	577	1.18
3	257	1.78
4	144	2.37
5	92	2.96

Optic Flood 3000K

E I On board dimmer
03.9635.40C
03.9635.14C
E I Dali 2
03.9635.40CDA
03.9635.14CDA
E I **Casambi Integrated
03.9635.40CCB
03.9635.14CCB




Luminous flux luminaire
790 lm (EXTREME CUT OFF)

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2464	0.59
2	616	1.18
3	274	1.78
4	154	2.37
5	99	2.96

2700K

E I On board dimmer
03.9626.40C
03.9626.14C
E I Dali 2
03.9626.40CDA
03.9626.14CDA
E I **Casambi Integrated
03.9626.40CCB
03.9626.14CCB




Luminous flux luminaire
720 lm (EXTREME CUT OFF)

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2250	0.60
2	563	1.19
3	250	1.79
4	141	2.39
5	90	2.99

3000K

E I On board dimmer
03.9636.40C
03.9636.14C
E I Dali 2
03.9636.40CDA
03.9636.14CDA
E I **Casambi Integrated
03.9636.40CCB
03.9636.14CCB




Luminous flux luminaire
768 lm (EXTREME CUT OFF)

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2400	0.60
2	600	1.19
3	267	1.79
4	150	2.39
5	96	2.99

2700K

E I On board dimmer
05.1821.40C
05.1821.14C
E I Dali 2
05.1821.40CDA
05.1821.14CDA
E I **Casambi Integrated
05.1821.40CCB
05.1821.14CCB




Luminous flux luminaire
841 lm (EXTREME CUT OFF)

Beam Angle:	27°	
h(m)	E(lx)	D(m)
1	3618	0.48
2	904	0.96
3	402	1.43
4	226	1.91
5	145	2.39

3000K

E I On board dimmer
05.1826.40C
05.1826.14C
E I Dali 2
05.1826.40CDA
05.1826.14CDA
E I **Casambi Integrated
05.1826.40CCB
05.1826.14CCB




Luminous flux luminaire
859 lm (EXTREME CUT OFF)

Beam Angle:	27°	
h(m)	E(lx)	D(m)
1	3694	0.48
2	923	0.96
3	411	1.43
4	231	1.91
5	148	2.39

2700K

E I On board dimmer
05.1822.40C
05.1822.14C
E I Dali 2
05.1822.40CDA
05.1822.14CDA
E I **Casambi Integrated
05.1822.40CCB
05.1822.14CCB




Luminous flux luminaire
809 lm (EXTREME CUT OFF)

Beam Angle:	26°	
h(m)	E(lx)	D(m)
1	3692	0.46
2	923	0.92
3	410	1.39
4	231	1.85
5	148	2.31

3000K

E I On board dimmer
05.1827.40C
05.1827.14C
E I Dali 2
05.1827.40CDA
05.1827.14CDA
E I **Casambi Integrated
05.1827.40CCB
05.1827.14CCB



Luminous flux luminaire
826 lm (EXTREME CUT OFF)


Beam Angle:	26°	
h(m)	E(lx)	D(m)
1	3770	0.46
2	942	0.92
3	419	1.39
4	236	1.85
5	151	2.31

** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Optic Wide Flood
2700K

E I On board dimmer
03.9660.40C
03.9660.14C
E I Dali 2
03.9660.40CDA
03.9660.14CDA
E I **Casambi Integrated
03.9660.40CCB
03.9660.14CCB





Luminous flux luminaire
735 lm


Beam Angle: 47°

h(m)	E(lx)	D(m)
1	1395	0.84
2	349	1.69
3	155	2.53
4	87	3.38
5	56	4.22

Optic Wide Flood
3000K

E I On board dimmer
03.9664.40C
03.9664.14C
E I Dali 2
03.9664.40CDA
03.9664.14CDA
E I **Casambi Integrated
03.9664.40CCB
03.9664.14CCB





Luminous flux luminaire
780 lm


Beam Angle: 47°

h(m)	E(lx)	D(m)
1	1454	0.83
2	363	1.67
3	162	2.50
4	91	3.34
5	58	4.17

2700K

E I On board dimmer
03.9661.40C
03.9661.14C
E I Dali 2
03.9661.40CDA
03.9661.14CDA
E I **Casambi Integrated
03.9661.40CCB
03.9661.14CCB





Luminous flux luminaire
731 lm


Beam Angle: 47°

h(m)	E(lx)	D(m)
1	1363	0.83
2	341	1.67
3	151	2.50
4	85	3.34
5	55	4.17

3000K

E I On board dimmer
03.9665.40C
03.9665.14C
E I Dali 2
03.9665.40CDA
03.9665.14CDA
E I **Casambi Integrated
03.9665.40CCB
03.9665.14CCB





Luminous flux luminaire
784 lm


Beam Angle: 47°

h(m)	E(lx)	D(m)
1	1488	0.84
2	372	1.69
3	165	2.53
4	93	3.38
5	60	4.22

2700K

E I On board dimmer
05.1831.40C
05.1831.14C
E I Dali 2
05.1831.40CDA
05.1831.14CDA
E I **Casambi Integrated
05.1831.40CCB
05.1831.14CCB





Luminous flux luminaire
786 lm (EXTREME CUT OFF)


Beam Angle: 38°

h(m)	E(lx)	D(m)
1	1947	0.70
2	487	1.39
3	216	2.09
4	122	2.78
5	78	3.48

3000K

E I On board dimmer
05.1836.40C
05.1836.14C
E I Dali 2
05.1836.40CDA
05.1836.14CDA
E I **Casambi Integrated
05.1836.40CCB
05.1836.14CCB





Luminous flux luminaire
806 lm (EXTREME CUT OFF)


Beam Angle: 38°

h(m)	E(lx)	D(m)
1	1996	0.70
2	499	1.39
3	222	2.09
4	125	2.78
5	80	3.48

2700K

E I On board dimmer
05.1832.40C
05.1832.14C
E I Dali 2
05.1832.40CDA
05.1832.14CDA
E I **Casambi Integrated
05.1832.40CCB
05.1832.14CCB





Luminous flux luminaire
767 lm (EXTREME CUT OFF)


Beam Angle: 41°

h(m)	E(lx)	D(m)
1	1796	0.74
2	449	1.48
3	200	2.22
4	112	2.96
5	72	3.70

3000K

E I On board dimmer
05.1837.40C
05.1837.14C
E I Dali 2
05.1837.40CDA
05.1837.14CDA
E I **Casambi Integrated
05.1837.40CCB
05.1837.14CCB





Luminous flux luminaire
783 lm (EXTREME CUT OFF)

Beam Angle: 41°


h(m)	E(lx)	D(m)
1	1834	0.74
2	458	1.48
3	204	2.22
4	115	2.96
5	73	3.70


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Light Shadow Wall-Washer

Power LED 10,8W - 4x298 lm - 2700K/CRI 90 / 10,8W - 4x318 lm - 3000K/CRI 90








LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system.
DC/DC, built-in electronic current converter.
For wireless lighting control, choose integrated Casambi versions.

Módulo de iluminación LED de 4 focos y bajo deslumbramiento para ser instalado en el sistema The Running Magnet.
Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.

2700K
On board dimmer
- 03.9905.40C
- 03.9905.14C

Dali 2
- 03.9905.40CDA
- 03.9905.14CDA

**Casambi Integrated
- 03.9905.40CCB
- 03.9905.14CCB



Luminous flux luminaire
801 lm


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	1029	0.54
2	257	1.08
3	114	1.62
4	64	2.16
5	41	2.70

3000K
On board dimmer
- 03.9904.40C
- 03.9904.14C

Dali 2
- 03.9904.40CDA
- 03.9904.14CDA

**Casambi Integrated
- 03.9904.40CCB
- 03.9904.14CCB



Luminous flux luminaire
945 lm

Beam Angle: 24°


h(m)	E(lx)	D(m)
1	1215	0.54
2	304	1.08
3	135	1.62
4	76	2.16
5	49	2.70


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Multi Spot 4

Power LED 10W - 840 lm - 2700K/CRI 90 / 896 lm - 3000K/CRI 90








Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter. For wireless lighting control, choose integrated Casambi versions.

See available accessories.

Módulo de iluminación LED de acento para ser instalado en el sistema The Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.

Ver accesorios disponibles.


2700K
On board dimmer
03.6305.14C
Dali 2
03.6305.14CDA
**Casambi Integrated
03.6305.14CCB



Luminous flux luminaire
614 lm

Beam Angle:	11°
h(m)	E(lx)	D(m)
1	14966	0.19
2	3742	0.38
3	1663	0.57
4	935	0.76
5	599	0.94

3000K
On board dimmer
03.6306.14C
Dali 2
03.6306.14CDA
**Casambi Integrated
03.6306.14CCB



Luminous flux luminaire
657 lm

Beam Angle:	11°
h(m)	E(lx)	D(m)
1	16014	0.19
2	4004	0.38
3	1779	0.57
4	1001	0.76
5	641	0.94

Accessories / Accesorios


Spot Module & Multi Spot 4

Frosted medium lens.
Medium lens accessory.

Lente frosted medium.
Accesorio de óptica medium.




08.8760.00



Luminous flux luminaire
381 lm

Beam Angle:	21°
h(m)	E(lx)	D(m)
1	2082	0.36
2	520	0.73
3	231	1.09
4	130	1.46
5	83	1.82



Luminous flux luminaire
611 lm (EXTREME CUT OFF)


Beam Angle:	21°
h(m)	E(lx)	D(m)
1	3245	0.37
2	811	0.75
3	361	1.12
4	203	1.50
5	130	1.87

Frosted flood lens.
Flood lens accessory.

Lente frosted flood.
Accesorio de óptica flood.




08.8761.00



Luminous flux luminaire
356 lm

Beam Angle:	31°
h(m)	E(lx)	D(m)
1	1074	0.55
2	269	1.09
3	119	1.64
4	67	2.19
5	43	2.73



Luminous flux luminaire
451 lm (EXTREME CUT OFF)


Beam Angle:	28°
h(m)	E(lx)	D(m)
1	1678	0.50
2	420	1.00
3	186	1.51
4	105	2.01
5	67	2.51

Elliptical lens.

Lente elíptica.




08.8759.00



Luminous flux luminaire
419 lm

Beam Angle:	46°
h(m)	E(lx)	D(m)
1	2282	0.17
2	571	0.34
3	254	0.51
4	143	0.68
5	91	0.85



Luminous flux luminaire
756 lm (EXTREME CUT OFF)


Beam Angle:	46°
h(m)	E(lx)	D(m)
1	4108	0.15
2	1027	0.30
3	456	0.44
4	257	0.59
5	164	0.74


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

String Light Sphere

Power LED 14W - 930 lm - 2700K/CRI 90 / 14W - 930 lm - 3000K/CRI 90







General lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.
For wireless lighting control, choose integrated Casambi versions.


Spot Module No DALI:
Maximum 9 spots for a single driver.

Módulo de iluminación LED general para ser instalado en el sistema The Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.

Spot Module No DALI:
Máximo 9 spots para un mismo driver.

String Light Cone






String Light Sphere 2700K

On board dimmer
- 03.6295.14A

Dali 2
- 03.6295.14ADA

**Casambi Integrated
- 03.6295.14ACB



Luminous flux luminaire
800 lm

Beam Angle: 177°


h(m)	E(lx)	D(m)
1	130	75.06
2	32	150.12
3	14	225.19
4	8	300.25
5	5	375.31

String Light Cone 2700K

On board dimmer
- 03.6297.14A

Dali 2
- 03.6297.14ADA

**Casambi Integrated
- 03.6297.14ACB



Luminous flux luminaire
604 lm

Beam Angle: 114°


h(m)	E(lx)	D(m)
1	207	3.08
2	52	6.16
3	23	9.24
4	13	12.32
5	8	15.40

String Light Sphere 3000K

On board dimmer
- 03.6296.14A

Dali 2
- 03.6296.14ADA

**Casambi Integrated
- 03.6296.14ACB



Luminous flux luminaire
866 lm

Beam Angle: 177°


h(m)	E(lx)	D(m)
1	140	75.06
2	35	150.12
3	16	225.19
4	9	300.25
5	6	375.31

String Light Cone 3000K

On board dimmer
- 03.6298.14A

Dali 2
- 03.6298.14ADA

**Casambi Integrated
- 03.6298.14ACB



Luminous flux luminaire
653 lm

Beam Angle: 114°


h(m)	E(lx)	D(m)
1	224	3.08
2	56	6.16
3	25	9.24
4	14	12.32
5	9	15.40


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Mini Glo-Ball

Power LED 7W - 800 lm - 2700K/CRI 80 / 7W - 880 lm - 3000K/CRI 80








General lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.
For wireless lighting control, choose integrated Casambi versions.

Spot Module No DALI:
Maximum 21 spots for a single driver.
Spot Module DALI:
Maximum 14 spots for a single driver.

Módulo de iluminación LED general para ser instalado en el sistema The Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.


Spot Module No DALI:
Máximo 21 spots para un mismo driver.
Spot Module DALI:
Máximo 14 spots para un mismo driver.

2700K
On board dimmer
03.6260.14B
Dali 2
03.6260.14ADA
*Casambi Integrated
03.6260.14.CB



Luminous flux luminaire
446 lm

3000K
On board dimmer
03.6261.14B
Dali 2
03.6261.14ADA
*Casambi Integrated
03.6261.14.CB





Luminous flux luminaire
508 lm

Mini Glo-Ball S

Power LED 3,5W - 400 lm - 2700K/CRI 80 / 3,5W - 440 lm - 3000K/CRI 80








General lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.
For wireless lighting control, choose integrated Casambi versions.

Spot Module No DALI:
Maximum 21 spots for a single driver.
Spot Module DALI:
Maximum 14 spots for a single driver.

Módulo de iluminación LED general para ser instalado en el sistema The Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.


Spot Module No DALI:
Máximo 21 spots para un mismo driver.
Spot Module DALI:
Máximo 14 spots para un mismo driver.

2700K
On board dimmer
03.6262.14B
Dali 2
03.6262.14ADA
**Casambi Integrated
03.6262.14.CB



Luminous flux luminaire
258 lm

3000K
On board dimmer
03.6263.14B
Dali 2
03.6263.14ADA
**Casambi Integrated
03.6263.14.CB




Luminous flux luminaire
271 lm


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Find Me 1 Suspension

Power LED 8W - 560 lm - 2700K/CRI 90 / 8W - 600 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.
For wireless lighting control, choose integrated Casambi versions.

Spot Module No DALI:
Maximum 21 spots for a single driver.
Spot Module DALI:
Maximum 14 spots for a single driver.

Módulo de iluminación LED de acento para ser instalado en el sistema The Running Magnet. Convertidor electrónico de corriente DC/DC incorporado.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.


Spot Module No DALI:
Máximo 21 spots para un mismo driver.
Spot Module DALI:
Máximo 14 spots para un mismo driver.

2700K
On board dimmer
- 03.6272.30D
- 03.6272.05D
- 03.6272.14D

Dali 2
- 03.6272.30EDA
- 03.6272.05EDA
- 03.6272.14EDA

**Casambi Integrated
- 03.6272.30DCB
- 03.6272.05DCB
- 03.6272.14DCB





Luminous flux luminaire
344 lm (EXTREME CUT OFF)

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	4642	0.24
2	1160	0.48
3	516	0.72
4	290	0.95
5	186	1.19

3000K
On board dimmer
- 03.6273.30D
- 03.6273.05D
- 03.6273.14D

Dali 2
- 03.6273.30EDA
- 03.6273.05EDA
- 03.6273.14EDA

**Casambi Integrated
- 03.6273.30DCB
- 03.6273.05DCB
- 03.6273.14DCB





Luminous flux luminaire
365 lm (EXTREME CUT OFF)

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	4881	0.24
2	1220	0.49
3	542	0.73
4	305	0.97
5	195	1.21

** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Control Units / Unidades de Control

Wireless Dimmer Bridge. From 1-10V to Casambi. For remote installation. See product specifications in the Flos Control manual. Recommended to act as a gateway from Lutron to Casambi.

Pasarela de regulación inalámbrica. De 1-10V a Casambi. Para instalación remota. Consulte las especificaciones de producto en el manual Flos Control. Aconsejado para actuar como pasarela de Lutron a Casambi.




DIM 1-10V >> Casambi
08.0824.14

Multifunction Smart Device

Multifunction Smart Device. Triple functionality 3x1: Casambi signal repeater, light sensor and presence detector.
FLOS Control® by Casambi.

Dispositivo multifunción inteligente. Triple funcionalidad 3x1: repetidor de señal Casambi, sensor de luz ambiental y detector de presencia.
FLOS Control® by Casambi.







06.1987.40
06.1987.14

Multifunction Smart Device. Triple Functionality 3x1


Repeater



Daylight Sensor




Presence Sensor




▲ Casambi object

RECESSED SURFACE SUSPENSION
UP&DOWN/DOWN



Recessed Profiles ■ 14 Black
14 Negro

Surface/Suspension Profiles ■ 14 Black
14 Negro
□ 40 White
40 Blanco
▨ 05 Polished Silver
05 Plata Pulida






Surface Flos Kit Installation

Recessed Flos Kit Installation

Recessed Conventional Installation

Anthony Spot

Description
Renewed indoor lighting system for surface, suspended and recessed in plasterboard wall/ceiling installation.
In the new proposal, beside the successful “On Board Dimmer” version, FLOS goes one step beyond, launching both track and luminaries designed for system management in a variety of options: DALI, 1-10V and Casambi.
There are three profile versions (recessed, surface/suspension and Up&Down), all manufactured with aluminium profiling of a maximum of 3m extruded in white, black or polished aluminium, provided with electric tracks powered at 48V.
Furthermore, the system controlled versions (DALI, 1-10V) are equipped with graphite data bus for regulation.
Luminaires are installed through a magnetic fixing system.
The Tracking Magnet product group is complemented with ambient and accent lighting modules, with different optics. The light fixtures are available with potentiometer incorporated, dimmable DALI, 1-10V or Casambi for remote setting.

Control
- For installation of “On Board Dimmer” fixtures use “On Board Dimmer” track version. Luminaries DALI and 1-10V are only compatible with track DALI, 1-10V.
Casambi luminaires can be installed on all profiles available in the system.
- To manage using DALI protocol, it is necessary to connect the control data bus directly to the profile.
- For the 1-10V management, the control system needs to be active (SOURCE, the controller generates the power signal) and the control data bus needs to be directly connected to the profile. If the controller is passive (SINK), the Control Dimming box unit will be necessary. It is located between the control unit and the track, and it must be ordered separately from the accessories department. In the 1-10V management system, all luminaries are dimmed at the same time (as a block or broadcast).
- For Casambi management (Max. 200 luminaires) it is mandatory to use fixtures in the Casambi version, these are compatible with all profiles available in the system.
For managing and controlling the Casambi system, the FLOS Control® app powered by Casambi for mobile devices is necessary (available in the Apple Store and Google Play).
Maximum number of track interconnections to guarantee the communication of the DALI or 1-10V signal: 20 interconnections including cuts, or 20 meters. Maximum number of track cuts to guarantee the communication of the DALI or 1-10V signal: 3 cuts.
The UP&DOWN version has a compatible DALI interface for controlling indirect lighting. Please note that since it is a DALI compatible component, it may not respond to advanced DALI protocol functions. For more information, see the technical specifications section on the Flos website.
The UP&DOWN version can be controlled independently via DALI.
Compatible with “BTcino My home” (please consult Front Office).

Power Supply
Remote 48V power supply not included.

Accessories
For the Anthony Spot lighting module there are elliptical, flood lenses (to be used with Anthony Spot Medium) and screening elements.
For the Spot tracking lighting modules, the honeycomb and screening crossbrace accessories are incorporated in the product, except for the chrome finish.
The Suspension versions offer two suspension systems that must be ordered separately: rigid bars to stop the profile tilting (straight structures with no corners) or for installations requiring a more rigid fixture system, and steel cable, recommended if a corner is included in the structure, where the tilt will not appear in any case.

Additional Information
Recessed version only to be installed in 12.5mm thick plasterboard surfaces.
The Tracking Magnet is a 48V electrical system limited to a maximum power current of 8A - 48Vdc to avoid overloads.
Maximum length with a single power source is 20 m.
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Renovado sistema de iluminación para interior en versiones superficie, suspendida o empotrada en pared/techo de cartón yeso.
En la nueva propuesta, además de la ya conocida versión “On Board Dimmer”, FLOS ha dado un paso más, añadiendo perfiles y luminarias que pueden controlarse con varios sistemas de control remoto: DALI, 1-10V y Casambi.
Existen tres versiones de perfil (empotrada, superficie/suspensión y Up&Down), todos fabricados con perfilería de aluminio máx. 3 m, extruido en blanco, negro o aluminio pulido, provistos de pistas eléctricas alimentadas a 48V.
Además, las versiones controlables como sistema (DALI, 1-10V) llevan bus de datos en grafito para su regulación. Las luminarias se instalan mediante un sistema de fijación magnética.
La familia Tracking Magnet se completa con módulos de iluminación ambiental y de acento, con diferentes ópticas. Los módulos de luz disponen de un potenciómetro instalado, regulación DALI, 1-10V o Casambi según se desee.

Control
- Para instalaciones de luminaria con sistema de dimado “On Board Dimmer” y FLOS Control®, usar perfil en versión “On Board Dimmer”. Las luminarias DALI y 1-10V solo son compatibles con perfil versión DALI, 1-10V. Las luminarias Casambi son compatibles con todos los perfiles.
- Para gestión mediante protocolo DALI es necesario conectar el bus de datos de control directamente al perfil.
- Para la gestión 1-10V es necesario que el sistema de control sea activo (SOURCE, el controlador genera la señal de tensión) y conectar el bus de datos de control directamente al perfil. Si el controlador es de tipo pasivo (SINK), es necesaria la unidad Control Dimming BOX (ubicada entre la unidad de control y el carril) que hay que pedir por separado en el apartado de accesorios. En el sistema de gestión 1-10V todas las luminarias se regulan a la vez (en bloque o broadcast).
- Para gestión mediante Casambi (Máximo 200 luminarias) es necesario pedir luminarias versión Casambi, estas son compatibles con cualquier tipo de perfil del sistema.
Necesaria APP FLOS Control® powered by Casambi para dispositivos móviles (disponible en Apple Store y Google Play).
Número máximo de interconexiones de carriles para garantizar la comunicación de la señal DALI o 1-10V será de 20 interconexiones incluyendo los cortes ó 20 metros. Número máximo de cortes de carril para garantizar la comunicación de la señal DALI o 1-10V será 3 cortes.
La versión UP&DOWN equipa un interfaz DALI compatible para el control de la iluminación indirecta. Tenga en cuenta que al ser un componente DALI compatible, éste puede no responder a funciones avanzadas del protocolo DALI. Para más información consulte el apartado de especificaciones técnicas en la web de Flos.
La versión UP&DOWN puede ser controlada independientemente vía DALI.
Compatibilidad con “BTcino My home” (consultar con Front Office).

Unidades de Alimentación
Fuente de alimentación remota de 48V no incluida.

Accesorios
Para el módulo de iluminación Anthony Spot existen lentes elípticas, flood (para usarse con Anthony Spot Medium) y elementos apantalladores.
Para los módulos de iluminación Spot tracking los accesorios honeycomb y cruceta de apantallamiento incorporados en el producto, salvo para el acabado cromo.
Las versiones Suspensión ofrecen dos sistemas de suspensión, que deben pedirse por separado: varillas rígidas para evitar la inclinación del Perfil (estructuras rectilíneas sin esquinas) o para instalaciones donde se requiere sistema de fijación más rígido, y cable de acero recomendado si una esquina está incluida en la estructura, donde la inclinación no aparecerá en ningún caso.

Información Adicional
La versión Recessed únicamente instalable en superficies de cartón-yeso de 12,5mm de espesor.
The Tracking Magnet es un sistema eléctrico alimentado a 48V y limitado a una corriente máxima de 8A - 48Vdc para evitar sobrecargas.
Longitud máxima con una sola fuente de alimentación 20m.
Índice de protección IP20.
Instalable sobre superficies normalmente inflamables.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

LIGHT MODULES

LIGHT STRIPE



LIGHT SOURCE
TOP LED
20W/m
1859 lm/m
2700K/CRI 90
1967 lm/m
3000K/CRI 90

SPOT 50



LIGHT SOURCE
POWER LED
3,5W
286 lm
2700K/CRI 90
307 lm
3000K/CRI 90

SPOT 90



LIGHT SOURCE
POWER LED
8,5W
610 lm
2700K/CRI 90
656 lm
3000K/CRI 90

SPOT 120



LIGHT SOURCE
POWER LED
12W
724 lm
2700K/CRI 90
779 lm
3000K/CRI 90

SPOT 120



LIGHT SOURCE
LED ARRAY
12,5W
1075 lm
2700K/CRI 90
1138 lm
3000K/CRI 90

SPOT 150



LIGHT SOURCE
LED ARRAY
22,5W
2411 lm
2700K/CRI 90
2569 lm
3000K/CRI 90

LIGHT SHADOW SPOT 30



LIGHT SOURCE
POWER LED
4,5W
298 lm
2700K/CRI 90
318 lm
3000K/CRI 90

LIGHT SHADOW SPOT 45



LIGHT SOURCE
LED ARRAY
10W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

LIGHT SHADOW SPOT 60



LIGHT SOURCE
LED ARRAY
Up to 20W
Up to 1563 lm
2700K/CRI 90
Up to 1751 lm
3000K/CRI 90

ANTHONY SPOT TRACK



LIGHT SOURCE
LED ARRAY
16,5W
1620 lm
2700K/CRI 90
1730 lm
3000K/CRI 90

WALLEE



LIGHT SOURCE
TOP LED
10W
773 lm
2700K/CRI 90
818 lm
3000K/CRI 90

MULTI SPOT MINI



LIGHT SOURCE
TOP LED
7,5W
635 lm
2700K/CRI 90
650 lm
3000K/CRI 90

MULTIFUNCTION SMART DEVICE



FLOS CONTROL®
by Casambi

Light Stripe

14 Black
14 Negro



Spot

40 White
40 Blanco



05 Polished Silver
05 Plata Pulida



14 Black
14 Negro



Light Shadow Spot

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



Anthony Spot Track

40 White
40 Blanco



05 Polished Silver
05 Plata Pulida



14 Black
14 Negro



Walee

40 White
40 Blanco



14 Black
14 Negro



Multi Spot Mini

40 White
40 Blanco



14 Black
14 Negro



Multifunction Smart Device

40 White
40 Blanco




14 Black
14 Negro



HOW TO ORDER

1 CHOOSE YOUR PROFILE AND LENGTH


RECESSED PROFILE






L: 1 / 1,5 / 2 / 2,5 / 3 m

SURFACE / SUSPENSION DOWN PROFILE












L: 1 / 1,5 / 2 / 2,5 / 3 m

SUSPENSION UP&DOWN PROFILE







L: 1 / 1,5 / 2 / 2,5 / 3 m

2 COMPLETE WITH MOUNTING ACCESSORIES

Feed connector



End cap



Intermediate connectors



Straight
Flexible/Electrical corner

90° Corner



mechanical joint

Inner corner



mechanical joint

Outer corner



mechanical joint

Accessories

Fixed ceiling kit



or

Adjustable ceiling kit



Surface Installation

Inner corner



mechanical joint

Surface / Suspension Down Installation

Feed connector



End cap



Intermediate connectors



Straight
Flexible/Electrical corner

90° Corner



electrical & mechanical joint

Surface Accessories

Kit surface bracket



Suspension Down Accessories

Kit suspension bracket



Intermediate suspension kit



Surface rose



or
Recessed rose



Power cable



Rigid rod



or
Suspension cable



Feed unit kit



Intermediate connectors



Straight
Flexible/Electrical corner

End cap



90° Corner



mechanical joint

Accessories

Intermediate suspension kit



Surface rose



or
Recessed rose



Rigid rod



or
Suspension cable



3 SELECT POWER SUPPLY AND CONTROL OPTION

(select the driver with the appropriate power according to the needs of your project)

Remote power supply
Profiles: Recessed, Surface & Suspension Down

On board dimmer / Casambi / Dali



185W *or* 320W

1-10V



185W *or* 320W

+



1-10V control box

(needed only to transform sink into source control signal)

Remote power supply
Profile: Suspension Up & Down

On board dimmer / Casambi



185W *or* 320W

Dali



185W *or* 320W

+



DALI Push

Up Control

1-10V



185W *or* 320W

+



1-10V Push

+



1-10V control box

(needed only to transform sink into source control signal)


Up Control **Down Control**

Surface power supply


On board dimmer / Casambi / Dali / *1-10V

*(only for 1-10V source signal)


Profile: Suspension Down



Profile: Suspension Up & Down



Profile: Surface



4 SELECT A LIGHT MODULE AND CONTROL OPTION

Dali / 1-10V / Casambi / On board dimmer

Light Stripe





General lighting

Multi Spot Mini





S/M/F

Spot 50





M

Spot 90





S/M

Spot 120





S/M/F

Spot 150





S/M/F

Light Shadow Spot 30





S/M/F/WF

Light Shadow Spot 45





S/M/F

Light Shadow Spot 60





SS/S/M/F/WF

Anthony Spot Track





S/M

Wallee






General lighting

Multifunction Smart Device
FLOS Control® by Casambi



RECESSED INSTALLATION





Profiles

Electromechanical profile for recessed installation in plasterboard ceilings and walls, available in lengths from 1m to 3m.
A version compatible with 'On Board Dimmer' and Casambi light fixtures is available. Version compatible with controllable lights such as DALI and 1-10V systems. Corners, connectors and accessories common for the two profile versions.
Feed connector, intermediated connector and end-caps to be ordered separately.
Mechanical 90° corners available in the same plane (symmetrical element for left and right corners), symmetrical 90° inner and outer corners in different planes.
Intermediate connectors to be ordered separately if electrical continuity on corners is required.
Corners do not admit installation of spots.
Fixed or adjustable fastening kits available (optional). The fastening kits for the roof permit installing without using aluminimum fastening profiles.
Recommended for installations where the Tracking Magnet can be installed before the suspended plasterboard ceiling.

Perfiles

Perfil electro-mecánico para instalaciones empotradas en techos/paredes de cartón yeso con longitudes de 1m a 3m.
Disponible versión compatible con luminarias "On Board Dimmer" y Casambi. Versión compatible con luminarias controlables como sistema DALI y 1-10V. Esquinas, conectores y accesorios comunes para las dos versiones.
Necesario pedir por separado conector de alimentación, conectores intermedios y tapas.
Disponibles esquinas mecánicas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha), esquinas simétricas de 90° en distinto plano en interior y exterior.
Necesario pedir por separado conector flexible para asegurar continuidad eléctrica en las esquinas.
No es posible instalar spots en las esquinas.
Kits de sujeción, fijo o ajustable, disponibles (opcional). Los kits de sujeción a techo permiten la instalación sin necesidad de perfiles de aluminio de sujeción. Recomendado para instalaciones en las que se puede instalar el perfil Tracking Magnet antes que el falso techo de cartón yeso.






On board dimmer / Casambi	DALI / 1-10V / Casambi
L: 1000 mm	L: 1000 mm
06.5050.14	06.5040.14
L: 1500 mm	L: 1500 mm
06.5051.14	06.5041.14
L: 2000 mm	L: 2000 mm
06.5052.14	06.5042.14
L: 2500 mm	L: 2500 mm
06.5053.14	06.5043.14
L: 3000 mm	L: 3000 mm
06.5054.14	06.5044.14

90° mechanical corner.
To create electrical continuity, order with the flexible intermediate connector.

Esquina mecánica 90°.
Para crear continuidad eléctrica pedir con el conector intermedio flexible.






06.5045.14

Inner mechanical corner.
To create electrical continuity, order with the flexible intermediate connector.

Esquina mecánica interior.
Para crear continuidad eléctrica pedir con el conector intermedio flexible.






06.5046.14

Outer mechanical corner.
To create electrical continuity, order with the flexible intermediate connector.

Esquina mecánica exterior.
Para crear continuidad eléctrica pedir con el conector intermedio flexible.






06.5047.14

Feed connector.

Conector alimentación.






08.0611.14

Intermediate connector.


Conector intermedio.





Straight
08.0612.14






Flexible/Electrical corner
08.0614.14

Fixed ceiling kit (optional).
2 unit kit.

Kit de sujeción a techo fijo (opcional). Kit de 2 unidades.






08.8866.14

Profile (mm)	Fixation points	Ceiling Kit to order
1000 / 1500	2	1
2000 / 2500	3	2
3000	4	2

Adjustable ceiling kit (optional).
2 unit kit.

Kit de sujeción a techo ajustable (opcional). Kit de 2 unidades.





08.8867.14

Profile (mm)	Fixation points	Ceiling Kit to order
1000 / 1500	2	1
2000 / 2500	3	2
3000	4	2

End caps. To be ordered separately.
2 unit kit.

Tapas. Se deben pedir por separado. Kit de 2 unidades.



06.5008.14


Drivers / Equipos

References shared with surface version. Please see next page.
Referencias compartidas con versión de superficie. Ver página siguiente.



Remote Drivers

SURFACE INSTALLATION





Profiles

Electromechanical profile for surface-mounting, available in lengths from 1m to 3m.
A version compatible with 'On Board Dimmer' and Casambi light fixtures is available. Version compatible with controllable lights such as DALI and 1-10V systems. Corners, connectors and accessories common for the two profile versions.
Feed connector, intermediated connector, end-caps and attachment accessories to be ordered separately.
Mechanical 90° corners available in the same plane (symmetrical element for left and right corner) and 90° symmetrical internal corners in a different plane.
Intermediate connectors to be ordered separately if electrical continuity on corners is required.
Corners do not admit installation of spots.

Perfiles

Perfil electro-mecánico para instalaciones en superficie o suspendidas, con longitudes de 1m a 3m.
Disponible versión compatible con luminarias "On Board Dimmer" y Casambi.
Versión compatible con luminarias controlables como sistema DALI y 1-10V.
Esquinas, conectores y accesorios comunes para las dos versiones.
Necesario pedir por separado conector de alimentación, conectores intermedios, tapas y accesorios de fijación.
Disponibles esquinas mecánicas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha) y esquinas simétricas de 90° en distinto plano en interior.
Necesario pedir por separado conector flexible para asegurar continuidad eléctrica en las esquinas.
No es posible instalar spots en las esquinas.





L: 1 m / 1,5 m / 2 m / 2,5 m / 3 m

On board dimmer / Casambi	DALI / 1-10V / Casambi
L: 1000 mm	L: 1000 mm
06.5060.40	06.5010.40
06.5060.05	06.5010.05
06.5060.14	06.5010.14
L: 1500 mm	L: 1500 mm
06.5061.40	06.5011.40
06.5061.05	06.5011.05
06.5061.14	06.5011.14
L: 2000 mm	L: 2000 mm
06.5062.40	06.5012.40
06.5062.05	06.5012.05
06.5062.14	06.5012.14
L: 2500 mm	L: 2500 mm
06.5063.40	06.5013.40
06.5063.05	06.5013.05
06.5063.14	06.5013.14
L: 3000 mm	L: 3000 mm
06.5064.40	06.5014.40
06.5064.14	06.5014.14

THE TRACKING MAGNET SURFACE/SUSPENSION — PROFILES

Surface

Kit Surface Bracket. Kit de sujeción a techo.

Profile (mm)	Fixation points	Ceiling Kit to order
1000 / 1500 / 2000	2	1
2500	3	2
3000	4	2




Surface
08.0615.00

Surface / Suspension

90° mechanical corner.
To create electrical continuity, order with the flexible intermediate connector.

Esquina mecánica 90°.
Para crear continuidad eléctrica pedir con el conector intermedio flexible.






06.5015.40
06.5015.05
06.5015.14

Inner mechanical corner.
Only for surface version.

Esquina mecánica interior.
Solo para versión surface.






06.5016.40
06.5016.05
06.5016.14

Feed connector.

Conector de alimentación.






08.0611.14

Intermediate connector.


Conector intermedio.





Straight
08.0612.14





Flexible/Electrical corner
08.0614.14

End caps. To be ordered separately.
2 unit kit.

Tapas. Se deben pedir por separado. Kit de 2 unidades.




06.5017.40
06.5017.05A
06.5017.14

Drivers / Equipos

LED power supply source for remote installation, 48V/320W. 100/240 Vac.

Fuente de alimentación LED para instalación remota, 48V/320W. 100/240 Vac.






*60.8919

LED power supply source for remote installation, 110Vac-135W / 220Vac-200W.

Fuente de alimentación LED para instalación remota, 110Vac-135W / 220Vac-200W.






*60.9607

Power Supply Surface Profile.
48V/250W. 220-240 Vac.

Perfil de Superficie con Fuente de Alimentación. 48V/250W. 220-240 Vac.






06.5096.40
06.5096.14

Control dimming box, 1-10V, 24/48V. For remote installation. For transforming passive systems (SINK) into active systems (SOURCE). It must be positioned between the control unit and the track. Important note: Maximum of 25 light modules.

Caja de control dimable 1-10V, 24/48V. Para instalación remota. Para transformar sistemas pasivos (SINK) en activos (SOURCE). Debe ubicarse entre la unidad de control y el carril. Nota importante: Máx. 25 módulos de luz.




DIM 1-10V - 24/48V
08.0613.14A


An active control system (SOURCE) is required and the data bus must be connected directly to the profile. For passive systems (SINK), a Dimming BOX Control unit is required (located between the control unit and the profile). / Es necesario un sistema de control activo (SOURCE) y conectar el bus de datos de control directamente al perfil. Para sistemas pasivos (SINK), es necesaria la unidad Control Dimming BOX (ubicada entre la unidad de control y el carril).

* For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source. / Para el dimensionado de la instalación mantener un margen de seguridad de un 15% de la potencia máxima de la fuente de alimentación LED.

SUSPENSION DOWN INSTALLATION



Suspension Kits. How to Order



Profiles 1000 / 1500 / 2000 Profiles 2500 Profiles 3000

Profile (mm)	Fixation points	Kits to order
1000 / 1500 / 2000	2	1A
2500	3	1A + 1B
3000	4	1A + 2B

A Kit suspension Bracket
B Intermediate Suspension Kit
(*) Suspension Cable/Rod must be ordered separately

Profiles & Drivers / Perfiles y equipos

References shared with surface version. Please see previous page.
Referencias compartidas con versión de superficie. Ver página anterior.


Profile


90° Corner


End Cap


Feed Unit





Intermediate Connector


Flexible Corner Connector




Remote Drivers

Accessories / Accesorios

Suspension Down


Surface power supply with 320W / 48Vdc driver included. 4-meter, 4-pole transparent cable included. Not suitable for installations with suspension rods. For 1-10V control, use only active signals.	Caja de alimentación de superficie con equipo incluido 320W / 48Vdc. Cable transparente de 4 polos y 4m incluido. No válido para instalaciones con varillas de suspensión. Para control 1-10V usar solo señales activas.		☐ 08.0600.40 ■ 08.0600.14
4-pole, 0.75 mm² section, 4-meter long, transparent power cable. To use with remote drivers.	Cable de alimentación transparente de 4 polos, 0,75 mm² de sección y 4m de longitud. Para usar con drivers remotos.		06.0157.00
Kit Surface Bracket.	Kit de sujeción a techo.		 Suspension 08.0616.00

Suspension Down / Up & Down

Intermediate suspension kit for joining profiles. It includes the electrical connection of the upper part. An intermediate connector is necessary. It must be ordered separately. Steel cable not included.	Kit de suspensión intermedio para unión de perfiles. Incluye la conexión eléctrica de la parte superior. Necesario conector intermedio, pedir por separado. Cable de acero no incluido.	 	■ 08.0627.00
1 m suspension rod with ceiling rose. M6 thread. Not applicable with a Surface power box.*	Varilla de suspensión de 1 m con rosetón con fileteado m6. No aplicable con caja de alimentación de superficie.*		☐ 60.3014.11 ■ 60.3014.14
1m suspension rod extension set m6 thread.*	Alargo para varilla de suspensión de 1 m con fileteado m6.*		☐ 60.3097.11 ■ 60.3097.14
A 4-meter steel suspension cable is recommended if the structure includes one or more angles, since in these structures the track does not tilt even if the weight of the luminaries is not balanced.	Cable de acero de suspensión de 4 m, recomendado si la estructura incluye una o más esquinas, ya que en estas estructuras el carril no se inclina, aunque no se equilibre el peso de las luminarias.		08.8634.00
Surface rose. Equipment, power cable and suspension cable not included. They must be ordered separately. Not suitable for installations with suspension rods.	Rosetón de alimentación de superficie. Equipo, cable de alimentación y de suspensión no incluidos, pedir por separado. No válido para instalaciones con varillas de suspensión.		☐ 08.8883.40A ■ 08.8883.14A
Recessed power supply rose. Equipment, power cable and suspension cable not included. They must be ordered separately. Not suitable for installations with suspension rods.	Rosetón de alimentación empotrado. Equipo, cable de alimentación y de suspensión no incluidos, pedir por separado. No válido para instalaciones con varillas de suspensión.		☐ 08.8889.40 ■ 08.8889.14

* Rigid rod to avoid the profile from tilting (rectilinear structures without corners) or to be installed in places where a more rigid fixing system is required.
* Varillas rígidas para evitar la inclinación del perfil (estructuras rectilíneas sin esquinas) o para instalaciones donde se requiere sistema de fijación más rígido.

SUSPENSION UP&DOWN INSTALLATION





Profiles

Electrical/mechanical profile for suspended installations.
The linear elements in the Up&Down version include indirect LED lighting in the upper part of the profile.
A version compatible with 'On Board Dimmer' and Casambi light fixtures is available. Version compatible with controllable lights such as DALI and 1-10V systems.
The profiles cannot be cut. The end caps must be ordered separately.
Suspension accessories (steel cable and rods) should be ordered separately.
90° corners available in the same plan (symmetrical element for left and right corners).
The corners do not have indirect lighting. Indirect lighting can be controlled either through the same circuit than direct lighting or independently.
The Up&Down version can be controlled independently via DALI.

Perfiles

Perfil electro-mecánico para instalaciones suspendidas.
Los elementos lineales en versión Up&Down incluyen iluminación LED indirecta en la parte superior del perfil.
Disponible versión compatible con luminarias "On Board Dimmer" y Casambi.
Versión compatible con luminarias controlables como sistema DALI y 1-10V.
Los perfiles no se pueden cortar. Las tapas se deben pedir por separado.
Accesorios de suspensión (cable de acero y varillas) se deben pedir por separado.
Disponibles esquinas de 90° en el mismo plano (elemento simétrico para esquina izquierda y derecha).
Las esquinas no llevan iluminación indirecta. La luz indirecta se puede controlar a través del mismo circuito que la luz directa o de forma independiente.
La versión Up&Down puede ser controlada independientemente vía DALI.





Beam Angle:	81°	
h(m)	E(lx)	D(m)
1	195	1.72
2	49	3.44
3	22	5.15
4	12	6.87
5	8	8.59

L: 1 m / 1,5 m / 2 m / 2,5 m / 3 m

Top LED 6,5W/m Up - 630 lm/m Up - 3000K/CRI 90

On board dimmer / Casambi	DALI / 1-10V / Casambi
L: 1000 mm	L: 1000 mm
06.5070.40	06.5020.40
06.5070.05	06.5020.05
06.5070.14	06.5020.14
L: 1500 mm	L: 1500 mm
06.5071.40	06.5021.40
06.5071.05	06.5021.05
06.5071.14	06.5021.14
L: 2000 mm	L: 2000 mm
06.5072.40	06.5022.40
06.5072.05	06.5022.05
06.5072.14	06.5022.14
L: 2500 mm	L: 2500 mm
06.5073.40	06.5023.40
06.5073.05	06.5023.05
06.5073.14	06.5023.14
L: 3000 mm	L: 3000 mm
06.5074.40	06.5024.40
06.5074.14	06.5024.14

Accessories & Drivers / Accesorios y equipos

Shared references with Down suspension version. Please see previous page.
Referencias compartidas con versión suspension Down. Ver página anterior.


Surface Rose


Recessed Power Supply Rose


Suspension Cable


Suspension Rod

Suspension Rod Extension


Intermediate Suspension Kit

References shared with surface version. Please see page.
Referencias compartidas con versión de superficie. Ver página.


Intermediate Connector


Flexible Corner Connector


Remote Drivers

Accessories / Accesorios

90° mechanical angle.
Two end suspension connections included. Steel cable not included. No lighting on the upper part. Upper part connections included.

Esquina mecánica 90°.
Dos conexiones finales de suspensión incluidas. Cable de acero no incluido. Sin iluminación en la parte superior. Conexiones de la parte superior incluidas.



06.5025.40
06.5025.05
06.5025.14

End caps. To be ordered separately.
2 unit kit.


Tapas. Se deben pedir por separado.
Kit de 2 unidades.



06.5026.40
06.5026.05A
06.5026.14

Feed Unit Kit. Includes two suspension accessories for the profile ends and a 6-pole and 4-meter long electrical cable. Steel cable not included. Central suspension accessories are included in the profile.


Feed Unit Kit. Incluye dos accesorios de suspensión para los extremos del perfil y cable eléctrico de 6 polos y 4 m. Cable de acero no incluido. Los accesorios de suspensión centrales vienen incluidos en el perfil.



08.0626.00

Surface power supply with driver included 320W / 48Vdc. Steel and electric cables not included. Not valid for installation with suspension rods. DALI / 1-10V / 0-10V / No dim.

Caja de alimentación de superficie con equipo incluido 320W / 48Vdc. Cables de acero y eléctricos no incluidos. No válido para instalación con varillas de suspensión. DALI / 1-10V / 0-10V / No dim.




1-10V
08.0631.40A
08.0631.14A
Dali Version
08.0632.40A
08.0632.14A

Remote Dimmers Accessories

Dimmable Dali control unit for 12-24-48V LED modules. Power supply not included. For controlling indirect lighting (UP).

Unidad de control dimable Dali para la regulación de módulos LED, para equipos de 12-24-48V. No incluye fuente de alimentación. Para control de la iluminación indirecta (UP).






Dali · Push
Max. 10A
60.9678A

1-10V Push 48V PWM Uplight dimmer for controlling indirect lighting (UP).


Uplight dimmer 1-10V Push 48V PWM para control de la iluminación indirecta (UP).





60.9395

Suspension Kits Up & Down. How to Order



Profiles 1000 / 1500 Profiles 2000 / 2500 Profiles 3000

Profile (mm)	Fixation points	Kits to order
1000 / 1500	2	1D
2000 / 2500	3	1D
3000	4	1D


D Feed Unit Kit (A+C)
B Intermediate Suspension Kit. Included in Up & Down profiles
(*) Suspension Cable/Rod must be ordered separately


• Can I feed a structure directly from a corner?
Yes. One or two power connectors must be used for linear profiles along with the corner, depending on whether you want to power just one of the profiles connected to the corner or both profiles.

• Can I cut a profile?
Yes, profiles can be cut to the desired size, except for the Up & Down version. The electrical continuity is done with the intermediate connector. If you need a new power cable after cutting, you must drill the power cable's pass-through hole in the area free of graphite tracks reserved for that purpose and use a feed connector, you should never drill through the graphite tracks.

• ¿Puedo alimentar una estructura directamente desde una esquina?
Sí, hay que usar uno o dos conectores de alimentación para los perfiles lineales junto a la esquina, en función de si se quiere alimentar solo uno de los perfiles conectados al corner o los dos.

• ¿Puedo cortar un perfil?
Sí, los perfiles se pueden cortar a la medida deseada, salvo en las versiones Up&Down. Siempre hay que cortar respetando el espacio reservado para el paso del cable de alimentación. La continuidad eléctrica se realiza con el conector intermedio. En caso de necesitar una nueva alimentación tras el corte, se debe taladrar para el paso del cable de alimentación, en la zona sin pistas de grafito reservada a tal efecto y usar un conector de alimentación, nunca se debe taladrar a través de las pistas de grafito.





• What is the maximum distance allowed between the driver and the profile?
With the recommended power sources, the maximum distance permitted is:
. Ø1.5 mm cable: 3 m
. Ø2.5 mm cable: 5 m

• What is the maximum length that can be fed with one power supply?
The maximum length of a profile that can be fed with a power supply is 20 meters or the resulting distance after 7 interconnections including cuts.


• Can I use a different, less powerful power supply?
All the information published on our website, catalogue and installation instructions meet the tests executed with the power sources recommended for our products. It must be a 48V power source with a maximum power of 320W.

• ¿Cuál es la distancia máxima permitida entre la fuente de alimentación y el perfil?
Con las fuentes de alimentación recomendadas, la distancia máxima permitida es:
. Cable de Ø1,5 mm: 3 m
. Cable de Ø2,5 mm: 5 m

• ¿Cuál es la longitud máxima que se puede alimentar con una fuente de alimentación en una estructura?
La longitud máxima de un perfil que puede alimentarse con una fuente de alimentación es 20 metros o la distancia resultante después de 7 interconexiones incluyendo los cortes.

• ¿Puedo utilizar una fuente de alimentación diferente - menos potente?
Toda la información publicada en nuestra web, catálogo e instrucciones de instalación se ajusta a los tests realizados con las fuentes de alimentación recomendadas para nuestros productos. Debe ser una fuente de alimentación de 48V con una potencia máxima de 320W.


Up&Down Connection Scheme / Esquema de Conexión Up&Down



Light Stripe


Top LED 20W/m - 1859 lm/m - 2700K/CRI 90 / 20W/m - 1967 lm/m - 3000K/CRI 90






Diffused LED light module to be installed in The Tracking Magnet System. Opal end covers not included. They must be ordered separately (08.0125.00 - two units included).
For wireless lighting control, choose integrated Casambi versions.

Módulo de iluminación LED de luz difusa para ser instalado en el sistema The Tracking Magnet. Tapas finales opales no incluidas, pedir por separado (08.0125.00 - incluye dos unidades).
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.



2700K
L: 300 mm - 6W - 558lm
On board dimmer
03.8000.14
*Dali 2
03.8000.14.DA
*1-10V
03.8000.14.1V
**Casambi
03.8000.14.CB




Luminous flux luminaire
191 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	68	2.80
2	17	5.59
3	8	8.39
4	4	11.18
5	3	13.98

3000K
L: 300 mm - 6W - 590lm
On board dimmer
03.8005.14
*Dali 2
03.8005.14.DA
*1-10V
03.8005.14.1V
**Casambi
03.8005.14.CB




Luminous flux luminaire
202 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	72	2.80
2	18	5.59
3	8	8.39
4	5	11.18
5	3	13.98

2700K
L: 600 mm - 12W - 1115lm
On board dimmer
03.8001.14
*Dali 2
03.8001.14.DA
*1-10V
03.8001.14.1V
**Casambi
03.8001.14.CB




Luminous flux luminaire
383 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	137	2.80
2	34	5.59
3	15	8.39
4	9	11.18
5	5	13.98

3000K
L: 600 mm - 12W - 1180lm
On board dimmer
03.8006.14
*Dali 2
03.8006.14.DA
*1-10V
03.8006.14.1V
**Casambi
03.8006.14.CB




Luminous flux luminaire
405 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	144	2.80
2	36	5.59
3	16	8.39
4	9	11.18
5	6	13.98

2700K
L: 900 mm - 18W - 1673lm
On board dimmer
03.8002.14
*Dali 2
03.8002.14.DA
*1-10V
03.8002.14.1V
**Casambi
03.8002.14.CB




Luminous flux luminaire
574 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	205	2.80
2	51	5.59
3	23	8.39
4	13	11.18
5	8	13.98

3000K
L: 900 mm - 18W - 1770lm
On board dimmer
03.8007.14
*Dali 2
03.8007.14.DA
*1-10V
03.8007.14.1V
**Casambi
03.8007.14.CB




Luminous flux luminaire
607 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	217	2.80
2	54	5.59
3	24	8.39
4	14	11.18
5	9	13.98

2700K
L: 1200 mm - 24W - 2230lm
On board dimmer
03.8003.14
*Dali 2
03.8003.14.DA
*1-10V
03.8003.14.1V
**Casambi
03.8003.14.CB




Luminous flux luminaire
766 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	273	2.80
2	68	5.59
3	30	8.39
4	17	11.18
5	11	13.98

3000K
L: 1200 mm - 24W - 2360lm
On board dimmer
03.8008.14
*Dali 2
03.8008.14.DA
*1-10V
03.8008.14.1V
**Casambi
03.8008.14.CB




Luminous flux luminaire
809 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	289	2.80
2	72	5.59
3	32	8.39
4	18	11.18
5	12	13.98

2700K
L: 1500 mm - 30W - 2788lm
On board dimmer
03.8004.14
*Dali 2
03.8004.14.DA
*1-10V
03.8004.14.1V
**Casambi
03.8004.14.CB




Luminous flux luminaire
957 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	341	2.80
2	85	5.59
3	38	8.39
4	21	11.18
5	14	13.98

3000K
L: 1500 mm - 30W - 2950lm
On board dimmer
03.8009.14
*Dali 2
03.8009.14.DA
*1-10V
03.8009.14.1V
**Casambi
03.8009.14.CB



Luminous flux luminaire
1012 lm

Beam Angle: 109°

h(m)	E(lx)	D(m)
1	361	2.80
2	90	5.59
3	40	8.39
4	23	11.18
5	14	13.98


* Only compatible with DALI, 1-10V profile version / Compatible solo con perfil en versión DALI, 1-10V.


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Spot 50

Power LED 3,5W - 286 lm - 2700K/CRI 90 / 3,5W - 307 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Tracking Magnet System.
For wireless lighting control, choose integrated Casambi versions.

Accessories included (honeycomb and screening crosspiece) except for the chrome finish.

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet. Para el control inalámbrico de las luminarias seleccionar versiones Casambi.


Accesorios incluidos (honeycomb y cruceta de apantallamiento), excepto para el acabado cromo.

2700K
On board dimmer
- 03.8032.40A
- 03.8032.05B
- 03.8032.14A

*Dali 2
- 03.8032.40ADA
- 03.8032.05BDA
- 03.8032.14ADA

*1-10V
- 03.8032.40A1V
- 03.8032.05B1V
- 03.8032.14A1V

**Casambi
- 03.8032.40ACB
- 03.8032.05BCB
- 03.8032.14ACB



Luminous flux luminaire 205 lm (EXTREME CUT OFF)

Beam Angle: 26°


h(m)	E(lx)	D(m)
1	977	0.47
2	244	0.94
3	109	1.41
4	61	1.88
5	39	2.35

3000K
On board dimmer
- 03.8033.40A
- 03.8033.05B
- 03.8033.14A

*Dali 2
- 03.8033.40ADA
- 03.8033.05BDA
- 03.8033.14ADA

*1-10V
- 03.8033.40A1V
- 03.8033.05B1V
- 03.8033.14A1V

**Casambi
- 03.8033.40ACB
- 03.8033.05BCB
- 03.8033.14ACB



Luminous flux luminaire 212 lm (EXTREME CUT OFF)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1012	0.47
2	253	0.94
3	112	1.41
4	63	1.88
5	40	2.35


* Only compatible with DALI, 1-10V profile version / Compatible solo con perfil en versión DALI, 1-10V.


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Spot 90

Power LED 8,5W - 610 lm - 2700K/CRI 90 / 8,5W - 656 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Tracking Magnet System.
For wireless lighting control, choose integrated Casambi versions.

Accessories included (honeycomb and screening crosspiece) except for the chrome finish.

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Accesorios incluidos (honeycomb y cruceta de apantallamiento), excepto para el acabado cromo.


2700K
On board dimmer
- 03.8042.40A
- 03.8042.05B
- 03.8042.14A

*Dali 2
- 03.8042.40ADA
- 03.8042.05BDA
- 03.8042.14ADA

*1-10V
- 03.8042.40A1V
- 03.8042.05B1V
- 03.8042.14A1V

**Casambi
- 03.8042.40ACB
- 03.8042.05BCB
- 03.8042.14ACB

14° SPOT



Luminous flux luminaire 428 lm [EXTREME CUT OFF]

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5601	0.25
2	1400	0.49
3	622	0.74
4	350	0.98
5	224	1.23


3000K
On board dimmer
- 03.8043.40A
- 03.8043.05B
- 03.8043.14A

*Dali 2
- 03.8043.40ADA
- 03.8043.05BDA
- 03.8043.14ADA

*1-10V
- 03.8043.40A1V
- 03.8043.05B1V
- 03.8043.14A1V

**Casambi
- 03.8043.40ACB
- 03.8043.05BCB
- 03.8043.14ACB

14° SPOT



Luminous flux luminaire 443 lm [EXTREME CUT OFF]

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5805	0.25
2	1451	0.49
3	645	0.74
4	363	0.98
5	232	1.23


2700K
On board dimmer
- 03.8044.40A
- 03.8044.05B
- 03.8044.14A

*Dali 2
- 03.8044.40ADA
- 03.8044.05BDA
- 03.8044.14ADA

*1-10V
- 03.8044.40A1V
- 03.8044.05B1V
- 03.8044.14A1V

**Casambi
- 03.8044.40ACB
- 03.8044.05BCB
- 03.8044.14ACB

22° MEDIUM



Luminous flux luminaire 392 lm [EXTREME CUT OFF]

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	2319	0.38
2	580	0.77
3	258	1.15
4	145	1.54
5	93	1.92


3000K
On board dimmer
- 03.8045.40A
- 03.8045.05B
- 03.8045.14A

*Dali 2
- 03.8045.40ADA
- 03.8045.05BDA
- 03.8045.14ADA

*1-10V
- 03.8045.40A1V
- 03.8045.05B1V
- 03.8045.14A1V

**Casambi
- 03.8045.40ACB
- 03.8045.05BCB
- 03.8045.14ACB

22° MEDIUM



Luminous flux luminaire 406 lm [EXTREME CUT OFF]

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	2403	0.38
2	601	0.77
3	267	1.15
4	150	1.54
5	96	1.92


* Only compatible with DALI, 1-10V profile version / Compatible solo con perfil en versión DALI, 1-10V.


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Spot 120

Power LED 12W - 724 lm - 2700K/CRI 90 / 12W - 779 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Tracking Magnet System.
For wireless lighting control, choose integrated Casambi versions.

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

2700K

On board dimmer

- 03.8052.40A
- 03.8052.05B
- 03.8052.14A

*Dali 2

- 03.8052.40ADA
- 03.8052.05BDA
- 03.8052.14ADA


*1-10V

- 03.8052.40A1V
- 03.8052.05B1V
- 03.8052.14A1V

**Casambi

- 03.8052.40ACB
- 03.8052.05BCB
- 03.8052.14ACB

11° SPOT



Luminous flux luminaire
539 lm (EXTREME CUT OFF)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	11417	0.19
2	2854	0.37
3	1269	0.56
4	714	0.75
5	457	0.93

3000K

On board dimmer

- 03.8053.40A
- 03.8053.05B
- 03.8053.14A

*Dali 2

- 03.8053.40ADA
- 03.8053.05BDA
- 03.8053.14ADA


*1-10V

- 03.8053.40A1V
- 03.8053.05B1V
- 03.8053.14A1V

**Casambi

- 03.8053.40ACB
- 03.8053.05BCB
- 03.8053.14ACB

11° SPOT



Luminous flux luminaire
558 lm (EXTREME CUT OFF)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	11834	0.19
2	2958	0.37
3	1315	0.56
4	740	0.75
5	473	0.93

2700K

On board dimmer

- 03.8054.40A
- 03.8054.05B
- 03.8054.14A

*Dali 2

- 03.8054.40ADA
- 03.8054.05BDA
- 03.8054.14ADA


*1-10V

- 03.8054.40A1V
- 03.8054.05B1V
- 03.8054.14A1V

**Casambi

- 03.8054.40ACB
- 03.8054.05BCB
- 03.8054.14ACB

17° MEDIUM



Luminous flux luminaire
487 lm (EXTREME CUT OFF)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	3865	0.29
2	966	0.59
3	429	0.88
4	242	1.18
5	155	1.47

3000K

On board dimmer

- 03.8055.40A
- 03.8055.05B
- 03.8055.14A

*Dali 2

- 03.8055.40ADA
- 03.8055.05BDA
- 03.8055.14ADA


*1-10V

- 03.8055.40A1V
- 03.8055.05B1V
- 03.8055.14A1V

**Casambi

- 03.8055.40ACB
- 03.8055.05BCB
- 03.8055.14ACB

17° MEDIUM



Luminous flux luminaire
505 lm (EXTREME CUT OFF)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	4006	0.29
2	1001	0.59
3	445	0.88
4	250	1.18
5	160	1.47


* Only compatible with DALI, 1-10V profile version / Compatible solo con perfil en versión DALI, 1-10V.


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Spot 120

LED Array 12,5W - 1075 lm - 2700K/CRI 90 / 12,5W - 1138 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Tracking Magnet System.
For wireless lighting control, choose integrated Casambi versions.

Accessories included (honeycomb and screening crosspiece) except for the chrome finish.

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Accesorios incluidos (honeycomb y cruceta de apantallamiento), excepto para el acabado cromo.


2700K
On board dimmer
- 03.8154.40
- 03.8154.05A
- 03.8154.14

*Dali 2
- 03.8154.40.DA
- 03.8154.05ADA
- 03.8154.14.DA

*1-10V
- 03.8154.40.1V
- 03.8154.05A1V
- 03.8154.14.1V

**Casambi
- 03.8154.40.CB
- 03.8154.05ACB
- 03.8154.14.CB

17° MEDIUM



Luminous flux luminaire 654 lm

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	4547	0.31
2	1137	0.61
3	505	0.92
4	284	1.23
5	182	1.53


3000K
On board dimmer
- 03.8155.40
- 03.8155.05A
- 03.8155.14

*Dali 2
- 03.8155.40.DA
- 03.8155.05ADA
- 03.8155.14.DA

*1-10V
- 03.8155.40.1V
- 03.8155.05A1V
- 03.8155.14.1V

**Casambi
- 03.8155.40.CB
- 03.8155.05ACB
- 03.8155.14.CB

17° MEDIUM



Luminous flux luminaire 687 lm

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	4780	0.31
2	1195	0.61
3	531	0.92
4	299	1.23
5	191	1.53


2700K
On board dimmer
- 03.8156.40
- 03.8156.05A
- 03.8156.14

*Dali 2
- 03.8156.40.DA
- 03.8156.05ADA
- 03.8156.14.DA

*1-10V
- 03.8156.40.1V
- 03.8156.05A1V
- 03.8156.14.1V

**Casambi
- 03.8156.40.CB
- 03.8156.05ACB
- 03.8156.14.CB

40° FLOOD



Luminous flux luminaire 599 lm

Beam Angle: 40°

h(m)	E(lx)	D(m)
1	1367	0.73
2	342	1.45
3	152	2.18
4	85	2.91
5	55	3.64


3000K
On board dimmer
- 03.8157.40
- 03.8157.05A
- 03.8157.14

*Dali 2
- 03.8157.40.DA
- 03.8157.05ADA
- 03.8157.14.DA

*1-10V
- 03.8157.40.1V
- 03.8157.05A1V
- 03.8157.14.1V

**Casambi
- 03.8157.40.CB
- 03.8157.05ACB
- 03.8157.14.CB

40° FLOOD



Luminous flux luminaire 629 lm

Beam Angle: 40°

h(m)	E(lx)	D(m)
1	1437	0.73
2	359	1.45
3	160	2.18
4	90	2.91
5	57	3.64


* Only compatible with DALI, 1-10V profile version / Compatible solo con perfil en versión DALI, 1-10V.


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Spot 150

LED Array 22,5W - 2411 lm - 2700K/CRI 90 / 22,5W - 2569 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Tracking Magnet System.
For wireless lighting control, choose integrated Casambi versions.

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.


2700K
On board dimmer
- 03.8072.40A
- 03.8072.05B
- 03.8072.14A

*Dali 2
- 03.8072.40ADA
- 03.8072.05BDA
- 03.8072.14ADA

*1-10V
- 03.8072.40A1V
- 03.8072.05B1V
- 03.8072.14A1V

**Casambi
- 03.8072.40ACB
- 03.8072.05BCB
- 03.8072.14ACB

21° SPOT



Luminous flux luminaire
1818 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	11239	0.37
2	2810	0.74
3	1249	1.11
4	702	1.48
5	450	1.85


3000K
On board dimmer
- 03.8073.40A
- 03.8073.05B
- 03.8073.14A

*Dali 2
- 03.8073.40ADA
- 03.8073.05BDA
- 03.8073.14ADA

*1-10V
- 03.8073.40A1V
- 03.8073.05B1V
- 03.8073.14A1V

**Casambi
- 03.8073.40ACB
- 03.8073.05BCB
- 03.8073.14ACB

21° SPOT



Luminous flux luminaire
1937 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	11975	0.37
2	2994	0.74
3	1331	1.11
4	748	1.48
5	479	1.85


2700K
On board dimmer
- 03.8074.40A
- 03.8074.05B
- 03.8074.14A

*Dali 2
- 03.8074.40ADA
- 03.8074.05BDA
- 03.8074.14ADA

*1-10V
- 03.8074.40A1V
- 03.8074.05B1V
- 03.8074.14A1V

**Casambi
- 03.8074.40ACB
- 03.8074.05BCB
- 03.8074.14ACB

27° MEDIUM



Luminous flux luminaire
1564 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	7167	0.49
2	1792	0.98
3	796	1.47
4	448	1.96
5	287	2.44


3000K
On board dimmer
- 03.8075.40A
- 03.8075.05B
- 03.8075.14A

*Dali 2
- 03.8075.40ADA
- 03.8075.05BDA
- 03.8075.14ADA

*1-10V
- 03.8075.40A1V
- 03.8075.05B1V
- 03.8075.14A1V

**Casambi
- 03.8075.40ACB
- 03.8075.05BCB
- 03.8075.14ACB

27° MEDIUM



Luminous flux luminaire
1667 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	7638	0.49
2	1910	0.98
3	849	1.47
4	477	1.96
5	306	2.44


2700K
On board dimmer
- 03.8076.40A
- 03.8076.05B
- 03.8076.14A

*Dali 2
- 03.8076.40ADA
- 03.8076.05BDA
- 03.8076.14ADA

*1-10V
- 03.8076.40A1V
- 03.8076.05B1V
- 03.8076.14A1V

**Casambi
- 03.8076.40ACB
- 03.8076.05BCB
- 03.8076.14ACB

36° FLOOD



Luminous flux luminaire
1569 lm

Beam Angle: 36°

h(m)	E(lx)	D(m)
1	4586	0.64
2	1146	1.28
3	510	1.92
4	287	2.56
5	183	3.20


3000K
On board dimmer
- 03.8077.40A
- 03.8077.05B
- 03.8077.14A

*Dali 2
- 03.8077.40ADA
- 03.8077.05BDA
- 03.8077.14ADA

*1-10V
- 03.8077.40A1V
- 03.8077.05B1V
- 03.8077.14A1V

**Casambi
- 03.8077.40ACB
- 03.8077.05BCB
- 03.8077.14ACB

36° FLOOD



Luminous flux luminaire
1672 lm

Beam Angle: 36°

h(m)	E(lx)	D(m)
1	4887	0.64
2	1222	1.28
3	543	1.92
4	305	2.56
5	195	3.20

* Only compatible with DALI, 1-10V profile version / Compatible solo con perfil en versión DALI, 1-10V.

** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Accesorios / Accessories

Spot 150***


Screening crosspiece.	Cruceta de apantallamiento.		08.8429.00
Elliptical lens.	Lente elíptica.		08.8431.00
Flood lens.	Lente flood.		08.8432.00
Honeycomb.	Honeycomb.		08.8428.00
Snoot shielding cone.	Cono apantallador.		08.0526.00 08.0526.40 08.0526.BW


*** Except chrome finish

Anthony Spot Track By Antonio Citterio

LED Array 16,5W - 1620 lm - 2700K/CRI 90 / 16,5W - 1730 lm - 3000K/CRI 90







Accent lighting LED module to be installed in The Tracking Magnet System.
For wireless lighting control, choose integrated Casambi versions.

See available accessories.

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Ver accesorios disponibles.


2700K
On board dimmer
- 03.8025.40
- 03.8025.05A
- 03.8025.14

*Dali 2
- 03.8025.40.DA
- 03.8025.05ADA
- 03.8025.14.DA

*1-10V
- 03.8025.40.1V
- 03.8025.05A1V
- 03.8025.14.1V

**Casambi
- 03.8025.40.CB
- 03.8025.05ACB
- 03.8025.14.CB

15° SPOT



Luminous flux luminaire
1241 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	12442	0.27
2	3110	0.54
3	1382	0.81
4	778	1.07
5	498	1.34


3000K
On board dimmer
- 03.8027.40
- 03.8027.05A
- 03.8027.14

*Dali 2
- 03.8027.40.DA
- 03.8027.05ADA
- 03.8027.14.DA

*1-10V
- 03.8027.40.1V
- 03.8027.05A1V
- 03.8027.14.1V

**Casambi
- 03.8027.40.CB
- 03.8027.05ACB
- 03.8027.14.CB

15° SPOT



Luminous flux luminaire
1425 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	14285	0.27
2	3571	0.54
3	1587	0.81
4	893	1.07
5	571	1.34


2700K
On board dimmer
- 03.8026.40
- 03.8026.05A
- 03.8026.14

*Dali 2
- 03.8026.40.DA
- 03.8026.05ADA
- 03.8026.14.DA

*1-10V
- 03.8026.40.1V
- 03.8026.05A1V
- 03.8026.14.1V

**Casambi
- 03.8026.40.CB
- 03.8026.05ACB
- 03.8026.14.CB

28° MEDIUM



Luminous flux luminaire
1242 lm

Beam Angle: 28°

h(m)	E(lx)	D(m)
1	5145	0.49
2	1286	0.98
3	572	1.47
4	322	1.97
5	206	2.46


3000K
On board dimmer
- 03.8028.40
- 03.8028.05A
- 03.8028.14

*Dali 2
- 03.8028.40.DA
- 03.8028.05ADA
- 03.8028.14.DA

*1-10V
- 03.8028.40.1V
- 03.8028.05A1V
- 03.8028.14.1V

**Casambi
- 03.8028.40.CB
- 03.8028.05ACB
- 03.8028.14.CB

28° MEDIUM



Luminous flux luminaire
1399 lm

Beam Angle: 28°

h(m)	E(lx)	D(m)
1	5799	0.49
2	1450	0.98
3	644	1.47
4	362	1.97
5	232	2.46

* Only compatible with DALI, 1-10V profile version / Compatible solo con perfil en versión DALI, 1-10V.

** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Accesorios / Accessories


Anthony Spot


Elliptical lens.	Lente elíptica.		08.8418.68A
Honeycomb.	Honeycomb.		08.8419.14A
Flood lens. To obtain flood optics (35º) order Anthony Spot Medium + flood lens.	Lente flood. Para alcanzar óptica flood (35º) pedir Anthony Spot Medium + lente flood.		08.0050.00

Light Shadow Spot 30

Power LED 4,5W - 298 lm - 2700K/CRI 90 / 4,5W - 318 lm - 3000K/CRI 90







LED accent lighting module for installation in The Tracking Magnet system.
For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Spot - 2700K


On board dimmer
- 05.9000.40A
- 05.9000.14A
- 05.9000.ERA
- 05.9000.ESA

Dali 2
- 05.9000.40ADA
- 05.9000.14ADA
- 05.9000.ERADA
- 05.9000.ESADA

1-10V
- 05.9000.40A1V
- 05.9000.14A1V
- 05.9000.ERA1V
- 05.9000.ESA1V

Casambi
- 05.9000.40ACB
- 05.9000.14ACB
- 05.9000.ERACB
- 05.9000.ESACB





Luminous flux luminaire 253 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4044	0.20
2	1011	0.40
3	449	0.60
4	253	0.80
5	162	1.00

Optic Spot - 3000K


On board dimmer
- 05.9005.40A
- 05.9005.14A
- 05.9005.ERA
- 05.9005.ESA

Dali 2
- 05.9005.40ADA
- 05.9005.14ADA
- 05.9005.ERADA
- 05.9005.ESADA

1-10V
- 05.9005.40A1V
- 05.9005.14A1V
- 05.9005.ERA1V
- 05.9005.ESA1V

Casambi
- 05.9005.40ACB
- 05.9005.14ACB
- 05.9005.ERACB
- 05.9005.ESACB





Luminous flux luminaire 270 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4316	0.20
2	1079	0.40
3	480	0.60
4	270	0.80
5	173	1.00

Optic Medium - 2700K


On board dimmer
- 05.9001.40A
- 05.9001.14A
- 05.9001.ERA
- 05.9001.ESA

Dali 2
- 05.9001.40ADA
- 05.9001.14ADA
- 05.9001.ERADA
- 05.9001.ESADA

1-10V
- 05.9001.40A1V
- 05.9001.14A1V
- 05.9001.ERA1V
- 05.9001.ESA1V

Casambi
- 05.9001.40ACB
- 05.9001.14ACB
- 05.9001.ERACB
- 05.9001.ESACB





Luminous flux luminaire 257 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1797	0.39
2	449	0.78
3	200	1.17
4	112	1.56
5	72	1.95

Optic Medium - 3000K


On board dimmer
- 05.9006.40A
- 05.9006.14A
- 05.9006.ERA
- 05.9006.ESA

Dali 2
- 05.9006.40ADA
- 05.9006.14ADA
- 05.9006.ERADA
- 05.9006.ESADA

1-10V
- 05.9006.40A1V
- 05.9006.14A1V
- 05.9006.ERA1V
- 05.9006.ESA1V

Casambi
- 05.9006.40ACB
- 05.9006.14ACB
- 05.9006.ERACB
- 05.9006.ESACB





Luminous flux luminaire 274 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1916	0.39
2	479	0.78
3	213	1.17
4	120	1.56
5	77	1.95

Optic Flood - 2700K

On board dimmer

- 05.9002.40A
- 05.9002.14A
- 05.9002.ERA
- 05.9002.ESA

Dali 2

- 05.9002.40ADA
- 05.9002.14ADA
- 05.9002.ERADA
- 05.9002.ESADA


1-10V

- 05.9002.40A1V
- 05.9002.14A1V
- 05.9002.ERA1V
- 05.9002.ESA1V

Casambi

- 05.9002.40ACB
- 05.9002.14ACB
- 05.9002.ERACB
- 05.9002.ESACB





Luminous flux luminaire
246 lm

Beam Angle:		29°
h(m)	E(lx)	D(m)
1	953	0.52
2	238	1.04
3	106	1.57
4	60	2.09
5	38	2.61

Optic Flood - 3000K

On board dimmer

- 05.9007.40A
- 05.9007.14A
- 05.9007.ERA
- 05.9007.ESA

Dali 2

- 05.9007.40ADA
- 05.9007.14ADA
- 05.9007.ERADA
- 05.9007.ESADA


1-10V

- 05.9007.40A1V
- 05.9007.14A1V
- 05.9007.ERA1V
- 05.9007.ESA1V

Casambi

- 05.9007.40ACB
- 05.9007.14ACB
- 05.9007.ERACB
- 05.9007.ESACB





Luminous flux luminaire
263 lm

Beam Angle:		29°
h(m)	E(lx)	D(m)
1	1019	0.52
2	255	1.04
3	113	1.57
4	64	2.09
5	41	2.61

Optic Wide Flood - 2700K

On board dimmer

- 05.9003.40A
- 05.9003.14A
- 05.9003.ERA
- 05.9003.ESA

Dali 2

- 05.9003.40ADA
- 05.9003.14ADA
- 05.9003.ERADA
- 05.9003.ESADA


1-10V

- 05.9003.40A1V
- 05.9003.14A1V
- 05.9003.ERA1V
- 05.9003.ESA1V

Casambi

- 05.9003.40ACB
- 05.9003.14ACB
- 05.9003.ERACB
- 05.9003.ESACB





Luminous flux luminaire
246 lm

Beam Angle:		43°
h(m)	E(lx)	D(m)
1	524	0.80
2	131	1.59
3	58	2.39
4	33	3.19
5	21	3.99

Optic Wide Flood - 3000K

On board dimmer

- 05.9008.40A
- 05.9008.14A
- 05.9008.ERA
- 05.9008.ESA

Dali 2

- 05.9008.40ADA
- 05.9008.14ADA
- 05.9008.ERADA
- 05.9008.ESADA


1-10V

- 05.9008.40A1V
- 05.9008.14A1V
- 05.9008.ERA1V
- 05.9008.ESA1V

Casambi

- 05.9008.40ACB
- 05.9008.14ACB
- 05.9008.ERACB
- 05.9008.ESACB






Luminous flux luminaire
262 lm


Beam Angle:		43°
h(m)	E(lx)	D(m)
1	559	0.80
2	140	1.59
3	62	2.39
4	35	3.19
5	22	3.99

Light Shadow Spot 45

LED Array 10W - 799 lm - 2700K/CRI 90 / 10W - 844 lm - 3000K/CRI 90







LED accent lighting module for installation in The Tracking Magnet system.
For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Spot - 2700K


On board dimmer
- 05.9030.40
- 05.9030.14
- 05.9030.ER
- 05.9030.ES

Dali 2
- 05.9030.40.DA
- 05.9030.14.DA
- 05.9030.ER.DA
- 05.9030.ES.DA

1-10V
- 05.9030.40.1V
- 05.9030.14.1V
- 05.9030.ER.1V
- 05.9030.ES.1V

Casambi
- 05.9030.40.CB
- 05.9030.14.CB
- 05.9030.ER.CB
- 05.9030.ES.CB





Luminous flux luminaire 650 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8012	0.27
2	2003	0.54
3	890	0.80
4	501	1.07
5	320	1.34

Optic Spot - 3000K


On board dimmer
- 05.9035.40
- 05.9035.14
- 05.9035.ER
- 05.9035.ES

Dali 2
- 05.9035.40.DA
- 05.9035.14.DA
- 05.9035.ER.DA
- 05.9035.ES.DA

1-10V
- 05.9035.40.1V
- 05.9035.14.1V
- 05.9035.ER.1V
- 05.9035.ES.1V

Casambi
- 05.9035.40.CB
- 05.9035.14.CB
- 05.9035.ER.CB
- 05.9035.ES.CB





Luminous flux luminaire 686 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8456	0.27
2	2114	0.54
3	940	0.80
4	528	1.07
5	338	1.34

Optic Medium - 2700K


On board dimmer
- 05.9031.40
- 05.9031.14
- 05.9031.ER
- 05.9031.ES

Dali 2
- 05.9031.40.DA
- 05.9031.14.DA
- 05.9031.ER.DA
- 05.9031.ES.DA

1-10V
- 05.9031.40.1V
- 05.9031.14.1V
- 05.9031.ER.1V
- 05.9031.ES.1V

Casambi
- 05.9031.40.CB
- 05.9031.14.CB
- 05.9031.ER.CB
- 05.9031.ES.CB





Luminous flux luminaire 645 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5163	0.36
2	1291	0.73
3	574	1.09
4	323	1.46
5	207	1.82

Optic Medium - 3000K


On board dimmer
- 05.9036.40
- 05.9036.14
- 05.9036.ER
- 05.9036.ES

Dali 2
- 05.9036.40.DA
- 05.9036.14.DA
- 05.9036.ER.DA
- 05.9036.ES.DA

1-10V
- 05.9036.40.1V
- 05.9036.14.1V
- 05.9036.ER.1V
- 05.9036.ES.1V

Casambi
- 05.9036.40.CB
- 05.9036.14.CB
- 05.9036.ER.CB
- 05.9036.ES.CB





Luminous flux luminaire 682 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5459	0.36
2	1365	0.73
3	607	1.09
4	341	1.46
5	218	1.82

Optic Flood - 2700K

On board dimmer

- 05.9032.40
- 05.9032.14
- 05.9032.ER
- 05.9032.ES

Dali 2

- 05.9032.40.DA
- 05.9032.14.DA
- 05.9032.ER.DA
- 05.9032.ES.DA

1-10V


- 05.9032.40.1V
- 05.9032.14.1V
- 05.9032.ER.1V
- 05.9032.ES.1V

Casambi

- 05.9032.40.CB
- 05.9032.14.CB
- 05.9032.ER.CB
- 05.9032.ES.CB



FLOOD



Luminous flux luminaire
646 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2296	0.56
2	574	1.11
3	255	1.67
4	144	2.22
5	92	2.78

Optic Flood - 3000K

On board dimmer

- 05.9037.40
- 05.9037.14
- 05.9037.ER
- 05.9037.ES

Dali 2

- 05.9037.40.DA
- 05.9037.14.DA
- 05.9037.ER.DA
- 05.9037.ES.DA

1-10V


- 05.9037.40.1V
- 05.9037.14.1V
- 05.9037.ER.1V
- 05.9037.ES.1V

Casambi

- 05.9037.40.CB
- 05.9037.14.CB
- 05.9037.ER.CB
- 05.9037.ES.CB



FLOOD




Luminous flux luminaire
682 lm


Beam Angle: 31°


h(m)	E(lx)	D(m)
1	2424	0.56
2	606	1.11
3	269	1.67
4	152	2.22
5	97	2.78

Light Shadow Spot 60

Super Spot: LED Array 10W - 799 lm - 2700K/CRI 90 / 10W - 844 lm - 3000K/CRI 90
S/M/F/WF: LED Array 20W - 1563 lm - 2700K/CRI 90 / 20W - 1751 lm - 3000K/CRI 90







LED accent lighting module for installation in The Tracking Magnet system.
For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Super Spot - 2700K


On board dimmer
- 05.9060.40
- 05.9060.14
- 05.9060.ER
- 05.9060.ES

Dali 2
- 05.9060.40.DA
- 05.9060.14.DA
- 05.9060.ER.DA
- 05.9060.ES.DA

1-10V
- 05.9060.40.1V
- 05.9060.14.1V
- 05.9060.ER.1V
- 05.9060.ES.1V

Casambi
- 05.9060.40.CB
- 05.9060.14.CB
- 05.9060.ER.CB
- 05.9060.ES.CB





Luminous flux luminaire
765 lm

Beam Angle: 9°

h(m)	E(lx)	D(m)
1	24922	0.16
2	6230	0.32
3	2769	0.48
4	1558	0.64
5	997	0.80

Optic Super Spot - 3000K


On board dimmer
- 05.9065.40
- 05.9065.14
- 05.9065.ER
- 05.9065.ES

Dali 2
- 05.9065.40.DA
- 05.9065.14.DA
- 05.9065.ER.DA
- 05.9065.ES.DA

1-10V
- 05.9065.40.1V
- 05.9065.14.1V
- 05.9065.ER.1V
- 05.9065.ES.1V

Casambi
- 05.9065.40.CB
- 05.9065.14.CB
- 05.9065.ER.CB
- 05.9065.ES.CB





Luminous flux luminaire
808 lm

Beam Angle: 9°

h(m)	E(lx)	D(m)
1	26322	0.16
2	6581	0.32
3	2925	0.48
4	1645	0.64
5	1053	0.80

Optic Spot - 2700K


On board dimmer
- 05.9061.40
- 05.9061.14
- 05.9061.ER
- 05.9061.ES

Dali 2
- 05.9061.40.DA
- 05.9061.14.DA
- 05.9061.ER.DA
- 05.9061.ES.DA

1-10V
- 05.9061.40.1V
- 05.9061.14.1V
- 05.9061.ER.1V
- 05.9061.ES.1V

Casambi
- 05.9061.40.CB
- 05.9061.14.CB
- 05.9061.ER.CB
- 05.9061.ES.CB





Luminous flux luminaire
1251 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	14350	0.27
2	3587	0.54
3	1594	0.81
4	897	1.09
5	574	1.36

Optic Spot - 3000K


On board dimmer
- 05.9066.40
- 05.9066.14
- 05.9066.ER
- 05.9066.ES

Dali 2
- 05.9066.40.DA
- 05.9066.14.DA
- 05.9066.ER.DA
- 05.9066.ES.DA

1-10V
- 05.9066.40.1V
- 05.9066.14.1V
- 05.9066.ER.1V
- 05.9066.ES.1V

Casambi
- 05.9066.40.CB
- 05.9066.14.CB
- 05.9066.ER.CB
- 05.9066.ES.CB





Luminous flux luminaire
1375 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	15772	0.27
2	3943	0.54
3	1752	0.81
4	986	1.09
5	631	1.36

Optic Medium - 2700K

On board dimmer

- 05.9062.40
- 05.9062.14
- 05.9062.ER
- 05.9062.ES

Dali 2

- 05.9062.40.DA
- 05.9062.14.DA
- 05.9062.ER.DA
- 05.9062.ES.DA

1-10V


- 05.9062.40.1V
- 05.9062.14.1V
- 05.9062.ER.1V
- 05.9062.ES.1V

Casambi

- 05.9062.40.CB
- 05.9062.14.CB
- 05.9062.ER.CB
- 05.9062.ES.CB



MEDIUM



Luminous flux luminaire
1298 lm

Beam Angle:	26°
h(m) E(lx)	D(m)
1 7377	0.45
2 1844	0.91
3 820	1.36
4 461	1.82
5 295	2.27

Optic Medium - 3000K

On board dimmer

- 05.9067.40
- 05.9067.14
- 05.9067.ER
- 05.9067.ES

Dali 2

- 05.9067.40.DA
- 05.9067.14.DA
- 05.9067.ER.DA
- 05.9067.ES.DA

1-10V


- 05.9067.40.1V
- 05.9067.14.1V
- 05.9067.ER.1V
- 05.9067.ES.1V

Casambi

- 05.9067.40.CB
- 05.9067.14.CB
- 05.9067.ER.CB
- 05.9067.ES.CB



MEDIUM



Luminous flux luminaire
1427 lm

Beam Angle:	26°
h(m) E(lx)	D(m)
1 8110	0.45
2 2027	0.91
3 901	1.36
4 507	1.82
5 324	2.27

Optic Flood - 2700K

On board dimmer

- 05.9063.40
- 05.9063.14
- 05.9063.ER
- 05.9063.ES

Dali 2

- 05.9063.40.DA
- 05.9063.14.DA
- 05.9063.ER.DA
- 05.9063.ES.DA

1-10V


- 05.9063.40.1V
- 05.9063.14.1V
- 05.9063.ER.1V
- 05.9063.ES.1V

Casambi

- 05.9063.40.CB
- 05.9063.14.CB
- 05.9063.ER.CB
- 05.9063.ES.CB



FLOOD



Luminous flux luminaire
1304 lm

Beam Angle:	33°
h(m) E(lx)	D(m)
1 4472	0.60
2 1118	1.20
3 497	1.80
4 279	2.40
5 179	3.00

Optic Flood - 3000K

On board dimmer

- 05.9068.40
- 05.9068.14
- 05.9068.ER
- 05.9068.ES

Dali 2

- 05.9068.40.DA
- 05.9068.14.DA
- 05.9068.ER.DA
- 05.9068.ES.DA

1-10V


- 05.9068.40.1V
- 05.9068.14.1V
- 05.9068.ER.1V
- 05.9068.ES.1V

Casambi

- 05.9068.40.CB
- 05.9068.14.CB
- 05.9068.ER.CB
- 05.9068.ES.CB



FLOOD





Luminous flux luminaire
1431 lm


Beam Angle:	33°
h(m) E(lx)	D(m)
1 4907	0.60
2 1227	1.20
3 545	1.80
4 307	2.40
5 196	3.00

Light Shadow Spot 60

Super Spot: LED Array 10W - 799 lm - 2700K/CRI 90 / 10W - 844 lm - 3000K/CRI 90
S/M/F/WF: LED Array 20W - 1563 lm - 2700K/CRI 90 / 20W - 1751 lm - 3000K/CRI 90







LED accent lighting module for installation in The Tracking Magnet system.
For wireless control of luminaires, please select Casambi integrated versions.
Accessories available, (honeycomb and CCT dichroic filters).

Módulo de iluminación LED de acento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi integrated.
Accesorios disponibles, (panel de abeja y filtros dicroicos CCT).

Optic Wide Flood - 2700K


On board dimmer
- 05.9064.40
- 05.9064.14
- 05.9064.ER
- 05.9064.ES

Dali 2
- 05.9064.40.DA
- 05.9064.14.DA
- 05.9064.ER.DA
- 05.9064.ES.DA

1-10V
- 05.9064.40.1V
- 05.9064.14.1V
- 05.9064.ER.1V
- 05.9064.ES.1V

Casambi
- 05.9064.40.CB
- 05.9064.14.CB
- 05.9064.ER.CB
- 05.9064.ES.CB





Luminous flux luminaire
1268 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	2761	0.79
2	690	1.59
3	307	2.38
4	173	3.17
5	110	3.97

Optic Wide Flood - 3000K


On board dimmer
- 05.9069.40
- 05.9069.14
- 05.9069.ER
- 05.9069.ES

Dali 2
- 05.9069.40.DA
- 05.9069.14.DA
- 05.9069.ER.DA
- 05.9069.ES.DA

1-10V
- 05.9069.40.1V
- 05.9069.14.1V
- 05.9069.ER.1V
- 05.9069.ES.1V

Casambi
- 05.9069.40.CB
- 05.9069.14.CB
- 05.9069.ER.CB
- 05.9069.ES.CB





Luminous flux luminaire
1390 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	3026	0.79
2	757	1.59
3	336	2.38
4	189	3.17
5	121	3.97

Accesorios / Accessories

Light Shadow Spot 30

Honeycomb	Panel de abeja		08.0790.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0791.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0792.00

Light Shadow Spot 45

Honeycomb	Panel de abeja		08.0793.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0794.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0795.00


Light Shadow Spot 60


Honeycomb	Panel de abeja		Super Spot 08.0175.14
			Spot / Medium / Flood / Wide Flood 08.0176.14
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase Super Spot 2700K >> 3125±75K 3000K >> 3600±75K 08.0796.00
			Spot / Medium / Flood / Wide Flood 2700K >> 3125±75K 3000K >> 3600±75K 08.0798.00
			Decrease Super Spot 2700K >> 2450±75K 3000K >> 2700±75K 08.0797.00
			Spot / Medium / Flood / Wide Flood 2700K >> 2450±75K 3000K >> 2700±75K 08.0799.00

Wallee Designed By Niels Bendtsen

Top LED 10W - 773 lm - 2700K/CRI 90 / 10W - 818 lm - 3000K/CRI 90







Lighting LED module to be installed in The Tracking Magnet System.
For wireless lighting control, choose integrated Casambi versions.

When installing Wallee, it may require a manual adjustment by the client/installer. Find information on how to carry out this adjustment in the instruction sheets.
Only allowed with Tracking Magnet Recessed and horizontal installation.
Includes frame holder up to 5kg.


Módulo de iluminación LED para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.

Al instalar Wallee, puede que requiera un ajuste manual por parte del cliente/instalador. Puede encontrar la información sobre cómo realizar este ajuste en las hojas de instrucciones.
Solo permitido para instalaciones con Tracking Magnet Recessed y en horizontal.
Incluye soporte para cuadros de hasta 5kg.

2700K
On board dimmer
03.8090.40
03.8090.14

*Casambi
03.8090.40.CB
03.8090.14.CB





Luminous flux luminaire
431 lm


Beam Angle: 103°

h(m)	E(lx)	D(m)
1	164	2.50
2	41	5.00
3	18	7.49
4	10	9.99
5	7	12.49

3000K
On board dimmer
03.8091.40
03.8091.14

*Casambi
03.8091.40.CB
03.8091.14.CB





Luminous flux luminaire
446 lm

Beam Angle: 103°


h(m)	E(lx)	D(m)
1	169	2.50
2	42	5.00
3	19	7.49
4	11	9.99
5	7	12.49


* The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Multi Spot Mini

Power LED 7,5W - 635 lm - 2700K/CRI 90 / 7,5W - 650 lm - 3000K/CRI 90







LED lighting module with 14 spotlights and low glare, to be installed in The Tracking Magnet system.
For wireless lighting control, choose integrated Casambi versions.

Módulo de iluminación LED de 14 focos y bajo deslumbramiento para ser instalado en el sistema The Tracking Magnet.
Para el control inalámbrico de las luminarias seleccionar versiones Casambi.


Optic Spot - 2700K

On board dimmer
- ☐ 05.3550.40
- ■ 05.3550.14

Dali 2
- ☐ 05.3550.40.DA
- ■ 05.3550.14.DA

1-10V
- ☐ 05.3550.40.1V
- ■ 05.3550.14.1V

*Casambi
- ☐ 05.3550.40.CB
- ■ 05.3550.14.CB



Luminous flux luminaire
398 lm (EXTREME CUT OFF)

Beam Angle:		15°
h(m)	E(lx)	D(m)
1	3719	0.27
2	930	0.54
3	413	0.81
4	232	1.08
5	149	1.35


Optic Spot - 3000K

On board dimmer
- ☐ 05.3551.40
- ■ 05.3551.14

Dali 2
- ☐ 05.3551.40.DA
- ■ 05.3551.14.DA

1-10V
- ☐ 05.3551.40.1V
- ■ 05.3551.14.1V

*Casambi
- ☐ 05.3551.40.CB
- ■ 05.3551.14.CB



Luminous flux luminaire
405 lm (EXTREME CUT OFF)

Beam Angle:		15°
h(m)	E(lx)	D(m)
1	3783	0.27
2	946	0.54
3	420	0.81
4	236	1.08
5	151	1.35


Optic Medium - 2700K

On board dimmer
- ☐ 05.3552.40
- ■ 05.3552.14

Dali 2
- ☐ 05.3552.40.DA
- ■ 05.3552.14.DA

1-10V
- ☐ 05.3552.40.1V
- ■ 05.3552.14.1V

*Casambi
- ☐ 05.3552.40.CB
- ■ 05.3552.14.CB



Luminous flux luminaire
424 lm (EXTREME CUT OFF)

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	2520	0.36
2	630	0.72
3	280	1.08
4	158	1.44
5	101	1.80


Optic Medium - 3000K

On board dimmer
- ☐ 05.3553.40
- ■ 05.3553.14

Dali 2
- ☐ 05.3553.40.DA
- ■ 05.3553.14.DA

1-10V
- ☐ 05.3553.40.1V
- ■ 05.3553.14.1V

*Casambi
- ☐ 05.3553.40.CB
- ■ 05.3553.14.CB



Luminous flux luminaire
431 lm (EXTREME CUT OFF)

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	2564	0.36
2	641	0.72
3	285	1.08
4	160	1.44
5	103	1.80


Optic Flood - 2700K

On board dimmer
- ☐ 05.3554.40
- ■ 05.3554.14

Dali 2
- ☐ 05.3554.40.DA
- ■ 05.3554.14.DA

1-10V
- ☐ 05.3554.40.1V
- ■ 05.3554.14.1V

*Casambi
- ☐ 05.3554.40.CB
- ■ 05.3554.14.CB



Luminous flux luminaire
391 lm (EXTREME CUT OFF)

Beam Angle:		32°
h(m)	E(lx)	D(m)
1	1086	0.58
2	271	1.15
3	121	1.73
4	68	2.30
5	43	2.88


Optic Flood - 3000K

On board dimmer
- ☐ 05.3555.40
- ■ 05.3555.14

Dali 2
- ☐ 05.3555.40.DA
- ■ 05.3555.14.DA

1-10V
- ☐ 05.3555.40.1V
- ■ 05.3555.14.1V

*Casambi
- ☐ 05.3555.40.CB
- ■ 05.3555.14.CB



Luminous flux luminaire
397 lm (EXTREME CUT OFF)

Beam Angle:		32°
h(m)	E(lx)	D(m)
1	1105	0.58
2	276	1.15
3	123	1.73
4	69	2.30
5	44	2.88


* The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Multifunction Smart Device

Multifunction Smart Device.
Triple functionality 3x1: Casambi signal repeater, light sensor and presence detector.
FLOS Control® by Casambi.

Dispositivo multifunción inteligente.
Triple funcionalidad 3x1: repetidor de señal Casambi, sensor de luz ambiental y detector de presencia.
FLOS Control® by Casambi.







06.1988.40
06.1988.14

Multifunction Smart Device. Triple Functionality 3x1


Repeater



Daylight Sensor



Presence Sensor




▲ Casambi object

NEW

THE TRACKING POWER EVO

DESIGNED BY FLOS ARCHITECTURAL



14 Black
14 Negro

LIGHT MODULES

UT PRO 150



LIGHT SOURCE
LED ARRAY
21W
2524 lm
3000K/CRI 80
2183 lm
3000K/CRI 90
2360 lm
4000K/CRI 90

UT PRO 175



LIGHT SOURCE
LED ARRAY
46,5W
4740 lm
3000K/CRI 80
3960 lm
3000K/CRI 90
4278 lm
4000K/CRI 90

UT PRO WALL-WASHER



LIGHT SOURCE
TOP LED
25,5W
2700 lm
3000K/CRI 90
2900 lm
4000K/CRI 90

WORKMATES IN-TRACK SMALL



LIGHT SOURCE
TOP LED
HIGH EFFICIENCY
Up to 15,5W
CRI 90
1817 lm / 3000K
1831 lm / 3500K
1858 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM
Up to 15,5W
CRI 98
1346 lm / 3000K
1357 lm / 3500K
1369 lm / 4000K

WORKMATES IN-TRACK LARGE



LIGHT SOURCE
TOP LED
HIGH EFFICIENCY
Up to 22W
CRI 90
2726 lm / 3000K
2758 lm / 3500K
2786 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM
Up to 22W
CRI 98
2018 lm / 3000K
2036 lm / 3500K
2053 lm / 4000K

NEW

Description
Exclusive 3-phase lighting profile for indoor use in recessed version that, thanks to its low visual impact, offers a complete integration into the architecture.
Tracking Power EVO's structural profiles are manufactured in black extruded aluminium, fitted with electric tracks where luminaries are installed using the exclusive Flos mounting system.
The Tracking Power EVO family is completed with a wide range of projectors which, combined with exclusive electronics integrated into the body of the luminaire, eliminate unnecessary volume and, as a result, have greater integration.
Moreover, the projectors are also available with standard 3-phase profiles.

Optic System
Light modules UT Pro 150 and UT Pro 175 are available with spot, medium and flood optics and a built-in high-efficiency borosilicate glass reflector.
The light module UT Pro Wall-Washer brings a uniform light distribution in a high-performance wall-washer.
Workmates In-Track (*Small* & *Large*).

Accessories – UT Modules
Shielding cylinder, elliptical lens, flood and honeycomb lens for accent lighting modules UT Pro 150 and UT Pro 175 available.

Additional Information
IN TRACK luminaries mount a compact adapter that, once installed, is completely integrated within the profile, especially designed for FLOS profile The Tracking Power EVO.
However, the same luminaries are available with a standard Nordic GA69 adapter for installation on FLOS standard 3-phase profiles FLOS.Guaranteed compatibility with 3-phase tracks manufactured by Nordic, Eutrac, Erco, Zumtobel and iGuzzini.
- UT Pro Wall-Washer:
Dali version available with GA-600 adaptor.
IP20 protection grade.
- Profile:
Recessed version that can only be installed in plasterboard ceilings that are 12,5 mm thick.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Exclusivo perfil trifásico de iluminación para interiores en versión empotrada que, gracias a su bajo impacto visual, ofrece una total integración en la arquitectura.
Los perfiles estructurales del Tracking Power EVO han sido realizados con aluminio extruido en negro, provistos de pistas eléctricas sobre las cuales se instalan las luminarias mediante el sistema exclusivo de fijación Flos.
La familia Tracking Power EVO se completa con una amplia gama de proyectores que, combinados con una electrónica exclusiva integrada en el cuerpo de la luminaria eliminan volúmenes innecesarios y consiguen, como resultado, una gran integración.
Además, estos proyectores están también disponibles con adaptadores de perfiles trifásicos estándar.

Sistema Óptico
Los módulos de luz UT Pro 150 y UT Pro 175 se encuentran disponibles con ópticas spot, medium y flood e incorporan reflector de cristal de borosilicato de alta eficiencia.
El módulo de luz UT Pro Wall-Washer proporciona una distribución luminosa homogénea, convirtiéndose en un bañador de paredes de altas prestaciones.
Workmates In-Track (*Small* & *Large*).

Accesorios – Módulos UT
Disponible cruceta de apantallamiento, lente elíptica, lente flood y honeycomb para los módulos de iluminación de acento UT Pro 150 y UT Pro 175.

Información Adicional
Las luminarias 'IN TRACK' montan un adaptador de reducidas dimensiones que, una vez instalado, se integra en su totalidad dentro del perfil, especialmente diseñado para utilización en perfil FLOS The Tracking Power EVO.
No obstante, también están disponibles las mismas luminarias con adaptador estándar Nordic GA69 para instalación en perfiles trifásicos estándar de FLOS.
Compatibilidad garantizada con perfiles trifásicos fabricados por Nordic, Eutrac, Erco, Zumtobel e iGuzzini.
- UT Pro Wall-Washer:
Disponible versión Dali con adaptador GA-600.
Índice de protección IP20.
- Perfil:
Versión empotrada, únicamente instalable en techos de cartón-yeso de 12,5mm de espesor.
Instalable sobre superficies normalmente inflamables.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

NEW

HOW TO ORDER

1 CHOOSE YOUR LENGTH





L: 1 / 2 / 3 m

2 COMPLETE WITH MOUNTING ACCESSORIES

End-Feed  Right or Left	L-Joint  Inner or Outer
Jointing Connector 	Insulating Connector 

End Cap No End-Feed



Accessories

Fast Fixing Clamp M6
(Optional)



NEW

3 SELECT A LIGHT MODULE

UT Pro 150



On board dimmer

S/M/F

UT Pro 175



On board dimmer

S/M/F

UT Pro Wall-Washer



Non dimmable

Wall-Washer

WORKMATES IN-TRACK SMALL



No DIM / DALI

WIDE FLOOD / OVAL / HIGH COMFORT

WORKMATES IN-TRACK LARGE



No DIM / DALI


WIDE FLOOD / OVAL / HIGH COMFORT


Profiles

Three-phase profile with minimum impact on the architecture for embedded installations in plasterboard ceilings.
Linear profiles available in three lengths: 1 / 2 / 3 m.
90° corners on the same plane are also available (different elements for the left and right corners).
A linear intermediate connector is required to connect several profiles. Power supply connectors available for the installation on the left or right-hand side.
The fastening of the Tracking Power EVO is performed by screwing the sides of the profile to the plasterboard surface, aided by aluminium fastening profiles.
The adjustable ceiling fastening kit (optional) permits the installation without the need for fastening aluminium profiles. Recommended for installations where the Tracking Power EVO profile can be installed before the suspended plasterboard.

Perfiles

Perfil trifásico con mínimo impacto en la arquitectura, para instalaciones empotradas en techos de cartón yeso.
Perfiles lineales disponibles en tres longitudes: 1 / 2 / 3 m.
Disponibles esquinas de 90° en el mismo plano (diferentes elementos para esquina izquierda y derecha).
Necesario conector intermedio lineal para conectar varios perfiles.
Conectores de alimentación disponibles para instalación en lado izquierdo o derecho.
La fijación del Tracking Power EVO se realiza atornillando las alas del perfil a la superficie de cartón yeso ayudándose de perfiles de aluminio de sujeción.
El kit de sujeción a techo ajustable (opcional) permite la instalación sin necesidad de perfiles de aluminio de sujeción. Recomendado para instalaciones en las que se puede instalar el perfil Tracking Power EVO antes que el falso techo de cartón yeso.






Dimmable
L: 1000 mm
ATP0001A0EAB1
L: 2000 mm
ATP0002A0EAB1
L: 3000 mm
ATP0003A0EAB1

L: 1 m / 2 m / 3 m

90° Corner.
With electrical feeding connection.

Esquina 90°.
Con conexión de alimentación eléctrica.






L-Joint Inner
ATP0105A0EAB1
L-Joint Outer
ATP0106A0EAB1

Feed connector. End cap included.

Conector alimentación. Tapa incluida.






End-Feed Right
ATP0101A0EAB1
End-Feed Left
ATP0102A0EAB1

Jointing Connector.

Conector de unión.






ATP0103A0EAB1

Insulating Connector.


Conector aislante.





ATP0104A0EAB1


NEW

Cutting tool for track conductors.	Herramienta de corte para los conductores del carril.		ATP0201A0EAZZ
End Cap.	Tapa.	 	ATP0205A0EAB1
Adjustable ceiling kit (optional). 2 unit kit.	Kit de sujeción a techo ajustable (opcional). Kit de 2 unidades.	 	■ ATP0202A0EAB1

Profile (mm)	Quantities Ceiling Kit
1000	1
2000	2
3000	3

The Tracking Power EVO profile is asymmetric to ensure the electric safety in the installation, and it provides a unique form in the installation of luminaires.
The diagram shows the position of the neutral track (red line) for the different possible configurations, which must be composed according to the requirements for each installation, respecting the electric continuity.


Para garantizar la seguridad eléctrica en la instalación, el perfil de Tracking Power EVO es asimétrico y ofrece una forma única para la instalación de las luminarias.
En el diagrama se muestra la posición del Perfil neutro (línea roja) para las distintas configuraciones posibles, que ha de componerse de acuerdo a los requisitos de cada instalación, respetando la continuidad eléctrica.




UT Pro 150

LED Array 20W - 2294 lm - 3000K/CRI 80 / 20W - 1984 lm - 3000K/CRI 90 / 20W - 2145 lm - 4000K/CRI 90







Finishes Available



Spotlight to be installed in Tracking Power EVO profile with LED light source. 120-277V power supply integrated. High performance reflector included.


.40 versions come with the track adapter, the arm and the rear of the head in black. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Proyector para ser instalado en perfil Tracking Power EVO con fuente de luz LED. Fuente de alimentación 120-277V integrada. Incluye reflector de alto rendimiento.

Las versiones .40 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas, solo el anillo anti-deslumbramiento permanece en color negro.

3000K - CRI 80
On board dimmer
09.7210.40D
09.7210.14D
All White
09.7210.40D78

21° SPOT




Luminous flux luminaire 2031 lm

Beam Angle:	21°
h(m) E(lx)	D(m)
1 12557	0.37
2 3139	0.74
3 1395	1.11
4 785	1.48
5 502	1.85

4000K - CRI 90
On board dimmer
09.7211.40D
09.7211.14D
All White
09.7211.40D78

21° SPOT




Luminous flux luminaire 1617 lm

Beam Angle:	21°
h(m) E(lx)	D(m)
1 9997	0.37
2 2499	0.74
3 1111	1.11
4 625	1.48
5 400	1.85

3000K - CRI 80
On board dimmer
09.7212.40D
09.7212.14D
All White
09.7212.40D78

27° MEDIUM




Luminous flux luminaire 1729 lm

Beam Angle:	27°
h(m) E(lx)	D(m)
1 7923	0.49
2 1981	0.98
3 880	1.47
4 495	1.96
5 317	2.44

4000K - CRI 90
On board dimmer
09.7213.40D
09.7213.14D
All White
09.7213.40D78

27° MEDIUM




Luminous flux luminaire 1617 lm

Beam Angle:	27°
h(m) E(lx)	D(m)
1 7409	0.49
2 1852	0.98
3 823	1.47
4 463	1.96
5 296	2.44

3000K - CRI 80
On board dimmer
09.7214.40D
09.7214.14D
All White
09.7214.40D78

35° FLOOD




Luminous flux luminaire 1701 lm

Beam Angle:	35°
h(m) E(lx)	D(m)
1 5035	0.64
2 1259	1.27
3 559	1.91
4 315	2.54
5 201	3.18

4000K - CRI 90
On board dimmer
09.7215.40D
09.7215.14D
All White
09.7215.40D78

36° FLOOD




Luminous flux luminaire 1396 lm

Beam Angle:	36°
h(m) E(lx)	D(m)
1 4080	0.64
2 1020	1.28
3 453	1.92
4 255	2.56
5 163	3.20

3000K - CRI 90
On board dimmer
09.7216.40D
09.7216.14D
All White
09.7216.40D78

21° SPOT




Luminous flux luminaire 1496 lm

Beam Angle:	21°
h(m) E(lx)	D(m)
1 9249	0.37
2 2312	0.74
3 1028	1.11
4 578	1.48
5 370	1.85

3000K - CRI 90
On board dimmer
09.7217.40D
09.7217.14D
All White
09.7217.40D78

27° MEDIUM




Luminous flux luminaire 1495 lm

Beam Angle:	27°
h(m) E(lx)	D(m)
1 6850	0.49
2 1713	0.98
3 761	1.47
4 428	1.96
5 274	2.44

3000K - CRI 90
On board dimmer
09.7218.40D
09.7218.14D
All White
09.7218.40D78

36° FLOOD




Luminous flux luminaire 1291 lm


Beam Angle:	36°
h(m) E(lx)	D(m)
1 3773	0.64
2 943	1.28
3 419	1.92
4 236	2.56
5 151	3.20

UT Pro 175

LED Array 46,5W - 4740 lm - 3000K/CRI 80 / 3960 lm - 3000K/CRI 90 / 4278 lm - 4000K/CRI 90







Finishes Available



Spotlight to be installed in Tracking Power EVO profile with LED light source. 120-277V power supply integrated. High performance reflector included.


.40 versions come with the track adapter, the arm and the rear of the head in black. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Proyector para ser instalado en perfil Tracking Power EVO con fuente de luz LED. Fuente de alimentación 120-277V integrada. Incluye reflector de alto rendimiento.

Las versiones .40 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas, solo el anillo anti-deslumbramiento permanece en color negro.

3000K - CRI 80
On board dimmer
09.7300.40B
09.7300.14B
All White
09.7300.40B78

20° SPOT




Luminous flux luminaire
3638 lm

Beam Angle:	20°
h(m) E(lx)	D(m)
1 21906	0.35
2 5477	0.70
3 2434	1.04
4 1369	1.39
5 876	1.74

3000K - CRI 90
On board dimmer
09.7301.40B
09.7301.14B
All White
09.7301.40B78

20° SPOT




Luminous flux luminaire
3037 lm

Beam Angle:	20°
h(m) E(lx)	D(m)
1 18287	0.35
2 4572	0.70
3 2032	1.04
4 1143	1.39
5 731	1.74

4000K - CRI 90
On board dimmer
09.7302.40B
09.7302.14B
All White
09.7302.40B78

20° SPOT




Luminous flux luminaire
3283 lm

Beam Angle:	20°
h(m) E(lx)	D(m)
1 19769	0.35
2 4942	0.70
3 2197	1.04
4 1236	1.39
5 791	1.74

3000K - CRI 80
On board dimmer
09.7303.40B
09.7303.14B
All White
09.7303.40B78

27° MEDIUM




Luminous flux luminaire
3531 lm

Beam Angle:	27°
h(m) E(lx)	D(m)
1 13450	0.48
2 3362	0.96
3 1494	1.44
4 841	1.93
5 538	2.41

3000K - CRI 90
On board dimmer
09.7304.40B
09.7304.14B
All White
09.7304.40B78

27° MEDIUM




Luminous flux luminaire
2947 lm

Beam Angle:	27°
h(m) E(lx)	D(m)
1 11225	0.48
2 2806	0.96
3 1247	1.44
4 702	1.93
5 449	2.41

4000K - CRI 90
On board dimmer
09.7305.40B
09.7305.14B
All White
09.7305.40B78

27° MEDIUM




Luminous flux luminaire
3187 lm

Beam Angle:	27°
h(m) E(lx)	D(m)
1 12140	0.48
2 3035	0.96
3 1349	1.44
4 759	1.93
5 486	2.41

3000K - CRI 80
On board dimmer
09.7306.40B
09.7306.14B
All White
09.7306.40B78

34° FLOOD




Luminous flux luminaire
3476 lm

Beam Angle:	34°
h(m) E(lx)	D(m)
1 8672	0.61
2 2168	1.22
3 964	1.83
4 542	2.44
5 347	3.04

3000K - CRI 90
On board dimmer
09.7307.40B
09.7307.14B
All White
09.7307.40B78

34° FLOOD




Luminous flux luminaire
2901 lm

Beam Angle:	34°
h(m) E(lx)	D(m)
1 7237	0.61
2 1809	1.22
3 804	1.83
4 452	2.44
5 289	3.04

4000K - CRI 90
On board dimmer
09.7308.40B
09.7308.14B
All White
09.7308.40B78

34° FLOOD




Luminous flux luminaire
3137 lm


Beam Angle:	34°
h(m) E(lx)	D(m)
1 7826	0.61
2 1957	1.22
3 870	1.83
4 489	2.44
5 313	3.04

UT Pro Wall-Washer

Top LED 25,5W - 2700 lm - 3000K/CRI 90 / 25,5W - 2900 lm - 4000K/CRI 90







Finishes Available




Wall-Washer lighting module to be installed in Tracking Power EVO profile with LED light source. 220-240V power supply integrated.

.40 versions come with the track adapter, the arm and the rear of the head in black. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white.

Módulo de iluminación Wall-Washer para ser instalado en perfil Tracking Power EVO con fuente de luz LED. Fuente de alimentación 220-240V integrada.

Las versiones .40 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas.


3000K - CRI 90
Non Dimmable
09.7500.40A
09.7500.14A
All White
09.7500.40A78



Luminous flux luminaire
1706 lm

Beam Angle:		36°
h(m)	E(lx)	D(m)
1	1199	0.78
2	300	1.56
3	133	2.34
4	75	3.12
5	48	3.90

4000K - CRI 90
Non Dimmable
09.7501.40A
09.7501.14A
All White
09.7501.40A78




Luminous flux luminaire
1700 lm


Beam Angle:		36°
h(m)	E(lx)	D(m)
1	1184	0.76
2	296	1.52
3	132	2.28
4	74	3.04
5	47	3.80

Workmates In-Track Small

Top LED High Efficiency
Non Dimming: 15,5W - 1817 lm - 3000K/CRI 90 / 1831 lm - 3500K/CRI 90 / 1858 lm - 4000K/CRI 90
Dali 2: 15W - 1817 lm - 3000K/CRI 90 / 1831 lm - 3500K/CRI 90 / 1858 lm - 4000K/CRI 90







Luminaire for use on a three-phase track, with adapters for No Dim and Dali control. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim y Dali. Fuente de luz de alta eficiencia. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360° para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65°<3000.

Optic Wide Flood - 3000K


Non Dimming

- 05.6280.40
- 05.6280.40.78
- 05.6280.14
- 05.6280.AP

Dali 2

- 05.6280.40.DA
- 05.6280.40.YU
- 05.6280.14.DA
- 05.6280.AP.DA





Luminous flux luminaire
1768 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1143	1.55
2	286	3.10
3	127	4.66
4	71	6.21
5	46	7.76

Optic Wide Flood - 4000K


Non Dimming

- 05.6282.40
- 05.6282.40.78
- 05.6282.14
- 05.6282.AP

Dali 2

- 05.6282.40.DA
- 05.6282.40.YU
- 05.6282.14.DA
- 05.6282.AP.DA





Luminous flux luminaire
1830 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1183	1.55
2	296	3.10
3	131	4.66
4	74	6.21
5	47	7.76

Optic Wide Flood - 3500K


Non Dimming

- 05.6281.40
- 05.6281.40.78
- 05.6281.14
- 05.6281.AP

Dali 2

- 05.6281.40.DA
- 05.6281.40.YU
- 05.6281.14.DA
- 05.6281.AP.DA





Luminous flux luminaire
1773 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1146	1.55
2	286	3.10
3	127	4.66
4	72	6.21
5	46	7.76

NEW

Optic Oval - 3000K


Non Dimming

- 05.6285.40
- 05.6285.40.78
- 05.6285.14
- 05.6285.AP

Dali 2

- 05.6285.40.DA
- 05.6285.40.YU
- 05.6285.14.DA
- 05.6285.AP.DA





Luminous flux luminaire
1720 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1096	1.67
2	274	3.34
3	122	5.00
4	68	6.67
5	44	8.34

Optic High Comfort - 3000K


Non Dimming

- 05.5780.40
- 05.5780.40.78
- 05.5780.14
- 05.5780.AP

Dali 2

- 05.5780.40.DA
- 05.5780.40.YU
- 05.5780.14.DA
- 05.5780.AP.DA





Luminous flux luminaire
1850 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1780	1.31
2	445	2.61
3	198	3.92
4	111	5.23
5	71	6.54

Optic Oval - 3500K


Non Dimming

- 05.6286.40
- 05.6286.40.78
- 05.6286.14
- 05.6286.AP

Dali 2

- 05.6286.40.DA
- 05.6286.40.YU
- 05.6286.14.DA
- 05.6286.AP.DA





Luminous flux luminaire
1725 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1099	1.67
2	275	3.34
3	122	5.00
4	69	6.67
5	44	8.34

Optic High Comfort - 3500K


Non Dimming

- 05.5781.40
- 05.5781.40.78
- 05.5781.14
- 05.5781.AP

Dali 2

- 05.5781.40.DA
- 05.5781.40.YU
- 05.5781.14.DA
- 05.5781.AP.DA





Luminous flux luminaire
1855 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1785	1.31
2	446	2.61
3	198	3.92
4	112	5.23
5	71	6.54

Optic Oval - 4000K


Non Dimming

- 05.6287.40
- 05.6287.40.78
- 05.6287.14
- 05.6287.AP

Dali 2

- 05.6287.40.DA
- 05.6287.40.YU
- 05.6287.14.DA
- 05.6287.AP.DA





Luminous flux luminaire
1780 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1134	1.67
2	283	3.34
3	126	5.00
4	71	6.67
5	45	8.34

Optic High Comfort - 4000K


Non Dimming

- 05.5782.40
- 05.5782.40.78
- 05.5782.14
- 05.5782.AP

Dali 2

- 05.5782.40.DA
- 05.5782.40.YU
- 05.5782.14.DA
- 05.5782.AP.DA






Luminous flux luminaire
1887 lm


Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1815	1.31
2	454	2.61
3	202	3.92
4	113	5.23
5	73	6.54

Workmates In-Track Small

Top LED Full Spectrum
Non Dimming: 15,5W - 1346 lm - 3000K/CRI 98 / 1357 lm - 3500K/CRI 98 / 1369 lm - 4000K/CRI 98
Dali 2: 15W - 1346 lm - 3000K/CRI 98 / 1357 lm - 3500K/CRI 98 / 1369 lm - 4000K/CRI 98







Luminaire for use on a three-phase track, with adapters for No Dim and Dali control. High-quality colour rendering *Full Spectrum* light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.


Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim y Dali. Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000.

Optic Wide Flood - 3000K

Non Dimming
- 05.6290.40
- 05.6290.40.78
- 05.6290.14
- 05.6290.AP

Dali 2
- 05.6290.40.DA
- 05.6290.40.YU
- 05.6290.14.DA
- 05.6290.AP.DA





Luminous flux luminaire
1231 lm


Beam Angle:		76°
h(m)	E(lx)	D(m)
1	796	1.55
2	199	3.10
3	88	4.66
4	50	6.21
5	32	7.76

Optic Wide Flood - 4000K

Non Dimming
- 05.6292.40
- 05.6292.40.78
- 05.6292.14
- 05.6292.AP

Dali 2
- 05.6292.40.DA
- 05.6292.40.YU
- 05.6292.14.DA
- 05.6292.AP.DA





Luminous flux luminaire
1300 lm


Beam Angle:		76°
h(m)	E(lx)	D(m)
1	840	1.55
2	210	3.10
3	93	4.66
4	53	6.21
5	34	7.76

Optic Wide Flood - 3500K

Non Dimming
- 05.6291.40
- 05.6291.40.78
- 05.6291.14
- 05.6291.AP

Dali 2
- 05.6291.40.DA
- 05.6291.40.YU
- 05.6291.14.DA
- 05.6291.AP.DA





Luminous flux luminaire
1238 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	800	1.55
2	200	3.10
3	89	4.66
4	50	6.21
5	32	7.76

NEW

Optic Oval - 3000K


Non Dimming

- 05.6295.40
- 05.6295.40.78
- 05.6295.14
- 05.6295.AP

Dali 2

- 05.6295.40.DA
- 05.6295.40.YU
- 05.6295.14.DA
- 05.6295.AP.DA





Luminous flux luminaire
1192 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	759	1.67
2	190	3.34
3	84	5.00
4	47	6.67
5	30	8.34

Optic High Comfort - 3000K


Non Dimming

- 05.5790.40
- 05.5790.40.78
- 05.5790.14
- 05.5790.AP

Dali 2

- 05.5790.40.DA
- 05.5790.40.YU
- 05.5790.14.DA
- 05.5790.AP.DA





Luminous flux luminaire
1289 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1240	1.31
2	310	2.61
3	138	3.92
4	77	5.23
5	50	6.54

Optic Oval - 3500K


Non Dimming

- 05.6296.40
- 05.6296.40.78
- 05.6296.14
- 05.6296.AP

Dali 2

- 05.6296.40.DA
- 05.6296.40.YU
- 05.6296.14.DA
- 05.6296.AP.DA





Luminous flux luminaire
1198 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	763	1.67
2	191	3.34
3	85	5.00
4	48	6.67
5	31	8.34

Optic High Comfort - 3500K


Non Dimming

- 05.5791.40
- 05.5791.40.78
- 05.5791.14
- 05.5791.AP

Dali 2

- 05.5791.40.DA
- 05.5791.40.YU
- 05.5791.14.DA
- 05.5791.AP.DA





Luminous flux luminaire
1293 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1244	1.31
2	311	2.61
3	138	3.92
4	78	5.23
5	50	6.54

Optic Oval - 4000K


Non Dimming

- 05.6297.40
- 05.6297.40.78
- 05.6297.14
- 05.6297.AP

Dali 2

- 05.6297.40.DA
- 05.6297.40.YU
- 05.6297.14.DA
- 05.6297.AP.DA





Luminous flux luminaire
1259 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	802	1.67
2	200	3.34
3	89	5.00
4	50	6.67
5	32	8.34

Optic High Comfort - 4000K


Non Dimming

- 05.5792.40
- 05.5792.40.78
- 05.5792.14
- 05.5792.AP

Dali 2

- 05.5792.40.DA
- 05.5792.40.YU
- 05.5792.14.DA
- 05.5792.AP.DA






Luminous flux luminaire
1357 lm


Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1306	1.31
2	326	2.61
3	145	3.92
4	82	5.23
5	52	6.54

Workmates In-Track Large

Top LED High Efficiency
Non Dimming: 21W - 2726 lm - 3000K/CRI 90 / 2758 lm - 3500K/CRI 90 / 2786 lm - 4000K/CRI 90
Dali 2: 22W - 2726 lm - 3000K/CRI 90 / 2758 lm - 3500K/CRI 90 / 2786 lm - 4000K/CRI 90







Luminaire for use on a three-phase track, with adapters for No Dim and Dali *control*. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim y Dali. Fuente de luz de alta eficiencia. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360° para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65°<3000.

Optic Wide Flood - 3000K


Non Dimming

- 05.6300.40
- 05.6300.40.78
- 05.6300.14
- 05.6300.AP

Dali 2

- 05.6300.40.DA
- 05.6300.40.YU
- 05.6300.14.DA
- 05.6300.AP.DA





Luminous flux luminaire
2582 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1634	1.57
2	409	3.13
3	182	4.70
4	102	6.26
5	65	7.83

Optic Wide Flood - 4000K


Non Dimming

- 05.6302.40
- 05.6302.40.78
- 05.6302.14
- 05.6302.AP

Dali 2

- 05.6302.40.DA
- 05.6302.40.YU
- 05.6302.14.DA
- 05.6302.AP.DA





Luminous flux luminaire
2673 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1692	1.57
2	423	3.13
3	188	4.70
4	106	6.26
5	68	7.83

Optic Wide Flood - 3500K


Non Dimming

- 05.6301.40
- 05.6301.40.78
- 05.6301.14
- 05.6301.AP

Dali 2

- 05.6301.40.DA
- 05.6301.40.YU
- 05.6301.14.DA
- 05.6301.AP.DA





Luminous flux luminaire
2590 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1639	1.57
2	410	3.13
3	182	4.70
4	102	6.26
5	66	7.83

NEW

Optic Oval - 3000K


Non Dimming

- 05.6305.40
- 05.6305.40.78
- 05.6305.14
- 05.6305.AP

Dali 2

- 05.6305.40.DA
- 05.6305.40.YU
- 05.6305.14.DA
- 05.6305.AP.DA





Luminous flux luminaire
2462 lm

Beam Angle:	80°
h(m)	E(lx) D(m)
1	1577 1.68
2	394 3.36
3	175 5.03
4	99 6.71
5	63 8.39

Optic High Comfort - 3000K


Non Dimming

- 05.5800.40
- 05.5800.40.78
- 05.5800.14
- 05.5800.AP

Dali 2

- 05.5800.40.DA
- 05.5800.40.YU
- 05.5800.14.DA
- 05.5800.AP.DA





Luminous flux luminaire
2711 lm

Beam Angle:	67°
h(m)	E(lx) D(m)
1	2563 1.32
2	641 2.64
3	285 3.96
4	160 5.28
5	103 6.61

Optic Oval - 3500K


Non Dimming

- 05.6306.40
- 05.6306.40.78
- 05.6306.14
- 05.6306.AP

Dali 2

- 05.6306.40.DA
- 05.6306.40.YU
- 05.6306.14.DA
- 05.6306.AP.DA





Luminous flux luminaire
2469 lm

Beam Angle:	80°
h(m)	E(lx) D(m)
1	1582 1.68
2	395 3.36
3	176 5.03
4	99 6.71
5	63 8.39

Optic High Comfort - 3500K


Non Dimming

- 05.5801.40
- 05.5801.40.78
- 05.5801.14
- 05.5801.AP

Dali 2

- 05.5801.40.DA
- 05.5801.40.YU
- 05.5801.14.DA
- 05.5801.AP.DA





Luminous flux luminaire
2718 lm

Beam Angle:	67°
h(m)	E(lx) D(m)
1	2571 1.32
2	643 2.64
3	286 3.96
4	161 5.28
5	103 6.61

Optic Oval - 4000K


Non Dimming

- 05.6307.40
- 05.6307.40.78
- 05.6307.14
- 05.6307.AP

Dali 2

- 05.6307.40.DA
- 05.6307.40.YU
- 05.6307.14.DA
- 05.6307.AP.DA





Luminous flux luminaire
2548 lm

Beam Angle:	80°
h(m)	E(lx) D(m)
1	1632 1.68
2	408 3.36
3	181 5.03
4	102 6.71
5	65 8.39

Optic High Comfort - 4000K


Non Dimming

- 05.5802.40
- 05.5802.40.78
- 05.5802.14
- 05.5802.AP

Dali 2

- 05.5802.40.DA
- 05.5802.40.YU
- 05.5802.14.DA
- 05.5802.AP.DA






Luminous flux luminaire
2790 lm


Beam Angle:	67°
h(m)	E(lx) D(m)
1	2639 1.32
2	660 2.64
3	293 3.96
4	165 5.28
5	106 6.61

Workmates In-Track Large

Top LED Full Spectrum
Non Dimming: 21W - 2018 lm - 3000K/CRI 98 / 2036 lm - 3500K/CRI 98 / 2053 lm - 4000K/CRI 98
Dali 2: 22W - 2018 lm - 3000K/CRI 98 / 2036 lm - 3500K/CRI 98 / 2053 lm - 4000K/CRI 98







Luminaire for use on a three-phase track, with adapters for No Dim and Dali *control*. High-quality colour rendering *Full Spectrum* light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim y Dali. Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000.

Optic Wide Flood - 3000K


Non Dimming

- 05.6310.40
- 05.6310.40.78
- 05.6310.14
- 05.6310.AP

Dali 2

- 05.6310.40.DA
- 05.6310.40.YU
- 05.6310.14.DA
- 05.6310.AP.DA





Luminous flux luminaire
1761 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1155	1.55
2	289	3.09
3	128	4.64
4	72	6.18
5	46	7.73

Optic Wide Flood - 4000K


Non Dimming

- 05.6312.40
- 05.6312.40.78
- 05.6312.14
- 05.6312.AP

Dali 2

- 05.6312.40.DA
- 05.6312.40.YU
- 05.6312.14.DA
- 05.6312.AP.DA





Luminous flux luminaire
1860 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1219	1.55
2	305	3.09
3	135	4.64
4	76	6.18
5	49	7.73

Optic Wide Flood - 3500K


Non Dimming

- 05.6311.40
- 05.6311.40.78
- 05.6311.14
- 05.6311.AP

Dali 2

- 05.6311.40.DA
- 05.6311.40.YU
- 05.6311.14.DA
- 05.6311.AP.DA





Luminous flux luminaire
1770 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1160	1.55
2	290	3.09
3	129	4.64
4	73	6.18
5	46	7.73

NEW

Optic Oval - 3000K


Non Dimming

- 05.6315.40
- 05.6315.40.78
- 05.6315.14
- 05.6315.AP

Dali 2

- 05.6315.40.DA
- 05.6315.40.YU
- 05.6315.14.DA
- 05.6315.AP.DA





Luminous flux luminaire
1744 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1117	1.68
2	279	3.36
3	124	5.03
4	70	6.71
5	45	8.39

Optic High Comfort - 3000K


Non Dimming

- 05.5810.40
- 05.5810.40.78
- 05.5810.14
- 05.5810.AP

Dali 2

- 05.5810.40.DA
- 05.5810.40.YU
- 05.5810.14.DA
- 05.5810.AP.DA





Luminous flux luminaire
1848 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1747	1.32
2	437	2.64
3	194	3.96
4	109	5.28
5	70	6.61

Optic Oval - 3500K


Non Dimming

- 05.6316.40
- 05.6316.40.78
- 05.6316.14
- 05.6316.AP

Dali 2

- 05.6316.40.DA
- 05.6316.40.YU
- 05.6316.14.DA
- 05.6316.AP.DA





Luminous flux luminaire
1753 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1123	1.68
2	281	3.36
3	125	5.03
4	70	6.71
5	45	8.39

Optic High Comfort - 3500K


Non Dimming

- 05.5811.40
- 05.5811.40.78
- 05.5811.14
- 05.5811.AP

Dali 2

- 05.5811.40.DA
- 05.5811.40.YU
- 05.5811.14.DA
- 05.5811.AP.DA





Luminous flux luminaire
1856 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1755	1.32
2	439	2.64
3	195	3.96
4	110	5.28
5	70	6.61

Optic Oval - 4000K


Non Dimming

- 05.6317.40
- 05.6317.40.78
- 05.6317.14
- 05.6317.AP

Dali 2

- 05.6317.40.DA
- 05.6317.40.YU
- 05.6317.14.DA
- 05.6317.AP.DA





Luminous flux luminaire
1842 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1180	1.68
2	295	3.36
3	131	5.03
4	74	6.71
5	47	8.39

Optic High Comfort - 4000K


Non Dimming

- 05.5812.40
- 05.5812.40.78
- 05.5812.14
- 05.5812.AP

Dali 2

- 05.5812.40.DA
- 05.5812.40.YU
- 05.5812.14.DA
- 05.5812.AP.DA





Luminous flux luminaire
1939 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1834	1.32
2	458	2.64
3	204	3.96
4	115	5.28
5	73	6.61

Accessories / Accesorios


UT Pro 150 / UT Pro 175

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Cruceta de apantallamiento, lentes y honeycomb directamente instalables en la cabeza de la luminaria sin necesidad de accesorio de sujeción. Compatibilidad de instalación de honeycomb + lente al mismo tiempo.

Screening crosspiece.	Cruceta de apantallamiento.		UT Pro 150 08.8429.00 UT Pro 175 08.9108.00
Elliptical lens.	Lente elíptica.		UT Pro 150 08.8431.00 UT Pro 175 08.9109.00
Flood lens.	Lente flood.		UT Pro 150 08.8432.00 UT Pro 175 08.9110.00
Honeycomb.	Honeycomb.		UT Pro 150 08.8428.00 UT Pro 175 08.9107.00
Snoot shielding cone.	Cono apantallador.	 	UT Pro 150 08.0526.00 08.0526.40 08.0526.BW UT Pro 175 08.9111.00

WALL-WASHER INSTALLATION




THE FAST TRACK

DESIGNED BY FLOS ARCHITECTURAL

RECESSED

SURFACE



Recessed Profiles ■ 14 Black
14 Negro

Surface Profiles □ 40 White
40 Blanco

■ 14 Black
14 Negro

LIGHT MODULES

THE FAST TRACK SPOT 100



LIGHT SOURCE
POWER LED
13W
780 lm
3000K/CRI 90
830 lm
4000K/CRI 90

THE FAST TRACK SPOT 150



LIGHT SOURCE
LED ARRAY
25,5W
2378 lm
3000K/CRI 90
2751 lm
4000K/CRI 90

MULTIFUNCTION SMART DEVICE



FLOS CONTROL®
by Casambi

■ 14 Black
14 Negro



□ BW White
BW Blanco



Description
Only system in the world that allows the intensity of different groups of light fittings to be moved, oriented, and adjusted at a distance.
Indoor system available in versions for installation on surfaces and recessed installation on the ceiling. Equipped with wireless control via the FLOS Control® by Casambi system managed using the dedicated app for mobile devices (covers a distance of about 20 m). The system allows up to 200 devices to be controlled via the app.
The lighting modules incorporate servos for moving and orienting them, as well as sensors to detect other spots and the end of the track.
The system can recognize the location of each spot at all times and memorize up to 24 scenes of light. It memorizes the orientation, rotation and light intensity for later use, as well as 4 time schedules to change from one scene to another.
The light scene can also be completely changed by recovering the memorized compositions with a simple click. The movement must always be performed manually and individually through the APP.
Structural profiles of the system are manufactured in black extruded aluminum and are white plated for the 40 version, provided with electric tracks fed at 48V, on which the LED luminaries are installed by means of a mechanical fixing system.
The family is composed of accent lighting, with different optics.
The only available control system is FLOS Control® by Casambi.
The app for mobile devices is also necessary (available in the Apple Store and Google Play).
The maximum length for each power source is 20 m.
The maximum length between the power supply and the start of the track is 2 m.

Optic system
The accent light modules are available with high-performance crystal optics. Super spot, spot, medium and flood angles.

Power Supply
Remote 48V power source not included.

Additional Information
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Único sistema mundial que permite mover, orientar y regular la intensidad, a distancia, los diferentes grupos de luminarias.
El sistema para interiores está disponible en versiones de montaje en superficie y empotrado en el techo. Equipado con un control inalámbrico con el sistema FLOS Control® de Casambi gestionado a través de una aplicación dedicada para dispositivos móviles (cubre una distancia de unos 20m). El sistema permite controlar hasta 200 dispositivos a través de la App.
Los módulos de iluminación incorporan servos para su movimiento y orientación, sensores para detectar otros spots y el final del carril.
El sistema es capaz de reconocer la ubicación de cada spot en todo momento y memorizar hasta un máximo de 24 escenas de luz, memorizando orientación, rotación e intensidad lumínica para su uso posterior, así como 4 programaciones horarias para cambiar de una escena a otra.
También se puede cambiar completamente de escena de luz recuperando las composiciones memorizadas con un simple click. La traslación debe realizarse siempre de forma manual e individual a través de la APP.
Perfiles estructurales del sistema de aluminio extruido en negro y chapados en blanco para la versión .40, provisto de pistas eléctricas alimentadas a 48V, sobre las cuales se instalan mediante un sistema de fijación mecánica de las luminarias LED.
La familia está compuesta por módulos de iluminación de acento, con diferentes ópticas.
El único sistema de control disponible es FLOS Control® by Casambi.
Necesaria APP para dispositivos móviles (disponible en Apple Store y Google Play).
La longitud máxima por cada fuente de alimentación es de 20 m.
La longitud máxima entre la fuente de alimentación y el inicio del carril es de 2 m.

Sistema Óptico
Los módulos de luz de acento se encuentran disponibles con ópticas de cristal alto rendimiento. Ángulos super spot, spot, médium y flood.

Unidades de Alimentación
Fuente de alimentación remota de 48V no incluida.

Información Adicional
Índice de protección IP20.
Instalable sobre superficies normalmente inflamables.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

FLOS
CONTROL BY CASAMBI


Available on the App Store

GET IT ON Google Play

HOW TO ORDER


1 CHOOSE YOUR PROFILE AND LENGTH

RECESSED PROFILE



L: 1 / 1,5 / 2 / 3 m

SURFACE PROFILE



L: 1 / 1,5 / 2 / 3 m

2 COMPLETE WITH MOUNTING ACCESSORIES

Feed cable



End cap



Intermediate cable



Electrical

Stopper



Recessed installation

Accessories
(Optional)

Fixed ceiling kit



or

Adjustable ceiling kit



Feed cable



End cap



Intermediate cable



Electrical

Stopper



Surface installation

Fixing ceiling kit included with the profile

3 SELECT POWER SUPPLY

Recessed installation

Remote power supply



185W



320W

(select the driver with the appropriate power according to the needs of your project)

Surface installation

Remote power supply



185W



320W

(select the driver with the appropriate power according to the needs of your project)

4 SELECT A LIGHT MODULE

Spot 100



Casambi integrated

SS/S/M

Spot 150



Casambi integrated

S/M/F

Multifunction Smart Device

FLOS Control® by Casambi





Profiles

Electro-mechanical profile for recessed installations in plasterboard ceilings, with 1m to 3m lengths. Power and interconnection cables must be ordered separately.
The covers must be ordered separately. Fixed or adjustable fastening kits available (optional). The roof fastening kits enable installation without the need for aluminium TC fastening profiles.

Perfiles

Perfil electro-mecánico para instalaciones empotradas en techos de cartón yeso con longitudes de 1m a 3m. Necesario pedir por separado cables de alimentación e interconexión.
Las tapas deben pedirse por separado. Kits de sujeción, fijo o ajustable, disponibles (opcional). Los kits de sujeción a techo permiten la instalación sin necesidad de perfiles TC de aluminio de sujeción.






L: 1000 mm
06.1850.14
L: 1500mm
06.1851.14
L: 2000 mm
06.1852.14
L: 3000 mm
06.1853.14

L: 1 m / 1,5 m / 2 m / 3 m

Fixed ceiling kit (optional).
2 unit kit.

Kit de sujeción a techo fijo (opcional). Kit de 2 unidades.






08.8866.14

Adjustable ceiling kit (optional).
2 unit kit.
Installation requires a M6 threaded rod, not included.

Kit de sujeción a techo ajustable (opcional). Kit de 2 unidades.
Para su instalación requiere varilla roscada de M6, no incluida.





08.8867.14

Profile (mm)	Quantities Ceiling Kit
1000	1
2000	2
3000	2
4000	3

1-m suspension rod with ceiling rose with m6 thread.

Varilla de suspensión de 1 m con rosetón con rosca m6.

60.3097.11
60.3097.14

End caps. To be ordered separately.
2 unit kit.

Tapas. Se deben pedir por separado. Kit de 2 unidades.



08.9070.14


THE FAST TRACK – SURFACE PROFILES


Profiles

Electro-mechanical profile for surface installations in plasterboard ceilings, with 1m to 3m lengths. Not suitable for suspended installations. Power and interconnection cables must be ordered separately.
Covers must be ordered separately. Fixed ceiling kit included.

Perfiles

Perfil electro-mecánico para instalaciones en superficie en techos de cartón yeso con longitudes de 1 m a 3 m. No válido para instalaciones en suspensión. Necesario pedir por separado cables de alimentación e interconexión.
Las tapas deben pedirse por separado. Kit de sujeción a techo fijo incluido.





L: 1000 mm
06.1860.40
06.1860.14
L: 1500 mm
06.1861.40
06.1861.14
L: 2000 mm
06.1862.40
06.1862.14
L: 3000 mm
06.1863.40
06.1863.14

L: 1 m / 1,5 m / 2 m / 3 m

End caps. Must be ordered separately. 2 unit kit.

Tapas. Se deben pedir por separado. Kit de 2 unidades.



08.9071.40
08.9071.14

The Fast Track Recessed / Surface versions

Stopper. To prevent spots from invading track areas powered by another driver and to prevent exceeding the maximum allowed power of each driver. It can also be used to limit movement for other reasons.

Stopper. Para evitar que los spots invadan zonas de carril alimentadas por otro driver y evitar superar la potencia máxima permitida de cada driver. También se puede usar para limitar el movimiento por otras razones.



08.9074.14

Power feed cable.

Cable de alimentación.



06.0303.00


Connection cable. Electrical connection.

Cable de conexión. Conexión eléctrica.




06.0301.00

RECESSED INSTALLATION




SURFACE INSTALLATION




The Fast Track Spot 100

Power LED 13W - 830 lm - 3000K/CRI 90 / 13W - 878 lm - 4000K/CRI 90








Spotlight to be installed in the The Fast Track system profile with a LED light source and super spot optic, very useful for great heights, medium and flood.
The boxes of the luminaries are manufactured only in black.

Proyector para ser instalado en perfil del sistema The Fast Track con fuente de luz LED y con óptica super spot muy útil para grandes alturas, medium y flood.
Las cajas de las luminarias se fabrican solo en negro.

3000K
**Casambi integrated
09.9070.BWA
09.9070.14A

4°
SUPER SPOT




Luminous flux luminaire
630 lm

Beam Angle: 4°

h(m)	E(lx)	D(m)
1	64970	0.07
2	16243	0.14
3	7219	0.21
4	4061	0.28
5	2599	0.35

4000K
**Casambi integrated
09.9075.BWA
09.9075.14A

4°
SUPER SPOT




Luminous flux luminaire
667 lm

Beam Angle: 4°

h(m)	E(lx)	D(m)
1	68792	0.07
2	17198	0.14
3	7644	0.21
4	4300	0.28
5	2752	0.35

3000K
**Casambi integrated
09.9071.BWA
09.9071.14A

15°
SPOT




Luminous flux luminaire
567 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5987	0.26
2	1497	0.52
3	665	0.77
4	374	1.03
5	239	1.29

4000K
**Casambi integrated
09.9076.BWA
09.9076.14A

15°
SPOT




Luminous flux luminaire
600 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6339	0.26
2	1585	0.52
3	704	0.77
4	396	1.03
5	254	1.29

3000K
**Casambi integrated
09.9072.BWA
09.9072.14A

27°
MEDIUM




Luminous flux luminaire
693 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	1777	0.48
2	444	0.95
3	197	1.43
4	111	1.91
5	71	2.38

4000K
**Casambi integrated
09.9077.BWA
09.9077.14A

27°
MEDIUM



Luminous flux luminaire
733 lm

Beam Angle: 27°


h(m)	E(lx)	D(m)
1	1881	0.48
2	470	0.95
3	209	1.43
4	118	1.91
5	75	2.38


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

The Fast Track Spot 150

LED Array 25,5 W - 2378 lm - 3000K/CRI 90 / 25,5 W - 2751 lm - 4000K/CRI 90








Spotlight to be installed in the The Fast Track system profile with a LED light source and glass optics: high performance spot, medium and flood lights.
The boxes of the luminaries are manufactured only in black.

Proyector para ser instalado en perfil del sistema The Fast Track con fuente de luz LED y ópticas de cristal spot, medium y flood de alto rendimiento.
Las cajas de las luminarias se fabrican solo en negro.

3000K
**Casambi integrated
09.9083.BWA
09.9083.14A

21°
SPOT




Luminous flux luminaire
1793 lm

Beam Angle:	21°	
h(m)	E(lx)	D(m)
1	11085	0.37
2	2771	0.74
3	1232	1.11
4	693	1.48
5	443	1.85

4000K
**Casambi integrated
09.9086.BWA
09.9086.14A

21°
SPOT




Luminous flux luminaire
1938 lm

Beam Angle:	21°	
h(m)	E(lx)	D(m)
1	11981	0.37
2	2995	0.74
3	1331	1.11
4	749	1.48
5	479	1.85

3000K
**Casambi integrated
09.9084.BWA
09.9084.14A

27°
MEDIUM




Luminous flux luminaire
1792 lm

Beam Angle:	27°	
h(m)	E(lx)	D(m)
1	8211	0.49
2	2053	0.98
3	912	1.47
4	513	1.96
5	328	2.44

4000K
**Casambi integrated
09.9087.BWA
09.9087.14A

27°
MEDIUM




Luminous flux luminaire
1938 lm

Beam Angle:	27°	
h(m)	E(lx)	D(m)
1	8880	0.49
2	2220	0.98
3	987	1.47
4	555	1.96
5	355	2.44

3000K
**Casambi integrated
09.9085.BWA
09.9085.14A

36°
FLOOD




Luminous flux luminaire
1547 lm

Beam Angle:	36°	
h(m)	E(lx)	D(m)
1	4521	0.64
2	1130	1.28
3	502	1.92
4	283	2.56
5	181	3.20

4000K
**Casambi integrated
09.9088.BWA
09.9088.14A

36°
FLOOD



Luminous flux luminaire
1673 lm

Beam Angle:	36°	
h(m)	E(lx)	D(m)
1	4890	0.64
2	1222	1.28
3	543	1.92
4	306	2.56
5	196	3.20

Accessories / Accesorios

The Fast Track Spot 150





Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.
Installation compatible with honeycomb + lense at the same time.

Cruceta de apantallamiento, lentes y honeycomb directamente instalables en la cabeza de la luminaria sin necesidad de accesorio de sujeción.
Compatibilidad de instalación de honeycomb + lente al mismo tiempo.

Screening crosspiece.	Cruceta de apantallamiento.		08.8429.00
Elliptical lens.	Lente elíptica.		08.8431.00
Flood lens.	Lente flood.		08.8432.00
Honeycomb.	Honeycomb.		08.8428.00
Snoot shielding cone.	Cono apantallador.		08.0526.00 08.0526.40 08.0526.BW


** The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi / El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

Drivers / Equipos


LED power supply source for remote installation, 48V/320W. 100/240 Vac.	Fuente de alimentación LED para instalación remota, 48V/320W. 100/240 Vac.			*60.8919
LED power supply source for remote installation, 110Vac-135W / 220Vac-200W.	Fuente de alimentación LED para instalación remota, 110Vac-135W / 220Vac-200W.			*60.9607
LED power supply source for remote installation, 48V/120W. 220/240 Vac.	Fuente de alimentación LED para instalación remota, 48V/120W. 220/240 Vac.			*60.9170
Multifunction Smart Device. Triple functionality 3x1: Casambi signal repeater, light sensor and presence detector. FLOS Control® by Casambi.	Dispositivo multifunción inteligente. Triple funcionalidad 3x1: repetidor de señal Casambi, sensor de luz ambiental y detector de presencia. FLOS Control® by Casambi.			06.1987.40 06.1987.14

Multifunction Smart Device. Triple Functionality 3x1


Repeater



Daylight Sensor



Presence Sensor



▲ Casambi object

* For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source / Para el dimensionado de la instalación mantener un margen de seguridad de un 15% de la potencia máxima de la fuente de alimentación LED.


IN-FINITY

DESIGNED BY FLOS ARCHITECTURAL

RECESSED

SURFACE

SUSPENSION
UP&DOWN / DOWN



Recessed
No Trim

Recessed
Trim

Surface

Suspension
Down

Suspension
Up&Down

Description
Built-in, surface or suspended LED lighting system (see type of mounting, depending on the model) designed for work areas and professional spaces. The lights are available in widths of 25 mm, 35 mm or 70 mm.
In the 25 mm wide model:
- The system is modular and consists of straight elements measuring between 1000 mm and 3000 mm, and accessories such as special kits and covers for suspended installation (with suspension and power cables). Each module can be connected to others mechanically. Electrically, each module operates with a separate power input connected to a driver (either dedicated to one module or shared between several).
- The LED module, profile, reflector and diffuser are offered together as one complete element under a single sale code (in the 5 lengths available).

In the 35 and 70 mm wide models:
- The system is modular and consists of straight elements measuring between 565 mm and 3095 mm, angled in the same plane or with ceiling-wall plane variations, and accessories such as covers and suspension kits. Each module can be connected to others mechanically and electrically. Electrically, the entire modular arrangement is powered from just one point.
- The lights are complete with:
  · LED light modules with driver included, in 3000K and 4000K versions.
  · Aluminium profile for installation.
  · Reflector.
  · Module connection system.
  · Fall-prevention safety cable for the lights, to ensure maximum protection during installation operations.
  · Two different diffusers available: opal for general lighting or micro-prism for increased visual comfort. Also available as a separate accessory to complete gaps in structures with corners or lengths greater than 3 m.
- The exterior profile in the Recessed No Trim version is only available in a white finish. All other versions are available with the following finishes: white, anodised grey and black.

Power supply units
In the 25 mm wide model:
- Drivers not included, see recommended equipment.

In the 35 and 70 mm wide models:
- Drivers included in lighting modules for direct connection to 220-240V network or to other system modules.

Accessories
If necessary for the installation, the following accessories must be requested separately for all models:
- Covers.
- Suspension kits.
- Power supply kits.

Additional information
In the 25 mm wide model:
- For adjustable options seek advice.
- IP20 protection rating.
- Insulation class III.

In the 35 and 70 mm wide models:
- DALI 1-100% version available.
- 1-10V dimmable version on request.
- IP20, IP40 protection rating.
- Insulation class I.

Combining models 25 and 35/70 may result in the light having slight colour differences. It is not advisable to combine model 25 with the 35/70 in shared spaces.

Before ordering, view the product details in the specifications on the Flos website, the technical sheet and the installation and assembly instructions, in order to fully understand information that may not appear in the catalogue, and which may be relevant for your actual project or installation.

Compliance with Standards and Quality Standards
The light complies with EU technical standard EN60598-1 and the sections contained within.

Descripción
Sistema de iluminación LED empotrado, de superficie o suspendido (consultar tipo de 'mounting', según modelo), diseñado para áreas de trabajo y espacios profesionales. Las luminarias están disponibles en anchos de 25 mm, 35 mm ó 70 mm.
En el modelo con ancho de 25 mm:
- El sistema es modular y se compone de elementos rectos con medidas desde 1000 mm a 3000 mm y accesorios como tapas y kits especiales para instalación suspendida (con cables de suspensión y de alimentación). Cada módulo se puede conectar mecánicamente entre sí. Eléctricamente, cada módulo funciona con una entrada de alimentación independiente vinculada a un driver (que podrá ser dedicado a un módulo o compartido para varios).
- El módulo LED, el perfil, reflector y difusor se ofrecen en conjunto como un solo elemento completo bajo un único código de venta (en las 5 opciones de longitud disponibles).

En modelos con anchos de 35 y 70 mm:
- El sistema es modular y se compone de elementos rectos con medidas desde 565 mm hasta 3095 mm, ángulo en la misma superficie o con cambio de plano techo-pared, y accesorios como tapas y kit de suspensión. Cada módulo se puede conectar eléctrica y mecánicamente entre sí. Eléctricamente, toda la composición modular se alimenta desde un solo punto.
- Las luminarias se completan con:
  · Módulos de luz LED con driver incluido, en versiones de 3000K y 4000K.
  · Perfil de aluminio por instalación.
  · Reflector.
  · Sistema de unión para la conexión de los módulos.
  · Cable de seguridad anti-caída de las luminarias, para garantizar la máxima protección en los trabajos de instalación.
  · Disponibles dos difusores diferentes: opal para iluminación general o difusor micro-prismático para un mayor confort visual. Disponibles también como accesorio separado para completar huecos en estructuras con esquinas o de longitud mayor de 3 m.
- El perfil exterior de la versión Recessed No Trim solo está disponible en acabado blanco. Todas las demás versiones están disponibles en los acabados: blanco, gris anodizado y negro.

Unidades de Alimentación
En el modelo con ancho 25 mm:
- Drivers no incluidos, consultar equipos recomendados.

En modelos con anchos de 35 y 70 mm:
- Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema.

Accesorios
En todos los modelos, si la instalación lo requiere, se deben pedir por separado los siguientes accesorios disponibles:
- Tapas.
- Kit de suspensión.
- Kit de alimentación.

Información Adicional
En el modelo de ancho 25 mm:
- Para opciones regulables, consultar.
- Índice de protección IP20.
- Clase de aislamiento III.

En modelos con anchos de 35 y 70 mm:
- Disponible en versión DALI 1-100%.
- Versión dimable 1-10V bajo pedido.
- Índice de protección IP20, IP40.
- Clase de aislamiento I.

La combinación de modelos 25 y 35/70 puede acarrear pequeñas diferencias de cromaticidad en la luz. Se recomienda no combinar el modelo 25 con el 35/70 en espacios compartidos.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

IN-FINITY

DESIGNED BY FLOS ARCHITECTURAL

SURFACE




SUSPENSION DOWN




25 mm

LIGHT SOURCE
TOP LED
19,5W/m
2103 lm/m
3000K/CRI 90
2195 lm/m
4000K/CRI 90

RECESSED TRIM / NO TRIM



SURFACE



SUSPENSION DOWN



35 mm

LIGHT SOURCE
TOP LED
18,5W/m
2665 lm/m
3000K/CRI 80
18,5W/m
2800 lm/m
4000K/CRI 80

70 mm

LIGHT SOURCE
TOP LED
25W/m
2985 lm/m
3000K/CRI 80
25W/m
3135 lm/m
4000K/CRI 80

SUSPENSION UP&DOWN



35 mm

LIGHT SOURCE
TOP LED
31,5W/m
1785 lm/m UP
2665 lm/m DOWN
3000K/CRI 80
31,5W/m
1875 lm/m UP
2800 lm/m DOWN
4000K/CRI 80

70 mm

LIGHT SOURCE
TOP LED
38W/m
1785 lm/m UP
2985 lm/m DOWN
3000K/CRI 80
38W/m
1875 lm/m UP
3135 lm/m DOWN
4000K/CRI 80

25

40 White
40 Blanco

29 Anodized Grey
29 Gris Anodizado



AN Black Anodized
AN Negro Anodizado




---


35 / 70

30 White
30 Blanco

02 Anodized Grey
02 Gris Anodizado




14 Black
14 Negro



In-Finity 25 mm

Top LED 19,5W/m - 2103 lm/m - 3000K/CRI 90 / 19,5W/m - 2195 lm/m - 4000K/CRI 90





LED profile for linear lighting, only 25 mm wide. Available in surface mounted versions, with possibility of suspended installation by means of a dedicated kit. Drivers not included.

Perfil LED para iluminación lineal de solo 25mm de anchura. Disponible en versiones de superficie, con posibilidad de instalación suspendida mediante kit dedicado. Drivers no incluidos.

Recommended power supply / Equipos recomendados*:

Non Dimmable 220-240V 60W	60.9705
Non Dimmable 220-240V 60W	60.9515
Non Dimmable 220-240V 120W	60.9516

* Refer to the Drivers chapter / Ver capítulo Drivers

3000K


L: 1000 mm
- 03.5330.40
- 03.5330.29
- 03.5330.AN

L: 1500 mm
- 03.5331.40
- 03.5331.29
- 03.5331.AN

L: 2000 mm
- 03.5332.40
- 03.5332.29
- 03.5332.AN

L: 2500 mm
- 03.5333.40
- 03.5333.29
- 03.5333.AN

L: 3000 mm
- 03.5334.40
- 03.5334.29
- 03.5334.AN



Luminous flux luminaire
1008 lm *L: 1000 mm

Beam Angle: 91°

h(m)	E(lx)	D(m)
1	425	2.04
2	106	4.07
3	47	6.11
4	27	8.15
5	17	10.18

4000K


L: 1000 mm
- 03.5335.40
- 03.5335.29
- 03.5335.AN

L: 1500 mm
- 03.5336.40
- 03.5336.29
- 03.5336.AN

L: 2000 mm
- 03.5337.40
- 03.5337.29
- 03.5337.AN

L: 2500 mm
- 03.5338.40
- 03.5338.29
- 03.5338.AN

L: 3000 mm
- 03.5339.40
- 03.5339.29
- 03.5339.AN



Luminous flux luminaire
1053 lm *L: 1000 mm

Beam Angle: 91°

h(m)	E(lx)	D(m)
1	444	2.04
2	111	4.07
3	49	6.11
4	28	8.15
5	18	10.18

Accessories / Accesorios

Metal end cap for the different profiles.
2 unit kit.

Tapa metálica para los diferentes perfiles.
Kit de 2 unidades.



- 08.0131.40
- 08.0131.29
- 08.0131.14

One unit suspension kit (L = 4 m). Maximum distance between the suspension cables: 850mm. Ceiling anchor dimensions (h=63mm, d=22mm) and anchor to profile (l=63mm a=22mm h=7,5mm)

Kit de suspensión de una pieza (L = 4 m). La distancia máxima entre los cables de suspensión es de 850mm. Dimensiones anclaje a techo (h=63mm, d=22mm) y anclaje a perfil (l=63mm a=22mm h=7,5mm)



08.0139.00

5-meter long, power cable. To use with remote drivers.

Cable de alimentación de 5m de longitud. Para usar con drivers remotos.



- 06.0420.30
- 06.0420.14


IN-FINITY 35 & 70

Profiles

Straight elements of different lengths and corner elements, to be composed according to the specific need of each project or to be completed by a pair of end caps and used as a single lamp.
All system elements are completely illuminated by an included LED module, the required driver, installation channel, and the diffuser for the version selected. Custom X or T elements available under request.

Perfiles

Elementos lineales y angulares de iluminación de distintas longitudes, para ser unidos dependiendo de las necesidades específicas de cada proyecto, o ser completadas con una tapa en cada extremo para ser utilizado como una única luminaria.
Todos los elementos del sistema están completamente iluminados por módulos LED que se encuentran incluidos, e incluyen además los drivers necesarios, canal de instalación y difusor de la versión seleccionada.
Elementos X o T custom disponibles bajo pedido.




Flat Corner / Esquina Plana

Corner element lamps for angles on the same surface, complete with a driver, installation channel and the diffuser for the version selected.

Luminaria de esquina para ángulos que se mantienen en la misma superficie, completada con el driver, el canal de instalación y el difusor de la versión seleccionada.






*L: 586 mm - N35 / L: 603 mm - N70

Dihedral Corner / Esquina Diédrica

Corner element lamps for angles with surface changes (example: angle ceiling / wall), complete with a driver, installation channel and the diffuser for the version selected. For suspended versions not available.

Luminaria de esquina para ángulos con cambio de superficie (ejemplo: ángulo de techo a pared), completada con el driver, el canal de instalación y el difusor de la versión seleccionada. No está disponible para versiones suspendidas.






*35 mm section

Emergency / Emergencia

Emergency module available for all versions except for the Up&Down version. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours.

Módulo de emergencia disponible en todas las versiones, excepto la versión Up&Down. En uso normal, mismo consumo que el In-Finity estándar. En uso de emergencia, emite un 10% del flujo normal durante 3 horas.



L: 1405 mm

***Opal Diffuser / Difusor Opal**

Diffuse, glare free and uniform lighting throughout the room.
Also available as separate accessory to fill gaps in structures with corners or longer than 3 meters.

Iluminación ambiental difusa, uniforme y apantallada.
Disponible también como accesorio separado para completar huecos en estructuras con esquinas o de longitud mayor de 3 m.



***Micro-Prismatic Diffuser / Difusor Microprismático**

Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam.
Also available as separate accessory to fill gaps in structures with corners or longer than 3 meters.

Difusor de alta eficiencia para iluminación apantallada de UGR<19, gracias a su especial textura microprismática multi-estrato.
Disponible también como accesorio separado para completar huecos en estructuras con esquinas o de longitud mayor de 3 m.



IN-FINITY 35 & 70

HOW TO GET YOUR CODE / CÓMO OBTENER SU CÓDIGO

For a quicker understanding and easier overview of the range, the part number structure for the In-Finity family has been created to be composed to match the requests of each specific installation.
According to the following table, for each field, just choose the number or letter corresponding to the In-Finity version you need, and you'll have the final code.

Para una comprensión más rápida y una visión general de la gama, la estructura de la numeración de las partes de la familia In-Finity se ha creado para que coincida, una vez compuesto, con las peticiones específicas de cada instalación.
De acuerdo con la siguiente tabla, para cada campo, simplemente seleccione el número o la letra correspondiente a la versión In-Finity que necesite, y obtendrá el código final.

N 70 S 25 4 U 14B DA

Section / Sección

35 mm	35
70 mm	70

***Installation / Instalación**

Recessed Trim	T
Recessed No Trim	N
Surface	S
Suspension Down	D
Suspension Up&Down	U

Elements / Elementos

Straight / Lineal 565 mm	05
Straight / Lineal 845 mm	08
Straight / Lineal 1125 mm	11
Straight / Lineal 1405 mm	14
Straight / Lineal 1690 mm	16
Straight / Lineal 1970 mm	19
Straight / Lineal 2530 mm	25
Straight / Lineal 3095 mm	30
Flat Corner / Esquina Plana	FC
Dihedral Corner / Esquina Diédrica	DC
Emergency / Emergencia (1405 mm)	EM

Color Tª / Temperatura de Color (°K)

3000K	3
4000K	4

****Optic / Óptica**

General Lighting (Opal)	G
Micro-Prismatic Diffuser	U

Colours / Colores

White / Blanco	30B
Anodized Grey / Gris Anodizado	02B
Black / Negro	14B

Version / Versión

Standard (Non Dimmable)	
Dali	DA

*No Trim Recessed version is only available in white finish (30) / La versión Recessed No Trim solo está disponible en acabado blanco (30).

*In Suspension versions only available flat corner / En las versiones Suspension solo está disponible la esquina plana.


*Suspension Up&Down version is not available in 565 mm linear profile / En la versión Suspension Up&Down no está disponible el perfil lineal de 565 mm.

**Also available as separate accessories to fill gaps in structures with corners or longer than 3 m / Disponibles también como accesorio separado para completar huecos en estructuras con esquinas o de longitud mayor de 3 m.

In-Finity Recessed Trim 35 mm

Top LED 18,5W/m - 2665 lm/m - 3000K/CRI 80 / 18,5W/m - 2800 lm/m - 4000K/CRI 80








LED modular system for recessed trim/no trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Sistema modular de iluminación LED empotrado trim/no trim, compuesto de módulos LED, perfil de aluminio y difusor. Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema.


In-Finity Recessed No Trim 35 mm







OPAL




Luminous flux luminaire
1242 lm *L: 1000 mm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	434	2.84
2	108	5.68
3	48	8.52
4	27	11.36
5	17	14.19



MICRO-
PRISMATIC




Luminous flux luminaire
968 lm *L: 1000 mm


Beam Angle: 76°

h(m)	E(lx)	D(m)
1	525	1.55
2	131	3.11
3	58	4.66
4	33	6.22
5	21	7.77

In-Finity Recessed Trim 70 mm

Top LED 25W/m - 2985 lm/m - 3000K/CRI 80 / 25W/m - 3135 lm/m - 4000K/CRI 80








LED modular system for recessed trim/no trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


Sistema modular de iluminación LED empotrado trim/no trim, compuesto de módulos LED, perfil de aluminio y difusor. Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema.

In-Finity Recessed No Trim 70 mm





OPAL




Luminous flux luminaire
1880 lm *L: 1000 mm

Beam Angle:		103°
h(m)	E(lx)	D(m)
1	705	2.51
2	176	5.03
3	78	7.54
4	44	10.05
5	28	12.57



MICRO-PRISMATIC




Luminous flux luminaire
1915 lm *L: 1000 mm

Beam Angle:		72°
h(m)	E(lx)	D(m)
1	1114	1.46
2	278	2.92
3	124	4.38
4	70	5.84
5	45	7.30

In-Finity Surface 35 mm

Top LED 18,5W/m - 2665 lm/m - 3000K/CRI 80 / 18,5W/m - 2800 lm/m - 4000K/CRI 80





IP 40

GWT 850°


1 - 100% DALI

LED INCL.

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Sistema modular de iluminación LED para superficie, compuesto de módulos LED, perfil de aluminio y difusor. Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema.

110° OPAL




Luminous flux luminaire
1242 lm *L: 1000 mm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	434	2.84
2	108	5.68
3	48	8.52
4	27	11.36
5	17	14.19

76° MICRO-PRISMATIC




Luminous flux luminaire
968 lm *L: 1000 mm


Beam Angle: 76°

h(m)	E(lx)	D(m)
1	525	1.55
2	131	3.11
3	58	4.66
4	33	6.22
5	21	7.77

In-Finity Surface 70 mm

Top LED 25W/m - 2985 lm/m - 3000K/CRI 80 / 25W/m - 3135 lm/m - 4000K/CRI 80





IP 40

GWT 850°


1 - 100% DALI

LED INCL.

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Sistema modular de iluminación LED para superficie, compuesto de módulos LED, perfil de aluminio y difusor. Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema.

103° OPAL




Luminous flux luminaire
1880 lm *L: 1000 mm

Beam Angle: 103°

h(m)	E(lx)	D(m)
1	705	2.51
2	176	5.03
3	78	7.54
4	44	10.05
5	28	12.57

72° MICRO-PRISMATIC




Luminous flux luminaire
1915 lm *L: 1000 mm


Beam Angle: 72°

h(m)	E(lx)	D(m)
1	1114	1.46
2	278	2.92
3	124	4.38
4	70	5.84
5	45	7.30

In-Finity Suspension Down 35 mm

Top LED 18,5W/m - 2665 lm/m - 3000K/CRI 80 / 18,5W/m - 2800 lm/m - 4000K/CRI 80





IP 20

GWT 850°


1 - 100% DALI

LED INCL

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Sistema modular de iluminación LED suspendido, compuesto de módulos LED, perfil de aluminio y difusor. Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema. Kit de suspensión no incluido.

110° OPAL




Luminous flux luminaire
1242 lm *L: 1000 mm

Beam Angle: 110°

h(m)	E(lx)	D(m)
1	434	2.84
2	108	5.68
3	48	8.52
4	27	11.36
5	17	14.19

76° MICRO-PRISMATIC



Luminous flux luminaire
968 lm *L: 1000 mm


Beam Angle: 76°

h(m)	E(lx)	D(m)
1	525	1.55
2	131	3.11
3	58	4.66
4	33	6.22
5	21	7.77

In-Finity Suspension Down 70 mm

Top LED 25W/m - 2985 lm/m - 3000K/CRI 80 / 25W/m - 3135 lm/m - 4000K/CRI 80





IP 20

GWT 850°


1 - 100% DALI

LED INCL

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Sistema modular de iluminación LED suspendido, compuesto de módulos LED, perfil de aluminio y difusor. Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema. Kit de suspensión no incluido.

103° OPAL




Luminous flux luminaire
1880 lm *L: 1000 mm

Beam Angle: 103°

h(m)	E(lx)	D(m)
1	705	2.51
2	176	5.03
3	78	7.54
4	44	10.05
5	28	12.57

72° MICRO-PRISMATIC




Luminous flux luminaire
1915 lm *L: 1000 mm


Beam Angle: 72°

h(m)	E(lx)	D(m)
1	1114	1.46
2	278	2.92
3	124	4.38
4	70	5.84
5	45	7.30

In-Finity Suspension Up&Down 35 mm

Top LED 31,5W/m - 1785 lm/m UP - 2665 lm/m DOWN - 3000K/CRI 80 / 31,5W/m - 1875 lm/m UP - 2800 lm/m DOWN - 3000K/CRI 80





IP 20

GWT 850°


1 - 100% DALI

LED INCL

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Sistema modular de iluminación LED suspendido, compuesto de módulos LED, perfil de aluminio y difusor. Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema. Kit de suspensión incluido.

103° OPAL




Luminous flux luminaire
2178 lm *L: 1000 mm

Beam Angle: 103°

h(m)	E(lx)	D(m)
1	730	1.55
2	182	3.11
3	81	4.66
4	46	6.22
5	29	7.77

76° MICRO-PRISMATIC



Luminous flux luminaire
2094 lm *L: 1000 mm


Beam Angle: 76°

h(m)	E(lx)	D(m)
1	702	1.55
2	175	3.11
3	78	4.66
4	44	6.22
5	28	7.77

In-Finity Suspension Up&Down 70 mm

Top LED 38W/m - 1785 lm/m UP - 2985 lm/m DOWN - 3000K/CRI 80 / 38W/m - 1875 lm/m UP - 3135 lm/m DOWN - 4000K/CRI 80





IP 20

GWT 850°


1 - 100% DALI

LED INCL

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Sistema modular de iluminación LED suspendido, compuesto de módulos LED, perfil de aluminio y difusor. Drivers incluidos en los módulos de iluminación para conexión directa a red 220-240V o a otros módulos del sistema. Kit de suspensión incluido.

103° OPAL




Luminous flux luminaire
3062 lm *L: 1000 mm

Beam Angle DIR: 103°

h(m)	E(lx)	D(m)
1	705	2.51
2	176	5.03
3	78	7.54
4	44	10.05
5	28	12.57

72° MICRO-PRISMATIC



Luminous flux luminaire
3108 lm *L: 1000 mm

Beam Angle DIR: 72°

h(m)	E(lx)	D(m)
1	1115	1.46
2	279	2.92
3	124	4.38
4	70	5.84
5	45	7.30

Accessories / Accesorios

Metal end cap for the different profiles.
2 unit kit.

Contact Flos Architectural team for a configuration without end caps.

*No Trim Recessed version is only available in white finish (40).

Tapa metálica para los diferentes perfiles.
Kit de 2 unidades.

Consultar al equipo Flos Architectural para una configuración sin tapas.

*La versión Recessed No Trim solo está disponible en acabado blanco (40).



Recessed Trim

35 mm
- 08.9051.40
- 08.9051.02
- 08.9051.NS

70 mm
- 08.9053.40
- 08.9053.02
- 08.9053.NS

Recessed No Trim*/ Surface / Suspension Down

35 mm
- 08.9050.40
- 08.9050.02
- 08.9050.NS

70 mm
- 08.9052.40
- 08.9052.02
- 08.9052.NS

Suspension Up&Down

35 mm
- 08.9056.40
- 08.9056.02
- 08.9056.NS

70 mm
- 08.9057.40
- 08.9057.02
- 08.9057.NS

One unit suspension kit (L = 4 m). Maximum distance between the suspension cables: 2 m. Ceiling anchor dimensions (h=63mm, d=22mm) and anchor to profile (l=36mm a=24mm h=9mm)

Kit de suspensión de una pieza (L = 4 m). La distancia máxima entre los cables de suspensión es de 2 m. Dimensiones anclaje a techo (h=63mm, d=22mm) y anclaje a perfil (l=36mm a=24mm h=9mm)



08.0030

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable.

Rosetón de alimentación para la instalación suspendida del In-Finity. La versión estándard se suministra con cable de tres polos para encendido simple. La versión Dali se suministra con cable de cinco polos que puede ser utilizado para el encendido doble independiente de la luz directa e indirecta en la versión Up&Down estándard. Incluye cable de suspensión de 4 m.



08.0031.00
Dali Version
08.0031.00.DA

---

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room.
Accessory to fill gaps in structures with corners or longer than 3 meters.

Accesorio difusor opal de 500 mm. Iluminación ambiental difusa, uniforme y apantallada.
Accesorio para completar huecos en estructuras con esquinas o de longitud mayor de 3 m.



In-Finity 35
08.0109.00
In-Finity 70
08.0110.00

---

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam.
Accessory to fill gaps in structures with corners or longer than 3 meters.

Accesorio microprismático opal de 500 mm. Difusor de alta eficiencia para iluminación apantallada de UGR<19, gracias a su especial textura microprismática multi-estrato.
Accesorio para completar huecos en estructuras con esquinas o de longitud mayor de 3 m.




In-Finity 35
08.0112.00
In-Finity 70
08.0113.00

LIGHT CUT MINI

DESIGNED BY FLOS ARCHITECTURAL

PERIMETRAL 70 mm 140 mm



SPOTS MODULES



LIGHT SOURCE
LED ARRAY
18W
1850 lm
3000K/CRI 90

LIGHT SOURCE
LED ARRAY
HIGHT
PERFORMANCE
18W
2193 lm
3000K/CRI 90



LIGHT SOURCE
LED ARRAY
14,4W
1380 lm
3000K/CRI 90

☐ 30 Matte White
30 Blanco Mate



■ 14 Matte Black
14 Negro Mate



Description
Lighting system comprising an extruded profile which integrates perfectly in plasterboard ceilings. It is prepared for the simple integration of lighting with LED projectors. The projectors are prepared for installation directly on the profile, with Class II remote equipment. Furthermore, they are available in two sizes depending on the installation.

Light Source
Possibility to integrate a different type of LED upon request. For more information, please contact our team.

Additional Information
Can only be installed in 12.5 mm thick plaster-board.
It is possible to cut the profiles to any size.
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Sistema de iluminación que se compone de un perfil de extrusión que se integra perfectamente en techos realizados en cartón yeso. Está preparado para integrar de una forma sencilla iluminación con proyectores LED. Los proyectores están preparados para ser instalados directamente sobre el perfil, con equipos remotos de clase II. Además están disponibles en dos tamaños en función de la instalación.

Fuente de luz
Posibilidad de integrar otro tipo de LED bajo demanda. Para más información, no dude en contactar con nuestro equipo.

Información Adicional
Únicamente instalable en superficies de cartón-yeso de 12,5 mm de espesor.
Es posible cortar los perfiles a cualquier medida.
Índice de protección IP20.
Instalable sobre superficies normalmente inflamables.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Profiles
Spot Module
Spot Module Electrical Connection

Channel 70 / Channel 140 Installation


Structural system in aluminium to integrate in plasterboard ceilings. It allows incorporation of projectors. Channel installation consists of 1 or 2 meter profiles, double inside and outside corners. It is possible to cut the profiles to any size.

Instalación Canal 70 / Canal 140

Sistema estructural realizado en aluminio para integrar en techos realizados en cartón yeso. Permite incorporar proyectores. Para la instalación en canal se compone de perfiles de 1 ó 2 metros, esquinas interiores y exteriores dobles. Es posible cortar los perfiles a cualquier medida.

Aluminium profile. 2 unit kit.


Perfil de aluminio. Kit de 2 unidades.




Channel 70 / 140
L: 1000 mm
08.8720.30
08.8720.14
L: 2000 mm
08.8721.30
08.8721.14

End cap.


Terminal.





Channel 70
08.8705.30
08.8705.14






Channel 140
08.8706.30
08.8706.14

Corner.


Esquina.





Channel 70
08.8707.30
08.8707.14







Channel 140
08.8708.30
08.8708.14

Perimetral Installation

Structural system in aluminium to integrate in plasterboard ceilings. It allows incorporation of projectors. Perimetral installation consists of 1 or 2 meter profiles, inside and outside corners. It is possible to cut the profiles to any size.

Instalación Perimetral


Sistema estructural realizado en aluminio para integrar en techos realizados en cartón yeso. Permite incorporar proyectores. Para la instalación permiteral se compone de perfiles de 1 ó 2 metros, esquinas interiores y exteriores. Es posible cortar los perfiles a cualquier medida.


Aluminium profile. 1 unit kit.	Perfil de aluminio. Kit de 1 unidad.			L: 1000 mm 08.8701.30 08.8701.14 L: 2000 mm 08.8702.30 08.8702.14
Inner corner.	Esquina interior.			08.8709.30 08.8709.14
Outer corner.	Esquina exterior.			08.8710.30 08.8710.14
Accessory for vertical corner.	Accesorio para esquina vertical.			08.8711.00

Spot Module Pro LED Array

LED Array DC 500 mA - 18W - 1850 lm - 3000K/CRI 90
LED Array High Performance DC 500 mA - 18W - 2193 lm - 3000K/CRI 90







Spotlight to be installed on Light Cut Mini system. Remote continuous current supply source not included. High performance part numbers include high performance reflector.

Proyector para ser instalado en sistema Light Cut Mini. Fuente de alimentación de corriente constante remota no incluida.
Las referencias “High Performance” incluyen reflector de alto rendimiento.


Recommended power supply / Equipos recomendados*:

Non Dimmable 220-240V	60.9160
Dimmable 0/1-10V / Push 220-240V	60.9188
Dimmable DALI 2 110-240V	60.9222
Mains Dimming 220-240V	60.9467
Casambi 220-240V	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

09.0360.30
09.0360.14

11° SPOT




Luminous flux luminaire 1234 lm

Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	13267	0.19
2	3317	0.39
3	1474	0.58
4	829	0.77
5	531	0.97

High Performance
09.0365.30A
09.0365.14A

21° SPOT




Luminous flux luminaire 1803 lm

Beam Angle: 21°		
h(m)	E(lx)	D(m)
1	11366	0.36
2	2842	0.73
3	1263	1.09
4	710	1.46
5	455	1.82

09.0361.30
09.0361.14

20° MEDIUM




Luminous flux luminaire 1207 lm

Beam Angle: 20°		
h(m)	E(lx)	D(m)
1	6553	0.35
2	1638	0.71
3	728	1.06
4	410	1.41
5	262	1.77

High Performance
09.0366.30A
09.0366.14A

27° MEDIUM




Luminous flux luminaire 1717 lm

Beam Angle: 27°		
h(m)	E(lx)	D(m)
1	7830	0.49
2	1957	0.97
3	870	1.46
4	489	1.95
5	313	2.43

09.0362.30
09.0362.14

42° FLOOD




Luminous flux luminaire 1162 lm

Beam Angle: 42°		
h(m)	E(lx)	D(m)
1	2752	0.76
2	688	1.53
3	306	2.29
4	172	3.05
5	110	3.81

High Performance
09.0367.30A
09.0367.14A

34° FLOOD




Luminous flux luminaire 1611 lm


Beam Angle: 34°		
h(m)	E(lx)	D(m)
1	4844	0.62
2	1211	1.24
3	538	1.86
4	303	2.48
5	194	3.10

Spot Module LED Array

LED Array DC 300 mA - 10W - 1380 lm - 3000K/CRI 90







Spotlight to be installed on Light Cut Mini system. Remote continuous current supply source not included.

Proyector para ser instalado en sistema Light Cut Mini. Fuente de alimentación de corriente constante remota no incluida.


Recommended power supply / Equipos recomendados*:

Non Dimmable 220-240V	60.9160
Dimmable 0/1-10V 110-240V	60.9188
Dimmable Dali 2 110-240V	60.8711A
Mains Dim. Trailing Edge 220-240V	60.9421
Casambi 220-240V	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

CRI 90
09.0217.30C
09.0217.14C

26° MEDIUM




Luminous flux luminaire 853 lm

Beam Angle: 26°		
h(m)	E(lx)	D(m)
1	2885	0.46
2	721	0.93
3	321	1.39
4	180	1.86
5	115	2.32

CRI 90
09.0219.30C
09.0219.14C

43° WIDE FLOOD




Luminous flux luminaire 886 lm

Beam Angle: 43°		
h(m)	E(lx)	D(m)
1	1672	0.79
2	418	1.58
3	186	2.37
4	105	3.16
5	67	3.95

CRI 90
09.0218.30C
09.0218.14C

30° FLOOD



Luminous flux luminaire 881 lm

Beam Angle: 30°		
h(m)	E(lx)	D(m)
1	2479	0.53
2	620	1.06
3	275	1.59
4	155	2.11
5	99	2.64

Accessory / Accesorio

Spot module: LED Array

Honeycomb Honeycomb		08.3309.14

HIGH COMFORT

Gustave, EMI, Oblique, Oblique Floor,
Workmates, Light Shadow Mini, Light Shadow,
Light Shadow Pro&Dots, Eclectic,
Circle of Light.

GUSTAVE

DESIGNED VINCENT VAN DUYSEN

GUSTAVE
RESIDENTIAL



LIGHT SOURCE
TOP LED
2,5W
221 lm
2700K/CRI 90

DY Matt White



DR Matt Anthracite



MR Laquered Brown



GX Laquered Green



05 Polished Silver



GUSTAVE

Description
Gustave is a portable indoor lamp with autonomous power supply, specifically designed for tabletop lighting applications and other related uses as auxiliary light. Within its compact dimensions, Gustave brings together a perfect balance of cutting-edge optical-lighting technology and disruptive engineering, developed in service of a specific goal by Flos: to create the first portable luminaire on the market conceived with a circular, ecological design approach and honestly designed against obsolescence.

Optical system
Gustave is the first luminaire to incorporate a system of asymmetric-emission lenses—exclusive and patented by Flos—arranged in rotation to cover 360° around the lamp's position. This pioneering innovation delivers a large illuminated surface relative to the central point of the light source. The width and intensity of the light distribution are designed to optimize illumination for typical applications on tables for 2 to 4 people. As a result, Gustave maximizes the ratio between the space it occupies and the area it illuminates.
Gustave's batteries are replaceable and rechargeable lithium-ion cells in a standard "battery" format, charged via a USB cable. This format is widely available from specialized retailers. This concept, a contemporary update of traditional flashlight batteries, breaks the link between battery lifespan and luminaire obsolescence. When the batteries reach the end of their cycle, they are simply replaced, allowing Gustave to continue operating as on the first day.

Autonomy: management and functionality
When charge drops below 20%, the indicator LED (located on the underside of the head) lights up red. Below 10%, in addition to the red indicator, maximum output is forcibly reduced to 25%. At 0%, the luminaire switches off automatically. Autonomy is 6 h at 100%, 10 h at 50%, and 18 h at 25%. Approximate recharge time is 5–6 h. During charging, the LED remains yellow and turns green when fully charged. Charging with the product switched off is recommended.

Control system
Gustave switches on, off, and dims via a capacitive button located at the base of the head. Dimming is sequential from 0–100% and back. It features last-setting memory and a blink to indicate maximum or minimum output.

Accessories and spare parts
Gustave offers a mains adapter for the USB charging cable as an accessory. Lithium-ion batteries are also available as accessories and/or spare parts. The product is sold with the batteries included. If batteries are purchased from a distributor other than Flos, ensure they meet the dimensional, electrical, and other requirements specified in the instructions.

Additional information
IP54 protection rating.

Standard Compliance and Quality Marks
Luminaire compliant with European Technical Standard EN60598-1 and related parts.

Descripción
Gustave es una lámpara portátil para iluminación interior, con alimentación autónoma, especialmente concebida para aplicaciones de iluminación de sobremesa y otros usos afines como luz auxiliar. En sus contenidas dimensiones, Gustave encierra un equilibrio perfecto entre la más innovadora tecnología óptico-lumínica y una ingeniería disruptiva, desarrollada al servicio de un propósito específico de Flos para este proyecto: crear la primera luminaria portátil del mercado con conciencia de diseño circular, ecológica y honestamente concebida contra la obsolescencia.

Sistema óptico
Gustave es la primera luminaria que incorpora un sistema de lentes de emisión asimétrica —exclusivas y patentadas por Flos— dispuestas en revolución, que abarcan 360° alrededor de la posición de la lámpara. Esta innovación pionera permite obtener una amplia superficie iluminada en relación con el punto central de la fuente luminosa. La amplitud e intensidad de la distribución lumínica se han diseñado para optimizar la luz en aplicaciones arquetípicas para mesas de 2 a 4 comensales. Así, con Gustave se maximiza la relación entre la superficie ocupada por la lámpara y el área iluminada.
Las baterías de Gustave son celdas de ion-litio tipo "pila", reemplazables y recargables mediante un cable USB. Este formato es estándar y fácil de adquirir en distribuidores especializados. Este concepto, una actualización contemporánea de las pilas de las linternas clásicas, rompe el vínculo entre la vida útil de las baterías y la obsolescencia de la lámpara. Al final de su ciclo, se sustituyen por otras nuevas y Gustave sigue funcionando como el primer día.

Autonomía: gestión y funcionalidad
Cuando Gustave desciende del 20% de carga, se enciende en rojo el LED indicador (situado en la parte inferior de la cabeza). Al bajar del 10%, además del indicador rojo, la intensidad máxima se atenúa forzadamente al 25%. Al llegar al 0%, la luminaria se apaga automáticamente. La autonomía es de 6 h al 100%, 10 h al 50% y 18 h al 25%. El tiempo aproximado de recarga es de 5 a 6 h. Durante la carga, el LED permanece en amarillo y, al completarse, cambia a verde. Se recomienda cargar el producto apagado.

Sistema de control
Gustave se enciende, apaga y regula mediante un botón capacitativo situado en la base de la cabeza. La regulación es secuencial de 0–100% y viceversa. Dispone de memoria de última posición y parpadeo para indicar el máximo o el mínimo.

Accesorios y recambios
Gustave ofrece como accesorio un adaptador a corriente para el cable de carga USB. Las pilas de ion-litio también están disponibles como accesorios y/o repuestos. El producto se vende con las pilas incluidas. Si se adquieren pilas a un distribuidor distinto de Flos, es importante verificar que cumplen los requisitos dimensionales, eléctricos y demás indicados en las instrucciones.


Información adicional
Índice de protección IP54.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Gustave Residential

Top Array DC 60 mA - 2,5W - 221 lm - 2700K/CRI 90 / 2,5W - 235 lm - 3000K/CRI 90






Portable luminaire for indoor lighting with autonomous battery, designed for residential applications. Powered by 'Button Type 18650 Li-Ion' batteries (2 units, included inside the product). USB-C charging cable (plug adapter not included). 0-100% sequential regulation by means of capacitive haptic push button.

Luminaria portátil para iluminación interior con batería autónoma, diseñada para aplicaciones residenciales. Funciona con baterías 'Button Type 18650 Li-Ion' (2 unidades, incluidas dentro del producto). Cable de carga USB-C (adaptador de enchufe no incluido). Regulación secuencial 0-100% mediante pulsador háptico capacitivo.

2700K

- 09.8405.DY
- 09.8405.DR
- 09.8405.MR
- 09.8405.GX
- 09.8405.05






Luminous flux luminaire
159 lm

Beam Angle: 145°

h(m)	E(lx)	D(m)
1	22	6.28
2	6	12.56
3	2	18.84
4	1	25.11
5	1	31.39

HOW TO ORDER GUSTAVE

Gustave Residential



Battery Pack
(Included)




Accessories & Spare parts

Cable for Gustave Residetial
(Included)



White Cable
Black Cable

Adapter 5V. Min 2A
(Not included)




Accessories (Residential) / Accesorios (Residential)

Adapter 5V. Min 2A.
EUR / USA / UK

Adaptador 5V. Min 2A.
EUR / USA / UK





Residential
RF27576
RF25965

Spare parts (Residential) / Repuestos (Residential)

Battery pack - Button Type
ICR18650 Li-Ion. 2600 mAh
by HWE

Pack Pilas - Button Type
ICR18650 Li-Ion. 2600 mAh
by HWE





Residential
Pack x2
08.0744.00

Cable for Gustave Residetial
USB-A/USB-C. - L= 1,2m.

Cable para Gustave Residetial
USB-A/USB-C. - L= 1,2m.



Residential
08.0761.14
08.0761.30

* Strict dimensional range / Rango dimensional estricto.

NEW

EMI

DESIGNED BY ERWAN BOUROULLEC



NEW

Description
Emi, designed by Erwan Bouroullec, combines different light sources with high visual comfort to create a unique experience of light and shadow. This intriguing contrast is achieved through the combination of an opaque, monolithic body with high-lumen optical assemblies and invisible light sources.
The design of this collection is based on the grouping of three luminous modules within compact linear extrusions, giving the lamp its triangular shape, which is reflected throughout its design. The main section, the stem, and the tiers share this shape, creating a coherent and aesthetically balanced structure.
Emi is primarily made of metals: the lamp base is cast iron, while the rod and main body are aluminum. Polymers are used for the upper and lower sections.
Significant efforts have been made to minimize surfaces and thicknesses across the collection to optimize material use.
The Emi collection is available in two versions: floor and table.

Models and optical system
The floor version of Emi appears to float in the air, lightened by a stem connecting it to the base, maintaining the triangular identity that characterizes the ceiling version. The lighting of this model is bidirectional: the upper light is powerful enough to illuminate the space without glare, thanks to the specific shape of the light beam. The lower light is soft and diffused, ideal for combining with other light sources, such as a television.
The table version functions similarly to the floor version, but with reduced dimensions, fitting perfectly and discreetly on any horizontal surface.

Control systems
The Floor and Table versions can be dimmed using capacitive Touch Dimming sensors located at the top of the central stem.

Additional information
Emi's advanced technology perfectly complements sustainable design. The lamp body is mainly made of aluminum (partially recycled and fully recyclable), ensuring a reduced environmental impact.
Durability is another key element of Emi's design. The product is designed to last, avoiding waste and rapid obsolescence. Each optical unit can be replaced individually for easy maintenance, while the absence of glues and welds simplifies disassembly and proper disposal of individual parts at the end of the product's life.
Before placing an order, also check the product details on the professional Flos website, the datasheet, and installation instructions to obtain all relevant information not included in this catalog.

Compliance with Standards and Quality Marks
Luminaire compliant with European Technical Standard EN60598-1 and related parts.

Descripción
Emi, diseñada por Erwan Bouroullec, combina diferentes fuentes de luz de alto confort visual para crear una experiencia única de luces y sombras. Este intrigante contraste se consigue gracias a la unión de un cuerpo opaco y monolítico con conjuntos ópticos de alto flujo lumínico y con origen de luz invisible.
El diseño de esta colección se concreta a partir de la agrupación de tres módulos luminosos dentro de extrusiones lineales y compactas, que dan a la lámpara su forma triangular que se refleja en todo su diseño. La sección principal, el poste y las gradas comparten esta forma, creando una estructura coherente y estéticamente equilibrada.
Emi se fabrica principalmente con metales: la base de la lámpara es de hierro fundido, mientras que la varilla y el cuerpo principal son de aluminio. Se utilizan polímeros para las secciones superior e inferior.
Se han realizado importantes esfuerzos para minimizar superficies y espesores en toda la colección con el fin de optimizar el uso de materiales.
La colección Emi está disponible en dos versiones: de pie y de mesa.

Modelos y sistema óptico
La versión de pie de Emi parece flotar en el aire, aligerada por un tallo que la une a la base, manteniendo la identidad triangular que caracteriza a la versión de techo. La iluminación de este modelo es bidireccional: en la parte superior, la luz es lo suficientemente potente como para iluminar todo el espacio sin deslumbrar, gracias a la forma particular del haz de luz. En la parte inferior, la luz es suave y difusa, perfecta para combinar con otras fuentes de luz como un televisor.
La versión de mesa de Emi funciona de manera similar a la versión de pie, pero con dimensiones reducidas, adaptándose a la perfección y de forma discreta a cualquier superficie horizontal.

Sistemas de control
Las versiones Floor y Table se pueden regular mediante sensores capacitativos Touch Dimming ubicados en la parte superior del tallo central.

Información adicional
La tecnología avanzada de Emi combina perfectamente con el diseño sostenible. El cuerpo de la lámpara está fabricado principalmente en aluminio (parcialmente reciclado y totalmente reciclable), lo que garantiza un impacto medioambiental reducido.
La durabilidad es otro elemento clave del diseño de Emi. El producto está diseñado para perdurar en el tiempo, evitando el desperdicio y la rápida obsolescencia. Cada unidad óptica se puede reemplazar individualmente para facilitar el mantenimiento, mientras que la ausencia de pegamentos y soldaduras simplifica el desmontaje y la eliminación adecuada de las piezas individuales al final de la vida útil del producto.
Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje para conocer toda la información relevante que pueda no estar recogida en este catálogo.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

NEW

EMI

DESIGNED BY ERWAN BOUROULLEC

EMI
TABLE



LIGHT SOURCE
UP
LED ARRAY
28W
3087 lm
2700K/CRI 90

DOWN
POWER LED
13W
1087 lm
2700K/CRI 90

EMI
FLOOR



LIGHT SOURCE
UP
LED ARRAY
38,5W
3714 lm
2700K/CRI 90

DOWN
POWER LED
13W
1087 lm
2700K/CRI 90

NEW

Emi Table

OW Off White | OW.XX All Off White | RY Deep Red | GY Deep Green | ZY Deep Blue







Emi Floor

OW Off White | OW.XX All Off White | RY Deep Red | GY Deep Green | ZY Deep Blue









NEW

Emi Table

Up: LED Array - 28W - 3087 lm - 2700K/CRI 90
Down: Power LED - 13W - 1087 lm - 2700K/CRI 90








Anti-glare appliance for installation on tables and coffee tables. Built-in 100-240 V power supply, with cable and plug. Spare parts for the optical module (lens) are available, please see the accessories. Independent control of the *Up&Down* lighting through *Touch Dimming* capacitive sensors in the top part of the central rod.
The technological heart of Emi combines with an exquisitely crafted base made of cast iron. Imperfections present on the surface of the base are the result of a manual production process that makes each product unique.

Luminaria de bajo deslumbramiento para instalación de sobremesa, mesas bajas o auxiliares. Fuente de alimentación 100-240V integrada, con cable y enchufe. Recambios del módulo óptico (lentes) disponibles, consultar accesorios. Control independiente de la iluminación *Up&Down* mediante sensores capacitivos *Touch Dimming* ubicados en la parte superior del tallo central.
El corazón tecnológico de Emi se combina con una base exquisitamente elaborada en hierro fundido. Las imperfecciones presentes en la superficie de la base son el resultado de un proceso de producción manual que hace que cada producto sea único.

2700K
Touch Dimming
- 05.4380.OW
- 05.4380.OW.78
- 05.4380.RY
- 05.4380.GY
- 05.4380.ZY



Luminous flux luminaire
2959 lm


Beam Angle: 32°32°


h(m)	E(lx)	D(m)
1	7339	0.56
2	1835	1.13
3	815	1.69
4	459	2.26
5	294	2.82

Emi Floor

Up: LED Array - 38,5W - 3714 lm - 2700K/CRI 90
Down: Power LED - 13W - 1087 lm - 2700K/CRI 90








Anti-glare appliance for installation on the floor. Built-in 100-240 V power supply, with cable and plug. Spare parts for the optical module (lens) are available, please see the accessories. Independent control of the *Up&Down* lighting through *Touch Dimming* capacitive sensors in the top part of the central rod.
The technological heart of Emi combines with an exquisitely crafted base made of cast iron. Imperfections present on the surface of the base are the result of a manual production process that makes each product unique.

Luminaria de bajo deslumbramiento para instalación en suelo. Fuente de alimentación 100-240V integrada, con cable y enchufe. Recambios del módulo óptico (lentes) disponibles, consultar accesorios. Control independiente de la iluminación *Up&Down* mediante sensores capacitivos *Touch Dimming* ubicados en la parte superior del tallo central.
El corazón tecnológico de Emi se combina con una base exquisitamente elaborada en hierro fundido. Las imperfecciones presentes en la superficie de la base son el resultado de un proceso de producción manual que hace que cada producto sea único.

2700K
Touch Dimming
- 05.4385.OW
- 05.4385.OW.78
- 05.4385.RY
- 05.4385.GY
- 05.4385.ZY




Luminous flux luminaire
3377 lm

Beam Angle: 32°31°

h(m)	E(lx)	D(m)
1	8786	0.56
2	2196	1.12
3	976	1.68
4	549	2.24
5	351	2.80

Emi Table & Floor



Emi Table & Floor

Lenses

Lentes



3x Opic Flood
08.0956.14
08.0956.40

OBLIQUE

DESIGNED BY VINCENT VAN DUYSEN



LIGHT SOURCE
TOP LED
8W
750 lm
2700K/CRI 90
800 lm
3000K/CRI 90
850 lm
4000K/CRI 90

DY Matt White
DY Blanco Mate



AH Gloss Grey
AH Gris Brillo



DX Matt Rust
DX Óxido Mate



DW Matt Brown
DW Marrón Mate



DR Matt Anthracite
DR Antracita Mate



DV Gloss Salvia
DV Salvia Brillo



Description
Table lamp with direct light and support. Body in die-cast aluminium. Head in die-cast aluminium with integrated full cut-off asymmetric lens in injection moulded methacrylate. LED source completely hidden from view for the best visual comfort without diaphragms or anti-glare accessories that would limit the performance of the lamp. The special patented optics group exceeds regular lighting standards for application in work and study environments, producing lighting values on the work surface greater than 1000 lux with high glare protection and minimum flickering.
All lamp base versions are equipped with a USB-C connection to recharge compatible devices.
The Qi versions have an external polymer covering on the base that allows for supplementary charging of mobile devices via wireless.
Structure made of an extruded tubular aluminium alloy produced mechanically.
The ON/OFF-dimmer switch is integrated into the base and features a timer.

Power Supply
100-240 V - 50/60 Hz electronic transformer.

Additional Information
IP20 protection grade.
Insulation class III.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Lámpara de mesa con luz directa y soporte. Cuerpo de aluminio fundido. Cabezal de aluminio fundido con lente asimétrica full cut-off integrada en metacrilato estampado por inyección. Fuentes LED totalmente ocultos a la vista para el máximo confort visual sin necesidad de diafragmas ni accesorios antideslumbrantes que limitan las prestaciones del cuerpo de la lámpara. La unidad óptica especial patentada supera los estándares de iluminación habituales para aplicaciones en entornos de trabajo y estudio, proporcionando unos valores de iluminación de la superficie de trabajo superiores a 1000 lux con una alta protección contra el deslumbramiento y una reducción al mínimo del parpadeo.
La base de la lámpara está equipada en todas las versiones con una toma USB-C para recargar dispositivos compatibles.
Las versiones Qi presentan una cubierta externa polimérica de la base que permite la recarga adicional de dispositivos móviles de forma inalámbrica. Estructura realizada con un tubo de aleación de aluminio extruido trabajado mecánicamente.
El interruptor regulador (dimmer) y ON/OFF está integrado en la base y dispone de temporizador.

Unidades de Alimentación
Trasformador electrónico 100-240V - 50/60 Hz.

Información Adicional
Índice de protección IP20.
Clase de aislamiento III.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Oblique

Top LED 8W - 750 lm - 2700K/CRI 90 / 8W - 800 lm - 3000K/CRI 90 / 8W - 850 lm - 4000K/CRI 90








Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices.
Driver input: 24 V

Lámpara de mesa profesional con óptica asimétrica patentada. Se incluye una fuente de alimentación externa equipada con un cable de 1500 mm. Toma USB-C integrada en la base de la luminaria diseñada para cargar dispositivos compatibles.
Driver input: 24 V

2700K

- 09.8300.DY
- 09.8300.AH
- 09.8300.DX
- 09.8300.DW
- 09.8300.DR
- 09.8300.DV




Luminous flux luminaire
479 lm

Beam Angle:	35°
h(m)	E(lx) D(m)
1	229 2.18
2	57 4.36
3	25 6.54
4	14 8.72
5	9 10.90

3000K

- 09.8301.DY
- 09.8301.AH
- 09.8301.DX
- 09.8301.DW
- 09.8301.DR
- 09.8301.DV




Luminous flux luminaire
482 lm

Beam Angle:	35°
h(m)	E(lx) D(m)
1	231 2.18
2	58 4.36
3	26 6.54
4	14 8.72
5	9 10.90

4000K

- 09.8302.DY
- 09.8302.AH
- 09.8302.DX
- 09.8302.DW
- 09.8302.DR
- 09.8302.DV




Luminous flux luminaire
525 lm


Beam Angle:	35°
h(m)	E(lx) D(m)
1	252 2.18
2	63 4.36
3	28 6.54
4	16 8.72
5	10 10.90

Oblique Qi

Top LED 8W - 750 lm - 2700K/CRI 90 / 8W - 800 lm - 3000K/CRI 90 / 8W - 850 lm - 4000K/CRI 90








Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Base with Qi compatible wireless recharging system for mobile devices and wireless recharging cases for compatible devices.
Driver input: 12 V

Lámpara de mesa profesional con óptica asimétrica patentada. Se incluye una fuente de alimentación externa equipada con un cable de 1500 mm. Toma USB-C integrada en la base de la luminaria diseñada para cargar dispositivos compatibles. Base con sistema de carga inalámbrica compatible con Qi preparada para dispositivos móviles y cargadores inalámbricos para dispositivos compatibles.
Driver input: 12 V

2700K

- 09.8310.DY
- 09.8310.AH
- 09.8310.DX
- 09.8310.DW
- 09.8310.DR
- 09.8310.DV




Luminous flux luminaire
479 lm

Beam Angle:	35°
h(m)	E(lx) D(m)
1	229 2.18
2	57 4.36
3	25 6.54
4	14 8.72
5	9 10.90

3000K

- 09.8311.DY
- 09.8311.AH
- 09.8311.DX
- 09.8311.DW
- 09.8311.DR
- 09.8311.DV




Luminous flux luminaire
482 lm

Beam Angle:	35°
h(m)	E(lx) D(m)
1	231 2.18
2	58 4.36
3	26 6.54
4	14 8.72
5	9 10.90

4000K

- 09.8312.DY
- 09.8312.AH
- 09.8312.DX
- 09.8312.DW
- 09.8312.DR
- 09.8312.DV



Luminous flux luminaire
525 lm

Beam Angle:	35°
h(m)	E(lx) D(m)
1	252 2.18
2	63 4.36
3	28 6.54
4	16 8.72
5	10 10.90

OBLIQUE FLOOR

DESIGNED BY VINCENT VAN DUYSEN



LIGHT SOURCE
TOP LED
8W
750 lm
2700K/CRI 90
800 lm
3000K/CRI 90
850 lm
4000K/CRI 90

DY Matte White
DY Blanco Mate

AH Gloss Grey
AH Gris Brillo

DX Matte Rust
DX Óxido Mate

DW Matte Brown
DW Marrón Mate

DR Matte Anthracite
DR Antracita Mate

DV Gloss Salvia
DV Salvia Brillo



Description
Floor lamp with asymmetrical direct lighting and floor stand. Haptic interaction for switching and dimming. Cast aluminum body. Cast aluminum head with integrated full cut-off asymmetric lens in injection molded methacrylate. Structure made of a mechanically worked extruded aluminum alloy tube. Completely invisible LED sources for maximum visual comfort without the need for diaphragms or anti-glare accessories that limit the performance of the luminaire. The patented special optical unit exceeds the usual lighting standards for applications in residential, work and study environments with high glare protection and outstanding light quality.

Power Supply
100-240 V - 50/60 Hz electronic transformer.

Additional Information
IP20 protection grade.
Insulation class III.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Lámpara de pie con iluminación directa asimétrica y soporte de suelo. Interacción háptica para encendido y regulación. Cuerpo de aluminio fundido. Cabezal de aluminio fundido con lente asimétrica full cut-off integrada en metacrilato estampado por inyección. Estructura realizada con un tubo de aleación de aluminio extruido trabajado mecánicamente. Fuentes LED totalmente ocultas a la vista para el máximo confort visual sin necesidad de diafragmas ni accesorios antideslumbrantes que limitan las prestaciones de la luminaria. La unidad óptica especial patentada supera los estándares de iluminación habituales para aplicaciones en entornos residenciales, de trabajo y estudio, con una alta protección contra el deslumbramiento y una calidad lumínica extraordinaria.

Unidades de Alimentación
Trasformador electrónico 100-240V - 50/60 Hz.

Información Adicional
Índice de protección IP20.
Clase de aislamiento III.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Oblique Floor

Top LED 8W - 24V - 750 lm - 2700K/CRI 90 / 8W - 24V - 800 lm - 3000K/CRI 90 / 8W - 24V - 850 lm - 4000K/CRI 90








Floor lamp that, thanks to its innovative patented lens, offers asymmetrical light distribution and excellent visual comfort. Its shape, height and dimensions are consistent with the functionality of the product, which provides excellent reading or companion lighting while keeping the light source invisible to the user.
Driver input: 24 V

Lámpara de pie que, gracias a su innovadora lente patentada, ofrece una distribución lumínica asimétrica a la par que un confort visual excelente. Su forma, altura y dimensiones están en concordancia con la funcionalidad del producto, que entrega una excelente iluminación de lectura o acompañamiento al tiempo que mantiene la fuente de luz oculta al acceso visual del usuario.
Driver input: 24 V

2700K

- 09.8220.DY
- 09.8220.AH
- 09.8220.DX
- 09.8220.DW
- 09.8220.DR
- 09.8220.DV




Luminous flux luminaire
479 lm

Beam Angle:	35°	
h(m)	E(lx)	D(m)
1	229	2.18
2	57	4.36
3	25	6.54
4	14	8.72
5	9	10.90

3000K

- 09.8221.DY
- 09.8221.AH
- 09.8221.DX
- 09.8221.DW
- 09.8221.DR
- 09.8221.DV




Luminous flux luminaire
482 lm

Beam Angle:	35°	
h(m)	E(lx)	D(m)
1	231	2.18
2	58	4.36
3	26	6.54
4	14	8.72
5	9	10.90

4000K

- 09.8222.DY
- 09.8222.AH
- 09.8222.DX
- 09.8222.DW
- 09.8222.DR
- 09.8222.DV




Luminous flux luminaire
525 lm


Beam Angle:	35°	
h(m)	E(lx)	D(m)
1	252	2.18
2	63	4.36
3	28	6.54
4	16	8.72
5	10	10.90

Oblique Floor USB-C

Top LED 8W - 24V - 750 lm - 2700K/CRI 90 / 8W - 24V - 800 lm - 3000K/CRI 90 / 8W - 24V - 850 lm - 4000K/CRI 90








Floor lamp that, thanks to its innovative patented lens, offers asymmetrical light distribution and excellent visual comfort. Its shape, height and dimensions are consistent with the functionality of the product, which provides excellent reading or companion lighting while keeping the light source invisible to the user.
Model with USB-C mobile charging in its base.
Driver input: 24 V

Lámpara de pie que, gracias a su innovadora lente patentada, ofrece una distribución lumínica asimétrica a la par que un confort visual excelente. Su forma, altura y dimensiones están en concordancia con la funcionalidad del producto, que entrega una excelente iluminación de lectura o acompañamiento al tiempo que mantiene la fuente de luz oculta al acceso visual del usuario.
Modelo con carga para móviles USB-C en su base.
Driver input: 24 V

2700K

- 09.8230.DY
- 09.8230.AH
- 09.8230.DX
- 09.8230.DW
- 09.8230.DR
- 09.8230.DV




Luminous flux luminaire
479 lm

Beam Angle:	35°	
h(m)	E(lx)	D(m)
1	229	2.18
2	57	4.36
3	25	6.54
4	14	8.72
5	9	10.90

3000K

- 09.8231.DY
- 09.8231.AH
- 09.8231.DX
- 09.8231.DW
- 09.8231.DR
- 09.8231.DV




Luminous flux luminaire
482 lm

Beam Angle:	35°	
h(m)	E(lx)	D(m)
1	231	2.18
2	58	4.36
3	26	6.54
4	14	8.72
5	9	10.90

4000K

- 09.8232.DY
- 09.8232.AH
- 09.8232.DX
- 09.8232.DW
- 09.8232.DR
- 09.8232.DV



Luminous flux luminaire
525 lm

Beam Angle:	35°	
h(m)	E(lx)	D(m)
1	252	2.18
2	63	4.36
3	28	6.54
4	16	8.72
5	10	10.90

NEW

WORKMATES

DESIGNED BY FLOS ARCHITECTURAL

FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play



NEW

Description
Workmates is Flos' luminaire ecosystem for new contemporary and multidisciplinary work spaces. From traditional offices through to *home offices*, from private offices to collaborative work spaces. With its ultraslim profile of only 15 mm, it defines a collection of products that have been designed to provide a versatile response to any lighting need or installation requirement. A lighting concept that places personal well-being at the very core of its technical development and adds careful attention to the aesthetics and details that emanate from the differential identity of the Flos design.
Workmates comes in 4 installation options (ceiling surface, suspension, floor and track), in order to adapt to the installation requirements of any space. All of these come in 3 finishes: *All White, White* and *Black*. In addition, an attractive *Anodized Silver* finish is available in all except the floor option.

Optical System
All of the luminaires in the Workmates ecosystem are offered with LED *High Efficiency* and *Full Spectrum* light sources. The former provides excellent performance in terms of Lm/W, while the *Full Spectrum* option provides optimal colour rendering with a quality that is unbeatably close to that of natural light across the entire spectrum.
The ceiling surface, track and suspension models offer two light distribution options in their *Down* emission: *Wide Flood* and *Oval*. *Wide Flood* distribution achieves perfect uniformity and intensity over the entire work surface (the top of the table or desk). The *Oval* option shapes the light to provide a longitudinal distribution which is suited to applications with long tables or spaces with an elongated layout, such as corridors, transit areas, etc.
Due to their displaced position with respect to the effective lighting plane, the floor-mounted models are designed with asymmetric light delivery in their *Down* emission.

In addition, the suspension and floor mounted versions have an *Up* emission with an *Extra Wide Flood* aperture to generate indirect diffuse light. This reduces users' visual fatigue as well as the jump in light levels between the work plane of the luminaire and the surrounding environment. *Up* emission is also available in *Tunable White* variable colour temperature, which allows the temperature of the indirect light to be adjusted to the circadian rhythm and, depending on the time of day, the generation of an HCL (*Human Centric Lighting*) lighting scheme.
Together with the *'extreme cut-off'* screen, in a glossy technical finish, all Worksmate lenses are designed by Flos to reduce glare and channel the gross flow of the LED optimally in order to achieve the best *Light Output Ratio* (L.O.R.).

Control Systems
Workmates is available with the following setting protocols *On/Off*, *On Board Dimming*, *1-10V, Dali* and *Casambi* (*see the protocols available for each model). The floor versions are also sold with a *Touch Dimming* controller through the built-in button panel.
The floor and pendant models also come in *Smart* versions equipped with motion detection sensors and brightness thresholds.

Additional Information
Workmates complies with the more restrictive requirements of the *EN 12464-1:2012* standard for workspace lighting. Therefore, they offer a UGR of less than 19 and maximum intensity value at an angle of 65° of less than 3000 cd/m^2.
The models with *High Efficiency* LEDs let you choose LEDs with a better 'binning' so you can have an even higher lm/W ratio (contact us for special orders).

Compatibility with the Track models:
- Workmates Track (*Small* & *Large*):
  · *On/Off* and *Casambi* settings compatible with Global, Ivela and Eutrac tracks.
  · *Dali 2* settings compatible with Unipro, Global and Stucchi tracks.

- Workmates In-Track (*Small* & *Large*):
  · *On/Off* settings compatible with Global, Stucchi and Eutrac tracks.
  · *Dali 2* settings compatible with Global and Stucchi tracks.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
Luminaire conforms to European Technical Standard EN60598-1 and secondary parts.

Descripción
Workmates es el ecosistema de luminarias de Flos para los nuevos espacios de trabajo contemporáneos y multidisciplinares. Desde oficinas clásicas hasta *home-office*, de despachos privados a áreas de trabajo colaborativo. Con su delgadísimo perfil de solo 15 mm, se define una colección de productos diseñados para responder con versatilidad a cualquier necesidad lumínica o requisito de instalación. Un concepto de iluminación que sitúa el bienestar de la persona en el centro de su desarrollo técnico y añade un esmerado cuidado de la estética y los detalles que emana de la identidad diferencial del diseño de Flos.
Workmates se deriva en 4 opciones de implementación (superficie de techo, suspensión, suelo y carril), para adaptarse a las necesidades de instalación de todos los espacios. En todas ellas se ofrecen 3 acabados: *All White, White* y *Black*. Además, en todas salvo en la opción de suelo, se añade la atractiva terminación *Anodized Silver*.

Sistema óptico
Todas las luminarias del ecosistema Workmates se ofrecen con fuentes de luz LED *High Efficiency* y *Full Spectrum*. Con la primera de ellas se obtiene un rendimiento excelente en términos de Lm/W, mientras que la opción *Full Spectrum* otorga una reproducción cromática óptima y de una calidad inmejorablemente cercana a la luz natural en todo su espectro.
Los modelos de superficie de techo, de carril y de suspensión ofrecen dos distribuciones lumínicas en su emisión *Down: Wide Flood* y *Oval*. La distribución *Wide Flood* consigue una uniformidad e intensidad perfecta en toda la superficie de trabajo (plano de la mesa o escritorio). La opción *Oval* modela la luz para entregar una distribución longitudinal adecuada para aplicaciones de mesas corridas o espacios de planta alargada como pasillos, zonas de tránsito, etc.
Los modelos de suelo, por su posición desplazada respecto al plano de iluminación efectivo, han sido diseñados con una entrega de la luz asimétrica en su emisión *Down*.

Además, las versiones de suspensión y de suelo disponen de emisión *Up* con apertura *Extra Wide Flood* para generar iluminación difusa indirecta. Se reduce así la fatiga visual de los usuarios y se atenúa el salto de nivel de luminosidad entre el plano de trabajo de la luminaria y el entorno. La emisión *Up* también está disponible en temperatura de color variable *Tunable White* que permite acomodar la temperatura de la luz indirecta al ritmo circadiano y, según la hora del día, generar un esquema de iluminación HCL (*Human Centric Lighting*).
Todas las lentes de Workmates han sido diseñadas por Flos para, junto a la pantalla *'extreme cut-off'* -en acabado técnico brillante-, reducir el deslumbramiento y encauzar el caudal bruto del LED de manera óptima para lograr el mejor *Light Output Ratio* (L.O.R.).

Sistemas de control
Workmates se ofrece con protocolos de regulación *On/Off*, *On Board Dimming*, *1-10V, Dali* y *Casambi* (*consulte los protocolos disponibles en cada modelo). Además, las versiones de suelo se comercializan también con control *Touch Dimming* -mediante botonera integrada-.
Los modelos de suelo y suspensión cuentan también con versiones *Smart* dotadas de sensores de detección de presencia y luminosidad.

Información Adicional
Workmates cumple con los requisitos más restrictivos de la normativa para iluminación de espacios de trabajo *EN 12464-1:2012*. Así, ofrece un UGR menor de 19 y un valor de intensidad máxima en un ángulo de 65° menor de 3000 cd/m^2.
Los modelos con LED *High Efficiency* ofrecen opcionalmente LEDs de 'binning' superior con los que obtener todavía mayor ratio de Lm/W (para realizar un pedido especial, consultar).

Compatibilidad de los modelos track:
- Workmates Track (*Small* & *Large*):
  · Regulación *On/Off* y *Casambi* compatible con carriles Global, Ivela y Eutrac.
  · Regulación *Dali 2* compatible con carriles Unipro, Global y Stucchi.

- Workmates In-Track (*Small* & *Large*):
  · Regulación *On/Off* compatible con carriles Global, Stucchi y Eutrac.
  · Regulación *Dali 2* compatible con carriles Global y Stucchi.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

NEW

WORKMATES

DESIGNED BY FLOS ARCHITECTURAL

WORKMATES SURFACE SMALL



LIGHT SOURCE
TOP LED
HIGH EFFICIENCY
14W
CRI 90
1817 lm / 3000K
1831 lm / 3500K
1858 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM
14W
CRI 98
1346 lm / 3000K
1357 lm / 3500K
1369 lm / 4000K

WORKMATES SURFACE LARGE



LIGHT SOURCE
TOP LED
HIGH EFFICIENCY
28W
CRI 90
3634 lm / 3000K
3662 lm / 3500K
3717 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM
28W
CRI 98
2691 lm / 3000K
2714 lm / 3500K
2737 lm / 4000K

WORKMATES SUSPENSION



WORKMATES SUSPENSION DOWN

LIGHT SOURCE
TOP LED
HIGH EFFICIENCY
Up to 28W
DOWN/CRI 90
4061 lm / 3000K
4090 lm / 3500K
4157 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM
Up to 28W
DOWN/CRI 98
2976 lm / 3000K
3005 lm / 3500K
3034 lm / 4000K

WORKMATES SUSPENSION UP&DOWN

LIGHT SOURCE
TOP LED
HIGH EFFICIENCY
Up to 58,5W

MAJORITY UP (70/30)
UP + DOWN/CRI 90
4316 + 1851 lm / 3000K
4413 + 1892 lm / 3500K
4531 + 1942 lm / 4000K

MAJORITY DOWN (40/60)
UP + DOWN/CRI 90
2588 + 3913 lm / 3000K
2621 + 3942 lm / 3500K
2733 + 4100 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM
Up to 58,5W

MAJORITY UP (70/30)
UP + DOWN/CRI 98
3809 + 1633 lm / 3000K
3911 + 1671 lm / 3500K
4022 + 1725 lm / 4000K

MAJORITY DOWN (40/60)
UP + DOWN/CRI 98
2122 + 3185 lm / 3000K
2238 + 3358 lm / 3500K
2081 + 3122 lm / 4000K

WORKMATES SUSPENSION UP&DOWN SMART

LIGHT SOURCE
TOP LED
HIGH EFFICIENCY

32,5W
UP/CRI 90
4281 lm / 3000K
4339 lm / 3500K
4397 lm / 4000K

26W
DOWN/CRI 90
4061 lm / 3000K
4090 lm / 3500K
4157 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM

32,5W
UP/CRI 98
4281 lm / 3000K
4339 lm / 3500K
4397 lm / 4000K

26W
DOWN/CRI 98
2976 lm / 3000K
3005 lm / 3500K
3034 lm / 4000K

WORKMATES SUSPENSION UP&DOWN TUNABLE WHITE / TUNABLE WHITE SMART

LIGHT SOURCE
TOP LED
HIGH EFFICIENCY

Up to 23W
UP/CRI 90
3619 lm / 2700-5700K

26W
DOWN/CRI 90
4061 lm / 3000K
4090 lm / 3500K
4157 lm / 4000K

LIGHT SOURCE
TOP LED
FULL SPECTRUM

Up to 23W
UP/CRI 90
3619 lm / 2700-5700K

26W
DOWN/CRI 98
2976 lm / 3000K
3005 lm / 3500K
3034 lm / 4000K

NEW

WORKMATES TRACK SMALL



LIGHT SOURCE	LIGHT SOURCE
TOP LED	TOP LED
HIGH EFFICIENCY	FULL SPECTRUM
Up to 15,5W	Up to 15,5W
CRI 90	CRI 98
1817 lm / 3000K	1346 lm / 3000K
1831 lm / 3500K	1357 lm / 3500K
1858 lm / 4000K	1369 lm / 4000K

WORKMATES TRACK LARGE



LIGHT SOURCE	LIGHT SOURCE
TOP LED	TOP LED
HIGH EFFICIENCY	FULL SPECTRUM
Up to 22W	Up to 22W
CRI 90	CRI 98
2726 lm / 3000K	2018 lm / 3000K
2758 lm / 3500K	2036 lm / 3500K
2786 lm / 4000K	2053 lm / 4000K

WORKMATES IN-TRACK SMALL



LIGHT SOURCE	LIGHT SOURCE
TOP LED	TOP LED
HIGH EFFICIENCY	FULL SPECTRUM
Up to 15,5W	Up to 15,5W
CRI 90	CRI 98
1817 lm / 3000K	1346 lm / 3000K
1831 lm / 3500K	1357 lm / 3500K
1858 lm / 4000K	1369 lm / 4000K

WORKMATES IN-TRACK LARGE



LIGHT SOURCE	LIGHT SOURCE
TOP LED	TOP LED
HIGH EFFICIENCY	FULL SPECTRUM
Up to 22W	Up to 22W
CRI 90	CRI 98
2726 lm / 3000K	2018 lm / 3000K
2758 lm / 3500K	2036 lm / 3500K
2786 lm / 4000K	2053 lm / 4000K

THE RUNNING MAGNET

WORKMATES SMALL



WORKMATES LARGE



* Refer to The Running Magnet chapter / Ver capítulo The Running Magnet

NEW

WORKMATES

DESIGNED BY FLOS ARCHITECTURAL

WORKMATES FLOOR SINGLE



WORKMATES FLOOR SINGLE / SINGLE SMART

LIGHT SOURCE	**LIGHT SOURCE**
TOP LED	TOP LED
UP HIGH EFFICIENCY	UP HIGH EFFICIENCY
DOWN HIGH EFFICIENCY	DOWN FULL SPECTRUM
65,4W	65,4W
UP/CRI 90	UP/CRI 90
DOWN/CRI 90	DOWN/CRI 98
11359 lm / 3000K	10161 lm / 3000K
11474 lm / 3500K	10264 lm / 3500K
11957 lm / 4000K	10718 lm / 4000K

WORKMATES FLOOR SINGLE TUNABLE WHITE / TUNABLE WHITE SMART

LIGHT SOURCE	**LIGHT SOURCE**
TOP LED	TOP LED
UP HIGH EFFICIENCY	UP HIGH EFFICIENCY
DOWN HIGH EFFICIENCY	DOWN FULL SPECTRUM
57,7W	57,7W
UP/2700K-5700K/CRI90	UP/2700K-5700K/CRI90
DOWN/CRI 90	DOWN/CRI 98
9127 lm / 3000K	7929 lm / 3000K
9219 lm / 3500K	8008 lm / 3500K
9594 lm / 4000K	8355 lm / 4000K

WORKMATES FLOOR DOUBLE



WORKMATES FLOOR DOUBLE / DOUBLE SMART

LIGHT SOURCE	**LIGHT SOURCE**
TOP LED	TOP LED
UP HIGH EFFICIENCY	UP HIGH EFFICIENCY
DOWN HIGH EFFICIENCY	DOWN FULL SPECTRUM
112W	112W
UP/CRI 90	UP/CRI 90
DOWN/CRI 90	DOWN/CRI 98
22718 lm / 3000K	20322 lm / 3000K
22948 lm / 3500K	20528 lm / 3500K
23914 lm / 4000K	21436 lm / 4000K

WORKMATES FLOOR DOUBLE TUNABLE WHITE / TUNABLE WHITE SMART

LIGHT SOURCE	**LIGHT SOURCE**
TOP LED	TOP LED
UP HIGH EFFICIENCY	UP HIGH EFFICIENCY
DOWN HIGH EFFICIENCY	DOWN FULL SPECTRUM
96W	96W
UP/2700K-5700K/CRI90	UP/2700K-5700K/CRI90
DOWN/CRI 90	DOWN/CRI 98
18254 lm / 3000K	15858 lm / 3000K
18438 lm / 3500K	16016 lm / 3500K
19188 lm / 4000K	16710 lm / 4000K

NEW

Workmates suspension

All White | White | Black | Anodized Silver



Workmates Surface

All White | White | Black | Anodized Silver



Workmates Track

All White | White | Black | Anodized Silver



Workmates In-Track

All White | White | Black | Anodized Silver



Workmates Floor

All White | White | Black




NEW

HOW TO ORDER

1 SELECT MOUNTING / MODEL

Ceiling Surface



Small Large

Three Phase Track



Small Large

Three Phase In-Track




Small Large

The Running Magnet



Small Large

Suspension



Down / Up & Down

Floor



Single Double

2 SELECT LED SOURCE & OPTICS (DOWN LIGHT)

High-efficiency LED



3000 K / 3500 K / 4000 K

Optics

Ceiling Surface

WIDE FLOOD OVAL

All Tracks / Suspension

WIDE FLOOD OVAL HIGH COMFORT

Floor

ASYMM.

Full Spectrum LED



3000 K / 3500 K / 4000 K

Optics

Ceiling Surface

WIDE FLOOD OVAL

All Tracks / Suspension


WIDE FLOOD OVAL HIGH COMFORT

Floor

ASYMM.


3 SELECT SPECIAL FEATURES

Ceiling Surface / All Tracks




STANDARD

Suspension Down




STANDARD

Suspension Up & Down




STANDARD TUNABLE WHITE




SMART TUNABLE WHITE SMART

Floor



STANDARD TUNABLE WHITE



SMART TUNABLE WHITE SMART

HOW TO ORDER

NEW

4 SELECT DIM CONTROL

Ceiling Surface / Three Phase Track

NO DIM DALI CASAMBI

In-Track

NO DIM DALI

The Running Magnet

NO DIM DALI 1-10V CASAMBI

Suspension Down

NO DIM / DALI CASAMBI

Suspension Up & Down

STANDARD

NO DIM / DALI CASAMBI

TUNABLE WHITE

DALI CASAMBI

SMART & TUNABLE WHITE SMART

CASAMBI

Floor

STANDARD & TUNABLE WHITE

TOUCH DIM CASAMBI

SMART & TUNABLE WHITE SMART

CASAMBI

5 SELECT POWER SUPPLY & BASE

Ceiling Surface / Tracks

POWER SUPPLY INCLUDED

Suspension



Remote Power Supply Kit



Surface Power Supply Kit



Recessed Power Supply Kit

Floor Single

POWER SUPPLY INCLUDED



Solid Base Plate



Open Base Plate

Floor Double



Power Supply

NOT INCLUDED



Solid Base Plate Open Base Plate

6 FINISHES

Ceiling Surface / All Tracks / Suspension



All White



White




Black



Anodized Silver

Floor



All White



White



Black


NLAS (Natural Light Average Secondment)

All the lights in the Workmates ecosystem are fitted with *High Efficiency* and *Full Spectrum* LED light sources. With the former, you get excellent performance in terms of lm/W, while with the *Full Spectrum* option, you get the perfect NLAS (Natural Light Average Secondment) index.

Natural light sets a very precise path within the visible light spectrum. The "*Full Spectrum*" LED option, available for Workmates, reflects the most accurate behaviour of artificial light compared with the performance of natural light. It therefore helps improve human well-being and respect the natural schemes of circadian lighting.

Todas las luminarias del ecosistema Workmates se ofrecen con fuentes de luz LED *High Efficiency* y *Full Spectrum*. Con la primera de ellas se obtiene un rendimiento excelente en términos de Lm/W. Con la opción *Full Spectrum* se consigue un índice *NLAS (Natural Light Average Secondment)* inmejorable.

Dentro del espectro visible de la radiación luminosa, la luz natural describe un recorrido muy concreto. La opción de LEDs "*Full Spectrum*", presente en Workmates, ofrece el comportamiento más fiel de una luz artificial, comparado con el rendimiento de la luz natural. De este modo, mejora el bienestar humano al respetar los esquemas naturales de iluminación circadiana.




Smart Lighting


With its *Dali* and wireless *Casambi* control systems, Workmates has built-in or external sensors to activate the desired lighting scenarios for each situation. All of it triggered by presence or absence detection, or the desired brightness thresholds.

Con los sistemas de control *Dali* e inalámbrico *Casambi*, Workamtes cuenta con sensores integrados o externos para activar las escenas de iluminación deseadas para cada situación. Todo, a reacción de la detección de presencia, ausencia o de los umbrales de luminosidad deseados.

Daylight Sensor



Presence Sensor




▲ Casambi object




Workmates Surface Small

Top LED High Efficiency 14W - 1817 lm - 3000K/CRI 90 / 1831 lm - 3500K/CRI 90 / 1858 lm - 4000K/CRI 90







Ceiling surface luminaire. High-efficiency light source. Integrated driver. *Casambi* version available for wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de superficie de techo. Fuente de luz de alta eficiencia. Driver integrado. Versión *Casambi* disponible para el control inalámbrico. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K

Non Dimming

- 05.6200.40
- 05.6200.40.78
- 05.6200.14
- 05.6200.AP


Dali 2

- 05.6200.40.DA
- 05.6200.40.YU
- 05.6200.14.DA
- 05.6200.AP.DA

Casambi

- 05.6200.40.CB
- 05.6200.40.C6
- 05.6200.14.CB
- 05.6200.AP.CB

76° WIDE FLOOD



Luminous flux luminaire 1768 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1143	1.55
2	286	3.10
3	127	4.66
4	71	6.21
5	46	7.76

Optic Oval - 3000K

Non Dimming

- 05.6205.40
- 05.6205.40.78
- 05.6205.14
- 05.6205.AP


Dali 2

- 05.6205.40.DA
- 05.6205.40.YU
- 05.6205.14.DA
- 05.6205.AP.DA

Casambi

- 05.6205.40.CB
- 05.6205.40.C6
- 05.6205.14.CB
- 05.6205.AP.CB

72° OVAL



Luminous flux luminaire 1720 lm

Beam Angle:		72°
h(m)	E(lx)	D(m)
1	1099	1.45
2	274	2.89
3	122	4.34
4	68	5.78
5	44	7.23

Optic Wide Flood - 3500K

Non Dimming

- 05.6201.40
- 05.6201.40.78
- 05.6201.14
- 05.6201.AP


Dali 2

- 05.6201.40.DA
- 05.6201.40.YU
- 05.6201.14.DA
- 05.6201.AP.DA

Casambi

- 05.6201.40.CB
- 05.6201.40.C6
- 05.6201.14.CB
- 05.6201.AP.CB

76° WIDE FLOOD



Luminous flux luminaire 1773 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1146	1.55
2	286	3.10
3	127	4.66
4	72	6.21
5	46	7.76

Optic Oval - 3500K

Non Dimming

- 05.6206.40
- 05.6206.40.78
- 05.6206.14
- 05.6206.AP


Dali 2

- 05.6206.40.DA
- 05.6206.40.YU
- 05.6206.14.DA
- 05.6206.AP.DA

Casambi

- 05.6206.40.CB
- 05.6206.40.C6
- 05.6206.14.CB
- 05.6206.AP.CB

72° OVAL



Luminous flux luminaire 1725 lm

Beam Angle:		72°
h(m)	E(lx)	D(m)
1	1099	1.45
2	275	2.89
3	122	4.34
4	69	5.78
5	44	7.23

Optic Wide Flood - 4000K

Non Dimming

- 05.6202.40
- 05.6202.40.78
- 05.6202.14
- 05.6202.AP


Dali 2

- 05.6202.40.DA
- 05.6202.40.YU
- 05.6202.14.DA
- 05.6202.AP.DA

Casambi

- 05.6202.40.CB
- 05.6202.40.C6
- 05.6202.14.CB
- 05.6202.AP.CB

76° WIDE FLOOD



Luminous flux luminaire 1830 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1183	1.55
2	296	3.10
3	131	4.66
4	74	6.21
5	47	7.76

Optic Oval - 4000K

Non Dimming

- 05.6207.40
- 05.6207.40.78
- 05.6207.14
- 05.6207.AP


Dali 2

- 05.6207.40.DA
- 05.6207.40.YU
- 05.6207.14.DA
- 05.6207.AP.DA

Casambi

- 05.6207.40.CB
- 05.6207.40.C6
- 05.6207.14.CB
- 05.6207.AP.CB

72° OVAL



Luminous flux luminaire 1780 lm


Beam Angle:		72°
h(m)	E(lx)	D(m)
1	1134	1.45
2	283	2.89
3	126	4.34
4	71	5.78
5	45	7.23


NEW

Workmates Surface Small

Top LED Full Spectrum 14W - 1346 lm - 3000K/CRI 98 / 1357 lm - 3500K/CRI 98 / 1369 lm - 4000K/CRI 98







Ceiling surface luminaire. High-quality colour rendering *Full Spectrum* light source. Integrated driver. *Casambi* version available for wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de superficie de techo. Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. Driver integrado. Versión *Casambi* disponible para el control inalámbrico. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.


Optic Wide Flood - 3000K

Non Dimming
- 05.6210.40
- 05.6210.40.78
- 05.6210.14
- 05.6210.AP

Dali 2
- 05.6210.40.DA
- 05.6210.40.YU
- 05.6210.14.DA
- 05.6210.AP.DA

Casambi
- 05.6210.40.CB
- 05.6210.40.C6
- 05.6210.14.CB
- 05.6210.AP.CB

76° WIDE FLOOD



Luminous flux luminaire 1231 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	796	1.55
2	199	3.10
3	88	4.66
4	50	6.21
5	32	7.76


Optic Oval - 3000K

Non Dimming
- 05.6215.40
- 05.6215.40.78
- 05.6215.14
- 05.6215.AP

Dali 2
- 05.6215.40.DA
- 05.6215.40.YU
- 05.6215.14.DA
- 05.6215.AP.DA

Casambi
- 05.6215.40.CB
- 05.6215.40.C6
- 05.6215.14.CB
- 05.6215.AP.CB

72° OVAL



Luminous flux luminaire 1192 lm

Beam Angle:		72°
h(m)	E(lx)	D(m)
1	759	1.45
2	190	2.89
3	84	4.34
4	47	5.78
5	30	7.23


Optic Wide Flood - 3500K

Non Dimming
- 05.6211.40
- 05.6211.40.78
- 05.6211.14
- 05.6211.AP

Dali 2
- 05.6211.40.DA
- 05.6211.40.YU
- 05.6211.14.DA
- 05.6211.AP.DA

Casambi
- 05.6211.40.CB
- 05.6211.40.C6
- 05.6211.14.CB
- 05.6211.AP.CB

76° WIDE FLOOD



Luminous flux luminaire 1238 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	800	1.55
2	200	3.10
3	89	4.66
4	50	6.21
5	32	7.76


Optic Oval - 3500K

Non Dimming
- 05.6216.40
- 05.6216.40.78
- 05.6216.14
- 05.6216.AP

Dali 2
- 05.6216.40.DA
- 05.6216.40.YU
- 05.6216.14.DA
- 05.6216.AP.DA

Casambi
- 05.6216.40.CB
- 05.6216.40.C6
- 05.6216.14.CB
- 05.6216.AP.CB

72° OVAL



Luminous flux luminaire 1198 lm

Beam Angle:		72°
h(m)	E(lx)	D(m)
1	763	1.45
2	191	2.89
3	85	4.34
4	48	5.78
5	31	7.23


Optic Wide Flood - 4000K

Non Dimming
- 05.6212.40
- 05.6212.40.78
- 05.6212.14
- 05.6212.AP

Dali 2
- 05.6212.40.DA
- 05.6212.40.YU
- 05.6212.14.DA
- 05.6212.AP.DA

Casambi
- 05.6212.40.CB
- 05.6212.40.C6
- 05.6212.14.CB
- 05.6212.AP.CB

76° WIDE FLOOD



Luminous flux luminaire 1300 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	840	1.55
2	210	3.10
3	93	4.66
4	53	6.21
5	34	7.76


Optic Oval - 4000K

Non Dimming
- 05.6217.40
- 05.6217.40.78
- 05.6217.14
- 05.6217.AP

Dali 2
- 05.6217.40.DA
- 05.6217.40.YU
- 05.6217.14.DA
- 05.6217.AP.DA

Casambi
- 05.6217.40.CB
- 05.6217.40.C6
- 05.6217.14.CB
- 05.6217.AP.CB

72° OVAL




Luminous flux luminaire 1256 lm


Beam Angle:		72°
h(m)	E(lx)	D(m)
1	800	1.45
2	200	2.89
3	89	4.34
4	50	5.78
5	32	7.23

Workmates Surface Large

Top LED High Efficiency 28W - 3634 lm - 3000K/CRI 90 / 3662 lm - 3500K/CRI 90 / 3717 lm - 4000K/CRI 90







Ceiling surface luminaire. High-efficiency light source. Integrated driver. *Casambi* version available for wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de superficie de techo. Fuente de luz de alta eficiencia. Driver integrado. Versión *Casambi* disponible para el control inalámbrico. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K

Non Dimming

- 05.6220.40
- 05.6220.40.78
- 05.6220.14
- 05.6220.AP


Dali 2

- 05.6220.40.DA
- 05.6220.40.YU
- 05.6220.14.DA
- 05.6220.AP.DA

Casambi

- 05.6220.40.CB
- 05.6220.40.C6
- 05.6220.14.CB
- 05.6220.AP.CB

73° WIDE FLOOD



Luminous flux luminaire 3392 lm

Beam Angle:	73°	
h(m)	E(lx)	D(m)
1	2249	1.49
2	562	2.99
3	250	4.48
4	141	5.97
5	90	7.46

Optic Oval - 3000K

Non Dimming

- 05.6225.40
- 05.6225.40.78
- 05.6225.14
- 05.6225.AP


Dali 2

- 05.6225.40.DA
- 05.6225.40.YU
- 05.6225.14.DA
- 05.6225.AP.DA

Casambi

- 05.6225.40.CB
- 05.6225.40.C6
- 05.6225.14.CB
- 05.6225.AP.CB

71° OVAL



Luminous flux luminaire 3216 lm

Beam Angle:	71°	
h(m)	E(lx)	D(m)
1	2095	1.42
2	524	2.85
3	233	4.27
4	131	5.70
5	84	7.12

Optic Wide Flood - 3500K

Non Dimming

- 05.6221.40
- 05.6221.40.78
- 05.6221.14
- 05.6221.AP


Dali 2

- 05.6221.40.DA
- 05.6221.40.YU
- 05.6221.14.DA
- 05.6221.AP.DA

Casambi

- 05.6221.40.CB
- 05.6221.40.C6
- 05.6221.14.CB
- 05.6221.AP.CB

73° WIDE FLOOD



Luminous flux luminaire 3408 lm

Beam Angle:	73°	
h(m)	E(lx)	D(m)
1	2259	1.49
2	565	2.99
3	251	4.48
4	141	5.97
5	90	7.46

Optic Oval - 3500K

Non Dimming

- 05.6226.40
- 05.6226.40.78
- 05.6226.14
- 05.6226.AP


Dali 2

- 05.6226.40.DA
- 05.6226.40.YU
- 05.6226.14.DA
- 05.6226.AP.DA

Casambi

- 05.6226.40.CB
- 05.6226.40.C6
- 05.6226.14.CB
- 05.6226.AP.CB

71° OVAL



Luminous flux luminaire 3232 lm

Beam Angle:	71°	
h(m)	E(lx)	D(m)
1	2105	1.42
2	526	2.85
3	234	4.27
4	132	5.70
5	84	7.12

Optic Wide Flood - 4000K

Non Dimming

- 05.6222.40
- 05.6222.40.78
- 05.6222.14
- 05.6222.AP


Dali 2

- 05.6222.40.DA
- 05.6222.40.YU
- 05.6222.14.DA
- 05.6222.AP.DA

Casambi

- 05.6222.40.CB
- 05.6222.40.C6
- 05.6222.14.CB
- 05.6222.AP.CB

73° WIDE FLOOD



Luminous flux luminaire 3594 lm

Beam Angle:	73°	
h(m)	E(lx)	D(m)
1	2382	1.49
2	596	2.99
3	265	4.48
4	149	5.97
5	95	7.46

Optic Oval - 4000K

Non Dimming

- 05.6227.40
- 05.6227.40.78
- 05.6227.14
- 05.6227.AP


Dali 2

- 05.6227.40.DA
- 05.6227.40.YU
- 05.6227.14.DA
- 05.6227.AP.DA

Casambi

- 05.6227.40.CB
- 05.6227.40.C6
- 05.6227.14.CB
- 05.6227.AP.CB

71° OVAL



Luminous flux luminaire 3408 lm


Beam Angle:	71°	
h(m)	E(lx)	D(m)
1	2220	1.42
2	555	2.85
3	247	4.27
4	139	5.70
5	89	7.12


NEW

Workmates Surface Large

Top LED Full Spectrum 28W - 2691 lm - 3000K/CRI 98 / 2714 lm - 3500K/CRI 98 / 2737 lm - 4000K/CRI 98







Ceiling surface luminaire. High-quality colour rendering *Full Spectrum* light source. Integrated driver. *Casambi* version available for wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de superficie de techo. Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. Driver integrado. Versión *Casambi* disponible para el control inalámbrico. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.


Optic Wide Flood - 3000K

Non Dimming
- 05.6230.40
- 05.6230.40.78
- 05.6230.14
- 05.6230.AP

Dali 2
- 05.6230.40.DA
- 05.6230.40.YU
- 05.6230.14.DA
- 05.6230.AP.DA

Casambi
- 05.6230.40.CB
- 05.6230.40.C6
- 05.6230.14.CB
- 05.6230.AP.CB

73° WIDE FLOOD



Luminous flux luminaire 2464 lm

Beam Angle:		73°
h(m)	E(lx)	D(m)
1	1607	1.49
2	402	2.97
3	179	4.46
4	100	5.95
5	64	7.43


Optic Oval - 3000K

Non Dimming
- 05.6235.40
- 05.6235.40.78
- 05.6235.14
- 05.6235.AP

Dali 2
- 05.6235.40.DA
- 05.6235.40.YU
- 05.6235.14.DA
- 05.6235.AP.DA

Casambi
- 05.6235.40.CB
- 05.6235.40.C6
- 05.6235.14.CB
- 05.6235.AP.CB

71° OVAL



Luminous flux luminaire 2365 lm

Beam Angle:		71°
h(m)	E(lx)	D(m)
1	1530	1.43
2	383	2.86
3	170	4.28
4	96	5.71
5	61	7.14


Optic Wide Flood - 3500K

Non Dimming
- 05.6231.40
- 05.6231.40.78
- 05.6231.14
- 05.6231.AP

Dali 2
- 05.6231.40.DA
- 05.6231.40.YU
- 05.6231.14.DA
- 05.6231.AP.DA

Casambi
- 05.6231.40.CB
- 05.6231.40.C6
- 05.6231.14.CB
- 05.6231.AP.CB

73° WIDE FLOOD



Luminous flux luminaire 2491 lm

Beam Angle:		73°
h(m)	E(lx)	D(m)
1	1624	1.49
2	406	2.97
3	180	4.46
4	102	5.95
5	65	7.43


Optic Oval - 3500K

Non Dimming
- 05.6236.40
- 05.6236.40.78
- 05.6236.14
- 05.6236.AP

Dali 2
- 05.6236.40.DA
- 05.6236.40.YU
- 05.6236.14.DA
- 05.6236.AP.DA

Casambi
- 05.6236.40.CB
- 05.6236.40.C6
- 05.6236.14.CB
- 05.6236.AP.CB

71° OVAL



Luminous flux luminaire 2392 lm

Beam Angle:		71°
h(m)	E(lx)	D(m)
1	1548	1.43
2	387	2.86
3	172	4.28
4	97	5.71
5	62	7.14


Optic Wide Flood - 4000K

Non Dimming
- 05.6232.40
- 05.6232.40.78
- 05.6232.14
- 05.6232.AP

Dali 2
- 05.6232.40.DA
- 05.6232.40.YU
- 05.6232.14.DA
- 05.6232.AP.DA

Casambi
- 05.6232.40.CB
- 05.6232.40.C6
- 05.6232.14.CB
- 05.6232.AP.CB

73° WIDE FLOOD



Luminous flux luminaire 2701 lm

Beam Angle:		73°
h(m)	E(lx)	D(m)
1	1761	1.49
2	440	2.97
3	196	4.46
4	110	5.95
5	70	7.43


Optic Oval - 4000K

Non Dimming
- 05.6237.40
- 05.6237.40.78
- 05.6237.14
- 05.6237.AP

Dali 2
- 05.6237.40.DA
- 05.6237.40.YU
- 05.6237.14.DA
- 05.6237.AP.DA

Casambi
- 05.6237.40.CB
- 05.6237.40.C6
- 05.6237.14.CB
- 05.6237.AP.CB

71° OVAL




Luminous flux luminaire 2593 lm


Beam Angle:		71°
h(m)	E(lx)	D(m)
1	1678	1.43
2	419	2.86
3	186	4.28
4	105	5.71
5	67	7.14

Workmates Track Small

Top LED High Efficiency
Non Dimming: 15,5W - 1817 lm - 3000K/CRI 90 / 1831 lm - 3500K/CRI 90 / 1858 lm - 4000K/CRI 90
Dali 2 / Casambi: 15W - 1817 lm - 3000K/CRI 90 / 1831 lm - 3500K/CRI 90 / 1858 lm - 4000K/CRI 90







Luminaire for use on a three-phase track, with adapters for No Dim, Dali and *Casambi* (wireless) control. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim, Dali y *Casambi* (inalámbrico). Fuente de luz de alta eficiencia. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.


Optic Wide Flood - 3000K

Non Dimming
- 05.6240.40
- 05.6240.40.78
- 05.6240.14
- 05.6240.AP

Dali 2
- 05.6240.40.DA
- 05.6240.40.YU
- 05.6240.14.DA
- 05.6240.AP.DA

Casambi
- 05.6240.40.CB
- 05.6240.40.C6
- 05.6240.14.CB
- 05.6240.AP.CB





Luminous flux luminaire
1768 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1143	1.55
2	286	3.10
3	127	4.66
4	71	6.21
5	46	7.76


Optic Wide Flood - 4000K

Non Dimming
- 05.6242.40
- 05.6242.40.78
- 05.6242.14
- 05.6242.AP

Dali 2
- 05.6242.40.DA
- 05.6242.40.YU
- 05.6242.14.DA
- 05.6242.AP.DA

Casambi
- 05.6242.40.CB
- 05.6242.40.C6
- 05.6242.14.CB
- 05.6242.AP.CB





Luminous flux luminaire
1830 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1183	1.55
2	296	3.10
3	131	4.66
4	74	6.21
5	47	7.76


Optic Wide Flood - 3500K

Non Dimming
- 05.6241.40
- 05.6241.40.78
- 05.6241.14
- 05.6241.AP

Dali 2
- 05.6241.40.DA
- 05.6241.40.YU
- 05.6241.14.DA
- 05.6241.AP.DA

Casambi
- 05.6241.40.CB
- 05.6241.40.C6
- 05.6241.14.CB
- 05.6241.AP.CB





Luminous flux luminaire
1773 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1146	1.55
2	286	3.10
3	127	4.66
4	72	6.21
5	46	7.76

NEW

Optic Oval - 3000K

Non Dimming

- 05.6245.40
- 05.6245.40.78
- 05.6245.14
- 05.6245.AP


Dali 2

- 05.6245.40.DA
- 05.6245.40.YU
- 05.6245.14.DA
- 05.6245.AP.DA

Casambi

- 05.6245.40.CB
- 05.6245.40.C6
- 05.6245.14.CB
- 05.6245.AP.CB

80°
OVAL



Luminous flux luminaire
1720 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1096	1.67
2	274	3.34
3	122	5.00
4	68	6.67
5	44	8.34

Optic High Comfort - 3000K

Non Dimming

- 05.5740.40
- 05.5740.40.78
- 05.5740.14
- 05.5740.AP


Dali 2

- 05.5740.40.DA
- 05.5740.40.YU
- 05.5740.14.DA
- 05.5740.AP.DA

Casambi

- 05.5740.40.CB
- 05.5740.40.C6
- 05.5740.14.CB
- 05.5740.AP.CB

66°
HIGH
COMFORT



Luminous flux luminaire
1850 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1780	1.31
2	445	2.61
3	198	3.92
4	111	5.23
5	71	6.54

Optic Oval - 3500K

Non Dimming

- 05.6246.40
- 05.6246.40.78
- 05.6246.14
- 05.6246.AP


Dali 2

- 05.6246.40.DA
- 05.6246.40.YU
- 05.6246.14.DA
- 05.6246.AP.DA

Casambi

- 05.6246.40.CB
- 05.6246.40.C6
- 05.6246.14.CB
- 05.6246.AP.CB

80°
OVAL



Luminous flux luminaire
1725 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1099	1.67
2	275	3.34
3	122	5.00
4	69	6.67
5	44	8.34

Optic High Comfort - 3500K

Non Dimming

- 05.5741.40
- 05.5741.40.78
- 05.5741.14
- 05.5741.AP


Dali 2

- 05.5741.40.DA
- 05.5741.40.YU
- 05.5741.14.DA
- 05.5741.AP.DA

Casambi

- 05.5741.40.CB
- 05.5741.40.C6
- 05.5741.14.CB
- 05.5741.AP.CB

66°
HIGH
COMFORT



Luminous flux luminaire
1855 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1785	1.31
2	446	2.61
3	198	3.92
4	112	5.23
5	71	6.54

Optic Oval - 4000K

Non Dimming

- 05.6247.40
- 05.6247.40.78
- 05.6247.14
- 05.6247.AP


Dali 2

- 05.6247.40.DA
- 05.6247.40.YU
- 05.6247.14.DA
- 05.6247.AP.DA

Casambi

- 05.6247.40.CB
- 05.6247.40.C6
- 05.6247.14.CB
- 05.6247.AP.CB

80°
OVAL



Luminous flux luminaire
1780 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1134	1.67
2	283	3.34
3	126	5.00
4	71	6.67
5	45	8.34

Optic High Comfort - 4000K

Non Dimming

- 05.5742.40
- 05.5742.40.78
- 05.5742.14
- 05.5742.AP


Dali 2

- 05.5742.40.DA
- 05.5742.40.YU
- 05.5742.14.DA
- 05.5742.AP.DA

Casambi

- 05.5742.40.CB
- 05.5742.40.C6
- 05.5742.14.CB
- 05.5742.AP.CB

66°
HIGH
COMFORT




Luminous flux luminaire
1887 lm


Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1815	1.31
2	454	2.61
3	202	3.92
4	113	5.23
5	73	6.54

Workmates Track Small

Top LED Full Spectrum
Non Dimming: 15,5W - 1346 lm - 3000K/CRI 98 / 1357 lm - 3500K/CRI 98 / 1369 lm - 4000K/CRI 98
Dali 2 / Casambi: 15W - 1346 lm - 3000K/CRI 98 / 1357 lm - 3500K/CRI 98 / 1369 lm - 4000K/CRI 98







Luminaire for use on a three-phase track, with adapters for No Dim, Dali and *Casambi* (wireless) control. High-quality colour rendering *Full Spectrum* light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim, Dali y *Casambi* (inalámbrico). Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.


Optic Wide Flood - 3000K

Non Dimming
- 05.6250.40
- 05.6250.40.78
- 05.6250.14
- 05.6250.AP

Dali 2
- 05.6250.40.DA
- 05.6250.40.YU
- 05.6250.14.DA
- 05.6250.AP.DA

Casambi
- 05.6250.40.CB
- 05.6250.40.C6
- 05.6250.14.CB
- 05.6250.AP.CB





Luminous flux luminaire
1231 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	796	1.55
2	199	3.10
3	88	4.66
4	50	6.21
5	32	7.76


Optic Wide Flood - 4000K

Non Dimming
- 05.6252.40
- 05.6252.40.78
- 05.6252.14
- 05.6252.AP

Dali 2
- 05.6252.40.DA
- 05.6252.40.YU
- 05.6252.14.DA
- 05.6252.AP.DA

Casambi
- 05.6252.40.CB
- 05.6252.40.C6
- 05.6252.14.CB
- 05.6252.AP.CB





Luminous flux luminaire
1300 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	840	1.55
2	210	3.10
3	93	4.66
4	53	6.21
5	34	7.76


Optic Wide Flood - 3500K

Non Dimming
- 05.6251.40
- 05.6251.40.78
- 05.6251.14
- 05.6251.AP

Dali 2
- 05.6251.40.DA
- 05.6251.40.YU
- 05.6251.14.DA
- 05.6251.AP.DA

Casambi
- 05.6251.40.CB
- 05.6251.40.C6
- 05.6251.14.CB
- 05.6251.AP.CB





Luminous flux luminaire
1238 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	800	1.55
2	200	3.10
3	89	4.66
4	50	6.21
5	32	7.76

NEW

Optic Oval - 3000K

Non Dimming

- 05.6255.40
- 05.6255.40.78
- 05.6255.14
- 05.6255.AP


Dali 2

- 05.6255.40.DA
- 05.6255.40.YU
- 05.6255.14.DA
- 05.6255.AP.DA

Casambi

- 05.6255.40.CB
- 05.6255.40.C6
- 05.6255.14.CB
- 05.6255.AP.CB





Luminous flux luminaire
1192 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	759	1.67
2	190	3.34
3	84	5.00
4	47	6.67
5	30	8.34

Optic High Comfort - 3000K

Non Dimming

- 05.5750.40
- 05.5750.40.78
- 05.5750.14
- 05.5750.AP


Dali 2

- 05.5750.40.DA
- 05.5750.40.YU
- 05.5750.14.DA
- 05.5750.AP.DA

Casambi

- 05.5750.40.CB
- 05.5750.40.C6
- 05.5750.14.CB
- 05.5750.AP.CB





Luminous flux luminaire
1289 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1240	1.31
2	310	2.61
3	138	3.92
4	77	5.23
5	50	6.54

Optic Oval - 3500K

Non Dimming

- 05.6256.40
- 05.6256.40.78
- 05.6256.14
- 05.6256.AP


Dali 2

- 05.6256.40.DA
- 05.6256.40.YU
- 05.6256.14.DA
- 05.6256.AP.DA

Casambi

- 05.6256.40.CB
- 05.6256.40.C6
- 05.6256.14.CB
- 05.6256.AP.CB





Luminous flux luminaire
1198 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	763	1.67
2	191	3.34
3	85	5.00
4	48	6.67
5	31	8.34

Optic High Comfort - 3500K

Non Dimming

- 05.5751.40
- 05.5751.40.78
- 05.5751.14
- 05.5751.AP


Dali 2

- 05.5751.40.DA
- 05.5751.40.YU
- 05.5751.14.DA
- 05.5751.AP.DA

Casambi

- 05.5751.40.CB
- 05.5751.40.C6
- 05.5751.14.CB
- 05.5751.AP.CB





Luminous flux luminaire
1293 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1244	1.31
2	311	2.61
3	138	3.92
4	78	5.23
5	50	6.54

Optic Oval - 4000K

Non Dimming

- 05.6257.40
- 05.6257.40.78
- 05.6257.14
- 05.6257.AP


Dali 2

- 05.6257.40.DA
- 05.6257.40.YU
- 05.6257.14.DA
- 05.6257.AP.DA

Casambi

- 05.6257.40.CB
- 05.6257.40.C6
- 05.6257.14.CB
- 05.6257.AP.CB





Luminous flux luminaire
1259 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	802	1.67
2	200	3.34
3	89	5.00
4	50	6.67
5	32	8.34

Optic High Comfort - 4000K

Non Dimming

- 05.5752.40
- 05.5752.40.78
- 05.5752.14
- 05.5752.AP


Dali 2

- 05.5752.40.DA
- 05.5752.40.YU
- 05.5752.14.DA
- 05.5752.AP.DA

Casambi

- 05.5752.40.CB
- 05.5752.40.C6
- 05.5752.14.CB
- 05.5752.AP.CB






Luminous flux luminaire
1357 lm


Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1306	1.31
2	326	2.61
3	145	3.92
4	82	5.23
5	52	6.54

Workmates Track Large

Top LED High Efficiency
Non Dimming: 21W - 2726 lm - 3000K/CRI 90 / 2758 lm - 3500K/CRI 90 / 2786 lm - 4000K/CRI 90
Dali 2 / Casambi: 22W - 2726 lm - 3000K/CRI 90 / 2758 lm - 3500K/CRI 90 / 2786 lm - 4000K/CRI 90







Luminaire for use on a three-phase track, with adapters for No Dim, Dali and *Casambi* (wireless) control. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.


Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim, Dali y *Casambi* (inalámbrico). Fuente de luz de alta eficiencia. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K

Non Dimming
- 05.6260.40
- 05.6260.40.78
- 05.6260.14
- 05.6260.AP

Dali 2
- 05.6260.40.DA
- 05.6260.40.YU
- 05.6260.14.DA
- 05.6260.AP.DA

Casambi
- 05.6260.40.CB
- 05.6260.40.C6
- 05.6260.14.CB
- 05.6260.AP.CB



Luminous flux luminaire 2371 lm


Beam Angle:		73°
h(m)	E(lx)	D(m)
1	1609	1.48
2	402	2.95
3	179	4.43
4	101	5.91
5	64	7.39

Optic Wide Flood - 4000K

Non Dimming
- 05.6262.40
- 05.6262.40.78
- 05.6262.14
- 05.6262.AP

Dali 2
- 05.6262.40.DA
- 05.6262.40.YU
- 05.6262.14.DA
- 05.6262.AP.DA

Casambi
- 05.6262.40.CB
- 05.6262.40.C6
- 05.6262.14.CB
- 05.6262.AP.CB



Luminous flux luminaire 2450 lm


Beam Angle:		73°
h(m)	E(lx)	D(m)
1	1662	1.48
2	416	2.95
3	185	4.43
4	104	5.91
5	66	7.39

Optic Wide Flood - 3500K

Non Dimming
- 05.6261.40
- 05.6261.40.78
- 05.6261.14
- 05.6261.AP

Dali 2
- 05.6261.40.DA
- 05.6261.40.YU
- 05.6261.14.DA
- 05.6261.AP.DA

Casambi
- 05.6261.40.CB
- 05.6261.40.C6
- 05.6261.14.CB
- 05.6261.AP.CB



Luminous flux luminaire 2378 lm

Beam Angle:		73°
h(m)	E(lx)	D(m)
1	1614	1.48
2	403	2.95
3	179	4.43
4	101	5.91
5	65	7.39

NEW

Optic Oval - 3000K

Non Dimming

- 05.6265.40
- 05.6265.40.78
- 05.6265.14
- 05.6265.AP


Dali 2

- 05.6265.40.DA
- 05.6265.40.YU
- 05.6265.14.DA
- 05.6265.AP.DA

Casambi

- 05.6265.40.CB
- 05.6265.40.C6
- 05.6265.14.CB
- 05.6265.AP.CB

80° OVAL



Luminous flux luminaire
2462 lm

Beam Angle:	80°
h(m)	E(lx) D(m)
1	1577 1.68
2	394 3.36
3	175 5.03
4	99 6.71
5	63 8.39

Optic High Comfort - 3000K

Non Dimming

- 05.5760.40
- 05.5760.40.78
- 05.5760.14
- 05.5760.AP


Dali 2

- 05.5760.40.DA
- 05.5760.40.YU
- 05.5760.14.DA
- 05.5760.AP.DA

Casambi

- 05.5760.40.CB
- 05.5760.40.C6
- 05.5760.14.CB
- 05.5760.AP.CB

67° HIGH COMFORT



Luminous flux luminaire
2711 lm

Beam Angle:	67°
h(m)	E(lx) D(m)
1	2563 1.32
2	641 2.64
3	285 3.96
4	160 5.28
5	103 6.61

Optic Oval - 3500K

Non Dimming

- 05.6266.40
- 05.6266.40.78
- 05.6266.14
- 05.6266.AP


Dali 2

- 05.6266.40.DA
- 05.6266.40.YU
- 05.6266.14.DA
- 05.6266.AP.DA

Casambi

- 05.6266.40.CB
- 05.6266.40.C6
- 05.6266.14.CB
- 05.6266.AP.CB

80° OVAL



Luminous flux luminaire
2469 lm

Beam Angle:	80°
h(m)	E(lx) D(m)
1	1582 1.68
2	395 3.36
3	176 5.03
4	99 6.71
5	63 8.39

Optic High Comfort - 3500K

Non Dimming

- 05.5761.40
- 05.5761.40.78
- 05.5761.14
- 05.5761.AP


Dali 2

- 05.5761.40.DA
- 05.5761.40.YU
- 05.5761.14.DA
- 05.5761.AP.DA

Casambi

- 05.5761.40.CB
- 05.5761.40.C6
- 05.5761.14.CB
- 05.5761.AP.CB

67° HIGH COMFORT



Luminous flux luminaire
2718 lm

Beam Angle:	67°
h(m)	E(lx) D(m)
1	2571 1.32
2	643 2.64
3	286 3.96
4	161 5.28
5	103 6.61

Optic Oval - 4000K

Non Dimming

- 05.6267.40
- 05.6267.40.78
- 05.6267.14
- 05.6267.AP


Dali 2

- 05.6267.40.DA
- 05.6267.40.YU
- 05.6267.14.DA
- 05.6267.AP.DA

Casambi

- 05.6267.40.CB
- 05.6267.40.C6
- 05.6267.14.CB
- 05.6267.AP.CB

80° OVAL



Luminous flux luminaire
2548 lm

Beam Angle:	80°
h(m)	E(lx) D(m)
1	1632 1.68
2	408 3.36
3	181 5.03
4	102 6.71
5	65 8.39

Optic High Comfort - 4000K

Non Dimming

- 05.5762.40
- 05.5762.40.78
- 05.5762.14
- 05.5762.AP


Dali 2

- 05.5762.40.DA
- 05.5762.40.YU
- 05.5762.14.DA
- 05.5762.AP.DA

Casambi

- 05.5762.40.CB
- 05.5762.40.C6
- 05.5762.14.CB
- 05.5762.AP.CB

67° HIGH COMFORT




Luminous flux luminaire
2790 lm


Beam Angle:	67°
h(m)	E(lx) D(m)
1	2639 1.32
2	660 2.64
3	293 3.96
4	165 5.28
5	106 6.61

Workmates Track Large

Top LED Full Spectrum
Non Dimming: 21W - 2018 lm - 3000K/CRI 98 / 2036 lm - 3500K/CRI 98 / 2053 lm - 4000K/CRI 98
Dali 2 / Casambi: 22W - 2018 lm - 3000K/CRI 98 / 2036 lm - 3500K/CRI 98 / 2053 lm - 4000K/CRI 98







Luminaire for use on a three-phase track, with adapters for No Dim, Dali and *Casambi* (wireless) control. High-quality colour rendering *Full Spectrum* light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim, Dali y *Casambi* (inalámbrico). Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.


Optic Wide Flood - 3000K

Non Dimming
- 05.6270.40
- 05.6270.40.78
- 05.6270.14
- 05.6270.AP

Dali 2
- 05.6270.40.DA
- 05.6270.40.YU
- 05.6270.14.DA
- 05.6270.AP.DA

Casambi
- 05.6270.40.CB
- 05.6270.40.C6
- 05.6270.14.CB
- 05.6270.AP.CB





Luminous flux luminaire
1761 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1155	1.55
2	289	3.09
3	128	4.64
4	72	6.18
5	46	7.73


Optic Wide Flood - 4000K

Non Dimming
- 05.6272.40
- 05.6272.40.78
- 05.6272.14
- 05.6272.AP

Dali 2
- 05.6272.40.DA
- 05.6272.40.YU
- 05.6272.14.DA
- 05.6272.AP.DA

Casambi
- 05.6272.40.CB
- 05.6272.40.C6
- 05.6272.14.CB
- 05.6272.AP.CB





Luminous flux luminaire
1860 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1219	1.55
2	305	3.09
3	135	4.64
4	76	6.18
5	49	7.73


Optic Wide Flood - 3500K

Non Dimming
- 05.6271.40
- 05.6271.40.78
- 05.6271.14
- 05.6271.AP

Dali 2
- 05.6271.40.DA
- 05.6271.40.YU
- 05.6271.14.DA
- 05.6271.AP.DA

Casambi
- 05.6271.40.CB
- 05.6271.40.C6
- 05.6271.14.CB
- 05.6271.AP.CB





Luminous flux luminaire
1770 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1160	1.55
2	290	3.09
3	129	4.64
4	73	6.18
5	46	7.73

NEW

Optic Oval - 3000K

Non Dimming

- 05.6275.40
- 05.6275.40.78
- 05.6275.14
- 05.6275.AP


Dali 2

- 05.6275.40.DA
- 05.6275.40.YU
- 05.6275.14.DA
- 05.6275.AP.DA

Casambi

- 05.6275.40.CB
- 05.6275.40.C6
- 05.6275.14.CB
- 05.6275.AP.CB

80° OVAL



Luminous flux luminaire
1744 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1117	1.68
2	279	3.36
3	124	5.03
4	70	6.71
5	45	8.39

Optic High Comfort - 3000K

Non Dimming

- 05.5770.40
- 05.5770.40.78
- 05.5770.14
- 05.5770.AP


Dali 2

- 05.5770.40.DA
- 05.5770.40.YU
- 05.5770.14.DA
- 05.5770.AP.DA

Casambi

- 05.5770.40.CB
- 05.5770.40.C6
- 05.5770.14.CB
- 05.5770.AP.CB

67° HIGH COMFORT



Luminous flux luminaire
1848 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1747	1.32
2	437	2.64
3	194	3.96
4	109	5.28
5	70	6.61

Optic Oval - 3500K

Non Dimming

- 05.6276.40
- 05.6276.40.78
- 05.6276.14
- 05.6276.AP


Dali 2

- 05.6276.40.DA
- 05.6276.40.YU
- 05.6276.14.DA
- 05.6276.AP.DA

Casambi

- 05.6276.40.CB
- 05.6276.40.C6
- 05.6276.14.CB
- 05.6276.AP.CB

80° OVAL



Luminous flux luminaire
1753 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1123	1.68
2	281	3.36
3	125	5.03
4	70	6.71
5	45	8.39

Optic High Comfort - 3500K

Non Dimming

- 05.5771.40
- 05.5771.40.78
- 05.5771.14
- 05.5771.AP


Dali 2

- 05.5771.40.DA
- 05.5771.40.YU
- 05.5771.14.DA
- 05.5771.AP.DA

Casambi

- 05.5771.40.CB
- 05.5771.40.C6
- 05.5771.14.CB
- 05.5771.AP.CB

67° HIGH COMFORT



Luminous flux luminaire
1856 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1755	1.32
2	439	2.64
3	195	3.96
4	110	5.28
5	70	6.61

Optic Oval - 4000K

Non Dimming

- 05.6277.40
- 05.6277.40.78
- 05.6277.14
- 05.6277.AP


Dali 2

- 05.6277.40.DA
- 05.6277.40.YU
- 05.6277.14.DA
- 05.6277.AP.DA

Casambi

- 05.6277.40.CB
- 05.6277.40.C6
- 05.6277.14.CB
- 05.6277.AP.CB

80° OVAL



Luminous flux luminaire
1842 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1180	1.68
2	295	3.36
3	131	5.03
4	74	6.71
5	47	8.39

Optic High Comfort - 4000K

Non Dimming

- 05.5772.40
- 05.5772.40.78
- 05.5772.14
- 05.5772.AP


Dali 2

- 05.5772.40.DA
- 05.5772.40.YU
- 05.5772.14.DA
- 05.5772.AP.DA

Casambi

- 05.5772.40.CB
- 05.5772.40.C6
- 05.5772.14.CB
- 05.5772.AP.CB

67° HIGH COMFORT




Luminous flux luminaire
1939 lm


Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1834	1.32
2	458	2.64
3	204	3.96
4	115	5.28
5	73	6.61

Workmates In-Track Small

Top LED High Efficiency
Non Dimming: 15,5W - 1817 lm - 3000K/CRI 90 / 1831 lm - 3500K/CRI 90 / 1858 lm - 4000K/CRI 90
Dali 2: 15W - 1817 lm - 3000K/CRI 90 / 1831 lm - 3500K/CRI 90 / 1858 lm - 4000K/CRI 90







Luminaire for use on a three-phase track, with adapters for No Dim and Dali control. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim y Dali. Fuente de luz de alta eficiencia. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360° para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65°<3000.

Optic Wide Flood - 3000K


Non Dimming

- 05.6280.40
- 05.6280.40.78
- 05.6280.14
- 05.6280.AP

Dali 2

- 05.6280.40.DA
- 05.6280.40.YU
- 05.6280.14.DA
- 05.6280.AP.DA





Luminous flux luminaire
1768 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1143	1.55
2	286	3.10
3	127	4.66
4	71	6.21
5	46	7.76

Optic Wide Flood - 4000K


Non Dimming

- 05.6282.40
- 05.6282.40.78
- 05.6282.14
- 05.6282.AP

Dali 2

- 05.6282.40.DA
- 05.6282.40.YU
- 05.6282.14.DA
- 05.6282.AP.DA





Luminous flux luminaire
1830 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1183	1.55
2	296	3.10
3	131	4.66
4	74	6.21
5	47	7.76

Optic Wide Flood - 3500K


Non Dimming

- 05.6281.40
- 05.6281.40.78
- 05.6281.14
- 05.6281.AP

Dali 2

- 05.6281.40.DA
- 05.6281.40.YU
- 05.6281.14.DA
- 05.6281.AP.DA





Luminous flux luminaire
1773 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	1146	1.55
2	286	3.10
3	127	4.66
4	72	6.21
5	46	7.76

NEW

Optic Oval - 3000K


Non Dimming

- 05.6285.40
- 05.6285.40.78
- 05.6285.14
- 05.6285.AP

Dali 2

- 05.6285.40.DA
- 05.6285.40.YU
- 05.6285.14.DA
- 05.6285.AP.DA





Luminous flux luminaire
1720 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1096	1.67
2	274	3.34
3	122	5.00
4	68	6.67
5	44	8.34

Optic High Comfort - 3000K


Non Dimming

- 05.5780.40
- 05.5780.40.78
- 05.5780.14
- 05.5780.AP

Dali 2

- 05.5780.40.DA
- 05.5780.40.YU
- 05.5780.14.DA
- 05.5780.AP.DA





Luminous flux luminaire
1850 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1780	1.31
2	445	2.61
3	198	3.92
4	111	5.23
5	71	6.54

Optic Oval - 3500K


Non Dimming

- 05.6286.40
- 05.6286.40.78
- 05.6286.14
- 05.6286.AP

Dali 2

- 05.6286.40.DA
- 05.6286.40.YU
- 05.6286.14.DA
- 05.6286.AP.DA





Luminous flux luminaire
1725 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1099	1.67
2	275	3.34
3	122	5.00
4	69	6.67
5	44	8.34

Optic High Comfort - 3500K


Non Dimming

- 05.5781.40
- 05.5781.40.78
- 05.5781.14
- 05.5781.AP

Dali 2

- 05.5781.40.DA
- 05.5781.40.YU
- 05.5781.14.DA
- 05.5781.AP.DA





Luminous flux luminaire
1855 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1785	1.31
2	446	2.61
3	198	3.92
4	112	5.23
5	71	6.54

Optic Oval - 4000K


Non Dimming

- 05.6287.40
- 05.6287.40.78
- 05.6287.14
- 05.6287.AP

Dali 2

- 05.6287.40.DA
- 05.6287.40.YU
- 05.6287.14.DA
- 05.6287.AP.DA





Luminous flux luminaire
1780 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1134	1.67
2	283	3.34
3	126	5.00
4	71	6.67
5	45	8.34

Optic High Comfort - 4000K


Non Dimming

- 05.5782.40
- 05.5782.40.78
- 05.5782.14
- 05.5782.AP

Dali 2

- 05.5782.40.DA
- 05.5782.40.YU
- 05.5782.14.DA
- 05.5782.AP.DA






Luminous flux luminaire
1887 lm


Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1815	1.31
2	454	2.61
3	202	3.92
4	113	5.23
5	73	6.54

Workmates In-Track Small

Top LED Full Spectrum
Non Dimming: 15,5W - 1346 lm - 3000K/CRI 98 / 1357 lm - 3500K/CRI 98 / 1369 lm - 4000K/CRI 98
Dali 2: 15W - 1346 lm - 3000K/CRI 98 / 1357 lm - 3500K/CRI 98 / 1369 lm - 4000K/CRI 98







Luminaire for use on a three-phase track, with adapters for No Dim and Dali control. High-quality colour rendering *Full Spectrum* light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.


Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim y Dali. Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000.

Optic Wide Flood - 3000K

Non Dimming
- 05.6290.40
- 05.6290.40.78
- 05.6290.14
- 05.6290.AP

Dali 2
- 05.6290.40.DA
- 05.6290.40.YU
- 05.6290.14.DA
- 05.6290.AP.DA





Luminous flux luminaire
1231 lm


Beam Angle:		76°
h(m)	E(lx)	D(m)
1	796	1.55
2	199	3.10
3	88	4.66
4	50	6.21
5	32	7.76

Optic Wide Flood - 4000K

Non Dimming
- 05.6292.40
- 05.6292.40.78
- 05.6292.14
- 05.6292.AP

Dali 2
- 05.6292.40.DA
- 05.6292.40.YU
- 05.6292.14.DA
- 05.6292.AP.DA





Luminous flux luminaire
1300 lm


Beam Angle:		76°
h(m)	E(lx)	D(m)
1	840	1.55
2	210	3.10
3	93	4.66
4	53	6.21
5	34	7.76

Optic Wide Flood - 3500K

Non Dimming
- 05.6291.40
- 05.6291.40.78
- 05.6291.14
- 05.6291.AP

Dali 2
- 05.6291.40.DA
- 05.6291.40.YU
- 05.6291.14.DA
- 05.6291.AP.DA





Luminous flux luminaire
1238 lm

Beam Angle:		76°
h(m)	E(lx)	D(m)
1	800	1.55
2	200	3.10
3	89	4.66
4	50	6.21
5	32	7.76

NEW

Optic Oval - 3000K


Non Dimming

- 05.6295.40
- 05.6295.40.78
- 05.6295.14
- 05.6295.AP

Dali 2

- 05.6295.40.DA
- 05.6295.40.YU
- 05.6295.14.DA
- 05.6295.AP.DA





Luminous flux luminaire
1192 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	759	1.67
2	190	3.34
3	84	5.00
4	47	6.67
5	30	8.34

Optic High Comfort - 3000K


Non Dimming

- 05.5790.40
- 05.5790.40.78
- 05.5790.14
- 05.5790.AP

Dali 2

- 05.5790.40.DA
- 05.5790.40.YU
- 05.5790.14.DA
- 05.5790.AP.DA





Luminous flux luminaire
1289 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1240	1.31
2	310	2.61
3	138	3.92
4	77	5.23
5	50	6.54

Optic Oval - 3500K


Non Dimming

- 05.6296.40
- 05.6296.40.78
- 05.6296.14
- 05.6296.AP

Dali 2

- 05.6296.40.DA
- 05.6296.40.YU
- 05.6296.14.DA
- 05.6296.AP.DA





Luminous flux luminaire
1198 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	763	1.67
2	191	3.34
3	85	5.00
4	48	6.67
5	31	8.34

Optic High Comfort - 3500K


Non Dimming

- 05.5791.40
- 05.5791.40.78
- 05.5791.14
- 05.5791.AP

Dali 2

- 05.5791.40.DA
- 05.5791.40.YU
- 05.5791.14.DA
- 05.5791.AP.DA





Luminous flux luminaire
1293 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1244	1.31
2	311	2.61
3	138	3.92
4	78	5.23
5	50	6.54

Optic Oval - 4000K


Non Dimming

- 05.6297.40
- 05.6297.40.78
- 05.6297.14
- 05.6297.AP

Dali 2

- 05.6297.40.DA
- 05.6297.40.YU
- 05.6297.14.DA
- 05.6297.AP.DA





Luminous flux luminaire
1259 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	802	1.67
2	200	3.34
3	89	5.00
4	50	6.67
5	32	8.34

Optic High Comfort - 4000K


Non Dimming

- 05.5792.40
- 05.5792.40.78
- 05.5792.14
- 05.5792.AP

Dali 2

- 05.5792.40.DA
- 05.5792.40.YU
- 05.5792.14.DA
- 05.5792.AP.DA






Luminous flux luminaire
1357 lm


Beam Angle:		66°
h(m)	E(lx)	D(m)
1	1306	1.31
2	326	2.61
3	145	3.92
4	82	5.23
5	52	6.54

Workmates In-Track Large

Top LED High Efficiency
Non Dimming: 21W - 2726 lm - 3000K/CRI 90 / 2758 lm - 3500K/CRI 90 / 2786 lm - 4000K/CRI 90
Dali 2: 22W - 2726 lm - 3000K/CRI 90 / 2758 lm - 3500K/CRI 90 / 2786 lm - 4000K/CRI 90







Luminaire for use on a three-phase track, with adapters for No Dim and Dali *control*. High-efficiency light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65°<3000 compliant.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim y Dali. Fuente de luz de alta eficiencia. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360° para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65°<3000.

Optic Wide Flood - 3000K


Non Dimming

- 05.6300.40
- 05.6300.40.78
- 05.6300.14
- 05.6300.AP

Dali 2

- 05.6300.40.DA
- 05.6300.40.YU
- 05.6300.14.DA
- 05.6300.AP.DA





Luminous flux luminaire
2582 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1634	1.57
2	409	3.13
3	182	4.70
4	102	6.26
5	65	7.83

Optic Wide Flood - 4000K


Non Dimming

- 05.6302.40
- 05.6302.40.78
- 05.6302.14
- 05.6302.AP

Dali 2

- 05.6302.40.DA
- 05.6302.40.YU
- 05.6302.14.DA
- 05.6302.AP.DA





Luminous flux luminaire
2673 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1692	1.57
2	423	3.13
3	188	4.70
4	106	6.26
5	68	7.83

Optic Wide Flood - 3500K


Non Dimming

- 05.6301.40
- 05.6301.40.78
- 05.6301.14
- 05.6301.AP

Dali 2

- 05.6301.40.DA
- 05.6301.40.YU
- 05.6301.14.DA
- 05.6301.AP.DA





Luminous flux luminaire
2590 lm

Beam Angle: 76°

h(m)	E(lx)	D(m)
1	1639	1.57
2	410	3.13
3	182	4.70
4	102	6.26
5	66	7.83

NEW

Optic Oval - 3000K


Non Dimming

- 05.6305.40
- 05.6305.40.78
- 05.6305.14
- 05.6305.AP

Dali 2

- 05.6305.40.DA
- 05.6305.40.YU
- 05.6305.14.DA
- 05.6305.AP.DA





Luminous flux luminaire
2462 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1577	1.68
2	394	3.36
3	175	5.03
4	99	6.71
5	63	8.39

Optic High Comfort - 3000K


Non Dimming

- 05.5800.40
- 05.5800.40.78
- 05.5800.14
- 05.5800.AP

Dali 2

- 05.5800.40.DA
- 05.5800.40.YU
- 05.5800.14.DA
- 05.5800.AP.DA





Luminous flux luminaire
2711 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	2563	1.32
2	641	2.64
3	285	3.96
4	160	5.28
5	103	6.61

Optic Oval - 3500K


Non Dimming

- 05.6306.40
- 05.6306.40.78
- 05.6306.14
- 05.6306.AP

Dali 2

- 05.6306.40.DA
- 05.6306.40.YU
- 05.6306.14.DA
- 05.6306.AP.DA





Luminous flux luminaire
2469 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1582	1.68
2	395	3.36
3	176	5.03
4	99	6.71
5	63	8.39

Optic High Comfort - 3500K


Non Dimming

- 05.5801.40
- 05.5801.40.78
- 05.5801.14
- 05.5801.AP

Dali 2

- 05.5801.40.DA
- 05.5801.40.YU
- 05.5801.14.DA
- 05.5801.AP.DA





Luminous flux luminaire
2718 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	2571	1.32
2	643	2.64
3	286	3.96
4	161	5.28
5	103	6.61

Optic Oval - 4000K


Non Dimming

- 05.6307.40
- 05.6307.40.78
- 05.6307.14
- 05.6307.AP

Dali 2

- 05.6307.40.DA
- 05.6307.40.YU
- 05.6307.14.DA
- 05.6307.AP.DA





Luminous flux luminaire
2548 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1632	1.68
2	408	3.36
3	181	5.03
4	102	6.71
5	65	8.39

Optic High Comfort - 4000K


Non Dimming

- 05.5802.40
- 05.5802.40.78
- 05.5802.14
- 05.5802.AP

Dali 2

- 05.5802.40.DA
- 05.5802.40.YU
- 05.5802.14.DA
- 05.5802.AP.DA






Luminous flux luminaire
2790 lm


Beam Angle:		67°
h(m)	E(lx)	D(m)
1	2639	1.32
2	660	2.64
3	293	3.96
4	165	5.28
5	106	6.61

Workmates In-Track Large

Top LED Full Spectrum
Non Dimming: 21W - 2018 lm - 3000K/CRI 98 / 2036 lm - 3500K/CRI 98 / 2053 lm - 4000K/CRI 98
Dali 2: 22W - 2018 lm - 3000K/CRI 98 / 2036 lm - 3500K/CRI 98 / 2053 lm - 4000K/CRI 98







Luminaire for use on a three-phase track, with adapters for No Dim and Dali *control*. High-quality colour rendering *Full Spectrum* light source. Also available in a The Running Magnet version. This can rotate by 360° on the axis of its rear arm to reach any position relative to the track (from parallel to perpendicular). UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.

Luminaria para aplicación en carril trifásico, con adaptadores para control No Dim y Dali. Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. También disponible en versión para The Running Magnet. Sobre el eje de su brazo trasero, puede girar 360º para adoptar cualquier posición con respecto al carril (desde paralela a perpendicular). UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000.

Optic Wide Flood - 3000K


Non Dimming

- 05.6310.40
- 05.6310.40.78
- 05.6310.14
- 05.6310.AP

Dali 2

- 05.6310.40.DA
- 05.6310.40.YU
- 05.6310.14.DA
- 05.6310.AP.DA





Luminous flux luminaire
1761 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1155	1.55
2	289	3.09
3	128	4.64
4	72	6.18
5	46	7.73

Optic Wide Flood - 4000K


Non Dimming

- 05.6312.40
- 05.6312.40.78
- 05.6312.14
- 05.6312.AP

Dali 2

- 05.6312.40.DA
- 05.6312.40.YU
- 05.6312.14.DA
- 05.6312.AP.DA





Luminous flux luminaire
1860 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1219	1.55
2	305	3.09
3	135	4.64
4	76	6.18
5	49	7.73

Optic Wide Flood - 3500K


Non Dimming

- 05.6311.40
- 05.6311.40.78
- 05.6311.14
- 05.6311.AP

Dali 2

- 05.6311.40.DA
- 05.6311.40.YU
- 05.6311.14.DA
- 05.6311.AP.DA





Luminous flux luminaire
1770 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	1160	1.55
2	290	3.09
3	129	4.64
4	73	6.18
5	46	7.73

NEW

Optic Oval - 3000K


Non Dimming

- 05.6315.40
- 05.6315.40.78
- 05.6315.14
- 05.6315.AP

Dali 2

- 05.6315.40.DA
- 05.6315.40.YU
- 05.6315.14.DA
- 05.6315.AP.DA





Luminous flux luminaire
1744 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1117	1.68
2	279	3.36
3	124	5.03
4	70	6.71
5	45	8.39

Optic High Comfort - 3000K


Non Dimming

- 05.5810.40
- 05.5810.40.78
- 05.5810.14
- 05.5810.AP

Dali 2

- 05.5810.40.DA
- 05.5810.40.YU
- 05.5810.14.DA
- 05.5810.AP.DA





Luminous flux luminaire
1848 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1747	1.32
2	437	2.64
3	194	3.96
4	109	5.28
5	70	6.61

Optic Oval - 3500K


Non Dimming

- 05.6316.40
- 05.6316.40.78
- 05.6316.14
- 05.6316.AP

Dali 2

- 05.6316.40.DA
- 05.6316.40.YU
- 05.6316.14.DA
- 05.6316.AP.DA





Luminous flux luminaire
1753 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1123	1.68
2	281	3.36
3	125	5.03
4	70	6.71
5	45	8.39

Optic High Comfort - 3500K


Non Dimming

- 05.5811.40
- 05.5811.40.78
- 05.5811.14
- 05.5811.AP

Dali 2

- 05.5811.40.DA
- 05.5811.40.YU
- 05.5811.14.DA
- 05.5811.AP.DA





Luminous flux luminaire
1856 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1755	1.32
2	439	2.64
3	195	3.96
4	110	5.28
5	70	6.61

Optic Oval - 4000K


Non Dimming

- 05.6317.40
- 05.6317.40.78
- 05.6317.14
- 05.6317.AP

Dali 2

- 05.6317.40.DA
- 05.6317.40.YU
- 05.6317.14.DA
- 05.6317.AP.DA





Luminous flux luminaire
1842 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1180	1.68
2	295	3.36
3	131	5.03
4	74	6.71
5	47	8.39

Optic High Comfort - 4000K


Non Dimming

- 05.5812.40
- 05.5812.40.78
- 05.5812.14
- 05.5812.AP

Dali 2

- 05.5812.40.DA
- 05.5812.40.YU
- 05.5812.14.DA
- 05.5812.AP.DA






Luminous flux luminaire
1939 lm

Beam Angle:		67°
h(m)	E(lx)	D(m)
1	1834	1.32
2	458	2.64
3	204	3.96
4	115	5.28
5	73	6.61

Workmates Suspension Down

Top LED High Efficiency
Non Dimming / Dali 2: 28W - 4061 lm - 3000K/CRI 90 / 4090 lm - 3500K/CRI 90 / 4157 lm - 4000K/CRI 90
Casambi: 26W - 4061 lm - 3000K/CRI 90 / 4090 lm - 3500K/CRI 90 / 4157 lm - 4000K/CRI 90







Suspension luminaire. *Down* emission. High-efficiency light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Mechanical union module available for modular lines for various units. UGR<19.
EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de suspensión. Emisión Down. Fuente de luz de alta eficiencia. Driver no incluido (Kit accesorio para driver remoto o de superficie). Altura de suspensión ajustable. Disponible módulo de unión mecánico para líneas modulares de varias unidades. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K


Non Dimming / Dali 2

- 05.6320.40
- 05.6320.40.78
- 05.6320.14
- 05.6320.AP

Casambi

- 05.6320.40.CB
- 05.6320.40.C6
- 05.6320.14.CB
- 05.6320.AP.CB





Luminous flux luminaire
3392 lm

Beam Angle: 73°

h(m)	E(lx)	D(m)
1	2249	1.49
2	562	2.99
3	250	4.48
4	141	5.97
5	90	7.46

Optic Wide Flood - 4000K


Non Dimming / Dali 2

- 05.6322.40
- 05.6322.40.78
- 05.6322.14
- 05.6322.AP

Casambi

- 05.6322.40.CB
- 05.6322.40.C6
- 05.6322.14.CB
- 05.6322.AP.CB





Luminous flux luminaire
3594 lm

Beam Angle: 73°

h(m)	E(lx)	D(m)
1	2383	1.49
2	596	2.99
3	265	4.48
4	149	5.97
5	95	7.46

Optic Wide Flood - 3500K


Non Dimming / Dali 2

- 05.6321.40
- 05.6321.40.78
- 05.6321.14
- 05.6321.AP

Casambi

- 05.6321.40.CB
- 05.6321.40.C6
- 05.6321.14.CB
- 05.6321.AP.CB





Luminous flux luminaire
3408 lm

Beam Angle: 73°

h(m)	E(lx)	D(m)
1	2259	1.49
2	565	2.99
3	251	4.48
4	141	5.97
5	90	7.46

NEW

Optic Oval - 3000K


Non Dimming / Dali 2

- 05.6325.40
- 05.6325.40.78
- 05.6325.14
- 05.6325.AP

Casambi

- 05.6325.40.CB
- 05.6325.40.C6
- 05.6325.14.CB
- 05.6325.AP.CB





Luminous flux luminaire
3216 lm

Beam Angle:		71°
h(m)	E(lx)	D(m)
1	2095	1.42
2	524	2.85
3	233	4.27
4	131	5.70
5	84	7.12

Optic High Comfort - 3000K


Non Dimming / Dali 2

- 05.5820.40
- 05.5820.40.78
- 05.5820.14
- 05.5820.AP

Casambi

- 05.5820.40.CB
- 05.5820.40.C6
- 05.5820.14.CB
- 05.5820.AP.CB





Luminous flux luminaire
3482 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	3350	1.31
2	837	2.61
3	372	3.92
4	209	5.23
5	134	6.54

Optic Oval - 3500K


Non Dimming / Dali 2

- 05.6326.40
- 05.6326.40.78
- 05.6326.14
- 05.6326.AP

Casambi

- 05.6326.40.CB
- 05.6326.40.C6
- 05.6326.14.CB
- 05.6326.AP.CB





Luminous flux luminaire
3232 lm

Beam Angle:		71°
h(m)	E(lx)	D(m)
1	2105	1.42
2	526	2.85
3	234	4.27
4	132	5.70
5	84	7.12

Optic High Comfort - 3500K


Non Dimming / Dali 2

- 05.5821.40
- 05.5821.40.78
- 05.5821.14
- 05.5821.AP

Casambi

- 05.5821.40.CB
- 05.5821.40.C6
- 05.5821.14.CB
- 05.5821.AP.CB





Luminous flux luminaire
3498 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	3365	1.31
2	841	2.61
3	374	3.92
4	210	5.23
5	135	6.54

Optic Oval - 4000K


Non Dimming / Dali 2

- 05.6327.40
- 05.6327.40.78
- 05.6327.14
- 05.6327.AP

Casambi

- 05.6327.40.CB
- 05.6327.40.C6
- 05.6327.14.CB
- 05.6327.AP.CB





Luminous flux luminaire
3408 lm

Beam Angle:		71°
h(m)	E(lx)	D(m)
1	2220	1.42
2	555	2.85
3	247	4.27
4	139	5.70
5	89	7.12

Optic High Comfort - 4000K


Non Dimming / Dali 2

- 05.5822.40
- 05.5822.40.78
- 05.5822.14
- 05.5822.AP

Casambi

- 05.5822.40.CB
- 05.5822.40.C6
- 05.5822.14.CB
- 05.5822.AP.CB






Luminous flux luminaire
3672 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	3533	1.31
2	883	2.61
3	393	3.92
4	221	5.23
5	141	6.54

Workmates Suspension Down

Top LED Full Spectrum
Non Dimming / Dali 2: 28W - 2976 lm - 3000K/CRI 98 / 3005 lm - 3500K/CRI 98 / 3034 lm - 4000K/CRI 98
Casambi: 26W - 2976 lm - 3000K/CRI 98 / 3005 lm - 3500K/CRI 98 / 3034 lm - 4000K/CRI 98







Suspension luminaire. *Down* emission. High-quality colour rendering *Full Spectrum* light source. Driver not included. Adjustable suspension height. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de suspensión. Emisión Down. Fuente de luz *Full Spectrum* de alta calidad en la reproducción cromática. Driver no incluido. Altura de suspensión ajustable. Disponible módulo de unión mecánico para líneas modulares de varias unidades. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K


Non Dimming / Dali 2

- 05.6330.40
- 05.6330.40.78
- 05.6330.14
- 05.6330.AP

Casambi

- 05.6330.40.CB
- 05.6330.40.C6
- 05.6330.14.CB
- 05.6330.AP.CB





Luminous flux luminaire
2464 lm

Beam Angle: 73°

h(m)	E(lx)	D(m)
1	1607	1.49
2	402	2.97
3	179	4.46
4	100	5.95
5	64	7.43

Optic Wide Flood - 4000K


Non Dimming / Dali 2

- 05.6332.40
- 05.6332.40.78
- 05.6332.14
- 05.6332.AP

Casambi

- 05.6332.40.CB
- 05.6332.40.C6
- 05.6332.14.CB
- 05.6332.AP.CB





Luminous flux luminaire
2701 lm

Beam Angle: 73°

h(m)	E(lx)	D(m)
1	1761	1.49
2	440	2.97
3	196	4.46
4	110	5.95
5	70	7.43

Optic Wide Flood - 3500K


Non Dimming / Dali 2

- 05.6331.40
- 05.6331.40.78
- 05.6331.14
- 05.6331.AP

Casambi

- 05.6331.40.CB
- 05.6331.40.C6
- 05.6331.14.CB
- 05.6331.AP.CB





Luminous flux luminaire
2491 lm

Beam Angle: 73°

h(m)	E(lx)	D(m)
1	1624	1.49
2	406	2.97
3	180	4.46
4	102	5.95
5	65	7.43

NEW

Optic Oval - 3000K


Non Dimming / Dali 2

- 05.6335.40
- 05.6335.40.78
- 05.6335.14
- 05.6335.AP

Casambi

- 05.6335.40.CB
- 05.6335.40.C6
- 05.6335.14.CB
- 05.6335.AP.CB





Luminous flux luminaire
2365 lm

Beam Angle:		71°
h(m)	E(lx)	D(m)
1	1530	1.43
2	383	2.86
3	170	4.28
4	96	5.71
5	61	7.14

Optic High Comfort - 3000K


Non Dimming / Dali 2

- 05.5830.40
- 05.5830.40.78
- 05.5830.14
- 05.5830.AP

Casambi

- 05.5830.40.CB
- 05.5830.40.C6
- 05.5830.14.CB
- 05.5830.AP.CB





Luminous flux luminaire
2554 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	2457	1.31
2	614	2.61
3	273	3.92
4	154	5.23
5	98	6.54

Optic Oval - 3500K


Non Dimming / Dali 2

- 05.6336.40
- 05.6336.40.78
- 05.6336.14
- 05.6336.AP

Casambi

- 05.6336.40.CB
- 05.6336.40.C6
- 05.6336.14.CB
- 05.6336.AP.CB





Luminous flux luminaire
2392 lm

Beam Angle:		71°
h(m)	E(lx)	D(m)
1	1548	1.43
2	387	2.86
3	172	4.28
4	97	5.71
5	62	7.14

Optic High Comfort - 3500K


Non Dimming / Dali 2

- 05.5831.40
- 05.5831.40.78
- 05.5831.14
- 05.5831.AP

Casambi

- 05.5831.40.CB
- 05.5831.40.C6
- 05.5831.14.CB
- 05.5831.AP.CB





Luminous flux luminaire
2579 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	2481	1.31
2	620	2.61
3	276	3.92
4	155	5.23
5	99	6.54

Optic Oval - 4000K


Non Dimming / Dali 2

- 05.6337.40
- 05.6337.40.78
- 05.6337.14
- 05.6337.AP

Casambi

- 05.6337.40.CB
- 05.6337.40.C6
- 05.6337.14.CB
- 05.6337.AP.CB





Luminous flux luminaire
2593 lm

Beam Angle:		71°
h(m)	E(lx)	D(m)
1	1678	1.43
2	419	2.86
3	186	4.28
4	105	5.71
5	67	7.14

Optic High Comfort - 4000K


Non Dimming / Dali 2

- 05.5832.40
- 05.5832.40.78
- 05.5832.14
- 05.5832.AP

Casambi

- 05.5832.40.CB
- 05.5832.40.C6
- 05.5832.14.CB
- 05.5832.AP.CB






Luminous flux luminaire
2775 lm

Beam Angle:		66°
h(m)	E(lx)	D(m)
1	2670	1.31
2	667	2.61
3	297	3.92
4	167	5.23
5	107	6.54

Workmates Suspension Up&Down

Top LED High Efficiency: Non Dimming / Dali 2: 57W / Casambi: 58,5W
Majority Up (70/30): 4316 lm Up - 1851 lm Down - 3000K/CRI 90 / 4413 lm Up - 1892 lm Down - 3500K/CRI 90 / 4531 lm Up - 1942 lm Down - 4000K/CRI 90
Majority Down (40/60): 2588 lm Up - 3913 lm Down - 3000K/CRI 90 / 2621 lm Up - 3942 lm Down - 3500K/CRI 90 / 2733 lm Up - 4100 lm Down - 4000K/CRI 90







Suspension luminaire. *Up&Down* emission. High-efficiency light source. Driver not included (accessory kit for remote or surface driver).
For *Non Dimming* models, you can configure the *Up&Down* luminous flux in 70/30 and 40/60 ratios (select the accessory kit for the driver concerned).
Adjustable suspension height.
Mechanical union module available for modular lines for various units.
UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de suspensión. Emisión *Up&Down*. Fuente de luz de alta eficiencia. Driver no incluido (Kit accesorio para driver remoto o de superficie). En los modelos *Non Dimming* existe la opción de configurar el flujo lumínico Up&Down en repartos 70/30 y 40/60 (seleccione el kit accesorio para el driver pertinente).
Altura de suspensión ajustable.
Disponible módulo de unión mecánico para líneas modulares de varias unidades. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000.
Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K


Non Dimming / Dali 2

- 05.6340.40
- 05.6340.40.78
- 05.6340.14
- 05.6340.AP

Casambi

- 05.6340.40.CB
- 05.6340.40.C6
- 05.6340.14.CB
- 05.6340.AP.CB


74° WIDE FLOOD MAJOR. UP



Luminous flux luminaire 5530 lm

Beam Angle: - 74°		
h(m)	E(lx)	D(m)
1	1393	1.49
2	348	2.99
3	155	4.48
4	87	5.97
5	56	7.46

74° WIDE FLOOD MAJOR. DOWN



Luminous flux luminaire 5570 lm

Beam Angle: - 74°		
h(m)	E(lx)	D(m)
1	2249	1.49
2	562	2.99
3	250	4.48
4	141	5.97
5	90	7.46

Optic Wide Flood - 3500K


Non Dimming / Dali 2

- 05.6341.40
- 05.6341.40.78
- 05.6341.14
- 05.6341.AP

Casambi

- 05.6341.40.CB
- 05.6341.40.C6
- 05.6341.14.CB
- 05.6341.AP.CB


74° WIDE FLOOD MAJOR. UP



Luminous flux luminaire 5655 lm

Beam Angle: - 74°		
h(m)	E(lx)	D(m)
1	1416	1.49
2	354	2.99
3	157	4.48
4	88	5.97
5	57	7.46

74° WIDE FLOOD MAJOR. DOWN



Luminous flux luminaire 5653 lm

Beam Angle: - 74°		
h(m)	E(lx)	D(m)
1	2259	1.49
2	565	2.99
3	251	4.48
4	141	5.97
5	90	7.46

Optic Wide Flood - 4000K


Non Dimming / Dali 2

- 05.6342.40
- 05.6342.40.78
- 05.6342.14
- 05.6342.AP

Casambi

- 05.6342.40.CB
- 05.6342.40.C6
- 05.6342.14.CB
- 05.6342.AP.CB


74° WIDE FLOOD MAJOR. UP



Luminous flux luminaire 5806 lm

Beam Angle: - 74°		
h(m)	E(lx)	D(m)
1	1456	1.49
2	364	2.99
3	162	4.48
4	91	5.97
5	58	7.46

74° WIDE FLOOD MAJOR. DOWN



Luminous flux luminaire 5880 lm

Beam Angle: - 74°		
h(m)	E(lx)	D(m)
1	2382	1.49
2	596	2.99
3	265	4.48
4	149	5.97
5	95	7.46

NEW

Optic Oval - 3000K


Non Dimming / Dali 2

- 05.6345.40
- 05.6345.40.78
- 05.6345.14
- 05.6345.AP

Casambi

- 05.6345.40.CB
- 05.6345.40.C6
- 05.6345.14.CB
- 05.6345.AP.CB


81° OVAL MAJOR. UP



Luminous flux luminaire 5456 lm

Beam Angle: -	81°
h(m)	E(lx) D(m)
1	1320 1.42
2	330 2.85
3	147 4.27
4	83 5.70
5	53 7.12

81° OVAL MAJOR. DOWN



Luminous flux luminaire 5395 lm

Beam Angle: -	81°
h(m)	E(lx) D(m)
1	2095 1.42
2	524 2.85
3	233 4.27
4	131 5.70
5	84 7.12

Optic High Comfort - 3000K


Non Dimming / Dali 2

- 05.5840.40
- 05.5840.40.78
- 05.5840.14
- 05.5840.AP

Casambi

- 05.5840.40.CB
- 05.5840.40.C6
- 05.5840.14.CB
- 05.5840.AP.CB


65° HIGH COMFORT MAJOR. UP



Luminous flux luminaire 4905 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2064 1.31
2	516 2.61
3	229 3.92
4	129 5.23
5	83 6.54

65° HIGH COMFORT MAJOR. DOWN



Luminous flux luminaire 5660 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	3271 1.31
2	818 2.61
3	363 3.92
4	204 5.23
5	131 6.54

Optic Oval - 3500K


Non Dimming / Dali 2

- 05.6346.40
- 05.6346.40.78
- 05.6346.14
- 05.6346.AP

Casambi

- 05.6346.40.CB
- 05.6346.40.C6
- 05.6346.14.CB
- 05.6346.AP.CB


81° OVAL MAJOR. UP



Luminous flux luminaire 5578 lm

Beam Angle: -	81°
h(m)	E(lx) D(m)
1	1341 1.42
2	335 2.85
3	149 4.27
4	84 5.70
5	54 7.12

81° OVAL MAJOR. DOWN



Luminous flux luminaire 5477 lm

Beam Angle: -	81°
h(m)	E(lx) D(m)
1	2105 1.42
2	526 2.85
3	234 4.27
4	132 5.70
5	84 7.12

Optic High Comfort - 3500K


Non Dimming / Dali 2

- 05.5841.40
- 05.5841.40.78
- 05.5841.14
- 05.5841.AP

Casambi

- 05.5841.40.CB
- 05.5841.40.C6
- 05.5841.14.CB
- 05.5841.AP.CB


65° HIGH COMFORT MAJOR. UP



Luminous flux luminaire 4945 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2081 1.31
2	520 2.61
3	231 3.92
4	130 5.23
5	83 6.54

65° HIGH COMFORT MAJOR. DOWN



Luminous flux luminaire 5752 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	3324 1.31
2	831 2.61
3	369 3.92
4	208 5.23
5	133 6.54

Optic Oval - 4000K


Non Dimming / Dali 2

- 05.6347.40
- 05.6347.40.78
- 05.6347.14
- 05.6347.AP

Casambi

- 05.6347.40.CB
- 05.6347.40.C6
- 05.6347.14.CB
- 05.6347.AP.CB


81° OVAL MAJOR. UP



Luminous flux luminaire 5726 lm

Beam Angle: -	81°
h(m)	E(lx) D(m)
1	1380 1.42
2	345 2.85
3	153 4.27
4	86 5.70
5	55 7.12

81° OVAL MAJOR. DOWN



Luminous flux luminaire 5694 lm

Beam Angle: -	81°
h(m)	E(lx) D(m)
1	2220 1.42
2	555 2.85
3	247 4.27
4	139 5.70
5	89 7.12

Optic High Comfort - 4000K


Non Dimming / Dali 2

- 05.5842.40
- 05.5842.40.78
- 05.5842.14
- 05.5842.AP

Casambi

- 05.5842.40.CB
- 05.5842.40.C6
- 05.5842.14.CB
- 05.5842.AP.CB


65° HIGH COMFORT MAJOR. UP



Luminous flux luminaire 5110 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2150 1.31
2	538 2.61
3	239 3.92
4	134 5.23
5	86 6.54

65° HIGH COMFORT MAJOR. DOWN




Luminous flux luminaire 6022 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	3480 1.31
2	870 2.61
3	387 3.92
4	217 5.23
5	139 6.54

Workmates Suspension Up&Down

Top LED Full Spectrum: Non Dimming / Dali 2: 57W / Casambi: 58,5W
Majority Up (70/30): 3809 lm Up - 1633 lm Down - 3000K/CRI 98 / 3911 lm Up - 1671 lm Down - 3500K/CRI 98 / 4022 lm Up - 1725 lm Down - 4000K/CRI 98
Majority Down (40/60): 2122 lm Up - 3185 lm Down - 3000K/CRI 98 / 2238 lm Up - 3358 lm Down - 3500K/CRI 98 / 2081 lm Up - 3122 lm Down - 4000K/CRI 98







Suspension luminaire. *Up&Down* emission. High-quality colour rendering *Down Full Spectrum* light source. High-efficiency *Up* light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de suspensión. Emisión *Up&Down*, con mayor cantidad de flujo lumínico en la parte inferior. Fuente de luz *Down Full Spectrum* de alta calidad en la reproducción cromática. Fuente de luz *Up* de alta eficiencia. Driver no incluido (Kit accesorio para driver remoto o de superficie). Altura de suspensión ajustable. Disponible módulo de unión mecánico para líneas modulares de varias unidades. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K


Non Dimming / Dali 2

- 05.6350.40
- 05.6350.40.78
- 05.6350.14
- 05.6350.AP

Casambi

- 05.6350.40.CB
- 05.6350.40.C6
- 05.6350.14.CB
- 05.6350.AP.CB


71° WIDE FLOOD MAJOR. UP



Luminous flux luminaire 4921 lm

Beam Angle: - 71°		
h(m)	E(lx)	D(m)
1	783	5.67
2	196	11.33
3	87	17.00
4	49	22.67
5	31	28.34

75° WIDE FLOOD MAJOR. DOWN



Luminous flux luminaire 4642 lm

Beam Angle: - 75°		
h(m)	E(lx)	D(m)
1	1607	1.49
2	402	2.97
3	179	4.46
4	100	5.95
5	64	7.43

Optic Wide Flood - 3500K


Non Dimming / Dali 2

- 05.6351.40
- 05.6351.40.78
- 05.6351.14
- 05.6351.AP

Casambi

- 05.6351.40.CB
- 05.6351.40.C6
- 05.6351.14.CB
- 05.6351.AP.CB


71° WIDE FLOOD MAJOR. UP



Luminous flux luminaire 5047 lm

Beam Angle: - 71°		
h(m)	E(lx)	D(m)
1	803	5.67
2	201	11.33
3	89	17.00
4	50	22.67
5	32	28.34

75° WIDE FLOOD MAJOR. DOWN



Luminous flux luminaire 4736 lm

Beam Angle: - 75°		
h(m)	E(lx)	D(m)
1	1624	1.49
2	406	2.97
3	180	4.46
4	102	5.95
5	65	7.43

Optic Wide Flood - 4000K


Non Dimming / Dali 2

- 05.6352.40
- 05.6352.40.78
- 05.6352.14
- 05.6352.AP

Casambi

- 05.6352.40.CB
- 05.6352.40.C6
- 05.6352.14.CB
- 05.6352.AP.CB


71° WIDE FLOOD MAJOR. UP



Luminous flux luminaire 5196 lm

Beam Angle: - 71°		
h(m)	E(lx)	D(m)
1	824	5.67
2	206	11.33
3	92	17.00
4	52	22.67
5	33	28.34

75° WIDE FLOOD MAJOR. DOWN



Luminous flux luminaire 4987 lm

Beam Angle: - 75°		
h(m)	E(lx)	D(m)
1	1761	1.49
2	440	2.97
3	196	4.46
4	110	5.95
5	70	7.43

NEW

Optic Oval - 3000K


Non Dimming / Dali 2

- 05.6355.40
- 05.6355.40.78
- 05.6355.14
- 05.6355.AP

Casambi

- 05.6355.40.CB
- 05.6355.40.C6
- 05.6355.14.CB
- 05.6355.AP.CB


71° OVAL MAJOR. UP



Luminous flux luminaire 4868 lm

Beam Angle: -	71°
h(m)	E(lx) D(m)
1	783 5.67
2	196 11.33
3	87 17.00
4	49 22.67
5	31 28.34

82° OVAL MAJOR. DOWN



Luminous flux luminaire 4543 lm

Beam Angle: -	82°
h(m)	E(lx) D(m)
1	1530 1.43
2	383 2.86
3	170 4.28
4	96 5.71
5	61 7.14

Optic High Comfort - 3000K


Non Dimming / Dali 2

- 05.5850.40
- 05.5850.40.78
- 05.5850.14
- 05.5850.AP

Casambi

- 05.5850.40.CB
- 05.5850.40.C6
- 05.5850.14.CB
- 05.5850.AP.CB


65° HIGH COMFORT MAJOR. UP



Luminous flux luminaire 5621 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2365 1.31
2	591 2.61
3	263 3.92
4	148 5.23
5	95 6.54

65° HIGH COMFORT MAJOR. DOWN



Luminous flux luminaire 4732 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2735 1.31
2	684 2.61
3	304 3.92
4	171 5.23
5	109 6.54

Optic Oval - 3500K


Non Dimming / Dali 2

- 05.6356.40
- 05.6356.40.78
- 05.6356.14
- 05.6356.AP

Casambi

- 05.6356.40.CB
- 05.6356.40.C6
- 05.6356.14.CB
- 05.6356.AP.CB


71° OVAL MAJOR. UP



Luminous flux luminaire 4993 lm

Beam Angle: -	71°
h(m)	E(lx) D(m)
1	803 5.67
2	201 11.33
3	89 17.00
4	50 22.67
5	32 28.34

82° OVAL MAJOR. DOWN



Luminous flux luminaire 4637 lm

Beam Angle: -	82°
h(m)	E(lx) D(m)
1	1548 1.43
2	387 2.86
3	172 4.28
4	97 5.71
5	62 7.14

Optic High Comfort - 3500K


Non Dimming / Dali 2

- 05.5851.40
- 05.5851.40.78
- 05.5851.14
- 05.5851.AP

Casambi

- 05.5851.40.CB
- 05.5851.40.C6
- 05.5851.14.CB
- 05.5851.AP.CB


65° HIGH COMFORT MAJOR. UP



Luminous flux luminaire 5761 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2424 1.31
2	606 2.61
3	269 3.92
4	151 5.23
5	97 6.54

65° HIGH COMFORT MAJOR. DOWN



Luminous flux luminaire 4836 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2795 1.31
2	699 2.61
3	311 3.92
4	175 5.23
5	112 6.54

Optic Oval - 4000K


Non Dimming / Dali 2

- 05.6357.40
- 05.6357.40.78
- 05.6357.14
- 05.6357.AP

Casambi

- 05.6357.40.CB
- 05.6357.40.C6
- 05.6357.14.CB
- 05.6357.AP.CB


71° OVAL MAJOR. UP



Luminous flux luminaire 5140 lm

Beam Angle: -	71°
h(m)	E(lx) D(m)
1	824 5.67
2	206 11.33
3	92 17.00
4	52 22.67
5	33 28.34

82° OVAL MAJOR. DOWN



Luminous flux luminaire 4879 lm

Beam Angle: -	82°
h(m)	E(lx) D(m)
1	1678 1.43
2	419 2.86
3	186 4.28
4	105 5.71
5	67 7.14

Optic High Comfort - 4000K


Non Dimming / Dali 2

- 05.5852.40
- 05.5852.40.78
- 05.5852.14
- 05.5852.AP

Casambi

- 05.5852.40.CB
- 05.5852.40.C6
- 05.5852.14.CB
- 05.5852.AP.CB


65° HIGH COMFORT MAJOR. UP



Luminous flux luminaire 5621 lm

Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2365 1.31
2	591 2.61
3	263 3.92
4	148 5.23
5	95 6.54

65° HIGH COMFORT MAJOR. DOWN



Luminous flux luminaire 5125 lm


Beam Angle: -	65°
h(m)	E(lx) D(m)
1	2962 1.31
2	740 2.61
3	329 3.92
4	185 5.23
5	118 6.54

NEW

Workmates Suspension Up&Down Smart

Top LED High Efficiency: Casambi: Up 32,5W - Down 26W
Up: 4281 lm - 3000K/CRI 90 / 4339 lm - 3500K/CRI 90 / 4397 lm - 4000K/CRI 90
Down: 4061 lm - 3000K/CRI 90 / 4090 lm - 3500K/CRI 90 / 4157 lm - 4000K/CRI 90







Suspension luminaire. *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Smart version with integrated presence detection and brightness sensors. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.


Luminaria de suspensión. Emisión *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz de alta eficiencia. Driver no incluido (Kit accesorio para driver remoto o de superficie). Altura de suspensión ajustable. Versión Smart con sensores de presencia y de luminosidad integrados. Disponible módulo de unión mecánico para líneas modulares de varias unidades. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K

Casambi

- 05.6360.40.CB
- 05.6360.40.C6
- 05.6360.14.CB
- 05.6360.AP.CB

74° WIDE FLOOD



Luminous flux luminaire 7202 lm

Beam Angle: - 74°


h(m)	E(lx)	D(m)
1	2249	1.49
2	562	2.99
3	250	4.48
4	141	5.97
5	90	7.46

Optic Wide Flood - 3500K

Casambi

- 05.6361.40.CB
- 05.6361.40.C6
- 05.6361.14.CB
- 05.6361.AP.CB

74° WIDE FLOOD



Luminous flux luminaire 7305 lm

Beam Angle: - 74°


h(m)	E(lx)	D(m)
1	2259	1.49
2	565	2.99
3	251	4.48
4	141	5.97
5	90	7.46

Optic Wide Flood - 4000K

Casambi

- 05.6362.40.CB
- 05.6362.40.C6
- 05.6362.14.CB
- 05.6362.AP.CB

74° WIDE FLOOD



Luminous flux luminaire 7633 lm

Beam Angle: - 74°


h(m)	E(lx)	D(m)
1	2382	1.49
2	596	2.99
3	265	4.48
4	149	5.97
5	95	7.46

Optic High Comfort - 3000K

Casambi

- 05.5860.40.CB
- 05.5860.40.C6
- 05.5860.14.CB
- 05.5860.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 7085 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	3152	1.31
2	788	2.61
3	350	3.92
4	197	5.23
5	126	6.54

Optic High Comfort - 3500K

Casambi

- 05.5861.40.CB
- 05.5861.40.C6
- 05.5861.14.CB
- 05.5861.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 7200 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	3203	1.31
2	801	2.61
3	356	3.92
4	200	5.23
5	128	6.54

Optic High Comfort - 4000K

Casambi

- 05.5862.40.CB
- 05.5862.40.C6
- 05.5862.14.CB
- 05.5862.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 7580 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	3372	1.31
2	843	2.61
3	375	3.92
4	211	5.23
5	135	6.54

Optic Oval - 3000K

Casambi

- 05.6365.40.CB
- 05.6365.40.C6
- 05.6365.14.CB
- 05.6365.AP.CB

81° OVAL



Luminous flux luminaire 7026 lm

Beam Angle: - 81°


h(m)	E(lx)	D(m)
1	2095	1.42
2	524	2.85
3	233	4.27
4	131	5.70
5	84	7.12

Optic Oval - 3500K

Casambi

- 05.6366.40.CB
- 05.6366.40.C6
- 05.6366.14.CB
- 05.6366.AP.CB

81° OVAL



Luminous flux luminaire 7129 lm

Beam Angle: - 81°


h(m)	E(lx)	D(m)
1	2105	1.42
2	526	2.85
3	234	4.27
4	132	5.70
5	84	7.12

Optic Oval - 4000K

Casambi

- 05.6367.40.CB
- 05.6367.40.C6
- 05.6367.14.CB
- 05.6367.AP.CB

81° OVAL



Luminous flux luminaire 7447 lm

Beam Angle: - 81°


h(m)	E(lx)	D(m)
1	2220	1.42
2	555	2.85
3	247	4.27
4	139	5.70
5	89	7.12

NEW

Workmates Suspension Up&Down Smart

Top LED Full Spectrum: Casambi: Up 32,5W - Down 26W
Up: 4281 lm - 3000K/CRI 98 / 4339 lm - 3500K/CRI 98 / 4397 lm - 4000K/CRI 98
Down: 2976 lm - 3000K/CRI 98 / 3005 lm - 3500K/CRI 98 / 3034 lm - 4000K/CRI 98







Suspension luminaire. *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering *Down Full Spectrum* light source. High-efficiency *Up* light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Smart version with integrated presence detection and brightness sensors. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.


Luminaria de suspensión. Emisión *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down Full Spectrum* de alta calidad en la reproducción cromática. Fuente de luz *Up* de alta eficiencia. Driver no incluido (Kit accesorio para driver remoto o de superficie). Altura de suspensión ajustable. Versión Smart con sensores de presencia y de luminosidad integrados. Disponible módulo de unión mecánico para líneas modulares de varias unidades.
UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K

Casambi

- 05.6370.40.CB
- 05.6370.40.C6
- 05.6370.14.CB
- 05.6370.AP.CB

75° WIDE FLOOD



Luminous flux luminaire 6274 lm

Beam Angle: - 75°


h(m)	E(lx)	D(m)
1	1607	1.49
2	402	2.97
3	179	4.46
4	100	5.95
5	64	7.43

Optic Wide Flood - 3500K

Casambi

- 05.6371.40.CB
- 05.6371.40.C6
- 05.6371.14.CB
- 05.6371.AP.CB

75° WIDE FLOOD



Luminous flux luminaire 6388 lm

Beam Angle: - 75°


h(m)	E(lx)	D(m)
1	1624	1.49
2	406	2.97
3	180	4.46
4	102	5.95
5	65	7.43

Optic Wide Flood - 4000K

Casambi

- 05.6372.40.CB
- 05.6372.40.C6
- 05.6372.14.CB
- 05.6372.AP.CB

75° WIDE FLOOD



Luminous flux luminaire 6740 lm

Beam Angle: - 75°


h(m)	E(lx)	D(m)
1	1761	1.49
2	440	2.97
3	196	4.46
4	110	5.95
5	70	7.43

Optic High Comfort - 3000K

Casambi

- 05.5870.40.CB
- 05.5870.40.C6
- 05.5870.14.CB
- 05.5870.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 6198 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	2299	1.31
2	575	2.61
3	255	3.92
4	144	5.23
5	92	6.54

Optic High Comfort - 3500K

Casambi

- 05.5871.40.CB
- 05.5871.40.C6
- 05.5871.14.CB
- 05.5871.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 6325 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	2346	1.31
2	587	2.61
3	261	3.92
4	147	5.23
5	94	6.54

Optic High Comfort - 4000K

Casambi

- 05.5872.40.CB
- 05.5872.40.C6
- 05.5872.14.CB
- 05.5872.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 6723 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	2494	1.31
2	624	2.61
3	277	3.92
4	156	5.23
5	100	6.54

Optic Oval - 3000K

Casambi

- 05.6375.40.CB
- 05.6375.40.C6
- 05.6375.14.CB
- 05.6375.AP.CB

82° OVAL



Luminous flux luminaire 6175 lm

Beam Angle: - 82°


h(m)	E(lx)	D(m)
1	1530	1.43
2	383	2.86
3	170	4.28
4	96	5.71
5	61	7.14

Optic Oval - 3500K

Casambi

- 05.6376.40.CB
- 05.6376.40.C6
- 05.6376.14.CB
- 05.6376.AP.CB

82° OVAL



Luminous flux luminaire 6289 lm

Beam Angle: - 82°


h(m)	E(lx)	D(m)
1	1548	1.43
2	387	2.86
3	172	4.28
4	97	5.71
5	62	7.14

Optic Oval - 4000K

Casambi

- 05.6377.40.CB
- 05.6377.40.C6
- 05.6377.14.CB
- 05.6377.AP.CB

82° OVAL



Luminous flux luminaire 6632 lm


Beam Angle: - 82°

h(m)	E(lx)	D(m)
1	1678	1.43
2	419	2.86
3	186	4.28
4	105	5.71
5	67	7.14

Workmates Suspension Up&Down Tunable White

Top LED High Efficiency: Dali 2: Up 23W - Down 26W / Casambi: Up 21,5W - Down 26W
Up: 3619 lm - 2700K-5700K/CRI90
Down: 4061 lm - 3000K/CRI 90 / 4090 lm - 3500K/CRI 90 / 4157 lm - 4000K/CRI 90







Suspension luminaire. *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency *Down* light source. *Tunable White* variable CCT *Up* light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m² @ 65°<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de suspensión. Emisión *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz de *Down* de alta eficiencia. Fuente de luz *Up* de CCT variable *Tunable White*. Driver no incluido (Kit accesorio para driver remoto o de superficie). Altura de suspensión ajustable. Disponible módulo de unión mecánico para líneas modulares de varias unidades. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65°<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K


Dali 2

- 05.6380.40.DA
- 05.6380.40.YU
- 05.6380.14.DA
- 05.6380.AP.DA

Casambi

- 05.6380.40.CB
- 05.6380.40.C6
- 05.6380.14.CB
- 05.6380.AP.CB





Luminous flux luminaire
6426 lm

Beam Angle: - 74°

h(m)	E(lx)	D(m)
1	2249	1.49
2	562	2.99
3	250	4.48
4	141	5.97
5	90	7.46

Optic Wide Flood - 4000K


Dali 2

- 05.6382.40.DA
- 05.6382.40.YU
- 05.6382.14.DA
- 05.6382.AP.DA

Casambi

- 05.6382.40.CB
- 05.6382.40.C6
- 05.6382.14.CB
- 05.6382.AP.CB





Luminous flux luminaire
6740 lm

Beam Angle: - 74°

h(m)	E(lx)	D(m)
1	2382	1.49
2	596	2.99
3	265	4.48
4	149	5.97
5	95	7.46

Optic Wide Flood - 3500K


Dali 2

- 05.6381.40.DA
- 05.6381.40.YU
- 05.6381.14.DA
- 05.6381.AP.DA

Casambi

- 05.6381.40.CB
- 05.6381.40.C6
- 05.6381.14.CB
- 05.6381.AP.CB





Luminous flux luminaire
6500 lm

Beam Angle: - 74°

h(m)	E(lx)	D(m)
1	2259	1.49
2	565	2.99
3	251	4.48
4	141	5.97
5	90	7.46

NEW

Optic Oval - 3000K


Dali 2

- 05.6385.40.DA
- 05.6385.40.YU
- 05.6385.14.DA
- 05.6385.AP.DA

Casambi

- 05.6385.40.CB
- 05.6385.40.C6
- 05.6385.14.CB
- 05.6385.AP.CB





Luminous flux luminaire
6250 lm

Beam Angle: - 81°

h(m)	E(lx)	D(m)
1	2095	1.42
2	524	2.85
3	233	4.27
4	131	5.70
5	84	7.12

Optic High Comfort - 3000K


Dali 2

- 05.5880.40.DA
- 05.5880.40.YU
- 05.5880.14.DA
- 05.5880.AP.DA

Casambi

- 05.5880.40.CB
- 05.5880.40.C6
- 05.5880.14.CB
- 05.5880.AP.CB





Luminous flux luminaire
6311 lm

Beam Angle: - 65°

h(m)	E(lx)	D(m)
1	3152	1.31
2	788	2.61
3	350	3.92
4	197	5.23
5	126	6.54

Optic Oval - 3500K


Dali 2

- 05.6386.40.DA
- 05.6386.40.YU
- 05.6386.14.DA
- 05.6386.AP.DA

Casambi

- 05.6386.40.CB
- 05.6386.40.C6
- 05.6386.14.CB
- 05.6386.AP.CB





Luminous flux luminaire
6324 lm

Beam Angle: - 81°

h(m)	E(lx)	D(m)
1	2105	1.42
2	526	2.85
3	234	4.27
4	132	5.70
5	84	7.12

Optic High Comfort - 3500K


Dali 2

- 05.5881.40.DA
- 05.5881.40.YU
- 05.5881.14.DA
- 05.5881.AP.DA

Casambi

- 05.5881.40.CB
- 05.5881.40.C6
- 05.5881.14.CB
- 05.5881.AP.CB





Luminous flux luminaire
6418 lm

Beam Angle: - 65°

h(m)	E(lx)	D(m)
1	3205	1.31
2	801	2.61
3	356	3.92
4	200	5.23
5	128	6.54

Optic Oval - 4000K


Dali 2

- 05.6387.40.DA
- 05.6387.40.YU
- 05.6387.14.DA
- 05.6387.AP.DA

Casambi

- 05.6387.40.CB
- 05.6387.40.C6
- 05.6387.14.CB
- 05.6387.AP.CB





Luminous flux luminaire
6554 lm

Beam Angle: - 81°

h(m)	E(lx)	D(m)
1	2220	1.42
2	555	2.85
3	247	4.27
4	139	5.70
5	89	7.12

Optic High Comfort - 4000K


Dali 2

- 05.5882.40.DA
- 05.5882.40.YU
- 05.5882.14.DA
- 05.5882.AP.DA

Casambi

- 05.5882.40.CB
- 05.5882.40.C6
- 05.5882.14.CB
- 05.5882.AP.CB





Luminous flux luminaire
6680 lm


Beam Angle: - 65°

h(m)	E(lx)	D(m)
1	3336	1.31
2	834	2.61
3	371	3.92
4	208	5.23
5	133	6.54

Workmates Suspension Up&Down Tunable White

Top LED Full Spectrum: Dali 2: Up 23W - Down 26W / Casambi: Up 21,5W - Down 26W
Up: 3619 lm - 2700K-5700K/CRI90
Down: 2976 lm - 3000K/CRI 98 / 3005 lm - 3500K/CRI 98 / 3034 lm - 4000K/CRI 98







Suspension luminaire. *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering *Down Full Spectrum* light source. *Tunable White* variable CCT *Up* light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m² @ 65°<3000 compliant. Casambi, maximum distance between fixtures: 50m.

Luminaria de suspensión. Emisión *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down Full Spectrum* de alta calidad en la reproducción cromática. Fuente de luz *Up* de CCT variable *Tunable White*. Driver no incluido (Kit accesorio para driver remoto o de superficie). Altura de suspensión ajustable. Disponible módulo de unión mecánico para líneas modulares de varias unidades.
UGR<19. Conforme a la norma EN12464 - cd/m² @ 65°<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K


Dali 2

- 05.6390.40.DA
- 05.6390.40.YU
- 05.6390.14.DA
- 05.6390.AP.DA

Casambi

- 05.6390.40.CB
- 05.6390.40.C6
- 05.6390.14.CB
- 05.6390.AP.CB





Luminous flux luminaire
5498 lm

Beam Angle: - 75°

h(m)	E(lx)	D(m)
1	1607	1.49
2	402	2.97
3	179	4.46
4	100	5.95
5	64	7.43

Optic Wide Flood - 4000K


Dali 2

- 05.6392.40.DA
- 05.6392.40.YU
- 05.6392.14.DA
- 05.6392.AP.DA

Casambi

- 05.6392.40.CB
- 05.6392.40.C6
- 05.6392.14.CB
- 05.6392.AP.CB





Luminous flux luminaire
5847 lm

Beam Angle: - 75°

h(m)	E(lx)	D(m)
1	1761	1.49
2	440	2.97
3	196	4.46
4	110	5.95
5	70	7.43

Optic Wide Flood - 3500K


Dali 2

- 05.6391.40.DA
- 05.6391.40.YU
- 05.6391.14.DA
- 05.6391.AP.DA

Casambi

- 05.6391.40.CB
- 05.6391.40.C6
- 05.6391.14.CB
- 05.6391.AP.CB





Luminous flux luminaire
5583 lm

Beam Angle: - 75°

h(m)	E(lx)	D(m)
1	1624	1.49
2	406	2.97
3	180	4.46
4	102	5.95
5	65	7.43

NEW

Optic Oval - 3000K


Dali 2

- 05.6395.40.DA
- 05.6395.40.YU
- 05.6395.14.DA
- 05.6395.AP.DA

Casambi

- 05.6395.40.CB
- 05.6395.40.C6
- 05.6395.14.CB
- 05.6395.AP.CB





Luminous flux luminaire
5399 lm

Beam Angle: - 82°

h(m)	E(lx)	D(m)
1	1530	1.43
2	383	2.86
3	170	4.28
4	96	5.71
5	61	7.14

Optic High Comfort - 3000K


Dali 2

- 05.5890.40.DA
- 05.5890.40.YU
- 05.5890.14.DA
- 05.5890.AP.DA

Casambi

- 05.5890.40.CB
- 05.5890.40.C6
- 05.5890.14.CB
- 05.5890.AP.CB





Luminous flux luminaire
5423 lm

Beam Angle: - 65°

h(m)	E(lx)	D(m)
1	2299	1.31
2	575	2.61
3	255	3.92
4	144	5.23
5	92	6.54

Optic Oval - 3500K


Dali 2

- 05.6396.40.DA
- 05.6396.40.YU
- 05.6396.14.DA
- 05.6396.AP.DA

Casambi

- 05.6396.40.CB
- 05.6396.40.C6
- 05.6396.14.CB
- 05.6396.AP.CB





Luminous flux luminaire
5484 lm

Beam Angle: - 82°

h(m)	E(lx)	D(m)
1	1548	1.43
2	387	2.86
3	172	4.28
4	97	5.71
5	62	7.14

Optic High Comfort - 3500K


Dali 2

- 05.5891.40.DA
- 05.5891.40.YU
- 05.5891.14.DA
- 05.5891.AP.DA

Casambi

- 05.5891.40.CB
- 05.5891.40.C6
- 05.5891.14.CB
- 05.5891.AP.CB





Luminous flux luminaire
5542 lm

Beam Angle: - 65°

h(m)	E(lx)	D(m)
1	2350	1.31
2	587	2.61
3	261	3.92
4	147	5.23
5	94	6.54

Optic Oval - 4000K


Dali 2

- 05.6397.40.DA
- 05.6397.40.YU
- 05.6397.14.DA
- 05.6397.AP.DA

Casambi

- 05.6397.40.CB
- 05.6397.40.C6
- 05.6397.14.CB
- 05.6397.AP.CB





Luminous flux luminaire
5739 lm

Beam Angle: - 82°

h(m)	E(lx)	D(m)
1	1678	1.43
2	419	2.86
3	186	4.28
4	105	5.71
5	67	7.14

Optic High Comfort - 4000K


Dali 2

- 05.5892.40.DA
- 05.5892.40.YU
- 05.5892.14.DA
- 05.5892.AP.DA

Casambi

- 05.5892.40.CB
- 05.5892.40.C6
- 05.5892.14.CB
- 05.5892.AP.CB





Luminous flux luminaire
5822 lm

Beam Angle: - 65°

h(m)	E(lx)	D(m)
1	2469	1.31
2	617	2.61
3	274	3.92
4	154	5.23
5	99	6.54


NEW

WORKMATES

Workmates Suspension Up&Down Tunable White Smart

Top LED High Efficiency: Casambi: Up 21,5W - Down 26W
Up: 3619 lm - 2700K-5700K/CRI90
Down: 4061 lm - 3000K/CRI 90 / 4090 lm - 3500K/CRI 90 / 4157 lm - 4000K/CRI 90







Suspension luminaire. *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency *Down* light source. *Tunable White* variable CCT *Up* light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Smart version with integrated presence detection and brightness sensors. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.


Luminaria de suspensión. Emisión *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz de *Down* de alta eficiencia. Fuente de luz *Up* de CCT variable *Tunable White*. Driver no incluido (Kit accesorio para driver remoto o de superficie). Altura de suspensión ajustable. Versión Smart con sensores de presencia y de luminosidad integrados. Disponible módulo de unión mecánico para líneas modulares de varias unidades. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K

Casambi

- 05.6400.40.CB
- 05.6400.40.C6
- 05.6400.14.CB
- 05.6400.AP.CB

74° WIDE FLOOD



Luminous flux luminaire 6426 lm

Beam Angle: - 74°


h(m)	E(lx)	D(m)
1	2249	1.49
2	562	2.99
3	250	4.48
4	141	5.97
5	90	7.46

Optic Wide Flood - 3500K

Casambi

- 05.6401.40.CB
- 05.6401.40.C6
- 05.6401.14.CB
- 05.6401.AP.CB

74° WIDE FLOOD



Luminous flux luminaire 6500 lm

Beam Angle: - 74°


h(m)	E(lx)	D(m)
1	2259	1.49
2	565	2.99
3	251	4.48
4	141	5.97
5	90	7.46

Optic Wide Flood - 4000K

Casambi

- 05.6402.40.CB
- 05.6402.40.C6
- 05.6402.14.CB
- 05.6402.AP.CB

74° WIDE FLOOD



Luminous flux luminaire 6740 lm

Beam Angle: - 74°


h(m)	E(lx)	D(m)
1	2382	1.49
2	596	2.99
3	265	4.48
4	149	5.97
5	95	7.46

Optic High Comfort - 3000K

Casambi

- 05.5900.40.CB
- 05.5900.40.C6
- 05.5900.14.CB
- 05.5900.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 6311 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	3152	1.31
2	788	2.61
3	350	3.92
4	197	5.23
5	126	6.54

Optic High Comfort - 3500K

Casambi

- 05.5901.40.CB
- 05.5901.40.C6
- 05.5901.14.CB
- 05.5901.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 6418 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	3205	1.31
2	801	2.61
3	356	3.92
4	200	5.23
5	128	6.54

Optic High Comfort - 4000K

Casambi

- 05.5902.40.CB
- 05.5902.40.C6
- 05.5902.14.CB
- 05.5902.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 6680 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	3336	1.31
2	834	2.61
3	371	3.92
4	208	5.23
5	133	6.54

Optic Oval - 3000K

Casambi

- 05.6405.40.CB
- 05.6405.40.C6
- 05.6405.14.CB
- 05.6405.AP.CB

81° OVAL



Luminous flux luminaire 6250 lm

Beam Angle: - 81°


h(m)	E(lx)	D(m)
1	2095	1.42
2	524	2.85
3	233	4.27
4	131	5.70
5	84	7.12

Optic Oval - 3500K

Casambi

- 05.6406.40.CB
- 05.6406.40.C6
- 05.6406.14.CB
- 05.6406.AP.CB

81° OVAL



Luminous flux luminaire 6324 lm

Beam Angle: - 81°


h(m)	E(lx)	D(m)
1	2105	1.42
2	526	2.85
3	234	4.27
4	132	5.70
5	84	7.12

Optic Oval - 4000K

Casambi

- 05.6407.40.CB
- 05.6407.40.C6
- 05.6407.14.CB
- 05.6407.AP.CB

81° OVAL



Luminous flux luminaire 6554 lm

Beam Angle: - 81°


h(m)	E(lx)	D(m)
1	2220	1.42
2	555	2.85
3	247	4.27
4	139	5.70
5	89	7.12

NEW

Workmates Suspension Up&Down Tunable White Smart

Top LED Full Spectrum: Casambi: Up 21,5W - Down 26W
Up: 3619 lm - 2700K-5700K/CRI90
Down: 2976 lm - 3000K/CRI 98 / 3005 lm - 3500K/CRI 98 / 3034 lm - 4000K/CRI 98







Suspension luminaire. *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering *Down Full Spectrum* light source. *Tunable White* variable CCT *Up* light source. Driver not included (accessory kit for remote or surface driver). Adjustable suspension height. Smart version with integrated presence detection and brightness sensors. Mechanical union module available for modular lines for various units. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant. Casambi, maximum distance between fixtures: 50m.


Luminaria de suspensión. Emisión *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down Full Spectrum* de alta calidad en la reproducción cromática. Fuente de luz *Up* de CCT variable *Tunable White*. Driver no incluido (Kit accesorio para driver remoto o de superficie). Altura de suspensión ajustable. Versión Smart con sensores de presencia y de luminosidad integrados. Disponible módulo de unión mecánico para líneas modulares de varias unidades.
UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. Casambi, distancia máxima entre luminarias: 50m.

Optic Wide Flood - 3000K

Casambi

- 05.6410.40.CB
- 05.6410.40.C6
- 05.6410.14.CB
- 05.6410.AP.CB

75° WIDE FLOOD



Luminous flux luminaire 5498 lm

Beam Angle: - 75°


h(m)	E(lx)	D(m)
1	1607	1.49
2	402	2.97
3	179	4.46
4	100	5.95
5	64	7.43

Optic Wide Flood - 3500K

Casambi

- 05.6411.40.CB
- 05.6411.40.C6
- 05.6411.14.CB
- 05.6411.AP.CB

75° WIDE FLOOD



Luminous flux luminaire 5583 lm

Beam Angle: - 75°


h(m)	E(lx)	D(m)
1	1624	1.49
2	406	2.97
3	180	4.46
4	102	5.95
5	65	7.43

Optic Wide Flood - 4000K

Casambi

- 05.6412.40.CB
- 05.6412.40.C6
- 05.6412.14.CB
- 05.6412.AP.CB

75° WIDE FLOOD



Luminous flux luminaire 5847 lm

Beam Angle: - 75°


h(m)	E(lx)	D(m)
1	1761	1.49
2	440	2.97
3	196	4.46
4	110	5.95
5	70	7.43

Optic High Comfort - 3000K

Casambi

- 05.5910.40.CB
- 05.5910.40.C6
- 05.5910.14.CB
- 05.5910.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 5423 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	2299	1.31
2	575	2.61
3	255	3.92
4	144	5.23
5	92	6.54

Optic High Comfort - 3500K

Casambi

- 05.5911.40.CB
- 05.5911.40.C6
- 05.5911.14.CB
- 05.5911.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 5542 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	2350	1.31
2	587	2.61
3	261	3.92
4	147	5.23
5	94	6.54

Optic High Comfort - 4000K

Casambi

- 05.5912.40.CB
- 05.5912.40.C6
- 05.5912.14.CB
- 05.5912.AP.CB

65° HIGH COMFORT



Luminous flux luminaire 5822 lm

Beam Angle: - 65°


h(m)	E(lx)	D(m)
1	2469	1.31
2	617	2.61
3	274	3.92
4	154	5.23
5	99	6.54

Optic Oval - 3000K

Casambi

- 05.6415.40.CB
- 05.6415.40.C6
- 05.6415.14.CB
- 05.6415.AP.CB

82° OVAL



Luminous flux luminaire 5399 lm

Beam Angle: - 82°


h(m)	E(lx)	D(m)
1	1530	1.43
2	383	2.86
3	170	4.28
4	96	5.71
5	61	7.14

Optic Oval - 3500K

Casambi

- 05.6416.40.CB
- 05.6416.40.C6
- 05.6416.14.CB
- 05.6416.AP.CB

82° OVAL



Luminous flux luminaire 5484 lm

Beam Angle: - 82°


h(m)	E(lx)	D(m)
1	1548	1.43
2	387	2.86
3	172	4.28
4	97	5.71
5	62	7.14

Optic Oval - 4000K

Casambi

- 05.6417.40.CB
- 05.6417.40.C6
- 05.6417.14.CB
- 05.6417.AP.CB

82° OVAL



Luminous flux luminaire 5739 lm

Beam Angle: - 82°


h(m)	E(lx)	D(m)
1	1678	1.43
2	419	2.86
3	186	4.28
4	105	5.71
5	67	7.14


Accessories / Accesorios

Remote Power Supply Kit / Kit de fuente de alimentación en remoto

Accessory kit for remote driver.
Driver Included.

Kit accesorio para driver remoto.
Driver incluido.





Down
Non Dimming
08.0900.40
08.0900.14
08.0900.AP

Up&Down (Up / Down)
Non Dimming*
08.0901.40
08.0901.14
08.0901.AP

Up&Down Tunable White
Dali 2
08.0905.40
08.0905.14
08.0905.AP

Dali 2
08.0903.40
08.0903.14
08.0903.AP


Dali 2
08.0904.40
08.0904.14
08.0904.AP

All Models
Casambi
08.0906.40
08.0906.14
08.0906.AP

Surface Power Supply Kit / Kit de fuente de alimentación en superficie

Accessory kit for surface driver.
Driver Included.

Kit de accesorios para driver en superficie. Driver incluido.



Down
Non Dimming
08.0910.40
08.0910.14
08.0910.AP

Up&Down (Up / Down)
Non Dimming*
08.0911.40
08.0911.14
08.0911.AP

Up&Down Tunable White
Dali 2
08.0915.40
08.0915.14
08.0915.AP

Dali 2
08.0913.40
08.0913.14
08.0913.AP


Dali 2
08.0914.40
08.0914.14
08.0914.AP

All Models
Casambi
08.0915.40
08.0915.14
08.0915.AP

Recessed Power Supply Kit / Kit de fuente de alimentación empotrable

Accessory kit for recessed driver.
Driver Included.

Kit de accesorios para driver empotrable. Driver incluido.





Down
Non Dimming
08.0920.40
08.0920.14
08.0920.AP

Up&Down (Up / Down)
Non Dimming*
08.0921.40
08.0921.14
08.0921.AP

Up&Down Tunable White
Dali 2
08.0925.40
08.0925.14
08.0925.AP

Dali 2
08.0923.40
08.0923.14
08.0923.AP

Dali 2
08.0924.40
08.0924.14
08.0924.AP

All Models
Casambi
08.0925.40
08.0925.14
08.0925.AP

Remote

White Black Anodized Silver



Surface

White Black Anodized Silver



Recessed

White Black Anodized Silver



* This accessory allows you to adjust two flow ratios (Up / Down: 70/30 or 40/60) depending on how the controller is connected. Please consult the instructions for further details.
Este accesorio le permite ajustar dos proporciones de flujo (Arriba / Abajo: 70/30 o 40/60) dependiendo de cómo se conecte el controlador. Por favor, consulta las instrucciones para más detalles.

NEW

Suspension · Interconnection Accessories / Accesorios de interconexión


The Workmates suspension versions come with a mechanical union accessory for the installation of various units in continuous lines.

Las versiones de suspensión de Workmates disponen de un accesorio de unión mecánico para implementar varias unidades en líneas continuas.

Mechanical profile for Workmates Suspension. Connection joints included.


Perfil mecánico para Workmates Suspension. Uniones de interconexión incluidas.





06.0436.40
06.0436.14
06.0436.AP

Interconnection Example / Ejemplo de interconexión




Interconnection Detail / Detalle de interconexión



Workmates Floor Single

Top LED High Efficiency 65,4W - 11359 lm - 3000K/CRI 90 / 11474 lm - 3500K/CRI 90 / 11957 lm - 4000K/CRI 90
Up: High Efficiency
Down: High Efficiency







Freestanding luminaire. Simple *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency, perfectly homogeneous asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. High-efficiency *Up* light source. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA. *Casambi* wireless control and integrated manual *Touch Dimming* capacitive keypad. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base is not included and must be ordered separately. See end of chapter.

Luminaria de pie. Emisión simple *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica de alta eficiencia y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de alta eficiencia. Driver y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA. Control inalámbrico *Casambi* y por botonera capacitiva *Touch Dimming* manual integrada. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. La base no está incluida y debe solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K


Touch Dimming

- 05.6500.40
- 05.6500.40.78
- 05.6500.14

Casambi

- 05.6500.40.CB
- 05.6500.40.C6
- 05.6500.14.CB





Luminous flux luminaire
9445 lm

Beam Angle: - 76°

h(m)	E(lx)	D(m)
1	2101	1.46
2	525	2.93
3	233	4.39
4	131	5.86
5	84	7.32

Optic Asymmetrical - 3500K


Touch Dimming

- 05.6501.40
- 05.6501.40.78
- 05.6501.14

Casambi

- 05.6501.40.CB
- 05.6501.40.C6
- 05.6501.14.CB





Luminous flux luminaire
9517 lm

Beam Angle: - 76°

h(m)	E(lx)	D(m)
1	2107	1.46
2	527	2.93
3	234	4.39
4	132	5.86
5	84	7.32

Optic Asymmetrical - 4000K


Touch Dimming

- 05.6502.40
- 05.6502.40.78
- 05.6502.14

Casambi

- 05.6502.40.CB
- 05.6502.40.C6
- 05.6502.14.CB





Luminous flux luminaire
9956 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	2190	1.46
2	548	2.93
3	243	4.39
4	137	5.86
5	88	7.32

NEW

Workmates Floor Single

Top LED Full Spectrum 65,4W - 10161 lm - 3000K/CRI 98 / 10264 lm - 3500K/CRI 98 / 10718 lm - 4000K/CRI 98
Up: High Efficiency
Down: Full Spectrum





1-100 | GWT 850° | 5,0 Kg | CE | F | III | LED INCL | IP 20

Freestanding luminaire. Simple *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering, perfectly homogeneous *Full Spectrum* asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. High-efficiency *Up* light source. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA. *Casambi* wireless control and integrated manual *Touch Dimming* capacitive keypad. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base is not included and must be ordered separately. See end of chapter.

Luminaria de pie. Emisión simple *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica *Full Spectrum* de alta calidad en la reproducción cromática y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de alta eficiencia. Driver y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA. Control inalámbrico *Casambi* y por botonera capacitiva *Touch Dimming* manual integrada. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. La base no está incluida y debe solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K


Touch Dimming

- 05.6505.40
- 05.6505.40.78
- 05.6505.14

Casambi

- 05.6505.40.CB
- 05.6505.40.C6
- 05.6505.14.CB

78° ASYMM.



Luminous flux luminaire 8530 lm

Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	1558	4.75
2	390	9.50
3	173	14.26
4	97	19.01
5	62	23.76

Optic Asymmetrical - 3500K


Touch Dimming

- 05.6506.40
- 05.6506.40.78
- 05.6506.14

Casambi

- 05.6506.40.CB
- 05.6506.40.C6
- 05.6506.14.CB

78° ASYMM.



Luminous flux luminaire 8616 lm

Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	1574	4.75
2	394	9.50
3	175	14.26
4	98	19.01
5	63	23.76

Optic Asymmetrical - 4000K


Touch Dimming

- 05.6507.40
- 05.6507.40.78
- 05.6507.14

Casambi

- 05.6507.40.CB
- 05.6507.40.C6
- 05.6507.14.CB

78° ASYMM.



Luminous flux luminaire 9042 lm


Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	1652	4.75
2	413	9.50
3	184	14.26
4	103	19.01
5	66	23.76

Workmates Floor Single Smart

Top LED High Efficiency 65,4W - 11359 lm - 3000K/CRI 90 / 11474 lm - 3500K/CRI 90 / 11957 lm - 4000K/CRI 90
Up: High Efficiency
Down: High Efficiency







Freestanding luminaire. Simple *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency, perfectly homogeneous asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. High-efficiency *Up* light source. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA. Smart version with integrated presence detection and brightness sensors. *Casambi* wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base is not included and must be ordered separately. See end of chapter.


Luminaria de pie. Emisión simple *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica de alta eficiencia y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de alta eficiencia. Driver y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA. Versión Smart con sensores de presencia y de luminosidad integrados. Control inalámbrico *Casambi*. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base no está incluida y debe solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K

Casambi

- 05.6510.40.CB
- 05.6510.40.C6
- 05.6510.14.CB





Luminous flux luminaire
9445 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	2101	1.46
2	525	2.93
3	233	4.39
4	131	5.86
5	84	7.32

Optic Asymmetrical - 3500K

Casambi

- 05.6511.40.CB
- 05.6511.40.C6
- 05.6511.14.CB





Luminous flux luminaire
9517 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	2107	1.46
2	527	2.93
3	234	4.39
4	132	5.86
5	84	7.32

Optic Asymmetrical - 4000K

Casambi

- 05.6512.40.CB
- 05.6512.40.C6
- 05.6512.14.CB





Luminous flux luminaire
9956 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	2190	1.46
2	548	2.93
3	243	4.39
4	137	5.86
5	88	7.32

NEW

Workmates Floor Single Smart

Top LED Full Spectrum 65,4W - 10161 lm - 3000K/CRI 98 / 10264 lm - 3500K/CRI 98 / 10718 lm - 4000K/CRI 98
Up: High Efficiency
Down: Full Spectrum







Freestanding luminaire. Simple *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering, perfectly homogeneous *Full Spectrum* asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. High-efficiency *Up* light source. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA.
Smart version with integrated presence detection and brightness sensors. *Casambi* wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base is not included and must be ordered separately. See end of chapter.


Luminaria de pie. Emisión simple *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica *Full Spectrum* de alta calidad en la reproducción cromática y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de alta eficiencia. Driver y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA.
Versión Smart con sensores de presencia y de luminosidad integrados. Control inalámbrico *Casambi*. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base no está incluida y debe solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K

Casambi

- 05.6515.40.CB
- 05.6515.40.C6
- 05.6515.14.CB





Luminous flux luminaire
8530 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	1558	4.75
2	390	9.50
3	173	14.26
4	97	19.01
5	62	23.76

Optic Asymmetrical - 3500K

Casambi

- 05.6516.40.CB
- 05.6516.40.C6
- 05.6516.14.CB





Luminous flux luminaire
8616 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	1574	4.75
2	394	9.50
3	175	14.26
4	98	19.01
5	63	23.76

Optic Asymmetrical - 4000K

Casambi

- 05.6517.40.CB
- 05.6517.40.C6
- 05.6517.14.CB





Luminous flux luminaire
9042 lm


Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	1652	4.75
2	413	9.50
3	184	14.26
4	103	19.01
5	66	23.76

Workmates Floor Single Tunable White

Top LED High Efficiency 57,7W - 9127 lm - 3000K/CRI 90 / 9219 lm - 3500K/CRI 90 / 9594 lm - 4000K/CRI 90
Up: High Efficiency - 2700K-5700K/CRI90
Down: High Efficiency







Freestanding luminaire. Simple *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency, perfectly homogeneous asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. *Tunable White* variable CCT *Up* light source. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA. *Casambi* wireless control and integrated manual *Touch Dimming* capacitive keypad. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base is not included and must be ordered separately. See end of chapter.

Luminaria de pie. Emisión simple *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica de alta eficiencia y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de CCT variable *Tunable White*. Driver y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA. Control inalámbrico *Casambi* y por botonera capacitiva *Touch Dimming* manual integrada. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. La base no está incluida y debe solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K


Touch Dimming

- ☐ 05.6520.40
- ◪ 05.6520.40.78
- ■ 05.6520.14

Casambi

- ☐ 05.6520.40.CB
- ◪ 05.6520.40.C6
- ■ 05.6520.14.CB





Luminous flux luminaire
7502 lm

Beam Angle: - 76°

h(m)	E(lx)	D(m)
1	2101	1.46
2	525	2.93
3	233	4.39
4	131	5.86
5	84	7.32

Optic Asymmetrical - 3500K


Touch Dimming

- ☐ 05.6521.40
- ◪ 05.6521.40.78
- ■ 05.6521.14

Casambi

- ☐ 05.6521.40.CB
- ◪ 05.6521.40.C6
- ■ 05.6521.14.CB





Luminous flux luminaire
7554 lm

Beam Angle: - 76°

h(m)	E(lx)	D(m)
1	2107	1.46
2	527	2.93
3	234	4.39
4	132	5.86
5	84	7.32

Optic Asymmetrical - 4000K


Touch Dimming

- ☐ 05.6522.40
- ◪ 05.6522.40.78
- ■ 05.6522.14

Casambi

- ☐ 05.6522.40.CB
- ◪ 05.6522.40.C6
- ■ 05.6522.14.CB





Luminous flux luminaire
7853 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	2190	1.46
2	548	2.93
3	243	4.39
4	137	5.86
5	88	7.32

NEW

Workmates Floor Single Tunable White

Top LED Full Spectrum 57,7W - 7929 lm - 3000K/CRI 98 / 8008 lm - 3500K/CRI 98 / 8355 lm - 4000K/CRI 98
Up: High Efficiency - 2700K-5700K/CRI90
Down: Full Spectrum





1-100

5,0 Kg

GWT 850°

LED INCL

IP 20

Freestanding luminaire. Simple *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering, perfectly homogeneous *Full Spectrum* asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. *Tunable White* variable CCT *Up* light source. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA.
Casambi wireless control and integrated manual *Touch Dimming* capacitive keypad. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base is not included and must be ordered separately. See end of chapter.

Luminaria de pie. Emisión simple *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica *Full Spectrum* de alta calidad en la reproducción cromática y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de CCT variable *Tunable White*. Driver y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA. Control inalámbrico *Casambi* y por botonera capacitiva *Touch Dimming* manual integrada. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. La base no está incluida y debe solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K


Touch Dimming

- 05.6525.40
- 05.6525.40.78
- 05.6525.14

Casambi

- 05.6525.40.CB
- 05.6525.40.C6
- 05.6525.14.CB

76° ASYMM.



Luminous flux luminaire
6587 lm

Beam Angle: - 76°

h(m)	E(lx)	D(m)
1	1496	1.46
2	374	2.93
3	166	4.39
4	94	5.86
5	60	7.32

Optic Asymmetrical - 3500K


Touch Dimming

- 05.6526.40
- 05.6526.40.78
- 05.6526.14

Casambi

- 05.6526.40.CB
- 05.6526.40.C6
- 05.6526.14.CB

76° ASYMM.



Luminous flux luminaire
6653 lm

Beam Angle: - 76°

h(m)	E(lx)	D(m)
1	1511	1.46
2	378	2.93
3	168	4.39
4	94	5.86
5	60	7.32

Optic Asymmetrical - 4000K


Touch Dimming

- 05.6527.40
- 05.6527.40.78
- 05.6527.14

Casambi

- 05.6527.40.CB
- 05.6527.40.C6
- 05.6527.14.CB

76° ASYMM.



Luminous flux luminaire
6939 lm


Beam Angle: - 76°

h(m)	E(lx)	D(m)
1	1586	1.46
2	396	2.93
3	176	4.39
4	99	5.86
5	63	7.32

Workmates Floor Single Tunable White Smart

Top LED High Efficiency 57,7W - 9127 lm - 3000K/CRI 90 / 9219 lm - 3500K/CRI 90 / 9594 lm - 4000K/CRI 90
Up: High Efficiency - 2700K-5700K/CRI90
Down: High Efficiency







Freestanding luminaire. Simple *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency, perfectly homogeneous asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. *Tunable White* variable CCT *Up* light source. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA. Smart version with integrated presence detection and brightness sensors. *Casambi* wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base is not included and must be ordered separately. See end of chapter.


Luminaria de pie. Emisión simple *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica de alta eficiencia y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de CCT variable *Tunable White*. Driver y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA. Versión Smart con sensores de presencia y de luminosidad integrados. Control inalámbrico *Casambi*. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. La base no está incluida y debe solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K

Casambi

- 05.6530.40.CB
- 05.6530.40.C6
- 05.6530.14.CB





Luminous flux luminaire
7502 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	2101	1.46
2	525	2.93
3	233	4.39
4	131	5.86
5	84	7.32

Optic Asymmetrical - 3500K

Casambi

- 05.6531.40.CB
- 05.6531.40.C6
- 05.6531.14.CB





Luminous flux luminaire
7554 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	2107	1.46
2	527	2.93
3	234	4.39
4	132	5.86
5	84	7.32

Optic Asymmetrical - 4000K

Casambi

- 05.6532.40.CB
- 05.6532.40.C6
- 05.6532.14.CB





Luminous flux luminaire
7853 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	2190	1.46
2	548	2.93
3	243	4.39
4	137	5.86
5	88	7.32

NEW

Workmates Floor Single Tunable White Smart

Top LED Full Spectrum 57,7W - 7929 lm - 3000K/CRI 98 / 8008 lm - 3500K/CRI 98 / 8355 lm - 4000K/CRI 98
Up: High Efficiency - 2700K-5700K/CRI90
Down: Full Spectrum





1-100

5,0 Kg

GWT 850°

LED INCL

IP 20

Freestanding luminaire. Simple *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering, perfectly homogeneous *Full Spectrum* asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. *Tunable White* variable CCT *Up* light source. Driver and plug included. Supplied with 3 plug types: EU, UK, and USA.
Smart version with integrated presence detection and brightness sensors. *Casambi* wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base is not included and must be ordered separately. See end of chapter.


Luminaria de pie. Emisión simple *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica *Full Spectrum* de alta calidad en la reproducción cromática y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de CCT variable *Tunable White*. Driver y enchufe incluidos. Se suministran 3 tipos de enchufe: UE, UK y USA.
Versión Smart con sensores de presencia y de luminosidad integrados. Control inalámbrico *Casambi*. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base no está incluida y debe solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K

Casambi

- 05.6535.40.CB
- 05.6535.40.C6
- 05.6535.14.CB

76° ASYMM.



Luminous flux luminaire 6587 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	1496	1.46
2	374	2.93
3	166	4.39
4	94	5.86
5	60	7.32

Optic Asymmetrical - 3500K

Casambi

- 05.6536.40.CB
- 05.6536.40.C6
- 05.6536.14.CB

76° ASYMM.



Luminous flux luminaire 6653 lm

Beam Angle: - 76°


h(m)	E(lx)	D(m)
1	1511	1.46
2	378	2.93
3	168	4.39
4	94	5.86
5	60	7.32

Optic Asymmetrical - 4000K

Casambi

- 05.6537.40.CB
- 05.6537.40.C6
- 05.6537.14.CB

76° ASYMM.



Luminous flux luminaire 6939 lm


Beam Angle: - 76°

h(m)	E(lx)	D(m)
1	1586	1.46
2	396	2.93
3	176	4.39
4	99	5.86
5	63	7.32

Workmates Floor Double

Top LED High Efficiency 112W - 22718 lm - 3000K/CRI 90 / 22948 lm - 3500K/CRI 90 / 23914 lm - 4000K/CRI 90
Up: High Efficiency
Down: High Efficiency





1-100 | 6,7 Kg | GWT 850° | CE | F | III | LED INCL | IP 20

Freestanding luminaire. Double *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency, perfectly homogeneous asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. High-efficiency *Up* light source. *Casambi* wireless control and integrated manual *Touch Dimming* capacitive keypad. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base and power supply are not included and must be ordered separately. See end of chapter.

Luminaria de pie. Emisión doble *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica de alta eficiencia y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de alta eficiencia. Control inalámbrico *Casambi* y por botonera capacitiva *Touch Dimming* manual integrada. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base y la fuente de alimentación no están incluidas y deben solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K


Touch Dimming

- 05.6700.40
- 05.6700.40.78
- 05.6700.14

Casambi

- 05.6700.40.CB
- 05.6700.40.C6
- 05.6700.14.CB

78° ASYMM.



Luminous flux luminaire
18893 lm

Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	3117	4.75
2	779	9.50
3	346	14.26
4	195	19.01
5	125	23.76

Optic Asymmetrical - 3500K


Touch Dimming

- 05.6701.40
- 05.6701.40.78
- 05.6701.14

Casambi

- 05.6701.40.CB
- 05.6701.40.C6
- 05.6701.14.CB

78° ASYMM.



Luminous flux luminaire
19036 lm

Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	3148	4.75
2	787	9.50
3	350	14.26
4	197	19.01
5	126	23.76

Optic Asymmetrical - 4000K


Touch Dimming

- 05.6702.40
- 05.6702.40.78
- 05.6702.14

Casambi

- 05.6702.40.CB
- 05.6702.40.C6
- 05.6702.14.CB

78° ASYMM.



Luminous flux luminaire
19163 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	3117	4.75
2	779	9.50
3	346	14.26
4	195	19.01
5	125	23.76

NEW

Workmates Floor Double

Top LED Full Spectrum 112W - 20322 lm - 3000K/CRI 98 / 20528 lm - 3500K/CRI 98 / 21436 lm - 4000K/CRI 98
Up: High Efficiency
Down: Full Spectrum





1-100

6,7 Kg

GWT 850°

CE

F

III

LED INCL

IP 20

Freestanding luminaire. Double *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering, perfectly homogeneous *Full Spectrum* asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. High-efficiency *Up* light source. *Casambi* wireless control and integrated manual *Touch Dimming* capacitive keypad. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base and power supply are not included and must be ordered separately. See end of chapter.

Luminaria de pie. Emisión doble *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica *Full Spectrum* de alta calidad en la reproducción cromática y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de alta eficiencia. Control inalámbrico *Casambi* y por botonera capacitiva *Touch Dimming* manual integrada. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base y la fuente de alimentación no están incluidas y deben solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K


Touch Dimming

- 05.6705.40
- 05.6705.40.78
- 05.6705.14

Casambi

- 05.6705.40.CB
- 05.6705.40.C6
- 05.6705.14.CB

78° ASYMM.



Luminous flux luminaire
13176 lm

Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	2151	4.75
2	538	9.50
3	239	14.26
4	134	19.01
5	86	23.76

Optic Asymmetrical - 3500K


Touch Dimming

- 05.6706.40
- 05.6706.40.78
- 05.6706.14

Casambi

- 05.6706.40.CB
- 05.6706.40.C6
- 05.6706.14.CB

78° ASYMM.



Luminous flux luminaire
17233 lm

Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	3148	4.75
2	787	9.50
3	350	14.26
4	197	19.01
5	126	23.76

Optic Asymmetrical - 4000K


Touch Dimming

- 05.6707.40
- 05.6707.40.78
- 05.6707.14

Casambi

- 05.6707.40.CB
- 05.6707.40.C6
- 05.6707.14.CB

78° ASYMM.



Luminous flux luminaire
18086 lm


Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	3304	4.75
2	826	9.50
3	367	14.26
4	206	19.01
5	132	23.76

Workmates Floor Double Smart

Top LED High Efficiency 112W - 22718 lm - 3000K/CRI 90 / 22948 lm - 3500K/CRI 90 / 23914 lm - 4000K/CRI 90
Up: High Efficiency
Down: High Efficiency







Freestanding luminaire. Double *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency, perfectly homogeneous asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. High-efficiency *Up* light source. Smart version with integrated presence detection and brightness sensors. *Casambi* wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base and power supply are not included and must be ordered separately. See end of chapter.


Luminaria de pie. Emisión doble *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica de alta eficiencia y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de alta eficiencia. Versión Smart con sensores de presencia y de luminosidad integrados. Control inalámbrico *Casambi*. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base y la fuente de alimentación no están incluidas y deben solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K

Casambi

- 05.6710.40.CB
- 05.6710.40.C6
- 05.6710.14.CB





Luminous flux luminaire
18893 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	3117	4.75
2	779	9.50
3	346	14.26
4	195	19.01
5	125	23.76

Optic Asymmetrical - 3500K

Casambi

- 05.6711.40.CB
- 05.6711.40.C6
- 05.6711.14.CB





Luminous flux luminaire
19036 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	3148	4.75
2	787	9.50
3	350	14.26
4	197	19.01
5	126	23.76

Optic Asymmetrical - 4000K

Casambi

- 05.6712.40.CB
- 05.6712.40.C6
- 05.6712.14.CB





Luminous flux luminaire
19163 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	3117	4.75
2	779	9.50
3	346	14.26
4	195	19.01
5	125	23.76

NEW

Workmates Floor Double Smart

Top LED Full Spectrum 112W - 20322 lm - 3000K/CRI 98 / 20528 lm - 3500K/CRI 98 / 21436 lm - 4000K/CRI 98
Up: High Efficiency
Down: Full Spectrum







Freestanding luminaire. Double *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering, perfectly homogeneous *Full Spectrum* asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. High-efficiency *Up* light source.
Smart version with integrated presence detection and brightness sensors. *Casambi* wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base and power supply are not included and must be ordered separately. See end of chapter.


Luminaria de pie. Emisión doble *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica *Full Spectrum* de alta calidad en la reproducción cromática y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de alta eficiencia. Versión Smart con sensores de presencia y de luminosidad integrados. Control inalámbrico *Casambi*. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000. La base y la fuente de alimentación no están incluidas y deben solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K

Casambi

- 05.6715.40.CB
- 05.6715.40.C6
- 05.6715.14.CB





Luminous flux luminaire
13176 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	2151	4.75
2	538	9.50
3	239	14.26
4	134	19.01
5	86	23.76

Optic Asymmetrical - 3500K

Casambi

- 05.6716.40.CB
- 05.6716.40.C6
- 05.6716.14.CB





Luminous flux luminaire
17233 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	3148	4.75
2	787	9.50
3	350	14.26
4	197	19.01
5	126	23.76

Optic Asymmetrical - 4000K

Casambi

- 05.6717.40.CB
- 05.6717.40.C6
- 05.6717.14.CB





Luminous flux luminaire
18086 lm


Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	3304	4.75
2	826	9.50
3	367	14.26
4	206	19.01
5	132	23.76

Workmates Floor Double Tunable White

Top LED High Efficiency 96W - 18254 lm - 3000K/CRI 90 / 18438 lm - 3500K/CRI 90 / 19188 lm - 4000K/CRI 90
Up: High Efficiency - 2700K-5700K/CRI90
Down: High Efficiency







Freestanding luminaire. Double *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency, perfectly homogeneous asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. *Tunable White* variable CCT *Up* light source. *Casambi* wireless control and integrated manual *Touch Dimming* capacitive keypad. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base and power supply are not included and must be ordered separately. See end of chapter.

Luminaria de pie. Emisión doble *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica de alta eficiencia y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de CCT variable *Tunable White*. Control inalámbrico *Casambi* y por botonera capacitiva *Touch Dimming* manual integrada. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base y la fuente de alimentación no están incluidas y deben solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K


Touch Dimming

- ☐ 05.6720.40
- ◪ 05.6720.40.78
- ■ 05.6720.14

Casambi

- ☐ 05.6720.40.CB
- ◪ 05.6720.40.C6
- ■ 05.6720.14.CB





Luminous flux luminaire
15006 lm

Beam Angle: - 95°

h(m)	E(lx)	D(m)
1	3182	1.53
2	795	3.05
3	354	4.58
4	199	6.11
5	127	7.64

Optic Asymmetrical - 3500K


Touch Dimming

- ☐ 05.6721.40
- ◪ 05.6721.40.78
- ■ 05.6721.14

Casambi

- ☐ 05.6721.40.CB
- ◪ 05.6721.40.C6
- ■ 05.6721.14.CB





Luminous flux luminaire
15110 lm

Beam Angle: - 95°

h(m)	E(lx)	D(m)
1	3191	1.53
2	798	3.05
3	355	4.58
4	199	6.11
5	128	7.64

Optic Asymmetrical - 4000K


Touch Dimming

- ☐ 05.6722.40
- ◪ 05.6722.40.78
- ■ 05.6722.14

Casambi

- ☐ 05.6722.40.CB
- ◪ 05.6722.40.C6
- ■ 05.6722.14.CB





Luminous flux luminaire
15708 lm

Beam Angle: - 95°


h(m)	E(lx)	D(m)
1	3317	1.53
2	829	3.05
3	369	4.58
4	207	6.11
5	133	7.64

NEW

Workmates Floor Double Tunable White

Top LED Full Spectrum 96W - 15858 lm - 3000K/CRI 98 / 16016 lm - 3500K/CRI 98 / 16710 lm - 4000K/CRI 98
Up: High Efficiency - 2700K-5700K/CRI90
Down: Full Spectrum





1-100

6,7 Kg

GWT 850°

LED INCL

IP 20

Freestanding luminaire. Double *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering, perfectly homogeneous *Full Spectrum* asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. *Tunable White* variable CCT *Up* light source. *Casambi* wireless control and integrated manual *Touch Dimming* capacitive keypad. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base and power supply are not included and must be ordered separately. See end of chapter.

Luminaria de pie. Emisión doble *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica *Full Spectrum* de alta calidad en la reproducción cromática y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de CCT variable *Tunable White*.
Control inalámbrico *Casambi* y por botonera capacitiva *Touch Dimming* manual integrada. UGR<19. Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base y la fuente de alimentación no están incluidas y deben solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K


Touch Dimming

- 05.6725.40
- 05.6725.40.78
- 05.6725.14

Casambi

- 05.6725.40.CB
- 05.6725.40.C6
- 05.6725.14.CB

78° ASYMM.



Luminous flux luminaire
13176 lm

Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	2151	4.75
2	538	9.50
3	239	14.26
4	134	19.01
5	86	23.76

Optic Asymmetrical - 3500K


Touch Dimming

- 05.6726.40
- 05.6726.40.78
- 05.6726.14

Casambi

- 05.6726.40.CB
- 05.6726.40.C6
- 05.6726.14.CB

78° ASYMM.



Luminous flux luminaire
13307 lm

Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	2172	4.75
2	543	9.50
3	241	14.26
4	136	19.01
5	87	23.76

Optic Asymmetrical - 4000K


Touch Dimming

- 05.6727.40
- 05.6727.40.78
- 05.6727.14

Casambi

- 05.6727.40.CB
- 05.6727.40.C6
- 05.6727.14.CB

78° ASYMM.



Luminous flux luminaire
13880 lm


Beam Angle: - 78°

h(m)	E(lx)	D(m)
1	2258	4.75
2	565	9.50
3	251	14.26
4	141	19.01
5	90	23.76

Workmates Floor Double Tunable White Smart

Top LED High Efficiency 96W - 18254 lm - 3000K/CRI 90 / 18438 lm - 3500K/CRI 90 / 19188 lm - 4000K/CRI 90
Up: High Efficiency - 2700K-5700K/CRI90
Down: High Efficiency







Freestanding luminaire. Double *Up&Down* emission, with greater light flux amounts in the upper part. High-efficiency, perfectly homogeneous asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. *Tunable White* variable CCT *Up* light source. Smart version with integrated presence detection and brightness sensors. *Casambi* wireless control. UGR<19.
EN12464 - cd/m² @ 65º<3000 compliant.
The base and power supply are not included and must be ordered separately. See end of chapter.


Luminaria de pie. Emisión doble *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica de alta eficiencia y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de CCT variable *Tunable White*. Versión Smart con sensores de presencia y de luminosidad integrados. Control inalámbrico *Casambi*. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base y la fuente de alimentación no están incluidas y deben solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K

Casambi

- 05.6730.40.CB
- 05.6730.40.C6
- 05.6730.14.CB





Luminous flux luminaire
15006 lm

Beam Angle: - 95°


h(m)	E(lx)	D(m)
1	3182	1.53
2	795	3.05
3	354	4.58
4	199	6.11
5	127	7.64

Optic Asymmetrical - 3500K

Casambi

- 05.6731.40.CB
- 05.6731.40.C6
- 05.6731.14.CB





Luminous flux luminaire
15110 lm

Beam Angle: - 95°


h(m)	E(lx)	D(m)
1	3191	1.53
2	798	3.05
3	355	4.58
4	199	6.11
5	128	7.64

Optic Asymmetrical - 4000K

Casambi

- 05.6732.40.CB
- 05.6732.40.C6
- 05.6732.14.CB





Luminous flux luminaire
15708 lm

Beam Angle: - 95°


h(m)	E(lx)	D(m)
1	3317	1.53
2	829	3.05
3	369	4.58
4	207	6.11
5	133	7.64

NEW

Workmates Floor Double Tunable White Smart

Top LED Full Spectrum 96W - 15858 lm - 3000K/CRI 98 / 16016 lm - 3500K/CRI 98 / 16710 lm - 4000K/CRI 98
Up: High Efficiency - 2700K-5700K/CRI90
Down: Full Spectrum





1-100 | GWT 850° | 6,7 Kg | CE | F | III | LED INCL | IP 20

Freestanding luminaire. Double *Up&Down* emission, with greater light flux amounts in the upper part. High-quality colour rendering, perfectly homogeneous *Full Spectrum* asymmetric *Down* light source on the functional plane at distances of *Up* to 2 meters. *Tunable White* variable CCT *Up* light source. Smart version with integrated presence detection and brightness sensors. *Casambi* wireless control. UGR<19. EN12464 - cd/m² @ 65º<3000 compliant.
The base and power supply are not included and must be ordered separately. See end of chapter.


Luminaria de pie. Emisión doble *Up&Down*, con mayor cantidad de flujo lumínico en la parte superior. Fuente de luz *Down* asimétrica *Full Spectrum* de alta calidad en la reproducción cromática y homogeneidad perfecta en el plano funcional desplazado hasta 2 metros. Fuente de luz *Up* de CCT variable *Tunable White*.
Versión Smart con sensores de presencia y de luminosidad integrados. Control inalámbrico *Casambi*. UGR<19.
Conforme a la norma EN12464 - cd/m² @ 65º<3000.
La base y la fuente de alimentación no están incluidas y deben solicitarse por separado. Consulte al final del capítulo.

Optic Asymmetrical - 3000K

Casambi

- 05.6735.40.CB
- 05.6735.40.C6
- 05.6735.14.CB

78° ASYMM.



Luminous flux luminaire
13176 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	2151	4.75
2	538	9.50
3	239	14.26
4	134	19.01
5	86	23.76

Optic Asymmetrical - 3500K

Casambi

- 05.6736.40.CB
- 05.6736.40.C6
- 05.6736.14.CB

78° ASYMM.



Luminous flux luminaire
13307 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	2172	4.75
2	543	9.50
3	241	14.26
4	136	19.01
5	87	23.76

Optic Asymmetrical - 4000K

Casambi

- 05.6737.40.CB
- 05.6737.40.C6
- 05.6737.14.CB

78° ASYMM.



Luminous flux luminaire
13880 lm

Beam Angle: - 78°


h(m)	E(lx)	D(m)
1	2258	4.75
2	565	9.50
3	251	14.26
4	141	19.01
5	90	23.76

Accessories / Accesorios

Workmates Floor Single

Solid Base Plate.


Placa Base Sólida.



□ 08.1040.40
■ 08.1040.14

Open Base Plate.

Placa Base Abierta.




□ 08.1041.40
■ 08.1041.14

Workmates Floor Double

Solid Base Plate.


Placa Base Sólida.



□ 08.1060.40
■ 08.1060.14

Open Base Plate.


Placa Base Abierta.



□ 08.1061.40
■ 08.1061.14

Power Supply Kit.
Driver and plug included.
(European Plug 2 poles).


Kit de Alimentación.
Driver y enchufe incluidos.
(Enchufe europeo de 2 polos)



150W - 220/240V
□ 06.0500.40
■ 06.0500.14


Workmates Floor Single

□ White ■ Black



Workmates Floor Double

□ White ■ Black



Power Supply Kit

□ White ■ Black




NEW


Adjustable base height depending on screw insertion depth.

Altura de base ajustable según la profundidad de inserción del tornillo.

1



2




Min: 7 mm - Max: 20 mm

NEW

LIGHT SHADOW MINI

DESIGNED BY FLOS ARCHITECTURAL



NEW

Description
Light Shadow Mini is a family of indoor luminaires in a compact format.
Thanks to its main features —ultra-small dimensions, high performance, and excellent shielding— it integrates discreetly and elegantly into any space.
It incorporates a high-efficiency FLOS LED module with advanced technology, custom-designed optics, and a patented inverted-curvature cone system, ensuring:
- Optimal performance.
- Color accuracy.
- Uniform distribution without losses.
- Reduced glare.
- Enhanced visual comfort.

Available versions
- 1 spot fix (Trim / No Trim).
- 2 / 4 spot fix / adjustable (Trim / No Trim).
- Round Fix (Trim).
The family offers Spot, Medium, and Flood optics, enabling accent, intermediate, and general lighting solutions.

Finishes
For more decorative applications, Light Shadow Mini includes a range of finishes to customize the luminaire according to the space:
- Exteriors: white and black.
- Interiors: white, steel, bronze and black (high optical comfort).

Power units
On/Off, DALI dimmable, Mains Dim, and Casambi versions available depending on the driver (to be ordered separately).

Accessories
For the No Trim version, a pre-installation frame is required for false ceilings (purchased separately). Not necessary in the Trim version.

Additional information
- UGR < 10.
- Protection rating IP55.
- Insulation class III.

Compliance and Quality Marks
Luminaire compliant with European Technical Standard EN60598-1 and related parts.

Before placing your order, please check product details on the professional FLOS website, as well as the technical sheet and installation instructions, to ensure you have all the information not included in this catalogue but relevant to your project or specific installation.

Descripción
Light Shadow Mini es una familia de luminarias de interior en formato compacto.
Gracias a sus principales cualidades —dimensiones ultra reducidas, alto rendimiento y excelente apantallamiento— se integra de manera discreta y elegante en cualquier espacio.
Incorpora un módulo LED de alta eficiencia de FLOS con tecnología avanzada, óptica diseñada a medida y un sistema patentado de conos con curvatura invertida, que garantizan:
- Rendimiento óptimo.
- Precisión cromática.
- Distribución uniforme sin pérdidas.
- Menor deslumbramiento.
- Mayor confort visual.

Versiones disponibles
- 1 spot fix (Trim / No Trim).
- 2 / 4 spot fix / adjustable (Trim / No Trim).
- Round Fix (Trim).
La familia ofrece ópticas Spot, Medium y Flood, que permiten soluciones de iluminación de acento, intermedia y general.

Acabados
Para aplicaciones más decorativas, Light Shadow Mini incluye una gama de acabados que permiten personalizar la luminaria según el espacio:
- Exteriores: blanco y negro.
- Interiores: blanco, acero, bronce y negro (alto confort óptico).

Unidades de alimentación
Versiones On/Off, DALI regulable, Mains Dim y Casambi, disponibles según el driver (a solicitar por separado).
Accesorios
Para la versión No Trim se requiere un marco de preinstalación para falsos techos (adquirido por separado). No necesario en versión Trim.

Información adicional
- UGR < 10.
- Índice de protección IP55.
- Clase de aislamiento III.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play

NEW

LIGHT SHADOW MINI

DESIGNED BY FLOS ARCHITECTURAL

DOTS



LIGHT SOURCE
POWER LED
1,5W
148 lm
2700K/CRI 90
155 lm
3000K/CRI 90

ROUND TRIM



LIGHT SOURCE
POWER LED
6,1W
658 lm
2700K/CRI 90
681 lm
3000K/CRI 90

FIXED TRIM/NO TRIM 2 SPOTS



LIGHT SOURCE
POWER LED
3,1W
295 lm
2700K/CRI 90
309 lm
3000K/CRI 90

ADJUSTABLE TRIM/NO TRIM 2 SPOTS



LIGHT SOURCE
POWER LED
3,1W
295 lm
2700K/CRI 90
309 lm
3000K/CRI 90

FIXED TRIM/NO TRIM 4 SPOTS



LIGHT SOURCE
POWER LED
6,2W
590 lm
2700K/CRI 90
618 lm
3000K/CRI 90

ADJUSTABLE TRIM / NO TRIM 4 SPOTS



LIGHT SOURCE
POWER LED
6,2W
590 lm
2700K/CRI 90
618 lm
3000K/CRI 90

NEW

Internal Finish / Acabado interior

Light Shadow Mini Dots / Round Trim / Fixed / Adjustable

White
Blanco



HIGH COMFORT

Black
Negro



Steel
Acero



Bronze
Bronce



External Finish White / Acabado exterior Blanco

Light Shadow Mini Round Trim / Fixed / Adjustable









External Finish Black / Acabado exterior Negro

Light Shadow Mini Round Trim / Fixed / Adjustable











Light Shadow Mini Dots

Power LED 1,5W - 148 lm - 2700K/CRI 90 / 1,5W - 155 lm - 3000K/CRI 90








LED lighting luminaire to be inserted in the recessed frames (Trim/No Trim). It requires a pre-installation frame, to be ordered separately. Installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included.

Luminaria de iluminación LED para insertar en los marcos empotrados (con/sin embellecedor). Requiere un marco de preinstalación, que debe pedirse por separado. Instalación mediante un sistema de bayoneta con puntos intercambiables. Disponible en versiones de una luz y grupos de dos y cuatro luces. El driver no está incluido.



Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠
No Dimmable	60.7887	1	B
No Dimmable	60.9954.0500	1 - 12	B
Dali 2	60.9957.0500	2 - 12	B
Casambi	60.9874.0500	4 - 6	B
Casambi	60.9207	3 - 12	B
1-10V	60.9188	1 - 8	B
1-10V	60.9439	4 - 12	B
Mains Dimming	60.9467	2 - 8	B


* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

Set of 1 spot
- 05.8400.40
- 05.8400.14
- 05.8400.ER
- 05.8400.ES

Set of 2 spots
- 05.8410.40
- 05.8410.14
- 05.8410.ER
- 05.8410.ES

Set of 4 spots
- 05.8420.40
- 05.8420.14
- 05.8420.ER
- 05.8420.ES



Luminous flux luminaire 133 lm

@White (40)

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	1790	0.24
2	447	0.48
3	199	0.72
4	112	0.97
5	72	1.21

Optic Spot 3000K

Set of 1 spots
- 05.8405.40
- 05.8405.14
- 05.8405.ER
- 05.8405.ES

Set of 2 spots
- 05.8415.40
- 05.8415.14
- 05.8415.ER
- 05.8415.ES

Set of 4 spots
- 05.8425.40
- 05.8425.14
- 05.8425.ER
- 05.8425.ES



Luminous flux luminaire 140 lm

@White (40)

Beam Angle: 14°


h(m)	E(lx)	D(m)
1	1884	0.24
2	471	0.48
3	209	0.72
4	118	0.97
5	75	1.21

Optic Medium 2700K

Set of 1 spots
- 05.8401.40
- 05.8401.14
- 05.8401.ER
- 05.8401.ES

Set of 2 spots
- 05.8411.40
- 05.8411.14
- 05.8411.ER
- 05.8411.ES

Set of 4 spots
- 05.8421.40
- 05.8421.14
- 05.8421.ER
- 05.8421.ES



Luminous flux luminaire 136 lm

@White (40)

Beam Angle: 26°


h(m)	E(lx)	D(m)
1	706	0.46
2	177	0.91
3	78	1.37
4	44	1.82
5	28	2.28

Optic Medium 3000K

Set of 1 spots
- 05.8406.40
- 05.8406.14
- 05.8406.ER
- 05.8406.ES

Set of 2 spots
- 05.8416.40
- 05.8416.14
- 05.8416.ER
- 05.8416.ES

Set of 4 spots
- 05.8426.40
- 05.8426.14
- 05.8426.ER
- 05.8426.ES



Luminous flux luminaire 143 lm

@White (40)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	743	0.46
2	186	0.91
3	83	1.37
4	46	1.82
5	30	2.28

NEW


Optic Flood
2700K

Set of 1 spots
- 05.8402.40
- 05.8402.14
- 05.8402.ER
- 05.8402.ES

Set of 2 spots
- 05.8412.40
- 05.8412.14
- 05.8412.ER
- 05.8412.ES

Set of 4 spots
- 05.8422.40
- 05.8422.14
- 05.8422.ER
- 05.8422.ES





Luminous flux luminaire
134 lm

@White (40)

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	382	0.68
2	95	1.35
3	42	2.03
4	24	2.71
5	15	3.39


Optic Flood
3000K

Set of 1 spots
- 05.8407.40
- 05.8407.14
- 05.8407.ER
- 05.8407.ES

Set of 2 spots
- 05.8417.40
- 05.8417.14
- 05.8417.ER
- 05.8417.ES

Set of 4 spots
- 05.8427.40
- 05.8427.14
- 05.8427.ER
- 05.8427.ES








Luminous flux luminaire
140 lm

@White (40)

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	399	0.68
2	100	1.35
3	44	2.03
4	25	2.71
5	16	3.39


Accessories / Accesorios: Light Shadow Mini Dot


Frame No Trim	Marco de instalación No Trim			08.1050.00
Frame Trim	Marco de instalación Trim			08.1053.14 08.1053.40
Extraction tool. Accessory to remove the product once installed.	Herramienta de extracción. Accesorio para poder extraer el producto una vez instalado.			08.1062.90

Light Shadow Mini Fixed Trim 2 Spots

Power LED 3,1W - 295 lm - 2700K/CRI 90 / 3,1W - 309 lm - 3000K/CRI 90








Fixed recessed luminaire with 2 LED lighting spots. Remote power supply not included (220-240V).
No pre-installation frame required.

E = External Finish
I = Internal Finish

Luminaria empotrada fija con 2 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V). Requiere un marco de preinstalación, que debe pedirse por separado.

E = Acabado Externo I = Acabado Interno



Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0500	1 - 6	A	80
Dali 2	60.9957.0500	1 - 6	A	80
Casambi	60.9874.0500	2 - 3	A	150
Casambi	60.9207	2 - 6	B	-
1-10V	60.9188	1 - 4	B	-
1-10V	60.9439	2 - 6	B	-
Mains Dimming	60.9467	1 - 4	B	-

* Refer to the Drivers chapter / Ver capítulo Drivers


Optic Spot 2700K

E I
05.8500.14
05.8500.40

05.8501.14
05.8501.40

05.8503.14
05.8503.40

05.8504.14
05.8504.40



Beam Angle: 14°

h(m)	E(lx)	D(m)
1	3579	0.24
2	895	0.48
3	398	0.72
4	224	0.97
5	143	1.21

Luminous flux luminaire 266 lm

@White (40)


Optic Spot 3000K

E I
05.8520.14
05.8520.40

05.8521.14
05.8521.40

05.8523.14
05.8523.40

05.8524.14
05.8524.40



Beam Angle: 14°

h(m)	E(lx)	D(m)
1	3741	0.24
2	935	0.48
3	416	0.72
4	234	0.97
5	150	1.21

Luminous flux luminaire 278 lm

@White (40)


Optic Medium 2700K

E I
05.8505.14
05.8505.40

05.8506.14
05.8506.40

05.8508.14
05.8508.40

05.8509.14
05.8509.40



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1413	0.46
2	353	0.91
3	157	1.37
4	88	1.82
5	57	2.28

Luminous flux luminaire 272 lm

@White (40)


Optic Medium 3000K

E I
05.8525.14
05.8525.40

05.8526.14
05.8526.40

05.8528.14
05.8528.40

05.8529.14
05.8529.40



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1481	0.46
2	370	0.91
3	165	1.37
4	93	1.82
5	59	2.28

Luminous flux luminaire 285 lm

@White (40)


Optic Flood 2700K

E I
05.8510.14
05.8510.40

05.8511.14
05.8511.40

05.8513.14
05.8513.40

05.8514.14
05.8514.40



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	757	0.68
2	189	1.35
3	84	2.03
4	47	2.71
5	30	3.39

Luminous flux luminaire 266 lm

@White (40)


Optic Flood 3000K

E I
05.8530.14
05.8530.40

05.8531.14
05.8531.40

05.8533.14
05.8533.40

05.8534.14
05.8534.40



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	794	0.68
2	199	1.35
3	88	2.03
4	50	2.71
5	32	3.39

Luminous flux luminaire 279 lm


@White (40)


NEW

Light Shadow Mini Fixed No Trim 2 Spots

Power LED 3,1W - 295 lm - 2700K/CRI 90 / 3,1W - 309 lm - 3000K/CRI 90








Fixed recessed luminaire with 2 LED lighting spots. Remote power supply not included (220-240V). It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish

Luminaria empotrada fija con 2 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V). Requiere un marco de preinstalación, que debe pedirse por separado.

E = Acabado Externo
I = Acabado Interno




Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0500	1 - 6	A	80
Dali 2	60.9957.0500	1 - 6	A	80
Casambi	60.9874.0500	2 - 3	A	150
Casambi	60.9207	2 - 6	B	-
1-10V	60.9188	1 - 4	B	-
1-10V	60.9439	2 - 6	B	-
Mains Dimming	60.9467	1 - 4	B	-

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

E I




05.8540.14
05.8540.40

05.8541.14
05.8541.40

05.8543.14
05.8543.40


05.8544.14
05.8544.40



@White (40)

Optic Spot 3000K

E I




05.8560.14
05.8560.40

05.8561.14
05.8561.40

05.8563.14
05.8563.40


05.8564.14
05.8564.40



@White (40)

Optic Medium 2700K

E I




05.8545.14
05.8545.40

05.8546.14
05.8546.40

05.8548.14
05.8548.40


05.8549.14
05.8549.40



@White (40)

Optic Medium 3000K

E I




05.8565.14
05.8565.40

05.8566.14
05.8566.40

05.8568.14
05.8568.40


05.8569.14
05.8569.40



@White (40)

Optic Flood 2700K

E I




05.8550.14
05.8550.40

05.8551.14
05.8551.40

05.8553.14
05.8553.40


05.8554.14
05.8554.40



@White (40)

Optic Flood 3000K

E I




05.8570.14
05.8570.40

05.8571.14
05.8571.40

05.8573.14
05.8573.40

05.8574.14
05.8574.40





@White (40)

Light Shadow Mini Fixed Trim 4 Spots

Power LED 6,2W - 590 lm - 2700K/CRI 90 / 6,2W - 618 lm - 3000K/CRI 90








Fixed recessed luminaire with 4 LED lighting spots. Remote power supply not included (220-240V).
No pre-installation frame required.

E = External Finish
I = Internal Finish

Luminaria empotrada fija con 4 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V). Requiere un marco de preinstalación, que debe pedirse por separado.

E = Acabado Externo I = Acabado Interno



Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0500	1 - 3	A	50
Dali 2	60.9957.0500	1 - 3	A	50
Casambi	60.9874.0500	1	A	80
Casambi	60.9207	1 - 3	B	-
1-10V	60.9188	1 - 2	A	70
1-10V	60.9439	1 - 3	B	-
Mains Dimming	60.9467	1 - 2	A	70

* Refer to the Drivers chapter / Ver capítulo Drivers


Optic Spot 2700K

E I
05.8600.14
05.8600.40

05.8601.14
05.8601.40

05.8603.14
05.8603.40

05.8604.14
05.8604.40



@White (40)


Optic Spot 3000K

E I
05.8620.14
05.8620.40

05.8621.14
05.8621.40

05.8623.14
05.8623.40

05.8624.14
05.8624.40



@White (40)


Optic Medium 2700K

E I
05.8605.14
05.8605.40

05.8606.14
05.8606.40

05.8608.14
05.8608.40

05.8609.14
05.8609.40



@White (40)


Optic Medium 3000K

E I
05.8625.14
05.8625.40

05.8626.14
05.8626.40

05.8628.14
05.8628.40

05.8629.14
05.8629.40



@White (40)


Optic Flood 2700K

E I
05.8610.14
05.8610.40

05.8611.14
05.8611.40

05.8613.14
05.8613.40

05.8614.14
05.8614.40



@White (40)


Optic Flood 3000K

E I
05.8630.14
05.8630.40

05.8631.14
05.8631.40

05.8633.14
05.8633.40

05.8634.14
05.8634.40




@White (40)


NEW

Light Shadow Mini Fixed No Trim 4 Spots

Power LED 6,2W - 590 lm - 2700K/CRI 90 / 6,2W - 618 lm - 3000K/CRI 90








Fixed recessed luminaire with 4 LED lighting spots. Remote power supply not included (220-240V). It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish

Luminaria empotrada fija con 4 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V). Requiere un marco de preinstalación, que debe pedirse por separado.

E = Acabado Externo
I = Acabado Interno




Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0500	1 - 3	A	50
Dali 2	60.9957.0500	1 - 3	A	50
Casambi	60.9874.0500	1	A	80
Casambi	60.9207	1 - 3	B	-
1-10V	60.9188	1 - 2	A	70
1-10V	60.9439	1 - 3	B	-
Mains Dimming	60.9467	1 - 2	A	70

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

E I
05.8640.14
05.8640.40
05.8641.14
05.8641.40
05.8643.14
05.8643.40
05.8644.14
05.8644.40



Beam Angle: 14°


h(m)	E(lx)	D(m)
1	7145	0.24
2	1786	0.48
3	794	0.72
4	447	0.97
5	286	1.21

Luminous flux luminaire 531 lm

@White (40)

Optic Spot 3000K

E I
05.8660.14
05.8660.40
05.8661.14
05.8661.40
05.8663.14
05.8663.40
05.8664.14
05.8664.40



Beam Angle: 14°


h(m)	E(lx)	D(m)
1	7481	0.24
2	1870	0.48
3	831	0.72
4	468	0.97
5	299	1.21

Luminous flux luminaire 556 lm

@White (40)

Optic Medium 2700K

E I
05.8645.14
05.8645.40
05.8646.14
05.8646.40
05.8648.14
05.8648.40
05.8649.14
05.8649.40



Beam Angle: 26°


h(m)	E(lx)	D(m)
1	2821	0.46
2	705	0.91
3	313	1.37
4	176	1.82
5	113	2.28

Luminous flux luminaire 543 lm

@White (40)

Optic Medium 3000K

E I
05.8665.14
05.8665.40
05.8666.14
05.8666.40
05.8668.14
05.8668.40
05.8669.14
05.8669.40



Beam Angle: 26°


h(m)	E(lx)	D(m)
1	2956	0.46
2	739	0.91
3	328	1.37
4	185	1.82
5	118	2.28

Luminous flux luminaire 569 lm

@White (40)

Optic Flood 2700K

E I
05.8650.14
05.8650.40
05.8651.14
05.8651.40
05.8653.14
05.8653.40
05.8654.14
05.8654.40



Beam Angle: 37°


h(m)	E(lx)	D(m)
1	1515	0.68
2	379	1.35
3	168	2.03
4	95	2.71
5	61	3.39

Luminous flux luminaire 532 lm

@White (40)

Optic Flood 3000K

E I
05.8670.14
05.8670.40
05.8671.14
05.8671.40
05.8673.14
05.8673.40
05.8674.14
05.8674.40



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	1589	0.68
2	397	1.35
3	177	2.03
4	99	2.71
5	64	3.39


Luminous flux luminaire 558 lm


@White (40)

Light Shadow Mini Adjustable Trim 2 Spots

Power LED 3,1W - 295 lm - 2700K/CRI 90 / 3,1W - 309 lm - 3000K/CRI 90









Adjustable recessed luminaire with 2 LED lighting spots. Remote power supply not included (220-240V). No pre-installation frame required.

E= External Finish
I= Internal Finish

Luminaria empotrada ajustable con 2 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V). No se requiere marco de preinstalación.

E = Acabado Externo
I = Acabado Interno





Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0500	1 - 6	A	60
Dali 2	60.9957.0500	1 - 6	A	60
Casambi	60.9874.0500	2 - 3	A	70
Casambi	60.9207	2 - 6	A	82
1-10V	60.9188	1 - 4	A	100
1-10V	60.9439	2 - 6	A	100
Mains Dimming	60.9467	1 - 4	A	100

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

E I


05.8700.14
05.8700.40

05.8701.14
05.8701.40

05.8703.14
05.8703.40

05.8704.14
05.8704.40

14° SPOT



Luminous flux luminaire 266 lm

@White (40)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	3579	0.24
2	895	0.48
3	398	0.72
4	224	0.97
5	143	1.21

Optic Spot 3000K

E I


05.8720.14
05.8720.40

05.8721.14
05.8721.40

05.8723.14
05.8723.40

05.8724.14
05.8724.40

14° SPOT



Luminous flux luminaire 278 lm

@White (40)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	3741	0.24
2	935	0.48
3	416	0.72
4	234	0.97
5	150	1.21

Optic Medium 2700K

E I


05.8705.14
05.8705.40

05.8706.14
05.8706.40

05.8708.14
05.8708.40

05.8709.14
05.8709.40

26° MEDIUM



Luminous flux luminaire 272 lm

@White (40)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1413	0.46
2	353	0.91
3	157	1.37
4	88	1.82
5	57	2.28

Optic Medium 3000K

E I


05.8725.14
05.8725.40

05.8726.14
05.8726.40

05.8728.14
05.8728.40

05.8729.14
05.8729.40

26° MEDIUM



Luminous flux luminaire 285 lm

@White (40)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1481	0.46
2	370	0.91
3	165	1.37
4	93	1.82
5	59	2.28

Optic Flood 2700K

E I


05.8710.14
05.8710.40

05.8711.14
05.8711.40

05.8713.14
05.8713.40

05.8714.14
05.8714.40

37° FLOOD



Luminous flux luminaire 266 lm

@White (40)

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	757	0.68
2	189	1.35
3	84	2.03
4	47	2.71
5	30	3.39

Optic Flood 3000K

E I


05.8730.14
05.8730.40

05.8731.14
05.8731.40

05.8733.14
05.8733.40

05.8734.14
05.8734.40

37° FLOOD



Luminous flux luminaire 279 lm

@White (40)

Beam Angle: 37°


h(m)	E(lx)	D(m)
1	794	0.68
2	199	1.35
3	88	2.03
4	50	2.71
5	32	3.39


NEW

Light Shadow Mini Adjustable No Trim 2 Spots

Power LED 3,1W - 295 lm - 2700K/CRI 90 / 3,1W - 309 lm - 3000K/CRI 90









Adjustable recessed luminaire with 2 LED lighting spots. Remote power supply not included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish

Luminaria empotrada ajustable con 2 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V). Requiere un marco de preinstalación, que debe pedirse por separado.

E = Acabado Externo
I = Acabado Interno






Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0500	1 - 6	A	60
Dali 2	60.9957.0500	1 - 6	A	60
Casambi	60.9874.0500	2 - 3	A	70
Casambi	60.9207	2 - 6	A	82
1-10V	60.9188	1 - 4	A	100
1-10V	60.9439	2 - 6	A	100
Mains Dimming	60.9467	1 - 4	A	100

* Refer to the Drivers chapter / Ver capítulo Drivers


Optic Spot 2700K

E I
05.8740.14
05.8740.40
05.8741.14
05.8741.40
05.8743.14
05.8743.40
05.8744.14
05.8744.40




Optic Spot 3000K

E I
05.8760.14
05.8760.40
05.8761.14
05.8761.40
05.8763.14
05.8763.40
05.8764.14
05.8764.40




Optic Medium 2700K

E I
05.8745.14
05.8745.40
05.8746.14
05.8746.40
05.8748.14
05.8748.40
05.8749.14
05.8749.40




Optic Medium 3000K

E I
05.8765.14
05.8765.40
05.8766.14
05.8766.40
05.8768.14
05.8768.40
05.8769.14
05.8769.40




Optic Flood 2700K

E I
05.8750.14
05.8750.40
05.8751.14
05.8751.40
05.8753.14
05.8753.40
05.8754.14
05.8754.40



Optic Flood 3000K


E I
05.8770.14
05.8770.40
05.8771.14
05.8771.40
05.8773.14
05.8773.40
05.8774.14
05.8774.40




Light Shadow Mini Adjustable Trim 4 Spots

Power LED 6,2W - 590 lm - 2700K/CRI 90 / 6,2W - 618 lm - 3000K/CRI 90








Adjustable recessed luminaire with 4 LED lighting spots. Remote power supply not included (220-240V). No pre-installation frame required.

E= External Finish
I= Internal Finish

Luminaria empotrada ajustable con 4 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V). No se requiere marco de preinstalación.

E = Acabado Externo
I = Acabado Interno





Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0500	1 - 3	A	50
Dali 2	60.9957.0500	1 - 3	A	50
Casambi	60.9874.0500	1	A	50
Casambi	60.9207	1 - 3	A	50
1-10V	60.9188	1 - 2	A	50
1-10V	60.9439	1 - 3	A	55
Mains Dimming	60.9467	1 - 2	A	50

* Refer to the Drivers chapter / Ver capítulo Drivers


Optic Spot 2700K

E I
05.8800.14
05.8800.40

05.8801.14
05.8801.40

05.8803.14
05.8803.40

05.8804.14
05.8804.40



Beam Angle: 14°

h(m)	E(lx)	D(m)
1	7145	0.24
2	1786	0.48
3	794	0.72
4	447	0.97
5	286	1.21

Luminous flux luminaire 531 lm

@White (40)


Optic Spot 3000K

E I
05.8820.14
05.8820.40

05.8821.14
05.8821.40

05.8823.14
05.8823.40

05.8824.14
05.8824.40



Beam Angle: 14°

h(m)	E(lx)	D(m)
1	7481	0.24
2	1870	0.48
3	831	0.72
4	468	0.97
5	299	1.21

Luminous flux luminaire 556 lm

@White (40)


Optic Medium 2700K

E I
05.8805.14
05.8805.40

05.8806.14
05.8806.40

05.8808.14
05.8808.40

05.8809.14
05.8809.40



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2821	0.46
2	705	0.91
3	313	1.37
4	176	1.82
5	113	2.28

Luminous flux luminaire 543 lm

@White (40)


Optic Medium 3000K

E I
05.8825.14
05.8825.40

05.8826.14
05.8826.40

05.8828.14
05.8828.40

05.8829.14
05.8829.40



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2956	0.46
2	739	0.91
3	328	1.37
4	185	1.82
5	118	2.28

Luminous flux luminaire 569 lm

@White (40)


Optic Flood 2700K

E I
05.8810.14
05.8810.40

05.8811.14
05.8811.40

05.8813.14
05.8813.40

05.8814.14
05.8814.40



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	1515	0.68
2	379	1.35
3	168	2.03
4	95	2.71
5	61	3.39

Luminous flux luminaire 532 lm

@White (40)


Optic Flood 3000K

E I
05.8830.14
05.8830.40

05.8831.14
05.8831.40

05.8833.14
05.8833.40

05.8834.14
05.8834.40



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	1589	0.68
2	397	1.35
3	177	2.03
4	99	2.71
5	64	3.39

Luminous flux luminaire 558 lm


@White (40)


NEW

Light Shadow Mini Adjustable No Trim 4 Spots

Power LED 6,2W - 590 lm - 2700K/CRI 90 / 6,2W - 618 lm - 3000K/CRI 90








Adjustable recessed luminaire with 4 LED lighting spots. Remote power supply not included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish

Luminaria empotrada ajustable con 4 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V). Requiere un marco de preinstalación, que debe pedirse por separado.

E = Acabado Externo
I = Acabado Interno





Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0500	1 - 3	A	50
Dali 2	60.9957.0500	1 - 3	A	50
Casambi	60.9874.0500	1	A	50
Casambi	60.9207	1 - 3	A	50
1-10V	60.9188	1 - 2	A	50
1-10V	60.9439	1 - 3	A	55
Mains Dimming	60.9467	1 - 2	A	50

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K


E I
05.8840.14
05.8840.40

05.8841.14
05.8841.40

05.8843.14
05.8843.40

05.8844.14
05.8844.40

14° SPOT



Luminous flux luminaire 531 lm

@White (40)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	7145	0.24
2	1786	0.48
3	794	0.72
4	447	0.97
5	286	1.21

Optic Spot 3000K


E I
05.8860.14
05.8860.40

05.8861.14
05.8861.40

05.8863.14
05.8863.40

05.8864.14
05.8864.40

14° SPOT



Luminous flux luminaire 556 lm

@White (40)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	7481	0.24
2	1870	0.48
3	831	0.72
4	468	0.97
5	299	1.21

Optic Medium 2700K


E I
05.8845.14
05.8845.40

05.8846.14
05.8846.40

05.8848.14
05.8848.40

05.8849.14
05.8849.40

26° MEDIUM



Luminous flux luminaire 543 lm

@White (40)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2821	0.46
2	705	0.91
3	313	1.37
4	176	1.82
5	113	2.28

Optic Medium 3000K


E I
05.8865.14
05.8865.40

05.8866.14
05.8866.40

05.8868.14
05.8868.40

05.8869.14
05.8869.40

26° MEDIUM



Luminous flux luminaire 569 lm

@White (40)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2956	0.46
2	739	0.91
3	328	1.37
4	185	1.82
5	118	2.28

Optic Flood 2700K


E I
05.8850.14
05.8850.40

05.8851.14
05.8851.40

05.8853.14
05.8853.40

05.8854.14
05.8854.40

37° FLOOD



Luminous flux luminaire 532 lm

@White (40)

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	1515	0.68
2	379	1.35
3	168	2.03
4	95	2.71
5	61	3.39

Optic Flood 3000K


E I
05.8870.14
05.8870.40

05.8871.14
05.8871.40

05.8873.14
05.8873.40

05.8874.14
05.8874.40

37° FLOOD







Luminous flux luminaire 558 lm

@White (40)

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	1589	0.68
2	397	1.35
3	177	2.03
4	99	2.71
5	64	3.39

Accessories / Accesorios
Light Shadow Mini Fixed / Adjustable


Frame No Trim Fixed	Marco de instalación No Trim Fijo			2L 08.1056.00
				4L 08.1057.00
Frame No Trim Adjustable	Marco de instalación No Trim Ajustable			2L 08.1058.00
				4L 08.1059.00


NEW

Light Shadow Mini Round Trim

Power LED 6,1W - 658 lm - 2700K/CRI 90 / 6,1W - 681 lm - 3000K/CRI 90








Recessed integrated luminaire with 7 LED lighting spots. Remote power supply not included (220-240V).
Pre-installation frame not required.

E= External Finish
I= Internal Finish

Luminaria empotrada fija con 7 puntos de iluminación LED. Fuente de alimentación remota no incluida (220-240V).
No se requiere marco de preinstalación.

E = Acabado Externo
I = Acabado Interno



Recommended power supply / Equipos recomendados*:

		Serial Con.	⚠	h
No Dimmable	60.9954.0300	1 - 2	A	60
Dali 2	60.9957.0300	1 - 2	A	60
Casambi	60.9874.0300	1	A	80
Casambi	60.9207	1 - 2	A	90
1-10V	60.9188	1	A	50
1-10V	60.9439	1 - 2	A	80
Mains Dimming	60.9467	1	A	50

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K


E I
05.8450.14
05.8450.40

05.8451.14
05.8451.40

05.8453.14
05.8453.40

05.8454.14
05.8454.40

14° SPOT



Luminous flux luminaire 568 lm

@White (40)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	7252	0.24
2	1813	0.48
3	806	0.72
4	453	0.96
5	290	1.20

Optic Spot 3000K


E I
05.8470.14
05.8470.40

05.8471.14
05.8471.40

05.8473.14
05.8473.40

05.8474.14
05.8474.40

14° SPOT



Luminous flux luminaire 590 lm

@White (40)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	7533	0.24
2	1883	0.48
3	837	0.72
4	471	0.96
5	301	1.20

Optic Medium 2700K


E I
05.8455.14
05.8455.40

05.8456.14
05.8456.40

05.8458.14
05.8458.40

05.8459.14
05.8459.40

25° MEDIUM



Luminous flux luminaire 596 lm

@White (40)

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	3154	0.45
2	789	0.89
3	350	1.34
4	197	1.78
5	126	2.23

Optic Medium 3000K


E I
05.8475.14
05.8475.40

05.8476.14
05.8476.40

05.8478.14
05.8478.40

05.8479.14
05.8479.40

25° MEDIUM



Luminous flux luminaire 618 lm

@White (40)

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	3271	0.45
2	818	0.89
3	363	1.34
4	204	1.78
5	131	2.23

Optic Flood 2700K


E I
05.8460.14
05.8460.40

05.8461.14
05.8461.40

05.8463.14
05.8463.40

05.8464.14
05.8464.40

38° FLOOD



Luminous flux luminaire 584 lm

@White (40)

Beam Angle: 38°

h(m)	E(lx)	D(m)
1	1633	0.68
2	408	1.36
3	181	2.04
4	102	2.72
5	65	3.40

Optic Flood 3000K


E I
05.8480.14
05.8480.40

05.8481.14
05.8481.40

05.8483.14
05.8483.40

05.8484.14
05.8484.40

38° FLOOD



Luminous flux luminaire 607 lm


@White (40)

Beam Angle: 38°

h(m)	E(lx)	D(m)
1	1698	0.68
2	424	1.36
3	189	2.04
4	106	2.72
5	68	3.40

LIGHT SHADOW

DESIGNED BY FLOS ARCHITECTURAL



Description
Indoor, embedded and surface luminaires.
Due to their main qualities (reduced size, high performance and great screening), they facilitate total integration into spaces.
The family was born of the need for a compact, easy-to-install luminaire, with the distinctive Flos style, able to produce high efficiency lighting, while respecting the highest standards of visual comfort, in versions with black screening bodies.
- Fixed and adjustable embedded versions: 2/4/8/12 spots (Trim/No Trim).
- Fixed surface versions: 4 spots.
- Wall-washer version: 4 spots (Trim / No Trim).
The family is offered with super accented, accented and general lighting optics.
For solutions in more decorative settings, the following range of colours has been developed, with a combination of interior and exterior painted finishes:
- exterior finishes: black and white.
- interior finishes: white, steel, bronze and black (high comfort optics).
- outdoor box surface version: black, white, brushed steel and brushed bronze.

Power Supply
DALI, Mains Dim and Casambi versions available. See models.
Versions with 110V equipment available upon request.

Accessories
For the No Trim version, pre-installation frame in aluminium for false ceiling installation. It needs to be ordered separately (not necessary for Trim version).

Additional Information
No Trim version has been designed for 12.5 mm thick plasterboard installation.
IP20, IP23, IP44, IP55 protection grade depending on the versions.
Insulation class II.
Suitable for installation on normally inflammable surfaces.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminarias de interior, empotrables y de superficie.
Debido a sus principales cualidades: reducido tamaño, rendimiento y gran apantallamiento, facilitan su total integración en espacios.
La familia nace de la necesidad de una luminaria compacta y de fácil instalación, con el estilo distintivo de Flos, capaz de producir una iluminación de alta eficiencia y respetando a su vez los más altos estándares de confort visual, en versiones con cuerpos de apantantallamiento negros.
- Versiones empotrables fijas y ajustables: 2/4/8/12 spots (Trim / No Trim).
- Versiones fijas de superficie: 4 spots.
- Versión wall-washer: 4 spots (Trim / No Trim).
La familia se ofrece con ópticas de súper acento, acento e iluminación general.
Para dar soluciones en ambientes más decorativos se ha desarrollado la siguiente gama de colores con combinación de acabados pintados exteriores e interiores:
- acabados exteriores: blanco y negro.
- acabados interiores: blanco, acero, bronce y negro (alto confort óptico).
- box exterior de la versión de superficie: blanco, negro acero cepillado y bronce cepillado.

Unidades de Alimentación
Versiones dimmables DALI, Mains Dim y Casambi disponibles. Ver modelos.
Versiones con equipo 110V disponibles bajo pedido.

Accesorios
Para la versión No Trim, necesario marco de pre-instalación realizado en aluminio para su instalación en falso techo. Ha de pedirse por separado (no es necesario para la versión Trim).

Información Adicional
La versión No Trim se ha diseñado para una instalación en placas de cartón yeso de un espesor de 12,5 mm.
Índice de protección IP20, IP23, IP44, IP55 según las versiones.
Clase de aislamiento II.
Instalable sobre superficies normalmente inflamables.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Trim | No Trim | Surface | Continuous Line

FIXED
TRIM/NO TRIM
2 SPOTS*



ADJUSTABLE
TRIM/NO TRIM
2 SPOTS*



FIXED
TRIM/NO TRIM
4 SPOTS



ADJUSTABLE
TRIM / NO TRIM
4 SPOTS



FIXED
TRIM/NO TRIM
4 SPOTS SQUARE




FIXED
TRIM/NO TRIM
8 SPOTS**



ADJUSTABLE
TRIM/NO TRIM
8 SPOTS**



FIXED
TRIM/NO TRIM
12 SPOTS**



ADJUSTABLE
TRIM/NO TRIM
12 SPOTS**



WALL-WASHER
TRIM/NO TRIM
4 SPOTS



SURFACE
4 SPOTS



SURFACE
4 SPOTS SQUARE**



LIGHT SOURCE
POWER LED
No dimmable/Dimmable
2,7W x Spot
298 lm x Spot
2700K/CRI 90
318 lm x Spot
3000K/CRI 90

LIGHT SOURCE
POWER LED
*No dimmable/Dimmable
3,5W x Spot
298 lm x Spot
2700K/CRI 90
318 lm x Spot
3000K/CRI 90

LIGHT SOURCE
POWER LED
**Mains dimming
2,3W x Spot
248 lm x Spot
2700K/CRI 90
265 lm x Spot
3000K/CRI 90

Internal Finish

Light Shadow Fixed / Fixed Square
Adjustable / Surface / Surface Square

White
Blanco



HIGH COMFORT

Black
Negro



Steel
Acero



Bronze
Bronce



External Plate Finish

Light Shadow Fixed / Fixed Square
Adjustable / Surface / Surface Square

White
Blanco



Black
Negro



External Plate Finish

Light Shadow Wall-Washer

White
Blanco



Black
Negro



Box Finish

Light Shadow Surface / Surface Square

White
Blanco



Black
Negro



Brushed Steel
Acero Cepillado



Brushed Bronze
Bronce Cepillado



Light Shadow for The Running Magnet

LIGHT SHADOW



LIGHT SHADOW
WALL-WASHER





See The Running Magnet collection / Ver la colección The Running Magnet

Light Shadow Fixed Trim 2 Spots

Power LED DC 900 mA 7W - 596 lm - 2700K/CRI 90 / 7W - 636 lm - 3000K/CRI 90







Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

E= External Finish
I= Internal Finish

Luminaria empotrable de 2 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable

03.8820.40C
03.8820.14C

Dali Version

03.8820.40CDA
03.8820.14CDA

Mains Dimming

03.8820.40CNI
03.8820.14CNI

Casambi

03.8820.40CCB
03.8820.14CCB

Non Dimmable

03.8821.40C
03.8821.14C

Dali Version

03.8821.40CDA
03.8821.14CDA

Mains Dimming

03.8821.40CNI
03.8821.14CNI

Casambi

03.8821.40CCB
03.8821.14CCB

Non Dimmable

05.1001.40C
05.1001.14C

Dali Version

05.1001.40CDA
05.1001.14CDA

Mains Dimming

05.1001.40CNI
05.1001.14CNI

Casambi

05.1001.40CCB
05.1001.14CCB

Non Dimmable

05.1002.40C
05.1002.14C

Dali Version

05.1002.40CDA
05.1002.14CDA


Mains Dimming

05.1002.40CNI
05.1002.14CNI

Casambi

05.1002.40CCB
05.1002.14CCB

12° SPOT



Luminous flux luminaire 530 lm

@White (40)

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	8555	0.20
2	2139	0.41
3	951	0.61
4	535	0.81
5	342	1.01

Optic Spot 3000K

E I Non Dimmable

03.8824.40C
03.8824.14C

Dali Version

03.8824.40CDA
03.8824.14CDA

Mains Dimming

03.8824.40CNI
03.8824.14CNI

Casambi

03.8824.40CCB
03.8824.14CCB

Non Dimmable

03.8825.40C
03.8825.14C

Dali Version

03.8825.40CDA
03.8825.14CDA

Mains Dimming

03.8825.40CNI
03.8825.14CNI

Casambi

03.8825.40CCB
03.8825.14CCB

Non Dimmable

05.1006.40C
05.1006.14C

Dali Version

05.1006.40CDA
05.1006.14CDA

Mains Dimming

05.1006.40CNI
05.1006.14CNI

Casambi

05.1006.40CCB
05.1006.14CCB

Non Dimmable

05.1007.40C
05.1007.14C

Dali Version

05.1007.40CDA
05.1007.14CDA


Mains Dimming

05.1007.40CNI
05.1007.14CNI

Casambi

05.1007.40CCB
05.1007.14CCB

12° SPOT



Luminous flux luminaire 566 lm

@White (40)


Beam Angle: 12°

h(m)	E(lx)	D(m)
1	9136	0.20
2	2284	0.41
3	1015	0.61
4	571	0.81
5	365	1.01

Optic Medium
2700K

E I Non Dimmable
03.9100.40C
03.9100.14C
Dali Version
03.9100.40CDA
03.9100.14CDA
Mains Dimming
03.9100.40CNI
03.9100.14CNI
Casambi
03.9100.40CCB
03.9100.14CCB
Non Dimmable
03.9101.40C
03.9101.14C
Dali Version
03.9101.40CDA
03.9101.14CDA
Mains Dimming
03.9101.40CNI
03.9101.14CNI
Casambi
03.9101.40CCB
03.9101.14CCB
Non Dimmable
05.1011.40C
05.1011.14C
Dali Version
05.1011.40CDA
05.1011.14CDA
Mains Dimming
05.1011.40CNI
05.1011.14CNI
Casambi
05.1011.40CCB
05.1011.14CCB
Non Dimmable
05.1012.40C
05.1012.14C
Dali Version
05.1012.40CDA
05.1012.14CDA
Mains Dimming
05.1012.40CNI
05.1012.14CNI
Casambi
05.1012.40CCB
05.1012.14CCB





Luminous flux luminaire
510 lm


@White (40)

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	3423	0.40
2	856	0.80
3	380	1.20
4	214	1.60
5	137	2.00

Optic Medium
3000K

E I Non Dimmable
03.9110.40C
03.9110.14C
Dali Version
03.9110.40CDA
03.9110.14CDA
Mains Dimming
03.9110.40CNI
03.9110.14CNI
Casambi
03.9110.40CCB
03.9110.14CCB
Non Dimmable
03.9111.40C
03.9111.14C
Dali Version
03.9111.40CDA
03.9111.14CDA
Mains Dimming
03.9111.40CNI
03.9111.14CNI
Casambi
03.9111.40CCB
03.9111.14CCB
Non Dimmable
05.1016.40C
05.1016.14C
Dali Version
05.1016.40CDA
05.1016.14CDA
Mains Dimming
05.1016.40CNI
05.1016.14CNI
Casambi
05.1016.40CCB
05.1016.14CCB
Non Dimmable
05.1017.40C
05.1017.14C
Dali Version
05.1017.40CDA
05.1017.14CDA
Mains Dimming
05.1017.40CNI
05.1017.14CNI
Casambi
05.1017.40CCB
05.1017.14CCB





Luminous flux luminaire
544 lm


@White (40)


Beam Angle:		23°
h(m)	E(lx)	D(m)
1	3651	0.40
2	913	0.80
3	406	1.20
4	228	1.60
5	146	2.00

Light Shadow Fixed Trim 2 Spots

Power LED DC 900 mA 7W - 596 lm - 2700K/CRI 90 / 7W - 636 lm - 3000K/CRI 90







Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 2 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9105.40C
03.9105.14C
Dali Version
03.9105.40CDA
03.9105.14CDA
Mains Dimming
03.9105.40CNI
03.9105.14CNI
Casambi
03.9105.40CCB
03.9105.14CCB
Non Dimmable
03.9106.40C
03.9106.14C
Dali Version
03.9106.40CDA
03.9106.14CDA
Mains Dimming
03.9106.40CNI
03.9106.14CNI
Casambi
03.9106.40CCB
03.9106.14CCB
Non Dimmable
05.1021.40C
05.1021.14C
Dali Version
05.1021.40CDA
05.1021.14CDA
Mains Dimming
05.1021.40CNI
05.1021.14CNI
Casambi
05.1021.40CCB
05.1021.14CCB
Non Dimmable
05.1022.40C
05.1022.14C
Dali Version
05.1022.40CDA
05.1022.14CDA
Mains Dimming
05.1022.40CNI
05.1022.14CNI
Casambi
05.1022.40CCB
05.1022.14CCB

29°
FLOOD



Luminous flux luminaire
514 lm


@White (40)

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	2070	0.51
2	517	1.03
3	230	1.54
4	129	2.05
5	83	2.57

Optic Flood 3000K

E I Non Dimmable
03.9115.40C
03.9115.14C
Dali Version
03.9115.40CDA
03.9115.14CDA
Mains Dimming
03.9115.40CNI
03.9115.14CNI
Casambi
03.9115.40CCB
03.9115.14CCB
Non Dimmable
03.9116.40C
03.9116.14C
Dali Version
03.9116.40CDA
03.9116.14CDA
Mains Dimming
03.9116.40CNI
03.9116.14CNI
Casambi
03.9116.40CCB
03.9116.14CCB
Non Dimmable
05.1026.40C
05.1026.14C
Dali Version
05.1026.40CDA
05.1026.14CDA
Mains Dimming
05.1026.40CNI
05.1026.14CNI
Casambi
05.1026.40CCB
05.1026.14CCB
Non Dimmable
05.1027.40C
05.1027.14C
Dali Version
05.1027.40CDA
05.1027.14CDA
Mains Dimming
05.1027.40CNI
05.1027.14CNI
Casambi
05.1027.40CCB
05.1027.14CCB

29°
FLOOD



Luminous flux luminaire
549 lm

@White (40)


Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	2211	0.51
2	553	1.03
3	246	1.54
4	138	2.05
5	88	2.57

Optic Wide Flood 2700K

E I Non Dimmable
03.8300.40C
03.8300.14C
Dali Version
03.8300.40CDA
03.8300.14CDA
Mains Dimming
03.8300.40CNI
03.8300.14CNI
Casambi
03.8300.40CCB
03.8300.14CCB
Non Dimmable
03.8301.40C
03.8301.14C
Dali Version
03.8301.40CDA
03.8301.14CDA
Mains Dimming
03.8301.40CNI
03.8301.14CNI
Casambi
03.8301.40CCB
03.8301.14CCB
Non Dimmable
05.1031.40C
05.1031.14C
Dali Version
05.1031.40CDA
05.1031.14CDA
Mains Dimming
05.1031.40CNI
05.1031.14CNI
Casambi
05.1031.40CCB
05.1031.14CCB
Non Dimmable
05.1032.40C
05.1032.14C
Dali Version
05.1032.40CDA
05.1032.14CDA
Mains Dimming
05.1032.40CNI
05.1032.14CNI
Casambi
05.1032.40CCB
05.1032.14CCB



WIDE FLOOD



Luminous flux luminaire 511 lm

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	1021	0.83
2	255	1.66
3	113	2.49
4	64	3.32
5	41	4.14


@White (40)

Optic Wide Flood 3000K

E I Non Dimmable
03.8304.40C
03.8304.14C
Dali Version
03.8304.40CDA
03.8304.14CDA
Mains Dimming
03.8304.40CNI
03.8304.14CNI
Casambi
03.8304.40CCB
03.8304.14CCB
Non Dimmable
03.8305.40C
03.8305.14C
Dali Version
03.8305.40CDA
03.8305.14CDA
Mains Dimming
03.8305.40CNI
03.8305.14CNI
Casambi
03.8305.40CCB
03.8305.14CCB
Non Dimmable
05.1036.40C
05.1036.14C
Dali Version
05.1036.40CDA
05.1036.14CDA
Mains Dimming
05.1036.40CNI
05.1036.14CNI
Casambi
05.1036.40CCB
05.1036.14CCB
Non Dimmable
05.1037.40C
05.1037.14C
Dali Version
05.1037.40CDA
05.1037.14CDA
Mains Dimming
05.1037.40CNI
05.1037.14CNI
Casambi
05.1037.40CCB
05.1037.14CCB



WIDE FLOOD



Luminous flux luminaire 545 lm

Beam Angle: 45°


h(m)	E(lx)	D(m)
1	1089	0.83
2	272	1.66
3	121	2.49
4	68	3.32
5	44	4.14

@White (40)

Light Shadow Fixed Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272 lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

* Multipack available.

E= External Finish
I= Internal Finish

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

* Embalaje múltiple disponible.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable

03.8828.40C
03.8828.14C

Dali Version

03.8828.40CDA
03.8828.14CDA

Mains Dimming

03.8828.40CNI
03.8828.14CNI

Casambi

03.8828.40CCB
03.8828.14CCB

Non Dimmable

03.8829.40C
03.8829.14C

Dali Version

03.8829.40CDA
03.8829.14CDA

Mains Dimming

03.8829.40CNI
03.8829.14CNI

Casambi

03.8829.40CCB
03.8829.14CCB

Non Dimmable

05.1101.40C
05.1101.14C

Dali Version

05.1101.40CDA
05.1101.14CDA

Mains Dimming

05.1101.40CNI
05.1101.14CNI

Casambi

05.1101.40CCB
05.1101.14CCB

Non Dimmable

05.1102.40C
05.1102.14C

Dali Version


05.1102.40CDA
05.1102.14CDA

Mains Dimming

05.1102.40CNI
05.1102.14CNI

Casambi

05.1102.40CCB
05.1102.14CCB



Beam Angle: 12°

h(m)	E(lx)	D(m)
1	17109	0.20
2	4277	0.41
3	1901	0.61
4	1069	0.81
5	684	1.01

Optic Spot 3000K

E I Non Dimmable

03.8832.40C
03.8832.14C

Dali Version

03.8832.40CDA
03.8832.14CDA

Mains Dimming

03.8832.40CNI
03.8832.14CNI

Casambi

03.8832.40CCB
03.8832.14CCB

Non Dimmable

03.8833.40C
03.8833.14C

Dali Version

03.8833.40CDA
03.8833.14CDA

Mains Dimming

03.8833.40CNI
03.8833.14CNI

Casambi

03.8833.40CCB
03.8833.14CCB

Non Dimmable

05.1106.40C
05.1106.14C

Dali Version

05.1106.40CDA
05.1106.14CDA

Mains Dimming

05.1106.40CNI
05.1106.14CNI

Casambi

05.1106.40CCB
05.1106.14CCB

Non Dimmable

05.1107.40C
05.1107.14C

Dali Version


05.1107.40CDA
05.1107.14CDA

Mains Dimming

05.1107.40CNI
05.1107.14CNI

Casambi

05.1107.40CCB
05.1107.14CCB



Beam Angle: 12°

h(m)	E(lx)	D(m)
1	18255	0.20
2	4564	0.41
3	2028	0.61
4	1141	0.81
5	730	1.01

Optic Medium 2700K

E I

Non Dimmable
03.9120.40C
03.9120.14C

Dali Version
03.9120.40CDA
03.9120.14CDA

Mains Dimming
03.9120.40CNI
03.9120.14CNI

Casambi
03.9120.40CCB
03.9120.14CCB

Non Dimmable
03.9121.40C
03.9121.14C

Dali Version
03.9121.40CDA
03.9121.14CDA

Mains Dimming
03.9121.40CNI
03.9121.14CNI

Casambi
03.9121.40CCB
03.9121.14CCB

Non Dimmable
05.1111.40C
05.1111.14C

Dali Version
05.1111.40CDA
05.1111.14CDA

Mains Dimming
05.1111.40CNI
05.1111.14CNI

Casambi
05.1111.40CCB
05.1111.14CCB


Non Dimmable
05.1112.40C
05.1112.14C

Dali Version
05.1112.40CDA
05.1112.14CDA

Mains Dimming
05.1112.40CNI
05.1112.14CNI

Casambi
05.1112.40CCB
05.1112.14CCB





Luminous flux luminaire
1020 lm

@White (40)

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	6846	0.40
2	1711	0.80
3	761	1.20
4	428	1.60
5	274	2.00

Optic Medium 3000K

E I

Non Dimmable
03.9130.40C
03.9130.14C

Dali Version
03.9130.40CDA
03.9130.14CDA

Mains Dimming
03.9130.40CNI
03.9130.14CNI

Casambi
03.9130.40CCB
03.9130.14CCB

Non Dimmable
03.9131.40C
03.9131.14C

Dali Version
03.9131.40CDA
03.9131.14CDA

Mains Dimming
03.9131.40CNI
03.9131.14CNI

Casambi
03.9131.40CCB
03.9131.14CCB

Non Dimmable
05.1116.40C
05.1116.14C

Dali Version
05.1116.40CDA
05.1116.14CDA

Mains Dimming
05.1116.40CNI
05.1116.14CNI

Casambi
05.1116.40CCB
05.1116.14CCB


Non Dimmable
05.1117.40C
05.1117.14C

Dali Version
05.1117.40CDA
05.1117.14CDA

Mains Dimming
05.1117.40CNI
05.1117.14CNI

Casambi
05.1117.40CCB
05.1117.14CCB





Luminous flux luminaire
1088 lm

@White (40)

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	7302	0.40
2	1826	0.80
3	811	1.20
4	456	1.60
5	292	2.00


*Multipack available (14 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.8828.40A - M3.8828.40A

*Embalaje múltiple disponible (14 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.8828.40A - M3.8828.40A

Light Shadow Fixed Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272 lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

* Multipack available.

E= External Finish
I= Internal Finish

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

* Embalaje múltiple disponible.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable

03.9125.40C
03.9125.14C

Dali Version

03.9125.40CDA
03.9125.14CDA

Mains Dimming

03.9125.40CNI
03.9125.14CNI

Casambi

03.9125.40CCB
03.9125.14CCB

Non Dimmable

03.9126.40C
03.9126.14C

Dali Version

03.9126.40CDA
03.9126.14CDA

Mains Dimming

03.9126.40CNI
03.9126.14CNI

Casambi

03.9126.40CCB
03.9126.14CCB

Non Dimmable

05.1121.40C
05.1121.14C

Dali Version

05.1121.40CDA
05.1121.14CDA

Mains Dimming

05.1121.40CNI
05.1121.14CNI

Casambi

05.1121.40CCB
05.1121.14CCB

Non Dimmable

05.1122.40C
05.1122.14C

Dali Version

05.1122.40CDA
05.1122.14CDA


Mains Dimming

05.1122.40CNI
05.1122.14CNI

Casambi

05.1122.40CCB
05.1122.14CCB

29°
FLOOD



Luminous flux luminaire
1029 lm

@White (40)

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	4143	0.51
2	1036	1.03
3	460	1.54
4	259	2.05
5	166	2.57

Optic Flood 3000K

E I Non Dimmable

03.9135.40C
03.9135.14C

Dali Version

03.9135.40CDA
03.9135.14CDA

Mains Dimming

03.9135.40CNI
03.9135.14CNI

Casambi

03.9135.40CCB
03.9135.14CCB

Non Dimmable

03.9136.40C
03.9136.14C

Dali Version

03.9136.40CDA
03.9136.14CDA

Mains Dimming

03.9136.40CNI
03.9136.14CNI

Casambi

03.9136.40CCB
03.9136.14CCB

Non Dimmable

05.1126.40C
05.1126.14C

Dali Version

05.1126.40CDA
05.1126.14CDA

Mains Dimming

05.1126.40CNI
05.1126.14CNI

Casambi

05.1126.40CCB
05.1126.14CCB

Non Dimmable

05.1127.40C
05.1127.14C

Dali Version

05.1127.40CDA
05.1127.14CDA


Mains Dimming

05.1127.40CNI
05.1127.14CNI

Casambi

05.1127.40CCB
05.1127.14CCB

29°
FLOOD



Luminous flux luminaire
1098 lm

@White (40)

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	4421	0.51
2	1105	1.03
3	491	1.54
4	276	2.05
5	177	2.57

Optic Wide Flood 2700K

E I

Non Dimmable
03.8308.40C
03.8308.14C

Dali Version
03.8308.40CDA
03.8308.14CDA

Mains Dimming
03.8308.40CNI
03.8308.14CNI

Casambi
03.8308.40CCB
03.8308.14CCB

Non Dimmable
03.8309.40C
03.8309.14C

Dali Version
03.8309.40CDA
03.8309.14CDA

Mains Dimming
03.8309.40CNI
03.8309.14CNI

Casambi
03.8309.40CCB
03.8309.14CCB

Non Dimmable
05.1131.40C
05.1131.14C

Dali Version
05.1131.40CDA
05.1131.14CDA

Mains Dimming
05.1131.40CNI
05.1131.14CNI

Casambi
05.1131.40CCB
05.1131.14CCB

Non Dimmable
05.1132.40C
05.1132.14C


Dali Version
05.1132.40CDA
05.1132.14CDA

Mains Dimming
05.1132.40CNI
05.1132.14CNI

Casambi
05.1132.40CCB
05.1132.14CCB



WIDE FLOOD



Luminous flux luminaire 1022 lm

@White (40)

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	2042	0.83
2	511	1.66
3	227	2.49
4	128	3.32
5	82	4.14

Optic Wide Flood 3000K

E I

Non Dimmable
03.8312.40C
03.8312.14C

Dali Version
03.8312.40CDA
03.8312.14CDA

Mains Dimming
03.8312.40CNI
03.8312.14CNI

Casambi
03.8312.40CCB
03.8312.14CCB

Non Dimmable
03.8313.40C
03.8313.14C

Dali Version
03.8313.40CDA
03.8313.14CDA

Mains Dimming
03.8313.40CNI
03.8313.14CNI

Casambi
03.8313.40CCB
03.8313.14CCB

Non Dimmable
05.1136.40C
05.1136.14C

Dali Version
05.1136.40CDA
05.1136.14CDA

Mains Dimming
05.1136.40CNI
05.1136.14CNI

Casambi
05.1136.40CCB
05.1136.14CCB

Non Dimmable
05.1137.40C
05.1137.14C


Dali Version
05.1137.40CDA
05.1137.14CDA

Mains Dimming
05.1137.40CNI
05.1137.14CNI

Casambi
05.1137.40CCB
05.1137.14CCB



WIDE FLOOD



Luminous flux luminaire 1091 lm

@White (40)

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	2180	0.83
2	545	1.66
3	242	2.49
4	136	3.32
5	87	4.14


*Multipack available (14 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.8828.40A - M3.8828.40A

*Embalaje múltiple disponible (14 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.8828.40A - M3.8828.40A

Light Shadow Fixed Trim 4 Spots Square

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272 lm - 3000K/CRI 90






GWT 850°




0.34 Kg




10 - 100%
DALI


h=75 min




LED INCL.



IP 55

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

E= External Finish
I= Internal Finish

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable

05.0600.40C
05.0600.14C

Dali Version
05.0600.40CDA
05.0600.14CDA

Mains Dimming
05.0600.40CNI
05.0600.14CNI

Casambi
05.0600.40CCB
05.0600.14CCB

Non Dimmable
05.0601.40C
05.0601.14C

Dali Version
05.0601.40CDA
05.0601.14CDA

Mains Dimming
05.0601.40CNI
05.0601.14CNI

Casambi
05.0601.40CCB
05.0601.14CCB

Non Dimmable
05.0604.40C
05.0604.14C

Dali Version
05.0604.40CDA
05.0604.14CDA

Mains Dimming
05.0604.40CNI
05.0604.14CNI

Casambi
05.0604.40CCB
05.0604.14CCB


Non Dimmable
05.0602.40C
05.0602.14C

Dali Version
05.0602.40CDA
05.0602.14CDA

Mains Dimming
05.0602.40CNI
05.0602.14CNI

Casambi
05.0602.40CCB
05.0602.14CCB





Luminous flux luminaire
982 lm

@White (40)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	17815	0.20
2	4454	0.40
3	1979	0.60
4	1113	0.80
5	713	1.00

Optic Spot 3000K

E I Non Dimmable

05.0605.40C
05.0605.14C

Dali Version
05.0605.40CDA
05.0605.14CDA

Mains Dimming
05.0605.40CNI
05.0605.14CNI

Casambi
05.0605.40CCB
05.0605.14CCB

Non Dimmable
05.0606.40C
05.0606.14C

Dali Version
05.0606.40CDA
05.0606.14CDA

Mains Dimming
05.0606.40CNI
05.0606.14CNI

Casambi
05.0606.40CCB
05.0606.14CCB

Non Dimmable
05.0609.40C
05.0609.14C

Dali Version
05.0609.40CDA
05.0609.14CDA

Mains Dimming
05.0609.40CNI
05.0609.14CNI

Casambi
05.0609.40CCB
05.0609.14CCB


Non Dimmable
05.0607.40C
05.0607.14C

Dali Version
05.0607.40CDA
05.0607.14CDA

Mains Dimming
05.0607.40CNI
05.0607.14CNI

Casambi
05.0607.40CCB
05.0607.14CCB





Luminous flux luminaire
1077 lm


@White (40)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	19539	0.20
2	4885	0.40
3	2171	0.60
4	1221	0.80
5	782	1.00

Optic Medium
2700K

E I Non Dimmable
05.0610.40C
05.0610.14C
Dali Version
05.0610.40CDA
05.0610.14CDA
Mains Dimming
05.0610.40CNI
05.0610.14CNI
Casambi
05.0610.40CCB
05.0610.14CCB
Non Dimmable
05.0611.40C
05.0611.14C
Dali Version
05.0611.40CDA
05.0611.14CDA
Mains Dimming
05.0611.40CNI
05.0611.14CNI
Casambi
05.0611.40CCB
05.0611.14CCB
Non Dimmable
05.0614.40C
05.0614.14C
Dali Version
05.0614.40CDA
05.0614.14CDA
Mains Dimming
05.0614.40CNI
05.0614.14CNI
Casambi
05.0614.40CCB
05.0614.14CCB
Non Dimmable
05.0612.40C
05.0612.14C
Dali Version
05.0612.40CDA
05.0612.14CDA
Mains Dimming
05.0612.40CNI
05.0612.14CNI
Casambi
05.0612.40CCB
05.0612.14CCB




Luminous flux luminaire
978 lm

@White (40)

Beam Angle:		25°
h(m)	E(lx)	D(m)
1	5628	0.44
2	1407	0.88
3	625	1.31
4	352	1.75
5	225	2.19

Optic Medium
3000K

E I Non Dimmable
05.0615.40C
05.0615.14C
Dali Version
05.0615.40CDA
05.0615.14CDA
Mains Dimming
05.0615.40CNI
05.0615.14CNI
Casambi
05.0615.40CCB
05.0615.14CCB
Non Dimmable
05.0616.40C
05.0616.14C
Dali Version
05.0616.40CDA
05.0616.14CDA
Mains Dimming
05.0616.40CNI
05.0616.14CNI
Casambi
05.0616.40CCB
05.0616.14CCB
Non Dimmable
05.0619.40C
05.0619.14C
Dali Version
05.0619.40CDA
05.0619.14CDA
Mains Dimming
05.0619.40CNI
05.0619.14CNI
Casambi
05.0619.40CCB
05.0619.14CCB
Non Dimmable
05.0617.40C
05.0617.14C
Dali Version
05.0617.40CDA
05.0617.14CDA
Mains Dimming
05.0617.40CNI
05.0617.14CNI
Casambi
05.0617.40CCB
05.0617.14CCB



Luminous flux luminaire
1072 lm


@White (40)

Beam Angle:		25°
h(m)	E(lx)	D(m)
1	6169	0.44
2	1542	0.88
3	685	1.31
4	386	1.75
5	247	2.19

Light Shadow Fixed Trim 4 Spots Square

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272 lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

E= External Finish
I= Internal Finish

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable

05.0620.40C
05.0620.14C

Dali Version

05.0620.40CDA
05.0620.14CDA

Mains Dimming

05.0620.40CNI
05.0620.14CNI

Casambi

05.0620.40CCB
05.0620.14CCB

Non Dimmable

05.0621.40C
05.0621.14C

Dali Version

05.0621.40CDA
05.0621.14CDA

Mains Dimming

05.0621.40CNI
05.0621.14CNI

Casambi

05.0621.40CCB
05.0621.14CCB

Non Dimmable

05.0624.40C
05.0624.14C

Dali Version

05.0624.40CDA
05.0624.14CDA

Mains Dimming

05.0624.40CNI
05.0624.14CNI

Casambi

05.0624.40CCB
05.0624.14CCB

Non Dimmable

05.0622.40C
05.0622.14C

Dali Version

05.0622.40CDA
05.0622.14CDA


Mains Dimming

05.0622.40CNI
05.0622.14CNI

Casambi

05.0622.40CCB
05.0622.14CCB

35°
FLOOD



Luminous flux luminaire
961 lm

@White (40)

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	2752	0.63
2	688	1.27
3	306	1.90
4	172	2.54
5	110	3.17

Optic Flood 3000K

E I Non Dimmable

05.0625.40C
05.0625.14C

Dali Version

05.0625.40CDA
05.0625.14CDA

Mains Dimming

05.0625.40CNI
05.0625.14CNI

Casambi

05.0625.40CCB
05.0625.14CCB

Non Dimmable

05.0626.40C
05.0626.14C

Dali Version

05.0626.40CDA
05.0626.14CDA

Mains Dimming

05.0626.40CNI
05.0626.14CNI

Casambi

05.0626.40CCB
05.0626.14CCB

Non Dimmable

05.0629.40C
05.0629.14C

Dali Version

05.0629.40CDA
05.0629.14CDA

Mains Dimming

05.0629.40CNI
05.0629.14CNI

Casambi

05.0629.40CCB
05.0629.14CCB

Non Dimmable

05.0627.40C
05.0627.14C

Dali Version

05.0627.40CDA
05.0627.14CDA


Mains Dimming

05.0627.40CNI
05.0627.14CNI

Casambi

05.0627.40CCB
05.0627.14CCB

35°
FLOOD



Luminous flux luminaire
1054 lm

@White (40)


Beam Angle: 35°

h(m)	E(lx)	D(m)
1	3018	0.63
2	755	1.27
3	335	1.90
4	189	2.54
5	121	3.17

Optic Wide Flood
2700K

E I Non Dimmable
05.0630.40C
05.0630.14C
Dali Version
05.0630.40CDA
05.0630.14CDA
Mains Dimming
05.0630.40CNI
05.0630.14CNI
Casambi
05.0630.40CCB
05.0630.14CCB
Non Dimmable
05.0631.40C
05.0631.14C
Dali Version
05.0631.40CDA
05.0631.14CDA
Mains Dimming
05.0631.40CNI
05.0631.14CNI
Casambi
05.0631.40CCB
05.0631.14CCB
Non Dimmable
05.0634.40C
05.0634.14C
Dali Version
05.0634.40CDA
05.0634.14CDA
Mains Dimming
05.0634.40CNI
05.0634.14CNI
Casambi
05.0634.40CCB
05.0634.14CCB
Non Dimmable
05.0632.40C
05.0632.14C
Dali Version
05.0632.40CDA
05.0632.14CDA
Mains Dimming
05.0632.40CNI
05.0632.14CNI
Casambi
05.0632.40CCB
05.0632.14CCB





Luminous flux luminaire
962 lm

@White (40)


Beam Angle: 49°

h(m)	E(lx)	D(m)
1	1564	0.90
2	391	1.81
3	174	2.71
4	98	3.62
5	63	4.52

Optic Wide Flood
3000K

E I Non Dimmable
05.0635.40C
05.0635.14C
Dali Version
05.0635.40CDA
05.0635.14CDA
Mains Dimming
05.0635.40CNI
05.0635.14CNI
Casambi
05.0635.40CCB
05.0635.14CCB
Non Dimmable
05.0636.40C
05.0636.14C
Dali Version
05.0636.40CDA
05.0636.14CDA
Mains Dimming
05.0636.40CNI
05.0636.14CNI
Casambi
05.0636.40CCB
05.0636.14CCB
Non Dimmable
05.0639.40C
05.0639.14C
Dali Version
05.0639.40CDA
05.0639.14CDA
Mains Dimming
05.0639.40CNI
05.0639.14CNI
Casambi
05.0639.40CCB
05.0639.14CCB
Non Dimmable
05.0637.40C
05.0637.14C
Dali Version
05.0637.40CDA
05.0637.14CDA
Mains Dimming
05.0637.40CNI
05.0637.14CNI
Casambi
05.0637.40CCB
05.0637.14CCB





Luminous flux luminaire
1055 lm

@White (40)


Beam Angle: 49°


h(m)	E(lx)	D(m)
1	1715	0.90
2	429	1.81
3	191	2.71
4	107	3.62
5	69	4.52

Light Shadow Fixed Trim 8 Spots

Power LED DC 900 mA 21,6W - 2384 lm - 2700K/CRI 90 / 21,6W - 2544 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 18,6W - 1984 lm - 2700K/CRI 90 / 18,6W - 2120 lm - 3000K/CRI 90







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

* Multipack available.

E= External Finish
I= Internal Finish

Luminaria empotrable de 8 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

* Embalaje múltiple disponible.


E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable

03.8836.40C
03.8836.14C
Dali Version
03.8836.40CDA
03.8836.14CDA
Mains Dimming
03.8836.40CNI
03.8836.14CNI
Casambi
03.8836.40CCB
03.8836.14CCB
Non Dimmable
03.8837.40C
03.8837.14C
Dali Version
03.8837.40CDA
03.8837.14CDA
Mains Dimming
03.8837.40CNI
03.8837.14CNI
Casambi
03.8837.40CCB
03.8837.14CCB
Non Dimmable
05.1201.40C
05.1201.14C
Dali Version
05.1201.40CDA
05.1201.14CDA
Mains Dimming
05.1201.40CNI
05.1201.14CNI
Casambi
05.1201.40CCB
05.1201.14CCB
Non Dimmable
05.1202.40C
05.1202.14C
Dali Version
05.1202.40CDA
05.1202.14CDA
Mains Dimming
05.1202.40CNI
05.1202.14CNI
Casambi
05.1202.40CCB
05.1202.14CCB

12° SPOT




Luminous flux luminaire 2120 lm

@White (40) 900mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	34219	0.20
2	8555	0.41
3	3802	0.61
4	2139	0.81
5	1369	1.01

12° SPOT



Luminous flux luminaire 1800 lm

@White (40) 750mA


Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	29054	0.20
2	7263	0.41
3	3228	0.61
4	1816	0.81
5	1162	1.01

Optic Spot 3000K

E I Non Dimmable

03.8840.40C
03.8840.14C
Dali Version
03.8840.40CDA
03.8840.14CDA
Mains Dimming
03.8840.40CNI
03.8840.14CNI
Casambi
03.8840.40CCB
03.8840.14CCB
Non Dimmable
03.8841.40C
03.8841.14C
Dali Version
03.8841.40CDA
03.8841.14CDA
Mains Dimming
03.8841.40CNI
03.8841.14CNI
Casambi
03.8841.40CCB
03.8841.14CCB
Non Dimmable
05.1206.40C
05.1206.14C
Dali Version
05.1206.40CDA
05.1206.14CDA
Mains Dimming
05.1206.40CNI
05.1206.14CNI
Casambi
05.1206.40CCB
05.1206.14CCB
Non Dimmable
05.1207.40C
05.1207.14C
Dali Version
05.1207.40CDA
05.1207.14CDA
Mains Dimming
05.1207.40CNI
05.1207.14CNI
Casambi
05.1207.40CCB
05.1207.14CCB

12° SPOT




Luminous flux luminaire 2262 lm

@White (40) 900mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	36511	0.20
2	9128	0.41
3	4057	0.61
4	2282	0.81
5	1460	1.01

12° SPOT



Luminous flux luminaire 2020 lm

@White (40) 750mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	32605	0.20
2	8151	0.41
3	3623	0.61
4	2038	0.81
5	1304	1.01

Optic Medium 2700K

E I

Non Dimmable
03.9140.40C
03.9140.14C

Dali Version
03.9140.40CDA
03.9140.14CDA

Mains Dimming
03.9140.40CNI
03.9140.14CNI

Casambi
03.9140.40CCB
03.9140.14CCB

Non Dimmable
03.9141.40C
03.9141.14C

Dali Version
03.9141.40CDA
03.9141.14CDA

Mains Dimming
03.9141.40CNI
03.9141.14CNI

Casambi
03.9141.40CCB
03.9141.14CCB

Non Dimmable
05.1211.40C
05.1211.14C

Dali Version
05.1211.40CDA
05.1211.14CDA

Mains Dimming
05.1211.40CNI
05.1211.14CNI

Casambi
05.1211.40CCB
05.1211.14CCB


Non Dimmable
05.1212.40C
05.1212.14C

Dali Version
05.1212.40CDA
05.1212.14CDA

Mains Dimming
05.1212.40CNI
05.1212.14CNI

Casambi
05.1212.40CCB
05.1212.14CCB

23°
MEDIUM




Luminous flux luminaire
2040 lm

@White (40) 900mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	13692	0.40
2	3423	0.80
3	1521	1.20
4	856	1.60
5	548	2.00

23°
MEDIUM



Luminous flux luminaire
1732 lm

@White (40) 750mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	11625	0.40
2	2906	0.80
3	1292	1.20
4	727	1.60
5	465	2.00

Optic Medium 3000K

E I

Non Dimmable
03.9150.40C
03.9150.14C

Dali Version
03.9150.40CDA
03.9150.14CDA

Mains Dimming
03.9150.40CNI
03.9150.14CNI

Casambi
03.9150.40CCB
03.9150.14CCB

Non Dimmable
03.9151.40C
03.9151.14C

Dali Version
03.9151.40CDA
03.9151.14CDA

Mains Dimming
03.9151.40CNI
03.9151.14CNI

Casambi
03.9151.40CCB
03.9151.14CCB

Non Dimmable
05.1216.40C
05.1216.14C

Dali Version
05.1216.40CDA
05.1216.14CDA

Mains Dimming
05.1216.40CNI
05.1216.14CNI

Casambi
05.1216.40CCB
05.1216.14CCB


Non Dimmable
05.1217.40C
05.1217.14C

Dali Version
05.1217.40CDA
05.1217.14CDA

Mains Dimming
05.1217.40CNI
05.1217.14CNI

Casambi
05.1217.40CCB
05.1217.14CCB

23°
MEDIUM




Luminous flux luminaire
2177 lm

@White (40) 900mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	14611	0.40
2	3653	0.80
3	1623	1.20
4	913	1.60
5	584	2.00

23°
MEDIUM



Luminous flux luminaire
1944 lm

@White (40) 750mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	13047	0.40
2	3262	0.80
3	1450	1.20
4	815	1.60
5	522	2.00


*Multipack available (12 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.8828.40A - M3.8828.40A


*Embalaje múltiple disponible (12 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.8828.40A - M3.8828.40A

Light Shadow Fixed Trim 8 Spots

Power LED DC 900 mA 21,6W - 2384 lm - 2700K/CRI 90 / 21,6W - 2544 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 18,6W - 1984 lm - 2700K/CRI 90 / 18,6W - 2120 lm - 3000K/CRI 90







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

* Multipack available.

E= External Finish
I= Internal Finish

Luminaria empotrable de 8 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.


* Embalaje múltiple disponible.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9145.40C
03.9145.14C
Dali Version
03.9145.40CDA
03.9145.14CDA
Mains Dimming
03.9145.40CNI
03.9145.14CNI
Casambi
03.9145.40CCB
03.9145.14CCB
Non Dimmable
03.9146.40C
03.9146.14C
Dali Version
03.9146.40CDA
03.9146.14CDA
Mains Dimming
03.9146.40CNI
03.9146.14CNI
Casambi
03.9146.40CCB
03.9146.14CCB
Non Dimmable
05.1221.40C
05.1221.14C
Dali Version
05.1221.40CDA
05.1221.14CDA
Mains Dimming
05.1221.40CNI
05.1221.14CNI
Casambi
05.1221.40CCB
05.1221.14CCB
Non Dimmable
05.1222.40C
05.1222.14C
Dali Version
05.1222.40CDA
05.1222.14CDA
Mains Dimming
05.1222.40CNI
05.1222.14CNI
Casambi
05.1222.40CCB
05.1222.14CCB


29° FLOOD



Luminous flux luminaire 2057 lm
@White (40) 900mA

Beam Angle:		29°
h(m)	E(lx)	D(m)
1	8282	0.51
2	2071	1.03
3	920	1.54
4	518	2.05
5	331	2.57

29° FLOOD




Luminous flux luminaire 1747 lm
@White (40) 750mA

Beam Angle:		29°
h(m)	E(lx)	D(m)
1	7034	0.51
2	1759	1.03
3	782	1.54
4	440	2.05
5	281	2.57

Optic Flood 3000K

E I Non Dimmable
03.9155.40C
03.9155.14C
Dali Version
03.9155.40CDA
03.9155.14CDA
Mains Dimming
03.9155.40CNI
03.9155.14CNI
Casambi
03.9155.40CCB
03.9155.14CCB
Non Dimmable
03.9156.40C
03.9156.14C
Dali Version
03.9156.40CDA
03.9156.14CDA
Mains Dimming
03.9156.40CNI
03.9156.14CNI
Casambi
03.9156.40CCB
03.9156.14CCB
Non Dimmable
05.1226.40C
05.1226.14C
Dali Version
05.1226.40CDA
05.1226.14CDA
Mains Dimming
05.1226.40CNI
05.1226.14CNI
Casambi
05.1226.40CCB
05.1226.14CCB
Non Dimmable
05.1227.40C
05.1227.14C
Dali Version
05.1227.40CDA
05.1227.14CDA
Mains Dimming
05.1227.40CNI
05.1227.14CNI
Casambi
05.1227.40CCB
05.1227.14CCB


29° FLOOD



Luminous flux luminaire 2195 lm
@White (40) 900mA

Beam Angle:		29°
h(m)	E(lx)	D(m)
1	8838	0.51
2	2210	1.03
3	982	1.54
4	552	2.05
5	354	2.57

29° FLOOD



Luminous flux luminaire 1961 lm
@White (40) 750mA

Beam Angle:		29°
h(m)	E(lx)	D(m)
1	7896	0.51
2	1974	1.03
3	877	1.54
4	493	2.05
5	316	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.8316.40C
03.8316.14C

Dali Version

03.8316.40CDA
03.8316.14CDA

Mains Dimming

03.8316.40CNI
03.8316.14CNI

Casambi

03.8316.40CCB
03.8316.14CCB

Non Dimmable

03.8317.40C
03.8317.14C

Dali Version

03.8317.40CDA
03.8317.14CDA

Mains Dimming

03.8317.40CNI
03.8317.14CNI

Casambi

03.8317.40CCB
03.8317.14CCB

Non Dimmable

05.1231.40C
05.1231.14C

Dali Version

05.1231.40CDA
05.1231.14CDA

Mains Dimming

05.1231.40CNI
05.1231.14CNI

Casambi

05.1231.40CCB
05.1231.14CCB

Non Dimmable

05.1232.40C
05.1232.14C

Dali Version

05.1232.40CDA
05.1232.14CDA


Mains Dimming

05.1232.40CNI
05.1232.14CNI

Casambi

05.1232.40CCB
05.1232.14CCB

45°
WIDE FLOOD




Luminous flux luminaire
2044 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	4085	0.83
2	1021	1.66
3	454	2.49
4	255	3.32
5	163	4.14

45°
WIDE FLOOD



Luminous flux luminaire
1736 lm

@White (40) 750mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	3469	0.83
2	867	1.66
3	385	2.49
4	217	3.32
5	139	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.8320.40C
03.8320.14C

Dali Version

03.8320.40CDA
03.8320.14CDA

Mains Dimming

03.8320.40CNI
03.8320.14CNI

Casambi

03.8320.40CCB
03.8320.14CCB

Non Dimmable

03.8321.40C
03.8321.14C

Dali Version

03.8321.40CDA
03.8321.14CDA

Mains Dimming

03.8321.40CNI
03.8321.14CNI

Casambi

03.8321.40CCB
03.8321.14CCB

Non Dimmable

05.1236.40C
05.1236.14C

Dali Version

05.1236.40CDA
05.1236.14CDA

Mains Dimming

05.1236.40CNI
05.1236.14CNI

Casambi

05.1236.40CCB
05.1236.14CCB

Non Dimmable

05.1237.40C
05.1237.14C

Dali Version

05.1237.40CDA
05.1237.14CDA


Mains Dimming

05.1237.40CNI
05.1237.14CNI

Casambi

05.1237.40CCB
05.1237.14CCB

45°
WIDE FLOOD




Luminous flux luminaire
2181 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	4358	0.83
2	1090	1.66
3	484	2.49
4	272	3.32
5	174	4.14

45°
WIDE FLOOD



Luminous flux luminaire
1948 lm

@White (40) 750mA


Beam Angle:		45°
h(m)	E(lx)	D(m)
1	3893	0.83
2	973	1.66
3	433	2.49
4	243	3.32
5	156	4.14


*Multipack available (12 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.8828.40A - M3.8828.40A
*Embalaje múltiple disponible (12 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.8828.40A - M3.8828.40A

Light Shadow Fixed Trim 12 Spots

Power LED DC 900 mA 32,4W - 3576 lm - 2700K/CRI 90 / 32,4W - 3816 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 28W - 2976 lm - 2700K/CRI 90 / 28W - 3180 lm - 3000K/CRI 90







Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 12 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8844.40C
03.8844.14C
Dali & Push Version
03.8844.40CDA
03.8844.14CDA
Mains Dimming
03.8844.40CNI
03.8844.14CNI
Casambi
03.8844.40CCB
03.8844.14CCB
Non Dimmable
03.8845.40C
03.8845.14C
Dali & Push Version
03.8845.40CDA
03.8845.14CDA
Mains Dimming
03.8845.40CNI
03.8845.14CNI
Casambi
03.8845.40CCB
03.8845.14CCB
Non Dimmable
05.1301.40C
05.1301.14C
Dali & Push Version
05.1301.40CDA
05.1301.14CDA
Mains Dimming
05.1301.40CNI
05.1301.14CNI
Casambi
05.1301.40CCB
05.1301.14CCB
Non Dimmable
05.1302.40C
05.1302.14C
Dali & Push Version
05.1302.40CDA
05.1302.14CDA
Mains Dimming
05.1302.40CNI
05.1302.14CNI
Casambi
05.1302.40CCB
05.1302.14CCB

12° SPOT




Luminous flux luminaire 3180 lm

@White (40) 900mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	51328	0.20
2	12832	0.41
3	5703	0.61
4	3208	0.81
5	2053	1.01

12° SPOT



Luminous flux luminaire 2849 lm


@White (40) 750mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	45985	0.20
2	11496	0.41
3	5109	0.61
4	2874	0.81
5	1839	1.01

Optic Spot 3000K

E I Non Dimmable
03.8848.40C
03.8848.14C
Dali & Push Version
03.8848.40CDA
03.8848.14CDA
Mains Dimming
03.8848.40CNI
03.8848.14CNI
Casambi
03.8848.40CCB
03.8848.14CCB
Non Dimmable
03.8849.40C
03.8849.14C
Dali & Push Version
03.8849.40CDA
03.8849.14CDA
Mains Dimming
03.8849.40CNI
03.8849.14CNI
Casambi
03.8849.40CCB
03.8849.14CCB
Non Dimmable
05.1306.40C
05.1306.14C
Dali & Push Version
05.1306.40CDA
05.1306.14CDA
Mains Dimming
05.1306.40CNI
05.1306.14CNI
Casambi
05.1306.40CCB
05.1306.14CCB
Non Dimmable
05.1307.40C
05.1307.14C
Dali & Push Version
05.1307.40CDA
05.1307.14CDA
Mains Dimming
05.1307.40CNI
05.1307.14CNI
Casambi
05.1307.40CCB
05.1307.14CCB

12° SPOT




Luminous flux luminaire 3394 lm

@White (40) 900mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	54782	0.20
2	13696	0.41
3	6087	0.61
4	3424	0.81
5	2191	1.01

12° SPOT



Luminous flux luminaire 3031 lm

@White (40) 750mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	48923	0.20
2	12231	0.41
3	5436	0.61
4	3058	0.81
5	1957	1.01

Optic Medium 2700K

E I Non Dimmable

03.9160.40C
03.9160.14C

Dali & Push Version

03.9160.40CDA
03.9160.14CDA

Mains Dimming

03.9160.40CNI
03.9160.14CNI

Casambi

03.9160.40CCB
03.9160.14CCB

Non Dimmable

03.9161.40C
03.9161.14C

Dali & Push Version

03.9161.40CDA
03.9161.14CDA

Mains Dimming

03.9161.40CNI
03.9161.14CNI

Casambi

03.9161.40CCB
03.9161.14CCB

Non Dimmable

05.1311.40C
05.1311.14C

Dali & Push Version

05.1311.40CDA
05.1311.14CDA

Mains Dimming

05.1311.40CNI
05.1311.14CNI

Casambi

05.1311.40CCB
05.1311.14CCB

Non Dimmable

05.1312.40C
05.1312.14C

Dali & Push Version

05.1312.40CDA
05.1312.14CDA


Mains Dimming

05.1312.40CNI
05.1312.14CNI

Casambi

05.1312.40CCB
05.1312.14CCB

23°
MEDIUM




Luminous flux luminaire
3060 lm

@White (40) 900mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	20538	0.40
2	5134	0.80
3	2282	1.20
4	1284	1.60
5	822	2.00

23°
MEDIUM



Luminous flux luminaire
2742 lm

@White (40) 750mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	18403	0.40
2	4601	0.80
3	2045	1.20
4	1150	1.60
5	736	2.00

Optic Medium 3000K

E I Non Dimmable

03.9170.40C
03.9170.14C

Dali & Push Version

03.9170.40CDA
03.9170.14CDA

Mains Dimming

03.9170.40CNI
03.9170.14CNI

Casambi

03.9170.40CCB
03.9170.14CCB

Non Dimmable

03.9171.40C
03.9171.14C

Dali & Push Version

03.9171.40CDA
03.9171.14CDA

Mains Dimming

03.9171.40CNI
03.9171.14CNI

Casambi

03.9171.40CCB
03.9171.14CCB

Non Dimmable

05.1316.40C
05.1316.14C

Dali & Push Version

05.1316.40CDA
05.1316.14CDA

Mains Dimming

05.1316.40CNI
05.1316.14CNI

Casambi

05.1316.40CCB
05.1316.14CCB

Non Dimmable

05.1317.40C
05.1317.14C

Dali & Push Version

05.1317.40CDA
05.1317.14CDA


Mains Dimming

05.1317.40CNI
05.1317.14CNI

Casambi

05.1317.40CCB
05.1317.14CCB

23°
MEDIUM




Luminous flux luminaire
3265 lm

@White (40) 900mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	21913	0.40
2	5478	0.80
3	2435	1.20
4	1370	1.60
5	877	2.00

23°
MEDIUM



Luminous flux luminaire
2916 lm

@White (40) 750mA


Beam Angle: 23°


h(m)	E(lx)	D(m)
1	19571	0.40
2	4893	0.80
3	2175	1.20
4	1223	1.60
5	783	2.00

Light Shadow Fixed Trim 12 Spots

Power LED DC 900 mA 32,4W - 3576 lm - 2700K/CRI 90 / 32,4W - 3816 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 28W - 2976 lm - 2700K/CRI 90 / 28W - 3180 lm - 3000K/CRI 90







Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 12 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9165.40C
03.9165.14C
Dali & Push Version
03.9165.40CDA
03.9165.14CDA
Mains Dimming
03.9165.40CNI
03.9165.14CNI
Casambi
03.9165.40CCB
03.9165.14CCB
Non Dimmable
03.9166.40C
03.9166.14C
Dali & Push Version
03.9166.40CDA
03.9166.14CDA
Mains Dimming
03.9166.40CNI
03.9166.14CNI
Casambi
03.9166.40CCB
03.9166.14CCB
Non Dimmable
05.1321.40C
05.1321.14C
Dali & Push Version
05.1321.40CDA
05.1321.14CDA
Mains Dimming
05.1321.40CNI
05.1321.14CNI
Casambi
05.1321.40CCB
05.1321.14CCB
Non Dimmable
05.1322.40C
05.1322.14C
Dali & Push Version
05.1322.40CDA
05.1322.14CDA
Mains Dimming
05.1322.40CNI
05.1322.14CNI
Casambi
05.1322.40CCB
05.1322.14CCB


29° FLOOD



Luminous flux luminaire 3086 lm
@White (40) 900mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	12426	0.51
2	3106	1.03
3	1381	1.54
4	777	2.05
5	497	2.57

29° FLOOD




Luminous flux luminaire 2765 lm
@White (40) 750mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	11133	0.51
2	2783	1.03
3	1237	1.54
4	696	2.05
5	445	2.57

Optic Flood 3000K

E I Non Dimmable
03.9175.40C
03.9175.14C
Dali & Push Version
03.9175.40CDA
03.9175.14CDA
Mains Dimming
03.9175.40CNI
03.9175.14CNI
Casambi
03.9175.40CCB
03.9175.14CCB
Non Dimmable
03.9176.40C
03.9176.14C
Dali & Push Version
03.9176.40CDA
03.9176.14CDA
Mains Dimming
03.9176.40CNI
03.9176.14CNI
Casambi
03.9176.40CCB
03.9176.14CCB
Non Dimmable
05.1326.40C
05.1326.14C
Dali & Push Version
05.1326.40CDA
05.1326.14CDA
Mains Dimming
05.1326.40CNI
05.1326.14CNI
Casambi
05.1326.40CCB
05.1326.14CCB
Non Dimmable
05.1327.40C
05.1327.14C
Dali & Push Version
05.1327.40CDA
05.1327.14CDA
Mains Dimming
05.1327.40CNI
05.1327.14CNI
Casambi
05.1327.40CCB
05.1327.14CCB


29° FLOOD



Luminous flux luminaire 3293 lm
@White (40) 900mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	13259	0.51
2	3315	1.03
3	1473	1.54
4	829	2.05
5	530	2.57

29° FLOOD



Luminous flux luminaire 2941 lm
@White (40) 750mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	11842	0.51
2	2960	1.03
3	1316	1.54
4	740	2.05
5	474	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.8324.40C
03.8324.14C

Dali & Push Version

03.8324.40CDA
03.8324.14CDA

Mains Dimming

03.8324.40CNI
03.8324.14CNI

Casambi

03.8324.40CCB
03.8324.14CCB

Non Dimmable

03.8325.40C
03.8325.14C

Dali & Push Version

03.8325.40CDA
03.8325.14CDA

Mains Dimming

03.8325.40CNI
03.8325.14CNI

Casambi

03.8325.40CCB
03.8325.14CCB

Non Dimmable

05.1331.40C
05.1331.14C

Dali & Push Version

05.1331.40CDA
05.1331.14CDA

Mains Dimming

05.1331.40CNI
05.1331.14CNI

Casambi

05.1331.40CCB
05.1331.14CCB

Non Dimmable

05.1332.40C
05.1332.14C

Dali & Push Version

05.1332.40CDA
05.1332.14CDA


Mains Dimming

05.1332.40CNI
05.1332.14CNI

Casambi

05.1332.40CCB
05.1332.14CCB

45° WIDE FLOOD




Luminous flux luminaire
3066 lm

@White (40) 900mA

Beam Angle:	45°
h(m)	E(lx) D(m)
1	6127 0.83
2	1532 1.66
3	681 2.49
4	383 3.32
5	245 4.14

45° WIDE FLOOD



Luminous flux luminaire
2747 lm

@White (40) 750mA

Beam Angle:	45°
h(m)	E(lx) D(m)
1	5490 0.83
2	1372 1.66
3	610 2.49
4	343 3.32
5	220 4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.8328.40C
03.8328.14C

Dali & Push Version

03.8328.40CDA
03.8328.14CDA

Mains Dimming

03.8328.40CNI
03.8328.14CNI

Casambi

03.8328.40CCB
03.8328.14CCB

Non Dimmable

03.8329.40C
03.8329.14C

Dali & Push Version

03.8329.40CDA
03.8329.14CDA

Mains Dimming

03.8329.40CNI
03.8329.14CNI

Casambi

03.8329.40CCB
03.8329.14CCB

Non Dimmable

05.1336.40C
05.1336.14C

Dali & Push Version

05.1336.40CDA
05.1336.14CDA

Mains Dimming

05.1336.40CNI
05.1336.14CNI

Casambi

05.1336.40CCB
05.1336.14CCB

Non Dimmable

05.1337.40C
05.1337.14C

Dali & Push Version

05.1337.40CDA
05.1337.14CDA


Mains Dimming

05.1337.40CNI
05.1337.14CNI

Casambi

05.1337.40CCB
05.1337.14CCB

45° WIDE FLOOD




Luminous flux luminaire
3272 lm

@White (40) 900mA

Beam Angle:	45°
h(m)	E(lx) D(m)
1	6539 0.83
2	1635 1.66
3	727 2.49
4	409 3.32
5	262 4.14

45° WIDE FLOOD



Luminous flux luminaire
2922 lm


@White (40) 750mA


Beam Angle:	45°
h(m)	E(lx) D(m)
1	5839 0.83
2	1460 1.66
3	649 2.49
4	365 3.32
5	234 4.14

Light Shadow Fixed No Trim 2 Spots

Power LED DC 900 mA 7W - 596 lm - 2700K/CRI 90 / 7W - 636 lm - 3000K/CRI 90







Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish

Luminaria empotrable de 2 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable

03.8852.40C
03.8852.14C

Dali Version

03.8852.40CDA
03.8852.14CDA

Mains Dimming

03.8852.40CNI
03.8852.14CNI

Casambi

03.8852.40CCB
03.8852.14CCB

Non Dimmable

03.8853.40C
03.8853.14C

Dali Version

03.8853.40CDA
03.8853.14CDA

Mains Dimming

03.8853.40CNI
03.8853.14CNI

Casambi

03.8853.40CCB
03.8853.14CCB

Non Dimmable

05.1041.40C
05.1041.14C

Dali Version

05.1041.40CDA
05.1041.14CDA

Mains Dimming

05.1041.40CNI
05.1041.14CNI

Casambi

05.1041.40CCB
05.1041.14CCB

Non Dimmable

05.1042.40C
05.1042.14C

Dali Version


05.1042.40CDA
05.1042.14CDA

Mains Dimming

05.1042.40CNI
05.1042.14CNI

Casambi

05.1042.40CCB
05.1042.14CCB



Luminous flux luminaire 530 lm

@White (40)

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	8555	0.20
2	2139	0.41
3	951	0.61
4	535	0.81
5	342	1.01

Optic Spot 3000K

E I Non Dimmable

03.8856.40C
03.8856.14C

Dali Version

03.8856.40CDA
03.8856.14CDA

Mains Dimming

03.8856.40CNI
03.8856.14CNI

Casambi

03.8856.40CCB
03.8856.14CCB

Non Dimmable

03.8857.40C
03.8857.14C

Dali Version

03.8857.40CDA
03.8857.14CDA

Mains Dimming

03.8857.40CNI
03.8857.14CNI

Casambi

03.8857.40CCB
03.8857.14CCB

Non Dimmable

05.1046.40C
05.1046.14C

Dali Version

05.1046.40CDA
05.1046.14CDA

Mains Dimming

05.1046.40CNI
05.1046.14CNI

Casambi

05.1046.40CCB
05.1046.14CCB

Non Dimmable

05.1047.40C
05.1047.14C

Dali Version


05.1047.40CDA
05.1047.14CDA

Mains Dimming

05.1047.40CNI
05.1047.14CNI

Casambi

05.1047.40CCB
05.1047.14CCB



Luminous flux luminaire 566 lm

@White (40)


Beam Angle: 12°

h(m)	E(lx)	D(m)
1	9136	0.20
2	2284	0.41
3	1015	0.61
4	571	0.81
5	365	1.01

Optic Medium
2700K

E I Non Dimmable
03.9200.40C
03.9200.14C
Dali Version
03.9200.40CDA
03.9200.14CDA
Mains Dimming
03.9200.40CNI
03.9200.14CNI
Casambi
03.9200.40CCB
03.9200.14CCB
Non Dimmable
03.9201.40C
03.9201.14C
Dali Version
03.9201.40CDA
03.9201.14CDA
Mains Dimming
03.9201.40CNI
03.9201.14CNI
Casambi
03.9201.40CCB
03.9201.14CCB
Non Dimmable
05.1051.40C
05.1051.14C
Dali Version
05.1051.40CDA
05.1051.14CDA
Mains Dimming
05.1051.40CNI
05.1051.14CNI
Casambi
05.1051.40CCB
05.1051.14CCB
Non Dimmable
05.1052.40C
05.1052.14C
Dali Version
05.1052.40CDA
05.1052.14CDA
Mains Dimming
05.1052.40CNI
05.1052.14CNI
Casambi
05.1052.40CCB
05.1052.14CCB





Luminous flux luminaire
510 lm


@White (40)

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	3423	0.40
2	856	0.80
3	380	0.20
4	214	1.60
5	137	2.00

Optic Medium
3000K

E I Non Dimmable
03.9210.40C
03.9210.14C
Dali Version
03.9210.40CDA
03.9210.14CDA
Mains Dimming
03.9210.40CNI
03.9210.14CNI
Casambi
03.9210.40CCB
03.9210.14CCB
Non Dimmable
03.9211.40C
03.9211.14C
Dali Version
03.9211.40CDA
03.9211.14CDA
Mains Dimming
03.9211.40CNI
03.9211.14CNI
Casambi
03.9211.40CCB
03.9211.14CCB
Non Dimmable
05.1056.40C
05.1056.14C
Dali Version
05.1056.40CDA
05.1056.14CDA
Mains Dimming
05.1056.40CNI
05.1056.14CNI
Casambi
05.1056.40CCB
05.1056.14CCB
Non Dimmable
05.1057.40C
05.1057.14C
Dali Version
05.1057.40CDA
05.1057.14CDA
Mains Dimming
05.1057.40CNI
05.1057.14CNI
Casambi
05.1057.40CCB
05.1057.14CCB





Luminous flux luminaire
544 lm


@White (40)


Beam Angle:		23°
h(m)	E(lx)	D(m)
1	3651	0.40
2	913	0.80
3	406	1.20
4	228	1.60
5	146	2.00

Light Shadow Fixed No Trim 2 Spots

Power LED DC 900 mA 7W - 596 lm - 2700K/CRI 90 / 7W - 636 lm - 3000K/CRI 90







Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish


Luminaria empotrable de 2 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9205.40C
03.9205.14C
Dali Version
03.9205.40CDA
03.9205.14CDA
Mains Dimming
03.9205.40CNI
03.9205.14CNI
Casambi
03.9205.40CCB
03.9205.14CCB
Non Dimmable
03.9206.40C
03.9206.14C
Dali Version
03.9206.40CDA
03.9206.14CDA
Mains Dimming
03.9206.40CNI
03.9206.14CNI
Casambi
03.9206.40CCB
03.9206.14CCB
Non Dimmable
05.1061.40C
05.1061.14C
Dali Version
05.1061.40CDA
05.1061.14CDA
Mains Dimming
05.1061.40CNI
05.1061.14CNI
Casambi
05.1061.40CCB
05.1061.14CCB
Non Dimmable
05.1062.40C
05.1062.14C
Dali Version
05.1062.40CDA
05.1062.14CDA
Mains Dimming
05.1062.40CNI
05.1062.14CNI
Casambi
05.1062.40CCB
05.1062.14CCB

29°
FLOOD



Beam Angle: 29°

h(m)	E(lx)	D(m)
1	2070	0.51
2	517	1.03
3	230	1.54
4	129	2.05
5	83	2.57


Luminous flux luminaire 514 lm

@White (40)

Optic Flood 3000K

E I Non Dimmable
03.9215.40C
03.9215.14C
Dali Version
03.9215.40CDA
03.9215.14CDA
Mains Dimming
03.9215.40CNI
03.9215.14CNI
Casambi
03.9215.40CCB
03.9215.14CCB
Non Dimmable
03.9216.40C
03.9216.14C
Dali Version
03.9216.40CDA
03.9216.14CDA
Mains Dimming
03.9216.40CNI
03.9216.14CNI
Casambi
03.9216.40CCB
03.9216.14CCB
Non Dimmable
05.1066.40C
05.1066.14C
Dali Version
05.1066.40CDA
05.1066.14CDA
Mains Dimming
05.1066.40CNI
05.1066.14CNI
Casambi
05.1066.40CCB
05.1066.14CCB
Non Dimmable
05.1067.40C
05.1067.14C
Dali Version
05.1067.40CDA
05.1067.14CDA
Mains Dimming
05.1067.40CNI
05.1067.14CNI
Casambi
05.1067.40CCB
05.1067.14CCB

29°
FLOOD



Beam Angle: 29°

h(m)	E(lx)	D(m)
1	2211	0.51
2	553	1.03
3	246	1.54
4	138	2.05
5	88	2.57

Luminous flux luminaire 549 lm


@White (40)

Optic Wide Flood 2700K

E I Non Dimmable
03.8350.40C
03.8350.14C
Dali Version
03.8350.40CDA
03.8350.14CDA
Mains Dimming
03.8350.40CNI
03.8350.14CNI
Casambi
03.8350.40CCB
03.8350.14CCB
Non Dimmable
03.8351.40C
03.8351.14C
Dali Version
03.8351.40CDA
03.8351.14CDA
Mains Dimming
03.8351.40CNI
03.8351.14CNI
Casambi
03.8351.40CCB
03.8351.14CCB
Non Dimmable
05.1071.40C
05.1071.14C
Dali Version
05.1071.40CDA
05.1071.14CDA
Mains Dimming
05.1071.40CNI
05.1071.14CNI
Casambi
05.1071.40CCB
05.1071.14CCB
Non Dimmable
05.1072.40C
05.1072.14C
Dali Version
05.1072.40CDA
05.1072.14CDA
Mains Dimming
05.1072.40CNI
05.1072.14CNI
Casambi
05.1072.40CCB
05.1072.14CCB



WIDE FLOOD



Luminous flux luminaire
511 lm

@White (40)

Beam Angle: 45°


h(m)	E(lx)	D(m)
1	1021	0.83
2	255	1.66
3	113	2.49
4	64	3.32
5	41	4.14

Optic Wide Flood 3000K

E I Non Dimmable
03.8354.40C
03.8354.14C
Dali Version
03.8354.40CDA
03.8354.14CDA
Mains Dimming
03.8354.40CNI
03.8354.14CNI
Casambi
03.8354.40CCB
03.8354.14CCB
Non Dimmable
03.8355.40C
03.8355.14C
Dali Version
03.8355.40CDA
03.8355.14CDA
Mains Dimming
03.8355.40CNI
03.8355.14CNI
Casambi
03.8355.40CCB
03.8355.14CCB
Non Dimmable
05.1076.40C
05.1076.14C
Dali Version
05.1076.40CDA
05.1076.14CDA
Mains Dimming
05.1076.40CNI
05.1076.14CNI
Casambi
05.1076.40CCB
05.1076.14CCB
Non Dimmable
05.1077.40C
05.1077.14C
Dali Version
05.1077.40CDA
05.1077.14CDA
Mains Dimming
05.1077.40CNI
05.1077.14CNI
Casambi
05.1077.40CCB
05.1077.14CCB



WIDE FLOOD



Luminous flux luminaire
545 lm

@White (40)


Beam Angle: 45°


h(m)	E(lx)	D(m)
1	1089	0.83
2	272	1.66
3	121	2.49
4	68	3.32
5	44	4.14

Light Shadow Fixed No Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

* Multipack available.

E= External Finish
I= Internal Finish.

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

* Embalaje múltiple disponible.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable

03.8860.40C
03.8860.14C

Dali Version

03.8860.40CDA
03.8860.14CDA

Mains Dimming

03.8860.40CNI
03.8860.14CNI

Casambi

03.8860.40CCB
03.8860.14CCB

Non Dimmable

03.8861.40C
03.8861.14C

Dali Version

03.8861.40CDA
03.8861.14CDA

Mains Dimming

03.8861.40CNI
03.8861.14CNI

Casambi

03.8861.40CCB
03.8861.14CCB

Non Dimmable

05.1141.40C
05.1141.14C

Dali Version

05.1141.40CDA
05.1141.14CDA

Mains Dimming

05.1141.40CNI
05.1141.14CNI

Casambi

05.1141.40CCB
05.1141.14CCB

Non Dimmable

05.1142.40C
05.1142.14C

Dali Version

05.1142.40CDA
05.1142.14CDA


Mains Dimming

05.1142.40CNI
05.1142.14CNI

Casambi

05.1142.40CCB
05.1142.14CCB

12° SPOT



Luminous flux luminaire 1060 lm

@White (40)

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	17109	0.20
2	4277	0.41
3	1901	0.61
4	1069	0.81
5	684	1.01

Optic Spot 3000K

E I Non Dimmable

03.8864.40C
03.8864.14C

Dali Version

03.8864.40CDA
03.8864.14CDA

Mains Dimming

03.8864.40CNI
03.8864.14CNI

Casambi

03.8864.40CCB
03.8864.14CCB

Non Dimmable

03.8865.40C
03.8865.14C

Dali Version

03.8865.40CDA
03.8865.14CDA

Mains Dimming

03.8865.40CNI
03.8865.14CNI

Casambi

03.8865.40CCB
03.8865.14CCB

Non Dimmable

05.1146.40C
05.1146.14C

Dali Version

05.1146.40CDA
05.1146.14CDA

Mains Dimming

05.1146.40CNI
05.1146.14CNI

Casambi

05.1146.40CCB
05.1146.14CCB

Non Dimmable

05.1147.40C
05.1147.14C

Dali Version

05.1147.40CDA
05.1147.14CDA


Mains Dimming

05.1147.40CNI
05.1147.14CNI

Casambi

05.1147.40CCB
05.1147.14CCB

12° SPOT



Luminous flux luminaire 1131 lm

@White (40)

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	18255	0.20
2	4564	0.41
3	2028	0.61
4	1141	0.81
5	730	1.01

Optic Medium 2700K

E I

Non Dimmable
03.9220.40C
03.9220.14C

Dali Version
03.9220.40CDA
03.9220.14CDA

Mains Dimming
03.9220.40CNI
03.9220.14CNI

Casambi
03.9220.40CCB
03.9220.14CCB

Non Dimmable
03.9221.40C
03.9221.14C

Dali Version
03.9221.40CDA
03.9221.14CDA

Mains Dimming
03.9221.40CNI
03.9221.14CNI

Casambi
03.9221.40CCB
03.9221.14CCB

Non Dimmable
05.1151.40C
05.1151.14C

Dali Version
05.1151.40CDA
05.1151.14CDA

Mains Dimming
05.1151.40CNI
05.1151.14CNI


Casambi
05.1151.40CCB
05.1151.14CCB

Non Dimmable
05.1152.40C
05.1152.14C

Dali Version
05.1152.40CDA
05.1152.14CDA

Mains Dimming
05.1152.40CNI
05.1152.14CNI

Casambi
05.1152.40CCB
05.1152.14CCB



Luminous flux luminaire
1020 lm

@White (40)

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	6846	0.40
2	1711	0.80
3	761	1.20
4	428	1.60
5	274	2.00

Optic Medium 3000K

E I

Non Dimmable
03.9230.40C
03.9230.14C

Dali Version
03.9230.40CDA
03.9230.14CDA

Mains Dimming
03.9230.40CNI
03.9230.14CNI

Casambi
03.9230.40CCB
03.9230.14CCB

Non Dimmable
03.9231.40C
03.9231.14C

Dali Version
03.9231.40CDA
03.9231.14CDA

Mains Dimming
03.9231.40CNI
03.9231.14CNI

Casambi
03.9231.40CCB
03.9231.14CCB

Non Dimmable
05.1156.40C
05.1156.14C

Dali Version
05.1156.40CDA
05.1156.14CDA

Mains Dimming
05.1156.40CNI
05.1156.14CNI


Casambi
05.1156.40CCB
05.1156.14CCB

Non Dimmable
05.1157.40C
05.1157.14C

Dali Version
05.1157.40CDA
05.1157.14CDA

Mains Dimming
05.1157.40CNI
05.1157.14CNI

Casambi
05.1157.40CCB
05.1157.14CCB



Luminous flux luminaire
1088 lm

@White (40)


Beam Angle:		23°
h(m)	E(lx)	D(m)
1	7302	0.40
2	1826	0.80
3	811	1.20
4	456	1.60
5	292	2.00


*Multipack available (14 pcs per box). How to order: “Replace the initial 0 with an M + reference”. Example: 03.8828.40A - M3.8828.40A
*Embalaje múltiple disponible (14 unidades por caja). Cómo hacer el pedido: “Sustituir el 0 inicial por una M + referencia”. Ejemplo: 03.8828.40A - M3.8828.40A

Light Shadow Fixed No Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

* Multipack available.

E= External Finish
I= Internal Finish.

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.


* Embalaje múltiple disponible.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9225.40C
03.9225.14C
Dali Version
03.9225.40CDA
03.9225.14CDA
Mains Dimming
03.9225.40CNI
03.9225.14CNI
Casambi
03.9225.40CCB
03.9225.14CCB
Non Dimmable
03.9226.40C
03.9226.14C
Dali Version
03.9226.40CDA
03.9226.14CDA
Mains Dimming
03.9226.40CNI
03.9226.14CNI
Casambi
03.9226.40CCB
03.9226.14CCB
Non Dimmable
05.1161.40C
05.1161.14C
Dali Version
05.1161.40CDA
05.1161.14CDA
Mains Dimming
05.1161.40CNI
05.1161.14CNI
Casambi
05.1161.40CCB
05.1161.14CCB
Non Dimmable
05.1162.40C
05.1162.14C
Dali Version
05.1162.40CDA
05.1162.14CDA
Mains Dimming
05.1162.40CNI
05.1162.14CNI
Casambi
05.1162.40CCB
05.1162.14CCB

29°
FLOOD



Luminous flux luminaire
1029 lm


@White (40)

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	4143	0.51
2	1036	1.03
3	460	1.54
4	259	2.05
5	166	2.57

Optic Flood 3000K

E I Non Dimmable
03.9235.40C
03.9235.14C
Dali Version
03.9235.40CDA
03.9235.14CDA
Mains Dimming
03.9235.40CNI
03.9235.14CNI
Casambi
03.9235.40CCB
03.9235.14CCB
Non Dimmable
03.9236.40C
03.9236.14C
Dali Version
03.9236.40CDA
03.9236.14CDA
Mains Dimming
03.9236.40CNI
03.9236.14CNI
Casambi
03.9236.40CCB
03.9236.14CCB
Non Dimmable
05.1166.40C
05.1166.14C
Dali Version
05.1166.40CDA
05.1166.14CDA
Mains Dimming
05.1166.40CNI
05.1166.14CNI
Casambi
05.1166.40CCB
05.1166.14CCB
Non Dimmable
05.1167.40C
05.1167.14C
Dali Version
05.1167.40CDA
05.1167.14CDA
Mains Dimming
05.1167.40CNI
05.1167.14CNI
Casambi
05.1167.40CCB
05.1167.14CCB

29°
FLOOD



Luminous flux luminaire
1098 lm

@White (40)

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	4421	0.51
2	1105	1.03
3	491	1.54
4	276	2.05
5	177	2.57

Optic Wide Flood
2700K

E I Non Dimmable

03.8358.40C
03.8358.14C

Dali Version

03.8358.40CDA
03.8358.14CDA

Mains Dimming

03.8358.40CNI
03.8358.14CNI

Casambi

03.8358.40CCB
03.8358.14CCB

Non Dimmable

03.8359.40C
03.8359.14C

Dali Version

03.8359.40CDA
03.8359.14CDA

Mains Dimming

03.8359.40CNI
03.8359.14CNI

Casambi

03.8359.40CCB
03.8359.14CCB

Non Dimmable

05.1171.40C
05.1171.14C

Dali Version

05.1171.40CDA
05.1171.14CDA

Mains Dimming

05.1171.40CNI
05.1171.14CNI

Casambi

05.1171.40CCB
05.1171.14CCB

Non Dimmable

05.1172.40C
05.1172.14C

Dali Version

05.1172.40CDA
05.1172.14CDA

Mains Dimming


05.1172.40CNI
05.1172.14CNI

Casambi

05.1172.40CCB
05.1172.14CCB



WIDE FLOOD



Luminous flux luminaire
1022 lm

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	2042	0.83
2	511	1.66
3	227	2.49
4	128	3.32
5	82	4.14

@White (40)

Optic Wide Flood
3000K

E I Non Dimmable

03.8362.40C
03.8362.14C

Dali Version

03.8362.40CDA
03.8362.14CDA

Mains Dimming

03.8362.40CNI
03.8362.14CNI

Casambi

03.8362.40CCB
03.8362.14CCB

Non Dimmable

03.8363.40C
03.8363.14C

Dali Version

03.8363.40CDA
03.8363.14CDA

Mains Dimming

03.8363.40CNI
03.8363.14CNI

Casambi

03.8363.40CCB
03.8363.14CCB

Non Dimmable

05.1176.40C
05.1176.14C

Dali Version

05.1176.40CDA
05.1176.14CDA

Mains Dimming

05.1176.40CNI
05.1176.14CNI

Casambi

05.1176.40CCB
05.1176.14CCB

Non Dimmable

05.1177.40C
05.1177.14C

Dali Version

05.1177.40CDA
05.1177.14CDA

Mains Dimming


05.1177.40CNI
05.1177.14CNI

Casambi

05.1177.40CCB
05.1177.14CCB



WIDE FLOOD



Luminous flux luminaire
1091 lm

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	2180	0.83
2	545	1.66
3	242	2.49
4	136	3.32
5	87	4.14

@White (40)


*Multipack available (14 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.8828.40A - M3.8828.40A

*Embalaje múltiple disponible (14 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.8828.40A - M3.8828.40A

Light Shadow Fixed No Trim 4 Spots Square

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90






GWT 850°




0,34 Kg




10 - 100%
DALI


h=75 min




LED INCL.



IP 55

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish.

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable


05.0640.40C
05.0640.14C

Dali Version


05.0640.40CDA
05.0640.14CDA

Mains Dimming


05.0640.40CNI
05.0640.14CNI

Casambi


05.0640.40CCB
05.0640.14CCB

Non Dimmable


05.0641.40C
05.0641.14C

Dali Version


05.0641.40CDA
05.0641.14CDA

Mains Dimming


05.0641.40CNI
05.0641.14CNI

Casambi


05.0641.40CCB
05.0641.14CCB

Non Dimmable


05.0644.40C
05.0644.14C

Dali Version


05.0644.40CDA
05.0644.14CDA

Mains Dimming


05.0644.40CNI
05.0644.14CNI

Casambi


05.0644.40CCB
05.0644.14CCB

Non Dimmable


05.0642.40C
05.0642.14C

Dali Version


05.0642.40CDA
05.0642.14CDA


Mains Dimming


05.0642.40CNI
05.0642.14CNI

Casambi


05.0642.40CCB
05.0642.14CCB





Luminous flux luminaire
982 lm

@White (40)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	17815	0.20
2	4454	0.40
3	1979	0.60
4	1113	0.80
5	713	1.00

Optic Spot 3000K

E I Non Dimmable


05.0645.40C
05.0645.14C

Dali Version


05.0645.40CDA
05.0645.14CDA

Mains Dimming


05.0645.40CNI
05.0645.14CNI

Casambi


05.0645.40CCB
05.0645.14CCB

Non Dimmable


05.0646.40C
05.0646.14C

Dali Version


05.0646.40CDA
05.0646.14CDA

Mains Dimming


05.0646.40CNI
05.0646.14CNI

Casambi


05.0646.40CCB
05.0646.14CCB

Non Dimmable


05.0649.40C
05.0649.14C

Dali Version


05.0649.40CDA
05.0649.14CDA

Mains Dimming


05.0649.40CNI
05.0649.14CNI

Casambi


05.0649.40CCB
05.0649.14CCB

Non Dimmable


05.0647.40C
05.0647.14C

Dali Version


05.0647.40CDA
05.0647.14CDA


Mains Dimming


05.0647.40CNI
05.0647.14CNI

Casambi


05.0647.40CCB
05.0647.14CCB





Luminous flux luminaire
1077 lm

@White (40)


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	19539	0.20
2	4885	0.40
3	2171	0.60
4	1221	0.80
5	782	1.00

Optic Medium 2700K

E I Non Dimmable
05.0650.40C
05.0650.14C
Dali Version
05.0650.40CDA
05.0650.14CDA
Mains Dimming
05.0650.40CNI
05.0650.14CNI
Casambi
05.0650.40CCB
05.0650.14CCB
Non Dimmable
05.0651.40C
05.0651.14C
Dali Version
05.0651.40CDA
05.0651.14CDA
Mains Dimming
05.0651.40CNI
05.0651.14CNI
Casambi
05.0651.40CCB
05.0651.14CCB
Non Dimmable
05.0654.40C
05.0654.14C
Dali Version
05.0654.40CDA
05.0654.14CDA
Mains Dimming
05.0654.40CNI
05.0654.14CNI
Casambi
05.0654.40CCB
05.0654.14CCB
Non Dimmable
05.0652.40C
05.0652.14C
Dali Version
05.0652.40CDA
05.0652.14CDA
Mains Dimming
05.0652.40CNI
05.0652.14CNI
Casambi
05.0652.40CCB
05.0652.14CCB

25°
MEDIUM



Luminous flux luminaire
978 lm


@White (40)

Beam Angle:	25°
h(m)	E(lx)	D(m)
1	5628	0.44
2	1407	0.88
3	625	1.31
4	352	1.75
5	225	2.19

Optic Medium 3000K

E I Non Dimmable
05.0655.40C
05.0655.14C
Dali Version
05.0655.40CDA
05.0655.14CDA
Mains Dimming
05.0655.40CNI
05.0655.14CNI
Casambi
05.0655.40CCB
05.0655.14CCB
Non Dimmable
05.0656.40C
05.0656.14C
Dali Version
05.0656.40CDA
05.0656.14CDA
Mains Dimming
05.0656.40CNI
05.0656.14CNI
Casambi
05.0656.40CCB
05.0656.14CCB
Non Dimmable
05.0659.40C
05.0659.14C
Dali Version
05.0659.40CDA
05.0659.14CDA
Mains Dimming
05.0659.40CNI
05.0659.14CNI
Casambi
05.0659.40CCB
05.0659.14CCB
Non Dimmable
05.0657.40C
05.0657.14C
Dali Version
05.0657.40CDA
05.0657.14CDA
Mains Dimming
05.0657.40CNI
05.0657.14CNI
Casambi
05.0657.40CCB
05.0657.14CCB

25°
MEDIUM



Luminous flux luminaire
1072 lm


@White (40)


Beam Angle:	25°
h(m)	E(lx)	D(m)
1	6169	0.44
2	1542	0.88
3	685	1.31
4	386	1.75
5	247	2.19

Light Shadow Fixed No Trim 4 Spots Square

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish.

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable

05.0660.40C
05.0660.14C

Dali Version

05.0660.40CDA
05.0660.14CDA

Mains Dimming

05.0660.40CNI
05.0660.14CNI

Casambi

05.0660.40CCB
05.0660.14CCB

Non Dimmable

05.0661.40C
05.0661.14C

Dali Version

05.0661.40CDA
05.0661.14CDA

Mains Dimming

05.0661.40CNI
05.0661.14CNI

Casambi

05.0661.40CCB
05.0661.14CCB

Non Dimmable

05.0664.40C
05.0664.14C

Dali Version

05.0664.40CDA
05.0664.14CDA

Mains Dimming

05.0664.40CNI
05.0664.14CNI

Casambi

05.0664.40CCB
05.0664.14CCB

Non Dimmable

05.0662.40C
05.0662.14C

Dali Version


05.0662.40CDA
05.0662.14CDA

Mains Dimming

05.0662.40CNI
05.0662.14CNI

Casambi

05.0662.40CCB
05.0662.14CCB



Luminous flux luminaire
961 lm

@White (40)

Beam Angle:	35°
h(m)	E(lx) D(m)
1	2752 0.63
2	688 1.27
3	306 1.90
4	172 2.54
5	110 3.17

Optic Flood 3000K

E I Non Dimmable

05.0665.40C
05.0665.14C

Dali Version

05.0665.40CDA
05.0665.14CDA

Mains Dimming

05.0665.40CNI
05.0665.14CNI

Casambi

05.0665.40CCB
05.0665.14CCB

Non Dimmable

05.0666.40C
05.0666.14C

Dali Version

05.0666.40CDA
05.0666.14CDA

Mains Dimming

05.0666.40CNI
05.0666.14CNI

Casambi

05.0666.40CCB
05.0666.14CCB

Non Dimmable

05.0669.40C
05.0669.14C

Dali Version

05.0669.40CDA
05.0669.14CDA

Mains Dimming

05.0669.40CNI
05.0669.14CNI

Casambi

05.0669.40CCB
05.0669.14CCB

Non Dimmable

05.0667.40C
05.0667.14C

Dali Version


05.0667.40CDA
05.0667.14CDA

Mains Dimming

05.0667.40CNI
05.0667.14CNI

Casambi

05.0667.40CCB
05.0667.14CCB



Luminous flux luminaire
1054 lm

@White (40)


Beam Angle:	35°
h(m)	E(lx) D(m)
1	3018 0.63
2	755 1.27
3	335 1.90
4	189 2.54
5	121 3.17

Optic Wide Flood
2700K

E I Non Dimmable
05.0670.40C
05.0670.14C
Dali Version
05.0670.40CDA
05.0670.14CDA
Mains Dimming
05.0670.40CNI
05.0670.14CNI
Casambi
05.0670.40CCB
05.0670.14CCB
Non Dimmable
05.0671.40C
05.0671.14C
Dali Version
05.0671.40CDA
05.0671.14CDA
Mains Dimming
05.0671.40CNI
05.0671.14CNI
Casambi
05.0671.40CCB
05.0671.14CCB
Non Dimmable
05.0674.40C
05.0674.14C
Dali Version
05.0674.40CDA
05.0674.14CDA
Mains Dimming
05.0674.40CNI
05.0674.14CNI
Casambi
05.0674.40CCB
05.0674.14CCB
Non Dimmable
05.0672.40C
05.0672.14C
Dali Version
05.0672.40CDA
05.0672.14CDA
Mains Dimming
05.0672.40CNI
05.0672.14CNI
Casambi
05.0672.40CCB
05.0672.14CCB



WIDE FLOOD



Luminous flux luminaire
962 lm

Beam Angle:		49°
h(m)	E(lx)	D(m)
1	1564	0.90
2	391	1.81
3	174	2.71
4	98	3.62
5	63	4.52


@White (40)

Optic Wide Flood
3000K

E I Non Dimmable
05.0675.40C
05.0675.14C
Dali Version
05.0675.40CDA
05.0675.14CDA
Mains Dimming
05.0675.40CNI
05.0675.14CNI
Casambi
05.0675.40CCB
05.0675.14CCB
Non Dimmable
05.0676.40C
05.0676.14C
Dali Version
05.0676.40CDA
05.0676.14CDA
Mains Dimming
05.0676.40CNI
05.0676.14CNI
Casambi
05.0676.40CCB
05.0676.14CCB
Non Dimmable
05.0679.40C
05.0679.14C
Dali Version
05.0679.40CDA
05.0679.14CDA
Mains Dimming
05.0679.40CNI
05.0679.14CNI
Casambi
05.0679.40CCB
05.0679.14CCB
Non Dimmable
05.0677.40C
05.0677.14C
Dali Version
05.0677.40CDA
05.0677.14CDA
Mains Dimming
05.0677.40CNI
05.0677.14CNI
Casambi
05.0677.40CCB
05.0677.14CCB



WIDE FLOOD



Luminous flux luminaire
1055 lm


Beam Angle:		49°
h(m)	E(lx)	D(m)
1	1715	0.90
2	429	1.81
3	191	2.71
4	107	3.62
5	69	4.52


@White (40)

Light Shadow Fixed No Trim 8 Spots

Power LED DC 900 mA 21,6W - 2384 lm - 2700K/CRI 90 / 21,6W - 2544 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 18,6W - 1984 lm - 2700K/CRI 90 / 18,6W - 2120 lm - 3000K/CRI 90







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

* Multipack available.

E= External Finish
I= Internal Finish

Luminaria empotrable de 8 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.


* Embalaje múltiple disponible.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8868.40C
03.8868.14C
Dali Version
03.8868.40CDA
03.8868.14CDA
Mains Dimming
03.8868.40CNI
03.8868.14CNI
Casambi
03.8868.40CCB
03.8868.14CCB
Non Dimmable
03.8869.40C
03.8869.14C
Dali Version
03.8869.40CDA
03.8869.14CDA
Mains Dimming
03.8869.40CNI
03.8869.14CNI
Casambi
03.8869.40CCB
03.8869.14CCB
Non Dimmable
05.1241.40C
05.1241.14C
Dali Version
05.1241.40CDA
05.1241.14CDA
Mains Dimming
05.1241.40CNI
05.1241.14CNI
Casambi
05.1241.40CCB
05.1241.14CCB
Non Dimmable
05.1242.40C
05.1242.14C
Dali Version
05.1242.40CDA
05.1242.14CDA
Mains Dimming
05.1242.40CNI
05.1242.14CNI
Casambi
05.1242.40CCB
05.1242.14CCB

12° SPOT




Luminous flux luminaire
2120 lm

@White (40) 900mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	34219	0.20
2	8555	0.41
3	3802	0.61
4	2139	0.81
5	1369	1.01

12° SPOT



Luminous flux luminaire
1800 lm


@White (40) 750mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	29054	0.20
2	7263	0.41
3	3228	0.61
4	1816	0.81
5	1162	1.01

Optic Spot 3000K

E I Non Dimmable
03.8872.40C
03.8872.14C
Dali Version
03.8872.40CDA
03.8872.14CDA
Mains Dimming
03.8872.40CNI
03.8872.14CNI
Casambi
03.8872.40CCB
03.8872.14CCB
Non Dimmable
03.8873.40C
03.8873.14C
Dali Version
03.8873.40CDA
03.8873.14CDA
Mains Dimming
03.8873.40CNI
03.8873.14CNI
Casambi
03.8873.40CCB
03.8873.14CCB
Non Dimmable
05.1246.40C
05.1246.14C
Dali Version
05.1246.40CDA
05.1246.14CDA
Mains Dimming
05.1246.40CNI
05.1246.14CNI
Casambi
05.1246.40CCB
05.1246.14CCB
Non Dimmable
05.1247.40C
05.1247.14C
Dali Version
05.1247.40CDA
05.1247.14CDA
Mains Dimming
05.1247.40CNI
05.1247.14CNI
Casambi
05.1247.40CCB
05.1247.14CCB

12° SPOT




Luminous flux luminaire
2262 lm

@White (40) 900mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	36511	0.20
2	9128	0.41
3	4057	0.61
4	2282	0.81
5	1460	1.01

12° SPOT



Luminous flux luminaire
2020 lm

@White (40) 750mA

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	32605	0.20
2	8151	0.41
3	3623	0.61
4	2038	0.81
5	1304	1.01

Optic Medium 2700K

E I

Non Dimmable
03.9240.40C
03.9240.14C

Dali Version
03.9240.40CDA
03.9240.14CDA

Mains Dimming
03.9240.40CNI
03.9240.14CNI

Casambi
03.9240.40CCB
03.9240.14CCB

Non Dimmable
03.9241.40C
03.9241.14C

Dali Version
03.9241.40CDA
03.9241.14CDA

Mains Dimming
03.9241.40CNI
03.9241.14CNI

Casambi
03.9241.40CCB
03.9241.14CCB

Non Dimmable
05.1251.40C
05.1251.14C

Dali Version
05.1251.40CDA
05.1251.14CDA

Mains Dimming
05.1251.40CNI
05.1251.14CNI

Casambi
05.1251.40CCB
05.1251.14CCB


Non Dimmable
05.1252.40C
05.1252.14C

Dali Version
05.1252.40CDA
05.1252.14CDA

Mains Dimming
05.1252.40CNI
05.1252.14CNI

Casambi
05.1252.40CCB
05.1252.14CCB

23°
MEDIUM




Luminous flux luminaire
2040 lm

@White (40) 900mA

Beam Angle:	23°
h(m)	E(lx)	D(m)
1	13692	0.40
2	3423	0.80
3	1521	1.20
4	856	1.60
5	548	2.00

23°
MEDIUM



Luminous flux luminaire
1732 lm

@White (40) 750mA

Beam Angle:	23°
h(m)	E(lx)	D(m)
1	11625	0.40
2	2906	0.80
3	1292	1.20
4	727	1.60
5	465	2.00

Optic Medium 3000K

E I

Non Dimmable
03.9250.40C
03.9250.14C

Dali Version
03.9250.40CDA
03.9250.14CDA

Mains Dimming
03.9250.40CNI
03.9250.14CNI

Casambi
03.9250.40CCB
03.9250.14CCB

Non Dimmable
03.9251.40C
03.9251.14C

Dali Version
03.9251.40CDA
03.9251.14CDA

Mains Dimming
03.9251.40CNI
03.9251.14CNI

Casambi
03.9251.40CCB
03.9251.14CCB

Non Dimmable
05.1256.40C
05.1256.14C

Dali Version
05.1256.40CDA
05.1256.14CDA

Mains Dimming
05.1256.40CNI
05.1256.14CNI

Casambi
05.1256.40CCB
05.1256.14CCB


Non Dimmable
05.1257.40C
05.1257.14C

Dali Version
05.1257.40CDA
05.1257.14CDA

Mains Dimming
05.1257.40CNI
05.1257.14CNI

Casambi
05.1257.40CCB
05.1257.14CCB

23°
MEDIUM




Luminous flux luminaire
2177 lm

@White (40) 900mA

Beam Angle:	23°
h(m)	E(lx)	D(m)
1	14611	0.40
2	3653	0.80
3	1623	1.20
4	913	1.60
5	584	2.00

23°
MEDIUM



Luminous flux luminaire
1944 lm

@White (40) 750mA

Beam Angle:	23°
h(m)	E(lx)	D(m)
1	13047	0.40
2	3262	0.80
3	1450	1.20
4	815	1.60
5	522	2.00


*Multipack available (12 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.8828.40A - M3.8828.40A


*Embalaje múltiple disponible (12 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.8828.40A - M3.8828.40A

Light Shadow Fixed No Trim 8 Spots

Power LED DC 900 mA 21,6W - 2384 lm - 2700K/CRI 90 / 21,6W - 2544 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 18,6W - 1984 lm - 2700K/CRI 90 / 18,6W - 2120 lm - 3000K/CRI 90







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

* Multipack available.

E= External Finish
I= Internal Finish

Luminaria empotrable de 8 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.


* Embalaje múltiple disponible.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9245.40C
03.9245.14C
Dali Version
03.9245.40CDA
03.9245.14CDA
Mains Dimming
03.9245.40CNI
03.9245.14CNI
Casambi
03.9245.40CCB
03.9245.14CCB
Non Dimmable
03.9246.40C
03.9246.14C
Dali Version
03.9246.40CDA
03.9246.14CDA
Mains Dimming
03.9246.40CNI
03.9246.14CNI
Casambi
03.9246.40CCB
03.9246.14CCB
Non Dimmable
05.1261.40C
05.1261.14C
Dali Version
05.1261.40CDA
05.1261.14CDA
Mains Dimming
05.1261.40CNI
05.1261.14CNI
Casambi
05.1261.40CCB
05.1261.14CCB
Non Dimmable
05.1262.40C
05.1262.14C
Dali Version
05.1262.40CDA
05.1262.14CDA
Mains Dimming
05.1262.40CNI
05.1262.14CNI
Casambi
05.1262.40CCB
05.1262.14CCB

29° FLOOD




Luminous flux luminaire
2057 lm

@White (40) 900mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	8282	0.51
2	2071	1.03
3	920	1.54
4	518	2.05
5	331	2.57

29° FLOOD



Luminous flux luminaire
1747 lm


@White (40) 750mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	7034	0.51
2	1759	1.03
3	782	1.54
4	440	2.05
5	281	2.57

Optic Flood 3000K

E I Non Dimmable
03.9255.40C
03.9255.14C
Dali Version
03.9255.40CDA
03.9255.14CDA
Mains Dimming
03.9255.40CNI
03.9255.14CNI
Casambi
03.9255.40CCB
03.9255.14CCB
Non Dimmable
03.9256.40C
03.9256.14C
Dali Version
03.9256.40CDA
03.9256.14CDA
Mains Dimming
03.9256.40CNI
03.9256.14CNI
Casambi
03.9256.40CCB
03.9256.14CCB
Non Dimmable
05.1266.40C
05.1266.14C
Dali Version
05.1266.40CDA
05.1266.14CDA
Mains Dimming
05.1266.40CNI
05.1266.14CNI
Casambi
05.1266.40CCB
05.1266.14CCB
Non Dimmable
05.1267.40C
05.1267.14C
Dali Version
05.1267.40CDA
05.1267.14CDA
Mains Dimming
05.1267.40CNI
05.1267.14CNI
Casambi
05.1267.40CCB
05.1267.14CCB

29° FLOOD




Luminous flux luminaire
2195 lm

@White (40) 900mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	8838	0.51
2	2210	1.03
3	982	1.54
4	552	2.05
5	354	2.57

29° FLOOD



Luminous flux luminaire
1961 lm

@White (40) 750mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	7896	0.51
2	1974	1.03
3	877	1.54
4	493	2.05
5	316	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.8366.40C
03.8366.14C

Dali Version

03.8366.40CDA
03.8366.14CDA

Mains Dimming

03.8366.40CNI
03.8366.14CNI

Casambi

03.8366.40CCB
03.8366.14CCB

Non Dimmable

03.8367.40C
03.8367.14C

Dali Version

03.8367.40CDA
03.8367.14CDA

Mains Dimming

03.8367.40CNI
03.8367.14CNI

Casambi

03.8367.40CCB
03.8367.14CCB

Non Dimmable

05.1271.40C
05.1271.14C

Dali Version

05.1271.40CDA
05.1271.14CDA

Mains Dimming

05.1271.40CNI
05.1271.14CNI

Casambi

05.1271.40CCB
05.1271.14CCB

Non Dimmable

05.1272.40C
05.1272.14C

Dali Version

05.1272.40CDA
05.1272.14CDA


Mains Dimming

05.1272.40CNI
05.1272.14CNI

Casambi

05.1272.40CCB
05.1272.14CCB

45° WIDE FLOOD




Luminous flux luminaire
2044 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	4085	0.83
2	1021	1.66
3	454	2.49
4	255	3.32
5	163	4.14

45° WIDE FLOOD



Luminous flux luminaire
1736 lm

@White (40) 750mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	3469	0.83
2	867	1.66
3	385	2.49
4	217	3.32
5	139	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.8370.40C
03.8370.14C

Dali Version

03.8370.40CDA
03.8370.14CDA

Mains Dimming

03.8370.40CNI
03.8370.14CNI

Casambi

03.8370.40CCB
03.8370.14CCB

Non Dimmable

03.8371.40C
03.8371.14C

Dali Version

03.8371.40CDA
03.8371.14CDA

Mains Dimming

03.8371.40CNI
03.8371.14CNI

Casambi

03.8371.40CCB
03.8371.14CCB

Non Dimmable

05.1276.40C
05.1276.14C

Dali Version

05.1276.40CDA
05.1276.14CDA

Mains Dimming

05.1276.40CNI
05.1276.14CNI

Casambi

05.1276.40CCB
05.1276.14CCB

Non Dimmable

05.1277.40C
05.1277.14C

Dali Version

05.1277.40CDA
05.1277.14CDA


Mains Dimming

05.1277.40CNI
05.1277.14CNI

Casambi

05.1277.40CCB
05.1277.14CCB

45° WIDE FLOOD




Luminous flux luminaire
2181 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	4358	0.83
2	1090	1.66
3	484	2.49
4	272	3.32
5	174	4.14

45° WIDE FLOOD



Luminous flux luminaire
1948 lm

@White (40) 750mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	3893	0.83
2	973	1.66
3	433	2.49
4	243	3.32
5	156	4.14


*Multipack available (12 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.8828.40A - M3.8828.40A


*Embalaje múltiple disponible (12 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.8828.40A - M3.8828.40A

Light Shadow Fixed No Trim 12 Spots

Power LED DC 900 mA 32,4W - 3576 lm - 2700K/CRI 90 / 32,4W - 3816 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 28W - 2976 lm - 2700K/CRI 90 / 28W - 3180 lm - 3000K/CRI 90







Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V). It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish


Luminaria empotrable de 12 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8876.40C
03.8876.14C
Dali & Push Version
03.8876.40CDA
03.8876.14CDA
Mains Dimming
03.8876.40CNI
03.8876.14CNI
Casambi
03.8876.40CCB
03.8876.14CCB
Non Dimmable
03.8877.40C
03.8877.14C
Dali & Push Version
03.8877.40CDA
03.8877.14CDA
Mains Dimming
03.8877.40CNI
03.8877.14CNI
Casambi
03.8877.40CCB
03.8877.14CCB
Non Dimmable
05.1341.40C
05.1341.14C
Dali & Push Version
05.1341.40CDA
05.1341.14CDA
Mains Dimming
05.1341.40CNI
05.1341.14CNI
Casambi
05.1341.40CCB
05.1341.14CCB
Non Dimmable
05.1342.40C
05.1342.14C
Dali & Push Version
05.1342.40CDA
05.1342.14CDA
Mains Dimming
05.1342.40CNI
05.1342.14CNI
Casambi
05.1342.40CCB
05.1342.14CCB

12° SPOT




Luminous flux luminaire
3180 lm

@White (40) 900mA

Beam Angle:	12°
h(m)	E(lx) D(m)
1	51328 0.20
2	12832 0.41
3	5703 0.61
4	3208 0.81
5	2053 1.01

12° SPOT



Luminous flux luminaire
2849 lm


@White (40) 750mA

Beam Angle:	12°
h(m)	E(lx) D(m)
1	45985 0.20
2	11496 0.41
3	5109 0.61
4	2874 0.81
5	1839 1.01

Optic Spot 3000K

E I Non Dimmable
03.8880.40C
03.8880.14C
Dali & Push Version
03.8880.40CDA
03.8880.14CDA
Mains Dimming
03.8880.40CNI
03.8880.14CNI
Casambi
03.8880.40CCB
03.8880.14CCB
Non Dimmable
03.8881.40C
03.8881.14C
Dali & Push Version
03.8881.40CDA
03.8881.14CDA
Mains Dimming
03.8881.40CNI
03.8881.14CNI
Casambi
03.8881.40CCB
03.8881.14CCB
Non Dimmable
05.1346.40C
05.1346.14C
Dali & Push Version
05.1346.40CDA
05.1346.14CDA
Mains Dimming
05.1346.40CNI
05.1346.14CNI
Casambi
05.1346.40CCB
05.1346.14CCB
Non Dimmable
05.1347.40C
05.1347.14C
Dali & Push Version
05.1347.40CDA
05.1347.14CDA
Mains Dimming
05.1347.40CNI
05.1347.14CNI
Casambi
05.1347.40CCB
05.1347.14CCB

12° SPOT




Luminous flux luminaire
3394 lm

@White (40) 900mA

Beam Angle:	12°
h(m)	E(lx) D(m)
1	54782 0.20
2	13696 0.41
3	6087 0.61
4	3424 0.81
5	2191 1.01

12° SPOT



Luminous flux luminaire
3031 lm

@White (40) 750mA

Beam Angle:	12°
h(m)	E(lx) D(m)
1	48923 0.20
2	12231 0.41
3	5436 0.61
4	3058 0.81
5	1957 1.01

Optic Medium 2700K

E I Non Dimmable

03.9260.40C
03.9260.14C

Dali & Push Version

03.9260.40CDA
03.9260.14CDA

Mains Dimming

03.9260.40CNI
03.9260.14CNI

Casambi

03.9260.40CCB
03.9260.14CCB

Non Dimmable

03.9261.40C
03.9261.14C

Dali & Push Version

03.9261.40CDA
03.9261.14CDA

Mains Dimming

03.9261.40CNI
03.9261.14CNI

Casambi

03.9261.40CCB
03.9261.14CCB

Non Dimmable

05.1351.40C
05.1351.14C

Dali & Push Version

05.1351.40CDA
05.1351.14CDA

Mains Dimming

05.1351.40CNI
05.1351.14CNI

Casambi

05.1351.40CCB
05.1351.14CCB

Non Dimmable

05.1352.40C
05.1352.14C

Dali & Push Version

05.1352.40CDA
05.1352.14CDA


Mains Dimming

05.1352.40CNI
05.1352.14CNI

Casambi

05.1352.40CCB
05.1352.14CCB

23°
MEDIUM




Luminous flux luminaire
3060 lm

@White (40) 900mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	20538	0.40
2	5134	0.80
3	2282	1.20
4	1284	1.60
5	822	2.00

23°
MEDIUM



Luminous flux luminaire
2742 lm

@White (40) 750mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	18403	0.40
2	4601	0.80
3	2045	1.20
4	1150	1.60
5	736	2.00

Optic Medium 3000K

E I Non Dimmable

03.9270.40C
03.9270.14C

Dali & Push Version

03.9270.40CDA
03.9270.14CDA

Mains Dimming

03.9270.40CNI
03.9270.14CNI

Casambi

03.9270.40CCB
03.9270.14CCB

Non Dimmable

03.9271.40C
03.9271.14C

Dali & Push Version

03.9271.40CDA
03.9271.14CDA

Mains Dimming

03.9271.40CNI
03.9271.14CNI

Casambi

03.9271.40CCB
03.9271.14CCB

Non Dimmable

05.1356.40C
05.1356.14C

Dali & Push Version

05.1356.40CDA
05.1356.14CDA

Mains Dimming

05.1356.40CNI
05.1356.14CNI

Casambi

05.1356.40CCB
05.1356.14CCB

Non Dimmable

05.1357.40C
05.1357.14C

Dali & Push Version

05.1357.40CDA
05.1357.14CDA


Mains Dimming

05.1357.40CNI
05.1357.14CNI

Casambi

05.1357.40CCB
05.1357.14CCB

23°
MEDIUM




Luminous flux luminaire
3265 lm

@White (40) 900mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	21913	0.40
2	5478	0.80
3	2435	1.20
4	1370	1.60
5	877	2.00

23°
MEDIUM



Luminous flux luminaire
2916 lm

@White (40) 750mA


Beam Angle: 23°


h(m)	E(lx)	D(m)
1	19571	0.40
2	4893	0.80
3	2175	1.20
4	1223	1.60
5	783	2.00

Light Shadow Fixed No Trim 12 Spots

Power LED DC 900 mA 32,4W - 3576 lm - 2700K/CRI 90 / 32,4W - 3816 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 28W - 2976 lm - 2700K/CRI 90 / 28W - 3180 lm - 3000K/CRI 90







Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V). It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish


Luminaria empotrable de 12 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9265.40C
03.9265.14C
Dali & Push Version
03.9265.40CDA
03.9265.14CDA
Mains Dimming
03.9265.40CNI
03.9265.14CNI
Casambi
03.9265.40CCB
03.9265.14CCB
Non Dimmable
03.9266.40C
03.9266.14C
Dali & Push Version
03.9266.40CDA
03.9266.14CDA
Mains Dimming
03.9266.40CNI
03.9266.14CNI
Casambi
03.9266.40CCB
03.9266.14CCB
Non Dimmable
05.1361.40C
05.1361.14C
Dali & Push Version
05.1361.40CDA
05.1361.14CDA
Mains Dimming
05.1361.40CNI
05.1361.14CNI
Casambi
05.1361.40CCB
05.1361.14CCB
Non Dimmable
05.1362.40C
05.1362.14C
Dali & Push Version
05.1362.40CDA
05.1362.14CDA
Mains Dimming
05.1362.40CNI
05.1362.14CNI
Casambi
05.1362.40CCB
05.1362.14CCB


29° FLOOD



Luminous flux luminaire 3086 lm
@White (40) 900mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	12426	0.51
2	3106	1.03
3	1381	1.54
4	777	2.05
5	497	2.57

29° FLOOD




Luminous flux luminaire 2765 lm
@White (40) 750mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	11133	0.51
2	2783	1.03
3	1237	1.54
4	696	2.05
5	445	2.57

Optic Flood 3000K

E I Non Dimmable
03.9275.40C
03.9275.14C
Dali & Push Version
03.9275.40CDA
03.9275.14CDA
Mains Dimming
03.9275.40CNI
03.9275.14CNI
Casambi
03.9275.40CCB
03.9275.14CCB
Non Dimmable
03.9276.40C
03.9276.14C
Dali & Push Version
03.9276.40CDA
03.9276.14CDA
Mains Dimming
03.9276.40CNI
03.9276.14CNI
Casambi
03.9276.40CCB
03.9276.14CCB
Non Dimmable
05.1366.40C
05.1366.14C
Dali & Push Version
05.1366.40CDA
05.1366.14CDA
Mains Dimming
05.1366.40CNI
05.1366.14CNI
Casambi
05.1366.40CCB
05.1366.14CCB
Non Dimmable
05.1367.40C
05.1367.14C
Dali & Push Version
05.1367.40CDA
05.1367.14CDA
Mains Dimming
05.1367.40CNI
05.1367.14CNI
Casambi
05.1367.40CCB
05.1367.14CCB


29° FLOOD



Luminous flux luminaire 3293 lm
@White (40) 900mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	13259	0.51
2	3315	1.03
3	1473	1.54
4	829	2.05
5	530	2.57

29° FLOOD



Luminous flux luminaire 2941 lm
@White (40) 750mA

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	11842	0.51
2	2960	1.03
3	1316	1.54
4	740	2.05
5	474	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.8374.40C
03.8374.14C

Dali & Push Version

03.8374.40CDA
03.8374.14CDA

Mains Dimming

03.8374.40CNI
03.8374.14CNI

Casambi

03.8374.40CCB
03.8374.14CCB

Non Dimmable

03.8375.40C
03.8375.14C

Dali & Push Version

03.8375.40CDA
03.8375.14CDA

Mains Dimming

03.8375.40CNI
03.8375.14CNI

Casambi

03.8375.40CCB
03.8375.14CCB

Non Dimmable

05.1371.40C
05.1371.14C

Dali & Push Version

05.1371.40CDA
05.1371.14CDA

Mains Dimming

05.1371.40CNI
05.1371.14CNI

Casambi

05.1371.40CCB
05.1371.14CCB

Non Dimmable

05.1372.40C
05.1372.14C

Dali & Push Version

05.1372.40CDA
05.1372.14CDA


Mains Dimming

05.1372.40CNI
05.1372.14CNI

Casambi

05.1372.40CCB
05.1372.14CCB






Luminous flux luminaire
3066 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	6127	0.83
2	1532	1.66
3	681	2.49
4	383	3.32
5	245	4.14





Luminous flux luminaire
2747 lm

@White (40) 750mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	5490	0.83
2	1372	1.66
3	610	2.49
4	343	3.32
5	220	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.8378.40C
03.8378.14C

Dali & Push Version

03.8378.40CDA
03.8378.14CDA

Mains Dimming

03.8378.40CNI
03.8378.14CNI

Casambi

03.8378.40CCB
03.8378.14CCB

Non Dimmable

03.8379.40C
03.8379.14C

Dali & Push Version

03.8379.40CDA
03.8379.14CDA

Mains Dimming

03.8379.40CNI
03.8379.14CNI

Casambi

03.8379.40CCB
03.8379.14CCB

Non Dimmable

05.1376.40C
05.1376.14C

Dali & Push Version

05.1376.40CDA
05.1376.14CDA

Mains Dimming

05.1376.40CNI
05.1376.14CNI

Casambi

05.1376.40CCB
05.1376.14CCB

Non Dimmable

05.1377.40C
05.1377.14C

Dali & Push Version

05.1377.40CDA
05.1377.14CDA


Mains Dimming

05.1377.40CNI
05.1377.14CNI

Casambi

05.1377.40CCB
05.1377.14CCB






Luminous flux luminaire
3272 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	6539	0.83
2	1635	1.66
3	727	2.49
4	409	3.32
5	262	4.14





Luminous flux luminaire
2922 lm


@White (40) 750mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	5839	0.83
2	1460	1.66
3	649	2.49
4	365	3.32
5	234	4.14

Light Shadow Adjustable Trim 2 Spots

Power LED DC 900 mA 7W - 596 lm - 2700K/CRI 90 / 7W - 636 lm - 3000K/CRI 90







Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V). Pre-Installation frame not required.


E= External Finish
I= Internal Finish

Luminaria empotrable de 2 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno


Optic Spot 2700K

E I Non Dimmable
03.8884.40C
03.8884.14C
Dali Version
03.8884.40CDA
03.8884.14CDA
Mains Dimming
03.8884.40CNI
03.8884.14CNI
Casambi
03.8884.40CCB
03.8884.14CCB
Non Dimmable
03.8885.40C
03.8885.14C
Dali Version
03.8885.40CDA
03.8885.14CDA
Mains Dimming
03.8885.40CNI
03.8885.14CNI
Casambi
03.8885.40CCB
03.8885.14CCB
Non Dimmable
05.1401.40C
05.1401.14C
Dali Version
05.1401.40CDA
05.1401.14CDA
Mains Dimming
05.1401.40CNI
05.1401.14CNI
Casambi
05.1401.40CCB
05.1401.14CCB
Non Dimmable
05.1402.40C
05.1402.14C
Dali Version
05.1402.40CDA
05.1402.14CDA
Mains Dimming
05.1402.40CNI
05.1402.14CNI
Casambi
05.1402.40CCB
05.1402.14CCB



Optic Spot 3000K

E I Non Dimmable
03.8888.40C
03.8888.14C
Dali Version
03.8888.40CDA
03.8888.14CDA
Mains Dimming
03.8888.40CNI
03.8888.14CNI
Casambi
03.8888.40CCB
03.8888.14CCB
Non Dimmable
03.8889.40C
03.8889.14C
Dali Version
03.8889.40CDA
03.8889.14CDA
Mains Dimming
03.8889.40CNI
03.8889.14CNI
Casambi
03.8889.40CCB
03.8889.14CCB
Non Dimmable
05.1406.40C
05.1406.14C
Dali Version
05.1406.40CDA
05.1406.14CDA
Mains Dimming
05.1406.40CNI
05.1406.14CNI
Casambi
05.1406.40CCB
05.1406.14CCB
Non Dimmable
05.1407.40C
05.1407.14C
Dali Version
05.1407.40CDA
05.1407.14CDA
Mains Dimming
05.1407.40CNI
05.1407.14CNI
Casambi
05.1407.40CCB
05.1407.14CCB




Optic Medium
2700K

E I Non Dimmable
03.9300.40C
03.9300.14C
Dali Version
03.9300.40CDA
03.9300.14CDA
E I Mains Dimming
03.9300.40CNI
03.9300.14CNI
Casambi
03.9300.40CCB
03.9300.14CCB
Non Dimmable
03.9301.40C
03.9301.14C
Dali Version
03.9301.40CDA
03.9301.14CDA
Mains Dimming
03.9301.40CNI
03.9301.14CNI
Casambi
03.9301.40CCB
03.9301.14CCB
Non Dimmable
05.1411.40C
05.1411.14C
Dali Version
05.1411.40CDA
05.1411.14CDA
Mains Dimming
05.1411.40CNI
05.1411.14CNI
Casambi
05.1411.40CCB
05.1411.14CCB
Non Dimmable
05.1412.40C
05.1412.14C
Dali Version
05.1412.40CDA
05.1412.14CDA
Mains Dimming
05.1412.40CNI
05.1412.14CNI
Casambi
05.1412.40CCB
05.1412.14CCB



MEDIUM



Luminous flux luminaire
510 lm

@White (40)


Beam Angle:		23°
h(m)	E(lx)	D(m)
1	3423	0.40
2	856	0.80
3	380	1.20
4	214	1.60
5	137	2.00

Optic Medium
3000K

E I Non Dimmable
03.9310.40C
03.9310.14C
Dali Version
03.9310.40CDA
03.9310.14CDA
Mains Dimming
03.9310.40CNI
03.9310.14CNI
Casambi
03.9310.40CCB
03.9310.14CCB
Non Dimmable
03.9311.40C
03.9311.14C
Dali Version
03.9311.40CDA
03.9311.14CDA
Mains Dimming
03.9311.40CNI
03.9311.14CNI
Casambi
03.9311.40CCB
03.9311.14CCB
Non Dimmable
05.1416.40C
05.1416.14C
Dali Version
05.1416.40CDA
05.1416.14CDA
Mains Dimming
05.1416.40CNI
05.1416.14CNI
Casambi
05.1416.40CCB
05.1416.14CCB
Non Dimmable
05.1417.40C
05.1417.14C
Dali Version
05.1417.40CDA
05.1417.14CDA
Mains Dimming
05.1417.40CNI
05.1417.14CNI
Casambi
05.1417.40CCB
05.1417.14CCB



MEDIUM



Luminous flux luminaire
544 lm


@White (40)

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	3651	0.40
2	913	0.80
3	406	1.20
4	228	1.60
5	146	2.00

Light Shadow Adjustable Trim 2 Spots

Power LED DC 900 mA 7W - 596 lm - 2700K/CRI 90 / 7W - 636 lm - 3000K/CRI 90







Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V). Pre-Installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 2 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9305.40C
03.9305.14C
Dali Version
03.9305.40CDA
03.9305.14CDA
Mains Dimming
03.9305.40CNI
03.9305.14CNI
Casambi
03.9305.40CCB
03.9305.14CCB
Non Dimmable
03.9306.40C
03.9306.14C
Dali Version
03.9306.40CDA
03.9306.14CDA
Mains Dimming
03.9306.40CNI
03.9306.14CNI
Casambi
03.9306.40CCB
03.9306.14CCB
Non Dimmable
05.1421.40C
05.1421.14C
Dali Version
05.1421.40CDA
05.1421.14CDA
Mains Dimming
05.1421.40CNI
05.1421.14CNI
Casambi
05.1421.40CCB
05.1421.14CCB
Non Dimmable
05.1422.40C
05.1422.14C
Dali Version
05.1422.40CDA
05.1422.14CDA
Mains Dimming
05.1422.40CNI
05.1422.14CNI
Casambi
05.1422.40CCB
05.1422.14CCB

29°
FLOOD



Luminous flux luminaire
514 lm

@White (40)


Beam Angle: 29°

h(m)	E(lx)	D(m)
1	2070	0.51
2	517	1.03
3	230	1.54
4	129	2.05
5	83	2.57

Optic Flood 3000K

E I Non Dimmable
03.9315.40C
03.9315.14C
Dali Version
03.9315.40CDA
03.9315.14CDA
Mains Dimming
03.9315.40CNI
03.9315.14CNI
Casambi
03.9315.40CCB
03.9315.14CCB
Non Dimmable
03.9316.40C
03.9316.14C
Dali Version
03.9316.40CDA
03.9316.14CDA
Mains Dimming
03.9316.40CNI
03.9316.14CNI
Casambi
03.9316.40CCB
03.9316.14CCB
Non Dimmable
05.1426.40C
05.1426.14C
Dali Version
05.1426.40CDA
05.1426.14CDA
Mains Dimming
05.1426.40CNI
05.1426.14CNI
Casambi
05.1426.40CCB
05.1426.14CCB
Non Dimmable
05.1427.40C
05.1427.14C
Dali Version
05.1427.40CDA
05.1427.14CDA
Mains Dimming
05.1427.40CNI
05.1427.14CNI
Casambi
05.1427.40CCB
05.1427.14CCB

29°
FLOOD



Luminous flux luminaire
549 lm

@White (40)

Beam Angle: 29°


h(m)	E(lx)	D(m)
1	2211	0.51
2	553	1.03
3	246	1.54
4	138	2.05
5	88	2.57

Optic Wide Flood
2700K

E I Non Dimmable
03.7300.40C
03.7300.14C
Dali Version
03.7300.40CDA
03.7300.14CDA
Mains Dimming
03.7300.40CNI
03.7300.14CNI
Casambi
03.7300.40CCB
03.7300.14CCB
Non Dimmable
03.7301.40C
03.7301.14C
Dali Version
03.7301.40CDA
03.7301.14CDA
Mains Dimming
03.7301.40CNI
03.7301.14CNI
Casambi
03.7301.40CCB
03.7301.14CCB
Non Dimmable
05.1431.40C
05.1431.14C
Dali Version
05.1431.40CDA
05.1431.14CDA
Mains Dimming
05.1431.40CNI
05.1431.14CNI
Casambi
05.1431.40CCB
05.1431.14CCB
Non Dimmable
05.1432.40C
05.1432.14C
Dali Version
05.1432.40CDA
05.1432.14CDA
Mains Dimming
05.1432.40CNI
05.1432.14CNI
Casambi
05.1432.40CCB
05.1432.14CCB



WIDE FLOOD



Luminous flux luminaire
511 lm

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	1021	0.83
2	255	1.66
3	113	2.49
4	64	3.32
5	41	4.14


@White (40)

Optic Wide Flood
3000K

E I Non Dimmable
03.7304.40C
03.7304.14C
Dali Version
03.7304.40CDA
03.7304.14CDA
Mains Dimming
03.7304.40CNI
03.7304.14CNI
Casambi
03.7304.40CCB
03.7304.14CCB
Non Dimmable
03.7305.40C
03.7305.14C
Dali Version
03.7305.40CDA
03.7305.14CDA
Mains Dimming
03.7305.40CNI
03.7305.14CNI
Casambi
03.7305.40CCB
03.7305.14CCB
Non Dimmable
05.1436.40C
05.1436.14C
Dali Version
05.1436.40CDA
05.1436.14CDA
Mains Dimming
05.1436.40CNI
05.1436.14CNI
Casambi
05.1436.40CCB
05.1436.14CCB
Non Dimmable
05.1437.40C
05.1437.14C
Dali Version
05.1437.40CDA
05.1437.14CDA
Mains Dimming
05.1437.40CNI
05.1437.14CNI
Casambi
05.1437.40CCB
05.1437.14CCB



WIDE FLOOD



Luminous flux luminaire
545 lm

Beam Angle: 45°


h(m)	E(lx)	D(m)
1	1089	0.83
2	272	1.66
3	121	2.49
4	68	3.32
5	44	4.14

@White (40)

Light Shadow Adjustable Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V). Pre-Installation frame not required.


E= External Finish
I= Internal Finish

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8892.40C
03.8892.14C
Dali Version
03.8892.40CDA
03.8892.14CDA
Mains Dimming
03.8892.40CNI
03.8892.14CNI
Casambi
03.8892.40CCB
03.8892.14CCB
Non Dimmable
03.8893.40C
03.8893.14C
Dali Version
03.8893.40CDA
03.8893.14CDA
Mains Dimming
03.8893.40CNI
03.8893.14CNI
Casambi
03.8893.40CCB
03.8893.14CCB
Non Dimmable
05.1501.40C
05.1501.14C
Dali Version
05.1501.40CDA
05.1501.14CDA
Mains Dimming
05.1501.40CNI
05.1501.14CNI
Casambi
05.1501.40CCB
05.1501.14CCB
Non Dimmable
05.1502.40C
05.1502.14C
Dali Version
05.1502.40CDA
05.1502.14CDA
Mains Dimming
05.1502.40CNI
05.1502.14CNI
Casambi
05.1502.40CCB
05.1502.14CCB




Luminous flux luminaire
1060 lm

@White (40)

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	17109	0.20
2	4277	0.41
3	1901	0.61
4	1069	0.81
5	684	1.01

Optic Spot 3000K

E I Non Dimmable
03.8896.40C
03.8896.14C
Dali Version
03.8896.40CDA
03.8896.14CDA
Mains Dimming
03.8896.40CNI
03.8896.14CNI
Casambi
03.8896.40CCB
03.8896.14CCB
Non Dimmable
03.8897.40C
03.8897.14C
Dali Version
03.8897.40CDA
03.8897.14CDA
Mains Dimming
03.8897.40CNI
03.8897.14CNI
Casambi
03.8897.40CCB
03.8897.14CCB
Non Dimmable
05.1506.40C
05.1506.14C
Dali Version
05.1506.40CDA
05.1506.14CDA
Mains Dimming
05.1506.40CNI
05.1506.14CNI
Casambi
05.1506.40CCB
05.1506.14CCB
Non Dimmable
05.1507.40C
05.1507.14C
Dali Version
05.1507.40CDA
05.1507.14CDA
Mains Dimming
05.1507.40CNI
05.1507.14CNI
Casambi
05.1507.40CCB
05.1507.14CCB




Luminous flux luminaire
1131 lm

@White (40)

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	18255	0.20
2	4564	0.41
3	2028	0.61
4	1141	0.81
5	730	1.01

Optic Medium
2700K

E I Non Dimmable
03.9320.40C
03.9320.14C
Dali Version
03.9320.40CDA
03.9320.14CDA
Mains Dimming
03.9320.40CNI
03.9320.14CNI
Casambi
03.9320.40CCB
03.9320.14CCB
Non Dimmable
03.9321.40C
03.9321.14C
Dali Version
03.9321.40CDA
03.9321.14CDA
Mains Dimming
03.9321.40CNI
03.9321.14CNI
Casambi
03.9321.40CCB
03.9321.14CCB
Non Dimmable
05.1511.40C
05.1511.14C
Dali Version
05.1511.40CDA
05.1511.14CDA
Mains Dimming
05.1511.40CNI
05.1511.14CNI
Casambi
05.1511.40CCB
05.1511.14CCB
Non Dimmable
05.1512.40C
05.1512.14C
Dali Version
05.1512.40CDA
05.1512.14CDA
Mains Dimming
05.1512.40CNI
05.1512.14CNI
Casambi
05.1512.40CCB
05.1512.14CCB




Luminous flux luminaire
1020 lm

@White (40)

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	6846	0.40
2	1711	0.80
3	761	1.20
4	428	1.60
5	274	2.00

Optic Medium
3000K

E I Non Dimmable
03.9330.40C
03.9330.14C
Dali Version
03.9330.40CDA
03.9330.14CDA
Mains Dimming
03.9330.40CNI
03.9330.14CNI
Casambi
03.9330.40CCB
03.9330.14CCB
Non Dimmable
03.9331.40C
03.9331.14C
Dali Version
03.9331.40CDA
03.9331.14CDA
Mains Dimming
03.9331.40CNI
03.9331.14CNI
Casambi
03.9331.40CCB
03.9331.14CCB
Non Dimmable
05.1516.40C
05.1516.14C
Dali Version
05.1516.40CDA
05.1516.14CDA
Mains Dimming
05.1516.40CNI
05.1516.14CNI
Casambi
05.1516.40CCB
05.1516.14CCB
Non Dimmable
05.1517.40C
05.1517.14C
Dali Version
05.1517.40CDA
05.1517.14CDA
Mains Dimming
05.1517.40CNI
05.1517.14CNI
Casambi
05.1517.40CCB
05.1517.14CCB



Luminous flux luminaire
1088 lm


@White (40)

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	7302	0.40
2	1826	0.80
3	811	1.20
4	456	1.60
5	292	2.00

Light Shadow Adjustable Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V). Pre-Installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9325.40C
03.9325.14C
Dali Version
03.9325.40CDA
03.9325.14CDA
Mains Dimming
03.9325.40CNI
03.9325.14CNI
Casambi
03.9325.40CCB
03.9325.14CCB
Non Dimmable
03.9326.40C
03.9326.14C
Dali Version
03.9326.40CDA
03.9326.14CDA
Mains Dimming
03.9326.40CNI
03.9326.14CNI
Casambi
03.9326.40CCB
03.9326.14CCB
Non Dimmable
05.1521.40C
05.1521.14C
Dali Version
05.1521.40CDA
05.1521.14CDA
Mains Dimming
05.1521.40CNI
05.1521.14CNI
Casambi
05.1521.40CCB
05.1521.14CCB
Non Dimmable
05.1522.40C
05.1522.14C
Dali Version
05.1522.40CDA
05.1522.14CDA
Mains Dimming
05.1522.40CNI
05.1522.14CNI
Casambi
05.1522.40CCB
05.1522.14CCB

29°
FLOOD



Luminous flux luminaire
1029 lm

@White (40)


Beam Angle: 29°

h(m)	E(lx)	D(m)
1	4143	0.51
2	1036	1.03
3	460	1.54
4	259	2.05
5	166	2.57

Optic Flood 3000K

E I Non Dimmable
03.9335.40C
03.9335.14C
Dali Version
03.9335.40CDA
03.9335.14CDA
Mains Dimming
03.9335.40CNI
03.9335.14CNI
Casambi
03.9335.40CCB
03.9335.14CCB
Non Dimmable
03.9336.40C
03.9336.14C
Dali Version
03.9336.40CDA
03.9336.14CDA
Mains Dimming
03.9336.40CNI
03.9336.14CNI
Casambi
03.9336.40CCB
03.9336.14CCB
Non Dimmable
05.1526.40C
05.1526.14C
Dali Version
05.1526.40CDA
05.1526.14CDA
Mains Dimming
05.1526.40CNI
05.1526.14CNI
Casambi
05.1526.40CCB
05.1526.14CCB
Non Dimmable
05.1527.40C
05.1527.14C
Dali Version
05.1527.40CDA
05.1527.14CDA
Mains Dimming
05.1527.40CNI
05.1527.14CNI
Casambi
05.1527.40CCB
05.1527.14CCB

29°
FLOOD



Luminous flux luminaire
1098 lm

@White (40)

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	4421	0.51
2	1105	1.03
3	491	1.54
4	276	2.05
5	177	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.7308.40C
03.7308.14C

Dali Version

03.7308.40CDA
03.7308.14CDA

Mains Dimming

03.7308.40CNI
03.7308.14CNI

Casambi

03.7308.40CCB
03.7308.14CCB

Non Dimmable

03.7309.40C
03.7309.14C

Dali Version

03.7309.40CDA
03.7309.14CDA

Mains Dimming

03.7309.40CNI
03.7309.14CNI

Casambi

03.7309.40CCB
03.7309.14CCB

Non Dimmable

05.1531.40C
05.1531.14C

Dali Version

05.1531.40CDA
05.1531.14CDA

Mains Dimming

05.1531.40CNI
05.1531.14CNI

Casambi

05.1531.40CCB
05.1531.14CCB

Non Dimmable

05.1532.40C
05.1532.14C

Dali Version

05.1532.40CDA
05.1532.14CDA

Mains Dimming


05.1532.40CNI
05.1532.14CNI

Casambi

05.1532.40CCB
05.1532.14CCB



WIDE FLOOD



Luminous flux luminaire 1022 lm

@White (40)

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	2042	0.83
2	511	1.66
3	227	2.49
4	128	3.32
5	82	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.7312.40C
03.7312.14C

Dali Version

03.7312.40CDA
03.7312.14CDA

Mains Dimming

03.7312.40CNI
03.7312.14CNI

Casambi

03.7312.40CCB
03.7312.14CCB

Non Dimmable

03.7313.40C
03.7313.14C

Dali Version

03.7313.40CDA
03.7313.14CDA

Mains Dimming

03.7313.40CNI
03.7313.14CNI

Casambi

03.7313.40CCB
03.7313.14CCB

Non Dimmable

05.1536.40C
05.1536.14C

Dali Version

05.1536.40CDA
05.1536.14CDA

Mains Dimming

05.1536.40CNI
05.1536.14CNI

Casambi

05.1536.40CCB
05.1536.14CCB

Non Dimmable

05.1537.40C
05.1537.14C

Dali Version

05.1537.40CDA
05.1537.14CDA

Mains Dimming


05.1537.40CNI
05.1537.14CNI

Casambi

05.1537.40CCB
05.1537.14CCB



WIDE FLOOD



Luminous flux luminaire 1091 lm

@White (40)


Beam Angle: 45°

h(m)	E(lx)	D(m)
1	2180	0.83
2	545	1.66
3	242	2.49
4	136	3.32
5	87	4.14

Light Shadow Adjustable Trim 8 Spots

Power LED DC 900 mA 21,6W - 2384 lm - 2700K/CRI 90 / 21,6W - 2544 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 18,6W - 1984 lm - 2700K/CRI 90 / 18,6W - 2120 lm - 3000K/CRI 90







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V). Pre-Installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 8 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8900.40C
03.8900.14C
Dali Version
03.8900.40CDA
03.8900.14CDA
Mains Dimming
03.8900.40CNI
03.8900.14CNI
Casambi
03.8900.40CCB
03.8900.14CCB
Non Dimmable
03.8901.40C
03.8901.14C
Dali Version
03.8901.40CDA
03.8901.14CDA
Mains Dimming
03.8901.40CNI
03.8901.14CNI
Casambi
03.8901.40CCB
03.8901.14CCB
Non Dimmable
05.1601.40C
05.1601.14C
Dali Version
05.1601.40CDA
05.1601.14CDA
Mains Dimming
05.1601.40CNI
05.1601.14CNI
Casambi
05.1601.40CCB
05.1601.14CCB
Non Dimmable
05.1602.40C
05.1602.14C
Dali Version
05.1602.40CDA
05.1602.14CDA
Mains Dimming
05.1602.40CNI
05.1602.14CNI
Casambi
05.1602.40CCB
05.1602.14CCB

12° SPOT




Luminous flux luminaire 2120 lm

@White (40) 900mA

Beam Angle:		12°
h(m)	E(lx)	D(m)
1	34219	0.20
2	8555	0.41
3	3802	0.61
4	2139	0.81
5	1369	1.01

12° SPOT



Luminous flux luminaire 1800 lm


@White (40) 750mA

Beam Angle:		12°
h(m)	E(lx)	D(m)
1	29054	0.20
2	7263	0.41
3	3228	0.61
4	1816	0.81
5	1162	1.01

Optic Spot 3000K

E I Non Dimmable
03.8904.40C
03.8904.14C
Dali Version
03.8904.40CDA
03.8904.14CDA
Mains Dimming
03.8904.40CNI
03.8904.14CNI
Casambi
03.8904.40CCB
03.8904.14CCB
Non Dimmable
03.8905.40C
03.8905.14C
Dali Version
03.8905.40CDA
03.8905.14CDA
Mains Dimming
03.8905.40CNI
03.8905.14CNI
Casambi
03.8905.40CCB
03.8905.14CCB
Non Dimmable
05.1606.40C
05.1606.14C
Dali Version
05.1606.40CDA
05.1606.14CDA
Mains Dimming
05.1606.40CNI
05.1606.14CNI
Casambi
05.1606.40CCB
05.1606.14CCB
Non Dimmable
05.1607.40C
05.1607.14C
Dali Version
05.1607.40CDA
05.1607.14CDA
Mains Dimming
05.1607.40CNI
05.1607.14CNI
Casambi
05.1607.40CCB
05.1607.14CCB

12° SPOT




Luminous flux luminaire 2262 lm

@White (40) 900mA

Beam Angle:		12°
h(m)	E(lx)	D(m)
1	36511	0.20
2	9128	0.41
3	4057	0.61
4	2282	0.81
5	1460	1.01

12° SPOT



Luminous flux luminaire 2020 lm

@White (40) 750mA

Beam Angle:		12°
h(m)	E(lx)	D(m)
1	32605	0.20
2	8151	0.41
3	3623	0.61
4	2038	0.81
5	1304	1.01

Optic Medium 2700K

E I Non Dimmable

03.9340.40C
03.9340.14C

Dali Version

03.9340.40CDA
03.9340.14CDA

Mains Dimming

03.9340.40CNI
03.9340.14CNI

Casambi

03.9340.40CCB
03.9340.14CCB

Non Dimmable

03.9341.40C
03.9341.14C

Dali Version

03.9341.40CDA
03.9341.14CDA

Mains Dimming

03.9341.40CNI
03.9341.14CNI

Casambi

03.9341.40CCB
03.9341.14CCB

Non Dimmable

05.1611.40C
05.1611.14C

Dali Version

05.1611.40CDA
05.1611.14CDA

Mains Dimming

05.1611.40CNI
05.1611.14CNI

Casambi

05.1611.40CCB
05.1611.14CCB

Non Dimmable

05.1612.40C
05.1612.14C

Dali Version

05.1612.40CDA
05.1612.14CDA


Mains Dimming

05.1612.40CNI
05.1612.14CNI

Casambi

05.1612.40CCB
05.1612.14CCB






Luminous flux luminaire
2040 lm

@White (40) 900mA

Beam Angle:	23°
h(m)	E(lx) D(m)
1	13692 0.40
2	3423 0.80
3	1521 1.20
4	856 1.60
5	548 2.00





Luminous flux luminaire
1732 lm

@White (40) 750mA

Beam Angle:	23°
h(m)	E(lx) D(m)
1	11625 0.40
2	2906 0.80
3	1292 1.20
4	727 1.60
5	465 2.00

Optic Medium 3000K

E I Non Dimmable

03.9350.40C
03.9350.14C

Dali Version

03.9350.40CDA
03.9350.14CDA

Mains Dimming

03.9350.40CNI
03.9350.14CNI

Casambi

03.9350.40CCB
03.9350.14CCB

Non Dimmable

03.9351.40C
03.9351.14C

Dali Version

03.9351.40CDA
03.9351.14CDA

Mains Dimming

03.9351.40CNI
03.9351.14CNI

Casambi

03.9351.40CCB
03.9351.14CCB

Non Dimmable

05.1616.40C
05.1616.14C

Dali Version

05.1616.40CDA
05.1616.14CDA

Mains Dimming

05.1616.40CNI
05.1616.14CNI

Casambi

05.1616.40CCB
05.1616.14CCB

Non Dimmable

05.1617.40C
05.1617.14C

Dali Version

05.1617.40CDA
05.1617.14CDA


Mains Dimming

05.1617.40CNI
05.1617.14CNI

Casambi

05.1617.40CCB
05.1617.14CCB






Luminous flux luminaire
2177 lm

@White (40) 900mA

Beam Angle:	23°
h(m)	E(lx) D(m)
1	14611 0.40
2	3653 0.80
3	1623 1.20
4	913 1.60
5	584 2.00





Luminous flux luminaire
1944 lm


@White (40) 750mA

Beam Angle:	23°
h(m)	E(lx) D(m)
1	13047 0.40
2	3262 0.80
3	1450 1.20
4	815 1.60
5	522 2.00

Light Shadow Adjustable Trim 8 Spots

Power LED DC 900 mA 21,6W - 2384 lm - 2700K/CRI 90 / 21,6W - 2544 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 18,6W - 1984 lm - 2700K/CRI 90 / 18,6W - 2120 lm - 3000K/CRI 90







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V). Pre-Installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 8 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9345.40C
03.9345.14C
Dali Version
03.9345.40CDA
03.9345.14CDA
Mains Dimming
03.9345.40CNI
03.9345.14CNI
Casambi
03.9345.40CCB
03.9345.14CCB
Non Dimmable
03.9346.40C
03.9346.14C
Dali Version
03.9346.40CDA
03.9346.14CDA
Mains Dimming
03.9346.40CNI
03.9346.14CNI
Casambi
03.9346.40CCB
03.9346.14CCB
Non Dimmable
05.1621.40C
05.1621.14C
Dali Version
05.1621.40CDA
05.1621.14CDA
Mains Dimming
05.1621.40CNI
05.1621.14CNI
Casambi
05.1621.40CCB
05.1621.14CCB
Non Dimmable
05.1622.40C
05.1622.14C
Dali Version
05.1622.40CDA
05.1622.14CDA
Mains Dimming
05.1622.40CNI
05.1622.14CNI
Casambi
05.1622.40CCB
05.1622.14CCB

29° FLOOD




Luminous flux luminaire 2057 lm
@White (40) 900mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	8282	0.51
2	2071	1.03
3	920	1.54
4	518	2.05
5	331	2.57

29° FLOOD



Luminous flux luminaire 1747 lm
@White (40) 750mA


Beam Angle: 29°

h(m)	E(lx)	D(m)
1	7034	0.51
2	1759	1.03
3	782	1.54
4	440	2.05
5	281	2.57

Optic Flood 3000K

E I Non Dimmable
03.9355.40C
03.9355.14C
Dali Version
03.9355.40CDA
03.9355.14CDA
Mains Dimming
03.9355.40CNI
03.9355.14CNI
Casambi
03.9355.40CCB
03.9355.14CCB
Non Dimmable
03.9356.40C
03.9356.14C
Dali Version
03.9356.40CDA
03.9356.14CDA
Mains Dimming
03.9356.40CNI
03.9356.14CNI
Casambi
03.9356.40CCB
03.9356.14CCB
Non Dimmable
05.1626.40C
05.1626.14C
Dali Version
05.1626.40CDA
05.1626.14CDA
Mains Dimming
05.1626.40CNI
05.1626.14CNI
Casambi
05.1626.40CCB
05.1626.14CCB
Non Dimmable
05.1627.40C
05.1627.14C
Dali Version
05.1627.40CDA
05.1627.14CDA
Mains Dimming
05.1627.40CNI
05.1627.14CNI
Casambi
05.1627.40CCB
05.1627.14CCB

29° FLOOD




Luminous flux luminaire 2195 lm
@White (40) 900mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	8838	0.51
2	2210	1.03
3	982	1.54
4	552	2.05
5	354	2.57

29° FLOOD



Luminous flux luminaire 1961 lm
@White (40) 750mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	7896	0.51
2	1974	1.03
3	877	1.54
4	493	2.05
5	316	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.7316.40C
03.7316.14C

Dali Version

03.7316.40CDA
03.7316.14CDA

Mains Dimming

03.7316.40CNI
03.7316.14CNI

Casambi

03.7316.40CCB
03.7316.14CCB

Non Dimmable

03.7317.40C
03.7317.14C

Dali Version

03.7317.40CDA
03.7317.14CDA

Mains Dimming

03.7317.40CNI
03.7317.14CNI

Casambi

03.7317.40CCB
03.7317.14CCB

Non Dimmable

05.1631.40C
05.1631.14C

Dali Version

05.1631.40CDA
05.1631.14CDA

Mains Dimming

05.1631.40CNI
05.1631.14CNI

Casambi

05.1631.40CCB
05.1631.14CCB

Non Dimmable

05.1632.40C
05.1632.14C

Dali Version

05.1632.40CDA
05.1632.14CDA


Mains Dimming

05.1632.40CNI
05.1632.14CNI

Casambi

05.1632.40CCB
05.1632.14CCB






Luminous flux luminaire
2044 lm

@White (40) 900mA

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	4085	0.83
2	1021	1.66
3	454	2.49
4	255	3.32
5	163	4.14





Luminous flux luminaire
1736 lm

@White (40) 750mA

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	3469	0.83
2	867	1.66
3	385	2.49
4	217	3.32
5	139	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.7320.40C
03.7320.14C

Dali Version

03.7320.40CDA
03.7320.14CDA

Mains Dimming

03.7320.40CNI
03.7320.14CNI

Casambi

03.7320.40CCB
03.7320.14CCB

Non Dimmable

03.7321.40C
03.7321.14C

Dali Version

03.7321.40CDA
03.7321.14CDA

Mains Dimming

03.7321.40CNI
03.7321.14CNI

Casambi

03.7321.40CCB
03.7321.14CCB

Non Dimmable

05.1636.40C
05.1636.14C

Dali Version

05.1636.40CDA
05.1636.14CDA

Mains Dimming

05.1636.40CNI
05.1636.14CNI

Casambi

05.1636.40CCB
05.1636.14CCB

Non Dimmable

05.1637.40C
05.1637.14C

Dali Version

05.1637.40CDA
05.1637.14CDA


Mains Dimming

05.1637.40CNI
05.1637.14CNI

Casambi

05.1637.40CCB
05.1637.14CCB






Luminous flux luminaire
2181 lm

@White (40) 900mA

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	4358	0.83
2	1090	1.66
3	484	2.49
4	272	3.32
5	174	4.14





Luminous flux luminaire
1948 lm

@White (40) 750mA


Beam Angle: 45°


h(m)	E(lx)	D(m)
1	3893	0.83
2	973	1.66
3	433	2.49
4	243	3.32
5	156	4.14

Light Shadow Adjustable Trim 12 Spots

Power LED DC 900 mA 32,4W - 3576 lm - 2700K/CRI 90 / 32,4W - 3816 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 28W - 2976 lm - 2700K/CRI 90 / 28W - 3180 lm - 3000K/CRI 90







Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 12 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8908.40C
03.8908.14C
Dali & Push Version
03.8908.40CDA
03.8908.14CDA
Mains Dimming
03.8908.40CNI
03.8908.14CNI
Casambi
03.8908.40CCB
03.8908.14CCB
Non Dimmable
03.8909.40C
03.8909.14C
Dali & Push Version
03.8909.40CDA
03.8909.14CDA
Mains Dimming
03.8909.40CNI
03.8909.14CNI
Casambi
03.8909.40CCB
03.8909.14CCB
Non Dimmable
05.1701.40C
05.1701.14C
Dali & Push Version
05.1701.40CDA
05.1701.14CDA
Mains Dimming
05.1701.40CNI
05.1701.14CNI
Casambi
05.1701.40CCB
05.1701.14CCB
Non Dimmable
05.1702.40C
05.1702.14C
Dali & Push Version
05.1702.40CDA
05.1702.14CDA
Mains Dimming
05.1702.40CNI
05.1702.14CNI
Casambi
05.1702.40CCB
05.1702.14CCB

12° SPOT




Luminous flux luminaire 3180 lm

@White (40) 900mA

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	51328	0.20
2	12832	0.41
3	5703	0.61
4	3208	0.81
5	2053	1.01

12° SPOT



Luminous flux luminaire 2849 lm

@White (40) 750mA


Beam Angle: 12°

h(m)	E(lx)	D(m)
1	45985	0.20
2	11496	0.41
3	5109	0.61
4	2874	0.81
5	1839	1.01

Optic Spot 3000K

E I Non Dimmable
03.8912.40C
03.8912.14C
Dali & Push Version
03.8912.40CDA
03.8912.14CDA
Mains Dimming
03.8912.40CNI
03.8912.14CNI
Casambi
03.8912.40CCB
03.8912.14CCB
Non Dimmable
03.8913.40C
03.8913.14C
Dali & Push Version
03.8913.40CDA
03.8913.14CDA
Mains Dimming
03.8913.40CNI
03.8913.14CNI
Casambi
03.8913.40CCB
03.8913.14CCB
Non Dimmable
05.1706.40C
05.1706.14C
Dali & Push Version
05.1706.40CDA
05.1706.14CDA
Mains Dimming
05.1706.40CNI
05.1706.14CNI
Casambi
05.1706.40CCB
05.1706.14CCB
Non Dimmable
05.1707.40C
05.1707.14C
Dali & Push Version
05.1707.40CDA
05.1707.14CDA
Mains Dimming
05.1707.40CNI
05.1707.14CNI
Casambi
05.1707.40CCB
05.1707.14CCB

12° SPOT




Luminous flux luminaire 3394 lm

@White (40) 900mA

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	54782	0.20
2	13696	0.41
3	6087	0.61
4	3424	0.81
5	2191	1.01

12° SPOT



Luminous flux luminaire 3031 lm

@White (40) 750mA

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	48923	0.20
2	12231	0.41
3	5436	0.61
4	3058	0.81
5	1957	1.01

Optic Medium 2700K

E I Non Dimmable

03.9360.40C
03.9360.14C

Dali & Push Version

03.9360.40CDA
03.9360.14CDA

Mains Dimming

03.9360.40CNI
03.9360.14CNI

Casambi

03.9360.40CCB
03.9360.14CCB

Non Dimmable

03.9361.40C
03.9361.14C

Dali & Push Version

03.9361.40CDA
03.9361.14CDA

Mains Dimming

03.9361.40CNI
03.9361.14CNI

Casambi

03.9361.40CCB
03.9361.14CCB

Non Dimmable

05.1711.40C
05.1711.14C

Dali & Push Version

05.1711.40CDA
05.1711.14CDA

Mains Dimming

05.1711.40CNI
05.1711.14CNI

Casambi

05.1711.40CCB
05.1711.14CCB

Non Dimmable

05.1712.40C
05.1712.14C

Dali & Push Version

05.1712.40CDA
05.1712.14CDA


Mains Dimming

05.1712.40CNI
05.1712.14CNI

Casambi

05.1712.40CCB
05.1712.14CCB

23°
MEDIUM




Luminous flux luminaire
3060 lm

@White (40) 900mA

Beam Angle:	23°
h(m)	E(lx) D(m)
1	20538 0.40
2	5134 0.80
3	2282 1.20
4	1284 1.60
5	822 2.00

23°
MEDIUM



Luminous flux luminaire
2742 lm

@White (40) 750mA

Beam Angle:	23°
h(m)	E(lx) D(m)
1	18403 0.40
2	4601 0.80
3	2045 1.20
4	1150 1.60
5	736 2.00

Optic Medium 3000K

E I Non Dimmable

03.9370.40C
03.9370.14C

Dali & Push Version

03.9370.40CDA
03.9370.14CDA

Mains Dimming

03.9370.40CNI
03.9370.14CNI

Casambi

03.9370.40CCB
03.9370.14CCB

Non Dimmable

03.9371.40C
03.9371.14C

Dali & Push Version

03.9371.40CDA
03.9371.14CDA

Mains Dimming

03.9371.40CNI
03.9371.14CNI

Casambi

03.9371.40CCB
03.9371.14CCB

Non Dimmable

05.1716.40C
05.1716.14C

Dali & Push Version

05.1716.40CDA
05.1716.14CDA

Mains Dimming

05.1716.40CNI
05.1716.14CNI

Casambi

05.1716.40CCB
05.1716.14CCB

Non Dimmable

05.1717.40C
05.1717.14C

Dali & Push Version

05.1717.40CDA
05.1717.14CDA


Mains Dimming

05.1717.40CNI
05.1717.14CNI

Casambi

05.1717.40CCB
05.1717.14CCB

23°
MEDIUM




Luminous flux luminaire
3265 lm

@White (40) 900mA

Beam Angle:	23°
h(m)	E(lx) D(m)
1	21913 0.40
2	5478 0.80
3	2435 1.20
4	1370 1.60
5	877 2.00

23°
MEDIUM



Luminous flux luminaire
2916 lm


@White (40) 750mA


Beam Angle:	23°
h(m)	E(lx) D(m)
1	19571 0.40
2	4893 0.80
3	2175 1.20
4	1223 1.60
5	783 2.00

Light Shadow Adjustable Trim 12 Spots

Power LED DC 900 mA 32,4W - 3576 lm - 2700K/CRI 90 / 32,4W - 3816 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 28W - 2976 lm - 2700K/CRI 90 / 28W - 3180 lm - 3000K/CRI 90







Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V). Pre-installation frame not required.

E= External Finish
I= Internal Finish


Luminaria empotrable de 12 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación no necesario.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9365.40C
03.9365.14C
Dali & Push Version
03.9365.40CDA
03.9365.14CDA
Mains Dimming
03.9365.40CNI
03.9365.14CNI
Casambi
03.9365.40CCB
03.9365.14CCB
Non Dimmable
03.9366.40C
03.9366.14C
Dali & Push Version
03.9366.40CDA
03.9366.14CDA
Mains Dimming
03.9366.40CNI
03.9366.14CNI
Casambi
03.9366.40CCB
03.9366.14CCB
Non Dimmable
05.1721.40C
05.1721.14C
Dali & Push Version
05.1721.40CDA
05.1721.14CDA
Mains Dimming
05.1721.40CNI
05.1721.14CNI
Casambi
05.1721.40CCB
05.1721.14CCB
Non Dimmable
05.1722.40C
05.1722.14C
Dali & Push Version
05.1722.40CDA
05.1722.14CDA
Mains Dimming
05.1722.40CNI
05.1722.14CNI
Casambi
05.1722.40CCB
05.1722.14CCB

29° FLOOD




Luminous flux luminaire 3086 lm
@White (40) 900mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	12426	0.51
2	3106	1.03
3	1381	1.54
4	777	2.05
5	497	2.57

29° FLOOD



Luminous flux luminaire 2765 lm
@White (40) 750mA


Beam Angle: 29°

h(m)	E(lx)	D(m)
1	11133	0.51
2	2783	1.03
3	1237	1.54
4	696	2.05
5	445	2.57

Optic Flood 3000K

E I Non Dimmable
03.9375.40C
03.9375.14C
Dali & Push Version
03.9375.40CDA
03.9375.14CDA
Mains Dimming
03.9375.40CNI
03.9375.14CNI
Casambi
03.9375.40CCB
03.9375.14CCB
Non Dimmable
03.9376.40C
03.9376.14C
Dali & Push Version
03.9376.40CDA
03.9376.14CDA
Mains Dimming
03.9376.40CNI
03.9376.14CNI
Casambi
03.9376.40CCB
03.9376.14CCB
Non Dimmable
05.1726.40C
05.1726.14C
Dali & Push Version
05.1726.40CDA
05.1726.14CDA
Mains Dimming
05.1726.40CNI
05.1726.14CNI
Casambi
05.1726.40CCB
05.1726.14CCB
Non Dimmable
05.1727.40C
05.1727.14C
Dali & Push Version
05.1727.40CDA
05.1727.14CDA
Mains Dimming
05.1727.40CNI
05.1727.14CNI
Casambi
05.1727.40CCB
05.1727.14CCB

29° FLOOD




Luminous flux luminaire 3293 lm
@White (40) 900mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	13259	0.51
2	3315	1.03
3	1473	1.54
4	829	2.05
5	530	2.57

29° FLOOD



Luminous flux luminaire 2941 lm
@White (40) 750mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	11842	0.51
2	2960	1.03
3	1316	1.54
4	740	2.05
5	474	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.7324.40C
03.7324.14C

Dali & Push Version

03.7324.40CDA
03.7324.14CDA

Mains Dimming

03.7324.40CNI
03.7324.14CNI

Casambi

03.7324.40CCB
03.7324.14CCB

Non Dimmable

03.7325.40C
03.7325.14C

Dali & Push Version

03.7325.40CDA
03.7325.14CDA

Mains Dimming

03.7325.40CNI
03.7325.14CNI

Casambi

03.7325.40CCB
03.7325.14CCB

Non Dimmable

05.1731.40C
05.1731.14C

Dali & Push Version

05.1731.40CDA
05.1731.14CDA

Mains Dimming

05.1731.40CNI
05.1731.14CNI

Casambi

05.1731.40CCB
05.1731.14CCB

Non Dimmable

05.1732.40C
05.1732.14C

Dali & Push Version

05.1732.40CDA
05.1732.14CDA


Mains Dimming

05.1732.40CNI
05.1732.14CNI

Casambi

05.1732.40CCB
05.1732.14CCB

45° WIDE FLOOD




Luminous flux luminaire
3066 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	6127	0.83
2	1532	1.66
3	681	2.49
4	383	3.32
5	245	4.14

45° WIDE FLOOD



Luminous flux luminaire
2747 lm

@White (40) 750mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	5490	0.83
2	1372	1.66
3	610	2.49
4	343	3.32
5	220	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.7328.40C
03.7328.14C

Dali & Push Version

03.7328.40CDA
03.7328.14CDA

Mains Dimming

03.7328.40CNI
03.7328.14CNI

Casambi

03.7328.40CCB
03.7328.14CCB

Non Dimmable

03.7329.40C
03.7329.14C

Dali & Push Version

03.7329.40CDA
03.7329.14CDA

Mains Dimming

03.7329.40CNI
03.7329.14CNI

Casambi

03.7329.40CCB
03.7329.14CCB

Non Dimmable

05.1736.40C
05.1736.14C

Dali & Push Version

05.1736.40CDA
05.1736.14CDA

Mains Dimming

05.1736.40CNI
05.1736.14CNI

Casambi

05.1736.40CCB
05.1736.14CCB

Non Dimmable

05.1737.40C
05.1737.14C

Dali & Push Version

05.1737.40CDA
05.1737.14CDA


Mains Dimming

05.1737.40CNI
05.1737.14CNI

Casambi

05.1737.40CCB
05.1737.14CCB

45° WIDE FLOOD




Luminous flux luminaire
3272 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	6539	0.83
2	1635	1.66
3	727	2.49
4	409	3.32
5	262	4.14

45° WIDE FLOOD



Luminous flux luminaire
2922 lm


@White (40) 750mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	5839	0.83
2	1460	1.66
3	649	2.49
4	365	3.32
5	234	4.14

Light Shadow Adjustable No Trim 2 Spots

Power LED DC 900 mA 7W - 596 lm - 2700K/CRI 90 / 7W - 636 lm - 3000K/CRI 90







Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish


Luminaria empotrable de 2 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8916.40C
03.8916.14C
Dali Version
03.8916.40CDA
03.8916.14CDA
Mains Dimming
03.8916.40CNI
03.8916.14CNI
Casambi
03.8916.40CCB
03.8916.14CCB
Non Dimmable
03.8917.40C
03.8917.14C
Dali Version
03.8917.40CDA
03.8917.14CDA
Mains Dimming
03.8917.40CNI
03.8917.14CNI
Casambi
03.8917.40CCB
03.8917.14CCB
Non Dimmable
05.1441.40C
05.1441.14C
Dali Version
05.1441.40CDA
05.1441.14CDA
Mains Dimming
05.1441.40CNI
05.1441.14CNI
Casambi
05.1441.40CCB
05.1441.14CCB
Non Dimmable
05.1442.40C
05.1442.14C
Dali Version
05.1442.40CDA
05.1442.14CDA
Mains Dimming
05.1442.40CNI
05.1442.14CNI
Casambi
05.1442.40CCB
05.1442.14CCB

12°
SPOT



Luminous flux luminaire
530 lm


@White (40)

Beam Angle:		12°
h(m)	E(lx)	D(m)
1	8555	0.20
2	2139	0.41
3	951	0.61
4	535	0.81
5	342	1.01

Optic Spot 3000K

E I Non Dimmable
03.8920.40C
03.8920.14C
Dali Version
03.8920.40CDA
03.8920.14CDA
Mains Dimming
03.8920.40CNI
03.8920.14CNI
Casambi
03.8920.40CCB
03.8920.14CCB
Non Dimmable
03.8921.40C
03.8921.14C
Dali Version
03.8921.40CDA
03.8921.14CDA
Mains Dimming
03.8921.40CNI
03.8921.14CNI
Casambi
03.8921.40CCB
03.8921.14CCB
Non Dimmable
05.1446.40C
05.1446.14C
Dali Version
05.1446.40CDA
05.1446.14CDA
Mains Dimming
05.1446.40CNI
05.1446.14CNI
Casambi
05.1446.40CCB
05.1446.14CCB
Non Dimmable
05.1447.40C
05.1447.14C
Dali Version
05.1447.40CDA
05.1447.14CDA
Mains Dimming
05.1447.40CNI
05.1447.14CNI
Casambi
05.1447.40CCB
05.1447.14CCB

12°
SPOT




Luminous flux luminaire
566 lm

@White (40)

Beam Angle:		12°
h(m)	E(lx)	D(m)
1	9136	0.20
2	2284	0.41
3	1015	0.61
4	571	0.81
5	365	1.01

Optic Medium
2700K

E I Non Dimmable
03.9400.40C
03.9400.14C
Dali Version
03.9400.40CDA
03.9400.14CDA
Mains Dimming
03.9400.40CNI
03.9400.14CNI
Casambi
03.9400.40CCB
03.9400.14CCB
Non Dimmable
03.9401.40C
03.9401.14C
Dali Version
03.9401.40CDA
03.9401.14CDA
Mains Dimming
03.9401.40CNI
03.9401.14CNI
Casambi
03.9401.40CCB
03.9401.14CCB
Non Dimmable
05.1451.40C
05.1451.14C
Dali Version
05.1451.40CDA
05.1451.14CDA
Mains Dimming
05.1451.40CNI
05.1451.14CNI
Casambi
05.1451.40CCB
05.1451.14CCB
Non Dimmable
05.1452.40C
05.1452.14C
Dali Version
05.1452.40CDA
05.1452.14CDA
Mains Dimming
05.1452.40CNI
05.1452.14CNI
Casambi
05.1452.40CCB
05.1452.14CCB




Luminous flux luminaire
510 lm

@White (40)

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	3423	0.40
2	856	0.80
3	380	1.20
4	214	1.60
5	137	2.00

Optic Medium
3000K

E I Non Dimmable
03.9410.40C
03.9410.14C
Dali Version
03.9410.40CDA
03.9410.14CDA
Mains Dimming
03.9410.40CNI
03.9410.14CNI
Casambi
03.9410.40CCB
03.9410.14CCB
Non Dimmable
03.9411.40C
03.9411.14C
Dali Version
03.9411.40CDA
03.9411.14CDA
Mains Dimming
03.9411.40CNI
03.9411.14CNI
Casambi
03.9411.40CCB
03.9411.14CCB
Non Dimmable
05.1456.40C
05.1456.14C
Dali Version
05.1456.40CDA
05.1456.14CDA
Mains Dimming
05.1456.40CNI
05.1456.14CNI
Casambi
05.1456.40CCB
05.1456.14CCB
Non Dimmable
05.1457.40C
05.1457.14C
Dali Version
05.1457.40CDA
05.1457.14CDA
Mains Dimming
05.1457.40CNI
05.1457.14CNI
Casambi
05.1457.40CCB
05.1457.14CCB



Luminous flux luminaire
544 lm


@White (40)

Beam Angle:		23°
h(m)	E(lx)	D(m)
1	3651	0.40
2	913	0.80
3	406	1.20
4	228	1.60
5	146	2.00

Light Shadow Adjustable No Trim 2 Spots

Power LED DC 900 mA 7W - 596 lm - 2700K/CRI 90 / 7W - 636 lm - 3000K/CRI 90







Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.


E= External Finish
I= Internal Finish

Luminaria empotrable de 2 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9405.40C
03.9405.14C
Dali Version
03.9405.40CDA
03.9405.14CDA
Mains Dimming
03.9405.40CNI
03.9405.14CNI
Casambi
03.9405.40CCB
03.9405.14CCB
Non Dimmable
03.9406.40C
03.9406.14C
Dali Version
03.9406.40CDA
03.9406.14CDA
Mains Dimming
03.9406.40CNI
03.9406.14CNI
Casambi
03.9406.40CCB
03.9406.14CCB
Non Dimmable
05.1461.40C
05.1461.14C
Dali Version
05.1461.40CDA
05.1461.14CDA
Mains Dimming
05.1461.40CNI
05.1461.14CNI
Casambi
05.1461.40CCB
05.1461.14CCB
Non Dimmable
05.1462.40C
05.1462.14C
Dali Version
05.1462.40CDA
05.1462.14CDA
Mains Dimming
05.1462.40CNI
05.1462.14CNI
Casambi
05.1462.40CCB
05.1462.14CCB



Luminous flux luminaire
514 lm


@White (40)

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	2070	0.51
2	517	1.03
3	230	1.54
4	129	2.05
5	83	2.57

Optic Flood 3000K

E I Non Dimmable
03.9415.40C
03.9415.14C
Dali Version
03.9415.40CDA
03.9415.14CDA
Mains Dimming
03.9415.40CNI
03.9415.14CNI
Casambi
03.9415.40CCB
03.9415.14CCB
Non Dimmable
03.9416.40C
03.9416.14C
Dali Version
03.9416.40CDA
03.9416.14CDA
Mains Dimming
03.9416.40CNI
03.9416.14CNI
Casambi
03.9416.40CCB
03.9416.14CCB
Non Dimmable
05.1466.40C
05.1466.14C
Dali Version
05.1466.40CDA
05.1466.14CDA
Mains Dimming
05.1466.40CNI
05.1466.14CNI
Casambi
05.1466.40CCB
05.1466.14CCB
Non Dimmable
05.1467.40C
05.1467.14C
Dali Version
05.1467.40CDA
05.1467.14CDA
Mains Dimming
05.1467.40CNI
05.1467.14CNI
Casambi
05.1467.40CCB
05.1467.14CCB



Luminous flux luminaire
549 lm

@White (40)

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	2211	0.51
2	553	1.03
3	246	1.54
4	138	2.05
5	88	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.7350.40C
03.7350.14C

Dali Version

03.7350.40CDA
03.7350.14CDA

Mains Dimming

03.7350.40CNI
03.7350.14CNI

Casambi

03.7350.40CCB
03.7350.14CCB

Non Dimmable

03.7351.40C
03.7351.14C

Dali Version

03.7351.40CDA
03.7351.14CDA

Mains Dimming

03.7351.40CNI
03.7351.14CNI

Casambi

03.7351.40CCB
03.7351.14CCB

Non Dimmable

05.1471.40C
05.1471.14C

Dali Version

05.1471.40CDA
05.1471.14CDA

Mains Dimming

05.1471.40CNI
05.1471.14CNI

Casambi

05.1471.40CCB
05.1471.14CCB

Non Dimmable

05.1472.40C
05.1472.14C

Dali Version

05.1472.40CDA
05.1472.14CDA

Mains Dimming


05.1472.40CNI
05.1472.14CNI

Casambi

05.1472.40CCB
05.1472.14CCB



WIDE FLOOD



Luminous flux luminaire
511 lm

@White (40)

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	1021	0.83
2	255	1.66
3	113	2.49
4	64	3.32
5	41	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.7354.40C
03.7354.14C

Dali Version

03.7354.40CDA
03.7354.14CDA

Mains Dimming

03.7354.40CNI
03.7354.14CNI

Casambi

03.7354.40CCB
03.7354.14CCB

Non Dimmable

03.7355.40C
03.7355.14C

Dali Version

03.7355.40CDA
03.7355.14CDA

Mains Dimming

03.7355.40CNI
03.7355.14CNI

Casambi

03.7355.40CCB
03.7355.14CCB

Non Dimmable

05.1476.40C
05.1476.14C

Dali Version

05.1476.40CDA
05.1476.14CDA

Mains Dimming

05.1476.40CNI
05.1476.14CNI

Casambi

05.1476.40CCB
05.1476.14CCB

Non Dimmable

05.1477.40C
05.1477.14C

Dali Version

05.1477.40CDA
05.1477.14CDA

Mains Dimming


05.1477.40CNI
05.1477.14CNI

Casambi

05.1477.40CCB
05.1477.14CCB



WIDE FLOOD



Luminous flux luminaire
545 lm

@White (40)


Beam Angle: 45°

h(m)	E(lx)	D(m)
1	1089	0.83
2	272	1.66
3	121	2.49
4	68	3.32
5	44	4.14

Light Shadow Adjustable No Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish.


Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8924.40C
03.8924.14C
Dali Version
03.8924.40CDA
03.8924.14CDA
Mains Dimming
03.8924.40CNI
03.8924.14CNI
Casambi
03.8924.40CCB
03.8924.14CCB
Non Dimmable
03.8925.40C
03.8925.14C
Dali Version
03.8925.40CDA
03.8925.14CDA
Mains Dimming
03.8925.40CNI
03.8925.14CNI
Casambi
03.8925.40CCB
03.8925.14CCB
Non Dimmable
05.1541.40C
05.1541.14C
Dali Version
05.1541.40CDA
05.1541.14CDA
Mains Dimming
05.1541.40CNI
05.1541.14CNI
Casambi
05.1541.40CCB
05.1541.14CCB
Non Dimmable
05.1542.40C
05.1542.14C
Dali Version
05.1542.40CDA
05.1542.14CDA
Mains Dimming
05.1542.40CNI
05.1542.14CNI
Casambi
05.1542.40CCB
05.1542.14CCB

12°
SPOT



Luminous flux luminaire
1060 lm


Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	17109	0.20
2	4277	0.41
3	1901	0.61
4	1069	0.81
5	684	1.01

@White (40)

Optic Spot 3000K

E I Non Dimmable
03.8928.40C
03.8928.14C
Dali Version
03.8928.40CDA
03.8928.14CDA
Mains Dimming
03.8928.40CNI
03.8928.14CNI
Casambi
03.8928.40CCB
03.8928.14CCB
Non Dimmable
03.8929.40C
03.8929.14C
Dali Version
03.8929.40CDA
03.8929.14CDA
Mains Dimming
03.8929.40CNI
03.8929.14CNI
Casambi
03.8929.40CCB
03.8929.14CCB
Non Dimmable
05.1546.40C
05.1546.14C
Dali Version
05.1546.40CDA
05.1546.14CDA
Mains Dimming
05.1546.40CNI
05.1546.14CNI
Casambi
05.1546.40CCB
05.1546.14CCB
Non Dimmable
05.1547.40C
05.1547.14C
Dali Version
05.1547.40CDA
05.1547.14CDA
Mains Dimming
05.1547.40CNI
05.1547.14CNI
Casambi
05.1547.40CCB
05.1547.14CCB

12°
SPOT




Luminous flux luminaire
1131 lm

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	18255	0.20
2	4564	0.41
3	2028	0.61
4	1141	0.81
5	730	1.01

@White (40)

Optic Medium
2700K

E I Non Dimmable
03.9420.40C
03.9420.14C
Dali Version
03.9420.40CDA
03.9420.14CDA
Mains Dimming
03.9420.40CNI
03.9420.14CNI
Casambi
03.9420.40CCB
03.9420.14CCB
Non Dimmable
03.9421.40C
03.9421.14C
Dali Version
03.9421.40CDA
03.9421.14CDA
Mains Dimming
03.9421.40CNI
03.9421.14CNI
Casambi
03.9421.40CCB
03.9421.14CCB
Non Dimmable
05.1551.40C
05.1551.14C
Dali Version
05.1551.40CDA
05.1551.14CDA
Mains Dimming
05.1551.40CNI
05.1551.14CNI
Casambi
05.1551.40CCB
05.1551.14CCB
Non Dimmable
05.1552.40C
05.1552.14C
Dali Version
05.1552.40CDA
05.1552.14CDA
Mains Dimming
05.1552.40CNI
05.1552.14CNI
Casambi
05.1552.40CCB
05.1552.14CCB




Luminous flux luminaire
1020 lm

@White (40)

Beam Angle:	23°
h(m)	E(lx) D(m)
1	6846 0.40
2	1711 0.80
3	761 1.20
4	428 1.60
5	274 2.00

Optic Medium
3000K

E I Non Dimmable
03.9430.40C
03.9430.14C
Dali Version
03.9430.40CDA
03.9430.14CDA
Mains Dimming
03.9430.40CNI
03.9430.14CNI
Casambi
03.9430.40CCB
03.9430.14CCB
Non Dimmable
03.9431.40C
03.9431.14C
Dali Version
03.9431.40CDA
03.9431.14CDA
Mains Dimming
03.9431.40CNI
03.9431.14CNI
Casambi
03.9431.40CCB
03.9431.14CCB
Non Dimmable
05.1556.40C
05.1556.14C
Dali Version
05.1556.40CDA
05.1556.14CDA
Mains Dimming
05.1556.40CNI
05.1556.14CNI
Casambi
05.1556.40CCB
05.1556.14CCB
Non Dimmable
05.1557.40C
05.1557.14C
Dali Version
05.1557.40CDA
05.1557.14CDA
Mains Dimming
05.1557.40CNI
05.1557.14CNI
Casambi
05.1557.40CCB
05.1557.14CCB



Luminous flux luminaire
1088 lm


@White (40)

Beam Angle:	23°
h(m)	E(lx) D(m)
1	7302 0.40
2	1826 0.80
3	811 1.20
4	456 1.60
5	292 2.00

Light Shadow Adjustable No Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish.


Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9425.40C
03.9425.14C
Dali Version
03.9425.40CDA
03.9425.14CDA
Mains Dimming
03.9425.40CNI
03.9425.14CNI
Casambi
03.9425.40CCB
03.9425.14CCB
Non Dimmable
03.9426.40C
03.9426.14C
Dali Version
03.9426.40CDA
03.9426.14CDA
Mains Dimming
03.9426.40CNI
03.9426.14CNI
Casambi
03.9426.40CCB
03.9426.14CCB
Non Dimmable
05.1561.40C
05.1561.14C
Dali Version
05.1561.40CDA
05.1561.14CDA
Mains Dimming
05.1561.40CNI
05.1561.14CNI
Casambi
05.1561.40CCB
05.1561.14CCB
Non Dimmable
05.1562.40C
05.1562.14C
Dali Version
05.1562.40CDA
05.1562.14CDA
Mains Dimming
05.1562.40CNI
05.1562.14CNI
Casambi
05.1562.40CCB
05.1562.14CCB

29°
FLOOD



Luminous flux luminaire
1029 lm


@White (40)

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	4143	0.51
2	1036	1.03
3	460	1.54
4	259	2.05
5	166	2.57

Optic Flood 3000K

E I Non Dimmable
03.9435.40C
03.9435.14C
Dali Version
03.9435.40CDA
03.9435.14CDA
Mains Dimming
03.9435.40CNI
03.9435.14CNI
Casambi
03.9435.40CCB
03.9435.14CCB
Non Dimmable
03.9436.40C
03.9436.14C
Dali Version
03.9436.40CDA
03.9436.14CDA
Mains Dimming
03.9436.40CNI
03.9436.14CNI
Casambi
03.9436.40CCB
03.9436.14CCB
Non Dimmable
05.1566.40C
05.1566.14C
Dali Version
05.1566.40CDA
05.1566.14CDA
Mains Dimming
05.1566.40CNI
05.1566.14CNI
Casambi
05.1566.40CCB
05.1566.14CCB
Non Dimmable
05.1567.40C
05.1567.14C
Dali Version
05.1567.40CDA
05.1567.14CDA
Mains Dimming
05.1567.40CNI
05.1567.14CNI
Casambi
05.1567.40CCB
05.1567.14CCB

29°
FLOOD



Luminous flux luminaire
1098 lm

@White (40)

Beam Angle:	29°	
h(m)	E(lx)	D(m)
1	4421	0.51
2	1105	1.03
3	491	1.54
4	276	2.05
5	177	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.7358.40C
03.7358.14C

Dali Version

03.7358.40CDA
03.7358.14CDA

Mains Dimming

03.7358.40CNI
03.7358.14CNI

Casambi

03.7358.40CCB
03.7358.14CCB

Non Dimmable

03.7359.40C
03.7359.14C

Dali Version

03.7359.40CDA
03.7359.14CDA

Mains Dimming

03.7359.40CNI
03.7359.14CNI

Casambi

03.7359.40CCB
03.7359.14CCB

Non Dimmable

05.1571.40C
05.1571.14C

Dali Version

05.1571.40CDA
05.1571.14CDA

Mains Dimming

05.1571.40CNI
05.1571.14CNI

Casambi

05.1571.40CCB
05.1571.14CCB

Non Dimmable

05.1572.40C
05.1572.14C

Dali Version

05.1572.40CDA
05.1572.14CDA

Mains Dimming


05.1572.40CNI
05.1572.14CNI

Casambi

05.1572.40CCB
05.1572.14CCB



WIDE FLOOD



Luminous flux luminaire
1022 lm

@White (40)

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	2042	0.83
2	511	1.66
3	227	2.49
4	128	3.32
5	82	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.7362.40C
03.7362.14C

Dali Version

03.7362.40CDA
03.7362.14CDA

Mains Dimming

03.7362.40CNI
03.7362.14CNI

Casambi

03.7362.40CCB
03.7362.14CCB

Non Dimmable

03.7363.40C
03.7363.14C

Dali Version

03.7363.40CDA
03.7363.14CDA

Mains Dimming

03.7363.40CNI
03.7363.14CNI

Casambi

03.7363.40CCB
03.7363.14CCB

Non Dimmable

05.1576.40C
05.1576.14C

Dali Version

05.1576.40CDA
05.1576.14CDA

Mains Dimming

05.1576.40CNI
05.1576.14CNI

Casambi

05.1576.40CCB
05.1576.14CCB

Non Dimmable

05.1577.40C
05.1577.14C

Dali Version

05.1577.40CDA
05.1577.14CDA

Mains Dimming


05.1577.40CNI
05.1577.14CNI

Casambi

05.1577.40CCB
05.1577.14CCB



WIDE FLOOD



Luminous flux luminaire
1091 lm

@White (40)


Beam Angle: 45°


h(m)	E(lx)	D(m)
1	2180	0.83
2	545	1.66
3	242	2.49
4	136	3.32
5	87	4.14

Light Shadow Adjustable No Trim 8 Spots

Power LED DC 900 mA 21,6W - 2384 lm - 2700K/CRI 90 / 21,6W - 2544 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 18,6W - 1984 lm - 2700K/CRI 90 / 18,6W - 2120 lm - 3000K/CRI 90







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish


Luminaria empotrable de 8 focos LED. Fuente de alimentación remota incluida. (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8932.40C
03.8932.14C
Dali Version
03.8932.40CDA
03.8932.14CDA
Mains Dimming
03.8932.40CNI
03.8932.14CNI
Casambi
03.8932.40CCB
03.8932.14CCB
Non Dimmable
03.8933.40C
03.8933.14C
Dali Version
03.8933.40CDA
03.8933.14CDA
Mains Dimming
03.8933.40CNI
03.8933.14CNI
Casambi
03.8933.40CCB
03.8933.14CCB
Non Dimmable
05.1641.40C
05.1641.14C
Dali Version
05.1641.40CDA
05.1641.14CDA
Mains Dimming
05.1641.40CNI
05.1641.14CNI
Casambi
05.1641.40CCB
05.1641.14CCB
Non Dimmable
05.1642.40C
05.1642.14C
Dali Version
05.1642.40CDA
05.1642.14CDA
Mains Dimming
05.1642.40CNI
05.1642.14CNI
Casambi
05.1642.40CCB
05.1642.14CCB

12° SPOT




Luminous flux luminaire
2120 lm

@White (40) 900mA

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	34219	0.20
2	8555	0.41
3	3802	0.61
4	2139	0.81
5	1369	1.01

12° SPOT



Luminous flux luminaire
1800 lm

@White (40) 750mA


Beam Angle: 12°

h(m)	E(lx)	D(m)
1	29054	0.20
2	7263	0.41
3	3228	0.61
4	1816	0.81
5	1162	1.01

Optic Spot 3000K

E I Non Dimmable
03.8936.40C
03.8936.14C
Dali Version
03.8936.40CDA
03.8936.14CDA
Mains Dimming
03.8936.40CNI
03.8936.14CNI
Casambi
03.8936.40CCB
03.8936.14CCB
Non Dimmable
03.8937.40C
03.8937.14C
Dali Version
03.8937.40CDA
03.8937.14CDA
Mains Dimming
03.8937.40CNI
03.8937.14CNI
Casambi
03.8937.40CCB
03.8937.14CCB
Non Dimmable
05.1646.40C
05.1646.14C
Dali Version
05.1646.40CDA
05.1646.14CDA
Mains Dimming
05.1646.40CNI
05.1646.14CNI
Casambi
05.1646.40CCB
05.1646.14CCB
Non Dimmable
05.1647.40C
05.1647.14C
Dali Version
05.1647.40CDA
05.1647.14CDA
Mains Dimming
05.1647.40CNI
05.1647.14CNI
Casambi
05.1647.40CCB
05.1647.14CCB

12° SPOT




Luminous flux luminaire
2262 lm

@White (40) 900mA

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	36511	0.20
2	9128	0.41
3	4057	0.61
4	2282	0.81
5	1460	1.01

12° SPOT



Luminous flux luminaire
2020 lm

@White (40) 750mA

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	32605	0.20
2	8151	0.41
3	3623	0.61
4	2038	0.81
5	1304	1.01

Optic Medium 2700K

E I

Non Dimmable
03.9440.40C
03.9440.14C

Dali Version
03.9440.40CDA
03.9440.14CDA

Mains Dimming
03.9440.40CNI
03.9440.14CNI

Casambi
03.9440.40CCB
03.9440.14CCB

Non Dimmable
03.9441.40C
03.9441.14C

Dali Version
03.9441.40CDA
03.9441.14CDA

Mains Dimming
03.9441.40CNI
03.9441.14CNI

Casambi
03.9441.40CCB
03.9441.14CCB

Non Dimmable
05.1651.40C
05.1651.14C

Dali Version
05.1651.40CDA
05.1651.14CDA

Mains Dimming
05.1651.40CNI
05.1651.14CNI

Casambi
05.1651.40CCB
05.1651.14CCB


Non Dimmable
05.1652.40C
05.1652.14C

Dali Version
05.1652.40CDA
05.1652.14CDA

Mains Dimming
05.1652.40CNI
05.1652.14CNI

Casambi
05.1652.40CCB
05.1652.14CCB

23°
MEDIUM




Luminous flux luminaire
2040 lm

@White (40) 900mA

Beam Angle:	23°
h(m)	E(lx)	D(m)
1	13692	0.40
2	3423	0.80
3	1521	1.20
4	856	1.60
5	548	2.00

23°
MEDIUM



Luminous flux luminaire
1732 lm

@White (40) 750mA

Beam Angle:	23°
h(m)	E(lx)	D(m)
1	11625	0.40
2	2906	0.80
3	1292	1.20
4	727	1.60
5	465	2.00

Optic Medium 3000K

E I

Non Dimmable
03.9450.40C
03.9450.14C

Dali Version
03.9450.40CDA
03.9450.14CDA

Mains Dimming
03.9450.40CNI
03.9450.14CNI

Casambi
03.9450.40CCB
03.9450.14CCB

Non Dimmable
03.9451.40C
03.9451.14C

Dali Version
03.9451.40CDA
03.9451.14CDA

Mains Dimming
03.9451.40CNI
03.9451.14CNI

Casambi
03.9451.40CCB
03.9451.14CCB

Non Dimmable
05.1656.40C
05.1656.14C

Dali Version
05.1656.40CDA
05.1656.14CDA

Mains Dimming
05.1656.40CNI
05.1656.14CNI

Casambi
05.1656.40CCB
05.1656.14CCB


Non Dimmable
05.1657.40C
05.1657.14C

Dali Version
05.1657.40CDA
05.1657.14CDA

Mains Dimming
05.1657.40CNI
05.1657.14CNI

Casambi
05.1657.40CCB
05.1657.14CCB

23°
MEDIUM




Luminous flux luminaire
2177 lm

@White (40) 900mA

Beam Angle:	23°
h(m)	E(lx)	D(m)
1	14611	0.40
2	3653	0.80
3	1623	1.20
4	913	1.60
5	584	2.00

23°
MEDIUM



Luminous flux luminaire
1944 lm


@White (40) 750mA


Beam Angle:	23°
h(m)	E(lx)	D(m)
1	13047	0.40
2	3262	0.80
3	1450	1.20
4	815	1.60
5	522	2.00

Light Shadow Adjustable No Trim 8 Spots

Power LED DC 900 mA 21,6W - 2384 lm - 2700K/CRI 90 / 21,6W - 2544 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 18,6W - 1984 lm - 2700K/CRI 90 / 18,6W - 2120 lm - 3000K/CRI 90







Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately.

E= External Finish
I= Internal Finish


Luminaria empotrable de 8 focos LED. Fuente de alimentación remota incluida. (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K

E I Non Dimmable
03.9445.40C
03.9445.14C
Dali Version
03.9445.40CDA
03.9445.14CDA
Mains Dimming
03.9445.40CNI
03.9445.14CNI
Casambi
03.9445.40CCB
03.9445.14CCB
Non Dimmable
03.9446.40C
03.9446.14C
Dali Version
03.9446.40CDA
03.9446.14CDA
Mains Dimming
03.9446.40CNI
03.9446.14CNI
Casambi
03.9446.40CCB
03.9446.14CCB
Non Dimmable
05.1661.40C
05.1661.14C
Dali Version
05.1661.40CDA
05.1661.14CDA
Mains Dimming
05.1661.40CNI
05.1661.14CNI
Casambi
05.1661.40CCB
05.1661.14CCB
Non Dimmable
05.1662.40C
05.1662.14C
Dali Version
05.1662.40CDA
05.1662.14CDA
Mains Dimming
05.1662.40CNI
05.1662.14CNI
Casambi
05.1662.40CCB
05.1662.14CCB

29° FLOOD




Luminous flux luminaire
2057 lm
@White (40) 900mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	8282	0.51
2	2071	1.03
3	920	1.54
4	518	2.05
5	331	2.57

29° FLOOD



Luminous flux luminaire
1747 lm
@White (40) 750mA


Beam Angle: 29°

h(m)	E(lx)	D(m)
1	7034	0.51
2	1759	1.03
3	782	1.54
4	440	2.05
5	281	2.57

Optic Flood 3000K

E I Non Dimmable
03.9455.40C
03.9455.14C
Dali Version
03.9455.40CDA
03.9455.14CDA
Mains Dimming
03.9455.40CNI
03.9455.14CNI
Casambi
03.9455.40CCB
03.9455.14CCB
Non Dimmable
03.9456.40C
03.9456.14C
Dali Version
03.9456.40CDA
03.9456.14CDA
Mains Dimming
03.9456.40CNI
03.9456.14CNI
Casambi
03.9456.40CCB
03.9456.14CCB
Non Dimmable
05.1666.40C
05.1666.14C
Dali Version
05.1666.40CDA
05.1666.14CDA
Mains Dimming
05.1666.40CNI
05.1666.14CNI
Casambi
05.1666.40CCB
05.1666.14CCB
Non Dimmable
05.1667.40C
05.1667.14C
Dali Version
05.1667.40CDA
05.1667.14CDA
Mains Dimming
05.1667.40CNI
05.1667.14CNI
Casambi
05.1667.40CCB
05.1667.14CCB

29° FLOOD




Luminous flux luminaire
2195 lm
@White (40) 900mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	8838	0.51
2	2210	1.03
3	982	1.54
4	552	2.05
5	354	2.57

29° FLOOD



Luminous flux luminaire
1961 lm
@White (40) 750mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	7896	0.51
2	1974	1.03
3	877	1.54
4	493	2.05
5	316	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.7366.40C
03.7366.14C

Dali Version

03.7366.40CDA
03.7366.14CDA

Mains Dimming

03.7366.40CNI
03.7366.14CNI

Casambi

03.7366.40CCB
03.7366.14CCB

Non Dimmable

03.7367.40C
03.7367.14C

Dali Version

03.7367.40CDA
03.7367.14CDA

Mains Dimming

03.7367.40CNI
03.7367.14CNI

Casambi

03.7367.40CCB
03.7367.14CCB

Non Dimmable

05.1671.40C
05.1671.14C

Dali Version

05.1671.40CDA
05.1671.14CDA

Mains Dimming

05.1671.40CNI
05.1671.14CNI

Casambi

05.1671.40CCB
05.1671.14CCB

Non Dimmable

05.1672.40C
05.1672.14C

Dali Version

05.1672.40CDA
05.1672.14CDA


Mains Dimming

05.1672.40CNI
05.1672.14CNI

Casambi

05.1672.40CCB
05.1672.14CCB






Luminous flux luminaire
2044 lm

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	4085	0.83
2	1021	1.66
3	454	2.49
4	255	3.32
5	163	4.14

@White (40) 900mA





Luminous flux luminaire
1736 lm

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	3469	0.83
2	867	1.66
3	385	2.49
4	217	3.32
5	139	4.14

@White (40) 750mA

Optic Wide Flood 3000K

E I Non Dimmable

03.7370.40C
03.7370.14C

Dali Version

03.7370.40CDA
03.7370.14CDA

Mains Dimming

03.7370.40CNI
03.7370.14CNI

Casambi

03.7370.40CCB
03.7370.14CCB

Non Dimmable

03.7371.40C
03.7371.14C

Dali Version

03.7371.40CDA
03.7371.14CDA

Mains Dimming

03.7371.40CNI
03.7371.14CNI

Casambi

03.7371.40CCB
03.7371.14CCB

Non Dimmable

05.1676.40C
05.1676.14C

Dali Version

05.1676.40CDA
05.1676.14CDA

Mains Dimming

05.1676.40CNI
05.1676.14CNI

Casambi

05.1676.40CCB
05.1676.14CCB

Non Dimmable

05.1677.40C
05.1677.14C

Dali Version

05.1677.40CDA
05.1677.14CDA


Mains Dimming

05.1677.40CNI
05.1677.14CNI

Casambi

05.1677.40CCB
05.1677.14CCB






Luminous flux luminaire
2181 lm

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	4358	0.83
2	1090	1.66
3	484	2.49
4	272	3.32
5	174	4.14

@White (40) 900mA





Luminous flux luminaire
1948 lm


Beam Angle:		45°
h(m)	E(lx)	D(m)
1	3893	0.83
2	973	1.66
3	433	2.49
4	243	3.32
5	156	4.14


@White (40) 750mA

Light Shadow Adjustable No Trim 12 Spots

Power LED DC 900 mA 32,4W - 3576 lm - 2700K/CRI 90 / 32,4W - 3816 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 28W - 2976 lm - 2700K/CRI 90 / 28W - 3180 lm - 3000K/CRI 90







Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V). It requires a pre-installation frame, to be ordered separately.


E= External Finish
I= Internal Finish

Luminaria empotrable de 12 focos LED. Fuente de alimentación remota incluida (220-240V). Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.8940.40C
03.8940.14C
Dali & Push Version
03.8940.40CDA
03.8940.14CDA
Mains Dimming
03.8940.40CNI
03.8940.14CNI
Casambi
03.8940.40CCB
03.8940.14CCB
Non Dimmable
03.8941.40C
03.8941.14C
Dali & Push Version
03.8941.40CDA
03.8941.14CDA
Mains Dimming
03.8941.40CNI
03.8941.14CNI
Casambi
03.8941.40CCB
03.8941.14CCB
Non Dimmable
05.1741.40C
05.1741.14C
Dali & Push Version
05.1741.40CDA
05.1741.14CDA
Mains Dimming
05.1741.40CNI
05.1741.14CNI
Casambi
05.1741.40CCB
05.1741.14CCB
Non Dimmable
05.1742.40C
05.1742.14C
Dali & Push Version
05.1742.40CDA
05.1742.14CDA
Mains Dimming
05.1742.40CNI
05.1742.14CNI
Casambi
05.1742.40CCB
05.1742.14CCB




Beam Angle: 12°

h(m)	E(lx)	D(m)
1	51328	0.20
2	12832	0.41
3	5703	0.61
4	3208	0.81
5	2053	1.01

Luminous flux luminaire
3180 lm

@White (40) 900mA



Beam Angle: 12°


h(m)	E(lx)	D(m)
1	45985	0.20
2	11496	0.41
3	5109	0.61
4	2874	0.81
5	1839	1.01

Luminous flux luminaire
2849 lm

@White (40) 750mA

Optic Spot 3000K

E I Non Dimmable
03.8944.40C
03.8944.14C
Dali & Push Version
03.8944.40CDA
03.8944.14CDA
Mains Dimming
03.8944.40CNI
03.8944.14CNI
Casambi
03.8944.40CCB
03.8944.14CCB
Non Dimmable
03.8945.40C
03.8945.14C
Dali & Push Version
03.8945.40CDA
03.8945.14CDA
Mains Dimming
03.8945.40CNI
03.8945.14CNI
Casambi
03.8945.40CCB
03.8945.14CCB
Non Dimmable
05.1746.40C
05.1746.14C
Dali & Push Version
05.1746.40CDA
05.1746.14CDA
Mains Dimming
05.1746.40CNI
05.1746.14CNI
Casambi
05.1746.40CCB
05.1746.14CCB
Non Dimmable
05.1747.40C
05.1747.14C
Dali & Push Version
05.1747.40CDA
05.1747.14CDA
Mains Dimming
05.1747.40CNI
05.1747.14CNI
Casambi
05.1747.40CCB
05.1747.14CCB




Beam Angle: 12°

h(m)	E(lx)	D(m)
1	54782	0.20
2	13696	0.41
3	6087	0.61
4	3424	0.81
5	2191	1.01

Luminous flux luminaire
3394 lm

@White (40) 900mA



Beam Angle: 12°

h(m)	E(lx)	D(m)
1	48923	0.20
2	12231	0.41
3	5436	0.61
4	3058	0.81
5	1957	1.01

Luminous flux luminaire
3031 lm

@White (40) 750mA

Optic Medium 2700K

E I Non Dimmable

03.9460.40C
03.9460.14C

Dali & Push Version

03.9460.40CDA
03.9460.14CDA

Mains Dimming

03.9460.40CNI
03.9460.14CNI

Casambi

03.9460.40CCB
03.9460.14CCB

Non Dimmable

03.9461.40C
03.9461.14C

Dali & Push Version

03.9461.40CDA
03.9461.14CDA

Mains Dimming

03.9461.40CNI
03.9461.14CNI

Casambi

03.9461.40CCB
03.9461.14CCB

Non Dimmable

05.1751.40C
05.1751.14C

Dali & Push Version

05.1751.40CDA
05.1751.14CDA

Mains Dimming

05.1751.40CNI
05.1751.14CNI

Casambi

05.1751.40CCB
05.1751.14CCB

Non Dimmable

05.1752.40C
05.1752.14C

Dali & Push Version

05.1752.40CDA
05.1752.14CDA


Mains Dimming

05.1752.40CNI
05.1752.14CNI

Casambi

05.1752.40CCB
05.1752.14CCB






Luminous flux luminaire
3060 lm

@White (40) 900mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	20538	0.40
2	5134	0.80
3	2282	1.20
4	1284	1.60
5	822	2.00





Luminous flux luminaire
2742 lm

@White (40) 750mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	18403	0.40
2	4601	0.80
3	2045	1.20
4	1150	1.60
5	736	2.00

Optic Medium 3000K

E I Non Dimmable

03.9470.40C
03.9470.14C

Dali & Push Version

03.9470.40CDA
03.9470.14CDA

Mains Dimming

03.9470.40CNI
03.9470.14CNI

Casambi

03.9470.40CCB
03.9470.14CCB

Non Dimmable

03.9471.40C
03.9471.14C

Dali & Push Version

03.9471.40CDA
03.9471.14CDA

Mains Dimming

03.9471.40CNI
03.9471.14CNI

Casambi

03.9471.40CCB
03.9471.14CCB

Non Dimmable

05.1756.40C
05.1756.14C

Dali & Push Version

05.1756.40CDA
05.1756.14CDA

Mains Dimming

05.1756.40CNI
05.1756.14CNI

Casambi

05.1756.40CCB
05.1756.14CCB

Non Dimmable

05.1757.40C
05.1757.14C

Dali & Push Version

05.1757.40CDA
05.1757.14CDA


Mains Dimming

05.1757.40CNI
05.1757.14CNI

Casambi

05.1757.40CCB
05.1757.14CCB






Luminous flux luminaire
3265 lm

@White (40) 900mA

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	21913	0.40
2	5478	0.80
3	2435	1.20
4	1370	1.60
5	877	2.00





Luminous flux luminaire
2916 lm

@White (40) 750mA


Beam Angle: 23°


h(m)	E(lx)	D(m)
1	19571	0.40
2	4893	0.80
3	2175	1.20
4	1223	1.60
5	783	2.00

Light Shadow Adjustable No Trim 12 Spots

Power LED DC 900 mA 32,4W - 3576 lm - 2700K/CRI 90 / 32,4W - 3816 lm - 3000K/CRI 90
Mains dimming: Power LED DC 750 mA 28W - 2976 lm - 2700K/CRI 90 / 28W - 3180 lm - 3000K/CRI 90







Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V). It requires a pre-installation frame, to be ordered separately.


E= External Finish
I= Internal Finish

Luminaria empotrable de 12 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K


E I Non Dimmable
03.9465.40C
03.9465.14C
Dali & Push Version
03.9465.40CDA
03.9465.14CDA
Mains Dimming
03.9465.40CNI
03.9465.14CNI
Casambi
03.9465.40CCB
03.9465.14CCB
Non Dimmable
03.9466.40C
03.9466.14C
Dali & Push Version
03.9466.40CDA
03.9466.14CDA
Mains Dimming
03.9466.40CNI
03.9466.14CNI
Casambi
03.9466.40CCB
03.9466.14CCB
Non Dimmable
05.1761.40C
05.1761.14C
Dali & Push Version
05.1761.40CDA
05.1761.14CDA
Mains Dimming
05.1761.40CNI
05.1761.14CNI
Casambi
05.1761.40CCB
05.1761.14CCB
Non Dimmable
05.1762.40C
05.1762.14C
Dali & Push Version
05.1762.40CDA
05.1762.14CDA
Mains Dimming
05.1762.40CNI
05.1762.14CNI
Casambi
05.1762.40CCB
05.1762.14CCB



Luminous flux luminaire
3086 lm
@White (40) 900mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	12426	0.51
2	3106	1.03
3	1381	1.54
4	777	2.05
5	497	2.57




Luminous flux luminaire
2765 lm
@White (40) 750mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	11133	0.51
2	2783	1.03
3	1237	1.54
4	696	2.05
5	445	2.57

Optic Flood 3000K


E I Non Dimmable
03.9475.40C
03.9475.14C
Dali & Push Version
03.9475.40CDA
03.9475.14CDA
Mains Dimming
03.9475.40CNI
03.9475.14CNI
Casambi
03.9475.40CCB
03.9475.14CCB
Non Dimmable
03.9476.40C
03.9476.14C
Dali & Push Version
03.9476.40CDA
03.9476.14CDA
Mains Dimming
03.9476.40CNI
03.9476.14CNI
Casambi
03.9476.40CCB
03.9476.14CCB
Non Dimmable
05.1766.40C
05.1766.14C
Dali & Push Version
05.1766.40CDA
05.1766.14CDA
Mains Dimming
05.1766.40CNI
05.1766.14CNI
Casambi
05.1766.40CCB
05.1766.14CCB
Non Dimmable
05.1767.40C
05.1767.14C
Dali & Push Version
05.1767.40CDA
05.1767.14CDA
Mains Dimming
05.1767.40CNI
05.1767.14CNI
Casambi
05.1767.40CCB
05.1767.14CCB



Luminous flux luminaire
3293 lm
@White (40) 900mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	13259	0.51
2	3315	1.03
3	1473	1.54
4	829	2.05
5	530	2.57



Luminous flux luminaire
2941 lm
@White (40) 750mA

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	11842	0.51
2	2960	1.03
3	1316	1.54
4	740	2.05
5	474	2.57

Optic Wide Flood 2700K

E I Non Dimmable

03.7374.40C
03.7374.14C

Dali & Push Version

03.7374.40CDA
03.7374.14CDA

Mains Dimming

03.7374.40CNI
03.7374.14CNI

Casambi

03.7374.40CCB
03.7374.14CCB

Non Dimmable

03.7375.40C
03.7375.14C

Dali & Push Version

03.7375.40CDA
03.7375.14CDA

Mains Dimming

03.7375.40CNI
03.7375.14CNI

Casambi

03.7375.40CCB
03.7375.14CCB

Non Dimmable

05.1771.40C
05.1771.14C

Dali & Push Version

05.1771.40CDA
05.1771.14CDA

Mains Dimming

05.1771.40CNI
05.1771.14CNI

Casambi

05.1771.40CCB
05.1771.14CCB

Non Dimmable

05.1772.40C
05.1772.14C

Dali & Push Version

05.1772.40CDA
05.1772.14CDA


Mains Dimming

05.1772.40CNI
05.1772.14CNI

Casambi

05.1772.40CCB
05.1772.14CCB






Luminous flux luminaire
3066 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	6127	0.83
2	1532	1.66
3	681	2.49
4	383	3.32
5	245	4.14





Luminous flux luminaire
2747 lm

@White (40) 750mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	5490	0.83
2	1372	1.66
3	610	2.49
4	343	3.32
5	220	4.14

Optic Wide Flood 3000K

E I Non Dimmable

03.7378.40C
03.7378.14C

Dali & Push Version

03.7378.40CDA
03.7378.14CDA

Mains Dimming

03.7378.40CNI
03.7378.14CNI

Casambi

03.7378.40CCB
03.7378.14CCB

Non Dimmable

03.7379.40C
03.7379.14C

Dali & Push Version

03.7379.40CDA
03.7379.14CDA

Mains Dimming

03.7379.40CNI
03.7379.14CNI

Casambi

03.7379.40CCB
03.7379.14CCB

Non Dimmable

05.1776.40C
05.1776.14C

Dali & Push Version

05.1776.40CDA
05.1776.14CDA

Mains Dimming

05.1776.40CNI
05.1776.14CNI

Casambi

05.1776.40CCB
05.1776.14CCB

Non Dimmable

05.1777.40C
05.1777.14C

Dali & Push Version

05.1777.40CDA
05.1777.14CDA


Mains Dimming

05.1777.40CNI
05.1777.14CNI

Casambi

05.1777.40CCB
05.1777.14CCB






Luminous flux luminaire
3272 lm

@White (40) 900mA

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	6539	0.83
2	1635	1.66
3	727	2.49
4	409	3.32
5	262	4.14





Luminous flux luminaire
2922 lm


@White (40) 750mA


Beam Angle:		45°
h(m)	E(lx)	D(m)
1	5839	0.83
2	1460	1.66
3	649	2.49
4	365	3.32
5	234	4.14

Light Shadow Wall-Washer Trim 4 Spots

Power LED 1 DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).
Pre-installation frame not required.

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación no necesario.

2700K

- 03.9901.40C
- 03.9901.14C

Dali Version


- 03.9901.40CDA
- 03.9901.14CDA

Mains Dimming

- 03.9901.40CNI
- 03.9901.14CNI

Casambi

- 03.9901.40CCB
- 03.9901.14CCB



Luminous flux luminaire
873 lm

@Black (14)

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	1122	0.54
2	280	1.08
3	125	1.62
4	70	2.16
5	45	2.70

3000K

- 03.9900.40C
- 03.9900.14C

Dali Version


- 03.9900.40CDA
- 03.9900.14CDA

Mains Dimming

- 03.9900.40CNI
- 03.9900.14CNI

Casambi

- 03.9900.40CCB
- 03.9900.14CCB



Luminous flux luminaire
945 lm

@Black (14)


Beam Angle: 24°


h(m)	E(lx)	D(m)
1	1215	0.54
2	304	1.08
3	135	1.62
4	76	2.16
5	49	2.70

Light Shadow Wall-Washer No Trim 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).
It requires a pre-installation frame, to be ordered separately (08.0511.00).

Luminaria empotrable de 4 focos LED. Fuente de alimentación remota incluida (220-240V).
Marco de pre-instalación necesario, ha de pedirse por separado (08.0511.00).

2700K

- 03.9903.40C
- 03.9903.14C

Dali Version


- 03.9903.40CDA
- 03.9903.14CDA

Mains Dimming

- 03.9903.40CNI
- 03.9903.14CNI

Casambi

- 03.9903.40CCB
- 03.9903.14CCB



Luminous flux luminaire
873 lm

@Black (14)

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	1122	0.54
2	280	1.08
3	125	1.62
4	70	2.16
5	45	2.70

3000K

- 03.9902.40C
- 03.9902.14C

Dali Version


- 03.9902.40CDA
- 03.9902.14CDA

Mains Dimming

- 03.9902.40CNI
- 03.9902.14CNI

Casambi

- 03.9902.40CCB
- 03.9902.14CCB



Luminous flux luminaire
945 lm





@Black (14)

Beam Angle: 24°






h(m)	E(lx)	D(m)
1	1215	0.54
2	304	1.08
3	135	1.62
4	76	2.16
5	49	2.70

Accessories / Accesorios



Light Shadow Fixed & Wall-Washer No Trim

Pre-installation frame.	Marco de pre-instalación.			2L 08.0510.00
Pre-installation frame.	Marco de pre-instalación.			4L 08.0511.00
Pre-installation frame.	Marco de pre-instalación.			8L 08.0512.00
Pre-installation frame.	Marco de pre-instalación.			12L 08.0513.00
Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim pre-installation frames.	Accesorio para montaje de la línea continua No Trim. Cada accesorio permite conectar dos marcos No Trim para la instalación previa.			08.0052.90

Light Shadow Adjustable No Trim

Pre-installation frame.	Marco de pre-instalación.			2L 08.0515.00
Pre-installation frame.	Marco de pre-instalación.			4L 08.0516.00
Pre-installation frame.	Marco de pre-instalación.			8L 08.0517.00
Pre-installation frame.	Marco de pre-instalación.			12L 08.0518.00
Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim pre-installation linear frames.	Accesorio para montaje de la línea continua No Trim. Cada accesorio permite conectar dos marcos lineales No Trim para la instalación previa.			08.0059.90


Light Shadow Fixed No Trim Square


Pre-installation frame. Each accessory allows connection between two No Trim pre-installation square frames.	Marco de pre-instalación. Cada accesorio permite conectar dos marcos cuadrados No Trim para la instalación previa.			4L 08.0269.00
Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim pre-installation square frames.	Accesorio para montaje de la línea continua No Trim. Cada accesorio permite conectar dos marcos cuadrados No Trim para la instalación previa.			4L 08.0270.00

Light Shadow Surface 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

E= External Finish
I= Internal Finish
B= Box Finish

Luminaria de superficie de 4 focos LED. Fuente de alimentación 220-240V integrada.


E= Acabado Externo
I= Acabado Interno
B= Acabado Box

Optic Spot 2700K

B E I

Non Dimmable
03.8956.40C
03.8956.14C
03.8957.40C
03.8957.14C
05.2103.40C

Dali Version
03.8956.40CDA
03.8956.14CDA
03.8957.40CDA
03.8957.14CDA
05.2103.40CDA



Beam Angle: 12°

h(m)	E(lx)	D(m)
1	17109	0.20
2	4277	0.41
3	1901	0.61
4	1069	0.81
5	684	1.01

Luminous flux luminaire
1060 lm

@White (40)

Non Dimmable
03.8965.14C
03.8965.40C
03.8964.14C
03.8964.40C
05.2143.14C

Dali Version
03.8965.14CDA
03.8965.40CDA
03.8964.14CDA
03.8964.40CDA
05.2143.14CDA

Non Dimmable
05.2340.14C
05.2341.14C

Dali Version
05.2340.14CDA
05.2341.14CDA

Non Dimmable
05.2200.14C
05.2201.14C


Dali Version
05.2200.14CDA
05.2201.14CDA

Optic Spot 3000K

B E I

Non Dimmable
03.8960.40C
03.8960.14C
03.8961.40C
03.8961.14C
05.2108.40C

Dali Version
03.8960.40CDA
03.8960.14CDA
03.8961.40CDA
03.8961.14CDA
05.2108.40CDA



Beam Angle: 12°

h(m)	E(lx)	D(m)
1	18255	0.20
2	4564	0.41
3	2028	0.61
4	1141	0.81
5	730	1.01

Luminous flux luminaire
1131 lm

@White (40)

Non Dimmable
03.8969.14C
03.8969.40C
03.8968.14C
03.8968.40C
05.2148.14C

Dali Version
03.8969.14CDA
03.8969.40CDA
03.8968.14CDA
03.8968.40CDA
05.2148.14CDA

Non Dimmable
05.2345.14C
05.2346.14C

Dali Version
05.2345.14CDA
05.2346.14CDA


Non Dimmable
05.2205.14C
05.2206.14C

Dali Version
05.2205.14CDA
05.2206.14CDA

Optic Medium 2700K


B E I

Non Dimmable




03.9720.40C
03.9720.14C
03.9721.40C
03.9721.14C
05.2113.40C

Dali Version




03.9720.40CDA
03.9720.14CDA
03.9721.40CDA
03.9721.14CDA
05.2113.40CDA

Non Dimmable



03.9821.14C
03.9821.40C
03.9820.14C
03.9820.40C
05.2153.14C

Dali Version



03.9821.14CDA
03.9821.40CDA
03.9820.14CDA
03.9820.40CDA
05.2153.14CDA

Non Dimmable



05.2350.14C
05.2351.14C

Dali Version



05.2350.14CDA
05.2351.14CDA

Non Dimmable




05.2210.14C
05.2211.14C

Dali Version



05.2210.14CDA
05.2211.14CDA





Luminous flux luminaire
1020 lm


@White (40)

Beam Angle:	23°
h(m)	E(lx) D(m)
1	6846 0.40
2	1711 0.80
3	761 1.20
4	428 1.60
5	274 2.00

Optic Medium 3000K


B E I

Non Dimmable




03.9730.40C
03.9730.14C
03.9731.40C
03.9731.14C
05.2118.40C

Dali Version




03.9730.40CDA
03.9730.14CDA
03.9731.40CDA
03.9731.14CDA
05.2118.40CDA

Non Dimmable



03.9831.14C
03.9831.40C
03.9830.14C
03.9830.40C
05.2158.14C

Dali Version



03.9831.14CDA
03.9831.40CDA
03.9830.14CDA
03.9830.40CDA
05.2158.14CDA

Non Dimmable



05.2355.14C
05.2356.14C

Dali Version



05.2355.14CDA
05.2356.14CDA

Non Dimmable




05.2215.14C
05.2216.14C

Dali Version



05.2215.14CDA
05.2216.14CDA





Luminous flux luminaire
1088 lm


@White (40)


Beam Angle:	23°
h(m)	E(lx) D(m)
1	7302 0.40
2	1826 0.80
3	811 1.20
4	456 1.60
5	292 2.00

Light Shadow Surface 4 Spots

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90







Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

E= External Finish
I= Internal Finish
B= Box Finish

Luminaria de superficie de 4 focos LED. Fuente de alimentación 220-240V integrada.


E= Acabado Externo
I= Acabado Interno
B= Acabado Box

Optic Flood 2700K

B E I

Non Dimmable
03.9725.40C
03.9725.14C
03.9726.40C
03.9726.14C
05.2123.40C

Dali Version
03.9725.40CDA
03.9725.14CDA
03.9726.40CDA
03.9726.14CDA
05.2123.40CDA



Luminous flux luminaire
1029 lm

Beam Angle:	29°
h(m)	E(lx)	D(m)
1	4143	0.51
2	1036	1.03
3	460	1.54
4	259	2.05
5	166	2.57

@White (40)

Non Dimmable
03.9826.14C
03.9826.40C
03.9825.14C
03.9825.40C
05.2163.14C

Dali Version
03.9826.14CDA
03.9826.40CDA
03.9825.14CDA
03.9825.40CDA
05.2163.14CDA

Non Dimmable
05.2360.14C
05.2361.14C

Dali Version
05.2360.14CDA
05.2361.14CDA

Non Dimmable
05.2220.14C
05.2221.14C


Dali Version
05.2220.14CDA
05.2221.14CDA

Optic Flood 3000K

B E I

Non Dimmable
03.9735.40C
03.9735.14C
03.9736.40C
03.9736.14C
05.2128.40C

Dali Version
03.9735.40CDA
03.9735.14CDA
03.9736.40CDA
03.9736.14CDA
05.2128.40CDA



Luminous flux luminaire
1098 lm

Beam Angle:	29°
h(m)	E(lx)	D(m)
1	4421	0.51
2	1105	1.03
3	491	1.54
4	276	2.05
5	177	2.57

@White (40)

Non Dimmable
03.9836.14C
03.9836.40C
03.9835.14C
03.9835.40C
05.2168.14C

Dali Version
03.9836.14CDA
03.9836.40CDA
03.9835.14CDA
03.9835.40CDA
05.2168.14CDA

Non Dimmable
05.2365.14C
05.2366.14C

Dali Version
05.2365.14CDA
05.2366.14CDA


Non Dimmable
05.2225.14C
05.2226.14C

Dali Version
05.2225.14CDA
05.2226.14CDA

Optic Wide Flood
2700K


B E I

Non Dimmable




03.9760.40C
03.9760.14C
03.9761.40C
03.9761.14C
05.2133.40C

Dali Version




03.9760.40CDA
03.9760.14CDA
03.9761.40CDA
03.9761.14CDA
05.2133.40CDA



Non Dimmable
03.9861.14C
03.9861.40C
03.9860.14C
03.9860.40C
05.2173.14C

Dali Version



03.9861.14CDA
03.9861.40CDA
03.9860.14CDA
03.9860.40CDA
05.2173.14CDA



Non Dimmable
05.2370.14C
05.2371.14C

Dali Version



05.2370.14CDA
05.2371.14CDA



Non Dimmable
05.2230.14C
05.2231.14C


Dali Version



05.2230.14CDA
05.2231.14CDA



WIDE FLOOD



Luminous flux luminaire
1022 lm

@White (40)


Beam Angle: 45°

h(m)	E(lx)	D(m)
1	2042	0.83
2	511	1.66
3	227	2.49
4	128	3.32
5	82	4.14

Optic Wide Flood
3000K


B E I

Non Dimmable




03.9764.40C
03.9764.14C
03.9765.40C
03.9765.14C
05.2138.40C

Dali Version




03.9764.40CDA
03.9764.14CDA
03.9765.40CDA
03.9765.14CDA
05.2138.40CDA



Non Dimmable
03.9865.14C
03.9865.40C
03.9864.14C
03.9864.40C
05.2178.14C

Dali Version



03.9865.14CDA
03.9865.40CDA
03.9864.14CDA
03.9864.40CDA
05.2178.14CDA



Non Dimmable
05.2375.14C
05.2376.14C

Dali Version



05.2375.14CDA
05.2376.14CDA



Non Dimmable
05.2235.14C
05.2236.14C


Dali Version



05.2235.14CDA
05.2236.14CDA



WIDE FLOOD



Luminous flux luminaire
1091 lm

@White (40)


Beam Angle: 45°


h(m)	E(lx)	D(m)
1	2180	0.83
2	545	1.66
3	242	2.49
4	136	3.32
5	87	4.14

Light Shadow Surface 4 Spots Square

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90
Mains dimming: Power LED DC 700 mA 9W - 992 lm - 2700K/CRI 90 / 9W - 1060 lm - 3000K/CRI 90







Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

E= External Finish
I= Internal Finish
B= Box Finish

Luminaria de superficie de 4 focos LED. Fuente de alimentación 220-240V integrada.

E= Acabado Externo
I= Acabado Interno
B= Acabado Box

Optic Spot 2700K


B E I

Non Dimmable
05.0700.40C
05.0700.14C
05.0701.40C
05.0701.14C
05.0703.40C

Dali Version
05.0700.40CDA
05.0700.14CDA
05.0701.40CDA
05.0701.14CDA
05.0703.40CDA

Mains Dimming
05.0700.40CNI
05.0700.14CNI
05.0701.40CNI
05.0701.14CNI
05.0703.40CNI

10° SPOT




Luminous flux luminaire
865 lm (EXTREME CUT OFF)

Beam Angle:	10°	
h(m)	E(lx)	D(m)
1	15829	0.17
2	3957	0.35
3	1759	0.52
4	989	0.70
5	633	0.87

@White (40) 900mA

10° SPOT



Luminous flux luminaire
694 lm (EXTREME CUT OFF)

Beam Angle:	10°	
h(m)	E(lx)	D(m)
1	12690	0.17
2	3173	0.35
3	1410	0.52
4	793	0.70
5	508	0.87

@White (40) 700mA

Non Dimmable
05.0741.14C
05.0741.40C
05.0740.14C
05.0740.40C
05.0743.14C

Dali Version
05.0741.14CDA
05.0741.40CDA
05.0740.14CDA
05.0740.40CDA
05.0743.14CDA

Mains Dimming
05.0741.14CNI
05.0741.40CNI
05.0740.14CNI
05.0740.40CNI
05.0743.14CNI

Non Dimmable
05.0940.14C
05.0941.14C

Dali Version
05.0940.14CDA
05.0941.14CDA

Mains Dimming
05.0940.14CNI
05.0941.14CNI

Non Dimmable
05.0800.14C
05.0801.14C

Dali Version
05.0800.14CDA
05.0801.14CDA

Mains Dimming
05.0800.14CNI
05.0801.14CNI

Optic Spot 3000K


B E I

Non Dimmable
05.0705.40C
05.0705.14C
05.0706.40C
05.0706.14C
05.0708.40C

Dali Version
05.0705.40CDA
05.0705.14CDA
05.0706.40CDA
05.0706.14CDA
05.0708.40CDA

Mains Dimming
05.0705.40CNI
05.0705.14CNI
05.0706.40CNI
05.0706.14CNI
05.0708.40CNI

11° SPOT




Luminous flux luminaire
1077 lm

Beam Angle:	11°	
h(m)	E(lx)	D(m)
1	19539	0.20
2	4885	0.40
3	2171	0.60
4	1221	0.80
5	782	1.00

@White (40) 900mA

11° SPOT



Luminous flux luminaire
854 lm

Beam Angle:	11°	
h(m)	E(lx)	D(m)
1	15493	0.20
2	3873	0.40
3	1721	0.60
4	968	0.80
5	620	1.00

@White (40) 700mA

Non Dimmable
05.0746.14C
05.0746.40C
05.0745.14C
05.0745.40C
05.0748.14C

Dali Version
05.0746.14CDA
05.0746.40CDA
05.0745.14CDA
05.0745.40CDA
05.0748.14CDA

Mains Dimming
05.0746.14CNI
05.0746.40CNI
05.0745.14CNI
05.0745.40CNI
05.0748.14CNI

Non Dimmable
05.0945.14C
05.0946.14C

Dali Version
05.0945.14CDA
05.0946.14CDA

Mains Dimming
05.0945.14CNI
05.0946.14CNI

Non Dimmable
05.0805.14C
05.0806.14C

Dali Version
05.0805.14CDA
05.0806.14CDA

Mains Dimming
05.0805.14CNI
05.0806.14CNI

Optic Medium 2700K


B E I

Non Dimmable
05.0710.40C
05.0710.14C
05.0711.40C
05.0711.14C
05.0713.40C

Dali Version
05.0710.40CDA
05.0710.14CDA
05.0711.40CDA
05.0711.14CDA
05.0713.40CDA

Mains Dimming
05.0710.40CNI
05.0710.14CNI
05.0711.40CNI
05.0711.14CNI
05.0713.40CNI

22°
MEDIUM




Beam Angle:	22°
h(m)	E(lx) D(m)
1	5724 0.39
2	1431 0.78
3	636 1.17
4	358 1.56
5	229 1.95

Luminous flux luminaire
856 lm (EXTREME CUT OFF)

@White (40) 900mA

22°
MEDIUM



Beam Angle:	22°
h(m)	E(lx) D(m)
1	4589 0.39
2	1147 0.78
3	510 1.17
4	287 1.56
5	184 1.95

Luminous flux luminaire
686 lm (EXTREME CUT OFF)

@White (40) 700mA

Non Dimmable
05.0751.14C
05.0751.40C
05.0750.14C
05.0750.40C
05.0753.14C

Dali Version
05.0751.14CDA
05.0751.40CDA
05.0750.14CDA
05.0750.40CDA
05.0753.14CDA

Mains Dimming
05.0751.14CNI
05.0751.40CNI
05.0750.14CNI
05.0750.40CNI
05.0753.14CNI

Non Dimmable
05.0950.14C
05.0951.14C

Dali Version
05.0950.14CDA
05.0951.14CDA

Mains Dimming
05.0950.14CNI
05.0951.14CNI

Non Dimmable
05.0810.14C
05.0811.14C

Dali Version
05.0810.14CDA
05.0811.14CDA

Mains Dimming
05.0810.14CNI
05.0811.14CNI

Optic Medium 3000K


B E I

Non Dimmable
05.0715.40C
05.0715.14C
05.0716.40C
05.0716.14C
05.0718.40C

Dali Version
05.0715.40CDA
05.0715.14CDA
05.0716.40CDA
05.0716.14CDA
05.0718.40CDA

Mains Dimming
05.0715.40CNI
05.0715.14CNI
05.0716.40CNI
05.0716.14CNI
05.0718.40CNI

22°
MEDIUM




Beam Angle:	22°
h(m)	E(lx) D(m)
1	5844 0.39
2	1461 0.78
3	649 1.17
4	365 1.56
5	234 1.95

Luminous flux luminaire
874 lm (EXTREME CUT OFF)

@White (40) 900mA

22°
MEDIUM



Beam Angle:	22°
h(m)	E(lx) D(m)
1	4673 0.39
2	1168 0.78
3	519 1.17
4	292 1.56
5	187 1.95

Luminous flux luminaire
699 lm (EXTREME CUT OFF)

@White (40) 700mA

Non Dimmable
05.0756.14C
05.0756.40C
05.0755.14C
05.0755.40C
05.0758.14C

Dali Version
05.0756.14CDA
05.0756.40CDA
05.0755.14CDA
05.0755.40CDA
05.0758.14CDA

Mains Dimming
05.0756.14CNI
05.0756.40CNI
05.0755.14CNI
05.0755.40CNI
05.0758.14CNI

Non Dimmable
05.0955.14C
05.0956.14C

Dali Version
05.0955.14CDA
05.0956.14CDA

Mains Dimming
05.0955.14CNI
05.0956.14CNI

Non Dimmable
05.0815.14C
05.0816.14C


Dali Version
05.0815.14CDA
05.0816.14CDA


Mains Dimming
05.0815.14CNI
05.0816.14CNI

Light Shadow Surface 4 Spots Square

Power LED DC 900 mA 10,8W - 1192 lm - 2700K/CRI 90 / 10,8W - 1272lm - 3000K/CRI 90
Mains dimming: Power LED DC 700 mA 9W - 992 lm - 2700K/CRI 90 / 9W - 1060 lm - 3000K/CRI 90







Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

E= External Finish
I= Internal Finish
B= Box Finish

Luminaria de superficie de 4 focos LED. Fuente de alimentación 220-240V integrada.

E= Acabado Externo
I= Acabado Interno
B= Acabado Box


Optic Flood 2700K

B E I

Non Dimmable
05.0720.40C
05.0720.14C
05.0721.40C
05.0721.14C
05.0723.40C

Dali Version
05.0720.40CDA
05.0720.14CDA
05.0721.40CDA
05.0721.14CDA
05.0723.40CDA


Mains Dimming
05.0720.40CNI
05.0720.14CNI
05.0721.40CNI
05.0721.14CNI
05.0723.40CNI



Luminous flux luminaire
853 lm (EXTREME CUT OFF)

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2660	0.59
2	665	1.18
3	296	1.78
4	166	2.37
5	106	2.96

@White (40) 900mA



Luminous flux luminaire
684 lm (EXTREME CUT OFF)

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2133	0.59
2	533	1.18
3	237	1.78
4	133	2.37
5	85	2.96

@White (40) 700mA


Optic Flood 3000K

B E I

Non Dimmable
05.0725.40C
05.0725.14C
05.0726.40C
05.0726.14C
05.0728.40C

Dali Version
05.0725.40CDA
05.0725.14CDA
05.0726.40CDA
05.0726.14CDA
05.0728.40CDA


Mains Dimming
05.0725.40CNI
05.0725.14CNI
05.0726.40CNI
05.0726.14CNI
05.0728.40CNI



Luminous flux luminaire
871 lm (EXTREME CUT OFF)

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2716	0.59
2	679	1.18
3	302	1.78
4	170	2.37
5	109	2.96

@White (40) 900mA



Luminous flux luminaire
697 lm (EXTREME CUT OFF)

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2172	0.59
2	543	1.18
3	241	1.78
4	136	2.37
5	87	2.96

@White (40) 700mA

Non Dimmable
05.0761.14C
05.0761.40C
05.0760.14C
05.0760.40C
05.0763.14C

Dali Version
05.0761.14CDA
05.0761.40CDA
05.0760.14CDA
05.0760.40CDA
05.0763.14CDA

Mains Dimming
05.0761.14CNI
05.0761.40CNI
05.0760.14CNI
05.0760.40CNI
05.0763.14CNI

Non Dimmable
05.0766.14C
05.0766.40C
05.0765.14C
05.0765.40C
05.0768.14C

Dali Version
05.0766.14CDA
05.0766.40CDA
05.0765.14CDA
05.0765.40CDA
05.0768.14CDA

Mains Dimming
05.0766.14CNI
05.0766.40CNI
05.0765.14CNI
05.0765.40CNI
05.0768.14CNI

Non Dimmable
05.0960.14C
05.0961.14C

Dali Version
05.0960.14CDA
05.0961.14CDA

Mains Dimming
05.0960.14CNI
05.0961.14CNI

Non Dimmable
05.0965.14C
05.0966.14C

Dali Version
05.0965.14CDA
05.0966.14CDA

Mains Dimming
05.0965.14CNI
05.0966.14CNI

Non Dimmable
05.0820.14C
05.0821.14C

Dali Version
05.0820.14CDA
05.0821.14CDA

Mains Dimming
05.0820.14CNI
05.0821.14CNI

Non Dimmable
05.0825.14C
05.0826.14C

Dali Version
05.0825.14CDA
05.0826.14CDA

Mains Dimming
05.0825.14CNI
05.0826.14CNI

Optic Wide Flood 2700K


B E I

Non Dimmable
05.0730.40C
05.0730.14C
05.0731.40C
05.0731.14C
05.0733.40C

Dali Version
05.0730.40CDA
05.0730.14CDA
05.0731.40CDA
05.0731.14CDA
05.0733.40CDA

Mains Dimming
05.0730.40CNI
05.0730.14CNI
05.0731.40CNI
05.0731.14CNI
05.0733.40CNI

45° WIDE FLOOD




Luminous flux luminaire
842 lm (EXTREME CUT OFF)

@White (40) 900mA

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	1570	0.83
2	392	1.67
3	174	2.50
4	98	3.34
5	63	4.17

49° WIDE FLOOD



Luminous flux luminaire
787 lm

@White (40) 700mA

Beam Angle: 49°

h(m)	E(lx)	D(m)
1	1279	0.90
2	320	1.81
3	142	2.71
4	80	3.62
5	51	4.52

Non Dimmable
05.0771.14C
05.0771.40C
05.0770.14C
05.0770.40C
05.0773.14C

Dali Version
05.0771.14CDA
05.0771.40CDA
05.0770.14CDA
05.0770.40CDA
05.0773.14CDA

Mains Dimming
05.0771.14CNI
05.0771.40CNI
05.0770.14CNI
05.0770.40CNI
05.0773.14CNI

Non Dimmable
05.0970.14C
05.0971.14C

Dali Version
05.0970.14CDA
05.0971.14CDA

Mains Dimming
05.0970.14CNI
05.0971.14CNI

Non Dimmable
05.0830.14C
05.0831.14C

Dali Version
05.0830.14CDA
05.0831.14CDA

Mains Dimming
05.0830.14CNI
05.0831.14CNI

Optic Wide Flood 3000K


B E I

Non Dimmable
05.0735.40C
05.0735.14C
05.0736.40C
05.0736.14C
05.0738.40C

Dali Version
05.0735.40CDA
05.0735.14CDA
05.0736.40CDA
05.0736.14CDA
05.0738.40CDA

Mains Dimming
05.0735.40CNI
05.0735.14CNI
05.0736.40CNI
05.0736.14CNI
05.0738.40CNI

45° WIDE FLOOD




Luminous flux luminaire
860 lm (EXTREME CUT OFF)

@White (40) 900mA

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	1603	0.83
2	401	1.67
3	178	2.50
4	100	3.34
5	64	4.17

49° WIDE FLOOD



Luminous flux luminaire
836 lm

@White (40) 700mA

Beam Angle: 49°

h(m)	E(lx)	D(m)
1	1359	0.90
2	340	1.81
3	151	2.71
4	85	3.62
5	54	4.52

Non Dimmable
05.0776.14C
05.0776.40C
05.0775.14C
05.0775.40C
05.0778.14C

Dali Version
05.0776.14CDA
05.0776.40CDA
05.0775.14CDA
05.0775.40CDA
05.0778.14CDA

Mains Dimming
05.0776.14CNI
05.0776.40CNI
05.0775.14CNI
05.0775.40CNI
05.0778.14CNI

Non Dimmable
05.0975.14C
05.0976.14C

Dali Version
05.0975.14CDA
05.0976.14CDA

Mains Dimming
05.0975.14CNI
05.0976.14CNI


Non Dimmable
05.0835.14C
05.0836.14C

Dali Version
05.0835.14CDA
05.0836.14CDA

Mains Dimming
05.0835.14CNI
05.0836.14CNI

LIGHT SHADOW PRO&DOTS

DESIGNED BY FLOS ARCHITECTURAL



LIGHT SHADOW PRO&DOTS

Description
Light Shadow Pro&Dots is a family of luminaires for ceiling installation, with different sizes, also allowing recessed and surface installation. The lighting applications of Light Shadow Pro&Dots range from a downlight emission to directional (both adjustable and push) or asymmetric (wall-washer) light beams. The family has watertightness options from IP20 to IP54 (please consult models).
All Light Shadow Pro&Dots share a common design philosophy: the achievement of the highest possible visual comfort. To this end, the geometry of the products has been conceived so that the light source is markedly recessed with respect to the outer plane of the luminaire. The cut-off angle of Light Shadow Pro&Dots is therefore very high, making direct visual access to the light source difficult. As a result, the origin of the light source cannot be seen directly from virtually any natural position in the field of view of the users of the room.
In addition, the state-of-the-art optical system, patented by Flos, almost completely avoids the incidence of light on the product shade, which achieves the "high-comfort" effect (especially in luminaires with a black inner cone). This effect ensures that the product perfectly illuminates the space, while giving the impression that it remains switched off.

Optical System
Thanks to its range of optical lenses, Light Shadow Pro&Dots offers a series of beam angles, from very narrow angles (Super Spot) to extremely wide ones (Wide Flood). Please consult beam angle options for each model.
For Light Shadow Pro models, Flos has developed exclusive and patented double focal silicone lenses to achieve perfect control of light distribution. These lenses eliminate stray light and achieve an unparalleled L.O.R. (Light Output Ratio) luminous efficiency. In this way, they take full advantage of the LED's raw luminous flux. This is not the case with other technologies such as reflectors or standard production lenses.
Moreover, thanks to their silicon material, these state-of-the-art lenses manage the temperature produced by the LED in an excellent way and are highly resistant to thermal and over-time deterioration. They thus avoid the degradation and yellowing (with its consequent loss of performance) that occurs over time in other types of lenses.

Power Supply Units
Recessed versions require a power supply unit which is not included, to be ordered separately according to recommendations. Please consult the dimensions of the unit: when it does not fit through the recessing hole, an accessible remote location for the unit is required. Some models can be powered with a single unit and serial connection, please consult the corresponding information tables. The surface-mounted versions have integrated units.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Control Systems
Light Shadow Pro&Dots has control systems for dimming the luminaires under different protocols. Please consult the options available for each model and, in some cases, the appropriate power intensity options to match the luminous fluxes of products with different protocols.

Accessories and Installation
The recessed versions of Light Shadow Pro&Dots require individual installation accessories (pre-installation frames) available in Trim and No Trim versions (depending on the models, please consult). This recessed installation method is valid only for plasterboard ceilings.
For Light Shadow Dots Fixed models, pre-installation frames include No Trim options to install several units in line. These are fully compatible with the No Trim pre-installation frames for the Push models. Thus, "lines" of Light Shadow Dots and Push can be created with the same spacing and appearance.
As for the power supply, in the recessed Light Shadow Pro the power supply is connected directly to the luminaire. In the Light Shadow Dots and Push models, the connection is made through the pre-installation frame. This pre-installation frame is protected with the Hot Plug system that allows the product to be replaced with the power on. In pre-installation frames comprising several units, it also avoids luminaires installed in the same pre-installation frame to stop working if one of them does not work.

Standard Compliance and Quality Marks
The luminaire complies with the EN60598-1 European Technical Standards and any subsequent additions.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Descripción
Light Shadow Pro&Dots es una familia de luminarias, para instalación en techo -con diferentes tallas- y posibilidades de instalación en empotramiento y superficie. Las aplicaciones lumínicas de Light Shadow Pro&Dots abarcan desde emisión downlight, a haces de luz direccionables (tanto ajustables, como 'push') o asimétricos (wall-washer). La familia cuenta con opciones de estanqueidad desde IP20 a IP54 (consultar modelos).
Todo Light Shadow Pro&Dots comparte una filosofía común de diseño: la consecución del mayor confort visual posible. Para ello, la geometría de los productos se ha concebido para que la fuente de luz quede marcadamente retranqueada respecto al plano exterior de la luminaria. Así, el ángulo cut-off de Light Shadow Pro&Dots es muy elevado, dificultando con ello el acceso visual directo a la fuente de luz. Como consecuencia, el origen de la luz no puede ser visto directamente desde prácticamente ninguna posición natural del campo de vista de los usuarios del espacio.
Además, el vanguardista sistema óptico, patentado por Flos, evita casi al completo la incidencia de luz en la pantalla del producto, lo que consigue el efecto 'high-confort' (especialmente en las luminarias de cono interior negro). Este efecto logra que el producto ilumine perfectamente el espacio, al tiempo que otorga la impresión de que la luminaria permanece apagada.

Sistema óptico
Gracias a su oferta de lentes ópticas, Light Shadow Pro&Dots ofrece un abanico de aperturas de haz desde ángulos muy cerrados (Super Spot) a ángulos extremadamente abiertos (Wide Flood). Consultar opciones de apertura en cada modelo.
En el caso de los modelos Light Shadow Pro, para logar el control perfecto de la distribución lumínica se han desarrollado unas lentes de silicona de doble focal, exclusivas y patentadas por Flos. Estas lentes eliminan la luz espuria y consiguen una eficiencia lumínica L.O.R. (Light Output Ratio) sin parangón. De este modo, aprovechan al máximo el caudal de flujo lumínico bruto del LED. Esto no sucede así con otras tecnologías como reflectores o lentes de producción estándar.
Por otra parte, estas lentes de última tecnología gestionan de manera excelente -por su material de silicona- la temperatura producida por el LED y presentan una alta resistencia al deterioro térmico y temporal. Evitan así la degradación y el amarilleamiento (con su consiguiente pérdida de rendimiento) que se produce con el paso del tiempo en otro tipo de lentes.

Unidades de Alimentación
Las versiones empotradas precisan de un equipo no incluido, pedir por separado según las recomendaciones. Consultar las dimensiones del equipo: cuando no cabe por el agujero de empotramiento es necesaria una ubicación remota accesible para el mismo. Algunos modelos pueden ser alimentados con un solo equipo y conexión en serie, consulte las tablas de información correspondientes. Las versiones de superficie llevan el equipo integrado.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).

Sistemas de control
Light Shadow Pro&Dots dispone de sistemas de control para la regulación de las luminarias bajo diversos protocolos, consultar las opciones disponibles para cada modelo y, en algunos casos, las opciones de intensidad de alimentación adecuadas para hacer coincidir los flujos lumínicos de productos con protocolos diferentes.

Accesorios e instalación
Las versiones empotradas de Light Shadow Pro&Dots precisan de accesorios de instalación individual (premarcos) disponibles en versión Trim y No Trim (según los modelos, consultar). Este método de instalación empotrada es válido únicamente para techos de cartón-yeso (escayola).
Dentro de la oferta de estos premarcos, para los modelos Light Shadow Dots Fixed, existen opciones No Trim para instalar varias unidades en línea. Estos son completamente compatibles con los premarcos No Trim para los modelos Push. Así, se pueden crear 'líneas' de Light Shadow Dots y Push con la misma interdistancia y apariencia.
En cuanto a la alimentación, en los Light Shadow Pro de instalación empotrada, la alimentación se conecta directamente a la luminaria. En los modelos Light Shadow Dots y Push, la conexión se realiza a través del premarco de instalación. Este premarco está protegido con el sistema 'Hot Plug' que permite reemplazar el producto con la alimentación encendida. También permite que -en premarcos de varias unidades- el fallo de una de ellas no obligue al cese de funcionamiento del resto de luminarias instaladas en el mismo premarco.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

LIGHT SHADOW PRO&DOTS

DESIGNED BY FLOS ARCHITECTURAL

DOTS Ø30 FIXED



LIGHT SOURCE*
POWER LED
Up to 2,7W
298 lm
2700K/CRI 90
318 lm
3000K/CRI 90
342 lm
4000K/CRI 90

PRO Ø45 FIXED



LIGHT SOURCE
LED ARRAY
8,8W
816 lm
2700K/CRI 90
834 lm
3000K/CRI 90
926 lm
4000K/CRI 90

PRO Ø60 FIXED



LIGHT SOURCE*
LED ARRAY
Up to 15W
1402 lm
2700K/CRI 90
1427 lm
3000K/CRI 90
1577 lm
4000K/CRI 90

PRO Ø90 FIXED



LIGHT SOURCE*
LED ARRAY
Up to 22W
2191 lm
2700K/CRI 90
2339 lm
3000K/CRI 90
2457 lm
4000K/CRI 90

DOTS Ø30 PUSH



LIGHT SOURCE*
POWER LED
Up to 2,7W
298 lm
2700K/CRI 90
318 lm
3000K/CRI 90
342 lm
4000K/CRI 90

PRO Ø45 PUSH



LIGHT SOURCE
LED ARRAY
8,5W
756 lm
2700K/CRI 90
799 lm
3000K/CRI 90
866 lm
4000K/CRI 90

PRO Ø60 ADJUSTABLE



LIGHT SOURCE
LED ARRAY
10,5W
888 lm
2700K/CRI 90
923 lm
3000K/CRI 90
963 lm
4000K/CRI 90

PRO Ø90 ADJUSTABLE



LIGHT SOURCE*
LED ARRAY
Up to 18W
1637 lm
2700K/CRI 90
1772 lm
3000K/CRI 90
1877 lm
4000K/CRI 90

PRO Ø45 SURFACE



LIGHT SOURCE
LED ARRAY
8,8W
800 lm
2700K/CRI 90
845 lm
3000K/CRI 90
915 lm
4000K/CRI 90

PRO Ø60 SURFACE



LIGHT SOURCE
LED ARRAY
15W
1185 lm
2700K/CRI 90
1275 lm
3000K/CRI 90
1355 lm
4000K/CRI 90

PRO Ø90 WALL-WASHER



LIGHT SOURCE
LED ARRAY
18W
1593 lm
2700K/CRI 90
1752 lm
3000K/CRI 90
1867 lm
4000K/CRI 90

* Certain models of this product are available with different light values. See the product page.

* Disponible con valores lumínicos diferentes para algún modelo de este producto. Consulte la página de producto.

Rear Finish (R)
Light Shadow Pro&Dots Push

☐ 40 White
40 Blanco

■ 14 Black
14 Negro



External Finish (E)
Light Shadow Dots Push / Light Shadow Pro Push & Surface

☐ 40 White
40 Blanco

■ 14 Black
14 Negro

ER Brushed Steel
ER Acero Cepillado

ES Brushed Bronze
ES Bronce Cepillado



Internal Finish (I)

HIGH COMFORT

☐ 40 White
40 Blanco

■ 14 Black
14 Negro

ER Steel
ER Acero

ES Bronze
ES Bronce



FLOS
CONTROL BY CASAMBI


Available on the App Store


GET IT ON Google Play

Light Shadow Dots Ø30 Fixed - Single Spot Module

Power LED DC 900 mA - 2,7W - 298 lm - 2700K/CRI 90 / 2,7W - 318 lm - 3000K/CRI 90 / 2,7W - 342 lm - 4000K/CRI 90
Set of 1 spot mains dimming. Power LED DC 750 mA - 2,3W - 248 lm - 2700K/CRI 90 / 2,3W - 265 lm - 3000K/CRI 90 / 2,3W - 285 lm - 4000K/CRI 90







LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.

Módulo de iluminación LED, de bajo deslumbramiento, para ser insertado en los marcos de empotramiento (no incluidos), instalación mediante sistema de bayoneta con focos intercambiables. Disponible en versiones de una luz y grupos de dos y cuatro luces. Driver no incluido, el driver se debe conectar directamente a los marcos de empotramiento.

Recommended power supply / Equipos recomendados*:

Non Dimmable 100-240V 900mA	60.8911
Non Dimmable 220-240V 900mA	60.7677**
Mains Dimming 230-240V 750mA	60.8534
Mains Dimming 220-240V 900mA	60.9467**
Dimmable 0-10V 900mA	60.9414
Dim DALI 900mA	60.9602
Casambi 900mA	60.9207**
Casambi 900mA	70.0637


* Refer to the Drivers chapter / Ver capítulo Drivers

** Only Serial Connection / Solo conexión en serie

Optic Spot 2700K

Set of 1 spot

03.8600.40C
03.8600.14C
03.8600.ERC
03.8600.ESC




Luminous flux luminaire 265 lm

Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	4264	0.20
2	1066	0.40
3	474	0.60
4	266	0.80
5	171	1.01

Set of 2 spots

03.8640.40C
03.8640.14C
03.8640.ERC
03.8640.ESC




Luminous flux luminaire 530 lm

Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	8528	0.20
2	2132	0.40
3	948	0.60
4	533	0.80
5	341	1.01

Set of 4 spots

03.8610.40C
03.8610.14C
03.8610.ERC
03.8610.ESC



Luminous flux luminaire 1060 lm


Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	17055	0.20
2	4264	0.40
3	1895	0.60
4	1066	0.80
5	682	1.01

Internal Finish (I) · White

3000K

Set of 1 spot

03.8603.40C
03.8603.14C
03.8603.ERC
03.8603.ESC




Luminous flux luminaire 283 lm

Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	4553	0.20
2	1138	0.40
3	506	0.60
4	285	0.80
5	182	1.01

Set of 2 spots

03.8643.40C
03.8643.14C
03.8643.ERC
03.8643.ESC




Luminous flux luminaire 566 lm

Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	9107	0.20
2	2277	0.40
3	1012	0.60
4	569	0.80
5	364	1.01

Set of 4 spots

03.8613.40C
03.8613.14C
03.8613.ERC
03.8613.ESC



Luminous flux luminaire 1131 lm


Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	18198	0.20
2	4549	0.40
3	2022	0.60
4	1137	0.80
5	728	1.01

Internal Finish (I) · White

Optic Spot 4000K

Set of 1 spot

03.8606.40C
03.8606.14C
03.8606.ERC
03.8606.ESC




Luminous flux luminaire 304 lm

Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	4891	0.20
2	1223	0.40
3	543	0.60
4	306	0.80
5	196	1.01

Set of 2 spots

03.8671.40C
03.8671.14C
03.8671.ERC
03.8671.ESC




Luminous flux luminaire 608 lm

Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	9783	0.20
2	2446	0.40
3	1087	0.60
4	611	0.80
5	391	1.01

Set of 4 spots

03.8616.40C
03.8616.14C
03.8616.ERC
03.8616.ESC



Luminous flux luminaire 1217 lm


Beam Angle: 11°		
h(m)	E(lx)	D(m)
1	19581	0.20
2	4895	0.40
3	2176	0.60
4	1224	0.80
5	783	1.01

Internal Finish (I) · White

Optic Medium
2700K

Set of 1 spot

03.8601.40C
03.8601.14C
03.8601.ERC
03.8601.ESC




Luminous flux luminaire
261 lm

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	1748	0.39
2	437	0.79
3	194	1.18
4	109	1.57
5	70	1.97

Set of 2 spots

03.8641.40C
03.8641.14C
03.8641.ERC
03.8641.ESC




Luminous flux luminaire
522 lm

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	3497	0.39
2	874	0.79
3	389	1.18
4	219	1.57
5	140	1.97

Set of 4 spots

03.8611.40C
03.8611.14C
03.8611.ERC
03.8611.ESC



Luminous flux luminaire
1044 lm


Beam Angle:	22°
h(m)	E(lx)	D(m)
1	6993	0.39
2	1748	0.79
3	777	1.18
4	437	1.57
5	280	1.97

Internal Finish (I) · White

Optic Flood
2700K

Set of 1 spot

03.8602.40C
03.8602.14C
03.8602.ERC
03.8602.ESC




Luminous flux luminaire
257 lm

Beam Angle:	28°
h(m)	E(lx)	D(m)
1	1033	0.51
2	258	1.01
3	115	1.52
4	65	2.03
5	41	2.53

Set of 2 spots

03.8642.40C
03.8642.14C
03.8642.ERC
03.8642.ESC




Luminous flux luminaire
514 lm

Beam Angle:	28°
h(m)	E(lx)	D(m)
1	2067	0.51
2	517	1.01
3	230	1.52
4	129	2.03
5	83	2.53

Set of 4 spots

03.8612.40C
03.8612.14C
03.8612.ERC
03.8612.ESC



Luminous flux luminaire
1029 lm


Beam Angle:	28°
h(m)	E(lx)	D(m)
1	4137	0.51
2	1034	1.01
3	460	1.52
4	259	2.03
5	165	2.53

Internal Finish (I) · White

3000K

Set of 1 spot

03.8604.40C
03.8604.14C
03.8604.ERC
03.8604.ESC




Luminous flux luminaire
279 lm

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	1869	0.39
2	467	0.79
3	208	1.18
4	117	1.57
5	75	1.97

Set of 2 spots

03.8644.40C
03.8644.14C
03.8644.ERC
03.8644.ESC




Luminous flux luminaire
557 lm

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	3731	0.39
2	933	0.79
3	415	1.18
4	233	1.57
5	149	1.97

Set of 4 spots

03.8614.40C
03.8614.14C
03.8614.ERC
03.8614.ESC



Luminous flux luminaire
1114 lm


Beam Angle:	22°
h(m)	E(lx)	D(m)
1	7462	0.39
2	1866	0.79
3	829	1.18
4	466	1.57
5	298	1.97

Internal Finish (I) · White

3000K

Set of 1 spot

03.8605.40C
03.8605.14C
03.8605.ERC
03.8605.ESC




Luminous flux luminaire
275 lm

Beam Angle:	28°
h(m)	E(lx)	D(m)
1	1106	0.51
2	276	1.01
3	123	1.52
4	69	2.03
5	44	2.53

Set of 2 spots

03.8645.40C
03.8645.14C
03.8645.ERC
03.8645.ESC




Luminous flux luminaire
549 lm

Beam Angle:	28°
h(m)	E(lx)	D(m)
1	2207	0.51
2	552	1.01
3	245	1.52
4	138	2.03
5	88	2.53

Set of 4 spots

03.8615.40C
03.8615.14C
03.8615.ERC
03.8615.ESC



Luminous flux luminaire
1098 lm


Beam Angle:	28°
h(m)	E(lx)	D(m)
1	4414	0.51
2	1104	1.01
3	490	1.52
4	276	2.03
5	177	2.53

Internal Finish (I) · White

4000K

Set of 1 spot

03.8607.40C
03.8607.14C
03.8607.ERC
03.8607.ESC




Luminous flux luminaire
299 lm

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	2003	0.39
2	501	0.79
3	223	1.18
4	125	1.57
5	80	1.97

Set of 2 spots

03.8672.40C
03.8672.14C
03.8672.ERC
03.8672.ESC




Luminous flux luminaire
599 lm

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	4012	0.39
2	1003	0.79
3	446	1.18
4	251	1.57
5	160	1.97

Set of 4 spots

03.8617.40C
03.8617.14C
03.8617.ERC
03.8617.ESC



Luminous flux luminaire
1198 lm


Beam Angle:	22°
h(m)	E(lx)	D(m)
1	8025	0.39
2	2006	0.79
3	892	1.18
4	502	1.57
5	321	1.97

Internal Finish (I) · White

4000K

Set of 1 spot

03.8608.40C
03.8608.14C
03.8608.ERC
03.8608.ESC




Luminous flux luminaire
295 lm

Beam Angle:	28°
h(m)	E(lx)	D(m)
1	1186	0.51
2	297	1.01
3	132	1.52
4	74	2.03
5	47	2.53

Set of 2 spots

03.8673.40C
03.8673.14C
03.8673.ERC
03.8673.ESC




Luminous flux luminaire
590 lm

Beam Angle:	28°
h(m)	E(lx)	D(m)
1	2372	0.51
2	593	1.01
3	264	1.52
4	148	2.03
5	95	2.53

Set of 4 spots

03.8618.40C
03.8618.14C
03.8618.ERC
03.8618.ESC



Luminous flux luminaire
1181 lm


Beam Angle:	28°
h(m)	E(lx)	D(m)
1	4748	0.51
2	1187	1.01
3	528	1.52
4	297	2.03
5	190	2.53


Internal Finish (I) · White

Light Shadow Dots Ø30 Fixed - Single Spot Module

Power LED DC 900 mA - 2,7W - 298 lm - 2700K/CRI 90 / 2,7W - 318 lm - 3000K/CRI 90 / 2,7W - 342 lm - 4000K/CRI 90
Set of 1 spot mains dimming. Power LED DC 750 mA - 2,3W - 248 lm - 2700K/CRI 90 / 2,3W - 265 lm - 3000K/CRI 90 / 2,3W - 285 lm - 4000K/CRI 90







LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.

Módulo de iluminación LED, de bajo deslumbramiento, para ser insertado en los marcos de empotramiento (no incluidos), instalación mediante sistema de bayoneta con focos intercambiables. Disponible en versiones de una luz y grupos de dos y cuatro luces. Driver no incluido, el driver se debe conectar directamente a los marcos de empotramiento.

Recommended power supply / Equipos recomendados*:

Non Dimmable 100-240V 900mA	60.8911
Non Dimmable 220-240V 900mA	60.7677**
Mains Dimming 230-240V 750mA	60.8534
Mains Dimming 220-240V 900mA	60.9467**
Dimmable 0-10V 900mA	60.9414
Dim DALI 900mA	60.9602
Casambi 900mA	60.9207**
Casambi 900mA	70.0637

* Refer to the Drivers chapter / Ver capítulo Drivers


** Only Serial Connection / Solo conexión en serie

Optic Wide Flood 2700K

Set of 1 spot

03.8630.40C
03.8630.14C
03.8630.ERC
03.8630.ESC






Luminous flux luminaire 256 lm

Beam Angle:	45°
h(m)	E(lx) D(m)
1	511 0.82
2	128 1.64
3	57 2.46
4	32 3.27
5	20 4.09

Set of 2 spots

03.8646.40C
03.8646.14C
03.8646.ERC
03.8646.ESC






Luminous flux luminaire 511 lm

Beam Angle:	45°
h(m)	E(lx) D(m)
1	1020 0.82
2	255 1.64
3	113 2.46
4	64 3.27
5	41 4.09

Set of 4 spots

03.8635.40C
03.8635.14C
03.8635.ERC
03.8635.ESC





Luminous flux luminaire 1022 lm

Beam Angle:	45°
h(m)	E(lx) D(m)
1	2040 0.82
2	510 1.64
3	227 2.46
4	128 3.27
5	82 4.09


Internal Finish (I) · White

3000K

Set of 1 spot

03.8631.40C
03.8631.14C
03.8631.ERC
03.8631.ESC






Luminous flux luminaire 273 lm

Beam Angle:	45°
h(m)	E(lx) D(m)
1	545 0.82
2	136 1.64
3	61 2.46
4	34 3.27
5	22 4.09

Set of 2 spots

03.8647.40C
03.8647.14C
03.8647.ERC
03.8647.ESC






Luminous flux luminaire 545 lm

Beam Angle:	45°
h(m)	E(lx) D(m)
1	1088 0.82
2	272 1.64
3	121 2.46
4	68 3.27
5	44 4.09

Set of 4 spots

03.8636.40C
03.8636.14C
03.8636.ERC
03.8636.ESC





Luminous flux luminaire 1091 lm

Beam Angle:	45°
h(m)	E(lx) D(m)
1	2178 0.82
2	544 1.64
3	242 2.46
4	136 3.27
5	87 4.09


Internal Finish (I) · White

Optic Wide Flood 4000K

Set of 1 spot

03.8633.40C
03.8633.14C
03.8633.ERC
03.8633.ESC






Luminous flux luminaire 293 lm

Beam Angle:	45°
h(m)	E(lx) D(m)
1	585 0.82
2	146 1.64
3	65 2.46
4	37 3.27
5	23 4.09

Set of 2 spots

03.8674.40C
03.8674.14C
03.8674.ERC
03.8674.ESC






Luminous flux luminaire 587 lm

Beam Angle:	45°
h(m)	E(lx) D(m)
1	1172 0.82
2	293 1.64
3	130 2.46
4	73 3.27
5	47 4.09

Set of 4 spots

03.8637.40C
03.8637.14C
03.8637.ERC
03.8637.ESC





Luminous flux luminaire 1173 lm


Beam Angle:	45°
h(m)	E(lx) D(m)
1	2341 0.82
2	585 1.64
3	260 2.46
4	146 3.27
5	94 4.09


Internal Finish (I) · White

Light Shadow Dots Ø30 Push

Power LED DC 900 mA - 2,7W - 298 lm - 2700K/CRI 90 / 2,7W - 318 lm - 3000K/CRI 90 / 2,7W - 342 lm - 4000K/CRI 90
Mains Dimming: Power LED DC 750 mA - 2,3W - 248 lm - 2700K/CRI 90 / 2,3W - 265 lm - 3000K/CRI 90 / 2,3W - 285 lm - 4000K/CRI 90







Luminaire with 2x1 functionality: it can work as downlight (recessed, flush with ceiling) or as a projector (fully adjustable). The passage from one position to the other can be made by moving the product easily by hand.


Luminaria con funcionalidad 2x1: puede actuar como downlight (empotrada, a ras del techo) o proyector (completamente orientable). El paso de una posición a otra se puede acometer moviendo el producto fácilmente con la mano.

R= Rear finish
E= External finish
I= Internal finish

R= Acabado trasero
E= Acabado exterior
I= Acabado interior

Optic Spot 2700K

R	E	I	
			05.9300.40A
		■	05.9301.40A
		◪	05.9303.40A
■			05.9305.40A
■		■	05.9304.40A
■		◪	05.9307.40A
■	■		05.9305.14A
■	■	■	05.9304.14A
■	■	◪	05.9307.14A
■	◪		05.9304.ERA
■	◪	◪	05.9307.ERA
■	▒		05.9304.ESA
■	▒	▒	05.9308.ESA



Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4264	0.20
2	1066	0.40
3	474	0.60
4	266	0.80
5	171	1.01

Luminous flux luminaire
265 lm
Internal Finish (I) · White

Recommended power supply / Equipos recomendados*:


Non Dimmable 100-240V 900mA	60.8911
Non Dimmable 220-240V 900mA	60.7677**
Mains Dimming 230-240V 750mA	60.8534
Mains Dimming 220-240V 900mA	60.9467**
Dimmable 0-10V 900mA	60.9414
Dim DALI 900mA	60.9602
Casambi 900mA	60.9207**
Casambi 900mA	06.1974.00

* Refer to the Drivers chapter / Ver capítulo Drivers

** Only Serial Connection / Solo conexión en serie

Optic Spot 3000K

R	E	I	
			05.9350.40A
		■	05.9351.40A
		◪	05.9353.40A
■			05.9355.40A
■		■	05.9354.40A
■		◪	05.9357.40A
■	■		05.9355.14A
■	■	■	05.9354.14A
■	■	◪	05.9357.14A
■	◪		05.9354.ERA
■	◪	◪	05.9357.ERA
■	▒		05.9354.ESA
■	▒	▒	05.9358.ESA




Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4553	0.20
2	1138	0.40
3	506	0.60
4	285	0.80
5	182	1.01

Luminous flux luminaire
283 lm
Internal Finish (I) · White

Optic Spot 4000K

R	E	I	
			05.9400.40A
		■	05.9401.40A
		◪	05.9403.40A
■			05.9405.40A
■		■	05.9404.40A
■		◪	05.9407.40A
■	■		05.9405.14A
■	■	■	05.9404.14A
■	■	◪	05.9407.14A
■	◪		05.9404.ERA
■	◪	◪	05.9407.ERA
■	▒		05.9404.ESA
■	▒	▒	05.9408.ESA



Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4891	0.20
2	1223	0.40
3	543	0.60
4	306	0.80
5	196	1.01

Luminous flux luminaire
304 lm
Internal Finish (I) · White

Optic Medium
2700K

R E I

05.9310.40A
05.9311.40A
05.9313.40A


05.9315.40A
05.9314.40A
05.9317.40A

05.9315.14A
05.9314.14A
05.9317.14A

05.9314.ERA
05.9317.ERA

05.9314.ESA
05.9318.ESA

22°
MEDIUM



Luminous flux luminaire
261 lm
Internal Finish (I) · White

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	1748	0.39
2	437	0.79
3	194	1.18
4	109	1.57
5	70	1.97

Optic Medium
3000K

R E I

05.9360.40A
05.9361.40A
05.9363.40A


05.9365.40A
05.9364.40A
05.9367.40A

05.9365.14A
05.9364.14A
05.9367.14A

05.9364.ERA
05.9367.ERA

05.9364.ESA
05.9368.ESA

22°
MEDIUM



Luminous flux luminaire
278 lm
Internal Finish (I) · White

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	1862	0.39
2	466	0.79
3	207	1.18
4	116	1.57
5	74	1.97

Optic Medium
4000K

R E I

05.9410.40A
05.9411.40A
05.9413.40A


05.9415.40A
05.9414.40A
05.9417.40A

05.9415.14A
05.9414.14A
05.9417.14A

05.9414.ERA
05.9417.ERA

05.9414.ESA
05.9418.ESA

22°
MEDIUM



Luminous flux luminaire
299 lm
Internal Finish (I) · White

Beam Angle:	22°
h(m)	E(lx)	D(m)
1	2003	0.39
2	501	0.79
3	223	1.18
4	125	1.57
5	80	1.97

Accessories / Accesorios

Light Shadow Dots Ø30 Push


Honeycomb	Panel de abeja		08.0790.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 4000K >> 5100±75K 08.0791.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 4000K >> 3400±75K 08.0792.00


Only available in black. For other colours, please ask. / Solo disponible en color negro. Otros colores, consultar.

Light Shadow Dots Ø30 Push

Power LED DC 900 mA - 2,7W - 298 lm - 2700K/CRI 90 / 2,7W - 318 lm - 3000K/CRI 90 / 2,7W - 342 lm - 4000K/CRI 90
Mains Dimming: Power LED DC 750 mA - 2,3W - 248 lm - 2700K/CRI 90 / 2,3W - 265 lm - 3000K/CRI 90 / 2,3W - 285 lm - 4000K/CRI 90







Luminaire with 2x1 functionality: it can work as downlight (recessed, flush with ceiling) or as a projector (fully adjustable). The passage from one position to the other can be made by moving the product easily by hand.

Luminaria con funcionalidad 2x1: puede actuar como downlight (empotrada, a ras del techo) o proyector (completamente orientable). El paso de una posición a otra se puede acometer moviendo el producto fácilmente con la mano.

R= Rear finish
E= External finish
I= Internal finish

R= Acabado trasero
E= Acabado exterior
I= Acabado interior

Optic Flood 2700K

R E I



05.9320.40A
05.9321.40A
05.9323.40A


05.9325.40A
05.9324.40A
05.9327.40A


05.9325.14A
05.9324.14A
05.9327.14A


05.9324.ERA
05.9327.ERA


05.9324.ESA
05.9328.ESA



Luminous flux luminaire
257 lm
Internal Finish (I) · White

Beam Angle:		28°
h(m)	E(lx)	D(m)
1	1033	0.51
2	258	1.01
3	115	1.52
4	65	2.03
5	41	2.53

Recommended power supply / Equipos recomendados*:

Non Dimmable 100-240V 900mA	60.8911
Non Dimmable 220-240V 900mA	60.7677**
Mains Dimming 230-240V 750mA	60.8534
Mains Dimming 220-240V 900mA	60.9467**
Dimmable 0-10V 900mA	60.9414
Dim DALI 900mA	60.9602
Casambi 900mA	60.9207**
Casambi 900mA	06.1974.00

* Refer to the Drivers chapter / Ver capítulo Drivers
** Only Serial Connection / Solo conexión en serie

Optic Flood 3000K

R E I



05.9370.40A
05.9371.40A
05.9373.40A


05.9375.40A
05.9374.40A
05.9377.40A


05.9375.14A
05.9374.14A
05.9377.14A


05.9374.ERA
05.9377.ERA


05.9374.ESA
05.9378.ESA



Luminous flux luminaire
274 lm
Internal Finish (I) · White

Beam Angle:		28°
h(m)	E(lx)	D(m)
1	1102	0.51
2	275	1.01
3	122	1.52
4	69	2.03
5	44	2.53

Optic Flood 4000K

R E I



05.9420.40A
05.9421.40A
05.9423.40A


05.9425.40A
05.9424.40A
05.9427.40A


05.9425.14A
05.9424.14A
05.9427.14A


05.9424.ERA
05.9427.ERA


05.9424.ESA
05.9428.ESA



Luminous flux luminaire
295 lm
Internal Finish (I) · White

Beam Angle:		28°
h(m)	E(lx)	D(m)
1	1186	0.51
2	297	1.01
3	132	1.52
4	74	2.03
5	47	2.53

Optic Wide Flood
2700K

R E I



05.9330.40A
05.9331.40A
05.9333.40A



05.9335.40A
05.9334.40A
05.9337.40A



05.9335.14A
05.9334.14A
05.9337.14A




05.9334.ERA
05.9337.ERA



05.9334.ESA
05.9338.ESA



WIDE FLOOD



Luminous flux luminaire
256 lm
Internal Finish (I) · White

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	511	0.82
2	128	1.64
3	57	2.46
4	32	3.27
5	20	4.09

Optic Wide Flood
3000K

R E I



05.9380.40A
05.9381.40A
05.9383.40A



05.9385.40A
05.9384.40A
05.9387.40A



05.9385.14A
05.9384.14A
05.9387.14A




05.9384.ERA
05.9387.ERA



05.9384.ESA
05.9388.ESA



WIDE FLOOD



Luminous flux luminaire
273 lm
Internal Finish (I) · White

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	545	0.82
2	136	1.64
3	61	2.46
4	34	3.27
5	22	4.09

Optic Wide Flood
4000K

R E I



05.9430.40A
05.9431.40A
05.9433.40A



05.9435.40A
05.9434.40A
05.9437.40A



05.9435.14A
05.9434.14A
05.9437.14A




05.9434.ERA
05.9437.ERA



05.9434.ESA
05.9438.ESA



WIDE FLOOD



Luminous flux luminaire
293 lm
Internal Finish (I) · White

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	585	0.82
2	146	1.64
3	65	2.46
4	37	3.27
5	23	4.09

Accessories / Accesorios


Light Shadow Dots Ø30 Push

Honeycomb	Panel de abeja		08.0790.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 4000K >> 5100±75K 08.0791.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 4000K >> 3400±75K 08.0792.00


Only available in black. For other colours, please ask. / Solo disponible en color negro. Otros colores, consultar.

HOW TO ORDER LIGHT SHADOW DOTS

Dots Fixed




Dots Fixed Trim



single frame
(ref. 08.0661.40)
(ref. 08.0661.14)


+ 1 spot set = Light Shadow Dots Fixed 1 Spot

Dots Fixed No Trim




single frame
(ref. 08.0580.00)

+ 1 spot set = Light Shadow Dots Fixed 1 Spot




2 spots frame (int 43)
(ref. 08.0581.00)

+ 2 spots set = Light Shadow Dots Fixed 2 Spots (int 43)




2 spots frame (int 70)
(ref. 08.0583.00)

+ 2 spots set = Light Shadow Dots Fixed 2 Spots (int 70)



4 spots frame (int 43)
(ref. 08.0582.00)


+ 4 spots set = Light Shadow Dots Fixed 4 Spots (int 43)




4 spots frame (int 70)
(ref. 08.0584.00)

+ 4 spots set = Light Shadow Dots Fixed 4 Spots (int 70)

Dots Push



Dots Push No Trim



single frame
(ref. 08.0756.00)


+ 1 spot set = Light Shadow Dots Push 1 Spot

HOW TO ORDER LIGHT SHADOW DOTS

Dots Push - Functionality and Positioning

Light Shadow Push can be placed in top position, functioning as a downlight (perfectly flush to ceiling), or in bottom position, functioning as an adjustable spotlight.

Light Shadow Push puede colocarse en posición superior -funcionando como un downlight (perfectamente enrasado a techo)-, o en posición inferior -funcionado como un proyector orientable-.



Dots Fixed & Push No Trim Frames - Continuity and Interdistance

When planning the lighting of an environment, the Light Shadow Dots family allows to project continuous light lines or random figures thanks to the simple interconnection between its luminaires (1, 2 and 4 lights) without the need for an additional tool. For the lighting designning and planning, the user can choose between two predefined distances of 43 and 70 mm between light points. For the 70 mm version, it is necessary to assemble an independent accessory (reference: 08.0586.00) between the luminaires.


A la hora de planificar la iluminación de un entorno, la familia Light Shadow Dots permite proyectar líneas continuas de luz o figuras aleatorias gracias a la sencilla interconexión entre sus luminarias (1, 2 y 4 luces) sin necesidad de utilizar herramienta adicional. En su diseño y planificación, el usuario podrá elegir entre dos distancias predefinidas entre puntos de luz, 43 y 70 mm, siendo necesario el montaje de un accesorio independiente (ref. 08.0586.00) entre luminarias para la versión 70 mm.




optional divider (int 70)
(ref. 08.0586.00)

Dots Frame (int 43)

Dots Frame (int 70)



Dots Push Frame




Interconnection information to build a continuous line / Detalle de interconexión para construir una línea continua


Dots Fixed & Push No Trim Frames - Compatibility

Light Shadow Dots Fixed and Push No Trim pre-installation frames are compatible and can be installed continuously, maintaining the spacing. In this way, when the Push models are in recessed position, they are indistinguishable from the Fixed versions.

Los premarcos No Trim de Light Shadow Dots Fixed y Push son compatibles y se pueden instalar de manera continua, manteniendo la interdistancia. De este modo, cuando los modelos Push están en posición empotrada, son indistinguibles de las versiones Fixed.




A: Dots Fixed no trim frames 1/2/4 (int 43/70)
+
B: Dots Push no trim frame 1




Accessories / Accesorios

Dots Fixed Trim




Pre-installation frame.
Marco de pre-instalación.





1L
08.0661.40
08.0661.14
08.0661.ER
08.0661.ES



40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado




ES Brushed Bronze
ES Bronce Cepillado




Drivers for Serial Connection / Equipos para Conexión en Serie

Driver	DIM Protocol	Driving current	Min-Max Spot(s) per Driver
60.8911	Non Dimmable	900	1 - 6
60.7677	Non Dimmable	900	2 - 11
60.8534	Mains Dimming	750	1 - 9
60.9467	Mains Dimming	900	2 - 6
60.9414	Dimmable 0-10V	900	1 - 6
60.9602	Dim DALI	900	1 - 6
60.9207	Casambi	900	3 - 10
06.1974.00	Casambi	900	1 - 5




Dots Fixed No Trim - Single & Int 43 Frames




Pre-installation frame.
Marco de pre-instalación.

1L
08.0580.00




Pre-installation frame.
Marco de pre-instalación.

2L - Int 43
08.0581.00




Pre-installation frame.
Marco de pre-instalación.

4L - Int 43
08.0582.00




Dots Push No Trim




Pre-installation frame.
Marco de pre-instalación.

1L
08.0756.00




Dots Fixed No Trim - Divider & Int 70 Frames



70 mm divider to keep the spacing between spots when putting together 70 mm modules.


Separador de 70mm para mantener la interdistancia en tres focos al unir módulos de 70mm.



Divider - Int 70
08.0586.00


Pre-installation frame.
Marco de pre-instalación.

2L - Int 70
08.0583.00



Pre-installation frame.
Marco de pre-instalación.


4L - Int 70
08.0584.00



Light Shadow Pro Ø45 Fixed

LED Array DC 700 mA 8,8W - 816 lm - 2700K/CRI 90 / 8,8W - 834 lm - 3000K/CRI 90 / 8,8W - 926 lm - 4000K/CRI 90







LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

Módulo de iluminación LED, de bajo deslumbramiento, para ser insertado en los marcos de empotramiento (no incluidos), instalación mediante sistema de bayoneta con focos intercambiables. Driver remoto no incluido.

Recommended power supply / Equipos recomendados*:


		Serial Con.	⚠
Non Dimmable 100-240V 12W	60.8529A	1 - 1	A**
Non Dimmable 100-277V 31W	60.9387	1 - 3	B
Non Dimmable 220-240V 32W	60.9592	1 - 3	B
Non Dimmable 220-240V 42W	60.7677	1 - 3	B
Dim Dali 2 220-240V 38W	60.7678	1 - 3	B
Dim Dali 2 220-240V 20W	60.9713.0700	1 - 2	B
Dim 1-10V/Push 110-240V	60.9208	1 - 2	B
Dim 1-10V	60.9845	1 - 3	B
Mains Dimming	60.9467	1 - 2	B
Mains Dimming	60.9692	1 - 3	B
Dim Casambi/Push	60.7785	1 - 2	B

* Refer to the Drivers chapter / Ver capítulo Drivers


** Driver pass-throught for Fixed model.

Register for service operation is required for Push model. / Driver pasante para el modelo Fixed. Para el driver del modelo Push es necesaria una caja de registro.

⚠ A: Driver pass-through



⚠ B: Register for service operation is required




Optic Spot

2700K

- 05.2500.40
- 05.2500.14
- 05.2500.ER
- 05.2500.ES

15° SPOT




Luminous flux luminaire 675 lm

Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	7930	0.27
2	1982	0.54
3	881	0.81
4	496	1.08
5	317	1.35

3000K

- 05.2505.40
- 05.2505.14
- 05.2505.ER
- 05.2505.ES

15° SPOT




Luminous flux luminaire 690 lm

Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	8100	0.27
2	2025	0.54
3	900	0.81
4	506	1.08
5	324	1.35

4000K

- 05.2510.40
- 05.2510.14
- 05.2510.ER
- 05.2510.ES

15° SPOT



Luminous flux luminaire 766 lm

Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	8999	0.27
2	2250	0.54
3	1000	0.81
4	562	1.08
5	360	1.35


Internal Finish (I) · White

Optic Medium

2700K

- 05.2501.40
- 05.2501.14
- 05.2501.ER
- 05.2501.ES

20° MEDIUM




Luminous flux luminaire 671 lm

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	5725	0.34
2	1431	0.69
3	636	1.03
4	358	1.38
5	229	1.72

3000K

- 05.2506.40
- 05.2506.14
- 05.2506.ER
- 05.2506.ES

20° MEDIUM




Luminous flux luminaire 685 lm

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	5848	0.34
2	1462	0.69
3	650	1.03
4	365	1.38
5	234	1.72

4000K

- 05.2511.40
- 05.2511.14
- 05.2511.ER
- 05.2511.ES

20° MEDIUM



Luminous flux luminaire 761 lm

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	6497	0.34
2	1624	0.69
3	722	1.03
4	406	1.38
5	260	1.72


Internal Finish (I) · White

Optic Flood

2700K

- 05.2502.40
- 05.2502.14
- 05.2502.ER
- 05.2502.ES

33° FLOOD




Luminous flux luminaire 678 lm

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2219	0.58
2	555	1.17
3	247	1.75
4	139	2.34
5	89	2.92

3000K

- 05.2507.40
- 05.2507.14
- 05.2507.ER
- 05.2507.ES

33° FLOOD




Luminous flux luminaire 692 lm

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2267	0.58
2	567	1.17
3	252	1.75
4	142	2.34
5	91	2.92

4000K

- 05.2512.40
- 05.2512.14
- 05.2512.ER
- 05.2512.ES

33° FLOOD



Luminous flux luminaire 769 lm

Beam Angle:	33°	
h(m)	E(lx)	D(m)
1	2519	0.58
2	630	1.17
3	280	1.75
4	157	2.34
5	101	2.92


Internal Finish (I) · White

Optic Wide Flood

2700K

- 05.2503.40
- 05.2503.14
- 05.2503.ER
- 05.2503.ES

38° WIDE FLOOD




Luminous flux luminaire 698 lm

Beam Angle:	38°	
h(m)	E(lx)	D(m)
1	1771	0.69
2	443	1.39
3	197	2.08
4	111	2.78
5	71	3.47

3000K

- 05.2508.40
- 05.2508.14
- 05.2508.ER
- 05.2508.ES

38° WIDE FLOOD




Luminous flux luminaire 713 lm

Beam Angle:	38°	
h(m)	E(lx)	D(m)
1	1809	0.69
2	452	1.39
3	201	2.08
4	113	2.78
5	72	3.47

4000K

- 05.2513.40
- 05.2513.14
- 05.2513.ER
- 05.2513.ES

38° WIDE FLOOD



Luminous flux luminaire 792 lm


Beam Angle:	38°	
h(m)	E(lx)	D(m)
1	2009	0.69
2	502	1.39
3	223	2.08
4	126	2.78
5	80	3.47

Internal Finish (I) · White

Light Shadow Pro Ø45 Push

LED Array DC 700 mA 8,5W - 756 lm - 2700K/CRI 90 / 8,5W - 799 lm - 3000K/CRI 90 / 8,5W - 866 lm - 4000K/CRI 90





Luminaire with 2x1 functionality: it can work as downlight (recessed, flush with ceiling) or as a projector (fully adjustable). The passage from one position to the other can be made by moving the product easily by hand.

Luminaria con funcionalidad 2x1: puede actuar como downlight (empotrada, a ras del techo) o proyector (completamente orientable). El paso de una posición a otra se puede acometer moviendo el producto fácilmente con la mano.

R= Rear finish
E= External finish
I= Internal finish

R= Acabado trasero
E= Acabado exterior
I= Acabado interior

Optic Spot 2700K

R E I

05.9500.40
05.9501.40
05.9503.40


05.9505.40
05.9504.40
05.9507.40

05.9505.14
05.9504.14
05.9507.14

05.9504.ER
05.9507.ER

05.9504.ES
05.9508.ES

15°
SPOT



Luminous flux luminaire 661 lm
Internal Finish (I) · White

Beam Angle:		15°
h(m)	E(lx)	D(m)
1	7765	0.27
2	1941	0.54
3	863	0.81
4	485	1.08
5	311	1.35

Recommended power supply / Equipos recomendados*:

Non Dimmable 100-240V 12W	60.8529A
Non Dimmable 100-277V 31W	60.9387
Non Dimmable 220-240V 32W	60.9592
Non Dimmable 220-240V 42W	60.7677
Dim Dali 2 220-240V 38W	60.7678
Dim Dali 2 220-240V 20W	60.9713.0700
Dim 1-10V/Push 110-240V	60.9208
Dim 1-10V	60.9845
Mains Dimming	60.9467
Mains Dimming	60.9692
Dim Casambi/Push	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 3000K

R E I

05.9530.40
05.9531.40
05.9533.40


05.9535.40
05.9534.40
05.9537.40

05.9535.14
05.9534.14
05.9537.14

05.9534.ER
05.9537.ER

05.9534.ES
05.9538.ES

15°
SPOT



Luminous flux luminaire 661 lm
Internal Finish (I) · White

Beam Angle:		15°
h(m)	E(lx)	D(m)
1	7765	0.27
2	1941	0.54
3	863	0.81
4	485	1.08
5	311	1.35

Optic Spot 4000K

R E I

05.9560.40
05.9561.40
05.9563.40


05.9565.40
05.9564.40
05.9567.40

05.9565.14
05.9564.14
05.9567.14

05.9564.ER
05.9567.ER

05.9564.ES
05.9568.ES

15°
SPOT



Luminous flux luminaire 716 lm
Internal Finish (I) · White

Beam Angle:		15°
h(m)	E(lx)	D(m)
1	8416	0.27
2	2104	0.54
3	935	0.81
4	526	1.08
5	337	1.35

LIGHT SHADOW PRO

Optic Medium
2700K

R E I


05.9510.40
05.9511.40
05.9513.40

05.9515.40
05.9514.40
05.9517.40

05.9515.14
05.9514.14
05.9517.14

05.9514.ER
05.9517.ER

05.9514.ES
05.9518.ES



Luminous flux luminaire
657 lm
Internal Finish (I) · White

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	5606	0.34
2	1401	0.69
3	623	1.03
4	350	1.38
5	224	1.72

Optic Medium
4000K

R E I


05.9570.40
05.9571.40
05.9573.40

05.9575.40
05.9574.40
05.9577.40

05.9575.14
05.9574.14
05.9577.14

05.9574.ER
05.9577.ER

05.9574.ES
05.9578.ES



Luminous flux luminaire
712 lm
Internal Finish (I) · White

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	6076	0.34
2	1519	0.69
3	675	1.03
4	380	1.38
5	243	1.72

Optic Medium
3000K

R E I


05.9540.40
05.9541.40
05.9543.40

05.9545.40
05.9544.40
05.9547.40

05.9545.14
05.9544.14
05.9547.14

05.9544.ER
05.9547.ER

05.9544.ES
05.9548.ES



Luminous flux luminaire
657 lm
Internal Finish (I) · White

Beam Angle:	20°	
h(m)	E(lx)	D(m)
1	5607	0.34
2	1402	0.69
3	623	1.03
4	350	1.38
5	224	1.72

Accessories / Accesorios

Light Shadow Pro Ø45 Push


Honeycomb	Panel de abeja		08.0793.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 4000K >> 5100±75K 08.0794.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 4000K >> 3400±75K 08.0795.00

Only available in black. For other colours, please ask. / Solo disponible en color negro. Otros colores, consultar.

Light Shadow Pro Ø45 Push

LED Array DC 700 mA 8,5W - 756 lm - 2700K/CRI 90 / 8,5W - 799 lm - 3000K/CRI 90 / 8,5W - 866 lm - 4000K/CRI 90





Luminaire with 2x1 functionality: it can work as downlight (recessed, flush with ceiling) or as a projector (fully adjustable). The passage from one position to the other can be made by moving the product easily by hand.

Luminaria con funcionalidad 2x1: puede actuar como downlight (empotrada, a ras del techo) o proyector (completamente orientable). El paso de una posición a otra se puede acometer moviendo el producto fácilmente con la mano.

R= Rear finish
E= External finish
I= Internal finish

R= Acabado trasero
E= Acabado exterior
I= Acabado interior

Optic Flood 2700K

R E I

05.9520.40
05.9521.40
05.9523.40


05.9525.40
05.9524.40
05.9527.40

05.9525.14
05.9524.14
05.9527.14

05.9524.ER
05.9527.ER

05.9524.ES
05.9528.ES

33° FLOOD



Luminous flux luminaire 663 lm
Internal Finish (I) · White

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	2173	0.58
2	543	1.17
3	241	1.75
4	136	2.34
5	87	2.92

Recommended power supply / Equipos recomendados*:

Non Dimmable 100-240V 12W	60.8529A
Non Dimmable 100-277V 31W	60.9387
Non Dimmable 220-240V 32W	60.9592
Non Dimmable 220-240V 42W	60.7677
Dim Dali 2 220-240V 38W	60.7678
Dim Dali 2 220-240V 20W	60.9713.0700
Dim 1-10V/Push 110-240V	60.9208
Dim 1-10V	60.9845
Mains Dimming	60.9467
Mains Dimming	60.9692
Dim Casambi/Push	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Flood 3000K

R E I

05.9550.40
05.9551.40
05.9553.40


05.9555.40
05.9554.40
05.9557.40

05.9555.14
05.9554.14
05.9557.14

05.9554.ER
05.9557.ER

05.9554.ES
05.9558.ES

33° FLOOD



Luminous flux luminaire 663 lm
Internal Finish (I) · White

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	2172	0.58
2	543	1.17
3	241	1.75
4	136	2.34
5	87	2.92

Optic Flood 4000K

R E I

05.9580.40
05.9581.40
05.9583.40


05.9585.40
05.9584.40
05.9587.40

05.9585.14
05.9584.14
05.9587.14

05.9584.ER
05.9587.ER

05.9584.ES
05.9588.ES

33° FLOOD



Luminous flux luminaire 719 lm
Internal Finish (I) · White

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	2355	0.58
2	589	1.17
3	262	1.75
4	147	2.34
5	94	2.92

Accessories / Accesorios

Light Shadow Pro Ø45 Push


Honeycomb	Panel de abeja		08.0793.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 2700K >> 3125±75K 3000K >> 3600±75K 4000K >> 5100±75K 08.0794.00
			Decrease 2700K >> 2450±75K 3000K >> 2700±75K 4000K >> 3400±75K 08.0795.00

Only available in black. For other colours, please ask. / Solo disponible en color negro. Otros colores, consultar.

Light Shadow Pro Ø45 Surface

LED Array DC 250 mA 8,8W - 800 lm - 2700K/CRI 90 / 8,8W - 845 lm - 3000K/CRI 90 / 8,8W - 915 lm - 4000K/CRI 90





Luminaire for surface installation.
Integrated 220-240 V power supply.
IP54 watertightness.

E= External finish
I= Internal finish

Luminaria para instalación en superficie. Fuente de alimentación 220-240V integrada. Estanqueidad IP54.

E= Acabado exterior
I= Acabado interior

Optic Spot 2700K


E I
05.2700.40
05.2701.40
05.2703.40

05.2700.14
05.2701.14
05.2703.14

05.2701.ER
05.2703.ER

05.2701.ES
05.2704.ES

15° SPOT



Luminous flux luminaire
661 lm (EXTREME CUT OFF)
Internal Finish (I) · White

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	7765	0.27
2	1941	0.54
3	863	0.81
4	485	1.08
5	311	1.35

Optic Medium 2700K


E I
05.2705.40
05.2706.40
05.2708.40

05.2705.14
05.2706.14
05.2708.14

05.2706.ER
05.2708.ER

05.2706.ES
05.2709.ES

20° MEDIUM



Luminous flux luminaire
657 lm (EXTREME CUT OFF)
Internal Finish (I) · White

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	5607	0.34
2	1402	0.69
3	623	1.03
4	350	1.38
5	224	1.72

3000K


E I
05.2720.40
05.2721.40
05.2723.40

05.2720.14
05.2721.14
05.2723.14

05.2721.ER
05.2723.ER

05.2721.ES
05.2724.ES

15° SPOT



Luminous flux luminaire
698 lm (EXTREME CUT OFF)
Internal Finish (I) · White

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8199	0.27
2	2050	0.54
3	911	0.81
4	512	1.08
5	328	1.35

3000K


E I
05.2725.40
05.2726.40
05.2728.40

05.2725.14
05.2726.14
05.2728.14

05.2726.ER
05.2728.ER

05.2726.ES
05.2729.ES

20° MEDIUM



Luminous flux luminaire
694 lm (EXTREME CUT OFF)
Internal Finish (I) · White

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	5923	0.34
2	1481	0.69
3	658	1.03
4	370	1.38
5	237	1.72

4000K


E I
05.2740.40
05.2741.40
05.2743.40

05.2740.14
05.2741.14
05.2743.14

05.2741.ER
05.2743.ER

05.2741.ES
05.2744.ES

15° SPOT



Luminous flux luminaire
757 lm (EXTREME CUT OFF)
Internal Finish (I) · White

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8892	0.27
2	2223	0.54
3	988	0.81
4	556	1.08
5	356	1.35

4000K


E I
05.2745.40
05.2746.40
05.2748.40

05.2745.14
05.2746.14
05.2748.14

05.2746.ER
05.2748.ER

05.2746.ES
05.2749.ES

20° MEDIUM



Luminous flux luminaire
752 lm (EXTREME CUT OFF)
Internal Finish (I) · White

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	6418	0.34
2	1604	0.69
3	713	1.03
4	401	1.38
5	257	1.72

Optic Flood

E I **2700K**

05.2710.40
05.2711.40
05.2713.40


05.2710.14
05.2711.14
05.2713.14

05.2711.ER
05.2713.ER

05.2711.ES
05.2714.ES



FLOOD



Luminous flux luminaire
663 lm [EXTREME CUT OFF]
Internal Finish (I) · White

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	2172	0.58
2	543	1.17
3	241	1.75
4	136	2.34
5	87	2.92

E I **3000K**

05.2730.40
05.2731.40
05.2733.40


05.2730.14
05.2731.14
05.2733.14

05.2731.ER
05.2733.ER

05.2731.ES
05.2734.ES



FLOOD



Luminous flux luminaire
701 lm [EXTREME CUT OFF]
Internal Finish (I) · White

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	2296	0.58
2	574	1.17
3	255	1.75
4	144	2.34
5	92	2.92

E I **4000K**

05.2750.40
05.2751.40
05.2753.40


05.2750.14
05.2751.14
05.2753.14

05.2751.ER
05.2753.ER

05.2751.ES
05.2754.ES



FLOOD



Luminous flux luminaire
760 lm [EXTREME CUT OFF]
Internal Finish (I) · White


Beam Angle: 33°


h(m)	E(lx)	D(m)
1	2490	0.58
2	622	1.17
3	277	1.75
4	156	2.34
5	100	2.92

Light Shadow Pro Ø60 Fixed

LED Array DC Up to 400 mA 15W - 1402 lm - 2700K/CRI 90 / 15W - 1427 lm - 3000K/CRI 90 / 15W - 1577 lm - 4000K/CRI 90
LED Array DC 250 mA** 9.5W - 883 lm - 2700K/CRI 90 / 9.5W - 950 lm - 3000K/CRI 90 / 9.5W - 1009 lm - 4000K/CRI 90







LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

**Please select 250 mA setting in the remote driver to match the power of the Adjustable version.

Módulo de iluminación LED, de bajo deslumbramiento, para ser insertado en los marcos de empotramiento (no incluidos), instalación mediante sistema de bayoneta con focos intercambiables. Driver remoto no incluido.

**Seleccione la configuración de 250 mA en el driver remoto para que coincida con la potencia de la versión "Adjustable".

Recommended power supply / Equipos recomendados*:


	250mA	400mA
Non Dimmable 220-240V	60.9160	60.7677
Mains Dimming	60.9467	60.9467
Dim 1-10V 220-240V	60.9405	60.9439
Dim 0/1-10V/Push 110-240V	60.9188	60.9188
Dim Dali 2 220-240V	60.7678	60.7678
Dim Dali 2 110-240V	60.9222	60.9222
Dim Casambi	60.9874.0250	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot

2700K
- 03.9950.40A
- 03.9950.14
- 03.9950.ER
- 03.9950.ES

16° SPOT




Luminous flux luminaire 1191 lm

Beam Angle:	16°	
h(m)	E(lx)	D(m)
1	13613	0.27
2	3403	0.55
3	1513	0.82
4	850	1.09
5	544	1.36

3000K
- 03.9954.40A
- 03.9954.14
- 03.9954.ER
- 03.9954.ES

16° SPOT




Luminous flux luminaire 1237 lm

Beam Angle:	16°	
h(m)	E(lx)	D(m)
1	14135	0.27
2	3533	0.55
3	1571	0.82
4	883	1.09
5	565	1.36

4000K
- 03.9910.40A
- 03.9910.14
- 03.9910.ER
- 03.9910.ES

16° SPOT



Luminous flux luminaire 1339 lm


Beam Angle:	16°	
h(m)	E(lx)	D(m)
1	15307	0.27
2	3826	0.55
3	1701	0.82
4	956	1.09
5	612	1.36

Internal Finish (I) · White

Optic Medium

2700K
- 03.9951.40A
- 03.9951.14
- 03.9951.ER
- 03.9951.ES

25° MEDIUM




Luminous flux luminaire 1180 lm

Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	6736	0.45
2	1684	0.90
3	748	1.36
4	421	1.81
5	269	2.26

3000K
- 03.9955.40A
- 03.9955.14
- 03.9955.ER
- 03.9955.ES

25° MEDIUM




Luminous flux luminaire 1226 lm

Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	6994	0.45
2	1749	0.90
3	777	1.36
4	438	1.81
5	279	2.26

4000K
- 03.9911.40A
- 03.9911.14
- 03.9911.ER
- 03.9911.ES

25° MEDIUM



Luminous flux luminaire 1327 lm


Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	7574	0.45
2	1894	0.90
3	841	1.36
4	474	1.81
5	303	2.26

Internal Finish (I) · White

Optic Flood

2700K
- 03.9952.40A
- 03.9952.14
- 03.9952.ER
- 03.9952.ES

34° FLOOD




Luminous flux luminaire 1201 lm

Beam Angle:	34°	
h(m)	E(lx)	D(m)
1	3966	0.61
2	992	1.22
3	441	1.83
4	247	2.44
5	158	3.05

3000K
- 03.9956.40A
- 03.9956.14
- 03.9956.ER
- 03.9956.ES

34° FLOOD




Luminous flux luminaire 1247 lm

Beam Angle:	34°	
h(m)	E(lx)	D(m)
1	4118	0.61
2	1030	1.22
3	458	1.83
4	257	2.44
5	165	3.05

4000K
- 03.9912.40A
- 03.9912.14
- 03.9912.ER
- 03.9912.ES

34° FLOOD



Luminous flux luminaire 1350 lm


Beam Angle:	34°	
h(m)	E(lx)	D(m)
1	4459	0.61
2	1115	1.22
3	495	1.83
4	278	2.44
5	178	3.05

Internal Finish (I) · White

Optic Wide Flood

2700K
- 03.9953.40A
- 03.9953.14
- 03.9953.ER
- 03.9953.ES

51° WIDE FLOOD




Luminous flux luminaire 1171 lm

Beam Angle:	51°	
h(m)	E(lx)	D(m)
1	1571	0.95
2	393	1.89
3	174	2.84
4	98	3.79
5	63	4.74

3000K
- 03.9957.40A
- 03.9957.14
- 03.9957.ER
- 03.9957.ES

51° WIDE FLOOD




Luminous flux luminaire 1216 lm

Beam Angle:	51°	
h(m)	E(lx)	D(m)
1	1631	0.95
2	408	1.89
3	181	2.84
4	102	3.79
5	66	4.74

4000K
- 03.9913.40A
- 03.9913.14
- 03.9913.ER
- 03.9913.ES

51° WIDE FLOOD



Luminous flux luminaire 1316 lm

Beam Angle:	51°	
h(m)	E(lx)	D(m)
1	1767	0.95
2	442	1.89
3	196	2.84
4	111	3.79
5	71	4.74


Internal Finish (I) · White


*Multipack available (36 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.9950.40A - M3.9950.40A
*Embalaje múltiple disponible (36 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.9950.40A - M3.9950.40A

Light Shadow Pro Ø60 Adjustable

LED Array DC 800 mA 10,5W - 888 lm - 2700K/CRI 90 / 10,5W - 923 lm - 3000K/CRI 90 / 10,5W - 963 lm - 4000K/CRI 90







LED lighting module, with low glare, to be inserted in the recessed frames (not included), with interchangeable spots. Remote driver not included.

Módulo de iluminación LED, de bajo deslumbramiento, para ser insertado en los marcos de empotramiento (no incluidos) con focos intercambiables. Driver remoto no incluido.

Recommended power supply / Equipos recomendados*:

Non Dimmable 220-240V	60.7677
Mains Dimming	60.9467
Dim 1-10V 220-240V	60.9439
Dim 0/1-10V/Push 110-240V	60.9188
Dim Dali 2 220-240V	60.7678
Dim Casambi	60.9207


* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot

2700K

- 03.9971.40B
- 03.9971.14A
- 03.9971.ERA
- 03.9971.ESA

16° SPOT



Luminous flux luminaire 722 lm


Beam Angle: 16°

h(m)	E(lx)	D(m)
1	8749	0.28
2	2187	0.55
3	972	0.83
4	547	1.11
5	350	1.39

3000K

- 03.9976.40B
- 03.9976.14A
- 03.9976.ERA
- 03.9976.ESA

16° SPOT



Luminous flux luminaire 765 lm


Beam Angle: 16°

h(m)	E(lx)	D(m)
1	9270	0.28
2	2317	0.55
3	1030	0.83
4	579	1.11
5	371	1.39

4000K

- 03.9931.40B
- 03.9931.14A
- 03.9931.ERA
- 03.9931.ESA

16° SPOT



Luminous flux luminaire 787 lm

Beam Angle: 16°

h(m)	E(lx)	D(m)
1	9541	0.28
2	2385	0.55
3	1060	0.83
4	596	1.11
5	382	1.39


Internal Finish (I) · White

Optic Flood

2700K

- 03.9973.40B
- 03.9973.14A
- 03.9973.ERA
- 03.9973.ESA

31° FLOOD



Luminous flux luminaire 738 lm


Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2638	0.56
2	659	1.11
3	293	1.67
4	165	2.23
5	106	2.79

3000K

- 03.9978.40B
- 03.9978.14A
- 03.9978.ERA
- 03.9978.ESA

31° FLOOD



Luminous flux luminaire 782 lm


Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2796	0.56
2	699	1.11
3	311	1.67
4	174	2.23
5	112	2.79

4000K

- 03.9933.40B
- 03.9933.14A
- 03.9933.ERA
- 03.9933.ESA

31° FLOOD



Luminous flux luminaire 805 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2877	0.56
2	719	1.11
3	320	1.67
4	180	2.23
5	115	2.79


Internal Finish (I) · White

Optic Medium

2700K

- 03.9972.40B
- 03.9972.14A
- 03.9972.ERA
- 03.9972.ESA

21° MEDIUM



Luminous flux luminaire 728 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5856	0.37
2	1464	0.73
3	651	1.10
4	366	1.47
5	234	1.83

3000K

- 03.9977.40B
- 03.9977.14A
- 03.9977.ERA
- 03.9977.ESA

21° MEDIUM



Luminous flux luminaire 771 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	6205	0.37
2	1552	0.73
3	689	1.10
4	388	1.47
5	248	1.83

4000K

- 03.9932.40B
- 03.9932.14A
- 03.9932.ERA
- 03.9932.ESA

21° MEDIUM



Luminous flux luminaire 794 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	6386	0.37
2	1597	0.73
3	710	1.10
4	399	1.47
5	256	1.83

Internal Finish (I) · White


*Multipack available (36 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.9971.40B - M3.9971.40B


*Embalaje múltiple disponible (36 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.9971.40B - M3.9971.40B

Light Shadow Pro Ø60 Surface

LED Array DC Up to 350 mA 15W - 1185 lm - 2700K/CRI 90 / 15W - 1275 lm - 3000K/CRI 90 / 15W - 1355 lm - 4000K/CRI 90







Luminaire for surface installation. Integrated 220-240 V power supply. For dimmable versions, please refer to the recommended dimmers. IP54 watertightness.

E= External finish
I= Internal finish

Luminaria para instalación en superficie. Fuente de alimentación 220-240V integrada. Para las versiones regulables, consultar los dimmers recomendados. Estanqueidad IP54.

E= Acabado exterior
I= Acabado interior


Non Dimmable
Optic Spot - 2700K

E I
- 05.2600.40
- 05.2601.40
- 05.2603.40

- 05.2600.14
- 05.2601.14
- 05.2603.14

- 05.2601.ER
- 05.2603.ER

- 05.2601.ES
- 05.2604.ES



Luminous flux luminaire 1006 lm
Internal Finish (I) · White

Beam Angle:		16°
h(m)	E(lx)	D(m)
1	11497	0.27
2	2874	0.55
3	1277	0.82
4	719	1.09
5	460	1.36


Mains Dimming
Optic Spot -2700K

E I
- 05.2600.40.NI
- 05.2601.40.NI
- 05.2603.40.NI

- 05.2600.14.NI
- 05.2601.14.NI
- 05.2603.14.NI

- 05.2601.ER.NI
- 05.2603.ER.NI

- 05.2601.ES.NI
- 05.2604.ES.NI



Luminous flux luminaire 1006 lm
Internal Finish (I) · White

Beam Angle:		16°
h(m)	E(lx)	D(m)
1	11497	0.27
2	2874	0.55
3	1277	0.82
4	719	1.09
5	460	1.36


Optic Spot - 3000K

E I
- 05.2620.40
- 05.2621.40
- 05.2623.40

- 05.2620.14
- 05.2621.14
- 05.2623.14

- 05.2621.ER
- 05.2623.ER

- 05.2621.ES
- 05.2624.ES



Luminous flux luminaire 1084 lm
Internal Finish (I) · White

Beam Angle:		16°
h(m)	E(lx)	D(m)
1	12389	0.27
2	3097	0.55
3	1377	0.82
4	774	1.09
5	496	1.36


Optic Spot - 3000K

E I
- 05.2620.40.NI
- 05.2621.40.NI
- 05.2623.40.NI

- 05.2620.14.NI
- 05.2621.14.NI
- 05.2623.14.NI

- 05.2621.ER.NI
- 05.2623.ER.NI

- 05.2621.ES.NI
- 05.2624.ES.NI



Luminous flux luminaire 1084 lm
Internal Finish (I) · White

Beam Angle:		16°
h(m)	E(lx)	D(m)
1	12389	0.27
2	3097	0.55
3	1377	0.82
4	774	1.09
5	496	1.36


Optic Spot - 4000K

E I
- 05.2640.40
- 05.2641.40
- 05.2643.40

- 05.2640.14
- 05.2641.14
- 05.2643.14

- 05.2641.ER
- 05.2643.ER

- 05.2641.ES
- 05.2644.ES



Luminous flux luminaire 1150 lm
Internal Finish (I) · White

Beam Angle:		16°
h(m)	E(lx)	D(m)
1	13143	0.27
2	3286	0.55
3	1460	0.82
4	821	1.09
5	526	1.36


Optic Spot - 4000K

E I
- 05.2640.40.NI
- 05.2641.40.NI
- 05.2643.40.NI

- 05.2640.14.NI
- 05.2641.14.NI
- 05.2643.14.NI

- 05.2641.ER.NI
- 05.2643.ER.NI

- 05.2641.ES.NI
- 05.2644.ES.NI



Luminous flux luminaire 1150 lm
Internal Finish (I) · White

Beam Angle:		16°
h(m)	E(lx)	D(m)
1	13143	0.27
2	3286	0.55
3	1460	0.82
4	821	1.09
5	526	1.36

Non Dimmable

E I **Optic Medium - 2700K**


05.2605.40
05.2606.40
05.2608.40

05.2605.14
05.2606.14
05.2608.14

05.2606.ER
05.2608.ER

05.2606.ES
05.2609.ES

25°
MEDIUM



Luminous flux luminaire
997 lm
Internal Finish (I) · White

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5690	0.45
2	1422	0.90
3	632	1.36
4	356	1.81
5	228	2.26

Mains Dimming

E I **Optic Medium - 2700K**


05.2605.40.NI
05.2606.40.NI
05.2608.40.NI

05.2605.14.NI
05.2606.14.NI
05.2608.14.NI

05.2606.ER.NI
05.2608.ER.NI

05.2606.ES.NI
05.2609.ES.NI

25°
MEDIUM



Luminous flux luminaire
997 lm
Internal Finish (I) · White

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5690	0.45
2	1422	0.90
3	632	1.36
4	356	1.81
5	228	2.26

E I **Optic Medium - 3000K**


05.2625.40
05.2626.40
05.2628.40

05.2625.14
05.2626.14
05.2628.14

05.2626.ER
05.2628.ER

05.2626.ES
05.2629.ES

25°
MEDIUM



Luminous flux luminaire
1074 lm
Internal Finish (I) · White

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	6129	0.45
2	1532	0.90
3	681	1.36
4	383	1.81
5	245	2.26

E I **Optic Medium - 3000K**


05.2625.40.NI
05.2626.40.NI
05.2628.40.NI

05.2625.14.NI
05.2626.14.NI
05.2628.14.NI

05.2626.ER.NI
05.2628.ER.NI

05.2626.ES.NI
05.2629.ES.NI

25°
MEDIUM



Luminous flux luminaire
1074 lm
Internal Finish (I) · White

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	6129	0.45
2	1532	0.90
3	681	1.36
4	383	1.81
5	245	2.26

E I **Optic Medium - 4000K**


05.2645.40
05.2646.40
05.2648.40

05.2645.14
05.2646.14
05.2648.14

05.2646.ER
05.2648.ER

05.2646.ES
05.2649.ES

25°
MEDIUM



Luminous flux luminaire
1140 lm
Internal Finish (I) · White

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	6506	0.45
2	1626	0.90
3	723	1.36
4	407	1.81
5	260	2.26

E I **Optic Medium - 4000K**


05.2645.40.NI
05.2646.40.NI
05.2648.40.NI

05.2645.14.NI
05.2646.14.NI
05.2648.14.NI

05.2646.ER.NI
05.2648.ER.NI

05.2646.ES.NI
05.2649.ES.NI

25°
MEDIUM



Luminous flux luminaire
1140 lm
Internal Finish (I) · White


Beam Angle: 25°


h(m)	E(lx)	D(m)
1	6506	0.45
2	1626	0.90
3	723	1.36
4	407	1.81
5	260	2.26

Light Shadow Pro Ø60 Surface

LED Array DC Up to 350 mA 15W - 1185 lm - 2700K/CRI 90 / 15W - 1275 lm - 3000K/CRI 90 / 15W - 1355 lm - 4000K/CRI 90







Luminaire for surface installation. Integrated 220-240 V power supply. For dimmable versions, please refer to the recommended dimmers. IP54 watertightness.

E= External finish
I= Internal finish

Luminaria para instalación en superficie. Fuente de alimentación 220-240V integrada. Para las versiones regulables, consultar los dimmers recomendados. Estanqueidad IP54.

E= Acabado exterior
I= Acabado interior


Non Dimmable
Optic Flood - 2700K

E I
- 05.2610.40
- 05.2611.40
- 05.2613.40

- 05.2610.14
- 05.2611.14
- 05.2613.14

- 05.2611.ER
- 05.2613.ER

- 05.2611.ES
- 05.2614.ES



Luminous flux luminaire
1014 lm
Internal Finish (I) · White

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	3349	0.61
2	837	1.22
3	372	1.83
4	209	2.44
5	134	3.05


Mains Dimming
Optic Flood - 2700K

E I
- 05.2610.40.NI
- 05.2611.40.NI
- 05.2613.40.NI

- 05.2610.14.NI
- 05.2611.14.NI
- 05.2613.14.NI

- 05.2611.ER.NI
- 05.2613.ER.NI

- 05.2611.ES.NI
- 05.2614.ES.NI



Luminous flux luminaire
1014 lm
Internal Finish (I) · White

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	3349	0.61
2	837	1.22
3	372	1.83
4	209	2.44
5	134	3.05


Optic Flood - 3000K

E I
- 05.2630.40
- 05.2631.40
- 05.2633.40

- 05.2630.14
- 05.2631.14
- 05.2633.14

- 05.2631.ER
- 05.2633.ER

- 05.2631.ES
- 05.2634.ES



Luminous flux luminaire
1093 lm
Internal Finish (I) · White

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	3610	0.61
2	903	1.22
3	401	1.83
4	226	2.44
5	144	3.05


Optic Flood - 3000K

E I
- 05.2630.40.NI
- 05.2631.40.NI
- 05.2633.40.NI

- 05.2630.14.NI
- 05.2631.14.NI
- 05.2633.14.NI

- 05.2631.ER.NI
- 05.2633.ER.NI

- 05.2631.ES.NI
- 05.2634.ES.NI



Luminous flux luminaire
1093 lm
Internal Finish (I) · White

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	3610	0.61
2	903	1.22
3	401	1.83
4	226	2.44
5	144	3.05


Optic Flood - 4000K

E I
- 05.2650.40
- 05.2651.40
- 05.2653.40

- 05.2650.14
- 05.2651.14
- 05.2653.14

- 05.2651.ER
- 05.2653.ER

- 05.2651.ES
- 05.2654.ES



Luminous flux luminaire
1159 lm
Internal Finish (I) · White

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	3828	0.61
2	957	1.22
3	425	1.83
4	239	2.44
5	153	3.05


Optic Flood - 4000K

E I
- 05.2650.40.NI
- 05.2651.40.NI
- 05.2653.40.NI

- 05.2650.14.NI
- 05.2651.14.NI
- 05.2653.14.NI

- 05.2651.ER.NI
- 05.2653.ER.NI

- 05.2651.ES.NI
- 05.2654.ES.NI



Luminous flux luminaire
1159 lm
Internal Finish (I) · White

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	3828	0.61
2	957	1.22
3	425	1.83
4	239	2.44
5	153	3.05

Non Dimmable

E I **Optic Wide Flood - 2700K**


05.2615.40
05.2616.40
05.2618.40

05.2615.14
05.2616.14
05.2618.14

05.2616.ER
05.2618.ER

05.2616.ES
05.2619.ES





Luminous flux luminaire
989 lm
Internal Finish (I) · White

Beam Angle: 51°

h(m)	E(lx)	D(m)
1	1327	0.95
2	332	1.89
3	147	2.84
4	83	3.79
5	53	4.74

Mains Dimming

E I **Optic Wide Flood - 2700K**


05.2615.40.NI
05.2616.40.NI
05.2618.40.NI

05.2615.14.NI
05.2616.14.NI
05.2618.14.NI

05.2616.ER.NI
05.2618.ER.NI

05.2616.ES.NI
05.2619.ES.NI





Luminous flux luminaire
989 lm
Internal Finish (I) · White

Beam Angle: 51°

h(m)	E(lx)	D(m)
1	1327	0.95
2	332	1.89
3	147	2.84
4	83	3.79
5	53	4.74

E I **Optic Wide Flood - 3000K**


05.2635.40
05.2636.40
05.2638.40

05.2635.14
05.2636.14
05.2638.14

05.2636.ER
05.2638.ER

05.2636.ES
05.2639.ES





Luminous flux luminaire
1065 lm
Internal Finish (I) · White

Beam Angle: 51°

h(m)	E(lx)	D(m)
1	1429	0.95
2	357	1.89
3	159	2.84
4	89	3.79
5	57	4.74

E I **Optic Wide Flood - 3000K**


05.2635.40.NI
05.2636.40.NI
05.2638.40.NI

05.2635.14.NI
05.2636.14.NI
05.2638.14.NI

05.2636.ER.NI
05.2638.ER.NI

05.2636.ES.NI
05.2639.ES.NI





Luminous flux luminaire
1065 lm
Internal Finish (I) · White

Beam Angle: 51°

h(m)	E(lx)	D(m)
1	1429	0.95
2	357	1.89
3	159	2.84
4	89	3.79
5	57	4.74

E I **Optic Wide Flood - 4000K**


05.2655.40
05.2656.40
05.2658.40

05.2655.14
05.2656.14
05.2658.14

05.2656.ER
05.2658.ER

05.2656.ES
05.2659.ES





Luminous flux luminaire
1130 lm
Internal Finish (I) · White

Beam Angle: 51°

h(m)	E(lx)	D(m)
1	1517	0.95
2	379	1.89
3	169	2.84
4	95	3.79
5	61	4.74

E I **Optic Wide Flood - 4000K**


05.2655.40.NI
05.2656.40.NI
05.2658.40.NI

05.2655.14.NI
05.2656.14.NI
05.2658.14.NI

05.2656.ER.NI
05.2658.ER.NI

05.2656.ES.NI
05.2659.ES.NI





Luminous flux luminaire
1130 lm
Internal Finish (I) · White


Beam Angle: 51°


h(m)	E(lx)	D(m)
1	1517	0.95
2	379	1.89
3	169	2.84
4	95	3.79
5	61	4.74

Light Shadow Pro Ø90 Fixed

Super Spot: LED Array DC 500 mA 18W - 1636 lm - 2700K/CRI 90 / 18W - 1723 lm - 3000K/CRI 90 / 18W - 1815 lm - 4000K/CRI 90
S/M/F/WF: LED Array DC 600 mA 22W - 2191 lm - 2700K/CRI 90 / 22W - 2339 lm - 3000K/CRI 90 / 22W - 2457 lm - 4000K/CRI 90
S/M/F/WF: LED Array DC 500 mA** 18W - 1803 lm - 2700K/CRI 90 / 18W - 1921 lm - 3000K/CRI 90 / 18W - 2057 lm - 4000K/CRI 90







LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

**Please select 500 mA setting in the remote driver to match the power of the Adjustable version.

Módulo de iluminación LED, de bajo deslumbramiento, para ser insertado en los marcos de empotramiento (no incluidos), instalación mediante sistema de bayoneta con focos intercambiables. Driver remoto no incluido.

**Seleccione la configuración de 500 mA en el driver remoto para que coincida con la potencia de la versión "Adjustable".


Recommended power supply / Equipos recomendados*:

	500mA	600mA
Non Dimmable 220-240V	60.7677	60.7677
Non Dimmable 110-240V	60.9387	60.9387
Mains Dimming	60.9467	60.9692
Dim 1-10V 220-240V	60.9439	60.9439
Dim 0/1-10V/Push 110-240V	60.9188	60.8533
Dim Dali 2 220-240V	60.7678	60.7678
Dim Casambi	60.9207	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Super Spot

2700K
- 03.9968.40A
- 03.9968.14
- 03.9968.ER
- 03.9968.ES




Luminous flux luminaire 1300 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	35593	0.17
2	8898	0.34
3	3955	0.51
4	2225	0.67
5	1424	0.84

3000K
- 03.9969.40A
- 03.9969.14
- 03.9969.ER
- 03.9969.ES




Luminous flux luminaire 1368 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	37479	0.17
2	9370	0.34
3	4164	0.51
4	2342	0.67
5	1499	0.84

4000K
- 03.9924.40A
- 03.9924.14
- 03.9924.ER
- 03.9924.ES



Luminous flux luminaire 1491 lm


Beam Angle: 10°

h(m)	E(lx)	D(m)
1	40831	0.17
2	10208	0.34
3	4537	0.51
4	2552	0.67
5	1633	0.84

Internal Finish (I) · White

Optic Medium

2700K
- 03.9961.40A
- 03.9961.14
- 03.9961.ER
- 03.9961.ES




Luminous flux luminaire 1814 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	9219	0.48
2	2305	0.95
3	1024	1.43
4	576	1.90
5	369	2.38

3000K
- 03.9965.40A
- 03.9965.14
- 03.9965.ER
- 03.9965.ES




Luminous flux luminaire 1936 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	9840	0.48
2	2460	0.95
3	1093	1.43
4	615	1.90
5	394	2.38

4000K
- 03.9921.40A
- 03.9921.14
- 03.9921.ER
- 03.9921.ES



Luminous flux luminaire 2034 lm


Beam Angle: 27°

h(m)	E(lx)	D(m)
1	10339	0.48
2	2585	0.95
3	1149	1.43
4	646	1.90
5	414	2.38

Internal Finish (I) · White

Optic Spot

2700K
- 03.9960.40A
- 03.9960.14
- 03.9960.ER
- 03.9960.ES




Luminous flux luminaire 1786 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	24449	0.25
2	6112	0.50
3	2717	0.75
4	1528	1.00
5	978	1.25

3000K
- 03.9964.40A
- 03.9964.14
- 03.9964.ER
- 03.9964.ES




Luminous flux luminaire 1906 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	26098	0.25
2	6524	0.50
3	2900	0.75
4	1631	1.00
5	1044	1.25

4000K
- 03.9920.40A
- 03.9920.14
- 03.9920.ER
- 03.9920.ES



Luminous flux luminaire 2003 lm


Beam Angle: 14°

h(m)	E(lx)	D(m)
1	27421	0.25
2	6855	0.50
3	3047	0.75
4	1714	1.00
5	1097	1.25

Internal Finish (I) · White

Optic Flood

2700K
- 03.9962.40A
- 03.9962.14
- 03.9962.ER
- 03.9962.ES




Luminous flux luminaire 1760 lm

Beam Angle: 39°

h(m)	E(lx)	D(m)
1	4809	0.71
2	1202	1.42
3	534	2.13
4	301	2.85
5	192	3.56

3000K
- 03.9966.40A
- 03.9966.14
- 03.9966.ER
- 03.9966.ES




Luminous flux luminaire 1878 lm

Beam Angle: 39°

h(m)	E(lx)	D(m)
1	5133	0.71
2	1283	1.42
3	570	2.13
4	321	2.85
5	205	3.56

4000K
- 03.9922.40A
- 03.9922.14
- 03.9922.ER
- 03.9922.ES



Luminous flux luminaire 1974 lm

Beam Angle: 39°

h(m)	E(lx)	D(m)
1	5393	0.71
2	1348	1.42
3	599	2.13
4	337	2.85
5	216	3.56

Internal Finish (I) · White


Optic Wide Flood

2700K

03.9963.40A
03.9963.14
03.9963.ER
03.9963.ES



WIDE FLOOD



Luminous flux luminaire
1872 lm

Beam Angle: 48°


h(m)	E(lx)	D(m)
1	3084	0.89
2	771	1.79
3	343	2.68
4	193	3.58
5	123	4.47

3000K

03.9967.40A
03.9967.14
03.9967.ER
03.9967.ES



WIDE FLOOD



Luminous flux luminaire
1999 lm

Beam Angle: 48°


h(m)	E(lx)	D(m)
1	3293	0.89
2	823	1.79
3	366	2.68
4	206	3.58
5	132	4.47

4000K

03.9923.40A
03.9923.14
03.9923.ER
03.9923.ES



WIDE FLOOD



Luminous flux luminaire
2100 lm

Beam Angle: 48°

h(m)	E(lx)	D(m)
1	3459	0.89
2	865	1.79
3	384	2.68
4	216	3.58
5	138	4.47


Internal Finish (I) · White


*Multipack available (24 pcs per box). How to order: “Replace the initial 0 with an M + reference”. Example: 03.9968.40A - M3.9968.40A
*Embalaje múltiple disponible (24 unidades por caja). Cómo hacer el pedido: “Sustituir el 0 inicial por una M + referencia”. Ejemplo: 03.9968.40A - M3.9968.40A

Light Shadow Pro Ø90 Adjustable

Super Spot: LED Array DC 800 mA 10W - 870 lm - 2700K/CRI 90 / 10W - 914 lm - 3000K/CRI 90 / 10W - 949 lm - 4000K/CRI 90
S/M/F: LED Array DC 500 mA 18W - 1637 lm - 2700K/CRI 90 / 18W - 1722 lm - 3000K/CRI 90 / 18W - 1877 lm - 4000K/CRI 90







LED lighting module, with low glare, to be inserted in the recessed frames (not included), with interchangeable spots. Remote driver not included.

Módulo de iluminación LED, de bajo deslumbramiento, para ser insertado en los marcos de empotramiento (no incluidos) con focos intercambiables. Driver remoto no incluido.

Recommended power supply / Equipos recomendados*:

	500mA 18W	800mA 10W
Non Dimmable 220-240V	60.7677	60.7677
Mains Dimming	60.9467	60.9467
Dim 1-10V 220-240V	60.9439	60.9439
Dim 0/1-10V/Push 110-240V	60.9188	60.9188
Dim Dali 2 220-240V	60.7678	60.7678
Dim Dali 2 110-240V	60.9222	
Dim Casambi	60.9207	60.9207


* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Super Spot

2700K

- 03.9980.40A
- 03.9980.14
- 03.9980.ER
- 03.9980.ES






Luminous flux luminaire 770 lm

Beam Angle:	9°
h(m)	E(lx) D(m)
1	26281 0.16
2	6570 0.31
3	2920 0.47
4	1643 0.62
5	1051 0.78

3000K

- 03.9985.40A
- 03.9985.14
- 03.9985.ER
- 03.9985.ES






Luminous flux luminaire 808 lm

Beam Angle:	9°
h(m)	E(lx) D(m)
1	27607 0.16
2	6902 0.31
3	3067 0.47
4	1725 0.62
5	1104 0.78

4000K

- 03.9940.40A
- 03.9940.14
- 03.9940.ER
- 03.9940.ES





Luminous flux luminaire 839 lm

Beam Angle:	9°
h(m)	E(lx) D(m)
1	28661 0.16
2	7165 0.31
3	3185 0.47
4	1791 0.62
5	1146 0.78


Internal Finish (I) · White

Optic Spot

2700K

- 03.9981.40A
- 03.9981.14
- 03.9981.ER
- 03.9981.ES






Luminous flux luminaire 1327 lm

Beam Angle:	16°
h(m)	E(lx) D(m)
1	15200 0.27
2	3800 0.54
3	1689 0.82
4	950 1.09
5	608 1.36

3000K

- 03.9986.40A
- 03.9986.14
- 03.9986.ER
- 03.9986.ES






Luminous flux luminaire 1397 lm

Beam Angle:	16°
h(m)	E(lx) D(m)
1	16001 0.27
2	4000 0.54
3	1778 0.82
4	1000 1.09
5	640 1.36

4000K

- 03.9941.40A
- 03.9941.14
- 03.9941.ER
- 03.9941.ES





Luminous flux luminaire 1522 lm

Beam Angle:	16°
h(m)	E(lx) D(m)
1	17438 0.27
2	4359 0.54
3	1938 0.82
4	1090 1.09
5	698 1.36


Internal Finish (I) · White

Optic Medium

2700K

- 03.9982.40A
- 03.9982.14
- 03.9982.ER
- 03.9982.ES






Luminous flux luminaire 1334 lm

Beam Angle:	24°
h(m)	E(lx) D(m)
1	9069 0.42
2	2267 0.83
3	1008 1.25
4	567 1.67
5	363 2.09

3000K

- 03.9987.40A
- 03.9987.14
- 03.9987.ER
- 03.9987.ES






Luminous flux luminaire 1404 lm

Beam Angle:	24°
h(m)	E(lx) D(m)
1	9546 0.42
2	2386 0.83
3	1061 1.25
4	597 1.67
5	382 2.09

4000K

- 03.9942.40A
- 03.9942.14
- 03.9942.ER
- 03.9942.ES





Luminous flux luminaire 1530 lm

Beam Angle:	24°
h(m)	E(lx) D(m)
1	10404 0.42
2	2601 0.83
3	1156 1.25
4	650 1.67
5	416 2.09


Internal Finish (I) · White

Optic Flood

2700K

- 03.9983.40A
- 03.9983.14
- 03.9983.ER
- 03.9983.ES






Luminous flux luminaire 1404 lm

Beam Angle:	33°
h(m)	E(lx) D(m)
1	4877 0.60
2	1219 1.19
3	542 1.79
4	305 2.39
5	195 2.98

3000K

- 03.9988.40A
- 03.9988.14
- 03.9988.ER
- 03.9988.ES






Luminous flux luminaire 1478 lm

Beam Angle:	33°
h(m)	E(lx) D(m)
1	5133 0.60
2	1283 1.19
3	570 1.79
4	321 2.39
5	205 2.98

4000K

- 03.9943.40A
- 03.9943.14
- 03.9943.ER
- 03.9943.ES





Luminous flux luminaire 1593 lm

Beam Angle:	33°
h(m)	E(lx) D(m)
1	5533 0.60
2	1383 1.19
3	615 1.79
4	346 2.39
5	221 2.98


Internal Finish (I) · White


*Multipack available (24 pcs per box). How to order: "Replace the initial 0 with an M + reference". Example: 03.9980.40A - M3.9980.40A
*Embalaje múltiple disponible (24 unidades por caja). Cómo hacer el pedido: "Sustituir el 0 inicial por una M + referencia". Ejemplo: 03.9980.40A - M3.9980.40A

Light Shadow Pro Ø90 Wall-Washer

LED Array DC 500 mA 18W - 1593 lm - 2700K/CRI 90 / 18W - 1752 lm - 3000K/CRI 90 / 18W - 1867 lm - 4000K/CRI 90







LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

Módulo de iluminación LED, de bajo deslumbramiento, para ser insertado en los marcos de empotramiento (no incluidos), instalación mediante sistema de bayoneta con focos intercambiables. Driver remoto no incluido.

Recommended power supply / Equipos recomendados*:

Non Dimmable 100-277V 31W	60.9387
Non Dimmable 220-240V 22W	60.9160
Non Dimmable 220-240V 42W	60.7677
Dim Dali 2 220-240V 38W	60.7678
Dim Dali 2 110-240V 20W	60.9222
Dim 1-10V/Push 110-240V	60.9208
Dim 1-10V	60.9843
Phase cut DIM	60.9467
Dim Casambi/Push	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers


Optic Medium

2700K

- 03.9890.40
- 03.9890.14
- 03.9890.ER
- 03.9890.ES



MEDIUM



Luminous flux luminaire
1216 lm

Beam Angle: 24°


h(m)	E(lx)	D(m)
1	3773	0.47
2	943	0.94
3	419	1.41
4	236	1.88
5	151	2.34

3000K

- 03.9891.40
- 03.9891.14
- 03.9891.ER
- 03.9891.ES



MEDIUM



Luminous flux luminaire
1336 lm

Beam Angle: 24°


h(m)	E(lx)	D(m)
1	4147	0.47
2	1037	0.94
3	461	1.41
4	259	1.88
5	166	2.34

4000K

- 03.9892.40
- 03.9892.14
- 03.9892.ER
- 03.9892.ES



MEDIUM




Luminous flux luminaire
1425 lm

Beam Angle: 24°


h(m)	E(lx)	D(m)
1	4421	0.47
2	1105	0.94
3	491	1.41
4	276	1.88
5	177	2.34

Internal Finish (I) · White

Fixed, Adjustable & Wall-Washer




Push



Pro Push - Functionality and Positioning


Light Shadow Push can be placed in top position, functioning as a downlight (perfectly flush to ceiling), or in bottom position, functioning as an adjustable spotlight.

Light Shadow Push puede colocarse en posición superior -funcionando como un downlight (perfectamente enrasado a techo)-, o en posición inferior -funcionado como un proyector orientable-.




Accessories Ø45 / Accesorios Ø45

Frame Trim Ø45.



Marco de Instalación Trim Ø45.









Fixed
08.0360.40
08.0360.14
08.0360.ER
08.0360.ES


Frame No Trim Ø45.




Marco de Instalación No Trim Ø45.










Fixed
08.0361.00












Push
08.0757.00

Drivers for Serial Connection / Equipos para Conexión en Serie*

Driver 60.8529A	DIM Protocol	Min-Max Spot(s) per Driver	⚠
60.9387	Non Dimmable 100-240V 12W	1 - 1	A** - B**
60.9592	Non Dimmable 100-277V 31W	1 - 3	B
60.7677	Non Dimmable 220-240V 32W	1 - 3	B
60.7678	Non Dimmable 220-240V 42W	1 - 3	B
60.9713.0700	Dim Dali 2 220-240V 38W	1 - 3	B
60.9208	Dim Dali 2 220-240V 20W	1 - 2	B
60.9845	Dim 1-10V/Push 110-240V	1 - 2	B
60.9467	Dim 1-10V	1 - 3	B
60.9692	Mains Dimming 220-240V 20W	1 - 2	B
60.7785	Mains Dimming 220-240V 30W	1 - 3	B
	Dim Casambi/Push	1 - 2	B



* Refer to the Drivers chapter / Ver capítulo Drivers

** Driver pass-throught for Fixed model.
Register for service operation is required for Push model. /
Driver pasante para el modelo Fixed.
Para el driver del modelo Push es necesaria una caja de registro.

40 White
40 Blanco



14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado




ES Brushed Bronze
ES Bronce Cepillado




Accessories Ø60 / Accesorios Ø60

Frame Trim Ø60.

Marco de Instalación Trim Ø60.











Fixed
08.0160.40
08.0160.14
08.0160.ER
08.0160.ES

Fixed Multipack 30U*
M8.0160.40
M8.0160.14











Adjustable
08.0164.40
08.0164.14
08.0164.ER
08.0164.ES

Adjustable Multipack 30U*
M8.0164.40
M8.0164.14

Frame No Trim Ø60.

Marco de Instalación No Trim Ø60.












Fixed
08.0192.00

Fixed Multipack 48U*
M8.0192.00









Adjustable
08.0166.00


Adjustable Multipack 48U*
M8.0166.00

Accessory Ø60 Adjustable / Accesorio Ø60 Adjustable

Orientation Toolkit
Adjustable Ø60.

Herramienta de orientación
Adjustable Ø60.





08.0825.00

---

40 White
40 Blanco





14 Black
14 Negro





ER Brushed Steel
ER Acero Cepillado





ES Brushed Bronze
ES Bronce Cepillado







* Multipack available. Please consult.
* Embalaje múltiple disponible. Consultar.

Accessories Ø90 / Accesorios Ø90


Frame Trim Ø90.

Marco de Instalación Trim Ø90.












Fixed & Wall-Washer**
08.0161.40
08.0161.14
08.0161.ER
08.0161.ES

Fixed & Wall-Washer** Multipack 20U*
M8.0161.40
M8.0161.14











Adjustable
08.0165.40
08.0165.14
08.0165.ER
08.0165.ES

Adjustable Multipack 20U*
M8.0165.40
M8.0165.14


Frame No Trim Ø90.

Marco de Instalación No Trim Ø90.












Fixed & Wall-Washer**
08.0193.00

Fixed & Wall-Washer** Multipack 48U*
M8.0193.00









Adjustable
08.0167.00


Adjustable Multipack 48U*
M8.0167.00

Accessory Ø90 Adjustable / Accesorio Ø90 Adjustable

Orientation Toolkit
Adjustable Ø90.

Herramienta de orientación
Adjustable Ø90.





08.0826.00

---

40 White
40 Blanco





14 Black
14 Negro





ER Brushed Steel
ER Acero Cepillado





ES Brushed Bronze
ES Bronce Cepillado





* Multipack available. Please consult.
* Embalaje múltiple disponible. Consultar.
** Wall-Washer: See the proper distance to wall and spacing between units in the installation instructions.
** Wall-Washer: Consulte la distancia a pared e interdistancia adecuadas en las instrucciones de instalación.

ECLECTIC

DESIGNED BY FLOS ARCHITECTURAL

ECLECTIC Ø70
FIXED



ECLECTIC Ø70
ADJUSTABLE



LIGHT SOURCE
LED ARRAY
7,5W
686 lm
2700K/CRI 90
768 lm
3000K/CRI 90

ECLECTIC Ø90
FIXED



LIGHT SOURCE
LED ARRAY
10,5W
1114 lm
2700K/CRI 90
1162 lm
3000K/CRI 90

LIGHT SOURCE
POWER LED
7W
534 lm
2700K/CRI 90
572 lm
3000K/CRI 90

ECLECTIC Ø90
ADJUSTABLE



LIGHT SOURCE
LED ARRAY
13W
1026 lm
1800K-3000K
CRI 90

The product pictures above represent Eclectic equipped with a Cone Style Module
Las imágenes superiores de Eclectic están equipadas con Cone Style Module

Cone Style Module

☐ 40 White*
40 Blanco*



■ 14 Black
14 Negro



Soft Style Module

☐ 40 White*
40 Blanco*



■ 14 Black
14 Negro



Flat Style Module

☐ 40 White*
40 Blanco*



■ 14 Black
14 Negro



* Adherent base suitable for painting / Base adherente apta para ser pintada

FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play

ECLECTIC

Description
Eclectic is a recessed in ceiling, indoor luminaire, designed with a fully modular concept, following the principles of circular design and economy. This means that the product, which is marketed as a complete luminaire, can be broken down into a series of modules that define its features and which, in turn, are offered as spare parts. These modules can be added, combined or mixed to configure a luminaire that specifically meets the requirements of each specific project. Even the aesthetics of the product are interchangeable. Moreover, modifications can be made at any point in the life cycle, even after it has been installed. Eclectic is therefore a "future-proof" design due to its versatility in adapting to changes in future needs.
To make this product design idea pragmatic, all parts of Eclectic can be easily disassembled without tools. Modules are combined using mechanical (clipping and threading) or magnetic (with magnets) connections, without the need for any glue, adhesive or soldering. This, in turn, makes the product easily separable for recycling, making it a sustainable and environmentally friendly product.

Optical System
Eclectic is equipped with a patented optical system with double focal lenses. This technology provides Eclectic with extraordinary control of light distribution, eliminating glare and achieving visual comfort, while providing high LOR (Light Output Ratio) and high luminous efficiency.
In addition, in order to offer a complete range of light beam angles, Eclectic combines an Array LED source with a Power LED source. Thus, Eclectic's range provides the specifier with Super Spot, Spot, Medium, Flood and Wide Flood beam angles (*check correspondence between beam angles, sizes and type of LED source).
In addition to the different lenses, the optical system is complemented by a screen made of high-gloss technical polycarbonate with anti-glare properties. The position of the LED, recessed with respect to the outer plane of the luminaire, provides a cut-off angle between 41º and 55º (depending on the model). Thanks to this, direct visual access to the light source by the user is limited and a "high comfort" effect is achieved.

Power Supplies
In Dim to Warm models the driver is included. In the rest of the models, it is supplied separately.
The drivers fit through the recessing hole.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Control System
Eclectic is available with Casambi (individual, point to point), DALI2 - Push, 0-10V, Phase cut (mains DIM) and on/off control protocols.

Spare Parts
Among all Eclectic modules (parts), Flos markets the following ones as independent, and as standard: mounting pre-frames (Trim / No Trim), the different lenses (Super Spot, Spot, Medium, Flood and Wide Flood**), the orientation modules (fixed or adjustable) and the style modules (flat, soft and cone) The module that acts as a light engine is not offered as a standard spare part in the catalog.
(**check correspondence between lenses, sizes and type of LED source).

Accessories
Eclectic is fitted with accessories that enhance the technical character of the luminaire, such as the anti-glare honeycomb grid, the IP54 accessories for the adjustable versions and dichroic filters for color temperature correction.

Installation
Once the installation pre-frames have been applied, Eclectic is fixed to them by means of a magnetic attachment system that is extremely easy and pleasant to use. This attachment method withstands the weight of the product and has passed the most demanding quality, durability and stress tests that guarantee its absolute safety.

Standard Compliance and Quality Marks
The luminaire complies with the EN60598-1 European Technical Standards and any subsequent additions.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Descripción
Eclectic es una luminaria de interior empotrable en techo que ha sido diseñada con un concepto totalmente modular, siguiendo los principios del diseño y la economía circular. Esto hace que el producto, que se comercializa como una luminaria completa, se pueda descomponer en una serie de módulos que definen sus características y que, a su vez, se ofrecen como piezas de repuesto / recambio.
Estos módulos se pueden añadir, combinar o mezclar para configurar una luminaria que cumpla específicamente con las exigencias de cada proyecto concreto. Incluso la estética del producto es intercambiable. Además, esta capacidad de modificación es posible en cualquier momento del ciclo de vida -incluso después de haber sido instalado-.
Por ello, Eclectic es un diseño *«future-proof»* (a prueba de obsolescencia), por su versatilidad para adaptarse a cambios en las necesidades futuras.
Para facilitar que esta idea de diseño de producto sea pragmática, todas las partes de Eclectic se pueden desmontar fácilmente sin necesidad de herramientas. La combinación de los módulos se realiza a través de uniones mecánicas (clipajes y roscas) o magnéticas (con imanes), sin necesidad de ningún tipo de cola, pegamento o soldadura. Esto hace, a su vez, que el producto sea fácilmente separable para su reciclaje, haciéndolo así un producto sostenible y respetuoso con el medioambiente.

Sistema óptico
Eclectic está provisto de un sistema óptico patentado con lentes de doble focal. Esta tecnología ofrece a Eclectic un extraordinario control de la distribución lumínica, que elimina el deslumbramiento y consigue un elevadísimo confort visual, a la par que una eficiencia lumínica de alto LOR *(Light Output Ratio)*.
Además, para ofertar una gama de aperturas de haz completa, Eclectic combina una fuente LED Array con otra *Power LED.* Así, la gama de Eclectic brinda al especificador aperturas *Super Spot, Spot, Medium, Flood* y *Wide Flood* (*consultar correspondencia entre aperturas, tallas y tipo de fuente LED).
Junto a las diferentes lentes, el sistema óptico viene complementado por una pantalla fabricada en policarbonato técnico de alto brillo y propiedades antideslumbramiento. La posición del LED, retranqueado respecto al plano exterior de la luminaria, propicia un *cut-off* angle de entre 41º y 55º (según el modelo). Así, se limita el acceso visual directo a la fuente de luz por parte del usuario y se logra el efecto «high comfort».

Unidades de Alimentación
El equipo se suministra por separado en todos los modelos, salvo en la versión Dim to Warm (en la que se comercializa el driver en conjunto con la luminaria).
Los drivers caben a través del agujero de empotramiento.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (Drivers).

Sistema de control
Eclectic está disponible con protocolos de control Casambi (individual, punto a punto), *DALI2 · Push, 0/1-10V*, Recorte de fase *(mains DIM)* y on/off.

Recambios
Entre todos los módulos (partes) de Eclectic, Flos comercializa -de serie-, como piezas independientes, los siguientes: premarcos de montaje *(Trim / No Trim)*, las diferentes lentes *(Super Spot, Spot, Medium, Flood* y *Wide Flood**)*, los módulos de orientabilidad (fijo o ajustable) y los módulos estéticos *(flat, soft* y *cone)*. El módulo que actúa como motor de luz no se ofrece de serie en catálogo como pieza de reemplazo.
(**consultar correspondencia entre lentes, tallas y tipo de fuente LED).

Accesorios
Eclectic cuenta con accesorios que incentivan el carácter técnico de la luminaria como son el panel de abeja antideslumbramiento, los accesorios IP54 para las versiones ajustables y los filtros dicroicos para la corrección de la temperatura de color.

Instalación
Una vez aplicados los premarcos de instalación, Eclectic se fija a ellos a través de un sistema de sujeción magnético de un uso extremadamente sencillo y agradable. Este método de unión soporta sobradamente el peso del producto y ha superado los más exigentes test de calidad, durabilidad y estrés que garantizan la absoluta seguridad del mismo.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Eclectic Ø70 - Fixed Cone

LED Array DC 600 mA - 7,5W - 686 lm - 2700K/CRI 90 / 7,5W - 768 lm - 3000K/CRI 90







Eclectic Ø70. Non-adjustable Downlight. "Cone" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 47° cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø70. Downlight no orientable. Frontal de estética tipo «cone». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 47°. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Recommended power supply / Equipos recomendados*:

Non Dimmable 32W	60.9592
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0600
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 40W	60.9845
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8000.40
05.8000.14






Luminous flux luminaire
405 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5713	0.26
2	1428	0.52
3	635	0.77
4	357	1.03
5	229	1.29

3000K
Optic Spot
05.8010.40
05.8010.14






Luminous flux luminaire
454 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6397	0.26
2	1599	0.52
3	711	0.77
4	400	1.03
5	256	1.29

Optic Medium
05.8001.40
05.8001.14






Luminous flux luminaire
514 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	4534	0.35
2	1133	0.69
3	504	1.04
4	283	1.38
5	181	1.73

Optic Medium
05.8011.40
05.8011.14






Luminous flux luminaire
576 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	5080	0.35
2	1270	0.69
3	564	1.04
4	318	1.38
5	203	1.73

Optic Flood
05.8002.40
05.8002.14






Luminous flux luminaire
529 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	1578	0.63
2	395	1.26
3	175	1.89
4	99	2.52
5	63	3.15

Optic Flood
05.8012.40
05.8012.14





Luminous flux luminaire
592 lm


Beam Angle: 35°


h(m)	E(lx)	D(m)
1	1767	0.63
2	442	1.26
3	196	1.89
4	110	2.52
5	71	3.15

Eclectic Ø70 - Fixed Soft

LED Array DC 600 mA - 7,5W - 686 lm - 2700K/CRI 90 / 7,5W - 768 lm - 3000K/CRI 90







Eclectic Ø70. Non-adjustable Downlight. "Soft" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 47° cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø70. Downlight no orientable. Frontal de estética tipo «soft». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 47°. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Recommended power supply / Equipos recomendados*:

Non Dimmable 32W	60.9592
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0600
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 40W	60.9845
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8003.40
05.8003.14






Luminous flux luminaire
419 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5820	0.26
2	1455	0.53
3	647	0.79
4	364	1.05
5	233	1.31

3000K
Optic Spot
05.8013.40
05.8013.14






Luminous flux luminaire
469 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6516	0.26
2	1629	0.53
3	724	0.79
4	407	1.05
5	261	1.31

Optic Medium
05.8004.40
05.8004.14






Luminous flux luminaire
514 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	4531	0.34
2	1133	0.69
3	503	1.03
4	283	1.38
5	181	1.72

Optic Medium
05.8014.40
05.8014.14






Luminous flux luminaire
575 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	5071	0.34
2	1268	0.69
3	563	1.03
4	317	1.38
5	203	1.72

Optic Flood
05.8005.40
05.8005.14






Luminous flux luminaire
529 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	1574	0.63
2	394	1.26
3	175	1.89
4	98	2.52
5	63	3.15

Optic Flood
05.8015.40
05.8015.14





Luminous flux luminaire
592 lm


Beam Angle: 35°


h(m)	E(lx)	D(m)
1	1763	0.63
2	441	1.26
3	196	1.89
4	110	2.52
5	71	3.15

Eclectic Ø70 - Fixed Flat

LED Array DC 600 mA - 7,5W - 686 lm - 2700K/CRI 90 / 7,5W - 768 lm - 3000K/CRI 90







Eclectic Ø70. Non-adjustable Downlight. "Flat" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 55º cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø70. Downlight no orientable. Frontal de estética tipo «flat». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 55º. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

Non Dimmable 32W	60.9592
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0600
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 40W	60.9845
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8006.40
05.8006.14




Luminous flux luminaire
404 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5909	0.26
2	1477	0.52
3	657	0.77
4	369	1.03
5	236	1.29

3000K
Optic Spot
05.8016.40
05.8016.14




Luminous flux luminaire
452 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6616	0.26
2	1654	0.52
3	735	0.77
4	413	1.03
5	265	1.29

Optic Medium
05.8007.40
05.8007.14




Luminous flux luminaire
502 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4575	0.34
2	1144	0.68
3	508	1.02
4	286	1.36
5	183	1.70

Optic Medium
05.8017.40
05.8017.14




Luminous flux luminaire
562 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	5124	0.34
2	1281	0.68
3	569	1.02
4	320	1.36
5	205	1.70

Optic Flood
05.8008.40
05.8008.14




Luminous flux luminaire
518 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	1577	0.63
2	394	1.25
3	175	1.88
4	99	2.50
5	63	3.13

Optic Flood
05.8018.40
05.8018.14



Luminous flux luminaire
581 lm


Beam Angle: 35°


h(m)	E(lx)	D(m)
1	1766	0.63
2	441	1.25
3	196	1.88
4	110	2.50
5	71	3.13

Eclectic Ø70 - Adjustable Cone

LED Array DC 600 mA - 7,5W - 686 lm - 2700K/CRI 90 / 7,5W - 768 lm - 3000K/CRI 90







Eclectic Ø70. Adjustable Downlight (35º tilt, 360º rotation). "Cone" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 47º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø70. Downlight orientable (basculación 35º, giro 360º). Frontal de estética tipo «cone». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 47º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

Non Dimmable 32W	60.9592
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0600
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 40W	60.9845
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8020.40
05.8020.14




Luminous flux luminaire
411 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5669	0.26
2	1417	0.53
3	630	0.79
4	354	1.06
5	227	1.32

3000K
Optic Spot
05.8030.40
05.8030.14




Luminous flux luminaire
460 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6347	0.26
2	1587	0.53
3	705	0.79
4	397	1.06
5	254	1.32

Optic Medium
05.8021.40
05.8021.14




Luminous flux luminaire
500 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4664	0.33
2	1166	0.66
3	518	0.98
4	291	1.31
5	187	1.64

Optic Medium
05.8031.40
05.8031.14




Luminous flux luminaire
560 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	5221	0.33
2	1305	0.66
3	580	0.98
4	326	1.31
5	209	1.64

Optic Flood
05.8022.40
05.8022.14




Luminous flux luminaire
511 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	1499	0.64
2	375	1.28
3	167	1.92
4	94	2.56
5	60	3.20

Optic Flood
05.8032.40
05.8032.14



Luminous flux luminaire
572 lm


Beam Angle: 35°


h(m)	E(lx)	D(m)
1	1679	0.64
2	420	1.28
3	187	1.92
4	105	2.56
5	67	3.20

Eclectic Ø70 - Adjustable Soft

LED Array DC 600 mA - 7,5W - 686 lm - 2700K/CRI 90 / 7,5W - 768 lm - 3000K/CRI 90







Eclectic Ø70. Adjustable Downlight (35º tilt, 360º rotation). "Soft" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 47º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø70. Downlight orientable (basculación 35º, giro 360º). Frontal de estética tipo «soft». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 47º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Recommended power supply / Equipos recomendados*:

Non Dimmable 32W	60.9592
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0600
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 40W	60.9845
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8023.40
05.8023.14






Luminous flux luminaire
408 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5593	0.27
2	1398	0.53
3	621	0.80
4	350	1.06
5	224	1.33

3000K
Optic Spot
05.8033.40
05.8033.14






Luminous flux luminaire
457 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6263	0.27
2	1566	0.53
3	696	0.80
4	391	1.06
5	251	1.33

Optic Medium
05.8024.40
05.8024.14






Luminous flux luminaire
497 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	3673	0.36
2	918	0.72
3	408	1.08
4	230	1.44
5	147	1.80

Optic Medium
05.8034.40
05.8034.14






Luminous flux luminaire
557 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	4113	0.36
2	1028	0.72
3	457	1.08
4	257	1.44
5	165	1.80

Optic Flood
05.8025.40
05.8025.14






Luminous flux luminaire
511 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	1484	0.64
2	371	1.28
3	165	1.92
4	93	2.56
5	59	3.20

Optic Flood
05.8035.40
05.8035.14





Luminous flux luminaire
572 lm


Beam Angle: 35°


h(m)	E(lx)	D(m)
1	1662	0.64
2	415	1.28
3	185	1.92
4	104	2.56
5	66	3.20

Eclectic Ø70 - Adjustable Flat

LED Array DC 600 mA - 7,5W - 686 lm - 2700K/CRI 90 / 7,5W - 768 lm - 3000K/CRI 90







Eclectic Ø70. Adjustable Downlight (35º tilt, 360º rotation). "Flat" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 55º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø70. Downlight orientable (basculación 35º, giro 360º). Frontal de estética tipo «flat». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 55º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

Non Dimmable 32W	60.9592
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0600
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 40W	60.9845
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8026.40
05.8026.14




Luminous flux luminaire
395 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5775	0.26
2	1444	0.52
3	642	0.77
4	361	1.03
5	231	1.29

3000K
Optic Spot
05.8036.40
05.8036.14




Luminous flux luminaire
444 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	6496	0.26
2	1624	0.52
3	722	0.77
4	406	1.03
5	260	1.29

Optic Medium
05.8027.40
05.8027.14




Luminous flux luminaire
448 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	3841	0.34
2	960	0.68
3	427	1.02
4	240	1.35
5	154	1.69

Optic Medium
05.8037.40
05.8037.14




Luminous flux luminaire
501 lm

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4298	0.34
2	1075	0.68
3	478	1.02
4	269	1.35
5	172	1.69

Optic Flood
05.8028.40
05.8028.14




Luminous flux luminaire
501 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	1490	0.63
2	372	1.27
3	166	1.90
4	93	2.54
5	60	3.17

Optic Flood
05.8038.40
05.8038.14




Luminous flux luminaire
560 lm


Beam Angle: 35°

h(m)	E(lx)	D(m)
1	1668	0.63
2	417	1.27
3	185	1.90
4	104	2.54
5	67	3.17

HOW TO ORDER ECLECTIC Ø70





ACCESSORIES & SPARE PARTS ECLECTIC Ø70



Light Engine Module not Sold as Spare Part. Special Orders Please Consult.

Accessories Ø70 / Accesorios Ø70

Trim Frame. For further and full installation measures & requirements, please consult mounting instructions.	Marco de Instalación Trim. Para conocer los requisitos y medidas de instalación al completo, por favor, consulte las instrucciones de montaje.			08.0670.40 08.0670.14
No Trim Frame. For further and full installation measures & requirements, please consult mounting instructions.	Marco de Instalación No Trim. Para conocer los requisitos y medidas de instalación al completo, por favor, consulte las instrucciones de montaje.			08.0672.00
Honeycomb	Panel de abeja			08.0727.00
Adjustable IP 54	IP 54 Ajustable			08.0729.00
Dichroic CCT Filter	Filtros Dicroicos CCT			Increase 2700K >> 3125±75K 3000K >> 3600±75K 08.0731.00 Decrease 2700K >> 2450±75K 3000K >> 2700±75K 08.0732.00

Spare parts Ø70 / Repuestos Ø70

Lenses	Lentes		Opic Spot 08.0711.00 Opic Medium 08.0712.00 Opic Flood 08.0713.00
Orientation Module	Módulo de Orientabilidad		Fixed 08.0739.00 Adjustable 08.0740.00
Style Modules	Módulos Estéticos		Cone 08.0721.40 08.0721.14 Soft 08.0722.40 08.0722.14 Flat 08.0723.40 08.0723.14

Drivers for Serial Connection / Equipos para Conexión en Serie


Driver	DIM Protocol	Min-Max Eclectic(s) per Driver.
60.9592	Non Dimmable 32W	1 - 3
60.7677	Non Dimmable 42W	1 - 3
60.7678	Dimmable Dali 2 38W	1 - 4
60.9713.0600	Dimmable Dali 2 20W	1 - 2
60.9208	Dimmable 0-10V 20W	1 - 2
60.9845	Dimmable 0-10V 40W	1 - 3
60.9467	Mains Dimming 20W	1 - 2
60.7785	Casambi 26W	1 - 3

* Refer to the Drivers chapter / Ver capítulo Drivers

Eclectic Ø90 - Fixed Cone

LED Array DC 300 mA - 10,5W - 1114 lm - 2700K/CRI 90 / 10,5W - 1162 lm - 3000K/CRI 90





Eclectic Ø90. Non-adjustable Downlight. "Cone" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41° cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight no orientable. Frontal de estética tipo «cone». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41°. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

Non Dimmable 22W	60.9160
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0300
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 20W	60.9843
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8100.40
05.8100.14




Luminous flux luminaire 862 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	10411	0.27
2	2603	0.54
3	1157	0.81
4	651	1.08
5	416	1.36

3000K
Optic Spot
05.8120.40
05.8120.14




Luminous flux luminaire 899 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	10855	0.27
2	2714	0.54
3	1206	0.81
4	678	1.08
5	434	1.36

Optic Medium
05.8101.40
05.8101.14




Luminous flux luminaire 923 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	5703	0.43
2	1426	0.87
3	634	1.30
4	356	1.73
5	228	2.17

Optic Medium
05.8121.40
05.8121.14




Luminous flux luminaire 963 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	5946	0.43
2	1486	0.87
3	661	1.30
4	372	1.73
5	238	2.17

Optic Flood
05.8102.40
05.8102.14




Luminous flux luminaire 925 lm

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	3300	0.59
2	825	1.18
3	367	1.78
4	206	2.37
5	132	2.96

Optic Flood
05.8122.40
05.8122.14




Luminous flux luminaire 964 lm

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	3441	0.59
2	860	1.18
3	382	1.78
4	215	2.37
5	138	2.96

Optic Wide Flood
05.8103.40
05.8103.14




Luminous flux luminaire 861 lm

Beam Angle: 42°

h(m)	E(lx)	D(m)
1	1921	0.77
2	480	1.54
3	213	2.31
4	120	3.08
5	77	3.85

Optic Wide Flood
05.8123.40
05.8123.14



Luminous flux luminaire 898 lm


Beam Angle: 42°

h(m)	E(lx)	D(m)
1	2003	0.77
2	501	1.54
3	223	2.31
4	125	3.08
5	80	3.85

Eclectic Ø90 - Fixed Cone

Power LED DC 600 mA - 7W - 534 lm - 2700K/CRI 90 / 7W - 572 lm - 3000K/CRI 90





Eclectic Ø90. Non-adjustable Downlight. "Cone" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP54 water tightness. Power LED light source*. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight no orientable. Frontal de estética tipo «cone». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP54. Fuente de luz, Power LED*. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

		Serial Con.
Non Dimmable 32W	60.9592	1 - 3
Non Dimmable 42W	60.7677	1 - 3
Dimmable Dali 2 38W	60.7678	1 - 4
Dimmable Dali 2 20W	60.9713.0600	1 - 2
Dimmable 0-10V 20W	60.9208	1 - 2
Dimmable 0-10V 40W	60.9845	1 - 3
Mains Dimming 20W	60.9467	1 - 2
Casambi 26W	60.7785	1 - 3

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Super Spot
05.8200.40
05.8200.14




Beam Angle: 7°

h(m)	E(lx)	D(m)
1	23070	0.12
2	5768	0.23
3	2563	0.35
4	1442	0.46
5	923	0.58

Luminous flux luminaire 399 lm

3000K
Optic Super Spot
05.8210.40
05.8210.14




Beam Angle: 7°

h(m)	E(lx)	D(m)
1	24717	0.12
2	6179	0.23
3	2746	0.35
4	1545	0.46
5	989	0.58

Luminous flux luminaire 428 lm

Optic Spot
05.8201.40
05.8201.14




Beam Angle: 10°

h(m)	E(lx)	D(m)
1	10468	0.17
2	2617	0.34
3	1163	0.50
4	654	0.67
5	419	0.84

Luminous flux luminaire 386 lm

Optic Spot
05.8211.40
05.8211.14




Beam Angle: 10°

h(m)	E(lx)	D(m)
1	11204	0.17
2	2801	0.34
3	1245	0.50
4	700	0.67
5	448	0.84

Luminous flux luminaire 413 lm

Optic Medium
05.8202.40
05.8202.14




Beam Angle: 22°

h(m)	E(lx)	D(m)
1	2044	0.38
2	511	0.76
3	227	1.14
4	128	1.52
5	82	1.90

Luminous flux luminaire 313 lm

Optic Medium
05.8212.40
05.8212.14



Beam Angle: 22°

h(m)	E(lx)	D(m)
1	2191	0.38
2	548	0.76
3	243	1.14
4	137	1.52
5	88	1.90

Luminous flux luminaire 335 lm


* The combination of models using Power LED and Array LED light sources can lead to slight differences in the chromaticity of the light. It is recommended to use the same light source in shared spaces.

* La combinación de modelos con fuente de luz Power LED y LED Array puede acarrear pequeñas diferencias de cromaticidad en la luz. Se recomienda emplear la misma fuente de luz en espacios compartidos.

Eclectic Ø90 - Fixed Soft

LED Array DC 300 mA - 10,5W - 1114 lm - 2700K/CRI 90 / 10,5W - 1162 lm - 3000K/CRI 90





Eclectic Ø90. Non-adjustable Downlight. "Soft" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight no orientable. Frontal de estética tipo «soft». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

Non Dimmable 22W	60.9160
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0300
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 20W	60.9843
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8105.40
05.8105.14




Luminous flux luminaire 860 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	10404	0.27
2	2601	0.54
3	1156	0.81
4	650	1.09
5	416	1.36

3000K
Optic Spot
05.8125.40
05.8125.14




Luminous flux luminaire 896 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	10846	0.27
2	2712	0.54
3	1205	0.81
4	678	1.09
5	434	1.36

Optic Medium
05.8106.40
05.8106.14




Luminous flux luminaire 922 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	5713	0.43
2	1428	0.87
3	635	1.30
4	357	1.73
5	229	2.16

Optic Medium
05.8126.40
05.8126.14




Luminous flux luminaire 961 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	5956	0.43
2	1489	0.87
3	662	1.30
4	372	1.73
5	238	2.16

Optic Flood
05.8107.40
05.8107.14




Luminous flux luminaire 925 lm

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	3276	0.59
2	819	1.19
3	364	1.78
4	205	2.38
5	131	2.97

Optic Flood
05.8127.40
05.8127.14




Luminous flux luminaire 964 lm

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	3416	0.59
2	854	1.19
3	380	1.78
4	213	2.38
5	137	2.97

Optic Wide Flood
05.8108.40
05.8108.14




Luminous flux luminaire 862 lm

Beam Angle: 42°

h(m)	E(lx)	D(m)
1	1939	0.77
2	485	1.53
3	215	2.30
4	121	3.06
5	78	3.83

Optic Wide Flood
05.8128.40
05.8128.14



Luminous flux luminaire 899 lm


Beam Angle: 42°

h(m)	E(lx)	D(m)
1	2021	0.77
2	505	1.53
3	225	2.30
4	126	3.06
5	81	3.83

Eclectic Ø90 - Fixed Soft

Power LED DC 600 mA - 7W - 534 lm - 2700K/CRI 90 / 7W - 572 lm - 3000K/CRI 90





Eclectic Ø90. Non-adjustable Downlight. "Soft" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP54 water tightness. Power LED light source*. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight no orientable. Frontal de estética tipo «soft». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP54. Fuente de luz, Power LED*. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

		Serial Con.
Non Dimmable 32W	60.9592	1 - 3
Non Dimmable 42W	60.7677	1 - 3
Dimmable Dali 2 38W	60.7678	1 - 4
Dimmable Dali 2 20W	60.9713.0600	1 - 2
Dimmable 0-10V 20W	60.9208	1 - 2
Dimmable 0-10V 40W	60.9845	1 - 3
Mains Dimming 20W	60.9467	1 - 2
Casambi 26W	60.7785	1 - 3

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Super Spot
05.8203.40
05.8203.14




Luminous flux luminaire 404 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	22903	0.12
2	5726	0.23
3	2545	0.35
4	1431	0.47
5	916	0.58

3000K
Optic Super Spot
05.8213.40
05.8213.14




Luminous flux luminaire 433 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	24526	0.12
2	6132	0.23
3	2725	0.35
4	1533	0.47
5	981	0.58

Optic Spot
05.8204.40
05.8204.14




Luminous flux luminaire 386 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	10462	0.17
2	2615	0.34
3	1162	0.50
4	654	0.67
5	418	0.84

Optic Spot
05.8214.40
05.8214.14




Luminous flux luminaire 413 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	11199	0.17
2	2800	0.34
3	1244	0.50
4	700	0.67
5	448	0.84

Optic Medium
05.8205.40
05.8205.14




Luminous flux luminaire 311 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	2058	0.38
2	514	0.75
3	229	1.13
4	129	1.51
5	82	1.89

Optic Medium
05.8215.40
05.8215.14



Luminous flux luminaire 333 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	2203	0.38
2	551	0.75
3	245	1.13
4	138	1.51
5	88	1.89


* The combination of models using Power LED and Array LED light sources can lead to slight differences in the chromaticity of the light. It is recommended to use the same light source in shared spaces.


* La combinación de modelos con fuente de luz Power LED y LED Array puede acarrear pequeñas diferencias de cromaticidad en la luz. Se recomienda emplear la misma fuente de luz en espacios compartidos.

Eclectic Ø90 - Fixed Flat

LED Array DC 300 mA - 10,5W - 1114 lm - 2700K/CRI 90 / 10,5W - 1162 lm - 3000K/CRI 90







Eclectic Ø90. Non-adjustable Downlight. “Flat” style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 49º cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90. Downlight no orientable. Frontal de estética tipo «flat». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 49º. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Recommended power supply / Equipos recomendados*:

Non Dimmable 22W	60.9160
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0300
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 20W	60.9843
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8110.40
05.8110.14






Luminous flux luminaire
860 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	10845	0.27
2	2711	0.53
3	1205	0.80
4	678	1.07
5	434	1.34

Optic Medium
05.8111.40
05.8111.14






Luminous flux luminaire
903 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5573	0.44
2	1393	0.88
3	619	1.32
4	348	1.76
5	223	2.20

Optic Flood
05.8112.40
05.8112.14






Luminous flux luminaire
901 lm

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	3292	0.59
2	823	1.18
3	366	1.77
4	206	2.36
5	132	2.95

Optic Wide Flood
05.8113.40
05.8113.14






Luminous flux luminaire
809 lm

Beam Angle: 42°

h(m)	E(lx)	D(m)
1	1862	0.76
2	466	1.52
3	207	2.28
4	116	3.04
5	74	3.81

3000K
Optic Spot
05.8130.40
05.8130.14






Luminous flux luminaire
897 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	11306	0.27
2	2827	0.53
3	1256	0.80
4	707	1.07
5	452	1.34

Optic Medium
05.8131.40
05.8131.14






Luminous flux luminaire
942 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5810	0.44
2	1453	0.88
3	646	1.32
4	363	1.76
5	232	2.20

Optic Flood
05.8132.40
05.8132.14






Luminous flux luminaire
939 lm

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	3432	0.59
2	858	1.18
3	381	1.77
4	215	2.36
5	137	2.95

Optic Wide Flood
05.8133.40
05.8133.14





Luminous flux luminaire
844 lm


Beam Angle: 42°

h(m)	E(lx)	D(m)
1	1942	0.76
2	485	1.52
3	216	2.28
4	121	3.04
5	78	3.81

Eclectic Ø90 - Fixed Flat

Power LED DC 600 mA - 7W - 534 lm - 2700K/CRI 90 / 7W - 572 lm - 3000K/CRI 90





Eclectic Ø90. Non-adjustable Downlight. “Flat” style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 49º cut-off angle. IP54 water tightness. Power LED light source*. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight no orientable. Frontal de estética tipo «flat». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 49º. Estanqueidad IP54. Fuente de luz, Power LED*. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

		Serial Con.
Non Dimmable 32W	60.9592	1 - 3
Non Dimmable 42W	60.7677	1 - 3
Dimmable Dali 2 38W	60.7678	1 - 4
Dimmable Dali 2 20W	60.9713.0600	1 - 2
Dimmable 0-10V 20W	60.9208	1 - 2
Dimmable 0-10V 40W	60.9845	1 - 3
Mains Dimming 20W	60.9467	1 - 2
Casambi 26W	60.7785	1 - 3

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Super Spot
05.8206.40
05.8206.14




Luminous flux luminaire 418 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	24420	0.12
2	6105	0.23
3	2713	0.35
4	1526	0.46
5	977	0.58

3000K
Optic Super Spot
05.8216.40
05.8216.14




Luminous flux luminaire 447 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	26136	0.12
2	6534	0.23
3	2904	0.35
4	1634	0.46
5	1045	0.58

Optic Spot
05.8207.40
05.8207.14




Luminous flux luminaire 396 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	11017	0.17
2	2754	0.34
3	1224	0.50
4	689	0.67
5	441	0.84

Optic Spot
05.8217.40
05.8217.14




Luminous flux luminaire 424 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	11789	0.17
2	2947	0.34
3	1310	0.50
4	737	0.67
5	472	0.84

Optic Medium
05.8208.40
05.8208.14




Luminous flux luminaire 320 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	2143	0.37
2	536	0.73
3	238	1.10
4	134	1.46
5	86	1.83

Optic Medium
05.8218.40
05.8218.14



Luminous flux luminaire 343 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	2295	0.37
2	574	0.73
3	255	1.10
4	143	1.46
5	92	1.83


* The combination of models using Power LED and Array LED light sources can lead to slight differences in the chromaticity of the light. It is recommended to use the same light source in shared spaces.


* La combinación de modelos con fuente de luz Power LED y LED Array puede acarrear pequeñas diferencias de cromaticidad en la luz. Se recomienda emplear la misma fuente de luz en espacios compartidos.

Eclectic Ø90 - Adjustable Cone

LED Array DC 300 mA - 10,5W - 1114 lm - 2700K/CRI 90 / 10,5W - 1162 lm - 3000K/CRI 90







Eclectic Ø90. Adjustable Downlight (40º tilt, 360º rotation). "Cone" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «cone». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Recommended power supply / Equipos recomendados*:

Non Dimmable 22W	60.9160
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0300
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 20W	60.9843
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
☐ 05.8140.40
■ 05.8140.14






Luminous flux luminaire
884 lm

Beam Angle: 16°

h(m)	E(lx)	D(m)
1	10458	0.28
2	2614	0.56
3	1162	0.84
4	654	1.12
5	418	1.39

Optic Medium
☐ 05.8141.40
■ 05.8141.14






Luminous flux luminaire
898 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5405	0.44
2	1351	0.88
3	601	1.32
4	338	1.76
5	216	2.21

Optic Flood
☐ 05.8142.40
■ 05.8142.14






Luminous flux luminaire
906 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3054	0.61
2	764	1.22
3	339	1.82
4	191	2.43
5	122	3.04

Optic Wide Flood
☐ 05.8143.40
■ 05.8143.14






Luminous flux luminaire
836 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	1827	0.79
2	457	1.58
3	203	2.37
4	114	3.16
5	73	3.95

3000K
Optic Spot
☐ 05.8160.40
■ 05.8160.14






Luminous flux luminaire
922 lm

Beam Angle: 16°

h(m)	E(lx)	D(m)
1	10903	0.28
2	2726	0.56
3	1211	0.84
4	681	1.12
5	436	1.39

Optic Medium
☐ 05.8161.40
■ 05.8161.14






Luminous flux luminaire
937 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5635	0.44
2	1409	0.88
3	626	1.32
4	352	1.76
5	225	2.21

Optic Flood
☐ 05.8162.40
■ 05.8162.14






Luminous flux luminaire
945 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3184	0.61
2	796	1.22
3	354	1.82
4	199	2.43
5	127	3.04

Optic Wide Flood
☐ 05.8163.40
■ 05.8163.14





Luminous flux luminaire
872 lm


Beam Angle: 43°


h(m)	E(lx)	D(m)
1	1905	0.79
2	476	1.58
3	212	2.37
4	119	3.16
5	76	3.95

Eclectic Ø90 - Adjustable Cone

Power LED DC 600 mA - 7W - 534 lm - 2700K/CRI 90 / 7W - 572 lm - 3000K/CRI 90







Eclectic Ø90. Adjustable Downlight (40º tilt, 360º rotation). "Cone" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Power LED light source*. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «cone». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Fuente de luz, Power LED*. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

		Serial Con.
Non Dimmable 32W	60.9592	1 - 3
Non Dimmable 42W	60.7677	1 - 3
Dimmable Dali 2 38W	60.7678	1 - 4
Dimmable Dali 2 20W	60.9713.0600	1 - 2
Dimmable 0-10V 20W	60.9208	1 - 2
Dimmable 0-10V 40W	60.9845	1 - 3
Mains Dimming 20W	60.9467	1 - 2
Casambi 26W	60.7785	1 - 3

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Super Spot
05.8220.40
05.8220.14




Luminous flux luminaire 393 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	21700	0.12
2	5425	0.24
3	2411	0.35
4	1356	0.47
5	868	0.59

3000K
Optic Super Spot
05.8230.40
05.8230.14




Luminous flux luminaire 421 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	23232	0.12
2	5808	0.24
3	2581	0.35
4	1452	0.47
5	929	0.59

Optic Spot
05.8221.40
05.8221.14




Luminous flux luminaire 380 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	10047	0.17
2	2512	0.34
3	1116	0.51
4	628	0.68
5	402	0.85

Optic Spot
05.8231.40
05.8231.14




Luminous flux luminaire 407 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	10769	0.17
2	2692	0.34
3	1197	0.51
4	673	0.68
5	431	0.85

Optic Medium
05.8222.40
05.8222.14




Luminous flux luminaire 309 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1982	0.38
2	495	0.77
3	220	1.15
4	124	1.54
5	79	1.92

Optic Medium
05.8232.40
05.8232.14



Luminous flux luminaire 331 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	2122	0.38
2	530	0.77
3	236	1.15
4	133	1.54
5	85	1.92


* The combination of models using Power LED and Array LED light sources can lead to slight differences in the chromaticity of the light. It is recommended to use the same light source in shared spaces.


* La combinación de modelos con fuente de luz Power LED y LED Array puede acarrear pequeñas diferencias de cromaticidad en la luz. Se recomienda emplear la misma fuente de luz en espacios compartidos.

Eclectic Ø90 - Adjustable Soft

LED Array DC 300 mA - 10,5W - 1114 lm - 2700K/CRI 90 / 10,5W - 1162 lm - 3000K/CRI 90







Eclectic Ø90. Adjustable Downlight (40º tilt, 360º rotation). "Soft" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «soft». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Recommended power supply / Equipos recomendados*:

Non Dimmable 22W	60.9160
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0300
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 20W	60.9843
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8145.40
05.8145.14






Luminous flux luminaire
868 lm

Beam Angle: 16°

h(m)	E(lx)	D(m)
1	10723	0.27
2	2681	0.55
3	1191	0.82
4	670	1.09
5	429	1.36

Optic Medium
05.8146.40
05.8146.14






Luminous flux luminaire
900 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5346	0.45
2	1337	0.89
3	594	1.34
4	334	1.78
5	214	2.23

Optic Flood
05.8147.40
05.8147.14






Luminous flux luminaire
904 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3109	0.60
2	777	1.21
3	345	1.81
4	194	2.41
5	124	3.01

Optic Wide Flood
05.8148.40
05.8148.14






Luminous flux luminaire
837 lm

Beam Angle: 43°

h(m)	E(lx)	D(m)
1	1825	0.79
2	456	1.59
3	203	2.38
4	114	3.17
5	73	3.97

3000K
Optic Spot
05.8165.40
05.8165.14






Luminous flux luminaire
905 lm

Beam Angle: 16°

h(m)	E(lx)	D(m)
1	11180	0.27
2	2795	0.55
3	1242	0.82
4	699	1.09
5	447	1.36

Optic Medium
05.8166.40
05.8166.14






Luminous flux luminaire
938 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5574	0.45
2	1393	0.89
3	619	1.34
4	348	1.78
5	223	2.23

Optic Flood
05.8167.40
05.8167.14






Luminous flux luminaire
942 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3241	0.60
2	810	1.21
3	360	1.81
4	203	2.41
5	130	3.01

Optic Wide Flood
05.8168.40
05.8168.14





Luminous flux luminaire
873 lm


Beam Angle: 43°


h(m)	E(lx)	D(m)
1	1902	0.79
2	476	1.59
3	211	2.38
4	119	3.17
5	76	3.97

Eclectic Ø90 - Adjustable Soft

Power LED DC 600 mA - 7W - 534 lm - 2700K/CRI 90 / 7W - 572 lm - 3000K/CRI 90







Eclectic Ø90. Adjustable Downlight (40º tilt, 360º rotation). "Soft" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Power LED light source*. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «soft». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Fuente de luz, Power LED*. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

		Serial Con.
Non Dimmable 32W	60.9592	1 - 3
Non Dimmable 42W	60.7677	1 - 3
Dimmable Dali 2 38W	60.7678	1 - 4
Dimmable Dali 2 20W	60.9713.0600	1 - 2
Dimmable 0-10V 20W	60.9208	1 - 2
Dimmable 0-10V 40W	60.9845	1 - 3
Mains Dimming 20W	60.9467	1 - 2
Casambi 26W	60.7785	1 - 3

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Super Spot
05.8223.40
05.8223.14




Luminous flux luminaire 400 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	22497	0.12
2	5624	0.23
3	2500	0.35
4	1406	0.47
5	900	0.59

3000K
Optic Super Spot
05.8233.40
05.8233.14




Luminous flux luminaire 429 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	24105	0.12
2	6026	0.23
3	2678	0.35
4	1507	0.47
5	964	0.59

Optic Spot
05.8224.40
05.8224.14




Luminous flux luminaire 373 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	9599	0.17
2	2400	0.35
3	1067	0.52
4	600	0.70
5	384	0.87

Optic Spot
05.8234.40
05.8234.14




Luminous flux luminaire 400 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	10292	0.17
2	2573	0.35
3	1144	0.52
4	643	0.70
5	412	0.87

Optic Medium
05.8225.40
05.8225.14




Luminous flux luminaire 307 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1984	0.38
2	496	0.77
3	220	1.15
4	124	1.54
5	79	1.92

Optic Medium
05.8235.40
05.8235.14



Luminous flux luminaire 329 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	2128	0.38
2	532	0.77
3	236	1.15
4	133	1.54
5	85	1.92


* The combination of models using Power LED and Array LED light sources can lead to slight differences in the chromaticity of the light. It is recommended to use the same light source in shared spaces.


* La combinación de modelos con fuente de luz Power LED y LED Array puede acarrear pequeñas diferencias de cromaticidad en la luz. Se recomienda emplear la misma fuente de luz en espacios compartidos.

Eclectic Ø90 - Adjustable Flat

LED Array DC 300 mA - 10,5W - 1114 lm - 2700K/CRI 90 / 10,5W - 1162 lm - 3000K/CRI 90







Eclectic Ø90. Adjustable Downlight (40° tilt, 360° rotation). "Flat" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 49° cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «flat». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 49º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

Non Dimmable 22W	60.9160
Non Dimmable 42W	60.7677
Dimmable Dali 2 38W	60.7678
Dimmable Dali 2 20W	60.9713.0300
Dimmable 0-10V 20W	60.9208
Dimmable 0-10V 20W	60.9843
Mains Dimming 20W	60.9467
Casambi 26W	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Spot
05.8150.40
05.8150.14




Luminous flux luminaire 852 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	11105	0.27
2	2776	0.53
3	1234	0.80
4	694	1.06
5	444	1.33

3000K
Optic Spot
05.8170.40
05.8170.14




Luminous flux luminaire 889 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	11578	0.27
2	2894	0.53
3	1286	0.80
4	724	1.06
5	463	1.33

Optic Medium
05.8151.40
05.8151.14




Luminous flux luminaire 874 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5410	0.44
2	1352	0.88
3	601	1.32
4	338	1.76
5	216	2.20

Optic Medium
05.8171.40
05.8171.14




Luminous flux luminaire 912 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	5641	0.44
2	1410	0.88
3	627	1.32
4	353	1.76
5	226	2.20

Optic Flood
05.8152.40
05.8152.14




Luminous flux luminaire 885 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3061	0.60
2	765	1.21
3	340	1.81
4	191	2.41
5	122	3.02

Optic Flood
05.8172.40
05.8172.14




Luminous flux luminaire 923 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3191	0.60
2	798	1.21
3	355	1.81
4	199	2.41
5	128	3.02

Optic Wide Flood
05.8153.40
05.8153.14




Luminous flux luminaire 782 lm

Beam Angle: 41°

h(m)	E(lx)	D(m)
1	1810	0.75
2	452	1.51
3	201	2.26
4	113	3.01
5	72	3.76

Optic Wide Flood
05.8173.40
05.8173.14



Luminous flux luminaire 815 lm


Beam Angle: 41°


h(m)	E(lx)	D(m)
1	1887	0.75
2	472	1.51
3	210	2.26
4	118	3.01
5	75	3.76

Eclectic Ø90 - Adjustable Flat

Power LED DC 600 mA - 7W - 534 lm - 2700K/CRI 90 / 7W - 572 lm - 3000K/CRI 90







Eclectic Ø90. Adjustable Downlight (40º tilt, 360º rotation). "Flat" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 49º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Power LED light source*. Alternative options for lenses, orientation modules and style façades are available as spare parts.


Eclectic Ø90. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «flat». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 49º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Fuente de luz, Power LED*. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Recommended power supply / Equipos recomendados*:

		Serial Con.
Non Dimmable 32W	60.9592	1 - 3
Non Dimmable 42W	60.7677	1 - 3
Dimmable Dali 2 38W	60.7678	1 - 4
Dimmable Dali 2 20W	60.9713.0600	1 - 2
Dimmable 0-10V 20W	60.9208	1 - 2
Dimmable 0-10V 40W	60.9845	1 - 3
Mains Dimming 20W	60.9467	1 - 2
Casambi 26W	60.7785	1 - 3

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
Optic Super Spot
05.8226.40
05.8226.14




Luminous flux luminaire 416 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	24004	0.12
2	6001	0.23
3	2667	0.35
4	1500	0.47
5	960	0.58

3000K
Optic Super Spot
05.8236.40
05.8236.14




Luminous flux luminaire 445 lm

Beam Angle: 7°

h(m)	E(lx)	D(m)
1	25708	0.12
2	6427	0.23
3	2856	0.35
4	1607	0.47
5	1028	0.58

Optic Spot
05.8227.40
05.8227.14




Luminous flux luminaire 411 lm

Beam Angle: 9°

h(m)	E(lx)	D(m)
1	9600	0.16
2	2400	0.33
3	1067	0.49
4	600	0.65
5	384	0.81

Optic Spot
05.8237.40
05.8237.14




Luminous flux luminaire 440 lm

Beam Angle: 9°

h(m)	E(lx)	D(m)
1	10289	0.16
2	2572	0.33
3	1143	0.49
4	643	0.65
5	412	0.81

Optic Medium
05.8228.40
05.8228.14




Luminous flux luminaire 300 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	2128	0.36
2	532	0.73
3	236	1.09
4	133	1.46
5	85	1.82

Optic Medium
05.8238.40
05.8238.14



Luminous flux luminaire 322 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	2282	0.36
2	570	0.73
3	254	1.09
4	143	1.46
5	91	1.82


* The combination of models using Power LED and Array LED light sources can lead to slight differences in the chromaticity of the light. It is recommended to use the same light source in shared spaces.


* La combinación de modelos con fuente de luz Power LED y LED Array puede acarrear pequeñas diferencias de cromaticidad en la luz. Se recomienda emplear la misma fuente de luz en espacios compartidos.

Eclectic Ø90 Dim To Warm. Fixed Cone

LED Array DC 300 mA - 13W - 1026 lm - 1800-3000K/CRI 90







Eclectic Ø90 Dim To Warm. Non-adjustable Downlight. “Cone” style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90 Dim To Warm. Downlight no orientable. Frontal de estética tipo «cone». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Optic Medium


Dali 2
- 05.8301.40.DA
- 05.8301.14.DA

1-10V
- 05.8301.40.1V
- 05.8301.14.1V

Casambi
- 05.8301.40.CB
- 05.8301.14.CB

Mains Dimming
- 05.8301.40.NI
- 05.8301.14.NI





Luminous flux luminaire
850 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	5251	0.43
2	1313	0.87
3	583	1.30
4	328	1.73
5	210	2.17

Optic Flood


Dali 2
- 05.8302.40.DA
- 05.8302.14.DA

1-10V
- 05.8302.40.1V
- 05.8302.14.1V

Casambi
- 05.8302.40.CB
- 05.8302.14.CB

Mains Dimming
- 05.8302.40.NI
- 05.8302.14.NI





Luminous flux luminaire
852 lm


Beam Angle: 33°


h(m)	E(lx)	D(m)
1	3040	0.59
2	760	1.18
3	338	1.78
4	190	2.37
5	122	2.96

Eclectic Ø90 Dim To Warm. Fixed Soft

LED Array DC 300 mA - 13W - 1026 lm - 1800-3000K/CRI 90







Eclectic Ø90 Dim To Warm. Non-adjustable Downlight. “Soft” style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90 Dim To Warm. Downlight no orientable. Frontal de estética tipo «soft». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Optic Medium


Dali 2
- 05.8306.40.DA
- 05.8306.14.DA

1-10V
- 05.8306.40.1V
- 05.8306.14.1V

Casambi
- 05.8306.40.CB
- 05.8306.14.CB

Mains Dimming
- 05.8306.40.NI
- 05.8306.14.NI





Luminous flux luminaire
849 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	5262	0.43
2	1316	0.87
3	585	1.30
4	329	1.73
5	210	2.16

Optic Flood


Dali 2
- 05.8307.40.DA
- 05.8307.14.DA

1-10V
- 05.8307.40.1V
- 05.8307.14.1V

Casambi
- 05.8307.40.CB
- 05.8307.14.CB

Mains Dimming
- 05.8307.40.NI
- 05.8307.14.NI





Luminous flux luminaire
851 lm


Beam Angle: 33°


h(m)	E(lx)	D(m)
1	3014	0.59
2	754	1.19
3	335	1.78
4	188	2.38
5	121	2.97

Eclectic Ø90 Dim To Warm. Fixed Flat

LED Array DC 300 mA - 13W - 1026 lm - 1800-3000K/CRI 90







Eclectic Ø90 Dim To Warm. Non-adjustable Downlight. “Flat” style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 49º cut-off angle. IP54 water tightness. Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90 Dim To Warm. Downlight no orientable. Frontal de estética tipo «flat». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 49º. Estanqueidad IP54. Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.

Optic Medium


Dali 2
- 05.8311.40.DA
- 05.8311.14.DA

1-10V
- 05.8311.40.1V
- 05.8311.14.1V

Casambi
- 05.8311.40.CB
- 05.8311.14.CB

Mains Dimming
- 05.8311.40.NI
- 05.8311.14.NI





Luminous flux luminaire
831 lm

Beam Angle:		25°
h(m)	E(lx)	D(m)
1	5128	0.44
2	1282	0.88
3	570	1.32
4	321	1.76
5	205	2.20

Optic Flood


Dali 2
- 05.8312.40.DA
- 05.8312.14.DA

1-10V
- 05.8312.40.1V
- 05.8312.14.1V

Casambi
- 05.8312.40.CB
- 05.8312.14.CB

Mains Dimming
- 05.8312.40.NI
- 05.8312.14.NI






Luminous flux luminaire
829 lm

Beam Angle:		33°
h(m)	E(lx)	D(m)
1	3031	0.59
2	758	1.18
3	337	1.77
4	189	2.36
5	121	2.95


ECLECTIC DIM TO WARM. HOW IT WORKS?




Eclectic Ø90 Dim To Warm. Adjustable Cone

LED Array DC 300 mA - 13W - 1026 lm - 1800-3000K/CRI 90







Eclectic Ø90 Dim To Warm. Adjustable Downlight (40º tilt, 360º rotation). “Cone” style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90 Dim To Warm. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «cone». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Optic Medium

Dali 2
- 05.8341.40.DA
- 05.8341.14.DA

1-10V
- 05.8341.40.1V
- 05.8341.14.1V

Casambi
- 05.8341.40.CB
- 05.8341.14.CB

Mains Dimming
- 05.8341.40.NI
- 05.8341.14.NI



Luminous flux luminaire
827 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	4976	0.44
2	1244	0.88
3	553	1.32
4	311	1.76
5	199	2.21


Optic Flood

Dali 2
- 05.8342.40.DA
- 05.8342.14.DA

1-10V
- 05.8342.40.1V
- 05.8342.14.1V

Casambi
- 05.8342.40.CB
- 05.8342.14.CB

Mains Dimming
- 05.8342.40.NI
- 05.8342.14.NI



Luminous flux luminaire
834 lm


Beam Angle: 34°


h(m)	E(lx)	D(m)
1	2811	0.61
2	703	1.22
3	312	1.82
4	176	2.43
5	112	3.04

Eclectic Ø90 Dim To Warm. Adjustable Soft

LED Array DC 300 mA - 13W - 1026 lm - 1800-3000K/CRI 90







Eclectic Ø90 Dim To Warm. Adjustable Downlight (40º tilt, 360º rotation). “Soft” style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 41º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90 Dim To Warm. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «soft». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 41º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Optic Medium

Dali 2
- 05.8346.40.DA
- 05.8346.14.DA

1-10V
- 05.8346.40.1V
- 05.8346.14.1V

Casambi
- 05.8346.40.CB
- 05.8346.14.CB

Mains Dimming
- 05.8346.40.NI
- 05.8346.14.NI



Luminous flux luminaire
828 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	4920	0.45
2	1230	0.89
3	547	1.34
4	308	1.78
5	197	2.23


Optic Flood

Dali 2
- 05.8347.40.DA
- 05.8347.14.DA

1-10V
- 05.8347.40.1V
- 05.8347.14.1V

Casambi
- 05.8347.40.CB
- 05.8347.14.CB

Mains Dimming
- 05.8347.40.NI
- 05.8347.14.NI



Luminous flux luminaire
832 lm


Beam Angle: 34°


h(m)	E(lx)	D(m)
1	2862	0.60
2	716	1.21
3	318	1.81
4	179	2.41
5	114	3.01

Eclectic Ø90 Dim To Warm. Adjustable Flat

LED Array DC 300 mA - 13W - 1026 lm - 1800-3000K/CRI 90







Eclectic Ø90 Dim To Warm. Adjustable Downlight (40º tilt, 360º rotation). "Flat" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 49º cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.

Eclectic Ø90 Dim To Warm. Downlight orientable (basculación 40º, giro 360º). Frontal de estética tipo «flat». Premarcos de instalación necesarios, no incluidos (pedir por separado). Posición del LED retranqueada: ángulo cut-off de 49º. Estanqueidad IP20 (para IP54, pedir accesorio dedicado). Opciones alternativas de lentes, módulos de orientabilidad y frontales estéticos están disponibles como repuestos / recambios.


Optic Medium

Dali 2
- 05.8351.40.DA
- 05.8351.14.DA

1-10V
- 05.8351.40.1V
- 05.8351.14.1V

Casambi
- 05.8351.40.CB
- 05.8351.14.CB

Mains Dimming
- 05.8351.40.NI
- 05.8351.14.NI



Luminous flux luminaire
805 lm

Beam Angle:		25°
h(m)	E(lx)	D(m)
1	4981	0.44
2	1245	0.88
3	553	1.32
4	311	1.76
5	199	2.20


Optic Flood

Dali 2
- 05.8352.40.DA
- 05.8352.14.DA

1-10V
- 05.8352.40.1V
- 05.8352.14.1V

Casambi
- 05.8352.40.CB
- 05.8352.14.CB


Mains Dimming
- 05.8352.40.NI
- 05.8352.14.NI




Luminous flux luminaire
815 lm

Beam Angle:		34°
h(m)	E(lx)	D(m)
1	2819	0.60
2	705	1.21
3	313	1.81
4	176	2.41
5	113	3.02

ECLECTIC DIM TO WARM. HOW IT WORKS?




HOW TO ORDER ECLECTIC Ø90



ACCESSORIES & SPARE PARTS ECLECTIC Ø90

LIGHT ENGINE MODULE
Not Sold as Spare Part



LED Array | Power LED | LED Array DIM To Warm*

LENS MODULE
Spare Part



Super Spot | Spot | Medium | Flood | Wide Flood

ACCESSORIES



Honeycomb | Dichroic filter CCT Increase | Dichroic filter CCT Decrease | IP 54 Accessory (Only for adjustable)


ORIENTATION MODULE
Spare Part



Fixed | Adjustable

MAGNETICALLY ATTACHED | MAGNETICALLY ATTACHED

STYLE MODULE
Spare Part



Cone | Soft | Flat


Light Engine Module not Sold as Spare Part. Special Orders Please Consult.
* In Dim to Warm models the driver is included. In the rest of the models, it is supplied separately.

Accessories Ø90 / Accesorios Ø90

Trim Frame.
For further and full installation measures & requirements, please consult mounting instructions.

Marco de Instalación Trim.
Para conocer los requisitos y medidas de instalación al completo, por favor, consulte las instrucciones de montaje.






08.0671.40
08.0671.14

No Trim Frame.
For further and full installation measures & requirements, please consult mounting instructions.

Marco de Instalación No Trim.
Para conocer los requisitos y medidas de instalación al completo, por favor, consulte las instrucciones de montaje.





08.0673.00

Honeycomb — Panel de abeja



08.0728.00

Adjustable IP 54 — IP 54 Ajustable

08.0730.00

Dichroic CCT Filter — Filtros Dicroicos CCT



Increase
2700K >> 3125±75K
3000K >> 3600±75K
08.0735.00

Decrease
2700K >> 2450±75K
3000K >> 2700±75K
08.0736.00

Spare parts Ø90 / Repuestos Ø90

Lenses — Lentes



LED Array
Opic Spot
08.0714.00
Opic Medium
08.0715.00
Opic Flood
08.0716.00
Opic Wide Flood
08.0717.00

LED Array DIM To Warm
Opic Medium
08.0715.00
Opic Flood
08.0716.00

Power LED
Opic Super Spot
08.0718.00
Opic Spot
08.0719.00
Opic Medium
08.0720.00

Orientation Module — Módulo de Orientabilidad



Fixed
08.0741.00

Adjustable
08.0742.00

Style Modules — Módulos Estéticos




Cone
08.0724.40
08.0724.14

Soft
08.0725.40
08.0725.14

Flat
08.0726.40
08.0726.14

CIRCLE OF LIGHT

DESIGNED BY FLOS ARCHITECTURAL



CIRCLE OF LIGHT
300 mm




LIGHT SOURCE
POWER LED
12x3W
12x325 lm
2700K/CRI 90
12x3W
12x370 lm
3000K/CRI 90

CIRCLE OF LIGHT
600 mm



LIGHT SOURCE
POWER LED
24x3W
24x325 lm
2700K/CRI 90
24x3W
24x370 lm
3000K/CRI 90

CIRCLE OF LIGHT
900 mm



LIGHT SOURCE
POWER LED
36x3W
36x325 lm
2700K/CRI 90
36x3W
36x370 lm
3000K/CRI 90

■ 14 Black
14 Negro



reddot design award
winner 2013

Description
A lighting system for indoor application comprised of a circular metal structure on which individual LED lighting spots are placed. The fitting is pre-wired and comes with a “Soft Architecture” type frame for an easy and seamless installation on the plasterboard ceiling.
The LED lighting modules are attached with a magnet for an easy mounting and for the maintenance no special tools are needed.
Circle of Light is available in three diameters: 300, 600 or 900 mm comprised of 12, 24 or 36 LED Lighting Spots, according to each size.

Reflectors
The LED spotlight set for the Circle of Light is available for Accent Lighting or General Lighting optic concepts. Herewith this fitting offers a some flexibility to create the desired ambiance.

Power Supply
Remote equipment 1050 mA included.
Driver 1-10V (1V means 10%) for passive dimming controls (sink system). Also compatible with active dimming controls 0,6-10V (source system).
The 1–10-V version can also be controlled a simple button without courtesy light. Cables available for synchronization between drivers (contact the technical department for more details about installation).

Additional Information
The luminaire is supplied with a constant current remote power supply which is connected to a connection distributor equipped with quick connections, to ensure a successful installation where no specific tools are required. Since the central part of the luminaire can be removed, subsequent access to both the power supply and the connection distributor and its interconnecting wiring is ensured. This means that the maintenance work can be carried out easily and conveniently.
IP20 protection grade.
Insulation class II.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance Of Standards And Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria empotrada de interiores con una fácil instalación en techos de cartón yeso, formada por una estructura circular sobre la cual viene posicionado un módulo de iluminación LED, reproducido a lo largo de su perímetro. El producto se suministra pre-instalado sobre un perfil tipo “Soft Architecture” para garantizar su fácil montaje y perfecta integración en el techo.
Mediante un sistema de fijación magnética las labores de instalación de los módulos de luz, así como futuras operaciones de mantenimiento, se pueden realizar sin la necesidad de herramientas específicas.
Circle of Light está disponible en tres diámetros: 300, 600 y 900 mm formados por 12, 24 ó 36 proyectores respectivamente.

Reflectores
La luminaria se encuentra disponible en versiones de luz de acento con ópticas intensivas (accent lighting) o luz ambiental con ópticas extensivas (general lighting), dotando al sistema de cierta flexibilidad para adecuarse a los requerimientos de iluminación.

Unidades de Alimentación
Fuente de alimentación remota a 1050 mA incluida.
Driver 1-10V (1V funciona al 10%) para sistemas de dimado pasivos (sink systems). También compatible con sistemas de dimado activos 0,6-10V (source system).
La versión 1-10V también puede ser controlada vía pulsador simple sin luz de cortesía. Disponibles cables de sincronización entre drivers (consultar departamento técnico para más detalles sobre su instalación).

Información Adicional
La luminaria se suministra con una fuente de alimentación remota de corriente constante que se conecta a un distribuidor de conexiones equipado con conexiones rápidas, de tal forma que su instalación correcta queda garantizada y no se requiere de herramientas específicas. El posterior acceso tanto a la fuente de alimentación, como al distribuidor de conexiones y su cableado de interconexión, queda garantizado gracias a la posibilidad de retirar la parte central de la luminaria, de tal modo que las labores de mantenimiento se puedan realizar de forma cómoda y sencilla.
Índice de protección IP20.
Clase de aislamiento II.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Circle Of Light 300 mm

Power LED 12x4,5W - 12x315 lm - 2700K/CRI 90 / 12x4,5W - 12x297 lm - 3000K/CRI 90







Lighting system, seamless ceiling mounted, for 12 individual LED lighting spots. Set of 12 spots, complete with junction box, power supply and cables, has to be ordered separately. The 1-10V version is dimmable from 10% to 100%.

Accent lighting and general lighting: 1 unit must be ordered.

For Casambi versions consult the Front Office.


Sistema de iluminación perfectamente integrado en el techo, preparado para albergar 12 focos tipo LED. Caja de 12 focos, junto con su correspondiente sistema eléctrico no incluido, se sirve por separado. La versión 1-10V es regulable desde 10% al 100%.

Luz de acento y luz general: se debe pedir 1 unidad.

Para versiones Casambi consultar con el Front Office.

Ø300
Soft Plate
SA.1050.1

2700K
Set of 12 spots. Accent Lighting




Luminous flux luminaire
2263 lm *1 x Set 12 Spots

Beam Angle: 14°		
h(m)	E(lx)	D(m)
1	37445	0.24
2	9361	0.48
3	4161	0.72
4	2340	0.95
5	1498	1.19

No DIM
08.8662.14D
1-10V
08.8662.14D1V
Dali Version
08.8662.14DDA

2700K
Set of 12 spots. General Lighting




Luminous flux luminaire
1799 lm *1 x Set 12 Spots

Beam Angle: 46°		
h(m)	E(lx)	D(m)
1	3622	0.84
2	905	1.69
3	402	2.53
4	226	3.37
5	145	4.22

No DIM
08.8663.14D
1-10V
08.8663.14D1V
Dali Version
08.8663.14DDA

3000K
Set of 12 spots. Accent Lighting




Luminous flux luminaire
2417 lm *1 x Set 12 Spots

Beam Angle: 12°		
h(m)	E(lx)	D(m)
1	44792	0.22
2	11198	0.43
3	4977	0.65
4	2800	0.87
5	1792	1.08

No DIM
08.8572.14D
1-10V
08.8572.14D1V
Dali Version
08.8572.14DDA

3000K
Set of 12 spots. General Lighting



Luminous flux luminaire
2592 lm *1 x Set 12 Spots


Beam Angle: 46°		
h(m)	E(lx)	D(m)
1	5219	0.84
2	1305	1.69
3	580	2.53
4	326	3.37
5	209	4.22


No DIM
08.8573.14D
1-10V
08.8573.14D1V
Dali Version
08.8573.14DDA

Circle Of Light 600 mm

Power LED 24x4,5W - 24x315 lm - 2700K/CRI 90 / 24x4,5W - 24x297 lm - 3000K/CRI 90







Lighting system, seamless ceiling mounted, for 24 individual LED lighting spots. Set of 12 spots, complete with junction box, power supply and cables, has to be ordered separately. The 1-10V version is dimmable from 10% to 100%.

Accent lighting and general lighting: 2 units must be ordered.

For Casambi versions consult the Front Office.


Sistema de iluminación perfectamente integrado en el techo, preparado para albergar 24 focos tipo LED. Cajas de 12 focos, junto con sus correspondientes sistemas eléctricos no incluidos, se sirven por separado. La versión 1-10V es regulable desde 10% al 100%.

Luz de acento y luz general: se deben pedir 2 unidades.

Para versiones Casambi consultar con el Front Office.

Ø600
Soft Plate
SA.1051.1

2700K
Set of 12 spots. Accent Lighting




Luminous flux luminaire
4529 lm *2 x Set 12 Spots

Beam Angle: 14°		
h(m)	E(lx)	D(m)
1	74942	0.24
2	18736	0.48
3	8327	0.72
4	4684	0.95
5	2998	1.19

No DIM
08.8662.14D
1-10V
08.8662.14D1V
Dali Version
08.8662.14DDA

2700K
Set of 12 spots. General Lighting




Luminous flux luminaire
3600 lm *2 x Set 12 Spots

Beam Angle: 46°		
h(m)	E(lx)	D(m)
1	7248	0.84
2	1812	1.69
3	805	2.53
4	453	3.37
5	290	4.22

No DIM
08.8663.14D
1-10V
08.8663.14D1V
Dali Version
08.8663.14DDA

3000K
Set of 12 spots. Accent Lighting




Luminous flux luminaire
4831 lm *2 x Set 12 Spots

Beam Angle: 12°		
h(m)	E(lx)	D(m)
1	89529	0.22
2	22382	0.43
3	9948	0.65
4	5596	0.87
5	3581	1.08

No DIM
08.8572.14D
1-10V
08.8572.14D1V
Dali Version
08.8572.14DDA

3000K
Set of 12 spots. General Lighting



Luminous flux luminaire
5189 lm *2 x Set 12 Spots


Beam Angle: 46°		
h(m)	E(lx)	D(m)
1	10449	0.84
2	2612	1.69
3	1161	2.53
4	653	3.37
5	418	4.22


No DIM
08.8573.14D
1-10V
08.8573.14D1V
Dali Version
08.8573.14DDA

Circle Of Light 900 mm

Power LED 36x4,5W - 36x315 lm - 2700K/CRI 90 / 36x4,5W - 36x297 lm - 3000K/CRI 90







Lighting system, seamless ceiling mounted, for 36 individual LED lighting spots. Set of 12 spots, complete with junction box, power supply and cables, has to be ordered separately. The 1-10V version is dimmable from 10% to 100%.

Accent lighting and general lighting: 3 units must be ordered.


Sistema de iluminación perfectamente integrado en el techo, preparado para albergar 36 focos tipo LED. Cajas de 12 focos, junto con sus correspondientes sistemas eléctricos no incluidos, se sirven por separado. La versión 1-10V es regulable desde 10% al 100%.

Luz de acento y luz general: se deben pedir 3 unidades.

Ø900
Soft Plate
SA.1052.1

2700K
Set of 12 spots. Accent Lighting

14°




Luminous flux luminaire
6794 lm *3 x Set 12 Spots

Beam Angle:	14°	
h(m)	E(lx)	D(m)
1	112414	0.24
2	28103	0.48
3	12490	0.72
4	7026	0.95
5	4497	1.19

No DIM
08.8662.14D
1-10V
08.8662.14D1V
Dali Version
08.8662.14DDA

3000K
Set of 12 spots. Accent Lighting

12°




Luminous flux luminaire
7246 lm *3 x Set 12 Spots

Beam Angle:	12°	
h(m)	E(lx)	D(m)
1	134293	0.22
2	33573	0.43
3	14921	0.65
4	8393	0.87
5	5372	1.08

No DIM
08.8572.14D
1-10V
08.8572.14D1V
Dali Version
08.8572.14DDA

2700K
Set of 12 spots. General Lighting

46°




Luminous flux luminaire
5399 lm *3 x Set 12 Spots

Beam Angle:	46°	
h(m)	E(lx)	D(m)
1	10872	0.84
2	2718	1.69
3	1208	2.53
4	680	3.37
5	435	4.22

No DIM
08.8663.14D
1-10V
08.8663.14D1V
Dali Version
08.8663.14DDA

3000K
Set of 12 spots. General Lighting

46°



Luminous flux luminaire
7784 lm *3 x Set 12 Spots

Beam Angle:	46°	
h(m)	E(lx)	D(m)
1	15673	0.84
2	3918	1.69
3	1741	2.53
4	980	3.37
5	627	4.22

No DIM
08.8573.14D
1-10V
08.8573.14D1V
Dali Version
08.8573.14DDA

DOWNLIGHTS

Kap, Bon Jour, UT Downlight,
Light Supply, Johnny.

KAP

DESIGNED BY FLOS ARCHITECTURAL

KAP Ø50

FIXED



ADJUSTABLE



LIGHT SOURCE
LED ARRAY
7,5W
595 lm
2700K/CRI 90
635 lm
3000K/CRI 90

KAP 80

FIXED



LIGHT SOURCE
KAP 80
LED ARRAY
9,2W
935 lm
2700K/CRI 90
974 lm
3000K/CRI 90

LIGHT SOURCE
KAP 80 PLUS
LED ARRAY
13W
1370 lm
2700K/CRI 90
1460 lm
3000K/CRI 90

ADJUSTABLE



LIGHT SOURCE
KAP 80 DTW
LED ARRAY
13W
1023 lm
1800K-2850K
CRI 95
Dim To Warm

WALL-WASHER



LIGHT SOURCE
LED
QR-CBC 51
GX5.3

LIGHT SOURCE
LED
PAR 16
GZ10

KAP Ø105

FIXED



LIGHT SOURCE
LED ARRAY
23W
2690 lm
2700K/CRI 90
2870 lm
3000K/CRI 90

ADJUSTABLE



LIGHT SOURCE
LED
QR-CBC 51
GX5.3

WALL-WASHER



LIGHT SOURCE
LED
PAR 16
GZ10

DEEP



LIGHT SOURCE
LED ARRAY
23W
2690 lm
2700K/CRI 90
2870 lm
3000K/CRI 90

SQUARE FIXED



LIGHT SOURCE
LED
QR-CBC 51
GX5.3

KAP COLORS - TRIMLESS MOUNTING

B1 White
B1 Blanco



GL Matte Gold
GL Oro Mate



74 Black
74 Negro



EASY KAP

DESIGNED BY FLOS ARCHITECTURAL

EASY KAP Ø30

FIXED



ADJUSTABLE



LIGHTSOURCE
POWER LED
3W
222 lm
2700K/CRI90
229 lm
3000K/CRI90

EASY KAP Ø50

FIXED



ADJUSTABLE



LIGHT SOURCE
LED ARRAY
7,5W
595 lm
2700K/CRI 90
635 lm
3000K/CRI 90

EASY KAP 80

FIXED



ADJUSTABLE



WALL-WASHER



LIGHT SOURCE
EASY KAP 80
LED ARRAY
9,2W
935 lm
2700K/CRI 90
974 lm
3000K/CRI 90

LIGHT SOURCE
EASY KAP 80 PLUS
LED ARRAY
13W
1370 lm
2700K/CRI 90
1460 lm
3000K/CRI 90

LIGHT SOURCE
EASY KAP 80 DTW
LED ARRAY
13W
1023 lm
1800K-2850K
CRI 95
Dim To Warm

LIGHT SOURCE
LED
QR-CBC 51
GX5.3

LIGHT SOURCE
LED
PAR 16
GZ10

EASY KAP Ø105

FIXED



ADJUSTABLE



WALL-WASHER



LIGHT SOURCE
LED ARRAY
23W
2690 lm
2700K/CRI 90
2870 lm
3000K/CRI 90

LIGHT SOURCE
LED
QR-CBC 51
GX5.3

LIGHT SOURCE
LED
PAR 16
GZ10

EASY KAP COLORS - TRIM MOUNTING

B1 White
B1 Blanco



GL Matte Gold
GL Oro Mate



74 Black
74 Negro



Description
Luminaire for embedded installation in ceilings for LEDs lamps.
The Easy Kap version has an aluminium injected body for the 50, 80 and 105 mm versions, with a liquid paint or dust with a glass or plastic diffuser depending on the version. Easy Kap: does not need a pre-installation frame.
The Kap version has an aluminium-injected body with a liquid paint finish. Available in three diameters: 50 mm, 80 mm and 105 mm.
Main optics in shiny anodised aluminium with a glass or plastic diffuser element, depending on the version.
Lamp holder with a dissipating element in injected aluminium and a thermoplastic embedding ring for the optic body.

Power Supply
Easy Kap 30/50/80/105 LED and Kap 50 and 80: Remote equipment not included.
Kap 105 LED/Kap 80 and Easy Kap 80 Dim To Warm: 1-10V remote equipment included. The output voltage of the equipment must always be less than 60Vdc.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Accessories
Pre-installation frame for the round and square Kap 50 and 80 and 105 version.
Available for installation on cement.

Additional Information
IP20, IP23, IP43, IP44, IP54, IP65 protection grade depending on the versions.
Insulation class I, II, III depending on the versions.
- KAP 50 / 80 / 105:
The LED modules installed on the LED Array versions have cutting-edge technology that permits a lower average temperature in the electronics. Thanks to this feature, the luminaire can operate at a higher power inside the safety parameters yet still offer 20% added luminous flux.
The new “Dim To Warm” technology reproduces the effect of a traditional lamp, offering a warmer light by reducing the light intensity.
The “Dim To Warm” luminaries are dimmed through the 1-10V protocol.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria para ser instalada empotrada en techos para lámparas LED.
La versión Easy Kap tiene un cuerpo de aluminio inyectado para las versiones de 50, 80 y 105 mm, con acabado en pintura líquida o en polvo y difusor de vidrio o plástico, según la versión. Easy Kap: no necesita pre-marco de instalación.
La versión Kap tiene un cuerpo de aluminio inyectado con acabado en pintura líquida. Está disponible en tres diámetros: 50mm, 80 mm y 105 mm.
Óptica principal realizada en aluminio anodizado brillo con elemento difusor realizado en cristal o plástico dependiendo de versiones.
Portalámparas con elemento disipador en aluminio inyectado y aro de empotramiento del cuerpo óptico en material termoplástico.

Unidades de Alimentación
Easy Kap 30/50/80/105 LED y Kap 50 y 80: equipo remoto no incluido.
Kap 105 LED/Kap 80 e Easy Kap 80 Dim To Warm: equipo remoto 1-10V incluido. El voltaje de salida del equipo debe ser siempre inferior a 60Vdc.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).

Accesorios
Pre-marco de instalación para las versiones Kap 50 y 80 redondo y cuadrado y 105 redondo.
Disponibles can para instalación en cemento.

Información Adicional
Índice de protección IP20, IP23, IP43, IP44, IP54, IP65, según las versiones.
Clase de aislamiento I, II, III, según las versiones.
- KAP 50 / 80 / 105:
Los módulos LED instalados en las versiones LED Array cuentan con la última generación tecnológica que permite una menor temperatura media en el funcionamiento de la electrónica. Gracias a esta característica, la luminaria puede operar dentro de parámetros de seguridad a una mayor potencia, ofreciendo una aumento del 20% del flujo luminoso.
La nueva tecnología “Dim To Warm” reproduce el efecto de las viejas lámparas halógenas al ser reguladas, ofreciendo más calidez al reducir la intensidad lumínica.
Las luminarias “Dim To Warm” se regulan mediante el protocolo 1-10V.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.


Easy Kap


Kap

Kap Ø50 Fixed

LED Array DC 200 mA - 7,5W - 595 lm - 2700K/CRI 90 / 7,5W - 635 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Remote power supply to be installed in an accessible place. Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Fuente de alimentación remota para ser instalada en un lugar accesible. Marco de pre-instalación. Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9160
Dimmable 0-10V	60.9483
Dimmable Dali 2	60.9604
Mains Dimming	60.9949
Casambi	60.9392 + DALI/1-10V Driver

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7300.B1
- 05.7300.GL
- 05.7300.74

15° SPOT



Luminous flux luminaire 543 lm [EXTREME CUT OFF] @White (B1)


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5025	0.27
2	1256	0.53
3	558	0.80
4	314	1.07
5	201	1.33

Optic Medium 2700K

- 05.7301.B1
- 05.7301.GL
- 05.7301.74

24° MEDIUM



Luminous flux luminaire 488 lm [EXTREME CUT OFF] @White (B1)


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	2032	0.43
2	508	0.86
3	226	1.30
4	127	1.73
5	81	2.16

Optic Flood 2700K

- 05.7302.B1
- 05.7302.GL
- 05.7302.74

49° FLOOD



Luminous flux luminaire 496 lm [EXTREME CUT OFF] @White (B1)


Beam Angle: 49°

h(m)	E(lx)	D(m)
1	720	0.91
2	180	1.83
3	80	2.74
4	45	3.66
5	29	4.57

Optic Spot 3000K

- 05.7305.B1
- 05.7305.GL
- 05.7305.74

15° SPOT



Luminous flux luminaire 583 lm [EXTREME CUT OFF] @White (B1)


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5398	0.27
2	1349	0.53
3	600	0.80
4	337	1.07
5	216	1.33

Optic Medium 3000K

- 05.7306.B1
- 05.7306.GL
- 05.7306.74

24° MEDIUM



Luminous flux luminaire 524 lm [EXTREME CUT OFF] @White (B1)


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	2183	0.43
2	546	0.86
3	243	1.30
4	136	1.73
5	87	2.16

Optic Flood 3000K

- 05.7307.B1
- 05.7307.GL
- 05.7307.74

49° FLOOD



Luminous flux luminaire 532 lm [EXTREME CUT OFF] @White (B1)


Beam Angle: 49°


h(m)	E(lx)	D(m)
1	774	0.91
2	193	1.83
3	86	2.74
4	48	3.66
5	31	4.57

Kap Ø50 Adjustable

LED Array DC 200 mA - 7,5W - 595 lm - 2700K/CRI 90 / 7,5W - 635 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Remote power supply to be installed in an accessible place. Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Fuente de alimentación remota para ser instalada en un lugar accesible. Marco de pre-instalación. Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9160
Dimmable 0-10V	60.9483
Dimmable Dali	60.9604
Mains Dimming	60.9949
Casambi	60.9392 + DALI/1-10V Driver

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7310.B1
- 05.7310.GL
- 05.7310.74

15° SPOT



Luminous flux luminaire 543 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5025	0.27
2	1256	0.53
3	558	0.80
4	314	1.07
5	201	1.33

Optic Medium 2700K

- 05.7311.B1
- 05.7311.GL
- 05.7311.74

24° MEDIUM



Luminous flux luminaire 488 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	2032	0.43
2	508	0.86
3	226	1.30
4	127	1.73
5	81	2.16

Optic Flood 2700K

- 05.7312.B1
- 05.7312.GL
- 05.7312.74

49° FLOOD



Luminous flux luminaire 496 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 49°

h(m)	E(lx)	D(m)
1	720	0.91
2	180	1.83
3	80	2.74
4	45	3.66
5	29	4.57

Optic Spot 3000K

- 05.7315.B1
- 05.7315.GL
- 05.7315.74

15° SPOT



Luminous flux luminaire 583 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5398	0.27
2	1349	0.53
3	600	0.80
4	337	1.07
5	216	1.33

Optic Medium 3000K

- 05.7316.B1
- 05.7316.GL
- 05.7316.74

24° MEDIUM



Luminous flux luminaire 524 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	2183	0.43
2	546	0.86
3	243	1.30
4	136	1.73
5	87	2.16

Optic Flood 3000K

- 05.7317.B1
- 05.7317.GL
- 05.7317.74

49° FLOOD



Luminous flux luminaire 532 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 49°


h(m)	E(lx)	D(m)
1	774	0.91
2	193	1.83
3	86	2.74
4	48	3.66
5	31	4.57

Kap Ø80 - Fixed

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 03.4531.B1
- 03.4531.GL
- 03.4531.74




Luminous flux luminaire
710 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2684	0.34
2	671	0.68
3	298	1.02
4	168	1.36
5	107	1.70

Optic Spot 3000K

- 03.4530.B1
- 03.4530.GL
- 03.4530.74




Luminous flux luminaire
739 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2792	0.34
2	698	0.68
3	310	1.02
4	175	1.36
5	112	1.70

Optic Medium 2700K

- 03.4181.B1
- 03.4181.GL
- 03.4181.74




Luminous flux luminaire
606 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1796	0.46
2	449	0.92
3	200	1.39
4	112	1.85
5	72	2.31

Optic Medium 3000K

- 03.4180.B1
- 03.4180.GL
- 03.4180.74




Luminous flux luminaire
630 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1868	0.46
2	467	0.92
3	208	1.39
4	117	1.85
5	75	2.31

Optic Flood 2700K

- 03.4533.B1
- 03.4533.GL
- 03.4533.74




Luminous flux luminaire
688 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 50°

h(m)	E(lx)	D(m)
1	1066	0.93
2	266	1.86
3	118	2.79
4	67	3.72
5	43	4.65

Optic Flood 3000K

- 03.4532.B1
- 03.4532.GL
- 03.4532.74



Luminous flux luminaire
715 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 50°


h(m)	E(lx)	D(m)
1	1108	0.93
2	277	1.86
3	123	2.79
4	69	3.72
5	44	4.65

Kap Ø80 Plus - Fixed

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7451.B1
- 05.7451.GL
- 05.7451.74





Luminous flux luminaire
1050 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	3968	0.34
2	992	0.68
3	441	1.02
4	248	1.36
5	159	1.70

Optic Medium 2700K

- 05.7411.B1
- 05.7411.GL
- 05.7411.74





Luminous flux luminaire
896 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2655	0.46
2	664	0.92
3	295	1.39
4	166	1.85
5	106	2.31

Optic Flood 2700K

- 05.7453.B1
- 05.7453.GL
- 05.7453.74





Luminous flux luminaire
1017 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 50°

h(m)	E(lx)	D(m)
1	1575	0.93
2	394	1.86
3	175	2.79
4	98	3.72
5	63	4.65

Optic Spot 3000K

- 05.7450.B1
- 05.7450.GL
- 05.7450.74





Luminous flux luminaire
1079 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4078	0.34
2	1019	0.68
3	453	1.02
4	255	1.36
5	163	1.70

Optic Medium 3000K

- 05.7410.B1
- 05.7410.GL
- 05.7410.74





Luminous flux luminaire
921 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2728	0.46
2	682	0.92
3	303	1.39
4	170	1.85
5	109	2.31

Optic Flood 3000K

- 05.7452.B1
- 05.7452.GL
- 05.7452.74





Luminous flux luminaire
1045 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 50°


h(m)	E(lx)	D(m)
1	1619	0.93
2	405	1.86
3	180	2.79
4	101	3.72
5	65	4.65

Kap Ø80 Fixed - Dim To Warm

LED Array DC 300mA - 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Optic Spot
1800K-2850K
- 03.4530.B1.LE
- 03.4530.GL.LE
- 03.4530.74.LE






Luminous flux luminaire
740 lm [EXTREME CUT OFF)
@White (B1)

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	2805	0.35
2	701	0.69
3	312	1.04
4	175	1.39
5	112	1.74

Optic Medium
1800K-2850K
- 03.4180.B1.LE
- 03.4180.GL.LE
- 03.4180.74.LE






Luminous flux luminaire
735 lm [EXTREME CUT OFF)
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	2015	0.49
2	504	0.98
3	224	1.46
4	126	1.95
5	81	2.44

Optic Flood
1800K-2850K
- 03.4532.B1.LE
- 03.4532.GL.LE
- 03.4532.74.LE





Luminous flux luminaire
729 lm [EXTREME CUT OFF)
@White (B1)


Beam Angle: 49°


h(m)	E(lx)	D(m)
1	1127	0.92
2	282	1.83
3	125	2.75
4	70	3.67
5	45	4.59

Kap 80 Square - Fixed

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 03.4535.B1
- 03.4535.GL
- 03.4535.74




Luminous flux luminaire
741 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	18°
h(m) E(lx)	D(m)
1 2656	0.31
2 664	0.62
3 295	0.94
4 166	1.25
5 106	1.56

Optic Medium 2700K

- 03.4183.B1
- 03.4183.GL
- 03.4183.74




Luminous flux luminaire
615 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	25°
h(m) E(lx)	D(m)
1 1605	0.45
2 401	0.90
3 178	1.34
4 100	1.79
5 64	2.24

Optic Flood 2700K

- 03.4537.B1
- 03.4537.GL
- 03.4537.74




Luminous flux luminaire
723 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	55°
h(m) E(lx)	D(m)
1 921	1.03
2 230	2.07
3 102	3.10
4 58	4.14
5 37	5.17

Optic Spot 3000K

- 03.4534.B1
- 03.4534.GL
- 03.4534.74




Luminous flux luminaire
771 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	18°
h(m) E(lx)	D(m)
1 2762	0.31
2 691	0.62
3 307	0.94
4 173	1.25
5 110	1.56

Optic Medium 3000K

- 03.4182.B1
- 03.4182.GL
- 03.4182.74




Luminous flux luminaire
640 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	25°
h(m) E(lx)	D(m)
1 1670	0.45
2 417	0.90
3 186	1.34
4 104	1.79
5 67	2.24

Optic Flood 3000K

- 03.4536.B1
- 03.4536.GL
- 03.4536.74




Luminous flux luminaire
752 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	55°
h(m) E(lx)	D(m)
1 958	1.03
2 240	2.07
3 106	3.10
4 60	4.14
5 38	5.17

Kap 80 Plus Square - Fixed

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7455.B1
- 05.7455.GL
- 05.7455.74

18° SPOT



Luminous flux luminaire
1096 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	3926	0.31
2	981	0.62
3	436	0.94
4	245	1.25
5	157	1.56

Optic Medium 2700K

- 05.7413.B1
- 05.7413.GL
- 05.7413.74

25° MEDIUM



Luminous flux luminaire
910 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	2373	0.45
2	593	0.90
3	264	1.34
4	148	1.79
5	95	2.24

Optic Flood 2700K

- 05.7457.B1
- 05.7457.GL
- 05.7457.74

55° FLOOD



Luminous flux luminaire
1069 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 55°

h(m)	E(lx)	D(m)
1	1362	1.03
2	340	2.07
3	151	3.10
4	85	4.14
5	54	5.17

Optic Spot 3000K

- 05.7454.B1
- 05.7454.GL
- 05.7454.74

18° SPOT



Luminous flux luminaire
1126 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	4034	0.31
2	1009	0.62
3	448	0.94
4	252	1.25
5	161	1.56

Optic Medium 3000K

- 05.7412.B1
- 05.7412.GL
- 05.7412.74

25° MEDIUM



Luminous flux luminaire
935 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	2439	0.45
2	610	0.90
3	271	1.34
4	152	1.79
5	98	2.24

Optic Flood 3000K

- 05.7456.B1
- 05.7456.GL
- 05.7456.74

55° FLOOD



Luminous flux luminaire
1099 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 55°


h(m)	E(lx)	D(m)
1	1399	1.03
2	350	2.07
3	155	3.10
4	87	4.14
5	56	5.17

Kap 80 Square Fixed - Dim To Warm

LED Array DC 300mA - 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Optic Spot
1800K-2850K
- 03.4534.B1.LE
- 03.4534.GL.LE
- 03.4534.74.LE






Luminous flux luminaire
753 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2620	0.32
2	655	0.64
3	291	0.96
4	164	1.28
5	105	1.60

Optic Medium
1800K-2850K
- 03.4182.B1.LE
- 03.4182.GL.LE
- 03.4182.74.LE






Luminous flux luminaire
750 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	1827	0.48
2	457	0.96
3	203	1.45
4	114	1.93
5	73	2.41

Optic Flood
1800K-2850K
- 03.4536.B1.LE
- 03.4536.GL.LE
- 03.4536.74.LE





Luminous flux luminaire
736 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 54°

h(m)	E(lx)	D(m)
1	952	1.02
2	238	2.04
3	106	3.06
4	59	4.08
5	38	5.10

Kap Ø80 Fixed

LED QR-CBC 51 GX5.3





GWT 850°
0,12 Kg
III
IP 23
h=130 min

Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.

03.4228.B1
03.4228.GL
03.4228.74

Kap 80 Square Fixed

LED QR-CBC 51 GX5.3





GWT 850°
0,12 Kg
III
IP 23
h=130 min
03

Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.

03.4226.B1
03.4226.GL
03.4226.74

Kap Ø80 Fixed

LED PAR 16 GZ10





GWT 850°
0,12 Kg
IP 23
h=155 min

Recessed luminaire with main voltage source.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.

03.4229.B1
03.4229.GL
03.4229.74

Kap 80 Square Fixed

LED PAR 16 GZ10





GWT 850°
0,12 Kg
IP 23
h=155 min
03

Recessed luminaire with main voltage source.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


03.4227.B1
03.4227.GL
03.4227.74

Kap Ø80 - Adjustable

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 03.4539.B1
- 03.4539.GL
- 03.4539.74

19° SPOT



Luminous flux luminaire 704 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2811	0.33
2	703	0.66
3	312	0.99
4	176	1.33
5	112	1.66

Optic Medium 2700K

- 03.4185.B1
- 03.4185.GL
- 03.4185.74

26° MEDIUM



Luminous flux luminaire 664 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1864	0.47
2	466	0.93
3	207	1.40
4	116	1.87
5	75	2.33

Optic Flood 2700K

- 03.4541.B1
- 03.4541.GL
- 03.4541.74

50° FLOOD



Luminous flux luminaire 688 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 50°

h(m)	E(lx)	D(m)
1	1063	0.94
2	266	1.89
3	118	2.83
4	66	3.77
5	43	4.71

Optic Spot 3000K

- 03.4538.B1
- 03.4538.GL
- 03.4538.74

19° SPOT



Luminous flux luminaire 732 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2924	0.33
2	731	0.66
3	325	0.99
4	183	1.33
5	117	1.66

Optic Medium 3000K

- 03.4184.B1
- 03.4184.GL
- 03.4184.74

26° MEDIUM



Luminous flux luminaire 691 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1939	0.47
2	485	0.93
3	215	1.40
4	121	1.87
5	78	2.33

Optic Flood 3000K

- 03.4540.B1
- 03.4540.GL
- 03.4540.74

50° FLOOD



Luminous flux luminaire 716 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 50°


h(m)	E(lx)	D(m)
1	1106	0.94
2	276	1.89
3	123	2.83
4	69	3.77
5	44	4.71

Kap Ø80 Plus - Adjustable

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7459.B1
- 05.7459.GL
- 05.7459.74




Luminous flux luminaire
1040 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4156	0.33
2	1039	0.66
3	462	0.99
4	260	1.33
5	166	1.66

Optic Medium 2700K

- 05.7415.B1
- 05.7415.GL
- 05.7415.74




Luminous flux luminaire
982 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2756	0.47
2	689	0.93
3	306	1.40
4	172	1.87
5	110	2.33

Optic Flood 2700K

- 05.7461.B1
- 05.7461.GL
- 05.7461.74




Luminous flux luminaire
1017 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 50°

h(m)	E(lx)	D(m)
1	1571	0.94
2	393	1.89
3	175	2.83
4	98	3.77
5	63	4.71

Optic Spot 3000K

- 05.7458.B1
- 05.7458.GL
- 05.7458.74




Luminous flux luminaire
1069 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4271	0.33
2	1068	0.66
3	475	0.99
4	267	1.33
5	171	1.66

Optic Medium 3000K

- 05.7414.B1
- 05.7414.GL
- 05.7414.74




Luminous flux luminaire
1009 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2832	0.47
2	708	0.93
3	315	1.40
4	177	1.87
5	113	2.33

Optic Flood 3000K

- 05.7460.B1
- 05.7460.GL
- 05.7460.74



Luminous flux luminaire
1045 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 50°


h(m)	E(lx)	D(m)
1	1615	0.94
2	404	1.89
3	179	2.83
4	101	3.77
5	65	4.71

Kap Ø80 Adjustable - Dim To Warm

LED Array DC 300mA - 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Optic Spot
1800K-2850K

- 03.4538.B1.LE
- 03.4538.GL.LE
- 03.4538.74.LE





Luminous flux luminaire
716 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2844	0.31
2	711	0.63
3	316	0.94
4	178	1.25
5	114	1.56

Optic Medium
1800K-2850K

- 03.4184.B1.LE
- 03.4184.GL.LE
- 03.4184.74.LE





Luminous flux luminaire
722 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 27°

h(m)	E(lx)	D(m)
1	1953	0.48
2	488	0.97
3	217	1.45
4	122	1.94
5	78	2.42

Optic Flood
1800K-2850K

- 03.4540.B1.LE
- 03.4540.GL.LE
- 03.4540.74.LE





Luminous flux luminaire
707 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 51°


h(m)	E(lx)	D(m)
1	1081	0.94
2	270	1.89
3	120	2.83
4	68	3.78
5	43	4.72

Kap 80 Square - Adjustable

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 03.4543.B1
- 03.4543.GL
- 03.4543.74





Luminous flux luminaire
738 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2730	0.31
2	682	0.62
3	303	0.93
4	171	1.24
5	109	1.55

Optic Medium 2700K

- 03.4187.B1
- 03.4187.GL
- 03.4187.74





Luminous flux luminaire
630 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1692	0.44
2	423	0.88
3	188	1.32
4	106	1.76
5	68	2.20

Optic Flood 2700K

- 03.4545.B1
- 03.4545.GL
- 03.4545.74





Luminous flux luminaire
722 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 53°

h(m)	E(lx)	D(m)
1	986	0.99
2	246	1.98
3	110	2.98
4	62	3.97
5	39	4.96

Optic Spot 3000K

- 03.4542.B1
- 03.4542.GL
- 03.4542.74





Luminous flux luminaire
768 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2840	0.31
2	710	0.62
3	316	0.93
4	177	1.24
5	114	1.55

Optic Medium 3000K

- 03.4186.B1
- 03.4186.GL
- 03.4186.74





Luminous flux luminaire
656 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1760	0.44
2	440	0.88
3	196	1.32
4	110	1.76
5	70	2.20

Optic Flood 3000K

- 03.4544.B1
- 03.4544.GL
- 03.4544.74





Luminous flux luminaire
751 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 53°


h(m)	E(lx)	D(m)
1	1025	0.99
2	256	1.98
3	114	2.98
4	64	3.97
5	41	4.96

Kap 80 Plus Square - Adjustable

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7463.B1
- 05.7463.GL
- 05.7463.74

18° SPOT



Luminous flux luminaire 1092 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	4036	0.31
2	1009	0.62
3	448	0.93
4	252	1.24
5	161	1.55

Optic Medium 2700K

- 05.7417.B1
- 05.7417.GL
- 05.7417.74

25° MEDIUM



Luminous flux luminaire 932 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	2501	0.44
2	625	0.88
3	278	1.32
4	156	1.76
5	100	2.20

Optic Flood 2700K

- 05.7465.B1
- 05.7465.GL
- 05.7465.74

53° FLOOD



Luminous flux luminaire 1068 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 53°

h(m)	E(lx)	D(m)
1	1457	0.99
2	364	1.98
3	162	2.98
4	91	3.97
5	58	4.96

Optic Spot 3000K

- 05.7462.B1
- 05.7462.GL
- 05.7462.74

18° SPOT



Luminous flux luminaire 1122 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	4147	0.31
2	1037	0.62
3	461	0.93
4	259	1.24
5	166	1.55

Optic Medium 3000K

- 05.7416.B1
- 05.7416.GL
- 05.7416.74

25° MEDIUM



Luminous flux luminaire 958 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	2570	0.44
2	643	0.88
3	286	1.32
4	161	1.76
5	103	2.20

Optic Flood 3000K

- 05.7464.B1
- 05.7464.GL
- 05.7464.74

53° FLOOD



Luminous flux luminaire 1097 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 53°


h(m)	E(lx)	D(m)
1	1497	0.99
2	374	1.98
3	166	2.98
4	94	3.97
5	60	4.96

Kap 80 Square Adjustable - Dim To Warm

LED Array DC 300mA - 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

Optic Spot
1800K-2850K
- 03.4542.B1.LE
- 03.4542.GL.LE
- 03.4542.74.LE






Luminous flux luminaire
754 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2629	0.31
2	657	0.63
3	292	0.94
4	164	1.26
5	105	1.57

Optic Medium
1800K-2850K
- 03.4186.B1.LE
- 03.4186.GL.LE
- 03.4186.74.LE






Luminous flux luminaire
752 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1844	0.47
2	461	0.94
3	205	1.41
4	115	1.88
5	74	2.35

Optic Flood
1800K-2850K
- 03.4544.B1.LE
- 03.4544.GL.LE
- 03.4544.74.LE





Luminous flux luminaire
732 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 53°


h(m)	E(lx)	D(m)
1	965	1.01
2	241	2.01
3	107	3.02
4	60	4.03
5	39	5.03

Kap Ø80 Adjustable

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


- 03.4236.B1
- 03.4236.GL
- 03.4236.74

Kap 80 Square Adjustable

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


- 03.4234.B1
- 03.4234.GL
- 03.4234.74

Kap Ø80 Adjustable

LED PAR 16 GZ10







Recessed luminaire with main voltage source.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


- 03.4237.B1
- 03.4237.GL
- 03.4237.74

Kap 80 Square Adjustable

LED PAR 16 GZ10







Recessed luminaire with main voltage source.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


- 03.4235.B1
- 03.4235.GL
- 03.4235.74

Kap Ø80 - Wall-Washer

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Elliptical lens included. Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Lente elíptica incluida. Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 03.4189.B1
- 03.4189.GL
- 03.4189.74




Luminous flux luminaire
598 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 28°

h(m)	E(lx)	D(m)
1	911	0.62
2	228	1.24
3	101	1.87
4	57	2.49
5	36	3.11

3000K

- 03.4188.B1
- 03.4188.GL
- 03.4188.74



Luminous flux luminaire
622 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 28°


h(m)	E(lx)	D(m)
1	947	0.62
2	237	1.24
3	105	1.87
4	59	2.49
5	38	3.11

Kap Ø80 Plus - Wall-Washer

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Elliptical lens included. Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Lente elíptica incluida. Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 05.7421.B1
- 05.7421.GL
- 05.7421.74




Luminous flux luminaire
884 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle: 28°

h(m)	E(lx)	D(m)
1	1347	0.62
2	337	1.24
3	150	1.87
4	84	2.49
5	54	3.11

3000K

- 05.7420.B1
- 05.7420.GL
- 05.7420.74



Luminous flux luminaire
908 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 28°


h(m)	E(lx)	D(m)
1	1384	0.62
2	346	1.24
3	154	1.87
4	86	2.49
5	55	3.11

Kap Ø80 Wall-Washer - Dim To Warm

LED Array DC 300mA - 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

1800K-2850K

- 03.4188.B1.LE
- 03.4188.GL.LE
- 03.4188.74.LE





Luminous flux luminaire
770 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 28°


h(m)	E(lx)	D(m)
1	1240	0.64
2	310	1.29
3	138	1.93
4	78	2.58
5	50	3.22

Kap 80 - Square Wall-Washer

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Elliptical lens included. Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Lente elíptica incluida. Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 03.4191.B1
- 03.4191.GL
- 03.4191.74




Luminous flux luminaire
625 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	1125	0.62
2	281	1.24
3	125	1.85
4	70	2.47
5	45	3.09

3000K

- 03.4190.B1
- 03.4190.GL
- 03.4190.74




Luminous flux luminaire
650 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 27°


h(m)	E(lx)	D(m)
1	1170	0.62
2	292	1.24
3	130	1.85
4	73	2.47
5	47	3.09

Kap 80 Plus - Square Wall-Washer

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Elliptical lens included. Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Lente elíptica incluida. Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 05.7423.B1
- 05.7423.GL
- 05.7423.74




Luminous flux luminaire
924 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	1663	0.62
2	416	1.24
3	185	1.85
4	104	2.47
5	67	3.09

3000K

- 05.7422.B1
- 05.7422.GL
- 05.7422.74



Luminous flux luminaire
950 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 27°


h(m)	E(lx)	D(m)
1	1709	0.62
2	427	1.24
3	190	1.85
4	107	2.47
5	68	3.09

Kap 80 Square Wall-Washer - Dim To Warm

LED Array DC 300mA - 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.

1800K-2850K

- 03.4190.B1.LE
- 03.4190.GL.LE
- 03.4190.74.LE





Luminous flux luminaire
723 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 28°

h(m)	E(lx)	D(m)
1	1199	0.68
2	300	1.37
3	133	2.05
4	75	2.74
5	48	3.42

Kap Ø80 Wall-Washer

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.

- 03.4244.B1
- 03.4244.GL
- 03.4244.74

Kap 80 Square Wall-Washer

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.

- 03.4242.B1
- 03.4242.GL
- 03.4242.74

Kap Ø80 Wall-Washer

LED PAR 16 GZ10







Recessed luminaire with main voltage source.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.

- 03.4245.B1
- 03.4245.GL
- 03.4245.74

Kap 80 Square Wall-Washer

LED PAR 16 GZ10







Recessed luminaire with main voltage source.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


- 03.4243.B1
- 03.4243.GL
- 03.4243.74

Kap Ø105 Fixed

LED Array DC 650 mA - 23W - 2690 lm - 2700K/CRI 90 / 23W - 2870 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Remote transformer not included.
Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Transformador remoto no incluido.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 1-10V	60.9439
Dimmable Dali 2	60.7709
Casambi	60.9207
Mains Dimming	60.9692

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7100.B1
- 05.7100.GL
- 05.7100.74




Luminous flux luminaire 1715 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	10889	0.30
2	2722	0.59
3	1210	0.89
4	681	1.18
5	436	1.48

Optic Medium 2700K

- 05.7101.B1
- 05.7101.GL
- 05.7101.74




Luminous flux luminaire 1675 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	6243	0.48
2	1561	0.97
3	694	1.45
4	390	1.93
5	250	2.41

Optic Flood 2700K

- 05.7102.B1
- 05.7102.GL
- 05.7102.74




Luminous flux luminaire 1815 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 51°

h(m)	E(lx)	D(m)
1	2755	0.96
2	689	1.91
3	306	2.87
4	172	3.82
5	110	4.78

Optic Spot 3000K

- 05.7105.B1
- 05.7105.GL
- 05.7105.74




Luminous flux luminaire 2275 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	14445	0.30
2	3611	0.59
3	1605	0.89
4	903	1.18
5	578	1.48

Optic Medium 3000K

- 05.7106.B1
- 05.7106.GL
- 05.7106.74




Luminous flux luminaire 2222 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	8281	0.48
2	2070	0.97
3	920	1.45
4	518	1.93
5	331	2.41

Optic Flood 3000K

- 05.7107.B1
- 05.7107.GL
- 05.7107.74



Luminous flux luminaire 2407 lm (EXTREME CUT OFF) @White (B1)


Beam Angle: 51°


h(m)	E(lx)	D(m)
1	3654	0.96
2	914	1.91
3	406	2.87
4	228	3.82
5	146	4.78

Kap 105 Square

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


03.4572.B1
03.4572.GL
03.4572.74

Kap Ø105 Fixed

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


05.7130.B1
05.7130.GL
05.7130.74

Kap Ø105 Fixed

LED PAR 16 GZ10







Recessed luminaire with main voltage source.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


05.7131.B1
05.7131.GL
05.7131.74

Kap Ø105 Adjustable

LED Array DC 650 mA - 23W - 2690 lm - 2700K/CRI 90 / 23W - 2870 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Remote transformer not included.
Diffusing lens included.
Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Transformador remoto no incluido.
Lente difusora incluida.
Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 1-10V	60.9439
Dimmable Dali 2	60.7709
Casambi	60.9207
Mains Dimming	60.9692

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7110.B1
- 05.7110.GL
- 05.7110.74




Luminous flux luminaire
1715 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	10889	0.30
2	2722	0.59
3	1210	0.89
4	681	1.18
5	436	1.48

Optic Medium 2700K

- 05.7111.B1
- 05.7111.GL
- 05.7111.74




Luminous flux luminaire
1675 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	6243	0.48
2	1561	0.97
3	694	1.45
4	390	1.93
5	250	2.41

Optic Flood 2700K

- 05.7112.B1
- 05.7112.GL
- 05.7112.74




Luminous flux luminaire
1815 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 51°

h(m)	E(lx)	D(m)
1	2755	0.96
2	689	1.91
3	306	2.87
4	172	3.82
5	110	4.78

Optic Spot 3000K

- 05.7115.B1
- 05.7115.GL
- 05.7115.74




Luminous flux luminaire
2275 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	14445	0.30
2	3611	0.59
3	1605	0.89
4	903	1.18
5	578	1.48

Optic Medium 3000K

- 05.7116.B1
- 05.7116.GL
- 05.7116.74




Luminous flux luminaire
2222 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	8281	0.48
2	2070	0.97
3	920	1.45
4	518	1.93
5	331	2.41

Optic Flood 3000K

- 05.7117.B1
- 05.7117.GL
- 05.7117.74



Luminous flux luminaire
2407 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 51°


h(m)	E(lx)	D(m)
1	3654	0.96
2	914	1.91
3	406	2.87
4	228	3.82
5	146	4.78

Kap Ø105 Adjustable

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.


- 05.7135.B1
- 05.7135.GL
- 05.7135.74

Kap Ø105 Adjustable

LED PAR 16 GZ10







Recessed luminaire with main voltage source.
Not suitable for lens accessories.
Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red.
Accesorios de lentes no disponibles.
Marco de pre-instalación. Se ha de pedir por separado.

- 05.7136.B1
- 05.7136.GL
- 05.7136.74

Kap Ø105 Wall-Washer

LED Array DC 650 mA - 23W - 2690 lm - 2700K/CRI 90 / 23W - 2870 lm - 3000K/CRI 90





GWT 850°
LED INCL.
0,48 Kg
III
h=134 min
IP 54

Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Transformador electrónico 220/240V remoto no incluido. Marco de pre-instalación. Se ha de pedir por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 1-10V	60.9439
Dimmable Dali 2	60.7709
Casambi	60.9207
Mains Dimming	60.9692

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 05.7120.B1
- 05.7120.GL
- 05.7120.74




Luminous flux luminaire
1621 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	4671	0.58
2	1168	1.15
3	519	1.73
4	292	2.31
5	187	2.89

3000K

- 05.7121.B1
- 05.7121.GL
- 05.7121.74



Luminous flux luminaire
2151 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	6196	0.58
2	1549	1.15
3	688	1.73
4	387	2.31
5	248	2.89

Kap Ø105 Wall-Washer

LED QR-CBC 51 GX5.3





GWT 850°
0,12 Kg
III
h=130 min
IP 54


Recessed 12V LED lamp luminaire. Remote transformer not included. Not suitable for lens accessories. Pre-installation frame. To be ordered separately.


Luminaria empotrable para lámpara LED de 12V. Transformador remoto no incluido. Accesorios de lentes no disponibles. Marco de pre-instalación. Se ha de pedir por separado.

- 05.7140.B1
- 05.7140.GL
- 05.7140.74

Kap Ø105 Wall-Washer

LED PAR 16 GZ10





GWT 850°
0,12 Kg
h=155 min
IP 54

Recessed luminaire with main voltage source. Not suitable for lens accessories. Pre-installation frame. To be ordered separately.


Luminaria empotrable con alimentación directa a red. Accesorios de lentes no disponibles. Marco de pre-instalación. Se ha de pedir por separado.


- 05.7141.B1
- 05.7141.GL
- 05.7141.74

Kap Ø105 Deep

LED Array DC 650 mA - 23W - 2690 lm - 2700K/CRI 90 / 23W - 2870 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Pre-installation frame. To be ordered separately.

Luminaria empotrable para fuente de luz LED. Transformador electrónico 220/240V remoto no incluido.
Marco de pre-instalación. Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 1-10V	60.9439
Dimmable Dali 2	60.7709
Casambi	60.9207
Mains Dimming	60.9692

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7150.B1
- 05.7150.GL
- 05.7150.74

16° SPOT



Luminous flux luminaire 1602 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 16°

h(m)	E(lx)	D(m)
1	12548	0.29
2	3137	0.57
3	1394	0.86
4	784	1.14
5	502	1.43

Optic Medium 2700K

- 05.7151.B1
- 05.7151.GL
- 05.7151.74

24° MEDIUM



Luminous flux luminaire 1537 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	7579	0.42
2	1895	0.84
3	842	1.26
4	474	1.69
5	303	2.11

Optic Flood 2700K

- 05.7152.B1
- 05.7152.GL
- 05.7152.74

37° FLOOD



Luminous flux luminaire 1581 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 37°

h(m)	E(lx)	D(m)
1	3818	0.68
2	954	1.36
3	424	2.03
4	239	2.71
5	153	3.39

Optic Spot 3000K

- 05.7155.B1
- 05.7155.GL
- 05.7155.74

16° SPOT



Luminous flux luminaire 1836 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 16°

h(m)	E(lx)	D(m)
1	14597	0.28
2	3649	0.56
3	1622	0.84
4	912	1.13
5	584	1.41

Optic Medium 3000K

- 05.7156.B1
- 05.7156.GL
- 05.7156.74

24° MEDIUM



Luminous flux luminaire 1759 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	8701	0.42
2	2175	0.84
3	967	1.26
4	544	1.68
5	348	2.10

Optic Flood 3000K

- 05.7157.B1
- 05.7157.GL
- 05.7157.74

37° FLOOD







Luminous flux luminaire 1795 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	4354	0.68
2	1089	1.35
3	484	2.03
4	272	2.71
5	174	3.38


Accessories / Accesorios


Installation frame No Trim. Kap ø50.	Marco de instalación No Trim. Kap ø50.		Kap ø50 Round ☐ 08.9114.00
Installation frame No Trim. Kap ø80/ø80 Plus	Marco de instalación No Trim. Kap ø80/ø80 Plus.		Kap ø80 Round ☐ 08.9102.00
Installation frame No Trim. Kap 80 Square/80 Plus Square.	Marco de instalación No Trim. Kap 80 Square/80 Plus Square.		Kap 80 Square ☐ 08.9103.00
Installation frame No Trim. Kap ø105 Deep.	Marco de instalación No Trim. Kap ø105 Deep.		Kap ø105 Deep ☐ 08.9104.00
Installation frame No Trim. Kap ø105.	Marco de instalación No Trim. Kap ø105.		Kap ø105 ☐ 08.0132.00
Installation frame No Trim. Kap 105 Square.	Marco de instalación No Trim. Kap 105 Square.		Kap 105 Square ☐ 08.8479.00
Installation can for concrete. Kap ø105 Deep.	Can de instalación para hormigón. Kap ø105 Deep		Kap ø105 Deep ☐ 08.8420.00

Easy Kap Ø30 Fixed

Power LED DC 900 mA - 3W - 222 lm - 2700K/CRI 90 / 3W - 229 lm - 3000K/CRI 90
Driver pass-through. Power LED DC 700 mA - 3,2W - 174 lm - 2700K/CRI 90 / 3,2W - 199 lm - 3000K/CRI 90








Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Marco de instalación no necesario.



Recommended power supply / Equipos recomendados*:


		Serial Con.	⚠
Non Dimmable 220-240V 700mA	60.9988	1	A
Non Dimmable 220-240V 900mA	60.9958	1 - 11	B
Dali 2 220-240V 900mA	60.9602	1 - 5	B
Dali 2 220-240V 900mA	60.9957	3 - 11	B
1-10V 220-240V 900mA	60.9414	1 - 5	B
1-10V 110-127 / 220-240 900mA	60.9208	2 - 5	B
Casambi 220-240V 900mA	06.1974.00	1 - 5	B
Mains Dimming 220-240V 900mA	60.9467	2 - 7	B
Mains Dimming 220-240V 900mA	60.9692	4 - 9	B

* Refer to the Drivers chapter / Ver capítulo Drivers

** Minimum embedding height 65mm only for 30mm ceiling thickness /
Altura mínima de empotramiento 65mm sólo para espesor de techo de 30mm

Optic Spot
2700K

Set of 1 spot
- 05.7600.B1A
- 05.7600.GLA
- 05.7600.74A



Luminous flux luminaire
212 lm

@White (B1)


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	1261	0.34
2	315	0.67
3	140	1.01
4	79	1.34
5	50	1.68

Set of 4 spots
- 05.7620.B1A
- 05.7620.GLA
- 05.7620.74A

Optic Medium
2700K

Set of 1 spot
- 05.7601.B1A
- 05.7601.GLA
- 05.7601.74A



Luminous flux luminaire
209 lm

@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	801	0.47
2	200	0.93
3	89	1.40
4	50	1.86
5	32	2.33

Set of 4 spots
- 05.7621.B1A
- 05.7621.GLA
- 05.7621.74A

3000K

Set of 1 spot
- 05.7605.B1A
- 05.7605.GLA
- 05.7605.74A



Luminous flux luminaire
218 lm

@White (B1)


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	1297	0.34
2	324	0.67
3	144	1.01
4	81	1.34
5	52	1.68

Set of 4 spots
- 05.7625.B1A
- 05.7625.GLA
- 05.7625.74A

3000K

Set of 1 spot
- 05.7606.B1A
- 05.7606.GLA
- 05.7606.74A



Luminous flux luminaire
215 lm

@White (B1)

Beam Angle: 26°


h(m)	E(lx)	D(m)
1	824	0.47
2	206	0.93
3	92	1.40
4	52	1.86
5	33	2.33

Set of 4 spots
- 05.7626.B1A
- 05.7626.GLA
- 05.7626.74A

Optic Flood
2700K

Set of 1 spot
05.7602.B1A
05.7602.GLA
05.7602.74A





Luminous flux luminaire
197 lm

@White (B1)


Beam Angle:		34°
h(m)	E(lx)	D(m)
1	475	0.62
2	119	1.23
3	53	1.85
4	30	2.47
5	19	3.09

Set of 4 spots
05.7622.B1A
05.7622.GLA
05.7622.74A

Optic Wide Flood
2700K

Set of 1 spot
05.7603.B1A
05.7603.GLA
05.7603.74A





Luminous flux luminaire
179 lm

@White (B1)


Beam Angle:		53°
h(m)	E(lx)	D(m)
1	234	1.00
2	59	2.00
3	26	3.01
4	15	4.01
5	9	5.01

Set of 4 spots
05.7623.B1A
05.7623.GLA
05.7623.74A

3000K

Set of 1 spot
05.7607.B1A
05.7607.GLA
05.7607.74A





Luminous flux luminaire
203 lm

@White (B1)


Beam Angle:		34°
h(m)	E(lx)	D(m)
1	490	0.62
2	122	1.23
3	54	1.85
4	31	2.47
5	20	3.09

Set of 4 spots
05.7627.B1A
05.7627.GLA
05.7627.74A

3000K

Set of 1 spot
05.7608.B1A
05.7608.GLA
05.7608.74A





Luminous flux luminaire
185 lm

@White (B1)


Beam Angle:		53°
h(m)	E(lx)	D(m)
1	242	1.00
2	60	2.00
3	27	3.01
4	15	4.01
5	10	5.01


Set of 4 spots
05.7628.B1A
05.7628.GLA
05.7628.74A

Easy Kap Ø30 Adjustable

Power LED DC 900 mA - 3W - 222 lm - 2700K/CRI 90 / 3W - 229 lm - 3000K/CRI 90
Driver pass-through. Power LED DC 700 mA - 3,2W - 174 lm - 2700K/CRI 90 / 3,2W - 199 lm - 3000K/CRI 90








Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Marco de instalación no necesario.



Recommended power supply / Equipos recomendados*:


		Serial Con.	⚠
Non Dimmable 220-240V 700mA	60.9988	1	A
Non Dimmable 220-240V 900mA	60.9958	1 - 11	B
Dali 2 220-240V 900mA	60.9602	1 - 5	B
Dali 2 220-240V 900mA	60.9957	3 - 11	B
1-10V 220-240V 900mA	60.9414	1 - 5	B
1-10V 110-127 / 220-240 900mA	60.9208	2 - 5	B
Casambi 220-240V 900mA	06.1974.00	1 - 5	B
Mains Dimming 220-240V 900mA	60.9467	2 - 7	B
Mains Dimming 220-240V 900mA	60.9692	4 - 9	B

* Refer to the Drivers chapter / Ver capítulo Drivers

** Minimum embedding height 65mm only for 30mm ceiling thickness /
Altura mínima de empotramiento 65mm sólo para espesor de techo de 30mm

Optic Spot
2700K

Set of 1 spot
- 05.7610.B1A
- 05.7610.GLA
- 05.7610.74A



Beam Angle: 19°

h(m)	E(lx)	D(m)
1	1182	0.34
2	296	0.68
3	131	1.02
4	74	1.36
5	47	1.70


Luminous flux luminaire
212 lm

@White (B1)

Set of 4 spots
- 05.7630.B1A
- 05.7630.GLA
- 05.7630.74A

Optic Medium
2700K

Set of 1 spot
- 05.7611.B1A
- 05.7611.GLA
- 05.7611.74A



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	772	0.47
2	193	0.94
3	86	1.40
4	48	1.87
5	31	2.34


Luminous flux luminaire
207 lm

@White (B1)

Set of 4 spots
- 05.7631.B1A
- 05.7631.GLA
- 05.7631.74A

3000K

Set of 1 spot
- 05.7615.B1A
- 05.7615.GLA
- 05.7615.74A



Beam Angle: 19°

h(m)	E(lx)	D(m)
1	1216	0.34
2	304	0.68
3	135	1.02
4	76	1.36
5	49	1.70


Luminous flux luminaire
218 lm

@White (B1)

Set of 4 spots
- 05.7635.B1A
- 05.7635.GLA
- 05.7635.74A

3000K

Set of 1 spot
- 05.7616.B1A
- 05.7616.GLA
- 05.7616.74A



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	794	0.47
2	199	0.94
3	88	1.40
4	50	1.87
5	32	2.34

Luminous flux luminaire
213 lm

@White (B1)


Set of 4 spots
- 05.7636.B1A
- 05.7636.GLA
- 05.7636.74A

Optic Flood
2700K

Set of 1 spot

05.7612.B1A
05.7612.GLA
05.7612.74A





Luminous flux luminaire
197 lm

@White (B1)

Beam Angle:		35°
h(m)	E(lx)	D(m)
1	472	0.62
2	118	1.24
3	52	1.87
4	29	2.49
5	19	3.11

Set of 4 spots


05.7632.B1A
05.7632.GLA
05.7632.74A

Optic Wide Flood
2700K

Set of 1 spot

05.7613.B1A
05.7613.GLA
05.7613.74A





Luminous flux luminaire
182 lm

@White (B1)

Beam Angle:		51°
h(m)	E(lx)	D(m)
1	256	0.96
2	64	1.91
3	28	2.87
4	16	3.82
5	10	4.78

Set of 4 spots


05.7633.B1A
05.7633.GLA
05.7633.74A

3000K

Set of 1 spot

05.7617.B1A
05.7617.GLA
05.7617.74A





Luminous flux luminaire
203 lm

@White (B1)

Beam Angle:		35°
h(m)	E(lx)	D(m)
1	486	0.62
2	121	1.24
3	54	1.87
4	30	2.49
5	19	3.11

Set of 4 spots


05.7637.B1A
05.7637.GLA
05.7637.74A

3000K

Set of 1 spot

05.7618.B1A
05.7618.GLA
05.7618.74A





Luminous flux luminaire
187 lm

@White (B1)

Beam Angle:		51°
h(m)	E(lx)	D(m)
1	263	0.96
2	66	1.91
3	29	2.87
4	16	3.82
5	11	4.78


Set of 4 spots


05.7638.B1A
05.7638.GLA
05.7638.74A

Easy Kap Ø50 Fixed

LED Array DC 200 mA - 7,5W - 595 lm - 2700K/CRI 90 / 7,5W - 635 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Marco de instalación no necesario.

Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9160
Dimmable 0-10V	60.9483
Dimmable Dali	60.9604
Mains Dimming	60.9949
Casambi	60.9392 + DALI/1-10V Driver


* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7200.B1
- 05.7200.GL
- 05.7200.74

Optic Spot 2700K - IP65

- 05.7220.B1
- 05.7220.GL
- 05.7220.74



Luminous flux luminaire 543 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	15°
h(m)	E(lx) D(m)
1	5025 0.27
2	1256 0.53
3	558 0.80
4	314 1.07
5	201 1.33

Optic Spot 3000K

- 05.7205.B1
- 05.7205.GL
- 05.7205.74

Optic Spot 3000K - IP65

- 05.7226.B1
- 05.7226.GL
- 05.7226.74



Luminous flux luminaire 583 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	15°
h(m)	E(lx) D(m)
1	5398 0.27
2	1349 0.53
3	600 0.80
4	337 1.07
5	216 1.33

Optic Medium 2700K

- 05.7201.B1
- 05.7201.GL
- 05.7201.74

Optic Medium 2700K - IP65

- 05.7223.B1
- 05.7223.GL
- 05.7223.74



Luminous flux luminaire 488 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	24°
h(m)	E(lx) D(m)
1	2032 0.43
2	508 0.86
3	226 1.30
4	127 1.73
5	81 2.16

Optic Medium 3000K

- 05.7206.B1
- 05.7206.GL
- 05.7206.74

Optic Medium 3000K - IP65

- 05.7225.B1
- 05.7225.GL
- 05.7225.74



Luminous flux luminaire 524 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	24°
h(m)	E(lx) D(m)
1	2183 0.43
2	546 0.86
3	243 1.30
4	136 1.73
5	87 2.16

Optic Flood 2700K

- 05.7202.B1
- 05.7202.GL
- 05.7202.74

Optic Flood 2700K - IP65

- 05.7224.B1
- 05.7224.GL
- 05.7224.74



Luminous flux luminaire 496 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	49°
h(m)	E(lx) D(m)
1	720 0.91
2	180 1.83
3	80 2.74
4	45 3.66
5	29 4.57

Optic Flood 3000K

- 05.7207.B1
- 05.7207.GL
- 05.7207.74

Optic Flood 3000K - IP65

- 05.7222.B1
- 05.7222.GL
- 05.7222.74




Luminous flux luminaire 532 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	49°
h(m)	E(lx) D(m)
1	774 0.91
2	193 1.83
3	86 2.74
4	48 3.66
5	31 4.57

Easy Kap Ø50 Adjustable

LED Array DC 200 mA - 7,5W - 595 lm - 2700K/CRI 90 / 7,5W - 635 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.
Marco de instalación no necesario.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9160
Dimmable 0-10V	60.9483
Dimmable Dali	60.9604
Mains Dimming	60.9949
Casambi	60.9392 + DALI/1-10V Driver

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7210.B1
- 05.7210.GL
- 05.7210.74

15° SPOT



Luminous flux luminaire 543 lm (EXTREME CUT OFF) @White (B1)


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5025	0.27
2	1256	0.53
3	558	0.80
4	314	1.07
5	201	1.33

Optic Medium 2700K

- 05.7211.B1
- 05.7211.GL
- 05.7211.74

24° MEDIUM



Luminous flux luminaire 488 lm (EXTREME CUT OFF) @White (B1)


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	2032	0.43
2	508	0.86
3	226	1.30
4	127	1.73
5	81	2.16

Optic Flood 2700K

- 05.7212.B1
- 05.7212.GL
- 05.7212.74

49° FLOOD



Luminous flux luminaire 496 lm (EXTREME CUT OFF) @White (B1)


Beam Angle: 49°

h(m)	E(lx)	D(m)
1	720	0.91
2	180	1.83
3	80	2.74
4	45	3.66
5	29	4.57

Optic Spot 3000K

- 05.7215.B1
- 05.7215.GL
- 05.7215.74

15° SPOT



Luminous flux luminaire 583 lm (EXTREME CUT OFF) @White (B1)


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5398	0.27
2	1349	0.53
3	600	0.80
4	337	1.07
5	216	1.33

Optic Medium 3000K

- 05.7216.B1
- 05.7216.GL
- 05.7216.74

24° MEDIUM



Luminous flux luminaire 524 lm (EXTREME CUT OFF) @White (B1)


Beam Angle: 24°

h(m)	E(lx)	D(m)
1	2183	0.43
2	546	0.86
3	243	1.30
4	136	1.73
5	87	2.16

Optic Flood 3000K

- 05.7217.B1
- 05.7217.GL
- 05.7217.74

49° FLOOD



Luminous flux luminaire 532 lm (EXTREME CUT OFF) @White (B1)


Beam Angle: 49°


h(m)	E(lx)	D(m)
1	774	0.91
2	193	1.83
3	86	2.74
4	48	3.66
5	31	4.57

Easy Kap Ø80 - Fixed

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario. Lente difusora incluida.

Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207


* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 03.4288.B1
- 03.4288.GL
- 03.4288.74

Optic Spot 2700K - IP65

- 05.7700.B1
- 05.7700.GL
- 05.7700.74



Luminous flux luminaire 710 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 19°


h(m)	E(lx)	D(m)
1	2684	0.34
2	671	0.68
3	298	1.02
4	168	1.36
5	107	1.70

Optic Spot 3000K

- 03.4287.B1
- 03.4287.GL
- 03.4287.74

Optic Spot 3000K - IP65

- 05.7705.B1
- 05.7705.GL
- 05.7705.74



Luminous flux luminaire 739 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 19°


h(m)	E(lx)	D(m)
1	2792	0.34
2	698	0.68
3	310	1.02
4	175	1.36
5	112	1.70

Optic Medium 2700K

- 03.4193.B1
- 03.4193.GL
- 03.4193.74

Optic Medium 2700K - IP65

- 05.7701.B1
- 05.7701.GL
- 05.7701.74



Luminous flux luminaire 606 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 26°


h(m)	E(lx)	D(m)
1	1796	0.46
2	449	0.92
3	200	1.39
4	112	1.85
5	72	2.31

Optic Medium 3000K

- 03.4192.B1
- 03.4192.GL
- 03.4192.74

Optic Medium 3000K - IP65

- 05.7706.B1
- 05.7706.GL
- 05.7706.74



Luminous flux luminaire 630 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 26°


h(m)	E(lx)	D(m)
1	1868	0.46
2	467	0.92
3	208	1.39
4	117	1.85
5	75	2.31

Optic Flood 2700K

- 03.4298.B1
- 03.4298.GL
- 03.4298.74

Optic Flood 2700K - IP65

- 05.7702.B1
- 05.7702.GL
- 05.7702.74



Luminous flux luminaire 688 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 50°


h(m)	E(lx)	D(m)
1	1066	0.93
2	266	1.86
3	118	2.79
4	67	3.72
5	43	4.65

Optic Flood 3000K

- 03.4297.B1
- 03.4297.GL
- 03.4297.74

Optic Flood 3000K - IP65

- 05.7707.B1
- 05.7707.GL
- 05.7707.74



Luminous flux luminaire 715 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 50°


h(m)	E(lx)	D(m)
1	1108	0.93
2	277	1.86
3	123	2.79
4	69	3.72
5	44	4.65

NEW

Easy Kap Ø80 Plus - Fixed

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90





GWT 850°

0.24 Kg

III

LED INCL

h=150 min

IP 54

IP 65

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario. Lente difusora incluida.

Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers


Optic Spot 2700K

- 05.7441.B1
- 05.7441.GL
- 05.7441.74

Optic Spot 2700K - IP65

- 05.7710.B1
- 05.7710.GL
- 05.7710.74

19° SPOT



Luminous flux luminaire 1050 lm (EXTREME CUT OFF)

@White (B1)

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	3968	0.34
2	992	0.68
3	441	1.02
4	248	1.36
5	159	1.70


Optic Spot 3000K

- 05.7440.B1
- 05.7440.GL
- 05.7440.74

Optic Spot 3000K - IP65

- 05.7715.B1
- 05.7715.GL
- 05.7715.74

19° SPOT



Luminous flux luminaire 1079 lm (EXTREME CUT OFF)

@White (B1)

Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4078	0.34
2	1019	0.68
3	453	1.02
4	255	1.36
5	163	1.70


Optic Medium 2700K

- 05.7431.B1
- 05.7431.GL
- 05.7431.74

Optic Medium 2700K - IP65

- 05.7711.B1
- 05.7711.GL
- 05.7711.74

26° MEDIUM



Luminous flux luminaire 896 lm (EXTREME CUT OFF)

@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2655	0.46
2	664	0.92
3	295	1.39
4	166	1.85
5	106	2.31


Optic Medium 3000K

- 05.7430.B1
- 05.7430.GL
- 05.7430.74

Optic Medium 3000K - IP65

- 05.7716.B1
- 05.7716.GL
- 05.7716.74

26° MEDIUM



Luminous flux luminaire 921 lm (EXTREME CUT OFF)

@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2728	0.46
2	682	0.92
3	303	1.39
4	170	1.85
5	109	2.31


Optic Flood 2700K

- 05.7447.B1
- 05.7447.GL
- 05.7447.74

Optic Flood 2700K - IP65

- 05.7712.B1
- 05.7712.GL
- 05.7712.74

50° FLOOD



Luminous flux luminaire 1017 lm (EXTREME CUT OFF)

@White (B1)

Beam Angle: 50°

h(m)	E(lx)	D(m)
1	1575	0.93
2	394	1.86
3	175	2.79
4	98	3.72
5	63	4.65


Optic Flood 3000K

- 05.7446.B1
- 05.7446.GL
- 05.7446.74

Optic Flood 3000K - IP65

- 05.7717.B1
- 05.7717.GL
- 05.7717.74

50° FLOOD



Luminous flux luminaire 1045 lm (EXTREME CUT OFF)

@White (B1)


Beam Angle: 50°


h(m)	E(lx)	D(m)
1	1619	0.93
2	405	1.86
3	180	2.79
4	101	3.72
5	65	4.65

Easy Kap Ø80 Fixed - Dim To Warm

LED Array 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Installation frame not necessary.
Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Marco de instalación no necesario.
Lente difusora incluida.

Optic Spot
1800K-2850K
- 03.4287.B1.LE
- 03.4287.GL.LE
- 03.4287.74.LE






Luminous flux luminaire
740 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	2805	0.35
2	701	0.69
3	312	1.04
4	175	1.39
5	112	1.74

Optic Medium
1800K-2850K
- 03.4192.B1.LE
- 03.4192.GL.LE
- 03.4192.74.LE






Luminous flux luminaire
735 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	2015	0.49
2	504	0.98
3	224	1.46
4	126	1.95
5	81	2.44

Optic Flood
1800K-2850K
- 03.4297.B1.LE
- 03.4297.GL.LE
- 03.4297.74.LE





Luminous flux luminaire
729 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 49°


h(m)	E(lx)	D(m)
1	1127	0.92
2	282	1.83
3	125	2.75
4	70	3.67
5	45	4.59

Easy Kap 80 Square - Fixed

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario.
Lente difusora incluida.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 03.4177.B1
- 03.4177.GL
- 03.4177.74




Luminous flux luminaire
741 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	18°	
h(m)	E(lx)	D(m)
1	2656	0.31
2	664	0.62
3	295	0.94
4	166	1.25
5	106	1.56

Optic Medium 2700K

- 03.4195.B1
- 03.4195.GL
- 03.4195.74




Luminous flux luminaire
615 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	1605	0.45
2	401	0.90
3	178	1.34
4	100	1.79
5	64	2.24

Optic Flood 2700K

- 03.4179.B1
- 03.4179.GL
- 03.4179.74




Luminous flux luminaire
723 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	55°	
h(m)	E(lx)	D(m)
1	921	1.03
2	230	2.07
3	102	3.10
4	58	4.14
5	37	5.17

Optic Spot 3000K

- 03.4176.B1
- 03.4176.GL
- 03.4176.74




Luminous flux luminaire
771 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	18°	
h(m)	E(lx)	D(m)
1	2762	0.31
2	691	0.62
3	307	0.94
4	173	1.25
5	110	1.56

Optic Medium 3000K

- 03.4194.B1
- 03.4194.GL
- 03.4194.74




Luminous flux luminaire
640 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	1670	0.45
2	417	0.90
3	186	1.34
4	104	1.79
5	67	2.24

Optic Flood 3000K

- 03.4178.B1
- 03.4178.GL
- 03.4178.74




Luminous flux luminaire
752 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	55°	
h(m)	E(lx)	D(m)
1	958	1.03
2	240	2.07
3	106	3.10
4	60	4.14
5	38	5.17

Easy Kap 80 Square Plus - Fixed

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario.
Lente difusora incluida.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7407.B1
- 05.7407.GL
- 05.7407.74




Luminous flux luminaire
1096 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	18°
h(m)	E(lx) D(m)
1	3926 0.31
2	981 0.62
3	436 0.94
4	245 1.25
5	157 1.56

Optic Medium 2700K

- 05.7433.B1
- 05.7433.GL
- 05.7433.74




Luminous flux luminaire
910 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	25°
h(m)	E(lx) D(m)
1	2373 0.45
2	593 0.90
3	264 1.34
4	148 1.79
5	95 2.24

Optic Flood 2700K

- 05.7409.B1
- 05.7409.GL
- 05.7409.74




Luminous flux luminaire
1069 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	55°
h(m)	E(lx) D(m)
1	1362 1.03
2	340 2.07
3	151 3.10
4	85 4.14
5	54 5.17

Optic Spot 3000K

- 05.7406.B1
- 05.7406.GL
- 05.7406.74




Luminous flux luminaire
1126 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	18°
h(m)	E(lx) D(m)
1	4034 0.31
2	1009 0.62
3	448 0.94
4	252 1.25
5	161 1.56

Optic Medium 3000K

- 05.7432.B1
- 05.7432.GL
- 05.7432.74




Luminous flux luminaire
935 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	25°
h(m)	E(lx) D(m)
1	2439 0.45
2	610 0.90
3	271 1.34
4	152 1.79
5	98 2.24

Optic Flood 3000K

- 05.7408.B1
- 05.7408.GL
- 05.7408.74




Luminous flux luminaire
1099 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	55°
h(m)	E(lx) D(m)
1	1399 1.03
2	350 2.07
3	155 3.10
4	87 4.14
5	56 5.17

Easy Kap 80 Square Fixed - Dim To Warm

LED Array 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Installation frame not necessary.
Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Marco de instalación no necesario.
Lente difusora incluida.

Optic Spot
1800K-2850K
- 03.4176.B1.LE
- 03.4176.GL.LE
- 03.4176.74.LE






Luminous flux luminaire
753 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2620	0.32
2	655	0.64
3	291	0.96
4	164	1.28
5	105	1.60

Optic Medium
1800K-2850K
- 03.4194.B1.LE
- 03.4194.GL.LE
- 03.4194.74.LE






Luminous flux luminaire
750 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	1827	0.48
2	457	0.96
3	203	1.45
4	114	1.93
5	73	2.41

Optic Flood
1800K-2850K
- 03.4178.B1.LE
- 03.4178.GL.LE
- 03.4178.74.LE





Luminous flux luminaire
736 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 54°


h(m)	E(lx)	D(m)
1	952	1.02
2	238	2.04
3	106	3.06
4	59	4.08
5	38	5.10

Easy Kap Ø80 Fixed

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido. Marco de instalación no necesario.
Accesorios de lentes no disponibles.


- 03.4210.B1
- 03.4210.GL
- 03.4210.74

Easy Kap 80 Square Fixed

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido. Marco de instalación no necesario.
Accesorios de lentes no disponibles.


- 03.4208.B1
- 03.4208.GL
- 03.4208.74

Easy Kap Ø80 Fixed

LED PAR 16 GZ10








Recessed luminaire with main voltage source.Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable con alimentación directa a red.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.


- 03.4211.B1
- 03.4211.GL
- 03.4211.74

Easy Kap 80 Square Fixed

LED PAR 16 GZ10







Recessed luminaire with main voltage source.Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable con alimentación directa a red.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.


- 03.4209.B1
- 03.4209.GL
- 03.4209.74

Easy Kap Ø80 - Adjustable

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario.
Lente difusora incluida.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 03.4153.B1
- 03.4153.GL
- 03.4153.74

18° SPOT



Luminous flux luminaire 704 lm (EXTREME CUT OFF)

@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2811	0.33
2	703	0.66
3	312	0.99
4	176	1.33
5	112	1.66

Optic Medium 2700K

- 03.4155.B1
- 03.4155.GL
- 03.4155.74

26° MEDIUM



Luminous flux luminaire 664 lm (EXTREME CUT OFF)

@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1864	0.47
2	466	0.93
3	207	1.40
4	116	1.87
5	75	2.33

Optic Flood 2700K

- 03.4157.B1
- 03.4157.GL
- 03.4157.74

47° FLOOD



Luminous flux luminaire 688 lm (EXTREME CUT OFF)

@White (B1)


Beam Angle: 47°

h(m)	E(lx)	D(m)
1	1063	0.94
2	266	1.89
3	118	2.83
4	66	3.77
5	43	4.71

Optic Spot 3000K

- 03.4170.B1
- 03.4170.GL
- 03.4170.74

18° SPOT



Luminous flux luminaire 732 lm (EXTREME CUT OFF)

@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2924	0.33
2	731	0.66
3	325	0.99
4	183	1.33
5	117	1.66

Optic Medium 3000K

- 03.4171.B1
- 03.4171.GL
- 03.4171.74

26° MEDIUM



Luminous flux luminaire 691 lm (EXTREME CUT OFF)

@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1939	0.47
2	485	0.93
3	215	1.40
4	121	1.87
5	78	2.33

Optic Flood 3000K

- 03.4172.B1
- 03.4172.GL
- 03.4172.74

47° FLOOD



Luminous flux luminaire 716 lm (EXTREME CUT OFF)

@White (B1)


Beam Angle: 47°


h(m)	E(lx)	D(m)
1	1106	0.94
2	276	1.89
3	123	2.83
4	69	3.77
5	44	4.71

Easy Kap Ø80 Plus - Adjustable

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario.
Lente difusora incluida.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7400.B1
- 05.7400.GL
- 05.7400.74

19° SPOT



Luminous flux luminaire 1040 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4156	0.33
2	1039	0.66
3	462	0.99
4	260	1.33
5	166	1.66

Optic Medium 2700K

- 05.7401.B1
- 05.7401.GL
- 05.7401.74

26° MEDIUM



Luminous flux luminaire 982 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2756	0.47
2	689	0.93
3	306	1.40
4	172	1.87
5	110	2.33

Optic Flood 2700K

- 05.7402.B1
- 05.7402.GL
- 05.7402.74

50° FLOOD



Luminous flux luminaire 1017 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 50°

h(m)	E(lx)	D(m)
1	1571	0.94
2	393	1.89
3	175	2.83
4	98	3.77
5	63	4.71

Optic Spot 3000K

- 05.7403.B1
- 05.7403.GL
- 05.7403.74

19° SPOT



Luminous flux luminaire 1069 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4271	0.33
2	1068	0.66
3	475	0.99
4	267	1.33
5	171	1.66

Optic Medium 3000K

- 05.7404.B1
- 05.7404.GL
- 05.7404.74

26° MEDIUM



Luminous flux luminaire 1009 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	2832	0.47
2	708	0.93
3	315	1.40
4	177	1.87
5	113	2.33

Optic Flood 3000K

- 05.7405.B1
- 05.7405.GL
- 05.7405.74

50° FLOOD



Luminous flux luminaire 1045 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 50°


h(m)	E(lx)	D(m)
1	1615	0.94
2	404	1.89
3	179	2.83
4	101	3.77
5	65	4.71

Easy Kap Ø80 Adjustable - Dim To Warm

LED Array 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Installation frame not necessary.
Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Marco de instalación no necesario.
Lente difusora incluida.

Optic Spot
1800K-2850K
- 03.4170.B1.LE
- 03.4170.GL.LE
- 03.4170.74.LE






Luminous flux luminaire
716 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2844	0.31
2	711	0.63
3	316	0.94
4	178	1.25
5	114	1.56

Optic Medium
1800K-2850K
- 03.4171.B1.LE
- 03.4171.GL.LE
- 03.4171.74.LE






Luminous flux luminaire
722 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	1953	0.48
2	488	0.97
3	217	1.45
4	122	1.94
5	78	2.42

Optic Flood
1800K-2850K
- 03.4172.B1.LE
- 03.4172.GL.LE
- 03.4172.74.LE





Luminous flux luminaire
707 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 51°


h(m)	E(lx)	D(m)
1	1081	0.94
2	270	1.89
3	120	2.83
4	68	3.78
5	43	4.72

Easy Kap 80 Square - Adjustable

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario.
Lente difusora incluida.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 03.4294.B1
- 03.4294.GL
- 03.4294.74

18° SPOT




Luminous flux luminaire
738 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	18°	
h(m)	E(lx)	D(m)
1	2730	0.31
2	682	0.62
3	303	0.93
4	171	1.24
5	109	1.55

Optic Medium 2700K

- 03.4201.B1
- 03.4201.GL
- 03.4201.74

25° MEDIUM




Luminous flux luminaire
630 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	1692	0.44
2	423	0.88
3	188	1.32
4	106	1.76
5	68	2.20

Optic Flood 2700K

- 03.4296.B1
- 03.4296.GL
- 03.4296.74

53° FLOOD




Luminous flux luminaire
722 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	53°	
h(m)	E(lx)	D(m)
1	986	0.99
2	246	1.98
3	110	2.98
4	62	3.97
5	39	4.96

Optic Spot 3000K

- 03.4293.B1
- 03.4293.GL
- 03.4293.74

18° SPOT




Luminous flux luminaire
768 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	18°	
h(m)	E(lx)	D(m)
1	2840	0.31
2	710	0.62
3	316	0.93
4	177	1.24
5	114	1.55

Optic Medium 3000K

- 03.4200.B1
- 03.4200.GL
- 03.4200.74

25° MEDIUM




Luminous flux luminaire
656 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	25°	
h(m)	E(lx)	D(m)
1	1760	0.44
2	440	0.88
3	196	1.32
4	110	1.76
5	70	2.20

Optic Flood 3000K

- 03.4295.B1
- 03.4295.GL
- 03.4295.74

53° FLOOD




Luminous flux luminaire
751 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	53°	
h(m)	E(lx)	D(m)
1	1025	0.99
2	256	1.98
3	114	2.98
4	64	3.97
5	41	4.96

Easy Kap 80 Square Plus - Adjustable

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario.
Lente difusora incluida.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7443.B1
- 05.7443.GL
- 05.7443.74

18° SPOT



Luminous flux luminaire
1092 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	4036	0.31
2	1009	0.62
3	448	0.93
4	252	1.24
5	161	1.55

Optic Medium 2700K

- 05.7439.B1
- 05.7439.GL
- 05.7439.74

25° MEDIUM



Luminous flux luminaire
932 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	2501	0.44
2	625	0.88
3	278	1.32
4	156	1.76
5	100	2.20

Optic Flood 2700K

- 05.7445.B1
- 05.7445.GL
- 05.7445.74

53° FLOOD



Luminous flux luminaire
1068 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 53°

h(m)	E(lx)	D(m)
1	1457	0.99
2	364	1.98
3	162	2.98
4	91	3.97
5	58	4.96

Optic Spot 3000K

- 05.7442.B1
- 05.7442.GL
- 05.7442.74

18° SPOT



Luminous flux luminaire
1122 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	4147	0.31
2	1037	0.62
3	461	0.93
4	259	1.24
5	166	1.55

Optic Medium 3000K

- 05.7438.B1
- 05.7438.GL
- 05.7438.74

25° MEDIUM



Luminous flux luminaire
958 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 25°

h(m)	E(lx)	D(m)
1	2570	0.44
2	643	0.88
3	286	1.32
4	161	1.76
5	103	2.20

Optic Flood 3000K

- 05.7444.B1
- 05.7444.GL
- 05.7444.74

53° FLOOD



Luminous flux luminaire
1097 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 53°


h(m)	E(lx)	D(m)
1	1497	0.99
2	374	1.98
3	166	2.98
4	94	3.97
5	60	4.96

Easy Kap 80 Square Adjustable - Dim To Warm

LED Array 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Installation frame not necessary.
Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Marco de instalación no necesario.
Lente difusora incluida.

Optic Spot
1800K-2850K
- 03.4293.B1.LE
- 03.4293.GL.LE
- 03.4293.74.LE






Luminous flux luminaire
754 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2629	0.31
2	657	0.63
3	292	0.94
4	164	1.26
5	105	1.57

Optic Medium
1800K-2850K
- 03.4200.B1.LE
- 03.4200.GL.LE
- 03.4200.74.LE






Luminous flux luminaire
752 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1844	0.47
2	461	0.94
3	205	1.41
4	115	1.88
5	74	2.35

Optic Flood
1800K-2850K
- 03.4295.B1.LE
- 03.4295.GL.LE
- 03.4295.74.LE





Luminous flux luminaire
732 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 53°


h(m)	E(lx)	D(m)
1	965	1.01
2	241	2.01
3	107	3.02
4	60	4.03
5	39	5.03

Easy Kap Ø80 Adjustable

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido. Marco de instalación no necesario.
Accesorios de lentes no disponibles.


03.4160.B1
03.4160.GL
03.4160.74

Easy Kap 80 Square Adjustable

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido. Marco de instalación no necesario.
Accesorios de lentes no disponibles.


03.4212.B1
03.4212.GL
03.4212.74

Easy Kap Ø80 Adjustable

LED PAR 16 GZ10







Recessed luminaire with main voltage source. Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable con alimentación directa a red. Marco de instalación no necesario.
Accesorios de lentes no disponibles.


03.4162.B1
03.4162.GL
03.4162.74

Easy Kap 80 Square Adjustable

LED PAR 16 GZ10







Recessed luminaire with main voltage source. Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable con alimentación directa a red. Marco de instalación no necesario.
Accesorios de lentes no disponibles.


03.4213.B1
03.4213.GL
03.4213.74

Easy Kap Ø80 - Wall-Washer

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Elliptical lens included.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario. Lente elíptica incluida.

Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers


2700K
- 03.4197.B1
- 03.4197.GL
- 03.4197.74



Luminous flux luminaire
598 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	28°	
h(m)	E(lx)	D(m)
1	911	0.62
2	228	1.24
3	101	1.87
4	57	2.49
5	36	3.11

3000K
- 03.4196.B1
- 03.4196.GL
- 03.4196.74




Luminous flux luminaire
622 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	28°	
h(m)	E(lx)	D(m)
1	947	0.62
2	237	1.24
3	105	1.87
4	59	2.49
5	38	3.11

Easy Kap Ø80 Plus - Wall-Washer

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Elliptical lens included.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario. Lente elíptica incluida.

Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers


2700K
- 05.7435.B1
- 05.7435.GL
- 05.7435.74



Luminous flux luminaire
884 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	28°	
h(m)	E(lx)	D(m)
1	1347	0.62
2	337	1.24
3	150	1.87
4	84	2.49
5	54	3.11

3000K
- 05.7434.B1
- 05.7434.GL
- 05.7434.74




Luminous flux luminaire
908 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	28°	
h(m)	E(lx)	D(m)
1	1384	0.62
2	346	1.24
3	154	1.87
4	86	2.49
5	55	3.11

Easy Kap Ø80 Wall-Washer - Dim To Warm

LED Array 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Installation frame not necessary.
Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Marco de instalación no necesario.
Lente difusora incluida.

1800K-2850K

- 03.4196.B1.LE
- 03.4196.GL.LE
- 03.4196.74.LE





Luminous flux luminaire
770 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle: 28°


h(m)	E(lx)	D(m)
1	1240	0.64
2	310	1.29
3	138	1.93
4	78	2.58
5	50	3.22

Easy Kap 80 Square - Wall-Washer

LED Array DC 500 mA - 9,2W - 935 lm - 2700K/CRI 90 / 9,2W - 974 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Elliptical lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario. Lente elíptica incluida.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 03.4199.B1
- 03.4199.GL
- 03.4199.74




Luminous flux luminaire
625 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle:	27°	
h(m)	E(lx)	D(m)
1	1125	0.62
2	281	1.24
3	125	1.85
4	70	2.47
5	45	3.09

3000K

- 03.4198.B1
- 03.4198.GL
- 03.4198.74




Luminous flux luminaire
650 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle:	27°	
h(m)	E(lx)	D(m)
1	1170	0.62
2	292	1.24
3	130	1.85
4	73	2.47
5	47	3.09

Easy Kap 80 Square Plus - Wall-Washer

LED Array DC 700 mA - 13W - 1370 lm - 2700K/CRI 90 / 13W - 1460 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Elliptical lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Marco de instalación no necesario. Lente elíptica incluida.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 05.7437.B1
- 05.7437.GL
- 05.7437.74




Luminous flux luminaire
924 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle:	27°	
h(m)	E(lx)	D(m)
1	1663	0.62
2	416	1.24
3	185	1.85
4	104	2.47
5	67	3.09

3000K

- 05.7436.B1
- 05.7436.GL
- 05.7436.74




Luminous flux luminaire
950 lm [EXTREME CUT OFF]
@White (B1)


Beam Angle:	27°	
h(m)	E(lx)	D(m)
1	1709	0.62
2	427	1.24
3	190	1.85
4	107	2.47
5	68	3.09

Easy Kap 80 Square Wall-Washer - Dim To Warm

LED Array 13W - 1023 lm - 1800K - 2850K/CRI 95 - Dim To Warm








Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.
For 110V PSU versions, please consult with the front office.
Installation frame not necessary.
Diffusing lens included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación 220-240V y dimable 1-10V incluida.
Para versiones con equipos 110V preguntar al Front office.
Marco de instalación no necesario.
Lente difusora incluida.

1800K-2850K
- 03.4198.B1.LE
- 03.4198.GL.LE
- 03.4198.74.LE






Luminous flux luminaire
723 lm [EXTREME CUT OFF]
@White (B1)

Beam Angle:		28°
h(m)	E(lx)	D(m)
1	1199	0.68
2	300	1.37
3	133	2.05
4	75	2.74
5	48	3.42

Easy Kap Ø80 Wall-Washer

LED QR-CBC 51 GX5.3








Recessed 12V lamp luminaire.
Remote transformer not included.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido. Marco de instalación no necesario.
Accesorios de lentes no disponibles.

- 03.4220.B1
- 03.4220.GL
- 03.4220.74

Easy Kap 80 Square Wall-Washer

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido. Marco de instalación no necesario.
Accesorios de lentes no disponibles.

- 03.4218.B1
- 03.4218.GL
- 03.4218.74

Easy Kap Ø80 Wall-Washer

LED PAR 16 GZ10







Recessed luminaire with main voltage source. Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable con alimentación directa a red.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.

- 03.4221.B1
- 03.4221.GL
- 03.4221.74

Easy Kap 80 Square Wall-Washer

LED PAR 16 GZ10








Recessed luminaire with main voltage source. Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable con alimentación directa a red.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.


- 03.4219.B1
- 03.4219.GL
- 03.4219.74

Easy Kap Ø105 Fixed

LED Array DC 650 mA - 23W - 2690 lm - 2700K/CRI 90 / 23W - 2870 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Remote transformer not included.
Installation frame not necessary.

Luminaria empotrable para fuente de luz LED.Transformador remoto no incluido.
Marco de instalación no necesario.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 1-10V	60.9439
Dimmable Dali 2	60.7709
Casambi	60.9207
Mains Dimming	60.9692

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7000.B1
- 05.7000.GL
- 05.7000.74




Luminous flux luminaire 1715 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	10889	0.30
2	2722	0.59
3	1210	0.89
4	681	1.18
5	436	1.48

Optic Medium 2700K

- 05.7001.B1
- 05.7001.GL
- 05.7001.74




Luminous flux luminaire 1675 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	6243	0.48
2	1561	0.97
3	694	1.45
4	390	1.93
5	250	2.41

Optic Flood 2700K

- 05.7002.B1
- 05.7002.GL
- 05.7002.74




Luminous flux luminaire 1815 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 51°

h(m)	E(lx)	D(m)
1	2755	0.96
2	689	1.91
3	306	2.87
4	172	3.82
5	110	4.78

Optic Spot 3000K

- 05.7005.B1
- 05.7005.GL
- 05.7005.74




Luminous flux luminaire 2275 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	14445	0.30
2	3611	0.59
3	1605	0.89
4	903	1.18
5	578	1.48

Optic Medium 3000K

- 05.7006.B1
- 05.7006.GL
- 05.7006.74




Luminous flux luminaire 2222 lm (EXTREME CUT OFF) @White (B1)

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	8281	0.48
2	2070	0.97
3	920	1.45
4	518	1.93
5	331	2.41

Optic Flood 3000K

- 05.7007.B1
- 05.7007.GL
- 05.7007.74



Luminous flux luminaire 2407 lm (EXTREME CUT OFF) @White (B1)


Beam Angle: 51°

h(m)	E(lx)	D(m)
1	3654	0.96
2	914	1.91
3	406	2.87
4	228	3.82
5	146	4.78

Easy Kap Ø105 Fixed EVO

LED QR-CBC 51 GX5.3





Recessed 12V lamp luminaire.
Remote transformer not included.
To replace the bulb, the luminaire must be removed.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Para sustituir la bombilla hay que extraer la liminaria.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.

- 05.7030.B1
- 05.7030.GL
- 05.7030.74

Easy Kap Ø105 Fixed EVO

LED PAR 16 GZ10





Recessed luminaire with main voltage source.
To replace the bulb, the luminaire must be removed.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable con alimentación directa a red.
Para sustituir la bombilla hay que extraer la liminaria.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.


- 05.7031.B1
- 05.7031.GL
- 05.7031.74

Easy Kap Ø105 Adjustable

LED Array DC 650 mA - 23W - 2690 lm - 2700K/CRI 90 / 23W - 2870 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Remote transformer not included.
Installation frame not necessary.

Luminaria empotrable para fuente de luz LED.Transformador remoto no incluido.
Marco de instalación no necesario.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 1-10V	60.9439
Dimmable Dali 2	60.7709
Casambi	60.9207
Mains Dimming	60.9692

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot 2700K

- 05.7010.B1
- 05.7010.GL
- 05.7010.74

17° SPOT



Luminous flux luminaire
1715 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 17°

h(m)	E(lx)	D(m)
1	10889	0.30
2	2722	0.59
3	1210	0.89
4	681	1.18
5	436	1.48

Optic Medium 2700K

- 05.7011.B1
- 05.7011.GL
- 05.7011.74

27° MEDIUM



Luminous flux luminaire
1675 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 27°

h(m)	E(lx)	D(m)
1	6243	0.48
2	1561	0.97
3	694	1.45
4	390	1.93
5	250	2.41

Optic Flood 2700K

- 05.7012.B1
- 05.7012.GL
- 05.7012.74

51° FLOOD



Luminous flux luminaire
1815 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 51°

h(m)	E(lx)	D(m)
1	2755	0.96
2	689	1.91
3	306	2.87
4	172	3.82
5	110	4.78

Optic Spot 3000K

- 05.7015.B1
- 05.7015.GL
- 05.7015.74

17° SPOT



Luminous flux luminaire
2275 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 17°

h(m)	E(lx)	D(m)
1	14445	0.30
2	3611	0.59
3	1605	0.89
4	903	1.18
5	578	1.48

Optic Medium 3000K

- 05.7016.B1
- 05.7016.GL
- 05.7016.74

27° MEDIUM



Luminous flux luminaire
2222 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 27°

h(m)	E(lx)	D(m)
1	8281	0.48
2	2070	0.97
3	920	1.45
4	518	1.93
5	331	2.41

Optic Flood 3000K

- 05.7017.B1
- 05.7017.GL
- 05.7017.74

51° FLOOD



Luminous flux luminaire
2407 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 51°


h(m)	E(lx)	D(m)
1	3654	0.96
2	914	1.91
3	406	2.87
4	228	3.82
5	146	4.78

Easy Kap Ø105 Adjustable

LED QR-CBC 51 GX5.3







Recessed 12V lamp luminaire.
Remote transformer not included.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.


- 05.7035.B1
- 05.7035.GL
- 05.7035.74

Easy Kap Ø105 Adjustable

LED PAR 16 GZ10







Recessed luminaire with main voltage source.
Marco de instalación no necesario.
Not suitable for lens accessories.


Luminaria empotrable con alimentación directa a red.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.

- 05.7036.B1
- 05.7036.GL
- 05.7036.74

Easy Kap Ø105 Wall-Washer

LED Array DC 650 mA - 23W - 2690 lm - 2700K/CRI 90 / 23W - 2870 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Installation frame not necessary.

Luminaria empotrable para fuente de luz LED. Transformador electrónico 220/240V remoto no incluido.
Marco de instalación no necesario.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 1-10V	60.9439
Dimmable Dali 2	60.7709
Casambi	60.9207
Mains Dimming	60.9692

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot
2700K

- 05.7020.B1
- 05.7020.GL
- 05.7020.74





Luminous flux luminaire
1621 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 26°

h(m)	E(lx)	D(m)
1	4671	0.58
2	1168	1.15
3	519	1.73
4	292	2.31
5	187	2.89

Optic Spot
3000K

- 05.7021.B1
- 05.7021.GL
- 05.7021.74





* Luminous flux luminaire
1898 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle: 28°

h(m)	E(lx)	D(m)
1	4214	0.63
2	1054	1.26
3	468	1.89
4	263	2.52
5	169	3.16

Easy Kap Ø105 Wall-Washer

LED QR-CBC 51 GX5.3








Recessed 12V lamp luminaire.
Remote transformer not included.
Installation frame not necessary.
Not suitable for lens accessories.


Luminaria empotrable para lámpara de 12V. Transformador remoto no incluido.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.

- 05.7040.B1
- 05.7040.GL
- 05.7040.74

Easy Kap Ø105 Wall-Washer

LED PAR 16 GZ10







Recessed luminaire with main voltage source.
Installation frame not necessary.
Not suitable for lens accessories.

Luminaria empotrable con alimentación directa a red.
Marco de instalación no necesario.
Accesorios de lentes no disponibles.

- 05.7041.B1
- 05.7041.GL
- 05.7041.74

BON JOUR

DESIGNED BY PHILIPPE STARCK

BON JOUR Ø45	BON JOUR Ø90	BON JOUR Ø145
		
LIGHT SOURCE POWER LED 6W 524 lm 2700K/CRI 90 605 lm 3000K/CRI 90	**LIGHT SOURCE** LED ARRAY 13,5W 1500 lm 2700K/CRI 90 16W 2093 lm 3000K/CRI 90	**LIGHT SOURCE** LED ARRAY 36W 3847 lm 2700K/CRI 90 3840 lm 3000K/CRI 90

☐ 01 White
01 Blanco

■ 14 Black
14 Negro





Description
LED luminaire for recessed mounting on plasterboard ceilings.
Once installed, the luminaire edge sticks out of the ceiling 10 mm creating a unique and very refined aesthetic effect.
The luminaire´s body is injected with aluminium. It is available in three sizes: Ø45 mm, Ø90 mm and Ø145 mm.
Reflector made of anodized gloss aluminium with diffuser element made of polycarbonate.

Power Supply
Cabling included, ready to be powered by included remote driver.
Dali dimmable version available.
Versions without driver and 110V driver available on request.

Accessories
- Installation frame made from thermoplastic material for installation in suspended ceilings required for the Ø90 mm and Ø145 mm versions (not necessary for Ø45 mm version).
- Honeycomb and cross screening cylinder (included for Ø45 mm version).
- Screening accesories available for the ø145 version, with the same finishes as the decorative Bon Jour luminaire. See the Flos “The Home Collection” catalogue for more information.

Additional Information
IP44 protection grade.
Insulation class II.
Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria LED para ser instalada en falso techo.
Una vez instalado, el borde de la luminaria sobresale del techo 10 mm creando un efecto estético único y refinado.
Cuerpo de la luminaria realizado en aluminio inyectado.
Disponible en tres tamaños: Ø45 mm, Ø90 mm y Ø145 mm.
Reflector de aluminio anodizado brillante con elemento difusor realizado en policarbonato.

Unidades de Alimentación
Cableado incluido, diponible para conectar a equipo remoto.
Versión Dali dimmable disponible.
Versiones sin equipo y con equipo 110V disponibles bajo pedido.

Accesorios
- Marco de instalación realizado en material termoplástico para su instalación en falso techo, necesario para las versiones Ø90 mm y Ø145 mm (no es necesario para la versión de Ø45 mm).
- Accesorios honeycomb y cruceta de apantallamiento (incluidos en la versión de Ø45 mm).
- Accesorios de apantallamiento disponibles para la versión ø145, con los mismos acabados que la luminaria Bon Jour decorativa. Ver el catálogo Flos “The Home Collection” para más detalles.

Información Adicional
Índice de protección IP44.
Clase de aislamiento II.
Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.


Ø45


Ø90 / Ø145

Bon Jour Ø45

Power LED DC 400 mA - 6W - 524 lm - 2700K/CRI 90 / 6W - 605 lm - 3000K/CRI 90








Recessed luminaire with LED light source. Remote 220/240V power supply included. It is necessary to anticipate a space for accessing the driver.

Accessories included (honeycomb and screening crosspiece).

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida. Necesario acceso al driver por registro.

Accesorios incluidos (honeycomb y cruceta de apantallamiento).


2700K
Non Dimmable
☐ 03.2001.01B
Dali Version
☐ 03.2001.01BDA



Luminous flux luminaire
306 lm

Beam Angle:	19°	
h(m)	E(lx)	D(m)
1	2062	0.34
2	516	0.68
3	229	1.02
4	129	1.36
5	82	1.70


3000K
Non Dimmable
☐ 03.2006.01B
Dali Version
☐ 03.2006.01BDA



Luminous flux luminaire
353 lm

Beam Angle:	19°	
h(m)	E(lx)	D(m)
1	2379	0.34
2	595	0.68
3	264	1.02
4	149	1.36
5	95	1.70


2700K
Non Dimmable
■ 03.2001.14B
Dali Version
■ 03.2001.14BDA



Luminous flux luminaire
311 lm

Beam Angle:	19°	
h(m)	E(lx)	D(m)
1	2138	0.34
2	534	0.67
3	238	1.01
4	134	1.34
5	86	1.68

3000K
Non Dimmable
■ 03.2006.14B
Dali Version
■ 03.2006.14BDA




Luminous flux luminaire
359 lm


Beam Angle:	19°	
h(m)	E(lx)	D(m)
1	2468	0.34
2	617	0.67
3	274	1.01
4	154	1.34
5	99	1.68

Bon Jour Ø90

LED Array DC 400 mA - 17,5W - 2040 lm - 2700K/CRI 90 / 17,5W - 2093 lm - 3000K/CRI 90








Recessed luminaire with LED light source. Remote 220/240V power supply included.

Pre-installation frame must be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida.

Marco de pre-instalación. Se ha de pedir por separado.


2700K
Non Dimmable
☐ 03.2003.01A
Dali Version
☐ 03.2003.01ADA



Luminous flux luminaire
885 lm

Beam Angle:	58°	
h(m)	E(lx)	D(m)
1	904	1.11
2	226	2.21
3	100	3.32
4	56	4.42
5	36	5.53


3000K
Non Dimmable
☐ 03.2007.01A
Dali Version
☐ 03.2007.01ADA



Luminous flux luminaire
907 lm

Beam Angle:	58°	
h(m)	E(lx)	D(m)
1	926	1.11
2	232	2.21
3	103	3.32
4	58	4.42
5	37	5.53


2700K
Non Dimmable
■ 03.2003.14A
Dali Version
■ 03.2003.14ADA



Luminous flux luminaire
448 lm

Beam Angle:	58°	
h(m)	E(lx)	D(m)
1	597	1.10
2	149	2.21
3	66	3.31
4	37	4.42
5	24	5.52

3000K
Non Dimmable
■ 03.2007.14A
Dali Version
■ 03.2007.14ADA




Luminous flux luminaire
460 lm


Beam Angle:	58°	
h(m)	E(lx)	D(m)
1	613	1.10
2	153	2.21
3	68	3.31
4	38	4.42
5	25	5.52

Bon Jour Ø145

LED Array DC 900 mA - 36W - 3847 lm - 2700K/CRI 90 / 36W - 3840 lm - 3000K/CRI 90








Recessed luminaire with LED light source. Remote 220/240V power supply included.

Pre-installation frame must be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida.

Marco de pre-instalación. Se ha de pedir por separado.

2700K
Non Dimmable
☐ 03.2005.01A
Dali Version
☐ 03.2005.01ADA




Luminous flux luminaire
1530 lm

Beam Angle: 58°

h(m)	E(lx)	D(m)
1	1528	1.10
2	382	2.20
3	170	3.29
4	96	4.39
5	61	5.49

3000K
Non Dimmable
☐ 03.2008.01A
Dali Version
☐ 03.2008.01ADA




Luminous flux luminaire
1527 lm

Beam Angle: 58°

h(m)	E(lx)	D(m)
1	1525	1.10
2	381	2.20
3	169	3.29
4	95	4.39
5	61	5.49

2700K
Non Dimmable
■ 03.2005.14A
Dali Version
■ 03.2005.14ADA




Luminous flux luminaire
695 lm

Beam Angle: 56°

h(m)	E(lx)	D(m)
1	971	1.05
2	243	2.11
3	108	3.16
4	61	4.22
5	39	5.27

3000K
Non Dimmable
■ 03.2008.14A
Dali Version
■ 03.2008.14ADA



Luminous flux luminaire
693 lm

Beam Angle: 56°

h(m)	E(lx)	D(m)
1	969	1.05
2	242	2.11
3	108	3.16
4	61	4.22
5	39	5.27

Accessories / Accesorios

Bon Jour Ø90

Pre-installation frame. Marco de pre-instalación.		08.8974.00
Honeycomb and screening crosspiece. Honeycomb y cruceta de apantallamiento.		08.8976.14

Bon Jour Ø145

Pre-installation frame. Marco de pre-instalación.		08.8975.00
Honeycomb and screening crosspiece. Honeycomb y cruceta de apantallamiento.		08.8980.14
Decorative screening accessory.		08.8977.00
Accesorio decorativo de apantallamiento.		08.8978.00

UT DOWNLIGHT

DESIGNED BY FLOS ARCHITECTURAL

TRIM / NO TRIM
Ø57



LIGHT SOURCE
LED ARRAY
18W
2000 lm
3000K/CRI 80
Up to 14,7W
1600 lm
3000K/CRI 90
4000K/CRI 90

TRIM / NO TRIM
Ø86



LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
27W
3214 lm
3000K/CRI 80
Up to 26,1W
2656 lm
3000K/CRI 90
2767 lm
4000K/CRI 90


☐ 30 White
30 Blanco



■ 14 Black
14 Negro



Can be rotated 360° and swivelled 90°.
Puede ser rotado 360° y orientado 90°.



Description
Interior lighting for embedded installation with high power LED technology light sources, in Dali and Non Dali versions.
The family is available in two sizes (Ø57 and Ø86).
In an upper position it functions as a downlight, and in a lower position it functions as a swivelling projector.
The optical body of the luminaire is manufactured in high-pressure die-cast aluminium, finished in black or white powder paint.
Remote power kit included.

Power Supply
Not dimmable or dimmable Dali 220-240V, constant current, power supply included.

Accessories
- Screening crosspiece, elliptical lens, flood lens and Honeycomb.
- No Trim installation frame.

Additional Information
IP20 protection grade.
Insulation class II.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria de interior para instalación empotrada con fuentes de luz de tecnología LED de alta potencia y en versión Dali y No Dali.
La familia está disponible en dos tamaños (Ø57 y Ø86).
En posición superior funciona como donwlight y en posición inferior funciona como proyector orientable.
El cuerpo óptico de la luminaria está fabricado en aluminio inyectado a alta presión, acabados en pintura polvo de color blanco o negro.
Equipo de alimentación remoto incluido.

Unidades de Alimentación
Fuente de alimentación de corriente constante no regulable o regulable Dali 220-240V incluida.

Accesorios
- Disponibles cruceta de apantallamiento, lente elíptica, lente Flood y Honeycomb.
- Marco de instalación No Trim.

Información Adicional
Índice de protección IP20.
Clase de aislamiento II.
Instalable sobre superficies normalmente inflamables.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.


Trim


No Trim

Ut Downlight Trim Ø57

LED Array
Non Dimming: 18W - 2000 lm - 3000K/CRI 80 / 14,1W - 1600 lm - 3000K/CRI 90 / 14,1W - 1600 lm - 4000K/CRI 90
Dali: 18W - 2000 lm - 3000K/CRI 80 / 14,7W - 1600 lm - 3000K/CRI 90 / 14,7W - 1600 lm - 4000K/CRI 90








Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220-240V, 50-60Hz incluida.

3000K - CRI 80
Non Dimmable
- 09.4510.30A
- 09.4510.14A

Dali Version
- 09.4510.30ADA
- 09.4510.14ADA

11° SPOT



Luminous flux luminaire 1295 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	14508	0.19
2	3627	0.39
3	1612	0.58
4	907	0.77
5	580	0.97

3000K - CRI 90
Non Dimmable
- 09.4513.30C
- 09.4513.14C

Dali Version
- 09.4513.30CDA
- 09.4513.14CDA

11° SPOT



Luminous flux luminaire 1067 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	11957	0.19
2	2989	0.39
3	1329	0.58
4	747	0.77
5	478	0.97

4000K - CRI 90
Non Dimmable
- 09.4516.30C
- 09.4516.14C

Dali Version
- 09.4516.30CDA
- 09.4516.14CDA

11° SPOT



Luminous flux luminaire 1212 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	13577	0.19
2	3394	0.39
3	1509	0.58
4	849	0.77
5	543	0.97

3000K - CRI 80
Non Dimmable
- 09.4511.30A
- 09.4511.14A

Dali Version
- 09.4511.30ADA
- 09.4511.14ADA

21° MEDIUM



Luminous flux luminaire 981 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5503	0.36
2	1376	0.72
3	611	1.09
4	344	1.45
5	220	1.81

3000K - CRI 90
Non Dimmable
- 09.4514.30C
- 09.4514.14C

Dali Version
- 09.4514.30CDA
- 09.4514.14CDA

21° MEDIUM



Luminous flux luminaire 808 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	4535	0.36
2	1134	0.72
3	504	1.09
4	283	1.45
5	181	1.81

4000K - CRI 90
Non Dimmable
- 09.4517.30C
- 09.4517.14C

Dali Version
- 09.4517.30CDA
- 09.4517.14CDA

21° MEDIUM



Luminous flux luminaire 918 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5149	0.36
2	1287	0.72
3	572	1.09
4	322	1.45
5	206	1.81

3000K - CRI 80
Non Dimmable
- 09.4512.30A
- 09.4512.14A

Dali Version
- 09.4512.30ADA
- 09.4512.14ADA

43° FLOOD



Luminous flux luminaire 995 lm


Beam Angle: 43°

h(m)	E(lx)	D(m)
1	2190	0.79
2	548	1.58
3	243	2.37
4	137	3.16
5	88	3.95

3000K - CRI 90
Non Dimmable
- 09.4515.30C
- 09.4515.14C

Dali Version
- 09.4515.30CDA
- 09.4515.14CDA

43° FLOOD



Luminous flux luminaire 820 lm


Beam Angle: 43°

h(m)	E(lx)	D(m)
1	1805	0.79
2	451	1.58
3	201	2.37
4	113	3.16
5	72	3.95

4000K - CRI 90
Non Dimmable
- 09.4518.30C
- 09.4518.14C

Dali Version
- 09.4518.30CDA
- 09.4518.14CDA

43° FLOOD



Luminous flux luminaire 932 lm


Beam Angle: 43°


h(m)	E(lx)	D(m)
1	2050	0.79
2	512	1.58
3	228	2.37
4	128	3.16
5	82	3.95

Ut Downlight No Trim Ø57

LED Array
Non Dimming: 18W - 2000 lm - 3000K/CRI 80 / 14,1W - 1600 lm - 3000K/CRI 90 / 14,1W - 1600 lm - 4000K/CRI 90
Dali: 18W - 2000 lm - 3000K/CRI 80 / 14,7W - 1600 lm - 3000K/CRI 90 / 14,7W - 1600 lm - 4000K/CRI 90







Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Pre-installation frame must be ordered separately.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220-240V, 50-60Hz incluida.

Marco de pre-instalación. Se ha de pedir por separado.

3000K - CRI 80
Non Dimmable
- 09.4519.30A
- 09.4519.14A

Dali Version
- 09.4519.30ADA
- 09.4519.14ADA

11° SPOT



Luminous flux luminaire
1295 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	14508	0.19
2	3627	0.39
3	1612	0.58
4	907	0.77
5	580	0.97

3000K - CRI 90
Non Dimmable
- 09.4522.30C
- 09.4522.14C

Dali Version
- 09.4522.30CDA
- 09.4522.14CDA

11° SPOT



Luminous flux luminaire
1067 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	11957	0.19
2	2989	0.39
3	1329	0.58
4	747	0.77
5	478	0.97

4000K - CRI 90
Non Dimmable
- 09.4525.30C
- 09.4525.14C

Dali Version
- 09.4525.30CDA
- 09.4525.14CDA

11° SPOT



Luminous flux luminaire
1212 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	13577	0.19
2	3394	0.39
3	1509	0.58
4	849	0.77
5	543	0.97

3000K - CRI 80
Non Dimmable
- 09.4520.30A
- 09.4520.14A

Dali Version
- 09.4520.30ADA
- 09.4520.14ADA

21° MEDIUM



Luminous flux luminaire
981 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5503	0.36
2	1376	0.72
3	611	1.09
4	344	1.45
5	220	1.81

3000K - CRI 90
Non Dimmable
- 09.4523.30C
- 09.4523.14C

Dali Version
- 09.4523.30CDA
- 09.4523.14CDA

21° MEDIUM



Luminous flux luminaire
808 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	4535	0.36
2	1134	0.72
3	504	1.09
4	283	1.45
5	181	1.81

4000K - CRI 90
Non Dimmable
- 09.4526.30C
- 09.4526.14C

Dali Version
- 09.4526.30CDA
- 09.4526.14CDA

21° MEDIUM



Luminous flux luminaire
918 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5149	0.36
2	1287	0.72
3	572	1.09
4	322	1.45
5	206	1.81

3000K - CRI 80
Non Dimmable
- 09.4521.30A
- 09.4521.14A

Dali Version
- 09.4521.30ADA
- 09.4521.14ADA

43° FLOOD



Luminous flux luminaire
995 lm


Beam Angle: 43°

h(m)	E(lx)	D(m)
1	2190	0.79
2	548	1.58
3	243	2.37
4	137	3.16
5	88	3.95

3000K - CRI 90
Non Dimmable
- 09.4524.30C
- 09.4524.14C

Dali Version
- 09.4524.30CDA
- 09.4524.14CDA

43° FLOOD



Luminous flux luminaire
820 lm


Beam Angle: 43°

h(m)	E(lx)	D(m)
1	1805	0.79
2	451	1.58
3	201	2.37
4	113	3.16
5	72	3.95

4000K - CRI 90
Non Dimmable
- 09.4527.30C
- 09.4527.14C

Dali Version
- 09.4527.30CDA
- 09.4527.14CDA

43° FLOOD



Luminous flux luminaire
932 lm


Beam Angle: 43°


h(m)	E(lx)	D(m)
1	2050	0.79
2	512	1.58
3	228	2.37
4	128	3.16
5	82	3.95

Ut Downlight Trim Ø86

LED Array High Performances
Non Dimming: 27W - 3214 lm - 3000K/CRI 80 / 25,3W - 2656 lm - 3000K/CRI 90 / 25,3W - 2767 lm - 4000K/CRI 90
Dali: 27W - 3214 lm - 3000K/CRI 80 / 26,1W - 2656 lm - 3000K/CRI 90 / 26,1W - 2767 lm - 4000K/CRI 90








Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220-240V, 50-60Hz incluida.

3000K - CRI 80
Non Dimmable
09.4910.30A
09.4910.14A
Dali Version
09.4910.30BDA
09.4910.14BDA

12° SPOT




Luminous flux luminaire
2259 lm

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	29106	0.21
2	7277	0.41
3	3234	0.62
4	1819	0.82
5	1164	1.03

4000K - CRI 90
Non Dimmable
09.4916.30C
09.4916.14C
Dali Version
09.4916.30CDA
09.4916.14CDA

12° SPOT




Luminous flux luminaire
1945 lm

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	25058	0.21
2	6265	0.41
3	2784	0.62
4	1566	0.82
5	1002	1.03

3000K - CRI 90
Non Dimmable
09.4913.30C
09.4913.14C
Dali Version
09.4913.30CDA
09.4913.14CDA

12° SPOT




Luminous flux luminaire
1867 lm

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	24053	0.21
2	6013	0.41
3	2673	0.62
4	1503	0.82
5	962	1.03

3000K - CRI 80
Non Dimmable
09.4911.30A
09.4911.14A
Dali Version
09.4911.30BDA
09.4911.14BDA

24° MEDIUM




Luminous flux luminaire
2155 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	9780	0.43
2	2445	0.86
3	1087	1.28
4	611	1.71
5	391	2.14

4000K - CRI 90
Non Dimmable
09.4917.30C
09.4917.14C
Dali Version
09.4917.30CDA
09.4917.14CDA

24° MEDIUM




Luminous flux luminaire
1855 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	8420	0.43
2	2105	0.86
3	936	1.28
4	526	1.71
5	337	2.14

3000K - CRI 90
Non Dimmable
09.4914.30C
09.4914.14C
Dali Version
09.4914.30CDA
09.4914.14CDA

24° MEDIUM




Luminous flux luminaire
1781 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	8082	0.43
2	2020	0.86
3	898	1.28
4	505	1.71
5	323	2.14

3000K - CRI 80
Non Dimmable
09.4912.30A
09.4912.14A
Dali Version
09.4912.30BDA
09.4912.14BDA

37° FLOOD




Luminous flux luminaire
2053 lm

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	5741	0.67
2	1435	1.34
3	638	2.01
4	359	2.69
5	230	3.36

4000K - CRI 90
Non Dimmable
09.4918.30C
09.4918.14C
Dali Version
09.4918.30CDA
09.4918.14CDA

37° FLOOD




Luminous flux luminaire
1768 lm

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	4943	0.67
2	1236	1.34
3	549	2.01
4	309	2.69
5	198	3.36

3000K - CRI 90
Non Dimmable
09.4915.30C
09.4915.14C
Dali Version
09.4915.30CDA
09.4915.14CDA

37° FLOOD



Luminous flux luminaire
1697 lm


Beam Angle: 37°


h(m)	E(lx)	D(m)
1	4745	0.67
2	1186	1.34
3	527	2.01
4	297	2.69
5	190	3.36

Ut Downlight No Trim Ø86

LED Array High Performances
Non Dimming: 27W - 3214 lm - 3000K/CRI 80 / 25,3W - 2656 lm - 3000K/CRI 90 / 25,3W - 2767 lm - 4000K/CRI 90
Dali: 27W - 3214 lm - 3000K/CRI 80 / 26,1W - 2656 lm - 3000K/CRI 90 / 26,1W - 2767 lm - 4000K/CRI 90







Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.


Pre-installation frame must be ordered separately.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220-240V, 50-60Hz incluida.

Marco de pre-instalación. Se ha de pedir por separado.

3000K - CRI 80
Non Dimmable
09.4919.30A
09.4919.14A
Dali Version
09.4919.30BDA
09.4919.14BDA

12° SPOT




Luminous flux luminaire
2259 lm

Beam Angle:	12°
h(m) E(lx)	D(m)
1 29106	0.21
2 7277	0.41
3 3234	0.62
4 1819	0.82
5 1164	1.03

4000K - CRI 90
Non Dimmable
09.4925.30C
09.4925.14C
Dali Version
09.4925.30CDA
09.4925.14CDA

12° SPOT




Luminous flux luminaire
1945 lm

Beam Angle:	12°
h(m) E(lx)	D(m)
1 25058	0.21
2 6265	0.41
3 2784	0.62
4 1566	0.82
5 1002	1.03

3000K - CRI 90
Non Dimmable
09.4922.30C
09.4922.14C
Dali Version
09.4922.30CDA
09.4922.14CDA

12° SPOT




Luminous flux luminaire
1867 lm

Beam Angle:	12°
h(m) E(lx)	D(m)
1 24053	0.21
2 6013	0.41
3 2673	0.62
4 1503	0.82
5 962	1.03

3000K - CRI 80
Non Dimmable
09.4920.30A
09.4920.14A
Dali Version
09.4920.30BDA
09.4920.14BDA

24° MEDIUM




Luminous flux luminaire
2155 lm

Beam Angle:	24°
h(m) E(lx)	D(m)
1 9780	0.43
2 2445	0.86
3 1087	1.28
4 611	1.71
5 391	2.14

4000K - CRI 90
Non Dimmable
09.4926.30C
09.4926.14C
Dali Version
09.4926.30CDA
09.4926.14CDA

24° MEDIUM




Luminous flux luminaire
1855 lm

Beam Angle:	24°
h(m) E(lx)	D(m)
1 8420	0.43
2 2105	0.86
3 936	1.28
4 526	1.71
5 337	2.14

3000K - CRI 90
Non Dimmable
09.4923.30C
09.4923.14C
Dali Version
09.4923.30CDA
09.4923.14CDA

24° MEDIUM




Luminous flux luminaire
1781 lm

Beam Angle:	24°
h(m) E(lx)	D(m)
1 8082	0.43
2 2020	0.86
3 898	1.28
4 505	1.71
5 323	2.14

3000K - CRI 80
Non Dimmable
09.4921.30A
09.4921.14A
Dali Version
09.4921.30BDA
09.4921.14BDA

37° FLOOD




Luminous flux luminaire
2053 lm

Beam Angle:	37°
h(m) E(lx)	D(m)
1 5741	0.67
2 1435	1.34
3 638	2.01
4 359	2.69
5 230	3.36

4000K - CRI 90
Non Dimmable
09.4927.30C
09.4927.14C
Dali Version
09.4927.30CDA
09.4927.14CDA

37° FLOOD




Luminous flux luminaire
1768 lm

Beam Angle:	37°
h(m) E(lx)	D(m)
1 4943	0.67
2 1236	1.34
3 549	2.01
4 309	2.69
5 198	3.36

3000K - CRI 90
Non Dimmable
09.4924.30C
09.4924.14C
Dali Version
09.4924.30CDA
09.4924.14CDA

37° FLOOD




Luminous flux luminaire
1697 lm

Beam Angle:	37°
h(m) E(lx)	D(m)
1 4745	0.67
2 1186	1.34
3 527	2.01
4 297	2.69
5 190	3.36

Accessories / Accesorios

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.
UT Downlight Ø86: Installation compatible with honeycomb + lense at the same time.

Cruceta de apantallamiento, lentes y honeycomb directamente instalables en la cabeza de la luminaria sin necesidad de accesorio de sujeción.
UT Downlight Ø86: Compatibilidad de instalación de honeycomb + lente al mismo tiempo.



UT Downlight Ø57

Installation frame No Trim. Marco de instalación No Trim.		08.8994.30 08.8994.14
Screening crosspiece Cruceta de apantallamiento		08.8429.00
Elliptical lens Lente elíptica		08.8431.00
Flood lens Lente flood For Spot & Medium optics		08.8432.00
Honeycomb Honeycomb		08.8428.00
Snoot shielding cone Cono apantallador	29 	08.0526.00 08.0526.40 08.0526.BW

UT Downlight Ø86

Installation frame No Trim. Marco de instalación No Trim.		08.8995.30 08.8995.14
Holding ring Aro soporte		08.8410.00
Screening crosspiece Cruceta de apantallamiento		08.8411.00
Elliptical lens Lente elíptica		08.8163.68
Flood lens Lente flood For Spot & Medium optics		08.8175.68
Honeycomb Honeycomb		08.8495.14

LIGHT SUPPLY

DESIGNED BY FLOS ARCHITECTURAL

FIXED
TRIM / NO TRIM





LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
29W
3572 lm
3000K/CRI 80
2910 lm
3000K/CRI 90
3164 lm
4000K/CRI 90

ADJUSTABLE
TRIM / NO TRIM





LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
30,1W
3772 lm
3000K/CRI 80
2910 lm
3000K/CRI 90
3153 lm
4000K/CRI 90

WALL-WASHER
TRIM / NO TRIM





LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
33,2W
3959 lm
3000K/CRI 80
3225 lm
3000K/CRI 90
3506 lm
4000K/CRI 90

Light Supply Adjustable

☐ 40 White
40 Blanco



■ 14 Black
14 Negro



Light Supply Fixed & Wall-Washer Trim

External Ring / Anillo Exterior

☐ White
Blanco

■ Black
Negro

Reflector / Reflector

Aluminium
Aluminio

☐ White
Blanco

Aluminium
Aluminio

White
Blanco










Can be rotated 365° and swivelled 35°.
Puede ser rotado 365° y orientado 35°.

Light Supply Adjustable



Description
New downlight family developed to get a maximum flux in a compact design. 165mm diameter offering up to 3000 lm thanks to latest technology LED modules.
Available in fixed, adjustable and wall-washer version.
Adjustable version features a dismountable optic support cylinder, to be easily unscrewed from the luminaire, in order to completely access the electronic and to install the professional accessories available.
To offer maximum flexibility and installation evolution in time, reflector of spot, medium and flood optic are also available as accessories, to change the light beam dimension without even needing to dismount the fixture from the ceiling.
All Light Supply No Trim versions can be mounted in a standard pre-installation metal frame or, for total integration in plasterboard ceiling, in a Soft Technology installation plate.

Reflectors
All super pure aluminum with specular finish. Circular roto symmetrical spot, medium and flood for the adjustable version, flood for the fixed version.

Power Supply
Cabling included, ready to be powered by included remote driver.
Versions without driver and 1-10V dimmable available on request.

Light Source
Possibility to integrate a different type of LED upon request. For more information, please contact our team.

Accessories
For adjustable version:
- Elliptical distribution lens.
- Honeycomb.
- Spare part of spot, medium, flood optics reflectors.
For all No Trim versions:
- Pre-installation frame or Soft Architecture installation plate for adjustable version.

Additional Information
In the adjustable versions, 35° tilt and 365° rotation.
IP23, IP44 protection grade depending on the versions.
Insulation class II.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Nueva familia de empotrables desarrollada para conseguir un flujo máximo de 3000 lm dentro de un diseño compacto de 165mm de diámetro gracias a la última tecnología de módulos LED.
Disponible en versiones fija, ajustable y wall-washer.
La versión ajustable cuenta con una óptica cilíndrica intercambiable para facilitar el acceso a la electrónica e intercambiar los accesorios disponibles.
Para ofrecer la máxima flexibilidad y mejorar la instalación, hay disponibles reflectores con ópticas cerradas, intermedias y abiertas. Intercambio de accesorios sin necesidad de desmontar el producto del techo.
Todas las versiones No Trim pueden ser montadas en marco de pre-instalación o integradas en techo de cartón yeso mediante la tecnología Soft.

Reflectores
Realizados con aluminio en acabado especular. Para la versión ajustable haz de luz cerrado, medio y amplio; para la versión fija aperturas amplias.

Unidades de Alimentación
Cableado incluido, diponible para conectar a equipo remoto. Versiones sin equipo y regulable 1-10V disponibles bajo pedido.

Fuente de luz
Posibilidad de integrar otro tipo de LED bajo demanda. Para más información, no dude en contactar con nuestro equipo.

Accesorios
Para la versión ajustable:
- Lente de distribución elíptica.
- Honeycomb.
- Recambio de reflectores con aperturas cerrada, media y abierta.
Para todas las versiones No Trim:
- Marco de pre-instalación o placa de instalación Soft Architecture para la versión ajustable.

Información Adicional
En las versiones ajustables, basculación de 35° y rotación de 365°.
Índice de protección IP23, IP44 según las versiones.
Clase de aislamiento II.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Fixed / Adjustable / Wall-Washer Trim

Fixed No Trim


Adjustable No Trim


Wall-Washer No Trim

Light Supply Fixed Trim

LED Array High Performances 29W - 3572 lm - 3000K/CRI 80 / 29W - 2910 lm - 3000K/CRI 90 / 29W - 3164 lm - 4000K/CRI 90







Recessed luminaire with LED light source. Remote 220/240V power supply included.

E= External Finish
I= Internal Finish.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida.

E= Acabado Externo
I= Acabado Interno.

3000K - CRI 90

E I Non Dimmable
03.6811.3BA
03.6811.3CA
E I Dali
03.6811.3BBDA
03.6811.3CADA
E I 1-10V
03.6811.3BA1V

62°



Luminous flux luminaire
1487 lm (EXTREME CUT OFF)


@White Reflector

Beam Angle: 62°

h(m)	E(lx)	D(m)
1	1492	1.19
2	373	2.39
3	166	3.58
4	93	4.77
5	60	5.97

E I Non Dimmable
03.6811.1BA
03.6811.1CA
E I Dali
03.6811.1BBDA
03.6811.1CADA
E I 1-10V
03.6811.1BA1V

47°



Luminous flux luminaire
1755 lm (EXTREME CUT OFF)

@Aluminium Reflector


Beam Angle: 47°

h(m)	E(lx)	D(m)
1	2684	0.86
2	671	1.73
3	298	2.59
4	168	3.46
5	107	4.32

4000K - CRI 90

E I Non Dimmable
03.6810.3BA
03.6810.3CA
E I Dali
03.6810.3BBDA
03.6810.3CADA
E I 1-10V
03.6810.3BA1V

62°



Luminous flux luminaire
1549 lm (EXTREME CUT OFF)


@White Reflector

Beam Angle: 62°

h(m)	E(lx)	D(m)
1	1554	1.19
2	389	2.39
3	173	3.58
4	97	4.77
5	62	5.97

E I Non Dimmable
03.6810.1BA
03.6810.1CA
E I Dali
03.6810.1BBDA
03.6810.1CADA
E I 1-10V
03.6810.1BA1V

47°



Luminous flux luminaire
1828 lm (EXTREME CUT OFF)

@Aluminium Reflector


Beam Angle: 47°

h(m)	E(lx)	D(m)
1	2797	0.86
2	699	1.73
3	311	2.59
4	175	3.46
5	112	4.32

3000K - CRI 80

E I Non Dimmable
03.6809.3BA
03.6809.3CA
E I Dali
03.6809.3BBDA
03.6809.3CADA
E I 1-10V
03.6809.3BA1V

62°



Luminous flux luminaire
1799 lm (EXTREME CUT OFF)


@White Reflector

Beam Angle: 62°

h(m)	E(lx)	D(m)
1	1805	1.19
2	451	2.39
3	201	3.58
4	113	4.77
5	72	5.97

E I Non Dimmable
03.6809.1BA
03.6809.1CA
E I Dali
03.6809.1BBDA
03.6809.1CADA
E I 1-10V
03.6809.1BA1V

47°



Luminous flux luminaire
2123 lm (EXTREME CUT OFF)

@Aluminium Reflector


Beam Angle: 47°


h(m)	E(lx)	D(m)
1	3248	0.86
2	812	1.73
3	361	2.59
4	203	3.46
5	130	4.32

Light Supply Fixed No Trim

LED Array High Performances 29W - 3572 lm - 3000K/CRI 80 / 29W - 2910 lm - 3000K/CRI 90 / 29W - 3164 lm - 4000K/CRI 90







Pre-installation frame. To be ordered separately.

Marco de pre-instalación. Se ha de pedir por separado.

3000K - CRI 90

Non Dimmable

- ☐ 03.6826.40A
- ☐ 03.6826.06A


Dali

- ☐ 03.6826.40BDA
- ☐ 03.6826.06ADA

1-10V

- ☐ 03.6826.40A1V

62°




Luminous flux luminaire
1487 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	62°	
h(m)	E(lx)	D(m)
1	1492	1.19
2	373	2.39
3	166	3.58
4	93	4.77
5	60	5.97

47°



Luminous flux luminaire
1755 lm (EXTREME CUT OFF)

@Aluminium Reflector

Beam Angle:	47°	
h(m)	E(lx)	D(m)
1	2684	0.86
2	671	1.73
3	298	2.59
4	168	3.46
5	107	4.32

4000K - CRI 90

Non Dimmable

- ☐ 03.6825.40A
- ☐ 03.6825.06A


Dali

- ☐ 03.6825.40BDA
- ☐ 03.6825.06ADA

1-10V

- ☐ 03.6825.40A1V

62°




Luminous flux luminaire
1549 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	62°	
h(m)	E(lx)	D(m)
1	1554	1.19
2	389	2.39
3	173	3.58
4	97	4.77
5	62	5.97

47°



Luminous flux luminaire
1828 lm (EXTREME CUT OFF)

@Aluminium Reflector

Beam Angle:	47°	
h(m)	E(lx)	D(m)
1	2797	0.86
2	699	1.73
3	311	2.59
4	175	3.46
5	112	4.32

3000K - CRI 80

Non Dimmable

- ☐ 03.6824.40A
- ☐ 03.6824.06A


Dali

- ☐ 03.6824.40BDA
- ☐ 03.6824.06ADA

1-10V

- ☐ 03.6824.40A1V

62°




Luminous flux luminaire
1799 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	62°	
h(m)	E(lx)	D(m)
1	1805	1.19
2	451	2.39
3	201	3.58
4	113	4.77
5	72	5.97

47°



Luminous flux luminaire
2123 lm (EXTREME CUT OFF)


@Aluminium Reflector


Beam Angle:	47°	
h(m)	E(lx)	D(m)
1	3248	0.86
2	812	1.73
3	361	2.59
4	203	3.46
5	130	4.32

Light Supply Adjustable Trim

LED Array High Performances 30,1W - 3772 lm - 3000K CRI 80







Recessed luminaire with LED light source. Remote 220/240V power supply included.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida.

3000K - CRI 80
Non Dimmable
- ☐ 03.6800.40A
- ■ 03.6800.14A

Dali
- ☐ 03.6800.40BDA
- ■ 03.6800.14BDA

1-10V
- ☐ 03.6800.40A1V
- ■ 03.6800.14A1V

13°
SPOT



Luminous flux luminaire
2208 lm (EXTREME CUT OFF)

Beam Angle: 13°


h(m)	E(lx)	D(m)
1	26681	0.23
2	6670	0.46
3	2965	0.69
4	1668	0.92
5	1067	1.15

3000K - CRI 80
Non Dimmable
- ☐ 03.6801.40A
- ■ 03.6801.14A

Dali
- ☐ 03.6801.40BDA
- ■ 03.6801.14BDA

1-10V
- ☐ 03.6801.40A1V
- ■ 03.6801.14A1V

21°
MEDIUM



Luminous flux luminaire
1777 lm (EXTREME CUT OFF)

Beam Angle: 21°


h(m)	E(lx)	D(m)
1	9765	0.37
2	2441	0.75
3	1085	1.12
4	610	1.49
5	391	1.87

3000K - CRI 80
Non Dimmable
- ☐ 03.6802.40A
- ■ 03.6802.14A

Dali
- ☐ 03.6802.40BDA
- ■ 03.6802.14BDA

1-10V
- ☐ 03.6802.40A1V
- ■ 03.6802.14A1V

39°
FLOOD



Luminous flux luminaire
1960 lm (EXTREME CUT OFF)


Beam Angle: 39°


h(m)	E(lx)	D(m)
1	5493	0.71
2	1373	1.42
3	610	2.14
4	343	2.85
5	220	3.56

Light Supply Adjustable No Trim

LED Array High Performances 30,1W - 3772 lm - 3000K CRI 80







Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.


Marco o Placa Soft Architecture para pre-instalación No Trim. Se ha de pedir por separado.

3000K - CRI 80
Non Dimmable
- ☐ 03.6815.40A
- ■ 03.6815.14A

Dali
- ☐ 03.6815.40BDA
- ■ 03.6815.14BDA

1-10V
- ☐ 03.6815.40A1V
- ■ 03.6815.14A1V

13°
SPOT



Luminous flux luminaire
2208 lm (EXTREME CUT OFF)

Beam Angle: 13°


h(m)	E(lx)	D(m)
1	26681	0.23
2	6670	0.46
3	2965	0.69
4	1668	0.92
5	1067	1.15

3000K - CRI 80
Non Dimmable
- ☐ 03.6816.40A
- ■ 03.6816.14A

Dali
- ☐ 03.6816.40BDA
- ■ 03.6816.14BDA

1-10V
- ☐ 03.6816.40A1V
- ■ 03.6816.14A1V

21°
MEDIUM



Luminous flux luminaire
1777 lm (EXTREME CUT OFF)

Beam Angle: 21°


h(m)	E(lx)	D(m)
1	9765	0.37
2	2441	0.75
3	1085	1.12
4	610	1.49
5	391	1.87

3000K - CRI 80
Non Dimmable
- ☐ 03.6817.40A
- ■ 03.6817.14A

Dali
- ☐ 03.6817.40BDA
- ■ 03.6817.14BDA

1-10V
- ☐ 03.6817.40A1V
- ■ 03.6817.14A1V

39°
FLOOD



Luminous flux luminaire
1960 lm (EXTREME CUT OFF)


Beam Angle: 39°


h(m)	E(lx)	D(m)
1	5493	0.71
2	1373	1.42
3	610	2.14
4	343	2.85
5	220	3.56

Light Supply Adjustable Trim

LED Array High Performances 30,1W - 2910 lm - 3000K/CRI 90 / 30,1W - 3153 lm - 4000K/CRI 90







h=239 min

Recessed luminaire with LED light source. Remote 220/240V power supply included.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida.

3000K - CRI 90
Non Dimmable
- ☐ 03.6806.40A
- ■ 03.6806.14A

Dali
- ☐ 03.6806.40BDA
- ■ 03.6806.14BDA

1-10V
- ☐ 03.6806.40A1V
- ■ 03.6806.14A1V

13° SPOT



Luminous flux luminaire 1698 lm [EXTREME CUT OFF)

Beam Angle: 13°


h(m)	E(lx)	D(m)
1	20522	0.23
2	5131	0.46
3	2280	0.69
4	1283	0.92
5	821	1.15

4000K - CRI 90
Non Dimmable
- ☐ 03.6803.40A
- ■ 03.6803.14A

Dali
- ☐ 03.6803.40BDA
- ■ 03.6803.14BDA

1-10V
- ☐ 03.6803.40A1V
- ■ 03.6803.14A1V

13° SPOT



Luminous flux luminaire 1846 lm [EXTREME CUT OFF)

Beam Angle: 13°


h(m)	E(lx)	D(m)
1	22306	0.23
2	5576	0.46
3	2478	0.69
4	1394	0.92
5	892	1.15

3000K - CRI 90
Non Dimmable
- ☐ 03.6807.40A
- ■ 03.6807.14A

Dali
- ☐ 03.6807.40BDA
- ■ 03.6807.14BDA

1-10V
- ☐ 03.6807.40A1V
- ■ 03.6807.14A1V

21° MEDIUM



Luminous flux luminaire 1367 lm [EXTREME CUT OFF)

Beam Angle: 21°


h(m)	E(lx)	D(m)
1	7511	0.37
2	1878	0.75
3	835	1.12
4	469	1.49
5	300	1.87

4000K - CRI 90
Non Dimmable
- ☐ 03.6804.40A
- ■ 03.6804.14A

Dali
- ☐ 03.6804.40BDA
- ■ 03.6804.14BDA

1-10V
- ☐ 03.6804.40A1V
- ■ 03.6804.14A1V

21° MEDIUM



Luminous flux luminaire 1486 lm [EXTREME CUT OFF)

Beam Angle: 21°


h(m)	E(lx)	D(m)
1	8164	0.37
2	2041	0.75
3	907	1.12
4	510	1.49
5	327	1.87

3000K - CRI 90
Non Dimmable
- ☐ 03.6808.40A
- ■ 03.6808.14A

Dali
- ☐ 03.6808.40BDA
- ■ 03.6808.14BDA

1-10V
- ☐ 03.6808.40A1V
- ■ 03.6808.14A1V

39° FLOOD



Luminous flux luminaire 1508 lm [EXTREME CUT OFF)

Beam Angle: 39°


h(m)	E(lx)	D(m)
1	4225	0.71
2	1056	1.42
3	469	2.14
4	264	2.85
5	169	3.56

4000K - CRI 90
Non Dimmable
- ☐ 03.6805.40A
- ■ 03.6805.14A

Dali
- ☐ 03.6805.40BDA
- ■ 03.6805.14BDA

1-10V
- ☐ 03.6805.40A1V
- ■ 03.6805.14A1V

39° FLOOD



Luminous flux luminaire 1639 lm [EXTREME CUT OFF)


Beam Angle: 39°


h(m)	E(lx)	D(m)
1	4592	0.71
2	1148	1.42
3	510	2.14
4	287	2.85
5	184	3.56

Light Supply Adjustable No Trim

LED Array High Performances 30,1W - 2910 lm - 3000K/CRI 90 / 30,1W - 3153 lm - 4000K/CRI 90







Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.


Marco o Placa Soft Architecture para pre-instalación No Trim. Se ha de pedir por separado.

3000K - CRI 90
Non Dimmable
- 03.6821.40A
- 03.6821.14A

Dali
- 03.6821.40BDA
- 03.6821.14BDA

1-10V
- 03.6821.40A1V
- 03.6821.14A1V

13° SPOT



Luminous flux luminaire
1698 lm [EXTREME CUT OFF]

Beam Angle: 13°


h(m)	E(lx)	D(m)
1	20522	0.23
2	5131	0.46
3	2280	0.69
4	1283	0.92
5	821	1.15

4000K - CRI 90
Non Dimmable
- 03.6818.40A
- 03.6818.14A

Dali
- 03.6818.40BDA
- 03.6818.14BDA

1-10V
- 03.6818.40A1V
- 03.6818.14A1V

13° SPOT



Luminous flux luminaire
1846 lm [EXTREME CUT OFF]

Beam Angle: 13°


h(m)	E(lx)	D(m)
1	22306	0.23
2	5576	0.46
3	2478	0.69
4	1394	0.92
5	892	1.15

3000K - CRI 90
Non Dimmable
- 03.6822.40A
- 03.6822.14A

Dali
- 03.6822.40BDA
- 03.6822.14BDA

1-10V
- 03.6822.40A1V
- 03.6822.14A1V

21° MEDIUM



Luminous flux luminaire
1367 lm [EXTREME CUT OFF]

Beam Angle: 21°


h(m)	E(lx)	D(m)
1	7511	0.37
2	1878	0.75
3	835	1.12
4	469	1.49
5	300	1.87

4000K - CRI 90
Non Dimmable
- 03.6819.40A
- 03.6819.14A

Dali
- 03.6819.40BDA
- 03.6819.14BDA

1-10V
- 03.6819.40A1V
- 03.6819.14A1V

21° MEDIUM



Luminous flux luminaire
1486 lm [EXTREME CUT OFF]

Beam Angle: 21°


h(m)	E(lx)	D(m)
1	8164	0.37
2	2041	0.75
3	907	1.12
4	510	1.49
5	327	1.87

3000K - CRI 90
Non Dimmable
- 03.6823.40A
- 03.6823.14A

Dali
- 03.6823.40BDA
- 03.6823.14BDA

1-10V
- 03.6823.40A1V
- 03.6823.14A1V

39° FLOOD



Luminous flux luminaire
1508 lm [EXTREME CUT OFF]

Beam Angle: 39°


h(m)	E(lx)	D(m)
1	4225	0.71
2	1056	1.42
3	469	2.14
4	264	2.85
5	169	3.56

4000K - CRI 90
Non Dimmable
- 03.6820.40A
- 03.6820.14A

Dali
- 03.6820.40BDA
- 03.6820.14BDA

1-10V
- 03.6820.40A1V
- 03.6820.14A1V

39° FLOOD



Luminous flux luminaire
1639 lm [EXTREME CUT OFF]


Beam Angle: 39°


h(m)	E(lx)	D(m)
1	4592	0.71
2	1148	1.42
3	510	2.14
4	287	2.85
5	184	3.56

Light Supply Wall-Washer Trim

LED Array High Performances 33,2W - 3959 lm - 3000K/CRI 80 / 33,2W - 3225 lm - 3000K/CRI 90 / 33,2W - 3506 lm - 4000K/CRI 90







Recessed luminaire with LED light source. Remote 220/240V power supply included.


E= External Finish
I= Internal Finish.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida.

E= Acabado Externo
I= Acabado Interno.

3000K - CRI 90

E I Non Dimmable
03.6814.3BA
03.6814.3CA
E I Dali
03.6814.3BBDA
03.6814.3CBDA
E I 1-10V
03.6814.3BA1V
03.6814.3CA1V




Luminous flux luminaire
1771 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	36°
h(m)	E(lx)	D(m)
1	2092	0.74
2	523	1.48
3	232	2.22
4	131	2.95
5	84	3.69

E I Non Dimmable
03.6814.1BA
03.6814.1CA
E I Dali
03.6814.1BBDA
03.6814.1CBDA
E I 1-10V
03.6814.1BA1V
03.6814.1CA1V




Luminous flux luminaire
1909 lm (EXTREME CUT OFF)

@Aluminium Reflector

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	2588	0.67
2	647	1.35
3	288	2.02
4	162	2.69
5	104	3.37

4000K - CRI 90

E I Non Dimmable
03.6813.3BA
03.6813.3CA
E I Dali
03.6813.3BBDA
03.6813.3CBDA
E I 1-10V
03.6813.3BA1V
03.6813.3CA1V




Luminous flux luminaire
1845 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	36°
h(m)	E(lx)	D(m)
1	2179	0.74
2	545	1.48
3	242	2.22
4	136	2.95
5	87	3.69

E I Non Dimmable
03.6813.1BA
03.6813.1CA
E I Dali
03.6813.1BBDA
03.6813.1CBDA
E I 1-10V
03.6813.1BA1V
03.6813.1CA1V




Luminous flux luminaire
1989 lm (EXTREME CUT OFF)

@Aluminium Reflector

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	2696	0.67
2	674	1.35
3	300	2.02
4	168	2.69
5	108	3.37

3000K - CRI 80

E I Non Dimmable
03.6812.3BA
03.6812.3CA
E I Dali
03.6812.3BBDA
03.6812.3CBDA
E I 1-10V
03.6812.3BA1V
03.6812.3CA1V




Luminous flux luminaire
2142 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	36°
h(m)	E(lx)	D(m)
1	2531	0.74
2	633	1.48
3	281	2.22
4	158	2.95
5	101	3.69

E I Non Dimmable
03.6812.1BA
03.6812.1CA
E I Dali
03.6812.1BBDA
03.6812.1CBDA
E I 1-10V
03.6812.1BA1V
03.6812.1CA1V



Luminous flux luminaire
2310 lm (EXTREME CUT OFF)


@Aluminium Reflector


Beam Angle:	34°
h(m)	E(lx)	D(m)
1	3131	0.67
2	783	1.35
3	348	2.02
4	196	2.69
5	125	3.37

Light Supply Wall-Washer No Trim

LED Array High Performances 33,2W - 3959 lm - 3000K/CRI 80 / 33,2W - 3225 lm - 3000K/CRI 90 / 33,2W - 3506 lm - 4000K/CRI 90







Pre-installation frame. To be ordered separately.

Marco de pre-instalación. Se ha de pedir por separado.

3000K - CRI 90

Non Dimmable


- 03.6829.40A
- 03.6829.06A

Dali

- 03.6829.40BDA
- 03.6829.06BDA

1-10V


- 03.6829.40A1V
- 03.6829.06A1V



Luminous flux luminaire
1771 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	36°
h(m)	E(lx)	D(m)
1	2092	0.74
2	523	1.48
3	232	2.22
4	131	2.95
5	84	3.69



Luminous flux luminaire
1909 lm (EXTREME CUT OFF)

@Aluminium Reflector

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	2588	0.67
2	647	1.35
3	288	2.02
4	162	2.69
5	104	3.37

4000K - CRI 90

Non Dimmable


- 03.6828.40A
- 03.6828.06A

Dali

- 03.6828.40BDA
- 03.6828.06BDA

1-10V


- 03.6828.40A1V
- 03.6828.06A1V



Luminous flux luminaire
1845 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	36°
h(m)	E(lx)	D(m)
1	2179	0.74
2	545	1.48
3	242	2.22
4	136	2.95
5	87	3.69



Luminous flux luminaire
1989 lm (EXTREME CUT OFF)

@Aluminium Reflector

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	2696	0.67
2	674	1.35
3	300	2.02
4	168	2.69
5	108	3.37

3000K - CRI 80

Non Dimmable


- 03.6827.40A
- 03.6827.06A

Dali

- 03.6827.40BDA
- 03.6827.06BDA

1-10V


- 03.6827.40A1V
- 03.6827.06A1V



Luminous flux luminaire
2142 lm (EXTREME CUT OFF)

@White Reflector

Beam Angle:	36°
h(m)	E(lx)	D(m)
1	2531	0.74
2	633	1.48
3	281	2.22
4	158	2.95
5	101	3.69



Luminous flux luminaire
2310 lm (EXTREME CUT OFF)

@Aluminium Reflector

Beam Angle:	34°
h(m)	E(lx)	D(m)
1	3131	0.67
2	783	1.35
3	348	2.02
4	196	2.69
5	125	3.37

Accessories / Accesorios

Pre-installation frame.

Marco de pre-instalación.



Adjustable No Trim
08.8119.00



Fixed No Trim
08.8359.00




Wall-Washer No Trim
08.8137.00

Soft Architecture installation plate for integration in plasterboard.

Placa Soft Architecture para pre-instalación en superficies de cartón yeso.





Adjustable No Trim
SA.6600.1

Accessories / Accesorios

For LED Array

Light Supply Adjustable spare reflector.	Reflector intercambiable para Light Supply Adjustable.		Spot 08.8450.00 Medium 08.8451.00 Flood 08.8452.00
Screening crosspiece.	Cruceta de apantallamiento.		08.8242.14
Elliptical lens.	Lente elíptica.		08.8118.68
Honeycomb.	Honeycomb.		Big Cells/Celdas Grandes 08.8377.14
Highly-efficient cylinder.	Cilindro de alta eficiencia.		08.8453.40 08.8453.14

JOHNNY

DESIGNED BY FLOS ARCHITECTURAL

JOHNNY 80
TRIM / NO TRIM
1L ROUND
1L/2L SQUARE



LIGHT SOURCE
POWER LED
6,2W
560 lm
2700K/CRI 90
600 lm
3000K/CRI 90

JOHNNY 80
SEMI-RECESSED
1L/2L SQUARE



LIGHT SOURCE
POWER LED
6,2W
560 lm
2700K/CRI 90
600 lm
3000K/CRI 90

JOHNNY 120
TRIM / NO TRIM
1L ROUND
1L/2L SQUARE



LIGHT SOURCE
LED ARRAY HIGH PERFORMANCE
20W
2049 lm
2700K/CRI 90
2183 lm
3000K/CRI 90

JOHNNY 120
SEMI-RECESSED
1L/2L SQUARE



LIGHT SOURCE
LED ARRAY
18W
1770 lm
2700K/CRI 90
1870 lm
3000K/CRI 90

Johnny 80
Trim / No Trim



☐ 40 White
40 Blanco

■ 14 Black
14 Negro

Johnny 120
Trim



☐ White
Blanco

■ Black
Negro

Johnny 120
No Trim



■ Black
Negro

Inside / Interior	☐ White Blanco	■ Black Negro	
Outside / Exterior	☐ 40 White 40 Blanco	■ CE Concrete CE Cemento	■ 14 Black 14 Negro

Johnny 80 Semi-Recessed




Johnny 120 Semi-Recessed




Can be rotated in any direction
Puede ser rotado en cualquier dirección.

Johnny 80



Johnny 120



Description
Illumination system consisting of one or two adjustable lights, in the embedded version (Trim and No Trim) and semi-embedded version to be installed on the ceiling.
Available in two sizes: 80 mm and 120 mm in round and square versions.
An exclusive, easy and adjustable system that enables an accurate adjustment of the light beam.

Power Supply
Remote constant power supply 220/240V not included.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Accessories
Johnny 80:
- Screening crosspiece and honeycomb included in the product

Johnny 120:
- Screening crosspiece
- Honeycomb
- Elliptical lens
- Flood lens

Additional Information
The Johnny 80 version has a orientation system integrated into the telescopic body.
IP20 protection grade.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Sistema de iluminación de uno o dos focos orientables, en versión empotrada (Trim y No Trim) y semi-empotrada para ser instalado en techo.
Disponible en dos tamaños: 80 mm y 120 mm en versiones redonda y cuadrada.
Sistema de orientación exclusivo de fácil fijación permitiendo la precisa orientación del haz de luz.

Unidades de Alimentación
Fuente de alimentación de corriente constante 220/240V remota no incluida.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).

Accesorios
Johnny 80:
- Cruceta de apantallamiento y honeycomb incluidos en el producto

Johnny 120:
- Cruceta de apantallamiento
- Honeycomb
- Lente elíptica
- Lente flood

Información Adicional
Sistema de orientación integrado en cuerpo telescópico para la versión Johnny 80.
Índice de protección IP20.
Instalable en superficies normalmente inflamables.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.


Johnny 80 1L Trim
Johnny 80 1L No Trim
Johnny 80 2L Trim
Johnny 80 2L No Trim
Johnny 80 Semi-Recessed
Johnny 120 Trim
Johnny 120 No Trim
Johnny 120 Semi-Recessed

Johnny Ø80 Trim 1L Round

Power LED
Without accessories: DC 500 mA - 6,2W - 560 lm - 2700K/CRI 90 / 6,2W - 600 lm - 3000K/CRI 90
With accessories: DC 450 mA - 5,5W - 505 lm - 2700K/CRI 90 / 5,5W - 540 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included.


Accessories included (honeycomb and screening crosspiece).

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.

Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Johnny Ø80 No Trim 1L Round






Recommended power supply / Equipos recomendados*:

	450 mA	500 mA
Non Dimmable	60.9160	60.9160
Dimmable 0/1-10V	60.9188	60.9188
Dimmable Dali 2	60.9222	60.9222
Mains Dimming	60.9467	60.9467
Casambi	60.9207	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
- 03.0701.40A
- 03.0701.14A
- 03.0701.40ANT
- 03.0701.14ANT

11° SPOT




Luminous flux luminaire
385 lm (EXTREME CUT OFF)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	7360	0.19
2	1840	0.38
3	818	0.57
4	460	0.76
5	294	0.95

3000K
- 03.0700.40A
- 03.0700.14A
- 03.0700.40ANT
- 03.0700.14ANT

11° SPOT




Luminous flux luminaire
399 lm (EXTREME CUT OFF)

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	7629	0.19
2	1907	0.38
3	848	0.57
4	477	0.76
5	305	0.95

2700K
- 03.0705.40A
- 03.0705.14A
- 03.0705.40ANT
- 03.0705.14ANT

21° MEDIUM




Luminous flux luminaire
359 lm (EXTREME CUT OFF)

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1919	0.37
2	480	0.74
3	213	1.12
4	120	1.49
5	77	1.86

3000K
- 03.0704.40A
- 03.0704.14A
- 03.0704.40ANT
- 03.0704.14ANT

21° MEDIUM




Luminous flux luminaire
373 lm (EXTREME CUT OFF)

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1989	0.37
2	497	0.74
3	221	1.12
4	124	1.49
5	80	1.86

2700K
- 03.0709.40A
- 03.0709.14A
- 03.0709.40ANT
- 03.0709.14ANT

31° FLOOD




Luminous flux luminaire
300 lm (EXTREME CUT OFF)

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	963	0.55
2	241	1.10
3	107	1.65
4	60	2.20
5	39	2.75

3000K
- 03.0708.40A
- 03.0708.14A
- 03.0708.40ANT
- 03.0708.14ANT

31° FLOOD



Luminous flux luminaire
311 lm (EXTREME CUT OFF)


Beam Angle: 31°


h(m)	E(lx)	D(m)
1	998	0.55
2	249	1.10
3	111	1.65
4	62	2.20
5	40	2.75

Johnny 80 Trim 1L Square

Power LED
Without accessories: DC 500 mA - 6,2W - 560 lm - 2700K/CRI 90 / 6,2W - 600 lm - 3000K/CRI 90
With accessories: DC 450 mA - 5,5W - 505 lm - 2700K/CRI 90 / 5,5W - 540 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included.


Accessories included (honeycomb and screening crosspiece).

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.

Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Johnny 80 No Trim 1L Square







Recommended power supply / Equipos recomendados*:

	450 mA	500 mA
Non Dimmable	60.9160	60.9160
Dimmable 0/1-10V	60.9188	60.9188
Dimmable Dali 2	60.9222	60.9222
Mains Dimming	60.9467	60.9467
Casambi	60.9207	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
- 03.0703.40A
- 03.0703.14A
- 03.0703.40ANT
- 03.0703.14ANT







Luminous flux luminaire
385 lm [EXTREME CUT OFF]

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	7360	0.19
2	1840	0.38
3	818	0.57
4	460	0.76
5	294	0.95

3000K
- 03.0702.40A
- 03.0702.14A
- 03.0702.40ANT
- 03.0702.14ANT






Luminous flux luminaire
399 lm [EXTREME CUT OFF]

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	7629	0.19
2	1907	0.38
3	848	0.57
4	477	0.76
5	305	0.95

2700K
- 03.0707.40A
- 03.0707.14A
- 03.0707.40ANT
- 03.0707.14ANT






Luminous flux luminaire
359 lm [EXTREME CUT OFF]

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1919	0.37
2	480	0.74
3	213	1.12
4	120	1.49
5	77	1.86

3000K
- 03.0706.40A
- 03.0706.14A
- 03.0706.40ANT
- 03.0706.14ANT







Luminous flux luminaire
373 lm [EXTREME CUT OFF]

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1989	0.37
2	497	0.74
3	221	1.12
4	124	1.49
5	80	1.86

2700K
- 03.0711.40A
- 03.0711.14A
- 03.0711.40ANT
- 03.0711.14ANT







Luminous flux luminaire
300 lm [EXTREME CUT OFF]

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	963	0.55
2	241	1.10
3	107	1.65
4	60	2.20
5	39	2.75

3000K
- 03.0710.40A
- 03.0710.14A
- 03.0710.40ANT
- 03.0710.14ANT





Luminous flux luminaire
311 lm [EXTREME CUT OFF]


Beam Angle: 31°


h(m)	E(lx)	D(m)
1	998	0.55
2	249	1.10
3	111	1.65
4	62	2.20
5	40	2.75

Johnny 80 Trim 2L Square

Power LED
Without accessories: 500 mA - 2x6,2W - 2x560 lm - 2700K/CRI 90 / 2x6,2W - 2x600 lm - 3000K/CRI 90
With accessories: DC 450 mA - 2x5,5W - 2x505 lm - 2700K/CRI 90 / 2x5,5W - 2x540 lm - 3000K/CRI 90







Recessed luminaire with LED light source. Power supply not included. Requires one power supply for each optic body.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Es necesaria una fuente de alimentación por cada cuerpo óptico.

Accessories included (honeycomb and screening crosspiece).

Accesorios incluidos (honeycomb y cruceta de apantallamiento).

Johnny 80 No Trim 2L Square





Pre-installation frame. To be ordered separately.


Marco de pre-instalación Se ha de pedir por separado.

Recommended power supply / Equipos recomendados*:

	450 mA	500 mA
Non Dimmable	60.9160	60.9160
Dimmable 0/1-10V	60.9188	60.9188
Dimmable Dali 2	60.9222	60.9222
Mains Dimming	60.9467	60.9467
Casambi	60.9207	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers


2700K
- ☐ 03.0713.40A
- ■ 03.0713.14A
- ☐ 03.0713.40ANT
- ■ 03.0713.14ANT



Luminous flux luminaire
385 lm (EXTREME CUT OFF)

Beam Angle:	11°
h(m) E(lx)	D(m)
1 7360	0.19
2 1840	0.38
3 818	0.57
4 460	0.76
5 294	0.95


3000K
- ☐ 03.0712.40A
- ■ 03.0712.14A
- ☐ 03.0712.40ANT
- ■ 03.0712.14ANT



Luminous flux luminaire
399 lm (EXTREME CUT OFF)

Beam Angle:	11°
h(m) E(lx)	D(m)
1 7629	0.19
2 1907	0.38
3 848	0.57
4 477	0.76
5 305	0.95


2700K
- ☐ 03.0715.40A
- ■ 03.0715.14A
- ☐ 03.0715.40ANT
- ■ 03.0715.14ANT



Luminous flux luminaire
359 lm (EXTREME CUT OFF)

Beam Angle:	21°
h(m) E(lx)	D(m)
1 1919	0.37
2 480	0.74
3 213	1.12
4 120	1.49
5 77	1.86


3000K
- ☐ 03.0714.40A
- ■ 03.0714.14A
- ☐ 03.0714.40ANT
- ■ 03.0714.14ANT



Luminous flux luminaire
373 lm (EXTREME CUT OFF)

Beam Angle:	21°
h(m) E(lx)	D(m)
1 1989	0.37
2 497	0.74
3 221	1.12
4 124	1.49
5 80	1.86


2700K
- ☐ 03.0717.40A
- ■ 03.0717.14A
- ☐ 03.0717.40ANT
- ■ 03.0717.14ANT



Luminous flux luminaire
300 lm (EXTREME CUT OFF)

Beam Angle:	31°
h(m) E(lx)	D(m)
1 963	0.55
2 241	1.10
3 107	1.65
4 60	2.20
5 39	2.75

3000K
- ☐ 03.0716.40A
- ■ 03.0716.14A
- ☐ 03.0716.40ANT
- ■ 03.0716.14ANT




Luminous flux luminaire
311 lm (EXTREME CUT OFF)


Beam Angle:	31°
h(m) E(lx)	D(m)
1 998	0.55
2 249	1.10
3 111	1.65
4 62	2.20
5 40	2.75

Johnny 80 Semi-Recessed 1L Square

Power LED
Without accessories: DC 500 mA - 6,2W - 560 lm - 2700K/CRI 90 / 6,2W - 600 lm - 3000K/CRI 90
With accessories: DC 450 mA - 5,5W - 505 lm - 2700K/CRI 90 / 5,5W - 540 lm - 3000K/CRI 90







Semi-recessed luminaire with LED light source. Power supply not included.

Accessories included (honeycomb and screening crosspiece).

E= External Finish
I= Internal Finish

Luminaria semi-empotrable para fuente de luz LED. Fuente de alimentación no incluida.

Accesorios incluidos (honeycomb y cruceta de apantallamiento).

E= Acabado Externo
I= Acabado Interno



Recommended power supply / Equipos recomendados*:


	450 mA	500 mA
Non Dimmable	60.9160	60.9160
Dimmable 0/1-10V	60.9188	60.9188
Dimmable Dali 2	60.9222	60.9222
Mains Dimming	60.9467	60.9467
Casambi	60.9207	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

E I **2700K**
03.0761.40A
03.0761.CEA
03.0761.14A

03.0719.40A
03.0719.CEA
03.0719.14A

11° SPOT



Luminous flux luminaire
385 lm [EXTREME CUT OFF]


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	7360	0.19
2	1840	0.38
3	818	0.57
4	460	0.76
5	294	0.95

E I **3000K**
03.0760.40A
03.0760.CEA
03.0760.14A

03.0718.40A
03.0718.CEA
03.0718.14A

11° SPOT



Luminous flux luminaire
399 lm [EXTREME CUT OFF]


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	7629	0.19
2	1907	0.38
3	848	0.57
4	477	0.76
5	305	0.95

E I **2700K**
03.0763.40A
03.0763.CEA
03.0763.14A

03.0721.40A
03.0721.CEA
03.0721.14A

21° MEDIUM



Luminous flux luminaire
359 lm [EXTREME CUT OFF]


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1919	0.37
2	480	0.74
3	213	1.12
4	120	1.49
5	77	1.86

E I **3000K**
03.0762.40A
03.0762.CEA
03.0762.14A

03.0720.40A
03.0720.CEA
03.0720.14A

21° MEDIUM



Luminous flux luminaire
373 lm [EXTREME CUT OFF]


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1989	0.37
2	497	0.74
3	221	1.12
4	124	1.49
5	80	1.86

E I **2700K**
03.0765.40A
03.0765.CEA
03.0765.14A

03.0723.40A
03.0723.CEA
03.0723.14A

31° FLOOD



Luminous flux luminaire
300 lm [EXTREME CUT OFF]


Beam Angle: 31°

h(m)	E(lx)	D(m)
1	963	0.55
2	241	1.10
3	107	1.65
4	60	2.20
5	39	2.75

E I **3000K**
03.0764.40A
03.0764.CEA
03.0764.14A

03.0722.40A
03.0722.CEA
03.0722.14A

31° FLOOD



Luminous flux luminaire
311 lm [EXTREME CUT OFF]


Beam Angle: 31°


h(m)	E(lx)	D(m)
1	998	0.55
2	249	1.10
3	111	1.65
4	62	2.20
5	40	2.75

Johnny 80 Semi-Recessed 2L Square

Power LED
Without accessories: 500 mA - 2x6,2W - 2x560 lm - 2700K/CRI 90 / 2x6,2W - 2x600 lm - 3000K/CRI 90
With accessories: DC 450 mA - 2x5,5W - 2x505 lm - 2700K/CRI 90 / 2x5,5W - 2x540 lm - 3000K/CRI 90







Semi-recessed luminaire with LED light source. Power supply not included. Requires one power supply for each optic body.

Accessories included (honeycomb and screening crosspiece).

E= External Finish
I= Internal Finish

Luminaria semi-empotrable para fuente de luz LED. Fuente de alimentación no incluida. Es necesaria una fuente de alimentación por cada cuerpo óptico.
Accesorios incluidos (honeycomb y cruceta de apantallamiento).

E= Acabado Externo
I= Acabado Interno



Recommended power supply / Equipos recomendados*:


	450 mA	500 mA
Non Dimmable	60.9160	60.9160
Dimmable 0/1-10V	60.9188	60.9188
Dimmable Dali 2	60.9222	60.9222
Mains Dimming	60.9467	60.9467
Casambi	60.9207	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

E I **2700K**
- 03.0771.40A
- 03.0771.CEA
- 03.0771.14A

- 03.0731.40A
- 03.0731.CEA
- 03.0731.14A

11° SPOT



Luminous flux luminaire
385 lm (EXTREME CUT OFF)


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	7360	0.19
2	1840	0.38
3	818	0.57
4	460	0.76
5	294	0.95

E I **3000K**
- 03.0770.40A
- 03.0770.CEA
- 03.0770.14A

- 03.0730.40A
- 03.0730.CEA
- 03.0730.14A

11° SPOT



Luminous flux luminaire
399 lm (EXTREME CUT OFF)


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	7629	0.19
2	1907	0.38
3	848	0.57
4	477	0.76
5	305	0.95

E I **2700K**
- 03.0773.40A
- 03.0773.CEA
- 03.0773.14A

- 03.0733.40A
- 03.0733.CEA
- 03.0733.14A

21° MEDIUM



Luminous flux luminaire
359 lm (EXTREME CUT OFF)


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1919	0.37
2	480	0.74
3	213	1.12
4	120	1.49
5	77	1.86

E I **3000K**
- 03.0772.40A
- 03.0772.CEA
- 03.0772.14A

- 03.0732.40A
- 03.0732.CEA
- 03.0732.14A

21° MEDIUM



Luminous flux luminaire
373 lm (EXTREME CUT OFF)


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1989	0.37
2	497	0.74
3	221	1.12
4	124	1.49
5	80	1.86

E I **2700K**
- 03.0775.40A
- 03.0775.CEA
- 03.0775.14A

- 03.0735.40A
- 03.0735.CEA
- 03.0735.14A

31° FLOOD



Luminous flux luminaire
300 lm (EXTREME CUT OFF)


Beam Angle: 31°

h(m)	E(lx)	D(m)
1	963	0.55
2	241	1.10
3	107	1.65
4	60	2.20
5	39	2.75

E I **3000K**
- 03.0774.40A
- 03.0774.CEA
- 03.0774.14A

- 03.0734.40A
- 03.0734.CEA
- 03.0734.14A

31° FLOOD



Luminous flux luminaire
311 lm (EXTREME CUT OFF)

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	998	0.55
2	249	1.10
3	111	1.65
4	62	2.20
5	40	2.75

Accessories / Accesorios

Johnny 80 No Trim 1L

Installation frame No Trim.
Johnny ø80.

Marco de instalación No Trim.
Johnny ø80.



Johnny ø80 Round
☐ 08.9102.00

Installation frame No Trim.
Johnny □80.

Marco de instalación No Trim.
Johnny □80.



Johnny □80 Square
☐ 08.9103.00

Johnny 80 No Trim 2L Square

Installation frame No Trim.
Johnny 80 2L Square.

Marco de instalación No Trim.
Johnny 80 2L Square.




☐ 08.9105.00

Johnny 120 Light Source

Without accessories: LED Array High Performance DC 500 mA - 20W - 2049 lm - 2700K/CRI 90 / 20W - 2183 lm - 3000K/CRI 90
With accessories: LED Array High Performance DC 450 mA - 18W - 1862 lm - 2700K/CRI 90 / 18W - 1984 lm - 3000K/CRI 90
Without accessories: LED Array DC 500 mA - 18W - 1770 lm - 2700K/CRI 90 / 18W - 1870 lm - 3000K/CRI 90
With accessories: LED Array DC 450 mA - 16W - 1612 lm - 2700K/CRI 90 / 16W - 1704 lm - 3000K/CRI 90





GWT 850°
IP 20
40°
03 **
F
0,65 Kg
IECEE CB SCHEME **
LED INCL.
CE
III

Recessed luminaire with LED light source. Power supply not included. One driver is needed per each light source.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida. Se necesita un equipo por fuente de luz.

**Part number with certificate: 0741 / 0743 / 0745 / 0740 / 0742 / 0744


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9160
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9222
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

High Performance 2700K
☐ 03.0801.40A
■ 03.0801.14A

21° SPOT




Luminous flux luminaire 1814 lm

Beam Angle: 21°		
h(m)	E(lx)	D(m)
1	11214	0.37
2	2804	0.74
3	1246	1.11
4	701	1.48
5	449	1.85

High Performance 3000K
☐ 03.0800.40A
■ 03.0800.14A

21° SPOT




Luminous flux luminaire 1933 lm

Beam Angle: 21°		
h(m)	E(lx)	D(m)
1	11950	0.37
2	2988	0.74
3	1328	1.11
4	747	1.48
5	478	1.85

2700K
☐ 03.0741.40
■ 03.0741.14

13° SPOT




Luminous flux luminaire 1324 lm (EXTREME CUT OFF)

Beam Angle: 13°		
h(m)	E(lx)	D(m)
1	12785	0.22
2	3196	0.44
3	1421	0.66
4	799	0.88
5	511	1.10

3000K
☐ 03.0740.40
■ 03.0740.14

13° SPOT




Luminous flux luminaire 1393 lm (EXTREME CUT OFF)

Beam Angle: 13°		
h(m)	E(lx)	D(m)
1	13445	0.22
2	3361	0.44
3	1494	0.66
4	840	0.88
5	538	1.10

High Performance 2700K
☐ 03.0803.40A
■ 03.0803.14A

27° MEDIUM




Luminous flux luminaire 1544 lm

Beam Angle: 27°		
h(m)	E(lx)	D(m)
1	7075	0.49
2	1769	0.98
3	786	1.47
4	442	1.96
5	283	2.44

High Performance 3000K
☐ 03.0802.40A
■ 03.0802.14A

27° MEDIUM




Luminous flux luminaire 1645 lm

Beam Angle: 27°		
h(m)	E(lx)	D(m)
1	7538	0.49
2	1884	0.98
3	838	1.47
4	471	1.96
5	302	2.44

2700K
☐ 03.0743.40
■ 03.0743.14

22° MEDIUM




Luminous flux luminaire 1222 lm (EXTREME CUT OFF)

Beam Angle: 22°		
h(m)	E(lx)	D(m)
1	6451	0.39
2	1613	0.79
3	717	1.18
4	403	1.58
5	258	1.97

3000K
☐ 03.0742.40
■ 03.0742.14

22° MEDIUM




Luminous flux luminaire 1285 lm (EXTREME CUT OFF)

Beam Angle: 22°		
h(m)	E(lx)	D(m)
1	6784	0.39
2	1696	0.79
3	754	1.18
4	424	1.58
5	271	1.97

High Performance 2700K
☐ 03.0805.40A
■ 03.0805.14A

36° FLOOD




Luminous flux luminaire 1519 lm

Beam Angle: 36°		
h(m)	E(lx)	D(m)
1	4440	0.64
2	1110	1.28
3	493	1.92
4	277	2.56
5	178	3.20

High Performance 3000K
☐ 03.0804.40A
■ 03.0804.14A

36° FLOOD




Luminous flux luminaire 1619 lm

Beam Angle: 36°		
h(m)	E(lx)	D(m)
1	4732	0.64
2	1183	1.28
3	526	1.92
4	296	2.56
5	189	3.20

2700K
☐ 03.0745.40
■ 03.0745.14

41° FLOOD




Luminous flux luminaire 1456 lm (EXTREME CUT OFF)

Beam Angle: 41°		
h(m)	E(lx)	D(m)
1	3499	0.75
2	875	1.50
3	389	2.25
4	219	3.00
5	140	3.75

3000K
☐ 03.0744.40
■ 03.0744.14

41° FLOOD




Luminous flux luminaire 1531 lm (EXTREME CUT OFF)

Beam Angle: 41°		
h(m)	E(lx)	D(m)
1	3680	0.75
2	920	1.50
3	409	2.25
4	230	3.00
5	147	3.75

Johnny 120 Round 1L – Recessed Universal Frame






Unique reference for Trim or No Trim recessed installation.
08.0555.00=includes white frame to complete Trim finishing.
08.0505.00=includes optional white and black frames to complete Trim finishing.


☐ 08.0555.00
+
1x Light Source
+
1x Driver

Referencia única para las instalaciones empotrables Trim o No Trim.
08.0555.00=incluye marco en blanco para completar el acabado Trim.
08.0505.00=incluye marcos opcionales en blanco y negro para completar el acabado Trim.

■ 08.0505.00
+
1x Light Source
+
1x Driver

Johnny 120 Square 1L – Recessed Universal Frame






Unique reference for Trim or No Trim recessed installation.
08.0550.00=includes white frame to complete Trim finishing.
08.0500.00=includes optional white and black frames to complete Trim finishing.


☐ 08.0550.00
+
1x Light Source
+
1x Driver

Referencia única para las instalaciones empotrables Trim o No Trim.
08.0550.00=incluye marco en blanco para completar el acabado Trim.
08.0500.00=incluye marcos opcionales en blanco y negro para completar el acabado Trim.

■ 08.0500.00
+
1x Light Source
+
1x Driver

Johnny 120 Square 2L – Recessed Universal Frame





Unique reference for Trim or No Trim recessed installation.
08.0551.00=includes white frame to complete Trim finishing.
08.0501.00=includes optional white and black frames to complete Trim finishing.


☐ 08.0551.00
+
2x Light Source
+
2x Driver

Referencia única para las instalaciones empotrables Trim o No Trim.
08.0551.00=incluye marco en blanco para completar el acabado Trim.
08.0501.00=incluye marcos opcionales en blanco y negro para completar el acabado Trim.

■ 08.0501.00
+
2x Light Source
+
2x Driver

Johnny 120 Semi-Recessed 1L Square – Housing






E I
08.0556.40
08.0556.CE
08.0556.14
+
1x Light Source
+
1x Driver

E I
08.0506.40
08.0506.CE
08.0506.14
+
1x Light Source
+
1x Driver

Johnny 120 Semi-Recessed 2L Square – Housing





E I
08.0557.40
08.0557.CE
08.0557.14
+
2x Light Source
+
2x Driver

E I
08.0507.40
08.0507.CE
08.0507.14
+
2x Light Source
+
2x Driver

With accessories: LED Array High Performance DC 450 mA - 18W - 1862 lm - 2700K/CRI 90 / 18W - 1984 lm - 3000K/CRI 90
With accessories: LED Array DC 450 mA - 16W - 1612 lm - 2700K/CRI 90 / 16W - 1704 lm - 3000K/CRI 90

Accessories / Accesorios

Screening crosspiece Cruceta de apantallamiento		08.8429.00
Elliptical lens Lente elíptica		08.8431.00
Flood lens Lente flood		08.8432.00
Honeycomb Honeycomb		08.8428.00
Snoot shielding cone Cono apantallador	 29	08.0526.00

HOW TO ORDER JOHNNY 120

TRIM / NO TRIM 1L ROUND

Universal frame




08.0505.00 + 08.0555.00

1x Light Source*



	2700K	3000K	2700K High Perf.	3000K High Perf.
Spot	03.0741.40 03.0741.14	03.0740.40 03.0740.14	03.0801.40 03.0801.14	03.0800.40 03.0800.14
Medium	03.0743.40 03.0743.14	03.0742.40 03.0742.14	03.0803.40 03.0803.14	03.0802.40 03.0802.14
Flood	03.0745.40 03.0745.14	03.0744.40 03.0744.14	03.0805.40 03.0805.14	03.0804.40 03.0804.14

=



TRIM / NO TRIM 1L SQUARE

Universal frame




08.0500.00 + 08.0550.00

1x Light Source*



	2700K	3000K	2700K High Perf.	3000K High Perf.
Spot	03.0741.40 03.0741.14	03.0740.40 03.0740.14	03.0801.40 03.0801.14	03.0800.40 03.0800.14
Medium	03.0743.40 03.0743.14	03.0742.40 03.0742.14	03.0803.40 03.0803.14	03.0802.40 03.0802.14
Flood	03.0745.40 03.0745.14	03.0744.40 03.0744.14	03.0805.40 03.0805.14	03.0804.40 03.0804.14

=



TRIM / NO TRIM 2L SQUARE

Universal frame




08.0501.00 + 08.0551.00

2x Light Source*



	2700K	3000K	2700K High Perf.	3000K High Perf.
Spot	03.0741.40 03.0741.14	03.0740.40 03.0740.14	03.0801.40 03.0801.14	03.0800.40 03.0800.14
Medium	03.0743.40 03.0743.14	03.0742.40 03.0742.14	03.0803.40 03.0803.14	03.0802.40 03.0802.14
Flood	03.0745.40 03.0745.14	03.0744.40 03.0744.14	03.0805.40 03.0805.14	03.0804.40 03.0804.14

=



* Power supply not included. One driver is needed per each light source / Fuente de alimentación no incluida. Se necesita un equipo por fuente de luz.

HOW TO ORDER JOHNNY 120

SEMI-RECESSED 1L SQUARE

Housing



08.0506.40 08.0506.CE 08.0506.14



08.0556.40 08.0556.CE 08.0556.14

\+

1x Light Source*



	2700K	3000K	2700K High Perf.	3000K High Perf.
Spot	03.0741.40 03.0741.14	03.0740.40 03.0740.14	03.0801.40 03.0801.14	03.0800.40 03.0800.14
Medium	03.0743.40 03.0743.14	03.0742.40 03.0742.14	03.0803.40 03.0803.14	03.0802.40 03.0802.14
Flood	03.0745.40 03.0745.14	03.0744.40 03.0744.14	03.0805.40 03.0805.14	03.0804.40 03.0804.14

=



White Concrete Black

SEMI-RECESSED 2L SQUARE

Housing



08.0507.40 08.0507.CE 08.0507.14



08.0557.40 08.0557.CE 08.0557.14

\+

2x Light Source*



	2700K	3000K	2700K High Perf.	3000K High Perf.
Spot	03.0741.40 03.0741.14	03.0740.40 03.0740.14	03.0801.40 03.0801.14	03.0800.40 03.0800.14
Medium	03.0743.40 03.0743.14	03.0742.40 03.0742.14	03.0803.40 03.0803.14	03.0802.40 03.0802.14
Flood	03.0745.40 03.0745.14	03.0744.40 03.0744.14	03.0805.40 03.0805.14	03.0804.40 03.0804.14

=



White Concrete Black

* Power supply not included. One driver is needed per each light source / Fuente de alimentación no incluida. Se necesita un equipo por fuente de luz.

SPOTLIGHTS

Light Shadow Spot, My Spot,
Find Me, UT Spot&Pro, Wan Spot.

NEW

LIGHT SHADOW SPOT

DESIGNED BY FLOS ARCHITECTURAL



NEW

Description
A range of spots that offers the exclusive and patented Flos technology for its Light Shadow family of luminaires, with double focal lenses and high shielding optical body and maximum visual comfort.
As a result, this family of spots (available for standard three-phase tracks and for compatible Flos systems and structures) represents the technological zenith in optical light management for this type of product.
The unbeatable treatment of the raw light source flux results in an excellent Light Output Ratio in any of its beam angles. This, together with an even and impeccable light distribution, makes this family of spotlights the perfect lighting tool for the most demanding professional projects.
These state-of-the-art technical conditions are found in a compact, simple and essential product. The Light Shadow Spots are also available in different finishes, including sophisticated metallic features that make them stand out as a decorative element with a personality of its own.
Other color options are available on request, both for the cylindrical bodies' finishes (external) and for the inner cones (internal), or the rear parts, arm and adapter (rear).

Optical System
The product family offers Beam Angle options from Super Spot to Wide Flood. Please see specific options for each model.

Control Systems
Light Shadow Spots are available in dimmable options under Casambi, DALI protocols and with integrated potentiometer. Please refer to specific options for each model.

Accessories
Optional accessories are available for all models:
- Honeycomb.
- CCT dichroic filters.

Additional Information
Before placing your order, please consult the product details also in the Flos professional website, in its technical data sheet and in the installation and assembly instructions in order to know in detail all the information that may not be included in this catalogue, that may have been updated online after this edition or that could be relevant to your project or specific installation.

Standard Compliance and Quality Marks
Luminaire complies with the European Technical Standard EN60598-1 and secondary parts.

Descripción
Gama de proyectores que ofrece la tecnología exclusiva y patentada de Flos para su familia de luminarias Light Shadow, con lentes de doble focal y cuerpo óptico de alto apantallamiento y máximo confort visual.
Gracias a ello, esta familia de 'spots' (disponibles para carriles trifásicos estándar y para los sistemas y estructuras compatibles de Flos) representan el cénit tecnológico en gestión óptica de la luz para esta tipología de producto.
El inmejorable tratamiento del flujo bruto de la fuente de luz deriva en un Light Output Ratio excelente en cualquiera de sus opciones de apertura (beam angle). Ello, unido a una distribución homogénea e impecable de la luz, hacen de esta familia de proyectores la herramienta lumínica perfecta para los proyectos profesionales más exigentes.
Estas condiciones técnicas de vanguardia se concentran en un producto compacto, formalmente sencillo y esencial. Los Light Shadow Spots se ofrecen además en diferentes acabados, entre los que destacan sofisticadas opciones metálicas que los distinguen como un elemento decorativo de personalidad propia. Otras opciones de color están disponibles bajo demanda, tanto para los acabados de los cuerpos cilíndricos (external) como para los conos interiores (internal) o las partes traseras, brazo y adaptador (rear).

Sistema Óptico
La familia de producto ofrece opciones de apertura Beam Angle desde Super Spot a Wide Flood. Consulte las opciones concretas de cada modelo.

Sistemas de Control
Los Light Shadow Spots están disponibles en opciones regulables bajo protocolos Casambi, DALI y con potenciómetro integrado. Consulte la información de cada modelo.

Accesorios
Todos los modelos cuentan con accesorios opcionales:
- Panel de abeja.
- Filtros Dicroicos CCT.

Información Adicional
Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo, haber sido actualizada online posteriormente a esta edición o ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play

NEW

LIGHT SHADOW SPOT

DESIGNED BY FLOS ARCHITECTURAL

LIGHT SHADOW SPOT 45



LIGHT SOURCE
LED ARRAY
11,5W
844 lm
3000K/CRI 90
915 lm
4000K/CRI 90

LIGHT SHADOW SPOT 60



LIGHT SOURCE
LED ARRAY
Up to 22W
Up to 1751 lm
3000K/CRI 90
Up to 1815 lm
4000K/CRI 90

40 White
40 Blanco



14 Black
14 Negro



40.78/YU/C6 All White



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



LIGHT SHADOW SPOT

NEW

THE TRACKING MAGNET & INFRA-STRUCTURE

LIGHT SHADOW SPOT 30



LIGHT SOURCE
POWER LED
4,5W
257 lm
2700K/CRI 90
263 lm
3000K/CRI 90

LIGHT SHADOW SPOT 45



LIGHT SOURCE
LED ARRAY
10W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

LIGHT SHADOW SPOT 60



LIGHT SOURCE
LED ARRAY
Up to 20W
Up to 1563 lm
2700K/CRI 90
Up to 1751 lm
3000K/CRI 90

* Refer to The Tracking Magnet & Infra-Structure chapter / Ver capítulo The Tracking Magnet & Infra-Structure

THE RUNNING MAGNET

LIGHT SHADOW SPOT 30



LIGHT SOURCE
POWER LED
4W
257 lm
2700K/CRI 90
263 lm
3000K/CRI 90

LIGHT SHADOW SPOT 45




LIGHT SOURCE
LED ARRAY
10W
756 lm
2700K/CRI 90
799 lm
3000K/CRI 90


* Refer to The Running Magnet chapter / Ver capítulo The Running Magnet

Light Shadow Spot 45

LED Array 11,5W - 844 lm - 3000K/CRI 90 / 11,5W - 915 lm - 4000K/CRI 90







Projector to be installed on three-phase track with LED light source. Built-in 220-240V, 50-60Hz power supply.
All finishes come with black track adapter, arm and back of the head. In the "all white" versions the track adapter, arm and back of the head come in white. The display is always offered in high gloss technical black anti-glare finish.
For other finishes, please consult us.

Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.
Todos los acabados tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones "all white" el adaptador a carril, el brazo y la trasera son blancas. La pantalla siempre se ofrece en acabado anti-deslumbramiento negro técnico de alto brillo.
Otros acabados, consultar.

Optic Spot - 3000K

Non Dimmable

- 05.9205.40
- 05.9205.14
- 05.9205.ER
- 05.9205.ES
- 05.9205.40.78


Dali 2

- 05.9205.40ADA
- 05.9205.14ADA
- 05.9205.ERADA
- 05.9205.ESADA
- 05.9205.40AYU

Casambi

- 05.9205.40ACB
- 05.9205.14ACB
- 05.9205.ERACB
- 05.9205.ESACB
- 05.9205.40AC6

15° SPOT



Luminous flux luminaire 686 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	8456	0.27
2	2114	0.54
3	940	0.80
4	528	1.07
5	338	1.34

Optic Spot - 4000K

Non Dimmable

- 05.9210.40
- 05.9210.14
- 05.9210.ER
- 05.9210.ES
- 05.9210.40.78


Dali 2

- 05.9210.40ADA
- 05.9210.14ADA
- 05.9210.ERADA
- 05.9210.ESADA
- 05.9210.40AYU

Casambi

- 05.9210.40ACB
- 05.9210.14ACB
- 05.9210.ERACB
- 05.9210.ESACB
- 05.9210.40AC6

15° SPOT



Luminous flux luminaire 744 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	9171	0.27
2	2293	0.54
3	1019	0.80
4	573	1.07
5	367	1.34

Optic Medium - 3000K

Non Dimmable

- 05.9206.40
- 05.9206.14
- 05.9206.ER
- 05.9206.ES
- 05.9206.40.78


Dali 2

- 05.9206.40ADA
- 05.9206.14ADA
- 05.9206.ERADA
- 05.9206.ESADA
- 05.9206.40AYU

Casambi

- 05.9206.40ACB
- 05.9206.14ACB
- 05.9206.ERACB
- 05.9206.ESACB
- 05.9206.40AC6

21° MEDIUM



Luminous flux luminaire 682 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5459	0.36
2	1365	0.73
3	607	1.09
4	341	1.46
5	218	1.82

Optic Medium - 4000K

Non Dimmable

- 05.9211.40
- 05.9211.14
- 05.9211.ER
- 05.9211.ES
- 05.9211.40.78


Dali 2

- 05.9211.40ADA
- 05.9211.14ADA
- 05.9211.ERADA
- 05.9211.ESADA
- 05.9211.40AYU

Casambi

- 05.9211.40ACB
- 05.9211.14ACB
- 05.9211.ERACB
- 05.9211.ESACB
- 05.9211.40AC6

21° MEDIUM



Luminous flux luminaire 739 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5916	0.36
2	1479	0.73
3	657	1.09
4	370	1.46
5	237	1.82

NEW

Optic Flood - 3000K

Non Dimmable

- 05.9207.40
- 05.9207.14
- 05.9207.ER
- 05.9207.ES
- 05.9207.40.78

Dali 2


- 05.9207.40ADA
- 05.9207.14ADA
- 05.9207.ERADA
- 05.9207.ESADA
- 05.9207.40AYU

Casambi

- 05.9207.40ACB
- 05.9207.14ACB
- 05.9207.ERACB
- 05.9207.ESACB
- 05.9207.40AC6



FLOOD



Luminous flux luminaire
682 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2424	0.56
2	606	1.11
3	269	1.67
4	152	2.22
5	97	2.78

Optic Flood - 4000K

Non Dimmable

- 05.9212.40
- 05.9212.14
- 05.9212.ER
- 05.9212.ES
- 05.9212.40.78

Dali 2


- 05.9212.40ADA
- 05.9212.14ADA
- 05.9212.ERADA
- 05.9212.ESADA
- 05.9212.40AYU

Casambi

- 05.9212.40ACB
- 05.9212.14ACB
- 05.9212.ERACB
- 05.9212.ESACB
- 05.9212.40AC6



FLOOD



Luminous flux luminaire
739 lm


Beam Angle: 31°


h(m)	E(lx)	D(m)
1	2627	0.56
2	657	1.11
3	292	1.67
4	164	2.22
5	105	2.78

Light Shadow Spot 60

Super Spot: LED Array 11W - 844 lm - 3000K/CRI 90 / 11W - 915 lm - 4000K/CRI 90
S/M/F/WF: LED Array 22W - 1751 lm - 3000K/CRI 90 / 22W - 1815 lm - 4000K/CRI 90







Projector to be installed on three-phase track with LED light source. Built-in 220-240V, 50-60Hz power supply.
All finishes come with black track adapter, arm and back of the head. In the “all white” versions the track adapter, arm and back of the head come in white. The display is always offered in high gloss technical black anti-glare finish.
For other finishes, please consult us.

Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.
Todos los acabados tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo y la trasera son blancas. La pantalla siempre se ofrece en acabado anti-deslumbramiento negro técnico de alto brillo.
Otros acabados, consultar.


Optic Super Spot - 3000K

Non Dimmable
- 05.9235.40
- 05.9235.14
- 05.9235.ER
- 05.9235.ES
- 05.9235.40.78

Dali 2
- 05.9235.40ADA
- 05.9235.14ADA
- 05.9235.ERADA
- 05.9235.ESADA
- 05.9235.40AYU

Casambi
- 05.9235.40ACB
- 05.9235.14ACB
- 05.9235.ERACB
- 05.9235.ESACB
- 05.9235.40AC6





Luminous flux luminaire
808 lm

Beam Angle: 9°

h(m)	E(lx)	D(m)
1	26322	0.16
2	6581	0.32
3	2925	0.48
4	1645	0.64
5	1053	0.80


Optic Super Spot - 4000K

Non Dimmable
- 05.9240.40
- 05.9240.14
- 05.9240.ER
- 05.9240.ES
- 05.9240.40.78

Dali 2
- 05.9240.40ADA
- 05.9240.14ADA
- 05.9240.ERADA
- 05.9240.ESADA
- 05.9240.40AYU

Casambi
- 05.9240.40ACB
- 05.9240.14ACB
- 05.9240.ERACB
- 05.9240.ESACB
- 05.9240.40AC6





Luminous flux luminaire
876 lm

Beam Angle: 9°

h(m)	E(lx)	D(m)
1	28538	0.16
2	7134	0.32
3	3171	0.48
4	1784	0.64
5	1142	0.80


Optic Spot - 3000K

Non Dimmable
- 05.9236.40
- 05.9236.14
- 05.9236.ER
- 05.9236.ES
- 05.9236.40.78

Dali 2
- 05.9236.40ADA
- 05.9236.14ADA
- 05.9236.ERADA
- 05.9236.ESADA
- 05.9236.40AYU

Casambi
- 05.9236.40ACB
- 05.9236.14ACB
- 05.9236.ERACB
- 05.9236.ESACB
- 05.9236.40AC6





Luminous flux luminaire
1375 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	15772	0.27
2	3943	0.54
3	1752	0.81
4	986	1.09
5	631	1.36


Optic Spot - 4000K

Non Dimmable
- 05.9241.40
- 05.9241.14
- 05.9241.ER
- 05.9241.ES
- 05.9241.40.78

Dali 2
- 05.9241.40ADA
- 05.9241.14ADA
- 05.9241.ERADA
- 05.9241.ESADA
- 05.9241.40AYU

Casambi
- 05.9241.40ACB
- 05.9241.14ACB
- 05.9241.ERACB
- 05.9241.ESACB
- 05.9241.40AC6





Luminous flux luminaire
1425 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	16346	0.27
2	4086	0.54
3	1816	0.81
4	1022	1.09
5	654	1.36

NEW

Optic Medium - 3000K

Non Dimmable

- 05.9237.40
- 05.9237.14
- 05.9237.ER
- 05.9237.ES
- 05.9237.40.78


Dali 2

- 05.9237.40ADA
- 05.9237.14ADA
- 05.9237.ERADA
- 05.9237.ESADA
- 05.9237.40AYU

Casambi

- 05.9237.40ACB
- 05.9237.14ACB
- 05.9237.ERACB
- 05.9237.ESACB
- 05.9237.40AC6





Luminous flux luminaire
1427 lm

Beam Angle:		26°
h(m)	E(lx)	D(m)
1	8110	0.45
2	2027	0.91
3	901	1.36
4	507	1.82
5	324	2.27

Optic Medium - 4000K

Non Dimmable

- 05.9242.40
- 05.9242.14
- 05.9242.ER
- 05.9242.ES
- 05.9242.40.78


Dali 2

- 05.9242.40ADA
- 05.9242.14ADA
- 05.9242.ERADA
- 05.9242.ESADA
- 05.9242.40AYU

Casambi

- 05.9242.40ACB
- 05.9242.14ACB
- 05.9242.ERACB
- 05.9242.ESACB
- 05.9242.40AC6





Luminous flux luminaire
1479 lm

Beam Angle:		26°
h(m)	E(lx)	D(m)
1	8405	0.45
2	2101	0.91
3	934	1.36
4	525	1.82
5	336	2.27

Optic Flood - 3000K

Non Dimmable

- 05.9238.40
- 05.9238.14
- 05.9238.ER
- 05.9238.ES
- 05.9238.40.78


Dali 2

- 05.9238.40ADA
- 05.9238.14ADA
- 05.9238.ERADA
- 05.9238.ESADA
- 05.9238.40AYU

Casambi

- 05.9238.40ACB
- 05.9238.14ACB
- 05.9238.ERACB
- 05.9238.ESACB
- 05.9238.40AC6





Luminous flux luminaire
1431 lm

Beam Angle:		33°
h(m)	E(lx)	D(m)
1	4907	0.60
2	1227	1.20
3	545	1.80
4	307	2.40
5	196	3.00

Optic Flood - 4000K

Non Dimmable

- 05.9243.40
- 05.9243.14
- 05.9243.ER
- 05.9243.ES
- 05.9243.40.78


Dali 2

- 05.9243.40ADA
- 05.9243.14ADA
- 05.9243.ERADA
- 05.9243.ESADA
- 05.9243.40AYU

Casambi

- 05.9243.40ACB
- 05.9243.14ACB
- 05.9243.ERACB
- 05.9243.ESACB
- 05.9243.40AC6





Luminous flux luminaire
1485 lm

Beam Angle:		33°
h(m)	E(lx)	D(m)
1	5092	0.60
2	1273	1.20
3	566	1.80
4	318	2.40
5	204	3.00

Optic Wide Flood - 3000K

Non Dimmable

- 05.9239.40
- 05.9239.14
- 05.9239.ER
- 05.9239.ES
- 05.9239.40.78


Dali 2

- 05.9239.40ADA
- 05.9239.14ADA
- 05.9239.ERADA
- 05.9239.ESADA
- 05.9239.40AYU

Casambi

- 05.9239.40ACB
- 05.9239.14ACB
- 05.9239.ERACB
- 05.9239.ESACB
- 05.9239.40AC6





Luminous flux luminaire
1390 lm

Beam Angle:		43°
h(m)	E(lx)	D(m)
1	3026	0.79
2	757	1.59
3	336	2.38
4	189	3.17
5	121	3.97

Optic WideFlood - 4000K

Non Dimmable

- 05.9244.40
- 05.9244.14
- 05.9244.ER
- 05.9244.ES
- 05.9244.40.78


Dali 2

- 05.9244.40ADA
- 05.9244.14ADA
- 05.9244.ERADA
- 05.9244.ESADA
- 05.9244.40AYU

Casambi

- 05.9244.40ACB
- 05.9244.14ACB
- 05.9244.ERACB
- 05.9244.ESACB
- 05.9244.40AC6





Luminous flux luminaire
1445 lm

Beam Angle:		43°
h(m)	E(lx)	D(m)
1	3146	0.79
2	787	1.59
3	350	2.38
4	197	3.17
5	126	3.97

Accesorios / Accessories

Light Shadow Spot 45

Honeycomb	Panel de abeja		08.0793.00
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase 3000K >> 3600±75K 4000K >> 5100±75K 08.0794.00
			Decrease 3000K >> 2700±75K 4000K >> 3400±75K 08.0795.00


Light Shadow Spot 60

Honeycomb	Panel de abeja		Super Spot 08.0175.14
			Spot / Medium / Flood / Wide Flood 08.0176.14
Dichroic CCT Filter	Filtros Dicroicos CCT		Increase Super Spot 3000K >> 3600±75K 4000K >> 5100±75K 08.0796.00
			Spot / Medium / Flood / Wide Flood 3000K >> 3600±75K 4000K >> 5100±75K 08.0798.00
			Decrease Super Spot 3000K >> 2700±75K 4000K >> 3400±75K 08.0797.00
			Spot / Medium / Flood / Wide Flood 3000K >> 2700±75K 4000K >> 3400±75K 08.0799.00

NEW

MY SPOT

DESIGNED BY MICHAEL ANASTASSIADES



NEW

Description
My Spot, the spotlight designed by Michael Anastassiades, is known for its unique and minimalist design. Now available in new recessed and surface-mounted versions, the possibilities for architectural integration become far greater. Equipped with advanced optics incorporating dual focal lens technology, these floodlights ensure high-quality uniform illumination, minimising glare and providing superior visual comfort.
The range includes two different sizes of floodlight (Ø25 - Ø35) to suit a variety of lighting needs, as well as two different stem sizes to allow for customised installation according to the requirements of the space. This configuration flexibility makes the floodlights suited to countless applications, from residential environments to high-demand commercial projects.
The spotlights in the My Spot range are fully adjustable, allowing both swivelling and tilting movements and giving total flexibility for directing the light precisely where desired. In addition, when in a downlight position, the connection arm is perfectly flush with the product, maintaining a clean aesthetic free from visual interruptions.
My Spot is available in multiple finishes, including sophisticated metallic options. These possibilities ensure the spotlights play not only a functional role but also become distinctive decorative elements with a personality of their own, adding a touch of refined design to any space.

Optical System
The product family offers Spot, Medium, and Flood beam angle options. Please check the specific options for each model.

Control Systems
My Spot is available in different control options for dimming.
Recessed: No Dim, Mains Dimming, 1-10V, Dali/Push, Casambi.
Surface: No Dim, Dali, Casambi.

Additional Information
Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Regulatory Compliance and Quality Labels
Appliance compliant with the European Technical Regulation EN60598-1 and Part 2.

Descripción
My Spot, el proyector diseñado por Michael Anastassiades, es reconocido por su diseño único y minimalista. Ahora, con nuevas versiones empotradas y de superficie, ofrece mayores posibilidades de integración arquitectónica.
Equipados con una óptica avanzada que incorpora tecnología de doble lente focal, estos proyectores garantizan una iluminación uniforme de alta calidad que minimiza el deslumbramiento y proporciona un confort visual superior.
La gama incluye dos tamaños diferentes de proyector (Ø25 - Ø35) para adaptarse a diversas necesidades de iluminación, así como dos tamaños de vástago diferentes para permitir una instalación personalizada según los requisitos del espacio. Esta flexibilidad de configuración hace que los proyectores sean adecuados para innumerables aplicaciones, desde entornos residenciales hasta proyectos comerciales de gran demanda.
Los focos de la gama My Spot son totalmente orientables, lo que permite tanto movimientos giratorios como basculantes y proporciona flexibilidad total para dirigir la luz con precisión hacia donde se desee. Además, cuando está en posición descendente, el brazo de conexión queda perfectamente alineado con el producto, manteniendo una estética limpia y sin interrupciones visuales.
My Spot está disponible en múltiples acabados, incluidas sofisticadas opciones metálicas. Estas posibilidades garantizan que los focos no solo desempeñen un papel funcional, sino que también se conviertan en elementos decorativos distintivos con personalidad propia, lo que añade un toque de diseño refinado a cualquier espacio.

Sistema Óptico
La familia de producto ofrece opciones de apertura Spot, Medium y Flood. Consulte las opciones concretas de cada modelo.

Sistemas de Control
My Spot está disponible en diferentes opciones de control para la regulación.
Empotrado: No Dim, Mains Dimming, 1-10V, Dali/Push, Casambi.
Superficie: No Dim, Dali, Casambi.

Información Adicional
Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

FLOS
CONTROL BY CASAMBI

Available on the App Store

GET IT ON Google Play

NEW

MY SPOT

DESIGNED BY MICHAEL ANASTASSIADES

RECESSED

MY SPOT Ø25 SHORT RECESSED



LIGHT SOURCE
POWER LED
2,5W
271 lm
2700K/CRI 90
326 lm
3000K/CRI 90

MY SPOT Ø25 LONG RECESSED



LIGHT SOURCE
POWER LED
2,5W
271 lm
2700K/CRI 90
326 lm
3000K/CRI 90

MY SPOT Ø35 SHORT RECESSED



LIGHT SOURCE
LED ARRAY
7,2W
623 lm
2700K/CRI 90
641 lm
3000K/CRI 90

MY SPOT Ø35 LONG RECESSED



LIGHT SOURCE
LED ARRAY
7,2W
623 lm
2700K/CRI 90
641 lm
3000K/CRI 90

SURFACE

MY SPOT Ø25 SHORT SURFACE



LIGHT SOURCE
POWER LED
4,7W
271 lm
2700K/CRI 90
326 lm
3000K/CRI 90

MY SPOT Ø25 LONG SURFACE



LIGHT SOURCE
POWER LED
4,7W
271 lm
2700K/CRI 90
326 lm
3000K/CRI 90

MY SPOT Ø35 SHORT SURFACE



LIGHT SOURCE
LED ARRAY
Up to 11,5W
623 lm
2700K/CRI 90
641 lm
3000K/CRI 90

MY SPOT Ø35 LONG SURFACE



LIGHT SOURCE
LED ARRAY
Up to 11,5W
623 lm
2700K/CRI 90
641 lm
3000K/CRI 90

MY SPOT

NEW

ZERO TRACK PRO

MY SPOT Ø25 SHORT



LIGHT SOURCE
POWER LED
Up to 4,7W
231 lm
2700K/CRI 90
235 lm
3000K/CRI 90

MY SPOT Ø25 LONG



LIGHT SOURCE
POWER LED
Up to 4,7W
231 lm
2700K/CRI 90
235 lm
3000K/CRI 90

MY SPOT Ø35 SHORT



LIGHT SOURCE
LED ARRAY
Up to 11W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

MY SPOT Ø35 LONG



LIGHT SOURCE
LED ARRAY
Up to 11W
799 lm
2700K/CRI 90
844 lm
3000K/CRI 90

* Refer to Zero Track Pro chapter / Ver capítulo Zero Track Pro

☐ 40 White
40 Blanco



■ 14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado



☐ 40 White
40 Blanco



■ 14 Black
14 Negro



ER Brushed Steel
ER Acero Cepillado




ES Brushed Bronze
ES Bronce Cepillado




My Spot Ø25 Short Recessed By Michael Anastassiades

Power LED DC 800 mA - 2,5W - 271 lm - 2700K/CRI 90 / 326 lm - 3000K/CRI 90







LED lighting module for recessed applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product. Power supply not included. Remote power supply to be installed in an accessible place.

Módulo de iluminación LED para aplicaciones de empotrar. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión queda perfectamente enrasado con el producto. Fuente de alimentación no incluida. Fuente de alimentación remota para ser instalada en un lugar accesible.

Recommended power supply / Equipos recomendados*:

Non Dimmable	60.7773
Dimmable 1-10V	60.9208
DALI/Push	60.7774
Mains Dimming	60.9467**
Casambi	60.7785


* Refer to the Drivers chapter / Ver capítulo Drivers

** At least 2 units must be connected / Hay que conectar mínimo 2 unidades

Optic Spot - 2700K

- 05.5400.40A
- 05.5400.14A
- 05.5400.ERA
- 05.5400.ESA





Luminous flux luminaire
203 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4075	0.19
2	1019	0.37
3	453	0.56
4	255	0.75
5	163	0.93

Optic Spot - 3000K

- 05.5405.40A
- 05.5405.14A
- 05.5405.ERA
- 05.5405.ESA





Luminous flux luminaire
216 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4336	0.19
2	1084	0.37
3	482	0.56
4	271	0.75
5	173	0.93

Optic Medium - 2700K

- 05.5401.40A
- 05.5401.14A
- 05.5401.ERA
- 05.5401.ESA





Luminous flux luminaire
207 lm


Beam Angle: 23°

h(m)	E(lx)	D(m)
1	1386	0.41
2	347	0.82
3	154	1.23
4	87	1.64
5	55	2.05

Optic Medium - 3000K

- 05.5406.40A
- 05.5406.14A
- 05.5406.ERA
- 05.5406.ESA





Luminous flux luminaire
220 lm


Beam Angle: 23°

h(m)	E(lx)	D(m)
1	1473	0.41
2	368	0.82
3	164	1.23
4	92	1.64
5	59	2.05

Optic Flood - 2700K

- 05.5402.40A
- 05.5402.14A
- 05.5402.ERA
- 05.5402.ESA





Luminous flux luminaire
187 lm


Beam Angle: 34°

h(m)	E(lx)	D(m)
1	592	0.62
2	148	1.23
3	66	1.85
4	37	2.46
5	24	3.08

Optic Flood - 3000K

- 05.5407.40A
- 05.5407.14A
- 05.5407.ERA
- 05.5407.ESA





Luminous flux luminaire
199 lm

Beam Angle: 34°


h(m)	E(lx)	D(m)
1	630	0.62
2	157	1.23
3	70	1.85
4	39	2.46
5	25	3.08


NEW

My Spot Ø25 Long Recessed By Michael Anastassiades

Power LED DC 800 mA - 2,5W - 271 lm - 2700K/CRI 90 / 326 lm - 3000K/CRI 90







LED lighting module for recessed applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product. Power supply not included. Remote power supply to be installed in an accessible place.

Módulo de iluminación LED para aplicaciones de empotrar. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión queda perfectamente enrasado con el producto. Fuente de alimentación no incluida. Fuente de alimentación remota para ser instalada en un lugar accesible.

Recommended power supply / Equipos recomendados*:

Non Dimmable	60.7773
Dimmable 1-10V	60.9208
Dali/Push	60.7774
Mains Dimming	60.9467**
Casambi	60.7785


* Refer to the Drivers chapter / Ver capítulo Drivers

** At least 2 units must be connected / Hay que conectar mínimo 2 unidades

Optic Spot - 2700K

- 05.5410.40A
- 05.5410.14A
- 05.5410.ERA
- 05.5410.ESA





Luminous flux luminaire
203 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4075	0.19
2	1019	0.37
3	453	0.56
4	255	0.75
5	163	0.93

Optic Medium - 2700K

- 05.5411.40A
- 05.5411.14A
- 05.5411.ERA
- 05.5411.ESA





Luminous flux luminaire
207 lm


Beam Angle: 23°

h(m)	E(lx)	D(m)
1	1386	0.41
2	347	0.82
3	154	1.23
4	87	1.64
5	55	2.05

Optic Flood - 2700K

- 05.5412.40A
- 05.5412.14A
- 05.5412.ERA
- 05.5412.ESA





Luminous flux luminaire
187 lm


Beam Angle: 34°

h(m)	E(lx)	D(m)
1	592	0.62
2	148	1.23
3	66	1.85
4	37	2.46
5	24	3.08

Optic Spot - 3000K

- 05.5415.40A
- 05.5415.14A
- 05.5415.ERA
- 05.5415.ESA





Luminous flux luminaire
216 lm


Beam Angle: 11°

h(m)	E(lx)	D(m)
1	4336	0.19
2	1084	0.37
3	482	0.56
4	271	0.75
5	173	0.93

Optic Medium - 3000K

- 05.5416.40A
- 05.5416.14A
- 05.5416.ERA
- 05.5416.ESA





Luminous flux luminaire
220 lm


Beam Angle: 23°

h(m)	E(lx)	D(m)
1	1473	0.41
2	368	0.82
3	164	1.23
4	92	1.64
5	59	2.05

Optic Flood - 3000K

- 05.5417.40A
- 05.5417.14A
- 05.5417.ERA
- 05.5417.ESA





Luminous flux luminaire
199 lm


Beam Angle: 34°


h(m)	E(lx)	D(m)
1	630	0.62
2	157	1.23
3	70	1.85
4	39	2.46
5	25	3.08

My Spot Ø35 Short Recessed By Michael Anastassiades

LED Array DC 400 mA - 7,2W - 623 lm - 2700K/CRI 90 / 641 lm - 3000K/CRI 90







LED lighting module for recessed applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product. Power supply not included. Remote power supply to be installed in an accessible place.

Módulo de iluminación LED para aplicaciones de empotrar. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión queda perfectamente enrasado con el producto. Fuente de alimentación no incluida. Fuente de alimentación remota para ser instalada en un lugar accesible.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.7773
Dimmable 1-10V	60.9208
DALI/Push	60.7774
Mains Dimming	60.9467
Casambi	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot - 2700K

- 05.5420.40
- 05.5420.14
- 05.5420.ER
- 05.5420.ES

15° SPOT



Luminous flux luminaire 531 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	7399	0.26
2	1850	0.51
3	822	0.77
4	462	1.02
5	296	1.28

Optic Spot - 3000K

- 05.5425.40
- 05.5425.14
- 05.5425.ER
- 05.5425.ES

15° SPOT



Luminous flux luminaire 556 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	7714	0.26
2	1929	0.52
3	857	0.78
4	482	1.04
5	309	1.30

Optic Medium - 2700K

- 05.5421.40
- 05.5421.14
- 05.5421.ER
- 05.5421.ES

19° MEDIUM



Luminous flux luminaire 573 lm


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	5386	0.34
2	1347	0.68
3	598	1.02
4	337	1.36
5	215	1.70

Optic Medium - 3000K

- 05.5426.40
- 05.5426.14
- 05.5426.ER
- 05.5426.ES

20° MEDIUM



Luminous flux luminaire 599 lm


Beam Angle: 20°

h(m)	E(lx)	D(m)
1	5430	0.35
2	1357	0.69
3	603	1.04
4	339	1.39
5	217	1.73

Optic Flood - 2700K

- 05.5422.40
- 05.5422.14
- 05.5422.ER
- 05.5422.ES

30° FLOOD



Luminous flux luminaire 588 lm


Beam Angle: 30°

h(m)	E(lx)	D(m)
1	2152	0.54
2	538	1.09
3	239	1.63
4	134	2.18
5	86	2.72

Optic Flood - 3000K

- 05.5427.40
- 05.5427.14
- 05.5427.ER
- 05.5427.ES

31° FLOOD



Luminous flux luminaire 615 lm

Beam Angle: 31°


h(m)	E(lx)	D(m)
1	2182	0.56
2	546	1.11
3	242	1.67
4	136	2.22
5	87	2.78


NEW

My Spot Ø35 Long Recessed By Michael Anastassiades

LED Array DC 400 mA - 7,2W - 623 lm - 2700K/CRI 90 / 641 lm - 3000K/CRI 90







LED lighting module for recessed applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product. Power supply not included. Remote power supply to be installed in an accessible place.

Módulo de iluminación LED para aplicaciones de empotrar. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión queda perfectamente enrasado con el producto. Fuente de alimentación no incluida. Fuente de alimentación remota para ser instalada en un lugar accesible.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.7773
Dimmable 1-10V	60.9208
Dali/Push	60.7774
Mains Dimming	60.9467
Casambi	60.7785

* Refer to the Drivers chapter / Ver capítulo Drivers

Optic Spot - 2700K

- 05.5430.40
- 05.5430.14
- 05.5430.ER
- 05.5430.ES

15° SPOT



Luminous flux luminaire 531 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	7399	0.26
2	1850	0.51
3	822	0.77
4	462	1.02
5	296	1.28

Optic Spot - 3000K

- 05.5435.40
- 05.5435.14
- 05.5435.ER
- 05.5435.ES

15° SPOT



Luminous flux luminaire 556 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	7714	0.26
2	1929	0.52
3	857	0.78
4	482	1.04
5	309	1.30

Optic Medium - 2700K

- 05.5431.40
- 05.5431.14
- 05.5431.ER
- 05.5431.ES

19° MEDIUM



Luminous flux luminaire 573 lm


Beam Angle: 19°

h(m)	E(lx)	D(m)
1	5386	0.34
2	1347	0.68
3	598	1.02
4	337	1.36
5	215	1.70

Optic Medium - 3000K

- 05.5436.40
- 05.5436.14
- 05.5436.ER
- 05.5436.ES

20° MEDIUM



Luminous flux luminaire 599 lm


Beam Angle: 20°

h(m)	E(lx)	D(m)
1	5430	0.35
2	1357	0.69
3	603	1.04
4	339	1.39
5	217	1.73

Optic Flood - 2700K

- 05.5432.40
- 05.5432.14
- 05.5432.ER
- 05.5432.ES

30° FLOOD



Luminous flux luminaire 588 lm


Beam Angle: 30°

h(m)	E(lx)	D(m)
1	2152	0.54
2	538	1.09
3	239	1.63
4	134	2.18
5	86	2.72

Optic Flood - 3000K

- 05.5437.40
- 05.5437.14
- 05.5437.ER
- 05.5437.ES

31° FLOOD



Luminous flux luminaire 615 lm


Beam Angle: 31°


h(m)	E(lx)	D(m)
1	2182	0.56
2	546	1.11
3	242	1.67
4	136	2.22
5	87	2.78

My Spot Ø25 Short Surface By Michael Anastassiades

Power LED 4,7W - 271 lm - 2700K/CRI 90 / 326 lm - 3000K/CRI 90







LED lighting module for surface-mounted applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.

Módulo de iluminación LED para aplicaciones de superficie. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión queda perfectamente enrasado con el producto.

Optic Spot - 2700K

Non Dimmable


- 05.5450.40A
- 05.5450.14A
- 05.5450.ERA
- 05.5450.ESA

Dali

- 05.5450.40ADA
- 05.5450.14ADA
- 05.5450.ERADA
- 05.5450.ESADA

Casambi

- 05.5450.40ACB
- 05.5450.14ACB
- 05.5450.ERACB
- 05.5450.ESACB



Luminous flux luminaire
118 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	2139	0.18
2	535	0.37
3	238	0.55
4	134	0.74
5	86	0.92

Optic Spot - 3000K

Non Dimmable


- 05.5455.40A
- 05.5455.14A
- 05.5455.ERA
- 05.5455.ESA

Dali

- 05.5455.40ADA
- 05.5455.14ADA
- 05.5455.ERADA
- 05.5455.ESADA

Casambi

- 05.5455.40ACB
- 05.5455.14ACB
- 05.5455.ERACB
- 05.5455.ESACB



Luminous flux luminaire
121 lm

Beam Angle: 13°

h(m)	E(lx)	D(m)
1	1701	0.22
2	425	0.44
3	189	0.66
4	106	0.88
5	68	1.10

Optic Medium - 2700K

Non Dimmable


- 05.5451.40A
- 05.5451.14A
- 05.5451.ERA
- 05.5451.ESA

Dali

- 05.5451.40ADA
- 05.5451.14ADA
- 05.5451.ERADA
- 05.5451.ESADA

Casambi

- 05.5451.40ACB
- 05.5451.14ACB
- 05.5451.ERACB
- 05.5451.ESACB



Luminous flux luminaire
130 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	967	0.39
2	242	0.77
3	107	1.16
4	60	1.54
5	39	1.93

Optic Medium - 3000K

Non Dimmable


- 05.5456.40A
- 05.5456.14A
- 05.5456.ERA
- 05.5456.ESA

Dali

- 05.5456.40ADA
- 05.5456.14ADA
- 05.5456.ERADA
- 05.5456.ESADA

Casambi

- 05.5456.40ACB
- 05.5456.14ACB
- 05.5456.ERACB
- 05.5456.ESACB



Luminous flux luminaire
133 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1078	0.37
2	270	0.75
3	120	1.12
4	67	1.49
5	43	1.86

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

NEW

Optic Flood - 2700K

Non Dimmable

- 05.5452.40A
- 05.5452.14A
- 05.5452.ERA
- 05.5452.ESA

Dali


- 05.5452.40ADA
- 05.5452.14ADA
- 05.5452.ERADA
- 05.5452.ESADA

Casambi

- 05.5452.40ACB
- 05.5452.14ACB
- 05.5452.ERACB
- 05.5452.ESACB



FLOOD



Luminous flux luminaire
124 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	363	0.63
2	91	1.26
3	40	1.89
4	23	2.51
5	15	3.14

Optic Flood - 3000K

Non Dimmable

- 05.5457.40A
- 05.5457.14A
- 05.5457.ERA
- 05.5457.ESA

Dali


- 05.5457.40ADA
- 05.5457.14ADA
- 05.5457.ERADA
- 05.5457.ESADA

Casambi

- 05.5457.40ACB
- 05.5457.14ACB
- 05.5457.ERACB
- 05.5457.ESACB



FLOOD



Luminous flux luminaire
127 lm

Beam Angle: 32°


h(m)	E(lx)	D(m)
1	399	0.58
2	100	1.16
3	44	1.75
4	25	2.33
5	16	2.91


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

My Spot Ø25 Long Surface By Michael Anastassiades

Power LED 4,7W - 271 lm - 2700K/CRI 90 / 326 lm - 3000K/CRI 90







LED lighting module for surface-mounted applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.

Módulo de iluminación LED para aplicaciones de superficie. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión queda perfectamente enrasado con el producto.

Optic Spot - 2700K

Non Dimmable


- 05.5460.40A
- 05.5460.14A
- 05.5460.ERA
- 05.5460.ESA

Dali

- 05.5460.40ADA
- 05.5460.14ADA
- 05.5460.ERADA
- 05.5460.ESADA

Casambi

- 05.5460.40ACB
- 05.5460.14ACB
- 05.5460.ERACB
- 05.5460.ESACB



Luminous flux luminaire
118 lm

Beam Angle: 11°

h(m)	E(lx)	D(m)
1	2139	0.18
2	535	0.37
3	238	0.55
4	134	0.74
5	86	0.92

Optic Spot - 3000K

Non Dimmable


- 05.5465.40A
- 05.5465.14A
- 05.5465.ERA
- 05.5465.ESA

Dali

- 05.5465.40ADA
- 05.5465.14ADA
- 05.5465.ERADA
- 05.5465.ESADA

Casambi

- 05.5465.40ACB
- 05.5465.14ACB
- 05.5465.ERACB
- 05.5465.ESACB



Luminous flux luminaire
121 lm

Beam Angle: 13°

h(m)	E(lx)	D(m)
1	1701	0.22
2	425	0.44
3	189	0.66
4	106	0.88
5	68	1.10

Optic Medium - 2700K

Non Dimmable


- 05.5461.40A
- 05.5461.14A
- 05.5461.ERA
- 05.5461.ESA

Dali

- 05.5461.40ADA
- 05.5461.14ADA
- 05.5461.ERADA
- 05.5461.ESADA

Casambi

- 05.5461.40ACB
- 05.5461.14ACB
- 05.5461.ERACB
- 05.5461.ESACB



Luminous flux luminaire
130 lm

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	967	0.39
2	242	0.77
3	107	1.16
4	60	1.54
5	39	1.93

Optic Medium - 3000K

Non Dimmable


- 05.5466.40A
- 05.5466.14A
- 05.5466.ERA
- 05.5466.ESA

Dali

- 05.5466.40ADA
- 05.5466.14ADA
- 05.5466.ERADA
- 05.5466.ESADA

Casambi

- 05.5466.40ACB
- 05.5466.14ACB
- 05.5466.ERACB
- 05.5466.ESACB



Luminous flux luminaire
133 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	1078	0.37
2	270	0.75
3	120	1.12
4	67	1.49
5	43	1.86

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

NEW

Optic Flood - 2700K

Non Dimmable

05.5462.40A
05.5462.14A
05.5462.ERA
05.5462.ESA

Dali


05.5462.40ADA
05.5462.14ADA
05.5462.ERADA
05.5462.ESADA

Casambi

05.5462.40ACB
05.5462.14ACB
05.5462.ERACB
05.5462.ESACB



FLOOD



Luminous flux luminaire
124 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	363	0.63
2	91	1.26
3	40	1.89
4	23	2.51
5	15	3.14

Optic Flood - 3000K

Non Dimmable

05.5467.40A
05.5467.14A
05.5467.ERA
05.5467.ESA

Dali


05.5467.40ADA
05.5467.14ADA
05.5467.ERADA
05.5467.ESADA

Casambi

05.5467.40ACB
05.5467.14ACB
05.5467.ERACB
05.5467.ESACB



FLOOD



Luminous flux luminaire
127 lm

Beam Angle: 32°


h(m)	E(lx)	D(m)
1	399	0.58
2	100	1.16
3	44	1.75
4	25	2.33
5	16	2.91


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

My Spot Ø35 Short Surface By Michael Anastassiades

LED Array
Non Dimming / Dali: 11,5W - 623 lm - 2700K/CRI 90 / 641 lm - 3000K/CRI 90
Casambi: 9,2W - 623 lm - 2700K/CRI 90 / 641 lm - 3000K/CRI 90







LED lighting module for surface-mounted applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.


Módulo de iluminación LED para aplicaciones de superficie. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión queda perfectamente enrasado con el producto.

Optic Spot - 2700K

Non Dimmable
- 05.5470.40
- 05.5470.14
- 05.5470.ER
- 05.5470.ES

Dali
- 05.5470.40.DA
- 05.5470.14.DA
- 05.5470.ER.DA
- 05.5470.ES.DA

Casambi
- 05.5470.40.CB
- 05.5470.14.CB
- 05.5470.ER.CB
- 05.5470.ES.CB



Luminous flux luminaire
531 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	7403	0.26
2	1851	0.51
3	823	0.77
4	463	1.02
5	296	1.28

Optic Spot - 3000K

Non Dimmable
- 05.5475.40
- 05.5475.14
- 05.5475.ER
- 05.5475.ES

Dali
- 05.5475.40.DA
- 05.5475.14.DA
- 05.5475.ER.DA
- 05.5475.ES.DA

Casambi
- 05.5475.40.CB
- 05.5475.14.CB
- 05.5475.ER.CB
- 05.5475.ES.CB



Luminous flux luminaire
556 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	7708	0.26
2	1927	0.52
3	856	0.78
4	482	1.04
5	308	1.30

Optic Medium - 2700K

Non Dimmable
- 05.5471.40
- 05.5471.14
- 05.5471.ER
- 05.5471.ES

Dali
- 05.5471.40.DA
- 05.5471.14.DA
- 05.5471.ER.DA
- 05.5471.ES.DA

Casambi
- 05.5471.40.CB
- 05.5471.14.CB
- 05.5471.ER.CB
- 05.5471.ES.CB



Luminous flux luminaire
573 lm

Beam Angle: 19°


h(m)	E(lx)	D(m)
1	5389	0.34
2	1347	0.68
3	599	1.02
4	337	1.36
5	216	1.70

Optic Medium - 3000K

Non Dimmable
- 05.5476.40
- 05.5476.14
- 05.5476.ER
- 05.5476.ES

Dali
- 05.5476.40.DA
- 05.5476.14.DA
- 05.5476.ER.DA
- 05.5476.ES.DA

Casambi
- 05.5476.40.CB
- 05.5476.14.CB
- 05.5476.ER.CB
- 05.5476.ES.CB



Luminous flux luminaire
599 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	5434	0.35
2	1358	0.69
3	604	1.04
4	340	1.39
5	217	1.73

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

NEW

Optic Flood - 2700K

Non Dimmable

- 05.5472.40
- 05.5472.14
- 05.5472.ER
- 05.5472.ES

Dali


- 05.5472.40.DA
- 05.5472.14.DA
- 05.5472.ER.DA
- 05.5472.ES.DA

Casambi

- 05.5472.40.CB
- 05.5472.14.CB
- 05.5472.ER.CB
- 05.5472.ES.CB



FLOOD



Luminous flux luminaire
588 lm

Beam Angle: 30°

h(m)	E(lx)	D(m)
1	2151	0.54
2	538	1.09
3	239	1.63
4	134	2.18
5	86	2.72

Optic Flood - 3000K

Non Dimmable

- 05.5477.40
- 05.5477.14
- 05.5477.ER
- 05.5477.ES

Dali


- 05.5477.40.DA
- 05.5477.14.DA
- 05.5477.ER.DA
- 05.5477.ES.DA

Casambi

- 05.5477.40.CB
- 05.5477.14.CB
- 05.5477.ER.CB
- 05.5477.ES.CB



FLOOD



Luminous flux luminaire
615 lm

Beam Angle: 31°


h(m)	E(lx)	D(m)
1	2181	0.56
2	545	1.11
3	242	1.67
4	136	2.22
5	87	2.78


The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

My Spot Ø35 Long Surface By Michael Anastassiades

LED Array
Non Dimming / Dali: 11,5W - 623 lm - 2700K/CRI 90 / 641 lm - 3000K/CRI 90
Casambi: 9,2W - 623 lm - 2700K/CRI 90 / 641 lm - 3000K/CRI 90







LED lighting module for surface-mounted applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.


Módulo de iluminación LED para aplicaciones de superficie. Óptica con tecnología de lentes de doble focal, bajo deslumbramiento y alto confort visual. Orientable mediante giro y basculación. En posición downlight, el brazo de conexión queda perfectamente enrasado con el producto.

Optic Spot - 2700K

Non Dimmable
- 05.5480.40
- 05.5480.14
- 05.5480.ER
- 05.5480.ES

Dali
- 05.5480.40.DA
- 05.5480.14.DA
- 05.5480.ER.DA
- 05.5480.ES.DA

Casambi
- 05.5480.40.CB
- 05.5480.14.CB
- 05.5480.ER.CB
- 05.5480.ES.CB



Luminous flux luminaire
531 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	7403	0.26
2	1851	0.51
3	823	0.77
4	463	1.02
5	296	1.28

Optic Spot - 3000K

Non Dimmable
- 05.5485.40
- 05.5485.14
- 05.5485.ER
- 05.5485.ES

Dali
- 05.5485.40.DA
- 05.5485.14.DA
- 05.5485.ER.DA
- 05.5485.ES.DA

Casambi
- 05.5485.40.CB
- 05.5485.14.CB
- 05.5485.ER.CB
- 05.5485.ES.CB



Luminous flux luminaire
556 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	7708	0.26
2	1927	0.52
3	856	0.78
4	482	1.04
5	308	1.30

Optic Medium - 2700K

Non Dimmable
- 05.5481.40
- 05.5481.14
- 05.5481.ER
- 05.5481.ES

Dali
- 05.5481.40.DA
- 05.5481.14.DA
- 05.5481.ER.DA
- 05.5481.ES.DA

Casambi
- 05.5481.40.CB
- 05.5481.14.CB
- 05.5481.ER.CB
- 05.5481.ES.CB



Luminous flux luminaire
573 lm

Beam Angle: 19°


h(m)	E(lx)	D(m)
1	5389	0.34
2	1347	0.68
3	599	1.02
4	337	1.36
5	216	1.70

Optic Medium - 3000K

Non Dimmable
- 05.5486.40
- 05.5486.14
- 05.5486.ER
- 05.5486.ES

Dali
- 05.5486.40.DA
- 05.5486.14.DA
- 05.5486.ER.DA
- 05.5486.ES.DA

Casambi
- 05.5486.40.CB
- 05.5486.14.CB
- 05.5486.ER.CB
- 05.5486.ES.CB



Luminous flux luminaire
599 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	5434	0.35
2	1358	0.69
3	604	1.04
4	340	1.39
5	217	1.73

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

NEW

Optic Flood - 2700K

Non Dimmable

- 05.5482.40
- 05.5482.14
- 05.5482.ER
- 05.5482.ES

Dali


- 05.5482.40.DA
- 05.5482.14.DA
- 05.5482.ER.DA
- 05.5482.ES.DA

Casambi

- 05.5482.40.CB
- 05.5482.14.CB
- 05.5482.ER.CB
- 05.5482.ES.CB



FLOOD



Luminous flux luminaire
588 lm

Beam Angle: 30°

h(m)	E(lx)	D(m)
1	2151	0.54
2	538	1.09
3	239	1.63
4	134	2.18
5	86	2.72

Optic Flood - 3000K

Non Dimmable

- 05.5487.40
- 05.5487.14
- 05.5487.ER
- 05.5487.ES

Dali


- 05.5487.40.DA
- 05.5487.14.DA
- 05.5487.ER.DA
- 05.5487.ES.DA

Casambi

- 05.5487.40.CB
- 05.5487.14.CB
- 05.5487.ER.CB
- 05.5487.ES.CB



FLOOD



Luminous flux luminaire
615 lm

Beam Angle: 31°

h(m)	E(lx)	D(m)
1	2181	0.56
2	545	1.11
3	242	1.67
4	136	2.22
5	87	2.78

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.
El sistema de control con las luminarias versión Casambi, se regula directa e individualmente vía inalámbrica mediante la aplicación FLOS Control® by Casambi.

FIND ME

DESIGNED BY JORGE HERRERA

FIND ME 0
TRIM / NO TRIM



LIGHT SOURCE
POWER LED
3,5W
300 lm
2700K/CRI 90
325 lm
3000K/CRI 90

FIND ME 1
TRIM / NO TRIM



FIND ME 1
SUSPENSION



LIGHT SOURCE
POWER LED
6W
560 lm
2700K/CRI 90
600 lm
3000K/CRI 90

FIND ME 2
TRIM / NO TRIM



LIGHT SOURCE
POWER LED
10W
860 lm
2700K/CRI 90
900 lm
3000K/CRI 90

30 White
30 Blanco

14 Black
14 Negro

05 Polished Silver
05 Plata Pulida

Mono Point



Suspension



Screening Cylinder Colours (included)
Colores del Cilindro Apantallador (incluidos)


Orange
Naranja

Black
Negro

Violet
Violeta



Can be rotated 360° and swivelled 90°.
Puede ser rotado 360° y orientado 90°.



reddot design award
winner 2013

Description
Spotlight family for indoor use, easy to mount on plasterboard ceilings and tracks. The luminaire is available in the Mono Point, Track and Suspension versions.
The Mono Point version is supplied with a recessed cylindrical frame which houses the lighting module. This lighting module can be placed in its upper position, functioning as a downlight, or in its lower position, becoming an adjustable spotlight.
The Mono Point version is supplied with a frame, installable fitted to the product if a Trim version is required, or not fitted if a No Trim version is required.
The Suspension version is a variant of the Mono Point version. Its main feature is its suspended mounting.
The Track version is supplied with an adapter for being used on three-phase tracks.

Reflectors
The models for installation in plasterboard ceilings are supplied with accent lighting optics. The track version is available in Spot, Medium and Flood optics.

Power Supply
For plasterboard ceiling installation versions, the product is supplied prewired, ready to be connected to a remote power supply (not included) installed in an accessible location or to be passed through the ceiling cut-out:
Find Me 0: 50 mm.
Find Me 1: 62 mm.
Find Me 2: 70 mm.

Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Accessories
The Suspension version comes with an anti-glare cylinder in 3 colors: orange, violet or black, which are interchangeable between them and incorporated into the light fixture. For Find Me 1 and 2: professional accessories included.

Additional Information
Orientation system allowing 360° rotation on the vertical axis and 90° on the horizontal axis.
IP20 protection rating.
Class III insulation, for Mono Point and Suspension versions.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
The luminaire complies with the EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Familia de proyectores de interiores con una fácil instalación en carril y en techos de cartón yeso. La luminaria está disponible en las versiones: Mono Point, Track y Suspension.
La versión Mono Point se suministra con un marco cilíndrico empotrable sobre el que se instala el módulo de iluminación. Dicho módulo de iluminación puede colocarse en su posición superior, funcionando como un donwlight, o en su posición inferior, convirtiéndose en un proyector orientable.
La versión Mono Point se suministra con un marco, aplicable al producto en caso de desear versión Trim, o no instalable en caso de desear versión No Trim.
La versión Suspension es una variante de la versión Mono Point. Su principal característica es su instalación mediante suspensión.
La versión Track se suministra con un adaptador para su uso en carriles trifásicos.

Reflectores
Los modelos de instalación en techos de cartón yeso se suministran en óptica accent lighting. La versión para carril se ofrece en ópticas Spot, Medium y Flood.

Unidades de Alimentación
En las versiones con instalación en techos de cartón yeso, el producto se suministra precableado para ser conectado a una fuente de alimentación remota (no incluida) instalada en un lugar accesible o que pase a través del agujero de empotramiento:
Find Me 0: 50 mm.
Find Me 1: 62 mm.
Find Me 2: 70 mm.

Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (Drivers).

Accesorios
La versión Suspension dispone de cilindro apantallador en 3 colores: naranja, violeta o negro, intercambiables entre sí, incluidos dentro de la luminaria. Para el Find Me 1 y 2: accesorios profesionales incluidos.

Información Adicional
Sistema de orientación que permite la rotación 360° en el eje vertical y 90° en el eje horizontal.
Índice de protección IP20.
Clase de aislamiento III, para las versiones Mono Point y Suspension.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Suspension Surface

Suspension Recessed


Mono Point No Trim


Mono Point Trim

Find Me 0 (Trim / No Trim)

Power LED DC 250 mA - 3W - 300 lm - 2700K/CRI 90 / 3W - 325 lm - 3000K/CRI 90







Recessed adjustable luminaire for indoor application. Remote power supply 250 mA not included. Accessories included (honeycomb and screening crosspiece). Remote power supply to be installed in an accessible place. It is not recommended to use dimmable drivers of several brands due to the specific dimming curves of each brand.

Luminaria empotrada de interiores orientable. Fuente de alimentación remota 250 mA no incluida. Accesorios incluidos (honeycomb y cruceta de apantallamiento). Fuente de alimentación remota para ser instalada en un lugar accesible. No se recomienda utilizar drivers regulables de diferentes marcas por tener curvas de regulación particulares.


Recommended power supply and number of luminaires per driver (L)* / Equipos recomendados y número de luminarias por driver (L)*:

1/2/3L* Non Dimmable 100-240V	60.9744
1/2/3L* Non Dimmable 220-240V	60.9160
1/2/3L* Dimmable Dali 2 220-240V	60.9601
1/2/3L* Dimmable 0-10V 220-240V	60.9405
2/3L* Mains Dimming 220-240V	60.9421
Casambi	60.9392 + 0-10V/Dali driver

Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 09.3781.30A
- 09.3781.05A
- 09.3781.14A




Luminous flux luminaire
170 lm (EXTREME CUT OFF)

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	786	0.45
2	197	0.91
3	87	1.36
4	49	1.82
5	31	2.27

3000K

- 09.3780.30A
- 09.3780.05A
- 09.3780.14A



Luminous flux luminaire
189 lm (EXTREME CUT OFF)

Beam Angle: 26°


h(m)	E(lx)	D(m)
1	877	0.45
2	219	0.91
3	97	1.36
4	55	1.82
5	35	2.27


Find Me 1 (Trim / No Trim)

Power LED DC 500 mA - 6W - 560 lm - 2700K/CRI 90 / 6W - 600 lm - 3000K/CRI 90









Recessed adjustable luminaire for indoor application. Remote power supply 500 mA not included. Accessories included (honeycomb and screening crosspiece). Remote power supply to be installed in an accessible place.


Luminaria empotrada de interiores orientable. Fuente de alimentación remota 500 mA no incluida. Accesorios incluidos (honeycomb y cruceta de apantallamiento). Fuente de alimentación remota para ser instalada en un lugar accesible.

Recommended power supply / Equipos recomendados*:

Non Dimmable 220-240V	60.9160
Non Dimmable 110-240V	60.8880
Dimmable Dali 2 110-240V	60.9222
Mains Dimming 220-240V	60.9467
Dimmable 0/1-10V&Push 110/240V	60.9188
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
09.3751.30A
09.3751.05A
09.3751.14A




Luminous flux luminaire
344 lm (EXTREME CUT OFF)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4642	0.24
2	1160	0.48
3	516	0.72
4	290	0.95
5	186	1.19

3000K
09.3750.30A
09.3750.05A
09.3750.14A




Luminous flux luminaire
365 lm (EXTREME CUT OFF)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4881	0.24
2	1220	0.49
3	542	0.73
4	305	0.97
5	195	1.21

2700K
09.3756.30A
09.3756.05A
09.3756.14A




Luminous flux luminaire
321 lm (EXTREME CUT OFF)

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2784	0.31
2	696	0.62
3	309	0.93
4	174	1.23
5	111	1.54

3000K
09.3755.30A
09.3755.05A
09.3755.14A



Luminous flux luminaire
350 lm (EXTREME CUT OFF)

Beam Angle: 18°


h(m)	E(lx)	D(m)
1	3036	0.31
2	759	0.62
3	337	0.93
4	190	1.23
5	121	1.54


Find Me 2 (Trim / No Trim)

Power LED DC max 850 mA - 10W - 915 Lm - 2700K/CRI 90 / 10W - 960 lm - 3000K/CRI 90









Recessed adjustable luminaire for indoor application. Remote power supply not included.
Accessories included (honeycomb and screening crosspiece).
Remote power supply to be installed in an accessible place.


Luminaria empotrada de interiores orientable. Fuente de alimentación remota no incluida.
Accesorios incluidos (honeycomb y cruceta de apantallamiento).
Fuente de alimentación remota para ser instalada en un lugar accesible.

Recommended power supply / Equipos recomendados*:

Non Dimmable MC 110-240V	60.8911
Non Dimmable MC 220-240V	60.7677
Non Dimmable 700mA 110-240V	60.8529A
Dimmable Dali 1 220-240V	60.7678
Mains Dimming	60.9467
Dim 1-10V/Dim Dali/Push MC 110-240V	60.8530
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
- 09.3707.30C
- 09.3707.05C
- 09.3707.14C




Luminous flux luminaire
693 lm (EXTREME CUT OFF)

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	5686	0.32
2	1421	0.64
3	632	0.96
4	355	1.28
5	227	1.60

3000K
- 09.3708.30C
- 09.3708.05C
- 09.3708.14C



Luminous flux luminaire
731 lm (EXTREME CUT OFF)

Beam Angle: 18°


h(m)	E(lx)	D(m)
1	5997	0.32
2	1499	0.64
3	666	0.96
4	375	1.28
5	240	1.60


	2700K		3000K	
Driver current (mA)	**Luminous flux (lm)**	**Power (W)**	**Luminous flux (lm)**	**Power (W)**
850	915	10	960	10
800	870	9	916	9
750	825	8,5	870	8,5
700	775	8	825	8

Find Me 1 Suspension

Power LED DC 500 mA - 6W - 560 lm - 2700K/CRI 90 / 6W - 600 lm - 3000K/CRI 90







Suspended ceiling-mounted luminaire. The product includes interchangeable shield cylinder in different colours (orange, violet and black). Remote power supply 500 mA not included.

Luminaria para ser instalada a techo mediante suspensión. El producto incluye cilindro apantallador intercambiable de distintos colores (naranja, violeta y negro). Fuente de alimentación remota 500 mA no incluida.


Recommended power supply / Equipos recomendados*:

Non Dimmable 220-240V	60.9160
Non Dimmable 110-240V	60.8880
Dimmable Dali 2 110-240V	60.9222
Mains Dimming 220-240V	60.9467
Dimmable 0/1-10V&Push 110/240V	60.9188
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 09.3711.30C
- 09.3711.05C
- 09.3711.14C




Luminous flux luminaire
344 lm (EXTREME CUT OFF)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4642	0.24
2	1160	0.48
3	516	0.72
4	290	0.95
5	186	1.19

3000K

- 09.3710.30C
- 09.3710.05C
- 09.3710.14C



Luminous flux luminaire
365 lm (EXTREME CUT OFF)

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4881	0.24
2	1220	0.49
3	542	0.73
4	305	0.97
5	195	1.21


Accessories / Accesorios

Recessed power supply rose.

Rosetón de alimentación empotrado.




08.8782.30



Surface power supply rose.

Rosetón de alimentación de superficie.



Non Dimmable

- 08.8783.30A
- 08.8783.05A
- 08.8783.14A

Dali

- 08.8783.30ADA
- 08.8783.05ADA
- 08.8783.14ADA

UT SPOT CEILING Ø57



LIGHT SOURCE
LED ARRAY
23,5W
2400 lm
3000K/CRI 80
Up to 18,7W
1950 lm
3000K/CRI 90
2150 lm
4000K/CRI 90

UT SPOT CEILING Ø86



LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
33W
3960 lm
3000K/CRI 80
Up to 32,4W
3250 lm
3000K/CRI 90
3500 lm
4000K/CRI 90

UT SPOT TRACK Ø57



LIGHT SOURCE
LED ARRAY
23,5W
2500 lm
3000K/CRI 80
Up to 19W
2000 lm
3000K/CRI 90
2150 lm
4000K/CRI 90

UT SPOT TRACK Ø86



LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
33W
3960 lm
3000K/CRI 80
Up to 32,8W
3250 lm
3000K/CRI 90
3500 lm
4000K/CRI 90

UT SPOT TRACK WALL-WASHER Ø86



LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
33W
3960 lm
3000K/CRI 80
Up to 32,8W
3250 lm
3000K/CRI 90
3500 lm
4000K/CRI 90

UT SPOT TRACK Ø57



LIGHT SOURCE
LED ARRAY
23,5W
2500 lm
3000K/CRI 80
Up to 19,5W
2000 lm
3000K/CRI 90
2150 lm
4000K/CRI 90

UT SPOT TRACK Ø86



LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
33,8W
3770 lm
3000K/CRI 80
Up to 14,7W
3116 lm
3000K/CRI 90
3246 lm
4000K/CRI 90

UT SPOT TRACK MULTICHIP Ø86



LIGHT SOURCE
TOP LED
11,5W
850 lm
3000K/CRI 90
950 lm
3000K/CRI 80
1000 lm
4000K/CRI 80

UT SPOT TRACK WALL-WASHER Ø86



LIGHT SOURCE
LED ARRAY
HIGH
PERFORMANCES
33W
3960 lm
3000K/CRI 80
Up to 32,1W
3250 lm
3000K/CRI 90
3500 lm
4000K/CRI 90

UT PRO 150 GA-69	UT PRO 175 GA-69	UT PRO 175 LENS GA-69	UT PRO WALL-WASHER GA-69
			
LIGHT SOURCE LED ARRAY 20W 2294 lm 3000K/CRI 80 1984 lm 3000K/CRI 90 2145 lm 4000K/CRI 90	**LIGHT SOURCE** LED ARRAY 46,5W 4740 lm 3000K/CRI 80 3960 lm 3000K/CRI 90 4278 lm 4000K/CRI 90	**LIGHT SOURCE** LED ARRAY 35,3W 3950 lm 3000K/CRI 80 3250 lm 3000K/CRI 90 3400 lm 4000K/CRI 90	**LIGHT SOURCE** TOP LED 25,5W 2700 lm 3000K/CRI 90 2900 lm 4000K/CRI 90

☐ 30 White
30 Blanco

■ 14 Black
14 Negro





☐ 30 White
30 Blanco

■ 14 Black
14 Negro

☐ 30.78 All White
30.78 All White













UT PRO 150	UT PRO 175	UT PRO 175 LENS	UT PRO WALL-WASHER
			

* Refer to The Tracking Power chapter / Ver capítulo The Tracking Power

Description
A luminaire for indoor use to be mounted on three phase track or on ceilings, available in LED technology light sources and in DALI and non-DIM versions.
The family is available in various models / sizes (Ø57 Ø75 and Ø86 and Rectagular WW) and two mounting options are available: Track (complete installation flexibility) and Ceiling (independent installation).
The luminaire offers the Multichip variant (to obtain opening angles *Super Spot*) and the cylindrical Wall-Washer (only Ø86 version).
The optical housing of the luminaire is manufactured in high-pressure injected aluminium, with white or black finishes.
Remote driver included in ceiling versions.
Also available UT Downlight (see Downlights catalogue section).

Power Supply
Not dimmable or dimmable Dali 220-240V, constant current, power supply included.
Includes a on board potentiometer in the track with box version. Versions with a on board adapter do not include a potentiometer.

Light Source
Possibility to integrate a different type of LED upon request. For more information, please contact our team.

Accessories
- Screening crosspiece, elliptical lens, flood lens and honeycomb.
- Support ring (UT Spot ø86).

Additional Information
Suitable for installation on normally inflammable surfaces.
FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. To verify compatibility with any other track, please contact FLOS before installation.
FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.
- UT Spot ø86 (Track / Ceiling):
The LED modules installed on the LED Array versions have cutting-edge technology that permit a lower average temperature in the electronics. Thanks to this feature, the luminaire can operate at a higher power inside the safety parameters, yet still offer 20% added luminous flux.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria de interior para ser instalada a carril trifásico o sobre techos, disponible con fuentes de luz de tecnología LED de alta potencia y en versión Dali y No DIM.
La familia está disponible en varios modelos / tamaños (Ø57 Ø 75 y Ø86 y Rectagular WW) y se ofrece en dos opciones de montaje: Track (flexibilidad de instalación total), Ceiling (instalación independiente).
Esta luminaria ofrece variatnes Multichip (para logar ángulos de apertura *Super Spot*) y Wall-Washer de formato cilíndrico (solo versión Ø86).
El cuerpo óptico de la luminaria está fabricado en aluminio inyectado a alta presión, acabados en pintura polvo de color blanco o negro.
Las luminarias a techo incluyen equipo de alimentación remoto.
También disponible UT Downlight (ver la sección Downlights del catálogo).

Unidades de Alimentación
Fuente de alimentación de corriente constante no regulable o regulable Dali 220-240V incluida.
Con potenciómetro incorporado en la versión track con caja. Las versiones con adaptador integrado no disponen de potenciómetro.

Fuente de luz
Posibilidad de integrar otro tipo de LED bajo demanda. Para más información, no dude en contactar con nuestro equipo.

Accesorios
- Disponibles cruceta de apantallamiento, lente elíptica, lente flood y honeycomb.
- Aro soporte (UT Spot ø86).

Información Adicional
Instalable sobre superficies normalmente inflamables.
Las luminarias de FLOS a carril trifásico estándar están diseñadas y completamente probadas para los carriles recomendados por FLOS. Su compatibilidad está garantizada con carriles trifásicos fabricados por Nordic Aluminium. Compatibilidad con Eutrac bajo pedido. Si desea confirmar su compatibilidad con otros carriles, póngase en contacto con FLOS antes de instalarlas.
Las luminarias de FLOS a carril trifásico DALI están diseñadas para Pulse DALI de Nordic Aluminium.
- UT Spot ø86 (Track / Ceiling):
Los módulos LED instalados en las versiones LED Array cuentan con la última generación tecnológica que permite una menor temperatura media en el funcionamiento de la electrónica. Gracias a esta característica, la luminaria puede operar dentro de parámetros de seguridad a una mayor potencia, ofreciendo una aumento del 20% del flujo luminoso.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.


UT Spot Ceiling


UT Spot Track

Ut Spot Ceiling Ø57

LED Array
Non Dimming: 23,5W - 2400 lm - 3000K/CRI 80 / 18,3W - 1950 lm - 3000K/CRI 90 / 18,3W - 2150 lm - 4000K/CRI 90
Dali: 23,5W - 2400 lm - 3000K/CRI 80 / 18,7W - 1950 lm - 3000K/CRI 90 / 18,7W - 2150 lm - 4000K/CRI 90








Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

Proyector para ser instalado a techo con fuente de luz LED. Fuente de alimentación remota 220-240V, 50-60Hz incluida.

3000K - CRI 80
Non Dimmable
- 09.4460.30A
- 09.4460.14A

Dali Version
- 09.4460.30ADA
- 09.4460.14ADA

10° SPOT



Luminous flux luminaire 1255 lm


Beam Angle: 10°

h(m)	E(lx)	D(m)
1	14650	0.18
2	3662	0.36
3	1628	0.54
4	916	0.72
5	586	0.90

4000K - CRI 90
Non Dimmable
- 09.4470.30C
- 09.4470.14C

Dali Version
- 09.4470.30CDA
- 09.4470.14CDA

10° SPOT



Luminous flux luminaire 1094 lm


Beam Angle: 10°

h(m)	E(lx)	D(m)
1	12780	0.18
2	3195	0.36
3	1420	0.54
4	799	0.72
5	511	0.90

3000K - CRI 90
Non Dimmable
- 09.4463.30C
- 09.4463.14C

Dali Version
- 09.4463.30CDA
- 09.4463.14CDA

10° SPOT



Luminous flux luminaire 997 lm


Beam Angle: 10°

h(m)	E(lx)	D(m)
1	11643	0.18
2	2911	0.36
3	1294	0.54
4	728	0.72
5	466	0.90

3000K - CRI 80
Non Dimmable
- 09.4461.30A
- 09.4461.14A

Dali Version
- 09.4461.30ADA
- 09.4461.14ADA

21° MEDIUM



Luminous flux luminaire 1184 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	6515	0.37
2	1629	0.73
3	724	1.10
4	407	1.47
5	261	1.83

4000K - CRI 90
Non Dimmable
- 09.4471.30C
- 09.4471.14C

Dali Version
- 09.4471.30CDA
- 09.4471.14CDA

21° MEDIUM



Luminous flux luminaire 1033 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5683	0.37
2	1421	0.73
3	631	1.10
4	355	1.47
5	227	1.83

3000K - CRI 90
Non Dimmable
- 09.4464.30C
- 09.4464.14C

Dali Version
- 09.4464.30CDA
- 09.4464.14CDA

21° MEDIUM



Luminous flux luminaire 941 lm


Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5178	0.37
2	1294	0.73
3	575	1.10
4	324	1.47
5	207	1.83

3000K - CRI 80
Non Dimmable
- 09.4462.30A
- 09.4462.14A

Dali Version
- 09.4462.30ADA
- 09.4462.14ADA

42° FLOOD



Luminous flux luminaire 1394 lm


Beam Angle: 42°

h(m)	E(lx)	D(m)
1	3301	0.76
2	825	1.52
3	367	2.28
4	206	3.05
5	132	3.81

4000K - CRI 90
Non Dimmable
- 09.4472.30C
- 09.4472.14C

Dali Version
- 09.4472.30CDA
- 09.4472.14CDA

42° FLOOD



Luminous flux luminaire 1216 lm


Beam Angle: 42°

h(m)	E(lx)	D(m)
1	2879	0.76
2	720	1.52
3	320	2.28
4	180	3.05
5	115	3.81

3000K - CRI 90
Non Dimmable
- 09.4465.30C
- 09.4465.14C

Dali Version
- 09.4465.30CDA
- 09.4465.14CDA

42° FLOOD



Luminous flux luminaire 1108 lm


Beam Angle: 42°


h(m)	E(lx)	D(m)
1	2623	0.76
2	656	1.52
3	291	2.28
4	164	3.05
5	105	3.81

Ut Spot Ceiling Ø86

LED Array High Performances
Non Dimming: 33W - 3960 lm - 3000K/CRI 80 / 31,9W - 3250 lm - 3000K/CRI 90 / 31,9W - 3500 lm - 4000K/CRI 90
Dali: 33W - 3960 lm - 3000K/CRI 80 / 32,4W - 3250 lm - 3000K/CRI 90 / 32,4W - 3500 lm - 4000K/CRI 90








Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

Proyector para ser instalado a techo con fuente de luz LED. Fuente de alimentación remota 220-240V, 50-60Hz incluida.

3000K - CRI 80
Non Dimmable
09.4860.30A
09.4860.14A
Dali Version
09.4860.30BDA
09.4860.14BDA

12° SPOT




Luminous flux luminaire 2650 lm

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	34142	0.21
2	8535	0.41
3	3794	0.62
4	2134	0.82
5	1366	1.03

4000K - CRI 90
Non Dimmable
09.4870.30C
09.4870.14C
Dali Version
09.4870.30CDA
09.4870.14CDA

12° SPOT




Luminous flux luminaire 2281 lm

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	29396	0.21
2	7349	0.41
3	3266	0.62
4	1837	0.82
5	1176	1.03

3000K - CRI 90
Non Dimmable
09.4863.30C
09.4863.14C
Dali Version
09.4863.30CDA
09.4863.14CDA

12° SPOT




Luminous flux luminaire 2190 lm

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	28219	0.21
2	7055	0.41
3	3135	0.62
4	1764	0.82
5	1129	1.03

3000K - CRI 80
Non Dimmable
09.4861.30A
09.4861.14A
Dali Version
09.4861.30BDA
09.4861.14BDA

24° MEDIUM




Luminous flux luminaire 2528 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	11472	0.43
2	2868	0.86
3	1275	1.28
4	717	1.71
5	459	2.14

4000K - CRI 90
Non Dimmable
09.4871.30C
09.4871.14C
Dali Version
09.4871.30CDA
09.4871.14CDA

24° MEDIUM




Luminous flux luminaire 2176 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	9877	0.43
2	2469	0.86
3	1097	1.28
4	617	1.71
5	395	2.14

3000K - CRI 90
Non Dimmable
09.4864.30C
09.4864.14C
Dali Version
09.4864.30CDA
09.4864.14CDA

24° MEDIUM




Luminous flux luminaire 2089 lm

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	9482	0.43
2	2370	0.86
3	1054	1.28
4	593	1.71
5	379	2.14

3000K - CRI 80
Non Dimmable
09.4862.30A
09.4862.14A
Dali Version
09.4862.30BDA
09.4862.14BDA

37° FLOOD




Luminous flux luminaire 2408 lm

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	6735	0.67
2	1684	1.34
3	748	2.01
4	421	2.69
5	269	3.36

4000K - CRI 90
Non Dimmable
09.4872.30C
09.4872.14C
Dali Version
09.4872.30CDA
09.4872.14CDA

37° FLOOD




Luminous flux luminaire 2074 lm

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	5799	0.67
2	1450	1.34
3	644	2.01
4	362	2.69
5	232	3.36

3000K - CRI 90
Non Dimmable
09.4865.30C
09.4865.14C
Dali Version
09.4865.30CDA
09.4865.14CDA

37° FLOOD



Luminous flux luminaire 1991 lm


Beam Angle: 37°


h(m)	E(lx)	D(m)
1	5566	0.67
2	1392	1.34
3	618	2.01
4	348	2.69
5	223	3.36

Ut Spot Track Ø57

LED Array
Non Dimming: 23,5W - 2500 lm - 3000K/CRI 80 / 18,3W - 2000 lm - 3000K/CRI 90 / 18,3W- 2150 lm - 4000K/CRI 90
Dali: 23,5W - 2500 lm - 3000K/CRI 80 / 19W - 2000 lm - 3000K/CRI 90 / 19W- 2150 lm - 4000K/CRI 90







Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

.30 versions come with the track adapter, the arm and the rear of the head in black. In the “All white” versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.

Las versiones .30 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas, solo el anillo anti-deslumbramiento permanece en color negro.

Finishes Available



3000K - CRI 80
Non Dimmable
- 09.7700.30A
- 09.7700.14A

Non Dimmable All White
- 09.7700.30A78

Dali 2
- 09.7700.30CDA
- 09.7700.14CDA

Dali 2 All White
- 09.7700.30CYU


3000K - CRI 90
Non Dimmable
- 09.7706.30C
- 09.7706.14C

Non Dimmable All White
- 09.7706.30C78

Dali 2
- 09.7706.30CDA
- 09.7706.14CDA


Dali 2 All White
- 09.7706.30CYU

10° SPOT



Luminous flux luminaire 1255 lm

Beam Angle: 10°		
h(m)	E(lx)	D(m)
1	14650	0.18
2	3662	0.36
3	1628	0.54
4	916	0.72
5	586	0.90



Luminous flux luminaire 997 lm

Beam Angle: 10°		
h(m)	E(lx)	D(m)
1	11643	0.18
2	2911	0.36
3	1294	0.54
4	728	0.72
5	466	0.90


4000K - CRI 90
Non Dimmable
- 09.7701.30C
- 09.7701.14C

Non Dimmable All White
- 09.7701.30C78

Dali 2
- 09.7701.30CDA
- 09.7701.14CDA

Dali 2 All White
- 09.7701.30CYU

10° SPOT



Luminous flux luminaire 1094 lm

Beam Angle: 10°		
h(m)	E(lx)	D(m)
1	12780	0.18
2	3195	0.36
3	1420	0.54
4	799	0.72
5	511	0.90

3000K - CRI 80
Non Dimmable
- 09.7702.30A
- 09.7702.14A

Non Dimmable All White
- 09.7702.30A78

Dali 2
- 09.7702.30CDA
- 09.7702.14CDA

Dali 2 All White
- 09.7702.30CYU


3000K - CRI 90
Non Dimmable
- 09.7707.30C
- 09.7707.14C

Non Dimmable All White
- 09.7707.30C78

Dali 2
- 09.7707.30CDA
- 09.7707.14CDA


Dali 2 All White
- 09.7707.30CYU

21° MEDIUM



Luminous flux luminaire 1184 lm

Beam Angle: 21°		
h(m)	E(lx)	D(m)
1	6515	0.37
2	1629	0.73
3	724	1.10
4	407	1.47
5	261	1.83



Luminous flux luminaire 941 lm

Beam Angle: 21°		
h(m)	E(lx)	D(m)
1	5178	0.37
2	1294	0.73
3	575	1.10
4	324	1.47
5	207	1.83


4000K - CRI 90
Non Dimmable
- 09.7703.30C
- 09.7703.14C

Non Dimmable All White
- 09.7703.30C78

Dali 2
- 09.7703.30CDA
- 09.7703.14CDA

Dali 2 All White
- 09.7703.30CYU

21° MEDIUM



Luminous flux luminaire 1033 lm

Beam Angle: 21°		
h(m)	E(lx)	D(m)
1	5683	0.37
2	1421	0.73
3	631	1.10
4	355	1.47
5	227	1.83

3000K - CRI 80
Non Dimmable
- 09.7704.30A
- 09.7704.14A

Non Dimmable All White
- 09.7704.30A78

Dali 2
- 09.7704.30CDA
- 09.7704.14CDA

Dali 2 All White
- 09.7704.30CYU


3000K - CRI 90
Non Dimmable
- 09.7708.30C
- 09.7708.14C

Non Dimmable All White
- 09.7708.30C78

Dali 2
- 09.7708.30CDA
- 09.7708.14CDA


Dali 2 All White
- 09.7708.30CYU

42° FLOOD



Luminous flux luminaire 1394 lm

Beam Angle: 42°		
h(m)	E(lx)	D(m)
1	3301	0.76
2	825	1.52
3	367	2.28
4	206	3.05
5	132	3.81



Luminous flux luminaire 1108 lm

Beam Angle: 42°		
h(m)	E(lx)	D(m)
1	2623	0.76
2	656	1.52
3	291	2.28
4	164	3.05
5	105	3.81


4000K - CRI 90
Non Dimmable
- 09.7705.30C
- 09.7705.14C

Non Dimmable All White
- 09.7705.30C78

Dali 2
- 09.7705.30CDA
- 09.7705.14CDA

Dali 2 All White
- 09.7705.30CYU

42° FLOOD




Luminous flux luminaire 1216 lm


Beam Angle: 42°		
h(m)	E(lx)	D(m)
1	2879	0.76
2	720	1.52
3	320	2.28
4	180	3.05
5	115	3.81

Ut Spot Track Ø86

LED Array High Performances
Non Dimming: 33W - 3770 lm - 3000K/CRI 80 / 32,3W - 3116 lm - 3000K/CRI 90 / 32,3W - 3246 lm - 4000K/CRI 90
Dali: 33W - 3770 lm - 3000K/CRI 80 / 32,8W - 3116 lm - 3000K/CRI 90 / 32,8W - 3246 lm - 4000K/CRI 90







Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

.30 versions come with the track adapter, the arm and the rear of the head in black. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.

Las versiones .30 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones "all white" el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas, solo el anillo anti-deslumbramiento permanece en color negro.


Finishes Available



3000K - CRI 80
Non Dimmable
09.7750.30B
09.7750.14B
Non Dimmable All White
09.7750.30B78
Dali 2
09.7750.30BDA
09.7750.14BDA
Dali 2 All White
09.7750.30BYU

3000K - CRI 90
Non Dimmable
09.7756.30C
09.7756.14C
Non Dimmable All White
09.7756.30C78
Dali 2
09.7756.30CDA
09.7756.14CDA
Dali 2 All White
09.7756.30CYU


12° SPOT



Luminous flux luminaire 2650 lm

Beam Angle:	12°
h(m)	E(lx) D(m)
1	34142 0.21
2	8535 0.41
3	3794 0.62
4	2134 0.82
5	1366 1.03

12° SPOT




Luminous flux luminaire 2190 lm

Beam Angle:	12°
h(m)	E(lx) D(m)
1	28219 0.21
2	7055 0.41
3	3135 0.62
4	1764 0.82
5	1129 1.03

4000K - CRI 90
Non Dimmable
09.7751.30C
09.7751.14C
Non Dimmable All White
09.7751.30C78
Dali 2
09.7751.30CDA
09.7751.14CDA
Dali 2 All White
09.7751.30CYU

12° SPOT




Luminous flux luminaire 2281 lm

Beam Angle:	12°
h(m)	E(lx) D(m)
1	29396 0.21
2	7349 0.41
3	3266 0.62
4	1837 0.82
5	1176 1.03

3000K - CRI 80
Non Dimmable
09.7752.30B
09.7752.14B
Non Dimmable All White
09.7752.30B78
Dali 2
09.7752.30BDA
09.7752.14BDA
Dali 2 All White
09.7752.30BYU

3000K - CRI 90
Non Dimmable
09.7757.30C
09.7757.14C
Non Dimmable All White
09.7757.30C78
Dali 2
09.7757.30CDA
09.7757.14CDA
Dali 2 All White
09.7757.30CYU


24° MEDIUM



Luminous flux luminaire 2528 lm

Beam Angle:	24°
h(m)	E(lx) D(m)
1	11472 0.43
2	2868 0.86
3	1275 1.28
4	717 1.71
5	459 2.14

24° MEDIUM




Luminous flux luminaire 2089 lm

Beam Angle:	24°
h(m)	E(lx) D(m)
1	9482 0.43
2	2370 0.86
3	1054 1.28
4	593 1.71
5	379 2.14

4000K - CRI 90
Non Dimmable
09.7753.30C
09.7753.14C
Non Dimmable All White
09.7753.3C78
Dali 2
09.7753.30CDA
09.7753.14CDA
Dali 2 All White
09.7753.30CYU

24° MEDIUM




Luminous flux luminaire 2176 lm

Beam Angle:	24°
h(m)	E(lx) D(m)
1	9877 0.43
2	2469 0.86
3	1097 1.28
4	617 1.71
5	395 2.14

3000K - CRI 80
Non Dimmable
09.7754.30B
09.7754.14B
Non Dimmable All White
09.7754.30B78
Dali 2
09.7754.30BDA
09.7754.14BDA
Dali 2 All White
09.7754.30BYU

3000K - CRI 90
Non Dimmable
09.7758.30C
09.7758.14C
Non Dimmable All White
09.7758.30C78
Dali 2
09.7758.30CDA
09.7758.14CDA
Dali 2 All White
09.7758.30CYU


37° FLOOD



Luminous flux luminaire 2408 lm

Beam Angle:	37°
h(m)	E(lx) D(m)
1	6735 0.67
2	1684 1.34
3	748 2.01
4	421 2.69
5	269 3.36

37° FLOOD




Luminous flux luminaire 1991 lm

Beam Angle:	37°
h(m)	E(lx) D(m)
1	5566 0.67
2	1392 1.34
3	618 2.01
4	348 2.69
5	223 3.36

4000K - CRI 90
Non Dimmable
09.7755.30C
09.7755.14C
Non Dimmable All White
09.7755.30C78
Dali 2
09.7755.30CDA
09.7755.14CDA
Dali 2 All White
09.7755.30CYU

37° FLOOD




Luminous flux luminaire 2074 lm


Beam Angle:	37°
h(m)	E(lx) D(m)
1	5799 0.67
2	1450 1.34
3	644 2.01
4	362 2.69
5	232 3.36

Ut Spot Track Wall-Washer Ø86

LED Array High Performances
Non Dimming: 33W - 3960 lm - 3000K/CRI 80 / 32,3W - 3250 lm - 3000K/CRI 90 / 32,3W - 3500 lm - 4000K/CRI 90
Dali: 33W - 3960 lm - 3000K/CRI 80 / 32,8W - 3250 lm - 3000K/CRI 90 / 32,8W - 3500 lm - 4000K/CRI 90







Finishes Available



Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

.30 versions come with the track adapter, the arm and the rear of the head in black. In the “All white” versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.

Las versiones .30 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas, solo el anillo anti-deslumbramiento permanece en color negro.

3000K - CRI 80


Non Dimmable
- ☐ 09.7770.30B
- ■ 09.7770.14B

All White
- ☐ 09.7770.30B78

Dali 2
- ☐ 09.7770.30BDA
- ■ 09.7770.14BDA

Dali 2 All White
- ☐ 09.7770.30BYU

50°



Luminous flux luminaire
2560 lm

Beam Angle: 50°

h(m)	E(lx)	D(m)
1	2596	0.98
2	649	1.97
3	288	2.95
4	162	3.94
5	104	4.92

3000K - CRI 90


Non Dimmable
- ☐ 09.7771.30C
- ■ 09.7771.14C

All White
- ☐ 09.7771.30C78

Dali 2
- ☐ 09.7771.30CDA
- ■ 09.7771.14CDA

Dali 2 All White
- ☐ 09.7771.30CYU

50°



Luminous flux luminaire
2116 lm

Beam Angle: 50°

h(m)	E(lx)	D(m)
1	2146	0.98
2	537	1.97
3	238	2.95
4	134	3.94
5	86	4.92

4000K - CRI 90


Non Dimmable
- ☐ 09.7772.30C
- ■ 09.7772.14C

All White
- ☐ 09.7772.30C78

Dali 2
- ☐ 09.7772.30CDA
- ■ 09.7772.14CDA

Dali 2 All White
- ☐ 09.7772.30CYU

50°



Luminous flux luminaire
2204 lm


Beam Angle: 50°


h(m)	E(lx)	D(m)
1	2236	0.98
2	559	1.97
3	248	2.95
4	140	3.94
5	89	4.92

Ut Spot Track Ø57

LED Array
Non Dimming: 23,5W - 2500 lm - 3000K/CRI 80 / 18,5W - 2000 lm - 3000K/CRI 90 / 18,5W - 2150 lm - 4000K/CRI 90
Dali: 23,5W - 2500 lm - 3000K/CRI 80 / 18,7W - 2000 lm - 3000K/CRI 90 / 18,7W - 2150 lm - 4000K/CRI 90
Dim on board: 23,5W - 2500 lm - 3000K/CRI 80 / 19,5W - 2000 lm - 3000K/CRI 90 / 19,5W - 2150 lm - 4000K/CRI 90








Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.

3000K - CRI 80
On board dimmer
09.4440.30A
09.4440.14A
Non Dimmable
09.4480.30A
09.4480.14A
Dali Version
09.4440.30BDA
09.4440.14BDA

10° SPOT




Luminous flux luminaire
1255 lm

Beam Angle:		10°
h(m)	E(lx)	D(m)
1	14650	0.18
2	3662	0.36
3	1628	0.54
4	916	0.72
5	586	0.90

3000K - CRI 90
On board dimmer
09.4443.30C
09.4443.14C
Non Dimmable
09.4486.30C
09.4486.14C
Dali Version
09.4443.30CDA
09.4443.14CDA

10° SPOT




Luminous flux luminaire
997 lm

Beam Angle:		10°
h(m)	E(lx)	D(m)
1	11643	0.18
2	2911	0.36
3	1294	0.54
4	728	0.72
5	466	0.90

4000K - CRI 90
On board dimmer included
09.4450.30C
09.4450.14C
Non Dimmable
09.4481.30C
09.4481.14C
Dali Version
09.4450.30CDA
09.4450.14CDA

10° SPOT




Luminous flux luminaire
1094 lm

Beam Angle:		10°
h(m)	E(lx)	D(m)
1	12780	0.18
2	3195	0.36
3	1420	0.54
4	799	0.72
5	511	0.90

3000K - CRI 80
On board dimmer
09.4441.30A
09.4441.14A
Non Dimmable
09.4482.30A
09.4482.14A
Dali Version
09.4441.30BDA
09.4441.14BDA

21° MEDIUM




Luminous flux luminaire
1184 lm

Beam Angle:		21°
h(m)	E(lx)	D(m)
1	6515	0.37
2	1629	0.73
3	724	1.10
4	407	1.47
5	261	1.83

3000K - CRI 90
On board dimmer
09.4444.30C
09.4444.14C
Non Dimmable
09.4487.30C
09.4487.14C
Dali Version
09.4444.30CDA
09.4444.14CDA

21° MEDIUM




Luminous flux luminaire
941 lm

Beam Angle:		21°
h(m)	E(lx)	D(m)
1	5178	0.37
2	1294	0.73
3	575	1.10
4	324	1.47
5	207	1.83

4000K - CRI 90
On board dimmer included
09.4451.30C
09.4451.14C
Non Dimmable
09.4483.30C
09.4483.14C
Dali Version
09.4451.30CDA
09.4451.14CDA

21° MEDIUM




Luminous flux luminaire
1033 lm

Beam Angle:		21°
h(m)	E(lx)	D(m)
1	5683	0.37
2	1421	0.73
3	631	1.10
4	355	1.47
5	227	1.83

3000K - CRI 80
On board dimmer
09.4442.30A
09.4442.14A
Non Dimmable
09.4484.30A
09.4484.14A
Dali Version
09.4442.30BDA
09.4442.14BDA

42° FLOOD




Luminous flux luminaire
1394 lm

Beam Angle:		42°
h(m)	E(lx)	D(m)
1	3301	0.76
2	825	1.52
3	367	2.28
4	206	3.05
5	132	3.81

3000K - CRI 90
On board dimmer
09.4445.30C
09.4445.14C
Non Dimmable
09.4488.30C
09.4488.14C
Dali Version
09.4445.30CDA
09.4445.14CDA

42° FLOOD




Luminous flux luminaire
1108 lm

Beam Angle:		42°
h(m)	E(lx)	D(m)
1	2623	0.76
2	656	1.52
3	291	2.28
4	164	3.05
5	105	3.81

4000K - CRI 90
On board dimmer included
09.4452.30C
09.4452.14C
Non Dimmable
09.4485.30C
09.4485.14C
Dali Version
09.4452.30CDA
09.4452.14CDA

42° FLOOD




Luminous flux luminaire
1216 lm


Beam Angle:		42°
h(m)	E(lx)	D(m)
1	2879	0.76
2	720	1.52
3	320	2.28
4	180	3.05
5	115	3.81

Ut Spot Track Ø86

LED Array High Performances
Non Dimming: 33W - 3770 lm - 3000K/CRI 80 / 31,8W - 3116 lm - 3000K/CRI 90 / 31,8W - 3246 lm - 4000K/CRI 90
Dali: 33W - 3770 lm - 3000K/CRI 80 / 32,1W - 3116 lm - 3000K/CRI 90 / 32,1W - 3246 lm - 4000K/CRI 90
Dim on board: 33W - 3770 lm - 3000K/CRI 80 / 33,8W - 3116 lm - 3000K/CRI 90 / 33,8W - 3246 lm - 4000K/CRI 90








Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.

3000K - CRI 80
On board dimmer
09.4840.30A
09.4840.14A
Non Dimmable
09.4880.30A
09.4880.14A
Dali Version
09.4840.30BDA
09.4840.14BDA

3000K - CRI 90
On board dimmer
09.4843.30C
09.4843.14C
Non Dimmable
09.4886.30C
09.4886.14C
Dali Version
09.4843.30CDA
09.4843.14CDA


12° SPOT



Luminous flux luminaire
2650 lm

Beam Angle:	12°
h(m)	E(lx)	D(m)
1	34142	0.21
2	8535	0.41
3	3794	0.62
4	2134	0.82
5	1366	1.03

12° SPOT




Luminous flux luminaire
2190 lm

Beam Angle:	12°
h(m)	E(lx)	D(m)
1	28219	0.21
2	7055	0.41
3	3135	0.62
4	1764	0.82
5	1129	1.03

4000K - CRI 90
On board dimmer included
09.4850.30C
09.4850.14C
Non Dimmable
09.4881.30C
09.4881.14C
Dali Version
09.4850.30CDA
09.4850.14CDA

12° SPOT




Luminous flux luminaire
2281 lm

Beam Angle:	12°
h(m)	E(lx)	D(m)
1	29396	0.21
2	7349	0.41
3	3266	0.62
4	1837	0.82
5	1176	1.03

3000K - CRI 80
On board dimmer
09.4841.30A
09.4841.14A
Non Dimmable
09.4882.30A
09.4882.14A
Dali Version
09.4841.30BDA
09.4841.14BDA

3000K - CRI 90
On board dimmer
09.4844.30C
09.4844.14C
Non Dimmable
09.4887.30C
09.4887.14C
Dali Version
09.4844.30CDA
09.4844.14CDA


24° MEDIUM



Luminous flux luminaire
2528 lm

Beam Angle:	24°
h(m)	E(lx)	D(m)
1	11472	0.43
2	2868	0.86
3	1275	1.28
4	717	1.71
5	459	2.14

24° MEDIUM




Luminous flux luminaire
2089 lm

Beam Angle:	24°
h(m)	E(lx)	D(m)
1	9482	0.43
2	2370	0.86
3	1054	1.28
4	593	1.71
5	379	2.14

4000K - CRI 90
On board dimmer included
09.4851.30C
09.4851.14C
Non Dimmable
09.4883.30C
09.4883.14C
Dali Version
09.4851.30CDA
09.4851.14CDA

24° MEDIUM




Luminous flux luminaire
2176 lm

Beam Angle:	24°
h(m)	E(lx)	D(m)
1	9877	0.43
2	2469	0.86
3	1097	1.28
4	617	1.71
5	395	2.14

3000K - CRI 80
On board dimmer
09.4842.30A
09.4842.14A
Non Dimmable
09.4884.30A
09.4884.14A
Dali Version
09.4842.30BDA
09.4842.14BDA

3000K - CRI 90
On board dimmer
09.4845.30C
09.4845.14C
Non Dimmable
09.4888.30C
09.4888.14C
Dali Version
09.4845.30CDA
09.4845.14CDA


37° FLOOD



Luminous flux luminaire
2408 lm

Beam Angle:	37°
h(m)	E(lx)	D(m)
1	6735	0.67
2	1684	1.34
3	748	2.01
4	421	2.69
5	269	3.36

37° FLOOD




Luminous flux luminaire
1991 lm

Beam Angle:	37°
h(m)	E(lx)	D(m)
1	5566	0.67
2	1392	1.34
3	618	2.01
4	348	2.69
5	223	3.36

4000K - CRI 90
On board dimmer included
09.4852.30C
09.4852.14C
Non Dimmable
09.4885.30C
09.4885.14C
Dali Version
09.4852.30CDA
09.4852.14CDA

37° FLOOD




Luminous flux luminaire
2074 lm

Beam Angle:	37°
h(m)	E(lx)	D(m)
1	5799	0.67
2	1450	1.34
3	644	2.01
4	362	2.69
5	232	3.36


Ut Spot Track Multichip Ø86

Top LED 11,5W - 850 lm - 3000K/CRI 90 / 11,5W - 950 lm - 3000K/CRI 80 / 11,5W - 1000 lm - 4000K/CRI 80





* On board dimmer/Non Dimmable
** Dali Version



Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

The accessories are not compatible with this version.

Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.


Los accesorios no son compatibles con esta versión.

3000K - CRI 80

On board dimmer
- 09.4980.30
- 09.4980.14

Non Dimmable
- 09.4983.30
- 09.4983.14

Dali Version
- 09.4980.30ADA
- 09.4980.14ADA



Luminous flux luminaire
776 lm


Beam Angle:		8°
h(m)	E(lx)	D(m)
1	20322	0.14
2	5081	0.27
3	2258	0.41
4	1270	0.54
5	813	0.68

4000K - CRI 80

On board dimmer
- 09.4982.30
- 09.4982.14

Non Dimmable
- 09.4985.30
- 09.4985.14

Dali Version
- 09.4982.30ADA
- 09.4982.14ADA



Luminous flux luminaire
807 lm


Beam Angle:		8°
h(m)	E(lx)	D(m)
1	21128	0.14
2	5282	0.27
3	2348	0.41
4	1321	0.54
5	845	0.68

3000K - CRI 90

On board dimmer
- 09.4981.30
- 09.4981.14

Non Dimmable
- 09.4984.30
- 09.4984.14

Dali Version
- 09.4981.30ADA
- 09.4981.14ADA




Luminous flux luminaire
687 lm

Beam Angle:		8°
h(m)	E(lx)	D(m)
1	17976	0.14
2	4494	0.27
3	1997	0.41
4	1124	0.54
5	719	0.68


Ut Spot Track Wall-Washer Ø86

LED Array High Performances
Non Dimming / Dim on board: 33W - 3960 lm - 3000K/CRI 80 / 31,8W - 3250 lm - 3000K/CRI 90 / 31,8W - 3500 lm - 4000K/CRI 90
Dali: 33W - 3960 lm - 3000K/CRI 80 / 32,1W - 3250 lm - 3000K/CRI 90 / 32,1W - 3500 lm - 4000K/CRI 90





* On board dimmer/Non Dimmable
** Dali Version



Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.


Proyector para ser instalado a carril trifásico con fuente de luz LED. Fuente de alimentación 220-240V, 50-60Hz integrada.

3000K - CRI 80

On board dimmer
- 09.4950.30A
- 09.4950.14A

Non Dimmable
- 09.4951.30A
- 09.4951.14A

Dali Version
- 09.4950.30BDA
- 09.4950.14BDA



Luminous flux luminaire
2560 lm


Beam Angle:		50°
h(m)	E(lx)	D(m)
1	2596	0.98
2	649	1.97
3	288	2.95
4	162	3.94
5	104	4.92

4000K - CRI 90

On board dimmer
- 09.4956.30C
- 09.4956.14C

Non Dimmable
- 09.4957.30C
- 09.4957.14C

Dali Version
- 09.4956.30CDA
- 09.4956.14CDA



Luminous flux luminaire
2204 lm


Beam Angle:		50°
h(m)	E(lx)	D(m)
1	2236	0.98
2	559	1.97
3	248	2.95
4	140	3.94
5	89	4.92

3000K - CRI 90

On board dimmer
- 09.4953.30C
- 09.4953.14C

Non Dimmable
- 09.4954.30C
- 09.4954.14C

Dali Version
- 09.4953.30CDA
- 09.4953.14CDA




Luminous flux luminaire
2116 lm


Beam Angle:		50°
h(m)	E(lx)	D(m)
1	2146	0.98
2	537	1.97
3	238	2.95
4	134	3.94
5	86	4.92

UT Pro 150 GA-69

LED Array 20W - 2294 lm - 3000K/CRI 80 / 20W - 1984 lm - 3000K/CRI 90 / 20W - 2145 lm - 4000K/CRI 90







Finishes Available



Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. It includes high performance reflector.


.40 versions come with the track adapter, the arm and the rear of the head in black. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Proyector para ser instalado en perfil trifásico estándar con fuente de luz LED. Fuente de alimentación 120-270V integrada. Incluye reflector de alto rendimiento.

Las versiones .40 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas, solo el anillo anti-deslumbramiento permanece en color negro.

3000K - CRI 80
On board dimmer
☐ 09.7270.40D
☐ 09.7270.14D
All White
☐ 09.7270.40D78

21° SPOT




Luminous flux luminaire
2266 lm

Beam Angle:	21°
h(m)	E(lx) D(m)
1	14010 0.37
2	3503 0.74
3	1557 1.11
4	876 1.48
5	560 1.85

3000K - CRI 90
On board dimmer
☐ 09.7276.40D
☐ 09.7276.14D
All White
☐ 09.7276.40D78

21° SPOT




Luminous flux luminaire
1931 lm

Beam Angle:	21°
h(m)	E(lx) D(m)
1	11938 0.37
2	2984 0.74
3	1326 1.11
4	746 1.48
5	478 1.85

4000K - CRI 90
On board dimmer
☐ 09.7271.40D
☐ 09.7271.14D
All White
☐ 09.7271.40D78

21° SPOT




Luminous flux luminaire
1779 lm

Beam Angle:	21°
h(m)	E(lx) D(m)
1	10998 0.37
2	2750 0.74
3	1222 1.11
4	687 1.48
5	440 1.85

3000K - CRI 80
On board dimmer
☐ 09.7272.40D
☐ 09.7272.14D
All White
☐ 09.7272.40D78

27° MEDIUM




Luminous flux luminaire
1902 lm

Beam Angle:	27°
h(m)	E(lx) D(m)
1	8715 0.49
2	2179 0.98
3	968 1.47
4	545 1.96
5	349 2.44

3000K - CRI 90
On board dimmer
☐ 09.7277.40D
☐ 09.7277.14D
All White
☐ 09.7277.40D78

27° MEDIUM




Luminous flux luminaire
1465 lm

Beam Angle:	27°
h(m)	E(lx) D(m)
1	6713 0.49
2	1678 0.98
3	746 1.47
4	420 1.96
5	269 2.44

4000K - CRI 90
On board dimmer
☐ 09.7273.40D
☐ 09.7273.14D
All White
☐ 09.7273.40D78

27° MEDIUM




Luminous flux luminaire
1779 lm

Beam Angle:	27°
h(m)	E(lx) D(m)
1	8152 0.49
2	2038 0.98
3	906 1.47
4	509 1.96
5	326 2.44

3000K - CRI 80
On board dimmer
☐ 09.7274.40D
☐ 09.7274.14D
All White
☐ 09.7274.40D78

35° FLOOD




Luminous flux luminaire
1898 lm

Beam Angle:	35°
h(m)	E(lx) D(m)
1	5618 0.64
2	1404 1.27
3	624 1.91
4	351 2.54
5	225 3.18

3000K - CRI 90
On board dimmer
☐ 09.7278.40D
☐ 09.7278.14D
All White
☐ 09.7278.40D78

36° FLOOD




Luminous flux luminaire
1666 lm

Beam Angle:	36°
h(m)	E(lx) D(m)
1	4869 0.64
2	1217 1.28
3	541 1.92
4	304 2.56
5	195 3.20

4000K - CRI 90
On board dimmer
☐ 09.7275.40D
☐ 09.7275.14D
All White
☐ 09.7275.40D78

36° FLOOD




Luminous flux luminaire
1536 lm


Beam Angle:	36°
h(m)	E(lx) D(m)
1	4489 0.64
2	1122 1.28
3	499 1.92
4	281 2.56
5	180 3.20

UT Pro 175 GA-69

LED Array 46,5W - 4740 lm - 3000K/CRI 80 / 3960 lm - 3000K/CRI 90 / 4278 lm - 4000K/CRI 90







Finishes Available



Spotlight to be installed in standard 3-phase track with LED light source. 120-270V power supply integrated. It includes high performance reflector.


.40 versions come with the track adapter, the arm and the rear of the head in black. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Proyector para ser instalado en perfil trifásico estándar con fuente de luz LED. Fuente de alimentación 120-270V integrada. Incluye reflector de alto rendimiento.

Las versiones .40 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas, solo el anillo anti-deslumbramiento permanece en color negro.

3000K - CRI 80
On board dimmer
☐ 09.7310.40A
☐ 09.7310.14A
All White
☐ 09.7310.40A78

20° SPOT




Luminous flux luminaire 3638 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	21906	0.35
2	5477	0.70
3	2434	1.04
4	1369	1.39
5	876	1.74

3000K - CRI 90
On board dimmer
☐ 09.7311.40A
☐ 09.7311.14A
All White
☐ 09.7311.40A78

20° SPOT




Luminous flux luminaire 3037 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	18287	0.35
2	4572	0.70
3	2032	1.04
4	1143	1.39
5	731	1.74

4000K - CRI 90
On board dimmer
☐ 09.7312.40A
☐ 09.7312.14A
All White
☐ 09.7312.40A78

20° SPOT




Luminous flux luminaire 3283 lm

Beam Angle: 20°

h(m)	E(lx)	D(m)
1	19769	0.35
2	4942	0.70
3	2197	1.04
4	1236	1.39
5	791	1.74

3000K - CRI 80
On board dimmer
☐ 09.7313.40A
☐ 09.7313.14A
All White
☐ 09.7313.40A78

27° MEDIUM




Luminous flux luminaire 3531 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	13450	0.48
2	3362	0.96
3	1494	1.44
4	841	1.93
5	538	2.41

3000K - CRI 90
On board dimmer
☐ 09.7314.40A
☐ 09.7314.14A
All White
☐ 09.7314.40A78

27° MEDIUM




Luminous flux luminaire 2947 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	11225	0.48
2	2806	0.96
3	1247	1.44
4	702	1.93
5	449	2.41

4000K - CRI 90
On board dimmer
☐ 09.7315.40A
☐ 09.7315.14A
All White
☐ 09.7315.40A78

27° MEDIUM




Luminous flux luminaire 3187 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	12140	0.48
2	3035	0.96
3	1349	1.44
4	759	1.93
5	486	2.41

3000K - CRI 80
On board dimmer
☐ 09.7316.40A
☐ 09.7316.14A
All White
☐ 09.7316.40A78

34° FLOOD




Luminous flux luminaire 3476 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	8672	0.61
2	2168	1.22
3	964	1.83
4	542	2.44
5	347	3.04

3000K - CRI 90
On board dimmer
☐ 09.7317.40A
☐ 09.7317.14A
All White
☐ 09.7317.40A78

34° FLOOD




Luminous flux luminaire 2901 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	7237	0.61
2	1809	1.22
3	804	1.83
4	452	2.44
5	289	3.04

4000K - CRI 90
On board dimmer
☐ 09.7318.40A
☐ 09.7318.14A
All White
☐ 09.7318.40A78

34° FLOOD



Luminous flux luminaire 3137 lm


Beam Angle: 34°


h(m)	E(lx)	D(m)
1	7826	0.61
2	1957	1.22
3	870	1.83
4	489	2.44
5	313	3.04

UT Pro 175 Lens GA-69

LED Array 35,3W - 3950 lm - 3000K/CRI 80 / 35,3W - 3250 lm - 3000K/CRI 90 / 35,3W - 3400 lm - 4000K/CRI 90







Finishes Available

Spotlight to be installed in standard 3-phase track with LED light source. Includes adjustable lens allowing opening angle calibration from 13º to 56º. 120-270V power supply integrated.


.40 versions come with the track adapter, the arm and the rear of the head in black. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Proyector para ser instalado en perfil trifásico estándar con fuente de luz LED. Incorpora lente ajustable que permite la calibración del ángulo de apertura de 13º a 56º.
Fuente de alimentación 120-270V integrada.

Las versiones .40 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas, solo el anillo anti-deslumbramiento permanece en color negro.

3000K - CRI 80
On board dimmer
- 09.7373.40
- 09.7373.14
  All White
- 09.7373.40.78


13° LENS OUT



Luminous flux luminaire 2314 lm

Beam Angle: 13°		
h(m)	E(lx)	D(m)
1	28212	0.23
2	7053	0.46
3	3135	0.70
4	1763	0.93
5	1128	1.16

56° LENS IN




Luminous flux luminaire 3468 lm

Beam Angle: 56°		
h(m)	E(lx)	D(m)
1	4649	1.07
2	1162	2.14
3	517	3.21
4	291	4.29
5	186	5.36

3000K - CRI 90
On board dimmer
- 09.7374.40
- 09.7374.14
  All White
- 09.7374.40.78


13° LENS OUT



Luminous flux luminaire 1912 lm

Beam Angle: 13°		
h(m)	E(lx)	D(m)
1	23312	0.23
2	5828	0.46
3	2590	0.70
4	1457	0.93
5	932	1.16

56° LENS IN




Luminous flux luminaire 2866 lm

Beam Angle: 56°		
h(m)	E(lx)	D(m)
1	3841	1.07
2	960	2.14
3	427	3.21
4	240	4.29
5	154	5.36

4000K - CRI 90
On board dimmer
- 09.7375.40
- 09.7375.14
  All White
- 09.7375.40.78


13° LENS OUT



Luminous flux luminaire 1992 lm

Beam Angle: 13°		
h(m)	E(lx)	D(m)
1	24291	0.23
2	6073	0.46
3	2699	0.70
4	1518	0.93
5	972	1.16

56° LENS IN




Luminous flux luminaire 2986 lm


Beam Angle: 56°		
h(m)	E(lx)	D(m)
1	4003	1.07
2	1001	2.14
3	445	3.21
4	250	4.29
5	160	5.36

UT Pro Wall-Washer GA-69 (Dali GA-600)

Top LED 25,5W - 2700 lm - 3000K/CRI 90 / 25,5W - 2900 lm - 4000K/CRI 90







Finishes Available

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. DALI version requires dimmable tracks (please refer to the “Tracks” chapter).

.40 versions come with the track adapter, the arm and the rear of the head in black. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white.


Módulo de iluminación Wall-Washer para ser instalado en perfil trifásico estándar con fuente de luz LED. Fuente de alimentación 220-240V integrada. Para la versión DALI necesita carriles dimmables (ver capítulo "Tracks").

Las versiones .40 tienen el adaptador a carril, el brazo y la trasera de la cabeza en negro. En las versiones “all white” el adaptador a carril, el brazo, la trasera de la cabeza y la cabeza son blancas.

3000K - CRI 90
Non Dimmable
- 09.7504.40
- 09.7504.14
  All White
- 09.7504.40.78

Dali Version
- 09.7504.40.DA
- 09.7504.14.DA
  All White
- 09.7504.40.YU

36°




Luminous flux luminaire 1706 lm

Beam Angle: 36°		
h(m)	E(lx)	D(m)
1	1199	0.78
2	300	1.56
3	133	2.34
4	75	3.12
5	48	3.90

4000K - CRI 90
Non Dimmable
- 09.7505.40
- 09.7505.14
  All White
- 09.7505.40.78

Dali Version
- 09.7505.40.DA
- 09.7505.14.DA
  All White
- 09.7505.40.YU

36°



Luminous flux luminaire 1700 lm

Beam Angle: 36°		
h(m)	E(lx)	D(m)
1	1184	0.76
2	296	1.52
3	132	2.28
4	74	3.04
5	47	3.80

Accessories / Accesorios

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

Cruceta de apantallamiento, lentes y honeycomb directamente instalables en la cabeza de la luminaria sin necesidad de accesorio de sujeción.

UT Spot Ø57 / UT Pro 150

Screening crosspiece.
Cruceta de apantallamiento.

08.8429.00

Elliptical lens
Lente elíptica

08.8431.00

Flood lens
Lente flood

08.8432.00

For Spot & Medium optics

Honeycomb
Honeycomb

08.8428.00

Snoot shielding cone
Cono apantallador

29
08.0526.00
08.0526.40
08.0526.BW

UT Pro 175

Screening crosspiece.
Cruceta de apantallamiento.

08.9108.00

Elliptical lens
Lente elíptica

08.9109.00

Flood lens
Lente flood

08.9110.00

Honeycomb
Honeycomb

08.9107.00


Snoot shielding cone
Cono apantallador

35
08.9111.00
08.9111.40
08.9111.BW

Accessories / Accesorios

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire.
UT Spot Ø86: Installation compatible with honeycomb + lense at the same time.
UT Spot Ø86 Multichip: The accessories are not compatible with this version.

Cruceta de apantallamiento, lentes y honeycomb directamente instalables en la cabeza de la luminaria.
UT Spot Ø86: Compatibilidad de instalación de honeycomb + lente al mismo tiempo.
UT Spot Ø86 Multichip: Los accesorios no son compatibles con esta versión.



UT Spot Ø86

Holding ring
Aro soporte

08.8410.00

UT Spot Ø86 LED Array

Screening crosspiece.
Cruceta de apantallamiento.

08.8411.00

UT Spot Ø86 LED Array
Mandatory holding ring or screening crosspiece.
Obligatorio aro soporte o cruceta de apantallamiento.

Elliptical lens
Lente elíptica

08.8163.68

Flood lens
Lente flood

08.8175.68

For Spot & Medium optics

Honeycomb
Honeycomb

08.8495.14

WAN SPOT

DESIGNED BY JOHANNA GRAWUNDER



LIGHT SOURCE
LED ARRAY
9,2W
945 lm
3000K/CRI 80



LIGHT SOURCE
LED
QT-14
G9

30 White
30 Blanco

05 Polished Silver
05 Plata Pulida

14 Black
14 Negro

GN Green
GN Verde










Can be rotated 360° and swivelled 60°.
Puede ser rotado 360° y orientado 60°.



Description
Wall or ceiling lamp providing direct light. Aluminum body, available in chrome, shiny white, enameled green, and shiny black finishes. Low glare shield.
Provided by two different ring due to fix the safety tempered glass, in shiny black and enameled green.

Reflectors
Sanded and chemically bleached aluminum reflector.

Power Supply
Pre-wiring included; ready for remote power supply.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Additional Information
0° - 360° vertical rotation and 0° - 60° adjustment.
IP20 protection grade.
Insulation class II, III depending on the versions.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria de luz directa para ser instalada a techo o pared. Cuerpo de aluminio disponible en acabado pulido, blanco brillante, verde esmaltado y negro brillante. Incorpora cono antideslumbramiento.
El producto lleva incorporados dos aros interiores intercambiables, que sujetan el cristal templado y el reflector, en negro brillante o verde esmaltado.

Reflectores
Reflector de aluminio tratado con chorro de arena y blanqueado químicamente.

Unidades de Alimentación
Luminaria precableada para ser alimentada mediante equipo remoto.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).

Información Adicional
Rotación en el eje vertical de hasta 360° y orientación hasta 60°.
Índice de protección IP20.
Clase de aislamiento II, III, según las versiones.
Instalable sobre superficies normalmente inflamables.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Equipo conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Wan Spot

LED Array DC 500 mA - 9,2W - 945 lm - 3000K/CRI 80







Spotlight to be installed recessed on ceiling/wall. Power supply not included.

Proyector para ser instalado empotrado en pared o techo. Fuente de alimentación no incluida.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9768
Dimmable 0/1-10V	60.9188
Dimmable Dali 2	60.9826
Mains Dimming	60.9467
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

- 03.6174.30B
- 03.6174.05A
- 03.6174.14B
- 03.6174.GNA





Luminous flux luminaire
505 lm


Beam Angle: 82°


h(m)	E(lx)	D(m)
1	362	1.75
2	91	3.50
3	40	5.25
4	23	7.00
5	14	8.75

Wan Spot

QT-14 G9 max 40W








Spotlight to be installed recessed on ceiling/wall with main voltage source.

Proyector para ser instalado empotrado en pared o techo, con alimentación directa a red.

- 03.6170.30B
- 03.6170.05
- 03.6170.14B
- 03.6170.GN






Luminous flux luminaire
460 lm

@Black Ring

Beam Angle: 68°

h(m)	E(lx)	D(m)
1	147	1.35
2	37	2.70
3	16	4.05
4	9	5.40
5	6	6.75





Luminous flux luminaire
460 lm

@Green Ring

Beam Angle: 69°

h(m)	E(lx)	D(m)
1	149	1.38
2	37	2.75
3	17	4.13
4	9	5.50
5	6	6.88

CEILING / WALL

C1, UT Pro Surface, Kap Surface&
Suspension, Super Line&Pro, Light Bell,
Fort Knox Wall&Mini, Thin LED,
G-O, TheBlockofLight.

NEW

C 1

DESIGNED BY VINCENT VAN DUYSEN

MONO SPOT CEILING SMALL



LIGHT SOURCE
POWER LED
6W
510 lm
2700K/CRI 90
560 lm
3000K/CRI 90

MONO SPOT WALL SMALL



LIGHT SOURCE
POWER LED
6W
510 lm
2700K/CRI 90
560 lm
3000K/CRI 90

DOUBLE SPOT WALL SMALL



LIGHT SOURCE
POWER LED
12W
1020 lm
2700K/CRI 90
1120 lm
3000K/CRI 90

DOUBLE SPOT SURFACE SMALL



LIGHT SOURCE
POWER LED
14,5W
1020 lm
2700K/CRI 90
1120 lm
3000K/CRI 90

MONO SPOT CEILING LARGE



LIGHT SOURCE
POWER LED
Up to 14W
1225 lm
2700K/CRI 90
1300 lm
3000K/CRI 90

MONO SPOT WALL LARGE



LIGHT SOURCE
POWER LED
Up to 14W
1225 lm
2700K/CRI 90
1300 lm
3000K/CRI 90

DOUBLE SPOT WALL LARGE



LIGHT SOURCE
POWER LED
Up to 28W
2450 lm
2700K/CRI 90
2600 lm
3000K/CRI 90

DY White
DY Blanco



DR Anthracite
DR Antracita




ER Brushed Steel
ER Acero Cepillado



ES Brushed Bronze
ES Bronce Cepillado




Can be rotated 180° and swivelled 60°.
Puede ser rotado 180° y orientado 60°.



Wall

Can be rotated 355° and swivelled 60°.
Puede ser rotado 355° y orientado 60°.



Ceiling & Surface

NEW

Description
New program of wall and ceiling-mounted luminaires developed for residential and hospitality use.
The extremely minimalist design of the product hides a special, integrated mechanical connection that allows the luminaire body to be extracted and oriented up to 60° on the vertical axis and on the horizontal axis (355° in the ceiling version and 140° in the wall version), ensuring an impressive versatility, ideal to meet the needs of any project.
Versions developed for wall mounting are available with single or dual emission.

Optical Group
Optical group with high visual comfort in the body of the product, available with differentiated beamwidths.
This luminaire is designed to provide diffuse light emission or a more concentrated light distribution, ideal when accent or spot lighting is needed for reading in bed headboard applications.
Dual-emission models include a diffusing screen as accessory that can be integrated into the optical unit, producing a soft light effect.

Power Supply
All devices must be powered by a remote controller (not included) available with various control options.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Control System
Units can be controlled by 0/1-10V, DALI, Push Dimming and Casambi. Broadcast control system. In devices with dual emission, direct and indirect emissions can be controlled independently.
C1 Double Surface includes the driver and supports ON/OFF, mains dimming, and DALI control.

Installation
The product is ready to be installed on different surface types.
All products are completed with a dedicated No Trim or plate installation mounting kit. The No Trim installation is only compatible with plasterboard surfaces with a minimum thickness of 9mm and a maximum of 25mm. Plate installation allows the electrical connection to be made inside the surface mount.

Additional Information
Constant voltage controlled electrical system.
IP20 Protection Index.
Suitable for installation on normally flammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598N/D European Technical Standards and any subsequent additions.

Descripción
Nuevo programa de luminarias para instalación en pared y techo desarrollado a medida para aplicaciones residenciales o de hostelería.
El diseño extremadamente minimalista del producto esconde una conexión mecánica especial integrada que permite extraer y orientar el cuerpo de la luminaria hasta 60° en el eje vertical y en el eje horizontal (355° para la versión de techo y 140° para la versión de pared), garantizando una impresionante versatilidad, perfecta para satisfacer las necesidades de cualquier proyecto.
Las versiones desarrolladas para instalación en pared están disponibles con emisión simple o doble.

Grupo Óptico
Grupo óptico con un elevado confort visual en el cuerpo del producto, disponible con aperturas de haz diferenciadas.
La luminaria está preparada para proporcionar una emisión de luz difusa o una distribución más concentrada, perfecta para iluminación de acento o puntual para la lectura en aplicaciones para cabecero de cama.
Los modelos de doble emisión incluyen una pantalla difusora como accesorio que se puede integrar en el grupo óptico dando como resultado un efecto de luz suave.

Unidades de Alimentación
Todos los aparatos deben ser alimentados mediante un controlador remoto no incluido, disponible con varias alternativas de control.

Sistema de Regulación
Los aparatos pueden ser controlados mediante 0/1-10V, DALI, Push Dimming y Casambi. Sistema de control broadcast. En los aparatos con doble emisión se pueden controlar las emisiones directa e indirecta de manera independiente.
C1 Double Surface incluye el driver y admite control ON/OFF, mains dimming y control DALI.

Instalación
El producto está preparado para ser instalado sobre diferentes tipos de superficies.
Todos los productos se completan con un kit de montaje específico para la instalación No Trim o con placa.
La instalación No Trim sólo es compatible con superficies en pladur con un grosor mínimo de 9 mm y máximo de 25 mm.
La instalación con placa permite realizar la conexión eléctrica en el interior del soporte en superficie.

Información Adicional
Sistema eléctrico controlado en tensión constante.
Índice de protección IP20.
Apto para instalación en superficies normalmente inflamables.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598N/D y partes segundas.

Mono Spot Ceiling Small Ø35

Power LED DC 500 mA - 6W - 510 lm - 2700K/CRI 90 / 6W - 560 lm - 3000K/CRI 90







Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis.
Integrated Full cut-off optical group.
The remote power supply (not included) must be placed in an accessible location.
The installation frame must be ordered separately.

Luminaria orientable con LED para uso en interiores, apta para instalación en techo. Es posible extraer el cuerpo del producto de la superficie de instalación para orientarlo 60° en eje vertical y 355° en eje horizontal.
Grupo óptico Full cut-off integrado.
La alimentación remota (no incluida) debe colocarse en un lugar accesible.
El marco de instalación ha de pedirse por separado.


Recommended power supply / Equipos recomendados*:

Non Dimmable	60.9592
Dimmable 1-10V	60.9208
Dimmable Dali 2 / Push	60.7678
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
- 03.1220.DY
- 03.1220.DR
- 03.1220.ER
- 03.1220.ES






Luminous flux luminaire
376 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	4139	0.26
2	1035	0.51
3	460	0.77
4	259	1.03
5	166	1.28

3000K
- 03.1225.DY
- 03.1225.DR
- 03.1225.ER
- 03.1225.ES






Luminous flux luminaire
382 lm

Beam Angle: 15°

h(m)	E(lx)	D(m)
1	4198	0.26
2	1050	0.51
3	466	0.77
4	262	1.03
5	168	1.28

2700K
- 03.1221.DY
- 03.1221.DR
- 03.1221.ER
- 03.1221.ES






Luminous flux luminaire
368 lm

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2640	0.32
2	660	0.65
3	293	0.97
4	165	1.30
5	106	1.62

3000K
- 03.1226.DY
- 03.1226.DR
- 03.1226.ER
- 03.1226.ES





Luminous flux luminaire
374 lm


Beam Angle: 18°


h(m)	E(lx)	D(m)
1	2678	0.32
2	669	0.65
3	298	0.97
4	167	1.30
5	107	1.62

Mono Spot Wall Small Ø35

Power LED DC 500 mA - 6W - 510 lm - 2700K/CRI 90 / 6W - 560 lm - 3000K/CRI 90







Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis.
Integrated Full cut-off optical group.
The remote power supply (not included) must be placed in an accessible location.
The installation frame must be ordered separately.

Luminaria orientable con LED para uso en interiores, apta para instalación en pared. Es posible extraer el cuerpo del producto de la superficie de instalación para orientarlo 60° en eje vertical y 180° en eje horizontal.
Grupo óptico Full cut-off integrado.
La alimentación remota (no incluida) debe colocarse en un lugar accesible.
El marco de instalación ha de pedirse por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 1-10V	60.9208
Dimmable Dali 2 / Push	60.7678
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 03.1200.DY
- 03.1200.DR
- 03.1200.ER
- 03.1200.ES

15° SPOT



Luminous flux luminaire
376 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	4139	0.26
2	1035	0.51
3	460	0.77
4	259	1.03
5	166	1.28

3000K

- 03.1205.DY
- 03.1205.DR
- 03.1205.ER
- 03.1205.ES

15° SPOT



Luminous flux luminaire
382 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	4198	0.26
2	1050	0.51
3	466	0.77
4	262	1.03
5	168	1.28

2700K

- 03.1201.DY
- 03.1201.DR
- 03.1201.ER
- 03.1201.ES

18° MEDIUM



Luminous flux luminaire
368 lm


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2640	0.32
2	660	0.65
3	293	0.97
4	165	1.30
5	106	1.62

3000K

- 03.1206.DY
- 03.1206.DR
- 03.1206.ER
- 03.1206.ES

18° MEDIUM



Luminous flux luminaire
374 lm


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2678	0.32
2	669	0.65
3	298	0.97
4	167	1.30
5	107	1.62

Double Spot Wall Small Ø35

Power LED DC 500 mA - 12W - 1020 lm - 2700K/CRI 90 / 12W - 1120 lm - 3000K/CRI 90





GWT 850°

LED INCL.

60°

III

180°

IP 20

Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60º orientation on the vertical axis and 180º on the horizontal axis. Integrated Full cut-off optical group. Accessories integrated (up diffuser). The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately

Luminaria orientable con LED para uso en interiores, apta para instalación en pared. Es posible extraer el cuerpo inferior del producto de la superficie de instalación para orientarlo 60º en eje vertical y 180º en eje horizontal. Grupo óptico Full cut-off integrado. Accesorios integrados (difusor up). La alimentación remota (no incluida) debe colocarse en un lugar accesible.
El marco de instalación ha de pedirse por separado.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9592
Dimmable 1-10V	60.9208
Dimmable Dali 2 / Push	60.7678
Casambi	60.9207

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K

- 03.1210.DY
- 03.1210.DR
- 03.1210.ER
- 03.1210.ES

15° SPOT



** Luminous flux luminaire 753 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	4140	0.26
2	1035	0.51
3	460	0.77
4	259	1.03
5	166	1.28

3000K

- 03.1215.DY
- 03.1215.DR
- 03.1215.ER
- 03.1215.ES

15° SPOT



** Luminous flux luminaire 763 lm


Beam Angle: 15°

h(m)	E(lx)	D(m)
1	4198	0.26
2	1049	0.51
3	466	0.77
4	263	1.03
5	168	1.28

2700K

- 03.1211.DY
- 03.1211.DR
- 03.1211.ER
- 03.1211.ES

18° MEDIUM



** Luminous flux luminaire 745 lm


Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2640	0.32
2	660	0.65
3	293	0.97
4	165	1.30
5	106	1.62

3000K

- 03.1216.DY
- 03.1216.DR
- 03.1216.ER
- 03.1216.ES

18° MEDIUM



** Luminous flux luminaire 755 lm

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2678	0.32
2	669	0.65
3	298	0.97
4	168	1.30
5	107	1.62


** Photometric data without up diffuser / Datos fotométricos sin difusor up.


NEW

Double Spot Surface Small Ø35

Power LED – 14,5W - 1020 lm - 2700K/CRI 90 / 14,5W - 1120 lm - 3000K/CRI 90







Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group and the power supply is included.


Luminaria orientable con LED para uso en interiores, apta para instalación en techo. Es posible extraer el cuerpo del producto de la superficie de instalación para orientarlo 60° en eje vertical y 180° en eje horizontal. Grupo óptico Full cut-off integrado y fuente de alimentación incluida.

Optic Spot - 2700K

Non Dimming
- 05.3500.DY
- 05.3500.DR
- 05.3500.ER
- 05.3500.ES

Mains Dimming
- 05.3500.DY.NI
- 05.3500.DR.NI
- 05.3500.ER.NI
- 05.3500.ES.NI

Dali
- 05.3500.DY.DA
- 05.3500.DR.DA
- 05.3500.ER.DA
- 05.3500.ES.DA



Luminous flux luminaire
752 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	8273	0.26
2	2068	0.51
3	919	0.77
4	517	1.03
5	331	1.28

Optic Spot - 3000K

Non Dimming
- 05.3505.DY
- 05.3505.DR
- 05.3505.ER
- 05.3505.ES

Mains Dimming
- 05.3505.DY.NI
- 05.3505.DR.NI
- 05.3505.ER.NI
- 05.3505.ES.NI

Dali
- 05.3505.DY.DA
- 05.3505.DR.DA
- 05.3505.ER.DA
- 05.3505.ES.DA



Luminous flux luminaire
764 lm

Beam Angle: 15°


h(m)	E(lx)	D(m)
1	8405	0.26
2	2101	0.51
3	934	0.77
4	525	1.03
5	336	1.28

Optic Medium - 2700K

Non Dimming
- 05.3501.DY
- 05.3501.DR
- 05.3501.ER
- 05.3501.ES

Mains Dimming
- 05.3501.DY.NI
- 05.3501.DR.NI
- 05.3501.ER.NI
- 05.3501.ES.NI

Dali
- 05.3501.DY.DA
- 05.3501.DR.DA
- 05.3501.ER.DA
- 05.3501.ES.DA



Luminous flux luminaire
736 lm

Beam Angle: 18°


h(m)	E(lx)	D(m)
1	5276	0.32
2	1319	0.65
3	586	0.97
4	330	1.30
5	211	1.62

Optic Medium - 3000K

Non Dimming
- 05.3506.DY
- 05.3506.DR
- 05.3506.ER
- 05.3506.ES

Mains Dimming
- 05.3506.DY.NI
- 05.3506.DR.NI
- 05.3506.ER.NI
- 05.3506.ES.NI

Dali
- 05.3506.DY.DA
- 05.3506.DR.DA
- 05.3506.ER.DA
- 05.3506.ES.DA



Luminous flux luminaire
748 lm


Beam Angle: 18°


h(m)	E(lx)	D(m)
1	5362	0.32
2	1340	0.65
3	596	0.97
4	335	1.30
5	214	1.62

Mono Spot Ceiling Large Ø56

Power LED DC 950 mA - 11W - 970 lm - 2700K/CRI 90 / 11W - 1050 lm - 3000K/CRI 90
Power LED DC 1200 mA - 14W - 1225 lm - 2700K/CRI 90 / 14W - 1300 lm - 3000K/CRI 90







Adjustable luminaire with LED for indoor use, suitable for ceiling installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 355° on the horizontal axis.
Integrated Full cut-off optical group.
The remote power supply (not included) must be placed in an accessible location.
The installation frame must be ordered separately.

Luminaria orientable con LED para uso en interiores, apta para instalación en techo. Es posible extraer el cuerpo del producto de la superficie de instalación para orientarlo 60° en eje vertical y 355° en eje horizontal.
Grupo óptico Full cut-off integrado.
La alimentación remota (no incluida) debe colocarse en un lugar accesible.
El marco de instalación ha de pedirse por separado.


Recommended power supply / Equipos recomendados*:

	950 mA	1200 mA
Non Dimmable	60.7677	60.9276
Dimmable Dali 2 / Push	60.7678	60.9276
Dimmable 0/1-10V	60.9439	60.9276
Casambi	60.9207	60.9276+60.9392

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
- 03.1250.DYB
- 03.1250.DRB
- 03.1250.ERB
- 03.1250.ESB

14° SPOT




Luminous flux luminaire 1070 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	15302	0.24
2	3825	0.48
3	1700	0.72
4	956	0.96
5	612	1.20

3000K
- 03.1255.DYB
- 03.1255.DRB
- 03.1255.ERB
- 03.1255.ESB

14° SPOT




Luminous flux luminaire 1070 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	15302	0.24
2	3825	0.48
3	1700	0.72
4	956	0.96
5	612	1.20

2700K
- 03.1251.DYB
- 03.1251.DRB
- 03.1251.ERB
- 03.1251.ESB

23° MEDIUM




Luminous flux luminaire 1094 lm

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	7998	0.40
2	1999	0.80
3	889	1.20
4	500	1.60
5	320	2.00

3000K
- 03.1256.DYB
- 03.1256.DRB
- 03.1256.ERB
- 03.1256.ESB

23° MEDIUM




Luminous flux luminaire 1158 lm

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	8468	0.40
2	2117	0.80
3	941	1.20
4	529	1.60
5	339	2.00

2700K
- 03.1252.DYB
- 03.1252.DRB
- 03.1252.ERB
- 03.1252.ESB

34° FLOOD




Luminous flux luminaire 1043 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3557	0.61
2	889	1.22
3	395	1.83
4	222	2.43
5	142	3.04

3000K
- 03.1257.DYB
- 03.1257.DRB
- 03.1257.ERB
- 03.1257.ESB

34° FLOOD




Luminous flux luminaire 1081 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3687	0.61
2	922	1.22
3	410	1.83
4	230	2.43
5	147	3.04

2700K
- 03.1253.DYB
- 03.1253.DRB
- 03.1253.ERB
- 03.1253.ESB

45° WIDE FLOOD




Luminous flux luminaire 1063 lm

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	2185	0.84
2	546	1.68
3	243	2.52
4	137	3.35
5	87	4.19

3000K
- 03.1258.DYB
- 03.1258.DRB
- 03.1258.ERB
- 03.1258.ESB

45° WIDE FLOOD



Luminous flux luminaire 1146 lm


Beam Angle: 45°


h(m)	E(lx)	D(m)
1	2357	0.84
2	589	1.68
3	262	2.52
4	147	3.35
5	94	4.19

Mono Spot Wall Large Ø56

Power LED DC 950 mA - 11W - 970 lm - 2700K/CRI 90 / 11W - 1050 lm - 3000K/CRI 90
Power LED DC 1200 mA - 14W - 1225 lm - 2700K/CRI 90 / 14W - 1300 lm - 3000K/CRI 90







Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis.
Integrated Full cut-off optical group.
The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Luminaria orientable con LED para uso en interiores, apta para instalación en pared. Es posible extraer el cuerpo del producto de la superficie de instalación para orientarlo 60° en eje vertical y 180° en eje horizontal.
Grupo óptico Full cut-off integrado.
La alimentación remota (no incluida) debe colocarse en un lugar accesible.
El marco de instalación ha de pedirse por separado.


Recommended power supply / Equipos recomendados*:

	950 mA	1200 mA
Non Dimmable	60.7677	60.9276
Dimmable Dali 2 / Push	60.7678	60.9276
Dimmable 0/1-10V	60.9439	60.9276
Casambi	60.9207	60.9276+60.9392

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
- 03.1230.DYB
- 03.1230.DRB
- 03.1230.ERB
- 03.1230.ESB






Luminous flux luminaire
1070 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	15302	0.24
2	3825	0.48
3	1700	0.72
4	956	0.96
5	612	1.20

3000K
- 03.1235.DYB
- 03.1235.DRB
- 03.1235.ERB
- 03.1235.ESB






Luminous flux luminaire
1132 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	16195	0.24
2	4049	0.48
3	1799	0.72
4	1012	0.96
5	648	1.20

2700K
- 03.1231.DYB
- 03.1231.DRB
- 03.1231.ERB
- 03.1231.ESB






Luminous flux luminaire
1094 lm

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	7998	0.40
2	1999	0.80
3	889	1.20
4	500	1.60
5	320	2.00

3000K
- 03.1236.DYB
- 03.1236.DRB
- 03.1236.ERB
- 03.1236.ESB






Luminous flux luminaire
1158 lm

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	8468	0.40
2	2117	0.80
3	941	1.20
4	529	1.60
5	339	2.00

2700K
- 03.1232.DYB
- 03.1232.DRB
- 03.1232.ERB
- 03.1232.ESB






Luminous flux luminaire
1043 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3557	0.61
2	889	1.22
3	395	1.83
4	222	2.43
5	142	3.04

3000K
- 03.1237.DYB
- 03.1237.DRB
- 03.1237.ERB
- 03.1237.ESB






Luminous flux luminaire
1081 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3687	0.61
2	922	1.22
3	410	1.83
4	230	2.43
5	147	3.04

2700K
- 03.1233.DYB
- 03.1233.DRB
- 03.1233.ERB
- 03.1233.ESB






Luminous flux luminaire
1063 lm

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	2185	0.84
2	546	1.68
3	243	2.52
4	137	3.35
5	87	4.19

3000K
- 03.1238.DYB
- 03.1238.DRB
- 03.1238.ERB
- 03.1238.ESB





Luminous flux luminaire
1146 lm


Beam Angle: 45°


h(m)	E(lx)	D(m)
1	2357	0.84
2	589	1.68
3	262	2.52
4	147	3.35
5	94	4.19

Double Spot Wall Large Ø56

Power LED DC 950 mA - 22W - 1940 lm - 2700K/CRI 90 / 22W - 2100 lm - 3000K/CRI 90
Power LED DC 1200 mA - 28W - 2450 lm - 2700K/CRI 90 / 28W - 2600 lm - 3000K/CRI 90







Adjustable luminaire with LED for indoor use, suitable for wall installation. The lower part of the body can be extracted from the installation surface for 60º orientation on the vertical axis and 180º on the horizontal axis. Integrated Full cut-off optical group. Accessories integrated (up diffuser). The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Luminaria orientable con LED para uso en interiores, apta para instalación en pared. Es posible extraer el cuerpo inferior del producto de la superficie de instalación para orientarlo 60º en eje vertical y 180º en eje horizontal. Grupo óptico Full cut-off integrado. Accesorios integrados (difusor up). La alimentación remota (no incluida) debe colocarse en un lugar accesible. El marco de instalación ha de pedirse por separado


Recommended power supply / Equipos recomendados*:

	950 mA	1200 mA
Non Dimmable	60.7677	60.9276
Dimmable Dali 2 / Push	60.7678	60.9276
Dimmable 0/1-10V	60.9439	60.9276
Casambi	60.9207	60.9276+60.9392

* Refer to the Drivers chapter / Ver capítulo Drivers

2700K
- 03.1240.DYB
- 03.1240.DRB
- 03.1240.ERB
- 03.1240.ESB

14° SPOT




**Luminous flux luminaire 2139 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	15301	0.24
2	3825	0.48
3	1701	0.72
4	956	0.96
5	612	1.20

3000K
- 03.1245.DYB
- 03.1245.DRB
- 03.1245.ERB
- 03.1245.ESB

14° SPOT




**Luminous flux luminaire 2139 lm

Beam Angle: 14°

h(m)	E(lx)	D(m)
1	15301	0.24
2	3825	0.48
3	1701	0.72
4	956	0.96
5	612	1.20

2700K
- 03.1241.DYB
- 03.1241.DRB
- 03.1241.ERB
- 03.1241.ESB

23° MEDIUM




**Luminous flux luminaire 2163 lm

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	7998	0.40
2	1999	0.80
3	889	1.20
4	500	1.60
5	320	2.00

3000K
- 03.1246.DYB
- 03.1246.DRB
- 03.1246.ERB
- 03.1246.ESB

23° MEDIUM




**Luminous flux luminaire 2228 lm

Beam Angle: 23°

h(m)	E(lx)	D(m)
1	8237	0.40
2	2059	0.80
3	916	1.20
4	515	1.60
5	330	2.00

2700K
- 03.1242.DYB
- 03.1242.DRB
- 03.1242.ERB
- 03.1242.ESB

34° FLOOD




**Luminous flux luminaire 2112 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3557	0.61
2	889	1.22
3	395	1.83
4	222	2.43
5	142	3.04

3000K
- 03.1247.DYB
- 03.1247.DRB
- 03.1247.ERB
- 03.1247.ESB

34° FLOOD




**Luminous flux luminaire 2150 lm

Beam Angle: 34°

h(m)	E(lx)	D(m)
1	3688	0.61
2	922	1.22
3	411	1.83
4	230	2.43
5	148	3.04

2700K
- 03.1243.DYB
- 03.1243.DRB
- 03.1243.ERB
- 03.1243.ESB

45° WIDE FLOOD




**Luminous flux luminaire 2132 lm

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	2186	0.84
2	546	1.68
3	243	2.52
4	136	3.35
5	87	4.19

3000K
- 03.1248.DYB
- 03.1248.DRB
- 03.1248.ERB
- 03.1248.ESB

45° WIDE FLOOD






**Luminous flux luminaire 2216 lm

Beam Angle: 45°






h(m)	E(lx)	D(m)
1	2358	0.84
2	589	1.68
3	261	2.52
4	146	3.35
5	95	4.19

** Photometric data without up diffuser / Datos fotométricos sin difusor up.

HOW TO ORDER C1

	SURFACE					RECESSED			
	SMALL			LARGE		SMALL		LARGE	
	Ceiling	Wall	Wall flush	Ceiling	Wall flush	Ceiling	Wall	Ceiling	Wall
Mono Spot									
Mono Spot									
Double Spot									

Accessories / Accesorios

No Trim installation frame for wall mounting.	Marco de instalación No Trim para instalación en pared.			C1 Wall Small Mono 08.0206.00 C1 Wall Small Double 08.0227.00
No Trim installation frame for wall mounting.	Marco de instalación No Trim para instalación en pared.			C1 Wall Large Mono 08.0205.00A C1 Wall Large Double 08.0226.00A
No Trim installation frame for ceiling mounting.	Marco de instalación No Trim para instalación en techo.			C1 Ceiling Small 08.0208.00
No Trim installation frame for ceiling mounting.	Marco de instalación No Trim para instalación en techo.			C1 Ceiling Large 08.0207.00A
Coated aluminum mount for surface installation (wall).	Soporte en aluminio barnizado para instalación en superficie (pared).			C1 Wall Small Mono 08.0209.DY 08.0209.DR 08.0209.ER 08.0209.ES C1 Wall Small Double 08.0228.DY 08.0228.DR 08.0228.ER 08.0228.ES
Aluminum mount for surface flush installation (wall). Fit for resistant surfaces such as brick, wood or concrete. Not valid for plasterboard walls. Includes female connector cable 500 mm.	Soporte en aluminio para instalación en superficie enrasado (pared). Válido para superficies resistentes como ladrillo, madera u hormigón. No es válido para paredes de yeso laminado. Incluye cable conector hembra 500 mm.			C1 Wall Small Mono 08.0231.00 C1 Wall Small Double 08.0255.00 C1 Wall Large Mono 08.0210.00A C1 Wall Large Double 08.0254.00A
Coated aluminum mount for surface installation (ceiling).	Soporte en aluminio barnizado para instalación en superficie (techo).			C1 Ceiling Small 08.0211.DY 08.0211.DR 08.0211.ER 08.0211.ES
Coated aluminum mount for surface installation (ceiling).	Soporte en aluminio barnizado para instalación en superficie (techo).			C1 Ceiling Large 08.0212.DYA 08.0212.DRA 08.0212.ERA 08.0212.ESA

UT PRO SURFACE

DESIGNED BY FLOS ARCHITECTURAL

UT PRO SURFACE
150



LIGHT SOURCE
LED ARRAY
21W
2524 lm
3000K/CRI 80
2183 lm
3000K/CRI 90
2360 lm
4000K/CRI 90

UT PRO SURFACE
175



LIGHT SOURCE
LED ARRAY
46,5W
4740 lm
3000K/CRI 80
3960 lm
3000K/CRI 90
4278 lm
4000K/CRI 90

☐ 40 White
40 Blanco



■ 14 Black
14 Negro



Description
Indoor luminaire for surface installation, available in high power, LED technology light sources and regulator included.
The optical housing of the luminaire, as well as the container of the power supply equipment, is manufactured in high-pressure injected aluminium, with white or black finishes.
The luminaires include a power supply unit in the luminaire's own body.

Optic System
Available with spot, medium and flood optics and a built-in high-efficiency borosilicate glass reflector.

Accessories
Shielding cylinder, elliptical lens, flood and honeycomb lens.

Additional Information
Possibility of 360º rotation in the vertical axis and 90º rotation in the horizontal axis. Blocking mechanism for horizontal axis integrated.
IP20 protection grade.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Compliance of Standards and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria de interior para ser instalada en superficie, disponible con fuentes de luz de tecnología LED de alta potencia y regulador incluido.
El cuerpo óptico de la luminaria, así como el contenedor de los equipos de alimentación, están fabricados en aluminio inyectado a alta presión, acabados en pintura polvo de color blanco o negro.
Las luminarias incluyen equipo de alimentación en el propio cuerpo de la luminaria.

Sistema Óptico
Se encuentran disponibles con ópticas spot, medium y flood e incorporan reflector de cristal de borosilicato de alta eficiencia.

Accesorios
Disponible cruceta de apantallamiento, lente elíptica, lente flood y honeycomb.

Información Adicional
Posibilidad de rotación 360º en eje vertical y 90º en eje horizontal. Mecanismo de bloqueo para el eje horizontal incorporado.
Índice de protección IP20.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

UT Pro Surface 150

LED Array 21W - 2524 lm - 3000K/CRI 80 / 21W - 2183 lm - 3000K/CRI 90 / 21W - 2360 lm - 4000K/CRI 90








LED light source projector for surface installation. 120-277V power supply unit and potentiometer included.

Proyector para ser instalado en superficie con fuente de luz LED. Fuente de alimentación 120-277V y potenciómetro incluidos.

3000K - CRI 80
On board dimmer
09.7290.40D
09.7290.14D

21° SPOT




Luminous flux luminaire
2266 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	14010	0.37
2	3503	0.74
3	1557	1.11
4	876	1.48
5	560	1.85

3000K - CRI 90
On board dimmer
09.7296.40D
09.7296.14D

21° SPOT




Luminous flux luminaire
1931 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	11938	0.37
2	2984	0.74
3	1326	1.11
4	746	1.48
5	478	1.85

4000K - CRI 90
On board dimmer
09.7291.40D
09.7291.14D

21° SPOT




Luminous flux luminaire
1779 lm

Beam Angle: 21°

h(m)	E(lx)	D(m)
1	10998	0.37
2	2750	0.74
3	1222	1.11
4	687	1.48
5	440	1.85

3000K - CRI 80
On board dimmer
09.7292.40D
09.7292.14D

27° MEDIUM




Luminous flux luminaire
1902 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	8715	0.49
2	2179	0.98
3	968	1.47
4	545	1.96
5	349	2.44

3000K - CRI 90
On board dimmer
09.7297.40D
09.7297.14D

27° MEDIUM




Luminous flux luminaire
1645 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	7538	0.49
2	1884	0.98
3	838	1.47
4	471	1.96
5	302	2.44

4000K - CRI 90
On board dimmer
09.7293.40D
09.7293.14D

27° MEDIUM




Luminous flux luminaire
1779 lm

Beam Angle: 27°

h(m)	E(lx)	D(m)
1	8152	0.49
2	2038	0.98
3	906	1.47
4	509	1.96
5	326	2.44

3000K - CRI 80
On board dimmer
09.7294.40D
09.7294.14D

35° FLOOD




Luminous flux luminaire
1898 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	5618	0.64
2	1404	1.27
3	624	1.91
4	351	2.54
5	225	3.18

3000K - CRI 90
On board dimmer
09.7298.40D
09.7298.14D

36° FLOOD




Luminous flux luminaire
1666 lm

Beam Angle: 36°

h(m)	E(lx)	D(m)
1	4869	0.64
2	1217	1.28
3	541	1.92
4	304	2.56
5	195	3.20

4000K - CRI 90
On board dimmer
09.7295.40D
09.7295.14D

36° FLOOD



Luminous flux luminaire
1536 lm


Beam Angle: 36°


h(m)	E(lx)	D(m)
1	4489	0.64
2	1122	1.28
3	499	1.92
4	281	2.56
5	180	3.20

UT Pro Surface 175

LED Array 46,5W - 4740 lm - 3000K/CRI 80 / 3960 lm - 3000K/CRI 90 / 4278 lm - 4000K/CRI 90








LED light source projector for surface installation. 120-277V power supply unit and potentiometer included.

Proyector para ser instalado en superficie con fuente de luz LED. Fuente de alimentación 120-277V y potenciómetro incluidos.

3000K - CRI 80
On board dimmer
09.7320.40A
09.7320.14A

20° SPOT




Luminous flux luminaire
3638 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	21906	0.35
2	5477	0.70
3	2434	1.04
4	1369	1.39
5	876	1.74

3000K - CRI 90
On board dimmer
09.7321.40A
09.7321.14A

20° SPOT




Luminous flux luminaire
3037 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	18287	0.35
2	4572	0.70
3	2032	1.04
4	1143	1.39
5	731	1.74

4000K - CRI 90
On board dimmer
09.7322.40A
09.7322.14A

20° SPOT




Luminous flux luminaire
3283 lm

Beam Angle:		20°
h(m)	E(lx)	D(m)
1	19769	0.35
2	4942	0.70
3	2197	1.04
4	1236	1.39
5	791	1.74

3000K - CRI 80
On board dimmer
09.7323.40A
09.7323.14A

27° MEDIUM




Luminous flux luminaire
3531 lm

Beam Angle:		27°
h(m)	E(lx)	D(m)
1	13450	0.48
2	3362	0.96
3	1494	1.44
4	841	1.93
5	538	2.41

3000K - CRI 90
On board dimmer
09.7324.40A
09.7324.14A

27° MEDIUM




Luminous flux luminaire
2947 lm

Beam Angle:		27°
h(m)	E(lx)	D(m)
1	11225	0.48
2	2806	0.96
3	1247	1.44
4	702	1.93
5	449	2.41

4000K - CRI 90
On board dimmer
09.7325.40A
09.7325.14A

27° MEDIUM




Luminous flux luminaire
3187 lm

Beam Angle:		27°
h(m)	E(lx)	D(m)
1	12140	0.48
2	3035	0.96
3	1349	1.44
4	759	1.93
5	486	2.41

3000K - CRI 80
On board dimmer
09.7326.40A
09.7326.14A

34° FLOOD




Luminous flux luminaire
3476 lm

Beam Angle:		34°
h(m)	E(lx)	D(m)
1	8672	0.61
2	2168	1.22
3	964	1.83
4	542	2.44
5	347	3.04

3000K - CRI 90
On board dimmer
09.7327.40A
09.7327.14A

34° FLOOD




Luminous flux luminaire
2901 lm

Beam Angle:		34°
h(m)	E(lx)	D(m)
1	7237	0.61
2	1809	1.22
3	804	1.83
4	452	2.44
5	289	3.04

4000K - CRI 90
On board dimmer
09.7328.40A
09.7328.14A

34° FLOOD



Luminous flux luminaire
3137 lm

Beam Angle:		34°
h(m)	E(lx)	D(m)
1	7826	0.61
2	1957	1.22
3	870	1.83
4	489	2.44
5	313	3.04

Accessories / Accesorios

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

Cruceta de apantallamiento, lentes y honeycomb directamente instalables en la cabeza de la luminaria sin necesidad de accesorio de sujeción.

Screening crosspiece.	Cruceta de apantallamiento.		UT Pro Surface 150 08.8429.00 UT Pro Surface 175 08.9108.00
Elliptical lens.	Lente elíptica.		UT Pro Surface 150 08.8431.00 UT Pro Surface 175 08.9109.00
Flood lens.	Lente flood.		UT Pro Surface 150 08.8432.00 UT Pro Surface 175 08.9110.00
Honeycomb.	Honeycomb.		UT Pro Surface 150 08.8428.00 UT Pro Surface 175 08.9107.00
Snoot shielding cone.	Cono apantallador.	 	UT Pro Surface 150 08.0526.00 08.0526.40 08.0526.BW UT Pro Surface 175 08.9111.00

KAP SURFACE&SUSPENSION

DESIGNED BY FLOS ARCHITECTURAL

CEILING
Ø80 ROUND



CEILING
80 SQUARE



LIGHT SOURCE
LED ARRAY
11,3W
935 lm
2700K/CRI 90
974 lm
3000K/CRI 90

CEILING
Ø100



WALL
Ø100



SUSPENSION
Ø100



LIGHT SOURCE
POWER LED
9W
1000 lm
3000K/CRI 80

Outside / Exterior

- ☐ B1 White / B1 Blanco
- ■ 14 Black / 14 Negro
- ■ 18 Deep Brown / 18 Deep Brown

Inside / Interior

- ☐ White / Blanco
- ■ Matte Gold / Oro Mate
- ■ Black / Negro

Kap 80
Round / Square








Outside / Exterior

- ☐ 11 White / 11 Blanco
- ■ AS Brushed Aluminium / AS Aluminio Satinado
- ■ B3 Brown / B3 Marrón

Inside / Interior

- ☐ White / Blanco
- ■ Matte Gold / Oro Mate
- ■ Black / Negro

Kap Ø100





Description
Family of luminaires with direct or indirect lighting depending on the version, to be installed on ceilings, walls or suspended. Version Ø80 comes with round or square lighting modules.
The main body of the luminaire is made of extruded aluminum.
Kap 80 Surface version is available in three external finishes (black, white and deep brown) and three internal finishes (white, matte gold and black).
The other versions are available in four external finishes (white, polished aluminium, black and brown) and three internal finishes (white, matte gold and black).

Reflectors
Version Ø100 has an internal reflector in painted polycarbonate in its internal part, while version Ø80 has a reflector in painted aluminum. Furthermore, both versions incorporate a diffusing lens in opal polycarbonate to ensure uniform light distribution.

Power Supply
Electronic transformer incorporated.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Additional Information
IP20 protection grade.
Insulation class I.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Familia de luminarias con iluminación directa o iluminación directa e indirecta según versión, para ser instalada a techo, a pared o suspendida. La versión Ø80 cuenta con módulos de iluminación redondos y cuadrados.
El cuerpo principal de la luminaria está realizado en aluminio extruido.
La versión Kap 80 Surface está disponible en tres acabados exteriores (blanco, negro y deep brown) y tres acabados interiores (blanco, oro mate y negro).
El resto de versiones están disponibles en 4 acabados exteriores (blanco, aluminio pulido, negro y marrón) y 3 acabados interiores (blanco, oro mate y negro).

Reflectores
La versión Ø100 dispone de un reflector interior realizado en policarbonato pintado por la parte interna, mientras que la versión Ø80 cuenta con un reflector realizado en aluminio pintado. Además, ambas versiones incorporan una lente difusora realizada en policarbonato opal para ofrecer una luz uniforme.

Unidades de Alimentación
Transformador electrónico incorporado.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).

Información Adicional
Índice de protección IP20.
Clase de aislamiento I.
Instalable sobre superficies normalmente inflamables.

Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.


Ceiling Suspension Wall

Kap 80 Surface Ceiling Round

LED Array 11,3W - 935 lm - 2700K/CRI 90 / 11,3W - 974 lm - 3000K/CRI 90







Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V - Main&Dali/Push dimmable 220/240V.

E= External Finish
I= Internal Finish

Luminaria para ser instalada a techo con fuente de luz LED. Fuente de alimentación integrada en el cuerpo de la luminaria. Non dimmable 110/240V - Main&Dali/Push dimmable 220/240V.


E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.6020.B1
03.6020.14
03.6020.18
Mains Dimming
03.5920.B1
03.5920.14
03.5920.18
Dali/Push Version
03.6020.B1ADA
03.6020.14ADA
03.6020.18ADA

Non Dimmable
03.6021.B1
03.6021.14
03.6021.18
Mains Dimming
03.5921.B1
03.5921.14
03.5921.18
Dali/Push Version
03.6021.B1ADA
03.6021.14ADA
03.6021.18ADA

Non Dimmable
03.6023.B1
03.6023.14
03.6023.18
Mains Dimming
03.5923.B1
03.5923.14
03.5923.18
Dali/Push Version
03.6023.B1ADA
03.6023.14ADA
03.6023.18ADA



Luminous flux luminaire
710 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:	19°
h(m)	E(lx)	D(m)
1	2684	0.34
2	671	0.68
3	298	1.02
4	168	1.36
5	107	1.70

Optic Spot 3000K

E I Non Dimmable
03.6024.B1
03.6024.14
03.6024.18
Mains Dimming
03.5924.B1
03.5924.14
03.5924.18
Dali/Push Version
03.6024.B1ADA
03.6024.14ADA
03.6024.18ADA

Non Dimmable
03.6025.B1
03.6025.14
03.6025.18
Mains Dimming
03.5925.B1
03.5925.14
03.5925.18
Dali/Push Version
03.6025.B1ADA
03.6025.14ADA
03.6025.18ADA

Non Dimmable
03.6027.B1
03.6027.14
03.6027.18
Mains Dimming
03.5927.B1
03.5927.14
03.5927.18
Dali/Push Version
03.6027.B1ADA
03.6027.14ADA
03.6027.18ADA



Luminous flux luminaire
739 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	19°
h(m)	E(lx)	D(m)
1	2792	0.34
2	698	0.68
3	310	1.02
4	175	1.36
5	112	1.70

Optic Medium 2700K

E I

Non Dimmable
- 03.6000.B1
- 03.6000.14
- 03.6000.18

Mains Dimming
- 03.5900.B1
- 03.5900.14
- 03.5900.18

Dali/Push Version
- 03.6000.B1ADA
- 03.6000.14ADA
- 03.6000.18ADA

Non Dimmable
- 03.6001.B1
- 03.6001.14
- 03.6001.18

Mains Dimming
- 03.5901.B1
- 03.5901.14
- 03.5901.18


Dali/Push Version
- 03.6001.B1ADA
- 03.6001.14ADA
- 03.6001.18ADA

Non Dimmable
- 03.6003.B1
- 03.6003.14
- 03.6003.18

Mains Dimming
- 03.5903.B1
- 03.5903.14
- 03.5903.18

Dali/Push Version
- 03.6003.B1ADA
- 03.6003.14ADA
- 03.6003.18ADA





Luminous flux luminaire
606 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:		26°
h(m)	E(lx)	D(m)
1	1796	0.46
2	449	0.92
3	200	1.39
4	112	1.85
5	72	2.31

Optic Medium 3000K

E I

Non Dimmable
- 03.6004.B1
- 03.6004.14
- 03.6004.18

Mains Dimming
- 03.5904.B1
- 03.5904.14
- 03.5904.18

Dali/Push Version
- 03.6004.B1ADA
- 03.6004.14ADA
- 03.6004.18ADA

Non Dimmable
- 03.6005.B1
- 03.6005.14
- 03.6005.18

Mains Dimming
- 03.5905.B1
- 03.5905.14
- 03.5905.18


Dali/Push Version
- 03.6005.B1ADA
- 03.6005.14ADA
- 03.6005.18ADA

Non Dimmable
- 03.6007.B1
- 03.6007.14
- 03.6007.18

Mains Dimming
- 03.5907.B1
- 03.5907.14
- 03.5907.18

Dali/Push Version
- 03.6007.B1ADA
- 03.6007.14ADA
- 03.6007.18ADA






Luminous flux luminaire
630 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:		26°
h(m)	E(lx)	D(m)
1	1868	0.46
2	467	0.92
3	208	1.39
4	117	1.85
5	75	2.31

Kap 80 Surface Ceiling Round

LED Array 11,3W - 935 lm - 2700K/CRI 90 / 11,3W - 974 lm - 3000K/CRI 90







Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V - Main&Dali/Push dimmable 220/240V.

E= External Finish
I= Internal Finish

Luminaria para ser instalada a techo con fuente de luz LED. Fuente de alimentación integrada en el cuerpo de la luminaria. Non dimmable 110/240V - Main&Dali/Push dimmable 220/240V.

E= Acabado Externo
I= Acabado Interno

Optic Flood 2700K


E I

Non Dimmable
03.6040.B1
03.6040.14
03.6040.18

Mains Dimming
03.5940.B1
03.5940.14
03.5940.18

Dali/Push Version
03.6040.B1ADA
03.6040.14ADA
03.6040.18ADA





Luminous flux luminaire
688 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	50°
h(m) E(lx)	D(m)
1 1066	0.93
2 266	1.86
3 118	2.79
4 67	3.72
5 43	4.65

Non Dimmable
03.6041.B1
03.6041.14
03.6041.18

Mains Dimming
03.5941.B1
03.5941.14
03.5941.18

Dali/Push Version
03.6041.B1ADA
03.6041.14ADA
03.6041.18ADA

Non Dimmable
03.6043.B1
03.6043.14
03.6043.18

Mains Dimming
03.5943.B1
03.5943.14
03.5943.18

Dali/Push Version
03.6043.B1ADA
03.6043.14ADA
03.6043.18ADA

Optic Flood 3000K


E I

Non Dimmable
03.6044.B1
03.6044.14
03.6044.18

Mains Dimming
03.5944.B1
03.5944.14
03.5944.18

Dali/Push Version
03.6044.B1ADA
03.6044.14ADA
03.6044.18ADA





Luminous flux luminaire
715 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:	50°
h(m) E(lx)	D(m)
1 1108	0.93
2 277	1.86
3 123	2.79
4 69	3.72
5 44	4.65

Non Dimmable
03.6045.B1
03.6045.14
03.6045.18

Mains Dimming
03.5945.B1
03.5945.14
03.5945.18

Dali/Push Version
03.6045.B1ADA
03.6045.14ADA
03.6045.18ADA

Non Dimmable
03.6047.B1
03.6047.14
03.6047.18


Mains Dimming
03.5947.B1
03.5947.14
03.5947.18


Dali/Push Version
03.6047.B1ADA
03.6047.14ADA
03.6047.18ADA

Kap 80 Surface Ceiling Square

LED Array 11,3W - 935 lm - 2700K/CRI 90 / 11,3W - 974 lm - 3000K/CRI 90







Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V - Main&Dali/Push dimmable 220/240V.

E= External Finish
I= Internal Finish

Luminaria para ser instalada a techo con fuente de luz LED. Fuente de alimentación integrada en el cuerpo de la luminaria. Non dimmable 110/240V - Main&Dali/Push dimmable 220/240V.


E= Acabado Externo
I= Acabado Interno

Optic Spot 2700K

E I Non Dimmable
03.6030.B1
03.6030.14
03.6030.18
Mains Dimming
03.5930.B1
03.5930.14
03.5930.18
Dali/Push Version
03.6030.B1ADA
03.6030.14ADA
03.6030.18ADA

Non Dimmable
03.6031.B1
03.6031.14
03.6031.18
Mains Dimming
03.5931.B1
03.5931.14
03.5931.18
Dali/Push Version
03.6031.B1ADA
03.6031.14ADA
03.6031.18ADA

Non Dimmable
03.6033.B1
03.6033.14
03.6033.18
Mains Dimming
03.5933.B1
03.5933.14
03.5933.18
Dali/Push Version
03.6033.B1ADA
03.6033.14ADA
03.6033.18ADA



Luminous flux luminaire
741 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:		18°
h(m)	E(lx)	D(m)
1	2656	0.31
2	664	0.62
3	295	0.94
4	166	1.25
5	106	1.56

Optic Spot 3000K

E I Non Dimmable
03.6034.B1
03.6034.14
03.6034.18
Mains Dimming
03.5934.B1
03.5934.14
03.5934.18
Dali/Push Version
03.6034.B1ADA
03.6034.14ADA
03.6034.18ADA

Non Dimmable
03.6035.B1
03.6035.14
03.6035.18
Mains Dimming
03.5935.B1
03.5935.14
03.5935.18
Dali/Push Version
03.6035.B1ADA
03.6035.14ADA
03.6035.18ADA

Non Dimmable
03.6037.B1
03.6037.14
03.6037.18
Mains Dimming
03.5937.B1
03.5937.14
03.5937.18
Dali/Push Version
03.6037.B1ADA
03.6037.14ADA
03.6037.18ADA




Luminous flux luminaire
771 lm (EXTREME CUT OFF)
@White (B1)


Beam Angle:		18°
h(m)	E(lx)	D(m)
1	2762	0.31
2	691	0.62
3	307	0.94
4	173	1.25
5	110	1.56

Kap 80 Surface Ceiling Square

LED Array 11,3W - 935 lm - 2700K/CRI 90 / 11,3W - 974 lm - 3000K/CRI 90







Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V - Main&Dali/Push dimmable 220/240V.

E= External Finish
I= Internal Finish

Luminaria para ser instalada a techo con fuente de luz LED. Fuente de alimentación integrada en el cuerpo de la luminaria. Non dimmable 110/240V - Main&Dali/Push dimmable 220/240V.

E= Acabado Externo
I= Acabado Interno

Optic Medium 2700K

E I

Non Dimmable
03.6010.B1
03.6010.14
03.6010.18

Mains Dimming
03.5910.B1
03.5910.14
03.5910.18

Dali/Push Version
03.6010.B1ADA
03.6010.14ADA
03.6010.18ADA

Non Dimmable
03.6011.B1
03.6011.14
03.6011.18


Mains Dimming
03.5911.B1
03.5911.14
03.5911.18

Dali/Push Version
03.6011.B1ADA
03.6011.14ADA
03.6011.18ADA

Non Dimmable
03.6013.B1
03.6013.14
03.6013.18

Mains Dimming
03.5913.B1
03.5913.14
03.5913.18

Dali/Push Version
03.6013.B1ADA
03.6013.14ADA
03.6013.18ADA



Luminous flux luminaire
615 lm (EXTREME CUT OFF)

@White (B1)

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1606	0.45
2	401	0.90
3	178	1.34
4	100	1.79
5	64	2.24

Optic Medium 3000K

E I

Non Dimmable
03.6014.B1
03.6014.14
03.6014.18

Mains Dimming
03.5914.B1
03.5914.14
03.5914.18

Dali/Push Version
03.6014.B1ADA
03.6014.14ADA
03.6014.18ADA

Non Dimmable
03.6015.B1
03.6015.14
03.6015.18


Mains Dimming
03.5915.B1
03.5915.14
03.5915.18

Dali/Push Version
03.6015.B1ADA
03.6015.14ADA
03.6015.18ADA

Non Dimmable
03.6017.B1
03.6017.14
03.6017.18

Mains Dimming
03.5917.B1
03.5917.14
03.5917.18

Dali/Push Version
03.6017.B1ADA
03.6017.14ADA
03.6017.18ADA



Luminous flux luminaire
640 lm (EXTREME CUT OFF)

@White (B1)

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1670	0.45
2	418	0.90
3	186	1.34
4	104	1.79
5	67	2.24

Optic Flood 2700K


E I

Non Dimmable
03.6050.B1
03.6050.14
03.6050.18

Mains Dimming
03.5950.B1
03.5950.14
03.5950.18

Dali/Push Version
03.6050.B1ADA
03.6050.14ADA
03.6050.18ADA





Luminous flux luminaire
723 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:		55°
h(m)	E(lx)	D(m)
1	921	1.03
2	230	2.07
3	102	3.10
4	58	4.14
5	37	5.17

Non Dimmable
03.6051.B1
03.6051.14
03.6051.18

Mains Dimming
03.5951.B1
03.5951.14
03.5951.18

Dali/Push Version
03.6051.B1ADA
03.6051.14ADA
03.6051.18ADA

Non Dimmable
03.6053.B1
03.6053.14
03.6053.18

Mains Dimming
03.5953.B1
03.5953.14
03.5953.18

Dali/Push Version
03.6053.B1ADA
03.6053.14ADA
03.6053.18ADA

Optic Flood 3000K


E I

Non Dimmable
03.6054.B1
03.6054.14
03.6054.18

Mains Dimming
03.5954.B1
03.5954.14
03.5954.18

Dali/Push Version
03.6054.B1ADA
03.6054.14ADA
03.6054.18ADA





Luminous flux luminaire
752 lm (EXTREME CUT OFF)
@White (B1)

Beam Angle:		55°
h(m)	E(lx)	D(m)
1	958	1.03
2	240	2.07
3	106	3.10
4	60	4.14
5	38	5.17

Non Dimmable
03.6055.B1
03.6055.14
03.6055.18

Mains Dimming
03.5955.B1
03.5955.14
03.5955.18

Dali/Push Version
03.6055.B1ADA
03.6055.14ADA
03.6055.18ADA

Non Dimmable
03.6057.B1
03.6057.14
03.6057.18


Mains Dimming
03.5957.B1
03.5957.14
03.5957.18


Dali/Push Version
03.6057.B1ADA
03.6057.14ADA
03.6057.18ADA

Kap Surface Ceiling

Power LED 9W - 1000 lm - 3000K/CRI 80







Luminaire for mounting on the ceiling with LED light source. Non-adjustable 110/240V - 50/60Hz power supply integrated into luminaire body.

E= External Finish
I= Internal Finish

Luminaria para ser instalada a techo con fuente de luz LED. Fuente de alimentación 110/240V - 50/60Hz no regulable integrada en el cuerpo de la luminaria.


E= Acabado Externo
I= Acabado Interno

E I
- 03.4520.11B
- 03.4520.ASB
- 03.4520.ANB
- 03.4520.B3B

E I
- 03.4521.11B
- 03.4521.ASB
- 03.4521.ANB
- 03.4521.B3B

E I
- 03.4523.11B
- 03.4523.ASB
- 03.4523.ANB
- 03.4523.B3B





Luminous flux luminaire
550 lm
@White (B1)


Beam Angle: 29°


h(m)	E(lx)	D(m)
1	1482	0.52
2	371	1.04
3	165	1.56
4	93	2.08
5	59	2.61

Kap Surface Wall

Power LED 9W - 1000 lm - 3000K/CRI 80







Luminaire for wall mounting with LED light source. Non-adjustable 110/240V - 50/60Hz power supply integrated into luminaire body.

E= External Finish
I= Internal Finish

Luminaria para ser instalada a pared con fuente de luz LED. Fuente de alimentación 110/240V - 50/60Hz no regulable integrada en el cuerpo de la luminaria.


E= Acabado Externo
I= Acabado Interno

E I
- 03.5730.11B
- 03.5730.ASB
- 03.5730.ANB
- 03.5730.B3B

E I
- 03.5731.11B
- 03.5731.ASB
- 03.5731.ANB
- 03.5731.B3B

E I
- 03.5733.11B
- 03.5733.ASB
- 03.5733.ANB
- 03.5733.B3B





Luminous flux luminaire
550 lm
@White (B1)


Beam Angle: 29°


h(m)	E(lx)	D(m)
1	1482	0.52
2	371	1.04
3	165	1.56
4	93	2.08
5	59	2.61

Kap Suspension

Power LED 9W - 1000 lm - 3000K/CRI 80







Suspended ceiling-mounted luminaire with LED light source. Non-adjustable 110/240V - 50/60Hz power supply integrated into luminaire body.

E= External Finish
I= Internal Finish

Luminaria suspendida para ser instalada a techo con fuente de luz LED. Fuente de alimentación 110/240V - 50/60Hz no regulable integrada en el cuerpo de la luminaria.


E= Acabado Externo
I= Acabado Interno

E I
- 03.5810.11B
- 03.5810.ASB
- 03.5810.ANB
- 03.5810.B3B

E I
- 03.5811.11B
- 03.5811.ASB
- 03.5811.ANB
- 03.5811.B3B

E I
- 03.5813.11B
- 03.5813.ASB
- 03.5813.ANB
- 03.5813.B3B





Luminous flux luminaire
550 lm

@White (B1)

Beam Angle: 29°

h(m)	E(lx)	D(m)
1	1482	0.52
2	371	1.04
3	165	1.56
4	93	2.08
5	59	2.61

SUPER LINE&PRO

DESIGNED BY FLOS ARCHITECTURAL

SUPER LINE UP&DOWN INDIRECT



LIGHT SOURCE
TOP LED
58W
4488 lm UP
2160 lm DOWN
3000K/CRI 90

4794 lm UP
2280 lm DOWN
4000K/CRI 90

SUPER LINE UP&DOWN DIRECT



LIGHT SOURCE
TOP LED
58W
2268 lm UP
4488 lm DOWN
3000K/CRI 90

2376 lm UP
4794 lm DOWN
4000K/CRI 90

SUPER LINE DOWN



LIGHT SOURCE
TOP LED
38,6W
4488 lm
3000K/CRI 90
4794 lm
4000K/CRI 90

SUPER LINE PRO UP&DOWN



LIGHT SOURCE
TOP LED
60W
UP TO 4075 lm UP
UP TO 4605 lm DOWN
3000K/CRI 90

UP TO 4337 lm UP
UP TO 4900 lm DOWN
4000K/CRI 90


SUPER LINE PRO DOWN



LIGHT SOURCE
TOP LED
40W
UP TO 5072 lm
3000K/CRI 90
UP TO 4765 lm
4000K/CRI 90

	40 White 40 Blanco	02 Grey 02 Gris	14 Black 14 Negro	ET Brushed Brass ET Latón Cepillado	EU Brushed Rose Gold EU Oro Rosa Cepillado
Super Line					
Super Line Pro					

Super Line



Super Line Pro



Description
Collection of suspended luminaries for general lighting with a signature minimalist shape, designed to offer high-performance lighting, light quality and visual comfort combined in a very compact size.
The Super Line Pro version was designed to meet all requirements to reduce glare and improve visual comfort in offices, complying with the most restrictive conditions. A UGR less than 14 and a maximum intensity value less than 3000 cd/m^2 at an angle of 65º according to the standard, guarantee the best conditions for workplaces and make it perfect for many other applications. (Refer to the UGR chart in the accessories section).
The main body of the lights is made from extruded aluminium. Super Line is equipped with a multilayer diffusion filter which, thanks to its combination of elliptical and prism-shaped filters, ensures that the light is perfectly distributed and improves the overall visual effect, as well as providing comfort with its anti-glare properties.
Super Line Up&Down is available in two different versions:
- Indirect: a version which is better for emitting light indirectly upwards, with a greater intensity of indirect luminosity that homogenizes the lighting area, designed to provide UGR<19 and the perfect lighting conditions for offices.
- Direct: a version which is better for direct lighting and maximises efficiency, but at the same time prevents any “cave effect” with its indirect intensity, guaranteeing a high level of comfort.
Super Line Pro Up&Down comes in only one version that can be adjusted using the corresponding driver to offer a higher flux in the upper or lower part.
To minimise the visual impact of the collection, the suspension cables are also the wires, which eliminates the need for a power supply cable. Suspension length: 4,25 meters.

Installation Information
The Super Line is constructed combining the selected light source module with one of the three existing installation kits:
- Surface Kit: includes surface mounted box including the power supply driver.
- Integrated Kit: includes flush-recessed installation box, including power supply driver.
- Remote Power Supply Kit: includes an accessory as pass-through cable protection as well as a power supply driver for a remote accessable installation.
All installation kits are available either in DALI version or in a non dimmable version.
Super Line Pro uses the same power kits. For the Up&Down version, the power sources have two outputs to the light fitting, each with an amount of current (mA). By connecting each of these outputs to an input of the light fitting (Up or Down), a higher or lower flux can be chosen for each part.
The non dimmable versions are equipped with a multi-current driver that can be set during the installation in order to achieve the required illumination conditions. The Super Line installation kits come from factory at 100% of their nominal power.
All luminaries host a high-precision circular level, simplifying the installation of the luminaire, controlling calibration in both axles.

Additional Information
Insulation class I.
IP20 protection grade.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Colección de luminarias suspendidas para una iluminación general con una distintiva forma minimalista y diseñadas para ofrecer una iluminación de calidad y alto rendimiento, así como un confort visual, combinados en un tamaño realmente compacto.
La versión Super Line Pro ha sido diseñada para cumplir todos los requisitos contra deslumbramiento y confort visual en oficinas, que son las condiciones más restrictivas. Ofreciendo un UGR menor de 14 y un valor de intensidad máxima en un ángulo de 65º acorde a la norma menor de 3000 cd/m^2, lo que garantiza las mejores condiciones en espacios de trabajo y la hace perfecta para muchas otras aplicaciones. (Ver tablas UGR en el apartado de Accesorios).
El cuerpo principal de las luminarias está fabricado en aluminio extruido. Super Line está equipado con un filtro difusor técnico multicapa que, gracias a su combinación de filtros prismáticos y elípticos, asegura una distribución perfecta de la luz y mejora el efecto óptico y el confort visual mediante sus propiedades antideslumbramiento.
Super Line Up&Down está disponible en dos versiones:
- Indirect: versión que privilegia la emisión indirecta hacia arriba, con una intensidad luminosa indirecta más importante que homogeneiza el entorno de iluminación, diseñada para ofrecer un UGR<19 y la condición luminosa ideal requerida en espacios de trabajo.
- Direct: versión que privilegia la iluminación directa y maximiza la eficiencia, pero al mismo tiempo previene el “efecto cueva” con su intensidad indirecta garantizando un alto nivel de confort.
Super Line Pro Up&Down solo tiene una versión que se puede ajustar mediante el driver correspondiente para ofrecer mayor cantidad de flujo en su parte superior o inferior.
Para minimizar el impacto visual de la colección los propios cables de suspensión son los conductores, por lo que se elimina la manguera de alimentación. La longitud de suspensión es de 4,25 m.

Información de Instalación
Super Line se ha creado combinando el módulo de fuente de luz seleccionado con uno de los tres kits de instalación existentes:
- Surface Kit: incluye caja para ser instalada en superficie que incluye la fuente de alimentación.
- Integrated Kit: incluye caja de instalación a ras o encastrada que incluye la fuente de alimentación.
- Remote Power Supply Kit: incluye accesorio pasamuro para proteger los cables. Incluye fuente de alimentación para una instalación accesible a distancia.
Todos los kits de instalación están disponibles en versión DALI o en versión no regulable.
Super Line PRO dispone de los mismos kits de alimentación. Para la versión Up&Down las fuentes de alimentación disponen de dos salidas hacia la luminaria, cada una con una intensidad de corriente (mA). Conectando estas salidas a cada una a las entradas (Up o Down) de la luminaria se selecciona el flujo mayoritario y minoritario en cada parte.
Las versiones no regulables están equipadas con una alimentación de corriente múltiple que puede configurarse durante la instalación para conseguir las condiciones de iluminación necesarias. Los kits de instalación de Super Line vienen regulados desde nuestra fábrica con el 100% de su potencia nominal.
Todas las luminarias disponen de un nivel circular de alta precisión que simplifica la instalación de la misma y controla la calibración en ambos ejes.

Información Adicional
Clase de aislamiento I.
índice de protección IP20.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Super Line Up&Down Indirect

Top LED 58W - 4488 lm UP - 2160 lm DOWN - 3000K/CRI 90 / 58W - 4794 lm UP - 2280 lm DOWN - 4000K/CRI 90








LED luminaire for direct and indirect lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately.

Luminaria LED de iluminación general directa e indirecta con un distintivo diseño minimalista y compacto para ser instalada a techo mediante suspensión.
Fuente de alimentación incluida en los distintos kits de instalación, que se han de pedir por separado.

3000K
- 03.9502.40
- 03.9502.02
- 03.9502.14
- 03.9502.ET
- 03.9502.EU




Luminous flux luminaire 4914 lm

Beam Angle DIR: 101°

h(m)	E(lx)	D(m)
1	1229	2.39
2	307	4.78
3	137	7.17
4	77	9.57
5	49	11.96

4000K
- 03.9503.40
- 03.9503.02
- 03.9503.14
- 03.9503.ET
- 03.9503.EU



Luminous flux luminaire 5225 lm


Beam Angle DIR: 101°


h(m)	E(lx)	D(m)
1	1307	2.39
2	327	4.78
3	145	7.17
4	82	9.57
5	52	11.96

Super Line Up&Down Direct

Top LED 58W - 2268 lm UP - 4488 lm DOWN - 3000K/CRI 90 / 58W - 2376 lm UP - 4794 lm DOWN - 4000K/CRI 90








LED luminaire for direct and indirect lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately.

Luminaria LED de iluminación general directa e indirecta con un distintivo diseño minimalista y compacto para ser instalada a techo mediante suspensión.
Fuente de alimentación incluida en los distintos kits de instalación, que se han de pedir por separado.

3000K
- 03.9500.40
- 03.9500.02
- 03.9500.14
- 03.9500.ET
- 03.9500.EU




Luminous flux luminaire 5154 lm

Beam Angle DIR: 82°

h(m)	E(lx)	D(m)
1	1948	1.57
2	487	3.13
3	216	4.70
4	122	6.27
5	78	7.84

4000K
- 03.9501.40
- 03.9501.02
- 03.9501.14
- 03.9501.ET
- 03.9501.EU



Luminous flux luminaire 5472 lm


Beam Angle DIR: 82°


h(m)	E(lx)	D(m)
1	2068	1.57
2	517	3.13
3	230	4.70
4	129	6.27
5	83	7.84

Super Line Down

Top LED 38,5W - 4488 lm - 3000K/CRI 90 / 38,5W- 4794 lm - 4000K/CRI 90








LED luminaire for general lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately.

Luminaria LED de iluminación general con un distintivo diseño minimalista y compacto para ser instalada a techo mediante suspensión.
Fuente de alimentación incluida en los distintos kits de instalación, que se han de pedir por separado.

3000K
- 03.9510.40
- 03.9510.02
- 03.9510.14
- 03.9510.ET
- 03.9510.EU




Luminous flux luminaire 3571 lm

Beam Angle: 82°

h(m)	E(lx)	D(m)
1	1948	1.57
2	487	3.13
3	216	4.70
4	122	6.27
5	78	7.84

4000K
- 03.9511.40
- 03.9511.02
- 03.9511.14
- 03.9511.ET
- 03.9511.EU



Luminous flux luminaire 3814 lm


Beam Angle: 82°


h(m)	E(lx)	D(m)
1	2080	1.57
2	520	3.13
3	231	4.70
4	130	6.27
5	83	7.84

Super Line Pro Up&Down

Majority UP - Top LED 60W - 4075 lm UP - 2500 lm DOWN - 3000K/CRI 90 / 60W - 4335 lm UP - 2660 lm DOWN - 4000K/CRI 90
Majority DOWN - Top LED 60W - 2590 lm UP - 4605 lm DOWN - 3000K/CRI 90 / 60W - 2755 lm UP - 4900 lm DOWN - 4000K/CRI 90








LED luminaire for direct and indirect lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately. Greater Up or Down intensity can be selected using power kits with a device with two independent outputs.

Luminaria LED de iluminación general directa e indirecta con un distintivo diseño minimalista y compacto para ser instalada a techo mediante suspensión.
Fuente de alimentación incluida en los distintos kits de instalación, que se han de pedir por separado.
La selección del de mayor intensidad Up o Down, se realiza en los Kits de alimentación que disponen de un equipo con dos salidas independientes.

3000K
- 03.9560.40
- 03.9560.02
- 03.9560.14
- 03.9560.ET
- 03.9560.EU






Luminous flux luminaire
6172 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1515	1.68
2	379	3.35
3	168	5.03
4	95	6.71
5	61	8.38






Luminous flux luminaire
6314 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	2367	1.68
2	592	3.36
3	263	5.04
4	148	6.72
5	95	8.40

@White (40)

4000K
- 03.9561.40
- 03.9561.02
- 03.9561.14
- 03.9561.ET
- 03.9561.EU






Luminous flux luminaire
6135 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	1493	1.68
2	373	3.35
3	166	5.03
4	93	6.71
5	60	8.38





Luminous flux luminaire
6172 lm


Beam Angle:		80°
h(m)	E(lx)	D(m)
1	2275	1.68
2	569	3.36
3	253	5.04
4	142	6.72
5	91	8.40


@White (40)

Super Line Pro Down

Top LED 40W - 4765 lm - 3000K/CRI 90 / 40W- 5070 lm - 4000K/CRI 90








LED luminaire for general lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately, allowing the maximum brightness to be selected.

Luminaria LED de iluminación general con un distintivo diseño minimalista y compacto para ser instalada a techo mediante suspensión.
Fuente de alimentación incluida en los distintos kits de instalación, que se han de pedir por separado, pudiendo seleccionar la intensidad máxima.

3000K
- 03.9570.40
- 03.9570.02
- 03.9570.14
- 03.9570.ET
- 03.9570.EU






Luminous flux luminaire
3955 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	2367	1.68
2	592	3.36
3	263	5.04
4	148	6.72
5	95	8.40

@White (40)

4000K
- 03.9571.40
- 03.9571.02
- 03.9571.14
- 03.9571.ET
- 03.9571.EU





Luminous flux luminaire
3801 lm

Beam Angle:		80°
h(m)	E(lx)	D(m)
1	2275	1.68
2	569	3.36
3	253	5.04
4	142	6.72
5	91	8.40

@White (40)

Accessories / Accesorios

The non-adjustable versions of Super Line and Super Line Pro Down are equipped with a multi-current driver, that can be set during the installation in order to achieve the required illumination conditions and comfort levels. Installation kits come from factory at 100% of their nominal power (1050 mA). At maximum power, all versions of Super Line Pro comply with the requirements UGR<19 and L 65º<3000 cd.

Las versiones no regulables de Super Line y Super Line Pro Down están equipadas con una alimentación de corriente múltiple que puede configurarse durante la instalación para conseguir las condiciones de iluminación y los niveles de confort requeridos. Los kits de instalación vienen de fábrica con el 100% de su potencia nominal (1050 mA). Super Line Pro cumple en todas sus versiones y a máxima potencia con los requisitos de UGR<19 y L 65º<3000 cd.

Super Line

		Indirect		Direct	
Driver setting	**Light emission**	**UGR***	**L 65º < 3000 cd**	**UGR***	**L 65º < 3000 cd**
1050 mA	100%	UGR < 19			
850 mA	80%	UGR < 19			
700 mA	70%	UGR < 19			
550 mA	55%	UGR < 19	√		
500 mA	50%	UGR < 19	√	UGR < 19	√
350 mA	36%	UGR < 19	√	UGR < 19	√

*X=4H, Y=8H, S=0.25H, reflections 70/50/20

Super Line Pro


Light emission	**UGR***	**L 65º < 3000 cd**
Up & Down Majority Up	UGR < 14	√
Up & Down Majority Down	UGR < 17	√
Down	UGR < 18	√

Super Line / Super Line Pro Down

Surface Power Supply Kit

60W – 220/240V power supply included. Kits for Super Line and Super Line Pro Down are equipped with a dip-switch driver to select the maximum intensities.

Incluye fuente de alimentación 60W - 220/240V. Los Kits para Super Line y Super Line Pro Down, disponen de driver con dip-switch para seleccionar las intensidades máximas.



Non Dimmable
- 08.0520.40A
- 08.0520.02A
- 08.0520.14A
- 08.0520.ETA
- 08.0520.EUA


Dali Version
- 08.0521.40A
- 08.0521.02A
- 08.0521.14A
- 08.0521.ETA
- 08.0521.EUA

Super Line Pro Up&Down

Surface Power Supply Kit

85W – 220/240V power supply included. Kits for Super Line Pro Up&Down are equipped with two outputs to select which part (Up or Down) is brighter.

Incluye fuente de alimentación 85W - 220/240V. Los Kits para Super Line Pro Up&Down disponen de dos salidas para seleccionar qué parte (Up o Down) dispone de mayor intensidad.




Non Dimmable / Dali Version
- 08.0640.40
- 08.0640.02
- 08.0640.14
- 08.0640.ET
- 08.0640.EU

Super Line / Super Line Pro Down

Recessed Power Supply Kit

60W – 220/240V power supply included. Kits for Super Line and Super Line Pro Down are equipped with a dip-switch driver to select the maximum intensities.

Incluye fuente de alimentación 60W - 220/240V. Los Kits para Super Line y Super Line Pro Down, disponen de driver con dip-switch para seleccionar las intensidades máximas.



Non Dimmable
- 08.0522.40A
- 08.0522.02A
- 08.0522.14A
- 08.0522.ETA
- 08.0522.EUA


Dali Version
- 08.0523.40A
- 08.0523.02A
- 08.0523.14A
- 08.0523.ETA
- 08.0523.EUA

Super Line Pro Up&Down

Recessed Power Supply Kit

85W – 220/240V power supply included. Kits for Super Line Pro Up&Down are equipped with two outputs to select which part (Up or Down) is brighter.

Incluye fuente de alimentación 85W - 220/240V. Los Kits para Super Line Pro Up&Down disponen de dos salidas para seleccionar qué parte (Up o Down) dispone de mayor intensidad.



Non Dimmable / Dali Version
- 08.0641.40
- 08.0641.02
- 08.0641.14
- 08.0641.ET
- 08.0641.EU


Accessories / Accesorios

Super Line / Super Line Pro Down

Remote Power Supply Kit

Includes two suspension kits and a 60W - 220/240V power supply. Kits for Super Line and Super Line Pro Down are equipped with a dip-switch driver to select the maximum intensities.

Incluye dos kits de suspensión y una fuente de alimentación de 60W - 220/240V. Los Kits para Super Line y Super Line Pro Down, disponen de driver con dip-switch para seleccionar las intensidades máximas.



Non Dimmable
- 08.0524.40
- 08.0524.02
- 08.0524.14
- 08.0524.ET
- 08.0524.EU


Dali Version
- 08.0525.40A
- 08.0525.02A
- 08.0525.14A
- 08.0525.ETA
- 08.0525.EUA

Super Line Pro Up&Down

Remote Power Supply Kit

Includes two suspension kits and two 45W - 220/240V power supplies. Kits for Super Line Pro Up&Down are equipped with two outputs to select which part (Up or Down) is brighter.

Incluye dos kits de suspensión y dos fuentes de alimentación de 45W - 220/240V. Los Kits para Super Line PRO Up&Down disponen de dos salidas para seleccionar qué parte (Up o Down) dispone de mayor intensidad.



Non Dimmable / Dali Version
- 08.0642.40
- 08.0642.02
- 08.0642.14
- 08.0642.ET
- 08.0642.EU


Interconnection Accessories / Accesorios de interconexión

Super Line

Mechanical union accessory for the installation of various units in continuous lines.

Accesorio de unión mecánico para implementar varias unidades en líneas continuas.






- 08.9076.40
- 08.9076.02
- 08.9076.14
- 08.9076.ET
- 08.9076.EU

Super Line Pro

Mechanical union accessory for the installation of various units in continuous lines.

Accesorio de unión mecánico para implementar varias unidades en líneas continuas.





- 08.9077.40
- 08.9077.02
- 08.9077.14
- 08.9077.ET
- 08.9077.EU

Interconnection Example / Ejemplo de interconexión

Super Line



Super Line Pro



LIGHT BELL

DESIGNED BY PIERO LISSONI



LIGHT SOURCE
LED ARRAY
55W
6388 lm
2700K/CRI 90
6714 lm
3000K/CRI 90



70 Matte White
70 Blanco Mate

Internal Finish

Anodized Aluminium
Aluminio Anodizado



AN Anodized Black
AN Negro Anodizado

Gold
Oro



AP Polished Aluminium
AP Aluminio Pulido

Anodized Aluminium
Aluminio Anodizado



76 Transparent Glass
76 Cristal Transparente



CE Concrete
CE Cemento

Description
Suspended general lighting luminaire for indoor mounting. It has a high efficiency latest generation LED light source and a low-loss technical thermoplastic diffuser.
The reflector is supplied separately and is available in spun aluminium with different patterns, and ixn transparent glass, depending on the versions. Power supply source integrated into luminaire housing.

Power Supply
Integrated 220/240V constant voltage power supply source.

Additional Information
Available in Dali, and Dimmable Push versions.
IP20 protection grade.
Insulation class I.
Pin-block type dissipater.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria suspendida de iluminación general para ser instalada en interiores. Cuenta con una fuente de luz LED de última generación de alta eficiencia y difusor realizado en termoplástico técnico de bajas pérdidas.
El reflector de la luminaria se sirve por separado, y está disponible en aluminio repulsado en distintos decorados y en cristal transparente según versiones. Fuente de alimentación integrada en el cuerpo de la luminaria.

Fuente de Alimentación
Fuente de alimentación de corriente constante 220/240V integrada.

Información Adicional
Disponible en versiones Dali, y Dimmable Push.
Índice de protección IP20.
Clase de aislamiento I.
Disipador tipo pin-block.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.

Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Light Bell Light Source

LED Array 55W - 6388 lm - 2700K/CRI 90 / 55W - 6714 lm - 3000K/CRI 90





3,81 Kg

GWT 850°

IP 20

DALI

LED INCL.

Suspended luminaire for mounting on the ceiling with LED light source. (4 metres maximum distance to ceiling). Power supply source 220/240V integrated into luminaire housing. Reflector not included; supplied separately.
Please ask us for a higher IP.
Includes a 4-meter suspension cable.
With glass screen, maximum height from the ground: 5 m.


Luminaria suspendida para ser instalada a techo con fuente de luz LED (máxima distancia al techo 4 metros). Fuente de alimentación 220/240V integrada en el cuerpo de la luminaria. Reflector no incluido, se sirve por separado.
Consultar para IP superior.
Incluye cable de suspensión de 4m.
Con pantalla de cristal, altura máxima respecto al suelo: 5m.

2700K
Non Dimmable
07.9641.14A
Dimmable Dali
07.9641.14ADA

3000K
Non Dimmable
07.9642.14A
Dimmable Dali
07.9642.14ADA

Light Bell Reflector






07.9630.70

0,95 Kg

E I **2700K**
07.9630.70
+
07.9641.14A

37°




Luminous flux luminaire
3026 lm (EXTREME CUT OFF)

Beam Angle:	37°
h(m) E(lx)	D(m)
1 4481	0.67
2 1120	1.33
3 498	2.00
4 280	2.67
5 179	3.34

E I **3000K**
07.9630.70
+
07.9642.14A

37°



Luminous flux luminaire
3139 lm (EXTREME CUT OFF)

Beam Angle:	37°
h(m) E(lx)	D(m)
1 4606	0.68
2 1152	1.35
3 512	2.03
4 288	2.70
5 184	3.38




07.9630.AP

0,95 Kg

E I **2700K**
07.9630.AP
+
07.9641.14A

37°




Luminous flux luminaire
3026 lm (EXTREME CUT OFF)

Beam Angle:	37°
h(m) E(lx)	D(m)
1 4481	0.67
2 1120	1.33
3 498	2.00
4 280	2.67
5 179	3.34

E I **3000K**
07.9630.AP
+
07.9642.14A

37°



Luminous flux luminaire
3139 lm (EXTREME CUT OFF)

Beam Angle:	37°
h(m) E(lx)	D(m)
1 4606	0.68
2 1152	1.35
3 512	2.03
4 288	2.70
5 184	3.38




07.9630.AN

0,95 Kg

E I **2700K**
07.9630.AN
+
07.9641.14A

78°




Luminous flux luminaire
2635 lm (EXTREME CUT OFF)

Beam Angle:	78°
h(m) E(lx)	D(m)
1 1860	1.61
2 465	3.22
3 207	4.84
4 116	6.45
5 74	8.06

E I **3000K**
07.9630.AN
+
07.9642.14A

78°



Luminous flux luminaire
2733 lm (EXTREME CUT OFF)

Beam Angle:	78°
h(m) E(lx)	D(m)
1 1920	1.62
2 480	3.23
3 213	4.85
4 120	6.47
5 77	8.08

E= External Finish
I= Internal Finish

E= Acabado Externo
I= Acabado Interno

Light Bell Reflector




07.9630.76

3,41 Kg

2700K
07.9630.76
+
07.9641.14A

46°




Luminous flux luminaire
3391 lm [EXTREME CUT OFF]

Beam Angle:		46°
h(m)	E(lx)	D(m)
1	2615	0.81
2	654	1.63
3	291	2.44
4	163	3.26
5	105	4.07

3000K
07.9630.76
+
07.9642.14A

46°



Luminous flux luminaire
3518 lm [EXTREME CUT OFF]

Beam Angle:		46°
h(m)	E(lx)	D(m)
1	2648	0.85
2	662	1.71
3	294	2.56
4	166	3.41
5	106	4.27




07.9630.CE

4 Kg

2700K
07.9630.CE
+
07.9641.14A

79°




Luminous flux luminaire
3099 lm [EXTREME CUT OFF]

Beam Angle:		79°
h(m)	E(lx)	D(m)
1	2077	1.66
2	519	3.32
3	231	4.97
4	130	6.63
5	83	8.29

3000K
07.9630.CE
+
07.9642.14A

79°



Luminous flux luminaire
3229 lm [EXTREME CUT OFF]

Beam Angle:		79°
h(m)	E(lx)	D(m)
1	2164	1.66
2	541	3.32
3	240	4.97
4	135	6.63
5	87	8.29

Accessories / Accesorios

Rosette for indoors. IP20.

Rosetón de alimentación para interiores. IP20.




Non Dimmable
F0556020
Dimmable Push/*Dali
F0557020


* The F0557020 Dali version has a 4-meter cable, 5 poles and a 0.75mm² section.
* La versión Dali F0557020 lleva cable de 4m, 5 polos y sección 0.75mm² .

Rosette. IP20.

Rosetón de alimentación. IP20.



08.8775.40



08.8775.14

FORT KNOX WALL

DESIGNED BY PHILIPPE STARCK

FORT KNOX
WALL



LIGHT SOURCE
POWER LED
35W
3715 lm
2700K/CRI 90
3900 lm
3000K/CRI 90
3774 lm
4000K/CRI 90

FORT KNOX
WALL MINI



LIGHT SOURCE
POWER LED
25W
2329 lm
2700K/CRI 90
2718 lm
3000K/CRI 90
2658 lm
4000K/CRI 90

40 White
40 Blanco



05 Polished Silver
05 Plata Pulida



14 Black/RAL 9005
14 Negro



Description
Luminary for wall application designed for indirect lighting.
Die-cast aluminium alloy body with hand polished finish and protected with transparent liquid paint, or powder-coated white or matte black.
Wall support made in injected aluminium. Thanks to its innovative design, this holder allows both horizontal and vertical regulation up to 10 mm, ensuring a perfect installation on any type of surface. Additionally, this product includes a spirit level, allowing a perfect luminaire calibration.

Reflectors
Thanks to its adapted design, the asymmetrical lens allow luminarie's maximum efficiency and optimal light distribution.

Power Supply
Non Dimmable, Dimmable 1-10V or Dimmable Dali power source incorporated in the luminaire body.

Additional Information
IP20 protection grade.
Insulation class I.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria de pared para luz indirecta.
Cuerpo realizado en aleación de aluminio inyectado a presión con acabado pulido a mano y protegido por pintura líquida transparente o barniz en polvo de color blanco o negro mate.
Soporte de pared realizado en aluminio inyectado. Gracias a su novedoso diseño, este soporte permite la regulación tanto en horizontal como en vertical de hasta 10 mm, garantizando una perfecta instalación sobre cualquier superficie. Además, el producto incorpora un nivel de burbuja que permite una perfecta calibración de la luminaria.

Reflectores
Lente asimétrica que gracias a su diseño adaptado, permite una eficiencia de la luminaria máxima además de una distribución óptima de la luz.

Unidades de Alimentación
Fuente de alimentación No Dimmable, Dimmable 1-10V o Dimmable Dali incorporada en el cuerpo principal de la luminaria.

Información Adicional
Índice de protección IP20.
Clase de aislamiento I.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Fort Knox Wall

Power LED 35W - 3715 lm - 2700K/CRI 90 / 3900 lm - 3000K/CRI 90 / 3774 lm - 4000K/CRI 90








Wall-mounted LED luminaire for indirect lighting. Power source 220-240V incorporated into luminaire's body.

Luminaria LED de pared para luz indirecta. Fuente de alimentación 220-240V integrada en el cuerpo de la luminaria.

2700K
Dimmable 1-10V
- ☐ 09.2111.40C
- ▒ 09.2111.05C
- ■ 09.2111.14C

Dali Version
- ☐ 09.2111.40CDA
- ▒ 09.2111.05CDA
- ■ 09.2111.14CDA




Luminous flux luminaire
2951 lm

Beam Angle:	30°
h(m)	E(lx) D(m)
1	681 2.24
2	170 4.49
3	76 6.73
4	43 8.97
5	27 11.21

3000K
Dimmable 1-10V
- ☐ 09.2110.40C
- ▒ 09.2110.05C
- ■ 09.2110.14C

Dali Version
- ☐ 09.2110.40CDA
- ▒ 09.2110.05CDA
- ■ 09.2110.14CDA




Luminous flux luminaire
3036 lm

Beam Angle:	30°
h(m)	E(lx) D(m)
1	700 2.24
2	175 4.49
3	78 6.73
4	44 8.97
5	28 11.21

4000K
Dimmable 1-10V
- ☐ 09.2112.40C
- ▒ 09.2112.05C
- ■ 09.2112.14C

Dali Version
- ☐ 09.2112.40CDA
- ▒ 09.2112.05CDA
- ■ 09.2112.14CDA




Luminous flux luminaire
3198 lm


Beam Angle:	30°
h(m)	E(lx) D(m)
1	738 2.24
2	184 4.49
3	82 6.73
4	46 8.97
5	30 11.21

Fort Knox Wall Mini

Power LED 25W - 2329 lm - 2700K/CRI 90 / 2718 lm - 3000K/CRI 90 / 2658 lm - 4000K/CRI 90








Wall-mounted LED luminaire for indirect lighting. Power source 220-240V incorporated into luminaire's body.

Luminaria LED de pared para luz indirecta. Fuente de alimentación 220-240V integrada en el cuerpo de la luminaria.

2700K
Non Dimmable
- ☐ 09.2126.40B
- ▒ 09.2126.05B
- ■ 09.2126.14B

Dali Version
- ☐ 09.2126.40BDA
- ▒ 09.2126.05BDA
- ■ 09.2126.14BDA




Luminous flux luminaire
1704 lm

Beam Angle:	33°
h(m)	E(lx) D(m)
1	394 2.88
2	98 5.75
3	44 8.63
4	25 11.50
5	16 14.38

3000K
Non Dimmable
- ☐ 09.2125.40B
- ▒ 09.2125.05B
- ■ 09.2125.14B

Dali Version
- ☐ 09.2125.40BDA
- ▒ 09.2125.05BDA
- ■ 09.2125.14BDA




Luminous flux luminaire
1986 lm

Beam Angle:	33°
h(m)	E(lx) D(m)
1	459 2.88
2	115 5.75
3	51 8.63
4	29 11.50
5	18 14.38

4000K
Non Dimmable
- ☐ 09.2127.40B
- ▒ 09.2127.05B
- ■ 09.2127.14B

Dali Version
- ☐ 09.2127.40BDA
- ▒ 09.2127.05BDA
- ■ 09.2127.14BDA



Luminous flux luminaire
1945 lm

Beam Angle:	33°
h(m)	E(lx) D(m)
1	449 2.88
2	112 5.75
3	50 8.63
4	28 11.50
5	18 14.38

THIN LED

DESIGNED BY FLOS ARCHITECTURAL



LIGHT SOURCE
TOP LED
20W/m
24V
1822 lm/m
3000K/CRI 90

30 White
30 Blanco



29 Anodized Aluminium
29 Aluminio Anodizado



BZ Anodized Bronze
BZ Bronce Anodizado



Patented and registered model / Modelo patentado y registrado.

Description
Wall application luminaire for indirect lighting.
Anodised aluminium housing with internal super-pure optical aluminium reflector. Very easy to install and extremely versatile. The printed circuit is made of jointed modules with double connector through silver contacts. This ensure a safe power supply avoiding damages which could be caused during assembling phase.
The utilized LED, with a very tight pitch and a 120° emission, together with the reflection system, grant a very high and even lighting emission performance.
Thanks to a patented light emission control system, the light fitting performance is really high, with an optimized and very comfortable light distribution.

Power Supply
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Additional Information
Led modules: 404 mm - 1201 mm - 1034 mm – 2040 mm - 2541 mm- 3042 mm.
Blind module: 1034 mm.
Max connection length 3044 mm.
Side covers included.
IP20 protection grade.
Classe d'isolation III.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Aparato de iluminación indirecta para ser instalado en la pared. Cuerpo en aluminio anodizado con reflector interior óptico realizado en aluminio super-puro. Muy fácil de instalar y extremadamente versátil. El circuito impreso está realizado con módulos articulados con un doble conector a través de contactos de plata. Esto asegura un alimentador de corriente seguro evitando daños que podrían originarse durante la fase de montaje.
Los LEDs utilizados con una ajustada frecuencia y una emisión de 120°, junto con el sistema reflector, garantizan unas prestaciones elevadas y una iluminación uniforme.
Gracias a un sistema patentado de control de emisiones de luz, el rendimiento de las lámparas es muy alto, con una distribución de iluminación óptima y muy confortable.

Unidades de Alimentación
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).

Información Adicional
Módulos de LED: 404 mm - 1201 mm - 1034 mm – 2040 mm - 2541 mm- 3042 mm.
Módulo deslumbramiento: 1034 mm.
Máxima longitud de conexión 3044 mm.
Cubiertas laterales incluidas.
Grado de protección IP20.
Clase de aislamiento III.
Instalable sobre superficies normalmente inflamables.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

Thin LED

Top LED 20W/m - 24V - 1822 lm/m - 3000K/CRI 90







Wall application luminaire for indirect lighting with LED. Remote transformer not included.

Luminaria de pared de iluminación indirecta con LED. Transformador remoto no incluido.

Recommended power supply / Equipos recomendados*:


Non Dimmable	60.9705 (60W)	404/1034/1201/2040/2541mm
Non Dimmable	60.9777A (120W)	3042mm
Dimmable 1-10V	60.9681 (120W)	
Dim DALI	60.9880 (120W)	
Casambi	60.9683 (120W)	
Mains Dimming	60.9881 (60W)	404/1034/1201/2040/2541mm

* Refer to the Drivers chapter / Ver capítulo Drivers

L: 404 mm

6,8W - 711 lm - 16 LEDs

09.0045.30B
09.0045.29B
09.0045.BZB



Luminous flux luminaire 621 lm


Beam Angle: 101°

h(m)	E(lx)	D(m)
1	118	6.46
2	30	12.92
3	13	19.38
4	7	25.84
5	5	32.30

L: 1034 mm

20,5W - 2133 lm - 42 LEDs

09.0100.30B
09.0100.29B
09.0100.BZB



Luminous flux luminaire 1863 lm


Beam Angle: 101°

h(m)	E(lx)	D(m)
1	355	6.46
2	89	12.92
3	39	19.38
4	22	25.84
5	14	32.30

L: 1201 mm

23,9W - 2450 lm - 55 LEDs

09.0120.30B
09.0120.29B
09.0120.BZB



Luminous flux luminaire 2173 lm

Beam Angle: 101°

h(m)	E(lx)	D(m)
1	414	6.46
2	104	12.92
3	46	19.38
4	26	25.84
5	17	32.30

L: 1034 mm BLIND*


09.0104.30A
09.0104.29A
09.0104.BZA

* To create continuous profile lines / Para crear líneas de perfil continuas.

L: 2040 mm

41W - 4266 lm - 84 LEDs

09.0101.30B
09.0101.29B
09.0101.BZB



Luminous flux luminaire 3726 lm


Beam Angle: 101°

h(m)	E(lx)	D(m)
1	710	6.46
2	178	12.92
3	79	19.38
4	44	25.84
5	28	32.30

L: 2541 mm

47,8W - 5250 lm - 105 LEDs

09.0102.30B
09.0102.29B
09.0102.BZB



Luminous flux luminaire 4657 lm


Beam Angle: 101°

h(m)	E(lx)	D(m)
1	888	6.46
2	222	12.92
3	99	19.38
4	55	25.84
5	36	32.30

L: 3042 mm

61,5W - 6399 lm - 126 LEDs

09.0103.30B
09.0103.29B
09.0103.BZB



Luminous flux luminaire 5588 lm

Beam Angle: 101°

h(m)	E(lx)	D(m)
1	1065	6.46
2	266	12.92
3	118	19.38
4	67	25.84
5	43	32.30

G - O

DESIGNED BY JORGE HERRERA



LIGHT SOURCE
TOP LED
1,2W
96 lm
3000K/CRI 90

30 White
30 Blanco



29 Anodized Aluminium
29 Aluminio Anodizado



55 Stainless Steel
55 Acero Inoxidable



BZ Bronze
BZ Bronce



AN Anodized Black
AN Negro Anodizado



Light Colours
Colores de la Luz

White Light
Luz Blanca



Amber Light
Luz Ámbar



Description
Embedded light fixture for indoor use in all its finishes, except stainless steel which is suitable for outdoor use.
Available with next-generation LED light source, suitable for responding to diverse signalling needs on pathways or stairways.
Available in different light shades, through coloured internal diffuser.
Light body made of aluminium, stainless steel or machined bronze.

Power Supply
Constant voltage power supply not included, available as an accessory.
Up to 6 or 15 G-O can be installed with the recommended power sources.

Accessories
With extruded aluminium accessories for embedding in concrete walls.

Additional Information
IP65 protection grade.
Insulation class III.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria empotrada concebida para uso interior en todos sus acabados, excepto el acero inoxidable que es apto también para uso exterior.
Disponible con fuente de luz LED de última generación apta para responder a las diversas necesidades de señalizadores a lo largo de caminos de paso o escaleras. Disponible en diferentes colores de luz mediante un difusor interno coloreado. El cuerpo de la luminaria está realizado en aluminio, acero inoxidable o bronce mecanizado.

Unidades de Alimentación
Fuente de alimentación de tensión constante no incluida, disponible como accesorio.
Es posible instalar hasta 6 ó 15 G-O con las fuentes de alimentación recomendadas.

Accesorios
Dispone de accesorio para empotrar en paredes de hormigón realizado en alumino extruido.

Información Adicional
Índice de protección IP65.
Clase de aislamiento III.
Instalable sobre superficie normalmente inflamables.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

G-O

Top LED 1,2W - 24V - 96 lm - 3000K/CRI 90







Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

Luminaria de señalización semiempotrada para aplicación interior a techo/pared. Fuente de alimentación no incluida. Inlcuye cable de alimentación de 1000 mm.

Equipment for remote installation in an accesible place: it does not fit through the recessing hole of the luminaire, except 60.9157.

Equipo para instalación remota en lugar accesible: no cabe a través del agujero de empotramiento de la luminaria, salvo el 60.9157.


Recommended power supply / Equipos recomendados*:

Non Dimmable 110-240V	60.9157 (8W)
Non Dimmable 220-240V	60.8703 (25W)

* Refer to the Drivers chapter / Ver capítulo Drivers

White Light/Luz Blanca

- 09.3200.30A
- 09.3200.29A
- 09.3200.55A
- 09.3200.BZA
- 09.3200.ANA




Luminous flux luminaire
4 lm

Beam Angle:	74°
h(m)	E(lx) D(m)
1	2 1.51
2	1 3.03
3	0 4.54
4	0 6.06
5	0 7.57

Amber Light/Luz Ámbar

- 09.3201.30A
- 09.3201.29A
- 09.3201.55A
- 09.3201.BZA
- 09.3201.ANA



Luminous flux luminaire
2 lm

Beam Angle:	72°
h(m)	E(lx) D(m)
1	1 1.46
2	0 2.92
3	0 4.38
4	0 5.85
5	0 7.31

Accessories / Accesorios

Housing for recessed installation made in anodized aluminium for outdoor installation.

Cuerpo de empotramiento realizado en aluminio anodizado para instalación en exterior.




08.8422.00

Control Units / Unidades de Control

Dimmable control unit with 1 channel for 24V LED modules. Power supply not included. Max. 120W - 5A.

Unidad de control dimable de 1 canal para la regulación de módulos LED, para equipos de 24V. No incluye fuente de alimentación. Max. 120W - 5A.





1-10V
60.8640
L1: 172

DALI
60.9766
L1: 181

THEBLOCKOFLIGHT

DESIGNED BY KNUD HOLSCHER



LIGHT SOURCE
POWER LED
2,2W
154 lm
3000K/CRI 80

☐ 01 Matte White
01 Blanco Mate



■ 72 Grey
72 Gris



■ 04 Matte Black
04 Negro Mate



Description
Embedded light fixture designed for indoor or outdoor use (IP65 protection grade). Available with next-generation LED light source in response to diverse signalling needs on pathways or stairways.
Front made of aluminium with finish in matte white, grey or matte black.

Power Supply
Built-in, non-regulable constant current power supply of 100/240V, 50/60Hz. 700 mA current.

Accessories
Has galvanised steel accessories for embedding in concrete walls.

Additional Information
IP65 protection grade.
Insulation class I.
Suitable for installation on normally inflammable surfaces.

Before placing your order, please consult the product details also on the Flos professional website, in its technical data sheet and in the installation and assembly instructions to find all the information that may not be included in this catalogue or that could be relevant to your specific project or installation.

Standard Compliance and Quality Marks
EN60598-1 European Technical Standards and any subsequent additions.

Descripción
Luminaria empotrada concebida para uso interior o exterior (grado de protección IP65). Disponible con fuente de luz LED de última generación apta para responder a las diversas necesidades de señalizadores a lo largo de caminos de paso o escaleras.
Frontal realizado en aluminio con acabado en pintura blanco mate, gris o negro mate.

Unidades de Alimentación
Fuente de alimentación de corriente constante 100/240V, 50/60Hz no regulable integrada. Alimentación a 700 mA.

Accesorios
Dispone de accesorio para empotrar en paredes de hormigón realizado en acero galvanizado.

Información Adicional
Índice de protección IP65.
Clase de aislamiento I.
Instalable sobre superficies normalmente inflamables.


Antes de realizar su pedido consulte los detalles del producto también en la página web profesional de Flos, en su ficha técnica y en las instrucciones de instalación y montaje a fin de conocer en detalle toda la información que pueda no estar recogida en este catálogo y ser relevante para su proyecto o instalación concreta.


Cumplimiento de Normativa y Marcas de Calidad
Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

TheBlockofLight

Power LED 2,2W - 154 lm - 3000K/CRI 80








Semi-recessed signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply and 500 mm power cable included.

Luminaria de señalización semiempotrada para aplicación interior o exterior. Fuente de alimentación no regulable 100-240V, 50-60Hz integrada. Inlcuye cable de alimentación de 500 mm.

☐ 09.3310.01C






Luminous flux luminaire
85 lm

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	15	1.79
2	4	3.58
3	2	5.37
4	1	7.16
5	1	8.95

■ 09.3310.04C






Luminous flux luminaire
40 lm

Beam Angle:		41°
h(m)	E(lx)	D(m)
1	5	1.64
2	1	3.28
3	1	4.92
4	0	6.55
5	0	8.19

■ 09.3310.72C





Luminous flux luminaire
50 lm

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	6	1.85
2	2	3.70
3	1	5.55
4	0	7.40
5	0	9.25

Accessories / Accesorios

Can for embedding in concrete.

Can para empotrar en hormigón.




08.8423.00


Three Phase Track
GLOBAL TRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL TRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments.

Carril Trifásico
GLOBAL TRACK ofrece ventajas para instalaciones avanzadas: los conectores principales son alimentables y el cable de alimentación puede ocultarse debajo de los elegantes accesorios de suspensión. Los carriles de iluminación GLOBAL TRACK están diseñados para facilitar su colocación superficial en paredes y techos, o empotrados en falsos techos. Los carriles pueden suspenderse a la altura deseada.
Otras ventajas del sistema trifásico son su alta capacidad de carga y la posibilidad de formar grupos lumínicos independientes en cada uno de los tres circuitos. Esto permite la iluminación de los entornos más exigentes.

Surface








1000 mm
- 60.3101.11
- 60.3101.29
- 60.3101.14


Dali Version
- 60.3101.11ADA
- 60.3101.29ADA
- 60.3101.14ADA


2000 mm
- 60.3102.11
- 60.3102.29
- 60.3102.14

Dali Version
- 60.3102.11ADA
- 60.3102.29ADA
- 60.3102.14ADA

Surface Dali








3000 mm
- 60.3103.11
- 60.3103.29
- 60.3103.14


Dali Version
- 60.3103.11ADA
- 60.3103.29ADA
- 60.3103.14ADA


4000 mm
- 60.3104.11
- 60.3104.29
- 60.3104.14


Dali Version
- 60.3104.11ADA
- 60.3104.29ADA



Recessed








1000 mm
- 60.3810.11
- 60.3810.29
- 60.3810.14


Dali Version
- 60.3810.11ADA
- 60.3810.29ADA
- 60.3810.14ADA


2000 mm
- 60.3820.11
- 60.3820.29
- 60.3820.14

Dali Version
- 60.3820.11ADA
- 60.3820.29ADA
- 60.3820.14ADA

Recessed Dali








3000 mm
- 60.3830.11
- 60.3830.29
- 60.3830.14

Dali Version
- 60.3830.11ADA
- 60.3830.29ADA
- 60.3830.14ADA



Rigid rod to avoid the profile from tilting (rectilinear structures without corners) or to be installed in places where a more rigid fixing system is required.
Varillas rígidas para evitar la inclinación del perfil (estructuras rectilíneas sin esquinas) o para instalaciones donde se requiere sistema de fijación más rígido.

Suspension rod with 1000mm rose. m6 thread.

Varilla de suspensión con rosetón 1000 mm con fileteado m6.



- 60.3014.11
- 60.3014.14

1000 mm suspension rod extension set m6 thread.

Extensión para varilla de suspensión 1000 mm con fileteado m6.

- 60.3097.11**
- 60.3097.14**

Attachment on track for steel cable suspension with M6 thread end

Fijación a carril para cable de acero con terminal roscado M6.



- 60.3008.11
- 60.3008.14

Ceiling fitting with rose.

Conexión de techo con rosetón.



- 60.3094.11
- 60.3094.14

Attachment on track for rod suspension M6 thread.

Fijación a carril para suspensión con varilla con fileteado M6.



- 60.3018.11
- 60.3018.14

** A steel cable is recommended if the structure, because of its dimensions, is stable and includes one or more angles, since in these structures the track does not tilt even if the weight of the luminaries is not balanced.

** Cable de acero recomendado si la estructura por sus dimensiones está equilibraba, es estable e incluye una o más esquinas, ya que en estas estructuras el carril no se inclina, aunque no se equilibre el peso de las luminarias.

Lead-weighted wire without rose and ceiling fitting.

Cable de suspensión con plomo sin rosetón a techo.



1500 mm
- 60.3095.29

3000 mm
- 60.3096.29

Bracket for track fixing wall/ceiling or suspension with lead-weighted wire.

Fijación a techo/pared o para cable de suspensión con plomo.



- 60.3025.11
- 60.3025.14
- 60.3025.29

Bracket for fixing track to wall or ceiling.

Fijación del carril a techo/pared lateral.



- 60.3093.29

Attachment on track for wire suspension.

Fijación a carril para suspensión con cable.



- 60.3057.11
- 60.3057.29

Complete wall support 70mm.

Soporte a pared completo con brazo 70mm.



- 60.3083.29

Track cover strip L 2000mm.

Cubre conductores 2000mm.



- 60.3090.11A
- 60.3090.14A

Power supply rose cover.

Rosetón cubre alimentación.



- 60.3092.11

Cover for power supply connectors recessed track.

Tapa para conexión de alimentación en los carriles empotrables.



- 60.3053.11
- 60.3053.14

Dali Version
- 60.3145.11
- 60.3145.14

Cover for connectors.

Tapa para las conexiones.



- 60.3091.11
- 60.3091.14

Dali Version
- 60.3146.11
- 60.3146.14

---

* Live end right.

Conector alimentación derecha.



- 60.3038.11
- 60.3038.14
- 60.3038.12

Dali Version
- 60.3038.11ADA
- 60.3038.14ADA
- 60.3038.12ADA

---

* Live end left.

Conector alimentación izquierda.



- 60.3039.11
- 60.3039.14
- 60.3039.12

Dali Version
- 60.3039.11ADA
- 60.3039.14ADA
- 60.3039.12ADA

---

* Feeding possible / Posibles puntos de alimentación.

Straght connector.

Conector lineal.



60.3044.11
60.3044.14
60.3044.12
Dali Version
60.3044.11ADA
60.3044.14ADA
60.3044.12ADA

---

* Mean connector.

Conector alimentación central.



60.3043.11
60.3043.14
60.3043.29
Dali Version
60.3043.11ADA
60.3043.14ADA
60.3043.29ADA

---

* Connector 90°.

Conector 90°.



Inside/Interior
60.3029.11
60.3029.14
60.3029.29
Dali Version
60.3029.11ADA
60.3029.14ADA
60.3029.29ADA

Outside/Exterior
60.3028.11
60.3028.14
60.3028.29
Dali Version
60.3028.11ADA
60.3028.14ADA
60.3028.29ADA

---

* Connector T - inside.

Conexión en T - interior.



Right/Derecha
60.3047.11
60.3047.14
60.3047.29
Dali Version
60.3047.11ADA
60.3047.14ADA
60.3047.29ADA

Left/Izquierda
60.3048.11
60.3048.14
60.3048.29
Dali Version
60.3048.11ADA
60.3048.14ADA
60.3048.29ADA

---

* Conector T - outside.

Conexión en T - exterior.



Right/Derecha
60.3049.11
60.3049.14
60.3049.29
Left/Izquierda
60.3049.11ADA
60.3049.14ADA
60.3049.29ADA

Dali Version
60.3051.11
60.3051.14
60.3051.29
Dali Version
60.3051.11ADA
60.3051.14ADA
60.3051.29ADA

---

* Cross coupling.

Conexión en cruz.



60.3036.11
60.3036.14
60.3036.29
Dali Version
60.3036.11ADA
60.3036.14ADA
60.3036.29ADA

Blind end.

Terminal de cierre.



60.3016.11
60.3016.14
60.3016.12

DALI flexible couple.

Conexión flexible DALI.



60.3037.11
60.3037.14
60.3037.29
Dali Version
60.3037.11ADA
60.3037.14ADA
60.3037.29ADA

Corner adjustable connector.

Conexión articulada.



60.3046.11
60.3046.14
60.3046.29

Recessed box for fix-point.

Base empotrable para proyector.



60.3022.11
60.3022.14

Fix-point.

Base de superficie para proyector.



60.3023.11
60.3023.14
60.3023.29

Lead bending key.

Llave para la manipulación de los conductores.




60.3054


---

* Feeding possible / Posibles puntos de alimentación.


Installation Instructions for the Three-Phase Tracks / Instrucciones para la Instalación de los Carriles Trifásicos (3P+N+PE) Un 400v, In 16A. 50Hz, Clase I, IP 20




The position of the neutral lead is shown by the thick line.
La posición lateral del conductor neutro viene indicada por una línea larga.




*Can be used as a power supply point / Puede ser usado como punto de alimentación



The position of the neutral lead is shown by the thick line.
La posición del conductor neutro viene indicada por una línea larga.




Mounting in a groove in the ceiling
Montaje en ranura en el techo



- tracks can be fixed through the flanges (A) or through the track bottom (B).
- manner A: with screws Ø 3,0 - 4,5, at distance of 500mm.
- manner B: with flat head screws Ø 3,0, supporting distance 1000mm-max. load 20 kg/m.

- los carriles se pueden fijar a través de las bridas (A) o a través de la parte inferior del carril (B).
- opción A: con tornillos Ø 3,0 - 4,5, a una distancia de 500 mm.
- opción B: con tornillos de cabeza plana Ø 3,0, distancia de apoyo 1000 mm-máx. carga 20 kg / m.


Mounting in suspended ceilings
Montaje en techos suspendidos




- with clamps 60.3025.XX.
- the ceiling plate structure must be easy to demount, the plates and the tracks are not fixed onto each others.
- hanging at max. 1000mm distance.
- plate load max. 1,2 kg/m per track flange.
- track hanging load max. 10 kg / hanging distance.

- con abrazaderas 60.3025.XX.
- la estructura de la placa del techo debe ser fácil de desmontar, las placas y los carriles no se fijan entre ellos.
- suspensión como máximo a 1000 mm de distancia.
- carga máx. de la placa 1,2 kg / m por brida en el carril.
- carga máx. de suspensión del carril 10 kg / distancia de suspensión.


Cutting Track / Corte de los Carriles a Medida



1 . Cutting the track
1 . Corte del carril




2 . Positioning bending key in the track
2 . Posicione la llave de manipulación del carril



3 . Lead bending
3 . Pliegue de los conductores




4 . Bent leads
4 . Conductores plegados




5 . Bent leads control
5 . Control del pliegue de los conductores


Connector Installation / Instalación de las Conexiones



1 . Guide flap
1 . Lengüeta de guía




2 . Canal
2 . Guía




3 . Pressure fixing
3 . Fijación a presión


Fixing the Track and Load Capacity / Fijación del Carril y Capacidad de Carga




Fastening Distance and Loading Capacity
Recommended fastening distance L=1000mm.
The tracks have fastening holes.

Distancia de Anclaje y Capacidad
La distancia de anclaje recomendada es L=1000mm.
Los carriles van equipados con agujeros de anclaje.








L mm	a mm	b mm	c mm	d mm
1000	250			
2000	250	1000		
3000	250		1000	1000
4000	250		1500	1000


Planning Information
When you install the track, you have to choose on which side you wish to have the ridge. The ridge will tell you which accessories to use with. Have a look at the following figures where the dotted line indicates the ridge on the track.
If you have only one track, you can choose on which side you connect it and use the corresponding parts.
Figure 1. Track of length 1 mt. with end feed (A) and its mirror image (B).
Figure 2. Shows two different cases. You will notice that the ridge can be either inside or outside the installation system. You can use respectively either (C) & (D) or (E) & (F).
If the ridge is outside, first case, you have to use the T connector (C) with its miror image (D). The L connectors are then the same for each corner, (H). Inversely, if you have the ridge inside, second case, you will have to use the T connector (E) with its miror image (F). The corresponding L connector is in this case (I).


Notas para el Proyecto
La posición lateral del conductor de tierra hace la estructura de los carriles asimétrica, por lo que los accesorios de conexión deberán ser los correspondientes para cada caso. En las figuras que se presentan a continuación, la línea punteada indica la posición del conductor de tierra.
Figura 1. Carril con toma de alimentación (A) y toma de alimentación (B).
Figura 2. Si el conductor de tierra es exterior - primer caso – deben de usarse las conexiones, en T, (C) con las conexiones (D) correspondientes. Las conexiones en L deberán de ser las mismas para cada esquina, (H). Si, en cambio, el conductor de tierra es interior – segundo caso – deberán de utilizarse las conexiones, en T, (I), con las conexiones (F) correspondientes. Las conexiones en L en este caso serán los (I).

1.




2.


















Example / Ejemplo











Constant Current Power Supply for LED / Fuente de Alimentación de Corriente Constante para LED

Non dimmable continuous current power supply. 110/240V.	Fuente de alimentación de corriente constante no regulable. 110/240V.			17W / 700 mA *60.8655 20W / 500 mA *60.8650 22W / 1050 mA *60.8670 *110V – 12W
Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA - 15W / 400mA - 17W / 450mA - 19W / 500mA - 22W / 550mA - 24W / 600mA - 26W / 650mA - 28W / 700mA - 30W.	Fuente de alimentación de corriente constante 15-30W, 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350mA - 15W / 400mA - 17W / 450mA - 19W / 500mA - 22W / 550mA - 24W / 600mA - 26W / 650mA - 28W / 700mA - 30W no regulable.			60.9592
Non dimmable continuous current power supply of 25W, 110/240V - 50/60Hz with power current selected through adjustable 350mA - 12W / 500mA - 15W /700 mA - 25W switch.	Fuente de alimentación de corriente constante 25W, 110/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350mA - 12W / 500mA - 15W /700 mA - 25W no regulable.			60.8437 110V – max 18W
Non dimmable continuous current power supply of 110/240V 32W, with power current selected through adjustable 350 mA-17W /500 mA-24W /700 mA-32W /900 mA - 32W. switch.	Fuente de alimentación de corriente constante 110*/240V 32W, con corriente de alimentación seleccionable mediante switch 350 mA-17W /500 mA-24W /700 mA-32W /900 mA - 32W no regulable.			60.9233 110V – max 15W
Non dimmable continuous current power supply of 15-20W, 110/240V - 50/60Hz, with power current selected through adjustable 350 mA-15W /500 mA/ /550 / 700 / 850 mA / 900 mA - 20W switch.	Fuente de alimentación de corriente constante 15-20W, 110/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350 mA-15W /500 mA/ /550 / 700 / 850 mA / 900 mA - 20W no regulable.			60.8911 110V – max 15W
Continuous current power supply of 25W, 110/240V - 50/60Hz with power current selected through adjustable 350 mA-18W / 400 mA - 21W / 500mA - 25W /600mA - 30W /700/750/900 mA - 32W switch. 1-10V or push dimming, synchronisation cables not included.	Fuente de alimentación de corriente constante 25W, 110/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350 mA-18W / 400 mA - 21W / 500mA - 25W /600mA - 30W /700/750/900 mA - 32W regulable. 1-10V o push dimming, requiere cables de sincronización no incluidos.			60.8533 110V – max 15W
Continuous current power supply of 25-50W, 110/240V - 50/60Hz with power current selected through adjustable 350mA - 25W /500mA - 35W/ 700mA - 50W /750mA - 54W /900/ 1050 mA - 60W switch. Dali 2, 0/1-10V or push dimming, synchronisation cables not included.	Fuente de alimentación de corriente constante 25-50W, 110/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350mA - 25W /500mA - 35W/ 700mA - 50W /750mA - 54W /900/ 1050 mA - 60W regulable. Dali 2, 0/1-10V o push dimming, requiere cables de sincronización no incluidos.			60.8530 110V – max 40W








Constant Current Power Supply for LED / Fuente de Alimentación de Corriente Constante para LED

Continuous current power supply of 13-20W, 110/240V - 50/60Hz with power current selected through adjustable 300 mA - 15W / 350 mA - 18W / 400/450/500/550/600/650/700/750/800/850/900 mA.	Fuente de alimentación de corriente constante 13-20W, 110/240V -50/60Hz con corriente de alimentación seleccionable mediante switch 300 mA - 15W / 350 mA - 18W / 400/450/500/550/600/650/700/750/800/850/900 mA.			60.9188 110V – max 15W
Continuous current power supply of12-20W, 110/240V - 50/60Hz with-power current selected through adjustable 250mA -12W / 350mA - 17W / 400mA - 19W / 450 / 500 / 550 / 600 / 700mA - 20W dimmable Dali 1 and Dali 2.	Fuente de alimentación de corriente constante 12-20W, 110/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 250mA -12W / 350mA - 17W / 400mA - 19W / 450 /500 / 550 / 600 / 700mA - 20W regulable Dali 1 y Dali 2.			60.9222 110V – max 15W
Continuous current power supply of 10-20W, 110/240V - 50/60Hz with power current selected through adjustable 250 mA - 12W /350 mA - 17W /400 mA - 19W /450/500/550/600/700 mA - 20W, Dali 2 switch. Max 15W.	Fuente de alimentación de corriente constante 10-20W, 110/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 250 mA - 12W /350 mA - 17W /400 mA - 19W /450/500/550/600/700 mA - 20W regulable Dali 2. Max 15W.			60.9746 110V – max 15W
Continuous current power supply of 13-20W, 110/240V - 50/60Hz with power current selected through adjustable 250 mA - 13W / 350 mA - 18W /400/450/500/550/600/700/800/900 mA - 20W, 1-10V or push dimming.	Fuente de alimentación de corriente constante 13-20W, 110/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 250 mA - 13W / 350 mA - 18W /400/450/500/550/600/700/800/900 mA - 20W, regulable 1-10V o push.			60.9208 110V – max 15W
Continuous current power supply of 20-40W, 110/240V - 50/60Hz with power current selected through adjustable 350 mA -18,5W / 400 mA - 21W / 500 mA - 26,5W / 600 mA - 31,5W /650 mA -34,5W /700 mA -37W /750 mA - 39,5W /800/850/900/950/1000/1050/1200 mA - 40W switch. Dali 2, 0/1-10V or push dimming, synchronisation cables not included. In the case of push control the following sync cable must be used: 60.1665.	Fuente de alimentación de corriente constante 20-40W, 110/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350 mA - 18,5W /400 mA - 21W / 500 mA - 26,5W / 600 mA - 31,5W /650 mA -34,5W /700 mA -37W /750 mA - 39,5W /800/850/900/950/1000/1050/1200 mA - 40W regulable. Dali 2, 0/1-10V o push dimming, requiere cables de sincronización no incluidos. En caso de regulación push es necesario emplear el siguiente cable de sincronismo: 60.1665.			60.9276
Non dimmable continuous current power supply of 220/240V - 50/60Hz with power current selected through adjustable with switch. 300mA - 14.4W / 350mA - 16.8W / 400mA - 19.2W / 450mA - 21.6W / 500mA - 24W / 550mA - 26.4W / 600mA - 31.2W / 650mA - 31.2W / 700mA - 33.6W / 750mA - 36W / 800mA - 38.4W / 850mA - 35.7W / 900mA - 37.8W / 950mA - 39.9W / 1000mA - 42W / 1050mA - 42W.	Fuente de alimentación no regulable de corriente constante 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch. 300mA - 14.4W / 350mA - 16.8W / 400mA - 19.2W / 450mA - 21.6W / 500mA - 24W / 550mA - 26.4W / 600mA - 31.2W / 650mA - 31.2W / 700mA - 33.6W / 750mA - 36W / 800mA - 38.4W / 850mA - 35.7W / 900mA - 37.8W / 950mA - 39.9W / 1000mA - 42W / 1050mA - 42W.			60.7677

Constant Current Power Supply for LED / Fuente de Alimentación de Corriente Constante para LED

Continuous current power supply of 6W, 100V / 14W, 240V - 50/60Hz with 500 mA supply voltage.	Fuente de alimentación de corriente constante 6W, 100V / 14W, 240V - 50/60Hz con corriente de alimentación 500 mA.			60.8880
Continuous current power supply of 7,2-24W, 220/240V - 50/60Hz with power current selected through adjustable 150 mA - 7,2W /200 mA - 9,5W /250 mA - 12W /300 mA -14,5W /350 mA -17W/400 mA - 19,5W /450 mA -21,5W /500 mA - 24W switch. Mains or push dimming. In the case of push control the following sync cable must be used: 60.1665.	Fuente de alimentación de corriente constante 7,2-24W, 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 150 mA - 7,2W /200 mA - 9,5W /250 mA - 12W /300 mA -14,5W /350 mA -17W/400 mA - 19,5W /450 mA -21,5W /500 mA - 24W regulable. Mains o push dimming. En caso de regulación push es necesario emplear el siguiente cable de sincronismo: 60.1665.			60.9421
Continuous current power supply of 10W, 110V / 12W, 240V - 50/60Hz with 700 mA supply voltage.	Fuente de alimentación de corriente constante 10W, 110V / 12W, 240V - 50/60Hz con corriente de alimentación 700 mA.			60.8529A
Continuous current power supply of 32W, 230/240V - 50/60Hz with power current selected through adjustable 350mA - 17W / 500mA - 24W / 700/ 750 mA - 32W switch by trailing and leading edge dimming (mains dimming), or push dimming.	Fuente de alimentación de corriente constante 32W, 230/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350mA - 17W / 500mA - 24W / 700/ 750 mA - 32W regulable mediante trailing and leading edge dimming (mains dimming), o push dimming.			60.8534
Electronic transformer with constant voltage (24V) for LED. 8W, 220/240V, 50/60Hz.	Transformador electrónico de tensión constante (24V) para LED. 8W, 220/240V, 50/60Hz.			60.8079
Electronic transformer with constant voltage (24V) for LED. 8W, 110/240V, 50/60Hz.	Transformador electrónico de tensión constante (24V) para LED. 8W, 110/240V, 50/60Hz.			60.9157
Constant voltage supply source of 10W, 100-240V - 50/60Hz with non adjustable 250 mA supply voltage.	Fuente de alimentación de corriente constante 10W, 100-240V - 50/60Hz con corriente de alimentación 250 mA no regulable.			60.9744
Constant voltage supply source of 20W, 220-240V - 50/60Hz with adjustable 250 mA supply voltage.	Fuente de alimentación de corriente constante 20W, 220-240V - 50/60Hz con corriente de alimentación 250 mA regulable.			0-10V 60.9405 Dali 60.9601

Constant Current Power Supply for LED / Fuente de Alimentación de Corriente Constante para LED


Non dimmable continuous current power supply of 220/240V - 50/60Hz with power current selected through adjustable with switch 200 mA - 8,5W / 300 mA - 13W / 350 mA - 15W / 400 mA - 17,5W / 450 mA - 19,5W / 500 mA - 22W.	Fuente de alimentación no regulable, de corriente constante 200/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 200 mA - 8,5W / 300 mA - 13W / 350 mA - 15W / 400 mA - 17,5W / 450 mA - 19,5W / 500 mA - 22W.			60.9160
Continuous current power supply, 0-10V dimmable, 220/240V - 50/60Hz, 200mA - 20W.	Fuente de alimentación de corriente constante, regulable 0-10V, 220/240V - 50/60Hz, 200mA - 20W.			60.9483
Continuous current power supply, dimmable Dali 2, 220/240V - 50/60Hz, 200mA - 20W.	Fuente de alimentación de corriente constante, regulable Dali 2, 220/240V - 50/60Hz, 200mA - 20W.			60.9604
Continuous current power supply, 0/1-10V dimmable, 220/240V - 50/60Hz, 300 mA - 16W / 350 mA - 18W / 400 mA - 21W / 500 mA - 27W / 600 mA - 32W / 650 mA - 35W /700/750/800/900/1000/1050 mA - 36W.	Fuente de alimentación de corriente constante, regulable 0/1-10V, 220/240V - 50/60Hz, 300 mA - 16W / 350 mA - 18W / 400 mA - 21W / 500 mA - 27W / 600 mA - 32W / 650 mA - 35W /700/750/800/900/1000/1050 mA - 36W.			60.9439
Continuous current power supply of 220/240V - 50/60Hz with power current selected through adjustable switch. Dali 1, Dali 2, Push dimming. 150mA - 7.8W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.6W / 350mA - 18.2W / 400mA - 20.8W / 500mA - 26W / 600mA - 31.2W / 700mA - 36.4W / 750mA - 39W / 800mA - 41.6W / 850mA - 41.6W / 900mA - 41.4W / 950mA - 41.8W / 1000mA - 42W / 1050mA - 42W.	Fuente de alimentación de corriente constante 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch. Regulable Dali 1, Dali 2, Push. 150mA - 7.8W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.6W / 350mA - 18.2W / 400mA - 20.8W / 500mA - 26W / 600mA - 31.2W / 700mA - 36.4W / 750mA - 39W / 800mA - 41.6W / 850mA - 41.6W / 900mA - 41.4W / 950mA - 41.8W / 1000mA - 42W / 1050mA - 42W.			60.7678
Continuous current power supply of 220/240V - 50/60Hz with power current selected through adjustable switch. Dali 1, Dali 2, Push dimming. 150mA - 7.8W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.6W / 350mA - 18.2W / 400mA - 20.8W / 450mA - 23.4W / 500mA - 26W / 550mA - 26.1W / 600mA - 26.1W / 650mA - 26W / 700mA - 26.3W.	Fuente de alimentación regulable de corriente constante 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch. Regulable Dali 1, Dali 2, Push. 150mA - 7.8W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.6W / 350mA - 18.2W / 400mA - 20.8W / 450mA - 23.4W / 500mA - 26W / 550mA - 26.1W / 600mA - 26.1W / 650mA - 26W / 700mA - 26.3W.			60.7709
Continuous current power supply, dimmable Casambi, 220/240V - 50/60Hz, 300mA - 16W / 350mA - 18,5W / 400mA - 21,5W / 450 mA - 24W / 500mA - 27W / 600mA - 32W / 650 mA - 35W / 700 mA - 36W /750/800/900/1000/1050/1200 mA - 38W.	Fuente de alimentación de corriente constante, regulable Casambi, 220/240V - 50/60Hz, 300mA - 16W / 350mA - 18,5W / 400mA - 21,5W / 450 mA - 24W / 500mA - 27W / 600mA - 32W / 650 mA - 35W / 700 mA - 36W /750/800/900/1000/1050/1200 mA - 38W.			60.9207

Constant Current Power Supply for LED / Fuente de Alimentación de Corriente Constante para LED

20W Constant current power supply, AC phase-cut adjustable, trailing and leading edge dimming (mains dimming), 220/240V - 50/60Hz, with dip-switch programmable power supply current.
Output current: 900mA - 20W / 850mA - 20W / 800mA - 20W / 750mA - 20W / 700mA - 20W / 650mA - 20W / 600mA - 20W / 550mA - 20W / 500mA - 20W / 450mA - 20W / 400mA - 19W / 350mA - 17W / 300mA - 14W / 250mA - 12W

Fuente de alimentación de corriente constante 20W, regulable mediante corte de fase en AC, trailing & leading edge dimming (mains dimming), 220/240V - 50/60Hz, con corriente de alimentación programable mediante dip-switch.
Corriente de salida: 900mA - 20W / 850mA - 20W / 800mA - 20W / 750mA - 20W / 700mA - 20W / 650mA - 20W / 600mA - 20W / 550mA - 20W / 500mA - 20W / 450mA - 20W / 400mA - 19W / 350mA - 17W / 300mA - 14W / 250mA - 12W






60.9467

Continuous current power supply 20W, 220/240V - 50/60Hz with power current selected through adjustable NFC. Non Dimmable.
Output current (Ta>45ºC).

Fuente de alimentación de corriente constante 20W, 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante NFC. No regulable.
Corriente de salida (Ta>45ºC).






500mA
60.9834.0500
600mA
60.9834.0600
700mA
60.9834.0700
800mA
60.9834.0800
900mA
60.9834.0900
1050mA
60.9834.1050

Constant current supply source of 3W, 220-240V - 50/60Hz with non adjustable 700 mA supply voltage.

Fuente de alimentación de corriente constante 3W, 220-240V - 50/60Hz con corriente de alimentación 700 mA no regulable.






60.9988

Constant current power supply with programmable power supply current via NFC. Pre-set: 900mA, 36W, 220/240 V - 50/60 Hz. Non Dimmable.

Fuente de alimentación de corriente constante con corriente de alimentación programable mediante NFC. Pre-seteada: 900mA, 36W, 220/240V - 50/60Hz. No regulable.






60.9958

Constant current supply source of 900mA, 20W, 220-240V - 50/60Hz. Dimmable by Casambi.

Fuente de alimentación de corriente constante 900mA, 20W, 220-240V - 50/60Hz. Regulable por Casambi.






06.1974.00

20 W, 220/240 V - 50/60 Hz constant current power supply with programmable power supply current via NFC. Dimmable by Dali2.







Fuente de alimentación de corriente constante 20W, 220/240V - 50/60Hz con corriente de alimentación programable mediante NFC. Regulable por Dali2.













200mA - 8.8W
60.9713.0200
300mA - 13.2W
60.9713.0300
400mA - 17.6W
60.9713.0400
500mA - 20W
60.9713.0500
600mA - 20W
60.9713.0600
700mA - 20W
60.9713.0700
800mA - 20W
60.9713.0800
900mA - 20W
60.9713.0900
1050mA - 20W
60.9713.1050







Constant Current Power Supply for LED / Fuente de Alimentación de Corriente Constante para LED

Continuous current power supply 20W, 220/240V - 50/60Hz with power current selected through adjustable switch. Dimmable 0-10V/ PWM/RX. Output current: 500mA - 21W / 450mA - 19W / 400mA - 17W / 350mA - 15W / 300mA - 12W / 250mA - 10W.	Fuente de alimentación de corriente constante 20W, 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch. Regulable por 0-10V/PWM/Rx. Corriente de salida: 500mA - 21W / 450mA - 19W / 400mA - 17W / 350mA - 15W / 300mA - 12W / 250mA - 10W.			60.9843
Continuous current power supply 40W, 220/240V - 50/60Hz with power current selected through adjustable switch. Dimmable 0-10V/ PWM/RX. Output current: 1050mA - 40W / 1000mA - 40W / 950mA - 40W / 900mA - 37W / 850mA - 35W / 800mA - 33W / 750mA - 31W / 700mA - 29W / 650mA - 29W / 600mA - 25W / 550mA - 23W.	Fuente de alimentación de corriente constante 40W, 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch. Regulable por 0-10V/PWM/Rx. Corriente de salida: 1050mA - 40W / 1000mA - 40W / 950mA - 40W / 900mA - 37W / 850mA - 35W / 800mA - 33W / 750mA - 31W / 700mA - 29W / 650mA - 29W / 600mA - 25W / 550mA - 23W.			60.9845
Continuous current power supply 31W, 100/277V - 50/60Hz with power current selected through adjustable switch. Non Dimmable. Output current: 1050mA - 30/38W (100-110V / 120-277V) / 1000mA - 30/38W (100-110V / 120-277V) / 950mA - 30/38W (100-110V / 120-277V) / 900mA - 30/38W (100-110V / 120-277V) / 850mA - 30/35W (100-110V / 120-277V) / 800mA - 30/33W (100-110V / 120-277V) / 750mA - 30/32W (100-110V / 120-277V) / 700mA - 30/31W (100-110V / 120-277V) / 650mA - 29W / 600mA - 27W / 550mA - 24W / 500mA - 22W / 450mA - 20W / 400mA - 18W / 350mA - 15W / 300mA - 13W.	Fuente de alimentación de corriente constante 31W, 100/277V - 50/60Hz con corriente de alimentación seleccionable mediante switch. No regulable. Corriente de salida: 1050mA - 30/38W (100-110V / 120-277V) / 1000mA - 30/38W (100-110V / 120-277V) / 950mA - 30/38W (100-110V / 120-277V) / 900mA - 30/38W (100-110V / 120-277V) / 850mA - 30/35W (100-110V / 120-277V) / 800mA - 30/33W (100-110V / 120-277V) / 750mA - 30/32W (100-110V / 120-277V) / 700mA - 30/31W (100-110V / 120-277V) / 650mA - 29W / 600mA - 27W / 550mA - 24W / 500mA - 22W / 450mA - 20W / 400mA - 18W / 350mA - 15W / 300mA - 13W.			60.9387
Non dimmable continuous current power supply of 20W, dimmable 0-10V, 220/240V - 50/60Hz with power current 900 mA.	Fuente de alimentación de corriente constante 20W, regulable 0-10V, 220/240V - 50/60Hz con corriente de alimentación 900 mA.			60.9414
Continuous current power supply of 20W, dimmable DALI 2, 220/240V - 50/60Hz with power current 900 mA.	Fuente de alimentación de corriente constante 20W, regulable DALI 2, 220/240V - 50/60Hz con corriente de alimentación 900 mA.			60.9602
30W, 220-240V - 50/60Hz Constant current power supply, with dip-switch programmable power supply current. Output current: 900mA - 29.7W / 850mA - 29.7W / 800mA - 30.4W / 750mA - 30W / 700mA - 29.4W / 650mA - 27.3W / 600mA - 25.2W / 550mA - 23.1W	Fuente de alimentación de corriente constante 30W, 220-240V - 50/60Hz con corriente de alimentación programable mediante dip-switch. Corriente de salida: 900mA - 29.7W / 850mA - 29.7W / 800mA - 30.4W / 750mA - 30W / 700mA - 29.4W / 650mA - 27.3W / 600mA - 25.2W / 550mA - 23.1W			60.9692

Constant Current Power Supply for LED / Fuente de Alimentación de Corriente Constante para LED

Continuous current power supply of 1-32W, 110*/240V - 50/60Hz with power current selected through adjustable 250 mA - 12W / 300 mA - 14W / 350 mA - 17W / 400 mA - 19W / 450 mA - 22W / 500 mA - 24W / 550 mA - 26W / 600 mA - 28W / 650 mA - 31W / 700 mA - 32W, Dali 2 switch. *110V = Max. 15W	Fuente de alimentación de corriente constante 1-32W, 110*/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 250 mA - 12W / 300 mA - 14W / 350 mA - 17W / 400 mA - 19W / 450 mA - 22W / 500 mA - 24W / 550 mA - 26W / 600 mA - 28W / 650 mA - 31W / 700 mA - 32W, regulable Dali 2. *Max 15W			60.8711A
Non dimmable continuous current power supply of 220/240V - 50/60Hz with power current selected through adjustable with switch 350mA - 7.35W / 400mA - 8.4W / 450mA - 9.45W / 500mA - 10.5W	Fuente de alimentación no regulable, de corriente constante 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350mA - 7.35W / 400mA - 8.4W / 450mA - 9.45W / 500mA - 10.5W			60.9768
Continuous current power supply of 100/240V - 50/60Hz with power current selected through adjustable 350mA - 15W / 500mA - 21W / 600mA - 26W / 700mA - 30W switch. Dali 1, Dali 2 dimming	Fuente de alimentación de corriente constante 100/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch 350mA - 15W / 500mA - 21W / 600mA - 26W / 700mA - 30W regulable Dali 1, Dali 2			60.9826
10W Constant current power supply, AC phase-cut adjustable, trailing and leading edge dimming (mains dimming), 220/240V - 50/60Hz, with 700mA power supply current.	Fuente de alimentación de corriente constante 10W, regulable mediante corte de fase en AC, trailing & leading edge dimming (mains dimming), 220/240V - 50/60Hz, con corriente de alimentación 700mA.			60.9379
12W Constant current power supply, AC phase-cut adjustable, trailing and leading edge dimming (mains dimming), 220/240V - 50/60Hz, with 250mA power supply current.	Fuente de alimentación de corriente constante 12W, regulable mediante corte de fase en AC, trailing & leading edge dimming (mains dimming), 220/240V - 50/60Hz, con corriente de alimentación 250mA.			60.9408
Continuous current power supply of 220/240V - 50/60Hz with power current selected through adjustable switch. 200mA - 8W / 250mA - 10W / 300mA - 12W / 350mA - 14W regulable trailing & leading edge dimming (mains dimming).	Fuente de alimentación de corriente constante 220/240V - 50/60Hz con corriente de alimentación seleccionable mediante switch. 200mA - 8W / 250mA - 10W / 300mA - 12W / 350mA - 14W regulable mediante trailing & leading edge dimming (mains dimming).			60.9949
Constant current power supply 28W, 220-240V - 50/60Hz with programmable output current via DIP switch. 100mA - 5.4W / 150mA - 7.9W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.5W / 350mA - 18W / 400mA - 20.4W / 450mA - 23W / 500mA - 25.8W / 550mA - 28.4W / 600mA - 31W / 650mA - 31.4W / 700mA - 31.8W / 750mA - 31.5W / 800mA - 31.8W. Non-dimmable.	Fuente de alimentación de corriente constante 28W, 220-240V - 50/60Hz con corriente de alimentación programable mediante DIP switch. 100mA - 5.4W / 150mA - 7.9W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.5W / 350mA - 18W / 400mA - 20.4W / 450mA - 23W / 500mA - 25.8W / 550mA - 28.4W / 600mA - 31W / 650mA - 31.4W / 700mA - 31.8W / 750mA - 31.5W / 800mA - 31.8W. No regulable.			60.7773
Constant current power supply 15W, 220-240V - 50/60Hz with programmable output current via DIP switch. 400mA - 11.6W / 450mA - 13W / 500mA - 14.5W / 550mA - 15.9W. Phase-cut dimmable (Triac).	Fuente de alimentación de corriente constante 15W, 220-240V - 50/60Hz con corriente de alimentación programable mediante DIP switch. 400m - 11.6W / 450mA - 13W / 500mA - 14.5W / 550mA - 15.9W. Regulable corte de fase Triac.			60.7661

Constant Current Power Supply for LED / Fuente de Alimentación de Corriente Constante para LED


Constant current power supply 20W, 220-240V - 50/60Hz with programmable output current via DIP switch. 100mA - 5.8W / 150mA - 8.3W / 200mA - 10.8W / 250mA - 13.2W / 300mA - 15.6W / 350mA - 18.1W / 400mA - 20.6W / 450mA - 23W / 500mA - 22.9W / 550mA - 22.7W / 600mA - 23W / 650mA - 22.6W / 700mA - 23.2W / 750mA - 23W / 800mA - 23.5W. DALI2 - Push Dim dimmable.	Fuente de alimentación de corriente constante 20W, 220-240V - 50/60Hz con corriente de alimentación programable mediante DIP switch. 100mA - 5.8W / 150mA - 8.3W / 200mA - 10.8W / 250mA - 13.2W / 300mA - 15.6W / 350mA - 18.1W / 400mA - 20.6W / 450mA - 23W / 500mA - 22.9W / 550mA - 22.7W / 600mA - 23W / 650mA - 22.6W / 700mA - 23.2W / 750mA - 23W / 800mA - 23.5W. Regulable DALI2 - Push Dim.			60.7774
Constant current power supply 42W, 220–240V - 50/60Hz with programmable output current via DIP switch. CASAMBI dimmable. 150mA – 7.9W / 200mA – 9.8W / 250mA – 12.3W / 300mA – 14.7W / 350mA – 17.2W / 400mA – 19.6W / 500mA – 24.5W / 600mA – 29.4W / 700mA – 34.3W / 750mA – 36.8W / 800mA – 39.2W / 850mA – 41.7W / 900mA – 42W / 950mA – 42W / 1000mA – 42W / 1050mA – 42W	Fuente de alimentación de corriente constante 42W, 220-240V - 50/60Hz con corriente de alimentación programable mediante DIP switch. Regulable CASAMBI. 150mA – 7.9W / 200mA – 9.8W / 250mA – 12.3W / 300mA – 14.7W / 350mA – 17.2W / 400mA – 19.6W / 500mA – 24.5W / 600mA – 29.4W / 700mA – 34.3W / 750mA – 36.8W / 800mA – 39.2W / 850mA – 41.7W / 900mA – 42W / 950mA – 42W / 1000mA – 42W / 1050mA – 42W			60.7785
Constant current power supply 3W, 220-240V - 50/60Hz fixed supply current. Non-dimmable. Output current: 2.25W - 500mA.	Fuente de alimentación de corriente constante 3W, 220-240V - 50/60Hz corriente de alimentación fija. No regulable. Corriente de salida: 2.25W - 500mA.			60.7887
Driver Multic. 36W 220-240V CC 36W150-900 NFC.	Driver Multic. 36W 220-240V CC 36W150-900 NFC.			300mA 60.9954.0300 500mA 60.9954.0500
Driver Casambi 15W 220-240V 150-1050mA 10-54V.	Driver Casambi 15W 220-240V 150-1050mA 10-54V.			300mA 60.9874.0300 500mA 60.9874.0500
Constant current power supply with programmable power supply current via NFC. 36W, 220/240 V - 50/60 Hz. Dimmable by Dali2.	Fuente de alimentación de corriente constante con corriente de alimentación programable mediante NFC. 36W, 220/240V - 50/60Hz. Regulable por Dali2.			300mA 60.9957.0300 500mA 60.9957.0500 900mA 60.9957

Constant Voltage Power Source for LED / Fuente de Alimentación de Tensión Constante para LED

Electronic transformer with constant voltage (24V) for LED. 100/240V.


Transformador electrónico de tensión constante (24V) para LED. 100/240V.






25W
60.8703





60W
60.9089






120W
60.9407

LED power supply source for remote installation in 24V/240W electric control panel. 100/240V.

Fuente de alimentación LED para instalación remota en cuadro eléctrico 24V/240W. 100/240V.






60.8268

Remote power supply. Dimmable through 0-1/10V protocol. 24V. Dimming range 10-100%. Minimum load 20W

Fuente de alimentación remota. Dimable mediante protocolo 0-1/10V. 24V Rango de regulación 10-100%. Carga mínima 20W.






120W - DIM 0-1/10V
60.9681

Remote power supply. Dimmable through Casambi protoco. 24V. Dimming range 10-100%. Minimum load 20W

Fuente de alimentación remota. Dimable mediante protocolo Casambi. 24V. Rango de regulación 10-100%. Carga mínima 20W






Casambi
120W - 110/240V
60.9683

Remote power supply. Dimmable through DALI protocol. 24V. Dimming range 10-100%. Minimum load 20W

Fuente de alimentación remota. Dimable mediante protocolo DALI2 2. 24V. Rango de regulación 10-100%. Carga mínima 20W






DALI
120W - 110/240V
60.9880

LED power supply source for remote installation in 24V/200W electric control panel.

Fuente de alimentación LED para instalación remota en cuadro eléctrico 24V/200W.






60.9352

Power supply source with constant voltage 24V - 60W, 220-240W-50/60Hz.

Fuente de alimentación de tensión constante 24V - 60W, 220-240W-50/60Hz.






60.9515

Power supply source with constant voltage 24V - 120W, 220-240W-50/60Hz.

Fuente de alimentación de tensión constante 24V - 120W, 220-240W-50/60Hz.









60.9516

DRIVERS / EQUIPOS


Constant Voltage Power Source for LED / Fuente de Alimentación de Tensión Constante para LED

Power supply source with constant voltage 24V - 120W, 220-240W-50/60Hz.	Fuente de alimentación de tensión constante 24V - 120W, 220-240W-50/60Hz.			120W - 220/240V 60.9777A
Power supply source with constant voltage 24V - 60W, 220-240W-50/60Hz.	Fuente de alimentación de tensión constante 24V - 60W, 220-240W-50/60Hz.			60.9705A
Power supply source with constant voltage 24V - 60W, 220-240W-50/60Hz.	Fuente de alimentación de tensión constante 24V - 60W, 220-240W-50/60Hz.			Mains Dimming 60.9881

12V / 24V Electronic Transformer / Transformador Electrónico 12V / 24V

12V electronic transformer. 230/240V, 50-225W. Please check compatibility with Retrofit LED lamps / Compruebe compatibilidad con lámparas LED Retrofit.	Transformador electrónico 12V. 230/240V, 50-225W.			60.8364

12V Conventional Transformer / Transformador Ferromagnético 12V

12V conventional transformer. 230V - 50/60Hz. IP67. Primary wire: 75 cm, secondary wire: 145 cm.	Transformador ferromagnético 12V. 230V - 50/60Hz. IP67. Cable primario: 75 cm, cable secundario: 145 cm.			50W 60.8311

Mains Dimming – Disclaimer

A dimmer compatible with mains dimming (leading/trailing edge) must be used.
Customer needs to check the compatibility between the dimmer used and the Flos luminaire.
Using dimmers that are not suitable for LED lighting can damage the luminaire, the driver and/or the dimmer. Therefore, their use is discouraged and any liability thereof is disclaimed.
The dimming range may vary depending on the model and the number of luminaires installed per dimmer, the driver and the dimmer used.
The maximum power installed per dimmer must not exceed 80% of the nominal power of the dimmer used.

Se debe usar un regulador compatible con regulación tipo mains dimming (leading/trailing edge).
El cliente debe comprobar la compatibilidad entre el regulador usado y la luminaria Flos.
El uso de reguladores no aptos para iluminación LED puede dañar la luminaria, el driver y/o el regulador por lo que se desaconseja su uso y se declina cualquier responsabilidad en su caso.
El rango de regulación puede variar dependiendo del modelo y la cantidad de luminarias instaladas por regulador, del driver y del regulador utilizado.
La potencia máxima instalada por regulador no debe superar el 80% de la potencia nominal del regulador utilizado.

Control
Greater Optical Control

The LED Array module has a high-density light surface that allows the light to be effectively controlled through reflectors. A wide variety of opening angles can be obtained, thereby catering for any application.

Control
Mayor Control Óptico

El módulo de LED Array dispone de una superficie de alta densidad lumínica que permite que, mediante reflectores, se pueda controlar de una forma muy eficaz la luz. Es posible obtener una gran variedad de ángulos de apertura, cubriendo de este modo, cualquier aplicación.

No Pixellation
White Light without Pixellation

Due to its configuration, the LED Array achieves a uniform standard of whites with no change in colour. In addition, during the useful life of the module, an exceptional maintenance of the luminous flow and colour temperature is obtained.

Sin Pixelación
Luz Blanca sin Pixelación

El LED Array, debido a su configuración, consigue un patrón de blancos uniforme sin variación de color. Además durante la vida útil del módulo consigue un excepcional mantenimiento del flujo luminoso y de la temperatura de color.

Cost Reduction
Reduction in Operating Costs

With this LED solution, there is a drastic reduction in maintenance costs due to its long useful life with a minimum luminous flow of 70 %. The energy consumed is reduced by 75 % compared to traditional lighting sources.

Reducción de Costes
Reducción de Costes de Operación

Con esta solución LED, la reducción de los costes de mantenimiento se ve reducida drásticamente debido a su larga vida útil con un flujo luminoso mínimo del 70 %. La energía consumida se reduce hasta en un 75 % comparada con las fuentes de iluminación tradicionales.

Retail Application
Light Source for Retail Application

The luminous flow contains no IR or UV radiation, which cause damage to clothing or the premature spoiling of food. The elimination of heat in the light beam is transformed into a reduction in air conditioning costs.

Aplicación Retail
Fuente de Luz para Aplicación Retail

El flujo luminoso no contiene rayos IR o UV, que son los causantes de los daños en ropa o un deterioro prematuro de los alimentos. La eliminación de calor en el haz luminoso se transforma en una reducción de los costes en aire acondicionado.

Reflectors
Light Performance

The LED module is not a point source. The light is emitted through the LEDS matrix resin area. This construction has an influence when making light calculations and controlling the LED opening angle. As a result, the best way to perform this light control is using reflectors.
These reflectors may be made of metallic thermoplastic material since there is no thermal demand on the light source. As they can be made of thermoplastic, there is greater flexibility in their design and the reflecting surface can be optimised with non-viable forms with traditional aluminium reflectors, with a performance of 90 %.
Opening angles of between approximately 20° and 60° can be obtained.

Reflectores
Rendimiento Luminoso

El módulo de LED Array no es una fuente puntual. La luz es emitida por el área de la resina de la matriz de LEDs. Esta construcción influye a la hora de realizar los cálculos lumínicos y de controlar el ángulo de apertura del LED. Por ello, la forma idónea de realizar este control luminoso es mediante reflectores.
Estos reflectores pueden realizarse en termoplástico metalizado, ya que no hay exigencias térmicas de la fuente luminosa. Al poderse realizar en termoplástico existe mayor flexibilidad en el diseño de los mismos y se puede optimizar la superficie reflectante con formas no viables con los reflectores tradicionales de aluminio, con un rendimiento del 90 %.
Es posible obtener ángulos de apertura desde unos 20° hasta 60° aproximadamente.

Light Beam
Closed Light Beam

Due to the fact that the light comes from a point source, optical control must be carried out using lenses. This optical control allows for the reduction of the light beam to very closed angles. For this reason, this is the most appropriate light source in applications which require a high light density.

Haz de Luz
Haz de Luz Cerrado

Debido a que la fuente de luz es puntual, el control óptico se debe de realizar mediante lentes. Este control óptico permite la reducción del haz de luz hasta ángulos muy cerrados. Por ello, en aplicaciones en que se necesite de una gran densidad de luz es la fuente luminosa más adecuada.

Design
Freedom of Design

The power LEDs are mounted on electronic board. These electronic boards can be designed in many different sizes and shapes, so that the complete light source design (electronic board + LED + Lenses) is extremely flexible and has great freedom. This flexibility makes it different from traditional light sources.

Diseño
Libertad de Diseño

Los power LED se montan en placas electrónicas. Estas placas electrónicas se pueden diseñar en infinidad de dimensiones y formas, de forma que el diseño completo de la fuente luminosa (placa electrónica + LED + Lentes) tiene gran flexibilidad y libertad. Esta flexibilidad lo hace desmarcarse de las fuentes de luz tradicionales.

Colour
Wide Range of Colour Temperatures

The power LEDs are discreet, and can be selected in a wide range of colour temperatures. Bins are established (chromatic spectrum ranges) in which it is guaranteed that the LEDs have a minimum chromatic change with respect to the colour temperature selected.

Color
Amplia Gama de Temperaturas de Color

Los power LED al ser LEDs discretos se pueden seleccionar en una gran variedad de temperaturas de color. Se establecen bins (rangos del espectro cromático) en donde se garantiza que los LEDs disponen de una variación cromática mínima con respecto a la temperatura de color seleccionada.

Light Beam
Diffuse Light

Given their geometry, they are excellent for applications that have no directed light requirements, such as indirect light or luminaires.

Haz De Luz
Luz Difusa

Debido a su geometría son excelentes para aplicaciones en las que no haya requerimientos de luz dirigida, como son la luz indirecta o luminarias con difusor incorporado.

Power Supply
Voltage 24V

Given their compact dimensions and simple power supply, the “Top LED” offer dozens of different solutions for designing a printed circuit. Their easy power supply using constant 12/24V voltage supplies with possible assemblies and connections in parallel, together with the possibility of creating grouped and irregular designs, make them the perfect candidate when a light source far from the conventions set my traditional light sources is necessary.

Alimentación
Tensión 24V

Por sus dimensiones compactas y su sencilla alimentación, los “Top led” ofrecen una multitud de soluciones diferentes a la hora de diseñar un circuito impreso. Su fácil alimentación mediante fuentes de tensión constante a 12/24V, con posibles montajes y conexiones en paralelo, junto con la posibilidad de crear diseño agrupados e irregulares, los hacen candidatos perfectos cuando es necesario el diseño de una fuente de luz lejos de los cánones establecidos por las fuentes de luz tradicionales.

Colour
Wide Range of Colour Temperatures

The “Top LED” like the “Power LED” are available in a large range of colour temperatures distributed throughout the entire chromatic spectrum. The selection made will be defined by its bin guaranteeing its homogeneity in it.

Color
Amplia Gama de Temperaturas de Color

Los “Top led” al igual que los “Power led” se encuentran disponibles en una extensa gama de temperaturas de color distribuidas a lo largo del espectro cromático. La selección determinada vendrá definida por su bin garantizándose su homogeneidad dentro del mismo.

Degree of Protection
Grado de Protección

IP
20

Protection degree offered by the fixture to the ingress of solids and liquids.

Índice de protección contra la penetración de partículas sólidas y húmedas.

IP
20

1st figure: protection against penetration by solid bodies.

1a cifra: protección contra la penetración de cuerpos sólidos.

0 No protection.
1 Protected against solid bodies over 50 mm in diameter.
2 Protected against solid bodies over 12 mm in diameter.
3 Protected against solid bodies over 2,5 mm in diameter.
4 Protected against solid bodies over 1 mm in diameter.
5 Protected against dust.
6 Fully protected against dust.


0 Ninguna protección.
1 Protección contra cuerpos sólidos de tamaño superior a 50 mm.
2 Protección contra cuerpos sólidos de tamaño superior a 12 mm.
3 Protección contra cuerpos sólidos de tamaño superior a 2,5 mm.
4 Protección contra cuerpos sólidos de tamaño superior a 1 mm.
5 Protección contra el polvo.
6 Totalmente protegido contra el polvo.

IP
2**0**

2nd figure: protection against penetration by water.

2a cifra: protección contra la penetración de agua.

0 No protection.
1 Protected against drops of water falting vertically.
2 Protected against drops of water at a max. inclination of 15 degrees.
3 Protected against drops of water at a max. inclination of 60 degrees.
4 Protected against splashed of water.
5 Protected against jets of water.
6 Protected against waves.
7 Protected against immersión.
8 Protected against long term immersión.



0 Ninguna protección.
1 Protección contra caída vertical de gotas de agua.
2 Protección contra caída vertical de gotas de agua, 15° máx. inclinación.
3 Protección contra caída vertical de gotas de agua, 60° máx. inclinación.
4 Protección contra salpicaduras de agua.
5 Protección contra chorros de agua.
6 Protección contra olas de agua.
7 Protección contra inmersión.
8 Protección contra inmersión prolongada.

Pictography
Simbología



Luminaire with builtin power packs or transformers, suitable for mounting directy onto normally inflammable surfaces.

Luminarias con balastos incorporados o transformadores previstos para montaje directo sobre superficies normalmente inflamables.



Conventional Ballast.

Balasto convencional.

GWT
850°

Passes Glow Wire Test at 850ºC according to standard IEC 60695-2-10.

Pasa ensayo de Hilo Incandescente (Glow Wire Test) a 850ºC según norma IEC 60695-2-10.



Luminaires designed to exclusively use wolfram halogen lamps or metal halide lamps with own protection screen.

Luminarias diseñadas para usar únicamente lámparas halógenas de volframio o lámparas de halogenuros metálicos con pantalla de protección propia.

Luminaires Classification
Clases de Aislamiento de las Luminarias



Class I

Luminaire in which protection against electrical shocks is not just based on the basic insulation but also on an additional safety precautions consisting of connecting the accesible conductive parts to a safety conductor (earth).

Luminaria cuya protección contra los choques eléctricos no está basada en un aislamiento básico del aparato sino en medidas de seguridad adicionales consistentes en conectar las partes accesibles conductoras de la luminaria a un conductor de seguridad o toma de tierra.



Class II

Luminaire in which protection against electrical shocks is not just based on the basic insulation but also on an additional safety precautions consisting of double reinforced insulation without conductive parts to a safety conductor (earth).

Luminaria cuya protección contra los choques eléctricos no está basada en un aislamiento básico del aparato sino en medidas de seguridad adicionales consistentes en un doble aislamiento reforzado.



Class III

Luminaire in which protection against electrical shocks is based on the very low safety supply voltage and no voltages are produced higher than this. A Class III luminaire must never be provided with earthing.

Luminaria cuya protección contra los choques eléctricos está basada en la muy baja tensión de alimentación sin que se produzcan voltajes mayores a ésta. Una luminaria de Clase III nunca debe ser suministrada con toma de tierra.

Homologations
Homologaciones

CE

All lamps manufactured and illustrated in this catalog comply with European Standard EN 60 598 and consequently meet the requirements set forth in Directive 73/23 EEC (Low Voltage Directive). They also comply with Directive 89/336 covering electromagnetic compatibility. All products falling under the scope of the above-mentioned Directives bear the CE mark as proof of their compliance with the respective requirements.

Todas las luminarias producidas y presentadas en este programa se han realizado en conformidad con la Norma Europea EN 60 598 y, por consiguiente, cumplen los requisitos establecidos por la Directiva CEE 73/23 (Directiva de Baja Tensión). Su realización garantiza también la conformidad con la Directiva 89/336 en lo concerniente la Compatibilidad Electromagnética. Todos los productos que forman parte del campo de aplicación de estas Directivas llevan el marcado CE que certifica su conformidad a los respectivos requisitos.

ENEC 03

The ENEC mark on the product stands for the compliance of European Standard as well as a trustworthy organisation and product system and is guaranteed by an accredited certification body.
This agreed mark stands for our engagement and represents the best guarantee in security and quality matter of our products.

La presencia del marcado ENEC en el producto testimonia el cumplimiento de la normativa europea y garantiza la fiabilidad del sistema organizativo y productivo responsable de su fabricación, a través de un organismo de certificación acreditado.
El marcado ENEC representa nuestro compromiso y mejor garantía en materias de seguridad y calidad en todos nuestros productos.

CERTIFIED IQNet MANAGEMENT SYSTEM

AENOR ER Empresa Registrada ER-0202/1/98 ISO 9001

The Spanish association for standardization and certification, AENOR, certifies that the Integrated Quality and Environmental Management System adopted by Antares Iluminación S.A. It complies with the requirements of the European Standards EN ISO 9001:2015 Quality Management System and EN ISO 14001:2015 Environmental Management System.

La asociación española de normalización y certificación AENOR certifica que el Sistema Integrado de Gestión de la Calidad y Medioambiente adoptado por Antares Iluminación S.A. es conforme a las exigencias de la Normas Europeas EN ISO 9001:2015 Sistema de gestión de la Calidad y EN ISO 14001:2015 Sistema de Gestión Ambiental.

QCERT ORGANISMO DE CERTIFICACION ACREDITADO ONAC CÓDIGO: 11-CPR-003 ISO IEC 17065:2012 CONSULTE EL ALCANCE DE NUESTROS PRODUCTOS CERTIFICADOS EN WWW.QCERT.COM.CO

The QCERT S.A.S. Certification Body evaluates the conformity of our products to enable their placement on the Colombian market while taking into account the current national and international regulations.
This product certification allows manufacturers and marketers to expand their markets and gain a competitive advantage that can transcend the boundaries of the local market while enhancing international trade.

El Organismo de Certificación QCERT S.A.S. evalúa la conformidad de nuestros productos para su comercialización en Colombia, considerando la normativa nacional e internacional vigente. Esta certificación de producto permite a los fabricantes y comercializadores expandir sus mercados y obtener una ventaja competitiva que puede trascender las fronteras del mercado local, potencializando el comercio a nivel internacional.

IECEE CB SCHEME

Created by IECEE, the CB certification system based on the IEC International Standards is recognized in Saudi Arabia, Argentina, Australia, Austria, Bahrain, Belgium, Belarus, Brazil, Bulgaria, Canada, China, Colombia, Croatia, Denmark, United Arab Emirates , Finland, France, Germany, Japan, Greece, India, Indonesia, Ireland, Israel, Italy, Kenya, Libya, Malaysia, Mexico, Norway, New Zealand, Netherlands, Pakistan, Poland, Portugal, United Kingdom, Czech Republic, Republic of Korea, Romania, Russia, Serbia, Singapore, Slovakia, Slovenia, Spain, United States, South Africa, Sweden, Switzerland, Thailand, Turkey, Ukraine, Hungary and Uruguay.

Creada por IECEE, el sistema de certificación CB basado en la Normas Internacionales IEC está reconocido en Arabia Saudí, Argentina, Australia, Austria, Bahréin, Bélgica, Bielorrusia, Brasil, Bulgaria, Canadá, China, Colombia, Croacia, Dinamarca, Emiratos Árabes Unidos, Finlandia, Francia, Alemania, Japón, Grecia, India, Indonesia, Irlanda, Israel, Italia, Kenia, Libia, Malasia, México, Noruega, Nueva Zelanda, Países Bajos, Pakistán, Polonia, Portugal, Reino Unido, República Checa, República de Corea, Rumanía, Rusia, Serbia, Singapur, Eslovaquia, Eslovenia, España, Estados Unidos, Sudáfrica, Suecia, Suiza, Tailandia, Turquía, Ucrania, Hungría y Uruguay.

Photometric Data
Datos Fotométricos

With the passing of time, we have been exposed to a rising number of visual impacts. It is currently estimated that about 75% of the information we processe when relating to our surroundings is received through our eyes, which work very much like a camera, through the light that is emitted or reflected from objects in a given environment. This means that the information processed by the brain is heavily reliant on the level and type of light, and how this environment is illuminated.
The photometric documentation that has been prepared (especially through the calculation program) aims to provide lighting designers with the material they need to develop lighting projects that comply with the EN 12464-1 standard now in force, in terms of sufficient light distribution, visual comfort, maximum lighting efficiency and consequently, the lowest possible energy consumption. In order to make the most of the calculation program, it is essential to have all the necessary information on the products to be used.

Con el paso del tiempo, el número de inputs visuales a los que el hombre se expone ha aumentado. Actualmente, parece que aproximadamente el 75% de la información que el hombre procesa para relacionarse con su medio ambiente la recibe a través de los ojos, que funcionan de manera parecida a una cámara fotográfica, utilizando la luz emitida o reflejada por los objetos que hay en un determinado ambiente. Esto significa que la información procesada por el cerebro depende en gran medida de los niveles, del tipo de luz y del modo en que se ilumina ese ambiente.
Con la documentación fotométrica redactada (en especial a través del programa de cálculo) queremos facilitar a los diseñadores de iluminación el material necesario para la realización de proyectos de alumbrado que satisfagan la actual normativa EN 12464-1 por lo que se refiere la adecuada distribución de la luz, confort visual, máxima eficiencia luminosa y la consiguiente reducción de energia. Para aprovechar al máximo las posibilidades del programa de cálculo es fundamental disponer de toda la información necesaria sobre los productos que pueden utilizarse.


EN 12464-1 Standard

Sets the technical lighting requirements that satisfy the needs of indoor visual performance, especially in workplaces, even when visual display terminals are used, by prescribing the average illuminance values Em, color rendering Ra, visual comfort UGR.
UGR (Unified Glare Rating)
Classifies the discomfort glare caused by an indoor lighting system, taking into account the kind of luminaires, the reflecting features and size of the rooms, the position of the observers.
For example, for CAD workstations, EN 12464-1 standards set Em = 500 lx, Ra= 80, UGR<=19.

Norma EN 12464-1

Especifica los requisitos luminotécnicos para satisfacer las exigencias de prestación visual en los lugares de trabajo en interiores, incluidos los que prevén la utilización de pantallas de ordenador, prescribiendo los valores medios de iluminancia Em, el índice de rendimiento cromático Ra y el confort visual UGR.
Índice unificado de deslumbramiento UGR (Unified Glare Rating)
Define la clase de deslumbramiento causado por la instalación de alumbrado en un interior, tomando en consideración el tipo de luminarias, las características de reflexión y las dimensiones de los locales, así como la posición de los observadores.
Por ejemplo, para puestos de trabajo en los que se trabaje con programas CAD las normas EN 12464-1 prescriben Em = 500 lx, Ra= 80, UGR<=19.

Diagram of the Characteristics of Light Output




Luminous intensity distribution is presented in the form of a polar plot of one or more C planes that cross-section the luminaire, passing though its light center of gravity. The planes and the intensity are shown by means of a system of spherical coordinates (C, γ, I). The curves that join the ends of the intensity vectors on a C plane are called photometric curves or output indicators.
The number of C-section planes is prescribed by CIE recommendations, and is referred to in the European Standards on photometric measurements and data presentation (CEN 13 032-1).
For revolving or symmetrical luminaires, light output is shown as a single curve. In all the other cases, the diagram shows the horizontal (C0-180) and longitudinal (C90-270) planes at least.
For luminaires that can be fitted with light sources that are geometrically the same but with different luminous fluxes, it is generally accepted that the polar plot shows an ideal luminous flux of 1,000 lumen and is therefore expressed in cd/klm.
For light sources that include reflectors, the maximum luminous intensity values provided in this catalogue are absolute (cd) and do not refer to a standard 1,000 lm flux. For other sources, the same values correspond to an ideal 1,000 lm (cd/klm) flux.
For LED-based products incorporating control electronics and heat sinks, products requiring only line voltage or DC power supply, including complete LED luminaires with no replaceable integrated LED sources, the LM-79 test method uses absolute photometry to directly measure total lumen output for a particular configuration.
The real distribution of light and light intensity are measured directly for the complete luminaire.

Representación Gráfica de las Características de Emisión Luminosa

La distribución de las intensidades luminosas emitidas por una luminaria se representa con un diagrama polar correspondiente a uno o más planos C que seccionan la luminaria pasando por su baricentro luminoso. Los planos y las intensidades están definidos por un sistema de coordenadas esféricas (C, γ, I). Las curvas que unen los extremos de los vectores intensidad sobre un plano C se llaman curvas fotométricas o indicadoras de emisión.
El número de planos sección C lo prescriben las recomendaciones CIE, y se indica en la Norma Europea correspondiente a las mediciones fotométricas y a la presentación de los datos (CEN 13 032-1). Para luminarias que presentan emisiones rotosimétricas, la emisión luminosa está representada por una única curva. En todos los demás casos la representación gráfica prevé, como mínimo, los planos transversal (C0-180) y longitudinal (C90-270). Para luminarias que pueden montar lámparas geométricamente iguales pero con flujos luminosos diferentes, por lo general se acepta que el diagrama polar de las intensidades esté representado por un flujo luminoso ideal de 1.000 lumen y por lo tanto expresado en cd/klm.
Para fuentes luminosas con óptica incorporada, los valores de la intensidad luminosa máxima facilitados en este catálogo son absolutos (cd) y no se refieren a un flujo normalizado de 1.000 lm, mientras en las demás fuentes los mismos valores corresponden a un flujo ideal de 1.000 lm (cd/klm).
Para productos LED que incorporan electrónica de control y disipadores de calor, que requieran tanto alimentación a tensión de red o mediante fuente de alimentación DC, incluyendo luminarias LED completas provistas de módulos LED no reemplazables, el método de ensayo LM-79 utiliza la fotometría absoluta para medir directamente el flujo luminoso total para una configuración particular.
La distribución real de la luz e intensidad luminosa se miden directamente de la luminaria completa.

E(lx/Klm) h(m)	D(m) 11°
1 4918	0.20
2 1229	0.40
3 546	0.60
4 307	0.80
5 197	0.99



Illuminance (shown as E)

The average illuminance expressed in lux (lx) on a surface is the quotient resulting from the luminous flux, expressed in lumen (lm), on the surface and the dimension (m^2) of the surface itself. Depending on the need, the illuminance value can be horizontal (e.g. on a desk: for reading), vertical (illumination of a sports fields: to see the players), semi-cylindrical (urban fittings: to see who is coming towards us).
In some cases, for example when using spotlights or lamps with a reflector, the performance features are simply shown by means of tables called “light cones” showing both the average and maximum illuminance values, as well as the diameter of the luminous spot, in relation to the distance of the plane from the luminaire. The vertex angle of the light cone is the luminaire’s beam, that is, the angle formed by the intensity vector when its module is greater than half of the maximum intensity.
Illuminance is expressed in lux per 1,000 lm (lx/klm). For light sources that include reflectors, the average and maximum illuminance values are absolute. For other sources, they correspond to an ideal 1,000 lm flux.

Iluminancia (representado con el Símbolo E)

El nivel medio de iluminancia expresado en lux (lx) sobre una superficie es el cociente entre el flujo luminoso, expresado en lumen (lm) que incide sobre la superficie y el tamaño (m^2) de dicha superficie. En función de las exigencias es posible calcular iluminancias horizontales (por ej. sobre un escritorio: para leer), verticales (alumbrado de un campo deportivo: para reconocer los atletas) o semicilíndricas (alumbrado urbano: para identificar con quien nos cruzamos).
En algunos casos, por ej. al utilizar focos y lámparas con reflector incorporado, la representación de las prestaciones se simplifica mediante tablas llamadas “conos de luz” que indican tanto los valores de las iluminancias medias y máximas como los diámetros de la mancha luminosa en relación con las distancias del plano respecto a la luminaria. El ángulo en el vértice del cono de luz es la apertura del haz de la luminaria, es decir el ángulo descrito por el vector intensidad cuando su módulo es mayor que la mitad de la intensidad máxima. La iluminancia se expresa en lux por cada 1.000 lm (lx/klm). Para fuentes luminosas con óptica incorporada, los valores de las iluminancias medias y máximas son absolutos, mientras que para las demás fuentes corresponden a un flujo ideal de 1.000 lm.

Isolux

The photometric results of a lighting installation can be shown on a surface using an “Isolux”, that is, lines connecting the points with the same illuminance. Isolux diagrams are used to quickly determine, albeit in an approximate manner, the average value and uniformity of the illuminance.

Isolux

Sobre una superficie, los resultados fotométricos de una instalación de iluminación pueden representarse gráficamente mediante “isolux”, es decir líneas que unen los puntos que tienen la misma iluminancia. Las isolux permiten evaluar rápidamente, aunque aproximadamente, el valor medio y la uniformidad de la iluminancia.

CIE 62/98/100/100/74
DIN A5O
UTE 0.47C+0.00T
CIBSE TM5 BZ3/2/BZ2

Photometric classification of luminaires

Using the classification of luminous flux distribution and using the various ratios between the flux emitted by a luminaire in the upper and lower hemispheres, as well as the ratio of their different yields, a luminaire can be classified on the basis of different recommendations and standards: CIE, DIN 5040, UTE, and CIBSE LG3.

Clasificación Fotométrica de las Luminarias

Considerando las características de distribución del flujo luminoso y según varias relaciones entre el flujo emitido por una lámpara en el hemisferio superior e inferior, así como la relación entre los varios rendimientos, es posible caracterizar una luminaria según distintas normas y estándares: CIE, DIN 5040, UTE y CIBSE LG3.

CIE

Diagram of flux distribution by a luminaire inside cones with specific angles; the last number of the series provides the total output ratio of the luminaire. Illuminating luminaires are classified on the basis of five numbers (CIE codes)
$N_1=F_1/F_4$ $N_2=F_2/F_4$ $N_3=F_3/F_4$ $N_4=F_4/F_5$ $N_5=F_5/F$= yield
Where:
F_1 is the flux emitted in the solid angle cone $\pi/2$, vertex angle 83°
F_2 is the flux emitted in the solid angle cone π, vertex angle 120°
F_3 is the flux emitted in the solid angle cone $3\pi/2$, vertex angle 151°
F_4 is the flux emitted in the solid angle cone 2π, vertex angle 180°
F_5 is the flux emitted in the solid angle cone 4π, vertex angle 360°
F is the installed flux.

CIE

Representación de la distribución del flujo emitido por la luminaria en el interior de conos con ángulos de apertura definidos; el último número de la serie indica el rendimiento total de la luminaria.
Las luminarias se clasifican según cinco números (códigos CIE)
$N_1=F_1/F_4$ $N_2=F_2/F_4$ $N_3=F_3/F_4$ $N_4=F_4/F_5$ $N_5=F_5/F$= rendimiento
Donde:
F_1 es el flujo emitido en el cono de ángulo sólido $\pi/2$, ángulo en el vértice 83°
F_2 es el flujo emitido en el cono de ángulo sólido π, ángulo en el vértice 120°
F_3 es el flujo emitido en el cono de ángulo sólido $3\pi/2$,S ángulo en el vértice 151°
F_4 es el flujo emitido en el cono de ángulo sólido 2π, ángulo en el vértice 180°
F_5 es el flujo emitido en el cono de ángulo sólido 4π, ángulo en el vértice 360°
F es el flujo instalado.

DIN 5040

The photometric classification of luminaires consists of a letter and two numbers. The letter indicates the luminous distribution starting from A: direct concentrated to E: indirect. The first number indicates the percentage of luminous flux emitted in the lower hemisphere (direct). The second number indicates the percentage of luminous flux in the upper hemisphere (indirect).

UTE

The photometric classification of luminaires consists of a number that indicates the direct output ratio followed by a letter that indicates the luminous distribution starting from A for a narrow angle to J for semi-indirect. Should the luminaire also have indirect emission (upper hemisphere), the indirect yield followed by the letter "T" is added. For example, for a luminaire emitting 30% of its flux downwards and 35% upwards, with a semi-indirect emission, the UTE code would be 0.30J + 0.35T.

CIBSE LG3

With the amendment of Lighting Guidance 3 in 2001, the category classification system (Cat) was abolished to conform to European Standard EN 12464-1.
This British Standard classified luminaires in three luminance categories: C0-180, C90-270, C135-315 and C225-45.
CIBSE LG3 Cat 1 if luminance was lower than 200 cd/m^2 starting at a 55° observation angle γ.
CIBSE LG3 Cat 2 if luminance was lower than 200 cd/m^2 starting at a 65° observation angle γ.
CIBSE LG3 Cat 3 if luminance was lower than 200 cd/m^2 starting at a 75° observation angle γ.

Colored Filters

The use of colored filters in a luminaire modifies its photo-colorimetric features, for example the color temperature of the light bulb, adapting it for accent lighting or for a special setting.
The use of filters also reduces the luminous output which can vary depending on the filter's characteristics.

Eulumdat Files

The Eulumdat files of all the FLOS luminaires are available on our website www.flos.com, so they can be used in technical lighting calculations.

DIN 5040

La clasificación fotométrica de las luminarias está constituida por una letra y dos números. La letra indica la distribución luminosa empezando por la A: directa concentrada, hasta la E: indirecta. La primera cifra indica el porcentaje de flujo luminoso emitido en el hemisferio inferior (directa). La segunda cifra indica el porcentaje de flujo en el hemisferio superior (indirecto).

UTE

La clasificación fotométrica de las luminarias está constituida por un número que indica el rendimiento directo seguido por una letra que indica la distribución luminosa a partir de A para el haz estrecho hasta J para el semiindirecto. Si la luminaria tuviera también una emisión indirecta (superior), se añadiría el rendimiento indirecto seguido por la letra "T". Por ejemplo para una luminaria que emita el 30% de su flujo hacia abajo y el 35% del flujo hacia arriba, con una emisión semiindirecta, el código UTE sería 0,30J + 0,35T.

CIBSE LG3

Con las modificaciones en el Lighting Guidance 3 de 2001 el sistema de clasificación por categorías (Cat) fue abolido para uniformarse con la normativa Europea EN 12464-1.
Esta normativa inglesa clasificaba las luminarias en tres categorías según la luminancia en cuatro planos: C0-180, C90-270, C135-315 y C225-45.
Estaban clasificadas como CIBSE LG3 Cat 1 las luminarias con luminancia inferior a 200 cd/m^2 para ángulos de observación γ a partir de 55°.
Estaban clasificadas como CIBSE LG3 Cat 2 las luminarias con luminancia inferior a 200 cd/m^2 para ángulos de observación γ a partir de 65°.
Estaban clasificadas como CIBSE LG3 Cat 3 las luminarias con luminancia inferior a 200 cd/m^2 para ángulos de observación γ a partir de 75°.

Filtros de Colores

La aplicación de filtros de colores a una luminaria permite modificar las características fotocolorimétricas, por ejemplo la temperatura del color de la lámpara, adecuándola a las exigencias de un alumbrado de acento o de una ambientación particular.
La utilización de filtros determina, además, una reducción de la emisión luminosa de entidad variable en función de las características del filtro.

Archivos Eulumdat

Los archivos Eulumdat de todas las luminarias de FLOS están disponibles en nuestra web www.flos.com, para permitir su utilización en programas de cálculo luminotécnico.

SOFT ARCHITECTURE

Juncos, Soft Spun, Abajourd'hui,
G-O In, Teardrop, Uso,
Round, Square & Vertical Light.

Juncos

Juncos 1L



Juncos 3L



Juncos 6L



Juncos 9L



Soft Spun

Soft Spun Small



Soft Spun Large



Abajourd'hui

Abajourd'hui Small




Abajourd'hui Large



Juncos Designed By Flos Soft Architecture

Juncos 1L





0,70 Kg

Semi-recessed LED luminaire for indoor applications. Seamless integration in the architectural environment by Soft Architecture technology. Power supply not included. See drivers in next page.


Pre-wired product to be connected to constant current.

Luminaria LED de interiores semiempotrada que combinada con la tecnología Soft Architecture se integra perfectamente en el espacio arquitectural. Fuente de alimentación no incluida. Ver drivers en la siguiente página.

Producto precableado para su conexión a corriente constante.

Juncos 3L







2,90 Kg

Pre-wired product for serial connection to constant current.

Producto precableado en serie para su conexión a corriente constante.

Juncos 6L







5,80 Kg

Pre-wired product for serial connection to constant current.

Producto precableado en serie para su conexión a corriente constante.

Juncos 9L





8,70 Kg

Pre-wired product for serial connection to constant current.

Producto precableado en serie para su conexión a corriente constante.

Soft Plate / Placa Soft

Juncos 1L
☐ SA.5200.5.120

Juncos 3L
☐ SA.5201.5.120


Juncos 6L
☐ SA.5202.5.120


Juncos 9L
☐ SA.5203.5.120

Junco 250 mm

Power LED DC 700 mA - 2,1W - 216 lm - 3000K/CRI 80 / 2,1W - 182 lm- 2700K/CRI 90









Luminaire that offers many possibilities. Can be individually focused and their recessed height is adjustable. Available in a black, white and chrome finish.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.

Luminaria que ofrece gran versatilidad. Individualmente orientable y nivel de empotramiento regulable. Disponible en acabado negro, blanco y cromo.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).


Junco 400 mm








Junco 250 mm
2700K
08.8595.40A
08.8595.05A
08.8595.AAA



Luminous flux luminaire
130 lm

Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	1443	0.27
2	361	0.53
3	160	0.80
4	90	1.07
5	58	1.34


3000K
08.8590.40A
08.8590.05A
08.8590.AAA



Luminous flux luminaire
173 lm

Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	1919	0.27
2	480	0.53
3	213	0.80
4	120	1.07
5	77	1.34


Junco 400 mm
2700K
08.8596.40A
08.8596.05A
08.8596.AAA



Luminous flux luminaire
130 lm

Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	1443	0.27
2	361	0.53
3	160	0.80
4	90	1.07
5	58	1.34

3000K
08.8591.40A
08.8591.05A
08.8591.AAA



Luminous flux luminaire
173 lm

Beam Angle:	15°	
h(m)	E(lx)	D(m)
1	1919	0.27
2	480	0.53
3	213	0.80
4	120	1.07
5	77	1.34

Drivers for Serial Connection / Equipos para Conexión en Serie

DIM Protocol	1L	3L	6L	9L
Non Dimmable	60.9592			
Non Dimmable	60.9408			
Non Dimmable - UL	60.8911			
Dimmable 1-10V - Push - UL	60.9188			-
Dimmable Dali	60.9222			
Casambi	-	60.7785	60.7785	60.7785
Mains Dimming	60.9379	60.9379	60.9692	60.9692


* Refer to the Drivers chapter / Ver capítulo Drivers


Max. distance from LED driver / Distancia máxima del equipo de LED Constant current driver (700mA) / Equipo de corriente constante			
Distance / Distancia	10 m	20 m	50 m
Cable section / Sección de cable	0,5mm^2	1mm^2	2,5mm^2

Soft Spun LED Small Designed By Sebastian Wrong

LED White 35W - 1800 lm - 3000K/CRI 90







Recessed luminaire for LED lamp. Non-dimmable 220/240V power supply included.

See Flos Decorative Collection catalogue.

Luminaria empotrable para lámpara LED. Alimentador 220/240V no dimable incluido.


Ver catálogo FLOS Decorative Collection.


SA.5006.1F

Soft Spun LED Large Designed By Sebastian Wrong

LED White 35W - 1800 lm - 3000K/CRI 90 (diffuser) / LED White 1,4W - 80 lm - 2700K/CRI>90 (base)







Recessed luminaire for LED lamp. Non-dimmable 220/240V power supply included.

See Flos Decorative Collection catalogue.

Luminaria empotrable para lámpara LED. Alimentador 220/240V no dimable incluido.


Ver catálogo FLOS Decorative Collection.


SA.5007.1F

Abajourd'hui Small Designed By Flos Soft Architecture

QT-32 E27 - max 75W







Recessed luminaire with direct connection to mains. Excluded light source. To be ordered separately.

See Flos Decorative Collection catalogue.

Luminaria empotrable con alimentación directa a red. Fuente de luz no incluida. Se ha de pedir por separado.


Ver catálogo FLOS Decorative Collection.


SA.5001.1

Abajourd'hui Large Designed By Flos Soft Architecture

QT-32 E27 - max 150W







Recessed luminaire with direct connection to mains.

See Flos Decorative Collection catalogue.

Luminaria empotrable con alimentación directa a red.

Ver catálogo FLOS Decorative Collection.

SA.5000.1

G-O In




Teardrop Small / Medium



USO

USO Kap 105



USO Cove Lighting

USO 900 Cove Lighting



USO 1700 Cove Lighting



USO 2200 Cove Lighting



USO 2500 Cove Lighting



USO 100 50 Cove Lighting



USO 140 90 Cove Lighting



Round Light Small



Square Light Small / Large




Vertical Light Small / Large



G-O In Designed By Jorge Herrera

Top LED 1,2W - 24V - 105 lm - 3000K/CRI 90







Recessed sign luminaire for indoor application. Power supply source not included: electronic transformer with constant voltage (24V) for LED. 220/240V, 50/60Hz. It includes 1000mm power supply cable.

Luminaria empotrada de señalización para aplicación interior. Fuente de alimentación no incluida: transformador electrónico de tensión constante (24V) para LED. 220/240V, 50/60Hz. Incluye cable de alimentación de 1000mm.

White Light / Luz Blanca
SA.5100.1A
Amber Light / Luz Ámbar
SA.5101.1A
Blue Light / Luz Azul
SA.5102.1A

Lighting Colours
Colores de la Luz

White
Blanco

Amber
Ámbar

Blue
Azul



Recommended power supply / Equipos recomendados*:

Non Dimmable 110-240V	60.9157 (8W)
Non Dimmable 220-240V	60.8703 (25W)
Dali Controler	60.9678A

* Refer to the Drivers chapter / Ver capítulo Drivers

Dali Controler	60.9766
1-10V Controler	60.8640


* Refer to Control Units bellow / Ver Unidades de Control abajo

For Dali installation, the non-dimmable kit and the Dali controller are needed.

Para instalación Dali es necesario el equipo no dimable y el controlador Dali.

Ensure correct polarity (+-) Red +/ Black.


Asegure la correcta polaridad (+-) Rojo +/ Negro.



Control Units / Unidades de Control

Dimmable control unit with 1 channel for 24V LED modules. Power supply not included. Max. 120W - 5A.

Unidad de control dimable de 1 canal para la regulación de módulos LED, para equipos de 24V. No incluye fuente de alimentación. Max. 120W - 5A.




1-10V
60.8640
L1: 172


DALI
60.9766
L1: 181


reddot design award
winner 2013

Teardrop Small Designed By Calvi Brambilla

LED QR-CBC-51 1xGU5.3








Recessed luminaire for 12V LED Retrofit lamp. Remote transformer not included: electronic transformer 12V. 220/240V, 50/60Hz. Adjustable by means of “leading and trailing edge”.
Mains Dimming Products – Please read Mains Dimming disclaimer in drivers chapter.


Luminaria empotrable para lámpara LED Retrofit de 12V. Transformador remoto no incluido: transformador electrónico 12V. 220/240V, 50/60Hz. Posibilidad de regulación “leading and trailing edge”.
Productos Mains Dimming - Lea la cláusula de exención de responsabilidad sobre Mains Dimming en el capítulo de controladores (*Drivers*).


SA.1039.1

Teardrop Medium Designed By Calvi Brambilla

TC-DEL 2xG24q - 26W









Recessed luminaire for fluorescent lamp. Non-dimmable ballasts 220-240V / 50-60Hz integrated.


Luminaria empotrable para lámpara fluorescente. Balastos no dimables 220-240V / 50-60Hz integrado.

SA.1040.1

USO Kap 105 Designed By Flos Soft Architecture







Soft technology architectonic application that permits perfect integration of the Flos architectural products.
For personal configuration, you can add light points in the structure. Ask Flos architectural sales team.

References do not include Flos architectural products.

Aplicación arquitectónica de tecnología Soft que permite una perfecta integración de los productos Flos architectural.
Para una configuración personal, puede añadir puntos de luz en la estructura. Consultar al equipo de ventas de Flos architectural.

Las referencias no incluyen los productos de Flos architectural.

SA.1034.3.116

Flos architectural Recommended Products / Productos Flos architectural Recomendados

Kap Ø105*




SA.1034.3.116
h=290

* Frame No Trim included / Marco No Trim incluido

USO 900 Cove Lighting Designed By Flos Soft Architecture

Cold Cathode 90W - 3x30W - 7776 lm - 3000K/CRI 85
LED White 75,6W - 21x3,6W - 7875 lm - 3000K/CRI 90 / LED RGB 75,6W - 21x3,6W





Recessed ceiling luminaire. Direct lighting with fluorescent, cold cathode or LED lamps. Control gear not included in LED versions.

See LED drivers.

Luminaria empotrada para ser instalada a techo. Iluminación directa con lámparas de fluorescencia, cátodo frío o LED. Equipos no incluidos en las versiones LED.
Ver controladores LED.

Cold Cathode
SA.1006.4.300


LED RGB
SA.1006.6E100

LED White
SA.1006.5E110

USO 1700 Cove Lighting Designed By Flos Soft Architecture

LED White 136,8W - 38x3,6W - 14250 lm - 3000K/CRI 90 / LED RGB 136,8W - 38x3,6W





Recessed ceiling luminaire. Direct lighting with fluorescent, cold cathode or LED lamps. Control gear not included in LED versions.

See LED drivers.

Delivered in two pieces.

Luminaria empotrada para ser instalada a techo. Iluminación directa con lámparas de fluorescencia, cátodo frío o LED. Equipos no incluidos en las versiones LED.
Ver controladores LED.

Se sirve en dos piezas.


LED RGB
SA.1007.6E100

LED White
SA.1007.5E110

USO 2200 Cove Lighting Designed By Flos Soft Architecture

Cold Cathode 205W - 4x51W - 17568 lm - 3000K/CRI 85
LED White 180W - 50x3,6W - 18750 lm - 3000K/CRI 90 / LED RGB 180W - 50x3,6W





Recessed ceiling luminaire. Direct lighting with fluorescent, cold cathode or LED lamps. Control gear not included in LED versions.

See LED drivers.

Delivered in two pieces.

Luminaria empotrada para ser instalada a techo. Iluminación directa con lámparas de fluorescencia, cátodo frío o LED. Equipos no incluidos en las versiones LED.
Ver controladores LED.

Se sirve en dos piezas.

Cold Cathode
SA.1008.4.300


LED RGB
SA.1008.6E100

LED White
SA.1008.5E110

USO 2500 Cove Lighting Designed By Flos Soft Architecture

Cold Cathode 230W - 19728 lm - 3000K/CRI 85
LED White 194W - 54x3,6W - 20250 lm - 3000K/CRI 90 / LED RGB 194W - 54x3,6W





Recessed ceiling luminaire. Direct lighting with fluorescent, cold cathode or LED lamps. Control gear not included in LED versions.

See LED drivers.

Delivered in two pieces.

Luminaria empotrada para ser instalada a techo. Iluminación directa con lámparas de fluorescencia, cátodo frío o LED. Equipos no incluidos en las versiones LED.
Ver controladores LED.

Se sirve en dos piezas.

Cold Cathode
SA.1009.4.300


LED RGB
SA.1009.6E100

LED White
SA.1009.5E110

USO 100 50 Cove Lighting Designed By Flos Soft Architecture

Cold Cathode 58W - 3x19W - 4968 lm - 3000K/CRI 85
LED White 57,6W - 16x3,6W - 6000 lm - 3000K/CRI 90 / LED RGB 57,6W - 16x3,6W





Recessed ceiling luminaire. Direct lighting with fluorescent, cold cathode or LED lamps. Control gear not included in LED versions.

See LED drivers.

Luminaria empotrada para ser instalada a techo. Iluminación directa con lámparas de fluorescencia, cátodo frío o LED. Equipos no incluidos en las versiones LED.
Ver controladores LED.

Cold Cathode
SA.1010.4.300


LED RGB
SA.1010.6E100

LED White
SA.1010.5E110

USO 140 90 Cove Lighting Designed By Flos Soft Architecture

LED White 75,6W - 21x3,6W - 7805 lm - 3000K/CRI 90 / LED RGB 75,6W - 21x3,6W





Recessed ceiling luminaire. Direct lighting with fluorescent, cold cathode or LED lamps. Control gear not included in LED versions.

See LED drivers.

Luminaria empotrada para ser instalada a techo. Iluminación directa con lámparas de fluorescencia, cátodo frío o LED. Equipos no incluidos en las versiones LED.
Ver controladores LED.


LED RGB
SA.1011.6E100

LED White
SA.1011.5E110

Round Light Small Designed By Flos Soft Architecture

LED White 1W - 60 lm - 3000K/CRI > 90





Recessed sign luminaire for indoor application. 100/240V power supply source included.


Luminaria empotrada de señalización para aplicación interior. Fuente de alimentación 100/240V incluida.


SA.3010.1C

Square Light Small Designed By Flos Soft Architecture

LED White 1W - 60 lm - 3000K/CRI > 90







Recessed sign luminaire for indoor application. 100/240V power supply source included.


Luminaria empotrada de señalización para aplicación interior. Fuente de alimentación 100/240V incluida.


SA.3013.1C

Square Light Large Designed By Flos Soft Architecture

LED White 7W - 720 lm - 3000K/CRI > 80







Recessed sign luminaire for indoor application. 100/240V power supply source included.


Luminaria empotrada de señalización para aplicación interior. Fuente de alimentación 100/240V incluida.


SA.3014.1B

Vertical Light Small Designed By Flos Soft Architecture

LED White 1W - 60 lm - 3000K/CRI > 90







Recessed sign luminaire for indoor application. 100/240V power supply source included.


Luminaria empotrada de señalización para aplicación interior. Fuente de alimentación 100/240V incluida.


SA.3015.1C

Vertical Light Large Designed By Flos Soft Architecture

LED White 1W - 60 lm - 3000K/CRI > 90







Recessed sign luminaire for indoor application. 100/240V power supply source included.

Luminaria empotrada de señalización para aplicación interior. Fuente de alimentación 100/240V incluida.

SA.3016.1C

For: USO Cove Lighting: USO 900 C.L., USO 1700 C.L., USO 2200 C.L., USO 2500 C.L., USO 100 50 C.L., USO 140 90 C.L.

Wiring
Cableado

500mm feed cable with fast connection.
Electronic power supply not included.

Cable de alimentación de 500 mm con conexión rápida.
Fuente de alimentación electrónica no incluida.

White	06.1016.00
RGB	06.1049.00

2 meters prolongation cable for LED modules with fast connection. Can be connected with each other to greater length. 20 meters max.

2 metros de prolongación de cable para módulos LED con conexión rápida. Pueden conectarse entre sí para una mayor longitud. 20 metros máximo.

White	08.8297.00
RGB	08.8298.00

Dimmable Interface
Interfaz Regulable

1-10V Master & PWM Repeater

Dimmable interface. Electronic power supply not included.

Interfaz regulable. Fuente de alimentación electrónica no incluida.

White	06.1022.00E

DALI Master

DALI Master interface with one 300mm feed cable for easy connection. It's able to control one USO. If more USOs are in the same installation it's necessary to expand the signal with Slave interfaces. Electronic power supply not included.

Interfaz "Master" DALI con un cable de alimentación de 300mm para una fácil conexión.Posibilidad de controlar un producto USO. Si existe más de un producto USO en la misma instalación, es necesario ampliar la señal con interfaces "Slave". Unidad de alimentación electrónica no incluida.

White	06.1019.00E
RGB	06.1012.00E

DMX Master

DMX Master interface with one 300mm feed cable for easy connection. It's able to control one USO. If more USOs are in the same installation it's necessary to expand the signal with Slave interfaces. Electronic power supply not included.

Interfaz DMX maestra con un cable de alimentación de 300 mm para una conexión sencilla. Puede controlar un USO. Si hay varios USO en la misma instalación, será necesario ampliar la señal con interfaces esclavas. Fuente de alimentación electrónica no incluida.

RGB	06.1005.00E

RF Master

Radio Frequency (RF) RGB Master interface with one 300mm feed cable for easy connection. Wall transmitter to make color changing integrated. It's able to control one USO. If more USOs are in the same installation it's necessary to expand the signal with Slave interfaces. Electronic power supply not included.

Interfaz Radio Frequency (RF) RGB maestra con un cable de alimentación de 300 mm para una conexión sencilla. Transmisor de pared para hacer que el cambio de color sea integrado. Puede controlar un USO. Si hay varios USO en la misma instalación, será necesario ampliar la señal con interfaces esclavas. Fuente de alimentación electrónica no incluida.

RGB	06.1013.00E

DALI, DMX & RF. Slave

Slave interface to expand the control signal. It's able to expand the Master signal in several USOs.
Electronic power supply not included.

Interfaz esclava para ampliar la señal de control. Permite ampliar la señal de la interfaz maestra a varios USO. Fuente de alimentación electrónica no incluida.

White	06.1020.00E
RGB	06.1014.00E

Casambi

Wireless Dimmable Interface. Electronic power supply not included. Interfaz Regulable Wireless.

Interfaz regulable inalámbrica Fuente de alimentación electrónica no incluida. Interfaz regulable inalámbrica

White & RGB	60.9658

For: USO Cove Lighting: USO 900 C.L., USO 1700 C.L., USO 2200 C.L., USO 2500 C.L., USO 100 50 C.L., USO 140 90 C.L.

Power Suply
Fuente de alimentación

Electronic 100W / Electrónica 100W
LED Power supply 100W – 24V. 100-240V, 50-60Hz.

Fuente de alimentación LED 100 W – 24 V. 100-240 V, 50-60 Hz. 60.9443

Electronic 200W / Electrónica 200W
LED Power supply. 200W – 24V. 100-240V, 50-60Hz.

Fuente de alimentación LED. 200 W – 24 V. 100-240 V, 50-60 Hz. 60.9352

Electronic 240W / Electrónica 240W
LED Power supply. 240W – 24V. 100-240V, 50-60Hz.

Fuente de alimentación LED. 240 W – 24 V. 100-240 V, 50-60 Hz. 60.8268

USO Cove Lighting

Configuration Guidelines. Single Individual Product.
Requisitos de configuración Una sola unidad.

For multiple product or a more complex configuration, please consult the technical department. For more detailed information, please refer to the instruction sheet.
Para varias unidades o una configuración más compleja, por favor contacte con el departamento técnico. Para obtener información más detallada, por favor consulte la hoja de instrucciones.

REFERENCE	POWER (W)	LED MODULES	POWER SUPPLY 24Vdc	Max. Distance			LED WHITE				RGB			
				PS-⊘	M-S	⊘-▭▭▭	NO DIM	1-10V	DALI	CASAMBI	DALI	DMX	RF	CASAMBI
							(12 LED modules x feed cable)	(8 LED modules x feed cable)		(10 LED modules x feed cable)	(12 LED modules x feed cable)*			(12 LED modules x feed cable)
USO 100 50 Cove Lighting WHT: SA.1010.5E110 RGB: SA.1010.6E100	58	12 + 4 for corners (16)	1x 100W 60.9443	15m (0,75mm²)	20m	20m	2x 06.1016.00 FEED CABLE	2x 06.1016.00 FEED CABLE + 1x 06.1022.00E MASTER 1-10V	2x 06.1016.00 FEED CABLE + 1 x 06.1022.00E REPEATER PWM + 1x 06.1019.00E DALI MASTER	2x 06.1016.00 FEED CABLE + 1 x 60.9658 CASAMBI 4CH PWM DIMMER	2x 06.1049.00 FEED CABLE + 1x 06.1012.00E MASTER DALI + 1x 06.1014.00E SLAVE RGB	2x 06.1049.00 FEED CABLE + 1x 06.1005.00E MASTER DMX + 1x 06.1014.00E SLAVE RGB	2x 06.1049.00 FEED CABLE + 1x 06.1013.00E MASTER RF + 1x 06.1014.00E SLAVE RGB	2x 06.1049.00 FEED CABLE + 1 x 60.9658 CASAMBI 4CH PWM DIMMER
USO 140 90 Cove Lighting WHT: SA.1011.5E110 RGB: SA.1011.6E100 USO 900 Cove Lighting WHT: SA.1006.5E110 RGB: SA.1006.6E100	76	17 + 4 for corners (21)	1x 100W 60.9443	15m (0,75mm²)	20m	20m	2x 06.1016.00 FEED CABLE	3x 06.1016.00 FEED CABLE + 1x 06.1022.00E MASTER 1-10V	3x 06.1016.00 FEED CABLE + 1 x 06.1022.00E REPEATER PWM + 1x 06.1019.00E DALI MASTER + 1 x 08.8297.00 2m CABLE WHT	3x 06.1016.00 FEED CABLE + 1 x 60.9658 CASAMBI 4CH PWM DIMMER + 1 x 08.8297.00 2m CABLE WHT	2x 06.1049.00 FEED CABLE + 1x 06.1012.00E MASTER DALI + 1x 06.1014.00E SLAVE RGB	2x 06.1049.00 FEED CABLE + 1x 06.1005.00E MASTER DMX + 1x 06.1014.00E SLAVE RGB	2x 06.1049.00 FEED CABLE + 1x 06.1013.00E MASTER RF + 1x 06.1014.00E SLAVE RGB	3x 06.1049.00 FEED CABLE + 1 x 60.9658 CASAMBI 4CH PWM DIMMER + 1 x 08.8297.00 2m CABLE WHT
USO 1700 Cove Lighting WHT: SA.1007.5E110 RGB: SA.1007.6E100	137	30 + 8 for corners (38)	1x 200W 60.9352	40m (1 mm)	20m	20m	4x 06.1016.00 FEED CABLE	6x 06.1016.00 FEED CABLE + 2 x 06.1022.00E MASTER 1-10V + 4 x 08.8297.00 2m CABLE	6x 06.1016.00 FEED CABLE + 1x 06.1019.00E DALI MASTER + 1x 06.1020.00E SLAVE WHT + 2x 06.1022.00E REPEATER PWM + 6 x 08.8297.00 2m CABLE WHT	4x 06.1016.00 FEED CABLE + 2 x 60.9658 CASAMBI 4CH PWM DIMMER + 6 x 08.8297.00 2m CABLE WHT	4x 06.1049.00 FEED CABLE + 1x 06.1012.00E MASTER DALI + 2x 06.1014.00E* SLAVE RGB + 6 x 08.8298.00 2m CABLE RGB	3x 06.1049.00 FEED CABLE + 1x 06.1005.00E MASTER DMX + 2x 06.1014.00E* SLAVE RGB + 6 x 08.8298.00 2m CABLE RGB	3x 06.1049.00 FEED CABLE + 1x 06.1013.00E MASTER RF + 2x 06.1014.00E* SLAVE RGB + 6 x 08.8298.00 2m CABLE RGB	4x 06.1049.00 FEED CABLE + 2 x 60.9658 CASAMBI 4CH PWM DIMMER + 6 x 08.8297.00 2m CABLE WHT
USO 2200 Cove Lighting WHT: SA.1008.5E110 RGB: SA.1008.6E100	180	38 + 12 for corners (50)	1x 240W 60.8268	40m (1 mm)	20m	20m	5x 06.1016.00 FEED CABLE	8x 06.1016.00 FEED CABLE + 2x 06.1022.00E MASTER 1-10V + 6 x 08.8297.00 2m CABLE	8x 06.1016.00 FEED CABLE + 1x 06.1019.00E DALI MASTER + 1x 06.1020.00E SLAVE WHT + 2x 06.1022.00E REPEATER PWM + 8 x 08.8297.00 2m CABLE WHT	6x 06.1016.00 FEED CABLE + 2 x 60.9658 CASAMBI 4CH PWM DIMMER + 4 x 08.8297.00 2m CABLE WHT	5x 06.1049.00 FEED CABLE + 1x 06.1012.00E MASTER DALI + 2x 06.1014.00E* SLAVE RGB + 8 x 08.8298.00 2m CABLE RGB	5x 06.1049.00 FEED CABLE + 1x 06.1005.00E MASTER DMX + 2x 06.1014.00E* SLAVE RGB + 8 x 08.8298.00 2m CABLE RGB	5x 06.1049.00 FEED CABLE + 1x 06.1013.00E MASTER RF + 2x 06.1014.00E* SLAVE RGB + 8 x 08.8298.00 2m CABLE RGB	6x 06.1049.00 FEED CABLE + 2 x 60.9658 CASAMBI 4CH PWM DIMMER + 4 x 08.8297.00 2m CABLE WHT
USO 2500 Cove Lighting WHT: SA.1009.5E110 RGB: SA.1009.6E100	194	42 + 12 for corners (54)	1x 240W 60.8268	40m (1 mm)	20m	20m								
											* For USO 2500 Cove Lighting RGB - 1st Slave: 12 + 12 LED modules 2nd Slave: 10 + 10 +10 LED modules			
											Note: WHITE: Max. 8 modules per cable RGB: Max. 12 modules per cable. Max. 30 Modules per Slave CASAMBI : Max. 32 modules WHITE or 36 modules RGB per interface			

PHYSICAL CHARACTERISTICS

Water Penetration
The material shall be suitable for all internal application, and shall not absorb moisture which may be present through excessive humidity. The material should not be used externally.

Reaction to Fire test for building products
The product Soft Architecture is classified as A1 or A1fl, according to UNE-EN 13501-1: 07, and test methods UNE-EN ISO 1716:02 and UNE-EN ISO 1182:02.

Chemical Resistance
The material shall not be exposed to liquid chemicals or deliquesced crystals.

Thermal Insulation
The material shall have a thermal conductivity value not greater than 0.47W/m. deg K.

Density
The material have a medium density of 1323 Kg/m3.

Structural Characteristics
The material shall have the following characteristics (following EN 13279-2:2006).
Flexion max load: 139N at 7.2mm thickness.
Compression: compression max load shall be bigger than 10000N.
Hardness: Shore C hardness shall be above 90.

CARACTERÍSTICAS FÍSICAS

Infiltración de Agua
El material es adecuado para todas las aplicaciones internas y no absorberá el vapor que se produzca por la excesiva humedad. El material no puede ser usado externamente.

Prueba de resistencia al Fuego para productos de construcción
El producto Soft Architecture está clasificado como A1 o A1fl, conforme a las normas UNE-EN 13501-1: 07, y los métodos de prueba UNE-EN ISO 1716:02 y UNE-EN ISO 1182:02.

Resistencia Química
El material no será expuesto a productos químicos líquidos ó cristales delicados.

Aislamiento Térmico
El material tiene un valor de conductividad térmica no superior a 0,47W/m2. deg K.

Densidad
El material tiene una densidad media de 1,65Kg/l.

Características Estructurales
El material tiene las siguientes características (según la norma EN 13279-2:2006).
Desviación máxima de carga: 139N a 7,2mm de espesor.
Compresión: la carga máxima de compresión es superior a 10000N.
Dureza: la dureza Shore C-80.

FEATURES OF MATERIALS

Water Eco Efficiency
Clean water from drinking network is used in correct proportion to provide optimum workability. Water is cyclically re-used through special filters to prevent ecologic damages to nature before disposal.

Mould Release Agents
Propietary mould release agents are incorporated or applied externally to the mould surface, to optimize cycle time and to achieve consistency of surface finish. These agents shall not have any adverse effect upon the surface of the produced item.

CARACTERÍSTICAS DE LOS MATERIALES

Eco Rendimiento del Agua
El agua potable se utiliza en la proporción correcta para ofrecer una óptima utilidad. El agua es reutilizada cíclicamente a través de filtros especiales que previenen daños ecológicos antes de ser reutilizada en el medio ambiente.

Productos de desmolde
Productos de desmolde patentados son incorporados o aplicados externamente a la superficie del molde, para optimizar el tiempo del ciclo y añadir consistencia al acabado. Estos productos no tienen ningún efecto adverso en la superficie de los productos fabricados.

DESIGN & MANUFACTURING

Design
Latest 3D technology has been applied to develop all components. They are being manufactured and designed in accordance with a fully documented quality assurance system complying with ISO 9001:2008.

DISEÑO & FABRICACIÓN

Diseño
Se ha aplicado la última tecnología 3D para desarrollar todos los componentes. Han sido fabricados y diseñados de acuerdo con un sistema de garantía de calidad totalmente documentado cumpliendo con la norma ISO 9001:2008.

QUALITY CONTROL

General
All components are individually inspected to prevent surface or manufacturing defects.
Normative: UNE-EN 13815: 06; UNE-EN 14246: 07.

Squareness
All components are individually inspected to prevent manufacturing defects bigger than 0.5mm to 500mm from corner.

Flatness
All components are individually inspected to prevent flatness manufacturing defects bigger than 1mm in 1m.

Thickness
All components for continuous ceilings are individually inspected to prevent changes bigger than 2mm in mean target thickness.

Dimensional Tolerance
All components are individually inspected to prevent dimensional tolerance above +/- 3mm.
For more info see www.soft-architecture.com.

Eflorescence
All components with illuminated/visible surface are individually inspected to prevent light eflorescence .

Handmade
This product has been manufactured by hand. Any imperfection is because of its handcrafted process.

CONTROL DE CALIDAD

General
Todos los componentes son inspeccionados individualmente para prevenir defectos superficiales o de fabricación.
Normativa: UNE-EN 13815: 06; UNE-EN 14246: 07.

Área
Todos los componentes son inspeccionados individualmente para prevenir defectos de fabricación mayores de 0,5mm a 500mm desde el ángulo.

Uniformidad
Todos los componentes son inspeccionados individualmente para prevenir defectos de uniformidad de fabricación mayores de 1mm en 1m.

Espesor
Todos los componentes para techos continuos son individualmente inspeccionados para prevenir cambios superiores a 2mm de promedio como objetivo de espesor.

Tolerancia Dimensional
Todos los componentes son inspeccionados individualmente para prevenir la tolerancia dimensional por encima de +/- 3mm.
Más información en www.soft-architecture.com.

Eflorescencia
Todos los componentes con la superficie iluminada/visible son inspeccionados individualmente para prevenir la eflorescencia.

Hecho a mano
Este producto ha sido fabricado a mano. Cualquier posible imperfección es debida a su proceso de fabricación artesanal.

1-10V
1-10 V is one of the earliest and simplest electronic lighting control. The control signal is a DC voltage that varies between one and ten volts. The controlled lighting should scale its output so that at 10 V, the controlled light should be at 100% of its potential output, and at 1 V it should at 0% output (i.e. “Off”).

1-10V
1-10V es uno de los primeros y más simples controles de iluminación electrónica. La señal de control es una tensión de corriente continua que varía entre uno y diez voltios. La iluminación controlada debería aumentar su producción de manera que a 10 V. la luz controlada estaría al 100% de su potencial producción , y a 1 V. estaría al 0% de su producción (es decir “apagada”).

CRI
The color rendering index (CRI) is a quantitative measure of the ability of a light source to reproduce the colors of various objects faithfully in comparison with an ideal or natural light source. Light sources with a high CRI are desirable in color-critical applications.

CRI
El índice de reproducción cromática (IRC) es una medida cuantitativa de la capacidad de una fuente de luz para reproducir fielmente los colores de varios objetos en comparación con una fuente de luz ideal o natural. Las fuentes de luz con un alto IRC son aconsejables en aplicaciones de color críticas.

DALI
Digital Addressable Lighting Interface (DALI) is a technical standard for network-based systems that control lighting in buildings. The DALI standard encompasses the communications protocol and electrical interface for lighting control networks.

DALI
Interfaz Digital de Iluminación Direccionable (DALI) es un estándar técnico para sistemas basados en la red que controlan la iluminación en los edificios. El estándar DALI abarca el protocolo de comunicaciones y la interfaz eléctrica para las redes de control de iluminación.

DIMMER
Dimmers are devices used to vary the brightness of a light.

DIMMER (REGULADOR DE VOLTAJE)
Los Dimmers son dispositivos utilizados para variar la intensidad de la luz.

DMX
DMX is a standard for digital communication networks that are commonly used to control stage lighting. Allows to program the colour regulation and variation for RGB.

DMX
DMX es un estándar para redes de comunicación digital que son comúnmente utilizadas para controlar la iluminación de escenario. Permite programar la regulación de color y variación para RGB.

KELVIN
The kelvin is used in the measure of the color temperature of light sources. Color temperature is a characteristic of visible light that has important applications in lighting because indicates if the light is warm (low color temperatures) or cold (high color temperatures).

KELVIN
El kelvin se utiliza para medir la temperatura del color de fuentes de iluminación. La temperatura del color es una característica de la luz visible que tiene importantes aplicaciones en iluminación porque indica si la luz es cálida (temperaturas de color bajas) o fría (temperaturas de color altas).

LUMEN
The lumen (symbol: lm) is the SI unit of luminous flux, a measure of the power of light perceived by the human eye.

LUMEN
El lumen (símbolo: lm) es la unidad SI de flujo luminoso, una medida de la potencia de la luz percibida por el ojo humano.

MASTER INTERFACE
The master interface it is an electronic device which receives the signal (DALI/DMX/...) and returns a modulated signal for the LED. It’s able to control the light with a maximum power load.

INTERFAZ MASTER
La interfaz Master es un dispositivo electrónico que recibe la señal (DALI/DMX/...) y devuelve una señal modulada para el LED. Es posible controlar la luz con una potencia máxima de carga.

POWER SUPPLY
A power supply is a device that supplies electrical energy to one or more electric loads.

UNIDAD DE ALIMENTACIÓN
Una unidad de alimentación es un dispositivo que suministra energía eléctrica a una o más cargas eléctricas.

RGB
The RGB color model is an additive color model in which red, green, and blue light are added together in various ways to reproduce a broad array of colors. The name of the model comes from the initials of the three additive primary colors, red, green, and blue.

RGB
El modelo a color RGB es un modelo a color añadido donde la luz roja, verde y azul son mezcladas juntas de varias formas para reproducir una amplia gama de colores. El nombre del modelo se da por las iniciales de los tres colores primarios, rojo, verde y azul.

SLAVE INTERFACE
The slave interface is used to reply the modulated signal of the master interface in installations where the master is overloaded.

INTERFAZ SLAVE
La interfaz slave se utiliza para responder a la señal modulada de la interfaz Master en instalaciones donde la interfaz Master está sobrecargada.

Note: Technical data are subject to changes without any previous notice. Information is consistent with our current production conditions and reflects typical values relating to manufacturing specification parameters and for typical end uses. We accept no liability or responsibility for any damage caused by products incorrectly applied in non typical end uses.

Nota: Los datos técnicos están sujetos a cambios sin previo aviso. La información es consecuente con nuestras condiciones actuales de producción y refleja los valores típicos relativos a los parámetros específicos de fabricación y para los USOs para los que fueron creados. La empresa se exime expresamente de toda responsabilidad por cualquier daño causado por productos aplicados de modo incorrecto o no utilizados con la típica finalidad para lo que fueron creados.

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.0700.14A	682	03.0731.CEA	686	03.1211.ER	750	03.1251.DYB	752	03.2237.14A	198	03.4155.74	637
03.0700.14ANT	682	03.0732.14A	686	03.1211.ES	750	03.1251.ERB	752	03.2237.40A	198	03.4155.B1	637
03.0700.40A	682	03.0732.40A	686	03.1215.DR	750	03.1251.ESB	752	03.2238.14A	198	03.4155.GL	637
03.0700.40ANT	682	03.0732.CEA	686	03.1215.DY	750	03.1252.DRB	752	03.2238.40A	198	03.4157.74	637
03.0701.14A	682	03.0733.14A	686	03.1215.ER	750	03.1252.DYB	752	03.2240.14A	200	03.4157.B1	637
03.0701.14ANT	682	03.0733.40A	686	03.1215.ES	750	03.1252.ERB	752	03.2240.40A	200	03.4157.GL	637
03.0701.40A	682	03.0733.CEA	686	03.1216.DR	750	03.1252.ESB	752	03.2241.14A	200	03.4160.74	643
03.0701.40ANT	682	03.0734.14A	686	03.1216.DY	750	03.1253.DRB	752	03.2241.40A	200	03.4160.B1	643
03.0702.14A	683	03.0734.40A	686	03.1216.ER	750	03.1253.DYB	752	03.2242.14A	200	03.4160.GL	643
03.0702.14ANT	683	03.0734.CEA	686	03.1216.ES	750	03.1253.ERB	752	03.2242.40A	200	03.4162.74	643
03.0702.40A	683	03.0735.14A	686	03.1220.DR	748	03.1253.ESB	752	03.2243.14A	200	03.4162.B1	643
03.0702.40ANT	683	03.0735.40A	686	03.1220.DY	748	03.1255.DRB	752	03.2243.40A	200	03.4162.GL	643
03.0703.14A	683	03.0735.CEA	686	03.1220.ER	748	03.1255.DYB	752	03.2245.14A	200	03.4170.74	637
03.0703.14ANT	683	03.0740.14	688	03.1220.ES	748	03.1255.ERB	752	03.2245.40A	200	03.4170.74.LE	639
03.0703.40A	683	03.0740.40	688	03.1221.DR	748	03.1255.ESB	752	03.2246.14A	200	03.4170.B1	637
03.0703.40ANT	683	03.0741.14	688	03.1221.DY	748	03.1256.DRB	752	03.2246.40A	200	03.4170.B1.LE	639
03.0704.14A	682	03.0741.40	688	03.1221.ER	748	03.1256.DYB	752	03.2247.14A	200	03.4170.GL	637
03.0704.14ANT	682	03.0742.14	688	03.1221.ES	748	03.1256.ERB	752	03.2247.40A	200	03.4170.GL.LE	639
03.0704.40A	682	03.0742.40	688	03.1225.DR	748	03.1256.ESB	752	03.2248.14A	200	03.4171.74	637
03.0704.40ANT	682	03.0743.14	688	03.1225.DY	748	03.1257.DRB	752	03.2248.40A	200	03.4171.74.LE	639
03.0705.14A	682	03.0743.40	688	03.1225.ER	748	03.1257.DYB	752	03.2250.14A	200	03.4171.B1	637
03.0705.14ANT	682	03.0744.14	688	03.1225.ES	748	03.1257.ERB	752	03.2250.40A	200	03.4171.B1.LE	639
03.0705.40A	682	03.0744.40	688	03.1226.DR	748	03.1257.ESB	752	03.2251.14A	200	03.4171.GL	637
03.0705.40ANT	682	03.0745.14	688	03.1226.DY	748	03.1258.DRB	752	03.2251.40A	200	03.4171.GL.LE	639
03.0706.14A	683	03.0745.40	688	03.1226.ER	748	03.1258.DYB	752	03.2252.14A	200	03.4172.74	637
03.0706.14ANT	683	03.0760.14A	685	03.1226.ES	748	03.1258.ERB	752	03.2252.40A	200	03.4172.74.LE	639
03.0706.40A	683	03.0760.40A	685	03.1230.DRB	753	03.1258.ESB	752	03.2253.14A	200	03.4172.B1	637
03.0706.40ANT	683	03.0760.CEA	685	03.1230.DYB	753	03.2001.01B	657	03.2253.40A	200	03.4172.B1.LE	639
03.0707.14A	683	03.0761.14A	685	03.1230.ERB	753	03.2001.01BDA	657	03.2255.14A	200	03.4172.GL	637
03.0707.14ANT	683	03.0761.40A	685	03.1230.ESB	753	03.2001.14B	657	03.2255.40A	200	03.4172.GL.LE	639
03.0707.40A	683	03.0761.CEA	685	03.1231.DRB	753	03.2001.14BDA	657	03.2256.14A	200	03.4176.74	633
03.0707.40ANT	683	03.0762.14A	685	03.1231.DYB	753	03.2003.01A	657	03.2256.40A	200	03.4176.74.LE	635
03.0708.14A	682	03.0762.40A	685	03.1231.ERB	753	03.2003.01ADA	657	03.2257.14A	200	03.4176.B1	633
03.0708.14ANT	682	03.0762.CEA	685	03.1231.ESB	753	03.2003.14A	657	03.2257.40A	200	03.4176.B1.LE	635
03.0708.40A	682	03.0763.14A	685	03.1232.DRB	753	03.2003.14ADA	657	03.2258.14A	200	03.4176.GL	633
03.0708.40ANT	682	03.0763.40A	685	03.1232.DYB	753	03.2005.01A	658	03.2258.40A	200	03.4176.GL.LE	635
03.0709.14A	682	03.0763.CEA	685	03.1232.ERB	753	03.2005.01ADA	658	03.2260.14	194	03.4177.74	633
03.0709.14ANT	682	03.0764.14A	685	03.1232.ESB	753	03.2005.14A	658	03.2261.14	194	03.4177.B1	633
03.0709.40A	682	03.0764.40A	685	03.1233.DRB	753	03.2005.14ADA	658	03.2262.14	194	03.4177.GL	633
03.0709.40ANT	682	03.0764.CEA	685	03.1233.DYB	753	03.2006.01B	657	03.2263.14	194	03.4178.74	633
03.0710.14A	683	03.0765.14A	685	03.1233.ERB	753	03.2006.01BDA	657	03.2264.14	194	03.4178.74.LE	635
03.0710.14ANT	683	03.0765.40A	685	03.1233.ESB	753	03.2006.14B	657	03.2265.14	194	03.4178.B1	633
03.0710.40A	683	03.0765.CEA	685	03.1235.DRB	753	03.2006.14BDA	657	03.2266.14	194	03.4178.B1.LE	635
03.0710.40ANT	683	03.0770.14A	686	03.1235.DYB	753	03.2007.01A	657	03.2267.14	194	03.4178.GL	633
03.0711.14A	683	03.0770.40A	686	03.1235.ERB	753	03.2007.01ADA	657	03.2268.14	194	03.4178.GL.LE	635
03.0711.14ANT	683	03.0770.CEA	686	03.1235.ESB	753	03.2007.14A	657	03.2269.14	194	03.4179.74	633
03.0711.40A	683	03.0771.14A	686	03.1236.DRB	753	03.2007.14ADA	657	03.2270.14	194	03.4179.B1	633
03.0711.40ANT	683	03.0771.40A	686	03.1236.DYB	753	03.2008.01A	658	03.2271.14	194	03.4179.GL	633
03.0712.14A	684	03.0771.CEA	686	03.1236.ERB	753	03.2008.01ADA	658	03.2272.14	194	03.4180.74	597
03.0712.14ANT	684	03.0772.14A	686	03.1236.ESB	753	03.2008.14A	658	03.2273.14	194	03.4180.74.LE	599
03.0712.40A	684	03.0772.40A	686	03.1237.DRB	753	03.2008.14ADA	658	03.2274.14	194	03.4180.B1	597
03.0712.40ANT	684	03.0772.CEA	686	03.1237.DYB	753	03.2210.14A	196	03.2275.14	194	03.4180.B1.LE	599
03.0713.14A	684	03.0773.14A	686	03.1237.ERB	753	03.2210.40A	196	03.2280.14	195	03.4180.GL	597
03.0713.14ANT	684	03.0773.40A	686	03.1237.ESB	753	03.2211.14A	196	03.2281.14	195	03.4180.GL.LE	599
03.0713.40A	684	03.0773.CEA	686	03.1238.DRB	753	03.2211.40A	196	03.2282.14	195	03.4181.74	597
03.0713.40ANT	684	03.0774.14A	686	03.1238.DYB	753	03.2212.14A	196	03.2283.14	195	03.4181.B1	597
03.0714.14A	684	03.0774.40A	686	03.1238.ERB	753	03.2212.40A	196	03.2284.14	195	03.4181.GL	597
03.0714.14ANT	684	03.0774.CEA	686	03.1238.ESB	753	03.2213.14A	196	03.2285.14	195	03.4182.74	600
03.0714.40A	684	03.0775.14A	686	03.1240.DRB	754	03.2213.40A	196	03.2286.14	195	03.4182.74.LE	602
03.0714.40ANT	684	03.0775.40A	686	03.1240.DYB	754	03.2215.14A	196	03.2287.14	195	03.4182.B1	600
03.0715.14A	684	03.0775.CEA	686	03.1240.ERB	754	03.2215.40A	196	03.2288.14	195	03.4182.B1.LE	602
03.0715.14ANT	684	03.0800.14A	688	03.1240.ESB	754	03.2216.14A	196	03.2289.14	195	03.4182.GL	600
03.0715.40A	684	03.0800.40A	688	03.1241.DRB	754	03.2216.40A	196	03.2290.14	195	03.4182.GL.LE	602
03.0715.40ANT	684	03.0801.14A	688	03.1241.DYB	754	03.2217.14A	196	03.2291.14	195	03.4183.74	600
03.0716.14A	684	03.0801.40A	688	03.1241.ERB	754	03.2217.40A	196	03.2292.14	195	03.4183.B1	600
03.0716.14ANT	684	03.0802.14A	688	03.1241.ESB	754	03.2218.14A	196	03.2293.14	195	03.4183.GL	600
03.0716.40A	684	03.0802.40A	688	03.1242.DRB	754	03.2218.40A	196	03.2294.14	195	03.4184.74	604
03.0716.40ANT	684	03.0803.14A	688	03.1242.DYB	754	03.2220.14A	197	03.2295.14	195	03.4184.74.LE	606
03.0717.14A	684	03.0803.40A	688	03.1242.ERB	754	03.2220.40A	197	03.2300.14A	197	03.4184.B1	604
03.0717.14ANT	684	03.0804.14A	688	03.1242.ESB	754	03.2221.14A	197	03.2300.40A	197	03.4184.B1.LE	606
03.0717.40A	684	03.0804.40A	688	03.1243.DRB	754	03.2221.40A	197	03.2301.14A	197	03.4184.GL	604
03.0717.40ANT	684	03.0805.14A	688	03.1243.DYB	754	03.2222.14A	197	03.2301.40A	197	03.4184.GL.LE	606
03.0718.14A	685	03.0805.40A	688	03.1243.ERB	754	03.2222.40A	197	03.2302.14A	197	03.4185.74	604
03.0718.40A	685	03.1200.DR	749	03.1243.ESB	754	03.2223.14A	197	03.2302.40A	197	03.4185.B1	604
03.0718.CEA	685	03.1200.DY	749	03.1245.DRB	754	03.2223.40A	197	03.2303.14A	197	03.4185.GL	604
03.0719.14A	685	03.1200.ER	749	03.1245.DYB	754	03.2225.14A	197	03.2303.40A	197	03.4186.74	607
03.0719.40A	685	03.1200.ES	749	03.1245.ERB	754	03.2225.40A	197	03.2320.14	202	03.4186.74.LE	609
03.0719.CEA	685	03.1201.DR	749	03.1245.ESB	754	03.2226.14A	197	03.2320.40	202	03.4186.B1	607
03.0720.14A	685	03.1201.DY	749	03.1246.DRB	754	03.2226.40A	197	03.2321.14	202	03.4186.B1.LE	609
03.0720.40A	685	03.1201.ER	749	03.1246.DYB	754	03.2227.14A	197	03.2321.40	202	03.4186.GL	607
03.0720.CEA	685	03.1201.ES	749	03.1246.ERB	754	03.2227.40A	197	03.2322.14	202	03.4186.GL.LE	609
03.0721.14A	685	03.1205.DR	749	03.1246.ESB	754	03.2228.14A	197	03.2322.40	202	03.4187.74	607
03.0721.40A	685	03.1205.DY	749	03.1247.DRB	754	03.2228.40A	197	03.2323.14	202	03.4187.B1	607
03.0721.CEA	685	03.1205.ER	749	03.1247.DYB	754	03.2230.14A	198	03.2323.40	202	03.4187.GL	607
03.0722.14A	685	03.1205.ES	749	03.1247.ERB	754	03.2230.40A	198	03.2330.14	203	03.4188.74	611
03.0722.40A	685	03.1206.DR	749	03.1247.ESB	754	03.2231.14A	198	03.2330.40	203	03.4188.74.LE	612
03.0722.CEA	685	03.1206.DY	749	03.1248.DRB	754	03.2231.40A	198	03.2331.14	203	03.4188.B1	611
03.0723.14A	685	03.1206.ER	749	03.1248.DYB	754	03.2232.14A	198	03.2331.40	203	03.4188.B1.LE	612
03.0723.40A	685	03.1206.ES	749	03.1248.ERB	754	03.2232.40A	198	03.2332.14	203	03.4188.GL	611
03.0723.CEA	685	03.1210.DR	750	03.1248.ESB	754	03.2233.14A	198	03.2332.40	203	03.4188.GL.LE	612
03.0730.14A	686	03.1210.DY	750	03.1250.DRB	752	03.2233.40A	198	03.2333.14	203	03.4189.74	611
03.0730.40A	686	03.1210.ER	750	03.1250.DYB	752	03.2235.14A	198	03.2333.40	203	03.4189.B1	611
03.0730.CEA	686	03.1210.ES	750	03.1250.ERB	752	03.2235.40A	198	03.4153.74	637	03.4189.GL	611
03.0731.14A	686	03.1211.DR	750	03.1250.ESB	752	03.2236.14A	198	03.4153.B1	637	03.4190.74	613
03.0731.40A	686	03.1211.DY	750	03.1251.DRB	752	03.2236.40A	198	03.4153.GL	637	03.4190.74.LE	614

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.4190.B1	613	03.4234.B1	610	03.4535.74	600	03.5810.ASB	769	03.5945.18	764	03.6020.14	762
03.4190.B1.LE	614	03.4234.GL	610	03.4535.B1	600	03.5810.B3B	769	03.5945.B1	764	03.6020.14ADA	762
03.4190.GL	613	03.4235.74	610	03.4535.GL	600	03.5811.11B	769	03.5947.14	764	03.6020.18	762
03.4190.GL.LE	614	03.4235.B1	610	03.4536.74	600	03.5811.ANB	769	03.5947.18	764	03.6020.18ADA	762
03.4191.74	613	03.4235.GL	610	03.4536.74.LE	602	03.5811.ASB	769	03.5947.B1	764	03.6020.B1	762
03.4191.B1	613	03.4236.74	610	03.4536.B1	600	03.5811.B3B	769	03.5950.14	767	03.6020.B1ADA	762
03.4191.GL	613	03.4236.B1	610	03.4536.B1.LE	602	03.5813.11B	769	03.5950.18	767	03.6021.14	762
03.4192.74	630	03.4236.GL	610	03.4536.GL	600	03.5813.ANB	769	03.5950.B1	767	03.6021.14ADA	762
03.4192.74.LE	632	03.4237.74	610	03.4536.GL.LE	602	03.5813.ASB	769	03.5951.14	767	03.6021.18	762
03.4192.B1	630	03.4237.B1	610	03.4537.74	600	03.5813.B3B	769	03.5951.18	767	03.6021.18ADA	762
03.4192.B1.LE	632	03.4237.GL	610	03.4537.B1	600	03.5900.14	763	03.5951.B1	767	03.6021.B1	762
03.4192.GL	630	03.4242.74	615	03.4537.GL	600	03.5900.18	763	03.5953.14	767	03.6021.B1ADA	762
03.4192.GL.LE	632	03.4242.B1	615	03.4538.74	604	03.5900.B1	763	03.5953.18	767	03.6023.14	762
03.4193.74	630	03.4242.GL	615	03.4538.74.LE	606	03.5901.14	763	03.5953.B1	767	03.6023.14ADA	762
03.4193.B1	630	03.4243.74	615	03.4538.B1	604	03.5901.18	763	03.5954.14	767	03.6023.18	762
03.4193.GL	630	03.4243.B1	615	03.4538.B1.LE	606	03.5901.B1	763	03.5954.18	767	03.6023.18ADA	762
03.4194.74	633	03.4243.GL	615	03.4538.GL	604	03.5903.14	763	03.5954.B1	767	03.6023.B1	762
03.4194.74.LE	635	03.4244.74	615	03.4538.GL.LE	606	03.5903.18	763	03.5955.14	767	03.6023.B1ADA	762
03.4194.B1	633	03.4244.B1	615	03.4539.74	604	03.5903.B1	763	03.5955.18	767	03.6024.14	762
03.4194.B1.LE	635	03.4244.GL	615	03.4539.B1	604	03.5904.14	763	03.5955.B1	767	03.6024.14ADA	762
03.4194.GL	633	03.4245.74	615	03.4539.GL	604	03.5904.18	763	03.5957.14	767	03.6024.18	762
03.4194.GL.LE	635	03.4245.B1	615	03.4540.74	604	03.5904.B1	763	03.5957.18	767	03.6024.18ADA	762
03.4195.74	633	03.4245.GL	615	03.4540.74.LE	606	03.5905.14	763	03.5957.B1	767	03.6024.B1	762
03.4195.B1	633	03.4287.74	630	03.4540.B1	604	03.5905.18	763	03.6000.14	763	03.6024.B1ADA	762
03.4195.GL	633	03.4287.74.LE	632	03.4540.B1.LE	606	03.5905.B1	763	03.6000.14ADA	763	03.6025.14	762
03.4196.74	644	03.4287.B1	630	03.4540.GL	604	03.5907.14	763	03.6000.18	763	03.6025.14ADA	762
03.4196.74.LE	645	03.4287.B1.LE	632	03.4540.GL.LE	606	03.5907.18	763	03.6000.18ADA	763	03.6025.18	762
03.4196.B1	644	03.4287.GL	630	03.4541.74	604	03.5907.B1	763	03.6000.B1	763	03.6025.18ADA	762
03.4196.B1.LE	645	03.4287.GL.LE	632	03.4541.B1	604	03.5910.14	766	03.6000.B1ADA	763	03.6025.B1	762
03.4196.GL	644	03.4288.74	630	03.4541.GL	604	03.5910.18	766	03.6001.14	763	03.6025.B1ADA	762
03.4196.GL.LE	645	03.4288.B1	630	03.4542.74	607	03.5910.B1	766	03.6001.14ADA	763	03.6027.14	762
03.4197.74	644	03.4288.GL	630	03.4542.74.LE	609	03.5911.14	766	03.6001.18	763	03.6027.14ADA	762
03.4197.B1	644	03.4293.74	640	03.4542.B1	607	03.5911.18	766	03.6001.18ADA	763	03.6027.18	762
03.4197.GL	644	03.4293.74.LE	642	03.4542.B1.LE	609	03.5911.B1	766	03.6001.B1	763	03.6027.18ADA	762
03.4198.74	646	03.4293.B1	640	03.4542.GL	607	03.5913.14	766	03.6001.B1ADA	763	03.6027.B1	762
03.4198.74.LE	647	03.4293.B1.LE	642	03.4542.GL.LE	609	03.5913.18	766	03.6003.14	763	03.6027.B1ADA	762
03.4198.B1	646	03.4293.GL	640	03.4543.74	607	03.5913.B1	766	03.6003.14ADA	763	03.6030.14	765
03.4198.B1.LE	647	03.4293.GL.LE	642	03.4543.B1	607	03.5914.14	766	03.6003.18	763	03.6030.14ADA	765
03.4198.GL	646	03.4294.74	640	03.4543.GL	607	03.5914.18	766	03.6003.18ADA	763	03.6030.18	765
03.4198.GL.LE	647	03.4294.B1	640	03.4544.74	607	03.5914.B1	766	03.6003.B1	763	03.6030.18ADA	765
03.4199.74	646	03.4294.GL	640	03.4544.74.LE	609	03.5915.14	766	03.6003.B1ADA	763	03.6030.B1	765
03.4199.B1	646	03.4295.74	640	03.4544.B1	607	03.5915.18	766	03.6004.14	763	03.6030.B1ADA	765
03.4199.GL	646	03.4295.74.LE	642	03.4544.B1.LE	609	03.5915.B1	766	03.6004.14ADA	763	03.6031.14	765
03.4200.74	640	03.4295.B1	640	03.4544.GL	607	03.5917.14	766	03.6004.18	763	03.6031.14ADA	765
03.4200.74.LE	642	03.4295.B1.LE	642	03.4544.GL.LE	609	03.5917.18	766	03.6004.18ADA	763	03.6031.18	765
03.4200.B1	640	03.4295.GL	640	03.4545.74	607	03.5917.B1	766	03.6004.B1	763	03.6031.18ADA	765
03.4200.B1.LE	642	03.4295.GL.LE	642	03.4545.B1	607	03.5920.14	762	03.6004.B1ADA	763	03.6031.B1	765
03.4200.GL	640	03.4296.74	640	03.4545.GL	607	03.5920.18	762	03.6005.14	763	03.6031.B1ADA	765
03.4200.GL.LE	642	03.4296.B1	640	03.4572.74	617	03.5920.B1	762	03.6005.14ADA	763	03.6033.14	765
03.4201.74	640	03.4296.GL	640	03.4572.B1	617	03.5921.14	762	03.6005.18	763	03.6033.14ADA	765
03.4201.B1	640	03.4297.74	630	03.4572.GL	617	03.5921.18	762	03.6005.18ADA	763	03.6033.18	765
03.4201.GL	640	03.4297.74.LE	632	03.5330.29	320	03.5921.B1	762	03.6005.B1	763	03.6033.18ADA	765
03.4208.74	636	03.4297.B1	630	03.5330.40	320	03.5923.14	762	03.6005.B1ADA	763	03.6033.B1	765
03.4208.B1	636	03.4297.B1.LE	632	03.5330.AN	320	03.5923.18	762	03.6007.14	763	03.6033.B1ADA	765
03.4208.GL	636	03.4297.GL	630	03.5331.29	320	03.5923.B1	762	03.6007.14ADA	763	03.6034.14	765
03.4209.74	636	03.4297.GL.LE	632	03.5331.40	320	03.5924.14	762	03.6007.18	763	03.6034.14ADA	765
03.4209.B1	636	03.4298.74	630	03.5331.AN	320	03.5924.18	762	03.6007.18ADA	763	03.6034.18	765
03.4209.GL	636	03.4298.B1	630	03.5332.29	320	03.5924.B1	762	03.6007.B1	763	03.6034.18ADA	765
03.4210.74	636	03.4298.GL	630	03.5332.40	320	03.5925.14	762	03.6007.B1ADA	763	03.6034.B1	765
03.4210.B1	636	03.4520.11B	768	03.5332.AN	320	03.5925.18	762	03.6010.14	766	03.6034.B1ADA	765
03.4210.GL	636	03.4520.ANB	768	03.5333.29	320	03.5925.B1	762	03.6010.14ADA	766	03.6035.14	765
03.4211.74	636	03.4520.ASB	768	03.5333.40	320	03.5927.14	762	03.6010.18	766	03.6035.14ADA	765
03.4211.B1	636	03.4520.B3B	768	03.5333.AN	320	03.5927.18	762	03.6010.18ADA	766	03.6035.18	765
03.4211.GL	636	03.4521.11B	768	03.5334.29	320	03.5927.B1	762	03.6010.B1	766	03.6035.18ADA	765
03.4212.74	643	03.4521.ANB	768	03.5334.40	320	03.5930.14	765	03.6010.B1ADA	766	03.6035.B1	765
03.4212.B1	643	03.4521.ASB	768	03.5334.AN	320	03.5930.18	765	03.6011.14	766	03.6035.B1ADA	765
03.4212.GL	643	03.4521.B3B	768	03.5335.29	320	03.5930.B1	765	03.6011.14ADA	766	03.6037.14	765
03.4213.74	643	03.4523.11B	768	03.5335.40	320	03.5931.14	765	03.6011.18	766	03.6037.14ADA	765
03.4213.B1	643	03.4523.ANB	768	03.5335.AN	320	03.5931.18	765	03.6011.18ADA	766	03.6037.18	765
03.4213.GL	643	03.4523.ASB	768	03.5336.29	320	03.5931.B1	765	03.6011.B1	766	03.6037.18ADA	765
03.4218.74	648	03.4523.B3B	768	03.5336.40	320	03.5933.14	765	03.6011.B1ADA	766	03.6037.B1	765
03.4218.B1	648	03.4530.74	597	03.5336.AN	320	03.5933.18	765	03.6013.14	766	03.6037.B1ADA	765
03.4218.GL	648	03.4530.74.LE	599	03.5337.29	320	03.5933.B1	765	03.6013.14ADA	766	03.6040.14	764
03.4219.74	648	03.4530.B1	597	03.5337.40	320	03.5934.14	765	03.6013.18	766	03.6040.14ADA	764
03.4219.B1	648	03.4530.B1.LE	599	03.5337.AN	320	03.5934.18	765	03.6013.18ADA	766	03.6040.18	764
03.4219.GL	648	03.4530.GL	597	03.5338.29	320	03.5934.B1	765	03.6013.B1	766	03.6040.18ADA	764
03.4220.74	648	03.4530.GL.LE	599	03.5338.40	320	03.5935.14	765	03.6013.B1ADA	766	03.6040.B1	764
03.4220.B1	648	03.4531.74	597	03.5338.AN	320	03.5935.18	765	03.6014.14	766	03.6040.B1ADA	764
03.4220.GL	648	03.4531.B1	597	03.5339.29	320	03.5935.B1	765	03.6014.14ADA	766	03.6041.14	764
03.4221.74	648	03.4531.GL	597	03.5339.40	320	03.5937.14	765	03.6014.18	766	03.6041.14ADA	764
03.4221.B1	648	03.4532.74	597	03.5339.AN	320	03.5937.18	765	03.6014.18ADA	766	03.6041.18	764
03.4221.GL	648	03.4532.74.LE	599	03.5730.11B	768	03.5937.B1	765	03.6014.B1	766	03.6041.18ADA	764
03.4226.74	603	03.4532.B1	597	03.5730.ANB	768	03.5940.14	764	03.6014.B1ADA	766	03.6041.B1	764
03.4226.B1	603	03.4532.B1.LE	599	03.5730.ASB	768	03.5940.18	764	03.6015.14	766	03.6041.B1ADA	764
03.4226.GL	603	03.4532.GL	597	03.5730.B3B	768	03.5940.B1	764	03.6015.14ADA	766	03.6043.14	764
03.4227.74	603	03.4532.GL.LE	599	03.5731.11B	768	03.5941.14	764	03.6015.18	766	03.6043.14ADA	764
03.4227.B1	603	03.4533.74	597	03.5731.ANB	768	03.5941.18	764	03.6015.18ADA	766	03.6043.18	764
03.4227.GL	603	03.4533.B1	597	03.5731.ASB	768	03.5941.B1	764	03.6015.B1	766	03.6043.18ADA	764
03.4228.74	603	03.4533.GL	597	03.5731.B3B	768	03.5943.14	764	03.6015.B1ADA	766	03.6043.B1	764
03.4228.B1	603	03.4534.74	600	03.5733.11B	768	03.5943.18	764	03.6017.14	766	03.6043.B1ADA	764
03.4228.GL	603	03.4534.74.LE	602	03.5733.ANB	768	03.5943.B1	764	03.6017.14ADA	766	03.6044.14	764
03.4229.74	603	03.4534.B1	600	03.5733.ASB	768	03.5944.14	764	03.6017.18	766	03.6044.14ADA	764
03.4229.B1	603	03.4534.B1.LE	602	03.5733.B3B	768	03.5944.18	764	03.6017.18ADA	766	03.6044.18	764
03.4229.GL	603	03.4534.GL	600	03.5810.11B	769	03.5944.B1	764	03.6017.B1	766	03.6044.18ADA	764
03.4234.74	610	03.4534.GL.LE	602	03.5810.ANB	769	03.5945.14	764	03.6017.B1ADA	766	03.6044.B1	764

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.6044.B1ADA	764	03.6275.14BDA	230	03.6805.14A1V	674	03.6816.14A	673	03.7004.14.CB	222	03.7320.40CCB	489
03.6045.14	764	03.6275.40B	230	03.6805.14BDA	674	03.6816.14A1V	673	03.7005.14	222	03.7320.40CDA	489
03.6045.14ADA	764	03.6275.40BCB	230	03.6805.40A	674	03.6816.14BDA	673	03.7005.14ADA	222	03.7320.40CNI	489
03.6045.18	764	03.6275.40BDA	230	03.6805.40A1V	674	03.6816.40A	673	03.7005.14.CB	222	03.7321.14C	489
03.6045.18ADA	764	03.6277.14B	230	03.6805.40BDA	674	03.6816.40A1V	673	03.7006.14	222	03.7321.14CCB	489
03.6045.B1	764	03.6277.14BCB	230	03.6806.14A	674	03.6816.40BDA	673	03.7006.14ADA	222	03.7321.14CDA	489
03.6045.B1ADA	764	03.6277.14BDA	230	03.6806.14A1V	674	03.6817.14A	673	03.7006.14.CB	222	03.7321.14CNI	489
03.6047.14	764	03.6277.40B	230	03.6806.14BDA	674	03.6817.14A1V	673	03.7007.14	222	03.7321.40C	489
03.6047.14ADA	764	03.6277.40BCB	230	03.6806.40A	674	03.6817.14BDA	673	03.7007.14ADA	222	03.7321.40CCB	489
03.6047.18	764	03.6277.40BDA	230	03.6806.40A1V	674	03.6817.40A	673	03.7007.14.CB	222	03.7321.40CDA	489
03.6047.18ADA	764	03.6278.14B	230	03.6806.40BDA	674	03.6817.40A1V	673	03.7300.14C	481	03.7321.40CNI	489
03.6047.B1	764	03.6278.14BCB	230	03.6807.14A	674	03.6817.40BDA	673	03.7300.14CCB	481	03.7324.14C	493
03.6047.B1ADA	764	03.6278.14BDA	230	03.6807.14A1V	674	03.6818.14A	675	03.7300.14CDA	481	03.7324.14CCB	493
03.6050.14	767	03.6278.40B	230	03.6807.14BDA	674	03.6818.14A1V	675	03.7300.14CNI	481	03.7324.14CDA	493
03.6050.14ADA	767	03.6278.40BCB	230	03.6807.40A	674	03.6818.14BDA	675	03.7300.40C	481	03.7324.14CNI	493
03.6050.18	767	03.6278.40BDA	230	03.6807.40A1V	674	03.6818.40A	675	03.7300.40CCB	481	03.7324.40C	493
03.6050.18ADA	767	03.6284.14C	229	03.6807.40BDA	674	03.6818.40A1V	675	03.7300.40CDA	481	03.7324.40CCB	493
03.6050.B1	767	03.6284.14CCB	229	03.6808.14A	674	03.6818.40BDA	675	03.7300.40CNI	481	03.7324.40CDA	493
03.6050.B1ADA	767	03.6284.14CDA	229	03.6808.14A1V	674	03.6819.14A	675	03.7301.14C	481	03.7324.40CNI	493
03.6051.14	767	03.6284.40C	229	03.6808.14BDA	674	03.6819.14A1V	675	03.7301.14CCB	481	03.7325.14C	493
03.6051.14ADA	767	03.6284.40CCB	229	03.6808.40A	674	03.6819.14BDA	675	03.7301.14CDA	481	03.7325.14CCB	493
03.6051.18	767	03.6284.40CDA	229	03.6808.40A1V	674	03.6819.40A	675	03.7301.14CNI	481	03.7325.14CDA	493
03.6051.18ADA	767	03.6285.14C	229	03.6808.40BDA	674	03.6819.40A1V	675	03.7301.40C	481	03.7325.14CNI	493
03.6051.B1	767	03.6285.14CCB	229	03.6809.1BA	670	03.6819.40BDA	675	03.7301.40CCB	481	03.7325.40C	493
03.6051.B1ADA	767	03.6285.14CDA	229	03.6809.1BA1V	670	03.6820.14A	675	03.7301.40CDA	481	03.7325.40CCB	493
03.6053.14	767	03.6285.40C	229	03.6809.1BBDA	670	03.6820.14A1V	675	03.7301.40CNI	481	03.7325.40CDA	493
03.6053.14ADA	767	03.6285.40CCB	229	03.6809.1CA	670	03.6820.14BDA	675	03.7304.14C	481	03.7325.40CNI	493
03.6053.18	767	03.6285.40CDA	229	03.6809.1CADA	670	03.6820.40A	675	03.7304.14CCB	481	03.7328.14C	493
03.6053.18ADA	767	03.6286.14C	229	03.6809.3BA	670	03.6820.40A1V	675	03.7304.14CDA	481	03.7328.14CCB	493
03.6053.B1	767	03.6286.14CCB	229	03.6809.3BA1V	670	03.6820.40BDA	675	03.7304.14CNI	481	03.7328.14CDA	493
03.6053.B1ADA	767	03.6286.14CDA	229	03.6809.3BBDA	670	03.6821.14A	675	03.7304.40C	481	03.7328.14CNI	493
03.6054.14	767	03.6286.40C	229	03.6809.3CA	670	03.6821.14A1V	675	03.7304.40CCB	481	03.7328.40C	493
03.6054.14ADA	767	03.6286.40CCB	229	03.6809.3CADA	670	03.6821.14BDA	675	03.7304.40CDA	481	03.7328.40CCB	493
03.6054.18	767	03.6286.40CDA	229	03.6810.1BA	670	03.6821.40A	675	03.7304.40CNI	481	03.7328.40CDA	493
03.6054.18ADA	767	03.6287.14C	229	03.6810.1BA1V	670	03.6821.40A1V	675	03.7305.14C	481	03.7328.40CNI	493
03.6054.B1	767	03.6287.14CCB	229	03.6810.1BBDA	670	03.6821.40BDA	675	03.7305.14CCB	481	03.7329.14C	493
03.6054.B1ADA	767	03.6287.14CDA	229	03.6810.1CA	670	03.6822.14A	675	03.7305.14CDA	481	03.7329.14CCB	493
03.6055.14	767	03.6287.40C	229	03.6810.1CADA	670	03.6822.14A1V	675	03.7305.14CNI	481	03.7329.14CDA	493
03.6055.14ADA	767	03.6287.40CCB	229	03.6810.3BA	670	03.6822.14BDA	675	03.7305.40C	481	03.7329.14CNI	493
03.6055.18	767	03.6287.40CDA	229	03.6810.3BA1V	670	03.6822.40A	675	03.7305.40CCB	481	03.7329.40C	493
03.6055.18ADA	767	03.6295.14A	246	03.6810.3BBDA	670	03.6822.40A1V	675	03.7305.40CDA	481	03.7329.40CCB	493
03.6055.B1	767	03.6295.14ACB	246	03.6810.3CA	670	03.6822.40BDA	675	03.7305.40CNI	481	03.7329.40CDA	493
03.6055.B1ADA	767	03.6295.14ADA	246	03.6810.3CADA	670	03.6823.14A	675	03.7308.14C	485	03.7329.40CNI	493
03.6057.14	767	03.6296.14A	246	03.6811.1BA	670	03.6823.14A1V	675	03.7308.14CCB	485	03.7350.14C	497
03.6057.14ADA	767	03.6296.14ACB	246	03.6811.1BA1V	670	03.6823.14BDA	675	03.7308.14CDA	485	03.7350.14CCB	497
03.6057.18	767	03.6296.14ADA	246	03.6811.1BBDA	670	03.6823.40A	675	03.7308.14CNI	485	03.7350.14CDA	497
03.6057.18ADA	767	03.6297.14A	246	03.6811.1CA	670	03.6823.40A1V	675	03.7308.40C	485	03.7350.14CNI	497
03.6057.B1	767	03.6297.14ACB	246	03.6811.1CADA	670	03.6823.40BDA	675	03.7308.40CCB	485	03.7350.40C	497
03.6057.B1ADA	767	03.6297.14ADA	246	03.6811.3BA	670	03.6824.06A	671	03.7308.40CDA	485	03.7350.40CCB	497
03.6170.05	743	03.6298.14A	246	03.6811.3BA1V	670	03.6824.06ADA	671	03.7308.40CNI	485	03.7350.40CDA	497
03.6170.14B	743	03.6298.14ACB	246	03.6811.3BBDA	670	03.6824.40A	671	03.7309.14C	485	03.7350.40CNI	497
03.6170.30B	743	03.6298.14ADA	246	03.6811.3CA	670	03.6824.40A1V	671	03.7309.14CCB	485	03.7351.14C	497
03.6170.GN	743	03.6302.14B	228	03.6811.3CADA	670	03.6824.40BDA	671	03.7309.14CDA	485	03.7351.14CCB	497
03.6174.05A	743	03.6302.14BCB	228	03.6812.1BA	676	03.6825.06A	671	03.7309.14CNI	485	03.7351.14CDA	497
03.6174.14B	743	03.6302.14CDA	228	03.6812.1BA1V	676	03.6825.06ADA	671	03.7309.40C	485	03.7351.14CNI	497
03.6174.30B	743	03.6303.14B	228	03.6812.1BBDA	676	03.6825.40A	671	03.7309.40CCB	485	03.7351.40C	497
03.6174.GNA	743	03.6303.14BCB	228	03.6812.1CA	676	03.6825.40A1V	671	03.7309.40CDA	485	03.7351.40CCB	497
03.6260.14ADA	247	03.6303.14CDA	228	03.6812.1CA1V	676	03.6825.40BDA	671	03.7309.40CNI	485	03.7351.40CDA	497
03.6260.14B	247	03.6305.14C	245	03.6812.1CBDA	676	03.6826.06A	671	03.7312.14C	485	03.7351.40CNI	497
03.6260.14.CB	247	03.6305.14CCB	245	03.6812.3BA	676	03.6826.06ADA	671	03.7312.14CCB	485	03.7354.14C	497
03.6261.14ADA	247	03.6305.14CDA	245	03.6812.3BA1V	676	03.6826.40A	671	03.7312.14CDA	485	03.7354.14CCB	497
03.6261.14B	247	03.6306.14C	245	03.6812.3BBDA	676	03.6826.40A1V	671	03.7312.14CNI	485	03.7354.14CDA	497
03.6261.14.CB	247	03.6306.14CCB	245	03.6812.3CA	676	03.6826.40BDA	671	03.7312.40C	485	03.7354.14CNI	497
03.6262.14ADA	247	03.6306.14CDA	245	03.6812.3CA1V	676	03.6827.06A	677	03.7312.40CCB	485	03.7354.40C	497
03.6262.14B	247	03.6800.14A	672	03.6812.3CBDA	676	03.6827.06A1V	677	03.7312.40CDA	485	03.7354.40CCB	497
03.6262.14.CB	247	03.6800.14A1V	672	03.6813.1BA	676	03.6827.06BDA	677	03.7312.40CNI	485	03.7354.40CDA	497
03.6263.14ADA	247	03.6800.14BDA	672	03.6813.1BA1V	676	03.6827.40A	677	03.7313.14C	485	03.7354.40CNI	497
03.6263.14B	247	03.6800.40A	672	03.6813.1BBDA	676	03.6827.40A1V	677	03.7313.14CCB	485	03.7355.14C	497
03.6263.14.CB	247	03.6800.40A1V	672	03.6813.1CA	676	03.6827.40BDA	677	03.7313.14CDA	485	03.7355.14CCB	497
03.6272.05D	248	03.6800.40BDA	672	03.6813.1CA1V	676	03.6828.06A	677	03.7313.14CNI	485	03.7355.14CDA	497
03.6272.05DCB	248	03.6801.14A	672	03.6813.1CBDA	676	03.6828.06A1V	677	03.7313.40C	485	03.7355.14CNI	497
03.6272.05EDA	248	03.6801.14A1V	672	03.6813.3BA	676	03.6828.06BDA	677	03.7313.40CCB	485	03.7355.40C	497
03.6272.14D	248	03.6801.14BDA	672	03.6813.3BA1V	676	03.6828.40A	677	03.7313.40CDA	485	03.7355.40CCB	497
03.6272.14DCB	248	03.6801.40A	672	03.6813.3BBDA	676	03.6828.40A1V	677	03.7313.40CNI	485	03.7355.40CDA	497
03.6272.14EDA	248	03.6801.40A1V	672	03.6813.3CA	676	03.6828.40BDA	677	03.7316.14C	489	03.7355.40CNI	497
03.6272.30D	248	03.6801.40BDA	672	03.6813.3CA1V	676	03.6829.06A	677	03.7316.14CCB	489	03.7358.14C	501
03.6272.30DCB	248	03.6802.14A	672	03.6813.3CBDA	676	03.6829.06A1V	677	03.7316.14CDA	489	03.7358.14CCB	501
03.6272.30EDA	248	03.6802.14A1V	672	03.6814.1BA	676	03.6829.06BDA	677	03.7316.14CNI	489	03.7358.14CDA	501
03.6273.05D	248	03.6802.14BDA	672	03.6814.1BA1V	676	03.6829.40A	677	03.7316.40C	489	03.7358.14CNI	501
03.6273.05DCB	248	03.6802.40A	672	03.6814.1BBDA	676	03.6829.40A1V	677	03.7316.40CCB	489	03.7358.40C	501
03.6273.05EDA	248	03.6802.40A1V	672	03.6814.1CA	676	03.6829.40BDA	677	03.7316.40CDA	489	03.7358.40CCB	501
03.6273.14D	248	03.6802.40BDA	672	03.6814.1CA1V	676	03.7000.14	222	03.7316.40CNI	489	03.7358.40CDA	501
03.6273.14DCB	248	03.6803.14A	674	03.6814.1CBDA	676	03.7000.14ADA	222	03.7317.14C	489	03.7358.40CNI	501
03.6273.14EDA	248	03.6803.14A1V	674	03.6814.3BA	676	03.7000.14.CB	222	03.7317.14CCB	489	03.7359.14C	501
03.6273.30D	248	03.6803.14BDA	674	03.6814.3BA1V	676	03.7001.14	222	03.7317.14CDA	489	03.7359.14CCB	501
03.6273.30DCB	248	03.6803.40A	674	03.6814.3BBDA	676	03.7001.14ADA	222	03.7317.14CNI	489	03.7359.14CDA	501
03.6273.30EDA	248	03.6803.40A1V	674	03.6814.3CA	676	03.7001.14.CB	222	03.7317.40C	489	03.7359.14CNI	501
03.6274.14B	230	03.6803.40BDA	674	03.6814.3CA1V	676	03.7002.14	222	03.7317.40CCB	489	03.7359.40C	501
03.6274.14BCB	230	03.6804.14A	674	03.6814.3CBDA	676	03.7002.14ADA	222	03.7317.40CDA	489	03.7359.40CCB	501
03.6274.14BDA	230	03.6804.14A1V	674	03.6815.14A	673	03.7002.14.CB	222	03.7317.40CNI	489	03.7359.40CDA	501
03.6274.40B	230	03.6804.14BDA	674	03.6815.14A1V	673	03.7003.14	222	03.7320.14C	489	03.7359.40CNI	501
03.6274.40BCB	230	03.6804.40A	674	03.6815.14BDA	673	03.7003.14ADA	222	03.7320.14CCB	489	03.7362.14C	501
03.6274.40BDA	230	03.6804.40A1V	674	03.6815.40A	673	03.7003.14.CB	222	03.7320.14CDA	489	03.7362.14CCB	501
03.6275.14B	230	03.6804.40BDA	674	03.6815.40A1V	673	03.7004.14	222	03.7320.14CNI	489	03.7362.14CDA	501
03.6275.14BCB	230	03.6805.14A	674	03.6815.40BDA	673	03.7004.14ADA	222	03.7320.40C	489	03.7362.14CNI	501

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.7362.40C	501	03.8004.14.DA	265	03.8033.05B1V	90	03.8045.05B	267	03.8055.05B	92	03.8074.40ADA	270
03.7362.40CCB	501	03.8005.14	265	03.8033.05B1V	266	03.8045.05B1V	91	03.8055.05B	268	03.8075.05B	94
03.7362.40CDA	501	03.8005.14.1V	265	03.8033.05BCB	90	03.8045.05B1V	267	03.8055.05B1V	92	03.8075.05B	270
03.7362.40CNI	501	03.8005.14.CB	265	03.8033.05BCB	266	03.8045.05BCB	91	03.8055.05B1V	268	03.8075.05B1V	94
03.7363.14C	501	03.8005.14.DA	265	03.8033.05BDA	90	03.8045.05BCB	267	03.8055.05BCB	92	03.8075.05B1V	270
03.7363.14CCB	501	03.8006.14	265	03.8033.05BDA	266	03.8045.05BDA	91	03.8055.05BCB	268	03.8075.05BCB	94
03.7363.14CDA	501	03.8006.14.1V	265	03.8033.14A	90	03.8045.05BDA	267	03.8055.05BDA	92	03.8075.05BCB	270
03.7363.14CNI	501	03.8006.14.CB	265	03.8033.14A	266	03.8045.14A	91	03.8055.05BDA	268	03.8075.05BDA	94
03.7363.40C	501	03.8006.14.DA	265	03.8033.14A1V	90	03.8045.14A	267	03.8055.14A	92	03.8075.05BDA	270
03.7363.40CCB	501	03.8007.14	265	03.8033.14A1V	266	03.8045.14A1V	91	03.8055.14A	268	03.8075.14A	94
03.7363.40CDA	501	03.8007.14.1V	265	03.8033.14ACB	90	03.8045.14A1V	267	03.8055.14A1V	92	03.8075.14A	270
03.7363.40CNI	501	03.8007.14.CB	265	03.8033.14ACB	266	03.8045.14ACB	91	03.8055.14A1V	268	03.8075.14A1V	94
03.7366.14C	505	03.8007.14.DA	265	03.8033.14ADA	90	03.8045.14ACB	267	03.8055.14ACB	92	03.8075.14A1V	270
03.7366.14CCB	505	03.8008.14	265	03.8033.14ADA	266	03.8045.14ADA	91	03.8055.14ACB	268	03.8075.14ACB	94
03.7366.14CDA	505	03.8008.14.1V	265	03.8033.40A	90	03.8045.14ADA	267	03.8055.14ADA	92	03.8075.14ACB	270
03.7366.14CNI	505	03.8008.14.CB	265	03.8033.40A	266	03.8045.40A	91	03.8055.14ADA	268	03.8075.14ADA	94
03.7366.40C	505	03.8008.14.DA	265	03.8033.40A1V	90	03.8045.40A	267	03.8055.40A	92	03.8075.14ADA	270
03.7366.40CCB	505	03.8009.14	265	03.8033.40A1V	266	03.8045.40A1V	91	03.8055.40A	268	03.8075.40A	94
03.7366.40CDA	505	03.8009.14.1V	265	03.8033.40ACB	90	03.8045.40A1V	267	03.8055.40A1V	92	03.8075.40A	270
03.7366.40CNI	505	03.8009.14.CB	265	03.8033.40ACB	266	03.8045.40ACB	91	03.8055.40A1V	268	03.8075.40A1V	94
03.7367.14C	505	03.8009.14.DA	265	03.8033.40ADA	90	03.8045.40ACB	267	03.8055.40ACB	92	03.8075.40A1V	270
03.7367.14CCB	505	03.8025.05A	272	03.8033.40ADA	266	03.8045.40ADA	91	03.8055.40ACB	268	03.8075.40ACB	94
03.7367.14CDA	505	03.8025.05A1V	272	03.8042.05B	91	03.8045.40ADA	267	03.8055.40ADA	92	03.8075.40ACB	270
03.7367.14CNI	505	03.8025.05ACB	272	03.8042.05B	267	03.8052.05B	92	03.8055.40ADA	268	03.8075.40ADA	94
03.7367.40C	505	03.8025.05ADA	272	03.8042.05B1V	91	03.8052.05B	268	03.8072.05B	94	03.8075.40ADA	270
03.7367.40CCB	505	03.8025.14	272	03.8042.05B1V	267	03.8052.05B1V	92	03.8072.05B	270	03.8076.05B	94
03.7367.40CDA	505	03.8025.14.1V	272	03.8042.05BCB	91	03.8052.05B1V	268	03.8072.05B1V	94	03.8076.05B	270
03.7367.40CNI	505	03.8025.14.CB	272	03.8042.05BCB	267	03.8052.05BCB	92	03.8072.05B1V	270	03.8076.05B1V	94
03.7370.14C	505	03.8025.14.DA	272	03.8042.05BDA	91	03.8052.05BCB	268	03.8072.05BCB	94	03.8076.05B1V	270
03.7370.14CCB	505	03.8025.40	272	03.8042.05BDA	267	03.8052.05BDA	92	03.8072.05BCB	270	03.8076.05BCB	94
03.7370.14CDA	505	03.8025.40.1V	272	03.8042.14A	91	03.8052.05BDA	268	03.8072.05BDA	94	03.8076.05BCB	270
03.7370.14CNI	505	03.8025.40.CB	272	03.8042.14A	267	03.8052.14A	92	03.8072.05BDA	270	03.8076.05BDA	94
03.7370.40C	505	03.8025.40.DA	272	03.8042.14A1V	91	03.8052.14A	268	03.8072.14A	94	03.8076.05BDA	270
03.7370.40CCB	505	03.8026.05A	272	03.8042.14A1V	267	03.8052.14A1V	92	03.8072.14A	270	03.8076.14A	94
03.7370.40CDA	505	03.8026.05A1V	272	03.8042.14ACB	91	03.8052.14A1V	268	03.8072.14A1V	94	03.8076.14A	270
03.7370.40CNI	505	03.8026.05ACB	272	03.8042.14ACB	267	03.8052.14ACB	92	03.8072.14A1V	270	03.8076.14A1V	94
03.7371.14C	505	03.8026.05ADA	272	03.8042.14ADA	91	03.8052.14ACB	268	03.8072.14ACB	94	03.8076.14A1V	270
03.7371.14CCB	505	03.8026.14	272	03.8042.14ADA	267	03.8052.14ADA	92	03.8072.14ACB	270	03.8076.14ACB	94
03.7371.14CDA	505	03.8026.14.1V	272	03.8042.40A	91	03.8052.14ADA	268	03.8072.14ADA	94	03.8076.14ACB	270
03.7371.14CNI	505	03.8026.14.CB	272	03.8042.40A	267	03.8052.40A	92	03.8072.14ADA	270	03.8076.14ADA	94
03.7371.40C	505	03.8026.14.DA	272	03.8042.40A1V	91	03.8052.40A	268	03.8072.40A	94	03.8076.14ADA	270
03.7371.40CCB	505	03.8026.40	272	03.8042.40A1V	267	03.8052.40A1V	92	03.8072.40A	270	03.8076.40A	94
03.7371.40CDA	505	03.8026.40.1V	272	03.8042.40ACB	91	03.8052.40A1V	268	03.8072.40A1V	94	03.8076.40A	270
03.7371.40CNI	505	03.8026.40.CB	272	03.8042.40ACB	267	03.8052.40ACB	92	03.8072.40A1V	270	03.8076.40A1V	94
03.7374.14C	509	03.8026.40.DA	272	03.8042.40ADA	91	03.8052.40ACB	268	03.8072.40ACB	94	03.8076.40A1V	270
03.7374.14CCB	509	03.8027.05A	272	03.8042.40ADA	267	03.8052.40ADA	92	03.8072.40ACB	270	03.8076.40ACB	94
03.7374.14CDA	509	03.8027.05A1V	272	03.8043.05B	91	03.8052.40ADA	268	03.8072.40ADA	94	03.8076.40ACB	270
03.7374.14CNI	509	03.8027.05ACB	272	03.8043.05B	267	03.8053.05B	92	03.8072.40ADA	270	03.8076.40ADA	94
03.7374.40C	509	03.8027.05ADA	272	03.8043.05B1V	91	03.8053.05B	268	03.8073.05B	94	03.8076.40ADA	270
03.7374.40CCB	509	03.8027.14	272	03.8043.05B1V	267	03.8053.05B1V	92	03.8073.05B	270	03.8077.05B	94
03.7374.40CDA	509	03.8027.14.1V	272	03.8043.05BCB	91	03.8053.05B1V	268	03.8073.05B1V	94	03.8077.05B	270
03.7374.40CNI	509	03.8027.14.CB	272	03.8043.05BCB	267	03.8053.05BCB	92	03.8073.05B1V	270	03.8077.05B1V	94
03.7375.14C	509	03.8027.14.DA	272	03.8043.05BDA	91	03.8053.05BCB	268	03.8073.05BCB	94	03.8077.05B1V	270
03.7375.14CCB	509	03.8027.40	272	03.8043.05BDA	267	03.8053.05BDA	92	03.8073.05BCB	270	03.8077.05BCB	94
03.7375.14CDA	509	03.8027.40.1V	272	03.8043.14A	91	03.8053.05BDA	268	03.8073.05BDA	94	03.8077.05BCB	270
03.7375.14CNI	509	03.8027.40.CB	272	03.8043.14A	267	03.8053.14A	92	03.8073.05BDA	270	03.8077.05BDA	94
03.7375.40C	509	03.8027.40.DA	272	03.8043.14A1V	91	03.8053.14A	268	03.8073.14A	94	03.8077.05BDA	270
03.7375.40CCB	509	03.8028.05A	272	03.8043.14A1V	267	03.8053.14A1V	92	03.8073.14A	270	03.8077.14A	94
03.7375.40CDA	509	03.8028.05A1V	272	03.8043.14ACB	91	03.8053.14A1V	268	03.8073.14A1V	94	03.8077.14A	270
03.7375.40CNI	509	03.8028.05ACB	272	03.8043.14ACB	267	03.8053.14ACB	92	03.8073.14A1V	270	03.8077.14A1V	94
03.7378.14C	509	03.8028.05ADA	272	03.8043.14ADA	91	03.8053.14ACB	268	03.8073.14ACB	94	03.8077.14A1V	270
03.7378.14CCB	509	03.8028.14	272	03.8043.14ADA	267	03.8053.14ADA	92	03.8073.14ACB	270	03.8077.14ACB	94
03.7378.14CDA	509	03.8028.14.1V	272	03.8043.40A	91	03.8053.14ADA	268	03.8073.14ADA	94	03.8077.14ACB	270
03.7378.14CNI	509	03.8028.14.CB	272	03.8043.40A	267	03.8053.40A	92	03.8073.14ADA	270	03.8077.14ADA	94
03.7378.40C	509	03.8028.14.DA	272	03.8043.40A1V	91	03.8053.40A	268	03.8073.40A	94	03.8077.14ADA	270
03.7378.40CCB	509	03.8028.40	272	03.8043.40A1V	267	03.8053.40A1V	92	03.8073.40A	270	03.8077.40A	94
03.7378.40CDA	509	03.8028.40.1V	272	03.8043.40ACB	91	03.8053.40A1V	268	03.8073.40A1V	94	03.8077.40A	270
03.7378.40CNI	509	03.8028.40.CB	272	03.8043.40ACB	267	03.8053.40ACB	92	03.8073.40A1V	270	03.8077.40A1V	94
03.7379.14C	509	03.8028.40.DA	272	03.8043.40ADA	91	03.8053.40ACB	268	03.8073.40ACB	94	03.8077.40A1V	270
03.7379.14CCB	509	03.8032.05B	90	03.8043.40ADA	267	03.8053.40ADA	92	03.8073.40ACB	270	03.8077.40ACB	94
03.7379.14CDA	509	03.8032.05B	266	03.8044.05B	91	03.8053.40ADA	268	03.8073.40ADA	94	03.8077.40ACB	270
03.7379.14CNI	509	03.8032.05B1V	90	03.8044.05B	267	03.8054.05B	92	03.8073.40ADA	270	03.8077.40ADA	94
03.7379.40C	509	03.8032.05B1V	266	03.8044.05B1V	91	03.8054.05B	268	03.8074.05B	94	03.8077.40ADA	270
03.7379.40CCB	509	03.8032.05BCB	90	03.8044.05B1V	267	03.8054.05B1V	92	03.8074.05B	270	03.8090.14	282
03.7379.40CDA	509	03.8032.05BCB	266	03.8044.05BCB	91	03.8054.05B1V	268	03.8074.05B1V	94	03.8090.14.CB	282
03.7379.40CNI	509	03.8032.05BDA	90	03.8044.05BCB	267	03.8054.05BCB	92	03.8074.05B1V	270	03.8090.40	282
03.8000.14	265	03.8032.05BDA	266	03.8044.05BDA	91	03.8054.05BCB	268	03.8074.05BCB	94	03.8090.40.CB	282
03.8000.14.1V	265	03.8032.14A	90	03.8044.05BDA	267	03.8054.05BDA	92	03.8074.05BCB	270	03.8091.14	282
03.8000.14.CB	265	03.8032.14A	266	03.8044.14A	91	03.8054.05BDA	268	03.8074.05BDA	94	03.8091.14.CB	282
03.8000.14.DA	265	03.8032.14A1V	90	03.8044.14A	267	03.8054.14A	92	03.8074.05BDA	270	03.8091.40	282
03.8001.14	265	03.8032.14A1V	266	03.8044.14A1V	91	03.8054.14A	268	03.8074.14A	94	03.8091.40.CB	282
03.8001.14.1V	265	03.8032.14ACB	90	03.8044.14A1V	267	03.8054.14A1V	92	03.8074.14A	270	03.8100.14A	88
03.8001.14.CB	265	03.8032.14ACB	266	03.8044.14ACB	91	03.8054.14A1V	268	03.8074.14A1V	94	03.8100.14A1V	88
03.8001.14.DA	265	03.8032.14ADA	90	03.8044.14ACB	267	03.8054.14ACB	92	03.8074.14A1V	270	03.8100.14ACB	88
03.8002.14	265	03.8032.14ADA	266	03.8044.14ADA	91	03.8054.14ACB	268	03.8074.14ACB	94	03.8100.14ADA	88
03.8002.14.1V	265	03.8032.40A	90	03.8044.14ADA	267	03.8054.14ADA	92	03.8074.14ACB	270	03.8100.40A	88
03.8002.14.CB	265	03.8032.40A	266	03.8044.40A	91	03.8054.14ADA	268	03.8074.14ADA	94	03.8100.40A1V	88
03.8002.14.DA	265	03.8032.40A1V	90	03.8044.40A	267	03.8054.40A	92	03.8074.14ADA	270	03.8100.40ACB	88
03.8003.14	265	03.8032.40A1V	266	03.8044.40A1V	91	03.8054.40A	268	03.8074.40A	94	03.8100.40ADA	88
03.8003.14.1V	265	03.8032.40ACB	90	03.8044.40A1V	267	03.8054.40A1V	92	03.8074.40A	270	03.8101.14A	88
03.8003.14.CB	265	03.8032.40ACB	266	03.8044.40ACB	91	03.8054.40A1V	268	03.8074.40A1V	94	03.8101.14A1V	88
03.8003.14.DA	265	03.8032.40ADA	90	03.8044.40ACB	267	03.8054.40ACB	92	03.8074.40A1V	270	03.8101.14ACB	88
03.8004.14	265	03.8032.40ADA	266	03.8044.40ADA	91	03.8054.40ACB	268	03.8074.40ACB	94	03.8101.14ADA	88
03.8004.14.1V	265	03.8033.05B	90	03.8044.40ADA	267	03.8054.40ADA	92	03.8074.40ACB	270	03.8101.40A	88
03.8004.14.CB	265	03.8033.05B	266	03.8045.05B	91	03.8054.40ADA	268	03.8074.40ADA	94	03.8101.40A1V	88

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.8101.40ACB	88	03.8130.FU.DA	104	03.8140.40ACB	106	03.8156.40.CB	269	03.8316.40C	453	03.8358.14CNI	465
03.8101.40ADA	88	03.8130.RC	104	03.8140.40ADA	106	03.8156.40.DA	93	03.8316.40CCB	453	03.8358.40C	465
03.8102.14A	88	03.8130.RC.1V	104	03.8141.14A	106	03.8156.40.DA	269	03.8316.40CDA	453	03.8358.40CCB	465
03.8102.14A1V	88	03.8130.RC.CB	104	03.8141.14A1V	106	03.8157.05A	93	03.8316.40CNI	453	03.8358.40CDA	465
03.8102.14ACB	88	03.8130.RC.DA	104	03.8141.14ACB	106	03.8157.05A	269	03.8317.14C	453	03.8358.40CNI	465
03.8102.14ADA	88	03.8131.00	104	03.8141.14ADA	106	03.8157.05A1V	93	03.8317.14CCB	453	03.8359.14C	465
03.8102.40A	88	03.8131.00.1V	104	03.8141.40A	106	03.8157.05A1V	269	03.8317.14CDA	453	03.8359.14CCB	465
03.8102.40A1V	88	03.8131.00.CB	104	03.8141.40A1V	106	03.8157.05ACB	93	03.8317.14CNI	453	03.8359.14CDA	465
03.8102.40ACB	88	03.8131.00.DA	104	03.8141.40ACB	106	03.8157.05ACB	269	03.8317.40C	453	03.8359.14CNI	465
03.8102.40ADA	88	03.8131.FU	104	03.8141.40ADA	106	03.8157.05ADA	93	03.8317.40CCB	453	03.8359.40C	465
03.8105.14A	88	03.8131.FU.1V	104	03.8142.14A	106	03.8157.05ADA	269	03.8317.40CDA	453	03.8359.40CCB	465
03.8105.14A1V	88	03.8131.FU.CB	104	03.8142.14A1V	106	03.8157.14	93	03.8317.40CNI	453	03.8359.40CDA	465
03.8105.14ACB	88	03.8131.FU.DA	104	03.8142.14ACB	106	03.8157.14	269	03.8320.14C	453	03.8359.40CNI	465
03.8105.14ADA	88	03.8131.RC	104	03.8142.14ADA	106	03.8157.14.1V	93	03.8320.14CCB	453	03.8362.14C	465
03.8105.40A	88	03.8131.RC.1V	104	03.8142.40A	106	03.8157.14.1V	269	03.8320.14CDA	453	03.8362.14CCB	465
03.8105.40A1V	88	03.8131.RC.CB	104	03.8142.40A1V	106	03.8157.14.CB	93	03.8320.14CNI	453	03.8362.14CDA	465
03.8105.40ACB	88	03.8131.RC.DA	104	03.8142.40ACB	106	03.8157.14.CB	269	03.8320.40C	453	03.8362.14CNI	465
03.8105.40ADA	88	03.8132.00	104	03.8142.40ADA	106	03.8157.14.DA	93	03.8320.40CCB	453	03.8362.40C	465
03.8106.14A	88	03.8132.00.1V	104	03.8143.14A	106	03.8157.14.DA	269	03.8320.40CDA	453	03.8362.40CCB	465
03.8106.14A1V	88	03.8132.00.CB	104	03.8143.14A1V	106	03.8157.40	93	03.8320.40CNI	453	03.8362.40CDA	465
03.8106.14ACB	88	03.8132.00.DA	104	03.8143.14ACB	106	03.8157.40	269	03.8321.14C	453	03.8362.40CNI	465
03.8106.14ADA	88	03.8132.FU	104	03.8143.14ADA	106	03.8157.40.1V	93	03.8321.14CCB	453	03.8363.14C	465
03.8106.40A	88	03.8132.FU.1V	104	03.8143.40A	106	03.8157.40.1V	269	03.8321.14CDA	453	03.8363.14CCB	465
03.8106.40A1V	88	03.8132.FU.CB	104	03.8143.40A1V	106	03.8157.40.CB	93	03.8321.14CNI	453	03.8363.14CDA	465
03.8106.40ACB	88	03.8132.FU.DA	104	03.8143.40ACB	106	03.8157.40.CB	269	03.8321.40C	453	03.8363.14CNI	465
03.8106.40ADA	88	03.8132.RC	104	03.8143.40ADA	106	03.8157.40.DA	93	03.8321.40CCB	453	03.8363.40C	465
03.8107.14A	88	03.8132.RC.1V	104	03.8154.05A	93	03.8157.40.DA	269	03.8321.40CDA	453	03.8363.40CCB	465
03.8107.14A1V	88	03.8132.RC.CB	104	03.8154.05A	269	03.8300.14C	441	03.8321.40CNI	453	03.8363.40CDA	465
03.8107.14ACB	88	03.8132.RC.DA	104	03.8154.05A1V	93	03.8300.14CCB	441	03.8324.14C	457	03.8363.40CNI	465
03.8107.14ADA	88	03.8133.00	104	03.8154.05A1V	269	03.8300.14CDA	441	03.8324.14CCB	457	03.8366.14C	473
03.8107.40A	88	03.8133.00.1V	104	03.8154.05ACB	93	03.8300.14CNI	441	03.8324.14CDA	457	03.8366.14CCB	473
03.8107.40A1V	88	03.8133.00.CB	104	03.8154.05ACB	269	03.8300.40C	441	03.8324.14CNI	457	03.8366.14CDA	473
03.8107.40ACB	88	03.8133.00.DA	104	03.8154.05ADA	93	03.8300.40CCB	441	03.8324.40C	457	03.8366.14CNI	473
03.8107.40ADA	88	03.8133.FU	104	03.8154.05ADA	269	03.8300.40CDA	441	03.8324.40CCB	457	03.8366.40C	473
03.8110.14A	89	03.8133.FU.1V	104	03.8154.14	93	03.8300.40CNI	441	03.8324.40CDA	457	03.8366.40CCB	473
03.8110.14A1V	89	03.8133.FU.CB	104	03.8154.14	269	03.8301.14C	441	03.8324.40CNI	457	03.8366.40CDA	473
03.8110.14ACB	89	03.8133.FU.DA	104	03.8154.14.1V	93	03.8301.14CCB	441	03.8325.14C	457	03.8366.40CNI	473
03.8110.14ADA	89	03.8133.RC	104	03.8154.14.1V	269	03.8301.14CDA	441	03.8325.14CCB	457	03.8367.14C	473
03.8110.40A	89	03.8133.RC.1V	104	03.8154.14.CB	93	03.8301.14CNI	441	03.8325.14CDA	457	03.8367.14CCB	473
03.8110.40A1V	89	03.8133.RC.CB	104	03.8154.14.CB	269	03.8301.40C	441	03.8325.14CNI	457	03.8367.14CDA	473
03.8110.40ACB	89	03.8133.RC.DA	104	03.8154.14.DA	93	03.8301.40CCB	441	03.8325.40C	457	03.8367.14CNI	473
03.8110.40ADA	89	03.8135.00	104	03.8154.14.DA	269	03.8301.40CDA	441	03.8325.40CCB	457	03.8367.40C	473
03.8111.14A	89	03.8135.00.1V	104	03.8154.40	93	03.8301.40CNI	441	03.8325.40CDA	457	03.8367.40CCB	473
03.8111.14A1V	89	03.8135.00.CB	104	03.8154.40	269	03.8304.14C	441	03.8325.40CNI	457	03.8367.40CDA	473
03.8111.14ACB	89	03.8135.00.DA	104	03.8154.40.1V	93	03.8304.14CCB	441	03.8328.14C	457	03.8367.40CNI	473
03.8111.14ADA	89	03.8135.FU	104	03.8154.40.1V	269	03.8304.14CDA	441	03.8328.14CCB	457	03.8370.14C	473
03.8111.40A	89	03.8135.FU.1V	104	03.8154.40.CB	93	03.8304.14CNI	441	03.8328.14CDA	457	03.8370.14CCB	473
03.8111.40A1V	89	03.8135.FU.CB	104	03.8154.40.CB	269	03.8304.40C	441	03.8328.14CNI	457	03.8370.14CDA	473
03.8111.40ACB	89	03.8135.FU.DA	104	03.8154.40.DA	93	03.8304.40CCB	441	03.8328.40C	457	03.8370.14CNI	473
03.8111.40ADA	89	03.8135.RC	104	03.8154.40.DA	269	03.8304.40CDA	441	03.8328.40CCB	457	03.8370.40C	473
03.8112.14A	89	03.8135.RC.1V	104	03.8155.05A	93	03.8304.40CNI	441	03.8328.40CDA	457	03.8370.40CCB	473
03.8112.14A1V	89	03.8135.RC.CB	104	03.8155.05A	269	03.8305.14C	441	03.8328.40CNI	457	03.8370.40CDA	473
03.8112.14ACB	89	03.8135.RC.DA	104	03.8155.05A1V	93	03.8305.14CCB	441	03.8329.14C	457	03.8370.40CNI	473
03.8112.14ADA	89	03.8136.00	105	03.8155.05A1V	269	03.8305.14CDA	441	03.8329.14CCB	457	03.8371.14C	473
03.8112.40A	89	03.8136.00.1V	105	03.8155.05ACB	93	03.8305.14CNI	441	03.8329.14CDA	457	03.8371.14CCB	473
03.8112.40A1V	89	03.8136.00.CB	105	03.8155.05ACB	269	03.8305.40C	441	03.8329.14CNI	457	03.8371.14CDA	473
03.8112.40ACB	89	03.8136.00.DA	105	03.8155.05ADA	93	03.8305.40CCB	441	03.8329.40C	457	03.8371.14CNI	473
03.8112.40ADA	89	03.8136.FU	105	03.8155.05ADA	269	03.8305.40CDA	441	03.8329.40CCB	457	03.8371.40C	473
03.8115.14A	89	03.8136.FU.1V	105	03.8155.14	93	03.8305.40CNI	441	03.8329.40CDA	457	03.8371.40CCB	473
03.8115.14A1V	89	03.8136.FU.CB	105	03.8155.14	269	03.8308.14C	445	03.8329.40CNI	457	03.8371.40CDA	473
03.8115.14ACB	89	03.8136.FU.DA	105	03.8155.14.1V	93	03.8308.14CCB	445	03.8350.14C	461	03.8371.40CNI	473
03.8115.14ADA	89	03.8136.RC	105	03.8155.14.1V	269	03.8308.14CDA	445	03.8350.14CCB	461	03.8374.14C	477
03.8115.40A	89	03.8136.RC.1V	105	03.8155.14.CB	93	03.8308.14CNI	445	03.8350.14CDA	461	03.8374.14CCB	477
03.8115.40A1V	89	03.8136.RC.CB	105	03.8155.14.CB	269	03.8308.40C	445	03.8350.14CNI	461	03.8374.14CDA	477
03.8115.40ACB	89	03.8136.RC.DA	105	03.8155.14.DA	93	03.8308.40CCB	445	03.8350.40C	461	03.8374.14CNI	477
03.8115.40ADA	89	03.8137.00	104	03.8155.14.DA	269	03.8308.40CDA	445	03.8350.40CCB	461	03.8374.40C	477
03.8116.14A	89	03.8137.00.1V	104	03.8155.40	93	03.8308.40CNI	445	03.8350.40CDA	461	03.8374.40CCB	477
03.8116.14A1V	89	03.8137.00.CB	104	03.8155.40	269	03.8309.14C	445	03.8350.40CNI	461	03.8374.40CDA	477
03.8116.14ACB	89	03.8137.00.DA	104	03.8155.40.1V	93	03.8309.14CCB	445	03.8351.14C	461	03.8374.40CNI	477
03.8116.14ADA	89	03.8137.FU	104	03.8155.40.1V	269	03.8309.14CDA	445	03.8351.14CCB	461	03.8375.14C	477
03.8116.40A	89	03.8137.FU.1V	104	03.8155.40.CB	93	03.8309.14CNI	445	03.8351.14CDA	461	03.8375.14CCB	477
03.8116.40A1V	89	03.8137.FU.CB	104	03.8155.40.CB	269	03.8309.40C	445	03.8351.14CNI	461	03.8375.14CDA	477
03.8116.40ACB	89	03.8137.FU.DA	104	03.8155.40.DA	93	03.8309.40CCB	445	03.8351.40C	461	03.8375.14CNI	477
03.8116.40ADA	89	03.8137.RC	104	03.8155.40.DA	269	03.8309.40CDA	445	03.8351.40CCB	461	03.8375.40C	477
03.8117.14A	89	03.8137.RC.1V	104	03.8156.05A	93	03.8309.40CNI	445	03.8351.40CDA	461	03.8375.40CCB	477
03.8117.14A1V	89	03.8137.RC.CB	104	03.8156.05A	269	03.8312.14C	445	03.8351.40CNI	461	03.8375.40CDA	477
03.8117.14ACB	89	03.8137.RC.DA	104	03.8156.05A1V	93	03.8312.14CCB	445	03.8354.14C	461	03.8375.40CNI	477
03.8117.14ADA	89	03.8138.00	105	03.8156.05A1V	269	03.8312.14CDA	445	03.8354.14CCB	461	03.8378.14C	477
03.8117.40A	89	03.8138.00.1V	105	03.8156.05ACB	93	03.8312.14CNI	445	03.8354.14CDA	461	03.8378.14CCB	477
03.8117.40A1V	89	03.8138.00.CB	105	03.8156.05ACB	269	03.8312.40C	445	03.8354.14CNI	461	03.8378.14CDA	477
03.8117.40ACB	89	03.8138.00.DA	105	03.8156.05ADA	93	03.8312.40CCB	445	03.8354.40C	461	03.8378.14CNI	477
03.8117.40ADA	89	03.8138.FU	105	03.8156.05ADA	269	03.8312.40CDA	445	03.8354.40CCB	461	03.8378.40C	477
03.8120.14	86	03.8138.FU.1V	105	03.8156.14	93	03.8312.40CNI	445	03.8354.40CDA	461	03.8378.40CCB	477
03.8120.40	86	03.8138.FU.CB	105	03.8156.14	269	03.8313.14C	445	03.8354.40CNI	461	03.8378.40CDA	477
03.8121.14	86	03.8138.FU.DA	105	03.8156.14.1V	93	03.8313.14CCB	445	03.8355.14C	461	03.8378.40CNI	477
03.8121.40	86	03.8138.RC	105	03.8156.14.1V	269	03.8313.14CDA	445	03.8355.14CCB	461	03.8379.14C	477
03.8122.14	86	03.8138.RC.1V	105	03.8156.14.CB	93	03.8313.14CNI	445	03.8355.14CDA	461	03.8379.14CCB	477
03.8122.40	86	03.8138.RC.CB	105	03.8156.14.CB	269	03.8313.40C	445	03.8355.14CNI	461	03.8379.14CDA	477
03.8130.00	104	03.8138.RC.DA	105	03.8156.14.DA	93	03.8313.40CCB	445	03.8355.40C	461	03.8379.14CNI	477
03.8130.00.1V	104	03.8140.14A	106	03.8156.14.DA	269	03.8313.40CDA	445	03.8355.40CCB	461	03.8379.40C	477
03.8130.00.CB	104	03.8140.14A1V	106	03.8156.40	93	03.8313.40CNI	445	03.8355.40CDA	461	03.8379.40CCB	477
03.8130.00.DA	104	03.8140.14ACB	106	03.8156.40	269	03.8316.14C	453	03.8355.40CNI	461	03.8379.40CDA	477
03.8130.FU	104	03.8140.14ADA	106	03.8156.40.1V	93	03.8316.14CCB	453	03.8358.14C	465	03.8379.40CNI	477
03.8130.FU.1V	104	03.8140.40A	106	03.8156.40.1V	269	03.8316.14CDA	453	03.8358.14CCB	465	03.8500.14.1V	77
03.8130.FU.CB	104	03.8140.40A1V	106	03.8156.40.CB	93	03.8316.14CNI	453	03.8358.14CDA	465	03.8500.14.CB	77

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.8500.14.DA	77	03.8522.GN	78	03.8637.14C	526	03.8829.14CNI	442	03.8853.14CDA	458	03.8877.14CCB	474
03.8500.18.1V	77	03.8522.GO	78	03.8637.40C	526	03.8829.40C	442	03.8853.14CNI	458	03.8877.14CDA	474
03.8500.18.CB	77	03.8522.M5	78	03.8637.ERC	526	03.8829.40CCB	442	03.8853.40C	458	03.8877.14CNI	474
03.8500.18.DA	77	03.8600.14C	524	03.8637.ESC	526	03.8829.40CDA	442	03.8853.40CCB	458	03.8877.40C	474
03.8500.GN.1V	77	03.8600.40C	524	03.8640.14C	524	03.8829.40CNI	442	03.8853.40CDA	458	03.8877.40CCB	474
03.8500.GN.CB	77	03.8600.ERC	524	03.8640.40C	524	03.8832.14C	442	03.8853.40CNI	458	03.8877.40CDA	474
03.8500.GN.DA	77	03.8600.ESC	524	03.8640.ERC	524	03.8832.14CCB	442	03.8856.14C	458	03.8877.40CNI	474
03.8500.GO.1V	77	03.8601.14C	525	03.8640.ESC	524	03.8832.14CDA	442	03.8856.14CCB	458	03.8880.14C	474
03.8500.GO.CB	77	03.8601.40C	525	03.8641.14C	525	03.8832.14CNI	442	03.8856.14CDA	458	03.8880.14CCB	474
03.8500.GO.DA	77	03.8601.ERC	525	03.8641.40C	525	03.8832.40C	442	03.8856.14CNI	458	03.8880.14CDA	474
03.8500.M5.1V	77	03.8601.ESC	525	03.8641.ERC	525	03.8832.40CCB	442	03.8856.40C	458	03.8880.14CNI	474
03.8500.M5.CB	77	03.8602.14C	525	03.8641.ESC	525	03.8832.40CDA	442	03.8856.40CCB	458	03.8880.40C	474
03.8500.M5.DA	77	03.8602.40C	525	03.8642.14C	525	03.8832.40CNI	442	03.8856.40CDA	458	03.8880.40CCB	474
03.8501.14.1V	77	03.8602.ERC	525	03.8642.40C	525	03.8833.14C	442	03.8856.40CNI	458	03.8880.40CDA	474
03.8501.14.CB	77	03.8602.ESC	525	03.8642.ERC	525	03.8833.14CCB	442	03.8857.14C	458	03.8880.40CNI	474
03.8501.14.DA	77	03.8603.14C	524	03.8642.ESC	525	03.8833.14CDA	442	03.8857.14CCB	458	03.8881.14C	474
03.8501.18.1V	77	03.8603.40C	524	03.8643.14C	524	03.8833.14CNI	442	03.8857.14CDA	458	03.8881.14CCB	474
03.8501.18.CB	77	03.8603.ERC	524	03.8643.40C	524	03.8833.40C	442	03.8857.14CNI	458	03.8881.14CDA	474
03.8501.18.DA	77	03.8603.ESC	524	03.8643.ERC	524	03.8833.40CCB	442	03.8857.40C	458	03.8881.14CNI	474
03.8501.GN.1V	77	03.8604.14C	525	03.8643.ESC	524	03.8833.40CDA	442	03.8857.40CCB	458	03.8881.40C	474
03.8501.GN.CB	77	03.8604.40C	525	03.8644.14C	525	03.8833.40CNI	442	03.8857.40CDA	458	03.8881.40CCB	474
03.8501.GN.DA	77	03.8604.ERC	525	03.8644.40C	525	03.8836.14C	450	03.8857.40CNI	458	03.8881.40CDA	474
03.8501.GO.1V	77	03.8604.ESC	525	03.8644.ERC	525	03.8836.14CCB	450	03.8860.14C	462	03.8881.40CNI	474
03.8501.GO.CB	77	03.8605.14C	525	03.8644.ESC	525	03.8836.14CDA	450	03.8860.14CCB	462	03.8884.14C	478
03.8501.GO.DA	77	03.8605.40C	525	03.8645.14C	525	03.8836.14CNI	450	03.8860.14CDA	462	03.8884.14CCB	478
03.8501.M5.1V	77	03.8605.ERC	525	03.8645.40C	525	03.8836.40C	450	03.8860.14CNI	462	03.8884.14CDA	478
03.8501.M5.CB	77	03.8605.ESC	525	03.8645.ERC	525	03.8836.40CCB	450	03.8860.40C	462	03.8884.14CNI	478
03.8501.M5.DA	77	03.8606.14C	524	03.8645.ESC	525	03.8836.40CDA	450	03.8860.40CCB	462	03.8884.40C	478
03.8505.14.1V	77	03.8606.40C	524	03.8646.14C	526	03.8836.40CNI	450	03.8860.40CDA	462	03.8884.40CCB	478
03.8505.14.CB	77	03.8606.ERC	524	03.8646.40C	526	03.8837.14C	450	03.8860.40CNI	462	03.8884.40CDA	478
03.8505.14.DA	77	03.8606.ESC	524	03.8646.ERC	526	03.8837.14CCB	450	03.8861.14C	462	03.8884.40CNI	478
03.8505.18.1V	77	03.8607.14C	525	03.8646.ESC	526	03.8837.14CDA	450	03.8861.14CCB	462	03.8885.14C	478
03.8505.18.CB	77	03.8607.40C	525	03.8647.14C	526	03.8837.14CNI	450	03.8861.14CDA	462	03.8885.14CCB	478
03.8505.18.DA	77	03.8607.ERC	525	03.8647.40C	526	03.8837.40C	450	03.8861.14CNI	462	03.8885.14CDA	478
03.8505.GN.1V	77	03.8607.ESC	525	03.8647.ERC	526	03.8837.40CCB	450	03.8861.40C	462	03.8885.14CNI	478
03.8505.GN.CB	77	03.8608.14C	525	03.8647.ESC	526	03.8837.40CDA	450	03.8861.40CCB	462	03.8885.40C	478
03.8505.GN.DA	77	03.8608.40C	525	03.8671.14C	524	03.8837.40CNI	450	03.8861.40CDA	462	03.8885.40CCB	478
03.8505.GO.1V	77	03.8608.ERC	525	03.8671.40C	524	03.8840.14C	450	03.8861.40CNI	462	03.8885.40CDA	478
03.8505.GO.CB	77	03.8608.ESC	525	03.8671.ERC	524	03.8840.14CCB	450	03.8864.14C	462	03.8885.40CNI	478
03.8505.GO.DA	77	03.8610.14C	524	03.8671.ESC	524	03.8840.14CDA	450	03.8864.14CCB	462	03.8888.14C	478
03.8505.M5.1V	77	03.8610.40C	524	03.8672.14C	525	03.8840.14CNI	450	03.8864.14CDA	462	03.8888.14CCB	478
03.8505.M5.CB	77	03.8610.ERC	524	03.8672.40C	525	03.8840.40C	450	03.8864.14CNI	462	03.8888.14CDA	478
03.8505.M5.DA	77	03.8610.ESC	524	03.8672.ERC	525	03.8840.40CCB	450	03.8864.40C	462	03.8888.14CNI	478
03.8506.14.1V	77	03.8611.14C	525	03.8672.ESC	525	03.8840.40CDA	450	03.8864.40CCB	462	03.8888.40C	478
03.8506.14.CB	77	03.8611.40C	525	03.8673.14C	525	03.8840.40CNI	450	03.8864.40CDA	462	03.8888.40CCB	478
03.8506.14.DA	77	03.8611.ERC	525	03.8673.40C	525	03.8841.14C	450	03.8864.40CNI	462	03.8888.40CDA	478
03.8506.18.1V	77	03.8611.ESC	525	03.8673.ERC	525	03.8841.14CCB	450	03.8865.14C	462	03.8888.40CNI	478
03.8506.18.CB	77	03.8612.14C	525	03.8673.ESC	525	03.8841.14CDA	450	03.8865.14CCB	462	03.8889.14C	478
03.8506.18.DA	77	03.8612.40C	525	03.8674.14C	526	03.8841.14CNI	450	03.8865.14CDA	462	03.8889.14CCB	478
03.8506.GN.1V	77	03.8612.ERC	525	03.8674.40C	526	03.8841.40C	450	03.8865.14CNI	462	03.8889.14CDA	478
03.8506.GN.CB	77	03.8612.ESC	525	03.8674.ERC	526	03.8841.40CCB	450	03.8865.40C	462	03.8889.14CNI	478
03.8506.GN.DA	77	03.8613.14C	524	03.8674.ESC	526	03.8841.40CDA	450	03.8865.40CCB	462	03.8889.40C	478
03.8506.GO.1V	77	03.8613.40C	524	03.8820.14C	438	03.8841.40CNI	450	03.8865.40CDA	462	03.8889.40CCB	478
03.8506.GO.CB	77	03.8613.ERC	524	03.8820.14CCB	438	03.8844.14C	454	03.8865.40CNI	462	03.8889.40CDA	478
03.8506.GO.DA	77	03.8613.ESC	524	03.8820.14CDA	438	03.8844.14CCB	454	03.8868.14C	470	03.8889.40CNI	478
03.8506.M5.1V	77	03.8614.14C	525	03.8820.14CNI	438	03.8844.14CDA	454	03.8868.14CCB	470	03.8892.14C	482
03.8506.M5.CB	77	03.8614.40C	525	03.8820.40C	438	03.8844.14CNI	454	03.8868.14CDA	470	03.8892.14CCB	482
03.8506.M5.DA	77	03.8614.ERC	525	03.8820.40CCB	438	03.8844.40C	454	03.8868.14CNI	470	03.8892.14CDA	482
03.8510.14	78	03.8614.ESC	525	03.8820.40CDA	438	03.8844.40CCB	454	03.8868.40C	470	03.8892.14CNI	482
03.8510.18	78	03.8615.14C	525	03.8820.40CNI	438	03.8844.40CDA	454	03.8868.40CCB	470	03.8892.40C	482
03.8510.GN	78	03.8615.40C	525	03.8821.14C	438	03.8844.40CNI	454	03.8868.40CDA	470	03.8892.40CCB	482
03.8510.GO	78	03.8615.ERC	525	03.8821.14CCB	438	03.8845.14C	454	03.8868.40CNI	470	03.8892.40CDA	482
03.8510.M5	78	03.8615.ESC	525	03.8821.14CDA	438	03.8845.14CCB	454	03.8869.14C	470	03.8892.40CNI	482
03.8511.14	78	03.8616.14C	524	03.8821.14CNI	438	03.8845.14CDA	454	03.8869.14CCB	470	03.8893.14C	482
03.8511.18	78	03.8616.40C	524	03.8821.40C	438	03.8845.14CNI	454	03.8869.14CDA	470	03.8893.14CCB	482
03.8511.GN	78	03.8616.ERC	524	03.8821.40CCB	438	03.8845.40C	454	03.8869.14CNI	470	03.8893.14CDA	482
03.8511.GO	78	03.8616.ESC	524	03.8821.40CDA	438	03.8845.40CCB	454	03.8869.40C	470	03.8893.14CNI	482
03.8511.M5	78	03.8617.14C	525	03.8821.40CNI	438	03.8845.40CDA	454	03.8869.40CCB	470	03.8893.40C	482
03.8512.14	78	03.8617.40C	525	03.8824.14C	438	03.8845.40CNI	454	03.8869.40CDA	470	03.8893.40CCB	482
03.8512.18	78	03.8617.ERC	525	03.8824.14CCB	438	03.8848.14C	454	03.8869.40CNI	470	03.8893.40CDA	482
03.8512.GN	78	03.8617.ESC	525	03.8824.14CDA	438	03.8848.14CCB	454	03.8872.14C	470	03.8893.40CNI	482
03.8512.GO	78	03.8618.14C	525	03.8824.14CNI	438	03.8848.14CDA	454	03.8872.14CCB	470	03.8896.14C	482
03.8512.M5	78	03.8618.40C	525	03.8824.40C	438	03.8848.14CNI	454	03.8872.14CDA	470	03.8896.14CCB	482
03.8513.14	78	03.8618.ERC	525	03.8824.40CCB	438	03.8848.40C	454	03.8872.14CNI	470	03.8896.14CDA	482
03.8513.18	78	03.8618.ESC	525	03.8824.40CDA	438	03.8848.40CCB	454	03.8872.40C	470	03.8896.14CNI	482
03.8513.GN	78	03.8630.14C	526	03.8824.40CNI	438	03.8848.40CDA	454	03.8872.40CCB	470	03.8896.40C	482
03.8513.GO	78	03.8630.40C	526	03.8825.14C	438	03.8848.40CNI	454	03.8872.40CDA	470	03.8896.40CCB	482
03.8513.M5	78	03.8630.ERC	526	03.8825.14CCB	438	03.8849.14C	454	03.8872.40CNI	470	03.8896.40CDA	482
03.8514.14	78	03.8630.ESC	526	03.8825.14CDA	438	03.8849.14CCB	454	03.8873.14C	470	03.8896.40CNI	482
03.8514.18	78	03.8631.14C	526	03.8825.14CNI	438	03.8849.14CDA	454	03.8873.14CCB	470	03.8897.14C	482
03.8514.GN	78	03.8631.40C	526	03.8825.40C	438	03.8849.14CNI	454	03.8873.14CDA	470	03.8897.14CCB	482
03.8514.GO	78	03.8631.ERC	526	03.8825.40CCB	438	03.8849.40C	454	03.8873.14CNI	470	03.8897.14CDA	482
03.8514.M5	78	03.8631.ESC	526	03.8825.40CDA	438	03.8849.40CCB	454	03.8873.40C	470	03.8897.14CNI	482
03.8520.14	78	03.8633.14C	526	03.8825.40CNI	438	03.8849.40CDA	454	03.8873.40CCB	470	03.8897.40C	482
03.8520.18	78	03.8633.40C	526	03.8828.14C	442	03.8849.40CNI	454	03.8873.40CDA	470	03.8897.40CCB	482
03.8520.GN	78	03.8633.ERC	526	03.8828.14CCB	442	03.8852.14C	458	03.8873.40CNI	470	03.8897.40CDA	482
03.8520.GO	78	03.8633.ESC	526	03.8828.14CDA	442	03.8852.14CCB	458	03.8876.14C	474	03.8897.40CNI	482
03.8520.M5	78	03.8635.14C	526	03.8828.14CNI	442	03.8852.14CDA	458	03.8876.14CCB	474	03.8900.14C	486
03.8521.14	78	03.8635.40C	526	03.8828.40C	442	03.8852.14CNI	458	03.8876.14CDA	474	03.8900.14CCB	486
03.8521.18	78	03.8635.ERC	526	03.8828.40CCB	442	03.8852.40C	458	03.8876.14CNI	474	03.8900.14CDA	486
03.8521.GN	78	03.8635.ESC	526	03.8828.40CDA	442	03.8852.40CCB	458	03.8876.40C	474	03.8900.14CNI	486
03.8521.GO	78	03.8636.14C	526	03.8828.40CNI	442	03.8852.40CDA	458	03.8876.40CCB	474	03.8900.40C	486
03.8521.M5	78	03.8636.40C	526	03.8829.14C	442	03.8852.40CNI	458	03.8876.40CDA	474	03.8900.40CCB	486
03.8522.14	78	03.8636.ERC	526	03.8829.14CCB	442	03.8853.14C	458	03.8876.40CNI	474	03.8900.40CDA	486
03.8522.18	78	03.8636.ESC	526	03.8829.14CDA	442	03.8853.14CCB	458	03.8877.14C	474	03.8900.40CNI	486

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.8901.14C	486	03.8924.40CNI	498	03.8949.14C	240	03.9111.40CCB	439	03.9141.40C	451	03.9171.14CNI	455
03.8901.14CCB	486	03.8925.14C	498	03.8949.14CCB	240	03.9111.40CDA	439	03.9141.40CCB	451	03.9171.40C	455
03.8901.14CDA	486	03.8925.14CCB	498	03.8949.14CDA	240	03.9111.40CNI	439	03.9141.40CDA	451	03.9171.40CCB	455
03.8901.14CNI	486	03.8925.14CDA	498	03.8949.40C	240	03.9115.14C	440	03.9141.40CNI	451	03.9171.40CDA	455
03.8901.40C	486	03.8925.14CNI	498	03.8949.40CCB	240	03.9115.14CCB	440	03.9145.14C	452	03.9171.40CNI	455
03.8901.40CCB	486	03.8925.40C	498	03.8949.40CDA	240	03.9115.14CDA	440	03.9145.14CCB	452	03.9175.14C	456
03.8901.40CDA	486	03.8925.40CCB	498	03.8952.14C	240	03.9115.14CNI	440	03.9145.14CDA	452	03.9175.14CCB	456
03.8901.40CNI	486	03.8925.40CDA	498	03.8952.14CCB	240	03.9115.40C	440	03.9145.14CNI	452	03.9175.14CDA	456
03.8904.14C	486	03.8925.40CNI	498	03.8952.14CDA	240	03.9115.40CCB	440	03.9145.40C	452	03.9175.14CNI	456
03.8904.14CCB	486	03.8928.14C	498	03.8952.40C	240	03.9115.40CDA	440	03.9145.40CCB	452	03.9175.40C	456
03.8904.14CDA	486	03.8928.14CCB	498	03.8952.40CCB	240	03.9115.40CNI	440	03.9145.40CDA	452	03.9175.40CCB	456
03.8904.14CNI	486	03.8928.14CDA	498	03.8952.40CDA	240	03.9116.14C	440	03.9145.40CNI	452	03.9175.40CDA	456
03.8904.40C	486	03.8928.14CNI	498	03.8953.14C	240	03.9116.14CCB	440	03.9146.14C	452	03.9175.40CNI	456
03.8904.40CCB	486	03.8928.40C	498	03.8953.14CCB	240	03.9116.14CDA	440	03.9146.14CCB	452	03.9176.14C	456
03.8904.40CDA	486	03.8928.40CCB	498	03.8953.14CDA	240	03.9116.14CNI	440	03.9146.14CDA	452	03.9176.14CCB	456
03.8904.40CNI	486	03.8928.40CDA	498	03.8953.40C	240	03.9116.40C	440	03.9146.14CNI	452	03.9176.14CDA	456
03.8905.14C	486	03.8928.40CNI	498	03.8953.40CCB	240	03.9116.40CCB	440	03.9146.40C	452	03.9176.14CNI	456
03.8905.14CCB	486	03.8929.14C	498	03.8953.40CDA	240	03.9116.40CDA	440	03.9146.40CCB	452	03.9176.40C	456
03.8905.14CDA	486	03.8929.14CCB	498	03.8956.14C	512	03.9116.40CNI	440	03.9146.40CDA	452	03.9176.40CCB	456
03.8905.14CNI	486	03.8929.14CDA	498	03.8956.14CDA	512	03.9120.14C	443	03.9146.40CNI	452	03.9176.40CDA	456
03.8905.40C	486	03.8929.14CNI	498	03.8956.40C	512	03.9120.14CCB	443	03.9150.14C	451	03.9176.40CNI	456
03.8905.40CCB	486	03.8929.40C	498	03.8956.40CDA	512	03.9120.14CDA	443	03.9150.14CCB	451	03.9200.14C	459
03.8905.40CDA	486	03.8929.40CCB	498	03.8957.14C	512	03.9120.14CNI	443	03.9150.14CDA	451	03.9200.14CCB	459
03.8905.40CNI	486	03.8929.40CDA	498	03.8957.14CDA	512	03.9120.40C	443	03.9150.14CNI	451	03.9200.14CDA	459
03.8908.14C	490	03.8929.40CNI	498	03.8957.40C	512	03.9120.40CCB	443	03.9150.40C	451	03.9200.14CNI	459
03.8908.14CCB	490	03.8932.14C	502	03.8957.40CDA	512	03.9120.40CDA	443	03.9150.40CCB	451	03.9200.40C	459
03.8908.14CDA	490	03.8932.14CCB	502	03.8960.14C	512	03.9120.40CNI	443	03.9150.40CDA	451	03.9200.40CCB	459
03.8908.14CNI	490	03.8932.14CDA	502	03.8960.14CDA	512	03.9121.14C	443	03.9150.40CNI	451	03.9200.40CDA	459
03.8908.40C	490	03.8932.14CNI	502	03.8960.40C	512	03.9121.14CCB	443	03.9151.14C	451	03.9200.40CNI	459
03.8908.40CCB	490	03.8932.40C	502	03.8960.40CDA	512	03.9121.14CDA	443	03.9151.14CCB	451	03.9201.14C	459
03.8908.40CDA	490	03.8932.40CCB	502	03.8961.14C	512	03.9121.14CNI	443	03.9151.14CDA	451	03.9201.14CCB	459
03.8908.40CNI	490	03.8932.40CDA	502	03.8961.14CDA	512	03.9121.40C	443	03.9151.14CNI	451	03.9201.14CDA	459
03.8909.14C	490	03.8932.40CNI	502	03.8961.40C	512	03.9121.40CCB	443	03.9151.40C	451	03.9201.14CNI	459
03.8909.14CCB	490	03.8933.14C	502	03.8961.40CDA	512	03.9121.40CDA	443	03.9151.40CCB	451	03.9201.40C	459
03.8909.14CDA	490	03.8933.14CCB	502	03.8964.14C	512	03.9121.40CNI	443	03.9151.40CDA	451	03.9201.40CCB	459
03.8909.14CNI	490	03.8933.14CDA	502	03.8964.14CDA	512	03.9125.14C	444	03.9151.40CNI	451	03.9201.40CDA	459
03.8909.40C	490	03.8933.14CNI	502	03.8964.40C	512	03.9125.14CCB	444	03.9155.14C	452	03.9201.40CNI	459
03.8909.40CCB	490	03.8933.40C	502	03.8964.40CDA	512	03.9125.14CDA	444	03.9155.14CCB	452	03.9205.14C	460
03.8909.40CDA	490	03.8933.40CCB	502	03.8965.14C	512	03.9125.14CNI	444	03.9155.14CDA	452	03.9205.14CCB	460
03.8909.40CNI	490	03.8933.40CDA	502	03.8965.14CDA	512	03.9125.40C	444	03.9155.14CNI	452	03.9205.14CDA	460
03.8912.14C	490	03.8933.40CNI	502	03.8965.40C	512	03.9125.40CCB	444	03.9155.40C	452	03.9205.14CNI	460
03.8912.14CCB	490	03.8936.14C	502	03.8965.40CDA	512	03.9125.40CDA	444	03.9155.40CCB	452	03.9205.40C	460
03.8912.14CDA	490	03.8936.14CCB	502	03.8968.14C	512	03.9125.40CNI	444	03.9155.40CDA	452	03.9205.40CCB	460
03.8912.14CNI	490	03.8936.14CDA	502	03.8968.14CDA	512	03.9126.14C	444	03.9155.40CNI	452	03.9205.40CDA	460
03.8912.40C	490	03.8936.14CNI	502	03.8968.40C	512	03.9126.14CCB	444	03.9156.14C	452	03.9205.40CNI	460
03.8912.40CCB	490	03.8936.40C	502	03.8968.40CDA	512	03.9126.14CDA	444	03.9156.14CCB	452	03.9206.14C	460
03.8912.40CDA	490	03.8936.40CCB	502	03.8969.14C	512	03.9126.14CNI	444	03.9156.14CDA	452	03.9206.14CCB	460
03.8912.40CNI	490	03.8936.40CDA	502	03.8969.14CDA	512	03.9126.40C	444	03.9156.14CNI	452	03.9206.14CDA	460
03.8913.14C	490	03.8936.40CNI	502	03.8969.40C	512	03.9126.40CCB	444	03.9156.40C	452	03.9206.14CNI	460
03.8913.14CCB	490	03.8937.14C	502	03.8969.40CDA	512	03.9126.40CDA	444	03.9156.40CCB	452	03.9206.40C	460
03.8913.14CDA	490	03.8937.14CCB	502	03.9100.14C	439	03.9126.40CNI	444	03.9156.40CDA	452	03.9206.40CCB	460
03.8913.14CNI	490	03.8937.14CDA	502	03.9100.14CCB	439	03.9130.14C	443	03.9156.40CNI	452	03.9206.40CDA	460
03.8913.40C	490	03.8937.14CNI	502	03.9100.14CDA	439	03.9130.14CCB	443	03.9160.14C	455	03.9206.40CNI	460
03.8913.40CCB	490	03.8937.40C	502	03.9100.14CNI	439	03.9130.14CDA	443	03.9160.14CCB	455	03.9210.14C	459
03.8913.40CDA	490	03.8937.40CCB	502	03.9100.40C	439	03.9130.14CNI	443	03.9160.14CDA	455	03.9210.14CCB	459
03.8913.40CNI	490	03.8937.40CDA	502	03.9100.40CCB	439	03.9130.40C	443	03.9160.14CNI	455	03.9210.14CDA	459
03.8916.14C	494	03.8937.40CNI	502	03.9100.40CDA	439	03.9130.40CCB	443	03.9160.40C	455	03.9210.14CNI	459
03.8916.14CCB	494	03.8940.14C	506	03.9100.40CNI	439	03.9130.40CDA	443	03.9160.40CCB	455	03.9210.40C	459
03.8916.14CDA	494	03.8940.14CCB	506	03.9101.14C	439	03.9130.40CNI	443	03.9160.40CDA	455	03.9210.40CCB	459
03.8916.14CNI	494	03.8940.14CDA	506	03.9101.14CCB	439	03.9131.14C	443	03.9160.40CNI	455	03.9210.40CDA	459
03.8916.40C	494	03.8940.14CNI	506	03.9101.14CDA	439	03.9131.14CCB	443	03.9161.14C	455	03.9210.40CNI	459
03.8916.40CCB	494	03.8940.40C	506	03.9101.14CNI	439	03.9131.14CDA	443	03.9161.14CCB	455	03.9211.14C	459
03.8916.40CDA	494	03.8940.40CCB	506	03.9101.40C	439	03.9131.14CNI	443	03.9161.14CDA	455	03.9211.14CCB	459
03.8916.40CNI	494	03.8940.40CDA	506	03.9101.40CCB	439	03.9131.40C	443	03.9161.14CNI	455	03.9211.14CDA	459
03.8917.14C	494	03.8940.40CNI	506	03.9101.40CDA	439	03.9131.40CCB	443	03.9161.40C	455	03.9211.14CNI	459
03.8917.14CCB	494	03.8941.14C	506	03.9101.40CNI	439	03.9131.40CDA	443	03.9161.40CCB	455	03.9211.40C	459
03.8917.14CDA	494	03.8941.14CCB	506	03.9105.14C	440	03.9131.40CNI	443	03.9161.40CDA	455	03.9211.40CCB	459
03.8917.14CNI	494	03.8941.14CDA	506	03.9105.14CCB	440	03.9135.14C	444	03.9161.40CNI	455	03.9211.40CDA	459
03.8917.40C	494	03.8941.14CNI	506	03.9105.14CDA	440	03.9135.14CCB	444	03.9165.14C	456	03.9211.40CNI	459
03.8917.40CCB	494	03.8941.40C	506	03.9105.14CNI	440	03.9135.14CDA	444	03.9165.14CCB	456	03.9215.14C	460
03.8917.40CDA	494	03.8941.40CCB	506	03.9105.40C	440	03.9135.14CNI	444	03.9165.14CDA	456	03.9215.14CCB	460
03.8917.40CNI	494	03.8941.40CDA	506	03.9105.40CCB	440	03.9135.40C	444	03.9165.14CNI	456	03.9215.14CDA	460
03.8920.14C	494	03.8941.40CNI	506	03.9105.40CDA	440	03.9135.40CCB	444	03.9165.40C	456	03.9215.14CNI	460
03.8920.14CCB	494	03.8944.14C	506	03.9105.40CNI	440	03.9135.40CDA	444	03.9165.40CCB	456	03.9215.40C	460
03.8920.14CDA	494	03.8944.14CCB	506	03.9106.14C	440	03.9135.40CNI	444	03.9165.40CDA	456	03.9215.40CCB	460
03.8920.14CNI	494	03.8944.14CDA	506	03.9106.14CCB	440	03.9136.14C	444	03.9165.40CNI	456	03.9215.40CDA	460
03.8920.40C	494	03.8944.14CNI	506	03.9106.14CDA	440	03.9136.14CCB	444	03.9166.14C	456	03.9215.40CNI	460
03.8920.40CCB	494	03.8944.40C	506	03.9106.14CNI	440	03.9136.14CDA	444	03.9166.14CCB	456	03.9216.14C	460
03.8920.40CDA	494	03.8944.40CCB	506	03.9106.40C	440	03.9136.14CNI	444	03.9166.14CDA	456	03.9216.14CCB	460
03.8920.40CNI	494	03.8944.40CDA	506	03.9106.40CCB	440	03.9136.40C	444	03.9166.14CNI	456	03.9216.14CDA	460
03.8921.14C	494	03.8944.40CNI	506	03.9106.40CDA	440	03.9136.40CCB	444	03.9166.40C	456	03.9216.14CNI	460
03.8921.14CCB	494	03.8945.14C	506	03.9106.40CNI	440	03.9136.40CDA	444	03.9166.40CCB	456	03.9216.40C	460
03.8921.14CDA	494	03.8945.14CCB	506	03.9110.14C	439	03.9136.40CNI	444	03.9166.40CDA	456	03.9216.40CCB	460
03.8921.14CNI	494	03.8945.14CDA	506	03.9110.14CCB	439	03.9140.14C	451	03.9166.40CNI	456	03.9216.40CDA	460
03.8921.40C	494	03.8945.14CNI	506	03.9110.14CDA	439	03.9140.14CCB	451	03.9170.14C	455	03.9216.40CNI	460
03.8921.40CCB	494	03.8945.40C	506	03.9110.14CNI	439	03.9140.14CDA	451	03.9170.14CCB	455	03.9220.14C	463
03.8921.40CDA	494	03.8945.40CCB	506	03.9110.40C	439	03.9140.14CNI	451	03.9170.14CDA	455	03.9220.14CCB	463
03.8921.40CNI	494	03.8945.40CDA	506	03.9110.40CCB	439	03.9140.40C	451	03.9170.14CNI	455	03.9220.14CDA	463
03.8924.14C	498	03.8945.40CNI	506	03.9110.40CDA	439	03.9140.40CCB	451	03.9170.40C	455	03.9220.14CNI	463
03.8924.14CCB	498	03.8948.14C	240	03.9110.40CNI	439	03.9140.40CDA	451	03.9170.40CCB	455	03.9220.40C	463
03.8924.14CDA	498	03.8948.14CCB	240	03.9111.14C	439	03.9140.40CNI	451	03.9170.40CDA	455	03.9220.40CCB	463
03.8924.14CNI	498	03.8948.14CDA	240	03.9111.14CCB	439	03.9141.14C	451	03.9170.40CNI	455	03.9220.40CDA	463
03.8924.40C	498	03.8948.40C	240	03.9111.14CDA	439	03.9141.14CCB	451	03.9171.14C	455	03.9220.40CNI	463
03.8924.40CCB	498	03.8948.40CCB	240	03.9111.14CNI	439	03.9141.14CDA	451	03.9171.14CCB	455	03.9221.14C	463
03.8924.40CDA	498	03.8948.40CDA	240	03.9111.40C	439	03.9141.14CNI	451	03.9171.14CDA	455	03.9221.14CCB	463

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.9221.14CDA	463	03.9251.14CCB	471	03.9301.14C	479	03.9330.40CNI	483	03.9360.40CDA	491	03.9410.40CCB	495
03.9221.14CNI	463	03.9251.14CDA	471	03.9301.14CCB	479	03.9331.14C	483	03.9360.40CNI	491	03.9410.40CDA	495
03.9221.40C	463	03.9251.14CNI	471	03.9301.14CDA	479	03.9331.14CCB	483	03.9361.14C	491	03.9410.40CNI	495
03.9221.40CCB	463	03.9251.40C	471	03.9301.14CNI	479	03.9331.14CDA	483	03.9361.14CCB	491	03.9411.14C	495
03.9221.40CDA	463	03.9251.40CCB	471	03.9301.40C	479	03.9331.14CNI	483	03.9361.14CDA	491	03.9411.14CCB	495
03.9221.40CNI	463	03.9251.40CDA	471	03.9301.40CCB	479	03.9331.40C	483	03.9361.14CNI	491	03.9411.14CDA	495
03.9225.14C	464	03.9251.40CNI	471	03.9301.40CDA	479	03.9331.40CCB	483	03.9361.40C	491	03.9411.14CNI	495
03.9225.14CCB	464	03.9255.14C	472	03.9301.40CNI	479	03.9331.40CDA	483	03.9361.40CCB	491	03.9411.40C	495
03.9225.14CDA	464	03.9255.14CCB	472	03.9305.14C	480	03.9331.40CNI	483	03.9361.40CDA	491	03.9411.40CCB	495
03.9225.14CNI	464	03.9255.14CDA	472	03.9305.14CCB	480	03.9335.14C	484	03.9361.40CNI	491	03.9411.40CDA	495
03.9225.40C	464	03.9255.14CNI	472	03.9305.14CDA	480	03.9335.14CCB	484	03.9365.14C	492	03.9411.40CNI	495
03.9225.40CCB	464	03.9255.40C	472	03.9305.14CNI	480	03.9335.14CDA	484	03.9365.14CCB	492	03.9415.14C	496
03.9225.40CDA	464	03.9255.40CCB	472	03.9305.40C	480	03.9335.14CNI	484	03.9365.14CDA	492	03.9415.14CCB	496
03.9225.40CNI	464	03.9255.40CDA	472	03.9305.40CCB	480	03.9335.40C	484	03.9365.14CNI	492	03.9415.14CDA	496
03.9226.14C	464	03.9255.40CNI	472	03.9305.40CDA	480	03.9335.40CCB	484	03.9365.40C	492	03.9415.14CNI	496
03.9226.14CCB	464	03.9256.14C	472	03.9305.40CNI	480	03.9335.40CDA	484	03.9365.40CCB	492	03.9415.40C	496
03.9226.14CDA	464	03.9256.14CCB	472	03.9306.14C	480	03.9335.40CNI	484	03.9365.40CDA	492	03.9415.40CCB	496
03.9226.14CNI	464	03.9256.14CDA	472	03.9306.14CCB	480	03.9336.14C	484	03.9365.40CNI	492	03.9415.40CDA	496
03.9226.40C	464	03.9256.14CNI	472	03.9306.14CDA	480	03.9336.14CCB	484	03.9366.14C	492	03.9415.40CNI	496
03.9226.40CCB	464	03.9256.40C	472	03.9306.14CNI	480	03.9336.14CDA	484	03.9366.14CCB	492	03.9416.14C	496
03.9226.40CDA	464	03.9256.40CCB	472	03.9306.40C	480	03.9336.14CNI	484	03.9366.14CDA	492	03.9416.14CCB	496
03.9226.40CNI	464	03.9256.40CDA	472	03.9306.40CCB	480	03.9336.40C	484	03.9366.14CNI	492	03.9416.14CDA	496
03.9230.14C	463	03.9256.40CNI	472	03.9306.40CDA	480	03.9336.40CCB	484	03.9366.40C	492	03.9416.14CNI	496
03.9230.14CCB	463	03.9260.14C	475	03.9306.40CNI	480	03.9336.40CDA	484	03.9366.40CCB	492	03.9416.40C	496
03.9230.14CDA	463	03.9260.14CCB	475	03.9310.14C	479	03.9336.40CNI	484	03.9366.40CDA	492	03.9416.40CCB	496
03.9230.14CNI	463	03.9260.14CDA	475	03.9310.14CCB	479	03.9340.14C	487	03.9366.40CNI	492	03.9416.40CDA	496
03.9230.40C	463	03.9260.14CNI	475	03.9310.14CDA	479	03.9340.14CCB	487	03.9370.14C	491	03.9416.40CNI	496
03.9230.40CCB	463	03.9260.40C	475	03.9310.14CNI	479	03.9340.14CDA	487	03.9370.14CCB	491	03.9420.14C	499
03.9230.40CDA	463	03.9260.40CCB	475	03.9310.40C	479	03.9340.14CNI	487	03.9370.14CDA	491	03.9420.14CCB	499
03.9230.40CNI	463	03.9260.40CDA	475	03.9310.40CCB	479	03.9340.40C	487	03.9370.14CNI	491	03.9420.14CDA	499
03.9231.14C	463	03.9260.40CNI	475	03.9310.40CDA	479	03.9340.40CCB	487	03.9370.40C	491	03.9420.14CNI	499
03.9231.14CCB	463	03.9261.14C	475	03.9310.40CNI	479	03.9340.40CDA	487	03.9370.40CCB	491	03.9420.40C	499
03.9231.14CDA	463	03.9261.14CCB	475	03.9311.14C	479	03.9340.40CNI	487	03.9370.40CDA	491	03.9420.40CCB	499
03.9231.14CNI	463	03.9261.14CDA	475	03.9311.14CCB	479	03.9341.14C	487	03.9370.40CNI	491	03.9420.40CDA	499
03.9231.40C	463	03.9261.14CNI	475	03.9311.14CDA	479	03.9341.14CCB	487	03.9371.14C	491	03.9420.40CNI	499
03.9231.40CCB	463	03.9261.40C	475	03.9311.14CNI	479	03.9341.14CDA	487	03.9371.14CCB	491	03.9421.14C	499
03.9231.40CDA	463	03.9261.40CCB	475	03.9311.40C	479	03.9341.14CNI	487	03.9371.14CDA	491	03.9421.14CCB	499
03.9231.40CNI	463	03.9261.40CDA	475	03.9311.40CCB	479	03.9341.40C	487	03.9371.14CNI	491	03.9421.14CDA	499
03.9235.14C	464	03.9261.40CNI	475	03.9311.40CDA	479	03.9341.40CCB	487	03.9371.40C	491	03.9421.14CNI	499
03.9235.14CCB	464	03.9265.14C	476	03.9311.40CNI	479	03.9341.40CDA	487	03.9371.40CCB	491	03.9421.40C	499
03.9235.14CDA	464	03.9265.14CCB	476	03.9315.14C	480	03.9341.40CNI	487	03.9371.40CDA	491	03.9421.40CCB	499
03.9235.14CNI	464	03.9265.14CDA	476	03.9315.14CCB	480	03.9345.14C	488	03.9371.40CNI	491	03.9421.40CDA	499
03.9235.40C	464	03.9265.14CNI	476	03.9315.14CDA	480	03.9345.14CCB	488	03.9375.14C	492	03.9421.40CNI	499
03.9235.40CCB	464	03.9265.40C	476	03.9315.14CNI	480	03.9345.14CDA	488	03.9375.14CCB	492	03.9425.14C	500
03.9235.40CDA	464	03.9265.40CCB	476	03.9315.40C	480	03.9345.14CNI	488	03.9375.14CDA	492	03.9425.14CCB	500
03.9235.40CNI	464	03.9265.40CDA	476	03.9315.40CCB	480	03.9345.40C	488	03.9375.14CNI	492	03.9425.14CDA	500
03.9236.14C	464	03.9265.40CNI	476	03.9315.40CDA	480	03.9345.40CCB	488	03.9375.40C	492	03.9425.14CNI	500
03.9236.14CCB	464	03.9266.14C	476	03.9315.40CNI	480	03.9345.40CDA	488	03.9375.40CCB	492	03.9425.40C	500
03.9236.14CDA	464	03.9266.14CCB	476	03.9316.14C	480	03.9345.40CNI	488	03.9375.40CDA	492	03.9425.40CCB	500
03.9236.14CNI	464	03.9266.14CDA	476	03.9316.14CCB	480	03.9346.14C	488	03.9375.40CNI	492	03.9425.40CDA	500
03.9236.40C	464	03.9266.14CNI	476	03.9316.14CDA	480	03.9346.14CCB	488	03.9376.14C	492	03.9425.40CNI	500
03.9236.40CCB	464	03.9266.40C	476	03.9316.14CNI	480	03.9346.14CDA	488	03.9376.14CCB	492	03.9426.14C	500
03.9236.40CDA	464	03.9266.40CCB	476	03.9316.40C	480	03.9346.14CNI	488	03.9376.14CDA	492	03.9426.14CCB	500
03.9236.40CNI	464	03.9266.40CDA	476	03.9316.40CCB	480	03.9346.40C	488	03.9376.14CNI	492	03.9426.14CDA	500
03.9240.14C	471	03.9266.40CNI	476	03.9316.40CDA	480	03.9346.40CCB	488	03.9376.40C	492	03.9426.14CNI	500
03.9240.14CCB	471	03.9270.14C	475	03.9316.40CNI	480	03.9346.40CDA	488	03.9376.40CCB	492	03.9426.40C	500
03.9240.14CDA	471	03.9270.14CCB	475	03.9320.14C	483	03.9346.40CNI	488	03.9376.40CDA	492	03.9426.40CCB	500
03.9240.14CNI	471	03.9270.14CDA	475	03.9320.14CCB	483	03.9350.14C	487	03.9376.40CNI	492	03.9426.40CDA	500
03.9240.40C	471	03.9270.14CNI	475	03.9320.14CDA	483	03.9350.14CCB	487	03.9400.14C	495	03.9426.40CNI	500
03.9240.40CCB	471	03.9270.40C	475	03.9320.14CNI	483	03.9350.14CDA	487	03.9400.14CCB	495	03.9430.14C	499
03.9240.40CDA	471	03.9270.40CCB	475	03.9320.40C	483	03.9350.14CNI	487	03.9400.14CDA	495	03.9430.14CCB	499
03.9240.40CNI	471	03.9270.40CDA	475	03.9320.40CCB	483	03.9350.40C	487	03.9400.14CNI	495	03.9430.14CDA	499
03.9241.14C	471	03.9270.40CNI	475	03.9320.40CDA	483	03.9350.40CCB	487	03.9400.40C	495	03.9430.14CNI	499
03.9241.14CCB	471	03.9271.14C	475	03.9320.40CNI	483	03.9350.40CDA	487	03.9400.40CCB	495	03.9430.40C	499
03.9241.14CDA	471	03.9271.14CCB	475	03.9321.14C	483	03.9350.40CNI	487	03.9400.40CDA	495	03.9430.40CCB	499
03.9241.14CNI	471	03.9271.14CDA	475	03.9321.14CCB	483	03.9351.14C	487	03.9400.40CNI	495	03.9430.40CDA	499
03.9241.40C	471	03.9271.14CNI	475	03.9321.14CDA	483	03.9351.14CCB	487	03.9401.14C	495	03.9430.40CNI	499
03.9241.40CCB	471	03.9271.40C	475	03.9321.14CNI	483	03.9351.14CDA	487	03.9401.14CCB	495	03.9431.14C	499
03.9241.40CDA	471	03.9271.40CCB	475	03.9321.40C	483	03.9351.14CNI	487	03.9401.14CDA	495	03.9431.14CCB	499
03.9241.40CNI	471	03.9271.40CDA	475	03.9321.40CCB	483	03.9351.40C	487	03.9401.14CNI	495	03.9431.14CDA	499
03.9245.14C	472	03.9271.40CNI	475	03.9321.40CDA	483	03.9351.40CCB	487	03.9401.40C	495	03.9431.14CNI	499
03.9245.14CCB	472	03.9275.14C	476	03.9321.40CNI	483	03.9351.40CDA	487	03.9401.40CCB	495	03.9431.40C	499
03.9245.14CDA	472	03.9275.14CCB	476	03.9325.14C	484	03.9351.40CNI	487	03.9401.40CDA	495	03.9431.40CCB	499
03.9245.14CNI	472	03.9275.14CDA	476	03.9325.14CCB	484	03.9355.14C	488	03.9401.40CNI	495	03.9431.40CDA	499
03.9245.40C	472	03.9275.14CNI	476	03.9325.14CDA	484	03.9355.14CCB	488	03.9405.14C	496	03.9431.40CNI	499
03.9245.40CCB	472	03.9275.40C	476	03.9325.14CNI	484	03.9355.14CDA	488	03.9405.14CCB	496	03.9435.14C	500
03.9245.40CDA	472	03.9275.40CCB	476	03.9325.40C	484	03.9355.14CNI	488	03.9405.14CDA	496	03.9435.14CCB	500
03.9245.40CNI	472	03.9275.40CDA	476	03.9325.40CCB	484	03.9355.40C	488	03.9405.14CNI	496	03.9435.14CDA	500
03.9246.14C	472	03.9275.40CNI	476	03.9325.40CDA	484	03.9355.40CCB	488	03.9405.40C	496	03.9435.14CNI	500
03.9246.14CCB	472	03.9276.14C	476	03.9325.40CNI	484	03.9355.40CDA	488	03.9405.40CCB	496	03.9435.40C	500
03.9246.14CDA	472	03.9276.14CCB	476	03.9326.14C	484	03.9355.40CNI	488	03.9405.40CDA	496	03.9435.40CCB	500
03.9246.14CNI	472	03.9276.14CDA	476	03.9326.14CCB	484	03.9356.14C	488	03.9405.40CNI	496	03.9435.40CDA	500
03.9246.40C	472	03.9276.14CNI	476	03.9326.14CDA	484	03.9356.14CCB	488	03.9406.14C	496	03.9435.40CNI	500
03.9246.40CCB	472	03.9276.40C	476	03.9326.14CNI	484	03.9356.14CDA	488	03.9406.14CCB	496	03.9436.14C	500
03.9246.40CDA	472	03.9276.40CCB	476	03.9326.40C	484	03.9356.14CNI	488	03.9406.14CDA	496	03.9436.14CCB	500
03.9246.40CNI	472	03.9276.40CDA	476	03.9326.40CCB	484	03.9356.40C	488	03.9406.14CNI	496	03.9436.14CDA	500
03.9250.14C	471	03.9276.40CNI	476	03.9326.40CDA	484	03.9356.40CCB	488	03.9406.40C	496	03.9436.14CNI	500
03.9250.14CCB	471	03.9300.14C	479	03.9326.40CNI	484	03.9356.40CDA	488	03.9406.40CCB	496	03.9436.40C	500
03.9250.14CDA	471	03.9300.14CCB	479	03.9330.14C	483	03.9356.40CNI	488	03.9406.40CDA	496	03.9436.40CCB	500
03.9250.14CNI	471	03.9300.14CDA	479	03.9330.14CCB	483	03.9360.14C	491	03.9406.40CNI	496	03.9436.40CDA	500
03.9250.40C	471	03.9300.14CNI	479	03.9330.14CDA	483	03.9360.14CCB	491	03.9410.14C	495	03.9436.40CNI	500
03.9250.40CCB	471	03.9300.40C	479	03.9330.14CNI	483	03.9360.14CDA	491	03.9410.14CCB	495	03.9440.14C	503
03.9250.40CDA	471	03.9300.40CCB	479	03.9330.40C	483	03.9360.14CNI	491	03.9410.14CDA	495	03.9440.14CCB	503
03.9250.40CNI	471	03.9300.40CDA	479	03.9330.40CCB	483	03.9360.40C	491	03.9410.14CNI	495	03.9440.14CDA	503
03.9251.14C	471	03.9300.40CNI	479	03.9330.40CDA	483	03.9360.40CCB	491	03.9410.40C	495	03.9440.14CNI	503

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.9440.40C	503	03.9470.14CNI	507	03.9625.40CCB	242	03.9761.40CDA	515	03.9903.14CDA	510	03.9953.40A	544
03.9440.40CCB	503	03.9470.40C	507	03.9625.40CDA	242	03.9764.14C	515	03.9903.14CNI	510	03.9953.ER	544
03.9440.40CDA	503	03.9470.40CCB	507	03.9626.14C	242	03.9764.14CDA	515	03.9903.40C	510	03.9953.ES	544
03.9440.40CNI	503	03.9470.40CDA	507	03.9626.14CCB	242	03.9764.40C	515	03.9903.40CCB	510	03.9954.14	544
03.9441.14C	503	03.9470.40CNI	507	03.9626.14CDA	242	03.9764.40CDA	515	03.9903.40CDA	510	03.9954.40A	544
03.9441.14CCB	503	03.9471.14C	507	03.9626.40C	242	03.9765.14C	515	03.9903.40CNI	510	03.9954.ER	544
03.9441.14CDA	503	03.9471.14CCB	507	03.9626.40CCB	242	03.9765.14CDA	515	03.9904.14C	244	03.9954.ES	544
03.9441.14CNI	503	03.9471.14CDA	507	03.9626.40CDA	242	03.9765.40C	515	03.9904.14CCB	244	03.9955.14	544
03.9441.40C	503	03.9471.14CNI	507	03.9630.14C	241	03.9765.40CDA	515	03.9904.14CDA	244	03.9955.40A	544
03.9441.40CCB	503	03.9471.40C	507	03.9630.14CCB	241	03.9820.14C	513	03.9904.40C	244	03.9955.ER	544
03.9441.40CDA	503	03.9471.40CCB	507	03.9630.14CDA	241	03.9820.14CDA	513	03.9904.40CCB	244	03.9955.ES	544
03.9441.40CNI	503	03.9471.40CDA	507	03.9630.40C	241	03.9820.40C	513	03.9904.40CDA	244	03.9956.14	544
03.9445.14C	504	03.9471.40CNI	507	03.9630.40CCB	241	03.9820.40CDA	513	03.9905.14C	244	03.9956.40A	544
03.9445.14CCB	504	03.9475.14C	508	03.9630.40CDA	241	03.9821.14C	513	03.9905.14CCB	244	03.9956.ER	544
03.9445.14CDA	504	03.9475.14CCB	508	03.9631.14C	241	03.9821.14CDA	513	03.9905.14CDA	244	03.9956.ES	544
03.9445.14CNI	504	03.9475.14CDA	508	03.9631.14CCB	241	03.9821.40C	513	03.9905.40C	244	03.9957.14	544
03.9445.40C	504	03.9475.14CNI	508	03.9631.14CDA	241	03.9821.40CDA	513	03.9905.40CCB	244	03.9957.40A	544
03.9445.40CCB	504	03.9475.40C	508	03.9631.40C	241	03.9825.14C	514	03.9905.40CDA	244	03.9957.ER	544
03.9445.40CDA	504	03.9475.40CCB	508	03.9631.40CCB	241	03.9825.14CDA	514	03.9910.14	544	03.9957.ES	544
03.9445.40CNI	504	03.9475.40CDA	508	03.9631.40CDA	241	03.9825.40C	514	03.9910.40A	544	03.9960.14	550
03.9446.14C	504	03.9475.40CNI	508	03.9635.14C	242	03.9825.40CDA	514	03.9910.ER	544	03.9960.40A	550
03.9446.14CCB	504	03.9476.14C	508	03.9635.14CCB	242	03.9826.14C	514	03.9910.ES	544	03.9960.ER	550
03.9446.14CDA	504	03.9476.14CCB	508	03.9635.14CDA	242	03.9826.14CDA	514	03.9911.14	544	03.9960.ES	550
03.9446.14CNI	504	03.9476.14CDA	508	03.9635.40C	242	03.9826.40C	514	03.9911.40A	544	03.9961.14	550
03.9446.40C	504	03.9476.14CNI	508	03.9635.40CCB	242	03.9826.40CDA	514	03.9911.ER	544	03.9961.40A	550
03.9446.40CCB	504	03.9476.40C	508	03.9635.40CDA	242	03.9830.14C	513	03.9911.ES	544	03.9961.ER	550
03.9446.40CDA	504	03.9476.40CCB	508	03.9636.14C	242	03.9830.14CDA	513	03.9912.14	544	03.9961.ES	550
03.9446.40CNI	504	03.9476.40CDA	508	03.9636.14CCB	242	03.9830.40C	513	03.9912.40A	544	03.9962.14	550
03.9450.14C	503	03.9476.40CNI	508	03.9636.14CDA	242	03.9830.40CDA	513	03.9912.ER	544	03.9962.40A	550
03.9450.14CCB	503	03.9500.02	772	03.9636.40C	242	03.9831.14C	513	03.9912.ES	544	03.9962.ER	550
03.9450.14CDA	503	03.9500.14	772	03.9636.40CCB	242	03.9831.14CDA	513	03.9913.14	544	03.9962.ES	550
03.9450.14CNI	503	03.9500.40	772	03.9636.40CDA	242	03.9831.40C	513	03.9913.40A	544	03.9963.14	551
03.9450.40C	503	03.9500.ET	772	03.9660.14C	243	03.9831.40CDA	513	03.9913.ER	544	03.9963.40A	551
03.9450.40CCB	503	03.9500.EU	772	03.9660.14CCB	243	03.9835.14C	514	03.9913.ES	544	03.9963.ER	551
03.9450.40CDA	503	03.9501.02	772	03.9660.14CDA	243	03.9835.14CDA	514	03.9920.14	550	03.9963.ES	551
03.9450.40CNI	503	03.9501.14	772	03.9660.40C	243	03.9835.40C	514	03.9920.40A	550	03.9964.14	550
03.9451.14C	503	03.9501.40	772	03.9660.40CCB	243	03.9835.40CDA	514	03.9920.ER	550	03.9964.40A	550
03.9451.14CCB	503	03.9501.ET	772	03.9660.40CDA	243	03.9836.14C	514	03.9920.ES	550	03.9964.ER	550
03.9451.14CDA	503	03.9501.EU	772	03.9661.14C	243	03.9836.14CDA	514	03.9921.14	550	03.9964.ES	550
03.9451.14CNI	503	03.9502.02	772	03.9661.14CCB	243	03.9836.40C	514	03.9921.40A	550	03.9965.14	550
03.9451.40C	503	03.9502.14	772	03.9661.14CDA	243	03.9836.40CDA	514	03.9921.ER	550	03.9965.40A	550
03.9451.40CCB	503	03.9502.40	772	03.9661.40C	243	03.9860.14C	515	03.9921.ES	550	03.9965.ER	550
03.9451.40CDA	503	03.9502.ET	772	03.9661.40CCB	243	03.9860.14CDA	515	03.9922.14	550	03.9965.ES	550
03.9451.40CNI	503	03.9502.EU	772	03.9661.40CDA	243	03.9860.40C	515	03.9922.40A	550	03.9966.14	550
03.9455.14C	504	03.9503.02	772	03.9664.14C	243	03.9860.40CDA	515	03.9922.ER	550	03.9966.40A	550
03.9455.14CCB	504	03.9503.14	772	03.9664.14CCB	243	03.9861.14C	515	03.9922.ES	550	03.9966.ER	550
03.9455.14CDA	504	03.9503.40	772	03.9664.14CDA	243	03.9861.14CDA	515	03.9923.14	551	03.9966.ES	550
03.9455.14CNI	504	03.9503.ET	772	03.9664.40C	243	03.9861.40C	515	03.9923.40A	551	03.9967.14	551
03.9455.40C	504	03.9503.EU	772	03.9664.40CCB	243	03.9861.40CDA	515	03.9923.ER	551	03.9967.40A	551
03.9455.40CCB	504	03.9510.02	772	03.9664.40CDA	243	03.9864.14C	515	03.9923.ES	551	03.9967.ER	551
03.9455.40CDA	504	03.9510.14	772	03.9665.14C	243	03.9864.14CDA	515	03.9924.14	550	03.9967.ES	551
03.9455.40CNI	504	03.9510.40	772	03.9665.14CCB	243	03.9864.40C	515	03.9924.40A	550	03.9968.14	550
03.9456.14C	504	03.9510.ET	772	03.9665.14CDA	243	03.9864.40CDA	515	03.9924.ER	550	03.9968.40A	550
03.9456.14CCB	504	03.9510.EU	772	03.9665.40C	243	03.9865.14C	515	03.9924.ES	550	03.9968.ER	550
03.9456.14CDA	504	03.9511.02	772	03.9665.40CCB	243	03.9865.14CDA	515	03.9931.14A	545	03.9968.ES	550
03.9456.14CNI	504	03.9511.14	772	03.9665.40CDA	243	03.9865.40C	515	03.9931.40B	545	03.9969.14	550
03.9456.40C	504	03.9511.40	772	03.9720.14C	513	03.9865.40CDA	515	03.9931.ERA	545	03.9969.40A	550
03.9456.40CCB	504	03.9511.ET	772	03.9720.14CDA	513	03.9890.14	553	03.9931.ESA	545	03.9969.ER	550
03.9456.40CDA	504	03.9511.EU	772	03.9720.40C	513	03.9890.40	553	03.9932.14A	545	03.9969.ES	550
03.9456.40CNI	504	03.9560.02	773	03.9720.40CDA	513	03.9890.ER	553	03.9932.40B	545	03.9971.14A	545
03.9460.14C	507	03.9560.14	773	03.9721.14C	513	03.9890.ES	553	03.9932.ERA	545	03.9971.40B	545
03.9460.14CCB	507	03.9560.40	773	03.9721.14CDA	513	03.9891.14	553	03.9932.ESA	545	03.9971.ERA	545
03.9460.14CDA	507	03.9560.ET	773	03.9721.40C	513	03.9891.40	553	03.9933.14A	545	03.9971.ESA	545
03.9460.14CNI	507	03.9560.EU	773	03.9721.40CDA	513	03.9891.ER	553	03.9933.40B	545	03.9972.14A	545
03.9460.40C	507	03.9561.02	773	03.9725.14C	514	03.9891.ES	553	03.9933.ERA	545	03.9972.40B	545
03.9460.40CCB	507	03.9561.14	773	03.9725.14CDA	514	03.9892.14	553	03.9933.ESA	545	03.9972.ERA	545
03.9460.40CDA	507	03.9561.40	773	03.9725.40C	514	03.9892.40	553	03.9940.14	552	03.9972.ESA	545
03.9460.40CNI	507	03.9561.ET	773	03.9725.40CDA	514	03.9892.ER	553	03.9940.40A	552	03.9973.14A	545
03.9461.14C	507	03.9561.EU	773	03.9726.14C	514	03.9892.ES	553	03.9940.ER	552	03.9973.40B	545
03.9461.14CCB	507	03.9570.02	773	03.9726.14CDA	514	03.9900.14C	510	03.9940.ES	552	03.9973.ERA	545
03.9461.14CDA	507	03.9570.14	773	03.9726.40C	514	03.9900.14CCB	510	03.9941.14	552	03.9973.ESA	545
03.9461.14CNI	507	03.9570.40	773	03.9726.40CDA	514	03.9900.14CDA	510	03.9941.40A	552	03.9976.14A	545
03.9461.40C	507	03.9570.ET	773	03.9730.14C	513	03.9900.14CNI	510	03.9941.ER	552	03.9976.40B	545
03.9461.40CCB	507	03.9570.EU	773	03.9730.14CDA	513	03.9900.40C	510	03.9941.ES	552	03.9976.ERA	545
03.9461.40CDA	507	03.9571.02	773	03.9730.40C	513	03.9900.40CCB	510	03.9942.14	552	03.9976.ESA	545
03.9461.40CNI	507	03.9571.14	773	03.9730.40CDA	513	03.9900.40CDA	510	03.9942.40A	552	03.9977.14A	545
03.9465.14C	508	03.9571.40	773	03.9731.14C	513	03.9900.40CNI	510	03.9942.ER	552	03.9977.40B	545
03.9465.14CCB	508	03.9571.ET	773	03.9731.14CDA	513	03.9901.14C	510	03.9942.ES	552	03.9977.ERA	545
03.9465.14CDA	508	03.9571.EU	773	03.9731.40C	513	03.9901.14CCB	510	03.9943.14	552	03.9977.ESA	545
03.9465.14CNI	508	03.9620.14C	241	03.9731.40CDA	513	03.9901.14CDA	510	03.9943.40A	552	03.9978.14A	545
03.9465.40C	508	03.9620.14CCB	241	03.9735.14C	514	03.9901.14CNI	510	03.9943.ER	552	03.9978.40B	545
03.9465.40CCB	508	03.9620.14CDA	241	03.9735.14CDA	514	03.9901.40C	510	03.9943.ES	552	03.9978.ERA	545
03.9465.40CDA	508	03.9620.40C	241	03.9735.40C	514	03.9901.40CCB	510	03.9950.14	544	03.9978.ESA	545
03.9465.40CNI	508	03.9620.40CCB	241	03.9735.40CDA	514	03.9901.40CDA	510	03.9950.40A	544	03.9980.14	552
03.9466.14C	508	03.9620.40CDA	241	03.9736.14C	514	03.9901.40CNI	510	03.9950.ER	544	03.9980.40A	552
03.9466.14CCB	508	03.9621.14C	241	03.9736.14CDA	514	03.9902.14C	510	03.9950.ES	544	03.9980.ER	552
03.9466.14CDA	508	03.9621.14CCB	241	03.9736.40C	514	03.9902.14CCB	510	03.9951.14	544	03.9980.ES	552
03.9466.14CNI	508	03.9621.14CDA	241	03.9736.40CDA	514	03.9902.14CDA	510	03.9951.40A	544	03.9981.14	552
03.9466.40C	508	03.9621.40C	241	03.9760.14C	515	03.9902.14CNI	510	03.9951.ER	544	03.9981.40A	552
03.9466.40CCB	508	03.9621.40CCB	241	03.9760.14CDA	515	03.9902.40C	510	03.9951.ES	544	03.9981.ER	552
03.9466.40CDA	508	03.9621.40CDA	241	03.9760.40C	515	03.9902.40CCB	510	03.9952.14	544	03.9981.ES	552
03.9466.40CNI	508	03.9625.14C	242	03.9760.40CDA	515	03.9902.40CDA	510	03.9952.40A	544	03.9982.14	552
03.9470.14C	507	03.9625.14CCB	242	03.9761.14C	515	03.9902.40CNI	510	03.9952.ER	544	03.9982.40A	552
03.9470.14CCB	507	03.9625.14CDA	242	03.9761.14CDA	515	03.9903.14C	510	03.9952.ES	544	03.9982.ER	552
03.9470.14CDA	507	03.9625.40C	242	03.9761.40C	515	03.9903.14CCB	510	03.9953.14	544	03.9982.ES	552

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
03.9983.14	552	05.0611.14CNI	447	05.0626.14CDA	448	05.0641.14CCB	466	05.0656.14C	467	05.0670.40CNI	469
03.9983.40A	552	05.0611.40C	447	05.0626.14CNI	448	05.0641.14CDA	466	05.0656.14CCB	467	05.0671.14C	469
03.9983.ER	552	05.0611.40CCB	447	05.0626.40C	448	05.0641.14CNI	466	05.0656.14CDA	467	05.0671.14CCB	469
03.9983.ES	552	05.0611.40CDA	447	05.0626.40CCB	448	05.0641.40C	466	05.0656.14CNI	467	05.0671.14CDA	469
03.9985.14	552	05.0611.40CNI	447	05.0626.40CDA	448	05.0641.40CCB	466	05.0656.40C	467	05.0671.14CNI	469
03.9985.40A	552	05.0612.14C	447	05.0626.40CNI	448	05.0641.40CDA	466	05.0656.40CCB	467	05.0671.40C	469
03.9985.ER	552	05.0612.14CCB	447	05.0627.14C	448	05.0641.40CNI	466	05.0656.40CDA	467	05.0671.40CCB	469
03.9985.ES	552	05.0612.14CDA	447	05.0627.14CCB	448	05.0642.14C	466	05.0656.40CNI	467	05.0671.40CDA	469
03.9986.14	552	05.0612.14CNI	447	05.0627.14CDA	448	05.0642.14CCB	466	05.0657.14C	467	05.0671.40CNI	469
03.9986.40A	552	05.0612.40C	447	05.0627.14CNI	448	05.0642.14CDA	466	05.0657.14CCB	467	05.0672.14C	469
03.9986.ER	552	05.0612.40CCB	447	05.0627.40C	448	05.0642.14CNI	466	05.0657.14CDA	467	05.0672.14CCB	469
03.9986.ES	552	05.0612.40CDA	447	05.0627.40CCB	448	05.0642.40C	466	05.0657.14CNI	467	05.0672.14CDA	469
03.9987.14	552	05.0612.40CNI	447	05.0627.40CDA	448	05.0642.40CCB	466	05.0657.40C	467	05.0672.14CNI	469
03.9987.40A	552	05.0614.14C	447	05.0627.40CNI	448	05.0642.40CDA	466	05.0657.40CCB	467	05.0672.40C	469
03.9987.ER	552	05.0614.14CCB	447	05.0629.14C	448	05.0642.40CNI	466	05.0657.40CDA	467	05.0672.40CCB	469
03.9987.ES	552	05.0614.14CDA	447	05.0629.14CCB	448	05.0644.14C	466	05.0657.40CNI	467	05.0672.40CDA	469
03.9988.14	552	05.0614.14CNI	447	05.0629.14CDA	448	05.0644.14CCB	466	05.0659.14C	467	05.0672.40CNI	469
03.9988.40A	552	05.0614.40C	447	05.0629.14CNI	448	05.0644.14CDA	466	05.0659.14CCB	467	05.0674.14C	469
03.9988.ER	552	05.0614.40CCB	447	05.0629.40C	448	05.0644.14CNI	466	05.0659.14CDA	467	05.0674.14CCB	469
03.9988.ES	552	05.0614.40CDA	447	05.0629.40CCB	448	05.0644.40C	466	05.0659.14CNI	467	05.0674.14CDA	469
05.0600.14C	446	05.0614.40CNI	447	05.0629.40CDA	448	05.0644.40CCB	466	05.0659.40C	467	05.0674.14CNI	469
05.0600.14CCB	446	05.0615.14C	447	05.0629.40CNI	448	05.0644.40CDA	466	05.0659.40CCB	467	05.0674.40C	469
05.0600.14CDA	446	05.0615.14CCB	447	05.0630.14C	449	05.0644.40CNI	466	05.0659.40CDA	467	05.0674.40CCB	469
05.0600.14CNI	446	05.0615.14CDA	447	05.0630.14CCB	449	05.0645.14C	466	05.0659.40CNI	467	05.0674.40CDA	469
05.0600.40C	446	05.0615.14CNI	447	05.0630.14CDA	449	05.0645.14CCB	466	05.0660.14C	468	05.0674.40CNI	469
05.0600.40CCB	446	05.0615.40C	447	05.0630.14CNI	449	05.0645.14CDA	466	05.0660.14CCB	468	05.0675.14C	469
05.0600.40CDA	446	05.0615.40CCB	447	05.0630.40C	449	05.0645.14CNI	466	05.0660.14CDA	468	05.0675.14CCB	469
05.0600.40CNI	446	05.0615.40CDA	447	05.0630.40CCB	449	05.0645.40C	466	05.0660.14CNI	468	05.0675.14CDA	469
05.0601.14C	446	05.0615.40CNI	447	05.0630.40CDA	449	05.0645.40CCB	466	05.0660.40C	468	05.0675.14CNI	469
05.0601.14CCB	446	05.0616.14C	447	05.0630.40CNI	449	05.0645.40CDA	466	05.0660.40CCB	468	05.0675.40C	469
05.0601.14CDA	446	05.0616.14CCB	447	05.0631.14C	449	05.0645.40CNI	466	05.0660.40CDA	468	05.0675.40CCB	469
05.0601.14CNI	446	05.0616.14CDA	447	05.0631.14CCB	449	05.0646.14C	466	05.0660.40CNI	468	05.0675.40CDA	469
05.0601.40C	446	05.0616.14CNI	447	05.0631.14CDA	449	05.0646.14CCB	466	05.0661.14C	468	05.0675.40CNI	469
05.0601.40CCB	446	05.0616.40C	447	05.0631.14CNI	449	05.0646.14CDA	466	05.0661.14CCB	468	05.0676.14C	469
05.0601.40CDA	446	05.0616.40CCB	447	05.0631.40C	449	05.0646.14CNI	466	05.0661.14CDA	468	05.0676.14CCB	469
05.0601.40CNI	446	05.0616.40CDA	447	05.0631.40CCB	449	05.0646.40C	466	05.0661.14CNI	468	05.0676.14CDA	469
05.0602.14C	446	05.0616.40CNI	447	05.0631.40CDA	449	05.0646.40CCB	466	05.0661.40C	468	05.0676.14CNI	469
05.0602.14CCB	446	05.0617.14C	447	05.0631.40CNI	449	05.0646.40CDA	466	05.0661.40CCB	468	05.0676.40C	469
05.0602.14CDA	446	05.0617.14CCB	447	05.0632.14C	449	05.0646.40CNI	466	05.0661.40CDA	468	05.0676.40CCB	469
05.0602.14CNI	446	05.0617.14CDA	447	05.0632.14CCB	449	05.0647.14C	466	05.0661.40CNI	468	05.0676.40CDA	469
05.0602.40C	446	05.0617.14CNI	447	05.0632.14CDA	449	05.0647.14CCB	466	05.0662.14C	468	05.0676.40CNI	469
05.0602.40CCB	446	05.0617.40C	447	05.0632.14CNI	449	05.0647.14CDA	466	05.0662.14CCB	468	05.0677.14C	469
05.0602.40CDA	446	05.0617.40CCB	447	05.0632.40C	449	05.0647.14CNI	466	05.0662.14CDA	468	05.0677.14CCB	469
05.0602.40CNI	446	05.0617.40CDA	447	05.0632.40CCB	449	05.0647.40C	466	05.0662.14CNI	468	05.0677.14CDA	469
05.0604.14C	446	05.0617.40CNI	447	05.0632.40CDA	449	05.0647.40CCB	466	05.0662.40C	468	05.0677.14CNI	469
05.0604.14CCB	446	05.0619.14C	447	05.0632.40CNI	449	05.0647.40CDA	466	05.0662.40CCB	468	05.0677.40C	469
05.0604.14CDA	446	05.0619.14CCB	447	05.0634.14C	449	05.0647.40CNI	466	05.0662.40CDA	468	05.0677.40CCB	469
05.0604.14CNI	446	05.0619.14CDA	447	05.0634.14CCB	449	05.0649.14C	466	05.0662.40CNI	468	05.0677.40CDA	469
05.0604.40C	446	05.0619.14CNI	447	05.0634.14CDA	449	05.0649.14CCB	466	05.0664.14C	468	05.0677.40CNI	469
05.0604.40CCB	446	05.0619.40C	447	05.0634.14CNI	449	05.0649.14CDA	466	05.0664.14CCB	468	05.0679.14C	469
05.0604.40CDA	446	05.0619.40CCB	447	05.0634.40C	449	05.0649.14CNI	466	05.0664.14CDA	468	05.0679.14CCB	469
05.0604.40CNI	446	05.0619.40CDA	447	05.0634.40CCB	449	05.0649.40C	466	05.0664.14CNI	468	05.0679.14CDA	469
05.0605.14C	446	05.0619.40CNI	447	05.0634.40CDA	449	05.0649.40CCB	466	05.0664.40C	468	05.0679.14CNI	469
05.0605.14CCB	446	05.0620.14C	448	05.0634.40CNI	449	05.0649.40CDA	466	05.0664.40CCB	468	05.0679.40C	469
05.0605.14CDA	446	05.0620.14CCB	448	05.0635.14C	449	05.0649.40CNI	466	05.0664.40CDA	468	05.0679.40CCB	469
05.0605.14CNI	446	05.0620.14CDA	448	05.0635.14CCB	449	05.0650.14C	467	05.0664.40CNI	468	05.0679.40CDA	469
05.0605.40C	446	05.0620.14CNI	448	05.0635.14CDA	449	05.0650.14CCB	467	05.0665.14C	468	05.0679.40CNI	469
05.0605.40CCB	446	05.0620.40C	448	05.0635.14CNI	449	05.0650.14CDA	467	05.0665.14CCB	468	05.0700.14C	516
05.0605.40CDA	446	05.0620.40CCB	448	05.0635.40C	449	05.0650.14CNI	467	05.0665.14CDA	468	05.0700.14CDA	516
05.0605.40CNI	446	05.0620.40CDA	448	05.0635.40CCB	449	05.0650.40C	467	05.0665.14CNI	468	05.0700.14CNI	516
05.0606.14C	446	05.0620.40CNI	448	05.0635.40CDA	449	05.0650.40CCB	467	05.0665.40C	468	05.0700.40C	516
05.0606.14CCB	446	05.0621.14C	448	05.0635.40CNI	449	05.0650.40CDA	467	05.0665.40CCB	468	05.0700.40CDA	516
05.0606.14CDA	446	05.0621.14CCB	448	05.0636.14C	449	05.0650.40CNI	467	05.0665.40CDA	468	05.0700.40CNI	516
05.0606.14CNI	446	05.0621.14CDA	448	05.0636.14CCB	449	05.0651.14C	467	05.0665.40CNI	468	05.0701.14C	516
05.0606.40C	446	05.0621.14CNI	448	05.0636.14CDA	449	05.0651.14CCB	467	05.0666.14C	468	05.0701.14CDA	516
05.0606.40CCB	446	05.0621.40C	448	05.0636.14CNI	449	05.0651.14CDA	467	05.0666.14CCB	468	05.0701.14CNI	516
05.0606.40CDA	446	05.0621.40CCB	448	05.0636.40C	449	05.0651.14CNI	467	05.0666.14CDA	468	05.0701.40C	516
05.0606.40CNI	446	05.0621.40CDA	448	05.0636.40CCB	449	05.0651.40C	467	05.0666.14CNI	468	05.0701.40CDA	516
05.0607.14C	446	05.0621.40CNI	448	05.0636.40CDA	449	05.0651.40CCB	467	05.0666.40C	468	05.0701.40CNI	516
05.0607.14CCB	446	05.0622.14C	448	05.0636.40CNI	449	05.0651.40CDA	467	05.0666.40CCB	468	05.0703.40C	516
05.0607.14CDA	446	05.0622.14CCB	448	05.0637.14C	449	05.0651.40CNI	467	05.0666.40CDA	468	05.0703.40CDA	516
05.0607.14CNI	446	05.0622.14CDA	448	05.0637.14CCB	449	05.0652.14C	467	05.0666.40CNI	468	05.0703.40CNI	516
05.0607.40C	446	05.0622.14CNI	448	05.0637.14CDA	449	05.0652.14CCB	467	05.0667.14C	468	05.0705.14C	516
05.0607.40CCB	446	05.0622.40C	448	05.0637.14CNI	449	05.0652.14CDA	467	05.0667.14CCB	468	05.0705.14CDA	516
05.0607.40CDA	446	05.0622.40CCB	448	05.0637.40C	449	05.0652.14CNI	467	05.0667.14CDA	468	05.0705.14CNI	516
05.0607.40CNI	446	05.0622.40CDA	448	05.0637.40CCB	449	05.0652.40C	467	05.0667.14CNI	468	05.0705.40C	516
05.0609.14C	446	05.0622.40CNI	448	05.0637.40CDA	449	05.0652.40CCB	467	05.0667.40C	468	05.0705.40CDA	516
05.0609.14CCB	446	05.0624.14C	448	05.0637.40CNI	449	05.0652.40CDA	467	05.0667.40CCB	468	05.0705.40CNI	516
05.0609.14CDA	446	05.0624.14CCB	448	05.0639.14C	449	05.0652.40CNI	467	05.0667.40CDA	468	05.0706.14C	516
05.0609.14CNI	446	05.0624.14CDA	448	05.0639.14CCB	449	05.0654.14C	467	05.0667.40CNI	468	05.0706.14CDA	516
05.0609.40C	446	05.0624.14CNI	448	05.0639.14CDA	449	05.0654.14CCB	467	05.0669.14C	468	05.0706.14CNI	516
05.0609.40CCB	446	05.0624.40C	448	05.0639.14CNI	449	05.0654.14CDA	467	05.0669.14CCB	468	05.0706.40C	516
05.0609.40CDA	446	05.0624.40CCB	448	05.0639.40C	449	05.0654.14CNI	467	05.0669.14CDA	468	05.0706.40CDA	516
05.0609.40CNI	446	05.0624.40CDA	448	05.0639.40CCB	449	05.0654.40C	467	05.0669.14CNI	468	05.0706.40CNI	516
05.0610.14C	447	05.0624.40CNI	448	05.0639.40CDA	449	05.0654.40CCB	467	05.0669.40C	468	05.0708.40C	516
05.0610.14CCB	447	05.0625.14C	448	05.0639.40CNI	449	05.0654.40CDA	467	05.0669.40CCB	468	05.0708.40CDA	516
05.0610.14CDA	447	05.0625.14CCB	448	05.0640.14C	466	05.0654.40CNI	467	05.0669.40CDA	468	05.0708.40CNI	516
05.0610.14CNI	447	05.0625.14CDA	448	05.0640.14CCB	466	05.0655.14C	467	05.0669.40CNI	468	05.0710.14C	517
05.0610.40C	447	05.0625.14CNI	448	05.0640.14CDA	466	05.0655.14CCB	467	05.0670.14C	469	05.0710.14CDA	517
05.0610.40CCB	447	05.0625.40C	448	05.0640.14CNI	466	05.0655.14CDA	467	05.0670.14CCB	469	05.0710.14CNI	517
05.0610.40CDA	447	05.0625.40CCB	448	05.0640.40C	466	05.0655.14CNI	467	05.0670.14CDA	469	05.0710.40C	517
05.0610.40CNI	447	05.0625.40CDA	448	05.0640.40CCB	466	05.0655.40C	467	05.0670.14CNI	469	05.0710.40CDA	517
05.0611.14C	447	05.0625.40CNI	448	05.0640.40CDA	466	05.0655.40CCB	467	05.0670.40C	469	05.0710.40CNI	517
05.0611.14CCB	447	05.0626.14C	448	05.0640.40CNI	466	05.0655.40CDA	467	05.0670.40CCB	469	05.0711.14C	517
05.0611.14CDA	447	05.0626.14CCB	448	05.0641.14C	466	05.0655.40CNI	467	05.0670.40CDA	469	05.0711.14CDA	517

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.0711.14CNI	517	05.0743.14CDA	516	05.0775.40C	519	05.0966.14CNI	518	05.1026.14CDA	440	05.1056.14CCB	459
05.0711.40C	517	05.0743.14CNI	516	05.0775.40CDA	519	05.0970.14C	519	05.1026.14CNI	440	05.1056.14CDA	459
05.0711.40CDA	517	05.0745.14C	516	05.0775.40CNI	519	05.0970.14CDA	519	05.1026.40C	440	05.1056.14CNI	459
05.0711.40CNI	517	05.0745.14CDA	516	05.0776.14C	519	05.0970.14CNI	519	05.1026.40CCB	440	05.1056.40C	459
05.0713.40C	517	05.0745.14CNI	516	05.0776.14CDA	519	05.0971.14C	519	05.1026.40CDA	440	05.1056.40CCB	459
05.0713.40CDA	517	05.0745.40C	516	05.0776.14CNI	519	05.0971.14CDA	519	05.1026.40CNI	440	05.1056.40CDA	459
05.0713.40CNI	517	05.0745.40CDA	516	05.0776.40C	519	05.0971.14CNI	519	05.1027.14C	440	05.1056.40CNI	459
05.0715.14C	517	05.0745.40CNI	516	05.0776.40CDA	519	05.0975.14C	519	05.1027.14CCB	440	05.1057.14C	459
05.0715.14CDA	517	05.0746.14C	516	05.0776.40CNI	519	05.0975.14CDA	519	05.1027.14CDA	440	05.1057.14CCB	459
05.0715.14CNI	517	05.0746.14CDA	516	05.0778.14C	519	05.0975.14CNI	519	05.1027.14CNI	440	05.1057.14CDA	459
05.0715.40C	517	05.0746.14CNI	516	05.0778.14CDA	519	05.0976.14C	519	05.1027.40C	440	05.1057.14CNI	459
05.0715.40CDA	517	05.0746.40C	516	05.0778.14CNI	519	05.0976.14CDA	519	05.1027.40CCB	440	05.1057.40C	459
05.0715.40CNI	517	05.0746.40CDA	516	05.0800.14C	516	05.0976.14CNI	519	05.1027.40CDA	440	05.1057.40CCB	459
05.0716.14C	517	05.0746.40CNI	516	05.0800.14CDA	516	05.1001.14C	438	05.1027.40CNI	440	05.1057.40CDA	459
05.0716.14CDA	517	05.0748.14C	516	05.0800.14CNI	516	05.1001.14CCB	438	05.1031.14C	441	05.1057.40CNI	459
05.0716.14CNI	517	05.0748.14CDA	516	05.0801.14C	516	05.1001.14CDA	438	05.1031.14CCB	441	05.1061.14C	460
05.0716.40C	517	05.0748.14CNI	516	05.0801.14CDA	516	05.1001.14CNI	438	05.1031.14CDA	441	05.1061.14CCB	460
05.0716.40CDA	517	05.0750.14C	517	05.0801.14CNI	516	05.1001.40C	438	05.1031.14CNI	441	05.1061.14CDA	460
05.0716.40CNI	517	05.0750.14CDA	517	05.0805.14C	516	05.1001.40CCB	438	05.1031.40C	441	05.1061.14CNI	460
05.0718.40C	517	05.0750.14CNI	517	05.0805.14CDA	516	05.1001.40CDA	438	05.1031.40CCB	441	05.1061.40C	460
05.0718.40CDA	517	05.0750.40C	517	05.0805.14CNI	516	05.1001.40CNI	438	05.1031.40CDA	441	05.1061.40CCB	460
05.0718.40CNI	517	05.0750.40CDA	517	05.0806.14C	516	05.1002.14C	438	05.1031.40CNI	441	05.1061.40CDA	460
05.0720.14C	518	05.0750.40CNI	517	05.0806.14CDA	516	05.1002.14CCB	438	05.1032.14C	441	05.1061.40CNI	460
05.0720.14CDA	518	05.0751.14C	517	05.0806.14CNI	516	05.1002.14CDA	438	05.1032.14CCB	441	05.1062.14C	460
05.0720.14CNI	518	05.0751.14CDA	517	05.0810.14C	517	05.1002.14CNI	438	05.1032.14CDA	441	05.1062.14CCB	460
05.0720.40C	518	05.0751.14CNI	517	05.0810.14CDA	517	05.1002.40C	438	05.1032.14CNI	441	05.1062.14CDA	460
05.0720.40CDA	518	05.0751.40C	517	05.0810.14CNI	517	05.1002.40CCB	438	05.1032.40C	441	05.1062.14CNI	460
05.0720.40CNI	518	05.0751.40CDA	517	05.0811.14C	517	05.1002.40CDA	438	05.1032.40CCB	441	05.1062.40C	460
05.0721.14C	518	05.0751.40CNI	517	05.0811.14CDA	517	05.1002.40CNI	438	05.1032.40CDA	441	05.1062.40CCB	460
05.0721.14CDA	518	05.0753.14C	517	05.0811.14CNI	517	05.1006.14C	438	05.1032.40CNI	441	05.1062.40CDA	460
05.0721.14CNI	518	05.0753.14CDA	517	05.0815.14C	517	05.1006.14CCB	438	05.1036.14C	441	05.1062.40CNI	460
05.0721.40C	518	05.0753.14CNI	517	05.0815.14CDA	517	05.1006.14CDA	438	05.1036.14CCB	441	05.1066.14C	460
05.0721.40CDA	518	05.0755.14C	517	05.0815.14CNI	517	05.1006.14CNI	438	05.1036.14CDA	441	05.1066.14CCB	460
05.0721.40CNI	518	05.0755.14CDA	517	05.0816.14C	517	05.1006.40C	438	05.1036.14CNI	441	05.1066.14CDA	460
05.0723.40C	518	05.0755.14CNI	517	05.0816.14CDA	517	05.1006.40CCB	438	05.1036.40C	441	05.1066.14CNI	460
05.0723.40CDA	518	05.0755.40C	517	05.0816.14CNI	517	05.1006.40CDA	438	05.1036.40CCB	441	05.1066.40C	460
05.0723.40CNI	518	05.0755.40CDA	517	05.0820.14C	518	05.1006.40CNI	438	05.1036.40CDA	441	05.1066.40CCB	460
05.0725.14C	518	05.0755.40CNI	517	05.0820.14CDA	518	05.1007.14C	438	05.1036.40CNI	441	05.1066.40CDA	460
05.0725.14CDA	518	05.0756.14C	517	05.0820.14CNI	518	05.1007.14CCB	438	05.1037.14C	441	05.1066.40CNI	460
05.0725.14CNI	518	05.0756.14CDA	517	05.0821.14C	518	05.1007.14CDA	438	05.1037.14CCB	441	05.1067.14C	460
05.0725.40C	518	05.0756.14CNI	517	05.0821.14CDA	518	05.1007.14CNI	438	05.1037.14CDA	441	05.1067.14CCB	460
05.0725.40CDA	518	05.0756.40C	517	05.0821.14CNI	518	05.1007.40C	438	05.1037.14CNI	441	05.1067.14CDA	460
05.0725.40CNI	518	05.0756.40CDA	517	05.0825.14C	518	05.1007.40CCB	438	05.1037.40C	441	05.1067.14CNI	460
05.0726.14C	518	05.0756.40CNI	517	05.0825.14CDA	518	05.1007.40CDA	438	05.1037.40CCB	441	05.1067.40C	460
05.0726.14CDA	518	05.0758.14C	517	05.0825.14CNI	518	05.1007.40CNI	438	05.1037.40CDA	441	05.1067.40CCB	460
05.0726.14CNI	518	05.0758.14CDA	517	05.0826.14C	518	05.1011.14C	439	05.1037.40CNI	441	05.1067.40CDA	460
05.0726.40C	518	05.0758.14CNI	517	05.0826.14CDA	518	05.1011.14CCB	439	05.1041.14C	458	05.1067.40CNI	460
05.0726.40CDA	518	05.0760.14C	518	05.0826.14CNI	518	05.1011.14CDA	439	05.1041.14CCB	458	05.1071.14C	461
05.0726.40CNI	518	05.0760.14CDA	518	05.0830.14C	519	05.1011.14CNI	439	05.1041.14CDA	458	05.1071.14CCB	461
05.0728.40C	518	05.0760.14CNI	518	05.0830.14CDA	519	05.1011.40C	439	05.1041.14CNI	458	05.1071.14CDA	461
05.0728.40CDA	518	05.0760.40C	518	05.0830.14CNI	519	05.1011.40CCB	439	05.1041.40C	458	05.1071.14CNI	461
05.0728.40CNI	518	05.0760.40CDA	518	05.0831.14C	519	05.1011.40CDA	439	05.1041.40CCB	458	05.1071.40C	461
05.0730.14C	519	05.0760.40CNI	518	05.0831.14CDA	519	05.1011.40CNI	439	05.1041.40CDA	458	05.1071.40CCB	461
05.0730.14CDA	519	05.0761.14C	518	05.0831.14CNI	519	05.1012.14C	439	05.1041.40CNI	458	05.1071.40CDA	461
05.0730.14CNI	519	05.0761.14CDA	518	05.0835.14C	519	05.1012.14CCB	439	05.1042.14C	458	05.1071.40CNI	461
05.0730.40C	519	05.0761.14CNI	518	05.0835.14CDA	519	05.1012.14CDA	439	05.1042.14CCB	458	05.1072.14C	461
05.0730.40CDA	519	05.0761.40C	518	05.0835.14CNI	519	05.1012.14CNI	439	05.1042.14CDA	458	05.1072.14CCB	461
05.0730.40CNI	519	05.0761.40CDA	518	05.0836.14C	519	05.1012.40C	439	05.1042.14CNI	458	05.1072.14CDA	461
05.0731.14C	519	05.0761.40CNI	518	05.0836.14CDA	519	05.1012.40CCB	439	05.1042.40C	458	05.1072.14CNI	461
05.0731.14CDA	519	05.0763.14C	518	05.0836.14CNI	519	05.1012.40CDA	439	05.1042.40CCB	458	05.1072.40C	461
05.0731.14CNI	519	05.0763.14CDA	518	05.0940.14C	516	05.1012.40CNI	439	05.1042.40CDA	458	05.1072.40CCB	461
05.0731.40C	519	05.0763.14CNI	518	05.0940.14CDA	516	05.1016.14C	439	05.1042.40CNI	458	05.1072.40CDA	461
05.0731.40CDA	519	05.0765.14C	518	05.0940.14CNI	516	05.1016.14CCB	439	05.1046.14C	458	05.1072.40CNI	461
05.0731.40CNI	519	05.0765.14CDA	518	05.0941.14C	516	05.1016.14CDA	439	05.1046.14CCB	458	05.1076.14C	461
05.0733.40C	519	05.0765.14CNI	518	05.0941.14CDA	516	05.1016.14CNI	439	05.1046.14CDA	458	05.1076.14CCB	461
05.0733.40CDA	519	05.0765.40C	518	05.0941.14CNI	516	05.1016.40C	439	05.1046.14CNI	458	05.1076.14CDA	461
05.0733.40CNI	519	05.0765.40CDA	518	05.0945.14C	516	05.1016.40CCB	439	05.1046.40C	458	05.1076.14CNI	461
05.0735.14C	519	05.0765.40CNI	518	05.0945.14CDA	516	05.1016.40CDA	439	05.1046.40CCB	458	05.1076.40C	461
05.0735.14CDA	519	05.0766.14C	518	05.0945.14CNI	516	05.1016.40CNI	439	05.1046.40CDA	458	05.1076.40CCB	461
05.0735.14CNI	519	05.0766.14CDA	518	05.0946.14C	516	05.1017.14C	439	05.1046.40CNI	458	05.1076.40CDA	461
05.0735.40C	519	05.0766.14CNI	518	05.0946.14CDA	516	05.1017.14CCB	439	05.1047.14C	458	05.1076.40CNI	461
05.0735.40CDA	519	05.0766.40C	518	05.0946.14CNI	516	05.1017.14CDA	439	05.1047.14CCB	458	05.1077.14C	461
05.0735.40CNI	519	05.0766.40CDA	518	05.0950.14C	517	05.1017.14CNI	439	05.1047.14CDA	458	05.1077.14CCB	461
05.0736.14C	519	05.0766.40CNI	518	05.0950.14CDA	517	05.1017.40C	439	05.1047.14CNI	458	05.1077.14CDA	461
05.0736.14CDA	519	05.0768.14C	518	05.0950.14CNI	517	05.1017.40CCB	439	05.1047.40C	458	05.1077.14CNI	461
05.0736.14CNI	519	05.0768.14CDA	518	05.0951.14C	517	05.1017.40CDA	439	05.1047.40CCB	458	05.1077.40C	461
05.0736.40C	519	05.0768.14CNI	518	05.0951.14CDA	517	05.1017.40CNI	439	05.1047.40CDA	458	05.1077.40CCB	461
05.0736.40CDA	519	05.0770.14C	519	05.0951.14CNI	517	05.1021.14C	440	05.1047.40CNI	458	05.1077.40CDA	461
05.0736.40CNI	519	05.0770.14CDA	519	05.0955.14C	517	05.1021.14CCB	440	05.1051.14C	459	05.1077.40CNI	461
05.0738.40C	519	05.0770.14CNI	519	05.0955.14CDA	517	05.1021.14CDA	440	05.1051.14CCB	459	05.1101.14C	442
05.0738.40CDA	519	05.0770.40C	519	05.0955.14CNI	517	05.1021.14CNI	440	05.1051.14CDA	459	05.1101.14CCB	442
05.0738.40CNI	519	05.0770.40CDA	519	05.0956.14C	517	05.1021.40C	440	05.1051.14CNI	459	05.1101.14CDA	442
05.0740.14C	516	05.0770.40CNI	519	05.0956.14CDA	517	05.1021.40CCB	440	05.1051.40C	459	05.1101.14CNI	442
05.0740.14CDA	516	05.0771.14C	519	05.0956.14CNI	517	05.1021.40CDA	440	05.1051.40CCB	459	05.1101.40C	442
05.0740.14CNI	516	05.0771.14CDA	519	05.0960.14C	518	05.1021.40CNI	440	05.1051.40CDA	459	05.1101.40CCB	442
05.0740.40C	516	05.0771.14CNI	519	05.0960.14CDA	518	05.1022.14C	440	05.1051.40CNI	459	05.1101.40CDA	442
05.0740.40CDA	516	05.0771.40C	519	05.0960.14CNI	518	05.1022.14CCB	440	05.1052.14C	459	05.1101.40CNI	442
05.0740.40CNI	516	05.0771.40CDA	519	05.0961.14C	518	05.1022.14CDA	440	05.1052.14CCB	459	05.1102.14C	442
05.0741.14C	516	05.0771.40CNI	519	05.0961.14CDA	518	05.1022.14CNI	440	05.1052.14CDA	459	05.1102.14CCB	442
05.0741.14CDA	516	05.0773.14C	519	05.0961.14CNI	518	05.1022.40C	440	05.1052.14CNI	459	05.1102.14CDA	442
05.0741.14CNI	516	05.0773.14CDA	519	05.0965.14C	518	05.1022.40CCB	440	05.1052.40C	459	05.1102.14CNI	442
05.0741.40C	516	05.0773.14CNI	519	05.0965.14CDA	518	05.1022.40CDA	440	05.1052.40CCB	459	05.1102.40C	442
05.0741.40CDA	516	05.0775.14C	519	05.0965.14CNI	518	05.1022.40CNI	440	05.1052.40CDA	459	05.1102.40CCB	442
05.0741.40CNI	516	05.0775.14CDA	519	05.0966.14C	518	05.1026.14C	440	05.1052.40CNI	459	05.1102.40CDA	442
05.0743.14C	516	05.0775.14CNI	519	05.0966.14CDA	518	05.1026.14CCB	440	05.1056.14C	459	05.1102.40CNI	442

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.1106.14C	442	05.1132.40CNI	445	05.1162.40CDA	464	05.1212.40CCB	451	05.1242.40C	470	05.1272.14CNI	473
05.1106.14CCB	442	05.1136.14C	445	05.1162.40CNI	464	05.1212.40CDA	451	05.1242.40CCB	470	05.1272.40C	473
05.1106.14CDA	442	05.1136.14CCB	445	05.1166.14C	464	05.1212.40CNI	451	05.1242.40CDA	470	05.1272.40CCB	473
05.1106.14CNI	442	05.1136.14CDA	445	05.1166.14CCB	464	05.1216.14C	451	05.1242.40CNI	470	05.1272.40CDA	473
05.1106.40C	442	05.1136.14CNI	445	05.1166.14CDA	464	05.1216.14CCB	451	05.1246.14C	470	05.1272.40CNI	473
05.1106.40CCB	442	05.1136.40C	445	05.1166.14CNI	464	05.1216.14CDA	451	05.1246.14CCB	470	05.1276.14C	473
05.1106.40CDA	442	05.1136.40CCB	445	05.1166.40C	464	05.1216.14CNI	451	05.1246.14CDA	470	05.1276.14CCB	473
05.1106.40CNI	442	05.1136.40CDA	445	05.1166.40CCB	464	05.1216.40C	451	05.1246.14CNI	470	05.1276.14CDA	473
05.1107.14C	442	05.1136.40CNI	445	05.1166.40CDA	464	05.1216.40CCB	451	05.1246.40C	470	05.1276.14CNI	473
05.1107.14CCB	442	05.1137.14C	445	05.1166.40CNI	464	05.1216.40CDA	451	05.1246.40CCB	470	05.1276.40C	473
05.1107.14CDA	442	05.1137.14CCB	445	05.1167.14C	464	05.1216.40CNI	451	05.1246.40CDA	470	05.1276.40CCB	473
05.1107.14CNI	442	05.1137.14CDA	445	05.1167.14CCB	464	05.1217.14C	451	05.1246.40CNI	470	05.1276.40CDA	473
05.1107.40C	442	05.1137.14CNI	445	05.1167.14CDA	464	05.1217.14CCB	451	05.1247.14C	470	05.1276.40CNI	473
05.1107.40CCB	442	05.1137.40C	445	05.1167.14CNI	464	05.1217.14CDA	451	05.1247.14CCB	470	05.1277.14C	473
05.1107.40CDA	442	05.1137.40CCB	445	05.1167.40C	464	05.1217.14CNI	451	05.1247.14CDA	470	05.1277.14CCB	473
05.1107.40CNI	442	05.1137.40CDA	445	05.1167.40CCB	464	05.1217.40C	451	05.1247.14CNI	470	05.1277.14CDA	473
05.1111.14C	443	05.1137.40CNI	445	05.1167.40CDA	464	05.1217.40CCB	451	05.1247.40C	470	05.1277.14CNI	473
05.1111.14CCB	443	05.1141.14C	462	05.1167.40CNI	464	05.1217.40CDA	451	05.1247.40CCB	470	05.1277.40C	473
05.1111.14CDA	443	05.1141.14CCB	462	05.1171.14C	465	05.1217.40CNI	451	05.1247.40CDA	470	05.1277.40CCB	473
05.1111.14CNI	443	05.1141.14CDA	462	05.1171.14CCB	465	05.1221.14C	452	05.1247.40CNI	470	05.1277.40CDA	473
05.1111.40C	443	05.1141.14CNI	462	05.1171.14CDA	465	05.1221.14CCB	452	05.1251.14C	471	05.1277.40CNI	473
05.1111.40CCB	443	05.1141.40C	462	05.1171.14CNI	465	05.1221.14CDA	452	05.1251.14CCB	471	05.1301.14C	454
05.1111.40CDA	443	05.1141.40CCB	462	05.1171.40C	465	05.1221.14CNI	452	05.1251.14CDA	471	05.1301.14CCB	454
05.1111.40CNI	443	05.1141.40CDA	462	05.1171.40CCB	465	05.1221.40C	452	05.1251.14CNI	471	05.1301.14CDA	454
05.1112.14C	443	05.1141.40CNI	462	05.1171.40CDA	465	05.1221.40CCB	452	05.1251.40C	471	05.1301.14CNI	454
05.1112.14CCB	443	05.1142.14C	462	05.1171.40CNI	465	05.1221.40CDA	452	05.1251.40CCB	471	05.1301.40C	454
05.1112.14CDA	443	05.1142.14CCB	462	05.1172.14C	465	05.1221.40CNI	452	05.1251.40CDA	471	05.1301.40CCB	454
05.1112.14CNI	443	05.1142.14CDA	462	05.1172.14CCB	465	05.1222.14C	452	05.1251.40CNI	471	05.1301.40CDA	454
05.1112.40C	443	05.1142.14CNI	462	05.1172.14CDA	465	05.1222.14CCB	452	05.1252.14C	471	05.1301.40CNI	454
05.1112.40CCB	443	05.1142.40C	462	05.1172.14CNI	465	05.1222.14CDA	452	05.1252.14CCB	471	05.1302.14C	454
05.1112.40CDA	443	05.1142.40CCB	462	05.1172.40C	465	05.1222.14CNI	452	05.1252.14CDA	471	05.1302.14CCB	454
05.1112.40CNI	443	05.1142.40CDA	462	05.1172.40CCB	465	05.1222.40C	452	05.1252.14CNI	471	05.1302.14CDA	454
05.1116.14C	443	05.1142.40CNI	462	05.1172.40CDA	465	05.1222.40CCB	452	05.1252.40C	471	05.1302.14CNI	454
05.1116.14CCB	443	05.1146.14C	462	05.1172.40CNI	465	05.1222.40CDA	452	05.1252.40CCB	471	05.1302.40C	454
05.1116.14CDA	443	05.1146.14CCB	462	05.1176.14C	465	05.1222.40CNI	452	05.1252.40CDA	471	05.1302.40CCB	454
05.1116.14CNI	443	05.1146.14CDA	462	05.1176.14CCB	465	05.1226.14C	452	05.1252.40CNI	471	05.1302.40CDA	454
05.1116.40C	443	05.1146.14CNI	462	05.1176.14CDA	465	05.1226.14CCB	452	05.1256.14C	471	05.1302.40CNI	454
05.1116.40CCB	443	05.1146.40C	462	05.1176.14CNI	465	05.1226.14CDA	452	05.1256.14CCB	471	05.1306.14C	454
05.1116.40CDA	443	05.1146.40CCB	462	05.1176.40C	465	05.1226.14CNI	452	05.1256.14CDA	471	05.1306.14CCB	454
05.1116.40CNI	443	05.1146.40CDA	462	05.1176.40CCB	465	05.1226.40C	452	05.1256.14CNI	471	05.1306.14CDA	454
05.1117.14C	443	05.1146.40CNI	462	05.1176.40CDA	465	05.1226.40CCB	452	05.1256.40C	471	05.1306.14CNI	454
05.1117.14CCB	443	05.1147.14C	462	05.1176.40CNI	465	05.1226.40CDA	452	05.1256.40CCB	471	05.1306.40C	454
05.1117.14CDA	443	05.1147.14CCB	462	05.1177.14C	465	05.1226.40CNI	452	05.1256.40CDA	471	05.1306.40CCB	454
05.1117.14CNI	443	05.1147.14CDA	462	05.1177.14CCB	465	05.1227.14C	452	05.1256.40CNI	471	05.1306.40CDA	454
05.1117.40C	443	05.1147.14CNI	462	05.1177.14CDA	465	05.1227.14CCB	452	05.1257.14C	471	05.1306.40CNI	454
05.1117.40CCB	443	05.1147.40C	462	05.1177.14CNI	465	05.1227.14CDA	452	05.1257.14CCB	471	05.1307.14C	454
05.1117.40CDA	443	05.1147.40CCB	462	05.1177.40C	465	05.1227.14CNI	452	05.1257.14CDA	471	05.1307.14CCB	454
05.1117.40CNI	443	05.1147.40CDA	462	05.1177.40CCB	465	05.1227.40C	452	05.1257.14CNI	471	05.1307.14CDA	454
05.1121.14C	444	05.1147.40CNI	462	05.1177.40CDA	465	05.1227.40CCB	452	05.1257.40C	471	05.1307.14CNI	454
05.1121.14CCB	444	05.1151.14C	463	05.1177.40CNI	465	05.1227.40CDA	452	05.1257.40CCB	471	05.1307.40C	454
05.1121.14CDA	444	05.1151.14CCB	463	05.1201.14C	450	05.1227.40CNI	452	05.1257.40CDA	471	05.1307.40CCB	454
05.1121.14CNI	444	05.1151.14CDA	463	05.1201.14CCB	450	05.1231.14C	453	05.1257.40CNI	471	05.1307.40CDA	454
05.1121.40C	444	05.1151.14CNI	463	05.1201.14CDA	450	05.1231.14CCB	453	05.1261.14C	472	05.1307.40CNI	454
05.1121.40CCB	444	05.1151.40C	463	05.1201.14CNI	450	05.1231.14CDA	453	05.1261.14CCB	472	05.1311.14C	455
05.1121.40CDA	444	05.1151.40CCB	463	05.1201.40C	450	05.1231.14CNI	453	05.1261.14CDA	472	05.1311.14CCB	455
05.1121.40CNI	444	05.1151.40CDA	463	05.1201.40CCB	450	05.1231.40C	453	05.1261.14CNI	472	05.1311.14CDA	455
05.1122.14C	444	05.1151.40CNI	463	05.1201.40CDA	450	05.1231.40CCB	453	05.1261.40C	472	05.1311.14CNI	455
05.1122.14CCB	444	05.1152.14C	463	05.1201.40CNI	450	05.1231.40CDA	453	05.1261.40CCB	472	05.1311.40C	455
05.1122.14CDA	444	05.1152.14CCB	463	05.1202.14C	450	05.1231.40CNI	453	05.1261.40CDA	472	05.1311.40CCB	455
05.1122.14CNI	444	05.1152.14CDA	463	05.1202.14CCB	450	05.1232.14C	453	05.1261.40CNI	472	05.1311.40CDA	455
05.1122.40C	444	05.1152.14CNI	463	05.1202.14CDA	450	05.1232.14CCB	453	05.1262.14C	472	05.1311.40CNI	455
05.1122.40CCB	444	05.1152.40C	463	05.1202.14CNI	450	05.1232.14CDA	453	05.1262.14CCB	472	05.1312.14C	455
05.1122.40CDA	444	05.1152.40CCB	463	05.1202.40C	450	05.1232.14CNI	453	05.1262.14CDA	472	05.1312.14CCB	455
05.1122.40CNI	444	05.1152.40CDA	463	05.1202.40CCB	450	05.1232.40C	453	05.1262.14CNI	472	05.1312.14CDA	455
05.1126.14C	444	05.1152.40CNI	463	05.1202.40CDA	450	05.1232.40CCB	453	05.1262.40C	472	05.1312.14CNI	455
05.1126.14CCB	444	05.1156.14C	463	05.1202.40CNI	450	05.1232.40CDA	453	05.1262.40CCB	472	05.1312.40C	455
05.1126.14CDA	444	05.1156.14CCB	463	05.1206.14C	450	05.1232.40CNI	453	05.1262.40CDA	472	05.1312.40CCB	455
05.1126.14CNI	444	05.1156.14CDA	463	05.1206.14CCB	450	05.1236.14C	453	05.1262.40CNI	472	05.1312.40CDA	455
05.1126.40C	444	05.1156.14CNI	463	05.1206.14CDA	450	05.1236.14CCB	453	05.1266.14C	472	05.1312.40CNI	455
05.1126.40CCB	444	05.1156.40C	463	05.1206.14CNI	450	05.1236.14CDA	453	05.1266.14CCB	472	05.1316.14C	455
05.1126.40CDA	444	05.1156.40CCB	463	05.1206.40C	450	05.1236.14CNI	453	05.1266.14CDA	472	05.1316.14CCB	455
05.1126.40CNI	444	05.1156.40CDA	463	05.1206.40CCB	450	05.1236.40C	453	05.1266.14CNI	472	05.1316.14CDA	455
05.1127.14C	444	05.1156.40CNI	463	05.1206.40CDA	450	05.1236.40CCB	453	05.1266.40C	472	05.1316.14CNI	455
05.1127.14CCB	444	05.1157.14C	463	05.1206.40CNI	450	05.1236.40CDA	453	05.1266.40CCB	472	05.1316.40C	455
05.1127.14CDA	444	05.1157.14CCB	463	05.1207.14C	450	05.1236.40CNI	453	05.1266.40CDA	472	05.1316.40CCB	455
05.1127.14CNI	444	05.1157.14CDA	463	05.1207.14CCB	450	05.1237.14C	453	05.1266.40CNI	472	05.1316.40CDA	455
05.1127.40C	444	05.1157.14CNI	463	05.1207.14CDA	450	05.1237.14CCB	453	05.1267.14C	472	05.1316.40CNI	455
05.1127.40CCB	444	05.1157.40C	463	05.1207.14CNI	450	05.1237.14CDA	453	05.1267.14CCB	472	05.1317.14C	455
05.1127.40CDA	444	05.1157.40CCB	463	05.1207.40C	450	05.1237.14CNI	453	05.1267.14CDA	472	05.1317.14CCB	455
05.1127.40CNI	444	05.1157.40CDA	463	05.1207.40CCB	450	05.1237.40C	453	05.1267.14CNI	472	05.1317.14CDA	455
05.1131.14C	445	05.1157.40CNI	463	05.1207.40CDA	450	05.1237.40CCB	453	05.1267.40C	472	05.1317.14CNI	455
05.1131.14CCB	445	05.1161.14C	464	05.1207.40CNI	450	05.1237.40CDA	453	05.1267.40CCB	472	05.1317.40C	455
05.1131.14CDA	445	05.1161.14CCB	464	05.1211.14C	451	05.1237.40CNI	453	05.1267.40CDA	472	05.1317.40CCB	455
05.1131.14CNI	445	05.1161.14CDA	464	05.1211.14CCB	451	05.1241.14C	470	05.1267.40CNI	472	05.1317.40CDA	455
05.1131.40C	445	05.1161.14CNI	464	05.1211.14CDA	451	05.1241.14CCB	470	05.1271.14C	473	05.1317.40CNI	455
05.1131.40CCB	445	05.1161.40C	464	05.1211.14CNI	451	05.1241.14CDA	470	05.1271.14CCB	473	05.1321.14C	456
05.1131.40CDA	445	05.1161.40CCB	464	05.1211.40C	451	05.1241.14CNI	470	05.1271.14CDA	473	05.1321.14CCB	456
05.1131.40CNI	445	05.1161.40CDA	464	05.1211.40CCB	451	05.1241.40C	470	05.1271.14CNI	473	05.1321.14CDA	456
05.1132.14C	445	05.1161.40CNI	464	05.1211.40CDA	451	05.1241.40CCB	470	05.1271.40C	473	05.1321.14CNI	456
05.1132.14CCB	445	05.1162.14C	464	05.1211.40CNI	451	05.1241.40CDA	470	05.1271.40CCB	473	05.1321.40C	456
05.1132.14CDA	445	05.1162.14CCB	464	05.1212.14C	451	05.1241.40CNI	470	05.1271.40CDA	473	05.1321.40CCB	456
05.1132.14CNI	445	05.1162.14CDA	464	05.1212.14CCB	451	05.1242.14C	470	05.1271.40CNI	473	05.1321.40CDA	456
05.1132.40C	445	05.1162.14CNI	464	05.1212.14CDA	451	05.1242.14CCB	470	05.1272.14C	473	05.1321.40CNI	456
05.1132.40CCB	445	05.1162.40C	464	05.1212.14CNI	451	05.1242.14CDA	470	05.1272.14CCB	473	05.1322.14C	456
05.1132.40CDA	445	05.1162.40CCB	464	05.1212.40C	451	05.1242.14CNI	470	05.1272.14CDA	473	05.1322.14CCB	456

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.1322.14CDA	456	05.1352.14CCB	475	05.1402.14C	478	05.1431.40CNI	481	05.1461.40CDA	496	05.1511.40CCB	483
05.1322.14CNI	456	05.1352.14CDA	475	05.1402.14CCB	478	05.1432.14C	481	05.1461.40CNI	496	05.1511.40CDA	483
05.1322.40C	456	05.1352.14CNI	475	05.1402.14CDA	478	05.1432.14CCB	481	05.1462.14C	496	05.1511.40CNI	483
05.1322.40CCB	456	05.1352.40C	475	05.1402.14CNI	478	05.1432.14CDA	481	05.1462.14CCB	496	05.1512.14C	483
05.1322.40CDA	456	05.1352.40CCB	475	05.1402.40C	478	05.1432.14CNI	481	05.1462.14CDA	496	05.1512.14CCB	483
05.1322.40CNI	456	05.1352.40CDA	475	05.1402.40CCB	478	05.1432.40C	481	05.1462.14CNI	496	05.1512.14CDA	483
05.1326.14C	456	05.1352.40CNI	475	05.1402.40CDA	478	05.1432.40CCB	481	05.1462.40C	496	05.1512.14CNI	483
05.1326.14CCB	456	05.1356.14C	475	05.1402.40CNI	478	05.1432.40CDA	481	05.1462.40CCB	496	05.1512.40C	483
05.1326.14CDA	456	05.1356.14CCB	475	05.1406.14C	478	05.1432.40CNI	481	05.1462.40CDA	496	05.1512.40CCB	483
05.1326.14CNI	456	05.1356.14CDA	475	05.1406.14CCB	478	05.1436.14C	481	05.1462.40CNI	496	05.1512.40CDA	483
05.1326.40C	456	05.1356.14CNI	475	05.1406.14CDA	478	05.1436.14CCB	481	05.1466.14C	496	05.1512.40CNI	483
05.1326.40CCB	456	05.1356.40C	475	05.1406.14CNI	478	05.1436.14CDA	481	05.1466.14CCB	496	05.1516.14C	483
05.1326.40CDA	456	05.1356.40CCB	475	05.1406.40C	478	05.1436.14CNI	481	05.1466.14CDA	496	05.1516.14CCB	483
05.1326.40CNI	456	05.1356.40CDA	475	05.1406.40CCB	478	05.1436.40C	481	05.1466.14CNI	496	05.1516.14CDA	483
05.1327.14C	456	05.1356.40CNI	475	05.1406.40CDA	478	05.1436.40CCB	481	05.1466.40C	496	05.1516.14CNI	483
05.1327.14CCB	456	05.1357.14C	475	05.1406.40CNI	478	05.1436.40CDA	481	05.1466.40CCB	496	05.1516.40C	483
05.1327.14CDA	456	05.1357.14CCB	475	05.1407.14C	478	05.1436.40CNI	481	05.1466.40CDA	496	05.1516.40CCB	483
05.1327.14CNI	456	05.1357.14CDA	475	05.1407.14CCB	478	05.1437.14C	481	05.1466.40CNI	496	05.1516.40CDA	483
05.1327.40C	456	05.1357.14CNI	475	05.1407.14CDA	478	05.1437.14CCB	481	05.1467.14C	496	05.1516.40CNI	483
05.1327.40CCB	456	05.1357.40C	475	05.1407.14CNI	478	05.1437.14CDA	481	05.1467.14CCB	496	05.1517.14C	483
05.1327.40CDA	456	05.1357.40CCB	475	05.1407.40C	478	05.1437.14CNI	481	05.1467.14CDA	496	05.1517.14CCB	483
05.1327.40CNI	456	05.1357.40CDA	475	05.1407.40CCB	478	05.1437.40C	481	05.1467.14CNI	496	05.1517.14CDA	483
05.1331.14C	457	05.1357.40CNI	475	05.1407.40CDA	478	05.1437.40CCB	481	05.1467.40C	496	05.1517.14CNI	483
05.1331.14CCB	457	05.1361.14C	476	05.1407.40CNI	478	05.1437.40CDA	481	05.1467.40CCB	496	05.1517.40C	483
05.1331.14CDA	457	05.1361.14CCB	476	05.1411.14C	479	05.1437.40CNI	481	05.1467.40CDA	496	05.1517.40CCB	483
05.1331.14CNI	457	05.1361.14CDA	476	05.1411.14CCB	479	05.1441.14C	494	05.1467.40CNI	496	05.1517.40CDA	483
05.1331.40C	457	05.1361.14CNI	476	05.1411.14CDA	479	05.1441.14CCB	494	05.1471.14C	497	05.1517.40CNI	483
05.1331.40CCB	457	05.1361.40C	476	05.1411.14CNI	479	05.1441.14CDA	494	05.1471.14CCB	497	05.1521.14C	484
05.1331.40CDA	457	05.1361.40CCB	476	05.1411.40C	479	05.1441.14CNI	494	05.1471.14CDA	497	05.1521.14CCB	484
05.1331.40CNI	457	05.1361.40CDA	476	05.1411.40CCB	479	05.1441.40C	494	05.1471.14CNI	497	05.1521.14CDA	484
05.1332.14C	457	05.1361.40CNI	476	05.1411.40CDA	479	05.1441.40CCB	494	05.1471.40C	497	05.1521.14CNI	484
05.1332.14CCB	457	05.1362.14C	476	05.1411.40CNI	479	05.1441.40CDA	494	05.1471.40CCB	497	05.1521.40C	484
05.1332.14CDA	457	05.1362.14CCB	476	05.1412.14C	479	05.1441.40CNI	494	05.1471.40CDA	497	05.1521.40CCB	484
05.1332.14CNI	457	05.1362.14CDA	476	05.1412.14CCB	479	05.1442.14C	494	05.1471.40CNI	497	05.1521.40CDA	484
05.1332.40C	457	05.1362.14CNI	476	05.1412.14CDA	479	05.1442.14CCB	494	05.1472.14C	497	05.1521.40CNI	484
05.1332.40CCB	457	05.1362.40C	476	05.1412.14CNI	479	05.1442.14CDA	494	05.1472.14CCB	497	05.1522.14C	484
05.1332.40CDA	457	05.1362.40CCB	476	05.1412.40C	479	05.1442.14CNI	494	05.1472.14CDA	497	05.1522.14CCB	484
05.1332.40CNI	457	05.1362.40CDA	476	05.1412.40CCB	479	05.1442.40C	494	05.1472.14CNI	497	05.1522.14CDA	484
05.1336.14C	457	05.1362.40CNI	476	05.1412.40CDA	479	05.1442.40CCB	494	05.1472.40C	497	05.1522.14CNI	484
05.1336.14CCB	457	05.1366.14C	476	05.1412.40CNI	479	05.1442.40CDA	494	05.1472.40CCB	497	05.1522.40C	484
05.1336.14CDA	457	05.1366.14CCB	476	05.1416.14C	479	05.1442.40CNI	494	05.1472.40CDA	497	05.1522.40CCB	484
05.1336.14CNI	457	05.1366.14CDA	476	05.1416.14CCB	479	05.1446.14C	494	05.1472.40CNI	497	05.1522.40CDA	484
05.1336.40C	457	05.1366.14CNI	476	05.1416.14CDA	479	05.1446.14CCB	494	05.1476.14C	497	05.1522.40CNI	484
05.1336.40CCB	457	05.1366.40C	476	05.1416.14CNI	479	05.1446.14CDA	494	05.1476.14CCB	497	05.1526.14C	484
05.1336.40CDA	457	05.1366.40CCB	476	05.1416.40C	479	05.1446.14CNI	494	05.1476.14CDA	497	05.1526.14CCB	484
05.1336.40CNI	457	05.1366.40CDA	476	05.1416.40CCB	479	05.1446.40C	494	05.1476.14CNI	497	05.1526.14CDA	484
05.1337.14C	457	05.1366.40CNI	476	05.1416.40CDA	479	05.1446.40CCB	494	05.1476.40C	497	05.1526.14CNI	484
05.1337.14CCB	457	05.1367.14C	476	05.1416.40CNI	479	05.1446.40CDA	494	05.1476.40CCB	497	05.1526.40C	484
05.1337.14CDA	457	05.1367.14CCB	476	05.1417.14C	479	05.1446.40CNI	494	05.1476.40CDA	497	05.1526.40CCB	484
05.1337.14CNI	457	05.1367.14CDA	476	05.1417.14CCB	479	05.1447.14C	494	05.1476.40CNI	497	05.1526.40CDA	484
05.1337.40C	457	05.1367.14CNI	476	05.1417.14CDA	479	05.1447.14CCB	494	05.1477.14C	497	05.1526.40CNI	484
05.1337.40CCB	457	05.1367.40C	476	05.1417.14CNI	479	05.1447.14CDA	494	05.1477.14CCB	497	05.1527.14C	484
05.1337.40CDA	457	05.1367.40CCB	476	05.1417.40C	479	05.1447.14CNI	494	05.1477.14CDA	497	05.1527.14CCB	484
05.1337.40CNI	457	05.1367.40CDA	476	05.1417.40CCB	479	05.1447.40C	494	05.1477.14CNI	497	05.1527.14CDA	484
05.1341.14C	474	05.1367.40CNI	476	05.1417.40CDA	479	05.1447.40CCB	494	05.1477.40C	497	05.1527.14CNI	484
05.1341.14CCB	474	05.1371.14C	477	05.1417.40CNI	479	05.1447.40CDA	494	05.1477.40CCB	497	05.1527.40C	484
05.1341.14CDA	474	05.1371.14CCB	477	05.1421.14C	480	05.1447.40CNI	494	05.1477.40CDA	497	05.1527.40CCB	484
05.1341.14CNI	474	05.1371.14CDA	477	05.1421.14CCB	480	05.1451.14C	495	05.1477.40CNI	497	05.1527.40CDA	484
05.1341.40C	474	05.1371.14CNI	477	05.1421.14CDA	480	05.1451.14CCB	495	05.1501.14C	482	05.1527.40CNI	484
05.1341.40CCB	474	05.1371.40C	477	05.1421.14CNI	480	05.1451.14CDA	495	05.1501.14CCB	482	05.1531.14C	485
05.1341.40CDA	474	05.1371.40CCB	477	05.1421.40C	480	05.1451.14CNI	495	05.1501.14CDA	482	05.1531.14CCB	485
05.1341.40CNI	474	05.1371.40CDA	477	05.1421.40CCB	480	05.1451.40C	495	05.1501.14CNI	482	05.1531.14CDA	485
05.1342.14C	474	05.1371.40CNI	477	05.1421.40CDA	480	05.1451.40CCB	495	05.1501.40C	482	05.1531.14CNI	485
05.1342.14CCB	474	05.1372.14C	477	05.1421.40CNI	480	05.1451.40CDA	495	05.1501.40CCB	482	05.1531.40C	485
05.1342.14CDA	474	05.1372.14CCB	477	05.1422.14C	480	05.1451.40CNI	495	05.1501.40CDA	482	05.1531.40CCB	485
05.1342.14CNI	474	05.1372.14CDA	477	05.1422.14CCB	480	05.1452.14C	495	05.1501.40CNI	482	05.1531.40CDA	485
05.1342.40C	474	05.1372.14CNI	477	05.1422.14CDA	480	05.1452.14CCB	495	05.1502.14C	482	05.1531.40CNI	485
05.1342.40CCB	474	05.1372.40C	477	05.1422.14CNI	480	05.1452.14CDA	495	05.1502.14CCB	482	05.1532.14C	485
05.1342.40CDA	474	05.1372.40CCB	477	05.1422.40C	480	05.1452.14CNI	495	05.1502.14CDA	482	05.1532.14CCB	485
05.1342.40CNI	474	05.1372.40CDA	477	05.1422.40CCB	480	05.1452.40C	495	05.1502.14CNI	482	05.1532.14CDA	485
05.1346.14C	474	05.1372.40CNI	477	05.1422.40CDA	480	05.1452.40CCB	495	05.1502.40C	482	05.1532.14CNI	485
05.1346.14CCB	474	05.1376.14C	477	05.1422.40CNI	480	05.1452.40CDA	495	05.1502.40CCB	482	05.1532.40C	485
05.1346.14CDA	474	05.1376.14CCB	477	05.1426.14C	480	05.1452.40CNI	495	05.1502.40CDA	482	05.1532.40CCB	485
05.1346.14CNI	474	05.1376.14CDA	477	05.1426.14CCB	480	05.1456.14C	495	05.1502.40CNI	482	05.1532.40CDA	485
05.1346.40C	474	05.1376.14CNI	477	05.1426.14CDA	480	05.1456.14CCB	495	05.1506.14C	482	05.1532.40CNI	485
05.1346.40CCB	474	05.1376.40C	477	05.1426.14CNI	480	05.1456.14CDA	495	05.1506.14CCB	482	05.1536.14C	485
05.1346.40CDA	474	05.1376.40CCB	477	05.1426.40C	480	05.1456.14CNI	495	05.1506.14CDA	482	05.1536.14CCB	485
05.1346.40CNI	474	05.1376.40CDA	477	05.1426.40CCB	480	05.1456.40C	495	05.1506.14CNI	482	05.1536.14CDA	485
05.1347.14C	474	05.1376.40CNI	477	05.1426.40CDA	480	05.1456.40CCB	495	05.1506.40C	482	05.1536.14CNI	485
05.1347.14CCB	474	05.1377.14C	477	05.1426.40CNI	480	05.1456.40CDA	495	05.1506.40CCB	482	05.1536.40C	485
05.1347.14CDA	474	05.1377.14CCB	477	05.1427.14C	480	05.1456.40CNI	495	05.1506.40CDA	482	05.1536.40CCB	485
05.1347.14CNI	474	05.1377.14CDA	477	05.1427.14CCB	480	05.1457.14C	495	05.1506.40CNI	482	05.1536.40CDA	485
05.1347.40C	474	05.1377.14CNI	477	05.1427.14CDA	480	05.1457.14CCB	495	05.1507.14C	482	05.1536.40CNI	485
05.1347.40CCB	474	05.1377.40C	477	05.1427.14CNI	480	05.1457.14CDA	495	05.1507.14CCB	482	05.1537.14C	485
05.1347.40CDA	474	05.1377.40CCB	477	05.1427.40C	480	05.1457.14CNI	495	05.1507.14CDA	482	05.1537.14CCB	485
05.1347.40CNI	474	05.1377.40CDA	477	05.1427.40CCB	480	05.1457.40C	495	05.1507.14CNI	482	05.1537.14CDA	485
05.1351.14C	475	05.1377.40CNI	477	05.1427.40CDA	480	05.1457.40CCB	495	05.1507.40C	482	05.1537.14CNI	485
05.1351.14CCB	475	05.1401.14C	478	05.1427.40CNI	480	05.1457.40CDA	495	05.1507.40CCB	482	05.1537.40C	485
05.1351.14CDA	475	05.1401.14CCB	478	05.1431.14C	481	05.1457.40CNI	495	05.1507.40CDA	482	05.1537.40CCB	485
05.1351.14CNI	475	05.1401.14CDA	478	05.1431.14CCB	481	05.1461.14C	496	05.1507.40CNI	482	05.1537.40CDA	485
05.1351.40C	475	05.1401.14CNI	478	05.1431.14CDA	481	05.1461.14CCB	496	05.1511.14C	483	05.1537.40CNI	485
05.1351.40CCB	475	05.1401.40C	478	05.1431.14CNI	481	05.1461.14CDA	496	05.1511.14CCB	483	05.1541.14C	498
05.1351.40CDA	475	05.1401.40CCB	478	05.1431.40C	481	05.1461.14CNI	496	05.1511.14CDA	483	05.1541.14CCB	498
05.1351.40CNI	475	05.1401.40CDA	478	05.1431.40CCB	481	05.1461.40C	496	05.1511.14CNI	483	05.1541.14CDA	498
05.1352.14C	475	05.1401.40CNI	478	05.1431.40CDA	481	05.1461.40CCB	496	05.1511.40C	483	05.1541.14CNI	498

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.1541.40C	498	05.1571.14CNI	501	05.1621.14CDA	488	05.1651.14CCB	503	05.1701.14C	490	05.1727.40CNI	492
05.1541.40CCB	498	05.1571.40C	501	05.1621.14CNI	488	05.1651.14CDA	503	05.1701.14CCB	490	05.1731.14C	493
05.1541.40CDA	498	05.1571.40CCB	501	05.1621.40C	488	05.1651.14CNI	503	05.1701.14CDA	490	05.1731.14CCB	493
05.1541.40CNI	498	05.1571.40CDA	501	05.1621.40CCB	488	05.1651.40C	503	05.1701.14CNI	490	05.1731.14CDA	493
05.1542.14C	498	05.1571.40CNI	501	05.1621.40CDA	488	05.1651.40CCB	503	05.1701.40C	490	05.1731.14CNI	493
05.1542.14CCB	498	05.1572.14C	501	05.1621.40CNI	488	05.1651.40CDA	503	05.1701.40CCB	490	05.1731.40C	493
05.1542.14CDA	498	05.1572.14CCB	501	05.1622.14C	488	05.1651.40CNI	503	05.1701.40CDA	490	05.1731.40CCB	493
05.1542.14CNI	498	05.1572.14CDA	501	05.1622.14CCB	488	05.1652.14C	503	05.1701.40CNI	490	05.1731.40CDA	493
05.1542.40C	498	05.1572.14CNI	501	05.1622.14CDA	488	05.1652.14CCB	503	05.1702.14C	490	05.1731.40CNI	493
05.1542.40CCB	498	05.1572.40C	501	05.1622.14CNI	488	05.1652.14CDA	503	05.1702.14CCB	490	05.1732.14C	493
05.1542.40CDA	498	05.1572.40CCB	501	05.1622.40C	488	05.1652.14CNI	503	05.1702.14CDA	490	05.1732.14CCB	493
05.1542.40CNI	498	05.1572.40CDA	501	05.1622.40CCB	488	05.1652.40C	503	05.1702.14CNI	490	05.1732.14CDA	493
05.1546.14C	498	05.1572.40CNI	501	05.1622.40CDA	488	05.1652.40CCB	503	05.1702.40C	490	05.1732.14CNI	493
05.1546.14CCB	498	05.1576.14C	501	05.1622.40CNI	488	05.1652.40CDA	503	05.1702.40CCB	490	05.1732.40C	493
05.1546.14CDA	498	05.1576.14CCB	501	05.1626.14C	488	05.1652.40CNI	503	05.1702.40CDA	490	05.1732.40CCB	493
05.1546.14CNI	498	05.1576.14CDA	501	05.1626.14CCB	488	05.1656.14C	503	05.1702.40CNI	490	05.1732.40CDA	493
05.1546.40C	498	05.1576.14CNI	501	05.1626.14CDA	488	05.1656.14CCB	503	05.1706.14C	490	05.1732.40CNI	493
05.1546.40CCB	498	05.1576.40C	501	05.1626.14CNI	488	05.1656.14CDA	503	05.1706.14CCB	490	05.1736.14C	493
05.1546.40CDA	498	05.1576.40CCB	501	05.1626.40C	488	05.1656.14CNI	503	05.1706.14CDA	490	05.1736.14CCB	493
05.1546.40CNI	498	05.1576.40CDA	501	05.1626.40CCB	488	05.1656.40C	503	05.1706.14CNI	490	05.1736.14CDA	493
05.1547.14C	498	05.1576.40CNI	501	05.1626.40CDA	488	05.1656.40CCB	503	05.1706.40C	490	05.1736.14CNI	493
05.1547.14CCB	498	05.1577.14C	501	05.1626.40CNI	488	05.1656.40CDA	503	05.1706.40CCB	490	05.1736.40C	493
05.1547.14CDA	498	05.1577.14CCB	501	05.1627.14C	488	05.1656.40CNI	503	05.1706.40CDA	490	05.1736.40CCB	493
05.1547.14CNI	498	05.1577.14CDA	501	05.1627.14CCB	488	05.1657.14C	503	05.1706.40CNI	490	05.1736.40CDA	493
05.1547.40C	498	05.1577.14CNI	501	05.1627.14CDA	488	05.1657.14CCB	503	05.1707.14C	490	05.1736.40CNI	493
05.1547.40CCB	498	05.1577.40C	501	05.1627.14CNI	488	05.1657.14CDA	503	05.1707.14CCB	490	05.1737.14C	493
05.1547.40CDA	498	05.1577.40CCB	501	05.1627.40C	488	05.1657.14CNI	503	05.1707.14CDA	490	05.1737.14CCB	493
05.1547.40CNI	498	05.1577.40CDA	501	05.1627.40CCB	488	05.1657.40C	503	05.1707.14CNI	490	05.1737.14CDA	493
05.1551.14C	499	05.1577.40CNI	501	05.1627.40CDA	488	05.1657.40CCB	503	05.1707.40C	490	05.1737.14CNI	493
05.1551.14CCB	499	05.1601.14C	486	05.1627.40CNI	488	05.1657.40CDA	503	05.1707.40CCB	490	05.1737.40C	493
05.1551.14CDA	499	05.1601.14CCB	486	05.1631.14C	489	05.1657.40CNI	503	05.1707.40CDA	490	05.1737.40CCB	493
05.1551.14CNI	499	05.1601.14CDA	486	05.1631.14CCB	489	05.1661.14C	504	05.1707.40CNI	490	05.1737.40CDA	493
05.1551.40C	499	05.1601.14CNI	486	05.1631.14CDA	489	05.1661.14CCB	504	05.1711.14C	491	05.1737.40CNI	493
05.1551.40CCB	499	05.1601.40C	486	05.1631.14CNI	489	05.1661.14CDA	504	05.1711.14CCB	491	05.1741.14C	506
05.1551.40CDA	499	05.1601.40CCB	486	05.1631.40C	489	05.1661.14CNI	504	05.1711.14CDA	491	05.1741.14CCB	506
05.1551.40CNI	499	05.1601.40CDA	486	05.1631.40CCB	489	05.1661.40C	504	05.1711.14CNI	491	05.1741.14CDA	506
05.1552.14C	499	05.1601.40CNI	486	05.1631.40CDA	489	05.1661.40CCB	504	05.1711.40C	491	05.1741.14CNI	506
05.1552.14CCB	499	05.1602.14C	486	05.1631.40CNI	489	05.1661.40CDA	504	05.1711.40CCB	491	05.1741.40C	506
05.1552.14CDA	499	05.1602.14CCB	486	05.1632.14C	489	05.1661.40CNI	504	05.1711.40CDA	491	05.1741.40CCB	506
05.1552.14CNI	499	05.1602.14CDA	486	05.1632.14CCB	489	05.1662.14C	504	05.1711.40CNI	491	05.1741.40CDA	506
05.1552.40C	499	05.1602.14CNI	486	05.1632.14CDA	489	05.1662.14CCB	504	05.1712.14C	491	05.1741.40CNI	506
05.1552.40CCB	499	05.1602.40C	486	05.1632.14CNI	489	05.1662.14CDA	504	05.1712.14CCB	491	05.1742.14C	506
05.1552.40CDA	499	05.1602.40CCB	486	05.1632.40C	489	05.1662.14CNI	504	05.1712.14CDA	491	05.1742.14CCB	506
05.1552.40CNI	499	05.1602.40CDA	486	05.1632.40CCB	489	05.1662.40C	504	05.1712.14CNI	491	05.1742.14CDA	506
05.1556.14C	499	05.1602.40CNI	486	05.1632.40CDA	489	05.1662.40CCB	504	05.1712.40C	491	05.1742.14CNI	506
05.1556.14CCB	499	05.1606.14C	486	05.1632.40CNI	489	05.1662.40CDA	504	05.1712.40CCB	491	05.1742.40C	506
05.1556.14CDA	499	05.1606.14CCB	486	05.1636.14C	489	05.1662.40CNI	504	05.1712.40CDA	491	05.1742.40CCB	506
05.1556.14CNI	499	05.1606.14CDA	486	05.1636.14CCB	489	05.1666.14C	504	05.1712.40CNI	491	05.1742.40CDA	506
05.1556.40C	499	05.1606.14CNI	486	05.1636.14CDA	489	05.1666.14CCB	504	05.1716.14C	491	05.1742.40CNI	506
05.1556.40CCB	499	05.1606.40C	486	05.1636.14CNI	489	05.1666.14CDA	504	05.1716.14CCB	491	05.1746.14C	506
05.1556.40CDA	499	05.1606.40CCB	486	05.1636.40C	489	05.1666.14CNI	504	05.1716.14CDA	491	05.1746.14CCB	506
05.1556.40CNI	499	05.1606.40CDA	486	05.1636.40CCB	489	05.1666.40C	504	05.1716.14CNI	491	05.1746.14CDA	506
05.1557.14C	499	05.1606.40CNI	486	05.1636.40CDA	489	05.1666.40CCB	504	05.1716.40C	491	05.1746.14CNI	506
05.1557.14CCB	499	05.1607.14C	486	05.1636.40CNI	489	05.1666.40CDA	504	05.1716.40CCB	491	05.1746.40C	506
05.1557.14CDA	499	05.1607.14CCB	486	05.1637.14C	489	05.1666.40CNI	504	05.1716.40CDA	491	05.1746.40CCB	506
05.1557.14CNI	499	05.1607.14CDA	486	05.1637.14CCB	489	05.1667.14C	504	05.1716.40CNI	491	05.1746.40CDA	506
05.1557.40C	499	05.1607.14CNI	486	05.1637.14CDA	489	05.1667.14CCB	504	05.1717.14C	491	05.1746.40CNI	506
05.1557.40CCB	499	05.1607.40C	486	05.1637.14CNI	489	05.1667.14CDA	504	05.1717.14CCB	491	05.1747.14C	506
05.1557.40CDA	499	05.1607.40CCB	486	05.1637.40C	489	05.1667.14CNI	504	05.1717.14CDA	491	05.1747.14CCB	506
05.1557.40CNI	499	05.1607.40CDA	486	05.1637.40CCB	489	05.1667.40C	504	05.1717.14CNI	491	05.1747.14CDA	506
05.1561.14C	500	05.1607.40CNI	486	05.1637.40CDA	489	05.1667.40CCB	504	05.1717.40C	491	05.1747.14CNI	506
05.1561.14CCB	500	05.1611.14C	487	05.1637.40CNI	489	05.1667.40CDA	504	05.1717.40CCB	491	05.1747.40C	506
05.1561.14CDA	500	05.1611.14CCB	487	05.1641.14C	502	05.1667.40CNI	504	05.1717.40CDA	491	05.1747.40CCB	506
05.1561.14CNI	500	05.1611.14CDA	487	05.1641.14CCB	502	05.1671.14C	505	05.1717.40CNI	491	05.1747.40CDA	506
05.1561.40C	500	05.1611.14CNI	487	05.1641.14CDA	502	05.1671.14CCB	505	05.1721.14C	492	05.1747.40CNI	506
05.1561.40CCB	500	05.1611.40C	487	05.1641.14CNI	502	05.1671.14CDA	505	05.1721.14CCB	492	05.1751.14C	507
05.1561.40CDA	500	05.1611.40CCB	487	05.1641.40C	502	05.1671.14CNI	505	05.1721.14CDA	492	05.1751.14CCB	507
05.1561.40CNI	500	05.1611.40CDA	487	05.1641.40CCB	502	05.1671.40C	505	05.1721.14CNI	492	05.1751.14CDA	507
05.1562.14C	500	05.1611.40CNI	487	05.1641.40CDA	502	05.1671.40CCB	505	05.1721.40C	492	05.1751.14CNI	507
05.1562.14CCB	500	05.1612.14C	487	05.1641.40CNI	502	05.1671.40CDA	505	05.1721.40CCB	492	05.1751.40C	507
05.1562.14CDA	500	05.1612.14CCB	487	05.1642.14C	502	05.1671.40CNI	505	05.1721.40CDA	492	05.1751.40CCB	507
05.1562.14CNI	500	05.1612.14CDA	487	05.1642.14CCB	502	05.1672.14C	505	05.1721.40CNI	492	05.1751.40CDA	507
05.1562.40C	500	05.1612.14CNI	487	05.1642.14CDA	502	05.1672.14CCB	505	05.1722.14C	492	05.1751.40CNI	507
05.1562.40CCB	500	05.1612.40C	487	05.1642.14CNI	502	05.1672.14CDA	505	05.1722.14CCB	492	05.1752.14C	507
05.1562.40CDA	500	05.1612.40CCB	487	05.1642.40C	502	05.1672.14CNI	505	05.1722.14CDA	492	05.1752.14CCB	507
05.1562.40CNI	500	05.1612.40CDA	487	05.1642.40CCB	502	05.1672.40C	505	05.1722.14CNI	492	05.1752.14CDA	507
05.1566.14C	500	05.1612.40CNI	487	05.1642.40CDA	502	05.1672.40CCB	505	05.1722.40C	492	05.1752.14CNI	507
05.1566.14CCB	500	05.1616.14C	487	05.1642.40CNI	502	05.1672.40CDA	505	05.1722.40CCB	492	05.1752.40C	507
05.1566.14CDA	500	05.1616.14CCB	487	05.1646.14C	502	05.1672.40CNI	505	05.1722.40CDA	492	05.1752.40CCB	507
05.1566.14CNI	500	05.1616.14CDA	487	05.1646.14CCB	502	05.1676.14C	505	05.1722.40CNI	492	05.1752.40CDA	507
05.1566.40C	500	05.1616.14CNI	487	05.1646.14CDA	502	05.1676.14CCB	505	05.1726.14C	492	05.1752.40CNI	507
05.1566.40CCB	500	05.1616.40C	487	05.1646.14CNI	502	05.1676.14CDA	505	05.1726.14CCB	492	05.1756.14C	507
05.1566.40CDA	500	05.1616.40CCB	487	05.1646.40C	502	05.1676.14CNI	505	05.1726.14CDA	492	05.1756.14CCB	507
05.1566.40CNI	500	05.1616.40CDA	487	05.1646.40CCB	502	05.1676.40C	505	05.1726.14CNI	492	05.1756.14CDA	507
05.1567.14C	500	05.1616.40CNI	487	05.1646.40CDA	502	05.1676.40CCB	505	05.1726.40C	492	05.1756.14CNI	507
05.1567.14CCB	500	05.1617.14C	487	05.1646.40CNI	502	05.1676.40CDA	505	05.1726.40CCB	492	05.1756.40C	507
05.1567.14CDA	500	05.1617.14CCB	487	05.1647.14C	502	05.1676.40CNI	505	05.1726.40CDA	492	05.1756.40CCB	507
05.1567.14CNI	500	05.1617.14CDA	487	05.1647.14CCB	502	05.1677.14C	505	05.1726.40CNI	492	05.1756.40CDA	507
05.1567.40C	500	05.1617.14CNI	487	05.1647.14CDA	502	05.1677.14CCB	505	05.1727.14C	492	05.1756.40CNI	507
05.1567.40CCB	500	05.1617.40C	487	05.1647.14CNI	502	05.1677.14CDA	505	05.1727.14CCB	492	05.1757.14C	507
05.1567.40CDA	500	05.1617.40CCB	487	05.1647.40C	502	05.1677.14CNI	505	05.1727.14CDA	492	05.1757.14CCB	507
05.1567.40CNI	500	05.1617.40CDA	487	05.1647.40CCB	502	05.1677.40C	505	05.1727.14CNI	492	05.1757.14CDA	507
05.1571.14C	501	05.1617.40CNI	487	05.1647.40CDA	502	05.1677.40CCB	505	05.1727.40C	492	05.1757.14CNI	507
05.1571.14CCB	501	05.1621.14C	488	05.1647.40CNI	502	05.1677.40CDA	505	05.1727.40CCB	492	05.1757.40C	507
05.1571.14CDA	501	05.1621.14CCB	488	05.1651.14C	503	05.1677.40CNI	505	05.1727.40CDA	492	05.1757.40CCB	507

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.1757.40CDA	507	05.1811.40CDA	241	05.2173.14C	515	05.2507.ES	536	05.2618.40	549	05.2641.ER.NI	546
05.1757.40CNI	507	05.1812.14C	241	05.2173.14CDA	515	05.2508.14	536	05.2618.40.NI	549	05.2641.ES	546
05.1761.14C	508	05.1812.14CCB	241	05.2178.14C	515	05.2508.40	536	05.2618.ER	549	05.2641.ES.NI	546
05.1761.14CCB	508	05.1812.14CDA	241	05.2178.14CDA	515	05.2508.ER	536	05.2618.ER.NI	549	05.2643.14	546
05.1761.14CDA	508	05.1812.40C	241	05.2200.14C	512	05.2508.ES	536	05.2619.ES	549	05.2643.14.NI	546
05.1761.14CNI	508	05.1812.40CCB	241	05.2200.14CDA	512	05.2510.14	536	05.2619.ES.NI	549	05.2643.40	546
05.1761.40C	508	05.1812.40CDA	241	05.2201.14C	512	05.2510.40	536	05.2620.14	546	05.2643.40.NI	546
05.1761.40CCB	508	05.1816.14C	241	05.2201.14CDA	512	05.2510.ER	536	05.2620.14.NI	546	05.2643.ER	546
05.1761.40CDA	508	05.1816.14CCB	241	05.2205.14C	512	05.2510.ES	536	05.2620.40	546	05.2643.ER.NI	546
05.1761.40CNI	508	05.1816.14CDA	241	05.2205.14CDA	512	05.2511.14	536	05.2620.40.NI	546	05.2644.ES	546
05.1762.14C	508	05.1816.40C	241	05.2206.14C	512	05.2511.40	536	05.2621.14	546	05.2644.ES.NI	546
05.1762.14CCB	508	05.1816.40CCB	241	05.2206.14CDA	512	05.2511.ER	536	05.2621.14.NI	546	05.2645.14	547
05.1762.14CDA	508	05.1816.40CDA	241	05.2210.14C	513	05.2511.ES	536	05.2621.40	546	05.2645.14.NI	547
05.1762.14CNI	508	05.1817.14C	241	05.2210.14CDA	513	05.2512.14	536	05.2621.40.NI	546	05.2645.40	547
05.1762.40C	508	05.1817.14CCB	241	05.2211.14C	513	05.2512.40	536	05.2621.ER	546	05.2645.40.NI	547
05.1762.40CCB	508	05.1817.14CDA	241	05.2211.14CDA	513	05.2512.ER	536	05.2621.ER.NI	546	05.2646.14	547
05.1762.40CDA	508	05.1817.40C	241	05.2215.14C	513	05.2512.ES	536	05.2621.ES	546	05.2646.14.NI	547
05.1762.40CNI	508	05.1817.40CCB	241	05.2215.14CDA	513	05.2513.14	536	05.2621.ES.NI	546	05.2646.40	547
05.1766.14C	508	05.1817.40CDA	241	05.2216.14C	513	05.2513.40	536	05.2623.14	546	05.2646.40.NI	547
05.1766.14CCB	508	05.1821.14C	242	05.2216.14CDA	513	05.2513.ER	536	05.2623.14.NI	546	05.2646.ER	547
05.1766.14CDA	508	05.1821.14CCB	242	05.2220.14C	514	05.2513.ES	536	05.2623.40	546	05.2646.ER.NI	547
05.1766.14CNI	508	05.1821.14CDA	242	05.2220.14CDA	514	05.2600.14	546	05.2623.40.NI	546	05.2646.ES	547
05.1766.40C	508	05.1821.40C	242	05.2221.14C	514	05.2600.14.NI	546	05.2623.ER	546	05.2646.ES.NI	547
05.1766.40CCB	508	05.1821.40CCB	242	05.2221.14CDA	514	05.2600.40	546	05.2623.ER.NI	546	05.2648.14	547
05.1766.40CDA	508	05.1821.40CDA	242	05.2225.14C	514	05.2600.40.NI	546	05.2624.ES	546	05.2648.14.NI	547
05.1766.40CNI	508	05.1822.14C	242	05.2225.14CDA	514	05.2601.14	546	05.2624.ES.NI	546	05.2648.40	547
05.1767.14C	508	05.1822.14CCB	242	05.2226.14C	514	05.2601.14.NI	546	05.2625.14	547	05.2648.40.NI	547
05.1767.14CCB	508	05.1822.14CDA	242	05.2226.14CDA	514	05.2601.40	546	05.2625.14.NI	547	05.2648.ER	547
05.1767.14CDA	508	05.1822.40C	242	05.2230.14C	515	05.2601.40.NI	546	05.2625.40	547	05.2648.ER.NI	547
05.1767.14CNI	508	05.1822.40CCB	242	05.2230.14CDA	515	05.2601.ER	546	05.2625.40.NI	547	05.2649.ES	547
05.1767.40C	508	05.1822.40CDA	242	05.2231.14C	515	05.2601.ER.NI	546	05.2626.14	547	05.2649.ES.NI	547
05.1767.40CCB	508	05.1826.14C	242	05.2231.14CDA	515	05.2601.ES	546	05.2626.14.NI	547	05.2650.14	548
05.1767.40CDA	508	05.1826.14CCB	242	05.2235.14C	515	05.2601.ES.NI	546	05.2626.40	547	05.2650.14.NI	548
05.1767.40CNI	508	05.1826.14CDA	242	05.2235.14CDA	515	05.2603.14	546	05.2626.40.NI	547	05.2650.40	548
05.1771.14C	509	05.1826.40C	242	05.2236.14C	515	05.2603.14.NI	546	05.2626.ER	547	05.2650.40.NI	548
05.1771.14CCB	509	05.1826.40CCB	242	05.2236.14CDA	515	05.2603.40	546	05.2626.ER.NI	547	05.2651.14	548
05.1771.14CDA	509	05.1826.40CDA	242	05.2340.14C	512	05.2603.40.NI	546	05.2626.ES	547	05.2651.14.NI	548
05.1771.14CNI	509	05.1827.14C	242	05.2340.14CDA	512	05.2603.ER	546	05.2626.ES.NI	547	05.2651.40	548
05.1771.40C	509	05.1827.14CCB	242	05.2341.14C	512	05.2603.ER.NI	546	05.2628.14	547	05.2651.40.NI	548
05.1771.40CCB	509	05.1827.14CDA	242	05.2341.14CDA	512	05.2604.ES	546	05.2628.14.NI	547	05.2651.ER	548
05.1771.40CDA	509	05.1827.40C	242	05.2345.14C	512	05.2604.ES.NI	546	05.2628.40	547	05.2651.ER.NI	548
05.1771.40CNI	509	05.1827.40CCB	242	05.2345.14CDA	512	05.2605.14	547	05.2628.40.NI	547	05.2651.ES	548
05.1772.14C	509	05.1827.40CDA	242	05.2346.14C	512	05.2605.14.NI	547	05.2628.ER	547	05.2651.ES.NI	548
05.1772.14CCB	509	05.1831.14C	243	05.2346.14CDA	512	05.2605.40	547	05.2628.ER.NI	547	05.2653.14	548
05.1772.14CDA	509	05.1831.14CCB	243	05.2350.14C	513	05.2605.40.NI	547	05.2629.ES	547	05.2653.14.NI	548
05.1772.14CNI	509	05.1831.14CDA	243	05.2350.14CDA	513	05.2606.14	547	05.2629.ES.NI	547	05.2653.40	548
05.1772.40C	509	05.1831.40C	243	05.2351.14C	513	05.2606.14.NI	547	05.2630.14	548	05.2653.40.NI	548
05.1772.40CCB	509	05.1831.40CCB	243	05.2351.14CDA	513	05.2606.40	547	05.2630.14.NI	548	05.2653.ER	548
05.1772.40CDA	509	05.1831.40CDA	243	05.2355.14C	513	05.2606.40.NI	547	05.2630.40	548	05.2653.ER.NI	548
05.1772.40CNI	509	05.1832.14C	243	05.2355.14CDA	513	05.2606.ER	547	05.2630.40.NI	548	05.2654.ES	548
05.1776.14C	509	05.1832.14CCB	243	05.2356.14C	513	05.2606.ER.NI	547	05.2631.14	548	05.2654.ES.NI	548
05.1776.14CCB	509	05.1832.14CDA	243	05.2356.14CDA	513	05.2606.ES	547	05.2631.14.NI	548	05.2655.14	549
05.1776.14CDA	509	05.1832.40C	243	05.2360.14C	514	05.2606.ES.NI	547	05.2631.40	548	05.2655.14.NI	549
05.1776.14CNI	509	05.1832.40CCB	243	05.2360.14CDA	514	05.2608.14	547	05.2631.40.NI	548	05.2655.40	549
05.1776.40C	509	05.1832.40CDA	243	05.2361.14C	514	05.2608.14.NI	547	05.2631.ER	548	05.2655.40.NI	549
05.1776.40CCB	509	05.1836.14C	243	05.2361.14CDA	514	05.2608.40	547	05.2631.ER.NI	548	05.2656.14	549
05.1776.40CDA	509	05.1836.14CCB	243	05.2365.14C	514	05.2608.40.NI	547	05.2631.ES	548	05.2656.14.NI	549
05.1776.40CNI	509	05.1836.14CDA	243	05.2365.14CDA	514	05.2608.ER	547	05.2631.ES.NI	548	05.2656.40	549
05.1777.14C	509	05.1836.40C	243	05.2366.14C	514	05.2608.ER.NI	547	05.2633.14	548	05.2656.40.NI	549
05.1777.14CCB	509	05.1836.40CCB	243	05.2366.14CDA	514	05.2609.ES	547	05.2633.14.NI	548	05.2656.ER	549
05.1777.14CDA	509	05.1836.40CDA	243	05.2370.14C	515	05.2609.ES.NI	547	05.2633.40	548	05.2656.ER.NI	549
05.1777.14CNI	509	05.1837.14C	243	05.2370.14CDA	515	05.2610.14	548	05.2633.40.NI	548	05.2656.ES	549
05.1777.40C	509	05.1837.14CCB	243	05.2371.14C	515	05.2610.14.NI	548	05.2633.ER	548	05.2656.ES.NI	549
05.1777.40CCB	509	05.1837.14CDA	243	05.2371.14CDA	515	05.2610.40	548	05.2633.ER.NI	548	05.2658.14	549
05.1777.40CDA	509	05.1837.40C	243	05.2375.14C	515	05.2610.40.NI	548	05.2634.ES	548	05.2658.14.NI	549
05.1777.40CNI	509	05.1837.40CCB	243	05.2375.14CDA	515	05.2611.14	548	05.2634.ES.NI	548	05.2658.40	549
05.1801.14C	240	05.1837.40CDA	243	05.2376.14C	515	05.2611.14.NI	548	05.2635.14	549	05.2658.40.NI	549
05.1801.14CCB	240	05.2103.40C	512	05.2376.14CDA	515	05.2611.40	548	05.2635.14.NI	549	05.2658.ER	549
05.1801.14CDA	240	05.2103.40CDA	512	05.2500.14	536	05.2611.40.NI	548	05.2635.40	549	05.2658.ER.NI	549
05.1801.40C	240	05.2108.40C	512	05.2500.40	536	05.2611.ER	548	05.2635.40.NI	549	05.2659.ES	549
05.1801.40CCB	240	05.2108.40CDA	512	05.2500.ER	536	05.2611.ER.NI	548	05.2636.14	549	05.2659.ES.NI	549
05.1801.40CDA	240	05.2113.40C	513	05.2500.ES	536	05.2611.ES	548	05.2636.14.NI	549	05.2700.14	542
05.1802.14C	240	05.2113.40CDA	513	05.2501.14	536	05.2611.ES.NI	548	05.2636.40	549	05.2700.40	542
05.1802.14CCB	240	05.2118.40C	513	05.2501.40	536	05.2613.14	548	05.2636.40.NI	549	05.2701.14	542
05.1802.14CDA	240	05.2118.40CDA	513	05.2501.ER	536	05.2613.14.NI	548	05.2636.ER	549	05.2701.40	542
05.1802.40C	240	05.2123.40C	514	05.2501.ES	536	05.2613.40	548	05.2636.ER.NI	549	05.2701.ER	542
05.1802.40CCB	240	05.2123.40CDA	514	05.2502.14	536	05.2613.40.NI	548	05.2636.ES	549	05.2701.ES	542
05.1802.40CDA	240	05.2128.40C	514	05.2502.40	536	05.2613.ER	548	05.2636.ES.NI	549	05.2703.14	542
05.1806.14C	240	05.2128.40CDA	514	05.2502.ER	536	05.2613.ER.NI	548	05.2638.14	549	05.2703.40	542
05.1806.14CCB	240	05.2133.40C	515	05.2502.ES	536	05.2614.ES	548	05.2638.14.NI	549	05.2703.ER	542
05.1806.14CDA	240	05.2133.40CDA	515	05.2503.14	536	05.2614.ES.NI	548	05.2638.40	549	05.2704.ES	542
05.1806.40C	240	05.2138.40C	515	05.2503.40	536	05.2615.14	549	05.2638.40.NI	549	05.2705.14	542
05.1806.40CCB	240	05.2138.40CDA	515	05.2503.ER	536	05.2615.14.NI	549	05.2638.ER	549	05.2705.40	542
05.1806.40CDA	240	05.2143.14C	512	05.2503.ES	536	05.2615.40	549	05.2638.ER.NI	549	05.2706.14	542
05.1807.14C	240	05.2143.14CDA	512	05.2505.14	536	05.2615.40.NI	549	05.2639.ES	549	05.2706.40	542
05.1807.14CCB	240	05.2148.14C	512	05.2505.40	536	05.2616.14	549	05.2639.ES.NI	549	05.2706.ER	542
05.1807.14CDA	240	05.2148.14CDA	512	05.2505.ER	536	05.2616.14.NI	549	05.2640.14	546	05.2706.ES	542
05.1807.40C	240	05.2153.14C	513	05.2505.ES	536	05.2616.40	549	05.2640.14.NI	546	05.2708.14	542
05.1807.40CCB	240	05.2153.14CDA	513	05.2506.14	536	05.2616.40.NI	549	05.2640.40	546	05.2708.40	542
05.1807.40CDA	240	05.2158.14C	513	05.2506.40	536	05.2616.ER	549	05.2640.40.NI	546	05.2708.ER	542
05.1811.14C	241	05.2158.14CDA	513	05.2506.ER	536	05.2616.ER.NI	549	05.2641.14	546	05.2709.ES	542
05.1811.14CCB	241	05.2163.14C	514	05.2506.ES	536	05.2616.ES	549	05.2641.14.NI	546	05.2710.14	543
05.1811.14CDA	241	05.2163.14CDA	514	05.2507.14	536	05.2616.ES.NI	549	05.2641.40	546	05.2710.40	543
05.1811.40C	241	05.2168.14C	514	05.2507.40	536	05.2618.14	549	05.2641.40.NI	546	05.2711.14	543
05.1811.40CCB	241	05.2168.14CDA	514	05.2507.ER	536	05.2618.14.NI	549	05.2641.ER	546	05.2711.40	543

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.2711.ER	543	05.2956.C5A	68	05.3221.40.1V	168	05.3550.40.DA	283	05.3560.ER.DA	140	05.3565.40.DA	140
05.2711.ES	543	05.2957.C5A	68	05.3221.40.DA	168	05.3551.14	107	05.3560.ES.1V	140	05.3565.ER.1V	140
05.2713.14	543	05.2958.C5A	68	05.3221.ER	168	05.3551.14	283	05.3560.ESA	36	05.3565.ERA	36
05.2713.40	543	05.2960.C5	69	05.3221.ER.1V	168	05.3551.14.1V	107	05.3560.ESA	140	05.3565.ERA	140
05.2713.ER	543	05.2961.C5	69	05.3221.ER.DA	168	05.3551.14.1V	283	05.3560.ES.DA	36	05.3565.ER.DA	36
05.2714.ES	543	05.2962.C5	69	05.3221.ES	168	05.3551.14.CB	107	05.3560.ES.DA	140	05.3565.ER.DA	140
05.2720.14	542	05.2965.C5	69	05.3221.ES.1V	168	05.3551.14.CB	283	05.3561.14.1V	140	05.3565.ES.1V	140
05.2720.40	542	05.2966.C5	69	05.3221.ES.DA	168	05.3551.14.DA	107	05.3561.14A	36	05.3565.ESA	36
05.2721.14	542	05.2967.C5	69	05.3230.14	169	05.3551.14.DA	283	05.3561.14A	140	05.3565.ESA	140
05.2721.40	542	05.2970.C5A	68	05.3230.14.1V	169	05.3551.40	107	05.3561.14.DA	36	05.3565.ES.DA	36
05.2721.ER	542	05.2971.C5A	68	05.3230.14.DA	169	05.3551.40	283	05.3561.14.DA	140	05.3565.ES.DA	140
05.2721.ES	542	05.2972.C5A	68	05.3230.40	169	05.3551.40.1V	107	05.3561.40.1V	140	05.3570.14	141
05.2723.14	542	05.2973.C5A	68	05.3230.40.1V	169	05.3551.40.1V	283	05.3561.40A	36	05.3570.14.1V	141
05.2723.40	542	05.2975.C5A	68	05.3230.40.DA	169	05.3551.40.CB	107	05.3561.40A	140	05.3570.14.DA	141
05.2723.ER	542	05.2976.C5A	68	05.3230.ER	169	05.3551.40.CB	283	05.3561.40.DA	36	05.3570.40	141
05.2724.ES	542	05.2977.C5A	68	05.3230.ER.1V	169	05.3551.40.DA	107	05.3561.40.DA	140	05.3570.40.1V	141
05.2725.14	542	05.2978.C5A	68	05.3230.ER.DA	169	05.3551.40.DA	283	05.3561.ER.1V	140	05.3570.40.DA	141
05.2725.40	542	05.2980.C5	69	05.3230.ES	169	05.3552.14	107	05.3561.ERA	36	05.3570.ER	141
05.2726.14	542	05.2981.C5	69	05.3230.ES.1V	169	05.3552.14	283	05.3561.ERA	140	05.3570.ER.1V	141
05.2726.40	542	05.2982.C5	69	05.3230.ES.DA	169	05.3552.14.1V	107	05.3561.ER.DA	36	05.3570.ER.DA	141
05.2726.ER	542	05.2985.C5	69	05.3231.14	169	05.3552.14.1V	283	05.3561.ER.DA	140	05.3570.ES	141
05.2726.ES	542	05.2986.C5	69	05.3231.14.1V	169	05.3552.14.CB	107	05.3561.ES.1V	140	05.3570.ES.1V	141
05.2728.14	542	05.2987.C5	69	05.3231.14.DA	169	05.3552.14.CB	283	05.3561.ESA	36	05.3570.ES.DA	141
05.2728.40	542	05.2990.C5	70	05.3231.40	169	05.3552.14.DA	107	05.3561.ESA	140	05.3571.14	141
05.2728.ER	542	05.2991.C5	71	05.3231.40.1V	169	05.3552.14.DA	283	05.3561.ES.DA	36	05.3571.14.1V	141
05.2729.ES	542	05.2992.C5	70	05.3231.40.DA	169	05.3552.40	107	05.3561.ES.DA	140	05.3571.14.DA	141
05.2730.14	543	05.2993.C5	71	05.3231.ER	169	05.3552.40	283	05.3562.14.1V	140	05.3571.40	141
05.2730.40	543	05.2994.C5	72	05.3231.ER.1V	169	05.3552.40.1V	107	05.3562.14A	36	05.3571.40.1V	141
05.2731.14	543	05.2995.C5	73	05.3231.ER.DA	169	05.3552.40.1V	283	05.3562.14A	140	05.3571.40.DA	141
05.2731.40	543	05.2996.C5	72	05.3231.ES	169	05.3552.40.CB	107	05.3562.14.DA	36	05.3571.ER	141
05.2731.ER	543	05.2997.C5	73	05.3231.ES.1V	169	05.3552.40.CB	283	05.3562.14.DA	140	05.3571.ER.1V	141
05.2731.ES	543	05.3200.14	168	05.3231.ES.DA	169	05.3552.40.DA	107	05.3562.40.1V	140	05.3571.ER.DA	141
05.2733.14	543	05.3200.14.1V	168	05.3500.DR	751	05.3552.40.DA	283	05.3562.40A	36	05.3571.ES	141
05.2733.40	543	05.3200.14.DA	168	05.3500.DR.DA	751	05.3553.14	107	05.3562.40A	140	05.3571.ES.1V	141
05.2733.ER	543	05.3200.40	168	05.3500.DR.NI	751	05.3553.14	283	05.3562.40.DA	36	05.3571.ES.DA	141
05.2734.ES	543	05.3200.40.1V	168	05.3500.DY	751	05.3553.14.1V	107	05.3562.40.DA	140	05.3572.14	141
05.2740.14	542	05.3200.40.DA	168	05.3500.DY.DA	751	05.3553.14.1V	283	05.3562.ER.1V	140	05.3572.14.1V	141
05.2740.40	542	05.3200.ER	168	05.3500.DY.NI	751	05.3553.14.CB	107	05.3562.ERA	36	05.3572.14.DA	141
05.2741.14	542	05.3200.ER.1V	168	05.3500.ER	751	05.3553.14.CB	283	05.3562.ERA	140	05.3572.40	141
05.2741.40	542	05.3200.ER.DA	168	05.3500.ER.DA	751	05.3553.14.DA	107	05.3562.ER.DA	36	05.3572.40.1V	141
05.2741.ER	542	05.3200.ES	168	05.3500.ER.NI	751	05.3553.14.DA	283	05.3562.ER.DA	140	05.3572.40.DA	141
05.2741.ES	542	05.3200.ES.1V	168	05.3500.ES	751	05.3553.40	107	05.3562.ES.1V	140	05.3572.ER	141
05.2743.14	542	05.3200.ES.DA	168	05.3500.ES.DA	751	05.3553.40	283	05.3562.ESA	36	05.3572.ER.1V	141
05.2743.40	542	05.3201.14	168	05.3500.ES.NI	751	05.3553.40.1V	107	05.3562.ESA	140	05.3572.ER.DA	141
05.2743.ER	542	05.3201.14.1V	168	05.3501.DR	751	05.3553.40.1V	283	05.3562.ES.DA	36	05.3572.ES	141
05.2744.ES	542	05.3201.14.DA	168	05.3501.DR.DA	751	05.3553.40.CB	107	05.3562.ES.DA	140	05.3572.ES.1V	141
05.2745.14	542	05.3201.40	168	05.3501.DR.NI	751	05.3553.40.CB	283	05.3563.14.1V	140	05.3572.ES.DA	141
05.2745.40	542	05.3201.40.1V	168	05.3501.DY	751	05.3553.40.DA	107	05.3563.14A	36	05.3573.14	141
05.2746.14	542	05.3201.40.DA	168	05.3501.DY.DA	751	05.3553.40.DA	283	05.3563.14A	140	05.3573.14.1V	141
05.2746.40	542	05.3201.ER	168	05.3501.DY.NI	751	05.3554.14	107	05.3563.14.DA	36	05.3573.14.DA	141
05.2746.ER	542	05.3201.ER.1V	168	05.3501.ER	751	05.3554.14	283	05.3563.14.DA	140	05.3573.40	141
05.2746.ES	542	05.3201.ER.DA	168	05.3501.ER.DA	751	05.3554.14.1V	107	05.3563.40.1V	140	05.3573.40.1V	141
05.2748.14	542	05.3201.ES	168	05.3501.ER.NI	751	05.3554.14.1V	283	05.3563.40A	36	05.3573.40.DA	141
05.2748.40	542	05.3201.ES.1V	168	05.3501.ES	751	05.3554.14.CB	107	05.3563.40A	140	05.3573.ER	141
05.2748.ER	542	05.3201.ES.DA	168	05.3501.ES.DA	751	05.3554.14.CB	283	05.3563.40.DA	36	05.3573.ER.1V	141
05.2749.ES	542	05.3210.14	169	05.3501.ES.NI	751	05.3554.14.DA	107	05.3563.40.DA	140	05.3573.ER.DA	141
05.2750.14	543	05.3210.14.1V	169	05.3505.DR	751	05.3554.14.DA	283	05.3563.ER.1V	140	05.3573.ES	141
05.2750.40	543	05.3210.14.DA	169	05.3505.DR.DA	751	05.3554.40	107	05.3563.ERA	36	05.3573.ES.1V	141
05.2751.14	543	05.3210.40	169	05.3505.DR.NI	751	05.3554.40	283	05.3563.ERA	140	05.3573.ES.DA	141
05.2751.40	543	05.3210.40.1V	169	05.3505.DY	751	05.3554.40.1V	107	05.3563.ER.DA	36	05.3574.14	141
05.2751.ER	543	05.3210.40.DA	169	05.3505.DY.DA	751	05.3554.40.1V	283	05.3563.ER.DA	140	05.3574.14.1V	141
05.2751.ES	543	05.3210.ER	169	05.3505.DY.NI	751	05.3554.40.CB	107	05.3563.ES.1V	140	05.3574.14.DA	141
05.2753.14	543	05.3210.ER.1V	169	05.3505.ER	751	05.3554.40.CB	283	05.3563.ESA	36	05.3574.40	141
05.2753.40	543	05.3210.ER.DA	169	05.3505.ER.DA	751	05.3554.40.DA	107	05.3563.ESA	140	05.3574.40.1V	141
05.2753.ER	543	05.3210.ES	169	05.3505.ER.NI	751	05.3554.40.DA	283	05.3563.ES.DA	36	05.3574.40.DA	141
05.2754.ES	543	05.3210.ES.1V	169	05.3505.ES	751	05.3555.14	107	05.3563.ES.DA	140	05.3574.ER	141
05.2900.C5	66	05.3210.ES.DA	169	05.3505.ES.DA	751	05.3555.14	283	05.3564.14.1V	140	05.3574.ER.1V	141
05.2901.C5	66	05.3211.14	169	05.3505.ES.NI	751	05.3555.14.1V	107	05.3564.14A	36	05.3574.ER.DA	141
05.2902.C5	66	05.3211.14.1V	169	05.3506.DR	751	05.3555.14.1V	283	05.3564.14A	140	05.3574.ES	141
05.2905.C5	66	05.3211.14.DA	169	05.3506.DR.DA	751	05.3555.14.CB	107	05.3564.14.DA	36	05.3574.ES.1V	141
05.2906.C5	66	05.3211.40	169	05.3506.DR.NI	751	05.3555.14.CB	283	05.3564.14.DA	140	05.3574.ES.DA	141
05.2907.C5	66	05.3211.40.1V	169	05.3506.DY	751	05.3555.14.DA	107	05.3564.40.1V	140	05.3575.14	141
05.2910.C5	67	05.3211.40.DA	169	05.3506.DY.DA	751	05.3555.14.DA	283	05.3564.40A	36	05.3575.14.1V	141
05.2911.C5	67	05.3211.ER	169	05.3506.DY.NI	751	05.3555.40	107	05.3564.40A	140	05.3575.14.DA	141
05.2912.C5	67	05.3211.ER.1V	169	05.3506.ER	751	05.3555.40	283	05.3564.40.DA	36	05.3575.40	141
05.2915.C5	67	05.3211.ER.DA	169	05.3506.ER.DA	751	05.3555.40.1V	107	05.3564.40.DA	140	05.3575.40.1V	141
05.2916.C5	67	05.3211.ES	169	05.3506.ER.NI	751	05.3555.40.1V	283	05.3564.ER.1V	140	05.3575.40.DA	141
05.2917.C5	67	05.3211.ES.1V	169	05.3506.ES	751	05.3555.40.CB	107	05.3564.ERA	36	05.3575.ER	141
05.2920.C5	66	05.3211.ES.DA	169	05.3506.ES.DA	751	05.3555.40.CB	283	05.3564.ERA	140	05.3575.ER.1V	141
05.2921.C5	66	05.3220.14	168	05.3506.ES.NI	751	05.3555.40.DA	107	05.3564.ER.DA	36	05.3575.ER.DA	141
05.2922.C5	66	05.3220.14.1V	168	05.3550.14	107	05.3555.40.DA	283	05.3564.ER.DA	140	05.3575.ES	141
05.2925.C5	66	05.3220.14.DA	168	05.3550.14	283	05.3560.14.1V	140	05.3564.ES.1V	140	05.3575.ES.1V	141
05.2926.C5	66	05.3220.40	168	05.3550.14.1V	107	05.3560.14A	36	05.3564.ESA	36	05.3575.ES.DA	141
05.2927.C5	66	05.3220.40.1V	168	05.3550.14.1V	283	05.3560.14A	140	05.3564.ESA	140	05.4380.GY	346
05.2930.C5	67	05.3220.40.DA	168	05.3550.14.CB	107	05.3560.14.DA	36	05.3564.ES.DA	36	05.4380.OW	346
05.2931.C5	67	05.3220.ER	168	05.3550.14.CB	283	05.3560.14.DA	140	05.3564.ES.DA	140	05.4380.OW.78	346
05.2932.C5	67	05.3220.ER.1V	168	05.3550.14.DA	107	05.3560.40.1V	140	05.3565.14.1V	140	05.4380.RY	346
05.2935.C5	67	05.3220.ER.DA	168	05.3550.14.DA	283	05.3560.40A	36	05.3565.14A	36	05.4380.ZY	346
05.2936.C5	67	05.3220.ES	168	05.3550.40	107	05.3560.40A	140	05.3565.14A	140	05.4385.GY	346
05.2937.C5	67	05.3220.ES.1V	168	05.3550.40	283	05.3560.40.DA	36	05.3565.14.DA	36	05.4385.OW	346
05.2950.C5A	68	05.3220.ES.DA	168	05.3550.40.1V	107	05.3560.40.DA	140	05.3565.14.DA	140	05.4385.OW.78	346
05.2951.C5A	68	05.3221.14	168	05.3550.40.1V	283	05.3560.ER.1V	140	05.3565.40.1V	140	05.4385.RY	346
05.2952.C5A	68	05.3221.14.1V	168	05.3550.40.CB	107	05.3560.ERA	36	05.3565.40A	36	05.4385.ZY	346
05.2953.C5A	68	05.3221.14.DA	168	05.3550.40.CB	283	05.3560.ERA	140	05.3565.40A	140	05.4500.14.CB	18
05.2955.C5A	68	05.3221.40	168	05.3550.40.DA	107	05.3560.ER.DA	36	05.3565.40.DA	36	05.4500.14.DA	18

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.4500.40.CB	18	05.4520.14.DA	23	05.4550.14.CB	19	05.4565.ES.DA	29	05.4585.ES.CB	33	05.4622.ER.DA	23
05.4500.40.DA	18	05.4520.40.CB	23	05.4550.14.DA	19	05.4570.14.CB	24	05.4585.ES.DA	33	05.4622.ES.CB	23
05.4500.ER.CB	18	05.4520.40.DA	23	05.4550.40.CB	19	05.4570.14.DA	24	05.4590.14.CB	27	05.4622.ES.DA	23
05.4500.ER.DA	18	05.4520.ER.CB	23	05.4550.40.DA	19	05.4570.40.CB	24	05.4590.40.CB	27	05.4624.14.CB	23
05.4500.ES.CB	18	05.4520.ER.DA	23	05.4550.ER.CB	19	05.4570.40.DA	24	05.4590.ER.CB	27	05.4624.14.DA	23
05.4500.ES.DA	18	05.4520.ES.CB	23	05.4550.ER.DA	19	05.4570.ER.CB	24	05.4590.ES.CB	27	05.4624.40.CB	23
05.4501.14.CB	18	05.4520.ES.DA	23	05.4550.ES.CB	19	05.4570.ER.DA	24	05.4591.14.CB	27	05.4624.40.DA	23
05.4501.14.DA	18	05.4521.14.CB	23	05.4550.ES.DA	19	05.4570.ES.CB	24	05.4591.40.CB	27	05.4624.ER.CB	23
05.4501.40.CB	18	05.4521.14.DA	23	05.4551.14.CB	19	05.4570.ES.DA	24	05.4591.ER.CB	27	05.4624.ER.DA	23
05.4501.40.DA	18	05.4521.40.CB	23	05.4551.14.DA	19	05.4571.14.CB	25	05.4591.ES.CB	27	05.4624.ES.CB	23
05.4501.ER.CB	18	05.4521.40.DA	23	05.4551.40.CB	19	05.4571.14.DA	25	05.4592.14.CB	27	05.4624.ES.DA	23
05.4501.ER.DA	18	05.4521.ER.CB	23	05.4551.40.DA	19	05.4571.40.CB	25	05.4592.40.CB	27	05.4630.14.CB	32
05.4501.ES.CB	18	05.4521.ER.DA	23	05.4551.ER.CB	19	05.4571.40.DA	25	05.4592.ER.CB	27	05.4630.14.DA	32
05.4501.ES.DA	18	05.4521.ES.CB	23	05.4551.ER.DA	19	05.4571.ER.CB	25	05.4592.ES.CB	27	05.4630.40.CB	32
05.4502.14.CB	18	05.4521.ES.DA	23	05.4551.ES.CB	19	05.4571.ER.DA	25	05.4593.14.CB	27	05.4630.40.DA	32
05.4502.14.DA	18	05.4522.14.CB	23	05.4551.ES.DA	19	05.4571.ES.CB	25	05.4593.40.CB	27	05.4630.ER.CB	32
05.4502.40.CB	18	05.4522.14.DA	23	05.4552.14.CB	19	05.4571.ES.DA	25	05.4593.ER.CB	27	05.4630.ER.DA	32
05.4502.40.DA	18	05.4522.40.CB	23	05.4552.14.DA	19	05.4572.14.CB	24	05.4593.ES.CB	27	05.4630.ES.CB	32
05.4502.ER.CB	18	05.4522.40.DA	23	05.4552.40.CB	19	05.4572.14.DA	24	05.4595.14.CB	24	05.4630.ES.DA	32
05.4502.ER.DA	18	05.4522.ER.CB	23	05.4552.40.DA	19	05.4572.40.CB	24	05.4595.14.DA	24	05.4632.14.CB	32
05.4502.ES.CB	18	05.4522.ER.DA	23	05.4552.ER.CB	19	05.4572.40.DA	24	05.4595.40.CB	24	05.4632.14.DA	32
05.4502.ES.DA	18	05.4522.ES.CB	23	05.4552.ER.DA	19	05.4572.ER.CB	24	05.4595.40.DA	24	05.4632.40.CB	32
05.4503.14.CB	18	05.4522.ES.DA	23	05.4552.ES.CB	19	05.4572.ER.DA	24	05.4595.ER.CB	24	05.4632.40.DA	32
05.4503.14.DA	18	05.4523.14.CB	23	05.4552.ES.DA	19	05.4572.ES.CB	24	05.4595.ER.DA	24	05.4632.ER.CB	32
05.4503.40.CB	18	05.4523.14.DA	23	05.4553.14.CB	19	05.4572.ES.DA	24	05.4595.ES.CB	24	05.4632.ER.DA	32
05.4503.40.DA	18	05.4523.40.CB	23	05.4553.14.DA	19	05.4573.14.CB	25	05.4595.ES.DA	24	05.4632.ES.CB	32
05.4503.ER.CB	18	05.4523.40.DA	23	05.4553.40.CB	19	05.4573.14.DA	25	05.4596.14.CB	25	05.4632.ES.DA	32
05.4503.ER.DA	18	05.4523.ER.CB	23	05.4553.40.DA	19	05.4573.40.CB	25	05.4596.14.DA	25	05.4634.14.CB	32
05.4503.ES.CB	18	05.4523.ER.DA	23	05.4553.ER.CB	19	05.4573.40.DA	25	05.4596.40.CB	25	05.4634.14.DA	32
05.4503.ES.DA	18	05.4523.ES.CB	23	05.4553.ER.DA	19	05.4573.ER.CB	25	05.4596.40.DA	25	05.4634.40.CB	32
05.4504.14.CB	18	05.4523.ES.DA	23	05.4553.ES.CB	19	05.4573.ER.DA	25	05.4596.ER.CB	25	05.4634.40.DA	32
05.4504.14.DA	18	05.4524.14.CB	23	05.4553.ES.DA	19	05.4573.ES.CB	25	05.4596.ER.DA	25	05.4634.ER.CB	32
05.4504.40.CB	18	05.4524.14.DA	23	05.4554.14.CB	19	05.4573.ES.DA	25	05.4596.ES.CB	25	05.4634.ER.DA	32
05.4504.40.DA	18	05.4524.40.CB	23	05.4554.14.DA	19	05.4574.14.CB	24	05.4596.ES.DA	25	05.4634.ES.CB	32
05.4504.ER.CB	18	05.4524.40.DA	23	05.4554.40.CB	19	05.4574.14.DA	24	05.4600.14.CB	18	05.4634.ES.DA	32
05.4504.ER.DA	18	05.4524.ER.CB	23	05.4554.40.DA	19	05.4574.40.CB	24	05.4600.14.DA	18	05.4650.14.CB	19
05.4504.ES.CB	18	05.4524.ER.DA	23	05.4554.ER.CB	19	05.4574.40.DA	24	05.4600.40.CB	18	05.4650.14.DA	19
05.4504.ES.DA	18	05.4524.ES.CB	23	05.4554.ER.DA	19	05.4574.ER.CB	24	05.4600.40.DA	18	05.4650.40.CB	19
05.4505.14.CB	18	05.4524.ES.DA	23	05.4554.ES.CB	19	05.4574.ER.DA	24	05.4600.ER.CB	18	05.4650.40.DA	19
05.4505.14.DA	18	05.4525.14.CB	23	05.4554.ES.DA	19	05.4574.ES.CB	24	05.4600.ER.DA	18	05.4650.ER.CB	19
05.4505.40.CB	18	05.4525.14.DA	23	05.4555.14.CB	19	05.4574.ES.DA	24	05.4600.ES.CB	18	05.4650.ER.DA	19
05.4505.40.DA	18	05.4525.40.CB	23	05.4555.14.DA	19	05.4575.14.CB	25	05.4600.ES.DA	18	05.4650.ES.CB	19
05.4505.ER.CB	18	05.4525.40.DA	23	05.4555.40.CB	19	05.4575.14.DA	25	05.4602.14.CB	18	05.4650.ES.DA	19
05.4505.ER.DA	18	05.4525.ER.CB	23	05.4555.40.DA	19	05.4575.40.CB	25	05.4602.14.DA	18	05.4652.14.CB	19
05.4505.ES.CB	18	05.4525.ER.DA	23	05.4555.ER.CB	19	05.4575.40.DA	25	05.4602.40.CB	18	05.4652.14.DA	19
05.4505.ES.DA	18	05.4525.ES.CB	23	05.4555.ER.DA	19	05.4575.ER.CB	25	05.4602.40.DA	18	05.4652.40.CB	19
05.4510.14.CB	28	05.4525.ES.DA	23	05.4555.ES.CB	19	05.4575.ER.DA	25	05.4602.ER.CB	18	05.4652.40.DA	19
05.4510.14.DA	28	05.4530.14.CB	32	05.4555.ES.DA	19	05.4575.ES.CB	25	05.4602.ER.DA	18	05.4652.ER.CB	19
05.4510.40.CB	28	05.4530.14.DA	32	05.4560.14.CB	29	05.4575.ES.DA	25	05.4602.ES.CB	18	05.4652.ER.DA	19
05.4510.40.DA	28	05.4530.40.CB	32	05.4560.14.DA	29	05.4580.14.CB	33	05.4602.ES.DA	18	05.4652.ES.CB	19
05.4510.ER.CB	28	05.4530.40.DA	32	05.4560.40.CB	29	05.4580.14.DA	33	05.4604.14.CB	18	05.4652.ES.DA	19
05.4510.ER.DA	28	05.4530.ER.CB	32	05.4560.40.DA	29	05.4580.40.CB	33	05.4604.14.DA	18	05.4654.14.CB	19
05.4510.ES.CB	28	05.4530.ER.DA	32	05.4560.ER.CB	29	05.4580.40.DA	33	05.4604.40.CB	18	05.4654.14.DA	19
05.4510.ES.DA	28	05.4530.ES.CB	32	05.4560.ER.DA	29	05.4580.ER.CB	33	05.4604.40.DA	18	05.4654.40.CB	19
05.4511.14.CB	28	05.4530.ES.DA	32	05.4560.ES.CB	29	05.4580.ER.DA	33	05.4604.ER.CB	18	05.4654.40.DA	19
05.4511.14.DA	28	05.4531.14.CB	32	05.4560.ES.DA	29	05.4580.ES.CB	33	05.4604.ER.DA	18	05.4654.ER.CB	19
05.4511.40.CB	28	05.4531.14.DA	32	05.4561.14.CB	29	05.4580.ES.DA	33	05.4604.ES.CB	18	05.4654.ER.DA	19
05.4511.40.DA	28	05.4531.40.CB	32	05.4561.14.DA	29	05.4581.14.CB	33	05.4604.ES.DA	18	05.4654.ES.CB	19
05.4511.ER.CB	28	05.4531.40.DA	32	05.4561.40.CB	29	05.4581.14.DA	33	05.4610.14.CB	28	05.4654.ES.DA	19
05.4511.ER.DA	28	05.4531.ER.CB	32	05.4561.40.DA	29	05.4581.40.CB	33	05.4610.14.DA	28	05.4660.14.CB	29
05.4511.ES.CB	28	05.4531.ER.DA	32	05.4561.ER.CB	29	05.4581.40.DA	33	05.4610.40.CB	28	05.4660.14.DA	29
05.4511.ES.DA	28	05.4531.ES.CB	32	05.4561.ER.DA	29	05.4581.ER.CB	33	05.4610.40.DA	28	05.4660.40.CB	29
05.4512.14.CB	28	05.4531.ES.DA	32	05.4561.ES.CB	29	05.4581.ER.DA	33	05.4610.ER.CB	28	05.4660.40.DA	29
05.4512.14.DA	28	05.4532.14.CB	32	05.4561.ES.DA	29	05.4581.ES.CB	33	05.4610.ER.DA	28	05.4660.ER.CB	29
05.4512.40.CB	28	05.4532.14.DA	32	05.4562.14.CB	29	05.4581.ES.DA	33	05.4610.ES.CB	28	05.4660.ER.DA	29
05.4512.40.DA	28	05.4532.40.CB	32	05.4562.14.DA	29	05.4582.14.CB	33	05.4610.ES.DA	28	05.4660.ES.CB	29
05.4512.ER.CB	28	05.4532.40.DA	32	05.4562.40.CB	29	05.4582.14.DA	33	05.4612.14.CB	28	05.4660.ES.DA	29
05.4512.ER.DA	28	05.4532.ER.CB	32	05.4562.40.DA	29	05.4582.40.CB	33	05.4612.14.DA	28	05.4662.14.CB	29
05.4512.ES.CB	28	05.4532.ER.DA	32	05.4562.ER.CB	29	05.4582.40.DA	33	05.4612.40.CB	28	05.4662.14.DA	29
05.4512.ES.DA	28	05.4532.ES.CB	32	05.4562.ER.DA	29	05.4582.ER.CB	33	05.4612.40.DA	28	05.4662.40.CB	29
05.4513.14.CB	28	05.4532.ES.DA	32	05.4562.ES.CB	29	05.4582.ER.DA	33	05.4612.ER.CB	28	05.4662.40.DA	29
05.4513.14.DA	28	05.4533.14.CB	32	05.4562.ES.DA	29	05.4582.ES.CB	33	05.4612.ER.DA	28	05.4662.ER.CB	29
05.4513.40.CB	28	05.4533.14.DA	32	05.4563.14.CB	29	05.4582.ES.DA	33	05.4612.ES.CB	28	05.4662.ER.DA	29
05.4513.40.DA	28	05.4533.40.CB	32	05.4563.14.DA	29	05.4583.14.CB	33	05.4612.ES.DA	28	05.4662.ES.CB	29
05.4513.ER.CB	28	05.4533.40.DA	32	05.4563.40.CB	29	05.4583.14.DA	33	05.4614.14.CB	28	05.4662.ES.DA	29
05.4513.ER.DA	28	05.4533.ER.CB	32	05.4563.40.DA	29	05.4583.40.CB	33	05.4614.14.DA	28	05.4664.14.CB	29
05.4513.ES.CB	28	05.4533.ER.DA	32	05.4563.ER.CB	29	05.4583.40.DA	33	05.4614.40.CB	28	05.4664.14.DA	29
05.4513.ES.DA	28	05.4533.ES.CB	32	05.4563.ER.DA	29	05.4583.ER.CB	33	05.4614.40.DA	28	05.4664.40.CB	29
05.4514.14.CB	28	05.4533.ES.DA	32	05.4563.ES.CB	29	05.4583.ER.DA	33	05.4614.ER.CB	28	05.4664.40.DA	29
05.4514.14.DA	28	05.4534.14.CB	32	05.4563.ES.DA	29	05.4583.ES.CB	33	05.4614.ER.DA	28	05.4664.ER.CB	29
05.4514.40.CB	28	05.4534.14.DA	32	05.4564.14.CB	29	05.4583.ES.DA	33	05.4614.ES.CB	28	05.4664.ER.DA	29
05.4514.40.DA	28	05.4534.40.CB	32	05.4564.14.DA	29	05.4584.14.CB	33	05.4614.ES.DA	28	05.4664.ES.CB	29
05.4514.ER.CB	28	05.4534.40.DA	32	05.4564.40.CB	29	05.4584.14.DA	33	05.4620.14.CB	23	05.4664.ES.DA	29
05.4514.ER.DA	28	05.4534.ER.CB	32	05.4564.40.DA	29	05.4584.40.CB	33	05.4620.14.DA	23	05.4670.14.CB	24
05.4514.ES.CB	28	05.4534.ER.DA	32	05.4564.ER.CB	29	05.4584.40.DA	33	05.4620.40.CB	23	05.4670.14.DA	24
05.4514.ES.DA	28	05.4534.ES.CB	32	05.4564.ER.DA	29	05.4584.ER.CB	33	05.4620.40.DA	23	05.4670.40.CB	24
05.4515.14.CB	28	05.4534.ES.DA	32	05.4564.ES.CB	29	05.4584.ER.DA	33	05.4620.ER.CB	23	05.4670.40.DA	24
05.4515.14.DA	28	05.4535.14.CB	32	05.4564.ES.DA	29	05.4584.ES.CB	33	05.4620.ER.DA	23	05.4670.ER.CB	24
05.4515.40.CB	28	05.4535.14.DA	32	05.4565.14.CB	29	05.4584.ES.DA	33	05.4620.ES.CB	23	05.4670.ER.DA	24
05.4515.40.DA	28	05.4535.40.CB	32	05.4565.14.DA	29	05.4585.14.CB	33	05.4620.ES.DA	23	05.4670.ES.CB	24
05.4515.ER.CB	28	05.4535.40.DA	32	05.4565.40.CB	29	05.4585.14.DA	33	05.4622.14.CB	23	05.4670.ES.DA	24
05.4515.ER.DA	28	05.4535.ER.CB	32	05.4565.40.DA	29	05.4585.40.CB	33	05.4622.14.DA	23	05.4672.14.CB	24
05.4515.ES.CB	28	05.4535.ER.DA	32	05.4565.ER.CB	29	05.4585.40.DA	33	05.4622.40.CB	23	05.4672.14.DA	24
05.4515.ES.DA	28	05.4535.ES.CB	32	05.4565.ER.DA	29	05.4585.ER.CB	33	05.4622.40.DA	23	05.4672.40.CB	24
05.4520.14.CB	23	05.4535.ES.DA	32	05.4565.ES.CB	29	05.4585.ER.DA	33	05.4622.ER.CB	23	05.4672.40.DA	24

QUICK SEARCH OF PRODUCT

Ref.	Page
05.4672.ER.CB	24
05.4672.ER.DA	24
05.4672.ES.CB	24
05.4672.ES.DA	24
05.4674.14.CB	24
05.4674.14.DA	24
05.4674.40.CB	24
05.4674.40.DA	24
05.4674.ER.CB	24
05.4674.ER.DA	24
05.4674.ES.CB	24
05.4674.ES.DA	24
05.4680.14.CB	33
05.4680.14.DA	33
05.4680.40.CB	33
05.4680.40.DA	33
05.4680.ER.CB	33
05.4680.ER.DA	33
05.4680.ES.CB	33
05.4680.ES.DA	33
05.4682.14.CB	33
05.4682.14.DA	33
05.4682.40.CB	33
05.4682.40.DA	33
05.4682.ER.CB	33
05.4682.ER.DA	33
05.4682.ES.CB	33
05.4682.ES.DA	33
05.4684.14.CB	33
05.4684.14.DA	33
05.4684.40.CB	33
05.4684.40.DA	33
05.4684.ER.CB	33
05.4684.ER.DA	33
05.4684.ES.CB	33
05.4684.ES.DA	33
05.4690.14.CB	27
05.4690.40.CB	27
05.4690.ER.CB	27
05.4690.ES.CB	27
05.4692.14.CB	27
05.4692.40.CB	27
05.4692.ER.CB	27
05.4692.ES.CB	27
05.4695.14.CB	24
05.4695.14.DA	24
05.4695.40.CB	24
05.4695.40.DA	24
05.4695.ER.CB	24
05.4695.ER.DA	24
05.4695.ES.CB	24
05.4695.ES.DA	24
05.5100.14	40
05.5100.14	142
05.5100.14.1V	143
05.5100.14.CB	40
05.5100.14.CB	142
05.5100.14.DA	41
05.5100.14.DA	143
05.5100.40	40
05.5100.40	142
05.5100.40.1V	143
05.5100.40.CB	40
05.5100.40.CB	142
05.5100.40.DA	41
05.5100.40.DA	143
05.5100.ER	40
05.5100.ER	142
05.5100.ER.1V	143
05.5100.ER.CB	40
05.5100.ER.CB	142
05.5100.ER.DA	41
05.5100.ER.DA	143
05.5100.ES	40
05.5100.ES	142
05.5100.ES.1V	143
05.5100.ES.CB	40
05.5100.ES.CB	142
05.5100.ES.DA	41
05.5100.ES.DA	143
05.5101.14	40
05.5101.14	142
05.5101.14.1V	143
05.5101.14.CB	40
05.5101.14.CB	142
05.5101.14.DA	41
05.5101.14.DA	143
05.5101.40	40
05.5101.40	142
05.5101.40.1V	143
05.5101.40.CB	40
05.5101.40.CB	142
05.5101.40.DA	41
05.5101.40.DA	143
05.5101.ER	40
05.5101.ER	142
05.5101.ER.1V	143
05.5101.ER.CB	40
05.5101.ER.CB	142
05.5101.ER.DA	41
05.5101.ER.DA	143
05.5101.ES	40
05.5101.ES	142
05.5101.ES.1V	143
05.5101.ES.CB	40
05.5101.ES.CB	142
05.5101.ES.DA	41
05.5101.ES.DA	143
05.5105.14	40
05.5105.14	142
05.5105.14.1V	143
05.5105.14.CB	40
05.5105.14.CB	142
05.5105.14.DA	41
05.5105.14.DA	143
05.5105.40	40
05.5105.40	142
05.5105.40.1V	143
05.5105.40.CB	40
05.5105.40.CB	142
05.5105.40.DA	41
05.5105.40.DA	143
05.5105.ER	40
05.5105.ER	142
05.5105.ER.1V	143
05.5105.ER.CB	40
05.5105.ER.CB	142
05.5105.ER.DA	41
05.5105.ER.DA	143
05.5105.ES	40
05.5105.ES	142
05.5105.ES.1V	143
05.5105.ES.CB	40
05.5105.ES.CB	142
05.5105.ES.DA	41
05.5105.ES.DA	143
05.5106.14	40
05.5106.14	142
05.5106.14.1V	143
05.5106.14.CB	40
05.5106.14.CB	142
05.5106.14.DA	41
05.5106.14.DA	143
05.5106.40	40
05.5106.40	142
05.5106.40.1V	143
05.5106.40.CB	40
05.5106.40.CB	142
05.5106.40.DA	41
05.5106.40.DA	143
05.5106.ER	40
05.5106.ER	142
05.5106.ER.1V	143
05.5106.ER.CB	40
05.5106.ER.CB	142
05.5106.ER.DA	41
05.5106.ER.DA	143
05.5106.ES	40
05.5106.ES	142
05.5106.ES.1V	143
05.5106.ES.CB	40
05.5106.ES.CB	142
05.5106.ES.DA	41
05.5106.ES.DA	143
05.5110.14	42
05.5110.14	144
05.5110.14.1V	145
05.5110.14.CB	42
05.5110.14.CB	144
05.5110.14.DA	43
05.5110.14.DA	145
05.5110.40	42
05.5110.40	144
05.5110.40.1V	145
05.5110.40.CB	42
05.5110.40.CB	144
05.5110.40.DA	43
05.5110.40.DA	145
05.5110.ER	42
05.5110.ER	144
05.5110.ER.1V	145
05.5110.ER.CB	42
05.5110.ER.CB	144
05.5110.ER.DA	43
05.5110.ER.DA	145
05.5110.ES	42
05.5110.ES	144
05.5110.ES.1V	145
05.5110.ES.CB	42
05.5110.ES.CB	144
05.5110.ES.DA	43
05.5110.ES.DA	145
05.5111.14	42
05.5111.14	144
05.5111.14.1V	145
05.5111.14.CB	42
05.5111.14.CB	144
05.5111.14.DA	43
05.5111.14.DA	145
05.5111.40	42
05.5111.40	144
05.5111.40.1V	145
05.5111.40.CB	42
05.5111.40.CB	144
05.5111.40.DA	43
05.5111.40.DA	145
05.5111.ER	42
05.5111.ER	144
05.5111.ER.1V	145
05.5111.ER.CB	42
05.5111.ER.CB	144
05.5111.ER.DA	43
05.5111.ER.DA	145
05.5111.ES	42
05.5111.ES	144
05.5111.ES.1V	145
05.5111.ES.CB	42
05.5111.ES.CB	144
05.5111.ES.DA	43
05.5111.ES.DA	145
05.5115.14	42
05.5115.14	144
05.5115.14.1V	145
05.5115.14.CB	42
05.5115.14.CB	144
05.5115.14.DA	43
05.5115.14.DA	145
05.5115.40	42
05.5115.40	144
05.5115.40.1V	145
05.5115.40.CB	42
05.5115.40.CB	144
05.5115.40.DA	43
05.5115.40.DA	145
05.5115.ER	42
05.5115.ER	144
05.5115.ER.1V	145
05.5115.ER.CB	42
05.5115.ER.CB	144
05.5115.ER.DA	43
05.5115.ER.DA	145
05.5115.ES	42
05.5115.ES	144
05.5115.ES.1V	145
05.5115.ES.CB	42
05.5115.ES.CB	144
05.5115.ES.DA	43
05.5115.ES.DA	145
05.5116.14	42
05.5116.14	144
05.5116.14.1V	145
05.5116.14.CB	42
05.5116.14.CB	144
05.5116.14.DA	43
05.5116.14.DA	145
05.5116.40	42
05.5116.40	144
05.5116.40.1V	145
05.5116.40.CB	42
05.5116.40.CB	144
05.5116.40.DA	43
05.5116.40.DA	145
05.5116.ER	42
05.5116.ER	144
05.5116.ER.1V	145
05.5116.ER.CB	42
05.5116.ER.CB	144
05.5116.ER.DA	43
05.5116.ER.DA	145
05.5116.ES	42
05.5116.ES	144
05.5116.ES.1V	145
05.5116.ES.CB	42
05.5116.ES.CB	144
05.5116.ES.DA	43
05.5116.ES.DA	145
05.5120.14	44
05.5120.14	146
05.5120.14.1V	147
05.5120.14.CB	44
05.5120.14.CB	146
05.5120.14.DA	45
05.5120.14.DA	147
05.5120.40	44
05.5120.40	146
05.5120.40.1V	147
05.5120.40.CB	44
05.5120.40.CB	146
05.5120.40.DA	45
05.5120.40.DA	147
05.5120.ER	44
05.5120.ER	146
05.5120.ER.1V	147
05.5120.ER.CB	44
05.5120.ER.CB	146
05.5120.ER.DA	45
05.5120.ER.DA	147
05.5120.ES	44
05.5120.ES	146
05.5120.ES.1V	147
05.5120.ES.CB	44
05.5120.ES.CB	146
05.5120.ES.DA	45
05.5120.ES.DA	147
05.5121.14	44
05.5121.14	146
05.5121.14.1V	147
05.5121.14.CB	44
05.5121.14.CB	146
05.5121.14.DA	45
05.5121.14.DA	147
05.5121.40	44
05.5121.40	146
05.5121.40.1V	147
05.5121.40.CB	44
05.5121.40.CB	146
05.5121.40.DA	45
05.5121.40.DA	147
05.5121.ER	44
05.5121.ER	146
05.5121.ER.1V	147
05.5121.ER.CB	44
05.5121.ER.CB	146
05.5121.ER.DA	45
05.5121.ER.DA	147
05.5121.ES	44
05.5121.ES	146
05.5121.ES.1V	147
05.5121.ES.CB	44
05.5121.ES.CB	146
05.5121.ES.DA	45
05.5121.ES.DA	147
05.5122.14	44
05.5122.14	146
05.5122.14.1V	147
05.5122.14.CB	44
05.5122.14.CB	146
05.5122.14.DA	45
05.5122.14.DA	147
05.5122.40	44
05.5122.40	146
05.5122.40.1V	147
05.5122.40.CB	44
05.5122.40.CB	146
05.5122.40.DA	45
05.5122.40.DA	147
05.5122.ER	44
05.5122.ER	146
05.5122.ER.1V	147
05.5122.ER.CB	44
05.5122.ER.CB	146
05.5122.ER.DA	45
05.5122.ER.DA	147
05.5122.ES	44
05.5122.ES	146
05.5122.ES.1V	147
05.5122.ES.CB	44
05.5122.ES.CB	146
05.5122.ES.DA	45
05.5122.ES.DA	147
05.5125.14	44
05.5125.14	146
05.5125.14.1V	147
05.5125.14.CB	44
05.5125.14.CB	146
05.5125.14.DA	45
05.5125.14.DA	147
05.5125.40	44
05.5125.40	146
05.5125.40.1V	147
05.5125.40.CB	44
05.5125.40.CB	146
05.5125.40.DA	45
05.5125.40.DA	147
05.5125.ER	44
05.5125.ER	146
05.5125.ER.1V	147
05.5125.ER.CB	44
05.5125.ER.CB	146
05.5125.ER.DA	45
05.5125.ER.DA	147
05.5125.ES	44
05.5125.ES	146
05.5125.ES.1V	147
05.5125.ES.CB	44
05.5125.ES.CB	146
05.5125.ES.DA	45
05.5125.ES.DA	147
05.5126.14	44
05.5126.14	146
05.5126.14.1V	147
05.5126.14.CB	44
05.5126.14.CB	146
05.5126.14.DA	45
05.5126.14.DA	147
05.5126.40	44
05.5126.40	146
05.5126.40.1V	147
05.5126.40.CB	44
05.5126.40.CB	146
05.5126.40.DA	45
05.5126.40.DA	147
05.5126.ER	44
05.5126.ER	146
05.5126.ER.1V	147
05.5126.ER.CB	44
05.5126.ER.CB	146
05.5126.ER.DA	45
05.5126.ER.DA	147
05.5126.ES	44
05.5126.ES	146
05.5126.ES.1V	147
05.5126.ES.CB	44
05.5126.ES.CB	146
05.5126.ES.DA	45
05.5126.ES.DA	147
05.5127.14	44
05.5127.14	146
05.5127.14.1V	147
05.5127.14.CB	44
05.5127.14.CB	146
05.5127.14.DA	45
05.5127.14.DA	147
05.5127.40	44
05.5127.40	146
05.5127.40.1V	147
05.5127.40.CB	44
05.5127.40.CB	146
05.5127.40.DA	45
05.5127.40.DA	147
05.5127.ER	44
05.5127.ER	146
05.5127.ER.1V	147
05.5127.ER.CB	44
05.5127.ER.CB	146
05.5127.ER.DA	45
05.5127.ER.DA	147
05.5127.ES	44
05.5127.ES	146
05.5127.ES.1V	147
05.5127.ES.CB	44
05.5127.ES.CB	146
05.5127.ES.DA	45
05.5127.ES.DA	147
05.5130.14	148
05.5130.14.1V	149
05.5130.14.CB	148
05.5130.14.DA	149
05.5130.40	148
05.5130.40.1V	149
05.5130.40.CB	148
05.5130.40.DA	149
05.5130.ER	148
05.5130.ER.1V	149
05.5130.ER.CB	148
05.5130.ER.DA	149
05.5130.ES	148
05.5130.ES.1V	149
05.5130.ES.CB	148
05.5130.ES.DA	149
05.5131.14	148
05.5131.14.1V	149
05.5131.14.CB	148
05.5131.14.DA	149
05.5131.40	148
05.5131.40.1V	149
05.5131.40.CB	148
05.5131.40.DA	149
05.5131.ER	148
05.5131.ER.1V	149
05.5131.ER.CB	148
05.5131.ER.DA	149
05.5131.ES	148
05.5131.ES.1V	149
05.5131.ES.CB	148
05.5131.ES.DA	149
05.5135.14	148
05.5135.14.1V	149
05.5135.14.CB	148
05.5135.14.DA	149
05.5135.40	148
05.5135.40.1V	149
05.5135.40.CB	148
05.5135.40.DA	149
05.5135.ER	148
05.5135.ER.1V	149
05.5135.ER.CB	148
05.5135.ER.DA	149
05.5135.ES	148
05.5135.ES.1V	149
05.5135.ES.CB	148
05.5135.ES.DA	149
05.5136.14	148
05.5136.14.1V	149
05.5136.14.CB	148
05.5136.14.DA	149
05.5136.40	148
05.5136.40.1V	149
05.5136.40.CB	148
05.5136.40.DA	149
05.5136.ER	148
05.5136.ER.1V	149
05.5136.ER.CB	148
05.5136.ER.DA	149
05.5136.ES	148
05.5136.ES.1V	149
05.5136.ES.CB	148
05.5136.ES.DA	149
05.5140.14	46
05.5140.14	162
05.5140.14.1V	163
05.5140.14.CB	46
05.5140.14.CB	162
05.5140.14.DA	47
05.5140.14.DA	163
05.5140.40	46
05.5140.40	162
05.5140.40.1V	163
05.5140.40.CB	46
05.5140.40.CB	162
05.5140.40.DA	47
05.5140.40.DA	163
05.5140.ER	46
05.5140.ER	162
05.5140.ER.1V	163
05.5140.ER.CB	46
05.5140.ER.CB	162
05.5140.ER.DA	47
05.5140.ER.DA	163
05.5140.ES	46
05.5140.ES	162
05.5140.ES.1V	163
05.5140.ES.CB	46
05.5140.ES.CB	162
05.5140.ES.DA	47
05.5140.ES.DA	163
05.5141.14	46
05.5141.14	162
05.5141.14.1V	163
05.5141.14.CB	46
05.5141.14.CB	162
05.5141.14.DA	47
05.5141.14.DA	163
05.5141.40	46
05.5141.40	162
05.5141.40.1V	163
05.5141.40.CB	46
05.5141.40.CB	162
05.5141.40.DA	47
05.5141.40.DA	163
05.5141.ER	46
05.5141.ER	162
05.5141.ER.1V	163
05.5141.ER.CB	46
05.5141.ER.CB	162
05.5141.ER.DA	47
05.5141.ER.DA	163
05.5141.ES	46
05.5141.ES	162
05.5141.ES.1V	163
05.5141.ES.CB	46
05.5141.ES.CB	162
05.5141.ES.DA	47
05.5141.ES.DA	163
05.5145.14	46
05.5145.14	162
05.5145.14.1V	163
05.5145.14.CB	46
05.5145.14.CB	162
05.5145.14.DA	47

QUICK SEARCH OF PRODUCT

Ref.	Page
05.5145.14.DA	163
05.5145.40	46
05.5145.40	162
05.5145.40.1V	163
05.5145.40.CB	46
05.5145.40.CB	162
05.5145.40.DA	47
05.5145.40.DA	163
05.5145.ER	46
05.5145.ER	162
05.5145.ER.1V	163
05.5145.ER.CB	46
05.5145.ER.CB	162
05.5145.ER.DA	47
05.5145.ER.DA	163
05.5145.ES	46
05.5145.ES	162
05.5145.ES.1V	163
05.5145.ES.CB	46
05.5145.ES.CB	162
05.5145.ES.DA	47
05.5145.ES.DA	163
05.5146.14	46
05.5146.14	162
05.5146.14.1V	163
05.5146.14.CB	46
05.5146.14.CB	162
05.5146.14.DA	47
05.5146.14.DA	163
05.5146.40	46
05.5146.40	162
05.5146.40.1V	163
05.5146.40.CB	46
05.5146.40.CB	162
05.5146.40.DA	47
05.5146.40.DA	163
05.5146.ER	46
05.5146.ER	162
05.5146.ER.1V	163
05.5146.ER.CB	46
05.5146.ER.CB	162
05.5146.ER.DA	47
05.5146.ER.DA	163
05.5146.ES	46
05.5146.ES	162
05.5146.ES.1V	163
05.5146.ES.CB	46
05.5146.ES.CB	162
05.5146.ES.DA	47
05.5146.ES.DA	163
05.5150.14	48
05.5150.14	164
05.5150.14.1V	165
05.5150.14.CB	48
05.5150.14.CB	164
05.5150.14.DA	49
05.5150.14.DA	165
05.5150.40	48
05.5150.40	164
05.5150.40.1V	165
05.5150.40.CB	48
05.5150.40.CB	164
05.5150.40.DA	49
05.5150.40.DA	165
05.5150.ER	48
05.5150.ER	164
05.5150.ER.1V	165
05.5150.ER.CB	48
05.5150.ER.CB	164
05.5150.ER.DA	49
05.5150.ER.DA	165
05.5150.ES	48
05.5150.ES	164
05.5150.ES.1V	165
05.5150.ES.CB	48
05.5150.ES.CB	164
05.5150.ES.DA	49
05.5150.ES.DA	165
05.5151.14	48
05.5151.14	164
05.5151.14.1V	165
05.5151.14.CB	48
05.5151.14.CB	164
05.5151.14.DA	49
05.5151.14.DA	165
05.5151.40	48
05.5151.40	164
05.5151.40.1V	165
05.5151.40.CB	48
05.5151.40.CB	164
05.5151.40.DA	49
05.5151.40.DA	165
05.5151.ER	48
05.5151.ER	164
05.5151.ER.1V	165
05.5151.ER.CB	48
05.5151.ER.CB	164
05.5151.ER.DA	49
05.5151.ER.DA	165
05.5151.ES	48
05.5151.ES	164
05.5151.ES.1V	165
05.5151.ES.CB	48
05.5151.ES.CB	164
05.5151.ES.DA	49
05.5151.ES.DA	165
05.5155.14	48
05.5155.14	164
05.5155.14.1V	165
05.5155.14.CB	48
05.5155.14.CB	164
05.5155.14.DA	49
05.5155.14.DA	165
05.5155.40	48
05.5155.40	164
05.5155.40.1V	165
05.5155.40.CB	48
05.5155.40.CB	164
05.5155.40.DA	49
05.5155.40.DA	165
05.5155.ER	48
05.5155.ER	164
05.5155.ER.1V	165
05.5155.ER.CB	48
05.5155.ER.CB	164
05.5155.ER.DA	49
05.5155.ER.DA	165
05.5155.ES	48
05.5155.ES	164
05.5155.ES.1V	165
05.5155.ES.CB	48
05.5155.ES.CB	164
05.5155.ES.DA	49
05.5155.ES.DA	165
05.5156.14	48
05.5156.14	164
05.5156.14.1V	165
05.5156.14.CB	48
05.5156.14.CB	164
05.5156.14.DA	49
05.5156.14.DA	165
05.5156.40	48
05.5156.40	164
05.5156.40.1V	165
05.5156.40.CB	48
05.5156.40.CB	164
05.5156.40.DA	49
05.5156.40.DA	165
05.5156.ER	48
05.5156.ER	164
05.5156.ER.1V	165
05.5156.ER.CB	48
05.5156.ER.CB	164
05.5156.ER.DA	49
05.5156.ER.DA	165
05.5156.ES	48
05.5156.ES	164
05.5156.ES.1V	165
05.5156.ES.CB	48
05.5156.ES.CB	164
05.5156.ES.DA	49
05.5156.ES.DA	165
05.5160.14	166
05.5160.14.1V	167
05.5160.14.CB	166
05.5160.14.DA	167
05.5160.40	166
05.5160.40.1V	167
05.5160.40.CB	166
05.5160.40.DA	167
05.5160.ER	166
05.5160.ER.1V	167
05.5160.ER.CB	166
05.5160.ER.DA	167
05.5160.ES	166
05.5160.ES.1V	167
05.5160.ES.CB	166
05.5160.ES.DA	167
05.5161.14	166
05.5161.14.1V	167
05.5161.14.CB	166
05.5161.14.DA	167
05.5161.40	166
05.5161.40.1V	167
05.5161.40.CB	166
05.5161.40.DA	167
05.5161.ER	166
05.5161.ER.1V	167
05.5161.ER.CB	166
05.5161.ER.DA	167
05.5161.ES	166
05.5161.ES.1V	167
05.5161.ES.CB	166
05.5161.ES.DA	167
05.5170.14	37
05.5170.14A	150
05.5170.14A1V	150
05.5170.14ADA	150
05.5170.14.DA	37
05.5170.40	37
05.5170.40A	150
05.5170.40A1V	150
05.5170.40ADA	150
05.5170.40.DA	37
05.5170.ER	37
05.5170.ERA	150
05.5170.ERA1V	150
05.5170.ERADA	150
05.5170.ER.DA	37
05.5170.ES	37
05.5170.ESA	150
05.5170.ESA1V	150
05.5170.ESADA	150
05.5170.ES.DA	37
05.5171.14	37
05.5171.14A	150
05.5171.14A1V	150
05.5171.14ADA	150
05.5171.14.DA	37
05.5171.40	37
05.5171.40A	150
05.5171.40A1V	150
05.5171.40ADA	150
05.5171.40.DA	37
05.5171.ER	37
05.5171.ERA	150
05.5171.ERA1V	150
05.5171.ERADA	150
05.5171.ER.DA	37
05.5171.ES	37
05.5171.ESA	150
05.5171.ESA1V	150
05.5171.ESADA	150
05.5171.ES.DA	37
05.5172.14	37
05.5172.14A	150
05.5172.14A1V	150
05.5172.14ADA	150
05.5172.14.DA	37
05.5172.40	37
05.5172.40A	150
05.5172.40A1V	150
05.5172.40ADA	150
05.5172.40.DA	37
05.5172.ER	37
05.5172.ERA	150
05.5172.ERA1V	150
05.5172.ERADA	150
05.5172.ER.DA	37
05.5172.ES	37
05.5172.ESA	150
05.5172.ESA1V	150
05.5172.ESADA	150
05.5172.ES.DA	37
05.5173.14	37
05.5173.14A	150
05.5173.14A1V	150
05.5173.14ADA	150
05.5173.14.DA	37
05.5173.40	37
05.5173.40A	150
05.5173.40A1V	150
05.5173.40ADA	150
05.5173.40.DA	37
05.5173.ER	37
05.5173.ERA	150
05.5173.ERA1V	150
05.5173.ERADA	150
05.5173.ER.DA	37
05.5173.ES	37
05.5173.ESA	150
05.5173.ESA1V	150
05.5173.ESADA	150
05.5173.ES.DA	37
05.5175.14	37
05.5175.14A	151
05.5175.14A1V	151
05.5175.14ADA	151
05.5175.14.DA	37
05.5175.40	37
05.5175.40A	151
05.5175.40A1V	151
05.5175.40ADA	151
05.5175.40.DA	37
05.5175.ER	37
05.5175.ERA	151
05.5175.ERA1V	151
05.5175.ERADA	151
05.5175.ER.DA	37
05.5175.ES	37
05.5175.ESA	151
05.5175.ESA1V	151
05.5175.ESADA	151
05.5175.ES.DA	37
05.5176.14	37
05.5176.14A	151
05.5176.14A1V	151
05.5176.14ADA	151
05.5176.14.DA	37
05.5176.40	37
05.5176.40A	151
05.5176.40A1V	151
05.5176.40ADA	151
05.5176.40.DA	37
05.5176.ER	37
05.5176.ERA	151
05.5176.ERA1V	151
05.5176.ERADA	151
05.5176.ER.DA	37
05.5176.ES	37
05.5176.ESA	151
05.5176.ESA1V	151
05.5176.ESADA	151
05.5176.ES.DA	37
05.5177.14	37
05.5177.14A	151
05.5177.14A1V	151
05.5177.14ADA	151
05.5177.14.DA	37
05.5177.40	37
05.5177.40A	151
05.5177.40A1V	151
05.5177.40ADA	151
05.5177.40.DA	37
05.5177.ER	37
05.5177.ERA	151
05.5177.ERA1V	151
05.5177.ERADA	151
05.5177.ER.DA	37
05.5177.ES	37
05.5177.ESA	151
05.5177.ESA1V	151
05.5177.ESADA	151
05.5177.ES.DA	37
05.5178.14	37
05.5178.14A	151
05.5178.14A1V	151
05.5178.14ADA	151
05.5178.14.DA	37
05.5178.40	37
05.5178.40A	151
05.5178.40A1V	151
05.5178.40ADA	151
05.5178.40.DA	37
05.5178.ER	37
05.5178.ERA	151
05.5178.ERA1V	151
05.5178.ERADA	151
05.5178.ER.DA	37
05.5178.ES	37
05.5178.ESA	151
05.5178.ESA1V	151
05.5178.ESADA	151
05.5178.ES.DA	37
05.5180.14	38
05.5180.14	152
05.5180.14.1V	152
05.5180.14.DA	38
05.5180.14.DA	152
05.5180.40	38
05.5180.40	152
05.5180.40.1V	152
05.5180.40.DA	38
05.5180.40.DA	152
05.5180.ER	38
05.5180.ER	152
05.5180.ER.1V	152
05.5180.ER.DA	38
05.5180.ER.DA	152
05.5180.ES	38
05.5180.ES	152
05.5180.ES.1V	152
05.5180.ES.DA	38
05.5180.ES.DA	152
05.5181.14	38
05.5181.14	152
05.5181.14.1V	152
05.5181.14.DA	38
05.5181.14.DA	152
05.5181.40	38
05.5181.40	152
05.5181.40.1V	152
05.5181.40.DA	38
05.5181.40.DA	152
05.5181.ER	38
05.5181.ER	152
05.5181.ER.1V	152
05.5181.ER.DA	38
05.5181.ER.DA	152
05.5181.ES	38
05.5181.ES	152
05.5181.ES.1V	152
05.5181.ES.DA	38
05.5181.ES.DA	152
05.5182.14	38
05.5182.14	152
05.5182.14.1V	152
05.5182.14.DA	38
05.5182.14.DA	152
05.5182.40	38
05.5182.40	152
05.5182.40.1V	152
05.5182.40.DA	38
05.5182.40.DA	152
05.5182.ER	38
05.5182.ER	152
05.5182.ER.1V	152
05.5182.ER.DA	38
05.5182.ER.DA	152
05.5182.ES	38
05.5182.ES	152
05.5182.ES.1V	152
05.5182.ES.DA	38
05.5182.ES.DA	152
05.5185.14	38
05.5185.14	153
05.5185.14.1V	153
05.5185.14.DA	38
05.5185.14.DA	153
05.5185.40	38
05.5185.40	153
05.5185.40.1V	153
05.5185.40.DA	38
05.5185.40.DA	153
05.5185.ER	38
05.5185.ER	153
05.5185.ER.1V	153
05.5185.ER.DA	38
05.5185.ER.DA	153
05.5185.ES	38
05.5185.ES	153
05.5185.ES.1V	153
05.5185.ES.DA	38
05.5185.ES.DA	153
05.5186.14	38
05.5186.14	153
05.5186.14.1V	153
05.5186.14.DA	38
05.5186.14.DA	153
05.5186.40	38
05.5186.40	153
05.5186.40.1V	153
05.5186.40.DA	38
05.5186.40.DA	153
05.5186.ER	38
05.5186.ER	153
05.5186.ER.1V	153
05.5186.ER.DA	38
05.5186.ER.DA	153
05.5186.ES	38
05.5186.ES	153
05.5186.ES.1V	153
05.5186.ES.DA	38
05.5186.ES.DA	153
05.5187.14	38
05.5187.14	153
05.5187.14.1V	153
05.5187.14.DA	38
05.5187.14.DA	153
05.5187.40	38
05.5187.40	153
05.5187.40.1V	153
05.5187.40.DA	38
05.5187.40.DA	153
05.5187.ER	38
05.5187.ER	153
05.5187.ER.1V	153
05.5187.ER.DA	38
05.5187.ER.DA	153
05.5187.ES	38
05.5187.ES	153
05.5187.ES.1V	153
05.5187.ES.DA	38
05.5187.ES.DA	153
05.5190.14	137
05.5190.14.1V	137
05.5190.14.DA	137
05.5191.14	137
05.5191.14.1V	137
05.5191.14.DA	137
05.5192.14	137
05.5192.14.1V	137
05.5192.14.DA	137
05.5193.14	137
05.5193.14.1V	137
05.5193.14.DA	137
05.5194.14	137
05.5194.14.1V	137
05.5194.14.DA	137
05.5195.14	137
05.5195.14.1V	137
05.5195.14.DA	137
05.5290.14	136
05.5290.14.1V	136
05.5290.14.DA	136
05.5291.14	136
05.5291.14.1V	136
05.5291.14.DA	136
05.5292.14	136
05.5292.14.1V	136
05.5292.14.DA	136
05.5293.14	136
05.5293.14.1V	136
05.5293.14.DA	136
05.5294.14	136
05.5294.14.1V	136
05.5294.14.DA	136
05.5295.14	136
05.5295.14.1V	136
05.5295.14.DA	136
05.5300.14A	154
05.5300.14A1V	154
05.5300.14ACB	154
05.5300.14ADA	154
05.5300.40A	154
05.5300.40A1V	154
05.5300.40ACB	154
05.5300.40ADA	154
05.5300.ERA	154
05.5300.ERA1V	154
05.5300.ERACB	154
05.5300.ERADA	154
05.5300.ESA	154
05.5300.ESA1V	154
05.5300.ESACB	154
05.5300.ESADA	154
05.5301.14A	155
05.5301.14A1V	155
05.5301.14ACB	155
05.5301.14ADA	155
05.5301.40A	155
05.5301.40A1V	155
05.5301.40ACB	155
05.5301.40ADA	155
05.5301.ERA	155
05.5301.ERA1V	155
05.5301.ERACB	155
05.5301.ERADA	155
05.5301.ESA	155
05.5301.ESA1V	155
05.5301.ESACB	155
05.5301.ESADA	155
05.5302.14A	155
05.5302.14A1V	155
05.5302.14ACB	155
05.5302.14ADA	155
05.5302.40A	155
05.5302.40A1V	155
05.5302.40ACB	155
05.5302.40ADA	155
05.5302.ERA	155
05.5302.ERA1V	155
05.5302.ERACB	155
05.5302.ERADA	155
05.5302.ESA	155
05.5302.ESA1V	155
05.5302.ESACB	155
05.5302.ESADA	155
05.5305.14A	154
05.5305.14A1V	154
05.5305.14ACB	154
05.5305.14ADA	154
05.5305.40A	154
05.5305.40A1V	154
05.5305.40ACB	154
05.5305.40ADA	154
05.5305.ERA	154
05.5305.ERA1V	154
05.5305.ERACB	154
05.5305.ERADA	154

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.5305.ESA	154	05.5315.ERADA	156	05.5325.ER.CB	158	05.5335.ER.1V	160	05.5417.14A	709	05.5455.ERACB	712
05.5305.ESA1V	154	05.5315.ESA	156	05.5325.ER.DA	158	05.5335.ER.CB	160	05.5417.40A	709	05.5455.ERADA	712
05.5305.ESACB	154	05.5315.ESA1V	156	05.5325.ES	158	05.5335.ER.DA	160	05.5417.ERA	709	05.5455.ESA	712
05.5305.ESADA	154	05.5315.ESACB	156	05.5325.ES.1V	158	05.5335.ES	160	05.5417.ESA	709	05.5455.ESACB	712
05.5306.14A	155	05.5315.ESADA	156	05.5325.ES.CB	158	05.5335.ES.1V	160	05.5420.14	710	05.5455.ESADA	712
05.5306.14A1V	155	05.5316.14A	157	05.5325.ES.DA	158	05.5335.ES.CB	160	05.5420.40	710	05.5456.14A	712
05.5306.14ACB	155	05.5316.14A1V	157	05.5326.14	159	05.5335.ES.DA	160	05.5420.ER	710	05.5456.14ACB	712
05.5306.14ADA	155	05.5316.14ACB	157	05.5326.14.1V	159	05.5336.14	161	05.5420.ES	710	05.5456.14ADA	712
05.5306.40A	155	05.5316.14ADA	157	05.5326.14.CB	159	05.5336.14.1V	161	05.5421.14	710	05.5456.40A	712
05.5306.40A1V	155	05.5316.40A	157	05.5326.14.DA	159	05.5336.14.CB	161	05.5421.40	710	05.5456.40ACB	712
05.5306.40ACB	155	05.5316.40A1V	157	05.5326.40	159	05.5336.14.DA	161	05.5421.ER	710	05.5456.40ADA	712
05.5306.40ADA	155	05.5316.40ACB	157	05.5326.40.1V	159	05.5336.40	161	05.5421.ES	710	05.5456.ERA	712
05.5306.ERA	155	05.5316.40ADA	157	05.5326.40.CB	159	05.5336.40.1V	161	05.5422.14	710	05.5456.ERACB	712
05.5306.ERA1V	155	05.5316.ERA	157	05.5326.40.DA	159	05.5336.40.CB	161	05.5422.40	710	05.5456.ERADA	712
05.5306.ERACB	155	05.5316.ERA1V	157	05.5326.ER	159	05.5336.40.DA	161	05.5422.ER	710	05.5456.ESA	712
05.5306.ERADA	155	05.5316.ERACB	157	05.5326.ER.1V	159	05.5336.ER	161	05.5422.ES	710	05.5456.ESACB	712
05.5306.ESA	155	05.5316.ERADA	157	05.5326.ER.CB	159	05.5336.ER.1V	161	05.5425.14	710	05.5456.ESADA	712
05.5306.ESA1V	155	05.5316.ESA	157	05.5326.ER.DA	159	05.5336.ER.CB	161	05.5425.40	710	05.5457.14A	713
05.5306.ESACB	155	05.5316.ESA1V	157	05.5326.ES	159	05.5336.ER.DA	161	05.5425.ER	710	05.5457.14ACB	713
05.5306.ESADA	155	05.5316.ESACB	157	05.5326.ES.1V	159	05.5336.ES	161	05.5425.ES	710	05.5457.14ADA	713
05.5307.14A	155	05.5316.ESADA	157	05.5326.ES.CB	159	05.5336.ES.1V	161	05.5426.14	710	05.5457.40A	713
05.5307.14A1V	155	05.5317.14A	157	05.5326.ES.DA	159	05.5336.ES.CB	161	05.5426.40	710	05.5457.40ACB	713
05.5307.14ACB	155	05.5317.14A1V	157	05.5327.14	159	05.5336.ES.DA	161	05.5426.ER	710	05.5457.40ADA	713
05.5307.14ADA	155	05.5317.14ACB	157	05.5327.14.1V	159	05.5337.14	161	05.5426.ES	710	05.5457.ERA	713
05.5307.40A	155	05.5317.14ADA	157	05.5327.14.CB	159	05.5337.14.1V	161	05.5427.14	710	05.5457.ERACB	713
05.5307.40A1V	155	05.5317.40A	157	05.5327.14.DA	159	05.5337.14.CB	161	05.5427.40	710	05.5457.ERADA	713
05.5307.40ACB	155	05.5317.40A1V	157	05.5327.40	159	05.5337.14.DA	161	05.5427.ER	710	05.5457.ESA	713
05.5307.40ADA	155	05.5317.40ACB	157	05.5327.40.1V	159	05.5337.40	161	05.5427.ES	710	05.5457.ESACB	713
05.5307.ERA	155	05.5317.40ADA	157	05.5327.40.CB	159	05.5337.40.1V	161	05.5430.14	711	05.5457.ESADA	713
05.5307.ERA1V	155	05.5317.ERA	157	05.5327.40.DA	159	05.5337.40.CB	161	05.5430.40	711	05.5460.14A	714
05.5307.ERACB	155	05.5317.ERA1V	157	05.5327.ER	159	05.5337.40.DA	161	05.5430.ER	711	05.5460.14ACB	714
05.5307.ERADA	155	05.5317.ERACB	157	05.5327.ER.1V	159	05.5337.ER	161	05.5430.ES	711	05.5460.14ADA	714
05.5307.ESA	155	05.5317.ERADA	157	05.5327.ER.CB	159	05.5337.ER.1V	161	05.5431.14	711	05.5460.40A	714
05.5307.ESA1V	155	05.5317.ESA	157	05.5327.ER.DA	159	05.5337.ER.CB	161	05.5431.40	711	05.5460.40ACB	714
05.5307.ESACB	155	05.5317.ESA1V	157	05.5327.ES	159	05.5337.ER.DA	161	05.5431.ER	711	05.5460.40ADA	714
05.5307.ESADA	155	05.5317.ESACB	157	05.5327.ES.1V	159	05.5337.ES	161	05.5431.ES	711	05.5460.ERA	714
05.5310.14A	156	05.5317.ESADA	157	05.5327.ES.CB	159	05.5337.ES.1V	161	05.5432.14	711	05.5460.ERACB	714
05.5310.14A1V	156	05.5320.14	158	05.5327.ES.DA	159	05.5337.ES.CB	161	05.5432.40	711	05.5460.ERADA	714
05.5310.14ACB	156	05.5320.14.1V	158	05.5330.14	160	05.5337.ES.DA	161	05.5432.ER	711	05.5460.ESA	714
05.5310.14ADA	156	05.5320.14.CB	158	05.5330.14.1V	160	05.5390.14	138	05.5432.ES	711	05.5460.ESACB	714
05.5310.40A	156	05.5320.14.DA	158	05.5330.14.CB	160	05.5390.14.DA	138	05.5435.14	711	05.5460.ESADA	714
05.5310.40A1V	156	05.5320.40	158	05.5330.14.DA	160	05.5391.14	138	05.5435.40	711	05.5461.14A	714
05.5310.40ACB	156	05.5320.40.1V	158	05.5330.40	160	05.5391.14.DA	138	05.5435.ER	711	05.5461.14ACB	714
05.5310.40ADA	156	05.5320.40.CB	158	05.5330.40.1V	160	05.5392.14	138	05.5435.ES	711	05.5461.14ADA	714
05.5310.ERA	156	05.5320.40.DA	158	05.5330.40.CB	160	05.5392.14.DA	138	05.5436.14	711	05.5461.40A	714
05.5310.ERA1V	156	05.5320.ER	158	05.5330.40.DA	160	05.5393.14	138	05.5436.40	711	05.5461.40ACB	714
05.5310.ERACB	156	05.5320.ER.1V	158	05.5330.ER	160	05.5393.14.DA	138	05.5436.ER	711	05.5461.40ADA	714
05.5310.ERADA	156	05.5320.ER.CB	158	05.5330.ER.1V	160	05.5394.14	138	05.5436.ES	711	05.5461.ERA	714
05.5310.ESA	156	05.5320.ER.DA	158	05.5330.ER.CB	160	05.5394.14.DA	138	05.5437.14	711	05.5461.ERACB	714
05.5310.ESA1V	156	05.5320.ES	158	05.5330.ER.DA	160	05.5395.14	138	05.5437.40	711	05.5461.ERADA	714
05.5310.ESACB	156	05.5320.ES.1V	158	05.5330.ES	160	05.5395.14.DA	138	05.5437.ER	711	05.5461.ESA	714
05.5310.ESADA	156	05.5320.ES.CB	158	05.5330.ES.1V	160	05.5400.14A	708	05.5437.ES	711	05.5461.ESACB	714
05.5311.14A	157	05.5320.ES.DA	158	05.5330.ES.CB	160	05.5400.40A	708	05.5450.14A	712	05.5461.ESADA	714
05.5311.14A1V	157	05.5321.14	159	05.5330.ES.DA	160	05.5400.ERA	708	05.5450.14ACB	712	05.5462.14A	715
05.5311.14ACB	157	05.5321.14.1V	159	05.5331.14	161	05.5400.ESA	708	05.5450.14ADA	712	05.5462.14ACB	715
05.5311.14ADA	157	05.5321.14.CB	159	05.5331.14.1V	161	05.5401.14A	708	05.5450.40A	712	05.5462.14ADA	715
05.5311.40A	157	05.5321.14.DA	159	05.5331.14.CB	161	05.5401.40A	708	05.5450.40ACB	712	05.5462.40A	715
05.5311.40A1V	157	05.5321.40	159	05.5331.14.DA	161	05.5401.ERA	708	05.5450.40ADA	712	05.5462.40ACB	715
05.5311.40ACB	157	05.5321.40.1V	159	05.5331.40	161	05.5401.ESA	708	05.5450.ERA	712	05.5462.40ADA	715
05.5311.40ADA	157	05.5321.40.CB	159	05.5331.40.1V	161	05.5402.14A	708	05.5450.ERACB	712	05.5462.ERA	715
05.5311.ERA	157	05.5321.40.DA	159	05.5331.40.CB	161	05.5402.40A	708	05.5450.ERADA	712	05.5462.ERACB	715
05.5311.ERA1V	157	05.5321.ER	159	05.5331.40.DA	161	05.5402.ERA	708	05.5450.ESA	712	05.5462.ERADA	715
05.5311.ERACB	157	05.5321.ER.1V	159	05.5331.ER	161	05.5402.ESA	708	05.5450.ESACB	712	05.5462.ESA	715
05.5311.ERADA	157	05.5321.ER.CB	159	05.5331.ER.1V	161	05.5405.14A	708	05.5450.ESADA	712	05.5462.ESACB	715
05.5311.ESA	157	05.5321.ER.DA	159	05.5331.ER.CB	161	05.5405.40A	708	05.5451.14A	712	05.5462.ESADA	715
05.5311.ESA1V	157	05.5321.ES	159	05.5331.ER.DA	161	05.5405.ERA	708	05.5451.14ACB	712	05.5465.14A	714
05.5311.ESACB	157	05.5321.ES.1V	159	05.5331.ES	161	05.5405.ESA	708	05.5451.14ADA	712	05.5465.14ACB	714
05.5311.ESADA	157	05.5321.ES.CB	159	05.5331.ES.1V	161	05.5406.14A	708	05.5451.40A	712	05.5465.14ADA	714
05.5312.14A	157	05.5321.ES.DA	159	05.5331.ES.CB	161	05.5406.40A	708	05.5451.40ACB	712	05.5465.40A	714
05.5312.14A1V	157	05.5322.14	159	05.5331.ES.DA	161	05.5406.ERA	708	05.5451.40ADA	712	05.5465.40ACB	714
05.5312.14ACB	157	05.5322.14.1V	159	05.5332.14	161	05.5406.ESA	708	05.5451.ERA	712	05.5465.40ADA	714
05.5312.14ADA	157	05.5322.14.CB	159	05.5332.14.1V	161	05.5407.14A	708	05.5451.ERACB	712	05.5465.ERA	714
05.5312.40A	157	05.5322.14.DA	159	05.5332.14.CB	161	05.5407.40A	708	05.5451.ERADA	712	05.5465.ERACB	714
05.5312.40A1V	157	05.5322.40	159	05.5332.14.DA	161	05.5407.ERA	708	05.5451.ESA	712	05.5465.ERADA	714
05.5312.40ACB	157	05.5322.40.1V	159	05.5332.40	161	05.5407.ESA	708	05.5451.ESACB	712	05.5465.ESA	714
05.5312.40ADA	157	05.5322.40.CB	159	05.5332.40.1V	161	05.5410.14A	709	05.5451.ESADA	712	05.5465.ESACB	714
05.5312.ERA	157	05.5322.40.DA	159	05.5332.40.CB	161	05.5410.40A	709	05.5452.14A	713	05.5465.ESADA	714
05.5312.ERA1V	157	05.5322.ER	159	05.5332.40.DA	161	05.5410.ERA	709	05.5452.14ACB	713	05.5466.14A	714
05.5312.ERACB	157	05.5322.ER.1V	159	05.5332.ER	161	05.5410.ESA	709	05.5452.14ADA	713	05.5466.14ACB	714
05.5312.ERADA	157	05.5322.ER.CB	159	05.5332.ER.1V	161	05.5411.14A	709	05.5452.40A	713	05.5466.14ADA	714
05.5312.ESA	157	05.5322.ER.DA	159	05.5332.ER.CB	161	05.5411.40A	709	05.5452.40ACB	713	05.5466.40A	714
05.5312.ESA1V	157	05.5322.ES	159	05.5332.ER.DA	161	05.5411.ERA	709	05.5452.40ADA	713	05.5466.40ACB	714
05.5312.ESACB	157	05.5322.ES.1V	159	05.5332.ES	161	05.5411.ESA	709	05.5452.ERA	713	05.5466.40ADA	714
05.5312.ESADA	157	05.5322.ES.CB	159	05.5332.ES.1V	161	05.5412.14A	709	05.5452.ERACB	713	05.5466.ERA	714
05.5315.14A	156	05.5322.ES.DA	159	05.5332.ES.CB	161	05.5412.40A	709	05.5452.ERADA	713	05.5466.ERACB	714
05.5315.14A1V	156	05.5325.14	158	05.5332.ES.DA	161	05.5412.ERA	709	05.5452.ESA	713	05.5466.ERADA	714
05.5315.14ACB	156	05.5325.14.1V	158	05.5335.14	160	05.5412.ESA	709	05.5452.ESACB	713	05.5466.ESA	714
05.5315.14ADA	156	05.5325.14.CB	158	05.5335.14.1V	160	05.5415.14A	709	05.5452.ESADA	713	05.5466.ESACB	714
05.5315.40A	156	05.5325.14.DA	158	05.5335.14.CB	160	05.5415.40A	709	05.5455.14A	712	05.5466.ESADA	714
05.5315.40A1V	156	05.5325.40	158	05.5335.14.DA	160	05.5415.ERA	709	05.5455.14ACB	712	05.5467.14A	715
05.5315.40ACB	156	05.5325.40.1V	158	05.5335.40	160	05.5415.ESA	709	05.5455.14ADA	712	05.5467.14ACB	715
05.5315.40ADA	156	05.5325.40.CB	158	05.5335.40.1V	160	05.5416.14A	709	05.5455.40A	712	05.5467.14ADA	715
05.5315.ERA	156	05.5325.40.DA	158	05.5335.40.CB	160	05.5416.40A	709	05.5455.40ACB	712	05.5467.40A	715
05.5315.ERA1V	156	05.5325.ER	158	05.5335.40.DA	160	05.5416.ERA	709	05.5455.40ADA	712	05.5467.40ACB	715
05.5315.ERACB	156	05.5325.ER.1V	158	05.5335.ER	160	05.5416.ESA	709	05.5455.ERA	712	05.5467.40ADA	715

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.5467.ERA	715	05.5481.40.DA	718	05.5750.40.78	369	05.5772.40	373	05.5792.40.78	299	05.5812.40	381
05.5467.ERACB	715	05.5481.ER	718	05.5750.40.C6	369	05.5772.40.78	373	05.5792.40.78	377	05.5812.40.78	303
05.5467.ERADA	715	05.5481.ER.CB	718	05.5750.40.CB	369	05.5772.40.C6	373	05.5792.40.DA	299	05.5812.40.78	381
05.5467.ESA	715	05.5481.ER.DA	718	05.5750.40.DA	369	05.5772.40.CB	373	05.5792.40.DA	377	05.5812.40.DA	303
05.5467.ESACB	715	05.5481.ES	718	05.5750.40.YU	369	05.5772.40.DA	373	05.5792.40.YU	299	05.5812.40.DA	381
05.5467.ESADA	715	05.5481.ES.CB	718	05.5750.AP	369	05.5772.40.YU	373	05.5792.40.YU	377	05.5812.40.YU	303
05.5470.14	716	05.5481.ES.DA	718	05.5750.AP.CB	369	05.5772.AP	373	05.5792.AP	299	05.5812.40.YU	381
05.5470.14.CB	716	05.5482.14	719	05.5750.AP.DA	369	05.5772.AP.CB	373	05.5792.AP	377	05.5812.AP	303
05.5470.14.DA	716	05.5482.14.CB	719	05.5751.14	369	05.5772.AP.DA	373	05.5792.AP.DA	299	05.5812.AP	381
05.5470.40	716	05.5482.14.DA	719	05.5751.14.CB	369	05.5780.14	297	05.5792.AP.DA	377	05.5812.AP.DA	303
05.5470.40.CB	716	05.5482.40	719	05.5751.14.DA	369	05.5780.14	375	05.5800.14	301	05.5812.AP.DA	381
05.5470.40.DA	716	05.5482.40.CB	719	05.5751.40	369	05.5780.14.DA	297	05.5800.14	379	05.5820.14	383
05.5470.ER	716	05.5482.40.DA	719	05.5751.40.78	369	05.5780.14.DA	375	05.5800.14.DA	301	05.5820.14.CB	383
05.5470.ER.CB	716	05.5482.ER	719	05.5751.40.C6	369	05.5780.40	297	05.5800.14.DA	379	05.5820.40	383
05.5470.ER.DA	716	05.5482.ER.CB	719	05.5751.40.CB	369	05.5780.40	375	05.5800.40	301	05.5820.40.78	383
05.5470.ES	716	05.5482.ER.DA	719	05.5751.40.DA	369	05.5780.40.78	297	05.5800.40	379	05.5820.40.C6	383
05.5470.ES.CB	716	05.5482.ES	719	05.5751.40.YU	369	05.5780.40.78	375	05.5800.40.78	301	05.5820.40.CB	383
05.5470.ES.DA	716	05.5482.ES.CB	719	05.5751.AP	369	05.5780.40.DA	297	05.5800.40.78	379	05.5820.AP	383
05.5471.14	716	05.5482.ES.DA	719	05.5751.AP.CB	369	05.5780.40.DA	375	05.5800.40.DA	301	05.5820.AP.CB	383
05.5471.14.CB	716	05.5485.14	718	05.5751.AP.DA	369	05.5780.40.YU	297	05.5800.40.DA	379	05.5821.14	383
05.5471.14.DA	716	05.5485.14.CB	718	05.5752.14	369	05.5780.40.YU	375	05.5800.40.YU	301	05.5821.14.CB	383
05.5471.40	716	05.5485.14.DA	718	05.5752.14.CB	369	05.5780.AP	297	05.5800.40.YU	379	05.5821.40	383
05.5471.40.CB	716	05.5485.40	718	05.5752.14.DA	369	05.5780.AP	375	05.5800.AP	301	05.5821.40.78	383
05.5471.40.DA	716	05.5485.40.CB	718	05.5752.40	369	05.5780.AP.DA	297	05.5800.AP	379	05.5821.40.C6	383
05.5471.ER	716	05.5485.40.DA	718	05.5752.40.78	369	05.5780.AP.DA	375	05.5800.AP.DA	301	05.5821.40.CB	383
05.5471.ER.CB	716	05.5485.ER	718	05.5752.40.C6	369	05.5781.14	297	05.5800.AP.DA	379	05.5821.AP	383
05.5471.ER.DA	716	05.5485.ER.CB	718	05.5752.40.CB	369	05.5781.14	375	05.5801.14	301	05.5821.AP.CB	383
05.5471.ES	716	05.5485.ER.DA	718	05.5752.40.DA	369	05.5781.14.DA	297	05.5801.14	379	05.5822.14	383
05.5471.ES.CB	716	05.5485.ES	718	05.5752.40.YU	369	05.5781.14.DA	375	05.5801.14.DA	301	05.5822.14.CB	383
05.5471.ES.DA	716	05.5485.ES.CB	718	05.5752.AP	369	05.5781.40	297	05.5801.14.DA	379	05.5822.40	383
05.5472.14	717	05.5485.ES.DA	718	05.5752.AP.CB	369	05.5781.40	375	05.5801.40	301	05.5822.40.78	383
05.5472.14.CB	717	05.5486.14	718	05.5752.AP.DA	369	05.5781.40.78	297	05.5801.40	379	05.5822.40.C6	383
05.5472.14.DA	717	05.5486.14.CB	718	05.5760.14	371	05.5781.40.78	375	05.5801.40.78	301	05.5822.40.CB	383
05.5472.40	717	05.5486.14.DA	718	05.5760.14.CB	371	05.5781.40.DA	297	05.5801.40.78	379	05.5822.AP	383
05.5472.40.CB	717	05.5486.40	718	05.5760.14.DA	371	05.5781.40.DA	375	05.5801.40.DA	301	05.5822.AP.CB	383
05.5472.40.DA	717	05.5486.40.CB	718	05.5760.40	371	05.5781.40.YU	297	05.5801.40.DA	379	05.5830.14	385
05.5472.ER	717	05.5486.40.DA	718	05.5760.40.78	371	05.5781.40.YU	375	05.5801.40.YU	301	05.5830.14.CB	385
05.5472.ER.CB	717	05.5486.ER	718	05.5760.40.C6	371	05.5781.AP	297	05.5801.40.YU	379	05.5830.40	385
05.5472.ER.DA	717	05.5486.ER.CB	718	05.5760.40.CB	371	05.5781.AP	375	05.5801.AP	301	05.5830.40.78	385
05.5472.ES	717	05.5486.ER.DA	718	05.5760.40.DA	371	05.5781.AP.DA	297	05.5801.AP	379	05.5830.40.C6	385
05.5472.ES.CB	717	05.5486.ES	718	05.5760.40.YU	371	05.5781.AP.DA	375	05.5801.AP.DA	301	05.5830.40.CB	385
05.5472.ES.DA	717	05.5486.ES.CB	718	05.5760.AP	371	05.5782.14	297	05.5801.AP.DA	379	05.5830.AP	385
05.5475.14	716	05.5486.ES.DA	718	05.5760.AP.CB	371	05.5782.14	375	05.5802.14	301	05.5830.AP.CB	385
05.5475.14.CB	716	05.5487.14	719	05.5760.AP.DA	371	05.5782.14.DA	297	05.5802.14	379	05.5831.14	385
05.5475.14.DA	716	05.5487.14.CB	719	05.5761.14	371	05.5782.14.DA	375	05.5802.14.DA	301	05.5831.14.CB	385
05.5475.40	716	05.5487.14.DA	719	05.5761.14.CB	371	05.5782.40	297	05.5802.14.DA	379	05.5831.40	385
05.5475.40.CB	716	05.5487.40	719	05.5761.14.DA	371	05.5782.40	375	05.5802.40	301	05.5831.40.78	385
05.5475.40.DA	716	05.5487.40.CB	719	05.5761.40	371	05.5782.40.78	297	05.5802.40	379	05.5831.40.C6	385
05.5475.ER	716	05.5487.40.DA	719	05.5761.40.78	371	05.5782.40.78	375	05.5802.40.78	301	05.5831.40.CB	385
05.5475.ER.CB	716	05.5487.ER	719	05.5761.40.C6	371	05.5782.40.DA	297	05.5802.40.78	379	05.5831.AP	385
05.5475.ER.DA	716	05.5487.ER.CB	719	05.5761.40.CB	371	05.5782.40.DA	375	05.5802.40.DA	301	05.5831.AP.CB	385
05.5475.ES	716	05.5487.ER.DA	719	05.5761.40.DA	371	05.5782.40.YU	297	05.5802.40.DA	379	05.5832.14	385
05.5475.ES.CB	716	05.5487.ES	719	05.5761.40.YU	371	05.5782.40.YU	375	05.5802.40.YU	301	05.5832.14.CB	385
05.5475.ES.DA	716	05.5487.ES.CB	719	05.5761.AP	371	05.5782.AP	297	05.5802.40.YU	379	05.5832.40	385
05.5476.14	716	05.5487.ES.DA	719	05.5761.AP.CB	371	05.5782.AP	375	05.5802.AP	301	05.5832.40.78	385
05.5476.14.CB	716	05.5740.14	367	05.5761.AP.DA	371	05.5782.AP.DA	297	05.5802.AP	379	05.5832.40.C6	385
05.5476.14.DA	716	05.5740.14.CB	367	05.5762.14	371	05.5782.AP.DA	375	05.5802.AP.DA	301	05.5832.40.CB	385
05.5476.40	716	05.5740.14.DA	367	05.5762.14.CB	371	05.5790.14	299	05.5802.AP.DA	379	05.5832.AP	385
05.5476.40.CB	716	05.5740.40	367	05.5762.14.DA	371	05.5790.14	377	05.5810.14	303	05.5832.AP.CB	385
05.5476.40.DA	716	05.5740.40.78	367	05.5762.40	371	05.5790.14.DA	299	05.5810.14	381	05.5840.14	387
05.5476.ER	716	05.5740.40.C6	367	05.5762.40.78	371	05.5790.14.DA	377	05.5810.14.DA	303	05.5840.14.CB	387
05.5476.ER.CB	716	05.5740.40.CB	367	05.5762.40.C6	371	05.5790.40	299	05.5810.14.DA	381	05.5840.40	387
05.5476.ER.DA	716	05.5740.40.DA	367	05.5762.40.CB	371	05.5790.40	377	05.5810.40	303	05.5840.40.78	387
05.5476.ES	716	05.5740.40.YU	367	05.5762.40.DA	371	05.5790.40.78	299	05.5810.40	381	05.5840.40.C6	387
05.5476.ES.CB	716	05.5740.AP	367	05.5762.40.YU	371	05.5790.40.78	377	05.5810.40.78	303	05.5840.40.CB	387
05.5476.ES.DA	716	05.5740.AP.CB	367	05.5762.AP	371	05.5790.40.DA	299	05.5810.40.78	381	05.5840.AP	387
05.5477.14	717	05.5740.AP.DA	367	05.5762.AP.CB	371	05.5790.40.DA	377	05.5810.40.DA	303	05.5840.AP.CB	387
05.5477.14.CB	717	05.5741.14	367	05.5762.AP.DA	371	05.5790.40.YU	299	05.5810.40.DA	381	05.5841.14	387
05.5477.14.DA	717	05.5741.14.CB	367	05.5770.14	373	05.5790.40.YU	377	05.5810.40.YU	303	05.5841.14.CB	387
05.5477.40	717	05.5741.14.DA	367	05.5770.14.CB	373	05.5790.AP	299	05.5810.40.YU	381	05.5841.40	387
05.5477.40.CB	717	05.5741.40	367	05.5770.14.DA	373	05.5790.AP	377	05.5810.AP	303	05.5841.40.78	387
05.5477.40.DA	717	05.5741.40.78	367	05.5770.40	373	05.5790.AP.DA	299	05.5810.AP	381	05.5841.40.C6	387
05.5477.ER	717	05.5741.40.C6	367	05.5770.40.78	373	05.5790.AP.DA	377	05.5810.AP.DA	303	05.5841.40.CB	387
05.5477.ER.CB	717	05.5741.40.CB	367	05.5770.40.C6	373	05.5791.14	299	05.5810.AP.DA	381	05.5841.AP	387
05.5477.ER.DA	717	05.5741.40.DA	367	05.5770.40.CB	373	05.5791.14	377	05.5811.14	303	05.5841.AP.CB	387
05.5477.ES	717	05.5741.40.YU	367	05.5770.40.DA	373	05.5791.14.DA	299	05.5811.14	381	05.5842.14	387
05.5477.ES.CB	717	05.5741.AP	367	05.5770.40.YU	373	05.5791.14.DA	377	05.5811.14.DA	303	05.5842.14.CB	387
05.5477.ES.DA	717	05.5741.AP.CB	367	05.5770.AP	373	05.5791.40	299	05.5811.14.DA	381	05.5842.40	387
05.5480.14	718	05.5741.AP.DA	367	05.5770.AP.CB	373	05.5791.40	377	05.5811.40	303	05.5842.40.78	387
05.5480.14.CB	718	05.5742.14	367	05.5770.AP.DA	373	05.5791.40.78	299	05.5811.40	381	05.5842.40.C6	387
05.5480.14.DA	718	05.5742.14.CB	367	05.5771.14	373	05.5791.40.78	377	05.5811.40.78	303	05.5842.40.CB	387
05.5480.40	718	05.5742.14.DA	367	05.5771.14.CB	373	05.5791.40.DA	299	05.5811.40.78	381	05.5842.AP	387
05.5480.40.CB	718	05.5742.40	367	05.5771.14.DA	373	05.5791.40.DA	377	05.5811.40.DA	303	05.5842.AP.CB	387
05.5480.40.DA	718	05.5742.40.78	367	05.5771.40	373	05.5791.40.YU	299	05.5811.40.DA	381	05.5850.14	389
05.5480.ER	718	05.5742.40.C6	367	05.5771.40.78	373	05.5791.40.YU	377	05.5811.40.YU	303	05.5850.14.CB	389
05.5480.ER.CB	718	05.5742.40.CB	367	05.5771.40.C6	373	05.5791.AP	299	05.5811.40.YU	381	05.5850.40	389
05.5480.ER.DA	718	05.5742.40.DA	367	05.5771.40.CB	373	05.5791.AP	377	05.5811.AP	303	05.5850.40.78	389
05.5480.ES	718	05.5742.40.YU	367	05.5771.40.DA	373	05.5791.AP.DA	299	05.5811.AP	381	05.5850.40.C6	389
05.5480.ES.CB	718	05.5742.AP	367	05.5771.40.YU	373	05.5791.AP.DA	377	05.5811.AP.DA	303	05.5850.40.CB	389
05.5480.ES.DA	718	05.5742.AP.CB	367	05.5771.AP	373	05.5792.14	299	05.5811.AP.DA	381	05.5850.AP	389
05.5481.14	718	05.5742.AP.DA	367	05.5771.AP.CB	373	05.5792.14	377	05.5812.14	303	05.5850.AP.CB	389
05.5481.14.CB	718	05.5750.14	369	05.5771.AP.DA	373	05.5792.14.DA	299	05.5812.14	381	05.5851.14	389
05.5481.14.DA	718	05.5750.14.CB	369	05.5772.14	373	05.5792.14.DA	377	05.5812.14.DA	303	05.5851.14.CB	389
05.5481.40	718	05.5750.14.DA	369	05.5772.14.CB	373	05.5792.40	299	05.5812.14.DA	381	05.5851.40	389
05.5481.40.CB	718	05.5750.40	369	05.5772.14.DA	373	05.5792.40	377	05.5812.40	303	05.5851.40.78	389

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.5851.40.C6	389	05.5902.AP.CB	396	05.5932.14.CB	235	05.5952.14.1V	239	05.6210.40.YU	363	05.6222.40.DA	364
05.5851.40.CB	389	05.5910.14.CB	397	05.5932.14.DA	235	05.5952.14.CB	239	05.6210.AP	363	05.6222.40.YU	364
05.5851.AP	389	05.5910.40.C6	397	05.5932.40	235	05.5952.14.DA	239	05.6210.AP.CB	363	05.6222.AP	364
05.5851.AP.CB	389	05.5910.40.CB	397	05.5932.40.1V	235	05.5952.40	239	05.6210.AP.DA	363	05.6222.AP.CB	364
05.5852.14	389	05.5910.AP.CB	397	05.5932.40.78	235	05.5952.40.1V	239	05.6211.14	363	05.6222.AP.DA	364
05.5852.14.CB	389	05.5911.14.CB	397	05.5932.40.C6	235	05.5952.40.78	239	05.6211.14.CB	363	05.6225.14	364
05.5852.40	389	05.5911.40.C6	397	05.5932.40.CB	235	05.5952.40.C6	239	05.6211.14.DA	363	05.6225.14.CB	364
05.5852.40.78	389	05.5911.40.CB	397	05.5932.40.DA	235	05.5952.40.CB	239	05.6211.40	363	05.6225.14.DA	364
05.5852.40.C6	389	05.5911.AP.CB	397	05.5932.40.RX	235	05.5952.40.DA	239	05.6211.40.78	363	05.6225.40	364
05.5852.40.CB	389	05.5912.14.CB	397	05.5932.40.YU	235	05.5952.40.RX	239	05.6211.40.C6	363	05.6225.40.78	364
05.5852.AP	389	05.5912.40.C6	397	05.5932.AP	235	05.5952.40.YU	239	05.6211.40.CB	363	05.6225.40.C6	364
05.5852.AP.CB	389	05.5912.40.CB	397	05.5932.AP.1V	235	05.5952.AP	239	05.6211.40.DA	363	05.6225.40.CB	364
05.5860.14.CB	390	05.5912.AP.CB	397	05.5932.AP.CB	235	05.5952.AP.1V	239	05.6211.40.YU	363	05.6225.40.DA	364
05.5860.40.C6	390	05.5920.14	233	05.5932.AP.DA	235	05.5952.AP.CB	239	05.6211.AP	363	05.6225.40.YU	364
05.5860.40.CB	390	05.5920.14.1V	233	05.5940.14	237	05.5952.AP.DA	239	05.6211.AP.CB	363	05.6225.AP	364
05.5860.AP.CB	390	05.5920.14.CB	233	05.5940.14.1V	237	05.6200.14	362	05.6211.AP.DA	363	05.6225.AP.CB	364
05.5861.14.CB	390	05.5920.14.DA	233	05.5940.14.CB	237	05.6200.14.CB	362	05.6212.14	363	05.6225.AP.DA	364
05.5861.40.C6	390	05.5920.40	233	05.5940.14.DA	237	05.6200.14.DA	362	05.6212.14.CB	363	05.6226.14	364
05.5861.40.CB	390	05.5920.40.1V	233	05.5940.40	237	05.6200.40	362	05.6212.14.DA	363	05.6226.14.CB	364
05.5861.AP.CB	390	05.5920.40.78	233	05.5940.40.1V	237	05.6200.40.78	362	05.6212.40	363	05.6226.14.DA	364
05.5862.14.CB	390	05.5920.40.C6	233	05.5940.40.78	237	05.6200.40.C6	362	05.6212.40.78	363	05.6226.40	364
05.5862.40.C6	390	05.5920.40.CB	233	05.5940.40.C6	237	05.6200.40.CB	362	05.6212.40.C6	363	05.6226.40.78	364
05.5862.40.CB	390	05.5920.40.DA	233	05.5940.40.CB	237	05.6200.40.DA	362	05.6212.40.CB	363	05.6226.40.C6	364
05.5862.AP.CB	390	05.5920.40.RX	233	05.5940.40.DA	237	05.6200.40.YU	362	05.6212.40.DA	363	05.6226.40.CB	364
05.5870.14.CB	391	05.5920.40.YU	233	05.5940.40.RX	237	05.6200.AP	362	05.6212.40.YU	363	05.6226.40.DA	364
05.5870.40.C6	391	05.5920.AP	233	05.5940.40.YU	237	05.6200.AP.CB	362	05.6212.AP	363	05.6226.40.YU	364
05.5870.40.CB	391	05.5920.AP.1V	233	05.5940.AP	237	05.6200.AP.DA	362	05.6212.AP.CB	363	05.6226.AP	364
05.5870.AP.CB	391	05.5920.AP.CB	233	05.5940.AP.1V	237	05.6201.14	362	05.6212.AP.DA	363	05.6226.AP.CB	364
05.5871.14.CB	391	05.5920.AP.DA	233	05.5940.AP.CB	237	05.6201.14.CB	362	05.6215.14	363	05.6226.AP.DA	364
05.5871.40.C6	391	05.5921.14	233	05.5940.AP.DA	237	05.6201.14.DA	362	05.6215.14.CB	363	05.6227.14	364
05.5871.40.CB	391	05.5921.14.1V	233	05.5941.14	237	05.6201.40	362	05.6215.14.DA	363	05.6227.14.CB	364
05.5871.AP.CB	391	05.5921.14.CB	233	05.5941.14.1V	237	05.6201.40.78	362	05.6215.40	363	05.6227.14.DA	364
05.5872.14.CB	391	05.5921.14.DA	233	05.5941.14.CB	237	05.6201.40.C6	362	05.6215.40.78	363	05.6227.40	364
05.5872.40.C6	391	05.5921.40	233	05.5941.14.DA	237	05.6201.40.CB	362	05.6215.40.C6	363	05.6227.40.78	364
05.5872.40.CB	391	05.5921.40.1V	233	05.5941.40	237	05.6201.40.DA	362	05.6215.40.CB	363	05.6227.40.C6	364
05.5872.AP.CB	391	05.5921.40.78	233	05.5941.40.1V	237	05.6201.40.YU	362	05.6215.40.DA	363	05.6227.40.CB	364
05.5880.14.CB	393	05.5921.40.C6	233	05.5941.40.78	237	05.6201.AP	362	05.6215.40.YU	363	05.6227.40.DA	364
05.5880.14.DA	393	05.5921.40.CB	233	05.5941.40.C6	237	05.6201.AP.CB	362	05.6215.AP	363	05.6227.40.YU	364
05.5880.40.C6	393	05.5921.40.DA	233	05.5941.40.CB	237	05.6201.AP.DA	362	05.6215.AP.CB	363	05.6227.AP	364
05.5880.40.CB	393	05.5921.40.RX	233	05.5941.40.DA	237	05.6202.14	362	05.6215.AP.DA	363	05.6227.AP.CB	364
05.5880.40.DA	393	05.5921.40.YU	233	05.5941.40.RX	237	05.6202.14.CB	362	05.6216.14	363	05.6227.AP.DA	364
05.5880.40.YU	393	05.5921.AP	233	05.5941.40.YU	237	05.6202.14.DA	362	05.6216.14.CB	363	05.6230.14	365
05.5880.AP.CB	393	05.5921.AP.1V	233	05.5941.AP	237	05.6202.40	362	05.6216.14.DA	363	05.6230.14.CB	365
05.5880.AP.DA	393	05.5921.AP.CB	233	05.5941.AP.1V	237	05.6202.40.78	362	05.6216.40	363	05.6230.14.DA	365
05.5881.14.CB	393	05.5921.AP.DA	233	05.5941.AP.CB	237	05.6202.40.C6	362	05.6216.40.78	363	05.6230.40	365
05.5881.14.DA	393	05.5922.14	233	05.5941.AP.DA	237	05.6202.40.CB	362	05.6216.40.C6	363	05.6230.40.78	365
05.5881.40.C6	393	05.5922.14.1V	233	05.5942.14	237	05.6202.40.DA	362	05.6216.40.CB	363	05.6230.40.C6	365
05.5881.40.CB	393	05.5922.14.CB	233	05.5942.14.1V	237	05.6202.40.YU	362	05.6216.40.DA	363	05.6230.40.CB	365
05.5881.40.DA	393	05.5922.14.DA	233	05.5942.14.CB	237	05.6202.AP	362	05.6216.40.YU	363	05.6230.40.DA	365
05.5881.40.YU	393	05.5922.40	233	05.5942.14.DA	237	05.6202.AP.CB	362	05.6216.AP	363	05.6230.40.YU	365
05.5881.AP.CB	393	05.5922.40.1V	233	05.5942.40	237	05.6202.AP.DA	362	05.6216.AP.CB	363	05.6230.AP	365
05.5881.AP.DA	393	05.5922.40.78	233	05.5942.40.1V	237	05.6205.14	362	05.6216.AP.DA	363	05.6230.AP.CB	365
05.5882.14.CB	393	05.5922.40.C6	233	05.5942.40.78	237	05.6205.14.CB	362	05.6217.14	363	05.6230.AP.DA	365
05.5882.14.DA	393	05.5922.40.CB	233	05.5942.40.C6	237	05.6205.14.DA	362	05.6217.14.CB	363	05.6231.14	365
05.5882.40.C6	393	05.5922.40.DA	233	05.5942.40.CB	237	05.6205.40	362	05.6217.14.DA	363	05.6231.14.CB	365
05.5882.40.CB	393	05.5922.40.RX	233	05.5942.40.DA	237	05.6205.40.78	362	05.6217.40	363	05.6231.14.DA	365
05.5882.40.DA	393	05.5922.40.YU	233	05.5942.40.RX	237	05.6205.40.C6	362	05.6217.40.78	363	05.6231.40	365
05.5882.40.YU	393	05.5922.AP	233	05.5942.40.YU	237	05.6205.40.CB	362	05.6217.40.C6	363	05.6231.40.78	365
05.5882.AP.CB	393	05.5922.AP.1V	233	05.5942.AP	237	05.6205.40.DA	362	05.6217.40.CB	363	05.6231.40.C6	365
05.5882.AP.DA	393	05.5922.AP.CB	233	05.5942.AP.1V	237	05.6205.40.YU	362	05.6217.40.DA	363	05.6231.40.CB	365
05.5890.14.CB	395	05.5922.AP.DA	233	05.5942.AP.CB	237	05.6205.AP	362	05.6217.40.YU	363	05.6231.40.DA	365
05.5890.14.DA	395	05.5930.14	235	05.5942.AP.DA	237	05.6205.AP.CB	362	05.6217.AP	363	05.6231.40.YU	365
05.5890.40.C6	395	05.5930.14.1V	235	05.5950.14	239	05.6205.AP.DA	362	05.6217.AP.CB	363	05.6231.AP	365
05.5890.40.CB	395	05.5930.14.CB	235	05.5950.14.1V	239	05.6206.14	362	05.6217.AP.DA	363	05.6231.AP.CB	365
05.5890.40.DA	395	05.5930.14.DA	235	05.5950.14.CB	239	05.6206.14.CB	362	05.6220.14	364	05.6231.AP.DA	365
05.5890.40.YU	395	05.5930.40	235	05.5950.14.DA	239	05.6206.14.DA	362	05.6220.14.CB	364	05.6232.14	365
05.5890.AP.CB	395	05.5930.40.1V	235	05.5950.40	239	05.6206.40	362	05.6220.14.DA	364	05.6232.14.CB	365
05.5890.AP.DA	395	05.5930.40.78	235	05.5950.40.1V	239	05.6206.40.78	362	05.6220.40	364	05.6232.14.DA	365
05.5891.14.CB	395	05.5930.40.C6	235	05.5950.40.78	239	05.6206.40.C6	362	05.6220.40.78	364	05.6232.40	365
05.5891.14.DA	395	05.5930.40.CB	235	05.5950.40.C6	239	05.6206.40.CB	362	05.6220.40.C6	364	05.6232.40.78	365
05.5891.40.C6	395	05.5930.40.DA	235	05.5950.40.CB	239	05.6206.40.DA	362	05.6220.40.CB	364	05.6232.40.C6	365
05.5891.40.CB	395	05.5930.40.RX	235	05.5950.40.DA	239	05.6206.40.YU	362	05.6220.40.DA	364	05.6232.40.CB	365
05.5891.40.DA	395	05.5930.40.YU	235	05.5950.40.RX	239	05.6206.AP	362	05.6220.40.YU	364	05.6232.40.DA	365
05.5891.40.YU	395	05.5930.AP	235	05.5950.40.YU	239	05.6206.AP.CB	362	05.6220.AP	364	05.6232.40.YU	365
05.5891.AP.CB	395	05.5930.AP.1V	235	05.5950.AP	239	05.6206.AP.DA	362	05.6220.AP.CB	364	05.6232.AP	365
05.5891.AP.DA	395	05.5930.AP.CB	235	05.5950.AP.1V	239	05.6207.14	362	05.6220.AP.DA	364	05.6232.AP.CB	365
05.5892.14.CB	395	05.5930.AP.DA	235	05.5950.AP.CB	239	05.6207.14.CB	362	05.6221.14	364	05.6232.AP.DA	365
05.5892.14.DA	395	05.5931.14	235	05.5950.AP.DA	239	05.6207.14.DA	362	05.6221.14.CB	364	05.6235.14	365
05.5892.40.C6	395	05.5931.14.1V	235	05.5951.14	239	05.6207.40	362	05.6221.14.DA	364	05.6235.14.CB	365
05.5892.40.CB	395	05.5931.14.CB	235	05.5951.14.1V	239	05.6207.40.78	362	05.6221.40	364	05.6235.14.DA	365
05.5892.40.DA	395	05.5931.14.DA	235	05.5951.14.CB	239	05.6207.40.C6	362	05.6221.40.78	364	05.6235.40	365
05.5892.40.YU	395	05.5931.40	235	05.5951.14.DA	239	05.6207.40.CB	362	05.6221.40.C6	364	05.6235.40.78	365
05.5892.AP.CB	395	05.5931.40.1V	235	05.5951.40	239	05.6207.40.DA	362	05.6221.40.CB	364	05.6235.40.C6	365
05.5892.AP.DA	395	05.5931.40.78	235	05.5951.40.1V	239	05.6207.40.YU	362	05.6221.40.DA	364	05.6235.40.CB	365
05.5900.14.CB	396	05.5931.40.C6	235	05.5951.40.78	239	05.6207.AP	362	05.6221.40.YU	364	05.6235.40.DA	365
05.5900.40.C6	396	05.5931.40.CB	235	05.5951.40.C6	239	05.6207.AP.CB	362	05.6221.AP	364	05.6235.40.YU	365
05.5900.40.CB	396	05.5931.40.DA	235	05.5951.40.CB	239	05.6207.AP.DA	362	05.6221.AP.CB	364	05.6235.AP	365
05.5900.AP.CB	396	05.5931.40.RX	235	05.5951.40.DA	239	05.6210.14	363	05.6221.AP.DA	364	05.6235.AP.CB	365
05.5901.14.CB	396	05.5931.40.YU	235	05.5951.40.RX	239	05.6210.14.CB	363	05.6222.14	364	05.6235.AP.DA	365
05.5901.40.C6	396	05.5931.AP	235	05.5951.40.YU	239	05.6210.14.DA	363	05.6222.14.CB	364	05.6236.14	365
05.5901.40.CB	396	05.5931.AP.1V	235	05.5951.AP	239	05.6210.40	363	05.6222.14.DA	364	05.6236.14.CB	365
05.5901.AP.CB	396	05.5931.AP.CB	235	05.5951.AP.1V	239	05.6210.40.78	363	05.6222.40	364	05.6236.14.DA	365
05.5902.14.CB	396	05.5931.AP.DA	235	05.5951.AP.CB	239	05.6210.40.C6	363	05.6222.40.78	364	05.6236.40	365
05.5902.40.C6	396	05.5932.14	235	05.5951.AP.DA	239	05.6210.40.CB	363	05.6222.40.C6	364	05.6236.40.78	365
05.5902.40.CB	396	05.5932.14.1V	235	05.5952.14	239	05.6210.40.DA	363	05.6222.40.CB	364	05.6236.40.C6	365

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.6236.40.CB	365	05.6250.40.C6	368	05.6262.40.78	370	05.6276.40	373	05.6286.40.YU	297	05.6296.40.DA	377
05.6236.40.DA	365	05.6250.40.CB	368	05.6262.40.C6	370	05.6276.40.78	373	05.6286.40.YU	375	05.6296.40.YU	299
05.6236.40.YU	365	05.6250.40.DA	368	05.6262.40.CB	370	05.6276.40.C6	373	05.6286.AP	297	05.6296.40.YU	377
05.6236.AP	365	05.6250.40.YU	368	05.6262.40.DA	370	05.6276.40.CB	373	05.6286.AP	375	05.6296.AP	299
05.6236.AP.CB	365	05.6250.AP	368	05.6262.40.YU	370	05.6276.40.DA	373	05.6286.AP.DA	297	05.6296.AP	377
05.6236.AP.DA	365	05.6250.AP.CB	368	05.6262.AP	370	05.6276.40.YU	373	05.6286.AP.DA	375	05.6296.AP.DA	299
05.6237.14	365	05.6250.AP.DA	368	05.6262.AP.CB	370	05.6276.AP	373	05.6287.14	297	05.6296.AP.DA	377
05.6237.14.CB	365	05.6251.14	368	05.6262.AP.DA	370	05.6276.AP.CB	373	05.6287.14	375	05.6297.14	299
05.6237.14.DA	365	05.6251.14.CB	368	05.6265.14	371	05.6276.AP.DA	373	05.6287.14.DA	297	05.6297.14	377
05.6237.40	365	05.6251.14.DA	368	05.6265.14.CB	371	05.6277.14	373	05.6287.14.DA	375	05.6297.14.DA	299
05.6237.40.78	365	05.6251.40	368	05.6265.14.DA	371	05.6277.14.CB	373	05.6287.40	297	05.6297.14.DA	377
05.6237.40.C6	365	05.6251.40.78	368	05.6265.40	371	05.6277.14.DA	373	05.6287.40	375	05.6297.40	299
05.6237.40.CB	365	05.6251.40.C6	368	05.6265.40.78	371	05.6277.40	373	05.6287.40.78	297	05.6297.40	377
05.6237.40.DA	365	05.6251.40.CB	368	05.6265.40.C6	371	05.6277.40.78	373	05.6287.40.78	375	05.6297.40.78	299
05.6237.40.YU	365	05.6251.40.DA	368	05.6265.40.CB	371	05.6277.40.C6	373	05.6287.40.DA	297	05.6297.40.78	377
05.6237.AP	365	05.6251.40.YU	368	05.6265.40.DA	371	05.6277.40.CB	373	05.6287.40.DA	375	05.6297.40.DA	299
05.6237.AP.CB	365	05.6251.AP	368	05.6265.40.YU	371	05.6277.40.DA	373	05.6287.40.YU	297	05.6297.40.DA	377
05.6237.AP.DA	365	05.6251.AP.CB	368	05.6265.AP	371	05.6277.40.YU	373	05.6287.40.YU	375	05.6297.40.YU	299
05.6240.14	366	05.6251.AP.DA	368	05.6265.AP.CB	371	05.6277.AP	373	05.6287.AP	297	05.6297.40.YU	377
05.6240.14.CB	366	05.6252.14	368	05.6265.AP.DA	371	05.6277.AP.CB	373	05.6287.AP	375	05.6297.AP	299
05.6240.14.DA	366	05.6252.14.CB	368	05.6266.14	371	05.6277.AP.DA	373	05.6287.AP.DA	297	05.6297.AP	377
05.6240.40	366	05.6252.14.DA	368	05.6266.14.CB	371	05.6280.14	296	05.6287.AP.DA	375	05.6297.AP.DA	299
05.6240.40.78	366	05.6252.40	368	05.6266.14.DA	371	05.6280.14	374	05.6290.14	298	05.6297.AP.DA	377
05.6240.40.C6	366	05.6252.40.78	368	05.6266.40	371	05.6280.14.DA	296	05.6290.14	376	05.6300.14	300
05.6240.40.CB	366	05.6252.40.C6	368	05.6266.40.78	371	05.6280.14.DA	374	05.6290.14.DA	298	05.6300.14	378
05.6240.40.DA	366	05.6252.40.CB	368	05.6266.40.C6	371	05.6280.40	296	05.6290.14.DA	376	05.6300.14.DA	300
05.6240.40.YU	366	05.6252.40.DA	368	05.6266.40.CB	371	05.6280.40	374	05.6290.40	298	05.6300.14.DA	378
05.6240.AP	366	05.6252.40.YU	368	05.6266.40.DA	371	05.6280.40.78	296	05.6290.40	376	05.6300.40	300
05.6240.AP.CB	366	05.6252.AP	368	05.6266.40.YU	371	05.6280.40.78	374	05.6290.40.78	298	05.6300.40	378
05.6240.AP.DA	366	05.6252.AP.CB	368	05.6266.AP	371	05.6280.40.DA	296	05.6290.40.78	376	05.6300.40.78	300
05.6241.14	366	05.6252.AP.DA	368	05.6266.AP.CB	371	05.6280.40.DA	374	05.6290.40.DA	298	05.6300.40.78	378
05.6241.14.CB	366	05.6255.14	369	05.6266.AP.DA	371	05.6280.40.YU	296	05.6290.40.DA	376	05.6300.40.DA	300
05.6241.14.DA	366	05.6255.14.CB	369	05.6267.14	371	05.6280.40.YU	374	05.6290.40.YU	298	05.6300.40.DA	378
05.6241.40	366	05.6255.14.DA	369	05.6267.14.CB	371	05.6280.AP	296	05.6290.40.YU	376	05.6300.40.YU	300
05.6241.40.78	366	05.6255.40	369	05.6267.14.DA	371	05.6280.AP	374	05.6290.AP	298	05.6300.40.YU	378
05.6241.40.C6	366	05.6255.40.78	369	05.6267.40	371	05.6280.AP.DA	296	05.6290.AP	376	05.6300.AP	300
05.6241.40.CB	366	05.6255.40.C6	369	05.6267.40.78	371	05.6280.AP.DA	374	05.6290.AP.DA	298	05.6300.AP	378
05.6241.40.DA	366	05.6255.40.CB	369	05.6267.40.C6	371	05.6281.14	296	05.6290.AP.DA	376	05.6300.AP.DA	300
05.6241.40.YU	366	05.6255.40.DA	369	05.6267.40.CB	371	05.6281.14	374	05.6291.14	298	05.6300.AP.DA	378
05.6241.AP	366	05.6255.40.YU	369	05.6267.40.DA	371	05.6281.14.DA	296	05.6291.14	376	05.6301.14	300
05.6241.AP.CB	366	05.6255.AP	369	05.6267.40.YU	371	05.6281.14.DA	374	05.6291.14.DA	298	05.6301.14	378
05.6241.AP.DA	366	05.6255.AP.CB	369	05.6267.AP	371	05.6281.40	296	05.6291.14.DA	376	05.6301.14.DA	300
05.6242.14	366	05.6255.AP.DA	369	05.6267.AP.CB	371	05.6281.40	374	05.6291.40	298	05.6301.14.DA	378
05.6242.14.CB	366	05.6256.14	369	05.6267.AP.DA	371	05.6281.40.78	296	05.6291.40	376	05.6301.40	300
05.6242.14.DA	366	05.6256.14.CB	369	05.6270.14	372	05.6281.40.78	374	05.6291.40.78	298	05.6301.40	378
05.6242.40	366	05.6256.14.DA	369	05.6270.14.CB	372	05.6281.40.DA	296	05.6291.40.78	376	05.6301.40.78	300
05.6242.40.78	366	05.6256.40	369	05.6270.14.DA	372	05.6281.40.DA	374	05.6291.40.DA	298	05.6301.40.78	378
05.6242.40.C6	366	05.6256.40.78	369	05.6270.40	372	05.6281.40.YU	296	05.6291.40.DA	376	05.6301.40.DA	300
05.6242.40.CB	366	05.6256.40.C6	369	05.6270.40.78	372	05.6281.40.YU	374	05.6291.40.YU	298	05.6301.40.DA	378
05.6242.40.DA	366	05.6256.40.CB	369	05.6270.40.C6	372	05.6281.AP	296	05.6291.40.YU	376	05.6301.40.YU	300
05.6242.40.YU	366	05.6256.40.DA	369	05.6270.40.CB	372	05.6281.AP	374	05.6291.AP	298	05.6301.40.YU	378
05.6242.AP	366	05.6256.40.YU	369	05.6270.40.DA	372	05.6281.AP.DA	296	05.6291.AP	376	05.6301.AP	300
05.6242.AP.CB	366	05.6256.AP	369	05.6270.40.YU	372	05.6281.AP.DA	374	05.6291.AP.DA	298	05.6301.AP	378
05.6242.AP.DA	366	05.6256.AP.CB	369	05.6270.AP	372	05.6282.14	296	05.6291.AP.DA	376	05.6301.AP.DA	300
05.6245.14	367	05.6256.AP.DA	369	05.6270.AP.CB	372	05.6282.14	374	05.6292.14	298	05.6301.AP.DA	378
05.6245.14.CB	367	05.6257.14	369	05.6270.AP.DA	372	05.6282.14.DA	296	05.6292.14	376	05.6302.14	300
05.6245.14.DA	367	05.6257.14.CB	369	05.6271.14	372	05.6282.14.DA	374	05.6292.14.DA	298	05.6302.14	378
05.6245.40	367	05.6257.14.DA	369	05.6271.14.CB	372	05.6282.40	296	05.6292.14.DA	376	05.6302.14.DA	300
05.6245.40.78	367	05.6257.40	369	05.6271.14.DA	372	05.6282.40	374	05.6292.40	298	05.6302.14.DA	378
05.6245.40.C6	367	05.6257.40.78	369	05.6271.40	372	05.6282.40.78	296	05.6292.40	376	05.6302.40	300
05.6245.40.CB	367	05.6257.40.C6	369	05.6271.40.78	372	05.6282.40.78	374	05.6292.40.78	298	05.6302.40	378
05.6245.40.DA	367	05.6257.40.CB	369	05.6271.40.C6	372	05.6282.40.DA	296	05.6292.40.78	376	05.6302.40.78	300
05.6245.40.YU	367	05.6257.40.DA	369	05.6271.40.CB	372	05.6282.40.DA	374	05.6292.40.DA	298	05.6302.40.78	378
05.6245.AP	367	05.6257.40.YU	369	05.6271.40.DA	372	05.6282.40.YU	296	05.6292.40.DA	376	05.6302.40.DA	300
05.6245.AP.CB	367	05.6257.AP	369	05.6271.40.YU	372	05.6282.40.YU	374	05.6292.40.YU	298	05.6302.40.DA	378
05.6245.AP.DA	367	05.6257.AP.CB	369	05.6271.AP	372	05.6282.AP	296	05.6292.40.YU	376	05.6302.40.YU	300
05.6246.14	367	05.6257.AP.DA	369	05.6271.AP.CB	372	05.6282.AP	374	05.6292.AP	298	05.6302.40.YU	378
05.6246.14.CB	367	05.6260.14	370	05.6271.AP.DA	372	05.6282.AP.DA	296	05.6292.AP	376	05.6302.AP	300
05.6246.14.DA	367	05.6260.14.CB	370	05.6272.14	372	05.6282.AP.DA	374	05.6292.AP.DA	298	05.6302.AP	378
05.6246.40	367	05.6260.14.DA	370	05.6272.14.CB	372	05.6285.14	297	05.6292.AP.DA	376	05.6302.AP.DA	300
05.6246.40.78	367	05.6260.40	370	05.6272.14.DA	372	05.6285.14	375	05.6295.14	299	05.6302.AP.DA	378
05.6246.40.C6	367	05.6260.40.78	370	05.6272.40	372	05.6285.14.DA	297	05.6295.14	377	05.6305.14	301
05.6246.40.CB	367	05.6260.40.C6	370	05.6272.40.78	372	05.6285.14.DA	375	05.6295.14.DA	299	05.6305.14	379
05.6246.40.DA	367	05.6260.40.CB	370	05.6272.40.C6	372	05.6285.40	297	05.6295.14.DA	377	05.6305.14.DA	301
05.6246.40.YU	367	05.6260.40.DA	370	05.6272.40.CB	372	05.6285.40	375	05.6295.40	299	05.6305.14.DA	379
05.6246.AP	367	05.6260.40.YU	370	05.6272.40.DA	372	05.6285.40.78	297	05.6295.40	377	05.6305.40	301
05.6246.AP.CB	367	05.6260.AP	370	05.6272.40.YU	372	05.6285.40.78	375	05.6295.40.78	299	05.6305.40	379
05.6246.AP.DA	367	05.6260.AP.CB	370	05.6272.AP	372	05.6285.40.DA	297	05.6295.40.78	377	05.6305.40.78	301
05.6247.14	367	05.6260.AP.DA	370	05.6272.AP.CB	372	05.6285.40.DA	375	05.6295.40.DA	299	05.6305.40.78	379
05.6247.14.CB	367	05.6261.14	370	05.6272.AP.DA	372	05.6285.40.YU	297	05.6295.40.DA	377	05.6305.40.DA	301
05.6247.14.DA	367	05.6261.14.CB	370	05.6275.14	373	05.6285.40.YU	375	05.6295.40.YU	299	05.6305.40.DA	379
05.6247.40	367	05.6261.14.DA	370	05.6275.14.CB	373	05.6285.AP	297	05.6295.40.YU	377	05.6305.40.YU	301
05.6247.40.78	367	05.6261.40	370	05.6275.14.DA	373	05.6285.AP	375	05.6295.AP	299	05.6305.40.YU	379
05.6247.40.C6	367	05.6261.40.78	370	05.6275.40	373	05.6285.AP.DA	297	05.6295.AP	377	05.6305.AP	301
05.6247.40.CB	367	05.6261.40.C6	370	05.6275.40.78	373	05.6285.AP.DA	375	05.6295.AP.DA	299	05.6305.AP	379
05.6247.40.DA	367	05.6261.40.CB	370	05.6275.40.C6	373	05.6286.14	297	05.6295.AP.DA	377	05.6305.AP.DA	301
05.6247.40.YU	367	05.6261.40.DA	370	05.6275.40.CB	373	05.6286.14	375	05.6296.14	299	05.6305.AP.DA	379
05.6247.AP	367	05.6261.40.YU	370	05.6275.40.DA	373	05.6286.14.DA	297	05.6296.14	377	05.6306.14	301
05.6247.AP.CB	367	05.6261.AP	370	05.6275.40.YU	373	05.6286.14.DA	375	05.6296.14.DA	299	05.6306.14	379
05.6247.AP.DA	367	05.6261.AP.CB	370	05.6275.AP	373	05.6286.40	297	05.6296.14.DA	377	05.6306.14.DA	301
05.6250.14	368	05.6261.AP.DA	370	05.6275.AP.CB	373	05.6286.40	375	05.6296.40	299	05.6306.14.DA	379
05.6250.14.CB	368	05.6262.14	370	05.6275.AP.DA	373	05.6286.40.78	297	05.6296.40	377	05.6306.40	301
05.6250.14.DA	368	05.6262.14.CB	370	05.6276.14	373	05.6286.40.78	375	05.6296.40.78	299	05.6306.40	379
05.6250.40	368	05.6262.14.DA	370	05.6276.14.CB	373	05.6286.40.DA	297	05.6296.40.78	377	05.6306.40.78	301
05.6250.40.78	368	05.6262.40	370	05.6276.14.DA	373	05.6286.40.DA	375	05.6296.40.DA	299	05.6306.40.78	379

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.6306.40.DA	301	05.6316.40.78	381	05.6332.AP	384	05.6352.40.CB	388	05.6382.40.DA	392	05.6406.AP.CB	396
05.6306.40.DA	379	05.6316.40.DA	303	05.6332.AP.CB	384	05.6352.AP	388	05.6382.40.YU	392	05.6407.14.CB	396
05.6306.40.YU	301	05.6316.40.DA	381	05.6335.14	385	05.6352.AP.CB	388	05.6382.AP.CB	392	05.6407.40.C6	396
05.6306.40.YU	379	05.6316.40.YU	303	05.6335.14.CB	385	05.6355.14	389	05.6382.AP.DA	392	05.6407.40.CB	396
05.6306.AP	301	05.6316.40.YU	381	05.6335.40	385	05.6355.14.CB	389	05.6385.14.CB	393	05.6407.AP.CB	396
05.6306.AP	379	05.6316.AP	303	05.6335.40.78	385	05.6355.40	389	05.6385.14.DA	393	05.6410.14.CB	397
05.6306.AP.DA	301	05.6316.AP	381	05.6335.40.C6	385	05.6355.40.78	389	05.6385.40.C6	393	05.6410.40.C6	397
05.6306.AP.DA	379	05.6316.AP.DA	303	05.6335.40.CB	385	05.6355.40.C6	389	05.6385.40.CB	393	05.6410.40.CB	397
05.6307.14	301	05.6316.AP.DA	381	05.6335.AP	385	05.6355.40.CB	389	05.6385.40.DA	393	05.6410.AP.CB	397
05.6307.14	379	05.6317.14	303	05.6335.AP.CB	385	05.6355.AP	389	05.6385.40.YU	393	05.6411.14.CB	397
05.6307.14.DA	301	05.6317.14	381	05.6336.14	385	05.6355.AP.CB	389	05.6385.AP.CB	393	05.6411.40.C6	397
05.6307.14.DA	379	05.6317.14.DA	303	05.6336.14.CB	385	05.6356.14	389	05.6385.AP.DA	393	05.6411.40.CB	397
05.6307.40	301	05.6317.14.DA	381	05.6336.40	385	05.6356.14.CB	389	05.6386.14.CB	393	05.6411.AP.CB	397
05.6307.40	379	05.6317.40	303	05.6336.40.78	385	05.6356.40	389	05.6386.14.DA	393	05.6412.14.CB	397
05.6307.40.78	301	05.6317.40	381	05.6336.40.C6	385	05.6356.40.78	389	05.6386.40.C6	393	05.6412.40.C6	397
05.6307.40.78	379	05.6317.40.78	303	05.6336.40.CB	385	05.6356.40.C6	389	05.6386.40.CB	393	05.6412.40.CB	397
05.6307.40.DA	301	05.6317.40.78	381	05.6336.AP	385	05.6356.40.CB	389	05.6386.40.DA	393	05.6412.AP.CB	397
05.6307.40.DA	379	05.6317.40.DA	303	05.6336.AP.CB	385	05.6356.AP	389	05.6386.40.YU	393	05.6415.14.CB	397
05.6307.40.YU	301	05.6317.40.DA	381	05.6337.14	385	05.6356.AP.CB	389	05.6386.AP.CB	393	05.6415.40.C6	397
05.6307.40.YU	379	05.6317.40.YU	303	05.6337.14.CB	385	05.6357.14	389	05.6386.AP.DA	393	05.6415.40.CB	397
05.6307.AP	301	05.6317.40.YU	381	05.6337.40	385	05.6357.14.CB	389	05.6387.14.CB	393	05.6415.AP.CB	397
05.6307.AP	379	05.6317.AP	303	05.6337.40.78	385	05.6357.40	389	05.6387.14.DA	393	05.6416.14.CB	397
05.6307.AP.DA	301	05.6317.AP	381	05.6337.40.C6	385	05.6357.40.78	389	05.6387.40.C6	393	05.6416.40.C6	397
05.6307.AP.DA	379	05.6317.AP.DA	303	05.6337.40.CB	385	05.6357.40.C6	389	05.6387.40.CB	393	05.6416.40.CB	397
05.6310.14	302	05.6317.AP.DA	381	05.6337.AP	385	05.6357.40.CB	389	05.6387.40.DA	393	05.6416.AP.CB	397
05.6310.14	380	05.6320.14	382	05.6337.AP.CB	385	05.6357.AP	389	05.6387.40.YU	393	05.6417.14.CB	397
05.6310.14.DA	302	05.6320.14.CB	382	05.6340.14	386	05.6357.AP.CB	389	05.6387.AP.CB	393	05.6417.40.C6	397
05.6310.14.DA	380	05.6320.40	382	05.6340.14.CB	386	05.6360.14.CB	390	05.6387.AP.DA	393	05.6417.40.CB	397
05.6310.40	302	05.6320.40.78	382	05.6340.40	386	05.6360.40.C6	390	05.6390.14.CB	394	05.6417.AP.CB	397
05.6310.40	380	05.6320.40.C6	382	05.6340.40.78	386	05.6360.40.CB	390	05.6390.14.DA	394	05.6420.14	232
05.6310.40.78	302	05.6320.40.CB	382	05.6340.40.C6	386	05.6360.AP.CB	390	05.6390.40.C6	394	05.6420.14.1V	232
05.6310.40.78	380	05.6320.AP	382	05.6340.40.CB	386	05.6361.14.CB	390	05.6390.40.CB	394	05.6420.14.CB	232
05.6310.40.DA	302	05.6320.AP.CB	382	05.6340.AP	386	05.6361.40.C6	390	05.6390.40.DA	394	05.6420.14.DA	232
05.6310.40.DA	380	05.6321.14	382	05.6340.AP.CB	386	05.6361.40.CB	390	05.6390.40.YU	394	05.6420.40	232
05.6310.40.YU	302	05.6321.14.CB	382	05.6341.14	386	05.6361.AP.CB	390	05.6390.AP.CB	394	05.6420.40.1V	232
05.6310.40.YU	380	05.6321.40	382	05.6341.14.CB	386	05.6362.14.CB	390	05.6390.AP.DA	394	05.6420.40.78	232
05.6310.AP	302	05.6321.40.78	382	05.6341.40	386	05.6362.40.C6	390	05.6391.14.CB	394	05.6420.40.C6	232
05.6310.AP	380	05.6321.40.C6	382	05.6341.40.78	386	05.6362.40.CB	390	05.6391.14.DA	394	05.6420.40.CB	232
05.6310.AP.DA	302	05.6321.40.CB	382	05.6341.40.C6	386	05.6362.AP.CB	390	05.6391.40.C6	394	05.6420.40.DA	232
05.6310.AP.DA	380	05.6321.AP	382	05.6341.40.CB	386	05.6365.14.CB	390	05.6391.40.CB	394	05.6420.40.RX	232
05.6311.14	302	05.6321.AP.CB	382	05.6341.AP	386	05.6365.40.C6	390	05.6391.40.DA	394	05.6420.40.YU	232
05.6311.14	380	05.6322.14	382	05.6341.AP.CB	386	05.6365.40.CB	390	05.6391.40.YU	394	05.6420.AP	232
05.6311.14.DA	302	05.6322.14.CB	382	05.6342.14	386	05.6365.AP.CB	390	05.6391.AP.CB	394	05.6420.AP.1V	232
05.6311.14.DA	380	05.6322.40	382	05.6342.14.CB	386	05.6366.14.CB	390	05.6391.AP.DA	394	05.6420.AP.CB	232
05.6311.40	302	05.6322.40.78	382	05.6342.40	386	05.6366.40.C6	390	05.6392.14.CB	394	05.6420.AP.DA	232
05.6311.40	380	05.6322.40.C6	382	05.6342.40.78	386	05.6366.40.CB	390	05.6392.14.DA	394	05.6421.14	232
05.6311.40.78	302	05.6322.40.CB	382	05.6342.40.C6	386	05.6366.AP.CB	390	05.6392.40.C6	394	05.6421.14.1V	232
05.6311.40.78	380	05.6322.AP	382	05.6342.40.CB	386	05.6367.14.CB	390	05.6392.40.CB	394	05.6421.14.CB	232
05.6311.40.DA	302	05.6322.AP.CB	382	05.6342.AP	386	05.6367.40.C6	390	05.6392.40.DA	394	05.6421.14.DA	232
05.6311.40.DA	380	05.6325.14	383	05.6342.AP.CB	386	05.6367.40.CB	390	05.6392.40.YU	394	05.6421.40	232
05.6311.40.YU	302	05.6325.14.CB	383	05.6345.14	387	05.6367.AP.CB	390	05.6392.AP.CB	394	05.6421.40.1V	232
05.6311.40.YU	380	05.6325.40	383	05.6345.14.CB	387	05.6370.14.CB	391	05.6392.AP.DA	394	05.6421.40.78	232
05.6311.AP	302	05.6325.40.78	383	05.6345.40	387	05.6370.40.C6	391	05.6395.14.CB	395	05.6421.40.C6	232
05.6311.AP	380	05.6325.40.C6	383	05.6345.40.78	387	05.6370.40.CB	391	05.6395.14.DA	395	05.6421.40.CB	232
05.6311.AP.DA	302	05.6325.40.CB	383	05.6345.40.C6	387	05.6370.AP.CB	391	05.6395.40.C6	395	05.6421.40.DA	232
05.6311.AP.DA	380	05.6325.AP	383	05.6345.40.CB	387	05.6371.14.CB	391	05.6395.40.CB	395	05.6421.40.RX	232
05.6312.14	302	05.6325.AP.CB	383	05.6345.AP	387	05.6371.40.C6	391	05.6395.40.DA	395	05.6421.40.YU	232
05.6312.14	380	05.6326.14	383	05.6345.AP.CB	387	05.6371.40.CB	391	05.6395.40.YU	395	05.6421.AP	232
05.6312.14.DA	302	05.6326.14.CB	383	05.6346.14	387	05.6371.AP.CB	391	05.6395.AP.CB	395	05.6421.AP.1V	232
05.6312.14.DA	380	05.6326.40	383	05.6346.14.CB	387	05.6372.14.CB	391	05.6395.AP.DA	395	05.6421.AP.CB	232
05.6312.40	302	05.6326.40.78	383	05.6346.40	387	05.6372.40.C6	391	05.6396.14.CB	395	05.6421.AP.DA	232
05.6312.40	380	05.6326.40.C6	383	05.6346.40.78	387	05.6372.40.CB	391	05.6396.14.DA	395	05.6422.14	232
05.6312.40.78	302	05.6326.40.CB	383	05.6346.40.C6	387	05.6372.AP.CB	391	05.6396.40.C6	395	05.6422.14.1V	232
05.6312.40.78	380	05.6326.AP	383	05.6346.40.CB	387	05.6375.14.CB	391	05.6396.40.CB	395	05.6422.14.CB	232
05.6312.40.DA	302	05.6326.AP.CB	383	05.6346.AP	387	05.6375.40.C6	391	05.6396.40.DA	395	05.6422.14.DA	232
05.6312.40.DA	380	05.6327.14	383	05.6346.AP.CB	387	05.6375.40.CB	391	05.6396.40.YU	395	05.6422.40	232
05.6312.40.YU	302	05.6327.14.CB	383	05.6347.14	387	05.6375.AP.CB	391	05.6396.AP.CB	395	05.6422.40.1V	232
05.6312.40.YU	380	05.6327.40	383	05.6347.14.CB	387	05.6376.14.CB	391	05.6396.AP.DA	395	05.6422.40.78	232
05.6312.AP	302	05.6327.40.78	383	05.6347.40	387	05.6376.40.C6	391	05.6397.14.CB	395	05.6422.40.C6	232
05.6312.AP	380	05.6327.40.C6	383	05.6347.40.78	387	05.6376.40.CB	391	05.6397.14.DA	395	05.6422.40.CB	232
05.6312.AP.DA	302	05.6327.40.CB	383	05.6347.40.C6	387	05.6376.AP.CB	391	05.6397.40.C6	395	05.6422.40.DA	232
05.6312.AP.DA	380	05.6327.AP	383	05.6347.40.CB	387	05.6377.14.CB	391	05.6397.40.CB	395	05.6422.40.RX	232
05.6315.14	303	05.6327.AP.CB	383	05.6347.AP	387	05.6377.40.C6	391	05.6397.40.DA	395	05.6422.40.YU	232
05.6315.14	381	05.6330.14	384	05.6347.AP.CB	387	05.6377.40.CB	391	05.6397.40.YU	395	05.6422.AP	232
05.6315.14.DA	303	05.6330.14.CB	384	05.6350.14	388	05.6377.AP.CB	391	05.6397.AP.CB	395	05.6422.AP.1V	232
05.6315.14.DA	381	05.6330.40	384	05.6350.14.CB	388	05.6380.14.CB	392	05.6397.AP.DA	395	05.6422.AP.CB	232
05.6315.40	303	05.6330.40.78	384	05.6350.40	388	05.6380.14.DA	392	05.6400.14.CB	396	05.6422.AP.DA	232
05.6315.40	381	05.6330.40.C6	384	05.6350.40.78	388	05.6380.40.C6	392	05.6400.40.C6	396	05.6425.14	233
05.6315.40.78	303	05.6330.40.CB	384	05.6350.40.C6	388	05.6380.40.CB	392	05.6400.40.CB	396	05.6425.14.1V	233
05.6315.40.78	381	05.6330.AP	384	05.6350.40.CB	388	05.6380.40.DA	392	05.6400.AP.CB	396	05.6425.14.CB	233
05.6315.40.DA	303	05.6330.AP.CB	384	05.6350.AP	388	05.6380.40.YU	392	05.6401.14.CB	396	05.6425.14.DA	233
05.6315.40.DA	381	05.6331.14	384	05.6350.AP.CB	388	05.6380.AP.CB	392	05.6401.40.C6	396	05.6425.40	233
05.6315.40.YU	303	05.6331.14.CB	384	05.6351.14	388	05.6380.AP.DA	392	05.6401.40.CB	396	05.6425.40.1V	233
05.6315.40.YU	381	05.6331.40	384	05.6351.14.CB	388	05.6381.14.CB	392	05.6401.AP.CB	396	05.6425.40.78	233
05.6315.AP	303	05.6331.40.78	384	05.6351.40	388	05.6381.14.DA	392	05.6402.14.CB	396	05.6425.40.C6	233
05.6315.AP	381	05.6331.40.C6	384	05.6351.40.78	388	05.6381.40.C6	392	05.6402.40.C6	396	05.6425.40.CB	233
05.6315.AP.DA	303	05.6331.40.CB	384	05.6351.40.C6	388	05.6381.40.CB	392	05.6402.40.CB	396	05.6425.40.DA	233
05.6315.AP.DA	381	05.6331.AP	384	05.6351.40.CB	388	05.6381.40.DA	392	05.6402.AP.CB	396	05.6425.40.RX	233
05.6316.14	303	05.6331.AP.CB	384	05.6351.AP	388	05.6381.40.YU	392	05.6405.14.CB	396	05.6425.40.YU	233
05.6316.14	381	05.6332.14	384	05.6351.AP.CB	388	05.6381.AP.CB	392	05.6405.40.C6	396	05.6425.AP	233
05.6316.14.DA	303	05.6332.14.CB	384	05.6352.14	388	05.6381.AP.DA	392	05.6405.40.CB	396	05.6425.AP.1V	233
05.6316.14.DA	381	05.6332.40	384	05.6352.14.CB	388	05.6382.14.CB	392	05.6405.AP.CB	396	05.6425.AP.CB	233
05.6316.40	303	05.6332.40.78	384	05.6352.40	388	05.6382.14.DA	392	05.6406.14.CB	396	05.6425.AP.DA	233
05.6316.40	381	05.6332.40.C6	384	05.6352.40.78	388	05.6382.40.C6	392	05.6406.40.C6	396	05.6426.14	233
05.6316.40.78	303	05.6332.40.CB	384	05.6352.40.C6	388	05.6382.40.CB	392	05.6406.40.CB	396	05.6426.14.1V	233

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.6426.14.CB	233	05.6436.14.1V	235	05.6446.14	237	05.6455.AP.DA	239	05.6521.40	404	05.6716.40.C6	411
05.6426.14.DA	233	05.6436.14.CB	235	05.6446.14.1V	237	05.6456.14	239	05.6521.40.78	404	05.6716.40.CB	411
05.6426.40	233	05.6436.14.DA	235	05.6446.14.CB	237	05.6456.14.1V	239	05.6521.40.C6	404	05.6717.14.CB	411
05.6426.40.1V	233	05.6436.40	235	05.6446.14.DA	237	05.6456.14.CB	239	05.6521.40.CB	404	05.6717.40.C6	411
05.6426.40.78	233	05.6436.40.1V	235	05.6446.40	237	05.6456.14.DA	239	05.6522.14	404	05.6717.40.CB	411
05.6426.40.C6	233	05.6436.40.78	235	05.6446.40.1V	237	05.6456.40	239	05.6522.14.CB	404	05.6720.14	412
05.6426.40.CB	233	05.6436.40.C6	235	05.6446.40.78	237	05.6456.40.1V	239	05.6522.40	404	05.6720.14.CB	412
05.6426.40.DA	233	05.6436.40.CB	235	05.6446.40.C6	237	05.6456.40.78	239	05.6522.40.78	404	05.6720.40	412
05.6426.40.RX	233	05.6436.40.DA	235	05.6446.40.CB	237	05.6456.40.C6	239	05.6522.40.C6	404	05.6720.40.78	412
05.6426.40.YU	233	05.6436.40.RX	235	05.6446.40.DA	237	05.6456.40.CB	239	05.6522.40.CB	404	05.6720.40.C6	412
05.6426.AP	233	05.6436.40.YU	235	05.6446.40.RX	237	05.6456.40.DA	239	05.6525.14	405	05.6720.40.CB	412
05.6426.AP.1V	233	05.6436.AP	235	05.6446.40.YU	237	05.6456.40.RX	239	05.6525.14.CB	405	05.6721.14	412
05.6426.AP.CB	233	05.6436.AP.1V	235	05.6446.AP	237	05.6456.40.YU	239	05.6525.40	405	05.6721.14.CB	412
05.6426.AP.DA	233	05.6436.AP.CB	235	05.6446.AP.1V	237	05.6456.AP	239	05.6525.40.78	405	05.6721.40	412
05.6427.14	233	05.6436.AP.DA	235	05.6446.AP.CB	237	05.6456.AP.1V	239	05.6525.40.C6	405	05.6721.40.78	412
05.6427.14.1V	233	05.6437.14	235	05.6446.AP.DA	237	05.6456.AP.CB	239	05.6525.40.CB	405	05.6721.40.C6	412
05.6427.14.CB	233	05.6437.14.1V	235	05.6447.14	237	05.6456.AP.DA	239	05.6526.14	405	05.6721.40.CB	412
05.6427.14.DA	233	05.6437.14.CB	235	05.6447.14.1V	237	05.6457.14	239	05.6526.14.CB	405	05.6722.14	412
05.6427.40	233	05.6437.14.DA	235	05.6447.14.CB	237	05.6457.14.1V	239	05.6526.40	405	05.6722.14.CB	412
05.6427.40.1V	233	05.6437.40	235	05.6447.14.DA	237	05.6457.14.CB	239	05.6526.40.78	405	05.6722.40	412
05.6427.40.78	233	05.6437.40.1V	235	05.6447.40	237	05.6457.14.DA	239	05.6526.40.C6	405	05.6722.40.78	412
05.6427.40.C6	233	05.6437.40.78	235	05.6447.40.1V	237	05.6457.40	239	05.6526.40.CB	405	05.6722.40.C6	412
05.6427.40.CB	233	05.6437.40.C6	235	05.6447.40.78	237	05.6457.40.1V	239	05.6527.14	405	05.6722.40.CB	412
05.6427.40.DA	233	05.6437.40.CB	235	05.6447.40.C6	237	05.6457.40.78	239	05.6527.14.CB	405	05.6725.14	413
05.6427.40.RX	233	05.6437.40.DA	235	05.6447.40.CB	237	05.6457.40.C6	239	05.6527.40	405	05.6725.14.CB	413
05.6427.40.YU	233	05.6437.40.RX	235	05.6447.40.DA	237	05.6457.40.CB	239	05.6527.40.78	405	05.6725.40	413
05.6427.AP	233	05.6437.40.YU	235	05.6447.40.RX	237	05.6457.40.DA	239	05.6527.40.C6	405	05.6725.40.78	413
05.6427.AP.1V	233	05.6437.AP	235	05.6447.40.YU	237	05.6457.40.RX	239	05.6527.40.CB	405	05.6725.40.C6	413
05.6427.AP.CB	233	05.6437.AP.1V	235	05.6447.AP	237	05.6457.40.YU	239	05.6530.14.CB	406	05.6725.40.CB	413
05.6427.AP.DA	233	05.6437.AP.CB	235	05.6447.AP.1V	237	05.6457.AP	239	05.6530.40.C6	406	05.6726.14	413
05.6430.14	234	05.6437.AP.DA	235	05.6447.AP.CB	237	05.6457.AP.1V	239	05.6530.40.CB	406	05.6726.14.CB	413
05.6430.14.1V	234	05.6440.14	236	05.6447.AP.DA	237	05.6457.AP.CB	239	05.6531.14.CB	406	05.6726.40	413
05.6430.14.CB	234	05.6440.14.1V	236	05.6450.14	238	05.6457.AP.DA	239	05.6531.40.C6	406	05.6726.40.78	413
05.6430.14.DA	234	05.6440.14.CB	236	05.6450.14.1V	238	05.6500.14	400	05.6531.40.CB	406	05.6726.40.C6	413
05.6430.40	234	05.6440.14.DA	236	05.6450.14.CB	238	05.6500.14.CB	400	05.6532.14.CB	406	05.6726.40.CB	413
05.6430.40.1V	234	05.6440.40	236	05.6450.14.DA	238	05.6500.40	400	05.6532.40.C6	406	05.6727.14	413
05.6430.40.78	234	05.6440.40.1V	236	05.6450.40	238	05.6500.40.78	400	05.6532.40.CB	406	05.6727.14.CB	413
05.6430.40.C6	234	05.6440.40.78	236	05.6450.40.1V	238	05.6500.40.C6	400	05.6535.14.CB	407	05.6727.40	413
05.6430.40.CB	234	05.6440.40.C6	236	05.6450.40.78	238	05.6500.40.CB	400	05.6535.40.C6	407	05.6727.40.78	413
05.6430.40.DA	234	05.6440.40.CB	236	05.6450.40.C6	238	05.6501.14	400	05.6535.40.CB	407	05.6727.40.C6	413
05.6430.40.RX	234	05.6440.40.DA	236	05.6450.40.CB	238	05.6501.14.CB	400	05.6536.14.CB	407	05.6727.40.CB	413
05.6430.40.YU	234	05.6440.40.RX	236	05.6450.40.DA	238	05.6501.40	400	05.6536.40.C6	407	05.6730.14.CB	414
05.6430.AP	234	05.6440.40.YU	236	05.6450.40.RX	238	05.6501.40.78	400	05.6536.40.CB	407	05.6730.40.C6	414
05.6430.AP.1V	234	05.6440.AP	236	05.6450.40.YU	238	05.6501.40.C6	400	05.6537.14.CB	407	05.6730.40.CB	414
05.6430.AP.CB	234	05.6440.AP.1V	236	05.6450.AP	238	05.6501.40.CB	400	05.6537.40.C6	407	05.6731.14.CB	414
05.6430.AP.DA	234	05.6440.AP.CB	236	05.6450.AP.1V	238	05.6502.14	400	05.6537.40.CB	407	05.6731.40.C6	414
05.6431.14	234	05.6440.AP.DA	236	05.6450.AP.CB	238	05.6502.14.CB	400	05.6700.14	408	05.6731.40.CB	414
05.6431.14.1V	234	05.6441.14	236	05.6450.AP.DA	238	05.6502.40	400	05.6700.14.CB	408	05.6732.14.CB	414
05.6431.14.CB	234	05.6441.14.1V	236	05.6451.14	238	05.6502.40.78	400	05.6700.40	408	05.6732.40.C6	414
05.6431.14.DA	234	05.6441.14.CB	236	05.6451.14.1V	238	05.6502.40.C6	400	05.6700.40.78	408	05.6732.40.CB	414
05.6431.40	234	05.6441.14.DA	236	05.6451.14.CB	238	05.6502.40.CB	400	05.6700.40.C6	408	05.6735.14.CB	415
05.6431.40.1V	234	05.6441.40	236	05.6451.14.DA	238	05.6505.14	401	05.6700.40.CB	408	05.6735.40.C6	415
05.6431.40.78	234	05.6441.40.1V	236	05.6451.40	238	05.6505.14.CB	401	05.6701.14	408	05.6735.40.CB	415
05.6431.40.C6	234	05.6441.40.78	236	05.6451.40.1V	238	05.6505.40	401	05.6701.14.CB	408	05.6736.14.CB	415
05.6431.40.CB	234	05.6441.40.C6	236	05.6451.40.78	238	05.6505.40.78	401	05.6701.40	408	05.6736.40.C6	415
05.6431.40.DA	234	05.6441.40.CB	236	05.6451.40.C6	238	05.6505.40.C6	401	05.6701.40.78	408	05.6736.40.CB	415
05.6431.40.RX	234	05.6441.40.DA	236	05.6451.40.CB	238	05.6505.40.CB	401	05.6701.40.C6	408	05.6737.14.CB	415
05.6431.40.YU	234	05.6441.40.RX	236	05.6451.40.DA	238	05.6506.14	401	05.6701.40.CB	408	05.6737.40.C6	415
05.6431.AP	234	05.6441.40.YU	236	05.6451.40.RX	238	05.6506.14.CB	401	05.6702.14	408	05.6737.40.CB	415
05.6431.AP.1V	234	05.6441.AP	236	05.6451.40.YU	238	05.6506.40	401	05.6702.14.CB	408	05.7000.74	649
05.6431.AP.CB	234	05.6441.AP.1V	236	05.6451.AP	238	05.6506.40.78	401	05.6702.40	408	05.7000.B1	649
05.6431.AP.DA	234	05.6441.AP.CB	236	05.6451.AP.1V	238	05.6506.40.C6	401	05.6702.40.78	408	05.7000.GL	649
05.6432.14	234	05.6441.AP.DA	236	05.6451.AP.CB	238	05.6506.40.CB	401	05.6702.40.C6	408	05.7001.74	649
05.6432.14.1V	234	05.6442.14	236	05.6451.AP.DA	238	05.6507.14	401	05.6702.40.CB	408	05.7001.B1	649
05.6432.14.CB	234	05.6442.14.1V	236	05.6452.14	238	05.6507.14.CB	401	05.6705.14	409	05.7001.GL	649
05.6432.14.DA	234	05.6442.14.CB	236	05.6452.14.1V	238	05.6507.40	401	05.6705.14.CB	409	05.7002.74	649
05.6432.40	234	05.6442.14.DA	236	05.6452.14.CB	238	05.6507.40.78	401	05.6705.40	409	05.7002.B1	649
05.6432.40.1V	234	05.6442.40	236	05.6452.14.DA	238	05.6507.40.C6	401	05.6705.40.78	409	05.7002.GL	649
05.6432.40.78	234	05.6442.40.1V	236	05.6452.40	238	05.6507.40.CB	401	05.6705.40.C6	409	05.7005.74	649
05.6432.40.C6	234	05.6442.40.78	236	05.6452.40.1V	238	05.6510.14.CB	402	05.6705.40.CB	409	05.7005.B1	649
05.6432.40.CB	234	05.6442.40.C6	236	05.6452.40.78	238	05.6510.40.C6	402	05.6706.14	409	05.7005.GL	649
05.6432.40.DA	234	05.6442.40.CB	236	05.6452.40.C6	238	05.6510.40.CB	402	05.6706.14.CB	409	05.7006.74	649
05.6432.40.RX	234	05.6442.40.DA	236	05.6452.40.CB	238	05.6511.14.CB	402	05.6706.40	409	05.7006.B1	649
05.6432.40.YU	234	05.6442.40.RX	236	05.6452.40.DA	238	05.6511.40.C6	402	05.6706.40.78	409	05.7006.GL	649
05.6432.AP	234	05.6442.40.YU	236	05.6452.40.RX	238	05.6511.40.CB	402	05.6706.40.C6	409	05.7007.74	649
05.6432.AP.1V	234	05.6442.AP	236	05.6452.40.YU	238	05.6512.14.CB	402	05.6706.40.CB	409	05.7007.B1	649
05.6432.AP.CB	234	05.6442.AP.1V	236	05.6452.AP	238	05.6512.40.C6	402	05.6707.14	409	05.7007.GL	649
05.6432.AP.DA	234	05.6442.AP.CB	236	05.6452.AP.1V	238	05.6512.40.CB	402	05.6707.14.CB	409	05.7010.74	651
05.6435.14	235	05.6442.AP.DA	236	05.6452.AP.CB	238	05.6515.14.CB	403	05.6707.40	409	05.7010.B1	651
05.6435.14.1V	235	05.6445.14	237	05.6452.AP.DA	238	05.6515.40.C6	403	05.6707.40.78	409	05.7010.GL	651
05.6435.14.CB	235	05.6445.14.1V	237	05.6455.14	239	05.6515.40.CB	403	05.6707.40.C6	409	05.7011.74	651
05.6435.14.DA	235	05.6445.14.CB	237	05.6455.14.1V	239	05.6516.14.CB	403	05.6707.40.CB	409	05.7011.B1	651
05.6435.40	235	05.6445.14.DA	237	05.6455.14.CB	239	05.6516.40.C6	403	05.6710.14.CB	410	05.7011.GL	651
05.6435.40.1V	235	05.6445.40	237	05.6455.14.DA	239	05.6516.40.CB	403	05.6710.40.C6	410	05.7012.74	651
05.6435.40.78	235	05.6445.40.1V	237	05.6455.40	239	05.6517.14.CB	403	05.6710.40.CB	410	05.7012.B1	651
05.6435.40.C6	235	05.6445.40.78	237	05.6455.40.1V	239	05.6517.40.C6	403	05.6711.14.CB	410	05.7012.GL	651
05.6435.40.CB	235	05.6445.40.C6	237	05.6455.40.78	239	05.6517.40.CB	403	05.6711.40.C6	410	05.7015.74	651
05.6435.40.DA	235	05.6445.40.CB	237	05.6455.40.C6	239	05.6520.14	404	05.6711.40.CB	410	05.7015.B1	651
05.6435.40.RX	235	05.6445.40.DA	237	05.6455.40.CB	239	05.6520.14.CB	404	05.6712.14.CB	410	05.7015.GL	651
05.6435.40.YU	235	05.6445.40.RX	237	05.6455.40.DA	239	05.6520.40	404	05.6712.40.C6	410	05.7016.74	651
05.6435.AP	235	05.6445.40.YU	237	05.6455.40.RX	239	05.6520.40.78	404	05.6712.40.CB	410	05.7016.B1	651
05.6435.AP.1V	235	05.6445.AP	237	05.6455.40.YU	239	05.6520.40.C6	404	05.6715.14.CB	411	05.7016.GL	651
05.6435.AP.CB	235	05.6445.AP.1V	237	05.6455.AP	239	05.6520.40.CB	404	05.6715.40.C6	411	05.7017.74	651
05.6435.AP.DA	235	05.6445.AP.CB	237	05.6455.AP.1V	239	05.6521.14	404	05.6715.40.CB	411	05.7017.B1	651
05.6436.14	235	05.6445.AP.DA	237	05.6455.AP.CB	239	05.6521.14.CB	404	05.6716.14.CB	411	05.7017.GL	651

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.7020.74	653	05.7155.GL	621	05.7317.B1	596	05.7439.74	641	05.7607.GLA	625	05.7710.B1	631
05.7020.B1	653	05.7156.74	621	05.7317.GL	596	05.7439.B1	641	05.7608.74A	625	05.7710.GL	631
05.7020.GL	653	05.7156.B1	621	05.7400.74	638	05.7439.GL	641	05.7608.B1A	625	05.7711.74	631
05.7021.74	653	05.7156.GL	621	05.7400.B1	638	05.7440.74	631	05.7608.GLA	625	05.7711.B1	631
05.7021.B1	653	05.7157.74	621	05.7400.GL	638	05.7440.B1	631	05.7610.74A	626	05.7711.GL	631
05.7021.GL	653	05.7157.B1	621	05.7401.74	638	05.7440.GL	631	05.7610.B1A	626	05.7712.74	631
05.7030.74	650	05.7157.GL	621	05.7401.B1	638	05.7441.74	631	05.7610.GLA	626	05.7712.B1	631
05.7030.B1	650	05.7200.74	628	05.7401.GL	638	05.7441.B1	631	05.7611.74A	626	05.7712.GL	631
05.7030.GL	650	05.7200.B1	628	05.7402.74	638	05.7441.GL	631	05.7611.B1A	626	05.7715.74	631
05.7031.74	650	05.7200.GL	628	05.7402.B1	638	05.7442.74	641	05.7611.GLA	626	05.7715.B1	631
05.7031.B1	650	05.7201.74	628	05.7402.GL	638	05.7442.B1	641	05.7612.74A	627	05.7715.GL	631
05.7031.GL	650	05.7201.B1	628	05.7403.74	638	05.7442.GL	641	05.7612.B1A	627	05.7716.74	631
05.7035.74	652	05.7201.GL	628	05.7403.B1	638	05.7443.74	641	05.7612.GLA	627	05.7716.B1	631
05.7035.B1	652	05.7202.74	628	05.7403.GL	638	05.7443.B1	641	05.7613.74A	627	05.7716.GL	631
05.7035.GL	652	05.7202.B1	628	05.7404.74	638	05.7443.GL	641	05.7613.B1A	627	05.7717.74	631
05.7036.74	652	05.7202.GL	628	05.7404.B1	638	05.7444.74	641	05.7613.GLA	627	05.7717.B1	631
05.7036.B1	652	05.7205.74	628	05.7404.GL	638	05.7444.B1	641	05.7615.74A	626	05.7717.GL	631
05.7036.GL	652	05.7205.B1	628	05.7405.74	638	05.7444.GL	641	05.7615.B1A	626	05.8000.14	560
05.7040.74	654	05.7205.GL	628	05.7405.B1	638	05.7445.74	641	05.7615.GLA	626	05.8000.40	560
05.7040.B1	654	05.7206.74	628	05.7405.GL	638	05.7445.B1	641	05.7616.74A	626	05.8001.14	560
05.7040.GL	654	05.7206.B1	628	05.7406.74	634	05.7445.GL	641	05.7616.B1A	626	05.8001.40	560
05.7041.74	654	05.7206.GL	628	05.7406.B1	634	05.7446.74	631	05.7616.GLA	626	05.8002.14	560
05.7041.B1	654	05.7207.74	628	05.7406.GL	634	05.7446.B1	631	05.7617.74A	627	05.8002.40	560
05.7041.GL	654	05.7207.B1	628	05.7407.74	634	05.7446.GL	631	05.7617.B1A	627	05.8003.14	561
05.7100.74	616	05.7207.GL	628	05.7407.B1	634	05.7447.74	631	05.7617.GLA	627	05.8003.40	561
05.7100.B1	616	05.7210.74	629	05.7407.GL	634	05.7447.B1	631	05.7618.74A	627	05.8004.14	561
05.7100.GL	616	05.7210.B1	629	05.7408.74	634	05.7447.GL	631	05.7618.B1A	627	05.8004.40	561
05.7101.74	616	05.7210.GL	629	05.7408.B1	634	05.7450.74	598	05.7618.GLA	627	05.8005.14	561
05.7101.B1	616	05.7211.74	629	05.7408.GL	634	05.7450.B1	598	05.7620.74A	624	05.8005.40	561
05.7101.GL	616	05.7211.B1	629	05.7409.74	634	05.7450.GL	598	05.7620.B1A	624	05.8006.14	562
05.7102.74	616	05.7211.GL	629	05.7409.B1	634	05.7451.74	598	05.7620.GLA	624	05.8006.40	562
05.7102.B1	616	05.7212.74	629	05.7409.GL	634	05.7451.B1	598	05.7621.74A	624	05.8007.14	562
05.7102.GL	616	05.7212.B1	629	05.7410.74	598	05.7451.GL	598	05.7621.B1A	624	05.8007.40	562
05.7105.74	616	05.7212.GL	629	05.7410.B1	598	05.7452.74	598	05.7621.GLA	624	05.8008.14	562
05.7105.B1	616	05.7215.74	629	05.7410.GL	598	05.7452.B1	598	05.7622.74A	625	05.8008.40	562
05.7105.GL	616	05.7215.B1	629	05.7411.74	598	05.7452.GL	598	05.7622.B1A	625	05.8010.14	560
05.7106.74	616	05.7215.GL	629	05.7411.B1	598	05.7453.74	598	05.7622.GLA	625	05.8010.40	560
05.7106.B1	616	05.7216.74	629	05.7411.GL	598	05.7453.B1	598	05.7623.74A	625	05.8011.14	560
05.7106.GL	616	05.7216.B1	629	05.7412.74	601	05.7453.GL	598	05.7623.B1A	625	05.8011.40	560
05.7107.74	616	05.7216.GL	629	05.7412.B1	601	05.7454.74	601	05.7623.GLA	625	05.8012.14	560
05.7107.B1	616	05.7217.74	629	05.7412.GL	601	05.7454.B1	601	05.7625.74A	624	05.8012.40	560
05.7107.GL	616	05.7217.B1	629	05.7413.74	601	05.7454.GL	601	05.7625.B1A	624	05.8013.14	561
05.7110.74	618	05.7217.GL	629	05.7413.B1	601	05.7455.74	601	05.7625.GLA	624	05.8013.40	561
05.7110.B1	618	05.7220.74	628	05.7413.GL	601	05.7455.B1	601	05.7626.74A	624	05.8014.14	561
05.7110.GL	618	05.7220.B1	628	05.7414.74	605	05.7455.GL	601	05.7626.B1A	624	05.8014.40	561
05.7111.74	618	05.7220.GL	628	05.7414.B1	605	05.7456.74	601	05.7626.GLA	624	05.8015.14	561
05.7111.B1	618	05.7222.74	628	05.7414.GL	605	05.7456.B1	601	05.7627.74A	625	05.8015.40	561
05.7111.GL	618	05.7222.B1	628	05.7415.74	605	05.7456.GL	601	05.7627.B1A	625	05.8016.14	562
05.7112.74	618	05.7222.GL	628	05.7415.B1	605	05.7457.74	601	05.7627.GLA	625	05.8016.40	562
05.7112.B1	618	05.7223.74	628	05.7415.GL	605	05.7457.B1	601	05.7628.74A	625	05.8017.14	562
05.7112.GL	618	05.7223.B1	628	05.7416.74	608	05.7457.GL	601	05.7628.B1A	625	05.8017.40	562
05.7115.74	618	05.7223.GL	628	05.7416.B1	608	05.7458.74	605	05.7628.GLA	625	05.8018.14	562
05.7115.B1	618	05.7224.74	628	05.7416.GL	608	05.7458.B1	605	05.7630.74A	626	05.8018.40	562
05.7115.GL	618	05.7224.B1	628	05.7417.74	608	05.7458.GL	605	05.7630.B1A	626	05.8020.14	563
05.7116.74	618	05.7224.GL	628	05.7417.B1	608	05.7459.74	605	05.7630.GLA	626	05.8020.40	563
05.7116.B1	618	05.7225.74	628	05.7417.GL	608	05.7459.B1	605	05.7631.74A	626	05.8021.14	563
05.7116.GL	618	05.7225.B1	628	05.7420.74	611	05.7459.GL	605	05.7631.B1A	626	05.8021.40	563
05.7117.74	618	05.7225.GL	628	05.7420.B1	611	05.7460.74	605	05.7631.GLA	626	05.8022.14	563
05.7117.B1	618	05.7226.74	628	05.7420.GL	611	05.7460.B1	605	05.7632.74A	627	05.8022.40	563
05.7117.GL	618	05.7226.B1	628	05.7421.74	611	05.7460.GL	605	05.7632.B1A	627	05.8023.14	564
05.7120.74	620	05.7226.GL	628	05.7421.B1	611	05.7461.74	605	05.7632.GLA	627	05.8023.40	564
05.7120.B1	620	05.7300.74	595	05.7421.GL	611	05.7461.B1	605	05.7633.74A	627	05.8024.14	564
05.7120.GL	620	05.7300.B1	595	05.7422.74	613	05.7461.GL	605	05.7633.B1A	627	05.8024.40	564
05.7121.74	620	05.7300.GL	595	05.7422.B1	613	05.7462.74	608	05.7633.GLA	627	05.8025.14	564
05.7121.B1	620	05.7301.74	595	05.7422.GL	613	05.7462.B1	608	05.7635.74A	626	05.8025.40	564
05.7121.GL	620	05.7301.B1	595	05.7423.74	613	05.7462.GL	608	05.7635.B1A	626	05.8026.14	565
05.7130.74	617	05.7301.GL	595	05.7423.B1	613	05.7463.74	608	05.7635.GLA	626	05.8026.40	565
05.7130.B1	617	05.7302.74	595	05.7423.GL	613	05.7463.B1	608	05.7636.74A	626	05.8027.14	565
05.7130.GL	617	05.7302.B1	595	05.7430.74	631	05.7463.GL	608	05.7636.B1A	626	05.8027.40	565
05.7131.74	617	05.7302.GL	595	05.7430.B1	631	05.7464.74	608	05.7636.GLA	626	05.8028.14	565
05.7131.B1	617	05.7305.74	595	05.7430.GL	631	05.7464.B1	608	05.7637.74A	627	05.8028.40	565
05.7131.GL	617	05.7305.B1	595	05.7431.74	631	05.7464.GL	608	05.7637.B1A	627	05.8030.14	563
05.7135.74	619	05.7305.GL	595	05.7431.B1	631	05.7465.74	608	05.7637.GLA	627	05.8030.40	563
05.7135.B1	619	05.7306.74	595	05.7431.GL	631	05.7465.B1	608	05.7638.74A	627	05.8031.14	563
05.7135.GL	619	05.7306.B1	595	05.7432.74	634	05.7465.GL	608	05.7638.B1A	627	05.8031.40	563
05.7136.74	619	05.7306.GL	595	05.7432.B1	634	05.7600.74A	624	05.7638.GLA	627	05.8032.14	563
05.7136.B1	619	05.7307.74	595	05.7432.GL	634	05.7600.B1A	624	05.7700.74	630	05.8032.40	563
05.7136.GL	619	05.7307.B1	595	05.7433.74	634	05.7600.GLA	624	05.7700.B1	630	05.8033.14	564
05.7140.74	620	05.7307.GL	595	05.7433.B1	634	05.7601.74A	624	05.7700.GL	630	05.8033.40	564
05.7140.B1	620	05.7310.74	596	05.7433.GL	634	05.7601.B1A	624	05.7701.74	630	05.8034.14	564
05.7140.GL	620	05.7310.B1	596	05.7434.74	644	05.7601.GLA	624	05.7701.B1	630	05.8034.40	564
05.7141.74	620	05.7310.GL	596	05.7434.B1	644	05.7602.74A	625	05.7701.GL	630	05.8035.14	564
05.7141.B1	620	05.7311.74	596	05.7434.GL	644	05.7602.B1A	625	05.7702.74	630	05.8035.40	564
05.7141.GL	620	05.7311.B1	596	05.7435.74	644	05.7602.GLA	625	05.7702.B1	630	05.8036.14	565
05.7150.74	621	05.7311.GL	596	05.7435.B1	644	05.7603.74A	625	05.7702.GL	630	05.8036.40	565
05.7150.B1	621	05.7312.74	596	05.7435.GL	644	05.7603.B1A	625	05.7705.74	630	05.8037.14	565
05.7150.GL	621	05.7312.B1	596	05.7436.74	646	05.7603.GLA	625	05.7705.B1	630	05.8037.40	565
05.7151.74	621	05.7312.GL	596	05.7436.B1	646	05.7605.74A	624	05.7705.GL	630	05.8038.14	565
05.7151.B1	621	05.7315.74	596	05.7436.GL	646	05.7605.B1A	624	05.7706.74	630	05.8038.40	565
05.7151.GL	621	05.7315.B1	596	05.7437.74	646	05.7605.GLA	624	05.7706.B1	630	05.8100.14	568
05.7152.74	621	05.7315.GL	596	05.7437.B1	646	05.7606.74A	624	05.7706.GL	630	05.8100.40	568
05.7152.B1	621	05.7316.74	596	05.7437.GL	646	05.7606.B1A	624	05.7707.74	630	05.8101.14	568
05.7152.GL	621	05.7316.B1	596	05.7438.74	641	05.7606.GLA	624	05.7707.B1	630	05.8101.40	568
05.7155.74	621	05.7316.GL	596	05.7438.B1	641	05.7607.74A	625	05.7707.GL	630	05.8102.14	568
05.7155.B1	621	05.7317.74	596	05.7438.GL	641	05.7607.B1A	625	05.7710.74	631	05.8102.40	568

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.8103.14	568	05.8202.40	569	05.8307.40.1V	580	05.8410.ES	422	05.8501.14	424	05.8600.40	426
05.8103.40	568	05.8203.14	571	05.8307.40.CB	580	05.8411.14	422	05.8501.40	424	05.8601.14	426
05.8105.14	570	05.8203.40	571	05.8307.40.DA	580	05.8411.40	422	05.8503.14	424	05.8601.40	426
05.8105.40	570	05.8204.14	571	05.8307.40.NI	580	05.8411.ER	422	05.8503.40	424	05.8603.14	426
05.8106.14	570	05.8204.40	571	05.8311.14.1V	581	05.8411.ES	422	05.8504.14	424	05.8603.40	426
05.8106.40	570	05.8205.14	571	05.8311.14.CB	581	05.8412.14	423	05.8504.40	424	05.8604.14	426
05.8107.14	570	05.8205.40	571	05.8311.14.DA	581	05.8412.40	423	05.8505.14	424	05.8604.40	426
05.8107.40	570	05.8206.14	573	05.8311.14.NI	581	05.8412.ER	423	05.8505.40	424	05.8605.14	426
05.8108.14	570	05.8206.40	573	05.8311.40.1V	581	05.8412.ES	423	05.8506.14	424	05.8605.40	426
05.8108.40	570	05.8207.14	573	05.8311.40.CB	581	05.8415.14	422	05.8506.40	424	05.8606.14	426
05.8110.14	572	05.8207.40	573	05.8311.40.DA	581	05.8415.40	422	05.8508.14	424	05.8606.40	426
05.8110.40	572	05.8208.14	573	05.8311.40.NI	581	05.8415.ER	422	05.8508.40	424	05.8608.14	426
05.8111.14	572	05.8208.40	573	05.8312.14.1V	581	05.8415.ES	422	05.8509.14	424	05.8608.40	426
05.8111.40	572	05.8210.14	569	05.8312.14.CB	581	05.8416.14	422	05.8509.40	424	05.8609.14	426
05.8112.14	572	05.8210.40	569	05.8312.14.DA	581	05.8416.40	422	05.8510.14	424	05.8609.40	426
05.8112.40	572	05.8211.14	569	05.8312.14.NI	581	05.8416.ER	422	05.8510.40	424	05.8610.14	426
05.8113.14	572	05.8211.40	569	05.8312.40.1V	581	05.8416.ES	422	05.8511.14	424	05.8610.40	426
05.8113.40	572	05.8212.14	569	05.8312.40.CB	581	05.8417.14	423	05.8511.40	424	05.8611.14	426
05.8120.14	568	05.8212.40	569	05.8312.40.DA	581	05.8417.40	423	05.8513.14	424	05.8611.40	426
05.8120.40	568	05.8213.14	571	05.8312.40.NI	581	05.8417.ER	423	05.8513.40	424	05.8613.14	426
05.8121.14	568	05.8213.40	571	05.8341.14.1V	582	05.8417.ES	423	05.8514.14	424	05.8613.40	426
05.8121.40	568	05.8214.14	571	05.8341.14.CB	582	05.8420.14	422	05.8514.40	424	05.8614.14	426
05.8122.14	568	05.8214.40	571	05.8341.14.DA	582	05.8420.40	422	05.8520.14	424	05.8614.40	426
05.8122.40	568	05.8215.14	571	05.8341.14.NI	582	05.8420.ER	422	05.8520.40	424	05.8620.14	426
05.8123.14	568	05.8215.40	571	05.8341.40.1V	582	05.8420.ES	422	05.8521.14	424	05.8620.40	426
05.8123.40	568	05.8216.14	573	05.8341.40.CB	582	05.8421.14	422	05.8521.40	424	05.8621.14	426
05.8125.14	570	05.8216.40	573	05.8341.40.DA	582	05.8421.40	422	05.8523.14	424	05.8621.40	426
05.8125.40	570	05.8217.14	573	05.8341.40.NI	582	05.8421.ER	422	05.8523.40	424	05.8623.14	426
05.8126.14	570	05.8217.40	573	05.8342.14.1V	582	05.8421.ES	422	05.8524.14	424	05.8623.40	426
05.8126.40	570	05.8218.14	573	05.8342.14.CB	582	05.8422.14	423	05.8524.40	424	05.8624.14	426
05.8127.14	570	05.8218.40	573	05.8342.14.DA	582	05.8422.40	423	05.8525.14	424	05.8624.40	426
05.8127.40	570	05.8220.14	575	05.8342.14.NI	582	05.8422.ER	423	05.8525.40	424	05.8625.14	426
05.8128.14	570	05.8220.40	575	05.8342.40.1V	582	05.8422.ES	423	05.8526.14	424	05.8625.40	426
05.8128.40	570	05.8221.14	575	05.8342.40.CB	582	05.8425.14	422	05.8526.40	424	05.8626.14	426
05.8130.14	572	05.8221.40	575	05.8342.40.DA	582	05.8425.40	422	05.8528.14	424	05.8626.40	426
05.8130.40	572	05.8222.14	575	05.8342.40.NI	582	05.8425.ER	422	05.8528.40	424	05.8628.14	426
05.8131.14	572	05.8222.40	575	05.8346.14.1V	582	05.8425.ES	422	05.8529.14	424	05.8628.40	426
05.8131.40	572	05.8223.14	577	05.8346.14.CB	582	05.8426.14	422	05.8529.40	424	05.8629.14	426
05.8132.14	572	05.8223.40	577	05.8346.14.DA	582	05.8426.40	422	05.8530.14	424	05.8629.40	426
05.8132.40	572	05.8224.14	577	05.8346.14.NI	582	05.8426.ER	422	05.8530.40	424	05.8630.14	426
05.8133.14	572	05.8224.40	577	05.8346.40.1V	582	05.8426.ES	422	05.8531.14	424	05.8630.40	426
05.8133.40	572	05.8225.14	577	05.8346.40.CB	582	05.8427.14	423	05.8531.40	424	05.8631.14	426
05.8140.14	574	05.8225.40	577	05.8346.40.DA	582	05.8427.40	423	05.8533.14	424	05.8631.40	426
05.8140.40	574	05.8226.14	579	05.8346.40.NI	582	05.8427.ER	423	05.8533.40	424	05.8633.14	426
05.8141.14	574	05.8226.40	579	05.8347.14.1V	582	05.8427.ES	423	05.8534.14	424	05.8633.40	426
05.8141.40	574	05.8227.14	579	05.8347.14.CB	582	05.8450.14	433	05.8534.40	424	05.8634.14	426
05.8142.14	574	05.8227.40	579	05.8347.14.DA	582	05.8450.40	433	05.8540.14	425	05.8634.40	426
05.8142.40	574	05.8228.14	579	05.8347.14.NI	582	05.8451.14	433	05.8540.40	425	05.8640.14	427
05.8143.14	574	05.8228.40	579	05.8347.40.1V	582	05.8451.40	433	05.8541.14	425	05.8640.40	427
05.8143.40	574	05.8230.14	575	05.8347.40.CB	582	05.8453.14	433	05.8541.40	425	05.8641.14	427
05.8145.14	576	05.8230.40	575	05.8347.40.DA	582	05.8453.40	433	05.8543.14	425	05.8641.40	427
05.8145.40	576	05.8231.14	575	05.8347.40.NI	582	05.8454.14	433	05.8543.40	425	05.8643.14	427
05.8146.14	576	05.8231.40	575	05.8351.14.1V	583	05.8454.40	433	05.8544.14	425	05.8643.40	427
05.8146.40	576	05.8232.14	575	05.8351.14.CB	583	05.8455.14	433	05.8544.40	425	05.8644.14	427
05.8147.14	576	05.8232.40	575	05.8351.14.DA	583	05.8455.40	433	05.8545.14	425	05.8644.40	427
05.8147.40	576	05.8233.14	577	05.8351.14.NI	583	05.8456.14	433	05.8545.40	425	05.8645.14	427
05.8148.14	576	05.8233.40	577	05.8351.40.1V	583	05.8456.40	433	05.8546.14	425	05.8645.40	427
05.8148.40	576	05.8234.14	577	05.8351.40.CB	583	05.8458.14	433	05.8546.40	425	05.8646.14	427
05.8150.14	578	05.8234.40	577	05.8351.40.DA	583	05.8458.40	433	05.8548.14	425	05.8646.40	427
05.8150.40	578	05.8235.14	577	05.8351.40.NI	583	05.8459.14	433	05.8548.40	425	05.8648.14	427
05.8151.14	578	05.8235.40	577	05.8352.14.1V	583	05.8459.40	433	05.8549.14	425	05.8648.40	427
05.8151.40	578	05.8236.14	579	05.8352.14.CB	583	05.8460.14	433	05.8549.40	425	05.8649.14	427
05.8152.14	578	05.8236.40	579	05.8352.14.DA	583	05.8460.40	433	05.8550.14	425	05.8649.40	427
05.8152.40	578	05.8237.14	579	05.8352.14.NI	583	05.8461.14	433	05.8550.40	425	05.8650.14	427
05.8153.14	578	05.8237.40	579	05.8352.40.1V	583	05.8461.40	433	05.8551.14	425	05.8650.40	427
05.8153.40	578	05.8238.14	579	05.8352.40.CB	583	05.8463.14	433	05.8551.40	425	05.8651.14	427
05.8160.14	574	05.8238.40	579	05.8352.40.DA	583	05.8463.40	433	05.8553.14	425	05.8651.40	427
05.8160.40	574	05.8301.14.1V	580	05.8352.40.NI	583	05.8464.14	433	05.8553.40	425	05.8653.14	427
05.8161.14	574	05.8301.14.CB	580	05.8400.14	422	05.8464.40	433	05.8554.14	425	05.8653.40	427
05.8161.40	574	05.8301.14.DA	580	05.8400.40	422	05.8470.14	433	05.8554.40	425	05.8654.14	427
05.8162.14	574	05.8301.14.NI	580	05.8400.ER	422	05.8470.40	433	05.8560.14	425	05.8654.40	427
05.8162.40	574	05.8301.40.1V	580	05.8400.ES	422	05.8471.14	433	05.8560.40	425	05.8660.14	427
05.8163.14	574	05.8301.40.CB	580	05.8401.14	422	05.8471.40	433	05.8561.14	425	05.8660.40	427
05.8163.40	574	05.8301.40.DA	580	05.8401.40	422	05.8473.14	433	05.8561.40	425	05.8661.14	427
05.8165.14	576	05.8301.40.NI	580	05.8401.ER	422	05.8473.40	433	05.8563.14	425	05.8661.40	427
05.8165.40	576	05.8302.14.1V	580	05.8401.ES	422	05.8474.14	433	05.8563.40	425	05.8663.14	427
05.8166.14	576	05.8302.14.CB	580	05.8402.14	423	05.8474.40	433	05.8564.14	425	05.8663.40	427
05.8166.40	576	05.8302.14.DA	580	05.8402.40	423	05.8475.14	433	05.8564.40	425	05.8664.14	427
05.8167.14	576	05.8302.14.NI	580	05.8402.ER	423	05.8475.40	433	05.8565.14	425	05.8664.40	427
05.8167.40	576	05.8302.40.1V	580	05.8402.ES	423	05.8476.14	433	05.8565.40	425	05.8665.14	427
05.8168.14	576	05.8302.40.CB	580	05.8405.14	422	05.8476.40	433	05.8566.14	425	05.8665.40	427
05.8168.40	576	05.8302.40.DA	580	05.8405.40	422	05.8478.14	433	05.8566.40	425	05.8666.14	427
05.8170.14	578	05.8302.40.NI	580	05.8405.ER	422	05.8478.40	433	05.8568.14	425	05.8666.40	427
05.8170.40	578	05.8306.14.1V	580	05.8405.ES	422	05.8479.14	433	05.8568.40	425	05.8668.14	427
05.8171.14	578	05.8306.14.CB	580	05.8406.14	422	05.8479.40	433	05.8569.14	425	05.8668.40	427
05.8171.40	578	05.8306.14.DA	580	05.8406.40	422	05.8480.14	433	05.8569.40	425	05.8669.14	427
05.8172.14	578	05.8306.14.NI	580	05.8406.ER	422	05.8480.40	433	05.8570.14	425	05.8669.40	427
05.8172.40	578	05.8306.40.1V	580	05.8406.ES	422	05.8481.14	433	05.8570.40	425	05.8670.14	427
05.8173.14	578	05.8306.40.CB	580	05.8407.14	423	05.8481.40	433	05.8571.14	425	05.8670.40	427
05.8173.40	578	05.8306.40.DA	580	05.8407.40	423	05.8483.14	433	05.8571.40	425	05.8671.14	427
05.8200.14	569	05.8306.40.NI	580	05.8407.ER	423	05.8483.40	433	05.8573.14	425	05.8671.40	427
05.8200.40	569	05.8307.14.1V	580	05.8407.ES	423	05.8484.14	433	05.8573.40	425	05.8673.14	427
05.8201.14	569	05.8307.14.CB	580	05.8410.14	422	05.8484.40	433	05.8574.14	425	05.8673.40	427
05.8201.40	569	05.8307.14.DA	580	05.8410.40	422	05.8500.14	424	05.8574.40	425	05.8674.14	427
05.8202.14	569	05.8307.14.NI	580	05.8410.ER	422	05.8500.40	424	05.8600.14	426	05.8674.40	427

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.8700.14	428	05.8774.40	429	05.8874.14	431	05.9002.ESADA	275	05.9006.ESACB	274	05.9030.ES.1V	276
05.8700.40	428	05.8800.14	430	05.8874.40	431	05.9002.ES.CB	97	05.9006.ESADA	274	05.9030.ES.CB	98
05.8701.14	428	05.8800.40	430	05.9000.14	96	05.9002.ES.DA	97	05.9006.ES.CB	96	05.9030.ES.CB	276
05.8701.40	428	05.8801.14	430	05.9000.14.1V	96	05.9003.14	97	05.9006.ES.DA	96	05.9030.ES.DA	98
05.8703.14	428	05.8801.40	430	05.9000.14A	274	05.9003.14.1V	97	05.9007.14	97	05.9030.ES.DA	276
05.8703.40	428	05.8803.14	430	05.9000.14A1V	274	05.9003.14A	275	05.9007.14.1V	97	05.9031.14	98
05.8704.14	428	05.8803.40	430	05.9000.14ACB	274	05.9003.14A1V	275	05.9007.14A	275	05.9031.14	276
05.8704.40	428	05.8804.14	430	05.9000.14ADA	274	05.9003.14ACB	275	05.9007.14A1V	275	05.9031.14.1V	98
05.8705.14	428	05.8804.40	430	05.9000.14.CB	96	05.9003.14ADA	275	05.9007.14ACB	275	05.9031.14.1V	276
05.8705.40	428	05.8805.14	430	05.9000.14.DA	96	05.9003.14.CB	97	05.9007.14ADA	275	05.9031.14.CB	98
05.8706.14	428	05.8805.40	430	05.9000.40	96	05.9003.14.DA	97	05.9007.14.CB	97	05.9031.14.CB	276
05.8706.40	428	05.8806.14	430	05.9000.40.1V	96	05.9003.40	97	05.9007.14.DA	97	05.9031.14.DA	98
05.8708.14	428	05.8806.40	430	05.9000.40A	274	05.9003.40.1V	97	05.9007.40	97	05.9031.14.DA	276
05.8708.40	428	05.8808.14	430	05.9000.40A1V	274	05.9003.40A	275	05.9007.40.1V	97	05.9031.40	98
05.8709.14	428	05.8808.40	430	05.9000.40ACB	274	05.9003.40A1V	275	05.9007.40A	275	05.9031.40	276
05.8709.40	428	05.8809.14	430	05.9000.40ADA	274	05.9003.40ACB	275	05.9007.40A1V	275	05.9031.40.1V	98
05.8710.14	428	05.8809.40	430	05.9000.40.CB	96	05.9003.40ADA	275	05.9007.40ACB	275	05.9031.40.1V	276
05.8710.40	428	05.8810.14	430	05.9000.40.DA	96	05.9003.40.CB	97	05.9007.40ADA	275	05.9031.40.CB	98
05.8711.14	428	05.8810.40	430	05.9000.ER	96	05.9003.40.DA	97	05.9007.40.CB	97	05.9031.40.CB	276
05.8711.40	428	05.8811.14	430	05.9000.ER.1V	96	05.9003.ER	97	05.9007.40.DA	97	05.9031.40.DA	98
05.8713.14	428	05.8811.40	430	05.9000.ERA	274	05.9003.ER.1V	97	05.9007.ER	97	05.9031.40.DA	276
05.8713.40	428	05.8813.14	430	05.9000.ERA1V	274	05.9003.ERA	275	05.9007.ER.1V	97	05.9031.ER	98
05.8714.14	428	05.8813.40	430	05.9000.ERACB	274	05.9003.ERA1V	275	05.9007.ERA	275	05.9031.ER	276
05.8714.40	428	05.8814.14	430	05.9000.ERADA	274	05.9003.ERACB	275	05.9007.ERA1V	275	05.9031.ER.1V	98
05.8720.14	428	05.8814.40	430	05.9000.ER.CB	96	05.9003.ERADA	275	05.9007.ERACB	275	05.9031.ER.1V	276
05.8720.40	428	05.8820.14	430	05.9000.ER.DA	96	05.9003.ER.CB	97	05.9007.ERADA	275	05.9031.ER.CB	98
05.8721.14	428	05.8820.40	430	05.9000.ES	96	05.9003.ER.DA	97	05.9007.ER.CB	97	05.9031.ER.CB	276
05.8721.40	428	05.8821.14	430	05.9000.ES.1V	96	05.9003.ES	97	05.9007.ER.DA	97	05.9031.ER.DA	98
05.8723.14	428	05.8821.40	430	05.9000.ESA	274	05.9003.ES.1V	97	05.9007.ES	97	05.9031.ER.DA	276
05.8723.40	428	05.8823.14	430	05.9000.ESA1V	274	05.9003.ESA	275	05.9007.ES.1V	97	05.9031.ES	98
05.8724.14	428	05.8823.40	430	05.9000.ESACB	274	05.9003.ESA1V	275	05.9007.ESA	275	05.9031.ES	276
05.8724.40	428	05.8824.14	430	05.9000.ESADA	274	05.9003.ESACB	275	05.9007.ESA1V	275	05.9031.ES.1V	98
05.8725.14	428	05.8824.40	430	05.9000.ES.CB	96	05.9003.ESADA	275	05.9007.ESACB	275	05.9031.ES.1V	276
05.8725.40	428	05.8825.14	430	05.9000.ES.DA	96	05.9003.ES.CB	97	05.9007.ESADA	275	05.9031.ES.CB	98
05.8726.14	428	05.8825.40	430	05.9001.14	96	05.9003.ES.DA	97	05.9007.ES.CB	97	05.9031.ES.CB	276
05.8726.40	428	05.8826.14	430	05.9001.14.1V	96	05.9005.14	96	05.9007.ES.DA	97	05.9031.ES.DA	98
05.8728.14	428	05.8826.40	430	05.9001.14A	274	05.9005.14.1V	96	05.9008.14	97	05.9031.ES.DA	276
05.8728.40	428	05.8828.14	430	05.9001.14A1V	274	05.9005.14A	274	05.9008.14.1V	97	05.9032.14	99
05.8729.14	428	05.8828.40	430	05.9001.14ACB	274	05.9005.14A1V	274	05.9008.14A	275	05.9032.14	277
05.8729.40	428	05.8829.14	430	05.9001.14ADA	274	05.9005.14ACB	274	05.9008.14A1V	275	05.9032.14.1V	99
05.8730.14	428	05.8829.40	430	05.9001.14.CB	96	05.9005.14ADA	274	05.9008.14ACB	275	05.9032.14.1V	277
05.8730.40	428	05.8830.14	430	05.9001.14.DA	96	05.9005.14.CB	96	05.9008.14ADA	275	05.9032.14.CB	99
05.8731.14	428	05.8830.40	430	05.9001.40	96	05.9005.14.DA	96	05.9008.14.CB	97	05.9032.14.CB	277
05.8731.40	428	05.8831.14	430	05.9001.40.1V	96	05.9005.40	96	05.9008.14.DA	97	05.9032.14.DA	99
05.8733.14	428	05.8831.40	430	05.9001.40A	274	05.9005.40.1V	96	05.9008.40	97	05.9032.14.DA	277
05.8733.40	428	05.8833.14	430	05.9001.40A1V	274	05.9005.40A	274	05.9008.40.1V	97	05.9032.40	99
05.8734.14	428	05.8833.40	430	05.9001.40ACB	274	05.9005.40A1V	274	05.9008.40A	275	05.9032.40	277
05.8734.40	428	05.8834.14	430	05.9001.40ADA	274	05.9005.40ACB	274	05.9008.40A1V	275	05.9032.40.1V	99
05.8740.14	429	05.8834.40	430	05.9001.40.CB	96	05.9005.40ADA	274	05.9008.40ACB	275	05.9032.40.1V	277
05.8740.40	429	05.8840.14	431	05.9001.40.DA	96	05.9005.40.CB	96	05.9008.40ADA	275	05.9032.40.CB	99
05.8741.14	429	05.8840.40	431	05.9001.ER	96	05.9005.40.DA	96	05.9008.40.CB	97	05.9032.40.CB	277
05.8741.40	429	05.8841.14	431	05.9001.ER.1V	96	05.9005.ER	96	05.9008.40.DA	97	05.9032.40.DA	99
05.8743.14	429	05.8841.40	431	05.9001.ERA	274	05.9005.ER.1V	96	05.9008.ER	97	05.9032.40.DA	277
05.8743.40	429	05.8843.14	431	05.9001.ERA1V	274	05.9005.ERA	274	05.9008.ER.1V	97	05.9032.ER	99
05.8744.14	429	05.8843.40	431	05.9001.ERACB	274	05.9005.ERA1V	274	05.9008.ERA	275	05.9032.ER	277
05.8744.40	429	05.8844.14	431	05.9001.ERADA	274	05.9005.ERACB	274	05.9008.ERA1V	275	05.9032.ER.1V	99
05.8745.14	429	05.8844.40	431	05.9001.ER.CB	96	05.9005.ERADA	274	05.9008.ERACB	275	05.9032.ER.1V	277
05.8745.40	429	05.8845.14	431	05.9001.ER.DA	96	05.9005.ER.CB	96	05.9008.ERADA	275	05.9032.ER.CB	99
05.8746.14	429	05.8845.40	431	05.9001.ES	96	05.9005.ER.DA	96	05.9008.ER.CB	97	05.9032.ER.CB	277
05.8746.40	429	05.8846.14	431	05.9001.ES.1V	96	05.9005.ES	96	05.9008.ER.DA	97	05.9032.ER.DA	99
05.8748.14	429	05.8846.40	431	05.9001.ESA	274	05.9005.ES.1V	96	05.9008.ES	97	05.9032.ER.DA	277
05.8748.40	429	05.8848.14	431	05.9001.ESA1V	274	05.9005.ESA	274	05.9008.ES.1V	97	05.9032.ES	99
05.8749.14	429	05.8848.40	431	05.9001.ESACB	274	05.9005.ESA1V	274	05.9008.ESA	275	05.9032.ES	277
05.8749.40	429	05.8849.14	431	05.9001.ESADA	274	05.9005.ESACB	274	05.9008.ESA1V	275	05.9032.ES.1V	99
05.8750.14	429	05.8849.40	431	05.9001.ES.CB	96	05.9005.ESADA	274	05.9008.ESACB	275	05.9032.ES.1V	277
05.8750.40	429	05.8850.14	431	05.9001.ES.DA	96	05.9005.ES.CB	96	05.9008.ESADA	275	05.9032.ES.CB	99
05.8751.14	429	05.8850.40	431	05.9002.14	97	05.9005.ES.DA	96	05.9008.ES.CB	97	05.9032.ES.CB	277
05.8751.40	429	05.8851.14	431	05.9002.14.1V	97	05.9006.14	96	05.9008.ES.DA	97	05.9032.ES.DA	99
05.8753.14	429	05.8851.40	431	05.9002.14A	275	05.9006.14.1V	96	05.9030.14	98	05.9032.ES.DA	277
05.8753.40	429	05.8853.14	431	05.9002.14A1V	275	05.9006.14A	274	05.9030.14	276	05.9035.14	98
05.8754.14	429	05.8853.40	431	05.9002.14ACB	275	05.9006.14A1V	274	05.9030.14.1V	98	05.9035.14	276
05.8754.40	429	05.8854.14	431	05.9002.14ADA	275	05.9006.14ACB	274	05.9030.14.1V	276	05.9035.14.1V	98
05.8760.14	429	05.8854.40	431	05.9002.14.CB	97	05.9006.14ADA	274	05.9030.14.CB	98	05.9035.14.1V	276
05.8760.40	429	05.8860.14	431	05.9002.14.DA	97	05.9006.14.CB	96	05.9030.14.CB	276	05.9035.14.CB	98
05.8761.14	429	05.8860.40	431	05.9002.40	97	05.9006.14.DA	96	05.9030.14.DA	98	05.9035.14.CB	276
05.8761.40	429	05.8861.14	431	05.9002.40.1V	97	05.9006.40	96	05.9030.14.DA	276	05.9035.14.DA	98
05.8763.14	429	05.8861.40	431	05.9002.40A	275	05.9006.40.1V	96	05.9030.40	98	05.9035.14.DA	276
05.8763.40	429	05.8863.14	431	05.9002.40A1V	275	05.9006.40A	274	05.9030.40	276	05.9035.40	98
05.8764.14	429	05.8863.40	431	05.9002.40ACB	275	05.9006.40A1V	274	05.9030.40.1V	98	05.9035.40	276
05.8764.40	429	05.8864.14	431	05.9002.40ADA	275	05.9006.40ACB	274	05.9030.40.1V	276	05.9035.40.1V	98
05.8765.14	429	05.8864.40	431	05.9002.40.CB	97	05.9006.40ADA	274	05.9030.40.CB	98	05.9035.40.1V	276
05.8765.40	429	05.8865.14	431	05.9002.40.DA	97	05.9006.40.CB	96	05.9030.40.CB	276	05.9035.40.CB	98
05.8766.14	429	05.8865.40	431	05.9002.ER	97	05.9006.40.DA	96	05.9030.40.DA	98	05.9035.40.CB	276
05.8766.40	429	05.8866.14	431	05.9002.ER.1V	97	05.9006.ER	96	05.9030.40.DA	276	05.9035.40.DA	98
05.8768.14	429	05.8866.40	431	05.9002.ERA	275	05.9006.ER.1V	96	05.9030.ER	98	05.9035.40.DA	276
05.8768.40	429	05.8868.14	431	05.9002.ERA1V	275	05.9006.ERA	274	05.9030.ER	276	05.9035.ER	98
05.8769.14	429	05.8868.40	431	05.9002.ERACB	275	05.9006.ERA1V	274	05.9030.ER.1V	98	05.9035.ER	276
05.8769.40	429	05.8869.14	431	05.9002.ERADA	275	05.9006.ERACB	274	05.9030.ER.1V	276	05.9035.ER.1V	98
05.8770.14	429	05.8869.40	431	05.9002.ER.CB	97	05.9006.ERADA	274	05.9030.ER.CB	98	05.9035.ER.1V	276
05.8770.40	429	05.8870.14	431	05.9002.ER.DA	97	05.9006.ER.CB	96	05.9030.ER.CB	276	05.9035.ER.CB	98
05.8771.14	429	05.8870.40	431	05.9002.ES	97	05.9006.ER.DA	96	05.9030.ER.DA	98	05.9035.ER.CB	276
05.8771.40	429	05.8871.14	431	05.9002.ES.1V	97	05.9006.ES	96	05.9030.ER.DA	276	05.9035.ER.DA	98
05.8773.14	429	05.8871.40	431	05.9002.ESA	275	05.9006.ES.1V	96	05.9030.ES	98	05.9035.ER.DA	276
05.8773.40	429	05.8873.14	431	05.9002.ESA1V	275	05.9006.ESA	274	05.9030.ES	276	05.9035.ES	98
05.8774.14	429	05.8873.40	431	05.9002.ESACB	275	05.9006.ESA1V	274	05.9030.ES.1V	98	05.9035.ES	276

QUICK SEARCH OF PRODUCT

Ref.	Page
05.9035.ES.1V	98
05.9035.ES.1V	276
05.9035.ES.CB	98
05.9035.ES.CB	276
05.9035.ES.DA	98
05.9035.ES.DA	276
05.9036.14	98
05.9036.14	276
05.9036.14.1V	98
05.9036.14.1V	276
05.9036.14.CB	98
05.9036.14.CB	276
05.9036.14.DA	98
05.9036.14.DA	276
05.9036.40	98
05.9036.40	276
05.9036.40.1V	98
05.9036.40.1V	276
05.9036.40.CB	98
05.9036.40.CB	276
05.9036.40.DA	98
05.9036.40.DA	276
05.9036.ER	98
05.9036.ER	276
05.9036.ER.1V	98
05.9036.ER.1V	276
05.9036.ER.CB	98
05.9036.ER.CB	276
05.9036.ER.DA	98
05.9036.ER.DA	276
05.9036.ES	98
05.9036.ES	276
05.9036.ES.1V	98
05.9036.ES.1V	276
05.9036.ES.CB	98
05.9036.ES.CB	276
05.9036.ES.DA	98
05.9036.ES.DA	276
05.9037.14	99
05.9037.14	277
05.9037.14.1V	99
05.9037.14.1V	277
05.9037.14.CB	99
05.9037.14.CB	277
05.9037.14.DA	99
05.9037.14.DA	277
05.9037.40	99
05.9037.40	277
05.9037.40.1V	99
05.9037.40.1V	277
05.9037.40.CB	99
05.9037.40.CB	277
05.9037.40.DA	99
05.9037.40.DA	277
05.9037.ER	99
05.9037.ER	277
05.9037.ER.1V	99
05.9037.ER.1V	277
05.9037.ER.CB	99
05.9037.ER.CB	277
05.9037.ER.DA	99
05.9037.ER.DA	277
05.9037.ES	99
05.9037.ES	277
05.9037.ES.1V	99
05.9037.ES.1V	277
05.9037.ES.CB	99
05.9037.ES.CB	277
05.9037.ES.DA	99
05.9037.ES.DA	277
05.9060.14	100
05.9060.14	278
05.9060.14.1V	100
05.9060.14.1V	278
05.9060.14.CB	100
05.9060.14.CB	278
05.9060.14.DA	100
05.9060.14.DA	278
05.9060.40	100
05.9060.40	278
05.9060.40.1V	100
05.9060.40.1V	278
05.9060.40.CB	100
05.9060.40.CB	278
05.9060.40.DA	100
05.9060.40.DA	278
05.9060.ER	100
05.9060.ER	278
05.9060.ER.1V	100
05.9060.ER.1V	278
05.9060.ER.CB	100
05.9060.ER.CB	278
05.9060.ER.DA	100
05.9060.ER.DA	278
05.9060.ES	100
05.9060.ES	278
05.9060.ES.1V	100
05.9060.ES.1V	278
05.9060.ES.CB	100
05.9060.ES.CB	278
05.9060.ES.DA	100
05.9060.ES.DA	278
05.9061.14	100
05.9061.14	278
05.9061.14.1V	100
05.9061.14.1V	278
05.9061.14.CB	100
05.9061.14.CB	278
05.9061.14.DA	100
05.9061.14.DA	278
05.9061.40	100
05.9061.40	278
05.9061.40.1V	100
05.9061.40.1V	278
05.9061.40.CB	100
05.9061.40.CB	278
05.9061.40.DA	100
05.9061.40.DA	278
05.9061.ER	100
05.9061.ER	278
05.9061.ER.1V	100
05.9061.ER.1V	278
05.9061.ER.CB	100
05.9061.ER.CB	278
05.9061.ER.DA	100
05.9061.ER.DA	278
05.9061.ES	100
05.9061.ES	278
05.9061.ES.1V	100
05.9061.ES.1V	278
05.9061.ES.CB	100
05.9061.ES.CB	278
05.9061.ES.DA	100
05.9061.ES.DA	278
05.9062.14	101
05.9062.14	279
05.9062.14.1V	101
05.9062.14.1V	279
05.9062.14.CB	101
05.9062.14.CB	279
05.9062.14.DA	101
05.9062.14.DA	279
05.9062.40	101
05.9062.40	279
05.9062.40.1V	101
05.9062.40.1V	279
05.9062.40.CB	101
05.9062.40.CB	279
05.9062.40.DA	101
05.9062.40.DA	279
05.9062.ER	101
05.9062.ER	279
05.9062.ER.1V	101
05.9062.ER.1V	279
05.9062.ER.CB	101
05.9062.ER.CB	279
05.9062.ER.DA	101
05.9062.ER.DA	279
05.9062.ES	101
05.9062.ES	279
05.9062.ES.1V	101
05.9062.ES.1V	279
05.9062.ES.CB	101
05.9062.ES.CB	279
05.9062.ES.DA	101
05.9062.ES.DA	279
05.9063.14	101
05.9063.14	279
05.9063.14.1V	101
05.9063.14.1V	279
05.9063.14.CB	101
05.9063.14.CB	279
05.9063.14.DA	101
05.9063.14.DA	279
05.9063.40	101
05.9063.40	279
05.9063.40.1V	101
05.9063.40.1V	279
05.9063.40.CB	101
05.9063.40.CB	279
05.9063.40.DA	101
05.9063.40.DA	279
05.9063.ER	101
05.9063.ER	279
05.9063.ER.1V	101
05.9063.ER.1V	279
05.9063.ER.CB	101
05.9063.ER.CB	279
05.9063.ER.DA	101
05.9063.ER.DA	279
05.9063.ES	101
05.9063.ES	279
05.9063.ES.1V	101
05.9063.ES.1V	279
05.9063.ES.CB	101
05.9063.ES.CB	279
05.9063.ES.DA	101
05.9063.ES.DA	279
05.9064.14	102
05.9064.14	280
05.9064.14.1V	102
05.9064.14.1V	280
05.9064.14.CB	102
05.9064.14.CB	280
05.9064.14.DA	102
05.9064.14.DA	280
05.9064.40	102
05.9064.40	280
05.9064.40.1V	102
05.9064.40.1V	280
05.9064.40.CB	102
05.9064.40.CB	280
05.9064.40.DA	102
05.9064.40.DA	280
05.9064.ER	102
05.9064.ER	280
05.9064.ER.1V	102
05.9064.ER.1V	280
05.9064.ER.CB	102
05.9064.ER.CB	280
05.9064.ER.DA	102
05.9064.ER.DA	280
05.9064.ES	102
05.9064.ES	280
05.9064.ES.1V	102
05.9064.ES.1V	280
05.9064.ES.CB	102
05.9064.ES.CB	280
05.9064.ES.DA	102
05.9064.ES.DA	280
05.9065.14	100
05.9065.14	278
05.9065.14.1V	100
05.9065.14.1V	278
05.9065.14.CB	100
05.9065.14.CB	278
05.9065.14.DA	100
05.9065.14.DA	278
05.9065.40	100
05.9065.40	278
05.9065.40.1V	100
05.9065.40.1V	278
05.9065.40.CB	100
05.9065.40.CB	278
05.9065.40.DA	100
05.9065.40.DA	278
05.9065.ER	100
05.9065.ER	278
05.9065.ER.1V	100
05.9065.ER.1V	278
05.9065.ER.CB	100
05.9065.ER.CB	278
05.9065.ER.DA	100
05.9065.ER.DA	278
05.9065.ES	100
05.9065.ES	278
05.9065.ES.1V	100
05.9065.ES.1V	278
05.9065.ES.CB	100
05.9065.ES.CB	278
05.9065.ES.DA	100
05.9065.ES.DA	278
05.9066.14	100
05.9066.14	278
05.9066.14.1V	100
05.9066.14.1V	278
05.9066.14.CB	100
05.9066.14.CB	278
05.9066.14.DA	100
05.9066.14.DA	278
05.9066.40	100
05.9066.40	278
05.9066.40.1V	100
05.9066.40.1V	278
05.9066.40.CB	100
05.9066.40.CB	278
05.9066.40.DA	100
05.9066.40.DA	278
05.9066.ER	100
05.9066.ER	278
05.9066.ER.1V	100
05.9066.ER.1V	278
05.9066.ER.CB	100
05.9066.ER.CB	278
05.9066.ER.DA	100
05.9066.ER.DA	278
05.9066.ES	100
05.9066.ES	278
05.9066.ES.1V	100
05.9066.ES.1V	278
05.9066.ES.CB	100
05.9066.ES.CB	278
05.9066.ES.DA	100
05.9066.ES.DA	278
05.9067.14	101
05.9067.14	279
05.9067.14.1V	101
05.9067.14.1V	279
05.9067.14.CB	101
05.9067.14.CB	279
05.9067.14.DA	101
05.9067.14.DA	279
05.9067.40	101
05.9067.40	279
05.9067.40.1V	101
05.9067.40.1V	279
05.9067.40.CB	101
05.9067.40.CB	279
05.9067.40.DA	101
05.9067.40.DA	279
05.9067.ER	101
05.9067.ER	279
05.9067.ER.1V	101
05.9067.ER.1V	279
05.9067.ER.CB	101
05.9067.ER.CB	279
05.9067.ER.DA	101
05.9067.ER.DA	279
05.9067.ES	101
05.9067.ES	279
05.9067.ES.1V	101
05.9067.ES.1V	279
05.9067.ES.CB	101
05.9067.ES.CB	279
05.9067.ES.DA	101
05.9067.ES.DA	279
05.9068.14	101
05.9068.14	279
05.9068.14.1V	101
05.9068.14.1V	279
05.9068.14.CB	101
05.9068.14.CB	279
05.9068.14.DA	101
05.9068.14.DA	279
05.9068.40	101
05.9068.40	279
05.9068.40.1V	101
05.9068.40.1V	279
05.9068.40.CB	101
05.9068.40.CB	279
05.9068.40.DA	101
05.9068.40.DA	279
05.9068.ER	101
05.9068.ER	279
05.9068.ER.1V	101
05.9068.ER.1V	279
05.9068.ER.CB	101
05.9068.ER.CB	279
05.9068.ER.DA	101
05.9068.ER.DA	279
05.9068.ES	101
05.9068.ES	279
05.9068.ES.1V	101
05.9068.ES.1V	279
05.9068.ES.CB	101
05.9068.ES.CB	279
05.9068.ES.DA	101
05.9068.ES.DA	279
05.9069.14	102
05.9069.14	280
05.9069.14.1V	102
05.9069.14.1V	280
05.9069.14.CB	102
05.9069.14.CB	280
05.9069.14.DA	102
05.9069.14.DA	280
05.9069.40	102
05.9069.40	280
05.9069.40.1V	102
05.9069.40.1V	280
05.9069.40.CB	102
05.9069.40.CB	280
05.9069.40.DA	102
05.9069.40.DA	280
05.9069.ER	102
05.9069.ER	280
05.9069.ER.1V	102
05.9069.ER.1V	280
05.9069.ER.CB	102
05.9069.ER.CB	280
05.9069.ER.DA	102
05.9069.ER.DA	280
05.9069.ES	102
05.9069.ES	280
05.9069.ES.1V	102
05.9069.ES.1V	280
05.9069.ES.CB	102
05.9069.ES.CB	280
05.9069.ES.DA	102
05.9069.ES.DA	280
05.9100.14A	224
05.9100.14A1V	224
05.9100.14ACB	224
05.9100.14ADA	224
05.9100.40A	224
05.9100.40A1V	224
05.9100.40ACB	224
05.9100.40ADA	224
05.9100.ERA	224
05.9100.ERA1V	224
05.9100.ERACB	224
05.9100.ERADA	224
05.9100.ESA	224
05.9100.ESA1V	224
05.9100.ESACB	224
05.9100.ESADA	224
05.9101.14A	224
05.9101.14A1V	224
05.9101.14ACB	224
05.9101.14ADA	224
05.9101.40A	224
05.9101.40A1V	224
05.9101.40ACB	224
05.9101.40ADA	224
05.9101.ERA	224
05.9101.ERA1V	224
05.9101.ERACB	224
05.9101.ERADA	224
05.9101.ESA	224
05.9101.ESA1V	224
05.9101.ESACB	224
05.9101.ESADA	224
05.9102.14A	225
05.9102.14A1V	225
05.9102.14ACB	225
05.9102.14ADA	225
05.9102.40A	225
05.9102.40A1V	225
05.9102.40ACB	225
05.9102.40ADA	225
05.9102.ERA	225
05.9102.ERA1V	225
05.9102.ERACB	225
05.9102.ERADA	225
05.9102.ESA	225
05.9102.ESA1V	225
05.9102.ESACB	225
05.9102.ESADA	225
05.9103.14A	225
05.9103.14A1V	225
05.9103.14ACB	225
05.9103.14ADA	225
05.9103.40A	225
05.9103.40A1V	225
05.9103.40ACB	225
05.9103.40ADA	225
05.9103.ERA	225
05.9103.ERA1V	225
05.9103.ERACB	225
05.9103.ERADA	225
05.9103.ESA	225
05.9103.ESA1V	225
05.9103.ESACB	225
05.9103.ESADA	225
05.9105.14A	224
05.9105.14A1V	224
05.9105.14ACB	224
05.9105.14ADA	224
05.9105.40A	224
05.9105.40A1V	224
05.9105.40ACB	224
05.9105.40ADA	224
05.9105.ERA	224
05.9105.ERA1V	224
05.9105.ERACB	224
05.9105.ERADA	224
05.9105.ESA	224
05.9105.ESA1V	224
05.9105.ESACB	224
05.9105.ESADA	224
05.9106.14A	224
05.9106.14A1V	224
05.9106.14ACB	224
05.9106.14ADA	224
05.9106.40A	224
05.9106.40A1V	224
05.9106.40ACB	224
05.9106.40ADA	224
05.9106.ERA	224
05.9106.ERA1V	224
05.9106.ERACB	224
05.9106.ERADA	224
05.9106.ESA	224
05.9106.ESA1V	224
05.9106.ESACB	224
05.9106.ESADA	224
05.9107.14A	225
05.9107.14A1V	225
05.9107.14ACB	225
05.9107.14ADA	225
05.9107.40A	225
05.9107.40A1V	225
05.9107.40ACB	225
05.9107.40ADA	225
05.9107.ERA	225
05.9107.ERA1V	225
05.9107.ERACB	225
05.9107.ERADA	225
05.9107.ESA	225
05.9107.ESA1V	225
05.9107.ESACB	225
05.9107.ESADA	225
05.9108.14A	225
05.9108.14A1V	225
05.9108.14ACB	225
05.9108.14ADA	225
05.9108.40A	225
05.9108.40A1V	225
05.9108.40ACB	225
05.9108.40ADA	225
05.9108.ERA	225
05.9108.ERA1V	225
05.9108.ERACB	225
05.9108.ERADA	225
05.9108.ESA	225
05.9108.ESA1V	225
05.9108.ESACB	225
05.9108.ESADA	225
05.9130.14	226
05.9130.14.1V	226
05.9130.14.CB	226
05.9130.14.DA	226
05.9130.40	226
05.9130.40.1V	226
05.9130.40.CB	226
05.9130.40.DA	226
05.9130.ER	226
05.9130.ER.1V	226
05.9130.ER.CB	226
05.9130.ER.DA	226
05.9130.ES	226
05.9130.ES.1V	226
05.9130.ES.CB	226
05.9130.ES.DA	226
05.9131.14	226
05.9131.14.1V	226
05.9131.14.CB	226
05.9131.14.DA	226
05.9131.40	226
05.9131.40.1V	226
05.9131.40.CB	226
05.9131.40.DA	226
05.9131.ER	226
05.9131.ER.1V	226
05.9131.ER.CB	226
05.9131.ER.DA	226
05.9131.ES	226
05.9131.ES.1V	226
05.9131.ES.CB	226
05.9131.ES.DA	226
05.9132.14	227
05.9132.14.1V	227
05.9132.14.CB	227
05.9132.14.DA	227
05.9132.40	227
05.9132.40.1V	227
05.9132.40.CB	227
05.9132.40.DA	227
05.9132.ER	227
05.9132.ER.1V	227
05.9132.ER.CB	227
05.9132.ER.DA	227
05.9132.ES	227
05.9132.ES.1V	227
05.9132.ES.CB	227
05.9132.ES.DA	227
05.9135.14	226
05.9135.14.1V	226
05.9135.14.CB	226
05.9135.14.DA	226

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
05.9135.40	226	05.9210.40ACB	698	05.9238.ERADA	701	05.9301.40A	528	05.9384.ERA	531	05.9527.14	540
05.9135.40.1V	226	05.9210.40ADA	698	05.9238.ES	701	05.9303.40A	528	05.9384.ESA	531	05.9527.40	540
05.9135.40.CB	226	05.9210.40AYU	698	05.9238.ESACB	701	05.9304.14A	528	05.9385.14A	531	05.9527.ER	540
05.9135.40.DA	226	05.9210.ER	698	05.9238.ESADA	701	05.9304.40A	528	05.9385.40A	531	05.9528.ES	540
05.9135.ER	226	05.9210.ERACB	698	05.9239.14	701	05.9304.ERA	528	05.9387.14A	531	05.9530.40	538
05.9135.ER.1V	226	05.9210.ERADA	698	05.9239.14ACB	701	05.9304.ESA	528	05.9387.40A	531	05.9531.40	538
05.9135.ER.CB	226	05.9210.ES	698	05.9239.14ADA	701	05.9305.14A	528	05.9387.ERA	531	05.9533.40	538
05.9135.ER.DA	226	05.9210.ESACB	698	05.9239.40	701	05.9305.40A	528	05.9388.ESA	531	05.9534.14	538
05.9135.ES	226	05.9210.ESADA	698	05.9239.40.78	701	05.9307.14A	528	05.9400.40A	528	05.9534.40	538
05.9135.ES.1V	226	05.9211.14	698	05.9239.40AC6	701	05.9307.40A	528	05.9401.40A	528	05.9534.ER	538
05.9135.ES.CB	226	05.9211.14ACB	698	05.9239.40ACB	701	05.9307.ERA	528	05.9403.40A	528	05.9534.ES	538
05.9135.ES.DA	226	05.9211.14ADA	698	05.9239.40ADA	701	05.9308.ESA	528	05.9404.14A	528	05.9535.14	538
05.9136.14	226	05.9211.40	698	05.9239.40AYU	701	05.9310.40A	529	05.9404.40A	528	05.9535.40	538
05.9136.14.1V	226	05.9211.40.78	698	05.9239.ER	701	05.9311.40A	529	05.9404.ERA	528	05.9537.14	538
05.9136.14.CB	226	05.9211.40AC6	698	05.9239.ERACB	701	05.9313.40A	529	05.9404.ESA	528	05.9537.40	538
05.9136.14.DA	226	05.9211.40ACB	698	05.9239.ERADA	701	05.9314.14A	529	05.9405.14A	528	05.9537.ER	538
05.9136.40	226	05.9211.40ADA	698	05.9239.ES	701	05.9314.40A	529	05.9405.40A	528	05.9538.ES	538
05.9136.40.1V	226	05.9211.40AYU	698	05.9239.ESACB	701	05.9314.ERA	529	05.9407.14A	528	05.9540.40	539
05.9136.40.CB	226	05.9211.ER	698	05.9239.ESADA	701	05.9314.ESA	529	05.9407.40A	528	05.9541.40	539
05.9136.40.DA	226	05.9211.ERACB	698	05.9240.14	700	05.9315.14A	529	05.9407.ERA	528	05.9543.40	539
05.9136.ER	226	05.9211.ERADA	698	05.9240.14ACB	700	05.9315.40A	529	05.9408.ESA	528	05.9544.14	539
05.9136.ER.1V	226	05.9211.ES	698	05.9240.14ADA	700	05.9317.14A	529	05.9410.40A	529	05.9544.40	539
05.9136.ER.CB	226	05.9211.ESACB	698	05.9240.40	700	05.9317.40A	529	05.9411.40A	529	05.9544.ER	539
05.9136.ER.DA	226	05.9211.ESADA	698	05.9240.40.78	700	05.9317.ERA	529	05.9413.40A	529	05.9544.ES	539
05.9136.ES	226	05.9212.14	699	05.9240.40AC6	700	05.9318.ESA	529	05.9414.14A	529	05.9545.14	539
05.9136.ES.1V	226	05.9212.14ACB	699	05.9240.40ACB	700	05.9320.40A	530	05.9414.40A	529	05.9545.40	539
05.9136.ES.CB	226	05.9212.14ADA	699	05.9240.40ADA	700	05.9321.40A	530	05.9414.ERA	529	05.9547.14	539
05.9136.ES.DA	226	05.9212.40	699	05.9240.40AYU	700	05.9323.40A	530	05.9414.ESA	529	05.9547.40	539
05.9137.14	227	05.9212.40.78	699	05.9240.ER	700	05.9324.14A	530	05.9415.14A	529	05.9547.ER	539
05.9137.14.1V	227	05.9212.40AC6	699	05.9240.ERACB	700	05.9324.40A	530	05.9415.40A	529	05.9548.ES	539
05.9137.14.CB	227	05.9212.40ACB	699	05.9240.ERADA	700	05.9324.ERA	530	05.9417.14A	529	05.9550.40	540
05.9137.14.DA	227	05.9212.40ADA	699	05.9240.ES	700	05.9324.ESA	530	05.9417.40A	529	05.9551.40	540
05.9137.40	227	05.9212.40AYU	699	05.9240.ESACB	700	05.9325.14A	530	05.9417.ERA	529	05.9553.40	540
05.9137.40.1V	227	05.9212.ER	699	05.9240.ESADA	700	05.9325.40A	530	05.9418.ESA	529	05.9554.14	540
05.9137.40.CB	227	05.9212.ERACB	699	05.9241.14	700	05.9327.14A	530	05.9420.40A	530	05.9554.40	540
05.9137.40.DA	227	05.9212.ERADA	699	05.9241.14ACB	700	05.9327.40A	530	05.9421.40A	530	05.9554.ER	540
05.9137.ER	227	05.9212.ES	699	05.9241.14ADA	700	05.9327.ERA	530	05.9423.40A	530	05.9554.ES	540
05.9137.ER.1V	227	05.9212.ESACB	699	05.9241.40	700	05.9328.ESA	530	05.9424.14A	530	05.9555.14	540
05.9137.ER.CB	227	05.9212.ESADA	699	05.9241.40.78	700	05.9330.40A	531	05.9424.40A	530	05.9555.40	540
05.9137.ER.DA	227	05.9235.14	700	05.9241.40AC6	700	05.9331.40A	531	05.9424.ERA	530	05.9557.14	540
05.9137.ES	227	05.9235.14ACB	700	05.9241.40ACB	700	05.9333.40A	531	05.9424.ESA	530	05.9557.40	540
05.9137.ES.1V	227	05.9235.14ADA	700	05.9241.40ADA	700	05.9334.14A	531	05.9425.14A	530	05.9557.ER	540
05.9137.ES.CB	227	05.9235.40	700	05.9241.40AYU	700	05.9334.40A	531	05.9425.40A	530	05.9558.ES	540
05.9137.ES.DA	227	05.9235.40.78	700	05.9241.ER	700	05.9334.ERA	531	05.9427.14A	530	05.9560.40	538
05.9205.14	698	05.9235.40AC6	700	05.9241.ERACB	700	05.9334.ESA	531	05.9427.40A	530	05.9561.40	538
05.9205.14ACB	698	05.9235.40ACB	700	05.9241.ERADA	700	05.9335.14A	531	05.9427.ERA	530	05.9563.40	538
05.9205.14ADA	698	05.9235.40ADA	700	05.9241.ES	700	05.9335.40A	531	05.9428.ESA	530	05.9564.14	538
05.9205.40	698	05.9235.40AYU	700	05.9241.ESACB	700	05.9337.14A	531	05.9430.40A	531	05.9564.40	538
05.9205.40.78	698	05.9235.ER	700	05.9241.ESADA	700	05.9337.40A	531	05.9431.40A	531	05.9564.ER	538
05.9205.40AC6	698	05.9235.ERACB	700	05.9242.14	701	05.9337.ERA	531	05.9433.40A	531	05.9564.ES	538
05.9205.40ACB	698	05.9235.ERADA	700	05.9242.14ACB	701	05.9338.ESA	531	05.9434.14A	531	05.9565.14	538
05.9205.40ADA	698	05.9235.ES	700	05.9242.14ADA	701	05.9350.40A	528	05.9434.40A	531	05.9565.40	538
05.9205.40AYU	698	05.9235.ESACB	700	05.9242.40	701	05.9351.40A	528	05.9434.ERA	531	05.9567.14	538
05.9205.ER	698	05.9235.ESADA	700	05.9242.40.78	701	05.9353.40A	528	05.9434.ESA	531	05.9567.40	538
05.9205.ERACB	698	05.9236.14	700	05.9242.40AC6	701	05.9354.14A	528	05.9435.14A	531	05.9567.ER	538
05.9205.ERADA	698	05.9236.14ACB	700	05.9242.40ACB	701	05.9354.40A	528	05.9435.40A	531	05.9568.ES	538
05.9205.ES	698	05.9236.14ADA	700	05.9242.40ADA	701	05.9354.ERA	528	05.9437.14A	531	05.9570.40	539
05.9205.ESACB	698	05.9236.40	700	05.9242.40AYU	701	05.9354.ESA	528	05.9437.40A	531	05.9571.40	539
05.9205.ESADA	698	05.9236.40.78	700	05.9242.ER	701	05.9355.14A	528	05.9437.ERA	531	05.9573.40	539
05.9206.14	698	05.9236.40AC6	700	05.9242.ERACB	701	05.9355.40A	528	05.9438.ESA	531	05.9574.14	539
05.9206.14ACB	698	05.9236.40ACB	700	05.9242.ERADA	701	05.9357.14A	528	05.9500.40	538	05.9574.40	539
05.9206.14ADA	698	05.9236.40ADA	700	05.9242.ES	701	05.9357.40A	528	05.9501.40	538	05.9574.ER	539
05.9206.40	698	05.9236.40AYU	700	05.9242.ESACB	701	05.9357.ERA	528	05.9503.40	538	05.9574.ES	539
05.9206.40.78	698	05.9236.ER	700	05.9242.ESADA	701	05.9358.ESA	528	05.9504.14	538	05.9575.14	539
05.9206.40AC6	698	05.9236.ERACB	700	05.9243.14	701	05.9360.40A	529	05.9504.40	538	05.9575.40	539
05.9206.40ACB	698	05.9236.ERADA	700	05.9243.14ACB	701	05.9361.40A	529	05.9504.ER	538	05.9577.14	539
05.9206.40ADA	698	05.9236.ES	700	05.9243.14ADA	701	05.9363.40A	529	05.9504.ES	538	05.9577.40	539
05.9206.40AYU	698	05.9236.ESACB	700	05.9243.40	701	05.9364.14A	529	05.9505.14	538	05.9577.ER	539
05.9206.ER	698	05.9236.ESADA	700	05.9243.40.78	701	05.9364.40A	529	05.9505.40	538	05.9578.ES	539
05.9206.ERACB	698	05.9237.14	701	05.9243.40AC6	701	05.9364.ERA	529	05.9507.14	538	05.9580.40	540
05.9206.ERADA	698	05.9237.14ACB	701	05.9243.40ACB	701	05.9364.ESA	529	05.9507.40	538	05.9581.40	540
05.9206.ES	698	05.9237.14ADA	701	05.9243.40ADA	701	05.9365.14A	529	05.9507.ER	538	05.9583.40	540
05.9206.ESACB	698	05.9237.40	701	05.9243.40AYU	701	05.9365.40A	529	05.9508.ES	538	05.9584.14	540
05.9206.ESADA	698	05.9237.40.78	701	05.9243.ER	701	05.9367.14A	529	05.9510.40	539	05.9584.40	540
05.9207.14	699	05.9237.40AC6	701	05.9243.ERACB	701	05.9367.40A	529	05.9511.40	539	05.9584.ER	540
05.9207.14ACB	699	05.9237.40ACB	701	05.9243.ERADA	701	05.9367.ERA	529	05.9513.40	539	05.9584.ES	540
05.9207.14ADA	699	05.9237.40ADA	701	05.9243.ES	701	05.9368.ESA	529	05.9514.14	539	05.9585.14	540
05.9207.40	699	05.9237.40AYU	701	05.9243.ESACB	701	05.9370.40A	530	05.9514.40	539	05.9585.40	540
05.9207.40.78	699	05.9237.ER	701	05.9243.ESADA	701	05.9371.40A	530	05.9514.ER	539	05.9587.14	540
05.9207.40AC6	699	05.9237.ERACB	701	05.9244.14	701	05.9373.40A	530	05.9514.ES	539	05.9587.40	540
05.9207.40ACB	699	05.9237.ERADA	701	05.9244.14ACB	701	05.9374.14A	530	05.9515.14	539	05.9587.ER	540
05.9207.40ADA	699	05.9237.ES	701	05.9244.14ADA	701	05.9374.40A	530	05.9515.40	539	05.9588.ES	540
05.9207.40AYU	699	05.9237.ESACB	701	05.9244.40	701	05.9374.ERA	530	05.9517.14	539	06.0157.00	261
05.9207.ER	699	05.9237.ESADA	701	05.9244.40.78	701	05.9374.ESA	530	05.9517.40	539	06.0173.14	79
05.9207.ERACB	699	05.9238.14	701	05.9244.40AC6	701	05.9375.14A	530	05.9517.ER	539	06.0301.00	311
05.9207.ERADA	699	05.9238.14ACB	701	05.9244.40ACB	701	05.9375.40A	530	05.9518.ES	539	06.0303.00	311
05.9207.ES	699	05.9238.14ADA	701	05.9244.40ADA	701	05.9377.14A	530	05.9520.40	540	06.0330.C5	58
05.9207.ESACB	699	05.9238.40	701	05.9244.40AYU	701	05.9377.40A	530	05.9521.40	540	06.0331.C5	58
05.9207.ESADA	699	05.9238.40.78	701	05.9244.ER	701	05.9377.ERA	530	05.9523.40	540	06.0332.C5	58
05.9210.14	698	05.9238.40AC6	701	05.9244.ERACB	701	05.9378.ESA	530	05.9524.14	540	06.0335.00	58
05.9210.14ACB	698	05.9238.40ACB	701	05.9244.ERADA	701	05.9380.40A	531	05.9524.40	540	06.0336.00	58
05.9210.14ADA	698	05.9238.40ADA	701	05.9244.ES	701	05.9381.40A	531	05.9524.ER	540	06.0337.00	59
05.9210.40	698	05.9238.40AYU	701	05.9244.ESACB	701	05.9383.40A	531	05.9524.ES	540	06.0338.00	59
05.9210.40.78	698	05.9238.ER	701	05.9244.ESADA	701	05.9384.14A	531	05.9525.14	540	06.0339.00	60
05.9210.40AC6	698	05.9238.ERACB	701	05.9300.40A	528	05.9384.40A	531	05.9525.40	540	06.0340.00	60

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
06.0341.00	61	06.0508.ES	21	06.0577.ER	126	06.0631.40	129	06.0666.14	130	06.1615.40A	218
06.0342.00	61	06.0550.14	125	06.0577.ES	126	06.0632.14	129	06.0666.40	130	06.1616.14A	218
06.0343.00	62	06.0550.40	125	06.0578.14	127	06.0632.40	129	06.0666.ER	130	06.1616.40A	218
06.0350.C5	62	06.0550.ER	125	06.0578.40	127	06.0633.14	129	06.0666.ES	130	06.1617.14A	218
06.0351.C5	62	06.0550.ES	125	06.0578.ER	127	06.0633.40	129	06.0667.14	130	06.1617.40A	218
06.0352.C5	62	06.0551.14	125	06.0578.ES	127	06.0634.14	129	06.0667.40	130	06.1618.14A	218
06.0353.C5	62	06.0551.40	125	06.0600.14	129	06.0634.40	129	06.0667.ER	130	06.1618.40A	218
06.0354.C5	63	06.0551.ER	125	06.0600.40	129	06.0640.14	129	06.0667.ES	130	06.1619.14A	218
06.0355.C5	63	06.0551.ES	125	06.0600.ER	129	06.0640.40	129	06.0668.14	131	06.1619.40A	218
06.0366.00	58	06.0552.14	125	06.0600.ES	129	06.0640.ER	129	06.0668.40	131	06.1620.14A	218
06.0367.00	58	06.0552.40	125	06.0601.14	129	06.0640.ES	129	06.0668.ER	131	06.1620.40A	218
06.0368.00	58	06.0552.ER	125	06.0601.40	129	06.0641.14	129	06.0668.ES	131	06.1621.14A	218
06.0369.00	58	06.0552.ES	125	06.0601.ER	129	06.0641.40	129	06.0670.00	127	06.1621.40A	218
06.0370.00	58	06.0553.14	125	06.0601.ES	129	06.0641.ER	129	06.0670.00	131	06.1622.14A	218
06.0371.00	58	06.0553.40	125	06.0602.14	129	06.0641.ES	129	06.0671.00	127	06.1622.40A	218
06.0372.00	58	06.0554.40	125	06.0602.40	129	06.0642.14	129	06.0671.00	131	06.1623.14A	218
06.0373.00	59	06.0555.14	125	06.0602.ER	129	06.0642.40	129	06.0672.00	130	06.1623.40A	218
06.0374.00	59	06.0555.14	125	06.0602.ES	129	06.0642.ER	129	06.0673.00	130	06.1624.14	219
06.0375.00	59	06.0555.40	125	06.0603.14	129	06.0642.ES	129	06.0674.14	132	06.1624.40	219
06.0376.00	59	06.0555.ER	125	06.0603.40	129	06.0643.14	129	06.0674.40	132	06.1626.14	216
06.0377.00	59	06.0555.ES	125	06.0603.ER	129	06.0643.40	129	06.0674.ER	132	06.1626.40	216
06.0378.00	59	06.0556.14	125	06.0603.ES	129	06.0643.ER	129	06.0674.ES	132	06.1627.14	216
06.0379.00	59	06.0556.40	125	06.0604.14	129	06.0643.ES	129	06.0675.00	132	06.1627.40	216
06.0380.00	59	06.0556.ER	125	06.0604.40	129	06.0644.14	129	06.0683.00	126	06.1628.14	216
06.0381.00	60	06.0556.ES	125	06.0604.ER	129	06.0644.40	129	06.0684.00	126	06.1628.40	216
06.0382.00	60	06.0557.14	125	06.0604.ES	129	06.0644.ER	129	06.0731.14	126	06.1629.14	216
06.0383.00	60	06.0557.40	125	06.0605.14	129	06.0644.ES	129	06.0731.40	126	06.1629.40	216
06.0384.00	60	06.0557.ER	125	06.0605.40	129	06.0645.14	129	06.0732.14	130	06.1630.14	216
06.0385.00	60	06.0557.ES	125	06.0605.ER	129	06.0645.40	129	06.0732.40	130	06.1630.40	216
06.0386.00	60	06.0558.14	125	06.0605.ES	129	06.0645.ER	129	06.0733.14	126	06.1631.14	216
06.0387.00	60	06.0558.40	125	06.0606.14	129	06.0645.ES	129	06.0733.40	126	06.1631.40	216
06.0388.00	60	06.0559.14	125	06.0606.40	129	06.0646.14	129	06.0734.14	130	06.1632.14	216
06.0389.00	61	06.0559.40	125	06.0606.ER	129	06.0646.40	129	06.0734.40	130	06.1632.40	216
06.0390.00	61	06.0560.14	125	06.0606.ES	129	06.0647.14	129	06.0735.14	127	06.1633.14	216
06.0391.00	61	06.0560.40	125	06.0607.14	129	06.0647.40	129	06.0735.14	131	06.1633.40	216
06.0392.00	61	06.0560.ER	125	06.0607.40	129	06.0648.14	129	06.0735.40	127	06.1634.14	216
06.0393.00	61	06.0560.ES	125	06.0607.ER	129	06.0648.40	129	06.0735.40	131	06.1634.40	216
06.0394.00	61	06.0561.14	125	06.0607.ES	129	06.0649.14	129	06.0736.14	127	06.1635.14	216
06.0395.00	61	06.0561.40	125	06.0608.14	129	06.0649.40	129	06.0736.14	131	06.1635.40	216
06.0396.00	61	06.0561.ER	125	06.0608.40	129	06.0650.14	129	06.0736.40	127	06.1638.14	212
06.0403.C5	63	06.0561.ES	125	06.0608.ER	129	06.0650.40	129	06.0736.40	131	06.1639.14	212
06.0404.C5	63	06.0562.14	125	06.0608.ES	129	06.0650.ER	129	06.0737.14	126	06.1640.14	212
06.0420.14	320	06.0562.40	125	06.0609.14	129	06.0650.ES	129	06.0737.14	130	06.1641.14	212
06.0420.30	320	06.0562.ER	125	06.0609.40	129	06.0651.14	129	06.0737.40	126	06.1642.14	212
06.0436.14	399	06.0562.ES	125	06.0610.14	129	06.0651.40	129	06.0737.40	130	06.1643.14	212
06.0436.40	399	06.0563.14	125	06.0610.40	129	06.0651.ER	129	06.0737.ER	126	06.1644.14	212
06.0436.AP	399	06.0563.40	125	06.0611.14	129	06.0651.ES	129	06.0737.ER	130	06.1645.14	212
06.0450.14	118	06.0564.40	125	06.0611.40	129	06.0652.14	129	06.0737.ES	126	06.1646.14	212
06.0451.14	118	06.0565.14	125	06.0612.14	129	06.0652.40	129	06.0737.ES	130	06.1647.14	212
06.0452.14	118	06.0565.14	125	06.0612.40	129	06.0652.ER	129	06.0738.14	126	06.1648.14	213
06.0453.14	118	06.0565.40	125	06.0613.14	129	06.0652.ES	129	06.0738.14	130	06.1650.14	213
06.0454.14	118	06.0565.ER	125	06.0613.40	129	06.0653.14	129	06.0738.40	126	06.1651.14	213
06.0455.14	118	06.0565.ES	125	06.0614.14	129	06.0653.40	129	06.0738.40	130	06.1656.14	217
06.0456.14	119	06.0566.14	125	06.0614.40	129	06.0653.ER	129	06.0738.ER	126	06.1656.40	217
06.0457.14	119	06.0566.40	125	06.0620.14	129	06.0653.ES	129	06.0738.ER	130	06.1657.14	217
06.0457.14	132	06.0566.ER	125	06.0620.40	129	06.0654.14	129	06.0738.ES	126	06.1657.40	217
06.0458.14	119	06.0566.ES	125	06.0620.ER	129	06.0654.40	129	06.0738.ES	130	06.1740.14	217
06.0459.14	119	06.0567.14	125	06.0620.ES	129	06.0654.ER	129	06.1005.00E	826	06.1741.14	217
06.0459.14	132	06.0567.40	125	06.0621.14	129	06.0654.ES	129	06.1012.00E	826	06.1742.14	217
06.0460.14	119	06.0567.ER	125	06.0621.40	129	06.0655.14	129	06.1013.00E	826	06.1850.14	310
06.0460.14	132	06.0567.ES	125	06.0621.ER	129	06.0655.40	129	06.1014.00E	826	06.1851.14	310
06.0461.14	119	06.0568.14	125	06.0621.ES	129	06.0655.ER	129	06.1016.00	826	06.1852.14	310
06.0500.14	416	06.0568.40	125	06.0622.14	129	06.0655.ES	129	06.1019.00E	826	06.1853.14	310
06.0500.40	416	06.0569.14	125	06.0622.40	129	06.0656.14	129	06.1020.00E	826	06.1860.14	311
06.0501.14	21	06.0569.40	125	06.0622.ER	129	06.0656.40	129	06.1022.00E	826	06.1860.40	311
06.0501.40	21	06.0570.14	127	06.0622.ES	129	06.0657.14	129	06.1049.00	826	06.1861.14	311
06.0501.ER	21	06.0570.40	127	06.0623.14	129	06.0657.40	129	06.1150.14	215	06.1861.40	311
06.0501.ES	21	06.0570.ER	127	06.0623.40	129	06.0658.14	129	06.1150.40	215	06.1862.14	311
06.0502.14	21	06.0570.ES	127	06.0623.ER	129	06.0658.40	129	06.1600.14	214	06.1862.40	311
06.0502.40	21	06.0571.14	127	06.0623.ES	129	06.0659.14	129	06.1600.40	214	06.1863.14	311
06.0502.ER	21	06.0571.40	127	06.0624.14	129	06.0659.40	129	06.1601.14	214	06.1863.40	311
06.0502.ES	21	06.0571.ER	127	06.0624.40	129	06.0660.14	131	06.1601.40	214	06.1974.00	798
06.0503.14	21	06.0571.ES	127	06.0624.ER	129	06.0660.40	131	06.1602.14	214	06.1987.14	249
06.0503.40	21	06.0572.14	127	06.0624.ES	129	06.0660.ER	131	06.1602.40	214	06.1987.14	315
06.0503.ER	21	06.0572.40	127	06.0625.14	129	06.0660.ES	131	06.1603.14	214	06.1987.40	249
06.0503.ES	21	06.0572.ER	127	06.0625.40	129	06.0661.14	131	06.1603.40	214	06.1987.40	315
06.0504.14	21	06.0572.ES	127	06.0625.ER	129	06.0661.40	131	06.1604.14	214	06.1988.14	87
06.0504.40	21	06.0573.14	127	06.0625.ES	129	06.0661.ER	131	06.1604.40	214	06.1988.14	108
06.0504.ER	21	06.0573.40	127	06.0626.14	129	06.0661.ES	131	06.1605.14	214	06.1988.14	284
06.0504.ES	21	06.0573.ER	127	06.0626.40	129	06.0662.14	131	06.1605.40	214	06.1988.40	87
06.0505.14	21	06.0573.ES	127	06.0626.ER	129	06.0662.40	131	06.1606.14	214	06.1988.40	108
06.0505.40	21	06.0574.14	126	06.0626.ES	129	06.0662.ER	131	06.1606.40	214	06.1988.40	284
06.0505.ER	21	06.0574.40	126	06.0627.14	129	06.0662.ES	131	06.1607.14	214	06.2500.06	174
06.0505.ES	21	06.0574.ER	126	06.0627.40	129	06.0663.14	131	06.1607.40	214	06.2500.14	174
06.0506.14	21	06.0574.ES	126	06.0627.ER	129	06.0663.40	131	06.1608.14	214	06.2500.18	174
06.0506.40	21	06.0575.14	126	06.0627.ES	129	06.0663.ER	131	06.1608.40	214	06.2500.40	174
06.0506.ER	21	06.0575.40	126	06.0628.14	129	06.0663.ES	131	06.1609.14	214	06.2500.CZ	174
06.0506.ES	21	06.0575.ER	126	06.0628.40	129	06.0664.14	130	06.1609.40	214	06.2501.06	174
06.0507.14	21	06.0575.ES	126	06.0628.ER	129	06.0664.40	130	06.1610.14	215	06.2501.14	174
06.0507.40	21	06.0576.14	126	06.0628.ES	129	06.0664.ER	130	06.1610.40	215	06.2501.18	174
06.0507.ER	21	06.0576.40	126	06.0629.14	129	06.0664.ES	130	06.1612.14	215	06.2501.40	174
06.0507.ES	21	06.0576.ER	126	06.0629.40	129	06.0665.14	130	06.1612.40	215	06.2501.CZ	174
06.0508.14	21	06.0576.ES	126	06.0630.14	129	06.0665.40	130	06.1614.14A	218	06.2502.06	174
06.0508.40	21	06.0577.14	126	06.0630.40	129	06.0665.ER	130	06.1614.40A	218	06.2502.14	174
06.0508.ER	21	06.0577.40	126	06.0631.14	129	06.0665.ES	130	06.1615.14A	218	06.2502.18	174

QUICK SEARCH OF PRODUCT

Ref.	Page
06.2502.40	174
06.2502.CZ	174
06.2506.14	174
06.2506.40	174
06.2509.14	175
06.2509.18	175
06.2509.40	175
06.2509.CZ	175
06.2510.05A	182
06.2510.14A	182
06.2510.18A	182
06.2510.40A	182
06.2510.CZA	182
06.2511.05A	182
06.2511.14A	182
06.2511.18A	182
06.2511.40A	182
06.2511.CZA	182
06.2540.14	174
06.2540.18	174
06.2540.40	174
06.2540.CZ	174
06.2541.14	174
06.2541.18	174
06.2541.40	174
06.2541.CZ	174
06.2542.14	174
06.2542.18	174
06.2542.40	174
06.2542.CZ	174
06.2543.14	174
06.2543.18	174
06.2543.40	174
06.2543.CZ	174
06.2544.14	174
06.2544.18	174
06.2544.40	174
06.2544.CZ	174
06.2545.14	175
06.2545.18	175
06.2545.40	175
06.2545.CZ	175
06.2546.14	175
06.2546.18	175
06.2546.40	175
06.2546.CZ	175
06.2600.14	120
06.2600.40	120
06.2600.ER	120
06.2600.ES	120
06.2601.14	120
06.2601.40	120
06.2601.ER	120
06.2601.ES	120
06.2602.14	120
06.2602.40	120
06.2603.14	120
06.2603.40	120
06.2603.ER	120
06.2603.ES	120
06.2604.14	120
06.2604.40	120
06.2604.ER	120
06.2604.ES	120
06.2605.14	120
06.2605.40	120
06.2606.14	121
06.2606.40	121
06.2606.ER	121
06.2606.ES	121
06.2607.14	121
06.2607.40	121
06.2607.ER	121
06.2607.ES	121
06.2608.14	119
06.2608.14	121
06.2608.14	132
06.2608.40	121
06.2609.14	121
06.2609.40	121
06.2609.ER	121
06.2609.ES	121
06.2610.14	121
06.2610.40	121
06.2611.14	122
06.2611.40	122
06.2611.ER	122
06.2611.ES	122
06.2612.14	122
06.2612.40	122
06.2612.ER	122
06.2612.ES	122
06.2613.14	121
06.2613.40	121
06.2613.ER	121
06.2613.ES	121
06.2614.14	121
06.2614.40	121
06.2614.ER	121
06.2614.ES	121
06.2615.14	122
06.2615.40	122
06.2615.ER	122
06.2615.ES	122
06.2616.14	122
06.2616.40	122
06.2616.ER	122
06.2616.ES	122
06.2617.14	122
06.2617.40	122
06.2617.ER	122
06.2617.ES	122
06.2618.14A	122
06.2618.40A	122
06.2619.14	123
06.2619.40	123
06.2619.ER	123
06.2619.ES	123
06.2620.14	123
06.2620.40	123
06.2620.ER	123
06.2620.ES	123
06.2621.14	121
06.2621.40	121
06.2621.ER	121
06.2621.ES	121
06.2640.14	118
06.2641.14	118
06.2642.14	118
06.2643.14	118
06.2644.14	118
06.2645.14	118
06.2660.14	20
06.2660.40	20
06.2660.ER	20
06.2660.ES	20
06.2661.14	20
06.2661.40	20
06.2661.ER	20
06.2661.ES	20
06.2662.14	20
06.2662.40	20
06.2662.ER	20
06.2662.ES	20
06.2663.14	20
06.2663.40	20
06.2663.ER	20
06.2663.ES	20
06.2664.14	20
06.2664.40	20
06.2664.ER	20
06.2664.ES	20
06.2665.14	20
06.2665.40	20
06.2665.ER	20
06.2665.ES	20
06.2666.14	30
06.2666.40	30
06.2666.ER	30
06.2666.ES	30
06.2667.14	30
06.2667.40	30
06.2667.ER	30
06.2667.ES	30
06.2668.14	30
06.2668.40	30
06.2668.ER	30
06.2668.ES	30
06.2669.14	30
06.2669.40	30
06.2669.ER	30
06.2669.ES	30
06.2670.14	30
06.2670.40	30
06.2670.ER	30
06.2670.ES	30
06.2671.14	30
06.2671.40	30
06.2671.ER	30
06.2671.ES	30
06.2672.14	26
06.2672.40	26
06.2672.ER	26
06.2672.ES	26
06.2673.14	26
06.2673.40	26
06.2673.ER	26
06.2673.ES	26
06.2674.14	26
06.2674.40	26
06.2674.ER	26
06.2674.ES	26
06.2675.14	26
06.2675.40	26
06.2675.ER	26
06.2675.ES	26
06.2676.14	26
06.2676.40	26
06.2676.ER	26
06.2676.ES	26
06.2677.14	26
06.2677.40	26
06.2677.ER	26
06.2677.ES	26
06.2678.14	34
06.2678.40	34
06.2678.ER	34
06.2678.ES	34
06.2679.14	34
06.2679.40	34
06.2679.ER	34
06.2679.ES	34
06.2680.14	34
06.2680.40	34
06.2680.ER	34
06.2680.ES	34
06.2681.14	34
06.2681.40	34
06.2681.ER	34
06.2681.ES	34
06.2682.14	34
06.2682.40	34
06.2682.ER	34
06.2682.ES	34
06.2683.14	34
06.2683.40	34
06.2683.ER	34
06.2683.ES	34
06.5008.14	257
06.5010.05	258
06.5010.14	258
06.5010.40	258
06.5011.05	258
06.5011.14	258
06.5011.40	258
06.5012.05	258
06.5012.14	258
06.5012.40	258
06.5013.05	258
06.5013.14	258
06.5013.40	258
06.5014.14	258
06.5014.40	258
06.5015.05	259
06.5015.14	259
06.5015.40	259
06.5016.05	259
06.5016.14	259
06.5016.40	259
06.5017.05A	259
06.5017.14	259
06.5017.40	259
06.5020.05	262
06.5020.14	262
06.5020.40	262
06.5021.05	262
06.5021.14	262
06.5021.40	262
06.5022.05	262
06.5022.14	262
06.5022.40	262
06.5023.05	262
06.5023.14	262
06.5023.40	262
06.5024.14	262
06.5024.40	262
06.5025.05	263
06.5025.14	263
06.5025.40	263
06.5026.05A	263
06.5026.14	263
06.5026.40	263
06.5040.14	256
06.5041.14	256
06.5042.14	256
06.5043.14	256
06.5044.14	256
06.5045.14	257
06.5046.14	257
06.5047.14	257
06.5050.14	256
06.5051.14	256
06.5052.14	256
06.5053.14	256
06.5054.14	256
06.5060.05	258
06.5060.14	258
06.5060.40	258
06.5061.05	258
06.5061.14	258
06.5061.40	258
06.5062.05	258
06.5062.14	258
06.5062.40	258
06.5063.05	258
06.5063.14	258
06.5063.40	258
06.5064.14	258
06.5064.40	258
06.5070.05	262
06.5070.14	262
06.5070.40	262
06.5071.05	262
06.5071.14	262
06.5071.40	262
06.5072.05	262
06.5072.14	262
06.5072.40	262
06.5073.05	262
06.5073.14	262
06.5073.40	262
06.5074.14	262
06.5074.40	262
06.5096.14	259
06.5096.40	259
06.5100.14	85
06.5100.40	85
06.5101.14	85
06.5101.40	85
06.5110.14	86
06.5110.40	86
06.5111.14	86
06.5111.40	86
06.5112.14	86
06.5112.40	86
06.5113.14	86
06.5113.40	86
06.5115.14	85
06.5115.40	85
06.5116.14	85
06.5116.40	85
06.5117.14	85
06.5117.40	85
06.5118.14	85
06.5118.40	85
06.5120.14	87
06.5120.40	87
06.5121.14	87
06.5121.40	87
06.5122.14	87
06.5122.40	87
06.5123.14	87
06.5123.40	87
06.5125.14	85
06.5125.40	85
06.5126.14	85
06.5126.40	85
06.5127.14	85
06.5127.40	85
06.5128.14	85
06.5128.40	85
06.5135.14A	85
06.5135.40A	85
06.5140.14	85
06.5140.40	85
06.5141.14	85
06.5141.40	85
06.5142.14A	85
06.5142.40A	85
06.5150.14	87
06.5150.40	87
06.5151.14	87
06.5151.40	87
06.5152.14	87
06.5152.40	87
06.5153.14	87
06.5153.40	87
06.5155.14	85
06.5155.40	85
06.5156.14	85
06.5156.40	85
06.5157.14	85
06.5157.40	85
06.5158.14	85
06.5158.40	85
06.6000.14	190
06.6001.14	190
06.6002.14	190
06.6003.14	190
06.6004.14	190
06.6010.14	191
06.6010.40	191
06.6011.14	191
06.6011.40	191
06.6012.14	191
06.6012.40	191
06.6013.14	191
06.6013.40	191
06.6014.14	191
06.6014.40	191
06.6030.14	190
06.6031.14	191
06.6031.40	191
06.6032.14	190
06.6033.14	191
06.6033.40	191
06.6034.14	190
06.6034.14	191
06.6034.40	191
06.6035.14	190
06.6035.14	191
06.6036.14	190
06.6036.14	191
06.6036.40	191
07.9630.70	778
07.9630.70	778
07.9630.76	779
07.9630.76	779
07.9630.AN	778
07.9630.AN	778
07.9630.AP	778
07.9630.AP	778
07.9630.CE	779
07.9630.CE	779
07.9641.14A	778
07.9641.14ADA	778
07.9642.14A	778
07.9642.14ADA	778
08.0030	329
08.0031.00	329
08.0031.00.DA	329
08.0032.00	85
08.0033.00	85
08.0050.00	231
08.0050.00	273
08.0052.90	511
08.0059.90	511
08.0109.00	329
08.0110.00	329
08.0112.00	329
08.0113.00	329
08.0131.14	320
08.0131.29	320
08.0131.40	320
08.0132.00	622
08.0139.00	320
08.0160.14	556
08.0160.40	556
08.0160.ER	556
08.0160.ES	556
08.0161.14	557
08.0161.40	557
08.0161.ER	557
08.0161.ES	557
08.0164.14	556
08.0164.40	556
08.0164.ER	556
08.0164.ES	556
08.0165.14	557
08.0165.40	557
08.0165.ER	557
08.0165.ES	557
08.0166.00	556
08.0167.00	557
08.0175.14	103
08.0175.14	281
08.0175.14	702
08.0176.14	103
08.0176.14	281
08.0176.14	702
08.0180.00	79
08.0181.00	79
08.0182.00	79
08.0190.14	204
08.0191.14	204
08.0192.00	556
08.0193.00	557
08.0194.00	79
08.0195.00	79
08.0205.00A	755
08.0206.00	755
08.0207.00A	755
08.0208.00	755
08.0209.DR	755
08.0209.DY	755
08.0209.ER	755
08.0209.ES	755
08.0210.00A	755
08.0211.DR	755
08.0211.DY	755
08.0211.ER	755
08.0211.ES	755
08.0212.DRA	755
08.0212.DYA	755
08.0212.ERA	755
08.0212.ESA	755
08.0226.00A	755
08.0227.00	755
08.0228.DR	755
08.0228.DY	755
08.0228.ER	755
08.0228.ES	755
08.0231.00	755
08.0254.00A	755
08.0255.00	755
08.0269.00	511
08.0270.00	511
08.0360.14	555
08.0360.40	555
08.0360.ER	555
08.0360.ES	555
08.0361.00	555
08.0500.00	689
08.0501.00	689
08.0505.00	689
08.0506.14	689
08.0506.40	689
08.0506.CE	689
08.0507.14	689
08.0507.40	689
08.0507.CE	689
08.0510.00	511
08.0511.00	511
08.0512.00	511
08.0513.00	511
08.0515.00	511
08.0516.00	511
08.0517.00	511
08.0518.00	511
08.0520.02A	774
08.0520.14A	774
08.0520.40A	774
08.0520.ETA	774
08.0520.EUA	774
08.0521.02A	774
08.0521.14A	774
08.0521.40A	774
08.0521.ETA	774
08.0521.EUA	774
08.0522.02A	774
08.0522.14A	774
08.0522.40A	774
08.0522.ETA	774
08.0522.EUA	774
08.0523.02A	774
08.0523.14A	774
08.0523.40A	774
08.0523.ETA	774
08.0523.EUA	774
08.0524.02	775
08.0524.14	775
08.0524.40	775
08.0524.ET	775
08.0524.EU	775
08.0525.02A	775
08.0525.14A	775
08.0525.40A	775
08.0525.ETA	775
08.0525.EUA	775
08.0526.00	95
08.0526.00	271
08.0526.00	304
08.0526.00	314
08.0526.00	666
08.0526.00	690
08.0526.00	740
08.0526.00	759
08.0526.40	95
08.0526.40	271
08.0526.40	304
08.0526.40	314
08.0526.40	666
08.0526.40	740
08.0526.40	759
08.0526.BW	95
08.0526.BW	271
08.0526.BW	304
08.0526.BW	314
08.0526.BW	666
08.0526.BW	740

QUICK SEARCH OF PRODUCT

Ref.	Page
08.0526.BW	759
08.0550.00	689
08.0551.00	689
08.0555.00	689
08.0556.14	689
08.0556.40	689
08.0556.CE	689
08.0557.14	689
08.0557.40	689
08.0557.CE	689
08.0580.00	535
08.0581.00	535
08.0582.00	535
08.0583.00	535
08.0584.00	535
08.0586.00	535
08.0600.14	261
08.0600.40	261
08.0611.14	257
08.0611.14	259
08.0612.14	257
08.0612.14	259
08.0613.14A	87
08.0613.14A	123
08.0613.14A	259
08.0614.14	257
08.0614.14	259
08.0615.00	22
08.0615.00	31
08.0615.00	259
08.0616.00	261
08.0626.00	263
08.0627.00	261
08.0630.14	175
08.0630.40	175
08.0631.14A	263
08.0631.40A	263
08.0632.14A	263
08.0632.40A	263
08.0640.02	774
08.0640.14	774
08.0640.40	774
08.0640.ET	774
08.0640.EU	774
08.0641.02	774
08.0641.14	774
08.0641.40	774
08.0641.ET	774
08.0641.EU	774
08.0642.02	775
08.0642.14	775
08.0642.40	775
08.0642.ET	775
08.0642.EU	775
08.0661.14	534
08.0661.40	534
08.0661.ER	534
08.0661.ES	534
08.0670.14	567
08.0670.40	567
08.0671.14	585
08.0671.40	585
08.0672.00	567
08.0673.00	585
08.0711.00	567
08.0712.00	567
08.0713.00	567
08.0714.00	585
08.0715.00	585
08.0715.00	585
08.0716.00	585
08.0716.00	585
08.0717.00	585
08.0718.00	585
08.0719.00	585
08.0720.00	585
08.0721.14	567
08.0721.40	567
08.0722.14	567
08.0722.40	567
08.0723.14	567
08.0723.40	567
08.0724.14	585
08.0724.40	585
08.0725.14	585
08.0725.40	585
08.0726.14	585
08.0726.40	585
08.0727.00	567
08.0728.00	585
08.0729.00	567
08.0730.00	585
08.0731.00	567
08.0732.00	567
08.0735.00	585
08.0736.00	585
08.0739.00	567
08.0740.00	567
08.0741.00	585
08.0742.00	585
08.0744.00	341
08.0756.00	535
08.0757.00	555
08.0761.14	341
08.0761.30	341
08.0790.00	39
08.0790.00	103
08.0790.00	151
08.0790.00	201
08.0790.00	225
08.0790.00	281
08.0790.00	529
08.0790.00	531
08.0791.00	39
08.0791.00	103
08.0791.00	151
08.0791.00	201
08.0791.00	225
08.0791.00	281
08.0791.00	529
08.0791.00	531
08.0792.00	39
08.0792.00	103
08.0792.00	151
08.0792.00	201
08.0792.00	225
08.0792.00	281
08.0792.00	529
08.0792.00	531
08.0793.00	39
08.0793.00	103
08.0793.00	153
08.0793.00	227
08.0793.00	281
08.0793.00	539
08.0793.00	541
08.0793.00	702
08.0794.00	39
08.0794.00	103
08.0794.00	153
08.0794.00	227
08.0794.00	281
08.0794.00	539
08.0794.00	541
08.0794.00	702
08.0795.00	39
08.0795.00	103
08.0795.00	153
08.0795.00	227
08.0795.00	281
08.0795.00	539
08.0795.00	541
08.0795.00	702
08.0796.00	103
08.0796.00	281
08.0796.00	702
08.0797.00	103
08.0797.00	281
08.0797.00	702
08.0798.00	103
08.0798.00	281
08.0798.00	702
08.0799.00	103
08.0799.00	281
08.0799.00	702
08.0824.14	62
08.0824.14	79
08.0824.14	87
08.0824.14	182
08.0824.14	204
08.0824.14	249
08.0825.00	556
08.0826.00	557
08.0900.14	398
08.0900.40	398
08.0900.AP	398
08.0901.14	398
08.0901.40	398
08.0901.AP	398
08.0903.14	398
08.0903.40	398
08.0903.AP	398
08.0904.14	398
08.0904.40	398
08.0904.AP	398
08.0905.14	398
08.0905.40	398
08.0905.AP	398
08.0906.14	398
08.0906.40	398
08.0906.AP	398
08.0910.14	398
08.0910.40	398
08.0910.AP	398
08.0911.14	398
08.0911.40	398
08.0911.AP	398
08.0913.14	398
08.0913.40	398
08.0913.AP	398
08.0914.14	398
08.0914.40	398
08.0914.AP	398
08.0915.14	398
08.0915.14	398
08.0915.40	398
08.0915.40	398
08.0915.AP	398
08.0915.AP	398
08.0920.14	398
08.0920.40	398
08.0920.AP	398
08.0921.14	398
08.0921.40	398
08.0921.AP	398
08.0923.14	398
08.0923.40	398
08.0923.AP	398
08.0924.14	398
08.0924.40	398
08.0924.AP	398
08.0925.14	398
08.0925.14	398
08.0925.40	398
08.0925.40	398
08.0925.AP	398
08.0925.AP	398
08.0956.14	347
08.0956.40	347
08.0961.00	62
08.1040.14	416
08.1040.40	416
08.1041.14	416
08.1041.40	416
08.1042.00	62
08.1050.00	423
08.1053.14	423
08.1053.40	423
08.1056.00	432
08.1057.00	432
08.1058.00	432
08.1059.00	432
08.1060.14	416
08.1060.40	416
08.1061.14	416
08.1061.40	416
08.1062.90	423
08.1205.14	22
08.1205.40	22
08.1205.ER	22
08.1205.ES	22
08.1206.14	22
08.1206.14	35
08.1206.40	22
08.1206.40	35
08.1206.ER	22
08.1206.ER	35
08.1206.ES	22
08.1206.ES	35
08.1207.14	22
08.1207.40	22
08.1207.ER	22
08.1207.ES	22
08.1208.14	22
08.1208.40	22
08.1208.ER	22
08.1208.ES	22
08.1209.14	31
08.1209.40	31
08.1209.ER	31
08.1209.ES	31
08.1210.14	31
08.1210.40	31
08.1210.ER	31
08.1210.ES	31
08.1211.14	31
08.1211.40	31
08.1211.ER	31
08.1211.ES	31
08.1212.14	31
08.1212.40	31
08.1212.ER	31
08.1212.ES	31
08.1213.14	22
08.1213.40	22
08.1213.ER	22
08.1213.ES	22
08.1230.14	133
08.1230.40	133
08.1230.ER	133
08.1230.ES	133
08.1231.14	133
08.1231.40	133
08.1231.ER	133
08.1231.ES	133
08.1232.14	133
08.1232.40	133
08.1233.14	133
08.1233.40	133
08.1234.14	133
08.1234.40	133
08.1235.14	133
08.1235.40	133
08.1236.14	133
08.1236.40	133
08.1236.ER	133
08.1236.ES	133
08.1237.14	133
08.1237.40	133
08.1237.ER	133
08.1237.ES	133
08.1238.14	133
08.1238.40	133
08.1238.ER	133
08.1238.ES	133
08.1239.14	133
08.1239.40	133
08.1239.ER	133
08.1239.ES	133
08.3309.14	335
08.8118.68	679
08.8119.00	678
08.8137.00	678
08.8163.68	666
08.8163.68	740
08.8175.68	666
08.8175.68	740
08.8242.14	679
08.8297.00	826
08.8298.00	826
08.8359.00	678
08.8377.14	679
08.8410.00	666
08.8410.00	740
08.8411.00	666
08.8411.00	740
08.8418.68A	231
08.8418.68A	273
08.8419.14A	231
08.8419.14A	273
08.8420.00	622
08.8422.00	785
08.8423.00	787
08.8427.14	228
08.8428.00	95
08.8428.00	271
08.8428.00	304
08.8428.00	314
08.8428.00	666
08.8428.00	690
08.8428.00	740
08.8428.00	759
08.8429.00	95
08.8429.00	271
08.8429.00	304
08.8429.00	314
08.8429.00	666
08.8429.00	690
08.8429.00	740
08.8429.00	759
08.8431.00	95
08.8431.00	271
08.8431.00	304
08.8431.00	314
08.8431.00	666
08.8431.00	690
08.8431.00	740
08.8431.00	759
08.8432.00	95
08.8432.00	271
08.8432.00	304
08.8432.00	314
08.8432.00	666
08.8432.00	690
08.8432.00	740
08.8432.00	759
08.8450.00	679
08.8451.00	679
08.8452.00	679
08.8453.14	679
08.8453.40	679
08.8479.00	622
08.8495.14	666
08.8495.14	740
08.8572.14D	588
08.8572.14D	588
08.8572.14D	589
08.8572.14D1V	588
08.8572.14D1V	588
08.8572.14D1V	589
08.8572.14DDA	588
08.8572.14DDA	588
08.8572.14DDA	589
08.8573.14D	588
08.8573.14D	588
08.8573.14D	589
08.8573.14D1V	588
08.8573.14D1V	588
08.8573.14D1V	589
08.8573.14DDA	588
08.8573.14DDA	588
08.8573.14DDA	589
08.8590.05A	816
08.8590.40A	816
08.8590.AAA	816
08.8591.05A	816
08.8591.40A	816
08.8591.AAA	816
08.8595.05A	816
08.8595.40A	816
08.8595.AAA	816
08.8596.05A	816
08.8596.40A	816
08.8596.AAA	816
08.8634.00	261
08.8662.14D	588
08.8662.14D	588
08.8662.14D	589
08.8662.14D1V	588
08.8662.14D1V	588
08.8662.14D1V	589
08.8662.14DDA	588
08.8662.14DDA	589
08.8663.14D	588
08.8663.14D	588
08.8663.14D	589
08.8663.14D1V	588
08.8663.14D1V	588
08.8663.14D1V	589
08.8663.14DDA	588
08.8663.14DDA	588
08.8663.14DDA	589
08.8701.14	333
08.8701.30	333
08.8702.14	333
08.8702.30	333
08.8705.14	332
08.8705.30	332
08.8706.14	332
08.8706.30	332
08.8707.14	332
08.8707.30	332
08.8708.14	332
08.8708.30	332
08.8709.14	333
08.8709.30	333
08.8710.14	333
08.8710.30	333
08.8711.00	333
08.8720.14	332
08.8720.30	332
08.8721.14	332
08.8721.30	332
08.8759.00	245
08.8760.00	245
08.8761.00	245
08.8775.14	779
08.8775.40	779
08.8782.30	725
08.8783.05A	725
08.8783.05ADA	725
08.8783.14A	725
08.8783.14ADA	725
08.8783.30A	725
08.8783.30ADA	725
08.8865.14A	213
08.8866.14	119
08.8866.14	213
08.8866.14	257
08.8866.14	310
08.8867.14	119
08.8867.14	213
08.8867.14	257
08.8867.14	310
08.8883.14A	217
08.8883.14A	261
08.8883.40A	217
08.8883.40A	261
08.8886.14	217
08.8886.14.CB	217
08.8886.14.DA	217
08.8886.40	217
08.8886.40.CB	217
08.8886.40.DA	217
08.8887.14A	215
08.8887.14A	217
08.8887.14A	219
08.8887.40A	215
08.8887.40A	217
08.8887.40A	219
08.8889.14	217
08.8889.14	261
08.8889.40	217
08.8889.40	261
08.8974.00	659
08.8975.00	659
08.8976.14	659
08.8977.00	659
08.8978.00	659
08.8980.14	659
08.8994.14	666
08.8994.30	666
08.8995.14	666
08.8995.30	666
08.9050.02	329
08.9050.40	329
08.9050.NS	329
08.9051.02	329
08.9051.40	329
08.9051.NS	329
08.9052.02	329
08.9052.40	329
08.9052.NS	329
08.9053.02	329
08.9053.40	329
08.9053.NS	329
08.9056.02	329
08.9056.40	329
08.9056.NS	329
08.9057.02	329
08.9057.40	329
08.9057.NS	329
08.9070.14	310
08.9071.14	311
08.9071.40	311
08.9074.14	311
08.9076.02	775
08.9076.14	775
08.9076.40	775
08.9076.ET	775
08.9076.EU	775
08.9077.02	775
08.9077.14	775
08.9077.40	775
08.9077.ET	775
08.9077.EU	775
08.9102.00	622
08.9102.00	687
08.9103.00	622
08.9103.00	687
08.9104.00	622
08.9105.00	687
08.9107.00	304
08.9107.00	740
08.9107.00	759
08.9108.00	304
08.9108.00	740
08.9108.00	759
08.9109.00	304
08.9109.00	740
08.9109.00	759
08.9110.00	304
08.9110.00	740
08.9110.00	759
08.9111.00	304
08.9111.00	740
08.9111.00	759
08.9111.40	740
08.9111.BW	740
08.9114.00	622
09.0045.29B	783
09.0045.30B	783
09.0045.BZB	783
09.0100.29B	783
09.0100.30B	783
09.0100.BZB	783
09.0101.29B	783
09.0101.30B	783
09.0101.BZB	783

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
09.0102.29B	783	09.3751.14A	723	09.3840.14A	181	09.3913.14A	177	09.3964.14A	178	09.4487.14C	734
09.0102.30B	783	09.3751.30A	723	09.3840.18A	181	09.3913.18A	177	09.3964.18A	178	09.4487.30C	734
09.0102.BZB	783	09.3755.05A	723	09.3840.40A	181	09.3913.40A	177	09.3964.40A	178	09.4488.14C	734
09.0103.29B	783	09.3755.14A	723	09.3840.CZA	181	09.3913.CZA	177	09.3964.CZA	178	09.4488.30C	734
09.0103.30B	783	09.3755.30A	723	09.3841.05	181	09.3920.05A	179	09.3965.05A	178	09.4510.14A	662
09.0103.BZB	783	09.3756.05A	723	09.3841.14A	181	09.3920.14A	179	09.3965.14A	178	09.4510.14ADA	662
09.0104.29A	783	09.3756.14A	723	09.3841.18A	181	09.3920.18A	179	09.3965.18A	178	09.4510.30A	662
09.0104.30A	783	09.3756.30A	723	09.3841.40A	181	09.3920.40A	179	09.3965.40A	178	09.4510.30ADA	662
09.0104.BZA	783	09.3780.05A	722	09.3841.CZA	181	09.3920.CZA	179	09.3965.CZA	178	09.4511.14A	662
09.0120.29B	783	09.3780.14A	722	09.3842.05	181	09.3921.05A	179	09.4440.14A	734	09.4511.14ADA	662
09.0120.30B	783	09.3780.30A	722	09.3842.14A	181	09.3921.14A	179	09.4440.14BDA	734	09.4511.30A	662
09.0120.BZB	783	09.3781.05A	722	09.3842.18A	181	09.3921.18A	179	09.4440.30A	734	09.4511.30ADA	662
09.0217.14C	334	09.3781.14A	722	09.3842.40A	181	09.3921.40A	179	09.4440.30BDA	734	09.4512.14A	662
09.0217.30C	334	09.3781.30A	722	09.3842.CZA	181	09.3921.CZA	179	09.4441.14A	734	09.4512.14ADA	662
09.0218.14C	334	09.3800.05A	176	09.3843.05	181	09.3922.05A	179	09.4441.14BDA	734	09.4512.30A	662
09.0218.30C	334	09.3800.14A	176	09.3843.14A	181	09.3922.14A	179	09.4441.30A	734	09.4512.30ADA	662
09.0219.14C	334	09.3800.18A	176	09.3843.18A	181	09.3922.18A	179	09.4441.30BDA	734	09.4513.14C	662
09.0219.30C	334	09.3800.40A	176	09.3843.40A	181	09.3922.40A	179	09.4442.14A	734	09.4513.14CDA	662
09.0360.14	334	09.3800.CZA	176	09.3843.CZA	181	09.3922.CZA	179	09.4442.14BDA	734	09.4513.30C	662
09.0360.30	334	09.3801.05A	176	09.3850.05	181	09.3923.05A	179	09.4442.30A	734	09.4513.30CDA	662
09.0361.14	334	09.3801.14A	176	09.3850.14	181	09.3923.14A	179	09.4442.30BDA	734	09.4514.14C	662
09.0361.30	334	09.3801.18A	176	09.3850.18	181	09.3923.18A	179	09.4443.14C	734	09.4514.14CDA	662
09.0362.14	334	09.3801.40A	176	09.3850.40	181	09.3923.40A	179	09.4443.14CDA	734	09.4514.30C	662
09.0362.30	334	09.3801.CZA	176	09.3850.CZ	181	09.3923.CZA	179	09.4443.30C	734	09.4514.30CDA	662
09.0365.14A	334	09.3802.05A	176	09.3851.05	181	09.3930.05	180	09.4443.30CDA	734	09.4515.14C	662
09.0365.30A	334	09.3802.14A	176	09.3851.14	181	09.3930.14A	180	09.4444.14C	734	09.4515.14CDA	662
09.0366.14A	334	09.3802.18A	176	09.3851.18	181	09.3930.18A	180	09.4444.14CDA	734	09.4515.30C	662
09.0366.30A	334	09.3802.40A	176	09.3851.40	181	09.3930.40A	180	09.4444.30C	734	09.4515.30CDA	662
09.0367.14A	334	09.3802.CZA	176	09.3851.CZ	181	09.3930.CZA	180	09.4444.30CDA	734	09.4516.14C	662
09.0367.30A	334	09.3803.05A	176	09.3860.05A	178	09.3931.05	180	09.4445.14C	734	09.4516.14CDA	662
09.2110.05C	781	09.3803.14A	176	09.3860.14A	178	09.3931.14A	180	09.4445.14CDA	734	09.4516.30C	662
09.2110.05CDA	781	09.3803.18A	176	09.3860.18A	178	09.3931.18A	180	09.4445.30C	734	09.4516.30CDA	662
09.2110.14C	781	09.3803.40A	176	09.3860.40A	178	09.3931.40A	180	09.4445.30CDA	734	09.4517.14C	662
09.2110.14CDA	781	09.3803.CZA	176	09.3860.CZA	178	09.3931.CZA	180	09.4450.14C	734	09.4517.14CDA	662
09.2110.40C	781	09.3810.05A	177	09.3861.05A	178	09.3932.05	180	09.4450.14CDA	734	09.4517.30C	662
09.2110.40CDA	781	09.3810.14A	177	09.3861.14A	178	09.3932.14A	180	09.4450.30C	734	09.4517.30CDA	662
09.2111.05C	781	09.3810.18A	177	09.3861.18A	178	09.3932.18A	180	09.4450.30CDA	734	09.4518.14C	662
09.2111.05CDA	781	09.3810.40A	177	09.3861.40A	178	09.3932.40A	180	09.4451.14C	734	09.4518.14CDA	662
09.2111.14C	781	09.3810.CZA	177	09.3861.CZA	178	09.3932.CZA	180	09.4451.14CDA	734	09.4518.30C	662
09.2111.14CDA	781	09.3811.05A	177	09.3862.05A	178	09.3933.05	180	09.4451.30C	734	09.4518.30CDA	662
09.2111.40C	781	09.3811.14A	177	09.3862.14A	178	09.3933.14A	180	09.4451.30CDA	734	09.4519.14A	663
09.2111.40CDA	781	09.3811.18A	177	09.3862.18A	178	09.3933.18A	180	09.4452.14C	734	09.4519.14ADA	663
09.2112.05C	781	09.3811.40A	177	09.3862.40A	178	09.3933.40A	180	09.4452.14CDA	734	09.4519.30A	663
09.2112.05CDA	781	09.3811.CZA	177	09.3862.CZA	178	09.3933.CZA	180	09.4452.30C	734	09.4519.30ADA	663
09.2112.14C	781	09.3812.05A	177	09.3863.05A	178	09.3940.05	181	09.4452.30CDA	734	09.4520.14A	663
09.2112.14CDA	781	09.3812.14A	177	09.3863.14A	178	09.3940.14A	181	09.4460.14A	729	09.4520.14ADA	663
09.2112.40C	781	09.3812.18A	177	09.3863.18A	178	09.3940.18A	181	09.4460.14ADA	729	09.4520.30A	663
09.2112.40CDA	781	09.3812.40A	177	09.3863.40A	178	09.3940.40A	181	09.4460.30A	729	09.4520.30ADA	663
09.2125.05B	781	09.3812.CZA	177	09.3863.CZA	178	09.3940.CZA	181	09.4460.30ADA	729	09.4521.14A	663
09.2125.05BDA	781	09.3813.05A	177	09.3864.05A	178	09.3941.05	181	09.4461.14A	729	09.4521.14ADA	663
09.2125.14B	781	09.3813.14A	177	09.3864.14A	178	09.3941.14A	181	09.4461.14ADA	729	09.4521.30A	663
09.2125.14BDA	781	09.3813.18A	177	09.3864.18A	178	09.3941.18A	181	09.4461.30A	729	09.4521.30ADA	663
09.2125.40B	781	09.3813.40A	177	09.3864.40A	178	09.3941.40A	181	09.4461.30ADA	729	09.4522.14C	663
09.2125.40BDA	781	09.3813.CZA	177	09.3864.CZA	178	09.3941.CZA	181	09.4462.14A	729	09.4522.14CDA	663
09.2126.05B	781	09.3820.05A	179	09.3865.05A	178	09.3942.05	181	09.4462.14ADA	729	09.4522.30C	663
09.2126.05BDA	781	09.3820.14A	179	09.3865.14A	178	09.3942.14A	181	09.4462.30A	729	09.4522.30CDA	663
09.2126.14B	781	09.3820.18A	179	09.3865.18A	178	09.3942.18A	181	09.4462.30ADA	729	09.4523.14C	663
09.2126.14BDA	781	09.3820.40A	179	09.3865.40A	178	09.3942.40A	181	09.4463.14C	729	09.4523.14CDA	663
09.2126.40B	781	09.3820.CZA	179	09.3865.CZA	178	09.3942.CZA	181	09.4463.14CDA	729	09.4523.30C	663
09.2126.40BDA	781	09.3821.05A	179	09.3900.05A	176	09.3943.05	181	09.4463.30C	729	09.4523.30CDA	663
09.2127.05B	781	09.3821.14A	179	09.3900.14A	176	09.3943.14A	181	09.4463.30CDA	729	09.4524.14C	663
09.2127.05BDA	781	09.3821.18A	179	09.3900.18A	176	09.3943.18A	181	09.4464.14C	729	09.4524.14CDA	663
09.2127.14B	781	09.3821.40A	179	09.3900.40A	176	09.3943.40A	181	09.4464.14CDA	729	09.4524.30C	663
09.2127.14BDA	781	09.3821.CZA	179	09.3900.CZA	176	09.3943.CZA	181	09.4464.30C	729	09.4524.30CDA	663
09.2127.40B	781	09.3822.05A	179	09.3901.05A	176	09.3950.05	181	09.4464.30CDA	729	09.4525.14C	663
09.2127.40BDA	781	09.3822.14A	179	09.3901.14A	176	09.3950.14	181	09.4465.14C	729	09.4525.14CDA	663
09.3200.29A	785	09.3822.18A	179	09.3901.18A	176	09.3950.18	181	09.4465.14CDA	729	09.4525.30C	663
09.3200.30A	785	09.3822.40A	179	09.3901.40A	176	09.3950.40	181	09.4465.30C	729	09.4525.30CDA	663
09.3200.55A	785	09.3822.CZA	179	09.3901.CZA	176	09.3950.CZ	181	09.4465.30CDA	729	09.4526.14C	663
09.3200.ANA	785	09.3823.05A	179	09.3902.05A	176	09.3951.05	181	09.4470.14C	729	09.4526.14CDA	663
09.3200.BZA	785	09.3823.14A	179	09.3902.14A	176	09.3951.14	181	09.4470.14CDA	729	09.4526.30C	663
09.3201.29A	785	09.3823.18A	179	09.3902.18A	176	09.3951.18	181	09.4470.30C	729	09.4526.30CDA	663
09.3201.30A	785	09.3823.40A	179	09.3902.40A	176	09.3951.40	181	09.4470.30CDA	729	09.4527.14C	663
09.3201.55A	785	09.3823.CZA	179	09.3902.CZA	176	09.3951.CZ	181	09.4471.14C	729	09.4527.14CDA	663
09.3201.ANA	785	09.3830.05	180	09.3903.05A	176	09.3960.05A	178	09.4471.14CDA	729	09.4527.30C	663
09.3201.BZA	785	09.3830.14A	180	09.3903.14A	176	09.3960.14A	178	09.4471.30C	729	09.4527.30CDA	663
09.3310.01C	787	09.3830.18A	180	09.3903.18A	176	09.3960.18A	178	09.4471.30CDA	729	09.4840.14A	735
09.3310.04C	787	09.3830.40A	180	09.3903.40A	176	09.3960.40A	178	09.4472.14C	729	09.4840.14BDA	735
09.3310.72C	787	09.3830.CZA	180	09.3903.CZA	176	09.3960.CZA	178	09.4472.14CDA	729	09.4840.30A	735
09.3707.05C	724	09.3831.05	180	09.3910.05A	177	09.3961.05A	178	09.4472.30C	729	09.4840.30BDA	735
09.3707.14C	724	09.3831.14A	180	09.3910.14A	177	09.3961.14A	178	09.4472.30CDA	729	09.4841.14A	735
09.3707.30C	724	09.3831.18A	180	09.3910.18A	177	09.3961.18A	178	09.4480.14A	734	09.4841.14BDA	735
09.3708.05C	724	09.3831.40A	180	09.3910.40A	177	09.3961.40A	178	09.4480.30A	734	09.4841.30A	735
09.3708.14C	724	09.3831.CZA	180	09.3910.CZA	177	09.3961.CZA	178	09.4481.14C	734	09.4841.30BDA	735
09.3708.30C	724	09.3832.05	180	09.3911.05A	177	09.3962.05A	178	09.4481.30C	734	09.4842.14A	735
09.3710.05C	725	09.3832.14A	180	09.3911.14A	177	09.3962.14A	178	09.4482.14A	734	09.4842.14BDA	735
09.3710.14C	725	09.3832.18A	180	09.3911.18A	177	09.3962.18A	178	09.4482.30A	734	09.4842.30A	735
09.3710.30C	725	09.3832.40A	180	09.3911.40A	177	09.3962.40A	178	09.4483.14C	734	09.4842.30BDA	735
09.3711.05C	725	09.3832.CZA	180	09.3911.CZA	177	09.3962.CZA	178	09.4483.30C	734	09.4843.14C	735
09.3711.14C	725	09.3833.05	180	09.3912.05A	177	09.3963.05A	178	09.4484.14A	734	09.4843.14CDA	735
09.3711.30C	725	09.3833.14A	180	09.3912.14A	177	09.3963.14A	178	09.4484.30A	734	09.4843.30C	735
09.3750.05A	723	09.3833.18A	180	09.3912.18A	177	09.3963.18A	178	09.4485.14C	734	09.4843.30CDA	735
09.3750.14A	723	09.3833.40A	180	09.3912.40A	177	09.3963.40A	178	09.4485.30C	734	09.4844.14C	735
09.3750.30A	723	09.3833.CZA	180	09.3912.CZA	177	09.3963.CZA	178	09.4486.14C	734	09.4844.14CDA	735
09.3751.05A	723	09.3840.05	181	09.3913.05A	177	09.3964.05A	178	09.4486.30C	734	09.4844.30C	735

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
09.4844.30CDA	735	09.4916.14C	664	09.7213.40D78	293	09.7312.40A	738	09.7705.14C	731	09.7772.30CYU	733
09.4845.14C	735	09.4916.14CDA	664	09.7214.14D	293	09.7312.40A78	738	09.7705.14CDA	731	09.8220.AH	351
09.4845.14CDA	735	09.4916.30C	664	09.7214.40D	293	09.7313.14A	738	09.7705.30C	731	09.8220.DR	351
09.4845.30C	735	09.4916.30CDA	664	09.7214.40D78	293	09.7313.40A	738	09.7705.30C78	731	09.8220.DV	351
09.4845.30CDA	735	09.4917.14C	664	09.7215.14D	293	09.7313.40A78	738	09.7705.30CDA	731	09.8220.DW	351
09.4850.14C	735	09.4917.14CDA	664	09.7215.40D	293	09.7314.14A	738	09.7705.30CYU	731	09.8220.DX	351
09.4850.14CDA	735	09.4917.30C	664	09.7215.40D78	293	09.7314.40A	738	09.7706.14C	731	09.8220.DY	351
09.4850.30C	735	09.4917.30CDA	664	09.7216.14D	293	09.7314.40A78	738	09.7706.14CDA	731	09.8221.AH	351
09.4850.30CDA	735	09.4918.14C	664	09.7216.40D	293	09.7315.14A	738	09.7706.30C	731	09.8221.DR	351
09.4851.14C	735	09.4918.14CDA	664	09.7216.40D78	293	09.7315.40A	738	09.7706.30C78	731	09.8221.DV	351
09.4851.14CDA	735	09.4918.30C	664	09.7217.14D	293	09.7315.40A78	738	09.7706.30CDA	731	09.8221.DW	351
09.4851.30C	735	09.4918.30CDA	664	09.7217.40D	293	09.7316.14A	738	09.7706.30CYU	731	09.8221.DX	351
09.4851.30CDA	735	09.4919.14A	665	09.7217.40D78	293	09.7316.40A	738	09.7707.14C	731	09.8221.DY	351
09.4852.14C	735	09.4919.14BDA	665	09.7218.14D	293	09.7316.40A78	738	09.7707.14CDA	731	09.8222.AH	351
09.4852.14CDA	735	09.4919.30A	665	09.7218.40D	293	09.7317.14A	738	09.7707.30C	731	09.8222.DR	351
09.4852.30C	735	09.4919.30BDA	665	09.7218.40D78	293	09.7317.40A	738	09.7707.30C78	731	09.8222.DV	351
09.4852.30CDA	735	09.4920.14A	665	09.7270.14D	737	09.7317.40A78	738	09.7707.30CDA	731	09.8222.DW	351
09.4860.14A	730	09.4920.14BDA	665	09.7270.40D	737	09.7318.14A	738	09.7707.30CYU	731	09.8222.DX	351
09.4860.14BDA	730	09.4920.30A	665	09.7270.40D78	737	09.7318.40A	738	09.7708.14C	731	09.8222.DY	351
09.4860.30A	730	09.4920.30BDA	665	09.7271.14D	737	09.7318.40A78	738	09.7708.14CDA	731	09.8230.AH	351
09.4860.30BDA	730	09.4921.14A	665	09.7271.40D	737	09.7320.14A	758	09.7708.30C	731	09.8230.DR	351
09.4861.14A	730	09.4921.14BDA	665	09.7271.40D78	737	09.7320.40A	758	09.7708.30C78	731	09.8230.DV	351
09.4861.14BDA	730	09.4921.30A	665	09.7272.14D	737	09.7321.14A	758	09.7708.30CDA	731	09.8230.DW	351
09.4861.30A	730	09.4921.30BDA	665	09.7272.40D	737	09.7321.40A	758	09.7708.30CYU	731	09.8230.DX	351
09.4861.30BDA	730	09.4922.14C	665	09.7272.40D78	737	09.7322.14A	758	09.7750.14B	732	09.8230.DY	351
09.4862.14A	730	09.4922.14CDA	665	09.7273.14D	737	09.7322.40A	758	09.7750.14BDA	732	09.8231.AH	351
09.4862.14BDA	730	09.4922.30C	665	09.7273.40D	737	09.7323.14A	758	09.7750.30B	732	09.8231.DR	351
09.4862.30A	730	09.4922.30CDA	665	09.7273.40D78	737	09.7323.40A	758	09.7750.30B78	732	09.8231.DV	351
09.4862.30BDA	730	09.4923.14C	665	09.7274.14D	737	09.7324.14A	758	09.7750.30BDA	732	09.8231.DW	351
09.4863.14C	730	09.4923.14CDA	665	09.7274.40D	737	09.7324.40A	758	09.7750.30BYU	732	09.8231.DX	351
09.4863.14CDA	730	09.4923.30C	665	09.7274.40D78	737	09.7325.14A	758	09.7751.14C	732	09.8231.DY	351
09.4863.30C	730	09.4923.30CDA	665	09.7275.14D	737	09.7325.40A	758	09.7751.14CDA	732	09.8232.AH	351
09.4863.30CDA	730	09.4924.14C	665	09.7275.40D	737	09.7326.14A	758	09.7751.30C	732	09.8232.DR	351
09.4864.14C	730	09.4924.14CDA	665	09.7275.40D78	737	09.7326.40A	758	09.7751.30C78	732	09.8232.DV	351
09.4864.14CDA	730	09.4924.30C	665	09.7276.14D	737	09.7327.14A	758	09.7751.30CDA	732	09.8232.DW	351
09.4864.30C	730	09.4924.30CDA	665	09.7276.40D	737	09.7327.40A	758	09.7751.30CYU	732	09.8232.DX	351
09.4864.30CDA	730	09.4925.14C	665	09.7276.40D78	737	09.7328.14A	758	09.7752.14B	732	09.8232.DY	351
09.4865.14C	730	09.4925.14CDA	665	09.7277.14D	737	09.7328.40A	758	09.7752.14BDA	732	09.8300.AH	349
09.4865.14CDA	730	09.4925.30C	665	09.7277.40D	737	09.7373.14	739	09.7752.30B	732	09.8300.DR	349
09.4865.30C	730	09.4925.30CDA	665	09.7277.40D78	737	09.7373.40	739	09.7752.30B78	732	09.8300.DV	349
09.4865.30CDA	730	09.4926.14C	665	09.7278.14D	737	09.7373.40.78	739	09.7752.30BDA	732	09.8300.DW	349
09.4870.14C	730	09.4926.14CDA	665	09.7278.40D	737	09.7374.14	739	09.7752.30BYU	732	09.8300.DX	349
09.4870.14CDA	730	09.4926.30C	665	09.7278.40D78	737	09.7374.40	739	09.7753.3C78	732	09.8300.DY	349
09.4870.30C	730	09.4926.30CDA	665	09.7290.14D	757	09.7374.40.78	739	09.7753.14C	732	09.8301.AH	349
09.4870.30CDA	730	09.4927.14C	665	09.7290.40D	757	09.7375.14	739	09.7753.14CDA	732	09.8301.DR	349
09.4871.14C	730	09.4927.14CDA	665	09.7291.14D	757	09.7375.40	739	09.7753.30C	732	09.8301.DV	349
09.4871.14CDA	730	09.4927.30C	665	09.7291.40D	757	09.7375.40.78	739	09.7753.30CDA	732	09.8301.DW	349
09.4871.30C	730	09.4927.30CDA	665	09.7292.14D	757	09.7500.14A	295	09.7753.30CYU	732	09.8301.DX	349
09.4871.30CDA	730	09.4950.14A	736	09.7292.40D	757	09.7500.40A	295	09.7754.14B	732	09.8301.DY	349
09.4872.14C	730	09.4950.14BDA	736	09.7293.14D	757	09.7500.40A78	295	09.7754.14BDA	732	09.8302.AH	349
09.4872.14CDA	730	09.4950.30A	736	09.7293.40D	757	09.7501.14A	295	09.7754.30B	732	09.8302.DR	349
09.4872.30C	730	09.4950.30BDA	736	09.7294.14D	757	09.7501.40A	295	09.7754.30B78	732	09.8302.DV	349
09.4872.30CDA	730	09.4951.14A	736	09.7294.40D	757	09.7501.40A78	295	09.7754.30BDA	732	09.8302.DW	349
09.4880.14A	735	09.4951.30A	736	09.7295.14D	757	09.7504.14	739	09.7754.30BYU	732	09.8302.DX	349
09.4880.30A	735	09.4953.14C	736	09.7295.40D	757	09.7504.14.DA	739	09.7755.14C	732	09.8302.DY	349
09.4881.14C	735	09.4953.14CDA	736	09.7296.14D	757	09.7504.40	739	09.7755.14CDA	732	09.8310.AH	349
09.4881.30C	735	09.4953.30C	736	09.7296.40D	757	09.7504.40.78	739	09.7755.30C	732	09.8310.DR	349
09.4882.14A	735	09.4953.30CDA	736	09.7297.14D	757	09.7504.40.DA	739	09.7755.30C78	732	09.8310.DV	349
09.4882.30A	735	09.4954.14C	736	09.7297.40D	757	09.7504.40.YU	739	09.7755.30CDA	732	09.8310.DW	349
09.4883.14C	735	09.4954.30C	736	09.7298.14D	757	09.7505.14	739	09.7755.30CYU	732	09.8310.DX	349
09.4883.30C	735	09.4956.14C	736	09.7298.40D	757	09.7505.14.DA	739	09.7756.14C	732	09.8310.DY	349
09.4884.14A	735	09.4956.14CDA	736	09.7300.14B	294	09.7505.40	739	09.7756.14CDA	732	09.8311.AH	349
09.4884.30A	735	09.4956.30C	736	09.7300.40B	294	09.7505.40.78	739	09.7756.30C	732	09.8311.DR	349
09.4885.14C	735	09.4956.30CDA	736	09.7300.40B78	294	09.7505.40.DA	739	09.7756.30C78	732	09.8311.DV	349
09.4885.30C	735	09.4957.14C	736	09.7301.14B	294	09.7505.40.YU	739	09.7756.30CDA	732	09.8311.DW	349
09.4886.14C	735	09.4957.30C	736	09.7301.40B	294	09.7700.14A	731	09.7756.30CYU	732	09.8311.DX	349
09.4886.30C	735	09.4980.14	736	09.7301.40B78	294	09.7700.14CDA	731	09.7757.14C	732	09.8311.DY	349
09.4887.14C	735	09.4980.14ADA	736	09.7302.14B	294	09.7700.30A	731	09.7757.14CDA	732	09.8312.AH	349
09.4887.30C	735	09.4980.30	736	09.7302.40B	294	09.7700.30A78	731	09.7757.30C	732	09.8312.DR	349
09.4888.14C	735	09.4980.30ADA	736	09.7302.40B78	294	09.7700.30CDA	731	09.7757.30C78	732	09.8312.DV	349
09.4888.30C	735	09.4981.14	736	09.7303.14B	294	09.7700.30CYU	731	09.7757.30CDA	732	09.8312.DW	349
09.4910.14A	664	09.4981.14ADA	736	09.7303.40B	294	09.7701.14C	731	09.7757.30CYU	732	09.8312.DX	349
09.4910.14BDA	664	09.4981.30	736	09.7303.40B78	294	09.7701.14CDA	731	09.7758.14C	732	09.8312.DY	349
09.4910.30A	664	09.4981.30ADA	736	09.7304.14B	294	09.7701.30C	731	09.7758.14CDA	732	09.8405.05	340
09.4910.30BDA	664	09.4982.14	736	09.7304.40B	294	09.7701.30C78	731	09.7758.30C	732	09.8405.DR	340
09.4911.14A	664	09.4982.14ADA	736	09.7304.40B78	294	09.7701.30CDA	731	09.7758.30C78	732	09.8405.DY	340
09.4911.14BDA	664	09.4982.30	736	09.7305.14B	294	09.7701.30CYU	731	09.7758.30CDA	732	09.8405.GX	340
09.4911.30A	664	09.4982.30ADA	736	09.7305.40B	294	09.7702.14A	731	09.7758.30CYU	732	09.8405.MR	340
09.4911.30BDA	664	09.4983.14	736	09.7305.40B78	294	09.7702.14CDA	731	09.7770.14B	733	09.9070.14A	313
09.4912.14A	664	09.4983.30	736	09.7306.14B	294	09.7702.30A	731	09.7770.14BDA	733	09.9070.BWA	313
09.4912.14BDA	664	09.4984.14	736	09.7306.40B	294	09.7702.30A78	731	09.7770.30B	733	09.9071.14A	313
09.4912.30A	664	09.4984.30	736	09.7306.40B78	294	09.7702.30CDA	731	09.7770.30B78	733	09.9071.BWA	313
09.4912.30BDA	664	09.4985.14	736	09.7307.14B	294	09.7702.30CYU	731	09.7770.30BDA	733	09.9072.14A	313
09.4913.14C	664	09.4985.30	736	09.7307.40B	294	09.7703.14C	731	09.7770.30BYU	733	09.9072.BWA	313
09.4913.14CDA	664	09.7210.14D	293	09.7307.40B78	294	09.7703.14CDA	731	09.7771.14C	733	09.9075.14A	313
09.4913.30C	664	09.7210.40D	293	09.7308.14B	294	09.7703.30C	731	09.7771.14CDA	733	09.9075.BWA	313
09.4913.30CDA	664	09.7210.40D78	293	09.7308.40B	294	09.7703.30C78	731	09.7771.30C	733	09.9076.14A	313
09.4914.14C	664	09.7211.14D	293	09.7308.40B78	294	09.7703.30CDA	731	09.7771.30C78	733	09.9076.BWA	313
09.4914.14CDA	664	09.7211.40D	293	09.7310.14A	738	09.7703.30CYU	731	09.7771.30CDA	733	09.9077.14A	313
09.4914.30C	664	09.7211.40D78	293	09.7310.40A	738	09.7704.14A	731	09.7771.30CYU	733	09.9077.BWA	313
09.4914.30CDA	664	09.7212.14D	293	09.7310.40A78	738	09.7704.14CDA	731	09.7772.14C	733	09.9083.14A	314
09.4915.14C	664	09.7212.40D	293	09.7311.14A	738	09.7704.30A	731	09.7772.14CDA	733	09.9083.BWA	314
09.4915.14CDA	664	09.7212.40D78	293	09.7311.40A	738	09.7704.30A78	731	09.7772.30C	733	09.9084.14A	314
09.4915.30C	664	09.7213.14D	293	09.7311.40A78	738	09.7704.30CDA	731	09.7772.30C78	733	09.9084.BWA	314
09.4915.30CDA	664	09.7213.40D	293	09.7312.14A	738	09.7704.30CYU	731	09.7772.30CDA	733	09.9085.14A	314

QUICK SEARCH OF PRODUCT

Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page	Ref.	Page
09.9085.BWA	314	60.3051.11	790	60.8670	794	60.9826	800				
09.9086.14A	314	60.3051.11ADA	790	60.8703	802	60.9834.0500	798				
09.9086.BWA	314	60.3051.14	790	60.8711A	800	60.9834.0600	798				
09.9087.14A	314	60.3051.14ADA	790	60.8723	62	60.9834.0700	798				
09.9087.BWA	314	60.3051.29	790	60.8880	796	60.9834.0800	798				
09.9088.14A	314	60.3051.29ADA	790	60.8911	794	60.9834.0900	798				
09.9088.BWA	314	60.3053.11	789	60.8919	87	60.9834.1050	798				
60.3008.11	789	60.3053.14	789	60.8919	259	60.9843	799				
60.3008.14	789	60.3054	790	60.8919	315	60.9845	799				
60.3014.11	261	60.3057.11	789	60.9089	213	60.9874.0300	801				
60.3014.11	789	60.3057.29	789	60.9089	215	60.9874.0500	801				
60.3014.14	261	60.3083.29	789	60.9089	219	60.9880	802				
60.3014.14	789	60.3090.11A	789	60.9089	802	60.9881	803				
60.3016.11	790	60.3090.14A	789	60.9157	796	60.9938	204				
60.3016.12	790	60.3091.11	789	60.9160	797	60.9938	219				
60.3016.14	790	60.3091.14	789	60.9170	79	60.9949	800				
60.3018.11	789	60.3092.11	789	60.9170	87	60.9954.0300	801				
60.3018.14	789	60.3093.29	789	60.9170	315	60.9954.0500	801				
60.3022.11	790	60.3094.11	789	60.9188	795	60.9957	801				
60.3022.14	790	60.3094.14	789	60.9207	797	60.9957.0300	801				
60.3023.11	790	60.3095.29	789	60.9208	795	60.9957.0500	801				
60.3023.14	790	60.3096.29	789	60.9222	795	60.9958	798				
60.3023.29	790	60.3097.11	261	60.9233	794	60.9988	798				
60.3025.11	789	60.3097.11	310	60.9276	795	ATP0001A0EAB1	290				
60.3025.14	789	60.3097.11	789	60.9352	123	ATP0002A0EAB1	290				
60.3025.29	789	60.3097.14	261	60.9352	213	ATP0003A0EAB1	290				
60.3028.11	790	60.3097.14	310	60.9352	215	ATP0101A0EAB1	290				
60.3028.11ADA	790	60.3097.14	789	60.9352	219	ATP0102A0EAB1	290				
60.3028.14	790	60.3101.11	788	60.9352	802	ATP0103A0EAB1	290				
60.3028.14ADA	790	60.3101.11ADA	788	60.9352	827	ATP0104A0EAB1	290				
60.3028.29	790	60.3101.14	788	60.9374	182	ATP0105A0EAB1	290				
60.3028.29ADA	790	60.3101.14ADA	788	60.9374	204	ATP0106A0EAB1	290				
60.3029.11	790	60.3101.29	788	60.9379	800	ATP0201A0EAZZ	291				
60.3029.11ADA	790	60.3101.29ADA	788	60.9387	799	ATP0202A0EAB1	291				
60.3029.14	790	60.3102.11	788	60.9394	204	ATP0205A0EAB1	291				
60.3029.14ADA	790	60.3102.11ADA	788	60.9395	263	F0556020	779				
60.3029.29	790	60.3102.14	788	60.9405	796	F0557020	779				
60.3029.29ADA	790	60.3102.14ADA	788	60.9407	213	M8.0160.14	556				
60.3036.11	790	60.3102.29	788	60.9407	215	M8.0160.40	556				
60.3036.11ADA	790	60.3102.29ADA	788	60.9407	219	M8.0161.14	557				
60.3036.14	790	60.3103.11	788	60.9407	802	M8.0161.40	557				
60.3036.14ADA	790	60.3103.11ADA	788	60.9408	800	M8.0164.14	556				
60.3036.29	790	60.3103.14	788	60.9414	799	M8.0164.40	556				
60.3036.29ADA	790	60.3103.14ADA	788	60.9421	796	M8.0165.14	557				
60.3037.11	790	60.3103.29	788	60.9439	797	M8.0165.40	557				
60.3037.11ADA	790	60.3103.29ADA	788	60.9443	182	M8.0166.00	556				
60.3037.14	790	60.3104.11	788	60.9443	204	M8.0167.00	557				
60.3037.14ADA	790	60.3104.11ADA	788	60.9443	827	M8.0192.00	556				
60.3037.29	790	60.3104.14	788	60.9467	798	M8.0193.00	557				
60.3037.29ADA	790	60.3104.29	788	60.9483	797	RF25965	341				
60.3038.11	789	60.3104.29ADA	788	60.9515	182	RF27576	341				
60.3038.11ADA	789	60.3145.11	789	60.9515	204	SA.1006.4.300	821				
60.3038.12	789	60.3145.14	789	60.9515	802	SA.1006.5E110	821				
60.3038.12ADA	789	60.3146.11	789	60.9516	182	SA.1006.6E100	821				
60.3038.14	789	60.3146.14	789	60.9516	204	SA.1007.5E110	821				
60.3038.14ADA	789	60.3810.11	788	60.9516	802	SA.1007.6E100	821				
60.3039.11	789	60.3810.11ADA	788	60.9592	794	SA.1008.4.300	822				
60.3039.11ADA	789	60.3810.14	788	60.9601	796	SA.1008.5E110	822				
60.3039.12	789	60.3810.14ADA	788	60.9602	799	SA.1008.6E100	822				
60.3039.12ADA	789	60.3810.29	788	60.9604	797	SA.1009.4.300	822				
60.3039.14	789	60.3810.29ADA	788	60.9607	79	SA.1009.5E110	822				
60.3039.14ADA	789	60.3820.11	788	60.9607	87	SA.1009.6E100	822				
60.3043.11	790	60.3820.11ADA	788	60.9607	259	SA.1010.4.300	822				
60.3043.11ADA	790	60.3820.14	788	60.9607	315	SA.1010.5E110	822				
60.3043.14	790	60.3820.14ADA	788	60.9658	826	SA.1010.6E100	822				
60.3043.14ADA	790	60.3820.29	788	60.9677A	204	SA.1011.5E110	823				
60.3043.29	790	60.3820.29ADA	788	60.9678A	219	SA.1011.6E100	823				
60.3043.29ADA	790	60.3830.11	788	60.9678A	263	SA.1034.3.116	820				
60.3044.11	790	60.3830.11ADA	788	60.9681	802	SA.1039.1	820				
60.3044.11ADA	790	60.3830.14	788	60.9683	802	SA.1040.1	820				
60.3044.12	790	60.3830.14ADA	788	60.9692	799	SA.1050.1	588				
60.3044.12ADA	790	60.3830.29	788	60.9705A	35	SA.1051.1	588				
60.3044.14	790	60.3830.29ADA	788	60.9705A	123	SA.1052.1	589				
60.3044.14ADA	790	60.7661	800	60.9705A	803	SA.3010.1C	823				
60.3046.11	790	60.7677	795	60.9713.0200	798	SA.3013.1C	824				
60.3046.14	790	60.7678	797	60.9713.0300	798	SA.3014.1B	824				
60.3046.29	790	60.7709	797	60.9713.0400	798	SA.3015.1C	824				
60.3047.11	790	60.7773	800	60.9713.0500	798	SA.3016.1C	825				
60.3047.11ADA	790	60.7774	801	60.9713.0600	798	SA.5000.1	817				
60.3047.14	790	60.7785	801	60.9713.0700	798	SA.5001.1	817				
60.3047.14ADA	790	60.7887	801	60.9713.0800	798	SA.5006.1F	817				
60.3047.29	790	60.8079	796	60.9713.0900	798	SA.5007.1F	817				
60.3047.29ADA	790	60.8268	802	60.9713.1050	798	SA.5100.1A	819				
60.3048.11	790	60.8268	827	60.9741	62	SA.5101.1A	819				
60.3048.11ADA	790	60.8311	803	60.9744	796	SA.5102.1A	819				
60.3048.14	790	60.8364	803	60.9746	795	SA.5200.5.120	815				
60.3048.14ADA	790	60.8437	794	60.9766	785	SA.5201.5.120	815				
60.3048.29	790	60.8529A	796	60.9766	819	SA.5202.5.120	815				
60.3048.29ADA	790	60.8530	794	60.9768	800	SA.5203.5.120	815				
60.3049.11	790	60.8533	794	60.9777A	35	SA.6600.1	678				
60.3049.11ADA	790	60.8534	796	60.9777A	123						
60.3049.14	790	60.8640	785	60.9777A	182						
60.3049.14ADA	790	60.8640	819	60.9777A	204						
60.3049.29	790	60.8650	794	60.9777A	803						
60.3049.29ADA	790	60.8655	794	60.9781	62						

DISTRIBUTION

BELGIUM
AND LUXEMBOURG
Flos Belux
M +32 474 739 080
flosbelux@flos.com

NORWAY
Drammensveien 120
0277 Oslo - Norway
Tel +47 2212 86 00
Fax +47 2212 86 08
info.norge@flos.com

SWEDEN
FLOS Sweden
Lützengatan 1
11520 Stockholm
Sweden
Tel +4686604405
info.se@flos.com

DENMARK
FLOS Scandinavia A/S
Kuglegaardsvej 13-17
1434 Copenhagen K
Denmark
Tel +4533886000
info.dk@flos.com

AMSTERDAM
Cruquiusweg 109S
1019 AG Amsterdam
The Netherlands
Tel +31 (0) 20 560 50 60
flosnetherlands@flos.com

FRANCE
Flos France
20-22, Passage Dauphine
75006 Paris
Tel +33 (0) 1 40 64 17 44
flos.france@flos.com

AUSTRIA - GERMANY
SWITZERLAND
Flos GmbH
Große Brinkgasse 26-28
50672 Köln, Germany
Tel. +49 221 37 99 46 0
backoffice.gmbh@flos.com

UNITED KINGDOM
Atrium Ltd.
28 Leonard Street
EC2A 4BY London
Tel +44 (0) 20 7681 9933
Fax +44 (0) 20 7681 9943
flos@atrium.ltd.uk

UNITED KINGDOM
International Projects
Boccia Giandonato
tel +44(0)20 7681 9933
giandonato.boccia@flos.com

DISTRIBUTION

JAPAN
Flos Japan K.K.
Hulic Aoyama 2nd Bldg 2F
1-3-3 Shibuya Shibuya-ku
Tokyo - Japan
Tel: +81 (0)3 6421 0840
flos.japan@flos.com

ASIA PACIFIC
Flos Representative Office
Antares Iluminacion Pte Ltd
50 Raffles Place, #30-00
Singapore Land Tower
Singapore 048623
+6590056328
+6591267780

CHINA
Flos Illumination
(Shanghai) Co. Ltd.
Unit 101, Floor 1, Building B9
No. 800 of Chang De road
Jing An District, Shanghai,
200040, China
Tel +86 021 62176187
floschina@flos.com
(South China)
Tel +86 1392 9975 703
alan.wong@flos.com

LATIN AMERICA
Flos LatAm
M +52 55 6960 1772
flos.latinoamerica@flos.com

INDIA
Flos Representative Office
1, Commonwealth Lane
#08-12, 149544 Singapore
Tel +91 9999306667
Fax +65 (0) 6372 7607
flosindia@flos.com

U.S.A.
Flos USA Inc.
40-20 22nd Street - 3rd Floor
Long Island City, NY 11101
Tel +1 (800) 841 4011
info@flosusa.com

MIDDLE EAST
Antares Iluminacion S.A.
Dubai Design District
Building 1B, Office 303
P.O.Box number 333025
Dubai, United Arab Emirates
Tel: +971 4 566 0123
Mob: +971 543567356

HONG KONG
M +852 9307 3713
flosasia@flos.com

SHOWROOMS

STOCKHOLM
FLOS Sweden
Lützengatan 1
11520 Stockholm
Sweden
Tel +4686604405
info.se@flos.com

COPENHAGEN
FLOS Scandinavia A/S
Kuglegaardsvej 13-17
1434 Copenhagen K
Denmark
Tel +4533886000
info.dk@flos.com

AMSTERDAM
Cruquiusweg 109S
1019 AG Amsterdam
The Netherlands
Tel +31 (0) 20 560 50 60
showroom.amsterdam@flos.com

OSLO
Drammensveien 120
0277 Oslo - Norway
Tel +47 (0) 2212 86 00
Fax +47 (0) 2212 86 08
info.norge@flos.com

MILANO
Corso Monforte, 15
20122 Milano
Tel +39 02 79 84 57
Fax +39 02 89 78 56 41
showroom.milan@flos.com

PARIS
20-22, Passage Dauphine
75006 Paris
Tel +33 (0) 1 40 64 17 44
flos.france@flos.com

TOKYO
PMC Building 8F
1-23-5 Higashiazabu
Minato-Ku
Tokyo 104-0044
Tel: +81 (0)3 3582 1468
Fax: +81 (0)3 3582 0974
showroom.tokyo@flos.com

FLAGSHIP STORES

MILANO
Corso Monforte, 9
20122 - Milano
Tel +39 02 37011080
Fax +39 02 780833
shop.milan@flos.com

ROMA
Via del Babuino, 85
00187 - Roma
Tel +39 06 3207631
Fax +39 06 3207690
flosroma@flos.com

NEW YORK
135 Madison Ave
New York, NY 10016
Tel +1 212 941 4760
Fax +1 212 941 4763
info@flosusa.com

PARIS
15, Rue de Bourgogne
75007 - Paris
Tel +33 (0) 1 53 85 49 93
Fax +33 (0) 1 53 85 49 99
flosparis@flos.com

LYON
17 Rue Jarente
69002 - Lyon
Tel +33 478621301
Fax +33 478622119
floslyon@flos.com

STOCKHOLM
FLOS Sverige
Lützengatan 1
11520 Stockholm
Sweden
Tel +46086604405
info.se@flos.com

COLOPHON

CONTACT

ITALY
Flos Spa
Via Angelo Faini, 2
25073 Bovezzo (Brescia)
Tel +39 0302438.1
Fax +39 0302438.250
info@flos.com

SPAIN
Antares Iluminación S.A.U.
Calle Mallorca, 1
Polígono Industrial Reva
46394 Ribarroja (Valencia)
Tel +34 96 166 95 20
Fax +34 96 166 82 86
flos.architectural@flos.com

CREDITS

ART DIRECTION
Apartamento Studios

GRAPHIC DESIGN
Apartamento Studios

PHOTO PRODUCT / RENDERING
Piero Fasanotto
Jorge Herrera
Mozing Studio
Salvador Martín

LAYOUT
Flos Architectural Team

PRODUCT INFORMATION UPDATE
02-02-2026

EDITION
02-02-2026

Copyright © Flos 2026
All rights reserved

As our world is in constant evolution, technical upgrades happens every day in our business.

Flos aim is to offer always the best reliable technology available, constantly reviewing our products and upgrading them as soon as technologic evolutions offers benefits for our partners and clients.

This philosophy means that our technical catalogue and product data sheets also are in constant evolution, requiring upgrades and constants reviewing.

Thus, when you need technical details and the most recent product information, please browse the product section of our Flos.com official website: it is updated daily, and there you'll find the latest product details, all available part numbers, all product documents available for immediate download.

Nuestro mundo está en constante evolución. Diariamente se presentan avances técnicos en nuestro sector.

El objetivo de Flos es ofrecer siempre la mejor tecnología disponible, revisando nuestros productos constantemente y mejorándolos tan pronto como la evolución tecnológica ofrezca ventajas para nuestros socios y clientes.

Esta filosofía implica que nuestro catálogo y nuestras fichas técnicas de producto también se encuentren en constante evolución y requieran mejoras y revisiones constantes.

Por tanto, si necesita consultar detalles técnicos y la información más reciente, diríjase a la sección de productos de nuestra página web oficial Flos.com: se actualiza a diario y en ella encontrará los últimos detalles sobre los productos, los códigos de los artículos disponibles y los documentos para su descarga inmediata.

www.flos.com

WORKING CATALOGUE 2026

THE GLOWING TRACK , MY CIRCUIT, BELT, INFRA-STRUCTURE, GUSTAVE, EMI, OBLIQUE, ZERO TRACK PRO , ZERO TRACK, THE MICRO RUNNING MAGNET, THE RUNNING MAGNET, THE TRACKING MAGNET, THE TRACKING POWER EVO, THE FAST TRACK, WORKMATES, LIGHT SHADOW MINI, LIGHT SHADOW, LIGHT SHADOW DOTS & PRO, ECLECTIC, LIGHT SHADOW SPOT, MY SPOT, SUPER LINE &, SUPERLINE PRO, KAP, C1, FIND ME, UT , BON JOUR, FORT KNOX, IN-FINITY, CIRCLE OF LIGHT, LIGHT CUT MINI, LIGHT BELL, THIN LED, LIGHT SUPPLY, JOHNNY, WAN , G-O, THEBLOCKOFLIGHT, JUNCOS, SOFT SPUN, ABAJOURD'HUI, USO, USO COVE LIGHTING, G-O IN, TEARDROP, ROUND, SQUARE & VERTICAL LIGHT

FLOS.COM