



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Description

The new Tracking Magnet 48V system is creative, flexible, reliable and precise. Accent luminaires are installed by a magnetic fastening system and a secondary mechanical fastener. The range of luminaires is composed of accent illumination modules with different optics and linear luminaires with the Flos signature design. The Tracking Magnet is available in recessed, surface, or pendant mounted applications, making it an option in even the most varied of job conditions. Vertical and horizontal corners complete the system. The Tracking Magnet is perfect for retail displays where frequent changes are typical and absolute performance is required.

Lamp

System Lamp Type	LED
Color Temperature	2700K, 3000K, *3500K, *4000K (See Notes)
Color Rendering	CRI90
Application	General Lighting / Accent lighting


Physical

Material	Aluminum
Ingress Protection Rating	IP20
Finishes	<input type="checkbox"/> 40 White <input checked="" type="checkbox"/> 14 White <input type="checkbox"/> 05 Chrome
Installation type	Ceiling Surface
Environment	Indoor
Field cuttable	No

Electrical & Control

Driver location	Remote
Driver Input Voltage	120V-277V
Driver Output Voltage	48V
Maximum Driver Wattage	Class 2 - 96W
Control	Standard 0-10V dimming / DALI / On board
Nº Circuit	1 circuit

Suspended Installation



Light Modules



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Notes

EC to supply site cabling from driver to track location.

Wattage per linear foot is dependent upon quantity and type of light modules used.


Spots and linear luminaires available with individually addressable DALI-Wireless circuitry, 0-10V (from 10% up to 100%) Dimming

0-10V Fixtures come from the factory set up at the lowest level 10% they always required a 0-10V signal to achieve the maximum output.

All linear profiles are field cuttable.

3500K , 4000K and other CCT available but not cataloged. Consult factory for additional color temperatures.

Suspended Installation



Light Modules



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.

How To Specify

A. Select and position corners

1. Horizontal - Connect sections on flat surfaces (90° corner)
2. Inside - Transition from wall to ceiling (inside corner)
3. External - Turn outside corners for walls and soffits (270° corner)

B. Fill lengths between corners with Linear Housings


Select dimmable (DALI-FLOS Smart control and 0-10V fixtures) or non dimmable track (Built-in dimmer fixtures). Available section lengths are 3.3', 4.9', 6.7' or 8.2'. Profile can be easily cut to site to exact length and joined together.

C. Drivers

Quantity of drivers determined by total wattage or light elements in section (total maximum possible per linear foot is 29W). Maximum driver distance is 15'. Locate drivers nearby.

D. Select Spot heads


Light Strips are available in three nominal lengths: 11.8", 23.6", 35.4", 47.2" and 59". Individual Spots are Spot 50, Spot 90, Spot 120, Spot 150 and Anthony.



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Track



How to specify: 06.5070.14

Length	Part Number	Delivered Lumens	Finish	Dimming Protocol
39.4" (1m)	06.5070	465 lm	<div><input type="checkbox"/> 40 = White</div> <div><input checked="" type="checkbox"/> 14 = Black</div> <div><input checked="" type="checkbox"/> 05 = Chrome</div>	Dimmable on Board
59" (1.5m)	06.5071	697.5 lm		
78.7" (2m)	06.5072	930 lm		
98.4" (2.5m)	06.5073	1162.5 lm		

Note: Track can be cut to different lengths in field

How to specify: 06.5070.14

Length	Part Number	Delivered Lumens	Finish	Dimming Protocol
39.4" (1m)	06.5020	465 lm	<div><input type="checkbox"/> 40 = White</div> <div><input checked="" type="checkbox"/> 14 = Black</div> <div><input checked="" type="checkbox"/> 05 = Chrome</div>	1-10V, 10% Dimming DALI, 10% Dimming
59" (1.5m)	06.5021	697.5 lm		
78.7" (2m)	06.5022	930 lm		
98.4" (2.5m)	06.5023	1162.5 lm		

Note: Track can be cut to different lengths in field

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Corners


90° horizontal ceiling mechanical corner available. In order to create electrical continuity the flexible intermediate connector is required.

Mechanical corner 90° horizontal

*no up light on the corner

Part Number:

- 06.5025.14
- 06.5025.40
- 06.5025.05




The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Connectors

Feed connector for Tracking Magnet Suspension Up&Down includes: 1 feed connector, 1 transparent feed cable 4m - 13ft. Includes begining and end fixing ceiling kit. Suspension cable or rigid Rod not included.

Part Number:
08.0626.00




Intermediate connector for Tracking Magnet Suspension Up&Down

Part Number:
08.0627.00



Flexible/Electrical Intermediate Corner for Tracking Magnet suspension if electrical continuity on corners is required.

Part Number:
08.0614.14



*Intermediate connectors to be ordered separately if electrical continuity on corners is required.

The Tracking Magnet EVO Suspension Up&Down


High-tech LED lighting system for interior architecture

Dimming controllers

Dimming Control Unit Box 48V
0-10V Required for a 0-10V Dimming
installation. 1 Dimming control can
control up to 20 fixtures

Part Number:








■ 08.0613.14A



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Required Accesories













Fixed Ceiling Kit (2 units)	End Cap kit (2 units)	Suspension steel cable, lenght 4m (13ft) Recommended where tilting will not occur in any case.
Part Number: 08.0616.00	Part Number: <input checked="" type="checkbox"/> 06.5017.14 <input type="checkbox"/> 06.5017.40 <input checked="" type="checkbox"/> 06.5017.05	Part Number: 08.8634.00
		
Suspension rod with rose, lenght 1m (3.3ft) M6 thread. Rigid rod to avoid the profile from tilting to be installed in places where a more rigid fixing system is required.	Suspension rod extension, lenght 1m(3.3ft) M6 thread. Rigid rod to avoid the profile from tilting to be installed in places where a more rigid fixing system is required.	Cover Plate 4" Junction Box Cover Plate for Remote Installation.
Part Number: <input checked="" type="checkbox"/> 60.3014.14 <input type="checkbox"/> 60.3014.11	Part Number: <input checked="" type="checkbox"/> 60.3097.14 <input type="checkbox"/> 60.3097.11	Part Number: <input checked="" type="checkbox"/> RM -C -B (Black) <input type="checkbox"/> RM -C -W (White)
		 

Profile	Minimum qty fixing points depending on track length
39.37" / 59.06" [1000 mm/ 1500 mm]	2
78.74" / 98.42" [2000 mm/ 2500 mm]	3

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Required Drivers

<p>LED power supply source for remote installation, 48V/96W, 120-277V, UL Listed</p> <p>Part Number:</p> <p>LEDSB96W48V-NDM-U0</p>  	<p>LED power supply source for remote installation, 48V/60W, 120-277V, UL Listed</p> <p>Part Number:</p> <p>LEDSB60W48V-NDM-U01</p>  	<p>LED power supply source for remote installation, 48V/30W, 120-277V, UL Listed</p> <p>Part Number:</p> <p>LEDSB40W48V-NDM-U01</p>  
<p>LED power supply source for remote installation, 48V/96W, 120-277V, UL Listed</p> <p>Part Number:</p> <p>LEDSB96W48V-NDM-D01</p>  	<p>LED power supply source for remote installation, 48V/60W, 120-277V, UL Listed</p> <p>Part Number:</p> <p>LEDSB60W48V-NDM-D01</p>  	<p>LED power supply source for remote installation, 48V/30W, 120-277V, UL Listed</p> <p>Part Number:</p> <p>LEDSB30W48V-NDM-D01</p>  

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture


Surface mounted canopies

<p>Surface mount canopy Non Dimmable for Tracking Magnet SuspensionUp&Down includes: 1 drivers downlight: 96W, 48V, 120-277V</p> <p>Part Number:</p> <p>08U4806.14</p> <p>08U4806.40</p>	<p>Surface mount canopy Non Dimmable for Tracking Magnet Suspension Down includes: 1 driver downlight: 60W, 48V, 120-277V</p> <p>Part Number:</p> <p>08U4807.14</p> <p>08U4807.40</p>	<p>Surface mount canopy Dimmable for Tracking Magnet Suspension Down includes: 1 driver downlight: 96W, 48V, 120-277V 1 Dimming Control Unit Box: 08.0613.14A</p> <p>Part Number:</p> <p>08U4806.14.1V</p> <p>08U4806.40.1V</p>
<p>Surface mount canopy Dimmable for Tracking Magnet Suspension Down includes: 1 driver downlight: 60W, 48V, 120-277V 1 Dimming Control Unit Box: 08.0613.14A</p> <p>Part Number:</p> <p>08U4807.40.1V</p> <p>08U4807.14.1V</p>		


The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

How to specify



Spot 50



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric														
3000	90	307	212	3.5	26°	03.8033	<div><div></div>40 = White</div> <div><div></div>14 = Black</div> <div><div></div>05 = Chrome</div>	A Dimmable on Board AIV = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div><p>Luminous flux luminaire 212 lm</p></div> <div><table><tr><th>E(h)</th><th>D(m)</th></tr><tr><td>h(m)</td><td>26°</td></tr><tr><td>1</td><td>1012 0.47</td></tr><tr><td>2</td><td>253 0.94</td></tr><tr><td>3</td><td>112 1.41</td></tr><tr><td>4</td><td>63 1.88</td></tr><tr><td>5</td><td>40 2.35</td></tr></table></div>	E(h)	D(m)	h(m)	26°	1	1012 0.47	2	253 0.94	3	112 1.41	4	63 1.88	5	40 2.35
E(h)	D(m)																						
h(m)	26°																						
1	1012 0.47																						
2	253 0.94																						
3	112 1.41																						
4	63 1.88																						
5	40 2.35																						
2700	90	286	205	3.5	26°	03.8032			<div><p>Luminous flux luminaire 205 lm</p></div> <div><table><tr><th>E(h)</th><th>D(m)</th></tr><tr><td>h(m)</td><td>26°</td></tr><tr><td>1</td><td>977 0.47</td></tr><tr><td>2</td><td>244 0.94</td></tr><tr><td>3</td><td>109 1.41</td></tr><tr><td>4</td><td>61 1.88</td></tr><tr><td>5</td><td>39 2.35</td></tr></table></div>	E(h)	D(m)	h(m)	26°	1	977 0.47	2	244 0.94	3	109 1.41	4	61 1.88	5	39 2.35
E(h)	D(m)																						
h(m)	26°																						
1	977 0.47																						
2	244 0.94																						
3	109 1.41																						
4	61 1.88																						
5	39 2.35																						


Included Accessories Spot 50



Cross Baffle	Honeycomb

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Spot 90



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric														
3000	90	656	443	8.5	14°	03.8043	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div><table><tr><td>E(lx)</td><td>D(m)</td></tr><tr><td>h(m)</td><td>14°</td></tr><tr><td>1</td><td>5805 0.25</td></tr><tr><td>2</td><td>1451 0.49</td></tr><tr><td>3</td><td>645 0.74</td></tr><tr><td>4</td><td>363 0.98</td></tr><tr><td>5</td><td>232 1.23</td></tr></table><div>Luminous flux luminaire 443 lm</div></div>	E(lx)	D(m)	h(m)	14°	1	5805 0.25	2	1451 0.49	3	645 0.74	4	363 0.98	5	232 1.23
E(lx)	D(m)																						
h(m)	14°																						
1	5805 0.25																						
2	1451 0.49																						
3	645 0.74																						
4	363 0.98																						
5	232 1.23																						
2700	90	610	428	8.5	14°	03.8042	<div><table><tr><td>E(lx)</td><td>D(m)</td></tr><tr><td>h(m)</td><td>14°</td></tr><tr><td>1</td><td>5601 0.25</td></tr><tr><td>2</td><td>1400 0.49</td></tr><tr><td>3</td><td>622 0.74</td></tr><tr><td>4</td><td>350 0.98</td></tr><tr><td>5</td><td>224 1.23</td></tr></table><div>Luminous flux luminaire 428 lm</div></div>	E(lx)	D(m)	h(m)	14°	1	5601 0.25	2	1400 0.49	3	622 0.74	4	350 0.98	5	224 1.23		
E(lx)	D(m)																						
h(m)	14°																						
1	5601 0.25																						
2	1400 0.49																						
3	622 0.74																						
4	350 0.98																						
5	224 1.23																						
3000	90	656	406	8.5	22°	03.8045	<div><table><tr><td>E(lx)</td><td>D(m)</td></tr><tr><td>h(m)</td><td>22°</td></tr><tr><td>1</td><td>2403 0.38</td></tr><tr><td>2</td><td>601 0.77</td></tr><tr><td>3</td><td>267 1.15</td></tr><tr><td>4</td><td>150 1.54</td></tr><tr><td>5</td><td>96 1.92</td></tr></table><div>Luminous flux luminaire 406 lm</div></div>	E(lx)	D(m)	h(m)	22°	1	2403 0.38	2	601 0.77	3	267 1.15	4	150 1.54	5	96 1.92		
E(lx)	D(m)																						
h(m)	22°																						
1	2403 0.38																						
2	601 0.77																						
3	267 1.15																						
4	150 1.54																						
5	96 1.92																						
2700	90	610	392	8.5	22°	03.8044	<div><table><tr><td>E(lx)</td><td>D(m)</td></tr><tr><td>h(m)</td><td>22°</td></tr><tr><td>1</td><td>2319 0.38</td></tr><tr><td>2</td><td>580 0.77</td></tr><tr><td>3</td><td>258 1.15</td></tr><tr><td>4</td><td>145 1.54</td></tr><tr><td>5</td><td>93 1.92</td></tr></table><div>Luminous flux luminaire 392 lm</div></div>	E(lx)	D(m)	h(m)	22°	1	2319 0.38	2	580 0.77	3	258 1.15	4	145 1.54	5	93 1.92		
E(lx)	D(m)																						
h(m)	22°																						
1	2319 0.38																						
2	580 0.77																						
3	258 1.15																						
4	145 1.54																						
5	93 1.92																						


Included Accessories Spot 90


Cross Baffle	Honeycomb

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Spot 120 Power LED



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric														
3000	90	779	558	12	11°	03.8053	<div><input type="checkbox"/> 40 = White</div> <div><input checked="" type="checkbox"/> 14 = Black</div> <div><input type="checkbox"/> 05 = Chrome</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	 <table><thead><tr><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>h(m)</td><td>17°</td></tr><tr><td>1</td><td>4780 0.31</td></tr><tr><td>2</td><td>1195 0.61</td></tr><tr><td>3</td><td>531 0.92</td></tr><tr><td>4</td><td>299 1.23</td></tr><tr><td>5</td><td>191 1.53</td></tr></tbody></table> <p>Luminous flux luminaire 887 lm</p>	E(lx)	D(m)	h(m)	17°	1	4780 0.31	2	1195 0.61	3	531 0.92	4	299 1.23	5	191 1.53
E(lx)	D(m)																						
h(m)	17°																						
1	4780 0.31																						
2	1195 0.61																						
3	531 0.92																						
4	299 1.23																						
5	191 1.53																						
2700	90	724	539	12	11°	03.8052	 <table><thead><tr><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>h(m)</td><td>17°</td></tr><tr><td>1</td><td>4547 0.31</td></tr><tr><td>2</td><td>1137 0.61</td></tr><tr><td>3</td><td>505 0.92</td></tr><tr><td>4</td><td>284 1.23</td></tr><tr><td>5</td><td>182 1.53</td></tr></tbody></table> <p>Luminous flux luminaire 854 lm</p>	E(lx)	D(m)	h(m)	17°	1	4547 0.31	2	1137 0.61	3	505 0.92	4	284 1.23	5	182 1.53		
E(lx)	D(m)																						
h(m)	17°																						
1	4547 0.31																						
2	1137 0.61																						
3	505 0.92																						
4	284 1.23																						
5	182 1.53																						
3000	90	779	505	12	17°	03.8055	 <table><thead><tr><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>h(m)</td><td>40°</td></tr><tr><td>1</td><td>1437 0.73</td></tr><tr><td>2</td><td>359 1.45</td></tr><tr><td>3</td><td>160 2.18</td></tr><tr><td>4</td><td>90 2.91</td></tr><tr><td>5</td><td>57 3.64</td></tr></tbody></table> <p>Luminous flux luminaire 829 lm</p>	E(lx)	D(m)	h(m)	40°	1	1437 0.73	2	359 1.45	3	160 2.18	4	90 2.91	5	57 3.64		
E(lx)	D(m)																						
h(m)	40°																						
1	1437 0.73																						
2	359 1.45																						
3	160 2.18																						
4	90 2.91																						
5	57 3.64																						
2700	90	724	487	12	17°	03.8054	 <table><thead><tr><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>h(m)</td><td>40°</td></tr><tr><td>1</td><td>1367 0.73</td></tr><tr><td>2</td><td>342 1.45</td></tr><tr><td>3</td><td>152 2.18</td></tr><tr><td>4</td><td>85 2.91</td></tr><tr><td>5</td><td>55 3.64</td></tr></tbody></table> <p>Luminous flux luminaire 599 lm</p>	E(lx)	D(m)	h(m)	40°	1	1367 0.73	2	342 1.45	3	152 2.18	4	85 2.91	5	55 3.64		
E(lx)	D(m)																						
h(m)	40°																						
1	1367 0.73																						
2	342 1.45																						
3	152 2.18																						
4	85 2.91																						
5	55 3.64																						

Included Accessories Spot 90

Cross Baffle




Honeycomb







The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Spot 120 LED ARRAY



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric														
3000	90	1138	687	12.5	17°	03.8155	<div>40 = White</div> <div>14 = Black</div> <div>05 = Chrome</div>	<div>Dimmable on Board</div> <div>1V = 0-10V, 10% Dimming</div> <div>DA = DALI, 10% Dimming</div>	<div><table><tr><th>E(x)</th><th>D(m)</th></tr><tr><td>h(m)</td><td>17°</td></tr><tr><td>1</td><td>4780 0.31</td></tr><tr><td>2</td><td>1195 0.61</td></tr><tr><td>3</td><td>531 0.92</td></tr><tr><td>4</td><td>299 1.23</td></tr><tr><td>5</td><td>191 1.53</td></tr></table><div>Luminous flux luminaire 687 lm</div></div>	E(x)	D(m)	h(m)	17°	1	4780 0.31	2	1195 0.61	3	531 0.92	4	299 1.23	5	191 1.53
E(x)	D(m)																						
h(m)	17°																						
1	4780 0.31																						
2	1195 0.61																						
3	531 0.92																						
4	299 1.23																						
5	191 1.53																						
2700	90	1075	654	12.5	17°	03.8154	<div><table><tr><th>E(x)</th><th>D(m)</th></tr><tr><td>h(m)</td><td>17°</td></tr><tr><td>1</td><td>4547 0.31</td></tr><tr><td>2</td><td>1137 0.61</td></tr><tr><td>3</td><td>505 0.92</td></tr><tr><td>4</td><td>284 1.23</td></tr><tr><td>5</td><td>182 1.53</td></tr></table><div>Luminous flux luminaire 654 lm</div></div>	E(x)	D(m)	h(m)	17°	1	4547 0.31	2	1137 0.61	3	505 0.92	4	284 1.23	5	182 1.53		
E(x)	D(m)																						
h(m)	17°																						
1	4547 0.31																						
2	1137 0.61																						
3	505 0.92																						
4	284 1.23																						
5	182 1.53																						
3000	90	1138	629	12.5	40°	03.8157	<div><table><tr><th>E(x)</th><th>D(m)</th></tr><tr><td>h(m)</td><td>40°</td></tr><tr><td>1</td><td>1437 0.73</td></tr><tr><td>2</td><td>359 1.45</td></tr><tr><td>3</td><td>160 2.18</td></tr><tr><td>4</td><td>90 2.91</td></tr><tr><td>5</td><td>57 3.64</td></tr></table><div>Luminous flux luminaire 629 lm</div></div>	E(x)	D(m)	h(m)	40°	1	1437 0.73	2	359 1.45	3	160 2.18	4	90 2.91	5	57 3.64		
E(x)	D(m)																						
h(m)	40°																						
1	1437 0.73																						
2	359 1.45																						
3	160 2.18																						
4	90 2.91																						
5	57 3.64																						
2700	90	1075	599	12.5	40°	03.8156	<div><table><tr><th>E(x)</th><th>D(m)</th></tr><tr><td>h(m)</td><td>40°</td></tr><tr><td>1</td><td>1367 0.73</td></tr><tr><td>2</td><td>342 1.45</td></tr><tr><td>3</td><td>152 2.18</td></tr><tr><td>4</td><td>85 2.91</td></tr><tr><td>5</td><td>55 3.64</td></tr></table><div>Luminous flux luminaire 599 lm</div></div>	E(x)	D(m)	h(m)	40°	1	1367 0.73	2	342 1.45	3	152 2.18	4	85 2.91	5	55 3.64		
E(x)	D(m)																						
h(m)	40°																						
1	1367 0.73																						
2	342 1.45																						
3	152 2.18																						
4	85 2.91																						
5	55 3.64																						

Included Accessories Spot 90

Cross Baffle




Honeycomb



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Spot 150








CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric																								
3000	90	2115	1872	22.5	16°	03.8073	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	Dimmable on Board	<div><table><tr><td>h(m)</td><td>16°</td></tr><tr><td>1</td><td>17329 0.28</td></tr><tr><td>2</td><td>4332 0.56</td></tr><tr><td>3</td><td>1925 0.84</td></tr><tr><td>4</td><td>1083 1.12</td></tr><tr><td>5</td><td>593 1.40</td></tr></table>Luminous flux luminaire 1872 lm</div>	h(m)	16°	1	17329 0.28	2	4332 0.56	3	1925 0.84	4	1083 1.12	5	593 1.40												
h(m)	16°																																
1	17329 0.28																																
2	4332 0.56																																
3	1925 0.84																																
4	1083 1.12																																
5	593 1.40																																
2700	90	2000	1770	22.5	16°	03.8072	A1V = 0-10V, 10% Dimming	<div><table><tr><td>h(m)</td><td>16°</td></tr><tr><td>1</td><td>16385 0.28</td></tr><tr><td>2</td><td>4096 0.56</td></tr><tr><td>3</td><td>1821 0.84</td></tr><tr><td>4</td><td>1024 1.12</td></tr><tr><td>5</td><td>555 1.40</td></tr></table>Luminous flux luminaire 1770 lm</div>	h(m)	16°	1	16385 0.28	2	4096 0.56	3	1821 0.84	4	1024 1.12	5	555 1.40													
h(m)	16°																																
1	16385 0.28																																
2	4096 0.56																																
3	1821 0.84																																
4	1024 1.12																																
5	555 1.40																																
3000	90	2115	1816	22.5	28°	03.8075	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	Dimmable on Board	<div><table><tr><td>h(m)</td><td>28°</td></tr><tr><td>1</td><td>8395 0.50</td></tr><tr><td>2</td><td>2099 1.00</td></tr><tr><td>3</td><td>933 1.50</td></tr><tr><td>4</td><td>525 2.00</td></tr><tr><td>5</td><td>336 2.50</td></tr></table>Luminous flux luminaire 1816 lm</div>	h(m)	28°	1	8395 0.50	2	2099 1.00	3	933 1.50	4	525 2.00	5	336 2.50												
h(m)	28°																																
1	8395 0.50																																
2	2099 1.00																																
3	933 1.50																																
4	525 2.00																																
5	336 2.50																																
2700	90	2000	1717	22.5	28°	03.8074	A1V = 0-10V, 10% Dimming	<div><table><tr><td>h(m)</td><td>28°</td></tr><tr><td>1</td><td>7938 0.50</td></tr><tr><td>2</td><td>1984 1.00</td></tr><tr><td>3</td><td>882 1.50</td></tr><tr><td>4</td><td>496 2.00</td></tr><tr><td>5</td><td>318 2.50</td></tr></table>Luminous flux luminaire 1717 lm</div>	h(m)	28°	1	7938 0.50	2	1984 1.00	3	882 1.50	4	496 2.00	5	318 2.50													
h(m)	28°																																
1	7938 0.50																																
2	1984 1.00																																
3	882 1.50																																
4	496 2.00																																
5	318 2.50																																
3000	90	2115	1838	22.5	40°	03.8077	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	Dimmable on Board	<div><table><tr><td>E(lx)</td><td>D(m)</td><td>h(m)</td><td>40°</td></tr><tr><td>1</td><td>4656</td><td>0.73</td><td></td></tr><tr><td>2</td><td>1164</td><td>1.46</td><td></td></tr><tr><td>3</td><td>517</td><td>2.18</td><td></td></tr><tr><td>4</td><td>291</td><td>2.91</td><td></td></tr><tr><td>5</td><td>186</td><td>3.64</td><td></td></tr></table>Luminous flux luminaire 1838 lm</div>	E(lx)	D(m)	h(m)	40°	1	4656	0.73		2	1164	1.46		3	517	2.18		4	291	2.91		5	186	3.64	
E(lx)	D(m)	h(m)	40°																														
1	4656	0.73																															
2	1164	1.46																															
3	517	2.18																															
4	291	2.91																															
5	186	3.64																															
2700	90	2000	1738	22.5	40°	03.8076	A1V = 0-10V, 10% Dimming	<div><table><tr><td>E(lx)</td><td>D(m)</td><td>h(m)</td><td>40°</td></tr><tr><td>1</td><td>4402</td><td>0.73</td><td></td></tr><tr><td>2</td><td>1101</td><td>1.46</td><td></td></tr><tr><td>3</td><td>489</td><td>2.18</td><td></td></tr><tr><td>4</td><td>275</td><td>2.91</td><td></td></tr><tr><td>5</td><td>176</td><td>3.64</td><td></td></tr></table>Luminous flux luminaire 1738 lm</div>	E(lx)	D(m)	h(m)	40°	1	4402	0.73		2	1101	1.46		3	489	2.18		4	275	2.91		5	176	3.64		
E(lx)	D(m)	h(m)	40°																														
1	4402	0.73																															
2	1101	1.46																															
3	489	2.18																															
4	275	2.91																															
5	176	3.64																															

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Optional Accessories Spot 150

<p>Cross Baffle</p> <hr/> <p>Part Number:</p> <p>08.8429.00</p> <hr/> 	<p>Elliptical Lens</p> <hr/> <p>Part Number:</p> <p>08.8431.00</p> <hr/> 	<p>Flood Lens</p> <hr/> <p>Part Number:</p> <p>08.8432.00</p> <hr/> 
<p>Honeycomb</p> <hr/> <p>Part Number:</p> <p>08.8428.00</p> <hr/> 	<p>Snoot shielding cone</p> <hr/> <p>Part Number:</p> <p>08.0526.00</p> <hr/> 	

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Light Strip




Length	CRI	CCT	Initial Lumens	Delivered Lumens	Watts	Part Number	Finish	Dimming Protocol
11.8" (300 mm)	90	2700	558	244	6	03.8000	■ 14 = Black	Dimmable on Board 1V = 0-10V, 10% Dimming DA = DALI, 10% Dimming
23.6" (600 mm)	90	2700	1115	488	12	03.8001		
35.4" (900 mm)	90	2700	1673	732	18	03.8002		
47.2" (1200 mm)	90	2700	2230	976	24	03.8003		
59" (1500 mm)	90	2700	2788	1220	30	03.8004		





Length	CRI	CCT	Initial Lumens	Delivered Lumens	Watts	Part Number	Finish	Dimming Protocol
11.8" (300 mm)	90	3000	590	258	6	03.8005	■ 14 = Black	Dimmable on Board 1V = 0-10V, 10% Dimming DA = DALI, 10% Dimming
23.6" (600 mm)	90	3000	1180	516	12	03.8006		
35.4" (900 mm)	90	3000	1670	773	18	03.8007		
47.2" (1200 mm)	90	3000	2360	1031	24	03.8008		
59" (1500 mm)	90	3000	2950	1289	30	03.8009		

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Anthony Spot Track



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric																		
3000	90	1730	1425	17.6	15°	03.8027	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	<div>Dimmable on Board</div> <div>1V = 0-10V, 10% Dimming</div> <div>DA = DALI, 10% Dimming</div>	<div><div>Beam Angle: 15°</div><table><thead><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>1</td><td>14285</td><td>0.27</td></tr><tr><td>2</td><td>3571</td><td>0.54</td></tr><tr><td>3</td><td>1587</td><td>0.81</td></tr><tr><td>4</td><td>893</td><td>1.07</td></tr><tr><td>5</td><td>571</td><td>1.34</td></tr></tbody></table><div>Luminous flux luminaire 1425 lm</div></div>	h(m)	E(lx)	D(m)	1	14285	0.27	2	3571	0.54	3	1587	0.81	4	893	1.07	5	571	1.34
h(m)	E(lx)	D(m)																									
1	14285	0.27																									
2	3571	0.54																									
3	1587	0.81																									
4	893	1.07																									
5	571	1.34																									
2700	90	1620	1241	17.6	15°	03.8025	<div><div>Beam Angle: 15°</div><table><thead><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>1</td><td>12442</td><td>0.27</td></tr><tr><td>2</td><td>3110</td><td>0.54</td></tr><tr><td>3</td><td>1382</td><td>0.81</td></tr><tr><td>4</td><td>778</td><td>1.07</td></tr><tr><td>5</td><td>498</td><td>1.34</td></tr></tbody></table><div>Luminous flux luminaire 1241 lm</div></div>	h(m)	E(lx)	D(m)	1	12442	0.27	2	3110	0.54	3	1382	0.81	4	778	1.07	5	498	1.34		
h(m)	E(lx)	D(m)																									
1	12442	0.27																									
2	3110	0.54																									
3	1382	0.81																									
4	778	1.07																									
5	498	1.34																									
3000	90	1730	1426	17.6	32°	03.8028	<div><div>Beam Angle: 28°</div><table><thead><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>1</td><td>5799</td><td>0.49</td></tr><tr><td>2</td><td>1450</td><td>0.98</td></tr><tr><td>3</td><td>644</td><td>1.47</td></tr><tr><td>4</td><td>362</td><td>1.97</td></tr><tr><td>5</td><td>232</td><td>2.46</td></tr></tbody></table><div>Luminous flux luminaire 1399 lm</div></div>	h(m)	E(lx)	D(m)	1	5799	0.49	2	1450	0.98	3	644	1.47	4	362	1.97	5	232	2.46		
h(m)	E(lx)	D(m)																									
1	5799	0.49																									
2	1450	0.98																									
3	644	1.47																									
4	362	1.97																									
5	232	2.46																									
2700	90	1620	1242	17.6	32°	03.8026	<div><div>Beam Angle: 28°</div><table><thead><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>1</td><td>5145</td><td>0.49</td></tr><tr><td>2</td><td>1286</td><td>0.98</td></tr><tr><td>3</td><td>572</td><td>1.47</td></tr><tr><td>4</td><td>322</td><td>1.97</td></tr><tr><td>5</td><td>206</td><td>2.46</td></tr></tbody></table><div>Luminous flux luminaire 1242 lm</div></div>	h(m)	E(lx)	D(m)	1	5145	0.49	2	1286	0.98	3	572	1.47	4	322	1.97	5	206	2.46		
h(m)	E(lx)	D(m)																									
1	5145	0.49																									
2	1286	0.98																									
3	572	1.47																									
4	322	1.97																									
5	206	2.46																									

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Optional Accessories Anthony Spot

Honeycomb	Elliptical Lens	Flood Lens (28° Anthony Fixture + Flood Lens = 35°)
Part Number: 08.8419.14A	Part Number: 08.8418.68A	Part Number: 08.0050.00
