



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Description


The new Tracking Magnet 48V system is creative, flexible, reliable and precise. Accent luminaires are installed by a magnetic fastening system and a secondary mechanical fastener. The range of luminaires is composed of accent illumination modules with different optics and linear luminaires with the Flos signature design. The Tracking Magnet is available in recessed, surface, or pendant mounted applications, making it an option in even the most varied of job conditions. Vertical and horizontal corners complete the system. The Tracking Magnet is perfect for retail displays where frequent changes are typical and absolute performance is required.



Lamp

System Lamp Type	LED
Color Temperature	2700K, 3000K, *3500K, *4000K (See Notes)
Color Rendering	CRI90
Application	General Lighting / Accent lighting

Suspended Installation



Light Modules



Physical

Material	Aluminum
Ingress Protection Rating	IP20
Finishes	<input type="checkbox"/> 40 White <input checked="" type="checkbox"/> 14 White <input type="checkbox"/> 05 Chrome
Installation type	Ceiling Surface
Environment	Indoor
Field cuttable	No

Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.

Electrical & Control

Driver location	Remote
Driver Input Voltage	120V-277V
Driver Output Voltage	48V
Maximum Driver Wattage	Class 2 - 96W
Control	Standard 0-10V dimming / DALI / On board / Casambi for Light Shadow Spot and Multi Spot Mini.
N° Circuit	1 circuit



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Notes

EC to supply site cabling from driver to track location.

Wattage per linear foot is dependent upon quantity and type of light modules used.

Spots and linear luminaires available with individually addressable DALI-Wireless circuitry, 0-10V (from 10% up to 100%) Dimming, Casambi for Light Shadow Spot and Multi Spot Mini.


0-10V Fixtures come from the factory set up at the lowest level 10% they always required a 0-10V signal to achieve the maximum output.

3500K, 4000K and other CCT available but not cataloged. Consult factory for additional color temperatures.



Suspended Installation

How To Specify



Light Modules



Certifications

Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.

A. Select and position corners

1. Horizontal - Connect sections on flat surfaces (90° corner)
2. Inside - Transition from wall to ceiling (inside corner)
3. External - Turn outside corners for walls and soffits (270° corner)

B. Fill lengths between corners with Linear Housings


Select dimmable (DALI-FLOS Smart control and 0-10V fixtures) or non dimmable track (Built-in dimmer fixtures). Available section lengths are 3.3', 4.9', 6.7' or 8.2'.

C. Drivers

Quantity of drivers determined by total wattage or light elements in section (total maximum possible per linear foot is 29W). Maximum driver distance is 15'. Locate drivers nearby.

D. Select Spot heads


Light Strips are available in three nominal lengths: 11.8", 23.6", 35.4", 47.2" and 59". Individual Spots are Spot 50, Spot 90, Spot 120, Spot 150 and Anthony.



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Track



How to specify: 06.5070.14

Length	Part Number	Delivered Lumens	Finish	Dimming Protocol
39.4" (1m)	06.5070	465 lm	40 = White 14 = Black 05 = Chrome	Dimmable on Board Dimmable Casambi
59" (1.5m)	06.5071	697.5 lm		
78.7" (2m)	06.5072	930 lm		
98.4" (2.5m)	06.5073	1162.5 lm		
118.11" (3m)	06.5074	1257 lm	40 = White 14 = Black	

How to specify: 06.5070.14

Length	Part Number	Delivered Lumens	Finish	Dimming Protocol
39.4" (1m)	06.5020	465 lm	40 = White 14 = Black 05 = Chrome	1-10V, 10% Dimming DALI, 10% Dimming Dimmable Casambi
59" (1.5m)	06.5021	697.5 lm		
78.7" (2m)	06.5022	930 lm		
98.4" (2.5m)	06.5023	1162.5 lm		
118.11" (3m)	06.5024	1257 lm	40 = White 14 = Black	

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Corners




90° horizontal ceiling mechanical corner available. In order to create electrical continuity the flexible intermediate connector is required.

90° mechanical angle.

Two end suspension connections included. Steel cable not included. No lighting on the upper part. Upper part connections included.

Part Number:







- ☒ 06.5025.14
- ☐ 06.5025.40
- ☐ 06.5025.05



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Connectors

<p>Feed connector for Tracking Magnet Suspension Up&Down includes: 1 feed connector, 1 transparent feed cable 4m - 13ft. Includes beginning and end fixing ceiling kit. Suspension cable or rigid Rod not included.</p> <p>Part Number:</p> <p>08.0626.00</p>  	<p>Intermediate connector for Tracking Magnet Suspension Up&Down (1 unit kit)</p> <p>Part Number:</p> <p>08.0612.14</p>  	<p>Flexible/Electrical Intermediate Corner for Tracking Magnet suspension if electrical continuity on corners is required.</p> <p>Part Number:</p> <p>08.0614.14</p>  
---	---	--

*Intermediate connectors to be ordered separately if electrical continuity on corners is required.

The Tracking Magnet EVO Suspension Up&Down


High-tech LED lighting system for interior architecture

Dimming controllers

Dimming Control Unit Box 48V
0-10V Required for a 0-10V Dimming
installation. 1 Dimming control can
control up to 20 fixtures

Part Number:








■ 08.0613.14A



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Required Accesories







Intermediate Suspension Kit Part Number: 08.0627.00	End Cap kit (2 units) Part Number: 06.5017.14 06.5017.40 06.5017.05	Suspension steel cable, lenght 4m (13ft) Recommended where tilting will not occur in any case. Part Number: 08.8634.00
		
Suspension rod with rose, lenght 1m (3.3ft) M6 thread. Rigid rod to avoid the profile from tilting to be installed in places where a more rigid fixing system is required. Part Number: 60.3014.14 60.3014.11	Suspension rod extension, lenght 1m(3.3ft) M6 thread. Rigid rod to avoid the profile from tilting to be installed in places where a more rigid fixing system is required. Part Number: 60.3097.14 60.3097.11	Cover Plate 5" Junction Box Cover Plate for Remote Installation. Part Number: 08.8883.40A 08.8883.14A
		 

Profile	Minimum qty fixing points depending on track length
39.37" / 59.06" [1000 mm/ 1500 mm]	2
78.74" / 98.42" [2000 mm/ 2500 mm]	3

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Required Drivers

LED power supply source for remote installation, 48V/96W, 120-277V, UL Listed	LED power supply source for remote installation, 48V/60W, 120-277V, UL Listed	LED power supply source for remote installation, 48V/30W, 120-277V, UL Listed
Part Number: LEDSB96W48V-NDM-D01	Part Number: LEDSB60W48V-NDM-D01	Part Number: LEDSB30W48V-NDM-D01
		
		

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture


Surface mounted canopies

Surface mount canopy Non Dimmable for Tracking Magnet SuspensionUp&Down includes: 1 drivers downlight: 96W, 48V, 120-277V	Surface mount canopy Dimmable for Tracking Magnet Suspension Down includes: 1 driver downlight: 96W, 48V, 120-277V 1 Dimming Control Unit Box: 08.0613.14A	Surface mount canopy Dimmable for Tracking Magnet Suspension Down includes: 1 driver downlight: 60W, 48V, 120-277V 1 Dimming Control Unit Box: 08.0613.14A
Part Number: 08U4806.14 08U4806.40	Part Number: 08U4806.14.1V 08U4806.40.1V	Part Number: 08U4807.40.1V 08U4807.14.1V


The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

How to specify



Spot 50



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric												
3000	90	307	212	3.5	26°	03.8033	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div><p>Luminous flux luminaire 212 lm</p></div> <div><table><tr><th>E(h)</th><th>D(m)</th></tr><tr><td>1</td><td>1012 0.47</td></tr><tr><td>2</td><td>253 0.94</td></tr><tr><td>3</td><td>112 1.41</td></tr><tr><td>4</td><td>63 1.88</td></tr><tr><td>5</td><td>40 2.35</td></tr></table></div>	E(h)	D(m)	1	1012 0.47	2	253 0.94	3	112 1.41	4	63 1.88	5	40 2.35
E(h)	D(m)																				
1	1012 0.47																				
2	253 0.94																				
3	112 1.41																				
4	63 1.88																				
5	40 2.35																				
2700	90	286	205	3.5	26°	03.8032	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	B Dimmable on Board B1V = 0-10V, 10% Dimming BDA = DALI, 10% Dimming	<div><p>Luminous flux luminaire 205 lm</p></div> <div><table><tr><th>E(h)</th><th>D(m)</th></tr><tr><td>1</td><td>977 0.47</td></tr><tr><td>2</td><td>244 0.94</td></tr><tr><td>3</td><td>109 1.41</td></tr><tr><td>4</td><td>61 1.88</td></tr><tr><td>5</td><td>39 2.35</td></tr></table></div>	E(h)	D(m)	1	977 0.47	2	244 0.94	3	109 1.41	4	61 1.88	5	39 2.35
E(h)	D(m)																				
1	977 0.47																				
2	244 0.94																				
3	109 1.41																				
4	61 1.88																				
5	39 2.35																				


Included Accessories Spot 50





Cross Baffle	Honeycomb

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Spot 90



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric														
3000	90	656	443	8.5	14°	03.8043	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div><table><thead><tr><th>E(x)</th><th>D(m)</th></tr><tr><th>h(m)</th><th></th></tr></thead><tbody><tr><td>1</td><td>5805 0.25</td></tr><tr><td>2</td><td>1451 0.49</td></tr><tr><td>3</td><td>645 0.74</td></tr><tr><td>4</td><td>363 0.98</td></tr><tr><td>5</td><td>232 1.23</td></tr></tbody></table></div>	E(x)	D(m)	h(m)		1	5805 0.25	2	1451 0.49	3	645 0.74	4	363 0.98	5	232 1.23
E(x)	D(m)																						
h(m)																							
1	5805 0.25																						
2	1451 0.49																						
3	645 0.74																						
4	363 0.98																						
5	232 1.23																						
2700	90	610	428	8.5	14°	03.8042	<div><table><thead><tr><th>E(x)</th><th>D(m)</th></tr><tr><th>h(m)</th><th></th></tr></thead><tbody><tr><td>1</td><td>5601 0.25</td></tr><tr><td>2</td><td>1400 0.49</td></tr><tr><td>3</td><td>622 0.74</td></tr><tr><td>4</td><td>350 0.98</td></tr><tr><td>5</td><td>224 1.23</td></tr></tbody></table></div>	E(x)	D(m)	h(m)		1	5601 0.25	2	1400 0.49	3	622 0.74	4	350 0.98	5	224 1.23		
E(x)	D(m)																						
h(m)																							
1	5601 0.25																						
2	1400 0.49																						
3	622 0.74																						
4	350 0.98																						
5	224 1.23																						
3000	90	656	406	8.5	22°	03.8045	<div><table><thead><tr><th>E(x)</th><th>D(m)</th></tr><tr><th>h(m)</th><th></th></tr></thead><tbody><tr><td>1</td><td>2403 0.38</td></tr><tr><td>2</td><td>601 0.77</td></tr><tr><td>3</td><td>267 1.15</td></tr><tr><td>4</td><td>150 1.54</td></tr><tr><td>5</td><td>96 1.92</td></tr></tbody></table></div>	E(x)	D(m)	h(m)		1	2403 0.38	2	601 0.77	3	267 1.15	4	150 1.54	5	96 1.92		
E(x)	D(m)																						
h(m)																							
1	2403 0.38																						
2	601 0.77																						
3	267 1.15																						
4	150 1.54																						
5	96 1.92																						
2700	90	610	392	8.5	22°	03.8044	<div><table><thead><tr><th>E(x)</th><th>D(m)</th></tr><tr><th>h(m)</th><th></th></tr></thead><tbody><tr><td>1</td><td>2319 0.38</td></tr><tr><td>2</td><td>580 0.77</td></tr><tr><td>3</td><td>258 1.15</td></tr><tr><td>4</td><td>145 1.54</td></tr><tr><td>5</td><td>93 1.92</td></tr></tbody></table></div>	E(x)	D(m)	h(m)		1	2319 0.38	2	580 0.77	3	258 1.15	4	145 1.54	5	93 1.92		
E(x)	D(m)																						
h(m)																							
1	2319 0.38																						
2	580 0.77																						
3	258 1.15																						
4	145 1.54																						
5	93 1.92																						


Included Accessories Spot 90

Cross Baffle	Honeycomb

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Spot 120 Power LED



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric
3000	90	779	558	12	11°	03.8053	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div></div>


Included Accessories Spot 90

Cross Baffle	Honeycomb

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Spot 120 LED ARRAY



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric
3000	90	1138	687	12.5	17°	03.8155	<div>40 = White</div> <div>14 = Black</div> <div>05 = Chrome</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div></div> <div>E(lx) D(m) h(m) 17° 1 4780 0.31 2 1195 0.61 3 531 0.92 4 299 1.23 5 191 1.53 Luminous flux luminaire 687 lm</div>
2700	90	1075	654	12.5	17°	03.8154			<div></div> <div>E(lx) D(m) h(m) 17° 1 4547 0.31 2 1137 0.61 3 505 0.92 4 284 1.23 5 182 1.53 Luminous flux luminaire 654 lm</div>
3000	90	1138	629	12.5	40°	03.8157		B Dimmable on Board B1V = 0-10V, 10% Dimming BDA = DALI, 10% Dimming	<div></div> <div>E(lx) D(m) h(m) 40° 1 1437 0.73 2 359 1.45 3 160 2.18 4 90 2.91 5 57 3.64 Luminous flux luminaire 629 lm</div>
2700	90	1075	599	12.5	40°	03.8156			<div></div> <div>E(lx) D(m) h(m) 40° 1 1367 0.73 2 342 1.45 3 152 2.18 4 85 2.91 5 55 3.64 Luminous flux luminaire 599 lm</div>


Included Accessories Spot 90







Cross Baffle	Honeycomb

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Spot 150








CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric															
3000	90	2115	1872	22.5	16°	03.8073	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div><div><div>h(m)</div><div>16°</div><table><tr><td>1</td><td>17329</td><td>0.28</td></tr><tr><td>2</td><td>4332</td><td>0.56</td></tr><tr><td>3</td><td>1925</td><td>0.84</td></tr><tr><td>4</td><td>1083</td><td>1.12</td></tr><tr><td>5</td><td>593</td><td>1.40</td></tr></table></div><div>Luminous flux luminaire 1872 lm</div></div>	1	17329	0.28	2	4332	0.56	3	1925	0.84	4	1083	1.12	5	593	1.40
1	17329	0.28																						
2	4332	0.56																						
3	1925	0.84																						
4	1083	1.12																						
5	593	1.40																						
2700	90	2000	1770	22.5	16°	03.8072	<div><div></div> 05 = Chrome</div>	B Dimmable on Board B1V = 0-10V, 10% Dimming BDA = DALI, 10% Dimming	<div><div><div>h(m)</div><div>16°</div><table><tr><td>1</td><td>16385</td><td>0.28</td></tr><tr><td>2</td><td>4096</td><td>0.56</td></tr><tr><td>3</td><td>1821</td><td>0.84</td></tr><tr><td>4</td><td>1024</td><td>1.12</td></tr><tr><td>5</td><td>555</td><td>1.40</td></tr></table></div><div>Luminous flux luminaire 1770 lm</div></div>	1	16385	0.28	2	4096	0.56	3	1821	0.84	4	1024	1.12	5	555	1.40
1	16385	0.28																						
2	4096	0.56																						
3	1821	0.84																						
4	1024	1.12																						
5	555	1.40																						
3000	90	2115	1816	22.5	28°	03.8075	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div><div><div>h(m)</div><div>28°</div><table><tr><td>1</td><td>8395</td><td>0.50</td></tr><tr><td>2</td><td>2099</td><td>1.00</td></tr><tr><td>3</td><td>933</td><td>1.50</td></tr><tr><td>4</td><td>525</td><td>2.00</td></tr><tr><td>5</td><td>336</td><td>2.50</td></tr></table></div><div>Luminous flux luminaire 1816 lm</div></div>	1	8395	0.50	2	2099	1.00	3	933	1.50	4	525	2.00	5	336	2.50
1	8395	0.50																						
2	2099	1.00																						
3	933	1.50																						
4	525	2.00																						
5	336	2.50																						
2700	90	2000	1717	22.5	28°	03.8074	<div><div></div> 05 = Chrome</div>	B Dimmable on Board B1V = 0-10V, 10% Dimming BDA = DALI, 10% Dimming	<div><div><div>h(m)</div><div>28°</div><table><tr><td>1</td><td>7938</td><td>0.50</td></tr><tr><td>2</td><td>1984</td><td>1.00</td></tr><tr><td>3</td><td>882</td><td>1.50</td></tr><tr><td>4</td><td>496</td><td>2.00</td></tr><tr><td>5</td><td>318</td><td>2.50</td></tr></table></div><div>Luminous flux luminaire 1717 lm</div></div>	1	7938	0.50	2	1984	1.00	3	882	1.50	4	496	2.00	5	318	2.50
1	7938	0.50																						
2	1984	1.00																						
3	882	1.50																						
4	496	2.00																						
5	318	2.50																						
3000	90	2115	1838	22.5	40°	03.8077	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div><div><div>E(lx)</div><div>D(m)</div><div>h(m)</div><div>40°</div><table><tr><td>1</td><td>4656</td><td>0.73</td></tr><tr><td>2</td><td>1164</td><td>1.46</td></tr><tr><td>3</td><td>517</td><td>2.18</td></tr><tr><td>4</td><td>291</td><td>2.91</td></tr><tr><td>5</td><td>186</td><td>3.64</td></tr></table></div><div>Luminous flux luminaire 1838 lm</div></div>	1	4656	0.73	2	1164	1.46	3	517	2.18	4	291	2.91	5	186	3.64
1	4656	0.73																						
2	1164	1.46																						
3	517	2.18																						
4	291	2.91																						
5	186	3.64																						
2700	90	2000	1738	22.5	40°	03.8076	<div><div></div> 05 = Chrome</div>	B Dimmable on Board B1V = 0-10V, 10% Dimming BDA = DALI, 10% Dimming	<div><div><div>E(lx)</div><div>D(m)</div><div>h(m)</div><div>40°</div><table><tr><td>1</td><td>4402</td><td>0.73</td></tr><tr><td>2</td><td>1101</td><td>1.46</td></tr><tr><td>3</td><td>489</td><td>2.18</td></tr><tr><td>4</td><td>275</td><td>2.91</td></tr><tr><td>5</td><td>176</td><td>3.64</td></tr></table></div><div>Luminous flux luminaire 1738 lm</div></div>	1	4402	0.73	2	1101	1.46	3	489	2.18	4	275	2.91	5	176	3.64
1	4402	0.73																						
2	1101	1.46																						
3	489	2.18																						
4	275	2.91																						
5	176	3.64																						

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture


Optional Accessories Spot 150

Cross Baffle	Elliptical Lens	Flood Lens
Part Number: 08.8429.00	Part Number: 08.8431.00	Part Number: 08.8432.00
		
Honeycomb	Snoot shielding cone	
Part Number: 08.8428.00	Part Number: 08.0526.00	
		

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Light Shadow Spot 30



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol
3000	90	263	214	4.5	10°	05.9005	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	257	209	4.5	10°	05.9000		
3000	90	263	205	4.5	22°	05.9006	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	257	201	4.5	22°	05.9001		
3000	90	263	204	4.5	33°	05.9007	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	257	200	4.5	33°	05.9002		
3000	90	263	214	4.5	46°	05.9008	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	257	209	4.5	46°	05.9003		

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Photometric Light Shadow Spot 30

Spot 10°

2700K

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	3772	0.18
2	943	0.36
3	419	0.54
4	236	0.72
5	151	0.90

3772 cd

Luminous flux luminaire 209 lm

3000K

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	3862	0.18
2	966	0.36
3	429	0.54
4	241	0.72
5	154	0.90

3862 cd

Luminous flux luminaire 214 lm

Medium 22°

2700K

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1374	0.39
2	344	0.78
3	153	1.17
4	86	1.56
5	55	1.95

1374 cd

Luminous flux luminaire 201 lm

3000K

Beam Angle: 22°

h(m)	E(lx)	D(m)
1	1402	0.39
2	350	0.78
3	156	1.17
4	88	1.56
5	56	1.95

1402 cd

Luminous flux luminaire 205 lm

Flood 33°

2700K

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	625	0.60
2	156	1.19
3	69	1.79
4	39	2.39
5	25	2.99

626 cd

Luminous flux luminaire 200 lm

3000K

Beam Angle: 33°

h(m)	E(lx)	D(m)
1	638	0.60
2	159	1.19
3	71	1.79
4	40	2.39
5	26	2.99

638 cd

Luminous flux luminaire 204 lm

Wide Flood 46°

2700K

Beam Angle: 46°

h(m)	E(lx)	D(m)
1	396	0.84
2	99	1.69
3	44	2.53
4	25	3.38
5	16	4.22

396 cd

Luminous flux luminaire 209 lm

3000K

Beam Angle: 46°

h(m)	E(lx)	D(m)
1	406	0.84
2	101	1.69
3	45	2.53
4	25	3.38
5	16	4.22

406 cd

Luminous flux luminaire 214 lm


Optional Accessories Light Shadow Spot 30

<p>Honeycomb</p> <p>Part Number:</p> <p>08.0790.00</p>	<p>Dicroic CCT Filter</p> <p>INCREASE</p> <p>2700K >> 3125±75K</p> <p>3000K >> 3600±75K</p> <p>Part Number:</p> <p>08.0791.00</p>	<p>Dicroic CCT Filter</p> <p>DECREASE</p> <p>2700K >> 2450±75K</p> <p>3000K >> 2700±75K</p> <p>Part Number:</p> <p>08.0792.00</p>
--	---	---

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture


Light Shadow Spot 45




CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol
3000	90	844	686	10.5	15°	05.9035	<div> <div></div> 40 = White <div></div> 14 = Black <div></div> ER = Brushed Steel <div></div> ES = Brushed Bronze <div></div> EQ = Brushed Copper </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	799	650	10.5	15°	05.9030		
3000	90	844	682	10.5	21°	05.9036	<div> <div></div> 40 = White <div></div> 14 = Black <div></div> ER = Brushed Steel <div></div> ES = Brushed Bronze <div></div> EQ = Brushed Copper </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	799	645	10.5	21°	05.9031		
3000	90	844	682	10.5	31°	05.9037	<div> <div></div> 40 = White <div></div> 14 = Black <div></div> ER = Brushed Steel <div></div> ES = Brushed Bronze <div></div> EQ = Brushed Copper </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	799	646	10.5	31°	05.9032		

Photometric Light Shadow Spot 45


Spot 15° 2700K




3000K




Medium 21° 2700K




3000K



Flood 31° 2700K



3000K



The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture


Optional Accessories Light Shadow Spot 45

Honeycomb	Dicroic CCT Filter INCREASE 2700K >> 3125±75K 3000K >> 3600±75K	Dicroic CCT Filter DECREASE 2700K >> 2450±75K 3000K >> 2700±75K
Part Number: 08.0793.00	Part Number: 08.0794.00	Part Number: 08.0795.00
		

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Light Shadow Spot 60



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol
3000	90	844	808	10	9°	05.9065	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	799	765	10	9°	05.9060		
3000	90	1751	1375	20	15°	05.9066	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	1593	1251	20	15°	05.9061		
3000	90	1751	1427	20	26°	05.9067	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	1593	1298	20	26°	05.9062		
3000	90	1751	1431	20	33°	05.9068	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	1593	1304	20	33°	05.9063		
3000	90	1751	1390	20	43°	05.9069	<div> <div>40 = White</div> <div>14 = Black</div> <div>ER = Brushed Steel</div> <div>ES = Brushed Bronze</div> <div>EQ = Brushed Copper</div> </div>	Dimmable on Board 1V = 0-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	1593	1268	20	43°	05.9064		


The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Photometric Light Shadow Spot 60

Super Spot 9°


2700K



Beam Angle: 9°

h(m)	E(lx)	D(m)
1	24922	0.16
2	6230	0.32
3	2769	0.48
4	1558	0.64
5	997	0.80

3000K




Beam Angle: 9°

h(m)	E(lx)	D(m)
1	26322	0.16
2	6581	0.32
3	2925	0.48
4	1645	0.64
5	1053	0.80

Spot 15°


2700K



Beam Angle: 15°

h(m)	E(lx)	D(m)
1	14350	0.27
2	3587	0.54
3	1594	0.81
4	897	1.09
5	574	1.36

3000K




Beam Angle: 15°

h(m)	E(lx)	D(m)
1	15772	0.27
2	3943	0.54
3	1752	0.81
4	986	1.09
5	631	1.36

Medium 26°


2700K



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	7377	0.45
2	1844	0.91
3	820	1.36
4	461	1.82
5	295	2.27

3000K




Beam Angle: 26°

h(m)	E(lx)	D(m)
1	8110	0.45
2	2027	0.91
3	901	1.36
4	507	1.82
5	324	2.27

Flood 33°


2700K



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	4472	0.60
2	1118	1.20
3	497	1.80
4	279	2.40
5	179	3.00

3000K




Beam Angle: 33°

h(m)	E(lx)	D(m)
1	4907	0.60
2	1227	1.20
3	545	1.80
4	307	2.40
5	196	3.00

Wide Flood 43°


2700K



Beam Angle: 43°

h(m)	E(lx)	D(m)
1	2761	0.79
2	690	1.59
3	307	2.38
4	173	3.17
5	110	3.97

3000K









Beam Angle: 43°

h(m)	E(lx)	D(m)
1	3026	0.79
2	757	1.59
3	336	2.38
4	189	3.17
5	121	3.97

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture


Optional Accessories Light Shadow Spot 60

Honeycomb Super Spot		Honeycomb Spot / Medium / Flood / Wide Flood	
Part Number:		Part Number:	
08.0175.14		08.0176.14	
			
INCREASE		INCREASE	
Dicroic Super Spot	2700K >> 3125±75K 3000K >> 3600±75K	Dicroic Spot / Medium / Flood / Wide Flood	2700K >> 3125±75K 3000K >> 3600±75K
Part Number:		Part Number:	
08.0796.00		08.0798.00	
			
DECREASE		DECREASE	
Dicroic Super Spot	2700K >> 2450±75K 3000K >> 2700±75K	Dicroic Spot / Medium / Flood / Wide Flood	2700K >> 2450±75K 3000K >> 2700±75K
Part Number:		Part Number:	
08.0797.00		08.0799.00	
			

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Light Strip




Length	CRI	CCT	Initial Lumens	Delivered Lumens	Watts	Part Number	Finish	Dimming Protocol
11.8" (300 mm)	90	2700	558	244	6	03.8000	■ 14 = Black	Dimmable on Board 1V = 0-10V, 10% Dimming DA = DALI, 10% Dimming
23.6" (600 mm)	90	2700	1115	488	12	03.8001		
35.4" (900 mm)	90	2700	1673	732	18	03.8002		
47.2 " (1200 mm)	90	2700	2230	976	24	03.8003		
59" (1500 mm)	90	2700	2788	1220	30	03.8004		





Length	CRI	CCT	Initial Lumens	Delivered Lumens	Watts	Part Number	Finish	Dimming Protocol
11.8" (300 mm)	90	3000	590	258	6	03.8005	■ 14 = Black	Dimmable on Board 1V = 0-10V, 10% Dimming DA = DALI, 10% Dimming
23.6" (600 mm)	90	3000	1180	516	12	03.8006		
35.4" (900 mm)	90	3000	1670	773	18	03.8007		
47.2 " (1200 mm)	90	3000	2360	1031	24	03.8008		
59" (1500 mm)	90	3000	2950	1289	30	03.8009		

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture

Anthony Spot Track



CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol	Photometric																		
3000	90	1730	1425	17.6	15°	03.8027	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div> <div><div></div> 05 = Chrome</div>	A Dimmable on Board A1V = 0-10V, 10% Dimming ADA = DALI, 10% Dimming	<div><p>Beam Angle: 15°</p><table><thead><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>1</td><td>14285</td><td>0.27</td></tr><tr><td>2</td><td>3571</td><td>0.54</td></tr><tr><td>3</td><td>1587</td><td>0.81</td></tr><tr><td>4</td><td>893</td><td>1.07</td></tr><tr><td>5</td><td>571</td><td>1.34</td></tr></tbody></table><p>Luminous flux luminaire 1425 lm</p></div>	h(m)	E(lx)	D(m)	1	14285	0.27	2	3571	0.54	3	1587	0.81	4	893	1.07	5	571	1.34
h(m)	E(lx)	D(m)																									
1	14285	0.27																									
2	3571	0.54																									
3	1587	0.81																									
4	893	1.07																									
5	571	1.34																									
2700	90	1620	1241	17.6	15°	03.8025	<div><p>Beam Angle: 15°</p><table><thead><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>1</td><td>12442</td><td>0.27</td></tr><tr><td>2</td><td>3110</td><td>0.54</td></tr><tr><td>3</td><td>1382</td><td>0.81</td></tr><tr><td>4</td><td>778</td><td>1.07</td></tr><tr><td>5</td><td>498</td><td>1.34</td></tr></tbody></table><p>Luminous flux luminaire 1241 lm</p></div>	h(m)	E(lx)	D(m)	1	12442	0.27	2	3110	0.54	3	1382	0.81	4	778	1.07	5	498	1.34		
h(m)	E(lx)	D(m)																									
1	12442	0.27																									
2	3110	0.54																									
3	1382	0.81																									
4	778	1.07																									
5	498	1.34																									
3000	90	1730	1426	17.6	32°	03.8028	<div><p>Beam Angle: 28°</p><table><thead><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>1</td><td>5799</td><td>0.49</td></tr><tr><td>2</td><td>1450</td><td>0.98</td></tr><tr><td>3</td><td>644</td><td>1.47</td></tr><tr><td>4</td><td>362</td><td>1.97</td></tr><tr><td>5</td><td>232</td><td>2.46</td></tr></tbody></table><p>Luminous flux luminaire 1399 lm</p></div>	h(m)	E(lx)	D(m)	1	5799	0.49	2	1450	0.98	3	644	1.47	4	362	1.97	5	232	2.46		
h(m)	E(lx)	D(m)																									
1	5799	0.49																									
2	1450	0.98																									
3	644	1.47																									
4	362	1.97																									
5	232	2.46																									
2700	90	1620	1242	17.6	32°	03.8026	<div><p>Beam Angle: 28°</p><table><thead><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr></thead><tbody><tr><td>1</td><td>5145</td><td>0.49</td></tr><tr><td>2</td><td>1286</td><td>0.98</td></tr><tr><td>3</td><td>572</td><td>1.47</td></tr><tr><td>4</td><td>322</td><td>1.97</td></tr><tr><td>5</td><td>206</td><td>2.46</td></tr></tbody></table><p>Luminous flux luminaire 1242 lm</p></div>	h(m)	E(lx)	D(m)	1	5145	0.49	2	1286	0.98	3	572	1.47	4	322	1.97	5	206	2.46		
h(m)	E(lx)	D(m)																									
1	5145	0.49																									
2	1286	0.98																									
3	572	1.47																									
4	322	1.97																									
5	206	2.46																									

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture


Optional Accessories Anthony Spot

Honeycomb	Elliptical Lens	Flood Lens (28° Anthony Fixture + Flood Lens = 35°)
Part Number: 08.8419.14A	Part Number: 08.8418.68A	Part Number: 08.0050.00
		

The Tracking Magnet EVO Suspension Up&Down

High-tech LED lighting system for interior architecture


Multi Spot Mini How to Specify ex. 05.3550.14 / 05.3550.14.CB / 05.3550.14.DA / 05.3550.14.1V




CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Dimming Protocol
2700	90	654.12	398	7.5	15°	05.3550	<div> <div></div> 40 = White <div></div> 14 = Black </div>	Dimmable on Board 1V = 1-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
2700	90	654.12	424	7.5	20°	05.3552		
2700	90	654.12	391	7.5	32°	05.3554		
3000	90	665.41	405	7.5	15°	05.3551	<div> <div></div> 40 = White <div></div> 14 = Black </div>	Dimmable on Board 1V = 1-10V, 10% Dimming CB = Dimmable Casambi DA = DALI, 10% Dimming
3000	90	665.41	431	7.5	20°	05.3553		
3000	90	665.41	397	7.5	32°	05.3555		

Photometric


Spot 15°




Medium 20°




Flood 32°



3000 K



3000 K



3000 K

