

## The Tracking Magnet EVO


High-tech LED lighting system for interior architecture



Wallee

How to specify

03.8091.40.DA

Suitable for installation on recessed Tracking Magnet profile, horizontally mounted in dry wall only. Light elements are quick to position and connect automatically with magnets. IP20. individually addressable DALI-Wireless circuitry, 0-10V (from 10% up to 100%) Dimming or built-in dimmer on each fixture head (from 30% up to 100%).



CCT	CRI	Initial Lumen	Delivered Lumens	Watts	Beam Spread	Finish	Part Number Built-in dimmer	Part Number DALI Dimming	Part Number 0-10V Dimming	Photometric														
3000	90	818	454	10	96°	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div>	03.8091.40 03.8091.14	03.8091.40.DA 03.8091.14.DA	03.8091.40.1V 03.8091.14.1V	<div><div>96°</div><div></div><div>Luminous flux luminaire 454 lm</div></div> <table><tr><th>E(x)</th><th>D(m)</th></tr><tr><td>h(m)</td><td>96°</td></tr><tr><td>1 183</td><td>2.21</td></tr><tr><td>2 46</td><td>4.43</td></tr><tr><td>3 20</td><td>6.64</td></tr><tr><td>4 11</td><td>8.85</td></tr><tr><td>5 7</td><td>11.07</td></tr></table>	E(x)	D(m)	h(m)	96°	1 183	2.21	2 46	4.43	3 20	6.64	4 11	8.85	5 7	11.07
E(x)	D(m)																							
h(m)	96°																							
1 183	2.21																							
2 46	4.43																							
3 20	6.64																							
4 11	8.85																							
5 7	11.07																							
2700	90	773	454	10	96°	<div><div></div> 40 = White</div> <div><div></div> 14 = Black</div>	03.8090.40 03.8090.14	03.8090.40.DA 03.8090.14.DA	03.8090.40.1V 03.8090.14.1V	<div><div>96°</div><div></div><div>Luminous flux luminaire 454 lm</div></div> <table><tr><th>E(x)</th><th>D(m)</th></tr><tr><td>h(m)</td><td>96°</td></tr><tr><td>1 183</td><td>2.21</td></tr><tr><td>2 46</td><td>4.43</td></tr><tr><td>3 20</td><td>6.64</td></tr><tr><td>4 11</td><td>8.85</td></tr><tr><td>5 7</td><td>11.07</td></tr></table>	E(x)	D(m)	h(m)	96°	1 183	2.21	2 46	4.43	3 20	6.64	4 11	8.85	5 7	11.07
E(x)	D(m)																							
h(m)	96°																							
1 183	2.21																							
2 46	4.43																							
3 20	6.64																							
4 11	8.85																							
5 7	11.07																							