


Dimensions



Certifications



Photometrics

For current IES files please visit
architectural.flosusa.com

Warranty

2 years from date of sale.

FLOS. USA
36 East 31st Street
Suite 402
New York N.Y. 10016
(800) 841.4011

Kap 80 Round Adjustable

NON-IC Ceiling Recessed Trimless Downlight

Description

LED trim-less luminaire for recessed mud-in mounting into plasterboard. Die-cast aluminum body with satin or metallic paint finish. A pre-installation frame is required. This LED downlight uses cutting edge technology which creates a higher powered downlight due to cooler operating electronics yielding 20% higher luminous flux than earlier models.

Lamp

Lamps Type	LED ARRAY
Wattage	9.2W
Output Nominal	935lm, 974lm
Color Temperature	2700K, 3000K
Color rendering	CRI 90

Optical

Beam Angle	17°/ 26°/ 50°
Lighting Type	Direct
Light Distribution	Symmetric


Physical

Material	Aluminum
Aiming	Adjustable to 20°
Weight	0.6 Lbs
Ingress Protection Rating	IP54
Finishes	Painted lacquer




Installation type	Ceiling
Environment	Indoor





Dimensions



Kap 80 Round Adjustable

NON-IC Ceiling Recessed Trimless Downlight

Electrical & Control

Input Voltage	120-277V
Control	Standard 0-10V dimming 1% linear
Driver	In Splice Box
Current	500mA

Performance

Maximum delivered output	739lm
Efficacy	80.33lm/W

Notes

Pre-installation frame has to be ordered separately

Non IC rated luminaire

Requires 11" Plenum space for installation

Splice Box has to be ordered separately.

3 Options:

- 0-10V Dimming 120V
- 0-10v Dimming 277 V
- ELV Dimming 120 V

Available in 4 different finishes: Black, White, Gold and Copper.

Maximum tilt angle for the Kap 80 (3.2") adjustable version is 20°

LED included not replaceable

Listings: UL listed, IP54

Certifications



Photometrics

For current IES files please visit
architectural.flosusa.com

Warranty


2 years from date of sale.

FLOS. USA
36 East 31st Street
Suite 402
New York N.Y. 10016
(800) 841.4011

Kap 80 Round Adjustable

NON-IC Ceiling Recessed Trimless Downlight

How to specify




How to Specify ex. 03.4538.B1.98

Part Number	CCT	CRI	Initial Lumens	Watts	Beam Angle	Finish	Variant
03.4538	3000	90	974	9.2W	19°	<div> <div></div> B1 = White <div></div> 74 = Black <div></div> GL = Gold </div>	UQ = US product. Splice Box* not included *Has to be Always supply by FLOS
03.4539	2700		935				
03.4184	3000		974		26°		
03.4185	2700		935				
03.4540	3000		974		50°		
03.4541	2700		935				

Kap 80 Round Adjustable

NON-IC Ceiling Recessed Trimless Downlight




Photometries Optic Spot



Kap 80 Round Adjustable

NON-IC Ceiling Recessed Trimless Downlight

Required Splice Box

Splice Box 14W, 20% dim, ELV, 120V. Size: 11" x 2" x 1.5"	Splice Box UL 9"x2"x1.5", With Driver Programmed to 500mA , 20W, 0-10V , Dimmable, Thermal 120V	Splice Box UL 9"x2"x1.5", With Driver Programmed to 500mA , 20W, 0-10V , Dimmable, Thermal 277V
SP14W500MA-ELV-E01	SP20W500MA-120-V01	SP20W500MA-277-V01
		

Required Accessories

Installation trimless Frame Kap80 Round

08.9102.00



Optional Accessories

Registration Tray -non electrical, place holder for non IC
new construction, Ø 4"

TRAY-0016

