




EasyKap 80 Squared Wall-Washer Airtight - IC Rated

Ceiling Recessed Trimless Downlight



Dimensions



Description

LED Downlight with minimal trim for recessed mounting into drywall or plasterboard ceilings. The Easy Kap has a die-cast aluminum body with a painted lacquer finish. This LED downlight uses cutting edge technology which creates a higher-powered downlight due to cooler operating electronics yielding 20% higher luminous flux than earlier models. Product is JA8-2019 CA Title 24 listed and CCEA Chicago Plenum.

Lamp

Lamps Type	LED ARRAY
Wattage	9.2W
Output Nominal	935lm, 974lm
Color Temperature	2700K, 3000K
Color rendering	CRI 90

Optical

Beam Angle	27°
Lighting Type	Direct
Light Distribution	Symmetric

Physical

Material	Aluminum
Aiming	Wall Washer
Weight	0.6 Lbs
Ingress Protection Rating	IP54

Finishes

Painted lacquer

☐ B1 White ☒ 74 Black ☐ GL Matt Gold ☐ BU Blue ☐ CU Copper



Certifications



Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

FLOS, USA
36 East 31st Street
Suite 402
New York N.Y. 10016
(800) 841.4011

Installation type



Ceiling Recessed

Environment

Indoor dry location

EasyKap 80 Squared Wall-Washer Airtight - IC Rated

Ceiling Recessed Trimless Downlight






Electrical & Control

Input Voltage	120-277V
Control	Standard 0-10V dimming 1% linear
Driver	Integral on housing
Current	500mA

Performance

Maximum delivered output	739lm
Efficacy	80.33 lm/W

Dimensions



14.7" x 11.1" x 4.2"

Notes

Integral LED. COB is not field replaceable.

Softening diffuser accessory provided.

IP54 - Suitable for Damp locations.

Airtight Listed housing for new construction only.

JA8-2019 CA Title 24 listed downlight, 0-10V dimmable. Not available with ELV dimming.

CCEA, Chicago Plenum standard 0-10V dimmable. Consult with factory for ELV option.

IC-rated downlight for direct insulation contact.

Certifications



Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

FLOS. USA
36 East 31st Street
Suite 402
New York N.Y. 10016
(800) 841.4011


For more information contact your representative or go to architectural.flosusa.com
©2023 Specifications and dimensions subject to change without notice. Issued 11.07.2023



EasyKap 80 Squared Wall-Washer Airtight - IC Rated

Ceiling Recessed Trimless Downlight


How to specify



How to Specify ex. 03.4198.B1.98

Part Number	CCT	CRI	Initial Lumens	Watts	Beam Angle	Finish	Variant
03.4198	3000	90	974	9,2W	27°	<div><div>B1 = White</div><div>74 = Black</div><div>GL = Gold</div><div>BL = Blue</div><div>CU = Copper</div></div>	.98 : CCEA, JA8-2019 CA Title 24 listed downlight. Housing is required.
03.4199	2700	90	935				

Photometries



EasyKap 80 Squared Wall-Washer Airtight - IC Rated

Ceiling Recessed Trimless Downlight

Required Housing and Hanger Bar

EasyKap 80 Airtight Housing for New construction, Integral 0-10V dimmable driver. Title 24 - JA8, CCEA Chicago Plenum	1 male, 1 female hanger bar Extendable from 14" to 24" centers. Qty required 2
08.7062.00.90	HOUS-HB

