

Light Shadow Fixed, Trimless 8L NON-IC

Ceiling Recessed Fixed Downlight.

Description

Flos introduces Light Shadow, a revolution in low-glare lighting. A patented and unique optical solution in this new family reaches extreme cut off angles without sacrificing efficiency. The optics have been designed exclusively by FLOS and guarantee maximum control and uniformity of the beam. Light Shadow is a downlight that can be perfectly incorporated into any architecture because of its extraordinary compact size that allows the integration even when there is a minimum space. The collection is available in 2/4/8/ or 12 spots, trimmed or trimless, and fixed or adjustable. It can be mounted in continuous row. The Light Shadow 4 spot is also available as a light element for Running Magnet 2.0.

Lamp

Lamp Type	LED
Wattage	21.6W
Initial Lumens	2384 lm / 2544 lm
Color Temperature	2700K, 3000K, 3500K* (See Notes)
Color rendering	CRI 90

Optical

Beam Angle	12°/ 23°/ 29°/ 45°
Lighting Type	Direct
Light Distribution	Symmetric

Physical

Material	Aluminum
Aiming	Fixed
Weight	1.1 Pounds
Ingress Protection Rating	IP55

Finishes:

Exterior:




Interior:

☐ White ☐ Black ☐ Steel ☐ Bronze



Dimensions



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.

Installation type	Ceiling Recessed
Environment	Indoor
Minimum Plenum height	4"
Maximum Ceiling thickness	5/8" (1/2" also available)

Light Shadow Fixed, Trimless 8L NON-IC

Ceiling Recessed Fixed Downlight.



Electrical & Control

Driver Input Voltage 120V or 277V (depending on Selected Splice Box)

Control 0-10V and ELV

Driver Integral - Splice Box

Current 900mA


Performance

up to 2120 lm / up to 2262 lm

Delivered Lumens up to 104 lm/W

Efficacy

Dimensions



Notes

Black reflector provides the greatest comfort level

Integral LED board is not field replaceable.

Pre-Installation frame required.


Splice Box is installed from below.

Non IC rated luminaire

Splice Box required has to be ordered separately always from FLOS. 3 Standard Options:

- 0-10V Dimming 120V
- 0-10V Dimming 277V
- ELV Dimming 120V

3500K and other CCT available but not cataloged. Consult factory for additional color temperatures.



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com


Warranty

2 years from date of sale.

Light Shadow Fixed, Trimless 8L NON-IC

Ceiling Recessed Fixed Downlight.

How to specify



How to Specify ex. 03.8869.14CUQ

CCT	CRI	Initial Lumens	Watts	Beam Angle	Part Number	Exterior Finish	Interior Finish	Variant
2700	90	2384	21.6	12°	03.8869	40 = White 14 = Black	Black	CUQ = US product. Splice Box* not included. *Has to be Always supply by FLOS
					03.8868		White	
					05.1241		Steel	
					05.1242		Bronze	
3000	90	2544	21.6		03.8873	40 = White 14 = Black	Black	
					03.8872		White	
					05.1246		Steel	
					05.1247		Bronze	
2700	90	2384	21.6	23°	03.9241	40 = White 14 = Black	Black	
					03.9240		White	
					05.1251		Steel	
					05.1252		Bronze	
3000	90	2544	21.6		03.9251	40 = White 14 = Black	Black	
					03.9250		White	
					05.1256		Steel	
					05.1257		Bronze	


Light Shadow Fixed, Trimless 8L NON-IC

Ceiling Recessed Fixed Downlight.

How to Specify ex. 03.9246.14CUQ

CCT	CRI	Initial Lumens	Watts	Beam Angle	Part Number	Exterior Finish	Interior Finish	Variant
2700	90	2384	21.6	29°	03.9246	40 = White 14 = Black	Black	CUQ = US product. Splice Box* not included. *Has to be Always supply by FLOS
					03.9245		White	
					05.1261		Steel	
					05.1262		Bronze	
3000	90	2544	21.6		03.9256	40 = White 14 = Black	Black	
					03.9255		White	
					05.1266		Steel	
					05.1267		Bronze	
2700	90	2384	21.6	45°	03.8367	40 = White 14 = Black	Black	
					03.8366		White	
					05.1271		Steel	
					05.1272		Bronze	
3000	90	2544	21.6		03.8371	40 = White 14 = Black	Black	
					03.8370		White	
					05.1276		Steel	
					05.1277		Bronze	

Photometrics




Light Shadow Fixed, Trimless 8L NON-IC

Ceiling Recessed Fixed Downlight.

Required Splice Box


Splice Box 25W, 1% dim, 0-10V, 120V.
Size: 9" x 3.59" x 1.25"

SP25W900MA-120-A01




Splice Box 25W, 1% dim, 0-10V, 277V.
Size: 9" x 3.59" x 1.25"

SP25W900MA-277-A01



Splice Box 30W, 20% dim, ELV, 120V.
Size: 9" x 3.59" x 1.25"

SP30W900MA-ELV-U01



Light Shadow Fixed, Trimless 8L NON-IC

Ceiling Recessed Fixed Downlight.

Required Accessories

Pre-installation trimless frame 8L 5/8" ceiling thickness


08.0512.00.90



Optional Accessories

Accessory for mounting trimless continuous line. Each accessory allows connection between two trimless pre-installation frames.

08.0052.90



Continuous Lines | How to Specify

A. Select modules sizes and pre-installation frames

1. 2 Lights module
2. 4 Lights module
3. 8 Lights Module
4. 12 Module

B. Remove the endcap of the frames

C. Use the accessory to joint the frames

Each accessory allows connection between two trimless pre-installation frames.

D. Install the continuous frame in the drywall ceiling and place the light modules

