


Light Shadow Fixed, Trim 12L NON-IC

Ceiling Recessed Fixed Downlight.



Dimensions



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.

Description

Flos introduces Light Shadow, a revolution in low-glare lighting. A patented and unique optical solution in this new family reaches extreme cut off angles without sacrificing efficiency. The optics have been designed exclusively by FLOS and guarantee maximum control and uniformity of the beam. Light Shadow is a downlight that can be perfectly incorporated into any architecture because of its extraordinary compact size that allows the integration even when there is a minimum space. The collection is available in 2/4/8/or 12 spots, trimmed or trimless, and fixed or adjustable. It can be mounted in a continuous row. The Light Shadow 4 spot is also available as a light element for Running Magnet 2.0.

Lamp

Lamp Type	LED
Wattage	32.4W
Initial Lumens	3576 lm, 3816 lm
Color Temperature	2700K, 3000K, 3500K* (See Notes)
Color rendering	CRI 90

Optical

Beam Angle	12°/ 23°/ 29°/ 45°
Lighting Type	Direct
Light Distribution	Symmetric

Physical

Material	Aluminum
Aiming	Fixed
Weight	1.3 Pounds
Ingress Protection Rating	IP55

Finishes:

Exterior:



Interior:

☐ White ☐ Black ☐ Steel ☐ Bronze



Installation type	Ceiling Recessed - Non IC
Environment	Indoor
Minimum Plenum height	4"
Maximum Ceiling thickness	0.98"

Light Shadow Fixed, Trim 12L NON-IC

Ceiling Recessed Fixed Downlight.




Electrical & Control

Driver Input Voltage	120V or 277V (depending on Selected Splice Box)
Control	0-10V
Driver	Integral - Splice Box
Current	900mA

Performance

Delivered Lumens	up to 3180 lm / up to 3394 lm
Efficacy	up to 104 lm/W

Dimensions



Notes

Black reflector provides the greatest comfort level

Integral LED board is not field replaceable.

Splice Box is installed from below.

Non IC rated luminaire

Splice Box required has to be ordered separately always from FLOS. 2 Standard Options:

- 0-10V Dimming 120V
- 0-10V Dimming 277V

3500K and other CCT available but not cataloged. Consult factory for additional color temperatures.

Certifications



Photometrics

For current IES files please visit
arch.flosusa.com


Warranty

2 years from date of sale.

Light Shadow Fixed, Trim 12L NON-IC

Ceiling Recessed Fixed Downlight.

How to specify



How to Specify ex. 03.8845.14CUQ

CCT	CRI	Initial Lumens	Watts	Beam Angle	Part Number	Exterior Finish	Interior Finish	Variant
2700	90	3576	32.4	12°	03.8845	40 = White 14 = Black	Black	CUQ = US product. Splice Box* not included. *Has to be Always supply by FLOS
					03.8844		White	
					05.1301		Steel	
					05.1302		Bronze	
3000	90	3816	32.4		03.8849	40 = White 14 = Black	Black	
					03.8848		White	
					05.1306		Steel	
					05.1307		Bronze	
2700	90	3576	32.4	23°	03.9161	40 = White 14 = Black	Black	
					03.9160		White	
					05.1311		Steel	
					05.1312		Bronze	
3000	90	3816	32.4		03.9171	40 = White 14 = Black	Black	
					03.9170		White	
					05.1316		Steel	
					05.1317		Bronze	


Light Shadow Fixed, Trim 12L NON-IC

Ceiling Recessed Fixed Downlight.

How to Specify ex. 03.9166.14CUQ

CCT	CRI	Initial Lumens	Watts	Beam Angle	Part Number	Exterior Finish	Interior Finish	Variant
2700	90	3576	32.4	29°	03.9166	40 = White 14 = Black	Black	CUQ = US product. Splice Box* not included. *Has to be Always supply by FLOS
					03.9165		White	
					05.1321		Steel	
					05.1322		Bronze	
3000	90	3816	32.4	29°	03.9176	40 = White 14 = Black	Black	
					03.9175		White	
					05.1326		Steel	
					05.1327		Bronze	
2700	90	3576	32.4	45°	03.8325	40 = White 14 = Black	Black	
					03.8324		White	
					05.1331		Steel	
					05.1332		Bronze	
3000	90	3816	32.4	45°	03.8329	40 = White 14 = Black	Black	
					03.8328		White	
					05.1336		Steel	
					05.1337		Bronze	

Photometrics




Light Shadow Fixed, Trim 12L NON-IC

Ceiling Recessed Fixed Downlight.

Required Splice Box

Splice Box 40W, 1% dim, 0-10V, 120V.
Size: 9" x 3.59" x 1.25"

SP40W900MA-120-A01



Splice Box 40W, 1% dim, 0-10V, 277V.
Size: 9" x 3.59" x 1.25"

SP40W900MA-277-A01

