




Dimensions



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.

Light Shadow Wall-Washer, Trim 4L NON-IC

Ceiling Recessed Wall-Washer Downlight.

Description

Flos introduces Light Shadow, a revolution in low-glare lighting. A patented and unique optical solution in this new family reaches extreme cut off angles without sacrificing efficiency. The optics have been designed exclusively by FLOS and guarantee maximum control and uniformity of the beam. Light Shadow is a downlight that can be perfectly incorporated into any architecture because of its extraordinary compact size that allows the integration even when there is a minimum space. The collection is available in 2/4/8/or 12 spots, trimmed or trimless, and fixed or adjustable. It can be mounted in a continuous row. The Light Shadow 4 spot is also available as a light element for Running Magnet 2.0.

Lamp

Table with 2 columns: Lamp Type, Wattage, Initial Lumens, Color Temperature, Color rendering. Values include LED, 10.8W, 1176 lm, 1280 lm, 2700K, 3000K, 3500K*, CRI 90.

Optical

Table with 2 columns: Beam Angle, Lighting Type, Light Distribution. Values include 24°, Direct, Asymmetric.

Physical

Table with 2 columns: Material, Aiming, Weight, Ingress Protection Rating, Finishes. Values include Aluminum, Fixed, Fixture: 0.75 Pounds, IP23, 40 White, 14 Black.

Table with 2 columns: Installation type, Environment, Minimum Plenum height, Maximum Ceiling thickness. Values include Ceiling Recessed - Non IC, Indoor, 6", 0.98".




Light Shadow Wall-Washer, Trim 4L NON-IC

Ceiling Recessed Wall-Washer Downlight.



Dimensions



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.

Electrical & Control

Driver Input Voltage	120V or 277V (depending on Selected Splice Box)
Control	0-10V and ELV
Driver	Integral - Splice Box
Current	900mA

Performance

Delivered Lumens	up to 873 lm / up to 945 lm
Efficacy	up to 87 lm/W

Notes

Black reflector provides the greatest comfort level

Integral LED board is not field replaceable.

Splice Box is installed from below.

Non IC rated luminaire

Splice Box required has to be ordered separately always from FLOS. 3 Standard Options:


- 0-10V Dimming 120V
- 0-10V Dimming 277V
- ELV Dimming 120V

3500K and other CCT available but not cataloged. Consult factory for additional color temperatures.

Light Shadow Wall-Washer, Trim 4L NON-IC

Ceiling Recessed Wall-Washer Downlight.

How to specify




How to Specify ex. 03.9901.40CUQ

CCT*	CRI	Initial Lumens	Delivered Lumens	Watts	Part Number	Exterior Finish	Variant
2700	90	1176	up to 873	10.8	03.9901	40 = White 14 = Black	CUQ : US product. Splice Box* not included. *Has to be Always supply by FLOS
3000	90	1280	up to 945	10.8	03.9900	40 = White 14 = Black	

* 3500K and other CCT available but not cataloged. Consult factory for additional color temperatures.

Photometrics




Light Shadow Wall-Washer, Trim 4L NON-IC

Ceiling Recessed Wall-Washer Downlight.

Required Accessories


Splice Box 25W, 1% dim, 0-10V, 120V.
Size: 9" x 3.59" x 1.25"

SP25W900MA-120-A01




Splice Box 25W, 1% dim, 0-10V, 277V.
Size: 9" x 3.59" x 1.25"

SP25W900MA-277-A01



Splice Box 20W, 20% dim, ELV, 120V.
Size: 9" x 2.22" x 1.25"



SP20W900MA-ELV-C01



Tray - Optional Accessories

Registration tray -non electrical, place
holder for non IC new construction,
6.14" x 2"

TRAY-0035



Light Shadow Wall-Washer, Trim 4L NON-IC

Ceiling Recessed Wall-Washer Downlight.

How to install

A. Select desired Part number

C. Position the fixture

B. Select required dimming protocol

In order to have a better performance position the Light fixture
0.8m-31.5inch from the wall and 0.8m-31.5inch space between two
consecutive downlights

