




EasyKap 80 (3.2") Squared Wall-Washer NON-IC

NON-IC Ceiling Recessed Trim Downlight



Dimensions



Certifications



Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

Description

LED luminaire for recessed mounting into plasterboard ceilings. The Easy Kap version has an aluminium injected body with a liquid paint, dust and/or metallic copper finish with a plastic diffuser included. It does not need a pre-installation frame. Thanks to remote-phosphor technology, the LED modules of the Phosphor LED version offer maximum quality light, the perception of objects and spaces, reaching chromatic reproduction indices of 90. The LED modules installed on the LED Array versions have cutting-edge technology that permits a lower average temperature in the electronics. Thanks to this feature, the luminaire can operate at a higher power inside the safety parameters yet still offer 20% added luminous flux.

Lamp

Lamps Type LED ARRAY

Wattage 9.2W

Output Nominal 935lm, 974lm

Color Temperature 2700K, 3000K

Color rendering CRI 90

Optical

Beam Angle 27°

Lighting Type Direct

Light Distribution Symmetric

Physical

Material Aluminum

Aiming Wall Washer

Weight 7.77 Lbs

Ingress Protection Rating IP54

Finishes Painted lacquer

☐ B1 White

☒ 74 Black

☐ GL Matt Gold




Installation type

Ceiling Recessed Non IC, 11"
recommended ceiling space to install

Environment

Indoor dry location



EasyKap 80 (3.2'') Squared Wall-Washer NON-IC

NON-IC Ceiling Recessed Trim Downlight


Electrical & Control

Input Voltage	120-277V
Control	Standard 0-10V dimming 1% linear
Driver	Driver in splice box
Current	500mA

Performance

Delivered lumens	from 565 lm up to 732 lm
Efficacy	70 lm/W

Dimensions



Notes

Pre-installation frame has to be ordered separately

Non IC rated luminaire

Ceiling Recessed Non IC, 11" recommended ceiling space to install

Driver must be ordered separately. 3 Options:

- 0-10V Dimming 120V
- 0-10v Dimming 277 V
- ELV Dimming 120 V

Available in 3 different finishes: Black, White and Gold.

Maximum tilt angle for the Kap 80 (3.2'') adjustable version is 20°

LED included not replaceable

Listings: UL listed, IP44

Certifications



Photometrics

For current IES files please visit
architectural.flosusa.com


Warranty

2 years from date of sale.

EasyKap 80 (3.2”) Squared Wall-Washer NON-IC

NON-IC Ceiling Recessed Trim Downlight


How to specify



How to Specify ex. 03.4198.B1.UQ

Table with 8 columns: Part Number, CCT, CRI, Initial Lumens, Watts, Beam Angle, Finish, Variant. It lists specifications for part numbers 03.4198 and 03.4199, including CCT (3000, 2700), CRI (90), Initial Lumens (974, 935), Watts (9.2W), Beam Angle (27°), and Finish options (B1 White, 74 Black, GL Gold). A note states 'UQ = US product. Splice Box* not included' and '*Has to be Always supply by FLOS'.

Photometries




EasyKap 80 (3.2") Squared Wall-Washer NON-IC

NON-IC Ceiling Recessed Trim Downlight

Required Splice Box


Splice Box 14W, 20% dim, ELV, 120V. Size: 9" x 2" x 1.5"

SP14W500MA-ELV-E01




Splice Box 20W, 1% dim, 0-10V, 120V. Size: 9" x 2" x 1.5"

SP20W500MA-120-V01



Splice Box 14W, 1% dim, 0-10V, 277V . Size: 9" x 2" x 1.5"

SP14W500MA-277-V01



Optional Accessories

Registration Tray -non electrical, place holder for non IC new construction, 2.95"x2.95"

TRAY-0002

