

Onninen besiūlių plieno vamzdžių asortimentas sandėlyje Kaune

Katilinėms skirta plieno markė P265GH/ P235GH TC1, standartas EN10216-2, ilgis 5-7 m.

N - naujiena

SAP kodas	Parametrai		SAP kodas	Parametrai	
AAA673	21,3x2,0 P235GH TC1		AAA680	88,9x3,2 P235/265GH TC1	
DCC439	21,3x2,6 P265GH TC1	N	AAW813	88,9x4,5 P265GH TC1	
AAA690	21,3x3,2 P235GH TC1		DCC453	88,9x5,6 P265GH TC1	N
DCC440	21,3x4,0 P265GH TC1	N	DCC454	88,9x6,3 P265GH TC1	N
AAA674	26,9x2,3 P235GH TC1		ANR239	108,0x4,0 P265GH TC1	
DCC441	26,9x2,9 P265GH TC1	N	AAA681	114,3x3,6 P235/265GH TC1	
AAW805	26,9x3,2 P235/265GH TC1		DCC455	114,3x4,5 P265GH TC1	N
DCC442	26,9x4,0 P265GH TC1	N	AAW816	114,3x5,0 P265GH TC1	
AAA675	33,7x2,6 P235/265GH TC1		DCC456	114,3x5,6 P265GH TC1	N
AAA696	33,7x3,2 P235/265GH TC1		DCC457	114,3x6,3 P265GH TC1	N
DCC443	33,7x3,6 P265GH TC1	N	ATM487	133,0x5,0 P235GH TC1	
DCC444	33,7x4,5 P265GH TC1	N	AAA682	139,7x4,0 P235GH TC1	
AAA676	42,4x2,6 P235/265GH TC1		DCC458	139,7x4,0 P265GH TC1	jau greitai N
AEV416	42,4x3,6 P235/265GH TC1		DCC459	139,7x5,0 P265GH TC1	N
DCC445	42,4x5,0 P265GH TC1	N	DCC460	139,7x6,3 P265GH TC1	N
AAA677	48,3x2,6 P235/265GH TC1		ANR240	159,0x5,0 P265GH TC1	
AAA705	48,3x3,6 P235/265GH TC1		AAA683	168,3x4,5 P235GH TC1	
DCC446	48,3x4,5 P265GH TC1	jau greitai N	DCC461	168,3x4,5 P265GH TC1	jau greitai N
DCC447	48,3x5,0 P265GH TC1	N	DCC463	168,3x6,3 P265GH TC1	N
ANR238	57,0x4,0 P265GH TC1		AAA684	219,1x6,3 P235GH TC1	
AAA678	60,3x2,9 P235/265GH TC1		DCC464	219,1x6,3 P265GH TC1	N
AAA708	60,3x3,6 P235/265GH TC1		DCC465	219,1x7,1 P265GH TC1	N
DCC448	60,3x4,0 P265GH TC1	N	CDV062	219,1x8,0 plienas A106 Gr.B	
DCC449	60,3x4,5 P265GH TC1	N	DCC466	219,1x8,0 P265GH TC1	jau greitai N
DCC450	60,3x6,3 P265GH TC1	N	AAA685	273,0x6,3 P235GH TC1	
AAA679	76,1x2,9 P235/265GH TC1		DCC467	273,0x6,3 P265GH TC1	N
CCE572	76,1x4,0 P265GH TC1		DCC468	273,0x8,0 P265GH TC1	N
DCC451	76,1x5,0 P265GH TC1	N	AAA686	323,9x7,1 P235GH TC1	
DCC452	76,1x6,3 P265GH TC1	N	AAA687	355,6x8,0 P235GH TC1	N
			AAA688	406,4x8,8 P235GH TC1	N