

What is a brand? It is the visual identity our company presents to our customers. It is our interaction with distributors, customers and fellow team members. And for more than 52 years, our brand has been simple – we are passionate about safety.

While our passion for providing the highest-quality safety solutions and emergency systems in our industry has not changed, our identity and brands have evolved.

Today, we are ECCO Safety Group® – the world's largest manufacturer of commercial and emergency vehicle warning and safety products. Our brands must reflect that level of distinction.

Branding goes far beyond a style guide of logos, colors, fonts and letterhead. The standards set forth in this book are crucial to maintaining the integrity of our brand in such a diverse organization and provide strategic guidance to all of our teams around the world.

CONTENTS

Who We Are
Our Mission & Values
Corporate Structure
Our Brands
ECCO SAFETY GROUP
Our Corporate Name
Corporate Logo
Corporate Clear Zone
Corporate Colors
Corporate Typography
, ,, , , ,
ECCO
Our Safety Solutions Brand
ECCO Logo
ECCO Colors
ECCO Clear Zone
ECCO Logo Don'ts
CODE 3
Our Emergency Systems Brand
Code 3 Logo
Code 3 Colors
Code 3 Clear Zone
Code 3 Logo Don'ts
=

ICONS

To download logos, color palettes, templates and more, look for these icons in the top corner of each page.



Click this icon to download logos and templates

Since 1972, ECCO Safety Group (ESG) has designed and manufactured some of the world's most effective and innovative visual and audible warning equipment for commercial and public safety vehicles, providing superior protection and enhanced safety both on job sites and out on the road.

Globally, ESG serves more than 3,000 OEM and private label, fleet and aftermarket customers in a range of industries. ESG has facilities in the Americas, Europe, Asia and Australia and a portfolio of the most respected brands in the industry. While we have reached global success, at our core we are committed to providing superior protection and enhanced safety to all of our customers.

OUR MISSION

PROTECTING PEOPLE WITH WORLD-LEADING INNOVATIVE SAFETY SOLUTIONS. ONE TEAM. ONE MISSION.

OUR VALUES

WE VALUE PEOPLE, CUSTOMERS, TEAMWORK, **COMPETITIVENESS, AND INNOVATION.**

ECCO Safety Group® (ESG) is the corporate name for our compilation of brands worldwide.



ECCO Safety Group® (ESG) is the corporate name for our compilation of brands worldwide.







ECCO®, Code 3® and LED Autolamps® are the primary company brands for all safety solution, emergency system and visibility solutions transitioning brands.









These historical brands will transition into the primary Safety Solutions or Emergency Systems brand. Britax and Preco should always be used alongside the ECCO brand and Hazard Systems and Premier Hazard should be used alongside the Code 3 brand until fully rationalized and/or transitioned.





This is our corporate name.

The octo-arc icon has been removed and should no longer be associated with the logo. Spacing has been increased between letters for legibility.

Use internally on company-wide documentation, and when representing multiple brands. Use sparingly on external communications, and demote to the footer when usage is required. ESG should never be used to represent our products or services.



CORPORATE LOGO

The primary corporate name, ESG, represents our organization in its entirety. It is only to be used when representing multiple brands or addressing the company internally. Do not use the ESG logo to represent a brand.

ECCO and Code 3 collateral should incorporate one of the following in the footer to represent our umbrella company (do not use the ESG logo).

For ECCO or Code 3 collateral use:
An ECCO SAFETY GROUP® Brand

For collateral representing multiple brands use:
Brands of **ECCO SAFETY GROUP®**

ESG®

1-color version

color version



white reversed



Clear zone equals a boundary the height of the "E"



To maintain the legibility and integrity of our brand logos, the minimum reproduction width for print and digital is 0.75"

CORPORATE CLEAR ZONE

To ensure the greatest visual impact, the logos must always be framed at the top and sides within a zone of "breathing" space that is equal to or greater than the height of the "E". No other graphic element or text may appear in this zone.



When placed on the same document as a primary brand, the ESG letter height should be equal to the brand letter height or smaller

10 | 2025 PUBLIC EDITION | Americas External | 11





CORPORATE COLORS

CORPORATE TYPOGRAPHY

BLUE **Primary Color**

C100 M76 Y8 K1 **R**0 **G**82 **B**153 **HEX** 0046ad PMS 293 (solid coated)

DARK BLUE Secondary Color

C100 M60 Y0 K60 **R**0 **G**46 **B**94 HEX 002e5e PMS 295 (solid coated)

Accent Color

PRIMARY / COPY FONT

Use for ESG, ECCO and Code 3 communications



Frutiger 55

abcdefghijklmnopgrstuvwxyz ABCDEFGHIJKLMNOPQRSTUVWXYZ

Frutiger 55 Bold abcdefghijklmnopqrstuvwxyz ABCDEFGHIJKLMNOPORSTUVWXYZ

SECONDARY / TITLE FONT

Use for ESG, ECCO and Code 3 communications



Eurostile Extended

abcdefghijklmnopgrstuvwxyz ABCDEFGHIJKLMNOPQRSTUVWXYZ

Eurostile Bold Extended

abcdefghijklmnopqrstuvwxyz **ABCDEFGHIJKLMNOPQRSTUVWXYZ**

DIGITAL / WEB FONT

Use for ESG, ECCO and Code 3 communications



Arial Regular

abcdefghijklmnopgrstuvwxyz ABCDEFGHIJKLMNOPQRSTUVWXYZ

Arial Bold

abcdefghijklmnopqrstuvwxyz **ABCDEFGHIJKLMNOPQRSTUVWXYZ**

12 | 2025 PUBLIC EDITION | Americas External 2025 PUBLIC EDITION | Americas External | 13





The ECCO brand should be used when representing Safety Solution applications.

Text should always align with the left side of the "E" and should not align with the octo-arc.





ECCO LOGO

The primary ECCO logo should be used in most instances when representing the commercial warning brand. The secondary ECCO logo may be used on a dark background.



full color version



white reversed

ECCO COLORS

DARK BLUE Accent Color

C100 M60 Y0 K60 R0 G46 B94 HEX 002e5e PMS 295 (solid coated) ORANGE Secondary Color

C0 M50 Y100 K0 R247 G148 B29 HEX f7941d PMS 1375 (solid coated) **BLUE Primary Color**

C100 M76 Y8 K1 R0 G82 B153 HEX 0046ad PMS 293 (solid coated)

16 | 2025 PUBLIC EDITION | Americas External | 17

ECCO CLEAR ZONE

To ensure the greatest visual impact, the logos must always be framed at the top and sides within a zone of "breathing" space that is equal to or greater than the height of the "E". No other graphic element or text may appear in this zone.



Clear zone equals a boundary the height of the "E"



When placed side by side, the ECCO and Code 3 logo font heights should be identical.



To maintain the legibility and integrity of our brand logos, the minimum reproduction width for print and digital is 1"

Logo Misuse

- stretching or changing proportions
- recreating the logo
- deviating from approved colors
- using low resolution or "non-vector" versions
- applying special effects
- rotating or angling the logo
- applying transparencies
- outlining the logo







LOGO DON'TS





Application Misuse

- invading the "breathing" space
- allowing text to overlap the logo
- decreasing opacity to create watermarks
- stepping and repeating the logo
- obscuring the logo with graphic elements
- replacing the brand name in copy with a logo
- printing on a background that detracts visibility









The Code 3 brand should be used when representing Emergency System applications.

Text should always align with the left side of the "C" and should not align with the angled strap lines.





CODE 3 LOGO

The primary Code 3 logo should be used in most instances when representing the emergency warning brand. The secondary Code 3 logo may be used on a dark background.



full color version



full color reversed



white reversed

CODE 3 COLORS

Accent Color

RED **Secondary Color**

C0 M100 Y100 K0 **R**237 **G**28 **B**36 HEX ed1c24 PMS 485 (solid coated)

BLACK Primary Color

C100 M100 Y100 K100 **R**3 **G**0 **B**0 **HEX** 030000 PMS 426 (solid coated)

CODE 3 CLEAR ZONE

To ensure the greatest visual impact, the logos must always be framed at the top and sides within a zone of "breathing" space that is equal to or greater than the height of the "C". No other graphic element or text may appear in this zone.



Clear zone equals a boundary the height of the "C"



When placed side by side, the ECCO and Code 3 logo font heights should be identical.



To maintain the legibility and integrity of our brand logos, the minimum reproduction width for print and digital is 1"

Logo Misuse

- stretching or changing proportions
- recreating the logo
- deviating from approved colors
- using low resolution or "non-vector" versions
- applying special effects
- rotating or angling the logo
- applying transparencies
- outlining the logo





LOGO DON'TS





Application Misuse

- invading the "breathing" space
- allowing text to overlap the logo
- decreasing opacity to create watermarks
- stepping and repeating the logo
- obscuring the logo with graphic elements
- replacing the brand name in copy with a logo
- printing on a background that detracts visibility









24 | 2025 PUBLIC EDITION | Americas External

AMERICAS MARKETING SUPPORT

Send marketing and branding support requests to ESG.Global/AmericasMarketingSupport and receive a response within 24 hours



Bryce Pielstick
Brand Manager
bryce.pielstick@esg.global



Jonah Teraberry Marketing Coordinator jonah.teraberry@esg.global



Ale Garcia
Digital Marketing Specialist
ale.garcia@esg.global

